

The Implementation of the caption kernel^{*}

Axel Sommerfeldt

axel.sommerfeldt@f-m.fm

2011/08/06

Abstract

The caption kernel consists of two parts – the kernel (`caption3.sty`) and the main package (`caption.sty`).

The kernel provides all the user commands and internal macros which are necessary for typesetting captions and setting parameters regarding these. While the standard \LaTeX document classes provide an internal command called `\@makecaption` and no options to control its behavior (except the vertical skips above and below the caption itself), we provide similar commands called `\caption@make` and `\caption@@make`, but with a lot of options which can be selected with `\captionsetup`. Loading the kernel part do not change the output of a $\text{\LaTeX}2\epsilon$ document – it just provides functionality which can be used by $\text{\LaTeX}2\epsilon$ packages which typesets captions, for example the `caption` and `subfig` packages.

^{*}This package has version number v1.3, last revised 2011/08/06.

Contents

1 Identification	4
2 Generic helpers	4
3 Information, Warnings, and Errors	7
4 Using the keyval package	8
5 Margin resp. width	13
6 Indentions	16
7 Styles	17
8 Formats	18
9 Label formats	19
10 Label separators	20
11 Text formats	21
12 Fonts	21
13 Justifications	23
13.1 The ragged2e package	24
14 Vertical spaces before and after captions	25
15 Positioning	25
16 Hooks	27
17 Lists	27
18 Debug option	28
19 Document classes & Babel support	28
19.1 The standard L ^A T _E X classes	28
19.2 The A _M S & SMF classes	28
19.3 The beamer class (Part one)	30
19.4 The KOMA-Script classes	31
19.5 The NTG Dutch classes	32
19.6 The thesis class	32

19.7	The frenchb Babel option	33
19.8	The frenchle/pro package	33
19.9	The hungarian and magyar Babel option	34
19.10	Unknown document class (or package)	34
20	Execution of options	35
21	Making an ‘List of’ entry	35
22	Typesetting the caption	35
23	Types & sub-types	40
24	subfig package adaptions	50

1 Identification

```
1 \NeedsTeXFormat{LaTeX2e} [1994/12/01]
2 \ProvidesPackage{caption3}[2011/08/06 v1.3 caption3 kernel (AR)]
```

2 Generic helpers

\@nameundef This is the opposite to \@namedef which is offered by the L^AT_EX kernel. We use it to remove the definition of some commands and keyval options after \begin{document} (to save T_EX memory) and to remove caption options defined with \captionsetup[⟨type⟩].

```
3 \providecommand*\@nameundef[1]{%
4   \expandafter\let\csname #1\endcsname\@undefined}
```

\l@addto@macro The L^AT_EX 2_E kernel offers the internal helper macro \g@addto@macro which globally adds tokens to existing macros, like in \AtBeginDocument. This is the same but it works local, not global (using \edef instead of \xdef).

```
5 \providecommand\l@addto@macro[2]{%
6   \begingroup
7     \toks@\expandafter{\#1\#2}%
8     \edef\@tempa{\endgroup\def\noexpand#1{\the\toks@}}%
9     \@tempa}
```

\bothIfFirst \bothIfSecond \bothIfFirst tests if the first argument is not empty, \bothIfSecond tests if the second argument is not empty. If yes both arguments get typeset, otherwise none of them.

```
10 \def\bothIfFirst#1#2{%
11   \protected@edef\caption@tempa{#1}%
12   \ifx\caption@tempa\empty \else
13     #1#2%
14   \fi}
15 \def\bothIfSecond#1#2{%
16   \protected@edef\caption@tempa{#2}%
17   \ifx\caption@tempa\empty \else
18     #1#2%
19   \fi}
```

\caption@ifinlist This helper macro checks if the first argument is in the comma separated list which is offered as second argument. So for example

```
\caption@ifinlist{frank}{axel,frank,olga,steven}{yes}{no}
```

would expand to yes.

```
20 \newcommand*\caption@ifinlist{%
21   \@expandtwoargs\caption@@ifinlist}
22 \newcommand*\caption@@ifinlist[2]{%
23   \begingroup
24   \def\@tempa##1,#1,##2\@nil{%
25     \endgroup
26     \ifx\relax##2\relax
27       \expandafter\@secondoftwo
28     \else
29       \expandafter\@firstoftwo
30     \fi}%
31   \@tempa,#2,#1,\@nil}%
```

```

\caption@ifin@list \caption@ifin@list{\langle cmd \rangle}{\langle list entry \rangle}{\langle yes \rangle}{\langle no \rangle}
32 \newcommand*\caption@ifin@list[2]{%
33   \caption@ifempty@list#1%
34   {\@secondoftwo}%
35   {\@expandtwoargs\caption@@ifinlist{\#2}{\#1}}}

\caption@g@addto@list \caption@g@addto@list{\langle cmd \rangle}{\langle list entry \rangle}
36 \newcommand*\caption@g@addto@list[2]{%
37   \caption@ifempty@list#1{\gdef#1{\#2}}{\g@addto@macro#1{,\#2}}}

\caption@l@addto@list \caption@l@addto@list{\langle cmd \rangle}{\langle list entry \rangle}
38 \newcommand*\caption@l@addto@list[2]{%
39   \caption@ifempty@list#1{\def#1{\#2}}{\l@addto@macro#1{,\#2}}}

caption@g@removefrom@list \caption@g@removefrom@list{\langle cmd \rangle}{\langle list entry \rangle}
40 \newcommand*\caption@g@removefrom@list[2]{%
41   \caption@l@removefrom@list#1{\#2}%
42   \global\let#1\@empty

caption@l@removefrom@list \caption@l@removefrom@list{\langle cmd \rangle}{\langle list entry \rangle}
Caveat: \langle cmd \rangle will be expanded during this process since \@removeelement is using \edef
to build the new list!
43 \newcommand*\caption@l@removefrom@list[2]{%
44   \caption@ifempty@list#1{\@expandtwoargs\@removeelement{\#2}\#1\@empty}

\caption@for@list \caption@for@list{\langle cmd \rangle}{code with #1}
45 \newcommand*\caption@for@list[2]{%
46   \caption@ifempty@list#1{\%%
47     \def\caption@tempb##1{\#2}%
48     \@for\caption@tempa:=#1\do{%
49       \expandafter\caption@tempb\expandafter{\expandafter\caption@tempa}}}}}

\caption@ifempty@list \caption@ifempty@list{\langle cmd \rangle}{true}{false}
50 \newcommand*\caption@ifempty@list[1]{%
51   \ifx#1\@undefined
52     \expandafter\@firstoftwo
53   \else\ifx#1\relax
54     \expandafter\expandafter\expandafter\@firstoftwo
55   \else\ifx#1\empty
56     \expandafter\expandafter\expandafter\expandafter\@firstoftwo
57     \expandafter\expandafter\expandafter\expandafter\@firstoftwo
58   \else
59     \expandafter\expandafter\expandafter\expandafter\expandafter
60     \expandafter\expandafter\expandafter\expandafter\expandafter\@secondoftwo
61   \fi\fi\fi}

\caption@setbool \ For setting and testing boolean options we offer these three helper macros:
\caption@setbool{\langle name \rangle}{\langle value \rangle}
               (with value = false/true/no/yes/off/on/0/1)
\caption@ifbool{\langle name \rangle}{\langle if-clause \rangle}{\langle else-clause \rangle}
\caption@undefbool{\langle name \rangle}

```

```

62 \newcommand*\caption@setbool[1]{%
63   \expandafter\caption@set@bool\csname caption@if#1\endcsname}%
64 \newcommand*\caption@set@bool[2]{%
65   \caption@ifinlist{#2}{1,true,yes,on}{%
66     \let#1\@firstoftwo
67   }{\caption@ifinlist{#2}{0,false,no,off}{%
68     \let#1\@secondoftwo
69   }}{%
70     \caption@Error{Undefined boolean value '#2'}%
71   }{}}
72 \newcommand*\caption@ifbool[1]{\@nameuse{caption@if#1}}
73 \newcommand*\caption@undefbool[1]{\@nameundef{caption@if#1}}


\caption@teststar \caption@teststar{\langle cmd \rangle}{\langle star arg \rangle}{\langle non-star arg \rangle}
\caption@teststar@\langle cmd \rangle{\langle star arg \rangle}{\langle non-star arg \rangle}
74 \newcommand*\caption@teststar[3]{\@ifstar{\#1{\#2}}{\#1{\#3}}}
75 \newcommand*\caption@teststar@[3]{%
76   \@ifstar{\#1{\#2}}{\caption@ifatletter{\#1{\#2}}{\#1{\#3}}}}
77 \AtBeginDocument{\let\caption@teststar@\caption@teststar}

78 \newcommand*\caption@ifatletter{%
79   \ifnum\the\catcode`@=11
80     \expandafter\@firstoftwo
81   \else
82     \expandafter\@secondoftwo
83   \fi}
84 \AtBeginDocument{\let\caption@ifatletter\@secondoftwo}

\caption@withoptargs \caption@withoptargs{\langle cmd \rangle}
85 \newcommand*\caption@withoptargs[1]{%
86   \@ifstar
87   { \def\caption@tempa{*}\caption@@withoptargs#1}%
88   { \def\caption@tempa{}\caption@@withoptargs#1}%
89 \def\caption@@withoptargs#1{%
90   \@ifnextchar[%]
91   { \caption@@@withoptargs#1}%
92   { \caption@&&@withoptargs#1}%
93 \def\caption@@@withoptargs#1[#2]{%
94   \l@addto@macro\caption@tempa{[\{#2\}]}}%
95   \caption@@withoptargs#1}
96 \def\caption@&&@withoptargs#1{%
97   \expandafter\expandafter\expandafter(\caption@tempa) }

\caption@CheckCommand \caption@CheckCommand{\langle macro \rangle}{\langle definition of macro \rangle}
\caption@IfCheckCommand checks if a command already exists, with the same definition. It can be used more-than-once to check if one of multiple definitions will finally match. (It redefines itself later on to \gobbletwo if the two commands match fine, making further checks harmless.)
\caption@IfCheckCommand{\langle true \rangle}{\langle false \rangle}
will execute the true code if one match was finally given, the false code otherwise. (It simply checks if \caption@CheckCommand is \gobbletwo and restores the starting definition of \caption@CheckCommand.)
```

```

98 \newcommand{\caption@DoCheckCommand}[2]{%
99   \begingroup
100  \let\@tempa#1%
101  #2%
102  \ifx\@tempa#1%
103  \endgroup
104  \let\caption@CheckCommand\@gobbletwo
105  \else
106  \endgroup
107  \fi}
108 \onlypreamble\caption@DoCheckCommand
109 \let\caption@CheckCommand\caption@DoCheckCommand
110 \onlypreamble\caption@CheckCommand
111 \newcommand*\caption@ifCheckCommand{%
112  \ifx\caption@CheckCommand\@gobbletwo
113  \let\caption@CheckCommand\caption@DoCheckCommand
114  \expandafter\@firstoftwo
115  \else
116  \expandafter\@secondoftwo
117  \fi}
118 \onlypreamble\caption@ifCheckCommand

\caption@AtBeginDocument
\caption@AtBeginDocument*{\langle code\rangle}
Same as \AtBeginDocument but the execution of code will be surrounded by two \PackageInfos. The starred variant causes the code to be executed after all code specified using the non-starred variant.
119 \let\caption@begindocumenthook\@empty
120 \let\caption@@begindocumenthook\@empty
121 \def\caption@AtBeginDocument{%
122  \caption@teststar\g@addto@macro
123  \caption@@begindocumenthook\caption@begindocumenthook}
124 \onlypreamble\caption@AtBeginDocument
125 \AtBeginDocument{%
126  \caption@InfoNoLine{Begin \noexpand\AtBeginDocument code}%
127  \def\caption@AtBeginDocument{%
128  \@ifstar{\g@addto@macro\caption@@begindocumenthook}\@firstofone}%
129  \caption@begindocumenthook
130  \let\caption@begindocumenthook\relax
131  \def\caption@AtBeginDocument{%
132  \@ifstar{\@firstofone\@firstofone}%
133  \caption@@begindocumenthook
134  \let\caption@@begindocumenthook\relax
135  \caption@InfoNoLine{End \noexpand\AtBeginDocument code} }

```

3 Information, Warnings, and Errors

```

\caption@Info \caption@Info{\langle message\rangle}
136 \newcommand*\caption@Info[1]{%
137  \PackageInfo{caption}{#1}}

```

```

\caption@InfoNoLine \caption@InfoNoLine{\langle message\rangle}

Note: The \@gobble at the end of the 2nd argument of \PackageInfo suppresses the line
number info. See TLC2[?], A.4.7, p885 for details.

138 \newcommand*\caption@InfoNoLine[1]{%
139   \PackageInfo{caption}{#1\@gobble}%

\caption@Warning \caption@Warning{\langle message\rangle}
140 \newcommand*\caption@Warning[1]{%
141   \caption@WarningNoLine{#1\on@line}%

\caption@WarningNoLine \caption@WarningNoLine{\langle message\rangle}
142 \newcommand*\caption@WarningNoLine[1]{%
143   \PackageWarning{caption}{#1.^.^J\caption@wh\@gobbletwo}%
144 \newcommand*\caption@wh{%
145   See the caption package documentation for explanation.}%

\caption@Error \caption@Error{\langle message\rangle}
146 \newcommand*\caption@Error[1]{%
147   \PackageError{caption}{#1}\caption@eh%
148 \newcommand*\caption@eh{%
149   If you do not understand this error, please take a closer look\MessageBreak
150   at the documentation of the 'caption' package, especially the\MessageBreak
151   section about errors.\MessageBreak\@ehc}%

\caption@KV@err
152 \let\caption@KV@err\caption@Error

```

4 Using the keyval package

We need the `keyval` package for option handling, so we load it here.

```
153 \RequirePackage{keyval}[1997/11/10]
```

```

\undefine@key \undefine@key{\langle family\rangle } {\langle key\rangle }
This helper macro is the opposite of \define@key, it removes a keyval definition.

154 \providecommand*\undefine@key[2]{%
155   \@nameundef{KV@#1@#2}\@nameundef{KV@#1@#2@default}%

\@onlypreamble@key \onlypreamble@key{\langle family\rangle } {\langle key\rangle }
Analogous to \@onlypreamble from LATEX2 $\epsilon$ .

156 \providecommand*\@preamble@keys{}%
157 \providecommand*\@onlypreamble@key[2]{\@cons\@preamble@keys{{#1}{#2}}}
158 \@onlypreamble\@onlypreamble@key
159 \@onlypreamble\@preamble@keys

160 \providecommand*\@notprerr@key[1]{\KV@err{Can be used only in preamble}%
161 \caption@AtBeginDocument*{%
162   \def\@elt#1#2{\expandafter\let\csname KV@#1@#2\endcsname\@notprerr@key}%
163   \@preamble@keys
164   \let\@elt\relax}
```

```

\DeclareCaptionOption  \DeclareCaptionOption{\langle option\rangle} [\langle default value\rangle] {\langle code\rangle}
\DeclareCaptionOption*{\langle option\rangle} [\langle default value\rangle] {\langle code\rangle}
We declare our options using these commands (instead of using \DeclareOption offered by LATEX 2E), so the keyval package is used. The starred form makes the option available during the lifetime of the current package only, so they can be used with \usepackage, but not with \captionsetup later on.
165 \newcommand*\DeclareCaptionOption{%
166   \caption@teststar\caption@declareoption\AtEndOfPackage\@gobble}%
167 \onlypreamble\DeclareCaptionOption
168 \newcommand*\caption@declareoption[2]{%
169   #1{\undefine@key{caption}{#2}}\define@key{caption}{#2}%
170 \onlypreamble\caption@declareoption

clareCaptionOptionNoValue \DeclareCaptionOptionNoValue{\langle option\rangle} {\langle code\rangle}
\DeclareCaptionOptionNoValue*{\langle option\rangle} {\langle code\rangle}
Same as \DeclareCaptionOption but issues an error if a value is given.
171 \newcommand*\DeclareCaptionOptionNoValue{%
172   \caption@teststar\caption@declareoption@novalue\AtEndOfPackage\@gobble}%
173 \onlypreamble\DeclareCaptionOptionNoValue
174 \newcommand\caption@declareoption@novalue[3]{%
175   \caption@declareoption{\#1}{\#2}[\KV@err]{%
176     \caption@option@novalue{\#2}{\#1}{\#3}}}%
177 \onlypreamble\caption@declareoption@novalue
178 \newcommand*\caption@option@novalue[2]{%
179   \ifx\KV@err\#2%
180     \expandafter\@firstofone
181   \else
182     \KV@err{No value allowed for #1}%
183   \expandafter\@gobble
184   \fi}

\ifcaptionsetup@star If the starred form of \captionsetup is used, this will be set to true. (It will be reset to false at the end of \caption@setkeys.)
185 \newif\ifcaptionsetup@star

\captionsetup \captionsetup[\langle type\rangle] {\langle keyval-list of options\rangle}
\captionsetup*[\langle type\rangle] {\langle keyval-list of options\rangle}
If the optional argument ‘type’ is specified, we simply save or append the option list, otherwise we ‘execute’ it with \setkeys. (The non-starred variant issues a warning if \langle keyval-list of options\rangle is not used later on.)
Note: The starred variant will be used inside packages automatically.
186 \newcommand*\captionsetup{%
187   \caption@teststar@\captionsetup\@gobble\@firstofone}%
188 \newcommand*\@captionsetup[1]{%
189   \captionsetup@startrue#1\captionsetup@starfalse
190   \@ifnextchar[\caption@setup@options\caption@setup}%
191 \newcommand*\caption@setup{\caption@setkeys{caption}}%
192 \def\caption@setup@options[#1]{%
193   \@bsphack

```

```

194      \ifcaptionsetup@star\captionsetup@starfalse\else\caption@addtooptlist{\#1}\fi
195      \expandafter\caption@l@addto@list\csname caption@opt@\#1\endcsname{\#2}%
196      \@esphack}

\clearcaptionsetup \clearcaptionsetup[option] {type}
\clearcaptionsetup* [option] {type}
This removes the saved option list associated with type. If option is given, only this
option will be removed from the list. (The starred variant does not issue warnings.)
Note: The starred variant will be used inside packages automatically.

197 \newcommand*\clearcaptionsetup{%
198   \caption@teststar@\@clearcaptionsetup@gobble@\firstofone}
199 \newcommand*\@clearcaptionsetup[1]{%
200   \let\caption@tempa#1%
201   \@testopt\@@clearcaptionsetup{}}
202 \def\@@clearcaptionsetup[#1]#2{%
203   \@bsphack
204   \expandafter\caption@ifempty@list\csname caption@opt@\#2\endcsname
205   {\caption@tempa{\caption@Warning{Option list '#2' undefined}}}{%
206   {\ifx,#1,%
207     \caption@clearsetup{\#2}%
208   \else
209     \caption@removefromsetup{\#1}{\#2}%
210   \fi}%
211   \@esphack}
212 \newcommand*\caption@clearsetup[1]{%
213   \caption@removefromoptlist{\#1}%
214   \nameundef{caption@opt@\#1}}
215 \newcommand*\caption@removefromsetup{%
216   \let\caption@tempa@gobble
217   \caption@removefromsetup}
218 \newcommand*\caption@removefromsetup[2]{%
219   \expandafter\let\expandafter\@tempa\csname caption@opt@\#2\endcsname
220   \expandafter\let\csname caption@opt@\#2\endcsname\@undefined
221   \def\@tempb##1=##2@\nil{##1}%
222   \edef\@tempc##1{%
223   \for\@tempa:=\@tempa\do{%
224     \edef\@tempd{\expandafter\@tempb\@tempa=\@nil}%
225     \ifx\@tempd\@tempc
226       \let\caption@tempa@gobble
227     \else
228       \expandafter\expandafter\expandafter\caption@l@addto@list
229         \expandafter\csname caption@opt@\#2\expandafter\endcsname
230         \expandafter{\@tempa}%
231     \fi}%
232   \expandafter\caption@ifempty@list\csname caption@opt@\#2\endcsname
233   {\caption@removefromoptlist{\#2}}{%
234   \caption@tempa{\caption@Warning{%
235     Option '#1' was not in list '#2'\MessageBreak}}}
235 }

\showcaptionsetup \showcaptionsetup[package] {type}
This comes for debugging issues: It shows the saved option list which is associated with
type.

```

```

236 \newcommand*\showcaptionsetup[2][\@firstofone]{%
237   \@bsphack
238   \GenericWarning{}{%
239     #1 Caption Info: Option list on '#2' \MessageBreak
240     #1 Caption Data: \@ifundefined{caption@opt@#2}{%
241       -none-%
242     }{%
243       {\expandafter\expandafter\expandafter\strip@prefix
244         \expandafter\meaning\csname caption@opt@#2\endcsname}%
245     }%
246   \@esphack}
247 \DeclareCaptionOption{options}{\caption@setoptions{\#1}}
248 \DeclareCaptionOption{options*}{\caption@setoptions*{\#1}}
\caption@setoptions \caption@setoptions*{\langle type or environment or... \rangle}
Caption options which have been saved with \captionsetup[\langle type \rangle] can be executed by using this command. It simply executes the saved option list (and clears it afterwards), if there is any. (The starred variant do not clear the option list.)
249 \newcommand*\caption@setoptions{%
250   \caption@teststar\caption@set@options\@gobble\@firstofone}
251 \newcommand*\caption@set@options[2]{%
252   \caption@Debug{options=\#2}%
253   \expandafter\let\expandafter\caption@opt\csname caption@opt@#2\endcsname
254   \ifx\caption@opt\relax \else
255     \caption@xsetup\caption@opt
256     #1{\caption@clearsetup{\#2}}% #1 = \@firstofone -or- \@gobble
257   \fi}
258 \newcommand*\caption@xsetup[1]{\expandafter\caption@setup\expandafter{\#1}}
\caption@addtooptlist \caption@addtooptlist{\langle type \rangle}
\caption@removefromoptlist{\langle type \rangle}
Adds or removes an \langle type \rangle to the list of unused caption options. Note that the catcodes of \langle type \rangle are sanitized here so removing \langle type \rangle from the list do not fail when the float package is used (since \float@getstyle gives a result which tokens have catcode 12 = “other”).
259 \newcommand*\caption@addtooptlist[1]{%
260   \@ifundefined{caption@opt@\#1@lineno}{%
261     \caption@dooptlist\caption@g@addto@list{\#1}%
262     \expandafter\xdef\csname caption@opt@\#1@lineno\endcsname{\the\inputlineno}%
263   }{}}
264 \newcommand*\caption@removefromoptlist[1]{%
265   \caption@dooptlist\caption@g@removefrom@list{\#1}%
266   \global\expandafter\let\csname caption@opt@\#1@lineno\endcsname\@undefined}
267 \newcommand*\caption@dooptlist[2]{%
268   \begingroup
269   \edef\@tempa{\#2}\@onellevel@sanitize\@tempa
270   \expandafter#1\expandafter\caption@optlist\expandafter{\@tempa}%
271   \endgroup}
272 \AtEndDocument{%
273   \caption@for@list\caption@optlist{%

```

```

274     \caption@WarningNoLine{%
275         Unused \string\captionsetup[#1]
276         on input line \csname caption@opt@\#1@lineno\endcsname}}}

\caption@setkeys \caption@setkeys[⟨package⟩]{⟨family⟩}{⟨key-values⟩}
This one simply calls \setkeys{⟨family⟩}{⟨key-values⟩} but lets the error messages
not refer to the keyval package, but to the ⟨package⟩ package instead.
277 \newcommand*\caption@setkeys{\@dblarg\caption@@setkeys}
278 \long\def\caption@@setkeys[#1]#2#3{%
279     \@bsphack
280     \expandafter\let\csname ORI@KV@err\caption@keydepth\endcsname\KV@err
281     \expandafter\let\csname ORI@KV@errx\caption@keydepth\endcsname\KV@errx
282     \expandafter\let\expandafter\KV@err\csname #1@KV@err\endcsname
283     \ifx\KV@err\relax
284         \def\KV@err##1{\PackageError{#1}{##1}{%
285             See the #1 package documentation for explanation.}}%
286     \fi
287     \let\KV@errx\KV@err
288     \edef\caption@keydepth{\caption@keydepth i}%
289     \caption@Debug{\protect\setkeys{#2}{#3}}%
290     \setkeys{#2}{#3}%
291     \edef\caption@keydepth{\expandafter\gobble\caption@keydepth}%
292     \expandafter\let\expandafter\KV@err\csname ORI@KV@err\caption@keydepth\endcsname
293     \expandafter\let\expandafter\KV@errx\csname ORI@KV@errx\caption@keydepth\endcsname
294     \ifx\caption@keydepth\empty \captionsetup@starfalse \fi
295     \@esphack}
296 \let\caption@keydepth\empty

\caption@ExecuteOptions \caption@ExecuteOptions[⟨package⟩]{⟨key-values⟩}
We execute our options using the keyval interface, so we use this one instead of
\ExecuteOptions offered by LATEX2 $\varepsilon$ .
297 \newcommand*\caption@ExecuteOptions[2]{%
298     \expandafter\@expandtwoargs\csname caption@setkeys@\#1\endcsname{#1}{#2}}%
299 \onlypreamble\caption@ExecuteOptions

\caption@ProcessOptions \caption@ProcessOptions*[⟨package⟩]
We process our options using the keyval package, so we use this one instead of
\ProcessOptions offered by LATEX2 $\varepsilon$ . The starred variant do not process the global
options. (This code was taken from the hyperref package[2] v6.74 and improved.)
300 \newcommand*\caption@ProcessOptions{%
301     \caption@teststar\caption@@ProcessOptions\@gobble\@firstofone}
302 \onlypreamble\caption@ProcessOptions

303 \newcommand\caption@@ProcessOptions[2]{%
304     \let\@tempc\relax
305     \let\caption@tempa\empty
306     #1{%
307         \ifx\@firstofone -or- \gobble
308             \for\CurrentOption:=\classoptionslist\do{%
309                 \ifundefined{KV@#2@\CurrentOption}{}{%
310                     \ifundefined{KV@#2@\CurrentOption @default}{}{%
311                         \PackageInfo{#2}{Global option '\CurrentOption' ignored}}%
312                 }%
313             }%
314     }%
315 }
```

```

311      }{%
312          \PackageInfo{\#2}{Global option '\CurrentOption' processed}%
313          \edef\caption@tempa{\caption@tempa\CurrentOption, }%
314          \@expandtwoargs\@removeelement\CurrentOption
315              \@unusedoptionlist\@unusedoptionlist
316      }%
317  }%
318 }%
319 \let\CurrentOption\@empty
320 }%
321 \caption@ExecuteOptions{\#2}{\caption@tempa\@optionlist{\@currname.\@currext}}%
322 \AtEndOfPackage{\let\@unprocessedoptions\relax}%
323 \onlypreamble\caption@@ProcessOptions

\caption@SetupOptions \caption@SetupOptions{\langle package\rangle }{\langle code\rangle }
After calling this macro \caption@ExecuteOptions and \usepackage[⟨options⟩]{⟨package⟩}
will both be mapped to ⟨code⟩ with ⟨package⟩ and ⟨options⟩ as arguments #1 and #2.
(This helps avoiding “Option clash” errors.)
324 \newcommand*\caption@packagelist{}%
325 \onlypreamble\caption@packagelist
326 \newcommand\caption@SetupOptions[2]{%
327     \@namedef{caption@setkeys@#1}##1##2{#2}%
328     \expandafter\onlypreamble\csname caption@setkeys@#1\endcsname
329     \@cons\caption@packagelist{\{#1\}}%
330 \onlypreamble\caption@SetupOptions
331 \let\caption@onefilewithoptions\onefilewithoptions
332 \def\@onefilewithoptions#1[#2]{%
333     \begingroup
334     \def\@tempa{%
335         \endgroup
336         \caption@onefilewithoptions{#1}[\{#2\}] }%
337     \def\@tempb{#1}%
338     \def\@elt##1{%
339         \def\@tempc{##1}%
340         \ifx\@tempb\@tempc
341             \def\@tempa{%
342                 \endgroup
343                 \caption@ExecuteOptions{#1}{#2}%
344                 \caption@onefilewithoptions{#1}[] }%
345         \fi}
346     \caption@packagelist
347     \@tempa}
348 \onlypreamble\caption@onefilewithoptions

```

5 Margin resp. width

\captionmargin and \captionwidth contain the extra margin resp. the total width used for captions. Please never set these values in a direct way, they are just accessible in user documents to provide compatibility to *vlx*.
Note that we can only set one value at a time, ‘margin’ or ‘width’. If \captionwidth is not zero we will take this value afterwards, otherwise \captionmargin and \captionmargin@.

```

349 \newdimen\captionmargin
350 \newdimen\captionmargin@
351 \newdimen\captionwidth

352 \DeclareCaptionOption{margin}{\setcaptionmargin{\#1}}
353 \DeclareCaptionOption{margin*}{\setcaptionmargin*{\#1}}
354 \DeclareCaptionOption{width}{\setcaptionwidth{\#1}}
355 \DeclareCaptionOption{width*}{\setcaptionwidth*{\#1}}
356 \DeclareCaptionOption{calcmargin}{\caption@setcalcmargin{\#1}}
357 \DeclareCaptionOption{calcmargin*}{\caption@setcalcmargin*{\#1}}
358 \DeclareCaptionOption{calcwidth}{\caption@setcalcwidth{\#1}}
359 \DeclareCaptionOption{calcwidth*}{\caption@setcalcwidth*{\#1}}
360 \DeclareCaptionOption{twoside}[1]{\caption@set@bool\caption@iftwoside{\#1}}
361 \DeclareCaptionOption{oneside}{\caption@set@bool\caption@iftwoside0}
362 \DeclareCaptionOption{minmargin}{\caption@setoptcmd\caption@minmargin{\#1}}
363 \DeclareCaptionOption{maxmargin}{\caption@setoptcmd\caption@maxmargin{\#1}}

\setcaptionmargin \setcaptionmargin{\langle amount\rangle}
\setcaptionmargin*{\langle amount\rangle}
Please never use this in user documents, it's just there to provide compatibility to the
caption2 package.

364 \newcommand*\setcaptionmargin{%
365   \caption@resetcalcmargin
366   \caption@setmargin}

367 \newcommand*\caption@setmargin{%
368   \caption@teststar\caption@setmargin@\gobble@\firstofone}

369 \newcommand*\caption@@setmargin[2]{%
370   #1{\captionwidth{z@}}%
371   \caption@@@setmargin#2,#2,\@nil}

372 \def\caption@@@setmargin#1,#2,#3\@nil{%
373   \setlength\captionmargin@{\#2}%
374   \setlength\captionmargin{\#1}%
375   \addtolength\captionmargin{-\captionmargin} }

\setcaptionwidth \setcaptionwidth{\langle amount\rangle}
\setcaptionwidth*{\langle amount\rangle}
Please never use this in user documents, it's just there to provide compatibility to the
caption2 package.

376 \newcommand*\setcaptionwidth{%
377   \caption@resetcalcmargin
378   \caption@setwidth}

379 \newcommand*\caption@setwidth{%
380   \caption@teststar\caption@setwidth@\gobble@\firstofone}

381 \newcommand*\caption@@setwidth[2]{%
382   #1{\captionmargin{z@}\captionmargin@\z@}%
383   \setlength\captionwidth{\#2} }%

\caption@resetcalcmargin

384 \newcommand*\caption@resetcalcmargin{%
385   \let\caption@calcmargin@hook\empty}

```

```

\caption@setcalcmargin
386 \newcommand*\caption@setcalcmargin{%
387   \caption@teststar{\caption@@setcalcmargin\caption@setmargin}%
388   \@secondoftwo\@firstoftwo}
389 \newcommand*\caption@@setcalcmargin[3]{%
390   #2{\caption@resetcalcmargin
391     \l@addto@macro\caption@calcmargin@hook{\#1{#3}}}%
392   {\l@addto@macro\caption@calcmargin@hook{\#1*{#3}}}}
\caption@setcalcwidth
393 \newcommand*\caption@setcalcwidth{%
394   \caption@teststar{\caption@@setcalcmargin\caption@setwidth}%
395   \@secondoftwo\@firstoftwo}
\caption@counter This counter numbers the captions. At the moment it will be used inside \caption@ifoddpage only.
396 \newcommand*\caption@thecounter{0}
397 \newcommand*\caption@stepcounter{%
398   \tempcnta\caption@thecounter
399   \advance\tempcnta\@ne
400   \xdef\caption@thecounter{\the\tempcnta}}
\caption@newlabel This command is a modified version of \newlabel from LATEX2e. It will be written to the .aux file to pass label information from one run to another. (We use it inside \caption@ifoddpage and \caption@ragged.)
401 \newcommand*\caption@newlabel{\@newl@bel{caption@r}}
\caption@thepage This command is a modified version of \thepage from LATEX2e. It will be used inside \caption@ifoddpage only.
402 \newcommand*\caption@thepage{\the\c@page}
\caption@label This command is a modified version of \label from LATEX2e. It will be used inside \caption@ifoddpage and \FP@helpNote.
403 \newcommand*\caption@label[1]{%
404   \caption@@label
405   \protected@write\auxout{\let\caption@thepage\relax}%
406   {\string\caption@newlabel{\#1}{\caption@thepage}}}
407 \newcommand*\caption@@label{%
408   \global\let\caption@@label\relax
409   \protected@write\auxout{}{%
410     {\string\providecommand*\string\caption@newlabel[2]{}}
\caption@pageref This command is a modified version of \pageref from LATEX2e. It will be used inside \caption@ifoddpage and \FP@helpNote.
411 \newcommand*\caption@pageref[1]{%
412   \expandafter\ifx\csname caption@r@\#1\endcsname\relax
413   \G@refundefinedtrue % => 'There are undefined references.'
414   \@latex@warning{Reference '#1' on page \thepage \space undefined}%
415   \else
416   \expandafter\let\expandafter\caption@thepage\csname caption@r@\#1\endcsname
417   \fi}

```

```

\caption@ifoddpage At the moment this macro uses an own label...ref mechanism, but an alternative implementation method would be using the refcount package[3] and \ifodd\getpagerefnumber{...}.  

Note: This macro re-defines itself so the .aux file will only be used once per group.

418 \newcommand*\caption@ifoddpage{%
419   \caption@iftwoside{%
420     \caption@label\caption@thecounter
421     \caption@pageref\caption@thecounter
422     \ifodd\caption@thepage
423       \let\caption@ifoddpage\@firstoftwo
424     \else
425       \let\caption@ifoddpage\@secondoftwo
426     \fi
427   }{\let\caption@ifoddpage\@firstoftwo}%
428 \caption@ifoddpage}

\caption@setoptcmd \caption@setoptcmd{\{cmd\}}{\{off-or-value\}}
429 \newcommand*\caption@setoptcmd[2]{%
430   \caption@ifinlist{\#2}{0, false, no, off}{\let#1\@undefined}{\def#1{\#2}}}

```

6 Indentions

```

\caption@indent These are the indentions we support.
\caption@parindent
\caption@hangindent

431 \newdimen\caption@indent
432 \newdimen\caption@parindent
433 \newdimen\caption@hangindent

434 \DeclareCaptionOption{indent}[\leftmargini]{% obsolete!
435   \setlength\caption@indent{\#1}}
436 \DeclareCaptionOption{indention}[\leftmargini]{%
437   \setlength\caption@indent{\#1}}
438 \DeclareCaptionOption{parindent}{%
439   \setlength\caption@parindent{\#1}}
440 \DeclareCaptionOption{hangindent}{%
441   \setlength\caption@hangindent{\#1}}
442 \DeclareCaptionOption{parskip}{%
443   \l@addto@macro\caption@par{\setlength{parskip}{\#1}}}

```

There is an option clash between the KOMA-Script document classes and the caption kernel, both define the options `parindent` and `parskip` but with different meaning. Furthermore the ones defined by the caption kernel take a value as parameter but the KOMA-Script ones do not. So we need special versions of the options `parindent` and `parskip` here which determine if a value is given (and therefore should be treated as our option) or not (and therefore should be ignored by us).¹

```

444 \providetcommand*\caption@ifkomaclass{%
445   \@ifundefined{scr@caption}\@gobble\@firstofone}
446 \@onlypreamble\caption@ifkomaclass

447 \caption@ifkomaclass{%

```

¹This problem was completely solved due a change of `\caption@ProcessOptions` in the caption kernel *v1.0h*, but we still need this workaround since these options would otherwise still collide with the current version 1.3 of the `subfig` package (Sigh!)

```

448 \let\caption@KV@parindent\KV@caption@parindent
449 \DeclareCaptionOption{parindent}[]{%
450   \ifx,#1,%
451     \caption@Debug{Option 'parindent' ignored}%
452   \else
453     \caption@KV@parindent{#1}%
454   \fi}%
455 \let\caption@KV@parskip\KV@caption@parskip
456 \DeclareCaptionOption{parskip}[]{%
457   \ifx,#1,%
458     \caption@Debug{Option 'parskip' ignored}%
459   \else
460     \caption@KV@parskip{#1}%
461   \fi}%
462 }

```

7 Styles

```

\DeclareCaptionStyle \DeclareCaptionStyle{\langle name\rangle}[\langle single-line-list-of-KV\rangle]{\langle list-of-KV\rangle}
463 \newcommand*\DeclareCaptionStyle[1]{%
464   \atopt{\caption@declarestyle{#1}}{}%
465 \onlypreamble\DeclareCaptionStyle
466 \def\caption@declarestyle#1[#2]#3{%
467   \global\@namedef{caption@sls@#1}{#2}%
468   \global\@namedef{caption@sty@#1}{#3}%
469 \onlypreamble\caption@declarestyle
470 \DeclareCaptionOption{style}{\caption@setstyle{#1}}
471 \DeclareCaptionOption{style*}{\caption@setstyle*{#1}}
472 \DeclareCaptionOption{singlelinecheck}[1]{\caption@set@bool\caption@ifslc{#1}}
473 \DeclareCaptionOption{slc}[1]{\KV@caption@singlelinecheck{#1}}

```

```
\caption@setstyle \caption@setstyle{\langle name\rangle}
\caption@setstyle*{\langle name\rangle}
```

Selecting a caption style means saving the additional *single-line-list-of-KV* (this will be done by `\caption@sls`), resetting the caption options to the base ones (this will be done using `\caption@resetstyle`) and executing the *list-of-KV* options (this will be done using `\caption@setup`).

The starred version will give no error message if the given style is not defined.

```

474 \newcommand*\caption@setstyle{%
475   \caption@teststar\caption@@setstyle@gobble@\firstofone}
476 \newcommand*\caption@@setstyle[2]{%
477   \ifundefined{caption@sty@#2}%
478     {\#1{\caption@Error{Undefined style '#2'}}}%
479     {\expandafter\let\expandafter\caption@sty\csname caption@sty@#2\endcsname
480      \ifx\caption@setstyle@flag@\undefined
481        \let\caption@setstyle@flag\relax
482        \caption@resetstyle
483        \caption@xsetup\caption@sty
484        \let\caption@setstyle@flag@\undefined
485      \else

```

```

486      \caption@xsetup\caption@sty
487      \fi
488      \expandafter\let\expandafter\caption@sls\csname caption@sls@\#2\endcsname
489      \expandafter\caption@l@addto@list\expandafter\caption@opt@singleline
490      \expandafter{\caption@sls}}}

```

\caption@resetstyle This resets (nearly) all caption options to the base ones. *Note that this does not touch the skips and the positioning!*

```

491 \newcommand*\caption@resetstyle{%
492   \caption@setup{%
493     format=plain,labelformat=default,labelsep=colon,textformat=simple,%
494     justification=justified,font=,size=,labelfont=,textfont=,%
495     margin=0pt,minmargin=0,maxmargin=0,%
496     indent=0pt,parindent=0pt,hangindent=0pt,%
497     slc,rule,strut}%
498   \caption@clearsetup{singleline}}

```

Currently there are two pre-defined styles, called ‘base’ & ‘default’. The first one is a perfect match to the behavior of \makecaption offered by the standard L^AT_EX document classes (and was called ‘default’ in the caption kernel *v1.0*), the second one matches the document class actually used.

```

499 \DeclareCaptionStyle{base}[indent=0pt, justification=centering]{}
500 \DeclareCaptionStyle{default}[indent=0pt, justification=centering]{%
501   format=default,labelsep=default,textformat=default,%
502   justification=default,font=default,labelfont=default,textfont=default}

```

8 Formats

\DeclareCaptionFormat \DeclareCaptionFormat {*name*} {*code with #1, #2, and #3*}
\DeclareCaptionFormat* {*name*} {*code with #1, #2, and #3*}

The starred form causes the code being typeset in vertical (instead of horizontal) mode, but does not support the *indentation*= option.

```

503 \newcommand*\DeclareCaptionFormat{%
504   \caption@teststar\caption@declareformat\@gobble\@firstofone}%
505 \onlypreamble\DeclareCaptionFormat
506 \newcommand*\caption@declareformat[2]{%
507   \dblarg{\caption@@declareformat#1{#2}}}
508 \onlypreamble\caption@declareformat
509 \long\def\caption@@declareformat#1#2[#3]#4{%
510   \global\expandafter\let\csname caption@ifh@\#2\endcsname#1%
511   \global\long\@namedef{caption@slfmt@\#2##1##2##3{#3}}%
512   \global\long\@namedef{caption@fmt@\#2##1##2##3{#4}}}
513 \onlypreamble\caption@@declareformat
514 \DeclareCaptionOption{format}{\caption@setformat{#1}}

```

\caption@setformat \caption@setformat {*name*}
Selecting a caption format simply means saving the code (in \caption@fmt) and if the code should be used in horizontal or vertical mode (\caption@ifh).

```

515 \newcommand*\caption@setformat[1]{%
516   \ifundefined{caption@fmt@\#1}%

```

```

517   {\caption@Error{Undefined format '#1'}}%
518   {\expandafter\let\expandafter\caption@ifh\csname caption@ifh@#1\endcsname
519     \expandafter\let\expandafter\caption@slfmt\csname caption@slfmt@#1\endcsname
520     \expandafter\let\expandafter\caption@fmt\csname caption@fmt@#1\endcsname}%
clareCaptionDefaultFormat
521 \newcommand*\DeclareCaptionDefaultFormat[1]{%
522   \expandafter\def\expandafter\caption@fmt@default\expandafter
523     {\csname caption@fmt@#1\endcsname}%
524   \expandafter\def\expandafter\caption@slfmt@default\expandafter
525     {\csname caption@slfmt@#1\endcsname}%
526   \expandafter\def\expandafter\caption@ifh@default\expandafter
527     {\csname caption@ifh@#1\endcsname}%
528 \onlypreamble\DeclareCaptionDefaultFormat

```

There are two pre-defined formats, called ‘plain’ and ‘hang’.

```

529 \DeclareCaptionFormat{plain}{#1#2#3\par}
530 \DeclareCaptionFormat{hang}{#1#2#3\par}%
531   \caption@ifin@list\caption@lsepclist\caption@lsepname
532   {\caption@Error{%
533     The option 'labelsep=\caption@lsepname' does not work\MessageBreak
534     with 'format=hang'}}%
535   {\@hangfrom{#1#2}%
536     \advance\caption@parindent\hangindent
537     \advance\caption@hangindent\hangindent
538     \caption@@par#3\par}
‘default’ usually maps to ‘plain’.
539 \DeclareCaptionDefaultFormat{plain}

```

9 Label formats

```

DeclareCaptionLabelFormat \DeclareCaptionLabelFormat{\<name>} {\<code with #1 and #2>}
540 \newcommand*\DeclareCaptionLabelFormat[2]{%
541   \global\@namedef{caption@lfmt@#1}##1##2{#2}}
542 \onlypreamble\DeclareCaptionLabelFormat
543 \DeclareCaptionOption{labelformat}{\caption@setlabelformat{#1}}
\caption@setlabelformat \caption@setlabelformat{\<name>}
Selecting a caption label format simply means saving the code (in \caption@lfmt).
544 \newcommand*\caption@setlabelformat[1]{%
545   \@ifundefined{caption@lfmt@#1}%
546     {\caption@Error{Undefined label format '#1'}}%
547     {\expandafter\let\expandafter\caption@lfmt\csname caption@lfmt@#1\endcsname}%

```

There are four pre-defined label formats, called ‘empty’, ‘simple’, ‘parens’, and ‘brace’.

```

548 \DeclareCaptionLabelFormat{empty} {}
549 \DeclareCaptionLabelFormat{simple}{\bothIfFirst{#1}{\nobreakspace}#2}
550 \DeclareCaptionLabelFormat{parens}{\bothIfFirst{#1}{\nobreakspace}(#2)}
551 \DeclareCaptionLabelFormat{brace}{\bothIfFirst{#1}{\nobreakspace}\#2}
‘default’ usually maps to ‘simple’.
552 \def\caption@lfmt@default{\caption@lfmt@simple}

```

10 Label separators

```
lareCaptionLabelSeparator \DeclareCaptionLabelSeparator{\langle name\rangle}{\langle code\rangle}
\DeclareCaptionLabelSeparator*{\langle name\rangle}{\langle code\rangle}
The starred form causes the label separator to be typeset without using \captionlabelfont.
553 \newcommand\DeclareCaptionLabelSeparator{%
554   \caption@teststar\caption@declarelabelseparator@gobble@\firstofone}%
555 \onlypreamble\DeclareCaptionLabelSeparator

556 \newcommand\caption@declarelabelseparator[3]{%
557   \global\@namedef{caption@iflf@#2}{#1}%
558   \global\long\@namedef{caption@lsep@#2}{#3}%
559   \caption@declarelabelseparator{#2}#3\\@nil}%
560 \onlypreamble\caption@declarelabelseparator

561 \long\def\caption@declarelabelseparator#1#2\\#3@nil{%
562   \def\@tempa{#3}\ifx\@tempa\empty\else
563     \caption@g@addto@list\caption@lsepclist{#1}%
564   \fi}
565 \onlypreamble\caption@declarelabelseparator

566 \DeclareCaptionOption{labelsep}{\caption@setlabelseparator{#1}}
567 \DeclareCaptionOption{labelseparator}{\caption@setlabelseparator{#1}}}

caption@setlabelseparator \caption@setlabelseparator{\langle name\rangle}
Selecting a caption label separator simply means saving the code (in \caption@lsep).
568 \newcommand*\caption@setlabelseparator[1]{%
569   \@ifundefined{caption@lsep@#1}{%
570     {\caption@Error{Undefined label separator '#1'}}}%
571   {\edef\caption@lsepname{#1}%
572     \expandafter\let\expandafter\caption@iflf\csname caption@iflf@#1\endcsname
573     \expandafter\let\expandafter\caption@lsep\csname caption@lsep@#1\endcsname}{}}

There are seven pre-defined label separators, called ‘none’, ‘colon’, ‘period’, ‘space’, ‘quad’, ‘newline’, and ‘endash’.
574 \DeclareCaptionLabelSeparator{none}{}
575 \DeclareCaptionLabelSeparator{colon}{: }
576 \DeclareCaptionLabelSeparator{period}{. }
577 \DeclareCaptionLabelSeparator{space}{ }
578 \DeclareCaptionLabelSeparator*{quad}{\quad}
579 \DeclareCaptionLabelSeparator*{newline}{\\}
580 \DeclareCaptionLabelSeparator*{endash}{\space\textrightarrow\space}

aption@setdefaultlabelsep
581 \newcommand*\caption@setdefaultlabelsep[1]{%
582   \ifx\caption@lsep\caption@lsep@default
583     \caption@set@default@labelsep{#1}%
584     \caption@setlabelseparator{default}%
585   \else
586     \caption@set@default@labelsep{#1}%
587   \fi}

588 \newcommand*\caption@set@default@labelsep[1]{%
589   \def\caption@lsep@default{\@nameuse{caption@lsep@#1}}%
590   \def\caption@iflf@default{\@nameuse{caption@iflf@#1}}} }
```

‘default’ usually maps to ‘colon’.

```
591 \caption@set@default@labelsep{colon}
```

11 Text formats

```
\DeclareCaptionTextFormat  \DeclareCaptionTextFormat {\langle name\rangle } {\langle code with #1\rangle }
592 \newcommand*\DeclareCaptionTextFormat [2] {%
593   \global\long\@namedef{caption@tfmt@#1}{\#1{#2}}%
594 \onlypreamble\DeclareCaptionTextFormat

595 \DeclareCaptionOption{textformat}{\caption@settextformat{\#1}}
596 \DeclareCaptionOption{strut}[1]{\caption@set@bool\caption@ifstrut{\#1} }

\caption@settextformat \caption@settextformat {\langle name\rangle }
Selecting a caption text format simply means saving the code (in \caption@tfmt).

597 \newcommand*\caption@settextformat [1] {%
598   \@ifundefined{caption@tfmt@#1}{%
599     {\caption@Error{Undefined text format '#1'}}}%
600   {\expandafter\let\expandafter\caption@tfmt\csname caption@tfmt@#1\endcsname}}
```

There are two pre-defined text formats, called ‘simple’ and ‘period’.

```
601 \DeclareCaptionTextFormat{simple}{#1}
602 \DeclareCaptionTextFormat{period}{#1.}

‘default’ usually maps to ‘simple’.
```

```
603 \def\caption@tfmt@default{\caption@tfmt@simple}
```

12 Fonts

```
\DeclareCaptionFont \DeclareCaptionFont {\langle name\rangle } {\langle code\rangle }
604 \newcommand*\DeclareCaptionFont [2] {%
605   \define@key{caption@fnt}{#1}[] {\l@addto@macro\caption@fnt{\#2}}%
606 \onlypreamble\DeclareCaptionFont

\DeclareCaptionDefaultFont \DeclareCaptionDefaultFont {\langle name\rangle } {\langle code\rangle }
607 \newcommand*\DeclareCaptionDefaultFont [2] {%
608   \global\@namedef{caption#1@default}{#2}%
609 \onlypreamble\DeclareCaptionDefaultFont

610 \DeclareCaptionOption{font}{\caption@setfont{font}{#1}}
611 \DeclareCaptionOption{font+}{\caption@addtofont{font}{#1}}
612 \DeclareCaptionDefaultFont{font}{}

613 \DeclareCaptionOption{labelfont}{\caption@setfont{labelfont}{#1}}
614 \DeclareCaptionOption{labelfont+}{\caption@addtofont{labelfont}{#1}}
615 \DeclareCaptionDefaultFont{labelfont}{}

616 \DeclareCaptionOption{textfont}{\caption@setfont{textfont}{#1}}
617 \DeclareCaptionOption{textfont+}{\caption@addtofont{textfont}{#1}}
618 \DeclareCaptionDefaultFont{textfont}{}
```

```

\caption@setfont  \caption@setfont {\langle name\rangle } {\langle keyval-list of names\rangle }
Selecting a caption font means saving all the code snippets in \caption{\langle name\rangle }.
619 \newcommand*\caption@setfont [1] {%
620   \expandafter\let\csname caption#1\endcsname\empty
621   \caption@addtofont{\#1} }

\caption@addtofont \caption@addtofont {\langle name\rangle } {\langle keyval-list of names\rangle }
Like \caption@setfont, but adds the code snippets to \caption{\langle name\rangle }.
Because we use \setkeys recursive here we need to do this inside an extra group.
622 \newcommand*\caption@addtofont [2] {%
623   \begingroup
624     \expandafter\let\expandafter\caption@fnt\csname caption#1\endcsname
625     \define@key{caption@fnt}{default}{}{%
626       \l@addto@macro\caption@fnt{\csname caption#1@default\endcsname}{}%
627       \caption@setkeys[caption]{caption@fnt}{\#2}%
628       \global\let\caption@tempa\caption@fnt
629   \endgroup
630   \expandafter\let\csname caption#1\endcsname\caption@tempa}

\caption@font  \caption@font {\langle keyval-list of names\rangle }
\caption@font* {\langle keyval-code\rangle }
Sets the given font, e.g. \caption@font{small,it} is equivalent to \small\itshape.
631 \newcommand*\caption@font{%
632   \caption@teststar\caption@font@\firstofone
633   {\caption@setkeys[caption]{caption@fnt}}}
634 \newcommand*\caption@@font [2] {%
635   \begingroup
636   \def\caption@fnt{\endgroup}%
637   #1{#2}%
638   \caption@fnt}

These are the pre-defined font code snippets.
639 \DeclareCaptionFont{normalcolor}{\normalcolor}
640 \DeclareCaptionFont{color}{\color{\#1}}
641 \DeclareCaptionFont{normalfont}{\normalfont}
642 \DeclareCaptionFont{up}{\upshape}
643 \DeclareCaptionFont{it}{\itshape}
644 \DeclareCaptionFont{sl}{\slshape}
645 \DeclareCaptionFont{sc}{\scshape}
646 \DeclareCaptionFont{md}{\mdseries}
647 \DeclareCaptionFont{bf}{\bfseries}
648 \DeclareCaptionFont{rm}{\rmfamily}
649 \DeclareCaptionFont{sf}{\sffamily}
650 \DeclareCaptionFont{tt}{\ttfamily}
651 \DeclareCaptionFont{scriptsize}{\scriptsize}
652 \DeclareCaptionFont{footnotesize}{\footnotesize}
653 \DeclareCaptionFont{small}{\small}
654 \DeclareCaptionFont{normalsize}{\normalsize}
655 \DeclareCaptionFont{large}{\large}
656 \DeclareCaptionFont{Large}{\Large}
657 \DeclareCaptionFont{sansmath}{\sansmath}

```

```

658 \DeclareCaptionFont{singlespacing}{%
659   \@ifundefined{setspace@singlespace}{}{%
660     \setstretch\setspace@singlespace}}% normally 1
661 \DeclareCaptionFont{onehalfspacing}{\onehalfspacing}
662 \DeclareCaptionFont{doublespacing}{\doublespacing}
663 \DeclareCaptionFont{stretch}{\setstretch{\#1}}
664 %\DeclareCaptionFont{normal}{%
665 %  \caption@font{normalcolor,normalfont,normalsize,singlespacing}
666 \DeclareCaptionFont{normal}{%
667   \caption@font*{%
668     \KV@caption@fnt@normalcolor\@unused
669     \KV@caption@fnt@normalfont\@unused
670     \KV@caption@fnt@normalsize\@unused
671     \KV@caption@fnt@singlespacing\@unused} }

```

The old versions *v1.x* of the `caption` kernel offered this command to setup the font size used for captions. We still do so old documents will work fine.

```

672 \DeclareCaptionOption{size}{\caption@setfont{size}{\#1}}
673 \DeclareCaptionDefaultFont{size}{}

```

13 Justifications

```

clareCaptionJustification \DeclareCaptionJustification{\langle name\rangle}{\langle code\rangle}
674 \newcommand*\DeclareCaptionJustification[2]{%
675   \global\@namedef{caption@hj@\#1}{\#2}% for compatibility to v1.0
676   \DeclareCaptionFont{\#1}{\#2}}
677 \onlypreamble\DeclareCaptionJustification

aptionDefaultJustification \DeclareCaptionDefaultJustification{\langle code\rangle}
678 \newcommand*\DeclareCaptionDefaultJustification[1]{%
679   \global\@namedef{caption@hj@default}{\#1}% for compatibility to v1.0
680   \DeclareCaptionDefaultFont{@hj}{\#1}}
681 \onlypreamble\DeclareCaptionDefaultJustification

682 \DeclareCaptionOption{justification}{\caption@setjustification{\#1}}
683 \DeclareCaptionDefaultJustification{ }

\caption@setjustification \caption@setjustification{\langle name\rangle}
Selecting a caption justification simply means saving the code (in \caption@hj).
684 \newcommand*\caption@setjustification{\caption@setfont{@hj}}
```

These are the pre-defined justification code snippets.

```

685 \DeclareCaptionJustification{justified}{}
686 \DeclareCaptionJustification{centering}{\centering}
687 \DeclareCaptionJustification{centerfirst}{\centerfirst}
688 \DeclareCaptionJustification{centerlast}{\centerlast}
689 \DeclareCaptionJustification{raggedleft}{\raggedleft}
690 \DeclareCaptionJustification{raggedright}{\raggedright}
```

```
\centerfirst Please blame Frank Mittelbach for the code of \centerfirst :-
691 \providecommand\centerfirst{%
692   \let\\@centercr
```

```

693 \edef\caption@normaladjust{%
694   \leftskip\the\leftskip
695   \rightskip\the\rightskip
696   \parfillskip\the\parfillskip\relax}%
697 \leftskip\z@\@plus -1fil%
698 \rightskip\z@\@plus 1fil%
699 \parfillskip\z@skip
700 \noindent\hspace{\z@\@plus 2fil}%
701 \setpar{\@par\@restpar\caption@normaladjust} }

```

\centerlast This is based on code from Anne Brüggemann-Klein[1]

```

702 \providecommand\centerlast{%
703   \let\\@centercr
704   \leftskip\z@\@plus 1fil%
705   \rightskip\z@\@plus -1fil%
706   \parfillskip\z@\@plus 2fil\relax}

```

13.1 The ragged2e package

We also support the upper-case commands offered by the `ragged2e` package. Note that these just map to their lower-case variants if the `ragged2e` package is not available.

```

707 \DeclareCaptionJustification{Centering}{%
708   \caption@ragged\Centering\centering}
709 \DeclareCaptionJustification{RaggedLeft}{%
710   \caption@ragged\RaggedLeft\raggedleft}
711 \DeclareCaptionJustification{RaggedRight}{%
712   \caption@ragged\RaggedRight\raggedright}

```

\caption@ragged \caption@ragged will be basically defined as

```

\AtBeginDocument{\IfFileExists{ragged2e.sty}{%
  \RequirePackage{ragged2e}\let\caption@ragged\@firstoftwo}%
  {\let\caption@ragged\@secondoftwo}}

```

but with an additional warning if the `ragged2e` package is not loaded (yet). (This warning will be type out only one time per option, that's why we need the `\caption\string#1` stuff.) Furthermore we load the `ragged2e` package, if needed and available.

```

713 \newcommand*\caption@ragged{%
714   \caption@Debug{We need ragged2e}%
715   \protected@write\@auxout{}{\string\caption@newlabel{ragged2e}{} }%
716   \global\let\caption@ragged\caption@ragged
717   \caption@ragged}

718 \caption@AtBeginDocument{%
719   \@ifundefined{caption@r@ragged2e}{%
720     \newcommand*\caption@{%
721       \caption@Warning{%
722         'ragged2e' support has been changed.\MessageBreak
723         Rerun to get captions right}%
724       \global\let\caption@ragged\@secondoftwo % suppress further warnings
725       \caption@ragged}%
726   }{%
727     \caption@Debug{We load ragged2e}%
728     \IfFileExists{ragged2e.sty}{%

```

```

729     \RequirePackage{ragged2e}%
730     \let\caption@@ragged\@firstoftwo
731 }{%
732     \newcommand*\caption@@ragged[2]{%
733         \@ifundefined{caption\string#1}{%
734             \caption@Warning{%
735                 'ragged2e' package not loaded, therefore\MessageBreak
736                 substituting \string#2 for \string#1\MessageBreak}%
737             \global\@namedef{caption\string#1}{}%
738         }%
739     }%
740 }

```

14 Vertical spaces before and after captions

\abovecaptionskip
\belowcaptionskip

Usually these skips are defined within the document class, but some document classes don't do so.

```

741 \@ifundefined{abovecaptionskip}{%
742     \newlength\abovecaptionskip\setlength\abovecaptionskip{10\p@}{}%
743 \@ifundefined{belowcaptionskip}{%
744     \newlength\belowcaptionskip\setlength\belowcaptionskip{0\p@}{}%
745 \DeclareCaptionOption{aboveskip}{\setlength\abovecaptionskip{\#1}}%
746 \DeclareCaptionOption{belowskip}{\setlength\belowcaptionskip{\#1}}%
747 \DeclareCaptionOption{skip}{\setlength\abovecaptionskip{\#1}}%

```

\caption@rule \caption@rule

Draws an invisible rule to adjust the “skip” setting.

```

748 \newcommand*\caption@rule{\caption@ifrule\caption@hrule\relax}
749 \newcommand*\caption@hrule{\hrule\@height\z@}
750 \DeclareCaptionOption{rule}[1]{\caption@set@bool\caption@ifrule{\#1}}

```

15 Positioning

These macros handle the right position of the caption. Note that the position is actually *not* controlled by the `caption3` kernel options, but by the user (or a specific package like the `float` package) instead. The user can put the `\caption` command wherever he likes! So this stuff is only to give us a *hint* where to put the right skips, the user usually has to take care for himself that this hint actually matches the right position.

```

751 \DeclareCaptionOption{position}{\caption@setposition{\#1}}
\caption@setposition \caption@setposition{<position>}
Selecting the caption position means that we put \caption@position to the right value. Please do not use the internal macro \caption@position in your own package or document, but use the wrapper macro \caption@iftop instead.
752 \newcommand*\caption@setposition[1]{%
753     \caption@ifinlist{\#1}{d,default}{%
754         \let\caption@position\caption@defaultpos
755     }{\caption@ifinlist{\#1}{t,top,above}{%

```

```

756     \let\caption@position\@firstoftwo
757 }{\caption@ifinlist{#1}{b,bottom,below}{%
758     \let\caption@position\@secondoftwo
759 }{\caption@ifinlist{#1}{a,auto}{%
760     \let\caption@position\@undefined
761 }{%
762     \caption@Error{Undefined position '#1'}%
763 }}}}}}

```

\caption@defaultpos The default ‘position’ is ‘auto’, this means that the `caption` kernel will try to guess the current position of the caption. (But in many cases, for example in `longtables`, this is doomed to fail!) The setting ‘bottom’ corresponds to the `\@makecaption` implementation in the standard L^AT_EX document classes, but ‘auto’ should give better results in most cases.

```

764 \% \caption@setdefaultpos{a} % default = auto
765 \let\caption@defaultpos\@undefined

```

\caption@iftop \caption@iftop{*true-code*} {*false-code*}
(If the `position=` is set to `auto` we assume a bottom position here.)

```

766 \newcommand*\caption@iftop{%
767   \ifx\caption@position\@undefined
768     \let\caption@position\@secondoftwo
769   = \caption@setposition b%
770   \fi
771   \caption@position}

```

\caption@fixposition \caption@fixposition
This macro checks if the ‘position’ is set to ‘auto’. If yes, `\caption@autoposition` will be called to set `\caption@position` to a proper value we can actually use.

```

772 \newcommand*\caption@fixposition{%
773   \ifx\caption@position\@undefined
774     \caption@autoposition
775   \fi}

```

\caption@autoposition \caption@autoposition
We guess the current position of the caption by checking `\prevdepth`. A different solution would be setting the `\spacefactor` to something not much less than 1000 (for example 994) in `\caption@start` and checking this value here by `\ifnum\spacefactor=994`. (It’s implemented in the `threeparttable` package[4] this way.) Another idea would be checking `\@ifminipage`, but since some packages typeset the caption within a simple `\vbox` this does not seem to be a good one.

```

776 \newcommand*\caption@autoposition{%
777   \ifvmode
778     \edef\caption@tempa{\the\prevdepth}%
779     \caption@Debug{\protect\prevdepth=\caption@tempa}%
780     \ifdim\prevdepth>-\p@
781       \let\caption@position\@secondoftwo
782     \else
783       \let\caption@position\@firstoftwo
784     \fi
785   = \caption@setposition{\ifdim\prevdepth>-\p@ b\else t\fi}%

```

```

786   \else
787     \caption@Debug{no \protect\prevdepth}%
788     \let\caption@position\@secondoftwo
789 %   = \caption@setposition b%
790   \fi}

\caption@setautoposition \caption@setautoposition{\i<position>}
replaces the above algorithm by a different one (or a fixed position setting).
791 \newcommand*\caption@setautoposition[1]{%
792   \def\caption@autoposition{\caption@setposition{\#1}}}

```

16 Hooks

```

\AtBeginCaption \AtBeginCaption {\i<code>}
\AtEndCaption \AtEndCaption {\i<code>}
These hooks can be used analogous to \AtBeginDocument and \AtEndDocument.
793 \newcommand*\caption@beginhook{}
794 \newcommand*\caption@endhook{}
795 \newcommand*\AtBeginCaption{\l@addto@macro\caption@beginhook}
796 \newcommand*\AtEndCaption{\l@addto@macro\caption@endhook}

```

17 Lists

```

797 \DeclareCaptionOption{list}[1]{\caption@setlist{\#1}}
798 \DeclareCaptionOption{listof}[1]{\caption@setlist{\#1}}
\caption@setlist \caption@setlist{\i<boolean>}
799 \newcommand*\caption@setlist{\caption@set@bool\caption@iflist}

\DeclareCaptionListFormat \DeclareCaptionListFormat{\i<name>} {\i<code with #1 and #2>}
800 \newcommand*\DeclareCaptionListFormat[2]{%
801   \global\@namedef{caption@lstfmt@\#1}##1##2{\#2}}
802 \onlypreamble\DeclareCaptionListFormat

803 \DeclareCaptionOption{listformat}{\caption@setlistformat{\#1}}

\caption@setlistformat \caption@setlistformat{\i<name>}
Selecting a caption list format simply means saving the code (in \caption@lstfmt).
804 \newcommand*\caption@setlistformat[1]{%
805   \@ifundefined{caption@lstfmt@\#1}%
806     {\caption@Error{Undefined list format '#1'}}%
807     {\expandafter\let\expandafter\caption@lstfmt
808       \csname caption@lstfmt@\#1\endcsname}}

```

There are five pre-defined list formats, taken from the `subfig` package.

```

809 \DeclareCaptionListFormat{empty} {}
810 \DeclareCaptionListFormat{simple}{\#1\#2}
811 \DeclareCaptionListFormat{parens}{\#1(\#2)}
812 \DeclareCaptionListFormat{subsimple}{\#2}
813 \DeclareCaptionListFormat{subparens}{(\#2)}

```

```

tion@setdefaultlistformat
814 \newcommand*\caption@setdefaultlistformat[1]{%
815   \ifx\caption@lstfmt\caption@lstfmt@default
816     \caption@set@default@listformat{\#1}%
817     \caption@setlistformat{default}%
818   \else
819     \caption@set@default@listformat{\#1}%
820   \fi}
821 \newcommand*\caption@set@default@listformat[1]{%
822   \def\caption@lstfmt@default{\@nameuse{caption@lstfmt@\#1}}}

‘default’ usually maps to ‘subsimple’.
823 \caption@set@default@listformat{subsimple}

```

18 Debug option

```

824 \DeclareCaptionOption{debug}[1]{%
825   \caption@set@bool\caption@ifdebug{\#1}%
826   \caption@ifdebug
827   {\let\caption@Debug\caption@Info}%
828   {\let\caption@Debug\@gobble}%
829 \DeclareOption{debug}{\setkeys{caption}{debug}}%
830 \setkeys{caption}{debug=0}}

```

19 Document classes & Babel support

19.1 The standard L^AT_EX classes

```

831 \caption@CheckCommand\@makecaption{%
832   % article|report|book [2005/09/16 v1.4f Standard LATEX document class]
833   \long\def\@makecaption#1#2{%
834     \vskip\abovecaptionskip
835     \sbox\@tempboxa{\#1: #2}%
836     \ifdim \wd\@tempboxa >\hsize
837       #1: #2\par
838     \else
839       \global \minipagefalse
840       \hb@xt@\hsize{\hfil\box\@tempboxa\hfil}%
841     \fi
842     \vskip\belowcaptionskip}}

```

19.2 The A_MS & SMF classes

```

\caption@ifamsclass
843 \providecommand*\caption@ifamsclass{%
844   \@ifundefined{@captionheadfont}\@gobble\@firstofone}%
845 \onlypreamble\caption@ifamsclass

846 \caption@ifamsclass{%
847   \caption@CheckCommand\@makecaption{%
848     % amsart|amsproc|amsbook [2004/08/06 v2.20]
849     \long\def\@makecaption#1#2{%

```

```

850   \setbox@\tempboxa\vbox{\color@setgroup
851     \advance\hsize-2\captionindent\noindent
852     \@captionfont \@captionheadfont#1\@xp\@ifnotempty\@xp
853       {\@cdr#2\@nil}{.\@captionfont\upshape\enspace#2}%
854     \unskip\kern-2\captionindent\par
855     \global\setbox@\ne\lastbox\color@endgroup}%
856 \ifhbox@\ne % the normal case
857   \setbox@\ne\hbox{\unhbox@\ne\unskip\unskip\unpenalty\unkern}%
858 \fi
859 \ifdim\wd@\tempboxa=\z@ % this means caption will fit on one line
860   \setbox@\ne\hbox to\columnwidth{\hss\kern-2\captionindent\box@\ne\hss}%
861 \else % tempboxa contained more than one line
862   \setbox@\ne\vbox{\unvbox@\tempboxa\parskip\z@skip
863     \noindent\unhbox@\ne\advance\hsize-2\captionindent\par}%
864 \fi
865 \ifnum@\tempcpta<64 % if the float IS a figure...
866   \addvspace\abovecaptionskip
867   \hbox to\hsize{\kern\captionindent\box@\ne\hss}%
868 \else % if the float IS NOT a figure...
869   \hbox to\hsize{\kern\captionindent\box@\ne\hss}%
870   \nobreak
871   \vskip\belowcaptionskip
872 \fi
873 \relax
874 }

875 \caption@CheckCommand\@makecaption{%
876   % smfart|smfbok [1999/11/15 v1.2f Classe LaTeX pour les articles publiés par
877   \long\def\@makecaption#1#2{%
878     \ifdim\captionindent>.1\hsize \captionindent.1\hsize \fi
879     \setbox@\tempboxa\vbox{\color@setgroup
880       \advance\hsize-2\captionindent\noindent
881       \@captionfont \@captionheadfont#1\@xp\@ifnotempty\@xp
882         {\@cdr#2\@nil}{.\@addpunct{.}\@captionfont\upshape\enspace#2}%
883       \unskip\kern-2\captionindent\par
884       \global\setbox@\ne\lastbox\color@endgroup}%
885     \ifhbox@\ne % the normal case
886       \setbox@\ne\hbox{\unhbox@\ne\unskip\unskip\unpenalty\unkern}%
887     \fi
888     \ifdim\wd@\tempboxa=\z@ % this means caption will fit on one line
889       \setbox@\ne\hbox to\columnwidth{\hss\kern-2\captionindent\box@\ne\hss}%
890       \tempdima\wd\@ne\advance\@tempdima-\captionindent
891       \wd\@ne\@tempdima
892     \else % tempboxa contained more than one line
893       \setbox@\ne\vbox{\rightskip=0pt plus\captionindent\relax
894         \unvbox@\tempboxa\parskip\z@skip
895         \noindent\unhbox@\ne\advance\hsize-2\captionindent\par}%
896     \fi
897     \ifnum@\tempcpta<64 % if the float IS a figure...
898       \addvspace\abovecaptionskip
899       \noindent\kern\captionindent\box@\ne
900     \else % if the float IS NOT a figure...
901       \noindent\kern\captionindent\box@\ne
902       \nobreak
903       \vskip\belowcaptionskip

```

```

904     \fi
905     \relax
906   }
907   \let\captionmargin\captionindent % set to 3pc by AMS class
908   \begingroup\edef@\tempa{\endgroup
909     \noexpand\caption@g@addto@list\noexpand\caption@sty@default
910     {margin=\the\captionmargin
911      \@ifundefined{smf@makecaption}{}{,maxmargin=.1\linewidth}}}
912   \atempa
913   \caption@g@addto@list\caption@sls@default{margin*=.5\captionmargin}
914   \DeclareCaptionLabelSeparator{default}{.\enspace}
915   \DeclareCaptionDefaultFont{font}{\@captionfont}
916   \DeclareCaptionDefaultFont{labelfont}{\@captionheadfont}
917   \DeclareCaptionDefaultFont{textfont}{\@captionfont\upshape}
918   \captionsetup[figure]{position=b}
919   \captionsetup[table]{position=t}
920 }

```

19.3 The beamer class (Part one)

\caption@ifbeamerclass

```

921 \providecommand*\caption@ifbeamerclass{%
922   \@ifclassloaded{beamer}\@firstofone\@gobble}
923 \onlypreamble\caption@ifbeamerclass

924 \caption@ifbeamerclass{%
925   \caption@CheckCommand\beamer@makecaption{%
926     % beamerbaselocalstructure.sty,v 1.53 2007/01/28 20:48:21 tantau
927     \long\def\beamer@makecaption#1#2{%
928       \def\insertcaptionname{\csname#1name\endcsname}%
929       \def\insertcaptionnumber{\csname the#1\endcsname}%
930       \def\insertcaption{#2}%
931       \nobreak\vskip\abovecaptionskip\nobreak
932       \sbox\@tempboxa\usebeamertemplate**{caption}}%
933       \ifdim \wd\@tempboxa >\hsize
934         \usebeamertemplate**{caption}\par
935       \else
936         \global \minipagetrue
937         \hb@xt@\hsize{\hfil\box\@tempboxa\hfil}%
938       \fi
939     \nobreak\vskip\belowcaptionskip\nobreak}}

```

\caption@ifbeamertemplate

```

940 \newcommand*\caption@ifbeamertemplate[1]{%
941   \begingroup
942     \let\beamer@@tmpl@caption@ORI\beamer@@tmpl@caption
943     \nameuse{beamer@@tmpop@caption@#1}%
944     \ifx\beamer@@tmpl@caption@ORI\beamer@@tmpl@caption
945       \endgroup\expandafter\@firstoftwo
946     \else
947       \endgroup\expandafter\@secondoftwo
948     \fi}

```

```

949 \DeclareCaptionLabelFormat{default}{%
950   #1\caption@ifbeamertemplate{numbered}{~#2}{}}
951 \caption@declarelabelseparator
952   {\caption@ifbeamertemplate{caption name own line}\@gobble\@firstofone}
953   {default}
954   {\caption@ifbeamertemplate{caption name own line}{\\}{: } }
955 \DeclareCaptionDefaultFont{font}{%
956   \usebeamerfont*{caption}%
957   \usebeamercolor[fg]{caption}%
958 \DeclareCaptionDefaultFont{labelfont}{%
959   \usebeamercolor[fg]{caption name}%
960   \usebeamerfont*{caption name}%
961 \DeclareCaptionDefaultJustification{\raggedright}
962 \DeclareOption{beamerclass}{%
963   \renewcommand\caption@ifslc{%
964     \caption@ifbeamertemplate{caption name own line}\@secondoftwo\@firstoftwo}
965   % Since the beamer class do not offer a 'list of figures' we switch this supp
966   \captionsetup{list=0}}
967 \PassOptionsToPackage{beamerclass}{caption3}

```

If the `beamer` document class is used, we offer a `beamer` template called ‘`caption3`’ which can be used with option ‘`beamer`’ or `\setbeamertemplate{caption}{caption3}`. (Note that this is of no use when the `caption` package is used, too.)

```

968 \defbeamertemplate{caption}{caption3}{%
969   \caption@make\insertcaptionname\insertcaptionnumber\insertcaption}
970 \DeclareOption{beamer}{%
971   % \usebeamertemplate*{caption} will set font
972   \DeclareCaptionDefaultFont{font}{}%
973   \setbeamertemplate{caption}{caption3}}
974 %
975 % \begin{macrocode}
976 }

```

19.4 The KOMA-Script classes

```

\caption@ifkomaclass
977 \providecommand*\caption@ifkomaclass{%
978   \@ifundefined{scr@caption}\@gobble\@firstofone}
979 \onlypreamble\caption@ifkomaclass

980 \caption@ifkomaclass{%
981   \caption@CheckCommand\@makecaption{%
982     % scrartcl|scrreprt|scrbook [2007/03/07 v2.97a KOMA-Script document class]
983     \long\def\@makecaption#1#2{%
984       \if@captionabove
985         \vskip\belowcaptionskip
986       \else
987         \vskip\abovecaptionskip
988       \fi
989       \@@makecaption\@firstofone{#1}{#2}%
990       \if@captionabove
991         \vskip\abovecaptionskip
992       \else

```

```

993     \vskip\belowcaptionskip
994     \fi}}}
995 \DeclareCaptionFormat{default}{#1#2#3\par}{%
996   \ifdim\cap@indent<\z@
997     \caption@ifin@list\caption@lsepclist\caption@lsepname
998     {\caption@Error{%
999       The option 'labelsep=\caption@lsepname' does not work\MessageBreak
1000       with \noexpand\setcapchanging (which is set by default)}}%
1001     {\caption@fmt@hang{#1}{#2}{#3}}%
1002   \else
1003     #1#2%
1004     \ifdim\cap@indent<\z@
1005       \par
1006       \noindent\hspace*{-\cap@indent}%
1007     \else\if@capbreak
1008       \par
1009     \fi\fi
1010     #3\par
1011   \fi}
1012 \DeclareCaptionLabelSeparator{default}{\captionformat}
1013 \DeclareCaptionDefaultFont{font}{\scr@fnt@caption}
1014 \DeclareCaptionDefaultFont{labelfont}{\scr@fnt@captionlabel}
1015 }

```

19.5 The NTG Dutch classes

```

\caption@ifntgclass
1016 \providecommand*\caption@ifntgclass{%
1017   \@ifundefined{CaptionFonts}\@gobble\@firstofone}
1018 \onlypreamble\caption@ifntgclass

1019 \caption@ifntgclass{%
1020   \caption@CheckCommand\@makecaption{%
1021     % artikel|rapport|boek [2004/06/07 v2.1a NTG LaTeX document class]
1022     \long\def\@makecaption#1#2{%
1023       \vskip\abovecaptionskip
1024       \sbox\@tempboxa{\CaptionLabelFont#1:\CaptionTextFont#2}%
1025       \ifdim\wd\@tempboxa>\hsize
1026         {\CaptionLabelFont#1:\CaptionTextFont#2\par}
1027       \else
1028         \global\minipagetrue
1029         \hb@xt@\hsize{\hfil\box\@tempboxa\hfil}%
1030       \fi
1031       \vskip\belowcaptionskip}}
1032 \DeclareCaptionDefaultFont{labelfont}{\CaptionLabelFont}
1033 \DeclareCaptionDefaultFont{textfont}{\CaptionTextFont}
1034 }

```

19.6 The thesis class

```
\caption@ifthesisclass
```

```

1035 \providecommand*\caption@ifthesisclass{%
1036   \@ifundefined{cph@font}{\@gobble}{\@ifundefined{cpb@font}{\@gobble}\@firstofone}%
1037 \caption@ifthesisclass{%
1038   \caption@CheckCommand\@makecaption{%
1039     % thesis.cls 1996/25/01 1.0g LaTeX document class (wm).
1040     \long\def\@makecaption#1#2{%
1041       \vskip\abovecaptionskip
1042       \setbox\@tempboxa\hbox{\{cph@font #1:\} {\cpb@font #2}\}%
1043       \ifdim \wd\@tempboxa >\hsize
1044         \hangfrom{\cph@font #1: }{\cpb@font #2\par}%
1045       \else
1046         \hbox to\hsize{\hfil\box\@tempboxa\hfil}%
1047       \fi
1048       \vskip\belowcaptionskip}%
1049   \DeclareCaptionDefaultFormat{hang}
1050   \DeclareCaptionDefaultFont{labelfont}{\cph@font}
1051   \DeclareCaptionDefaultFont{textfont}{\cpb@font}
1052 }

```

19.7 The frenchb Babel option

```

1053 \@ifundefined{FB@makecaption}{}{%
1054   \caption@CheckCommand\@makecaption{%
1055     % frenchb.ldf [2005/02/06 v1.6g French support from the babel system]
1056     % frenchb.ldf [2007/10/05 v2.0e French support from the babel system]
1057     \long\def\@makecaption#1#2{%
1058       \vskip\abovecaptionskip
1059       \sbox\@tempboxa{\#1\CaptionSeparator #2}%
1060       \ifdim \wd\@tempboxa >\hsize
1061         #1\CaptionSeparator #2\par
1062       \else
1063         \global \minipagetrue
1064         \hb@xt@\hsize{\hfil\box\@tempboxa\hfil}%
1065       \fi
1066       \vskip\belowcaptionskip}%
1067   \ifx\@makecaption\STD@makecaption
1068     \DeclareCaptionLabelSeparator{default}{\CaptionSeparator}
1069     \def\caption@frenchb{%
1070       \let\STD@makecaption\@makecaption
1071       \let\FB@makecaption\@makecaption}
1072   \else
1073     \ifx\@makecaption\@undefined\else
1074       \caption@InfoNoLine{%
1075         The definition of \protect\@makecaption\space
1076         has been changed, \MessageBreak
1077         frenchb will NOT customize it}%
1078     \fi
1079   \fi
1080 }

```

19.8 The frenchle/pro package

```

1081 \@ifundefined{frenchTeXmods}{}{%
1082   \caption@CheckCommand\@makecaption{%
1083     % french(le).sty [2006/10/03 The french(le) package /V5,9991/]
1084     % french(le).sty [2007/06/28 The french(le) package /V5,9994/]
1085   \def\@makecaption#1#2{%
1086     \iftTY{%
1087       \def\@secondofmany##1##2\void{##2}%
1088       \def\@tempa{\@secondofmany#2\void}%
1089       \ifx\@tempa\empty{%
1090         \let\captionseparator\empty{%
1091       }%
1092       \mcORI{#1}{\relax\captionfont{#2}}{%
1093     }%
1094     }%
1095     \else{%
1096       \mcORI{#1}{#2}{%
1097     }%
1098     }%
1099     \fi{%
1100       \def\@secondofmany##1##2\void{##2}%
1101       \protected@edef\@tempa{\@secondofmany#2\void}%
1102       \ifx\@tempa\empty{%
1103         \let\captionseparator\empty{%
1104       }%
1105       \mcORI{#1}{\relax\captionfont{#2}}{%
1106     }%
1107     }%
1108     \fi{%
1109       \DeclareCaptionDefaultFont{textfont}{\itshape}%
1110       \DeclareCaptionLabelSeparator{default}{\captionseparator\space}%
1111     }%
1112   }%
1113   \def\caption@tempa#1{\@ifundefined{extras#1}{}{%
1114     \expandafter\addto\csname extras#1\endcsname{%
1115       % change default labelsep and listformat
1116       \caption@setdefaultlabelsep{period}%
1117       \caption@setdefaultlistformat{subperiod}%
1118     }%
1119     \expandafter\addto\csname noextras#1\endcsname{%
1120       % change default labelsep and listformat
1121       \caption@setdefaultlabelsep{colon}%
1122       \caption@setdefaultlistformat{subsimple}%
1123   }%
1124   \caption@tempa{hungarian}%
1125   \caption@tempa{magyar}%
1126 }%
1127 }%

```

19.9 The hungarian and magyar Babel option

```

1112 \DeclareCaptionListFormat{subperiod}{#2.}%
1113 \def\caption@tempa#1{\@ifundefined{extras#1}{}{%
1114   \expandafter\addto\csname extras#1\endcsname{%
1115     % change default labelsep and listformat
1116     \caption@setdefaultlabelsep{period}%
1117     \caption@setdefaultlistformat{subperiod}%
1118   }%
1119   \expandafter\addto\csname noextras#1\endcsname{%
1120     % change default labelsep and listformat
1121     \caption@setdefaultlabelsep{colon}%
1122     \caption@setdefaultlistformat{subsimple}%
1123 }%
1124 \caption@tempa{hungarian}%
1125 \caption@tempa{magyar}%

```

19.10 Unknown document class (or package)

```

1125 \caption@ifCheckCommand{%
1126   \caption@setbool{documentclass}{1}%
1127 }{%

```

```

1128 \caption@setbool{documentclass}{0}%
1129 \caption@InfoNoLine{%
1130     Unknown document class (or package), \MessageBreak
1131     standard defaults will be used}%
1132 \caption@Debug{\string\@makecaption\space=\space\meaning\@makecaption\@gobble}%
1133 }

```

20 Execution of options

```

1134 \captionsetup{style=default,position=default,%
1135             list,listformat=default,twoside=\if@twoside 1\else 0\fi}
1136 \ProcessOptions*

```

21 Making an ‘List of’ entry

<pre>\caption@addcontentsline</pre>	<pre>\caption@addcontentsline{\langle type\rangle } {\langle list entry\rangle }</pre> <p>Makes an entry in the list-of-whatever, if requested, i.e. the argument <i>⟨list entry⟩</i> is not empty and <i>listof</i>= was set to true.</p>
	<pre>1137 \newcommand*\caption@addcontentsline[2]{% 1138 \caption@iflist 1139 {\def\@tempa{\#2}}% 1140 {\let\@tempa\@empty}% 1141 \ifx\@tempa\@empty \else 1142 {\let\\space 1143 \@ifundefined{ext@\#1}% 1144 {\caption@Error{No float type '#1' defined}}% 1145 {\caption@addcontentsline 1146 {\csname ext@\#1\endcsname}% 1147 {\#1}% 1148 {\caption@lstmt{\@nameuse{p@\#1}}{\@nameuse{the\#1}}}% 1149 {\ignorespaces \#2}}}}% 1150 \fi}</pre>
	<pre>1151 \newcommand*\caption@@addcontentsline[4]{% 1152 \addcontentsline{\#1}{\#2}{\protect\numberline{\#3}{\#4}}}</pre>

22 Typesetting the caption

<pre>\ifcaption@star</pre>	<p>If the starred form of <i>\caption</i> is used, this will be set to true. (It will be reset to false at the end of <i>\caption@make</i>.)</p>
	<pre>1153 \newif\ifcaption@star</pre>
<pre>\caption@fnum</pre>	<pre>\caption@fnum{\langle float type\rangle }</pre> <p>Typesets the caption label; as replacement for <i>\fnum@⟨float type⟩</i>.</p>
	<pre>1154 \newcommand*\caption@fnum[1]{\caption@lfmt{\@nameuse{\#1name}}{\@nameuse{the\#1}}}</pre>
<pre>\caption@make</pre>	<pre>\caption@make{\langle float name\rangle } {\langle ref. number\rangle } {\langle text\rangle }</pre> <p>Typesets the caption.</p>
	<pre>1155 \newcommand\caption@make[2]{\caption@@make{\caption@lfmt{\#1}{\#2}}}</pre>

```

\caption@@make \caption@@make{\langle caption label\rangle}{\langle caption text\rangle}
1156 \newcommand\caption@@make[2]{%
1157   \begingroup
1158   \caption@stepcounter
1159   \caption@beginhook
Check margin, if \caption@minmargin or \caption@maxmargin is set
1160 % TODO: Move this to \caption@calcmargin!?
1161   \ifx\caption@maxmargin\@undefined \else
1162     \ifdim\captionmargin>\caption@maxmargin\relax
1163       \captionmargin\caption@maxmargin\relax
1164     \fi
1165   \fi
1166   \ifx\caption@minmargin\@undefined \else
1167     \ifdim\captionmargin<\caption@minmargin\relax
1168       \captionmargin\caption@minmargin\relax
1169     \fi
1170   \fi
Special single-line treatment (option singlelinecheck=)
1171   \caption@ifslc{\caption@slc{#1}{#2}\captionwidth\relax}{}%
Typeset the left margin (option margin=)
1172   \caption@calcmargin
1173   \tempdima\captionmargin
1174   \ifdim\captionmargin@=\z@ \else
1175     \caption@ifoddpage{}{\advance\tempdima\captionmargin@}%
1176   \fi
1177   \caption@ifh{\advance\tempdima\caption@indent}%
1178   \hspace\tempdima
We actually use a \vbox of width \captionwidth - \caption@indent to
typeset the caption.
Note: \captionindent is not supported if the caption format was defined with \DeclareCaptionFormat*.
1179   \tempdima\captionwidth
1180   \caption@ifh{\advance\tempdima-\caption@indent}%
1181   \caption@parbox\tempdima%
Typeset the indentation (option indentation=)
Bugfix 04-05-05: \hskip-\caption@indent replaced by \ifdim\caption@indent=\z@...
1182   \caption@ifh{%
1183     \ifdim\caption@indent=\z@
1184       \leavevmode
1185     \else
1186       \hskip-\caption@indent
1187     \fi}%
Typeset the caption itself and close the \caption@parbox
1188   \caption@@make{#1}{#2}%
Typeset the right margin (option margin=)
1189   \tempdima\captionmargin
1190   \ifdim\captionmargin@=\z@ \else
1191     \caption@ifoddpage{\advance\tempdima\captionmargin@}{}%
1192   \fi
1193   \hspace\tempdima

```

```

1194 \caption@endhook
1195 \endgroup
1196 \global\caption@starfalse}

\caption@calcmargin \caption@calcmargin
Calculate \captionmargin & \captionwidth, so both contain valid values.
1197 \newcommand*\caption@calcmargin{%
1198   \caption@calcmargin@hook
1199   \ifdim\captionwidth=\z@
1200     \captionwidth\linewidth
1201     \advance\captionwidth by -2\captionmargin
1202     \advance\captionwidth by -\captionmargin@
1203   \else
1204     \captionmargin\linewidth
1205     \advance\captionmargin by -\captionwidth
1206     \divide\captionmargin by 2
1207     \captionmargin@\z@
1208   \fi
1209   \caption@Debug{%
1210     \string\hsize=\the\hsize,
1211     \string\linewidth=\the\linewidth,\MessageBreak
1212     \string\leftmargin=\the\leftmargin,
1213     \string\rightmargin=\the\rightmargin,\MessageBreak
1214     \string\margin=\the\captionmargin,
1215     \string\margin@=\the\captionmargin@,
1216     \string\width=\the\captionwidth}%
1217 }

\caption@slc \caption@slc{\langle label\rangle } {\langle text\rangle } {\langle width\rangle } {\langle extra code\rangle }
This one does the single-line-check.
1218 \newcommand\caption@slc[4]{%
1219   \caption@@slc{\#1}{\#2}{\#3}{\caption@singleline{\#4}}{}}

1220 \newcommand\caption@@slc[5]{%
1221   \caption@Debug{Begin SLC}%
1222   \begingroup
1223   \caption@singleline
1224   \let\caption@hj\@empty
1225   \caption@calcmargin % calculate #3 if necessary
1226   \caption@prepareslc
1227   \sbox{\tempboxa}{\caption@@make{\#1}{\#2}}%
1228   \ifdim\wd\tempboxa>\#3%
1229     \endgroup
1230     #5%
1231   \else
1232     \endgroup
1233     #4%
1234   \fi
1235   \caption@Debug{End SLC} }

1236 \newcommand*\caption@singleline{%
1237   \caption@xsetup\caption@opt@singleline
1238   \let\caption@fmt\caption@slfmt}

```

```

\caption@prepareslc \caption@prepareslc
Re-define anything which would disturb the single-line-check.

1239 \newcommand*\caption@prepareslc{%
1240   \def\label{\caption@withoptargs@gobbletwo}%
1241   \let\caption@footnote@ORI\footnote
1242   \def\footnote{\caption@withoptargs\caption@footnote}%
1243   \let\caption@footnotemark@ORI\footnotemark
1244   \def\footnotemark{\caption@withoptargs\caption@footnotemark}%
1245   \let\@footnotetext\gobble
1246   \let\@endnotetext\gobble}
1247 \newcommand\caption@footnote[2]{%
1248   \begingroup
1249     \let\stepcounter\caption@l@stepcounter
1250     \caption@footnote@ORI#1{#2}%
1251   \endgroup}
1252 \newcommand\caption@footnotemark[1]{%
1253   \begingroup
1254     \let\stepcounter\caption@l@stepcounter
1255     \caption@footnotemark@ORI#1%
1256   \endgroup}
1257 \newcommand*\caption@l@stepcounter[1]{%
1258   \advance\csname c@\#1\endcsname\@ne\relax}

\caption@parbox \caption@parbox{\width}{\contents}
This macro defines the box which surrounds the caption paragraph.

1259 \newcommand*\caption@parbox{\parbox[b]}

\caption@applyfont \caption@applyfont
This macro executes the font relevant macros, i.e. by default the options set by
justification=, font=, and size=.

1260 \newcommand*\caption@applyfont{%
1261   \caption@hj\captionfont\captionsize}

\caption@@@make \caption@@@make{\caption label}{\caption text}
This one finally typesets the caption paragraph, without margin and indentation.

1262 \newcommand\caption@@@make[2]{%
If the label is empty, we use no caption label separator.

1263   \sbox\@tempboxa{\#1}%
1264   \ifdim\wd\@tempboxa=\z@
1265     \let\caption@lsep\relax
1266   %   \capbreakfalse
1267   \fi
If the text is empty, we use no caption label separator, too. (And no text format either.)

1268   \caption@ifempty{\#2}{%
1269     \let\caption@lsep\empty
1270     \let\caption@tfmt\@firstofone
1271   %   \capbreakfalse
1272   %   \let\caption@ifstrut\@secondoftwo
1273   }%

```

Take care that `\caption@parindent` and `\caption@hangindent` will be used to typeset the paragraph.

1274 `\@setpar{\@@par\caption@@par}\caption@@par`

Finally typeset the caption.

```
1275  \caption@applyfont
1276  \caption@fmt
1277  {\ifcaption@star\else{\captionlabelfont#1\fi}%
1278  {\ifcaption@star\else{\caption@iflf\captionlabelfont\caption@lsep}\fi}%
1279  {{\captionontextfont
1280    \caption@ifstrut{\vrule\@height\ht\strutbox\@width\z@\{}%
1281    \nobreak\hskip\z@skip % enable hyphenation
1282    \caption@tfmt{\#2}%
1283  \% \caption@ifstrut{\vrule\@height\z@\@depth\dp\strutbox\@width\z@\{}%
1284  \caption@ifstrut{\ifhmode\@finalstrut\strutbox\fi}\{}%
1285  \par}}}}
```

`\caption@ifempty \caption@ifempty{\langle text\rangle }{\langle true\rangle }{\langle false\rangle }`

This one tests if the `\langle text\rangle` is actually empty.

Note: This will be done without expanding the text, therefore this is far away from being bullet-proof.

Note: This macro is re-defining itself so only the first test (in a group) will actually be done.

```
1286 \newcommand\caption@ifempty[1]{%
1287   \caption@if@empty{\#1}%
1288   \caption@ifempty\@unused}
1289 \newcommand\caption@if@empty[1]{%
1290   \def\caption@tempa{\#1}%
1291   \ifx\caption@tempa\@empty
1292     \let\caption@ifempty\@secondoftwo
1293   \else
1294     \expandafter\def\expandafter\caption@tempa\expandafter{%
1295       \caption@car\#1\caption@if@empty\caption@nil}%
1296     \def\caption@tempb{\caption@if@empty}%
1297     \ifx\caption@tempa\caption@tempb
1298       \let\caption@ifempty\@secondoftwo
1299     \else
1300       \def\caption@tempb{\ignorespaces}%
1301       \ifx\caption@tempa\caption@tempb
1302         \expandafter\caption@if@empty\expandafter{\@gobble\#1}%
1303       \else
1304         \def\caption@tempb{\label}%
1305         \ifx\caption@tempa\caption@tempb
1306           \expandafter\caption@if@empty\expandafter{\@gobbletwo\#1}%
1307         \else
1308           \def\caption@tempb{\index}%
1309           \ifx\caption@tempa\caption@tempb
1310             \expandafter\caption@if@empty\expandafter{\@gobbletwo\#1}%
1311           \else
1312             \def\caption@tempb{\glossary}%
1313             \ifx\caption@tempa\caption@tempb
1314               \expandafter\caption@if@empty\expandafter{\@gobbletwo\#1}%
1315             \else
1316               \let\caption@ifempty\@gobbletwo
```

```

1317           \fi
1318           \fi
1319           \fi
1320           \fi
1321           \fi
1322       \fi}

1323 \long\def\caption@car#1{\caption@nil{#1}}% same as \car, but \long
\caption@@par \caption@@par
This command will be executed with every \par inside the caption.
1324 \newcommand*{\caption@@par}{%
1325   \parindent\caption@parindent\hangindent\caption@hangindent}%

```

23 Types & sub-types

```

\DeclareCaptionType \DeclareCaptionType[<options>]{<environment>} [<name>] [<list name>]
1326 \newcommand*{\DeclareCaptionType}{%
1327   \@testopt{\DeclareCaptionType}{}}
1328 \onlypreamble\DeclareCaptionType

1329 \def{@\DeclareCaptionType}[#1]{%
1330   \def{\caption@type}{#2}%
1331   \caption@Debug{New type '#2'}%
1332   \newcounter{#2}\@namedef{theH#2}{}%
1333   \KV@caption@DCT@within\caption@within@default
1334   \caption@DeclareWithinOption{#2}%
1335   \KV@caption@DCT@placement{tbp}%
1336   \@ifundefined{c@float@type}%
1337     {\newcounter{float@type}%
1338      \setcounter{float@type}{\@ifundefined{c@figure}{14}}%
1339    }%
1340   \caption@Debug{float type '#2'=\the\value{float@type}}%
1341   \expandafter\xdef\csname ftype@#2\endcsname{\the\value{float@type}}%
1342   \addtocounter{float@type}{\value{float@type}}%
1343   \KV@caption@DCT@fileext{lo#2}%
1344   \@namedef{fnum@#2}{\nameuse{#2name}\nobreakspace\nameref{the#2}}%
1345   \newenvironment{#2}{\@float{#2}}{\end@float}%
1346   \newenvironment{#2*}{\dblfloat{#2}}{\end@dblfloat}%
1347   \expandafter\newcommand\csname listof#2s\endcsname{\caption@listof{#2}}%
1348   \expandafter\newcommand\csname listof#2es\endcsname{\caption@listof{#2}}%
1349   \@ifundefined{l@figure}%
1350     {\namedef{l@#2}{\dottedtocline{1}{1.5em}{2.3em}}}% 
1351     {\expandafter\let\csname l@#2\endcsname{l@figure}}%
1352   \expandafter\newcommand\csname #2name\endcsname{}%
1353   \edef@tempa{\def\noexpand@tempa{\car#2\@nil}}%
1354   \uppercase\expandafter{\@tempa}%
1355   \edef@tempb{\noexpand\g@addto@macro\noexpand@tempa{\cdr#2\@nil}}%
1356   \@tempb
1357   \expandafter\let\csname #2name\endcsname{\tempa}%
1358   \expandafter\newcommand\csname list#2name\endcsname{}%
1359   \expandafter\xdef\csname list#2name\endcsname{List of \tempa s}%

```

```

1360  \@cons\caption@typelist{\#2}%
1361  \caption@setkeys[caption]{caption@DCT}{#1}%
1362  \@ifundefined{float@exts}{\newtoks\float@exts{} }%
1363  \let\float@do=\relax
1364  \edef@\tempa{\noexpand\float@exts{\the\float@exts\float@do{\@nameuse{ext@\#2}}}}%
1365  \@tempa
1366  \@ifundefined{float@addtolists}{%
1367    \newcommand\float@addtolists[1]{%
1368      \def\float@do####1{\addtocontents{####1}{\#1}}\the\float@exts}%
1369  \@ifundefined{@chapter}{}{\caption@PatchChapter}{} }%
1370  \@ifnextchar[\@@DeclareCaptionType\relax}
1371 \onlypreamble\DeclareCaptionType
1372 \def\@@DeclareCaptionType[#1]{%
1373   \KV@caption@DCT@name{#1}%
1374   \@ifnextchar[\@@@DeclareCaptionType\relax}
1375 \onlypreamble\@@DeclareCaptionType
1376 \def\@@@DeclareCaptionType[#1]{%
1377   \KV@caption@DCT@listname{#1}%
1378 \onlypreamble\@@@DeclareCaptionType
1379 \let\DeclareFloatingEnvironment\DeclareCaptionType % old command name
1380 \onlypreamble\DeclareFloatingEnvironment

```

\caption@within@default **The default ‘within’ value.**

```

1381 \newcommand*\caption@within@default{\@ifundefined{c@chapter}{none}{chapter}}
1382 \onlypreamble\caption@within@default

```

\caption@listof \caption@listof{*float type*}
1383 \newcommand*\caption@listof[1]{%
1384 \begingroup
1385 \expandafter\let\expandafter\listfigurename\csname list#1name\endcsname
1386 \expandafter\let\expandafter\ext@figure\csname ext@\#1\endcsname
1387 \let\caption@ORI@starttoc\starttoc
1388 \renewcommand*\@starttoc[1]{%
1389 \expandafter\caption@ORI@starttoc\expandafter{\ext@figure} }%
1390 \listoffigures
1391 \endgroup

\caption@typelist An \elt-list containing the caption types defined with \DeclareCaptionType.

```

1392 \newcommand*\caption@typelist{}

```

The available *options* are: fileext=⟨file extension⟩, listname=⟨list name⟩, name=⟨prosa name⟩, placement=⟨htbp⟩, within=⟨none,chapter,section⟩, and without.

```

1393 \define@key{caption@DCT}{fileext}{\@namedef{ext@\caption@type}{#1}}
1394 \onlypreamble\define@key{caption@DCT}{fileext}
1395 \define@key{caption@DCT}{listname}{\@namedef{list\caption@type name}{#1}}
1396 \onlypreamble\define@key{caption@DCT}{listname}
1397 \define@key{caption@DCT}{name}{\@namedef{\caption@type name}{#1}}
1398 \onlypreamble\define@key{caption@DCT}{name}
1399 \define@key{caption@DCT}{placement}{\@namedef{fps@\caption@type}{#1}}
1400 \onlypreamble\define@key{caption@DCT}{placement}
1401 \define@key{caption@DCT}{within}{%

```

```

1402  \@ifundefined{c@chapter}{}{\@removefromreset\caption@type{chapter}}%
1403  \@removefromreset\caption@type{section}%
1404  \begingroup
1405    \caption@setkeys[caption]{caption@within}{#1}%
1406  \endgroup}
1407 %\@onlypreamble@key{caption@DCT}{within}
1408 \define@key{caption@DCT}{without}{\KV@caption@DCT@within{none}}
1409 %\@onlypreamble@key{caption@DCT}{without}
1410 \define@key{caption@within}{none}[]{%
1411   \caption@within{}{}}
1412 %\@onlypreamble@key{caption@within}{none}
1413 \define@key{caption@within}{section}[]{%
1414   \addtoreset\caption@type{section}%
1415   \caption@within{\ifnum\c@section>\z@\thesection.\fi}{\theHsection.}}
1416 %\@onlypreamble@key{caption@within}{section}
1417 \ifundefined{c@chapter}{}{%
1418   \define@key{caption@within}{chapter}[]{%
1419     \addtoreset\caption@type{chapter}%
1420     \caption@within{\ifnum\c@chapter>\z@\thechapter.\fi}{\theHchapter.}}
1421 }% \@onlypreamble@key{caption@within}{chapter}

\caption@within \caption@within{\langle thecode\rangle}{\langle theHcode\rangle}
1422 \newcommand*\caption@within{%
1423   \expandafter\caption@within@\expandafter{\caption@type}}
1424 %\@onlypreamble\caption@within
1425 \newcommand*\caption@within@[3]{%
1426   \global\@namedef{the#1}{#2\arabic{#1}}%
1427   \@ifundefined{theH#1}\caption@AtBeginDocument@\firstofone
1428   {\global\@namedef{theH#1}{#3\arabic{#1}}}}
1429 %\@onlypreamble\caption@within@

\@removefromreset This code was taken from the remreset package which is part of the ‘carlisle’ package bundle. (Copyright 1997 David Carlisle)
1430 \providecommand*\@removefromreset[2]{%
1431   \expandafter\let\csname c#1\endcsname\@removefromreset
1432   \def\@elt##1{%
1433     \expandafter\ifx\csname c##1\endcsname\@removefromreset
1434     \else
1435       \noexpand\@elt{##1}%
1436     \fi}%
1437   \expandafter\xdef\csname cl##2\endcsname{%
1438     \csname cl##2\endcsname}{}}

\caption@PatchChapter We try to patch \@chapter so \float@addtolists will be supported. (Note: The KOMA-Script classes already support \float@addtolists.)
1439 \newcommand*\caption@PatchChapter{%
1440   \providecommand*\@chapterlistsgap{10\p@}%
1441   % report.cls [2005/09/16 v1.4f Standard LaTeX document class]
1442   \caption@patch@chapter{report}{%
1443     \ifnum \c@section>\m@ne
1444       \refstepcounter{chapter}%
1445       \typeout{@chapapp\space\thechapter.}%
1446       \addcontentsline{toc}{chapter}%

```

```

1447     {\protect\numberline{\thechapter}##1}%
1448 \else
1449   \addcontentsline{toc}{chapter}##1}%
1450 \fi
1451 \chaptermark{##1}%
1452 \addtocontents{lof}{\protect\addvspace{10\p@}}%
1453 \addtocontents{lot}{\protect\addvspace{10\p@}}%
1454 \if@twocolumn
1455   \atopnewpage[\@makechapterhead##2]%
1456 \else
1457   \@makechapterhead##2}%
1458   \afterheading
1459 \fi
1460 }{%
1461 \ifnum \c@secnumdepth >\m@ne
1462   \refstepcounter{chapter}%
1463   \typeout{\@chapapp\space\thechapter.}%
1464   \addcontentsline{toc}{chapter}%
1465     {\protect\numberline{\thechapter}##1}%
1466 \else
1467   \addcontentsline{toc}{chapter}##1}%
1468 \fi
1469 \chaptermark{##1}%
1470 \ifdim \@chapterlistsgap>\z@
1471   \addtocontents{lof}{\protect\addvspace{\@chapterlistsgap}}%
1472   \addtocontents{lot}{\protect\addvspace{\@chapterlistsgap}}%
1473   \float@addtolists{\protect\addvspace{\@chapterlistsgap}}%
1474 \fi
1475 \if@twocolumn
1476   \atopnewpage[\@makechapterhead##2]%
1477 \else
1478   \@makechapterhead##2}%
1479   \afterheading
1480 \fi}%
1481 % book.cls [2005/09/16 v1.4f Standard LaTeX document class]
1482 \caption@patch@chapter{book}{%
1483   \ifnum \c@secnumdepth >\m@ne
1484     \if@mainmatter
1485       \refstepcounter{chapter}%
1486       \typeout{\@chapapp\space\thechapter.}%
1487       \addcontentsline{toc}{chapter}%
1488         {\protect\numberline{\thechapter}##1}%
1489     \else
1490       \addcontentsline{toc}{chapter}##1}%
1491     \fi
1492   \else
1493     \addcontentsline{toc}{chapter}##1}%
1494   \fi
1495 \chaptermark{##1}%
1496 \addtocontents{lof}{\protect\addvspace{10\p@}}%
1497 \addtocontents{lot}{\protect\addvspace{10\p@}}%
1498 \if@twocolumn
1499   \atopnewpage[\@makechapterhead##2]%
1500 \else

```

```

1501      \@makechapterhead{##2}%
1502      \@afterheading
1503      \fi
1504  }{%
1505      \ifnum \c@secnumdepth >\m@ne
1506          \if@mainmatter
1507              \refstepcounter{chapter}%
1508              \typeout{\@chapapp\space\thechapter.}%
1509              \addcontentsline{toc}{chapter}%
1510                  {\protect\numberline{\thechapter}##1}%
1511          \else
1512              \addcontentsline{toc}{chapter}##1}%
1513          \fi
1514      \else
1515          \addcontentsline{toc}{chapter}##1}%
1516      \fi
1517      \chaptermark{##1}%
1518      \ifdim \@chapterlistsgap>\z@
1519          \addtocontents{lof}{\protect\addvspace{\@chapterlistsgap}}%
1520          \addtocontents{lot}{\protect\addvspace{\@chapterlistsgap}}%
1521          \float@addtolists{\protect\addvspace{\@chapterlistsgap}}%
1522      \fi
1523      \if@twocolumn
1524          \@topnewpage[\@makechapterhead{##2}]%
1525      \else
1526          \@makechapterhead{##2}%
1527          \@afterheading
1528      \fi}%
1529  % amsbook.cls [2004/08/06 v2.20]
1530  % smfbook.cls [1999/11/15 v1.2f Classe LaTeX pour les monographies editees par
1531  \caption@patch@chapter{ams/smfbook}{%
1532      \refstepcounter{chapter}%
1533      \ifnum\c@secnumdepth<\z@ \let\@secnumber\empty
1534      \else \let\@secnumber\thechapter \fi
1535      \typeout{\chaptername\space\@secnumber}%
1536      \def\@toclevel{0}%
1537      \ifx\chaptername\appendixname \tocwriteb\tocappendix{chapter}##2}%
1538      \else \tocwriteb\tocchapter{chapter}##2\fi
1539      \chaptermark{##1}%
1540      \addtocontents{lof}{\protect\addvspace{10\p@}}%
1541      \addtocontents{lot}{\protect\addvspace{10\p@}}%
1542      \@makechapterhead{##2}\@afterheading
1543  }{%
1544      \refstepcounter{chapter}%
1545      \ifnum\c@secnumdepth<\z@ \let\@secnumber\empty
1546      \else \let\@secnumber\thechapter \fi
1547      \typeout{\chaptername\space\@secnumber}%
1548      \def\@toclevel{0}%
1549      \ifx\chaptername\appendixname \tocwriteb\tocappendix{chapter}##2}%
1550      \else \tocwriteb\tocchapter{chapter}##2\fi
1551      \chaptermark{##1}%
1552      \ifdim \@chapterlistsgap>\z@
1553          \addtocontents{lof}{\protect\addvspace{\@chapterlistsgap}}%
1554          \addtocontents{lot}{\protect\addvspace{\@chapterlistsgap}}%

```

```

1555     \float@addtolists{\protect\addvspace{\@chapterlistsgap}}%
1556     \fi
1557     \makechapterhead{##2}\@afterheading}%
1558     % scrreprt/scrbook.cls
1559     \@ifundefined{KOMAClassName}{}{%
1560       \caption@Debug{document class '\KOMAClassName' detected}%
1561       \let\caption@patch@chapter\gobblethree}%
1562     % rapport1/3.cls [2004/06/07 v2.1a NTG LaTeX document class]
1563     \caption@patch@chapter{rapport}{%
1564       \ifnum \c@secnumdepth >\m@ne
1565         \refstepcounter{chapter}%
1566         \typeout{\@chapapp\space\thechapter.}%
1567         \addcontentsline{toc}{chapter}%
1568           {\protect\numberline{\thechapter}\toc@font0 ##1}%
1569       \else
1570         \addcontentsline{toc}{chapter}{\toc@font0 ##1}%
1571       \fi
1572       \chaptermark{##1}%
1573       \addtocontents{lof}{\protect\addvspace{10\p@}}%
1574       \addtocontents{lot}{\protect\addvspace{10\p@}}%
1575       \if@twocolumn
1576         \atopnewpage[\makechapterhead{##2}]%
1577       \else
1578         \makechapterhead{##2}%
1579         \afterheading
1580       \fi
1581     }{%
1582       \ifnum \c@secnumdepth >\m@ne
1583         \refstepcounter{chapter}%
1584         \typeout{\@chapapp\space\thechapter.}%
1585         \addcontentsline{toc}{chapter}%
1586           {\protect\numberline{\thechapter}\toc@font0 ##1}%
1587       \else
1588         \addcontentsline{toc}{chapter}{\toc@font0 ##1}%
1589       \fi
1590       \chaptermark{##1}%
1591       \ifdim \章间距>\z@
1592         \addtocontents{lof}{\protect\addvspace{\章间距}}%
1593         \addtocontents{lot}{\protect\addvspace{\章间距}}%
1594         \float@addtolists{\protect\addvspace{\章间距}}%
1595       \fi
1596       \if@twocolumn
1597         \atopnewpage[\makechapterhead{##2}]%
1598       \else
1599         \makechapterhead{##2}%
1600         \afterheading
1601       \fi}%
1602     % boek(3).cls [2004/06/07 v2.1a NTG LaTeX document class]
1603     \caption@patch@chapter{boek}{%
1604       \ifnum \c@secnumdepth >\m@ne
1605         \if@mainmatter
1606           \refstepcounter{chapter}%
1607           \typeout{\@chapapp\space\thechapter.}%

```

```

1608     \addcontentsline{toc}{chapter}%
1609     {\protect\numberline{\thechapter}\toc@font0 ##1}%
1610 \else
1611     \addcontentsline{toc}{chapter}{\toc@font0 ##1}%
1612 \fi
1613 \else
1614     \addcontentsline{toc}{chapter}{\toc@font0 ##1}%
1615 \fi
1616 \chaptermark{##1}%
1617 \addtocontents{lof}{\protect\addvspace{10\p@}}%
1618 \addtocontents{lot}{\protect\addvspace{10\p@}}%
1619 \if@twocolumn
1620     \@topnewpage[\@makechapterhead{##2}]%
1621 \else
1622     \@makechapterhead{##2}%
1623     \@afterheading
1624 \fi
1625 }{%
1626 \ifnum \c@secnumdepth >\m@ne
1627 \if@mainmatter
1628     \refstepcounter{chapter}%
1629     \typeout{\@chapapp\space\thechapter.}%
1630     \addcontentsline{toc}{chapter}%
1631     {\protect\numberline{\thechapter}\toc@font0 ##1}%
1632 \else
1633     \addcontentsline{toc}{chapter}{\toc@font0 ##1}%
1634 \fi
1635 \else
1636     \addcontentsline{toc}{chapter}{\toc@font0 ##1}%
1637 \fi
1638 \chaptermark{##1}%
1639 \ifdim \@chapterlistsgap>z@
1640     \addtocontents{lof}{\protect\addvspace{\@chapterlistsgap}}%
1641     \addtocontents{lot}{\protect\addvspace{\@chapterlistsgap}}%
1642     \float@addtolists{\protect\addvspace{\@chapterlistsgap}}%
1643 \fi
1644 \if@twocolumn
1645     \@topnewpage[\@makechapterhead{##2}]%
1646 \else
1647     \@makechapterhead{##2}%
1648     \@afterheading
1649 \fi}%
1650 % thesis.cls [1996/25/01 1.0g LaTeX document class (wm).]
1651 \caption@patch@chapter{thesis}{%
1652 \ifnum \c@secnumdepth >\m@ne
1653 \if@mainmatter
1654     \refstepcounter{chapter}%
1655     \typeout{\chaptername\space\thechapter.}%
1656 \if@thema
1657     \ifx@\shortauthor@\empty
1658         \addcontentsline{toc}{chapter}{%
1659             \protect\numberline{\thechapter.}##1}%
1660     \else
1661         \addcontentsline{toc}{chapter}{%

```

```

1662           \protect\numberline{\thechapter.}%
1663           \@shortauthor\hfill\mbox{}\vskip\normallineskip ##1}%
1664       \fi
1665     \else
1666       \addcontentsline{toc}{chapter}{%
1667         \protect\numberline{\thechapter.}##1}%
1668       \fi
1669     \else
1670       \addcontentsline{toc}{chapter}{##1}
1671       \fi
1672     \else
1673       \addcontentsline{toc}{chapter}{##1}
1674     \fi
1675   \chaptermark{##1}
1676   \addtocontents{lof}{\protect\addvspace{10pt}}
1677   \addtocontents{lot}{\protect\addvspace{10pt}}
1678   \if@twocolumn
1679     \atopnewpage[\@makechapterhead{##2}]
1680   \else
1681     \@makechapterhead{##2}
1682     \afterheading
1683   \fi
1684 }{%
1685   \ifnum \c@secnumdepth >\m@ne
1686     \if@mainmatter
1687       \refstepcounter{chapter}%
1688       \typeout{\chaptername\space\thechapter.}%
1689     \if@thema
1690       \ifx\@shortauthor\empty
1691         \addcontentsline{toc}{chapter}{%
1692           \protect\numberline{\thechapter.}##1}%
1693       \else
1694         \addcontentsline{toc}{chapter}{%
1695           \protect\numberline{\thechapter.}%
1696           \@shortauthor\hfill\mbox{}\vskip\normallineskip ##1}%
1697         \fi
1698       \else
1699         \addcontentsline{toc}{chapter}{%
1700           \protect\numberline{\thechapter.}##1}%
1701         \fi
1702       \else
1703         \addcontentsline{toc}{chapter}{##1}%
1704       \fi
1705     \else
1706       \addcontentsline{toc}{chapter}{##1}%
1707     \fi
1708   \chaptermark{##1}%
1709   \ifdim \@chapterlistsgap>\z@
1710     \addtocontents{lof}{\protect\addvspace{\@chapterlistsgap}}%
1711     \addtocontents{lot}{\protect\addvspace{\@chapterlistsgap}}%
1712     \float@addtolists{\protect\addvspace{\@chapterlistsgap}}%
1713   \fi
1714   \if@twocolumn
1715     \atopnewpage[\@makechapterhead{##2}]%

```

```

1716     \else
1717         \@makechapterhead{##2}%
1718         \@afterheading
1719     \fi}%
1720 \ifx\caption@patch@chapter\@gobblethree \else
1721     \caption@Debug{%
1722         Unsupported document class detected, \MessageBreak
1723         or \noexpand\@chapter was redefined by another package}%
1724     \fi
1725 \let\caption@PatchChapter\@undefined}
1726 %\onlypreamble\caption@PatchChapter
1727 \newcommand\caption@patch@chapter[3]{%
1728     \begingroup
1729     \let\if@twocolumn\iffalse
1730     \let\if@mainmatter\iffalse
1731     \let\if@thema\iffalse
1732     \def\@tempa[##1]##2{##2}%
1733     \ifx\@tempa\@chapter
1734         \caption@Debug{document class '#1' detected}%
1735         \gdef\@chapter[##1]##2{##3}%
1736         \global\let\caption@patch@chapter\@gobblethree
1737     \fi
1738     \endgroup}
1739 %\onlypreamble\caption@patch@chapter
1740 \long\def \gobblethree #1#2#3{}

\@stpelt We patch \@stpelt so a list of ‘connected’ counters will be reset, too. (Like
\stepcounter does in ltcounts.dtx.)
1741 \newcommand*\caption@patch@stpelt{%
1742     \let\caption@stpelt\@stpelt
1743     \def\@stpelt##1{%
1744         \caption@stpelt{##1}%
1745         \begingroup
1746             \let\@elt\caption@stpelt
1747             \csname caption@cl@##1\endcsname
1748         \endgroup}%
1749     \let\caption@patch@stpelt\relax}
1750 \onlypreamble\caption@patch@stpelt

\caption@addtoreset Like \@addtoreset from ltcounts.dtx
1751 \newcommand*\caption@addtoreset[2]{%
1752     \caption@patch@stpelt
1753     \ifundefined{caption@cl@#2}{\@namedef{caption@cl@#2}{}{}}{}}%
1754     \expandafter\@cons\csname caption@cl@#2\endcsname{##1}}}
1755 \onlypreamble\caption@addtoreset

\caption@addtoreset Like \@removefromreset from remreset.sty
1756 \newcommand*\caption@removefromreset[2]{%
1757     \begingroup
1758     \expandafter\let\csname c@##1\endcsname\caption@removefromreset
1759     \def\@elt##1{%
1760         \expandafter\ifx\csname c@##1\endcsname\caption@removefromreset

```

```

1761     \else
1762         \noexpand\@elt{\#1}%
1763     \fi}%
1764     \expandafter\xdef\csname caption@cl\#2\endcsname{%
1765         \csname caption@cl\#2\endcsname}%
1766 \endgroup
1767 \@onlypreamble\caption@removefromreset

\DeclareCaptionSubType{} % This is the standard declaration
\DeclareCaptionSubType*{} % This is the starred declaration

The starred variant provides the numbering format <type>. <subtype> while the non-starred variant simply uses <subtype>.
1768 \newcommand*\DeclareCaptionSubType{%
1769     \caption@teststar\caption@declarestype@\firstoftwo@\secondoftwo}
1770 \@onlypreamble\DeclareCaptionSubType
1771 \newcommand*\caption@declarestype[1]{%
1772     \@testopt{\caption@@declarestype{\#1}}{\alph{}}}
1773 \@onlypreamble\caption@declarestype
1774 \def\caption@@declarestype#1[#2]#3{%
1775     \@ifundefined{c@#3}{%
1776         {\caption@Error{No float type '#3' defined}}%
1777         {\@ifundefined{c@sub#3}{%
1778             {\caption@Debug{New subtype 'sub#3'}}%
1779             \newcounter{sub#3}%
1780             \caption@addtoreset{sub#3}{#3}%
1781             \namedef{ext@sub#3}{\csname ext\#3\endcsname}%
1782             \caption@declarelistentry{#3}%
1783             \cons\caption@subtypelist{{#3}}%
1784             {\caption@Debug{Modify caption 'sub#3'}}%
1785             \@namedef{sub#3name}{}%
1786             \@namedef{sub#3autorefname}{\csname #3name\endcsname}%
1787             #1 is \firstoftwo in star form, and \secondoftwo otherwise
1788             {\@namedef{p@sub#3}}%
1789             {\namedef{thesub#3}{\csname the#3\endcsname.\nameuse{#2}{sub#3}}%
1790             {\@namedef{p@sub#3}{\csname the#3\endcsname}%
1791             {\namedef{thesub#3}{\nameuse{#2}{sub#3}}}}%
1792             {\namedef{theHsub#3}{\csname theH#3\endcsname.\arabic{sub#3}}}}%
1793         }%
1794     }%
1795 \newcommand*\caption@declarelistentry{%
1796     \@ifundefined{l@chapter}{%
1797         {\caption@@declarelistentry\l@subsubsection}%
1798         {\caption@@declarelistentry\l@subsection}}%
1799 }%
1800 \newcommand*\caption@@declarelistentry[2]{%
1801     \ifx#1\undefined
1802         \caption@@@declarelistentry\relax\@dottedtocline\caption@nil{#2}%
1803     \else
1804         \expandafter\caption@@@declarelistentry#1{}{}\@dottedtocline\caption@nil{#2}%
1805     \fi}%
1806 }%

```

```

1807 \long\def\caption@@@declare sublistentry#1{@dottedtocline#2\caption@nil#3}{%
1808   \def@\tempa{#1}%
1809 % Does \l@(sub)section start with \@dottedtocline?
1810   \ifx@\tempa\empty
1811 % Yes
1812     \caption@@@declare sublistentry{#3}#2\caption@nil
1813   \else
1814 % No
1815     \caption@@@declare sublistentry{#3}{3.8em}{3.2em}\caption@nil
1816   \fi}
1817 \onlypreamble\caption@@@declare sublistentry
1818 \def\caption@@@declare sublistentry#1#2#3#4#5\caption@nil{%
1819   \expandafter\caption@@@declare sublistentry\expandafter
1820   {\csname @dotted\csname ext@#1\endcsname line\endcsname{#1}{#3}{#4}}}
1821 \onlypreamble\caption@@@declare sublistentry
1822 \newcommand*\caption@@@declare sublistentry[4]{%
1823   \namedef{l@sub#2}{#1{2}{#3}{#4}}%
1824   \caption@@@declare sublistentry#1{c@\csname ext@#2\endcsname depth}}
1825 \onlypreamble\caption@@@declare sublistentry
1826 \newcommand*\caption@@@declare sublistentry[2]{%
1827   \ifx#1\relax
1828     \def#1#1{%
1829       \def\next{\@dottedtocline{##1}}%
1830       \@ifundefined{#2}{}{%
1831         \ifnum ##1>\@nameuse{#2}\relax
1832           \let\next\gobblefour
1833         \fi}%
1834       \next}%
1835     \fi}
1836 \onlypreamble\caption@@@declare sublistentry
\caption@subtypelist An \elt-list containing the subtypes defined with \DeclareCaptionSubType.
1837 \newcommand*\caption@subtypelist{}

\caption@For \caption@For{\langle elt-list\rangle}{\langle code with #1\rangle}
\caption@For*\{\langle elt-list\rangle\}{\langle code with #1\rangle}
1838 \newcommand*\caption@For{\caption@withoptargs\caption@@For}
1839 %\onlypreamble\caption@For
1840 \newcommand\caption@@For[3]{%
1841   \caption@AtBeginDocument#1{%
1842     \def@\elt#1{#3}%
1843     \@nameuse{caption@#2}%
1844     \let@\elt\relax}%
1845 }%\onlypreamble\caption@@For

```

24 subfig package adaptions

We have to make several adaptions to the caption kernel *v1.1* here.

```

1846 \caption@AtBeginDocument{%
1847   \def@\tempa{\@ifstar\sf@\subref\sf@\subref}%
1848   \ifx\subref\@tempa
1849     \caption@InfoNoLine{subfig package 1.2 or 1.3 is loaded}%

```

```

1850 \let\caption@setfloattype\@gobble
1851 \let\@dottedxxxline\sf@NEW@dottedxxxline
1852 \let\sf@subfloat\sf@NEW@subfloat
1853 \fi
1854 \let\sf@NEW@dottedxxxline\@undefined
1855 \let\sf@NEW@subfloat\@undefined}

1856 \def\sf@NEW@dottedxxxline#1#2#3#4#5#6#7{%
1857 \begingroup
1858   \caption@setfloattype{#1}%
1859   \caption@setoptions{subfloat}%
1860   \caption@setoptions{sub#1}%
1861   \ifnum #3>\@nameuse{c@#2depth}\else
1862     \@dottedtocline{\z@}{#4}{#5}{#6}{#7}%
1863   \fi
1864 \endgroup}

1865 \def\sf@NEW@subfloat{%
1866 \begingroup
1867   \caption@setfloattype\@capttype
1868   \sf@ifpositiontop{%
1869     \maincaptiontoptrue
1870   }{%
1871     \maincaptiontopfalse
1872   }%
1873   \caption@setoptions{subfloat}%
1874   \caption@setoptions{sub\@capttype}%
1875   \let\sf@oldlabel=\label
1876   \let\label=\subfloat@label
1877   \ifmaincaptiontop\else
1878     \advance\@nameuse{c@\@capttype}\@ne
1879   \fi
1880   \refstepcounter{sub\@capttype}%
1881   \setcounter{sub\@capttype}{\value{sub\@capttype}}%
1882   \@ifnextchar [{}{ }]{\match left bracket
1883     {\subfloat}%
1884     {\subfloat[\empty]}{}}

```

References

- [1] Anne Brüggemann-Klein:
Einführung in die Dokumentverarbeitung,
B.G. Teubner, Stuttgart, 1989
- [2] Sebastian Rahtz & Heiko Oberdiek:
Hypertext marks in L^AT_EX,
November 12, 2007
- [3] Heiko Oberdiek:
The refcount package,
2006/02/20
- [4] Donald Arseneau:
Three part tables: title, tabular environment, notes,
2003/06/13