

the chemmacros bundle

v4.0 2013/07/06


packages **chemmacros** (v4.0), **chemformula** (v4.0), **ghsystem** (v4.0) and
chemgreek (v0.1a)

documentation for the **chemgreek** package

Clemens NIEDERBERGER

<https://bitbucket.org/cgnieder/chemmacros/>
contact@mychemistry.eu

English documentation



Contents

| | | | |
|---|---|---|---|
| | 4 | Predefined Mappings and Selection of a Mapping | 3 |
| 1 | 1 | Introduction | |
| 2 | 2 | Licence and Requirements | 4 |
| 3 | 2 | Define Mappings | 5 |
| | 5 | Changing a Specific Symbol in an Existing Mapping | |
| | | Index | |

1 Introduction

The **CHEMGREEK** package is an auxiliary package for other chemistry packages such as **CHEMMACROS**. In chemistry there is often the need for upright greek letters. The **CHEMGREEK** package provides an interface to various other packages that provide upright greek letters. One could mention `textgreek`,¹ `upgreek`,² `newtx`³ or `kpfonts`.⁴ All of these packages provide upright greek letters, some a whole alphabet some only the upright variants of the standard italic symbols for which macros are defined in base \LaTeX .

CHEMGREEK offers a possibility to map those different interfaces to a unified set of macros for usage in a chemistry package.

¹ on CTAN: `textgreek` ² on CTAN: `upgreek` ³ on CTAN: `newtx` ⁴ on CTAN: `kpfonts`

2 Licence and Requirements

Permission is granted to copy, distribute and/or modify this software under the terms of the L^AT_EX project public license (lppl) version 1.3 or later (<http://www.latex-project.org/lppl.txt>). The package has the status “maintained.”

CHEMGREEK loads the following packages: `expl3`⁵ and `xparse`.⁶

3 Define Mappings

CHEMGREEK’s main commands are:

`\newchemgreekmapping{<name>}{<mapping list>}`

Add a new mapping to **CHEMGREEK**. Issue an error if it already exists.

`\renewchemgreekmapping{<name>}{<mapping list>}`

Renew a **CHEMGREEK** mapping. Issue an error if it doesn’t exist yet.

`\newchemgreekmapping{<name>}{<mapping list>}`

Declare a new mapping to **CHEMGREEK**. If the mapping already exists it will be overwritten.

The command `\newchemgreekmapping` needs to get a comma separated list of 24 pairs divided by a slash. The first entry is the lowercase version und the second the uppercase version for the corresponding greek letter at the current position. This will become clearer if you look at how the default mapping is defined:

```

1 \newchemgreekmapping{default}
2 {
3   \ensuremath{\alpha} / \ensuremath{\mathrm{A}} , % 1: alpha
4   \ensuremath{\beta} / \ensuremath{\mathrm{B}} , % 2: beta
5   \ensuremath{\gamma} / \ensuremath{\mathrm{\Gamma}} , % 3: gamma
6   \ensuremath{\delta} / \ensuremath{\mathrm{\Delta}} , % 4: delta
7   \ensuremath{\epsilon} / \ensuremath{\mathrm{E}} , % 5: epsilon
8   \ensuremath{\zeta} / \ensuremath{\mathrm{Z}} , % 6: zeta
9   \ensuremath{\eta} / \ensuremath{\mathrm{H}} , % 7: eta
10  \ensuremath{\theta} / \ensuremath{\mathrm{\Theta}} , % 8: theta
11  \ensuremath{\iota} / \ensuremath{\mathrm{I}} , % 9: iota
12  \ensuremath{\kappa} / \ensuremath{\mathrm{K}} , % 10: kappa
13  \ensuremath{\lambda} / \ensuremath{\mathrm{\Lambda}} , % 11: lambda
14  \ensuremath{\mu} / \ensuremath{\mathrm{M}} , % 12: mu
15  \ensuremath{\nu} / \ensuremath{\mathrm{N}} , % 13: nu
16  \ensuremath{\xi} / \ensuremath{\mathrm{\Xi}} , % 14: xi
17  \ensuremath{o} / \ensuremath{\mathrm{O}} , % 15: omikron
18  \ensuremath{\pi} / \ensuremath{\mathrm{\Pi}} , % 16: pi
19  \ensuremath{\rho} / \ensuremath{\mathrm{P}} , % 17: rho
20  \ensuremath{\sigma} / \ensuremath{\mathrm{\Sigma}} , % 18: sigma
21  \ensuremath{\tau} / \ensuremath{\mathrm{T}} , % 19: tau
22  \ensuremath{\upsilon} / \ensuremath{\mathrm{\Upsilon}} , % 20: upsilon
23  \ensuremath{\phi} / \ensuremath{\mathrm{\Phi}} , % 21: phi
24  \ensuremath{\psi} / \ensuremath{\mathrm{\Psi}} , % 22: psi
25  \ensuremath{\chi} / \ensuremath{\mathrm{X}} , % 23: chi

```

⁵ on CTAN: l3kernel ⁶ on CTAN: l3packages

4 Predefined Mappings and Selection of a Mapping

```

26 \ensuremath{\omega} / \ensuremath{\Omega} % 24: omega
27 }

```

There *must* be 24 pairs of entries, i.e., a complete mapping! Those entries are the ones that will be used by the interface macros. For each letter a pair `\Chemalpha/\ChemAlpha` is defined that uses the entries of the currently active mapping. That means there are 48 (robust) macros defined each beginning with `\Chem...` followed by the lowercase or uppercase name of the Greek letter.

The default mapping is – as you can probably see – *not an upright one*. This is because `CHEMGREEK` will not make any choice for a specific package but let's the user (or another package) choose. The `CHEMMACROS` package for example provides a package option that selects one of the available mappings.

```

1 Default mapping: \Chemphi\ and \ChemPhi, $\phi$ and $\Phi$

Default mapping:  $\phi$  and  $\Phi$ ,  $\phi$  and  $\Phi$ 

```

4 Predefined Mappings and Selection of a Mapping

`CHEMGREEK` predefines some mappings. Some of the mappings require additional packages to be loaded. The mapping names and the required packages are listed in table 1.

| mapping | package |
|-------------|-----------|
| default | — |
| var-default | — |
| textgreek | textgreek |
| upgreek | upgreek |
| newtx | newtxmath |
| kpfonts | kpfonts |

Table 1: Predefined mappings.

A mapping is selected and activated with one of the following commands:

`\activatechemgreekmapping* [<options>] {<name>}`

This command selects and activates the mapping `<name>`. If the star variant is used also the package `<name>` is loaded with options `<options>`. This obviously only makes sense if the package name is the same as the mapping name. The command can only be used in the document preamble.

`\selectchemgreekmapping{<name>}` This command selects and activates the mapping `<name>`. A required package has to be loaded additionally the usual way via `\usepackage` or `\RequirePackage`. The command can be used throughout the document.

```

1 % requires the 'newtxmath' package to be loaded:
2 \Chemphi\ and \ChemPhi, $\phi$ and $\Phi$\par
3 \selectchemgreekmapping{newtx}
4 \Chemphi\ and \ChemPhi, $\upphi$ and $\upPhi$

```

$$\phi \text{ and } \Phi, \phi \text{ and } \Phi$$

$$\phi \text{ and } \Phi, \phi \text{ and } \Phi$$

5 Changing a Specific Symbol in an Existing Mapping

If you should want to change a specific entry of a specific mapping it would be rather tedious to redefine the whole mapping. That is why **CHEMGREEK** provides a command for that purpose:

`\changechemgreksymbol{<mapping name>}{upper|lower}{<entry name>}{<entry>}`

Changes the upper- or lowercase entry <entry name> in the mapping <mapping name>.

In order to activate the change you need to (re-) activate the affected mapping afterwards:

```

1 \changechemgreksymbol{default}{lower}{alpha}{xxx}
2 \selectchemgrekmapping{default}
3 \Chemalpha
xxx

```

Index

Section titles are indicated **bold**,
packages sans serif, commands
`\brown`, options `yellow` and
modules (only `CHEMMACROS`)
`blue`.

A

`\activatechemgreekmapping` .. 3

C

`\changechemgreeksymbol` 4

`\ChemAlpha` 3

`\Chemalpha` 3

E

`expl3` 2

K

`kpfonts` 1, 3

N

`\newchemgreekmapping`..... 2

`newtx`..... 1

`newtxmath`..... 3

R

`\renewchemgreekmapping`..... 2

S

`\selectchemgreekmapping` 3

T

`textgreek`..... 1, 3

U

`upgreek`..... 1, 3

X

`xparse`..... 2