

chemmacros v1.0

2011/05/15

Clemens NIEDERBERGER

<http://www.mychemistry.eu/>
contact@mychemistry.eu

‘chemmacros’ is a collection of macros and commands which are intended to make typesetting chemistry documents faster and more convenient. This includes some nomenclature commands, oxidation numbers, thermodynamic data, newman projections...

Inhaltsverzeichnis

1 Licence, Requirements	2
2 Particles, Ions and a Symbol	3
3 Stereo Descriptors, Nomenclature	4
4 Oxidation Numbers and (real) Charges	5
4.1 Ion Charges	5
4.2 Oxidation Numbers	6
4.3 Partial Charges and similar Stuff	6
5 Redox Reactions	7
6 (Standard) State, Thermodynamics	9
6.1 With ‘siunitx’	9
6.2 State	10
7 Environments for ‘mhchem’	11
8 Newman Projections	12
9 p-Orbitals	14
10 Package Options	15
11 List of Commands	16

1 Licence, Requirements

chemmacros v1.0 underlies the The L^AT_EX project public license (<http://www.latex-project.org/lppl.txt>).

chemmacros internally loads the packages ‘xkeyval’¹, ‘amsmath’² and ‘tikz’ (Ti~~k~~Z = ‘pgf’³). If they’re missing it will cause an error.

The definition of some commands depends on which packages have been loaded *before* chemmacros was loaded. Some commands are only defined if a certain package has

¹<http://www.ctan.org/pkg/xkeyval>

²<http://www.ctan.org/pkg/amsmath>

³<http://www.ctan.org/pkg/pgf>

been loaded. This concern the packages ‘mhchem’⁴, ‘siunitx’⁵ and ‘chemstyle’⁶ and the commands from section 2, \ox (section 4.2), the commands from section 6 and the environments drom section 7.

The package option `xspace` (section 10) needs the package ‘xspace’⁷ to be available.

If the user loads ‘mhchem’ *before* chemmacros, the packages ‘mathtools’⁸ and ‘environ’⁹ are needed.

The \redox command (section 5) and the \newman command (section 8 need the tikz library ‘calc’ to be loaded.

The full functionality should be guaranteed with a preamble like this:

```
1 \usepackage{siunitx,chemstyle}
2 \usepackage[version=3,arrows=pgf]{mhchem}
3 \usepackage[xspace=true]{chemmacros}
4 \usetikzlibrary{calc}
```

2 Particles, Ions and a Symbol

Some simple macros for displaying often needed particles and a symbol:

- \Hpl H[⊕] (proton)
- \Hyd OH[⊖] (hydroxide)
- \HtO H₃O[⊕] (oxonium)
- \el e[⊖] (electron)
- \prt p[⊕] (proton)
- \ntr n⁰ (neutron)
- \transitionstatesymbol ≠ transition state symbol (uses Ti~~k~~Z)

⁴<http://www.ctan.org/pkg/mhchem>

⁵<http://www.ctan.org/pkg/siunitx>

⁶<http://www.ctan.org/pkg/chemstyle>

⁷<http://www.ctan.org/pkg/xspace>

⁸<http://www.ctan.org/pkg/mathtools>

⁹<http://www.ctan.org/pkg/environ>

These commands are working both in text mode and math mode. Depending on whether ‘mhchem’ has been loaded, the first three particles are defined with the `\cf{}` command or with `\ensuremath{\text{}}`.

3 Stereo Descriptors, Nomenclature

The following macros are intended to make the writing of IUPAC names more convenient:

- Cahn-Ingold-Prelog:
 - `\Rcip` (*R*)
 - `\Scip` (*S*)
 - `\cip{<conf>}` e.g.: `\cip{R,S}` (*R,S*)
- Fischer:
 - `\Dfi` D
 - `\Lfi` L
- cis/trans & zusammen/entgegen:
 - `\Z` (*Z*)
 - `\E` (*E*)
 - `\cis` *cis*
 - `\trans` *trans*
- ortho/meta/para:
 - `\ortho` *o*
 - `\meta` *m*
 - `\para` *p*

absolute configuration (uses *TikZ*):

- $\backslash Rconf[<letter>] \backslash Rconf: (R) \backslash Rconf[]: (S)$
 - $\backslash Sconf[<letter>] \backslash Sconf: (S) \backslash Sconf[]: (R)$
- 1 \Dfi-Weinsäure = \cip{2S,3S}-Weinsäure, \Dfi-(\$-\$)-Threose = \cip{2S,3R}-(\$-\$)-2,3,4-Trihydroxybutanal\\
- 2 \cis-2-Buten = \Z-2-Butene, \cip{2E,4Z}-Hexadiene\\
- 3 \meta-Xylol = 1,3-Dimethylbenzene
- 4 % with 'bpchem' command \IUPAC:
- 5 \IUPAC{\Dfi-Wein\|säure} = \IUPAC{\cip{2S,3S}-Wein\|säure}, \IUPAC{\Dfi-(\$-\$)-Threose} = \IUPAC{\cip{2S,3R}-(\$-\$)-2,3,4-Tri\|hydroxy\|butanal}

D-Weinsäure = (2S,3S)-Weinsäure, D-(-)-Threose = (2S,3R)-(-)-2,3,4-Trihydroxybutanal
cis-2-Buten = (Z)-2-Butene, (2E,4Z)-Hexadiene
m-Xylol = 1,3-Dimethylbenzene

D-Weinsäure = (2S,3S)-Weinsäure, D-(-)-Threose = (2S,3R)-(-)-2,3,4-Trihydroxybutanal

The last example uses the \IUPAC command, which is provided by the ‘bpchem’¹⁰ package.

4 Oxidation Numbers and (real) Charges

4.1 Ion Charges

Simple displaying of charges:

- \pch[<number>] positive charge (**p**lus + **charge**), \pch, Na\pch, Ca\pch[2] \oplus , Na \oplus , Ca $^{2\oplus}$
- \mch[<number>] negative charge (**m**inus + **charge**), \mch, F\mch, S\mch[2] \ominus , F \ominus , S $^{2\ominus}$

¹⁰<http://www.ctan.org/pkg/bpchem>

4.2 Oxidation Numbers

Typesetting oxidation numbers:

- `\ox{<number>,<atom>}` places `<number>` above `<atom>`; `\ox{+1,Na}`, `\ox{+I,Na}`,
`\ox{-2,S}`, `\ox{-II,S}` $\overset{+1}{\text{Na}}$, $\overset{+I}{\text{Na}}$, $\overset{-2}{\text{S}}$, $\overset{-II}{\text{S}}$

If the package ‘mhchem’ has been loaded $\text{\textless atom\textgreater}$ is set inside the \ce command: \ce{[+II,-I]{Ca}\ce{ox}{-I,F2} CaF2}. Without ‘mhchem’ this isn’t working this way (CaF2) and you need to use the math way: \ce{[+II,Ca]\ce{ox}{-I,F\$-_2\$} CaF2}.

4.3 Partial Charges and similar Stuff

The next ones probably are seldomly needed but nevertheless useful:


- $\backslash\text{delp}$ $\delta\oplus$ (**delta + plus**)
 - $\backslash\text{delm}$ $\delta\ominus$ (**delta + minus**)

These macros for example can be used with the `\ox` command or with the ‘chemfig’¹¹ package:

```

1 \ox{\delp,H}\ox{\delm,C1}\par
2 \chemfig{\chemabove[3pt]{\lewis{246,Br}}{\delm}-\chemabove[3pt]{H}{\delp}}

```



Also the following macros are useful together with ‘chemfig’:

- $\backslash \text{scrp} \oplus (\text{scriptstyle} + \text{plus})$
 - $\backslash \text{scrm} \ominus (\text{scriptstyle} + \text{minus})$

For example:

¹¹ <http://www.ctan.org/pkg/chemfig>

```

1 {\setatomsep{1.8em}\chemfig{CH_3-CH_2-\chemabove{\lewis
{026,0}}{\hspace{5mm}\text{scrn}}}}

```



5 Redox Reactions

chemmacros provides two commands ¹² to visualize the transfer of electrons in redox reactions. Both commands are using ‘*TikZ*’, the second also needs the *tikz* library ‘*calc*’, which thus must be loaded in the preamble.

```

1 \OX{<name>,<atom>}
2 \redox(<name1>,<name2>) [<tikz>] [<dim>]{<text>}

```

\OX places *<atom>* into a node, which is named with *<name>*. If you have set two\OX, they can be connected with a line using \redox. To do so the names of the two nodes that shall be connected are written in the round braces. Since \redox draw a tikzpicture with options *remember picture,overlay*, the document needs to be *compiled at least two times*.

```

1 \OX{a,Na} $\rightarrow \OX{b,Na}\poch\redox(a,b) {
  oxidation
  \begin{tikzpicture}[remember picture, overlay]
    \draw[red, ->, very thick] (a) -- (b);
    \node[below=1.5ex] at (a) {Na → Na⊕};
  \end{tikzpicture}
}
```

This line can be customized using *TikZ* keys in *<tikz>*:

```

1 \OX{a,Na} $\rightarrow \OX{b,Na}\poch\redox(a,b) [->,red] {
  ox
  \begin{tikzpicture}[remember picture, overlay]
    \draw[red, ->, very thick] (a) -- (b);
    \node[below=1.5ex] at (a) {Na → Na⊕};
  \end{tikzpicture}
}
```


<dim> can be used to adjust the length of the vertical line. The default value is *.6em*. If you use a negative value the line is placed *below* the text.

```

1 \begin{center}
2 \OX{a,Na} $\rightarrow \OX{b,Na}\poch\redox(a,b) [->,red
  ]{ox}\redox(a,b)[->,blue][-.6em]{red}
3 \end{center}

```

¹²Thanks to Peter Cao who suggested the feature.




Both commands also can be used with the ‘mhchem’ command `\ce` and with the `\ox` command (section 4.2).



```

1 \ce{ 2 \OX{o1,Na} + \OX{r1,Cl2} -> 2 \OX{o2,Na}\pch + 2 \
      \OX{r2,Cl}\mch }
2 \redox(o1,o2){\small OX: $- 2\el$}
3 \redox(r1,r2)[][-.6em]{\small RED: $+ 2\el$}
4
5 \vskip2cm
6 \ce{ 2 \OX{o1,\ox{0,Na}} + \OX{r1,\ox{0,Cl2}} -> 2 \OX{o
      2,\ox{+I,Na}}\pch + 2 \OX{r2,\ox{-I,Cl}}\mch }
7 \redox(o1,o2){\small OX: $- 2\el$}
8 \redox(r1,r2)[][-.6em]{\small RED: $+ 2\el$}
9
10 \vskip3cm
11 \ce{ 2 \OX{o1,\ox{0,Na}} + \OX{r1,\ox{0,Cl2}} -> 2 \OX{o
      2,\ox{+I,Na}}\pch + 2 \OX{r2,\ox{-I,Cl}}\mch }
12 \redox(o1,o2)[draw=red,->][2em]{\small OX: $- 2\el$}
13 \redox(r1,r2)[draw=blue,->]{\small RED: $+ 2\el$}
14
15 \vskip1cm
16 \ce{ 2 \OX{o1,\ox{0,Na}} + \OX{r1,\ox{0,Cl2}} -> 2 \OX{o
      2,\ox{+I,Na}}\pch + 2 \OX{r2,\ox{-I,Cl}}\mch }
17 \redox(o1,o2)[green,-stealth]{\small OX: $- 2\el$}
18 \redox(r1,r2)[purple,-stealth][-.6em]{\small RED: $+ 2\el$}
$}
OX:  $-2e^{\ominus}$ 

$$2 \text{Na} + \text{Cl}_2 \longrightarrow 2 \text{Na}^{\oplus} + 2 \text{Cl}^{\ominus}$$

RED:  $+2e^{\ominus}$ 
```





6 (Standard) State, Thermodynamics

6.1 With ‘siunitx’

If the package ‘siunitx’ has been loaded, the following commands are available:

- `\Enthalpy[<kind>, <exponent>, <unit>]{<value>}`
- `\Entropy[<kind>, <exponent>, <unit>]{<value>}`
- `\Gibbs[<kind>, <exponent>, <unit>]{<value>}`

Their usage is pretty much self-explaining: `\Enthalpy{-123.4}` gives $\Delta H^\circ = -123.4 \text{ kJ mol}^{-1}$.

If you want to specify what kind of enthalpy (reaction, formation,...) is meant Möchte
you can use the first optional argument:

`\Enthalpy[r]{-123.4} $\Delta_r H^\circ = -123.4 \text{ kJ mol}^{-1}$.`

The standard state symbol can be replaced by the second optional argument...

`\Enthalpy[, o]{-123.4} $\Delta H^\circ = -123.4 \text{ kJ mol}^{-1}$`

...and is anyway only set as standard state if the package ‘chemstyle’ has been loaded,
see section 6.2.

The third optional argument can be used to change the unit:

`\Enthalpy[, kcal/mol]{-123.4} $\Delta H^\circ = -123.4 \text{ kcal/mol}$`

The unit is set corresponding to the rules of ‘siunitx’ and depends on its settings:

```

1  \Enthalpy{-1234.56e3}\par
2  \sisetup{per-mode=symbol, exponent-product=\cdot, output-
           decimal-marker={,}, group-four-digits=true}
3  \Enthalpy{-1234.56e3}

```

$$\Delta H^\circ = -1234.56 \times 10^3 \text{ kJ mol}^{-1}$$

$$\Delta H^\circ = -1\,234,56 \cdot 10^3 \text{ kJ/mol}$$

The other two commands work exactly the same way.

```
1 \Entropy{12.3}, \Gibbs{-12.3}.
```

$$S^\circ = 12.3 \text{ J K}^{-1} \text{ mol}^{-1}, \Delta G^\circ = -12.3 \text{ kJ mol}^{-1}.$$

You can use the command `\setnewstate[<standard exponent>, <Delta symbol>]{<name>}{<symbol>}{<unit>}` to create new corresponding commands:

```
1 \setnewstate{Helmholtz}{A}{\kilo\joule\per\mole}
2 \setnewstate{ElPot}{E}{Volt}
3 \Helmholtz{123.4} \ElPot{-1.1}
```

$$\Delta A^\circ = 123.4 \text{ kJ mol}^{-1} \quad \Delta E^\circ = -1.1 \text{ Volt}$$

Indeed, the commands

```
1 \Enthalpy, \Entropy, \Gibbs
```

are defined as follows:

```
1 \setnewstate{Enthalpy}{H}{\kilo\joule\per\mole}
2 \setnewstate[, ]{Entropy}{S}{\joule\per\kelvin\per\mole}
3 \setnewstate{Gibbs}{G}{\kilo\joule\per\mole}
```

With `\setnewstate` you also can redefine the existing commands:

```
1 \setnewstate{Enthalpy}{X}{\joule\per\mole}
2 \Enthalpy[f]{12.5}
```

$$\Delta_f X^\circ = 12.5 \text{ J mol}^{-1}$$

6.2 State

The commands presented in section 6.1 internally all use the command

```
1 \State[<exponent>, <Delta symbol>]{<symbol>}{<kind>}
```

which also is available without ‘siunitx’. It can be used to write the thermodynamic variables without value and unit.

```
1 \State[G]{f}, \State[ ]{E}{}, \State[\SI{1000}{\celsius}]{H}{f}, \State[ ,\delta]{+}{}
```

$$\Delta_f G^\circ, \Delta E, \Delta_f H^{1000\text{ }^\circ\text{C}}, \delta +$$

The standard state symbol \circ is only used, if the ‘chemstyle’ package has been loaded, which provides it through the command `\standardstate`. With ‘chemstyle’: $\text{\State}\{A\}\{b\} \Delta_b A^\circ$, without: $\Delta_b A$.

7 Environments for ‘mhchem’

If the package ‘mhchem’ has been loaded the environments

```

1 \begin{reaction}
2   <mhchem code>
3 \end{reaction}
4 \begin{reactions}
5   <mhchem code>
6 \end{reactions}
```

and the starred versions

```

1 \begin{reaction*}
2   <mhchem code>
3 \end{reaction*}
4 \begin{reactions*}
5   <mhchem code>
6 \end{reactions*}
```

are defined. `reaction/reaction*` uses the math environment `equation/equation*` and `reactions/reactions*` uses the math environment `align/align*` to display the reactions.

```


1 reaction with counter:
2 \begin{reaction}
3   H2 + 1/2 O2 -> H2O
4 \end{reaction}
5 reaction without counter:
6 \begin{reaction*}
7   C + O2 -> CO2
8 \end{reaction*}
9 several aligned reactions with counter:
10 \begin{reactions}
11   Cl2 &-> 2 Cl. \\
12   Cl.{} + CH4 &-> HCl + {}.CH3\\
```

```


13  {}{}.CH3 + Cl2 &-> CH3Cl + Cl.
14 \end{reactions}
15 several aligned reactions without counter:
16 \begin{reactions*}
17 \Hpl + \Hyd &lt;=> H2O \\
18 SO4 \mch[2] + Ba \pch[2] &-> BaSO4 v
19 \end{reactions*}

```


reaction with counter:




reaction without counter:



several aligned reactions with counter:



several aligned reactions without counter:



If you want to change the layout of the counter tags, you can use `\renewtagform{<tagname>}[<format>]{<right delim>}{<left delim>}`¹³.

```

1 \renewtagform{CMreaction}[R \textbf{textbf}]{[]{}}
2 \begin{reaction}
3 H2O + CO2 <<=> H2CO3
4 \end{reaction}

```



8 Newman Projections

The command

```
1 \newman[<angle>,<scale>,<tikz>]{<1>,<2>,<3>,<4>,<5>,<6>}
```





¹³provided by the package ‘mathtools’

allows you to create newman projections (uses *TikZ*). You need to load the *tikz* library ‘*calc*’ for that:

```
1 \usetikzlibrary{calc}
```


Examples:

```
1 \newman{}\par% default: staggered
2 \newman[165]{}\par% rotated by 165 degrees => eclipsed
3 \newman{1,2,3,4,5,6} \newman{1,2,3} \newman{,,,4,5,6}\par
    % with atoms
4 \newman[,.75,draw=blue,fill=blue!20]{}% scaled and
    customized with TikZ
```



Another option allows you to customize the nodes within which the atoms are placed:

```
1 \newman[] [<tikz nodes>]{<1>,<2>,<3>,<4>,<5>,<6>}
2 % example:
3 \newman[] [draw=red,fill=red!20,inner sep=2pt,rounded
corners]{1,2,3,4,5,6}
```




If you want to display the "frontatoms differently from the "backatoms, you can use a third option:

```

1 \newman[] [<tikz front nodes>][[<tikz back nodes
>]]{<1>,<2>,<3>,<4>,<5>,<6>}
2 % example:
3 \newman[] [draw=red,fill=red!20,inner sep=2pt,rounded
corners][draw=blue,fill=blue!20,inner sep=2pt,rounded
corners]{1,2,3,4,5,6} \newman[170][draw=red,fill=red
!20,inner sep=2pt,rounded corners][draw=blue,fill=blue
!20,inner sep=2pt,rounded corners]{1,2,3,4,5,6}

```



9 p-Orbitals

chemmacros provides commands to visualize p-orbitals.

```

1 \porb[<size factor>,<color>,<angle>]
2 \phorb[<size factor>,<color>,<angle>]
3 \setorbheight{<length>}


```

This displays a horizontal orbital or one rotated by <angle>: \porb \qquad \porb[, ,30]

\phorb only displays one half orbital: \phorb[, red, 90]

There are shortcuts for the x-, y- and z-orbitals:

```
1 \pzorb \qquad \pyorb \qquad \pxorb
```



With suitable shifting you can display them all on one spot:


```

1 \hspace{2cm}\pxorb\hspace{-.3em}\pyorb\hspace{-.3em}\
2   pzorb
3 \tikz[overlay]{
4   \draw[->](0,0)--(1,0)node[right]{$y$};
5   \draw[dashed](0,0)--(-1,0);
6   \draw[->](0,0)--(0,1)node[above]{$z$};
7   \draw[dashed](0,0)--(0,-1);
8   \draw[->](0,0)--(-.707,-.707)node[below left]{$x$};
9 }
```

The orbitals also can be used together with ‘chemfig’:

```

1 \setorbheight{2em}\setbondoffset{0pt}
2 \chemfig{?\pzorb-[,1.3]\pzorb-[:30,1.1]\pzorb-[:150,.9]\
3   pzorb-[4,1.3]\pzorb-[:-150,1.1]\pzorb?}\quad
4 \chemfig{?\pzorb-[,1.3]{\porb[,, -90]}-[:30,1.1]\pzorb
5   -[:150,.9]{\porb[,, -90]}-[4,1.3]\pzorb-[:-150,1.1]{\
6     \porb[,, -90]}?}
```



10 Package Options

chemmacros has two package options:

- **xspace=<boolean>** With the option `xspace=true` the commands `\Hyd`, `\HtO`, `\Hyd`, `\HtO`, `\OH`, `\H3O`, `\OH`, `\H3O`, `\Text`

get a `\xspace`.

Default: `xspace=false`

- `circled=<boolean>` not everybody likes circled charge symbols (\oplus and \ominus). Some prefer them without circles (+ and -). This can be chosen this option. With `circled=false` all chemmacros commands are set without circles.

Default: `circled=true`

11 List of Commands

<code>\el, \prt, \ntr \HtO, \Hpl, \Hyd \transitionstatesymbol</code>	section 2: Particles, Ions and a Symbol
<code>\cip, \Rcip, \Scip \Dfi, \Lfi \E, \Z, \cis, \trans \Rconf, \Sconf \ortho, \meta, \para</code>	section 3: Stereo Descriptors, Nomenclature
<code>\delm, \delp \mch, \pch \ox \scrm, \scrp</code>	section 4: Oxidation Numbers and (real) Charges
<code>\Enthalpy, \Entropy, \Gibbs \setnewstate \State</code>	section 6: (Standard) State, Thermodynamics
<code>\newman</code>	section 8: Newman Projections
<code>\redox, \OX</code>	section 5: Redox Reactions
<code>\begin{reaction}, \begin{reaction*}, \begin{reactions}, \begin{reactions*}</code>	section 7: Environments for ‘mhchem’
<code>\phorb, \porb, \pxorb, \pyorb, \pzorb \setorbheight</code>	section 9: p-Orbitals