

chemstyle — Writing chemistry with style^{*}

Joseph Wright[†]

Released 2008/08/18

Abstract

The chemstyle package provides a “one-stop shop” for setting up formatting of L^AT_EX documents following the editorial policies of various chemical journals. It provides a number of handy chemistry-related commands, and loads several support packages to aid the chemist.

Contents

1	Introduction	2	7	The package code	8
			7.1	Setup code	8
2	Style options for chemstyle	2	7.2	Option handling	8
	2.1 Creating styles	3	7.3	Extra units	10
	2.2 Package options	3	7.4	Standard state symbol . .	11
3	Naming of the references section	3	7.5	Alkyl radicals	11
			7.6	Float formatting	12
			7.7	Cross-references	12
			7.8	Latin phrases	12
			7.9	Loading the style definition	14
			7.10	Handling reference section naming	14
4	Additional macros	4	8	Configuration files	16
	4.1 Additional units	4	8.1	RSC style	16
	4.2 The standard state symbol	4	8.2	<i>Angew. Chem.</i> style . . .	17
	4.3 Alkyl radicals	4	8.3	<i>J. Organomet. Chem.</i> style	17
	4.4 Latin phrases	5	8.4	<i>Tetrahedron Lett.</i> style . .	17
5	Additional information	6	8.5	<i>J. Am. Chem. Soc.</i> style .	18
	5.1 Advice for users of the rsc package	6	8.6	<i>Inorg. Chem.</i> style	18
	5.2 Interactions with other packages	6	8.7	<i>J. Phys. Chem.</i> style	18
	5.3 Captions above floats	6	8.8	<i>Org. Lett.</i> style	18
			8.9	The empty style — none	20
6	A template for chemical articles	7	9	Change History	20
			10	Index	21

^{*}This file describes version v1.3c, last revised 2008/08/18.

[†]E-mail: joseph.wright@morningstar2.co.uk

Table 1: Styles provided by chemstyle

Option	Journals using this style
none	Not applicable
angew	<i>Angew. Chem., Chem. Eur. J.</i>
jomc	<i>J. Organomet. Chem., Coord. Chem. Rev.</i>
ic	<i>Inorg. Chem.</i>
jacs	<i>J. Am. Chem. Soc.</i>
jcp	<i>J. Phys. Chem. A, J. Phys. Chem. B</i>
orglett	<i>Org. Lett.</i>
rsc	<i>Chem. Commun., Org. Biomol. Chem.</i> <i>Dalton Trans.</i>
tetlett	<i>Tetrahedron, Tetrahedron Lett.</i>

1 Introduction

The aim of chemstyle is to provide a quick method to set up various document parameters (such as caption formatting), simply by specifying the model journal. The package has also been designed to allow rapid addition of new journal styles. Each style definition is a separate file, and new styles can be added very readily. chemstyle has grown out of the rsc package, which had a similar aim but was much more limited (and less robustly implemented). The chemstyle package is also designed with the use of biblatex in mind: the rsc package is closely bound to traditional BibTeX use.

As a successor to the rsc package, chemstyle provides a range of chemistry-related additional macros. The set provided here is an extended version of those provided by rsc. Everything that can be done using the rsc L^AT_EX package is therefore possible using the chemstyle package.

The formatting system provided by chemstyle are intended for writing a variety of documents. Thus the stylistic changes made by the package do not seek to reproduce the appearance of printed journal articles. The package aims to be suitable for use in preparing drafts of papers, but also for writing reports, theses and so on.

2 Style options for chemstyle

journal chemstyle should be loaded with a package option specifying which journal style to follow. Currently, chemstyle is aware of the styles listed in Table 1. New styles can be developed by creating a new file modelled on the existing definitions; chemstyle will automatically search for correctly-named styles. The style files provided with chemstyle have been derived from current practice in the target journals. It is not always easy to pick the correct stylistic settings from (sometimes inconsistent) real-world examples. The package author welcomes feedback on the styles provided.

The none style is notable as it is not based on a journal. Instead this is a minimal style, which provides the additional commands without making formatting changes. It is also the default style if no option is given. This

document has been compiled implicitly using the `none` option, for example.

2.1 Creating styles

The process of creating a new styles for `chemstyle` is intended to be relatively easy. New styles should be saved as files with the extension `.jdf` (standing for Journal Definition File), and should be saved somewhere in the path searched by `\TeX`.¹ The definition files included in the package should provide a guide to the basic options available for producing new styles. Arbitrary `\TeX` commands can be included, if they are necessary for a particular style. For example, other packages can be loaded in `\usepackage`.

The maintainer of `chemstyle` is happy to add new styles to the package, either by contribution by users or on request (when he has sufficient time!). If you have a new style to add (or corrections to an existing one), please contact the package author.

2.2 Package options

<code>journal</code>	As of version 1.2, <code>chemstyle</code> uses the <code>keyval</code> system for option management. The choice of journal style can therefore be given as a normal option or by using the key <code>journal=</code> . The other package options provided by the package are described as they arise in the documentation.
<code>\cstsetup</code>	Some of the package options can only be set when loading the package. The choice of journal style is one of these. Others can be altered anywhere in the document, using the <code>\cstsetup</code> macro. This accepts a <code>keyval</code> list and processes it as needed.
<code>chemcompounds</code>	<code>chemstyle</code> loads the <code>chemscheme</code> package, and therefore will pass through the <code>chemcompounds</code> option. It can also request floats are created either by <code>float</code> or <code>floatrow</code> ; this is controlled by the <code>floatrow</code> option. Setting <code>floatrow=false</code> means that <code>float</code> is used to generate floats; the default value is <code>true</code> .
<code>floatrow</code>	
<code>notes</code>	
<code>nonotes</code>	

3 Naming of the references section

`chemstyle` alters the naming of the references section of a document. By default, `chemstyle` alters the value of `\bibname` or `\refname` (as appropriate) to the form of words chosen by the target journal for the “References” section.

The “Notes and References” naming commands are language-aware, *via* the `babel` interface. Currently, `chemstyle` includes appropriate labels for `babel` languages `english`, `UKenglish`, `ngerman` and `french`. Other languages can be added if appropriate wordings are provided to the author. The naming system is designed to work correctly with both `natbib` and `biblatex`.

The package recognises the `notes` option for controlling how the references section is named. The accepts the values `true`, `false` and `auto`. The Boolean values either enable or disable the addition of “Notes and” to the “References” of the section title. The `auto` option works in conjunction with the `notes2bib` package. If notes are added, “Notes and” is included in the section title, whereas

¹Depending on your `\TeX` distribution, you may need to rebuild your file database after creating a new style. For `MiK\TeX` users, this can be done graphically or by typing `mpm -update-db` at the command line; for `TeXLive`, run `texhash`.

`notesbefore`

if no notes are given the section title remains as “References”. The `nonotes` option is equivalent to `notes=false`.

The second option for this area is `notesbefore`. This takes `true` and `false` only, and sets whether “Notes and References” or “References and Notes” is produced.

4 Additional macros

4.1 Additional units

`\Hz`
`\mmHg`
`\molar`
`\Molar`
`\cmc`

`10\Hz`
`20\mmHg`
`30\mol\dm^{-3}`
`40\m`
`50\cm^3`

`\SI{10}{\Hz} \\`
`\SI{20}{\mmHg} \\`
`\SI{30}{\molar} \\`
`\SI{40}{\Molar} \\`
`\SI{50}{\cmc}`

4.2 The standard state symbol

`\standardstate`

Related to the above, but not exactly a unit is the `\standardstate` command.² This generates the tricky `\standardstate` symbol. The symbol will adapt to local sizing.

the standard conditions are indicated:
⊖
Common but not correct: ΔG_f° or
 ΔG_f^\diamond
Better: $\Delta_f G^\circ$
Sizing: $\int_{T^\circ}^{T_{\text{out}}}$

the standard conditions are indicated: `\standardstate`
Common but not correct:
`$\Delta G_{\mathit{f}}^{\circ}\standardstate$` or
`$\Delta G_{\mathit{f}}^{\diamond}\standardstate$`
Better:
`$\Delta_f G^{\circ}\standardstate$`
Sizing:
`$\int^{\mathit{T}_{\text{out}}}_{T^\circ}\standardstate$`

4.3 Alkyl radicals

`\nPr`
`\iPr`
`\nBu`
`\iBu`
`\sBu`

There are a few alkyl radicals that come up all of the time. No one seems to have put these into a package, so they are provided here. As you would expect, `\iPr` gives *i*-Pr, `\iBu` gives *i*-Bu and `\tBu` gives *t*-Bu, and so on. The style of the output depends on the journal style specified; most journals seem to favour one version of the abbreviation.

The `\alkyl` group could be *n*-Pr, *i*-Pr or *n*-Bu without affecting the selectivity.

The alkyl group could be `\nPr`, `\iPr` or `\nBu` without affecting the selectivity.

`xspace`

When `chemstyle` is loaded using the `xspace` option, the `xspace` package is

²The `\standardstate` macro is only defined if the user does not have their own version.

`radhyphen`
`rademph`
`radsuper`
`radprefix`

`iPr tBu`
`Bu-i Bu-s`

automatically used to add space after the command names, so that `\iPr` group will result in “*i-Pr* group” being typeset.

The appearance of these radical abbreviations is controlled by the package options `radhyphen`, `rademph`, `radsuper` and `radprefix`. The journal styles set these automatically, but they can be redefined at any point. The options work as might be expected, and are Boolean switches.

```
\cstsetup{radhyphen=false, radsuper=true} \\
\iPr \tBu
\cstsetup{radhyphen=true, radsuper=false, %
           radprefix=false, rademph=false} \\
\iBu \sBu
```

4.4 Latin phrases

`\latin`
`\etc`
`\eg`
`\ie`
`\etal`
`\invacuo`
`abbrmeph`

et al. or *in vacuo* plus some text
i.e. equals e.g. perhaps etc.

The various Latin phrases commonly used in chemistry are made available as the obvious commands. By altering the definition of `\latin`, this allows ready switching from italic to Roman typesetting. Notice that `\etc`, `\ie` and `\eg` are aware of trailing periods, and so doubling-up should not occur. Once again, these macros use `xspace` when given as a package option to handle automatic addition of spaces after these phrases.

The use of italic for these abbreviations is set by altering the package option `abbrmeph`, which takes values `true` and `false`.

```
\etal or \invacuo plus \latin{some text} \\
\cstsetup{abbrmeph=false}
\ie equals \eg perhaps \etc
```

`abbrcomma`

e.g. this
i.e., that

For American journals, where it is obligatory to follow “*e.g.*” and “*i.e.*” with a comma, the package provides a mechanism for handling this automatically. Thus, when using an appropriate journal style, `\eg`, `\eg.` and `\eg,` will all result in typesetting “*e.g.*”. The Boolean package option `abbrcomma` controls this.

```
\eg this \\
\cstsetup{abbrcomma=true}
\ie that
```

The `\etc` and `\etal` commands are set up on the assumption that they come at the end of a sentence. Hence the spacing after these will default to an inter-sentence space. If you desire an inter-word space, use the normal methods

etc. more text
et al. have shown

```
\etc\ more text \\
\etal~have shown
```

`nophrases`

`\latinemphon`
`\latinemphoff`

The definitions of all of the phrases are designed not to overwrite any given by the user *in the preamble*. So, if you have your own `\latin` macro, it will be used even if you load `chemstyle`. If you encounter any problems, try loading the package with the `nophrases` option; this option prevents the package even trying to define any of the phrase macros.

For backward-compatibility with previous versions of `chemstyle`, the macros `\latinemphon` and `\latinemphoff` are provided. These work as would be expected, to alter the formatting produced by `\latin`. The more general `keyval` method is now preferred for making this change.

5 Additional information

5.1 Advice for users of the rsc package

The chemstyle package is intended as a replacement for the rsc package. As such, it covers almost everything the the rsc L^AT_EX package does, and more. Users of rsc are strongly encouraged to update to using chemstyle. The bibliography styles provided by rsc will continue to be required, of course. Migration of these styles to biblatex is an on-going project.

5.2 Interactions with other packages

The chemstyle package has been designed to avoid, as far as possible, clashes with other packages. The package requires the presence of the standard graphicx and varioref packages. If these packages need to be loaded with explicit options, this should be done *before* loading chemstyle. The chemscheme package is also needed, as it provides the floating scheme environment essential in synthetic chemistry documents.

5.3 Captions above floats

The scheme float type is generated using either the float or floatrow package. This has the side-effect that the placement of captions for floats does not depend on where the \caption command comes inside the floating environment.³ If you wish to alter the placement of captions, the mechanism of the underlying package will be needed. There are some subtle differences between the two: although floatrow provides the float macros, they are not all 100% compatible. This document is compiled using floatrow, and so to fix the position of captions the following code is appropriate.

```
\begin{table} [ht]
    The float contents
    \caption{A caption below the float contents in the source}
\end{table}
\floatingsetup[table]{style=plain} % When using floatrow
% \floatstyle{plain}
% \restylefloat{table} When using float
\begin{table} [ht]
    The second float contents, which should be above the caption
    \caption{A second caption below the float contents
        in the source}
\end{table}
```

Table 2: A caption below the float contents in the source

The float contents

³Normally this is a good thing.

The second float contents, which should be above the caption

Table 3: A second caption below the float contents in the source

6 A template for chemical articles

This is a very simple template for chemistry-related documents. Hopefully it contains a few extra hints for getting well-formatted documents quickly. For simplicity, the template assumes that the user is writing a thesis for a U.K. university. Hence it uses U.K. defaults and RSC-based styling. Most of the packages used have good documentation, but a brief summary of why they are recommended follows.

```
1 \documentclass[fontsize=10pt,paper=a4,english,UKenglish]
2   {scrreprt}
3 \usepackage{geometry,upgreek,booktabs,babel}
4 \usepackage[journal=rsc,xspace=true]{chemstyle}
5 \usepackage[version=3]{mhchem}
6 \usepackage[footnotes]{notes2bib}
7 \usepackage[final]{microtype}
8 \usepackage[final,inactive]{pst-pdf}
9 \usepackage[colorlinks]{hyperref}
10 \begin{document}
11 Document contents go here
12 \end{document}
```

The versatile KOMA-script bundle provides more advanced versions of the standard document classes. If you want paragraphs separated out, with no indents (a common style for theses), add the `parskip` option to the font and paper size ones given here.

The `babel` system is loaded to sort out hyphenation and so on, and could be useful if there are any foreign-language quotes.

`geometry` allows the users to alter page layout with ease: much better than trying to hack the raw L^AT_EX system. `booktabs` gives much nicer looking tables than the L^AT_EX 2_E default. `upgreek` provides non-italic lowercase Greek letters, which should be used for things such as bond descriptions.

π -bond σ^* -orbital

$\$\\uppi\$$ -bond $\$\\upsigma^*\\$$ -orbital

Load `chemstyle` (of course) to give not only some easy formatting, but also to automatically provide a float type for schemes, thanks to the `chemscheme` package. This also loads either `chemcompounds` or (optionally) `bpchem` to track compound numbers.

The `mhchem` package provides the `\ce` command for rapidly typesetting formulas, so that you can type `\ce{H2SO4}` and get H₂SO₄.⁴

The `microtype` package improves formatting when used with the pdftEX engine. By giving the `final` option, it is active even when using `draft` as a global option.

Using `notes2bib` allows the user to automatically add notes to the bibliography from within the document body. So you can put `\bibnote{A note}` in the

⁴There is a slight cheat here, as this document uses lower-case numerals in the text. The example is written as `\ce{H2SO4}`.

source, and this will move into the References section without any further effort. The `footnotes` option means that footnotes do the same.

Finally, the `hyperref` package makes headings, citations and so on into hyperlinks.

7 The package code

7.1 Setup code

\cst@id First of all, the package identifies itself and loads other packages needed to function. Loading `chemscheme` is deferred until later, to allow processing of options at the correct point.

```
13 \NeedsTeXFormat{LaTeX2e}
14 \def\cst@id$#1: #2.#3 #4 #5-#6-#7 #8 #9${%
15   \def\cst@ver{#5/#6/#7\space v1.3c\space}%
16 \cst@id $Id: chemstyle.dtx 50 2008-08-18 16:21:24Z joseph $%
17 \ProvidesPackage{chemstyle}%
18   [\cst@ver Writing chemistry with style]
```

Packages that are needed under all circumstances are loaded here. There are some limitations on the age of `xkeyval`.

```
19 \RequirePackage{xkeyval}[2005/05/07]
20 \RequirePackage{graphicx,varioref,caption,xspace}
```

\cst@tempa A couple of temporary private macros.

```
21 \newcommand*\cst@tempa{}%
22 \newcommand*\cst@tempb{}%
```

7.2 Option handling

\cst@boolkey Option handling is processed using `xkeyval`. As a number of Boolean keys are needed, a shortcut is handy.

```
23 \newcommand*\cst@boolkey[1]{%
24   \define@boolkey[cst]{opt}{cst@}{#1}{true}{}}
```

\ifcst@chemcompounds The Boolean keys are now defined.

```
25 \cst@boolkey{chemcompounds}
26 \cst@boolkey{floatrow}
27 \cst@boolkey{xspace}
28 \cst@boolkey{phrases}
29 \cst@boolkey{radprefix}
30 \cst@boolkey{rademph}
31 \cst@boolkey{radsuper}
32 \cst@boolkey{radhyphen}
33 \cst@boolkey{abbremph}
34 \cst@boolkey{abbrcomma}
35 \cst@boolkey{notesbefore}
```

\ifcst@notes For notes, some choices are available. These need a bit of testing.

```
36 \newif\ifcst@notes
37 \newif\ifcst@autonotes
  \cst@tempa
  \cst@tempb
```

```

38 \define@choicekey*[cst]{opt}{notes}[\cst@tempa]
39   {true, false, auto}[true]
40   {\cst@notesfalse
41     \cst@autonotesfalse
42     \edef\cst@tempb{auto}
43     \ifx\cst@tempa\cst@tempb
44       \cst@notestrue
45       \cst@autonotestrue
46     \fi
47     \edef\cst@tempb{true}
48     \ifx\cst@tempa\cst@tempb
49       \cst@notestrue
50     \fi}

```

Some old options are no longer needed at all.

```

51 \DeclareOptionX[cst]<opt>{siunits}
52   {\PackageInfo{chemstyle}{Option siunits no longer required}}
53 \DeclareOptionX[cst]<opt>{SIunits}
54   {\PackageInfo{chemstyle}{Option siunits no longer required}}
55 \DeclareOptionX[cst]<opt>{nonotes}
56   {\ExecuteOptionsX[cst]<opt>{notes=false}}
57 \DeclareOptionX[cst]<opt>{nophrases}
58   {\ExecuteOptionsX[cst]<opt>{phrases=false}}

```

\cst@journal The journal option can be given with or without `journal=`.

\cst@language `\cst@language`

```

59 \define@cmdkeys[cst]{opt}[\cst@]{journal,language}
60 \DeclareOptionX*{\edef\cst@journal{\CurrentOption}}

```

The default options are executed, and the user options are processed.

```

61 \setkeys[cst]{opt}{
62   notes=true,
63   phrases=true,
64   chemcompounds=true,
65   xspace=true,
66   floatrow=true,
67   journal=none,
68   radprefix=true,
69   rademph=true,
70   radsuper=false,
71   radhyphen=true,
72   abbrempth=true,
73   abbrcomma=false,
74   language=english,
75   notesbefore=true}
76 \ProcessOptionsX[cst]<opt>

```

With the options processed, those to be passed to `chemscheme` are sorted out.

```

77 \ifcst@chemcompounds
78   \PassOptionsToPackage{chemcompounds}{chemscheme}
79 \fi
80 \ifcst@floatrow
81   \RequirePackage[floats=floatrow]{chemscheme}
82 \else
83   \RequirePackage[floats=float]{chemscheme}
84 \fi

```

\cst@disablekey Some of the options are no longer relevant once the package is loaded. These are disabled here with a suitable message.

```
85 \newcommand*{\cst@disablekey}[1]{%
86   \define@key[cst]{opt}{#1}{\PackageWarning{chemstyle}%
87     {Option '#1' only valid when loading package}}}
88 \AtBeginDocument{%
89   \cst@disablekey{floatrow}%
90   \cst@disablekey{journal}%
91   \cst@disablekey{phrases}%
92   \cst@disablekey{nophrases}%
93   \cst@disablekey{notes}%
94   \cst@disablekey{nonotes}%
95   \cst@disablekey{chemcompounds}}
```

\cstsetup A macro for changing the settings at run-time without needing to know the internals of the package.

```
96 \newcommand*{\cstsetup}[1]{%
97   \iffalse{\fi\ifnum0='}\fi%
98   \setkeys[cst]{opt}{#1}%
99   \ifnum0='{\fi\iffalse}\fi}
```

7.3 Extra units

\cmc \Hz \cubiccentimeter \Molar \molar \mmHg \mol The **siunitx** package provides all of the units desired here. So if it is loaded, the module **synchem** is all that needs to be loaded. Otherwise, a series of tests are needed for **Slunits** and **unitsdef**. If either of these are loaded, they are used; if not, then **siunitx** is loaded in any case.

```
100 \@ifpackageloaded{siunitx}{%
101   {\requiresiconfigs{synchem}}%
102   {\@ifpackageloaded{SIunits}{%
103     {\newcommand*{\cubiccentimeter}{\centi\metre\cubed}%
104      \newcommand*{\Molar}{\textsc{m}}%
105      \newcommand*{\molar}{\mole\usk\deci\metre\cubed}%
106      \newcommand*{\mmHg}{\milli\metre Hg}%
107      \newcommand*{\mol}{\mole}%
108      \newcommand*{\cmc}{\cubiccentimeter}%
109      \newcommand*{\Hz}{\hertz}}%
110   {\@ifpackageloaded{unitsdef}{%
111     {\newunit{\cubiccentimeter}{%
112       \cm\unitsuperscript{3}}%
113     \newunit{\Molar}{\textsc{m}}%
114     \newunit{\molar}{%
115       \mole\unitsep\dm\unitsuperscript{--3}}%
116     \newunit{\mmHg}{\mmHg}%
117     \newunit{\mol}{\mole}%
118     \newcommand*{\cmc}{\cubiccentimeter}%
119     \newcommand*{\Hz}{\hertz}}%
120   {\RequirePackage[alsoload=synchem]{siunitx}}}}}}
```

7.4 Standard state symbol

```
\standardstate
  \cst@sstate
  \cst@s@state
  121 \providecommand*{\standardstate}{%
    122   \ensuremath{\protect\cst@sstate}}}
  123 \newcommand*{\cst@sstate}{\mathpalette\cst@s@state\circ}
  124 \newcommand*{\cst@s@state}[2]{%
  125   \oalign{\hfil$#1-$\hfil\cr\hfil$#1#2$\hfil\cr}}
```

7.5 Alkyl radicals

```
\cst@radical
The \cst@radical macro does the hard work of declaring each abbreviation.
The commands are made robust so they can (hopefully) be used anywhere.
  126 \newcommand*{\cst@radical}[2]{%
  127   \expandafter\DeclareRobustCommand\expandafter*\expandafter{%
  128     \csname #1#2\endcsname}{%
```

\cst@emph
\cst@hyphen To allow redefinition while running, the various component parts of the system are defined each time an abbreviation is used.

```
 129   \ifcst@radhyphen
 130     \def\cst@hyphen{-}%
 131   \else
 132     \let\cst@hyphen\relax
 133   \fi
 134   \ifcst@radsuper
 135     \let\cst@super\textsuperscript
 136   \else
 137     \let\cst@super\relax
 138   \fi
 139   \ifcst@rademph
 140     \let\cst@emph\emph
 141   \else
 142     \let\cst@emph\relax
 143   \fi
```

The final check is for a prefix, which is easiest to do here.

```
 144   \ifcst@radprefix
 145     \cst@super{\cst@emph{#1}}\cst@hyphen#2%
 146   \else
 147     #2\cst@hyphen\cst@super{\cst@emph{#1}}%
 148   \fi
 149   \cst@xspace}
```

\cst@xspace A re-useable \xspace-based macro.

```
 150 \newcommand*{\cst@xspace}{%
 151   \ifcst@xspace
 152     \expandafter\xspace%
 153   \fi}
```

\nPr With a mechanism in place, the abbreviations are declared. The format of the
\iPr resulting output will depend upon the configuration file used.

\nBu
\iBu
\sBu
\tBu

```

154 \cst@radical{n}{Pr}%
155 \cst@radical{i}{Pr}%
156 \cst@radical{n}{Bu}%
157 \cst@radical{i}{Bu}%
158 \cst@radical{s}{Bu}%
159 \cst@radical{t}{Bu}%

```

7.6 Float formatting

The next step is to format the floats correctly. The standard float types are now restyled to place the captions correctly (for most journals). Normally in chemical documents the author expects the float to be “here” if possible; this is therefore set as the default.

```

160 \floatstyle{plaintop}
161 \restylefloat{table}
162 \floatstyle{plain}
163 \restylefloat{figure}
164 \floatplacement{table}{htbp}
165 \floatplacement{figure}{htbp}

```

Work with schemes needs to be done after `hyperref` might be loaded.

```

166 \AtBeginDocument{
167   \restylefloat{scheme}
168   \floatplacement{scheme}{htbp}}

```

The contents of floats are centred by default, using the hook from the `chemscheme` package.

```
169 \floatcontentscentre
```

7.7 Cross-references

The naming for cross-references is sorted out properly using the `variorref` package.

```

170 \labelformat{figure}{\figurename~#1}
171 \labelformat{table}{\tablename~#1}
172 \AtBeginDocument{\labelformat{scheme}{\schemename~#1}}

```

7.8 Latin phrases

```

\latin
\cst@latin
\latinemphon
\latinemphoff

```

A series of Latin phrases are provided, with a quick switch to print them in Roman letters if needed. A mechanism is needed to alter the effect of the `\latin` command *only* if the user does not have their own version. This is achieved here, with precautions taken to ensure the user can define their own `\latin` command *after* loading `chemstyle` and still have everything work properly.

```

173 \newcommand*\cst@latin{%
174   \ifcst@abbremph
175     \expandafter\emph%
176   \fi}
177 \newcommand*\latinemphon{\cstsetup{abbremph=true}}
178 \newcommand*\latinemphoff{\cstsetup{abbremph=false}}
179 \AtBeginDocument{\providecommand*\latin{\cst@latin}}

```

\etc For the macros themselves, care is taken about trailing full stops. The \xspace command deals with any problems of spacing. Things could go wrong with complex punctuation, as no other checks are performed. All of these functions use \providecommand to avoid standing on the user's own versions, if they exist.

```

180 \ifcst@phrases
181   \AtBeginDocument{
182     \providecommand*\{\etc}
183       {\@ifnextchar.\{\cst@etc\}\cst@etc.\cst@xspace}
184     \providecommand*\{\invacuo}
185       {\latin{in vacuo}}\cst@xspace
186     \providecommand*\{\etal}
187       {\@ifnextchar.\{\cst@etal\}\cst@etal.\cst@xspace}
188     \providecommand*\{\eg}
189       {\ifcst@abbrcomma
190         \expandafter\cst@commaabbr%
191       \else
192         \expandafter\cst@nocommaabbr%
193       \fi
194       {eg}}
195     \providecommand*\{\ie}
196       {\ifcst@abbrcomma
197         \expandafter\cst@commaabbr%
198       \else
199         \expandafter\cst@nocommaabbr%
200       \fi
201       {ie} })
202 \fi

```

\cst@etal Internal macros are used for items ending in a full stop, to allow clean handling of spacing. Notice that \ie and \eg cannot come at the end of a sentence, they are designed to give only an inter-word space.

```

203 \newcommand*\{\cst@etal\}\latin{et~al}}
204 \newcommand*\{\cst@etc\}\latin{etc}
205 \newcommand*\{\cst@ie\}\latin{i.e}\spacefactor999\relax}
206 \newcommand*\{\cst@eg\}\latin{e.g}\spacefactor999\relax}

```

\cst@commaabbr To handle the comma issue, two general macros are used.

```

207 \newcommand*\{\cst@commaabbr\}[1]{%
208   \csname cst@\#1\endcsname%
209   \cst@addpunct}
210 \newcommand*\{\cst@nocommaabbr\}[1]{%
211   \@ifnextchar.%
212     {\csname cst@\#1\endcsname}
213     {\csname cst@\#1\endcsname.\cst@xspace} }

```

\cst@addpunct The following macros are very closely based on those in the cite package used for moving citations after punctuation. The first macro is used as an initial hook. Notice that \relax is essential here, as it provides an argument for \cst@add@punct in the first round of checking.

```

214 \newcommand*\{\cst@addpunct\}{%
215   \cst@add@punct\relax}

```

\cst@add@punct	Here, a plain \TeX \futurelet is used to test the next character. Notice that this macro takes a single argument, which is used to recursively gobble up punctuation.
	216 \newcommand*{\cst@add@punct}[1]{% 217 \futurelet\cst@tempa\cst@add@punct@}
\cst@add@punct@ \cst@tempa \cst@tempb	The checking occurs here. If a match is made, then the process is repeated to allow the punctuation to be gobbled.
	218 \newcommand*{\cst@add@punct@}{% 219 \ifx.\cst@tempa 220 \let\cst@tempb\cst@add@punct 221 \else 222 \ifx,\cst@tempa 223 \let\cst@tempb\cst@add@punct

No match, and so new punctuation is to be added and the loop ended.

```
224 \else  
225 \let\cst@tempb\cst@commapunct  
226 \fi  
227 \fi  
228 \cst@tempb}
```

\cst@commapunct	The \cst@punct macro holds the comma-containing punctuation to be added.
	229 \newcommand*{\cst@commapunct}{.,\cst@xspace}

7.9 Loading the style definition

The style definition is loaded here, once everything necessary is in place. A style must be loaded, so a default is provided to be on the safe side. The journal style file must have extension .jdf.

```
230 \InputIfFileExists{\cst@journal.jdf}  
231 {\PackageInfo{chemstyle}  
232 {Loaded \cst@journal.jdf}}  
233 {\PackageWarning{chemstyle}  
234 {Requested style '\cst@journal' does not exist\MessageBreak  
235 Loading default style}  
236 \InputIfFileExists{none.jdf}{}  
237 {\PackageError{chemstyle}{Failed to load none.jdf}  
238 {The default journal definition file was not  
239 found\MessageBreak This is a core part of  
240 chemstyle\MessageBreak Something is wrong with  
241 the installation}}}
```

7.10 Handling reference section naming

\cst@refsec	To enable the renaming of \bibname or \refname to the desired value, some work is needed. Both natbib and biblatex alter the behaviour here subtly. The babel package also requires careful handling. The initial step is to find whether the document class defines chapters, as this affects whether \refname or \bibname should be changed. This is done inside a group so that a false definition is not left around. ⁵ A second check is needed, in case the document class does not
-------------	--

⁵If @undefined is ever fixed, this will no longer be needed. If $\varepsilon\text{-}\text{\TeX}$ was required, the \ifdefined would be a choice here; however, $\varepsilon\text{-}\text{\TeX}$ is not going to be required just for this.

define any reference section at all (for example, minimal does not).

```
242 \begingroup
243   \@ifundefined{chapter}
244     {\@ifundefined{refname}
245       {\PackageInfo{chemstyle}
246         {No bibliography name command found}
247         \cstsetup{notes=false}}
248       {\gdef\cst@refsec{\refname}}}
249     {\gdef\cst@refsec{\bibname}}
250 \endgroup
```

\c@bibnote The business-end of the work is only carried out if the notes option is set to true or auto. The check above means that a reference section is also defined. First, some checking for the auto option occurs; the counter used by notes2bib needs to be defined even if the package is not loaded.

```
251 \ifcst@autonotes
252   \AtBeginDocument{
253     \@ifpackageloaded{notes2bib} {}
254     {\newcounter{bibnote}}}
255 \fi
```

\cst@refname The internal macros to actually display the reference section name deals with the various options. The \expandafters are for caution here: nothing *should* go wrong with the nested \if statements.

```
256 \newcommand*\cst@refname{%
257   \ifcst@notes
258     \ifcst@autonotes
259       \ifnum\the\value{bibnote}>\z@
260         \expandafter\expandafter\expandafter\expandafter
261           \expandafter\expandafter\expandafter\cst@ref@name
262       \else
263         \expandafter\expandafter\expandafter\expandafter
264           \expandafter\expandafter\expandafter\cst@ref@name@
265       \fi
266     \else
267       \expandafter\expandafter\expandafter\cst@ref@name
268     \fi
269   \else
270     \expandafter\cst@ref@name@%
271   \fi}
272 \newcommand*\cst@ref@name[3]{%
273   \ifcst@notesbefore
274     #3\space#2\space#1%
275   \else
276     #1\space#2\space#3%
277   \fi}
278 \newcommand*\cst@ref@name@[3]{#1}
```

\cst@setrefname Setting up the section name is a tricky affair. If no section is defined, then the whole process is skipped. Otherwise, the first check made is if the default language matches the definition given. If so, the heading is changed now.

```
279 \@ifundefined{cst@refsec}
280   {\let\cst@setrefname@gobblefour}
```

```

281  {\newcommand*{\cst@setrefname}[4]{
282    \edef\cst@tempa{#1}%
283    \ifx\cst@tempa\cst@language
284      \expandafter\renewcommand\expandafter*\expandafter{%
285        \cst@refsec}
286        {\cst@refname{#2}{#3}{#4}}}
287  \fi

```

cst@tempa At the beginning of the document, a check needs to be made for babel and biblatex. For the later, a low-level hack is made to attach to the mechanism. For babel the appropriate commands are added to the \captions... macro.

```

288  \AtBeginDocument{
289    \@ifpackageloaded{biblatex}{%
290      \def\cst@tempa{\csgappto{bib@strings@#1}{%
291        \expandafter\cst@tempa\expandafter{\expandafter{%
292          \renewcommand\expandafter*\expandafter{%
293            \cst@refsec}{%
294              \cst@refname{#2}{#3}{#4}}}}}}%
295    \@ifpackageloaded{babel}{%
296      \def\cst@tempa{\expandafter\addto\expandafter{%
297        \csname captions#1\endcsname}{%
298          \expandafter\cst@tempa\expandafter{%
299            \expandafter\renewcommand\expandafter*\expandafter{%
300              \cst@refsec}{%
301                \cst@refname{#2}{#3}{#4}}}}}}%

```

To make sure the changes are applied *now*, the current language is re-selected.

```

302    \expandafter\selectlanguage\expandafter{%
303      \languagename}%
304    {}}}}}

```

Default names are loaded for a range of languages. Most journals stick to the same words, with only the order changing.

```

305 \cst@setrefname{english}{References}{and}{Notes}
306 \cst@setrefname{UKenglish}{References}{and}{Notes}
307 \cst@setrefname{ngerman}{Literatur}{und}{Notizen}
308 \cst@setrefname{german}{Literatur}{und}{Notizen}
309 \cst@setrefname{french}{R\'ef\'erences}{et}{Notes}
310 \cst@setrefname{frenchb}{R\'ef\'erences}{et}{Notes}

```

8 Configuration files

Each journal style needs slightly differing commands to get the formatting just right. This is handled here, with each style in a separate file. There is not a lot happening in most of these files, as the information is by its nature quite repetitive.

8.1 RSC style

```

311 \ProvidesFile{rsc.jdf}
312   [\cst@ver RSC journal style]
313 \AtBeginDocument{%

```

```

314 \renewcommand{\figurename}{Fig.}
315 \captionsetup{labelsep=quad, labelfont=bf}
316 \setkeys[cst]{opt}{
317   radprefix=true,
318   rademph=true,
319   radsuper=false,
320   radhyphen=true,
321   abbrempth=true,
322   abbrcomma=false}

```

8.2 *Angew. Chem.* style

```

323 \ProvidesFile{angew.def}
324   [\cst@ver Angew. Chem. journal style]
325 \captionsetup{labelsep=period, labelfont={bf, it}, font=sf,
326   singlelinecheck=off}
327 \captionsetup[table]{labelsep=colon}
328 \setkeys[cst]{opt}{
329   radprefix=true,
330   rademph=true,
331   radsuper=false,
332   radhyphen=false,
333   abbrempth=false,
334   abbrcomma=false}

```

8.3 *J. Organomet. Chem.* style

```

335 \ProvidesFile{jomc.def}
336   [\cst@ver J. Organomet. Chem. journal style]
337 \captionsetup{labelsep=period}
338 \captionsetup[table]{labelsep=newline, singlelinecheck=off}
339 \AtBeginDocument{%
340   \renewcommand{\figurename}{Fig.}}
341 \setkeys[cst]{opt}{
342   radprefix=true,
343   rademph=true,
344   radsuper=true,
345   radhyphen=false,
346   abbrempth=false,
347   abbrcomma=false,
348   notesbefore=true}

```

8.4 *Tetrahedron Lett.* style

```

349 \ProvidesFile{tetlett.def}
350   [\cst@ver Tetrahedron Lett. journal style]
351 \captionsetup{labelsep=period, singlelinecheck=off, labelfont=bf}
352 \setkeys[cst]{opt}{
353   radprefix=true,
354   rademph=true,
355   radsuper=false,
356   radhyphen=true,
357   abbrempth=false,
358   abbrcomma=true,
359   notesbefore=true}

```

8.5 *J. Am. Chem. Soc.* style

```
360 \ProvidesFile{jacs.jdf}
361   [\cst@ver J. Am. Chem. Soc. journal style]
362 \DeclareCaptionLabelSeparator{perquad}{.\quad}
363 \captionsetup{labelfont={bf,it,sf},textfont=sf,
364   labelsep=perquad}
365 \captionsetup[figure]{textfont=rm}
366 \captionsetup{singlelinecheck=off}
367 \setkeys[cst]{opt}{
368   radprefix=true,
369   rademph=true,
370   radsuper=true,
371   radhyphen=false,
372   abbrempth=false,
373   abbrcomma=true,
374   notesbefore=true}
375 \floatstyle{plaintop}
376 \restylefloat{scheme}
377 \floatstyle{plain}
378 \cst@notesbeforefalse
```

8.6 *Inorg. Chem.* style

Almost exactly the same as for *J. Am. Chem. Soc.*, so most of the work is left to *jacs.jdf*.

```
379 \ProvidesFile{ic.jdf}
380   [\cst@ver Inorg. Chem. journal style]
381 \input {jacs.jdf}
382 \captionsetup{textfont=rm}
```

8.7 *J. Phys. Chem.* style

```
383 \ProvidesFile{jpc.jdf}
384   [\cst@ver J. Phys. Chem. journal style]
385 \DeclareCaptionFormat{labelcaps}{\MakeUppercase{#1}#2#3}
386 \captionsetup{font=bf,labelsep=colon,format=labelcaps}
387 \captionsetup[figure]{format=plain,textfont=md,labelsep=period}
388 \captionsetup{singlelinecheck=off}
389 \setkeys[cst]{opt}{
390   radprefix=true,
391   rademph=true,
392   radsuper=false,
393   radhyphen=false,
394   abbrempth=false,
395   abbrcomma=true,
396   notesbefore=true}
397 \floatstyle{plaintop}
398 \restylefloat{scheme}
399 \floatstyle{plain}
400 \cst@notesbeforefalse
```

8.8 *Org. Lett.* style

```
401 \ProvidesFile{orglett.jdf}
```

	<pre> 402 [\cst@ver Org. Lett. journal style] 403 \RequirePackage{xcolor} </pre>
	<p>Currently, this style only works with <code>float</code>.</p>
	<pre> 404 \@ifpackageloaded{floatrow} 405 {\PackageError{chemstyle}{% 406 {Org. Lett. style only works with float} 407 {Load chemstyle with the floatrow=false option 408 to\MessageBreak use the orglett style}}} 409 {} </pre>
\OrgLettColour	<p>To allow the user to control the colour of the “bars” in this style, an additional macro is provided. The purple colour looks about right for matching the printed journal, but if anyone has a better suggestion please let the package author know.</p>
	<pre> 410 \newcommand*{\OrgLettColour}[1]{purple} </pre>
\fs@orglett	<p>In order to get the distinctive coloured bars used by <i>Org. Lett.</i>, a new style for floats is needed. This is based on the <code>ruled</code> style from the <code>float</code> package.</p>
	<pre> 411 \newcommand*{\fs@orglett}{% 412 \def\@fs@cfont{\bfseries}% 413 \let\@fs@capt\floatc@ruled 414 \def\@fs@pre{(\begin{group}\color{\OrgLettColour}% 415 \hrule height12pt depth0pt \kern2pt\end{group})% </pre>
	<p>This is the same <code>\@fs@mid</code> as is used in the <code>float</code> package for <code>plaintop</code> floats.</p>
	<pre> 416 \def\@fs@mid{(\vspace{belowcaptionskip}\relax)% 417 \def\@fs@post{(\begin{group}\color{\OrgLettColour}\kern2pt 418 \hrule height1.5pt depth0pt\end{group})% 419 \let\@fs@iftopcapt\iftrue} </pre>
\fs@orglettfig	<p>Figures need to be slightly different, so an almost identical command is needed.</p>
	<pre> 420 \newcommand*{\fs@orglettfig}{% 421 \def\@fs@cfont{\bfseries}% 422 \let\@fs@capt\floatc@plain 423 \def\@fs@pre{(\begin{group}\color{\OrgLettColour}% 424 \hrule height12pt depth0pt \kern2pt\end{group})% 425 \def\@fs@mid{(\vspace{abovecaptionskip}\relax)% 426 \def\@fs@post{(\begin{group}\color{\OrgLettColour}\kern2pt 427 \hrule height1.5pt depth0pt\end{group})% 428 \let\@fs@iftopcapt\iffalse} </pre>
	<p>The new style is now applied. Users can change back to normal floats by changing back to the plain style.</p>
	<pre> 429 \floatstyle{orglettfig} 430 \restylefloat{figure} 431 \floatstyle{orglett} 432 \restylefloat{scheme} 433 \restylefloat{table} </pre>
	<p>The more usual style commands now occur.</p>
	<pre> 434 \DeclareCaptionLabelSeparator{perquad}{.\quad} 435 \captionsetup{labelfont=bf,labelsep=perquad} 436 \setkeys[cst]{opt}{% 437 radprefix=true, 438 rademph=true, </pre>

```

439 radsuper=true,
440 radhyphen=false,
441 abbrempm=false,
442 abbrcomma=true,
443 notesbefore=true}
444 \cst@notesbeforefalse

```

8.9 The empty style — none

To allow the user to load the extra macros provided here without any style changes, a “do nothing” style is provided. It simply makes sure that very little changes compared to the L^AT_EX kernel. This requires undoing the defaults provided above. For commands where a default is needed (*e.g.* the `\latin` command) the style of the RSC is followed. As the `float` package has been loaded, notice that captions will be placed below floats even if the `\caption` command appears above the contents of the floating environment.

```

445 \ProvidesFile{none.jdf}
446   [\cst@ver Empty journal style]
447 \floatstyle{plain}
448 \restylefloat{table}
449 \labelformat{figure}{#1}
450 \labelformat{table}{#1}
451 \floatplacement{table}{tbp}
452 \floatplacement{figure}{tbp}
453 \AtBeginDocument{
454   \floatplacement{scheme}{tbp}
455   \labelformat{scheme}{#1}}

```

9 Change History

v1.0	General: Initial release of package	1	Fixed (another) error in alkyl for-	
			matting	16
v1.0a	General: Added <i>J. Phys. Chem.</i> style	18	Fixed error with spacing after	
	Added <i>Org. Lett.</i> style	18	<i>e.g.</i> and <i>i.e.</i>	1
	Fixed incorrect Latin formatting		License changed from GPL to LPPL	1
	for angew option	16	Phrases modified to better avoid	
	No longer load <code>fixltx2e</code> pack-		clash with user’s own com-	
	age	8	mands	1
v1.0b	General: Added <code>microtype</code> and		\cst@add@punct: New macro . . .	13
	<code>notes2bib</code> to template	1	\cst@add@punct@: New macro . . .	13
	Fixed formatting of alkyls	16	\cst@addpunct: New macro . . .	13
	Sorted a problem with <code>babel</code>		\cst@latin: New macro	12
	and figure name format	16	\eg: Adds comma for ACS journals	12
v1.1	General: Added <code>phrases</code> option	1	\ie: Adds comma for ACS journals	12
	Added <code>siunits</code> option	1	v1.1a	
	Added <code>xspace</code> option	1	General: Fixed error in documenta-	
			tion compilation under L ^A T _E X . . .	1
		v1.1b	General: Load <code>caption</code> even when	
			journal style does not exist . . .	14

v1.1c	General: Added Slunits option	<u>1</u>	Various internal tweaks	<u>1</u>	
	Added frenchb alias for french	<u>16</u>	\cst@add@punct@: Internal tweaks	<u>13</u>	
	Added german alias for ngerman	<u>16</u>	\cst@commaabbr: New macro	<u>13</u>	
	Documentation improved	<u>1</u>	\cst@commapunct: Name change from \cst@punct	<u>14</u>	
	Fixed problems with capitalisation of Slunits	<u>1</u>	\cst@latin: Change of definition to allow better working with run-time options	<u>12</u>	
v1.1d	General: Require caption in all cases	<u>8</u>	\cst@nocommaabbr: New macro	<u>13</u>	
v1.1e	General: Fixed packaging problem .	<u>1</u>	\cst@radical: Re-write to allow definition to change at run-time	<u>10</u>	
v1.1f	\cst@addpunct: No longer used when comma not required	<u>13</u>	\cst@ref@name: New macro	<u>15</u>	
	\cst@eg: New macro	<u>13</u>	\cst@ref@name@: New macro	<u>15</u>	
	\cst@etal: New macro	<u>13</u>	\cst@refname: New macro	<u>15</u>	
	\cst@etc: New macro	<u>13</u>	\cst@refsec: New macro	<u>14</u>	
	\cst@ie: New macro	<u>13</u>	\cst@setrefname: New macro	<u>15</u>	
	\eg: Definition comma-mode dependent	<u>12</u>	\cst@tempa: New macro	<u>8</u>	
	Fixed problem with full stop spacing	<u>12</u>	\cst@tempb: New macro	<u>8</u>	
	\etal: Fixed problem with full stop spacing	<u>12</u>	\cst@xspace: New definition	<u>11</u>	
	\ie: Definition comma-mode dependent	<u>12</u>	\eg: Dynamic definition for comma mode	<u>12</u>	
	Fixed problem with full stop spacing	<u>12</u>	\ie: Dynamic definition for comma mode	<u>12</u>	
v1.1g	General: Added jomc style	<u>17</u>	\latinemphoff: New definition to work with xkeyval system	<u>12</u>	
	Fixed problem with cross-referencing when babel is not loaded	<u>12</u>	\latinemphon: New definition to work with xkeyval system	<u>12</u>	
v1.1h	General: Added tetlett style	<u>17</u>	v1.2a	General: Fixed error with restyling scheme floats, caused by change in chemscheme	<u>1</u>
v1.2	General: Added xkeyval interface	<u>8</u>	v1.2b	General: Change due to name change of si package to siunitx	<u>10</u>
	Re-write of reference-section renaming code	<u>14</u>	v1.2c	General: Altered call to siunitx function	<u>10</u>
	Re-write of units section	<u>10</u>	v1.3a	\standardstate: Completely new definition	<u>10</u>
	Removed obsolete ch and chapter options	<u>1</u>	v1.3b	General: Default to loading siunitx	<u>10</u>

10 Index

Numbers written in italic refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

A	
abbrcomma (option)	<u>5</u>
abbremph (option)	<u>5</u>

C	
\c@bibnote	<u>251</u>
chemcompounds (option)	<u>3</u>
\circ	<u>123</u>
\cmc	<u>3, 100</u>
\cr	<u>125</u>
\cst@add@punct ...	<u>215, 216, 220, 223</u>
\cst@add@punct@	<u>217, 218</u>
\cst@addpunct	<u>209, 214</u>
\cst@autonotesfalse	<u>41</u>
\cst@autonettrue	<u>45</u>
\cst@boolkey	<u>23, 25–35</u>
\cst@commaabbr	<u>190, 197, 207</u>
\cst@commapunct	<u>225, 229</u>
\cst@disablekey	<u>85</u>
\cst@eg	<u>203</u>
\cst@emph	<u>129, 145, 147</u>
\cst@etal	<u>187, 203</u>
\cst@etc	<u>183, 203</u>
\cst@hyphen	<u>129, 145, 147</u>
\cst@id	<u>13</u>
\cst@ie	<u>203</u>
\cst@journal	<u>59, 230, 232, 234</u>
\cst@language	<u>59, 283</u>
\cst@latin	<u>173</u>
\cst@nocommaabbr	<u>192, 199, 207</u>
\cst@notesbeforefalse	<u>378, 400, 444</u>
\cst@notesfalse	<u>40</u>
\cst@notesttrue	<u>44, 49</u>
\cst@radical	<u>126, 154–159</u>
\cst@ref@name	<u>256</u>
\cst@ref@name@	<u>256</u>
\cst@refname	<u>256, 286, 294, 301</u>
\cst@refsec	<u>242, 285, 293, 300</u>
\cst@s@state	<u>121</u>
\cst@setrefname	<u>279, 305–310</u>
\cst@sstate	<u>121</u>
\cst@super	<u>129, 145, 147</u>
\cst@tempa	<u>21, 36, 217, 218, 282, 283, 288, 290, 291, 296, 298</u>
\cst@tempb	<u>21, 36, 218</u>
\cst@ver	<u>13, 312, 324, 336, 350, 361, 380, 384, 402, 446</u>
\cst@xspace	
...	<u>149, 150, 183, 185, 187, 213, 229</u>
\cstsetup	<u>3, 96, 177, 178, 247</u>
\cubiccentimeter	<u>100</u>
E	
\eg	<u>4, 180</u>
F	
\etal	<u>4, 180</u>
\etc	<u>4, 180</u>
H	
\hfil	<u>125</u>
\Hz	<u>3, 100</u>
I	
\iBu	<u>4, 154</u>
\ie	<u>4, 180</u>
\ifcst@abbrcomma	<u>25, 189, 196</u>
\ifcst@abbremph	<u>25, 174</u>
\ifcst@autonotes	<u>36, 251, 258</u>
\ifcst@chemcompounds	<u>25, 77</u>
\ifcst@floatrow	<u>25, 80</u>
\ifcst@notes	<u>36, 257</u>
\ifcst@notesbefore	<u>25, 273</u>
\ifcst@phrases	<u>25, 180</u>
\ifcst@rademph	<u>25, 139</u>
\ifcst@radhyphen	<u>25, 129</u>
\ifcst@radprefix	<u>25, 144</u>
\ifcst@radsuper	<u>25, 134</u>
\ifcst@xspace	<u>25, 151</u>
\invacuo	<u>4, 180</u>
\iPr	<u>4, 154</u>
J	
journal (option)	<u>2, 3</u>
L	
\latin	<u>4, 173, 185, 203–206</u>
\latinemphoff	<u>5, 173</u>
\latinemphon	<u>5, 173</u>
M	
\mathpalette	<u>123</u>
\mmHg	<u>3, 100</u>
\mol	<u>100</u>
\Molar	<u>3, 100</u>
\molar	<u>3, 100</u>
N	
\nBu	<u>4, 154</u>
nonotes (option)	<u>3</u>
nophrases (option)	<u>5</u>
notes (option)	<u>3</u>
notesbefore (option)	<u>3</u>

\nPr	<i>4, <u>154</u></i>	\OrgLettColour	<i>410</i>
O		P	
\ooalign	<i>125</i>	\protect	<i>122</i>
options:			
abbrcomma	<i>5</i>	R	
abbremph	<i>5</i>	rademph (option)	<i>4</i>
chemcompounds	<i>3</i>	radhyphen (option)	<i>4</i>
floatrow	<i>3</i>	radprefix (option)	<i>4</i>
journal	<i>2, 3</i>	radsuper (option)	<i>4</i>
nonotes	<i>3</i>	S	
nophrases	<i>5</i>	\sBu	<i>4, <u>154</u></i>
notes	<i>3</i>	\standardstate	<i>4, <u>121</u></i>
notesbefore	<i>3</i>	T	
rademph	<i>4</i>	\tBu	<i>4, <u>154</u></i>
radhyphen	<i>4</i>	X	
radprefix	<i>4</i>	xspace (option)	<i>4</i>
radsuper	<i>4</i>		
xspace	<i>4</i>		