

chemstyle — Writing chemistry with style^{*}

Joseph Wright[†]

Released 2008/04/14

Abstract

The chemstyle package provides a “one-stop shop” for setting up formatting of L^AT_EX documents following the editorial policies of various chemical journals. It provides a number of handy chemistry-related commands, and loads several support packages to aid the chemist.

Contents

1	Introduction	1	7	The package code	8
			7.1	Setup code	8
			7.2	Option handling	8
2	Style options for chemstyle	2	7.3	Extra units	10
	2.1 Creating styles	3	7.4	Standard state symbol . .	11
	2.2 Package options	3	7.5	Alkyl radicals	11
3	Naming of the references section	3	7.6	Float formatting	12
			7.7	Cross-references	12
			7.8	Latin phrases	13
			7.9	Loading the style definition	14
			7.10	Handling reference section naming	15
4	Additional macros	4	8	Configuration files	17
	4.1 Additional units	4	8.1	RSC style	17
	4.2 The standard state symbol	4	8.2	<i>Angew. Chem.</i> style . .	17
	4.3 Alkyl radicals	4	8.3	<i>J. Organomet. Chem.</i> style	17
	4.4 Latin phrases	5	8.4	<i>Tetrahedron Lett.</i> style . .	17
5	Additional information	6	8.5	<i>J. Am. Chem. Soc.</i> style .	18
	5.1 Advice for users of the rsc package	6	8.6	<i>Inorg. Chem.</i> style	18
	5.2 Interactions with other packages	6	8.7	<i>J. Phys. Chem.</i> style	18
	5.3 Captions above floats	6	8.8	<i>Org. Lett.</i> style	19
6	A template for chemical articles	7	8.9	The empty style — none	20
			9	Change History	20
			10	Index	21

^{*}This file describes version v1.2b, last revised 2008/04/14.

[†]E-mail: joseph.wright@morningstar2.co.uk

Table 1: Styles provided by chemstyle

Option	Journals using this style
none	Not applicable
angew	<i>Angew. Chem., Chem. Eur. J.</i>
jomc	<i>J. Organomet. Chem., Coord. Chem. Rev.</i>
ic	<i>Inorg. Chem.</i>
jacs	<i>J. Am. Chem. Soc.</i>
jcp	<i>J. Phys. Chem. A, J. Phys. Chem. B</i>
orglett	<i>Org. Lett.</i>
rsc	<i>Chem. Commun., Org. Biomol. Chem.</i> <i>Dalton Trans.</i>
tetlett	<i>Tetrahedron, Tetrahedron Lett.</i>

1 Introduction

The aim of chemstyle is to provide a quick method to set up various document parameters (such as caption formatting), simply by specifying the model journal. The package has also been designed to allow rapid addition of new journal styles. Each style definition is a separate file, and new styles can be added very readily. chemstyle has grown out of the rsc package, which had a similar aim but was much more limited (and less robustly implemented). The chemstyle package is also designed with the use of biblatex in mind: the rsc package is closely bound to traditional BibTeX use.

As a successor to the rsc package, chemstyle provides a range of chemistry-related additional macros. The set provided here is an extended version of those provided by rsc. Everything that can be done using the rsc L^AT_EX package is therefore possible using the chemstyle package.

The formatting system provided by chemstyle are intended for writing a variety of documents. Thus the stylistic changes made by the package do not seek to reproduce the appearance of printed journal articles. The package aims to be suitable for use in preparing drafts of papers, but also for writing reports, theses and so on.

2 Style options for chemstyle

journal chemstyle should be loaded with a package option specifying which journal style to follow. Currently, chemstyle is aware of all the styles listed in Table 1. New styles can be developed by creating a new file modelled on the existing definitions; chemstyle will automatically search for correctly-named styles. The style files provided with chemstyle have been derived from current practice in the target journals. It is not always easy to pick the correct stylistic settings from (sometimes inconsistent) real-world examples. The package author welcomes feedback on the styles provided.

The none style is notable as it is not based on a journal. Instead this is a minimal style, which provides the additional commands without making formatting changes. It is also the default style if no option is given. This

document has been compiled implicitly using the `none` option, for example.

2.1 Creating styles

The process of creating a new styles for chemstyle is intended to be relatively easy. New styles should be saved as files with the extension `.jdf` (standing for Journal Definition File), and should be saved somewhere in the path searched by TeX.¹ The definition files included in the package should provide a guide to the basic options available for producing new styles. Arbitrary TeX commands can be included, if they are necessary for a particular style. For example, other packages can be loaded in `\usepackage`.

The maintainer of chemstyle is happy to add new styles to the package, either by contribution by users or on request (when he has sufficient time!). If you have a new style to add (or corrections to an existing one), please contact the package author.

2.2 Package options

<code>journal</code>	As of version 1.2, chemstyle uses the keyval system for option management. The choice of journal style can therefore be given as a normal option or by using the key <code>journal=</code> . The other package options provided by the package are described as they arise in the documentation.
<code>\cstsetup</code>	Some of the package options can only be set when loading the package. The choice of journal style is one of these. Others can be altered anywhere in the document, using the <code>\cstsetup</code> macro. This accepts a keyval list and processes it as needed.
<code>chemcompounds</code>	chemstyle loads the chemscheme package, and therefore will pass through the <code>optchemcompounds</code> option.
<code>notes</code> <code>nonotes</code>	

3 Naming of the references section

chemstyle alters the naming of the references section of a document. By default, chemstyle alters the value of `\bibname` or `\refname` (as appropriate) to the form of words chosen by the target journal for the “References” section.

The “Notes and References” naming commands are language-aware, *via* the babel interface. Currently, chemstyle includes appropriate labels for babel languages `english`, `UKenglish`, `ngerman` and `french`. Other languages can be added if appropriate wordings are provided to the author. The naming system is designed to work correctly with both `natbib` and `blatex`.

The package recognises the `notes` option for controlling how the references section is named. The accepts the values `true`, `false` and `auto`. The Boolean values either enable or disable the addition of “Notes and” to the “References” of the section title. The `auto` option works in conjunction with the `notes2bib` package. If notes are added, “Notes and” is included in the section title, whereas if no notes are given the section title remains as “References”. The `nonotes` option is equivalent to `notes=false`.

¹Depending on your TeX distribution, you may need to rebuild your file database after creating a new style. For MikTeX users, this can be done graphically or by typing `mpm -update-db` at the command line; for TeXLive, run `texhash`.

`notesbefore`

The second option for this area is `notesbefore`. This takes `true` and `false` only, and sets whether “Notes and References” or “References and Notes” is produced.

4 Additional macros

4.1 Additional units

<code>\Hz</code>	Both the <code>Slunits</code> and <code>unitsdef</code> packages provide methods for handling a range of units, but do not include a small number of unit macros useful to chemists. The package therefore provides these, using <code>Slunits</code> by default. ² The definitions follow the pattern of the appropriate package.
<code>\mmHg</code>	
<code>\molar</code>	
<code>\Molar</code>	
<code>\cmc</code>	
<code>10 Hz</code>	<code>\unit{10}{\Hz}</code>
<code>20 mmHg</code>	<code>\unit{20}{\mmHg}</code>
<code>30 mol dm⁻³</code>	<code>\unit{30}{\molar}</code>
<code>40 M</code>	<code>\unit{40}{\Molar}</code>
<code>50 cm³</code>	<code>\unit{50}{\cmc}</code>

The `siunitx` package is currently under development as a replacement for `Slunits` and `unitsdef`.³ `siunitx` includes definitions for the above units, and so if it is loaded the definitions are taken from there, rather than provided by `chemstyle`. Looking to the future, once `siunitx` reaches version 1.0, it will become the default support package for `chemstyle`.

4.2 The standard state symbol

<code>\standardstate</code>	Related to the above, but not exactly a unit is the <code>\standardstate</code> command. ⁴ This generates the tricky <code>\standardstate</code> symbol.
-----------------------------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------

the standard conditions are indicated: ΔS^\ominus

the standard conditions are indicated: `\standardstate\$ \Delta S\$ \standardstate$`

4.3 Alkyl radicals

<code>\nPr</code>	There are a few alkyl radicals that come up all of the time. No one seems to
<code>\iPr</code>	have put these into a package, so they are provided here. As you would expect,
<code>\nBu</code>	<code>\iPr</code> gives <i>i</i> -Pr, <code>\iBu</code> gives <i>i</i> -Bu and <code>\tBu</code> gives <i>t</i> -Bu, and so on. The style of
<code>\iBu</code>	the output depends on the journal style specified; most journals seem to favour
<code>\sBu</code>	one version of the abbreviation.

The `\alky` group could be *n*-Pr, *i*-Pr or *n*-Bu without affecting the selectivity.

The alkyl group could be `\nPr`, `\iPr` or `\nBu` without affecting the selectivity.

<code>xspace</code>	When <code>chemstyle</code> is loaded using the <code>xspace</code> option, the <code>xspace</code> package is automatically used to add space after the command names, so that <code>\iPr</code> group will result in “ <i>i</i> -Pr group” being typeset.
---------------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

The appearance of these radical abbreviations is controlled by the package

`radhyphen`
`rademph`
`radsuper`
`radprefix`

²This is a change in v1.2: previous versions used `unitsdef`.

³By the maintainer of `chemstyle`.

⁴The `\standardstate` macro is only defined if the user does not have their own version.

options `radhyphen`, `rademph`, `radsuper` and `radprefix`. The journal styles set these automatically, but they can be redefined at any point. The options work as might be expected, and are Boolean switches.

*i*Pr ^tBu
Bu-i Bu-s

```
\cstsetup{radhyphen=false, radsuper=true} \\
\iPr \tBu
\cstsetup{radhyphen=true, radsuper=false, %
           radprefix=false, rademph=false} \\
\iBu \sBu
```

4.4 Latin phrases

`\latin`
`\etc`
`\eg`
`\ie`
`\etal`
`\invacuo`
`abbrempf`

The various Latin phrases commonly used in chemistry are made available as the obvious commands. By altering the definition of `\latin`, this allows ready switching from italic to Roman typesetting. Notice that `\etc`, `\ie` and `\eg` are aware of trailing periods, and so doubling-up should not occur. Once again, these macros use `xspace` when given as a package option to handle automatic addition of spaces after these phrases.

The use of italic for these abbreviations is set by altering the package option `abbrempf`, which takes values `true` and `false`.

et al. or *in vacuo* plus some text
i.e. equals e.g. perhaps etc.

```
\etal or \invacuo plus \latin{some text} \\
\cstsetup{abbrempf=false}
\ie equals \eg perhaps \etc
```

`abbrcomma`

For American journals, where it is obligatory to follow “*e.g.*” and “*i.e.*” with a comma, the package provides a mechanism for handling this automatically. Thus, when using an appropriate journal style, `\eg`, `\eg.` and `\eg,` will all result in typesetting “*e.g.*”. The Boolean package option `abbrcomma` controls this.

e.g. this
i.e., that

```
\eg this \\
\cstsetup{abbrcomma=true}
\ie that
```

The `\etc` and `\etal` commands are set up on the assumption that they come at the end of a sentence. Hence the spacing after these will default to an inter-sentence space. If you desire an inter-word space, use the normal methods

etc. more text
et al. have shown

```
\etc\ more text \\
\etal~have shown
```

`nophrases`

The definitions of all of the phrases are designed not to overwrite any given by the user *in the preamble*. So, if you have your own `\latin` macro, it will be used even if you load `chemstyle`. If you encounter any problems, try loading the package with the `nophrases` option; this option prevents the package even trying to define any of the phrase macros.

`\latinemphon`
`\latinemphoff`

For backward-compatibility with previous versions of `chemstyle`, the macros `\latinemphon` and `\latinemphoff` are provided. These work as would be expected, to alter the formatting produced by `\latin`. The more general `keyval` method is now preferred for making this change.

5 Additional information

5.1 Advice for users of the rsc package

The chemstyle package is intended as a replacement for the rsc package. As such, it covers almost everything the the rsc L^AT_EX package does, and more. Users of rsc are strongly encouraged to update to using chemstyle. The bibliography styles provided by rsc will continue to be required, of course. Migration of these styles to bblatex is an on-going project.

5.2 Interactions with other packages

The chemstyle package has been designed to avoid, as far as possible, clashes with other packages. The package requires the presence of the standard graphicx and varioref packages. If these packages need to be loaded with explicit options, this should be done *before* loading chemstyle. The chemscheme package is also needed, as it provides the floating scheme environment essential in synthetic chemistry documents.

5.3 Captions above floats

The scheme float type is generated using the float package. This has the side-effect that the placement of captions for floats does not depend on where the \caption command comes inside the floating environment.⁵ If you wish to alter the placement of captions, the mechanism of the underlying float package will be needed. This requires the use of \floatstyle to load the desired settings, followed by \restylefloat to apply the settings. This is most usually done with tables.

```
\begin{table} [h]
    The float contents
    \caption{A caption below the float contents in the source}
\end{table}
\floatstyle{plain}
\restylefloat{table}
\begin{table} [h]
    The second float contents, which should be above the caption
    \caption{A second caption below the float contents
        in the source}
\end{table}
```

Table 2: A caption below the float contents in the source

The float contents

The second float contents, which should be above the caption

Table 3: A second caption below the float contents in the source

⁵Normally this is a good thing.

6 A template for chemical articles

This is a very simple template for chemistry-related documents. Hopefully it contains a few extra hints for getting well-formatted documents quickly. For simplicity, the template assumes that the user is writing a thesis for a U.K. university. Hence it uses U.K. defaults and RSC-based styling. Most of the packages used have good documentation, but a brief summary of why they are recommended follows. The file `chemstyle.ltx` will be generated by compiling this documentation, and contains the example “ready to run”.

```
\documentclass[fontsize=10pt,paper=a4,english,UKenglish]
  {scrreprt}
\usepackage{geometry,upgreek,booktabs,babel}
\usepackage[journal=rsc,xspace=true]{chemstyle}
\usepackage[version=3]{mhchem}
\usepackage[footnotes]{notes2bib}
\usepackage[final]{microtype}
\usepackage[colorlinks]{hyperref}
\begin{document}
  Document contents go here
\end{document}
```

The versatile KOMA-script bundle provides more advanced versions of the standard document classes. If you want paragraphs separated out, with no indents (a common style for theses), add the `parskip` option to the font and paper size ones given here.

The `babel` system is loaded to sort out hyphenation and so on, and could be useful if there are any foreign-language quotes.

`geometry` allows the users to alter page layout with ease: much better than trying to hack the raw L^AT_EX system. `booktabs` gives much nicer looking tables than the L^AT_EX 2_E default. `upgreek` provides non-italic lowercase Greek letters, which should be used for things such as bond descriptions.

π -bond σ^* -orbital

$\$\\uppi\$$ -bond $\$\\upsigma^*\$$ -orbital

Load `chemstyle` (of course) to give not only some easy formatting, but also to automatically provide a float type for schemes, thanks to the `chemscheme` package. This also loads either `chemcompounds` or (optionally) `bpchem` to track compound numbers.

The `mhchem` package provides the `\ce` command for rapidly typesetting formulas, so that you can type `\ce{H2SO4}` and get H₂SO₄⁶.

The `microtype` package improves formatting when used with the pdftEX engine. By giving the `final` option, it is active even when using `draft` as a global option.

Using `notes2bib` allows the user to automatically add notes to the bibliography from within the document body. So you can put `\bibnote{A note}` in the source, and this will move into the References section without any further effort. The `footnotes` option means that footnotes do the same.

Finally, the `hyperref` package makes headings, citations and so on into hyperlinks.

⁶There is a slight cheat here, as this document uses lower-case numerals in the text. The example is written as `\ce{H2SO4}`.

7 The package code

7.1 Setup code

First of all, the package identifies itself and loads other packages needed to function. Loading `chemscheme` is deferred until later, to allow processing of options at the correct point.

```
1 \NeedsTeXFormat{LaTeX2e}
2 \ProvidesPackage{chemstyle}
3   [2008/04/14 v1.2b Writing chemistry with style]
```

Packages that are needed under all circumstances are loaded here. There are some limitations on the age of `xkeyval`.

```
4 \RequirePackage{xkeyval}
5 \@ifpackagelater{xkeyval}{2005/05/07}
6 {}
7 {\PackageError{chemstyle}
8   {xkeyval >= 2.5 required}
9   {chemstyle requires the 'xkeyval' package, version 2.5
10    or later.\MessageBreak The version loaded is:
11    '\@nameuse{ver@xkeyval.sty}'.\MessageBreak
12    This is a fatal error: loading will abort.}
13 \endinput}
14 \RequirePackage{graphicx,varioref,caption,xspace}
```

\cst@tempa A couple of temporary private macros.

```
15 \newcommand*\cst@tempa{}
16 \newcommand*\cst@tempb{}
```

7.2 Option handling

\cst@boolkey Option handling is processed using `xkeyval`. As a number of Boolean keys are needed, a shortcut is handy.

```
17 \newcommand*\cst@boolkey[1]{
18   \define@boolkey[cst]{opt}[\cst@]{#1}[true]{}{}}
```

\ifcst@chemcompounds The Boolean keys are now defined.

```
19 \cst@boolkey{chemcompounds}
20 \cst@boolkey{xspace}
21 \cst@boolkey{phrases}
22 \cst@boolkey{radprefix}
23 \cst@boolkey{rademph}
24 \cst@boolkey{radsuper}
25 \cst@boolkey{radhyphen}
26 \cst@boolkey{abbremph}
27 \cst@boolkey{abbrcomma}
28 \cst@boolkey{notesbefore}
```

\ifcst@notes For notes, some choices are available. These need a bit of testing.

```
29 \newif\ifcst@notes
30 \newif\ifcst@autonotes
31 \define@choicekey*[cst]{opt}{notes}[\cst@tempa]
32   {true,false,auto}[true]
```

```

33  {\cst@notesfalse
34  \cst@autonotesfalse
35  \edef\cst@tempb{auto}
36  \ifx\cst@tempa\cst@tempb
37      \cst@notestrue
38      \cst@autonotestrue
39  \fi
40  \edef\cst@tempb{true}
41  \ifx\cst@tempa\cst@tempb
42      \cst@notestrue
43  \fi}

```

Some old options are no longer needed at all.

```

44 \DeclareOptionX[cst]<opt>{siunits}
45   {\PackageInfo{chemstyle}{Option siunits no longer required}}
46 \DeclareOptionX[cst]<opt>{SIunits}
47   {\PackageInfo{chemstyle}{Option siunits no longer required}}
48 \DeclareOptionX[cst]<opt>{nonotes}
49   {\ExecuteOptionsX[cst]<opt>{notes=false}}
50 \DeclareOptionX[cst]<opt>{nophrases}
51   {\ExecuteOptionsX[cst]<opt>{phrases=false}}

```

\cst@journal The journal option can be given with or without journal=.

```

\cst@language 52 \define@cmdkeys[cst]{opt}[cst@]{journal,language}
53 \DeclareOptionX*{\edef\cst@journal{\CurrentOption}}

```

The default options are executed, and the user options are processed.

```

54 \setkeys[cst]{opt} {
55   notes=true,
56   phrases=true,
57   chemcompounds=true,
58   xspace=true,
59   journal=none,
60   radprefix=true,
61   rademph=true,
62   radsuper=false,
63   radhyphen=true,
64   abbrevmph=true,
65   abbrcomma=false,
66   language=english,
67   notesbefore=true}
68 \ProcessOptionsX[cst]<opt>

```

With the options processed, those to be passed to chemscheme are sorted out.

```

69 \ifcst@chemcompounds
70   \PassOptionsToPackage{chemcompounds}{chemscheme}
71 \fi
72 \RequirePackage{chemscheme}

```

\cst@disablekey Some of the options are no longer relevant once the package is loaded. These are disabled here with a suitable message.

```

73 \newcommand*{\cst@disablekey}[1]{
74   \define@key[cst]{opt}{#1}{\PackageWarning{chemstyle}{%
75     {Option '#1' only valid when loading package}}}

```

```

76 \AtBeginDocument{
77   \cst@disablekey{journal}
78   \cst@disablekey{phrases}
79   \cst@disablekey{nophrases}
80   \cst@disablekey{notes}
81   \cst@disablekey{nonotes}
82   \cst@disablekey{chemcompounds} }

\cstsetup A macro for changing the settings at run-time without needing to know the
internals of the package.

83 \newcommand*{\cstsetup}[1]{%
84   \iffalse{\fi\ifnum0='}\fi
85   \setkeys[cst]{opt}{#1}%
86   \ifnum0='{\fi\iffalse}\fi}

```

7.3 Extra units

The upcoming `siunitx` package⁷ will include the extra chemistry units as a loadable modules (`alsoload=synchem`). A series of checks are therefore made before any definitions are given. If `siunitx` is loaded, the necessary part of that package is loaded; the `\si@requirecfgs` macro from that package is used. The `\makeatletter` macro is needed here as otherwise the configuration file is loaded with the wrong category codes.

```

87 \AtBeginDocument{
88   \@ifpackageloaded{siunitx}{%
89     \makeatletter
90     \si@requirecfgs{synchem}
91     \makeatother}

```

`\cmc` Neither `unitsdef` nor `Slunits` define these two macros.

```

\Hz 92   \newcommand*{\cmc}{\cubiccentimeter}
93   \newcommand*{\Hz}{\hertz}

```

`\cubiccentimeter` A check is for the `unitsdef` package, so that the package-dependant definitions can be given.

```

\Molar 94   \@ifpackageloaded{unitsdef}{%
95     \newunit{\cubiccentimeter}{\cm\unitsuperscript{3}}
96     \newunit{\Molar}{\textsc{m}}
97     \newunit{\molar}{\mole\unitsep\dm\unitsuperscript{--3}}
98     \newunit{\mmHg}{\mmHg}
99     \newunit{\mol}{\mole}}

```

Two checks are made for `Slunits` to allow for odd capitalisation. If it is not found, then the package is loaded.⁸

```

100   \@ifpackageloaded{SIunits}{}%
101   {\@ifpackageloaded{siunits}{}%
102     {\RequirePackage{SIunits}}%
103     \newcommand*{\cubiccentimeter}{\centi\metre\cubed}
104     \newcommand*{\Molar}{\textsc{m}}
105     \newcommand*{\molar}{\mole\usk\decil\metre\rpcubed}

```

⁷An improved replacement for all of the existing unit packages.

⁸This will change when `siunitx` reaches version 1.0.

```

106      \newcommand{\mmHg}{\milli\metre Hg}
107      \newcommand{\mol}{\mole}}}
```

7.4 Standard state symbol

\cst@varnothing
\standardstate

The “standard state” symbol is handy. This is produced by rotating the “varnothing” symbol from the AMS set. Note that the rotation angle here has been carefully checked, but is set by eye. The symbol is loaded directly here, rather than using the `amssymb` package, to avoid any clashes.

```

108 \DeclareSymbolFont{CSTAMS}{U}{msb}{m}{n}
109 \DeclareMathSymbol{\cst@varnothing}{\mathord}{CSTAMS}{"3F}
110 \providecommand{\standardstate}{%
111   {\textsuperscript{\rotatebox[origin=c]{138.8}{\cst@varnothing}}}}
112   {\ensuremath{\cst@varnothing}}}}
```

7.5 Alkyl radicals

\cst@radical

The `\cst@radical` macro does the hard work of declaring each abbreviation. The commands are made robust so they can (hopefully) be used anywhere.

```

113 \newcommand{\cst@radical}[2]{%
114   \expandafter\DeclareRobustCommand\expandafter*\expandafter{%
115     \csname #1#2\endcsname}}%
```

\cst@emph
\cst@hyphen

To allow redefinition while running, the various component parts of the system are defined each time an abbreviation is used.

```

116   \ifcst@radhyphen
117     \def\cst@hyphen{-}%
118   \else
119     \let\cst@hyphen\relax
120   \fi
121   \ifcst@radsuper
122     \let\cst@super\textsuperscript
123   \else
124     \let\cst@super\relax
125   \fi
126   \ifcst@rademph
127     \let\cst@emph\emph
128   \else
129     \let\cst@emph\relax
130   \fi
```

The final check is for a prefix, which is easiest to do here.

```

131   \ifcst@radprefix
132     \cst@super{\cst@emph{#1}}\cst@hyphen#2%
133   \else
134     #2\cst@hyphen\cst@super{\cst@emph{#1}}%
135   \fi
136   \cst@xspace}
```

\cst@xspace

A re-useable `\xspace`-based macro.

```

137 \newcommand{\cst@xspace}{%
138   \ifcst@xspace
```

```
139     \expandafter\xspace%
140 \fi}
```

\nPr With a mechanism in place, the abbreviations are declared. The format of the resulting output will depend upon the configuration file used.

```
141 \cst@radical{n}{Pr}%
142 \cst@radical{i}{Pr}%
143 \cst@radical{n}{Bu}%
144 \cst@radical{i}{Bu}%
145 \cst@radical{s}{Bu}%
146 \cst@radical{t}{Bu}%
```

7.6 Float formatting

The next step is to format the floats correctly. Unfortunately, memoir does not provide all of the commands needed to achieve this. Thus the float package is needed; in order to load it, the `\newfloat` command in memoir is killed off. The chemscheme package does not load `float` when memoir is being used, because creating a new float type is catered for directly by memoir. Unfortunately, the memoir system isn't flexible enough for what is needed by chemstyle, so the hard work of chemscheme is undone here! For other document classes, float will already have been loaded by chemscheme.

```
147 \@ifclassloaded{memoir}
148   {\let\newfloat@\undefined
149    \RequirePackage{float}}
150 }
```

The standard float types are now restyled to place the captions correctly (for most journals). Normally in chemical documents the author expects the float to be "here" if possible; this is therefore set as the default.

```
151 \floatstyle{plaintop}
152 \restylefloat{table}
153 \floatstyle{plain}
154 \restylefloat{figure}
155 \floatplacement{table}{htbp}
156 \floatplacement{figure}{htbp}
```

Work with schemes needs to be done after hyperref might be loaded.

```
157 \AtBeginDocument{
158   \restylefloat{scheme}
159   \floatplacement{scheme}{htbp}}
```

The contents of floats are centred by default, using the hook from the chemscheme package.

```
160 \floatcontentscentre
```

7.7 Cross-references

The naming for cross-references is sorted out properly using the varioref package.

```
161 \labelformat{figure}{\figurename~#1}
162 \labelformat{table}{\tablename~#1}
163 \AtBeginDocument{\labelformat{scheme}{\schemename~#1}}
```

7.8 Latin phrases

```
\latin  
\cst@latin  
\latinemphon  
\latinemphoff
```

A series of Latin phrases are provided, with a quick switch to print them in Roman letters if needed. A mechanism is needed to alter the effect of the \latin command *only* if the user does not have their own version. This is achieved here, with precautions taken to ensure the user can define their own \latin command *after* loading chemstyle and still have everything work properly.

```
164 \newcommand*{\cst@latin}{%  
165   \ifcst@abbremph  
166     \expandafter\emph%  
167   \fi}  
168 \newcommand*{\latinemphon}{\cstsetup{abbremph=true}}  
169 \newcommand*{\latinemphoff}{\cstsetup{abbremph=false}}  
170 \AtBeginDocument{\providecommand*\latin{\cst@latin}}
```

```
\etc  
\invacuo  
\etal  
\eg  
\ie
```

For the macros themselves, care is taken about trailing full stops. The \xspace command deals with any problems of spacing. Things could go wrong with complex punctuation, as no other checks are performed. All of these functions use \providecommand to avoid standing on the user's own versions, if they exist.

```
171 \ifcst@phrases  
172   \AtBeginDocument{  
173     \providecommand*{\etc}{  
174       {\@ifnextchar.{\cst@etc}{\cst@etc.\cst@xspace}}} }  
175     \providecommand*{\invacuo}{  
176       {\latin{in vacuo}}\cst@xspace}  
177     \providecommand*{\etal}{  
178       {\@ifnextchar.{\cst@etal}{\cst@etal.\cst@xspace}}} }  
179     \providecommand*{\eg}{  
180       {\ifcst@abbrcomma  
181         \expandafter\cst@commaabbr%  
182       \else  
183         \expandafter\cst@nocommaabbr%  
184       \fi  
185       {eg}}}  
186     \providecommand*{\ie}{  
187       {\ifcst@abbrcomma  
188         \expandafter\cst@commaabbr%  
189       \else  
190         \expandafter\cst@nocommaabbr%  
191       \fi  
192       {ie}} } }
```

```
\cst@etal  
\cst@etc  
\cst@eg  
\cst@ie
```

Internal macros are used for items ending in a full stop, to allow clean handling of spacing. Notice that \ie and \eg cannot come at the end of a sentence, they are designed to give only an inter-word space.

```
193 \newcommand*{\cst@etal}{\latin{et~al}}  
194 \newcommand*{\cst@etc}{\latin{etc}}  
195 \newcommand*{\cst@ie}{\latin{i.e}\spacefactor999\relax}  
196 \newcommand*{\cst@eg}{\latin{e.g}\spacefactor999\relax}
```

\cst@commaabbr
\cst@nocommaabbr

To handle the comma issue, two general macros are used.

```
197 \newcommand*{\cst@commaabbr}[1]{%
```

```

198 \csname cst@#1\endcsname%
199 \cst@addpunct}
200 \newcommand*{\cst@nocommaabbr}[1]{%
201 \@ifnextchar.%
202 {\csname cst@#1\endcsname}
203 {\csname cst@#1\endcsname.\cst@xspace}}

```

\cst@addpunct The following macros are very closely based on those in the cite package used for moving citations after punctuation. The first macro is used as an initial hook. Notice that \relax is essential here, as it provides an argument for \cst@add@punct in the first round of checking.

```

204 \newcommand*{\cst@addpunct}{%
205 \cst@add@punct\relax}

```

\cst@add@punct Here, a plain TeX \futurelet is used to test the next character. Notice that this macro takes a single argument, which is used to recursively gobble up punctuation.

```

206 \newcommand*{\cst@add@punct}[1]{%
207 \futurelet\cst@tempa\cst@add@punct@}

```

\cst@add@punct@ \cst@tempa \cst@tempb The checking occurs here. If a match is made, then the process is repeated to allow the punctuation to be gobbled.

```

208 \newcommand*{\cst@add@punct@}{%
209 \ifx.\cst@tempa
210 \let\cst@tempb\cst@add@punct
211 \else
212 \ifx,\cst@tempa
213 \let\cst@tempb\cst@add@punct

```

No match, and so new punctuation is to be added and the loop ended.

```

214 \else
215 \let\cst@tempb\cst@commapunct
216 \fi
217 \fi
218 \cst@tempb}

```

\cst@commapunct The \cst@punct macro holds the comma-containing punctuation to be added.

```

219 \newcommand*{\cst@commapunct}{.,\cst@xspace}

```

7.9 Loading the style definition

The style definition is loaded here, once everything necessary is in place. A style must be loaded, so a default is provided to be on the safe side. The journal style file must have extension .jdf.

```

220 \InputIfFileExists{\cst@journal.jdf}
221 {\PackageInfo{chemstyle}%
222 {Loaded \cst@journal.jdf}}
223 {\PackageWarning{chemstyle}%
224 {Requested style '\cst@journal' does not exist\MessageBreak
225 Loading default style}}
226 \InputIfFileExists{none.jdf}{%
227 {\PackageError{chemstyle}{Failed to load none.jdf}%
228 {The default journal definition file was not

```

```

229     found\MessageBreak This is a core part of chemstyle
230     \MessageBreak Something is wrong with the installation}}}

```

7.10 Handling reference section naming

- \cst@refsec To enable the renaming of \bibname or \refname to the desired value, some work is needed. Both natbib and biblatex alter the behaviour here subtly. The babel package also requires careful handling. The initial step is to find whether the document class defines chapters, as this affects whether \refname or \bibname should be changed. This is done inside a group so that a false definition is not left around.⁹ A second check is needed, in case the document class does not define any reference section at all (for example, minimal does not).

```

231 \begingroup
232   \@ifundefined{chapter}
233     {\@ifundefined{refname}
234       {\PackageInfo{chemstyle}
235         {No bibliography name command found}
236         \cstsetup{notes=false}}
237       {\gdef\cst@refsec{\refname}}}
238     {\gdef\cst@refsec{\bibname}}
239 \endgroup

```

- \c@bibnote The business-end of the work is only carried out if the notes option is set to true or auto. The check above means that a reference section is also defined. First, some checking for the auto option occurs; the counter used by notes2bib needs to be defined even if the package is not loaded.

```

240 \ifcst@autonotes
241   \AtBeginDocument{
242     \@ifpackageloaded{notes2bib} {}
243     {\newcounter{bibnote}}}
244 \fi

```

- \cst@refname \cst@ref@name \cst@ref@name@ The internal macros to actually display the reference section name deals with the various options. The \expandafters are for caution here: nothing *should* go wrong with the nested \if statements.

```

245 \newcommand*{\cst@refname}{%
246   \ifcst@notes
247     \ifcst@autonotes
248       \ifnum\the\value{bibnote}>\z@
249         \expandafter\expandafter\expandafter\expandafter\expandafter
250           \expandafter\expandafter\cst@ref@name%
251     \else
252       \expandafter\expandafter\expandafter\expandafter\expandafter
253         \expandafter\expandafter\cst@ref@name@%
254     \fi
255   \else
256     \expandafter\expandafter\expandafter\cst@ref@name%
257   \fi
258 \else
259   \expandafter\cst@ref@name@%

```

⁹If \@undefined is ever fixed, this will no longer be needed. If ε-TEx was required, the \ifdef would be a choice here; however, ε-TEx is not going to be required just for this.

```

260   \fi}
261 \newcommand*{\cst@ref@name}[3]{%
262   \ifcst@notesbefore
263     #3\space#2\space#1%
264   \else
265     #1\space#2\space#3%
266   \fi}
267 \newcommand*{\cst@ref@name@}[3]{#1}

```

\cst@setrefname Setting up the section name is a tricky affair. If no section is defined, then the whole process is skipped. Otherwise, the first check made is if the default language matches the definition given. If so, the heading is changed now.

```

268 \@ifundefined{cst@refsec}
269   {\let\cst@setrefname@gobblefour}
270   {\newcommand*{\cst@setrefname}[4]{
271     \edef\cst@tempa{#1}%
272     \ifx\cst@tempa\cst@language
273       \expandafter\renewcommand\expandafter*\expandafter{%
274         \cst@refsec}
275       {\cst@refname{#2}{#3}{#4}}}
276   \fi}

```

cst@tempa At the beginning of the document, a check needs to be made for babel and biblatax. For the later, a low-level hack is made to attach to the mechanism. For babel the appropriate commands are added to the \captions... macro.

```

277   \AtBeginDocument{
278     \@ifpackageloaded{biblatax}
279       {\def\cst@tempa{\csgappto{bib@strings@#1}}
280        \expandafter\cst@tempa\expandafter{\expandafter\renewcommand%
281          \expandafter*\expandafter{\cst@refsec}{%
282            \cst@refname{#2}{#3}{#4}}}}
283     \@ifpackageloaded{babel}
284       {\def\cst@tempa{\expandafter\addto\expandafter{%
285         \csname captions#1\endcsname}}
286        \expandafter\cst@tempa\expandafter
287        {\expandafter\renewcommand\expandafter*\expandafter{%
288          {\cst@refsec}\cst@refname{#2}{#3}{#4}}}}

```

To make sure the changes are applied *now*, the current language is re-selected.

```

289           \expandafter\selectlanguage\expandafter{\languagename}
290           {}{}}

```

Default names are loaded for a range of languages. Most journals stick to the same words, with only the order changing.

```

291 \cst@setrefname{english}{References}{and}{Notes}
292 \cst@setrefname{UKenglish}{References}{and}{Notes}
293 \cst@setrefname{ngerman}{Literatur}{und}{Notizen}
294 \cst@setrefname{german}{Literatur}{und}{Notizen}
295 \cst@setrefname{french}{R\'ef\'erences}{et}{Notes}
296 \cst@setrefname{frenchb}{R\'ef\'erences}{et}{Notes}

```

8 Configuration files

Each journal style needs slightly differing commands to get the formatting just right. This is handled here, with each style in a separate file. There is not a lot happening in most of these files, as the information is by its nature quite repetitive.

8.1 RSC style

```
297 \ProvidesFile{rsc.jdf}
298   [2008/04/14 v1.2b RSC journal style]
299 \AtBeginDocument{%
300   \renewcommand{\figurename}{Fig.}}
301 \captionsetup{labelsep=quad,labelfont=bf}
302 \setkeys[cst]{opt}{
303   radprefix=true,
304   rademph=true,
305   radsuper=false,
306   radhyphen=true,
307   abbrempth=true,
308   abbrcomma=false}
```

8.2 Angew. Chem. style

```
309 \ProvidesFile{angew.def}
310   [2008/04/14 v1.2b Angew. Chem. journal style]
311 \captionsetup{labelsep=period,labelfont={bf,it},font=sf,singlelinecheck=off}
312 \captionsetup[table]{labelsep=colon}
313 \setkeys[cst]{opt}{
314   radprefix=true,
315   rademph=true,
316   radsuper=false,
317   radhyphen=false,
318   abbrempth=false,
319   abbrcomma=false}
```

8.3 J. Organomet. Chem. style

```
320 \ProvidesFile{jomc.def}
321   [2008/04/14 v1.2b J. Organomet. Chem. journal style]
322 \captionsetup{labelsep=period}
323 \captionsetup[table]{labelsep=newline,singlelinecheck=off}
324 \AtBeginDocument{%
325   \renewcommand{\figurename}{Fig.}}
326 \setkeys[cst]{opt}{
327   radprefix=true,
328   rademph=true,
329   radsuper=true,
330   radhyphen=false,
331   abbrempth=false,
332   abbrcomma=false,
333   notesbefore=true}
```

8.4 Tetrahedron Lett. style

```

334 \ProvidesFile{tetlett.def}
335   [2008/04/14 v1.2b Tetrahedron Lett. journal style]
336 \captionsetup{labelsep=period,singlelinecheck=off,labelfont=bf}
337 \setkeys[cst]{opt}{
338   radprefix=true,
339   rademph=true,
340   radsuper=false,
341   radhyphen=true,
342   abbrempf=false,
343   abbrcomma=true,
344   notesbefore=true}

```

8.5 *J. Am. Chem. Soc.* style

```

345 \ProvidesFile{jacs.jdf}
346   [2008/04/14 v1.2b J. Am. Chem. Soc. journal style]
347 \DeclareCaptionLabelSeparator{perquad}{.\quad}
348 \captionsetup{labelfont={bf,it,sf},textfont=sf,labelsep=perquad}
349 \captionsetup[figure]{textfont=rm}
350 \captionsetup{singlelinecheck=off}
351 \setkeys[cst]{opt}{
352   radprefix=true,
353   rademph=true,
354   radsuper=true,
355   radhyphen=false,
356   abbrempf=false,
357   abbrcomma=true,
358   notesbefore=true}
359 \floatstyle{plaintop}
360 \restylefloat{scheme}
361 \floatstyle{plain}
362 \cst@notesbeforefalse

```

8.6 *Inorg. Chem.* style

Almost exactly the same as for *J. Am. Chem. Soc.*, so most of the work is left to *jacs.jdf*.

```

363 \ProvidesFile{ic.jdf}
364   [2008/04/14 v1.2b Inorg. Chem. journal style]
365 \input {jacs.jdf}
366 \captionsetup{textfont=rm}

```

8.7 *J. Phys. Chem.* style

```

367 \ProvidesFile{jpc.jdf}
368   [2008/04/14 v1.2b J. Phys. Chem. journal style]
369 \DeclareCaptionFormat{labelcaps}{\MakeUppercase{#1}\#2#3}
370 \captionsetup{font=bf,labelsep=colon,format=labelcaps}
371 \captionsetup[figure]{format=plain,textfont=md,labelsep=period}
372 \captionsetup{singlelinecheck=off}
373 \setkeys[cst]{opt}{
374   radprefix=true,
375   rademph=true,
376   radsuper=false,
377   radhyphen=false,

```

```

378   abbrempmh=false,
379   abbrcomma=true,
380   notesbefore=true}
381 \floatstyle{plaintop}
382 \restylefloat{scheme}
383 \floatstyle{plain}
384 \cst@notesbeforefalse

```

8.8 Org. Lett. style

```

385 \ProvidesFile{orglett.jdf}
386 [2008/04/14 v1.2b Org. Lett. journal style]
387 \RequirePackage{xcolor}

```

\OrgLettColour To allow the user to control the colour of the “bars” in this style, an additional macro is provided. The purple colour looks about right for matching the printed journal, but if anyone has a better suggestion please let the package author know.
388 \newcommand*{\OrgLettColour}{purple}

\fs@orglett In order to get the distinctive coloured bars used by *Org. Lett.*, a new style for floats is needed. This is based on the `ruled` style from the `float` package.

```

389 \newcommand*{\fs@orglett}{%
390   \def\@fs@cfont{\bfseries}%
391   \let\@fs@capt\floatc@ruled
392   \def\@fs@pre{\begingroup\color{\OrgLettColour}%
393     \hrule height12pt depth0pt \kern2pt\endgroup}%

```

This is the same \fs@mid as is used in the float package for `plaintop` floats.

```

394   \def\@fs@mid{\vspace\belowcaptionskip\relax}%
395   \def\@fs@post{\begingroup\color{\OrgLettColour}\kern2pt
396     \hrule height1.5pt depth0pt\endgroup}%
397   \let\@fs@iftopcapt\iftrue}

```

\fs@orglettfig Figures need to be slightly different, so an almost identical command is needed.

```

398 \newcommand*{\fs@orglettfig}{%
399   \def\@fs@cfont{\bfseries}%
400   \let\@fs@capt\floatc@plain
401   \def\@fs@pre{\begingroup\color{\OrgLettColour}%
402     \hrule height12pt depth0pt \kern2pt\endgroup}%
403   \def\@fs@mid{\vspace\abovecaptionskip\relax}%
404   \def\@fs@post{\begingroup\color{\OrgLettColour}\kern2pt
405     \hrule height1.5pt depth0pt\endgroup}%
406   \let\@fs@iftopcapt\iffalse}

```

The new style is now applied. Users can change back to normal floats by changing back to the plain style.

```

407 \floatstyle{orglettfig}
408 \restylefloat{figure}
409 \floatstyle{orglett}
410 \restylefloat{scheme}
411 \restylefloat{table}

```

The more usual style commands now occur.

```

412 \DeclareCaptionLabelSeparator{perquad}{.\quad}
413 \captionsetup{labelfont=bf,labelsep=perquad}

```

```

414 \setkeys[cst]{opt} {
415   radprefix=true,
416   rademph=true,
417   radsuper=true,
418   radhyphen=false,
419   abbrempth=false,
420   abbrcomma=true,
421   notesbefore=true}
422 \cst@notesbeforefalse

```

8.9 The empty style — none

To allow the user to load the extra macros provided here without any style changes, a “do nothing” style is provided. It simply makes sure that very little changes compared to the L^AT_EX kernel. This requires undoing the defaults provided above. For commands where a default is needed (*e.g.* the `\latin` command) the style of the RSC is followed. As the `float` package has been loaded, notice that captions will be placed below floats even if the `\caption` command appears above the contents of the floating environment.

```

423 \ProvidesFile{none.jdf}
424   [2008/04/14 v1.2b Empty journal style]
425 \floatstyle{plain}
426 \restylefloat{table}
427 \labelformat{figure}{\#1}
428 \labelformat{table}{\#1}
429 \floatplacement{table}{tbp}
430 \floatplacement{figure}{tbp}
431 \AtBeginDocument{
432   \floatplacement{scheme}{tbp}
433   \labelformat{scheme}{\#1}}

```

9 Change History

v1.0	Added <code>siunits</code> option	1
	General: Initial release of package . .	1
v1.0a	General: Added <i>J. Phys. Chem.</i> style .	18
	Added <i>Org. Lett.</i> style	19
	Fixed incorrect Latin formatting	
	for <code>angew</code> option	17
	No longer load <code>fixltx2e</code> pack-	
	age	8
v1.0b	General: Added <code>microtype</code> and	
	<code>notes2bib</code> to template	1
	Fixed formatting of alkyls	17
	Sorted a problem with <code>babel</code>	
	and figure name format	17
v1.1	General: Added phrases option . . .	1
	Added <code>siunits</code> option	1
	<code>\cst@add@punct:</code> New macro . .	14
	<code>\cst@add@punct@:</code> New macro . .	14
	<code>\cst@addpunct:</code> New macro . . .	14
	<code>\cst@latin:</code> New macro	13
	<code>\cst@varnothing:</code> New macro . . .	11
	<code>\eg:</code> Adds comma for ACS journals	13
	<code>\ie:</code> Adds comma for ACS journals	13

v1.1a	General: Fixed error in documentation compilation under L ^A T _E X . . .	<u>1</u>	v1.1h	General: Added <code>tetlett</code> style . . .	<u>17</u>
v1.1b	General: Load caption even when journal style does not exist . . .	<u>14</u>	v1.2	General: Added <code>xkeyval</code> interface . .	<u>8</u>
v1.1c	General: Added <code>Slunits</code> option . . .	<u>1</u>		Re-write of reference-section renaming code	<u>15</u>
	Added <code>frenchb</code> alias for <code>french</code>	<u>16</u>		Re-write of units section	<u>10</u>
	Added <code>german</code> alias for <code>ngerman</code>	<u>16</u>		Removed obsolete <code>ch</code> and chapter options	<u>1</u>
	Documentation improved	<u>1</u>		Various internal tweaks	<u>1</u>
	Fixed problems with capitalisation of <code>Slunits</code>	<u>1</u>	\cst@add@punct@:	Internal tweaks	<u>14</u>
	\standardstate: Altered angle of rotation for better appearance .	<u>11</u>	\cst@commaabbr:	New macro	<u>13</u>
	Definition only occurs if user does not have own version	<u>11</u>	\cst@commapunct:	Name change from \cst@punct	<u>14</u>
v1.1d	General: Require caption in all cases	<u>8</u>	\cst@latin:	Change of definition to allow better working with run-time options	<u>13</u>
v1.1e	General: Fixed packaging problem .	<u>1</u>	\cst@nocommaabbr:	New macro	<u>13</u>
v1.1f	\cst@addpunct: No longer used when comma not required . . .	<u>14</u>	\cst@radical:	Re-write to allow definition to change at run-time	<u>11</u>
	\cst@eg: New macro	<u>13</u>	\cst@ref@name:	New macro	<u>15</u>
	\cst@etal: New macro	<u>13</u>	\cst@ref@name@:	New macro	<u>15</u>
	\cst@etc: New macro	<u>13</u>	\cst@refname:	New macro	<u>15</u>
	\cst@ie: New macro	<u>13</u>	\cst@refsec:	New macro	<u>15</u>
	\eg: Definition comma-mode dependent	<u>13</u>	\cst@setrefname:	New macro	<u>16</u>
	Fixed problem with full stop spacing	<u>13</u>	\cst@tempa:	New macro	<u>8</u>
	\etal: Fixed problem with full stop spacing	<u>13</u>	\cst@tempb:	New macro	<u>8</u>
	\ie: Definition comma-mode dependent	<u>13</u>	\cst@xspace:	New definition . . .	<u>11</u>
	Fixed problem with full stop spacing	<u>13</u>	\eg:	Dynamic definition for comma mode	<u>13</u>
v1.1g	General: Added <code>jomc</code> style	<u>17</u>	\ie:	Dynamic definition for comma mode	<u>13</u>
	Fixed problem with cross-referencing when <code>babel</code> is not loaded	<u>12</u>	\latinemphoff:	New definition to work with <code>xkeyval</code> system . .	<u>13</u>
			\latinemphon:	New definition to work with <code>xkeyval</code> system . .	<u>13</u>
v1.2a	General: Fixed error with restyling scheme floats, caused by change in <code>chemscheme</code>	<u>1</u>	v1.2a	General: Fixed error with restyling scheme floats, caused by change in <code>chemscheme</code>	<u>1</u>
v1.2b	General: Change due to name change of <code>si</code> package to <code>siunitx</code> .	<u>10</u>			

10 Index

Numbers written in italic refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

Symbols	A	
\'	abbrempf (option)	<u>5</u>
	abbrcomma (option)	<u>5</u>

C		L	
\c@bibnote	240	271, 272, 277, 279, 280, 284, 286	\latin 5, 164, 176, 193–196
chemcompounds (option)	3	\cst@tempb . 15, 29, 208	\latinemphoff . 5, 164
\cmc	4, 92	\cst@varnothing . 108	\latinemphon . 5, 164
\cst@add@punct ..		\cst@xspace	
. 205, 206, 210, 213		. 136, 137, 174, 176, 178, 203, 219	
\cst@add@punct@ ..		\cstsetup	
. 207, 208		. 3, 83, 168, 169, 236	
\cst@addpunct 199, 204		\cubiccentimeter	
\cst@autonotesfalse 92, 94	
. 34			
\cst@autonotestrue ..		E	
. 38		\eg 5, 171	
\cst@boolkey 17, 19–28		\etal 5, 171	
\cst@commaabbr ..		\etc 5, 171	
. 181, 188, 197			
\cst@commapunct ..		F	
. 215, 219		\fs@orglett	389
\cst@disablekey ..	73	\fs@orglettfig ..	398
\cst@eg	193		
\cst@emph 116, 132, 134		H	
\cst@etal	178, 193	\Hz 4, 92	
\cst@etc	174, 193		
\cst@hyphen 116, 132, 134		I	
\cst@ie	193	\iBu 4, 141	
\cst@journal		\ie 5, 171	
. 52, 220, 222, 224		\ifcst@abbrcomma	
\cst@language ..	52, 272 19, 180, 187	
\cst@latin	164	\ifcst@abbremph 19, 165	
\cst@nocommaabbr ..		\ifcst@autonotes	
. 183, 190, 197	 29, 240, 247	
\cst@notesbeforefalse ..		\ifcst@chemcompounds	
. 362, 384, 422	 19, 69	
\cst@notesfalse ..	33	\ifcst@notes .. 29, 246	
\cst@notesttrue ..	37, 42	\ifcst@notesbefore	
\cst@radical 19, 262	
. 113, 141–146		\ifcst@phrases 19, 171	
\cst@ref@name ..	245	\ifcst@radempf 19, 126	
\cst@ref@name@ ..	245	\ifcst@radhypen	
\cst@refname 19, 116	
. 245, 275, 282, 288		\ifcst@radprefix	
\cst@refsec 19, 131	
. 231, 274, 281, 288		\ifcst@radsuper 19, 121	
\cst@setrefname ..		\ifcst@xspace . 19, 138	
. 268, 291–296		\invacuo 5, 171	
\cst@super 116, 132, 134		\iPr 4, 141	
\cst@tempa			
. 15, 29, 207, 208,		J	
		journal (option) ... 2, 3	
			X
		xspace (option) 4	