

# The citeall package, v1.0

Ulrike Fischer

February 18, 2015

## 1 Important

`citeall` works only together with `biblatex`. `biblatex` should be loaded before `citeall`.

The package relies on some inner working of `biblatex`, so it could break with future versions.

## 2 The aim of the package

The `citeall` package is a package to help to adapt and debug `biblatex` citation styles. When adapting such a style one often needs to inspect the output of examples. While it is easy with `\nocite{*}` to output all entries of a bib-file in the bibliography it is more troublesome to show citations. So I wrote a (very) small package which allows me to show citations of all entries of the bib-files.

## 3 The command

The main command of the package is called like the package and has two optional arguments:

`\citeall` [*<list of commands>*] [*<number of entries>*]

The second optional argument sets the number of entries of the .bib (more precisely the .bbl-file) printed by `\citeall`. By default everything is cited.

The first optional argument is a comma separated list. For each entrykey in the .bbl `\citeall` will loop through this list and pass to each item the entrykey as last argument. By default this list consist simply of a `\cite` command. The items don't need to be cite commands. As the examples show you can add text and other commands.

- The last command should be something that can handle the entry key argument.
- If there are brackets e.g. from optional argument of a `\cite` you should protect them with braces.
- If there are commas you should protect them with braces.

- If you want to insert a paragraph break, use `\endgraf`
- Don't overdo the system. It is meant for simple debugging not for complicated citation printouts.

## 4 Some examples

```
\citeall BookAuthor 2015      \citeall [] [1] BookAuthor 2015
      Fischer 2015
      Muster 2015
```

```
\citeall[\fullcite] Eva BookAuthor (2015). a book. Ed. by Ben Editor. Publisher
      Ulrike Fischer (2015). The citeall package
      Max Muster (2015). "Title of Article". In: Testjournal 1.2, p. 15
```

```
\citeall[\cite[15],\cite] BookAuthor 2015, p. 15, ibid.
      Fischer 2015, p. 15, ibid.
      Muster 2015, p. 15, ibid.
```

```
\citeall[Key: \textcolor{red},{\cite[15]},Test ibid: \cite]
      Key: book2015, BookAuthor 2015, p. 15, Test ibid: ibid.
      Key: fischer2015, Fischer 2015, p. 15, Test ibid: ibid.
      Key: article2015, Muster 2015, p. 15, Test ibid: ibid.
```

```
\citeall[{\cite[15]},\endgraf \cite]
      BookAuthor 2015, p. 15,
      ibid.
      Fischer 2015, p. 15,
      ibid.
      Muster 2015, p. 15,
      ibid.
```

## 5 Configuration

```
\citeallgroupseparator
\citeallseparator
\citeallfinentry
\citealldefaultcite
```

By default the item of an entry are separated by a comma and a space. This can be changed by redefining `\citeallseparator`. The last item is finished by `\citeallfinentry` (default nothing). The entries are separated by a `\par`, this can be changed by redefining `\citeallgroupseparator`.