

# English Module for datetime2 Package

Nicola L. C. Talbot

2015-04-09 (v1.01)

## Abstract

This is the English language module for the `datetime2` package. If you want to use the settings in this module you must install it in addition to installing `datetime2`. If you use `babel` or `polyglossia`, you will need this module to prevent them from redefining `\today`. The `datetime2 useregional` setting must be on (`text` or `numeric`) for the language styles to be set. Alternatively, you can set them in the document using `\DTMsetstyle`, but without the `useregional` setting on the style will be changed by `\date<language>`.

## Contents

<b>1</b>	<b>Introduction</b>	<b>3</b>
<b>2</b>	<b>Base module</b>	<b>4</b>
<b>3</b>	<b>English (no region)</b>	<b>4</b>
<b>4</b>	<b>English (GB)</b>	<b>4</b>
<b>5</b>	<b>English (US)</b>	<b>6</b>
<b>6</b>	<b>English (CA)</b>	<b>7</b>
<b>7</b>	<b>English (AU)</b>	<b>7</b>
<b>8</b>	<b>English (NZ)</b>	<b>8</b>
<b>9</b>	<b>English (GG)</b>	<b>8</b>
<b>10</b>	<b>English (JE)</b>	<b>8</b>
<b>11</b>	<b>English (IM)</b>	<b>8</b>
<b>12</b>	<b>English (MT)</b>	<b>8</b>
<b>13</b>	<b>English (IE)</b>	<b>9</b>

<b>14 The Code</b>	<b>9</b>
14.1 Base Code ( <code>datetime2-english-base.ldf</code> ) . . . . .	9
14.2 Default English Code ( <code>datetime2-english.ldf</code> ) . . . . .	14
14.3 English (GB) Code ( <code>datetime2-en-GB.ldf</code> ) . . . . .	16
14.4 English (US) Code ( <code>datetime2-en-US.ldf</code> ) . . . . .	21
14.5 English (Canada) Code ( <code>datetime2-en-CA.ldf</code> ) . . . . .	26
14.6 English (Australia) Code ( <code>datetime2-en-AU.ldf</code> ) . . . . .	31
14.7 English (New Zealand) Code ( <code>datetime2-en-NZ.ldf</code> ) . . . . .	35
14.8 English (GG) Code ( <code>datetime2-en-GG.ldf</code> ) . . . . .	40
14.9 English (JE) Code ( <code>datetime2-en-JE.ldf</code> ) . . . . .	45
14.10 English (IM) Code ( <code>datetime2-en-IM.ldf</code> ) . . . . .	50
14.11 English (MT) Code ( <code>datetime2-en-MT.ldf</code> ) . . . . .	55
14.12 English (IE) Code ( <code>datetime2-en-IE.ldf</code> ) . . . . .	60
<b>Change History</b>	<b>65</b>
<b>Index</b>	<b>65</b>

# 1 Introduction

This bundle provides the English modules for `datetime2`. The basic `english` module is used when `english` has been detected as one of the document's language settings but no regional variant has been detected. Note that the `tracklang` package can't detect the variant passed to `polyglossia` unless it's been passed as a document class option or passed to `tracklang`. See the `tracklang` documentation for further details.

Here are some example usage for British English with `polyglossia`:

1. Pass `british` in the document class option list:

```
\documentclass[british]{article}

\usepackage{fontspec}
\usepackage{polyglossia}
\usepackage{datetime2}
```

(You need to set the `useregional` option to either `text` or `numeric` to enable the `en-GB` or `en-GB-numeric` styles.)

2. Pass `en-GB` in the document class option list and use `polyglossia`'s language interface:

```
\documentclass[en-GB]{article}

\usepackage{fontspec}
\usepackage{polyglossia}
\setdefaultlanguage[variant=uk]{english}

\usepackage{datetime2}
```

(You need to set the `useregional` option to either `text` or `numeric` to enable the `en-GB` or `en-GB-numeric` styles.)

3. Pass `en-GB` to `datetime2`:

```
\documentclass{article}

\usepackage{fontspec}
\usepackage{polyglossia}
\setdefaultlanguage[variant=uk]{english}

\usepackage[en-GB]{datetime2}
```

In this last example, the style is automatically switched to `en-GB`.

Note that if you pass the language setting through the `datetime2` package option list (as in the above example) this will also set the `useregional` option to `text`.

If you’re not using `babel` or `polyglossia` but still want to use the English modules, you can similarly use the language or regional setting in the document class or `datetime2` package options. Note that since `datetime2` loads `tracklang`, this setting will be remembered by any subsequently loaded packages that use `tracklang` to determine the document language settings.

For example, to use the `en-GB` date style without loading `babel` or `polyglossia`:

```
\documentclass{article}
\usepackage[en-GB]{datetime2}
\begin{document}
\today
\end{document}
```

## 2 Base module

The `english-base` module is loaded by all the English modules. It provides the commands that produce text, such as the month names. It also provides a 12 hour time style called `englishampm`.

## 3 English (no region)

The default `english` module is used when English has been set as one of the document languages, but no regional variant has been detected or there is no support for the given region.

This basic module provides the date-time style `english` which uses the same style as L<sup>A</sup>T<sub>E</sub>X’s default `\today`. (That is, the middle-endian date style.) This style ignores most of the settings, including `showdow` and the date separators. The time style uses the `englishampm` style defined in the base module which uses the package-wide `hourminsep` setting. The zone style is the same as that provided by the `default` style. (That is, numerical ISO or just “Z”.) The full date, time and zone style (used by `\DTMdisplay`) have spaces between each block. The `showdate`, `showzone`, `showseconds`, `showzoneminutes` and `showisoZ` `datetime2` settings are honoured.

This module checks for the existence of `\dateenglish` or `\date⟨dialect⟩` (in the case of an unknown English variant that doesn’t match any of the supplied English dialect modules). If it exists, the command will be redefined so that it sets the date, time and zone styles to `english` if the `useregional` setting is set to `text`. If the setting is `numeric` the `default` numeric style will be used as the lack of region makes it ambiguous.

## 4 English (GB)

The `en-GB` module is loaded if British English has been specified. This may be specified through options such as `british`, `en-GB` or `UKenglish`. (See the note on `polyglossia` in §1.)

This module defines the text style `en-GB` and the numeric style `en-GB-numeric` style. The `en-GB` style will automatically be set if the `useregional` option is set to `text`. The `en-GB-numeric` style will automatically be set if the `useregional` option is set to `numeric`.

The `en-GB` time style uses the base `englishampm` style.

There are a number of settings provided that can be used in `\DTMlangsetup` to modify the date style. These are:

`daymonthsep` The separator between the day and the month name in the `en-GB` style. This defaults to `\space`.

`monthlyearsep` The separator between the month name and year in the `en-GB` style. This defaults to `\space`.

`datesep` The separator between the date numbers in the `en-GB-numeric` style. This defaults to `/` (slash).

`timesep` The separator between the hours and minutes in the `en-GB-numeric` style. This defaults to `:` (colon).

`datetimesep` The separator between the date and time for the full date-time format (as used by `\DTMdisplay`) for both the `en-GB` and `en-GB-numeric` styles. This defaults to `\space`.

`timezonesep` The separator between the time and zone for the full date-time format (as used by `\DTMdisplay`) for both the `en-GB` and `en-GB-numeric` styles. This defaults to `\space`.

`abbr` This is a boolean key. If `true`, the month (and week day name if shown) is abbreviated for the `en-GB` style. The default is `false`.

`mapzone` This is a boolean key. If `true` the time zone mappings are applied. (The default is `true`.) The `en-GB` and `en-GB-numeric` styles set the mappings `GMT` (`UTC+00:00`) and `BST` (`UTC+01:00`). Other time zone mappings that have previously been set (for example, by another regional style) will remain unchanged unless you redefine `\DTMresetzones` to reset or unset them.

`ord` This may take one of the following values: `level` (ordinal suffix level with the number), `raise` (ordinal suffix as a superscript<sup>1</sup>), `omit` (omit the ordinal suffix) and `sc` (small caps ordinal suffix). If you want a different style you can redefine `\DTMenumGBfmtordsuffix` which takes one argument (the suffix). Take care if `\DTMenumGBfmtordsuffix` contains fragile commands, as they will need to be protected against expansion.

---

<sup>1</sup>Just in case you plan to send me an irate email on this issue, the superscript is a regional handwriting style not an invention of word processors although they have adopted the style. I was using this style in school in the 1970s before I'd ever heard of a word processor so please don't tell me I've picked up the habit from Word. I'm not a time-traveller, nor were my primary school teachers—that I know of! If, conversely, you want to know why the default is `level` rather than `raise`, it's because the main purpose of the `datetime2` package is to provide an *expandable* text format and `\textsuperscript` isn't expandable.

**showdayofmonth** A boolean key that determines whether or not to show the day of the month. The default value is **true**. If **false** the day-month separator is also omitted.

**showyear** A boolean key that determines whether or not to show the year. The default value is **true**. If **false** the month-year separator is also omitted.

The above settings are specific to this module. In addition, the **showdow** boolean option provided by the **datetime2** package is also checked to determine whether or not to show the day of the week in the **en-GB** style.

The time zone checks the **mapzone** setting (described above). If it's set, then **\DTMusezonemapordefault** is used otherwise a numeric  $\langle TZH \rangle \langle sep \rangle \langle TZM \rangle$  is displayed. (The minute part will be omitted if the **datetime2** package option **showzoneminutes** is set to **false**. The zone style ignores the **showisoZ** option.

## 5 English (US)

The **en-US** module is loaded if US English has been specified. This may be done through options such as **american**, **en-US** or **USenglish**. (See the note on polyglossia in §1.)

This module defines the styles **en-US** and **en-US-numeric**. There a number of settings that can be used in **\DTMlangsetup** to modify these styles. They are:

**monthdaysep** The separator between the month name and the day in the **en-US** style. The default is **\space**

**dayyearsep** The separator between the day and the year in the **en-US** style. The default is **,** **\space**

**datesep** The separator between the date numbers in the **en-US-numeric** format.

**timesep** The separator between the hour and minutes in the **en-US-numeric** format.

**datetimesep** The separator between the date and the time for the full style used by **\DTMdisplay** for the **en-US** and **en-US-numeric**. The default is **\space**

**timezonesep** The separator between the times and zone for the full style used by **\DTMdisplay**. The default is **\space**

**abbr** This is a boolean key. If **true**, the month is abbreviated. The default is **false**.

**mapzone** This is a boolean key. If **true** the time zone mappings are applied. (The default is **false**.) The **en-US** style sets the mappings ADT (UTC-03:00), AST (UTC-04:00), EST (UTC-05:00), CST (UTC-06:00), MST (UTC-07:00) and PST (UTC-08:00). If you want to use different mappings, you can redefine **\DTMusezonemaps**. Other time zone mappings

that have previously been set (for example, by another regional style) will remain unchanged unless you redefine `\DTMresetzones` to reset or unset them.

`ord` The same as the `en-GB` style except that the default value is `omit`.

`showdayofmonth` A boolean key that determines whether or not to show the day of the month. The default value is `true`. If `false` the day-year separator is also omitted.

`showyear` A boolean key that determines whether or not to show the year. The default value is `true`. If `false` the day-year separator is also omitted if the day of the month is shown otherwise both the day-year and month-day separators are omitted.

The `en-US` style doesn't use the `showdow` setting.

The `en-US` time style uses the `englishampm`. The `en-US-numeric` uses a 24 hour style. The time zone checks the `mapzone` setting (described above). If it's set, then `\DTMusezonemapordefault` is used otherwise a numeric  $\langle TZH \rangle : \langle TZM \rangle$  is displayed. (The minute part will be omitted if the `datetime2` package option `showzoneminutes` is set to `false`. The zone style ignores the `showisoZ` option.

## 6 English (CA)

The `en-CA` module is loaded if Canadian English has been specified. This may be done through options such as `en-CA` or `canadian`. (See the note on polyglossia in §1.)

This module provides the `en-CA` and `en-CA-numeric` styles that are virtually identical to the `en-US` and `en-US-numeric` style. These have the same options as for the US styles but the zone maps are provided by `\DTMenzonemaps`, which can be redefined as required. This has the additional time zones NDT and NST. Note that other than NDT, daylight saving isn't taken into account.

## 7 English (AU)

The `en-AU` module is loaded if Australian English has been specified. This may be done through options such as `en-AU` or `australian`. (See the note on polyglossia in §1.)

This module provides the `en-AU` and `en-AU-numeric` styles that are virtually identical to the `en-GB` and `en-GB-numeric` styles. These have the same options as the GB styles (except that the default value of `ord` is `omit` rather than `level` and the default value of `mapzone` is `false`) but the zone maps are provided by `\DTMenzonemaps`, which can be redefined as required. Note that daylight saving isn't taken into account.

## 8 English (NZ)

The `en-NZ` module is loaded if New Zealand English has been specified. This may be done through options such as `en-NZ` or `newzealand`. (See the note on polyglossia in §1.)

This module provides the `en-NZ` and `en-NZ-numeric` styles that are virtually identical to the AU styles but the zone maps are provided by `\DTMenzzonemaps`, which can be redefined as required.

## 9 English (GG)

The Guernsey English `en-GG` and `en-GG-numeric` styles are like the British English `en-GB` and `en-GB-numeric` styles, but replace `enGB` with `enGG` in the command names. This style can be loaded by using `en-GG` as a document class option or as a package option for either `tracklang` or `datetime2`.

## 10 English (JE)

The Jersey English `en-JE` and `en-JE-numeric` styles are like the British English `en-GB` and `en-GB-numeric` styles, but replace `enGB` with `enJE` in the command names. This style can be loaded by using `en-JE` as a document class option or as a package option for either `tracklang` or `datetime2`.

## 11 English (IM)

The Isle of Man `en-IM` and `en-IM-numeric` styles are like the British English `en-GB` and `en-GB-numeric` styles, but replace `enGB` with `enIM` in the command names. This style can be loaded by using `en-IM` as a document class option or as a package option for either `tracklang` or `datetime2`.

## 12 English (MT)

The Malta English `en-MT` and `en-MT-numeric` styles are like the British English `en-GB` and `en-GB-numeric` styles, but replace `enGB` with `enMT` in the command names. This style can be loaded by using `en-MT` as a document class option or as a package option for either `tracklang` or `datetime2`.

There are two main differences in the `en-GB/en-GB-numeric` and `en-MT/en-MT-numeric` styles: the `ord` option (for the text styles) defaults to `omit` and the CET (+01:00) and CEST (+02:00) time zone mappings are added (for both the text and numeric styles).

## 13 English (IE)

The Republic of Ireland English `en-IE` and `en-IE-numeric` styles are like the British English `en-GB` and `en-GB-numeric` styles, but replace `enGB` with `enIE` in the command names. This style can be loaded by using `en-IE` as a document class option or as a package option for either `tracklang` or `datetime2`. You will need at least version 1.2 of the `tracklang` package installed.

The only difference in the `en-GB/en-GB-numeric` and `en-IE/en-IE-numeric` styles is that the `+01:00` time zone is mapped to IST instead of BST. If you prefer WET/WEST time zones, you can do:

```
\renewcommand*{\DTMenglishzonemap}{%
  \DTMdefzonemap{00}{00}{WET}%
  \DTMdefzonemap{01}{00}{WEST}%
}
```

For Irish Gaelic you need the `irish` module instead.

## 14 The Code

### 14.1 Base Code (`datetime2-english-base.1df`)

This file contains the code common to all the English regional variations. Identify module

```
1 \ProvidesDateTimeModule{english-base}[2015/04/09 v1.01 (NLCT)]
```

Since the main emphasize of the `datetime2` package is to provide expandable dates where possible, the commands here need to be expandable. (Anything that wasn't expandable would need to be protected.) Therefore the default ordinal format is a simple expandable format (which is why `fmtcount` isn't being used).

```
\DTMenglishordinal
1 \newcommand*{\DTMenglishordinal}[1]{%
2   \number#1 % space intended
3   \DTMenglishfmtordsuffix{%
4     \ifcase#1
5       \or \DTMenglishst
6       \or \DTMenglishnd
7       \or \DTMenglishrd
8       \or \DTMenglishth
9       \or \DTMenglishth
10      \or \DTMenglishth
11      \or \DTMenglishth
12      \or \DTMenglishth
13      \or \DTMenglishth
14      \or \DTMenglishth
15      \or \DTMenglishth
16      \or \DTMenglishth
17      \or \DTMenglishth
18      \or \DTMenglishth}
```

```

19      \or \DTMenglishth
20      \or \DTMenglishth
21      \or \DTMenglishth
22      \or \DTMenglishth
23      \or \DTMenglishth
24      \or \DTMenglishth
25      \or \DTMenglishth
26      \or \DTMenglishst
27      \or \DTMenglishnd
28      \or \DTMenglishrd
29      \or \DTMenglishth
30      \or \DTMenglishth
31      \or \DTMenglishth
32      \or \DTMenglishth
33      \or \DTMenglishth
34      \or \DTMenglishth
35      \or \DTMenglishth
36      \or \DTMenglishst
37      \fi
38  }%
39 }

```

Just in case a user has some need to change the ordinal suffixes, these are provided as commands.

```

\DTMenglishst
40 \newcommand*{\DTMenglishst}{st}

\DTMenglishnd
41 \newcommand*{\DTMenglishnd}{nd}

\DTMenglishrd
42 \newcommand*{\DTMenglishrd}{rd}

\DTMenglishth
43 \newcommand*{\DTMenglishth}{th}

```

`\DTMenglishfmtordsuffix` The suffix can have a format applied to it (for example, made a superscript or converted to small caps). The default ignores the argument, which makes it consistent with TeX's default date format. This can be changed by regional modules.

```
44 \newcommand*{\DTMenglishfmtordsuffix}[1]{}
```

`\DTMenglishmonthname` English month names.

```

45 \newcommand*{\DTMenglishmonthname}[1]{%
46   \ifcase#1
47   \or
48   January%
49   \or
50   February%

```

```

51   \or
52   March%
53   \or
54   April%
55   \or
56   May%
57   \or
58   June%
59   \or
60   July%
61   \or
62   August%
63   \or
64   September%
65   \or
66   October%
67   \or
68   November%
69   \or
70   December%
71   \fi
72 }

```

\DTMenglishshortmonthname Abbreviated English month names.

```

73 \newcommand*{\DTMenglishshortmonthname}[1]{%
74   \ifcase#1
75     \or
76     Jan%
77     \or
78     Feb%
79     \or
80     Mar%
81     \or
82     Apr%
83     \or
84     May%
85     \or
86     Jun%
87     \or
88     Jul%
89     \or
90     Aug%
91     \or
92     Sep%
93     \or
94     Oct%
95     \or
96     Nov%
97     \or
98     Dec%

```

```

99    \fi
100 }

\DTMenglishweekdayname English day of week names.
101 \newcommand*{\DTMenglishweekdayname}[1]{%
102   \ifcase#1
103     Monday%
104   \or
105     Tuesday%
106   \or
107     Wednesday%
108   \or
109     Thursday%
110   \or
111     Friday%
112   \or
113     Saturday%
114   \or
115     Sunday%
116   \fi
117 }

```

```

\DTMenglishweekdayname English abbreviated day of week names.
118 \newcommand*{\DTMenglishshortweekdayname}[1]{%
119   \ifcase#1
120     Mon%
121   \or
122     Tue%
123   \or
124     Wed%
125   \or
126     Thu%
127   \or
128     Fri%
129   \or
130     Sat%
131   \or
132     Sun%
133   \fi
134 }

```

12 hour time tags.

```

\DTMenglisham
135 \newcommand*{\DTMenglisham}{am}%

\DTMenglishpm
136 \newcommand*{\DTMenglishpm}{pm}%

```

```

\DTMenglishmidnight
137 \newcommand*\DTMenglishmidnight{midnight}%

\DTMenglishnoon
138 \newcommand*\DTMenglishnoon{noon}%
      am/pm time style.

\DTMenglishampmfmt
139 \newcommand*\{\DTMenglishampmfmt}[1]{#1}

\DTMenglishtimesep
140 \newcommand*\{\DTMenglishtimesep}{\DTMsep{hourmin}>

      This style ignores seconds.

141 \DTMnewtimestyle
142 {englishampm}%
143 {%
144   \renewcommand*\DTMdisplaytime[3]{%
145     \ifnum##2=0
146     \ifnum##1=12
147       \DTMtexorpdfstring
148         {\DTMenglishampmfmt{\DTMenglishnoon}}%
149         {\DTMenglishnoon}%
150     \else
151     \ifnum##1=0
152       \DTMtexorpdfstring
153         {\DTMenglishampmfmt{\DTMenglishmidnight}}%
154         {\DTMenglishmidnight}%
155     \else
156     \ifnum##1=24
157       \DTMtexorpdfstring
158         {\DTMenglishampmfmt{\DTMenglishmidnight}}%
159         {\DTMenglishmidnight}%
160     \else
161     \ifnum##1<12
162       \number##1
163       \DTMtexorpdfstring
164         {\DTMenglishampmfmt{\DTMenglisham}}%
165         {\DTMenglisham}%
166     \else
167       \number\numexpr##1-12\relax
168       \DTMtexorpdfstring
169         {\DTMenglishampmfmt{\DTMenglishpm}}%
170         {\DTMenglishpm}%
171     \fi
172     \fi
173   \fi
174 }

```

```

175      \else
176          \ifnum##1<13
177              \ifnum##1=0
178                  12%
179              \else
180                  \number##1
181          \fi
182          \DTMenglishtimesep\DTMtwodigits{##2}%
183          \ifnum##1=12
184              \DTMtexorpdfstring
185                  {\DTMenglishampf{\DTMenglisham}}%
186                  {\DTMenglishpm}}%
187          \else
188              \DTMtexorpdfstring
189                  {\DTMenglishampf{\DTMenglisham}}%
190                  {\DTMenglisham}}%
191          \fi
192      \else
193          \number\numexpr##1-12\relax
194          \DTMenglishtimesep\DTMtwodigits{##2}%
195          \ifnum##1=24
196              \DTMtexorpdfstring
197                  {\DTMenglishampf{\DTMenglishpm}}%
198                  {\DTMenglisham}}%
199          \else
200              \DTMtexorpdfstring
201                  {\DTMenglishampf{\DTMenglishpm}}%
202                  {\DTMenglishpm}}%
203          \fi
204      \fi
205  \fi
206 }%
207 }%

```

## 14.2 Default English Code (datetime2-english.ldf)

This file contains the style used if English is requested without a known region. It uses TeX's default date style. This style ignores the `showdow` (show day of week) setting.

Identify Module

```
208 \ProvidesDateTimeModule{english}[2015/04/09 v1.01 (NLCT)]
```

Load the base English module.

```
209 \RequireDateTimeModule{english-base}
```

Define default English text style (TeX's default) labelled `english`. The time zone is just the `default` style (no mappings applied) but `showisoZ` setting checked. The full style places a space between each block (date, time and zone). The numeric setting is ambiguous without a region so it will use the `default` style.

```

210 \DTMnewstyle
211   {english}%
212   {%
213     \renewcommand*\DTMenglishfmtordsuffix}[1]{}
214     \renewcommand*\DTMdisplaydate[4]{%
215       \DTMenglishmonthname{##2}\space\number##3, \number##1
216     }%
217     \renewcommand*\DTMDisplaydate[4]{\DTMdisplaydate##1##2##3##4}%
218   }%
219   {%
220     \renewcommand*\DTMenglishtimesep}{\DTMsep{hourmin}}%
221     \DTMsetimestyle{englishampm}%
222   }%
223   {%
224     \DTMsetzonestyle{default}%
225   }%
226   {%
227     \renewcommand*\DTMdisplay[9]{%
228       \ifDTMshowdate
229         \DTMdisplaydate##1##2##3##4%
230         \space
231       \fi
232         \DTMdisplaytime##5##6##7%
233         \ifDTMshowzone
234           \space
235             \DTMdisplayzone##8##9%
236           \fi
237         }%
238       \renewcommand*\DTMDisplay}{\DTMdisplay}%
239   }%

```

Switch the style according to the `useregional` setting.

```

240 \DTMifcaseregional
241 {}% do nothing
242 {\DTMsetstyle{english}}%
243 {\DTMsetstyle{default}}%

```

Redefine `\dateenglish` (or `\date{dialect}`) to prevent `babel` from resetting `\today`. (For this to work, `babel` must already have been loaded if it's required.)

```

244 \ifcsundef{date\CurrentTrackedDialect}
245 {%
246   \ifundef{\dateenglish}
247   {}% do nothing
248   }%
249 {%
250   \def{\dateenglish}{%
251     \DTMifcaseregional
252     {}% do nothing
253     {\DTMsetstyle{english}}%
254     {\DTMsetstyle{default}}%
255   }%

```

```

256  }%
257 }%
258 {%
259   \csdef{date\CurrentTrackedDialect}{%
260     \DTMifcaseregional
261     {}% do nothing
262     {\DTMsetstyle{english}}%
263     {\DTMsetstyle{default}}%
264   }%
265 }%

```

### 14.3 English (GB) Code (datetime2-en-GB.1df)

This file contains the British English style. Identify this module.

```
266 \ProvidesDateTimeModule{en-GB}[2015/04/09 v1.01 (NLCT)]
```

Load base English module.

```
267 \RequireDateTimeModule{english-base}
```

Allow the user a way of configuring the en-GB and en-GB-numeric styles. This doesn't use the package wide separators such as \dtm@datetimesep in case other date formats are also required.

- \DTM{en-GB}{daymonthsep} The separator between the day and month for the text format.  
268 \newcommand\*{\DTM{en-GB}{daymonthsep}}{\space}
- \DTM{en-GB}{monthyearsep} The separator between the month and year for the text format.  
269 \newcommand\*{\DTM{en-GB}{monthyearsep}}{\space}
- \DTM{en-GB}{datetimesep} The separator between the date and time blocks in the full format (either text or numeric).  
270 \newcommand\*{\DTM{en-GB}{datetimesep}}{\space}
- \DTM{en-GB}{timezonesep} The separator between the time and zone blocks in the full format (either text or numeric).  
271 \newcommand\*{\DTM{en-GB}{timezonesep}}{\space}
- \DTM{en-GB}{datesep} The separator for the numeric date format.  
272 \newcommand\*{\DTM{en-GB}{datesep}}{/}
- \DTM{en-GB}{timesep} The separator for the numeric time format.  
273 \newcommand\*{\DTM{en-GB}{timesep}}{:}

Provide keys that can be used in \DTMlangsetup to set these separators.

```

274 \DTMdefkey{en-GB}{daymonthsep}{\renewcommand*{\DTM{en-GB}{daymonthsep}}{\#1}}
275 \DTMdefkey{en-GB}{monthyearsep}{\renewcommand*{\DTM{en-GB}{monthyearsep}}{\#1}}
276 \DTMdefkey{en-GB}{datetimesep}{\renewcommand*{\DTM{en-GB}{datetimesep}}{\#1}}
277 \DTMdefkey{en-GB}{timezonesep}{\renewcommand*{\DTM{en-GB}{timezonesep}}{\#1}}
278 \DTMdefkey{en-GB}{datesep}{\renewcommand*{\DTM{en-GB}{datesep}}{\#1}}
279 \DTMdefkey{en-GB}{timesep}{\renewcommand*{\DTM{en-GB}{timesep}}{\#1}}

```

Define a boolean key that can switch between full and abbreviated formats for the month and day of week names in the text format.

```
280 \DTMdefboolkey{en-GB}{abbr}[true]{}
```

The default is the full name.

```
281 \DTMsetbool{en-GB}{abbr}{false}
```

Define a boolean key that determines if the time zone mappings should be used.

```
282 \DTMdefboolkey{en-GB}{mapzone}[true]{}
```

The default is to use mappings.

```
283 \DTMsetbool{en-GB}{mapzone}{true}
```

Define a boolean key that determines whether to show or hide the day of the month. (Called `showdayofmonth` instead of `showday` to avoid confusion with the day of the week.)

```
284 \DTMdefboolkey{en-GB}{showdayofmonth}[true]{}
```

The default is to show the day of the month.

```
285 \DTMsetbool{en-GB}{showdayofmonth}{true}
```

Define a boolean key that determines whether to show or hide the year.

```
286 \DTMdefboolkey{en-GB}{showyear}[true]{}
```

The default is to show the year.

```
287 \DTMsetbool{en-GB}{showyear}{true}
```

`\DTMenGBfmtordsuffix` Define the ordinal suffix to be used by this style.

```
288 \newcommand*{\DTMenGBfmtordsuffix}[1]{#1}
```

Define a setting to change the ordinal suffix style.

```
289 \DTMdefchoicekey{en-GB}{ord}[\val\nr]{level,raise,omit,sc}{%
290   \ifcase\nr\relax
291     \renewcommand*{\DTMenGBfmtordsuffix}[1]{##1}%
292   \or
293     \renewcommand*{\DTMenGBfmtordsuffix}[1]{%
294       \DTMtexorpdfstring{\protect\textsuperscript{##1}}{##1}}%
295   \or
296     \renewcommand*{\DTMenGBfmtordsuffix}[1]{ }%
297   \or
298     \renewcommand*{\DTMenGBfmtordsuffix}[1]{%
299       \DTMtexorpdfstring{\protect\textsc{##1}}{##1}}%
300   \fi
301 }
```

Define the `en-GB` style.

```
302 \DTMnewstyle
303 {en-GB}%
304 {%
305   \renewcommand*{\DTMenglishfmtordsuffix}{\DTMenGBfmtordsuffix}%
306   \renewcommand*\DTMdisplaydate[4]{%
```

```

307      \ifDTMshowdow
308          \ifnum##4>-1
309              \DTMifbool{en-GB}{abbr}%
310                  {\DTMenglishshortweekdayname{##4}}%
311                  {\DTMenglishweekdayname{##4}}%
312              \space
313          \fi
314      \fi
315      \DTMifbool{en-GB}{showdayofmonth}%
316      {%
317          \DTMenglishordinal{##3}%
318          \DTMEnGBdaymonthsep
319      }%
320      {}%
321      \DTMifbool{en-GB}{abbr}%
322      {\DTMenglishshortmonthname{##2}}%
323      {\DTMenglishmonthname{##2}}%
324      \DTMifbool{en-GB}{showyear}%
325      {%
326          \DTMEnGBmonthyearsep\number##1 % space intended
327      }%
328      {}%
329  }%
330  \renewcommand*\{\DTMDisplaydate}[4]{\DTMdisplaydate{##1}{##2}{##3}{##4}}%
331 }%
332 {%
333     \renewcommand*\DTMenglishtimesep{\DTMEnGBTimesep}%
334     \DTMsettimestyle{englishampm}%
335 }%
336 {%
337     \DTMresetzones
338     \DTMEnGBzonemaps
339     \renewcommand*\{\DTMdisplayzone}[2]{%
340         \DTMifbool{en-GB}{mapzone}%
341         {\DTMusezonemapordefault{##1}{##2}}%
342     }%
343     \ifnum##1<0\else+\fi\DTMtowodigits{##1}%
344     \ifDTMshowzoneminutes\DTMEnGBTimesep\DTMtowodigits{##2}\fi
345 }%
346 }%
347 }%
348 {%
349     \renewcommand*\{\DTMdisplay}[9]{%
350         \ifDTMshowdate
351             \DTMdisplaydate{##1}{##2}{##3}{##4}%
352             \DTMEnGBdatetimesep
353         \fi
354         \DTMdisplaytime{##5}{##6}{##7}%
355         \ifDTMshowzone
356             \DTMEnGBTimezonesep

```

```

357      \DTMdisplayzone{##8}{##9}%
358      \fi
359  }%
360  \renewcommand*\DTMDisplay{\DTMdisplay}
361 }%
Define numeric style.
362 \DTMnewstyle
363 {en-GB-numeric}%
364 {%
365   \renewcommand*\DTMdisplaydate[4]{%
366     \DTMifbool{en-GB}{showdayofmonth}%
367   }%
368   \number##3 % space intended
369   \DTMendatesep
370 }%
371 }%
372 \number##2 % space intended
373 \DTMifbool{en-GB}{showyear}%
374 }%
375 \DTMendatesep
376 \number##1 % space intended
377 }%
378 }%
379 }%
380 \renewcommand*\DTMDisplaydate[4]{\DTMdisplaydate{##1}{##2}{##3}{##4}}%
381 }%
382 {%
383   \renewcommand*\DTMdisplaytime[3]{%
384     \number##1
385     \DTMendatesep\DTMtwodigits{##2}%
386     \ifDTMshowseconds\DTMendatesep\DTMtwodigits{##3}\fi
387   }%
388 }%
389 {%
390   \DTMresetzones
391   \DTMendatesep
392   \renewcommand*\DTMdisplayzone[2]{%
393     \DTMifbool{en-GB}{mapzone}%
394     {\DTMusezonemapordefault{##1}{##2}}%
395   }%
396   \ifnum##1<0\else+\fi\DTMtwodigits{##1}%
397   \ifDTMshowzoneminutes\DTMendatesep\DTMtwodigits{##2}\fi
398 }%
399 }%
400 }%
401 {%
402   \renewcommand*\DTMdisplay[9]{%
403     \ifDTMshowdate
404       \DTMdisplaydate{##1}{##2}{##3}{##4}%

```

```

405      \DTMenGBdatetimesep
406      \fi
407      \DTMdisplaytime{##5}{##6}{##7}%
408      \ifDTMshowzone
409          \DTMenGBtimezonesep
410          \DTMdisplayzone{##8}{##9}%
411      \fi
412  }%
413  \renewcommand*\{\DTMDisplay}{\DTMdisplay}%
414 }

```

**\DTMenGBzonemaps** The time zone mappings are set through this command, which can be redefined if extra mappings are required or mappings need to be removed.

```

415 \newcommand*\{\DTMenGBzonemaps}{%
416     \DTMdefzonemap{00}{00}{GMT}%
417     \DTMdefzonemap{01}{00}{BST}%
418 }

```

Switch style according to the `useregional` setting.

```

419 \DTMifcaseregional
420 {}% do nothing
421 {\DTMsetstyle{en-GB}}%
422 {\DTMsetstyle{en-GB-numeric}}%

```

Redefine `\dateenglish` (or `\date<dialect>`) to prevent `babel` from resetting `\today`. (For this to work, `babel` must already have been loaded if it's required.)

```

423 \ifcsundef{date\CurrentTrackedDialect}
424 {}% do nothing
425     \ifundef\dateenglish
426         {%
427         }%
428         {%
429             \def\dateenglish{%
430                 \DTMifcaseregional
431                     {}% do nothing
432                     {\DTMsetstyle{en-GB}}%
433                     {\DTMsetstyle{en-GB-numeric}}%
434             }%
435         }%
436     }%
437     {%
438         \csdef{date\CurrentTrackedDialect}{%
439             \DTMifcaseregional
440                 {}% do nothing
441                 {\DTMsetstyle{en-GB}}%
442                 {\DTMsetstyle{en-GB-numeric}}%
443             }%
444     }%

```

## 14.4 English (US) Code (datetime2-en-US.1df)

This file contains the US English style.

Identify this module.

```
445 \ProvidesDateTimeModule{en-US}[2015/04/09 v1.01 (NLCT)]
```

Load base English module.

```
446 \RequireDateTimeModule{english-base}
```

Allow the user a way of configuring the en-US date format. This doesn't use the package wide separators such as `\dtm@datetimesep` in case other date formats are also required.

- `\DTMnUSmonthdaysep` The separator between the month and day for the text format.  
447 `\newcommand*{\DTMnUSmonthdaysep}{\space}`
  - `\DTMnUSdayyearsep` The separator between the day and year for the text format.  
448 `\newcommand*{\DTMnUSdayyearsep}{, \space}`
  - `\DTMnUSdatetimesep` The separator between the date and time blocks in the full format (either text or numeric).  
449 `\newcommand*{\DTMnUSdatetimesep}{\space}`
  - `\DTMnUSTimezonesep` The separator between the time and zone blocks in the full format (either text or numeric).  
450 `\newcommand*{\DTMnUSTimezonesep}{\space}`
  - `\DTMnUSdatesep` The separator for the numeric date format.  
451 `\newcommand*{\DTMnUSdatesep}{/}`
  - `\DTMnUSTimesep` The separator for the numeric time format.  
452 `\newcommand*{\DTMnUSTimesep}{:}`
- Provide keys that can be used in `\DTMlangsetup` to set these separators.
- 453 `\DTMdefkey{en-US}{monthdaysep}{\renewcommand*{\DTMnUSmonthdaysep}{#1}}`
  - 454 `\DTMdefkey{en-US}{dayyearsep}{\renewcommand*{\DTMnUSdayyearsep}{#1}}`
  - 455 `\DTMdefkey{en-US}{datetimesep}{\renewcommand*{\DTMnUSdatetimesep}{#1}}`
  - 456 `\DTMdefkey{en-US}{timezonesep}{\renewcommand*{\DTMnUSTimezonesep}{#1}}`
  - 457 `\DTMdefkey{en-US}{datesep}{\renewcommand*{\DTMnUSdatesep}{#1}}`
  - 458 `\DTMdefkey{en-US}{timesep}{\renewcommand*{\DTMnUSTimesep}{#1}}`
- Define a boolean key that can switch between full and abbreviated formats for the month and day of week names in the text format.
- 459 `\DTMdefboolkey{en-US}{abbr}{true}{}{}`
- The default is the full name.
- 460 `\DTMsetbool{en-US}{abbr}{false}`
- Define a boolean key that determines if the time zone mappings should be used.
- 461 `\DTMdefboolkey{en-US}{mapzone}{true}{}{}`

The default is no mappings.

```
462 \DTMsetbool{en-US}{mapzone}{false}
```

Define a boolean key that determines whether to show or hide the day of the month. (Called `showdayofmonth` instead of `showday` to avoid confusion with the day of the week.)

```
463 \DTMdefboolkey{en-US}{showdayofmonth}[true]{}
```

The default is to show the day of the month.

```
464 \DTMsetbool{en-US}{showdayofmonth}{true}
```

Define a boolean key that determines whether to show or hide the year.

```
465 \DTMdefboolkey{en-US}{showyear}[true]{}
```

The default is to show the year.

```
466 \DTMsetbool{en-US}{showyear}{true}
```

`\DTMenUSfmtordsuffix` Define the ordinal suffix to be used by this style.

```
467 \newcommand*{\DTMenUSfmtordsuffix}[1]{}
```

Define a setting to change the ordinal suffix style.

```
468 \DTMdefchoicekey{en-US}{ord}{\val\nr}{level,raise,omit,sc}{%
469   \ifcase\nr\relax
470     \renewcommand*{\DTMenUSfmtordsuffix}[1]{##1}%
471   \or
472     \renewcommand*{\DTMenUSfmtordsuffix}[1]{%
473       \DTMtexorpdfstring{\protect\textrightsupscript{##1}}{##1}}%
474   \or
475     \renewcommand*{\DTMenUSfmtordsuffix}[1]{%
476       \DTMtexorpdfstring{\protect\textrightsupscript{##1}}{##1}}%
477   \or
478     \renewcommand*{\DTMenUSfmtordsuffix}[1]{%
479       \DTMtexorpdfstring{\protect\textrightsupscript{##1}}{##1}}%
480 }
```

Define the `en-US` style. Hiding the day of month is a bit awkward as the default day-year separator has a comma that should disappear if the day number is missing so the month-day separator is used as the month-year separator if the day is missing.

```
481 \DTMnewstyle
482 {en-US}%
483 {%
484   \renewcommand*{\DTMenglishfmtordsuffix}{\DTMenUSfmtordsuffix}%
485   \renewcommand*\DTMdisplaydate[4]{%
486     \DTMifbool{en-US}{abbr}{%
487       \DTMenglishshortmonthname{##2}}{%
488       \DTMenglishmonthname{##2}}%
489     \DTMifbool{en-US}{showdayofmonth}{%
490       \%
491       \DTMenUSmonthdaysep
492       \DTMenglishordinal{##3}}{}}
```

```

493     \DTMifbool{en-US}{showyear}%
494     {%
495         \DTMEnUSdayyearsep
496         \number##1 % intended
497     }%
498     {}%
499 }%
500 {}%
501     \DTMifbool{en-US}{showyear}%
502     {%
503         \DTMEnUSmonthdaysep
504         \number##1 % intended
505     }%
506     {}%
507 }%
508 }%
509 \renewcommand*{\DTMDisplaydate}[4]{\DTMdisplaydate{##1}{##2}{##3}{##4}}%
510 }%
511 {% time style
512     \renewcommand*{\DTMenglishtimesep}{\DTMEnUSTimesep}%
513     \DTMsettimestyle{englishampm}%
514 }%
515 {% zone style
516     \DTMresetzones
517     \DTMEnUSzonemaps
518     \renewcommand*{\DTMdisplayzone}[2]{%
519         \DTMifbool{en-US}{mapzone}%
520         {\DTMusezonemapordefault{##1}{##2}}%
521     }%
522         \ifnum##1<0\else+\fi\DTMtowodigits{##1}%
523         \ifDTMshowzoneminutes\DTMEnUSTimesep\DTMtowodigits{##2}\fi
524     }%
525 }%
526 }%
527 {% full style
528     \renewcommand*{\DTMdisplay}[9]{%
529         \ifDTMshowdate
530             \DTMdisplaydate{##1}{##2}{##3}{##4}%
531             \DTMEnUSdatetimesep
532         \fi
533         \DTMdisplaytime{##5}{##6}{##7}%
534         \ifDTMshowzone
535             \DTMEnUSTimezonesep
536             \DTMdisplayzone{##8}{##9}%
537         \fi
538     }%
539     \renewcommand*{\DTMDisplay}{\DTMdisplay}%
540 }%

```

Define numeric style.

```

541 \DTMnewstyle
542 {en-US-numeric}%
543 {%
544   \renewcommand*\DTMdisplaydate[4]{%
545     \number##2 % space intended
546     \DTMifbool{en-US}{showdayofmonth}%
547   }%
548   \DTMEnUSdatesep
549   \number##3 % space intended
550 }%
551 }%
552 \DTMifbool{en-US}{showyear}%
553 }%
554   \DTMEnUSdatesep
555   \number##1 % space intended
556 }%
557 }%
558 }%
559 \renewcommand*{\DTMDisplaydate}[4]{\DTMdisplaydate{##1}{##2}{##3}{##4}}%
560 }%
561 {%
562   \renewcommand*\DTMdisplaytime[3]{%
563     \number##1
564     \DTMEnUStimesep\DTMtwodigits{##2}%
565     \ifDTMshowseconds\DTMEnUStimesep\DTMtwodigits{##3}\fi
566   }%
567 }%
568 {%
569   \DTMresetzones
570   \DTMEnUSzonemaps
571   \renewcommand*{\DTMdisplayzone}[2]{%
572     \DTMifbool{en-US}{mapzone}%
573     {\DTMusezonemapordefault{##1}{##2}}%
574   }%
575   \ifnum##1<0\else+\fi\DTMtwodigits{##1}%
576   \ifDTMshowzoneminutes\DTMEnUStimesep\DTMtwodigits{##2}\fi
577 }%
578 }%
579 }%
580 {%
581   \renewcommand*{\DTMdisplay}[9]{%
582     \ifDTMshowdate
583       \DTMdisplaydate{##1}{##2}{##3}{##4}%
584       \DTMEnUSdatetimesep
585     \fi
586     \DTMdisplaytime{##5}{##6}{##7}%
587     \ifDTMshowzone
588       \DTMEnUStimezonesep
589       \DTMdisplayzone{##8}{##9}%
590     \fi

```

```

591     }%
592     \renewcommand*\{\DTMDisplay}{\DTMdisplay}%
593 }

\DTMenUSzonemaps The time zone mappings are set through this command, which can be redefined if extra mappings are required or mappings need to be removed. (These don't take daylight saving into account.)
594 \newcommand*\{\DTMenUSzonemaps}{%
595   \DTMdefzonemap{-3}{00}{ADT}%
596   \DTMdefzonemap{-4}{00}{AST}%
597   \DTMdefzonemap{-5}{00}{EST}%
598   \DTMdefzonemap{-6}{00}{CST}%
599   \DTMdefzonemap{-7}{00}{MST}%
600   \DTMdefzonemap{-8}{00}{PST}%
601 }

Switch style according to the useregional setting.
602 \DTMifcaseregional
603 {}% do nothing
604 {\DTMsetstyle{en-US}}%
605 {\DTMsetstyle{en-US-numeric}}%

Redefine \dateenglish (or \date{dialect}) to prevent babel from resetting \today. (For this to work, babel must already have been loaded if it's required.)
606 \ifcsundef{date\CurrentTrackedDialect}%
607 {}% do nothing
608   \ifundef{\dateenglish}%
609   {}%
610 {}%
611 {}%
612   \def{\dateenglish}{%
613     \DTMifcaseregional
614     {}% do nothing
615     {\DTMsetstyle{en-US}}%
616     {\DTMsetstyle{en-US-numeric}}%
617   }%
618 }%
619 {}%
620 {}%
621   \csdef{date\CurrentTrackedDialect}{%
622     \DTMifcaseregional
623     {}% do nothing
624     {\DTMsetstyle{en-US}}%
625     {\DTMsetstyle{en-US-numeric}}%
626   }%
627 }%

```

## 14.5 English (Canada) Code (datetime2-en-CA.1df)

This file contains the Canadian English style. This is very similar to the US style.

Identify this module.

628 \ProvidesDateTimeModule{en-CA}[2015/04/09 v1.01 (NLCT)]

Load base English module.

629 \RequireDateTimeModule{english-base}

Allow the user a way of configuring the en-CA and en-CA-numeric formats. This doesn't use the package wide separators such as \dtm@datetimesep in case other date formats are also required.

- \DTM{enCA}{monthdaysep} The separator between the month and day for the text format.  
630 \newcommand\*{\DTM{enCA}{monthdaysep}}{\space}
- \DTM{enCA}{dayyearsep} The separator between the day and year for the text format.  
631 \newcommand\*{\DTM{enCA}{dayyearsep}}{\space}
- \DTM{enCA}{datetimesep} The separator between the date and time blocks in the full format (either text or numeric).  
632 \newcommand\*{\DTM{enCA}{datetimesep}}{\space}
- \DTM{enCA}{timezonesep} The separator between the time and zone blocks in the full format (either text or numeric).  
633 \newcommand\*{\DTM{enCA}{timezonesep}}{\space}
- \DTM{enCA}{datesep} The separator for the numeric date format.  
634 \newcommand\*{\DTM{enCA}{datesep}}{/}
- \DTM{enCA}{timesep} The separator for the numeric time format.  
635 \newcommand\*{\DTM{enCA}{timesep}}{:}

Provide keys that can be used in \DTMlangsetup to set these separators.

636 \DTMdefkey{en-CA}{monthdaysep}{\renewcommand\*{\DTM{enCA}{monthdaysep}}{\#1}}  
637 \DTMdefkey{en-CA}{dayyearsep}{\renewcommand\*{\DTM{enCA}{dayyearsep}}{\#1}}  
638 \DTMdefkey{en-CA}{datetimesep}{\renewcommand\*{\DTM{enCA}{datetimesep}}{\#1}}  
639 \DTMdefkey{en-CA}{timezonesep}{\renewcommand\*{\DTM{enCA}{timezonesep}}{\#1}}  
640 \DTMdefkey{en-CA}{datesep}{\renewcommand\*{\DTM{enCA}{datesep}}{\#1}}  
641 \DTMdefkey{en-CA}{timesep}{\renewcommand\*{\DTM{enCA}{timesep}}{\#1}}

Define a boolean key that can switch between full and abbreviated formats for the month and day of week names in the text format.

642 \DTMdefboolkey{en-CA}{abbr}[true]{}

The default is the full name.

643 \DTMsetbool{en-CA}{abbr}{false}

Define a boolean key that determines if the time zone mappings should be used.

```
644 \DTMdefboolkey{en-CA}{mapzone}[true]{}
```

The default is no mappings.

```
645 \DTMsetbool{en-CA}{mapzone}{false}
```

Define a boolean key that determines whether to show or hide the day of the month. (Called `showdayofmonth` instead of `showday` to avoid confusion with the day of the week.)

```
646 \DTMdefboolkey{en-CA}{showdayofmonth}[true]{}
```

The default is to show the day of the month.

```
647 \DTMsetbool{en-CA}{showdayofmonth}{true}
```

Define a boolean key that determines whether to show or hide the year.

```
648 \DTMdefboolkey{en-CA}{showyear}[true]{}
```

The default is to show the year.

```
649 \DTMsetbool{en-CA}{showyear}{true}
```

`\DTMenCAFmtordsuffix` Define the ordinal suffix to be used by this style.

```
650 \newcommand*{\DTMenCAFmtordsuffix}[1]{}
```

Define a setting to change the ordinal suffix style.

```
651 \DTMdefchoicekey{en-CA}{ord}{\val\nr}{level,raise,omit,sc}{%
652   \ifcase\nr\relax
653     \renewcommand*{\DTMenCAFmtordsuffix}[1]{##1}%
654   \or
655     \renewcommand*{\DTMenCAFmtordsuffix}[1]{%
656       \DTMtexorpdfstring{\protect\textsuperscript{##1}}{##1}}%
657   \or
658     \renewcommand*{\DTMenCAFmtordsuffix}[1]{}%
659   \or
660     \renewcommand*{\DTMenCAFmtordsuffix}[1]{%
661       \DTMtexorpdfstring{\protect\textsc{##1}}{##1}}%
662   \fi
663 }
```

Define the `en-CA` style (similar to `en-US`).

```
664 \DTMnewstyle
665 {en-CA}%
666   label
667   {%
668     date style
669     \renewcommand*{\DTMenglishfmtordsuffix}{\DTMenCAFmtordsuffix}%
670     \renewcommand*\DTMdisplaydate[4]{%
671       \DTMifbool{en-CA}{abbr}{%
672         {\DTMenglishshortmonthname{##2}}%
673         {\DTMenglishmonthname{##2}}%
674       \DTMifbool{en-CA}{showdayofmonth}{%
675         {%
676           \DTMenCAmonthdaysep
677         }%
678       }%
679     }%
680   }%
681 }
```

```

675     \DTMenglishordinal{##3}%
676     \DTMifbool{en-CA}{showyear}%
677     {%
678         \DTMEnCAdayyearsep
679         \number##1 % intended
680     }%
681     {}%
682 }%
683 {}%
684     \DTMifbool{en-CA}{showyear}%
685     {%
686         \DTMEnCAMonthdaysep
687         \number##1 % intended
688     }%
689     {}%
690 }%
691 }%
692 \renewcommand*{\DTMDisplaydate}[4]{\DTMdisplaydate{##1}{##2}{##3}{##4}}%
693 }%
694 {% time style
695     \renewcommand*{\DTMenglishtimesep}{\DTMEnCATimesep}%
696     \DTMsetimestyle{englishampm}%
697 }%
698 {% zone style
699     \DTMresetzones
700     \DTMEnCAzonemaps
701     \renewcommand*{\DTMdisplayzone}[2]{%
702         \DTMifbool{en-CA}{mapzone}%
703         {\DTMusezonemapordefault{##1}{##2}}%
704     }%
705     \ifnum##1<0\else+\fi\DTMtwodigits{##1}%
706     \ifDTMshowzoneminutes\DTMEnCATimesep\DTMtwodigits{##2}\fi
707 }%
708 }%
709 }%
710 {% full style
711     \renewcommand*{\DTMdisplay}[9]{%
712         \ifDTMshowdate
713             \DTMdisplaydate{##1}{##2}{##3}{##4}%
714             \DTMEnCAdatetimesep
715         \fi
716         \DTMdisplaytime{##5}{##6}{##7}%
717         \ifDTMshowzone
718             \DTMEnCATimezonesep
719             \DTMdisplayzone{##8}{##9}%
720         \fi
721     }%
722     \renewcommand*{\DTMDisplay}{\DTMdisplay}%
723 }%

```

Define numeric style.

```
724 \DTMnewstyle
725 {en-CA-numeric}%
726 {%
727   \renewcommand*\DTMdisplaydate[4]{%
728     \number##2 % space intended
729     \DTMifbool{en-CA}{showdayofmonth}%
730   }%
731   \DTMEnCAdatesep
732   \number##3 % space intended
733 }%
734 }%
735 \DTMifbool{en-CA}{showyear}%
736 }%
737 \DTMEnCAdatesep
738 \number##1 % space intended
739 }%
740 }%
741 }%
742 \renewcommand*{\DTMDisplaydate}[4]{\DTMdisplaydate{##1}{##2}{##3}{##4}}%
743 }%
744 {%
745   \renewcommand*\DTMdisplaytime[3]{%
746     \number##1
747     \DTMEnCATimesep\DTMtwodigits{##2}%
748     \ifDTMshowseconds\DTMEnCATimesep\DTMtwodigits{##3}\fi
749   }%
750 }%
751 {%
752   \DTMresetzones
753   \DTMEnCAzonemaps
754   \renewcommand*{\DTMdisplayzone}[2]{%
755     \DTMifbool{en-CA}{mapzone}%
756     {\DTMusezonemapordefault{##1}{##2}}%
757   }%
758   \ifnum##1<0\else+\fi\DTMtwodigits{##1}%
759   \ifDTMshowzoneminutes\DTMEnCATimesep\DTMtwodigits{##2}\fi
760 }%
761 }%
762 }%
763 {%
764   \renewcommand*{\DTMdisplay}[9]{%
765     \ifDTMshowdate
766       \DTMdisplaydate{##1}{##2}{##3}{##4}%
767       \DTMEnCAdatetimesep
768     \fi
769     \DTMdisplaytime{##5}{##6}{##7}%
770     \ifDTMshowzone
771       \DTMEnCAtimezonesep
```

```

772     \DTMdisplayzone{##8}{##9}%
773     \fi
774   }%
775   \renewcommand*\{\DTMDisplay\}{\DTMdisplay}%
776 }

```

\DTMenzonemaps The time zone mappings are set through this command, which can be redefined if extra mappings are required or mappings need to be removed. (These don't take daylight saving into account, except for NDT.)

```

777 \newcommand*\{\DTMenzonemaps\}{%
778   \DTMdefzonemap{-2}{30}{NDT}%
779   \DTMdefzonemap{-3}{30}{NST}%
780   \DTMdefzonemap{-4}{00}{AST}%
781   \DTMdefzonemap{-5}{00}{EST}%
782   \DTMdefzonemap{-6}{00}{CST}%
783   \DTMdefzonemap{-7}{00}{MST}%
784   \DTMdefzonemap{-8}{00}{PST}%
785 }

```

Switch style according to the `useregional` setting.

```

786 \DTMifcaseregional
787 {}% do nothing
788 {\DTMsetstyle{en-CA}}%
789 {\DTMsetstyle{en-CA-numeric}}%

```

Redefine `\dateenglish` (or `\date{dialect}`) to prevent `babel` from resetting `\today`. (For this to work, `babel` must already have been loaded if it's required.)

```

790 \ifcsundef{date\CurrentTrackedDialect}%
791 {}% do nothing
792   \ifundef\dateenglish
793   {}%
794   }%
795   {}%
796   \def\dateenglish{%
797     \DTMifcaseregional
798     {}% do nothing
799     {\DTMsetstyle{en-CA}}%
800     {\DTMsetstyle{en-CA-numeric}}%
801   }%
802 }%
803 }%
804 {}%
805 \csdef{date\CurrentTrackedDialect}{%
806   \DTMifcaseregional
807   {}% do nothing
808   {\DTMsetstyle{en-CA}}%
809   {\DTMsetstyle{en-CA-numeric}}%
810 }%
811 }%

```

## 14.6 English (Australia) Code (datetime2-en-AU.1df)

This file contains the Australian English style.

Identify this module.

812 \ProvidesDateTimeModule{en-AU}[2015/04/09 v1.01 (NLCT)]

Load base English module.

813 \RequireDateTimeModule{english-base}

Allow the user a way of configuring the en-AU and en-AU-numeric styles. This doesn't use the package wide separators such as \dtm@datetimesep in case other date formats are also required.

\DTMnAUdaymonthsep The separator between the day and month for the text format.

814 \newcommand\*{\DTMnAUdaymonthsep}{\space}

\DTMnAUmonthyearsep The separator between the month and year for the text format.

815 \newcommand\*{\DTMnAUmonthyearsep}{\space}

\DTMnAUdatetimesep The separator between the date and time blocks in the full format (either text or numeric).

816 \newcommand\*{\DTMnAUdatetimesep}{\space}

\DTMnAUtimezonesep The separator between the time and zone blocks in the full format (either text or numeric).

817 \newcommand\*{\DTMnAUtimezonesep}{\space}

\DTMnAUdatesep The separator for the numeric date format.

818 \newcommand\*{\DTMnAUdatesep}{/}

\DTMnAUtimesep The separator for the numeric time format.

819 \newcommand\*{\DTMnAUtimesep}{:}

Provide keys that can be used in \DTMlangsetup to set these separators.

820 \DTMdefkey{en-AU}{daymonthsep}{\renewcommand\*{\DTMnAUdaymonthsep}{#1}}

821 \DTMdefkey{en-AU}{monthyearsep}{\renewcommand\*{\DTMnAUmonthyearsep}{#1}}

822 \DTMdefkey{en-AU}{datetimesep}{\renewcommand\*{\DTMnAUdatetimesep}{#1}}

823 \DTMdefkey{en-AU}{timezonesep}{\renewcommand\*{\DTMnAUtimezonesep}{#1}}

824 \DTMdefkey{en-AU}{datesep}{\renewcommand\*{\DTMnAUdatesep}{#1}}

825 \DTMdefkey{en-AU}{timesep}{\renewcommand\*{\DTMnAUtimesep}{#1}}

Define a boolean key that can switch between full and abbreviated formats for the month and day of week names in the text format.

826 \DTMdefboolkey{en-AU}{abbr}[true]{}

The default is the full name.

827 \DTMsetbool{en-AU}{abbr}{false}

Define a boolean key that determines if the time zone mappings should be used.

828 \DTMdefboolkey{en-AU}{mapzone}[true]{}

The default is no mappings.

```
829 \DTMsetbool{en-AU}{mapzone}{false}
```

Define a boolean key that determines whether to show or hide the day of the month. (Called `showdayofmonth` instead of `showday` to avoid confusion with the day of the week.)

```
830 \DTMdefboolkey{en-AU}{showdayofmonth}[true]{}
```

The default is to show the day of the month.

```
831 \DTMsetbool{en-AU}{showdayofmonth}{true}
```

Define a boolean key that determines whether to show or hide the year.

```
832 \DTMdefboolkey{en-AU}{showyear}[true]{}
```

The default is to show the year.

```
833 \DTMsetbool{en-AU}{showyear}{true}
```

`\DTMenAUfmtordsuffix` Define the ordinal suffix to be used by this style.

```
834 \newcommand*{\DTMenAUfmtordsuffix}[1]{}
```

Define a setting to change the ordinal suffix style.

```
835 \DTMdefchoicekey{en-AU}{ord}{\val\nr}{level,raise,omit,sc}{%
836   \ifcase\nr\relax
837     \renewcommand*{\DTMenAUfmtordsuffix}[1]{##1}%
838   \or
839     \renewcommand*{\DTMenAUfmtordsuffix}[1]{%
840       \DTMtexorpdfstring{\protect\textsuperscript{##1}}{##1}}%
841   \or
842     \renewcommand*{\DTMenAUfmtordsuffix}[1]{%
843       \DTMtexorpdfstring{\protect\textsc{##1}}{##1}}%
844   \or
845     \renewcommand*{\DTMenAUfmtordsuffix}[1]{%
846       \DTMtexorpdfstring{\protect\textit{##1}}{##1}}%
847 }
```

Define the `en-AU` style.

```
848 \DTMnewstyle
849   {en-AU}%
850   {%
851     \renewcommand*{\DTMenglishfmtordsuffix}{\DTMenAUfmtordsuffix}%
852     \renewcommand*\DTMdisplaydate[4]{%
853       \ifDTMshowdow
854         \ifnum##4>-1%
855           \DTMifbool{en-AU}{abbr}{%
856             {\DTMenglishshortweekdayname{##4}}%
857             {\DTMenglishweekdayname{##4}}%
858             \space
859           }%
860         \fi
861       \DTMifbool{en-AU}{showdayofmonth}{%
862         \fi
863       }%
864     }%
865   }%
```

```

863     \DTMenglishordinal{##3}%
864     \DTMendaymonthsep
865   }%
866   {}%
867   \DTMifbool{en-AU}{abbr}%
868   {\DTMenglishshortmonthname{##2}}%
869   {\DTMenglishmonthname{##2}}%
870   \DTMifbool{en-AU}{showyear}%
871   {%
872     \DTMendayyearsep\number##1 % space intended
873   }%
874   {}%
875 }%
876 \renewcommand*\{\DTMDisplaydate}[4]{\DTMdisplaydate{##1}{##2}{##3}{##4}}%
877 }%
878 {% time style
879   \renewcommand*\{\DTMenglishtimesep}{\DTMendaytimesep}%
880   \DTMsettimestyle{englishampm}%
881 }%
882 {% zone style
883   \DTMresetzones
884   \DTMendayzonemaps
885   \renewcommand*\{\DTMdisplayzone}[2]{%
886     \DTMifbool{en-AU}{mapzone}%
887     {\DTMusezonemapordefault{##1}{##2}}%
888     {%
889       \ifnum##1<0\else+\fi\DTMtwodigits{##1}%
890       \ifDTMshowzoneminutes\DTMendaytimesep\DTMtwodigits{##2}\fi
891     }%
892   }%
893 }%
894 {% full style
895   \renewcommand*\{\DTMdisplay}[9]{%
896     \ifDTMshowdate
897     \DTMdisplaydate{##1}{##2}{##3}{##4}%
898     \DTMendaydatetimesep
899     \fi
900     \DTMdisplaytime{##5}{##6}{##7}%
901     \ifDTMshowzone
902     \DTMendaytimezonesepr
903     \DTMdisplayzone{##8}{##9}%
904     \fi
905   }%
906   \renewcommand*\{\DTMDisplay}{\DTMdisplay}%
907 }%

```

Define numeric style.

```

908 \DTMnewstyle
909 {en-AU-numeric}%
910 {} date style

```

```

911   \renewcommand*\DTMdisplaydate[4]{%
912     \DTMifbool{en-AU}{showdayofmonth}%
913     {%
914       \number##3 % space intended
915       \DTMendatesep
916     }%
917     {}%
918     \number##2 % space intended
919     \DTMifbool{en-AU}{showyear}%
920     {%
921       \DTMendatesep
922       \number##1 % space intended
923     }%
924     {}%
925   }%
926   \renewcommand*{\DTMDisplaydate}[4]{\DTMdisplaydate{##1}{##2}{##3}{##4}}%
927 }%
928 {%
929   \renewcommand*\DTMdisplaytime[3]{%
930     \number##1
931     \DTMendatesep\DTMtwodigits{##2}%
932     \ifDTMshowseconds\DTMendatesep\DTMtwodigits{##3}\fi
933   }%
934 }%
935 {%
936   \DTMresetzones
937   \DTMendauzonemaps
938   \renewcommand*{\DTMdisplayzone}[2]{%
939     \DTMifbool{en-AU}{mapzone}%
940     {\DTMusezonemapOrDefault{##1}{##2}}%
941     {%
942       \ifnum##1<0\else+\fi\DTMtwodigits{##1}%
943       \ifDTMshowzoneminutes\DTMendatesep\DTMtwodigits{##2}\fi
944     }%
945   }%
946 }%
947 {%
948   \renewcommand*{\DTMdisplay}[9]{%
949     \ifDTMshowdate
950     \DTMdisplaydate{##1}{##2}{##3}{##4}%
951     \DTMendatetimesep
952   \fi
953   \DTMdisplaytime{##5}{##6}{##7}%
954   \ifDTMshowzone
955     \DTMendauzonesep
956     \DTMdisplayzone{##8}{##9}%
957   \fi
958 }%
959   \renewcommand*{\DTMDisplay}{\DTMdisplay}%
960 }

```

\DTMdefzonemap{10}{30}{ACDT} Australian Central Daylight Time  
 \DTMdefzonemap{11}{00}{AEDT} Australian Eastern Daylight Time  
 \DTMdefzonemap{9}{00}{AWDT} Australian Western Daylight Time  
 \DTMdefzonemap{9}{30}{ACST} Australian Central Standard Time  
 \DTMdefzonemap{8}{45}{ACWST} Australian Central Western Standard Time  
 \DTMdefzonemap{10}{00}{AEDT} Australian Eastern Standard Time  
 \DTMdefzonemap{8}{00}{AWDT} Australian Western Standard Time  
 \DTMdefzonemap{7}{00}{CXT} Christmas Island Time  
 \DTMdefzonemap{11}{30}{NFT} Norfolk Island Time

```

961 \newcommand*\DTMdefzonemap[3]{%
962   \DTMdefzonemap{#1}{#2}{#3}%
963   Australian #1 Daylight Time%
964   Australian #1 Eastern Daylight Time%
965   Australian #1 Western Daylight Time%
966   Australian #1 Central Standard Time%
967   Australian #1 Central Western Standard Time%
968   Australian #1 Eastern Standard Time%
969   Australian #1 Western Standard Time%
970   Australian #1 Christmas Island Time%
971 }

```

Switch style according to the `useregional` setting.

```

972 \DTMifcaseregional
973 {}% do nothing
974 {\DTMsetstyle{en-AU}}%
975 {\DTMsetstyle{en-AU-numeric}}%

```

Redefine `\dateenglish` (or `\date{dialect}`) to prevent `babel` from resetting `\today`. (For this to work, `babel` must already have been loaded if it's required.)

```

976 \ifcsundef{date\CurrentTrackedDialect}%
977 {}% do nothing
978   \ifundef{\dateenglish}%
979   {}%
980   {}%
981   {}%
982   \def{\dateenglish}{%
983     \DTMifcaseregional
984     {}% do nothing
985     {\DTMsetstyle{en-AU}}%
986     {\DTMsetstyle{en-AU-numeric}}%
987   }%
988   {}%
989   {}%
990   {}%
991   \csdef{date\CurrentTrackedDialect}{%
992     \DTMifcaseregional
993     {}% do nothing
994     {\DTMsetstyle{en-AU}}%
995     {\DTMsetstyle{en-AU-numeric}}%
996   }%
997 }%

```

## 14.7 English (New Zealand) Code (datetime2-en-NZ.1df)

This file contains the New Zealand English style.

Identify this module.

```

998 \ProvidesDateTimeModule{en-NZ}[2015/04/09 v1.01 (NLCT)]
Load base English module.
999 \RequireDateTimeModule{english-base}
Allow the user a way of configuring the en-NZ and en-NZ-numeric styles. This
doesn't use the package wide separators such as \dtm@datetimesep in case other
date formats are also required.

\DTMenzdaymonthsep The separator between the day and month for the text format.
1000 \newcommand*\{\DTMenzdaymonthsep}{\space}

\DTMenzmonthyearsep The separator between the month and year for the text format.
1001 \newcommand*\{\DTMenzmonthyearsep}{\space}

\DTMenzdatetimesep The separator between the date and time blocks in the full format (either text or
numeric).
1002 \newcommand*\{\DTMenzdatetimesep}{\space}

\DTMenztimezonesep The separator between the time and zone blocks in the full format (either text or
numeric).
1003 \newcommand*\{\DTMenztimezonesep}{\space}

\DTMenzdatesep The separator for the numeric date format.
1004 \newcommand*\{\DTMenzdatesep}{/}

\DTMenztimesep The separator for the numeric time format.
1005 \newcommand*\{\DTMenztimesep}{::}

Provide keys that can be used in \DTMlangsetup to set these separators.
1006 \DTMdefkey{en-NZ}{daymonthsep}{\renewcommand*\{\DTMenzdaymonthsep}{#1}}
1007 \DTMdefkey{en-NZ}{monthyearsep}{\renewcommand*\{\DTMenzmonthyearsep}{#1}}
1008 \DTMdefkey{en-NZ}{datetimesep}{\renewcommand*\{\DTMenzdatetimesep}{#1}}
1009 \DTMdefkey{en-NZ}{timezonesep}{\renewcommand*\{\DTMenztimezonesep}{#1}}
1010 \DTMdefkey{en-NZ}{datesep}{\renewcommand*\{\DTMenzdatesep}{#1}}
1011 \DTMdefkey{en-NZ}{timesep}{\renewcommand*\{\DTMenztimesep}{#1}}

Define a boolean key that can switch between full and abbreviated formats for
the month and day of week names in the text format.
1012 \DTMdefboolkey{en-NZ}{abbr}[true]{}

The default is the full name.
1013 \DTMsetbool{en-NZ}{abbr}{false}

Define a boolean key that determines if the time zone mappings should be
used.
1014 \DTMdefboolkey{en-NZ}{mapzone}[true]{}

The default is no mappings.
1015 \DTMsetbool{en-NZ}{mapzone}{false}

```

Define a boolean key that determines whether to show or hide the day of the month. (Called `showdayofmonth` instead of `showday` to avoid confusion with the day of the week.)

```
1016 \DTMdefboolkey{en-NZ}{showdayofmonth}[true]{}
```

The default is to show the day of the month.

```
1017 \DTMsetbool{en-NZ}{showdayofmonth}{true}
```

Define a boolean key that determines whether to show or hide the year.

```
1018 \DTMdefboolkey{en-NZ}{showyear}[true]{}
```

The default is to show the year.

```
1019 \DTMsetbool{en-NZ}{showyear}{true}
```

`\DTMenNZfmtordsuffix` Define the ordinal suffix to be used by this style.

```
1020 \newcommand*{\DTMenNZfmtordsuffix}[1]{}
```

Define a setting to change the ordinal suffix style.

```
1021 \DTMdefchoicekey{en-NZ}{ord}{\val\nr}{level,raise,omit,sc}{%
1022   \ifcase\nr\relax
1023     \renewcommand*{\DTMenNZfmtordsuffix}[1]{##1}%
1024   \or
1025     \renewcommand*{\DTMenNZfmtordsuffix}[1]{%
1026       \DTMtexorpdfstring{\protect\textsuperscript{##1}}{##1}}%
1027   \or
1028     \renewcommand*{\DTMenNZfmtordsuffix}[1]{%
1029   \or
1030     \renewcommand*{\DTMenNZfmtordsuffix}[1]{%
1031       \DTMtexorpdfstring{\protect\textsc{##1}}{##1}}%
1032   \fi
1033 }
```

Define the `en-NZ` style.

```
1034 \DTMnewstyle
1035 {en-NZ}%
1036 {%
1037   \renewcommand*{\DTMenglishfmtordsuffix}{\DTMenNZfmtordsuffix}%
1038   \renewcommand*\DTMdisplaydate[4]{%
1039     \ifDTMshowdow
1040       \ifnum##4>-1%
1041         \DTMifbool{en-NZ}{abbr}{%
1042           {\DTMenglishshortweekdayname{##4}}%
1043           {\DTMenglishweekdayname{##4}}%
1044           \space
1045         \fi
1046       \fi
1047       \DTMifbool{en-NZ}{showdayofmonth}{%
1048         \%
1049         \DTMenglishordinal{##3}%
1050         \DTMenzdaymonthsep
1051       }%
1052 }
```

```

1052     {}%
1053     \DTMifbool{en-NZ}{abbr}%
1054     {\DTMenglishshortmonthname{\##2}}%
1055     {\DTMenglishmonthname{\##2}}%
1056     \DTMifbool{en-NZ}{showyear}%
1057     {}%
1058     \DTMenzmonthyearsep\number##1 % space intended
1059     }%
1060     {}%
1061   }%
1062   \renewcommand*\{\DTMDisplaydate}[4]{\DTMdisplaydate{\##1}{\##2}{\##3}{\##4}}%
1063 }%
1064 {%
1065   \renewcommand*\DTMenglishtimesep{\DTMenztimesep}%
1066   \DTMsettimestyle{englishampm}%
1067 }%
1068 {%
1069   \DTMresetzones
1070   \DTMenzzonemaps
1071   \renewcommand*\{\DTMdisplayzone}[2]{%
1072     \DTMifbool{en-NZ}{mapzone}%
1073     {\DTMusezonemapordefault{\##1}{\##2}}%
1074     {}%
1075     \ifnum##1<0\else+\fi\DTMtowodigits{\##1}%
1076     \ifDTMshowzoneminutes\DTMenztimesep\DTMtowodigits{\##2}\fi
1077   }%
1078 }%
1079 }%
1080 {%
1081   \renewcommand*\{\DTMdisplay}[9]{%
1082     \ifDTMshowdate
1083       \DTMdisplaydate{\##1}{\##2}{\##3}{\##4}%
1084       \DTMenzdatetimesep
1085       \fi
1086       \DTMdisplaytime{\##5}{\##6}{\##7}%
1087       \ifDTMshowzone
1088         \DTMenztimezonesep
1089         \DTMdisplayzone{\##8}{\##9}%
1090       \fi
1091   }%
1092   \renewcommand*\{\DTMDisplay}{\DTMdisplay}%
1093 }%

```

Define numeric style.

```

1094 \DTMnewstyle
1095 {en-NZ-numeric}%
1096 {%
1097   \renewcommand*\DTMdisplaydate[4]{%
1098     \DTMifbool{en-NZ}{showdayofmonth}%
1099     {}%

```

```

1100      \number##3 % space intended
1101      \DTMenzdatesep
1102  }%
1103  {}%
1104  \number##2 % space intended
1105  \DTMifbool{en-NZ}{showyear}%
1106  {%
1107      \DTMenzdatesep
1108      \number##1 % space intended
1109  }%
1110  {}%
1111  {}%
1112  \renewcommand*{\DTMDisplaydate}[4]{\DTMdisplaydate{##1}{##2}{##3}{##4}}%
1113 }%
1114 {%
1115     \renewcommand*{\DTMdisplaytime}[3]{%
1116         \number##1
1117         \DTMenztimesep\DTMtwodigits{##2}%
1118         \ifDTMshowseconds\DTMenztimesep\DTMtwodigits{##3}\fi
1119     }%
1120 }%
1121 {%
1122     \DTMresetzones
1123     \DTMenzzonemaps
1124     \renewcommand*{\DTMdisplayzone}[2]{%
1125         \DTMifbool{en-NZ}{mapzone}%
1126         {\DTMusezonemapordefault{##1}{##2}}%
1127     }%
1128     \ifnum##1<0\else+\fi\DTMtwodigits{##1}%
1129     \ifDTMshowzoneminutes\DTMenztimesep\DTMtwodigits{##2}\fi
1130 }%
1131 }%
1132 }%
1133 {%
1134     \renewcommand*{\DTMdisplay}[9]{%
1135         \ifDTMshowdate
1136             \DTMdisplaydate{##1}{##2}{##3}{##4}%
1137             \DTMenzdatetimesep
1138         \fi
1139         \DTMdisplaytime{##5}{##6}{##7}%
1140         \ifDTMshowzone
1141             \DTMenztimezonesep
1142             \DTMdisplayzone{##8}{##9}%
1143         \fi
1144     }%
1145     \renewcommand*{\DTMDisplay}{\DTMdisplay}%
1146 }

```

**\DTMenzzonemaps** The time zone mappings are set through this command, which can be redefined if extra mappings are required or mappings need to be removed.

```

1147 \newcommand*{\DTMenzzonemaps}{%
1148   \DTMdefzonemap{12}{00}{NZST}%
1149   \DTMdefzonemap{12}{45}{CHAST}%
1150   \DTMdefzonemap{13}{00}{NZDT}%
1151   \DTMdefzonemap{13}{45}{CHADT}%
1152 }

Switch style according to the useregional setting.

1153 \DTMifcaseregional
1154 {}% do nothing
1155 {\DTMsetstyle{en-NZ}}%
1156 {\DTMsetstyle{en-NZ-numeric}}%

Redefine \dateenglish (or \date{dialect}) to prevent babel from resetting
\today. (For this to work, babel must already have been loaded if it's required.)

1157 \ifcsundef{date\CurrentTrackedDialect}
1158 {}% do nothing
1159   \ifundef{\dateenglish}
1160   {}%
1161   {}%
1162   {}%
1163   \def{\dateenglish}{%
1164     \DTMifcaseregional
1165     {}% do nothing
1166     {\DTMsetstyle{en-NZ}}%
1167     {\DTMsetstyle{en-NZ-numeric}}%
1168   }%
1169 }%
1170 }%
1171 {}%
1172 \csdef{date\CurrentTrackedDialect}{%
1173   \DTMifcaseregional
1174   {}% do nothing
1175   {\DTMsetstyle{en-NZ}}%
1176   {\DTMsetstyle{en-NZ-numeric}}%
1177 }%
1178 }%

```

## 14.8 English (GG) Code (`datetime2-en-GG.1df`)

This file contains the `en-GG` style.

Identify this module.

```
1179 \ProvidesDateTimeModule{en-GG}[2015/04/09 v1.01 (NLCT)]
```

Load base English module.

```
1180 \RequireDateTimeModule{english-base}
```

Allow the user a way of configuring the `en-GG` and `en-GG-numeric` styles. This
doesn't use the package wide separators such as `\dtm@datetimesep` in case other
date formats are also required.

\DTMGGdaymonthsep The separator between the day and month for the text format.  
1181 \newcommand\*\{\DTMGGdaymonthsep\}{\space}

\DTMGGmonthyearsep The separator between the month and year for the text format.  
1182 \newcommand\*\{\DTMGGmonthyearsep\}{\space}

\DTMGGdatetimesep The separator between the date and time blocks in the full format (either text or numeric).  
1183 \newcommand\*\{\DTMGGdatetimesep\}{\space}

\DTMGGtimezonesep The separator between the time and zone blocks in the full format (either text or numeric).  
1184 \newcommand\*\{\DTMGGtimezonesep\}{\space}

\DTMGGdatesep The separator for the numeric date format.  
1185 \newcommand\*\{\DTMGGdatesep\}{/}

\DTMGGtimesep The separator for the numeric time format.  
1186 \newcommand\*\{\DTMGGtimesep\}{:}

Provide keys that can be used in \DTMlangsetup to set these separators.

1187 \DTMdefkey{en-GG}{daymonthsep}{\renewcommand\*\{\DTMGGdaymonthsep\}{#1}}  
1188 \DTMdefkey{en-GG}{monthyearsep}{\renewcommand\*\{\DTMGGmonthyearsep\}{#1}}  
1189 \DTMdefkey{en-GG}{datetimesep}{\renewcommand\*\{\DTMGGdatetimesep\}{#1}}  
1190 \DTMdefkey{en-GG}{timezonesep}{\renewcommand\*\{\DTMGGtimezonesep\}{#1}}  
1191 \DTMdefkey{en-GG}{datesep}{\renewcommand\*\{\DTMGGdatesep\}{#1}}  
1192 \DTMdefkey{en-GG}{timesep}{\renewcommand\*\{\DTMGGtimesep\}{#1}}

Define a boolean key that can switch between full and abbreviated formats for the month and day of week names in the text format.

1193 \DTMdefboolkey{en-GG}{abbr}[true]{}

The default is the full name.

1194 \DTMsetbool{en-GG}{abbr}{false}

Define a boolean key that determines if the time zone mappings should be used.

1195 \DTMdefboolkey{en-GG}{mapzone}[true]{}

The default is to use mappings.

1196 \DTMsetbool{en-GG}{mapzone}{true}

Define a boolean key that determines whether to show or hide the day of the month. (Called `showdayofmonth` instead of `showday` to avoid confusion with the day of the week.)

1197 \DTMdefboolkey{en-GG}{showdayofmonth}[true]{}

The default is to show the day of the month.

1198 \DTMsetbool{en-GG}{showdayofmonth}{true}

Define a boolean key that determines whether to show or hide the year.

```
1199 \DTMdefboolkey{en-GG}{showyear}[true]{}
```

The default is to show the year.

```
1200 \DTMsetbool{en-GG}{showyear}{true}
```

\DTMenGGfmtordsuffix Define the ordinal suffix to be used by this style.

```
1201 \newcommand*{\DTMenGGfmtordsuffix}[1]{#1}
```

Define a setting to change the ordinal suffix style.

```
1202 \DTMdefchoicekey{en-GG}{ord}{\val\nr}{level,raise,omit,sc}{%
1203   \ifcase\nr\relax
1204     \renewcommand*{\DTMenGGfmtordsuffix}[1]{##1}%
1205   \or
1206     \renewcommand*{\DTMenGGfmtordsuffix}[1]{%
1207       \DTMtexorpdfstring{\protect\textrsuperscript{##1}}{##1}}%
1208   \or
1209     \renewcommand*{\DTMenGGfmtordsuffix}[1]{%
1210       \DTMtexorpdfstring{\protect\textrsc{##1}}{##1}}%
1211   \or
1212     \renewcommand*{\DTMenGGfmtordsuffix}[1]{%
1213       \DTMtexorpdfstring{\protect\textrsc{##1}}{##1}}%
1214 }
```

Define the en-GG style.

```
1215 \DTMnewstyle
1216   {en-GG}%
1217   {%
1218     \renewcommand*{\DTMenglishfmtordsuffix}{\DTMenGGfmtordsuffix}%
1219     \renewcommand*\DTMdisplaydate[4]{%
1220       \ifDTMshowdow
1221         \ifnum##4>-1%
1222           \DTMifbool{en-GG}{abbr}{%
1223             {\DTMenglishshortweekdayname{##4}}%
1224             {\DTMenglishweekdayname{##4}}%
1225             \space
1226           }%
1227         \fi
1228       \DTMifbool{en-GG}{showdayofmonth}{%
1229         \%
1230         \DTMenglishordinal{##3}%
1231         \DTMGGdaymonthsep
1232       }%
1233     }%
1234     \DTMifbool{en-GG}{abbr}{%
1235       {\DTMenglishshortmonthname{##2}}%
1236       {\DTMenglishmonthname{##2}}%
1237     \DTMifbool{en-GG}{showyear}{%
1238       \%
1239       \DTMGGmonthyearsep\space\intended
1240     }%
1241   }%
1242 }
```

```

1240      }%
1241      {}%
1242      }%
1243      \renewcommand*{\DTMDisplaydate}[4]{\DTMdisplaydate{##1}{##2}{##3}{##4}}%
1244      }%
1245      {%
1246          \renewcommand*{\DTMenglishtimesep}{\DTMengGGtimesep}%
1247          \DTMsetimestyle{englishampm}%
1248      }%
1249      {%
1250          \DTMresetzones
1251          \DTMengGzonemaps
1252          \renewcommand*{\DTMdisplayzone}[2]{%
1253              \DTMifbool{en-GG}{mapzone}%
1254              {\DTMusezonemapordefault{##1}{##2}}%
1255              {}%
1256              \ifnum##1<0\else+\fi\DTMtwodigits{##1}%
1257              \ifDTMshowzoneminutes\DTMengGGtimesep\DTMtwodigits{##2}\fi
1258          }%
1259      }%
1260  }%
1261  {%
1262      \renewcommand*{\DTMdisplay}[9]{%
1263          \ifDTMshowdate
1264              \DTMdisplaydate{##1}{##2}{##3}{##4}%
1265              \DTMengGGdatetimesep
1266              \fi
1267              \DTMdisplaytime{##5}{##6}{##7}%
1268              \ifDTMshowzone
1269                  \DTMengGGtimezonesep
1270                  \DTMdisplayzone{##8}{##9}%
1271              \fi
1272      }%
1273      \renewcommand*{\DTMDisplay}{\DTMdisplay}%
1274  }%

```

Define numeric style.

```

1275 \DTMnewstyle
1276  {en-GG-numeric}%
1277  {%
1278      \renewcommand*{\DTMdisplaydate}[4]{%
1279          \DTMifbool{en-GG}{showdayofmonth}%
1280          {}%
1281          \number##3 % space intended
1282          \DTMengGGdatesep
1283      }%
1284      {}%
1285      \number##2 % space intended
1286      \DTMifbool{en-GG}{showyear}%
1287      {}%

```

```

1288      \DTMendatesep
1289      \number##1 % space intended
1290  }%
1291  {}%
1292 }%
1293 \renewcommand*\DTMDisplaydate[4]{\DTMdisplaydate{##1}{##2}{##3}{##4}}%
1294 }%
1295 {%
1296   \renewcommand*\DTMdisplaytime[3]{%
1297     \number##1
1298     \DTMendatesep\DTMtwodigits{##2}%
1299     \ifDTMshowseconds\DTMendatesep\DTMtwodigits{##3}\fi
1300   }%
1301 }%
1302 {%
1303   \DTMresetzones
1304   \DTMendGzonemaps
1305   \renewcommand*\DTMdisplayzone[2]{%
1306     \DTMifbool{en-GG}{mapzone}%
1307     \{\DTMusezonemapordefault{##1}{##2}\}%
1308   }%
1309   \ifnum##1<0\else+\fi\DTMtwodigits{##1}%
1310   \ifDTMshowzoneminutes\DTMendatesep\DTMtwodigits{##2}\fi
1311 }%
1312 }%
1313 }%
1314 {%
1315   \renewcommand*\DTMdisplay[9]{%
1316     \ifDTMshowdate
1317       \DTMdisplaydate{##1}{##2}{##3}{##4}%
1318       \DTMendatesep
1319     \fi
1320     \DTMdisplaytime{##5}{##6}{##7}%
1321     \ifDTMshowzone
1322       \DTMendGzonemaps
1323       \DTMdisplayzone{##8}{##9}%
1324     \fi
1325   }%
1326   \renewcommand*\DTMDisplay{\DTMdisplay}%
1327 }

```

**\DTMendGzonemaps** The time zone mappings are set through this command, which can be redefined if extra mappings are required or mappings need to be removed.

```

1328 \newcommand*\DTMendGzonemaps{%
1329   \DTMdefzonemap{00}{00}{GMT}%
1330   \DTMdefzonemap{01}{00}{BST}%
1331 }

```

Switch style according to the **useregional** setting.

```

1332 \DTMifcaseregional
1333 {}% do nothing
1334 {\DTMsetstyle{en-GG}}%
1335 {\DTMsetstyle{en-GG-numeric}}%
Redefine \dateenglish (or \date⟨dialect⟩) to prevent babel from resetting
\today. (For this to work, babel must already have been loaded if it's required.)
1336 \ifcsundef{date\CurrentTrackedDialect}%
1337 {}% do nothing
1338 \ifundef{\dateenglish}%
1339 {}%
1340 {}%
1341 {}%
1342 \def{\dateenglish}{%
1343 \DTMifcaseregional
1344 {}% do nothing
1345 {\DTMsetstyle{en-GG}}%
1346 {\DTMsetstyle{en-GG-numeric}}%
1347 }%
1348 }%
1349 }%
1350 {}%
1351 \csdef{date\CurrentTrackedDialect}{%
1352 \DTMifcaseregional
1353 {}% do nothing
1354 {\DTMsetstyle{en-GG}}%
1355 {\DTMsetstyle{en-GG-numeric}}%
1356 }%
1357 }%

```

## 14.9 English (JE) Code (datetime2-en-JE.1df)

This file contains the en-JE style.

Identify this module.

```
1358 \ProvidesDateTimeModule{en-JE}[2015/04/09 v1.01 (NLCT)]
```

Load base English module.

```
1359 \RequireDateTimeModule{english-base}
```

Allow the user a way of configuring the en-JE and en-JE-numeric styles. This doesn't use the package wide separators such as \dtm@datetimesep in case other date formats are also required.

\DTMEnJEdaymonthsep The separator between the day and month for the text format.

```
1360 \newcommand*{\DTMEnJEdaymonthsep}{\space}
```

\DTMEnJEmonthyearsep The separator between the month and year for the text format.

```
1361 \newcommand*{\DTMEnJEmonthyearsep}{\space}
```

\DTMEnJEdatetimesep The separator between the date and time blocks in the full format (either text or numeric).  
1362 \newcommand\*\{\DTMEnJEdatetimesep\}{\space}

\DTMEnJEtimezonesep The separator between the time and zone blocks in the full format (either text or numeric).  
1363 \newcommand\*\{\DTMEnJEtimezonesep\}{\space}

\DTMEnJEdatesep The separator for the numeric date format.  
1364 \newcommand\*\{\DTMEnJEdatesep\}{/}

\DTMEnJEtimesep The separator for the numeric time format.  
1365 \newcommand\*\{\DTMEnJEtimesep\}{:}

Provide keys that can be used in \DTMlangsetup to set these separators.

1366 \DTMdefkey{en-JE}{daymonthsep}{\renewcommand\*\{\DTMEnJEdaymonthsep\}{#1}}  
1367 \DTMdefkey{en-JE}{monthyearsep}{\renewcommand\*\{\DTMEnJEmonthyearsep\}{#1}}  
1368 \DTMdefkey{en-JE}{datetimesep}{\renewcommand\*\{\DTMEnJEdatetimesep\}{#1}}  
1369 \DTMdefkey{en-JE}{timezonesep}{\renewcommand\*\{\DTMEnJEtimezonesep\}{#1}}  
1370 \DTMdefkey{en-JE}{datesep}{\renewcommand\*\{\DTMEnJEdatesep\}{#1}}  
1371 \DTMdefkey{en-JE}{timesep}{\renewcommand\*\{\DTMEnJEtimesep\}{#1}}

Define a boolean key that can switch between full and abbreviated formats for the month and day of week names in the text format.  
1372 \DTMdefboolkey{en-JE}{abbr}[true]{}

The default is the full name.  
1373 \DTMsetbool{en-JE}{abbr}{false}

Define a boolean key that determines if the time zone mappings should be used.  
1374 \DTMdefboolkey{en-JE}{mapzone}[true]{}

The default is to use mappings.  
1375 \DTMsetbool{en-JE}{mapzone}{true}

Define a boolean key that determines whether to show or hide the day of the month. (Called `showdayofmonth` instead of `showday` to avoid confusion with the day of the week.)  
1376 \DTMdefboolkey{en-JE}{showdayofmonth}[true]{}

The default is to show the day of the month.  
1377 \DTMsetbool{en-JE}{showdayofmonth}{true}

Define a boolean key that determines whether to show or hide the year.  
1378 \DTMdefboolkey{en-JE}{showyear}[true]{}

The default is to show the year.  
1379 \DTMsetbool{en-JE}{showyear}{true}

\DTMEnJEfmtordsuffix Define the ordinal suffix to be used by this style.  
1380 \newcommand\*\{\DTMEnJEfmtordsuffix\}[1]{#1}

Define a setting to change the ordinal suffix style.

```
1381 \DTMdefchoicekey{en-JE}{ord}{\val\nr}{level,raise,omit,sc}{%
1382   \ifcase\nr\relax
1383     \renewcommand*\{\DTMnJEfmtordsuffix}[1]{##1}%
1384   \or
1385     \renewcommand*\{\DTMnJEfmtordsuffix}[1]{%
1386       \DTMtexorpdfstring{\protect\textsuperscript{##1}}{##1}}%
1387   \or
1388     \renewcommand*\{\DTMnJEfmtordsuffix}[1]{%
1389       \or
1390         \renewcommand*\{\DTMnJEfmtordsuffix}[1]{%
1391           \DTMtexorpdfstring{\protect\textsc{##1}}{##1}}%
1392   \fi
1393 }
```

Define the en-JE style.

```
1394 \DTMnewstyle
1395 {en-JE}%
1396 {%
1397   \renewcommand*\{\DTMenglishfmtordsuffix}{\DTMnJEfmtordsuffix}%
1398   \renewcommand*\DTMdisplaydate[4]{%
1399     \ifDTMshowdow
1400       \ifnum##4>-1%
1401         \DTMifbool{en-JE}{abbr}%
1402         {\DTMenglishshortweekdayname{##4}}%
1403         {\DTMenglishweekdayname{##4}}%
1404       \space
1405     \fi
1406   \fi
1407   \DTMifbool{en-JE}{showdayofmonth}%
1408   {%
1409     \DTMenglishordinal{##3}%
1410     \DTMnJEdaymonthsep
1411   }%
1412   {%
1413     \DTMifbool{en-JE}{abbr}%
1414     {\DTMenglishshortmonthname{##2}}%
1415     {\DTMenglishmonthname{##2}}%
1416     \DTMifbool{en-JE}{showyear}%
1417   }%
1418   \DTMnJEmonthyearsep\number##1 % space intended
1419   }%
1420   {%
1421   }%
1422   \renewcommand*\{\DTMDisplaydate}[4]{\DTMdisplaydate{##1}{##2}{##3}{##4}}%
1423 }%
1424 {%
1425   \renewcommand*\DTMenglishtimesep{\DTMnJEtimesep}%
1426   \DTMsetimestyle{englishampm}%
1427 }%
```

```

1428  {%
1429    \DTMresetzones
1430    \DTMEnJEzonemaps
1431    \renewcommand*{\DTMdisplayzone}[2]{%
1432      \DTMifbool{en-JE}{\mapzone}{%
1433        {\DTMusezonemapordefault{\##1}{\##2}}%
1434      }%
1435      \ifnum##1<0\else+\fi\DTMtwodigits{\##1}%
1436      \ifDTMshowzoneminutes\DTMEnJEtimesep\DTMtwodigits{\##2}\fi
1437    }%
1438  }%
1439 }%
1440 {%
1441   \renewcommand*{\DTMdisplay}[9]{%
1442     \ifDTMshowdate
1443       \DTMdisplaydate{\##1}{\##2}{\##3}{\##4}%
1444       \DTMEnJEdatetimesep
1445     \fi
1446     \DTMdisplaytime{\##5}{\##6}{\##7}%
1447     \ifDTMshowzone
1448       \DTMEnJEtimezonesep
1449       \DTMdisplayzone{\##8}{\##9}%
1450     \fi
1451   }%
1452   \renewcommand*{\DTMDisplay}{\DTMdisplay}%
1453 }%

```

Define numeric style.

```

1454 \DTMnewstyle
1455 {en-JE-numeric}%
1456 {%
1457   \renewcommand*{\DTMdisplaydate}[4]{%
1458     \DTMifbool{en-JE}{\showdayofmonth}{%
1459       \number##3 % space intended
1460       \DTMEnJEdatesep
1461     }%
1462   }%
1463   \number##2 % space intended
1464   \DTMifbool{en-JE}{\showyear}{%
1465     \number##1 % space intended
1466     \DTMEnJEdatesep
1467     \number##1 % space intended
1468   }%
1469   \number##1 %
1470 }%
1471 }%
1472 \renewcommand*{\DTMDisplaydate}[4]{\DTMdisplaydate{\##1}{\##2}{\##3}{\##4}}%
1473 }%
1474 {%
1475   \renewcommand*{\DTMdisplaytime}[3]{%

```

```

1476     \number##1
1477     \DTMEnJEtimesep\DTMtwodigits{##2}%
1478     \ifDTMshowseconds\DTMEnJEtimesep\DTMtwodigits{##3}\fi
1479   }%
1480 }%
1481 {%
1482   \DTMresetzones
1483   \DTMEnJEzonemaps
1484   \renewcommand*\{\DTMdisplayzone}[2]{%
1485     \DTMifbool{en-JE}{mapzone}%
1486     {\DTMusezonemapordefault{##1}{##2}}%
1487     \fi%
1488     \ifnum##1<0\else+\fi\DTMtwodigits{##1}%
1489     \ifDTMshowzoneminutes\DTMEnJEtimesep\DTMtwodigits{##2}\fi
1490   }%
1491 }%
1492 }%
1493 {%
1494   \renewcommand*\{\DTMdisplay}[9]{%
1495     \ifDTMshowdate
1496       \DTMdisplaydate{##1}{##2}{##3}{##4}%
1497       \DTMEnJEdatetimesep
1498       \fi
1499       \DTMdisplaytime{##5}{##6}{##7}%
1500     \ifDTMshowzone
1501       \DTMEnJETIMEZONESEP
1502       \DTMdisplayzone{##8}{##9}%
1503     \fi
1504   }%
1505   \renewcommand*\{\DTMDisplay}{\DTMdisplay}%
1506 }

```

\DTMEnJEzonemaps The time zone mappings are set through this command, which can be redefined if extra mappings are required or mappings need to be removed.

```

1507 \newcommand*\{\DTMEnJEzonemaps}{%
1508   \DTMdefzonemap{00}{00}{GMT}%
1509   \DTMdefzonemap{01}{00}{BST}%
1510 }

```

Switch style according to the `useregional` setting.

```

1511 \DTMifcaseregional
1512 {}% do nothing
1513 {\DTMsetstyle{en-JE}}%
1514 {\DTMsetstyle{en-JE-numeric}}%

```

Redefine `\dateenglish` (or `\date{dialect}`) to prevent `babel` from resetting `\today`. (For this to work, `babel` must already have been loaded if it's required.)

```

1515 \ifcsundef{date\CurrentTrackedDialect}
1516 {}% do nothing
1517 \ifundef{\dateenglish}

```

```

1518  {%
1519  }%
1520  {%
1521      \def\dateenglish{%
1522          \DTMifcaseregional
1523              {}% do nothing
1524              {\DTMsetstyle{en-JE}}%
1525              {\DTMsetstyle{en-JE-numeric}}%
1526      }%
1527  }%
1528 }%
1529 {%
1530     \csdef{date\CurrentTrackedDialect}{%
1531         \DTMifcaseregional
1532             {}% do nothing
1533             {\DTMsetstyle{en-JE}}%
1534             {\DTMsetstyle{en-JE-numeric}}%
1535     }%
1536 }%

```

## 14.10 English (IM) Code (datetime2-en-IM.1df)

This file contains the `en-IM` style.

Identify this module.

```
1537 \ProvidesDateTimeModule{en-IM}[2015/04/09 v1.01 (NLCT)]
```

Load base English module.

```
1538 \RequireDateTimeModule{english-base}
```

Allow the user a way of configuring the `en-IM` and `en-IM-numeric` styles. This doesn't use the package wide separators such as `\dtm@datetimesep` in case other date formats are also required.

`\DTM{en-IM}{daymonthsep}` The separator between the day and month for the text format.

```
1539 \newcommand*{\DTM{en-IM}{daymonthsep}}{\space}
```

`\DTM{en-IM}{monthyearsep}` The separator between the month and year for the text format.

```
1540 \newcommand*{\DTM{en-IM}{monthyearsep}}{\space}
```

`\DTM{en-IM}{datetimesep}` The separator between the date and time blocks in the full format (either text or numeric).

```
1541 \newcommand*{\DTM{en-IM}{datetimesep}}{\space}
```

`\DTM{en-IM}{timezonesep}` The separator between the time and zone blocks in the full format (either text or numeric).

```
1542 \newcommand*{\DTM{en-IM}{timezonesep}}{\space}
```

`\DTM{en-IM}{datesep}` The separator for the numeric date format.

```
1543 \newcommand*{\DTM{en-IM}{datesep}}{/}
```

\DTMnIMtimesep The separator for the numeric time format.

```
1544 \newcommand*{\DTMnIMtimesep}{:}
```

Provide keys that can be used in \DTMlangsetup to set these separators.

```
1545 \DTMdefkey{en-IM}{daymonthsep}{\renewcommand*{\DTMnIMdaymonthsep}{#1}}
1546 \DTMdefkey{en-IM}{monthyearsep}{\renewcommand*{\DTMnIMmonthyearsep}{#1}}
1547 \DTMdefkey{en-IM}{datetimesep}{\renewcommand*{\DTMnIMdatetimesep}{#1}}
1548 \DTMdefkey{en-IM}{timezonesep}{\renewcommand*{\DTMnIMtimezonesep}{#1}}
1549 \DTMdefkey{en-IM}{datesep}{\renewcommand*{\DTMnIMdatesep}{#1}}
1550 \DTMdefkey{en-IM}{timesep}{\renewcommand*{\DTMnIMtimesep}{#1}}
```

Define a boolean key that can switch between full and abbreviated formats for the month and day of week names in the text format.

```
1551 \DTMdefboolkey{en-IM}{abbr}[true]{}
```

The default is the full name.

```
1552 \DTMsetbool{en-IM}{abbr}{false}
```

Define a boolean key that determines if the time zone mappings should be used.

```
1553 \DTMdefboolkey{en-IM}{mapzone}[true]{}
```

The default is to use mappings.

```
1554 \DTMsetbool{en-IM}{mapzone}{true}
```

Define a boolean key that determines whether to show or hide the day of the month. (Called `showdayofmonth` instead of `showday` to avoid confusion with the day of the week.)

```
1555 \DTMdefboolkey{en-IM}{showdayofmonth}[true]{}
```

The default is to show the day of the month.

```
1556 \DTMsetbool{en-IM}{showdayofmonth}{true}
```

Define a boolean key that determines whether to show or hide the year.

```
1557 \DTMdefboolkey{en-IM}{showyear}[true]{}
```

The default is to show the year.

```
1558 \DTMsetbool{en-IM}{showyear}{true}
```

\DTMnIMfmtordsuffix Define the ordinal suffix to be used by this style.

```
1559 \newcommand*{\DTMnIMfmtordsuffix}[1]{#1}
```

Define a setting to change the ordinal suffix style.

```
1560 \DTMdefchoicekey{en-IM}{ord}{\val\nr}{level,raise,omit,sc}{%
1561   \ifcase\nr\relax
1562     \renewcommand*{\DTMnIMfmtordsuffix}[1]{##1}%
1563   \or
1564     \renewcommand*{\DTMnIMfmtordsuffix}[1]{%
1565       \DTMtexorpdfstring{\protect\textrightsquigarrow}{##1}{}{##1}}%
1566   \or
1567     \renewcommand*{\DTMnIMfmtordsuffix}[1]{()}%
1568   \or}
```

```

1569     \renewcommand*{\DTMenglishfmtordsuffix}[1]{%
1570     \DTMtexorpdfstring{\protect\textsc{##1}}{##1}%
1571   \fi
1572 }

Define the en-IM style.

1573 \DTMnewstyle
1574 {en-IM}% label
1575 {%
1576   \renewcommand*{\DTMenglishfmtordsuffix}{\DTMenglishfmtordsuffix}%
1577   \renewcommand*\DTMdisplaydate[4]{%
1578     \ifDTMshowdow
1579       \ifnum##4>-1%
1580         \DTMifbool{en-IM}{abbr}%
1581         {\DTMenglishshortweekdayname{##4}}%
1582         {\DTMenglishweekdayname{##4}}%
1583         \space
1584       \fi
1585     \fi
1586     \DTMifbool{en-IM}{showdayofmonth}%
1587     \f%
1588       \DTMenglishordinal{##3}%
1589       \DTMenglishmonthsep
1590     \f%
1591     \f%
1592     \DTMifbool{en-IM}{abbr}%
1593     {\DTMenglishshortmonthname{##2}}%
1594     {\DTMenglishmonthname{##2}}%
1595     \DTMifbool{en-IM}{showyear}%
1596     \f%
1597       \DTMenglishyearsep\number##1 % space intended
1598     \f%
1599     \f%
1600   \f%
1601   \renewcommand*{\DTMDisplaydate}[4]{\DTMdisplaydate{##1}{##2}{##3}{##4}}%
1602 \f%
1603 {%
1604   \renewcommand*\DTMenglishtimesep{\DTMenglishtimesep}%
1605   \DTMsettimestyle{englishampm}%
1606 \f%
1607 {%
1608   \DTMresetzones
1609   \DTMenglishzonemaps
1610   \renewcommand*{\DTMdisplayzone}[2]{%
1611     \DTMifbool{en-IM}{mapzone}%
1612     {\DTMusezonemapdefault{##1}{##2}}%
1613     \f%
1614       \ifnum##1<0\else+\fi\DTMtwodigits{##1}%
1615       \ifDTMshowzoneminutes\DTMenglishtimesep\DTMtwodigits{##2}\fi
1616     \f%

```

```

1617     }%
1618 }%
1619 {%
1620   \renewcommand*\{\DTMdisplay\}[9]{%
1621     \ifDTMshowdate
1622       \DTMdisplaydate{##1}{##2}{##3}{##4}%
1623       \DTMenIMdatetimesep
1624     \fi
1625     \DTMdisplaytime{##5}{##6}{##7}%
1626     \ifDTMshowzone
1627       \DTMenIMtimezonesep
1628       \DTMdisplayzone{##8}{##9}%
1629     \fi
1630   }%
1631   \renewcommand*\{\DTMDisplay\}{\DTMdisplay}%
1632 }%
1633 Define numeric style.
1634 \DTMnewstyle
1635 {en-IM-numeric}%
1636   label
1637   {%
1638     \renewcommand*\DTMdisplaydate[4]{%
1639       \DTMifbool{en-IM}{showdayofmonth}%
1640       \number##3 % space intended
1641       \DTMenIMdatesep
1642     }%
1643     \number##2 % space intended
1644     \DTMifbool{en-IM}{showyear}%
1645     \number##1 % space intended
1646     \DTMenIMdatesep
1647     \number##1 % space intended
1648   }%
1649   {}%
1650 }%
1651   \renewcommand*\{\DTMDisplaydate\}[4]{\DTMdisplaydate{##1}{##2}{##3}{##4}}%
1652 }%
1653 {%
1654   \renewcommand*\DTMdisplaytime[3]{%
1655     \number##1
1656     \DTMenIMtimesep\DTMtwodigits{##2}%
1657     \ifDTMshowseconds\DTMenIMtimesep\DTMtwodigits{##3}\fi
1658   }%
1659 }%
1660 {%
1661   \DTMresetzones
1662   \DTMenIMzonemaps
1663   \renewcommand*\{\DTMdisplayzone\}[2]{%
1664     \DTMifbool{en-IM}{mapzone}%

```

```

1665      {\DTMusezonemapordefault{##1}{##2}}%
1666      {%
1667          \ifnum##1<0\else+\fi\DTMtwodigits{##1}%
1668          \ifDTMshowzoneminutes\DTMenIMtimesep\DTMtwodigits{##2}\fi
1669      }%
1670  }%
1671 }%
1672 {%
1673     \renewcommand*\{\DTMdisplay}[9]{%
1674         \ifDTMshowdate
1675             \DTMdisplaydate{##1}{##2}{##3}{##4}%
1676             \DTMenIMdatetimesep
1677             \fi
1678             \DTMdisplaytime{##5}{##6}{##7}%
1679             \ifDTMshowzone
1680                 \DTMenIMtimezonesep
1681                 \DTMdisplayzone{##8}{##9}%
1682             \fi
1683     }%
1684     \renewcommand*\{\DTMDisplay}{\DTMdisplay}%
1685 }

```

**\DTMenIMzonemaps** The time zone mappings are set through this command, which can be redefined if extra mappings are required or mappings need to be removed.

```

1686 \newcommand*\{\DTMenIMzonemaps}{%
1687     \DTMdefzonemap{00}{00}{GMT}%
1688     \DTMdefzonemap{01}{00}{BST}%
1689 }

```

Switch style according to the `useregional` setting.

```

1690 \DTMifcaseregional
1691 {}% do nothing
1692 {\DTMsetstyle{en-IM}}%
1693 {\DTMsetstyle{en-IM-numeric}}%

```

Redefine `\dateenglish` (or `\date{dialect}`) to prevent `babel` from resetting `\today`. (For this to work, `babel` must already have been loaded if it's required.)

```

1694 \ifcsundef{date\CurrentTrackedDialect}
1695 {}% do nothing
1696     \ifundef{\dateenglish}
1697     {}%
1698 }%
1699 {}%
1700     \def{\dateenglish}{%
1701         \DTMifcaseregional
1702         {}% do nothing
1703         {\DTMsetstyle{en-IM}}%
1704         {\DTMsetstyle{en-IM-numeric}}%
1705     }%
1706 }%

```

```

1707 }%
1708 {%
1709   \csdef{date\CurrentTrackedDialect}{%
1710     \DTMifcaseregional
1711     {}% do nothing
1712     {\DTMsetstyle{en-IM}}%
1713     {\DTMsetstyle{en-IM-numeric}}%
1714   }%
1715 }%

```

## 14.11 English (MT) Code (datetime2-en-MT.ldf)

This file contains the `en-MT` style.

Identify this module.

```
1716 \ProvidesDateTimeModule{en-MT}[2015/04/09 v1.01 (NLCT)]
```

Load base English module.

```
1717 \RequireDateTimeModule{english-base}
```

Allow the user a way of configuring the `en-MT` and `en-MT-numeric` styles. This doesn't use the package wide separators such as `\dtm@datetimesep` in case other date formats are also required.

`\DTM{en-MT}{daymonthsep}` The separator between the day and month for the text format.

```
1718 \newcommand*{\DTM{en-MT}{daymonthsep}}{\space}
```

`\DTM{en-MT}{monthyearsep}` The separator between the month and year for the text format.

```
1719 \newcommand*{\DTM{en-MT}{monthyearsep}}{\space}
```

`\DTM{en-MT}{datetimesep}` The separator between the date and time blocks in the full format (either text or numeric).

```
1720 \newcommand*{\DTM{en-MT}{datetimesep}}{\space}
```

`\DTM{en-MT}{timezonesep}` The separator between the time and zone blocks in the full format (either text or numeric).

```
1721 \newcommand*{\DTM{en-MT}{timezonesep}}{\space}
```

`\DTM{en-MT}{datesep}` The separator for the numeric date format.

```
1722 \newcommand*{\DTM{en-MT}{datesep}}{/}
```

`\DTM{en-MT}{timesep}` The separator for the numeric time format.

```
1723 \newcommand*{\DTM{en-MT}{timesep}}{::}
```

Provide keys that can be used in `\DTMlangsetup` to set these separators.

```

1724 \DTMdefkey{en-MT}{daymonthsep}{\renewcommand*{\DTM{en-MT}{daymonthsep}}{\#1}}
1725 \DTMdefkey{en-MT}{monthyearsep}{\renewcommand*{\DTM{en-MT}{monthyearsep}}{\#1}}
1726 \DTMdefkey{en-MT}{datetimesep}{\renewcommand*{\DTM{en-MT}{datetimesep}}{\#1}}
1727 \DTMdefkey{en-MT}{timezonesep}{\renewcommand*{\DTM{en-MT}{timezonesep}}{\#1}}
1728 \DTMdefkey{en-MT}{datesep}{\renewcommand*{\DTM{en-MT}{datesep}}{\#1}}
1729 \DTMdefkey{en-MT}{timesep}{\renewcommand*{\DTM{en-MT}{timesep}}{\#1}}

```

Define a boolean key that can switch between full and abbreviated formats for the month and day of week names in the text format.

```
1730 \DTMdefboolkey{en-MT}{abbr}{true}{}{}
```

The default is the full name.

```
1731 \DTMsetbool{en-MT}{abbr}{false}
```

Define a boolean key that determines if the time zone mappings should be used.

```
1732 \DTMdefboolkey{en-MT}{mapzone}{true}{}{}
```

The default is to use mappings.

```
1733 \DTMsetbool{en-MT}{mapzone}{true}
```

Define a boolean key that determines whether to show or hide the day of the month. (Called `showdayofmonth` instead of `showday` to avoid confusion with the day of the week.)

```
1734 \DTMdefboolkey{en-MT}{showdayofmonth}{true}{}{}
```

The default is to show the day of the month.

```
1735 \DTMsetbool{en-MT}{showdayofmonth}{true}
```

Define a boolean key that determines whether to show or hide the year.

```
1736 \DTMdefboolkey{en-MT}{showyear}{true}{}{}
```

The default is to show the year.

```
1737 \DTMsetbool{en-MT}{showyear}{true}
```

`\DTMendMTfmtordsuffix` Define the ordinal suffix to be used by this style.

```
1738 \newcommand*{\DTMendMTfmtordsuffix}[1]{}{}
```

Define a setting to change the ordinal suffix style.

```
1739 \DTMdefchoicekey{en-MT}{ord}{\val\nr}{level,raise,omit,sc}{%  
1740   \ifcase\nr\relax  
1741     \renewcommand*{\DTMendMTfmtordsuffix}[1]{##1}%  
1742   \or  
1743     \renewcommand*{\DTMendMTfmtordsuffix}[1]{%  
1744       \DTMtexorpdfstring{\protect\textsuperscript{##1}}{##1}}%  
1745   \or  
1746     \renewcommand*{\DTMendMTfmtordsuffix}[1]{}}%  
1747   \or  
1748     \renewcommand*{\DTMendMTfmtordsuffix}[1]{%  
1749       \DTMtexorpdfstring{\protect\textsc{##1}}{##1}}%  
1750 \fi  
1751 }
```

Define the `en-MT` style.

```
1752 \DTMnewstyle  
1753 {en-MT} % label  
1754 { % date style  
1755   \renewcommand*{\DTMenglishfmtordsuffix}{\DTMendMTfmtordsuffix}%  
1756   \renewcommand*\DTMdisplaydate[4]{%
```

```

1757   \ifDTMshowdow
1758     \ifnum##4>-1%
1759       \DTMifbool{en-MT}{abbr}%
1760         {\DTMenglishshortweekdayname{##4}}%
1761         {\DTMenglishweekdayname{##4}}%
1762       \space
1763     \fi
1764   \fi
1765   \DTMifbool{en-MT}{showdayofmonth}%
1766   {%
1767     \DTMenglishordinal{##3}%
1768     \DTMendaymonthsep
1769   }%
1770   {}%
1771   \DTMifbool{en-MT}{abbr}%
1772   {\DTMenglishshortmonthname{##2}}%
1773   {\DTMenglishmonthname{##2}}%
1774   \DTMifbool{en-MT}{showyear}%
1775   {%
1776     \DTMendayyearsep\number##1 % space intended
1777   }%
1778   {}%
1779 }%
1780   \renewcommand*\{\DTMDisplaydate}[4]{\DTMdisplaydate{##1}{##2}{##3}{##4}}%
1781 }%
1782 {%
1783   \renewcommand*\DTMenglishtimesep{\DTMendatetimesep}%
1784   \DTMsettimestyle{englishampm}%
1785 }%
1786 {%
1787   \DTMresetzones
1788   \DTMendzonemaps
1789   \renewcommand*\{\DTMdisplayzone}[2]{%
1790     \DTMifbool{en-MT}{mapzone}%
1791     {\DTMusezonemapordefault{##1}{##2}}%
1792   }%
1793   \ifnum##1<0\else+\fi\DTMtowodigits{##1}%
1794   \ifDTMshowzoneminutes\DTMendatetimesep\DTMtowodigits{##2}\fi
1795 }%
1796 }%
1797 }%
1798 {%
1799   \renewcommand*\{\DTMdisplay}[9]{%
1800     \ifDTMshowdate
1801       \DTMdisplaydate{##1}{##2}{##3}{##4}%
1802       \DTMendatetimesep
1803     \fi
1804     \DTMdisplaytime{##5}{##6}{##7}%
1805     \ifDTMshowzone
1806       \DTMendtimezonesep

```

```

1807      \DTMdisplayzone{##8}{##9}%
1808      \fi
1809  }%
1810  \renewcommand*{\DTMDisplay}{\DTMdisplay}%
1811 }%
Define numeric style.
1812 \DTMnewstyle
1813 {en-MT-numeric}%
1814 {%
1815   \renewcommand*{\DTMdisplaydate}[4]{%
1816     \DTMifbool{en-MT}{showdayofmonth}%
1817   }%
1818   \number##3 % space intended
1819   \DTMendatesep
1820 }%
1821 }%
1822 \number##2 % space intended
1823 \DTMifbool{en-MT}{showyear}%
1824 }%
1825   \DTMendatesep
1826   \number##1 % space intended
1827 }%
1828 }%
1829 }%
1830 \renewcommand*{\DTMDisplaydate}[4]{\DTMdisplaydate{##1}{##2}{##3}{##4}}%
1831 }%
1832 {%
1833   \renewcommand*{\DTMdisplaytime}[3]{%
1834     \number##1
1835     \DTMendtimesep\DTMtwodigits{##2}%
1836     \ifDTMshowseconds\DTMendtimesep\DTMtwodigits{##3}\fi
1837   }%
1838 }%
1839 }%
1840 \DTMresetzones
1841 \DTMendzonemaps
1842 \renewcommand*{\DTMdisplayzone}[2]{%
1843   \DTMifbool{en-MT}{mapzone}%
1844   {\DTMusezonemapordefault{##1}{##2}}%
1845 }%
1846   \ifnum##1<0\else+\fi\DTMtwodigits{##1}%
1847   \ifDTMshowzoneminutes\DTMendtimesep\DTMtwodigits{##2}\fi
1848 }%
1849 }%
1850 }%
1851 }%
1852 \renewcommand*{\DTMdisplay}[9]{%
1853   \ifDTMshowdate
1854     \DTMdisplaydate{##1}{##2}{##3}{##4}%

```

```

1855     \DTMenMTdatetimesep
1856     \fi
1857     \DTMdisplaytime{##5}{##6}{##7}%
1858     \ifDTMshowzone
1859     \DTMenMTtimezonesep
1860     \DTMdisplayzone{##8}{##9}%
1861     \fi
1862   }%
1863   \renewcommand*\{\DTMDisplay}{\DTMdisplay}%
1864 }

```

**\DTMenMTzonemaps** The time zone mappings are set through this command, which can be redefined if extra mappings are required or mappings need to be removed.

```

1865 \newcommand*\{\DTMenMTzonemaps}{%
1866   \DTMdefzonemap{02}{00}{CEST}%
1867   \DTMdefzonemap{01}{00}{CET}%
1868 }

```

Switch style according to the `useregional` setting.

```

1869 \DTMifcaseregional
1870 {}% do nothing
1871 {\DTMsetstyle{en-MT}}%
1872 {\DTMsetstyle{en-MT-numeric}}%

```

Redefine `\dateenglish` (or `\date{dialect}`) to prevent `babel` from resetting `\today`. (For this to work, `babel` must already have been loaded if it's required.)

```

1873 \ifcsundef{date\CurrentTrackedDialect}
1874 {}% do nothing
1875   \ifundef\dateenglish
1876   {}%
1877   {}%
1878   {}%
1879   \def\dateenglish{%
1880     \DTMifcaseregional
1881     {}% do nothing
1882     {\DTMsetstyle{en-MT}}%
1883     {\DTMsetstyle{en-MT-numeric}}%
1884   }%
1885 }%
1886 }%
1887 {}%
1888 \csdef{date\CurrentTrackedDialect}{%
1889   \DTMifcaseregional
1890   {}% do nothing
1891   {\DTMsetstyle{en-MT}}%
1892   {\DTMsetstyle{en-MT-numeric}}%
1893 }%
1894 }%

```

## 14.12 English (IE) Code (datetime2-en-IE.ldf)

This file contains the en-IE style.

Identify this module.

1895 \ProvidesDateTimeModule{en-IE}[2015/04/09 v1.01 (NLCT)]

Load base English module.

1896 \RequireDateTimeModule{english-base}

Allow the user a way of configuring the en-IE and en-IE-numeric styles. This doesn't use the package wide separators such as \dtm@datetimesep in case other date formats are also required.

\DTMnIEDaymonthsep The separator between the day and month for the text format.

1897 \newcommand\*{\DTMnIEDaymonthsep}{\space}

\DTMnIEmonthyearsep The separator between the month and year for the text format.

1898 \newcommand\*{\DTMnIEmonthyearsep}{\space}

\DTMnIEDatetimesep The separator between the date and time blocks in the full format (either text or numeric).

1899 \newcommand\*{\DTMnIEDatetimesep}{\space}

\DTMnIEtimezonesep The separator between the time and zone blocks in the full format (either text or numeric).

1900 \newcommand\*{\DTMnIEtimezonesep}{\space}

\DTMnIEDatesep The separator for the numeric date format.

1901 \newcommand\*{\DTMnIEDatesep}{/}

\DTMnIEtimesep The separator for the numeric time format.

1902 \newcommand\*{\DTMnIEtimesep}{:}

Provide keys that can be used in \DTMlangsetup to set these separators.

1903 \DTMdefkey{en-IE}{daymonthsep}{\renewcommand\*{\DTMnIEDaymonthsep}{#1}}

1904 \DTMdefkey{en-IE}{monthyearsep}{\renewcommand\*{\DTMnIEmonthyearsep}{#1}}

1905 \DTMdefkey{en-IE}{datetimesep}{\renewcommand\*{\DTMnIEDatetimesep}{#1}}

1906 \DTMdefkey{en-IE}{timezonesep}{\renewcommand\*{\DTMnIEtimezonesep}{#1}}

1907 \DTMdefkey{en-IE}{datesep}{\renewcommand\*{\DTMnIEDatesep}{#1}}

1908 \DTMdefkey{en-IE}{timesep}{\renewcommand\*{\DTMnIEtimesep}{#1}}

Define a boolean key that can switch between full and abbreviated formats for the month and day of week names in the text format.

1909 \DTMdefboolkey{en-IE}{abbr}[true]{}

The default is the full name.

1910 \DTMsetbool{en-IE}{abbr}{false}

Define a boolean key that determines if the time zone mappings should be used.

1911 \DTMdefboolkey{en-IE}{mapzone}[true]{}

The default is to use mappings.

```
1912 \DTMsetbool{en-IE}{mapzone}{true}
```

Define a boolean key that determines whether to show or hide the day of the month. (Called `showdayofmonth` instead of `showday` to avoid confusion with the day of the week.)

```
1913 \DTMdefboolkey{en-IE}{showdayofmonth}[true]{}
```

The default is to show the day of the month.

```
1914 \DTMsetbool{en-IE}{showdayofmonth}{true}
```

Define a boolean key that determines whether to show or hide the year.

```
1915 \DTMdefboolkey{en-IE}{showyear}[true]{}
```

The default is to show the year.

```
1916 \DTMsetbool{en-IE}{showyear}{true}
```

`\DTMnIEfmtordsuffix` Define the ordinal suffix to be used by this style.

```
1917 \newcommand*{\DTMnIEfmtordsuffix}[1]{#1}
```

Define a setting to change the ordinal suffix style.

```
1918 \DTMdefchoicekey{en-IE}{ord}{\val\nr}{level,raise,omit,sc}{%
1919   \ifcase\nr\relax
1920     \renewcommand*{\DTMnIEfmtordsuffix}[1]{##1}%
1921   \or
1922     \renewcommand*{\DTMnIEfmtordsuffix}[1]{%
1923       \DTMtexorpdfstring{\protect\textsuperscript{##1}}{##1}}%
1924   \or
1925     \renewcommand*{\DTMnIEfmtordsuffix}[1]{%
1926       \DTMtexorpdfstring{\protect\textsc{##1}}{##1}}%
1927   \or
1928     \renewcommand*{\DTMnIEfmtordsuffix}[1]{%
1929       \DTMtexorpdfstring{\protect\textsc{##1}}{##1}}%
1930 }
```

Define the `en-IE` style.

```
1931 \DTMnewstyle
1932 {en-IE}%
1933 {%
1934   \renewcommand*{\DTMenglishfmtordsuffix}{\DTMnIEfmtordsuffix}%
1935   \renewcommand*\DTMdisplaydate[4]{%
1936     \ifDTMshowdow
1937       \ifnum##4>-1%
1938         \DTMifbool{en-IE}{abbr}{%
1939           {\DTMenglishshortweekdayname{##4}}%
1940           {\DTMenglishweekdayname{##4}}%
1941           \space
1942         }%
1943       \fi
1944     \DTMifbool{en-IE}{showdayofmonth}{%
1945       \fi
1946 }
```

```

1946      \DTMenglishordinal{##3}%
1947      \DTMnIEdaymonthsep
1948  }%
1949  {}%
1950  \DTMifbool{en-IE}{abbr}%
1951  {\DTMenglishshortmonthname{##2}}%
1952  {\DTMenglishmonthname{##2}}%
1953  \DTMifbool{en-IE}{showyear}%
1954  {%
1955      \DTMnIEmonthyearsep\number##1 % space intended
1956  }%
1957  {}%
1958  {}%
1959  \renewcommand*\{\DTMDisplaydate\}[4]{\DTMdisplaydate{##1}{##2}{##3}{##4}}%
1960 }%
1961 {%
1962     \renewcommand*\{\DTMenglishtimesep\{\DTMnIEtimesep\}%
1963     \DTMsettimestyle{englishampm}}%
1964 }%
1965 {%
1966     \DTMresetzones
1967     \DTMnIEzonemaps
1968     \renewcommand*\{\DTMdisplayzone\}[2]{%
1969         \DTMifbool{en-IE}{mapzone}%
1970         {\DTMusezonemapordefault{##1}{##2}}%
1971         {%
1972             \ifnum##1<0\else+\fi\DTMtwodigits{##1}%
1973             \ifDTMshowzoneminutes\DTMnIEtimesep\DTMtwodigits{##2}\fi
1974         }%
1975     }%
1976 }%
1977 {%
1978     \renewcommand*\{\DTMdisplay\}[9]{%
1979         \ifDTMshowdate
1980             \DTMdisplaydate{##1}{##2}{##3}{##4}%
1981             \DTMnIEdatetimesep
1982         \fi
1983         \DTMdisplaytime{##5}{##6}{##7}%
1984         \ifDTMshowzone
1985             \DTMnIEtmezonesep
1986             \DTMdisplayzone{##8}{##9}%
1987         \fi
1988     }%
1989     \renewcommand*\{\DTMDisplay\}{\DTMdisplay}%
1990 }%

```

Define numeric style.

```

1991 \DTMnewstyle
1992 {en-IE-numeric}%
1993 {} date style

```

```

1994 \renewcommand*\DTMdisplaydate[4]{%
1995   \DTMifbool{en-IE}{showdayofmonth}%
1996   {%
1997     \number##3 % space intended
1998     \DTMnIEdatesep
1999   }%
2000   {}%
2001   \number##2 % space intended
2002   \DTMifbool{en-IE}{showyear}%
2003   {%
2004     \DTMnIEdatesep
2005     \number##1 % space intended
2006   }%
2007   {}%
2008   }%
2009 \renewcommand*{\DTMDisplaydate}[4]{\DTMdisplaydate{##1}{##2}{##3}{##4}}%
2010 }%
2011 {%
2012   \renewcommand*\DTMdisplaytime[3]{%
2013     \number##1
2014     \DTMnIetimesep\DTMtwodigits{##2}%
2015     \ifDTMshowseconds\DTMnIetimesep\DTMtwodigits{##3}\fi
2016   }%
2017 }%
2018 {%
2019   \DTMresetzones
2020   \DTMnIEzonemaps
2021 \renewcommand*{\DTMdisplayzone}[2]{%
2022   \DTMifbool{en-IE}{mapzone}%
2023   {\DTMusezonemapordefault{##1}{##2}}%
2024   {%
2025     \ifnum##1<0\else+\fi\DTMtwodigits{##1}%
2026     \ifDTMshowzoneminutes\DTMnIetimesep\DTMtwodigits{##2}\fi
2027   }%
2028 }%
2029 }%
2030 {%
2031   \renewcommand*{\DTMdisplay}[9]{%
2032     \ifDTMshowdate
2033       \DTMdisplaydate{##1}{##2}{##3}{##4}%
2034       \DTMnIEdatetimesep
2035     \fi
2036     \DTMdisplaytime{##5}{##6}{##7}%
2037     \ifDTMshowzone
2038       \DTMnIEtimezonesep
2039       \DTMdisplayzone{##8}{##9}%
2040     \fi
2041   }%
2042   \renewcommand*{\DTMDisplay}{\DTMdisplay}%
2043 }

```

\DTMdefzonemaps The time zone mappings are set through this command, which can be redefined if extra mappings are required or mappings need to be removed.

```
2044 \newcommand*{\DTMdefzonemaps}{%
2045   \DTMdefzonemap{00}{00}{GMT}%
2046   \DTMdefzonemap{01}{00}{IST}%
2047 }
```

Switch style according to the `userregional` setting.

```
2048 \DTMifcaseregional
2049 {}% do nothing
2050 {\DTMsetstyle{en-IE}}%
2051 {\DTMsetstyle{en-IE-numeric}}%
2052 \ifcsundef{date\CurrentTrackedDialect}
2053 {}% do nothing
2054   \ifundef{\dateenglish}
2055   {}%
2056 }%
2057 {}%
2058   \def{\dateenglish}{%
2059     \DTMifcaseregional
2060     {}% do nothing
2061     {\DTMsetstyle{en-IE}}%
2062     {\DTMsetstyle{en-IE-numeric}}%
2063   }%
2064 }%
2065 }%
2066 {}%
2067 \csdef{date\CurrentTrackedDialect}{%
2068   \DTMifcaseregional
2069   {}% do nothing
2070   {\DTMsetstyle{en-IE}}%
2071   {\DTMsetstyle{en-IE-numeric}}%
2072 }%
2073 }%
```

## Change History

1.0	General: Initial release . . . . .	9, 14, 16, 21, 26, 31, 35, 40, 45, 50, 55, 60	1.01	General: fixed mispelt style name	19
-----	------------------------------------	--	------	-----------------------------------	----

## Index

<b>A</b>	
abbr . . . . .	5, 6
<b>D</b>	
datesep . . . . .	5, 6
datetimesep . . . . .	5, 6
daymonthsep . . . . .	5
dayyearsep . . . . .	6
\DTMengAUdatesep . . . . .	31
\DTMengAUdatetimesep . . . . .	31
\DTMengAUdaymonthsep . . . . .	31
\DTMengAUfmtordsuffix . . . . .	32
\DTMengAUmonthyearsep . . . . .	31
\DTMengAUtimesep . . . . .	31
\DTMengAUtimezonesep . . . . .	31
\DTMengAUzonemaps . . . . .	35
\DTMengCAdatesep . . . . .	26
\DTMengCADatetimesep . . . . .	26
\DTMengCADayyearsep . . . . .	26
\DTMengCAFmtordsuffix . . . . .	27
\DTMengCAMonthdaysep . . . . .	26
\DTMengCATimesep . . . . .	26
\DTMengCATimezonesep . . . . .	26
\DTMengCAzonemaps . . . . .	30
\DTMengGBdatesep . . . . .	16
\DTMengGBdatetimesep . . . . .	16
\DTMengGBdaymonthsep . . . . .	16
\DTMengGBfmtordsuffix . . . . .	17
\DTMengGBmonthyearsep . . . . .	16
\DTMengGBTimesep . . . . .	16
\DTMengGBtimezonesep . . . . .	16
\DTMengGBzonemaps . . . . .	20
\DTMengGGdatesep . . . . .	41
\DTMengGGdatetimesep . . . . .	41
\DTMengGGdaymonthsep . . . . .	41
\DTMengGGfmtordsuffix . . . . .	42
\DTMengGGmonthyearsep . . . . .	41
\DTMengGGtimesep . . . . .	41
\DTMengGGtimezonesep . . . . .	44
\DTMenglisham . . . . .	12
\DTMenglishampmfmt . . . . .	13
\DTMenglishfmtordsuffix . . . . .	10
\DTMenglishmidnight . . . . .	13
\DTMenglishmonthname . . . . .	10
\DTMenglishnd . . . . .	10
\DTMenglishnoon . . . . .	13
\DTMenglishordinal . . . . .	9
\DTMenglishpm . . . . .	12
\DTMenglishrd . . . . .	10
\DTMenglishshortmonthname . . . . .	11
\DTMenglishst . . . . .	10
\DTMenglishth . . . . .	10
\DTMenglishtimesep . . . . .	13
\DTMenglishweekdayname . . . . .	12
\DTMengIEdatesep . . . . .	60
\DTMengIEDatetimesep . . . . .	60
\DTMengIEDaymonthsep . . . . .	60
\DTMengIEfmtordsuffix . . . . .	61
\DTMengIEmonthyearsep . . . . .	60
\DTMengIEtimesep . . . . .	60
\DTMengIEtimezonesep . . . . .	60
\DTMengIEzonemaps . . . . .	64
\DTMengIMdatesep . . . . .	50
\DTMengIMdatetimesep . . . . .	50
\DTMengIMdaymonthsep . . . . .	50
\DTMengIMfmtordsuffix . . . . .	51
\DTMengIMmonthyearsep . . . . .	50
\DTMengIMtimesep . . . . .	51
\DTMengIMtimezonesep . . . . .	50
\DTMengIMzonemaps . . . . .	54
\DTMengJEdatesep . . . . .	46
\DTMengJEdatetimesep . . . . .	46
\DTMengJEdaymonthsep . . . . .	45
\DTMengJEfmtordsuffix . . . . .	46

\DTM{en}{JE}{month}{year}{sep} . . . . .	45	H	
\DTM{en}{JE}{times}{sep} . . . . .	46	hourminsep . . . . .	4
\DTM{en}{JE}{timezone}{sep} . . . . .	46		
\DTM{en}{JE}{zonemaps} . . . . .	49	M	
\DTM{en}{MT}{dates}{sep} . . . . .	55	mapzone . . . . .	5–7
\DTM{en}{MT}{date}{time}{sep} . . . . .	55	monthdaysep . . . . .	6
\DTM{en}{MT}{day}{month}{sep} . . . . .	55	monthlyearsep . . . . .	5
\DTM{en}{MT}{fmt}{tord}{suffix} . . . . .	56		
\DTM{en}{MT}{month}{year}{sep} . . . . .	55	O	
\DTM{en}{MT}{times}{sep} . . . . .	55	ord . . . . .	5, 7, 8
\DTM{en}{MT}{timezone}{sep} . . . . .	55		
\DTM{en}{MT}{zonemaps} . . . . .	59	S	
\DTM{en}{NZ}{dates}{sep} . . . . .	36	showdate . . . . .	4
\DTM{en}{NZ}{date}{time}{sep} . . . . .	36	showdayofmonth . . . . .	6, 7
\DTM{en}{NZ}{day}{month}{sep} . . . . .	36	showdow . . . . .	4, 6, 7, 14
\DTM{en}{NZ}{fmt}{tord}{suffix} . . . . .	37	showisoZ . . . . .	4, 6, 7
\DTM{en}{NZ}{month}{year}{sep} . . . . .	36	showseconds . . . . .	4
\DTM{en}{NZ}{times}{sep} . . . . .	36	showyear . . . . .	6, 7
\DTM{en}{NZ}{timezone}{sep} . . . . .	36	showzone . . . . .	4
\DTM{en}{NZ}{zonemaps} . . . . .	39	showzoneminutes . . . . .	4, 6, 7
\DTM{en}{US}{dates}{sep} . . . . .	21		
\DTM{en}{US}{date}{time}{sep} . . . . .	21	T	
\DTM{en}{US}{day}{year}{sep} . . . . .	21	timesep . . . . .	5, 6
\DTM{en}{US}{fmt}{tord}{suffix} . . . . .	22	timezonesep . . . . .	5, 6
\DTM{en}{US}{month}{day}{sep} . . . . .	21		
\DTM{en}{U}{times}{sep} . . . . .	21	U	
\DTM{en}{U}{timezone}{sep} . . . . .	21	useregional . . . . .	1, 3–5, 15,
\DTM{en}{US}{zonemaps} . . . . .	25		20, 25, 30, 35, 40, 44, 49, 54, 59, 64