

docshots: L^AT_EX Package that Renders T_EX Samples Next to Their PDF Snapshots*

Yegor Bugayenko
yegor256@gmail.com

2022-11-29, 0.4.0

NB! This package doesn't work on Windows! Also, you must run T_EX processor with --shell-escape option. Also, you must have pdflatex, Perl, Ghostscript, and pdffcrop installed.

1 Introduction

When you want to demonstrate to the readers of your documentation how to use certain T_EX commands, the best way would be to show exactly how the entire document will be rendered in PDF, using a subprocess that would render it (via pdf_La_TE_X, for example). To my best knowledge, there were no packages that would allow you do exactly this. That's why I created this simple package.

For example, this code:

```
\begin{docshot}
\documentclass{article}
\usepackage{xcolor}
\pagestyle{empty}
\begin{document}
Hello, {\color{orange}\LaTeX}!
\end{document}
\end{docshot}
```


is rendered as such:

Hello, L^AT_EX!

```
1 | \documentclass{article}
2 | \usepackage{xcolor}
3 | \pagestyle{empty}
4 | \begin{document}
5 |   Hello, {\color{orange}\LaTeX}!
6 | \end{document}
```

Here is a more complex example:

*The sources are in GitHub at [yegor256/docshots](https://github.com/yegor256/docshots)



```

1 \documentclass{article}
2 \usepackage{tikz}
3 \pagestyle{empty}
4 \begin{document}
5 \begin{tikzpicture}
6 \node [circle,draw] (v0) {$v_0$};
7 \node [circle,draw=orange,thick,
8     below right of=v0] (v1) {$v_1$};
9 \draw [->] (v0) -- (v1);
10 \end{tikzpicture}
11 \end{document}

```

The picture you see on the left side is rendered by a subprocess executing `pdflatex` with the `.tex` content taken from the source file. After a successful processing of \TeX sources, we use [pdfcrop](#) to trim the document.

We execute `pdflatex` with `-interaction=batchmode` and `-halt-on-error` options. This means that \TeX processing will stop at the first error. Check your \TeX log to understand what went wrong.

When you render a text instead of a single picture, it's recommended to use [geometry](#) package to change the size of the page:

“There is no sadder thing than a young pessimist, except an old pessimist” — *Mark Twain*

```

1 \documentclass{article}
2 \usepackage[paperwidth=2in,
3     paperheight=2.3in]{geometry}
4 \begin{document}
5 ‘‘There is no sadder thing than
6 a young pessimist, except an old
7 pessimist’’ --- \emph{Mark Twain}
8 \end{document}

```

1

You can also use `\pagestyle{empty}` as was done in previous docshots.

2 Package Options

`pdflatex` The default command line tool for turning `.tex` into `.pdf` is `pdflatex`. However, you can change that by using `pdflatex` package option, for example:

```

\documentclass{article}
\usepackage[pdflatex=/usr/local/bin/pdflatex]{docshot}
\begin{document}
\begin{docshot}
Hello, world!
\end{docshot}
\end{document}

```

`gs` The default location of Ghostscript is just `gs`. You can change that by using `gs` package

option, for example:

```
\usepackage[gs=/usr/bin/ghostscript]{docshot}
```

pdfcrop The default location of pdfcrop is just pdfcrop. You can change that by using pdfcrop package option, for example:

```
\usepackage[pdfcrop=/bin/pdfcrop]{docshot}
```

margin When we crop the PDF rendered, we leave a margin around the content. The default value may be changed by the package option **margin**:

```
\usepackage[margin=10]{docshot}
```

nocrop You may disable cropping with the help of **nocrop** option:

```
\usepackage[nocrop]{docshot}
```

hspace The horizontal distance between the image and its verbatim \TeX source may be configured via **hspace** package option:

```
\usepackage[hspace=1em]{docshot}
```

left The default width of the image may be changed by **left** option, while the width of **right** the verbatim \TeX source may be modified by **right** option:

```
\usepackage[left=2in,right=.5\linewidth]{docshot}
```

dtx If you use this package inside .dtx documentation, add **dtx** package option. Thanks to this option all comment symbols will be removed from line starts:

```
\usepackage[dtx]{docshot}
```

tmpdir The default location of temp files is **_docshots**. You can change this using **tmpdir** option:

```
\usepackage[tmpdir=/tmp/foo]{docshot}
```

runs By default, we run pdflatex just once for each docshot. You can change this number using the package option **runs**. This may be helpful if you need Bib \TeX processing, for example:

```
\usepackage[runs=3]{docshot}
```

small You don't have too much freedom in formatting of verbatim texts, but you can make **tiny** their font a bit smaller using **small** package option. You can also make it very small using **tiny** option:

```
\usepackage[small]{docshot}
```

log With **log** option you can make us print all possible logs to the main \TeX log. By default, we don't do this and you won't see the output of pdflatex compilation, for example. Just use it like this:

```
\usepackage[log]{docshot}
```

inputminted By default, we render the verbatim text using \VerbatimInput command. You can change that and make us use \inputminted from **minted** package instead, for example:

```
\usepackage{minted}
\setminted[java]{frame=lines,framesep=2mm}
\usepackage[inputminted=java]{docshot}
```

`\lstinputlisting` By default, we render the verbatim text using `\VerbatimInput` command. You can change that and make us use `\lstinputlisting` from [listings](#) package instead, for example:

```
\usepackage{listings}
\lstset{basicstyle=\small}
\usepackage[lstinputlisting]{docshot}
```

3 Fine-tuning Options

`\docshotOptions` By default, we render the verbatim text using `\VerbatimInput` command with no options. You can add your options using `\docshotOptions` command:

```
\docshotOptions{firstline=4}
\begin{docshot}
...
\end{docshot}
```

The options will be cleaned up by the first render of a docshot.

4 Prerequisites

`\docshotPrerequisite` If you need some files to be present next to the `.tex` snippet while it's rendered by `pdflatex`, you can use `\docshotPrerequisite` with a single mandatory argument. The argument is the name of a file you need to be copied from current directory to the temporary directory, where all snippets are rendered. The command can be used either in the body of the document or in the preamble — it doesn't matter, as long as it shows up before the docshot that needs the prerequisite. For example:

```
\documentclass{article}
\usepackage{docshot}
\docshotPrerequisite{duck.jpg}
\begin{document}
\begin{docshot}
\documentclass{article}
\usepackage{graphicx}
\pagestyle{empty}
\begin{document}
This is my favorite picture of a duck:
\includegraphics[width=2in]{duck.jpg}
\end{document}
\end{docshot}
\end{document}
```

`\docshotAfter` If you need something to happen after each `pdflatex` run of a docshot, you may use `\docshotAfter` command right before `docshot` environment. For example, you have a bibliography file that you want to be visible for all snippets and you want all of them to run [biber](#) in order to process citations:

```
\documentclass{article}
\usepackage{docshot}
\docshotPrerequisite{main.bib}
\begin{document}
```

```

\docshotAfter{biber $2}
\begin{docshot}
\documentclass{acmart}
\usepackage[natbib=true]{biblatex}
\addbibresource{main.bib}
\pagestyle{empty}
\begin{document}
    You must read the book of \citet{knuth1984}.
    \printbibliography
\end{document}
\end{docshot}
\end{document}

```

The script you specify in the first argument of `\docshotAfter` will get three arguments when it runs:

\$1 the cycle of pdflatex processing (1, 2, ...),
\$2 the hash of the snippet,
\$3 the name of the .tex file.

\$2 is basically equals to \$1 with an attached .tex suffix. `\docshotAfter` applies only to the first docshot environment that goes after it! You must specify `\docshotAfter` before each docshot where you want such post-processing to happen.

5 Implementation

First, we include a few packages:

```

1 \RequirePackage{iexec}
2 \RequirePackage{fancyvrb}
3 \RequirePackage{xcolor}
4 \RequirePackage{graphicx}
5 \RequirePackage{tikz}

```

Then, we process package options:

```

6 \RequirePackage{pgfopts}
7 \RequirePackage{ifluatex}
8 \RequirePackage{ifxetex}
9 \def\docshots@log{}
10 \pgfkeys{
11   /docshots/.cd,
12   dtx/.store in=\docshots@dtx,
13   log/.code=\def\docshots@log{\log},
14   nocrop/.code=\def\docshots@nocrop{},
15   lstinputlisting/.store in=\docshots@lstinputlisting,
16   inputminted/.store in=\docshots@inputminted,
17   tmpdir/.store in=\docshots@tmpdir,
18   tmpdir/.default=_docshots@ifxetex-xe\else\ifluatex-lua\fi\fi,
19   small/.store in=\docshots@small,
20   tiny/.store in=\docshots@tiny,
21   runs/.store in=\docshots@runs,
22   runs/.default=1,
23   pdflatex/.store in=\docshots@pdflatex,
24   pdflatex/.default=pdflatex,

```

```

25 gs/.store in=\docshots@gs,
26 gs/.default=gs,
27 pdfcrop/.store in=\docshots@pdfcrop,
28 pdfcrop/.default=pdfcrop,
29 margin/.store in=\docshots@margin,
30 margin/.default=5,
31 hspace/.store in=\docshots@hspace,
32 hspace/.default=.05\linewidth,
33 left/.store in=\docshots@left,
34 left/.default=.3\linewidth,
35 right/.store in=\docshots@right,
36 right/.default=.55\linewidth,
37 tmpdir,pdflatex,gs, pdfcrop,margin,hspace, left,right,runs
38 }
39 \ProcessPgfOptions{/docshots}

```

Then, we print the version of `pdflatex` to \TeX log:

```
40 \iexec[\docshots@log,quiet]{"\docshots@pdflatex" --version}%

```

Then, we print the version of `pdfcrop` to \TeX log:

```

41 \ifdef{\docshots@nocrop}{\else{%
42 \iexec[\docshots@log,quiet]{"\docshots@pdfcrop" --version}%
43 \fi}%

```

Then, we print the version of `ghostscript` to \TeX log:

```
44 \iexec[\docshots@log,quiet]{"\docshots@gs" --version}%

```

Then, we make a directory where all temporary files will be kept:

```
45 \iexec[null]{mkdir -p "\docshots@tmpdir/\jobname"}%
```

`\docshots@mdfive` Then, we define a command for MD5 hash calculating of a file:

```

46 \RequirePackage{pdftexcmds}
47 \makeatletter\newcommand\docshots@mdfive[1]{\pdf@filemdfivesum{\#1}}\makeatother

```

`docshot` Then, we define `docshot` environment:

```

48 \makeatletter\newenvironment{docshot}{%
49 {\VerbatimEnvironment\begin{VerbatimOut}{%
50 {\docshots@tmpdir/\jobname/verbatim.tex}}%
51 \end{VerbatimOut}}%

```

If we are in `dtx` mode, leading percent characters must be removed:

```

52 \ifdef{\docshots@dtx}{%
53 \iexec[null]{perl -i -0777pe "s/(\\n|^)\\x{25}\\s?//g"%
54 \docshots@tmpdir/\jobname/verbatim.tex}%
55 \fi}%

```

We calculate MD5 hashsum of the file content:

```
56 \def\hash{\docshots@mdfive{\docshots@tmpdir/\jobname/verbatim.tex}}%
```

If the PDF with the required name already exists, we ignore this step. Otherwise, we copy `verbatim.tex` into new file and run `pdflatex`:

```

57 \IfFileExists{\docshots@tmpdir/\jobname/\hash.pdf}{%
58 {\message{\docshots: Won't render,%
59 the PDF '\docshots@tmpdir/\jobname/\hash.pdf' already exists^^J}}%
60 {\iexec[\docshots@log,quiet]{cp "\docshots@tmpdir/\jobname/verbatim.tex"%
61 "\docshots@tmpdir/\jobname/\hash.tex"}%}

```

```

62  \message{docshots: rendering at line no. \the\inputlineno^^J}%
63  \foreach \n in {1,...,\docshots@runs}{%
64    \iexec[\docshots@log,
65      stdout=\docshots@tmpdir/\jobname/\hash.stdout,
66      exit=\docshots@tmpdir/\jobname/\hash.ret,
67      quiet,trace]{cd "\docshots@tmpdir/\jobname" &&
68      "\docshots@pdflatex"
69      -interaction=errorstopmode
70      -halt-on-error
71      -shell-escape
72      \hash.tex}%
73  \ifnum\n=1\else%
74    \message{docshots: pdflatex run no.\n^^J}%
75  \fi%
76  \IfFileExists{\docshots@tmpdir/\jobname/after.sh}
77    {\iexec[\docshots@log,quiet]{chmod a+x
78      "\docshots@tmpdir/\jobname/after.sh"}
79    \iexec[\docshots@log,quiet]{cd "\docshots@tmpdir/\jobname" &&
80      ./after.sh \n\space \hash\space \hash.tex}%
81  }{}%

```

Here we delete `after.sh` which may exist here after the last compilation of `pdflatex`:

```
82  \iexec[\docshots@log,quiet]{rm -f "\docshots@tmpdir/\jobname/after.sh"}
```

If a cropped version of the PDF with the required name already exists, we ignore this step. Otherwise, we ask `pdfcrop` to crop the PDF:

```

83  \IfFileExists{\docshots@tmpdir/\jobname/\hash.crop.pdf}
84    {\message{docshots: Won't pdfcrop,
85      the PDF '\docshots@tmpdir/\jobname/\hash.crop.pdf'
86      already exists^^J}%
87    \ifdef{\docshots@nocrop}
88      \iexec[\docshots@log,quiet]{cp
89        "\docshots@tmpdir/\jobname/\hash.pdf"
90        "\docshots@tmpdir/\jobname/\hash.crop.pdf"}%
91    \else%
92      \iexec[\docshots@log,quiet]{"\docshots@pdfcrop"
93        --margins 0
94        "\docshots@tmpdir/\jobname/\hash.pdf"
95        "\docshots@tmpdir/\jobname/\hash.crop.pdf"}%
96    \fi}%

```

We configure `fancyvrb`:

```

97  \fvset{numbers=left,numbersep=3pt}%
98  \fvset{frame=leftline,framerule=.2pt,rulecolor=\color{gray}}%
99  \fvset{samepage=true}%
100 \fvset{baselinestretch=1}%
101 \ifdef{\docshots@small}%
102   \fvset{fontsize=\small}%
103 \fi%
104 \ifdef{\docshots@tiny}%
105   \fvset{fontsize=\scriptsize}%
106 \fi%

```

Finally, we render the two-column content:

```

107 \begingroup%
108 \par%

```

```

109 \tikz [baseline=(a.north)]
110   \node (a) [draw=gray,inner sep=\docshots@margin,
111   line width=.2pt]
112   {\includegraphics [width=\docshots@left]
113   {\docshots@tmpdir/\jobname/\hash.crop.pdf}};%
114 \hspace{\docshots@hskip}%
115 \begin{minipage}[t]{\docshots@right}%
116 \vspace{0pt}%
117 \ifdefined\docshots@lstinputlisting%
118   \expandafter\lstinputlisting\expandafter[\docshots@opts]
119   {\docshots@tmpdir/\jobname/\hash.tex}%
120 \else\ifdefined\docshots@inputminted%
121   \expandafter\inputminted\expandafter[\docshots@opts]
122   {\docshots@inputminted}%
123   {\docshots@tmpdir/\jobname/\hash.tex}%
124 \else%
125   \expandafter\VerbatimInput\expandafter[\docshots@opts]
126   {\docshots@tmpdir/\jobname/\hash.tex}%
127 \fi\fi%
128 \vspace{0pt}%
129 \end{minipage}%
130 \par%
131 \endgroup%
132 \docshotOptions{}%
133 }\makeatother

```

`\docshotPrerequisite` Then, we define `\docshotPrerequisite` command:

```

134 \makeatletter\newcommand\docshotPrerequisite[1]{
135   \iexec[\docshots@log,quiet]{cp #1 "\docshots@tmpdir/\jobname"}%
136   \message{\docshots: File '#1' copied to
137   '\docshots@tmpdir/\jobname/#1'^^J}%
138 }\makeatother

```

`\docshotAfter` Then, we define `\docshotAfter` command:

```

139 \makeatletter\newcommand\docshotAfter[1]{
140   \iexec[\docshots@log,quiet]{/bin/echo -n '\detokenize{\#1}'%
141   > "\docshots@tmpdir/\jobname/after.sh"}%
142   \message{\docshots: File
143   '\docshots@tmpdir/\jobname/after.sh' created^^J}%
144 }\makeatother

```

`\docshotOptions` Finally, we define `\docshotOptions` command:

```

145 \makeatletter
146 \gdef\docshots@opts{}%
147 \newcommand\docshotOptions[1]{%
148   \gdef\docshots@opts{\#1}%
149 }\makeatother

```

Change History

0.0.1	General: Initial version	5	0.1.1	\docshots@mdfive: New supplementary command added to calculate MD5 sum of a file.	6
0.0.3	General: The command is added to enable copying of supplementary files into docshots snippets processing directory.	4	0.2.0	General: New package option "nocrop" added to allow disabling of "pdfcrop" execution.	5
0.0.4	General: Package options "lstinputlisting" and "inputminted" introduced to enable printing of verbatim text either via listings or minted packages.	5	0.3.0	\docshotOptions: New command introduced to help specify custom options for verbatim environments.	8
0.0.5	General: Package option "log" added, which enables detailed logging via exec. By default, there is no logging at all.	5	0.3.1	docshot: A bug fixed, now handling of leading percentage symbols is done right.	6
0.1.0	docshot: The output is saved to a hash-named file, for better uniqueness of temporary files.	6	0.4.0	docshot: Now, \TeX output has a log message with the number of the line in the source file, which we render.	6

Index

Numbers written in italic refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

B	E	L
\begin 49, 115	83, 85, 89, 90, 94, 95, 113, 119, 123, 126, 135, 137, 141, 143	\ linewidth 32, 34, 36 \lstinputlisting .. 118
C	F	M
\color 98	\end 51, 129 \expandafter 118, 121, 125	\makeatletter 47, 48, 134, 139, 145
D	G	N
\def 9, 13, 14, 56 \detokenize 140 \docshot 48 \docshotAfter 139 \docshotOptions 132, 145 \docshotPrerequisite 134 \docshots@dtx 12, 52 \docshots@gs 25, 44 \docshots@hskip 31, 114 \docshots@inputminted 16, 120, 122 \docshots@left .. 33, 112 \docshots@log 9, 13, 40, 42, 44, 60, 64, 77, 79, 82, 88, 92, 135, 140 \docshots@lstinputlisting \iexec 40, 42, 44, 15, 117 \docshots@margin 29, 110 \docshots@mdfive . 46, 56 \docshots@nocrop .. 14, 41, 87 \docshots@opts 118, 121, 125, 146, 148 \docshots@pdfcrop 27, 42, 92 \docshots@pdflatex .. 23, 40, 68 \docshots@right .. 35, 115 \docshots@runs .. 21, 63 \docshots@small .. 19, 101 \docshots@tiny .. 20, 104 \docshots@tmpdir 17, 45, 50, 54, 56, 57, 59, 60, 61, 65, 66, 67, 76, 78, 79, 82,	\foreach 63 \fvset 97, 98, 99, 100, 102, 105 \gdef 146, 148 \hash 56, 57, 59, 61, 65, 66, 72, 80, 83, 85, 89, 90, 94, 95, 113, 119, 123, 126 \hspace 114	\newcommand 47, 134, 139, 147 \newenvironment 48 \node 110
I	J	P
\iexec 40, 42, 44, 15, 117 \ifdefined 41, 52, 87, 101, 104, 117, 120 \IfExists .. 57, 76, 83 \ifluatex 18 \ifnum 73 \ifxetex 18 \includegraphics .. 112 \inputlineno 62 \inputminted 121	\jobname 45, 50, 54, 56, 57, 59, 60, 61, 65, 66, 67, 76, 78, 79, 82, 83, 85, 89, 90, 94, 95, 113, 119, 123, 126, 135, 137, 141, 143	\par 108, 130 \pdf@filemdfivesum .. 47 \pgfkeys 10 \ProcessPgfOptions .. 39
R	S	T
\RequirePackage .. 1, 2, 3, 4, 5, 6, 7, 8, 46	\scriptsize 105 \small 102 \space 80	\the 62 \tikz 109
V		
	\VerbatimEnvironment 49 \VerbatimInput 125 \vspace 116, 128	