

THE DYNKIN DIAGRAMS PACKAGE
VERSION 3.14159265358

BEN MCKAY

CONTENTS

1. Quick introduction, 1
 2. Set options globally, 3
 3. Coxeter diagrams, 3
 4. Satake diagrams, 4
 5. How to fold, 6
 6. Labels for the roots, 7
 7. Label subscripts, 10
 8. Height and depth of labels, 12
 9. Text style for the labels, 12
 10. Bracing roots, 13
 11. Style, 17
 12. Suppress or reverse arrows, 19
 13. Backwards and upside down, 19
 14. Drawing on top of a Dynkin diagram, 20
 15. Mark lists, 21
 16. Indefinite edges, 22
 17. Root ordering, 25
 18. Parabolic subgroups, 26
 19. Extended Dynkin diagrams, 27
 20. Affine twisted and untwisted Dynkin diagrams, 28
 21. Extended Coxeter diagrams, 29
 22. Kac style, 30
 23. Ceref style, 32
 24. More on folded Dynkin diagrams, 33
 25. Typesetting mathematical names of Dynkin diagrams, 39
 26. Connecting Dynkin diagrams, 39
 27. Other examples, 41
 28. Example: the complex simple Lie algebras, 50
 29. An example of Mikhail Borovoi, 52
 30. Syntax, 52
 31. Options, 52
- References, 56

1. QUICK INTRODUCTION

Load the Dynkin diagram package (see options below)

```
\documentclass{amsart}
\usepackage{dynkin-diagrams}
\begin{document}
The Dynkin diagram of  $(B_3)$  is \dynkin B3.
\end{document}
```

Invoke it

The Dynkin diagram of (B_3) is \dynkin B3.

The Dynkin diagram of B_3 is $\bullet \text{---} \bullet \Rightarrow \bullet$.

Inside a TikZ statement

The Dynkin diagram of (B_3) is
`\tikz \dynkin B3;`

The Dynkin diagram of B_3 is $\bullet \text{---} \bullet \Rightarrow \bullet$

Inside a Dynkin diagram environment

The Dynkin diagram of (B_3) is
`\begin{dynkinDiagram}B3`
`\draw[very thick,red] (root 1) to [out=-45, in=-135] (root 3);`
`\end{dynkinDiagram}`

The Dynkin diagram of B_3 is $\bullet \text{---} \bullet \Rightarrow \bullet$

Inside a TikZ environment

Baseline controls vertical alignment:
the Dynkin diagram of (B_3) is
`\begin{tikzpicture}[baseline=(origin.base)]`
`\dynkin B3`
`\draw[very thick,red] (root 1) to [out=-45, in=-135] (root 3);`
`\end{tikzpicture}`

Baseline controls vertical alignment: the Dynkin diagram of B_3 is $\bullet \text{---} \bullet \Rightarrow \bullet$

In a TikZ picture, you might need to kill the default vertical shift (needed to allow inline Dynkin diagrams):

Inside TikZ pictures

```
\begin{tikzpicture}
\draw (0,0) -- (.5,1) -- (1,0);
\dynkin[vertical shift=0,edge length=1cm]G2
\end{tikzpicture}
```



Indefinite rank Dynkin diagrams

```
\dynkin B{}
```



Table 1: The Dynkin diagrams of the reduced simple root systems [3] pp. 265–290, plates I–IX

A_n		<code>\dynkin A{}</code>
C_n		<code>\dynkin C{}</code>
D_n		<code>\dynkin D{}</code>
E_6		<code>\dynkin E6</code>
E_7		<code>\dynkin E7</code>
E_8		<code>\dynkin E8</code>
F_4		<code>\dynkin F4</code>
G_2		<code>\dynkin G2</code>

2. SET OPTIONS GLOBALLY

Most options set globally ...

```
\pgfkeys{/Dynkin diagram,edge length=.5cm,fold radius=.5cm,
indefinite edge/.style={
draw=black,fill=white,thin,densely dashed}}
```

You can also pass options to the package in `\usepackage`. *Danger*: spaces in option names are replaced with hyphens: `edge length=1cm` is `edge-length=1cm` as a global option; moreover you should drop the extension `/.style` on any option with spaces in its name (but not otherwise). For example,

... or pass global options to the package

```
\usepackage[
  ordering=Kac,
  edge/.style=blue,
  indefinite-edge={draw=green,fill=white,densely dashed},
  indefinite-edge-ratio=5,
  mark=o,
  root-radius=.06cm]
{dynkin-diagrams}
```

3. COXETER DIAGRAMS

Coxeter diagram option

```
\dynkin[Coxeter]{F}{4}
```



gonality option for G_2 and I_n Coxeter diagrams

```
\(G_2=\dynkin[Coxeter,gonality=n]G2\), \
\ (I_n=\dynkin[Coxeter,gonality=n]I{\})
```

$G_2 = \overset{n}{\bullet}\bullet$, $I_n = \overset{n}{\bullet}\bullet$

Table 2: The Coxeter diagrams of the simple reflection groups

A_n		<code>\dynkin[Coxeter]A{}</code>
B_n		<code>\dynkin[Coxeter]B{}</code>
C_n		<code>\dynkin[Coxeter]C{}</code>
E_6		<code>\dynkin[Coxeter]E6</code>
E_7		<code>\dynkin[Coxeter]E7</code>
E_8		<code>\dynkin[Coxeter]E8</code>
F_4		<code>\dynkin[Coxeter]F4</code>
G_2		<code>\dynkin[Coxeter,gonality=n]G2</code>
H_3		<code>\dynkin[Coxeter]H3</code>
H_4		<code>\dynkin[Coxeter]H4</code>

continued ...

Table 2: ... continued

I_n		<code>\dynkin[Coxeter,gonality=n]I{}</code>
-------	--	---

4. SATAKE DIAGRAMS

Satake diagrams use the standard name instead of a rank

`\(A_{IIIb}=\dynkin A{IIIb}\)`

$A_{IIIb} =$

We use a solid gray bar to denote the folding of a Dynkin diagram, rather than the usual double arrow, since the diagrams turn out simpler and easier to read.

Table 3: The Satake diagrams of the real simple Lie algebras [13] p. 532–534

A_I		<code>\dynkin AI</code>
A_{II}		<code>\dynkin A{II}</code>
A_{IIIa}		<code>\dynkin A{IIIa}</code>
A_{IIIb}		<code>\dynkin A{IIIb}</code>
A_{IV}		<code>\dynkin A{IV}</code>
B_I		<code>\dynkin BI</code>
B_{II}		<code>\dynkin B{II}</code>
C_I		<code>\dynkin CI</code>
C_{IIa}		<code>\dynkin C{IIa}</code>
C_{IIb}		<code>\dynkin C{IIb}</code>
D_{Ia}		<code>\dynkin D{Ia}</code>
D_{Ib}		<code>\dynkin D{Ib}</code>
D_{Ic}		<code>\dynkin D{Ic}</code>
D_{II}		<code>\dynkin D{II}</code>
D_{IIIa}		<code>\dynkin D{IIIa}</code>

continued ...

Table 3: ...continued

D_{IIIb}		<code>\dynkin D{IIIb}</code>
E_I		<code>\dynkin EI</code>
E_{II}		<code>\dynkin E{II}</code>
E_{III}		<code>\dynkin E{III}</code>
E_{IV}		<code>\dynkin E{IV}</code>
E_V		<code>\dynkin EV</code>
E_{VI}		<code>\dynkin E{VI}</code>
E_{VII}		<code>\dynkin E{VII}</code>
E_{VIII}		<code>\dynkin E{VIII}</code>
E_{IX}		<code>\dynkin E{IX}</code>
F_I		<code>\dynkin FI</code>
F_{II}		<code>\dynkin F{II}</code>
G_I		<code>\dynkin GI</code>


5. HOW TO FOLD

If you don't like the solid gray "folding bar", most people use arrows. Here is E_{II}

```


\newcommand{\invol}[2]{\draw[latex-latex] (root #1) to
[out=-60,in=-120] node[midway,below]{\sigma} (root #2);}
\begin{dynkinDiagram}[edge length=.75cm,labels*={1,...,6}]E6
\invol 16\invol 35
\end{dynkinDiagram}

```




The double arrows for A_{IIIa} are big

```
\newcommand{\invol}[2]{\draw[latex-latex] (root #1) to
[out=-60,in=-120] node[midway,below]{\sigma} (root #2);}
\begin{dynkinDiagram}[edge length=.75cm]{A}{oo.o**.oo}
\invol 1{10}\invol 29\invol 38\invol 47\invol 56
\end{dynkinDiagram}
```




If you don't like the solid gray "folding bar", most people use arrows ...

```
\tikzset{/Dynkin diagram/fold style/.style={stealth-stealth,thick,
shorten <=1mm,shorten >=1mm,}}
\dynkin[ply=3,edge length=.75cm]D4
\begin{dynkinDiagram}[ply=4]D[1]%
{****.*****.*****}
\dynkinFold 1{13}
\dynkinFold[bend right=90] 0{14}
\end{dynkinDiagram}
```



... but you could try springs pulling roots together


```
\tikzset{/Dynkin diagram/fold style/.style=
{decorate,decoration={name=coil,aspect=0.5,
segment length=1mm,amplitude=.6mm}}}
\dynkin[ply=3,edge length=.75cm]D4
\begin{dynkinDiagram}[ply=4]D[1]%
{****.*****.*****}
\dynkinFold 1{13}
\dynkinFold[bend right=90] 0{14}
\end{dynkinDiagram}
```



6. LABELS FOR THE ROOTS


Make a macro to assign labels to roots

```
\dynkin[label,label macro/.code={\alpha_{\drlap{#1}}},edge
length=.75cm]D5
```



Labelling several roots

```
\dynkin[labels={,2,...,5,,7},label macro/.code={\alpha_{\drlap{#1}}}]A7
```




The foreach notation I

```
\dynkin[labels={1,3,...,7},]A9
```




The foreach notation II

```
\dynkin[labels={,\alpha_2,\alpha_...,,\alpha_7},]A7
```



The foreach notation III

```
\dynkin[label macro/.code={\beta_{\drlap{#1}}},labels={,2,...,7},]A7
```



Label the roots individually by root number

```
\dynkin[label]B3
```



Label a single root

```
\begin{dynkinDiagram}B3
\dynkinLabelRoot 2{\alpha_{\drlap{2}}}
\end{dynkinDiagram}
```




Access root labels via TikZ

```
\begin{dynkinDiagram}B3
\node[below] at (root 2) {\(\alpha_{\drlap{2}}\)};
\end{dynkinDiagram}
```




Commands to label several roots

```
\begin{dynkinDiagram}A7
\dynkinLabelRoots{\alpha_2,\alpha_3,\alpha_4,\alpha_5,,\alpha_7}
\end{dynkinDiagram}
```




The labels have default locations, mostly below roots

```
\dynkin[edge length=.75cm,labels={1,2,3}]E8
```




The starred form flips labels to alternate locations, mostly above roots

```
\dynkin[edge length=.75cm,labels*={1,2,3}]E8
```




Labelling several roots and alternates

```
\dynkin[%
label macro/.code={\alpha_{\drlap{#1}}},
label macro*/.code={\gamma_{\drlap{#1}}},
labels={,2,...,5,,7},
labels*={1,3,4,5,6}]A7
```



Commands to label several roots

```
\begin{dynkinDiagram}A7
\dynkinLabelRoots{,\alpha_2,\alpha_3,\alpha_4,\alpha_5,,\alpha_7}
\dynkinLabelRoots*{a,b,c,d,e,f,g}
\end{dynkinDiagram}
```




7. LABEL SUBSCRIPTS

Note the slight improvement that `\drlap` makes: the labels are centered on the middle of the letter α , ignoring the space taken up by the subscripts, using the `mathtools` command `\mathrlap`, but only for labels which are *not* placed to the left or right of a root.

Label subscript spacing

```
\dynkin[label,label macro/.code={\alpha_{#1}},
edge length=.75cm]D{15}
\par\noindent{%
\dynkin[label,label macro/.code={\alpha_{\drlap{#1}}},
edge length=.75cm]D{15}
```




Label subscript spacing

```

\dynkin[label,label macro/.code={\alpha_{#1}},
  edge length=.75cm]E8
\dynkin[label,label macro/.code={\alpha_{#1}},backwards,
  edge length=.75cm]E8
\par\noindent{}%
\dynkin[label,label macro/.code={\alpha_{\mathrlap{#1}}},
  edge length=.75cm]E8
\dynkin[label,label macro/.code={\alpha_{\mathrlap{#1}}},backwards,
  edge length=.75cm]E8
\par\noindent{}%
\dynkin[label,label macro/.code={\alpha_{\drlap{#1}}},
  edge length=.75cm]E8
\dynkin[label,label macro/.code={\alpha_{\drlap{#1}}},backwards,
  edge length=.75cm]E8

```




8. HEIGHT AND DEPTH OF LABELS

Labels are set with default maximum height the height of the character b , and default maximum depth the depth of the character g . To change these, set label height and label depth:

Change height and depth of characters

```
\dynkin[labels={a,b,c,d},label height=d,label depth=d]F4
\dynkin[labels*={a,b,c,d},label height=d,label depth=d]F4
\dynkin[%
label macro/.code={\alpha_{\drlap{#1}}},
label macro*/.code={\gamma_{\drlap{#1}}},
label height=${\alpha_1},
label depth=${\alpha_1},
labels={,2,...,5,,7},
labels*={1,3,4,5,6}]A7
\dynkin[labels={A,B,C,D},label height=${A},label depth=${A}]F4
\dynkin[labels={a^1,b^2,c^3,d^4},label height=${X^X}]F4
```



9. TEXT STYLE FOR THE LABELS

Use a text style: big and blue

```
\begin{dynkinDiagram}[text style={scale=1.2,blue},
edge length=.75cm,
labels={1,2,n-1,n},
label macro/.code={\alpha_{\drlap{#1}}}
]A{}
\end{dynkinDiagram}
```



Use a text style; font selection is in the label macro


```
\begin{dynkinDiagram}[text style={scale=1.2,blue},
edge length=.75cm,
labels={1,2,n-1,n},
label macro/.code={\mathbb{A}_{\drlap{#1}}}A{}
\end{dynkinDiagram}
```



10. BRACING ROOTS


Bracing roots

```
\begin{dynkinDiagram}A{*.x*.*}
\dynkinBrace[p]12
\dynkinBrace[q]45
\end{dynkinDiagram}
```



Bracing roots, and a starred form

```
\begin{dynkinDiagram}A{10}
\dynkinBrace[\text{Roots 2 to 9}]29
\dynkinBrace*[\text{Roots 3 to 8}]38
\end{dynkinDiagram}
```




Bracing roots

```
\newcommand\circleRoot[1]{\draw (root #1) circle (3pt);}
\begin{dynkinDiagram}A{**.*.*.*.*.*.*.*}
\circleRoot 4\circleRoot 7\circleRoot 10\circleRoot 13
\dynkinBrace[y-1]13
\dynkinBrace[z-1]56
\dynkinBrace[t-1]{11}{12}
\dynkinBrace[x-1]{14}{16}
\end{dynkinDiagram}
```




Table 4: Dynkin diagrams from Euler products [17]




continued ...

Table 4: ... continued



continued ...

Table 4: ... continued



```

\tikzset{/Dynkin diagram,ordering=Dynkin,label macro/.code={\alpha_{\drlap{#1}}}}
\newcounter{EPNo}
\setcounter{EPNo}{0}
\NewDocumentCommand\EP{smmmm}%
{%
\stepcounter{EPNo}\roman{EPNo}. &%
\def\eL{.6cm}%
\IfStrEqCase{#2}%
{%
D{\gdef\eL{1cm}}%
E{\gdef\eL{.75cm}}%
F{\gdef\eL{.35cm}}%
G{\gdef\eL{.35cm}}%
}%
\IfBooleanTF{#1}%
{\dynkin[edge length=\eL,backwards,labels*={#4},labels={#5}]{#2}{#3}}
{\dynkin[edge length=\eL,labels*={#4},labels={#5}]{#2}{#3}}
\\
}%
\renewcommand*\do[1]{\EP#1}%
\begin{longtable}{MM}
\caption{Dynkin diagrams from Euler products \cite{Langlands:1967}}\\
\endfirsthead
\caption{\dots continued}\\
\endhead
\multicolumn{2}{c}{continued \dots}\\
\endfoot
\endlastfoot
\docsvlist{
A{***.}*}{1,1,1,1,1}{1,2,n-1,n},
A{***.}*}{1,1,1,1,1}{1,2,n-1,n},
A{**.***.}*}{1,1,1,1,1}{1,2,m-1,,m,n},
B{**.***}{2,2,2,2,1}{1,2,n-1,n},
*B{***.}*}{2,2,2,2,1}{n,n-1,2,1,},
C{**.***}{1,1,1,1,2}{1,2,n-1,},
*C{***.}*}{1,1,1,1,2}{n,n-1,2,1,},
D{**.****}{1,1,1,1,1,1}{1,2,n-2,n-1,n},
D{**.****}{1,1,1,1,1,1}{1,2,n-2,n-1,n},
E6{1,1,1,1,1,1}{1,...,5},
*E7{1,1,1,1,1,1,1}{6,...,1},
E7{1,1,1,1,1,1,1}{1,...,6},

```

```

*E8{1,1,1,1,1,1,1,1}{7,...,1},
E8{1,1,1,1,1,1,1,1}{1,...,7},
G2{1,3}{1},
G2{1,3}{1},
B{**.*.**}{2,2,2,2,1}{1,2,n-1,n},
F4{1,1,2,2}{3,2,1},
C3{1,1,2}{2,1},
C{**.**}{1,1,1,2}{1,n-2,n-1,n},
*B3{2,2,1}{1,2},
F4{1,1,2,2}{1,2,3},
D{**.**}{1,1,1,1,1}{1,2,n-2,n-2,n,n},
E6{1,1,1,1,1,1}{1,2,3,4,5},
E6{1,1,1,1,1,1}{1,2,3,5,4},
*E7{1,1,1,1,1,1,1}{5,...,1,6},
*E7{1,1,1,1,1,1,1}{6,4,3,2,1,5},
*E8{1,1,1,1,1,1,1,1}{6,...,1,7},
*E8{1,1,1,1,1,1,1,1}{7,5,4,3,2,1,6},
*E7{1,1,1,1,1,1,1}{5,...,1,6},
*E7{1,1,1,1,1,1,1}{1,...,5,6},
*E8{1,1,1,1,1,1,1,1}{6,...,1,7}
\end{longtable}

```

11. STYLE

Colours

```

\dynkin[
  edge/.style={blue!50,thick},
  */.style=blue!50!red,
  arrow style=red]{F}{4}

```



Arrow shapes

```

\dynkin[arrow shape/.style={-{Stealth[blue,width=3mm]}}]{F4}

```



Edge lengths

```

The Dynkin diagram of  $(A_3)$  is \dynkin[edge length=1.2]A3

```


The Dynkin diagram of A_3 is 

Root marks

```

\dynkin E8
\dynkin[mark=*]E8
\dynkin[mark=o]E8
\dynkin[mark=O]E8
\dynkin[mark=t]E8
\dynkin[mark=x]E8
\dynkin[mark=X]E8

```



At the moment, you can only use:

- * • solid dot
- o ○ hollow circle
- O ⊙ double hollow circle
- t ⊗ tensor root
- x × crossed root
- X × thickly crossed root

Mark styles

The parabolic subgroup $(E_{8,124})$ is
`\dynkin[parabolic=124,x/.style={brown,very thick}]E8`

The parabolic subgroup $E_{8,124}$ is

Sizes of root marks

$(A_{3,3})$ with big root marks is `\dynkin[root radius=.08cm,parabolic=3]A3`

$A_{3,3}$ with big root marks is

12. SUPPRESS OR REVERSE ARROWS

Some diagrams have double or triple edges

```
\dynkin F4
\dynkin G2
```



Suppress arrows

```
\dynkin[arrows=false]F4
\dynkin[arrows=false]G2
```



Reverse arrows

```
\dynkin[reverse arrows]F4
\dynkin[reverse arrows]G2
```



13. BACKWARDS AND UPSIDE DOWN

Default

```
\dynkin E8
\dynkin F4
\dynkin G2
```



Backwards

```
\dynkin[backwards]E8
\dynkin[backwards]F4
\dynkin[backwards]G2
```



Reverse arrows

```
\dynkin[reverse arrows]F4
\dynkin[reverse arrows]G2
```




Backwards, reverse arrows

```
\dynkin[backwards,reverse arrows]F4
\dynkin[backwards,reverse arrows]G2
```



Backwards versus upside down

```
\dynkin[label]E8
\dynkin[label,backwards]E8
\dynkin[label,upside down]E8
\dynkin[label,backwards,upside down]E8
```



14. DRAWING ON TOP OF A DYNKIN DIAGRAM


TikZ can access the roots themselves

```
\begin{dynkinDiagram}A4
  \fill[white,draw=black] (root 2) circle (.15cm);
  \fill[white,draw=black] (root 2) circle (.1cm);
  \draw[black] (root 2) circle (.05cm);
\end{dynkinDiagram}
```




Draw curves between the roots

```
\begin{dynkinDiagram}[label]E8
  \draw[very thick, black!50,-latex]
    (root 3.south) to [out=-45, in=-135] (root 6.south);
\end{dynkinDiagram}
```



Change marks

```
\begin{dynkinDiagram}[mark=o,label]E8
  \dynkinRootMark{*}5
  \dynkinRootMark{*}8
\end{dynkinDiagram}
```



15. MARK LISTS

The package allows a list of root marks instead of a rank:

A mark list

```
\dynkin E{oo**ttxx}
```



The mark list `oo**ttxx` has one mark for each root: `o`, `o`, `*`, `*`, `t`, `x`, `x`. Roots are listed in the current default ordering. (Careful: in an affine root system, a mark list will *not* contain a mark for root zero.)

If you need to repeat a mark, you can give a *single digit* positive integer to indicate how many times to repeat it.

A mark list with repetitions

```
\dynkin A{x4o3t4}
```



Table 5: Classical Lie superalgebras [10]. We need a slightly larger root radius parameter to distinguish the tensor product symbols from the solid dots.

	<code>\tikzset{/Dynkin diagram,root radius=.07cm}</code>	
A_{mn}		<code>\dynkin A{o3.oto.oo}</code>
B_{mn}		<code>\dynkin B{o3.oto.oo}</code>
B_{0n}		<code>\dynkin B{o3.o3.o*}</code>
C_n		<code>\dynkin C{too.oto.oo}</code>
D_{mn}		<code>\dynkin D{o3.oto.o4}</code>
$D_{21\alpha}$		<code>\dynkin A{oto}</code>
F_4		<code>\dynkin F{ooot}</code>
G_3		<code>\dynkin[extended,affine mark=t,reverse arrows]G2</code>

Table 6: Classical Lie superalgebras [10]. Here we see the problem with using the default root radius parameter, which is too small for tensor product symbols.

A_{mn}		<code>\dynkin A{o3.oto.oo}</code>
B_{mn}		<code>\dynkin B{o3.oto.oo}</code>
B_{0n}		<code>\dynkin B{o3.o3.o*}</code>
C_n		<code>\dynkin C{too.oto.oo}</code>
D_{mn}		<code>\dynkin D{o3.oto.o4}</code>
$D_{21\alpha}$		<code>\dynkin A{oto}</code>
F_4		<code>\dynkin F{ooot}</code>
G_3		<code>\dynkin[extended,affine mark=t,reverse arrows]G2</code>

16. INDEFINITE EDGES

An *indefinite edge* is a dashed edge between two roots, $\bullet\text{---}\bullet$ indicating that an indefinite number of roots have been omitted from the Dynkin diagram. In between any two entries in a mark list, place a period to indicate an indefinite edge:


Indefinite edges

`\dynkin D{o.o*.t.to.t}`

In certain diagrams, roots may have an edge between them even though they are not subsequent in the ordering. For such rare situations, there is an option:


Indefinite edge option

```
\dynkin[make indefinite edge={3-5},label]D5
```




Give a list of edges to become indefinite

```
\dynkin[make indefinite edge/.list={1-2,3-5},label]D5
```



Indefinite edge style

```
\dynkin[indefinite edge/.style={
  draw=black,fill=white,thin,densely dashed},
  edge length=1cm,
  make indefinite edge={3-5}]D5
```



The ratio of the lengths of indefinite edges to those of other edges

```
\dynkin[edge length = .5cm,
  indefinite edge ratio=3,
  make indefinite edge={3-5}]D5
```
















Table 7: Springer's table of indices [24], pp. 320-321, with one form of E_7 corrected

A_n		
A_n		
B_n		
C_n		
D_n		
E_6		<code>\dynkin E{*oooo*}</code>
E_6		<code>\dynkin E{o*o*oo}</code>
E_6		<code>\dynkin E{o*oooo}</code>
E_6		<code>\dynkin E{**ooo*}</code>
E_7		<code>\dynkin E{*oooooo}</code>
E_7		<code>\dynkin E{ooooo*o}</code>
E_7		<code>\dynkin E{oooooo*}</code>
E_7		<code>\dynkin E{*oooo*o}</code>
E_7		<code>\dynkin E{*oooo**}</code>
E_7		<code>\dynkin E{*o**o*o}</code>
E_8		<code>\dynkin E{*ooooooo}</code>
E_8		<code>\dynkin E{ooooooo*}</code>
E_8		<code>\dynkin E{*oooooo*}</code>
E_8		<code>\dynkin E{oooooo**}</code>
E_8		<code>\dynkin E{*oooo***}</code>
F_4		<code>\dynkin F{ooo*}</code>
D_4		<code>\dynkin D{o*oo}</code>

17. ROOT ORDERING

Root ordering

```

\dynkin[label,ordering=Adams]E6
\dynkin[label,ordering=Bourbaki]E6
\dynkin[label,ordering=Carter]E6
\dynkin[label,ordering=Dynkin]E6
\dynkin[label,ordering=Kac]E6
    
```

Default is Bourbaki. Sources are Adams [1] p. 56–57, Bourbaki [3] p. pp. 265–290 plates I-IX, Carter [5] p. 540–609, Dynkin [8], Kac [15] p. 43.

	Adams	Bourbaki	Carter	Dynkin	Kac
E_6					
E_7					
E_8					
F_4					
G_2					

The marks are set down in order according to the current root ordering:

```

\dynkin[label]E{*otxXOt*}
\dynkin[label,ordering=Carter]E{*otxXOt*}
\dynkin[label,ordering=Kac]E{*otxXOt*}
    
```

Convert between orderings

```

\newcount\r
\dynkinOrder E8.Carter::6->Bourbaki.{\r}
    
```

In (E_8) , root 6 in Carter's ordering is root $\text{\the\rr{}}$ in Bourbaki's ordering.

In E_8 , root 6 in Carter's ordering is root 2 in Bourbaki's ordering.

18. PARABOLIC SUBGROUPS

Each set of roots is assigned a number, with each binary digit zero or one to say whether the corresponding root is crossed or not:

The flag variety of pointed lines in projective 3-space is associated to the Dynkin diagram $\text{\dynkin[parabolic=3]A3}$.

The flag variety of pointed lines in projective 3-space is associated to the Dynkin diagram $\times \rightarrow \bullet$.

Table 9: The Hermitian symmetric spaces

A_n		Grassmannian of k -planes in \mathbb{C}^{n+1}
B_n		$(2n - 1)$ -dimensional hyperquadric, i.e. the variety of null lines in \mathbb{C}^{2n+1}
C_n		space of Lagrangian n -planes in \mathbb{C}^{2n}
D_n		$(2n - 2)$ -dimensional hyperquadric, i.e. the variety of null lines in \mathbb{C}^{2n}
D_n		one component of the variety of maximal dimension null subspaces of \mathbb{C}^{2n}
D_n		the other component
E_6		complexified octave projective plane
E_6		its dual plane
E_7		the space of null octave 3-planes in octave 6-space

```

\NewDocumentCommand\HSS{mommm}
{#1&\IfNoValueTF{#2}{\dynkin{#3}{#4}}{\dynkin[parabolic=#2]{#3}{#4}}&#5\}
\renewcommand*{\arraystretch}{1.5}
\begin{longtable}
{>{\columncolor[gray]{.9}}>$1<$>{\columncolor[gray]{.9}}>$1<$>{\columncolor[gray]{.9}}1}
\caption{The Hermitian symmetric spaces}\endfirsthead
\caption{\dots continued}\ \endhead
\caption{continued \dots}\ \endfoot
\endlastfoot
\HSS{A_n}A{**.*x.**}{Grassmannian of $k$-planes in $\mathbb{C}\{n+1\}$}
\HSS{B_n}[1]B{\{$(2n-1)$-dimensional hyperquadric, i.e. the variety of null lines in $\mathbb{C}\{2n+1\}$}
\HSS{C_n}[16]C{\{space of Lagrangian $n$-planes in $\mathbb{C}\{2n\}$}

```

```

\HSS{D_n}[1]D{\$(2n-2)$-dimensional hyperquadric, i.e. the variety of null lines in $\mathbb{C}^{2n}$}
\HSS{D_n}[32]D{\{one component of the variety of maximal dimension null subspaces of $\mathbb{C}^{2n}$}
\HSS{D_n}[16]D{\{the other component}
\HSS{E_6}[1]E6{complexified octave projective plane}
\HSS{E_6}[32]E6{its dual plane}
\HSS{E_7}[64]E7{the space of null octave 3-planes in octave 6-space}
\end{longtable}

```

19. EXTENDED DYNKIN DIAGRAMS

Extended Dynkin diagrams

```
\dynkin[extended]A7
```

The extended Dynkin diagrams are also described in the notation of Kac [15] p. 55 as affine untwisted Dynkin diagrams: we extend `\dynkin{A}{7}` to become `\dynkin A[1]7`:

Extended Dynkin diagrams

```
\dynkin A[1]7
```

Table 10: The Dynkin diagrams of the extended simple root systems

A_1^1		<code>\dynkin[extended]A1</code>
A_n^1		<code>\dynkin[extended]A{}</code>
B_n^1		<code>\dynkin[extended]B{}</code>
C_n^1		<code>\dynkin[extended]C{}</code>
D_n^1		<code>\dynkin[extended]D{}</code>
E_6^1		<code>\dynkin[extended]E6</code>
E_7^1		<code>\dynkin[extended]E7</code>
E_8^1		<code>\dynkin[extended]E8</code>
F_4^1		<code>\dynkin[extended]F4</code>
G_2^1		<code>\dynkin[extended]G2</code>

20. AFFINE TWISTED AND UNTWISTED DYNKIN DIAGRAMS

The affine Dynkin diagrams are described in the notation of Kac [15] p. 55:

Affine Dynkin diagrams

```

\(\A^{(1)}_7=\dynkin A[1]7, \
E^{(2)}_6=\dynkin E[2]6, \
D^{(3)}_4=\dynkin D[3]4\

```




$A_7^{(1)} =$ ,
 $E_6^{(2)} =$ ,
 $D_4^{(3)} =$ 

Table 11: The affine Dynkin diagrams


A_1^1		<code>\dynkin A[1]1</code>
A_n^1		<code>\dynkin A[1]{}</code>
B_n^1		<code>\dynkin B[1]{}</code>
C_n^1		<code>\dynkin C[1]{}</code>
D_n^1		<code>\dynkin D[1]{}</code>
E_6^1		<code>\dynkin E[1]6</code>
E_7^1		<code>\dynkin E[1]7</code>
E_8^1		<code>\dynkin E[1]8</code>
F_4^1		<code>\dynkin F[1]4</code>
G_2^1		<code>\dynkin G[1]2</code>
A_2^2		<code>\dynkin A[2]2</code>
A_{ev}^2		<code>\dynkin A[2]{even}</code>
A_{od}^2		<code>\dynkin A[2]{odd}</code>
D_n^2		<code>\dynkin D[2]{}</code>
E_6^2		<code>\dynkin E[2]6</code>
D_4^3		<code>\dynkin D[3]4</code>

Table 12: Some more affine Dynkin diagrams

A_4^2		<code>\dynkin A[2]4</code>
---------	---	----------------------------

continued ...

Table 12: ... continued

A_5^2		<code>\dynkin A[2]5</code>
A_6^2		<code>\dynkin A[2]6</code>
A_7^2		<code>\dynkin A[2]7</code>
A_8^2		<code>\dynkin A[2]8</code>
D_3^2		<code>\dynkin D[2]3</code>
D_4^2		<code>\dynkin D[2]4</code>
D_5^2		<code>\dynkin D[2]5</code>
D_6^2		<code>\dynkin D[2]6</code>
D_7^2		<code>\dynkin D[2]7</code>
D_8^2		<code>\dynkin D[2]8</code>
D_4^3		<code>\dynkin D[3]4</code>
E_6^2		<code>\dynkin E[2]6</code>

Table 13: Some more Kac–Moody Dynkin diagrams, only allowed in Kac ordering

E_6		<code>\dynkin[ordering=Kac,label]E6</code>
E_7		<code>\dynkin[ordering=Kac,label]E7</code>
E_8		<code>\dynkin[ordering=Kac,label]E8</code>
E_9		<code>\dynkin[ordering=Kac,label]E9</code>
E_{10}		<code>\dynkin[ordering=Kac,label]E{10}</code>
E_{11}		<code>\dynkin[ordering=Kac,label]E{11}</code>

21. EXTENDED COXETER DIAGRAMS

Extended and Coxeter options together

`\dynkin[extended,Coxeter]F4`



Table 14: The extended (affine) Coxeter diagrams

A_n		<code>\dynkin[extended,Coxeter]A{}</code>
B_n		<code>\dynkin[extended,Coxeter]B{}</code>
C_n		<code>\dynkin[extended,Coxeter]C{}</code>
D_n		<code>\dynkin[extended,Coxeter]D{}</code>
E_6		<code>\dynkin[extended,Coxeter]E6</code>
E_7		<code>\dynkin[extended,Coxeter]E7</code>
E_8		<code>\dynkin[extended,Coxeter]E8</code>
F_4		<code>\dynkin[extended,Coxeter]F4</code>
G_2		<code>\dynkin[extended,Coxeter]G2</code>
H_3		<code>\dynkin[extended,Coxeter]H3</code>
H_4		<code>\dynkin[extended,Coxeter]H4</code>
I_1		<code>\dynkin[extended,Coxeter]I1</code>

22. KAC STYLE

We include a style called `Kac` which tries to imitate the style of [15].

Kac style	
<code>\dynkin[Kac]F4</code>	

$\circ - \circ \Rightarrow \circ - \circ$	

Table 15: The Dynkin diagrams of the simple root systems in Kac style

A_n	$\circ - \circ - \dots - \circ - \circ$	<code>\dynkin A{}</code>
B_n	$\circ - \circ - \dots - \circ - \circ \Rightarrow \circ$	<code>\dynkin B{}</code>
C_n	$\circ - \circ - \dots - \circ - \circ \Leftarrow \circ$	<code>\dynkin C{}</code>
D_n	$\circ - \circ - \dots - \circ - \circ \begin{matrix} / \circ \\ \backslash \circ \end{matrix}$	<code>\dynkin D{}</code>
E_6	$\circ - \circ - \circ \begin{matrix} / \circ \\ \backslash \circ \end{matrix}$	<code>\dynkin E6</code>

continued ...

Table 15: ... continued

E_7		<code>\dynkin E7</code>
E_8		<code>\dynkin E8</code>
F_4	$\circ - \circ \Rightarrow \circ - \circ$	<code>\dynkin F4</code>
G_2	$\circ \Rightarrow \circ$	<code>\dynkin G2</code>

Table 16: The Dynkin diagrams of the extended simple root systems in Kac style

A_1^1	$\Leftarrow \Rightarrow \circ$	<code>\dynkin[extended]A1</code>
A_n^1		<code>\dynkin[extended]A{}</code>
B_n^1		<code>\dynkin[extended]B{}</code>
C_n^1	$\circ \Rightarrow \circ - \circ - \dots - \circ - \circ \Leftarrow \circ$	<code>\dynkin[extended]C{}</code>
D_n^1		<code>\dynkin[extended]D{}</code>
E_6^1		<code>\dynkin[extended]E6</code>
E_7^1		<code>\dynkin[extended]E7</code>
E_8^1		<code>\dynkin[extended]E8</code>
F_4^1	$\circ - \circ - \circ \Rightarrow \circ - \circ$	<code>\dynkin[extended]F4</code>
G_2^1	$\circ - \circ \Rightarrow \circ$	<code>\dynkin[extended]G2</code>

Table 17: The Dynkin diagrams of the twisted simple root systems in Kac style

A_2^2		<code>\dynkin A[2]2</code>
A_{ev}^2		<code>\dynkin A[2]{even}</code>
A_{od}^2		<code>\dynkin A[2]{odd}</code>
D_n^2		<code>\dynkin D[2]{}</code>
E_6^2		<code>\dynkin E[2]6</code>
D_4^3		<code>\dynkin D[3]4</code>

23. CEREF STYLE

We include a style called `ceref` which paints oblong root markers with shadows. The word “ceref” is an old form of the word “serif”.

Ceref style

`\dynkin[ceref]F4`

Table 18: The Dynkin diagrams of the simple root systems in ceref style

A_n		<code>\dynkin A{}</code>
B_n		<code>\dynkin B{}</code>
C_n		<code>\dynkin C{}</code>
D_n		<code>\dynkin D{}</code>
E_6		<code>\dynkin E6</code>
E_7		<code>\dynkin E7</code>
E_8		<code>\dynkin E8</code>
F_4		<code>\dynkin F4</code>
G_2		<code>\dynkin G2</code>

Table 19: The Dynkin diagrams of the extended simple root systems in ceref style

A_1^1		<code>\dynkin[extended]A1</code>
A_n^1		<code>\dynkin[extended]A{}</code>
B_n^1		<code>\dynkin[extended]B{}</code>
C_n^1		<code>\dynkin[extended]C{}</code>
D_n^1		<code>\dynkin[extended]D{}</code>
E_6^1		<code>\dynkin[extended]E6</code>
E_7^1		<code>\dynkin[extended]E7</code>
E_8^1		<code>\dynkin[extended]E8</code>
F_4^1		<code>\dynkin[extended]F4</code>
G_2^1		<code>\dynkin[extended]G2</code>

Table 20: The Dynkin diagrams of the twisted simple root systems in ceref style

A_2^2		<code>\dynkin A[2]2</code>
A_{ev}^2		<code>\dynkin A[2]{even}</code>
A_{od}^2		<code>\dynkin A[2]{odd}</code>
D_n^2		<code>\dynkin D[2]{}</code>
E_6^2		<code>\dynkin E[2]6</code>
D_4^3		<code>\dynkin D[3]4</code>

24. MORE ON FOLDED DYNKIN DIAGRAMS

The Dynkin diagrams package has limited support for folding Dynkin diagrams.


Folding

`\dynkin[fold]A{13}`



Big fold radius

```
\dynkin[fold, fold radius=1cm]A{13}
```



Small fold radius

```
\dynkin[fold, fold radius=.2cm]A{13}
```



Some Dynkin diagrams have multiple foldings, which we attempt to distinguish (not entirely successfully) by their *ply*: the maximum number of roots folded together. Most diagrams can only allow a 2-ply folding, so `fold` is a synonym for `ply=2`.

3-ply

```
\dynkin[ply=3]D4
\dynkin[ply=3, fold right]D4
\dynkin[ply=3]D[1]4
```



4-ply


```
\dynkin[ply=4]D[1]4
```



The $D_\ell^{(1)}$ diagrams can be folded on their left end and separately on their right end:

Left, right and both

```
\dynkin D[1]{ } \
\dynkin[fold left]D[1]{ } \
\dynkin[fold right]D[1]{ } \
\dynkin[fold]D[1]{ }
```



We have to be careful about the 4-ply foldings of $D_{2\ell}^{(1)}$, for which we can have two different patterns, so by default, the package only draws as much as it can without distinguishing the two:

Default $D_{2\ell}^{(1)}$ and the two ways to finish it

```
\dynkin[ply=4]D[1]{****.*****.*****}%
\
\begin{dynkinDiagram}[ply=4]{D}[1]{****.*****.*****}%
\dynkinFold[bend right=90]1{13}%
\dynkinFold[bend right=90]0{14}%
\end{dynkinDiagram} \
\begin{dynkinDiagram}[ply=4]{D}[1]{****.*****.*****}%
\dynkinFold01%
\dynkinFold1{13}%
\dynkinFold{13}{14}%
\end{dynkinDiagram}
```




Table 21: Some foldings of Dynkin diagrams. For these diagrams, we want to compare a folding diagram with the diagram that results when we fold it, so it looks best to set `fold radius` and `edge length` to equal lengths.

A_3		<code>\dynkin[fold]A[0]3</code>
C_2		<code>\dynkin C[0]2</code>

continued ...

Table 21: ...continued

$A_{2\ell-1}$		<code>\dynkin[fold]A{**.****.**}</code>
C_ℓ		<code>\dynkin C{}</code>
B_3		<code>\dynkin[fold]B[0]3</code>
G_2		<code>\dynkin[reverse arrows]G[0]2</code>
D_4		<code>\dynkin[ply=3, fold right]D4</code>
G_2		<code>\dynkin G2</code>
$D_{\ell+1}$		<code>\dynkin[fold]D{}</code>
B_ℓ		<code>\dynkin B{}</code>
E_6		<code>\dynkin[fold]E[0]6</code>
F_4		<code>\dynkin[reverse arrows]F[0]4</code>
A_3^1		<code>\dynkin[ply=4]A[1]3</code>
A_1^1		<code>\dynkin A[1]1</code>
$A_{2\ell-1}^1$		<code>\dynkin[fold]A[1]{**.****.**}</code>
C_ℓ^1		<code>\dynkin C[1]{}</code>
B_3^1		<code>\dynkin[ply=3]B[1]3</code>
A_2^2		<code>\dynkin A[2]2</code>
B_3^1		<code>\dynkin[ply=2]B[1]3</code>
G_2^1		<code>\dynkin G[1]2</code>
B_ℓ^1		<code>\dynkin[fold]B[1]{}</code>
D_ℓ^2		<code>\dynkin D[2]{}</code>
D_4^1		<code>\dynkin[ply=3]D[1]4</code>
B_3^1		<code>\dynkin B[1]3</code>

continued ...

Table 21: ...continued

D_4^1		<code>\dynkin[ply=3]D[1]4</code>
G_2^1		<code>\dynkin G[1]2</code>
$D_{\ell+1}^1$		<code>\dynkin[fold]D[1]{}</code>
D_ℓ^2		<code>\dynkin D[2]{}</code>
$D_{\ell+1}^1$		<code>\dynkin[fold right]D[1]{}</code>
B_ℓ^1		<code>\dynkin B[1]{}</code>
$D_{2\ell}^1$		<code>\begin{dynkinDiagram}[ply=4]D[1]{</code> <code>{****.*****.*****}</code> <code>\dynkinFold01</code> <code>\dynkinFold1{13}</code> <code>\dynkinFold{13}{14}</code> <code>\end{dynkinDiagram}</code>
A_{odd}^2		<code>\dynkin A[2]{\text{odd}}</code>
$D_{2\ell}^1$		<code>\begin{dynkinDiagram}[ply=4]{D}[1]{</code> <code>{****.*****.*****}</code> <code>\dynkinFold[bend right=90]1{13}</code> <code>\dynkinFold[bend right=90]0{14}</code> <code>\end{dynkinDiagram}</code>
A_{even}^2		<code>\dynkin A[2]{\text{even}}</code>
E_6^1		<code>\dynkin[fold]E[1]6</code>
F_4^1		<code>\dynkin[reverse arrows]F[1]4</code>
E_6^1		<code>\dynkin[ply=3]E[1]6</code>
D_4^3		<code>\dynkin D[3]4</code>
E_7^1		<code>\dynkin[fold]E[1]7</code>
E_6^2		<code>\dynkin E[2]6</code>

continued ...

Table 21: ...continued

F_4^1		<code>\dynkin[fold]F[1]4</code>
G_2^1		<code>\dynkin G[1]2</code>
A_{odd}^2		<code>\dynkin[odd,fold]A[2]{****.***}</code>
A_{even}^2		<code>\dynkin A[2]{even}</code>
D_3^2		<code>\dynkin[fold]D[2]3</code>
A_2^2		<code>\dynkin A[2]2</code>

Table 22: Frobenius fixed point subgroups of finite simple groups of Lie type [4] p. 15

$A_{\ell \geq 1}$		<code>\dynkin A{}</code>
${}^2A_{\ell \geq 2}$		<code>\dynkin[fold]A{}</code>
$B_{\ell \geq 2}$		<code>\dynkin B{}</code>
2B_2		<code>\dynkin[fold]B2</code>
$C_{\ell \geq 3}$		<code>\dynkin C{}</code>
$D_{\ell \geq 4}$		<code>\dynkin D{}</code>
${}^2D_{\ell \geq 4}$		<code>\dynkin[fold]D{}</code>
3D_4		<code>\dynkin[ply=3]D4</code>
E_6		<code>\dynkin E6</code>
2E_6		<code>\dynkin[fold]E6</code>
E_7		<code>\dynkin E7</code>
E_8		<code>\dynkin E8</code>
F_4		<code>\dynkin F4</code>
2F_4		<code>\dynkin[fold]F4</code>
G_2		<code>\dynkin G2</code>
2G_2		<code>\dynkin[fold]G2</code>

25. TYPESETTING MATHEMATICAL NAMES OF DYNKIN DIAGRAMS

The `\dynkinName` command, with the same syntax as `\dynkin`, typesets a default name of your diagram in \LaTeX . It is perhaps only useful when automatically generating a large collection of Dynkin diagrams in a computer program.

Name of a diagram

```
\dynkinName[label,extended]B7
\dynkinName A[2]{even}
\dynkinName[Coxeter]B7
\dynkinName[label,extended]B*
\dynkinName D[3]4
```

B_7^1 A_{ev}^2 B_7 B_1^1 D_4^3

26. CONNECTING DYNKIN DIAGRAMS

We can make some sophisticated folded diagrams by drawing multiple diagrams, each with a name:

Name a diagram

```
\dynkin[name=Bob]D6
```



We can then connect the two with folding edges:

Connect diagrams

```
\begin{dynkinDiagram}[name=upper]A3
  \node (current) at ($(upper root 1)+(0,-.3cm)$) {};
  \dynkin[at=(current),name=lower]A3
  \begin{pgfonlayer}{Dynkin behind}
    \foreach \i in {1,...,3}%
    {%
      \draw[/Dynkin diagram/fold style]
        ($(upper root \i)$)
        -- ($(lower root \i)$);%
    }%
  \end{pgfonlayer}
\end{dynkinDiagram}
```




The following diagrams arise in the Satake diagrams of the pseudo-Riemannian symmetric spaces [2].

```

\pgfkeys{/Dynkin diagram,edge length=.5cm,fold radius=.5cm}
\begin{tikzpicture}
  \dynkin[name=1]A{IIIb}
  \node (a) at (-.3,-.4){};
  \dynkin[name=2,at=(a)]A{IIIb}
  \begin{pgfonlayer}{Dynkin behind}
    \foreach \i in {1,...,7}%
      {%
        \draw[/Dynkin diagram/fold style]
          ( $(1 root \i)$ )
          --
          ( $(2 root \i)$ );%
      }%
    \end{pgfonlayer}
\end{tikzpicture}


```



```


\pgfkeys{/Dynkin diagram,
edge length=.75cm,
edge/.style={draw=example-color,double=black,very thick}}
\begin{tikzpicture}
  \foreach \d in {1,...,4}
  {
    \node (current) at ( $(\d*.05,\d*.3)$ );
    \dynkin[name=\d,at=(current)]D{oo.oooo}
  }
  \begin{pgfonlayer}{Dynkin behind}
    \foreach \i in {1,...,6}%
      {%
        \draw[/Dynkin diagram/fold style] ( $(1 root \i)$ ) -- ( $(2
root \i)$ );%
        \draw[/Dynkin diagram/fold style] ( $(2 root \i)$ ) -- ( $(3
root \i)$ );%
        \draw[/Dynkin diagram/fold style] ( $(3 root \i)$ ) -- ( $(4
root \i)$ );%
      }%
    \end{pgfonlayer}
\end{tikzpicture}

```




27. OTHER EXAMPLES

1D_4 4-ply tied straight:



1D_4 4-ply tied bending:



```

\tikzset{/Dynkin diagram,edge length=1cm,fold radius=1cm}
\tikzset{/Dynkin diagram,label macro/.code={\alpha_{#1}},label macro*/.code={\beta_{#1}}}
\({}^1D_4\) 4-ply tied straight:
\begin{dynkinDiagram}[ply=4]D[1]
{****.****.****}
\dynkinFold 01
\dynkinFold 1{13}

```

```

\dynkinFold{13}{14}
\dynkinLabelRoots{0,...,14}
\dynkinLabelRoots*{0,...,14}
\end{dynkinDiagram}
\({}^1 D_4\ 4\text{-ply tied bending:}
\begin{dynkinDiagram}[ply=4]D[1]%
{****.****.****}
\dynkinFold1{13}
\dynkinFold[bend right=65]0{14}
\dynkinLabelRoots{0,...,14}
\dynkinLabelRoots*{0,...,14}
\end{dynkinDiagram}

```

Below we draw the Vogan diagrams of some affine Lie superalgebras [21, 20].

$\mathfrak{sl}(2m|2n)^{(2)}$

```

\begin{dynkinDiagram}[ply=2,label]{B}[1]{oo.oto.oo}
  \dynkinLabelRoot*71
\end{dynkinDiagram}

```

```

\dynkin[label]B[1]{oo.oto.oo}

```

```

\dynkin[ply=2,label]B[1]{oo.Oto.Oo}


```

```


\dynkin[label]B[1]{oo.Oto.Oo}

```


`\dynkin[label]D[1]{oo.oto.ooo}`



`\dynkin[label]D[1]{oO.otO.ooo}`




`\dynkin[label,fold]D[1]{oo.oto.ooo}`




$\mathfrak{sl}(2m+1|2n)^2$


`\dynkin[label]B[1]{oo.oto.oo}`



`\dynkin[label]B[1]{oO.otO.oO}`




`\dynkin[label,fold]B[1]{oo.oto.oo}`




$$\mathfrak{sl}(2m+1|2n+1)^2$$

`\dynkin[label]D[2]{o.oto.oo}`




`\dynkin[label]D[2]{o.OtO.oo}`




$$\mathfrak{sl}(2|2n+1)^{(2)}$$


`\dynkin[ply=2,label,double edges]B[1]{oo.Oto.Oo}`




`\dynkin[ply=2,label,double fold]B[1]{oo.Oto.Oo}`



`\dynkin[ply=2,label,double edges]B[1]{oo.OtO.oo}`




`\dynkin[ply=2,label,double fold]B[1]{oo.OtO.oo}`




$\mathfrak{sl}(2|2n)^{(2)}$

`\dynkin[ply=2,label,double edges]D[1]{oo.oto.ooo}`




`\dynkin[ply=2,label,double fold left]D[1]{oo.oto.ooo}`




$\mathfrak{osp}(2m|2n)^{(2)}$

`\dynkin[label,label macro/.code={1}]D[2]{o.oto.oo}`




`\dynkin[label,label macro/.code={1}]D[2]{o.Oto.Oo}`



$\mathfrak{osp}(2|2n)^{(2)}$


`\dynkin[label,label macro/.code=\lablIt{#1},
affine mark=*]
D[2]{o.o.o.o*}`




```
\dynkin[label,label macro/.code=\lablIt{#1},
  affine mark=*]
D[2]{o.O.o.o*}
```


 $sl(1|2n+1)^4$

```
\dynkin[label,label macro/.code={1}]D[2]{o.o.o.o*}
```




```
\dynkin[label,label macro/.code={1}]D[2]{o.o.O.o*}
```


 A^1


```
\begin{tikzpicture}
  \dynkin[name=upper]A{o.t.oo}
  \node (Dynkin current) at (upper root 1){};
  \dynkinSouth
  \dynkin[at=(Dynkin current),name=lower]A{o.t.oo}
  \begin{pgfonlayer}{Dynkin behind}
  \foreach \i in {1,...,5}{
    \draw[/Dynkin diagram/fold style]
      ($(\text{upper root } \i)$) -- ($(\text{lower root } \i)$);
  }
  \end{pgfonlayer}
\end{tikzpicture}
```




`\dynkin[fold]A[1]{oo.t.oooo.t.oo}`



`\dynkin[fold,affine mark=t]A[1]{oo.o.ootoo.o.oo}`




`\dynkin[affine mark=t]A[1]{o*.t.*o}`




B^1


`\dynkin[affine mark=*]A[2]{o.ot.o.o*}`




`\dynkin[affine mark=*]A[2]{o.ot.o.o*}`




`\dynkin[affine mark=*]A[2]{o.ooo.oo}`




`\dynkin[odd]A[2]{oo.*to.*o}`



`\dynkin[odd,fold]A[2]{oo.oto.oo}`



`\dynkin[odd,fold]A[2]{o*.oto.o*}`



D^1

`\dynkin D{otoo}`



`\dynkin D{ot*o}`




`\dynkin[fold]D{otoo}`




C^1

```
\dynkin[double edges,fold,affine mark=t,odd]A[2]{to.o*}
```



```
\dynkin[double edges,fold,affine mark=t,odd]A[2]{t*.oo}
```

 F^1


```
\begin{dynkinDiagram}A{oto*}%
  \dynkinQuadrupleEdge 12%
  \dynkinTripleEdge 43%
\end{dynkinDiagram}%
```



```
\begin{dynkinDiagram}A{*too}%
  \dynkinQuadrupleEdge 12%
  \dynkinTripleEdge 43%
\end{dynkinDiagram}%
```

 G^1

```
\begin{dynkinDiagram}A{ot*oo}%
  \dynkinQuadrupleEdge 12%
  \dynkinDefiniteDoubleEdge 43%
\end{dynkinDiagram}%
```



```

\begin{dynkinDiagram}A{oto*o}%
  \dynkinQuadrupleEdge 12%
  \dynkinDefiniteDoubleEdge 43%
\end{dynkinDiagram}%
    
```

```

\begin{dynkinDiagram}A{*too*}%
  \dynkinQuadrupleEdge 12%
  \dynkinDefiniteDoubleEdge 43%
\end{dynkinDiagram}%
    
```

```


\begin{dynkinDiagram}A{*tooo}%
  \dynkinQuadrupleEdge 12%
  \dynkinDefiniteDoubleEdge 43%
\end{dynkinDiagram}%
    
```

28. EXAMPLE: THE COMPLEX SIMPLE LIE ALGEBRAS

\mathfrak{g}	Diagram	Weights	Roots	Simple roots
A_n		$\frac{1}{n+1}\mathbb{Z}^{n+1} / \langle \sum e_j \rangle$	$e_i - e_j$	$e_i - e_{i+1}$
B_n		$\frac{1}{2}\mathbb{Z}^n$	$\pm e_i, \pm e_i \pm e_j, i \neq j$	$e_i - e_{i+1}, e_n$
C_n		\mathbb{Z}^n	$\pm 2e_i, \pm e_i \pm e_j, i \neq j$	$e_i - e_{i+1}, 2e_n$
D_n		$\frac{1}{2}\mathbb{Z}^n$	$\pm e_i \pm e_j, i \neq j$	$e_i - e_{i+1}, \quad i \leq n-1$ $e_{n-1} + e_n$
E_8		$\frac{1}{2}\mathbb{Z}^8$	$\pm 2e_i \pm 2e_j, \quad i \neq j,$ $\sum_i (-1)^{m_i} e_i, \quad \sum m_i \text{ even}$	$2e_1 - 2e_2,$ $2e_2 - 2e_3,$ $2e_3 - 2e_4,$ $2e_4 - 2e_5,$ $2e_5 - 2e_6,$ $2e_6 + 2e_7,$ $-\sum e_j,$ $2e_6 - 2e_7$


```
\end{bunch}&
\begin{bunch}(-1,0,1),\ (2,-1,-1)\end{bunch}
\end{longtable}
```

29. AN EXAMPLE OF MIKHAIL BOROVOI



```
\tikzset{big arrow/.style={
-Stealth,line cap=round,line width=1mm,
shorten <=1mm,shorten >=1mm}}
\newcommand\catholic[2]{\draw[big arrow,green!25!white]
(root #1) to (root #2);}
\newcommand\protestant[2]{
\begin{scope}[transparency group, opacity=.25]
\draw[big arrow,orange] (root #1) to (root #2);
\end{scope}}
\begin{dynkinDiagram}[edge length=1.2cm,
indefinite edge/.style={thick,loosely dotted},
labels*={0,1,2,3,\ell-3,\ell-2,\ell-1,\ell}]D[1]{
\catholic 06\catholic 17
\protestant 70\protestant 61
\end{dynkinDiagram}
```

30. SYNTAX

The syntax is `\dynkin[<options>]{<letter>[<twisted rank>]{<rank>}` where `<letter>` is A, B, C, D, E, F or G, the family of root system for the Dynkin diagram, `<twisted rank>` is 0, 1, 2, 3 (default is 0) representing:

- 0 finite root system
- 1 affine extended root system, i.e. of type ⁽¹⁾
- 2 affine twisted root system of type ⁽²⁾
- 3 affine twisted root system of type ⁽³⁾

and `<rank>` is

- (1) an integer representing the rank or
- (2) blank to represent an indefinite rank or
- (3) the name of a Satake diagram as in section 4.

The environment syntax is `\begin{dynkinDiagram}` followed by the same parameters as `\dynkin`, then various Dynkin diagram and *TikZ* commands, and then `\end{dynkinDiagram}`.

31. OPTIONS

```
*/.style = (TikZ style data),
default : solid,draw=black,fill=black
continued ...
```

Table 24: ... continued

style for roots like \bullet
`o/.style = <TikZ style data>`,
 default : `solid,draw=black,fill=white`
 style for roots like \circ
`O/.style = <TikZ style data>`,
 default : `solid,draw=black,fill=white`
 style for roots like \odot
`t/.style = <TikZ style data>`,
 default : `solid,draw=black,fill=black`
 style for roots like \otimes
`x/.style = <TikZ style data>`,
 default : `solid,draw=black,line cap=round`
 style for roots like \times
`X/.style = <TikZ style data>`,
 default : `solid,draw=black,thick,line cap=round`
 style for roots like \star
`affine mark = o,O,t,x,X,*`,
 default : `*`
 default root mark for root zero in an affine Dynkin diagram
`arrow shape/.style = TikZ style data`,
 default : `-\{Computer Modern Rightarrow[black]\}`
 shape of arrow heads for most Dynkin diagrams that have arrows.
`arrow style = TikZ style data`,
 default : `black`
 set to override the default style for the arrows in nonsimply laced
 Dynkin diagrams, including length, width, line width and color
`arrows = <true or false>`,
 default : `true`
 whether to draw the arrows that arise along the edges.
`backwards = <true or false>`,
 default : `false`
 whether to reverse right to left.
`ceref = <true or false>`,
 default : `false`
 whether to draw roots in a “ceref” style.
`Coxeter = <true or false>`,
 default : `false`
 whether to draw a Coxeter diagram, rather than a Dynkin diagram.
`double edges = <>`,
 default : `not set`
 set to override the `fold` style when folding roots together in a
 Dynkin diagram, so that the foldings are indicated with double
 edges (like those of an F_4 Dynkin diagram without arrows).
`double fold = <>`,
 default : `not set`

continued ...

Table 24: ...continued

set to override the `fold` style when folding roots together in a Dynkin diagram, so that the foldings are indicated with double edges (like those of an F_4 Dynkin diagram without arrows), but filled in solidly.

`double left = $\langle \rangle$,`
`default : not set`
 set to override the `fold` style when folding roots together at the left side of a Dynkin diagram, so that the foldings are indicated with double edges (like those of an F_4 Dynkin diagram without arrows).

`double fold left = $\langle \rangle$,`
`default : not set`
 set to override the `fold` style when folding roots together at the left side of a Dynkin diagram, so that the foldings are indicated with double edges (like those of an F_4 Dynkin diagram without arrows), but filled in solidly.

`double right = $\langle \rangle$,`
`default : not set`
 set to override the `fold` style when folding roots together at the right side of a Dynkin diagram, so that the foldings are indicated with double edges (like those of an F_4 Dynkin diagram without arrows).

`double fold right = $\langle \rangle$,`
`default : not set`
 set to override the `fold` style when folding roots together at the right side of a Dynkin diagram, so that the foldings are indicated with double edges (like those of an F_4 Dynkin diagram without arrows), but filled in solidly.

`edge label/.style = TikZ style data,`
`default : text height=0,text depth=0,label distance=-2pt`
 style of edge labels in the Dynkin diagram, as found, for example, on some Coxeter diagrams

`edge length = $\langle \text{number} \rangle$ cm,`
`default : .35cm`
 distance between nodes in the Dynkin diagram

`edge/.style = TikZ style data,`
`default : solid,draw=black,fill=white,thin`
 style of edges in the Dynkin diagram

`fold = $\langle \text{true or false} \rangle$,`
`default : true`
 whether, when drawing Dynkin diagrams, to draw them 2-ply.

`fold left = $\langle \text{true or false} \rangle$,`
`default : true`
 whether to fold the roots on the left side of a Dynkin diagram.

`fold radius = $\langle \text{length} \rangle$,`
`default : .3cm`

continued ...

Table 24: ... continued

	the radius of circular arcs used in curved edges of folded Dynkin diagrams.
<code>fold right</code>	= $\langle \text{true or false} \rangle$,
default :	<code>true</code>
	whether to fold the roots on the right side of a Dynkin diagram.
<code>fold left style/.style</code>	= $\langle \text{TikZ style data} \rangle$,
default :	style to override the <code>fold</code> style when folding roots together on the left half of a Dynkin diagram
<code>fold right style/.style</code>	= $\langle \text{TikZ style data} \rangle$,
default :	style to override the <code>fold</code> style when folding roots together on the right half of a Dynkin diagram
<code>fold style/.style</code>	= $\langle \text{TikZ style data} \rangle$,
default :	<code>solid,draw=black!40,fill=none,line width=radius</code>
	when drawing folded diagrams, style for the fold indicators.
<code>indefinite edge ratio</code>	= $\langle \text{float} \rangle$,
default :	<code>1.6</code>
	ratio of indefinite edge lengths to other edge lengths.
<code>indefinite edge/.style</code>	= $\langle \text{TikZ style data} \rangle$,
default :	<code>solid,draw=black,fill=white,thin,densely dotted</code>
	style of the dotted or dashed middle third of each indefinite edge.
<code>Kac</code>	= $\langle \text{true or false} \rangle$,
default :	<code>false</code>
	whether to draw in the style of [15]
<code>label</code>	= <code>true</code> or <code>false</code> ,
default :	<code>false</code>
	whether to label the roots according to the current labelling scheme.
<code>label macro</code>	= $\langle \text{1-parameter T}_{\text{E}}\text{X macro} \rangle$,
default :	<code>#1</code>
	the current labelling scheme for roots.
<code>label macro*</code>	= $\langle \text{1-parameter T}_{\text{E}}\text{X macro} \rangle$,
default :	<code>#1</code>
	the current labelling scheme for alternate roots.
<code>label height</code>	= $\langle \text{1-parameter T}_{\text{E}}\text{X macro} \rangle$,
default :	<code>b</code>
	the current maximal height of text labels for the roots, set by giving mathematics text of that height.
<code>label depth</code>	= $\langle \text{1-parameter T}_{\text{E}}\text{X macro} \rangle$,
default :	<code>g</code>
	the current maximal depth of text labels for the roots, set by giving mathematics text of that depth.
<code>make indefinite edge</code>	= $\langle \text{edge pair } i\text{-}j \text{ or list of such} \rangle$,
default :	<code>{}</code>
	edge pair or list of edge pairs to treat as having indefinitely many roots on them.

continued ...

Table 24: ...continued

<code>mark =</code>	<code><o,O,t,x,X,*></code> ,
<code>default :</code>	<code>*</code> default root mark
<code>name =</code>	<code><string></code> ,
<code>default :</code>	<code>anonymous</code> A name for the Dynkin diagram, with <code>anonymous</code> treated as a blank; see section 26.
<code>ordering =</code>	<code><Adams, Bourbaki, Carter, Dynkin, Kac></code> ,
<code>default :</code>	<code>Bourbaki</code> which ordering of the roots to use in exceptional root systems as in section 17.
<code>parabolic =</code>	<code><integer></code> ,
<code>default :</code>	<code>0</code> A parabolic subgroup with specified integer, where the integer is computed as $n = \sum 2^{i-1} a_i$, $a_i = 0$ or 1 , to say that root i is crossed, i.e. a noncompact root.
<code>ply =</code>	<code><0,1,2,3,4></code> ,
<code>default :</code>	<code>0</code> how many roots get folded together, at most.
<code>reverse arrows =</code>	<code><true or false></code> ,
<code>default :</code>	<code>true</code> whether to reverse the direction of the arrows that arise along the edges.
<code>root radius =</code>	<code><number>cm</code> ,
<code>default :</code>	<code>.05cm</code> size of the dots and of the crosses in the Dynkin diagram
<code>text style =</code>	<code><TikZ style data></code> ,
<code>default :</code>	<code>scale=.7</code> Style for any labels on the roots.
<code>upside down =</code>	<code><true or false></code> ,
<code>default :</code>	<code>false</code> whether to reverse up to down.

All other options are passed to TikZ.

REFERENCES

1. J. F. Adams, *Lectures on exceptional Lie groups*, Chicago Lectures in Mathematics, University of Chicago Press, Chicago, IL, 1996, With a foreword by J. Peter May, Edited by Zafer Mahmud and Mamoru Mimura. MR 1428422
2. Kurando Baba, *Satake diagrams and restricted root systems of semisimple pseudo-Riemannian symmetric spaces*, Tokyo J. Math. **32** (2009), no. 1, 127–158. MR 2541161
3. Nicolas Bourbaki, *Lie groups and Lie algebras. Chapters 4–6*, Elements of Mathematics (Berlin), Springer-Verlag, Berlin, 2002, Translated from the 1968 French original by Andrew Pressley. MR 1890629
4. R. W. Carter, *On the representation theory of the finite groups of Lie type over an algebraically closed field of characteristic 0* [MR1170353 (93j:20034)], Algebra, IX, Encyclopaedia Math. Sci., vol. 77, Springer, Berlin, 1995, pp. 1–120, 235–239. MR 1392478

5. ———, *Lie algebras of finite and affine type*, Cambridge Studies in Advanced Mathematics, vol. 96, Cambridge University Press, Cambridge, 2005. MR 2188930
6. Meng-Kiat Chuah, *Cartan automorphisms and Vogan superdiagrams*, Math. Z. **273** (2013), no. 3-4, 793–800. MR 3030677
7. Cristina Draper Fontanals and Valerio Guido, *On the real forms of the exceptional Lie algebra e_6 and their Satake diagrams*, Non-associative and non-commutative algebra and operator theory, Springer Proc. Math. Stat., vol. 160, Springer, Cham, 2016, pp. 211–226. MR 3613831
8. E. B. Dynkin, *Semisimple subalgebras of semisimple Lie algebras*, Mat. Sbornik N.S. **30(72)** (1952), 349–462 (3 plates), Reprinted in English translation in [9]. MR 0047629
9. ———, *Selected papers of E. B. Dynkin with commentary*, American Mathematical Society, Providence, RI; International Press, Cambridge, MA, 2000, Edited by A. A. Yushkevich, G. M. Seitz and A. L. Onishchik. MR 1757976
10. L. Frappat, A. Sciarrino, and P. Sorba, *Structure of basic Lie superalgebras and of their affine extensions*, Comm. Math. Phys. **121** (1989), no. 3, 457–500. MR 990776
11. William Fulton and Joe Harris, *Representation theory*, Graduate Texts in Mathematics, vol. 129, Springer-Verlag, New York, 1991, A first course, Readings in Mathematics. MR 1153249
12. L. C. Grove and C. T. Benson, *Finite reflection groups*, second ed., Graduate Texts in Mathematics, vol. 99, Springer-Verlag, New York, 1985. MR 777684
13. Sigurdur Helgason, *Differential geometry, Lie groups, and symmetric spaces*, Graduate Studies in Mathematics, vol. 34, American Mathematical Society, Providence, RI, 2001, Corrected reprint of the 1978 original. MR 1834454
14. James E. Humphreys, *Reflection groups and Coxeter groups*, Cambridge Studies in Advanced Mathematics, vol. 29, Cambridge University Press, Cambridge, 1990. MR 1066460
15. Victor G. Kac, *Infinite-dimensional Lie algebras*, third ed., Cambridge University Press, Cambridge, 1990. MR 1104219
16. S. Pratik Khastgir and Ryu Sasaki, *Non-canonical folding of Dynkin diagrams and reduction of affine Toda theories*, Progr. Theoret. Phys. **95** (1996), no. 3, 503–518. MR 1388245
17. Robert P. Langlands, *Euler products*, Yale University Press, New Haven, Conn.-London, 1971, A James K. Whittemore Lecture in Mathematics given at Yale University, 1967, Yale Mathematical Monographs, 1. MR 0419366
18. A. L. Onishchik and È. B. Vinberg, *Lie groups and algebraic groups*, Springer Series in Soviet Mathematics, Springer-Verlag, Berlin, 1990, Translated from the Russian and with a preface by D. A. Leites. MR 91g:22001
19. A. L. Onishchik and È. B. Vinberg, *Lie groups and algebraic groups*, Springer Series in Soviet Mathematics, Springer-Verlag, Berlin, 1990, Translated from the Russian and with a preface by D. A. Leites. MR 1064110
20. B. Ransingh, *Vogan diagrams of affine twisted Lie superalgebras*, ArXiv e-prints (2013), 1–9.
21. Biswajit Ransingh, *Vogan diagrams of untwisted affine Kac-Moody superalgebras*, Asian-Eur. J. Math. **6** (2013), no. 4, 1350062, 10. MR 3149279
22. V. Regelskis and B. Vlaar, *Reflection matrices, coideal subalgebras and generalized Satake diagrams of affine type*, ArXiv e-prints (2016), 1–118.
23. Ichirô Satake, *Algebraic structures of symmetric domains*, Kanô Memorial Lectures, vol. 4, Iwanami Shoten, Tokyo; Princeton University Press, Princeton, N.J., 1980. MR 591460
24. T. A. Springer, *Linear algebraic groups*, second ed., Modern Birkhäuser Classics, Birkhäuser Boston, Inc., Boston, MA, 2009. MR 2458469
25. È. B. Vinberg (ed.), *Lie groups and Lie algebras, III*, Encyclopaedia of Mathematical Sciences, vol. 41, Springer-Verlag, Berlin, 1994, Structure of Lie groups and Lie algebras, A translation of it Current problems in mathematics. Fundamental directions. Vol. 41 (Russian), Akad. Nauk SSSR, Vsesoyuz. Inst. Nauchn. i Tekhn. Inform., Moscow, 1990 [MR1056485 (91b:22001)], Translation by V. Minachin [V. V. Minakhin], Translation edited by A. L. Onishchik and È. B. Vinberg. MR 1349140
26. Jean-Bernard Zuber, *Generalized Dynkin diagrams and root systems and their folding*, Topological field theory, primitive forms and related topics (Kyoto, 1996), Progr. Math., vol. 160, Birkhäuser Boston, Boston, MA, 1998, pp. 453–493. MR 1653035

SCHOOL OF MATHEMATICAL SCIENCES, UNIVERSITY COLLEGE CORK, CORK, IRELAND

Email address: b.mckay@ucc.ie