

eledmac

A presumptuous attempt to port
EDMAC, TABMAC and EDSTANZA to LaTeX*

Peter Wilson

Herries Press[†]

Maïeul Rouquette[‡]

based on the original work by

John Lavagnino, Dominik Wujastyk, Herbert Breger and Wayne Sullivan

Abstract

EDMAC, a set of PLAIN T_EX macros, was made at the beginning of 90's for typesetting critical editions in the traditional way, i.e., similar to the Oxford Classical Texts, Teubner, Arden Shakespeare and other series. A separate set of PLAIN T_EX macros, TABMAC, provides for tabular material. Another set of PLAIN T_EX macros, EDSTANZA, assists in typesetting verse.

The eledmac package makes the EDMAC, TABMAC and EDSTANZA facilities available to authors who would prefer to use L^AT_EX. The principal functions provided by the package are marginal line numbering and multiple series of foot- and endnotes keyed to line numbers.

In addition to the EDMAC, TABMAC and EDSTANZA functions the package also provides for index entries keyed to both page and line numbers. Multiple series of the familiar numbered footnotes are also available.

Other L^AT_EX packages for critical editions include EDNOTES, and poemscol for poetical works.

eledmac provides many tools and options. Normally, they are all documented in this file. Also provided is a help folder, “examples”. The folder contains additional examples (although not for all cases)

To report bugs, please go to ledmac's GitHub page and click “New Issue”: <https://github.com/maieul/ledmac/issues/>. You must open an account with github.com to access my page (maieul/ledmac). GitHub accounts are free for open-source users. You can report bugs in English or in French (better).

You can subscribe to the eledmac mail list in:

<http://geekographie.maieul.net/146>

*This file (eledmac.dtx) has version number v1.14.0, last revised 2014/10/27.

[†]herries dot press at earthlink dot net

[‡]maieul at maieul dot net

Contents

1 Introduction	6
1.1 Overview	6
1.2 History	7
1.2.1 EDMAC	7
1.2.2 eledmac	9
1.2.3 List of works edited with (e)ledmac	9
2 The eledmac package	9
3 Numbering text lines and paragraphs	10
3.1 Lineation commands	13
3.2 Changing the line numbers	14
4 The apparatus	15
4.1 Commands	15
4.2 Alternate footnote formatting	18
4.3 Display options	18
4.3.1 Control line number printing	18
4.3.2 Separator between the lemma and the note content	20
4.3.3 Font style	20
4.3.4 Font of the lemma	21
4.3.5 Styles of notes content	21
4.3.6 Arbitrary code at the beginning of notes	21
4.3.7 Options for notes in columns	21
4.3.8 Options for paragraphed footnotes	22
4.3.9 Options for block of notes	22
4.4 Page layout	23
4.5 Fonts	23
4.6 Create a new series	24
5 Verse	25
5.1 Repeating stanza indents	25
5.2 Stanza breaking	26
5.3 Hanging symbol	26
5.4 Long verse and page break	27
5.5 Various tools	27
5.6 Hanging symbol	27
5.7 Text before/after verses	28
6 Grouping	28
7 Crop marks	28
8 Endnotes	29

<i>Contents</i>	3
9 Cross referencing	29
10 Side notes	30
11 Familiar footnotes	31
11.1 Position of the familiar footnotes	32
12 Indexing	32
13 Tabular material	33
14 Sectioning commands	36
15 Quotation environments	38
16 Page breaks	38
17 Miscellaneous	39
17.1 Known and suspected limitations	39
17.2 Use with other packages	40
17.3 Parallel typesetting	41
17.4 Notes for EDMAC users	42
18 Implementation overview	44
19 Preliminaries	44
19.1 Package options	45
19.2 Packages loading	46
19.3 Boolean flags	46
19.4 Messages	46
19.5 Gobbling	50
19.6 Miscellaneous commands	50
20 Sectioning commands	50
21 Line counting	54
21.1 Choosing the system of lineation	54
21.2 List macros	59
21.3 Line-number counters and lists	60
21.4 Reading the line-list file	64
21.5 Commands within the line-list file	65
21.6 Writing to the line-list file	72
22 Marking text for notes	76
22.1 <code>\edtext</code> and <code>\critext</code> themselves	77
22.2 Substitute lemma	82
22.3 Substitute line numbers	82

23 Paragraph decomposition and reassembly	83
23.1 Boxes, counters, <code>\pstart</code> and <code>\pend</code>	83
23.2 Processing one line	87
23.3 Line and page number computation	89
23.4 Line number printing	92
23.5 Pstart number printing in side	96
23.6 Add insertions to the vertical list	97
23.7 Penalties	98
23.8 Printing leftover notes	99
24 Critical footnotes	99
24.1 Fonts	99
24.2 Outer-level footnote commands	100
24.3 Normal footnote formatting	101
24.4 Standard footnote definitions	107
24.5 Paragraphed footnotes	109
24.6 Insertion of the footnotes separator	115
24.7 Columnar footnotes	115
25 Familiar footnotes	120
25.1 Generality	120
25.2 Footnote formats	122
25.3 Two columns footnotes	126
25.4 Three columns footnotes	127
25.5 Paragraphed footnotes	129
26 Footnotes' width for two columns	132
27 Footnotes' order	133
28 Footnotes' rule	133
29 Footnotes' output	133
30 Endnotes	134
31 Generate series	137
31.1 Test if series is still existing	137
31.2 Create all commands to memorize display options	137
31.3 Create inserts, needed to add notes in foot	138
31.4 Create commands for critical apparatus, <code>\Xfootnote</code>	138
31.5 Create tools for familiar footnotes (<code>\footnotex</code>)	139
31.6 The endnotes	140
31.7 Init standards series (A,B,C,D,E,Z)	140
31.8 Some tools	140
31.9 Old commands, kept for backward compatibility	144
31.10 Hooks for a particular footnote	145

31.11 Alias	145
31.12 Line number printing	145
32 Output routine	147
33 Cross referencing	153
34 Side notes	158
35 Minipages and such	164
36 Indexing	168
36.1 Memoir compatibility	169
36.2 Normal setting	171
36.3 Choose the good variant	172
36.4 Hyperref compatibility	172
37 Macro as environment	173
38 Verse	177
39 Arrays and tables	180
40 Section's title commands	200
40.1 Deprecated commands	200
40.2 New commands : <code>\eledxxx</code>	203
41 Page breaking or no page breaking depending of specific lines	212
42 Long verse: prevents being separated by a page break	213
43 The End	214
Appendix A Some things to do when changing version	215
Appendix A.1 Migration from ledmac to eledmac	215
Appendix A.2 Migration to eledmac 1.5.1	215
Appendix A.3 Migration to eledmac 1.12.0	216
References	217
Index	217
Change History	237

List of Figures

1 Introduction

The EDMAC macros [LW90] for typesetting critical editions of texts have been available for use with TeX since 90's. Since EDMAC was introduced there has been a small but constant demand for a version of EDMAC that could be used with LaTeX. The `eledmac` package is an attempt to satisfy that request.

`eledmac` would not have been possible without the amazing work by John Lavagnino and Dominik Wujastyk, the original authors of EDMAC. I, Peter Wilson, am very grateful for their encouragement and permission to use EDMAC as a base. The majority of both the code and this manual are by these two. The tabular material is based on the TABMAC code [Bre96], by permission of its author, Herbert Breger. The verse-related code is by courtesy of Wayne Sullivan, the author of EDSTANZA [Sul92], who has kindly supplied more than his original macros.

Since 2011's Maïeul Rouquette begun to maintain and extend `eledmac`. As plain TeX is used by little people, and L^AT_EX by more people `eledmac` and original EDMAC are more and more distant.

1.1 Overview

The `eledmac` package, together with LaTeX, provides several important facilities for formatting critical editions of texts in a traditional manner. Major features include:

- automatic stepped line numbering, by page or by section;
- sub-lineation within the main series of line numbers;
- variant readings automatically keyed to line numbers;
- caters for both prose and verse;
- multiple series of the footnotes and endnotes;
- block or columnar formatting of the footnotes;
- simple tabular material may be line numbered;
- indexing keyed to page and line numbers.

`eledmac` allows the scholar engaged in preparing a critical edition to focus attention wholly on the task of creating the critical text and evaluating the variant readings, text-critical notes and testimonia. L^AT_EX and `eledmac` will take care of the formatting and visual correlation of all the disparate types of information.

The original EDMAC can be used as a 'stand alone' processor or as part of a process. One example is its use as the formatting engine or 'back end' for the output of an automatic manuscript collation program. COLLATE, written by Peter Robinson, runs on the Apple Macintosh, can collate simultaneously up to a hundred manuscripts of any length, and provides facilities for the scholar to tailor the collation interactively. For further details of this and other related work, visit the EDMAC home page at <http://www.homepages.ucl.ac.uk/~ucgadkw/edmac/index.html>.

Apart from `eledmac` there are some other \LaTeX packages for critical edition typesetting. As Peter Wilson is not an author, or even a prospective one, of any critical edition work he could not provide any opinions on what authors in this area might feel comfortable with or how well any of the packages meet their needs.

`EDNOTES` [Lüc03], by Uwe Lück and Christian Tapp, is another \LaTeX package being developed for critical editions. Unlike `eledmac` which is based on `EDMAC`, `EDNOTES` takes a different (internal) approach and provides a different set of features. For example it provides additional facilities for overlapping lemmas and for handling tables. For more information there is a web site at <http://ednotes.sty.de.vu> or email to ednotes.sty@web.de.

The `poemscol` package [Bur01] by John Burt is designed for typesetting critical editions of collections of poems. I do not know how, or whether, `poemscol` and `eledmac` will work together.

Critical authors may find it useful to look at `EDMAC`, `EDNOTES`, `eledmac`, and `poemscol` to see which best meets their needs.

At the time of writing Peter Wilson knows of two web sites, apart from the `EDMAC` home page, that have information on `eledmac`, and other programs.

- Jerónimo Leal pointed me to <http://www.guit.sssup.it/latex/critical.html>. This also mentions another package for critical editions called `MauroTeX` (<http://www.maurolico.unipi.it/mtex/mtex.htm>). These sites are both in Italian.
- Dirk-Jan Dekker maintains <http://www.djdekker.net/ledmac> which is a FAQ for typesetting critical editions and `eledmac`.

This manual contains a general description of how to use the \LaTeX version of `EDMAC`, namely `eledmac` (in sections 2 through 17.4); the complete source code for the package, with extensive documentation (in sections 18 and following) ; and an Index to the source code. We do not suggest that you need to read the source code for this package in order to use it; we provide this code primarily for reference, and many of our comments on it repeat material that is also found in the earlier sections. But no documentation, however thorough, can cover every question that comes up, and many can be answered quickly by consultation of the code. On a first reading, we suggest that you should read only the general documentation in sections 2, unless you are particularly interested in the innards of `eledmac`.

1.2 History

1.2.1 EDMAC

The original version of `EDMAC` was `TEXTED.TEX`, written by John Lavagnino in late 1987 and early 1988 for formatting critical editions of English plays.

John passed these macros on to Dominik Wujastyk who, in September–October 1988, added the footnote paragraphing mechanism, margin swapping and other changes to suit his own purposes, making the style more like that traditionally used for classical texts in Latin and Greek (e.g., the Oxford Classical Texts series). He

also wrote some extra documentation and sent the files out to several people. This version of the macros was the first to be called **EDMAC**.

The present version was developed in the summer of 1990, with the intent of adding necessary features, streamlining and documenting the code, and further generalizing it to make it easily adaptable to the needs of editors in different disciplines. John did most of the general reworking and documentation, with the financial assistance of the Division of the Humanities and Social Sciences, California Institute of Technology. Dominik adapted the code to the conventions of Frank Mittelbach's **doc** option, and added some documentation, multiple-column footnotes, cross-references, and crop marks.¹ A description by John and Dominik of this version of **EDMAC** was published as 'An overview of **EDMAC**: a **PLAIN T_EX** format for critical editions', *TUGboat 11* (1990), pp. 623–643.

From 1991 through 1994, the macros continued to evolve, and were tested at a number of sites. We are very grateful to all the members of the (now defunct) `edmac@mailbase.ac.uk` discussion group who helped us with smoothing out bugs and infelicities in the macros. Ron Whitney and our anonymous reviewer at the TUG were both of great help in ironing out last-minute wrinkles, while Ron made some important suggestions which may help to make future versions of **EDMAC** even more efficient. Wayne Sullivan, in particular, provided several important fixes and contributions, including adapting the Mittelbach/Schöpf 'New Font Selection Scheme' for use with **PLAIN T_EX** and **EDMAC**. Another project Wayne has worked on is a DVI post-processor which works with an **EDMAC** that has been slightly modified to output `\specials`. This combination enables you to recover to some extent the text of each line, as ASCII code, facilitating the creation of concordances, an *index verborum*, etc.

At the time of writing (1994), we are pleased to be able to say that **EDMAC** is being used for real-life book production of several interesting editions, such as the Latin texts of Euclid's *Elements*,² an edition of the letters of Nicolaus Copernicus,³ Simon Bredon's *Arithmetica*,⁴ a Latin translation by Plato of Tivoli of an Arabic astrolabe text,⁵ a Latin translation of part II of the Arabic *Algebra* by Abū Kāmil Shujā' b. Aslam,⁶ the Latin *Rithmachia* of Werinher von Tegernsee,⁷ a middle-Dutch romance epic on the Crusades,⁸ a seventeenth-century Hungarian politico-philosophical tract,⁹ an anonymous Latin compilation from Hungary enti-

¹This version of the macros was used to format the Sanskrit text in volume I of *Metarules of Pāṇinian Grammar* by Dominik Wujastyk (Groningen: Forsten, 1993).

²Gerhard Brey used **EDMAC** in the production of Hubert L. L. Busard and Menso Folkerts, *Robert of Chester's (?) Redaction of Euclid's Elements, the so-called Adelard II Version*, 2 vols., (Basel, Boston, Berlin: Birkhäuser, 1992).

³Being prepared at the German Copernicus Research Institute, Munich.

⁴Being prepared by Menso Folkerts *et al.*, at the Institut für Geschichte der Naturwissenschaften in Munich.

⁵Richard Lorch, Gerhard Brey *et al.*, at the same Institute.

⁶Richard Lorch, 'Abū Kāmil on the Pentagon and Decagon' in *Vestigia Mathematica*, ed. M. Folkerts and J. P. Hogendijk (Amsterdam, Atlanta: Rodopi, 1993).

⁷Menso Folkerts, 'Die *Rithmachia* des Werinher von Tegernsee', *ibid.*

⁸Geert H. M. Claassens, *De Middelnederlandse Kruisvaartromans*, (Amsterdam: Schipshower en Brinkman, 1993).

⁹Emil Hargittay, *Csáky István: Politica philosophiai Okoskodás-szerint való rendes életnek*

tled *Sermones Compilati in Studio Generali Quinqueecclesiensi in Regno Ungarie*,¹⁰ the collected letters and papers of Leibniz,¹¹ Theodosius's *Spherics*, the German *Algorismus* of Sacrobosco, the Sanskrit text of the *Kāśikāvṛtti* of Vāmana and Jayāditya,¹² and the English texts of Thomas Middleton's collected works.

1.2.2 eledmac

Version 1.0 of **TABMAC** was released by Herbert Breger in October 1996. This added the capability for typesetting tabular material.

Version 0.01 of **EDSTANZA** was released by Wayne Sullivan in June 1992, to help a colleague with typesetting Irish verse.

In March 2003 Peter Wilson started an attempt to port **EDMAC** from TeX to LaTeX. The starting point was **EDMAC** version 3.16 as documented on 19 July 1994 (available from CTAN). In August 2003 the **TABMAC** functions were added; the starting point for these being version 1.0 of October 1996. The **EDSTANZA** (v0.01) functions were added in February 2004. Sidenotes and regular footnotes in numbered text were added in April 2004.

This port was called *ledmac*.

Since July 2011, *ledmac* is maintained by Maïeul Rouquette.

Important changes were put in version 1.0, to make *eledmac* more easily extensible (see 4.3 p.18). These changes can trigger small problems with the old customization. That is why a new name was selected: *eledmac*. To migrate from *ledmac* to *eledmac*, please read Appendix A.1 (p.215).

1.2.3 List of works edited with (e)ledmac

A collaborative list of works edited with (e)ledmac is available on https://www.zotero.org/groups/critical_editions_typeset_with_edmac_ledmac_and_eledmac/items. Please add your own edition made with (e)ledmac.

2 The eledmac package

eledmac is a three-pass package like L^AT_EX itself. Although your textual apparatus and line numbers will be printed even on the first run, it takes two more passes through L^AT_EX to be sure that everything gets to its right place. Any changes you make to the input file may similarly require three passes to get everything to the right place, if the changes alter the number of lines or notes. *eledmac* will tell you that you need to make more runs, when it notices, but it does not expend the labor to check this thoroughly. If you have problems with a line or two misnumbered at the top of a page, try running L^AT_EX once or twice more.

példája (1664–1674) (Budapest: Argumentum Kiadó, 1992).

¹⁰Being produced, as was the previous book, by Gyula Mayer in Budapest.

¹¹Leibniz, *Sämtliche Schriften und Briefe*, series I, III, VII, being edited by Dr. H. Breger, Dr. N. Gädeke and others, at the Leibniz-Archiv, Niedersächsische Landesbibliothek, Hannover. (see <http://www.nlb-hannover.de/Leibniz>)

¹²Being prepared at Poona and Lausanne Universities.

A file may mix *numbered* and *unnumbered* text. Numbered text is printed with marginal line numbers and can include footnotes and endnotes that are referenced to those line numbers: this is how you'll want to print the text that you're editing. Unnumbered text is not printed with line numbers, and you can't use `eledmac`'s note commands with it: this is appropriate for introductions and other material added by the editor around the edited text.

3 Numbering text lines and paragraphs

`\beginnumbering` Each section of numbered text must be preceded by `\beginnumbering` and followed by `\endnumbering`, like:

```
\beginnumbering
<text>
\endnumbering
```

The `\beginnumbering` macro resets the line number to zero, reads an auxiliary file called `<jobname>.nn` (where `<jobname>` is the name of the main input file for this job, and `nn` is 1 for the first numbered section, 2 for the second section, and so on), and then creates a new version of this auxiliary file to collect information during this run. The first instance of `\beginnumbering` also opens a file called `<jobname>.end` to receive the text of the endnotes. `\endnumbering` closes the `<jobname>.nn` file.

If the line numbering of a text is to be continuous from start to end, then the whole text will be typed between one pair of `\beginnumbering` and `\endnumbering` commands. But your text will most often contain chapter or other divisions marking sections that should be independently numbered, and these will be appropriate places to begin new numbered sections. `eledmac` has to read and store in memory a certain amount of information about the entire section when it encounters a `\beginnumbering` command, so it speeds up the processing and reduces memory use when a text is divided into a larger number of sections (at the expense of multiplying the number of external files that are generated).

`\pstart` Within a numbered section, each paragraph of numbered text must be marked using the `\pstart` and `\pend` commands:

```
\pstart
<paragraph of text>
\pend
```

Text that appears within a numbered section but isn't marked with `\pstart` and `\pend` will not be numbered.

The following example shows the proper section and paragraph markup, and the kind of output that would typically be generated:

<code>\beginnumbering</code>	
<code>\pstart</code>	
This is a sample paragraph, with	
lines numbered automatically.	
<code>\pend</code>	1 This is a sample paragraph
	2 with lines numbered
<code>\pstart</code>	3 automatically.
This paragraph too has its	4 This paragraph too
lines automatically numbered.	5 has its lines automatically
<code>\pend</code>	6 numbered.
The lines of this paragraph are	The lines of this paragraph
not numbered.	are not numbered.
<code>\pstart</code>	7 And here the numbering
And here the numbering begins	8 begins again.
again.	
<code>\pend</code>	
<code>\endnumbering</code>	

Both `\pstart` and `\pend` can take a optional argument, in brackets. Its content will be printed before the beginning of the `\pstart` / after the end of the `\pend`. If you need to start a `\pstart` by brackets, or to add brackets after a `\pend`, just add a `\relax` between `\pstart`/`\pend` and the brackets.

This feature is not needed for normal use of `eledmac`, but it is needed when using verse (see 5 p. 25) or `eledpar` (see 17.3 p. 41).

A `\noindent` is automatically added before this argument.

`\autopar` You can use `\autopar` to avoid the nuisance of this paragraph markup and still have every paragraph automatically numbered. The scope of the `\autopar` command needs to be limited by keeping it within a group, as follows:

<code>\begingroup</code>	
<code>\beginnumbering</code>	
<code>\autopar</code>	
A paragraph of numbered text.	1 A paragraph of numbered
	2 text.
Another paragraph of numbered	3 Another paragraph of
text.	4 numbered text.
<code>\endnumbering</code>	
<code>\endgroup</code>	

`\autopar` fails, however, on paragraphs that start with a `{` or with any other command that starts a new group before it generates any text. Such paragraphs need to be started explicitly, before the new group is opened, using `\indent`, `\noindent`, or `\leavevmode`, or using `\pstart` itself.¹³

`\firstlinenum` By default, `eledmac` numbers every 5th line. There are two counters,
`\linenumincrement`

¹³For a detailed study of the reasons for this restriction, see Barbara Beeton, 'Initiation rites', *TUGboat* 12 (1991), pp. 257–258.

`firstlinenum` and `linenumincrement`, that control this behaviour; they can be changed using `\firstlinenum{<num>}` and `\linenumincrement{<num>}`. `\firstlinenum` specifies the first line that will have a printed number, and `\linenumincrement` is the difference between successive numbered lines. For example, to start printing numbers at the first line and to have every other line numbered:

```
\firstlinenum{1} \linenumincrement{2}
```

```
\firstsublinenum
\sublinenumincrement
\numberpstarttrue
```

There are similar commands, `\firstsublinenum{<num>}` and `\sublinenumincrement{<num>}` for controlling sub-line numbering.

You can use the command `\numberpstarttrue` to insert a number on every `\pstart`. To stop the numbering, you must use `\numberpstartfalse`. To reset the numbering of `\pstarts`, insert

```
\setcounter{pstart}{0}
```

```
\pausenumbering
\resumenumbering
```

`eledmac` stores a lot of information about line numbers and footnotes in memory as it goes through a numbered section. But at the end of such a section, it empties its memory out, so to speak. If your text has a very long numbered section it is possible that your \LaTeX may reach its memory limit. There are two solutions to this. The first is to get a larger \LaTeX with increased memory. The second solution is to split your long section into several smaller ones. The trouble with this is that your line numbering will start again at zero with each new section. To avoid this problem, we provide `\pausenumbering` and `\resumenumbering` which are just like `\endnumbering ... \beginnumbering`, except that they arrange for your line numbering to continue across the break. Use `\pausenumbering` only between numbered paragraphs:

```
\beginnumbering
\pstart
Paragraph of text.
\pend
\pausenumbering
\resumenumbering
\pstart
Another paragraph.
\pend
\endnumbering
```

1 Paragraph of
2 text.
3 Another paragraph.

We have defined these commands as two macros, in case you find it necessary to insert text between numbered sections without disturbing the line numbering. But if you are really just using these macros to save memory, you might as well say

```
\newcommand{\memorybreak}{\pausenumbering\resumenumbering}
```

and say `\memorybreak` between the relevant `\pend` and `\pstart`.

It's possible to insert a number at every `\pstart` command. You must use `\numberpstarttrue` the `\numberpstarttrue` command to have it. You can stop the numbering with

`\numberpstartfalse` `\numberpstartfalse`. You can redefine the command `\thepstart` to change style. On each `\beginnumbering` the numbering restarts.

With the `\sidepstartnumtrue` command, the number of `\pstart` will be printed in side. In this case, the line number will be not printed.

With the `\labelpstarttrue` command, a `\label` added just after a `\pstart` will refer to the number of this `pstart`.

3.1 Lineation commands

`\numberlinefalse` Line numbering can be disabled with `\numberlinefalse`. It can be enabled again with `\numberlinetrue`. Lines can be numbered either by page, by `pstart` or by section; you specify this using the `\lineation{<arg>}` macro, where `<arg>` is either `page`, `pstart` or `section`. You may only use this command at places where numbering is not in effect; you can't change the lineation system within a section. You can change it between sections: they don't all have to use the same lineation system. The package's standard setting is `\lineation{section}`. If the lineation is by `pstart`, the `pstart` number will be printed before the line number in the notes.

`\linenummargin` The command `\linenummargin{<location>}` specifies the margin where the line (or `pstart`) numbers will be printed. The permissible value for `<location>` is one out of the list `left`, `right`, `inner`, or `outer`, for example `\linenummargin{inner}`. The package's default setting is

`\linenummargin{left}`

to typeset the numbers in the left hand margin. You can change this whenever you're not in the middle of making a paragraph.

More precisely, the value of `\linenummargin` used is that in effect at the `\pend` of a numbered paragraph. Apart from an initial setting for `\linenummargin`, only change it after a `\pend`, whereupon it will apply to all following numbered paragraphs, until changed again (changing it between a `\pstart` and `\pend` pair will apply the change to all the current paragraph).

`\firstlinenum` In most cases, you will not want a number printed for every single line of the text. Four L^AT_EX counters control the printing of marginal numbers and they can be set by the macros `\firstlinenum{<num>}`, etc. `\firstlinenum` specifies the number of the first line in a section to number, and `\linenumincrement` is the increment between numbered lines. `\firstsublinenum` and `\sublinenumincrement` do the same for sub-lines. Initially, all these are set to 5 (e.g., `\firstlinenum{5}`).

`\linenumberlist` You can define `\linenumberlist` to specify a non-uniform distribution of printed line numbers. For example:

```
\def\linenumberlist{1,2,3,5,7,11,13,17,19,23,29}
```

to have numbers printed on prime-numbered lines only. There must be no spaces within the definition which consists of comma-separated decimal numbers. The numbers can be in any order but it is easier to read if you put them in numerical order. Either omitting the definition of `\linenumberlist` or following the vacuous definition

```
\def\linenumberlist{}
```

the standard numbering sequence is applied. The standard sequence is that specified by the combination of the `firstlinenum`, `linenumincrement`, `firstsublinenum`

and `linenumincrement` counter values.

`\leftlinenum` When a marginal line number is to be printed, there are a lot of ways to
`\rightlinenum` display it. You can redefine `\leftlinenum` and `\rightlinenum` to change the
`\linenumsep` way marginal line numbers are printed in the left and right margins respectively;
the initial versions print the number in font `\numlabfont` (described below) at a
distance `\linenumsep` (initially set to one pica) from the text.

3.2 Changing the line numbers

Normally the line numbering starts at 1 for the first line of a section and steps up by one for each line thereafter. There are various common modifications of this system, however; the commands described here allow you to put such modifications into effect.

`\startsub` You insert the `\startsub` and `\endsub` commands in your text to turn sub-
`\endsub` lineation on and off. In plays, for example, stage directions are often numbered
with sub-line numbers: as line 10.1, 10.2, 10.3, rather than as 11, 12, and 13.
Titles and headings are sometimes numbered with sub-line numbers as well.

When sub-lineation is in effect, the line number counter is frozen and the sub-line counter advances instead. If one of these commands appears in the middle of a line, it doesn't take effect until the next line; in other words, a line is counted as a line or sub-line depending on what it started out as, even if that changes in the middle.

`\startlock` The `\startlock` command, used in running text, locks the line number at its
`\endlock` current value, until you say `\endlock`. It can tell for itself whether you are in a
patch of line or sub-line numbering. One use for line-number locking is in printing
poetry: there the line numbers should be those of verse lines rather than of printed
lines, even when a verse line requires several printed lines.

`\lockdisp` When line-number locking is used, several printed lines may have the same line
number, and you have to specify whether you want the number attached to the
first printed line or the last, or whether you just want the number printed by them
all. (This assumes that, on the basis of the settings of the previous parameters,
it is necessary to display a line number for this line.) You specify your preference
using `\lockdisp{<arg>}`; its argument is a word, either `first`, `last`, or `all`. The
package initially sets this as `\lockdisp{first}`.

`\setline` In some cases you may want to modify the line numbers that are automatically
`\advanceline` calculated: if you are printing only fragments of a work but want to print line
numbers appropriate to a complete version, for example. The `\setline{<num>}` and
`\advanceline{<num>}` commands may be used to change the current line's num-
ber (or the sub-line number, if sub-lineation is currently on). They change both
the marginal line numbers and the line numbers passed to the notes. `\setline`
takes one argument, the value to which you want the line number set; it must be
0 or greater. `\advanceline` takes one argument, an amount that should be added
to the current line number; it may be positive or negative.

`\setlinenum` The `\setline` and `\advanceline` macros should only be used within a
`\pstart...pend` group. The `\setlinenum{<num>}` command can be used out-
side such a group, for example between a `pend` and a `\pstart`. It sets the line

number to $\langle num \rangle$. It has no effect if used within a `\pstart... \pend` group

`\linenumberstyle` Line numbers are normally printed as arabic numbers. You can use `\linenumberstyle{\langle style \rangle}`

`\sublinenumberstyle` to change the numbering style. $\langle style \rangle$ must be one of:

`Alph` Uppercase letters (A...Z).

`alph` Lowercase letters (a...z).

`arabic` Arabic numerals (1, 2, ...)

`Roman` Uppercase Roman numerals (I, II, ...)

`roman` Lowercase Roman numerals (i, ii, ...)

Note that with the `Alph` or `alph` styles, ‘numbers’ must be between 1 and 26 inclusive.

Similarly `\sublinenumberstyle{\langle style \rangle}` can be used to change the numbering style of sub-line numbers, which is normally arabic numerals.

`\skipnumbering` When inserted into a numbered line the macro `\skipnumbering` causes the numbering of that particular line to be skipped; that is, the line number is unchanged and no line number will be printed.

4 The apparatus

4.1 Commands

`\edtext` Within numbered paragraphs, all footnotes and endnotes are generated by the `\edtext` macro:

`\edtext{\langle lemma \rangle}{\langle commands \rangle}`

The $\langle lemma \rangle$ argument is the lemma in the main text: `\edtext` both prints this as part of the text, and makes it available to the $\langle commands \rangle$ you specify to generate notes.

For example:

<code>I saw my friend \edtext{Smith}{</code> <code>\Afootnote{Jones C, D.}}</code> <code>on Tuesday.</code>	1 I saw my friend 2 Smith on Tuesday. 2 Smith] Jones C, D.
---	--

The lemma `Smith` is printed as part of this sentence in the text, and is also made available to the footnote that specifies a variant, `Jones C, D`. The footnote macro is supplied with the line number at which the lemma appears in the main text.

The $\langle lemma \rangle$ may contain further `\edtext` commands. Nesting makes it possible to print an explanatory note on a long passage together with notes on variants for individual words within the passage. For example:

<pre> \edtext{I saw my friend \edtext{Smith}{\Afootnote{Jones C, D.}} on Tuesday.}{ \Bfootnote{The date was July 16, 1954.} } </pre>	<pre> 1 I saw my friend 2 Smith on Tuesday. 2 Smith] Jones C, D. 1-2 I saw my friend Smith on Tuesday.] The date was July 16, 1954. </pre>
--	--

However, `\edtext` cannot handle overlapping but unnested notes—for example, one note covering lines 10–15, and another covering 12–18; a `\edtext` that starts in the `\lemma` argument of another `\edtext` must end there, too. (The `\lemma` and `\linenum` commands may be used to generate overlapping notes if necessary.)

Commands used in `\edtext`’s second argument The second argument of the `\edtext` macro, `\langle commands \rangle`, may contain a series of subsidiary commands that generate various kinds of notes.

<pre> \Afootnote \Bfootnote \Cfootnote \Dfootnote \Efootnote </pre>	<p>Five separate series of the footnotes are maintained; each macro taking one argument like <code>\Afootnote{\langle text \rangle}</code>. When all five are used, the A notes appear in a layer just below the main text, followed by the rest in turn, down to the E notes at the bottom. These are the main macros that you will use to construct the critical apparatus of your text. The package provides five layers of notes in the belief that this will be adequate for the most demanding editions. But it is not hard to add further layers of notes should they be required.</p>
---	---

An optional argument can be added before the text of the footnote. Its value is a comma separated list of options. The available options are:

- `nonum` to disable line numbering for this note.
- `nosep` to disable the lemma separator for this note.

Example: `\Afootnote[nonum]{\langle text \rangle}`.

<pre> \Aendnote \Bendnote \Cendnote \Dendnote \Eendnote </pre>	<p>The package also maintains five separate series of endnotes. Like footnotes each macro takes a single argument like <code>\Aendnote{\langle text \rangle}</code>. Normally, none of them are printed: you must use the <code>\doendnotes</code> macro described below (p.29) to call for their output at the appropriate point in your document.</p> <p>By default, no paragraph can be made in the notes of critical apparatus. You can allow it by adding the options <code>parapparatus</code> when loading the package :</p>
--	---

```
\usepackage[parapparatus]{eledmac}
```

<pre>\lemma</pre>	<p>If you want to change the lemma that gets passed to the notes, you can do this by using <code>\lemma{\langle alternative \rangle}</code> within the second argument to <code>\edtext</code>, before the note commands. The most common use of this command is to abbreviate the lemma that’s printed in the notes. For example:</p>
-------------------	--

<code>\edtext{I saw my friend</code>	1 I saw my friend
<code>\edtext{Smith}{\Afootnote{Jones</code>	2 Smith on Tuesday.
<code>C, D.}} on Tuesday.}</code>	
<code>{\lemma{I \dots\ Tuesday.}}</code>	<u>2 Smith]</u> Jones C, D.
<code>\Bfootnote{The date was</code>	<u>1-2 I ...</u> Tuesday.]
<code>July 16, 1954.}</code>	
<code>}</code>	The date was July 16, 1954.

`\linenum` You can use `\linenum{⟨arg⟩}` to change the line numbers passed to the notes. The notes are actually given seven parameters: the page, line, and sub-line number for the start of the lemma; the same three numbers for the end of the lemma; and the font specifier for the lemma. As the argument to `\linenum`, you specify those seven parameters in that order, separated by vertical bars (the `|` character). However, you can retain the value computed by `eledmac` for any number by simply omitting it; and you can omit a sequence of vertical bars at the end of the argument. For example, `\linenum{||23}` changes one number, the ending page number of the current lemma.

This command doesn't change the marginal line numbers in any way; it just changes the numbers passed to the footnotes. Its use comes in situations that `\edtext` has trouble dealing with for whatever reason. If you need notes for overlapping passages that aren't nested, for instance, you can use `\lemma` and `\linenum` to generate such notes despite the limitations of `\edtext`. If the `⟨lemma⟩` argument to `\edtext` is extremely long, you may run out of memory; here again you can specify a note with an abbreviated lemma using `\lemma` and `\linenum`. The numbers used in `\linenum` need not be entered manually; you can use the 'x-' symbolic cross-referencing commands below (p. 29) to compute them automatically.

Similarly, being able to manually change the lemma's font specifier in the notes might be important if you were using multiple scripts or languages. The form of the font specifier is three separate codes separated by `/` characters, giving the family, series, and shape codes as defined within NFSS.

Changing the names of these commands The commands for generating the apparatus have been given rather bland names, because editors in different fields have widely divergent notions of what sort of notes are required, where they should be printed, and what they should be called. But this doesn't mean you have to type `\Afootnote` when you'd rather say something you find more meaningful, like `\variant`. We recommend that you create a series of such aliases and use them instead of the names chosen here; all you have to do is put commands of this form at the start of your file ¹⁴:

```
\newcommandx{\variant}[2][1,usedefault]{\Afootnote[#1]{#2}}
\newcommandx{\explanatory}[2][1,usedefault]{\Bfootnote[#1]{#2}}
\newcommand{\trivial}[1]{\Aendnote{#1}}
```

¹⁴We use `\newcommand` and `\newcommandx` instead of classical `\let` command because the edtabular environments have to modify the notes definition, and we need to use the newest definition of notes. Read the handbook of `xargs` to know more about `\newcommandx`.

```
\newcommandx{\testimonia}[2][1,usedefault]{\Cfootnote[#1]{#2}}
```

4.2 Alternate footnote formatting

If you just launch into `eledmac` using the commands outlined above, you will get a standard layout for your text and notes. You may be happy to accept this at the very beginning, while you get the hang of things, but the standard layout is not particularly pretty, and you will certainly want to modify it in due course. The package provides ways of changing the fonts and layout of your text, but these are not aimed at being totally comprehensive. They are enough to deal with simple variations from the norm, and to exemplify how you might go on to make more significant changes.

`\footparagraph` By default, all footnotes are formatted as a series of separate paragraphs in one column. Three other formats are also available for notes, and using these macros you can select a different format for a series of notes.

- `\footparagraph` formats all the footnotes of a series as a single paragraph;
- `\foottwocol` formats them as separate paragraphs, but in two columns;
- `\footthreecol`, in three columns.

Each of these macros takes one argument: a letter (between **A** and **E**) for the series of notes you want changed. So a text with three layers of notes might begin thus:

```
\footnormal{A}
\footthreecol{B}
\footparagraph{C}
```

This would make the A-notes ordinary, B-notes would be in three columns, and the bottom layer of notes would be formed into a paragraph on each page.

4.3 Display options

Since version 1.0, some commands can be used to change the display of the footnotes. All can have an optional argument `[\langle s \rangle]`, which is the letter of the series — or a list of letters separated by comma — depending on which option is applied.

When a length, noted $\langle l \rangle$, is used, it can be stretchable: **a plus b minus c**. The final length **m** is calculated by \LaTeX to have: $a - c \leq m \leq a + b$. If you use relative unity¹⁵, it will be relative to fontsize of the footnote.

4.3.1 Control line number printing

`\numberonlyfirstinline` By default, the line number is printed in every note. If you want to print it only the first time for a value (i.e one time for line 1, one time for line 2 etc.), you can use

¹⁵Like `em` which is the width of a M.

`\numberonlyfirstinline[⟨s⟩]`. Use `\numberonlyfirstinline[⟨s⟩][false]` to cancel it (`<s>` can be empty if you want to disable it for every series).

`\numberonlyfirstintwolines`

Suppose you have a lemma on line 2 and a lemma between line 2 and line 3. With `\numberonlyfirstinline`, the second lemma is considered to be on the same line as the first lemma. But if you use both `\numberonlyfirstinline[⟨s⟩]` and `\numberonlyfirstintwolines[⟨s⟩]`, the distinction is made. Use `\numberonlyfirstintwolines[⟨s⟩][false]` to cancel it (`<s>` can be empty if you want to disable it for every series).

`\symlinenum`

For setting a particular symbol in place of the line number, you can use `\symlinenum[⟨s⟩]{⟨symbol⟩}` in combination with `\numberonlyfirstinline[⟨s⟩]`. From the second lemma of the same line, the symbol will be used instead of line number.

`\nonumberinfootnote`

You can use `\nonumberinfootnote[⟨s⟩]` if you don't want to have the line number in a footnote. To cancel it, use `\nonumberinfootnote[⟨s⟩][false]`.

`\pstartinfootnote`

You can use `\pstartinfootnote[⟨s⟩]` if you want to print the pstart number in the footnote, before the line and subline number. Use `\pstartinfootnote[⟨s⟩][false]` to cancel it (`<s>` can be empty if you want to disable it for every series). Note that when you change the lineation system, the option is automatically switched :

- If you use lineation by pstart, the option is enabled.
- If you use lineation by section or by page, the option is disabled.

`\onlypstartinfootnote`

In combination with `\pstartinfootnote`, you can use `\onlypstartinfootnote[⟨s⟩]` if you want to print only the pstart number in the footnote, and not the line and subline number. Use `\onlypstartinfootnote[⟨s⟩][false]` to cancel it (`<s>` can be empty if you want to disable it for every series).

`\beforenumberinfootnote`

With `\beforenumberinfootnote[⟨s⟩]{⟨l⟩}`, you can add some space before the line number in a footnote. If the line number is not printed, the space is not either. The default value is 0 pt.

`\afternumberinfootnote`

With `\afternumberinfootnote[⟨s⟩]{⟨l⟩}` you can add some space after the line number in a footnote. If the line number is not printed, the space is not either. The default value is 0.5 em.

`\nonbreakableafternumber`

By default, the space defined by `\afternumberinfootnote` is breakable. With `\nonbreakableafternumber[⟨s⟩]` it becomes nonbreakable. Use `\nonbreakableafternumber[⟨s⟩][false]` to cancel it (`<s>` can be empty if you want to disable it for every series).

`\beforesymlinenum`

With `\beforesymlinenum[⟨s⟩]{⟨l⟩}` you can add some space before the line symbol in a footnote. The default value is value set by `\beforenumberinfootnote`.

`\aftersymlinenum`

With `\aftersymlinenum[⟨s⟩]{⟨l⟩}` you can add some space after the line symbol in a footnote. The default value is value set by `\afternumberinfootnote`.

`\inplaceofnumber`

If no number or symbolic line number is printed, you can add a space, with `\inplaceofnumber[⟨s⟩]{⟨l⟩}`. The default value is 1 em.

`\boxlinenum`

It could be useful to put the line number inside a fixed box: the content of the note will be printed after this box. You can use `\boxlinenum[⟨s⟩]{⟨l⟩}` to do that. To subsequently disable this feature, use `\boxlinenum` with length equal to 0 pt. One use of this feature is to print line number in a column, and the note in an other column:

```
\Xhangindent{1em}
\afternumberinfootnote{0em}
\boxlinenum{1em}
```

`\boxsymlinenum` `\boxsymlinenum[⟨s⟩]{⟨l⟩}` is the same as `\boxlinenum` but for the line number symbol.

4.3.2 Separator between the lemma and the note content

`\lemmaseparator` By default, in a footnote, the separator between the lemma and thenote is a right bracket (`\rbracket`). You can use `\lemmaseparator[⟨s⟩]{⟨l⟩}` to change it. The optional argument can be used to specify in which series it is applied. Note that there is a non-breakable space between lemma and separator, but **breakable** space between separator and lemma.

`\beforelemmaseparator` Using `\beforelemmaseparator[⟨s⟩]{⟨l⟩}` you can add some space between lemma and separator. If your lemma separator is empty, this space won't be printed. The default value is 0 em.

`\afterlemmaseparator` Using `\afterlemmaseparator[⟨s⟩]{⟨l⟩}` you can add some space between separator and note. If your lemma separator is empty, this space won't be printed. The default value is 0.5 em.

`\nolemmaseparator` You can suppress the lemma separator, using `\nolemmaseparator[⟨s⟩]`, which is simply a alias of `\lemmaseparator[⟨s⟩]{}`.

`\inplaceoflemmaseparator` With `\inplaceoflemmaseparator[⟨s⟩]{⟨l⟩}` you can add a space if no lemma separator is printed. The default value is 1 em.

4.3.3 Font style

`\Xnotenumfont` `\Xnotenumfont[⟨s⟩]{⟨command⟩}` is used to change the font style for line numbers in critical footnotes ; `⟨command⟩` must be one (or more) switching command, like `\bfseries`.

`\Xendnotenumfont` `\Xendnotenumfont[⟨s⟩]{⟨command⟩}` is used to change the font style for line numbers in critical footnotes. `⟨command⟩` must be one (or more) switching command, like `\bfseries`.

`\notenumfontX` `\notenumfontX[⟨s⟩]{⟨command⟩}` is used to change the font style for note numbers in familiar footnotes. `⟨command⟩` must be one (or more) switching command, like `\bfseries`.

`\Xnotefontsize` `\Xnotefontsize[⟨s⟩]{⟨command⟩}` is used to define the font size of critical footnotes of the series. The default value is `\footnotesize`. The `⟨command⟩` must not be a size in pt, but a standard L^AT_EX size, like `\small`.

`\notefontsizeX` `\notefontsizeX[⟨s⟩]{⟨command⟩}` is used to define the font size of critical footnotes of the series. The default value is `\footnotesize`. The `⟨command⟩` must not be a size in pt, but a standard L^AT_EX size, like `\small`.

`\Xendnotefontsize` `\Xendnotefontsize[⟨s⟩]{⟨l⟩}` is used to define the font size of end critical footnotes of the series. The default value is `\footnotesize`. The `⟨command⟩` must not be a size in pt, but a standard L^AT_EX size, like `\small`.

4.3.4 Font of the lemma

`\lemmadisablefontselection` By default, font of the lemma in footnote is the same as font of the lemma in the main text. For example, if the lemma is in italic in the main text, it is also in italic in note. The `\Xlemmadisablefontselection[⟨s⟩]` command allows to disable it for a specific series.

`\endlemmadisablefontselection` By default, font of the lemma in endnote is the same as font of the lemma in the main text. For example, if the lemma is in italic in the main text, it is also in italic in note. The command allows `\Xendlemmadisablefontselection[⟨s⟩]` to disable it for a specific series.

4.3.5 Styles of notes content

`\Xhangindent` For critical notes NOT paragraphed you can define an indent with `\Xhangindent[⟨s⟩]{⟨l⟩}`, which will be applied in the second line of notes. It can help to make distinction between a new note and a break in a note. The default value is 0 pt.

`\hangindentX` For familiar notes NOT paragraphed you can define an indent with `\Xhangindent[⟨s⟩]{⟨l⟩}`, which will be applied in the second line of notes. It can help to make a distinction between a new note and a break in a note.

4.3.6 Arbitrary code at the beginning of notes

The three next commands add an arbitrary code at the beginning of notes. As the name's space is local to the notes, you can use it to redefine some style inside the notes. For example, if you don't want the `pstart` number to be in bold, use :

```
\bhookXnote{\renewcommand{\thepstart}{\arabic{pstart}.}}
```

`\bhookXnote` `\bhookXnote[⟨series⟩]{⟨code⟩}` is to be used at the beginning of the critical footnotes.

`\bhooknoteX` `\bhooknoteX[⟨series⟩]{⟨code⟩}` is to be used at the beginning of the familiar footnotes.

`\bhookXendnote` `\bhookXendnote[⟨series⟩]{⟨code⟩}` is to be used at the beginning of the end-notes.

4.3.7 Options for notes in columns

For the following four macros, be careful that the columns are made from right to left.

`\hsizetwocol` `\hsizetwocol[⟨s⟩]{⟨l⟩}` is used to change width of a column when critical notes are displaying in two columns. Default value is `.45 \hsizetwocol`.

`\hsizethreecol` `\hsizethreecol[⟨s⟩]{⟨l⟩}` is used to change width of a column when critical notes are displaying in three columns. Default value is `.3 \hsizethreecol`.

`\hsizetwocolX` `\hsizetwocolX[⟨s⟩]{⟨l⟩}` is used to change width of a column when familiar notes are displaying in two columns. Default value is `.45 \hsizetwocolX`.

`\hsizethreecolX` `\hsizethreecolX[⟨s⟩]{⟨l⟩}` is used to change width of a column when familiar notes are displaying in three columns. Default value is `.3 \hsizethreecolX`.

4.3.8 Options for paragraphed footnotes

<code>\afternote</code>	You can add some space after a note by using <code>\afternote[⟨s⟩]{⟨l⟩}</code> . The default value is <code>1em plus.4em minus.4em</code> .
<code>\parafootsep</code>	For paragraphed footnotes (see below), you can choose the separator between each note by <code>\parafootsep[⟨s⟩]{⟨l⟩}</code> . A common separator is a double pipe (<code>\$ \$</code>), which you can set by <code>\parafootsep{\$ \$}</code> .
<code>\Xragged</code>	Text in paragraphed critical notes is justified, but you can use <code>\Xragged[⟨s⟩]+L+</code> if you want it to be ragged left, or <code>\Xragged[⟨s⟩]+R</code> if you want it to be ragged right.
<code>\raggedX</code>	Text in paragraphed footnotes is justified, but you can use <code>\raggedX[⟨s⟩]+L+</code> if you want it to be ragged left, or <code>\raggedX[⟨s⟩]+R</code> if you want it to be ragged right.

4.3.9 Options for block of notes

<code>\txtbeforeXnotes</code>	You can add some text before critical notes with <code>\txtbeforeXnotes[⟨s⟩]{⟨text⟩}</code> .
<code>\beforeXnotes</code>	You can change the vertical space printed before the rule of the critical notes with <code>\beforeXnotes[⟨s⟩]{⟨l⟩}</code> . The default value is <code>1.2em plus .6em minus .6em</code> . Be careful, the standard L^AT_EX footnote rule, which is used by eledmac , decreases by 3pt. This 3pt decrease is not changed by this command..
<code>\beforenotesX</code>	You can change the vertical space printed before the rule of the familiar notes with <code>\beforenotesX[⟨s⟩]{⟨l⟩}</code> . The default value is <code>1.2em plus .6em minus .6em</code> . Be careful, the standard L^AT_EX footnote rule, which is used by eledmac , decreases 3pt. These 3pt are not changed by this command.
<code>\afterXrule</code>	You can change the vertical space printed after the rule of the critical notes with <code>\afterXrule[⟨s⟩]{⟨l⟩}</code> . The default value is <code>0pt</code> . Be careful, the standard L^AT_EX footnote rule, which is used by eledmac , adds 2.6pt. These 2.6pt are not changed by this command. Be careful with this setting: it can place notes by the page number, at the bottom of the page.
<code>\afterruleX</code>	You can change the vertical space printed after the rule of the familiar notes with <code>\beforenotesX[⟨s⟩]{⟨l⟩}</code> . The default value is <code>0pt</code> . Be careful, the standard L^AT_EX footnote rule, which is used by eledmac , adds 2.6pt. These 2.6pt are not changed by this command. Be careful with this setting: it can place notes by the page number, at the bottom of the page.
<code>\preXnotes</code>	You can set the space before the first series of critical notes printed on each page and set a different amount of space for subsequent the series on the page. You can do it with <code>\preXnotes{⟨l⟩}</code> . Default value is <code>0pt</code> . You can disable this feature by setting the length to <code>0pt</code> . Be careful with this setting: it can place notes by the page number, at the bottom of the page.
<code>\prenotesX</code>	You can want the space before the first printed (in a page) series of familiar notes not to be the same as before other series. Default value is <code>0pt</code> . You can

do it with `\prenotesX{<l>}`. You can disable this feature by setting the length to 0 pt.

`\maxhXnotes` Be careful with this setting: it could make the notes be written on the bottom pages number. By default, one series of critical notes can take 80% of the page size, before being broken to the next page. If you want to change the size use `\maxhXnotes[<s>]{<l>}`. Be careful : the length can't be flexible, and is relative to the the current font. For example, if you want the note to take, at most, 33 of the text height, do `\maxhXnotes{.33\textheight}`.

`\maxhnotesX` `\maxhnotesX[<s>]{<l>}` is the same as previous, but for familiar footnotes.

Be careful with the two previous commands. Actually, for technical purposes, one paragraphed note is considered as one block. Consequently, it can't be broken between two pages, even if you used these commands. The debug is in the todolist.

4.4 Page layout

You should set up the page layout parameters, and in particular the `\baselineskip` of the footnotes (this is done for you if you use the standard `\notefontsetup`), before you call any of these macros because their action depends on these; too much or too little space will be allotted for the notes on the page if these macros use the wrong values.¹⁶

If you use `eledpar` `\columns` macro, you can call :

- `\Xnoteswidthliketwocolumns[<s>]` to create critical notes with a two-column size width. Use `\Xnoteswidthliketwocolumns[<s>][false]` to disable it.
- `\notesXwidthliketwocolumns[<s>]` to create familiar notes with a two-column size width. Use `\notesXwidthliketwocolumns[<s>][false]` to disable it.

4.5 Fonts

One of the most important features of the appearance of the notes, and indeed of your whole document, will be the fonts used. We will first describe the commands that give you control over the use of fonts in the different structural elements of the document, especially within the notes, and then in subsequent sections specify how these commands are used.

For those who are setting up for a large job, here is a list of the complete set of `eledmac` macros relating to fonts that are intended for manipulation by the user: `\endashchar`, `\fullstop`, `\numlabfont`, and `\rbracket`.

`\numlabfont` Line numbers for the main text are usually printed in a smaller font in the margin. The `\numlabfont` macro is provided as a standard name for that font: it is initially defined as

¹⁶There is one tiny proviso about using paragraphed notes: you shouldn't force any explicit line-breaks inside such notes: do not use `\par`, `\break`, or `\penalty=-10000`. If you must have a line-break for some obscure reason, just suggest the break very strongly: `\penalty=-9999` will do the trick. Page 112 explains why this restriction is necessary.

`\newcommand{\numlabfont}{\normalfont\scriptsize}`

You might wish to use a different font if, for example, you preferred to have these line numbers printed using old-style numerals.

`\endashchar`
`\fullstop`
`\rbracket`

A relatively trivial matter relates to punctuation. In your footnotes, there will sometimes be spans of line numbers like this: 12–34, or lines with sub-line numbers like this: 55.6. The en-dash and the full stop are taken from the same font as the numbers, and it all works nicely. But what if you wanted to use old-style numbers, like 12 and 34? These look nice in an edition, but when you use the fonts provided by PLAIN T_EX they are taken from a math font which does not have the en-dash or full stop in the same places as a text font. If you (or your macros) just typed `$_oldstyle 12--34$` or `$_oldstyle 55.6$` you would get ‘12”34’ and ‘55▷6’. So we define `\endashchar` and `\fullstop`, which produce an en-dash and a full stop respectively from the normal document font, whatever font you are using for the numbers. These two macros are used in the macros which format the line numbers in the margins and footnotes, instead of explicit punctuation. We also define an `\rbracket` macro for the right square bracket printed at the end of the lemma in many styles of textual notes (including `eledmac`’s standard style). For polyglossia, when the lemma is RTL, the bracket automatically switches to a left bracket.

`\select@lemmafnt`

We will briefly discuss `\select@lemmafnt` here because it is important to know about it now, although it is not one of the macros you would expect to change in the course of a simple job. Hence it is ‘protected’ by having the @-sign in its name.

When you use the `\edtext` macro to mark a word in your text as a lemma, that word will normally be printed again in your apparatus. If the word in the text happens to be in a font such as italic or bold you would probably expect it to appear in the apparatus in the same font. This becomes an absolute necessity if the font is actually a different script, such as Arabic or Cyrillic. `\select@lemmafnt` does the work of decoding `eledmac`’s data about the fonts used to print the lemma in the main text and calling up those fonts for printing the lemma in the note.

`\select@lemmafnt` is a macro that takes one long argument—the cluster of line numbers passed to the note commands. This cluster ends with a code indicating what fonts were in use at the start of the lemma. `\select@lemmafnt` selects the appropriate font for the note using that font specifier.

`eledmac` uses `\select@lemmafnt` in a standard footnote format macro called `\normalfootfmt`. The footnote formats for each of the layers A to E are `\let` equal to `\normalfootfmt`. So all the layers of the footnotes are formatted in the same way.

4.6 Create a new series

If you need more than 5 series of critical footnotes you can create extra series, using `\newseries` command. For example to create G and H series `\newseriesG,H`.

5 Verse

In 1992 Wayne Sullivan¹⁷ wrote the `EDSTANZA` macros [Sul92] for typesetting verse in a critical edition. More specifically they were for handling poetry stanzas which use indentation to indicate rhyme or metre.

With Wayne Sullivan's permission the majority of this section has been taken from [Sul92]. Peter has made a few changes to enable his macros to be used in the L^AT_EX `ledmac`, and now in `eledmac`. package.

`\stanza` Use `\stanza` at the start of a stanza. Each line in a stanza is ended by an
`\&` ampersand (&), and the stanza itself is ended by putting `\&` at the end of the last
line.

Be careful: you must have NO space between the end of your verse and & or \&. In most cases, you will see no difference, but if your verse is exactly the same length as a line, then you will have an empty hanging verse.

`\stanzaindentbase` Lines within a stanza may be indented. The indents are integer multiples of
the length `\stanzaindentbase`, whose default value is 20pt.

`\setstanzaindentbase` In order to use the stanza macros, one must set the indentation values. First
the value of `\stanzaindentbase` should be set, unless the default value 20pt is
desired. Every stanza line indentation is a multiple of this.

To specify these multiples one invokes, for example
`\setstanzaindentbase{3,1,2,1,2}`.

The numerical entries must be whole numbers, 0 or greater, separated by commas without embedded spaces. The first entry gives the hanging indentation to be used if the stanza line requires more than one print line.

If it is known that each stanza line will fit on more than one print line, then this first entry should be 0; T_EX does less work in this case, but no harm ensues if the hanging indentation is not 0 but is never used.

If you want the hanging verse to be flush right, you can use `\hanginsymbol`: see p. 27.

Enumeration is by stanza lines, not by print lines. In the above example the lines are indented one unit, two units, one unit, two units, with 3 units of hanging indentation in case a stanza line is too long to fit on one print line.

5.1 Repeating stanza indents

Since version 0.13, if the indentation is repeated every n verses of the stanza, you can define only the n first indentations, and say they are repeated, defining the value of the `stanzaindentbase` counter at n . For example:

```
\setstanzaindentbase{5,1,0}
\setcounter{stanzaindentbase}{2}
```

is like

¹⁷Department of Mathematics, University College, Dublin 4, Ireland

```
\setstanzaindents{0,1,0,1,0,1,0,1,0,1,0}
```

Be careful: the feature change in eledmac 1.5.1. See Appendix A.2 p. 215.

If you don't use the `stanzaindentsrepetition` counter, make sure you have at least one more numerical entry in `\setstanzavalues` than the number of lines in the stanza.

If you want to disable this feature again, just put the counter to 0:

```
\setcounter{stanzaindentsrepetition}{0}
```

The macros make no restriction on the number of lines in a stanza. Stanza indentation values (and penalty values) obey T_EX's grouping conventions, so if one stanza among several has a different structure, its indentations (penalties) may be set within a group; the prior values will be restored when the group ends.

5.2 Stanza breaking

`\setstanzapenalties` When the stanzas run over several pages, it is often desirable that page breaks should arise between certain lines in the stanza, so a facility for including penalties after stanza lines is provided. If you are satisfied with the page breaks, you need not set the penalty values.

The command

```
\setstanzapenalties{1,5000,10100,5000,0}
```

results in a penalty of 5000 being placed after the first and third lines of the stanza, and a penalty of −100 after the second.

The first entry “1” is a control value. If it is zero, then no penalties are passed on to T_EX, which is the default. Values between 0 and 10000 are penalty values; values between 10001 and 20000 have 10000 subtracted and the result is given as a negative penalty. The mechanism used for indentations and penalties requires unsigned values less than 32768. No penalty is placed after the last line, so the final ,0 in then example above could be omitted. The control sequence `\endstanzaextra` can be defined to include a penalty. A penalty of 10000 will prevent a page break; such a penalty is included automatically where there is stanza hanging indentation. A penalty of −10000 (corresponding to the entry value 20000 in this context) forces a page break. Values in between act as suggestions as to the desirability of a page break at a given line. There is a subtle interaction between penalties and *glue*, so it may take some adjustment of skips and penalties to achieve the best results.

5.3 Hanging symbol

`\hangingsymbol` It's possible to insert a symbol in each line of hanging verse, as in French typography for ‘[’. To insert in eledmac, redefine macro `\hangingsymbol` with this code:

```
\renewcommand{\hangingsymbol}{[\,]}
```

You can also use it to force hanging verse to be flush right:

```
\renewcommand{\hangingsymbol}{\protect\hfill}
```

5.4 Long verse and page break

If you want to prevent page breaks inside long verses, use the option `nopbinverse` when loading package, or use `\lednopbinversetrue`. Read 16 p. 38 for further details.

5.5 Various tools

`\ampersand` If you need to print an & symbol in a stanza, use the `\ampersand` macro, not `\&` which will end the stanza.

`\endstanzaextra` The macro `\endstanzaextra`, if it is defined, is called at the end of a stanza. You could define this, for example, to add extra space between stanzas (by default there is no extra space between stanzas); if you are using the `memoir` class, it provides a length `\stanzaskip` which may come in handy.

`\startstanzahook` Similarly, if `\startstanzahook` is defined, it is called by `\stanza` at the start. This can be defined to do something.

`\flagstanza` Putting `\flagstanza[⟨len⟩]{⟨text⟩}` at the start of a line in a stanza (or elsewhere) will typeset `⟨text⟩` at a distance `⟨len⟩` before the line. The default `⟨len⟩` is `\stanzaindentbase`.

For example, to put a verse number before the first line of a stanza you could proceed along the lines:

```
\newcounter{stanzanum}
\setcounter{stanzanum}{0}
\newcommand*{\startstanzahook}{\refstepcounter{stanzanum}}
\newcommand{\numberit}{\flagstanza{\thestanzanum}}
...
\stanza
\numberit First line...&
    rest of stanza&

\stanza
\numberit First line, second stanza...
```

5.6 Hanging symbol

It's possible to insert a symbol on each line of hanging verse, as in French typography for '['. To insert in `eledmac`, redefine macro `\hangingsymbol` with this code:

```
\hangingsymbol \renewcommand{\hangingsymbol}{[\,]}
```

5.7 Text before/after verses

It is possible to add text, like a subtitle, before or after verse:

- `\stanza` command can take a optional argument (in brackets). Its content will be printed before the stanza.
- `&` can be replaced by `\newverse` with two optional arguments (in brackets). The first will be printed after the current verse, the second before the next verse.
- `\&` can take a optional argument (in brackets). Its content will be printed after the stanza.

6 Grouping

In a `minipage` environment L^AT_EX changes `\footnote` numbering from arabic to alphabetic and puts the footnotes at the end of the minipage.

minipage You can put numbered text with critical footnotes in a minipage and the footnotes are set at the end of the minipage.

You can also put familiar footnotes (see section 11) in a minipage but unlike with `\footnote` the numbering scheme is unaltered.

ledgroup Minipages, of course, aren't broken across pages. Footnotes in a `ledgroup` environment are typeset at the end of the environment, as with minipages, but the environment includes normal page breaks. The environment makes no change to the `textwidth` so it appears as normal text; it just might be that footnotes appear in the middle of a page, with text above and below.

ledgroupsize The `ledgroupsize` environment is similar to `ledgroup` except that you must specify a width for the environment, as with a minipage.
`\begin{ledgroupsize}[\langle pos \rangle]{\langle width \rangle}`.

The required `\langle width \rangle` argument is the text width for the environment. The optional `\langle pos \rangle` argument is for positioning numbered text within the normal `textwidth`. It may be one of the characters:

l (left) numbered text is flush left with respect to the normal `textwidth`. This is the default.

c (center) numbered text is in the center of the `textwidth`.

r (right) numbered text is flush right with respect to the normal `textwidth`.

Note that normal text, footnotes, and so forth are all flush left.

`\begin{ledgroupsize}{\textwidth}` is effectively the same as `\begin{ledgroup}`

7 Crop marks

The `eledmac` package does not provide crop marks. These are available with either the `memoir` class [Wil02] or the `crop` package.

8 Endnotes

`\doendnotes` `\doendnotes{<letter>}` closes the `.end` file that contains the text of the endnotes, if it's open, and prints one series of endnotes, as specified by a series-letter argument, e.g., `\doendnotes{A}`. `\endprint` is the macro that's called to print each note. It uses `\select@lemmafnt` to select fonts, just as the footnote macros do (see p. 100 above).

As endnotes may be printed at any point in the document they always start with the page number of where they were specified. The macro `\printnpnum{<num>}` is used to print these numbers. Its default definition is:

```
\newcommand*{\printnpnum}[1]{p.#1} }
```

`\noendnotes` If you aren't going to have any endnotes, you can say `\noendnotes` in your file, before the first `\beginnumbering`, to suppress the generation of an unneeded `.end` file.

9 Cross referencing

The package provides a simple cross-referencing facility that allows you to mark places in the text with labels, and generate page and line number references to those places elsewhere using those labels.

`\edlabel` First you place a label in the text using the command `\edlabel{<lab>}`. `<lab>` can be almost anything you like, including letters, numbers, punctuation, or a combination—anything but spaces; you might say `\edlabel{toves-3}`, for example.¹⁸

`\edpageref` Elsewhere in the text, either before or after the `\edlabel`, you can refer to its location via `\edpageref{<lab>}`, or `\lineref{<lab>}`, `\sublineref{<lab>}`, or `\pstartref{<lab>}`. These commands will produce, respectively, the page, line, sub-line and pstart on which the `\edlabel{<lab>}` command occurred.

An `\edlabel` command may appear in the main text, or in the first argument of `\edtext`, but not in the apparatus itself. But `\edpageref`, `\lineref`, `\sublineref`, `\pstartref` commands can also be used in the apparatus to refer to `\edlabels` in the text.

The `\edlabel` command works by writing macros to `LaTeX.aux` file. You will need to process your document through `LaTeX` twice in order for the references to be resolved.

You will be warned if you say `\edlabel{foo}` and `foo` has been used as a label before. The `ref` commands will return references to the last place in the file marked with this label. You will also be warned if a reference is made to an undefined label. (This will also happen the first time you process a document after adding a new `\edlabel` command: the auxiliary file will not have been updated yet.)

If you want to refer to a word inside an `\edtext{...}{...}` command, the `\edlabel` should be defined inside the first argument, e.g.,

¹⁸More precisely, you should stick to characters in the `TeX` categories of 'letter' and 'other'.

The `\edtext{creature\edlabel{elephant} was quite
unafraid}{\Afootnote{Of the mouse, that is.}}`

`\xpageref` However, there are situations in which you'll want `eledmac` to return a number
`\xlineref` without displaying any warning messages about undefined labels or the like: if
`\xsublineref` you want to use the reference in a context where \LaTeX is looking for a number,
`\xpstartref` such a warning will lead to a complaint that the number is missing. This is
the case for references used within the argument to `\linenum`, for example. For
this situation, three variants of the reference commands, with the `x` prefix, are
supplied: `\xpageref`, `\xlineref`, `\xsublineref` and `\xpstartref`. They have
these limitations:

- They will not tell you if the label is undefined.
- They must be preceded in the file by at least one of the four other cross-reference commands—e.g., a `\edlabel{foo}` command, even if you never refer to that label—since those commands can all do the necessary processing of the `.aux` file, and the `\x...` ones cannot.
- When `hyperref` is loaded, the `hyperref` link won't be added. (Indeed, it's not a limitation, but a feature.

`\xxref` The macros `\xxref` and `\edmakelabel` let you manipulate numbers and labels
in ways which you may find helpful in tricky situations.

The `\xxref{<lab1>}{<lab2>}` command generates a reference to a sequence of
lines, for use in the second argument of `\edtext`. It takes two arguments, both
of which are labels: e.g., `\xxref{mouse}{elephant}`. It calls `\linenum` (q.v.,
p.17 above) and sets the beginning page, line, and sub-line numbers to those of
the place where `\edlabel{mouse}` was placed, and the ending numbers to those
where `\edlabel{elephant}` occurs.

`\edmakelabel` Sometimes the `\edlabel` command cannot be used to specify exactly the
page and line desired—for example, if you want to refer to a page and line
number in another volume of your edition. In such cases, you can use the
`\edmakelabel{<lab>}{<numbers>}` macro so that you can 'roll your own' label.
For example, if you say '`\edmakelabel{elephant}{10|25|0}`' you will create
a new label, and a later call to `\edpageref{elephant}` would print '10' and
`\lineref{elephant}` would print '25'. The sub-line number here is zero. It is
usually best to collect your `\edmakelabel` statements near the top of your docu-
ment, so that you can see them at a glance.

`\label` The normal `\label`, `\ref` and `\pageref` macros may be used within num-
`\ref` bered text, and operate in the familiar fashion.
`\pageref`

10 Side notes

The `\marginpar` command does not work in numbered text. Instead the package
provides for non-floating sidenotes in either margin.

`\ledinnernote` `\ledinnernote{<text>}` will put `<text>` into the inner margin level with where the command was issued. Similarly, `\ledouternote{<text>}` puts `<text>` in the outer margin.

`\ledleftnote` `\ledsidenote{<text>}` will put `<text>` into the margin specified by the current setting of `\sidenotemargin{<location>}`. The permissible value for `<location>` is one out of the list `left`, `right`, `inner`, or `outer`, for example `\sidenotemargin{outer}`. The package's default setting is `\sidenotemargin{right}` to typeset `\ledsidenotes` in the right hand margin. This is the opposite to the default margin for line numbers. The style for a `\ledsidenote` follows that for a `\ledleftnote` or a `\ledrightnote` depending on the margin it is put in.

If two, say, `\ledleftnote`, commands are called in the same line the second `<text>` will obliterate the first. There is no problem though with having both a left and a right sidenote on the same line.

`\ledlsnotewidth` The left sidenote text is put into a box of width `\ledlsnotewidth` and the right text into a box of width `\ledrsnotewidth`. These are initially set to the value of `\marginparwidth`.

`\ledrsnotewidth`

`\rightnoteupfalse` By default, Sidenotes are placed to align with the last line of the note to which it refers. If you want them to be placed to align with the first line of the note to which it refers, use `\leftnoteupfalse` (for left note) and/or `\rightnoteupfalse` (for right note).

`\leftnoteupfalse`

`\ledlsnotesep` The texts are put a distance `\ledlsnotesep` (or `\ledrsnotesep`) into the left (or right) margin. These lengths are initially set to the value of `\linenumsep`.

`\ledrsnotesep`

`\ledlsnotefontsetup` These macros specify how the sidenote texts are to be typeset. The initial definitions are:

`\ledrsnotefontsetup`

```

\newcommand*{\ledlsnotefontsetup}{\raggedleft\footnotesize}% left
\newcommand*{\ledrsnotefontsetup}{\raggedright\footnotesize}% right

```

These can of course be changed to suit.

`\sidenotesep` If you have two or more sidenotes for the same line, they are separated by a comma. But if you want to change this separator, you can redefine the macro `\sidenotesep`.

11 Familiar footnotes

The `footmisc` package [Fai03] by Robin Fairbairns has an option whereby sequential footnote marks in the text can be separated by commas^{3,4} like so. As a convenience `eledmac` provides this automatically.

`\multfootsep` `\multfootsep` is used as the separator between footnote markers. Its default definition is:

```

\providecommand*{\multfootsep}{\textsuperscript{\normalfont,}}

```

and can be changed if necessary.

`\footnoteA` As well as the standard L^AT_EX footnotes generated via `\footnote`, the package also provides five series of additional footnotes called `\footnoteA` through `\footnoteE`

`\footnoteB`

`\footnoteC`

`\footnoteD`

`\footnoteE`

`\footnoteE`. These have the familiar marker in the text, and the marked text at the foot of the page can be formatted using any of the styles described for the critical footnotes. Note that the ‘regular’ footnotes have the series letter at the end of the macro name whereas the critical footnotes have the series letter at the start of the name.

`\footnormalX` Each of the `\foot...X` macros takes one argument which is the series letter (e.g., B). `\footnormalX` is the typical footnote format. With `\footparagraphX` the series is typeset a one paragraph, with `\foottwocolX` the notes are in two columns, and are in three columns with `\foothreecolX`.
`\thefootnoteA` As well as using the `\foot...X` macros to specify the general footnote arrangement for a series, each series uses a set of macros for styling the marks. The mark numbering scheme is defined by the `\thefootnoteA` macro; the default is:
`\bodyfootmarkA`
`\footfootmarkA`

`\renewcommand*{\thefootnoteA}{\arabic{footnoteA}}`
 The appearance of the mark in the text is controlled by `\bodyfootmarkA` which is defined as:

```
\newcommand*{\bodyfootmarkA}{%
  \hbox{\textsuperscript{\normalfont\@nameuse{@thefnmarkA}}}}
```

The command `\footfootmarkA` controls the appearance of the mark at the start of the footnote text. It is defined as:

```
\newcommand*{\footfootmarkA}{\textsuperscript{\@nameuse{@thefnmarkA}}}
```

There are similar command triples for the other series.

Additional footnote series can be easily defined: you just have to use `\newseries`, defined above (see 4.6 p.24).

11.1 Position of the familiar footnotes

`\fnpos` There is a historical incoherence in (e)ledmac. The familiar footnotes are before
`\mpfnpos` the critical footnotes in a normal page, but after in a minipage or in a ledgroup. However, it is possible to change the relative position of both types of footnotes. If you want to have familiar footnotes after critical footnotes in a normal page, use:

```
\fnpos{critical-familiar}
```

Or, if you want a minipage or ledgroup to have critical footnotes after familiar footnotes, use:

```
\mpfnpos{familiar-critical}
```

12 Indexing

`\edindex` L^AT_EX provides the `\index{<item>}` command for specifying that `<item>` and the current page number should be added to the raw index (`idx`) file. The `\edindex{<item>}` macro can be used in numbered text to specify that `<item>` and the current page & linenum should be added to the raw index file.

If the `memoir` class or the `imakeidx` package is used then the macro takes an optional argument, which is the name of a raw index file. For example `\edindex[line]{item}` will use `line.idx` as the raw file instead of `\jobname.idx`.

The minimal version of `imakeidx` package to be used is the version 1.3a uploaded on CTAN on 2013/07/11.

Be careful with the order of package loading and index declaration. You must use this order:

1. Load `imakeidx`.
2. Load `eledmac`.
3. Declare the index with the macro `\makeindex` of `imakeidx`.

`\pagelinesep` The page & lineNumber combination is written as `page\pagelinesep line`, where the default definition is `\newcommand{\pagelinesep}{-}` so that an item on page 3, line 5 will be noted as being at 3-5. You can renew `\pagelinesep` to get a different separator (but it just so happens that `-` is the default separator used by the MAKEINDEX program).

`\edindexlab` The `\edindex` process uses a `\label/\ref` mechanism to get the correct line number. It automatically generates labels of the form `\label{\edindexlab N}`, where N is a number, and the default definition of `\edindexlab` is:
`\newcommand*{\edindexlab}{\&}`
 in the hopes that this will not be used by any other labels (`\edindex`'s labels are like `\label{\&27}`). You can change `\edindexlab` to something else if you need to.

13 Tabular material

L^AT_EX's normal `tabular` and `array` environments cannot be used where line numbering is being done; more precisely, they can be used but with odd results, so don't use them. However, `eledmac` provides some simple tabulation environments that can be line numbered. The environments can also be used in normal unnumbered text.

`edarrayl` There are six environments; the `edarray*` environments are for math and
`edarrayc` `edtabular*` for text entries. The final `l`, `c`, or `r` in the environment names indicate
`edarrayr` that the entries will be flushleft (`l`), centered (`c`) or flushright (`r`). There is
`edtabularl` no means of specifying different formats for each column, nor for specifying a
`edtabularc` fixed width for a column. The environments are centered with respect to the
`edtabularr` surrounding text.

```
\begin{edtabularc}
1 & 2 & 3 \\
a & bb & ccc \\
AAA & BB & C
\end{edtabularc}
```

1	2	3
a	bb	ccc
AAA	BB	C

Entries in the environments are the same as for the normal `array` and `tabular` environments but there must be no ending `\\` at the end of the last row. *There*

Macros like `\edtext` can be used as part of an entry. For example:

produces the following parallel pair of verses.

```
\begin{edtabularrr}
1          & 2      & 3      & 4      & 5 \\
Q          & & fd & h      & qwertziohg \\
```

```

v                & wptz & x & y & vb \\
g                & nnn & \edrowfill{3}{5}{\upbracefill} & & \\
\edrowfill{1}{3}{\downbracefill} & & & pq & dgh \\
k                & & & 1 & co & ghweropjklmnbvcxys \\
1                & 2 & 3 & \edrowfill{4}{5}{\hrulefill} & \\
\end{tabularr}

```

1	2	3	4	5
Q		fd	h	qwertziohg
v	wptz	x	y	vb
g	nnn	$\underbrace{\hspace{10em}}$		
			pq	dgh
k		1	co ghweropjklmnbvcxys	
1	2	3	$\underline{\hspace{10em}}$	

You can also define your own ‘fill’. For example:

```

\newcommand*{\upbracketfill}{%
  \vrule height 4pt depth 0pt\hrulefill\vrule height 4pt depth 0pt}

```

is a fill like `\upbracefill` except it has the appearance of a (horizontal) bracket instead of a brace. It can be used like this:

```

\begin{edarrayc}
1 & 2 & & & 3 & 4 & \\
a & & \edrowfill{2}{3}{\upbracketfill} & & d & & \\
A & B & & & C & D & \\
\end{edarrayc}

```

1	2	3	4
a	$\underbrace{\hspace{1.5em}}$		d
A	B	C	D

`\edatleft` `\edatleft[$\langle math \rangle$]{ $\langle symbol \rangle$ }{ $\langle halfheight \rangle$ }` typesets the math $\langle symbol \rangle$ as `\left<symbol>` with the optional $\langle math \rangle$ centered before it. The $\langle symbol \rangle$ is twice $\langle halfheight \rangle$ tall. The `\edatright` macro is similar and it typesets `\right<symbol>` with $\langle math \rangle$ centered after it.

```

\begin{edarrayc}
& 1 & 2 & 3 & & \\
& 4 & 5 & 6 & & \\
\edatleft[left =]{\{ }{1.5\baselineskip}
& 7 & 8 & 9 & & \\
\edatright[= right]{\} }{1.5\baselineskip}
\end{edarrayc}

```

$$left = \begin{pmatrix} 1 & 2 & 3 \\ 4 & 5 & 6 \\ 7 & 8 & 9 \end{pmatrix} = right$$

`\edbeforetab` `\edbeforetab{⟨text⟩}{⟨entry⟩}`, where `⟨entry⟩` is an entry in the leftmost column, typesets `⟨text⟩` left justified before the `⟨entry⟩`. Similarly `\edaftertab{⟨entry⟩}{⟨text⟩}`, where `⟨entry⟩` is an entry in the rightmost column, typesets `⟨text⟩` right justified after the `⟨entry⟩`.

For example:

```
\begin{edarrayl}
      A & 1 & 2 & 3 & \\\
\edbeforetab{Before}{B} & 1 & 3 & 6 & \\\
      C & 1 & 4 & \edaftertab{8}{After} & \\\
      D & 1 & 5 & 0 & \\
\end{edarrayl}
```

	A 1 2 3	
Before	B 1 3 6	
	C 1 4 8	After
	D 1 5 0	

`\edvertline` The macro `\edvertline{⟨height⟩}` draws a vertical line `⟨height⟩` high (contrast this with `\edatright` where the size argument is half the desired height).

`\edvertdots`

```
\begin{edarrayr}
a & b & C & d & & \\\
v & w & x & y & & \\\
m & n & o & p & & \\\
k & & L & cvb & \edvertline{4pc} \\
\end{edarrayr}
```

<i>a</i>	<i>b</i>	<i>C</i>	<i>d</i>	
<i>v</i>	<i>w</i>	<i>x</i>	<i>y</i>	
<i>m</i>	<i>n</i>	<i>o</i>	<i>p</i>	
<i>k</i>		<i>L</i>	<i>cvb</i>	

The `\edvertdots` macro is similar to `\edvertline` except that it produces a vertical dotted instead of a solid line.

14 Sectioning commands

The standard sectioning command (`\chapter`, `\section` etc.) can be used inside a numbered text. But the line which contains it won't be numbered, and you can't add critical notes inside. In the past (between versions 1.1.0 and 1.12.0), these following commands were provided:

- `\ledchapter[⟨text⟩]{⟨critical text⟩}`
- `\ledchapter*`
- `\ledsection[⟨text⟩]{⟨critical text⟩}`
- `\ledsection*`
- `\ledsubsection[⟨text⟩]{⟨critical text⟩}`
- `\ledsubsection*`
- `\ledsubsubsection[⟨text⟩]{⟨critical text⟩}`
- `\ledsubsubsection*`

These commands are deprecated, and won't be maintained anymore, because of a bad conception. Since version 1.12.0, you have to use the following commands:

- `\eledchapter[⟨text⟩]{⟨critical text⟩}`
- `\eledchapter*`
- `\eledsection[⟨text⟩]{⟨critical text⟩}`
- `\eledsection*`
- `\eledsubsection[⟨text⟩]{⟨critical text⟩}`
- `\eledsubsection*`
- `\eledsubsubsection[⟨text⟩]{⟨critical text⟩}`
- `\eledsubsubsection*`

Which are equivalent to the L^AT_EX commands. Each individual command must be called alone in a `\pstart... \pend`:

```
\pstart
\eledsection*{xxxx\ledsidenote{section}}
\pend
\pstart
\eledsubsection*{xxxx\ledsidenote{sub}}
\pend
\pstart
normal text
\pend
```

At the first run, you will see only the text. It's normal. At the second run, you will see the formatting. And consequently, at the third run, you will see the table of contents.

For technical reasons, the page break before `\elechapter` can't be added automatically. You have to insert it manually via `\beforeeledchapter`, which must be called outside of a numbering section. If you aren't going to have any `\eledxxx` commands, you can say `\noeledsec` in your file, before the first `\beginnumbering`, to suppress the generation of unneeded `.eledsec` file.

`\noeledsec`

15 Quotation environments

The `quotation` and `quote` environment can be used so that same definition/note appears both inside and outside a numbered section. The typographical consequences will resemble the outside numbered sections, based on the styles of the *book* class. However, if you use a package that redefines these environments, these redefinitions won't be available inside the numbering section. You must open the quotation environments inside a `\start-\pend` block, not outside. A quotation environment **MUST** not be opened immediately after a `\pstart` and **MUST** not be closed immediately before a `\pend`.

In some case, you don't want these environments be redefined in numbered section. You can load the package with the option `noquotation` to prevent this redefinition.

16 Page breaks

`Eledmac` and `eledpar` break pages automatically. However, you may sometimes want to either force page breaks or prevent them. The packages provide two macros:

- `\ledpb` adds a page break.
- `\lednopb` prevents a page break, by adding one line to the current page if needed.

These commands have effect only at the second run.

These two commands take effect at the beginning of line in which they are called. For example, if you call `\ledpb` at l. 444, the l. 443 will be at the p. n , and the l. 444 at the p. $n + 1$. However you can change the behavior, and decide they will have effect after the end of the line, adding `\ledpbsetting{after}` at the beginning of your file (better: in your preamble). With the previous example, the l. 444 will be at the p. n and the l. 445 will be at the p. $n + 1$.

If you are using `eledpar` to typeset parallel pages you must use `\lednopb` on both sides in the two corresponding lines. This is especially important when you are using stanzas; otherwise the pages will run out of sync. You can also decide to prevent page breaks between two lines of a long verse. To do this, use `nopbinverse` when loading package, or add `\lednopbinversetrue` in the beginning of your file (better: in your preamble). This feature works only with verse of 2 lines, not more. It works at the third run, or at fourth run with `eledpar`. By default, when a long verse runs normally between two pages, a page break will be placed at the beginning of the verse. However, if you have added `\ledpbsetting{after}`, the page break will be placed at the end of the long verse, and the page containing the long verse will have one extra line.

17 Miscellaneous

`\extensionchars` When the package assembles the name of the auxiliary file for a section, it prefixes `\extensionchars` to the section number. This is initially defined to be empty, but you can add some characters to help distinguish these files if you like; what you use is likely to be system-dependent. If, for example, you said `\renewcommand{\extensionchars}{!}`, then you would get temporary files called `jobname.!1`, `jobname.!2`, etc.

`\ifledfinal` The package can take options. The option ‘final’, which is the default is for final typesetting; this sets `\ifledfinal` to TRUE. The other option, ‘draft’, may be useful during earlier stages and sets `\ifledfinal` to FALSE.

`\showlemma` The lemma within the text is printed via `\showlemma{lemma}`. Normally, or with the ‘final’ option, the definition of `\showlemma` is:

```
\newcommand*{\showlemma}[1]{#1}
```

so it just produces its argument. With the ‘draft’ option it is defined as

```
\newcommand*{\showlemma}[1]{\textit{#1}}
```

so that its argument is typeset in an italic font, which may make it easier to check that all lemmas have been treated.

If you would prefer some other style, you could put something like this in the preamble:

```
\ifledfinal\else
  \renewcommand{\showlemma}[1]{\textbf{#1}}% or simply ...[1]{#1}
\fi
```

17.1 Known and suspected limitations

In general, `eledmac`’s system for adding marginal line numbers breaks anything that makes direct use of the `LATEX` insert system, which includes `marginpars`, `footnotes` and `floats`.

However, you can use both `\footnote` and the familiar footnote series notes in numbered text. A `\marginpar` in numbered text will throw away its contents and send a warning message to the terminal and log file, but will do no harm.

`\parshape` cannot be used within numbered text, except in a very restricted way.

`\ballast` `LATEX` is a three-pass system, but even after a document has been processed three times, there are some tricky situations in which the page breaks decided by `TEX` never settle down. At each successive run, `eledmac` may oscillate between two different sets of page decisions. To stop this happening, should it arise, Wayne Sullivan suggested the inclusion of the quantity `\ballast`. The amount of `\ballast` will be subtracted from the penalties which apply to the page breaks calculated on the *previous* run through `TEX`, thus reinforcing these breaks. So if you find your page breaks oscillating, say

```
\setcounter{ballast}{100}
```

or some such figure, and with any luck the page breaks will settle down. Luckily, this problem doesn’t crop up at all often.

The restriction on explicit line-breaking in paragraphed footnotes, mentioned in a footnote 16, p. 23, and described in more detail on p. 112, really is a nuisance if that's something you need to do. There are some possible solutions, described by Michael Downes, but this area remains unsatisfactory.

L^AT_EX has a reputation for putting things in the wrong margin after a page break. The `eledmac` package does nothing to improve the situation — in fact it just makes it more obvious if numbered text crosses a page (or column) boundary and the numbers are meant to flip from side to side. Try and keep the numbers in the same margin all the time. Another aspect of TeX's page breaking mechanism is that when numbering lines by the page, the first few numbers after a page break may continue as though the lines were still on the previous page.

`\pageparbreak`

If you can't resist flipping the numbers or numbering by the page, then you might find that judicious use of `\pageparbreak` may help if numbering goes awry across a page (or column) break. It tries to force TeX into partitioning the current paragraph into two invisibly joined paragraphs with a page break between them. Insert the command between the last word on one page and the first word on the next page. If later you change something earlier in the document the natural page break may be in a different place, and you will have to adjust the location of `\pageparbreak` accordingly.

`\footfudgefiddle`

For paragraphed footnotes T_EX has to estimate the amount of space required. If it underestimates this then the notes may get too long and run off the bottom of the text block. `\footfudgefiddle` can be increased from its default 64 (say to 68) to increase the estimate. You have to use `\renewcommand` for this, like:

```
\renewcommand{\footfudgefiddle}{68}
```

Help, suggestions and corrections will be gratefully received.

17.2 Use with other packages

Because of `eledmac`'s complexity it may not play well with other packages. In particular `eledmac` is sensitive to commands in the arguments to the `\edtext` and `*footnote` macros (this is discussed in more detail in section 22, and in particular the discussion about `\no@expands` and `\morenoexpands`). You will have to see what works or doesn't work in your particular case.

It is possible that `eledmac` and the `hyperref` package may work together. I have not tried this combination but past experience with `hyperref` suggests that cooperation is unlikely; `hyperref` changes many L^AT_EX internals and `eledmac` does things that are not normally seen in L^AT_EX.

If you want to use the option *bottom* of the `footmisc` package, you must load this package *before* the `eledmac` package.

`\morenoexpands`

You can define the macro `\morenoexpands` to modify macros that you call within `\edtext`. Because of the way `eledmac` numbers the lines the arguments to `\edtext` can be processed more than once and in some cases a macro should only be processed once. One example is the `\colorbox` macro from the `color` package, which you might use like this:

```
... \edtext{\colorbox{mycolor}{lemma}}{\Afootnote{... \colorbox{...}}}
```


If you actually try this¹⁹ you will find L^AT_EX whinging ‘Missing { inserted’, and then things start to fall apart. The trick in this case is to specify either:

```
\newcommand{\morenoexpands}{\let\colorbox=0}
```

or

```
\makeatletter
\newcommand{\morenoexpands}{\let\colorbox\@secondoftwo}
\makeatother
```

(\@secondoftwo is an internal L^AT_EX macro that takes two arguments and throws away the first one.) The first incantation lets color show in both the main text and footnotes whereas the second one shows color in the main text but kills it in the lemma and footnotes. On the other hand if you use \textcolor instead, like

```
... \edtext{\textcolor{mycolor}{lemma}}{\Afootnote{... \textcolor{...}}}
```

there is no need to fiddle with \morenoexpands as the color will naturally be displayed in both the text and footnotes. To kill the color in the lemma and footnotes, though, you can do:

```
\makeatletter
\newcommand{\morenoexpands}{\let\textcolor\@secondoftwo}
\makeatother
```

It took me a little while to discover all this. If you run into this sort of problem you may have to spend some time experimenting before hitting on a solution.

17.3 Parallel typesetting

Peter Wilson has developed the *Ledpar* package as an extension to *eledmac* specifically for parallel typesetting of critical texts. This also cooperates with the *babel* / *polyglossia* packages for typesetting in multiple languages. The package has been called *eledpar* since September 2012.

He also developed the *ledarab* package for handling parallel Arabic text in critical editions. However, this package is not maintained by Maïeul Rouquette. You should use the capabilities of a modern TeX processor, like Xe(La)TeX

¹⁹Reported by Dirk-Jan Dekker in the CTT thread ‘Incompatibility of “color” package’ on 2003/08/28.

17.4 Notes for EDMAC users

If you have never used EDMAC, ignore this section. If you have used EDMAC and are starting on a completely new document, ignore this section. Only read this section if you are converting an original EDMAC document to use `eledmac`.

The package still provides the original `\text` command, but it is (a) deprecated, and (b) its name has been changed²⁰ to `\critext`; use the `\edtext` macro instead. However, if you do use `\critext` (the new name for `\text`), the following is a reminder.

`\critext` Within numbered paragraphs, footnotes and endnotes are generated by forms of the `\critext` macro:

```
\critext{⟨lemma⟩}⟨commands⟩/
```

The `⟨lemma⟩` argument is the lemma in the main text: `\critext` both prints this as part of the text, and makes it available to the `⟨commands⟩` you specify to generate notes. The `/` at the end terminates the command; it is part of the macro's definition so that spaces after the macro will be treated as significant.

For example:

<code>I saw my friend \critext{Smith}</code>	1 I saw my friend
<code>\Afootnote{Jones C, D.}/</code>	2 Smith on Tuesday.
<code>on Tuesday.</code>	<u>2 Smith]</u> Jones C, D.

The lemma `Smith` is printed as part of this sentence in the text, and is also made available to the footnote that specifies a variant, `Jones C, D`. The footnote macro is supplied with the line number at which the lemma appears in the main text.

The `⟨lemma⟩` may contain further `\critext` commands. Nesting makes it possible to print an explanatory note on a long passage together with notes on variants for individual words within the passage. For example:

<code>\critext{I saw my friend</code>	1 I saw my friend
<code>\critext{Smith}{\Afootnote{Jones</code>	2 Smith on Tuesday.
<code>C, D.}/ on Tuesday.}</code>	<u>2 Smith]</u> Jones C, D.
<code>\Bfootnote{The date was</code>	<u>1–2 I saw my friend</u>
<code>July 16, 1954.}</code>	<code>Smith on Tuesday.] The</code>
<code>/</code>	<code>date was July 16, 1954.</code>

However, `\critext` cannot handle overlapping but unnested notes—for example, one note covering lines 10–15, and another covering 12–18; a `\critext` that starts in the `⟨lemma⟩` argument of another `\critext` must end there, too. (The `\lemma` and `\linenum` commands may be used to generate overlapping notes if necessary.)

The second argument of the `\critext` macro, `⟨commands⟩`, is the same as the second argument to the `\edtext` macro.

It is possible to define aliases for `\critext`, which can be easier to type. You can make a single character substitute for `\critext` by saying this:

²⁰A name like `\text` is likely to be defined by other L^AT_EX packages (it certainly is by the AMS packages) and it seems sensible to try and avoid clashes with other definitions.

```
\catcode'\<=\active
\let<=\critext
```

Then you might say `<{Smith}\variant{Jones}/`. This of course destroys the ability to use `<` in any new macro definitions, so long as it remains in effect; hence it should be used with care.

Changing the character at the end of the command requires more work:

```
\catcode'\<=\active
\def\xtext#1#2>{\critext{#1}{#2}/}
\let<=\xtext
```

This allows you to say `<{Smith}\Afootnote{Jones}>`.

Aliases for `\critext` of the first kind shown here also can't be nested—that is, you can't use the alias in the text that forms the first argument to `\critext`. (See section 22 to find out why.) Aliases of the second kind may be nested without any problem.

If you really have to use `\critext` in any of the tabular or array environments, then `\edtext` must not be used in the same environment. If you use `\critext` in one of these environments then you have to issue the declaration `\usingcritext` beforehand. The declaration `\usingedtext` must be issued to revert to the default assumption that `\edtext` will be used.

18 Implementation overview

We present the `eledmac` code in roughly the order in which it's used during a run of \TeX . The order is *exactly* that in which it's read when you load The `eledmac` package, because the same file is used to generate this manual and to generate the \LaTeX package file. Most of what follows consists of macro definitions, but there are some commands that are executed immediately—especially at the start of the code. The documentation generally describes the code from the point of view of what happens when the macros are executed, though. As each macro is introduced, its name is printed in the margin.

We begin with the commands you use to start and stop line numbering in a section of text (Section 19). Next comes the machinery for writing and reading the auxiliary file for each section that helps us count lines, and for creating list macros encoding the information from that file (Section 21); this auxiliary file will be read at the start of each section, to create those list macros, and a new version of the file will be started to collect information from the body of the section.

Next are commands for marking sections of the text for footnotes (Section 22), followed by the macros that take each paragraph apart, attach the line numbers and insertions, and send the result to the vertical list (Section 23). The footnote commands (Section 24) and output routine (Section 32) finish the main part of the processing; cross-referencing (Section 33) and endnotes (Section 30) complete the story.

In what follows, macros with an `@` in their name are more internal to the workings of `eledmac` than those made up just of ordinary letters, just as in `PLAIN \TeX` (see *The TeXbook*, p.344). You are meant to be able to make free with ordinary macros, but the '`@`' ones should be treated with more respect, and changed only if you are pretty sure of what you are doing.

19 Preliminaries

We try and use `l@d` in macro names to help avoid name clashes, but this is not a hard and fast rule. For example, if an original `EDMAC` macro includes `edmac` We will simply change that to `eledmac`.

Announce the name and version of the package, which is targetted for $\text{\LaTeX}2\epsilon$.

```
1 (*code)
2 \NeedsTeXFormat{LaTeX2e}
3 \ProvidesPackage{eledmac}[2014/10/27 v1.14.0 LaTeX port of EDMAC]%
```

Generally, these are the modifications to the original. `EDMAC` code:

- Replace as many `\def`'s by `\newcommand`'s as possible to avoid overwriting \LaTeX macros.
- Replace user-level \TeX counts by \LaTeX counters.
- Use the \LaTeX font handling mechanisms.
- Use \LaTeX messaging and file facilities.

19.1 Package options

`\iflabeledfinal` Use this to remember which option is used, set and execute the options with final as the default.

```

\ifparapparatus@
\ifnoquotation@
\iflabeledgroup
\ifwidthliketwocolumns
\iflabeledseccolnumber
4 \newif\iflabeledfinal
5 \newif\ifparapparatus@
6 \newif\ifnoquotation@
7 \newif\iflabeledgroup
8 \newif\ifwidthliketwocolumns%
9 \newif\iflabeledseccolnumber
10 \newif\iflabeledgroup
11 \parapparatus@false
12 \DeclareOption{noquotation}{\noquotation@true}
13 \DeclareOption{final}{\labeledfinaltrue}
14 \DeclareOption{draft}{\labeledfinalfalse}
15 \DeclareOption{parapparatus}{\parapparatus@true}
16 \DeclareOption{nopbinverse}{\labelednopbinversetrue}
17 \DeclareOption{labeledseccolnumber}{\labeledseccolnumbertrue}
18 \DeclareOption{widthliketwocolumns}{\widthliketwocolumnstrue}%
19 \ExecuteOptions{final}

```

Use the starred form of `\ProcessOptions` which executes options in the order listed in the source file: class options, then listed package options, so a package option can override a class option with the same name. This was suggested by Dan Luecking in the `ctt` thread *Class/package option processing*, on 27 February 2004.

```

20 \ProcessOptions*\relax
21

```

Loading package *xargs* to declare commands with optional arguments. *Etoolbox* is also used to make code clearer - for example, in dynamic command names (which can replace `\csname` etc.). Use *suffix* to declare commands with a starred version, *xstring* to work with strings and *iflutex* to test if LuaLaTeX is running, and *ragged2e* to manage ragging for paragraphed notes.

```

22 \RequirePackage{xargs}
23 \RequirePackage{etoolbox}
24 \reserveinserts{32}
25 \RequirePackage{suffix}
26 \RequirePackage{xstring}
27 \RequirePackage{iflutex}
28 \RequirePackage{ragged2e}

```

`\if@RTL` The `\if@RTL` is defined by the *bidi* package, which is sometimes loaded by *polyglossia*. But we define it if the *bidi* package is not loaded.

```

29 \ifdefined\if@RTL\else\newif\if@RTL\fi

```

`\showlemma` `\showlemma{<lemma>}` typesets the lemma text in the body. It depends on the option.

```

30 \iflabeledfinal

```

```

31 \newcommand*{\showlemma}[1]{#1}
32 \else
33 \newcommand*{\showlemma}[1]{\underline{#1}}
34 \fi
35

```

19.2 Packages loading

Loading package *xargs* to declare commands with optional arguments. *Etoolbox* is also used to make code clearer - for example, in dynamic command names (which can replace `\csname` etc.). Use *suffix* to declare commands with a starred version, *xstring* to work with strings and *iflutex* to test if LuaLaTeX is running, and *ragged2e* to manage ragging for paragraphed notes.

```

36 \RequirePackage{xargs}
37 \RequirePackage{etoolbox}
38 \reserveinserts{32}
39 \RequirePackage{suffix}
40 \RequirePackage{xstring}
41 \RequirePackage{ifluatex}
42 \RequirePackage{ragged2e}

```

19.3 Boolean flags

`\ifl@dmemoir` Define a flag for if the memoir class has been used.

```

43 \newif\ifl@dmemoir
44 \@ifclassloaded{memoir}{\l@dmemoirtrue}{\l@dmemoirfalse}
45

```

`\ifl@imakeidx` Define a flag for if the imakeidx package has been used.

```

46 \newif\ifl@imakeidx
47 \@ifpackageloaded{imakeidx}{\l@imakeidxtrue}{\l@imakeidxfalse}

```

`\if@RTL` The `\if@RTL` is defined by the bidi package, which is sometimes loaded by *polyglossia*. But we define it if the bidi package is not loaded.

```

48 \ifcsdef{if@RTL}{\newif\if@RTL}

```

19.4 Messages

All the messages are grouped here as macros. This saves TeX's memory when the same message is repeated and also lets them be edited easily.

`\eledmac@warning` Write a warning message.

```

49 \newcommand{\eledmac@warning}[1]{\PackageWarning{eledmac}{#1}}

```

`\eledmac@error` Write an error message.

```

50 \newcommand{\eledmac@error}[2]{\PackageError{eledmac}{#1}{#2}}

```

```

\led@err@NumberingStarted
d@err@NumberingNotStarted 51 \newcommand*{\led@err@NumberingStarted}{%
umberingShouldHaveStarted 52 \eledmac@error{Numbering has already been started}{\@ehc}}
53 \newcommand*{\led@err@NumberingNotStarted}{%
54 \eledmac@error{Numbering was not started}{\@ehc}}
55 \newcommand*{\led@err@NumberingShouldHaveStarted}{%
56 \eledmac@error{Numbering should already have been started}{\@ehc}}

\led@mess@NotesChanged
57 \newcommand*{\led@mess@NotesChanged}{%
58 \typeout{eledmac reminder: }%
59 \typeout{ The number of the footnotes in this section
60 has changed since the last run.}%
61 \typeout{ You will need to run LaTeX two more times
62 before the footnote placement}%
63 \typeout{ and line numbering in this section are
64 correct.}}

led@mess@SectionContinued
65 \newcommand*{\led@mess@SectionContinued}[1]{%
66 \message{Section #1 (continuing the previous section)}}

d@err@LineationInNumbered
67 \newcommand*{\led@err@LineationInNumbered}{%
68 \eledmac@error{You can't use \string\lineation\space within
69 a numbered section}{\@ehc}}

\led@warn@BadLineation
led@warn@BadLinenummargin 70 \newcommand*{\led@warn@BadLineation}{%
\led@warn@BadLockdisp 71 \eledmac@warning{Bad \string\lineation\space argument}}
\led@warn@BadSublockdisp 72 \newcommand*{\led@warn@BadLinenummargin}{%
73 \eledmac@warning{Bad \string\linenummargin\space argument}}
74 \newcommand*{\led@warn@BadLockdisp}{%
75 \eledmac@warning{Bad \string\lockdisp\space argument}}
76 \newcommand*{\led@warn@BadSublockdisp}{%
77 \eledmac@warning{Bad \string\sublockdisp\space argument}}

\led@warn@NoLineFile
78 \newcommand*{\led@warn@NoLineFile}[1]{%
79 \eledmac@warning{Can't find line-list file #1}}

arn@BadAdvancelineSubline
d@warn@BadAdvancelineLine 80 \newcommand*{\led@warn@BadAdvancelineSubline}{%
81 \eledmac@warning{\string\advanceline\space produced a sub-line
82 number less than zero.}}
83 \newcommand*{\led@warn@BadAdvancelineLine}{%
84 \eledmac@warning{\string\advanceline\space produced a line
85 number less than zero.}}

```

```

\led@warn@BadSetline
\led@warn@BadSetlinenum 86 \newcommand*{\led@warn@BadSetline}{%
                        87 \eledmac@warning{Bad \string\setline\space argument}}
                        88 \newcommand*{\led@warn@BadSetlinenum}{%
                        89 \eledmac@warning{Bad \string\setlinenum\space argument}}

\led@err@PstartNotNumbered
\led@err@PstartInPstart 90 \newcommand*{\led@err@PstartNotNumbered}{%
\led@err@PendNotNumbered 91 \eledmac@error{\string\pstart\space must be used within a
\led@err@PendNoPstart 92 numbered section}{\@ehc}}
\led@err@AutoparNotNumbered 93 \newcommand*{\led@err@PstartInPstart}{%
94 \eledmac@error{\string\pstart\space encountered while another
95 \string\pstart\space was in effect}{\@ehc}}
96 \newcommand*{\led@err@PendNotNumbered}{%
97 \eledmac@error{\string\pend\space must be used within a
98 numbered section}{\@ehc}}
99 \newcommand*{\led@err@PendNoPstart}{%
100 \eledmac@error{\string\pend\space must follow a \string\pstart}{\@ehc}}
101 \newcommand*{\led@err@AutoparNotNumbered}{%
102 \eledmac@error{\string\autopar\space must be used within a
103 numbered section}{\@ehc}}

\led@warn@BadAction
104 \newcommand*{\led@warn@BadAction}{%
105 \eledmac@warning{Bad action code, value \next@action.}}

\led@warn@DuplicateLabel
\led@warn@RefUndefined 106 \newcommand*{\led@warn@DuplicateLabel}[1]{%
107 \eledmac@warning{Duplicate definition of label ‘#1’ on page \the\pageno.}}
108 \newcommand*{\led@warn@RefUndefined}[1]{%
109 \eledmac@warning{Reference ‘#1’ on page \the\pageno\space undefined.
110 Using ‘000’.}}

\led@warn@NoMarginpars
111 \newcommand*{\led@warn@NoMarginpars}{%
112 \eledmac@warning{You can’t use \string\marginpar\space in numbered text}}

\led@warn@BadSidenotemargin
113 \newcommand*{\led@warn@BadSidenotemargin}{%
114 \eledmac@warning{Bad \string\sidenotemmargin\space argument}}

\led@warn@NoIndexFile
115 \newcommand*{\led@warn@NoIndexFile}[1]{%
116 \eledmac@warning{Undefined index file #1}}

\led@warn@AddfootinsXobsolete
\led@warn@Addfootinsobsolete 117 \newcommand{\led@warn@AddfootinsXobsolete}{%
118 \eledmac@warning{AddfootinsX is obsolete in eledmac 1.0. Use newseries instead.}}

```



```

119 }%
120 \newcommand{\led@warn@AddfootinsObsolete}{%
121   \eledmac@warning{Addfootins is obsolete in eledmac 1.0. Use newseries instead.}%
122 }%

\led@warn@SeriesStillExist

123 \newcommand{\led@warn@SeriesStillExist}[1]{%
124   \eledmac@warning{Series #1 is still existing !}%
125 }%

\led@err@ManySidenotes
\led@err@ManyLeftnotes 126 \newcommand{\led@err@ManySidenotes}{%
\led@err@ManyRightnotes 127   \ifledRcol%
128     \eledmac@warning{\itemcount@ space sidenotes on line \the\line@numR space p. \the\page@numR}%
129   \else%
130     \eledmac@warning{\itemcount@ space sidenotes on line \the\line@num space p. \the\page@num}%
131   \fi%
132 }%
133 \newcommand{\led@err@ManyLeftnotes}{%
134   \ifledRcol%
135     \eledmac@warning{\itemcount@ space leftnotes on line \the\line@numR space p. \the\page@numR}%
136   \else%
137     \eledmac@warning{\itemcount@ space leftnotes on line \the\line@num space p. \the\page@num}%
138   \fi%
139 }%
140 \newcommand{\led@err@ManyRightnotes}{%
141   \ifledRcol%
142     \eledmac@warning{\itemcount@ space rightnotes on line \the\line@numR space p. \the\page@numR}%
143   \else%
144     \eledmac@warning{\itemcount@ space rightnotes on line \the\line@num space p. \the\page@num}%
145   \fi%
146 }%

\war@FalseverseDeprecated
\led@war@ledxxxDeprecated 147 \newcommand{\led@war@FalseverseDeprecated}{%
148   \eledmac@warning{\string\falseverse space deprecated. Look at \string\newverse space instead.}%
149 }%
150 \newcommand{\led@war@ledxxxDeprecated}[1]{%
151   \eledmac@warning{\string\led#1 space deprecated. Look at \string\led#1 instead.}%
152 }%

\led@err@TooManyColumns
\led@err@UnequalColumns 153 \newcommand*\led@err@TooManyColumns{%
\led@err@LowStartColumn 154   \eledmac@error{Too many columns}{\@ehc}
\led@err@HighEndColumn 155 \newcommand*\led@err@UnequalColumns{%
\led@err@ReverseColumns 156   \eledmac@error{Number of columns is not equal to the number
157     in the previous row (or \protect\ \space forgotten?)}{\@ehc}
158 \newcommand*\led@err@LowStartColumn{%
159   \eledmac@error{Start column is too low}{\@ehc}

```

```

160 \newcommand*\led@err@HighEndColumn}{%
161   \eledmac@error{End column is too high}{\@ehc}}
162 \newcommand*\led@err@ReverseColumns}{%
163   \eledmac@error{Start column is greater than end column}{\@ehc}}

```

`\led@err@EdtextWithoutFootnote`

```

164 \newcommand{\led@err@EdtextWithoutFootnote}{%
165   \eledmac@error{edtext without Xfootnote. Check syntaxis.}{\@ehd}%
166 }%

```

`\led@error@ImakeidxAfterEledmac`

```

167 \newcommand{\led@error@ImakeidxAfterEledmac}{%
168   \eledmac@error{Imakeidx must be loaded before eledmac.}{\@ehd}%
169 }%

```

19.5 Gobbling

`\@gobblethree`

```

\@gobblefour 170 \providecommand*\@gobblethree}[3]{}
171 \providecommand*\@gobblefour}[4]{}

```

Here, we define some commands which gobble their arguments.

19.6 Miscellaneous commands

`\linenumberlist` The code for the `\linenumberlist` mechanism was given to Peter Wilson by Wayne Sullivan on 2004/02/11.

Initialize it as `\empty`

```

172 \let\linenumberlist=\empty
173

```

`\@l@tempcnta`

In imitation of L^AT_EX, we create a couple of scratch counters.

`\@l@tempcntb`

L^AT_EX already defines `\@tempcnta` and `\@tempcntb` but Peter Wilson have found in the past that it can be dangerous to use these (for example one of the AMS packages did something nasty to the `ccaption` package's use of one of these).

```

174 \newcount\@l@tempcnta \newcount\@l@tempcntb

```

20 Sectioning commands

`\section@num`

You use `\beginnumbering` and `\endnumbering` to begin and end a line-numbered section of the text; the pair of commands may be used as many times as you like within one document to start and end multiple, separately line-numbered sections. L^AT_EX will maintain and display a 'section number' as a count named `\section@num` that counts how many `\beginnumbering` and `\resumenummering` commands have appeared; it needn't be related to the logical divisions of your text.

`\extensionchars` Each section will read and write an associated ‘line-list file’, containing information used to do the numbering; the file will be called `\jobname.nn`, where `nn` is the section number. However, you may direct that an extra string be added before the `nn` in that filename, in order to distinguish these temporary files from others: that string is called `\extensionchars`. Initially it’s empty, since different operating systems have greatly varying ideas about what characters are permitted in file names. So `\renewcommand{\extensionchars}{-}` gives temporary files called `jobname.-1`, `jobname.-2`, etc.

```

175 \newcount\section@num
176 \section@num=0
177 \let\extensionchars=\empty

```

`\ifnumbering` The `\ifnumbering` flag is set to `true` if we’re within a numbered section (that is, between `\beginnumbering` and `\endnumbering`). You can use `\ifnumbering` in your own code to check whether you’re in a numbered section, but don’t change the flag’s value.

```

178 \newif\ifnumbering

```

`\ifnumberingR` In preparation for the `eledpar` package, these are related to the ‘left’ text of parallel texts (when `\ifl@dpairing` is `TRUE`). They are explained in the `eledpar` manual.

```

\ifl@dpairing
\ifl@dpaging
\l@dpagingtrue 179 \newif\ifl@dpairing
\l@dpagingfalse 180 \l@dpairingfalse
\l@dpairingtrue 181 \newif\ifl@dpaging%
\l@dpairingfalse 182 \l@dpagingfalse%
\ifpst@rtedL 183 \newif\ifpst@rtedL
\pst@rtedLtrue 184 \pst@rtedLfalse
\pst@rtedLfalse 185 \newcount\l@dnumpstartsL
\l@dnumpstartsL \ifl@dpairing is set to true in the Rightside environment. It must be distinguished
\ifl@dpairing from \ifl@dpairing@ which is set to true when a right line is processed, in \Pages
\ifl@dpairing@ or \Columns.
186 \newif\ifl@dpairing
187 \newif\ifl@dpairing@

```

The `\ifnumberingR` flag is set to `true` if we’re within a right text numbered section.

```

188 \newif\ifnumberingR

```

`\beginnumbering` `\beginnumbering` begins a section of numbered text. When it’s executed we increment the section number, initialize our counters, send a message to your terminal, and call macros to start the lineation machinery and endnote files.

`\initnumbering@reg` The initializations here are trickier than they look. `\line@list@stuff` will use all of the counters that are zeroed here when it assembles the line-list and other lists of information about the lineation. But it will do all of this locally and within a group, and when it’s done the lists will remain but the counters will return to zero. Those same counters will then be used as we process the text of this section, but the assignments will be made globally. These initializations actually apply

to both uses, though in all other respects there should be no direct interaction between the use of these counters and variables in the two processing steps.

For parallel processing :

- zero `\l@dnumpstartsL` — the number of chunks to be processed.
- set `\ifpst@rtedL` to FALSE.

```

189 \newcommand*{\beginnumbering}{%
190   \ifnumbering
191     \led@err@NumberingStarted
192     \endnumbering
193   \fi
194   \global\numberingtrue
195   \global\advance\section@num \@ne
196   \initnumbering@reg
197   \message{Section \the\section@num }%
198   \line@list@stuff{\jobname.\extensionchars\the\section@num}%
199   \l@dend@stuff
200   \setcounter{pstart}{1}
201   \ifl@dpairing
202     \global\l@dnumpstartsL \z@
203     \global\pst@rtedLfalse

```

The tools for section's title commands are called:

- Define old (deprecated) sectioning commands.
- Define an empty list of pstart number where sectioning commands are called.
- Input auxiliary file with the description of section titles.
- Open the same auxiliary file to write in.

```

204   \else
205     \begingroup
206     \initnumbering@sectcmd
207     \ifwidthliketwocolumns%
208       \csuse{setwidthliketwocolumns@\columns@position}%
209       \csuse{setpositionliketwocolumns@\columns@position}%
210     \fi%
211   \fi
212   \gdef\eled@sections@@{}%
213   \if@noeled@sec\else%
214     \makeatletter\inputIfFileExists{\jobname.eledsec\the\section@num}{-}{\makeatother}%
215     \immediate\openout\eled@sectioning@out=\jobname.eledsec\the\section@num\relax%
216   \fi%
217 }
218 \newcommand*{\initnumbering@reg}{%
219   \global\pst@rtedLfalse
220   \global\l@dnumpstartsL \z@
221   \global\absline@num \z@

```

```

222 \gdef\normal@page@break{}
223 \gdef\l@prev@pb{}
224 \gdef\l@prev@nopb{}
225 \global\line@num \z@
226 \global\subline@num \z@
227 \global\@lock \z@
228 \global\sub@lock \z@
229 \global\sublines@false
230 \global\let\next@page@num=\relax
231 \global\let\sub@change=\relax
232 \resetprevline@
233 \resetprevpage@num
234 }
235

```

`\endnumbering` `\endnumbering` must follow the last text for a numbered section. It takes care of notifying you when changes have been noted in the input that require running the file through again to move everything to the right place.

```

236 \def\endnumbering{%
237   \ifnumbering
238     \global\numberingfalse
239     \normal@pars
240     \ifl@dpairing
241       \global\pst@rtedLfalse
242     \else
243       \ifx\insertlines@list\empty\else
244         \global\noteschanged@true
245       \fi
246       \ifx\line@list\empty\else
247         \global\noteschanged@true
248       \fi
249     \fi
250     \ifnoteschanged@
251       \led@mess@NotesChanged
252     \fi
253   \else
254     \led@err@NumberingNotStarted
255   \fi
256   \autoparfalse
257   \if@noeled@sec\else%
258     \immediate\closeout\eled@sectioning@out%
259   \fi%
260   \ifl@dpairing\else
261     \global\l@dnumpstartsL=\z@%
262   \endgroup
263 \fi
264 }

```

`\pausenumbering` The `\pausenumbering` macro is just the same as `\endnumbering`, but with the `\resumenumbering`

`\ifnumbering` flag set to `true`, to show that numbering continues across the gap.²¹

```
265 \newcommand{\pausenumbering}{%
266   \ifautopar\global\autopar@pausetrue\fi%
267   \endnumbering\global\numberingtrue}
```

The `\resumenumbering` macro is a bit more involved, but not much. It does most of the same things as `\beginnumbering`, but without resetting the various counters. Note that no check is made by `\resumenumbering` to ensure that `\pausenumbering` was actually invoked.

```
268 \newcommand*{\resumenumbering}{%
269   \ifnumbering
270     \ifautopar@pause\autopar\fi
271     \global\pst@rtedLtrue
272     \global\advance\section@num \@ne
273     \led@mess@SectionContinued{\the\section@num}%
274     \line@list@stuff{\jobname.\extensionchars\the\section@num}%
275     \l@dend@stuff
276     \ifl@dpairing\else%
277       \begingroup%
278       \initnumbering@sectcmd%
279       \ifwidthliketwocolumns%
280         \csuse{setwidthliketwocolumns@\columns@position}%
281         \csuse{setpositionliketwocolumns@\columns@position}%
282       \fi%
283     \fi%
284   \else
285     \led@err@NumberingShouldHaveStarted
286     \endnumbering
287     \beginnumbering
288   \fi}
289
290
```

21 Line counting

21.1 Choosing the system of lineation

Sometimes you want line numbers that start at 1 at the top of each page; sometimes you want line numbers that start at 1 at each `\pstart`; other times you want line numbers that start at 1 at the start of each section and increase regardless of page breaks. `eledmac` can do it either way, and you can switch from one to the other within one work. But you have to choose one or the other for all line numbers and line references within each section. Here we will define internal codes for these systems and the macros you use to select them.

<pre>\ifbypstart@ \byppstart@true \byppstart@false \ifbypage@ \bypage@true \bypage@false</pre>	<p>The <code>\ifbypage@</code> and <code>\ifbypstart@</code> flag specify the current lineation system:</p> <hr style="width: 20%; margin-left: 0;"/> <p>²¹Our thanks to Wayne Sullivan, who suggested the idea behind these macros.</p>
--	---

- line-of-page: `bypstart@ = false` and `bypage@ = true`.
- line-of-pstart: `bypstart@ = true` and `bypage@ = false`.

`eledmac` will use the line-of-section system unless instructed otherwise.

```
291 \newif\ifbypage@
292 \newif\ifbypstart@
```

`\lineation` `\lineation{<word>}` is the macro you use to select the lineation system. Its argument is a string: either `page` or `section` or `pstart`.

```
293 \newcommand*{\lineation}[1]{%
294   \ifnumbering
295     \led@err@LineationInNumbered
296   \else
297     \def\@tempa{#1}\def\@tempb{page}%
298     \ifx\@tempa\@tempb
299       \global\bypage@true
300       \global\bypstart@false
301       \pstartinfootnote[] [false]
302     \else
303       \def\@tempb{pstart}%
304       \ifx\@tempa\@tempb
305         \global\bypage@false
306         \global\bypstart@true
307         \pstartinfootnote
308       \else
309         \def\@tempb{section}
310         \ifx\@tempa\@tempb
311           \global\bypage@false
312           \global\bypstart@false
313           \pstartinfootnote[] [false]
314         \else
315           \led@warn@BadLineation
316         \fi
317       \fi
318     \fi
319   \fi}}
```

`\linenummargin` `\linenummargin{<word>}` You call `\linenummargin{<word>}` to specify which margin you want your line numbers in; it takes one argument, a string. You can put the line numbers in the same margin on every page using `left` or `right`; or you can use `inner` or `outer` to get them in the inner or outer margins. (These last two options assume that even-numbered pages will be on the left-hand side of every opening in your book.) You can change this within a numbered section, but the change may not take effect just when you'd like; if it's done between paragraphs nothing surprising should happen.

The selection is recorded in the count `\line@margin`: 0 for left, 1 for right, 2 for outer, and 3 for inner.

```
320 \newcount\line@margin
```

```

321 \newcommand*{\linenummargin}[1]{%
322   \l@getline@margin{#1}%
323   \ifnum\l@dttempcntb>\m@ne
324     \global\line@margin=\l@dttempcntb
325   \fi}}
326 \newcommand*{\l@getline@margin}[1]{%
327   \def\@tempa{#1}\def\@tempb{left}%
328   \ifx\@tempa\@tempb
329     \l@dttempcntb \z@
330   \else
331     \def\@tempb{right}%
332     \ifx\@tempa\@tempb
333       \l@dttempcntb \@ne
334     \else
335       \def\@tempb{outer}%
336       \ifx\@tempa\@tempb
337         \l@dttempcntb \tw@
338       \else
339         \def\@tempb{inner}%
340         \ifx\@tempa\@tempb
341           \l@dttempcntb \thr@@
342         \else
343           \led@warn@BadLinenummargin
344           \l@dttempcntb \m@ne
345         \fi
346       \fi
347     \fi
348   \fi}
349

```

`\c@firstlinenum` The following counters tell `eledmac` which lines should be printed with line numbers. `firstlinenum` is the number of the first line in each section that gets a number; `linenumincrement` is the difference between successive numbered lines. The initial values of these counters produce labels on lines 5, 10, 15, etc. `linenumincrement` must be at least 1.

```

350 \newcounter{firstlinenum}
351   \setcounter{firstlinenum}{5}
352 \newcounter{linenumincrement}
353   \setcounter{linenumincrement}{5}

```

`\c@firstsublinenum` The following parameters are just like `firstlinenum` and `linenumincrement`, but
`\c@sublinenumincrement` for sub-line numbers. `sublinenumincrement` must be at least 1.

```

354 \newcounter{firstsublinenum}
355   \setcounter{firstsublinenum}{5}
356 \newcounter{sublinenumincrement}
357   \setcounter{sublinenumincrement}{5}
358

```

`\firstlinenum` These macros can be used to set the corresponding counters.
`\linenumincrement`
`\firstsublinenum`
`\sublinenumincrement`


```

359 \newcommand*{\firstlinenum}[1]{\setcounter{firstlinenum}{#1}}
360 \newcommand*{\linenumincrement}[1]{\setcounter{linenumincrement}{#1}}
361 \newcommand*{\firstsublinenum}[1]{\setcounter{firstsublinenum}{#1}}
362 \newcommand*{\sublinenumincrement}[1]{\setcounter{sublinenumincrement}{#1}}
363

```

`\lockdisp` When line locking is being used, the `\lockdisp{<word>}` macro specifies whether
`\lock@disp` a line number—if one is due to appear—should be printed on the first printed line
`\l@dgetlock@disp` or on the last, or by all of them. Its argument is a word, either **first**, **last**, or
all. Initially, it is set to **first**.

`\lock@disp` encodes the selection: 0 for first, 1 for last, 2 for all.

```

364 \newcount\lock@disp
365 \newcommand{\lockdisp}[1]{%
366   \l@dgetlock@disp{#1}%
367   \ifnum\@l@tempcntb>\m@ne
368     \global\lock@disp=\@l@tempcntb
369   \else
370     \led@warn@BadLockdisp
371   \fi}}
372 \newcommand*{\l@dgetlock@disp}[1]{
373   \def\@tempa{#1}\def\@tempb{first}%
374   \ifx\@tempa\@tempb
375     \@l@tempcntb \z@
376   \else
377     \def\@tempb{last}%
378     \ifx\@tempa\@tempb
379       \@l@tempcntb \@ne
380     \else
381       \def\@tempb{all}%
382       \ifx\@tempa\@tempb
383         \@l@tempcntb \tw@
384       \else
385         \@l@tempcntb \m@ne
386       \fi
387     \fi
388   \fi}
389

```

`\sublockdisp` The same questions about where to print the line number apply to sub-lines, and
`\sublock@disp` these are the analogous macros for dealing with the problem.

```

390 \newcount\sublock@disp
391 \newcommand{\sublockdisp}[1]{%
392   \l@dgetlock@disp{#1}%
393   \ifnum\@l@tempcntb>\m@ne
394     \global\sublock@disp=\@l@tempcntb
395   \else
396     \led@warn@BadSublockdisp
397   \fi}}
398

```

`\linenumberstyle` We provide a mechanism for using different representations of the line numbers, not just the normal arabic.
`\linenumrep`
`\linenumr@p` NOTE: In v0.7 `\linenumrep` and `\sublinenumrep` replaced the internal
`\sublinenumberstyle` `\linenumr@p` and `\sublinenumr@p`.
`\sublinenumrep` `\linenumberstyle` and `\sublinenumberstyle` are user level macros for setting the number representation (`\linenumrep` and `\sublinenumrep`) for line and sub-line numbers.
`\sublinenumr@p`

```

399 \newcommand*{\linenumberstyle}[1]{%
400   \def\linenumrep##1{\@nameuse{##1}{##1}}
401 \newcommand*{\sublinenumberstyle}[1]{%
402   \def\sublinenumrep##1{\@nameuse{##1}{##1}}
   Initialise the number styles to arabic.
403 \linenumberstyle{arabic}
404 \let\linenumr@p\linenumrep
405 \sublinenumberstyle{arabic}
406 \let\sublinenumr@p\sublinenumrep
407
```

`\leftlinenum` `\leftlinenum` and `\rightlinenum` are the macros that are called to print marginal line numbers on a page, for left- and right-hand margins respectively.
`\rightlinenum`
`\linenumsep` They're made easy to access and change, since you may often want to change the styling in some way. These standard versions illustrate the general sort of thing that will be needed; they're based on the `\leftheadline` macro in *The TeXbook*, p. 416.
`\numlabfont`
`\ledlinenum`

Whatever these macros output gets printed in a box that will be put into the appropriate margin without any space between it and the line of text. You'll generally want a kern between a line number and the text, and `\linenumsep` is provided as a standard way of storing its size. Line numbers are usually printed in a smaller font, and `\numlabfont` is provided as a standard name for that font. When called, these macros will be executed within a group, so font changes and the like will remain local.

`\ledlinenum` typesets the line (and subline) number.

The original `\numlabfont` specification is equivalent to the L^AT_EX `\scriptsize` for a 10pt document.

```

408 \newlength{\linenumsep}
409 \setlength{\linenumsep}{1pc}
410 \newcommand*{\numlabfont}{\normalfont\scriptsize}
411 \newcommand*{\ledlinenum}{%
412   \numlabfont\linenumrep{\line@num}%
413   \ifsublines@
414     \ifnum\subline@num>0\relax
415       \unskip\fullstop\sublinenumrep{\subline@num}%
416       \fi
417   \fi}
418 \newcommand*{\leftlinenum}{%
419   \ledlinenum
420   \kern\linenumsep}

```

```

421 \newcommand*{\rightlinenum}{%
422   \kern\linenumsep
423   \ledlinenum}
424

```

21.2 List macros

Reminder: compare these with the L^AT_EX list macros in case they would be suitable instead.

We will make heavy use of lists of information, which will be built up and taken apart by the following macros; they are adapted from *The TeXbook*, pp. 378–379, which discusses their use in more detail.

These macros consume a large amount of the run-time of this code. We intend to replace them in a future version, and in anticipation of doing so have defined their interface in such a way that it is not sensitive to details of the underlying code.

\list@create The **\list@create** macro creates a new list. In this version of **eledmac** this macro doesn't do anything beyond initializing an empty list macro, but in future versions it may do more.

```

425 \newcommand*{\list@create}[1]{\global\let#1=\empty}

```

\list@clear The **\list@clear** macro just initializes a list to the empty list; in this version of **eledmac** it is no different from **\list@create**.

```

426 \newcommand*{\list@clear}[1]{\global\let#1=\empty}

```

\xright@appenditem **\xright@appenditem** expands an item and appends it to the right end of a list macro. We want the expansion because we'll often be using this to store the current value of a counter. **\xright@appenditem** creates global control sequences, like **\xdef**, and uses two temporary token-list registers, **\@toksa** and **\@toksb**.

```

427 \newtoks\led@toksa \newtoks\led@toksb
428 \global\led@toksa={\}
429 \long\def\xright@appenditem#1\to#2{%
430   \global\led@toksb=\expandafter{#2}%
431   \xdef#2{\the\led@toksb\the\led@toksa\expandafter{#1}}%
432   \global\led@toksb={}}

```

\xleft@appenditem **\xleft@appenditem** expands an item and appends it to the left end of a list macro; it is otherwise identical to **\xright@appenditem**.

```

433 \long\def\xleft@appenditem#1\to#2{%
434   \global\led@toksb=\expandafter{#2}%
435   \xdef#2{\the\led@toksa\expandafter{#1}\the\led@toksb}%
436   \global\led@toksb={}}

```

\gl@p The **\gl@p** macro removes the leftmost item from a list and places it in a control sequence. You say **\gl@p\l\to\z** (where **\l** is the list macro, and **\z** receives the left item). **\l** is assumed nonempty: say **\ifx\l\empty** to test for an empty **\l**. The control sequences created by **\gl@p** are all global.

```

437 \def\gl@p#1\to#2{\expandafter\gl@poff#1\gl@poff#1#2}
438 \long\def\gl@poff\#1#2\gl@poff#3#4{\gdef#4{#1}\gdef#3{#2}}
439

```

21.3 Line-number counters and lists

Footnote references using line numbers rather than symbols can't be generated in one pass, because we don't know the line numbers till we ship out the pages. It would be possible if footnotes were never keyed to more than one line; but some footnotes gloss passages that may run for several lines, and they must be tied to the first line of the passage glossed. And even one-line passages require two passes if we want line-per-page numbering rather than line-per-section numbering.

So we run \LaTeX over the text several times, and each time save information about page and line numbers in a 'line-list file' to be used during the next pass. At the start of each section—whenever `\beginnumbering` is executed—the line-list file for that section is read, and the information from it is encoded into a few list macros.

We need first to define the different line numbers that are involved in these macros, and the associated counters.

`\line@num` The count `\line@num` stores the line number that's used in marginal line numbering and in notes: counting either from the start of the page or from the start of the section, depending on your choice for this section. This may be qualified by `\subline@num`.

```
440 \newcount\line@num
```

`\subline@num` The count `\subline@num` stores a sub-line number that qualifies `\line@num`. For example, line 10 might have sub-line numbers 1, 2 and 3, which might be printed as lines 10.1, 10.2, 10.3.

```
441 \newcount\subline@num
```

`\ifsublines@` We maintain an associated flag, `\ifsublines@`, to tell us whether we're within a sub-line range or not.

`\sublines@true`

`\sublines@false`

You may wonder why we don't just use the value of `\subline@num` to determine this—treating anything greater than 0 as an indication that sub-lineation is on. We need a separate flag because sub-lineation can be used together with line-number locking in odd ways: several pieces of a logical line might be interrupted by pieces of sub-lineated text, and those sub-line numbers should not return to zero until the next change in the major line number. This is common in the typesetting of English Renaissance verse drama, in which stage directions are given sub-line numbers: a single line of verse may be interrupted by several stage directions.

```
442 \newif\ifsublines@
```

`\absline@num` The count `\absline@num` stores the absolute number of lines since the start of the section: that is, the number we've actually printed, no matter what numbers we attached to them. This value is never printed on an output page, though `\line@num` will often be equal to it. It is used internally to keep track of where

notes are to appear and where new pages start: using this value rather than `\line@num` is a lot simpler, because it doesn't depend on the lineation system in use.

```
443 \newcount\absline@num
```

We'll be calling `\absline@num` numbers 'absolute' numbers, and `\line@num` and `\subline@num` numbers 'visible' numbers.

`\@lock` The counts `\@lock` and `\sub@lock` tell us the state of line-number and sub-line-number locking. 0 means we're not within a locked set of lines; 1 means we're at the first line in the set; 2, at some intermediate line; and 3, at the last line.

```
444 \newcount\@lock
```

```
445 \newcount\sub@lock
```

`\line@list` Now we can define the list macros that will be created from the line-list file. We will maintain the following lists:

`\insertlines@list`
`\actionlines@list`
`\actions@list`

- `\line@list`: the page and line numbers for every lemma marked by `\edtext`. There are seven pieces of information, separated by vertical bars:

1. the starting page,
2. line, and
3. sub-line numbers, followed by the
4. ending page,
5. line, and
6. sub-line numbers, and then the
7. font specifier for the lemma.

These line numbers are all visible numbers. The font specifier is a set of four codes for font encoding, family, series, and shape, separated by / characters. Thus a lemma that started on page 23, line 35 and went on until page 24, line 3 (with no sub-line numbering), and was typeset in a normal roman font would have a line list entry like this:

```
23|35|0|24|3|0|OT1/cmr/m/n.
```

There is one item in this list for every lemma marked by `\edtext`, even if there are several notes to that lemma, or no notes at all. `\edtext` reads the data in this list, making it available for use in the text of notes.

- `\insertlines@list`: the line numbers of lines that have footnotes or other insertions. These are the absolute numbers where the corresponding lemmas begin. This list contains one entry for every footnote in the section; one lemma may contribute no footnotes or many footnotes. This list is used by `\add@inserts` within `\do@line`, to tell it where to insert notes.
- `\actionlines@list`: a list of absolute line numbers at which we are to perform special actions; these actions are specified by the `\actions@list` list defined below.

- `\actions@list`: action codes corresponding to the line numbers in `\actionlines@list`. These codes tell `eledmac` what action it's supposed to take at each of these lines. One action, the page-start action, is generated behind the scenes by `eledmac` itself; the others, for specifying sub-lineation, line-number locking, and line-number alteration, are generated only by explicit commands in your input file. The page-start and line-number-alteration actions require arguments, to specify the new values for the page or line numbers; instead of storing those arguments in another list, we have chosen the action-code values so that they can encode both the action and the argument in these cases. Action codes greater than -1000 are page-start actions, and the code value is the page number; action codes less than -5000 specify line numbers, and the code value is a transformed version of the line number; action codes between these two values specify other actions which require no argument.

Here is the full list of action codes and their meanings:

Any number greater than -1000 is a page-start action: the line number associated with it is the first line on a page, and the action number is the page number. (The cutoff of -1000 is chosen because negative page-number values are used by some macro packages; we assume that page-number values less than -1000 are not common.) Page-start action codes are added to the list by the `\page@action` macro, which is (indirectly) triggered by the workings of the `\page@start` macro; that macro should always be called in the output routine, just before the page contents are assembled. `eledmac` calls it in `\pagecontents`.

The action code -1001 specifies the start of sub-lineation: meaning that, starting with the next line, we should be advancing `\subline@num` at each start-of-line command, rather than `\line@num`.

The action code -1002 specifies the end of sub-lineation. At the next start-of-line, we should clear the sub-line counter and start advancing the line number. The action codes for starting and ending sub-lineation are added to the list by the `\sub@action` macro, as called to implement the `\startsub` and `\endsub` macros.

The action code -1003 specifies the start of line number locking. After the number for the current line is computed, it will remain at that value through the next line that has an action code to end locking.

The action code -1004 specifies the end of line number locking.

The action code -1005 specifies the start of sub-line number locking. After the number for the current sub-line is computed, it will remain at that value through the next sub-line that has an action code to end locking.

The action code -1006 specifies the end of sub-line number locking.

The four action codes for line and sub-line number locking are added to the list by the `\do@lockon` and `\do@lockoff` macros, as called to implement the `\startlock` and `\endlock` macros.

An action code of -5000 or less sets the current visible line number (either the line number or the sub-line number, whichever is currently being advanced) to a specific positive value. The value of the code is $-(5000 + n)$, where n is the value (always ≥ 0) assigned to the current line number. Action codes of this type are added to the list by the `\set@line@action` macro, as called to implement the `\advanceline` and `\setline` macros: this action only occurs when the user has specified some change to the line numbers using those macros. Normally `eledmac` computes the visible line numbers from the absolute line numbers with reference to the other action codes and the settings they invoke; it doesn't require an entry in the action-code list for every line.

Here are the commands to create these lists:

```
446 \list@create{\line@list}
447 \list@create{\insertlines@list}
448 \list@create{\actionlines@list}
449 \list@create{\actions@list}
450
```

```
\page@num We'll need some counts while we read the line-list, for the page number and the
\endpage@num ending page, line, and sub-line numbers. Some of these will be used again later
\endline@num on, when we are acting on the data in our list macros.
\endsubline@num
451 \newcount\page@num
452 \newcount\endpage@num
453 \newcount\endline@num
454 \newcount\endsubline@num
```

```
\ifnoteschanged@ If the number of the footnotes in a section is different from what it was during
\noteschanged@true the last run, or if this is the very first time you've run LATEX, on this file, the
\noteschanged@false information from the line-list used to place the notes will be wrong, and some
notes will probably be misplaced. When this happens, we prefer to give a single
error message for the whole section rather than messages at every point where we
notice the problem, because we don't really know where in the section notes were
added or removed, and the solution in any case is simply to run LATEX two more
times; there's no fix needed to the document. The \ifnoteschanged@ flag is set
if such a change in the number of notes is discovered at any point.
```

```
455 \newif\ifnoteschanged@
```

```
\resetprevline@ Inside the apparatus, at each note, the line number is stored in a macro called
\prevlineX, where X is the letter of the current series. This macro is called when
using \numberonlyfirstinline. This macro must be reset at the same time as
the line number. The \resetprevline@ does this resetting for every series.
```

```
\resetprevline@
456 \newcommand*{\resetprevline@}{%
457 \def\do##1{\global\csundef{prevline##1}}%
458 \dolistloop{\@series}%
459 }
```

`\resetprevpage@num` Inside the apparatus, at each note, the page number is stored in a macro called `\prevpageX@num`, where X is the letter of the current series. This macro is called when using `\parafootsep`. This macro must be reset at the beginning of each numbered section. The `\resetprevpage@` command resets this macro for every series.

`\resetprevpage@`

```
460 \newcommand*{\resetprevpage@num}{%
461   \def\do##1{\ifcsdef{prevpage##1@num}{\global\csname prevpage##1@num\endcsname=0}{}}%
462   \dolistloop{\@series}%
463 }
```

21.4 Reading the line-list file

`\read@linelist` `\read@linelist{<file>}` is the control sequence that's called by `\beginnumbering` (via `\line@list@stuff`) to open and process a line-list file; its argument is the name of the file.

```
464 \newread\@inputcheck
465 \newcommand*{\read@linelist}[1]{%
466   \list@clearing@reg
```

When the file is there we start a new group and make some special definitions we'll need to process it: it's a sequence of TeX commands, but they require a few special settings. We make [and] become grouping characters: they're used that way in the line-list file, because we need to write them out one at a time rather than in balanced pairs, and it's easier to just use something other than real braces. @ must become a letter, since this is run in the ordinary L^AT_EX context. We ignore carriage returns, since if we're in horizontal mode they can get interpreted as spaces to be printed.

Our line, page, and line-locking counters were already zeroed by `\line@list@stuff` if this is being called from within `\beginnumbering`; sub-lineation will be turned off as well in that case. On the other hand, if this is being called from `\resumenummering`, those things should still have the values they had when `\pausenummering` was executed.

If the file is not there, we print an informative message.

Now, after these preliminaries, we start interpreting the file.

```
467   \get@linelistfile{#1}%
468   \endgroup
```

When the reading is done, we're all through with the line-list file. All the information we needed from it will now be encoded in our list macros.

Finally, we initialize the `\next@actionline` and `\next@action` macros, which specify where and what the next action to be taken is.

```
469   \global\page@num=\m@ne
470   \ifx\actionlines@list\empty
471     \gdef\next@actionline{1000000}%
472   \else
473     \glp\actionlines@list\to\next@actionline
```



```

474      \gl@p\actions@list\to\next@action
475  \fi}
476
\list@clearing@reg  Clears the lists for \read@linelist
477 \newcommand*{\list@clearing@reg}{%
478   \list@clear{\line@list}%
479   \list@clear{\insertlines@list}%
480   \list@clear{\actionlines@list}%
481   \list@clear{\actions@list}}

\get@linelistfile  eldmac can take advantage of the LATEX ‘safe file input’ macros to get the line-list
file.
482 \newcommand*{\get@linelistfile}[1]{%
483   \InputIfFileExists{#1}{%
484     \global\noteschanged@false
485     \begingroup
486       \catcode'\[=1 \catcode'\]=2
487       \makeatletter \catcode'\^M=9}{%
488       \led@warn@NoLineFile{#1}%
489       \global\noteschanged@true
490       \begingroup}%
491 }
492

```

This version of `\read@linelist` creates list macros containing data for the entire section, so they could get rather large. It would be no more difficult to read the line-list file incrementally rather than all at once: we could read, at the start of each paragraph, only the commands relating to that paragraph. But this would require that we have two line-lists open at once, one for reading, one for writing, and on systems without version numbers we’d have to do some file renaming outside of L^AT_EX for that to work. We’ve retained this slower approach to avoid that sort of hacking about, but have provided the `\pausenumbering` and `\resumenumbering` macros to help you if you run into macro memory limitations (see p. 12 above).

21.5 Commands within the line-list file

This section defines the commands that can appear within a line-list file. They all have very short names because we are likely to be writing very large numbers of them out. One macro, `\@nl`, is especially short, since it will be written to the line-list file once for every line of text in a numbered section. (Another of these commands, `\@lab`, will be introduced in a later section, among the cross-referencing commands it is associated with.)

When these commands modify the various page and line counters, they deliberately do not say `\global`. This is because we want them to affect only the counter values within the current group when nested calls of `\@ref` occur. (The code assumes throughout that the value of `\globaldefs` is zero.)

The macros with `action` in their names contain all the code that modifies the action-code list: again, this is so that they can be turned off easily for nested calls of `\@ref`.

`\@nl` `\@nl` does everything related to the start of a new line of numbered text.
`\@nl@reg` In order to get the `\setlinenum` to work Peter Wilson had to slip in some new code at the start of the macro, to get the timing of the actions correct. The problem was that his original naive implementation of `\setlinenum` had a unfortunate tendency to change the number of the last line of the *preceding* paragraph. The new code is sort of based on the page number handling and `\setline`. It seems that a lot of fiddling with the line number internals is required.

In November 2004 in order to accurately determine page numbers Peter Wilson added these to the macro. It is now:

`\@nl{<page counter number>}{<printed page number>}`

I don't (yet) use the printed number (i.e., the `\thepage`) but it may come in handy later. The macro `\fix@page` checks if a new page has started.

```
493 \newcommand{\@nl}[2]{%
494   \fix@page{#1}%
495   \@nl@reg}
496 \newcommand*{\@nl@reg}{%
497   \ifx\l@dchset@num\relax \else
498     \advance\absline@num \@ne
499     \set@line@action
500     \let\l@dchset@num=\relax
501     \advance\absline@num \m@ne
502     \advance\line@num \m@ne
503   \fi
```

First increment the absolute line-number, and perform deferred actions relating to page starts and sub-lines.

```
504   \advance\absline@num \@ne
505     \ifx\next@page@num\relax \else
506       \page@action
507       \let\next@page@num=\relax
508     \fi
509     \ifx\sub@change\relax \else
510       \ifnum\sub@change>\z@
511         \sublines@true
512       \else
513         \sublines@false
514       \fi
515       \sub@action
516       \let\sub@change=\relax
517     \fi
```

Fix the lock counters, if necessary. A value of 1 is advanced to 2; 3 advances to 0; other values are unchanged.

```
518     \ifcase\@lock
519       \or
```

```

520         \@lock \tw@
521         \or \or
522         \@lock \z@
523     \fi
524     \ifcase\sub@lock
525         \or
526         \sub@lock \tw@
527         \or \or
528         \sub@lock \z@
529     \fi

```

Now advance the visible line number, unless it's been locked.

```

530     \ifsublines@
531         \ifnum\sub@lock<\tw@
532             \advance\subline@num \@ne
533         \fi
534     \else
535         \ifnum\@lock<\tw@
536             \advance\line@num \@ne \subline@num \z@
537         \fi
538     \fi}
539

```

`\last@page@num` `\fix@page` basically replaces `\@page`. It determines whether or not a new page has been started, based on the page values held by `\@nl`.

```

540 \newcount\last@page@num
541 \last@page@num=-10000
542 \newcommand*{\fix@page}[1]{%
543     \ifnum #1=\last@page@num
544     \else
545         \ifbypage@
546             \line@num=\z@ \subline@num=\z@
547         \fi
548         \page@num=#1\relax
549         \last@page@num=#1\relax
550         \def\next@page@num{#1}%
551         \listcsxadd{normal@page@break}{\the\absline@num}
552     \fi}
553

```

`\@pend` These don't do anything at this point, but will have been added to the auxiliary file(s) if the `eledpar` package has been used. They are just here to stop `eledmac` from moaning if the `eledpar` is used for one run and then not for the following one.

`\@lopL`

`\@lopR`

```

554 \newcommand*{\@pend}[1]{%
555 \newcommand*{\@pendR}[1]{%
556 \newcommand*{\@lopL}[1]{%
557 \newcommand*{\@lopR}[1]{%
558

```

`\sub@on` The `\sub@on` and `\sub@off` macros turn sub-lineation on and off: but not directly, since such changes don't really take effect until the next line of text. Instead they set a flag that notifies `\@nl` of the necessary action.

```

559 \newcommand*{\sub@on}{\ifsublines@
560     \let\sub@change=\relax
561   \else
562     \def\sub@changes{1}%
563   \fi}
564 \newcommand*{\sub@off}{\ifsublines@
565     \def\sub@changes{-1}%
566   \else
567     \let\sub@change=\relax
568   \fi}
569
```

`\@adv` The `\@adv{<num>}` macro advances the current visible line number by the amount specified as its argument. This is used to implement `\advance\line`.

```

570 \newcommand*{\@adv}[1]{\ifsublines@
571     \advance\subline@num by #1\relax
572     \ifnum\subline@num<\z@
573       \led@warn@BadAdvancelineSubline
574       \subline@num \z@
575     \fi
576   \else
577     \advance\line@num by #1\relax
578     \ifnum\line@num<\z@
579       \led@warn@BadAdvancelineLine
580       \line@num \z@
581     \fi
582   \fi
583   \set@line@action}
584
```

`\@set` The `\@set{<num>}` macro sets the current visible line number to the value specified as its argument. This is used to implement `\set\line`.

```

585 \newcommand*{\@set}[1]{\ifsublines@
586     \subline@num=#1\relax
587   \else
588     \line@num=#1\relax
589   \fi
590   \set@line@action}
591
```

`\l@d@set` The `\l@d@set{<num>}` macro sets the line number for the next `\pstart...` to the value specified as its argument. This is used to implement `\set\linenum`.

`\l@dchset@num` is a flag to the `\@l` macro. If it is not `\relax` then a linenum change is to be done.

```

592 \newcommand*{\l@d@set}[1]{%
593   \line@num=#1\relax
```

```

594 \advance\line@num \@ne
595 \def\l@dchset@num{#1}}
596 \let\l@dchset@num\relax
597

```

`\page@action` `\page@action` adds an entry to the action-code list to change the page number.

```

598 \newcommand*{\page@action}{%
599 \xright@appenditem{\the\absline@num}\to\actionlines@list
600 \xright@appenditem{\next@page@num}\to\actions@list}

```

`\set@line@action` `\set@line@action` adds an entry to the action-code list to change the visible line number.

```

601 \newcommand*{\set@line@action}{%
602 \xright@appenditem{\the\absline@num}\to\actionlines@list
603 \ifsublines@
604     \l@dtempcnta=-\subline@num
605 \else
606     \l@dtempcnta=-\line@num
607 \fi
608 \advance\l@dtempcnta by -5000
609 \xright@appenditem{\the\l@dtempcnta}\to\actions@list}

```

`\sub@action` `\sub@action` adds an entry to the action-code list to turn sub-lineation on or off, according to the current value of the `\ifsublines@` flag.

```

610 \newcommand*{\sub@action}{%
611 \xright@appenditem{\the\absline@num}\to\actionlines@list
612 \ifsublines@
613     \xright@appenditem{-1001}\to\actions@list
614 \else
615     \xright@appenditem{-1002}\to\actions@list
616 \fi}

```

`\lock@on` `\lock@on` adds an entry to the action-code list to turn line number locking on.
`\do@lockon` The current setting of the sub-lineation flag tells us whether this applies to line
`\do@lockonL` numbers or sub-line numbers.

Adding commands to the action list is slow, and it's very often the case that a lock-on command is immediately followed by a lock-off command in the line-list file, and therefore really does nothing. We use a look-ahead scheme here to detect such pairs, and add nothing to the line-list in those cases.

```

617 \newcommand*{\lock@on}{\futurelet\next\do@lockon}
618 \newcommand*{\do@lockon}{%
619 \ifx\next\lock@off
620     \global\let\lock@off=\skip@lockoff
621 \else
622     \do@lockonL
623 \fi}
624 \newcommand*{\do@lockonL}{%
625 \xright@appenditem{\the\absline@num}\to\actionlines@list
626 \ifsublines@

```

```

627 \xright@appenditem{-1005}\to\actions@list
628 \ifnum\sub@lock=\z@
629 \sub@lock \@ne
630 \else
631 \ifnum\sub@lock=\thr@@
632 \sub@lock \@ne
633 \fi
634 \fi
635 \else
636 \xright@appenditem{-1003}\to\actions@list
637 \ifnum\@lock=\z@
638 \@lock \@ne
639 \else
640 \ifnum\@lock=\thr@@
641 \@lock \@ne
642 \fi
643 \fi
644 \fi}
645

\lock@off \lock@off adds an entry to the action-code list to turn line number locking off.
\do@lockoff 646 \newcommand*{\do@lockoffL}{%
\do@lockoffL 647 \xright@appenditem{\the\absline@num}\to\actionlines@list
\skip@lockoff 648 \ifsublines@
649 \xright@appenditem{-1006}\to\actions@list
650 \ifnum\sub@lock=\tw@
651 \sub@lock \thr@@
652 \else
653 \sub@lock \z@
654 \fi
655 \else
656 \xright@appenditem{-1004}\to\actions@list
657 \ifnum\@lock=\tw@
658 \@lock \thr@@
659 \else
660 \@lock \z@
661 \fi
662 \fi}
663 \newcommand*{\do@lockoff}{\do@lockoffL}
664 \newcommand*{\skip@lockoff}{\global\let\lock@off=\do@lockoff}
665 \global\let\lock@off=\do@lockoff
666

\n@num This macro implements the \skipnumbering command. It uses a new action code,
\n@num@reg namely 1007.
667 \newcommand*{\n@num}{\n@num@reg}
668 \newcommand*{\n@num@reg}{%
669 \xright@appenditem{\the\absline@num}\to\actionlines@list
670 \xright@appenditem{-1007}\to\actions@list}
671

```

`\@ref` `\@ref` marks the start of a passage, for creation of a footnote reference. It takes `\insert@count` two arguments:

- #1, the number of entries to add to `\insertlines@list` for this reference. This value, here and within `\edtext`, which computes it and writes it to the line-list file, will be stored in the count `\insert@count`.

```
672 \newcount\insert@count
```

- #2, a sequence of other line-list-file commands, executed to determine the ending line-number. (This may also include other `\@ref` commands, corresponding to uses of `\edtext` within the first argument of another instance of `\edtext`.)

`\dummy@ref` When nesting of `\@ref` commands does occur, it's necessary to temporarily redefine `\@ref` within `\@ref`, so that we're only doing one of these at a time.

```
673 \newcommand*\@dummy@ref}[2]{#2}
```

`\@ref@reg` The first thing `\@ref` (i.e. `\@ref@reg`) itself does is to add the specified number of items to the `\insertlines@list` list.

```
674 \newcommand*\@ref}[2]{%
675 \@ref@reg{#1}{#2}}
676 \newcommand*\@ref@reg}[2]{%
677 \global\insert@count=#1\relax
678 \loop\ifnum\insert@count>\z@
679 \xright@appenditem{\the\absline@num}\to\insertlines@list
680 \global\advance\insert@count \m@ne
681 \repeat
```

Next, process the second argument to determine the page and line numbers for the end of this lemma. We temporarily equate `\@ref` to a different macro that just executes its argument, so that nested `\@ref` commands are just skipped this time. Some other macros need to be temporarily redefined to suppress their action.

```
682 \begingroup
683 \let\@ref=\@dummy@ref
684 \let\page@action=\relax
685 \let\sub@action=\relax
686 \let\set@line@action=\relax
687 \let\@lab=\relax
688 #2
689 \global\endpage@num=\page@num
690 \global\endline@num=\line@num
691 \global\endsubline@num=\subline@num
692 \endgroup
```

Now store all the information about the location of the lemma's start and end in `\line@list`.

```
693 \xright@appenditem%
694 {\the\page@num|\the\line@num|%
```

```

695      \ifsublines@ \the\subline@num \else 0\fi}%
696      \the\endpage@num|\the\endline@num|}%
697      \ifsublines@ \the\endsubline@num \else 0\fi}\to\line@list

```

Finally, execute the second argument of `\@ref` again, to perform for real all the commands within it.

```

698      #2}
699

```

21.6 Writing to the line-list file

We’ve now defined all the counters, lists, and commands involved in reading the line-list file at the start of a section. Now we’ll cover the commands that `eledmac` uses within the text of a section to write commands out to the line-list.

`\linenum@out` The file will be opened on output stream `\linenum@out`.

```

700 \newwrite\linenum@out

```

`\iffirst@linenum@out@` Once any file is opened on this stream, we keep it open forever, or else switch to another file that we keep open. The reason is that we want the output routine to write the page number for every page to this file; otherwise we’d have to write it at the start of every line. But it’s not very easy for the output routine to tell whether an output stream is open or not. There’s no way to test the status of a particular output stream directly, and the asynchronous nature of output routines makes the status hard to determine by other means.

We can manage pretty well by means of the `\iffirst@linenum@out@` flag; its inelegant name suggests the nature of the problem that made its creation necessary. It’s set to be `true` before any `\linenum@out` file is opened. When such a file is opened for the first time, it’s done using `\immediate`, so that it will at once be safe for the output routine to write to it; we then set this flag to `false`.

```

701 \newif\iffirst@linenum@out@
702 \first@linenum@out@true

```

`\line@list@stuff` The `\line@list@stuff{<file>}` macro, which is called by `\beginnumbering`, performs all the line-list operations needed at the start of a section. Its argument is the name of the line-list file.

```

703 \newcommand*\line@list@stuff}[1]{%

```

First, use the commands of the previous section to interpret the line-list file from the last run.

```

704 \read@linelist{#1}%

```

Now close the current output line-list file, if any, and open a new one. The first time we open a line-list file for output, we do it using `\immediate`, and clear the `\iffirst@linenum@out@` flag.

```

705 \iffirst@linenum@out@
706 \immediate\closeout\linenum@out%
707 \global\first@linenum@out@false%
708 \immediate\openout\linenum@out=#1\relax%
709 \else

```


If we get here, then this is not the first line-list we've seen, so we don't open or close the files immediately, except if we are in a minipage and this minipage is not a ledgroup.

```

710     \if@minipage%
711         \if@ledgroup%
712             \closeout\linenum@out%
713             \openout\linenum@out=#1\relax%
714         \else%
715             \immediate\closeout\linenum@out%
716             \immediate\openout\linenum@out=#1\relax%
717         \fi
718     \else%
719         \closeout\linenum@out%
720         \openout\linenum@out=#1\relax%
721     \fi%
722 \fi}
723

```

`\new@line` The `\new@line` macro sends the `\@nl` command to the line-list file, to mark the start of a new text line, and its page number.

```

724 \newcommand*{\new@line}{%
725   \IfStrEq{\led@pb@setting}{after}%
726     {\xifinlistcs{\the\absline@num}{l@prev@nopb}%
727       {\xifinlistcs{\the\absline@num}{normal@page@break}%
728         {\numgdef{\@next@page}{\thepage+1}%
729           \write\linenum@out{\string\@nl[\@next@page][\@next@page]}}%
730       }%
731     {\write\linenum@out{\string\@nl[\the\c@page][\thepage]}}%
732   }%
733   {\write\linenum@out{\string\@nl[\the\c@page][\thepage]}}}%
734 }%
735 \IfStrEq{\led@pb@setting}{before}%
736   {\numgdef{\next@absline}{\the\absline@num+1}%
737     \xifinlistcs{\next@absline}{l@prev@nopb}%
738     {\xifinlistcs{\the\absline@num}{normal@page@break}%
739       {\numgdef{\nc@page}{\c@page+1}%
740         \write\linenum@out{\string\@nl[\nc@page][\nc@page]}}%
741     }%
742     {\write\linenum@out{\string\@nl[\the\c@page][\thepage]}}%
743   }%
744   {\write\linenum@out{\string\@nl[\the\c@page][\thepage]}}}%
745 }%
746 {}%
747 \IfStrEqCase{\led@pb@setting}{{before}{\relax}{after}{\relax}}{\write\linenum@out{\string\@nl[\the\c@page][\thepage]}}%
748 }
749

```

`\if@noneed@Footnote` We enclose a lemma marked by `\edtext` in `\flag@start` and `\flag@end`: these
`\flag@start` send the `\@ref` command to the line-list file. `\edtext` is responsible for setting
`\flag@end`

the value of `\insert@count` appropriately; it actually gets done by the various footnote macros.

```

750 \newif\if@noneed@Footnote%Bool to check if we have to print a error message
751
752 \newcommand*{\flag@start}{%
753   \ifledRcol%
754     \edef\next{\write\linenum@outR{%
755       \string\@ref[\the\insert@countR] []}%
756     \next%
757     \ifnum\insert@countR<1%
758       \if@noneed@Footnote\else%
759         \led@err@EdtextWithoutFootnote%
760       \fi%
761     \fi%
762   \else%
763     \edef\next{\write\linenum@out{%
764       \string\@ref[\the\insert@count] []}%
765     \next%
766     \ifnum\insert@count<1%
767       \if@noneed@Footnote\else%
768         \led@err@EdtextWithoutFootnote%
769       \fi%
770     \fi%
771   \fi}%
772

```

`\page@start` Originally the commentary was: `\page@start` writes a command to the line-list file noting the current page number; when used within an output routine, this should be called so as to place its `\write` within the box that gets shipped out, and as close to the top of that box as possible.

However, in October 2004 Alexej Krukov discovered that when processing long paragraphs that included Russian, Greek and Latin texts `eledmac` would go into an infinite loop, emitting thousands of blank pages. This was caused by being unable to find an appropriate place in the output routine. A different algorithm is now used for getting page numbers.

```

773 \newcommand*{\page@start}{}
774

```

`\startsub` `\startsub` and `\endsub` turn sub-lineation on and off, by writing appropriate instructions to the line-list file. When sub-lineation is in effect, the line number counter is frozen and the sub-line counter advances instead. If one of these commands appears in the middle of a line, it doesn't take effect until the next line; in other words, a line is counted as a line or sub-line depending on what it started out as, even if that changes in the middle.

We tinker with `\lastskip` because a command of either sort really needs to be attached to the last word preceding the change, not the first word that follows the change. This is because sub-lineation will often turn on and off in mid-line—stage directions, for example, often are mixed with dialogue in that way—and when a

line is mixed we want to label it using the system that was in effect at its start. But when sub-lineation begins at the very start of a line we have a problem, if we don't put in this code.

```

775 \newcommand*{\startsub}{\dimen0\lastskip
776 \ifdim\dimen0>0pt \unskip \fi
777 \write\linenum@out{\string\sub@on}%
778 \ifdim\dimen0>0pt \hskip\dimen0 \fi}
779 \def\endsub{\dimen0\lastskip
780 \ifdim\dimen0>0pt \unskip \fi
781 \write\linenum@out{\string\sub@off}%
782 \ifdim\dimen0>0pt \hskip\dimen0 \fi}
783

```

`\advanceline` You can use `\advanceline{<num>}` in running text to advance the current visible line-number by a specified value, positive or negative.

```

784 \newcommand*{\advanceline}[1]{\write\linenum@out{\string\@adv[#1]}}

```

`\setline` You can use `\setline{<num>}` in running text (i.e., within `\pstart... \pend`) to set the current visible line-number to a specified positive value.

```

785 \newcommand*{\setline}[1]{%
786 \ifnum#1<\z@
787 \led@warn@BadSetline
788 \else
789 \write\linenum@out{\string\@set[#1]}%
790 \fi}
791

```

`\setlinenum` You can use `\setlinenum{<num>}` before a `\pstart` to set the visible line-number to a specified positive value. It writes a `\l@d@set` command to the line-list file.

```

792 \newcommand*{\setlinenum}[1]{%
793 \ifnum#1<\z@
794 \led@warn@BadSetlinenum
795 \else
796 \write\linenum@out{\string\l@d@set[#1]}%
797 \fi}
798

```

`\startlock` You can use `\startlock` or `\endlock` in running text to start or end line number locking at the current line. They decide whether line numbers or sub-line numbers are affected, depending on the current state of the sub-lineation flags.

```

799 \newcommand*{\startlock}{\write\linenum@out{\string\lock@on}}
800 \def\endlock{\write\linenum@out{\string\lock@off}}
801

```

`\ifl@dskipnumber` In numbered text `\skipnumbering` will suspend the numbering for that particular line.
`\l@dskipnumbertrue`
`\l@dskipnumberfalse` 802 \newif\ifl@dskipnumber
`\skipnumbering` 803 \l@dskipnumberfalse
`\skipnumbering@reg`

```

804 \newcommand*{\skipnumbering}{\skipnumbering@reg}
805 \newcommand*{\skipnumbering@reg}{%
806   \write\linenum@out{\string\n@num}%
807   \advance\line{-1}}
808

```

22 Marking text for notes

The `\edtext` (or `\critext`) macro is used to create all footnotes and endnotes, as well as to print the portion of the main text to which a given note or notes is keyed. The idea is to have that lemma appear only once in the `.tex` file: all instances of it in the main text and in the notes are copied from that one appearance.

For convenience, I will use `*text` when I do not need to distinguish between `\edtext` and `\critext`. The `*text` macros take two arguments, the only difference between `\edtext` and `\critext` is how the second argument is delineated.

`\critext` requires two arguments. At any point within numbered text, you use it by saying:

```
\critext{#1}#2/
```

Similarly `\edtext` requires the same two arguments but you use it by saying:

```
\edtext{#1}{#2}
```

- `#1` is the piece of the main text being glossed; it gets added to the main text, and is also used as a lemma for notes to it.
- `#2` is a series of subsidiary macros that generate various kinds of notes. With `\critext` the `/` after `#2` *must* appear: it marks the end of the macro. (*The TeXbook*, p. 204, points out that when additional text to be matched follows the arguments like this, spaces following the macro are not skipped, which is very desirable since this macro will never be used except within text. Having an explicit terminator also helps keep things straight when nested calls to `\critext` are used.) Braces around `#2` are optional with `\critext` and required for `\edtext`.

The `*text` macro may be used (somewhat) recursively; that is, `*text` may be used within its own first argument. The code would be much simpler without this feature, but nested notes will commonly be necessary: it's quite likely that we'll have an explanatory note for a long passage and notes on variants for individual words within that passage. The situation we can't handle is overlapping notes that aren't nested: for example, one note covering lines 10–15, and another covering 12–18. You can handle such cases by using the `\lemma` and `\linenum` macros within `#2`: they alter the copy of the lemma and the line numbers that are passed to the notes, and hence allow you to overcome any limitations of this system, albeit with extra effort.

The recursive operation of `*text` will fail if you try to use a copy that is called something other than `*text`. In order to handle recursion, `*text` needs to redefine its own definition temporarily at one point, and that doesn't work if the macro you are calling is not actually named `*text`. There's no problem as long as `*text` is not invoked in the first argument. If you want to call `*text` something else, it is best to create instead a macro that expands to an invocation of `*text`, rather than copying `*text` and giving it a new name; otherwise you will need to add an appropriate definition for your new macro to `\morenoexpands`.

Side effects of our line-numbering code make it impossible to use the usual footnote macros directly within a paragraph whose lines are numbered (see comments to `\do@line`, p.87). Instead, the appropriate note-generating command is appended to the list macro `\inserts@list`, and when `\pend` completes the paragraph it inserts all the notes at the proper places.

Note that we don't provide previous-note information, although it's often wanted; your own macros must handle that. We can't do it correctly without keeping track of what kind of notes have gone past: it's not just a matter of remembering the line numbers associated with the previous invocation of `*text`, because that might have been for a different kind of note. It is preferable for your footnote macros to store and recall this kind of information if they need it.

An example where some 'memory' of line numbers might be required is where there are several variant readings per line of text, and you do not wish the line number to be repeated for each lemma in the notes. After the first occurrence of the line number, you might want the symbol '||' instead of further occurrences, for instance. This can easily be done by a macro like `\printlines`, if it saves the last value of `\l@d@nums` that *it* saw, and then performs a simple conditional test to see whether to print a number or a '||'.

22.1 `\edtext` and `\critext` themselves

The various note-generating macros might want to request that commands be executed not at once, but in close connection with the start or end of the lemma. For example, footnote numbers in the text should be connected to the end of the lemma; or, instead of a single macro to create a note listing variants, you might want to use several macros in series to create individual variants, which would each add information to a private macro or token register, which in turn would be formatted and output when all of #2 for the lemma has been read.

`\end@lemmas` To accomodate this, we provide a list macro to which macros may add commands that should subsequently be executed at the end of the lemma when that lemma is added to the text of the paragraph. A macro should add its contribution to `\end@lemmas` by using `\xleft@appenditem`. (Anything that needs to be done at the *start* of the lemma may be handled using `\aftergroup`, since the commands specified within `\critext`'s second argument are executed within a group that ends just before the lemma is added to the main text.)

`\end@lemmas` is intended for the few things that need to be associated with the end of the lemma, like footnote numbers. Such numbers are not implemented

in the current version, and indeed no use is currently made of `\end@lemmas` or of the `\aftergroup` trick. The general approach would be to define a macro to be used within the second argument of `\critext` that would add the appropriate command to `\end@lemmas`.

Commands that are added to this list should always take care not to do anything that adds possible line-breaks to the output; otherwise line numbering could be thrown off.

```
809 \list@create{\end@lemmas}
```

`\dummy@text` We now need to define a number of macros that allow us to weed out nested instances of `\critext`, and other problematic macros, from our lemma. This is similar to what we did in reading the line-list file using `\dummy@ref` and various redefinitions—and that’s because nested `\critext` macros create nested `\@ref` entries in the line-list file.

Here’s a macro that takes the same arguments as `\critext` but merely returns the first argument and ignores the second.

```
810 \long\def\dummy@text#1#2/{#1}
```

`\dummy@edtext` L^AT_EX users are not used to delimited arguments, so we provide a `\edtext` macro as well.

```
811 \newcommand{\dummy@edtext}[2]{#1}
```

`\dummy@edtext@showlemma` Some time, we want to obtain only the first argument of `\edtext`, while also wrapping it in `\showlemma`. For example, when printing a `\eledsection`.

```
812 \newcommand{\dummy@edtext@showlemma}[2]{\showlemma{#1}}%
```

We’re going to need another macro that takes one argument and ignores it entirely. This is supplied by the L^AT_EX `\@gobble{<arg>}`.

`\no@expands` We need to turn off macro expansion for certain sorts of macros we’re likely to see within the lemma and within the notes.

The first class is font-changing macros. We suppress expansion for them by letting them become equal to zero.²² This is done because we want to pass into our notes the generic commands to change to roman or whatever, and not their expansions that will ask for a particular style at a specified size. The notes may well be in a smaller font, so the command should be expanded later, when the note’s environment is in effect.

A second sort to turn off includes a few of the accent macros. Most are not a problem: an accent that’s expanded to an `\accent` command may be harder to read but it works just the same. The ones that cause problems are: those that use alignments—T_EX seems to get confused about the difference between alignment parameters and macro parameters; those that use temporary control sequences; and those that look carefully at what the current font is.

²²Since ‘control sequences equivalent to characters are not expandable’—*The TeXbook*, answer to Exercise 20.14.

(The `\copyright` macro defined in PLAIN `TeX` has this sort of problem as well, but isn't used enough to bother with. That macro, and any other that causes trouble, will get by all right if you put a `\protect` in front of it in your file.)

We also need to eliminate all `eledmac` macros like `\edlabel` and `\setline` that write things to auxiliary files: that writing should be done only once. And we make `\critext` itself, if it appears within its own argument, do nothing but copy its first argument.

Finally, we execute `\morenoexpands`. The version of `\morenoexpands` defined here does nothing; but you may define a version of your own when you need to add more expansion suppressions as needed with your macros. That makes it possible to make such additions without needing to copy or modify the standard `eledmac` code. If you define your own `\morenoexpands`, you must be very careful about spaces: if the macro adds any spaces to the text when it runs, extra space will appear in the main text when `\critext` is used.

(A related problem, not addressed by these two macros, is that of characters whose category code is changed by any the macros used in the arguments to `\critext`. Since the category codes are set when the arguments are scanned, macros that depend on changing them will not work. We have most often encountered this with characters that are made 'active' within text in some, but not all, of the languages used within the document. One way around the problem, if it takes this form, is to ensure that those characters are *always* active; within languages that make no special use of them, their associated control sequences should simply return the proper character.)

```

813 \newcommand*{\no@expands}{%
814   \let\select@lemmafnt=0%
815   \let\startsub=\relax \let\endsub=\relax
816   \let\startlock=\relax \let\endlock=\relax
817   \let\edlabel=\@gobble
818   \let\setline=\@gobble \let\advanceline=\@gobble
819   \let\critext=dummy@text
820   \let\edtext=dummy@edtext
821   \l@dtabnoexpands
822   \morenoexpands}
823 \let\morenoexpands=\relax
824
```

`\@tag` Now, we define an empty `\@tag` command. It will be redefine by `\edtext`: its value is the first args. It will be used by the `\Xfootnote` commands.

```

825 \newcommand{\@tag}{}
826 % \end{macrocode}
827 % \end{macro}
828 % \begin{macro}{\critext}
829 % Now we begin \cs{critext} itself. The definition requires a \verb"/" after
830 % the arguments: this eliminates the possibility of problems about
831 % knowing where \verb"#2" ends. This also changes the handling of spaces
832 % following an invocation of the macro: normally such spaces are
```

```

833 % skipped, but in this case they're significant because \verb"#2" is
834 % a 'delimited parameter'. Since \cs{critext} is always used in running
835 % text, it seems more appropriate to pay attention to spaces than to
836 % skip them.
837 %
838 % When executed, \cs{critext} first ensures that we're in
839 % horizontal mode.
840 % \begin{macrocode}
841 \long\def\critext#1#2/{\leavevmode

```

`\@tag` Our normal lemma is just argument `#1`; but that argument could have further invocations of `\critext` within it. We get a copy of the lemma without any `\critext` macros within it by temporarily redefining `\critext` to just copy its first argument and ignore the other, and then expand `#1` into `\@tag`, our lemma.

This is done within a group that starts here, in order to get the original `\critext` restored; within this group we've also turned off the expansion of those control sequences commonly found within text that can cause trouble for us.

```

842 \begingroup
843 \global\renewcommand{\@tag}{\no@expands #1}%%

```

`\l@d@nums` Prepare more data for the benefit of note-generating macros: the line references and font specifier for this lemma go to `\l@d@nums`.

```

844 \set@line

```

`\insert@count` will be altered by the note-generating macros: it counts the number of deferred footnotes or other insertions generated by this instance of `\critext`.

```

845 \global\insert@count=0

```

Now process the note-generating macros in argument `#2` (i.e., `\Afootnote`, `\lemma`, etc.). `\ignorespaces` is here to skip over any spaces that might appear at the start of `#2`; otherwise they wind up in the main text. Footnote and other macros that are used within `#2` should all end with `\ignorespaces` as well, to skip any spaces between macros when several are used in series.

```

846 \ignorespaces #2\relax

```

Finally, we're ready to admit the first argument into the current paragraph.

It's important that we generate and output all the notes for this chunk of text *before* putting the text into the paragraph: notes that are referenced by line number should generally be tied to the start of the passage they gloss, not the end. That should all be done within the expansion of `#2` above, or in `\aftergroup` commands within that expansion.

```

847 \ifundefined{xpg@main@language}{%if not polyglossia
848 \flag@start}%
849 {\if@RTL\flag@end\else\flag@start\fi% With polyglossia, you must track whether the
850 }
851 \endgroup
852 \showlemma{#1}%

```


Finally, we add any insertions that are associated with the *end* of the lemma. Footnotes that are identified by symbols rather than by where the lemma begins in the main text need to be done here, and not above.

```

853 \ifx\end@lemmas\empty \else
854   \glp\end@lemmas\to\x@lemma
855   \x@lemma
856   \global\let\x@lemma=\relax
857 \fi
858 \@ifundefined{xpg@main@language}{%if not polyglossia
859   \flag@end}%
860   {\ifRTL\flag@start\else\flag@end\fi% With polyglossia, you must track whether the language re
861   }
862 }
```

`\edtext`

```

863 \newcommand{\edtext}[2]{\leavevmode
864   \begingroup
865     \global\renewcommand{\@tag}{\no@expands #1}%
866     \set@line
867     \global\insert@count=0
868     \ignorespaces #2\relax
869     \@ifundefined{xpg@main@language}{%if not polyglossia
870       \flag@start}%
871       {\ifRTL\flag@end\else\flag@start\fi% With polyglossia, you must track whether the language re
872       }%
873   \endgroup
874   \showlemma{#1}%
875   \ifx\end@lemmas\empty \else
876     \glp\end@lemmas\to\x@lemma
877     \x@lemma
878     \global\let\x@lemma=\relax
879   \fi
880   \@ifundefined{xpg@main@language}{%if not polyglossia
881     \flag@end}%
882     {\ifRTL\flag@start\else\flag@end\fi% With polyglossia, you must track whether the language re
883     }%
884   \global\@noneed@Footnotefalse%
885 }
886
887 \newcommand*{\flag@end}{%
888   \ifledRcol%
889     \write\linenum@outR{]}%
890   \else%
891     \write\linenum@out{]}%
892   \fi}%
893
```

`\ifnumberline` The `\ifnumberline` option can be set to `FALSE` to disable line numbering.

```
894 \newif\ifnumberline
895 \numberlinetrue
```

\set@line The **\set@line** macro is called by **\critext** to put the line-reference field and font specifier for the current block of text into **\l@d@nums**.

One instance of **\critext** may generate several notes, or it may generate none—it’s legitimate for argument #2 to **\critext** to be empty. But **\flag@start** and **\flag@end** induce the generation of a single entry in **\line@list** during the next run, and it’s vital to also remove one and only one **\line@list** entry here.

```
896 \newcommand*{\set@line}{%
```

If no more lines are listed in **\line@list**, something’s wrong—probably just some change in the input. We set all the numbers to zeros, following an old publishing convention for numerical references that haven’t yet been resolved.

```
897 \ifx\line@list\empty
898   \global\noteschanged@true
899   \xdef\l@d@nums{000|000|000|000|000|000|\edfont@info}%
900 \else
901   \gl@p\line@list\to\@tempb
902   \xdef\l@d@nums{\@tempb|\edfont@info}%
903   \global\let\@tempb=\undefined
904 \fi}
905
```

\edfont@info The macro **\edfont@info** returns coded information about the current font.

```
906 \newcommand*{\edfont@info}{\f@encoding/\f@family/\f@series/\f@shape}
907
```

22.2 Substitute lemma

\lemma The **\lemma{<text>}** macro allows you to change the lemma that’s passed on to the notes.

```
908 \newcommand*{\lemma}[1]{\global\renewcommand{\@tag}{\no@expands #1}}
```

22.3 Substitute line numbers

\linenum The **\linenum** macro can change any or all of the page and line numbers that are passed on to the notes.

As argument **\linenum** takes a set of seven parameters separated by vertical bars, in the format used internally for **\l@d@nums** (see p.61): the starting page, line, and sub-line numbers, followed by the ending page, line, and sub-line numbers, and then the font specifier for the lemma. However, you can omit any parameters you don’t want to change, and you can omit a string of vertical bars at the end of the argument. Hence **\linenum{18|4|0|18|7|1|0}** is an invocation that changes all the parameters, but **\linenum{|3}** only changes the starting line number, and leaves the rest unaltered.

We use **** as an internal separator for the macro parameters.

```

909 \newcommand*{\linenum}[1]{%
910   \xdef\@tempa{#1|||||}\noexpand\\\l@d@nums}%
911   \global\let\l@d@nums=\empty
912   \expandafter\line@set\@tempa|\\\ignorespaces}

```

\line@set `\linenum` calls `\line@set` to do the actual work; it looks at the first number in the argument to `\linenum`, sets the corresponding value in `\l@d@nums`, and then calls itself to process the next number in the `\linenum` argument, if there are more numbers in `\l@d@nums` to process.

```

913 \def\line@set#1|#2|#3|#4\\{%
914   \gdef\@tempb{#1}%
915   \ifx\@tempb\empty
916     \l@d@add{#3}%
917   \else
918     \l@d@add{#1}%
919   \fi
920   \gdef\@tempb{#4}%
921   \ifx\@tempb\empty\else
922     \l@d@add{|\line@set#2|#4\\}%
923   \fi}

```

\l@d@add `\line@set` uses `\l@d@add` to tack numbers or vertical bars onto the right hand end of `\l@d@nums`.

```

924 \newcommand{\l@d@add}[1]{\xdef\l@d@nums{\l@d@nums#1}}
925

```

23 Paragraph decomposition and reassembly

In order to be able to count the lines of text and affix line numbers, we add an extra stage of processing for each paragraph. We send the paragraph into a box register, rather than straight onto the vertical list, and when the paragraph ends we slice the paragraph into its component lines; to each line we add any notes or line numbers, add a command to write to the line-list, and then at last send the line to the vertical list. This section contains all the code for this processing.

23.1 Boxes, counters, `\pstart` and `\pend`

\raw@text Here are numbers and flags that are used internally in the course of the paragraph decomposition.

\ifnumberedpar@

\numberedpar@true When we first form the paragraph, it goes into a box register, `\raw@text`, instead of onto the current vertical list. The `\ifnumberedpar@` flag will be `true`

\numberedpar@false while a paragraph is being processed in that way. `\num@lines` will store the

\num@lines number of lines in the paragraph when it's complete. When we chop it up into

\one@line lines, each line in turn goes into the `\one@line` register, and `\par@line` will be

\par@line the number of that line within the paragraph.

```

926 \newbox\raw@text
927 \newif\ifnumberedpar@

```

```

928 \newcount\num@lines
929 \newbox\one@line
930 \newcount\par@line

\pstart \pstart starts the paragraph by clearing the \inserts@list list and other rele-
\numberpstarttrue vant variables, and then arranges for the subsequent text to go into the \raw@text
\numberpstartfalse box. \pstart needs to appear at the start of every paragraph that's to be num-
\labelpstarttrue bered; the \autopar command below may be used to insert these commands
\labelpstartfalse automatically.
\thepstart Beware: everything that occurs between \pstart and \pend is happening
within a group; definitions must be global if you want them to survive past the
end of the paragraph.

931
932 \newcounter{pstart}
933 \renewcommand{\thepstart}{\bfseries\@arabic{c@pstart}. }
934 \newif\ifnumberpstart
935 \numberpstartfalse
936 \newif\iflabelpstart
937 \labelpstartfalse
938 \newcommand*{\pstart}[1][1]{%
939 \ifstrempy{#1}{\noindent#1}%
940 \if@nbreak%
941 \let\@oldnbreak\@nbreaktrue%
942 \else%
943 \let\@oldnbreak\@nbreakfalse%
944 \fi%
945 \@nbreaktrue%
946 \ifnumbering \else%
947 \led@err@PstartNotNumbered%
948 \beginnumbering%
949 \fi%
950 \ifnumberedpar@%
951 \led@err@PstartInPstart%
952 \pend%
953 \fi%
954 \list@clear{\inserts@list}%
955 \global\let\next@insert=\empty%
956 \begingroup\normal@pars%
957 \global\advance \l@dnumpstartsL\@ne
958 \global\setbox\raw@text=\vbox\bgroup%
959 \ifautopar\else%
960 \ifnumberpstart%
961 \ifinstanza\else%
962 \ifsidepstartnum\else%
963 \thepstart%
964 \fi%
965 \fi%
966 \fi%
967 \fi%

```

```

968 \numberedpar@true%
969 \iflabelpstart\protected@edef\@currentlabel%
970     {\p@pstart\thepstart}
971 \fi%
972 \l@dzeroopenalties%
973 }

```

\pend \pend must be used to end a numbered paragraph.

```

974 \newcommand*{\pend}[1][1]{\ifnumbering \else%
975     \led@err@PendNotNumbered%
976 \fi%
977 \ifnumberedpar@ \else%
978     \led@err@PendNoPstart%
979 \fi%

```

We set all the usual interline penalties to zero and then immediately call \endgraf to end the paragraph; this ensures that there'll be no large interline penalties to prevent us from slicing the paragraph into pieces. These penalties revert to the values that you set when the group for the \vbox ends. Then we call \do@line to slice a line off the top of the paragraph, add a line number and footnotes, and restore it to the page; we keep doing this until there aren't any more lines left.

```

980 \l@dzeroopenalties%
981 \endgraf\global\num@lines=\prevgraf\egroup%
982 \global\par@line=0%

```

We check if lineation is by pstart: in this case, we reset line number, but only in the second line of the pstart, to prevent some trouble. We can't reset line number at the beginning of \pstart \setline is parsed at the end of previous \pend, and so, we must do it at the end of first line of pstart.

```

983 \csnumdef{pstartline}{0}%
984 \loop\ifvbox\raw@text%
985     \csnumdef{pstartline}{\pstartline+1}%
986     \do@line%
987     \ifbypstart@%
988         \ifnumequal{pstartline}{1}{\setline{1}\resetprevline@}{}%
989     \fi%
990 \repeat%

```

Deal with any leftover notes, and then end the group that was begun in the \pstart.

```

991 \flush@notes%
992 \endgroup%
993 \ignorespaces%
994 \ifnumberpstart%
995     \pstartnumtrue%
996 \fi%
997 \@oldnobreak%
998 \addtocounter{pstart}{1}%
999 \ifstrempy{#1}{\noindent#1}%
1000 }

```

1001

`\l@dzeropenalties` A macro to zero penalties for `\pend`.

```
1002 \newcommand*{\l@dzeropenalties}{%
1003   \brokenpenalty \z@ \clubpenalty \z@
1004   \displaywidowpenalty \z@ \interlinepenalty \z@ \predisplaypenalty \z@
1005   \postdisplaypenalty \z@ \widowpenalty \z@}
1006
```

`\autopar` In most cases it's only an annoyance to have to label the paragraphs to be numbered with `\pstart` and `\pend`. `\autopar` will do that automatically, allowing you to start a paragraph with its first word and no other preliminaries, and to end it with a blank line or a `\par` command. The command should be issued within a group, after `\beginnumbering` has been used to start the numbering; all paragraphs within the group will be affected.

A few situations can cause problems. One is a paragraph that begins with a begin-group character or command: `\pstart` will not get invoked until after such a group beginning is processed; as a result the character that ends the group will be mistaken for the end of the `\vbox` that `\pstart` creates, and the rest of the paragraph will not be numbered. Such paragraphs need to be started explicitly using `\indent`, `\noindent`, or `\leavevmode`—or `\pstart`, since you can still include your own `\pstart` and `\pend` commands even with `\autopar` on.

Prematurely ending the group within which `\autopar` is in effect will cause a similar problem. You must either leave a blank line or use `\par` to end the last paragraph before you end the group.

The functioning of this macro is more tricky than the usual `\everypar`: we don't want anything to go onto the vertical list at all, so we have to end the paragraph, erase any evidence that it ever existed, and start it again using `\pstart`. We remove the paragraph-indentation box using `\lastbox` and save the width, and then skip backwards over the `\parskip` that's been added for this paragraph. Then we start again with `\pstart`, restoring the indentation that we saved, and locally change `\par` so that it'll do our `\pend` for us.

```
1007 \newif\ifautopar
1008 \autoparfalse
1009 \newcommand*{\autopar}{
1010   \ifledRcol
1011     \ifnumberingR \else
1012       \led@err@AutoparNotNumbered
1013     \beginnumberingR
1014     \fi
1015   \else
1016     \ifnumbering \else
1017       \led@err@AutoparNotNumbered
1018     \beginnumbering
1019     \fi
1020   \fi
1021   \autopartrue
1022   \everypar{\setbox0=\lastbox
```

```

1023 \endgraf \vskip-\parskip
1024 \pstart \noindent \kern\wd0 \ifnumberpstart\ifinstanza\else\thepstart\fi\fi
1025 \let\par=\pend}%
1026 \ignorespaces}

```

`\normal@pars` We also define a macro which we can rely on to turn off the `\autopar` definitions at various important places, if they are in force. We'll want to do this within a footnotes, for example.

```

1027 \newcommand*{\normal@pars}{\everypar{}\let\par\endgraf}
1028

```

`\ifautopar@pause` We define a boolean test switched to true at the beginning of the `\pausenumbering` command if the autopar is enabled. This boolean will be tested at the beginning of `\resumenumbering` to continue the autopar if needed.

```

1029 \newif\ifautopar@pause

```

23.2 Processing one line

`\do@line` The `\do@line` macro is called by `\pend` to do all the processing for a single line of text.

```

1030 \newcommand*{\l@dunhbox@line}[1]{\unhbox #1}
1031 \newcommand*{\do@line}{%
1032   {\vbadness=10000
1033    \splittopskip=\z@
1034    \do@linehook
1035    \l@emptyd@ta
1036    \global\setbox\one@line=\vsplit\raw@text to\baselineskip}%
1037    \unvbox\one@line \global\setbox\one@line=\lastbox
1038    \getline@num
1039    \IfStrEq{\led@pb@setting}{before}{\led@check@pb\led@check@nopb}{%}
1040    \ifnum\@lock>\@ne
1041      \inserthangingsymboltrue
1042    \else
1043      \inserthangingsymbolfalse
1044    \fi
1045    \check@pb@in@verse
1046    \affixline@num

```

Depending whether a sectioning command is called at this pstart or not we print sectioning command or normal line,

```

1047 \xifinlist{\the\l@dnumpstartsL}{\eled@sections@@}%
1048   {\print@eledsection}%
1049   {\print@line}%
1050 \IfStrEq{\led@pb@setting}{after}{\led@check@pb\led@check@nopb}{%}
1051 }%

```

`\print@line`

```

1052 % \cs{print@line} is for normal line, i. e line without sectioning command.

```

```

1053 \def\print@line{
1054   \affixpstart@num%
1055   \hb@xt@ \linewidth{\do@insidelinehook\l@dld@ta%
1056     \add@inserts\affixside@note%
1057     \l@dlsn@te
1058     {\ledllfill\hb@xt@ \wd\one@line{\new@line\inserthangingsymbol \l@dunhbox@line{\on
1059     \l@drsn@te
1060   }}%
1061   \add@penalties%
1062 }

```

`\print@eledsection` `\print@eledsection` to print sectioning command with line number. It sets the correct spacing, depending whether a sectioning command was called at previous `\pstart`, calls the sectioning command, prints the normal line outside of the paper, to be able to have critical footnotes. Because of how this prints, a vertical spacing correction is added.

```

1063 \def\print@eledsection{%
1064   \add@inserts\affixside@note%
1065   \numdef{\temp@}{\l@dnumstartsL-1}%
1066   \xifinlist{\temp@}{\eled@sections@}{\@nobreaktrue}{\@nobreakfalse}%
1067   \@eled@sectioningtrue%
1068   \csuse{eled@sectioning@the\l@dnumstartsL}%
1069   \@eled@sectioningfalse%
1070   \global\csundef{eled@sectioning@the\l@dnumstartsL}%
1071   \if@RTL%
1072     \hspace{-3\paperwidth}%
1073     {\hbox{\l@dunhbox@line{\one@line}}\new@line}%
1074   \else%
1075     \hspace{3\paperwidth}%
1076     {\new@line \hbox{\l@dunhbox@line{\one@line}}}%
1077   \fi%
1078   \vskip-\baselineskip%
1079 }

```

`\dolinehook` These high level commands just redefine the low level commands. They have to be used by user, without `\makeatletter`.

```

1080 \newcommand*{\dolinehook}[1]{\gdef\do@linehook{#1}}%
1081 \newcommand*{\doinsidelinehook}[1]{\gdef\do@insidelinehook{#1}}%
1082

```

`\do@linehook` Two hooks into `\do@line`. The first is called at the beginning of `\do@line`, the second is called in the line box. The second can, for example, have a `\markboth` command inside, the first can't.

```

1083 \newcommand*{\do@linehook}{ }
1084 \newcommand*{\do@insidelinehook}{ }

```

`\l@demptyd@ta` Nulls the `\...d@ta`, which may later hold line numbers. Similarly for `\l@dcsnotetext`,
`\l@dld@ta` `\l@dcsnotetext@l`, `\l@dcsnotetext@r` for the texts of the sidenotes, left and
`\l@drd@ta` right notes.
`\l@dcsnotetext`
`\l@dcsnotetext@l`
`\l@dcsnotetext@r`


```

1085 \newcommand*{\l@emptyd@ta}{%
1086   \gdef\l@dld@ta{}%
1087   \gdef\l@drd@ta{}%
1088   \gdef\l@dcstetext@l{}%
1089   \gdef\l@dcstetext@r{}%
1090   \gdef\l@dcstetext{}}
1091

```

`\l@dlsn@te` Zero width boxes of the left and right side notes, together with their kerns.

```

\l@drsn@te 1092 \newcommand{\l@dlsn@te}{%
1093   \hb@xt@ \z@{\hss\box\l@dldp@rbox\kern\ledlsnotesep}}
1094 \newcommand{\l@drsn@te}{%
1095   \hb@xt@ \z@{\kern\ledrsnotesep\box\l@drp@rbox\hss}}
1096

```

`\ledllfill` These macros are called at the left (`\ledllfill`) and the right (`\ledllfill`) of each numbered line. The initial definitions correspond to the original code for `\do@line`.

```

1097 \newcommand*{\ledllfill}{\hfil}
1098 \newcommand*{\ledrlfill}{}
1099

```

23.3 Line and page number computation

`\getline@num` The `\getline@num` macro determines the page and line numbers for the line we're about to send to the vertical list.

```

1100 \newcommand*{\getline@num}{%
1101   \global\advance\absline@num \@ne
1102   \do@actions
1103   \do@ballast
1104   \ifnumberline
1105   \ifsublines@
1106     \ifnum\sub@lock<\tw@
1107       \global\advance\subline@num \@ne
1108     \fi
1109   \else
1110     \ifnum\@lock<\tw@
1111       \global\advance\line@num \@ne
1112       \global\subline@num \z@
1113     \fi
1114   \fi
1115   \fi
1116 }

```

`\do@ballast` The real work in the macro above is done in `\do@actions`, but before we plunge into that, let's get `\do@ballast` out of the way. This macro looks to see if there is an action to be performed on the *next* line, and if it is going to be a page break action, `\do@ballast` decreases the count `\ballast@count` counter by the amount of `ballast`. This means, in practice, that when `\add@penalties` assigns penalties

at this point, T_EX will be given extra encouragement to break the page here (see p. 98).

`\ballast@count` First we set up the required counters; they are initially set to zero, and will remain
`\c@ballast` so unless you say `\setcounter{ballast}{\langle some figure \rangle}` in your document.

```
1117 \newcount\ballast@count
1118 \newcounter{ballast}
1119 \setcounter{ballast}{0}
```

And here is `\do@ballast` itself. It advances `\absline@num` within the protection of a group to make its check for what happens on the next line.

```
1120 \newcommand*{\do@ballast}{\global\ballast@count \z@
1121 \begingroup
1122   \advance\absline@num \@ne
1123   \ifnum\next@actionline=\absline@num
1124     \ifnum\next@action>-1001\relax
1125     \global\advance\ballast@count by -\c@ballast
1126   \fi
1127 \fi
1128 \endgroup}
```

`\do@actions` The `\do@actions` macro looks at the list of actions to take at particular absolute
`\do@actions@next` line numbers, and does everything that's specified for the current line.

It may call itself recursively, and to do this efficiently (using T_EX's optimization for tail recursion), we define a control-sequence called `\do@actions@next` that is always the last thing that `\do@actions` does. If there could be more actions to process for this line, `\do@actions@next` is set equal to `\do@actions`; otherwise it's just `\relax`.

```
1129 \newcommand*{\do@actions}{%
1130   \global\let\do@actions@next=\relax
1131   \ifnum\absline@num<\next@actionline\else
```

First, page number changes, which will generally be the most common actions. If we're restarting lineation on each page, this is where it happens.

```
1132   \ifnum\next@action>-1001
1133     \global\page@num=\next@action
1134     \ifbypage@
1135       \global\line@num=\z@ \global\subline@num=\z@
1136       \resetprevline@
1137   \fi
```

Next, we handle commands that change the line-number values. (We subtract 5001 rather than 5000 here because the line number is going to be incremented automatically in `\getline@num`.)

```
1138   \else
1139     \ifnum\next@action<-4999
1140       \@l@dtmpcnta=-\next@action
1141       \advance\@l@dtmpcnta by -5001
1142     \ifsublines@
```

```

1143      \global\subline@num=\@l@tempcnta
1144      \else
1145          \global\line@num=\@l@tempcnta
1146      \fi

```

It's one of the fixed codes. We rescale the value in `\@l@tempcnta` so that we can use a case statement.

```

1147      \else
1148          \@l@tempcnta=-\next@action
1149          \advance\@l@tempcnta by -1000
1150          \do@actions@fixedcode
1151      \fi
1152  \fi

```

Now we get information about the next action off the list, and then set `\do@actions@next` so that we'll call ourself recursively: the next action might also be for this line.

There's no warning if we find `\actionlines@list` empty, since that will always happen near the end of the section.

```

1153      \ifx\actionlines@list\empty
1154          \gdef\next@actionline{1000000}%
1155      \else
1156          \gl@p\actionlines@list\to\next@actionline
1157          \gl@p\actions@list\to\next@action
1158          \global\let\do@actions@next=\do@actions
1159      \fi
1160  \fi

```

Make the recursive call, if necessary.

```

1161 \do@actions@next}
1162

```

`\do@actions@fixedcode` This macro handles the fixed codes for `\do@actions`. It is one big case statement.

```

1163 \newcommand*{\do@actions@fixedcode}{%
1164   \ifcase\@l@tempcnta
1165     \or%                % 1001
1166       \global\sublines@true
1167     \or%                % 1002
1168       \global\sublines@false
1169     \or%                % 1003
1170       \global\@lock=\@ne
1171     \or%                % 1004
1172       \ifnum\@lock=\tw@
1173         \global\@lock=\thr@@
1174       \else
1175         \global\@lock=\z@
1176       \fi
1177     \or%                % 1005
1178       \global\sub@lock=\@ne

```

```

1179 \or% % 1006
1180 \ifnum\sub@lock=\tw@
1181 \global\sub@lock=\thr@@
1182 \else
1183 \global\sub@lock=\z@
1184 \fi
1185 \or% % 1007
1186 \l@dskipnumbertrue
1187 \else
1188 \led@warn@BadAction
1189 \fi}
1190
1191

```

23.4 Line number printing

`\affixline@num` `\affixline@num` originally took a single argument, a series of commands for printing the line just split off by `\do@line`; it put that line back on the vertical list, and added a line number if necessary. It now just puts a left line number into `\l@dld@ta` or a right line number into `\l@drd@ta` if required.

To determine whether we need to affix a line number to this line, we compute the following:

$$n = \text{int}((\text{linenum} - \text{firstlinenum}) / \text{linenumincrement})$$

$$m = \text{firstlinenum} + (n \times \text{linenumincrement})$$

(where *int* truncates a real number to an integer). *m* will be equal to *linenum* only if we're to paste a number on here. However, the formula breaks down for the first line to number (and any before that), so we check that case separately: if `\line@num ≤ \firstlinenum`, we compare the two directly instead of making these calculations.

We compute, in the scratch counter `\@l@tempcnta`, the number of the next line that should be printed with a number (*m* in the above discussion), and move the current line number into the counter `\@l@tempcntb` for comparison.

First, the case when we're within a sub-line range.

```

1192 \newcommand*{\affixline@num}{%
No number is attached if \ifl@dskipnumber is TRUE (and then it is set to its
normal FALSE value). No number is attached if \ifnumberline is FALSE (the
normal value is TRUE).
1193 \ifledgroupnotesL@\else\ifnumberline
1194 \ifl@dskipnumber
1195 \global\l@dskipnumberfalse
1196 \else
1197 \ifsublines@
1198 \@l@tempcntb=\subline@num
1199 \ifnum\subline@num>\c@firstsublinenum
1200 \@l@tempcnta=\subline@num
1201 \advance\@l@tempcnta by-\c@firstsublinenum

```

```

1202      \divide\@l@dtmpcnta by\c@sublinenumincrement
1203      \multiply\@l@dtmpcnta by\c@sublinenumincrement
1204      \advance\@l@dtmpcnta by\c@firstsublinenum
1205      \else
1206      \@l@dtmpcnta=\c@firstsublinenum
1207      \fi

```

That takes care of computing the values for comparison, but if line number locking is in effect we have to make a further check. If this check fails, then we disable the line-number display by setting the counters to arbitrary but unequal values.

```

1208      \ch@cksub@l@ck

```

Now the line number case, which works the same way.

```

1209      \else
1210      \@l@dtmpcntb=\line@num

```

Check on the `\linenumberlist` If it's `\empty` use the standard algorithm.

```

1211      \ifx\linenumberlist\empty
1212      \ifnum\line@num>\c@firstlinenum
1213      \@l@dtmpcnta=\line@num
1214      \advance\@l@dtmpcnta by-\c@firstlinenum
1215      \divide\@l@dtmpcnta by\c@linenumincrement
1216      \multiply\@l@dtmpcnta by\c@linenumincrement
1217      \advance\@l@dtmpcnta by\c@firstlinenum
1218      \else
1219      \@l@dtmpcnta=\c@firstlinenum
1220      \fi
1221      \else

```

The `\linenumberlist` wasn't `\empty`, so here's Wayne's numbering mechanism. This takes place in TeX's mouth.

```

1222      \@l@dtmpcnta=\line@num
1223      \edef\rem@inder{\linenumberlist,\number\line@num,}%
1224      \edef\sc@n@list{\def\noexpand\sc@n@list
1225      ###1,\number\@l@dtmpcnta,###2|{\def\noexpand\rem@inder{###2}}}%
1226      \sc@n@list\expandafter\sc@n@list\rem@inder|
1227      \ifx\rem@inder\empty\advance\@l@dtmpcnta\@ne\fi
1228      \fi

```

A locking check for lines, just like the version for sub-line numbers above.

```

1229      \ch@ck@l@ck
1230      \fi

```

The following test is true if we need to print a line number.

```

1231      \ifnum\@l@dtmpcnta=\@l@dtmpcntb

```

If we got here, we're going to print a line number; so now we need to calculate a number that will tell us which side of the page will get the line number. We start from `\line@margin`, which asks for one side always if it's less than 2; and then if the side does depend on the page number, we simply add the page number to this side code—because the values of `\line@margin` have been devised so that this

produces a number that's even for left-margin numbers and odd for right-margin numbers.

For L^AT_EX we have to consider two column documents as well. In this case I think we need to put the numbers at the outside of the column — the left of the first column and the right of the second. Do the twocolumn stuff before going on with the original code.

`\l@dld@ta` A left line number is stored in `\l@dld@ta` and a right one in `\l@drd@ta`.

```
\l@drd@ta 1232 \if@twocolumn
1233     \if@firstcolumn
1234         \gdef\l@dld@ta{\llap{\leftlinenum}}}%
1235     \else
1236         \gdef\l@drd@ta{\rlap{\rightlinenum}}}%
1237     \fi
1238 \else
```

Continuing the original code ...

```
1239     \l@dtmptb=\line@margin
1240     \ifnum\l@dtmptb>\@ne
1241         \advance\l@dtmptb \page@num
1242     \fi
```

Now print the line (#1) with its page number.

```
1243     \ifodd\l@dtmptb
1244         \gdef\l@drd@ta{\rlap{\rightlinenum}}}%
1245     \else
1246         \gdef\l@dld@ta{\llap{\leftlinenum}}}%
1247     \fi
1248 \fi
1249 \else
```

As no line number is to be appended, we just print the line as is.

```
1250 %%     #1%
1251 \fi
```

Now fix the lock counters, if necessary. A value of 1 is advanced to 2; 3 advances to 0; other values are unchanged.

```
1252 \f@x@l@cks
1253 \fi
1254 \fi
1255 \fi
1256 }
1257
```

`\ch@cksub@l@ck` These macros handle line number locking for `\affixline@num`. `\ch@cksub@l@ck`
`\ch@ck@l@ck` checks subline locking. If it fails, then we disable the line-number display by setting
`\f@x@l@cks` the counters to arbitrary but unequal values.

```
1258 \newcommand*{\ch@cksub@l@ck}{%
1259     \ifcase\sub@lock
1260         \or
```

```

1261      \ifnum\sublock@disp=\@ne
1262          \@l@dttempcntb=\z@ \@l@dttempcnta=\@ne
1263      \fi
1264      \or
1265          \ifnum\sublock@disp=\tw@ \else
1266              \@l@dttempcntb=\z@ \@l@dttempcnta=\@ne
1267          \fi
1268      \or
1269          \ifnum\sublock@disp=\z@
1270              \@l@dttempcntb=\z@ \@l@dttempcnta=\@ne
1271          \fi
1272      \fi}

```

Similarly for line numbers.

```

1273 \newcommand*{\ch@ck@l@ck}{%
1274     \ifcase\@lock
1275     \or
1276         \ifnum\lock@disp=\@ne
1277             \@l@dttempcntb=\z@ \@l@dttempcnta=\@ne
1278         \fi
1279     \or
1280         \ifnum\lock@disp=\tw@ \else
1281             \@l@dttempcntb=\z@ \@l@dttempcnta=\@ne
1282         \fi
1283     \or
1284         \ifnum\lock@disp=\z@
1285             \@l@dttempcntb=\z@ \@l@dttempcnta=\@ne
1286         \fi
1287     \fi}

```

Fix the lock counters. A value of 1 is advanced to 2; 3 advances to 0; other values are unchanged.

```

1288 \newcommand*{\f@x@l@cks}{%
1289     \ifcase\@lock
1290     \or
1291         \global\@lock=\tw@
1292     \or \or
1293         \global\@lock=\z@
1294     \fi
1295     \ifcase\sub@lock
1296     \or
1297         \global\sub@lock=\tw@
1298     \or \or
1299         \global\sub@lock=\z@
1300     \fi}
1301

```

`\pageparbreak` Because of TeX's asynchronous page breaking mechanism we can never be sure juust where it will make a break and, naturally, it has already decided exactly how it will typeset any remainder of a paragraph that crosses the break. This

is disconcerting when trying to number lines by the page or put line numbers in different margins. This macro tries to force an invisible paragraph break and a page break.

```
1302 \newcommand{\pageparbreak}{\pend\newpage\pstart\noindent}
1303
```

23.5 Pstart number printing in side

In side, the printing of pstart number is running like the printing of line number. There is only some differences:

- The pstarts counter is upgrade in the `\pend` command. Consequently, the `\affixpstart@num` command has not to upgrade it, unlike the `\affixline@num` which upgrades the lines counter.
- To print the pstart number only at the beginning of a pstart, and not in every line, a boolean test is made. The `\pstartnum` boolean is set to TRUE at every `\pend`. It's tried in the `\leftpstartnum` and `\rightpstartnum` commands. After the try, it is set to FALSE.

```
\leftpstartnum
\rightpstartnum 1304
\ifsidepstartnum 1305 \newif\ifsidepstartnum
1306 \newcommand*{\affixpstart@num}{%
1307   \ifsidepstartnum
1308     \if@twocolumn
1309       \if@firstcolumn
1310         \gdef\l@dld@ta{\llap{\leftpstartnum}}}%
1311       \else
1312         \gdef\l@drd@ta{\rlap{\rightpstartnum}}}%
1313     \fi
1314   \else
1315     \@l@tempcntb=\line@margin
1316     \ifnum\@l@tempcntb>\@ne
1317       \advance\@l@tempcntb \page@num
1318     \fi
1319     \ifodd\@l@tempcntb
1320       \gdef\l@drd@ta{\rlap{\rightpstartnum}}}%
1321     \else
1322       \gdef\l@dld@ta{\llap{\leftpstartnum}}}%
1323     \fi
1324   \fi
1325 \fi
1326
1327 }
1328 %
1329
1330 \newif\ifpstartnum
1331 \pstartnumtrue
```



```

1332 \newcommand*{\leftpstartnum}{
1333     \ifpstartnum\thepstart
1334     \kern\linenumsep\fi
1335     \global\pstartnumfalse
1336 }
1337 \newcommand*{\rightpstartnum}{
1338     \ifpstartnum
1339     \kern\linenumsep
1340     \thepstart
1341     \fi
1342     \global\pstartnumfalse
1343 }

```

23.6 Add insertions to the vertical list

`\inserts@list` `\inserts@list` is the list macro that contains the inserts that we save up for one paragraph.

```
1344 \list@create{\inserts@list}
```

`\add@inserts` `\add@inserts` is the penultimate macro used by `\do@line`; it takes insertions saved in a list macro and sends them onto the vertical list.

It may call itself recursively, and to do this efficiently (using \TeX 's optimization for tail recursion), we define a control-sequence called `\add@inserts@next` that is always the last thing that `\add@inserts` does. If there could be more inserts to process for this line, `\add@inserts@next` is set equal to `\add@inserts`; otherwise it's just `\relax`.

```

1345 \newcommand*{\add@inserts}{%
1346     \global\let\add@inserts@next=\relax

```

If `\inserts@list` is empty, there aren't any more notes or insertions for this paragraph, and we needn't waste our time.

```
1347 \ifx\inserts@list\empty \else
```

The `\next@insert` macro records the number of the line that receives the next footnote or other insert; it's empty when we start out, and just after we've affixed a note or insert.

```

1348 \ifx\next@insert\empty
1349     \ifx\insertlines@list\empty
1350         \global\noteschanged@true
1351         \gdef\next@insert{100000}%
1352     \else
1353         \gl@p\insertlines@list\to\next@insert
1354     \fi
1355 \fi

```

If the next insert's for this line, tack it on (and then erase the contents of the insert macro, as it could be quite large). In that case, we also set `\add@inserts@next` so that we'll call ourself recursively: there might be another insert for this same line.

```

1356 \ifnum\next@insert=\absline@num
1357   \gl@p\inserts@list\to\@insert
1358   \@insert
1359   \global\let\@insert=\undefined
1360   \global\let\next@insert=\empty
1361   \global\let\add@inserts@next=\add@inserts
1362 \fi
1363 \fi

```

Make the recursive call, if necessary.

```

1364 \add@inserts@next}
1365

```

23.7 Penalties

`\add@penalties` `\add@penalties` is the last macro used by `\do@line`. It adds up the club, widow, and interline penalties, and puts a single penalty of the appropriate size back into the paragraph; these penalties get removed by the `\vsplit` operation. `\displaywidowpenalty` and `\brokenpenalty` are not restored, since we have no easy way to find out where we should insert them.

In this code, `\num@lines` is the number of lines in the whole paragraph, and `\par@line` is the line we're working on at the moment. The count `\@l@tempcnta` is used to calculate and accumulate the penalty; it is initially set to the value of `\ballast@count`, which has been worked out in `\do@ballast` above (p.89).

Finally, the penalty is checked to see that it doesn't go below -10000 .

```

1366 \newcommand*{\add@penalties}{\@l@tempcnta=\ballast@count
1367   \ifnum\num@lines>\@ne
1368     \global\advance\par@line \@ne
1369     \ifnum\par@line=\@ne
1370       \advance\@l@tempcnta \clubpenalty
1371     \fi
1372     \@l@tempcntb=\par@line \advance\@l@tempcntb \@ne
1373     \ifnum\@l@tempcntb=num@lines
1374       \advance\@l@tempcnta \widowpenalty
1375     \fi
1376     \ifnum\par@line<\num@lines
1377       \advance\@l@tempcnta \interlinepenalty
1378     \fi
1379   \fi
1380   \ifnum\@l@tempcnta=\z@
1381     \relax
1382   \else
1383     \ifnum\@l@tempcnta>-10000
1384       \penalty\@l@tempcnta
1385     \else
1386       \penalty -10000
1387     \fi
1388   \fi}
1389

```

23.8 Printing leftover notes

`\flush@notes` The `\flush@notes` macro is called after the entire paragraph has been sliced up and sent on to the vertical list. If the number of notes to this paragraph has increased since the last run of `TEX`, then there can be leftover notes that haven't yet been printed. An appropriate error message will be printed elsewhere; but it's best to go ahead and print these notes somewhere, even if it's not in quite the right place. What we do is dump them all out here, so that they should be printed on the same page as the last line of the paragraph. We can hope that's not too far from the proper location, to which they'll move on the next run.

```

1390 \newcommand*{\flush@notes}{%
1391   \@xloop
1392   \ifx\inserts@list\empty \else
1393     \gl@p\inserts@list\to\@insert
1394     \@insert
1395     \global\let\@insert=\undefined
1396   \repeat}
1397
```

`\@xloop` `\@xloop` is a variant of the PLAIN `TEX` `\loop` macro, useful when it's hard to construct a positive test using the `TEX` `\if` commands—as in `\flush@notes` above. One says `\@xloop ... \if ... \else ... \repeat`, and the action following `\else` is repeated as long as the `\if` test fails. (This macro will work wherever the PLAIN `TEX` `\loop` is used, too, so we could just call it `\loop`; but it seems preferable not to change the definitions of any of the standard macros.)

This variant of `\loop` was introduced by Alois Kabelschacht in *TUGboat* 8 (1987), pp. 184–5.

```

1398 \def\@xloop#1\repeat{%
1399   \def\body{#1\expandafter\body\fi}%
1400   \body}
1401
```

24 Critical footnotes

The footnote macros are adapted from those in PLAIN `TEX`, but they differ in these respects: the outer-level commands must add other commands to a list macro rather than doing insertions immediately; there are five separate levels of the footnotes, not just one; and there are options to reformat footnotes into paragraphs or into multiple columns.

24.1 Fonts

Before getting into the details of formatting the notes, we set up some font macros. It is the notes that present the greatest challenge for our font-handling mechanism, because we need to be able to take fragments of our main text and print them in different forms: it is common to reduce the size, for example, without otherwise changing the fonts used.

`\select@lemmafont` `\select@lemmafont` is provided to set the right font for the lemma in a note.
`\select@@lemmafont` This macro extracts the font specifier from the line and page number cluster, and issues the associated font-changing command, so that the lemma is printed in its original font.

```

1402 \def\select@lemmafont#1|#2|#3|#4|#5|#6|#7|{\select@@lemmafont#7|}
1403 \def\select@@lemmafont#1/#2/#3/#4|{%
1404     {\fontencoding{#1}\fontfamily{#2}\fontseries{#3}\fontshape{#4}%
1405     \selectfont}
1406 
```

24.2 Outer-level footnote commands

`\footnoteoptions@` The `\footnoteoption@` [*side*] [*options*] [*value*] change the value of on options of Xfootnote, to switch between true and false.

```

1407 \newcommandx*{\footnoteoptions@}[3][1=L,usedefault]{%
1408     \def\do##1{%
1409         \ifstrequal{#1}{L}{% In Leftside
1410             \xright@appenditem{\global\noexpand\settoggle{##1@}{#3}}\to\inserts@list% Switch
1411             \global\advance\insert@count \@ne% Increment the left insert counter.
1412         }%
1413         {%
1414             \xright@appenditem{\global\noexpand\settoggle{##1@}{#3}}\to\inserts@listR% Swit
1415             \global\advance\insert@countR \@ne% Increment the right insert counter insert.
1416         }%
1417     }%
1418     \notblank{#2}{\docsvlist{#2}}}% Parsing all options
1419 }
```

`\footnotelang@lua` `\footnotelang@lua` is called to remember the information about the language of a lemma when LuaLaTeX is used.

```

1420 \newcommandx*{\footnotelang@lua}[1][1=L,usedefault]{%
1421     \ifstrequal{#1}{L}{%
1422         \xright@appenditem{{\csxdef{footnote@luatextextdir}{\the\luatextextdir}}}\to\inserts@list
1423         \global\advance\insert@count \@ne%
1424         \xright@appenditem{{\csxdef{footnote@luatexpardir}{\the\luatexpardir}}}\to\inserts@listR
1425         \global\advance\insert@countR \@ne%
1426     }%
1427     {%
1428         \xright@appenditem{{\csxdef{footnote@luatextextdir}{\the\luatextextdir}}}\to\inserts@list
1429         \global\advance\insert@countR \@ne%
1430         \xright@appenditem{{\csxdef{footnote@luatexpardir}{\the\luatexpardir}}}\to\inserts@listR
1431         \global\advance\insert@countR \@ne%
1432     }%
1433 }
```

`\footnotelang@poly` `\footnotelang@poly` is called to remember the information about the language of a lemma when Polyglossia is used.

```

1434 \newcommandx*{\footnotelang@poly}[1][1=L,usedefault]{%
```

```

1435 \ifstrequal{#1}{L}{%
1436   \ifRTL%
1437     \xright@appenditem{{\csxdef{footnote@dir}{@RTLtrue}}}\to\inserts@list%Know the language of le
1438     \global\advance\insert@count \@ne%
1439   \else
1440     \xright@appenditem{{\csxdef{footnote@dir}{@RTLfalse}}}\to\inserts@list%Know the language of
1441     \global\advance\insert@count \@ne%
1442   \fi%
1443   \xright@appenditem{{\csxdef{footnote@lang}{\csexpandonce{language name}}}\to\inserts@list%Know th
1444   \global\advance\insert@count \@ne%
1445 }%
1446 {%
1447   \ifRTL
1448     \xright@appenditem{{\csxdef{footnote@dir}{@RTLtrue}}}\to\inserts@listR%Know the language of l
1449     \global\advance\insert@countR \@ne%
1450   \else
1451     \xright@appenditem{{\csxdef{footnote@dir}{@RTLfalse}}}\to\inserts@listR%Know the language of
1452     \global\advance\insert@countR \@ne%
1453   \fi
1454   \xright@appenditem{{\csxdef{footnote@lang}{\csexpandonce{language name}}}\to\inserts@listR%Know t
1455   \global\advance\insert@countR \@ne%
1456 }%
1457 }

```

24.3 Normal footnote formatting

The processing of each note is done by four principal macros: the `\vfootnote` macro takes the text of the footnote and does the `\insert`; it calls on the `\footfmt` macro to select the right fonts, print the line number and lemma, and do any other formatting needed for that individual note. Within the output routine, the two other macros, `\footstart` and `\footgroup`, are called; the first prints extra vertical space and a footnote rule, if desired; the second does any reformatting of the whole set of the footnotes in this series for this page—such as paragraphing or division into columns—and then sends them to the page.

These four macros, and the other macros and parameters shown here, are distinguished by the ‘series letter’ that indicates which set of the footnotes we’re dealing with—A, B, C, D, or E. The series letter always precedes the string `foot` in macro and parameter names. Hence, for the A series, the four macros are called `\vAfootnote`, `\Afootfmt`, `\Afootstart`, and `\Afootgroup`.

\normalvfootnote We now begin a series of commands that do ‘normal’ footnote formatting: a format much like that implemented in PLAIN T_EX, in which each footnote is a separate paragraph.

`\normalvfootnote` takes the series letter as `#1`, and the entire text of the footnote is `#2`. It does the `\insert` for this note, calling on the `\footfmt` macro for this note series to format the text of the note.

```

1458 \notbool{parapparatus@}{\newcommand*}{\newcommand}{\normalvfootnote}[2]{%
1459   \insert\csname #1footins\endcsname\bgroup

```

```

1460 \csuse{bhookXnote@#1}
1461 \csuse{Xnotefontsize@#1}
1462 \footssplitskips
1463 \ifl@dpairing\ifl@dpaging\else%
1464   \setXnoteswidthliketwocolumns@{#1}%
1465 \fi\fi%
1466 \setXnotespositionliketwocolumns@{#1}%
1467 \spaceskip=\z@skip \xspaceskip=\z@skip
1468 \csname #1footfmt\endcsname #2[#1]\egroup}

```

`\footssplitskips` Some setup code that is common for a variety of the footnotes.

```

1469 \newcommand*{\footssplitskips}{%
1470   \interlinepenalty=\interfootnotelinepenalty
1471   \floatingpenalty=\@MM
1472   \splittopskip=\ht\strutbox \splitmaxdepth=\dp\strutbox
1473   \leftskip=\z@skip \rightskip=\z@skip}
1474

```

`\mpnormalvfootnote` And a somewhat different version for minipages.

```

1475 \notbool{parapparatus@}{\newcommand*}{\newcommand}{\mpnormalvfootnote}[2]{%
1476   \global\setbox\@nameuse{mp#1footins}\vbox{%
1477     \unvbox\@nameuse{mp#1footins}
1478     \csuse{bhookXnote@#1}
1479     \csuse{Xnotefontsize@#1}
1480     \hsize\columnwidth
1481     \@parboxrestore
1482     \color@begingroup
1483     \csname #1footfmt\endcsname #2[#1]\color@endgroup}}
1484

```

`\ledsetnormalparstuff` `\normalfootfmt` is a ‘normal’ macro to take the footnote line and page number information (see p.61), and the desired text, and output what’s to be printed. Argument #1 contains the line and page number information and lemma font specifier; #2 is the lemma; #3 is the note’s text. This version is very rudimentary—it uses `\printlines` to print just the range of line numbers, followed by a square bracket, the lemma, and the note text; it’s intended to be copied and modified as necessary.

`\par` should always be redefined to `\endgraf` within the format macro (this is what `\normal@pars` does), to override tricky material in the main text to get the lines numbered automatically (as set up by `\autopar`, for example).

```

1485 \newcommand*{\ledsetnormalparstuff}{%
1486   \ifluatex%
1487     \luatextextdir\footnote@luatextextdir%
1488     \luatexpardir\footnote@luatexpardir%
1489   \fi%
1490   \csuse{\csuse{footnote@dir}}}%
1491   \normal@pars%
1492   \noindent \parfillskip \z@ \@plus 1fil}

```

```

1493
1494 \notbool{parapparatus@}{\newcommandx*}{\newcommandx}{\normalfootfmt}[4][4=Z]{% 4th arg is optional, f
1495   \ledsetnormalparstuff%
1496   \hangindent=\csuse{Xhangindent@#4}
1497   \strut{\printlinefootnote{#1}{#4}}%
1498   {\nottoggle{Xlemmadisablefontselection@#4}{\select@lemmafont#1|#2}{#2}}%
1499   \iftoggle{nosep@}{\hskip\csuse{inplaceoflemmaseparator@#4}}{\ifcsemtyp{lemmaseparator@#4}%
1500     {\hskip\csuse{inplaceoflemmaseparator@#4}}%
1501     {\nobreak\hskip\csuse{beforelemmaseparator@#4}\csuse{lemmaseparator@#4}\hskip\csuse{afterlemmasep
1502   }}%
1503   #3\strut\par}

```

\endashchar The fonts that are used for printing notes might not have the character mapping we expect: for example, the Computer Modern font that contains old-style numerals does not contain an en-dash or square brackets, and its period and comma are in odd locations. To allow use of the standard footnote macros with such fonts, we use the following macros for certain characters.

The **\endashchar** macro is simply an en-dash from the normal font and is immune to changes in the surrounding font. The same goes for the full stop. These two are used in **\printlines**. The right bracket macro is the same again; it crops up in **\normalfootfmt** and the other footnote macros for controlling the format of the footnotes.

With polyglossia, each critical note has a **\footnote@lang** which shows the language of the lemma, and which can be used to switch the bracket from right to left.

```

1504 \def\endashchar{\textnormal{--}}
1505 \newcommand*{\fullstop}{\textnormal{.}}
1506 \newcommand*{\rbracket}{\textnormal{}}
1507   \csuse{text}\csuse{footnote@lang}}{%
1508     \ifluatex%
1509     \ifdefstring{footnote@luatextextdir}{TRT}{\thinspace[]\thinspace}%
1510     \else%
1511     \thinspace}%
1512     \fi}%
1513   }%
1514 }
1515

```

\printpstart The **\printpstart** macro prints the pstart number for a note.

```

1516 \newcommand{\printpstart}[0]{%
1517   \ifl@dpairing%
1518   \ifledRcol%
1519     \thepstartR%
1520   \else%
1521     \thepstartL%
1522   \fi%
1523   \else%
1524     \thepstart%

```

```

1525     \fi%
1526 }

```

The `\printlines` macro prints the line numbers for a note—which, in the general case, is a rather complicated task. The seven parameters of the argument are the line numbers as stored in `\l@d@nums`, in the form described on page 61: the starting page, line, and sub-line numbers, followed by the ending page, line, and sub-line numbers, and then the font specifier for the lemma.

The original EDMAC code used several counters at this point, saying:

To simplify the logic, we use a lot of counters to tell us which numbers need to get printed (using 1 for yes, 0 for no, so that `\ifodd` tests for ‘yes’). The counter assignments are:

- `\@pnun` for page numbers;
- `\@ssub` for starting sub-line;
- `\@elin` for ending line;
- `\@esl` for ending sub-line; and
- `\@dash` for the dash between the starting and ending groups.

There’s no counter for the line number because it’s always printed.

L^AT_EX tends to use a lot of counters and packages should try and minimise the number of new ones they create. In line with this Peter Wilson have reverted to traditional booleans.

```

\ifl@d@pnun
\ifl@d@ssub 1527 \newif\ifl@d@pnun
\ifl@d@elin 1528 \l@d@pnunfalse
\ifl@d@esl 1529 \newif\ifl@d@ssub
\ifl@d@dash 1530 \l@d@ssubfalse
1531 \newif\ifl@d@elin
1532 \l@d@elinfalse
1533 \newif\ifl@d@esl
1534 \l@d@eslfalse
1535 \newif\ifl@d@dash
1536 \l@d@dashfalse

\l@dp@rsefootsspec \l@dp@rsefootsspec{<spec>}{<lemma>}{<text>} parses a footnote specification.
\l@dp@rsefootsspec <lemma> and <text> are the lemma and text respectively. <spec> is the line and
\l@dp@rsefootsspec page number and lemma font specifier in \l@d@nums style format. The real work
\l@dp@rsefootsspec is done by \l@dp@rsefootsspec which defines macros holding the numeric values.
\l@dp@rsefootsspec 1537 \newcommand*{\l@dp@rsefootsspec}[3]{\l@dp@rsefootsspec#1|}
\l@dp@rsefootsspec 1538 \def\l@dp@rsefootsspec#1|#2|#3|#4|#5|#6|#7|{%
\l@dp@rsefootsspec 1539 \gdef\l@dp@rsefootsspec#1{%
\l@dp@rsefootsspec 1540 \gdef\l@dp@rsefootsspec#2{%
1541 \gdef\l@dp@rsefootsspec#3{%
1542 \gdef\l@dp@rsefootsspec#4{%
1543 \gdef\l@dp@rsefootsspec#5{%
1544 \gdef\l@dp@rsefootsspec#6{%
1545 }

```


Initialise the several number value macros.

```
1546 \def\l@dparsedstartpage{0}%
1547 \def\l@dparsedstartline{0}%
1548 \def\l@dparsedstartsub{0}%
1549 \def\l@dparsedendpage{0}%
1550 \def\l@dparsedendline{0}%
1551 \def\l@dparsedendsub{0}%
1552
```

\setprintlines First of all, we print the page numbers only if: 1) we're doing the lineation by page, and 2) the ending page number is different from the starting page number.

Just a reminder of the arguments:

```
\printlines    #1      | #2 | #3      | #4      | #5 | #6      | #7
\printlines start-page | line | subline | end-page | line | subline | font
```

The macro **\setprintlines** does the work of deciding what numbers should be printed. Its arguments are the same as the first 6 of **\printlines**.

```
1553 \newcommand*\setprintlines}[6]{%
1554   \l@dpnumfalse \l@ddashfalse
1555   \ifbypage@
1556     \ifnum#4=#1 \else
1557       \l@dpnumtrue
1558       \l@ddashtrue
1559     \fi
1560   \fi
```

We print the ending line number if: (1) we're printing the ending page number, or (2) it's different from the starting line number.

```
1561   \ifl@dpnum \l@d@elintrue \else \l@d@elinfalse \fi
1562   \ifnum#2=#5 \else
1563     \l@d@elintrue
1564     \l@ddashtrue
1565   \fi
```

We print the starting sub-line if it's nonzero.

```
1566   \l@d@ssubfalse
1567   \ifnum#3=0 \else
1568     \l@d@ssubtrue
1569   \fi
```

We print the ending sub-line if it's nonzero and: (1) it's different from the starting sub-line number, or (2) the ending line number is being printed.

```
1570   \l@d@eslfalse
1571   \ifnum#6=0 \else
1572     \ifnum#6=#3
1573       \ifl@d@elin \l@d@esltrue \else \l@d@eslfalse \fi
1574     \else
1575       \l@d@esltrue
1576       \l@ddashtrue
1577     \fi
1578   \fi}
```

`\printlines` Now we're ready to print it all. If the lineation is by `pstart`, we print the `pstart`.

```

1579 \def\printlines#1|#2|#3|#4|#5|#6|#7|{\begingroup
1580   \setprintlines{#1}{#2}{#3}{#4}{#5}{#6}%

One subtlety left here is when to print a period between numbers. But the only
instance in which this is tricky is for the ending sub-line number: it could come
after the starting sub-line number (in which case we want only the dash) or after
an ending line number (in which case we need to insert a period).

1581   \ifl@d@pnum #1\fullstop\fi
1582   \linenumrep{#2}

1583   \ifl@d@ssub \fullstop \sublinenumrep{#3}\fi
1584   \ifl@d@dash \endashchar\fi
1585   \ifl@d@pnum #4\fullstop\fi
1586   \ifl@d@elin \linenumrep{#5}\fi
1587   \ifl@d@esl \ifl@d@elin \fullstop\fi \sublinenumrep{#6}\fi
1588 \endgroup}

```

`\normalfootstart` `\normalfootstart` is a standard footnote-starting macro, called in the output routine whenever there are footnotes of this series to be printed: it skips a bit and then draws a rule.

Any `footstart` macro must put onto the page something that takes up space exactly equal to the `\skip\footins` value for the associated series of notes. `TEX` makes page computations based on that `\skip` value, and the output pages will suffer from spacing problems if what you add takes up a different amount of space.

But if the `\skip \preXnotes@` is greater than 0 pt, it's used instead of `\skip\footins` for the first printed series.

The `\leftskip` and `\rightskip` values are both zeroed here. Similarly, these skips are cancelled in the `vfootnote` macros for the various types of notes. Strictly speaking, this is necessary only if you are using paragraphed footnotes, but we have put it here and in the other `vfootnote` macros too so that the behavior of `eledmac` in this respect is general across all footnote types (you can change this). What this means is that any `\leftskip` and `\rightskip` you specify applies to the main text, but not the footnotes. The footnotes continue to be of width `\hsize`.

```

1589 \newcommand*{\normalfootstart}[1]{%
1590   \ifdimequal{0pt}{\preXnotes@}{}%
1591   {%
1592     \iftoggle{preXnotes@}{%
1593       \togglefalse{preXnotes@}\skip\c@name #1footins\endc@name=\csuse{preXnotes@}}%
1594     }%
1595   }%
1596   \vskip\skip\c@name #1footins\endc@name%
1597   \leftskip0pt \rightskip0pt
1598   \ifl@dpairing\else%
1599     \hsize=\old@hsize%
1600   \fi%
1601   \setXnoteswidthliketwocolumns@{#1}%

```

```

1602 \setXnotespositionliketwocolumns@{#1}%
1603 \print@Xfootnoterule{#1}%%
1604 \vskip\csuse{afterXrule@#1}%
1605 \noindent\leavevmode}

\normalfootnoterule \normalfootnoterule is a standard footnote-rule macro, for use by a footstart
macro: just the same as the PLAIN TEX footnote rule.
1606 \let\normalfootnoterule=\footnoterule

\normalfootgroup \normalfootgroup is a standard footnote-grouping macro: it sends the contents
of the footnote-insert box to the output page without alteration.
1607 \newcommand*{\normalfootgroup}[1]{%
1608   {\csuse{Xnotefontsize@#1}\noindent\csuse{txtbeforeXnotes@#1}}%
1609   \unvbox\csname #1footins\endcsname%
1610   \hsize=\old@hsize%
1611   }%
1612

\mpnormalfootgroup A somewhat different version for minipages.
1613 \newcommand*{\mpnormalfootgroup}[1]{%
1614   \vskip\skip\@nameuse{mp#1footins}
1615   \ifl@dpairing\ifparledgroup%
1616     \leavevmode\marks\parledgroup@{begin}%
1617     \marks\parledgroup@series{#1}%
1618     \marks\parledgroup@type{Xfootnote}%
1619   \fi\fi\normalcolor%
1620   \ifparledgroup%
1621     \ifl@dpairing%
1622     \else%
1623       \setXnoteswidthliketwocolumns@{#1}%
1624       \setXnotespositionliketwocolumns@{#1}%
1625       \print@Xfootnoterule{#1}%%
1626       \vskip\csuse{afterXrule@#1}%
1627     \fi%
1628   \else%
1629     \setXnoteswidthliketwocolumns@{#1}%
1630     \setXnotespositionliketwocolumns@{#1}%
1631     \print@Xfootnoterule{#1}%%
1632     \vskip\csuse{afterXrule@#1}%
1633   \fi%
1634   \setlength{\parindent}{0pt}
1635   {\csuse{Xnotefontsize@#1}\csuse{txtbeforeXnotes@#1}}
1636   \unvbox\csname mp#1footins\endcsname}}
1637

```

24.4 Standard footnote definitions

`\footnormal` We can now define all the parameters for the five series of footnotes; initially they use the ‘normal’ footnote formatting, which is set up by calling `\footnormal`. You

can switch to another type of formatting by using `\footparagraph`, `\foottwocol`, or `\footthreecol`.

Switching to a variation of ‘normal’ formatting requires changing the quantities defined in `\footnormal`. The best way to proceed would be to make a copy of this macro, with a different name, make your desired changes in that copy, and then invoke it, giving it the letter of the footnote series you wish to control.

(We have not defined baseline skip values like `\abaselineskip`, since this is one of the quantities set in `\notefontsetup`.)

What we want to do here is to say something like the following for each footnote series. (This is an example, not part of the actual `eledmac` code.)

```
\skip\Afootins=12pt plus5pt minus5pt
\count\Afootins=1000
\dimen\Afootins=0.8\vsiz
\let\vAfootnote=\normalvfootnote \let\Afootfmt=\normalfootfmt
\let\Afootstart=\normalfootstart \let\Afootgroup=\normalfootgroup
\let\Afootnoterule=\normalfootnoterule
```

Instead of repeating ourselves, we define a `\footnormal` macro that makes all these assignments for us, for any given series letter. This also makes it easy to change from any different system of formatting back to the `normal` setting.

`\ledfootinsdim` Have a constant value for the `\dimen\footins`

1638 `\newcommand*{\ledfootinsdim}{0.8\vsiz}` % kept for backward compatibility, should’nt be us

`\preXnotes@` If user redefines `\preXnotes@`, via `\preXnotes` to a value greater than 0 pt, this
`\preXnotes` skip will be added before first series notes instead of the notes skip.

```
1639 \newtoggle{preXnotes@}
1640 \toggletrue{preXnotes@}
1641 \newcommand{\preXnotes@}{0pt}
1642 \newcommand*{\preXnotes}[1]{\renewcommand{\preXnotes@}{#1}}
```

The same, but for familiar footnotes.

```
\preXnotes
\preXnotes@ 1643 \newtoggle{prenotesX@}
1644 \toggletrue{prenotesX@}
1645 \newcommand{\prenotesX@}{0pt}
1646 \newcommand*{\prenotesX}[1]{\renewcommand{\prenotesX@}{#1}}
```

Now we set up the `\footnormal` macro itself. It takes one argument: the footnote series letter.

```
1647 \newcommand*{\footnormal}[1]{%
1648   \csgdef{series@display#1}{normal}
1649   \expandafter\let\csname #1footstart\endcsname=\normalfootstart
1650   \expandafter\let\csname v#1footnote\endcsname=\normalvfootnote
1651   \expandafter\let\csname #1footfmt\endcsname=\normalfootfmt
1652   \expandafter\let\csname #1footgroup\endcsname=\normalfootgroup
```

```

1653 \expandafter\let\csname #1footnoterule\endcsname=%
1654                                     \normalfootnoterule
1655 \count\csname #1footins\endcsname=1000
1656 \dimen\csname #1footins\endcsname=\csuse{maxhXnotes@#1}
1657 \skip\csname #1footins\endcsname=\csuse{beforeXnotes@#1}

```

Now do the setup for minipage footnotes. We use as much as possible of the normal setup as we can (so the notes will have a similar layout).

```

1658 \expandafter\let\csname mpv#1footnote\endcsname=\mpnormalvfootnote
1659 \expandafter\let\csname mp#1footgroup\endcsname=\mpnormalfootgroup
1660 \count\csname mp#1footins\endcsname=1000
1661 \dimen\csname mp#1footins\endcsname=\csuse{maxhXnotes@#1}
1662 \skip\csname mp#1footins\endcsname=\csuse{beforeXnotes@#1}
1663 }
1664

```

Some of these values deserve comment: the `\dimen` setting allows 80% of the page to be occupied by notes; the `\skip` setting is deliberately flexible, since pages with lots of notes attached to many of the lines can be a bit hard for T_EX to make.

24.5 Paraphrased footnotes

The `paraphrased-footnote` option reformats all the footnotes of one series for a page into a single paragraph; this is especially appropriate when the notes are numerous and brief. The code is based on *The T_EXbook*, pp.398–400, with alterations for our environment. This algorithm uses a considerable amount of save-stack space: a T_EX of ordinary size may not be able to handle more than about 100 notes of this kind on a page.

\footparagraph The `\footparagraph` macro sets up everything for one series of the footnotes so that they'll be paraphrased; it takes the series letter as argument. We include the setting of `\count\footins` to 1000 for the footnote series just in case you are switching to paraphrased footnotes after having columnar ones, since they change this value (see below).

It is important to call `\footparagraph` only after `\hsize` has been set for the pages that use this series of notes; otherwise T_EX will try to put too many or too few of these notes on each page. If you need to change the `\hsize` within the document, call `\footparagraph` again afterwards to take account of the new value. The argument of `\footparagraph` is the letter (A–E) denoting the series of notes to be paraphrased.

```

1665 \newcommand*{\footparagraph}[1]{%
1666   \csgdef{series@display#1}{paragraph}
1667   \expandafter\newcount\csname prevpage#1@num\endcsname
1668   \expandafter\let\csname #1footstart\endcsname=\parafootstart
1669   \expandafter\let\csname v#1footnote\endcsname=\para@vfootnote
1670   \expandafter\let\csname #1footfmt\endcsname=\parafootfmt
1671   \expandafter\let\csname #1footgroup\endcsname=\para@footgroup
1672   \count\csname #1footins\endcsname=1000

```

```

1673 \dimen\csname #1footins\endcsname=\csuse{maxhXnotes@#1}
1674 \skip\csname #1footins\endcsname=\csuse{beforeXnotes@#1}
1675 \para@footsetup{#1}

```

And the extra setup for minipages.

```

1676 \expandafter\let\csname mpv#1footnote\endcsname=\mppara@vfootnote
1677 \expandafter\let\csname mp#1footgroup\endcsname=\mppara@footgroup
1678 \count\csname mp#1footins\endcsname=1000
1679 \dimen\csname mp#1footins\endcsname=\csuse{maxhXnotes@#1}
1680 \skip\csname mp#1footins\endcsname=\csuse{beforeXnotes@#1}
1681 }

```

`\footfudgefiddle` For paragraphed footnotes \TeX has to estimate the amount of space required. If it underestimates this then the notes may get too long and run off the bottom of the text block. `\footfudgefiddle` can be increased from its default 64 (say to 70) to increase the estimate.

```
1682 \providecommand{\footfudgefiddle}{64}
```

`\para@footsetup` `\footparagraph` calls the `\para@footsetup` macro to calculate a special fudge factor, which is the ratio of the `\baselineskip` to the `\hsize`. We assume that the proper value of `\baselineskip` for the footnotes (normally 9pt) has been set already, in `\notefontsetup`. The argument of the macro is again the note series letter.

Peter Wilson thinks that `\columnwidth` should be used here for \LaTeX not `\hsize`. I've also included `\footfudgefiddle`.

```

1683 \newcommand*{\para@footsetup}[1]{\csuse{Xnotefontsize@#1}
1684 \setXnoteswidthliketwocolumns@#1}%
1685 \dimen0=\baselineskip
1686 \multiply\dimen0 by 1024
1687 \divide \dimen0 by \columnwidth \multiply\dimen0 by \footfudgefiddle\relax
1688 \csxdef{#1footfudgefactor}{%
1689 \expandafter\strip@pt\dimen0 }}
1690

```

EDMAC defines `\en@number` which does the same as the \LaTeX kernel `\strip@pt`, namely strip the characters `pt` from a `dimen` value. Eledmac use `\strip@pt`.

`\parafootstart` `\parafootstart` is the same as `\normalfootstart`, but we give it again to ensure that `\rightskip` and `\leftskip` are zeroed (this needs to be done before `\para@footgroup` in the output routine). You might have decided to change this for other kinds of note, but here it should stay as it is. The size of paragraphed notes is calculated using a fudge factor which in turn is based on `\hsize`. So the paragraph of notes needs to be that wide.

The argument of the macro is again the note series letter.

```

1691 \newcommand*{\parafootstart}[1]{%
1692 \rightskip=0pt \leftskip=0pt \parindent=0pt
1693 \ifdimequal{0pt}{\preXnotes@}{}%
1694 }%

```

```

1695     \iftoggle{preXnotes@}{%
1696         \togglefalse{preXnotes@}\skip\csname #1footins\endcsname=\csuse{preXnotes@}}%
1697     }%
1698 }%
1699 \vskip\skip\csname #1footins\endcsname%
1700 \setXnoteswidthliketwocolumns@{#1}%
1701 \setXnotespositionliketwocolumns@{#1}%
1702 \print@Xfootnoterule{#1}%
1703 \vskip\csuse{afterXrule@#1}%
1704 \noindent\leavevmode}

```

`\para@vfootnote` `\para@vfootnote` is a version of the `\vfootnote` command that's used for paraphed notes. It gets appended to the `\inserts@list` list by an outer-level footnote command like `\Afootnote`. The first argument is the note series letter; the second is the full text of the printed note itself, including line numbers, lemmata, and footnote text.

The initial model for this insertion is, of course, the `\insert\footins` definition in *The TeXbook*, p. 398. There, the footnotes are first collected up in hboxes, and these hboxes are later unpacked and stuck together into a paragraph.

However, Michael Downes has pointed out that because text in hboxes gets typeset in restricted horizontal mode, there are some undesirable side-effects if you later want to break such text across lines. In restricted horizontal mode, where \TeX does not expect to have to break lines, it does not insert certain items like `\discretionary`s. If you later unbox these hboxes and stick them together, as the *TeXbook* macros do to make these footnotes, you lose the ability to hyphenate after an explicit hyphen. This can lead to overfull `\hboxes` when you would not expect to find them, and to the uninitiated it might be very hard to see why the problem had arisen.²³

Wayne Sullivan pointed out to us another subtle problem that arises from the same cause: \TeX also leaves the `\language` whatsit nodes out of the horizontal list.²⁴ So changes from one language to another will not invoke the proper hyphenation rules in such footnotes. Since critical editions often do deal with several languages, especially in a footnotes, we really ought to get this bit of code right.

To get around these problems, Wayne suggested emendations to the *TeXbook* versions of these macros which are broadly the same as those described by Michael: the central idea (also suggested by Donald Knuth in a letter to Michael) is to avoid collecting the text in an `\hbox` in the first place, but instead to collect it in a `\vbox` whose width is (virtually) infinite. The text is therefore typeset in unrestricted horizontal mode, as a paragraph consisting of a single long line. Later, there is an extra level of unboxing to be done: we have to unpack the `\vbox`, as well as the hboxes inside it, but that's not too hard. For details, we refer you to Michael's article, where the issues are clearly explained.²⁵ Michael's unboxing macro is called `\unvxh`: `unvbox`, extract the last line, and `unhbox` it.

²³Michael Downes, 'Line Breaking in `\unhboxed` Text', *TUGboat* 11 (1990), pp. 605–612.

²⁴See *The TeXbook*, p. 455 (editions after January 1990).

²⁵Wayne supplied his own macros to do this, but since they were almost identical to Michael's, we have used the latter's `\unvxh` macro since it is publicly documented.

Doing things this way has an important consequence: as Michael pointed out, you really can't put an explicit line-break into a note built in a `\vbox` the way we are doing.²⁶ In other words, be very careful not to say `\break`, or `\penalty-10000`, or any equivalent inside your para-footnote. If you do, most of the note will probably disappear. You *are* allowed to make strong suggestions; in fact `\penalty-9999` will be quite okay. Just don't make the break mandatory. We haven't applied any of Michael's solutions here, since we feel that the problem is exiguous, and `eledmac` is quite baroque enough already. If you think you are having this problem, look up Michael's solutions.

One more thing; we set `\leftskip` and `\rightskip` to zero. This has the effect of neutralizing any such skips which may apply to the main text (cf. p. 106 above). We need to do this, since `footfudgefactor` is calculated on the assumption that the notes are `\hsize` wide.

So, finally, here is the modified foot-paragraph code, which sets the footnote in vertical mode so that language and discretionary nodes are included.

```

1705 \newcommand*{\para@vfootnote}[2]{%
1706   \insert\csname #1footins\endcsname
1707   \bgroup
1708     \csuse{bhookXnote@#1}
1709     \csuse{Xnotefontsize@#1}
1710     \footsplitskips
1711     \setbox0=\vbox{\hsize=\maxdimen
1712       \noindent\csname #1footfmt\endcsname#2[#1]}%
1713     \setbox0=\hbox{\unvvh0[#1]}%
1714     \dp0=0pt
1715     \ht0=\csname #1footfudgefactor\endcsname\wd0

```

Here we produce the contents of the footnote from box 0, and add a penalty of 0 between boxes in this insert.

```

1716   \if@RTL\noindent \leavevmode\fi\box0%
1717   \penalty0
1718   \egroup}
1719

```

The final penalty of 0 was added here at Wayne's suggestion to avoid a weird page-breaking problem, which occurs on those occasions when `TeX` attempts to split foot paragraphs. After trying out such a split (see *The TeXbook*, p. 124), `TeX` inserts a penalty of `-10000` here, which nearly always forces the break at the end of the whole footnote paragraph (since individual notes can't be split) even when this leads to an overfull vbox. The change above results in a penalty of 0 instead which allows, but doesn't force, such breaks. This penalty of 0 is later removed, after page breaks have been decided, by the `\unpenalty` macro in `\makehboxofhboxes`. So it does not affect how the footnote paragraphs are typeset (the notes still have a penalty of `-10` between them, which is added by `\parafootfmt`).

²⁶'Line Breaking', p. 610.

`\mppara@vfootnote` This version is for minipages.

```

1720 \newcommand*{\mppara@vfootnote}[2]{%
1721   \global\setbox\@nameuse{mp#1footins}\vbox{%
1722     \unvbox\@nameuse{mp#1footins}%
1723     \csuse{bhookXnote@#1}
1724     \csuse{Xnotefontsize@#1}
1725     \footsplitskips
1726     \setbox0=\vbox{\hsize=\maxdimen
1727       \noindent\color@begingroup\csname #1footfmt\endcsname #2[#1]\color@endgroup}%
1728     \setbox0=\hbox{\unvxh0[#1]}%
1729     \dp0=\z@
1730     \ht0=\csname #1footfudgefactor\endcsname\wd0
1731     \box0
1732     \penalty0
1733   }}
1734
```

`\unvxh` Here is (modified) Michael's definition of `\unvxh`, used above. Michael's macro also takes care to remove some unwanted penalties and glue that T_EX automatically attaches to the end of paragraphs. When T_EX finishes a paragraph, it throws away any remaining glue, and then tacks on the following items: a `\penalty` of 10000, a `\parfillskip` and a `\rightskip` (*The TeXbook*, pp.99–100). `\unvxh` cancels these unwanted paragraph-final items using `\unskip` and `\unpenalty`.

```

1735 \newcommand*{\unvxh}[2][2=Z]{% 2th is optional for retro-compatibility
1736   \setbox0=\vbox{\unvbox#1%
1737     \global\setbox1=\lastbox}%
1738   \unhbox1
1739   \unskip           % remove \rightskip,
1740   \unskip           % remove \parfillskip,
1741   \unpenalty        % remove \penalty of 10000,
1742   \hskip\csuse{afternote@#2}} % but add the glue to go between the notes
1743
```

`\parafootfmt` `\parafootfmt` is `\normalfootfmt` adapted to do the special stuff needed for paragraphed notes—leaving out the `\endgraf` at the end, sticking in special penalties and kern, and leaving out the `\footstrut`. The first argument is the line and page number information, the second is the lemma, the third is the text of the footnote, and the fourth is the series (optional, for backward compatibility).

```

1744 \newcommand*{\parafootfmt}[4][4=Z]{%
1745   \insertparafootsep{#4}%
1746   \ledsetnormalparstuff%
1747   \printlinefootnote{#1}{#4}%
1748   {\nottoggle{Xlemmadisablefontselection@#4}{\select@lemmafnt#1|#2}{#2}}%
1749   \iftoggle{nosep@}{\hskip\csuse{inplaceoflemmaseparator@#4}}{\ifcempty{lemmaseparator@#4}%
1750     {\hskip\csuse{inplaceoflemmaseparator@#4}}%
1751     {\nobreak\hskip\csuse{beforelemmaseparator@#4}\csuse{lemmaseparator@#4}\hskip\csuse{afterlemmasep
1752   }}%
1753   #3\penalty-10 }
```

Note that in the above definition, the penalty of -10 encourages a line break between notes, so that notes have a slight tendency to begin on new lines. The `\insertparafootsep` command is used to insert the `\parafootsep@series` between each note in the *same* page.

`\para@footgroup` This `footgroup` code is modelled on the macros in *The TeXbook*, p. 399. The only difference is the `\unpenalty` in `\makehboxofhboxes`, which is there to remove the penalty of 0 which was added to the end of each footnote by `\para@vfootnote`.

The call to `\notefontsetup` is to ensure that the correct `\baselineskip` for the footnotes is used. The argument is the note series letter.

```

1754 \newcommand*{\para@footgroup}[1]{%
1755   \unvbox\csname #1footins\endcsname
1756   \ifcsstring{Xragged@#1}{L}{\RaggedLeft}{}%
1757   \ifcsstring{Xragged@#1}{R}{\RaggedRight}{}%
1758   \makehboxofhboxes
1759   \setbox0=\hbox{{\csuse{Xnotefontsize@#1}\csuse{txtbeforeXnotes@#1}}\unhbox0 \removebox0
1760   \csuse{Xnotefontsize@#1}
1761   \noindent\unhbox0\par%
1762   \global\hsize=\old@hsize%
1763   }%
1764
```

`\mppara@footgroup` The minipage version.

```

1765 \newcommand*{\mppara@footgroup}[1]{%
1766   \setXnoteswidthliketwocolumns@{#1}%
1767   \vskip\skip\@nameuse{mp#1footins}
1768   \ifl@dpairing\ifparledgroup%
1769     \leavevmode\marks\parledgroup@{begin}%
1770     \marks\parledgroup@series{#1}%
1771     \marks\parledgroup@type{Xfootnote}%
1772   \fi\fi\normalcolor
1773   \ifparledgroup%
1774     \ifl@dpairing%
1775     \else%
1776       \setXnoteswidthliketwocolumns@{#1}%
1777       \setXnotespositionliketwocolumns@{#1}%
1778       \print@Xfootnoterule{#1}%
1779       \vskip\csuse{afterXrule@#1}%
1780     \fi%
1781   \else%
1782     \setXnoteswidthliketwocolumns@{#1}%
1783     \setXnotespositionliketwocolumns@{#1}%
1784     \print@Xfootnoterule{#1}%
1785     \vskip\csuse{afterXrule@#1}%
1786   \fi%
1787   \unvbox\csname mp#1footins\endcsname
1788   \ifcsstring{Xragged@#1}{L}{\RaggedLeft}{}%
1789   \ifcsstring{Xragged@#1}{R}{\RaggedRight}{}%
1790   \makehboxofhboxes

```

```

1791 \setbox0=\hbox{{\csuse{Xnotefontsize@#1}\csuse{txtbeforeXnotes@#1}}\unhbox0 \removehboxes}%
1792 \csuse{Xnotefontsize@#1}
1793 \noindent\unhbox0\par}}
1794

```

`\makehboxofhboxes`

```

\removehboxes 1795 \newcommand*\makehboxofhboxes{\setbox0=\hbox{}%
1796 \loop
1797 \unpenalty
1798 \setbox2=\lastbox
1799 \ifhbox2
1800 \setbox0=\hbox{\box2\unhbox0}%
1801 \repeat}
1802
1803 \newcommand*\removehboxes{\setbox0=\lastbox
1804 \ifhbox0{\removehboxes}\unhbox0 \fi}
1805

```

24.6 Insertion of the footnotes separator

The command `\insertparafootsep{<series>}` must be called at the beginning of `\parafootftm` (and like commands).

```

\prevpage@num
\insertparafootsep 1806 \newcommand{\insertparafootsep}[1]{%
1807 \ifnumequal{\csuse{prevpage#1@num}}{\page@num}%
1808 {\ifcsdef{prevline#1}% Be sur \prevline#1 exists.
1809 {\ifnumequal{\csuse{prevline#1}}{\line@num}%
1810 {\ifcsemt{symp\line@num}}{\csuse{parafootsep@#1}}{}}}%
1811 {\csuse{parafootsep@#1}}}%
1812 }%
1813 {\csuse{parafootsep@#1}}}%
1814 }%
1815 {}%
1816 \global\csname prevpage#1@num\endcsname=\page@num%
1817 }

```

24.7 Columnar footnotes

`\rigidbalance` We will now define macros for three-column notes and two-column notes. Both sets of macros will use `\rigidbalance`, which splits a box (#1) into into a number (#2) of columns, each with a space (#3) between the top baseline and the top of the `\vbox`. The `\rigidbalance` macro is taken from *The TeXbook*, p.397, with a slight change to the syntax of the arguments so that they don't depend on white space. Note also the extra unboxing in `\splitoff`, which allows the new `\vbox` to have its natural height as it goes into the alignment.

The L^AT_EX `\line` macro has no relationship to the TeX `\line`. The L^AT_EX equivalent is `\@@line`.

```

1818 \newcount\@k \newdimen\@h
1819 \newcommand*\rigidbalance}[3]{\setbox0=\box#1 \@k=#2 \@h=#3
1820 \@@line{\splittopskip=\@h \vbadness=\@M \hfilneg
1821 \valign{##\vfil\cr\dosplits}}}}
1822
1823 \newcommand*\dosplits{\ifnum\@k>0 \noalign{\hfil}\splitoff
1824 \global\advance\@k-1\cr\dosplits\fi}
1825
1826 \newcommand*\splitoff{\dimen0=\ht0
1827 \divide\dimen0 by\@k \advance\dimen0 by\@h
1828 \setbox2 \vsplit0 to \dimen0
1829 \unvbox2 }
1830

```

Three columns

`\footthreecol` You say `\footthreecol{A}` to have the A series of the footnotes typeset in three columns. It is important to call this only after `\hsize` has been set for the document.

```

1831 \newcommand*\footthreecol}[1]{%
1832 \csgdef{series@display#1}{threecol}
1833 \expandafter\let\csname v#1footnote\endcsname=\threecolvfootnote
1834 \expandafter\let\csname #1footfmt\endcsname=\threecolfootfmt
1835 \expandafter\let\csname #1footgroup\endcsname=\threecolfootgroup
1836 \threecolfootsetup{#1}

```

The additional setup for minipages.

```

1837 \expandafter\let\csname mpv#1footnote\endcsname=\mpnormalvfootnote
1838 \expandafter\let\csname mp#1footgroup\endcsname=\mpthreecolfootgroup
1839 \mpthreecolfootsetup{#1}
1840 }
1841

```

The `\footstart` and `\footnoterule` macros for these notes assume the normal values (p. 106 above).

`\threecolfootsetup` The `\threecolfootsetup` macro calculates and sets some numbers for three-column footnotes.

We set the `\count` of the foot insert to 333. Each footnote can be thought of as contributing only one third of its height to the page, since the footnote insertion has been made as a long narrow column, which then gets trisected by the `\rigidbalance` routine (inside `\threecolfootgroup`). These new, shorter columns are saved in a box, and then that box is *put back* into the footnote insert, replacing the original collection of the footnotes. This new box is, therefore, only about a third of the height of the original one.

The `\dimen` value for this note series has to change in the inverse way: it needs to be three times the actual limit on the amount of space these notes are allowed to fill on the page, because when `TEX` is accumulating material for the page and checking that limit, it doesn't apply the `\count` scaling.

```

1842 \newcommand*{\threecolfootsetup}[1]{%
1843   \count\csname #1footins\endcsname 333
1844   \multiply\dimen\csname #1footins\endcsname \thr@@}

```

`\mpthreecolfootsetup` The setup for minipages.

```

1845 \newcommand*{\mpthreecolfootsetup}[1]{%
1846   \count\csname mp#1footins\endcsname 333
1847   \multiply\dimen\csname mp#1footins\endcsname \thr@@}
1848

```

`\threecolvfootnote` `\threecolvfootnote` is the `\vfootnote` command for three-column notes. The call to `\notefontsetup` ensures that the `\splittopskip` and `\splitmaxdepth` take their values from the right `\strutbox`: the one used in a footnotes. Note especially the importance of temporarily reducing the `\hsize` to 0.3 of its normal value. This determines the widths of the individual columns. So if the normal `\hsize` is, say, 10 cm, then each column will be $0.3 \times 10 = 3$ cm wide, leaving a gap of 1 cm spread equally between columns (i.e., .5 cm between each).

The arguments are 1) the note series letter and 2) the full text of the note (including numbers, lemma and text).

```

1849 \notbool{parapparatus@}{\newcommand*}{\newcommand}{\threecolvfootnote}[2]{%
1850   \insert\csname #1footins\endcsname\bgroup
1851   \csuse{Xnotefontsize@#1}
1852   \footsplitskips
1853   \csname #1footfmt\endcsname #2[#1]\egroup}

```

`\threecolfootfmt` `\threecolfootfmt` is the command that formats one note. It uses `\raggedright`, which will usually be preferable with such short lines. Setting the `\parindent` to zero means that, within each individual note, the lines begin flush left.

The arguments are 1) the line numbers, 2) the lemma and 3) the text of the `-footnote` command 4) optional (for backward compatibility): the series.

```

1854 \notbool{parapparatus@}{\newcommand*}{\newcommand}{\threecolfootfmt}[4][4=Z]{%
1855   \normal@pars
1856   \hsize \csuse{hsizethreecol@#4}
1857   \parindent=0pt
1858   \tolerance=5000
1859   \raggedright
1860   \hangindent=\csuse{Xhangindent@#4}
1861   \leavevmode
1862   \strut{\printlinefootnote{#1}{#4}}%
1863   {\nottoggle{Xlemmadisablefontselection@#4}}{\select@lemfont#1|#2}{#2}}%
1864   \iftoggle{nosep@}{\hskip\csuse{inplaceoflemmaseparator@#4}}{\ifcempty{lemmaseparator@#4}%
1865     {\hskip\csuse{inplaceoflemmaseparator@#4}}%
1866     {\nobreak\hskip\csuse{beforelemmaseparator@#4}\csuse{lemmaseparator@#4}\hskip\csuse{afterlemmasep
1867     }}}%
1868   #3\strut\par\allowbreak}

```

`\threecolfootgroup` And here is the `footgroup` macro that's called within the output routine to re-group the notes into three columns. Once again, the call to `\notefontsetup` is

there to ensure that it is the right `\splittopskip`—the one used in footnotes—which is used to provide the third argument for `\rigidbalance`. This third argument (`\@h`) is the `topskip` for the box containing the text of the footnotes, and does the job of making sure the top lines of the columns line up horizontally. In *The TeXbook*, p. 398, Donald Knuth suggests retrieving the output of `\rigidbalance`, putting it back into the insertion box, and then printing the box. Here, we just print the `\line` which comes out of `\rigidbalance` directly, without any re-boxing.

```
1869 \newcommand*{\threecolfootgroup}[1]{\notefontsetup
1870   {\csuse{Xnotefontsize@#1}\noindent\csuse{txtbeforeXnotes@#1}}\par
1871   \splittopskip=\ht\strutbox
1872   \expandafter
1873   \rigidbalance\csname #1footins\endcsname \thr@@ \splittopskip}}
```

`\mpthreecolfootgroup` The setup for minipages.

```
1874 \newcommand*{\mpthreecolfootgroup}[1]{%
1875   \vskip\skip\@nameuse{mp#1footins}
1876   \ifl@dpairing\ifparledgroup%
1877     \leavevmode\marks\parledgroup@{begin}%
1878     \marks\parledgroup@series{#1}%
1879     \marks\parledgroup@type{Xfootnote}%
1880   \fi\fi\normalcolor
1881   \ifparledgroup%
1882     \ifl@dpairing%
1883     \else%
1884       \setXnoteswidthliketwocolumns@{#1}%
1885       \setXnotespositionliketwocolumns@{#1}%
1886       \print@Xfootnoterule{#1}%%
1887       \vskip\csuse{afterXrule@#1}%
1888     \fi%
1889   \else%
1890     \setXnoteswidthliketwocolumns@{#1}%
1891     \setXnotespositionliketwocolumns@{#1}%
1892     \print@Xfootnoterule{#1}%%
1893     \vskip\csuse{afterXrule@#1}%
1894   \fi%
1895   {\csuse{Xnotefontsize@#1}\noindent\csuse{txtbeforeXnotes@#1}}\par
1896   \splittopskip=\ht\strutbox
1897   \expandafter
1898   \rigidbalance\csname mp#1footins\endcsname \thr@@ \splittopskip}}
1899
```

Two columns

`\foottwocol` You say `\foottwocol{A}` to have the A series of the footnotes typeset in two columns. It is important to call this only after `\hsize` has been set for the document.

```
1900 \newcommand*{\foottwocol}[1]{%
```

```

1901 \csgdef{series@display#1}{twocol}
1902 \expandafter\let\csname v#1footnote\endcsname=\twocolvfootnote
1903 \expandafter\let\csname #1footfmt\endcsname=\twocolfootfmt
1904 \expandafter\let\csname #1footgroup\endcsname=\twocolfootgroup
1905 \twocolfootsetup{#1}

```

The additional setup for minipages.

```

1906 \expandafter\let\csname mpv#1footnote\endcsname=\mpnormalvfootnote
1907 \expandafter\let\csname mp#1footgroup\endcsname=\mptwocolfootgroup
1908 \mptwocolfootsetup{#1}
1909 }
1910

```

`\twocolfootsetup` Here is a series of macros which are very similar to their three-column counterparts.

`\twocolvfootnote` In this case, each note is assumed to contribute only a half a line of text. And the

`\twocolfootfmt` notes are set in columns giving a gap between them of one tenth of the `\hsize`.

```

\twocolfootgroup 1911 \newcommand*{\twocolfootsetup}[1]{%
1912 \count\csname #1footins\endcsname 500
1913 \multiply\dimen\csname #1footins\endcsname \tw@}

1914 \notbool{parapparatus@}{\newcommand*{\newcommand}{\twocolvfootnote}[2]{\insert\csname #1footins\endcsname
1915 \csuse{Xnotefontsize@#1}
1916 \footssplitsskips
1917 \csname #1footfmt\endcsname #2[#1]\egroup}

1918 \notbool{parapparatus@}{\newcommand*{\newcommandx}{\twocolfootfmt}[4][4=Z]{% 4th arg is optional, f
1919 \normal@pars
1920 \hsize \csuse{hsize\twocol@#4}
1921 \parindent=0pt
1922 \tolerance=5000
1923 \raggedright
1924 \hangindent=\csuse{Xhangindent@#4}
1925 \leavevmode
1926 \strut{\printlinefootnote{#1}{#4}}}%
1927 {\nottoggle{Xlemmadisablefontselection@#4}{\select@lemmafnt#1|#2}{#2}}}%
1928 \iftoggle{nosep@}{\hskip\csuse{inplaceoflemmaseparator@#4}}{\ifcsemt{lemmaseparator@#4}}%
1929 {\hskip\csuse{inplaceoflemmaseparator@#4}}%
1930 {\nobreak\hskip\csuse{beforelemmaseparator@#4}\csuse{lemmaseparator@#4}\hskip\csuse{afterlemmasep
1931 }}%
1932 #3\strut\par\allowbreak}

1933 \newcommand*{\twocolfootgroup}[1]{\csuse{Xnotefontsize@#1}
1934 {\csuse{Xnotefontsize@#1}\noindent\csuse{txtbeforeXnotes@#1}}\par
1935 \splittopskip=\ht\strutbox
1936 \expandafter
1937 \rigidbalance\csname #1footins\endcsname \tw@ \splittopskip}}
1938

```

`\mptwocolfootsetup` The versions for minipages.

```

\mptwocolfootgroup 1939 \newcommand*{\mptwocolfootsetup}[1]{%
1940 \count\csname mp#1footins\endcsname 500
1941 \multiply\dimen\csname mp#1footins\endcsname \tw@}

```

```

1942 \newcommand*{\mptwocolfootgroup}[1]{%
1943   \vskip\skip\@nameuse{mp#1footins}
1944   \ifl@dpairing\ifparledgroup%
1945     \leavevmode\marks\parledgroup@{begin}%
1946     \marks\parledgroup@series{#1}%
1947     \marks\parledgroup@type{Xfootnote}%
1948   \fi\fi\normalcolor
1949   \ifparledgroup%
1950     \ifl@dpairing%
1951     \else%
1952       \setXnoteswidthliketwocolumns@{#1}%
1953       \setXnotespositionliketwocolumns@{#1}%
1954       \print@Xfootnoterule{#1}%%
1955       \vskip\csuse{afterXrule@#1}%
1956     \fi%
1957   \else%
1958     \setXnoteswidthliketwocolumns@{#1}%
1959     \setXnotespositionliketwocolumns@{#1}%
1960     \print@Xfootnoterule{#1}%%
1961     \vskip\csuse{afterXrule@#1}%
1962   \fi%
1963   {\csuse{Xnotefontsize@#1}\noindent\csuse{txtbeforeXnotes@#1}}\par
1964   \splittopskip=\ht\strutbox
1965   \expandafter
1966   \rigidbalance\csname mp#1footins\endcsname \tw@ \splittopskip}}
1967

```

25 Familiar footnotes

25.1 Generality

The original EDMAC provided users with five series of critical footnotes (`\Afootnote`, `\Bfootnote`, `\Cfootnote`, `\Dfootnote`, `\Efootnote`), and L^AT_EX provides a single numbered footnote. The `eledmac` package uses the EDMAC mechanism to provide five series of numbered footnotes.

First, though, the `footmisc` package has an option whereby two or more consecutive `\footnotes` have their marks separated by commas. This seems such a useful ability that it is provided automatically by `eledmac`.

`\multiplefootnotemarker` These macros may have been defined by the `memoir` class, are provided by the `footmisc` package and perhaps by other footnote packages.

```

1968 \providecommand*{\multiplefootnotemarker}{3sp}
1969 \providecommand*{\multfootsep}{\textsuperscript{\normalfont,}}
1970

```

`\m@mmf@prepare` A pair of self-cancelling kerns. This may have been defined in the `memoir` class.

```

1971 \providecommand*{\m@mmf@prepare}{%
1972   \kern-\multiplefootnotemarker

```



```
1973 \kern\multiplefootnotemarker\relax}
```

`\m@mmf@check` This may have been defined in the memoir class. If it recognises the last kern as `\multiplefootnotemarker` it typesets `\multfootsep`.

```
1974 \providecommand*\m@mmf@check}{%
1975   \ifdim\lastkern=\multiplefootnotemarker\relax
1976     \edef\x@sf{\the\spacefactor}%
1977     \unkern
1978     \multfootsep
1979     \spacefactor\x@sf\relax
1980   \fi}
1981
```

We have to modify `\@footnotetext` and `\@footnotemark`. However, if memoir is used the modifications have already been made.

```
1982 \ifclassloaded{memoir}{}%
```

`\@footnotetext` Add `\m@mmf@prepare` at the end of `\@footnotetext`.

```
1983 \let\l@dold@footnotetext\@footnotetext
1984 \renewcommand{\@footnotetext}[1]{%
1985   \l@dold@footnotetext{#1}%
1986   \m@mmf@prepare}
```

`\@footnotemark` Modify `\@footnotemark` to cater for adjacent `\footnotes`.

```
1987 \renewcommand*\@footnotemark}{%
1988   \leavevmode
1989   \ifhmode
1990     \edef\x@sf{\the\spacefactor}%
1991     \m@mmf@check
1992     \nobreak
1993   \fi
1994   \@makefnmark
1995   \m@mmf@prepare
1996   \ifhmode\spacefactor\x@sf\fi
1997   \relax}
```

Finished the modifications for the non-memoir case.

```
1998 }
1999
```

`\l@doldold@footnotetext` In order to enable the regular `\footnotes` in numbered text we have to play around with its `\@footnotetext`, using different forms for when in numbered or regular text.

```
2000 \let\l@doldold@footnotetext\@footnotetext
2001 \renewcommand{\@footnotetext}[1]{%
2002   \ifnumberedpar@
2003     \edtext{\l@dbfnote{#1}}%
2004   \else
2005     \l@doldold@footnotetext{#1}%
2006   \fi}
```

`\l@dbfnote` `\l@dbfnote` adds the footnote to the insert list, and `\vl@dbfnote` calls the original `\vl@dbfnote` `\@footnotetext`.

```

2007 \newcommand{\l@dbfnote}[1]{%
2008   \ifnumberedpar@
2009   \gdef\@tag{#1}%
2010   \xright@appenditem{\noexpand\vl@dbfnote{\csexpandonce{\@tag}}{\@thefnmark}}{%
2011     \to\inserts@list
2012     \global\advance\insert@count \@ne
2013   \fi\ignorespaces}
2014 \newcommand{\vl@dbfnote}[2]{%
2015   \def\@thefnmark{#2}%
2016   \l@doldold@footnotetext{#1}}

```

25.2 Footnote formats

Some of the code for the various formats is remarkably similar to that in section 24.3.

The following macros generally set things up for the ‘standard’ footnote format.

`\prebodyfootmark` Two convenience macros for use by `\...@footnotemark...` macros.

`\postbodyfootmark`

```

2017 \newcommand*{\prebodyfootmark}{%
2018   \leavevmode
2019   \ifhmode
2020     \edef\x@sf{\the\spacefactor}%
2021     \m@mmf@check
2022     \nobreak
2023   \fi}
2024 \newcommand{\postbodyfootmark}{%
2025   \m@mmf@prepare
2026   \ifhmode\spacefactor\x@sf\fi\relax}
2027

```

`\normal@footnotemarkX` `\normal@footnotemarkX{<series>}` sets up the typesetting of the marker at the point where the footnote is called for.

```

2028 \newcommand*{\normal@footnotemarkX}[1]{%
2029   \prebodyfootmark
2030   \@nameuse{bodyfootmark#1}%
2031   \postbodyfootmark}
2032

```

`\normalbodyfootmarkX` The `\normalbodyfootmarkX{<series>}` *really* typesets the in-text marker. The style is the normal superscript.

```

2033 \newcommand*{\normalbodyfootmarkX}[1]{%
2034   \hbox{\textsuperscript{\normalfont\@nameuse{@thefnmark#1}}}}

```

`\normalvfootnoteX` `\normalvfootnoteX{<series>}{<text>}` does the `\insert` for the `<series>` and calls the series’ `\footfmt...` to format the `<text>`.

```

2035 \newcommand*{\normalvfootnoteX}[2]{%

```

```

2036 \insert\@nameuse{footins#1}\bgroup
2037 \csuse{bhooknoteX@#1}
2038 \csuse{notefontsizeX@#1}
2039 \footsplitskips
2040 \ifl@dpairing\ifl@dpaging\else%
2041 \setnotesXwidthliketwocolumns@{#1}%
2042 \fi\fi%
2043 \setnotesXpositionliketwocolumns@{#1}%
2044 \spaceskip=\z@skip \xspaceskip=\z@skip
2045 \csuse{\csuse{footnote@dir}}\if@RTL\else\noindent\leavevmode\fi\@nameuse{footfmt#1}-{#1}-{#2}\egroup
2046

```

`\mpnormalvfootnoteX` The minipage version.

```

2047 \newcommand*{\mpnormalvfootnoteX}[2]{%
2048 \global\setbox\@nameuse{mpfootins#1}\vbox{%
2049 \unvbox\@nameuse{mpfootins#1}
2050 \csuse{bhooknoteX@#1}
2051 \csuse{notefontsizeX@#1}
2052 \hsize\columnwidth
2053 \@parboxrestore
2054 \color@begingroup
2055 \@nameuse{footfmt#1}-{#1}-{#2}\color@endgroup}}
2056

```

`\normalfootfmtX` `\normalfootfmtX{<series>}{<text>}` typesets the footnote text, prepended by the marker.

```

2057 \newcommand*{\normalfootfmtX}[2]{%
2058 \protected@edef\@currentlabel{%
2059 \@nameuse{@thefnmark#1}%
2060 }%
2061 \ledsetnormalparstuff
2062 \hangindent=\csuse{hangindentX@#1}%
2063 {{\csuse{notenumberfontX@#1}\@nameuse{footfootmark#1}}\strut%\enspace
2064 #2\strut\par}}
2065

```

`\normalfootfootmarkX` `\normalfootfootmarkX{<series>}` is called by `\normalfootfmtX` to typeset the footnote marker in the footer before the footnote text.

```

2066 \newcommand*{\normalfootfootmarkX}[1]{%
2067 \textsuperscript{\@nameuse{@thefnmark#1}}}
2068

```

`\normalfootstartX` `\normalfootstartX{<series>}` is the `<series>` footnote starting macro used in the output routine.

```

2069 \newcommand*{\normalfootstartX}[1]{%
2070 \ifdimequal{0pt}{\prenotesX@}{}%
2071 {%
2072 \iftoggle{prenotesX@}{%
2073 \togglefalse{prenotesX@} \skip\cname footins#1\endcname=\csuse{prenotesX@}}%

```

```

2074      {}%
2075      }%
2076      \vskip\skip\csname footins#1\endcsname%
2077      \leftskip=\z@
2078      \rightskip=\z@
2079      \ifl@dpairing\else%
2080      \hspace=\old@hspace%
2081      \fi%
2082      \setnotesXwidthliketwocolumns@{#1}%
2083      \setnotesXpositionliketwocolumns@{#1}%
2084      \print@footnoterule{#1}%
2085      \vskip\csuse{afterruleX@#1}}
2086

```

`\normalfootnoteruleX` The rule drawn before the footnote series group.

```

2087 \let\normalfootnoteruleX=\footnoterule
2088

```

`\normalfootgroupX` `\normalfootgroupX{<series>}` sends the contents of the `<series>` insert box to the output page without alteration.

```

2089 \newcommand*{\normalfootgroupX}[1]{%
2090   \unvbox\@nameuse{footins#1}%
2091   \hspace=\old@hspace%
2092   }%
2093

```

`\mpnormalfootgroupX` The minipage version.

```

2094 \newcommand*{\mpnormalfootgroupX}[1]{%
2095   \vskip\skip\@nameuse{mpfootins#1}
2096   \ifl@dpairing\ifparledgroup%
2097     \leavevmode\marks\parledgroup@{begin}%
2098     \marks\parledgroup@series{#1}%
2099     \marks\parledgroup@type{footnoteX}%
2100   \fi\fi\normalcolor
2101   \ifparledgroup%
2102     \ifl@dpairing%
2103     \else%
2104       \setnotesXwidthliketwocolumns@{#1}%
2105       \setnotesXpositionliketwocolumns@{#1}%
2106       \print@footnoterule{#1}%
2107       \vskip\csuse{afterruleX@#1}%
2108     \fi%
2109   \else%
2110     \setnotesXwidthliketwocolumns@{#1}%
2111     \setnotesXpositionliketwocolumns@{#1}%
2112     \print@footnoterule{#1}%
2113     \vskip\csuse{afterruleX@#1}%
2114   \fi%
2115   \unvbox\@nameuse{mpfootins#1}}
2116

```

\normalbfnoteX

```

2117 \newcommand{\normalbfnoteX}[2]{%
2118   \ifnumberedpar@
2119     \protected@csxdef{thisfootnote}{\csuse{thefootnote#1}}%
2120     \xright@appenditem{\noexpand\vbfnoteX{#1}{#2}}{\csexpandonce{thisfootnote}}}%
2121     \to\inserts@list
2122   \global\advance\insert@count \@ne
2123 \fi\ignorespaces}
2124

```

\vbfnoteX

```

2125 \newcommand{\vbfnoteX}[3]{%
2126   \@namedef{@thefnmark#1}{#3}%
2127   \@nameuse{regvfootnote#1}{#1}{#2}}
2128

```

\vnumfootnoteX

```

2129 \newcommand{\vnumfootnoteX}[2]{%
2130   \ifnumberedpar@
2131     \edtext{}{\normalbfnoteX{#1}{#2}}%
2132   \else
2133     \@nameuse{regvfootnote#1}{#1}{#2}%
2134   \fi}
2135

```

\footnormalX **\footnormalX{<series>}** initialises the settings for the <series> footnotes. This should always be called for each series.

```

2136 \newcommand*{\footnormalX}[1]{%
2137   \csgdef{series@displayX#1}{normalX}
2138   \expandafter\let\csname footstart#1\endcsname=\normalfootstartX
2139   \@namedef{@footnotemark#1}{\normal@footnotemarkX{#1}}
2140   \@namedef{bodyfootmark#1}{\normalbodyfootmarkX{#1}}
2141   \expandafter\let\csname regvfootnote#1\endcsname=\normalvfootnoteX
2142   \expandafter\let\csname vfootnote#1\endcsname=\vnumfootnoteX
2143   \expandafter\let\csname footfmt#1\endcsname=\normalfootfmtX
2144   \@namedef{footfootmark#1}{\normalfootfootmarkX{#1}}
2145   \expandafter\let\csname footgroup#1\endcsname=\normalfootgroupX
2146   \expandafter\let\csname footnoterule#1\endcsname=\normalfootnoteruleX
2147   \count\csname footins#1\endcsname=1000
2148   \dimen\csname footins#1\endcsname=\csuse{maxhnotesX@#1}
2149   \skip\csname footins#1\endcsname=\csuse{beforenotesX@#1}

```

Aditions for minipages.

```

2150   \expandafter\let\csname mpvfootnote#1\endcsname=\mpnormalvfootnoteX
2151   \expandafter\let\csname mpfootgroup#1\endcsname=\mpnormalfootgroupX
2152   \count\csname mpfootins#1\endcsname=1000
2153   \dimen\csname mpfootins#1\endcsname=\csuse{maxhnotesX@#1}
2154   \skip\csname mpfootins#1\endcsname=\csuse{beforenotesX@#1}
2155 }
2156

```

25.3 Two columns footnotes

The following macros set footnotes in two columns. It is assumed that the length of each footnote is less than the column width.

```

\foottwocolX \foottwocolX{<series>}
2157 \newcommand*{\foottwocolX}[1]{%
2158   \csgdef{series@displayX#1}{twocol}
2159   \expandafter\let\csname regvfootnote#1\endcsname=\twocolvfootnoteX
2160   \expandafter\let\csname footfmt#1\endcsname=\twocolfootfmtX
2161   \expandafter\let\csname footgroup#1\endcsname=\twocolfootgroupX
2162   \twocolfootsetupX{#1}
2163   \expandafter\let\csname mpvfootnote#1\endcsname=\mpnormalvfootnoteX
2164   \expandafter\let\csname mpfootgroup#1\endcsname=\mptwocolfootgroupX
2165   \mptwocolfootsetupX{#1}}
2166

\twocolfootsetupX \twocolfootsetupX{<series>}
\mptwocolfootsetupX 2167 \newcommand*{\twocolfootsetupX}[1]{%
2168   \count\csname footins#1\endcsname 500
2169   \multiply\dimen\csname footins#1\endcsname by \tw@}
2170 \newcommand*{\mptwocolfootsetupX}[1]{%
2171   \count\csname mpfootins#1\endcsname 500
2172   \multiply\dimen\csname mpfootins#1\endcsname by \tw@}
2173

\twocolvfootnoteX \twocolvfootnoteX{<series>}
2174 \newcommand*{\twocolvfootnoteX}[2]{%
2175   \insert\csname footins#1\endcsname\bgroup
2176   \csuse{notefontsizeX@#1}
2177   \footsplitskips
2178   \spaceskip=\z@skip \xspaceskip=\z@skip
2179   \@nameuse{footfmt#1}{#1}{#2}\egroup}
2180

\twocolfootfmtX \twocolfootfmtX{<series>}
2181 \newcommand*{\twocolfootfmtX}[2]{%
2182   \protected@edef\@currentlabel{%
2183     \@nameuse{thefnmark#1}%
2184   }%
2185   \normal@pars
2186   \hangindent=\csuse{hangindentX@#1}%
2187   \hsize \csuse{hsizetwocolX@#1}
2188   \parindent=\z@
2189   %%% \parfillskip=0pt \@plus 1fil
2190   \tolerance=5000\relax
2191   \raggedright
2192   \leavevmode
2193   {\csuse{notenunfontX@#1}\@nameuse{footfootmark#1}\strut%\enspace

```

```

2194      #2\strut\par}\allowbreak}
2195
\twocolfootgroupX \twocolfootgroupX{\series}
\mptwocolfootgroupX 2196 \newcommand*\twocolfootgroupX[1]{\csuse{notefontsizeX@#1}
2197 \splittopskip=\ht\strutbox
2198 \expandafter
2199 \rigidbalance\csname footins#1\endcsname \tw@ \splittopskip}}
2200 \newcommand*\mptwocolfootgroupX[1]{\%
2201 \vskip\skip\@nameuse{mpfootins#1}
2202 \ifl@dpairing\ifparledgroup%
2203 \leavevmode\marks\parledgroup@{begin}%
2204 \marks\parledgroup@series{#1}%
2205 \marks\parledgroup@type{footnoteX}%
2206 \fi\fi\normalcolor
2207 \ifparledgroup%
2208 \ifl@dpairing%
2209 \else%
2210 \setnotesXwidthliketwocolumns@{#1}%
2211 \setnotesXpositionliketwocolumns@{#1}%
2212 \print@footnoteXrule{#1}%
2213 \vskip\csuse{afterruleX@#1}%
2214 \fi%
2215 \else%
2216 \setnotesXwidthliketwocolumns@{#1}%
2217 \setnotesXpositionliketwocolumns@{#1}%
2218 \print@footnoteXrule{#1}%
2219 \vskip\csuse{afterruleX@#1}%
2220 \fi%
2221 \splittopskip=\ht\strutbox
2222 \expandafter
2223 \rigidbalance\csname mpfootins#1\endcsname \tw@ \splittopskip}}
2224

```

25.4 Three columns footnotes

The following macros set footnotes in three columns. It is assumed that the length of each footnote is less than the column width.

```

\footthreecolX \footthreecolX{\series}
2225 \newcommand*\footthreecolX[1]{\%
2226 \csgdef{series@displayX#1}{threecol}
2227 \expandafter\let\csname regvfootnote#1\endcsname=\threecolvfootnoteX
2228 \expandafter\let\csname footfmt#1\endcsname=\threecolfootfmtX
2229 \expandafter\let\csname footgroup#1\endcsname=\threecolfootgroupX
2230 \threecolfootsetupX{#1}
2231 \expandafter\let\csname mpvfootnote#1\endcsname=\mpnormalvfootnoteX
2232 \expandafter\let\csname mpfootgroup#1\endcsname=\mpthreecolfootgroupX
2233 \mpthreecolfootsetupX{#1}}
2234

```

```

\threecolfootsetupX \threecolfootsetupX{\series}
\mpthreecolfootsetupX 2235 \newcommand*{\threecolfootsetupX}[1]{%
2236   \count\csname footins#1\endcsname 333
2237   \multiply\dimen\csname footins#1\endcsname by \thr@@
2238   \newcommand*{\mpthreecolfootsetupX}[1]{%
2239     \count\csname mpfootins#1\endcsname 333
2240     \multiply\dimen\csname mpfootins#1\endcsname by \thr@@
2241
\threecolvfootnoteX \threecolvfootnoteX{\series}{\text}
2242 \newcommand*{\threecolvfootnoteX}[2]{%
2243   \insert\csname footins#1\endcsname\bgroup
2244     \csuse{notefontsizeX@#1}
2245     \footsplitskips
2246     \@nameuse{footfmt#1}{#1}{#2}\egroup
2247
\threecolfootfmtX \threecolfootfmtX{\series}
2248 \newcommand*{\threecolfootfmtX}[2]{%
2249   \protected@edef\@currentlabel{%
2250     \@nameuse{@thefnmark#1}%
2251   }%
2252   \hangindent=\csuse{hangindentX@#1}%
2253   \normal@pars
2254   \hsize \csuse{hsizethreecolX@#1}
2255   \parindent=\z@
2256   %%% \parfillskip=0pt \@plus 1fil
2257   \tolerance=5000\relax
2258   \raggedright
2259   \leavevmode
2260   {\csuse{notenunfontX@#1}\@nameuse{footfootmark#1}\strut%\enspace
2261     #2\strut\par}\allowbreak}
2262
\threecolfootgroupX \threecolfootgroupX{\series}
\mpthreecolfootgroupX 2263 \newcommand*{\threecolfootgroupX}[1]{\csuse{notefontsizeX@#1}
2264   \splittopskip=\ht\strutbox
2265   \expandafter
2266   \rigidbalance\csname footins#1\endcsname \thr@@ \splittopskip}}
2267 \newcommand*{\mpthreecolfootgroupX}[1]{%
2268   \vskip\skip\@nameuse{mpfootins#1}
2269   \ifl@dpairing\ifparledgroup
2270     \leavevmode\marks\parledgroup@{begin}%
2271     \marks\parledgroup@series{#1}%
2272     \marks\parledgroup@type{footnoteX}%
2273   \fi\fi\normalcolor
2274   \ifparledgroup%
2275     \ifl@dpairing%
2276     \else%

```



```

2277 \setnotesXwidthliketwocolumns@{#1}%
2278 \setnotesXpositionliketwocolumns@{#1}%
2279 \print@footnoteXrule{#1}%
2280 \vskip\csuse{afterruleX@#1}%
2281 \fi%
2282 \else%
2283 \setnotesXwidthliketwocolumns@{#1}%
2284 \setnotesXpositionliketwocolumns@{#1}%
2285 \print@footnoteXrule{#1}%
2286 \vskip\csuse{afterruleX@#1}%
2287 \fi%
2288 \splittopskip=\ht\strutbox
2289 \expandafter
2290 \rigidbalance\csname mpfootins#1\endcsname \thr@@ \splittopskip}}
2291

```

25.5 Paraphed footnotes

The following macros set footnotes as one paragraph.

```

\footparagraphX \footparagraphX{<series>}
2292 \newcommand*{\footparagraphX}[1]{%
2293 \csgdef{series@displayX#1}{paragraph}
2294 \expandafter\newcount\csname prevpage#1@num\endcsname
2295 \expandafter\let\csname footstart#1\endcsname=\parafootstartX
2296 \expandafter\let\csname regvfootnote#1\endcsname=\para@vfootnoteX
2297 \expandafter\let\csname footfmt#1\endcsname=\parafootfmtX
2298 \expandafter\let\csname footgroup#1\endcsname=\para@footgroupX
2299 \expandafter\let\csname footnoterule#1\endcsname=\normalfootnoteruleX
2300 \count\csname footins#1\endcsname=1000
2301 \dimen\csname footins#1\endcsname=\csuse{maxhnotesX@#1}
2302 \skip\csname footins#1\endcsname=\csuse{beforenotesX@#1}
2303 \expandafter\let\csname mpvfootnote#1\endcsname=\mppara@vfootnoteX
2304 \expandafter\let\csname mpfootgroup#1\endcsname=\mppara@footgroupX
2305 \count\csname mpfootins#1\endcsname=1000
2306 \dimen\csname mpfootins#1\endcsname=\csuse{maxhnotesX@#1}
2307 \skip\csname mpfootins#1\endcsname=\csuse{beforenotesX@#1}
2308 \para@footsetupX{#1}}
2309
\para@footsetupX \para@footsetupX{<series>}
2310 \newcommand*{\para@footsetupX}[1]{\csuse{notefontsizeX@#1}
2311 \setnotesXwidthliketwocolumns@{#1}%
2312 \dimen0=\baselineskip
2313 \multiply\dimen0 by 1024
2314 \divide\dimen0 by \columnwidth \multiply\dimen0 by \footfudgefiddle\relax%
2315 \expandafter
2316 \xdef\csname footfudgefactor#1\endcsname{%
2317 \expandafter\strip@pt\dimen0 }}
2318

```

```

\parafootstartX \parafootstartX{<series>}
2319 \newcommand*{\parafootstartX}[1]{%
2320     \ifdimequal{0pt}{\prenotesX@}{}%
2321     {%
2322         \iftoggle{prenotesX@}{%
2323             \togglefalse{prenotesX@}\skip\csname footins#1\endcsname=\csuse{prenotesX@}}%
2324             }%
2325     }%
2326     \vskip\skip\csname footins#1\endcsname%
2327     \leftskip=\z@
2328     \rightskip=\z@
2329     \parindent=\z@
2330     \vskip\skip\@nameuse{footins#1}%
2331     \setnotesXwidthliketwocolumns@{#1}%
2332     \setnotesXpositionliketwocolumns@{#1}%
2333     \print@footnoteXrule{#1}%
2334     \vskip\csuse{afterruleX@#1}%
2335 }
2336

\para@vfootnoteX \para@vfootnoteX{<series>}{<text>}
\mppara@vfootnoteX 2337 \newcommand*{\para@vfootnoteX}[2]{%
2338     \insert\csname footins#1\endcsname
2339     \bgroup
2340     \csuse{bhooknoteX@#1}
2341     \csuse{notefontsizeX@#1}
2342     \footsplitskips
2343     \setbox0=\vbox{\hsize=\maxdimen
2344         \noindent\@nameuse{footfmt#1}{#1}{#2}}%
2345     \setbox0=\hbox{\unvxh0[#1]}%
2346     \dp0=\z@
2347     \ht0=\csname footfudgefactor#1\endcsname\wd0
2348     \box0
2349     \penalty0
2350     \egroup}
2351 \newcommand*{\mppara@vfootnoteX}[2]{%
2352     \global\setbox\@nameuse{mpfootins#1}\vbox{%
2353         \unvbox\@nameuse{mpfootins#1}
2354         \csuse{bhooknoteX@#1}
2355         \csuse{notefontsizeX@#1}
2356         \footsplitskips
2357         \setbox0=\vbox{\hsize=\maxdimen
2358             \noindent\color@begingroup\@nameuse{footfmt#1}{#1}{#2}\color@endgroup}%
2359         \setbox0=\hbox{\unvxh0[#1]}%
2360         \dp0=\z@
2361         \ht0=\csname footfudgefactor#1\endcsname\wd0
2362         \box0
2363         \penalty0}}
2364

```

```

\parafootfmtX \parafootfmtX{<series>}
2365 \newcommand*{\parafootfmtX}[2]{%
2366   \protected@edef\@currentlabel{%
2367     \@nameuse{@thefnmark#1}%
2368   }%
2369   \insertparafootsep{#1}%
2370   \ledsetnormalparstuff
2371   {\csuse{notenumfontX@#1}\csuse{notenumfontX@#1}\@nameuse{footfootmark#1}\strut%\enspace
2372     #2\penalty-10}}
2373
\para@footgroupX \para@footgroupX{<series>}
\mppara@footgroupX 2374 \newcommand*{\para@footgroupX}[1]{%
2375   \unvbox\csname footins#1\endcsname
2376   \ifcsstring{raggedX@#1}{L}{\RaggedLeft}{}%
2377   \ifcsstring{raggedX@#1}{R}{\RaggedRight}{}%
2378   \makehboxofhboxes
2379   \setbox0=\hbox{\unhbox0 \removehboxes}%
2380   \csuse{notefontsizeX@#1}
2381   \noindent\unhbox0\par}
2382 \newcommand*{\mppara@footgroupX}[1]{%
2383   \setnotesXwidthliketwocolumns@{#1}%
2384   \vskip\skip\@nameuse{mpfootins#1}
2385   \ifl@dpairing\ifparledgroup
2386     \leavevmode%
2387     \leavevmode\marks\parledgroup@{begin}%
2388     \marks\parledgroup@series{#1}%
2389     \marks\parledgroup@type{footnoteX}%
2390     \fi\fi\normalcolor
2391     \ifparledgroup%
2392       \ifl@dpairing%
2393       \else%
2394         \setnotesXwidthliketwocolumns@{#1}%
2395         \setnotesXpositionliketwocolumns@{#1}%
2396         \print@footnoteXrule{#1}%
2397         \vskip\csuse{afterruleX@#1}%
2398       \fi%
2399     \else%
2400       \setnotesXwidthliketwocolumns@{#1}%
2401       \setnotesXpositionliketwocolumns@{#1}%
2402       \print@footnoteXrule{#1}%
2403       \vskip\csuse{afterruleX@#1}%
2404     \fi%
2405     \unvbox\csname mpfootins#1\endcsname
2406     \ifcsstring{raggedX@#1}{L}{\RaggedLeft}{}%
2407     \ifcsstring{raggedX@#1}{R}{\RaggedRight}{}%
2408     \makehboxofhboxes
2409     \setbox0=\hbox{\unhbox0 \removehboxes}%
2410     \csuse{notefontsizeX@#1}
2411     \noindent\unhbox0\par}}

```

2412

26 Footnotes' width for two columns

We define here some commands which make sense only with `eledpar`, but must be called when defining notes parameters. These commands change the width of block notes to allow them to have the same size than two parallel columns.

`\old@hsize` These two commands are called at the beginning of critical or familiar notes groups. They set, if the option is enabled, the `\hsize`. They are also called `\setXnoteswidthliketwocolumns@` `\setnotesXwidthliketwocolumns@` at the on the setup for paragraphed notes.

```

2413
2414 \newdimen\old@hsize%
2415 \old@hsize=\hsize%
2416
2417 \newcommand{\setXnoteswidthliketwocolumns@}[1]{%
2418   \global\let\hsize@fornote=\hsize%
2419   \old@hsize=\hsize%
2420   \iftoggle{Xnoteswidthliketwocolumns@#1}%
2421     {%
2422       \csuse{setwidthliketwocolumns@\columns@position}%
2423       \global\let\hsize@fornote=\hsize%
2424     }%
2425   }%
2426   \let\hsize=\hsize@fornote%
2427   \let\columnwidth=\hsize@fornote%
2428 }%
2429
2430 \newcommand{\setnotesXwidthliketwocolumns@}[1]{%
2431   \global\let\hsize@fornote=\hsize%
2432   \old@hsize=\hsize%
2433   \iftoggle{notesXwidthliketwocolumns@#1}%
2434     {%
2435       \csuse{setwidthliketwocolumns@\columns@position}%
2436       \global\let\hsize@fornote=\hsize%
2437     }%
2438   }%
2439   \let\hsize=\hsize@fornote%
2440   \let\columnwidth=\hsize@fornote%
2441 }%
2442
```

`\setXnotespositionliketwocolumns@` `\setnotesXpositionliketwocolumns@` These two commands set the position of the critical / familiar footnotes, depending on the hooks `Xnoteswidthliketwocolumns` and `notesXwidthliketwocolumns`. They call commands which are defined only in `eledpar`, because this feature has no sens without `eledpar`.

```

2443 \newcommand{\setXnotespositionliketwocolumns@}[1]{%
2444   \iftoggle{Xnoteswidthliketwocolumns@#1}{%

```

```

2445 \csuse{setnotespositionliketwocolumns@\columns@position}%
2446 }{}%
2447 }%
2448
2449 \newcommand{\setnotesXpositionliketwocolumns@[1]{%
2450 \iftoggle{notesXwidthliketwocolumns@#1}{%
2451 \csuse{setnotespositionliketwocolumns@\columns@position}%
2452 }{}%
2453 }%
2454

```

27 Footnotes' order

`\fnpos` The `\fnpos` and `\mpfnpos` simply place their arguments in `\@fnpos` and `\@mpfnpos`,
`\mpfnpos` which will be used later in the output routine.

```

\@fnpos 2455 \def\@fnpos{familiar-critical}
\@mpfnpos 2456 \def\@mpfnpos{critical-familiar}
2457 \newcommand{\fnpos}[1]{\xdef\@fnpos{#1}}
2458 \newcommand{\mpfnpos}[1]{\xdef\@mpfnpos{#1}}

```

28 Footnotes' rule

Because the footnotes' rules can be shifted to the right when footnotes are set like two columns, we don't print them directly, but we put them in a `\vbox`.

```

\print@Xfootnoterule
\print@footnoteXrule 2459 \newcommand{\print@Xfootnoterule}[1]{%
2460 \nointerlineskip%
2461 \moveleft-\leftskip\vbox{\csuse{#1footnoterule}}%
2462 \nointerlineskip%
2463 }%
2464
2465 \newcommand{\print@footnoteXrule}[1]{%
2466 \nointerlineskip%
2467 \moveleft-\leftskip\vbox{\csuse{footnoterule#1}}%
2468 \nointerlineskip%
2469 }%
2470

```

29 Footnotes' output

`\doxtrafeeti` We have to add all the new kinds of familiar footnotes to the output routine.
`\doreinxtrafeeti` These are the class 1 feet.

```

2471 \newcommand*\doxtrafeeti{%
2472 \setbox\@outputbox \vbox{%
2473 \unvbox\@outputbox

```

```

2474 \def\do##1{\ifvoid\csuse{footins##1}\else\csuse{footstart##1}{##1}\csuse{footgroup##1}%
2475 \dolistloop{\@series}%
2476 }}
2477
2478 \newcommand{\doreinextrafeeti}{%
2479 \def\do##1{\ifvoid\csuse{footins##1}\else\insert\csuse{footins##1}{\unvbox\csuse{footins##1}}%
2480 \dolistloop{\@series}%
2481 }
2482

```

`\addfootinsX` Juste for backward compatibility: print a warning message.

```

2483 \newcommand*{\addfootinsX}[1]{%
2484 \led@warn@AddfootinsX@obsolete%
2485 \footnormalX{#1}%
2486 \g@addto@macro{\doextrafeeti}{%
2487 \setbox\@outputbox \vbox{%
2488 \unvbox\@outputbox
2489 \ifvoid\@nameuse{footins#1}\else
2490 \@nameuse{footstart#1}{#1}\@nameuse{footgroup#1}{#1}\fi}}%as
2491 \g@addto@macro{\doreinextrafeeti}{%
2492 \ifvoid\@nameuse{footins#1}\else
2493 \insert\@nameuse{footins#1}{\unvbox\@nameuse{footins#1}\fi}%
2494 \g@addto@macro{\l@dfambeginmini}{%
2495 \expandafter\expandafter\expandafter\let\expandafter\expandafter
2496 \csname footnote#1\endcsname \csname mpfootnote#1\endcsname}%
2497 \g@addto@macro{\l@dfamendmini}{%
2498 \ifvoid\@nameuse{mpfootins#1}\else\@nameuse{mpfootgroup#1}{#1}\fi}%
2499 }

```

30 Endnotes

`\l@d@end` Endnotes of all varieties are saved up in a file, typically named `<jobname>.end`.
`\ifl@dend@` `\l@d@end` is the output stream number for this file, and `\ifl@dend@` is a flag that's
`\l@dend@true` true when the file is open.
`\l@dend@false` 2500 `\newwrite\l@d@end`
2501 `\newif\ifl@dend@`

`\l@dend@open` `\l@dend@open` and `\l@dend@close` are the macros that are used to open and close
`\l@dend@close` the endnote file. Note that all our writing to this file is `\immediate`: all page and
line numbers for the endnotes are generated by the same mechanism we use for
the footnotes, so that there's no need to defer any writing to catch information
from the output routine.

```

2502 \newcommand{\l@dend@open}[1]{\global\l@dend@true\immediate\openout\l@d@end=#1\relax}
2503 \newcommand{\l@dend@close}{\global\l@dend@false\immediate\closeout\l@d@end}
2504

```

`\l@dend@stuff` `\l@dend@stuff` is used by `\beginnumbering` to do everything that's necessary for
the endnotes at the start of each section: it opens the `\l@d@end` file, if necessary,

and writes the section number to the endnote file.

```
2505 \newcommand{\l@dend@stuff}{%
2506   \ifl@dend@relax\else
2507     \l@dend@open{\jobname.end}%
2508   \fi
2509   \immediate\write\l@dend{\string\l@d@section{\the\section@num}}
2510 }
```

`\endprint` The `\endprint` here is nearly identical in its functioning to `\normalfootfmt`.
`\l@d@section` The endnote file also contains `\l@d@section` commands, which supply the section numbers from the main text; standard `eledmac` does nothing with this information, but it's there if you want to write custom macros to do something with it.

```
2511 \def\endprint#1#2#3#4{{\csuse{bhookXendnote@#4}\csuse{Xendnotefontsize@#4}{\csuse{Xendnotenumfont@#4}
2512   \enspace{\nottoggle{Xendlemmadisablefontselection@#4}{\select@lemmafnt#1|#2-#2}}\enskip#3\par
2513 }
2514 \let\l@d@section=\@gobble
2515 }
```

`\setprintendlines` The `\printendlines` macro is similar to `\printlines` but is for printing endnotes rather than footnotes.

The principal difference between foot- and endnotes is that footnotes are printed on the page where they are specified but endnotes are printed at a different point in the document. We need an indication of the source of an endnote; `\setprintendlines` provides this by always printing the page number. The coding is slightly simpler than `\setprintlines`.

First of all, we print the second page number only if the ending page number is different from the starting page number.

```
2516 \newcommand*{\setprintendlines}[6]{%
2517   \l@d@pnumfalse \l@d@dashfalse
2518   \ifnum#4=#1 \else
2519     \l@d@pnumtrue
2520     \l@d@dashtrue
2521   \fi
```

We print the ending line number if: (1) we're printing the ending page number, or (2) it's different from the starting line number.

```
2522   \ifl@d@pnum \l@d@elintrue \else \l@d@elinfalse \fi
2523   \ifnum#2=#5 \else
2524     \l@d@elintrue
2525     \l@d@dashtrue
2526   \fi
```

We print the starting sub-line if it's nonzero.

```
2527   \l@d@ssubfalse
2528   \ifnum#3=0 \else
2529     \l@d@ssubtrue
2530   \fi
```

We print the ending sub-line if it's nonzero and: (1) it's different from the starting sub-line number, or (2) the ending line number is being printed.

```

2531 \l@deslfalse
2532 \ifnum#6=0 \else
2533     \ifnum#6=#3
2534         \ifl@d@elin \l@d@esltrue \else \l@d@eslfalse \fi
2535     \else
2536         \l@d@esltrue
2537         \l@d@dashtrue
2538     \fi
2539 \fi}

```

`\printendlines` Now we're ready to print it all.

```

2540 \def\printendlines#1|#2|#3|#4|#5|#6|#7|{\begingroup
2541     \setprintendlines{#1}{#2}{#3}{#4}{#5}{#6}%

```

The only subtlety left here is when to print a period between numbers. But the only instance in which this is tricky is for the ending sub-line number: it could be coming after the starting sub-line number (in which case we want only the dash) or after an ending line number (in which case we need to insert a period).

```

2542 \printnpnum{#1} \linenumrep{#2}%
2543 \ifl@d@ssub \fullstop \sublinenumrep{#3}\fi
2544 \ifl@d@dash \endashchar\fi
2545 \ifl@d@pnum \printnpnum{#4}\fi
2546 \ifl@d@elin \linenumrep{#5}\fi
2547 \ifl@d@esl \ifl@d@elin \fullstop\fi \sublinenumrep{#6}\fi
2548 \endgroup}
2549

```

`\printnpnum` A macro to print a page number in an endnote.

```

2550 \newcommand*{\printnpnum}[1]{p.#1} }
2551

```

`\doendnotes` `\doendnotes` is the command you use to print one series of endnotes; it takes one argument: the series letter of the note series you want to print.

```

2552 \newcommand*{\doendnotes}[1]{\l@dend@close
2553     \begingroup
2554     \makeatletter
2555     \expandafter\let\csname #1end\endcsname=\endprint
2556     \input\jobname.end
2557     \endgroup}

```

`\noendnotes` You can say `\noendnotes` before the first `\beginnumbering` in your file if if you will not use any of the endnote commands: this will suppress the creation of an `.end` file. If you do have some lingering endnote commands in your file, the notes will be written to your terminal and to the log file.

```

2558 \newcommand*{\noendnotes}{\global\let\l@dend@stuff=\relax
2559     \global\chardef\l@dend@end=16 }

```


31 Generate series

In this section, X means the name of the series (A, B etc.)

`\series` `\series\series` creates one more newseries. It's the public command, which just loops on the private command `\newseries@`.

```
2560 \newcommand{\newseries}[1]{%
2561     \def\do##1{\newseries@{##1}}%
2562     \docsvlist{#1}
2563 }
```

`@series` The `\series@` macro is an etoolbox list, which contains the name of all series.

```
2564 \newcommand{\@series}{}%
```

The command `\newseries@\series` creates a new series of the footnote.

`\newseries@`

```
2565 \newcommand{\newseries@}[1]{
```

31.1 Test if series is still existing

```
2566     \xifinlist{#1}{\@series}{\led@warn@SeriesStillExist{#1}}%
2567     {%
```

31.2 Create all commands to memorize display options

```
2568     \newtoggle{Xlemmadisablefontselection@#1}
2569     \newtoggle{Xendlemmadisablefontselection@#1}
2570     \csgdef{Xhangindent@#1}{0pt}%
2571     \csgdef{hangindentX@#1}{0pt}%
2572     \csgdef{Xragged@#1}{}%
2573     \csgdef{raggedX@#1}{}%
2574     \csgdef{hsizetwocol@#1}{0.45 \hsize}%
2575     \csgdef{hsizetwocolX@#1}{0.45 \hsize}%
2576     \csgdef{hsizethreecol@#1}{.3 \hsize}%
2577     \csgdef{hsizethreecolX@#1}{.3 \hsize}%
2578     \csgdef{Xnotenumfont@#1}{\notenumfont}%
2579     \csgdef{Xendnotenumfont@#1}{\notenumfont}%
2580     \csgdef{notenumfontX@#1}{\notenumfont}%
2581     \csgdef{Xnotefontsize@#1}{\notefontsetup}%
2582     \csgdef{notefontsizeX@#1}{\notefontsetup}%
2583     \csgdef{Xendnotefontsize@#1}{\notefontsetup}%
2584     \csgdef{bhooknoteX@#1}{}%
2585     \csgdef{bhookXnote@#1}{}%
2586     \csgdef{bhookXendnote@#1}{}%
2587     \csgdef{boxlinenum@#1}{0pt}%
2588     \csgdef{boxsymlinenum@#1}{0pt}%
2589     \newtoggle{numberonlyfirstinline@#1}%
2590     \newtoggle{numberonlyfirstintwolines@#1}%
2591     \newtoggle{onlypstartinfootnote@#1}%
```

```

2592 \newtoggle{pstartinfootnote@#1}%
2593 \csgdef{symlinenum@#1}{\symlinenum}%
2594 \newtoggle{nonnumberinfootnote@#1}%
2595 \csgdef{beforenumberinfootnote@#1}{0pt}%
2596 \csgdef{afternumberinfootnote@#1}{0.5em}%
2597 \newtoggle{nonbreakableafternumber@#1}%
2598 \csgdef{beforesymlinenum@#1}{\csuse{beforenumberinfootnote@#1}}%
2599 \csgdef{aftersymlinenum@#1}{\csuse{afternumberinfootnote@#1}}%
2600 \csgdef{inplaceofnumber@#1}{1em}%
2601 \global\cslet{lemmaseparator@#1}{\rbracket}%
2602 \csgdef{beforelemmaseparator@#1}{0em}%
2603 \csgdef{afterlemmaseparator@#1}{0.5em}%
2604 \csgdef{inplaceoflemmaseparator@#1}{1em}%
2605 \csgdef{afternote@#1}{1em plus.4em minus.4em}%
2606 \csgdef{parafootsep@#1}{\parafootftmsep}%
2607 \csgdef{beforeXnotes@#1}{1.2em \@plus .6em \@minus .6em}%
2608 \csgdef{beforenotesX@#1}{1.2em \@plus .6em \@minus .6em}%
2609 \csgdef{afterXrule@#1}{0pt}%
2610 \csgdef{afterruleX@#1}{0pt}%
2611 \csgdef{txtbeforeXnotes@#1}{\relax}%
2612 \csgdef{maxhnotesX@#1}{\ledfootinsdim}%
2613 \csgdef{maxhXnotes@#1}{\ledfootinsdim}%
2614 \newtoggle{Xnoteswidthliketwocolumns@#1}%
2615 \newtoggle{notesXwidthliketwocolumns@#1}%

```

31.3 Create inserts, needed to add notes in foot

Concerning inserts, see chapter 15 of the TeXBook by D. Knuth

```

2616
2617 \expandafter\newinsert\csname mpfootins#1\endcsname
2618 \expandafter\newinsert\csname footins#1\endcsname
2619 \expandafter\newinsert\csname #1footins\endcsname
2620 \expandafter\newinsert\csname mp#1footins\endcsname

```

31.4 Create commands for critical apparatus, \Xfootnote

Note the double # in command: it's because command is made inside another command.

```

2621
2622 \global\newbool{parapparatus@}{\expandafter\newcommand\expandafter *}{\expandafter\new
2623 \begingroup%
2624 \newcommand{\content}{##2}%
2625 \ifnumberedpar@
2626 \ifledRcol%
2627 \ifluatex%
2628 \footnotelang@lua[R]%
2629 \fi%
2630 \@ifundefined{xpg@main@language}%if polyglossia
2631 {}%
2632 {\footnotelang@poly[R]}%

```

```

2633         \footnoteoptions@{R}{##1}{true}%
2634         \xright@appenditem{\noexpand\prepare@edindex@fornote{\l@d@nums}}%
2635 \noexpand\csuse{v#1footnote}{#1}%
2636         {{\l@d@nums}{\csexpandonce{@tag}}{\csexpandonce{content}}}}\to\inserts@listR
2637         \footnoteoptions@{R}{##1}{false}%
2638         \global\advance\insert@countR \@ne%
2639     \else%
2640         \ifluatex%
2641             \footnotelang@lua%
2642         \fi%
2643         \ifundefined{xpg@main@language}%if polyglossia
2644             {}%
2645             {\footnotelang@poly}%
2646         \footnoteoptions@{##1}{true}%
2647         \xright@appenditem{\noexpand\prepare@edindex@fornote{\l@d@nums}}%
2648 \noexpand\csuse{v#1footnote}{#1}%
2649         {{\l@d@nums}{\csexpandonce{@tag}}{\csexpandonce{content}}}}\to\inserts@list
2650         \global\advance\insert@count \@ne%
2651         \footnoteoptions@{##1}{false}%
2652     \fi
2653 \else
2654     \csuse{v#1footnote}{#1}{\{0|0|0|0|0|0|0\}}{##1}%
2655 \fi%
2656 \ignorespaces%
2657 \endgroup
2658 }

```

Set standard display and remember the display.

```

2659 \csgdef{series@display#1}{%
2660 \footnormal{#1}

```

31.5 Create tools for familiar footnotes (`\footnoteX`)

First, create the `\footnoteX` command.

```

2661
2662 \global\expandafter\newcommand\csname footnote#1\endcsname[1]{%
2663     \begingroup%
2664         \newcommand{\content}{##1}%
2665         \stepcounter{footnote#1}%
2666         \protected@csxdef{thefnmark#1}{\csuse{thefootnote#1}}%
2667         \csuse{@footnotemark#1}%
2668         \csuse{vfootnote#1}{#1}{\csexpandonce{content}}\m@mmf@prepare%
2669     \endgroup%
2670 }

```

The counters.

```

2671 \newcounter{footnote#1}
2672 \global\expandafter\renewcommand\csname thefootnote#1\endcsname{\arabic{footnote#1}}
2673 % \end{macrocode}
2674 % Don't forget to initialize series

```

```

2675 %      \begin{macrocode}
2676      \csgdef{series@displayX#1}{%
2677      \footnormalX{#1}

```

31.6 The endnotes

The `\Xendnote` macro functions to write one endnote to the `.end` file. We change `\newlinechar` so that in the file every space becomes the start of a new line; this generally ensures that a long note doesn't exceed restrictions on the length of lines in files.

```

2678
2679      \global\expandafter\newcommand\csname #1endnote\endcsname[2]{\newlinechar='40
2680      \global\@noneed@Footnotetrue%
2681      \newcommand{\content}{##1}%
2682      \immediate\write\l@d@end{\expandafter\string\csname #1end\endcsname%
2683      {\ifnumberedpar@l@d@nums\fi}%
2684      {\ifnumberedpar@csexpandonce{tag}\fi}{\csexpandonce{content}}{#1}}\ignorespaces
2685      }

```

`\Xendnote` commands called `\Xend` commands on to the endnote file; these are analogous to the various `footfmt` commands above, and they take the same arguments. When we process this file, we'll want to pick out the notes of one series and ignore all the rest. To do that, we equate the `end` command for the series we want to `\endprint`, and leave the rest equated to `\@gobblethree`, which just skips over its three arguments.²⁷

```

2686
2687      \global\cslet{#1end}{\@gobblefour}
2688 %\end{macrocode}
2689 % We need to be able to modify \Eledmac's footnote macros and restore their
2690
2691      \global\csletcs{#1@footnote}{#1footnote}
2692 % \cs{Stock series in \cs{@series}
2693 %      \begin{macrocode}
2694
2695      \listxadd{\@series}{#1}
2696 }
2697 }% End of \newseries

```

31.7 Init standards series (A,B,C,D,E,Z)

```

2698 \newseries{A,B,C,D,E,Z}

```

31.8 Some tools

`\firstseries` `\seriesatbegin{<s>}` changes the order of series, to put the series `<s>` at the beginning of the list. The series can be the result of a command.

```

2699 \newcommand{\seriesatbegin}[1]{

```

²⁷Christophe Hebeisen (christophe.hebeisen@a3.epfl.ch) emailed on 2003/11/05 to say he had found that `\@gobblethree` was also defined in the `amsfonts` package.

```

2700     \edef\series{#1}
2701     \def\new{}
2702     \listadd{\new}{\series}
2703     \def\do##1{\ifcsstring{series}{##1}{\listadd{\new}{##1}}}
2704     \dolistloop{\@series}
2705     \xdef\@series{\new}
2706 }
2707 % \end{macrocode}
2708 % \end{macro}
2709 % \begin{macro}{\seriesatend}
2710 % And \cs{seriesatend} moves the series to the end of the list.
2711 % \begin{macrocode}
2712 \newcommand{\seriesatend}[1]{
2713     \edef\series{#1}
2714     \def\new{}
2715     \def\do##1{\ifcsstring{series}{##1}{\listadd{\new}{##1}}}
2716     \dolistloop{\@series}
2717     \listadd{\new}{\series}
2718     \xdef\@series{\new}
2719 }
2720 % \end{macrocode}
2721 % \end{macro}
2722 % \subsection{Display}
2723 % \changes{v1.0}{2012/09/15}{New generic commands to customize footnote display.}
2724 % \subsubsection{Options}
2725 % \begin{macro}{\settoggle@series}
2726 % \changes{v1.1}{2012/09/25}{\cs{settoggle@series} switch the global value of the toggle, not only th
2727 % \changes{v1.13.0}{2014/09/16}{\cs{settoggle@series} can take an optional arguments to reload series
2728 % \cs{settoggle@series}\marg{series}\marg{toggle}\marg{value} is a generic command to switch toggles
2729
2730 % \begin{macrocode}
2731 \newcommandx{\settoggle@series}[4][4]{%
2732     \def\do##1{%
2733         \global\settoggle{#2@##1}{#3}%
2734         \ifstrequal{#4}{reload}%
2735             {%
2736                 \csuse{foot\csuse{series@display##1}}{##1}%
2737                 \csuse{foot\csuse{series@displayX##1}}{##1}%
2738             }%
2739         {%
2740             }%
2741         \ifstreempty{#1}{%
2742             \dolistloop{\@series}%
2743         }%
2744         {%
2745             \docsvlist{#1}%
2746         }%
2747 }

```

`\setcommand@series` `\setcommand@series{<series>}{<command>}{<value>}` is a generic command to

change commands for some series.

```

2748 \newcommandx{\setcommand@series}[4][4]{%
2749   \def\do##1{
2750     \csgdef{#2@##1}{#3}
2751     \ifstrequal{#4}{reload}{
2752       \csuse{foot\csuse{series@display##1}}{##1}
2753       \csuse{foot\csuse{series@displayX##1}}{##1}
2754     }{}}
2755   \ifstreempty{#1}{%
2756     \dolistloop{\@series}%
2757   }%
2758   {%
2759     \docsvlist{#1}%
2760   }%
2761 }%
```

`\newhookcommand@series` `\newhookcommand@series\command` names is a generic command to add new commands for hooks, like `\hsizetwocol`.

```

2762 \newcommand{\newhookcommand@series}[1]{%
2763   \global\expandafter\newcommand\expandafter*\csname #1\endcsname[2][1]{%
2764     \setcommand@series{##1}{#1}{##2}%
2765   }%
2766 }
2767 \newhookcommand@series{Xhangindent}
2768
2769 \newhookcommand@series{hangindentX}
2770
2771 \newhookcommand@series{Xragged}
2772
2773 \newhookcommand@series{raggedX}
2774
2775 \newhookcommand@series{hsizetwocol}
2776
2777 \newhookcommand@series{hsizethreecol}
2778
2779 \newhookcommand@series{hsizetwocolX}
2780
2781 \newhookcommand@series{hsizethreecolX}
2782
2783 \newhookcommand@series{Xnotenumfont}
2784
2785 \newhookcommand@series{notenumfontX}
2786
2787 \newhookcommand@series{Xendnotenumfont}
2788
2789 \newhookcommand@series{bhooknoteX}
2790
2791 \newhookcommand@series{bhookXnote}
2792
```

```

2793 \newhookcommand@series{bhookXendnote}
2794
2795 \newhookcommand@series{Xnotefontsize}
2796
2797 \newhookcommand@series{notefontsizeX}
2798
2799 \newhookcommand@series{Xendnotefontsize}
2800
2801 \newhookcommand@series{boxlinenum}
2802
2803 \newhookcommand@series{boxsymlinenum}
2804
2805 \newhookcommand@series{parafootsep}
2806
2807 \newhookcommand@series{symlinenum}
2808
2809 \newhookcommand@series{beforenumberinfootnote}
2810
2811 \newhookcommand@series{afternumberinfootnote}
2812
2813 \newhookcommand@series{beforesymlinenum}
2814
2815 \newhookcommand@series{aftersymlinenum}
2816
2817 \newhookcommand@series{inplaceofnumber}
2818
2819 \newhookcommand@series{lemmaseparator}
2820
2821 \newhookcommand@series{beforelemmaseparator}
2822
2823 \newhookcommand@series{afterlemmaseparator}
2824
2825 \newhookcommand@series{inplaceoflemmaseparator}
2826
2827 \newhookcommand@series{afternote}
2828
2829 \newhookcommand@series{txtbeforeXnotes}
2830
2831 \newhookcommand@series{afterruleX}
2832
2833 \newhookcommand@series{afterXrule}
2834

```

`hookcommand@series@reload` `\newhookcommand@series@reload` does the same thing as `\newhookcommand@series` but the commands created by this macro also reload the series displaying (normal, paragraph, twocol, threecol).

```

2835 \newcommand{\newhookcommand@series@reload}[1]{%
2836   \global\expandafter\newcommand\expandafter*\csname #1\endcsname[2][1]{%
2837     \setcommand@series{##1}{#1}{##2}[reload]%
2838   }%

```

```

2839 }
2840 \newhookcommand@series@reload{beforeXnotes}
2841
2842 \newhookcommand@series@reload{beforenotesX}
2843
2844 \newhookcommand@series@reload{maxhnotesX}
2845
2846 \newhookcommand@series@reload{maxhXnotes}
2847 % \end{macrocode}
2848 % \end{macro}
2849 % \begin{macro}{\newhooktoggle@series}
2850 % \cs{newhooktoggle@series}\cs{command names} is a generic command to add new commands for
2851 % \begin{macrocode}
2852 \newcommand{\newhooktoggle@series}[1]{%
2853   \global\expandafter\newcommandx\expandafter*\csname #1\endcsname[2][1,2={true},usedefault]
2854   \settoggle@series{##1}{#1}{##2}%
2855   }%
2856 }
2857 \newhooktoggle@series{numberonlyfirstinline}
2858 \newhooktoggle@series{numberonlyfirstintwolines}
2859 \newhooktoggle@series{nonnumberinfootnote}
2860 \newhooktoggle@series{pstartinfootnote}
2861 \newhooktoggle@series{onlypstartinfootnote}
2862 \newhooktoggle@series{nonbreakableafternumber}
2863 \newhooktoggle@series{Xlemmadisablefontselection}
2864 \newhooktoggle@series{Xendlemmadisablefontselection}

\newhooktoggle@series \newhookcommand@toggle@reload does the same thing as \newhooktoggle@series
but the commands created by this macro also reload the series displaying (normal,
paragraph, twocol, threecol).

2865 \newcommand{\newhooktoggle@series@reload}[1]{%
2866   \global\expandafter\newcommandx\expandafter*\csname #1\endcsname[2][1,2={true},usedefault]
2867   \settoggle@series{##1}{#1}{##2}[reload]%
2868   }%
2869 }%
2870
2871 \newhooktoggle@series@reload{Xnoteswidthliketwocolumns}%
2872 \newhooktoggle@series@reload{notesXwidthliketwocolumns}%
2873

```

31.9 Old commands, kept for backward compatibility

The next commands are kept for ascendant compatibility, but should not be used anymore.

```

\notenumfont
\notefontsetup 2874 \newcommand*{\notenumfont}{\normalfont}
\ifledplinenum 2875 \newcommand*{\notefontsetup}{\footnotesize}
\symplinenum 2876 \newif\ifledplinenum

```



```
2877 \ledplinenumtrue
2878 \newcommand*\symplinenum{}
```

31.10 Hooks for a particular footnote

`\nonum@` `\nonum@` toggle is used to disable line number printing in a particular footnote.

```
2879 \newtoggle{nonum@}
```

`\nosep@` `\nonum@` toggle is used to disable the lemma separator in a particular footnote.

```
2880 \newtoggle{nosep@}
```

31.11 Alias

`\nolemmaseparator` `\nolemmaseparator[<series>]` is just an alias for `\lemmaseparator[<series>]`.

```
2881 \newcommand*\nolemmaseparator[1][1]{\lemmaseparator[#1]}
```

`\interparanoteglue` The `\ipn@skip` skip and `\interparanoteglue` command are kept for backward compatibility, but should not be used anymore.

```
\ipn@skip
2882 \newskip\ipn@skip
2883 \newcommand*\interparanoteglue[1]{%
2884     {\notefontsetup\global\ipn@skip=#1 \relax}}
2885 \interparanoteglue{1em plus.4em minus.4em}
```

`\parafootftmsep` The `\parafootftmsep` macro is kept for backward compatibility. It is default value of `\parafootsep@series`.

```
2886 \newcommand{\parafootftmsep}{}%
```

31.12 Line number printing

`\printlinefootnote` The `\printlinefootnote` macro is called in each `\<type>footfmt` command. It controls whether the line number is printed or not, according to the previous options. Its first argument is the information about lines, its second is the series of the footnote.

```
2887 \newcommand{\printlinefootnote}[2]{%
2888     \def\extractline@##1|##2|##3|##4|##5|##6|##7|{##2}%
2889     \def\extractsubline@##1|##2|##3|##4|##5|##6|##7|{##3}%
2890     \def\extractendline@##1|##2|##3|##4|##5|##6|##7|{##5}%
2891     \def\extractendsubline@##1|##2|##3|##4|##5|##6|##7|{##6}%
2892     \iftoggle{numberonlyfirstintwolines@#2}{%
2893         \edef\lineinfo@{\extractline@ #1| - \extractsubline@ #1| - \extractendline@ #1| - \extractendsubline@ #1|}%
2894         }%
2895         {%
2896             \edef\lineinfo@{\extractline@ #1| - \extractsubline@ #1|}%
2897             }%
2898     \iftoggle{nonum@}{%Try if the line number must printed for this specific not (by default, yes)
2899     \hspace{\csuse{inplaceofnumber@#2}}%
2900     }%
```

```

2901   {%
2902       {%
2903           \iftoggle{nonnumberinfootnote@#2}%Try if the line number must printed (by default)
2904           {%
2905               \hspace{\csuse{inplaceofnumber@#2}}%
2906           }%
2907       {%
2908           {\iftoggle{numberonlyfirstinline@#2}% If for this series the line number must
2909           {%
2910               \ifcsdef{prevline#2}%
2911               {%Be sure the \prevline exists.
2912               \ifcsequal{prevline#2}{lineinfo@}%Try it
2913               {%
2914                   \ifcsempy{symlinenum@#2}% Try if a symbol is defined
2915                   {%
2916                       \hspace{\csuse{inplaceofnumber@#2}}%
2917                   }%
2918                   {\hspace{\csuse{beforeasymlinenum@#2}}\csuse{Xnotenumfont@#2}%
2919                   \ifdimequal{\csuse{boxsymlinenum@#2}}{0pt}%
2920                       {\csuse{symlinenum@#2}}%
2921                       {\hbox to \csuse{boxsymlinenum@#2}{\csuse{symlinenum@#2}\hfill}}
2922                   \hspace{\csuse{aftersymlinenum@#2}}}%
2923               }%
2924           }%
2925           \hspace{\csuse{beforenumberinfootnote@#2}}\csuse{Xnotenumfont@#2}%
2926           \ifdimequal{\csuse{boxlinenum@#2}}{0pt}{%
2927               \iftoggle{pstartinfootnote@#2}{\printpstart}{}%
2928               \printlines#1|}%
2929           {%
2930               \hbox to \csuse{boxlinenum@#2}{%
2931                   \iftoggle{pstartinfootnote@#2}{\printpstart}{}%
2932                   \iftoggle{onlypstartinfootnote@#2}{\printlines#1|}%
2933               }%
2934           }%
2935           \iftoggle{nonbreakableafternumber@#2}{\nobreak}{\hspace{\csuse{afternumber@#2}}}
2936       }%
2937   }%
2938   {%
2939       \hspace{\csuse{beforenumberinfootnote@#2}}\csuse{Xnotenumfont@#2}%
2940       \ifdimequal{\csuse{boxlinenum@#2}}{0pt}{%
2941           \iftoggle{pstartinfootnote@#2}{\printpstart}{}%
2942           \iftoggle{onlypstartinfootnote@#2}{\printlines#1|}%
2943       }%
2944       \hbox to \csuse{boxlinenum@#2}{%
2945           \iftoggle{pstartinfootnote@#2}{\printpstart}{}%
2946           \iftoggle{onlypstartinfootnote@#2}{\printlines#1|}%
2947       }%
2948   }%
2949   \iftoggle{nonbreakableafternumber@#2}{\nobreak}{\hspace{\csuse{afternumber@#2}}}
2950 }%

```

```

2951      }%
2952      {%
2953      \hspace{\csuse{beforenumberinfootnote@#2}}\csuse{Xnotenumfont@#2}%
2954      \ifdimequal{\csuse{boxlinenum@#2}}{0pt}{%
2955          \iftoggle{pstartinfootnote@#2}{\printpstart}{}%
2956          \iftoggle{onlypstartinfootnote@#2}{\printlines#1|}%
2957      }%
2958      {%
2959      \hbox to \csuse{boxlinenum@#2}{%
2960          \iftoggle{pstartinfootnote@#2}{\printpstart}{}%
2961          \iftoggle{onlypstartinfootnote@#2}{\printlines#1|}%
2962          \hfill}%
2963      }%
2964      \iftoggle{nonbreakableafternumber@#2}{\nobreak}{\hspace{\csuse{afternumberinfootnote@#2}}}%
2965      }%
2966      \csxdef{prevline#2}{\lineinfo@}%
2967      }%
2968      }%
2969      }%
2970      }%
2971 }

```

32 Output routine

Now we begin the output routine and associated things.

```

\pageno \pageno is a page number, starting at 1, and \advancepageno increments the
\advancepageno number.
2972 \countdef\pageno=0 \pageno=1
2973 \newcommand*{\advancepageno}{\ifnum\pageno<\z@ \global\advance\pageno\m@ne
2974 \else\global\advance\pageno\@ne\fi}
2975

```

The next portion is probably the trickiest part of moving from TeX to L^AT_EX. The original code is below, but we need something very different.

This is a new output routine, with changes to handle printing all our footnotes. Those changes have not been added directly, but are in macros that get called here: that should make it easier to see what would need to be taken over to a different output routine. We continue to use the `\pagebody`, `\makeheadline`, `\makefootline`, and `\dosupereject` macros of PLAIN TeX; for those macros, and the original version of `\output`, see *The TeXbook*, p. 364.

```

\output{\edmac@output}
\def\edmac@output{\shipout\vbox{\normal@pars
\box{\makeheadline\pagebody\makefootline}%
}%
\advancepageno
\ifnum\outputpenalty>-\@MM\else\dosupereject\fi}

```

```

\def\pagecontents{\page@start
\ifvoid\topins\else\unvbox\topins\fi
\dimen@=\dp\@cclv \unvbox\@cclv % open up \box255
\do@feet
\ifraggedbottom \kern-\dimen@ \vfil \fi}

```

\do@feet ships out all the footnotes. Standard EDMAC has only five feet, but there is nothing in principal to prevent you from creating an arachnoid or centipedal edition; straightforward modifications of EDMAC are all that's required. However, the myriapedal edition is ruled out by eTeX limitations: the number of insertion classes is limited to 2^{16} .

With luck we might only have to change \@makecol and \@reinserts. The kernel definition of these, and perhaps some other things, is:

```

\gdef \@makecol {%
\ifvoid\footins
\setbox\@outputbox \box\@cclv
\else
\setbox\@outputbox \vbox {%
\boxmaxdepth \@maxdepth
\@tempdima\dp\@cclv
\unvbox \@cclv
\vskip \skip\footins
\color@begingroup
\normalcolor
\footnoterule
\unvbox \footins
\color@endgroup
}%
\fi
\edef\@freelist{\@freelist\@midlist}%
\global \let \@midlist \@empty
\@combinefloats
\ifvbox\@kludgeins
\@makespecialcolbox
\else
\setbox\@outputbox \vbox to\@colht {%
\@texttop
\dimen@ \dp\@outputbox
\unvbox\@outputbox
\vskip -\dimen@
\@textbottom
}%
\fi
\global \maxdepth \@maxdepth
}

\gdef \@reinserts{%

```

```

\ifvoid\footins\else\insert\footins{\unvbox\footins}\fi
\ifvbox\@kludgeins\insert\@kludgeins{\unvbox\@kludgeins}\fi
}

```

Now we start actually changing things.

`\m@m@makecolfloats` These macros are defined in the memoir class and form part of the definition of `\m@m@makecoltext` `\@makecol`.

```

\m@m@makecolintro 2976 \providecommand{\m@m@makecolfloats}{%
2977   \xdef\@freelist{\@freelist\@midlist}%
2978   \global \let \@midlist \@empty
2979   \@combinefloats}
2980 \providecommand{\m@m@makecoltext}{%
2981   \ifvbox\@kludgeins
2982     \@makespecialcolbox
2983   \else
2984     \setbox\@outputbox \vbox to\@colht {%
2985       \@texttop
2986       \dimen@ \dp\@outputbox
2987       \unvbox\@outputbox
2988       \vskip -\dimen@
2989       \@textbottom}%
2990   \fi}
2991 \providecommand{\m@m@makecolintro}{%
2992

```

`\l@d@makecol` This is a partitioned version of the ‘standard’ `\@makecol`, with the initial code put into another macro.

```

2993 \gdef\l@d@makecol{%
2994   \l@ddofootinsert
2995   \m@m@makecolfloats
2996   \m@m@makecoltext
2997   \global \maxdepth \@maxdepth}
2998

```

`\ifFN@bottom` The `\ifFN@bottom` macro is defined by the footmisc package. If this package is not loaded, we define it.

```

2999 \AtBeginDocument{\@ifpackageloaded{footmisc}{\newif\ifFN@bottom}}

```

`\l@ddofootinsert` This macro essentially holds the initial portion of the kernel `\@makecol` code.

```

3000 \newcommand*\l@ddofootinsert{%
3001   %% \page@start
3002   \ifvoid\footins
3003     \setbox\@outputbox \box\@cclv
3004   \else
3005     \setbox\@outputbox \vbox {%
3006       \boxmaxdepth \@maxdepth

```

```

3007      \@tempdima\dp\@cclv
3008      \unvbox \@cclv
3009      \ifFN@bottom\vfill\fi\vskip \skip\footins%% If the option bottom of loadmisc pack
3010      \color@begingroup
3011      \normalcolor
3012      \footnoterule
3013      \unvbox \footins
3014      \color@endgroup
3015      }%
3016  \fi

```

That's the end of the copy of the kernel code. We finally call a macro to handle all the additional EDMAC feet.

```

3017  \l@ddoxtrafeet
3018 }
3019

```

`\doxtrafeet` `\doxtrafeet` is the code extending `\@makecol` to cater for the extra `eledmac` feet. We have two classes of extra footnotes. By default, we order the footnote inserts so that the regular footnotes are first, then class 1 (familiar footnotes) and finally class 2 (critical footnotes).

```

3020 \newcommand*{\l@ddoxtrafeet}{%
3021   \IfStrEq{familiar-critical}{\@fnpos}%
3022   {\doxtrafeeti\doxtrafeetii}%
3023   {%
3024     \IfStrEq{critical-familiar}{\@fnpos}%
3025     {\doxtrafeetii\doxtrafeeti}%
3026     {\doxtrafeeti\doxtrafeetii}%
3027   }%
3028 }%
3029

```

`\doxtrafeetii` `\doxtrafeetii` is the code extending `\@makecol` to cater for the extra critical feet (class 2 feet). NOTE: the code is likely to be 'featurefull'.

```

3030 \newcommand*{\doxtrafeetii}{%
3031   \setbox\@outputbox \vbox{%
3032     \unvbox\@outputbox
3033     \@opxtrafeetii}}

```

`\@opxtrafeetii` The extra critical feet to be aded to the output.

```

3034 \newcommand*{\@opxtrafeetii}{%
3035   \def\do##1{\ifvoid\csuse{##1footins}\else\csuse{##1footstart}{##1}\csuse{##1footgroup}{##1}}
3036   \dolistloop{\@series}}

```

`\l@ddodoreinextrafeet` `\l@ddodoreinextrafeet` is the code for catering for the extra footnotes within `\@reinserts`. The implementation may well have to change. We use the same classes and ordering as in `\l@ddoxtrafeet`.

```

3037 \newcommand*{\l@ddodoreinextrafeet}{%
3038   \doreinextrafeeti

```

```

3039 \doreinextrafeetii}
3040

```

`\doreinextrafeetii` `\doreinextrafeetii` is the code for catering for the class 2 extra critical footnotes within `\@reinserts`. The implementation may well have to change.

```

3041 \newcommand*{\doreinextrafeetii}{%
3042   \def\do##1{\ifvoid\csuse{##1footins}\else\insert\csuse{##1ootins}{\unvbox\csuse{##1footins}}\fi}
3043   \dolistloop{\@series}
3044 }
3045

```

`\l@d@reinserts` And here is the modified version of `\@reinserts`.

```

3046 \gdef \l@d@reinserts{%
3047   \ifvoid\footins\else\insert\footins{\unvbox\footins}\fi
3048   \l@dd@doreinextrafeet
3049   \ifvbox\@kludgeins\insert\@kludgeins{\unvbox\@kludgeins}\fi
3050 }
3051

```

The memoir class does not use the ‘standard’ versions of `\@makecol` and `\@reinserts`, due to its sidebar insert. We had better add that code if memoir is used. (It can be awkward dealing with `\if` code within `\if` code, so don’t use `\ifl@dmemoir` here.)

```

3052 \@ifclassloaded{memoir}{%
    memoir is loaded so we use memoir’s built in hooks.
3053   \g@addto@macro{\m@m@doextrafeet}{\l@dd@extrafeet}%
3054   \g@addto@macro{\m@m@dodoreinextrafeet}{\l@dd@doreinextrafeet}%
3055 }{%

```

memoir has not been loaded, so redefine `@makecol` and `@reinserts`.

```

3056 \gdef\@makecol{\l@d@makecol}%
3057 \gdef\@reinserts{\l@d@reinserts}%
3058 }
3059

```

`\addfootins` `\addfootins` is for backward compatibility, but should’nt be used anymore.

```

3060 \newcommand*{\addfootins}[1]{%
3061   \led@warn@AddfootinsObsolete%
3062   \footnormal{#1}
3063   \g@addto@macro{\@opxtrafeetii}{%
3064     \ifvoid\@nameuse{#1footins}\else
3065       \@nameuse{#1footstart{#1}}\@nameuse{#1footgroup}{#1}\fi}
3066   \g@addto@macro{\doreinextrafeetii}{%
3067     \ifvoid\@nameuse{#1footins}\else
3068       \insert\@nameuse{#1footins}{\unvbox\@nameuse{#1footins}}\fi}
3069   \g@addto@macro{\l@dedbeginmini}{%
3070     \expandafter\let\csname #1footnote\endcsname = \@nameuse{mp#1footnote}}
3071   \g@addto@macro{\l@dedendmini}{%
3072     \ifvoid\@nameuse{mp#1footins}\else\@nameuse{mpfootgroup#1{#1}}\fi}
3073 }

```

It turns out that `\@doclearpage` also needs modifying.

`\if@led@nofoot` We have to check if there are any leftover feet. `\@led@extranofeet` is a hook for
`\@led@extranofeet` handling further footnotes.

```
3074 \newif\if@led@nofoot
3075 \newcommand*{\@led@extranofeet}{}
3076
3077 \@ifclassloaded{memoir}{%
```

If the memoir class is loaded we hook into its modified `\@doclearpage`.

`\@mem@extranofeet`

```
3078 \g@addto@macro{\@mem@extranofeet}{%
3079 \def\do#1{\ifvoid\csuse{#1footins}\else\@mem@nofootfalse\fi%
3080 \ifvoid\csuse{footins#1}\else\@mem@nofootfalse\fi%
3081 }
3082 \dolistloop{\@series}%
3083 \@led@extranofeet}
3084 }{%
```

As memoir is not loaded we have to do it all here.

`\@led@testifnofoot`

```
\@doclearpage 3085 \newcommand*{\@led@testifnofoot}{%
3086 \@led@nofoottrue
3087 \ifvoid\footins\else\@led@nofootfalse\fi
3088 \def\do##1{\ifvoid\csuse{##1footins}\else\@led@nofootfalse\fi%
3089 \ifvoid\csuse{footins##1}\else\@led@nofootfalse\fi}%
3090 \dolistloop{\@series}
3091 \@led@extranofeet}
3092
3093 \renewcommand{\@doclearpage}{%
3094 \@led@testifnofoot
3095 \if@led@nofoot
3096 \setbox\@tempboxa\vsplit\@cclv to\z@ \unvbox\@tempboxa
3097 \setbox\@tempboxa\box\@cclv
3098 \xdef\@deferlist{\@toplist\@botlist\@deferlist}%
3099 \global \let \@toplist \@empty
3100 \global \let \@botlist \@empty
3101 \global \@colroom \@colht
3102 \ifx \@currlist \@empty
3103 \else
3104 \@latexerr{Float(s) lost}\@ehb
3105 \global \let \@currlist \@empty
3106 \fi
3107 \@makefcolumn\@deferlist
3108 \@whiles\if@fcolmade \fi{\@opcol\@makefcolumn\@deferlist}%
3109 \if@twocolumn
3110 \if@firstcolumn
3111 \xdef\@dbldeferlist{\@dbltoplist\@dbldeferlist}%
```



```

3112     \global \let \@dbltoplist \@empty
3113     \global \@colht \textheight
3114     \begingroup
3115         \@dblfloatplacement
3116         \@makefcolumn\@dbldeferlist
3117         \@whilesw\if@fcolmade \fi{\@outputpage
3118                                 \@makefcolumn\@dbldeferlist}%
3119     \endgroup
3120     \else
3121         \vbox{}\clearpage
3122     \fi
3123 \fi
3124 \else
3125     \setbox\@cclv\vbox{\box\@cclv\vfil}%
3126     \l@{makecol}\@opcol
3127     \clearpage
3128 \fi}
3129 }
3130

```

33 Cross referencing

Peter Wilson have rewritten portions of the code in this section so that the LaTeX `.aux` file is used. This will also handle `\included` files.

Further, I have renamed some of the original EDMAC macros so that they do not clash with the LaTeX label/ref commands (EDMAC and LaTeX use very different mechanisms). In particular, the original EDMAC `\label` and `\pageref` have been renamed as `\edlabel` and `\edpageref` respectively.

You can mark a place in the text using a command of the form `\edlabel{foo}`, and later refer to it using the label `foo` by saying `\edpageref{foo}`, or `\lineref{foo}` or `\sublineref{foo}`. These reference commands will produce, respectively, the page, line and sub-line on which the `\edlabel{foo}` command occurred.

The reference macros warn you if a reference is made to an undefined label. If `foo` has been used as a label before, the `\edlabel{foo}` command will issue a complaint; subsequent `\edpageref` and `\lineref` commands will refer to the latest occurrence of `\label{foo}`.

`\labelref@list` Set up a new list, `\labelref@list`, to hold the page, line and sub-line numbers for each label.

```

3131 \list@create{\labelref@list}

```

`\zz@@@` A convenience macro to zero two labeling counters in one go.

```

3132 %% \newcommand*{\zz@@@}{000|000|000} % set three counters to zero in one go
3133 \newcommand*{\zz@@@}{000|000} % set two counters to zero in one go
3134

```

`\edlabel` The `\edlabel` command first writes a `\@lab` macro to the `\linenum@out` file. It then checks to see that the `\labelref@list` actually has something in it (if not, it creates a dummy entry), and pops the next value for the current label, storing it in `\label@refs`. Finally it defines the label to be `\empty` so that any future check will turn up the fact that it has been used.²⁸

This version of the original EDMAC `\label` uses `\@bsphack` and `\@esphack` to eliminate extra space problems and also the LaTeX write methods for the `.aux` file.

Jesse Billett²⁹ found that the original code could be off by several pages. This version, hopefully cures that, and also allows for non-arabic page numbering.

```

3135 \newcommand*{\edlabel}[1]{\@bsphack
3136   \write\linenum@out{\string\@lab}%
3137   \ifx\labelref@list\empty
3138     \xdef\label@refs{\zz@@}%
3139   \else
3140     \gl@p\labelref@list\to\label@refs
3141   \ifvmode
3142     \advancelabel@refs
3143   \fi
3144   \fi

```

Use code from the kernel `\label` command to write the correct page number (it seems possible that the original EDMAC's `\page@num` scheme might also have had problems in this area). Also define an `hypertarget` if `hyperref` package is loaded.

```

3145   \protected@write\@auxout{}%
3146     {\string\l@dmake@labels\space\thepage|\label@refs|\the\c@pstart|{#1}}%
3147   \ifdef{\hypertarget}{\hypertarget{#1}}{}%
3148   \@esphack}
3149

```

`\advancelabel@refs` In cases where `\edlabel` is the first element in a paragraph, we have a problem with line counts, because line counts change only at the first horizontal box of the paragraph. Hence, we need to test `\edlabel` if it occurs at the start of a paragraph. To do so, we use `\ifvmode`. If the test is true, we must advance by one unit the amount of text we write into the `.aux` file. We do so using `\advancelabel@refs` command.

```

3150 \newcounter{line}%
3151 \newcounter{subline}%
3152 \newcommand{\advancelabel@refs}{%
3153   \setcounter{line}{\expandafter\labelrefsparseline\label@refs}%
3154   \stepcounter{line}%
3155   \ifsublines%
3156     \setcounter{subline}{\expandafter\labelrefsparsesubline\label@refs}%
3157     \stepcounter{subline}{1}%
3158     \def\label@refs{\theline|\thesubline}%

```

²⁸The remaining macros in this section were kindly revised by Wayne Sullivan, who substantially improved their efficiency and flexibility.

²⁹(jdb43@cam.ac.uk) via the ctt thread 'ledmac cross referencing', 25 August 2003.

```

3159     \else%
3160         \def\label@refs{\theline|0}%
3161     \fi%
3162 }
3163 \def\labelrefsparseline#1|#2{#1}
3164 \def\labelrefsparsesubline#1|#2{#2}

```

\l@make@labels The `\l@make@labels` macro gets executed when the labels file is read. For each label it defines a macro, whose name is made up partly from the label you supplied, that contains the page, line and sub-line numbers. But first it checks to see whether the label has already been used (and complains if it has).

The initial use of `\newcommand` is to catch if `\l@make@labels` has been previously defined (by a class or package).

```

3165 \newcommand*\l@make@labels{}
3166 \def\l@make@labels#1|#2|#3|#4|#5{%
3167     \expandafter\ifx\csname the@label#5\endcsname \relax\else
3168         \led@warn@DuplicateLabel{#5}%
3169     \fi
3170     \expandafter\gdef\csname the@label#5\endcsname{#1|#2|#3|#4}%
3171     \ignorespaces}
3172

```

LaTeX reads the aux file at both the beginning and end of the document, so we have to switch off duplicate label checking after the first time the file is read.

```

3173 \AtBeginDocument{%
3174     \def\l@make@labels#1|#2|#3|#4|#5{%
3175 }
3176

```

\@lab The `\@lab` command, which appears in the `\linenum@out` file, appends the current values of page, line and sub-line to the `\labelref@list`. These values are defined by the earlier `\@page`, `\@nl`, and the `\sub@on` and `\sub@off` commands appearing in the `\linenum@out` file.

LaTeX uses the `page` counter for page numbers. However, it appears that this is not the right place to grab the page number. That task is now done in the `\edlabel` macro. This version of `\@lab` appends just the current line and sub-line numbers to `\labelref@list`.

```

3177 \newcommand*\@lab{\xright@appenditem
3178     {\linenumrep{\line@num}|%
3179         \ifsublines@ \sublinenumrep{\subline@num}\else 0\fi}\to\labelref@list}
3180

```

\wrap@edcrossref `\wrap@edcrossref` is called around all `eledmac` crossref commands, except those which start with `x`. It adds the hyperlink.

```

3181 \newrobustcmd{\wrap@edcrossref}[2]{%
3182     \ifdef{\hyperlink}%
3183         {\hyperlink{#1}{#2}}%
3184     {#2}%
3185 }

```

`\edpageref` If the specified label exists, `\edpageref` gives its page number. For this reference command, as for the other two, a special version with prefix `x` is provided for use in places where the command is to be scanned as a number, as in `\linenum`. These special versions have two limitations: they don't print error messages if the reference is unknown, and they can't appear as the first label or reference command in the file; you must ensure that a `\edlabel` or a normal reference command appears first, or these `x`-commands will always return zeros. LaTeX already defines a `\pageref`, so changing the name to `\edpageref`.

```
3186 \newcommand*{\edpageref}[1]{\l@dref@undefined{#1}\wrap@edcrossref{#1}{\l@dgetref@num{1}{#1}}
3187 \newcommand*{\xpageref}[1]{\l@dgetref@num{1}{#1}}
3188
```

`\lineref` If the specified label exists, `\lineref` gives its line number.

```
\xlineref 3189 \newcommand*{\lineref}[1]{\l@dref@undefined{#1}\wrap@edcrossref{#1}{\l@dgetref@num{2}{#1}}
3190 \newcommand*{\xlineref}[1]{\l@dgetref@num{2}{#1}}
3191
```

`\sublineref` If the specified label exists, `\sublineref` gives its sub-line number.

```
\xsublineref 3192 \newcommand*{\sublineref}[1]{\l@dref@undefined{#1}\wrap@edcrossref{#1}{\l@dgetref@num{3}{#1}}
3193 \newcommand*{\xsublineref}[1]{\l@dgetref@num{3}{#1}}
3194
```

`\pstartref` If the specified label exists, `\pstartref` gives its `pstart` number.

```
\xpstartref 3195 \newcommand*{\pstartref}[1]{\l@dref@undefined{#1}\wrap@edcrossref{#1}{\l@dgetref@num{4}{#1}}
3196 \newcommand*{\xpstartref}[1]{\l@dgetref@num{4}{#1}}
3197
```

The next three macros are used by the referencing commands above, and do the job of extracting the right numbers from the label macro that contains the page, line, and sub-line number.

`\l@dref@undefined` The `\l@dref@undefined` macro is called when you refer to a label with the normal referencing macros. Its argument is a label, and it just checks that the label has been defined.

```
3198 \newcommand*{\l@dref@undefined}[1]{%
3199   \expandafter\ifx\csname the@label#1\endcsname\relax
3200     \led@warn@RefUndefined{#1}%
3201   \fi}
3202
```

`\l@dgetref@num` Next, `\l@dgetref@num` fetches the number we want. It has two arguments: the first is simply a digit, specifying whether to fetch a page (1), line (2) or sub-line (3) number. (This switching is done by calling `\l@dlabel@parse`.) The second argument is the label-macro, which because of the `\@lab` macro above is defined to be a string of the type `123|456|789`.

```
3203 \newcommand*{\l@dgetref@num}[2]{%
3204   \expandafter
```

```

3205 \ifx\csname the@label#2\endcsname \relax
3206     000%
3207 \else
3208     \expandafter\expandafter\expandafter
3209     \l@dlabel@parse\csname the@label#2\endcsname|#1%
3210 \fi}
3211

```

`\l@dlabel@parse` Notice that we slipped another `|` delimiter into the penultimate line of `\l@dgetref@num`, to keep the ‘switch-number’ separate from the reference numbers. This `|` is used as another parameter delimiter by `\l@dlabel@parse`, which extracts the appropriate number from its first arguments. The `|`-delimited arguments consist of the expanded label-macro (three reference numbers), followed by the switch-number (1, 2, or 3) which defines which of the earlier three numbers to pick out. (It was earlier given as the first argument of `\l@dgetref@num`.)

```

3212 \newcommand*{\l@dlabel@parse}{%
3213 \def\l@dlabel@parse#1|#2|#3|#4|#5{%
3214     \ifcase #5%
3215     \or #1%
3216     \or #2%
3217     \or #3%
3218     \or #4%
3219 \fi}

```

`\xxref` The `\xxref` command takes two arguments, both of which are labels, e.g., `\xxref{mouse}{elephant}`. It first does some checking to make sure that the labels do exist (if one doesn’t, those numbers are set to zero). Then it calls `\linenum` and sets the beginning page, line, and sub-line numbers to those of the place where `\label{mouse}` was placed, and the ending numbers to those at `\label{elephant}`. The point of this is to be able to manufacture footnote line references to passages which can’t be specified in the normal way as the first argument to `\critext` for one reason or another. Using `\xxref` in the second argument of `\critext` lets you set things up at least semi-automatically.

```

3220 \newcommand*{\xxref}[2]{%
3221     {%
3222     \expandafter\ifx\csname the@label#1\endcsname \relax%
3223     \expandafter\let\csname the@@label#1\endcsname\zz@@@%
3224     \else%
3225     \expandafter\def\csname the@@label#1\endcsname{\l@dgetref@num{1}{#1}|\l@dgetref@num{2}{#1}|\l@d
3226     \fi%
3227     \expandafter\ifx\csname the@label#2\endcsname \relax%
3228     \expandafter\let\csname the@@label#2\endcsname\zz@@@%
3229     \else%
3230     \expandafter\def\csname the@@label#2\endcsname{\l@dgetref@num{1}{#2}|\l@dgetref@num{2}{#2}|\l@d
3231     \fi%
3232     \linenum{\csname the@@label#1\endcsname|%
3233     \csname the@@label#2\endcsname}}%
3234

```

`\edmakelabel` Sometimes the `\edlabel` command cannot be used to specify exactly the page and line desired; you can use the `\edmakelabel` macro make your own label. For example, if you say `'\edmakelabel{elephant}{10|25|0}'` you will have created a new label, and a later call to `\edpageref{elephant}` would print '10' and `\lineref{elephant}` would print '25'. The sub-line number here is zero. `\edmakelabel` takes a label, followed by a page and a line number(s) as arguments. LaTeX defines a `\makelabel` macro which is used in lists. I've changed the name to `\edmakelabel`.

```
3235 \newcommand*{\edmakelabel}[2]{\expandafter\xdef\csname the@label#1\endcsname{#2}}
3236
```

(If you are only going to refer to such a label using `\xxref`, then you can omit entries in the same way as with `\linenum` (see pp. 82 and 61), since `\xxref` makes a call to `\linenum` in order to do its work.)

34 Side notes

Regular `\marginpars` do not work inside numbered text — they don't produce any note but do put an extra unnumbered blank line into the text.

`\l@dold@xympar` Changing `\@xympar` a little at least ensures that `\marginpars` in numbered text
`\@xympar` do not disturb the flow.

```
3237 \let\l@dold@xympar\@xympar
3238 \renewcommand{\@xympar}{%
3239   \ifnumberedpar@
3240     \led@warn@NoMarginpars
3241     \esphack
3242   \else
3243     \l@dold@xympar
3244   \fi}
3245
```

We provide side notes as replacement for `\marginpar` in numbered text.

`\sidenote@margin` These are the sidenote equivalents to `\line@margin` and `\linenummargin` for
`\sidenotemargin` specifying which margin. The default is the right margin (opposite to the default
`\l@dgetsidenote@margin` for line numbers). `\l@dgetsidenote@margin` returns the number associated to
side note margin:

left : 0

right : 1

outer : 2

inner : 3

```

3246 \newcount\sidenote@margin
3247 \newcommand*{\sidenotemargin}[1]{\%
3248   \l@getssidenote@margin{#1}%
3249   \ifnum\l@dttempcntb>\m@ne
3250     \ifledRcol
3251       \global\sidenote@marginR=\l@dttempcntb
3252     \else
3253       \global\sidenote@margin=\l@dttempcntb
3254     \fi
3255   \fi}}
3256 \newcommand*{\l@getssidenote@margin}[1]{\%
3257   \def\@tempa{#1}\def\@tempb{left}%
3258   \ifx\@tempa\@tempb
3259     \l@dttempcntb \z@
3260   \else
3261     \def\@tempb{right}%
3262     \ifx\@tempa\@tempb
3263       \l@dttempcntb \@ne
3264     \else
3265       \def\@tempb{outer}%
3266       \ifx\@tempa\@tempb
3267         \l@dttempcntb \tw@
3268       \else
3269         \def\@tempb{inner}%
3270         \ifx\@tempa\@tempb
3271           \l@dttempcntb \thr@@
3272         \else
3273           \led@warn@BadSidenotemargin
3274           \l@dttempcntb \m@ne
3275         \fi
3276       \fi
3277     \fi
3278   \fi}
3279 \sidenotemargin{right}
3280

```

\l@dlp@rbox We need two boxes to store sidenote texts.

```

\l@drp@rbox 3281 \newbox\l@dlp@rbox
3282 \newbox\l@drp@rbox
3283

```

\ledlsnotewidth These specify the width of the left/right boxes (initialised to \marginparwidth,
\ledrsnotewidth their distance from the text (initialised to \linenumsep, and the fonts used.

```

\ledlsnotesep 3284 \newdimen\ledlsnotewidth \ledlsnotewidth=\marginparwidth
\ledrsnotesep 3285 \newdimen\ledrsnotewidth \ledrsnotewidth=\marginparwidth
\ledlsnotefontsetup 3286 \newdimen\ledlsnotesep \ledlsnotesep=\linenumsep
\ledrsnotefontsetup 3287 \newdimen\ledrsnotesep \ledrsnotesep=\linenumsep
3288 \newcommand*{\ledlsnotefontsetup}{\raggedleft\footnotesize}
3289 \newcommand*{\ledrsnotefontsetup}{\raggedright\footnotesize}
3290

```

`\ledleftnote` `\ledleftnote`, `\ledrightnote`, `\ledinnernote`, `\ledouternote` are the user commands for left, right, inner and outer sidenotes. The two last one are just alias for the two first one, depending of the page number. `\ledsidenote{<text>}` `\ledouterote` is the command for a moveable sidenote.

```

\ledsidenote 3291 \newcommand*{\ledleftnote}[1]{\edtext{}\l@dlsnote{#1}}
              3292 \newcommand*{\ledrightnote}[1]{\edtext{}\l@drsnote{#1}}
              3293
              3294 \newcommand*{\ledinnernote}[1]{%
              3295   \ifodd\c@page% Do not use \page@num, because it is not yet calculated when command is called
              3296     \ledleftnote{#1}%
              3297   \else%
              3298     \ledrightnote{#1}%
              3299   \fi%
              3300 }
              3301
              3302 \newcommand*{\ledouternote}[1]{%
              3303   \ifodd\c@page% Do not use \page@num, because it is not yet calculated when command is called
              3304     \ledrightnote{#1}%
              3305   \else%
              3306     \ledleftnote{#1}%
              3307   \fi%
              3308 }
              3309
              3310 \newcommand*{\ledsidenote}[1]{\edtext{}\l@dcsnote{#1}}

```

`\l@dlsnote` . The ‘footnotes’ for left, right, and moveable sidenotes. The whole scheme is reminiscent of the critical footnotes code.

```

\l@dcsnote 3311 \newif\ifrightnoteup
              3312   \rightnoteuptrue
              3313
              3314 \newcommand*{\l@dlsnote}[1]{%
              3315   \begingroup%
              3316   \newcommand{\content}{#1}%
              3317   \ifnumberedpar@
              3318     \ifledRcol%
              3319       \xright@appenditem{\noexpand\l@dlsnote{\csexpandonce{content}}}%
              3320         \to\inserts@listR
              3321       \global\advance\insert@countR \@ne%
              3322     \else%
              3323       \xright@appenditem{\noexpand\l@dlsnote{\csexpandonce{content}}}%
              3324         \to\inserts@list
              3325       \global\advance\insert@count \@ne%
              3326     \fi
              3327   \fi\ignorespaces\endgroup}
              3328
              3329 \newcommand*{\l@drsnote}[1]{%
              3330   \begingroup%
              3331   \newcommand{\content}{#1}%
              3332   \ifnumberedpar@

```



```

3333 \ifledRcol%
3334 \xright@appenditem{\noexpand\vl@drsnote{\csexpandonce{content}}}%
3335 \to\inserts@listR
3336 \global\advance\insert@countR \@ne%
3337 \else%
3338 \xright@appenditem{\noexpand\vl@drsnote{\csexpandonce{content}}}%
3339 \to\inserts@list
3340 \global\advance\insert@count \@ne%
3341 \fi
3342 \fi\ignorespaces\endgroup}
3343
3344 \newcommand*{\l@dcnote}[1]{%
3345 \begingroup%
3346 \newcommand{\content}{#1}%
3347 \ifnumberedpar@
3348 \ifledRcol%
3349 \xright@appenditem{\noexpand\vl@dcnote{\csexpandonce{content}}}%
3350 \to\inserts@listR
3351 \global\advance\insert@countR \@ne%
3352 \else%
3353 \xright@appenditem{\noexpand\vl@dcnote{\csexpandonce{content}}}%
3354 \to\inserts@list
3355 \global\advance\insert@count \@ne%
3356 \fi
3357 \fi\ignorespaces\endgroup}
3358

```

`\vl@dlsnote` Put the left/right text into boxes, but just save the moveable text. `\l@dcnotetext`, `\vl@drsnote` `\l@dcnotetext@l` and `\l@dcnotetext@r` are etoolbox lists which will store the content of side notes. We store the content in lists, because we need to loop later on them, in case many sidenote co-exist for the same line. That is there some special test to do, in order to:

- Store the content of `\ledsidenote` to `\l@dcnotetext` in any cases.
- Store the content of `\rightsidenote` to:
 - `\l@dcnotetext` if `\ledsidenote` is to be put on right.
 - `\l@dcnotetext@r` if `\ledsidenote` is to be put on left.
- Store the content of `\leftsidenote` to:
 - `\l@dcnotetext` if `\ledsidenote` is to be put on left.
 - `\l@dcnotetext@l` if `\ledsidenote` is to be put on right.

```

3359 \newcommand*{\vl@dlsnote}[1]{%
3360 \ifledRcol@%
3361 \@l@tempcntb=\sidenote@marginR%
3362 \ifnum\@l@tempcntb>\@ne%
3363 \advance\@l@tempcntb by\page@numR%

```

```

3364 \fi%
3365 \else%
3366 \l@dttempcntb=\sidenote@margin%
3367 \ifnum\l@dttempcntb>\@ne%
3368 \advance\l@dttempcntb by\page@num%
3369 \fi%
3370 \fi%
3371 \ifodd\l@dttempcntb%
3372 \listgadd{\l@dcstotetext@l}{#1}%
3373 \else%
3374 \listgadd{\l@dcstotetext}{#1}%
3375 \fi
3376 }
3377 \newcommand*{\vl@drsnote}[1]{%
3378 \ifledRcol@%
3379 \l@dttempcntb=\sidenote@marginR%
3380 \ifnum\l@dttempcntb>\@ne%
3381 \advance\l@dttempcntb by\page@numR%
3382 \fi%
3383 \else%
3384 \l@dttempcntb=\sidenote@margin%
3385 \ifnum\l@dttempcntb>\@ne%
3386 \advance\l@dttempcntb by\page@num%
3387 \fi%
3388 \fi%
3389 \ifodd\l@dttempcntb%
3390 \listgadd{\l@dcstotetext}{#1}%
3391 \else%
3392 \listgadd{\l@dcstotetext@r}{#1}%
3393 \fi%
3394 }
3395 \newcommand*{\vl@dcstote}[1]{\listgadd{\l@dcstotetext}{#1}}
3396

```

`\setl@dlp@rbox` `\setl@dlprbox{<lednums>}{<tag>}{<text>}` puts `<text>` into the `\l@dlp@rbox` box.
`\setl@drpr@rbox` And similarly for the right side box. It is these boxes that finally get displayed in the margins.

```

3397 \newcommand*{\setl@dlp@rbox}[1]{%
3398 {\parindent\z@\hspace=\ledlsnotewidth\ledlsnotefontsetup
3399 \global\setbox\l@dlp@rbox
3400 \ifleftnoteup
3401 =\vbox to\z@{\vss #1}%
3402 \else
3403 =\vbox to 0.70\baselineskip{\strut#1\vss}%
3404 \fi}}
3405 \newcommand*{\setl@drp@rbox}[1]{%
3406 {\parindent\z@\hspace=\ledrsnotewidth\ledrsnotefontsetup
3407 \global\setbox\l@drp@rbox
3408 \ifrightnoteup
3409 =\vbox to\z@{\vss#1}%

```

```

3410 \else
3411     =\vbox to0.7\baselineskip{\strut#1\vss}%
3412 \fi}}
3413 \newif\ifleftnoteup
3414 \leftnoteuptrue

```

`\sidenotessep` This macro is used to separate sidenotes of the same line.

```

3415 \newcommand{\sidenotessep}{, }
3416 % \end{macrocode}
3417 % \end{macro}
3418 % \begin{macro}{\affixside@note}
3419 % This macro puts any moveable sidenote text into the left or right sidenote
3420 % box, depending on which margin it is meant to go in. It's a very much
3421 % stripped down version of \cs{affixlin@num}.
3422 %
3423 % Before do it, we concatenate all moveable sidenotes of the line, using \cs{sidenotessep} as separator
3424 % It's the result that we put on the sidenote.
3425 % \changes{v1.4.1}{2012/11/16}{Remove spurious spaces.}
3426 % \begin{macrocode}
3427 \newcommand*{\affixside@note}{%
3428     \def\sidenotecontent@{}%
3429     \numgdef\itemcount@{0}%
3430     \def\do##1{%
3431         \ifnumequal{\itemcount@}{0}%
3432             {%
3433                 \appto\sidenotecontent@{##1}}% Not print not separator before the 1st note
3434             {\appto\sidenotecontent@{\sidenotessep ##1}}%
3435             {%
3436                 \numgdef\itemcount@{\itemcount@+1}%
3437             }%
3438     \dolistloop{\l@dcnotesetext}%
3439     \ifnumgreater{\itemcount@}{1}{\led@err@ManySidenotes}{}%

```

And we do the same for left and right notes (not movable).

```

3440 \gdef\@templ@d{}%
3441 \gdef\@templ@n{\l@dcnotesetext\l@dcnotesetextl\l@dcnotesetext@r}%
3442 \ifx\@templ@d\@templ@n \else%
3443     \if@twocolumn%
3444         \if@firstcolumn%
3445             \setl@dlp@rbox{##1}{\sidenotecontent@}%
3446         \else%
3447             \setl@drp@rbox{\sidenotecontent@}%
3448         \fi%
3449     \else%
3450         \@l@tempcntb=\sidenote@margin%
3451         \ifnum\@l@tempcntb>\@ne%
3452             \advance\@l@tempcntb by\page@num%
3453         \fi%
3454         \ifodd\@l@tempcntb%
3455             \setl@drp@rbox{\sidenotecontent@}%

```

```

3456      \gdef\sidenotecontent@{}%
3457      \numgdef\itemcount@{0}%
3458      \dolistloop{\l@dcstetext@l}%
3459      \ifnumgreater\itemcount@{1}{\led@err@ManyLeftnotes}{}%
3460      \setl@dlp@rbox{\sidenotecontent@}%
3461      \else%
3462      \setl@dlp@rbox{\sidenotecontent@}%
3463      \gdef\sidenotecontent@{}%
3464      \numgdef\itemcount@{0}%
3465      \dolistloop{\l@dcstetext@r}%
3466      \ifnumgreater\itemcount@{1}{\led@err@ManyRightnotes}{}%
3467      \setl@drp@rbox{\sidenotecontent@}%
3468      \fi%
3469      \fi%
3470      \fi%
3471 }

```

35 Minipages and such

We can put footnotes into minipages. The preparatory code has been set up earlier, all that remains is to ensure that it is available inside a minipage box. This requires some alteration to the kernel code, specifically the `\@iiiminipage` and `\endminipage` macros. We'll arrange this so that additional series can be easily added.

```

\l@dfetbeginmini These will be the hooks in \@iiiminipage and \endminipage They can be extended
\l@dfetendmini   to handle other things if necessary.

3472 \newcommand*\l@dfetbeginmini{\l@dedbeginmini\l@dfambeginmini}
3473 \newcommand*\l@dfetendmini{%
3474     \IfStrEq{critical-familiar}{\@mpfnpos}%
3475     {\l@dedendmini\l@dfamendmini}%
3476     {%
3477         \IfStrEq{familiar-critical}{\@mpfnpos}%
3478         {\l@dfamendmini\l@dedendmini}%
3479         {\l@dedendmini\l@dfamendmini}%
3480     }%
3481 }%

\l@dedbeginmini These handle the initiation and closure of critical footnotes in a minipage envi-
\l@dedendmini   ronment.

3482 \newcommand*\l@dedbeginmini{%
3483     \def\do##1{\csletcs{v##1footnote}{mpv##1footnote}}%
3484     \dolistloop{\@series}%
3485 }
3486 \newcommand*\l@dedendmini{%
3487     \ifl@dpairing
3488     \ifledRcol
3489     \flush@notesR

```

```

3490 \else
3491 \flush@notes
3492 \fi
3493 \fi
3494 \def\do##1{
3495 \ifvoid\csuse{mp##1footins}\else%
3496 \ifl@dpairing\ifparledgroup%
3497 \ifledRcol%
3498 \dimgdef{\parledgroup@beforenotesR}{\parledgroup@beforenotesR+\skip\@nameuse{mp##1footins}}
3499 \else%
3500 \dimgdef{\parledgroup@beforenotesL}{\parledgroup@beforenotesL+\skip\@nameuse{mp##1footins}}
3501 \fi%
3502 \fi\fi%
3503 \csuse{mp##1footgroup}{##1}%
3504 \fi}%
3505 \dolistloop{\@series}%
3506 }
3507

```

`\l@dfambeginmini` These handle the initiation and closure of familiar footnotes in a minipage environment.
`\l@dfamendmini`

```

3508 \newcommand*{\l@dfambeginmini}{%
3509 \def\do##1{\csletcs{vfootnote##1}{mpvfootnote##1}}%
3510 \dolistloop{\@series}}
3511 \newcommand*{\l@dfamendmini}{%
3512 \def\do##1{\ifvoid\csuse{mpfootins##1}\else\csuse{mpfootgroup##1}{##1}\fi}%
3513 \dolistloop{\@series}}

```

`\@iiiminipage` This is our extended form of the kernel `\@iiiminipage` defined in `ltboxes.dtx`.

```

3514 \def\@iiiminipage#1#2[#3]#4{%
3515 \leavevmode
3516 \@pboxswfalse
3517 \setlength\@tempdima{#4}%
3518 \def\@mpargs{{#1}{#2}[#3]{#4}}%
3519 \setbox\@tempboxa\vbox\bgroup
3520 \color@begingroup
3521 \hsize\@tempdima
3522 \textwidth\hsize \columnwidth\hsize
3523 \@parboxrestore
3524 \def\@mpfn{mpfootnote}\def\thempfn{\thempfootnote}\c@mpfootnote\z@
3525 \let\@footnotetext\@mpfootnotetext

```

The next line is our addition to the original.

```

3526 \l@dfetbeginmini% added
3527 \let\@listdepth\@mplistdepth \@mplistdepth\z@
3528 \@minipagerestore
3529 \@setminipage}
3530

```

`\endminipage` This is our extended form of the kernel `\endminipage` defined in `ltboxes.dtx`.

```

3531 \def\endminipage{%
3532   \par
3533   \unskip
3534   \ifvoid\@mpfootins\else
3535     \l@dunboxmpfoot
3536   \fi

```

The next line is our addition to the original.

```

3537   \l@dfeetendmini%          added
3538   \@minipagefalse
3539   \color@endgroup
3540   \egroup
3541   \expandafter\@iiparbox\@mpargs{\unvbox\@tempboxa}}
3542

```

`\l@dunboxmpfoot`

```

3543 \newcommand*{\l@dunboxmpfoot}{%
3544   \vskip\skip\@mpfootins
3545   \normalcolor
3546   \footnoterule
3547   \ifparledgroup
3548     \ifl@dpairing
3549       \ifledRcol
3550         \dimgdef{\parledgroup@beforenotesR}{\parledgroup@beforenotesR+\skip\@mpfootins}
3551       \else
3552         \dimgdef{\parledgroup@beforenotesL}{\parledgroup@beforenotesL+\skip\@mpfootins}
3553       \fi
3554     \fi
3555   \fi
3556   \unvbox\@mpfootins}
3557

```

`ledgroup` This environment puts footnotes at the end, even if that happens to be in the middle of a page, or crossing a page boundary. It is a sort of unboxed, fixed width minipage.

```

3558 \newif\if@ledgroup
3559 \newenvironment{ledgroup}{%
3560   \resetprevpage@num\@ledgrouptrue\def\@mpfn{mpfootnote}\def\thempfn{\thempfootnote}\c@mpfn
3561   \let\@footnotetext\@mpfootnotetext
3562   \l@dfeetbeginmini%
3563 }{%
3564   \par
3565   \unskip
3566   \ifvoid\@mpfootins\else
3567     \l@dunboxmpfoot
3568   \fi
3569   \l@dfeetendmini%
3570   \@ledgroupfalse%
3571 }

```

3572

`ledgroupsize` `\begin{ledgroupsize}[\langle pos \rangle][\langle width \rangle]`

This environment puts footnotes at the end, even if that happens to be in the middle of a page, or crossing a page boundary. It is a sort of unboxed, variable $\langle width \rangle$ minipage. The optional $\langle pos \rangle$ controls the sideways position of numbered text.

3573 `\newenvironment{ledgroupsize}[2][1]{%`

Set the various text measures.

3574 `\hsize #2\relax`

3575 `%% \textwidth #2\relax`

3576 `%% \columnwidth #2\relax`

Initialize fills for centering.

3577 `\let\ledllfill\hfil`

3578 `\let\ledrlfill\hfil`

3579 `\def\@tempa{#1}\def\@tempb{1}%`

Left adjusted numbered lines

3580 `\ifx\@tempa\@tempb`

3581 `\let\ledllfill\relax`

3582 `\else`

3583 `\def\@tempb{r}%`

3584 `\ifx\@tempa\@tempb`

Right adjusted numbered lines

3585 `\let\ledrlfill\relax`

3586 `\fi`

3587 `\fi`

Set up the footnoting.

3588 `\@ledgrouptrue%`

3589 `\def\@mpfn{mpfootnote}\def\thempfn{\thempfootnote}\c@mpfootnote\z@`

3590 `\let\@footnotetext\@mpfootnotetext`

3591 `\l@dfetbeginmini%`

3592 `\fi%`

3593 `\par`

3594 `\unskip`

3595 `\ifvoid\@mpfootins\else`

3596 `\l@dunboxmpfoot`

3597 `\fi`

3598 `\l@dfetendmini%`

3599 `\@ledgroupfalse%`

3600 `}`

3601

`\ifledgroupnotesL@` These boolean tests check if we are in the notes of a ledgroup. If we are, we don't
`\ifledgroupnotesR@` number the lines.

3602 `\newif\ifledgroupnotesL@`

3603 `\newif\ifledgroupnotesR@`

36 Indexing

Here's some code for indexing using page & line numbers.

```
\ifeledmac@check@imakeidx@ First, ensure that imakeidx is loaded before eledmac.
3604 \newif\ifeledmac@after@imakeidx@
3605 \@ifpackageloaded{imakeidx}{\eledmac@after@imakeidx@true}{%
3606 \AtBeginDocument{%
3607   \ifeledmac@after@imakeidx@else%
3608     \@ifpackageloaded{imakeidx}{\led@error@ImakeidxAfterEledmac}{}%
3609   \fi
3610 }

\pagelinesep In order to get a correct line number we have to use the label/ref mechanism.
\edindexlab These macros are for that.
\c@labidx 3611 \newcommand{\pagelinesep}{-}
3612 \newcommand{\edindexlab}{\&}
3613 \newcounter{labidx}
3614 \setcounter{labidx}{0}
3615

\doedindexlabel This macro sets an \edlabel.
3616 \newcommand{\doedindexlabel}{\stepcounter{labidx}%
3617   \edlabel{\edindexlab\thelabidx}}
3618

\thepageline This macro makes up the page/line number combo from the label/ref.
3619 \newcommand{\thepageline}{%
3620   \thepage\pagelinesep\xlineref{\edindexlab\thelabidx}}

\thestartpageline These macros make up the page/line start/end number when the \edindex com-
\theendpageline mand is called in critical notes.
3621 \newcommand{\thestartpageline}{\l@dparsedstartpage\pagelinesep\l@dparsedstartline}
3622 \newcommand{\theendpageline}{\l@dparsedendpage\pagelinesep\l@dparsedendline}

\if@edindex@fornote@true This boolean test is switching at the beginning of each critical note, to allow
indexing in this note.
3623 \newif\if@edindex@fornote@

\prepare@edindex@fornote This macro is called at the beginning of each critical note. It switches some
parameters, to allow indexing in this note, with reference to page and line number.
3624 \newcommand{\prepare@edindex@fornote}[1]{%
3625   \l@dp@rsefootspec#1}%
3626   \@edindex@fornote@true
3627 }

\get@index@command This macro is used to analyse if a text to be indexed has a command after a |.
3628 \def\get@index@command#1|#2+{%
```



```

3629 \gdef\@index@txt{#1}%
3630 \gdef\@index@command{#2}%
3631 \xdef\@index@parenthesis{}%
3632 \IfBeginWith{\@index@command}{(}{%
3633   \StrGobbleLeft{\@index@command}{1}{\@index@command@}%
3634   \global\let\@index@command\@index@command@%
3635   \xdef\@index@parenthesis{(%}%
3636   }{}%
3637 \IfBeginWith{\@index@command}{)}{%
3638   \StrGobbleLeft{\@index@command}{1}{\@index@command@}%
3639   \global\let\@index@command\@index@command@%
3640   \xdef\@index@parenthesis{)%}%
3641   }{}%
3642 }

```

`\ledinnote` These macros are used to specify that an index reference points to a note.

```

\ledinnotehyperpage 3643 \newcommand{\ledinnote}[2]{\csuse{#1}{#2\emph{n}}}
3644 \newcommand{\ledinnotehyperpage}[2]{\csuse{#1}{\hyperpage{#2}\emph{n}}}

```

The memoir class provides more flexible indexing than the standard classes. We need different code if the memoir class is being used, except if imakeidx is used.

`\edindex` 36.1 Memoir compatibility

`\create@edindex@for@memoir` `\create@edindex@for@memoir` define the `\edindex` command and related tool when:

1. Memoir class is used.
2. AND imakeidx is not used.

Need to add the definition of `\edindex` to `\makeindex`, and initialise `\edindex` to do nothing. In this case `\edindex` has an optional argument. We use the hook provided in memoir v1.61.

```

3645 \def\create@edindex@for@memoir{
3646   \g@addto@macro{\makememindexhook}{%
3647     \def\edindex{\@bsphack%
3648       \@ifnextchar [{\l@d@index}{\l@d@index[\jobname]}}%
3649     \newcommand{\edindex}[2][\jobname]{\@bsphack\@esphack}

```

`\l@d@index` `\l@d@index[file]` is the first stage of `\edindex`, handling the `idx` file. This is a virtually a verbatim copy of memoir's `\@index`, the change being calling `\l@dwrindexm@m` instead of `\@wrindexm@m`.

```

3650 \def\l@d@index[##1]{%
3651   \@ifundefined{##1idxfile}%
3652   {\ifreportnoidxfile
3653     \led@warn@NoIndexFile{##1}%
3654     \fi

```

```

3655 \begingroup
3656 \@sanitize
3657 \@nowrindex}%
3658 {\def\@idxfile{##1}%
3659 \doedindexlabel
3660 \begingroup
3661 \@sanitize
3662 \l@d@wrindexm@m}}

```

`\l@d@wrindexm@m` `\l@d@wrindexm@m{item}` writes the idx file name and the indexed item to the aux file. These are almost verbatim copies of memoir's `\@wrindexm@m` and `\@wrindexhyp`.

```

3663 \newcommand{\l@d@wrindexm@m}[1]{\l@d@wrindexhyp##1||\}
3664 \def\l@d@wrindexhyp##1|##2|##3\{%
3665 \ifshowindexmark\@showidx{##1}\fi
3666 \ifx\##2\%
3667 \if@edindex@fornote%
3668 \protected@write\@auxout{%
3669 {\string\@wrindexm@m{\@idxfile}{##1}(\ledinnotehyperpage){\thestartpageline}}%
3670 \protected@write\@auxout{%
3671 {\string\@wrindexm@m{\@idxfile}{##1})ledinnotehyperpage}{\theendpageline}}%
3672 \else%
3673 \protected@write\@auxout{%
3674 {\string\@wrindexm@m{\@idxfile}{##1}hyperpage}{\thepageline}}%
3675 \fi%
3676 \else
3677 \def\Hy@temp@A{##2}%
3678 \ifx\Hy@temp@A\HyInd@ParenLeft
3679 \if@edindex@fornote%
3680 \protected@write\@auxout{%
3681 {\string\@wrindexm@m{\@idxfile}{##1}(\ledinnotehyperpage{##2}){\thestartpageline}}%
3682 \protected@write\@auxout{%
3683 {\string\@wrindexm@m{\@idxfile}{##1})ledinnotehyperpage{##2}}{\theendpageline}}%
3684 \else%
3685 \protected@write\@auxout{%
3686 {\string\@wrindexm@m{\@idxfile}{##1|##2hyperpage}{\thepageline}}%
3687 \fi%
3688 \else
3689 \if@edindex@fornote%
3690 \protected@write\@auxout{%
3691 {\string\@wrindexm@m{\@idxfile}{##1}(\ledinnote{##2}){\thestartpageline}}%
3692 \protected@write\@auxout{%
3693 {\string\@wrindexm@m{\@idxfile}{##1})ledinnote{##2}}{\theendpageline}}%
3694 \else%
3695 \protected@write\@auxout{%
3696 {\string\@wrindexm@m{\@idxfile}{##1|##2}{\thepageline}}%
3697 \fi%
3698 \fi
3699 \fi
3700 \endgroup

```

```
3701 \esphack}
```

That finishes the memoir-specific code.

```
3702 }
```

36.2 Normal setting

ate@edindex@notfor@memoir \create@edindex@notfor@memoir define the \edindex command and related tool when:

1. Memoir class is NOT used.
2. OR imakeidx is used.

```
3703 \def\create@edindex@notfor@memoir{
```

\@wredindex Write the index information to the idx file.

```
3704 \newcommandx{\@wredindex}[2][1=\expandonce\jobname,usedefault]{%#1 = the index name, #2 = the text
3705 \global\let\old@Rlineflag\Rlineflag%
3706 \gdef\Rlineflag{}%
3707 \ifl@imakeidx%
3708 \if@edindex@fornote%
3709 \IfSubStr[1]{##2}{|}{\get@index@command##2+}{\get@index@command##2|+}%
3710 \expandafter\imki@wrindexentry{##1}{\@index@txt|(ledinnote{\@index@command})}{\thestartpageline}
3711 \expandafter\imki@wrindexentry{##1}{\@index@txt|)ledinnote{\@index@command}}{\theendpageline}
3712 \else%
3713 \get@edindex@hyperref{##2}%
3714 \imki@wrindexentry{##1}{\@index@txt\@edindex@hyperref}{\thepageline}%
3715 \fi%
3716 \else%
3717 \if@edindex@fornote%
3718 \IfSubStr[1]{##2}{|}{\get@index@command##2+}{\get@index@command##2|+}%
3719 \expandafter\protected@write\@indexfile{}%
3720 {\string\indexentry{\@index@txt|(ledinnote{\@index@command})}{\thestartpageline}
3721 }%
3722 \expandafter\protected@write\@indexfile{}%
3723 {\string\indexentry{\@index@txt|)ledinnote{\@index@command}}{\theendpageline}
3724 }%
3725 \else%
3726 \protected@write\@indexfile{}%
3727 {\string\indexentry{##2}{\thepageline}
3728 }%
3729 \fi%
3730 \fi%
3731 \endgroup
3732 \global\let\Rlineflag\old@Rlineflag%
3733 \esphack}
```

Need to add the definition of \edindex to \makeindex, and initialise \edindex to do nothing.

```

3734 \pretocmd{\makeindex}{%
3735   \def\edindex{\@bsphack
3736     \doedindexlabel
3737     \begingroup
3738     \@sanitize
3739     \@wredindex}}{}{}
3740 \newcommand{\edindex}[1]{\@bsphack\@esphack}
3741 % That finishes the non-\Lpack{memoir} index code.
3742 }

```

36.3 Choose the good variant

And now, call `\create@edindex@for@memoir` or `\create@edindex@notfor@memoir` depending of the use of memoir and imakeidx

```

3743 \@ifclassloaded{memoir}{%
3744   \@ifpackageloaded{imakeidx}%
3745     {\create@edindex@notfor@memoir}{\create@edindex@for@memoir}%
3746   }%
3747   {\create@edindex@notfor@memoir}%

```

36.4 Hyperref compatibility

`\hyperlinkformat` `\hyperlinkformat` command is to be used to have both a internal hyperlink and a format, when indexing.

```

3748 \newcommand{\hyperlinkformat}[3]{%
3749   \ifstrepty{#1}%
3750     {\hyperlink{#2}{#3}}%
3751     {\csuse{#1}{\hyperlink{#2}{#3}}}%
3752   }%

```

`\hyperlinkR` `\hyperlinkR` command is to be used to create a internal hyperlink and `\ledRflag`, when indexing.

```

3753 \newcommand{\hyperlinkR}[2]{%
3754   \hyperlink{#1}{#2\Rlineflag}%
3755 }%
3756

```

`\hyperlinkformatR` `\hyperlinkformatR` command is to be used to create a internal hyperlink, a format and a `\Rlineflag`, when indexing.

```

3757 \newcommand{\hyperlinkformatR}[3]{%
3758   \hyperlinkformat{#1}{#2}{#3\Rlineflag}%
3759 }%
3760

```

`\get@edindex@hyperref` `\get@edindex@hyperref` is to be used to define the `\@edindex@hyperref` macro, which, in index, links to the point where the index was called (with `hyperref`).

```

3761 \newcommand{\get@edindex@hyperref}[1]{%
3762   \ifdef{\hyperlink}%

```

We have to disable spaces to work with a xstring bug

```

3763   {%
3764   \edef\temp@{%
3765   \catcode'\ =9 %space need for catcode
3766   #1%
3767   \catcode'\ =10 % space need for catcode
3768   }%
3769   \IfSubStr{\temp@}{|}%
3770   {\get@index@command#1+%
3771   \ifledRcol%
3772   \gdef\@edindex@hyperref{|\@index@parenthesis %space kept
3773   hyperlinkformatR{\@index@command}%
3774   {\edindexlab\thelabidx}}%
3775   \else%
3776   \gdef\@edindex@hyperref{|\@index@parenthesis %space kept
3777   hyperlinkformat{\@index@command}%
3778   {\edindexlab\thelabidx}}%
3779   \fi%
3780   }%
3781   {\get@index@command#1|+
3782   \ifledRcol%
3783   \gdef\@edindex@hyperref{|hyperlinkR{\edindexlab\thelabidx}}%
3784   \else%
3785   \gdef\@edindex@hyperref{|hyperlink{\edindexlab\thelabidx}}%
3786   \fi%
3787   }%
3788   }%
3789   {%
3790   \gdef\@index@txt{#1}%
3791   \gdef\@edindex@hyperref{}%
3792 }

```

37 Macro as environment

The following is borrowed, and renamed, from the `amsmath` package. See also the CTT thread ‘`eeq` and `amstex`’, 1995/08/31, started by Keith Reckdahl and ended definitively by David M. Jones.

Several of the `[math]` macros scan their body twice. This means we must collect all text in the body of an environment form before calling the macro.

`\@emptytoks` This is actually defined in the `amsgen` package.

```

3793 \newtoks\@emptytoks
3794

```

The rest is from `amsmath`.

`\l@denbody` A token register to contain the body.

```
3795 \newtoks\l@denbody
3796
```

`\addtol@denbody` `\addtol@denbody{arg}` adds `arg` to the token register `\l@denbody`.

```
3797 \newcommand{\addtol@denbody}[1]{%
3798   \global\l@denbody\expandafter{\the\l@denbody#1}}
3799
```

`\l@dcollect@body` The macro `\l@dcollect@body` starts the scan for the `\end{...}` command of the current environment. It takes a macro name as argument. This macro is supposed to take the whole body of the environment as its argument. For example, given `cenv#1{...}` as a macro that processes `#1`, then the environment form, `\begin{env}` would call `\l@dcollect@body\cenv`.

```
3800 \newcommand{\l@dcollect@body}[1]{%
3801   \l@denbody{\expandafter#1\expandafter{\the\l@denbody}}%
3802   \edef\processl@denbody{\the\l@denbody\noexpand\end{\@currentenv}}%
3803   \l@denbody\@emptytoks \def\l@dbegin@stack{b}%
3804   \begingroup
3805     \expandafter\let\csname\@currentenv\endcsname\l@dcollect@@body
3806     \edef\processl@denbody{\expandafter\noexpand\csname\@currentenv\endcsname}%
3807     \processl@denbody%
3808   }%
3809
```

`\l@dpush@begins` When adding a piece of the current environment's contents to `\l@denbody`, we scan it to check for additional `\begin` tokens, and add a 'b' to the stack for any that we find.

```
3810 \def\l@dpush@begins#1\begin#2{%
3811   \ifx\end#2\else b\expandafter\l@dpush@begins\fi}
3812
```

`\l@dcollect@@body` `\l@dcollect@@body` takes two arguments: the first will consist of all text up to the next `\end` command, and the second will be the `\end` command's argument. If there are any extra `\begin` commands in the body text, a marker is pushed onto a stack by the `\l@dpush@begins` function. Empty state for this stack means we have reached the `\end` that matches our original `\begin`. Otherwise we need to include the `\end` and its argument in the material we are adding to the environment body accumulator.

```
3813 \def\l@dcollect@@body#1\end#2{%
3814   \edef\l@dbegin@stack{\l@dpush@begins#1\begin\end
3815     \expandafter\@gobble\l@dbegin@stack}%
3816   \ifx\@empty\l@dbegin@stack
3817     \endgroup
3818     \@checkend{#2}%
3819     \addtol@denbody{#1}%
3820   \else
3821     \addtol@denbody{#1\end{#2}}%
3822   \fi
```

```

3823 \processl@denbody % A little tricky! Note the grouping
3824 }
3825

```

There was a question on CTT about how to use `\collect@body` for a macro taking an argument. The following is part of that thread.

```

From: Heiko Oberdiek <oberdiek@uni-freiburg.de>
Newsgroups: comp.text.tex
Subject: Re: Using \collect@body with commands that take >1 argument
Date: Fri, 08 Aug 2003 09:03:20 +0200

```

```

eed132@psu.edu (Evan) wrote:
> I'm trying to make a new Latex environment that acts like the>
> \colorbox command that is part of the color package. I looked through
> the FAQ and ran across this bit about using the \collect@body command
> that is part of AMSLaTeX:
> http://www.tex.ac.uk/cgi-bin/texfaq2html?label=cmdasenv
>
> It almost works. If I do something like the following:
> \newcommand{\redbox}[1]{\colorbox{red}{#1}}
>
> \makeatletter
> \newenvironment{redbox}{\collect@body \redbox}{\}

```

You will get an error message: Command `\redbox` already defined.
Thus you must rename either the command `\redbox` or the environment name.

```

> \begin{coloredbox}{blue}
> Yadda yadda yadda... this is on a blue background...
> \end{coloredbox}
> and can't figure out how to make the \collect@body take this.

> \collect@body \colorbox{red}
> \collect@body {\colorbox{red}}

```

The argument of `\collect@body` has to be one token exactly.

```

\documentclass{article}
\usepackage{color}
\usepackage{amsmath}

\newcommand{\redbox}[1]{\colorbox{red}{#1}}
\makeatletter
\newenvironment{coloredbox}[1]{%
  \def\next@{\colorbox{#1}}%
  \collect@body\next@
}{\}

```

```

% ignore spaces at begin and end of environment
\newenvironment{coloredboxII}[1]{%
  \def\next@{\mycoloredbox{#1}}%
  \collect@body\next@
}{%}
\newcommand{\mycoloredbox}[2]{%
  \colorbox{#1}{\ignorespaces#2\unskip}%
}

% support of optional color model argument
\newcommand\coloredboxIII\endcsname{}
\def\coloredboxIII#1#{%
  \@coloredboxIII{#1}%
}
\def\@coloredboxIII#1#2{%
  \def\next@{\mycoloredboxIII{#1}{#2}}%
  \collect@body\next@
}
\newcommand{\mycoloredboxIII}[3]{%
  \colorbox{#1}{#2}{\ignorespaces#3\unskip}%
}

\makeatother

\begin{document}
  Black text before
  \begin{coloredbox}{blue}
    Hello World
  \end{coloredbox}
  Black text after

  Black text before
  \begin{coloredboxII}{blue}
    Hello World
  \end{coloredboxII}
  Black text after

  Black text before
  \begin{coloredboxIII}[rgb]{0,0,1}
    Hello World
  \end{coloredboxIII}
  Black text after

\end{document}

Yours sincerely
Heiko <oberdiek@uni-freiburg.de>

```


38 Verse

This is principally Wayne Sullivan's code and commentary from EDSTANZA [Sul92].

The macro `\hangingsymbol` is used to insert a symbol on each hanging of verses. For example, in french typographie the symbol is ' '. We obtain it by the next code:

```
\renewcommand{\hangingsymbol}{[,}
```

The `\ifinstanza` boolean is used to be sure that we are in a stanza part.

```
\hangingsymbol
\ifinstanza 3826 \newcommand*{\hangingsymbol}{,}
3827 \newif\ifinstanza
3828 \instanzafalse

\inserthangingsymbol The boolean \inserthangingsymbol is set to TRUE when \@lock is greater
\ifinserthangingsymbol than 1, i.e. when we are not in the first line of a verse. The switch of
\ifinserthangingsymbol \ifinserthangingsymbol is made in \do@line before the printing of line but
after the line number calculation.
3829 \newif\ifinserthangingsymbol
3830 \newcommand{\inserthangingsymbol}{%
3831 \ifinserthangingsymbol%
3832 \ifinstanza%
3833 \hangingsymbol%
3834 \fi%
3835 \fi%
3836 }
```

`\ampersand` Within a stanza the `\&` macro is going to be usurped. We need an alias in case an `&` needs to be typeset in a stanza. Define it rather than letting it in case some other package has already defined it.

```
3837 \newcommand*{\ampersand}{\char'\&}
3838
```

`\stanza@count` Before we can define the main macros we need to save and reset some category
`\stanzaindentbase` codes. To save the current values we use `\next` and `\body` from the `\loop` macro.

```
3839 \chardef\body=\catcode'\@
3840 \catcode'\@=11
3841 \chardef\next=\catcode'\&
3842 \catcode'\&=\active
3843
```

A count register is allocated for counting lines in a stanza; also allocated is a dimension register which is used to specify the base value for line indentation; all stanza indentations are multiples of this value. The default value of `\stanzaindentbase` is 20pt.

```
3844 \newcount\stanza@count
3845 \newlength{\stanzaindentbase}
3846 \setlength{\stanzaindentbase}{20pt}
3847
```

`\strip@szacnt` The indentations of stanza lines are non-negative integer multiples of the unit called `\stanzaindentbase`. To make it easier for the user to specify these numbers, some list macros are defined. These take numerical values in a list separated by commas and assign the values to special control sequences using `\mathchardef`. Though this does limit the range from 0 to 32767, it should suffice for most applications, including *penalties*, which will be discussed below.

```

3848 \def\strip@szacnt#1,#2|{\def\@tempb{#1}\def\@tempa{#2|}}
3849 \newcommand*\setstanzavalues}[2]{\def\@tempa{#2,,|}%
3850     \stanza@count\z@
3851     \def\next{\expandafter\strip@szacnt\@tempa
3852         \ifx\@tempb\empty\let\next\relax\else
3853         \expandafter\mathchardef\csname #1@\number\stanza@count
3854         \@endcsname\@tempb\relax
3855         \advance\stanza@count\@ne\fi\next}%
3856     \next}
3857

```

`\setstanzaindents` In the original `\setstanzavalues{sza}{...}` had to be called to set the indents, and similarly `\setstanzavalues{szp}{...}` to set the penalties. These two macros are a convenience to give the user one less thing to worry about (misspelling the first argument). Since version 0.13, the `stanzaindentrepetition` counter can be used when the indentation is repeated every *n* verses. The `\managestanza@modulo` is a command which modifies the counter `stanza@modulo`. The command adds 1 to `stanza@modulo`, but if `stanza@modulo` is equal to the `stanzaindentrepetition` counter, the command restarts it.

```

3858 \newcommand*\setstanzaindents}[1]{\setstanzavalues{sza}{#1}}
3859 \newcommand*\setstanzapenalties}[1]{\setstanzavalues{szp}{#1}}
3860
3861 \newcounter{stanzaindentrepetition}
3862 \newcount\stanza@modulo
3863
3864 \newcommand*\managestanza@modulo}[0]{
3865     \advance\stanza@modulo\@ne
3866     \ifnum\stanza@modulo>\value{stanzaindentrepetition}
3867         \stanza@modulo\@ne
3868     \fi
3869 }

```

`\stanza@line` Now we arrive at the main works. `\stanza@line` sets the indentation for the line and starts a numbered paragraph—each line is treated as a paragraph.

`\stanza@hang` `\stanza@hang` sets the hanging indentation to be used if the stanza line requires more than one print line. If it is known that each stanza line will fit on one print line, it is advisable to set the hanging indentation to zero.

`\sza@penalty` `\sza@penalty` places the specified penalty following each stanza line. By default, this facility is turned off so that no penalty is included. However, the user may initiate these penalties to indicate good and bad places in the stanza for page breaking.

```

3870 \newcommandx{\stanza@line}[1][1]{
3871     \ifnum\value{stanzaindentrepetition}=0

```

```

3872     \parindent=\csname sza@\number\stanza@count
3873             @\endcsname\stanzaindentbase
3874   \else
3875     \parindent=\csname sza@\number\stanza@modulo
3876             @\endcsname\stanzaindentbase
3877     \managestanza@modulo
3878   \fi
3879   \pstart[#1]\stanza@hang\ignorespaces}
3880 \xdef\stanza@hang{\noexpand\leavevmode\noexpand\startlock
3881             \hangindent\expandafter
3882             \noexpand\csname sza@0@\endcsname\stanzaindentbase
3883             \hangafter\@ne}
3884 \def\sza@penalty{\count@\csname szp@\number\stanza@count @\endcsname
3885             \ifnum\count@>\@M\advance\count@-\@M\penalty-\else
3886             \penalty\fi\count@}

```

`\startstanzahook` Now we have the components of the `\stanza` macro, which appears at the start of a group of lines. This macro initializes the count and checks to see if hanging indentation and penalties are to be included. Hanging indentation suspends the line count, so that the enumeration is by verse line rather than by print line. If `\@startstanza` the print line count is desired, invoke `\let\startlock=\relax` and do the same for `\endlock`. Here and above we have used `\xdef` to make the stored macros take up a bit less space, but it also makes them more obscure to the reader. Lines of the stanza are delimited by ampersands `&`. The last line of the stanza must end with `\&`. For convenience the macro `\endstanzaextra` is included. The user may use this to add vertical space or penalties between stanzas.

As a further convenience, the macro `\startstanzahook` is called at the beginning of a stanza. This can be defined to do something useful.

```

3887 \let\startstanzahook\relax
3888 \let\endstanzaextra\relax
3889 \xdef\@startstanza[#1]{%
3890   \noexpand\instanzatrue\expandafter
3891   \begingroup\startstanzahook%
3892   \catcode'\noexpand\&\active%
3893   \global\stanza@count\@ne\stanza@modulo\@ne
3894   \noexpand\ifnum\expandafter\noexpand
3895   \csname sza@0@\endcsname=\z@\let\noexpand\stanza@hang\relax
3896   \let\noexpand\endlock\relax\noexpand\else\interlinepenalty
3897   \@M\rightskip\z@ plus 1fil\relax\noexpand\fi\noexpand\ifnum
3898   \expandafter\noexpand\csname szp@0@\endcsname=\z@
3899   \let\noexpand\sza@penalty\relax\noexpand\fi%
3900   \def\noexpand\falseverse{%
3901     \noexpand\led@war@FalseverseDeprecated%
3902     \global\advance\stanza@modulo-\@ne%
3903     \global\advance\stanza@count-\@ne%
3904     \relax\noexpand\&\leavevmode\skipnumbering}
3905   \def\noexpand\&{%
3906     \noexpand\newverse [] []}%
3907   \def\noexpand\&{\noexpand\@stopstanza}%

```

```

3908 \noexpand\stanza@line[#1]}
3909
3910 \newcommandx{\stanza}[1][1,usedefault]{\@startstanza[#1]}
3911
3912 \newcommandx{\@stopstanza}[1][1,usedefault]{%
3913 \endlock%
3914 \pend[#1]%
3915 \endgroup%
3916 \instanzafalse%
3917 \endstanzaextra%
3918 }
3919
3920 \newcommandx*\newverse}[2][1,2,usedefault]{%
3921 \endlock\pend[#1]\sza@penalty\global%
3922 \advance\stanza@count\@ne\stanza@line[#2]%
3923 }
3924

```

`\flagstanza` Use `\flagstanza[len]{text}` at the start of a line to put *text* a distance *len* before the start of the line. The default for *len* is `\stanzaindentbase`.

```

3925 \newcommand*\flagstanza}[2][\stanzaindentbase]{%
3926 \hskip -#1\llap{#2}\hskip #1\ignorespaces}
3927

```

The ampersand & is used to mark the end of each stanza line, except the last, which is marked with `\&`. This means that `\halign` may not be used directly within a stanza line. This does not affect macros involving alignments defined outside `\stanza \&`. Since these macros usurp the control sequence `\&`, the replacement `\ampersand` is defined to be used if this symbol is needed in a stanza. Also we reset the modified category codes and initialize the penalty default.

```

3928 \catcode'\&=\next
3929 \catcode'\@=\body
3930 %% \let\ampersand=\&
3931 \setstanzavalues{szp}{0}
3932

```

39 Arrays and tables

This is based on the work by Herbert Breger in developing `tabmac.tex`.

```

%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
% This is file tabmac.tex 1.0.
% You find here macros for tabular structures compatible with
% Edmac (authored by Lavagnino/Wujastyk). The use of the macros is
% explained in German language in file tabanlei.dvi. The macros were
% developed for Edmac 2.3, but this file has been adjusted to Edmac 3.16.
%
% ATTENTION: This file uses some Edmac control sequences (like

```

```
% \text, \Afootnote etc.) and redefines \morenoexpands. If you yourself
% redefined some Edmac control sequences, be careful: some adjustments
% might be necessary.
% October 1996
%
% My kind thanks to Nora G^?deke for valuable support. Any hints and
% comments are welcome, please contact Herbert Breger,
% Leibniz-Archiv, Waterloostr. 8, D -- 30169 Hannover, Germany
% Tel.: 511 - 1267 327
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
```

The original `tabmac.tex` file was void of comments or any explanatory text other than the above notice. The algorithm is Breger's. I have made some cosmetic changes to the original code and reimplemented some things so they are more LaTeX-like. All the commentary is mine, as are any mistakes or errors.

`\l@dtabnoexpands` An extended and modified version of the original additional no expansions..

```
3933 \newcommand*\l@dtabnoexpands}{%
3934   \let\rtab=0%
3935   \let\ctab=0%
3936   \let\ltab=0%
3937   \let\rtabtext=0%
3938   \let\ltabtext=0%
3939   \let\ctabtext=0%
3940   \let\edbeforetab=0%
3941   \let\edaftertab=0%
3942   \let\edatab=0%
3943   \let\edatabell=0%
3944   \let\edatleft=0%
3945   \let\edatright=0%
3946   \let\edvertline=0%
3947   \let\edvertdots=0%
3948   \let\edrowfill=0%
3949 }
3950
```

`\disable@familiarnotes` Macros to disable and restore familiar notes, to prevent them from printing multiple times in edtabularx and edarrayx environments.

```
3951 \newcommand{\disable@familiarnotes}{%
3952   \def\do##1{%
3953     \csletcs{footnote@##1}{footnote##1}%
3954     \expandafter\renewcommand \csname footnote##1\endcsname[1]{%
3955       \protected@csxdef{thefnmark##1}{\csuse{thefootnote##1}}%
3956       \csuse{footnotemark##1}%
3957     }%
3958   }%
3959   \dolistloop{\@series}%
```

```

3960 }%
3961 \newcommand{\restore@familiarnotes}{%
3962   \def\do##1{%
3963     \csletcs{footnote##1}{footnote@@##1}%
3964   }%
3965   \dolistloop{\@series}%
3966 }%
3967

\disable@sidenotes The sames, for side notes.
\restore@sidenotes 3968 \newcommand{\disable@sidenotes}{%
3969   \let\@@ledrightnote\ledrightnote%
3970   \let\@@ledleftnote\ledleftnote%
3971   \let\@@ledsidenote\ledsidenote%
3972   \let\ledrightnote\@gobble%
3973   \let\ledleftnote\@gobble%
3974   \let\ledsidenote\@gobble%
3975 }%
3976 \newcommand{\restore@sidenotes}{%
3977   \let\ledrightnote\@@ledrightnote%
3978   \let\ledleftnote\@@ledleftnote%
3979   \let\ledsidenote\@@ledsidenote%
3980 }%

\disable@notes Disable/restore side and familiar notes.
\restore@notes 3981 \newcommand{\disable@notes}{%
3982   \disable@sidenotes%
3983   \disable@familiarnotes%
3984 }%
3985 \newcommand{\restore@notes}{%
3986   \restore@sidenotes%
3987   \restore@familiarnotes%
3988 }%

\l@dampcount \l@dampcount is a counter for the & column dividers and \l@dcolcount is a
\l@dcolcount counter for the columns. These were \Undcount and \stellencount respectively.
3989 \newcount\l@dampcount
3990 \l@dampcount=1\relax
3991 \newcount\l@dcolcount
3992 \l@dcolcount=0\relax
3993

\hilfsbox Some (temporary) helper items.
\hilfsskip 3994 \newbox\hilfsbox
\Hilfsbox 3995 \newskip\hilfsskip
\hilfscount 3996 \newbox\Hilfsbox
3997 \newcount\hilfscount
3998

```

30 columns should be adequate (compared to the original 60). These are the column widths. (Originally these were German spelled numbers e.g., `\eins`, `\zwei`, etc).

```

3999 \newdimen\dcoli
4000 \newdimen\dcolii
4001 \newdimen\dcoliii
4002 \newdimen\dcoliv
4003 \newdimen\dcolv
4004 \newdimen\dcolvi
4005 \newdimen\dcolvii
4006 \newdimen\dcolviii
4007 \newdimen\dcolix
4008 \newdimen\dcolx
4009 \newdimen\dcolxi
4010 \newdimen\dcolxii
4011 \newdimen\dcolxiii
4012 \newdimen\dcolxiv
4013 \newdimen\dcolxv
4014 \newdimen\dcolxvi
4015 \newdimen\dcolxvii
4016 \newdimen\dcolxviii
4017 \newdimen\dcolxix
4018 \newdimen\dcolxx
4019 \newdimen\dcolxxi
4020 \newdimen\dcolxxii
4021 \newdimen\dcolxxiii
4022 \newdimen\dcolxxiv
4023 \newdimen\dcolxxv
4024 \newdimen\dcolxxvi
4025 \newdimen\dcolxxvii
4026 \newdimen\dcolxxviii
4027 \newdimen\dcolxxix
4028 \newdimen\dcolxxx
4029 \newdimen\dcolerr    % added for error handling
4030

```

`\l@dcolwidth` This is a cunning way of storing the columnwidths indexed by the column number `\l@dcolcount`, like an array. (was `\Dimenzuordnung`)

```

4031 \newcommand{\l@dcolwidth}{\ifcase \the\l@dcolcount \dcoli %???
4032 \or \dcoli \or \dcolii \or \dcoliii
4033 \or \dcoliv \or \dcolv \or \dcolvi
4034 \or \dcolvii \or \dcolviii \or \dcolix \or \dcolx
4035 \or \dcolxi \or \dcolxii \or \dcolxiii
4036 \or \dcolxiv \or \dcolxv \or \dcolxvi
4037 \or \dcolxvii \or \dcolxviii \or \dcolxix \or \dcolxx
4038 \or \dcolxxi \or \dcolxxii \or \dcolxxiii
4039 \or \dcolxxiv \or \dcolxxv \or \dcolxxvi
4040 \or \dcolxxvii \or \dcolxxviii \or \dcolxxix \or \dcolxxx
4041 \else \dcolerr \fi}

```

4042

`\step1@dcolcount` This increments the column counter, and issues an error message if it is too large.

```
4043 \newcommand*{\step1@dcolcount}{\advance\l@dcolcount\@ne
4044 \ifnum\l@dcolcount>30\relax
4045   \led@err@TooManyColumns
4046 \fi}
4047
```

`\l@dsetmaxcolwidth` Sets the column width to the maximum value seen so far. (was `\dimenzuordnung`)

```
4048 \newcommand{\l@dsetmaxcolwidth}{%
4049 \ifdim\l@dcolwidth < \wd\hilfsbox
4050   \l@dcolwidth = \wd\hilfsbox
4051 \else \relax \fi}
4052
```

`\EDTEXT` We need to be able to modify the `\edtext` and `\critext` macros and also restore `\xedtext` their original definitions.

```
\CRITEXT 4053 \let\EDTEXT=\edtext
\xcritext 4054 \newcommand{\xedtext}[2]{\EDTEXT{#1}{#2}}
4055 \let\CRITEXT=\critext
4056 \long\def\xcritext #1#2/{\CRITEXT{#1}{#2}/}
```

`\EDLABEL` We need to be able to modify and restore the `\edlabel` macro.

```
\xedlabel 4057 \let\EDLABEL=\edlabel
4058 \newcommand*{\xedlabel}[1]{\EDLABEL{#1}}
```

`\EDINDEX` Macros supporting modification and restoration of `\edindex`.

```
\xedindex 4059 \let\EDINDEX=\edindex
\nulledindex 4060 \ifl@dmemoir
4061   \newcommand{\xedindex}{\@bsphack%
4062     \@ifnextchar [{\l@d@index}{\l@d@index[\jobname]}}
4063   \newcommand{\nulledindex}[2][\jobname]{\@bsphack\@esphack}
4064 \else
4065   \newcommand{\xedindex}{\@bsphack%
4066     \doedindexlabel
4067     \begingroup
4068     \@sanitize
4069     \@wredindex}
4070   \newcommand{\nulledindex}[1]{\@bsphack\@esphack}
4071 \fi
4072
```

`\@line@num` Macro supporting restoration of `\linenum`.

```
4073 \let\@line@num=\linenum
```

`\l@dgoobledarg` `\l@dgoobledarg` replaces its delineated argument by `\relax` (was `\verschwinden`).

`\l@dgooblearg` `\l@dgoobleoptarg[\arg]{\arg}` replaces these two arguments (first is optional) by `\relax`.


```

4074 \def\l@dgoobledarg #1/{\relax}
4075 \newcommand*{\l@dgoobleoptarg}[2][\relax]%
4076

\Relax
\NEXT 4077 \let\Relax=\relax
\@hilfs@count 4078 \let\NEXT=\next
4079 \newcount\@hilfs@count
4080

\measuremcell Measure (recursively) the width required for a math cell. (was \messen)
4081 \def\measuremcell #1{%
4082   \ifx #1\ \ifnum\l@dcolcount=0\let\NEXT\relax%
4083   \else\l@dcheckcols%
4084   \l@dcolcount=0%
4085   \let\NEXT\measuremcell%
4086   \fi%
4087   \else\setbox\hilfsbox=\hbox{$\displaystyle{#1}$}%
4088   \step\l@dcolcount%
4089   \l@dsetmaxcolwidth%
4090   \let\NEXT\measuremcell%
4091   \fi\NEXT}
4092

\measuretcell Measure (recursively) the width required for a text cell. (was \messentext)
4093 \def\measuretcell #1{%
4094   \ifx #1\ \ifnum\l@dcolcount=0\let\NEXT\relax%
4095   \else\l@dcheckcols%
4096   \l@dcolcount=0%
4097   \let\NEXT\measuretcell%
4098   \fi%
4099   \else\setbox\hilfsbox=\hbox{#1}%
4100   \step\l@dcolcount%
4101   \l@dsetmaxcolwidth%
4102   \let\NEXT\measuretcell%
4103   \fi\NEXT}
4104

\measuremrow Measure (recursively) the width required for a math row. (was \Messen)
4105 \def\measuremrow #1\\{%
4106   \ifx #1\let\NEXT\relax%
4107   \else\measuremcell #1\\&&%
4108   \let\NEXT\measuremrow%
4109   \fi\NEXT}

\measuretrow Measure (recursively) the width required for a text row. (was \Messentext)
4110 \def\measuretrow #1\\{%
4111   \ifx #1\let\NEXT\relax%
4112   \else\measuretcell #1\\&&%

```

```

4113     \let\NEXT\measuretrrow%
4114     \fi\NEXT}
4115

```

`\edtabcolsep` The length `\edtabcolsep` controls the distance between columns. (was `\abstand`)

```

4116 \newskip\edtabcolsep
4117 \global\edtabcolsep=10pt
4118

```

`\NEXT`

```

\Next 4119 \let\NEXT\relax
4120 \let\Next=\next

```

`\variab`

```

4121 \newcommand{\variab}{\relax}
4122

```

`\l@dcheckcols` Check that the number of columns is consistent. (was `\tabfehlermeldung`)

```

4123 \newcommand*{\l@dcheckcols}{%
4124   \ifnum\l@dcolcount=1\relax
4125   \else
4126     \ifnum\l@dampcount=1\relax
4127     \else
4128       \ifnum\l@dcolcount=\l@dampcount\relax
4129       \else
4130         \l@d@err@UnequalColumns
4131       \fi
4132     \fi
4133     \l@dampcount=\l@dcolcount
4134   \fi}
4135

```

`\l@dmodforcritext` Modify and restore various macros for when `\critext` is used.

```

\l@drestoreforcritext 4136 \newcommand{\l@dmodforcritext}{%
4137   \let\critext\relax%
4138   \def\do##1{\global\csletcs{##1footnote}{\l@dgobbledarg}}
4139   \dolistloop{\@series}%
4140   \let\edindex\nulledindex%
4141   \let\linenum@gobble}
4142 \newcommand{\l@drestoreforcritext}{%
4143   \def\do##1{\csdef{##1footnote}##1##2/{\csuse{##1@footnote}{##1}{##2}}}
4144   \dolistloop{\@series}%
4145   \let\edindex\xedndex}
4146

```

`\l@dmodforedtext` Modify and restore various macros for when `\edtext` is used.

```

\l@drestoreforedtext 4147 \newcommand{\l@dmodforedtext}{%
4148   \let\edtext\relax
4149   \def\do##1{\global\csletcs{##1footnote}{\l@dgobbleoptarg}}%

```

```

4150 \dolistloop{\@series}%
4151 \let\edindex\nulledindex
4152 \let\linenum\@gobble}
4153 \newcommand{\l@drestorefordtext}{%
4154 \def\do##1{\global\csletcs{##1footnote}{##1@footnote}}
4155 \dolistloop{\@series}%
4156 \let\edindex\xedndex}

```

`\l@dnullfills` Nullify and restore some column fillers, etc.

```

\l@drestorefills 4157 \newcommand{\l@dnullfills}{%
4158 \def\edlabel##1{}%
4159 \def\edrowfill##1##2##3{}%
4160 }
4161 \newcommand{\l@drestorefills}{%
4162 \def\edrowfill##1##2##3{\@EDROWFILL@{##1}{##2}{##3}}%
4163 }
4164

```

The original definition of `\rverteilen` and friends (‘verteilen’ is approximately ‘distribute’) was along the lines:

```

\def\rverteilen #1&{\def\label##1{}%
  \ifx #1! \ifnum\l@dcolcount=0%\removelastskip
    \let\Next\relax%
  \else\l@dcolcount=0%
    \let\Next=\rverteilen%
  \fi%
\else%
  \footnoteverschw%
  \stepl@dcolcount%
  \setbox\hilfsbox=\hbox{$\displaystyle{#1}$}%
  \let\critext=\xcritext\let\Dfootnote=\D@@footnote
  \let\Afootnote=\A@@footnote\let\Bfootnote=\B@@footnote
  \let\Cfootnote=\C@@footnote\let\linenum=\@line@num%
  \hilfsskip=\Dimenzuordnung%
  \advance\hilfsskip by -\wd\hilfsbox
  \def\label##1{\xlabel{##1}}%
  \hskip\hilfsskip$\displaystyle{#1}$%
  \hskip\edtabcolsep%
  \let\Next=\rverteilen%
\fi\Next}

```

where the lines

```

\let\critext=\xcritext\let\Dfootnote=\D@@footnote
\let\Afootnote=\A@@footnote\let\Bfootnote=\B@@footnote
\let\Cfootnote=\C@@footnote\let\linenum=\@line@num%
\hilfsskip=\Dimenzuordnung%
\advance\hilfsskip by -\wd\hilfsbox
\def\label##1{\xlabel{##1}}%

```

were common across the several **verteilen** macros, and also

```
\def\footnoteverschw{%
  \let\critext\relax
  \let\Afootnote=\verschwinden
  \let\Bfootnote=\verschwinden
  \let\Cfootnote=\verschwinden
  \let\Dfootnote=\verschwinden
  \let\linenum=\@gobble}
```

\letsforverteilen Gathers some lets and other code that is common to the **verteilen** macros.

```
4165 \newcommand{\letsforverteilen}{%
4166   \let\critext\xcritext
4167   \let\edtext\xedtext
4168   \let\edindex\xedindex
4169   \def\do##1{\global\csletcs{##1footnote}{##1@footnote}}
4170   \dolistloop{\@series}%
4171   \let\linenum\@line@num
4172   \hilfsskip=\l@dcwidth%
4173   \advance\hilfsskip by -\wd\hilfsbox
4174   \def\edlabel##1{\xedlabel{##1}}
4175 }
```

\setmcellright Typeset (recursively) cells of display math right justified. (was *\rverteilen*)

```
4176 \def\setmcellright #1&{\def\edlabel##1}%
4177   \let\edindex\nulledindex
4178   \ifx #1\ \ifnum\l@dcwidth=0%\removelastskip
4179     \let\Next\relax%
4180   \else\l@dcwidth=0%
4181     \let\Next=\setmcellright%
4182   \fi%
4183   \else%
4184     \disablel@dtabfeet%
4185     \step1@dcwidth%
4186     \disable@notes%
4187     \setbox\hilfsbox=\hbox{$\displaystyle{#1}$}%
4188     \restore@notes%
4189     \letsforverteilen%
4190     \hskip\hilfsskip$\displaystyle{#1}$%
4191     \hskip\edtabcolsep%
4192     \let\Next=\setmcellright%
4193   \fi\Next}
4194
```

\settcellright Typeset (recursively) cells of text right justified. (was *\rverteilentext*)

```
4195 \def\settcellright #1&{\def\edlabel##1}%
4196   \let\edindex\nulledindex
4197   \ifx #1\ \ifnum\l@dcwidth=0%\removelastskip
4198     \let\Next\relax%
```

```

4199         \else\l@dcolcount=0%
4200             \let\Next=\settcellright%
4201         \fi%
4202     \else%
4203         \disablel@dtabfeet%
4204         \step1@dcolcount%
4205         \disable@notes%
4206         \setbox\hilfsbox=\hbox{#1}%
4207         \restore@notes%
4208         \letsforverteilen%
4209         \hskip\hilfsskip#1%
4210         \hskip\edtabcolsep%
4211         \let\Next=\settcellright%
4212     \fi\Next}

```

`\setmcellleft` Typeset (recursively) cells of display math left justified. (was `\lverteilen`)

```

4213 \def\setmcellleft #1&{\def\edlabel##1{}%
4214     \let\edindex\nulledindex
4215     \ifx #1\ \ifnum\l@dcolcount=0 \let\Next\relax%
4216         \else\l@dcolcount=0%
4217             \let\Next=\setmcellleft%
4218         \fi%
4219     \else \disablel@dtabfeet%
4220         \step1@dcolcount%
4221         \disable@notes%
4222         \setbox\hilfsbox=\hbox{$\displaystyle{#1}$}%
4223         \restore@notes%
4224         \letsforverteilen%
4225         $\displaystyle{#1}$\hskip\hilfsskip\hskip\edtabcolsep%
4226         \let\Next=\setmcellleft%
4227     \fi\Next}
4228

```

`\settcellleft` Typeset (recursively) cells of text left justified. (was `\lverteilentext`)

```

4229 \def\settcellleft #1&{\def\edlabel##1{}%
4230     \let\edindex\nulledindex
4231     \ifx #1\ \ifnum\l@dcolcount=0 \let\Next\relax%
4232         \else\l@dcolcount=0%
4233             \let\Next=\settcellleft%
4234         \fi%
4235     \else \disablel@dtabfeet%
4236         \step1@dcolcount%
4237         \disable@notes%
4238         \setbox\hilfsbox=\hbox{#1}%
4239         \restore@notes%
4240         \letsforverteilen%
4241         #1\hskip\hilfsskip\hskip\edtabcolsep%
4242         \let\Next=\settcellleft%
4243     \fi\Next}

```

`\setmcellcenter` Typeset (recursively) cells of display math centered. (was `\zverteilen`)

```

4244 \def\setmcellcenter #1&{\def\edlabel##1{}}%
4245   \let\edindex\nulledindex
4246   \ifx #1\\ \ifnum\l@dc@colcount=0\let\Next\relax%
4247           \else\l@dc@colcount=0%
4248           \let\Next=\setmcellcenter%
4249           \fi%
4250   \else   \disablel@dtabfeet%
4251           \stepl@dc@colcount%
4252           \disable@notes%
4253           \setbox\hilfsbox=\hbox{$\displaystyle{#1}$}%
4254           \restore@notes%
4255           \letsforverteilen%
4256           \hskip 0.5\hilfsskip$\displaystyle{#1}$\hskip0.5\hilfsskip%
4257           \hskip\edtabcolsep%
4258           \let\Next=\setmcellcenter%
4259   \fi\Next}
4260

```

`\settc@cellcenter` Typeset (recursively) cells of text centered. (new)

```

4261 \def\settc@cellcenter #1&{\def\edlabel##1{}}%
4262   \let\edindex\nulledindex
4263   \ifx #1\\ \ifnum\l@dc@colcount=0 \let\Next\relax%
4264           \else\l@dc@colcount=0%
4265           \let\Next=\settc@cellcenter%
4266           \fi%
4267   \else   \disablel@dtabfeet%
4268           \stepl@dc@colcount%
4269           \disable@notes%
4270           \setbox\hilfsbox=\hbox{#1}%
4271           \restore@notes%
4272           \letsforverteilen%
4273           \hskip 0.5\hilfsskip #1\hskip 0.5\hilfsskip%
4274           \hskip\edtabcolsep%
4275           \let\Next=\settc@cellcenter%
4276   \fi\Next}
4277

```

`\NEXT`

```

4278 \let\NEXT=\relax
4279

```

`\setmrowright` Typeset (recursively) rows of right justified math. (was `\rsetzen`)

```

4280 \def\setmrowright #1\\{%
4281   \ifx #1& \let\NEXT\relax
4282   \else \centerline{\setmcellright #1&\\&\\&}
4283   \let\NEXT=\setmrowright
4284   \fi\NEXT}

```

`\settroright` Typeset (recursively) rows of right justified text. (was `\rsetzentext`)

```
4285 \def\settroright #1\\{%
4286   \ifx #1& \let\NEXT\relax
4287   \else \centerline{\settcclright #1&\\&\\&}
4288         \let\NEXT=\settroright
4289   \fi\NEXT}
4290
```

`\setmrowleft` Typeset (recursively) rows of left justified math. (was `\lsetzen`)

```
4291 \def\setmrowleft #1\\{%
4292   \ifx #1& \let\NEXT\relax
4293   \else \centerline{\setmcclleft #1&\\&\\&}
4294         \let\NEXT=\setmrowleft
4295   \fi\NEXT}
```

`\settrorleft` Typeset (recursively) rows of left justified text. (was `\lsetzentext`)

```
4296 \def\settrorleft #1\\{%
4297   \ifx #1& \let\NEXT\relax
4298   \else \centerline{\settcclleft #1&\\&\\&}
4299         \let\NEXT=\settrorleft
4300   \fi\NEXT}
4301
```

`\setmrowcenter` Typeset (recursively) rows of centered math. (was `\zsetzen`)

```
4302 \def\setmrowcenter #1\\{%
4303   \ifx #1& \let\NEXT\relax%
4304   \else \centerline{\setmcclcenter #1&\\&\\&}
4305         \let\NEXT=\setmrowcenter
4306   \fi\NEXT}
```

`\settrorcenter` Typeset (recursively) rows of centered text. (new)

```
4307 \def\settrorcenter #1\\{%
4308   \ifx #1& \let\NEXT\relax
4309   \else \centerline{\settcclcenter #1&\\&\\&}
4310         \let\NEXT=\settrorcenter
4311   \fi\NEXT}
4312
```

`\nullsetzen` (was `\nullsetzen`)

```
4313 \newcommand{\nullsetzen}{%
4314   \step1@dcolcount%
4315   \l@dcolwidth=0pt%
4316   \ifnum\l@dcolcount=30\let\NEXT\relax%
4317       \l@dcolcount=0\relax
4318   \else\let\NEXT\nullsetzen%
4319   \fi\NEXT}
4320
```

```

\edatleft \edatleft[⟨math⟩]{⟨symbol⟩}{⟨len⟩} (combination and generalisation of original
\Seklam and \Seklamgl). Left ⟨symbol⟩, 2⟨len⟩ high with prepended ⟨math⟩
vertically centered.
4321 \newcommand{\edatleft}[3][\@empty]{%
4322   \ifx#1\@empty
4323     \vbox to 10pt{\vss\hbox{$\left#2\vrule width0pt height #3
4324                               depth 0pt \right. $\hss}\vfil}
4325   \else
4326     \vbox to 4pt{\vss\hbox{$#1\left#2\vrule width0pt height #3
4327                               depth 0pt \right. $\vfil}
4328   \fi}

\edatright \edatright[⟨math⟩]{⟨symbol⟩}{⟨len⟩} (combination and generalisation of origi-
nal \sekla and \sekla). Right ⟨symbol⟩, 2⟨len⟩ high with appended ⟨math⟩
vertically centered.
4329 \newcommand{\edatright}[3][\@empty]{%
4330   \ifx#1\@empty
4331     \vbox to 10pt{\vss\hbox{$\right.\vrule width0pt height #3
4332                               depth 0pt \right#2 $\hss}\vfil}
4333   \else
4334     \vbox to 4pt{\vss\hbox{$\right.\vrule width0pt height #3
4335                               depth 0pt \right#2 #1 $\vfil}
4336   \fi}
4337

\edvertline \edvertline{⟨len⟩} vertical line ⟨len⟩ high. (was \sestrich)
4338 \newcommand{\edvertline}[1]{\vbox to 8pt{\vss\hbox{\vrule height #1}\vfil}}
4339

\edvertdots \edvertdots{⟨len⟩} vertical dotted line ⟨len⟩ high. (was \sepunkte)
4340 \newcommand{\edvertdots}[1]{\vbox to 1pt{\vss\vbox to #1%
4341   {\cleaders\hbox{$\m@th\hbox{.}\vbox to 0.5em{ }$}\vfil}}}
4342

```

I don't know if this is relevant here, and I haven't tried it, but the following appeared on CTT.

From: mdw@nsict.org (Mark Wooding)
 Newsgroups: comp.text.tex
 Subject: Re: Dotted line
 Date: 13 Aug 2003 13:51:14 GMT

Alexis Eisenhofer <alexis@eisenhofer.de> wrote:
 > Can anyone provide me with the LaTeX command for a vertical dotted line?

How dotted? Here's the basic rune.
 \newbox\linedotbox
 \setbox\linedotbox=\vbox{...}
 \leaders\copy\linedotbox\vskip2in

For just dots, this works:

```
\setbox\linedotbox=\vbox{\hbox{\normalfont.}\kern2pt}
```

For dashes, something like

```
\setbox\linedotbox=\vbox{\leaders\vrule\vskip2pt\vskip2pt}
```

is what you want. (Adjust the ‘2pt’ values to taste. The first one is the length of the dashes, the second is the length of the gaps.)

For dots in mid-paragraph, you need to say something like

```
\lower10pt\vbox{\leaders\copy\linedotbox\vskip2in}
```

which is scungy but works.

-- [mdw]

`\edfilldimen` A length. (was `\klamdimen`)

```
4343 \newdimen\edfilldimen
```

```
4344 \edfilldimen=0pt
```

```
4345
```

`\c@addcolcount` A counter to hold the number of a column. We use a roman number so that we
`\theaddcolcount` can grab the column dimension from `\dcol....`

```
4346 \newcounter{addcolcount}
```

```
4347 \renewcommand{\theaddcolcount}{\roman{addcolcount}}
```

`\l@dtabaddcols` `\l@dtabaddcols{<startcol>}{<endcol>}` adds the widths of the columns `<startcol>` through `<endcol>` to `\edfilldimen`. It is a LaTeX style reimplementaion of the original `\@add@`.

```
4348 \newcommand{\l@dtabaddcols}[2]{%
```

```
4349 \l@dccheckstartend{#1}{#2}%
```

```
4350 \ifl@dstartendok
```

```
4351 \setcounter{addcolcount}{#1}%
```

```
4352 \@whilenum \value{addcolcount}<#2\relax \do
```

```
4353 {\advance\edfilldimen by \the \csname dcol\theaddcolcount\endcsname
```

```
4354 \advance\edfilldimen by \edtabcolsep
```

```
4355 \stepcounter{addcolcount}}%
```

```
4356 \advance\edfilldimen by \the \csname dcol\theaddcolcount\endcsname
```

```
4357 \fi
```

```
4358 }
```

```
4359
```

`\ifl@dstartendok` `\l@dccheckstartend{<startcol>}{<endcol>}` checks that the values of `<startcol>` and `<endcol>` are sensible. If they are then `\ifl@dstartendok` is set TRUE, otherwise it is set FALSE.

```
4360 \newif\ifl@dstartendok
```

```
4361 \newcommand{\l@dccheckstartend}[2]{%
```

```
4362 \l@dstartendoktrue
```

```
4363 \ifnum #1<\@ne
```

```

4364 \l@dstartendokfalse
4365 \led@err@LowStartColumn
4366 \fi
4367 \ifnum #2>30\relax
4368 \l@dstartendokfalse
4369 \led@err@HighEndColumn
4370 \fi
4371 \ifnum #1>#2\relax
4372 \l@dstartendokfalse
4373 \led@err@ReverseColumns
4374 \fi
4375 }
4376

```

`\edrowfill` `\edrowfill{<startcol>}{<endcol>}` fill fills columns `<startcol>` to `<endcol>` inclusive with `<fill>` (e.g. `\hrulefill`, `\upbracefill`). This is a LaTeX style reimplementa-
`\@edrowfill@` tion and generalization of the original `\waklam`, `\Waklam`, `\waklamec`, `\wastricht`
`\@EDROWFILL@` and `\wapunktel` macros.

```

4377 \newcommand*{\edrowfill}[3]{%
4378 \l@dtabaddcols{#1}{#2}%
4379 \hb@xt@ \the\l@dcolwidth{\hb@xt@ \the\edfilldimen{#3}\hss}}
4380 \let\@edrowfill@=\edrowfill
4381 \def\@EDROWFILL@#1#2#3{\@edrowfill@{#1}{#2}{#3}}
4382

```

`\edbeforetab` The macro `\edbeforetab{<text>}{<math>}` puts `<text>` at the left margin be-
`\edaftertab` fore array cell entry `<math>`. Conversely, the macro `\edaftertab{<math>}{<text>}`
puts `<text>` at the right margin after array cell entry `<math>`. `\edbeforetab` should
be in the first column and `\edaftertab` in the last column. The following macros
support these.

`\leftltab` `\leftltab{<text>}` for `\edbeforetab` in `\ltab`. (was `\linksltab`)

```

4383 \newcommand{\leftltab}[1]{%
4384 \hb@xt@ \z@{\vbox{\edtabindent%
4385 \moveleft\Hilfsskip\hbox{\ #1}}\hss}}
4386

```

`\leftrtab` `\leftrtab{<text>}{<math>}` for `\edbeforetab` in `\rtab`. (was `\linksrta`)

```

4387 \newcommand{\leftrtab}[2]{%
4388 #2\hb@xt@ \z@{\vbox{\edtabindent%
4389 \advance\Hilfsskip by\dcoli%
4390 \moveleft\Hilfsskip\hbox{\ #1}}\hss}}
4391

```

`\leftctab` `\leftctab{<text>}{<math>}` for `\edbeforetab` in `\ctab`. (was `\linksztab`)

```

4392 \newcommand{\leftctab}[2]{%
4393 \hb@xt@ \z@{\vbox{\edtabindent\l@dcolcount=\l@dampcount%
4394 \advance\Hilfsskip by 0.5\dcoli%
4395 \setbox\hilfsbox=\hbox{\def\edlabel#1{}}%

```

```

4396      \disablel@dtabfeet$\displaystyle{#2}$}%
4397      \advance\Hilfsskip by -0.5\wd\hilfsbox%
4398      \moveleft\Hilfsskip\hbox{\ #1}}\hss}%
4399      #2}
4400

```

`\rightctab` `\rightctab{ $\langle math \rangle$ { $\langle text \rangle$ }}` for `\edaftertab` in `\ctab`. (was `\rechtsztab`)

```

4401 \newcommand{\rightctab}[2]{%
4402     \setbox\hilfsbox=\hbox{\def\edlabel##1{%
4403         \disablel@dtabfeet#2}\l@dampcount=\l@dcolcount%
4404         #1\hb@xt@z@{\vbox{\edtabindent\l@dcolcount=\l@dampcount%
4405             \advance\Hilfsskip by 0.5\l@dcolwidth%
4406             \advance\Hilfsskip by -\wd\hilfsbox%
4407             \setbox\hilfsbox=\hbox{\def\edlabel##1{%
4408                 \disablel@dtabfeet$\displaystyle{#1}$}%
4409                 \advance\Hilfsskip by -0.5\wd\hilfsbox%
4410                 \advance\Hilfsskip by \edtabcolsep%
4411                 \moveright\Hilfsskip\hbox{ #2}}\hss}%
4412             }
4413

```

`\rightltab` `\rightltab{ $\langle math \rangle$ { $\langle text \rangle$ }}` for `\edaftertab` in `\ltab`. (was `\rechtsltab`)

```

4414 \newcommand{\rightltab}[2]{%
4415     \setbox\hilfsbox=\hbox{\def\edlabel##1{%
4416         \disablel@dtabfeet#2}\l@dampcount=\l@dcolcount%
4417         #1\hb@xt@z@{\vbox{\edtabindent\l@dcolcount=\l@dampcount%
4418             \advance\Hilfsskip by\l@dcolwidth%
4419             \advance\Hilfsskip by-\wd\hilfsbox%
4420             \setbox\hilfsbox=\hbox{\def\edlabel##1{%
4421                 \disablel@dtabfeet$\displaystyle{#1}$}%
4422                 \advance\Hilfsskip by-\wd\hilfsbox%
4423                 \advance\Hilfsskip by\edtabcolsep%
4424                 \moveright\Hilfsskip\hbox{ #2}}\hss}%
4425             }
4426

```

`\rightrtab` `\rightrtab{ $\langle math \rangle$ { $\langle text \rangle$ }}` for `\edaftertab` in `\rtab`. (was `\rechtsrtab`)

```

4427 \newcommand{\rightrtab}[2]{%
4428     \setbox\hilfsbox=\hbox{\def\edlabel##1{%
4429         \disablel@dtabfeet#2}%
4430         #1\hb@xt@z@{\vbox{\edtabindent%
4431             \advance\Hilfsskip by-\wd\hilfsbox%
4432             \advance\Hilfsskip by\edtabcolsep%
4433             \moveright\Hilfsskip\hbox{ #2}}\hss}%
4434         }
4435

```

`\rtab` `\rtab{ $\langle body \rangle$ }` typesets $\langle body \rangle$ as an array with the entries right justified. (was `\edbforetab` `\rtab`) (Here and elsewhere, `\edbforetab` and `\edaftertab` were originally `\edaftertab`

`\davor` and `\danach`) The original `\rtab` and friends included a fair bit of common code which I have extracted into macros.

The process is first to measure the $\langle body \rangle$ to get the column widths, and then in a second pass to typeset the body.

```

4436 \newcommand{\rtab}[1]{%
4437   \l@dnnullfills
4438   \def\edbeforetab##1##2{\lefttab{##1}{##2}}%
4439   \def\edaftertab##1##2{\righttab{##1}{##2}}%
4440   \measurebody{#1}%
4441   \l@drestorefills
4442   \variab
4443   \setmrowright #1\\&\\%
4444   \enablel@dtabfeet}
4445

```

`\measurebody` `\measurebody{ $\langle body \rangle$ }` measures the array $\langle body \rangle$.

```

4446 \newcommand{\measurebody}[1]{%
4447   \disablel@dtabfeet%
4448   \l@dcolcount=0%
4449   \nullsetzen%
4450   \l@dcolcount=0
4451   \measuremrow #1\\&\\%
4452   \global\l@dampcount=1}
4453

```

`\rtabtext` `\rtabtext{ $\langle body \rangle$ }` typesets $\langle body \rangle$ as a tabular with the entries right justified. (was `\rtabtext`)

```

4454 \newcommand{\rtabtext}[1]{%
4455   \l@dnnullfills
4456   \measuretbody{#1}%
4457   \l@drestorefills
4458   \variab
4459   \settroright #1\\&\\%
4460   \enablel@dtabfeet}
4461

```

`\measuretbody` `\measuretbody{ $\langle body \rangle$ }` measures the tabular $\langle body \rangle$.

```

4462 \newcommand{\measuretbody}[1]{%
4463   \disable@notes%
4464   \disablel@dtabfeet%
4465   \l@dcolcount=0%
4466   \nullsetzen%
4467   \l@dcolcount=0
4468   \measuretbody #1\\&\\%
4469   \restore@notes%
4470   \global\l@dampcount=1}
4471

```

`\ltab` Array with entries left justified. (was `\ltab`)

```

\edbeforetab
\edaftertab

```

```

4472 \newcommand{\ltab}[1]{%
4473   \l@dnnullfills
4474   \def\edbeforetab##1##2{\leftltab{##1}{##2}}%
4475   \def\edaftertab##1##2{\rightltab{##1}{##2}}%
4476   \measuretbody{#1}%
4477   \l@drestorefills
4478   \variab
4479   \setmrowleft #1\&\&\%
4480   \enablel@dtabfeet}
4481

```

`\ltabtext` Tabular with entries left justified. (was `\ltabtext`)

```

4482 \newcommand{\ltabtext}[1]{%
4483   \l@dnnullfills
4484   \measuretbody{#1}%
4485   \l@drestorefills
4486   \variab
4487   \settrrowleft #1\&\&\%
4488   \enablel@dtabfeet}
4489

```

`\ctab` Array with centered entries. (was `\ztab`)

```

\edbeforetab 4490 \newcommand{\ctab}[1]{%
\edaftertab 4491   \l@dnnullfills
4492   \def\edbeforetab##1##2{\leftctab{##1}{##2}}%
4493   \def\edaftertab##1##2{\rightctab{##1}{##2}}%
4494   \measuretbody{#1}%
4495   \l@drestorefills
4496   \variab
4497   \setmrowcenter #1\&\&\%
4498   \enablel@dtabfeet}
4499

```

`\ctabtext` Tabular with entries centered. (new)

```

4500 \newcommand{\ctabtext}[1]{%
4501   \l@dnnullfills
4502   \measuretbody{#1}%
4503   \l@drestorefills
4504   \variab
4505   \settrrowcenter #1\&\&\%
4506   \enablel@dtabfeet}
4507

```

`\spreadtext` (was `\breitertext`)

```

4508 \newcommand{\spreadtext}[1]{%\l@dcolcount=\l@dampcount%
4509   \hb@xt@ \the\l@dcolwidth{\hbox{#1}\hss}}

```

`\spreadmath` (was `\breiter`, ‘breiter’ = ‘broadly’)

```

4510 \newcommand{\spreadmath}[1]{%

```

```

4511 \hb@xt@ \the\l@dcowidth{\hbox{$\displaystyle{#1}$}\hss}}
4512

```

I have left the remaining TABMAC alone, apart from changing some names. I'm not yet sure what they do or how they do it. Authors should not use any of these as they are likely to be mutable.

`\tabellzwischen` (was `\tabellzwischen`)

```

4513 \def\tabellzwischen #1&{%
4514     \ifx #1\ \let\NEXT\relax \l@dcowcount=0
4515     \else \step1@dcowcount%
4516         \l@dcowwidth = #1 mm
4517     \let\NEXT=\tabellzwischen
4518     \fi \NEXT }
4519

```

`\edatabell` For example `\edatabell 4 & 19 & 8 \` specifies 3 columns with widths of 4, 19, and 8mm. (was `\atabell`)

```

4520 \def\edatabell #1\{%
4521     \tabellzwischen #1&\&}

```

`\Setzen` (was `\Setzen`, 'setzen' = 'set')

```

4522 \def\Setzen #1&{%
4523     \ifx #1\relax \let\NEXT=\relax
4524     \else \step1@dcowcount%
4525         \let\tabelskip=\l@dcowwidth
4526         \EDTAB #1|
4527     \let\NEXT=\Setzen
4528     \fi\NEXT}
4529

```

`\EDATAB` (was `\ATAB`)

```

4530 \def\EDATAB #1\{%
4531     \ifx #1\Relax \centerline{\Setzen #1\relax&}
4532     \let\Next\relax
4533     \else \centerline{\Setzen #1&\relax&}
4534     \let\Next=\EDATAB
4535     \fi\Next}

```

`\edatab` (was `\atab`)

```

4536 \newcommand{\edatab}[1]{%
4537     \variab%
4538     \EDATAB #1\\Relax\\}
4539

```

`\HILFSskip` More helpers.

```

\Hilfsskip 4540 \newskip\HILFSskip
4541 \newskip\Hilfsskip
4542

```



```
edarrayl The ‘environment’ forms for \ltab, \ctab and \rtab.  
edarrayc 4580 \newenvironment{edarrayl}{\l@dcollect@body\ltab}{  
edarrayr 4581 \newenvironment{edarrayc}{\l@dcollect@body\ctab}{  
         4582 \newenvironment{edarrayr}{\l@dcollect@body\rtab}{  
         4583
```

```

edtabularl The 'environment' forms for \ltabtext, \ctabtext and \rtabtext.
edtabularc 4584 \newenvironment{edtabularl}{\l@dcollect@body\ltabtext}{}
edtabularr 4585 \newenvironment{edtabularc}{\l@dcollect@body\ctabtext}{}
4586 \newenvironment{edtabularr}{\l@dcollect@body\rtabtext}{}
4587

```

```

\usingcritext  Declarations for using \critext{}.../ or using \edtext{}{} inside tabulars.
\disablel@dtabfeet  The default at this point is for \edtext.
\enablel@dtabfeet 4588 \newcommand{\usingcritext}{%
    \usingedtext 4589 \def\disablel@dtabfeet{\l@dmodforcritext}%
    4590 \def\enablel@dtabfeet{\l@drestoreforcritext}}
    4591 \newcommand{\usingedtext}{%
    4592 \def\disablel@dtabfeet{\l@dmodforedtext}%
    4593 \def\enablel@dtabfeet{\l@drestoreforedtext}}
    4594
    4595 \usingedtext
    4596

```

40.1 Deprecated commands

```

\initnumbering@sectcmd \initnumbering@sectcmd defines \ledxxx commands. These commands are dep-
\ledsection          recated. It also defines quotation environment. Note: this assumes that the user
\ledsection*         didn't change \chapter. If he did, he should redefine \initnumbering@sectcmd.
\ledsubsection 4597 \newcommand{\initnumbering@sectcmd}{
\ledsubsection* 4598 \newcommand{\ledsection}[2] [] {%
\ledsubsubsection 4599 \led@war@ledxxxDeprecated{section}%
\ledsubsubsection* 4600 \leavevmode\pend\vspace{3.5ex \@plus 1ex \@minus .2ex}\ifl@dpairing\else\skipnumbe
\ledchapter 4601 \pstart%
\ledchapter* 4602 \leavevmode\ifledsecnolinenummer\skipnumbering\fi\section{##1}{##2}\leavevmode\vsp
\@patchforledchapter 4603 \vspace{-2\parskip}\vspace{-2\baselineskip}%
\quotation 4604 \ifautopar\else\pstart\fi
\endquotation 4605 }
\endquotation 4606 \WithSuffix\newcommand\ledsection*[1]{%
\quote 4607 \led@war@ledxxxDeprecated{section}%
\endquote 4608 \leavevmode\pend\vspace{3.5ex \@plus 1ex \@minus .2ex}\ifl@dpairing\else\skipnumbe

```



```

4609     \pstart%
4610     \leavevmode\ifledsecnolinenumber\skipnumbering\fi\section*{##1}\leavevmode\vspace{2.3ex \@plus
4611     \vspace{-2\parskip}\vspace{-2\baselineskip}%
4612     \ifautopar\else\pstart\fi
4613 }
4614 \newcommand{\ledsubsection}[2][]{%
4615     \led@war@ledxxxDeprecated{subsection}%
4616     \leavevmode\pend\vspace{3.5ex \@plus 1ex \@minus .2ex}\ifl@dpairing\else\skipnumbering\fi%
4617     \pstart%
4618     \leavevmode\ifledsecnolinenumber\skipnumbering\fi\subsection[##1]{##2}\leavevmode\vspace{1.5ex \@plus
4619     \vspace{-2\parskip}\vspace{-2\baselineskip}%
4620     \ifautopar\else\pstart\fi
4621 }
4622 \WithSuffix\newcommand\ledsubsection*[1]{%
4623     \led@war@ledxxxDeprecated{subsection*}%
4624     \leavevmode\pend\vspace{3.5ex \@plus 1ex \@minus .2ex}\ifl@dpairing\else\skipnumbering\fi%
4625     \pstart%
4626     \leavevmode\ifledsecnolinenumber\skipnumbering\fi\subsection*{##1}\leavevmode\vspace{1.5ex \@plus
4627     \vspace{-2\parskip}\vspace{-2\baselineskip}%
4628     \ifautopar\else\pstart\fi
4629 }
4630 \newcommand{\ledsubsubsection}[2][]{%
4631     \led@war@ledxxxDeprecated{subsubsection}%
4632     \leavevmode\pend\vspace{3.5ex \@plus 1ex \@minus .2ex}\ifl@dpairing\else\skipnumbering\fi%
4633     \pstart%
4634     \leavevmode\ifledsecnolinenumber\skipnumbering\fi\subsubsection[##1]{##2}\leavevmode\vspace{1.5ex \@plus
4635     \vspace{-2\parskip}\vspace{-2\baselineskip}%
4636     \ifautopar\else\pstart\fi
4637 }
4638 \WithSuffix\newcommand\ledsubsubsection*[1]{%
4639     \led@war@ledxxxDeprecated{subsubsection*}%
4640     \leavevmode\pend\vspace{3.5ex \@plus 1ex \@minus .2ex}\ifl@dpairing\else\skipnumbering\fi%
4641     \pstart%
4642     \leavevmode\ifledsecnolinenumber\skipnumbering\fi\subsubsection*{##1}\leavevmode\vspace{1.5ex \@plus
4643     \vspace{-2\parskip}\vspace{-2\baselineskip}%
4644     \ifautopar\else\pstart\fi
4645 }
4646 \newcommand\ledchapter[2][]{%
4647     \led@war@ledxxxDeprecated{chapter}%
4648     \ifl@dmemoir%
4649     \gdef\ch@pt@c{##1}%
4650     \fi%
4651     ~\pend\skipnumbering%
4652     \pstart%
4653     \@patchforledchapter\chapter[##1]{##2}%
4654     \pend\pstart}
4655 \WithSuffix\newcommand\ledchapter*[1]{%
4656     \led@war@ledxxxDeprecated{chapter*}%
4657     ~\pend\skipnumbering%
4658     \pstart%

```

```

4659     \@patchforledchapter\chapter*{##1}\pend%
4660     \pstart}
4661 \def\@patchforledchapter{
4662     \patchcmd{\@makeschapterhead}{1\par}{1}{-}{-}
4663     \pretocmd{\@makeschapterhead}{\par}{-}{-}
4664     \apptocmd{\@makeschapterhead}{\par}{-}{-}
4665     \patchcmd{\@makeschapterhead}{\vskip 40\p@}{-}{-}{-}
4666     \patchcmd{\@makechapterhead}{1\par}{1}{-}{-}
4667     \pretocmd{\@makechapterhead}{\par}{-}{-}
4668     \apptocmd{\@makechapterhead}{\par}{-}{-}
4669     \patchcmd{\@makechapterhead}{\vskip 40\p@}{-}{-}{-}
4670     \apptocmd{\@chapter}{\par\leavevmode\vspace{40 \p@}\skipnumbering}{-}{-}
4671     \apptocmd{\@schapter}{\par\leavevmode\vspace{40 \p@}\skipnumbering}{-}{-}
4672     \newcommand\beforeledchapter{\pend\cleardoublepage\pstart}
4673     \patchcmd{\chapter}{\cleardoublepage}{\relax}{-}{-}
4674     \patchcmd{\chapter}{\clearpage}{\relax}{-}{-}
4675 }
4676 \ifnoquotation@else
4677 \renewcommand{\quotation}{\par\leavevmode%
4678     \parindent=1.5em%
4679     \skipnumbering%
4680     \ifautopar%
4681         \vskip-\parskip%
4682     \else%
4683         \vskip\topsep%
4684     \fi%
4685     \global\leftskip=\leftmargin%
4686     \global\rightskip=\leftmargin%
4687 }
4688 \renewcommand{\endquotation}{\par%
4689     \global\leftskip=0pt%
4690     \global\rightskip=0pt%
4691     \leavevmode%
4692     \skipnumbering%
4693     \ifautopar%
4694         \vskip-\parskip%
4695     \else%
4696         \vskip\topsep%
4697     \fi%
4698 }
4699 \renewcommand{\quote}{\par\leavevmode%
4700     \parindent=0pt%
4701     \skipnumbering%
4702     \ifautopar%
4703         \vskip-\parskip%
4704     \else%
4705         \vskip\topsep%
4706     \fi%
4707     \global\leftskip=\leftmargin%
4708     \global\rightskip=\leftmargin%

```

```

4709 }
4710 \renewcommand{\endquote}{\par%
4711     \global\leftskip=0pt%
4712     \global\rightskip=0pt%
4713     \leavevmode%
4714     \skipnumbering%
4715     \ifautopar%
4716         \vskip-\parskip%
4717     \else%
4718         \vskip\topsep%
4719     \fi%
4720 }
4721 \fi
4722 }

```

`\ledsectnotoc` The `\ledsectnotoc` only disables the `\addcontentsline` macro.

```

4723 \newcommand{\ledsectnotoc}{\let\addcontentsline\@gobblethree}

```

`\ledsectnomark` The `\ledsectnomark` only disables the `\chaptermark`, `\sectionmark` and `\subsectionmark` macros.

```

4724 \newcommand{\ledsectnomark}{%
4725     \let\chaptermark\@gobble%
4726     \let\sectionmark\@gobble%
4727     \let\subsectionmark\@gobble%
4728 }

```

40.2 New commands : `\eledxxx`

The new system of `\eledxxx` commands to section text work like this:

- When one of these commands is called, `eledmac` writes to an auxiliary files:
 - The section level.
 - The section title.
 - The side (when `eledpar` is used).
 - The `pstart` where the command is called.
 - If we have starred version or not.
- `eledmac` adds the title of the section to `pstart`, as normal content. This is to enable critical notes.
- When \LaTeX is run a other time, this file is read. That:
 - Adds the `pstart` number to a list of `pstarts` where a sectioning command is used.
 - Defines a command, the name of which contains the `pstart` number, and which calls the normal \LaTeX sectioning command.

4. This last command is called when the pstart is effectively printed.

`\beforeeledchapter` For technical reasons, not yet solved, page-breaking before chapters can't be made automatically by `eledmac`. Users have to use `\beforeeledchapter`.

```
4729 \ifl@dmemoir
4730   \newcommand\beforeeledchapter{\clearforchapter}
4731 \else
4732   \newcommand\beforeeledchapter{\if@openright\cleardoublepage\else\clearpage\fi}
4733 \fi
```

`\if@eled@sectioning` The boolean `\if@eled@sectioning` is set to true when a sectioning command is called by a `\eledxxx` command, and set to false after. It is used to enable/disable line number printing.

```
4734 \newif\if@eled@sectioning
```

`\print@leftmargin@eledsection` `\print@leftmargin@eledsection` and `\print@rightmargin@eledsection` are added by `eledmac` inside the code of sectioning command, in order to affix line numbers. They include tests for RTL languages.

```
4735 \def\print@rightmargin@eledsection{%
4736   \if@eled@sectioning%
4737     \begingroup%
4738     \if@RTL%
4739       \let\llap\rlap%
4740       \let\leftlinenum\rightlinenum%
4741       \let\leftlinenumR\rightlinenumR%
4742       \let\l@dld@ta\l@dld@ta%
4743       \let\l@dlsn@te\l@dlsn@te%
4744     \fi%
4745     \hfill\l@dld@ta \csuse{LR}{\l@dlsn@te}%
4746     \endgroup%
4747   \fi%
4748 }%
4749
4750 \def\print@leftmargin@eledsection{%
4751   \if@eled@sectioning%
4752     \leavevmode%
4753     \begingroup%
4754     \if@RTL%
4755       \let\rlap\llap%
4756       \let\rightlinenum\leftlinenum%
4757       \let\rightlinenumR\leftlinenumR%
4758       \let\l@dld@ta\l@dld@ta%
4759       \let\l@dlsn@te\l@dlsn@te%
4760     \fi%
4761     \l@dld@ta\csuse{LR}{\l@dlsn@te}%
4762     \endgroup%
4763   \fi%
4764 }%
4765
```

`\chapter` We have to patch L^AT_EX, book and memoir sectioning commands in order to:

`\M@sect`

- Disable `\edtext` inside.

`\@mem@old@ssect`

`\@makechapterhead`

- Disable page breaking (for `\chapter`).

`\@makechapterhead`

`\@makeschapterhead`

- Add line numbers and sidenotes.

`\@sect`

`\@ssect`

Unfortunately, Maïeul Rouquette was not able to try if memoir is loaded. That is why `eledmac` tries to define for both standard class and memoir class.

```

4766 \catcode'\#12 % Space NEEDS by \catcode
4767 \AtBeginDocument{%
4768 \patchcmd{\chapter}{\clearforchapter}{%
4769 \if@eled@sectioning\else%
4770 \clearforchapter
4771 \fi%
4772 }
4773 {}
4774 {}
4775
4776 \pretocmd{\M@sect}
4777 {\let\old@edtext=\edtext%
4778 \let\edtext=\dummy@edtext@showlemma%
4779 }
4780 {}
4781 {}
4782
4783 \apptocmd{\M@sect}
4784 {\let\edtext=\old@edtext}
4785 {}
4786 {}
4787
4788 \patchcmd{\M@sect}
4789 { #9}
4790 { #9%
4791 \print@rightmargin@eledsection%
4792 }
4793 {}
4794 {}
4795
4796 \patchcmd{\M@sect}
4797 {\hskip #3\relax}
4798 {\hskip #3\relax%
4799 \print@leftmargin@eledsection%
4800 }
4801 {}
4802 {}
4803
4804 \pretocmd{\@mem@old@ssect}
4805 {\let\old@edtext=\edtext%
```

```

4806 \let\edtext=\dummy@edtext@showlemma%
4807 }
4808 {}
4809 {}
4810
4811 \apptocmd{\@mem@old@ssect}
4812 {\let\edtext=\old@edtext}
4813 {}
4814 {}
4815
4816 \patchcmd{\@mem@old@ssect}
4817 {#5}
4818 {#5%
4819 \print@leftmargin@eledsection%
4820 }
4821 {}
4822 {}
4823
4824 \patchcmd{\@mem@old@ssect}
4825 {\hskip #1}
4826 {\hskip #1%
4827 \print@rightmargin@eledsection%
4828 }
4829 {}
4830 {}
4831
4832 \patchcmd{\chapter}{\if@openright\cleardoublepage\else\clearpage\fi}{%
4833 \if@eled@sectioning\else%
4834 \if@openright\cleardoublepage\else\clearpage\fi}%No clearpage inside a \eledsection : v
4835 \fi%
4836 }%
4837 {}%
4838 {}%
4839
4840 \patchcmd{\@makechapterhead}
4841 {#1}
4842 {\print@leftmargin@eledsection%
4843 #1%
4844 \print@rightmargin@eledsection%
4845 }
4846 {}
4847 {}
4848
4849 \patchcmd{\@makechapterhead}% For BIDI
4850 {\if@RTL\raggedleft\else\raggedright\fi}%
4851 {\if@eled@sectioning\else%
4852 \if@RTL\raggedleft\else\raggedright\fi%
4853 \fi%
4854 }%
4855 {}%

```

```

4856 {}%
4857
4858 \patchcmd{\@makeschapterhead}
4859   {#1}
4860   {\print@leftmargin@eledsection%
4861     #1%
4862     \print@rightmargin@eledsection%
4863   }
4864 {}
4865 {}
4866
4867 \pretocmd{\@sect}
4868   {\let\old@edtext=\edtext
4869     \let\edtext=\dummy@edtext@showlemma%
4870   }
4871 {}
4872 {}
4873
4874 \apptocmd{\@sect}
4875   {\let\edtext=\old@edtext}
4876 {}
4877 {}
4878
4879 \patchcmd{\@sect}
4880   {#8}
4881   {#8%
4882     \print@rightmargin@eledsection%
4883   }
4884 {}
4885 {}
4886
4887 \patchcmd{\@sect}
4888   {\hskip #3\relax}
4889   {\hskip #3\relax%
4890     \print@leftmargin@eledsection%
4891   }
4892 {}
4893 {}
4894
4895 \pretocmd{\@ssect}
4896   {\let\old@edtext=\edtext%
4897     \let\edtext=\dummy@edtext@showlemma%
4898   }
4899 {}
4900 {}
4901
4902 \apptocmd{\@ssect}
4903   {\let\edtext=\old@edtext}
4904 {}
4905 {}

```

```

4906
4907 \patchcmd{\@ssect}
4908   {\#5}
4909   {\#5%
4910   \print@rightmargin@eledsection%
4911   }
4912   {}
4913   {}
4914
4915 \patchcmd{\@ssect}
4916   {\hskip #1}
4917   {\hskip #1%
4918   \print@leftmargin@eledsection%
4919   }
4920   {}
4921   {}
4922 }%
4923 \catcode'\#=#6 %Space NEEDS by \catcode

\eled@sectioning@out  \eled@sectioning@out is the output file, to dump the pstarts where a sectioning
                      command is used.
4924 \newwrite\eled@sectioning@out

\noeledsec  The boolean \if@noeled@sec is set to true when \noeledsec is called. It is used
\if@noeled@sec  to disable external file creation.
4925 \newif\if@noeled@sec%
4926 \newcommand{\noeledsec}{\global\@noeled@sectrue}%

\eledchapter  And now, the user sectioning commands, which write to the file, and also add
\eledsection  content as a "normal" line.
\eledsubsection 4927 \newcommand{\eledchapter}[2] [] {%
\eledsubsubsection 4928   #2%
\eledchapter* 4929   \ifledRcol%
\eledsection* 4930     \immediate\write\eled@sectioningR@out{%
\eledsubsection* 4931       \string\eled@chapter{#1}{\unexpanded{#2}}{\the\l@dnumpstartsR}{R}
\eledsubsubsection* 4932       }%
4933   \else%
4934     \immediate\write\eled@sectioning@out{%
4935       \string\eled@chapter{#1}{\unexpanded{#2}}{\the\l@dnumpstartsL}{L}
4936       }%
4937   \fi%
4938 }
4939
4940 \newcommand{\eledsection}[2] [] {%
4941   #2%
4942   \ifledRcol%
4943     \immediate\write\eled@sectioningR@out{%
4944       \string\eled@section{#1}{\unexpanded{#2}}{\the\l@dnumpstartsR}{R}
4945       }%

```



```

4946 \else%
4947 \immediate\write\eled@sectioning@out{%
4948 \string\eled@section{#1}{\unexpanded{#2}}{\the\l@dumpstartsL}{-}{-}
4949 }%
4950 \fi%
4951 }
4952
4953 \newcommand{\eledsubsection}[2][{}]{%
4954 #2%
4955 \ifledRcol%
4956 \immediate\write\eled@sectioningR@out{%
4957 \string\eled@subsection{#1}{\unexpanded{#2}}{\the\l@dumpstartsR}{-}{R}
4958 }%
4959 \else%
4960 \immediate\write\eled@sectioning@out{%
4961 \string\eled@subsection{#1}{\unexpanded{#2}}{\the\l@dumpstartsL}{-}{-}
4962 }%
4963 \fi%
4964 }
4965 \newcommand{\eledsubsubsection}[2][{}]{%
4966 #2%
4967 \ifledRcol%
4968 \immediate\write\eled@sectioningR@out{%
4969 \string\eled@subsubsection{#1}{\unexpanded{#2}}{\the\l@dumpstartsR}{-}{R}
4970 }%
4971 \else%
4972 \immediate\write\eled@sectioning@out{%
4973 \string\eled@subsubsection{#1}{\unexpanded{#2}}{\the\l@dumpstartsL}{-}{-}
4974 }%
4975 \fi%
4976 }
4977
4978
4979 \WithSuffix\newcommand\eledchapter*[2][{}]{%
4980 #2%
4981 \ifledRcol%
4982 \immediate\write\eled@sectioningR@out{%
4983 \string\eled@chapter{#1}{\unexpanded{#2}}{\the\l@dumpstartsR}{*}{R}
4984 }%
4985 \else%
4986 \immediate\write\eled@sectioning@out{%
4987 \string\eled@chapter{#1}{\unexpanded{#2}}{\the\l@dumpstartsL}{*}{-}
4988 }%
4989 \fi%
4990 }
4991
4992 \WithSuffix\newcommand\eledsection*[2][{}]{%
4993 #2%
4994 \ifledRcol%
4995 \immediate\write\eled@sectioningR@out{%

```

```

4996     \string\eled@section{#1}{\unexpanded{#2}}{\the\l@dnumpstartsR}{*}{R}
4997     }%
4998   \else%
4999     \immediate\write\eled@sectioning@out{%
5000       \string\eled@section{#1}{\unexpanded{#2}}{\the\l@dnumpstartsL}{*}{L}
5001     }%
5002   \fi%
5003 }
5004
5005 \WithSuffix\newcommand\eledsubsection*[2][]{%
5006   #2%
5007   \ifledRcol%
5008     \immediate\write\eled@sectioningR@out{%
5009       \string\eled@subsection{#1}{\unexpanded{#2}}{\the\l@dnumpstartsR}{*}{R}
5010     }%
5011   \else%
5012     \immediate\write\eled@sectioning@out{%
5013       \string\eled@subsection{#1}{\unexpanded{#2}}{\the\l@dnumpstartsL}{*}{L}
5014     }%
5015   \fi%
5016 }
5017
5018 \WithSuffix\newcommand\eledsubsubsection*[2][]{%
5019   #2%
5020   \ifledRcol%
5021     \immediate\write\eled@sectioningR@out{%
5022       \string\eled@subsubsection{#1}{\unexpanded{#2}}{\the\l@dnumpstartsR}{*}{R}
5023     }%
5024   \else%
5025     \immediate\write\eled@sectioning@out{%
5026       \string\eled@subsubsection{#1}{\unexpanded{#2}}{\the\l@dnumpstartsL}{*}{L}
5027     }%
5028   \fi%
5029 }

```

<code>\eled@chapter</code> <code>\eled@section</code> <code>\eled@subsection</code> <code>\eled@subsubsection</code>	<p>The sectioning macros, called in the auxiliary file. They have five arguments:</p> <ol style="list-style-type: none"> 1. Optional arguments of L^AT_EX sectioning command. 2. Mandatory arguments of L^AT_EX sectioning command. 3. Pstart number. 4. Side: R if right, nothing if left. 5. Starred or not.
---	---

```

5030 \def\eled@chapter#1#2#3#4#5{%
5031   \ifstrempy{#4}%
5032   {%
5033     \ifstrempy{#1}%

```

```

5034      {%
5035      \global\csdef{eled@sectioning@#3#5}{\let\edtext=\dummy@edtext@showlemma\chapter{#2}}%
5036      \global\csdef{eled@sectmark@#3#5}{\let\edtext=\dummy@edtext{}\chaptermark{#2}}%
5037      }%Need for \pairs, because of using parbox.
5038      {%
5039      \global\csdef{eled@sectioning@#3#5}{\let\edtext=\dummy@edtext@showlemma\chapter[#1]{#2}}%
5040      \global\csdef{eled@sectmark@#3#5}{\let\edtext=\dummy@edtext{}\chaptermark{#2}}%Need for \pairs
5041      }%
5042      }%
5043      {%
5044      \ifstrempy{#1}%
5045      {\global\csdef{eled@sectioning@#3#5}{\let\edtext=\dummy@edtext@showlemma\chapter*{#2}}}%
5046      {\global\csdef{eled@sectioning@#3#5}{\let\edtext=\dummy@edtext@showlemma\chapter*{#1}{#2}}}%Bug
5047      }%
5048      \listcsadd{eled@sections#500}{#3}%
5049      }
5050 \def\eled@section#1#2#3#4#5{%
5051   \ifstrempy{#4}%
5052   {\ifstrempy{#1}%
5053    {%
5054     \global\csdef{eled@sectioning@#3#5}{\section{#2}}%
5055     \global\csdef{eled@sectmark@#3#5}{\let\edtext=\dummy@edtext{}\sectionmark{#2}}%Need for \pairs
5056     }%
5057     {%
5058     \global\csdef{eled@sectioning@#3#5}{\section[#1]{#2}}%
5059     \global\csdef{eled@sectmark@#3#5}{\let\edtext=\dummy@edtext{}\sectionmark{#1}}%Need for \pairs
5060     }%
5061     }%
5062     {\ifstrempy{#1}%
5063      {\global\csdef{eled@sectioning@#3#5}{\section*{#2}}}%
5064      {\global\csdef{eled@sectioning@#3#5}{\section*{#1}{#2}}}%Bug in LaTeX!
5065     }
5066     \listcsadd{eled@sections#500}{#3}%
5067     }
5068 \def\eled@subsection#1#2#3#4#5{%
5069   \ifstrempy{#4}%
5070   {\ifstrempy{#1}%
5071    {%
5072     \global\csdef{eled@sectioning@#3#5}{\subsection{#2}}%
5073     \global\csdef{eled@sectmark@#3#5}{\let\edtext=\dummy@edtext{}\csuse{subsectionmark}{#2}}%Need
5074     }%
5075     {%
5076     \global\csdef{eled@sectioning@#3#5}{\subsection[#1]{#2}}%
5077     \global\csdef{eled@sectmark@#3#5}{\let\edtext=\dummy@edtext{}\csuse{subsectionmark}{#1}}%Need
5078     }%
5079     }%
5080     {\ifstrempy{#1}%
5081      {\global\csdef{eled@sectioning@#3#5}{\subsection*{#2}}}%
5082      {\global\csdef{eled@sectioning@#3#5}{\subsection*{#1}{#2}}}%Bug in LaTeX!
5083     }

```

```

5084 \listcsadd{eled@sections#5@@}{#3}%
5085 }
5086 \def\eled@subsubsection#1#2#3#4#5{%
5087   \ifstrempy{#4}%
5088     {\ifstrempy{#1}%
5089       {\global\csdef{eled@sectioning@#3#5}{\subsubsection{#2}}}%
5090       {\global\csdef{eled@sectioning@#3#5}{\subsubsection{#1}{#2}}}%
5091     }%
5092     {\ifstrempy{#1}%
5093       {\global\csdef{eled@sectioning@#3#5}{\subsubsection*{#2}}}%
5094       {\global\csdef{eled@sectioning@#3#5}{\subsubsection*{#1}{#2}}}%Bug in LaTeX!
5095     }
5096 \listcsadd{eled@sections#5@@}{#3}%
5097 }
5098

```

41 Page breaking or no page breaking depending of specific lines

By default, page breaks are automatic. However, the user can define lines which will force page breaks, or prevent page breaks around one specific line. On the first run, the line-list file records the line number of where the page break is being changed (either forced, or prevented). On the next run, page breaks occur either before or after this line, depending on how the user sets the command. The default setting is after the line.

`\normal@page@break` `\normal@page@break` is an etoolbox list which contains the absolute line number of the last line, for each page.

```
5099 \def\normal@page@break{}
```

`\prev@pb` The `\l@prev@pb` macro is a etoolbox list, which contains the lines in which page breaks occur (before or after). The `\l@prev@nopb` macro is a etoolbox list, which contains the lines with NO page break before or after.

```
5100 \def\l@prev@pb{}
```

```
5101 \def\l@prev@nopb{}
```

`\ledpb` The `\ledpb` macro writes the call to `\led@pb` in line-list file. The `\ledpbnum` macro writes the call to `\led@pbnum` in line-list file. The `\lednopb` macro writes the call to `\led@nopb` in line-list file. The `\lednopbnum` macro writes the call to `\led@nopbnum` in line-list file.

```
5102 \newcommand{\ledpb}{\write\linenum@out{\string\led@pb}}
```

```
5103 \newcommand{\ledpbnum}[1]{\write\linenum@out{\string\led@pbnum{#1}}}
```

```
5104 \newcommand{\lednopb}{\write\linenum@out{\string\led@nopb}}
```

```
5105 \newcommand{\lednopbnum}[1]{\write\linenum@out{\string\led@nopbnum{#1}}}
```

`\led@pb` The `\led@pb` adds the absolute line number in the `\prev@pb` list. The `\led@pbnum` adds the argument in the `\prev@pb` list. The `\led@nopb` adds the absolute line
`\led@pbnum`
`\led@nopb`
`\led@nopbnum`

number in the `\prev@nopb` list. The `\led@nopbnum` adds the argument in the `\prev@nopb` list.

```
5106 \newcommand{\led@pb}{\listcsxadd{1@prev@pb}{\the\absline@num}}
5107 \newcommand{\led@pbnum}[1]{\listcsxadd{1@prev@pb}{#1}}
5108 \newcommand{\led@nopb}{\listcsxadd{1@prev@nopb}{\the\absline@num}}
5109 \newcommand{\led@nopbnum}[1]{\listcsxadd{1@prev@nopb}{#1}}
```

`\ledpbsetting` The `\ledpbsetting` macro only changes the value of `\led@pb@macro`, for which `\led@pb@setting` the default value is `before`.

```
5110 \def\led@pb@setting{before}
5111 \newcommand{\ledpbsetting}[1]{\gdef\led@pb@setting{#1}}
```

`\led@check@pb` The `\led@check@pb` and `\led@check@nopb` are called before or after each line.
`\led@check@nopb` They check if a page break must occur, depending on the current line and on the content of `\l@pb`.

```
5112 \newcommand{\led@check@pb}{\xifinlistcs{\the\absline@num}{1@prev@pb}{\pagebreak[4]}{}}
5113 \newcommand{\led@check@nopb}{%
5114   \IfStrEq{\led@pb@setting}{before}{%
5115     \xifinlistcs{\the\absline@num}{1@prev@nopb}{%
5116       {\numdef{\abs@prevline}{\the\absline@num-1}}%
5117       \xifinlistcs{\abs@prevline}{normal@page@break}{%
5118         {\nopagebreak[4]\enlargethispage{\baselineskip}}%
5119       }%
5120     }%
5121   }%
5122 }%
5123 \IfStrEq{\led@pb@setting}{after}{%
5124   \xifinlistcs{\the\absline@num}{1@prev@nopb}{%
5125     \xifinlistcs{\the\absline@num}{normal@page@break}{%
5126       {\nopagebreak[4]\enlargethispage{\baselineskip}}%
5127     }%
5128 }%
5129 }%
5130 }%
5131 }%
5132 }
```

42 Long verse: prevents being separated by a page break

`\iflednopbinverse` The `\lednopbinverse` boolean is set to false by default. If set to true, `eledmac` will automatically prevent page breaks inside verse. The declaration is made at the beginning of the file, because it is used as a package option.

`\check@pb@in@verse` The `\check@pb@in@verse` checks if a verse is broken in two page. If true, it adds:

- The absolute line number of the first line of the verse -1 in the `\led@pb` list, if the page break must occur before the verse.

- The absolute line number of the first line of the verse -1 in the `\led@nopb` list, if the page break must occur after the verse.

```

5133 \newcommand{\check@pb@in@verse}{%
5134   \ifinstanza\iflednopbinverse\ifinserthangingsymbol% Using stanzas and enabling page b
5135   \ifnum\page@num=\last@page@num\else%If we have change page
5136     \IfStrEq{\led@pb@setting}{before}{%
5137       \numgdef{\abs@line@verse}{\the\absline@num-1}%
5138       \ledpbnum{\abs@line@verse}%
5139     }{}%
5140     \IfStrEq{\led@pb@setting}{after}{%
5141       \numgdef{\abs@line@verse}{\the\absline@num-1}%
5142       \lednopbnum{\abs@line@verse}%
5143     }{}%
5144   \fi%
5145 \fi\fi\fi%
5146 }
```

43 The End

`i/codei`

Appendix A Some things to do when changing version

Appendix A.1 Migration from ledmac to eledmac

In eledmac, some changes were made in the code to allow for easy customization. This can cause problems for people who have made their own customizations. The next sections explain how to correct this.

If you created your own series using `\addfootins` and `\addfootinsX`, you should instead use the `\newseries` command (see 4.6 p.24). You must delete your `\Xfootnote` command.

If you customized the `\XXXXXfmt` command, you should see if commands for display options (4.3 p.18) and options in `\Xfootnote` (4.1 p.16) can't do the same things. If not, you can add a new ticket in Github to request a new function it³⁰.

If for some reason you don't want to make the modifications to use eledmac new functions, you can continue to use your own `\XXXXXfmt` command, but you must replace:

```
\renewcommand*{XXXXfmt}[3]
```

with

```
\renewcommandx*{XXXXfmt}[4][4=Z]
```

If you don't do that, you will see a spurious `[X]`, where X is series letter.

If you used a `\protect` command inside a `\footnote` command inside a numbered section, you must change the `\protect` to `\noexpand`. If you don't, the command after the `\protect` won't be displayed.

Appendix A.2 Migration to eledmac 1.5.1

The version 1.5.1 corrects a bug with `stanzaindentrepitition` (cf. p. 25). This bug had two consequences:

1. `stanzaindentrepitition` didn't work when its value was greater than 2.
2. `stanzaindentrepitition` worked wrong when its value was equal to 2.

So, if you used `stanzaindentrepitition` with value equal to 2, you must change your `\setstanzaindent`. Explanation:

```
\setcounter{stanzaindentrepitition}{2}
\setstanzaindent{5,1,0}
```

³⁰<https://github.com/maieul/ledmac/issues>

This code, in a version older than 1.5.1, made that the first verse had an indent of 0, the second verse of 1, the third verse of 0, the fourth verse of 1 etc.

But instead the code should have assigned the reverse: the first verse had an indent of 1, the second verse of 0, the third verse of 1, the fourth verse of 0 etc.

So version 1.5.1 corrected this bug. If you want to keep the older presentation, you must change:

```
\setcounter{stanzaindentrepetition}{2}
\setstanzaindent{5,1,0}
```

by:

```
\setcounter{stanzaindentrepetition}{2}
\setstanzaindent{5,0,1}
```

Appendix A.3 Migration to **eledmac 1.12.0**

The migration to **eledmac 1.12.0** is easy:

- You must delete all the auxiliary files, and so one, make the normal three runs.
- If you have modified `\l@reg`, which is not advisable, you must rename it to `\@nl@reg`.

Anyway, there is another problem. If you have text in brackets just after `\pstart` or `\pend`, the text will be considered an optional argument of `\pstart` or `\pend` (see 3, p. 11). In this case, just add a `\relax` between `\pstart`/`\pend` and the brackets.

The version 1.12.0 adds new best way to manage section title inside numbered text. Please read § 14 (p. 36).

References

- [Bre96] Herbert Breger. **TABMAC**. October 1996. (Available from CTAN in `macros/plain/contrib/tabmac`)
- [Bur01] John Burt. ‘Typesetting critical editions of poetry’. *TUGboat*, **22**, 4, pp 353–361, December 2001. (Code available from CTAN in `macros/latex/contrib/poemscol`)
- [Eck03] Matthias Eckermann. *The Parallel-Package*. April 2003. (Available from CTAN in `macros/latex/contrib/parallel`)
- [Fai03] Robin Fairbairns. *footmisc — a portmanteau package for customising footnotes in L^AT_EX*. February 2003. (Available from CTAN in `macros/latex/contrib/footmisc`)
- [LW90] John Lavagnino and Dominik Wujastyk. ‘An overview of EDMAC: a PLAIN TeX format for critical editions’. *TUGboat*, **11**, 4, pp. 623–643, November 1990. (Code available from CTAN in `macros/plain/contrib/edmac`)
- [Lüc03] Uwe Lück. ‘ednotes — critical edition typesetting with LaTeX’. *TUGboat*, **24**, 2, pp. 224–236, 2003. (Code available from CTAN in `macros/latex/contrib/ednotes`)
- [Sul92] Wayne G. Sullivan. *The file edstanza.doc*. June 1992. (Available from CTAN in `macros/plain/contrib/edmac`)
- [Wil02] Peter Wilson. *The memoir class for configurable typesetting*. November 2002. (Available from CTAN in `macros/latex/contrib/memoir`)
- [Wil04] Peter Wilson and Maïeul Rouquette. *Parallel typesetting for critical editions: the eledpar package*. December 2004. (Available from CTAN in `macros/latex/contrib/ledmmac`)

Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

Symbols		3841, 3842, 3892, 3907, 3928, 3930
<code>\#</code> 4766, 4923	<code>\@@ledleftnote</code> 3970, 3978
<code>\&</code> 21, 3837,	<code>\@@ledrightnote</code> 3969, 3977

- \@ledsidenote 3971, 3979
- \@oline 1820
- \@wrindexm@m ... 3669, 3671, 3674,
3681, 3683, 3686, 3691, 3693, 3696
- \@EDROWFILL@ 4162, 4377
- \@M 1820, 3885, 3897
- \@MM 1471
- \@adv 570, 784
- \@arabic 933
- \@auxout .. 3145, 3668, 3670, 3673,
3680, 3682, 3685, 3690, 3692, 3695
- \@botlist 3098, 3100
- \@cclv 3003, 3007, 3008, 3096, 3097, 3125
- \@chapter 4670
- \@checkend 3818
- \@colht 2984, 3101, 3113
- \@colroom 3101
- \@combinefloats 2979
- \@currentlabel
..... 969, 2058, 2182, 2249, 2366
- \@currenvir 3802, 3805, 3806
- \@currlist 3102, 3105
- \@dbldeferlist 3111, 3116, 3118
- \@dblfloatplacement 3115
- \@dbltoplist 3111, 3112
- \@deferlist 3098, 3107, 3108
- \@doclearpage 3085
- \@edindex@fornote@true 3626
- \@edindex@hyperref 3714, 3761
- \@edrowfill@ 4377
- \@ehb 3104
- \@ehd 165, 168
- \@eled@sectioningfalse 1069
- \@eled@sectioningtrue 1067
- \@emptytoks 3793, 3803
- \@fnpos 2455, 3021, 3024
- \@footnotemark 1987
- \@footnotetext
..... 1983, 2000, 3525, 3561, 3590
- \@freelist 2977
- \@gobble 817, 818, 2514, 3815,
3972–3974, 4141, 4152, 4725–4727
- \@gobblefour 170, 2687
- \@gobblethree 170, 4723
- \@h 1818
- \@hilfs@count 4077
- \@idxfile . 3658, 3669, 3671, 3674,
3681, 3683, 3686, 3691, 3693, 3696
- \@ifclassloaded
..... 44, 1982, 3052, 3077, 3743
- \@ifnextchar 3648, 4062
- \@ifpackageloaded
..... 47, 2999, 3605, 3608, 3744
- \@iiiminipage 3514
- \@iiiparbox 3541
- \@index@command
. 3630, 3632–3634, 3637–3639,
3710, 3711, 3720, 3723, 3773, 3777
- \@index@command@ 3633, 3634, 3638, 3639
- \@index@parenthesis
..... 3631, 3635, 3640, 3772, 3776
- \@index@txt 3629,
3710, 3711, 3714, 3720, 3723, 3790
- \@indexfile 3719, 3722, 3726
- \@inputcheck 464
- \@insert 1357–1359, 1393–1395
- \@k 1818
- \@kludgeins 2981, 3049
- \@l@dttempcnta .. 174, 604, 606, 608,
609, 1140, 1141, 1143, 1145,
1148, 1149, 1164, 1200–1204,
1206, 1213–1217, 1219, 1222,
1225, 1227, 1231, 1262, 1266,
1270, 1277, 1281, 1285, 1366,
1370, 1374, 1377, 1380, 1383, 1384
- \@l@dttempcntb
. 174, 323, 324, 329, 333, 337,
341, 344, 367, 368, 375, 379,
383, 385, 393, 394, 1198, 1210,
1231, 1239–1241, 1243, 1262,
1266, 1270, 1277, 1281, 1285,
1315–1317, 1319, 1372, 1373,
3249, 3251, 3253, 3259, 3263,
3267, 3271, 3274, 3361–3363,
3366–3368, 3371, 3379–3381,
3384–3386, 3389, 3450–3452, 3454
- \@lab 687, 3136, 3177
- \@latexerr 3104
- \@led@extranofeet .. 3074, 3083, 3091
- \@led@nofootfalse 3087–3089
- \@led@nofoottrue 3086
- \@led@testifnofoot 3085
- \@ledgroupfalse 3570, 3599
- \@ledgrouptrue 3560, 3588
- \@line@@num 4073, 4171
- \@listdepth 3527
- \@lock . 227, 444, 518, 520, 522, 535,
637, 638, 640, 641, 657, 658,
660, 1040, 1110, 1170, 1172,
1173, 1175, 1274, 1289, 1291, 1293

- \@lopL 554
 - \@lopR 554
 - \@makechapterhead .. 4666–4669, 4766
 - \@makecol 3056
 - \@makefcolumn .. 3107, 3108, 3116, 3118
 - \@makeschapterhead .. 4662–4665, 4766
 - \@makespecialcolbox 2982
 - \@maxdepth 2997, 3006
 - \@mem@extranofeet 3078
 - \@mem@nofootfalse 3079, 3080
 - \@mem@old@ssect 4766
 - \@midlist 2977, 2978
 - \@minipagefalse 3538
 - \@minipagerestore 3528
 - \@minus 2607, 2608,
4600, 4608, 4616, 4624, 4632, 4640
 - \@mpargs 3518, 3541
 - \@mpfn 3524, 3560, 3589
 - \@mpfnpos 2455, 3474, 3477
 - \@mpfootins 3534,
3544, 3550, 3552, 3556, 3566, 3595
 - \@mpfootnotetext ... 3525, 3561, 3590
 - \@mplistdepth 3527
 - \@nameuse 400, 402, 1476,
1477, 1614, 1721, 1722, 1767,
1875, 1943, 2030, 2034, 2036,
2045, 2048, 2049, 2055, 2059,
2063, 2067, 2090, 2095, 2115,
2127, 2133, 2179, 2183, 2193,
2201, 2246, 2250, 2260, 2268,
2330, 2344, 2352, 2353, 2358,
2367, 2371, 2384, 2489, 2490,
2492, 2493, 2498, 3064, 3065,
3067, 3068, 3070, 3072, 3498, 3500
 - \@next@page 728, 729
 - \@nl .. 493, 729, 731, 733, 740, 744, 747
 - \@nl@reg 493
 - \@nobreakfalse 943, 1066
 - \@nobreaktrue 941, 945, 1066
 - \@noeled@ssectrue 4926
 - \@noneed@Footnotefalse 884
 - \@noneed@Footnotetrue 2680
 - \@nowrindex 3657
 - \@oldnobreak 941, 943, 997
 - \@opcol 3108, 3126
 - \@opxtrafeetii 3033, 3034, 3063
 - \@outputbox
2472, 2473, 2487, 2488, 2984,
2986, 2987, 3003, 3005, 3031, 3032
 - \@outputpage 3117
 - \@parboxrestore 1481, 2053, 3523
 - \@patchforledchapter 4597
 - \@pboxswfalse 3516
 - \@pend 554
 - \@pendR 554
 - \@plus 1492,
2189, 2256, 2607, 2608, 4600,
4602, 4608, 4610, 4616, 4618,
4624, 4626, 4632, 4634, 4640, 4642
 - \@ref 672, 755, 764
 - \@ref@reg 674
 - \@reinserts 3057
 - \@schapter 4671
 - \@sect 4766
 - \@series 458, 462,
2475, 2480, 2564, 2566, 2695,
2704, 2705, 2716, 2718, 2742,
2756, 3036, 3043, 3082, 3090,
3484, 3505, 3510, 3513, 3959,
3965, 4139, 4144, 4150, 4155, 4170
 - \@set 585, 789
 - \@setminipage 3529
 - \@showidx 3665
 - \@ssect 4766
 - \@startstanza 3887
 - \@stopstanza 3887
 - \@tag 825, 842, 865, 908, 2009
 - \@tempboxa 3096, 3097, 3519, 3541
 - \@tempdima 3007, 3517, 3521
 - \@templ@d 3440, 3442
 - \@templ@n 3441, 3442
 - \@textbottom 2989
 - \@texttop 2985
 - \@toplist 3098, 3099
 - \@whilenum 4352
 - \@whilesw 3108, 3117
 - \@wredindex 3704, 4069
 - \@x@sf 1976, 1979, 1990, 1996, 2020, 2026
 - \@xloop 1391, 1398
 - \@xympar 3237
 - ^ 487
 - _ 3765, 3767, 4385, 4390, 4398
- A**
- \abs@line@verse 5137, 5138, 5141, 5142
 - \abs@prevline 5116, 5117
 - \absline@num 221, 443,
498, 501, 504, 551, 599, 602,

- 611, 625, 647, 669, 679, 726,
727, 736, 738, 1101, 1122, 1123,
1131, 1356, 5106, 5108, 5112,
5115, 5116, 5124, 5125, 5137, 5141
Abu Kamil Shuja' b. Aslam 5
\actionlines@list
. 446, 470, 473, 480, 599,
602, 611, 625, 647, 669, 1153, 1156
\actions@list
. 446, 474, 481, 600, 609, 613,
615, 627, 636, 649, 656, 670, 1157
\add@inserts 1056, 1064, 1345
\add@inserts@next 1345
\add@penalties 1061, 1366
\addcontentsline 4723
\addfootins 3060
\addfootinsX 2483
\addtocounter 998
\addtol@denvbody . . . 3797, 3819, 3821
Adelard II 4
\advancelabel@refs 3142, 3150
\advanceline . . . 10, 81, 84, 784, 807, 818
\advancepageno 2972
\Aendnote 12
\affixline@num 1046, 1192
\affixpstart@num 1054, 1304
\affixside@note 1056, 1064, 3418, 3427
\Afootnote 12
\afterlemmaseparator 16
\afternote 18
\afternumberinfootnote 15
\afterruleX 18
\aftersymmlinenumber 15
\afterXrule 18
\allowbreak 1868, 1932, 2194, 2261
\ampersand 23, 3837, 3930
\appto 3433, 3434
\apptocmd 4664, 4668,
4670, 4671, 4783, 4811, 4874, 4902
\AtBeginDocument 2999, 3173, 3606, 4767
\autopar 7, 102, 270, 1007
\autopar@pausetrue 266
\autoparfalse 256, 1008
\autopartrue 1021
- B**
- \ballast 35
\ballast@count . . 1117, 1120, 1125, 1366
Beeton, Barbara Ann Neuhaus Friend 8
\beforeeledchapter 4729
\beforeeledchapter 4672
\beforelemmaseparator 16
\beforenotesX 18
\beforenumberinfootnote 15
\beforesymmlinenumber 15
\beforeXnotes 18
\beginnumbering 6, 189, 287, 948, 1018
\beginnumberingR 1013
\Bendnote 12
\Bfootnote 12
\bfseries 933
\hooknoteX 17
\hookXendnote 17
\hookXnote 17
\body 1399, 1400, 3839, 3929
\bodyfootmarkA 28
\box . . . 1093, 1095, 1716, 1731, 1800,
1819, 2348, 2362, 3003, 3097, 3125
\boxlinenum 15
\boxmaxdepth 3006
\boxsymmlinenumber 16
Bredon, Simon 4
Breger, Herbert 2, 5, 176
Brey, Gerhard 4, 5
\brokenpenalty 1003
Burt, John 3
Busard, Hubert L. L. 4
\bypage@false 291, 305, 311
\bypage@true 291, 299
\bypstart@false 291, 300, 312
\bypstart@true 291, 306
- C**
- \c@addcolcount 4346
\c@ballast 1117, 1125
\c@firstlinenum
. 350, 1212, 1214, 1217, 1219
\c@firstsublinenum
. 354, 1199, 1201, 1204, 1206
\c@labidx 3611
\c@linenumincrement . . 350, 1215, 1216
\c@mpfootnote 3524, 3560, 3589
\c@page 731,
733, 739, 742, 744, 747, 3295, 3303
\c@pstart 933, 3146
\c@sublinenumincrement 354, 1202, 1203
\Cendnote 12
\centerline 4282, 4287,
4293, 4298, 4304, 4309, 4531, 4533
\Cfootnote 12

- \ch@ck@l@ck 1229, 1258
- \ch@cksub@l@ck 1208, 1258
- \ch@pt@c 4649
- \changes 2723, 2726, 2727, 3425
- \chapter 4653, 4659, 4673,
4674, 4766, 5035, 5039, 5045, 5046
- \chaptermark 4725, 5036, 5040
- \char 3837
- \chardef 2559, 3839, 3841
- \check@pb@in@verse 1045, 5133
- Chester, Robert of 4
- Claassens, Geert H. M. 5
- class 1 feet 129, 146
- class 2 feet 146, 147
- \cleaders 4341
- \cleardoublepage
. 4672, 4673, 4732, 4832, 4834
- \clearforchapter 4730, 4768, 4770
- \closeout 258, 706, 712, 715, 719, 2503
- \clubpenalty 1003, 1370
- \color@begingroup
1482, 1727, 2054, 2358, 3010, 3520
- \color@endgroup
1483, 1727, 2055, 2358, 3014, 3539
- \columns@position 208, 209,
280, 281, 2422, 2435, 2445, 2451
- \columnwidth 1480, 1687,
2052, 2314, 2427, 2440, 3522, 3576
- \content
2624, 2664, 2681, 3316, 3331, 3346
- Copernicus, Nicolaus 4
- \count 1655, 1660, 1672, 1678, 1843,
1846, 1912, 1940, 2147, 2152,
2168, 2171, 2236, 2239, 2300, 2305
- \countdef 2972
- \cr 1821, 1824
- \create@edindex@for@memoir 3645, 3745
- \create@edindex@notfor@memoir . .
. 3703, 3745, 3747
- \CRITEXT 4053
- \critext
38, 819, 828, 841, 4055, 4137, 4166
- \cs 829, 834, 838, 1052, 2692,
2710, 2726–2728, 2850, 3421, 3423
- \csdef 4143, 5035,
5036, 5039, 5040, 5045, 5046,
5054, 5055, 5058, 5059, 5063,
5064, 5072, 5073, 5076, 5077,
5081, 5082, 5089, 5090, 5093, 5094
- \csexpandonce 1443, 1454, 2010,
2120, 2636, 2649, 2668, 2684,
3319, 3323, 3334, 3338, 3349, 3353
- \csgdef 1648, 1666, 1832, 1901,
2137, 2158, 2226, 2293, 2570–
2588, 2593, 2595, 2596, 2598–
2600, 2602–2613, 2659, 2676, 2750
- \cslet 2601, 2687
- \csletcs 2691, 3483, 3509,
3953, 3963, 4138, 4149, 4154, 4169
- \csnumdef 983, 985
- \csundef 457, 1070
- \csuse 208, 209, 280,
281, 1068, 1460, 1461, 1478,
1479, 1490, 1496, 1499–1501,
1507, 1593, 1604, 1608, 1626,
1632, 1635, 1656, 1657, 1661,
1662, 1673, 1674, 1679, 1680,
1683, 1696, 1703, 1708, 1709,
1723, 1724, 1742, 1749–1751,
1759, 1760, 1779, 1785, 1791,
1792, 1807, 1809–1811, 1813,
1851, 1856, 1860, 1864–1866,
1870, 1887, 1893, 1895, 1915,
1920, 1924, 1928–1930, 1933,
1934, 1955, 1961, 1963, 2037,
2038, 2045, 2050, 2051, 2062,
2063, 2073, 2085, 2107, 2113,
2119, 2148, 2149, 2153, 2154,
2176, 2186, 2187, 2193, 2196,
2213, 2219, 2244, 2252, 2254,
2260, 2263, 2280, 2286, 2301,
2302, 2306, 2307, 2310, 2323,
2334, 2340, 2341, 2354, 2355,
2371, 2380, 2397, 2403, 2410,
2422, 2435, 2445, 2451, 2461,
2467, 2474, 2479, 2511, 2598,
2599, 2635, 2648, 2654, 2666–
2668, 2736, 2737, 2752, 2753,
2899, 2905, 2916, 2918–2922,
2925, 2926, 2930, 2935, 2939,
2940, 2944, 2949, 2953, 2954,
2959, 2964, 3035, 3042, 3079,
3080, 3088, 3089, 3495, 3503,
3512, 3643, 3644, 3751, 3955,
3956, 4143, 4745, 4761, 5073, 5077
- \csxdef 1422,
1424, 1428, 1430, 1437, 1440,
1443, 1448, 1451, 1454, 1688, 2966
- \ctab 3935, 4490, 4581

- \ctabtext 3939, [4500](#), 4585
- D**
- \dcolerr 4029, 4041
- \dcoli ... 3999, 4031, 4032, 4389, 4394
- \dcolii 4000, 4032
- \dcoliii 4001, 4032
- \dcoliv 4002, 4033
- \dcolix 4007, 4034
- \dcolv 4003, 4033
- \dcolvi 4004, 4033
- \dcolvii 4005, 4034
- \dcolviii 4006, 4034
- \dcolx 4008, 4034
- \dcolxi 4009, 4035
- \dcolxii 4010, 4035
- \dcolxiii 4011, 4035
- \dcolxiv 4012, 4036
- \dcolxix 4017, 4037
- \dcolxv 4013, 4036
- \dcolxvi 4014, 4036
- \dcolxvii 4015, 4037
- \dcolxviii 4016, 4037
- \dcolxx 4018, 4037
- \dcolxxi 4019, 4038
- \dcolxxii 4020, 4038
- \dcolxxiii 4021, 4038
- \dcolxxiv 4022, 4039
- \dcolxxix 4027, 4040
- \dcolxxv 4023, 4039
- \dcolxxvi 4024, 4039
- \dcolxxvii 4025, 4040
- \dcolxxviii 4026, 4040
- \dcolxxx 4028, 4040
- \DeclareOption 12–18
- Dekker, Dirk-Jan 3, 37
- \Dendnote [12](#)
- \Dfootnote [12](#)
- \dimen 775, 776,
778–780, 782, 1656, 1661, 1673,
1679, 1685–1687, 1689, 1826–
1828, 1844, 1847, 1913, 1941,
2148, 2153, 2169, 2172, 2237,
2240, 2301, 2306, 2312–2314, 2317
- \dimen@ 2986, 2988
- \dingdef 3498, 3500, 3550, 3552
- \disable@familiarnotes .. [3951](#), 3983
- \disable@notes [3981](#), 4186,
4205, 4221, 4237, 4252, 4269, 4463
- \disable@sidenotes [3968](#), 3982
- \disable@dtabfeet
..... 4184, 4203, 4219, 4235,
4250, 4267, 4396, 4403, 4408,
4416, 4421, 4429, 4447, 4464, [4588](#)
- \displaystyle 4087, 4187,
4190, 4222, 4225, 4253, 4256,
4396, 4408, 4421, 4511, 4563, 4564
- \displaywidowpenalty 1004
- \divide .. 1202, 1215, 1687, 1827, 2314
- \do@actions 1102, [1129](#)
- \do@actions@fixedcode ... 1150, [1163](#)
- \do@actions@next [1129](#)
- \do@ballast 1103, [1117](#)
- \do@insidelinehook .. 1055, 1081, [1083](#)
- \do@line 986, [1030](#)
- \do@linehook 1034, 1080, [1083](#)
- \do@lockoff [646](#)
- \do@lockoffL [646](#)
- \do@lockon [617](#)
- \do@lockonL [617](#)
- \docsvlist 1418, 2562, 2745, 2759
- \doedindexlabel [3616](#), 3659, 3736, 4066
- \doendnotes [25](#), [2552](#)
- \doinsidelinehook [1080](#)
- \dolinehook [1080](#)
- \dolistloop
.. 458, 462, 2475, 2480, 2704,
2716, 2742, 2756, 3036, 3043,
3082, 3090, 3438, 3458, 3465,
3484, 3505, 3510, 3513, 3959,
3965, 4139, 4144, 4150, 4155, 4170
- \doreinextrafeeti ... [2471](#), 2491, 3038
- \doreinextrafeetii .. 3039, [3041](#), 3066
- \dosplits [1818](#)
- Downes, Michael 36, 107, 109
- \doxtrafeet [3020](#)
- \doxtrafeeti
.... [2471](#), 2486, 3022, 3025, 3026
- \doxtrafeetii .. 3022, 3025, 3026, [3030](#)
- \dp 1472,
1714, 1729, 2346, 2360, 2986, 3007
- \dummy@edtext [811](#), 820,
5036, 5040, 5055, 5059, 5073, 5077
- \dummy@edtext@showlemma
..... [812](#), 4778, 4806,
4869, 4897, 5035, 5039, 5045, 5046
- \dummy@ref [673](#), 683
- \dummy@text [810](#), 819

E

- `\edaftertab` 32, 190, 3941, 4436, 4472, 4490
- `edarrayc` (environment) 29, 4580
- `edarrayl` (environment) 29, 4580
- `edarrayr` (environment) 29, 4580
- `\EDATAB` 4530, 4538
- `\edatab` 3942, 4536
- `\edatabell` 3943, 4520
- `\edatleft` 31, 3944, 4321
- `\edatright` 31, 3945, 4329
- `\edbeforetab` 32, 190, 3940, 4436, 4472, 4490
- `\edfilldimen` 4343, 4353, 4354, 4356, 4379
- `\edfont@info` 899, 902, 906
- `\EDINDEX` 4059
- `\edindex` 28, 3645, 4059, 4140, 4145, 4151, 4156, 4168, 4177, 4196, 4214, 4230, 4245, 4262
- `\edindexlab` 29, 3611, 3617, 3620, 3774, 3778, 3783, 3785
- `\EDLABEL` 4057
- `\edlabel` 25, 817, 3135, 3617, 4057, 4158, 4174, 4176, 4195, 4213, 4229, 4244, 4261, 4395, 4402, 4407, 4415, 4420, 4428
- `\edmakelabel` 26, 3235
- `\edpageref` 25, 3186
- `\edrowfill` . 30, 3948, 4159, 4162, 4377
- `\EDTAB` 4526, 4562
- `\edtabcolsep` 30, 4116, 4191, 4210, 4225, 4241, 4257, 4274, 4354, 4410, 4423, 4432, 4548
- `\EDTABINDENT` 4543, 4556
- `\edtabindent` 4384, 4388, 4393, 4404, 4417, 4430, 4552
- `\EDTABtext` 4570
- `edtabularc` (environment) 29, 4584
- `edtabularl` (environment) 29, 4584
- `edtabularr` (environment) 29, 4584
- `\EDTEXT` 4053
- `\edtext` 11, 820, 863, 2003, 2131, 3291, 3292, 3310, 4053, 4148, 4167, 4777, 4778, 4784, 4805, 4806, 4812, 4868, 4869, 4875, 4896, 4897, 4903, 5035, 5036, 5039, 5040, 5045, 5046, 5055, 5059, 5073, 5077
- `\edvertdots` 32, 3947, 4340
- `\edvertline` 32, 3946, 4338
- `\Eendnote` 12
- `\Efootnote` 12
- `\eled@chapter` 4931, 4935, 4983, 4987, 5030
- `\eled@section` 4944, 4948, 4996, 5000, 5030
- `\eled@sectioning@out` 215, 258, 4924, 4934, 4947, 4960, 4972, 4986, 4999, 5012, 5025
- `\eled@sectioningR@out` 4930, 4943, 4956, 4968, 4982, 4995, 5008, 5021
- `\eled@sections@@` 212, 1047, 1066
- `\eled@subsection` 4957, 4961, 5009, 5013, 5030
- `\eled@subsubsection` 4969, 4973, 5022, 5026, 5030
- `\eledchapter` 4927
- `\eledchapter*` 4927
- `\Eledmac` 2689
- `\eledmac@after@imakeidx@true` .. 3605
- `\eledmac@error` 50, 52, 54, 56, 68, 91, 94, 97, 100, 102, 154, 156, 159, 161, 163, 165, 168
- `\eledmac@warning` 49, 71, 73, 75, 77, 79, 81, 84, 87, 89, 105, 107, 109, 112, 114, 116, 118, 121, 124, 128, 130, 135, 137, 142, 144, 148, 151
- `\eledsection` 4834, 4927
- `\eledsection*` 4927
- `\eledsubsection` 4927
- `\eledsubsection*` 4927
- `\eledsubsubsection` 4927
- `\eledsubsubsection*` 4927
- `\emph` 3643, 3644
- `\empty` 172, 177, 243, 246, 425, 426, 470, 853, 875, 897, 911, 915, 921, 955, 1153, 1211, 1227, 1347–1349, 1360, 1392, 3137, 3852
- `\enablel@dtabfeet` 4444, 4460, 4480, 4488, 4498, 4506, 4588
- `\end@lemmas` ... 809, 853, 854, 875, 876
- `\endashchar` 20, 1504, 1584, 2544
- `\endgraf` 981, 1023, 1027
- `\endline@num` 451, 690, 696
- `\endlock` 10, 799, 816, 3896, 3913, 3921
- `\endminipage` 3531
- `\endnumbering` ... 6, 192, 236, 267, 286
- `\endpage@num` 451, 689, 696

- `\endprint` 25, 2511, 2555
- `\endquotation` 4597
- `\endquote` 4597
- `\endstanzaextra` 23, 3887
- `\endsub` 10, 775, 815
- `\endsubline@num` 451, 691, 697
- `\enlargethispage` 5118, 5126
- `\enskip` 2512
- `\enspace` 2063, 2193, 2260, 2371, 2512
- environments:
 - `edarrayc` 29, 4580
 - `edarrayl` 29, 4580
 - `edarrayr` 29, 4580
 - `edtabularc` 29, 4584
 - `edtabularl` 29, 4584
 - `edtabularr` 29, 4584
 - `ledgroup` 24, 3558
 - `ledgroupsize` 24, 3573
 - `minipage` 24
- Euclid 4
- `\ExecuteOptions` 19
- `\expandonce` 3704
- `\extensionchars` 35, 175, 198, 274
- `\extractendline@` 2890, 2893
- `\extractendsubline@` 2891, 2893
- `\extractline@` 2888, 2893, 2896
- `\extractsubline@` 2889, 2893, 2896
- F**
- `\f@encoding` 906
- `\f@family` 906
- `\f@series` 906
- `\f@shape` 906
- `\f@x@l@cks` 1252, 1258
- Fairbairns, Robin 27
- `\falseverse` 148, 3887
- `\first@linenum@out@false` 701, 707
- `\first@linenum@out@true` 701
- `\firstlinenum` 8, 9, 359
- `\firstseries` 2699
- `\firstsublinenum` 8, 9, 359
- `\fix@page` 494, 540
- `\flag@end` 750,
849, 859, 860, 871, 881, 882, 887
- `\flag@start`
. 750, 848, 849, 860, 870, 871, 882
- `\flagstanza` 23, 3925
- `\floatingpenalty` 1471
- `\flush@notes` 991, 1390, 3491
- `\flush@notesR` 3489
- `\fnpos` 28, 2455
- Folkerts, Menso 4
- `\fontencoding` 1404
- `\fontfamily` 1404
- `\fontseries` 1404
- `\fontshape` 1404
- `\footfootmarkA` 28
- `\footfudgefiddle` 36, 1682, 1687, 2314
- `\footins` 3002, 3009, 3013, 3047, 3087
- `\footnormal` 1638, 2660, 3062
- `\footnormalX` 28, 2136, 2485, 2677
- `\footnote@luatexpardir` 1488
- `\footnote@luatextextdir` 1487, 1509
- `\footnoteA` 27
- `\footnoteB` 27
- `\footnoteC` 27
- `\footnoteD` 27
- `\footnoteE` 27
- `\footnotelang@lua` 1420, 2628, 2641
- `\footnotelang@poly` 1434, 2632, 2645
- `\footnoteoptions@`
. 1407, 2633, 2637, 2646, 2651
- `\footnoterule` 1606, 2087, 3012, 3546
- `\footnotesize` 2875, 3288, 3289
- `\footparagraph` 14, 1665
- `\footparagraphX` 28, 2292
- `\footsplitskips`
. 1462, 1469, 1710, 1725, 1852,
1916, 2039, 2177, 2245, 2342, 2356
- `\footthreecol` 14, 1831
- `\footthreecolX` 28, 2225
- `\foottwocol` 14, 1900
- `\foottwocolX` 28, 2157
- `\foottwocolX` 2157
- `\fullstop` 20, 415, 1504,
1581, 1583, 1585, 1587, 2543, 2547
- G**
- `\g@addto@macro` 2486,
2491, 2494, 2497, 3053, 3054,
3063, 3066, 3069, 3071, 3078, 3646
- Gädeke, Nora 5
- `\get@edindex@hyperref` 3713, 3761
- `\get@index@command`
. 3628, 3709, 3718, 3770, 3781
- `\get@linelistfile` 467, 482
- `\getline@num` 1038, 1100
- `\gl@p` 437, 473, 474, 854, 876, 901,
1156, 1157, 1353, 1357, 1393, 3140
- `\gl@poff` 437, 438

H

`\hangafter` 3883
`\hangindentX` 17
`\hangingsymbol` 22, 23, 3826, 3833
`\hb@xt@` 1055, 1058,
 1093, 1095, 4379, 4384, 4388,
 4393, 4404, 4417, 4430, 4509, 4511
`\hfilneg` 1820
`\Hilfsbox` 3994
`\hilfsbox` 3994, 4049, 4050,
 4087, 4099, 4173, 4187, 4206,
 4222, 4238, 4253, 4270, 4395,
 4397, 4402, 4406, 4407, 4409,
 4415, 4419, 4420, 4422, 4428, 4431
`\hilfscount` 3994, 4547–4549, 4555
`\HILFSskip` 4540
`\Hilfsskip` 4385,
 4389, 4390, 4394, 4397, 4398,
 4405, 4406, 4409–4411, 4418,
 4419, 4422–4424, 4431–4433,
 4540, 4546, 4548, 4554, 4558, 4559
`\hilfsskip`
 . 3994, 4172, 4173, 4190, 4209,
 4225, 4241, 4256, 4273, 4557–4559
`\hsize@fornote` 2418, 2423,
 2426, 2427, 2431, 2436, 2439, 2440
`\hsizethreecol` 17
`\hsizethreecolX` 17
`\hsizetwocol` 17
`\hsizetwocolX` 17
`\Hy@temp@A` 3677, 3678
`\HyInd@ParenLeft` 3678
`\hyperlink`
 3182, 3183, 3750, 3751, 3754, 3762
`\hyperlinkformat` 3748, 3758
`\hyperlinkformatR` 3757
`\hyperlinkR` 3753
`\hyperpage` 3644
`\hypertarget` 3147

I

`\if@edindex@fornote@`
 3623, 3667, 3679, 3689, 3708, 3717
`\if@edindex@fornote@true` 3623
`\if@eled@sectioning`
 4734, 4736, 4751, 4769, 4833, 4851
`\if@fcolmade` 3108, 3117
`\if@firstcolumn` 1233, 1309, 3110, 3444
`\if@led@nofoot` 3074, 3095
`\if@led@group` 711, 3558

`\if@nobreak` 940
`\if@noeled@sec` 213, 257, 4925
`\if@noneed@Footnote` 750
`\if@openright` 4732, 4832, 4834
`\if@RTL` 29, 48, 849,
 860, 871, 882, 1071, 1436, 1447,
 1716, 2045, 4738, 4754, 4850, 4852
`\ifautopar` 266, 959,
 1007, 4604, 4612, 4620, 4628,
 4636, 4644, 4680, 4693, 4702, 4715
`\ifautopar@pause` 270, 1029
`\IfBeginWith` 3632, 3637
`\ifbypage@` 291, 545, 1134, 1555
`\ifbypstart@` 291, 987
`\ifcsdef` 48, 461, 1808, 2910
`\ifcseempty`
 1499, 1749, 1810, 1864, 1928, 2914
`\ifcsequal` 2912
`\ifcsstring` 1756, 1757, 1788, 1789,
 2376, 2377, 2406, 2407, 2703, 2715
`\ifdef` 29, 3147, 3182, 3762
`\ifdefstring` 1509
`\ifdim` 776, 778, 780, 782, 1975, 4049, 4547
`\ifdimequal` 1590, 1693,
 2070, 2320, 2919, 2926, 2940, 2954
`\ifeledmac@after@imakeidx@` 3604, 3607
`\ifeledmac@check@imakeidx@` 3604
`\iffirst@linenum@out@` 701, 705
`\ifFN@bottom` 2999, 3009
`\ifhbox` 1799, 1804
`\ifhmode` 1989, 1996, 2019, 2026
`\ifinserthangingsymbol` .. 3829, 5134
`\ifinstanza` 961, 1024, 3826, 3832, 5134
`\ifl@d@dash` 1527, 1584, 2544
`\ifl@d@elin` 1527,
 1573, 1586, 1587, 2534, 2546, 2547
`\ifl@d@esl` 1527, 1587, 2547
`\ifl@d@pnun`
 1527, 1561, 1581, 1585, 2522, 2545
`\ifl@d@ssub` 1527, 1583, 2543
`\ifl@dend@` 2500, 2506
`\ifl@dmemoir` 43, 4060, 4648, 4729
`\ifl@dpaging` 179, 1463, 2040
`\ifl@dpairing` .. 179, 201, 240, 260,
 276, 1463, 1517, 1598, 1615,
 1621, 1768, 1774, 1876, 1882,
 1944, 1950, 2040, 2079, 2096,
 2102, 2202, 2208, 2269, 2275,
 2385, 2392, 3487, 3496, 3548,
 4600, 4608, 4616, 4624, 4632, 4640

- \ifl@dskipnumber 802, 1194
- \ifl@dstartendok 4350, 4360
- \ifl@imakeidx 46, 3707
- \iflabelpstart 936, 969
- \ifledfinal 4, 30, 35
- \ifledgroupnotesL@ 1193, 3602
- \ifledgroupnotesR@ 3602
- \iflednopbinverse 4, 5133, 5134
- \ifledplinenum 2874
- \ifledRcol 179, 753,
888, 1010, 1518, 2626, 3250,
3318, 3333, 3348, 3488, 3497,
3549, 3771, 3782, 4929, 4942,
4955, 4967, 4981, 4994, 5007, 5020
- \ifledRcol@
... 127, 134, 141, 179, 3360, 3378
- \ifledsecnolinenum 4,
4602, 4610, 4618, 4626, 4634, 4642
- \ifleftnoteup 3400, 3413
- \ifluatex 1486, 1508, 2627, 2640
- \ifnoquotation@ 4, 4676
- \ifnoteschanged@ 250, 455
- \ifnumberedpar@ ... 926, 950, 977,
2002, 2008, 2118, 2130, 2625,
2683, 2684, 3239, 3317, 3332, 3347
- \ifnumbering 178,
190, 237, 269, 294, 946, 974, 1016
- \ifnumberingR 179, 1011
- \ifnumberline 894, 1104, 1193
- \ifnumberpstart .. 934, 960, 994, 1024
- \ifnumequal 988, 1807, 1809, 3431
- \ifnumgreater 3439, 3459, 3466
- \ifodd 1243,
1319, 3295, 3303, 3371, 3389, 3454
- \ifparapparatus@ 4
- \ifparledgroup 4, 1615, 1620,
1768, 1773, 1876, 1881, 1944,
1949, 2096, 2101, 2202, 2207,
2269, 2274, 2385, 2391, 3496, 3547
- \ifpst@rtedL 179
- \ifpstartnum 1330, 1333, 1338
- \ifreportnoidxfile 3652
- \ifrightnoteup 3311, 3408
- \ifshowindexmark 3665
- \ifsidepstartnum 962, 1304
- \ifstrempty 939,
999, 2741, 2755, 3749, 5031,
5033, 5044, 5051, 5052, 5062,
5069, 5070, 5080, 5087, 5088, 5092
- \IfStrEq 725,
735, 1039, 1050, 3021, 3024,
3474, 3477, 5114, 5123, 5136, 5140
- \IfStrEqCase 747
- \ifstrequal 1409, 1421, 1435, 2734, 2751
- \ifsublines@
. 413, 442, 530, 559, 564, 570,
585, 603, 612, 626, 648, 695,
697, 1105, 1142, 1197, 3155, 3179
- \IfSubStr 3709, 3718, 3769
- \iftoggle . 1499, 1592, 1695, 1749,
1864, 1928, 2072, 2322, 2420,
2433, 2444, 2450, 2892, 2898,
2903, 2908, 2927, 2931, 2932,
2935, 2941, 2942, 2945, 2946,
2949, 2955, 2956, 2960, 2961, 2964
- \ifvbox 984, 2981, 3049
- \ifvmode 3141
- \ifvoid 2474, 2479, 2489, 2492, 2498,
3002, 3035, 3042, 3047, 3064,
3067, 3072, 3079, 3080, 3087–
3089, 3495, 3512, 3534, 3566, 3595
- \ifwidthliketwocolumns .. 4, 207, 279
- \imki@wrindexentry .. 3710, 3711, 3714
- \indexentry 3720, 3723, 3727
- \initnumbering@reg 189
- \initnumbering@sectcmd 206, 278, 4597
- \inplaceoflemmaseparator 16
- \inplaceofnumber 15
- \InputIfFileExists 214, 483
- \insert 1459, 1706, 1850,
1914, 2036, 2175, 2243, 2338,
2479, 2493, 3042, 3047, 3049, 3068
- \insert@count 671, 672,
764, 766, 845, 867, 1411, 1423,
1425, 1438, 1441, 1444, 2012,
2122, 2650, 3325, 3340, 3355
- \insert@countR 755,
757, 1415, 1429, 1431, 1449,
1452, 1455, 2638, 3321, 3336, 3351
- \inserthangingsymbol 1058, 3830
- \inserthangingsymbolfalse 1043
- \inserthangingsymboltrue 1041
- \inserthangingymbol 3829
- \insertlines@list
... 243, 446, 479, 679, 1349, 1353
- \insertparafootsep .. 1745, 1806, 2369
- \inserts@list 954, 1344,
1347, 1357, 1392, 1393, 1410,

- 1422, 1424, 1437, 1440, 1443,
2011, 2121, 2649, 3324, 3339, 3354
`\inserts@listR`
..... 1414, 1428, 1430, 1448,
1451, 1454, 2636, 3320, 3335, 3350
`\instanzafalse` 3828, 3916
`\instanzatru` 3890
`\interfootnotelinepenalty` 1470
`\interlinepenalty`
..... 1004, 1377, 1470, 3896
`\interparanoteglue` 2882
`\ipn@skip` 2882
`\itemcount@` 128, 130,
135, 137, 142, 144, 3429, 3431,
3436, 3439, 3457, 3459, 3464, 3466
- J**
- Jayaditya 5
- K**
- Kabelschacht, Alois 95
Krukov, Alexej 70
- L**
- `\l@d@wrindexhyp` 3663
`\l@d@add` 916, 918, 922, 924
`\l@d@dashfalse` 1536, 1554, 2517
`\l@d@dashtrue`
1558, 1564, 1576, 2520, 2525, 2537
`\l@d@elinfalse` 1532, 1561, 2522
`\l@d@elintrue` .. 1561, 1563, 2522, 2524
`\l@d@end`
2500, 2502, 2503, 2509, 2559, 2682
`\l@d@err@UnequalColumns` 4130
`\l@d@eslfalse`
..... 1534, 1570, 1573, 2531, 2534
`\l@d@esltrue` ... 1573, 1575, 2534, 2536
`\l@d@index` 3648, 3650, 4062
`\l@d@makecol` 2993, 3056, 3126
`\l@d@nums` . 844, 899, 902, 910, 911,
924, 2634, 2636, 2647, 2649, 2683
`\l@d@pnumfalse` 1528, 1554, 2517
`\l@d@pnumtrue` 1557, 2519
`\l@d@reinserts` 3046, 3057
`\l@d@section` 2509, 2511
`\l@d@set` 592, 796
`\l@d@ssubfalse` 1530, 1566, 2527
`\l@d@ssubtrue` 1568, 2529
`\l@d@wrindexm@m` 3662, 3663
`\l@dampcount` 3989,
4126, 4128, 4133, 4393, 4403,
4404, 4416, 4417, 4452, 4470, 4508
`\l@dbegin@stack` 3803, 3814–3816
`\l@dbfnote` 2003, 2007
`\l@dcheckcols` 4083, 4095, 4123
`\l@dcheckstartend` 4349, 4360
`\l@dchset@num` 497, 500, 592
`\l@dcolcount` 3989, 4031,
4043, 4044, 4082, 4084, 4094,
4096, 4124, 4128, 4133, 4178,
4180, 4197, 4199, 4215, 4216,
4231, 4232, 4246, 4247, 4263,
4264, 4316, 4317, 4393, 4403,
4404, 4416, 4417, 4448, 4450,
4465, 4467, 4508, 4514, 4544, 4553
`\l@dcollect@@body` 3805, 3813
`\l@dcollect@body`
..... 3800, 4580–4582, 4584–4586
`\l@dcolwidth` 4031, 4049, 4050,
4172, 4315, 4379, 4405, 4418,
4509, 4511, 4516, 4525, 4546, 4547
`\l@dcsnote` 3310, 3311
`\l@dcsnotetext`
1085, 3374, 3390, 3395, 3438, 3441
`\l@dcsnotetext@l` 1085, 3372, 3441, 3458
`\l@dcsnotetext@r` 1085, 3392, 3441, 3465
`\l@ddodoreinxtrafeet` 3037, 3048, 3054
`\l@ddofootinsert` 2994, 3000
`\l@ddoxtrafeet` 3017, 3020, 3053
`\l@deditbeginmini` 3069, 3472, 3482
`\l@deditendmini`
..... 3071, 3475, 3478, 3479, 3482
`\l@demptyd@ta` 1035, 1085
`\l@dend@close` 2502, 2552
`\l@dend@false` 2500, 2503
`\l@dend@open` 2502, 2507
`\l@dend@stuff` ... 199, 275, 2505, 2558
`\l@dend@true` 2500, 2502
`\l@denvbody` 3795, 3798, 3801–3803
`\l@dfambeginmini` ... 2494, 3472, 3508
`\l@dfamendmini`
..... 2497, 3475, 3478, 3479, 3508
`\l@dfeetbeginmini`
..... 3472, 3526, 3562, 3591
`\l@dfeetendmini` 3472, 3537, 3569, 3598
`\l@dgetline@margin` 320
`\l@dgetlock@disp` 364, 392

- \l@getref@num
 . 3186, 3187, 3189, 3190, 3192,
 3193, 3195, 3196, 3203, 3225, 3230
- \l@dgetsidenote@margin 3246
- \l@dobblearg 4074
- \l@dobbledarg 4074
- \l@dobbleoptarg 4075
- \l@dlabel@parse 3209, 3212
- \l@dld@ta 1055, 1085,
 1232, 1310, 1322, 4742, 4758, 4761
- \l@dlp@rbox 1093, 3281, 3399
- \l@dlsn@te 1057, 1092, 4743, 4759, 4761
- \l@dlsnote 3291, 3311
- \l@dmake@labels 3146, 3165, 3174
- \l@dmemoirfalse 44
- \l@dmemoirtrue 44
- \l@dmodforcritext 4136, 4589
- \l@dmodforedtext 4147, 4592
- \l@dnullfills 4157,
 4437, 4455, 4473, 4483, 4491, 4501
- \l@dnumpstartsL
 . 179, 202, 220, 261, 957, 1047,
 1065, 1068, 1070, 4935, 4948,
 4961, 4973, 4987, 5000, 5013, 5026
- \l@dnumpstartsR 4931, 4944,
 4957, 4969, 4983, 4996, 5009, 5022
- \l@dold@footnotetext 1983, 1985
- \l@dold@xympar 3237
- \l@doldold@footnotetext . 2000, 2016
- \l@dp@rsefootspec 1537, 3625
- \l@dpagingfalse 179
- \l@dpagingtrue 179
- \l@dpairingfalse 179
- \l@dpairingtrue 179
- \l@dparsedendline 1537, 3622
- \l@dparsedendpage 1537, 3622
- \l@dparsedendsub 1537
- \l@dparsedstartline 1537, 3621
- \l@dparsedstartpage 1537, 3621
- \l@dparsedstartsub 1537
- \l@dparsefootspec 1537
- \l@dpush@begins 3810, 3814
- \l@drd@ta 1058, 1085,
 1232, 1312, 1320, 4742, 4745, 4758
- \l@dref@undefined
 3186, 3189, 3192, 3195, 3198
- \l@drestorefills 4157,
 4441, 4457, 4477, 4485, 4495, 4503
- \l@drestoreforcritext ... 4136, 4590
- \l@drestoreforedtext 4147, 4593
- \l@drp@rbox 1095, 3281, 3407
- \l@drsn@te 1059, 1092, 4743, 4745, 4759
- \l@drsnote 3292, 3311
- \l@dsetmaxcolwidth .. 4048, 4089, 4101
- \l@dskipnumberfalse 802, 1195
- \l@dskipnumbertrue 802, 1186
- \l@dstartendokfalse . 4364, 4368, 4372
- \l@dstartendoktrue 4362
- \l@dtabaddcols 4348, 4378
- \l@dtabnoexpands 821, 3933
- \l@dunboxmpfoot 3535, 3543, 3567, 3596
- \l@dunhbox@line 1030, 1058, 1073, 1076
- \l@dzeropenalties 972, 980, 1002
- \l@imakeidxfalse 47
- \l@imakeidxtrue 47
- \l@prev@nopb 224, 5101
- \l@prev@pb 223, 5100
- Lück, Uwe 3
- \label 26
- \label@refs 3138,
 3140, 3146, 3153, 3156, 3158, 3160
- \labelpstartfalse 931
- \labelpstarttrue 931
- \labelref@list . 3131, 3137, 3140, 3179
- \labelrefsparseline 3150
- \labelrefsparsesubline 3150
- \last@page@num 540, 5135
- \lastbox . 1022, 1037, 1737, 1798, 1803
- \lastkern 1975
- \lastskip 775, 779
- Lavagnino, John 2, 4
- Leal, Jeronimo@Leal, Jerónimo 3
- \led 151
- \led@check@nopb 1039, 1050, 5112
- \led@check@pb 1039, 1050, 5112
- \led@err@AutoparNotNumbered
 90, 1012, 1017
- \led@err@EdtextWithoutFootnote .
 164, 759, 768
- \led@err@HighEndColumn ... 153, 4369
- \led@err@LineationInNumbered 67, 295
- \led@err@LowStartColumn .. 153, 4365
- \led@err@ManyLeftnotes ... 126, 3459
- \led@err@ManyRightnotes .. 126, 3466
- \led@err@ManySidenotes ... 126, 3439
- \led@err@NumberingNotStarted 51, 254
- \led@err@NumberingShouldHaveStarted
 51, 285
- \led@err@NumberingStarted ... 51, 191
- \led@err@PendNoPstart 90, 978

- \led@err@PendNotNumbered [90](#), [975](#)
- \led@err@PstartInPstart [90](#), [951](#)
- \led@err@PstartNotNumbered [90](#), [947](#)
- \led@err@ReverseColumns [153](#), [4373](#)
- \led@err@TooManyColumns [153](#), [4045](#)
- \led@err@UnequalColumns [153](#)
- \led@error@ImakeidxAfterEledmac [167](#), [3608](#)
- \led@mess@NotesChanged [57](#), [251](#)
- \led@mess@SectionContinued [65](#), [273](#)
- \led@nopb [5104](#), [5106](#)
- \led@nopbnum [5105](#), [5106](#)
- \led@pb [5102](#), [5106](#)
- \led@pb@setting [725](#), [735](#), [747](#), [1039](#), [1050](#), [5110](#), [5114](#), [5123](#), [5136](#), [5140](#)
- \led@pbnum [5103](#), [5106](#)
- \led@toksa [427](#), [435](#)
- \led@toksb [427](#), [434–436](#)
- \led@war@FalseverseDeprecated [147](#), [3901](#)
- \led@war@ledxxxDeprecated [147](#), [4599](#), [4607](#), [4615](#), [4623](#), [4631](#), [4639](#), [4647](#), [4656](#)
- \led@warn@AddfootinsObsolete [120](#), [3061](#)
- \led@warn@Addfootinsobsolete [117](#)
- \led@warn@AddfootinsXObsolete [117](#), [2484](#)
- \led@warn@AddfootinsXobsolete [117](#)
- \led@warn@BadAction [104](#), [1188](#)
- \led@warn@BadAdvancelineLine [80](#), [579](#)
- \led@warn@BadAdvancelineSubline [80](#), [573](#)
- \led@warn@BadLineation [70](#), [315](#)
- \led@warn@BadLinenummargin [70](#), [343](#)
- \led@warn@BadLockdisp [70](#), [370](#)
- \led@warn@BadSetline [86](#), [787](#)
- \led@warn@BadSetlinenum [86](#), [794](#)
- \led@warn@BadSidenotemargin [113](#), [3273](#)
- \led@warn@BadSublockdisp [70](#), [396](#)
- \led@warn@DuplicateLabel [106](#), [3168](#)
- \led@warn@NoIndexFile [115](#), [3653](#)
- \led@warn@NoLineFile [78](#), [488](#)
- \led@warn@NoMarginpars [111](#), [3240](#)
- \led@warn@RefUndefined [106](#), [3200](#)
- \led@warn@SeriesStillExist [123](#), [2566](#)
- \ledchapter [4597](#)
- \ledchapter* [4597](#)
- \ledfinalfalse [14](#)
- \ledfinaltrue [13](#)
- \ledfootinsdim [1638](#), [2612](#), [2613](#)
- ledgroup (environment) [24](#), [3558](#)
- ledgroupsized (environment) [24](#), [3573](#)
- \ledinnernote [27](#), [3291](#)
- \ledinnote [3643](#)
- \ledinnotehyperpage [3643](#)
- \ledleftnote [27](#), [3291](#), [3970](#), [3973](#), [3978](#)
- \ledlinenum [408](#)
- \ledllfill [1058](#), [1097](#), [3577](#), [3581](#)
- \ledlsnotefontsetup [27](#), [3284](#), [3398](#)
- \ledlsnotesep [27](#), [1093](#), [3284](#)
- \ledlsnotewidth [27](#), [3284](#), [3398](#)
- \lednopb [34](#), [5102](#)
- \lednopbinversetrue [16](#), [34](#)
- \lednopbnum [5102](#), [5142](#)
- \ledouternote [27](#), [3302](#)
- \ledouterote [3291](#)
- \ledpb [34](#), [5102](#)
- \ledpbnum [5102](#), [5138](#)
- \ledpbsetting [34](#), [5110](#)
- \ledplinumtrue [2877](#)
- \ledrightnote [27](#), [3291](#), [3969](#), [3972](#), [3977](#)
- \ledrlfill [1058](#), [1097](#), [3578](#), [3585](#)
- \ledrsnotefontsetup [27](#), [3284](#), [3406](#)
- \ledrsnotesep [27](#), [1095](#), [3284](#)
- \ledrsnotewidth [27](#), [3284](#), [3406](#)
- \ledsecnolinenumtrue [17](#)
- \ledsection [4597](#)
- \ledsection* [4597](#)
- \ledsectnomark [4724](#)
- \ledsectnotoc [4723](#)
- \ledsetnormalparstuff [1485](#), [1746](#), [2061](#), [2370](#)
- \ledsidenote [27](#), [3291](#), [3971](#), [3974](#), [3979](#)
- \ledsubsection [4597](#)
- \ledsubsection* [4597](#)
- \ledsubsubsection [4597](#)
- \ledsubsubsection* [4597](#)
- \left [4323](#), [4326](#), [4331](#), [4334](#)
- \leftctab [4392](#), [4492](#)
- \leftlinenum [10](#), [408](#), [1234](#), [1246](#), [4740](#), [4756](#)
- \leftlinenumR [4741](#), [4757](#)
- \leftltab [4383](#), [4474](#)
- \leftmargin [4685](#), [4686](#), [4707](#), [4708](#)
- \leftnoteupfalse [27](#)
- \leftnoteuptrue [3414](#)
- \leftpstartnum [1304](#)
- \leftrtab [4387](#), [4438](#)
- Leibniz [5](#)

- \lemma 12, [908](#)
 - \lemmaseparator 16, [2881](#)
 - \letsforverteilen [4165](#),
4189, 4208, 4224, 4240, 4255, 4272
 - \line@list 246, [446](#), 478, 697, 897, 901
 - \line@list@stuff 198, 274, [703](#)
 - \line@margin [320](#), 1239, 1315
 - \line@num . 130, 137, 144, 225, 412,
[440](#), 502, 536, 546, 577, 578,
580, 588, 593, 594, 606, 690,
694, 1111, 1135, 1145, 1210,
1212, 1213, 1222, 1223, 1809, 3178
 - \line@numR 128, 135, 142
 - \line@set 912, [913](#)
 - \lineation 9, 68, 71, [293](#)
 - \lineinfo@ 2893, 2896, 2966
 - \linenum [13](#),
909, 3232, 4073, 4141, 4152, 4171
 - \linenum@out ... [700](#), 706, 708, 712,
713, 715, 716, 719, 720, 729,
731, 733, 740, 742, 744, 747,
763, 777, 781, 784, 789, 796,
799, 800, 806, 891, 3136, 5102–5105
 - \linenum@outR 754, 889
 - \linenumberlist ... 9, [172](#), 1211, 1223
 - \linenumberstyle 11, [399](#)
 - \linenumincrement 8, 9, [359](#)
 - \linenummargin 9, 73, [320](#)
 - \linenumr@p [399](#)
 - \linenumrep [399](#),
412, 1582, 1586, 2542, 2546, 3178
 - \linenumsep
.. 10, [408](#), 1334, 1339, 3286, 3287
 - \lineref 25, [3189](#)
 - \linewidth 1055
 - \list@clear [426](#), 478–481, 954
 - \list@clearing@reg 466, [477](#)
 - \list@create
... [425](#), 446–449, 809, 1344, 3131
 - \listadd 2703, 2715
 - \listcsgadd 5048, 5066, 5084, 5096
 - \listcsxadd 551, 5106–5109
 - \listead 2702, 2717
 - \listgadd 3372, 3374, 3390, 3392, 3395
 - \listxadd 2695
 - \lock@disp [364](#), 1276, 1280, 1284
 - \lock@off 619, 620, [646](#), 800
 - \lock@on [617](#), 799
 - \lockdisp 10, 75, [364](#)
 - Lorch, Richard 5
 - \Lpack 3741
 - \ltab 3936, [4472](#), 4580
 - \ltabtext 3938, [4482](#), 4584
 - \luatexpardir 1424, 1430, 1488
 - \luatextextdir 1422, 1428, 1487
 - Luecking, Dan 41
- M**
- \m@m@makecolfloats [2976](#), 2995
 - \m@m@makecolintro [2976](#)
 - \m@m@makecoltext [2976](#), 2996
 - \m@mdodoreinextrafeet 3054
 - \m@m@doextrafeet 3053
 - \m@mmf@check [1974](#), 1991, 2021
 - \m@mmf@prepare
.... [1971](#), 1986, 1995, 2025, 2668
 - \M@sect [4766](#)
 - \m@th 4341
 - \makehboxofhboxes
.... 1758, 1790, [1795](#), 2378, 2408
 - \makememindexhook 3646
 - \managestanza@modulo [3858](#), 3877
 - \marg 2728
 - \marginparwidth 3284, 3285
 - \marks 1616–1618, 1769–1771, 1877–
1879, 1945–1947, 2097–2099,
2203–2205, 2270–2272, 2387–2389
 - \mathchardef 3853
 - \maxdepth 2997
 - \maxdimen 1711, 1726, 2343, 2357
 - \maxhnotesX 19
 - \maxhXnotes 19
 - Mayer, Gyula 5
 - \measurebody .. 4440, [4446](#), 4476, 4494
 - \measurecell [4081](#), 4107
 - \measuremrow [4105](#), 4451
 - \measuretbody .. 4456, [4462](#), 4484, 4502
 - \measuretbodycell [4093](#), 4112
 - \measuretbodyrow [4110](#), 4468
 - \message 66, 197
 - Middleton, Thomas 5, 56
 - minipage (environment) 24
 - Mittelbach, Frank 4
 - \morenoexpands [36](#), [813](#)
 - \moveleft 2461, 2467, 4385, 4390, 4398
 - \moveright 4411, 4424, 4433
 - \mpfnpos 28, [2455](#)
 - \mpnnormalfootgroup [1613](#), 1659
 - \mpnnormalfootgroupX [2094](#), 2151

- \mpnnormalvfootnote 3311, 3413, 3558, 3602–3604,
..... 1475, 1658, 1837, 1906 3623, 3827, 3829, 4360, 4734, 4925
- \mpnnormalvfootnoteX \newinsert 2617–2620
..... 2047, 2150, 2163, 2231 \newlength 408, 3845
- \mppara@footgroup 1677, 1765 \newlinechar 2679
- \mppara@footgroupX 2304, 2374 \newread 464
- \mppara@vfootnote 1676, 1720 \newrobustcmd 3181
- \mppara@vfootnoteX 2303, 2337 \newseries 2560, 2697, 2698
- \mpthreecolfootgroup 1838, 1874 \newseries@ 2561, 2565
- \mpthreecolfootgroupX ... 2232, 2263 \newtoggle 1639,
..... 1839, 1845 1643, 2568, 2569, 2589–2592,
..... 2233, 2235 2594, 2597, 2614, 2615, 2879, 2880
- \mptwocolfootgroup 1907, 1939 \newverse 148, 3887
- \mptwocolfootgroupX 2164, 2196 \newwrite 700, 2500, 4924
- \mptwocolfootsetup 1908, 1939 \NEXT 4077,
..... 2165, 2167 4082, 4085, 4090, 4091, 4094,
..... 27, 1968, 1978 4097, 4102, 4103, 4106, 4108,
..... 1968, 1972, 1973, 1975 4109, 4111, 4113, 4114, 4119,
..... 4278, 4281, 4283, 4284, 4286,
..... 4288, 4289, 4292, 4294, 4295,
..... 4297, 4299, 4300, 4303, 4305,
..... 4306, 4308, 4310, 4311, 4316,
..... 4318, 4319, 4514, 4517, 4518,
..... 4523, 4527, 4528, 4544, 4550, 4551
- N
- \n@l 742
- \n@num 667, 806
- \n@num@reg 667
- \nc@page 739, 740
- \NeedsTeXFormat 2
- \new 2701–
2703, 2705, 2714, 2715, 2717, 2718
- \new@line 724, 1058, 1073, 1076
- \newbox 926, 929,
3281, 3282, 3994, 3996, 4577, 4578
- \newcommandx . 938, 974, 1407, 1420,
1434, 1494, 1735, 1744, 1854,
1918, 2731, 2748, 2853, 2866,
2881, 3704, 3870, 3910, 3912, 3920
- \newcounter
. 350, 352, 354, 356, 932, 1118,
2671, 3150, 3151, 3613, 3861, 4346
- \newhookcommand@series 2762
- \newhookcommand@series@reload . 2835
- \newhooktoggle@series
..... 2849, 2852, 2857–2864, 2865
- \newhooktoggle@series@reload ...
..... 2865, 2871, 2872
- \newif 4–10, 29, 43, 46, 48, 178, 179,
181, 183, 186–188, 291, 292,
442, 455, 701, 750, 802, 894,
927, 934, 936, 1007, 1029, 1305,
1330, 1527, 1529, 1531, 1533,
1535, 2501, 2876, 2999, 3074,
- \next 4119, 4179,
4181, 4192, 4193, 4198, 4200,
4211, 4212, 4215, 4217, 4226,
4227, 4231, 4233, 4242, 4243,
4246, 4248, 4258, 4259, 4263,
4265, 4275, 4276, 4532, 4534, 4535
- \next@absline 736, 737
- \next@action 105, 474, 1124,
1132, 1133, 1139, 1140, 1148, 1157
- \next@actionline
. 471, 473, 1123, 1131, 1154, 1156
- \next@insert
955, 1348, 1351, 1353, 1356, 1360
- \next@page@num 230, 505, 507, 550, 600
- \no@expands 813, 843, 865, 908
- \noalign 1823
- \noeledsec 33, 4925
- \noendnotes 25, 2558
- \noindent 939,
999, 1024, 1302, 1492, 1605,
1608, 1704, 1712, 1716, 1727,
1761, 1793, 1870, 1895, 1934,
1963, 2045, 2344, 2358, 2381, 2411
- \nointerlineskip 2460, 2462, 2466, 2468
- \nolemmaseparator 16, 2881
- \nonbreakableafternumber 15

- \nonum@ 2879
 - \nonumberinfofootnote 15
 - \noquotation@true 12
 - \normal@footnotemarkX 2028, 2139
 - \normal@page@break 222, 5099
 - \normal@pars 239, 956,
1027, 1491, 1855, 1919, 2185, 2253
 - \normalbfnoteX 2117, 2131
 - \normalbodyfootmarkX 2033, 2140
 - \normalcolor 1619, 1772, 1880, 1948,
2100, 2206, 2273, 2390, 3011, 3545
 - \normalfont 410, 1969, 2034, 2874
 - \normalfootfmt 1485, 1651
 - \normalfootfmtX 2057, 2143
 - \normalfootfootmarkX 2066, 2144
 - \normalfootgroup 1607, 1652
 - \normalfootgroupX 2089, 2145
 - \normalfootnoterule 1606, 1654
 - \normalfootnoteruleX 2087, 2146, 2299
 - \normalfootstart 1589, 1649
 - \normalfootstartX 2069, 2138
 - \normalvfootnote 1458, 1650
 - \normalvfootnoteX 2035, 2141
 - \nosep@ 2880
 - \notblank 1418
 - \notbool 1458, 1475,
1494, 1849, 1854, 1914, 1918, 2622
 - \notfontsetup
.... 1869, 2581–2583, 2874, 2884
 - \notfontsizeX 16
 - \notenumfont 2578–2580, 2874
 - \notenumfontX 16
 - \noteschanged@false 455, 484
 - \noteschanged@true
.... 244, 247, 455, 489, 898, 1350
 - \notesXwidthliketwocolumns 19
 - \nottoggle 1498, 1748, 1863, 1927, 2512
 - \nulledindex 4059, 4140, 4151,
4177, 4196, 4214, 4230, 4245, 4262
 - \nullsetzen 4313, 4449, 4466
 - \num@lines . 926, 981, 1367, 1373, 1376
 - \numberedpar@false 926
 - \numberedpar@true 926, 968
 - \numberingfalse 178, 238
 - \numberingtrue 178, 194, 267
 - \numberlinefalse 9
 - \numberlinetrue 9, 895
 - \numberonlyfirstinline 14
 - \numberonlyfirstintwolines 15
 - \numberpstartfalse 9, 931
 - \numberpstarttrue 8, 9, 931
 - \numdef 736, 1065, 5116
 - \numgdef 728, 739,
3429, 3436, 3457, 3464, 5137, 5141
 - \numlabfont 19, 408
- O**
- \old@edtext 4777, 4784,
4805, 4812, 4868, 4875, 4896, 4903
 - \old@hsize
1599, 1610, 1762, 2080, 2091, 2413
 - \old@Rlineflag 3705, 3732
 - \one@line
926, 1036, 1037, 1058, 1073, 1076
 - \onlypstartinfofootnote 15
 - \openout . 215, 708, 713, 716, 720, 2502
- P**
- \p@pstart 970
 - \PackageError 50
 - \PackageWarning 49
 - \page@action 506, 598, 684
 - \page@num 130, 137,
144, 451, 469, 548, 689, 694,
1133, 1241, 1317, 1807, 1816,
3295, 3303, 3368, 3386, 3452, 5135
 - \page@numR .. 128, 135, 142, 3363, 3381
 - \page@start 773, 3001
 - \pagebreak 5112
 - \pagelinesep 29, 3611, 3620–3622
 - \pageno 107, 109, 2972
 - \pageparbreak 36, 1302
 - \pageref 26
 - \pairs 5037, 5040, 5055, 5059, 5073, 5077
 - \paperwidth 1072, 1075
 - \par@line
. 926, 982, 1368, 1369, 1372, 1376
 - \para@footgroup 1671, 1754
 - \para@footgroupX 2298, 2374
 - \para@footsetup 1675, 1683
 - \para@footsetupX 2308, 2310
 - \para@vfootnote 1669, 1705
 - \para@vfootnoteX 2296, 2337
 - \parafootfmt 1670, 1744
 - \parafootfmtX 2297, 2365
 - \parafootftmsep 2606, 2886
 - \parafootsep 18
 - \parafootstart 1668, 1691
 - \parafootstartX 2295, 2319
 - \parapparus@false 11

- \parapparatus@true 15
 - \parledgroup@ 1616, 1769,
1877, 1945, 2097, 2203, 2270, 2387
 - \parledgroup@beforenotesL 3500, 3552
 - \parledgroup@beforenotesR 3498, 3550
 - \parledgroup@series .. 1617, 1770,
1878, 1946, 2098, 2204, 2271, 2388
 - \parledgroup@type ... 1618, 1771,
1879, 1947, 2099, 2205, 2272, 2389
 - \patchcmd 4662, 4665, 4666,
4669, 4673, 4674, 4768, 4788,
4796, 4816, 4824, 4832, 4840,
4849, 4858, 4879, 4887, 4907, 4915
 - \pausenumbering 8, 265
 - \pend 6, 97, 100, 952, 974,
1025, 1302, 3914, 3921, 4600,
4602, 4608, 4610, 4616, 4618,
4624, 4626, 4632, 4634, 4640,
4642, 4651, 4654, 4657, 4659, 4672
 - Plato of Tivoli 4
 - \postbodyfootmark 2017, 2031
 - \postdisplaypenalty 1005
 - \prebodyfootmark 2017, 2029
 - \predisplaypenalty 1004
 - \prenotesX 18, 1646
 - \prenotesX@ 1645, 1646, 2070, 2320
 - \prepare@edindex@fornote
..... 2634, 2647, 3624
 - \pretocmd 3734,
4663, 4667, 4776, 4804, 4867, 4895
 - \prev@nopb 5100
 - \prev@pb 5100
 - \prevgraf 981
 - \prevline 1808, 2911
 - \prevpage@num 1806
 - \preXnotes 18, 1639, 1643
 - \preXnotes@ 1590, 1639, 1643, 1693
 - \print@eledsection 1048, 1063
 - \print@footnoteXrule
. 2084, 2106, 2112, 2212, 2218,
2279, 2285, 2333, 2396, 2402, 2459
 - \print@leftmargin@eledsection ..
..... 4735,
4799, 4819, 4842, 4860, 4890, 4918
 - \print@line 1049, 1052
 - \print@rightmargin@eledsection .
..... 4735,
4791, 4827, 4844, 4862, 4882, 4910
 - \print@Xfootnoterule
. 1603, 1625, 1631, 1702, 1778,
1784, 1886, 1892, 1954, 1960, 2459
 - \printendlines 2511, 2540
 - \printlinefootnote
.... 1497, 1747, 1862, 1926, 2887
 - \printlines 1579,
2928, 2932, 2942, 2946, 2956, 2961
 - \printnpnum 25, 2542, 2545, 2550
 - \printpstart 1516,
2927, 2931, 2941, 2945, 2955, 2960
 - \processl@denvbody
..... 3802, 3806, 3807, 3823
 - \ProcessOptions 20
 - \protected@csxdef .. 2119, 2666, 3955
 - \protected@edef
..... 969, 2058, 2182, 2249, 2366
 - \protected@write 3145, 3668,
3670, 3673, 3680, 3682, 3685,
3690, 3692, 3695, 3719, 3722, 3726
 - \ProvidesPackage 3
 - \pst@rtedLfalse ... 179, 203, 219, 241
 - \pst@rtedLtrue 179, 271
 - \pstart 6, 91, 94, 95, 100,
931, 1024, 1302, 3879, 4601,
4604, 4609, 4612, 4617, 4620,
4625, 4628, 4633, 4636, 4641,
4644, 4652, 4654, 4658, 4660, 4672
 - \pstarteref 3195
 - \pstartinfootnote .. 15, 301, 307, 313
 - \pstartline 985, 988
 - \pstartnum 1304
 - \pstartnumfalse 1335, 1342
 - \pstartnumtrue 995, 1331
 - \pstartref 25, 3195
- Q**
- \quotation 4597
 - \quote 4597
- R**
- \RaggedLeft 1756, 1788, 2376, 2406
 - \RaggedRight ... 1757, 1789, 2377, 2407
 - \raggedright 1859,
1923, 2191, 2258, 3289, 4850, 4852
 - \raggedX 18
 - \raw@text 926, 958, 984, 1036
 - \rbracket 20, 1504, 2601
 - \read@linelist 464, 704
 - \ref 26

- \Relax 4077, 4531, 4538
 - \rem@inder 1223, 1225–1227
 - \removehboxes
..... 1759, 1791, 1795, 2379, 2409
 - \removelastskip 4178, 4197
 - \RequirePackage
..... 22, 23, 25–28, 36, 37, 39–42
 - \reserveinserts 24, 38
 - \resetprevline@ 59, 232, 456, 988, 1136
 - \resetprevpage@ 460
 - \resetprevpage@num . 60, 233, 460, 3560
 - \restore@familiarnotes .. 3951, 3987
 - \restore@notes 3981, 4188,
4207, 4223, 4239, 4254, 4271, 4469
 - \restore@sidenotes 3968, 3986
 - \resumenumbering 8, 265
 - \right 4324, 4327, 4332, 4335
 - \rightctab 4401, 4493
 - \rightlinenum
.. 10, 408, 1236, 1244, 4740, 4756
 - \rightlinenumR 4741, 4757
 - \rightltab 4414, 4475
 - \rightnoteupfalse 27
 - \rightnoteuptrue 3312
 - \rightpstartnum 1312, 1320, 1337
 - \rightrtab 4427, 4439
 - \rightstartnum 1304
 - \rigidbalance ... 1818, 1873, 1898,
1937, 1966, 2199, 2223, 2266, 2290
 - \rlap 1236, 1244, 1312, 1320, 4739, 4755
 - \Rlineflag 3705, 3706, 3732, 3754, 3758
 - Robinson, Peter 3
 - \roman 4347
 - \rtab 3934, 4436, 4582
 - \rtabtext 3937, 4454, 4586
- S**
- Sacrobosco 5
 - \sc@n@list 1224, 1226
 - Schöpf, Rainer 4
 - \section@num 175, 195,
197, 198, 214, 215, 272–274, 2509
 - \sectionmark 4726, 5055, 5059
 - \select@lemfont 814, 1402
 - \select@lemfont 20,
1402, 1498, 1748, 1863, 1927, 2512
 - \series .. 2560, 2700, 2702, 2713, 2717
 - \seriesatbegin 2699
 - \seriesatend 2709, 2712
 - \set@line 844, 866, 896
 - \set@line@action 499, 583, 590, 601, 686
 - \setcommand@series .. 2748, 2764, 2837
 - \setl@dlp@rbox . 3397, 3445, 3460, 3462
 - \setl@drp@rbox . 3405, 3447, 3455, 3467
 - \setl@drpr@box 3397
 - \setline 10, 87, 785, 818, 988
 - \setlinenum 11, 89, 792
 - \setmcellcenter 4244, 4304
 - \setmcellleft 4213, 4293
 - \setmcellright 4176, 4282
 - \setmrowcenter 4302, 4497
 - \setmrowleft 4291, 4479
 - \setmrowright 4280, 4443
 - \setnotesXpositionliketwocolumns@
..... 2043,
2083, 2105, 2111, 2211, 2217,
2278, 2284, 2332, 2395, 2401, 2443
 - \setnotesXwidthliketwocolumns@ .
..... 2041, 2082, 2104,
2110, 2210, 2216, 2277, 2283,
2311, 2331, 2383, 2394, 2400, 2413
 - \setprintendlines 2516, 2541
 - \setprintlines 1553, 1580
 - \setstanzaindents 21, 3858
 - \setstanzapenalties 22, 3858
 - \setstanzavalues 3848, 3858, 3859, 3931
 - \settcclcenter 4261, 4309
 - \settcclleft 4229, 4298
 - \settcclright 4195, 4287
 - \settoggle 1410, 1414, 2733
 - \settoggle@series
..... 2725, 2731, 2854, 2867
 - \setthrowcenter 4307, 4505
 - \setthrowleft 4296, 4487
 - \setthrowright 4285, 4459
 - \setXnotespositionliketwocolumns@
..... 1466,
1602, 1624, 1630, 1701, 1777,
1783, 1885, 1891, 1953, 1959, 2443
 - \setXnoteswidthliketwocolumns@ .
..... 1464, 1601, 1623,
1629, 1684, 1700, 1766, 1776,
1782, 1884, 1890, 1952, 1958, 2413
 - \Setzen 4522, 4531, 4533
 - \showlemma 30, 35, 812, 852, 874
 - \sidenote@margin 3246, 3366, 3384, 3450
 - \sidenote@marginR .. 3251, 3361, 3379
 - \sidenotecontent@
.. 3428, 3433, 3434, 3445, 3447,
3455, 3456, 3460, 3462, 3463, 3467

- \sidenotemargin 27, 3246
 - \sidenotemmargin 114
 - \sidenotesep 27, 3415
 - \skip . 1593, 1596, 1614, 1657, 1662,
1674, 1680, 1696, 1699, 1767,
1875, 1943, 2073, 2076, 2095,
2149, 2154, 2201, 2268, 2302,
2307, 2323, 2326, 2330, 2384,
3009, 3498, 3500, 3544, 3550, 3552
 - \skip@lockoff 620, 646
 - \skipnumbering 11, 802,
3904, 4600, 4602, 4608, 4610,
4616, 4618, 4624, 4626, 4632,
4634, 4640, 4642, 4651, 4657,
4670, 4671, 4679, 4692, 4701, 4714
 - \skipnumbering@reg 802
 - \spacefactor
1976, 1979, 1990, 1996, 2020, 2026
 - \spaceskip 1467, 2044, 2178
 - \splitmaxdepth 1472
 - \splitoff 1818
 - \splittopskip ... 1033, 1472, 1820,
1871, 1873, 1896, 1898, 1935,
1937, 1964, 1966, 2197, 2199,
2221, 2223, 2264, 2266, 2288, 2290
 - \spreadmath 30, 4510
 - \spreadtext 30, 4508
 - \stanza 21, 3887
 - \stanza@count ... 3839, 3850, 3853,
3855, 3872, 3884, 3893, 3903, 3922
 - \stanza@hang 3870, 3895
 - \stanza@line 3870, 3908, 3922
 - \stanza@modulo
3862, 3865–3867, 3875, 3893, 3902
 - \stanzaindentbase
. 21, 3839, 3873, 3876, 3882, 3925
 - \startlock 10, 799, 816, 3880
 - \startstanzahook 23, 3887
 - \startsub 10, 775, 815
 - \stepcounter
.... 2665, 3154, 3157, 3616, 4355
 - \stepl@dcollcount ... 4043, 4088,
4100, 4185, 4204, 4220, 4236,
4251, 4268, 4314, 4515, 4524, 4545
 - \StrGobbleLeft 3633, 3638
 - \strip@pt 1689, 2317
 - \strip@szacnt 3848
 - \sub@action 515, 610, 685
 - \sub@change 231, 509, 510, 516, 560, 567
 - \sub@changes 562, 565
 - \sub@lock 228, 444, 524, 526,
528, 531, 628, 629, 631, 632,
650, 651, 653, 1106, 1178, 1180,
1181, 1183, 1259, 1295, 1297, 1299
 - \sub@off 559, 781
 - \sub@on 559, 777
 - \subline@num 226, 414, 415,
441, 532, 536, 546, 571, 572,
574, 586, 604, 691, 695, 1107,
1112, 1135, 1143, 1198–1200, 3179
 - \sublinenumberstyle 11, 399
 - \sublinenumincrement 8, 9, 359
 - \sublinenumr@p 399
 - \sublinenumrep 399,
415, 1583, 1587, 2543, 2547, 3179
 - \sublineref 25, 3192
 - \sublines@false .. 229, 442, 513, 1168
 - \sublines@true 442, 511, 1166
 - \sublock@disp .. 390, 1261, 1265, 1269
 - \sublockdisp 77, 390
 - \subsection 2722,
4618, 4626, 5072, 5076, 5081, 5082
 - \subsectionmark 4727, 5073, 5077
 - \subsubsection 2724,
4634, 4642, 5089, 5090, 5093, 5094
 - Sullivan, Wayne 4,
5, 21, 35, 46, 50, 107, 108, 150, 173
 - \symlinenum 15
 - \symplinenum 2593, 2874
 - \sza@penalty 3870, 3899, 3921
- T**
- \tabellzwischen 4513, 4521
 - \tabelskip 4525, 4565–4567, 4573–4575
 - \tabHilfbox 4564,
4566, 4568, 4572, 4574, 4576, 4577
 - \tabhilfbox 4563,
4565, 4567, 4571, 4573, 4575, 4577
 - Tapp, Christian 3
 - \temp@ 1065, 1066, 3764, 3769
 - \textheight 3113
 - \textnormal 1504–1506
 - \textsuperscript ... 1969, 2034, 2067
 - \textwidth 3522, 3575
 - \theaddcolcount 4346, 4353, 4356
 - \theendpageline
3621, 3671, 3683, 3693, 3711, 3723
 - \thefootnoteA 28
 - \thelabidx
3617, 3620, 3774, 3778, 3783, 3785

`\theline` 3158, 3160
`\thempfn` 3524, 3560, 3589
`\thempfootnote` 3524, 3560, 3589
`Theodosius` 5
`\thepage` 728,
 731, 733, 742, 744, 747, 3146, 3620
`\thepageline`
 3619, 3674, 3686, 3696, 3714, 3727
`\thepstart` 9, 931, 1024, 1333, 1340, 1524
`\thepstartL` 1521
`\thepstartR` 1519
`\thestartpageline`
 3621, 3669, 3681, 3691, 3710, 3720
`\thesubline` 3158
`\thinspace` 1509, 1511
`\thr@@` 341, 631, 640, 651, 658,
 1173, 1181, 1844, 1847, 1873,
 1898, 2237, 2240, 2266, 2290, 3271
`\threecolfootfmt` 1834, 1854
`\threecolfootfmtX` 2228, 2248
`\threecolfootgroup` 1835, 1869
`\threecolfootgroupX` 2229, 2263
`\threecolfootsetup` 1836, 1842
`\threecolfootsetupX` 2230, 2235
`\threecolvfootnote` 1833, 1849
`\threecolvfootnoteX` 2227, 2242
`\togglefalse` ... 1593, 1696, 2073, 2323
`\toggletrue` 1640, 1644
`\tolerance` 1858, 1922, 2190, 2257
`\twocolfootfmt` 1903, 1911
`\twocolfootfmtX` 2160, 2181
`\twocolfootgroup` 1904, 1911
`\twocolfootgroupX` 2161, 2196
`\twocolfootsetup` 1905, 1911
`\twocolfootsetupX` 2162, 2167
`\twocolvfootnote` 1902, 1911
`\twocolvfootnoteX` 2159, 2174
`\txtbeforeXnotes` 18

U

`\unexpanded`
 4931, 4935, 4944, 4948, 4957,
 4961, 4969, 4973, 4983, 4987,
 4996, 5000, 5009, 5013, 5022, 5026
`\unhbox` 1030, 1738, 1759, 1761, 1791,
 1793, 1800, 1804, 2379, 2381,
 2409, 2411, 4567, 4568, 4575, 4576
`\unkern` 1977
`\unpenalty` 1741, 1797

`\unvbox` ... 1037, 1477, 1609, 1636,
 1722, 1736, 1755, 1787, 1829,
 2049, 2090, 2115, 2353, 2375,
 2405, 2473, 2479, 2488, 2493,
 2987, 3008, 3013, 3032, 3042,
 3047, 3049, 3068, 3096, 3541, 3556
`\unvxh` ... 1713, 1728, 1735, 2345, 2359
`\usingcritext` 4588
`\usingedtext` 4588

V

`\valign` 1821
`\value` 3866, 3871, 4352
`Vamana` 5
`\variab` 4121, 4442,
 4458, 4478, 4486, 4496, 4504, 4537
`\vbadness` 1032, 1820
`\vbfnoteX` 2120, 2125
`\vbox` 958,
 1476, 1711, 1721, 1726, 1736,
 2048, 2343, 2352, 2357, 2461,
 2467, 2472, 2487, 2984, 3005,
 3031, 3121, 3125, 3401, 3403,
 3409, 3411, 3519, 4323, 4326,
 4331, 4334, 4338, 4340, 4341,
 4384, 4388, 4393, 4404, 4417, 4430
`\vfil` 1821, 3125,
 4324, 4327, 4332, 4335, 4338, 4341
`\vfill` 3009
`\vl@dbfnote` 2007
`\vl@dcnote` 3349, 3353, 3359
`\vl@dlsnote` 3319, 3323, 3359
`\vl@drsnote` 3334, 3338, 3359
`\vnumfootnoteX` 2129, 2142
`\vrule` ... 4323, 4326, 4331, 4334, 4338
`\vsize` 1638
`\vsplit` 1036, 1828, 3096

W

`\wd` 1024, 1058, 1715,
 1730, 2347, 2361, 4049, 4050,
 4173, 4397, 4406, 4409, 4419,
 4422, 4431, 4565, 4566, 4573, 4574
`Whitney, Ron` 4
`\widowpenalty` 1005, 1374
`\widthliketwocolumnstrue` 18
`\WithSuffix` 4606, 4622,
 4638, 4655, 4979, 4992, 5005, 5018
`\wrap@edcrossref`
 3181, 3186, 3189, 3192, 3195

Wujastyk, Dominik	2, 4	\Xnoteswidthliketwocolumns	19
X			
\x@lemma	854–856, 876–878	\xpageref	26, 3186
\xcritext	4053 , 4166	\xpstartref	26, 3195
\xedindex	4059 , 4145, 4156, 4168	\Xragged	18
\xedlabel	4057 , 4174	\xright@appenditem	427 , 599,
\xedtext	4053 , 4167	600, 602, 609, 611, 613, 615,	
\Xendlemmadisablefontselection ..	17	625, 627, 636, 647, 649, 656,	
\Xendnotefontsize	16	669, 670, 679, 693, 1410, 1414,	
\Xendnotenumfont	16	1422, 1424, 1428, 1430, 1437,	
\Xhangindent	17	1440, 1443, 1448, 1451, 1454,	
\xifinlist	1047, 1066, 2566	2010, 2120, 2634, 2647, 3177,	
\xifinlistcs	726, 727, 737,	3319, 3323, 3334, 3338, 3349, 3353	
738, 5112, 5115, 5117, 5124, 5125		\xspaceskip	1467, 2044, 2178
\xleft@appenditem	433	\xsublineref	26, 3192
\Xlemmadisablefontselection	17	\xxref	26, 3220
\xlineref	26, 3189 , 3620	Z	
\Xnotefontsize	16	\z@skip	1467, 1473, 2044, 2178
\Xnotenumfont	16	\zz@@@	3132 , 3138, 3223, 3228

Change History

v0.1.		\doxtrafeet: Renamed \doxtrafeet	
General: First public release	1	to \l@ddoxtrafeet	146
v0.2.		\edlabel: Tweaked \edlabel to	
General: Added tabmac code, and		get correct page numbers ...	150
extended indexing	1	\l@d@makecol: Rewrote \@makecol,	
\eledmac@error: Added \eledmac@error		calling it \l@d@makecol	145
and replaced error messages ..	42	\l@ddodoreinxtrafeet: Re-	
\ifl@d@memoir: Added \ifl@d@memoir		named \dodoreinxtrafeet to	
for memoir class having been		\l@ddodoreinxtrafeet	146
used	42	\l@ddofootinsert: Renamed	
\morenoexpands: Added \l@dtabnoexpands		\dofootinsert as \l@ddofootinsert	
to \no@expands	75	145
v0.2.1.		\m@m@makecolintro: Added	
\@lab: Removed page setting from		\m@m@makecolfloats, \m@m@makecoltext	
\@lab	151	and \m@m@makecolintro ...	145
General: Added text about normal		\morenoexpands: Removed some	
labeling	26	\lets from \no@expands. These	
Bug fixes and match with mem-		were in EDMAC but I feel that	
patch v1.8	1	they should not have been as	
Major changes to insert code		they disabled page/line refs in	
when memoir is loaded	147	a footnotes	75

- \zz@@@: Minor change to \zz@@@ . 149
- v0.2.2.
- General: Improved paragraph foot-
notes 1
 - New Dekker example 1
 - Used \providecommand for
\@gobblethree to avoid clash
with the amsfonts package ... 46
 - \footfudgefiddle: Added
\footfudgefiddle 106
 - \line@list@stuff: Added ini-
tial write of page number in
\line@list@stuff 68
 - \para@footsetup: Added
\footfudgefiddle to
\para@footsetup 106
 - \para@footsetupX: Added
\footfudgefiddle to
\para@footsetupX 125
- v0.3.
- \@lab: Replaced \the\line@num
by \linenumr@p\line@num in
\@lab, and similar for sub-lines 151
 - \@nl@reg: Added a bunch of code to
\@nl for handling \setlinenum 62
 - General: Includes edstanza and
more 1
 - \ledlinenum: Added \linenumr@p
and \sublinenum@rep
to \leftlinenum and
\rightlinenum 54
 - \linenumberlist: Added
\linenumberlist mechanism . 46
 - \printendlines: Added \linenumr@p
and \sublinenumr@p to
\printendlines 132
 - \printlines: Added \linenumr@p
and \sublinenumr@p to
\printlines 102
 - \sublinenumr@p: Added \linenumberstyle
and \sublinenumberstyle ... 54
- v0.3.1.
- General: Not released. Added re-
marks about the parallel pack-
age 1
- v0.4.
- \@iiiminipage: Modified ker-
nel \@iiiminipage and
\endminipage to cater for criti-
cal footnotes 161
- General: Added \showlemma to
\edtext (and \critext) 77
- Added minipage, etc., support . 1
 - ledgroupsize: Added ledgroup-
sized environment 163
 - \footnormal: Added minpage foot-
note setup to \footnormal . 105
 - \if@ledgroup: Added ledgroup en-
vironment 162
 - \ifledsecnolinenum: Added fi-
nal/draft options 41
 - \l@dfeetendmini: Added
\l@dfeetbeginmini, \l@dfeetendmini
and all their supporting code 160
 - \mpnormalfootgroup: Added
\mpnormalfootgroup 103
 - \mpnormalvfootnote: Added
\mpnormalvfootnote 98
 - \showlemma: Added \showlemma . 41
- v0.4.1.
- \@opxtrafeetii: Added \@opxtrafeetii
..... 146
 - General: Added code for changing
\@docleapage 148
 - Not released. Minor editorial im-
provements and code tweaks .. 1
 - Only change \@footnotetext
and \@footnotemark if memoir
not used 117
 - \doxtrafeetii: Changed
\doxtrafeetii code for easier
extensions 146
 - \edindex: Let eledmac take advan-
tage of memoir's indexing .. 165
- v0.5.
- \@footnotetext: Enabled regular
\footnote in numbered text 117
 - \@xympar: Eliminated \marginpar
disturbance 154
 - General: Added left and right side
notes 154
 - Added sidenotes, familiar foot-
notes in numbered text 1
- v0.5.1.
- General: Added moveable side note 154
 - Fixed right line numbers killed in
v0.5 1
 - \affixline@num: Changed
\affixline@num to cater for
sidenotes 88

ledgroupsize: Only change \hsize in ledgroupsize envi- ronment otherwise page number can be in wrong place	163	\do@insidelinehook: Added \do@linehook for use in \do@line	84
\l@getsidenote@margin: Added \sidenotemargin and \sidenote@margin	155	\endnumbering: Changed \endnumbering for eledpar . .	49
v0.6. \@lopR: Added \@pend,\@pendR, \@lopL and \@lopR in anticipa- tion of parallel processing . . .	63	\f@x@l@cks: Added \ch@cksub@l@ck, \ch@ck@l@ck and \f@x@l@cks . .	90
\@nl@reg: Added \fix@page to \@nl	62	\footsplitskips: Added \footsplitskips for use in many footnote styles	98
Extended \@nl to include the page number	62	\get@linelistfile: Added \get@linelistfile	61
General: Fixed long paragraphs looping	1	\ifledRcol@: Added \l@dnumpstartsL, \ifl@dpairing and \ifp@st@rted for/from eledpar	47
Fixed minor typos	1	\initnumbering@reg: Added \initnumbering@reg	48
Prepared for eledpar package . .	1	\l@dcsnotetext@r: Added \l@emptyd@ta	84
\fix@page: Added \last@page@num and \fix@page	63	\l@ddofootinsert: Deleted \page@start from \l@ddofootinsert	145
\new@line: Extended \new@line to output page numbers	69	\l@dgetline@margin: Added \l@dgetline@margin	51
\page@start: Made \page@start a no-op	70	\l@dgetlock@disp: Added \l@dgetlock@disp	53
\v@l@dbfnote: Changed \l@dbfnote and \v@l@dbfnote as originals could give incorrect markers in the footnotes	118	\l@dgetsidenote@margin: Added \l@dgetsidenote@margin . .	155
v0.7. \@nl@reg: Added \@nl@reg	62	\l@drsn@te: Added \l@dlsn@te and \l@drsn@te for use in \do@line	85
\@ref@reg: Added \@ref@reg . . .	67	\l@dunboxmpfoot: Added \l@dunboxmpfoot containing some common code	162
General: eledmac having been avail- able for 2 years, deleted the commented out original edmac texts	1	\l@dzeropenalties: Added \l@dzeropenalties	82
Maïeul Rouquette new main- tainer	1	\ledlinenum: Added \ledlinenum for use by \leftlinenum and \rightlinenum	54
Made macros of all messages . .	42	\line@list@stuff: Deleted \page@start from \line@list@stuff	68
Replaced all \interAfootnotelinepenalty etc., by just \interfootnotelinepenalty	1	\list@clearing@reg: Added \list@clearing@reg	61
Tidying up for eledpar and ledarab packages	1	\n@num@reg: Added \n@num	66
\affixline@num: Added skipnum- mering to \affixline@num . .	88	\normalbfnoteX: Removed extraneous space from \normalbfnoteX	121
\do@actions@fixedcode: Added \do@actions@fixedcode	87	\resumenumbering: Changed \resumenumbering for eledpar .	50
\do@actions@next: Added number skipping to \do@actions	86		

<code>\setprintendlines:</code>	Added	Possibility to number <code>\pstart</code> . . .	9
<code>\setprintendlines</code> for use by		Possibility to number the	
<code>\printendlines</code>	131	<code>pstart</code> with the commands	
<code>\setprintlines:</code> Added <code>\setprintlines</code>		<code>\numberpstarttrue</code>	1
for use by <code>\printlines</code>	101	<code>\ifledRcol@:</code> Added <code>\ifledRcol</code>	
<code>\skipnumbering@reg:</code> Added		and <code>\ifnumberingR</code> for/from	
<code>\skipnumbering</code> and supports	71	<code>eledpar</code>	47
<code>\sublinenumincrement:</code> Added		v0.12.1.	
<code>\firstlinenum, \linenumincrement,</code>		General: Don't number <code>\pstarts</code> of	
<code>\firstsublinenum</code> and		stanza.	1
<code>\linenumincrement</code>	52	The numbering of <code>\pstarts</code>	
<code>\sublinenumr@p:</code> Using <code>\linenumrep</code>		restarts on each <code>\beginnumbering</code> .	
instead of <code>\linenumr@p</code>	54	1
Using <code>\sublinenumrep</code> instead of		v0.13.	
<code>\sublinenumr@p</code>	54	General: New <code>stanzaindentsrepetition</code>	
<code>\vnumfootnoteX:</code> Removed		counter to repeat stanza in-	
extraneous space from		dents every n verses.	21
<code>\vnumfootnoteX</code>	121	New <code>stanzaindentsrepetition</code>	
v0.8.		counter: to repeat stanza in-	
General: Bug on endnotes fixed: in		dents every n verses.	1
a // text, all endnotes will print		<code>\managestanza@modulo:</code> New stan-	
and be placed at the ends of		zaindentsrepetition counter to	
columns ()	1	repeat stanza indents every n	
v0.8.1.		verses.	174
General: Bug on <code>\edtext</code> ; <code>\critex</code>		v0.13.1.	
; <code>\lemma</code> fixed: we can now us		General: <code>\thepstartL</code> and	
non switching commands	1	<code>\thepstartR</code> use now	
v0.9.		<code>\bfseries</code> and not <code>\bf</code> , which	
General: No more <code>ledpatch</code> . All		is deprecated and makes con-	
patches are now in the main		flicts with memoir class.	1
file.	1	v0.14.	
v0.9.1.		General: Tweaked <code>\edlabel</code> to get	
General: Fix some bugs linked to in-		correct line number if the com-	
tegrating <code>ledpatch</code> on the main		mand is first element of a para-	
file.	1	graph.	1
v0.10.		<code>\edlabel:</code> Tweaked <code>\edlabel</code> to	
General: Corrections to <code>\section</code>		get correct line number if the	
and other titles in numbered		command is first element of a	
sections	1	paragraph.	150
v0.11.		v0.15.	
General: Makes it possible to add		General: Line numbering can be re-	
a symbol on each verse's hang-		set at each <code>pstart</code>	50
ing, as in French typogra-		Possibility to print <code>\pstart</code> num-	
phy. Redefines the command		ber in side.	9
<code>\hangingsymbol</code> to define the		<code>\affixline@num:</code> Line numbering	
character.	1	can be disabled.	88
v0.12.		<code>\ifinserthangingsymbol:</code> New	
General: For compatibility with		management of <code>hangingsymbol</code>	
<code>eledpar</code> , possibility to use		insertion, preventing undesir-	
<code>\autopar</code> on the right side. . . .	1	able insertions.	173

<code>\printlines</code> : Line numbering can be reset at each pstart.	102	<code>\preXnotes</code> : Debug in familiar footnotes (but introduced by v1.1).	104
v0.17.		v1.3.	
<code>\ifinserthangingsymbol</code> : New new management of hangingsymbol insertion, preventing undesirable insertions.	173	<code>\endquote</code> : <i>Quotation</i> and quote environment inside the numbering sections.	196
v1.0.		v1.4.	
General: <code>\lemma</code> can contain commands.	12	General: Compatibility of <code>\edtext</code> (and <code>\critext</code>) with the right-to-left direction (with Polyglossia).	77
Debug in lineation command	9	Compatibility with LuaTeX of RTL notes.	41, 42
New generic commands to customize footnote display.	14	<code>\newseries@</code> : Remembers the language of the lemma, in order to create a correct direction for the footnote separator.	134
Options nonum and nosepp in <code>\Xfootnote</code>	12	<code>\normalfootfmt</code> : Direction of footnotes with polyglossia.	98
Options of <code>\Xfootnotes</code>	96	<code>\rbracket</code> : Switch the right bracket to a left bracket when the lemma is RTL (needs polyglossia or LuaTeX).	99
Possibility to have commands in sidenotes.	27		
Some compatibility break with eledmac. Change of name: eledmac.	1		
<code>\morenoexpands</code> : Change to be compatible with new features	75		
v1.0.1.		v1.4.1.	
General: Correction on <code>\numberonlyfirstinlineline</code> with lineation by pstart or by page.	14	<code>\endquote</code> : New option <i>noquotation</i>	196
v1.1.		<code>\labelrefsparsesubline</code> : Fix bug with <code>\edlabel</code>	150
General: Add <code>\labelpstarttrue</code>	9	v1.4.2.	
Add <code>\numberonlyfirstintwolines</code>	15	General: Debug with some special classes.	1
Add <code>\pstartinfootnote</code> and <code>\onlypstartinfootnote</code>	15	v1.4.3.	
New hook to add arbitrary code at the beginning of the notes	17	General: Add <code>\nonbreakableafternumber</code>	15
New options for block of notes.	18	Spurious space after familiar footnotes.	1
New package option: parapparat.	1	v1.4.4.	
New tools to change order of series	136	General: Label inside familiar footnotes.	1
<code>\ledfootinsdim</code> : Deprecated		v1.4.5.	
<code>\ledfootinsdim</code>	104	General: Bug with komascript + eledpar + chapter.	1
<code>\preXnotes</code> : New skip <code>\preXnotes@</code>	104	v1.4.6.	
v1.1.0.		General: Bug with memoir class introduced by 1.4.5.	1
General: Sectioning commands.	32	v1.4.7.	
v1.2.		<code>\endquote</code> : Compatibility of sectioning commands with <code>\autopar</code>	196
<code>\endquote</code> : Compatibility of <code>\ledchapter</code> with the <i>memoir</i> class.	196		

- v1.4.8.
General: Corrects a bug with parallel texts introduced by 1.1. . . . 1
- v1.4.9.
`\normalbfnoteX`: Allow to redefine `\thefootnoteX` with `alph` when some packages are loaded. . . 121
- v1.5.
General: Correct indexing when the call is made in critical notes. 164
`\do@insidelinehook`: Added `\do@insidelinehook` for use in `\do@line` 84
`\edindex`: Compatibility with `imakeidx` package, and possibility to use multiple index with `\edindex`. 165
`\ifFN@bottom`: Use the bottom option of `footmisc` package. . . 145
- v1.5.1.
`\managestanza@modulo`: Correct `stanzaindentsrepetition` counter 174
`\normalvfootnoteX`: Fix bug with normal familiar footnotes when mixing RTL and LTR text. . 118
- v1.5.2.
`\line@list@stuff`: Open / close immediatly the line-list file when in minipage, except if the minipage is a ledgroup. . . . 68
- v1.6.0.
`\falseverse`: Add `\falseverse` macro. 175
- v1.6.1.
General: Corrects a false hanging verse when a verse is exactly the length of a line. 1
`\ifinserthangingsymbol`: Hang verse is now not automatically flush right. 173
`\l@dunhbox@line`: Move the call to `\inserthangingsymbol` to allow use `\hfill` inside. 83
`\pend`: Spurious space in `\pend`. . 81
`\pstart`: Spurious space in `\pstart`. 80
- v1.7.0.
General: New features for managing page breaks. 34
- v1.8.0.
General: Compatibility with `parledgroup` option of `eledpar` package. 1
If `imakeidx` and `hyperref` are loaded, adds `hyperref` in the index. 164
`\endquote`: Correction of sectioning commands in parallel texts. . 196
`\get@index@command`: Debug `\get@index@command` and compatibility with `hyperref` package. 164
`\newhookcommand@series@reload`: Debug `\beforenotesX` and `\maxhnotesX` which didn't work. 139
`\prevpage@num`: Correct `\parafootsep` when using with `ledgroup`. . 111
- v1.8.1.
General: Debug endnotes when more than one series is used (change the position where tools for endnotes are defined). . . 130
- v1.8.2.
General: Debug compatibility problem with `hebrew` option of `babel` package. 1
- v1.8.3.
General: Fixes spurious spaces added by v1.7.0. 1
- v1.8.5.
General: Debug indexing in right column, with `eledpar`. . . . 164
- v1.9.0.
`\doextrafeet`: Add `\fnpos` to choice the order of footnotes. . . . 146
`\l@dfheetendmini`: Add `\mpfnpos` to choice the order of footnotes in minipage / `ledgroup`. . . . 160
- v1.10.0.
General: Add `\pstartref` and `\xpstartref` to refer to a `pstart` number (extension of `\edlabel`). 1
`\endquote`: Correction of sectioning commands in parallel texts. . 196
- v1.10.1.
General: Compatibility with `cleveref`. 1

v1.10.2.	General: Compatibility of stanza with v1.8a of babel-greek.	1		
v1.10.3.	General: Debug of cross-referencing.	1		
v1.10.4.	General: Debug of critical notes in edtabular environment.	1		
v1.10.5.	General: Debug of <code>\pausenumbering</code>	1		
	Debug of <code>\xxref</code>	1		
v1.10.6.	General: Debug of interaction between <code>\autopar</code> and <code>\pausenumbering</code>	1		
v1.11.0.	General: Add hooks to disable the font selection for lemma in footnote.	17		
v1.11.1.	General: Correct a bug when a critical note starts with plus or minus.	1		
v1.12.0.	<code>\@nl@reg</code> : To ensure compatibility with <code>\musixtex</code> , <code>\@l</code> becomes <code>\@l</code> . Consequently, <code>\@l@reg</code> becomes <code>\@nl@reg</code>	62		
	General: Add <code>\ledinnernote</code> and <code>\ledouternote</code> commands. . .	27		
	Add hyperlink to crossref (needs hyperref package).	25		
	Compatibility with <code>musixtex</code> . . .	1		
	Debug <code>eledmac</code> sectioning command after using <code>\resumenumbering</code>	1		
	New hooks: <code>\afterXrule</code> and <code>\aftererruleX</code>	18		
	New options for ragged-paragraph notes	18		
	New sectioning commands. . . .	32		
	Optional arguments for <code>\pstart</code> and <code>\pend</code>	7		
	<code>\edindex</code> : Use correctly default index when <code>imakeidx</code> is loaded.	165		
	<code>\endquote</code> : <code>\ledxxx</code> sectioning commands are deprecated and replaced by <code>\eledxxx</code> commands.	196		
	<code>\ifeledmac@check@imakeidx</code> : Ensure that <code>imakeidx</code> is loaded before <code>eledmac</code>	164		
	<code>\ifledRcol@</code> : Add <code>\ifledRcol@</code> for <code>eledpar</code>	47		
	<code>\initnumbering@reg</code> : <code>\beginnumbering</code> is defined only on <code>eledmac</code> , not on <code>eledpar</code>	48		
	<code>\l@dcnote</code> : <code>\l@dlsnote</code> , <code>\l@drsnote</code> and <code>\l@dcnote</code> defined only one time, in <code>eledmac</code> , including needs for <code>eledpar</code> case.	156		
	<code>\l@dgetsidenote@margin</code> : <code>\sidenotemargin</code> is now directly defined in <code>eledmac</code> to be able to manage <code>eledpar</code>	155		
	<code>\l@dunhbox@line</code> : <code>\do@line</code> is split in more little commands. . . .	83		
	<code>\newhookcommand@series@reload</code> : Debug <code>\beforenotesX</code> and <code>\maxhnotesX</code> which didn't work when called after <code>\footparagraphX</code>	139		
	Debug <code>\beforeXnotes</code> and <code>\maxhXnotes</code> which didn't work when called after <code>\footparagraph</code>	139		
	<code>\pend</code> : New optional argument for <code>\pend</code> , to execute code after it.	81		
	<code>\pstart</code> : New optional argument for <code>\pstart</code> , to execute code before it.	80		
	<code>\stanza</code> : <code>&</code> can have an optional argument: content to be printed after.	175		
	<code>\Stanza</code> can have an optional argument: content to be printed before.	175		
	Add <code>\newverse</code> macro, <code>\falseverse</code> deprecated. . .	175		
v1.12.1.	<code>\wrap@edcrossref</code> : Fix spurious spaces.	151		
v1.12.2.	<code>\l@dunhbox@line</code> : Fix a bug with critical notes at the tops of pages (added by v12.0.0)	83		

- v1.12.3.
 General: Add macros for new messages since v0.7 42
 Correct bug with side and familiar notes in tabular environments. 1
 Debug `\eledxxx` with some paper size 1
 Debug `\ledinnernote` and `\ledouternote` commands in the top of pages. 27
 Debug left and right notes (bugs added by 1.12.0) 1
 Underline lemma in `\eledxxx` when using draft mode. 1
`\eledmac@error`: Replaced error messages 42
`\flag@end`: `\flag@start` and `\flag@end` are now defined only one time for `eledmac` and `eledpar` 69
`\flag@start` send a error message when a `\edtext` is done without insert (note) 69
- v1.12.4.
 General: Debug spurious page breaks before `\chapter` (bug added by 1.12.0) 1
- v1.12.5.
`\@edindex@hyperref`: Debug `\edindex` when `hyperref` is not loaded 168
`\@ssect`: Debug `\eledchapter` in parallel with `memoir` 201
`\doinsidelinehook`: Added `\dolinehook` and `\doinsidelinehook` 84
`\endnumbering`: Allow to mix parallel columns and normal text when using `\pausenumbering` 49
`\l@dgobblearg`: `\l@dgobblearg` becomes `\l@dgobbeloptarg` 180
`\l@drestoreforedtext`: Debug optional arguments of `\Xfootnote` in tabular context 182
`\resumenumbering`: Debug `\resumenumbering` 50
- v1.12.6.
`\noeledsec`: Add `\noeledsec` macro. 204
- v1.12.7.
`\wrap@edcrossref`: `\wrap@edcrossref` is now robust 151
- v1.12.8.
`\flag@end`: `\flag@start` don't send a error message when a `\edtext` is done without insert (note) but have a endnote 69
- v1.13.0.
 General: Add `\Xnoteswidthliketwocolumns` and `\notesXwidthliketwocolumns` 19
`\ifledsecnolinenumber`: Added `widthliketwocolumns` option 41
`\newhooktoggle@series`: Add `\newhookcommand@toggle@reload` 140
`\para@footsetupX`: In `\para@footsetupX`, use `\columnwidth` instead of `\hsize` 125
- v1.13.1.
 General: Coming back of page and line breaking penalties's management, deleted by error in v0.17. 1
 Debug quotation environment inside of a `\pstart` when preceded by a sectioning command. 1
`\thepstart`: Add `\l@dzeropenalties` in `\pstart` 80
- v1.13.2.
 General: Fix bug with normal footnotes, added by v1.13.0. 1
`\ifledRcol@`: Add `\ifl@dpaging` for `eledpar` 47
- v1.13.3.
 General: Fix extra spaces with paragraphed footnotes, added by v1.13.0. 1
- v1.13.4.
 General: Fix bug with index when `memoir` class is used without `hyperref` 1
- v1.14.0.
 General: Debug spurious characters before endnotes. 130
 Delete previous override of `\l@d@wrindexhyp` at the beginning of a document when `hyperref` was not loaded. 169

Moves gobbling command	46	vantage of imakeidx even when	
Provide <code>\gobblefour</code>	46	memoir class is used	165
<code>\edindex</code> : Let <code>eledmac</code> take ad-			