

# eledmac

## A presumptuous attempt to port EDMAC, TABMAC and EDSTANZA to LaTeX\*

Peter Wilson

Herries Press<sup>†</sup>

Maïeul Rouquette<sup>‡</sup>

based on the original work by

John Lavagnino, Dominik Wujastyk, Herbert Breger and Wayne Sullivan

### Abstract

EDMAC, a set of PLAIN T<sub>E</sub>X macros, was made at the beginning of 90's for typesetting critical editions in the traditional way, i.e., similar to the Oxford Classical Texts, Teubner, Arden Shakespeare and other series. A separate set of PLAIN T<sub>E</sub>X macros, TABMAC, provides for tabular material. Another set of PLAIN T<sub>E</sub>X macros, EDSTANZA, assists in typesetting verse.

The eledmac package makes the EDMAC, TABMAC and EDSTANZA facilities available to authors who would prefer to use LaTeX. The principal functions provided by the package are marginal line numbering and multiple series of footnotes and endnotes keyed to line numbers.

In addition to the EDMAC, TABMAC and EDSTANZA functions the package also provides for index entries keyed to both page and line numbers. Multiple series of the familiar numbered footnotes are also available.

Other LaTeX packages for critical editions include EDNOTES, and poemscol for poetical works.

In October 2012, Maïeul Rouquette released the *eledform* package<sup>1</sup>. Based on eledmac, this package provides tools for creating a formal description (formalism) of textual variants.

To report bugs, please go to ledmac's GitHub page and click "New Issue": <https://github.com/maieul/ledmac/issues/>. You must open an account with github.com to access my page (maieul/ledmac). GitHub accounts are free for open-source users.

You can subscribe to the eledmac mail list in:

<https://lists.berlios.de/pipermail/ledmac-users/>

---

\*This file (eledmac.dtx) has version number v1.4.7, last revised 2013/06/07.

<sup>†</sup>herries dot press at earthlink dot net

<sup>‡</sup>maieul at maieul dot net

<sup>1</sup><http://www.ctan.org/eledform>.

## Contents

<b>1</b>	<b>Introduction</b>	<b>5</b>
1.1	Overview . . . . .	5
1.2	History . . . . .	6
1.2.1	EDMAC . . . . .	6
1.2.2	eledmac . . . . .	8
<b>2</b>	<b>The eledmac package</b>	<b>8</b>
<b>3</b>	<b>Numbering text lines and paragraphs</b>	<b>9</b>
3.1	Lineation commands . . . . .	11
3.2	Changing the line numbers . . . . .	12
<b>4</b>	<b>The apparatus</b>	<b>14</b>
4.1	Commands . . . . .	14
4.2	Alternate footnote formatting . . . . .	16
4.3	Display options . . . . .	17
4.3.1	Control line number printing . . . . .	17
4.3.2	Separator between the lemma and the note content . . . . .	18
4.3.3	Font style . . . . .	19
4.3.4	Styles of notes content . . . . .	19
4.3.5	Arbitrary code at the beginning of notes . . . . .	19
4.3.6	Options for notes in columns . . . . .	20
4.3.7	Options for paragraphed footnotes . . . . .	20
4.3.8	Options for block of notes . . . . .	20
4.4	Page layout . . . . .	21
4.5	Fonts . . . . .	21
4.6	Create a new series . . . . .	22
<b>5</b>	<b>Verse</b>	<b>22</b>
5.1	Hanging symbol . . . . .	24
<b>6</b>	<b>Grouping</b>	<b>24</b>
<b>7</b>	<b>Crop marks</b>	<b>25</b>
<b>8</b>	<b>Endnotes</b>	<b>25</b>
<b>9</b>	<b>Cross referencing</b>	<b>25</b>
<b>10</b>	<b>Side notes</b>	<b>27</b>
<b>11</b>	<b>Familiar footnotes</b>	<b>28</b>
<b>12</b>	<b>Indexing</b>	<b>28</b>
<b>13</b>	<b>Tabular material</b>	<b>29</b>

<i>Contents</i>	3
<b>14 Sectioning commands</b>	<b>32</b>
<b>15 Quotation environments</b>	<b>33</b>
<b>16 Miscellaneous</b>	<b>34</b>
16.1 Known and suspected limitations . . . . .	34
16.2 Use with other packages . . . . .	35
16.3 Parallel typesetting . . . . .	36
16.4 Notes for EDMAC users . . . . .	36
<b>17 Implementation overview</b>	<b>39</b>
<b>18 Preliminaries</b>	<b>39</b>
18.1 Messages . . . . .	41
<b>19 Sectioning commands</b>	<b>43</b>
<b>20 Line counting</b>	<b>48</b>
20.1 Choosing the system of lineation . . . . .	48
20.2 List macros . . . . .	53
20.3 Line-number counters and lists . . . . .	54
20.4 Reading the line-list file . . . . .	57
20.5 Commands within the line-list file . . . . .	59
20.6 Writing to the line-list file . . . . .	66
<b>21 Marking text for notes</b>	<b>69</b>
21.1 <code>\edtext</code> and <code>\critext</code> themselves . . . . .	70
21.2 Substitute lemma . . . . .	75
21.3 Substitute line numbers . . . . .	75
<b>22 Paragraph decomposition and reassembly</b>	<b>76</b>
22.1 Boxes, counters, <code>\pstart</code> and <code>\pend</code> . . . . .	76
22.2 Processing one line . . . . .	79
22.3 Line and page number computation . . . . .	80
22.4 Line number printing . . . . .	83
22.5 Pstart number printing in side . . . . .	87
22.6 Add insertions to the vertical list . . . . .	88
22.7 Penalties . . . . .	89
22.8 Printing leftover notes . . . . .	90
<b>23 Footnotes</b>	<b>91</b>
23.1 Fonts . . . . .	91
23.2 Outer-level footnote commands . . . . .	91
23.3 Standard footnote definitions . . . . .	98
23.4 Paragraphed footnotes . . . . .	100
23.4.1 Insertion of the footnotes separator . . . . .	105
23.5 Columnar footnotes . . . . .	106

<b>24 Familiar footnotes</b>	<b>110</b>
24.1 Generality . . . . .	110
24.2 Two columns footnotes . . . . .	115
24.3 Three columns footnotes . . . . .	116
24.4 Paragraphed footnotes . . . . .	117
24.5 Footnotes' output . . . . .	120
<b>25 Generate series</b>	<b>120</b>
25.0.1 Test if series is still existing . . . . .	121
25.0.2 Create all commands to memorize display options . . . . .	121
25.0.3 Create inserts, needed to add notes in foot . . . . .	122
25.0.4 Create command for critical apparatus, <code>\Xfootnote</code> . . . . .	122
25.0.5 Create tools for familiar footnotes ( <code>\footnoteX</code> ) . . . . .	123
25.0.6 The endnotes . . . . .	123
25.0.7 Init standards series (A,B,C,D,E,Z) . . . . .	124
25.0.8 Some tools . . . . .	124
25.0.9 Old commands, kept for backward compatibility . . . . .	127
25.0.10 Hooks for a particular footnote . . . . .	127
25.0.11 Alias . . . . .	128
25.0.12 Line number printing . . . . .	128
<b>26 Output routine</b>	<b>130</b>
<b>27 Cross referencing</b>	<b>136</b>
<b>28 Endnotes</b>	<b>140</b>
<b>29 Side notes</b>	<b>143</b>
<b>30 Minipages and such</b>	<b>146</b>
<b>31 Indexing</b>	<b>149</b>
<b>32 Macro as environment</b>	<b>152</b>
<b>33 Verse</b>	<b>155</b>
<b>34 Arrays and tables</b>	<b>158</b>
<b>Appendix A Migration from ledmac to eledmac</b>	<b>178</b>
<b>References</b>	<b>179</b>
<b>Index</b>	<b>179</b>
<b>Change History</b>	<b>195</b>

# List of Figures

## 1 Introduction

The **EDMAC** macros [LW90] for typesetting critical editions of texts have been available for use with TeX since 90's. Since **EDMAC** was introduced there has been a small but constant demand for a version of **EDMAC** that could be used with LaTeX. The **eledmac** package is an attempt to satisfy that request.

**eledmac** would not have been possible without the amazing work by John Lavagnino and Dominik Wujastyk, the original authors of **EDMAC**. I, Peter Wilson, am very grateful for their encouragement and permission to use **EDMAC** as a base. The majority of both the code and this manual are by these two. The tabular material is based on the **TABMAC** code [Bre96], by permission of its author, Herbert Breger. The verse-related code is by courtesy of Wayne Sullivan, the author of **EDSTANZA** [Sul92], who has kindly supplied more than his original macros.

Since 2011's Maieul Rouquette begun to maintain and extend **eledmac**. As plain TeX is used by little people, and LaTeX by more people **eledmac** and original **EDMAC** are more and more distant.

### 1.1 Overview

The **eledmac** package, together with LaTeX, provides several important facilities for formatting critical editions of texts in a traditional manner. Major features include:

- automatic stepped line numbering, by page or by section;
- sub-lineation within the main series of line numbers;
- variant readings automatically keyed to line numbers;
- caters for both prose and verse;
- multiple series of the footnotes and endnotes;
- block or columnar formatting of the footnotes;
- simple tabular material may be line numbered;
- indexing keyed to page and line numbers.

**eledmac** allows the scholar engaged in preparing a critical edition to focus attention wholly on the task of creating the critical text and evaluating the variant readings, text-critical notes and testimonia. LaTeX and **eledmac** will take care of the formatting and visual correlation of all the disparate types of information.

The original **EDMAC** can be used as a 'stand alone' processor or as part of a process. One example is its use as the formatting engine or 'back end' for the output of an automatic manuscript collation program. **COLLATE**, written by Peter Robinson, runs on the Apple Macintosh, can collate simultaneously up to a hundred manuscripts of any length, and provides facilities for the scholar to tailor

the collation interactively. For further details of this and other related work, visit the EDMAC home page at <http://www.homepages.ucl.ac.uk/~ucgadkw/edmac/index.html>.

Apart from `eledmac` there are some other LaTeX packages for critical edition typesetting. As Peter Wilson is not an author, or even a prospective one, of any critical edition work he could not provide any opinions on what authors in this area might feel comfortable with or how well any of the packages meet their needs.

EDNOTES [Lüc03], by Uwe Lück and Christian Tapp, is another LaTeX package being developed for critical editions. Unlike `eledmac` which is based on EDMAC, EDNOTES takes a different (internal) approach and provides a different set of features. For example it provides additional facilities for overlapping lemmas and for handling tables. For more information there is a web site at <http://ednotes.sty.de.vu> or email to [ednotes.sty@web.de](mailto:ednotes.sty@web.de).

The `poemscol` package [Bur01] by John Burt is designed for typesetting critical editions of collections of poems. I do not know how, or whether, `poemscol` and `eledmac` will work together.

Critical authors may find it useful to look at EDMAC, EDNOTES, `eledmac`, and `poemscol` to see which best meets their needs.

At the time of writing Peter Wilson knows of two web sites, apart from the EDMAC home page, that have information on `eledmac`, and other programs.

- Jerónimo Leal pointed me to <http://www.guit.sssup.it/latex/critical.html>. This also mentions another package for critical editions called MauroTeX (<http://www.maurolico.unipi.it/mtex/mtex.htm>). These sites are both in Italian.
- Dirk-Jan Dekker maintains <http://www.djdekker.net/ledmac> which is a FAQ for typesetting critical editions and `eledmac`.

This manual contains a general description of how to use the LaTeX version of EDMAC, namely `eledmac` (in sections 2 through 16.4); the complete source code for the package, with extensive documentation (in sections 17 and following) ; and an Index to the source code. We do not suggest that you need to read the source code for this package in order to use it; we provide this code primarily for reference, and many of our comments on it repeat material that is also found in the earlier sections. But no documentation, however thorough, can cover every question that comes up, and many can be answered quickly by consultation of the code. On a first reading, we suggest that you should read only the general documentation in sections 2, unless you are particularly interested in the innards of `eledmac`.

## 1.2 History

### 1.2.1 EDMAC

The original version of EDMAC was `TEXTED.TEX`, written by John Lavagnino in late 1987 and early 1988 for formatting critical editions of English plays.

John passed these macros on to Dominik Wujastyk who, in September–October 1988, added the footnote paragraphing mechanism, margin swapping and other

changes to suit his own purposes, making the style more like that traditionally used for classical texts in Latin and Greek (e.g., the Oxford Classical Texts series). He also wrote some extra documentation and sent the files out to several people. This version of the macros was the first to be called **EDMAC**.

The present version was developed in the summer of 1990, with the intent of adding necessary features, streamlining and documenting the code, and further generalizing it to make it easily adaptable to the needs of editors in different disciplines. John did most of the general reworking and documentation, with the financial assistance of the Division of the Humanities and Social Sciences, California Institute of Technology. Dominik adapted the code to the conventions of Frank Mittelbach's **doc** option, and added some documentation, multiple-column footnotes, cross-references, and crop marks.<sup>2</sup> A description by John and Dominik of this version of **EDMAC** was published as 'An overview of **EDMAC**: a **PLAIN T<sub>E</sub>X** format for critical editions', *TUGboat* 11 (1990), pp. 623–643.

From 1991 through 1994, the macros continued to evolve, and were tested at a number of sites. We are very grateful to all the members of the (now defunct) **edmac@mailbase.ac.uk** discussion group who helped us with smoothing out bugs and infelicities in the macros. Ron Whitney and our anonymous reviewer at the TUG were both of great help in ironing out last-minute wrinkles, while Ron made some important suggestions which may help to make future versions of **EDMAC** even more efficient. Wayne Sullivan, in particular, provided several important fixes and contributions, including adapting the Mittelbach/Schöpf 'New Font Selection Scheme' for use with **PLAIN T<sub>E</sub>X** and **EDMAC**. Another project Wayne has worked on is a DVI post-processor which works with an **EDMAC** that has been slightly modified to output **\specials**. This combination enables you to recover to some extent the text of each line, as ASCII code, facilitating the creation of concordances, an *index verborum*, etc.

At the time of writing (1994), we are pleased to be able to say that **EDMAC** is being used for real-life book production of several interesting editions, such as the Latin texts of Euclid's *Elements*,<sup>3</sup> an edition of the letters of Nicolaus Copernicus,<sup>4</sup> Simon Bredon's *Arithmetica*,<sup>5</sup> a Latin translation by Plato of Tivoli of an Arabic astrolabe text,<sup>6</sup> a Latin translation of part II of the Arabic *Algebra* by Abū Kāmil Shujā' b. Aslam,<sup>7</sup> the Latin *Rithmachia* of Werinher von Tegernsee,<sup>8</sup> a middle-Dutch romance epic on the Crusades,<sup>9</sup> a seventeenth-century Hungar-

<sup>2</sup>This version of the macros was used to format the Sanskrit text in volume I of *Metarules of Pāṇinian Grammar* by Dominik Wujastyk (Groningen: Forsten, 1993).

<sup>3</sup>Gerhard Brey used **EDMAC** in the production of Hubert L. L. Busard and Menso Folkerts, *Robert of Chester's (?) Redaction of Euclid's Elements, the so-called Adelard II Version*, 2 vols., (Basel, Boston, Berlin: Birkhäuser, 1992).

<sup>4</sup>Being prepared at the German Copernicus Research Institute, Munich.

<sup>5</sup>Being prepared by Menso Folkerts *et al.*, at the Institut für Geschichte der Naturwissenschaften in Munich.

<sup>6</sup>Richard Lorch, Gerhard Brey *et al.*, at the same Institute.

<sup>7</sup>Richard Lorch, 'Abū Kāmil on the Pentagon and Decagon' in *Vestigia Mathematica*, ed. M. Folkerts and J. P. Hogendijk (Amsterdam, Atlanta: Rodopi, 1993).

<sup>8</sup>Menso Folkerts, 'Die *Rithmachia* des Werinher von Tegernsee', *ibid.*

<sup>9</sup>Geert H. M. Claassens, *De Middelnederlandse Kruisvaartromans*, (Amsterdam: Schipphower en Brinkman, 1993).

ian politico-philosophical tract,<sup>10</sup> an anonymous Latin compilation from Hungary entitled *Sermones Compilati in Studio Generali Quinqueecclesiensi in Regno Ungarie*,<sup>11</sup> the collected letters and papers of Leibniz,<sup>12</sup> Theodosius's *Spherics*, the German *Algorismus* of Sacrobosco, the Sanskrit text of the *Kāśikāvṛtti* of Vāmana and Jayāditya,<sup>13</sup> and the English texts of Thomas Middleton's collected works.

### 1.2.2 eledmac

Version 1.0 of **TABMAC** was released by Herbert Breger in October 1996. This added the capability for typesetting tabular material.

Version 0.01 of **EDSTANZA** was released by Wayne Sullivan in June 1992, to help a colleague with typesetting Irish verse.

In March 2003 Peter Wilson started an attempt to port **EDMAC** from TeX to LaTeX. The starting point was **EDMAC** version 3.16 as documented on 19 July 1994 (available from CTAN). In August 2003 the **TABMAC** functions were added; the starting point for these being version 1.0 of October 1996. The **EDSTANZA** (v0.01) functions were added in February 2004. Sidenotes and regular footnotes in numbered text were added in April 2004.

This port was called *ledmac*.

Since July 2011, *ledmac* is maintained by Maïeul Rouquette.

Important changes were put in version 1.0, to make *eledmac* more easily extensible (see 4.3 p.17). They can make some little troubles with old customization. That is why a new name was selected: *eledmac*. To migrate from *ledmac* to *eledmac*, please read Appendix Appendix A (p.178).

## 2 The *eledmac* package

*eledmac* is a three-pass package like LaTeX itself. Although your textual apparatus and line numbers will be printed even on the first run, it takes two more passes through LaTeX to be sure that everything gets to its right place. Any changes you make to the input file may similarly require three passes to get everything to the right place, if the changes alter the number of lines or notes. *eledmac* will tell you that you need to make more runs, when it notices, but it does not expend the labor to check this thoroughly. If you have problems with a line or two misnumbered at the top of a page, try running LaTeX once or twice more.

A file may mix *numbered* and *unnumbered* text. Numbered text is printed with marginal line numbers and can include footnotes and endnotes that are referenced to those line numbers: this is how you'll want to print the text that you're editing. Unnumbered text is not printed with line numbers, and you can't use *eledmac*'s

<sup>10</sup>Emil Hargittay, *Csáky István: Politica philosophiai Okoskodás-szerint való rendes életnek példája (1664–1674)* (Budapest: Argumentum Kiadó, 1992).

<sup>11</sup>Being produced, as was the previous book, by Gyula Mayer in Budapest.

<sup>12</sup>Leibniz, *Sämtliche Schriften und Briefe*, series I, III, VII, being edited by Dr. H. Breger, Dr. N. Gädeke and others, at the Leibniz-Archiv, Niedersächsische Landesbibliothek, Hannover. (see <http://www.nlb-hannover.de/Leibniz>)

<sup>13</sup>Being prepared at Poona and Lausanne Universities.



note commands with it: this is appropriate for introductions and other material added by the editor around the edited text.

### 3 Numbering text lines and paragraphs

`\beginnumbering` Each section of numbered text must be preceded by `\beginnumbering` and followed by `\endnumbering`, like:

```
\beginnumbering
<text>
\endnumbering
```

The `\beginnumbering` macro resets the line number to zero, reads an auxiliary file called `<jobname>.nn` (where `<jobname>` is the name of the main input file for this job, and `nn` is 1 for the first numbered section, 2 for the second section, and so on), and then creates a new version of this auxiliary file to collect information during this run. The first instance of `\beginnumbering` also opens a file called `<jobname>.end` to receive the text of the endnotes. `\endnumbering` closes the `<jobname>.nn` file.

If the line numbering of a text is to be continuous from start to end, then the whole text will be typed between one pair of `\beginnumbering` and `\endnumbering` commands. But your text will most often contain chapter or other divisions marking sections that should be independently numbered, and these will be appropriate places to begin new numbered sections. `eledmac` has to read and store in memory a certain amount of information about the entire section when it encounters a `\beginnumbering` command, so it speeds up the processing and reduces memory use when a text is divided into a larger number of sections (at the expense of multiplying the number of external files that are generated).

`\pstart` Within a numbered section, each paragraph of numbered text must be marked using the `\pstart` and `\pend` commands:

```
\pstart
<paragraph of text>
\pend
```

Text that appears within a numbered section but isn't marked with `\pstart` and `\pend` will not be numbered.

The following example shows the proper section and paragraph markup, and the kind of output that would typically be generated:

```

\beginnumbering
\pstart
This is a sample paragraph, with
lines numbered automatically.
\pend

```

1 This is a sample paragraph  
2 with lines numbered  
3 automatically.

```

\pstart
This paragraph too has its
lines automatically numbered.
\pend

```

4 This paragraph too  
5 has its lines automatically  
6 numbered.

The lines of this paragraph are  
not numbered.

The lines of this paragraph  
are not numbered.

```

\pstart
And here the numbering begins
again.
\pend
\endnumbering

```

7 And here the numbering  
8 begins again.

`\autopar` You can use `\autopar` to avoid the nuisance of this paragraph markup and still have every paragraph automatically numbered. The scope of the `\autopar` command needs to be limited by keeping it within a group, as follows:

```

\begingroup
\beginnumbering
\autopar

```

A paragraph of numbered text.

1 A paragraph of numbered  
2 text.

Another paragraph of numbered  
text.

3 Another paragraph of  
4 numbered text.

```

\endnumbering
\endgroup

```

`\autopar` fails, however, on paragraphs that start with a `{` or with any other command that starts a new group before it generates any text. Such paragraphs need to be started explicitly, before the new group is opened, using `\indent`, `\noindent`, or `\leavevmode`, or using `\pstart` itself.<sup>14</sup>

`\firstlinenum` By default, `eledmac` numbers every 5th line. There are two counters, `\firstlinenum` and `linenumincrement`, that control this behaviour; they can be changed using `\firstlinenum{<num>}` and `\linenumincrement{<num>}`. `\firstlinenum` specifies the first line that will have a printed number, and `\linenumincrement` is the difference between successive numbered lines. For example, to start printing numbers at the first line and to have every other line numbered:

```
\firstlinenum{1} \linenumincrement{2}
```

<sup>14</sup>For a detailed study of the reasons for this restriction, see Barbara Beeton, 'Initiation rites', *TUGboat* **12** (1991), pp. 257–258.

There are similar commands, `\firstsublinenum{⟨num⟩}` and `\sublinenumincrement{⟨num⟩}` for controlling sub-line numbering.

`eledmac` stores a lot of information about line numbers and footnotes in memory as it goes through a numbered section. But at the end of such a section, it empties its memory out, so to speak. If your text has a very long numbered section it is possible that your LaTeX may reach its memory limit. There are two solutions to this. The first is to get a larger LaTeX with increased memory. The second solution is to split your long section into several smaller ones. The trouble with this is that your line numbering will start again at zero with each new section. To avoid this problem, we provide `\pausenumbering` and `\resumenumbering` which are just like `\endnumbering ... \beginnumbering`, except that they arrange for your line numbering to continue across the break. Use `\pausenumbering` only between numbered paragraphs:

```
\beginnumbering
\pstart
Paragraph of text.
\pend
\pausenumbering
1 Paragraph of
2 text.
\resumenumbering
3 Another paragraph.
\pstart
Another paragraph.
\pend
\endnumbering
```

We have defined these commands as two macros, in case you find it necessary to insert text between numbered sections without disturbing the line numbering. But if you are really just using these macros to save memory, you might as well say

```
\newcommand{\memorybreak}{\pausenumbering\resumenumbering}
```

and say `\memorybreak` between the relevant `\pend` and `\pstart`.

It's possible to insert a number at every `\pstart` command. You must use `\numberpstarttrue` the `\numberpstarttrue` command to have it. You can stop the numbering with `\numberpstartfalse`. You can redefine the command `\thepstart` to change `\thepstart` style. On each `\beginnumbering` the numbering restarts.

With the `\sidepstartnumtrue` command, the number of `\pstart` will be printed in side. In this case, the line number will be not printed.

With the `\labelpstarttrue` command, a `\label` added just after a `\pstart` will refer to the number of this `pstart`.

### 3.1 Lineation commands

<code>\numberlinefalse</code>	Line numbering can be disabled with <code>\numberlinefalse</code> . It can be enabled again
<code>\numberlinetrue</code>	with <code>\numberlinetrue</code> . Lines can be numbered either by page, by pstart or
<code>\lineation</code>	by section; you specify this using the <code>\lineation{&lt;arg&gt;}</code> macro, where <arg> is

either `page`, `pstart` or `section`. You may only use this command at places where numbering is not in effect; you can't change the lineation system within a section. You can change it between sections: they don't all have to use the same lineation system. The package's standard setting is `\lineation{section}`. If the lineation is by `pstart`, the `pstart` number will be printed before the line number in the notes.

`\linenummargin`

The command `\linenummargin{location}` specifies the margin where the line (or `pstart`) numbers will be printed. The permissible value for `location` is one out of the list `left`, `right`, `inner`, or `outer`, for example `\linenummargin{inner}`. The package's default setting is

`\linenummargin{left}`

to typeset the numbers in the left hand margin. You can change this whenever you're not in the middle of making a paragraph.

More precisely, the value of `\linenummargin` used is that in effect at the `\pend` of a numbered paragraph. Apart from an initial setting for `\linenummargin`, only change it after a `\pend`, whereupon it will apply to all following numbered paragraphs, until changed again (changing it between a `\pstart` and `\pend` pair will apply the change to all the current paragraph).

`\firstlinenum`

`\linenumincrement`

`\firstsublinenum`

`\sublinenumincrement`

In most cases, you will not want a number printed for every single line of the text. Four L<sup>A</sup>T<sub>E</sub>X counters control the printing of marginal numbers and they can be set by the macros `\firstlinenum{num}`, etc. `\firstlinenum` specifies the number of the first line in a section to number, and `\linenumincrement` is the increment between numbered lines. `\firstsublinenum` and `\sublinenumincrement` do the same for sub-lines. Initially, all these are set to 5 (e.g., `\firstlinenum{5}`).

`\linenumberlist`

You can define `\linenumberlist` to specify a non-uniform distribution of printed line numbers. For example:

`\def\linenumberlist{1,2,3,5,7,11,13,17,19,23,29}`

to have numbers printed on prime-numbered lines only. There must be no spaces within the definition which consists of comma-separated decimal numbers. The numbers can be in any order but it is easier to read if you put them in numerical order. Either omitting the definition of `\linenumberlist` or following the vacuous definition

`\def\linenumberlist{}`

the standard numbering sequence is applied. The standard sequence is that specified by the combination of the `firstlinenum`, `linenumincrement`, `firstsublinenum` and `linenumincrement` counter values.

`\leftlinenum`

`\rightlinenum`

`\linenumsep`

When a marginal line number is to be printed, there are a lot of ways to display it. You can redefine `\leftlinenum` and `\rightlinenum` to change the way marginal line numbers are printed in the left and right margins respectively; the initial versions print the number in font `\numlabfont` (described below) at a distance `\linenumsep` (initially set to one pica) from the text.

## 3.2 Changing the line numbers

Normally the line numbering starts at 1 for the first line of a section and steps up by one for each line thereafter. There are various common modifications of this

system, however; the commands described here allow you to put such modifications into effect.

**\startsub**     You insert the **\startsub** and **\endsub** commands in your text to turn sub-lineation on and off. In plays, for example, stage directions are often numbered with sub-line numbers: as line 10.1, 10.2, 10.3, rather than as 11, 12, and 13. Titles and headings are sometimes numbered with sub-line numbers as well.

When sub-lineation is in effect, the line number counter is frozen and the sub-line counter advances instead. If one of these commands appears in the middle of a line, it doesn't take effect until the next line; in other words, a line is counted as a line or sub-line depending on what it started out as, even if that changes in the middle.

**\startlock**     The **\startlock** command, used in running text, locks the line number at its current value, until you say **\endlock**. It can tell for itself whether you are in a patch of line or sub-line numbering. One use for line-number locking is in printing poetry: there the line numbers should be those of verse lines rather than of printed lines, even when a verse line requires several printed lines.

**\lockdisp**     When line-number locking is used, several printed lines may have the same line number, and you have to specify whether you want the number attached to the first printed line or the last, or whether you just want the number printed by them all. (This assumes that, on the basis of the settings of the previous parameters, it is necessary to display a line number for this line.) You specify your preference using **\lockdisp{<arg>}**; its argument is a word, either **first**, **last**, or **all**. The package initially sets this as **\lockdisp{first}**.

**\setline**     In some cases you may want to modify the line numbers that are automatically calculated: if you are printing only fragments of a work but want to print line numbers appropriate to a complete version, for example. The **\setline{<num>}** and **\advanceline{<num>}** commands may be used to change the current line's number (or the sub-line number, if sub-lineation is currently on). They change both the marginal line numbers and the line numbers passed to the notes. **\setline** takes one argument, the value to which you want the line number set; it must be 0 or greater. **\advanceline** takes one argument, an amount that should be added to the current line number; it may be positive or negative.

**\setlinenum**     The **\setline** and **\advanceline** macros should only be used within a **\pstart...pend** group. The **\setlinenum{<num>}** command can be used outside such a group, for example between a **pend** and a **\pstart**. It sets the line number to **<num>**. It has no effect if used within a **\pstart...pend** group

**\linenumberstyle**     Line numbers are normally printed as arabic numbers. You can use **\linenumberstyle{<style>}**  
**\sublinenumberstyle** to change the numbering style. **<style>** must be one of:

**Alph** Uppercase letters (A...Z).

**alph** Lowercase letters (a...z).

**arabic** Arabic numerals (1, 2, ...)

**Roman** Uppercase Roman numerals (I, II, ...)

**roman** Lowercase Roman numerals (i, ii, ...)

Note that with the `Alph` or `alph` styles, ‘numbers’ must be between 1 and 26 inclusive.

Similarly `\sublinenumberstyle{<style>}` can be used to change the numbering style of sub-line numbers, which is normally arabic numerals.

`\skipnumbering` When inserted into a numbered line the macro `\skipnumbering` causes the numbering of that particular line to be skipped; that is, the line number is unchanged and no line number will be printed.

## 4 The apparatus

### 4.1 Commands

`\edtext` Within numbered paragraphs, all footnotes and endnotes are generated by the `\edtext` macro:

`\edtext{<lemma>}{<commands>}`

The `<lemma>` argument is the lemma in the main text: `\edtext` both prints this as part of the text, and makes it available to the `<commands>` you specify to generate notes.

For example:

<code>I saw my friend \edtext{Smith}{</code> <code>\Afootnote{Jones C, D.}}</code> <code>on Tuesday.</code>	1 I saw my friend 2 Smith on Tuesday. 2 Smith] Jones C, D.
---	--

The lemma `Smith` is printed as part of this sentence in the text, and is also made available to the footnote that specifies a variant, `Jones C, D`. The footnote macro is supplied with the line number at which the lemma appears in the main text.

The `<lemma>` may contain further `\edtext` commands. Nesting makes it possible to print an explanatory note on a long passage together with notes on variants for individual words within the passage. For example:

<code>\edtext{I saw my friend</code> <code>\edtext{Smith}{\Afootnote{Jones</code> <code>C, D.}} on Tuesday.}{</code> <code>\Bfootnote{The date was</code> <code>July 16, 1954.}</code> <code>}</code>	1 I saw my friend 2 Smith on Tuesday. 2 Smith] Jones C, D. 1–2 I saw my friend Smith on Tuesday.] The date was July 16, 1954.
--	--

However, `\edtext` cannot handle overlapping but unnested notes—for example, one note covering lines 10–15, and another covering 12–18; a `\edtext` that starts in the `<lemma>` argument of another `\edtext` must end there, too. (The `\lemma` and `\linenum` commands may be used to generate overlapping notes if necessary.)

**Commands used in `\edtext`’s second argument** The second argument of the `\edtext` macro, `<commands>`, may contain a series of subsidiary commands that generate various kinds of notes.

`\Afootnote` Five separate series of the footnotes are maintained; each macro taking one  
`\Bfootnote` argument like `\Afootnote{<text>}`. When all five are used, the A notes appear  
`\Cfootnote` in a layer just below the main text, followed by the rest in turn, down to the E  
`\Dfootnote` notes at the bottom. These are the main macros that you will use to construct  
`\Efootnote` the critical apparatus of your text. The package provides five layers of notes in  
the belief that this will be adequate for the most demanding editions. But it is  
not hard to add further layers of notes should they be required.

An optional argument can be added before the text of the footnote. Its value  
is a comma separated list of options. The available options are:

- `nonum` to disable line numbering for this note.
- `nosep` to disable the lemma separator for this note.

Example: `\Afootnote[nonum]{<text>}`.

`\Aendnote` The package also maintains five separate series of endnotes. Like footnotes  
`\Bendnote` each macro takes a single argument like `\Aendnote{<text>}`. Normally, none of  
`\Cendnote` them are printed: you must use the `\doendnotes` macro described below (p.25)  
`\Dendnote` to call for their output at the appropriate point in your document.

`\Eendnote` By default, no paragraph can be made in the notes of critical apparatus. You  
can allow it by adding the options `parapparatus` when loading the package :

`\usepackage[parapparatus]{eledmac}`

`\lemma` If you want to change the lemma that gets passed to the notes, you can do this  
by using `\lemma{<alternative>}` within the second argument to `\edtext`, before  
the note commands. The most common use of this command is to abbreviate the  
lemma that's printed in the notes. For example:

<code>\edtext{I saw my friend</code>	1 I saw my friend
<code>\edtext{Smith}{\Afootnote{Jones</code>	2 Smith on Tuesday.
<code>C, D.}} on Tuesday.}</code>	<u>2 Smith]</u> Jones C, D.
<code>{\lemma{I \dots\ Tuesday.}</code>	<u>1-2 I ...</u> Tuesday.]
<code>\Bfootnote{The date was</code>	
<code>July 16, 1954.}</code>	The date was July 16, 1954.
<code>}</code>	

`\linenum` You can use `\linenum{<arg>}` to change the line numbers passed to the notes.  
The notes are actually given seven parameters: the page, line, and sub-line num-  
ber for the start of the lemma; the same three numbers for the end of the lemma;  
and the font specifier for the lemma. As the argument to `\linenum`, you specify  
those seven parameters in that order, separated by vertical bars (the | character).  
However, you can retain the value computed by `eledmac` for any number by sim-  
ply omitting it; and you can omit a sequence of vertical bars at the end of the  
argument. For example, `\linenum{||23}` changes one number, the ending page  
number of the current lemma.

This command doesn't change the marginal line numbers in any way; it just  
changes the numbers passed to the footnotes. Its use comes in situations that  
`\edtext` has trouble dealing with for whatever reason. If you need notes for

overlapping passages that aren't nested, for instance, you can use `\lemma` and `\linenum` to generate such notes despite the limitations of `\edtext`. If the `\lemma` argument to `\edtext` is extremely long, you may run out of memory; here again you can specify a note with an abbreviated lemma using `\lemma` and `\linenum`. The numbers used in `\linenum` need not be entered manually; you can use the 'x-' symbolic cross-referencing commands below (p. 25) to compute them automatically.

Similarly, being able to manually change the lemma's font specifier in the notes might be important if you were using multiple scripts or languages. The form of the font specifier is three separate codes separated by / characters, giving the family, series, and shape codes as defined within NFSS.

**Changing the names of these commands** The commands for generating the apparatus have been given rather bland names, because editors in different fields have widely divergent notions of what sort of notes are required, where they should be printed, and what they should be called. But this doesn't mean you have to type `\Afootnote` when you'd rather say something you find more meaningful, like `\variant`. We recommend that you create a series of such aliases and use them instead of the names chosen here; all you have to do is put commands of this form at the start of your file:

```
\let\variant=\Afootnote
\let\explanatory=\Bfootnote
\let\trivial=\Aendnote
\let\testimonia=\Cfootnote
```

**Formalism for textual criticism** If your notes are for textual criticism, you should use the *eledform* package<sup>15</sup>.

This package provides tools to describes the textual variants in a formal way. It is based on *eledmac* for the typographical aspect.

## 4.2 Alternate footnote formatting

If you just launch into *eledmac* using the commands outlined above, you will get a standard layout for your text and notes. You may be happy to accept this at the very beginning, while you get the hang of things, but the standard layout is not particularly pretty, and you will certainly want to modify it in due course. The package provides ways of changing the fonts and layout of your text, but these are not aimed at being totally comprehensive. They are enough to deal with simple variations from the norm, and to exemplify how you might go on to make more significant changes.

`\footparagraph` By default, all footnotes are formatted as a series of separate paragraphs in one column. Three other formats are also available for notes, and using these macros you can select a different format for a series of notes.

`\foottwocol`  
`\footthreecol`

<sup>15</sup><http://www.ctan.org/pkg/eledform>.



- `\footparagraph` formats all the footnotes of a series as a single paragraph;
- `\foottwocol` formats them as separate paragraphs, but in two columns;
- `\footthreecol`, in three columns.

Each of these macros takes one argument: a letter (between A and E) for the series of notes you want changed. So a text with three layers of notes might begin thus:

```
\footnormal{A}
\footthreecol{B}
\footparagraph{C}
```

This would make the A-notes ordinary, B-notes would be in three columns, and the bottom layer of notes would be formed into a paragraph on each page.

### 4.3 Display options

Since version 1.0, some commands can be used to change the display of the footnotes. All can have an optional argument `[\langle s \rangle]`, which is the letter of the series — or a list of letters separated by comma — depending on which option is applied.

When a length, noted  $\langle l \rangle$ , is used, it can be stretchable: **a minus b minus c**. The final length  $m$  is calculated by L<sup>A</sup>T<sub>E</sub>X to have:  $b - a \leq m \leq b + c$ . If you use relative unity<sup>16</sup>, it will be relative to fontsize of the footnote.

#### 4.3.1 Control line number printing

`\numberonlyfirstinline`

By default, the line number is printed in every note. If you want to print it only the first time for a value (i.e one time for line 1, one time for line 2 etc.), you can use `\numberonlyfirstinline[\langle s \rangle]`. Use `\numberonlyfirstinline[\langle s \rangle][\langle false \rangle]` to cancel it (`<s>` can be empty if you want to disable it for every series).

`\numberonlyfirstintwolines`

Suppose you have a lemma on line 2 and a lemma between line 2 and line 3. With `\numberonlyfirstinline`, the second lemma is considered to be on the same line as the first lemma. But if you add `\numberonlyfirstintwolines[\langle s \rangle]`, the distinction is made. Use `\numberonlyfirstintwolines[\langle s \rangle][\langle false \rangle]` to cancel it (`<s>` can be empty if you want to disable it for every series).

`\symlinenum`

For setting a particular symbol in place of the line number, you can use `\symlinenum[\langle s \rangle]{\langle symbol \rangle}` in combination with `\numberonlyfirstinline[\langle s \rangle]`. From the second lemma of the same line, the symbol will be used instead of line number.

`\nonumberinfootnote`

You can use `\nonumberinfootnote[\langle s \rangle]` if you don't want to have the line number in a footnote. To cancel it, use `\nonumberinfootnote[\langle s \rangle][\langle false \rangle]`.

`\pstartinfootnote`

You can use `\pstartinfootnote[\langle s \rangle]` if you want to print the pstart number in the footnote, before the line and subline number. Use `\pstartinfootnote[\langle s \rangle][\langle false \rangle]` to cancel it (`<s>` can be empty if you want to disable it for every series). Note that when you change the lineation system, the option is automatically switched :

<sup>16</sup>Like `em` which is the width of a M.

- If you use lineation by pstart, the option is enabled.
- If you use lineation by section or by page, the option is disabled.

<code>\onlypstartinfootnote</code>	In combination with <code>\pstartinfootnote</code> , you can use <code>\onlypstartinfootnote[⟨s⟩]</code> if you want to print only the pstart number in the footnote, and not the line and subline number. Use <code>\onlypstartinfootnote[⟨s⟩][⟨false⟩]</code> to cancel it (⟨s⟩ can be empty if you want to disable it for every series).
<code>\beforenumberinfootnote</code>	With <code>\beforenumberinfootnote[⟨s⟩]{⟨l⟩}</code> , you can add some space before the line number in a footnote. If the line number is not printed, the space is not either. The default value is 0 pt.
<code>\afternumberinfootnote</code>	With <code>\afternumberinfootnote[⟨s⟩]{⟨l⟩}</code> you can add some space after the line number in a footnote. If the line number is not printed, the space is not either. The default value is 0.5 em.
<code>\nonbreakableafternumber</code>	By default, the space defined by <code>\afternumberinfootnote</code> is breakable. With <code>\afternumberinfootnote[⟨s⟩]</code> it becomes non breakable. Use <code>\afternumberinfootnote[⟨s⟩][⟨false⟩]</code> to cancel it (⟨s⟩ can be empty if you want to disable it for every series).
<code>\beforesymlinenum</code>	With <code>\beforesymlinenum[⟨s⟩]{⟨l⟩}</code> you can add some space before the line symbol in a footnote. The default value is value set by <code>\beforenumberinfootnote</code> .
<code>\aftersymlinenum</code>	With <code>\aftersymlinenum[⟨s⟩]{⟨l⟩}</code> you can add some space before the line symbol in a footnote. The default value is value set by <code>\afternumberinfootnote</code> .
<code>\inplaceofnumber</code>	If no number or symbolic line number is printed, you can add a space, with <code>\inplaceofnumber[⟨s⟩]{⟨l⟩}</code> . The default value is 1 em.
<code>\boxlinenum</code>	It could be useful to put the line number inside a fixed box: the content of the note will be printed after this box. You can use <code>\boxlinenum[⟨s⟩]{⟨l⟩}</code> to do that. To subsequently disable this feature, use <code>\boxlinenum</code> with length equal to 0 pt. One use of this feature is to print line number in a column, and the note in another column:  <pre> \Xhangindent{1em} \afternumberinfootnote{0em} \boxlinenum{1em} </pre>
<code>\boxsymlinenum</code>	<code>\boxsymlinenum[⟨s⟩]{⟨l⟩}</code> is the same as <code>\boxlinenum</code> but for the line number symbol.

### 4.3.2 Separator between the lemma and the note content

<code>\lemmaseparator</code>	By default, in a footnote, the separator between the lemma and thenote is a right bracket ( <code>\rbracket</code> ). You can use <code>\lemmaseparator[⟨s⟩]{⟨lemmaseparator⟩}</code> to change it. The optional argument can be used to specify in which series it is applied. Note that there is a non-breakable space between lemma and separator, but <b>breakable</b> space between separator and lemma.
<code>\beforelemmaseparator</code>	Using <code>\beforelemmaseparator[⟨s⟩]{⟨l⟩}</code> you can add some space between lemma and separator. If your lemma separator is empty, this space won't be printed. The default value is 0 em.

<code>\afterlemmaseparator</code>	Using <code>\afterlemmaseparator[⟨s⟩]{⟨l⟩}</code> you can add some space between separator and note. If your lemma separator is empty, this space won't be printed. The default value is 0.5 em.
<code>\nolemmaseparator</code>	You can suppress the lemma separator, using <code>\nolemmaseparator[⟨s⟩]</code> , which is simply a alias of <code>\lemmaseparator[⟨s⟩]{}</code> .
<code>\inplaceoflemmaseparator</code>	With <code>\inplaceoflemmaseparator[⟨s⟩]{⟨l⟩}</code> you can add a space if no lemma separator is printed. The default value is 1 em.

### 4.3.3 Font style

<code>Xnotenumfont</code>	<code>\Xnotenumfont[⟨s⟩]{⟨command⟩}</code> is used to change the font style for line numbers in critical footnotes ; <code>⟨command⟩</code> must be one (or more) switching command, like <code>\bfseries</code> .
<code>Xendnotenumfont</code>	<code>\Xendnotenumfont[⟨s⟩]{⟨command⟩}</code> is used to change the font style for line numbers in critical footnotes. <code>⟨command⟩</code> must be one (or more) switching command, like <code>\bfseries</code> .
<code>notenumfontX</code>	<code>\notenumfontX[⟨s⟩]{⟨command⟩}</code> is used to change the font style for note numbers in familiar footnotes. <code>⟨command⟩</code> must be one (or more) switching command, like <code>\bfseries</code> .
<code>\Xnotefontsize</code>	<code>\Xnotefontsize[⟨s⟩]{⟨command⟩}</code> is used to define the font size of critical footnotes of the series. The default value is <code>\footnotesize</code> . The <code>⟨command⟩</code> must not be a size in pt, but a standard LaTeX size, like <code>\small</code> .
<code>\notefontsizeX</code>	<code>\notefontsizeX[⟨s⟩]{⟨command⟩}</code> is used to define the font size of critical footnotes of the series. The default value is <code>\footnotesize</code> . The <code>⟨command⟩</code> must not be a size in pt, but a standard LaTeX size, like <code>\small</code> .
<code>\Xendnotefontsize</code>	<code>\Xendnotefontsize[⟨s⟩]{⟨l⟩}</code> is used to define the font size of end critical footnotes of the series. The default value is <code>\footnotesize</code> . The <code>⟨command⟩</code> must not be a size in pt, but a standard LaTeX size, like <code>\small</code> .

### 4.3.4 Styles of notes content

<code>\Xhangindent</code>	For critical notes NOT paragraphed you can define an indent with <code>\Xhangindent[⟨s⟩]{⟨l⟩}</code> , which will be applied in the second line of notes. It can help to make distinction between a new note and a break in a note. The default value is 0 pt.
<code>\hangindentX</code>	For familiar notes NOT paragraphed you can define an indent with <code>\Xhangindent[⟨s⟩]{⟨l⟩}</code> , which will be applied in the second line of notes. It can help to make a distinction between a new note and a break in a note.

### 4.3.5 Arbitrary code at the beginning of notes

The three next commands add an arbitrary code at the beginning of notes. As the name's space is local to the notes, you can use it to redefine some style inside the notes. For example, if you don't want the `pstart` number to be in bold, use :

```
\hookXnote{\renewcommand{\thepstart}{\arabic{pstart}.}}
```

<code>\bhookXnote</code>	<code>\bhookXnote[<i>&lt;series&gt;</i>]{<i>&lt;code&gt;</i>}</code> is to be used at the beginning of the critical footnotes.
<code>\bhooknoteX</code>	<code>\bhooknoteX[<i>&lt;series&gt;</i>]{<i>&lt;code&gt;</i>}</code> is to be used at the beginning of the familiar footnotes.
<code>\bhookXendnote</code>	<code>\bhookXendnote[<i>&lt;series&gt;</i>]{<i>&lt;code&gt;</i>}</code> is to be used at the beginning of the end-notes.

### 4.3.6 Options for notes in columns

For the following four macros, be careful that the columns are made from right to left.

<code>\hsizetwocol</code>	<code>\hsizetwocol[<i>&lt;s&gt;</i>]{<i>&lt;l&gt;</i>}</code> is used to change width of a column when critical notes are displaying in two columns. Default value is <code>.45 \hsizetwocol</code> .
<code>\hsizethreecol</code>	<code>\hsizethreecol[<i>&lt;s&gt;</i>]{<i>&lt;l&gt;</i>}</code> is used to change width of a column when critical notes are displaying in three columns. Default value is <code>.3 \hsizethreecol</code> .
<code>\hsizetwocolX</code>	<code>\hsizetwocolX[<i>&lt;s&gt;</i>]{<i>&lt;l&gt;</i>}</code> is used to change width of a column when familiar notes are displaying in two columns. Default value is <code>.45 \hsizetwocolX</code> .
<code>\hsizethreecolX</code>	<code>\hsizethreecolX[<i>&lt;s&gt;</i>]{<i>&lt;l&gt;</i>}</code> is used to change width of a column when familiar notes are displaying in three columns. Default value is <code>.3 \hsizethreecolX</code> .

### 4.3.7 Options for paragraphed footnotes

<code>\afternote</code>	You can add some space after a note by using <code>\afternote[<i>&lt;s&gt;</i>]{<i>&lt;l&gt;</i>}</code> . The default value is <code>1em plus .4em minus .4em</code> .
<code>\parafootsep</code>	For paragraphed footnotes (see below), you can choose the separator between each note by <code>\parafootsep[<i>&lt;s&gt;</i>]{<i>&lt;l&gt;</i>}</code> . A common separator is double pipe ( <code>\$  \$</code> ), which you can set by <code>\parafootsep\$  \$</code> .

### 4.3.8 Options for block of notes

<code>\txtbeforeXnotes</code>	You can add some text before critical notes with <code>\txtbeforeXnotes[<i>&lt;s&gt;</i>]{<i>&lt;text&gt;</i>}</code> .
<code>\beforeXnotes</code>	You can change the vertical space printed before the rule of the critical notes with <code>\beforeXnotes[<i>&lt;s&gt;</i>]{<i>&lt;l&gt;</i>}</code> . The default value is <code>1.2em plus .6em minus .6em</code> .
<code>\beforenotesX</code>	You can change the vertical space printed before the rule of the familiar notes with <code>\beforenotesX[<i>&lt;s&gt;</i>]{<i>&lt;l&gt;</i>}</code> . The default value is <code>1.2em plus .6em minus .6em</code> .
<code>\preXnotes</code>	You can set the space before the first series of critical notes printed on each page and set a different amount of space for subsequent the series on the page. You can do it with <code>\preXnotes{<i>&lt;l&gt;</i>}</code> . You can disable this feature by setting the length to 0 pt.
<code>\prenotesX</code>	You can want the space before the first printed (in a page) series of familiar notes not to be the same as before other series. You can do it with <code>\prenotesX{<i>&lt;l&gt;</i>}</code> . You can disable this feature by setting the length to 0 pt.
<code>\maxhXnotes</code>	By default, one series of critical notes can take 80% of the page size, before being broken to the next page. If you want to change the size use <code>\maxhXnotes[<i>&lt;s&gt;</i>]{<i>&lt;l&gt;</i>}</code> . Be careful : the length can't be flexible, and is relative to the the current font. For example, if you want that note takes, at most, 33 of the text height, do <code>\maxhnotes{33\textheight}</code> .

`\maxnotesX`      `\maxnotesX[⟨s⟩]{⟨l⟩}` is the same as previous, but for familiar footnotes.  
 Be careful with the two previous commands. Actually, for technical purposes, one paragraphed note is considered as one block. Consequently, it can't be broken between two pages, even if you used these commands. The debug is in the `todolist`.

## 4.4 Page layout

You should set up the page layout parameters, and in particular the `\baselineskip` of the footnotes (this is done for you if you use the standard `\notefontsetup`), before you call any of these macros because their action depends on these; too much or too little space will be allotted for the notes on the page if these macros use the wrong values.<sup>17</sup>

## 4.5 Fonts

One of the most important features of the appearance of the notes, and indeed of your whole document, will be the fonts used. We will first describe the commands that give you control over the use of fonts in the different structural elements of the document, especially within the notes, and then in subsequent sections specify how these commands are used.

For those who are setting up for a large job, here is a list of the complete set of `eledmac` macros relating to fonts that are intended for manipulation by the user: `\endashchar`, `\fullstop`, `\numlabfont`, and `\rbracket`.

`\numlabfont`      Line numbers for the main text are usually printed in a smaller font in the margin. The `\numlabfont` macro is provided as a standard name for that font: it is initially defined as

```
\newcommand{\numlabfont}{\normalfont\scriptsize}
```

You might wish to use a different font if, for example, you preferred to have these line numbers printed using old-style numerals.

`\endashchar`      A relatively trivial matter relates to punctuation. In your footnotes, there will sometimes be spans of line numbers like this: 12–34, or lines with sub-line numbers like this: 55.6. The en-dash and the full stop are taken from the same font as the numbers, and it all works nicely. But what if you wanted to use old-style numbers, like 12 and 34? These look nice in an edition, but when you use the fonts provided by PLAIN  $\text{\TeX}$  they are taken from a math font which does not have the en-dash or full stop in the same places as a text font. If you (or your macros) just typed `\oldstyle 12--34` or `\oldstyle 55.6` you would get ‘12>>34’ and ‘55>6’. So we define `\endashchar` and `\fullstop`, which produce an en-dash and a full stop respectively from the normal document font, whatever font you are using for the numbers. These two macros are used in the macros which format the line numbers in the margins and footnotes, instead of explicit punctuation. We also define an `\rbracket` macro for the right square bracket printed at the end of the lemma in

<sup>17</sup>There is one tiny proviso about using paragraphed notes: you shouldn't force any explicit line-breaks inside such notes: do not use `\par`, `\break`, or `\penalty=-10000`. If you must have a line-break for some obscure reason, just suggest the break very strongly: `\penalty=-9999` will do the trick. Page 102 explains why this restriction is necessary.

many styles of textual notes (including `eledmac`'s standard style). For polyglossia, when the lemma is RTL, the bracket automatically switches to a left bracket.

`\select@lemmafnt`

We will briefly discuss `\select@lemmafnt` here because it is important to know about it now, although it is not one of the macros you would expect to change in the course of a simple job. Hence it is 'protected' by having the `@`-sign in its name.

When you use the `\edtext` macro to mark a word in your text as a lemma, that word will normally be printed again in your apparatus. If the word in the text happens to be in a font such as italic or bold you would probably expect it to appear in the apparatus in the same font. This becomes an absolute necessity if the font is actually a different script, such as Arabic or Cyrillic. `\select@lemmafnt` does the work of decoding `eledmac`'s data about the fonts used to print the lemma in the main text and calling up those fonts for printing the lemma in the note.

`\select@lemmafnt` is a macro that takes one long argument—the cluster of line numbers passed to the note commands. This cluster ends with a code indicating what fonts were in use at the start of the lemma. `\select@lemmafnt` selects the appropriate font for the note using that font specifier.

`eledmac` uses `\select@lemmafnt` in a standard footnote format macro called `\normalfootfmt`. The footnote formats for each of the layers A to E are `\let` equal to `\normalfootfmt`. So all the layers of the footnotes are formatted in the same way.

## 4.6 Create a new series

If you need more than 5 series of critical footnotes you can create extra series, using `\newseries` command. For example to create G and H series `\newseriesG,H`.

## 5 Verse

In 1992 Wayne Sullivan<sup>18</sup> wrote the `EDSTANZA` macros [Sul92] for typesetting verse in a critical edition. More specifically they were for handling poetry stanzas which use indentation to indicate rhyme or metre.

With Wayne Sullivan's permission the majority of this section has been taken from [Sul92]. I have made a few changes to enable his macros to be used in the LaTeX `eledmac` package.

`\stanza`

`\&`

Use `\stanza` at the start of a stanza. Each line in a stanza is ended by an ampersand (`&`), and the stanza itself is ended by putting `\&` at the end of the last line.

`\stanzaindentbase`

Lines within a stanza may be indented. The indents are integer multiples of the length `\stanzaindentbase`, whose default value is 20pt.

`\setstanzaindent`

In order to use the stanza macros, one must set the indentation values. First the value of `\stanzaindentbase` should be set, unless the default value 20pt is desired. Every stanza line indentation is a multiple of this.

---

<sup>18</sup>Department of Mathematics, University College, Dublin 4, Ireland

To specify these multiples one invokes, for example  
`\setstanzaindents{3,1,2,1,2}`.

The numerical entries must be whole numbers, 0 or greater, separated by commas without embedded spaces. The first entry gives the hanging indentation to be used if the stanza line requires more than one print line. If it is known that each stanza line will fit on a single print line, then this first entry should be 0;  $\text{\TeX}$  does less work in this case, but no harm ensues if the hanging indentation is not 0 but is never used. Enumeration is by stanza lines, not by print lines. In the above example the lines are indented one unit, two units, one unit, two units, with 3 units of hanging indentation in case a stanza line is too long to fit on one print line.

Since version 0.13, if the indentation is repeated every  $n$  verses of the stanza, you can define only the  $n$  first indentations, and say they are repeated, defining the value of the `stanzaindentsrepetition` counter at  $n$ . For example:

```
\setstanzaindents{0,1,0}
\setcounter{stanzaindentsrepetition}{2}
```

is like

```
\setstanzaindents{0,1,0,1,0,1,0,1,0,1,0}
```

If you don't use the `stanzaindentsrepetition` counter, make sure you have at least one more numerical entry in `\setstanzavalues` than the number of lines in the stanza. The macros make no restriction on the number of lines in a stanza. Stanza indentation values (and penalty values) obey  $\text{\TeX}$ 's grouping conventions, so if one stanza among several has a different structure, its indentations (penalties) may be set within a group; the prior values will be restored when the group ends.

`\setstanzapenalties`

When the stanzas run over several pages, often it is desirable that page breaks should arise between certain lines in the stanza, so a facility for including penalties after stanza lines is provided. If you are satisfied with the page breaks, you need not set the penalty values.

The command

```
\setstanzapenalties{1,5000,10100,5000,0}
```

results in a penalty of 5000 being placed after the first and third lines of the stanza, and a penalty of  $-100$  after the second.

The first entry "1" is a control value. If it is zero, then no penalties are passed on to  $\text{\TeX}$ , which is the default. Values between 0 and 10000 are penalty values; values between 10001 and 20000 have 10000 subtracted and the result is given as a negative penalty. The mechanism used for indentations and penalties requires unsigned values less than 32768. No penalty is placed after the last line, so the final ,0 in then example above could be omitted. The control sequence `\endstanzaextra` can be defined to include a penalty. A penalty of 10000 will prevent a page break; such a penalty is included automatically where there is stanza hanging indentation. A penalty of  $-10000$  (corresponding to the entry value

20000 in this context) forces a page break. Values in between act as suggestions as to the desirability of a page break at a given line. There is a subtle interaction between penalties and *glue*, so it may take some adjustment of skips and penalties to achieve the best results.

<code>\ampersand</code>	If you need to print an & symbol in a stanza, use the <code>\ampersand</code> macro, not <code>\&amp;</code> which will end the stanza.
<code>\endstanzaextra</code>	The macro <code>\endstanzaextra</code> , if it is defined, is called at the end of a stanza. You could define this, for example, to add extra space between stanzas (by default there is no extra space between stanzas); if you are using the <code>memoir</code> class, it provides a length <code>\stanzaskip</code> which may come in handy.
<code>\startstanzahook</code>	Similarly, if <code>\startstanzahook</code> is defined, it is called by <code>\stanza</code> at the start. This can be defined to do something.
<code>\flagstanza</code>	Putting <code>\flagstanza[⟨len⟩]{⟨text⟩}</code> at the start of a line in a stanza (or elsewhere) will typeset <code>⟨text⟩</code> at a distance <code>⟨len⟩</code> before the line. The default <code>⟨len⟩</code> is <code>\stanzaindentbase</code> . For example, to put a verse number before the first line of a stanza you could proceed along the lines:

```

\newcounter{stanzanum}
\setcounter{stanzanum}{0}
\newcommand*{\startstanzahook}{\refstepcounter{stanzanum}}
\newcommand{\numberit}{\flagstanza{\thestanzanum}}
...
\stanza
\numberit First line...&
    rest of stanza&

\stanza
\numberit First line, second stanza...

```

## 5.1 Hanging symbol

It's possible to insert a symbol on each line of verse's hanging, as in French typography for '['. To insert in `eledmac`, redefine macro `\hangingsymbol` with this code:

```
\renewcommand{\hangingsymbol}{[,]}
```

## 6 Grouping

In a `minipage` environment LaTeX changes `\footnote` numbering from arabic to alphabetic and puts the footnotes at the end of the `minipage`.

`minipage` You can put numbered text with critical footnotes in a `minipage` and the footnotes are set at the end of the `minipage`.

You can also put familiar footnotes (see section 11) in a `minipage` but unlike with `\footnote` the numbering scheme is unaltered.



**ledgroup** Minipages, of course, aren't broken across pages. Footnotes in a **ledgroup** environment are typeset at the end of the environment, as with minipages, but the environment includes normal page breaks. The environment makes no change to the textwidth so it appears as normal text; it just might be that footnotes appear in the middle of a page, with text above and below.

**ledgroupsize** The **ledgroupsize** environment is similar to **ledgroup** except that you must specify a width for the environment, as with a minipage.  
`\begin{ledgroupsize}[\langle pos \rangle]{\langle width \rangle}`.

The required  $\langle width \rangle$  argument is the text width for the environment. The optional  $\langle pos \rangle$  argument is for positioning numbered text within the normal textwidth. It may be one of the characters:

l (left) numbered text is flush left with respect to the normal textwidth. This is the default.

c (center) numbered text is in the center of the textwidth.

r (right) numbered text is flush right with respect to the normal textwidth.

Note that normal text, footnotes, and so forth are all flush left.

`\begin{ledgroupsize}{\textwidth}` is effectively the same as `\begin{ledgroup}`

## 7 Crop marks

The **eledmac** package does not provide crop marks. These are available with either the memoir class [Wil02] or the **crop** package.

## 8 Endnotes

**\doendnotes** `\doendnotes{\langle letter \rangle}` closes the `.end` file that contains the text of the endnotes, if it's open, and prints one series of endnotes, as specified by a series-letter argument, e.g., `\doendnotes{A}`. **\endprint** is the macro that's called to print each note. It uses `\select@lemmafnt` to select fonts, just as the footnote macros do (see p. 91 above).

As endnotes may be printed at any point in the document they always start with the page number of where they were specified. The macro `\printnpnum{\langle num \rangle}` is used to print these numbers. Its default definition is:

`\newcommand*\printnpnum[1]{p.#1}`

**\noendnotes** If you aren't going to have any endnotes, you can say `\noendnotes` in your file, before the first `\beginnumbering`, to suppress the generation of an unneeded `.end` file.

## 9 Cross referencing

The package provides a simple cross-referencing facility that allows you to mark places in the text with labels, and generate page and line number references to

those places elsewhere using those labels.

`\edlabel` First you place a label in the text using the command `\edlabel{<lab>}`. *<lab>* can be almost anything you like, including letters, numbers, punctuation, or a combination—anything but spaces; you might say `\edlabel{toves-3}`, for example.<sup>19</sup>

`\edpageref` Elsewhere in the text, either before or after the `\edlabel`, you can refer to its location via `\edpageref{<lab>}`, or `\lineref{<lab>}`, or `\sublineref{<lab>}`.

`\lineref` These commands will produce, respectively, the page, line and sub-line on which the `\edlabel{<lab>}` command occurred.

`\sublineref`

An `\edlabel` command may appear in the main text, or in the first argument of `\edtext`, but not in the apparatus itself. But `\edpageref`, `\lineref` and `\sublineref` commands can also be used in the apparatus to refer to `\edlabel`'s in the text.

The `\edlabel` command works by writing macros to the LaTeX `.aux` file. You will need to process your document through LaTeX twice in order for the references to be resolved.

You will be warned if you say `\edlabel{foo}` and `foo` has been used as a label before. The `ref` commands will return references to the last place in the file marked with this label. You will also be warned if a reference is made to an undefined label. (This will also happen the first time you process a document after adding a new `\edlabel` command: the auxiliary file will not have been updated yet.)

If you want to refer to a word inside an `\edtext{...}{...}` command, the `\edlabel` should be defined inside the first argument, e.g.,

```
The \edtext{creature\edlabel{elephant} was quite
unafraid}{\Afootnote{Of the mouse, that is.}}
```

`\xpageref` However, there are situations in which you'll want `eledmac` to return a number without displaying any warning messages about undefined labels or the like: if you want to use the reference in a context where LaTeX is looking for a number, such a warning will lead to a complaint that the number is missing. This is the case for references used within the argument to `\linenum`, for example. For this situation, three variants of the reference commands, with the `x` prefix, are supplied: `\xpageref`, `\xlineref`, and `\xsublineref`. They have these limitations: they will not tell you if the label is undefined, and they must be preceded in the file by at least one of the four other cross-reference commands—e.g., a `\edlabel{foo}` command, even if you never refer to that label—since those commands can all do the necessary processing of the `.aux` file, and the `\x...` ones cannot.

`\xxref` The macros `\xxref` and `\edmakelabel` let you manipulate numbers and labels in ways which you may find helpful in tricky situations.

The `\xxref{<lab1>}{<lab2>}` command generates a reference to a sequence of lines, for use in the second argument of `\edtext`. It takes two arguments, both of which are labels: e.g., `\xxref{mouse}{elephant}`. It calls `\linenum` (q.v.,

<sup>19</sup>More precisely, you should stick to characters in the TeX categories of 'letter' and 'other'.

p.15 above) and sets the beginning page, line, and sub-line numbers to those of the place where `\edlabel{mouse}` was placed, and the ending numbers to those where `\edlabel{elephant}` occurs.

`\edmakelabel` Sometimes the `\edlabel` command cannot be used to specify exactly the page and line desired—for example, if you want to refer to a page and line number in another volume of your edition. In such cases, you can use the `\edmakelabel{<lab>}{<numbers>}` macro so that you can ‘roll your own’ label. For example, if you say `\edmakelabel{elephant}{10|25|0}` you will create a new label, and a later call to `\edpageref{elephant}` would print ‘10’ and `\lineref{elephant}` would print ‘25’. The sub-line number here is zero. It is usually best to collect your `\edmakelabel` statements near the top of your document, so that you can see them at a glance.

`\label`      The normal `\label`, `\ref` and `\pageref` macros may be used within numbered text, and operate in the familiar fashion.  
`\ref`  
`\pageref`

## 10 Side notes

The `\marginpar` command does not work in numbered text. Instead the package provides for non-floating sidenotes in either margin.

`\ledleftnote`      `\ledleftnote{<text>}` will put `<text>` into the left margin level with where the command was issued. Similarly, `\ledrightnote{<text>}` puts `<text>` in the right margin. `\ledsidenote{<text>}` will put `<text>` into the margin specified by the current setting of `\sidenotemargin{<location>}`. The permissible value for `<location>` is one out of the list `left`, `right`, `inner`, or `outer`, for example `\sidenotemargin{outer}`. The package’s default setting is `\sidenotemargin{right}`

to typeset `\ledsidenotes` in the right hand margin. This is the opposite to the default margin for line numbers. The style for a `\ledsidenote` follows that for a `\ledleftnote` or a `\ledrightnote` depending on the margin it is put in.

If two, say, `\ledleftnote`, commands are called in the same line the second `<text>` will obliterate the first. There is no problem though with having both a left and a right sidenote on the same line.

`\ledlsnotewidth`      The left sidenote text is put into a box of width `\ledlsnotewidth` and the right text into a box of width `\ledrsnotewidth`. These are initially set to the value of `\marginparwidth`.  
`\ledrsnotewidth`

`\rightnoteupfalse`      By default, left and right sidenotes have their *end* at the line they are called. If you want they to have their *start* at the line they are called, use `\leftnoteupfalse` (for left note) and/or `\rightnoteupfalse` (for right note).  
`\leftnoteupfalse`

`\ledlsnotesep`      The texts are put a distance `\ledlsnotesep` (or `\ledrsnotesep`) into the left (or right) margin. These lengths are initially set to the value of `\linenumsep`.  
`\ledrsnotesep`

`\ledlsnotefontsetup`      These macros specify how the sidenote texts are to be typeset. The initial definitions are:  
`\ledrsnotefontsetup`

```
\newcommand*{\ledlsnotefontsetup}{\raggedleft\footnotesize}% left
\newcommand*{\ledrsnotefontsetup}{\raggedright\footnotesize}% right
```

These can of course be changed to suit.

`\sidenotesep` If you have two or more sidenotes for the same line, they are separated by a comma. But if you want to change this separator, you can redefine the macro `\sidenotesep`.

## 11 Familiar footnotes

The `footmisc` package [Fai03] by Robin Fairbairns has an option whereby sequential footnote marks in the text can be separated by commas<sup>3,4</sup> like so. As a convenience `eledmac` provides this automatically.

`\multfootsep` `\multfootsep` is used as the separator between footnote markers. Its default definition is:

```
\providecommand*\multfootsep{\textsuperscript{\normalfont,}}
```

and can be changed if necessary.

`\footnoteA` As well as the standard LaTeX footnotes generated via `\footnote`, the package also provides three series of additional footnotes called `\footnoteA` through `\footnoteE`. These have the familiar marker in the text, and the marked text at the foot of the page can be formatted using any of the styles described for the critical footnotes. Note that the ‘regular’ footnotes have the series letter at the end of the macro name whereas the critical footnotes have the series letter at the start of the name.

`\footnormalX` Each of the `\foot...X` macros takes one argument which is the series letter (e.g., B). `\footnormalX` is the typical footnote format. With `\footparagraphX` the series is typeset a one paragraph, with `\foottwocolX` the notes are in two columns, and are in three columns with `\foothreecolX`.

`\thefootnoteA` As well as using the `\foot...X` macros to specify the general footnote arrangement for a series, each series uses a set of macros for styling the marks. The mark numbering scheme is defined by the `\thefootnoteA` macro; the default is:

```
\renewcommand*\thefootnoteA{\arabic{footnoteA}}
```

The appearance of the mark in the text is controlled by `\bodyfootmarkA` which is defined as:

```
\newcommand*\bodyfootmarkA{%
  \hbox{\textsuperscript{\normalfont\thefootnoteA}}}
```

The command `\footfootmarkA` controls the appearance of the mark at the start of the footnote text. It is defined as:

```
\newcommand*\footfootmarkA{\textsuperscript{\thefootnoteA}}
```

There are similar command triples for the other series.

Additional footnote series can be easily defined: you just have to use `\newseries`, defined above (see 4.6 p.22).

## 12 Indexing

`\edindex` LaTeX provides the `\index{<item>}` command for specifying that `<item>` and the current page number should be added to the raw index (`idx`) file. The

`\edindex{<item>}` macro can be used in numbered text to specify that *<item>* and the current page & linenumber should be added to the raw index file.

If the `memoir` class is used then the macro takes an optional argument, which is the name of a raw index file. For example `\edindex[line]{item}` will use `line.idx` as the raw file instead of `\jobname.idx`.

`\pagelinesep` The page & linenumber combination is written as `page\pagelinesep line`, where the default definition is `\newcommand{\pagelinesep}{-}` so that an item on page 3, line 5 will be noted as being at 3-5. You can renew `\pagelinesep` to get a different separator (but it just so happens that `-` is the default separator used by the MAKEINDEX program).

`\edindexlab` The `\edindex` process uses a `\label/\ref` mechanism to get the correct line number. It automatically generates labels of the form `\label{\edindexlab N}`, where N is a number, and the default definition of `\edindexlab` is:

`\newcommand*{\edindexlab}{\&\&}`

in the hopes that this will not be used by any other labels (`\edindex`'s labels are like `\label{\&\&27}`). You can change `\edindexlab` to something else if you need to.

## 13 Tabular material

LaTeX's normal `tabular` and `array` environments cannot be used where line numbering is being done; more precisely, they can be used but with odd results, so don't use them. However, `eledmac` provides some simple tabulation environments that can be line numbered. The environments can also be used in normal unnumbered text.

`edarrayl` There are six environments; the `edarray*` environments are for math and  
`edarrayc` `edtabular*` for text entries. The final `l`, `c`, or `r` in the environment names indicate  
`edarrayr` that the entries will be flushleft (`l`), centered (`c`) or flushright (`r`). There is  
`edtabularl` no means of specifying different formats for each column, nor for specifying a  
`edtabularc` fixed width for a column. The environments are centered with respect to the  
`edtabularr` surrounding text.

`\begin{edtabularc}`

1 & 2 & 3 \\\

a & bb & ccc \\\

AAA & BB & C

`\end{edtabularc}`

1	2	3
a	bb	ccc
AAA	BB	C

Entries in the environments are the same as for the normal `array` and `tabular` environments but there must be no ending `\\` at the end of the last row. *There must be the same number of column designators (the &'s) in each row.* There is no equivalent to any line drawing commands (such as `\hline`). However, unlike the normal environments, the `ed...` environments can cross page breaks.

Macros like `\edtext` can be used as part of an entry.

For example:

`\beginnumbering`  
`\pstart`

```

\begin{edtabularl}
\textbf{\Large I} & \& wish I was a little bug\edindex{bug} &
\textbf{\Large I} & \& eat my peas with honey\edindex{honey} \\\
& \& With whiskers \edtext{round}{\Afootnote{around}} my tummy &
& \& I've done it all my life. \\\
& \& I'd climb into a honey\edindex{honey} pot &
& \& It makes the peas taste funny \\\
& \& And get my tummy gummy.\edindex{gummy} &
& \& But it keeps them on the knife.
\end{edtabularr}
\pend
\endnumbering

```

produces the following parallel pair of verses.

1	<b>I</b> wish I was a little bug	<b>I</b> eat my peas with honey
2	With whiskers round my tummy	I've done it all my life.
3	I'd climb into a honey pot	It makes the peas taste funny
4	And get my tummy gummy.	But it keeps them on the knife.

`\edtabcolsep` The distance between the columns is controlled by the length `\edtabcolsep`.  
`\spreadmath` `\spreadmath{<math>}</math>` typesets `{<math>}</math>` but the `{<math>}</math>` has no effect on  
`\spreadtext` the calculation of column widths. `\spreadtext{<text>}` is the analagous command  
for use in `edtabular` environments.

```

\begin{edarrayl}
1 & \& 2 & \& 3 & \& 4 & \\\
& \& \spreadmath{F+G+C} & \& \& \\\
a & \& bb & \& ccc & \& dddd
\end{edarrayl}

```

1	2	3	4
$F + G + C$			
<i>a</i>	<i>bb</i>	<i>ccc</i>	<i>dddd</i>

`\edrowfill` The macro `\edrowfill{<start>}{<end>}{<fill>}` fills columns number `<start>` to `<end>` inclusive with `<fill>`. The `<fill>` argument can be any horizontal ‘fill’. For example `\hrulefill` or `\upbracefill`.

Note that every row must have the same number of columns, even if some would not appear to be necessary.

The `\edrowfill` macro can be used in both `tabular` and `array` environments. The typeset appearance of the following code is shown below.

```

\begin{edtabularr}
1 & & \& 2 & \& 3 & \& 4 & \& 5 & \\\
Q & & \& & \& fd & \& h & \& qwertziohg & \\\
v & & \& wptz & \& x & \& y & \& vb & \\\
g & & \& nnn & \& \edrowfill{3}{5}{\upbracefill} & \& \& \\\
\edrowfill{1}{3}{\downbracefill} & \& & \& pq & \& dgh & \\\
k & & \& & \& l & \& co & \& ghweropjklmbvcxys & \\\
1 & & \& 2 & \& 3 & \& \edrowfill{4}{5}{\hrulefill} & \&
\end{edtabularr}

```

1	2	3	4	5
Q		fd	h	qwertziohg
v	wptz	x	y	vb
g	nnn			
k		1	pq	dgh
1	2	3	co	ghweropjklmnbvcxys

You can also define your own ‘fill’. For example:

```
\newcommand*{\upbracketfill}{%
  \vrule height 4pt depth 0pt\hrulefill\vrule height 4pt depth 0pt}
```

is a fill like `\upbracefill` except it has the appearance of a (horizontal) bracket instead of a brace. It can be used like this:

```
\begin{edarrayc}
1 & 2 & & & 3 & 4 & \\
a & \edrowfill{2}{3}{\upbracketfill} & & & d & \\
A & B & & & C & D & \\
\end{edarrayc}
```

1	2	3	4
a	└───		d
A	B	C	D

`\edatleft`      `\edatleft[ $\langle math \rangle\{\langle symbol \rangle\}\langle halfheight \rangle]$`  typesets the math  $\langle symbol \rangle$  as `\left<symbol>` with the optional  $\langle math \rangle$  centered before it. The  $\langle symbol \rangle$  is twice  $\langle halfheight \rangle$  tall. The `\edatright` macro is similar and it typesets `\right<symbol>` with  $\langle math \rangle$  centered after it.

```
\begin{edarrayc}
& 1 & 2 & 3 & & \\
& 4 & 5 & 6 & & \\
\edatleft[left =]{\{ }\{1.5\baselineskip}
& 7 & 8 & 9 & & \\
\edatright[= right]{\} }\{1.5\baselineskip}
\end{edarrayc}
```

$$left = \left( \begin{array}{ccc} 1 & 2 & 3 \\ 4 & 5 & 6 \\ 7 & 8 & 9 \end{array} \right) = right$$

`\edbeforetab`      `\edbeforetab{\langle text \rangle\{\langle entry \rangle\}}`, where  $\langle entry \rangle$  is an entry in the leftmost column, typesets  $\langle text \rangle$  left justified before the  $\langle entry \rangle$ . Similarly `\edaftertab{\langle entry \rangle\{\langle text \rangle\}}`,

where  $\langle entry \rangle$  is an entry in the rightmost column, typesets  $\langle text \rangle$  right justified after the  $\langle entry \rangle$ .

For example:

```
\begin{edarrayl}
      A & 1 & 2 & 3 \\
\edbeforetab{Before}{B} & 1 & 3 & 6 \\
      C & 1 & 4 & \edaftertab{8}{After} \\
      D & 1 & 5 & 0
\end{edarrayl}
```

	$A$ 1 2 3 $B$ 1 3 6 $C$ 1 4 8 $D$ 1 5 0	After
--	--	-------

`\edvertline`      The macro `\edvertline{ $\langle height \rangle$ }` draws a vertical line  $\langle height \rangle$  high (contrast this with `\edatright` where the size argument is half the desired height).

`\edvertdots`

```
\begin{edarrayr}
a & b & C & d & \\
v & w & x & y & \\
m & n & o & p & \\
k & & L & cvb & \edvertline{4pc}
\end{edarrayr}
```

$a$	$b$	$C$	$d$	
$v$	$w$	$x$	$y$	
$m$	$n$	$o$	$p$	
$k$		$L$	$cvb$	

The `\edvertdots` macro is similar to `\edvertline` except that it produces a vertical dotted instead of a solid line.

## 14 Sectioning commands

The standard sectioning command (`\chapter`, `\section` etc.) can be used inside a numbered text. But the line which contains it won't be numbered, and you can't add critical notes inside.

However, `eledmac` provides the following commands :

- `\ledchapter[ $\langle text \rangle$ ]{ $\langle critical text \rangle$ }`
- `\ledchapter*`
- `\ledsection[ $\langle text \rangle$ ]{ $\langle critical text \rangle$ }`



- `\ledsection*`
- `\ledsubsection[⟨text⟩]{⟨critical text⟩}`
- `\ledsubsection*`
- `\ledsubsubsection[⟨text⟩]{⟨critical text⟩}`
- `\ledsubsubsection*`

Which are the equivalent of the standard LaTeX commands, but be careful. Note the following points :

1. All these commands close a `\pstart`, and open a new one. The content of the command itself is between `\pstart` and `\pend`.
2. Don't try to make `\let\chapter\ledchapter`, or other things like it: the `\ledsection` commands call the standard commands.
3. For the non-starred sections, use the optional argument `⟨text⟩` to provide the text to the table of contents.
4. The `\ledchapter` doesn't open a new page. You must use `\beforeledchapter` before. This also closes a `\pstart` and opens a new.

`\ledsectnotoc` You can create a table of contents that indexes only the titles that appear on the left side of the edition: for instance, titles from the original language, not the translation. You could use `\ledsectnotoc` at the beginning of the side environment :

```
\begin{Rightside}
\ledsectnotoc
...
\end{Rightside}
```

## 15 Quotation environments

The `quotation` and `quote` environment can be used so that same definition/note appears both inside and outside a numbered section. The typographical consequences will resemble the outside numbered sections, based on the styles of the *book* class. However, if you use a package that redefines these environments, these redefinitions won't be available inside the numbering section. You must open the quotation environments inside a `\start-\pend` block, not outside.

In some case, you don't want these environments be redefined in numbered section. You can load the package with the option `noquotation` to prevent this redefinition.

## 16 Miscellaneous

<code>\extensionchars</code>	When the package assembles the name of the auxiliary file for a section, it prefixes <code>\extensionchars</code> to the section number. This is initially defined to be empty, but you can add some characters to help distinguish these files if you like; what you use is likely to be system-dependent. If, for example, you said <code>\renewcommand{\extensionchars}{!}</code> , then you would get temporary files called <code>jobname.!1</code> , <code>jobname.!2</code> , etc.
<code>\ifledfinal</code>	The package can take options. The option ‘final’, which is the default is for final typesetting; this sets <code>\ifledfinal</code> to TRUE. The other option, ‘draft’, may be useful during earlier stages and sets <code>\ifledfinal</code> to FALSE.
<code>\showlemma</code>	<p>The lemma within the text is printed via <code>\showlemma{lemma}</code>. Normally, or with the ‘final’ option, the definition of <code>\showlemma</code> is:</p> <pre>\newcommand*{\showlemma}[1]{#1}</pre> <p>so it just produces its argument. With the ‘draft’ option it is defined as</p> <pre>\newcommand*{\showlemma}[1]{\textit{#1}}</pre> <p>so that its argument is typeset in an italic font, which may make it easier to check that all lemmas have been treated.</p> <p>If you would prefer some other style, you could put something like this in the preamble:</p> <pre>\ifledfinal\else \renewcommand{\showlemma}[1]{\textbf{#1}}% or simply ... [1]{#1} \fi</pre>

### 16.1 Known and suspected limitations

In general, `eledmac`’s system for adding marginal line numbers breaks anything that makes direct use of the LaTeX insert system, which includes `marginpars`, `footnotes` and `floats`.

However, you can use both `\footnote` and the familiar footnote series notes in numbered text. A `\marginpar` in numbered text will throw away its contents and send a warning message to the terminal and log file, but will do no harm.

`\parshape` cannot be used within numbered text, except in a very restricted way.

<code>\ballast</code>	<p>LaTeX is a three-pass system, but even after a document has been processed three times, there are some tricky situations in which the page breaks decided by <code>TeX</code> never settle down. At each successive run, <code>eledmac</code> may oscillate between two different sets of page decisions. To stop this happening, should it arise, Wayne Sullivan suggested the inclusion of the quantity <code>\ballast</code>. The amount of <code>\ballast</code> will be subtracted from the penalties which apply to the page breaks calculated on the <i>previous</i> run through <code>TeX</code>, thus reinforcing these breaks. So if you find your page breaks oscillating, say</p> <pre>\setcounter{ballast}{100}</pre> <p>or some such figure, and with any luck the page breaks will settle down. Luckily, this problem doesn’t crop up at all often.</p>
-----------------------	---

The restriction on explicit line-breaking in paragraphed footnotes, mentioned in a footnote 17, p. 21, and described in more detail on p. 102, really is a nuisance if that's something you need to do. There are some possible solutions, described by Michael Downes, but this area remains unsatisfactory.

LaTeX has a reputation for putting things in the wrong margin after a page break. The `eledmac` package does nothing to improve the situation — in fact it just makes it more obvious if numbered text crosses a page (or column) boundary and the numbers are meant to flip from side to side. Try and keep the numbers in the same margin all the time. Another aspect of TeX's page breaking mechanism is that when numbering lines by the page, the first few numbers after a page break may continue as though the lines were still on the previous page.

`\pageparbreak`

If you can't resist flipping the numbers or numbering by the page, then you might find that judicious use of `\pageparbreak` may help if numbering goes awry across a page (or column) break. It tries to force TeX into partitioning the current paragraph into two invisibly joined paragraphs with a page break between them. Insert the command between the last word on one page and the first word on the next page. If later you change something earlier in the document the natural page break may be in a different place, and you will have to adjust the location of `\pageparbreak` accordingly.

`\footfudgefiddle`

For paragraphed footnotes TeX has to estimate the amount of space required. If it underestimates this then the notes may get too long and run off the bottom of the text block. `\footfudgefiddle` can be increased from its default 64 (say to 68) to increase the estimate. You have to use `\renewcommand` for this, like:

```
\renewcommand{\footfudgefiddle}{68}
```

Help, suggestions and corrections will be gratefully received.

## 16.2 Use with other packages

Because of `eledmac`'s complexity it may not play well with other packages. In particular `eledmac` is sensitive to commands in the arguments to the `\edtext` and `\*footnote` macros (this is discussed in more detail in section 21, and in particular the discussion about `\no@expands` and `\morenoexpands`). You will have to see what works or doesn't work in your particular case.

It is possible that `eledmac` and the `hyperref` package may work together. I have not tried this combination but past experience with `hyperref` suggests that cooperation is unlikely; `hyperref` changes many LaTeX internals and `eledmac` does things that are not normally seen in LaTeX.

`\morenoexpands`

You can define the macro `\morenoexpands` to modify macros that you call within `\edtext`. Because of the way `eledmac` numbers the lines the arguments to `\edtext` can be processed more than once and in some cases a macro should only be processed once. One example is the `\colorbox` macro from the `color` package, which you might use like this:

```
... \edtext{\colorbox{mycolor}{lemma}}{\Afootnote{...\colorbox{...}}}
```

If you actually try this<sup>20</sup> you will find LaTeX whinging ‘Missing { inserted’, and then things start to fall apart. The trick in this case is to specify either:

```
\newcommand{\morenoexpands}{\let\colorbox=0}
```

or

```
\makeatletter
\newcommand{\morenoexpands}{\let\colorbox\@secondoftwo}
\makeatother
```

(\@secondoftwo is an internal LaTeX macro that takes two arguments and throws away the first one.) The first incantation lets color show in both the main text and footnotes whereas the second one shows color in the main text but kills it in the lemma and footnotes. On the other hand if you use \textcolor instead, like

```
... \edtext{\textcolor{mycolor}{lemma}}{\Afootnote{... \textcolor{...}}}
```

there is no need to fiddle with \morenoexpands as the color will naturally be displayed in both the text and footnotes. To kill the color in the lemma and footnotes, though, you can do:

```
\makeatletter
\newcommand{\morenoexpands}{\let\textcolor\@secondoftwo}
\makeatother
```

It took me a little while to discover all this. If you run into this sort of problem you may have to spend some time experimenting before hitting on a solution.

### 16.3 Parallel typesetting

Peter Wilson have developed the Ledpar package as an adjunct to **eledmac** specifically for parallel typesetting of critical texts. This also cooperates with the **babel** package for typesetting in multiple languages. The package is called *eledpar* since september 2012.

He also developed the **ledarab** package for handling parallel arabic text in critical editions. However, this package is not maintained by Maïeul Rouquette. You should use the possibility of modern TeX processor, like Xe(La)TeX

### 16.4 Notes for EDMAC users

If you have never used EDMAC, ignore this section. If you have used EDMAC and are starting on a completely new document, ignore this section. Only read this section if you are converting an original EDMAC document to use eledmac.

---

<sup>20</sup>Reported by Dirk-Jan Dekker in the CTT thread ‘Incompatibility of “color” package’ on 2003/08/28.

The package still provides the original `\text` command, but it is (a) deprecated, and (b) its name has been changed<sup>21</sup> to `\critext`; use the `\edtext` macro instead. However, if you do use `\critext` (the new name for `\text`), the following is a reminder.

`\critext` Within numbered paragraphs, footnotes and endnotes are generated by forms of the `\critext` macro:

```
\critext{⟨lemma⟩}⟨commands⟩/
```

The `⟨lemma⟩` argument is the lemma in the main text: `\critext` both prints this as part of the text, and makes it available to the `⟨commands⟩` you specify to generate notes. The `/` at the end terminates the command; it is part of the macro's definition so that spaces after the macro will be treated as significant.

For example:

<pre>I saw my friend \critext{Smith} \Afootnote{Jones C, D.}/ on Tuesday.</pre>	<pre>1 I saw my friend 2 Smith on Tuesday. 2 Smith] Jones C, D.</pre>
---	---

The lemma `Smith` is printed as part of this sentence in the text, and is also made available to the footnote that specifies a variant, `Jones C, D`. The footnote macro is supplied with the line number at which the lemma appears in the main text.

The `⟨lemma⟩` may contain further `\critext` commands. Nesting makes it possible to print an explanatory note on a long passage together with notes on variants for individual words within the passage. For example:

<pre>\critext{I saw my friend \critext{Smith}{\Afootnote{Jones C, D.}/ on Tuesday.} \Bfootnote{The date was July 16, 1954.} /</pre>	<pre>1 I saw my friend 2 Smith on Tuesday. 2 Smith] Jones C, D. 1–2 I saw my friend Smith on Tuesday.] The date was July 16, 1954.</pre>
---	--

However, `\critext` cannot handle overlapping but unnested notes—for example, one note covering lines 10–15, and another covering 12–18; a `\critext` that starts in the `⟨lemma⟩` argument of another `\critext` must end there, too. (The `\lemma` and `\linenum` commands may be used to generate overlapping notes if necessary.)

The second argument of the `\critext` macro, `⟨commands⟩`, is the same as the second argument to the `\edtext` macro.

It is possible to define aliases for `\critext`, which can be easier to type. You can make a single character substitute for `\critext` by saying this:

```
\catcode'\<=\active
\let<=\critext
```

---

<sup>21</sup>A name like `\text` is likely to be defined by other LaTeX packages (it certainly is by the AMS packages) and it seems sensible to try and avoid clashes with other definitions.

Then you might say `<{Smith}\variant{Jones}/`. This of course destroys the ability to use `<` in any new macro definitions, so long as it remains in effect; hence it should be used with care.

Changing the character at the end of the command requires more work:

```
\catcode'\<=\active
\def\xtext#1#2>{\critext{#1}{#2}/}
\let<=\xtext
```

This allows you to say `<{Smith}\Afootnote{Jones}>`.

Aliases for `\critext` of the first kind shown here also can't be nested—that is, you can't use the alias in the text that forms the first argument to `\critext`. (See section 21 to find out why.) Aliases of the second kind may be nested without any problem.

If you really have to use `\critext` in any of the tabular or array environments, then `\edtext` must not be used in the same environment. If you use `\critext` in one of these environments then you have to issue the declaration `\usingcritext` beforehand. The declaration `\usingedtext` must be issued to revert to the default assumption that `\edtext` will be used.

## 17 Implementation overview

We present the `eledmac` code in roughly the order in which it's used during a run of `TEX`. The order is *exactly* that in which it's read when you load The `eledmac` package, because the same file is used to generate this manual and to generate the LaTeX package file. Most of what follows consists of macro definitions, but there are some commands that are executed immediately—especially at the start of the code. The documentation generally describes the code from the point of view of what happens when the macros are executed, though. As each macro is introduced, its name is printed in the margin.

We begin with the commands you use to start and stop line numbering in a section of text (Section 18). Next comes the machinery for writing and reading the auxiliary file for each section that helps us count lines, and for creating list macros encoding the information from that file (Section 20); this auxiliary file will be read at the start of each section, to create those list macros, and a new version of the file will be started to collect information from the body of the section.

Next are commands for marking sections of the text for footnotes (Section 21), followed by the macros that take each paragraph apart, attach the line numbers and insertions, and send the result to the vertical list (Section 22). The footnote commands (Section 23) and output routine (Section 26) finish the main part of the processing; cross-referencing (Section 27) and endnotes (Section 28) complete the story.

In what follows, macros with an `@` in their name are more internal to the workings of `eledmac` than those made up just of ordinary letters, just as in PLAIN `TEX` (see *The TeXbook*, p.344). You are meant to be able to make free with ordinary macros, but the `@` ones should be treated with more respect, and changed only if you are pretty sure of what you are doing.

## 18 Preliminaries

We try and use `l@d` in macro names to help avoid name clashes, but this is not a hard and fast rule. For example, if an original `EDMAC` macro includes `edmac` We will simply change that to `eledmac`.

Announce the name and version of the package, which is targetted for LaTeX2e.

```
1 (*code)
2 \NeedsTeXFormat{LaTeX2e}
3 \ProvidesPackage{eledmac}[2013/06/07 v1.4.7 LaTeX port of EDMAC]
```

In general there is the following modifications to the original `EDMAC` code:

- Replace as many `\def`'s by `\newcommand`'s as possible to avoid overwriting LaTeX macros.
- Replace user-level TeX counts by LaTeX counters.
- Use the LaTeX font handling mechanisms.

- Use LaTeX messaging and file facilities.

`\ifledfinal` Use this to remember which option is used, set and execute the options with final as the default.

```

4 \newif\ifledfinal
5 \newif\ifparapparatus@
6 \newif\ifnoquotation@
7 \parapparatus@false
8 \DeclareOption{noquotation}{\noquotation@true}
9 \DeclareOption{final}{\ledfinaltrue}
10 \DeclareOption{draft}{\ledfinalfalse}
11 \DeclareOption{parapparatus}{\parapparatus@true}
12 \ExecuteOptions{final}

```

Use the starred form of `\ProcessOptions` which executes options in the order listed in the source file: class options, then listed package options, so a package option can override a class option with the same name. This was suggested by Dan Luecking in the `ctt` thread *Class/package option processing*, on 27 February 2004.

```

13 \ProcessOptions*\relax
14

```

Loading package *xargs* to declare commands with optional arguments. *Etoolbox* is also used to make code clearer - for example, in dynamic command names (which can replace `\csname` etc.). Use *suffix* to declare commands with starred versions/a starred version, and *iflutex* to test if LuaLaTeX is running.

```

15 \RequirePackage{xargs}
16 \RequirePackage{etoolbox}
17 \reserveinserts{32}
18 \RequirePackage{suffix}
19 \RequirePackage{ifluatex}

```

`\if@RTL` The `\if@RTL` is defined by the *bidi* package, which is sometimes loaded by *polyglossia*. But we define it if the *bidi* package is not loaded.

```

20 \ifcsdef{if@RTL}{\newif\if@RTL}

```

`\showlemma` `\showlemma{<lemma>}` typesets the lemma text in the body. It depends on the option.

```

21 \ifledfinal
22   \newcommand*{\showlemma}[1]{#1}
23 \else
24   \newcommand*{\showlemma}[1]{\underline{#1}}
25 \fi
26

```

`\linenumberlist` The code for the `\linenumberlist` mechanism was given to Peter Wilson by Wayne Sullivan on 2004/02/11.

Initialize it as `\empty`

```

27 \let\linenumberlist=\empty
28

```



```

\@l@dtmpcnta In imitation of LATEX, we create a couple of scratch counters.
\@l@dtmpcntb LaTeX already defines \@tempcnta and \@tempcntb but Peter Wilson have
found in the past that it can be dangerous to use these (for example one of the
AMS packages did something nasty to the ccaption package's use of one of these).
29 \newcount\@l@dtmpcnta \newcount\@l@dtmpcntb

```

```

\ifl@dmemoir Define a flag for if the memoir class has been used.
30 \newif\ifl@dmemoir
31 \@ifclassloaded{memoir}{\l@dmemoirtrue}{\l@dmemoirfalse}
32

```

## 18.1 Messages

All the messages are grouped here as macros. This saves TeX's memory when the same message is repeated and also lets them be edited easily.

```

\eledmac@warning Write a warning message.
33 \newcommand{\eledmac@warning}[1]{\PackageWarning{eledmac}{#1}}

\eledmac@error Write an error message.
34 \newcommand{\eledmac@error}[2]{\PackageError{eledmac}{#1}{#2}}

```

```

\led@err@NumberingStarted
\led@err@NumberingNotStarted 35 \newcommand*\led@err@NumberingStarted{%
\led@err@NumberingShouldHaveStarted 36 \eledmac@error{Numbering has already been started}{\@ehc}}
37 \newcommand*\led@err@NumberingNotStarted{%
38 \eledmac@error{Numbering was not started}{\@ehc}}
39 \newcommand*\led@err@NumberingShouldHaveStarted{%
40 \eledmac@error{Numbering should already have been started}{\@ehc}}

```

```

\led@mess@NotesChanged
41 \newcommand*\led@mess@NotesChanged{%
42 \typeout{eledmac reminder: }%
43 \typeout{ The number of the footnotes in this section
44 has changed since the last run.}%
45 \typeout{ You will need to run LaTeX two more times
46 before the footnote placement}%
47 \typeout{ and line numbering in this section are
48 correct.}}

```

```

\led@mess@SectionContinued
49 \newcommand*\led@mess@SectionContinued[1]{%
50 \message{Section #1 (continuing the previous section)}}

```

```

\led@err@LineationInNumbered
51 \newcommand*\led@err@LineationInNumbered{%
52 \eledmac@error{You can't use \string\lineation\space within
53 a numbered section}{\@ehc}}

```

```

\led@warn@BadLineation
\led@warn@BadLinenummargin 54 \newcommand*{\led@warn@BadLineation}{%
\led@warn@BadLockdisp 55 \eledmac@warning{Bad \string\lineation\space argument}}
\led@warn@BadSubblockdisp 56 \newcommand*{\led@warn@BadLinenummargin}{%
57 \eledmac@warning{Bad \string\linenummargin\space argument}}
58 \newcommand*{\led@warn@BadLockdisp}{%
59 \eledmac@warning{Bad \string\lockdisp\space argument}}
60 \newcommand*{\led@warn@BadSubblockdisp}{%
61 \eledmac@warning{Bad \string\subblockdisp\space argument}}

\led@warn@NoLineFile
62 \newcommand*{\led@warn@NoLineFile}[1]{%
63 \eledmac@warning{Can't find line-list file #1}}

\led@warn@BadAdvancelineSubline
\led@warn@BadAdvancelineLine 64 \newcommand*{\led@warn@BadAdvancelineSubline}{%
65 \eledmac@warning{\string\advanceline\space produced a sub-line
66 number less than zero.}}
67 \newcommand*{\led@warn@BadAdvancelineLine}{%
68 \eledmac@warning{\string\advanceline\space produced a line
69 number less than zero.}}

\led@warn@BadSetline
\led@warn@BadSetlinenum 70 \newcommand*{\led@warn@BadSetline}{%
71 \eledmac@warning{Bad \string\setline\space argument}}
72 \newcommand*{\led@warn@BadSetlinenum}{%
73 \eledmac@warning{Bad \string\setlinenum\space argument}}

\led@err@PstartNotNumbered
\led@err@PstartInPstart 74 \newcommand*{\led@err@PstartNotNumbered}{%
\led@err@PendNotNumbered 75 \eledmac@error{\string\pstart\space must be used within a
\led@err@PendNoPstart 76 numbered section}{\@ehc}}
\led@err@AutoparNotNumbered 77 \newcommand*{\led@err@PstartInPstart}{%
78 \eledmac@error{\string\pstart\space encountered while another
79 \string\pstart\space was in effect}{\@ehc}}
80 \newcommand*{\led@err@PendNotNumbered}{%
81 \eledmac@error{\string\pend\space must be used within a
82 numbered section}{\@ehc}}
83 \newcommand*{\led@err@PendNoPstart}{%
84 \eledmac@error{\string\pend\space must follow a \string\pstart}{\@ehc}}
85 \newcommand*{\led@err@AutoparNotNumbered}{%
86 \eledmac@error{\string\autopar\space must be used within a
87 numbered section}{\@ehc}}

\led@warn@BadAction
88 \newcommand*{\led@warn@BadAction}{%
89 \eledmac@warning{Bad action code, value \next@action.}}

```

```

\led@warn@DuplicateLabel
\led@warn@RefUndefined 90 \newcommand*{\led@warn@DuplicateLabel}[1]{%
91 \eledmac@warning{Duplicate definition of label ‘#1’ on page \the\pageno.}}
92 \newcommand*{\led@warn@RefUndefined}[1]{%
93 \eledmac@warning{Reference ‘#1’ on page \the\pageno\space undefined.
94 Using ‘000’.}}

\led@warn@NoMarginpars
95 \newcommand*{\led@warn@NoMarginpars}{%
96 \eledmac@warning{You can’t use \string\marginpar\space in numbered text}}

\led@warn@BadSidenotemargin
97 \newcommand*{\led@warn@BadSidenotemargin}{%
98 \eledmac@warning{Bad \string\sidenotemmargin\space argument}}

\led@warn@NoIndexFile
99 \newcommand*{\led@warn@NoIndexFile}[1]{%
100 \eledmac@warning{Undefined index file #1}}

\led@err@TooManyColumns
\led@err@UnequalColumns 101 \newcommand*{\led@err@TooManyColumns}{%
\led@err@LowStartColumn 102 \eledmac@error{Too many columns}{\@ehc}}
\led@err@HighEndColumn 103 \newcommand*{\led@err@UnequalColumns}{%
\led@err@ReverseColumns 104 \eledmac@error{Number of columns is not equal to the number
105 in the previous row (or \protect\\ \space forgotten?)}{\@ehc}}
106 \newcommand*{\led@err@LowStartColumn}{%
107 \eledmac@error{Start column is too low}{\@ehc}}
108 \newcommand*{\led@err@HighEndColumn}{%
109 \eledmac@error{End column is too high}{\@ehc}}
110 \newcommand*{\led@err@ReverseColumns}{%
111 \eledmac@error{Start column is greater than end column}{\@ehc}}

```

## 19 Sectioning commands

`\section@num` You use `\beginnumbering` and `\endnumbering` to begin and end a line-numbered section of the text; the pair of commands may be used as many times as you like within one document to start and end multiple, separately line-numbered sections. LaTeX will maintain and display a ‘section number’ as a count named `\section@num` that counts how many `\beginnumbering` and `\resumenumbers` commands have appeared; it needn’t be related to the logical divisions of your text.

`\extensionchars` Each section will read and write an associated ‘line-list file’, containing information used to do the numbering; the file will be called `<jobname>.\nn`, where `nn` is the section number. However, you may direct that an extra string be added before the `nn` in that filename, in order to distinguish these temporary files from others: that string is called `\extensionchars`. Initially it’s empty, since different operating

systems have greatly varying ideas about what characters are permitted in file names. So `\renewcommand{\extensionchars}{-}` gives temporary files called `jobname.-1`, `jobname.-2`, etc.

```
112 \newcount\section@num
113 \section@num=0
114 \let\extensionchars=\empty
```

`\ifnumbering` The `\ifnumbering` flag is set to `true` if we're within a numbered section (that is, between `\beginnumbering` and `\endnumbering`). You can use `\ifnumbering` in your own code to check whether you're in a numbered section, but don't change the flag's value.

```
115 \newif\ifnumbering
```

`\ifnumberingR` In preparation for the `eledpar` package, these are related to the 'left' text of parallel texts (when `\ifl@dpairing` is `TRUE`). They are explained in the `eledpar` manual.

```
\ifl@dpairingtrue
\l@dpairingtrue
\l@dpairingfalse 116 \newif\ifl@dpairing
\ifpst@rtedL 117 \l@dpairingfalse
\pst@rtedLtrue 118 \newif\ifpst@rtedL
\pst@rtedLfalse 119 \pst@rtedLfalse
\l@dnumpstartsl 120 \newcount\l@dnumpstartsl
\ifledRcol 121 \newif\ifledRcol
```

The `\ifnumberingR` flag is set to `true` if we're within a right text numbered section.

```
122 \newif\ifnumberingR
```

`\beginnumbering` `\beginnumbering` begins a section of numbered text. When it's executed we increment the section number, initialize our counters, send a message to your terminal, and call macros to start the lineation machinery and endnote files.

The initializations here are trickier than they look. `\line@list@stuff` will use all of the counters that are zeroed here when it assembles the line-list and other lists of information about the lineation. But it will do all of this locally and within a group, and when it's done the lists will remain but the counters will return to zero. Those same counters will then be used as we process the text of this section, but the assignments will be made globally. These initializations actually apply to both uses, though in all other respects there should be no direct interaction between the use of these counters and variables in the two processing steps.

```
123 \newcommand*{\beginnumbering}{%
124   \ifnumbering
125     \led@err@NumberingStarted
126   \endnumbering
127   \fi
128   \global\numberingtrue
129   \global\advance\section@num \@ne
130   \initnumbering@reg
131   \message{Section \the\section@num }%
132   \line@list@stuff{\jobname.\extensionchars\the\section@num}%
```

```

133 \l@dend@stuff
134 \setcounter{pstart}{1}
135 \begingroup
136 \initnumbering@sectcmd
137 }
138 \newcommand*{\initnumbering@reg}{%
139 \global\pst@rtedLfalse
140 \global\l@dnumstartL \z@
141 \global\absline@num \z@
142 \global\line@num \z@
143 \global\subline@num \z@
144 \global\@lock \z@
145 \global\sub@lock \z@
146 \global\sublines@false
147 \global\let\next@page@num=\relax
148 \global\let\sub@change=\relax
149 \resetprevline@
150 }
151

```

```

\initnumbering@sectcmd \initnumbering@sectcmd defines sectioning commands inside numbered section.
\ledsection It also defines quotation environment. Note that it's suppose user didn't change
\ledsection* \chapter. If he did, he should redefine \initnumbering@sectcmd.
\ledsubsection 152 \newcommand{\initnumbering@sectcmd}{
\ledsubsection* 153 \newcommand{\ledsection}[2][]{%
\ledsubsubsection 154 \leavevmode\pend\vspace{3.5ex \@plus 1ex \@minus .2ex}\skipnumbering%
\ledsubsubsection* 155 \pstart%
\ledchapter 156 \leavevmode\section{##1}{##2}\leavevmode\vspace{2.3ex \@plus .2ex}\skipnumbering\pend%
\ledchapter* 157 \vspace{-2\parskip}\vspace{-2\baselineskip}%
\quotation 158 \ifautopar\else\pstart\fi
\endquotation 159 }
\quote 160 \WithSuffix\newcommand\ledsection*[1]{%
\endquote 161 \leavevmode\pend\vspace{3.5ex \@plus 1ex \@minus .2ex}\skipnumbering%
162 \pstart%
163 \leavevmode\section*{##1}\leavevmode\vspace{2.3ex \@plus .2ex}\skipnumbering\pend%
164 \vspace{-2\parskip}\vspace{-2\baselineskip}%
165 \ifautopar\else\pstart\fi
166 }
167 \newcommand{\ledsubsection}[2][]{%
168 \leavevmode\pend\vspace{3.5ex \@plus 1ex \@minus .2ex}\skipnumbering%
169 \pstart%
170 \leavevmode\subsection{##1}{##2}\leavevmode\vspace{1.5ex \@plus .2ex}\skipnumbering\pend%
171 \vspace{-2\parskip}\vspace{-2\baselineskip}%
172 \ifautopar\else\pstart\fi
173 }
174 \WithSuffix\newcommand\ledsubsection*[1]{%
175 \leavevmode\pend\vspace{3.5ex \@plus 1ex \@minus .2ex}\skipnumbering%
176 \pstart%
177 \leavevmode\subsection*{##1}\leavevmode\vspace{1.5ex \@plus .2ex}\skipnumbering\pend%
178 \vspace{-2\parskip}\vspace{-2\baselineskip}%

```

```

179     \ifautopar\else\pstart\fi
180 }
181 \newcommand{\ledsubsubsection}[2][{}]{%
182     \leavevmode\pend\vspace{3.5ex \@plus 1ex \@minus .2ex}\skipnumbering%
183     \pstart%
184     \leavevmode\subsubsection[##1]{##2}\leavevmode\vspace{1.5ex \@plus .2ex}\skipnumbering%
185     \vspace{-2\parskip}\vspace{-2\baselineskip}%
186     \ifautopar\else\pstart\fi
187 }
188 \WithSuffix\newcommand{\ledsubsubsection*}[1]{%
189     \leavevmode\pend\vspace{3.5ex \@plus 1ex \@minus .2ex}\skipnumbering%
190     \pstart%
191     \leavevmode\subsubsection*{##1}\leavevmode\vspace{1.5ex \@plus .2ex}\skipnumbering%
192     \vspace{-2\parskip}\vspace{-2\baselineskip}%
193     \ifautopar\else\pstart\fi
194 }
195 \newcommand{\ledchapter}[2][{}]{\ifl@dmemoir\gdef\ch@pt@c{##1}\fi~\pend\skipnumbering\pstart}
196 \WithSuffix\newcommand{\ledchapter*}[1]{~\pend\skipnumbering\pstart\chapter*{##1}\pend\pstart}
197 \patchcmd{\@makeschapterhead}{1\par}{1}{-}{-}
198 \pretocmd{\@makeschapterhead}{\par}{-}{-}
199 \apptocmd{\@makeschapterhead}{\par}{-}{-}
200 \patchcmd{\@makeschapterhead}{\vskip 40\p@}{-}{-}{-}
201 \patchcmd{\@makechapterhead}{1\par}{1}{-}{-}
202 \pretocmd{\@makechapterhead}{\par}{-}{-}
203 \apptocmd{\@makechapterhead}{\par}{-}{-}
204 \patchcmd{\@makechapterhead}{\vskip 40\p@}{-}{-}{-}
205 \apptocmd{\@chapter}{\par\leavevmode\vspace{40\p@}\skipnumbering}{-}{-}
206 \apptocmd{\@schapter}{\par\leavevmode\vspace{40\p@}\skipnumbering}{-}{-}
207 \newcommand\beforeledchapter{\pend\cleardoublepage\pstart}
208 \patchcmd{\chapter}{\cleardoublepage}{\relax}{-}{-}
209 \patchcmd{\chapter}{\clearpage}{\relax}{-}{-}
210 \ifnoquotation@else
211 \renewcommand{\quotation}{\par\leavevmode%
212     \parindent=1.5em%
213     \skipnumbering%
214     \ifautopar%
215         \vskip-\parskip%
216     \else%
217         \vskip\topsep%
218     \fi%
219     \global\leftskip=\leftmargin%
220     \global\rightskip=\leftmargin%
221 }
222 \renewcommand{\endquotation}{\par%
223     \global\leftskip=0pt%
224     \global\rightskip=0pt%
225     \leavevmode%
226     \skipnumbering%
227     \ifautopar%
228         \vskip-\parskip%

```

```

229             \else%
230             \vskip\topsep%
231             \fi%
232         }
233     \renewcommand{\quote}{\par\leavevmode%
234             \parindent=0pt%
235             \skipnumbering%
236             \ifautopar%
237             \vskip-\parskip%
238             \else%
239             \vskip\topsep%
240             \fi%
241             \global\leftskip=\leftmargin%
242             \global\rightskip=\leftmargin%
243     }
244     \renewcommand{\endquote}{\par%
245             \global\leftskip=0pt%
246             \global\rightskip=0pt%
247             \leavevmode%
248             \skipnumbering%
249             \ifautopar%
250             \vskip-\parskip%
251             \else%
252             \vskip\topsep%
253             \fi%
254     }
255     \fi
256 }

```

`\ledsectnotoc` The `\ledsectnotoc` only disables the `\addcontentsline` macro.

```

257 \newcommand{\ledsectnotoc}{\let\addcontentsline\@gobblethree}

```

`\endnumbering` `\endnumbering` must follow the last text for a numbered section. It takes care of notifying you when changes have been noted in the input that require running the file through again to move everything to the right place.

```

258 \def\endnumbering{%
259     \ifnumbering
260     \global\numberingfalse
261     \normal@pars
262     \ifl@dpairing
263     \global\pst@rtedLfalse
264     \else
265     \ifx\insertlines@list\empty\else
266     \global\noteschanged@true
267     \fi
268     \ifx\line@list\empty\else
269     \global\noteschanged@true
270     \fi
271     \fi

```

```

272 \ifnoteschanged@
273 \led@mess@NotesChanged
274 \fi
275 \else
276 \led@err@NumberingNotStarted
277 \fi
278 \autoparfalse\endgroup}

```

`\pausenumbering` The `\pausenumbering` macro is just the same as `\endnumbering`, but with the `\resumenumbering` `\ifnumbering` flag set to true, to show that numbering continues across the gap.<sup>22</sup>

```

279 \newcommand{\pausenumbering}{%
280 \endnumbering\global\numberingtrue}

```

The `\resumenumbering` macro is a bit more involved, but not much. It does most of the same things as `\beginnumbering`, but without resetting the various counters. Note that no check is made by `\resumenumbering` to ensure that `\pausenumbering` was actually invoked.

```

281 \newcommand*{\resumenumbering}{%
282 \ifnumbering
283 \global\pst@rtedLtrue
284 \global\advance\section@num \@ne
285 \led@mess@SectionContinued{\the\section@num}%
286 \line@list@stuff{\jobname.\extensionchars\the\section@num}%
287 \l@dend@stuff
288 \else
289 \led@err@NumberingShouldHaveStarted
290 \endnumbering
291 \beginnumbering
292 \fi}
293

```

## 20 Line counting

### 20.1 Choosing the system of lineation

Sometimes you want line numbers that start at 1 at the top of each page; sometimes you want line numbers that start at 1 at each `\pstart`; other times you want line numbers that start at 1 at the start of each section and increase regardless of page breaks. `eledmac` can do it either way, and you can switch from one to the other within one work. But you have to choose one or the other for all line numbers and line references within each section. Here we will define internal codes for these systems and the macros you use to select them.

`\ifbypstart@` The `\ifbypage@` and `\ifbypstart@` flag specify the current lineation system:

```

\byppstart@true
\byppstart@false
\ifbypage@
\byppage@true
\byppage@false

```

- line-of-page: `bypstart@ = false` and `bypage@ = true`.

---

<sup>22</sup>Our thanks to Wayne Sullivan, who suggested the idea behind these macros.



- line-of-pstart: `bypstart@ = true` and `bypage@ = false`.

eledmac will use the line-of-section system unless instructed otherwise.

```
294 \newif\ifbypage@
295 \newif\ifbypstart@
```

`\lineation` `\lineation{<word>}` is the macro you use to select the lineation system. Its argument is a string: either `page` or `section` or `pstart`.

```
296 \newcommand*{\lineation}[1]{%
297   \ifnumbering
298     \led@err@LineationInNumbered
299   \else
300     \def\@tempa{#1}\def\@tempb{page}%
301     \ifx\@tempa\@tempb
302       \global\bypage@true
303       \global\bypstart@false
304       \pstartinfootnote[] [false]
305     \else
306       \def\@tempb{pstart}%
307       \ifx\@tempa\@tempb
308         \global\bypage@false
309         \global\bypstart@true
310         \pstartinfootnote
311       \else
312         \def\@tempb{section}
313         \ifx\@tempa\@tempb
314           \global\bypage@false
315           \global\bypstart@false
316           \pstartinfootnote[] [false]
317         \else
318           \led@warn@BadLineation
319         \fi
320       \fi
321     \fi
322   \fi}}
```

`\linenummargin` You call `\linenummargin{<word>}` to specify which margin you want your line numbers in; it takes one argument, a string. You can put the line numbers in the same margin on every page using `left` or `right`; or you can use `inner` or `outer` to get them in the inner or outer margins. (These last two options assume that even-numbered pages will be on the left-hand side of every opening in your book.) You can change this within a numbered section, but the change may not take effect just when you'd like; if it's done between paragraphs nothing surprising should happen.

The selection is recorded in the count `\line@margin`: 0 for left, 1 for right, 2 for outer, and 3 for inner.

```
323 \newcount\line@margin
324 \newcommand*{\linenummargin}[1]{%
325   \l@getline@margin{#1}%
```

```

326 \ifnum\@l@tempcntb>\m@ne
327   \global\line@margin=\@l@tempcntb
328 \fi}}
329 \newcommand*{\l@getline@margin}[1]{%
330   \def\@tempa{#1}\def\@tempb{left}%
331   \ifx\@tempa\@tempb
332     \@l@tempcntb \z@
333   \else
334     \def\@tempb{right}%
335     \ifx\@tempa\@tempb
336       \@l@tempcntb \@ne
337     \else
338       \def\@tempb{outer}%
339       \ifx\@tempa\@tempb
340         \@l@tempcntb \tw@
341       \else
342         \def\@tempb{inner}%
343         \ifx\@tempa\@tempb
344           \@l@tempcntb \thr@@
345         \else
346           \led@warn@BadLinenummargin
347           \@l@tempcntb \m@ne
348         \fi
349       \fi
350     \fi
351 \fi}
352

```

`\c@firstlinenum` The following counters tell `eledmac` which lines should be printed with line numbers. `firstlinenum` is the number of the first line in each section that gets a number; `linenumincrement` is the difference between successive numbered lines. The initial values of these counters produce labels on lines 5, 10, 15, etc. `linenumincrement` must be at least 1.

```

353 \newcounter{firstlinenum}
354 \setcounter{firstlinenum}{5}
355 \newcounter{linenumincrement}
356 \setcounter{linenumincrement}{5}

```

`\c@firstsublinenum` The following parameters are just like `firstlinenum` and `linenumincrement`, but  
`\c@sublinenumincrement` for sub-line numbers. `sublinenumincrement` must be at least 1.

```

357 \newcounter{firstsublinenum}
358 \setcounter{firstsublinenum}{5}
359 \newcounter{sublinenumincrement}
360 \setcounter{sublinenumincrement}{5}
361

```

These macros can be used to set the corresponding counters.

```

\firstlinenum 362 \newcommand*{\firstlinenum}[1]{\setcounter{firstlinenum}{#1}}
\linenumincrement 363 \newcommand*{\linenumincrement}[1]{\setcounter{linenumincrement}{#1}}
\firstsublinenum
\sublinenumincrement

```

```

364 \newcommand*{\firstsublinenum}[1]{\setcounter{firstsublinenum}{#1}}
365 \newcommand*{\sublinenumincrement}[1]{\setcounter{sublinenumincrement}{#1}}
366

```

`\lockdisp` When line locking is being used, the `\lockdisp{<word>}` macro specifies whether a line number—if one is due to appear—should be printed on the first printed line  
`\lock@disp` a line number—if one is due to appear—should be printed on the first printed line  
`\l@getlock@disp` or on the last, or by all of them. Its argument is a word, either **first**, **last**, or **all**. Initially, it is set to **first**.

`\lock@disp` encodes the selection: 0 for first, 1 for last, 2 for all.

```

367 \newcount\lock@disp
368 \newcommand{\lockdisp}[1]{%
369   \l@getlock@disp{#1}%
370   \ifnum\@l@tempcntb>\m@ne
371     \global\lock@disp=\@l@tempcntb
372   \else
373     \led@warn@BadLockdisp
374   \fi}}
375 \newcommand*{\l@getlock@disp}[1]{
376   \def\@tempa{#1}\def\@tempb{first}%
377   \ifx\@tempa\@tempb
378     \@l@tempcntb \z@
379   \else
380     \def\@tempb{last}%
381     \ifx\@tempa\@tempb
382       \@l@tempcntb \@ne
383     \else
384       \def\@tempb{all}%
385       \ifx\@tempa\@tempb
386         \@l@tempcntb \tw@
387       \else
388         \@l@tempcntb \m@ne
389       \fi
390     \fi
391   \fi}
392

```

`\sublockdisp` The same questions about where to print the line number apply to sub-lines, and  
`\sublock@disp` these are the analogous macros for dealing with the problem.

```

393 \newcount\sublock@disp
394 \newcommand{\sublockdisp}[1]{%
395   \l@getlock@disp{#1}%
396   \ifnum\@l@tempcntb>\m@ne
397     \global\sublock@disp=\@l@tempcntb
398   \else
399     \led@warn@BadSublockdisp
400   \fi}}
401

```

`\linenumberstyle` We provide a mechanism for using different representations of the line numbers,  
`\linenumrep` not just the normal arabic.  
`\linenumr@p`  
`\sublinenumberstyle`  
`\sublinenumrep`  
`\sublinenumr@p`

NOTE: In v0.7 `\linenumrep` and `\sublinenumrep` replaced the internal `\linenumr@p` and `\sublinenumr@p`.

`\linenumberstyle` and `\sublinenumberstyle` are user level macros for setting the number representation (`\linenumrep` and `\sublinenumrep`) for line and sub-line numbers.

```
402 \newcommand*{\linenumberstyle}[1]{%
403   \def\linenumrep##1{\@nameuse{#1}{##1}}
404 \newcommand*{\sublinenumberstyle}[1]{%
405   \def\sublinenumrep##1{\@nameuse{#1}{##1}}
406 \linenumberstyle{arabic}
407 \let\linenumr@p\linenumrep
408 \sublinenumberstyle{arabic}
409 \let\sublinenumr@p\sublinenumrep
410
```

Initialise the number styles to arabic.

<pre>\leftlinenum \rightlinenum \linenumsep \numlabfont \ledlinenum</pre>	<p><code>\leftlinenum</code> and <code>\rightlinenum</code> are the macros that are called to print marginal line numbers on a page, for left- and right-hand margins respectively. They're made easy to access and change, since you may often want to change the styling in some way. These standard versions illustrate the general sort of thing that will be needed; they're based on the <code>\leftheadline</code> macro in <i>The TeXbook</i>, p. 416.</p>
---	--

Whatever these macros output gets printed in a box that will be put into the appropriate margin without any space between it and the line of text. You'll generally want a kern between a line number and the text, and `\linenumsep` is provided as a standard way of storing its size. Line numbers are usually printed in a smaller font, and `\numlabfont` is provided as a standard name for that font. When called, these macros will be executed within a group, so font changes and the like will remain local.

`\ledlinenum` typesets the line (and subline) number.

The original `\numlabfont` specification is equivalent to the LaTeX `\scriptsize` for a 10pt document.

```
411 \newlength{\linenumsep}
412 \setlength{\linenumsep}{1pc}
413 \newcommand*{\numlabfont}{\normalfont\scriptsize}
414 \newcommand*{\ledlinenum}{%
415   \numlabfont\linenumrep{\line@num}%
416   \ifsublines@
417     \ifnum\subline@num>0\relax
418       \unskip\fullstop\sublinenumrep{\subline@num}%
419     \fi
420   \fi}
421 \newcommand*{\leftlinenum}{%
422   \ledlinenum
423   \kern\linenumsep}
424 \newcommand*{\rightlinenum}{%
425   \kern\linenumsep
```

```
426 \ledlinenum}
427
```

## 20.2 List macros

Reminder: compare these with the LaTeX list macros in case they would be suitable instead.

We will make heavy use of lists of information, which will be built up and taken apart by the following macros; they are adapted from *The TeXbook*, pp. 378–379, which discusses their use in more detail.

These macros consume a large amount of the run-time of this code. We intend to replace them in a future version, and in anticipation of doing so have defined their interface in such a way that it is not sensitive to details of the underlying code.

**\list@create** The **\list@create** macro creates a new list. In this version of **eledmac** this macro doesn't do anything beyond initializing an empty list macro, but in future versions it may do more.

```
428 \newcommand*{\list@create}[1]{\global\let#1=\empty}
```

**\list@clear** The **\list@clear** macro just initializes a list to the empty list; in this version of **eledmac** it is no different from **\list@create**.

```
429 \newcommand*{\list@clear}[1]{\global\let#1=\empty}
```

**\xright@appenditem** **\xright@appenditem** expands an item and appends it to the right end of a list macro. We want the expansion because we'll often be using this to store the current value of a counter. It creates global control sequences, like **\xdef**, and uses two temporary token-list registers, **\@toksa** and **\@toksb**.

```
430 \newtoks\@toksa \newtoks\@toksb
431 \global\@toksa={\}
432 \long\def\xright@appenditem#1\to#2{%
433   \global\@toksb=\expandafter{#2}%
434   \xdef#2{\the\@toksb\the\@toksa\expandafter{#1}}%
435   \global\@toksb={}}
```

**\xleft@appenditem** **\xleft@appenditem** expands an item and appends it to the left end of a list macro; it is otherwise identical to **\xright@appenditem**.

```
436 \long\def\xleft@appenditem#1\to#2{%
437   \global\@toksb=\expandafter{#2}%
438   \xdef#2{\the\@toksa\expandafter{#1}\the\@toksb}%
439   \global\@toksb={}}
```

**\gl@p** The **\gl@p** macro removes the leftmost item from a list and places it in a control sequence. You say **\gl@p\l\to\z** (where **\l** is the list macro, and **\z** receives the left item). **\l** is assumed nonempty: say **\ifx\l\empty** to test for an empty **\l**. The control sequences created by **\gl@p** are all global.

```
440 \def\gl@p#1\to#2{\expandafter\gl@poff#1\gl@poff#1#2}
441 \long\def\gl@poff\#1#2\gl@poff#3#4{\gdef#4{#1}\gdef#3{#2}}
442
```

### 20.3 Line-number counters and lists

Footnote references using line numbers rather than symbols can't be generated in one pass, because we don't know the line numbers till we ship out the pages. It would be possible if footnotes were never keyed to more than one line; but some footnotes gloss passages that may run for several lines, and they must be tied to the first line of the passage glossed. And even one-line passages require two passes if we want line-per-page numbering rather than line-per-section numbering.

So we run LaTeX over the text several times, and each time save information about page and line numbers in a 'line-list file' to be used during the next pass. At the start of each section—whenever `\beginnumbering` is executed—the line-list file for that section is read, and the information from it is encoded into a few list macros.

We need first to define the different line numbers that are involved in these macros, and the associated counters.

```

\line@num The count \line@num stores the line number that's used in marginal line number-
ing and in notes: counting either from the start of the page or from the start of
the section, depending on your choice for this section. This may be qualified by
\subline@num.
443 \newcount\line@num

\subline@num The count \subline@num stores a sub-line number that qualifies \line@num. For
example, line 10 might have sub-line numbers 1, 2 and 3, which might be printed
as lines 10.1, 10.2, 10.3.
444 \newcount\subline@num

\ifsublines@ We maintain an associated flag, \ifsublines@, to tell us whether we're within a
\sublines@true sub-line range or not.
\sublines@false You may wonder why we don't just use the value of \subline@num to determine
this—treating anything greater than 0 as an indication that sub-lineation is on. We
need a separate flag because sub-lineation can be used together with line-number
locking in odd ways: several pieces of a logical line might be interrupted by pieces
of sub-lineated text, and those sub-line numbers should not return to zero until
the next change in the major line number. This is common in the typesetting
of English Renaissance verse drama, in which stage directions are given sub-line
numbers: a single line of verse may be interrupted by several stage directions.
445 \newif\ifsublines@

\absline@num The count \absline@num stores the absolute number of lines since the start of
the section: that is, the number we've actually printed, no matter what numbers
we attached to them. This value is never printed on an output page, though
\line@num will often be equal to it. It is used internally to keep track of where
notes are to appear and where new pages start: using this value rather than
\line@num is a lot simpler, because it doesn't depend on the lineation system in
use.
446 \newcount\absline@num

```

We'll be calling `\absline@num` numbers 'absolute' numbers, and `\line@num` and `\subline@num` numbers 'visible' numbers.

`\@lock`    The counts `\@lock` and `\sub@lock` tell us the state of line-number and sub-line-number locking. 0 means we're not within a locked set of lines; 1 means we're at the first line in the set; 2, at some intermediate line; and 3, at the last line.

447 `\newcount\@lock`

448 `\newcount\sub@lock`

`\line@list`    Now we can define the list macros that will be created from the line-list file. We  
`\insertlines@list` will maintain the following lists:

`\actionlines@list`  
`\actions@list`

- `\line@list`: the page and line numbers for every lemma marked by `\edtext`. There are seven pieces of information, separated by vertical bars:

1. the starting page,
2. line, and
3. sub-line numbers, followed by the
4. ending page,
5. line, and
6. sub-line numbers, and then the
7. font specifier for the lemma.

These line numbers are all visible numbers. The font specifier is a set of four codes for font encoding, family, series, and shape, separated by / characters. Thus a lemma that started on page 23, line 35 and went on until page 24, line 3 (with no sub-line numbering), and was typeset in a normal roman font would have a line list entry like this:

23|35|0|24|3|0|OT1/cmr/m/n.

There is one item in this list for every lemma marked by `\edtext`, even if there are several notes to that lemma, or no notes at all. `\edtext` reads the data in this list, making it available for use in the text of notes.

- `\insertlines@list`: the line numbers of lines that have footnotes or other insertions. These are the absolute numbers where the corresponding lemmas begin. This list contains one entry for every footnote in the section; one lemma may contribute no footnotes or many footnotes. This list is used by `\add@inserts` within `\do@line`, to tell it where to insert notes.
- `\actionlines@list`: a list of absolute line numbers at which we are to perform special actions; these actions are specified by the `\actions@list` list defined below.
- `\actions@list`: action codes corresponding to the line numbers in `\actionlines@list`. These codes tell `eledmac` what action it's supposed to take at each of these lines. One action, the page-start action, is generated behind the scenes by `eledmac` itself; the others, for specifying sub-lineation, line-number locking, and line-number alteration, are generated only by explicit commands in your input file. The page-start and line-number-alteration actions require arguments, to specify the new values for the page or line numbers; instead of

storing those arguments in another list, we have chosen the action-code values so that they can encode both the action and the argument in these cases. Action codes greater than  $-1000$  are page-start actions, and the code value is the page number; action codes less than  $-5000$  specify line numbers, and the code value is a transformed version of the line number; action codes between these two values specify other actions which require no argument.

Here is the full list of action codes and their meanings:

Any number greater than  $-1000$  is a page-start action: the line number associated with it is the first line on a page, and the action number is the page number. (The cutoff of  $-1000$  is chosen because negative page-number values are used by some macro packages; we assume that page-number values less than  $-1000$  are not common.) Page-start action codes are added to the list by the `\page@action` macro, which is (indirectly) triggered by the workings of the `\page@start` macro; that macro should always be called in the output routine, just before the page contents are assembled. `eledmac` calls it in `\pagecontents`.

The action code  $-1001$  specifies the start of sub-lineation: meaning that, starting with the next line, we should be advancing `\subline@num` at each start-of-line command, rather than `\line@num`.

The action code  $-1002$  specifies the end of sub-lineation. At the next start-of-line, we should clear the sub-line counter and start advancing the line number. The action codes for starting and ending sub-lineation are added to the list by the `\sub@action` macro, as called to implement the `\startsub` and `\endsub` macros.

The action code  $-1003$  specifies the start of line number locking. After the number for the current line is computed, it will remain at that value through the next line that has an action code to end locking.

The action code  $-1004$  specifies the end of line number locking.

The action code  $-1005$  specifies the start of sub-line number locking. After the number for the current sub-line is computed, it will remain at that value through the next sub-line that has an action code to end locking.

The action code  $-1006$  specifies the end of sub-line number locking.

The four action codes for line and sub-line number locking are added to the list by the `\do@lockon` and `\do@lockoff` macros, as called to implement the `\startlock` and `\endlock` macros.

An action code of  $-5000$  or less sets the current visible line number (either the line number or the sub-line number, whichever is currently being advanced) to a specific positive value. The value of the code is  $-(5000 + n)$ , where  $n$  is the value (always  $\geq 0$ ) assigned to the current line number. Action codes of this type are added to the list by the `\set@line@action` macro, as called to implement the `\advanceline` and `\setline` macros: this action only occurs when the user has specified some change to the line numbers using those macros. Normally `eledmac` computes the visible line numbers



from the absolute line numbers with reference to the other action codes and the settings they invoke; it doesn't require an entry in the action-code list for every line.

Here are the commands to create these lists:

```
449 \list@create{\line@list}
450 \list@create{\insertlines@list}
451 \list@create{\actionlines@list}
452 \list@create{\actions@list}
453
```

```
\page@num We'll need some counts while we read the line-list, for the page number and the
\endpage@num ending page, line, and sub-line numbers. Some of these will be used again later
\endline@num on, when we are acting on the data in our list macros.
\endsubline@num
454 \newcount\page@num
455 \newcount\endpage@num
456 \newcount\endline@num
457 \newcount\endsubline@num
```

```
\ifnoteschanged@ If the number of the footnotes in a section is different from what it was during
\noteschanged@true the last run, or if this is the very first time you've run LaTeX, on this file, the
\noteschanged@false information from the line-list used to place the notes will be wrong, and some
notes will probably be misplaced. When this happens, we prefer to give a single
error message for the whole section rather than messages at every point where we
notice the problem, because we don't really know where in the section notes were
added or removed, and the solution in any case is simply to run LaTeX two more
times; there's no fix needed to the document. The \ifnoteschanged@ flag is set
if such a change in the number of notes is discovered at any point.
458 \newif\ifnoteschanged@
```

```
\resetprevline@ Inside the apparatus, at each note, the line number is memorized in a macro
called \prevlineX, where X is the letter of the current series. This macro is called
when using \numberonlyfirstinline. This macro must be reset at the same time
as the line number. The \resetprevline@ does this resetting for every series.
```

```
\resetprevline@
459 \newcommand*{\resetprevline@}{%
460 \def\do##1{\global\csundef{prevline##1}}%
461 \dolistloop{\@series}%
462 }
```

## 20.4 Reading the line-list file

```
\read@linelist \read@linelist{<file>} is the control sequence that's called by \beginnumbering
(via \line@list@stuff) to open and process a line-list file; its argument is the
name of the file.
463 \newread\@inputcheck
```

```

464 \newcommand*{\read@linelist}[1]{%
465   \list@clearing@reg

```

When the file is there we start a new group and make some special definitions we'll need to process it: it's a sequence of T<sub>E</sub>X commands, but they require a few special settings. We make [ and ] become grouping characters: they're used that way in the line-list file, because we need to write them out one at a time rather than in balanced pairs, and it's easier to just use something other than real braces. @ must become a letter, since this is run in the ordinary LaTeX context. We ignore carriage returns, since if we're in horizontal mode they can get interpreted as spaces to be printed.

Our line, page, and line-locking counters were already zeroed by \line@list@stuff if this is being called from within \beginnumbering; sub-lineation will be turned off as well in that case. On the other hand, if this is being called from \resumenummering, those things should still have the values they had when \pausenumbering was executed.

If the file is not there, we print an informative message.

Now, after these preliminaries, we start interpreting the file.

```

466   \get@linelistfile{#1}%
467   \endgroup

```

When the reading is done, we're all through with the line-list file. All the information we needed from it will now be encoded in our list macros.

Finally, we initialize the \next@actionline and \next@action macros, which specify where and what the next action to be taken is.

```

468   \global\page@num=\m@ne
469   \ifx\actionlines@list\empty
470     \gdef\next@actionline{1000000}%
471   \else
472     \glp\actionlines@list\to\next@actionline
473     \glp\actions@list\to\next@action
474   \fi}
475

```

\list@clearing@reg    Clears the lists for \read@linelist

```

476 \newcommand*{\list@clearing@reg}{%
477   \list@clear{\line@list}%
478   \list@clear{\insertlines@list}%
479   \list@clear{\actionlines@list}%
480   \list@clear{\actions@list}}

```

\get@linelistfile    eldmac can take advantage of the LaTeX 'safe file input' macros to get the line-list file.

```

481 \newcommand*{\get@linelistfile}[1]{%
482   \InputIfFileExists{#1}{%
483     \global\noteschanged@false
484     \begingroup
485     \catcode'\[=1 \catcode'\]=2

```

```

486     \makeatletter \catcode'\^^M=9}{%
487     \led@warn@NoLineFile{#1}%
488     \global\noteschanged@true
489     \begingroup}%
490 }
491

```

This version of `\read@linelist` creates list macros containing data for the entire section, so they could get rather large. It would be no more difficult to read the line-list file incrementally rather than all at once: we could read, at the start of each paragraph, only the commands relating to that paragraph. But this would require that we have two line-lists open at once, one for reading, one for writing, and on systems without version numbers we'd have to do some file renaming outside of LaTeX for that to work. We've retained this slower approach to avoid that sort of hacking about, but have provided the `\pausenumbering` and `\resumenumbering` macros to help you if you run into macro memory limitations (see p.11 above).

## 20.5 Commands within the line-list file

This section defines the commands that can appear within a line-list file. They all have very short names because we are likely to be writing very large numbers of them out. One macro, `\@l`, is especially short, since it will be written to the line-list file once for every line of text in a numbered section. (Another of these commands, `\@lab`, will be introduced in a later section, among the cross-referencing commands it is associated with.)

When these commands modify the various page and line counters, they deliberately do not say `\global`. This is because we want them to affect only the counter values within the current group when nested calls of `\@ref` occur. (The code assumes throughout that the value of `\globaldefs` is zero.)

The macros with `action` in their names contain all the code that modifies the action-code list: again, this is so that they can be turned off easily for nested calls of `\@ref`.

**\@l** `\@l` does everything related to the start of a new line of numbered text.

**\@l@reg** In order to get the `\setlinenum` to work Peter Wilson had to slip in some new code at the start of the macro, to get the timing of the actions correct. The problem was that his original naive implementation of `\setlinenum` had a unfortunate tendency to change the number of the last line of the *preceding* paragraph. The new code is sort of based on the page number handling and `\setline`. It seems that a lot of fiddling with the line number internals is required.

In November 2004 in order to accurately determine page numbers Peter Wilson added these to the macro. It is now:

```
\@l{\<page counter number>}\{\<printed page number>}
```

I don't (yet) use the printed number (i.e., the `\thepage`) but it may come in handy later. The macro `\fix@page` checks if a new page has started.

```

492 \newcommand{\@l}[2]{%
493   \fix@page{#1}%
494   \@l@reg}
495 \newcommand*{\@l@reg}{%
496   \ifx\l@dchset@num\relax \else
497     \advance\absline@num \@ne
498     \set@line@action
499     \let\l@dchset@num=\relax
500     \advance\absline@num \m@ne
501     \advance\line@num \m@ne
502   \fi

```

First increment the absolute line-number, and perform deferred actions relating to page starts and sub-lines.

```

503   \advance\absline@num \@ne
504     \ifx\next@page@num\relax \else
505       \page@action
506       \let\next@page@num=\relax
507     \fi
508     \ifx\sub@change\relax \else
509       \ifnum\sub@change>\z@
510         \sublines@true
511       \else
512         \sublines@false
513       \fi
514       \sub@action
515       \let\sub@change=\relax
516     \fi

```

Fix the lock counters, if necessary. A value of 1 is advanced to 2; 3 advances to 0; other values are unchanged.

```

517     \ifcase\@lock
518       \or
519         \@lock \tw@
520       \or \or
521         \@lock \z@
522     \fi
523     \ifcase\sub@lock
524       \or
525         \sub@lock \tw@
526       \or \or
527         \sub@lock \z@
528     \fi

```

Now advance the visible line number, unless it's been locked.

```

529     \ifsublines@
530       \ifnum\sub@lock<\tw@
531         \advance\subline@num \@ne
532       \fi
533     \else
534       \ifnum\@lock<\tw@

```

```

535             \advance\line@num \@ne \subline@num \z@
536             \fi
537     \fi}
538

```

`\@page \@page{<num>}` marks the start of a new output page; its argument is the number of that page.

First we reset the visible line numbers, if we're numbering by page, and store the page number itself in a count.

```

539 \newcommand*{\@page}[1]{%
540   \ifbypage@
541     \line@num \z@ \subline@num \z@
542   \fi
543   \page@num=#1\relax

```

And we set a flag that tells `\@l` that a new page number is to be set, because other associated actions shouldn't occur until the next line-start occurs.

```

544   \def\next@page@num{#1}}
545

```

`\last@page@num` `\fix@page` basically replaces `\@page`. It determines whether or not a new page has been started, based on the page values held by `\@l`.

```

546 \newcount\last@page@num
547 \last@page@num=-10000
548 \newcommand*{\fix@page}[1]{%
549   \ifnum #1=\last@page@num
550   \else
551     \ifbypage@
552       \line@num=\z@ \subline@num=\z@
553     \fi
554     \page@num=#1\relax
555     \last@page@num=#1\relax
556     \def\next@page@num{#1}%
557   \fi}
558

```

`\@pend` These don't do anything at this point, but will have been added to the auxiliary file(s) if the `eledpar` package has been used. They are just here to stop `eledmac` from moaning if the `eledpar` is used for one run and then not for the following one.

```

559 \newcommand*{\@pend}[1]{}
560 \newcommand*{\@pendR}[1]{}
561 \newcommand*{\@lopL}[1]{}
562 \newcommand*{\@lopR}[1]{}
563

```

`\sub@on` The `\sub@on` and `\sub@off` macros turn sub-lineation on and off: but not directly, since such changes don't really take effect until the next line of text. Instead they set a flag that notifies `\@l` of the necessary action.

```

564 \newcommand*{\sub@on}{\ifsublines@
565     \let\sub@change=\relax
566 \else
567     \def\sub@change{1}%
568 \fi}
569 \newcommand*{\sub@off}{\ifsublines@
570     \def\sub@change{-1}%
571 \else
572     \let\sub@change=\relax
573 \fi}
574

```

`\@adv` The `\@adv{<num>}` macro advances the current visible line number by the amount specified as its argument. This is used to implement `\advanceline`.

```

575 \newcommand*{\@adv}[1]{\ifsublines@
576     \advance\subline@num by #1\relax
577     \ifnum\subline@num<\z@
578         \led@warn@BadAdvancelineSubline
579         \subline@num \z@
580     \fi
581 \else
582     \advance\line@num by #1\relax
583     \ifnum\line@num<\z@
584         \led@warn@BadAdvancelineLine
585         \line@num \z@
586     \fi
587 \fi
588 \set@line@action}
589

```

`\@set` The `\@set{<num>}` macro sets the current visible line number to the value specified as its argument. This is used to implement `\setline`.

```

590 \newcommand*{\@set}[1]{\ifsublines@
591     \subline@num=#1\relax
592 \else
593     \line@num=#1\relax
594 \fi
595 \set@line@action}
596

```

`\l@d@set` The `\l@d@set{<num>}` macro sets the line number for the next `\pstart...` to the value specified as its argument. This is used to implement `\setlinenum`.

`\l@dchset@num` is a flag to the `\@l` macro. If it is not `\relax` then a linenum change is to be done.

```

597 \newcommand*{\l@d@set}[1]{%
598     \line@num=#1\relax
599     \advance\line@num \@ne
600     \def\l@dchset@num{#1}}
601 \let\l@dchset@num\relax

```

602

`\page@action` `\page@action` adds an entry to the action-code list to change the page number.

```
603 \newcommand*{\page@action}{%
604   \xright@appenditem{\the\absline@num}\to\actionlines@list
605   \xright@appenditem{\next@page@num}\to\actions@list}
```

`\set@line@action` `\set@line@action` adds an entry to the action-code list to change the visible line number.

```
606 \newcommand*{\set@line@action}{%
607   \xright@appenditem{\the\absline@num}\to\actionlines@list
608   \ifsublines@
609     \l@ldtempcnta=-\subline@num
610   \else
611     \l@ldtempcnta=-\line@num
612   \fi
613   \advance\l@ldtempcnta by -5000
614   \xright@appenditem{\the\l@ldtempcnta}\to\actions@list}
```

`\sub@action` `\sub@action` adds an entry to the action-code list to turn sub-lineation on or off, according to the current value of the `\ifsublines@` flag.

```
615 \newcommand*{\sub@action}{%
616   \xright@appenditem{\the\absline@num}\to\actionlines@list
617   \ifsublines@
618     \xright@appenditem{-1001}\to\actions@list
619   \else
620     \xright@appenditem{-1002}\to\actions@list
621   \fi}
```

`\lock@on` `\lock@on` adds an entry to the action-code list to turn line number locking on.

`\do@lockon` The current setting of the sub-lineation flag tells us whether this applies to line numbers or sub-line numbers.

`\do@lockonL`

Adding commands to the action list is slow, and it's very often the case that a lock-on command is immediately followed by a lock-off command in the line-list file, and therefore really does nothing. We use a look-ahead scheme here to detect such pairs, and add nothing to the line-list in those cases.

```
622 \newcommand*{\lock@on}{\futurelet\next\do@lockon}
623 \newcommand*{\do@lockon}{%
624   \ifx\next\lock@off
625     \global\let\lock@off=\skip@lockoff
626   \else
627     \do@lockonL
628   \fi}
629 \newcommand*{\do@lockonL}{%
630   \xright@appenditem{\the\absline@num}\to\actionlines@list
631   \ifsublines@
632     \xright@appenditem{-1005}\to\actions@list
633   \ifnum\sub@lock=\z@
634     \sub@lock \@ne
```

```

635     \else
636         \ifnum\sub@lock=\thr@@
637             \sub@lock \@ne
638         \fi
639     \fi
640 \else
641     \xright@appenditem{-1003}\to\actions@list
642     \ifnum\@lock=\z@
643         \@lock \@ne
644     \else
645         \ifnum\@lock=\thr@@
646             \@lock \@ne
647         \fi
648     \fi
649 \fi}
650

```

`\lock@off` `\lock@off` adds an entry to the action-code list to turn line number locking off.

```

\do@lockoff 651 \newcommand*{\do@lockoff}{%
\do@lockoffL 652 \xright@appenditem{\the\absline@num}\to\actionlines@list
\skip@lockoff 653 \ifsublines@
654     \xright@appenditem{-1006}\to\actions@list
655     \ifnum\sub@lock=\tw@
656         \sub@lock \thr@@
657     \else
658         \sub@lock \z@
659     \fi
660 \else
661     \xright@appenditem{-1004}\to\actions@list
662     \ifnum\@lock=\tw@
663         \@lock \thr@@
664     \else
665         \@lock \z@
666     \fi
667 \fi}
668 \newcommand*{\do@lockoff}{\do@lockoffL}
669 \newcommand*{\skip@lockoff}{\global\let\lock@off=\do@lockoff}
670 \global\let\lock@off=\do@lockoff
671

```

`\n@num` This macro implements the `\skipnumbering` command. It uses a new action code, namely 1007.

```

672 \newcommand*{\n@num}{\n@num@reg}
673 \newcommand*{\n@num@reg}{%
674     \xright@appenditem{\the\absline@num}\to\actionlines@list
675     \xright@appenditem{-1007}\to\actions@list}
676

```

`\@ref` `\@ref` marks the start of a passage, for creation of a footnote reference. It takes `\insert@count` two arguments:



- #1, the number of entries to add to `\insertlines@list` for this reference. This value, here and within `\edtext`, which computes it and writes it to the line-list file, will be stored in the count `\insert@count`.

```
677 \newcount\insert@count
```

- #2, a sequence of other line-list-file commands, executed to determine the ending line-number. (This may also include other `\@ref` commands, corresponding to uses of `\edtext` within the first argument of another instance of `\edtext`.)

`\dummy@ref` When nesting of `\@ref` commands does occur, it's necessary to temporarily redefine `\@ref` within `\@ref`, so that we're only doing one of these at a time.

```
678 \newcommand*\dummy@ref}[2]{#2}
```

`\@ref@reg` The first thing `\@ref` (i.e. `\@ref@reg`) itself does is to add the specified number of items to the `\insertlines@list` list.

```
679 \newcommand*\@ref}[2]{%
680 \@ref@reg{#1}{#2}}
681 \newcommand*\@ref@reg}[2]{%
682 \global\insert@count=#1\relax
683 \loop\ifnum\insert@count>\z@
684 \xright@appenditem{\the\absline@num}\to\insertlines@list
685 \global\advance\insert@count \m@ne
686 \repeat
```

Next, process the second argument to determine the page and line numbers for the end of this lemma. We temporarily equate `\@ref` to a different macro that just executes its argument, so that nested `\@ref` commands are just skipped this time. Some other macros need to be temporarily redefined to suppress their action.

```
687 \begingroup
688 \let\@ref=\dummy@ref
689 \let\page@action=\relax
690 \let\sub@action=\relax
691 \let\set@line@action=\relax
692 \let\@lab=\relax
693 #2
694 \global\endpage@num=\page@num
695 \global\endline@num=\line@num
696 \global\endsubline@num=\subline@num
697 \endgroup
```

Now store all the information about the location of the lemma's start and end in `\line@list`.

```
698 \xright@appenditem%
699 {\the\page@num|\the\line@num}%
700 \ifsublines@ \the\subline@num \else 0\fi}%
701 \the\endpage@num|\the\endline@num}%
702 \ifsublines@ \the\endsubline@num \else 0\fi}\to\line@list
```

Finally, execute the second argument of `\@ref` again, to perform for real all the commands within it.

```
703 #2}
704
```

## 20.6 Writing to the line-list file

We've now defined all the counters, lists, and commands involved in reading the line-list file at the start of a section. Now we'll cover the commands that `eledmac` uses within the text of a section to write commands out to the line-list.

`\linenum@out` The file will be opened on output stream `\linenum@out`.

```
705 \newwrite\linenum@out
```

```
\iffirst@linenum@out@
\first@linenum@out@true
\first@linenum@out@false
```

Once any file is opened on this stream, we keep it open forever, or else switch to another file that we keep open. The reason is that we want the output routine to write the page number for every page to this file; otherwise we'd have to write it at the start of every line. But it's not very easy for the output routine to tell whether an output stream is open or not. There's no way to test the status of a particular output stream directly, and the asynchronous nature of output routines makes the status hard to determine by other means.

We can manage pretty well by means of the `\iffirst@linenum@out@` flag; its inelegant name suggests the nature of the problem that made its creation necessary. It's set to be `true` before any `\linenum@out` file is opened. When such a file is opened for the first time, it's done using `\immediate`, so that it will at once be safe for the output routine to write to it; we then set this flag to `false`.

```
706 \newif\iffirst@linenum@out@
707 \first@linenum@out@true
```

`\line@list@stuff` The `\line@list@stuff{<file>}` macro, which is called by `\beginnumbering`, performs all the line-list operations needed at the start of a section. Its argument is the name of the line-list file.

```
708 \newcommand*\line@list@stuff}[1]{%
```

First, use the commands of the previous section to interpret the line-list file from the last run.

```
709 \read@linelist{#1}%
```

Now close the current output line-list file, if any, and open a new one. The first time we open a line-list file for output, we do it using `\immediate`, and clear the `\iffirst@linenum@out@` flag.

```
710 \iffirst@linenum@out@
711 \immediate\closeout\linenum@out
712 \global\first@linenum@out@false
713 \immediate\openout\linenum@out=#1\relax
714 \else
```

If we get here, then this is not the first line-list we've seen, so we don't open or close the files immediately.

```
715     \closeout\linenum@out
716     \openout\linenum@out=#1\relax
717 \fi}
718
```

**\new@line** The **\new@line** macro sends the **\@l** command to the line-list file, to mark the start of a new text line, and its page number.

```
719 \newcommand*{\new@line}{\write\linenum@out{\string\@l[\the\c@page][\thepage]}}
```

**\flag@start** We enclose a lemma marked by **\edtext** in **\flag@start** and **\flag@end**: these send the **\@ref** command to the line-list file. **\edtext** is responsible for setting the value of **\insert@count** appropriately; it actually gets done by the various footnote macros.

```
720 \newcommand*{\flag@start}{%
721   \edef\next{\write\linenum@out{%
722     \string\@ref[\the\insert@count] []}%
723   \next}
724 \newcommand*{\flag@end}{\write\linenum@out{[]}}
```

**\page@start** Originally the commentary was: **\page@start** writes a command to the line-list file noting the current page number; when used within an output routine, this should be called so as to place its **\write** within the box that gets shipped out, and as close to the top of that box as possible.

However, in October 2004 Alexej Krukov discovered that when processing long paragraphs that included Russian, Greek and Latin texts **eledmac** would go into an infinite loop, emitting thousands of blank pages. This was caused by being unable to find an appropriate place in the output routine. A different algorithm is now used for getting page numbers.

```
725 \newcommand*{\page@start}{}
726
```

**\startsub** **\startsub** and **\endsub** turn sub-lineation on and off, by writing appropriate instructions to the line-list file. When sub-lineation is in effect, the line number counter is frozen and the sub-line counter advances instead. If one of these commands appears in the middle of a line, it doesn't take effect until the next line; in other words, a line is counted as a line or sub-line depending on what it started out as, even if that changes in the middle.

We tinker with **\lastskip** because a command of either sort really needs to be attached to the last word preceding the change, not the first word that follows the change. This is because sub-lineation will often turn on and off in mid-line—stage directions, for example, often are mixed with dialogue in that way—and when a line is mixed we want to label it using the system that was in effect at its start. But when sub-lineation begins at the very start of a line we have a problem, if we don't put in this code.

```
727 \newcommand*{\startsub}{\dimen0\lastskip
```

```

728 \ifdim\dimen0>0pt \unskip \fi
729 \write\linenum@out{\string\sub@on}%
730 \ifdim\dimen0>0pt \hskip\dimen0 \fi}
731 \def\endsub{\dimen0\lastskip
732 \ifdim\dimen0>0pt \unskip \fi
733 \write\linenum@out{\string\sub@off}%
734 \ifdim\dimen0>0pt \hskip\dimen0 \fi}
735

\advanceline You can use \advanceline{<num>} in running text to advance the current visible
line-number by a specified value, positive or negative.
736 \newcommand*{\advanceline}[1]{\write\linenum@out{\string\@adv[#1]}}

\setline You can use \setline{<num>} in running text (i.e., within \pstart...\pend) to
set the current visible line-number to a specified positive value.
737 \newcommand*{\setline}[1]{%
738 \ifnum#1<\z@
739 \led@warn@BadSetline
740 \else
741 \write\linenum@out{\string\@set[#1]}%
742 \fi}
743

\setlinenum You can use \setlinenum{<num>} before a \pstart to set the visible line-number
to a specified positive value. It writes a \l@d@set command to the line-list file.
744 \newcommand*{\setlinenum}[1]{%
745 \ifnum#1<\z@
746 \led@warn@BadSetlinenum
747 \else
748 \write\linenum@out{\string\l@d@set[#1]}%
749 \fi}
750

\startlock You can use \startlock or \endlock in running text to start or end line number
\endlock locking at the current line. They decide whether line numbers or sub-line numbers
are affected, depending on the current state of the sub-lineation flags.
751 \newcommand*{\startlock}{\write\linenum@out{\string\lock@on}}
752 \def\endlock{\write\linenum@out{\string\lock@off}}
753

\ifl@dskipnumber In numbered text \skipnumbering will suspend the numbering for that particular
\l@dskipnumbertrue line.
\l@dskipnumberfalse 754 \newif\ifl@dskipnumber
\skipnumbering 755 \l@dskipnumberfalse
\skipnumbering@reg 756 \newcommand*{\skipnumbering}{\skipnumbering@reg}
757 \newcommand*{\skipnumbering@reg}{%
758 \write\linenum@out{\string\n@num}%
759 \advanceline{-1}}
760

```

## 21 Marking text for notes

The `\edtext` (or `\critext`) macro is used to create all footnotes and endnotes, as well as to print the portion of the main text to which a given note or notes is keyed. The idea is to have that lemma appear only once in the `.tex` file: all instances of it in the main text and in the notes are copied from that one appearance.

For convenience, I will use `\*text` when I do not need to distinguish between `\edtext` and `\critext`. The `\*text` macros take two arguments, the only difference between `\edtext` and `\critext` is how the second argument is delineated.

`\critext` requires two arguments. At any point within numbered text, you use it by saying:

```
\critext{#1}#2/
```

Similarly `\edtext` requires the same two arguments but you use it by saying:

```
\edtext{#1}{#2}
```

- `#1` is the piece of the main text being glossed; it gets added to the main text, and is also used as a lemma for notes to it.
- `#2` is a series of subsidiary macros that generate various kinds of notes. With `\critext` the `/` after `#2` *must* appear: it marks the end of the macro. (*The TeXbook*, p. 204, points out that when additional text to be matched follows the arguments like this, spaces following the macro are not skipped, which is very desirable since this macro will never be used except within text. Having an explicit terminator also helps keep things straight when nested calls to `\critext` are used.) Braces around `#2` are optional with `\critext` and required for `\edtext`.

The `\*text` macro may be used (somewhat) recursively; that is, `\*text` may be used within its own first argument. The code would be much simpler without this feature, but nested notes will commonly be necessary: it's quite likely that we'll have an explanatory note for a long passage and notes on variants for individual words within that passage. The situation we can't handle is overlapping notes that aren't nested: for example, one note covering lines 10–15, and another covering 12–18. You can handle such cases by using the `\lemma` and `\linenum` macros within `#2`: they alter the copy of the lemma and the line numbers that are passed to the notes, and hence allow you to overcome any limitations of this system, albeit with extra effort.

The recursive operation of `\*text` will fail if you try to use a copy that is called something other than `\*text`. In order to handle recursion, `\*text` needs to redefine its own definition temporarily at one point, and that doesn't work if the macro you are calling is not actually named `\*text`. There's no problem as long as `\*text` is not invoked in the first argument. If you want to call `\*text` something else, it is best to create instead a macro that expands to an invocation

of `\*text`, rather than copying `\*text` and giving it a new name; otherwise you will need to add an appropriate definition for your new macro to `\morenoexpands`.

Side effects of our line-numbering code make it impossible to use the usual footnote macros directly within a paragraph whose lines are numbered (see comments to `\do@line`, p. 79). Instead, the appropriate note-generating command is appended to the list macro `\inserts@list`, and when `\pend` completes the paragraph it inserts all the notes at the proper places.

Note that we don't provide previous-note information, although it's often wanted; your own macros must handle that. We can't do it correctly without keeping track of what kind of notes have gone past: it's not just a matter of remembering the line numbers associated with the previous invocation of `\*text`, because that might have been for a different kind of note. It is preferable for your footnote macros to store and recall this kind of information if they need it.

An example where some 'memory' of line numbers might be required is where there are several variant readings per line of text, and you do not wish the line number to be repeated for each lemma in the notes. After the first occurrence of the line number, you might want the symbol '||' instead of further occurrences, for instance. This can easily be done by a macro like `\printlines`, if it saves the last value of `\l@d@nums` that *it* saw, and then performs a simple conditional test to see whether to print a number or a '||'.

## 21.1 `\edtext` and `\critext` themselves

The various note-generating macros might want to request that commands be executed not at once, but in close connection with the start or end of the lemma. For example, footnote numbers in the text should be connected to the end of the lemma; or, instead of a single macro to create a note listing variants, you might want to use several macros in series to create individual variants, which would each add information to a private macro or token register, which in turn would be formatted and output when all of #2 for the lemma has been read.

`\end@lemmas` To accomodate this, we provide a list macro to which macros may add commands that should subsequently be executed at the end of the lemma when that lemma is added to the text of the paragraph. A macro should add its contribution to `\end@lemmas` by using `\xleft@appenditem`. (Anything that needs to be done at the *start* of the lemma may be handled using `\aftergroup`, since the commands specified within `\critext`'s second argument are executed within a group that ends just before the lemma is added to the main text.)

`\end@lemmas` is intended for the few things that need to be associated with the end of the lemma, like footnote numbers. Such numbers are not implemented in the current version, and indeed no use is currently made of `\end@lemmas` or of the `\aftergroup` trick. The general approach would be to define a macro to be used within the second argument of `\critext` that would add the appropriate command to `\end@lemmas`.

Commands that are added to this list should always take care not to do anything that adds possible line-breaks to the output; otherwise line numbering could

be thrown off.

```
761 \list@create{\end@lemmas}
```

`\dummy@text` We now need to define a number of macros that allow us to weed out nested instances of `\critext`, and other problematic macros, from our lemma. This is similar to what we did in reading the line-list file using `\dummy@ref` and various redefinitions—and that’s because nested `\critext` macros create nested `\@ref` entries in the line-list file.

Here’s a macro that takes the same arguments as `\critext` but merely returns the first argument and ignores the second.

```
762 \long\def\dummy@text#1#2/{#1}
```

`\dummy@edtext` LaTeX users are not used to delimited arguments, so I provide a `\edtext` macro as well.

```
763 \newcommand{\dummy@edtext}[2]{#1}
```

We’re going to need another macro that takes one argument and ignores it entirely. This is supplied by the LaTeX `\@gobble{<arg>}`.

`\no@expands` We need to turn off macro expansion for certain sorts of macros we’re likely to see  
`\morenoexpands` within the lemma and within the notes.

The first class is font-changing macros. We suppress expansion for them by letting them become equal to zero.<sup>23</sup> This is done because we want to pass into our notes the generic commands to change to roman or whatever, and not their expansions that will ask for a particular style at a specified size. The notes may well be in a smaller font, so the command should be expanded later, when the note’s environment is in effect.

A second sort to turn off includes a few of the accent macros. Most are not a problem: an accent that’s expanded to an `\accent` command may be harder to read but it works just the same. The ones that cause problems are: those that use alignments— $\TeX$  seems to get confused about the difference between alignment parameters and macro parameters; those that use temporary control sequences; and those that look carefully at what the current font is.

(The `\copyright` macro defined in PLAIN  $\TeX$  has this sort of problem as well, but isn’t used enough to bother with. That macro, and any other that causes trouble, will get by all right if you put a `\protect` in front of it in your file.)

We also need to eliminate all `\eledmac` macros like `\edlabel` and `\setline` that write things to auxiliary files: that writing should be done only once. And we make `\critext` itself, if it appears within its own argument, do nothing but copy its first argument.

Finally, we execute `\morenoexpands`. The version of `\morenoexpands` defined here does nothing; but you may define a version of your own when you need to add more expansion suppressions as needed with your macros. That makes it possible

---

<sup>23</sup>Since ‘control sequences equivalent to characters are not expandable’—*The TeXbook*, answer to Exercise 20.14.

to make such additions without needing to copy or modify the standard `eledmac` code. If you define your own `\morenoexpands`, you must be very careful about spaces: if the macro adds any spaces to the text when it runs, extra space will appear in the main text when `\critext` is used.

(A related problem, not addressed by these two macros, is that of characters whose category code is changed by any the macros used in the arguments to `\critext`. Since the category codes are set when the arguments are scanned, macros that depend on changing them will not work. We have most often encountered this with characters that are made ‘active’ within text in some, but not all, of the languages used within the document. One way around the problem, if it takes this form, is to ensure that those characters are *always* active; within languages that make no special use of them, their associated control sequences should simply return the proper character.)

```

764 \newcommand*{\noexpands}{%
765   \let\select@lemfont=0%
766   \let\startsub=\relax \let\endsub=\relax
767   \let\startlock=\relax \let\endlock=\relax
768   \let\edlabel=\@gobble
769   \let\setline=\@gobble \let\advanceline=\@gobble
770   \let\critext=\dummy@text
771   \let\edtext=\dummy@edtext
772   \l@dtabnoexpands
773   \morenoexpands}
774 \let\morenoexpands=\relax
775
```

`\@tag` Now, we define an empty `\@tag` command. It will be redefine by `\edtext`: its value is the first args. It will be used by the `\Xfootnote` commands.

```

776 \newcommand{\@tag}{}
777 % \end{macrocode}
778 % \end{macro}
779 % \begin{macro}{\critext}
780 % Now we begin \cs{critext} itself. The definition requires a \verb"/" after
781 % the arguments: this eliminates the possibility of problems about
782 % knowing where \verb"#2" ends. This also changes the handling of spaces
783 % following an invocation of the macro: normally such spaces are
784 % skipped, but in this case they're significant because \verb"#2" is
785 % a 'delimited parameter'. Since \cs{critext} is always used in running
786 % text, it seems more appropriate to pay attention to spaces than to
787 % skip them.
788 %
789 % When executed, \cs{critext} first ensures that we're in
790 % horizontal mode.
791 % \begin{macrocode}
792 \long\def\critext#1#2/{\leavevmode
```

`\@tag` Our normal lemma is just argument #1; but that argument could have further invocations of `\critext` within it. We get a copy of the lemma without any



`\critext` macros within it by temporarily redefining `\critext` to just copy its first argument and ignore the other, and then expand `#1` into `\@tag`, our lemma.

This is done within a group that starts here, in order to get the original `\critext` restored; within this group we've also turned off the expansion of those control sequences commonly found within text that can cause trouble for us.

```
793 \begingroup
794 \global\renewcommand{\@tag}{\no@expands #1}%
```

`\l@d@nums` Prepare more data for the benefit of note-generating macros: the line references and font specifier for this lemma go to `\l@d@nums`.

```
795 \set@line
```

`\insert@count` will be altered by the note-generating macros: it counts the number of deferred footnotes or other insertions generated by this instance of `\critext`.

```
796 \global\insert@count=0
```

Now process the note-generating macros in argument `#2` (i.e., `\Afootnote`, `\lemma`, etc.). `\ignorespaces` is here to skip over any spaces that might appear at the start of `#2`; otherwise they wind up in the main text. Footnote and other macros that are used within `#2` should all end with `\ignorespaces` as well, to skip any spaces between macros when several are used in series.

```
797 \ignorespaces #2\relax
```

Finally, we're ready to admit the first argument into the current paragraph.

It's important that we generate and output all the notes for this chunk of text *before* putting the text into the paragraph: notes that are referenced by line number should generally be tied to the start of the passage they gloss, not the end. That should all be done within the expansion of `#2` above, or in `\aftergroup` commands within that expansion.

```
798 \@ifundefined{xpg@main@language}{%if not polyglossia
799 \flag@start}%
800 {\if@RTL\flag@end\else\flag@start\fi% With polyglossia, you must track whether the language re
801 }
802 \endgroup
803 \showlemma{#1}%
```

Finally, we add any insertions that are associated with the *end* of the lemma. Footnotes that are identified by symbols rather than by where the lemma begins in the main text need to be done here, and not above.

```
804 \ifx@end@lemmas\empty \else
805 \glp@end@lemmas\to\x@lemma
806 \x@lemma
807 \global\let\x@lemma=\relax
808 \fi
809 \@ifundefined{xpg@main@language}{%if not polyglossia
810 \flag@end}%
811 {\if@RTL\flag@start\else\flag@end\fi% With polyglossia, you must track whether the language re
812 }
```

```
813 }
```

```
\edtext
```

```
814 \newcommand{\edtext}[2]{\leavevmode
815   \begingroup
816     \global\renewcommand{\@tag}{\no@expands #1}%%
817     \set@line
818     \global\insert@count=0
819     \ignorespaces #2\relax
820     \@ifundefined{xpg@main@language}{%if not polyglossia
821       \flag@start}%
822     {%ifRTL\flag@end\else\flag@start\fi% With polyglossia, you must track whether the
823       }%
824   \endgroup
825   \showlemma{#1}%
826   \ifx\end@lemmas\empty \else
827     \glp\end@lemmas\to\x@lemma
828     \x@lemma
829     \global\let\x@lemma=\relax
830   \fi
831   \@ifundefined{xpg@main@language}{%if not polyglossia
832     \flag@end}%
833   {%ifRTL\flag@start\else\flag@end\fi% With polyglossia, you must track whether the
834     }%
835 }
```

```
836
```

`\ifnumberline` The `\ifnumberline` option can be set to `FALSE` to disable line numbering.

```
837 \newif\ifnumberline
838 \numberlinetrue
```

`\set@line` The `\set@line` macro is called by `\critext` to put the line-reference field and font specifier for the current block of text into `\l@d@nums`.

One instance of `\critext` may generate several notes, or it may generate none—it’s legitimate for argument #2 to `\critext` to be empty. But `\flag@start` and `\flag@end` induce the generation of a single entry in `\line@list` during the next run, and it’s vital to also remove one and only one `\line@list` entry here.

```
839 \newcommand*{\set@line}{%
```

If no more lines are listed in `\line@list`, something’s wrong—probably just some change in the input. We set all the numbers to zeros, following an old publishing convention for numerical references that haven’t yet been resolved.

```
840   \ifx\line@list\empty
841     \global\noteschanged@true
842     \xdef\l@d@nums{000|000|000|000|000|000|\edfont@info}%
843   \else
844     \glp\line@list\to\@tempb
845     \xdef\l@d@nums{\@tempb|\edfont@info}%
```

```

846 \global\let\@tempb=\undefined
847 \fi}
848

```

`\edfont@info` The macro `\edfont@info` returns coded information about the current font.

```

849 \newcommand*{\edfont@info}{\f@encoding/\f@family/\f@series/\f@shape}
850

```

## 21.2 Substitute lemma

`\lemma` The `\lemma{<text>}` macro allows you to change the lemma that's passed on to the notes.

```

851 \newcommand*{\lemma}[1]{\global\renewcommand{\@tag}{\no@expands #1}}

```

## 21.3 Substitute line numbers

`\linenum` The `\linenum` macro can change any or all of the page and line numbers that are passed on to the notes.

As argument `\linenum` takes a set of seven parameters separated by vertical bars, in the format used internally for `\l@d@nums` (see p.55): the starting page, line, and sub-line numbers, followed by the ending page, line, and sub-line numbers, and then the font specifier for the lemma. However, you can omit any parameters you don't want to change, and you can omit a string of vertical bars at the end of the argument. Hence `\linenum{18|4|0|18|7|1|0}` is an invocation that changes all the parameters, but `\linenum{|3}` only changes the starting line number, and leaves the rest unaltered.

We use `\\` as an internal separator for the macro parameters.

```

852 \newcommand*{\linenum}[1]{%
853 \xdef\@tempa{#1|||||\\noexpand\\l@d@nums}%
854 \global\let\l@d@nums=\empty
855 \expandafter\line@set\@tempa|\\ignorespaces}

```

`\line@set` `\linenum` calls `\line@set` to do the actual work; it looks at the first number in the argument to `\linenum`, sets the corresponding value in `\l@d@nums`, and then calls itself to process the next number in the `\linenum` argument, if there are more numbers in `\l@d@nums` to process.

```

856 \def\line@set#1|#2\\#3|#4\\{%
857 \gdef\@tempb{#1}%
858 \ifx\@tempb\empty
859 \l@d@add{#3}%
860 \else
861 \l@d@add{#1}%
862 \fi
863 \gdef\@tempb{#4}%
864 \ifx\@tempb\empty\else
865 \l@d@add{|}\line@set#2\\#4\\%
866 \fi}

```

```

\l@d@add \line@set uses \l@d@add to tack numbers or vertical bars onto the right hand
end of \l@d@nums.
867 \newcommand{\l@d@add}[1]{\xdef\l@d@nums{\l@d@nums#1}}
868

```

## 22 Paragraph decomposition and reassembly

In order to be able to count the lines of text and affix line numbers, we add an extra stage of processing for each paragraph. We send the paragraph into a box register, rather than straight onto the vertical list, and when the paragraph ends we slice the paragraph into its component lines; to each line we add any notes or line numbers, add a command to write to the line-list, and then at last send the line to the vertical list. This section contains all the code for this processing.

### 22.1 Boxes, counters, \pstart and \pend

```

\raw@text Here are numbers and flags that are used internally in the course of the paragraph
\ifnumberedpar@ decomposition.
\numberedpar@true When we first form the paragraph, it goes into a box register, \raw@text,
\numberedpar@false instead of onto the current vertical list. The \ifnumberedpar@ flag will be true
\num@lines while a paragraph is being processed in that way. \num@lines will store the
\one@line number of lines in the paragraph when it's complete. When we chop it up into
\par@line lines, each line in turn goes into the \one@line register, and \par@line will be
the number of that line within the paragraph.
869 \newbox\raw@text
870 \newif\ifnumberedpar@
871 \newcount\num@lines
872 \newbox\one@line
873 \newcount\par@line

\pstart \pstart starts the paragraph by clearing the \inserts@list list and other rele-
\numberpstarttrue vant variables, and then arranges for the subsequent text to go into the \raw@text
\numberpstartfalse box. \pstart needs to appear at the start of every paragraph that's to be num-
\labelpstarttrue bered; the \autopar command below may be used to insert these commands
\labelpstartfalse automatically.
thepstart Beware: everything that occurs between \pstart and \pend is happening
within a group; definitions must be global if you want them to survive past the
end of the paragraph.
You can use the command \numberpstarttrue to insert a number on every
\pstart. To stop the numbering, you must use \numberpstartfalse. To reset
the numebering of \pstarts, insert

\setcounter{pstart}{0}

874
875 \newcounter{pstart}

```

```

876 \renewcommand{\thepstart}{\bfseries\@arabic\c@pstart}. }
877 \newif\ifnumberpstart
878 \numberpstartfalse
879 \newif\iflabelpstart
880 \labelpstartfalse
881 \newcommand*{\pstart}{
882 \if@nobreak
883 \let\@oldnobreak\@nobreaktrue
884 \else
885 \let\@oldnobreak\@nobreakfalse
886 \fi
887 \@nobreaktrue
888 \ifnumbering \else
889     \led@err@PstartNotNumbered
890     \beginnumbering
891 \fi
892 \ifnumberedpar@
893     \led@err@PstartInPstart
894 \pend
895 \fi
896 \list@clear{\inserts@list}%
897 \global\let\next@insert=\empty
898 \begingroup\normal@pars
899 \global\setbox\raw@text=\vbox\bgroup\ifautopar\else\ifnumberpstart\ifinstanza\else\ifsidepstartnum\
900 \numberedpar@true
901 \iflabelpstart\protected@edef\@currentlabel
902     {\p@pstart\thepstart}\fi
903 }

```

`\pend` `\pend` must be used to end a numbered paragraph.

```

904 \newcommand*{\pend}{\ifnumbering \else
905     \led@err@PendNotNumbered
906 \fi
907 \ifnumberedpar@ \else
908     \led@err@PendNoPstart
909 \fi

```

We set all the usual interline penalties to zero and then immediately call `\endgraf` to end the paragraph; this ensures that there'll be no large interline penalties to prevent us from slicing the paragraph into pieces. These penalties revert to the values that you set when the group for the `\vbox` ends. Then we call `\do@line` to slice a line off the top of the paragraph, add a line number and footnotes, and restore it to the page; we keep doing this until there aren't any more lines left.

```

910 \l@dzeropenalties
911 \endgraf\global\num@lines=\prevgraf\egroup
912 \global\par@line=0

```

We check if lineation is by `pstart`: in this case, we reset line number, but only in the second line of the `pstart`, to prevent some trouble. We can't reset line number

at the beginning of `\pstart` `\setline` is parsed at the end of previous `\pend`, and so, we must do it at the end of first line of `pstart`.

```

913 \csnumdef{pstartline}{0}
914 \loop\ifvbox\raw@text
915   \csnumdef{pstartline}{\pstartline+1}%
916   \do@line
917   \ifbypstart@%
918     \ifnumequal{pstartline}{1}{\setline{1}\resetprevline@}{}%
919   \fi
920 \repeat

```

Deal with any leftover notes, and then end the group that was begun in the `\pstart`.

```

921 \flush@notes
922 \endgroup
923 \ignorespaces
924 \ifnumberpstart
925   \pstartnumtrue
926 \fi
927 \@oldnobreak
928 \addtocounter{pstart}{1}}
929

```

`\l@dzzeropenalties` A macro to zero penalties for `\pend`.

```

930 \newcommand*{\l@dzzeropenalties}{%
931   \brokenpenalty \z@ \clubpenalty \z@
932   \displaywidowpenalty \z@ \interlinepenalty \z@ \predisplaypenalty \z@
933   \postdisplaypenalty \z@ \widowpenalty \z@}
934

```

`\autopar` In most cases it's only an annoyance to have to label the paragraphs to be numbered with `\pstart` and `\pend`. `\autopar` will do that automatically, allowing you to start a paragraph with its first word and no other preliminaries, and to end it with a blank line or a `\par` command. The command should be issued within a group, after `\beginnumbering` has been used to start the numbering; all paragraphs within the group will be affected.

A few situations can cause problems. One is a paragraph that begins with a begin-group character or command: `\pstart` will not get invoked until after such a group beginning is processed; as a result the character that ends the group will be mistaken for the end of the `\vbox` that `\pstart` creates, and the rest of the paragraph will not be numbered. Such paragraphs need to be started explicitly using `\indent`, `\noindent`, or `\leavevmode`—or `\pstart`, since you can still include your own `\pstart` and `\pend` commands even with `\autopar` on.

Prematurely ending the group within which `\autopar` is in effect will cause a similar problem. You must either leave a blank line or use `\par` to end the last paragraph before you end the group.

The functioning of this macro is more tricky than the usual `\everypar`: we don't want anything to go onto the vertical list at all, so we have to end the paragraph, erase any evidence that it ever existed, and start it again using `\pstart`.

We remove the paragraph-indentation box using `\lastbox` and save the width, and then skip backwards over the `\parskip` that's been added for this paragraph. Then we start again with `\pstart`, restoring the indentation that we saved, and locally change `\par` so that it'll do our `\pend` for us.

```

935 \newif\ifautopar
936 \autoparfalse
937 \newcommand*{\autopar}{
938   \ifledRcol
939     \ifnumberingR \else
940     \led@err@AutoparNotNumbered
941     \beginnumberingR
942     \fi
943   \else
944     \ifnumbering \else
945     \led@err@AutoparNotNumbered
946     \beginnumbering
947     \fi
948   \fi
949   \autopartrue
950   \everypar={\setbox0=\lastbox
951     \endgraf \vskip-\parskip
952     \pstart \noindent \kern\wd0 \ifnumberpstart\ifinstanza\else\thepstart\fi\fi
953     \let\par=\pend}%
954   \ignorespaces}

```

`\normal@pars` We also define a macro which we can rely on to turn off the `\autopar` definitions at various important places, if they are in force. We'll want to do this within a footnotes, for example.

```

955 \newcommand*{\normal@pars}{\everypar={}\let\par\endgraf}
956

```

## 22.2 Processing one line

`\do@line` The `\do@line` macro is called by `\pend` to do all the processing for a single line of text.

```

957 \newcommand*{\l@dunhbox@line}[1]{\unhbox #1}
958 \newcommand*{\do@line}{%
959   {\vbadness=10000
960     \splittopskip=\z@
961     \do@linehook
962     \l@emptyd@ta
963     \global\setbox\one@line=\vsplit\raw@text to\baselineskip}%
964     \unvbox\one@line \global\setbox\one@line=\lastbox
965     \getline@num
966     \ifnum\@lock>\@ne
967       \inserthangingsymboltrue
968     \else
969       \inserthangingsymbolfalse

```

```

970 \fi
971 \affixline@num
972 \affixstart@num
973 \hb@xt@ \linewidth{\inserthangingsymbol\l@dld@ta\add@inserts\affixside@note
974 \l@dlsn@te
975 {\ledllfill\hb@xt@ \wd\one@line{\new@line\l@dunhbox@line{\one@line}}\ledrlfill\l@drd@
976 \l@drsn@te
977 }}}}

\do@linehook A hook into \do@line.
978 \newcommand*{\do@linehook}{}

\l@emptyd@ta Nulls the \...d@ta, which may later hold line numbers. Similarly for \l@dcsnotetext
\l@dld@ta for the texts of the sidenotes.
\l@drd@ta 979 \newcommand*{\l@emptyd@ta}{%
\l@dcsnotetext 980 \gdef\l@dld@ta{}%
981 \gdef\l@drd@ta{}%
982 \gdef\l@dcsnotetext{}}
983

\l@dlsn@te Zero width boxes of the left and right side notes, together with their kerns.
\l@drsn@te 984 \newcommand{\l@dlsn@te}{%
985 \hb@xt@ \z@{\hss\box\l@dldp@rbox\kern\ledlsnotesep}}
986 \newcommand{\l@drsn@te}{%
987 \hb@xt@ \z@{\kern\ledrsnotesep\box\l@drp@rbox\hss}}
988

\ledllfill These macros are called at the left (\ledllfill) and the right (\ledrlfill) of
\ledrlfill each numbered line. The initial definitions correspond to the original code for
\do@line.
989 \newcommand*{\ledllfill}{\hfil}
990 \newcommand*{\ledrlfill}{}
991

```

## 22.3 Line and page number computation

```

\getline@num The \getline@num macro determines the page and line numbers for the line we're
about to send to the vertical list.
992 \newcommand*{\getline@num}{%
993 \global\advance\absline@num \@ne
994 \do@actions
995 \do@ballast
996 \ifnumberline
997 \ifsublines@
998 \ifnum\sub@lock<\tw@
999 \global\advance\subline@num \@ne
1000 \fi
1001 \else

```



```

1002     \ifnum\@lock<\tw@
1003         \global\advance\line@num \@ne
1004         \global\subline@num \z@
1005     \fi
1006 \fi
1007 \fi
1008 }

```

`\do@ballast` The real work in the macro above is done in `\do@actions`, but before we plunge into that, let's get `\do@ballast` out of the way. This macro looks to see if there is an action to be performed on the *next* line, and if it is going to be a page break action, `\do@ballast` decreases the count `\ballast@count` counter by the amount of `ballast`. This means, in practice, that when `\add@penalties` assigns penalties at this point, T<sub>E</sub>X will be given extra encouragement to break the page here (see p. 89).

`\ballast@count` First we set up the required counters; they are initially set to zero, and will remain  
`\c@ballast` so unless you say `\setcounter{ballast}{<some figure>}` in your document.

```

1009 \newcount\ballast@count
1010 \newcounter{ballast}
1011 \setcounter{ballast}{0}

```

And here is `\do@ballast` itself. It advances `\absline@num` within the protection of a group to make its check for what happens on the next line.

```

1012 \newcommand*{\do@ballast}{\global\ballast@count \z@
1013 \begingroup
1014     \advance\absline@num \@ne
1015     \ifnum\next@actionline=\absline@num
1016         \ifnum\next@action>-1001\relax
1017         \global\advance\ballast@count by -\c@ballast
1018     \fi
1019 \fi
1020 \endgroup}

```

`\do@actions` The `\do@actions` macro looks at the list of actions to take at particular absolute  
`\do@actions@next` line numbers, and does everything that's specified for the current line.

It may call itself recursively, and to do this efficiently (using T<sub>E</sub>X's optimization for tail recursion), we define a control-sequence called `\do@actions@next` that is always the last thing that `\do@actions` does. If there could be more actions to process for this line, `\do@actions@next` is set equal to `\do@actions`; otherwise it's just `\relax`.

```

1021 \newcommand*{\do@actions}{%
1022     \global\let\do@actions@next=\relax
1023     \ifnum\absline@num<\next@actionline\else

```

First, page number changes, which will generally be the most common actions.

If we're restarting lineation on each page, this is where it happens.

```

1024     \ifnum\next@action>-1001
1025         \global\page@num=\next@action

```

```

1026     \ifbypage@
1027         \global\line@num=\z@ \global\subline@num=\z@
1028         \resetprevline@
1029     \fi

```

Next, we handle commands that change the line-number values. (We subtract 5001 rather than 5000 here because the line number is going to be incremented automatically in `\getline@num`.)

```

1030     \else
1031         \ifnum\next@action<-4999
1032             \@l@dttempcnta=-\next@action
1033             \advance\@l@dttempcnta by -5001
1034             \ifsublines@
1035                 \global\subline@num=\@l@dttempcnta
1036             \else
1037                 \global\line@num=\@l@dttempcnta
1038             \fi

```

It's one of the fixed codes. We rescale the value in `\@l@dttempcnta` so that we can use a case statement.

```

1039         \else
1040             \@l@dttempcnta=-\next@action
1041             \advance\@l@dttempcnta by -1000
1042             \do@actions@fixedcode
1043         \fi
1044     \fi

```

Now we get information about the next action off the list, and then set `\do@actions@next` so that we'll call ourselves recursively: the next action might also be for this line.

There's no warning if we find `\actionlines@list` empty, since that will always happen near the end of the section.

```

1045     \ifx\actionlines@list\empty
1046         \gdef\next@actionline{1000000}%
1047     \else
1048         \gl@p\actionlines@list\to\next@actionline
1049         \gl@p\actions@list\to\next@action
1050         \global\let\do@actions@next=\do@actions
1051     \fi
1052 \fi

```

Make the recursive call, if necessary.

```

1053 \do@actions@next}
1054

```

`\do@actions@fixedcode` This macro handles the fixed codes for `\do@actions`. It is one big case statement.

```

1055 \newcommand*{\do@actions@fixedcode}{%
1056     \ifcase\@l@dttempcnta
1057     \or%                % 1001

```

```

1058 \global\sublines@true
1059 \or% % 1002
1060 \global\sublines@false
1061 \or% % 1003
1062 \global\@lock=\@ne
1063 \or% % 1004
1064 \ifnum\@lock=\tw@
1065 \global\@lock=\thr@@
1066 \else
1067 \global\@lock=\z@
1068 \fi
1069 \or% % 1005
1070 \global\sub@lock=\@ne
1071 \or% % 1006
1072 \ifnum\sub@lock=\tw@
1073 \global\sub@lock=\thr@@
1074 \else
1075 \global\sub@lock=\z@
1076 \fi
1077 \or% % 1007
1078 \l@dskipnumbertrue
1079 \else
1080 \led@warn@BadAction
1081 \fi}
1082
1083

```

## 22.4 Line number printing

`\affixline@num` `\affixline@num` originally took a single argument, a series of commands for printing the line just split off by `\do@line`; it put that line back on the vertical list, and added a line number if necessary. It now just puts a left line number into `\l@dld@ta` or a right line number into `\l@drd@ta` if required.

To determine whether we need to affix a line number to this line, we compute the following:

$$\begin{aligned}
 n &= \text{int}((\text{linenum} - \text{firstlinenum}) / \text{linenumincrement}) \\
 m &= \text{firstlinenum} + (n \times \text{linenumincrement})
 \end{aligned}$$

(where *int* truncates a real number to an integer). *m* will be equal to *linenum* only if we're to paste a number on here. However, the formula breaks down for the first line to number (and any before that), so we check that case separately: if `\line@num`  $\leq$  `\firstlinenum`, we compare the two directly instead of making these calculations.

We compute, in the scratch counter `\l@dttempcnta`, the number of the next line that should be printed with a number (*m* in the above discussion), and move the current line number into the counter `\l@dttempcntb` for comparison.

First, the case when we're within a sub-line range.

```

1084 \newcommand*{\affixline@num}{%

```

No number is attached if `\ifl@dskipnumber` is TRUE (and then it is set to its normal FALSE value). No number is attached if `\ifnumberline` is FALSE (the normal value is TRUE).

```

1085 \ifnumberline
1086 \ifl@dskipnumber
1087 \global\l@dskipnumberfalse
1088 \else
1089   \ifsublines@
1090     \l@dttempcntb=\subline@num
1091     \ifnum\subline@num>\c@firstsublinenum
1092       \l@dttempcnta=\subline@num
1093       \advance\l@dttempcnta by-\c@firstsublinenum
1094       \divide\l@dttempcnta by\c@sublinenumincrement
1095       \multiply\l@dttempcnta by\c@sublinenumincrement
1096       \advance\l@dttempcnta by\c@firstsublinenum
1097     \else
1098       \l@dttempcnta=\c@firstsublinenum
1099     \fi

```

That takes care of computing the values for comparison, but if line number locking is in effect we have to make a further check. If this check fails, then we disable the line-number display by setting the counters to arbitrary but unequal values.

```

1100   \ch@cksub@l@ck

```

Now the line number case, which works the same way.

```

1101   \else
1102     \l@dttempcntb=\line@num

```

Check on the `\linenumberlist` If it's `\empty` use the standard algorithm.

```

1103   \ifx\linenumberlist\empty
1104     \ifnum\line@num>\c@firstlinenum
1105       \l@dttempcnta=\line@num
1106       \advance\l@dttempcnta by-\c@firstlinenum
1107       \divide\l@dttempcnta by\c@linenumincrement
1108       \multiply\l@dttempcnta by\c@linenumincrement
1109       \advance\l@dttempcnta by\c@firstlinenum
1110     \else
1111       \l@dttempcnta=\c@firstlinenum
1112     \fi
1113   \else

```

The `\linenumberlist` wasn't `\empty`, so here's Wayne's numbering mechanism.

This takes place in TeX's mouth.

```

1114     \l@dttempcnta=\line@num
1115     \edef\rem@inder{\linenumberlist,\number\line@num,}%
1116     \edef\sc@n@list{\def\noexpand\sc@n@list
1117       ###1,\number\l@dttempcnta,###2|{\def\noexpand\rem@inder{###2}}}%
1118     \sc@n@list\expandafter\sc@n@list\rem@inder|
1119     \ifx\rem@inder\empty\advance\l@dttempcnta\@ne\fi
1120   \fi

```

A locking check for lines, just like the version for sub-line numbers above.

```
1121 \check@l@ck
1122 \fi
```

The following test is true if we need to print a line number.

```
1123 \ifnum\@l@tempcnta=\@l@tempcntb
```

If we got here, we're going to print a line number; so now we need to calculate a number that will tell us which side of the page will get the line number. We start from `\line@margin`, which asks for one side always if it's less than 2; and then if the side does depend on the page number, we simply add the page number to this side code—because the values of `\line@margin` have been devised so that this produces a number that's even for left-margin numbers and odd for right-margin numbers.

For LaTeX we have to consider two column documents as well. In this case I think we need to put the numbers at the outside of the column — the left of the first column and the right of the second. Do the twocolumn stuff before going on with the original code.

`\l@dld@ta` A left line number is stored in `\l@dld@ta` and a right one in `\l@drd@ta`.

```
\l@drd@ta 1124 \if@twocolumn
1125 \if@firstcolumn
1126 \gdef\l@dld@ta{\llap{\leftlinenum}}}%
1127 \else
1128 \gdef\l@drd@ta{\rlap{\rightlinenum}}}%
1129 \fi
1130 \else
```

Continuing the original code ...

```
1131 \@l@tempcntb=\line@margin
1132 \ifnum\@l@tempcntb>\@ne
1133 \advance\@l@tempcntb \page@num
1134 \fi
```

Now print the line (#1) with its page number.

```
1135 \ifodd\@l@tempcntb
1136 \gdef\l@drd@ta{\rlap{\rightlinenum}}}%
1137 \else
1138 \gdef\l@dld@ta{\llap{\leftlinenum}}}%
1139 \fi
1140 \fi
1141 \else
```

As no line number is to be appended, we just print the line as is.

```
1142 %% #1%
1143 \fi
```

Now fix the lock counters, if necessary. A value of 1 is advanced to 2; 3 advances to 0; other values are unchanged.

```
1144 \f@x@l@cks
```

```

1145 \fi
1146 \fi
1147 }
1148

```

`\ch@cksub@l@ck` These macros handle line number locking for `\affixline@num`. `\ch@cksub@l@ck`  
`\ch@ck@l@ck` checks subline locking. If it fails, then we disable the line-number display by setting  
`\f@x@l@cks` the counters to arbitrary but unequal values.

```

1149 \newcommand*{\ch@cksub@l@ck}{%
1150   \ifcase\sub@lock
1151     \or
1152       \ifnum\sublock@disp=\@ne
1153         \@l@tempcntb=\z@ \@l@tempcnta=\@ne
1154       \fi
1155     \or
1156       \ifnum\sublock@disp=\tw@ \else
1157         \@l@tempcntb=\z@ \@l@tempcnta=\@ne
1158       \fi
1159     \or
1160       \ifnum\sublock@disp=\z@
1161         \@l@tempcntb=\z@ \@l@tempcnta=\@ne
1162       \fi
1163   \fi}

```

Similarly for line numbers.

```

1164 \newcommand*{\ch@ck@l@ck}{%
1165   \ifcase\@lock
1166     \or
1167       \ifnum\lock@disp=\@ne
1168         \@l@tempcntb=\z@ \@l@tempcnta=\@ne
1169       \fi
1170     \or
1171       \ifnum\lock@disp=\tw@ \else
1172         \@l@tempcntb=\z@ \@l@tempcnta=\@ne
1173       \fi
1174     \or
1175       \ifnum\lock@disp=\z@
1176         \@l@tempcntb=\z@ \@l@tempcnta=\@ne
1177       \fi
1178   \fi}

```

Fix the lock counters. A value of 1 is advanced to 2; 3 advances to 0; other values are unchanged.

```

1179 \newcommand*{\f@x@l@cks}{%
1180   \ifcase\@lock
1181     \or
1182       \global\@lock=\tw@
1183     \or \or
1184       \global\@lock=\z@
1185   \fi

```

```

1186 \ifcase\sub@lock
1187 \or
1188   \global\sub@lock=\tw@
1189 \or \or
1190   \global\sub@lock=\z@
1191 \fi}
1192

```

`\pageparbreak` Because of TeX's asynchronous page breaking mechanism we can never be sure juust where it will make a break and, naturally, it has already decided exactly how it will typeset any remainder of a paragraph that crosses the break. This is disconcerting when trying to number lines by the page or put line numbers in different margins. This macro tries to force an invisible paragraph break and a page break.

```

1193 \newcommand{\pageparbreak}{\pend\newpage\pstart\noindent}
1194

```

## 22.5 Pstart number printing in side

In side, the printing of pstart number is running like the printing of line number. There is only some differences:

- The pstarts counter is upgrade in the `\pend` command. Consequently, the `\affixpstart@num` command has not to upgrade it, unlike the `\affixline@num` which upgrades the lines counter.
- To print the pstart number only at the beginning of a pstart, and not in every line, a boolean test is made. The `\pstartnum` boolean is set to TRUE at every `\pend`. It's tried in the `\leftpstartnum` and `\rightpstartnum` commands. After the try, it is set to FALSE.

```

\leftpstartnum
\rightpstartnum 1195
\ifsidepstartnum 1196 \newif\ifsidepstartnum
1197 \newcommand*{\affixpstart@num}{%
1198   \ifsidepstartnum
1199     \if@twocolumn
1200       \if@firstcolumn
1201         \gdef\l@dld@ta{\llap{{\leftpstartnum}}}%
1202       \else
1203         \gdef\l@drd@ta{\rlap{{\rightpstartnum}}}%
1204       \fi
1205     \else
1206       \@l@tempcntb=\line@margin
1207       \ifnum\@l@tempcntb>\@ne
1208         \advance\@l@tempcntb \page@num
1209       \fi
1210       \ifodd\@l@tempcntb
1211         \gdef\l@drd@ta{\rlap{{\rightpstartnum}}}%

```

```

1212         \else
1213             \gdef\l@dld@ta{\llap{{\leftpstartnum}}}%
1214         \fi
1215     \fi
1216 \fi
1217
1218 }
1219 %
1220
1221 \newif\ifpstartnum
1222 \pstartnumtrue
1223 \newcommand*{\leftpstartnum}{
1224     \ifpstartnum\thepstart
1225     \kern\linenumsep\fi
1226     \global\pstartnumfalse
1227 }
1228 \newcommand*{\rightpstartnum}{
1229     \ifpstartnum
1230     \kern\linenumsep
1231     \thepstart
1232     \fi
1233     \global\pstartnumfalse
1234 }

```

## 22.6 Add insertions to the vertical list

`\inserts@list` `\inserts@list` is the list macro that contains the inserts that we save up for one paragraph.

```
1235 \list@create{\inserts@list}
```

`\add@inserts` `\add@inserts` is the penultimate macro used by `\do@line`; it takes insertions saved in a list macro and sends them onto the vertical list.

It may call itself recursively, and to do this efficiently (using  $\text{\TeX}$ 's optimization for tail recursion), we define a control-sequence called `\add@inserts@next` that is always the last thing that `\add@inserts` does. If there could be more inserts to process for this line, `\add@inserts@next` is set equal to `\add@inserts`; otherwise it's just `\relax`.

```

1236 \newcommand*{\add@inserts}{%
1237     \global\let\add@inserts@next=\relax

```

If `\inserts@list` is empty, there aren't any more notes or insertions for this paragraph, and we needn't waste our time.

```
1238 \ifx\inserts@list\empty \else
```

The `\next@insert` macro records the number of the line that receives the next footnote or other insert; it's empty when we start out, and just after we've affixed a note or insert.

```

1239 \ifx\next@insert\empty
1240     \ifx\insertlines@list\empty

```



```

1241     \global\noteschanged@true
1242     \gdef\next@insert{100000}%
1243     \else
1244     \gl@p\insertlines@list\to\next@insert
1245     \fi
1246 \fi

```

If the next insert's for this line, tack it on (and then erase the contents of the insert macro, as it could be quite large). In that case, we also set `\add@inserts@next` so that we'll call ourself recursively: there might be another insert for this same line.

```

1247 \ifnum\next@insert=\absline@num
1248 \gl@p\inserts@list\to\next@insert
1249 \@insert
1250 \global\let\@insert=\undefined
1251 \global\let\next@insert=\empty
1252 \global\let\add@inserts@next=\add@inserts
1253 \fi
1254 \fi

```

Make the recursive call, if necessary.

```

1255 \add@inserts@next}
1256

```

## 22.7 Penalties

`\add@penalties` `\add@penalties` is the last macro used by `\do@line`. It adds up the club, widow, and interline penalties, and puts a single penalty of the appropriate size back into the paragraph; these penalties get removed by the `\vsplit` operation. `\displaywidowpenalty` and `\brokenpenalty` are not restored, since we have no easy way to find out where we should insert them.

In this code, `\num@lines` is the number of lines in the whole paragraph, and `\par@line` is the line we're working on at the moment. The count `\@l@tempcnta` is used to calculate and accumulate the penalty; it is initially set to the value of `\ballast@count`, which has been worked out in `\do@ballast` above (p.81). Finally, the penalty is checked to see that it doesn't go below `-10000`.

```

1257 \newcommand*{\add@penalties}{\@l@tempcnta=\ballast@count
1258 \ifnum\num@lines>\@ne
1259 \global\advance\par@line \@ne
1260 \ifnum\par@line=\@ne
1261 \advance\@l@tempcnta \clubpenalty
1262 \fi
1263 \@l@tempcntb=\par@line \advance\@l@tempcntb \@ne
1264 \ifnum\@l@tempcntb=\num@lines
1265 \advance\@l@tempcnta \widowpenalty
1266 \fi
1267 \ifnum\par@line<\num@lines
1268 \advance\@l@tempcnta \interlinepenalty

```

```

1269 \fi
1270 \fi
1271 \ifnum\@l@dttempcnta=\z@
1272 \relax
1273 \else
1274 \ifnum\@l@dttempcnta>-10000
1275 \penalty\@l@dttempcnta
1276 \else
1277 \penalty -10000
1278 \fi
1279 \fi}
1280

```

## 22.8 Printing leftover notes

**\flush@notes** The **\flush@notes** macro is called after the entire paragraph has been sliced up and sent on to the vertical list. If the number of notes to this paragraph has increased since the last run of **T<sub>E</sub>X**, then there can be leftover notes that haven't yet been printed. An appropriate error message will be printed elsewhere; but it's best to go ahead and print these notes somewhere, even if it's not in quite the right place. What we do is dump them all out here, so that they should be printed on the same page as the last line of the paragraph. We can hope that's not too far from the proper location, to which they'll move on the next run.

```

1281 \newcommand*{\flush@notes}{%
1282 \@xloop
1283 \ifx\inserts@list\empty \else
1284 \glp\inserts@list\to\@insert
1285 \@insert
1286 \global\let\@insert=\undefined
1287 \repeat}
1288

```

**\@xloop** **\@xloop** is a variant of the PLAIN **T<sub>E</sub>X** **\loop** macro, useful when it's hard to construct a positive test using the **T<sub>E</sub>X** **\if** commands—as in **\flush@notes** above. One says **\@xloop ... \if ... \else ... \repeat**, and the action following **\else** is repeated as long as the **\if** test fails. (This macro will work wherever the PLAIN **T<sub>E</sub>X** **\loop** is used, too, so we could just call it **\loop**; but it seems preferable not to change the definitions of any of the standard macros.)

This variant of **\loop** was introduced by Alois Kabelschacht in *TUGboat* 8 (1987), pp. 184–5.

```

1289 \def\@xloop#1\repeat{%
1290 \def\body{#1\expandafter\body\fi}%
1291 \body}
1292

```

## 23 Footnotes

The footnote macros are adapted from those in PLAIN T<sub>E</sub>X, but they differ in these respects: the outer-level commands must add other commands to a list macro rather than doing insertions immediately; there are five separate levels of the footnotes, not just one; and there are options to reformat footnotes into paragraphs or into multiple columns.

### 23.1 Fonts

Before getting into the details of formatting the notes, we set up some font macros. It is the notes that present the greatest challenge for our font-handling mechanism, because we need to be able to take fragments of our main text and print them in different forms: it is common to reduce the size, for example, without otherwise changing the fonts used.

`\select@lemmafont` `\select@lemmafont` is provided to set the right font for the lemma in a note.  
`\select@@lemmafont` This macro extracts the font specifier from the line and page number cluster, and issues the associated font-changing command, so that the lemma is printed in its original font.

```
1293 \def\select@lemmafont#1|#2|#3|#4|#5|#6|#7|{\select@@lemmafont#7|}
1294 \def\select@@lemmafont#1/#2/#3/#4|{%
1295   {\fontencoding{#1}\fontfamily{#2}\fontseries{#3}\fontshape{#4}%
1296    \selectfont}
1297
```

### 23.2 Outer-level footnote commands

`\footnoteoptions@` The `\footnoteoption@` [*side*] {*options*} {*value*} change the value of on options of Xfootnote, to switch between true and false.

```
1298 \newcommand*{\footnoteoptions@}[3][1=L,usedefault]{%
1299   \def\do##1{%
1300     \ifstrequal{#1}{L}{% In Leftside
1301       \xright@appenditem{\global\noexpand\settoggle{##1@}{#3}}\to\inserts@list% Switch toogle, in
1302       \global\advance\insert@count \@ne% Increment the left insert counter.
1303     }%
1304     {%
1305       \xright@appenditem{\global\noexpand\settoggle{##1@}{#3}}\to\inserts@listR% Switch toogle, i
1306       \global\advance\insert@countR \@ne% Increment the right insert counter insert.
1307     }%
1308   }%
1309   \notblank{#2}{\docsvlist{#2}}{}}% Parsing all options
1310 }
```

`\footnotelang@lua` `\footnotelang@lua` is called to remember the information about the language of a lemma when LuaLaTeX is used.

```
1311 \newcommand*{\footnotelang@lua}[1][1=L,usedefault]{%
1312 \ifstrequal{#1}{L}{%
```

```

1313 \xright@appenditem{{\csxdef{footnote@luatextextdir}{\the\luatextextdir}}}\to\inserts@list%
1314     \global\advance\insert@count \@ne%
1315     \xright@appenditem{{\csxdef{footnote@luatexpardir}{\the\luatexpardir}}}\to\inserts@list%
1316     \global\advance\insert@count \@ne%
1317 }%
1318 {%
1319 \xright@appenditem{{\csxdef{footnote@luatextextdir}{\the\luatextextdir}}}\to\inserts@list%
1320     \global\advance\insert@countR \@ne%
1321     \xright@appenditem{{\csxdef{footnote@luatexpardir}{\the\luatexpardir}}}\to\inserts@list%
1322     \global\advance\insert@countR \@ne%
1323 }%
1324 }
1325 % \end{macrocode}
1326 % \end{macro}
1327 % \begin{macro}{\footnotelang@poly}
1328 % \begin{macrocode}
1329 % \cs{footnotelang@poly} is called to remember the information about the language of a lemma
1330 \newcommandx*{\footnotelang@poly}[1][1=L,usedefault]{%
1331 \ifstrequal{#1}{L}{%
1332     \ifRTL%
1333         \xright@appenditem{{\csxdef{footnote@dir}{@RTLtrue}}}\to\inserts@list%Know the language
1334         \global\advance\insert@count \@ne%
1335     \else
1336         \xright@appenditem{{\csxdef{footnote@dir}{@RTLfalse}}}\to\inserts@list%Know the language
1337         \global\advance\insert@count \@ne%
1338     \fi%
1339     \xright@appenditem{{\csxdef{footnote@lang}{\csexpandonce{language}}}\to\inserts@list%
1340     \global\advance\insert@count \@ne%
1341 }%
1342 {%
1343     \ifRTL
1344         \xright@appenditem{{\csxdef{footnote@dir}{@RTLtrue}}}\to\inserts@listR%Know the language
1345         \global\advance\insert@countR \@ne%
1346     \else
1347         \xright@appenditem{{\csxdef{footnote@dir}{@RTLfalse}}}\to\inserts@listR%Know the language
1348         \global\advance\insert@countR \@ne%
1349     \fi
1350     \xright@appenditem{{\csxdef{footnote@lang}{\csexpandonce{language}}}\to\inserts@listR%
1351     \global\advance\insert@countR \@ne%
1352 }%
1353 }
1354 % \end{macrocode}
1355 % \end{macro}
1356 % \subsection{Normal footnote formatting} \label{sec:nfootformat}
1357 %
1358 % The processing of each note is done
1359 % by four principal macros: the \cs{vfootnote} macro takes the text
1360 % of the footnote and does the \cs{insert}; it calls on the
1361 % \cs{footfmt} macro to select the right fonts, print the line
1362 % number and lemma, and do any other formatting needed for that individual

```

```

1363 % note. Within the output routine, the two other macros, \cs{footstart}
1364 % and \cs{footgroup}, are called; the first prints extra vertical
1365 % space and a footnote rule, if desired; the second does any reformatting
1366 % of the whole set of the footnotes in this series for this page---such
1367 % as paragraphing or division into columns---and then sends them to the
1368 % page.
1369 %
1370 % These four macros, and the other macros and parameters shown
1371 % here, are distinguished by the 'series letter'
1372 % that indicates which set of the footnotes
1373 % we're dealing with---\texttt{A}, \texttt{B}, \texttt{C}, \texttt{D}, or \texttt{E}.
1374 % The series letter always precedes the string \verb"foot" in macro
1375 % and parameter names. Hence, for the \texttt{A} series, the four macros
1376 % are called \cs{vAfootnote}, \cs{Afootfmt}, \cs{Afootstart},
1377 % and \cs{Afootgroup}.
1378 %
1379 % \begin{macro}{\normalvfootnote}
1380 % We now begin a series of commands that do 'normal' footnote
1381 % formatting: a format much like that implemented
1382 % in \PlainTeX{}, in which each footnote
1383 % is a separate paragraph.
1384 %
1385 % \cs{normalvfootnote} takes the series letter as \verb"#1",
1386 % and the entire text of the footnote is \verb"#2". It does the
1387 % \cs{insert} for this note, calling on the \cs{footfmt} macro for
1388 % this note series to format the text of the note.
1389 % \begin{macrocode}
1390 \notbool{parapparatus@}{\newcommand*}{\newcommand}{\normalvfootnote}[2]{%
1391 \insert\csname #1footins\endcsname\bgroup
1392 \csuse{bhookXnote@#1}
1393 \csuse{Xnotefontsize@#1}
1394 \footsplitskips
1395 \spaceskip=\z@skip \xspaceskip=\z@skip
1396 \csname #1footfmt\endcsname #2[#1]\egroup}

```

`\footsplitskips` Some setup code that is common for a variety of the footnotes.

```

1397 \newcommand*{\footsplitskips}{%
1398 \interlinepenalty=\interfootnotelinepenalty
1399 \floatingpenalty=\@MM
1400 \splittopskip=\ht\strutbox \splitmaxdepth=\dp\strutbox
1401 \leftskip=\z@skip \rightskip=\z@skip}
1402

```

`\mpnormalvfootnote` And a somewhat different version for minipages.

```

1403 \notbool{parapparatus@}{\newcommand*}{\newcommand}{\mpnormalvfootnote}[2]{%
1404 \global\setbox\@nameuse{mp#1footins}\vbox{%
1405 \unvbox\@nameuse{mp#1footins}
1406 \csuse{bhookXnote@#1}
1407 \csuse{Xnotefontsize@#1}
1408 \hsize\columnwidth

```

```

1409    \@parboxrestore
1410    \color@begingroup
1411    \csname #1footfmt\endcsname #2[#1]\color@endgroup}}
1412

```

`\ledsetnormalparstuff` `\normalfootfmt` is a ‘normal’ macro to take the footnote line and page number information (see p. 55), and the desired text, and output what’s to be printed. Argument #1 contains the line and page number information and lemma font specifier; #2 is the lemma; #3 is the note’s text. This version is very rudimentary—it uses `\printlines` to print just the range of line numbers, followed by a square bracket, the lemma, and the note text; it’s intended to be copied and modified as necessary.

`\par` should always be redefined to `\endgraf` within the format macro (this is what `\normal@pars` does), to override tricky material in the main text to get the lines numbered automatically (as set up by `\autopar`, for example).

```

1413 \newcommand*\ledsetnormalparstuff{%
1414   \ifluatex%
1415     \luatextextdir\footnote@luatextextdir%
1416   \luatexpardir\footnote@luatexpardir%
1417   \fi%
1418   \csuse{\csuse{footnote@dir}}}%
1419   \normal@pars%
1420   \noindent \parfillskip \z@ \@plus 1fil}
1421
1422 \notbool{parapparatus@}{\newcommandx*{\newcommandx}{\normalfootfmt}[4][4=Z]{% 4th arg is
1423   \ledsetnormalparstuff%
1424   \hangindent=\csuse{Xhangindent@#4}
1425   \strut{\printlinefootnote{#1}{#4}}}%
1426   {\select@lemmafont#1|#2}%
1427   \iftoggle{nosep@}{\hskip\csuse{inplaceoflemmaseparator@#4}}{\ifcsemtty{lemmaseparator@#
1428     {\hskip\csuse{inplaceoflemmaseparator@#4}}}%
1429     {\nobreak\hskip\csuse{beforelemmaseparator@#4}\csuse{lemmaseparator@#4}\hskip\csuse{a
1430   }}%
1431   #3\strut\par}

```

`\endashchar` The fonts that are used for printing notes might not have the character mapping we expect: for example, the Computer Modern font that contains old-style numerals does not contain an en-dash or square brackets, and its period and comma are in odd locations. To allow use of the standard footnote macros with such fonts, we use the following macros for certain characters.

The `\endashchar` macro is simply an en-dash from the normal font and is immune to changes in the surrounding font. The same goes for the full stop. These two are used in `\printlines`. The right bracket macro is the same again; it crops up in `\normalfootfmt` and the other footnote macros for controlling the format of the footnotes.

With polyglossia, each critical note has a `\footnote@lang` which shows the language of the lemma, and which can be used to switch the bracket from right to left.

```

1432 \def\endashchar{\textnormal{--}}
1433 \newcommand*\fullstop{\textnormal{.}}
1434 \newcommand*\rbracket{\textnormal{}}
1435 \csuse{text\csuse{footnote@lang}}{%
1436 \ifluatex%
1437 \ifdefstring{\footnote@luatexttextdir}{TRT}{\thinspace[]\thinspace}}%
1438 \else%
1439 \thinspace}%
1440 \fi}%
1441 }%
1442 }
1443

```

`\printpstart` The `\printpstart` macro prints the pstart number for a note.

```

1444 \newcommand{\printpstart}[0]{%
1445   \ifl@dpairing%
1446     \ifledRcol%
1447       \thepstartR%
1448     \else%
1449       \thepstartL%
1450     \fi%
1451   \else%
1452     \thepstart%
1453   \fi%
1454 }

```

The `\printlines` macro prints the line numbers for a note—which, in the general case, is a rather complicated task. The seven parameters of the argument are the line numbers as stored in `\l@d@nums`, in the form described on page 55: the starting page, line, and sub-line numbers, followed by the ending page, line, and sub-line numbers, and then the font specifier for the lemma.

The original EDMAC code used several counters at this point, saying:

To simplify the logic, we use a lot of counters to tell us which numbers need to get printed (using 1 for yes, 0 for no, so that `\ifodd` tests for ‘yes’). The counter assignments are:

- `\@pnum` for page numbers;
- `\@ssub` for starting sub-line;
- `\@elin` for ending line;
- `\@esl` for ending sub-line; and
- `\@dash` for the dash between the starting and ending groups.

There’s no counter for the line number because it’s always printed.

LaTeX tends to use a lot of counters and packages should try and minimise the number of new ones they create. In line with this Peter Wilson have reverted to traditional booleans.

```

\ifl@d@pnum
\ifl@d@ssub 1455 \newif\ifl@d@pnum
\ifl@d@elin 1456 \l@d@pnumfalse
\ifl@d@esl 1457 \newif\ifl@d@ssub
\ifl@d@dash 1458 \l@d@ssubfalse
1459 \newif\ifl@d@elin
1460 \l@d@elinfalse
1461 \newif\ifl@d@esl
1462 \l@d@eslfalse
1463 \newif\ifl@d@dash
1464 \l@d@dashfalse

\l@d@parsefootspec \l@d@parsefootspec{<spec>}{<lemma>}{<text>} parses a footnote specification.
\l@d@p@rsefootspec <lemma> and <text> are the lemma and text respectively. <spec> is the line and
\l@d@parsedstartpage page number and lemma font specifier in \l@d@nums style format. The real work
\l@d@parsedstartline is done by \l@d@p@rsefootspec which defines macros holding the numeric values.
\l@d@parsedstartsub 1465 \newcommand*{\l@d@parsefootspec}[3]{\l@d@p@rsefootspec#1|}
\l@d@parsedendpage 1466 \def\l@d@p@rsefootspec#1|#2|#3|#4|#5|#6|#7|{%
\l@d@parsedendline 1467 \gdef\l@d@parsedstartpage{#1}%
\l@d@parsedendsub 1468 \gdef\l@d@parsedstartline{#2}%
1469 \gdef\l@d@parsedstartsub{#3}%
1470 \gdef\l@d@parsedendpage{#4}%
1471 \gdef\l@d@parsedendline{#5}%
1472 \gdef\l@d@parsedendsub{#6}%
1473 }

Initialise the several number value macros.
1474 \def\l@d@parsedstartpage{0}%
1475 \def\l@d@parsedstartline{0}%
1476 \def\l@d@parsedstartsub{0}%
1477 \def\l@d@parsedendpage{0}%
1478 \def\l@d@parsedendline{0}%
1479 \def\l@d@parsedendsub{0}%
1480

\setprintlines First of all, we print the page numbers only if: 1) we're doing the lineation by
page, and 2) the ending page number is different from the starting page number.
Just a reminder of the arguments:
\printlines #1 | #2 | #3 | #4 | #5 | #6 | #7
\printlines start-page | line | subline | end-page | line | subline | font
The macro \setprintlines does the work of deciding what numbers should
be printed. Its arguments are the same as the first 6 of \printlines.
1481 \newcommand*{\setprintlines}[6]{%
1482 \l@d@pnumfalse \l@d@dashfalse
1483 \ifbypage@
1484 \ifnum#4=#1 \else
1485 \l@d@pnumtrue
1486 \l@d@dashtrue
1487 \fi

```



```

1488 \fi
      We print the ending line number if: (1) we're printing the ending page number,
      or (2) it's different from the starting line number.
1489 \ifl@d@pnum \l@d@elintrue \else \l@d@elinfalse \fi
1490 \ifnum#2=#5 \else
1491     \l@d@elintrue
1492     \l@d@dashtrue
1493 \fi
      We print the starting sub-line if it's nonzero.
1494 \l@d@ssubfalse
1495 \ifnum#3=0 \else
1496     \l@d@ssubtrue
1497 \fi
      We print the ending sub-line if it's nonzero and: (1) it's different from the
      starting sub-line number, or (2) the ending line number is being printed.
1498 \l@d@eslfalse
1499 \ifnum#6=0 \else
1500     \ifnum#6=#3
1501         \ifl@d@elin \l@d@esltrue \else \l@d@eslfalse \fi
1502     \else
1503         \l@d@esltrue
1504         \l@d@dashtrue
1505     \fi
1506 \fi}

```

`\printlines` Now we're ready to print it all. If the lineation is by `pstart`, we print the `pstart`.

```

1507 \def\printlines#1|#2|#3|#4|#5|#6|#7|{\begingroup
1508   \setprintlines{#1}{#2}{#3}{#4}{#5}{#6}%
      One subtlety left here is when to print a period between numbers. But the only
      instance in which this is tricky is for the ending sub-line number: it could be
      coming after the starting sub-line number (in which case we want only the dash)
      or after an ending line number (in which case we need to insert a period).
1509   \ifl@d@pnum #1\fullstop\fi
1510   \linenumrep{#2}

1511   \ifl@d@ssub \fullstop \sublinenumrep{#3}\fi
1512   \ifl@d@dash \endashchar\fi
1513   \ifl@d@pnum #4\fullstop\fi
1514   \ifl@d@elin \linenumrep{#5}\fi
1515   \ifl@d@esl \ifl@d@elin \fullstop\fi \sublinenumrep{#6}\fi
1516 \endgroup}

```

`\normalfootstart` `\normalfootstart` is a standard footnote-starting macro, called in the output routine whenever there are footnotes of this series to be printed: it skips a bit and then draws a rule.

Any `footstart` macro must put onto the page something that takes up space exactly equal to the `\skip\footins` value for the associated series of notes.  $\text{\TeX}$  makes page computations based on that `\skip` value, and the output pages will suffer from spacing problems if what you add takes up a different amount of space.

But if the skip `\preXnotes@` is greater than 0 pt, it's used instead of `\skip\footins` for the first printed series.

The `\leftskip` and `\rightskip` values are both zeroed here. Similarly, these skips are cancelled in the `vfootnote` macros for the various types of notes. Strictly speaking, this is necessary only if you are using paragraphed footnotes, but we have put it here and in the other `vfootnote` macros too so that the behavior of `eledmac` in this respect is general across all footnote types (you can change this). What this means is that any `\leftskip` and `\rightskip` you specify applies to the main text, but not the footnotes. The footnotes continue to be of width `\hsize`.

```

1517 \newcommand*{\normalfootstart}[1]{%
1518     \ifdimequal{0pt}{\preXnotes@}{}%
1519     {%
1520         \iftoggle{preXnotes@}{%
1521             \togglefalse{preXnotes@}\skip\csname #1footins\endcsname=\csuse{preXnotes@}}%
1522         }%
1523     }%
1524     \vskip\skip\csname #1footins\endcsname%
1525     \leftskip0pt \rightskip0pt
1526     \csname #1footnoterule\endcsname\noindent\leavevmode}

```

`\normalfootnoterule` `\normalfootnoterule` is a standard footnote-rule macro, for use by a `footstart` macro: just the same as the PLAIN  $\text{\TeX}$  footnote rule.

```
1527 \let\normalfootnoterule=\footnoterule
```

`\normalfootgroup` `\normalfootgroup` is a standard footnote-grouping macro: it sends the contents of the footnote-insert box to the output page without alteration.

```

1528 \newcommand*{\normalfootgroup}[1]{\csuse{Xnotefontsize@#1}\noindent\csuse{txtbeforeXnotes@#1}}
1529

```

`\mpnormalfootgroup` A somewhat different version for minipages.

```

1530 \newcommand*{\mpnormalfootgroup}[1]{%
1531     \vskip\skip\@nameuse{mp#1footins}
1532     \normalcolor
1533     \@nameuse{#1footnoterule}
1534     {\csuse{Xnotefontsize@#1}\noindent\csuse{txtbeforeXnotes@#1}}
1535     \unvbox\csname mp#1footins\endcsname}}
1536

```

### 23.3 Standard footnote definitions

`\footnormal` We can now define all the parameters for the five series of footnotes; initially they use the ‘normal’ footnote formatting, which is set up by calling `\footnormal`. You can switch to another type of formatting by using `\footparagraph`, `\foottwocol`, or `\footthreecol`.



```

1554 \count\csname #1footins\endcsname=1000
1555 \dimen\csname #1footins\endcsname=\csuse{maxhXnotes@#1}
1556 \skip\csname #1footins\endcsname=\csuse{beforeXnotes@#1}

```

Now do the setup for minipage footnotes. We use as much as possible of the normal setup as we can (so the notes will have a similar layout).

```

1557 \expandafter\let\csname mpv#1footnote\endcsname=\mpnormalvfootnote
1558 \expandafter\let\csname mp#1footgroup\endcsname=\mpnormalfootgroup
1559 \count\csname mp#1footins\endcsname=1000
1560 \dimen\csname mp#1footins\endcsname=\csuse{maxhXnotes@#1}
1561 \skip\csname mp#1footins\endcsname=\csuse{beforeXnotes@#1}
1562 }
1563

```

Some of these values deserve comment: the `\dimen` setting allows 80% of the page to be occupied by notes; the `\skip` setting is deliberately flexible, since pages with lots of notes attached to many of the lines can be a bit hard for  $\text{\TeX}$  to make.

## 23.4 Paragraphed footnotes

The paragraphed-footnote option reformats all the footnotes of one series for a page into a single paragraph; this is especially appropriate when the notes are numerous and brief. The code is based on *The TeXbook*, pp.398–400, with alterations for our environment. This algorithm uses a considerable amount of save-stack space: a  $\text{\TeX}$  of ordinary size may not be able to handle more than about 100 notes of this kind on a page.

`\footparagraph` The `\footparagraph` macro sets up everything for one series of the footnotes so that they'll be paragraphed; it takes the series letter as argument. We include the setting of `\count\footins` to 1000 for the footnote series just in case you are switching to paragraphed footnotes after having columnar ones, since they change this value (see below).

It is important to call `\footparagraph` only after `\hsize` has been set for the pages that use this series of notes; otherwise  $\text{\TeX}$  will try to put too many or too few of these notes on each page. If you need to change the `\hsize` within the document, call `\footparagraph` again afterwards to take account of the new value. The argument of `\footparagraph` is the letter (A–E) denoting the series of notes to be paragraphed.

```

1564 \newcommand*{\footparagraph}[1]{%
1565   \csgdef{series@display#1}{paragraph}
1566   \expandafter\newcount\csname prevpage#1@num\endcsname
1567   \expandafter\let\csname #1footstart\endcsname=\parafootstart
1568   \expandafter\let\csname v#1footnote\endcsname=\para@vfootnote
1569   \expandafter\let\csname #1footfmt\endcsname=\parafootfmt
1570   \expandafter\let\csname #1footgroup\endcsname=\para@footgroup
1571   \count\csname #1footins\endcsname=1000
1572   \para@footsetup{#1}

```

And the extra setup for minipages.

```

1573 \expandafter\let\csname mpv#1footnote\endcsname=\mppara@vfootnote
1574 \expandafter\let\csname mp#1footgroup\endcsname=\mppara@footgroup
1575 \count\csname mp#1footins\endcsname=1000
1576 }

```

`\footfudgefiddle` For paragraphed footnotes T<sub>E</sub>X has to estimate the amount of space required. If it underestimates this then the notes may get too long and run off the bottom of the text block. `\footfudgefiddle` can be increased from its default 64 (say to 70) to increase the estimate.

```

1577 \providecommand{\footfudgefiddle}{64}

```

`\para@footsetup` `\footparagraph` calls the `\para@footsetup` macro to calculate a special fudge factor, which is the ratio of the `\baselineskip` to the `\hsize`. We assume that the proper value of `\baselineskip` for the footnotes (normally 9 pt) has been set already, in `\notefontsetup`. The argument of the macro is again the note series letter.

Peter Wilson thinks that `\columnwidth` should be used here for LaTeX, not `\hsize`. I've also included `\footfudgefiddle`.

```

1578 \newcommand*{\para@footsetup}[1]{\csuse{Xnotefontsize@#1}
1579 \dimen0=\baselineskip
1580 \multiply\dimen0 by 1024
1581 \divide \dimen0 by \columnwidth \multiply\dimen0 by \footfudgefiddle\relax
1582 \expandafter
1583 \xdef\csname #1footfudgefactor\endcsname{%
1584 \expandafter\strip@pt\dimen0 }}
1585

```

EDMAC defines `\en@number` which does the same as the LaTeX kernel `\strip@pt`, namely strip the characters `pt` from a `dimen` value. Eledmac use `\strip@pt`.

`\parafootstart` `\parafootstart` is the same as `\normalfootstart`, but we give it again to ensure that `\rightskip` and `\leftskip` are zeroed (this needs to be done before `\para@footgroup` in the output routine). You might have decided to change this for other kinds of note, but here it should stay as it is. The size of paragraphed notes is calculated using a fudge factor which in turn is based on `\hsize`. So the paragraph of notes needs to be that wide.

The argument of the macro is again the note series letter.

```

1586 \newcommand*{\parafootstart}[1]{%
1587 \rightskip=0pt \leftskip=0pt \parindent=0pt
1588 \ifdimequal{0pt}{\preXnotes@}{}%
1589 {%
1590 \iftoggle{preXnotes@}{%
1591 \togglefalse{preXnotes@}\skip\csname #1footins\endcsname=\csuse{preXnotes@}}%
1592 }%
1593 }%
1594 \vskip\skip\csname #1footins\endcsname%
1595 \csname #1footnoterule\endcsname\noindent\leavevmode}

```

`\para@vfootnote` `\para@vfootnote` is a version of the `\vfootnote` command that's used for paragraphed notes. It gets appended to the `\inserts@list` list by an outer-level footnote command like `\Afootnote`. The first argument is the note series letter; the second is the full text of the printed note itself, including line numbers, lemmata, and footnote text.

The initial model for this insertion is, of course, the `\insert\footins` definition in *The TeXbook*, p. 398. There, the footnotes are first collected up in hboxes, and these hboxes are later unpacked and stuck together into a paragraph.

However, Michael Downes has pointed out that because text in hboxes gets typeset in restricted horizontal mode, there are some undesirable side-effects if you later want to break such text across lines. In restricted horizontal mode, where  $\TeX$  does not expect to have to break lines, it does not insert certain items like `\discretionary`s. If you later unbox these hboxes and stick them together, as the *TeXbook* macros do to make these footnotes, you lose the ability to hyphenate after an explicit hyphen. This can lead to overfull `\hboxes` when you would not expect to find them, and to the uninitiated it might be very hard to see why the problem had arisen.<sup>24</sup>

Wayne Sullivan pointed out to us another subtle problem that arises from the same cause:  $\TeX$  also leaves the `\language` whatsit nodes out of the horizontal list.<sup>25</sup> So changes from one language to another will not invoke the proper hyphenation rules in such footnotes. Since critical editions often do deal with several languages, especially in a footnotes, we really ought to get this bit of code right.

To get around these problems, Wayne suggested emendations to the *TeXbook* versions of these macros which are broadly the same as those described by Michael: the central idea (also suggested by Donald Knuth in a letter to Michael) is to avoid collecting the text in an `\hbox` in the first place, but instead to collect it in a `\vbox` whose width is (virtually) infinite. The text is therefore typeset in unrestricted horizontal mode, as a paragraph consisting of a single long line. Later, there is an extra level of unboxing to be done: we have to unpack the `\vbox`, as well as the hboxes inside it, but that's not too hard. For details, we refer you to Michael's article, where the issues are clearly explained.<sup>26</sup> Michael's unboxing macro is called `\unvxh`: unvbox, extract the last line, and unhbox it.

Doing things this way has an important consequence: as Michael pointed out, you really can't put an explicit line-break into a note built in a `\vbox` the way we are doing.<sup>27</sup> In other words, be very careful not to say `\break`, or `\penalty-10000`, or any equivalent inside your para-footnote. If you do, most of the note will probably disappear. You *are* allowed to make strong suggestions; in fact `\penalty-9999` will be quite okay. Just don't make the break mandatory. We haven't applied any of Michael's solutions here, since we feel that the problem is exiguous, and `eledmac` is quite baroque enough already. If you think you are having this problem, look up Michael's solutions.

<sup>24</sup>Michael Downes, 'Line Breaking in `\unhboxed` Text', *TUGboat* **11** (1990), pp. 605–612.

<sup>25</sup>See *The TeXbook*, p. 455 (editions after January 1990).

<sup>26</sup>Wayne supplied his own macros to do this, but since they were almost identical to Michael's, we have used the latter's `\unvxh` macro since it is publicly documented.

<sup>27</sup>'Line Breaking', p. 610.

One more thing; we set `\leftskip` and `\rightskip` to zero. This has the effect of neutralizing any such skips which may apply to the main text (cf. p. 98 above). We need to do this, since `footfudgefactor` is calculated on the assumption that the notes are `\hsize` wide.

So, finally, here is the modified foot-paragraph code, which sets the footnote in vertical mode so that language and discretionary nodes are included.

```

1596 \newcommand*{\para@vfootnote}[2]{%
1597   \insert\csname #1footins\endcsname
1598   \bgroup
1599     \csuse{bhookXnote@#1}
1600     \csuse{Xnotefontsize@#1}
1601     \footplitskips
1602     \setbox0=\vbox{\hsize=\maxdimen
1603       \noindent\csname #1footfmt\endcsname#2[#1]}%
1604     \setbox0=\hbox{\unvbox0[#1]}%
1605     \dp0=0pt
1606     \ht0=\csname #1footfudgefactor\endcsname\wd0

```

Here we produce the contents of the footnote from box 0, and add a penalty of 0 between boxes in this insert.

```

1607   \if@RTL\noindent \leavevmode\fi\box0%
1608   \penalty0
1609   \egroup}
1610

```

The final penalty of 0 was added here at Wayne's suggestion to avoid a weird page-breaking problem, which occurs on those occasions when  $\text{\TeX}$  attempts to split foot paragraphs. After trying out such a split (see *The TeXbook*, p. 124),  $\text{\TeX}$  inserts a penalty of  $-10000$  here, which nearly always forces the break at the end of the whole footnote paragraph (since individual notes can't be split) even when this leads to an overfull vbox. The change above results in a penalty of 0 instead which allows, but doesn't force, such breaks. This penalty of 0 is later removed, after page breaks have been decided, by the `\unpenalty` macro in `\makehboxoffboxes`. So it does not affect how the footnote paragraphs are typeset (the notes still have a penalty of  $-10$  between them, which is added by `\parafootfmt`).

`\mppara@vfootnote` This version is for minipages.

```

1611 \newcommand*{\mppara@vfootnote}[2]{%
1612   \global\setbox\@nameuse{mp#1footins}\vbox{%
1613     \unvbox\@nameuse{mp#1footins}%
1614     \csuse{bhookXnote@#1}
1615     \csuse{Xnotefontsize@#1}
1616     \footplitskips
1617     \setbox0=\vbox{\hsize=\maxdimen
1618       \noindent\color@begingroup\csname #1footfmt\endcsname #2[#1]\color@endgroup}%
1619     \setbox0=\hbox{\unvbox0[#1]}%
1620     \dp0=\z@
1621     \ht0=\csname #1footfudgefactor\endcsname\wd0

```

```

1622     \box0
1623     \penalty0
1624 }}
1625

```

`\unvxh` Here is (modified) Michael’s definition of `\unvxh`, used above. Michael’s macro also takes care to remove some unwanted penalties and glue that `TeX` automatically attaches to the end of paragraphs. When `TeX` finishes a paragraph, it throws away any remaining glue, and then tacks on the following items: a `\penalty` of 10000, a `\parfillskip` and a `\rightskip` (*The TeXbook*, pp.99–100). `\unvxh` cancels these unwanted paragraph-final items using `\unskip` and `\unpenalty`.

```

1626 \newcommand*{\unvxh}[2][2=Z]{% 2th is optional for retro-compatibility
1627   \setbox0=\vbox{\unvbox#1%
1628     \global\setbox1=\lastbox}%
1629   \unhbox1
1630   \unskip           % remove \rightskip,
1631   \unskip           % remove \parfillskip,
1632   \unpenalty        % remove \penalty of 10000,
1633   \hskip\csuse{afternote@#2}} % but add the glue to go between the notes
1634

```

`\parafootfmt` `\parafootfmt` is `\normalfootfmt` adapted to do the special stuff needed for paragraphed notes—leaving out the `\endgraf` at the end, sticking in special penalties and kern, and leaving out the `\footstrut`. The first argument is the line and page number information, the second is the lemma, the third is the text of the footnote, and the fourth is the series (optional, for backward compatibility).

```

1635 \newcommand*{\parafootfmt}[4][4=Z]{%
1636   \insertparafootsep{#4}%
1637   \ledsetnormalparstuff%
1638   \printlinefootnote{#1}{#4}%
1639   {\select@lemmafnt#1|#2}%
1640   \iftoggle{nosep@}{\hskip\csuse{inplaceoflemmaseparator@#4}}{\ifcsemtyp{lemmaseparator@#4}}
1641     {\hskip\csuse{inplaceoflemmaseparator@#4}}%
1642     {\nobreak\hskip\csuse{beforelemmaseparator@#4}\csuse{lemmaseparator@#4}\hskip\csuse{a
1643   }}%
1644   #3\penalty-10 }

```

Note that in the above definition, the penalty of  $-10$  encourages a line break between notes, so that notes have a slight tendency to begin on new lines. The `\insertparafootsep` command is used to insert the `\parafootsep@series` between each note in the *same* page.

`\para@footgroup` This `footgroup` code is modelled on the macros in *The TeXbook*, p.399. The only difference is the `\unpenalty` in `\makehboxofhboxes`, which is there to remove the penalty of 0 which was added to the end of each footnote by `\para@vfootnote`.

The call to `\notefontsetup` is to ensure that the correct `\baselineskip` for the footnotes is used. The argument is the note series letter.

```

1645 \newcommand*{\para@footgroup}[1]{%
1646   \unvbox\csname #1footins\endcsname

```



```

1647 \makehboxofhboxes
1648 \setbox0=\hbox{{\csuse{Xnotefontsize@#1}\csuse{txtbeforeXnotes@#1}}\unhbox0 \removehboxes}%
1649 \csuse{Xnotefontsize@#1}
1650 \noindent\unhbox0\par}
1651

```

`\mppara@footgroup` The minipage version.

```

1652 \newcommand*{\mppara@footgroup}[1]{%
1653   \vskip\skip\@nameuse{mp#1footins}
1654   \normalcolor
1655   \@nameuse{#1footnoterule}%
1656   \unvbox\csname mp#1footins\endcsname
1657   \makehboxofhboxes
1658   \setbox0=\hbox{{\csuse{Xnotefontsize@#1}\csuse{txtbeforeXnotes@#1}}\unhbox0 \removehboxes}%
1659   \csuse{Xnotefontsize@#1}
1660   \noindent\unhbox0\par}}
1661

```

`\makehboxofhboxes`

```

\removehboxes 1662 \newcommand*{\makehboxofhboxes}{\setbox0=\hbox{}%
1663   \loop
1664     \unpenalty
1665     \setbox2=\lastbox
1666     \ifhbox2
1667       \setbox0=\hbox{\box2\unhbox0}%
1668     \repeat}
1669
1670 \newcommand*{\removehboxes}{\setbox0=\lastbox
1671   \ifhbox0{\removehboxes}\unhbox0 \fi}
1672

```

### 23.4.1 Insertion of the footnotes separator

The command `\insertparafootsep{<series>}` must be called at the beginning of `\parafootftm` (and like commands).

`\prevpage@num`

```

\insertparafootsep 1673 \newcommand{\insertparafootsep}[1]{%
1674   \ifnumequal{\csuse{prevpage#1@num}}{\page@num}%
1675     {\ifcsdef{prevline#1}% Be sur \prevline#1 exists.
1676       {\ifnumequal{\csuse{prevline#1}}{\line@num}%
1677         {\ifcsemt{symp\line@num}{\csuse{parafootsep@#1}}{}}%
1678         {\csuse{parafootsep@#1}}}%
1679     }%
1680     {\csuse{parafootsep@#1}}%
1681   }%
1682   {}%
1683   \global\csname prevpage#1@num\endcsname=\page@num%
1684 }

```

## 23.5 Columnar footnotes

`\rigidbalance` We will now define macros for three-column notes and two-column notes. Both sets of macros will use `\rigidbalance`, which splits a box (#1) into into a number (#2) of columns, each with a space (#3) between the top baseline and the top of the `\vbox`. The `\rigidbalance` macro is taken from *The TeXbook*, p. 397, with a slight change to the syntax of the arguments so that they don't depend on white space. Note also the extra unboxing in `\splitoff`, which allows the new `\vbox` to have its natural height as it goes into the alignment.

The LaTeX `\line` macro has no relationship to the TeX `\line`. The LaTeX equivalent is `\@@line`.

```

1685 \newcount\@k \newdimen\@h
1686 \newcommand*\rigidbalance}[3]{\setbox0=\box#1 \@k=#2 \@h=#3
1687   \@@line{\splittopskip=\@h \vbadness=\@M \hfilneg
1688   \valign{##\vfil\cr\dosplits}}}}
1689
1690 \newcommand*\dosplits{\ifnum\@k>0 \noalign{\hfil}\splitoff
1691   \global\advance\@k-1\cr\dosplits\fi}
1692
1693 \newcommand*\splitoff{\dimen0=\ht0
1694   \divide\dimen0 by\@k \advance\dimen0 by\@h
1695   \setbox2 \vsplit0 to \dimen0
1696   \unvbox2 }
1697
```

### Three columns

`\footthreecol` You say `\footthreecol{A}` to have the A series of the footnotes typeset in three columns. It is important to call this only after `\hsize` has been set for the document.

```

1698 \newcommand*\footthreecol}[1]{%
1699   \csgdef{series@display#1}{threecol}
1700   \expandafter\let\csname v#1footnote\endcsname=\threecolvfootnote
1701   \expandafter\let\csname #1footfmt\endcsname=\threecolfootfmt
1702   \expandafter\let\csname #1footgroup\endcsname=\threecolfootgroup
1703   \threecolfootsetup{#1}

```

The additional setup for minipages.

```

1704   \expandafter\let\csname mpv#1footnote\endcsname=\mpnormalvfootnote
1705   \expandafter\let\csname mp#1footgroup\endcsname=\mpthreecolfootgroup
1706   \mpthreecolfootsetup{#1}
1707 }
1708
```

The `\footstart` and `\footnoterule` macros for these notes assume the normal values (p. 97 above).

`\threecolfootsetup` The `\threecolfootsetup` macro calculates and sets some numbers for three-column footnotes.

We set the `\count` of the foot insert to 333. Each footnote can be thought of as contributing only one third of its height to the page, since the footnote insertion has been made as a long narrow column, which then gets trisected by the `\rigidbalance` routine (inside `\threecolfootgroup`). These new, shorter columns are saved in a box, and then that box is *put back* into the footnote insert, replacing the original collection of the footnotes. This new box is, therefore, only about a third of the height of the original one.

The `\dimen` value for this note series has to change in the inverse way: it needs to be three times the actual limit on the amount of space these notes are allowed to fill on the page, because when T<sub>E</sub>X is accumulating material for the page and checking that limit, it doesn't apply the `\count` scaling.

```
1709 \newcommand*{\threecolfootsetup}[1]{%
1710   \count\csname #1footins\endcsname 333
1711   \multiply\dimen\csname #1footins\endcsname \thr@@}
```

`\mpthreecolfootsetup` The setup for minipages.

```
1712 \newcommand*{\mpthreecolfootsetup}[1]{%
1713   \count\csname mp#1footins\endcsname 333
1714   \multiply\dimen\csname mp#1footins\endcsname \thr@@}
1715
```

`\threecolvfootnote` `\threecolvfootnote` is the `\vfootnote` command for three-column notes. The call to `\notefontsetup` ensures that the `\splittopskip` and `\splitmaxdepth` take their values from the right `\strutbox`: the one used in a footnotes. Note especially the importance of temporarily reducing the `\hsize` to 0.3 of its normal value. This determines the widths of the individual columns. So if the normal `\hsize` is, say, 10 cm, then each column will be  $0.3 \times 10 = 3$  cm wide, leaving a gap of 1 cm spread equally between columns (i.e., .5 cm between each).

The arguments are 1) the note series letter and 2) the full text of the note (including numbers, lemma and text).

```
1716 \notbool{parapparatus@}{\newcommand*}{\newcommand}{\threecolvfootnote}[2]{%
1717   \insert\csname #1footins\endcsname\bgroup
1718   \csuse{Xnotefontsize@#1}
1719   \footsplittskips
1720   \csname #1footfmt\endcsname #2[#1]\egroup}
```

`\threecolfootfmt` `\threecolfootfmt` is the command that formats one note. It uses `\raggedright`, which will usually be preferable with such short lines. Setting the `\parindent` to zero means that, within each individual note, the lines begin flush left.

The arguments are 1) the line numbers, 2) the lemma and 3) the text of the `-footnote` command 4) optional (for backward compatibility): the series.

```
1721 \notbool{parapparatus@}{\newcommandx*}{\newcommandx}{\threecolfootfmt}[4][4=Z]{%
1722   \normal@pars
1723   \hsize \csuse{hsizethreecol@#4}
1724   \parindent=0pt
1725   \tolerance=5000
1726   \raggedright}
```

```

1727 \hangindent=\csuse{Xhangindent@#4}
1728 \leavevmode
1729 \strut{\printlinefootnote{#1}{#4}}%
1730 {\select@lemmafont#1|#2}%
1731 \iftoggle{nosep@}{\hskip\csuse{inplaceoflemmaseparator@#4}}{\ifcseempty{lemmaseparator@#4}}
1732 {\hskip\csuse{inplaceoflemmaseparator@#4}}%
1733 {\nobreak\hskip\csuse{beforelemmaseparator@#4}\csuse{lemmaseparator@#4}\hskip\csuse{afterlemmaseparator@#4}}%
1734 }%
1735 #3\strut\par\allowbreak

```

`\threecolfootgroup` And here is the `footgroup` macro that's called within the output routine to re-group the notes into three columns. Once again, the call to `\notefontsetup` is there to ensure that it is the right `\splittopskip`—the one used in footnotes—which is used to provide the third argument for `\rigidbalance`. This third argument (`\@h`) is the `topskip` for the box containing the text of the footnotes, and does the job of making sure the top lines of the columns line up horizontally. In *The TeXbook*, p.398, Donald Knuth suggests retrieving the output of `\rigidbalance`, putting it back into the insertion box, and then printing the box. Here, we just print the `\line` which comes out of `\rigidbalance` directly, without any re-boxing.

```

1736 \newcommand*{\threecolfootgroup}[1]{\notefontsetup
1737 {\csuse{Xnotefontsize@#1}\noindent\csuse{txtbeforeXnotes@#1}}\par
1738 \splittopskip=\ht\strutbox
1739 \expandafter
1740 \rigidbalance\csname #1footins\endcsname \thr@@ \splittopskip}

```

`\mpthreecolfootgroup` The setup for minipages.

```

1741 \newcommand*{\mpthreecolfootgroup}[1]{%
1742 \vskip\skip\@nameuse{mp#1footins}
1743 \normalcolor
1744 \@nameuse{#1footnoterule}
1745 {\csuse{Xnotefontsize@#1}\noindent\csuse{txtbeforeXnotes@#1}}\par
1746 \splittopskip=\ht\strutbox
1747 \expandafter
1748 \rigidbalance\csname mp#1footins\endcsname \thr@@ \splittopskip}
1749

```

## Two columns

`\foottwocol` You say `\foottwocol{A}` to have the A series of the footnotes typeset in two columns. It is important to call this only after `\hsize` has been set for the document.

```

1750 \newcommand*{\foottwocol}[1]{%
1751 \csgdef{series@display#1}{twocol}
1752 \expandafter\let\csname v#1footnote\endcsname=\twocolvfootnote
1753 \expandafter\let\csname #1footfmt\endcsname=\twocolfootfmt
1754 \expandafter\let\csname #1footgroup\endcsname=\twocolfootgroup
1755 \twocolfootsetup{#1}

```

The additional setup for minipages.

```

1756 \expandafter\let\csname mpv#1footnote\endcsname=\mpnormalvfootnote
1757 \expandafter\let\csname mp#1footgroup\endcsname=\mptwocolfootgroup
1758 \mptwocolfootsetup{#1}
1759 }
1760

```

`\twocolfootsetup` Here is a series of macros which are very similar to their three-column counterparts.

`\twocolvfootnote` In this case, each note is assumed to contribute only a half a line of text. And the

`\twocolfootfmt` notes are set in columns giving a gap between them of one tenth of the `\hsize`.

```

\twocolfootgroup 1761 \newcommand*\twocolfootsetup}[1]{%
1762   \count\csname #1footins\endcsname 500
1763   \multiply\dimen\csname #1footins\endcsname \tw@}

1764 \notbool{parapparatus@}{\newcommand*{\twocolvfootnote}[2]{\insert\csname #1footins\endcsname
1765   \csuse{Xnotefontsize@#1}
1766   \footsplitskips
1767   \csname #1footfmt\endcsname #2[#1]\egroup}

1768 \notbool{parapparatus@}{\newcommand*\twocolfootfmt}[4][4=Z]{% 4th arg is optional, f
1769   \normal@pars
1770   \hsize \csuse{hsizetwocol@#4}
1771   \parindent=0pt
1772   \tolerance=5000
1773   \raggedright
1774   \hangindent=\csuse{Xhangindent@#4}
1775   \leavevmode
1776   \strut{\printlinefootnote{#1}{#4}}%
1777   {\select@lemmafont#1|#2}%
1778   \iftoggle{nosep@}{\hskip\csuse{inplaceoflemmaseparator@#4}}{\ifcsemtylemmaseparator@#4}%
1779     {\hskip\csuse{inplaceoflemmaseparator@#4}}%
1780     {\nobreak\hskip\csuse{beforelemmaseparator@#4}\csuse{lemmaseparator@#4}\hskip\csuse{afterlemmasep
1781     }}%
1782   #3\strut\par\allowbreak}

1783 \newcommand*\twocolfootgroup}[1]{\csuse{Xnotefontsize@#1}
1784   {\csuse{Xnotefontsize@#1}\noindent\csuse{txtbeforeXnotes@#1}}\par
1785   \splittopskip=\ht\strutbox
1786   \expandafter
1787   \rigidbalance\csname #1footins\endcsname \tw@ \splittopskip}}
1788

```

`\mptwocolfootsetup` The versions for minipages.

```

\mptwocolfootgroup 1789 \newcommand*\mptwocolfootsetup}[1]{%
1790   \count\csname mp#1footins\endcsname 500
1791   \multiply\dimen\csname mp#1footins\endcsname \tw@}

1792 \newcommand*\mptwocolfootgroup}[1]{%
1793   \vskip\skip\@nameuse{mp#1footins}
1794   \normalcolor
1795   \@nameuse{#1footnoterule}

```

```

1796   {\csuse{Xnotefontsize@#1}\noindent\csuse{txtbeforeXnotes@#1}}\par
1797   \splittopskip=\ht\strutbox
1798   \expandafter
1799   \rigidbalance\csname mp#1footins\endcsname \tw@ \splittopskip}}
1800

```

## 24 Familiar footnotes

### 24.1 Generality

The original EDMAC provided the five series of critical footnotes, and LaTeX provides a single numbered footnote. The `eledmac` package uses the EDMAC mechanism to provide a few series of numbered footnotes.

First, though, the `footmisc` package has an option whereby two or more consecutive `\footnotes` have their marks separated by commas. This seems such a useful ability that it is provided automatically by `eledmac`.

`\multiplefootnotemarker` These macros may have been defined by the `memoir` class, are provided by the `footmisc` package and perhaps by other footnote packages.

```

1801 \providecommand*\multiplefootnotemarker}{3sp}
1802 \providecommand*\multfootsep}{\textsuperscript{\normalfont,}}
1803

```

`\m@mmf@prepare` A pair of self-cancelling kerns. This may have been defined in the `memoir` class.

```

1804 \providecommand*\m@mmf@prepare}{%
1805   \kern-\multiplefootnotemarker
1806   \kern\multiplefootnotemarker\relax}

```

`\m@mmf@check` This may have been defined in the `memoir` class. If it recognises the last kern as `\multiplefootnotemarker` it typesets `\multfootsep`.

```

1807 \providecommand*\m@mmf@check}{%
1808   \ifdim\lastkern=\multiplefootnotemarker\relax
1809     \edef\x@sf{\the\spacefactor}%
1810     \unkern
1811     \multfootsep
1812     \spacefactor\x@sf\relax
1813   \fi}
1814

```

We have to modify `\@footnotetext` and `\@footnotemark`. However, if `memoir` is used the modifications have already been made.

```

1815 \ifclassloaded{memoir}{\%

```

`\@footnotetext` Add `\m@mmf@prepare` at the end of `\@footnotetext`.

```

1816 \let\l@dold@footnotetext\@footnotetext
1817 \renewcommand{\@footnotetext}[1]{%
1818   \l@dold@footnotetext{#1}%
1819   \m@mmf@prepare}

```

`\@footnotemark` Modify `\@footnotemark` to cater for adjacent `\footnotes`.

```

1820 \renewcommand*{\@footnotemark}{%
1821   \leavevmode
1822   \ifhmode
1823     \edef\x@sf{\the\spacefactor}%
1824     \m@mmf@check
1825     \nobreak
1826   \fi
1827   \@makefnmark
1828   \m@mmf@prepare
1829   \ifhmode\spacefactor\x@sf\fi
1830 \relax}

```

Finished the modifications for the non-memoir case.

```

1831 }
1832

```

`\l@doldold@footnotetext` In order to enable the regular `\footnotes` in numbered text we have to play around with its `\@footnotetext`, using different forms for when in numbered or regular text.

```

1833 \let\l@doldold@footnotetext\@footnotetext
1834 \renewcommand{\@footnotetext}[1]{%
1835   \ifnumberedpar@
1836     \edtext{}{\l@dbfnote{#1}}%
1837   \else
1838     \l@doldold@footnotetext{#1}%
1839 \fi}

```

`\l@dbfnote` `\l@dbfnote` adds the footnote to the insert list, and `\vl@dbfnote` calls the original `\@footnotetext`.

```

1840 \newcommand{\l@dbfnote}[1]{%
1841   \ifnumberedpar@
1842   \gdef\@tag{#1}%
1843   \xright@appenditem{\noexpand\vl@dbfnote{\csexpandonce{\@tag}}{\@thefnmark}}%
1844   \to\inserts@list
1845   \global\advance\insert@count \@ne
1846   \fi\ignorespaces}
1847 \newcommand{\vl@dbfnote}[2]{%
1848   \def\@thefnmark{#2}%
1849   \l@doldold@footnotetext{#1}}
1850 % \end{macrocode}
1851 % \end{macro}
1852 % \end{macro}
1853 %
1854 %
1855 %
1856 %
1857 %
1858 %

```

```

1859 % \subsection{Footnote formats}
1860 %
1861 % Some of the code for the various formats is remarkably similar to that
1862 % in section~\ref{sec:nfootformat}.
1863 %
1864 % The following macros generally set things up for the ‘standard’ footnote
1865 % format.
1866 %
1867 % \begin{macro}{\prebodyfootmark}
1868 % \begin{macro}{\postbodyfootmark}
1869 % Two convenience macros for use by \cs{...@footnotemark...} macros.
1870 % \begin{macrocode}
1871 \newcommand*{\prebodyfootmark}{%
1872 \leavevmode
1873 \ifhmode
1874 \edef\x@sf{\the\spacefactor}%
1875 \m@mmf@check
1876 \nobreak
1877 \fi}
1878 \newcommand{\postbodyfootmark}{%
1879 \m@mmf@prepare
1880 \ifhmode\spacefactor\x@sf\fi\relax}
1881
\normal@footnotemarkX \normal@footnotemarkX{<series>} sets up the typesetting of the marker at the
point where the footnote is called for.
1882 \newcommand*{\normal@footnotemarkX}[1]{%
1883 \prebodyfootmark
1884 \@nameuse{bodyfootmark#1}%
1885 \postbodyfootmark}
1886
\normalbodyfootmarkX The \normalbodyfootmarkX{<series>} really typesets the in-text marker. The
style is the normal superscript.
1887 \newcommand*{\normalbodyfootmarkX}[1]{%
1888 \hbox{\textsuperscript{\normalfont\@nameuse{@thefnmark#1}}}}

\normalvfootnoteX \normalvfootnoteX{<series>}{<text>} does the \insert for the <series> and calls
the series’ \footfmt... to format the <text>.
1889 \newcommand*{\normalvfootnoteX}[2]{%
1890 \insert\@nameuse{footins#1}\bgroup
1891 \csuse{bhooknoteX@#1}
1892 \csuse{notefontsizeX@#1}
1893 \footplitskips
1894 \spaceskip=\z@skip \xspaceskip=\z@skip
1895 \@nameuse{footfmt#1}{#1}{#2}\egroup}
1896

\mpnormalvfootnoteX The minipage version.

```



```

1897 \newcommand*{\mpnormalvfootnoteX}[2]{%
1898   \global\setbox\@nameuse{mpfootins#1}\vbox{%
1899     \unvbox\@nameuse{mpfootins#1}
1900     \csuse{bhooknoteX@#1}
1901     \csuse{notefontsizeX@#1}
1902     \hsize\columnwidth
1903     \@parboxrestore
1904     \color@begingroup
1905     \@nameuse{footfmt#1}{#1}{#2}\color@endgroup}}
1906

```

`\normalfootfmtX` `\normalfootfmtX{<series>}{<text>}` typesets the footnote text, prepended by the marker.

```

1907 \newcommand*{\normalfootfmtX}[2]{%
1908   \protected@edef\@currentlabel{%
1909     \@nameuse{@thefnmark#1}%
1910   }%
1911   \ledsetnormalparstuff
1912   \hangindent=\csuse{hangindentX@#1}%
1913   {{\csuse{notenunfontX@#1}\@nameuse{footfootmark#1}}\strut%\enspace
1914     #2\strut\par}}
1915

```

`\normalfootfootmarkX` `\normalfootfootmarkX{<series>}` is called by `\normalfootfmtX` to typeset the footnote marker in the footer before the footnote text.

```

1916 \newcommand*{\normalfootfootmarkX}[1]{%
1917   \textsuperscript{\@nameuse{@thefnmark#1}}
1918

```

`\normalfootstartX` `\normalfootstartX{<series>}` is the `<series>` footnote starting macro used in the output routine.

```

1919 \newcommand*{\normalfootstartX}[1]{%
1920   \ifdimequal{0pt}{\prenotesX@}{}%
1921   {%
1922     \iftoggle{prenotesX@}{%
1923       \togglefalse{prenotesX@} \skip\csname footins#1\endcsname=\csuse{prenotesX@}}%
1924     }%
1925   }%
1926   \vskip\skip\csname footins#1\endcsname%
1927   \leftskip=\z@
1928   \rightskip=\z@
1929   \@nameuse{footnoterule#1}}
1930

```

`\normalfootnoteruleX` The rule drawn before the footnote series group.

```

1931 \let\normalfootnoteruleX=\footnoterule
1932

```

`\normalfootgroupX` `\normalfootgroupX{<series>}` sends the contents of the `<series>` insert box to the output page without alteration.

```
1933 \newcommand*{\normalfootgroupX}[1]{%
1934   \unvbox\@nameuse{footins#1}}
1935
```

`\mpnormalfootgroupX` The minipage version.

```
1936 \newcommand*{\mpnormalfootgroupX}[1]{%
1937   \vskip\skip\@nameuse{mpfootins#1}
1938   \normalcolor
1939   \@nameuse{footnoterule#1}
1940   \unvbox\@nameuse{mpfootins#1}}
1941
```

`\normalbfnoteX`

```
1942 \newcommand{\normalbfnoteX}[2]{%
1943   \ifnumberedpar@
1944     \xright@appenditem{\noexpand\vbfnoteX{#1}{#2}}{\@nameuse{thefootnote#1}}}%
1945     \to\inserts@list
1946     \global\advance\insert@count \@ne
1947   \fi\ignorespaces}
1948
```

`\vbfnoteX`

```
1949 \newcommand{\vbfnoteX}[3]{%
1950   \@namedef{@thefnmark#1}{#3}%
1951   \@nameuse{regvfootnote#1}{#1}{#2}}
1952
```

`\vnumfootnoteX`

```
1953 \newcommand{\vnumfootnoteX}[2]{%
1954   \ifnumberedpar@
1955     \edtext{}{\normalbfnoteX{#1}{#2}}%
1956   \else
1957     \@nameuse{regvfootnote#1}{#1}{#2}%
1958   \fi}
1959
```

`\footnormalX` `\footnormalX{<series>}` initialises the settings for the `<series>` footnotes. This should always be called for each series.

```
1960 \newcommand*{\footnormalX}[1]{%
1961   \csgdef{series@displayX#1}{normalX}
1962   \expandafter\let\csname footstart#1\endcsname=\normalfootstartX
1963   \@namedef{@footnotemark#1}{\normal@footnotemarkX{#1}}
1964   \@namedef{bodyfootmark#1}{\normalbodyfootmarkX{#1}}
1965   \expandafter\let\csname regvfootnote#1\endcsname=\normalvfootnoteX
1966   \expandafter\let\csname vfootnote#1\endcsname=\vnumfootnoteX
1967   \expandafter\let\csname footfmt#1\endcsname=\normalfootfmtX
1968   \@namedef{footfootmark#1}{\normalfootfootmarkX{#1}}
```

```

1969 \expandafter\let\csname footgroup#1\endcsname=\normalfootgroupX
1970 \expandafter\let\csname footnoterule#1\endcsname=\normalfootnoteruleX
1971 \count\csname footins#1\endcsname=1000
1972 \dimen\csname footins#1\endcsname=\csuse{maxhnotesX@#1}
1973 \skip\csname footins#1\endcsname=\csuse{beforenotesX@#1}

```

Additions for minipages.

```

1974 \expandafter\let\csname mpvfootnote#1\endcsname=\mpnormalvfootnoteX
1975 \expandafter\let\csname mpfootgroup#1\endcsname=\mpnormalfootgroupX
1976 \count\csname mpfootins#1\endcsname=1000
1977 \dimen\csname mpfootins#1\endcsname=\csuse{maxhnotesX@#1}
1978 \skip\csname mpfootins#1\endcsname=\csuse{beforenotesX@#1}
1979 }
1980

```

## 24.2 Two columns footnotes

The following macros set footnotes in two columns. It is assumed that the length of each footnote is less than the column width.

```

\foottwocolX \foottwocolX{<series>}
1981 \newcommand*\foottwocolX[1]{%
1982 \csgdef{series@displayX#1}{twocol}
1983 \expandafter\let\csname regvfootnote#1\endcsname=\twocolvfootnoteX
1984 \expandafter\let\csname footfmt#1\endcsname=\twocolfootfmtX
1985 \expandafter\let\csname footgroup#1\endcsname=\twocolfootgroupX
1986 \twocolfootsetupX{#1}
1987 \expandafter\let\csname mpvfootnote#1\endcsname=\mpnormalvfootnoteX
1988 \expandafter\let\csname mpfootgroup#1\endcsname=\mptwocolfootgroupX
1989 \mptwocolfootsetupX{#1}}
1990

```

```

\twocolfootsetupX \twocolfootsetupX{<series>}
\mptwocolfootsetupX 1991 \newcommand*\twocolfootsetupX[1]{%
1992 \count\csname footins#1\endcsname 500
1993 \multiply\dimen\csname footins#1\endcsname by \tw@}
1994 \newcommand*\mptwocolfootsetupX[1]{%
1995 \count\csname mpfootins#1\endcsname 500
1996 \multiply\dimen\csname mpfootins#1\endcsname by \tw@}
1997

```

```

\twocolvfootnoteX \twocolvfootnoteX{<series>}
1998 \newcommand*\twocolvfootnoteX[2]{%
1999 \insert\csname footins#1\endcsname\bgroup
2000 \csuse{notefontsizeX@#1}
2001 \footsplitskips
2002 \spaceskip=\z@skip \xspaceskip=\z@skip
2003 \@nameuse{footfmt#1}{#1}{#2}\egroup}
2004

```

```

\twocolfootfmtX \twocolfootfmtX{<series>}
2005 \newcommand*{\twocolfootfmtX}[2]{%
2006   \protected@edef\@currentlabel{%
2007     \@nameuse{thefnmark#1}%
2008   }%
2009   \normal@pars
2010   \hangindent=\csuse{hangindentX@#1}%
2011   \hsize \csuse{hsizeX@#1}
2012   \parindent=\z@
2013   %% \parfillskip=0pt \@plus 1fil
2014   \tolerance=5000\relax
2015   \raggedright
2016   \leavevmode
2017   {\csuse{notenumfontX@#1}\@nameuse{footfootmark#1}\strut%\enspace
2018     #2\strut\par}\allowbreak}
2019

\twocolfootgroupX \twocolfootgroupX{<series>}
\mptwocolfootgroupX 2020 \newcommand*{\twocolfootgroupX}[1]{\csuse{notefontsizeX@#1}
2021   \splittopskip=\ht\strutbox
2022   \expandafter
2023   \rigidbalance\csname footins#1\endcsname \tw@ \splittopskip}}
2024 \newcommand*{\mptwocolfootgroupX}[1]{%
2025   \vskip\skip\@nameuse{mpfootins#1}
2026   \normalcolor
2027   \@nameuse{footnoterule#1}
2028   \splittopskip=\ht\strutbox
2029   \expandafter
2030   \rigidbalance\csname mpfootins#1\endcsname \tw@ \splittopskip}}
2031

```

### 24.3 Three columns footnotes

The following macros set footnotes in three columns. It is assumed that the length of each footnote is less than the column width.

```

\footthreecolX \footthreecolX{<series>}
2032 \newcommand*{\footthreecolX}[1]{%
2033   \csgdef{series@displayX#1}{threecol}
2034   \expandafter\let\csname regvfootnote#1\endcsname=\threecolvfootnoteX
2035   \expandafter\let\csname footfmt#1\endcsname=\threecolfootfmtX
2036   \expandafter\let\csname footgroup#1\endcsname=\threecolfootgroupX
2037   \threecolfootsetupX{#1}
2038   \expandafter\let\csname mpvfootnote#1\endcsname=\mpnormalvfootnoteX
2039   \expandafter\let\csname mpfootgroup#1\endcsname=\mpthreecolfootgroupX
2040   \mpthreecolfootsetupX{#1}}
2041

\threecolfootsetupX \threecolfootsetupX{<series>}
\mpthreecolfootsetupX

```

```

2042 \newcommand*{\threecolfootsetupX}[1]{%
2043   \count\csname footins#1\endcsname 333
2044   \multiply\dimen\csname footins#1\endcsname by \thr@@}
2045 \newcommand*{\mpthreecolfootsetupX}[1]{%
2046   \count\csname mpfootins#1\endcsname 333
2047   \multiply\dimen\csname mpfootins#1\endcsname by \thr@@}
2048
\threecolvfootnoteX \threecolvfootnoteX{<series>}{<text>}
2049 \newcommand*{\threecolvfootnoteX}[2]{%
2050   \insert\csname footins#1\endcsname\bgroup
2051     \csuse{notefontsizeX@#1}
2052     \footplitskips
2053     \@nameuse{footfmt#1}{#1}{#2}\egroup}
2054
\threecolfootfmtX \threecolfootfmtX{<series>}
2055 \newcommand*{\threecolfootfmtX}[2]{%
2056   \protected@edef\@currentlabel{%
2057     \@nameuse{@thefnmark#1}%
2058   }%
2059   \hangindent=\csuse{hangindentX@#1}%
2060   \normal@pars
2061   \hsize \csuse{hsizethreecolX@#1}
2062   \parindent=\z@
2063   %% \parfillskip=0pt \@plus 1fil
2064   \tolerance=5000\relax
2065   \raggedright
2066   \leavevmode
2067   {\csuse{notenumfontX@#1}\@nameuse{footfootmark#1}\strut%\enspace
2068     #2\strut\par}\allowbreak}
2069
\threecolfootgroupX \threecolfootgroupX{<series>}
\mpthreecolfootgroupX 2070 \newcommand*{\threecolfootgroupX}[1]{\csuse{notefontsizeX@#1}
2071   \splittopskip=\ht\strutbox
2072   \expandafter
2073   \rigidbalance\csname footins#1\endcsname \thr@@ \splittopskip}}
2074 \newcommand*{\mpthreecolfootgroupX}[1]{%
2075   \vskip\skip\@nameuse{mpfootins#1}
2076   \normalcolor
2077   \@nameuse{footnoterule#1}
2078   \splittopskip=\ht\strutbox
2079   \expandafter
2080   \rigidbalance\csname mpfootins#1\endcsname \thr@@ \splittopskip}}
2081

```

## 24.4 Paragraped footnotes

The following macros set footnotes as one paragraph.

`\footparagraphX \footparagraphX{<series>}`

```
2082 \newcommand*{\footparagraphX}[1]{%
2083   \csgdef{series@displayX#1}{\paragraph}
2084   \expandafter\newcount\csname prevpage#1@num\endcsname
2085   \expandafter\let\csname footstart#1\endcsname=\parafootstartX
2086   \expandafter\let\csname regvfootnote#1\endcsname=\para@vfootnoteX
2087   \expandafter\let\csname footfmt#1\endcsname=\parafootfmtX
2088   \expandafter\let\csname footgroup#1\endcsname=\para@footgroupX
2089   \expandafter\let\csname footnoterule#1\endcsname=\normalfootnoteruleX
2090   \count\csname footins#1\endcsname=1000
2091   \expandafter\let\csname mpvfootnote#1\endcsname=\mppara@vfootnoteX
2092   \expandafter\let\csname mpfootgroup#1\endcsname=\mppara@footgroupX
2093   \count\csname mpfootins#1\endcsname=1000
2094   \para@footsetupX{#1}}
2095
```

`\para@footsetupX \para@footsetupX{<series>}`

```
2096 \newcommand*{\para@footsetupX}[1]{\csuse{notefontsizeX@#1}
2097   \dimen0=\baselineskip
2098   \multiply\dimen0 by 1024
2099   \divide\dimen0 by \hsize \multiply\dimen0 by \footfudgefiddle\relax
2100   \expandafter
2101   \xdef\csname footfudgefactor#1\endcsname{%
2102     \expandafter\strip@pt\dimen0 }}
2103
```

`\parafootstartX \parafootstartX{<series>}`

```
2104 \newcommand*{\parafootstartX}[1]{%
2105   \ifdimequal{0pt}{\prenotesX@}{}%
2106   {%
2107     \iftoggle{prenotesX@}{%
2108       \togglefalse{prenotesX@}\skip\csname footins#1\endcsname=\csuse{prenotesX@}}%
2109     }%
2110   }%
2111   \vskip\skip\csname footins#1\endcsname%
2112   \leftskip=\z@
2113   \rightskip=\z@
2114   \parindent=\z@
2115   \vskip\skip\@nameuse{footins#1}%
2116   \@nameuse{footnoterule#1}}
2117
```

`\para@vfootnoteX \para@vfootnoteX{<series>}{<text>}`

```
\mppara@vfootnoteX 2118 \newcommand*{\para@vfootnoteX}[2]{%
2119   \insert\csname footins#1\endcsname
2120   \bgroup
2121     \csuse{bhooknoteX@#1}
2122     \csuse{notefontsizeX@#1}
2123     \footplitskips
```

```

2124 \setbox0=\vbox{\hsize=\maxdimen
2125 \noindent\@nameuse{footfmt#1}{#1}{#2}}%
2126 \setbox0=\hbox{\unvbox0[#1]}%
2127 \dp0=\z@
2128 \ht0=\csname footfudgefactor#1\endcsname\wd0
2129 \box0
2130 \penalty0
2131 \egroup}
2132 \newcommand*\mppara@vfootnoteX}[2]{%
2133 \global\setbox\@nameuse{mpfootins#1}\vbox{%
2134 \unvbox\@nameuse{mpfootins#1}
2135 \csuse{bhooknoteX@#1}
2136 \csuse{notefontsizeX@#1}
2137 \footplitskips
2138 \setbox0=\vbox{\hsize=\maxdimen
2139 \noindent\color@begingroup\@nameuse{footfmt#1}{#1}{#2}\color@endgroup}%
2140 \setbox0=\hbox{\unvbox0[#1]}%
2141 \dp0=\z@
2142 \ht0=\csname footfudgefactor#1\endcsname\wd0
2143 \box0
2144 \penalty0}}
2145

```

\parafootfmtX \parafootfmtX{*series*}

```

2146 \newcommand*\parafootfmtX}[2]{%
2147 \protected@edef\@currentlabel{%
2148 \@nameuse{@thefnmark#1}%
2149 }%
2150 \insertparafootsep{#1}%
2151 \ledsetnormalparstuff
2152 {\csuse{notenumfontX@#1}\csuse{notenumfontX@#1}\@nameuse{footfootmark#1}\strut%\enspace
2153 #2\penalty-10}}
2154

```

\para@footgroupX \para@footgroupX{*series*}

```

\mppara@footgroupX 2155 \newcommand*\para@footgroupX}[1]{%
2156 \unvbox\csname footins#1\endcsname
2157 \makehboxofhboxes
2158 \setbox0=\hbox{\unhbox0 \removehboxes}%
2159 \csuse{notefontsizeX@#1}
2160 \noindent\unhbox0\par}
2161 \newcommand*\mppara@footgroupX}[1]{%
2162 \vskip\skip\@nameuse{mpfootins#1}
2163 \normalcolor
2164 \@nameuse{footnoterule#1}
2165 \unvbox\csname mpfootins#1\endcsname
2166 \makehboxofhboxes
2167 \setbox0=\hbox{\unhbox0 \removehboxes}%
2168 \csuse{notefontsizeX@#1}
2169 \noindent\unhbox0\par}}

```

2170

## 24.5 Footnotes' output

`\doxtrafeeti` We have to add all the new kinds of familiar footnotes to the output routine.  
`\doreinextrafeeti` These are the class 1 feet.

```
2171 \newcommand*\doxtrafeeti{%
2172   \setbox\@outputbox \vbox{%
2173     \unvbox\@outputbox
2174     \def\do##1{\ifvoid\csuse{footins##1}\else\csuse{footstart##1}{##1}\csuse{footgroup##1}%
2175     \dolistloop{\@series}%
2176   }}
2177
2178 \newcommand{\doreinextrafeeti}{%
2179   \def\do##1{\ifvoid\csuse{footins##1}\else\insert\csuse{footins##1}{\unvbox\csuse{footins##1}%
2180   \dolistloop{\@series}%
2181   }
2182 }
```

`\addfootinsX` Juste for backward compatibility: print a warning message.

```
2183 \newcommand*\addfootinsX[1]{%
2184   \eledmac@warning{AddfootinsX is obsolete in eledmac 1.0. Use newseries instead.}%
2185   \footnormalX{#1}%
2186   \g@addto@macro{\doxtrafeeti}{%
2187     \setbox\@outputbox \vbox{%
2188       \unvbox\@outputbox
2189       \ifvoid\@nameuse{footins#1}\else
2190         \@nameuse{footstart#1}{#1}\@nameuse{footgroup#1}{#1}\fi}%as
2191   \g@addto@macro{\doreinextrafeeti}{%
2192     \ifvoid\@nameuse{footins#1}\else
2193       \insert\@nameuse{footins#1}{\unvbox\@nameuse{footins#1}}\fi}%
2194   \g@addto@macro{\l@dfambeginmini}{%
2195     \expandafter\expandafter\expandafter\let\expandafter\expandafter
2196       \csname footnote#1\endcsname \csname mpfootnote#1\endcsname}%
2197   \g@addto@macro{\l@dfamendmini}{%
2198     \ifvoid\@nameuse{mpfootins#1}\else\@nameuse{mpfootgroup#1}{#1}\fi}%
2199 }
```

## 25 Generate series

In this section, X means the name of the series (A, B etc.)

`\series` `\series` creates one more newseries. It's the public command, which just loops on the private command `\newseries@`.

```
2200 \newcommand{\newseries}[1]{%
2201   \def\do##1{\newseries@{##1}}%
2202   \docsvlist{#1}
2203 }
```



`\@series` The `\series@` macro is an etoolbox list, which contains the name of all series.

2204 `\newcommand{\@series}{}`

The command `\newseries@series` creates a new series of the footnote.

`\newseries@`

2205 `\newcommand{\newseries@}[1]{`

### 25.0.1 Test if series is still existing

2206 `\xifinlist{#1}{\@series}{\eledmac@warning{Series #1 is still existing !}}`  
 2207 `{%`

### 25.0.2 Create all commands to memorize display options

2208 `\csgdef{Xhangindent@#1}{0pt}%`  
 2209 `\csgdef{hangindentX@#1}{0pt}`  
 2210 `\csgdef{hsizetwocol@#1}{0.45 \hsize}%`  
 2211 `\csgdef{hsizetwocolX@#1}{0.45 \hsize}%`  
 2212 `\csgdef{hsizethreecol@#1}{.3 \hsize}%`  
 2213 `\csgdef{hsizethreecolX@#1}{.3 \hsize}%`  
 2214 `\csgdef{Xnotenumfont@#1}{\notenumfont}%`  
 2215 `\csgdef{Xendnotenumfont@#1}{\notenumfont}%`  
 2216 `\csgdef{notenumfontX@#1}{\notenumfont}%`  
 2217 `\csgdef{Xnotefontsize@#1}{\notefontsetup}%`  
 2218 `\csgdef{notefontsizeX@#1}{\notefontsetup}%`  
 2219 `\csgdef{Xendnotefontsize@#1}{\notefontsetup}%`  
 2220 `\csgdef{bhooknoteX@#1}{}%`  
 2221 `\csgdef{bhookXnote@#1}{}%`  
 2222 `\csgdef{bhookXendnote@#1}{}%`  
 2223 `\csgdef{boxlinenum@#1}{0pt}%`  
 2224 `\csgdef{boxsymlinenum@#1}{0pt}%`  
 2225 `\newtoggle{numberonlyfirstinline@#1}%`  
 2226 `\newtoggle{numberonlyfirstintwolines@#1}%`  
 2227 `\newtoggle{onlypstartinfootnote@#1}%`  
 2228 `\newtoggle{pstartinfootnote@#1}%`  
 2229 `\csgdef{symlinenum@#1}{\symlinenum}%`  
 2230 `\newtoggle{nonnumberinfootnote@#1}%`  
 2231 `\csgdef{beforenumberinfootnote@#1}{0pt}%`  
 2232 `\csgdef{afternumberinfootnote@#1}{0.5em}%`  
 2233 `\newtoggle{nonbreakableafternumber@#1}%`  
 2234 `\csgdef{beforesymlinenum@#1}{\csuse{beforenumberinfootnote@#1}}%`  
 2235 `\csgdef{aftersymlinenum@#1}{\csuse{afternumberinfootnote@#1}}%`  
 2236 `\csgdef{inplaceofnumber@#1}{1em}%`  
 2237 `\global\cslet{\lemmaseparator@#1}{\rbracket}%`  
 2238 `\csgdef{beforelemmaseparator@#1}{0em}%`  
 2239 `\csgdef{afterlemmaseparator@#1}{0.5em}%`  
 2240 `\csgdef{inplaceoflemmaseparator@#1}{1em}%`  
 2241 `\csgdef{afternote@#1}{1em plus.4em minus.4em}%`  
 2242 `\csgdef{parafootsep@#1}{\parafootftmsep}%`  
 2243 `\csgdef{beforeXnotes@#1}{1.2em \@plus .6em \@minus .6em}`

```

2244 \csgdef{beforenotesX@#1}{1.2em \@plus .6em \@minus .6em}
2245 \csgdef{txtbeforeXnotes@#1}{}
2246 \csgdef{maxhnotesX@#1}{\ledfootinsdim}%
2247 \csgdef{maxhXnotes@#1}{\ledfootinsdim}

```

### 25.0.3 Create inserts, needed to add notes in foot

Concerning inserts, see chapter 15 of the TeXBook by D. Knuth

```

2248
2249 \expandafter\newinsert\csname mpfootins#1\endcsname
2250 \expandafter\newinsert\csname footins#1\endcsname
2251 \expandafter\newinsert\csname #1footins\endcsname
2252 \expandafter\newinsert\csname mp#1footins\endcsname

```

### 25.0.4 Create command for critical apparatus, \Xfootnote

Note the double # in command: it's because command is made inside another command.

```

2253
2254 \global\newcommand{\parapparatus@}{\expandafter\newcommand\expandafter *}{\expandafter\newcommand}
2255 \begin{group}
2256 \newcommand{\content}{##2}%
2257 \ifnumberedpar@
2258 \ifledRcol%
2259 \ifluatex%
2260 \footnotelang@lua[R]%
2261 \fi%
2262 \ifundefined{xpg@main@language}{}%if polyglossia
2263 {\footnotelang@poly[R]}%
2264 \footnoteoptions@[R]{##1}{true}%
2265 \xright@appenditem{\noexpand\csuse{v#1footnote}}{#1}%
2266 {\l@nums}{\csexpandonce{tag}}{\csexpandonce{content}}}\to\inserts@li
2267 \footnoteoptions@[R]{##1}{false}%
2268 \global\advance\insert@countR \@ne%
2269 \else%
2270 \ifluatex%
2271 \footnotelang@lua%
2272 \fi%
2273 \ifundefined{xpg@main@language}{}%if polyglossia
2274 {\footnotelang@poly}%
2275 \footnoteoptions@{##1}{true}%
2276 \xright@appenditem{\noexpand\csuse{v#1footnote}}{#1}%
2277 {\l@nums}{\csexpandonce{tag}}{\csexpandonce{content}}}\to\inserts@li
2278 \global\advance\insert@count \@ne%
2279 \footnoteoptions@{##1}{false}%
2280 \fi
2281 \else
2282 \csuse{v#1footnote}{#1}{\{0|0|0|0|0|0|0\}}{##1}%
2283 \fi%
2284 \ignorespaces%

```

```

2285     \endgroup
2286   }

```

Set standard display and remember the display.

```

2287     \csgdef{series@display#1}{%
2288     \footnormal{#1}

```

### 25.0.5 Create tools for familiar footnotes (`\footnoteX`)

First, create the `\footnoteX` command.

```

2289
2290     \global\expandafter\newcommand\csname footnote#1\endcsname[1]{%
2291     \begingroup%
2292         \newcommand{\content}{##1}%
2293         \stepcounter{footnote#1}%
2294         \protected@csxdef{thefnmark#1}{\csuse{thefootnote#1}}%
2295         \csuse{@footnotemark#1}%
2296         \csuse{vfootnote#1}{#1}{\csexpandonce{content}}\m@mmf@prepare%
2297     \endgroup%
2298   }

```

The counters.

```

2299     \newcounter{footnote#1}
2300     \global\expandafter\renewcommand\csname thefootnote#1\endcsname{\arabic{footnote#1}}
2301 % \end{macrocode}
2302 % Don't forget to initialize series
2303 % \begin{macrocode}
2304     \csgdef{series@displayX#1}{%
2305     \footnormalX{#1}

```

### 25.0.6 The endnotes

The `\Xendnote` macro functions to write one endnote to the `.end` file. We change `\newlinechar` so that in the file every space becomes the start of a new line; this generally ensures that a long note doesn't exceed restrictions on the length of lines in files.

```

2306
2307     \global\expandafter\newcommand\csname #1endnote\endcsname[2]{\newlinechar='40
2308     \newcommand{\content}{##1}%
2309     \immediate\write\l@d@end{\expandafter\string\csname #1end\endcsname%
2310     {\ifnumberedpar@ \l@d@nums\fi}%
2311     {\ifnumberedpar@\csexpandonce{@tag}\fi}{\csexpandonce{content}}{#1}}\ignorespaces%
2312   }

```

`\Xendnote` commands called `\Xend` commands on to the endnote file; these are analogous to the various `footfmt` commands above, and they take the same arguments. When we process this file, we'll want to pick out the notes of one series and ignore all the rest. To do that, we equate the `end` command for the series

we want to `\endprint`, and leave the rest equated to `\@gobblethree`, which just skips over its three arguments.<sup>28</sup>

```

2313
2314   \global\csletcs{#1end}{\@gobblethree}
2315 %\end{macrocode}
2316 % We need to be able to modify \Eledmac's footnote macros and restore their
2317
2318   \global\csletcs{#1@@footnote}{#1footnote}
2319 % \cs{Stock series in \cs{@series}
2320 %   \begin{macrocode}
2321
2322   \listxadd{\@series}{#1}
2323 }
2324 }% End of \newseries

```

### 25.0.7 Init standards series (A,B,C,D,E,Z)

```
2325 \newseries{A,B,C,D,E,Z}
```

### 25.0.8 Some tools

`\firstseries \seriesatbegin{<s>}` changes the order of series, to put the series `<s>` at the beginning of the list. The series can be the result of a command.

```

2326 \newcommand{\seriesatbegin}[1]{
2327   \edef\series{#1}
2328   \def\new{}
2329   \listead{\new}{\series}
2330   \def\do##1{\ifcsstring{series}{##1}{\listadd{\new}{##1}}}
2331   \dolistloop{\@series}
2332   \xdef\@series{\new}
2333 }
2334 %   \end{macrocode}
2335 % \end{macro}
2336 % \begin{macro}{\seriesatend}
2337 % And \cs{seriesatend} moves the series to the end of the list.
2338 % \begin{macrocode}
2339 \newcommand{\seriesatend}[1]{
2340   \edef\series{#1}
2341   \def\new{}
2342   \def\do##1{\ifcsstring{series}{##1}{\listadd{\new}{##1}}}
2343   \dolistloop{\@series}
2344   \listead{\new}{\series}
2345   \xdef\@series{\new}
2346 }
2347 % \end{macrocode}
2348 % \end{macro}
2349 % \subsection{Display}

```

---

<sup>28</sup>Christophe Hebeisen ([christophe.hebeisen@a3.epfl.ch](mailto:christophe.hebeisen@a3.epfl.ch)) emailed on 2003/11/05 to say he had found that `\@gobblethree` was also defined in the `amsfonts` package.

```

2350 % \changes{v1.0}{2012/09/15}{New generic commands to customize footnote display.}
2351 % \subsubsection{Options}
2352 % \begin{macro}{\settoggle@series}
2353 % \changes{v1.1}{2012/09/25}{\cs{settoggle@series} switch the global value of the toggle, not only th
2354 % \cs{settoggle@series}\cs{series}{toggle}{value} is a generic command to switch one toggle for one s
2355 % \begin{macrocode}
2356 \newcommand{\settoggle@series}[3]{%
2357   \def\do##1{\global\settoggle{#2@##1}{#3}}
2358   \ifstrempy{#1}{%
2359     \dolistloop{\@series}%
2360   }%
2361   {%
2362     \docsvlist{#1}%
2363   }%
2364 }

```

`\setcommand@series` `\setcommand@series{<series>}{<command>}{<value>}` is a generic command to change one command for one series.

```

2365 \newcommandx{\setcommand@series}[4][4]{%
2366   \def\do##1{
2367     \csgdef{#2@##1}{#3}
2368     \ifstrequal{#4}{reload}{\csuse{foot\csuse{series@display##1}}{##1}}{}}
2369   \ifstrempy{#1}{%
2370     \dolistloop{\@series}%
2371   }%
2372   {%
2373     \docsvlist{#1}%
2374   }%
2375 }%

```

`\newhookcommand@series` `\newhookcommand@series\command` names is a generic command to add new commands for new commands hook, like `\hsizetwocol`.

```

2376 \newcommand{\newhookcommand@series}[1]{%
2377   \global\expandafter\newcommand\expandafter*\csname #1\endcsname[2][\csuse{setcommand@series}{##1}]
2378 }
2379 \newhookcommand@series{Xhangindent}
2380
2381 \newhookcommand@series{hangindentX}
2382
2383 \newhookcommand@series{hsizetwocol}
2384
2385 \newhookcommand@series{hsizethreecol}
2386
2387 \newhookcommand@series{hsizetwocolX}
2388
2389 \newhookcommand@series{hsizethreecolX}
2390
2391 \newhookcommand@series{Xnotenumfont}
2392

```

```

2393 \newhookcommand@series{notenumfontX}
2394
2395 \newhookcommand@series{Xendnotenumfont}
2396
2397 \newhookcommand@series{bhooknoteX}
2398
2399 \newhookcommand@series{bhookXnote}
2400
2401 \newhookcommand@series{bhookXendnote}
2402
2403 \newhookcommand@series{Xnotefontsize}
2404
2405 \newhookcommand@series{notefontsizeX}
2406
2407 \newhookcommand@series{Xendnotefontsize}
2408
2409 \newhookcommand@series{boxlinenum}
2410
2411 \newhookcommand@series{boxsymlinenum}
2412
2413 \newhookcommand@series{parafootsep}
2414
2415 \newhookcommand@series{symlinenum}
2416
2417 \newhookcommand@series{beforenumberinfootnote}
2418
2419 \newhookcommand@series{afternumberinfootnote}
2420
2421 \newhookcommand@series{beforeasymlinenum}
2422
2423 \newhookcommand@series{afterasymlinenum}
2424
2425 \newhookcommand@series{inplaceofnumber}
2426
2427 \newhookcommand@series{lemmaseparator}
2428
2429 \newhookcommand@series{beforelemmaseparator}
2430
2431 \newhookcommand@series{afterlemmaseparator}
2432
2433 \newhookcommand@series{inplaceoflemmaseparator}
2434
2435 \newhookcommand@series{afternote}
2436
2437 \newhookcommand@series{txtbeforeXnotes}
2438

```

`\newhookcommand@series@reload` `\newhookcommand@series@reload` does the same thing as `\newhookcommand@series` but the commands created by this macro also reload the series displaying (normal,

paragraph, twocol)

```

2439 \newcommand{\newhookcommand@series@reload}[1]{%
2440   \global\expandafter\newcommand\expandafter*\csname #1\endcsname[2][1]{%
2441     \csuse{setcommand@series}{##1}{#1}{##2}[reload]
2442   }%
2443 }
2444 \newhookcommand@series@reload{beforeXnotes}
2445
2446 \newhookcommand@series@reload{beforenotesX}
2447
2448 \newhookcommand@series@reload{maxhnotesX}
2449
2450 \newhookcommand@series@reload{maxhXnotes}
2451 % \end{macrocode}
2452 % \end{macro}
2453 % \begin{macro}{\newhooktoggle@series}
2454 %\cs{newhooktoggle@series}\cs{command names} is a generic command to add new commands for new toggle
2455 %   \begin{macrocode}
2456 \newcommand{\newhooktoggle@series}[1]{%
2457   \global\expandafter\newcommandx\expandafter*\csname #1\endcsname[2][1,2={true},usedefault]{\settoggle{#1}{#2}}
2458 }
2459 \newhooktoggle@series{numberonlyfirstinline}
2460 \newhooktoggle@series{numberonlyfirstintwolines}
2461 \newhooktoggle@series{nonumberinfootnote}
2462 \newhooktoggle@series{pstartinfootnote}
2463 \newhooktoggle@series{onlypstartinfootnote}
2464 \newhooktoggle@series{nonbreakableafternumber}

```

### 25.0.9 Old commands, kept for backward compatibility

The next commands are kept for ascendant compatibily, but should'nt be used anymore.

```

\notenumfont
\notefontsetup 2465 \newcommand*\notenumfont{\normalfont}
\ifledplinenum 2466 \newcommand*\notefontsetup{\footnotesize}
\symplinenum 2467 \newif\ifledplinenum
2468   \ledplinenumtrue
2469 \newcommand*\symplinenum{}

```

### 25.0.10 Hooks for a particular footnote

`\nonum@` `\nonum@` toggle is used to disable line number printing in a particular footnote.

```
2470 \newtoggle{\nonum@}
```

`\nosep@` `\nonum@` toggle is used to disable the lemma separator in a particular footnote.

```
2471 \newtoggle{\nosep@}
```

### 25.0.11 Alias

`\nolemmaseparator` `\nolemmaseparator[<series>]` is just an alias for `\lemmaseparator[<series>]{}`.

```
2472 \newcommand*{\nolemmaseparator}[1][1]{\lemmaseparator[#1]{}}
```

`\interparanoteglue` The `\ipn@skip` skip and `\interparanoteglue` command are kept for backward compatibility, but should not be used anymore.

```
2473 \newskip\ipn@skip
```

```
2474 \newcommand*{\interparanoteglue}[1]{%
```

```
2475     {\notefontsetup\global\ipn@skip=#1 \relax}}
```

```
2476 \interparanoteglue{1em plus.4em minus.4em}
```

`\parafootftmsep` The `\parafootftmsep` macro is kept for backward compatibility. It is default value of `\parafootsep@series`.

```
2477 \newcommand{\parafootftmsep}{}%
```

### 25.0.12 Line number printing

`\printlinefootnote` The `\printlinefootnote` macro is called in each `\<type>footfmt` command. It controls whether the line number is printed or not, according to the previous options. Its first argument is the information about lines, its second is the series of the footnote.

```
2478 \newcommand{\printlinefootnote}[2]{%
```

```
2479     \def\extractline@##1|##2|##3|##4|##5|##6|##7|{##2}%
```

```
2480     \def\extractsubline@##1|##2|##3|##4|##5|##6|##7|{##3}%
```

```
2481     \def\extractendline@##1|##2|##3|##4|##5|##6|##7|{##5}%
```

```
2482     \def\extractendsubline@##1|##2|##3|##4|##5|##6|##7|{##6}%
```

```
2483     \iftoggle{numberonlyfirstintwolines@#2}{%
```

```
2484         \edef\lineinfo@{\extractline@ #1| - \extractsubline@ #1| - \extractendline@ #1| - \
```

```
2485         }%
```

```
2486         {%
```

```
2487         \edef\lineinfo@{\extractline@ #1| - \extractsubline@ #1|}%
```

```
2488         }%
```

```
2489     \iftoggle{nonum@}{%Try if the line number must printed for this specific not (by default
```

```
2490     \hspace{\csuse{inplaceofnumber@#2}}}%
```

```
2491     }%
```

```
2492     {%
```

```
2493     {%
```

```
2494         \iftoggle{nonumberinfofootnote@#2}%Try if the line number must printed (by default
```

```
2495         {%
```

```
2496         \hspace{\csuse{inplaceofnumber@#2}}}%
```

```
2497         }%
```

```
2498         {%
```

```
2499             {\iftoggle{numberonlyfirstinline@#2}% If for this series the line number must
```

```
2500             {%
```

```
2501                 \ifcsdef{prevline#2}%
```

```
2502                 {%Be sure the \prevline exists.
```

```
2503                 \ifcsequal{prevline#2}{\lineinfo@}%Try it
```

```
2504                 {%
```



```

2505 \ifcempty{symlinenumber@#2}% Try if a symbol is define
2506 {%
2507 \hspace{\csuse{inplaceofnumber@#2}}%
2508 }%
2509 {\hspace{\csuse{beforenumberinfootnote@#2}}\csuse{Xnotenumfont@#2}}%
2510 \ifdimequal{\csuse{boxsymlinenumber@#2}}{0pt}%
2511 {\csuse{symlinenumber@#2}}%
2512 {\hbox to \csuse{boxsymlinenumber@#2}{\csuse{symlinenumber@#2}\hfill}}%
2513 \hspace{\csuse{aftersymlinenumber@#2}}}%
2514 }%
2515 {%
2516 \hspace{\csuse{beforenumberinfootnote@#2}}\csuse{Xnotenumfont@#2}}%
2517 \ifdimequal{\csuse{boxsymlinenumber@#2}}{0pt}{%
2518 \iftoggle{pstartinfootnote@#2}{\printpstart}{}%
2519 \printlines#1}%
2520 {%
2521 \hbox to \csuse{boxsymlinenumber@#2}{%
2522 \iftoggle{pstartinfootnote@#2}{\printpstart}{}%
2523 \iftoggle{onlypstartinfootnote@#2}{\printlines#1}}%
2524 \hfill}%
2525 }%
2526 \iftoggle{nonbreakableafternumber@#2}{\nobreak}{\hspace{\csuse{afternumberinfootnote@#2}}}%
2527 }%
2528 }%
2529 {%
2530 \hspace{\csuse{beforenumberinfootnote@#2}}\csuse{Xnotenumfont@#2}}%
2531 \ifdimequal{\csuse{boxsymlinenumber@#2}}{0pt}{%
2532 \iftoggle{pstartinfootnote@#2}{\printpstart}{}%
2533 \iftoggle{onlypstartinfootnote@#2}{\printlines#1}}%
2534 {%
2535 \hbox to \csuse{boxsymlinenumber@#2}{%
2536 \iftoggle{pstartinfootnote@#2}{\printpstart}{}%
2537 \iftoggle{onlypstartinfootnote@#2}{\printlines#1}}%
2538 \hfill}%
2539 }%
2540 \iftoggle{nonbreakableafternumber@#2}{\nobreak}{\hspace{\csuse{afternumberinfootnote@#2}}}%
2541 }%
2542 }%
2543 {%
2544 \hspace{\csuse{beforenumberinfootnote@#2}}\csuse{Xnotenumfont@#2}}%
2545 \ifdimequal{\csuse{boxsymlinenumber@#2}}{0pt}{%
2546 \iftoggle{pstartinfootnote@#2}{\printpstart}{}%
2547 \iftoggle{onlypstartinfootnote@#2}{\printlines#1}}%
2548 }%
2549 {%
2550 \hbox to \csuse{boxsymlinenumber@#2}{%
2551 \iftoggle{pstartinfootnote@#2}{\printpstart}{}%
2552 \iftoggle{onlypstartinfootnote@#2}{\printlines#1}}%
2553 \hfill}%
2554 }%

```

```

2555         \iftoggle{nonbreakableafternumber@#2}{\nobreak}{\hspace{\csuse{afternumber:
2556         }%
2557         \csxdef{prevline#2}{\lineinfo@}%
2558         }%
2559     }%
2560 }%
2561 }%
2562 }

```

## 26 Output routine

Now we begin the output routine and associated things.

`\pageno` `\pageno` is a page number, starting at 1, and `\advancepageno` increments the number.

```

2563 \countdef\pageno=0 \pageno=1
2564 \newcommand*{\advancepageno}{\ifnum\pageno<\z@ \global\advance\pageno\m@ne
2565   \else\global\advance\pageno\@ne\fi}
2566

```

The next portion is probably the trickiest part of moving from TeX to LaTeX. The original code is below, but we need something very different.

This is a new output routine, with changes to handle printing all our footnotes. Those changes have not been added directly, but are in macros that get called here: that should make it easier to see what would need to be taken over to a different output routine. We continue to use the `\pagebody`, `\makeheadline`, `\makefootline`, and `\dosupereject` macros of PLAIN TeX; for those macros, and the original version of `\output`, see *The TeXbook*, p. 364.

```

\output{\edmac@output}
\def\edmac@output{\shipout\vbox{\normal@pars
  \vbox{\makeheadline\pagebody\makefootline}%
}%
\advancepageno
\ifnum\outputpenalty>-\@MM\else\dosupereject\fi}

\def\pagecontents{\page@start
\ifvoid\topins\else\unvbox\topins\fi
\dimen@=\dp\@cclv \unvbox\@cclv % open up \box255
\do@feet
\ifrggedbottom \kern-\dimen@ \vfil \fi}

```

`\do@feet` ships out all the footnotes. Standard EDMAC has only five feet, but there is nothing in principal to prevent you from creating an arachnoid or centipedal edition; straightforward modifications of EDMAC are all that's required. However, the myriapedal edition is ruled out by eTeX limitations: the number of insertion classes is limited to  $2^{16}$ .

With luck we might only have to change `\@makecol` and `\@reinserts`. The kernel definition of these, and perhaps some other things, is:

```
\gdef \@makecol {%
  \ifvoid\footins
    \setbox\@outputbox \box\@cclv
  \else
    \setbox\@outputbox \vbox {%
      \boxmaxdepth \@maxdepth
      \@tempdima\dp\@cclv
      \unvbox \@cclv
      \vskip \skip\footins
      \color@begingroup
      \normalcolor
      \footnoterule
      \unvbox \footins
      \color@endgroup
    }%
  \fi
  \xdef\@freelist{\@freelist\@midlist}%
  \global \let \@midlist \@empty
  \@combinefloats
  \ifvbox\@kludgeins
    \@makespecialcolbox
  \else
    \setbox\@outputbox \vbox to\@colht {%
      \@texttop
      \dimen@ \dp\@outputbox
      \unvbox\@outputbox
      \vskip -\dimen@
      \@textbottom
    }%
  \fi
  \global \maxdepth \@maxdepth
}

\gdef \@reinserts{%
  \ifvoid\footins\else\insert\footins{\unvbox\footins}\fi
  \ifvbox\@kludgeins\insert\@kludgeins{\unvbox\@kludgeins}\fi
}
```

Now we start actually changing things.

```
\m@m@makecolfloats These macros are defined in the memoir class and form part of the definition of
  \m@m@makecoltext \@makecol.
\m@m@makecolintro 2567 \providecommand{\m@m@makecolfloats}{%
  2568   \xdef\@freelist{\@freelist\@midlist}%
  2569   \global \let \@midlist \@empty
  2570   \@combinefloats}
```

```

2571 \providecommand{\m@m@makecoltext}{%
2572   \ifvbox\@kludgeins
2573     \@makespecialcolbox
2574   \else
2575     \setbox\@outputbox \vbox to\@colht {%
2576       \@texttop
2577       \dimen@ \dp\@outputbox
2578       \unvbox\@outputbox
2579       \vskip -\dimen@
2580       \@textbottom}%
2581   \fi}
2582 \providecommand{\m@m@makecolintro}{%
2583
```

`\l@d@makecol` This is a partitioned version of the ‘standard’ `\@makecol`, with the initial code put into another macro.

```

2584 \gdef\l@d@makecol{%
2585   \l@ddofootinsert
2586   \m@m@makecolfloats
2587   \m@m@makecoltext
2588   \global \maxdepth \@maxdepth}
2589
```

`\l@ddofootinsert` This macro essentially holds the initial portion of the kernel `\@makecol` code.

```

2590 \newcommand*{\l@ddofootinsert}{%
2591   %% \page@start
2592   \ifvoid\footins
2593     \setbox\@outputbox \box\@ccclv
2594   \else
2595     \setbox\@outputbox \vbox {%
2596       \boxmaxdepth \@maxdepth
2597       \@tempdima \dp\@ccclv
2598       \unvbox \@ccclv
2599       \vskip \skip\footins
2600       \color@begingroup
2601         \normalcolor
2602         \footnoterule
2603         \unvbox \footins
2604       \color@endgroup
2605     }%
2606   \fi
```

That’s the end of the copy of the kernel code. We finally call a macro to handle all the additional EDMAC feet.

```

2607   \l@ddoxtrafeet
2608 }
2609
```

`\doxtrafeet` `\doxtrafeet` is the code extending `\@makecol` to cater for the extra `eledmac` feet. We have two classes of extra footnotes. We order the footnote inserts so that

the regular footnotes are first, then class 1 (familiar footnotes) and finally class 2 (critical footnotes).

```
2610 \newcommand*{\l@ddoxtrafeet}{%
2611   \doxtrafeeti
2612   \doxtrafeetii}
2613
```

`\doxtrafeetii` `\doxtrafeetii` is the code extending `\@makecol` to cater for the extra critical feet (class 2 feet). NOTE: the code is likely to be ‘featurefull’.

```
2614 \newcommand*{\doxtrafeetii}{%
2615   \setbox\@outputbox \vbox{%
2616     \unvbox\@outputbox
2617     \@opxtrafeetii}}
```

`\@opxtrafeetii` The extra critical feet to be added to the output.

```
2618 \newcommand*{\@opxtrafeetii}{%
2619   \def\do##1{\ifvoid\csuse{##1footins}\else\csuse{##1footstart}{##1}\csuse{##1footgroup}{##1}\fi}
2620   \dolistloop{\@series}}
```

`\l@ddodoreinextrafeet` `\l@ddodoreinextrafeet` is the code for catering for the extra footnotes within `\@reinserts`. The implementation may well have to change. We use the same classes and ordering as in `\l@ddoxtrafeet`.

```
2621 \newcommand*{\l@ddodoreinextrafeet}{%
2622   \doreinextrafeeti
2623   \doreinextrafeetii}
2624
```

`\doreinextrafeetii` `\doreinextrafeetii` is the code for catering for the class 2 extra critical footnotes within `\@reinserts`. The implementation may well have to change.

```
2625 \newcommand*{\doreinextrafeetii}{%
2626   \def\do##1{\ifvoid\csuse{##1footins}\else\insert\csuse{##1footins}{\unvbox\csuse{##1footins}}\fi}
2627   \dolistloop{\@series}
2628 }
2629
```

`\l@d@reinserts` And here is the modified version of `\@reinserts`.

```
2630 \gdef \l@d@reinserts{%
2631   \ifvoid\footins\else\insert\footins{\unvbox\footins}\fi
2632   \l@ddodoreinextrafeet
2633   \ifvbox\@kludgeins\insert\@kludgeins{\unvbox\@kludgeins}\fi
2634 }
2635
```

The memoir class does not use the ‘standard’ versions of `\@makecol` and `\@reinserts`, due to its sidebar insert. We had better add that code if memoir is used. (It can be awkward dealing with `\if` code within `\if` code, so don’t use `\ifl@dmemoir` here.)

```
2636 \ifclassloaded{memoir}{%
```

memoir is loaded so we use memoir's built in hooks.

```
2637 \g@addto@macro{\m@mdoextrafeet}{\l@ddoxtrafeet}%
2638 \g@addto@macro{\m@mdodoreinextrafeet}{\l@ddodoreinextrafeet}%
2639 }{%
```

memoir has not been loaded, so redefine @makecol and @reinserts.

```
2640 \gdef\@makecol{\l@d@makecol}%
2641 \gdef\@reinserts{\l@d@reinserts}%
2642 }
2643
```

\addfootins \addfootins is for backward compatibility, but should'nt be used anymore.

```
2644 \newcommand*{\addfootins}[1]{%
2645   \eledmac@warning{addfootins is deprecated, use newseries instead}
2646   \footnormal{#1}
2647   \g@addto@macro{\@opxtrafeetii}{%
2648     \ifvoid\@nameuse{#1footins}\else
2649       \@nameuse{#1footstart{#1}}\@nameuse{#1footgroup}{#1}\fi}
2650   \g@addto@macro{\doreinextrafeetii}{%
2651     \ifvoid\@nameuse{#1footins}\else
2652       \insert\@nameuse{#1footins}{\unvbox\@nameuse{#1footins}}\fi}
2653   \g@addto@macro{\l@d@dedbeginmini}{%
2654     \expandafter\let\csname #1footnote\endcsname = \@nameuse{mp#1footnote}}
2655   \g@addto@macro{\l@d@dedendmini}{%
2656     \ifvoid\@nameuse{mp#1footins}\else\@nameuse{mpfootgroup#1{#1}}\fi}
2657 }
```

It turns out that \@doclearpage also needs modifying.

\if@led@nofoot We have to check if there are any leftover feet. \@led@extranofeet is a hook for  
 \@led@extranofeet handling further footnotes.

```
2658 \newif\if@led@nofoot
2659 \newcommand*{\@led@extranofeet}{}
2660
```

```
2661 \@ifclassloaded{memoir}{%
```

If the memoir class is loaded we hook into its modified \@doclearpage.

\@mem@extranofeet

```
2662 \g@addto@macro{\@mem@extranofeet}{%
2663   \def\do#1{\ifvoid\csuse{#1footins}\else\@mem@nofootfalse\fi%
2664     \ifvoid\csuse{footins#1}\else\@mem@nofootfalse\fi%
2665   }
2666   \dolistloop{\@series}%
2667   \@led@extranofeet}
2668 }{%
```

As memoir is not loaded we have to do it all here.

```

\@led@testifnofoot
\@doclearpage 2669 \newcommand*{\@led@testifnofoot}{%
2670   \@led@nofoottrue
2671   \ifvoid\footins\else\@led@nofootfalse\fi
2672   \def\do##1{\ifvoid\csuse{##1footins}\else\@led@nofootfalse\fi%
2673   \ifvoid\csuse{footins##1}\else\@led@nofootfalse\fi}%
2674   \dolistloop{\@series}
2675   \@led@extranofeet}
2676
2677 \renewcommand{\@doclearpage}{%
2678   \@led@testifnofoot
2679   \if@led@nofoot
2680     \setbox\@tempboxa\vsplit\@cclv to\z@ \unvbox\@tempboxa
2681     \setbox\@tempboxa\box\@cclv
2682     \xdef\@deferlist{\@toplist\@botlist\@deferlist}%
2683     \global \let \@toplist \@empty
2684     \global \let \@botlist \@empty
2685     \global \@colroom \@colht
2686     \ifx \@currlist\@empty
2687       \else
2688         \@latexerr{Float(s) lost}\@ehb
2689         \global \let \@currlist \@empty
2690       \fi
2691       \@makefcolumn\@deferlist
2692       \@whilesw\if@fcolmade \fi{\@opcol\@makefcolumn\@deferlist}%
2693       \if@twocolumn
2694         \if@firstcolumn
2695           \xdef\@dbldeferlist{\@dbltoplist\@dbldeferlist}%
2696           \global \let \@dbltoplist \@empty
2697           \global \@colht \textheight
2698           \begingroup
2699             \@dblfloatplacement
2700             \@makefcolumn\@dbldeferlist
2701             \@whilesw\if@fcolmade \fi{\@outputpage
2702               \@makefcolumn\@dbldeferlist}%
2703           \endgroup
2704         \else
2705           \vbox{}\clearpage
2706         \fi
2707       \fi
2708     \else
2709       \setbox\@cclv\vbox{\box\@cclv\vfil}%
2710       \l@makecol\@opcol
2711       \clearpage
2712     \fi}
2713 }
2714

```

## 27 Cross referencing

Peter Wilson have rewritten portions of the code in this section so that the LaTeX .aux file is used. This will also handle \included files.

Further, I have renamed some of the original EDMAC macros so that they do not clash with the LaTeX label/ref commands (EDMAC and LaTeX use very different mechanisms). In particular, the original EDMAC \label and \pageref have been renamed as \edlabel and \edpageref respectively.

You can mark a place in the text using a command of the form \edlabel{foo}, and later refer to it using the label foo by saying \edpageref{foo}, or \lineref{foo} or \sublineref{foo}. These reference commands will produce, respectively, the page, line and sub-line on which the \edlabel{foo} command occurred.

The reference macros warn you if a reference is made to an undefined label. If foo has been used as a label before, the \edlabel{foo} command will issue a complaint; subsequent \edpageref and \lineref commands will refer to the latest occurrence of \label{foo}.

\labelref@list Set up a new list, \labelref@list, to hold the page, line and sub-line numbers for each label.

```
2715 \list@create{\labelref@list}
```

\zz@@@ A convenience macro to zero two labeling counters in one go.

```
2716 %% \newcommand*\zz@@@{000|000|000} % set three counters to zero in one go
2717 \newcommand*\zz@@@{000|000} % set two counters to zero in one go
2718
```

\edlabel The \edlabel command first writes a \@lab macro to the \linenum@out file. It then checks to see that the \labelref@list actually has something in it (if not, it creates a dummy entry), and pops the next value for the current label, storing it in \label@refs. Finally it defines the label to be \empty so that any future check will turn up the fact that it has been used.<sup>29</sup>

This version of the original EDMAC \label uses \@bsphack and \@esphack to eliminate extra space problems and also the LaTeX write methods for the .aux file.

Jesse Billett<sup>30</sup> found that the original code could be off by several pages. This version, hopefully cures that, and also allows for non-arabic page numbering.

```
2719 \newcommand*\edlabel}[1]{\@bsphack
2720   \write\linenum@out{\string\@lab}%
2721   \ifx\labelref@list\empty
2722     \xdef\label@refs{\zz@@@}%
2723   \else
2724     \gl@p\labelref@list\to\label@refs
2725   \ifvmode
```

<sup>29</sup>The remaining macros in this section were kindly revised by Wayne Sullivan, who substantially improved their efficiency and flexibility.

<sup>30</sup>(jdb43@cam.ac.uk) via the ctt thread 'ledmac cross referencing', 25 August 2003.



```

2726     \advancelabel@refs
2727 \fi
2728 \fi
2729 % \edef\next{\write\@aux{\string\l@dmake@labels\label@refs|{#1}}}%
2730 % \next}

```

Use code from the kernel `\label` command to write the correct page number (it seems possible that the original EDMAC's `\page@num` scheme might also have had problems in this area).

```

2731 \protected@write\@auxout{}%
2732   {\string\l@dmake@labels\space\thepage|\label@refs|{#1}}%
2733 \@esphack}
2734

```

`\advancelabel@refs` In cases where `\edlabel` is the first element in a paragraph, we have a problem  
`\labelrefsparseline` with line counts, because line counts change only at the first horizontal box of the  
`\labelrefsparsesubline` paragraph. Hence, we need to test `\edlabel` if it occurs at the start of a paragraph.  
 To do so, we use `\ifvmode`. If the test is true, we must advance by one unit the  
 amount of text we write into the `.aux` file. We do so using `\advancelabel@refs`  
 command.

```

2735 \newcounter{line}%
2736 \newcounter{subline}%
2737 \newcommand{\advancelabel@refs}{%
2738   \setcounter{line}{\expandafter\labelrefsparseline\label@refs}%
2739   \stepcounter{line}%
2740   \ifsublines0%
2741     \setcounter{subline}{\expandafter\labelrefsparsesubline\label@refs}%
2742     \stepcounter{subline}{1}%
2743     \def\label@refs{\theline|\thesubline}%
2744   \else%
2745     \def\label@refs{\theline|0}%
2746   \fi%
2747 }
2748 \def\labelrefsparseline#1|#2{#1}
2749 \def\labelrefsparsesubline#1|#2{#2}

```

`\l@dmake@labels` The `\l@dmake@labels` macro gets executed when the labels file is read. For each  
 label it defines a macro, whose name is made up partly from the label you supplied,  
 that contains the page, line and sub-line numbers. But first it checks to see whether  
 the label has already been used (and complains if it has).

The initial use of `\newcommand` is to catch if `\l@dmake@labels` has been pre-  
 viously defined (by a class or package).

```

2750 \newcommand*{\l@dmake@labels}{%
2751 \def\l@dmake@labels#1|#2|#3|#4{%
2752   \expandafter\ifx\csname the@label#4\endcsname \relax\else
2753     \led@warn@DuplicateLabel{#4}%
2754   \fi
2755   \expandafter\gdef\csname the@label#4\endcsname{#1|#2|#3}%
2756   \ignorespaces}

```

2757

LaTeX reads the `aux` file at both the beginning and end of the document, so we have to switch off duplicate label checking after the first time the file is read.

```
2758 \AtBeginDocument{%
2759   \def\l@dmake@labels#1|#2|#3|#4{%
2760 }
2761
```

`\@lab` The `\@lab` command, which appears in the `\linenum@out` file, appends the current values of page, line and sub-line to the `\labelref@list`. These values are defined by the earlier `\@page`, `\@l`, and the `\sub@on` and `\sub@off` commands appearing in the `\linenum@out` file.

LaTeX uses the `page` counter for page numbers. However, it appears that this is not the right place to grab the page number. That task is now done in the `\edlabel` macro. This version of `\@lab` appends just the current line and sub-line numbers to `\labelref@list`.

```
2762 \newcommand*{\@lab}{\xright@appenditem
2763   {\linenumrep{\line@num}|%
2764     \ifsublines@ \sublinenumrep{\subline@num}\else 0\fi}\to\labelref@list}
2765
```

`\edpageref` If the specified label exists, `\edpageref` gives its page number. For this reference command, as for the other two, a special version with prefix `x` is provided for use in places where the command is to be scanned as a number, as in `\linenum`. These special versions have two limitations: they don't print error messages if the reference is unknown, and they can't appear as the first label or reference command in the file; you must ensure that a `\edlabel` or a normal reference command appears first, or these `x`-commands will always return zeros. LaTeX already defines a `\pageref`, so changing the name to `\edpageref`.

```
2766 \newcommand*{\edpageref}[1]{\l@dref@undefined{#1}\l@dgetref@num{1}{#1}}
2767 \newcommand*{\xpageref}[1]{\l@dgetref@num{1}{#1}}
2768
```

`\lineref` If the specified label exists, `\lineref` gives its line number.

```
\xlineref 2769 \newcommand*{\lineref}[1]{\l@dref@undefined{#1}\l@dgetref@num{2}{#1}}
2770 \newcommand*{\xlineref}[1]{\l@dgetref@num{2}{#1}}
2771
```

`\sublineref` If the specified label exists, `\sublineref` gives its sub-line number.

```
\xsublineref 2772 \newcommand*{\sublineref}[1]{\l@dref@undefined{#1}\l@dgetref@num{3}{#1}}
2773 \newcommand*{\xsublineref}[1]{\l@dgetref@num{3}{#1}}
2774
```

The next three macros are used by the referencing commands above, and do the job of extracting the right numbers from the label macro that contains the page, line, and sub-line number.

`\l@dref@undefined` The `\l@dref@undefined` macro is called when you refer to a label with the normal referencing macros. Its argument is a label, and it just checks that the label has been defined.

```
2775 \newcommand*{\l@dref@undefined}[1]{%
2776   \expandafter\ifx\csname the@label#1\endcsname\relax
2777     \led@warn@RefUndefined{#1}%
2778   \fi}
2779
```

`\l@dgetref@num` Next, `\l@dgetref@num` fetches the number we want. It has two arguments: the first is simply a digit, specifying whether to fetch a page (1), line (2) or sub-line (3) number. (This switching is done by calling `\l@dlabel@parse`.) The second argument is the label-macro, which because of the `\@lab` macro above is defined to be a string of the type 123|456|789.

```
2780 \newcommand*{\l@dgetref@num}[2]{%
2781   \expandafter
2782   \ifx\csname the@label#2\endcsname \relax
2783     000%
2784   \else
2785     \expandafter\expandafter\expandafter
2786     \l@dlabel@parse\csname the@label#2\endcsname|#1%
2787   \fi}
2788
```

`\l@dlabel@parse` Notice that we slipped another `|` delimiter into the penultimate line of `\l@dgetref@num`, to keep the ‘switch-number’ separate from the reference numbers. This `|` is used as another parameter delimiter by `\l@dlabel@parse`, which extracts the appropriate number from its first arguments. The `|`-delimited arguments consist of the expanded label-macro (three reference numbers), followed by the switch-number (1, 2, or 3) which defines which of the earlier three numbers to pick out. (It was earlier given as the first argument of `\l@dgetref@num`.)

```
2789 \newcommand*{\l@dlabel@parse}{%
2790   \def\l@dlabel@parse#1|#2|#3|#4{%
2791     \ifcase #4\relax
2792     \or #1%
2793     \or #2%
2794     \or #3%
2795   \fi}
2796
```

`\xxref` The `\xxref` command takes two arguments, both of which are labels, e.g., `\xxref{mouse}{elephant}`. It first does some checking to make sure that the labels do exist (if one doesn’t, those numbers are set to zero). Then it calls `\linenum` and sets the beginning page, line, and sub-line numbers to those of the place where `\label{mouse}` was placed, and the ending numbers to those at `\label{elephant}`. The point of this is to be able to manufacture footnote line references to passages which can’t be specified in the normal way as the first

argument to `\critext` for one reason or another. Using `\xxref` in the second argument of `\critext` lets you set things up at least semi-automatically.

```
2797 \newcommand*{\xxref}[2]{%
2798   {\expandafter\ifx\csname the@label#1\endcsname
2799     \relax \expandafter\let\csname the@label#1\endcsname\zz@@@%fi
2800   \expandafter\ifx\csname the@label#2\endcsname \relax
2801     \expandafter\let\csname the@label#2\endcsname\zz@@@%fi
2802   \linenum{\csname the@label#1\endcsname}%
2803   \csname the@label#2\endcsname}}
2804
```

`\edmakelabel` Sometimes the `\edlabel` command cannot be used to specify exactly the page and line desired; you can use the `\edmakelabel` macro make your own label. For example, if you say ‘`\edmakelabel{elephant}{10|25|0}`’ you will have created a new label, and a later call to `\edpageref{elephant}` would print ‘10’ and `\lineref{elephant}` would print ‘25’. The sub-line number here is zero. `\edmakelabel` takes a label, followed by a page and a line number(s) as arguments. LaTeX defines a `\makelabel` macro which is used in lists. I’ve changed the name to `\edmakelabel`.

```
2805 \newcommand*{\edmakelabel}[2]{\expandafter\xdef\csname the@label#1\endcsname{#2}}
2806
```

(If you are only going to refer to such a label using `\xxref`, then you can omit entries in the same way as with `\linenum` (see pp. 75 and 55), since `\xxref` makes a call to `\linenum` in order to do its work.)

## 28 Endnotes

```
\l@d@end Endnotes of all varieties are saved up in a file, typically named <jobname>.end.
\ifl@dend@ \l@d@end is the output stream number for this file, and \ifl@dend@ is a flag that’s
\l@dend@true true when the file is open.
\l@dend@false 2807 \newwrite\l@d@end
                2808 \newif\ifl@dend@
```

```
\l@dend@open \l@dend@open and \l@dend@close are the macros that are used to open and close
\l@dend@close the endnote file. Note that all our writing to this file is \immediate: all page and
                line numbers for the endnotes are generated by the same mechanism we use for
                the footnotes, so that there’s no need to defer any writing to catch information
                from the output routine.
```

```
2809 \newcommand{\l@dend@open}[1]{\global\l@dend@true\immediate\openout\l@d@end=#1\relax}
2810 \newcommand{\l@dend@close}{\global\l@dend@false\immediate\closeout\l@d@end}
2811
```

```
\l@dend@stuff \l@dend@stuff is used by \beginnumbering to do everything that’s necessary for
                the endnotes at the start of each section: it opens the \l@d@end file, if necessary,
                and writes the section number to the endnote file.
```

```
2812 \newcommand{\l@dend@stuff}{%
```

```

2813 \ifl@dend@relax\else
2814   \l@dend@open{\jobname.end}%
2815 \fi
2816 \immediate\write\l@d@end{\string\l@d@section{\the\section@num}}
2817

```

`\endprint` The `\endprint` here is nearly identical in its functioning to `\normalfootfmt`.

`\@gobblethree` The endnote file also contains `\l@d@section` commands, which supply the  
`\l@d@section` section numbers from the main text; standard `eledmac` does nothing with this information, but it's there if you want to write custom macros to do something with it.

```

2818 \def\endprint#1#2#3#4{{\csuse{bhookXendnote@#4}\csuse{Xendnotefontsize@#4}{\csuse{Xendnotenumfont@#4}}
2819   \enspace{\select@lemmafnt#1|#2}\enskip#3\par}}
2820 \providecommand*\@gobblethree}[3]{}
2821
2822 \let\l@d@section=\@gobble
2823

```

`\setprintendlines` The `\printendlines` macro is similar to `\printlines` but is for printing endnotes rather than footnotes.

The principal difference between foot- and endnotes is that footnotes are printed on the page where they are specified but endnotes are printed at a different point in the document. We need an indication of the source of an endnote; `\setprintendlines` provides this by always printing the page number. The coding is slightly simpler than `\setprintlines`.

First of all, we print the second page number only if the ending page number is different from the starting page number.

```

2824 \newcommand*\setprintendlines}[6]{%
2825   \l@d@pnumfalse \l@d@dashfalse
2826   \ifnum#4=#1 \else
2827     \l@d@pnumtrue
2828     \l@d@dashtrue
2829   \fi

```

We print the ending line number if: (1) we're printing the ending page number, or (2) it's different from the starting line number.

```

2830   \ifl@d@pnum \l@d@elintrue \else \l@d@elinfalse \fi
2831   \ifnum#2=#5 \else
2832     \l@d@elintrue
2833     \l@d@dashtrue
2834   \fi

```

We print the starting sub-line if it's nonzero.

```

2835   \l@d@ssubfalse
2836   \ifnum#3=0 \else
2837     \l@d@ssubtrue
2838   \fi

```

We print the ending sub-line if it's nonzero and: (1) it's different from the starting sub-line number, or (2) the ending line number is being printed.

```

2839 \l@deslfalse
2840 \ifnum#6=0 \else
2841     \ifnum#6=#3
2842         \ifl@d@elin \l@d@esltrue \else \l@d@eslfalse \fi
2843     \else
2844         \l@d@esltrue
2845         \l@d@dashtrue
2846     \fi
2847 \fi}

```

`\printendlines` Now we're ready to print it all.

```

2848 \def\printendlines#1|#2|#3|#4|#5|#6|#7|{\begingroup
2849     \setprintendlines{#1}{#2}{#3}{#4}{#5}{#6}%

```

The only subtlety left here is when to print a period between numbers. But the only instance in which this is tricky is for the ending sub-line number: it could be coming after the starting sub-line number (in which case we want only the dash) or after an ending line number (in which case we need to insert a period).

```

2850 \printnpnum{#1} \linenumrep{#2}%
2851 \ifl@d@ssub \fullstop \sublinenumrep{#3}\fi
2852 \ifl@d@dash \endashchar\fi
2853 \ifl@d@pnum \printnpnum{#4}\fi
2854 \ifl@d@elin \linenumrep{#5}\fi
2855 \ifl@d@esl \ifl@d@elin \fullstop\fi \sublinenumrep{#6}\fi
2856 \endgroup}
2857

```

`\printnpnum` A macro to print a page number in an endnote.

```

2858 \newcommand*{\printnpnum}[1]{p.#1} }
2859

```

`\doendnotes` `\doendnotes` is the command you use to print one series of endnotes; it takes one argument, the series letter of the note series you want to print.

```

2860 \newcommand*{\doendnotes}[1]{\l@dend@close
2861     \begingroup
2862         \makeatletter
2863         \expandafter\let\csname #1end\endcsname=\endprint
2864         \input\jobname.end
2865     \endgroup}

```

`\noendnotes` You can say `\noendnotes` before the first `\beginnumbering` in your file if you aren't going to be using any of the endnote commands: this will suppress the creation of an `.end` file. If you do have some lingering endnote commands in your file, the notes will be written to your terminal and to the log file.

```

2866 \newcommand*{\noendnotes}{\global\let\l@dend@stuff=\relax
2867     \global\chardef\l@dend=16 }

```

## 29 Side notes

Regular `\marginpars` do not work inside numbered text — they don't produce any note but do put an extra unnumbered blank line into the text.

`\l@dold@xympar` Changing `\@xympar` a little at least ensures that `\marginpars` in numbered text  
`\@xympar` do not disturb the flow.

```
2868 \let\l@dold@xympar\@xympar
2869 \renewcommand{\@xympar}{%
2870   \ifnumberedpar@
2871     \led@warn@NoMarginpars
2872     \esphack
2873   \else
2874     \l@dold@xympar
2875   \fi}
2876
```

We provide side notes as replacement for `\marginpar` in numbered text.

`\sidenote@margin` These are the sidenote equivalents to `\line@margin` and `\linenummargin` for  
`\sidenotemargin` specifying which margin. The default is the right margin (opposite to the default  
`\l@dgetsidenote@margin` for line numbers).

```
2877 \newcount\sidenote@margin
2878 \newcommand*{\sidenotemargin}[1]{%
2879   \l@dgetsidenote@margin{#1}%
2880   \ifnum\@l@dttempcntb>\m@ne
2881     \global\sidenote@margin=\@l@dttempcntb
2882   \fi}%
2883 \newcommand*{\l@dgetsidenote@margin}[1]{%
2884   \def\@tempa{#1}\def\@tempb{left}%
2885   \ifx\@tempa\@tempb
2886     \@l@dttempcntb \z@
2887   \else
2888     \def\@tempb{right}%
2889     \ifx\@tempa\@tempb
2890       \@l@dttempcntb \@ne
2891     \else
2892       \def\@tempb{outer}%
2893       \ifx\@tempa\@tempb
2894         \@l@dttempcntb \tw@
2895       \else
2896         \def\@tempb{inner}%
2897         \ifx\@tempa\@tempb
2898           \@l@dttempcntb \thr@@
2899         \else
2900           \led@warn@BadSidenotemargin
2901           \@l@dttempcntb \m@ne
2902         \fi
2903       \fi

```

```

2904     \fi
2905   \fi}
2906 \sidenotemargin{right}
2907

\l@dlp@rbox We need two boxes to store sidenote texts.
\l@drp@rbox 2908 \newbox\l@dlp@rbox
2909 \newbox\l@drp@rbox
2910

\ledlsnotewidth These specify the width of the left/right boxes (initialised to \marginparwidth,
\ledrsnotewidth their distance from the text (initialised to \linenumsep, and the fonts used.
\ledlsnotesep 2911 \newdimen\ledlsnotewidth \ledlsnotewidth=\marginparwidth
\ledrsnotesep 2912 \newdimen\ledrsnotewidth \ledrsnotewidth=\marginparwidth
\ledlsnotefontsetup 2913 \newdimen\ledlsnotesep \ledlsnotesep=\linenumsep
\ledrsnotefontsetup 2914 \newdimen\ledrsnotesep \ledrsnotesep=\linenumsep
2915 \newcommand*{\ledlsnotefontsetup}{\raggedleft\footnotesize}
2916 \newcommand*{\ledrsnotefontsetup}{\raggedright\footnotesize}
2917

\ledleftnote \ledleftnote{<text>} and \ledrightnote{<text>} are the user commands for
\ledrightnote left and right sidenotes. \ledsidenote{<text>} is the command for a moveable
\ledsidenote sidenote.

2918 \newcommand*{\ledleftnote}[1]{\edtext{}{\l@dlsnote{#1}}}
2919 \newcommand*{\ledrightnote}[1]{\edtext{}{\l@drsnote{#1}}}
2920 \newcommand*{\ledsidenote}[1]{\edtext{}{\l@dcsnote{#1}}}
2921
2922

\l@dlsnote The ‘footnotes’ for left, right, and moveable sidenotes. The whole scheme is rem-
\l@drsnote iniscent of the critical footnotes code.
\l@dcsnote 2923 \newif\ifrighnoteup
2924 \righnoteuptrue
2925 \newcommand*{\l@dlsnote}[1]{%
2926   \begingroup%
2927   \newcommand{\content}{#1}%
2928   \ifnumberedpar@
2929     \xright@appenditem{\noexpand\l@dlsnote{\csexpandonce{content}}}%
2930     \to\inserts@list
2931     \global\advance\insert@count \@ne
2932   \fi\ignorespaces\endgroup}
2933 \newcommand*{\l@drsnote}[1]{%
2934   \begingroup%
2935   \newcommand{\content}{#1}%
2936   \ifnumberedpar@
2937     \xright@appenditem{\noexpand\l@drsnote{\csexpandonce{content}}}%
2938     \to\inserts@list
2939     \global\advance\insert@count \@ne
2940   \fi\ignorespaces\endgroup}

```



```

2941 \newcommand*{\l@dcnote}[1]{\begingroup%
2942   \newcommand{\content}{#1}%
2943   \ifnumberedpar@
2944     \xright@appenditem{\noexpand\l@dcnote{\csexpandonce{content}}}%
2945     \to\inserts@list
2946     \global\advance\insert@count \@ne
2947   \fi\ignorespaces\endgroup}
2948

```

`\vl@dlsnote` Put the left/right text into boxes, but just save the moveable text. `\l@dcnotetext`

`\vl@drsnote` is a etoolbox list (comma separated)

```

\vl@dcnote 2949 \newcommand*{\vl@dlsnote}[1]{\setl@dlp@rbox{#1}}
2950 \newcommand*{\vl@drsnote}[1]{\setl@drp@rbox{#1}}
2951 \newcommand*{\vl@dcnote}[1]{\listgadd{\l@dcnotetext}{#1}}
2952

```

`\setl@dlp@rbox` `\setl@dlprbox{<lednums>}{<tag>}{<text>}` puts `<text>` into the `\l@dlp@rbox` box.

`\setl@drpr@box` And similarly for the right side box. It is these boxes that finally get displayed in the margins.

```

2953 \newcommand*{\setl@dlp@rbox}[1]{%
2954   {\parindent\z@\hspace=\ledlsnotewidth\ledlsnotefontsetup
2955     \global\setbox\l@dlp@rbox
2956     \ifleftnoteup
2957       =\vbox to\z@{\vss #1}%
2958     \else
2959       =\vbox to 0.70\baselineskip{\strut#1\vss}%
2960     \fi}}
2961 \newcommand*{\setl@drp@rbox}[1]{%
2962   {\parindent\z@\hspace=\ledrsnotewidth\ledrsnotefontsetup
2963     \global\setbox\l@drp@rbox
2964     \ifrightnoteup
2965       =\vbox to\z@{\vss#1}%
2966     \else
2967       =\vbox to0.7\baselineskip{\strut#1\vss}%
2968     \fi}}
2969 \newif\ifleftnoteup
2970 \leftnoteuptrue

```

`\sidenotesep` This macro is used to separate sidenotes of the same line.

```

2971 \newcommand{\sidenotesep}{, }
2972 % \end{macrocode}
2973 % \end{macro}
2974 % \begin{macro}{\affixside@note}
2975 % This macro puts any moveable sidenote text into the left or right sidenote
2976 % box, depending on which margin it is meant to go in. It's a very much
2977 % stripped down version of \cs{affixlin@num}.
2978 %
2979 % Before do it, we concatenate all moveable sidenotes of the line, using \cs{sidenotesep} as separator
2980 % It's the result that we put on the sidenote.

```

```

2981 % \changes{v1.4.1}{2012/11/16}{Remove spurious spaces.}
2982 % \begin{macrocode}
2983 \newcommand*{\affixside@note}{%
2984   \def\sidenotecontent@{}%
2985   \numdef\itemcount@{0}%
2986   \def\do##1{%
2987     \ifnumequal{\itemcount@}{0}%
2988       {%
2989         \appto\sidenotecontent@{##1}}% Not print not separator before the 1st note
2990         {\appto\sidenotecontent@{\sidenotesep ##1}}%
2991       }%
2992     \numdef\itemcount@{\itemcount@+1}%
2993   }%
2994   \dolistloop{\l@dcstotetext}%
2995   \ifnumgreater{\itemcount@}{1}{\eledmac@warning{\itemcount@\space sidenotes on line \tl

```

And now, the main part of the macro

```

2996 \gdef\@templ@d{%
2997 \ifx\@templ@d\l@dcstotetext \else%
2998 \if@twocolumn%
2999   \if@firstcolumn%
3000     \setl@dlp@rbox{##1}{\sidenotecontent@}%
3001   \else%
3002     \setl@drp@rbox{\sidenotecontent@}%
3003   \fi%
3004 \else%
3005   \l@dttempcntb=\sidenote@margin%
3006   \ifnum\l@dttempcntb>\@ne%
3007     \advance\l@dttempcntb by\page@num%
3008   \fi%
3009   \ifodd\l@dttempcntb%
3010     \setl@drp@rbox{\sidenotecontent@}%
3011   \else%
3012     \setl@dlp@rbox{\sidenotecontent@}%
3013   \fi%
3014 \fi%
3015 \fi}

```

## 30 Minipages and such

We can put footnotes into minipages. The preparatory code has been set up earlier, all that remains is to ensure that it is available inside a minipage box. This requires some alteration to the kernel code, specifically the `\@iiminipage` and `\endminipage` macros. We'll arrange this so that additional series can be easily added.

```

\l@dfeetbeginmini These will be the hooks in \@iiminipage and \endminipage They can be extended
\l@dfeetendmini   to handle other things if necessary.
3016 \newcommand*{\l@dfeetbeginmini}{\l@ddebbeginmini\l@dfambeginmini}

```

```

3017 \newcommand*{\l@dfetendmini}{\l@dedendmini\l@dfamendmini}
3018

```

`\l@dedbeginmini` These handle the initiation and closure of critical footnotes in a minipage environment.  
`\l@dedendmini`

```

3019 \newcommand*{\l@dedbeginmini}{%
3020   \def\do##1{\csletcs{v##1footnote}{mpv##1footnote}}%
3021   \dolistloop{\@series}%
3022 }
3023 \newcommand*{\l@dedendmini}{%
3024   \ifl@dpairing
3025     \ifl@Rcol
3026       \flush@notesR
3027     \else
3028       \flush@notes
3029     \fi
3030   \fi
3031   \def\do##1{\ifvoid\csuse{mp##1footins}\else\csuse{mp##1footgroup}{##1}\fi}%
3032   \dolistloop{\@series}%
3033 }
3034

```

`\l@dfambeginmini` These handle the initiation and closure of familiar footnotes in a minipage environment.  
`\l@dfamendmini`

```

3035 \newcommand*{\l@dfambeginmini}{%
3036   \def\do##1{\csletcs{vfootnote##1}{mpvfootnote##1}}%
3037   \dolistloop{\@series}}
3038 \newcommand*{\l@dfamendmini}{%
3039   \def\do##1{\ifvoid\csuse{mpfootins##1}\else\csuse{mpfootgroup##1}{##1}\fi}%
3040   \dolistloop{\@series}}

```

`\@iiiminipage` This is our extended form of the kernel `\@iiiminipage` defined in `ltboxes.dtx`.

```

3041 \def\@iiiminipage#1#2[#3]#4{%
3042   \leavevmode
3043   \@pboxswfalse
3044   \setlength\@tempdima{#4}%
3045   \def\@mpargs{#1}#2[#3]{#4}}%
3046   \setbox\@tempboxa\vbox\bgroup
3047     \color@begingroup
3048     \hsize\@tempdima
3049     \textwidth\hsize \columnwidth\hsize
3050     \@parboxrestore
3051     \def\@mpfn{mpfootnote}\def\thempfn{\thempfootnote}\c@mpfootnote\z@
3052     \let\@footnotetext\@mpfootnotetext

```

The next line is our addition to the original.

```

3053     \l@dfetbeginmini% added
3054     \let\@listdepth\@mplistdepth \@mplistdepth\z@
3055     \@minipagerestore

```

```

3056     \@setminipage}
3057

```

`\endminipage` This is our extended form of the kernel `\endminipage` defined in `ltboxes.dtx`.

```

3058 \def\endminipage{%
3059   \par
3060   \unskip
3061   \ifvoid\@mpfootins\else
3062     \l@dunboxmpfoot
3063   \fi
3064   \l@dfeetendmini%          added
3065   \@minipagefalse
3066   \color@endgroup
3067   \egroup
3068   \expandafter\@iiiparbox\@mpargs{\unvbox\@tempboxa}}
3069

```

The next line is our addition to the original.

`\l@dunboxmpfoot`

```

3070 \newcommand*{\l@dunboxmpfoot}{%
3071   \vskip\skip\@mpfootins
3072   \normalcolor
3073   \footnoterule
3074   \unvbox\@mpfootins}
3075

```

`ledgroup` This environment puts footnotes at the end, even if that happens to be in the middle of a page, or crossing a page boundary. It is a sort of unboxed, fixed width minipage.

```

3076 \newenvironment{ledgroup}{%
3077   \def\@mpfn{mpfootnote}\def\thempfn{\thempfootnote}\c@mpfootnote\z@
3078   \let\@footnotetext\@mpfootnotetext
3079   \l@dfeetbeginmini%
3080 }{%
3081   \par
3082   \unskip
3083   \ifvoid\@mpfootins\else
3084     \l@dunboxmpfoot
3085   \fi
3086   \l@dfeetendmini%
3087 }
3088

```

`ledgroupsize` `\begin{ledgroupsize}[\langle pos \rangle]{\langle width \rangle}`

This environment puts footnotes at the end, even if that happens to be in the middle of a page, or crossing a page boundary. It is a sort of unboxed, variable  $\langle width \rangle$  minipage. The optional  $\langle pos \rangle$  controls the sideways position of numbered text.

```

3089 \newenvironment{ledgroupsize}[2][1]{%

```

Set the various text measures.

```
3090 \hsize #2\relax
3091 %% \textwidth #2\relax
3092 %% \columnwidth #2\relax
```

Initialize fills for centering.

```
3093 \let\ledllfill\hfil
3094 \let\ledrlfill\hfil
3095 \def\@tempa{#1}\def\@tempb{1}%
```

Left adjusted numbered lines

```
3096 \ifx\@tempa\@tempb
3097 \let\ledllfill\relax
3098 \else
3099 \def\@tempb{r}%
3100 \ifx\@tempa\@tempb
```

Right adjusted numbered lines

```
3101 \let\ledrlfill\relax
3102 \fi
3103 \fi
```

Set up the footnoting.

```
3104 \def\@mpfn{mpfootnote}\def\thempfn{\thempfootnote}\c@mpfootnote\z@
3105 \let\@footnotetext\@mpfootnotetext
3106 \l@dfetbeginmini%
3107 }{%
3108 \par
3109 \unskip
3110 \ifvoid\@mpfootins\else
3111 \l@dunboxmpfoot
3112 \fi
3113 \l@dfetendmini%
3114 }
3115
```

## 31 Indexing

Here's some code for indexing using page & line numbers.

`\pagelinesep` In order to get a correct line number we have to use the label/ref mechanism.  
`\edindexlab` These macros are for that.

```
\c@labidx 3116 \newcommand{\pagelinesep}{-}
3117 \newcommand{\edindexlab}{\&}
3118 \newcounter{labidx}
3119 \setcounter{labidx}{0}
3120
```

`\doedindexlabel` This macro sets an `\edlabel`.

```
3121 \newcommand{\doedindexlabel}{\stepcounter{labidx}%
```

```

3122 \edlabel{\edindexlab\thelabidx}}
3123

```

`\thepageline` This macro makes up the page/line number combo from the label/ref.

```

3124 \newcommand{\thepageline}{%
3125 \thepage\pagelinesep\lineref{\edindexlab\thelabidx}}
3126

```

The memoir class provides more flexible indexing than the standard classes. We need different code if the memoir class is being used.

```

3127 \ifclassloaded{memoir}{%
    memoir is being used.

```

`\makeindex` Need to add the definition of `\edindex` to `\makeindex`, and initialise `\edindex` to do nothing. In this case `\edindex` has an optional argument. We use the hook provided in memoir v1.61.

```

3128 \g@addto@macro{\makememindexhook}{%
3129 \def\edindex{\@bsphack%
3130 \ifnextchar [{\l@d@index}{\l@d@index[\jobname]}}
3131 \newcommand{\edindex}[2][\jobname]{\@bsphack\@esphack}

```

`\l@d@index` `\l@d@index[file]` is the first stage of `\edindex`, handling the `idx` file. This is a virtually a verbatim copy of memoir's `\@index`, the change being calling `\l@d@wrindexm@m` instead of `\@wrindexm@m`.

```

3132 \def\l@d@index[#1]{%
3133 \ifundefined{#1idxfile}%
3134 {\ifreportnoidxfile
3135 \led@warn@NoIndexFile{#1}%
3136 \fi
3137 \begingroup
3138 \@sanitize
3139 \@nowrindex}%
3140 {\def\@idxfile{#1}%
3141 \doedindexlabel
3142 \begingroup
3143 \@sanitize
3144 \l@d@wrindexm@m}}

```

`\l@d@wrindexm@m` `\l@d@wrindexm@m{item}` writes the `idx` file name and the indexed item to the aux file. These are almost verbatim copies of memoir's `\@wrindexm@m` and `\@wrindexhyp`.

```

3145 \newcommand{\l@d@wrindexm@m}[1]{\l@d@wrindexhyp#1||\}
3146 \def\l@d@wrindexhyp#1|#2|#3\{\%
3147 \ifshowindexmark\@showidx{#1}\fi
3148 \ifx\#2\%
3149 \protected@write\@auxout{%
3150 {\string\@wrindexm@m{\@idxfile}{#1|hyperpage}{\thepageline}}%
3151 \else

```

```

3152     \def\Hy@temp@A{#2}%
3153     \ifx\Hy@temp@A\HyInd@ParenLeft
3154         \protected@write\@auxout{}%
3155             {\string\@wrindexm@m{\@idxfile}{#1|#2hyperpage}{\thepageline}}%
3156     \else
3157         \protected@write\@auxout{}%
3158             {\string\@wrindexm@m{\@idxfile}{#1|#2}{\thepageline}}%
3159     \fi
3160 \fi
3161 \endgroup
3162 \@esphack}

```

That finishes the memoir-specific code.

```
3163 }{%
```

memoir is not being used, which makes life somewhat simpler.

`\makeindex` Need to add the definition of `\edindex` to `\makeindex`, and initialise `\edindex` to do nothing.

```

3164 \g@addto@macro{\makeindex}{%
3165     \def\edindex{\@bsphack
3166         \doedindexlabel
3167         \begingroup
3168         \@sanitize
3169         \@wredindex}}
3170 \newcommand{\edindex}[1]{\@bsphack\@esphack}

```

`\@wredindex` Write the index information to the `idx` file.

```

3171 \newcommand{\@wredindex}[1]{%
3172     \protected@write\@indexfile{}%
3173         {\string\indexentry{#1}{\thepageline}}%
3174 \endgroup
3175 \@esphack}

```

That finishes the non-memoir index code.

```

3176 }
3177

```

`\l@d@wrindexhyp` If the `hyperref` package is not loaded, it doesn't make sense to clutter up the index with hyperreffing things.

```

3178 \AtBeginDocument{\@ifpackageloaded{hyperref}{}{%
3179     \def\l@d@wrindexhyp#1||\{\%
3180         \ifshowindexmark\@showidx{#1}\fi
3181         \protected@write\@auxout{}%
3182             {\string\@wrindexm@m{\@idxfile}{#1}{\thepageline}}%
3183     \endgroup
3184     \@esphack}}}
3185

```

## 32 Macro as environment

The following is borrowed, and renamed, from the `amsmath` package. See also the CTT thread ‘`eq and amstex`’, 1995/08/31, started by Keith Reckdahl and ended definitively by David M. Jones.

Several of the `[math]` macros scan their body twice. This means we must collect all text in the body of an environment form before calling the macro.

`\@emptytoks` This is actually defined in the `amsgen` package.

```
3186 \newtoks\@emptytoks
3187
```

The rest is from `amsmath`.

`\l@denvbody` A token register to contain the body.

```
3188 \newtoks\l@denvbody
3189
```

`\addtol@denvbody` `\addtol@denvbody{arg}` adds `arg` to the token register `\l@denvbody`.

```
3190 \newcommand{\addtol@denvbody}[1]{%
3191   \global\l@denvbody\expandafter{\the\l@denvbody#1}}
3192
```

`\l@dcollect@body` The macro `\l@dcollect@body` starts the scan for the `\end{...}` command of the current environment. It takes a macro name as argument. This macro is supposed to take the whole body of the environment as its argument. For example, given `cenv#1{...}` as a macro that processes `#1`, then the environment form, `\begin{env}` would call `\l@dcollect@body\cenv`.

```
3193 \newcommand{\l@dcollect@body}[1]{%
3194   \l@denvbody{\expandafter#1\expandafter{\the\l@denvbody}}%
3195   \edef\processl@denvbody{\the\l@denvbody\noexpand\end{\@currenvir}}%
3196   \l@denvbody\@emptytoks \def\l@dbegin@stack{b}%
3197   \begingroup
3198     \expandafter\let\csname\@currenvir\endcsname\l@dcollect@@body
3199     \edef\processl@denvbody{\expandafter\noexpand\csname\@currenvir\endcsname}%
3200     \processl@denvbody}
3201
```

`\l@dpush@begins` When adding a piece of the current environment’s contents to `\l@denvbody`, we scan it to check for additional `\begin` tokens, and add a ‘b’ to the stack for any that we find.

```
3202 \def\l@dpush@begins#1\begin#2{%
3203   \ifx\end#2\else b\expandafter\l@dpush@begins\fi}
3204
```

`\l@dcollect@@body` `\l@dcollect@@body` takes two arguments: the first will consist of all text up to the next `\end` command, and the second will be the `\end` command’s argument. If there are any extra `\begin` commands in the body text, a marker is pushed onto a



stack by the `l@dpush@begins` function. Empty state for this stack means we have reached the `\end` that matches our original `\begin`. Otherwise we need to include the `\end` and its argument in the material we are adding to the environment body accumulator.

```

3205 \def\l@collect@@body#1\end#2{%
3206   \edef\l@dbegin@stack{\l@dpush@begins#1\begin\end
3207     \expandafter\@gobble\l@dbegin@stack}%
3208   \ifx\@empty\l@dbegin@stack
3209     \endgroup
3210     \@checkend{#2}%
3211     \addtol@denvbody{#1}%
3212   \else
3213     \addtol@denvbody{#1\end{#2}}%
3214   \fi
3215   \processl@denvbody % A little tricky! Note the grouping
3216 }
3217

```

There was a question on CTT about how to use `\collect@body` for a macro taking an argument. The following is part of that thread.

From: Heiko Oberdiek <oberdiek@uni-freiburg.de>  
 Newsgroups: comp.text.tex  
 Subject: Re: Using `\collect@body` with commands that take >1 argument  
 Date: Fri, 08 Aug 2003 09:03:20 +0200

eed132@psu.edu (Evan) wrote:  
 > I'm trying to make a new Latex environment that acts like the  
 > `\colorbox` command that is part of the `color` package. I looked through  
 > the FAQ and ran across this bit about using the `\collect@body` command  
 > that is part of AMSLaTeX:  
 > <http://www.tex.ac.uk/cgi-bin/texfaq2html?label=cmdasenv>  
 >  
 > It almost works. If I do something like the following:  
 > `\newcommand{\redbox}[1]{\colorbox{red}{#1}}`  
 >  
 > `\makeatletter`  
 > `\newenvironment{redbox}{\collect@body \redbox}{}`

You will get an error message: Command `\redbox` already defined.  
 Thus you must rename either the command `\redbox` or the environment name.

```

> \begin{coloredbox}{blue}
>   Yadda yadda yadda... this is on a blue background...
> \end{coloredbox}
> and can't figure out how to make the \collect@body take this.

> \collect@body \colorbox{red}
> \collect@body {\colorbox{red}}

```

The argument of `\collect@body` has to be one token exactly.

```

\documentclass{article}
\usepackage{color}
\usepackage{amsmath}

\newcommand{\redbox}[1]{\colorbox{red}{#1}}
\makeatletter
\newenvironment{coloredbox}[1]{%
  \def\next@{\colorbox{#1}}%
  \collect@body\next@
}{%

% ignore spaces at begin and end of environment
\newenvironment{coloredboxII}[1]{%
  \def\next@{\mycoloredbox{#1}}%
  \collect@body\next@
}{%
\newcommand{\mycoloredbox}[2]{%
  \colorbox{#1}{\ignorespaces#2\unskip}%
}

% support of optional color model argument
\newcommand\coloredboxIII\endcsname{}
\def\coloredboxIII#1#{%
  \@coloredboxIII{#1}%
}
\def\@coloredboxIII#1#2{%
  \def\next@{\mycoloredboxIII{#1}{#2}}%
  \collect@body\next@
}
\newcommand{\mycoloredboxIII}[3]{%
  \colorbox#1{#2}{\ignorespaces#3\unskip}%
}

\makeatother

\begin{document}
  Black text before
  \begin{coloredbox}{blue}
    Hello World
  \end{coloredbox}
  Black text after

  Black text before
  \begin{coloredboxII}{blue}
    Hello World
  \end{coloredboxII}
  Black text after

```

```

Black text before
\begin{coloredboxIII}[rgb]{0,0,1}
  Hello World
\end{coloredboxIII}
Black text after

\end{document}

Yours sincerely
Heiko <oberdiek@uni-freiburg.de>

```

### 33 Verse

This is principally Wayne Sullivan's code and commentary from EDSTANZA [Sul92].

The macro `\hangingsymbol` is used to insert a symbol on each hanging of verses. For example, in french typographie the symbol is ‘[’. We obtain it by the next code:

```
\renewcommand{\hangingsymbol}{[,]}
```

The `\ifinstanza` boolean is used to be sure that we are in a stanza part.

```

\hangingsymbol
\ifinstanza 3218 \newcommand*{\hangingsymbol}{}
            3219 \newif\ifinstanza
            3220 \instanzafalse

\inserthangingsymbol The boolean \ifinserthangingsymbol is set to TRUE when \@lock is greater
\ifinserthangingsymbol than 1, i.e. when we are not in the first line of a verse. The switch of
                        \ifinserthangingsymbol is made in \do@line before the printing of line but
                        after the line number calculation.

3221 \newif\ifinserthangingsymbol
3222 \newcommand{\inserthangingsymbol}{%
3223 \ifinserthangingsymbol%
3224   \ifinstanza%
3225     \hfill\hangingsymbol%
3226   \fi%
3227 \fi%
3228 }

```

`\ampersand` Within a stanza the `&` macro is going to be usurped. We need an alias in case an `&` needs to be typeset in a stanza. Define it rather than letting it in case some other package has already defined it.

```

3229 \newcommand*{\ampersand}{\char'\&}
3230

```

`\stanza@count` Before we can define the main macros we need to save and reset some category codes. To save the current values we use `\next` and `\body` from the `\loop` macro.

```
3231 \chardef\body=\catcode'\@
3232 \catcode'\@=11
3233 \chardef\next=\catcode'\&
3234 \catcode'\&=\active
3235
```

A count register is allocated for counting lines in a stanza; also allocated is a dimension register which is used to specify the base value for line indentation; all stanza indentations are multiples of this value. The default value of `\stanzaindentbase` is 20pt.

```
3236 \newcount\stanza@count
3237 \newlength{\stanzaindentbase}
3238 \setlength{\stanzaindentbase}{20pt}
3239
```

`\strip@szacnt` The indentations of stanza lines are non-negative integer multiples of the unit called `\stanzaindentbase`. To make it easier for the user to specify these numbers, some list macros are defined. These take numerical values in a list separated by commas and assign the values to special control sequences using `\mathchardef`. Though this does limit the range from 0 to 32767, it should suffice for most applications, including *penalties*, which will be discussed below.

```
3240 \def\strip@szacnt#1,#2|{\def\@tempb{#1}\def\@tempa{#2|}}
3241 \newcommand*{\setstanzavalues}[2]{\def\@tempa{#2,,|}%
3242     \stanza@count\z@
3243     \def\next{\expandafter\strip@szacnt\@tempa
3244         \ifx\@tempb\empty\let\next\relax\else
3245         \expandafter\mathchardef\csname #1@\number\stanza@count
3246         \@endcsname\@tempb\relax
3247         \advance\stanza@count\@ne\fi\next}%
3248     \next}
3249
```

`\setstanzaindents` In the original `\setstanzavalues{sza}{...}` had to be called to set the indents, and similarly `\setstanzavalues{szp}{...}` to set the penalties. These two macros are a convenience to give the user one less thing to worry about (misspelling the first argument). Since version 0.13, the `stanzaindentrepetition` counter can be used when the indentation is repeated every *n* verses. The `\managestanza@modulo` is a command which modifies the counter `stanza@modulo`. The command adds 1 to `stanza@modulo`, but if `stanza@modulo` is equal to the `stanzaindentrepetition` counter, the command restarts it.

```
3250 \newcommand*{\setstanzaindents}[1]{\setstanzavalues{sza}{#1}}
3251 \newcommand*{\setstanzapenalties}[1]{\setstanzavalues{szp}{#1}}
3252
3253 \newcounter{stanzaindentrepetition}
3254 \newcount\stanza@modulo
3255
```

```

3256 \newcommand*{\managestanza@modulo}[0]{
3257     \advance\stanza@modulo\@ne
3258     \ifnum\stanza@modulo>\value{stanzaindentrepetition}
3259         \stanza@modulo\@ne
3260     \fi
3261 }

```

`\stanza@line` Now we arrive at the main works. `\stanza@line` sets the indentation for the line and starts a numbered paragraph—each line is treated as a paragraph.

`\stanza@hang` `\stanza@hang` sets the hanging indentation to be used if the stanza line requires more than one print line. If it is known that each stanza line will fit on one print line, it is advisable to set the hanging indentation to zero. `\sza@penalty` places the specified penalty following each stanza line. By default, this facility is turned off so that no penalty is included. However, the user may initiate these penalties to indicate good and bad places in the stanza for page breaking.

```

3262 \def\stanza@line{
3263     \ifnum\value{stanzaindentrepetition}=0
3264         \parindent=\csname sza@\number\stanza@count
3265             @\endcsname\stanzaindentbase
3266     \else
3267         \managestanza@modulo
3268         \parindent=\csname sza@\number\stanza@modulo
3269             @\endcsname\stanzaindentbase
3270     \fi
3271     \pstart\stanza@hang\ignorespaces}
3272 \xdef\stanza@hang{\noexpand\leavevmode\noexpand\startlock
3273     \hangindent\expandafter
3274     \noexpand\csname sza@0@\endcsname\stanzaindentbase
3275     \hangafter\@ne}
3276 \def\sza@penalty{\count@\csname szp@\number\stanza@count @\endcsname
3277     \ifnum\count@>\@M\advance\count@-\@M\penalty-\else
3278     \penalty\fi\count@}

```

`\startstanzahook` Now we have the components of the `\stanza` macro, which appears at the start of a group of lines. This macro initializes the count and checks to see if hanging indentation and penalties are to be included. Hanging indentation suspends the line count, so that the enumeration is by verse line rather than by print line. If the print line count is desired, invoke `\let\startlock=\relax` and do the same for `\endlock`. Here and above we have used `\xdef` to make the stored macros take up a bit less space, but it also makes them more obscure to the reader. Lines of the stanza are delimited by ampersands &. The last line of the stanza must end with `\&`. For convenience the macro `\endstanzaextra` is included. The user may use this to add vertical space or penalties between stanzas.

As a further convenience, the macro `\startstanzahook` is called at the beginning of a stanza. This can be defined to do something useful.

```

3279 \let\startstanzahook\relax
3280 \let\endstanzaextra\relax
3281 \xdef\stanza{\noexpand\instanzatrue\expandafter

```

```

3282 \begingroup\startstanzahook%
3283 \catcode'\&\active\global\stanza@count\@ne\stanza@modulo\@ne
3284 \noexpand\ifnum\expandafter\noexpand
3285 \csname sza@0@\endcsname=\z@\let\noexpand\stanza@hang\relax
3286 \let\noexpand\endlock\relax\noexpand\else\interlinepenalty
3287 \@M\rightskip\z@ plus 1fil\relax\noexpand\fi\noexpand\ifnum
3288 \expandafter\noexpand\csname szp@0@\endcsname=\z@
3289 \let\noexpand\sza@penalty\relax\noexpand\fi \def\noexpand&{%
3290 \noexpand\endlock\noexpand\pend\noexpand\sza@penalty\global
3291 \advance\stanza@count\@ne\noexpand\stanza@line}\def\noexpand
3292 &{\noexpand\endlock\noexpand\pend\endgroup\noexpand\instanzafalse\expandafter\er
3293 \noexpand\stanza@line}
3294

```

`\flagstanza` Use `\flagstanza[len]{text}` at the start of a line to put *text* a distance *len* before the start of the line. The default for *len* is `\stanzaindentbase`.

```

3295 \newcommand*{\flagstanza}[2][\stanzaindentbase]{%
3296 \hskip -#1\llap{#2}\hskip #1\ignorespaces}
3297

```

The ampersand & is used to mark the end of each stanza line, except the last, which is marked with `\&`. This means that `\halign` may not be used directly within a stanza line. This does not affect macros involving alignments defined outside `\stanza` `\&`. Since these macros usurp the control sequence `\&`, the replacement `\ampersand` is defined to be used if this symbol is needed in a stanza. Also we reset the modified category codes and initialize the penalty default.

```

3298 \catcode'\&=\next
3299 \catcode'\@=\body
3300 %% \let\ampersand=\&
3301 \setstanzavalues{szp}{0}
3302

```

## 34 Arrays and tables

This is based on the work by Herbert Breger in developing `tabmac.tex`.

```

%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
% This is file tabmac.tex 1.0.
% You find here macros for tabular structures compatible with
% Edmac (authored by Lavagnino/Wujastyk). The use of the macros is
% explained in German language in file tabanlei.dvi. The macros were
% developed for Edmac 2.3, but this file has been adjusted to Edmac 3.16.
%
% ATTENTION: This file uses some Edmac control sequences (like
% \text, \footnote etc.) and redefines \morenoexpands. If you yourself
% redefined some Edmac control sequences, be careful: some adjustments
% might be necessary.
% October 1996

```

```
%
% My kind thanks to Nora G^?deke for valuable support. Any hints and
% comments are welcome, please contact Herbert Breger,
% Leibniz-Archiv, Waterloostr. 8, D -- 30169 Hannover, Germany
% Tel.: 511 - 1267 327
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
```

The original `tabmac.tex` file was void of comments or any explanatory text other than the above notice. The algorithm is Breger's. I have made some cosmetic changes to the original code and reimplemented some things so they are more LaTeX-like. All the commentary is mine, as are any mistakes or errors.

`\l@dtabnoexpands` An extended and modified version of the original additional no expansions..

```
3303 \newcommand*{\l@dtabnoexpands}{%
3304   \let\rtab=0%
3305   \let\ctab=0%
3306   \let\ltab=0%
3307   \let\rtabtext=0%
3308   \let\ltabtext=0%
3309   \let\ctabtext=0%
3310   \let\edbeforetab=0%
3311   \let\edaftertab=0%
3312   \let\edatab=0%
3313   \let\edatabell=0%
3314   \let\edatleft=0%
3315   \let\edatright=0%
3316   \let\edvertline=0%
3317   \let\edvertdots=0%
3318   \let\edrowfill=0%
3319 }
3320
```

`\l@dampcount` `\l@dampcount` is a counter for the & column dividers and `\l@dcolcount` is a  
`\l@dcolcount` counter for the columns. These were `\Undcount` and `\stellencount` respectively.

```
3321 \newcount\l@dampcount
3322 \l@dampcount=1\relax
3323 \newcount\l@dcolcount
3324 \l@dcolcount=0\relax
3325
```

`\hilfsbox` Some (temporary) helper items.

```
\hilfsskip 3326 \newbox\hilfsbox
\Hilfsbox 3327 \newskip\hilfsskip
\hilfscount 3328 \newbox\Hilfsbox
3329 \newcount\hilfscount
3330
```

30 columns should be adequate (compared to the original 60). These are the column widths. (Originally these were German spelled numbers e.g., `\eins`, `\zwei`, etc).

```

3331 \newdimen\dcoli
3332 \newdimen\dcolii
3333 \newdimen\dcoliii
3334 \newdimen\dcoliv
3335 \newdimen\dcolv
3336 \newdimen\dcolvi
3337 \newdimen\dcolvii
3338 \newdimen\dcolviii
3339 \newdimen\dcolix
3340 \newdimen\dcolx
3341 \newdimen\dcolxi
3342 \newdimen\dcolxii
3343 \newdimen\dcolxiii
3344 \newdimen\dcolxiv
3345 \newdimen\dcolxv
3346 \newdimen\dcolxvi
3347 \newdimen\dcolxvii
3348 \newdimen\dcolxviii
3349 \newdimen\dcolxix
3350 \newdimen\dcolxx
3351 \newdimen\dcolxxi
3352 \newdimen\dcolxxii
3353 \newdimen\dcolxxiii
3354 \newdimen\dcolxxiv
3355 \newdimen\dcolxxv
3356 \newdimen\dcolxxvi
3357 \newdimen\dcolxxvii
3358 \newdimen\dcolxxviii
3359 \newdimen\dcolxxix
3360 \newdimen\dcolxxx
3361 \newdimen\dcolerr    % added for error handling
3362

```

`\l@dcolwidth` This is a cunning way of storing the columnwidths indexed by the column number `\l@dcolcount`, like an array. (was `\Dimenzuordnung`)

```

3363 \newcommand{\l@dcolwidth}{\ifcase \the\l@dcolcount \dcoli %???
3364   \or \dcoli \or \dcolii \or \dcoliii
3365   \or \dcoliv \or \dcolv \or \dcolvi
3366   \or \dcolvii \or \dcolviii \or \dcolix \or \dcolx
3367   \or \dcolxi \or \dcolxii \or \dcolxiii
3368   \or \dcolxiv \or \dcolxv \or \dcolxvi
3369   \or \dcolxvii \or \dcolxviii \or \dcolxix \or \dcolxx
3370   \or \dcolxxi \or \dcolxxii \or \dcolxxiii
3371   \or \dcolxxiv \or \dcolxxv \or \dcolxxvi
3372   \or \dcolxxvii \or \dcolxxviii \or \dcolxxix \or \dcolxxx
3373   \else \dcolerr \fi}

```



3374

`\step1@dcolcount` This increments the column counter, and issues an error message if it is too large.

```
3375 \newcommand*{\step1@dcolcount}{\advance\1@dcolcount\@ne
3376 \ifnum\1@dcolcount>30\relax
3377   \led@err@TooManyColumns
3378 \fi}
3379
```

`\1@dsetmaxcolwidth` Sets the column width to the maximum value seen so far. (was `\dimenzuordnung`)

```
3380 \newcommand{\1@dsetmaxcolwidth}{%
3381   \ifdim\1@dcolwidth < \wd\hilfsbox
3382     \1@dcolwidth = \wd\hilfsbox
3383   \else \relax \fi}
3384
```

`\EDTEXT` We need to be able to modify the `\edtext` and `\critext` macros and also restore `\xedtext` their original definitions.

```
\CRITEXT 3385 \let\EDTEXT=\edtext
\xcritext 3386 \newcommand{\xedtext}[2]{\EDTEXT{#1}{#2}}
3387 \let\CRITEXT=\critext
3388 \long\def\xcritext #1#2/{\CRITEXT{#1}{#2}/}
```

`\EDLABEL` We need to be able to modify and restore the `\edlabel` macro.

```
\xedlabel 3389 \let\EDLABEL=\edlabel
3390 \newcommand*{\xedlabel}[1]{\EDLABEL{#1}}
```

`\EDINDEX` Macros supporting modification and restoration of `\edindex`.

```
\xedindex 3391 \let\EDINDEX=\edindex
\nulledindex 3392 \if1@dmemoir
3393   \newcommand{\xedindex}{\@bsphack%
3394     \ifnextchar [{\1@d@index}{\1@d@index[\jobname]}}
3395   \newcommand{\nulledindex}[2][\jobname]{\@bsphack\@esphack}
3396 \else
3397   \newcommand{\xedindex}{\@bsphack%
3398     \doedindexlabel
3399     \begingroup
3400     \@sanitize
3401     \@wredindex}
3402   \newcommand{\nulledindex}[1]{\@bsphack\@esphack}
3403 \fi
3404
```

`\@line@num` Macro supporting restoration of `\linenum`.

```
3405 \let\@line@num=\linenum
```

`\1@dgobbledarg` `\1@dgobbledarg` replaces its delineated argument by `\relax` (was `\verschwinden`).

`\1@dgonblearg` `\1@dgonblearg{<arg>}` replaces its argument by `\relax`.

```
3406 \def\1@dgonbledarg #1/{\relax}
```

```

3407 \newcommand*{\l@dgobblearg}[1]{\relax}
3408
\Relax
\NEXT 3409 \let\Relax=\relax
\@hilfs@count 3410 \let\NEXT=\next
3411 \newcount\@hilfs@count
3412
\measuremcell Measure (recursively) the width required for a math cell. (was \messen)
3413 \def\measuremcell #1{%
3414     \ifx #1\ \ifnum\l@dc@count=0\let\NEXT\relax%
3415         \else\l@dcheckcols%
3416             \l@dc@count=0%
3417             \let\NEXT\measuremcell%
3418         \fi%
3419     \else\setbox\hilfsbox=\hbox{$\displaystyle{#1}$}%
3420         \step\l@dc@count%
3421         \l@dsetmaxcolwidth%
3422         \let\NEXT\measuremcell%
3423     \fi\NEXT}
3424
\measuretcell Measure (recursively) the width required for a text cell. (was \messentext)
3425 \def\measuretcell #1{%
3426     \ifx #1\ \ifnum\l@dc@count=0\let\NEXT\relax%
3427         \else\l@dcheckcols%
3428             \l@dc@count=0%
3429             \let\NEXT\measuretcell%
3430         \fi%
3431     \else\setbox\hilfsbox=\hbox{#1}%
3432         \step\l@dc@count%
3433         \l@dsetmaxcolwidth%
3434         \let\NEXT\measuretcell%
3435     \fi\NEXT}
3436
\measuremrow Measure (recursively) the width required for a math row. (was \Messen)
3437 \def\measuremrow #1\{%
3438     \ifx #1\let\NEXT\relax%
3439     \else\measuremcell #1\&\&\&%
3440         \let\NEXT\measuremrow%
3441     \fi\NEXT}
\measuretrow Measure (recursively) the width required for a text row. (was \Messentext)
3442 \def\measuretrow #1\{%
3443     \ifx #1\let\NEXT\relax%
3444     \else\measuretcell #1\&\&\&%
3445         \let\NEXT\measuretrow%

```

```

3446   \fi\NEXT}
3447

```

`\edtabcolsep` The length `\edtabcolsep` controls the distance between columns. (was `\abstand`)

```

3448 \newskip\edtabcolsep
3449 \global\edtabcolsep=10pt
3450

```

`\NEXT`

```

\Next 3451 \let\NEXT\relax
3452 \let\Next=\next

```

`\variab`

```

3453 \newcommand{\variab}{\relax}
3454

```

`\l@dcheckcols` Check that the number of columns is consistent. (was `\tabfehlermeldung`)

```

3455 \newcommand*{\l@dcheckcols}{%
3456   \ifnum\l@dcolcount=1\relax
3457   \else
3458     \ifnum\l@dampcount=1\relax
3459     \else
3460       \ifnum\l@dcolcount=\l@dampcount\relax
3461       \else
3462         \l@d@err@UnequalColumns
3463       \fi
3464     \fi
3465     \l@dampcount=\l@dcolcount
3466   \fi}
3467

```

`\l@dmodforcritext` Modify and restore various macros for when `\critext` is used.

```

\l@drestoreforcritext 3468 \newcommand{\l@dmodforcritext}{%
3469   \let\critext\relax%
3470   \def\do##1{\global\csletcs{##1footnote}{\l@dgobbledarg}}
3471   \dolistloop{\@series}%
3472   \let\edindex\nulledindex%
3473   \let\linenum@gobble}
3474 \newcommand{\l@drestoreforcritext}{%
3475   \def\do##1{\csdef{##1footnote}##1##2/{\csuse{##1@footnote}{##1}{##2}}}
3476   \dolistloop{\@series}%
3477   \let\edindex\xedndex}
3478

```

`\l@dmodforedtext` Modify and restore various macros for when `\edtext` is used.

```

\l@drestoreforedtext 3479 \newcommand{\l@dmodforedtext}{%
3480   \let\edtext\relax
3481   \def\do##1{\global\csletcs{##1footnote}{\l@dgobblearg}}
3482   \dolistloop{\@series}%

```

```

3483 \let\edindex\nulledindex
3484 \let\linenum@gobble}
3485 \newcommand{\l@drestoreforedtext}{%
3486 \def\do##1{\csgdef{##1footnote}##1{\csuse{##1@footnote}{##1}}}
3487 \dolistloop{\@series}%
3488 \let\edindex\xedndex}

```

\l@dnnullfills Nullify and restore some column fillers, etc.

```

\l@drestorefills 3489 \newcommand{\l@dnnullfills}{%
3490 \def\edlabel##1{}%
3491 \def\edrowfill##1##2##3{%
3492 }
3493 \newcommand{\l@drestorefills}{%
3494 \def\edrowfill##1##2##3{\@EDROWFILL@{##1}{##2}{##3}}%
3495 }
3496

```

The original definition of \rverteilen and friends (‘verteilen’ is approximately ‘distribute’) was along the lines:

```

\def\rverteilen #1&{\def\label##1{%
\ifx #1! \ifnum\l@dcolcount=0%\removelastskip
\let\Next\relax%
\else\l@dcolcount=0%
\let\Next=\rverteilen%
\fi%
\else%
\footnoteverschw%
\step\l@dcolcount%
\setbox\hilfsbox=\hbox{$\displaystyle{#1}$}%
\let\critext=\xcritext\let\Dfootnote=D@@footnote
\let\Afootnote=A@@footnote\let\Bfootnote=B@@footnote
\let\Cfootnote=C@@footnote\let\linenum=@line@num%
\hilfsskip=\Dimenzuordnung%
\advance\hilfsskip by -\wd\hilfsbox
\def\label##1{\xlabel{##1}}%
\hskip\hilfsskip$\displaystyle{#1}$%
\hskip\edtabcolsep%
\let\Next=\rverteilen%
\fi\Next}

```

where the lines

```

\let\critext=\xcritext\let\Dfootnote=D@@footnote
\let\Afootnote=A@@footnote\let\Bfootnote=B@@footnote
\let\Cfootnote=C@@footnote\let\linenum=@line@num%
\hilfsskip=\Dimenzuordnung%
\advance\hilfsskip by -\wd\hilfsbox
\def\label##1{\xlabel{##1}}%

```

were common across the several *\*verteilen\** macros, and also

```
\def\footnoteverschw{%
  \let\critext\relax
  \let\Afootnote=\verschwinden
  \let\Bfootnote=\verschwinden
  \let\Cfootnote=\verschwinden
  \let\Dfootnote=\verschwinden
  \let\linenum=\@gobble}
```

`\letsforverteilen` Gathers some lets and other code that is common to the *\*verteilen\** macros.

```
3497 \newcommand{\letsforverteilen}{%
3498   \let\critext\xcritext
3499   \let\edtext\xedtext
3500   \let\edindex\xedindex
3501   \def\do##1{\global\csletcs{##1footnote}{##1@footnote}}
3502   \dolistloop{\@series}%
3503   \let\linenum\@line@num
3504   \hilfsskip=\l@dcolwidth%
3505   \advance\hilfsskip by -\wd\hilfsbox
3506   \def\edlabel##1{\xedlabel{##1}}
3507 }
```

`\setmcellright` Typeset (recursively) cells of display math right justified. (was `\rverteilen`)

```
3508 \def\setmcellright #1&{\def\edlabel##1{%
3509   \let\edindex\nulledindex
3510   \ifx #1\ \ifnum\l@dcolcount=0%\removelastskip
3511     \let\Next\relax%
3512   \else\l@dcolcount=0%
3513     \let\Next=\setmcellright%
3514   \fi%
3515   \else%
3516     \disablel@dtabfeet%
3517     \step1@dcolcount%
3518     \setbox\hilfsbox=\hbox{$\displaystyle{#1}$}%
3519     \letsforverteilen%
3520     \hskip\hilfsskip$\displaystyle{#1}$%
3521     \hskip\edtabcolsep%
3522     \let\Next=\setmcellright%
3523   \fi\Next}
3524 }
```

`\settcclright` Typeset (recursively) cells of text right justified. (was `\rverteilentext`)

```
3525 \def\settcclright #1&{\def\edlabel##1{%
3526   \let\edindex\nulledindex
3527   \ifx #1\ \ifnum\l@dcolcount=0%\removelastskip
3528     \let\Next\relax%
3529   \else\l@dcolcount=0%
3530     \let\Next=\settcclright%
3531   \fi\Next}
```

```

3531         \fi%
3532     \else%
3533         \disablel@dtabfeet%
3534         \step1@dcolcount%
3535         \setbox\hilfsbox=\hbox{#1}%
3536         \letsforverteilen%
3537         \hskip\hilfsskip#1%
3538         \hskip\edtabcolsep%
3539         \let\Next=\settccllright%
3540     \fi\Next}

```

`\setmcellleft` Typeset (recursively) cells of display math left justified. (was `\lverteilen`)

```

3541 \def\setmcellleft #1&{\def\edlabel##1}%
3542         \let\edindex\nulledindex
3543     \ifx #1\\ \ifnum\l@dcolcount=0 \let\Next\relax%
3544         \else\l@dcolcount=0%
3545         \let\Next=\setmcellleft%
3546         \fi%
3547     \else \disablel@dtabfeet%
3548         \step1@dcolcount%
3549         \setbox\hilfsbox=\hbox{$\displaystyle{#1}$}%
3550         \letsforverteilen
3551         $\displaystyle{#1}$\hskip\hilfsskip\hskip\edtabcolsep%
3552         \let\Next=\setmcellleft%
3553     \fi\Next}
3554

```

`\settcclleft` Typeset (recursively) cells of text left justified. (was `\lverteilentext`)

```

3555 \def\settcclleft #1&{\def\edlabel##1}%
3556         \let\edindex\nulledindex
3557     \ifx #1\\ \ifnum\l@dcolcount=0 \let\Next\relax%
3558         \else\l@dcolcount=0%
3559         \let\Next=\settcclleft%
3560         \fi%
3561     \else \disablel@dtabfeet%
3562         \step1@dcolcount%
3563         \setbox\hilfsbox=\hbox{#1}%
3564         \letsforverteilen
3565         #1\hskip\hilfsskip\hskip\edtabcolsep%
3566         \let\Next=\settcclleft%
3567     \fi\Next}

```

`\setmcellcenter` Typeset (recursively) cells of display math centered. (was `\zverteilen`)

```

3568 \def\setmcellcenter #1&{\def\edlabel##1}%
3569         \let\edindex\nulledindex
3570     \ifx #1\\ \ifnum\l@dcolcount=0\let\Next\relax%
3571         \else\l@dcolcount=0%
3572         \let\Next=\setmcellcenter%
3573     \fi%

```

```

3574 \else \disablel@dtabfeet%
3575 \stepl@dcolcount%
3576 \setbox\hilfsbox=\hbox{$\displaystyle{#1}$}%
3577 \letsforverteilen%
3578 \hskip 0.5\hilfsskip$\displaystyle{#1}$\hskip0.5\hilfsskip%
3579 \hskip\edtabcolsep%
3580 \let\Next=\setmcellcenter%
3581 \fi\Next}
3582

```

**\settcclcenter** Typeset (recursively) cells of text centered. (new)

```

3583 \def\settcclcenter #1{\def\edlabel##1{%
3584 \let\edindex\nulledindex
3585 \ifx #1\ \ifnum\l@dcolcount=0 \let\Next\relax%
3586 \else\l@dcolcount=0%
3587 \let\Next=\settcclcenter%
3588 \fi%
3589 \else \disablel@dtabfeet%
3590 \stepl@dcolcount%
3591 \setbox\hilfsbox=\hbox{#1}%
3592 \letsforverteilen%
3593 \hskip 0.5\hilfsskip #1\hskip 0.5\hilfsskip%
3594 \hskip\edtabcolsep%
3595 \let\Next=\settcclcenter%
3596 \fi\Next}
3597

```

**\NEXT**

```

3598 \let\NEXT=\relax
3599

```

**\setmrowright** Typeset (recursively) rows of right justified math. (was \rsetzen)

```

3600 \def\setmrowright #1\{%
3601 \ifx #1& \let\NEXT\relax
3602 \else \centerline{\setmcellright #1&\&\&}
3603 \let\NEXT=\setmrowright
3604 \fi\NEXT}

```

**\settroright** Typeset (recursively) rows of right justified text. (was \rsetzentext)

```

3605 \def\settroright #1\{%
3606 \ifx #1& \let\NEXT\relax
3607 \else \centerline{\settcclright #1&\&\&}
3608 \let\NEXT=\settroright
3609 \fi\NEXT}
3610

```

**\setmrowleft** Typeset (recursively) rows of left justified math. (was \lsetzen)

```

3611 \def\setmrowleft #1\{%
3612 \ifx #1&\let\NEXT\relax

```

```

3613 \else \centerline{\setmcellleft #1\\&\\&}
3614 \let\NEXT=\setmrowleft
3615 \fi\NEXT}

```

`\settrorleft` Typeset (recursively) rows of left justified text. (was `\lsetzentext`)

```

3616 \def\settrorleft #1\\{%
3617 \ifx #1& \let\NEXT\relax
3618 \else \centerline{\settrcellleft #1\\&\\&}
3619 \let\NEXT=\settrorleft
3620 \fi\NEXT}
3621

```

`\setmrowcenter` Typeset (recursively) rows of centered math. (was `\zsetzen`)

```

3622 \def\setmrowcenter #1\\{%
3623 \ifx #1& \let\NEXT\relax%
3624 \else \centerline{\setmcellcenter #1\\&\\&}
3625 \let\NEXT=\setmrowcenter
3626 \fi\NEXT}

```

`\settrorcenter` Typeset (recursively) rows of centered text. (new)

```

3627 \def\settrorcenter #1\\{%
3628 \ifx #1& \let\NEXT\relax
3629 \else \centerline{\settrcellcenter #1\\&\\&}
3630 \let\NEXT=\settrorcenter
3631 \fi\NEXT}
3632

```

`\nullsetzen` (was `\nullsetzen`)

```

3633 \newcommand{\nullsetzen}{%
3634 \stepl@dc@colcount%
3635 \l@dc@colwidth=0pt%
3636 \ifnum\l@dc@colcount=30\let\NEXT\relax%
3637 \l@dc@colcount=0\relax
3638 \else\let\NEXT\nullsetzen%
3639 \fi\NEXT}
3640

```

`\edatleft` `\edatleft[ $\langle math \rangle$ ]{ $\langle symbol \rangle$ }{ $\langle len \rangle$ }` (combination and generalisation of original `\Seklam` and `\Seklamgl`). Left  $\langle symbol \rangle$ , 2 $\langle len \rangle$  high with prepended  $\langle math \rangle$  vertically centered.

```

3641 \newcommand{\edatleft}[3][\@empty]{%
3642 \ifx#1\@empty
3643 \vbox to 10pt{\vss\hbox{$\left#2\vrule width0pt height #3
3644 \depth 0pt \right. $\hss}\vfil}
3645 \else
3646 \vbox to 4pt{\vss\hbox{$#1\left#2\vrule width0pt height #3
3647 \depth 0pt \right. $\}\vfil}
3648 \fi}

```



`\edatright` `\edatright[ $\langle math \rangle$ ]{ $\langle symbol \rangle$ }{ $\langle len \rangle$ }` (combination and generalisation of original `\seklam` and `\seklamgl`). Right  $\langle symbol \rangle$ ,  $2\langle len \rangle$  high with appended  $\langle math \rangle$  vertically centered.

```

3649 \newcommand{\edatright}[3][\@empty]{%
3650   \ifx#1\@empty
3651     \vbox to 10pt{\vss\hbox{$\left.\vrule width0pt height #3
3652       depth 0pt \right#2 $\hss\} \vfil}
3653   \else
3654     \vbox to 4pt{\vss\hbox{$\left.\vrule width0pt height #3
3655       depth 0pt \right#2 #1 $\} \vfil}
3656   \fi}
3657
\edvertline \edvertline{ $\langle len \rangle$ } vertical line  $\langle len \rangle$  high. (was \sestrich)
3658 \newcommand{\edvertline}[1]{\vbox to 8pt{\vss\hbox{\vrule height #1}\vfil}}
3659
\edvertdots \edvertdots{ $\langle len \rangle$ } vertical dotted line  $\langle len \rangle$  high. (was \sepunkte)
3660 \newcommand{\edvertdots}[1]{\vbox to 1pt{\vss\vbox to #1%
3661   {\cleaders\hbox{$\m@th\hbox{.}\vbox to 0.5em{ }\$}\vfil}}}
3662

```

I don't know if this is relevant here, and I haven't tried it, but the following appeared on CTT.

From: mdw@nsict.org (Mark Wooding)  
 Newsgroups: comp.text.tex  
 Subject: Re: Dotted line  
 Date: 13 Aug 2003 13:51:14 GMT

Alexis Eisenhofer <alexis@eisenhofer.de> wrote:  
 > Can anyone provide me with the LaTeX command for a vertical dotted line?

How dotted? Here's the basic rune.

```

\newbox\linedotbox
\setbox\linedotbox=\vbox{...}
\leaders\copy\linedotbox\vskip2in

```

For just dots, this works:

```

\setbox\linedotbox=\vbox{\hbox{\normalfont.}\kern2pt}

```

For dashes, something like

```

\setbox\linedotbox=\vbox{\leaders\vrule\vskip2pt\vskip2pt}

```

is what you want. (Adjust the '2pt' values to taste. The first one is the length of the dashes, the second is the length of the gaps.)

For dots in mid-paragraph, you need to say something like

```

\lower10pt\vbox{\leaders\copy\linedotbox\vskip2in}

```

which is scungy but works.

-- [mdw]

```

\edfilldimen A length. (was \klamdimen)
3663 \newdimen\edfilldimen
3664 \edfilldimen=0pt
3665

\c@addcolcount A counter to hold the number of a column. We use a roman number so that we
\theadcolcount can grab the column dimension from \dcol....
3666 \newcounter{addcolcount}
3667 \renewcommand{\theadcolcount}{\roman{addcolcount}}

\l@dtabaddcols \l@dtabaddcols{<startcol>}{<endcol>} adds the widths of the columns <startcol>
through <endcol> to \edfilldimen. It is a LaTeX style reimplementaion of the
original \@add@.
3668 \newcommand{\l@dtabaddcols}[2]{%
3669   \l@dccheckstartend{#1}{#2}%
3670   \ifl@dstartendok
3671     \setcounter{addcolcount}{#1}%
3672     \@whilenum \value{addcolcount}<#2\relax \do
3673     {\advance\edfilldimen by \the \csname dcol\theadcolcount\endcsname
3674      \advance\edfilldimen by \edtabcolsep
3675      \stepcounter{addcolcount}}%
3676     \advance\edfilldimen by \the \csname dcol\theadcolcount\endcsname
3677   \fi
3678 }
3679

\ifl@dstartendok \l@dccheckstartend{<startcol>}{<endcol>} checks that the values of <startcol> and
\l@dccheckstartend <endcol> are sensible. If they are then \ifl@dstartendok is set TRUE, otherwise
it is set FALSE.
3680 \newif\ifl@dstartendok
3681 \newcommand{\l@dccheckstartend}[2]{%
3682   \l@dstartendoktrue
3683   \ifnum #1<\@ne
3684     \l@dstartendokfalse
3685     \led@err@LowStartColumn
3686   \fi
3687   \ifnum #2>30\relax
3688     \l@dstartendokfalse
3689     \led@err@HighEndColumn
3690   \fi
3691   \ifnum #1>#2\relax
3692     \l@dstartendokfalse
3693     \led@err@ReverseColumns
3694   %% \eledmac@error{Start column is greater than end column}{\@ehc}%
3695   \fi

```

3696 }  
3697

`\edrowfill` `\edrowfill{<startcol>}{<endcol>}` fill fills columns `<startcol>` to `<endcol>` inclusive with `<fill>` (e.g. `\hrulefill`, `\upbracefill`). This is a LaTeX style reimplementa-  
`\@edrowfill@` tion and generalization of the original `\waklam`, `\Waklam`, `\waklamec`, `\wastricht`  
`\@EDROWFILL@` and `\wapunktet` macros.

3698 `\newcommand*{\edrowfill}[3]{%`  
3699 `\l@dtabaddcols{#1}{#2}%`  
3700 `\hb@xt@ \the\l@dcollwidth{\hb@xt@ \the\edfilldimen{#3}\hss}}`  
3701 `\let\@edrowfill@=\edrowfill`  
3702 `\def\@EDROWFILL@#1#2#3{\@edrowfill@{#1}{#2}{#3}}`  
3703

`\edbeforetab` The macro `\edbeforetab{<text>}{<math>}` puts `<text>` at the left margin be-  
`\edaftertab` fore array cell entry `<math>`. Conversely, the macro `\edaftertab{<math>}{<text>}`  
puts `<text>` at the right margin after array cell entry `<math>`. `\edbeforetab` should  
be in the first column and `\edaftertab` in the last column. The following macros  
support these.

`\leftltab` `\leftltab{<text>}` for `\edbeforetab` in `\ltab`. (was `\linksltab`)

3704 `\newcommand{\leftltab}[1]{%`  
3705 `\hb@xt@\z@\vbox{\edtabindent%`  
3706 `\moveleft\Hilfsskip\hbox{\ #1}}\hss}}`  
3707

`\leftrtab` `\leftrtab{<text>}{<math>}` for `\edbeforetab` in `\rtab`. (was `\linksrtab`)

3708 `\newcommand{\leftrtab}[2]{%`  
3709 `\#2\hb@xt@\z@\vbox{\edtabindent%`  
3710 `\advance\Hilfsskip by\dcoli%`  
3711 `\moveleft\Hilfsskip\hbox{\ #1}}\hss}}`  
3712

`\leftctab` `\leftctab{<text>}{<math>}` for `\edbeforetab` in `\ctab`. (was `\linksztab`)

3713 `\newcommand{\leftctab}[2]{%`  
3714 `\hb@xt@\z@\vbox{\edtabindent\l@dcollcount=\l@dampcount%`  
3715 `\advance\Hilfsskip by 0.5\dcoli%`  
3716 `\setbox\hilfsbox=\hbox{\def\edlabel##1{}}`  
3717 `\disablel@dtabfeet$\displaystyle{#2}$}`  
3718 `\advance\Hilfsskip by -0.5\wd\hilfsbox%`  
3719 `\moveleft\Hilfsskip\hbox{\ #1}}\hss}%`  
3720 `\#2}`  
3721

`\rightctab` `\rightctab{<math>}{<text>}` for `\edaftertab` in `\ctab`. (was `\rechtsztab`)

3722 `\newcommand{\rightctab}[2]{%`  
3723 `\setbox\hilfsbox=\hbox{\def\edlabel##1{}}`  
3724 `\disablel@dtabfeet#2}\l@dampcount=\l@dcollcount%`  
3725 `\#1\hb@xt@\z@\vbox{\edtabindent\l@dcollcount=\l@dampcount%`

```

3726 \advance\Hilfsskip by 0.5\l@dcwidth%
3727 \advance\Hilfsskip by -\wd\hilfsbox%
3728 \setbox\hilfsbox=\hbox{\def\edlabel##1}%
3729 \disablel@dtabfeet$\displaystyle{#1}$}%
3730 \advance\Hilfsskip by -0.5\wd\hilfsbox%
3731 \advance\Hilfsskip by \edtabcolsep%
3732 \moveright\Hilfsskip\hbox{ #2}\hss}%
3733 }
3734

```

`\rightltab` `\rightltab{<math>}<{<text>}` for `\edaftertab` in `\ltab`. (was `\rechtsltab`)

```

3735 \newcommand{\rightltab}[2]{%
3736 \setbox\hilfsbox=\hbox{\def\edlabel##1}%
3737 \disablel@dtabfeet#2}\l@dampcount=\l@dcwidth%
3738 #1\hb@xt@{\z@{\vbox{\edtabindent\l@dcwidth=\l@dampcount%
3739 \advance\Hilfsskip by\l@dcwidth%
3740 \advance\Hilfsskip by-\wd\hilfsbox%
3741 \setbox\hilfsbox=\hbox{\def\edlabel##1}%
3742 \disablel@dtabfeet$\displaystyle{#1}$}%
3743 \advance\Hilfsskip by-\wd\hilfsbox%
3744 \advance\Hilfsskip by\edtabcolsep%
3745 \moveright\Hilfsskip\hbox{ #2}\hss}%
3746 }
3747

```

`\rightrtab` `\rightrtab{<math>}<{<text>}` for `\edaftertab` in `\rtab`. (was `\rechtsrtab`)

```

3748 \newcommand{\rightrtab}[2]{%
3749 \setbox\hilfsbox=\hbox{\def\edlabel##1}%
3750 \disablel@dtabfeet#2}%
3751 #1\hb@xt@{\z@{\vbox{\edtabindent%
3752 \advance\Hilfsskip by-\wd\hilfsbox%
3753 \advance\Hilfsskip by\edtabcolsep%
3754 \moveright\Hilfsskip\hbox{ #2}\hss}%
3755 }
3756

```

`\rtab` `\rtab{<body>}` typesets `<body>` as an array with the entries right justified. (was `\edbeforetab` `\rtab`) (Here and elsewhere, `\edbeforetab` and `\edaftertab` were originally `\edbeforetab` and `\danach`) The original `\rtab` and friends included a fair bit of common code which I have extracted into macros.

The process is first to measure the `<body>` to get the column widths, and then in a second pass to typeset the body.

```

3757 \newcommand{\rtab}[1]{%
3758 \l@dnnullfills
3759 \def\edbeforetab##1##2{\leftltab{##1}{##2}}%
3760 \def\edaftertab##1##2{\rightltab{##1}{##2}}%
3761 \measurebody{#1}%
3762 \l@drecoverfills
3763 \variab

```

```

3764 \setmrowright #1\\&\\%
3765 \enablel@dtabfeet}
3766

```

`\measurebody` `\measurebody{⟨body⟩}` measures the array `⟨body⟩`.

```

3767 \newcommand{\measurebody}[1]{%
3768 \disablel@dtabfeet%
3769 \l@dcolcount=0%
3770 \nullsetzen%
3771 \l@dcolcount=0
3772 \measuremrow #1\\&\\%
3773 \global\l@dampcount=1}
3774

```

`\rtabtext` `\rtabtext{⟨body⟩}` typesets `⟨body⟩` as a tabular with the entries right justified. (was `\rtabtext`)

```

3775 \newcommand{\rtabtext}[1]{%
3776 \l@dnnullfills
3777 \measuretbody{#1}%
3778 \l@drestorefills
3779 \variab
3780 \settroright #1\\&\\%
3781 \enablel@dtabfeet}
3782

```

`\measuretbody` `\measuretbody{⟨body⟩}` measures the tabular `⟨body⟩`.

```

3783 \newcommand{\measuretbody}[1]{%
3784 \disablel@dtabfeet%
3785 \l@dcolcount=0%
3786 \nullsetzen%
3787 \l@dcolcount=0
3788 \measuretrorow #1\\&\\%
3789 \global\l@dampcount=1}
3790

```

`\ltab` Array with entries left justified. (was `\ltab`)

```

\edbeforetab 3791 \newcommand{\ltab}[1]{%
\edaftertab 3792 \l@dnnullfills
3793 \def\edbeforetab##1##2{\leftltab{##1}{##2}}%
3794 \def\edaftertab##1##2{\rightltab{##1}{##2}}%
3795 \measuretbody{#1}%
3796 \l@drestorefills
3797 \variab
3798 \setmrowleft #1\\&\\%
3799 \enablel@dtabfeet}
3800

```

`\ltabtext` Tabular with entries left justified. (was `\ltabtext`)

```

3801 \newcommand{\ltabtext}[1]{%

```

```

3802 \l@dnnullfills
3803 \measuretbody{#1}%
3804 \l@drestorefills
3805 \variab
3806 \settrorleft #1\\&\\%
3807 \enablel@dtabfeet}
3808

\ctab Array with centered entries. (was \ztab)
\edbeforetab 3809 \newcommand{\ctab}[1]{%
\edaftertab 3810 \l@dnnullfills
3811 \def\edbeforetab##1##2{\leftctab{##1}{##2}}%
3812 \def\edaftertab##1##2{\rightctab{##1}{##2}}%
3813 \measuretbody{#1}%
3814 \l@drestorefills
3815 \variab
3816 \setmrowcenter #1\\&\\%
3817 \enablel@dtabfeet}
3818

\ctabtext Tabular with entries centered. (new)
3819 \newcommand{\ctabtext}[1]{%
3820 \l@dnnullfills
3821 \measuretbody{#1}%
3822 \l@drestorefills
3823 \variab
3824 \settrorcenter #1\\&\\%
3825 \enablel@dtabfeet}
3826

\spreadtext (was \breitertext)
3827 \newcommand{\spreadtext}[1]{%\l@dcolcount=\l@dampcount%
3828 \hb@xt@ \the\l@dcolwidth{\hbox{#1}\hss}}

\spreadmath (was \breiter, 'breiter' = 'broadly')
3829 \newcommand{\spreadmath}[1]{%
3830 \hb@xt@ \the\l@dcolwidth{\hbox{$\displaystyle{#1}$}\hss}}
3831

I have left the remaining TABMAC alone, apart from changing some names. I'm
not yet sure what they do or how they do it. Authors should not use any of these
as they are likely to be mutable.

\tabellzwischen (was \tabellzwischen)
3832 \def\tabellzwischen #1&{%
3833 \ifx #1\\ \let\NEXT\relax \l@dcolcount=0
3834 \else \step\l@dcolcount%
3835 \l@dcolwidth = #1 mm
3836 \let\NEXT=\tabellzwischen

```

```

3837     \fi \NEXT }
3838

```

\edatabell For example \edatabell 4 & 19 & 8 \\ specifies 3 columns with widths of 4, 19, and 8mm. (was \atabell)

```

3839 \def\edatabell #1\\{%
3840     \tabellzwischen #1&\\&}

```

\Setzen (was \Setzen, 'setzen' = 'set')

```

3841 \def\Setzen #1{%
3842     \ifx #1\relax \let\NEXT=\relax
3843     \else \stepl@dc@count%
3844         \let\tabelskip=\l@dc@width
3845         \EDTAB #1|
3846         \let\NEXT=\Setzen
3847     \fi\NEXT}
3848

```

\EDATAB (was \ATAB)

```

3849 \def\EDATAB #1\\{%
3850     \ifx #1\Relax \centerline{\Setzen #1\relax&}
3851         \let\Next\relax
3852     \else \centerline{\Setzen #1&\relax&}
3853         \let\Next=\EDATAB
3854     \fi\Next}

```

\edatab (was \atab)

```

3855 \newcommand{\edatab}[1]{%
3856     \variab%
3857     \EDATAB #1\\Relax\\}
3858

```

\HILFSskip More helpers.

```

\Hilfsskip 3859 \newskip\HILFSskip
3860 \newskip\Hilfsskip
3861

```

\EDTABINDENT (was \TABINDENT)

```

3862 \newcommand{\EDTABINDENT}{%
3863     \ifnum\l@dc@count=30\let\NEXT\relax\l@dc@count=0%
3864     \else\stepl@dc@count%
3865         \advance\Hilfsskip by\l@dc@width%
3866         \ifdim\l@dc@width=0pt\advance\hilfscount\@ne
3867         \else\advance\Hilfsskip by \the\hilfscount\edtabcolsep%
3868         \hilfscount=1\fi%
3869         \let\NEXT=\EDTABINDENT%
3870     \fi\NEXT}%

```

```

\edtabindent (was \tabindent)
3871 \newcommand{\edtabindent}{%
3872     \l@dcolcount=0\relax
3873     \Hilfsskip=Opt%
3874     \hilfscount=1\relax
3875     \EDTABINDENT%
3876     \hilfsskip=\hsize%
3877     \advance\hilfsskip -\Hilfsskip%
3878     \Hilfsskip=0.5\hilfsskip%
3879 }%
3880

\EDTAB (was \TAB)
3881 \def\EDTAB #1|#2|{%
3882     \setbox\tabhilfbox=\hbox{$\displaystyle{#1}$}%
3883     \setbox\tabHilfbox=\hbox{$\displaystyle{#2}$}%
3884     \advance\tabelskip -\wd\tabhilfbox%
3885     \advance\tabelskip -\wd\tabHilfbox%
3886     \unhbox\tabhilfbox\hskip\tabelskip%
3887     \unhbox\tabHilfbox}%
3888

\EDTABtext (was \TABtext)
3889 \def\EDTABtext #1|#2|{%
3890     \setbox\tabhilfbox=\hbox{#1}%
3891     \setbox\tabHilfbox=\hbox{#2}%
3892     \advance\tabelskip -\wd\tabhilfbox%
3893     \advance\tabelskip -\wd\tabHilfbox%
3894     \unhbox\tabhilfbox\hskip\tabelskip%
3895     \unhbox\tabHilfbox}%

\tabhilfbox Further helpers.
\tabHilfbox
3896 \newbox\tabhilfbox
3897 \newbox\tabHilfbox
3898

%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
% That finishes tabmac
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%

edarrayl The ‘environment’ forms for \ltab, \ctab and \rtab.
edarrayc 3899 \newenvironment{edarrayl}{\l@dcollect@body\ltab}{\}
edarrayr 3900 \newenvironment{edarrayc}{\l@dcollect@body\ctab}{\}
3901 \newenvironment{edarrayr}{\l@dcollect@body\rtab}{\}
3902

edtabularl The ‘environment’ forms for \ltabtext, \ctabtext and \rtabtext.
edtabularc 3903 \newenvironment{edtabularl}{\l@dcollect@body\ltabtext}{\}
edtabularr

```



```

\usingcritext  Declarations for using \critext{...}/ or using \edtext{}{} inside tabulars.
\disablel@dtabfeet  The default at this point is for \edtext.
\enablel@dtabfeet 3907 \newcommand{\usingcritext}{%
    \usingedtext 3908 \def\disablel@dtabfeet{\l@dmodforcritext}%
    3909 \def\enablel@dtabfeet{\l@drestoreforcritext}}
    3910 \newcommand{\usingedtext}{%
    3911 \def\disablel@dtabfeet{\l@dmodforedtext}%
    3912 \def\enablel@dtabfeet{\l@drestoreforedtext}}
    3913
    3914 \usingedtext
    3915

```

## Appendix A Migration from ledmac to eledmac

In eledmac, some changes were made in the code to allow for easy customization. This can cause problems for people who have made their own customizations. The next sections explain how to correct this.

If you created your own series using `\addfootins` and `\addfootinsX`, you should instead use the `\newseries` command (see 4.6 p.22). You must delete your `\Xfootnote` command.

If you customized the `\XXXXXfmt` command, you should see if commands for display options (4.3 p.17) and options in `\Xfootnote` (4.1 p.15) can't do the same things. If not, you can add a new ticket in Github to request a new function it<sup>31</sup>.

If for some reason you don't want to make the modifications to use eledmac new functions, you can continue to use your own `\XXXXXfmt` command, but you must replace:

```
\renewcommand*{XXXXfmt}[3]
```

with

```
\renewcommandx*{XXXXfmt}[4][4=Z]
```

If you don't do that, you will see a spurious `[X]`, where X is series letter.

If you used a `\protect` command inside a `\footnote` command inside a numbered section, you must change the `\protect` to `\noexpand`. If you don't, the command after the `\protect` won't be displayed.

---

<sup>31</sup><https://github.com/maieul/ledmac/issues>

## References

- [Bre96] Herbert Breger. **TABMAC**. October 1996. (Available from CTAN in `macros/plain/contrib/tabmac`)
- [Bur01] John Burt. ‘Typesetting critical editions of poetry’. *TUGboat*, **22**, 4, pp 353–361, December 2001. (Code available from CTAN in `macros/latex/contrib/poemscol`)
- [Eck03] Matthias Eckermann. *The Parallel-Package*. April 2003. (Available from CTAN in `macros/latex/contrib/parallel`)
- [Fai03] Robin Fairbairns. *footmisc — a portmanteau package for customising footnotes in LaTeX*. February 2003. (Available from CTAN in `macros/latex/contrib/footmisc`)
- [LW90] John Lavagnino and Dominik Wujastyk. ‘An overview of EDMAC: a PLAIN TeX format for critical editions’. *TUGboat*, **11**, 4, pp. 623–643, November 1990. (Code available from CTAN in `macros/plain/contrib/edmac`)
- [Lüc03] Uwe Lück. ‘ednotes — critical edition typesetting with LaTeX’. *TUGboat*, **24**, 2, pp. 224–236, 2003. (Code available from CTAN in `macros/latex/contrib/ednotes`)
- [Sul92] Wayne G. Sullivan. *The file edstanza.doc*. June 1992. (Available from CTAN in `macros/plain/contrib/edmac`)
- [Wil02] Peter Wilson. *The memoir class for configurable typesetting*. November 2002. (Available from CTAN in `macros/latex/contrib/memoir`)
- [Wil04] Peter Wilson and Maïeul Rouquette. *Parallel typesetting for critical editions: the eledpar package*. December 2004. (Available from CTAN in `macros/latex/contrib/ledmmac`)

## Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in *roman* refer to the code lines where the entry is used.

<b>Symbols</b>	3233, 3234, 3283, 3292, 3298, 3300
<code>\&amp;</code> .....	22, 3229,

- \@oline ..... 1687
- \@wrindexm@m .. 3150, 3155, 3158, 3182
- \@EDROWFILL@ ..... 3494, 3698
- \@M ..... 1687, 3277, 3287
- \@MM ..... 1399
- \@adv ..... 575, 736
- \@arabic ..... 876
- \@aux ..... 2729
- \@auxout . 2731, 3149, 3154, 3157, 3181
- \@botlist ..... 2682, 2684
- \@cc1v 2593, 2597, 2598, 2680, 2681, 2709
- \@chapter ..... 205
- \@checkend ..... 3210
- \@colht ..... 2575, 2685, 2697
- \@colroom ..... 2685
- \@combinefloats ..... 2570
- \@currentlabel .....
  - ..... 901, 1908, 2006, 2056, 2147
- \@currenvir ..... 3195, 3198, 3199
- \@currlist ..... 2686, 2689
- \@dbldeferlist ..... 2695, 2700, 2702
- \@dblfloatplacement ..... 2699
- \@dbltoplist ..... 2695, 2696
- \@deferlist ..... 2682, 2691, 2692
- \@docclearpage ..... 2669
- \@edrowfill@ ..... 3698
- \@ehb ..... 2688
- \@emptytoks ..... 3186, 3196
- \@footnotemark ..... 1820
- \@footnotetext .....
  - ..... 1816, 1833, 3052, 3078, 3105
- \@freelist ..... 2568
- \@gobble 768, 769, 2822, 3207, 3473, 3484
- \@gobblethree ..... 257, 2818
- \@h ..... 1685
- \@hilfs@count ..... 3409
- \@idxfile 3140, 3150, 3155, 3158, 3182
- \@ifclassloaded .....
  - ..... 31, 1815, 2636, 2661, 3127
- \@ifnextchar ..... 3130, 3394
- \@ifpackageloaded ..... 3178
- \@iiiminipage ..... 3041
- \@iiiparbox ..... 3068
- \@indexfile ..... 3172
- \@inputcheck ..... 463
- \@insert ..... 1248–1250, 1284–1286
- \@k ..... 1685
- \@kludgeins ..... 2572, 2633
- \@l ..... 492, 719
- \@l@tempcnta ... 29, 609, 611, 613,
  - 614, 1032, 1033, 1035, 1037,
  - 1040, 1041, 1056, 1092–1096,
  - 1098, 1105–1109, 1111, 1114,
  - 1117, 1119, 1123, 1153, 1157,
  - 1161, 1168, 1172, 1176, 1257,
  - 1261, 1265, 1268, 1271, 1274, 1275
- \@l@tempcntb 29, 326, 327, 332, 336,
  - 340, 344, 347, 370, 371, 378,
  - 382, 386, 388, 396, 397, 1090,
  - 1102, 1123, 1131–1133, 1135,
  - 1153, 1157, 1161, 1168, 1172,
  - 1176, 1206–1208, 1210, 1263,
  - 1264, 2880, 2881, 2886, 2890,
  - 2894, 2898, 2901, 3005–3007, 3009
- \@l@reg ..... 492
- \@lab ..... 692, 2720, 2762
- \@latexerr ..... 2688
- \@led@extranofeet .. 2658, 2667, 2675
- \@led@nofootfalse ..... 2671–2673
- \@led@nofoottrue ..... 2670
- \@led@testifnofoot ..... 2669
- \@line@num ..... 3405, 3503
- \@listdepth ..... 3054
- \@lock .... 144, 447, 517, 519, 521,
  - 534, 642, 643, 645, 646, 662,
  - 663, 665, 966, 1002, 1062, 1064,
  - 1065, 1067, 1165, 1180, 1182, 1184
- \@lopL ..... 559
- \@lopR ..... 559
- \@makechapterhead ..... 201–204
- \@makecol ..... 2640
- \@makefcolumn .. 2691, 2692, 2700, 2702
- \@makeschapterhead ..... 197–200
- \@makespecialcolbox ..... 2573
- \@maxdepth ..... 2588, 2596
- \@mem@extranofeet ..... 2662
- \@mem@nofootfalse ..... 2663, 2664
- \@midlist ..... 2568, 2569
- \@minipagefalse ..... 3065
- \@minipagerestore ..... 3055
- \@minus ..... 154,
  - 161, 168, 175, 182, 189, 2243, 2244
- \@mpargs ..... 3045, 3068
- \@mpfn ..... 3051, 3077, 3104
- \@mpfootins 3061, 3071, 3074, 3083, 3110
- \@mpfootnotetext ... 3052, 3078, 3105
- \@mplistdepth ..... 3054
- \@nameuse ..... 403, 405,
  - 1404, 1405, 1531, 1533, 1612,

1613, 1653, 1655, 1742, 1744, 1793, 1795, 1884, 1888, 1890, 1895, 1898, 1899, 1905, 1909, 1913, 1917, 1929, 1934, 1937, 1939, 1940, 1944, 1951, 1957, 2003, 2007, 2017, 2025, 2027, 2053, 2057, 2067, 2075, 2077, 2115, 2116, 2125, 2133, 2134, 2139, 2148, 2152, 2162, 2164, 2189, 2190, 2192, 2193, 2198, 2648, 2649, 2651, 2652, 2654, 2656	\@whilenum ..... 3672 \@whilesw ..... 2692, 2701 \@wredindex ..... 3169, <u>3171</u> , 3401 \@x@sf 1809, 1812, 1823, 1829, 1874, 1880 \@xloop ..... 1282, <u>1289</u> \@xympar ..... <u>2868</u> \^ ..... 486
\@nobreakfalse ..... 885 \@nobreaktrue ..... 883, 887 \@nowrindex ..... 3139 \@oldnobreak ..... 883, 885, 927 \@opcol ..... 2692, 2710 \@opxtrafeetii ..... 2617, <u>2618</u> , 2647 \@outputbox ..... . 2172, 2173, 2187, 2188, 2575, 2577, 2578, 2593, 2595, 2615, 2616 \@outputpage ..... 2701 \@page ..... <u>539</u> \@parboxrestore .... 1409, 1903, 3050 \@pboxswfalse ..... 3043 \@pend ..... <u>559</u> \@pendR ..... <u>559</u> \@plus .... 154, 156, 161, 163, 168, 170, 175, 177, 182, 184, 189, 191, 1420, 2013, 2063, 2243, 2244 \@ref ..... <u>677</u> , 722 \@ref@reg ..... <u>679</u> \@reinsets ..... 2641 \@schapter ..... 206 \@series ... 461, 2175, 2180, <u>2204</u> , 2206, 2322, 2331, 2332, 2343, 2345, 2359, 2370, 2620, 2627, 2666, 2674, 3021, 3032, 3037, 3040, 3471, 3476, 3482, 3487, 3502 \@set ..... <u>590</u> , 741 \@setminipage ..... 3056 \@showidx ..... 3147, 3180 \@tag ..... <u>776</u> , <u>793</u> , 816, 851, 1842 \@tempboxa .... 2680, 2681, 3046, 3068 \@tempdima ..... 2597, 3044, 3048 \@templ@ld ..... 2996, 2997 \@textbottom ..... 2580 \@texttop ..... 2576 \@toksa ..... <u>430</u> , 438 \@toksb ..... <u>430</u> , 437–439 \@toplist ..... 2682, 2683	\_ ..... 3706, 3711, 3719  <b>A</b> \absline@num 141, <u>446</u> , 497, 500, 503, 604, 607, 616, 630, 652, 674, 684, 993, 1014, 1015, 1023, 1247 Abu Kamil Shuja' b. Aslam ..... 7 \actionlines@list ..... ..... <u>449</u> , 469, 472, 479, 604, 607, 616, 630, 652, 674, 1045, 1048 \actions@list ..... . <u>449</u> , 473, 480, 605, 614, 618, 620, 632, 641, 654, 661, 675, 1049 \add@inserts ..... 973, <u>1236</u> \add@inserts@next ..... <u>1236</u> \add@penalties ..... <u>1257</u> \addcontentsline ..... 257 \addfootins ..... <u>2644</u> \addfootinsX ..... <u>2183</u> \addtocounter ..... 928 \addtol@den@body ... <u>3190</u> , 3211, 3213 Adelard II ..... 7 \advancelabel@refs ..... 2726, <u>2735</u> \advanceline . 13, 65, 68, <u>736</u> , 759, 769 \advancepageno ..... <u>2563</u> \Aendnote ..... 15 \affixline@num ..... 971, <u>1084</u> \affixpstart@num ..... 972, <u>1195</u> \affixside@note ..... 973, 2974, 2983 \Afootnote ..... 15 \afterlemmaseparator ..... 19 \afternote ..... 20 \afternumberinfootnote ..... 18 \aftersym@linenum ..... 18 \allowbreak .... 1735, 1782, 2018, 2068 \ampersand ..... 24, <u>3229</u> , 3300 \appto ..... 2989, 2990 \apptocmd ..... 199, 203, 205, 206 \AtBeginDocument ..... 2758, 3178 \autopar ..... 10, 86, <u>935</u> \autoparfalse ..... 278, 936

- \autopartrue ..... 949
- B**
- \ballast ..... 34
- \ballast@count . 1009, 1012, 1017, 1257
- Beeton, Barbara Ann Neuhaus Friend 10
- \beforeledchapter ..... 207
- \beforelemmaseparator ..... 18
- \beforenotesX ..... 20
- \beforenumberinfootnote ..... 18
- \beforexymmlinenum ..... 18
- \beforeXnotes ..... 20
- \beginnumbering . 9, 123, 291, 890, 946
- \beginnumberingR ..... 941
- \Bendnote ..... 15
- \Bfootnote ..... 15
- \bfseries ..... 876
- \bhooknoteX ..... 20
- \bhookXendnote ..... 20
- \bhookXnote ..... 20
- \body ..... 1290, 1291, 3231, 3299
- \bodyfootmarkA ..... 28
- \box . . . . 985, 987, 1607, 1622, 1667,  
1686, 2129, 2143, 2593, 2681, 2709
- \boxlinenum ..... 18
- \boxmaxdepth ..... 2596
- \boxxymmlinenum ..... 18
- Bredon, Simon ..... 7
- Breger, Herbert ..... 5, 8, 158
- Brey, Gerhard ..... 7
- \brokenpenalty ..... 931
- Burt, John ..... 6
- Busard, Hubert L. L. .... 7
- \bypage@false ..... 294, 308, 314
- \bypage@true ..... 294, 302
- \bypstart@false ..... 294, 303, 315
- \bypstart@true ..... 294, 309
- C**
- \c@addcolcount ..... 3666
- \c@ballast ..... 1009, 1017
- \c@firstlinenum .....  
..... 353, 1104, 1106, 1109, 1111
- \c@firstsublinenum .....  
..... 357, 1091, 1093, 1096, 1098
- \c@labidx ..... 3116
- \c@linenumincrement . . 353, 1107, 1108
- \c@mpfootnote ..... 3051, 3077, 3104
- \c@page ..... 719
- \c@pstart ..... 876
- \c@sublinenumincrement 357, 1094, 1095
- \Cendnote ..... 15
- \centerline ..... 3602, 3607,  
3613, 3618, 3624, 3629, 3850, 3852
- \Cfootnote ..... 15
- \ch@ck@l@ck ..... 1121, 1149
- \ch@cksub@l@ck ..... 1100, 1149
- \ch@pt@c ..... 195
- \changes ..... 2350, 2353, 2981
- \chapter ..... 195, 196, 208, 209
- \char ..... 3229
- \chardef ..... 2867, 3231, 3233
- Chester, Robert of ..... 7
- Claassens, Geert H. M. .... 7
- class 1 feet ..... 120, 133
- class 2 feet ..... 133
- \cleaders ..... 3661
- \cleardoublepage ..... 207, 208
- \closeout ..... 711, 715, 2810
- \clubpenalty ..... 931, 1261
- \color@begingroup .....  
1410, 1618, 1904, 2139, 2600, 3047
- \color@endgroup .....  
1411, 1618, 1905, 2139, 2604, 3066
- \columnwidth .....  
..... 1408, 1581, 1902, 3049, 3092
- \content .....  
2256, 2292, 2308, 2927, 2935, 2942
- Copernicus, Nicolaus ..... 7
- \count 1554, 1559, 1571, 1575, 1710,  
1713, 1762, 1790, 1971, 1976,  
1992, 1995, 2043, 2046, 2090, 2093
- \countdef ..... 2563
- \cr ..... 1688, 1691
- \CRITEXT ..... 3385
- \critext .....  
37, 770, 779, 792, 3387, 3469, 3498
- \cs ..... 780, 785, 789, 1329,  
1359–1361, 1363, 1364, 1376,  
1377, 1385, 1387, 1869, 2319,  
2337, 2353, 2354, 2454, 2977, 2979
- \csdef ..... 3475
- \csexpandonce 1339, 1350, 1843, 2266,  
2277, 2296, 2311, 2929, 2937, 2944
- \csgdef 1547, 1565, 1699, 1751, 1961,  
1982, 2033, 2083, 2208–2224,  
2229, 2231, 2232, 2234–2236,  
2238–2247, 2287, 2304, 2367, 3486
- \cslet ..... 2237

- `\csletcs` ..... 2314,  
 2318, 3020, 3036, 3470, 3481, 3501  
`\csnumdef` ..... 913, 915  
`\csundef` ..... 460  
`\csuse` ..... 1392, 1393,  
 1406, 1407, 1418, 1424, 1427–  
 1429, 1435, 1521, 1528, 1534,  
 1555, 1556, 1560, 1561, 1578,  
 1591, 1599, 1600, 1614, 1615,  
 1633, 1640–1642, 1648, 1649,  
 1658, 1659, 1674, 1676–1678,  
 1680, 1718, 1723, 1727, 1731–  
 1733, 1737, 1745, 1765, 1770,  
 1774, 1778–1780, 1783, 1784,  
 1796, 1891, 1892, 1900, 1901,  
 1912, 1913, 1923, 1972, 1973,  
 1977, 1978, 2000, 2010, 2011,  
 2017, 2020, 2051, 2059, 2061,  
 2067, 2070, 2096, 2108, 2121,  
 2122, 2135, 2136, 2152, 2159,  
 2168, 2174, 2179, 2234, 2235,  
 2265, 2276, 2282, 2294–2296,  
 2368, 2377, 2441, 2490, 2496,  
 2507, 2509–2513, 2516, 2517,  
 2521, 2526, 2530, 2531, 2535,  
 2540, 2544, 2545, 2550, 2555,  
 2619, 2626, 2663, 2664, 2672,  
 2673, 2818, 3031, 3039, 3475, 3486  
`\csxdef` 1313, 1315, 1319, 1321, 1333,  
 1336, 1339, 1344, 1347, 1350, 2557  
`\ctab` ..... 3305, 3809, 3900  
`\ctabtext` ..... 3309, 3819, 3904
- D**
- `\dcolerr` ..... 3361, 3373  
`\dcoli` ... 3331, 3363, 3364, 3710, 3715  
`\dcolii` ..... 3332, 3364  
`\dcoliii` ..... 3333, 3364  
`\dcoliv` ..... 3334, 3365  
`\dcolix` ..... 3339, 3366  
`\dcolv` ..... 3335, 3365  
`\dcolvi` ..... 3336, 3365  
`\dcolvii` ..... 3337, 3366  
`\dcolviii` ..... 3338, 3366  
`\dcolx` ..... 3340, 3366  
`\dcolxi` ..... 3341, 3367  
`\dcolxii` ..... 3342, 3367  
`\dcolxiii` ..... 3343, 3367  
`\dcolxiv` ..... 3344, 3368  
`\dcolxix` ..... 3349, 3369  
`\dcolxv` ..... 3345, 3368  
`\dcolxvi` ..... 3346, 3368  
`\dcolxvii` ..... 3347, 3369  
`\dcolxviii` ..... 3348, 3369  
`\dcolxx` ..... 3350, 3369  
`\dcolxxi` ..... 3351, 3370  
`\dcolxxii` ..... 3352, 3370  
`\dcolxxiii` ..... 3353, 3370  
`\dcolxxiv` ..... 3354, 3371  
`\dcolxxix` ..... 3359, 3372  
`\dcolxxv` ..... 3355, 3371  
`\dcolxxvi` ..... 3356, 3371  
`\dcolxxvii` ..... 3357, 3372  
`\dcolxxviii` ..... 3358, 3372  
`\dcolxxx` ..... 3360, 3372  
`\DeclareOption` ..... 8–11  
 Dekker, Dirk-Jan ..... 6, 36  
`\Dendnote` ..... 15  
`\Dfootnote` ..... 15  
`\dimen` ..... 727, 728, 730–732,  
 734, 1555, 1560, 1579–1581,  
 1584, 1693–1695, 1711, 1714,  
 1763, 1791, 1972, 1977, 1993,  
 1996, 2044, 2047, 2097–2099, 2102  
`\dimen@` ..... 2577, 2579  
`\disablel@dtabfeet` .....  
 ..... 3516, 3533, 3547, 3561,  
 3574, 3589, 3717, 3724, 3729,  
 3737, 3742, 3750, 3768, 3784, 3907  
`\displaystyle` ..... 3419, 3518,  
 3520, 3549, 3551, 3576, 3578,  
 3717, 3729, 3742, 3830, 3882, 3883  
`\displaywidowpenalty` ..... 932  
`\divide` .. 1094, 1107, 1581, 1694, 2099  
`\do@actions` ..... 994, 1021  
`\do@actions@fixedcode` ... 1042, 1055  
`\do@actions@next` ..... 1021  
`\do@ballast` ..... 995, 1009  
`\do@line` ..... 916, 957  
`\do@linehook` ..... 961, 978  
`\do@lockoff` ..... 651  
`\do@lockoffL` ..... 651  
`\do@lockon` ..... 622  
`\do@lockonL` ..... 622  
`\docsvlist` .... 1309, 2202, 2362, 2373  
`\doedindexlabel` 3121, 3141, 3166, 3398  
`\doendnotes` ..... 25, 2860  
`\dolistloop` .....  
 .. 461, 2175, 2180, 2331, 2343,  
 2359, 2370, 2620, 2627, 2666,

- 2674, 2994, 3021, 3032, 3037,  
3040, 3471, 3476, 3482, 3487, 3502  
`\doreinxtrafeeti` . . . 2171, 2191, 2622  
`\doreinxtrafeetii` . . 2623, 2625, 2650  
`\dosplits` . . . . . 1685  
Downes, Michael . . . . . 35, 102, 104  
`\doxtrafeet` . . . . . 2610  
`\doxtrafeeti` . . . . . 2171, 2186, 2611  
`\doxtrafeetii` . . . . . 2612, 2614  
`\dp` . . . . . 1400,  
1605, 1620, 2127, 2141, 2577, 2597  
`\dummy@edtext` . . . . . 763, 771  
`\dummy@ref` . . . . . 678, 688  
`\dummy@text` . . . . . 762, 770
- E**
- `\edaftertab` . . . . .  
. . . 31, 171, 3311, 3757, 3791, 3809  
`edarrayc` (environment) . . . . 29, 3899  
`edarrayl` (environment) . . . . 29, 3899  
`edarrayr` (environment) . . . . 29, 3899  
`\EDATAB` . . . . . 3849, 3857  
`\edatab` . . . . . 3312, 3855  
`\edatabell` . . . . . 3313, 3839  
`\edatleft` . . . . . 31, 3314, 3641  
`\edatright` . . . . . 31, 3315, 3649  
`\edbeforetab` . . . . .  
. . . 31, 171, 3310, 3757, 3791, 3809  
`\edfilldimen` . . . . .  
. . . . 3663, 3673, 3674, 3676, 3700  
`\edfont@info` . . . . . 842, 845, 849  
`\EDINDEX` . . . . . 3391  
`\edindex` . . . . 28, 3128, 3164, 3391,  
3472, 3477, 3483, 3488, 3500,  
3509, 3526, 3542, 3556, 3569, 3584  
`\edindexlab` . . . . 29, 3116, 3122, 3125  
`\EDLABEL` . . . . . 3389  
`\edlabel` . . . . . 26, 768, 2719,  
3122, 3389, 3490, 3506, 3508,  
3525, 3541, 3555, 3568, 3583,  
3716, 3723, 3728, 3736, 3741, 3749  
`\edmakelabel` . . . . . 27, 2805  
`\edpageref` . . . . . 26, 2766  
`\edrowfill` . . 30, 3318, 3491, 3494, 3698  
`\EDTAB` . . . . . 3845, 3881  
`\edtabcolsep` . . . . . 30, 3448,  
3521, 3538, 3551, 3565, 3579,  
3594, 3674, 3731, 3744, 3753, 3867  
`\EDTABINDENT` . . . . . 3862, 3875  
`\edtabindent` . . . . . 3705,  
3709, 3714, 3725, 3738, 3751, 3871  
`\EDTABtext` . . . . . 3889  
`edtabularc` (environment) . . . . 29, 3903  
`edtabularl` (environment) . . . . 29, 3903  
`edtabularr` (environment) . . . . 29, 3903  
`\EDTEXT` . . . . . 3385  
`\edtext` . . . . . 14, 771, 814, 1836,  
1955, 2918–2920, 3385, 3480, 3499  
`\edvertdots` . . . . . 32, 3317, 3660  
`\edvertline` . . . . . 32, 3316, 3658  
`\Eendnote` . . . . . 15  
`\Efootnote` . . . . . 15  
`\Eledmac` . . . . . 2316  
`\eledmac@error` . . . . . 34,  
36, 38, 40, 52, 75, 78, 81, 84,  
86, 102, 104, 107, 109, 111, 3694  
`\eledmac@warning` . . 33, 55, 57, 59,  
61, 63, 65, 68, 71, 73, 89, 91, 93,  
96, 98, 100, 2184, 2206, 2645, 2995  
`\empty` . . . . . 27, 114, 265, 268, 428,  
429, 469, 804, 826, 840, 854,  
858, 864, 897, 1045, 1103, 1119,  
1238–1240, 1251, 1283, 2721, 3244  
`\enablel@dtabfeet` . . . . . 3765,  
3781, 3799, 3807, 3817, 3825, 3907  
`\end@lemmas` . . . 761, 804, 805, 826, 827  
`\endashchar` . . . . 21, 1432, 1512, 2852  
`\endgraf` . . . . . 911, 951, 955  
`\endline@num` . . . . . 454, 695, 701  
`\endlock` . . 13, 751, 767, 3286, 3290, 3292  
`\endminipage` . . . . . 3058  
`\endnumbering` . . . 9, 126, 258, 280, 290  
`\endpage@num` . . . . . 454, 694, 701  
`\endprint` . . . . . 25, 2818, 2863  
`\endquotation` . . . . . 152  
`\endquote` . . . . . 152  
`\endstanzaextra` . . . . . 24, 3279  
`\endsub` . . . . . 13, 727, 766  
`\endsubline@num` . . . . . 454, 696, 702  
`\enskip` . . . . . 2819  
`\enspace` . . 1913, 2017, 2067, 2152, 2819  
environments:  
`edarrayc` . . . . . 29, 3899  
`edarrayl` . . . . . 29, 3899  
`edarrayr` . . . . . 29, 3899  
`edtabularc` . . . . . 29, 3903  
`edtabularl` . . . . . 29, 3903  
`edtabularr` . . . . . 29, 3903  
`ledgroup` . . . . . 25, 3076



- ledgroupsize . . . . . 25, 3089
- minipage . . . . . 24
- Euclid . . . . . 7
- \ExecuteOptions . . . . . 12
- \extensionchars . . . . . 34, 112, 132, 286
- \extractendline@ . . . . . 2481, 2484
- \extractendsubline@ . . . . . 2482, 2484
- \extractline@ . . . . . 2479, 2484, 2487
- \extractsubline@ . . . . . 2480, 2484, 2487
- F**
- \f@encoding . . . . . 849
- \f@family . . . . . 849
- \f@series . . . . . 849
- \f@shape . . . . . 849
- \f@x@l@cks . . . . . 1144, 1149
- Fairbairns, Robin . . . . . 28
- \first@linenum@out@false . . . . . 706, 712
- \first@linenum@out@true . . . . . 706
- \firstlinenum . . . . . 10, 12, 362
- \firstseries . . . . . 2326
- \firstsublinenum . . . . . 11, 12, 362
- \fix@page . . . . . 493, 546
- \flag@end . . . . . 720, 800, 810, 811, 822, 832, 833
- \flag@start . . . . . 720, 799, 800, 811, 821, 822, 833
- \flagstanza . . . . . 24, 3295
- \floatingpenalty . . . . . 1399
- \flush@notes . . . . . 921, 1281, 3028
- \flush@notesR . . . . . 3026
- Folkerts, Menso . . . . . 7
- \fontencoding . . . . . 1295
- \fontfamily . . . . . 1295
- \fontseries . . . . . 1295
- \fontshape . . . . . 1295
- \footfootmarkA . . . . . 28
- \footfudgefiddle . . . . . 35, 1577, 1581, 2099
- \footins . . . . . 2592, 2599, 2603, 2631, 2671
- \footnormal . . . . . 1537, 2288, 2646
- \footnormalX . . . . . 28, 1960, 2185, 2305
- \footnote@luatexpardir . . . . . 1416
- \footnote@luatextextdir . . . . . 1415, 1437
- \footnoteA . . . . . 28
- \footnoteB . . . . . 28
- \footnoteC . . . . . 28
- \footnoteD . . . . . 28
- \footnoteE . . . . . 28
- \footnotelang@lua . . . . . 1311, 2260, 2271
- \footnotelang@poly . . . . . 1327, 1330, 2263, 2274
- \footnoteoptions@ . . . . . 1298, 2264, 2267, 2275, 2279
- \footnoterule . . . . . 1527, 1931, 2602, 3073
- \footnotesize . . . . . 2466, 2915, 2916
- \footparagraph . . . . . 16, 1564
- \footparagraphX . . . . . 28, 2082
- \footsplitskips . . . . . 1394, 1397, 1601, 1616, 1719, 1766, 1893, 2001, 2052, 2123, 2137
- \footthreecol . . . . . 16, 1698
- \footthreecolX . . . . . 28, 2032
- \foottwocol . . . . . 16, 1750
- \foottwocolX . . . . . 28, 1981
- \foottwocolX . . . . . 1981
- \fullstop . . . . . 21, 418, 1432, 1509, 1511, 1513, 1515, 2851, 2855
- G**
- \g@addto@macro . . . . . 2186, 2191, 2194, 2197, 2637, 2638, 2647, 2650, 2653, 2655, 2662, 3128, 3164
- Gädeke, Nora . . . . . 8
- \get@linelistfile . . . . . 466, 481
- \getline@num . . . . . 965, 992
- \gl@p . . . . . 440, 472, 473, 805, 827, 844, 1048, 1049, 1244, 1248, 1284, 2724
- \gl@poff . . . . . 440, 441
- H**
- \hangafter . . . . . 3275
- \hangindentX . . . . . 19
- \hangingsymbol . . . . . 24, 3218, 3225
- \hb@xt@ . . . . . 973, 975, 985, 987, 3700, 3705, 3709, 3714, 3725, 3738, 3751, 3828, 3830
- \hfilneg . . . . . 1687
- \Hilfsbox . . . . . 3326
- \hilfsbox . . . . . 3326, 3381, 3382, 3419, 3431, 3505, 3518, 3535, 3549, 3563, 3576, 3591, 3716, 3718, 3723, 3727, 3728, 3730, 3736, 3740, 3741, 3743, 3749, 3752
- \hilfscount . . . . . 3326, 3866–3868, 3874
- \HILFSskip . . . . . 3859
- \Hilfsskip . . . . . 3706, 3710, 3711, 3715, 3718, 3719, 3726, 3727, 3730–3732, 3739,

- 3740, 3743–3745, 3752–3754,  
3859, 3865, 3867, 3873, 3877, 3878  
`\hilfsskip` .....  
    . 3326, 3504, 3505, 3520, 3537,  
    3551, 3565, 3578, 3593, 3876–3878  
`\hsizethreecol` ..... 20  
`\hsizethreecolX` ..... 20  
`\hsizetwocol` ..... 20  
`\hsizetwocolX` ..... 20  
`\Hy@temp@A` ..... 3152, 3153  
`\HyInd@ParenLeft` ..... 3153
- I**
- `\if@fcolmade` ..... 2692, 2701  
`\if@firstcolumn` 1125, 1200, 2694, 2999  
`\if@led@nofoot` ..... 2658, 2679  
`\if@nobreak` ..... 882  
`\if@RTL` ..... 20,  
    800, 811, 822, 833, 1332, 1343, 1607  
`\ifautopar` 158, 165, 172, 179, 186,  
    193, 214, 227, 236, 249, 899, 935  
`\ifbypage@` .. 294, 540, 551, 1026, 1483  
`\ifbypstart@` ..... 294, 917  
`\ifcsdef` ..... 20, 1675, 2501  
`\ifcsempy` .....  
    1427, 1640, 1677, 1731, 1778, 2505  
`\ifcsequal` ..... 2503  
`\ifcsstring` ..... 2330, 2342  
`\ifdefstring` ..... 1437  
`\ifdim` 728, 730, 732, 734, 1808, 3381, 3866  
`\ifdimequal` ..... 1518, 1588,  
    1920, 2105, 2510, 2517, 2531, 2545  
`\iffirst@linenum@out@` ..... 706, 710  
`\ifhbox` ..... 1666, 1671  
`\ifhmode` ..... 1822, 1829, 1873, 1880  
`\ifinserthangingsymbol` ..... 3221  
`\ifinstanza` ..... 899, 952, 3218, 3224  
`\ifl@d@dash` ..... 1455, 1512, 2852  
`\ifl@d@elin` ..... 1455,  
    1501, 1514, 1515, 2842, 2854, 2855  
`\ifl@d@esl` ..... 1455, 1515, 2855  
`\ifl@d@pnum` .....  
    1455, 1489, 1509, 1513, 2830, 2853  
`\ifl@d@ssub` ..... 1455, 1511, 2851  
`\ifl@dend@` ..... 2807, 2813  
`\ifl@dmemoir` ..... 30, 195, 3392  
`\ifl@dpairing` ... 116, 262, 1445, 3024  
`\ifl@dskipnumber` ..... 754, 1086  
`\ifl@dstartendok` ..... 3670, 3680  
`\iflabelpstart` ..... 879, 901  
`\ifledfinal` ..... 4, 21, 34  
`\ifledplinenum` ..... 2465  
`\ifledRcol` .. 116, 938, 1446, 2258, 3025  
`\ifleftnoteup` ..... 2956, 2969  
`\ifluatex` ..... 1414, 1436, 2259, 2270  
`\ifnoquotation@` ..... 6, 210  
`\ifnoteschanged@` ..... 272, 458  
`\ifnumberedpar@` ... 869, 892, 907,  
    1835, 1841, 1943, 1954, 2257,  
    2310, 2311, 2870, 2928, 2936, 2943  
`\ifnumbering` ..... 115,  
    124, 259, 282, 297, 888, 904, 944  
`\ifnumberingR` ..... 116, 939  
`\ifnumberline` ..... 837, 996, 1085  
`\ifnumberpstart` ... 877, 899, 924, 952  
`\ifnumequal` .... 918, 1674, 1676, 2987  
`\ifnumgreater` ..... 2995  
`\ifodd` ..... 1135, 1210, 3009  
`\ifparapparatus@` ..... 4  
`\ifpst@rtedL` ..... 116  
`\ifpstartnum` ..... 1221, 1224, 1229  
`\ifreportnoidxfile` ..... 3134  
`\ifrightnoteup` ..... 2923, 2964  
`\ifshowindexmark` ..... 3147, 3180  
`\ifsidepstartnum` ..... 899, 1195  
`\ifstreempty` ..... 2358, 2369  
`\ifstrequal` .... 1300, 1312, 1331, 2368  
`\ifsublines@` .....  
    . 416, 445, 529, 564, 569, 575,  
    590, 608, 617, 631, 653, 700,  
    702, 997, 1034, 1089, 2740, 2764  
`\iftoggle` .....  
    . 1427, 1520, 1590, 1640, 1731,  
    1778, 1922, 2107, 2483, 2489,  
    2494, 2499, 2518, 2522, 2523,  
    2526, 2532, 2533, 2536, 2537,  
    2540, 2546, 2547, 2551, 2552, 2555  
`\ifvbox` ..... 914, 2572, 2633  
`\ifvmode` ..... 2725  
`\ifvoid` 2174, 2179, 2189, 2192, 2198,  
    2592, 2619, 2626, 2631, 2648,  
    2651, 2656, 2663, 2664, 2671–  
    2673, 3031, 3039, 3061, 3083, 3110  
`\indexentry` ..... 3173  
`\initnumbering@reg` ..... 123  
`\initnumbering@sectcmd` .... 136, 152  
`\inplaceoflemmaseparator` ..... 19  
`\inplaceofnumber` ..... 18  
`\InputIfFileExists` ..... 482

- \insert ..... 1391, 1597, 1717,  
1764, 1890, 1999, 2050, 2119,  
2179, 2193, 2626, 2631, 2633, 2652
  - \insert@count .....  
. 676, 677, 722, 796, 818, 1302,  
1314, 1316, 1334, 1337, 1340,  
1845, 1946, 2278, 2931, 2939, 2946
  - \insert@countR ..... 1306,  
1320, 1322, 1345, 1348, 1351, 2268
  - \inserthangingsymbol ..... 973, 3222
  - \inserthangingsymbolfalse ..... 969
  - \inserthangingsymboltrue ..... 967
  - \inserthangingymbol ..... 3221
  - \insertlines@list .....  
... 265, 449, 478, 684, 1240, 1244
  - \insertparafootsep .. 1636, 1673, 2150
  - \inserts@list ..... 896, 1235,  
1238, 1248, 1283, 1284, 1301,  
1313, 1315, 1333, 1336, 1339,  
1844, 1945, 2277, 2930, 2938, 2945
  - \inserts@listR ..... 1305,  
1319, 1321, 1344, 1347, 1350, 2266
  - \instanzafalse ..... 3220, 3292
  - \instanzatrue ..... 3281
  - \interfootnotelinepenalty ..... 1398
  - \interlinepenalty 932, 1268, 1398, 3286
  - \interparanoteglue ..... 2473
  - \ipn@skip ..... 2473
  - \itemcount@ .... 2985, 2987, 2992, 2995
- J**
- Jayaditya ..... 8
- K**
- Kabelschacht, Alois ..... 90
- Krukov, Alexej ..... 67
- L**
- \l@d@@wrindexhyp ..... 3145, 3178
  - \l@d@add ..... 859, 861, 865, 867
  - \l@d@dashfalse ..... 1464, 1482, 2825
  - \l@d@dashtrue .....  
1486, 1492, 1504, 2828, 2833, 2845
  - \l@d@elinfalse ..... 1460, 1489, 2830
  - \l@d@elintrue .. 1489, 1491, 2830, 2832
  - \l@d@end .....  
2309, 2807, 2809, 2810, 2816, 2867
  - \l@d@err@UnequalColumns ..... 3462
  - \l@d@eslfalse .....  
.... 1462, 1498, 1501, 2839, 2842
  - \l@d@esltrue ... 1501, 1503, 2842, 2844
  - \l@d@index ..... 3130, 3132, 3394
  - \l@d@makecol ..... 2584, 2640, 2710
  - \l@d@nums ..... 795, 842,  
845, 853, 854, 867, 2266, 2277, 2310
  - \l@d@pnumfalse ..... 1456, 1482, 2825
  - \l@d@pnumtrue ..... 1485, 2827
  - \l@d@reinserts ..... 2630, 2641
  - \l@d@section ..... 2816, 2818
  - \l@d@set ..... 597, 748
  - \l@d@ssubfalse ..... 1458, 1494, 2835
  - \l@d@ssubtrue ..... 1496, 2837
  - \l@d@wrindexm@m ..... 3144, 3145
  - \l@dampcount ..... 3321,  
3458, 3460, 3465, 3714, 3724,  
3725, 3737, 3738, 3773, 3789, 3827
  - \l@dbegin@stack .... 3196, 3206–3208
  - \l@dbfnote ..... 1836, 1840
  - \l@dcheckcols ..... 3415, 3427, 3455
  - \l@dcheckstartend ..... 3669, 3680
  - \l@dchset@num ..... 496, 499, 597
  - \l@dcolcount ..... 3321, 3363,  
3375, 3376, 3414, 3416, 3426,  
3428, 3456, 3460, 3465, 3510,  
3512, 3527, 3529, 3543, 3544,  
3557, 3558, 3570, 3571, 3585,  
3586, 3636, 3637, 3714, 3724,  
3725, 3737, 3738, 3769, 3771,  
3785, 3787, 3827, 3833, 3863, 3872
  - \l@dcollect@@body ..... 3198, 3205
  - \l@dcollect@body .....  
.... 3193, 3899–3901, 3903–3905
  - \l@dcolwidth .... 3363, 3381, 3382,  
3504, 3635, 3700, 3726, 3739,  
3828, 3830, 3835, 3844, 3865, 3866
  - \l@dcsnote ..... 2920, 2923
  - \l@dcsnotetext . 979, 2951, 2994, 2997
  - \l@ddodoreinextrafeet 2621, 2632, 2638
  - \l@ddofootinsert ..... 2585, 2590
  - \l@ddoxtrafeet ..... 2607, 2610, 2637
  - \l@dedbeginmini .... 2653, 3016, 3019
  - \l@dedendmini ..... 2655, 3017, 3019
  - \l@demptyd@ta ..... 962, 979
  - \l@dend@close ..... 2809, 2860
  - \l@dend@false ..... 2807, 2810
  - \l@dend@open ..... 2809, 2814
  - \l@dend@stuff ... 133, 287, 2812, 2866
  - \l@dend@true ..... 2807, 2809
  - \l@denvbody .... 3188, 3191, 3194–3196
  - \l@dfambeginmini ... 2194, 3016, 3035

- \l@dfamendmini . . . . . 2197, 3017, 3035
- \l@dfeetbeginmini . . . . . 3016, 3053, 3079, 3106
- \l@dfeetendmini . . . . . 3016, 3064, 3086, 3113
- \l@dgetline@margin . . . . . 323
- \l@dgetlock@disp . . . . . 367, 395
- \l@dgetref@num . . . . . 2766, 2767, 2769, 2770, 2772, 2773, 2780
- \l@dgetsidenote@margin . . . . . 2877
- \l@dobblearg . . . . . 3406
- \l@dobbledarg . . . . . 3406
- \l@dlabel@parse . . . . . 2786, 2789
- \l@dld@eta . . . . . 973, 979, 1124, 1201, 1213
- \l@dldp@rbox . . . . . 985, 2908, 2955
- \l@dlsn@te . . . . . 974, 984
- \l@dlsnote . . . . . 2918, 2923
- \l@dmake@labels . . . . . 2729, 2732, 2750, 2759
- \l@dmemoirfalse . . . . . 31
- \l@dmemoirtrue . . . . . 31
- \l@dmodforcritext . . . . . 3468, 3908
- \l@dmodforedtext . . . . . 3479, 3911
- \l@dnullfills . . . . . 3489, 3758, 3776, 3792, 3802, 3810, 3820
- \l@dnumpstartsL . . . . . 116, 140
- \l@dold@footnotetext . . . . . 1816, 1818
- \l@dold@xympar . . . . . 2868
- \l@doldold@footnotetext . . . . . 1833, 1849
- \l@dprsefootspec . . . . . 1465
- \l@dpairingfalse . . . . . 116
- \l@dpairingtrue . . . . . 116
- \l@dparseendline . . . . . 1465
- \l@dparseendpage . . . . . 1465
- \l@dparseendsub . . . . . 1465
- \l@dparsestartline . . . . . 1465
- \l@dparsestartpage . . . . . 1465
- \l@dparsestartsub . . . . . 1465
- \l@dparsefootspec . . . . . 1465
- \l@dpush@begins . . . . . 3202, 3206
- \l@drd@eta . . . . . 975, 979, 1124, 1203, 1211
- \l@dref@undefined . . . . . 2766, 2769, 2772, 2775
- \l@drestorefills . . . . . 3489, 3762, 3778, 3796, 3804, 3814, 3822
- \l@drestoreforcritext . . . . . 3468, 3909
- \l@drestoreforedtext . . . . . 3479, 3912
- \l@drp@rbox . . . . . 987, 2908, 2963
- \l@drrsn@te . . . . . 976, 984
- \l@drrsnote . . . . . 2919, 2923
- \l@dsetmaxcolwidth . . . . . 3380, 3421, 3433
- \l@dskipnumberfalse . . . . . 754, 1087
- \l@dskipnumbertrue . . . . . 754, 1078
- \l@dstartendokfalse . . . . . 3684, 3688, 3692
- \l@dstartendoktrue . . . . . 3682
- \l@dtabaddcols . . . . . 3668, 3699
- \l@dtabnoexpands . . . . . 772, 3303
- \l@dunboxmpfoot . . . . . 3062, 3070, 3084, 3111
- \l@dunhbox@line . . . . . 957
- \l@dzeropenalties . . . . . 910, 930
- Lück, Uwe . . . . . 6
- \label . . . . . 27, 1356
- \label@refs . . . . . 2722, 2724, 2729, 2732, 2738, 2741, 2743, 2745
- \labelpstartfalse . . . . . 874
- \labelpstarttrue . . . . . 874
- \labelref@list . . . . . 2715, 2721, 2724, 2764
- \labelrefsparseline . . . . . 2735
- \labelrefsparsesubline . . . . . 2735
- \last@page@num . . . . . 546
- \lastbox . . . . . 950, 964, 1628, 1665, 1670
- \lastkern . . . . . 1808
- \lastskip . . . . . 727, 731
- Lavagnino, John . . . . . 5, 6
- Leal, Jeronimo@Leal, Jerónimo . . . . . 6
- \led@err@AutoparNotNumbered . . . . . 74, 940, 945
- \led@err@HighEndColumn . . . . . 101, 3689
- \led@err@LineationInNumbered . . . . . 51, 298
- \led@err@LowStartColumn . . . . . 101, 3685
- \led@err@NumberingNotStarted . . . . . 35, 276
- \led@err@NumberingShouldHaveStarted . . . . . 35, 289
- \led@err@NumberingStarted . . . . . 35, 125
- \led@err@PendNoPstart . . . . . 74, 908
- \led@err@PendNotNumbered . . . . . 74, 905
- \led@err@PstartInPstart . . . . . 74, 893
- \led@err@PstartNotNumbered . . . . . 74, 889
- \led@err@ReverseColumns . . . . . 101, 3693
- \led@err@TooManyColumns . . . . . 101, 3377
- \led@err@UnequalColumns . . . . . 101
- \led@mess@NotesChanged . . . . . 41, 273
- \led@mess@SectionContinued . . . . . 49, 285
- \led@warn@BadAction . . . . . 88, 1080
- \led@warn@BadAdvancelineLine . . . . . 64, 584
- \led@warn@BadAdvancelineSubline . . . . . 64, 578
- \led@warn@BadLineation . . . . . 54, 318
- \led@warn@BadLinenummarg . . . . . 54, 346
- \led@warn@BadLockdisp . . . . . 54, 373
- \led@warn@BadSetline . . . . . 70, 739
- \led@warn@BadSetlinenum . . . . . 70, 746

- \led@warn@BadSidenotemargin 97, 2900
  - \led@warn@BadSublockdisp . . . . 54, 399
  - \led@warn@DuplicateLabel . . . 90, 2753
  - \led@warn@NoIndexFile . . . . 99, 3135
  - \led@warn@NoLineFile . . . . . 62, 487
  - \led@warn@NoMarginpars . . . . 95, 2871
  - \led@warn@RefUndefined . . . . 90, 2777
  - \ledchapter . . . . . 152
  - \ledchapter\* . . . . . 152
  - \ledfinalfalse . . . . . 10
  - \ledfinaltrue . . . . . 9
  - \ledfootinsdim . . . . 1537, 2246, 2247
  - ledgroup (environment) . . . . 25, 3076
  - ledgroupsize (environment) . . 25, 3089
  - \ledleftnote . . . . . 27, 2918
  - \ledlinenum . . . . . 411
  - \ledllfill . . . . 975, 989, 3093, 3097
  - \ledlsnotefontsetup . . . 27, 2911, 2954
  - \ledlsnotesep . . . . . 27, 985, 2911
  - \ledlsnotewidth . . . . . 27, 2911, 2954
  - \ledplinumtrue . . . . . 2468
  - \ledrightnote . . . . . 27, 2918
  - \ledrlfill . . . . 975, 989, 3094, 3101
  - \ledrsnotefontsetup . . . 27, 2911, 2962
  - \ledrsnotesep . . . . . 27, 987, 2911
  - \ledrsnotewidth . . . . . 27, 2911, 2962
  - \ledsection . . . . . 152
  - \ledsection\* . . . . . 152
  - \ledsectnotoc . . . . . 33, 257
  - \ledsetnormalparstuff . . . . . 1413, 1637, 1911, 2151
  - \ledsidenote . . . . . 27, 2918
  - \ledsubsection . . . . . 152
  - \ledsubsection\* . . . . . 152
  - \ledsubsubsection . . . . . 152
  - \ledsubsubsection\* . . . . . 152
  - \left . . . . . 3643, 3646, 3651, 3654
  - \leftctab . . . . . 3713, 3811
  - \leftlinenum . . . . 12, 411, 1126, 1138
  - \leftltab . . . . . 3704, 3793
  - \leftmargin . . . . . 219, 220, 241, 242
  - \leftnoteupfalse . . . . . 27
  - \leftnoteuptrue . . . . . 2970
  - \leftpstartnum . . . . . 1195
  - \leftrtab . . . . . 3708, 3759
  - Leibniz . . . . . 8
  - \lemma . . . . . 15, 851
  - \lemmaseparator . . . . . 18, 2472
  - \letsforverteilen . . . . . 3497, 3519, 3536, 3550, 3564, 3577, 3592
  - \line@list 268, 449, 477, 702, 840, 844
  - \line@list@stuff . . . . . 132, 286, 708
  - \line@margin . . . . . 323, 1131, 1206
  - \line@num . . . . . 142, 415, 443, 501, 535, 541, 552, 582, 583, 585, 593, 598, 599, 611, 695, 699, 1003, 1027, 1037, 1102, 1104, 1105, 1114, 1115, 1676, 2763, 2995
  - \line@set . . . . . 855, 856
  - \lineation . . . . . 11, 52, 55, 296
  - \lineinfo@ . . . . . 2484, 2487, 2557
  - \linenum . . . . . 15, 852, 2802, 3405, 3473, 3484, 3503
  - \linenum@out . . . 705, 711, 713, 715, 716, 719, 721, 724, 729, 733, 736, 741, 748, 751, 752, 758, 2720
  - \linenumberlist . . . 12, 27, 1103, 1115
  - \linenumberstyle . . . . . 13, 402
  - \linenumincrement . . . . . 10, 12, 362
  - \linenummargin . . . . . 12, 57, 323
  - \linenumr@p . . . . . 402
  - \linenumrep . . . . . 402, 415, 1510, 1514, 2763, 2850, 2854
  - \linenumsep . . . . . 12, 411, 1225, 1230, 2913, 2914
  - \lineref . . . . . 26, 2769, 3125
  - \linewidth . . . . . 973
  - \list@clear . . . . . 429, 477–480, 896
  - \list@clearing@reg . . . . . 465, 476
  - \list@create . . . . . 428, 449–452, 761, 1235, 2715
  - \listadd . . . . . 2330, 2342
  - \listead . . . . . 2329, 2344
  - \listgadd . . . . . 2951
  - \listxadd . . . . . 2322
  - \lock@disp . . . . 367, 1167, 1171, 1175
  - \lock@off . . . . . 624, 625, 651, 752
  - \lock@on . . . . . 622, 751
  - \lockdisp . . . . . 13, 59, 367
  - Lorch, Richard . . . . . 7
  - \ltab . . . . . 3306, 3791, 3899
  - \ltabtext . . . . . 3308, 3801, 3903
  - \luatexpardir . . . . . 1315, 1321, 1416
  - \luatextextdir . . . . . 1313, 1319, 1415
  - Luecking, Dan . . . . . 40
- M**
- \m@m@makecolfloats . . . . . 2567, 2586
  - \m@m@makecolintro . . . . . 2567
  - \m@m@makecoltext . . . . . 2567, 2587

- \m@dodoreinextrafeet ..... 2638
  - \m@doextrafeet ..... 2637
  - \m@mmf@check ..... 1807, 1824, 1875
  - \m@mmf@prepare .....
    - ..... 1804, 1819, 1828, 1879, 2296
  - \m@th ..... 3661
  - \makehboxofhboxes .....
    - ..... 1647, 1657, 1662, 2157, 2166
  - \makeindex ..... 3128, 3164
  - \makememindexhook ..... 3128
  - \managestanza@modulo .... 3250, 3267
  - \marginparwidth ..... 2911, 2912
  - \mathchardef ..... 3245
  - \maxdepth ..... 2588
  - \maxdimen ..... 1602, 1617, 2124, 2138
  - \maxhnotesX ..... 21
  - \maxhXnotes ..... 20
  - Mayer, Gyula ..... 8
  - \measurebody .. 3761, 3767, 3795, 3813
  - \measurecell ..... 3413, 3439
  - \measuremrow ..... 3437, 3772
  - \measuretbody .. 3777, 3783, 3803, 3821
  - \measuretbody .. 3777, 3783, 3803, 3821
  - \measuretbody .. 3777, 3783, 3803, 3821
  - \measuretbody .. 3777, 3783, 3803, 3821
  - \measuretbody .. 3777, 3783, 3803, 3821
  - \measuretbody .. 3777, 3783, 3803, 3821
  - \measuretbody .. 3777, 3783, 3803, 3821
  - \measuretbody .. 3777, 3783, 3803, 3821
  - \message ..... 50, 131
  - Middleton, Thomas ..... 8, 54
  - minipage (environment) ..... 24
  - Mittelbach, Frank ..... 7
  - \morenoexpands ..... 35, 764
  - \moveleft ..... 3706, 3711, 3719
  - \moveright ..... 3732, 3745, 3754
  - \mpnormalfootgroup ..... 1530, 1558
  - \mpnormalfootgroupX ..... 1936, 1975
  - \mpnormalvfootnote .....
    - ..... 1403, 1557, 1704, 1756
  - \mpnormalvfootnoteX .....
    - ..... 1897, 1974, 1987, 2038
  - \mppara@footgroup ..... 1574, 1652
  - \mppara@footgroupX ..... 2092, 2155
  - \mppara@vfootnote ..... 1573, 1611
  - \mppara@vfootnoteX ..... 2091, 2118
  - \mpthreecolfootgroup .... 1705, 1741
  - \mpthreecolfootgroupX ... 2039, 2070
  - \mpthreecolfootsetup .... 1706, 1712
  - \mpthreecolfootsetupX ... 2040, 2042
  - \mptwocolfootgroup ..... 1757, 1789
  - \mptwocolfootgroupX ..... 1988, 2020
  - \mptwocolfootsetup ..... 1758, 1789
  - \mptwocolfootsetupX ..... 1989, 1991
  - \multfootsep ..... 28, 1801, 1811
  - \multiplefootnotemarker .....
    - ..... 1801, 1805, 1806, 1808
- N
- \n@num ..... 672, 758
  - \n@num@reg ..... 672
  - \NeedsTeXFormat ..... 2
  - \new ..... 2328–
    - 2330, 2332, 2341, 2342, 2344, 2345
  - \new@line ..... 719, 975
  - \newbox ..... 869, 872,
    - 2908, 2909, 3326, 3328, 3896, 3897
  - \newcommandx .....
    - . 1298, 1311, 1330, 1422, 1626,
    - 1635, 1721, 1768, 2365, 2457, 2472
  - \newcounter .....
    - . 353, 355, 357, 359, 875, 1010,
    - 2299, 2735, 2736, 3118, 3253, 3666
  - \newhookcommand@series ..... 2376
  - \newhookcommand@series@reload . 2439
  - \newhooktoggle@series .....
    - ..... 2453, 2456, 2459–2464
  - \newif .. 4–6, 20, 30, 115, 116, 118,
    - 121, 122, 294, 295, 445, 458,
    - 706, 754, 837, 870, 877, 879,
    - 935, 1196, 1221, 1455, 1457,
    - 1459, 1461, 1463, 2467, 2658,
    - 2808, 2923, 2969, 3219, 3221, 3680
  - \newinsert ..... 2249–2252
  - \newlength ..... 411, 3237
  - \newlinechar ..... 2307
  - \newread ..... 463
  - \newseries ..... 2200, 2324, 2325
  - \newseries@ ..... 2201, 2205
  - \newtoggle ..... 1538, 1542,
    - 2225–2228, 2230, 2233, 2470, 2471
  - \newwrite ..... 705, 2807
  - \NEXT ..... 3409,
    - 3414, 3417, 3422, 3423, 3426,
    - 3429, 3434, 3435, 3438, 3440,
    - 3441, 3443, 3445, 3446, 3451,
    - 3598, 3601, 3603, 3604, 3606,
    - 3608, 3609, 3612, 3614, 3615,
    - 3617, 3619, 3620, 3623, 3625,
    - 3626, 3628, 3630, 3631, 3636,
    - 3638, 3639, 3833, 3836, 3837,
    - 3842, 3846, 3847, 3863, 3869, 3870
  - \Next ..... 3451, 3511,
    - 3513, 3522, 3523, 3528, 3530,
    - 3539, 3540, 3543, 3545, 3552,

- 3553, 3557, 3559, 3566, 3567,  
 3570, 3572, 3580, 3581, 3585,  
 3587, 3595, 3596, 3851, 3853, 3854  
 \next@action ..... 89, 473, 1016,  
 1024, 1025, 1031, 1032, 1040, 1049  
 \next@actionline .....  
 . 470, 472, 1015, 1023, 1046, 1048  
 \next@insert .....  
 897, 1239, 1242, 1244, 1247, 1251  
 \next@page@num .....  
 ..... 147, 504, 506, 544, 556, 605  
 \no@expands ..... 764, 794, 816, 851  
 \noalign ..... 1690  
 \noendnotes ..... 25, 2866  
 \noindent .. 952, 1193, 1420, 1526,  
 1528, 1534, 1595, 1603, 1607,  
 1618, 1650, 1660, 1737, 1745,  
 1784, 1796, 2125, 2139, 2160, 2169  
 \nolemmaseparator ..... 19, 2472  
 \nonbreakableafternumber ..... 18  
 \nonum@ ..... 2470  
 \nonumberinfootnote ..... 17  
 \noquotation@true ..... 8  
 \normal@footnotemarkX ... 1882, 1963  
 \normal@pars ..... 261, 898,  
955, 1419, 1722, 1769, 2009, 2060  
 \normalbfnoteX ..... 1942, 1955  
 \normalbodyfootmarkX .... 1887, 1964  
 \normalcolor 1532, 1654, 1743, 1794,  
 1938, 2026, 2076, 2163, 2601, 3072  
 \normalfont .... 413, 1802, 1888, 2465  
 \normalfootfmt ..... 1413, 1550  
 \normalfootfmtX ..... 1907, 1967  
 \normalfootfootmarkX .... 1916, 1968  
 \normalfootgroup ..... 1528, 1551  
 \normalfootgroupX ..... 1933, 1969  
 \normalfootnoterule ..... 1527, 1553  
 \normalfootnoteruleX 1931, 1970, 2089  
 \normalfootstart ..... 1517, 1548  
 \normalfootstartX ..... 1919, 1962  
 \normalvfootnote ... 1379, 1390, 1549  
 \normalvfootnoteX ..... 1889, 1965  
 \nosep@ ..... 2471  
 \notblank ..... 1309  
 \notbool ..... 1390, 1403,  
 1422, 1716, 1721, 1764, 1768, 2254  
 \notefontsetup .....  
 .... 1736, 2217–2219, 2465, 2475  
 \notefontsizeX ..... 19  
 \notenumfont ..... 2214–2216, 2465  
 \notenumfontX ..... 19  
 \noteschanged@false ..... 458, 483  
 \noteschanged@true .....  
 .... 266, 269, 458, 488, 841, 1241  
 \nulledindex .... 3391, 3472, 3483,  
 3509, 3526, 3542, 3556, 3569, 3584  
 \nullsetzen ..... 3633, 3770, 3786  
 \num@lines . 869, 911, 1258, 1264, 1267  
 \numberedpar@false ..... 869  
 \numberedpar@true ..... 869, 900  
 \numberingfalse ..... 115, 260  
 \numberingtrue ..... 115, 128, 280  
 \numberlinefalse ..... 11  
 \numberlinetrue ..... 11, 838  
 \numberonlyfirstinline ..... 17  
 \numberonlyfirstintwoline ..... 17  
 \numberpstartfalse ..... 11, 874  
 \numberpstarttrue ..... 11, 874  
 \numdef ..... 2985, 2992  
 \numlabfont ..... 21, 411
- O**
- \one@line ..... 869, 963, 964, 975  
 \onlypstartinfootnote ..... 18  
 \openout ..... 713, 716, 2809
- P**
- \p@pstart ..... 902  
 \PackageError ..... 34  
 \PackageWarning ..... 33  
 \page@action ..... 505, 603, 689  
 \page@num ..... 454,  
 468, 543, 554, 694, 699, 1025,  
 1133, 1208, 1674, 1683, 2995, 3007  
 \page@start ..... 725, 2591  
 \pagelinesep ..... 29, 3116, 3125  
 \pageno ..... 91, 93, 2563  
 \pageparbreak ..... 35, 1193  
 \pageref ..... 27  
 \par@line .....  
 . 869, 912, 1259, 1260, 1263, 1267  
 \para@footgroup ..... 1570, 1645  
 \para@footgroupX ..... 2088, 2155  
 \para@footsetup ..... 1572, 1578  
 \para@footsetupX ..... 2094, 2096  
 \para@vfootnote ..... 1568, 1596  
 \para@vfootnoteX ..... 2086, 2118  
 \parafootfmt ..... 1569, 1635  
 \parafootfmtX ..... 2087, 2146  
 \parafootftmsep ..... 2242, 2477

- `\parafootsep` ..... 20
  - `\parafootstart` ..... 1567, [1586](#)
  - `\parafootstartX` ..... 2085, [2104](#)
  - `\parapparatus@false` ..... 7
  - `\parapparatus@true` ..... 11
  - `\patchcmd` . 197, 200, 201, 204, 208, 209
  - `\pausenumbering` ..... 11, [279](#)
  - `\pend` ..... 9, 81, 84, 154, 156,  
161, 163, 168, 170, 175, 177,  
182, 184, 189, 191, 195, 196,  
207, 894, [904](#), 953, 1193, 3290, 3292
  - `\PlainTeX` ..... 1382
  - Plato of Tivoli ..... 7
  - `\postbodyfootmark` .. 1868, 1878, 1885
  - `\postdisplaypenalty` ..... 933
  - `\prebodyfootmark` ... 1867, 1871, 1883
  - `\predisplaypenalty` ..... 932
  - `\prenotesX` ..... 20, 1545
  - `\prenotesX@` .... 1544, 1545, 1920, 2105
  - `\pretocmd` ..... 198, 202
  - `\prevgraf` ..... 911
  - `\prevline` ..... 1675, 2502
  - `\prevpage@num` ..... [1673](#)
  - `\preXnotes` ..... 20, [1538](#), [1542](#)
  - `\preXnotes@` .... 1518, [1538](#), [1542](#), 1588
  - `\printendlines` ..... 2818, [2848](#)
  - `\printlinefootnote` .....  
.... 1425, 1638, 1729, 1776, [2478](#)
  - `\printlines` ..... [1507](#),  
2519, 2523, 2533, 2537, 2547, 2552
  - `\printnpnum` .... 25, 2850, 2853, [2858](#)
  - `\printpstart` ..... [1444](#),  
2518, 2522, 2532, 2536, 2546, 2551
  - `\processl@denvbody` .....  
..... 3195, 3199, 3200, 3215
  - `\ProcessOptions` ..... 13
  - `\protected@csxdef` ..... 2294
  - `\protected@edef` .....  
..... 901, 1908, 2006, 2056, 2147
  - `\protected@write` .....  
2731, 3149, 3154, 3157, 3172, 3181
  - `\ProvidesPackage` ..... 3
  - `\pst@rtedLfalse` ..... [116](#), 139, 263
  - `\pst@rtedLtrue` ..... [116](#), 283
  - `\pstart` ..... 9, 75, 78, 79,  
84, 155, 158, 162, 165, 169, 172,  
176, 179, 183, 186, 190, 193,  
195, 196, 207, [874](#), 952, 1193, 3271
  - `\pstartinfootnote` .. 17, 304, 310, 316
  - `\pstartline` ..... 915, 918
  - `\pstartnum` ..... [1195](#)
  - `\pstartnumfalse` ..... 1226, 1233
  - `\pstartnumtrue` ..... 925, 1222
- Q**
- `\quotation` ..... [152](#)
  - `\quote` ..... [152](#)
- R**
- `\raggedright` .....  
.... 1726, 1773, 2015, 2065, 2916
  - `\raw@text` ..... [869](#), 899, 914, 963
  - `\rbracket` ..... 21, [1432](#), 2237
  - `\read@linelist` ..... [463](#), 709
  - `\ref` ..... 27, 1862
  - `\Relax` ..... [3409](#), 3850, 3857
  - `\rem@inder` ..... 1115, 1117–1119
  - `\removehboxes` .....  
.... 1648, 1658, [1662](#), 2158, 2167
  - `\removelastskip` ..... 3510, 3527
  - `\RequirePackage` ..... 15, 16, 18, 19
  - `\reserveinserts` ..... 17
  - `\resetprevline@` 57, 149, [459](#), 918, 1028
  - `\resumenumbering` ..... 11, [279](#)
  - `\right` ..... 3644, 3647, 3652, 3655
  - `\rightctab` ..... [3722](#), 3812
  - `\rightlinenum` .... 12, [411](#), 1128, 1136
  - `\rightltab` ..... [3735](#), 3794
  - `\rightnoteupfalse` ..... 27
  - `\rightnoteuptrue` ..... 2924
  - `\rightpstartnum` .... 1203, 1211, 1228
  - `\rightrtab` ..... [3748](#), 3760
  - `\rightstartnum` ..... [1195](#)
  - `\rigidbalance` ... [1685](#), 1740, 1748,  
1787, 1799, 2023, 2030, 2073, 2080
  - `\rlap` ..... 1128, 1136, 1203, 1211
  - Robinson, Peter ..... 5
  - `\roman` ..... 3667
  - `\rtab` ..... 3304, [3757](#), 3901
  - `\rtabtext` ..... 3307, [3775](#), 3905
- S**
- Sacrobosco ..... 8
  - `\sc@n@list` ..... 1116, 1118
  - Schöpf, Rainer ..... 7
  - `\section@num` .....  
..... [112](#), 129, 131, 132, 284–286, 2816
  - `\select@lemmafnt` ..... 765, [1293](#)
  - `\select@lemmafnt` ..... 22,  
[1293](#), 1426, 1639, 1730, 1777, 2819



- `\series` .. [2200](#), [2327](#), [2329](#), [2340](#), [2344](#)
- `\seriesatbegin` ..... [2326](#)
- `\seriesatend` ..... [2336](#), [2339](#)
- `\set@line` ..... [795](#), [817](#), [839](#)
- `\set@line@action` [498](#), [588](#), [595](#), [606](#), [691](#)
- `\setcommand@series` ..... [2365](#)
- `\setl@dlp@rbox` . [2949](#), [2953](#), [3000](#), [3012](#)
- `\setl@drp@rbox` . [2950](#), [2961](#), [3002](#), [3010](#)
- `\setl@drpr@box` ..... [2953](#)
- `\setline` ..... [13](#), [71](#), [737](#), [769](#), [918](#)
- `\setlinenum` ..... [13](#), [73](#), [744](#)
- `\setmcellcenter` ..... [3568](#), [3624](#)
- `\setmcellleft` ..... [3541](#), [3613](#)
- `\setmcellright` ..... [3508](#), [3602](#)
- `\setmrowcenter` ..... [3622](#), [3816](#)
- `\setmrowleft` ..... [3611](#), [3798](#)
- `\setmrowright` ..... [3600](#), [3764](#)
- `\setprintendlines` ..... [2824](#), [2849](#)
- `\setprintlines` ..... [1481](#), [1508](#)
- `\setstanzaindents` ..... [22](#), [3250](#)
- `\setstanzapenalties` ..... [23](#), [3250](#)
- `\setstanzavalues` [3240](#), [3250](#), [3251](#), [3301](#)
- `\settcclcenter` ..... [3583](#), [3629](#)
- `\settcclleft` ..... [3555](#), [3618](#)
- `\settcclright` ..... [3525](#), [3607](#)
- `\settoggle` ..... [1301](#), [1305](#), [2357](#)
- `\settoggle@series` .. [2352](#), [2356](#), [2457](#)
- `\setthrowcenter` ..... [3627](#), [3824](#)
- `\setthrowleft` ..... [3616](#), [3806](#)
- `\setthrowright` ..... [3605](#), [3780](#)
- `\Setzen` ..... [3841](#), [3850](#), [3852](#)
- `\showlemma` ..... [21](#), [34](#), [803](#), [825](#)
- `\sidenote@margin` ..... [2877](#), [3005](#)
- `\sidenotecontent@` ..... [2984](#),  
2989, 2990, 3000, 3002, 3010, 3012
- `\sidenotemargin` ..... [27](#), [2877](#)
- `\sidenotemmargin` ..... [98](#)
- `\sidenotesep` ..... [28](#), [2971](#)
- `\skip` ..... [1521](#), [1524](#),  
1531, 1556, 1561, 1591, 1594,  
1653, 1742, 1793, 1923, 1926,  
1937, 1973, 1978, 2025, 2075,  
2108, 2111, 2115, 2162, 2599, 3071
- `\skip@lockoff` ..... [625](#), [651](#)
- `\skipnumbering` ..... [14](#), [154](#), [156](#),  
161, 163, 168, 170, 175, 177,  
182, 184, 189, 191, 195, 196,  
205, 206, 213, 226, 235, 248, [754](#)
- `\skipnumbering@reg` ..... [754](#)
- `\spacefactor` .....  
1809, 1812, 1823, 1829, 1874, 1880
- `\spaceskip` ..... [1395](#), [1894](#), [2002](#)
- `\splitmaxdepth` ..... [1400](#)
- `\splitoff` ..... [1685](#)
- `\splittopskip` .... [960](#), [1400](#), [1687](#),  
1738, 1740, 1746, 1748, 1785,  
1787, 1797, 1799, 2021, 2023,  
2028, 2030, 2071, 2073, 2078, 2080
- `\spreadmath` ..... [30](#), [3829](#)
- `\spreadtext` ..... [30](#), [3827](#)
- `\stanza` ..... [22](#), [3279](#)
- `\stanza@count` ..... [3231](#), [3242](#),  
3245, 3247, 3264, 3276, 3283, 3291
- `\stanza@hang` ..... [3262](#), [3285](#)
- `\stanza@line` ..... [3262](#), [3291](#), [3293](#)
- `\stanza@modulo` .....  
.... [3254](#), [3257–3259](#), [3268](#), [3283](#)
- `\stanzaindentbase` .....  
.. [22](#), [3231](#), [3265](#), [3269](#), [3274](#), [3295](#)
- `\startlock` ..... [13](#), [751](#), [767](#), [3272](#)
- `\startstanzahook` ..... [24](#), [3279](#)
- `\startsub` ..... [13](#), [727](#), [766](#)
- `\stepcounter` .....  
.... [2293](#), [2739](#), [2742](#), [3121](#), [3675](#)
- `\stepl@dcclcount` .... [3375](#), [3420](#),  
3432, 3517, 3534, 3548, 3562,  
3575, 3590, 3634, 3834, 3843, 3864
- `\strip@pt` ..... [1584](#), [2102](#)
- `\strip@szacnt` ..... [3240](#)
- `\sub@action` ..... [514](#), [615](#), [690](#)
- `\sub@change` ..... [148](#),  
508, 509, 515, 565, 567, 570, 572
- `\sub@lock` .... [145](#), [447](#), [523](#), [525](#),  
527, 530, 633, 634, 636, 637,  
655, 656, 658, 998, 1070, 1072,  
1073, 1075, 1150, 1186, 1188, 1190
- `\sub@off` ..... [564](#), [733](#)
- `\sub@on` ..... [564](#), [729](#)
- `\subline@num` ... [143](#), [417](#), [418](#), [444](#),  
531, 535, 541, 552, 576, 577,  
579, 591, 609, 696, 700, 999,  
1004, 1027, 1035, 1090–1092, 2764
- `\sublinenumberstyle` ..... [13](#), [402](#)
- `\sublinenumincrement` .... [11](#), [12](#), [362](#)
- `\sublinenumr@p` ..... [402](#)
- `\sublinenumrep` ..... [402](#),  
418, 1511, 1515, 2764, 2851, 2855
- `\sublineref` ..... [26](#), [2772](#)
- `\sublines@false` .. [146](#), [445](#), [512](#), [1060](#)

- \sublines@true . . . . . [445](#), 510, 1058
  - \sublock@disp . . . . . [393](#), 1152, 1156, 1160
  - \sublockdisp . . . . . 61, [393](#)
  - \subsection . . . . . 170, 177, 1356, 1859, 2349
  - \subsubsection . . . . . 184, 191, 2351
  - Sullivan, Wayne . . . . . 7,  
8, 22, 34, 40, 48, 102, 103, 136, 155
  - \symlinenum . . . . . 17
  - \symplinenum . . . . . 2229, [2465](#)
  - \sza@penalty . . . . . [3262](#), 3289, 3290
- T**
- \tabellzwischen . . . . . [3832](#), 3840
  - \tabelskip 3844, 3884–3886, 3892–3894
  - \tabhilfbox . . . . . 3883,  
3885, 3887, 3891, 3893, 3895, [3896](#)
  - \tabhilfbox . . . . . 3882,  
3884, 3886, 3890, 3892, 3894, [3896](#)
  - Tapp, Christian . . . . . 6
  - \textheight . . . . . 2697
  - \textnormal . . . . . 1432–1434
  - \textsuperscript . . . . . 1802, 1888, 1917
  - \texttt . . . . . 1373, 1375
  - \textwidth . . . . . 3049, 3091
  - \theadcolcount . . . . . [3666](#), 3673, 3676
  - \thefootnoteA . . . . . 28
  - \thelabidx . . . . . 3122, 3125
  - \theline . . . . . 2743, 2745
  - \thempfn . . . . . 3051, 3077, 3104
  - \thempfootnote . . . . . 3051, 3077, 3104
  - Theodosius . . . . . 8
  - \thepage . . . . . 719, 2732, 3125
  - \thepageline . . . . .  
3124, 3150, 3155, 3158, 3173, 3182
  - \thepstart . . . . . 11, [874](#),  
876, 899, 902, 952, 1224, 1231, 1452
  - \thepstartL . . . . . 1449
  - \thepstartR . . . . . 1447
  - \thesubline . . . . . 2743
  - \thinspace . . . . . 1437, 1439
  - \thr@@ . . . . . 344, 636, 645, 656, 663,  
1065, 1073, 1711, 1714, 1740,  
1748, 2044, 2047, 2073, 2080, 2898
  - \threecolfootfmt . . . . . 1701, [1721](#)
  - \threecolfootfmtX . . . . . 2035, [2055](#)
  - \threecolfootgroup . . . . . 1702, [1736](#)
  - \threecolfootgroupX . . . . . 2036, [2070](#)
  - \threecolfootsetup . . . . . 1703, [1709](#)
  - \threecolfootsetupX . . . . . 2037, [2042](#)
  - \threecolvfootnote . . . . . 1700, [1716](#)
  - \threecolvfootnoteX . . . . . 2034, [2049](#)
  - \togglefalse . . . . . 1521, 1591, 1923, 2108
  - \toggletrue . . . . . 1539, 1543
  - \tolerance . . . . . 1725, 1772, 2014, 2064
  - \twocolfootfmt . . . . . 1753, [1761](#)
  - \twocolfootfmtX . . . . . 1984, [2005](#)
  - \twocolfootgroup . . . . . 1754, [1761](#)
  - \twocolfootgroupX . . . . . 1985, [2020](#)
  - \twocolfootsetup . . . . . 1755, [1761](#)
  - \twocolfootsetupX . . . . . 1986, [1991](#)
  - \twocolvfootnote . . . . . 1752, [1761](#)
  - \twocolvfootnoteX . . . . . 1983, [1998](#)
  - \txtbeforeXnotes . . . . . 20
- U**
- \unhbox 957, 1629, 1648, 1650, 1658,  
1660, 1667, 1671, 2158, 2160,  
2167, 2169, 3886, 3887, 3894, 3895
  - \unkern . . . . . 1810
  - \unpenalty . . . . . 1632, 1664
  - \unvbox . . . . . 964, 1405, 1528, 1535,  
1613, 1627, 1646, 1656, 1696,  
1899, 1934, 1940, 2134, 2156,  
2165, 2173, 2179, 2188, 2193,  
2578, 2598, 2603, 2616, 2626,  
2631, 2633, 2652, 2680, 3068, 3074
  - \unvxh . . . . . 1604, 1619, [1626](#), 2126, 2140
  - \usingcritext . . . . . [3907](#)
  - \usingedtext . . . . . [3907](#)
- V**
- \valign . . . . . 1688
  - \value . . . . . 3258, 3263, 3672
  - Vamana . . . . . 8
  - \variab . . . . . [3453](#), 3763,  
3779, 3797, 3805, 3815, 3823, 3856
  - \vbadness . . . . . 959, 1687
  - \vbfnoteX . . . . . 1944, [1949](#)
  - \vbox . . . . . 899, 1404, 1602, 1612,  
1617, 1627, 1898, 2124, 2133,  
2138, 2172, 2187, 2575, 2595,  
2615, 2705, 2709, 2957, 2959,  
2965, 2967, 3046, 3643, 3646,  
3651, 3654, 3658, 3660, 3661,  
3705, 3709, 3714, 3725, 3738, 3751
  - \vfil . . . . . 1688, 2709,  
3644, 3647, 3652, 3655, 3658, 3661
  - \vl@dbfnote . . . . . [1840](#)
  - \vl@dcsnote . . . . . 2944, [2949](#)
  - \vl@dlsnote . . . . . 2929, [2949](#)

<code>\vl@drsnote</code> . . . . .	2937, <a href="#">2949</a>	<code>\Xendnotenumfont</code> . . . . .	<a href="#">19</a>
<code>\vnumfootnoteX</code> . . . . .	<a href="#">1953</a> , 1966	<code>\Xhangindent</code> . . . . .	<a href="#">19</a>
<code>\vrule</code> . . . . .	3643, 3646, 3651, 3654, 3658	<code>\xifinlist</code> . . . . .	2206
<code>\vsize</code> . . . . .	1537	<code>\xleft@appenditem</code> . . . . .	<a href="#">436</a>
<code>\vsplit</code> . . . . .	963, 1695, 2680	<code>\xlineref</code> . . . . .	<a href="#">26</a> , <a href="#">2769</a>
<b>W</b>			
<code>\wd</code> . . . . .	952, 975, 1606, 1621, 2128, 2142, 3381, 3382, 3505, 3718, 3727, 3730, 3740, 3743, 3752, 3884, 3885, 3892, 3893	<code>\Xnotefontsize</code> . . . . .	<a href="#">19</a>
Whitney, Ron . . . . .	7	<code>\Xnotenumfont</code> . . . . .	<a href="#">19</a>
<code>\widowpenalty</code> . . . . .	933, 1265	<code>\xpageref</code> . . . . .	<a href="#">26</a> , <a href="#">2766</a>
<code>\WithSuffix</code> . . . . .	160, 174, 188, 196	<code>\xright@appenditem</code> . . . . .	430, 604, 605, 607, 614, 616, 618, 620, 630, 632, 641, 652, 654, 661, 674, 675, 684, 698, 1301, 1305, 1313, 1315, 1319, 1321, 1333, 1336, 1339, 1344, 1347, 1350, 1843, 1944, 2265, 2276, 2762, 2929, 2937, 2944
Wujastyk, Dominik . . . . .	5, 6	<code>\xspaceskip</code> . . . . .	1395, 1894, 2002
<b>X</b>			
<code>\x@lemma</code> . . . . .	805–807, 827–829	<code>\xsublineref</code> . . . . .	<a href="#">26</a> , <a href="#">2772</a>
<code>\xcritext</code> . . . . .	<a href="#">3385</a> , 3498	<code>\xxref</code> . . . . .	<a href="#">26</a> , <a href="#">2797</a>
<code>\xedindex</code> . . . . .	<a href="#">3391</a> , 3477, 3488, 3500	<b>Z</b>	
<code>\xedlabel</code> . . . . .	<a href="#">3389</a> , 3506	<code>\z@skip</code> . . . . .	1395, 1401, 1894, 2002
<code>\xedtext</code> . . . . .	<a href="#">3385</a> , 3499	<code>\zz@@@</code> . . . . .	<a href="#">2716</a> , 2722, 2799, 2801
<code>\Xendnotefontsize</code> . . . . .	<a href="#">19</a>		

## Change History

v0.1	General: First public release . . . . .	1	Possibility to number the pstart with the commands <code>\numberpstarttrue</code> . . . . .	1
v0.10	General: Corrections to <code>\section</code> and other titles in numbered sections . . . . .	1	<code>\ifledRcol</code> : Added <code>\ifledRcol</code> and <code>\ifnumberingR</code> for/from eledpar . . . . .	44
v0.11	General: Makes it possible to add a symbol on each verse's hang- ing, as in French typogra- phy. Redefines the command <code>\hangingsymbol</code> to define the character. . . . .	1	v0.12.1 General: Don't number <code>\pstarts</code> of stanza. . . . .	1
			The numbering of <code>\pstarts</code> restarts on each <code>\beginnumbering</code> . . . . . .	1
v0.12	General: For compatibility with eledpar, possibility to use <code>\autopar</code> on the right side. . . . .	1	v0.13 General: New <code>stanzaindentsrepeti-</code> tion counter to repeat stanza in- dents every <i>n</i> verses. . . . .	23
	Possibility to number <code>\pstart</code> . . . . .	11	New <code>stanzaindentsrepetition</code> counter: to repeat stanza in-	

dents every $n$ verses. . . . .	1	General: Added text about normal labeling . . . . .	27
<code>\managestanza@modulo</code> : New stanzaindentsrepetition counter to repeat stanza indents every $n$ verses. . . . .	156	Bug fixes and match with mempatch v1.8 . . . . .	1
v0.13.1		Major changes to insert code when memoir is loaded . . . .	133
General: <code>\thepstartL</code> and <code>\thepstartR</code> use now <code>\bfseries</code> and not <code>\bf</code> , which is deprecated and makes conflicts with memoir class. . . . .	1	<code>\doxtrafeet</code> : Renamed <code>\doxtrafeet</code> to <code>\l@ddoxtrafeet</code> . . . . .	133
v0.14		<code>\edlabel</code> : Tweaked <code>\edlabel</code> to get correct page numbers . . .	136
General: Tweaked <code>\edlabel</code> to get correct line number if the command is first element of a paragraph. . . . .	1	<code>\l@d@makecol</code> : Rewrote <code>\makecol</code> , calling it <code>\l@d@makecol</code> . . .	132
<code>\edlabel</code> : Tweaked <code>\edlabel</code> to get correct line number if the command is first element of a paragraph. . . . .	136	<code>\l@ddodoreinextrafeet</code> : Renamed <code>\dodoreinextrafeet</code> to <code>\l@ddodoreinextrafeet</code> . . .	133
v0.15		<code>\l@ddofootinsert</code> : Renamed <code>\dofootinsert</code> as <code>\l@ddofootinsert</code> . . . . .	132
General: Line numbering can be reset at each <code>pstart</code> . . . . .	48	<code>\m@m@makecolintro</code> : Added <code>\m@m@makecolfloats</code> , <code>\m@m@makecoltext</code> and <code>\m@m@makecolintro</code> . . .	131
New management of hangingsymbol insertion, preventing undesirable insertions. . . . .	155	<code>\morenoexpands</code> : Removed some <code>\lets</code> from <code>\no@expands</code> . These were in EDMAC but I feel that they should not have been as they disabled page/line refs in a footnotes . . . . .	72
Possibility to print <code>\pstart</code> number in side. . . . .	11	<code>\zz@@@</code> : Minor change to <code>\zz@@@</code> .	136
<code>\affixline@num</code> : Line numbering can be disabled. . . . .	84	v0.2.2	
<code>\printlines</code> : Line numbering can be reset at each <code>pstart</code> . . . . .	97	General: Improved paragraph footnotes . . . . .	1
v0.17		New Dekker example . . . . .	1
General: New new management of hangingsymbol insertion, preventing undesirable insertions. . . . .	155	<code>\footfudgefiddle</code> : Added <code>\footfudgefiddle</code> . . . . .	101
v0.2		<code>\l@d@section</code> : Used <code>\providecommand</code> for <code>\@gobblethree</code> to avoid clash with the <code>amsfonts</code> package . . . . .	141
General: Added <code>tabmac</code> code, and extended indexing . . . . .	1	<code>\line@list@stuff</code> : Added initial write of page number in <code>\line@list@stuff</code> . . . . .	66
<code>\eledmac@error</code> : Added <code>\eledmac@error</code> and replaced error messages . .	41	<code>\para@footsetup</code> : Added <code>\footfudgefiddle</code> to <code>\para@footsetup</code> . . . . .	101
<code>\ifl@dmemoir</code> : Added <code>\ifl@dmemoir</code> for memoir class having been used . . . . .	41	<code>\para@footsetupX</code> : Added <code>\footfudgefiddle</code> to <code>\para@footsetupX</code> . . . . .	118
<code>\morenoexpands</code> : Added <code>\l@dtabnoexpands</code> to <code>\no@expands</code> . . . . .	72	v0.3	
v0.2.1		<code>\@lab</code> : Removed page setting from <code>\@lab</code> . . . . .	138
<code>\@lab</code> : Removed page setting from <code>\@lab</code> . . . . .	138	<code>\@l@reg</code> : Added a bunch of code to <code>\@l</code> for handling <code>\setlinenum</code> .	59

\@lab: Replaced \the\line@num by \linenumr@p\line@num in \@lab, and similar for sub-lines	138	General: Added code for changing \docclearpage	134
General: Includes edstanza and more	1	Let eledmac take advantage of memoir's indexing	150
\ledlinenum: Added \linenumr@p and \sublinenum@rep to \leftlinenum and \rightlinenum	52	Not released. Minor editorial improvements and code tweaks	1
\linenumberlist: Added \linenumberlist mechanism	40	Only change \@footnotetext and \@footnotemark if memoir not used	110
\printendlines: Added \linenumr@p and \sublinenumr@p to \printendlines	142	\doxtrafeetii: Changed \doxtrafeetii code for easier extensions	133
\printlines: Added \linenumr@p and \sublinenumr@p to \printlines	97	v0.5	
\sublinenumr@p: Added \linenumberstyle and \sublinenumberstyle	52	\@footnotetext: Enabled regular \footnote in numbered text	111
v0.3.1		\@xympar: Eliminated \marginpar disturbance	143
General: Not released. Added remarks about the parallel package	1	General: Added left and right side notes	143
v0.4		Added sidenotes, familiar footnotes in numbered text	1
\@iiiminipage: Modified kernel \@iiiminipage and \endminipage to cater for critical footnotes	147	v0.5.1	
General: Added \showlemma to \edtext (and \critext)	74	General: Added moveable side note	143
Added minipage, etc., support	1	Fixed right line numbers killed in v0.5	1
ledgroup: Added ledgroup environment	148	\affixline@num: Changed \affixline@num to cater for sidenotes	83
ledgroupsize: Added ledgroupsize environment	148	ledgroupsize: Only change \hsize in ledgroupsize environment otherwise page number can be in wrong place	148
\footnormal: Added minpage footnote setup to \footnormal	100	\l@dgetsidenote@margin: Added \sidenotemargin and \sidenote@margin	143
\ifparapparatus@: Added final/draft options	40	v0.6	
\l@dfeetendmini: Added \l@dfeetbeginmini, \l@dfeetendmini and all their supporting code	146	\@l@reg: Added \fix@page to \@l	59
\mpnormalfootgroup: Added \mpnormalfootgroup	98	Extended \@l to include the page number	59
\mpnormalvfootnote: Added \mpnormalvfootnote	93	\@lopR: Added \@pend, \@pendR, \@lopL and \@lopR in anticipation of parallel processing	61
\showlemma: Added \showlemma	40	General: Fixed long paragraphs looping	1
v0.4.1		Fixed minor typos	1
\@opxtrafeetii: Added \@opxtrafeetii	133	Prepared for eledpar package	1
		\fix@page: Added \last@page@num and \fix@page	61
		\new@line: Extended \new@line to output page numbers	67

<code>\page@start</code> : Made <code>\page@start</code> a no-op . . . . .	67	<code>\l@getlock@disp</code> : Added	
<code>\v1@dbfnote</code> : Changed <code>\l@dbfnote</code> and <code>\v1@dbfnote</code> as originals could give incorrect markers in the footnotes . . . . .	111	<code>\l@getlock@disp</code> . . . . .	51
v0.7		<code>\l@dgetsidenote@margin</code> : Added	
<code>\@l@reg</code> : Added <code>\@l@reg</code> . . . . .	59	<code>\l@dgetsidenote@margin</code> . .	143
<code>\@ref@reg</code> : Added <code>\@ref@reg</code> . . .	65	<code>\l@drsn@te</code> : Added <code>\l@dlsn@te</code> and <code>\l@drsn@te</code> for use in <code>\do@line</code> . . . . .	80
General: eledmac having been available for 2 years, deleted the commented out original edmac texts . . . . .	1	<code>\l@dunboxmpfoot</code> : Added	
Maïeul Rouquette new maintainer . . . . .	1	<code>\l@dunboxmpfoot</code> containing some common code . . . . .	148
Made macros of all messages . .	41	<code>\l@dzeropenalties</code> : Added	
Replaced all <code>\interAfootnotelinepenalty</code> , etc., by just <code>\interfootnotelinepenalty</code> . . . . .	1	<code>\l@dzeropenalties</code> . . . . .	78
Tidying up for eledpar and ledarab packages . . . . .	1	<code>\ledlinenum</code> : Added <code>\ledlinenum</code> for use by <code>\leftlinenum</code> and <code>\rightlinenum</code> . . . . .	52
<code>\affixline@num</code> : Added skipnummering to <code>\affixline@num</code> . .	83	<code>\line@list@stuff</code> : Deleted	
<code>\do@actions@fixedcode</code> : Added		<code>\page@start</code> from <code>\line@list@stuff</code> . . . . .	66
<code>\do@actions@fixedcode</code> . . . .	82	<code>\list@clearing@reg</code> : Added	
<code>\do@actions@next</code> : Added number skipping to <code>\do@actions</code> . . . .	81	<code>\list@clearing@reg</code> . . . . .	58
<code>\do@linehook</code> : Added <code>\do@linehook</code> for use in <code>\do@line</code> . . . . .	80	<code>\n@num@reg</code> : Added <code>\n@num</code> . . . .	64
<code>\endnumbering</code> : Changed		<code>\normalbfnoteX</code> : Removed	
<code>\endnumbering</code> for eledpar . .	47	extraneous space from	
<code>\f@x@l@cks</code> : Added <code>\ch@cksub@l@ck</code> , <code>\ch@ck@l@ck</code> and <code>\f@x@l@cks</code> . .	86	<code>\normalbfnoteX</code> . . . . .	114
<code>\footplitskips</code> : Added		<code>\resumenummering</code> : Changed	
<code>\footplitskips</code> for use in many footnote styles . . . . .	93	<code>\resumenummering</code> for eledpar .	48
<code>\get@linelistfile</code> : Added		<code>\setprintendlines</code> : Added	
<code>\get@linelistfile</code> . . . . .	58	<code>\setprintendlines</code> for use by <code>\printendlines</code> . . . . .	141
<code>\ifledRcol</code> : Added <code>\l@dnumpstartsL</code> , <code>\ifl@dpairing</code> and <code>\ifpst@rted</code> for/from eledpar . . . . .	44	<code>\setprintlines</code> : Added <code>\setprintlines</code> for use by <code>\printlines</code> . . . .	96
<code>\initnumbering@reg</code> : Added		<code>\skipnumbering@reg</code> : Added	
<code>\initnumbering@reg</code> . . . . .	44	<code>\skipnumbering</code> and supports .	68
<code>\l@dcstotetext</code> : Added <code>\l@demptyd@ta</code> . . . . .	80	<code>\sublinenumincrement</code> : Added	
<code>\l@ddofootinsert</code> : Deleted		<code>\firstlinenum</code> , <code>\linenumincrement</code> , <code>\firstsublinenum</code> and <code>\linenumincrement</code> . . . . .	50
<code>\page@start</code> from <code>\l@ddofootinsert</code> . . . . .	132	<code>\sublinenumr@p</code> : Using <code>\linenumrep</code> instead of <code>\linenumr@p</code> . . . .	52
<code>\l@dgetline@margin</code> : Added		Using <code>\sublinenumrep</code> instead of <code>\sublinenumr@p</code> . . . . .	52
<code>\l@dgetline@margin</code> . . . . .	49	<code>\vnumfootnoteX</code> : Removed	
		extraneous space from	
		<code>\vnumfootnoteX</code> . . . . .	114
		v0.8	
		General: Bug on endnotes fixed: in a // text, all endnotes will print and be placed at the ends of columns () . . . . .	1

v0.8.1	General: Bug on <code>\edtext</code> ; <code>\critex</code> ; <code>\lemma</code> fixed: we can now us non switching commands . . . . .	1	v1.2	General: Add <code>\ledsectnotoc</code> com- mand. . . . .	33
v0.9	General: No more ledpatch. All patches are now in the main file. . . . .	1		<code>\endquote</code> : Compatibility of <code>\ledchapter</code> with the <i>memoir</i> class. . . . .	45
v0.9.1	General: Fix some bugs linked to in- tegrating ledpatch on the main file. . . . .	1	v1.3	<code>\preXnotes</code> : Debug in familiar foot- notes (but introduced by v1.1). . . . .	99
v1.0	General: <code>\lemma</code> can contain com- mands. . . . .	15		<code>\endquote</code> : <i>Quotation</i> and quote environment inside the number- ing sections. . . . .	45
	Debug in lineation command . . . . .	11	v1.4	General: Compatibility of <code>\edtext</code> (and <code>\critext</code> ) with the right- to-left direction (with Polyglos- sia). . . . .	74
	New generic commands to cus- tomize footnote display. . . . .	17		Compatibility with LuaTeX of RTL notes. . . . .	40
	Options nonum and nosep in <code>\Xfootnote</code> . . . . .	15		<code>\newseries@</code> : Remembers the lan- guage of the lemma, in order to create a correct direction for the footnote separator. . . . .	122
	Options of <code>\Xfootnotes</code> . . . . .	91		<code>\normalfootfmt</code> : Direction of foot- notes with polyglossia. . . . .	94
	Possibility to have commands in sidenotes. . . . .	27		<code>\rbracket</code> : Switch the right bracket to a left bracket when the lemma is RTL (needs polyglos- sia). . . . .	94
	Some compatibility break with eledmac. Change of name: eled- mac. . . . .	1			
	<code>\morenoexpands</code> : Change to be compatible with new features . . . . .	72	v1.4.1	<code>\endquote</code> : New option <i>noquota-</i> <i>tion</i> . . . . .	45
v1.0.1	General: Correction on <code>\numberonlyfirstinlinesia</code> or LuaTeX). . . . .	94		<code>\labelrefsparsesubline</code> : Fix bug with <code>\edlabel</code> . . . . .	137
	with lineation by pstart or by page. . . . .	17	v1.4.2	General: Debug with some special classes. . . . .	1
v1.1	General: Add <code>\labelpstarttrue</code> . . . . .	11	v1.4.3	General: Add <code>\nonbreakableafternumber</code> . . . . . .	18
	Add <code>\numberonlyfirstintwolines</code> . . . . .	17		Spurious space after familiar footnotes. . . . .	1
	Add <code>\pstartinfootnote</code> and <code>\onlypstartinfootnote</code> . . . . .	17	v1.4.4	General: Label inside familiar foot- notes. . . . .	1
	New hook to add arbitrary code at the beginning of the notes . . . . .	19	v1.4.5	General: Bug with komasscript + eledpar + chapter. . . . .	1
	New options for block of notes. . . . .	20			
	New package option: parappara- tus. . . . .	1			
	New tools to change order of se- ries . . . . .	124			
	sectioning commands . . . . .	32			
	<code>\ledfootinsdim</code> : Deprecated <code>\ledfootinsdim</code> . . . . .	99			
	<code>\preXnotes</code> : New skip <code>\preXnotes@</code> . . . . .	99			

v1.4.6	tionning commands with	
General: Bug with memoir class in-	<code>\autopar</code> . . . . .	45
troducted by 1.4.5. . . . .		1
v1.4.7		
<code>\endquote</code> : Compatibility of sec-		