

Tabulars with eledmac

October 7, 2015

Abstract

This file provides example of using tabular environments with *eledmac*.
We use `edtabularl`, `edtabularc` and `edtabularr`, with marginal,
critical and familiar notes. We also use optional arguments of `\pstart`.

1 Left align

1		linea prima	linea prima	sidenote l
2		linea secunda	linea secunda ¹	
3		linea tertia	linea tertia	
4		linea quarta	linea quarta	
5		linea quinta	linea quinta ¹	
6		linea sexta	linea sexta	

2 Center align

7		linea prima	linea prima	sidenote c
8		linea secunda	linea secunda ²	
9		linea tertia	linea tertia	
10		linea quarta	linea quarta	
11		linea quinta	linea quinta ²	
12		linea sexta	linea sexta	

3 Right align

13		linea prima	linea prima	sidenote r
<hr/>				
		¹ familiar footnote A.		
		² familiar footnote A.		
<hr/>				
		¹ familiar footnote B.		
		² familiar footnote B.		
<hr/>				
3	tertia]	critical note A		
9	tertia]	critical note A		
<hr/>				
4	quarta]	critical note B		
10	quarta]	critical note B		

14	linea secunda	linea secunda ³
15	linea tertia	linea tertia
16	linea quarta	linea quarta
17	linea quinta	linea quinta ³
18	linea sexta	linea sexta

³familiar footnote A.

³familiar footnote B.

15 tertia] critical note A

16 quarta] critical note B