

Running Headers for Endnotes*

John Burt
burt@brandeis.edu

November 9, 2006

Abstract

`endheads` provides running headers of the form “Notes to pp. xx–yy” for endnotes. `endheads` is designed to work with `endnotes` and `fancyhdr`.

Contents

1	Introduction	1
2	Setup	1
3	Implementation	2
3.1	General Purpose Routines	2
3.2	Building Blocks	3
3.3	User Code	4

1 Introduction

It is a convenience, if you are flipping through the endnotes of a book, to be able to find the endnote you are looking for by looking at the running header. `endheads` uses the `\mark` mechanism to update the running header continuously, so that it always indicates to what pages in the main text the notes on a particular page refer. `endheads` also enables one to reset endnote numbering at the beginning of each chapter.

`endheads` requires the following packages to work correctly: `endnotes` (obviously), `fancyhdr` (also obviously), `ifthen` (for comparing page numbers), `needspace` (to prevent widowed chapter titles in notes sections when resetting notes by chapter using either `\notesbychapter` or `\resetendnotes`), and `titleref` (to send the chapter titles to the notes section).

2 Setup

`\setupendnoteheaders` This is the only macro you need to call to use this package. If you use `\setupendnoteheaders` you should remember to start your endnotes on a new page. `\setupendnoteheaders` sets the first page of the notes section to the `empty`

*This document corresponds to `endheads` 1.152, dated 9 November 2006.

pagestyle, since you normally don't have running headers on the first page of a section. And it changes the pagestyle for subsequent pages to have a running header of the form "Notes to pages xx-yy." This header will appear in the center of each header. Then it modifies the `\endnote` command, having it increment a counter that keeps track of all the endnotes (even if you are resetting the number by chapter), and defines a label for that note. Finally, it writes on the external file for the endnotes a command to set the `\mark` for that page of the endnotes using a `\pageref` to the label it has just defined. `endheads` creates a label and a `\pageref` for every note.

`\notesbychapter` `\notesbychapter` resets the note counter every time you issue a `\chapter` command, and it puts a centered line reading "Chapter <chapter number> <chapter title>" in the notes at that point. If you want only the chapter number, not its title, issue `\titleinnotesfalse` in your preamble. Please note that `endheads` modifies `@chapter`, adding a few lines on to the end of the command. If some other package does the same, you will need to reconcile them.

`\resetendnotes` Conceivably you might wish to do what `\notesbychapter` does for each chapter individually. For instance, there may be a chapter without endnotes, in which case `\notesbychapter` would issue the centered line for that chapter, but no notes would follow, which is ugly. Also, since the Bibliography is, as far as L^AT_EX is concerned, a chapter, you must use `\resetendnotes` before each chapter rather issuing `\notesbychapter` in the preamble if you have a bibliography, or odd results will follow.

3 Implementation

3.1 General Purpose Routines

Essentially these routines are code posted by Heiko Oberdiek to comp.text.tex. If you set a counter from a `\pageref`, that `\pageref` is undefined on the first run, and T_EX will not only complain about the undefined reference, but give a "missing number" error if you try to do anything with that reference, such as compare one page number to another. These commands enable one to use the `\pageref` without generating the missing number error on the first run.

```

1 \providecommand*\ifrefundefined}[1]{%
2   \expandafter\ifx\csname r@#1\endcsname\relax
3     \expandafter\@firstoftwo
4   \else
5     \expandafter\@secondoftwo
6   \fi
7 }
8 \providecommand*\@extract@ref}[2]{%
9   \expandafter\expandafter\expandafter#1\csname
10 r@#2\endcsname\@nil
11 }
12
13 \providecommand*\@extract@ref{%
14   \@extract@ref\@car
15 }
16
17 \providecommand*\@extract@pageref{%
18   \@extract@ref\@secondcar

```

```

19 }
20
21 \long\def\@secondcar#1#2#3\@nil{#2}
22
23 \providecommand*\setcounterfromref}[2]{%
24   \ifrefundefined{#2}{%
25     \protect\G@refundefinedtrue
26     \@latex@warning{Reference ‘#2’ on page \thepage \space
27       undefined}%
28     \setcounter{#1}{0}%
29   }{%
30     \setcounter{#1}{\@extractref{#2}}%
31   }%
32 }
33 \providecommand*\setcounterfrompageref}[2]{%
34   \ifrefundefined{#2}{%
35     \protect\G@refundefinedtrue
36     \@latex@warning{Reference ‘#2’ on page \thepage \space
37       undefined}%
38     \setcounter{#1}{0}%
39   }{%
40     \setcounter{#1}{\@extractpageref{#2}}%
41   }%
42 }
43 \long\def\appendtomacro#1#2{%
44 \begingroup
45   \toks@{\expandafter{#1#2}}%
46   \xdef#1{\the\toks@}%
47 \endgroup}

```

3.2 Building Blocks

First, define some counters:

```

48 \newcounter{allendnotes}
49 \setcounter{allendnotes}{1}
50 \newcounter{notepageholder}

```

`\mymarks` A command to set the marks. This will be called by the page style.

```

51 \newcommand{\mymarks}{%
52   \ifthenelse{equal{\firstmark}{\botmark}}
53     {to p.\firstmark} % if equal
54     {to pp.\firstmark--\botmark}}%if not equal

```

`\endnotespagestyle` A command to set the page style in fancyhdr. You might want to change some aspects of this, such as where to put the page number, to make it consistent with the rest of your document.

```

55 \fancypagestyle{plain}{%
56 \fancyhf{}
57 \fancyhead[R0,LE]{\small\textrm{\thepage}}
58 \renewcommand{\headrulewidth}{0pt}
59 \renewcommand{\footrulewidth}{0pt}
60 }
61 \fancypagestyle{endnotesstyle}{%

```

```

62 \fancyhf{}
63 \fancyhead[CO]{\small{\em Notes~\mymarks}}
64 \fancyhead[CE]{\small{\em Notes~\mymarks}}
65 \renewcommand{\headrulewidth}{0pt}
66 \renewcommand{\footrulewidth}{0pt}
67 \fancyhead[RO,LE]{\small\textrm{\thepage}}
68 }

```

`\checknoteheaders` This macro sets the counter `notepageholder` to the value given by the `pageref` of the note that is being output. All that strange business with `\string` is there because I want to use the `\immediate\write` mechanism to control what gets expanded and what doesn't get expanded on the external file for the endnotes, `\jobname.ent`. Everything except the actual number of the endnote is written to the external file as unexpanded tokens. When, after you call `\theendnotes`, you read in the external file for the endnotes, `\jobname.ent`, all these tokens become a command to set the `\mark`.

```

69 \newcommand{\checknoteheaders}{%
70 \string\setcounterfrompageref\string{notepageholder\string}%
71 \string{notl\theallendnotes\string}%
72 \string\mark\string{\string\thenotepageholder\string}%
73 }

```

3.3 User Code

`\setupendnoteheaders` `\setupendnoteheaders` turns on processing of running headers, and adds two lines to the definition of `\endnote`

```

74 \newif\ifendnoteheaderson \endnoteheadersonfalse
75 \newcommand{\setupendnoteheaders}{%
76 \endnoteheadersontrue
77 \if@enotesopen \else \@openenotes \fi
78 \immediate\write\@enotes{%
79 \string\thispagestyle\string{empty\string}
80 \string\pagestyle\string{endnotesstyle\string}}
81 \def\endnote{\@ifnextchar[\@xendnote{\stepcounter{endnote}%
82 % my addition begins
83 \stepcounter{allendnotes}\label{notl\theallendnotes}%
84 \immediate\write\@enotes{\checknoteheaders}%
85 % my addition ends
86 \protected@xdef\@theenmark{\theendnote}%
87 \@endnotemark\@endnotetext}}
88 \let\oldtheendnotes=\theendnotes
89 \renewcommand{\theendnotes}{%
90 \immediate\write\@enotes{\string\thispagestyle\string{endnotesstyle\string}}
91 \oldtheendnotes}
92 }

```

`\resetendnotes` Tells the `\chapter` macro to reset the note counter and to put a line with the chapter number in the endnotes.

```

93 \newif\iftitleinnotes \titleinnotestrue
94 \newcommand{\resetendnotes}{%
95 \setcounter{endnote}{0}%
96 \if@enotesopen \else \@openenotes \fi
97 \immediate\write\@enotes{\string\goodbreak}

```

```

98 \immediate\write\@enotes{\string\Needspace\string{5\string\baselineskip\string}}
99 \immediate\write\@enotes{\string\begin\string{center\string}}
100 \immediate\write\@enotes{Chapter \thechapter\string~}
101 \iftitleinnotes
102 \immediate\write\@enotes{\string\titleref\string{chapter\thechapter\string}}
103 \fi
104 \immediate\write\@enotes{\string\end\string{center\string}}
105 \immediate\write\@enotes{\string\nopagebreak}
106 }

```

\notesbychapter

```

107 % \newcommand{\notesbychapter}{%
108 % \appendtomacro{\chapter}{%
109 % \relax
110 % \resetendnotes}%
111 % }
112 \newif\ifnotesbychapteron \notesbychapteronfalse
113 \newcommand{\notesbychapter}{\notesbychapterontrue}
114 \def\@chapter[#1]#2{\ifnum \c@secnumdepth >\m@ne
115     \if@mainmatter
116         \refstepcounter{chapter}%
117         \typeout{\@chapapp\space\thechapter.}%
118         \addcontentsline{toc}{chapter}%
119             {\protect\numberline{\thechapter}#1}%
120     \else
121         \addcontentsline{toc}{chapter}{#1}%
122     \fi
123 \else
124     \addcontentsline{toc}{chapter}{#1}%
125 \fi
126 \chaptermark{#1}%
127 \addtocontents{lof}{\protect\addvspace{10\p@}}%
128 \addtocontents{lot}{\protect\addvspace{10\p@}}%
129 \if@twocolumn
130     \@topnewpage[\@makechapterhead{#2}]%
131 \else
132     \@makechapterhead{#2}%
133     \@afterheading
134 \fi
135 \iftitleinnotes%
136 \label{chapter\thechapter}%
137 \fi%
138 \ifnotesbychapteron%
139 \relax%
140 \resetendnotes%
141 \fi}

```

Change History

v1.0

General: Initial version 1

v1.1

General: uses needspace prevent
orphan chapter beginnings in

notes	1	guide	1
v1.15		v1.152	
General: uses titleref to capture		General: Fixed strange white space	
chapter titles for notes	1	error	1
v1.151			
General: Corrections to user's			

Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

Symbols	E
<code>\@afterheading</code>	133
<code>\@car</code>	14
<code>\@chapapp</code>	117
<code>\@chapter</code>	114
<code>\@endnotemark</code>	87
<code>\@endnotetext</code>	87
<code>\@enotes</code>	78, 84, 90, 97–100, 102, 104, 105
<code>\@extract@ref</code>	8, 14, 18
<code>\@extractpageref</code>	17, 40
<code>\@extractref</code>	13, 30
<code>\@firstoftwo</code>	3
<code>\@ifnextchar</code>	81
<code>\@latex@warning</code>	26, 36
<code>\@makechapterhead</code>	130, 132
<code>\@nil</code>	10, 21
<code>\@openenotes</code>	77, 96
<code>\@secondcar</code>	18, 21
<code>\@secondoftwo</code>	5
<code>\@theenmark</code>	86
<code>\@topnewpage</code>	130
<code>\@xendnote</code>	81
<code>\end</code>	104
<code>\endcsname</code>	2, 10
<code>\endgroup</code>	47
<code>\endnote</code>	81
<code>\endnoteheadersonfalse</code>	74
<code>\endnoteheadersontrue</code>	76
<code>\endnotespagestyle</code>	<u>55</u>
G	I
<code>\G@refundefinedtrue</code>	25, 35
<code>\goodbreak</code>	97
<code>\if@enotesopen</code>	77, 96
<code>\if@mainmatter</code>	115
<code>\if@twocolumn</code>	129
<code>\ifendnoteheaderson</code>	74
<code>\ifnotesbychapteron</code>	112, 138
<code>\ifnum</code>	114
<code>\ifrefundefined</code>	1, 24, 34
<code>\iftitleinnotes</code>	93, 101, 135
<code>\ifx</code>	2
L	M
<code>\long</code>	21, 43
<code>\m@ne</code>	114
<code>\mark</code>	72
<code>\mymarks</code>	<u>51</u> , 63, 64
N	O
<code>\Needspace</code>	98
<code>\nopagebreak</code>	105
<code>\notesbychapter</code>	2, <u>107</u>
<code>\notesbychapteronfalse</code>	112
<code>\notesbychapterontrue</code>	113
<code>\numberline</code>	119
<code>\oldtheendnotes</code>	88, 91
A	B
<code>\addcontentsline</code>	118, 121, 124
<code>\addtocontents</code>	127, 128
<code>\addvspace</code>	127, 128
<code>\appendtomacro</code>	43, 108
C	
<code>\c@secnumdepth</code>	114
<code>\chapter</code>	108
<code>\chaptermark</code>	126
<code>\checknoteheaders</code>	<u>69</u> , 84
<code>\csname</code>	2, 9

P		T	
\protect	25, 35, 119, 127, 128	\the	46
\protected@xdef	86	\theallendnotes	71, 83
\providecommand	1, 8, 13, 17, 23, 33	\thechapter	100, 102, 117, 119, 136
R		\theendnote	86
\refstepcounter	116	\theendnotes	88, 89
\resetendnotes	2, <u>93</u> , 110, 140	\thenotepageholder	72
S		\thispagestyle	79, 90
\setcounterfrompageref	33, 70	\titleinnotestruer	93
\setcounterfromref	23	\titleref	102
\setupendnoteheaders	1, <u>74</u>	\toks@	45, 46
\space	26, 36, 117	\typeout	117
\stepcounter	81, 83	X	
		\xdef	46