

# ENOTEZ

VO.6      2013/04/06

Endnotes for L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub>

Clemens NIEDERBERGER

<https://bitbucket.org/cgnieder/enotez/>  
[contact@mychemistry.eu](mailto:contact@mychemistry.eu)

English documentation

## Contents

	4.2.2	The list Template . . .	7
<b>1</b>	<b>Licence and Requirements</b>	<b>1</b>	<b>5</b>
<b>2</b>	<b>Motivation</b>	<b>2</b>	<b>5</b>
<b>3</b>	<b>Usage</b>	<b>2</b>	<b>6</b>
3.1	Placing the Notes . . . . .	2	<b>Language Support</b>
3.2	Printing the Notes . . . . .	3	<b>8</b>
<b>4</b>	<b>Options</b>	<b>4</b>	<b>7</b>
4.1	Package Options . . . . .	4	<b>hyperref Support</b>
4.2	Customizing the List . . . . .	5	<b>9</b>
4.2.1	The paragraph Template	5	<b>Notes</b>
			<b>9</b>
			<b>References</b>
			<b>10</b>
			<b>Index</b>
			<b>11</b>

## 1 Licence and Requirements

Permission is granted to copy, distribute and/or modify this software under the terms of the L<sup>A</sup>T<sub>E</sub>X Project Public License, version 1.3 or later (<http://www.latex-project.org/lppl.txt>). The package has the status “maintained.”

**ENOTEZ** needs and loads the following packages: `expl3`<sup>1</sup> [Tea13a], `xparse`,<sup>2</sup> `xtemplate`<sup>3</sup> and `l3keys2e`<sup>4</sup> [Tea13b], `xpatch`<sup>5</sup> [Gre12] and `scrfile`<sup>6</sup> [Koh12].

---

<sup>1</sup> CTAN: `expl3`    <sup>2</sup> CTAN: `xparse`    <sup>3</sup> CTAN: `xtemplate`    <sup>4</sup> CTAN: `l3keys2e`    <sup>5</sup> CTAN: `xpatch`    <sup>6</sup> CTAN: `scrfile`

## 2 Motivation

**ENOTEZ** is a new implementation of endnotes for L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> since the `endnotes`<sup>7</sup> package [Faio3] has some deficiencies. Nested endnotes, for example, are not supported, neither is `hyperref`<sup>8</sup> [OR12]. The `sepfootnotes`<sup>9</sup> package [Lim13] also provides means for endnotes but actually has a different purpose: to separate input and usage both of footnotes and endnotes. So it might not be the best solution in every case.<sup>10</sup> It also does not allow nested endnotes.

While **ENOTEZ** worked in tests nicely with the `memoir` [WM11] class please keep in mind that `memoir` provides its own endnote mechanism.

**ENOTEZ** enables nested endnotes properly and has another mechanism of customizing the list of endnotes which is easily extendable. One of the main features of **ENOTEZ** is a split list of endnotes in which the notes are automatically separated by the sections or chapters they were set in, see section 5 for more information.

As an aside: **ENOTEZ** is nicely compatible with the `fnpct`<sup>11</sup> package [Nie13b]. Version 0.2j or newer of `fnpct` automatically detects **ENOTEZ** and adapts the `\endnote` command.

## 3 Usage

### 3.1 Placing the Notes

The usage is simple: use `\endnote` in the text where you want to place the note mark.

`\endnote[<mark>]{<text>}`  
Add an endnote in the text.

```
1 This is some text.\endnote{With an endnote.}

This is some text.1
```

There's not really much more to it. It is possible to add a custom mark by using the optional argument but that shouldn't be needed too often. `\endnote` works fine inside tables, minipages, floats and captions.<sup>12</sup> Endnotes can also be nested.

Since this functionality seemed making a pair `\endnotemark/\endnotetext` superfluous they are *not* defined by **ENOTEZ**.

---

<sup>7</sup> CTAN: endnotes   <sup>8</sup> CTAN: hyperref   <sup>9</sup> CTAN: sepfootnotes   <sup>10</sup> You have to write the actual notes in the preamble or a separate file and reference them in the text.   <sup>11</sup> CTAN: fnpct   <sup>12</sup> This has been tested with the standard classes, `memoir`, and the KOMA-Script classes, with and without the `caption` package. If you're using another package that redefines `\caption` or are using another class it might not work. Before you place a note in a caption you should re-think the idea anyway.

Introduced in  
version 0.6

```
1 This is some text.\endnote{With another endnote.\endnote{This is a
2 nested\endnote{And another level deeper\ldots} endnote!}}
3 % uses package 'kantlipsum' to produce dummy text:
4 Of course you can have several paragraphs\endnote{\kant[1-3]} in an
   endnote.
```

This is some text.<sup>2</sup> Of course you can have several paragraphs<sup>3</sup> in an endnote.

The marks of the endnotes in the running text are printed through the command `\enotezwritemark` which defaults to `\textsuperscript`. Its argument contains the current mark which is preceded by `\enmarkstyle`. Both of these commands can be redefined of course to adapt to custom settings. This can also be done using options, see section 4. The mark of the endnote that has been set last is stored in `\theendnote` and in `\@currentlabel`.

This could be used to define a command which writes a mark:

```
1 \makeatletter
2 \def\endnotemark{\@ifnextchar[{\@endnotemark}{\@endnotemark[\theendnote]}}
3 \def\@endnotemark[#1]{\enotezwritemark{\enmarkstyle#1}}
4 \makeatother
5 Text\endnotemark

Text3
```

Please note that this definition *does not* step the endnote counter but either refers to the last number (no optional argument) or uses the one provided in the optional argument.

Endnotes can also be labelled and later be referred to:

```
1 The next endnote\endnote{This endnote gets a label.}\label{en:test}
2 has the number~\ref{en:test}. We can use this with the previous definition
3 of \string\endnotemark\endnotemark[\ref{en:test}].
```

The next endnote<sup>4</sup> has the number 4. We can use this with the previous definition of `\endnotemark4`.

## 3.2 Printing the Notes

The notes are printed by using the command `\printendnotes`.

`\printendnotes* [<style>]`

Print the list of endnotes. `<style>` is one of the instances explained in section 4.2.

If used without argument it prints all notes set so far with `\endnote`. The current list will then be cleared. All endnotes set after it are stored again for the next usage of `\printendnotes`. The starred version will print *all* endnotes but shouldn't be used more than once if you have nested endnotes.

It may take several compilation runs until all notes are printed correctly. In a first run they are written to the aux file. In the second run they are available to `\printendnotes`. If you

have nested endnotes they will be written to the aux file the first time they're printed with `\printendnotes` which means you might have to compile your file once more. If you change any of the endnotes or add another one you again will need at least two runs, maybe more. `ENOTEZ` tries to warn you in these cases by invoking the warning

Endnotes may have changed. Rerun to get them right.

but may not catch all cases.

`ENOTEZ` provides two commands that allow to set some kinds of preamble and postamble to a list, either to every list or only to the next one:

`\AtEveryEndnotesList{<text>}`

inserts <text> between heading and the actual notes every time `\printendnotes` is used.

Introduced in  
version 0.5

`\AtNextEndnotesList{<text>}`

inserts <text> between heading and the actual notes the next time `\printendnotes` is used. This overwrites a possible preamble set with `\AtEveryEndnotesList` for this instance of `\printendnotes`.

Introduced in  
version 0.5

`\AfterEveryEndnotesList{<text>}`

inserts <text> after the notes list every time `\printendnotes` is used.

Introduced in  
version 0.5

`\AfterNextEndnotesList{<text>}`

inserts <text> after the notes list the next time `\printendnotes` is used. This overwrites a possible postamble set with `\AfterEveryEndnotesList` for this instance of `\printendnotes`.

Introduced in  
version 0.5

If something is inserted with one of these commands the inserted <text> will be followed by a `\par` and a vertical skip for the preamble. The postambles follow a `\par` and a vertical skip. The skips can be set using an option, see section 4.

## 4 Options

### 4.1 Package Options

`ENOTEZ` has a few package options which should be pretty self-explanatory. They can be set either as package options with `\usepackage[<options>]{enotez}` or with the setup command.

`\setenotez{<options>}`

Setup command for setting `ENOTEZ`' options.

`list-name = <list name>`

Default: Notes

The name of the notes list. This name is used for the heading of the list.

`reset = true|false`

Default: false

If set to `true` the notes numbers will start from 1 again after `\printendnotes` has been invoked.

**counter-format** = arabic|alph|Alph|roman|Roman Default: arabic  
Change the format of the endnote counter.

**mark-format** = <code> (initially empty)  
Redefine `\enmarkstyle` to execute <code>. This command is placed directly before the endnote mark in the text.

**mark-cs** = <command> Default: `\textsuperscript`  
Lets `\enotezwritemark` to be equal to <command>. This command is used to typeset the endnote marks in the text and should take one argument.

**totoc** = section|chapter|false Default: false  
Add an entry to the table of contents.

**list-style** = <style> Default: plain  
Sets the default list style, see section 4.2 for details.

Introduced in  
version 0.5

**list-preamble-skip** = <skip> Default: `\medskipamount`  
Sets the vertical skip (a rubber length) that is inserted if a list preamble is inserted by using either `\AtNextEndnotesList` or `\AtEveryEndnotesList`. It's default is set equal to `\medskipamount`.

Introduced in  
version 0.5

**list-postamble-skip** = <skip> Default: `\medskipamount`  
Sets the vertical skip (a rubber length) that is inserted if a list postamble is inserted by using either `\AfterNextEndnotesList` or `\AfterEveryEndnotesList`. It's default is set equal to `\medskipamount`.

## 4.2 Customizing the List

The list is typeset with xtemplate's possibilities. `ENOTEZ` declares the object `enotez-list` and two templates for it, the template paragraph and the template list.

### 4.2.1 The paragraph Template

The paragraph template's interface is defined as follows:

```
1 \DeclareTemplateInterface{enotez-list}{paragraph}{1}
2 {
3   % parameter : type = default
4   heading    : function 1 = \section*{#1} ,
5   format     : tokenlist = \footnotesize ,
6   number     : function 1 = \enmark{#1} ,
7   number-format : tokenlist = \normalfont ,
8   notes-sep  : length    = .5\baselineskip ,
9 }
```

The parameters functions are these:

**heading**

The command with which the heading is typeset.

**format**

The format of the whole list.

**number**

The command that is used to typeset the numbers of the notes. The command `\enmark` is explained soon.

**numbers-format**

The format of the numbers.

**notes-sep**

Additional space between the notes.

`ENOTEZ` uses this template to define the instance plain:

```
1 \DeclareInstance{enotez-list}{plain}{paragraph}{}
```

This is the default style of the list.

You can easily define your own instances, though:

```
1 \DeclareInstance{enotez-list}{custom}{paragraph}
2 {
3   heading    = \chapter*{#1}          ,
4   notes-sep  = \baselineskip          ,
5   format     = \normalfont            ,
6   number     = \textsuperscript{#1}
7 }
```

This would use a chapter heading for the title, separate the notes with `\baselineskip` and typeset them with `\normalfont`. The numbers would be typeset with `\textsuperscript`. You could now use it like this:

```
1 \printendnotes[custom]
```

If you wanted superscripted numbers, you could also redefine `\enmark`.

**`\enmark`**

is defined like this: `\newcommand*\enmark[1]{#1.}`

### 4.2.2 The list Template

The list template's interface is defined as follows:

```
1 \DeclareTemplateInterface{enotez-list}{list}{1}  
2 {  
3   % parameter : type = default  
4   heading : function 1 = \section*{#1} ,  
5   format : tokenlist = \footnotesize ,  
6   number : function 1 = \enmark{#1} ,  
7   number-format : tokenlist = \normalfont ,  
8   list-type : tokenlist = description ,  
9 }
```

This template uses a list to typeset the notes. As you can see the default list is a description list.

**ENOTEZ** defines two instances of this template:

```
1 \DeclareInstance{enotez-list}{description}{list}{}  
2 \DeclareInstance{enotez-list}{itemize}{list}{list-type = itemize}
```

They're available through `\printendnotes[description]` and `\printendnotes[itemize]`, respectively.

Again you can define your own instances using whatever list you want, possibly one defined with the power of `enumitem`.<sup>13</sup>

## 5 Collect Notes Section-wise and Print List Stepwise

*This feature is experimental and surely has some limitations. Please let me know if something doesn't work as expected.*

Not to be misunderstood: you can use `\printendnotes` as often as you like, possibly after each section. That is *not* what is meant here. Let's suppose you are writing a book and have many endnotes in many chapters. It would be nice if the list of endnotes at the end of the book could be split into parts for each chapter. This section describes how you can achieve that with **ENOTEZ**.

First of all **ENOTEZ** will rely on the fact that you use `\printendnotes` only *once*! If you call it more times nobody knows what will happen...

You'll need to tell **ENOTEZ** that you want to split the notes into groups.

`split = section|chapter|false`  
Enable the automatic splitting.

Default: false

---

<sup>13</sup> CTAN: `enumitem`

`split-sectioning` = <csname> (initially empty)

The command that is used to display the titles between the splits. It needs to be a command that takes one argument and should be entered without the leading backslash. If the option is not used `ENOTEZ` will choose subsection\* for `split` = section and section\* for `split` = chapter.

`split-title` = <tokenlist> Default: Notes for <name> <ref>

The title that will be inserted between the splits. <name> is replaced by section for `split` = section and chapter for `split` = chapter. <ref> is replaced by the corresponding `\thesection` or `\thechapter`.

Set the `split` option:

```
1 \setenotez{split=section}
```

Well – that’s it, basically. You’ll have to be careful, though: If you’re having nested endnotes the nested ones appear first in the “Notes” section (or chapter, respectively). In this case you should have a numbered section title for the notes, presumably in the appendix. You’ll need to create a new list style:

```
1 % preamble:
2 \usepackage{enotez}
3 \DeclareInstance{enotez-list}{section}{paragraph}{heading=\section
4   {#1}}
5 \setenotez{list-style=section,split=section}
6 % document:
7 \appendix
8 \printendnotes
```

Please beware that the option `reset` also impacts here: the numbering will be reset for each section or chapter, depending on the choice you made for `split`.

`ENOTEZ` comes with an example document for a split list which you should find in the same folder as this documentation.

## 6 Language Support

`ENOTEZ` uses the translations package (part of the `exsheets`<sup>14</sup> [Nie13a] bundle) to translate language dependent strings. The advantage of this is that language settings with `babel`<sup>15</sup> [Bra08] or `polyglossia`<sup>16</sup> [RC12] are detected automatically. However, the available translations are somewhat limited due to my limited language knowledge. If you find missing or wrong translations you can try to add or correct them by adding the corresponding versions of the following lines to your preamble:

<sup>14</sup> CTAN: exsheets    <sup>15</sup> CTAN: babel    <sup>16</sup> CTAN: polyglossia



```

1 \DeclareTranslation{English}{enotez-title}{Notes}
2 % ''<name> <ref>' is a placeholder for e.g. ''section 1'':
3 \DeclareTranslation{English}{enotez-splitted-title}{Notes for <name>
   <ref>}
4 \DeclareTranslation{English}{enotez-section}{section}
5 \DeclareTranslation{English}{enotez-chapter}{chapter}

```

If you like you can also drop me an email at [contact@mychemistry.eu](mailto:contact@mychemistry.eu) and I'll add the correct translations to **ENOTEZ**.

## 7 hyperref Support

If hyperref is loaded and you are using the option **totoc** (see p 5) the list title is linked via a **\phantomsection**.

If hyperref is used with hyperfootnotes set to true the endnote marks are linked to the respective entries in the list.

### Notes

This is an example of a preamble to the list set with **\AtNextEndnotesList**.

1. With an endnote.
2. With another endnote.<sup>5</sup>
3. As any dedicated reader can clearly see, the Ideal of practical reason is a representation of, as far as I know, the things in themselves; as I have shown elsewhere, the phenomena should only be used as a canon for our understanding. The paralogisms of practical reason are what first give rise to the architectonic of practical reason. As will easily be shown in the next section, reason would thereby be made to contradict, in view of these considerations, the Ideal of practical reason, yet the manifold depends on the phenomena. Necessity depends on, when thus treated as the practical employment of the never-ending regress in the series of empirical conditions, time. Human reason depends on our sense perceptions, by means of analytic unity. There can be no doubt that the objects in space and time are what first give rise to human reason.

Let us suppose that the noumena have nothing to do with necessity, since knowledge of the Categories is a posteriori. Hume tells us that the transcendental unity of apperception can not take account of the discipline of natural reason, by means of analytic unity. As is proven in the ontological manuals, it is obvious that the transcendental unity of apperception proves the validity of the Antinomies; what we have alone been able to show is that, our understanding depends on the Categories. It remains a mystery why the Ideal stands in need of reason. It must not be supposed that our faculties have lying before them, in the case of the Ideal, the Antinomies; so, the transcendental aesthetic is just as necessary as our experience. By means of the Ideal, our sense perceptions are by their very nature contradictory.

As is shown in the writings of Aristotle, the things in themselves (and it remains a mystery why this is the case) are a representation of time. Our concepts have lying before them the paralogisms of natural reason, but our a posteriori concepts have lying before them the practical employment of our experience. Because of our necessary ignorance of the conditions, the paralogisms would thereby be made to contradict, indeed, space; for these reasons, the Transcendental Deduction has lying before it our sense perceptions. (Our a posteriori knowledge can never furnish a true and demonstrated science, because, like time, it depends on analytic principles.) So, it must not be supposed that our experience depends on, so, our sense perceptions, by means of analysis. Space constitutes the

whole content for our sense perceptions, and time occupies part of the sphere of the Ideal concerning the existence of the objects in space and time in general.

4. This endnote gets a label.
5. This is a nested<sup>6</sup> endnote!
6. And another level deeper...

This is an example of a postamble to the list set with `\AfterEveryEndnotesList`. Note that it would have started with a paragraph indent which was prevented here by using `\noindent`.

## References

- [Brao8] Johannes Braams. babel. Version 3.8m. July 8, 2008. URL: <http://mirror.ctan.org/macros/latex/required/babel/base>.
- [Faio3] Robin Fairbairns (current maintainer). endnotes. Version NA. Jan. 15, 2003. URL: <http://mirror.ctan.org/macros/latex/contrib/endnotes>.
- [Gre12] Enrico Gregorio. xpatch. Version 0.3. Oct. 2, 2012. URL: <http://mirror.ctan.org/macros/latex/contrib/xpatch>.
- [Koh12] Markus Kohm. scrfile. Version 3.12. June 15, 2012. URL: <http://mirror.ctan.org/macros/latex/contrib/koma-script>.
- [Lim13] Eduardo C. Lourenço de Lima. sepfootnotes. Version 0.2. Jan. 17, 2013. URL: <http://mirror.ctan.org/macros/latex/contrib/sepfootnotes>.
- [Nie13a] Clemens Niederberger. exsheets. Version 0.8a. Apr. 4, 2013. URL: <http://mirror.ctan.org/macros/latex/contrib/exsheets>.
- [Nie13b] Clemens Niederberger. fnpct. Version 0.2j. Feb. 28, 2013. URL: <http://mirror.ctan.org/macros/latex/contrib/fnpct>.
- [OR12] Heiko Oberdiek and Sebastian Rahtz. hyperref. Version 6.83m. Nov. 6, 2012. URL: <http://mirror.ctan.org/macros/latex/contrib/hyperref>.
- [RC12] Arthur Reutenauer and François Charette. polyglossia. Version 1.2.1. Apr. 29, 2012. URL: <http://mirror.ctan.org/macros/xelatex/latex/polyglossia>.
- [Tea13a] The L<sup>A</sup>T<sub>E</sub>X3 Team. l3kernel. Version 4469. Mar. 14, 2013. URL: <http://mirror.ctan.org/macros/latex/contrib/l3kernel>.
- [Tea13b] The L<sup>A</sup>T<sub>E</sub>X3 Team. l3packages. Version 4467. Mar. 12, 2013. URL: <http://mirror.ctan.org/macros/latex/contrib/l3packages>.
- [WM11] Peter Wilson and Lars Madsen. memoir. Version 3.6j. Mar. 6, 2011. URL: <http://mirror.ctan.org/macros/latex/contrib/memoir>.

# Index

Section titles are indicated **bold**, packages sans serif, commands \brown and options yellow.

## A

\AfterEveryEndnotesList 4 f.,  
10  
\AfterNextEndnotesList...4 f.  
\AtEveryEndnotesList...4 f.  
\AtNextEndnotesList...4 f., 9

## B

babel.....8

## C

caption.....2  
counter-format.....5

## E

\endnote.....2 f.  
\endnotemark.....2  
endnotes.....2  
\endnotetext.....2  
\enmark.....6  
\enmarkstyle.....3, 5  
\enotezwritemark.....3, 5  
enumitem.....7  
expl3.....1  
exsheets.....8

## F

fnpct.....2

## H

hyperref.....2, 9  
**hyperref Support**.....9

## K

KOMA-Script.....2

## L

l3keys2e.....1  
**Language Support**.....8 f.  
**Licence**.....1  
list-name.....4  
list-postamble-skip.....5  
list-preamble-skip.....5  
list-style.....5

## M

mark-cs.....5  
mark-format.....5  
\medskipamount.....5  
memoir.....2  
**Motivation**.....2

## N

\noindent.....10

## O

**Options**.....4–8

## P

\par.....4  
polyglossia.....8  
\printendnotes.....3 f., 7

## R

reset.....4, 8

## S

scrfile.....1  
sepfootnotes.....2  
\setenotez.....4  
split.....7 f.  
split-sectioning.....8  
split-title.....8

## T

\textsuperscript.....3, 8  
\theendnote.....3  
totoc.....5, 9  
translations.....8

## U

**Usage**.....2 ff.

## X

xparse.....1  
xpatch.....1  
xtemplate.....1, 5