

Writing derivatives

Eddie Saudrais

June 26, 2001

Abstract

This document describes the package `esdiff` that makes writing derivatives very easy. It allows to write derivatives, partial derivatives, multiple derivatives. Some typographic options are available. The macro about crossed derivatives was given on `comp.text.tex` by Peter Schmitt.

1 Derivatives

`\diff`

Derivatives are obtained with the command `diff`.

To get $\frac{df}{dx}$, just write `\diff{f}{x}`.

The order of the derivative can be set in square brackets. So `\diff[n]{f}{x}` gives $\frac{d^n f}{dx^n}$.

`\diff*`

It's easy to precise the point where the derivative is calculated:

`\diff*[f]{x}{x_0}` gives $\left(\frac{df}{dx}\right)_{x_0}$.

Of course, those two options can be used together: `\diff*[2]{g}{y}{0}` gives as expected $\left(\frac{d^2 g}{dy^2}\right)_0$.

2 Partial derivatives

`\diffp`

Partial derivatives are obtained with the macro `diffp`, using the same syntax as with `diff`: a star version to put a subscript, and square brackets to set the order of the derivative according to only one variable.

To get $\frac{\partial f}{\partial x}$, just write `\diffp{f}{x}`.

We obtain $\frac{\partial^2 f}{\partial x^2}$ writing `\diffp[2]{f}{x}`.

`\diffp*`

The notation $\left(\frac{\partial p}{\partial V}\right)_T$ is the result of `\diffp*[p]{V}{T}`.

The notation of crossed derivatives is automatic. To get $\frac{\partial^3 f}{\partial x \partial y^2}$, write `\diffp{f}{{x}{y^2}}`. This method can be used to write a partial derivative, without square brackets. So `\diffp{f}{{x^2}}` gives $\frac{\partial^2 f}{\partial x^2}$.

We can mix options: $\text{\diffp*}{f}{{x^2}{y^3}}{z}$ gives $\left(\frac{\partial^5 f}{\partial x^2 \partial y^3}\right)_z$.

3 Options

Several options are available:

- by default, derivatives are written in `displaystyle` on text mode. The `display` option set this default. With the `text` option, derivatives are written in `textstyle` on text mode;
- by default, the `d` of the derivative is written in `roman`. Available options are `roman` and `italic`;
- we can set the space between the `d` and the symbol of the function or of the variable. By default, this space is null. Available options are `thin`, `med` and `big`. It may be fine to add a space when the `d` is in `italic`;
- We can set the space between the `∂` and the symbol of the function or of the variable. By default, this space is null. Available options are `thinp`, `medp` and `bigp`;
- the space between `∂x` and `∂y` in crossed derivatives may be too narrow. It is null by default. Available options are `thinc`, `medc` and `bigc`;

4 The code

The package presents itself.

```
1 {*package}
2 \NeedsTeXFormat{LaTeX2e}
3 \ProvidesPackage{esdiff}
```

We set default values for the options.

```
4 \newcommand{\taille}[1]{\displaystyle{#1}}
5 \newcommand{\difint}{\mkern 0mu}
6 \newcommand{\derpint}{\mkern 0mu}
7 \newcommand{\croisint}{\mkern 0mu}
```

The `d` is `roman` by default..

```
8 \newcommand{\dop}{\mathrm{d}}
```

Options:

```
9 \DeclareOption{display}{\renewcommand{\taille}[1]{\displaystyle{#1}}}
10 \DeclareOption{text}{\renewcommand{\taille}[1]{\textstyle{#1}}}
11 \DeclareOption{roman}{\renewcommand{\dop}{\ensuremath{\mathrm{d}}}}
12 \DeclareOption{italic}{\renewcommand{\dop}{\mathit{d}}}
13 \DeclareOption{thin}{\renewcommand{\difint}{\mathrel{\mkern-1mu},\mkern-1mu}}
14 \DeclareOption{med}{\renewcommand{\difint}{\mathrel{\mkern-1mu};\mkern-1mu}}
15 \DeclareOption{big}{\renewcommand{\difint}{\mathrel{\mkern-1mu}:\mkern-1mu}}
16 \DeclareOption{thinp}{\renewcommand{\derpint}{\mathrel{\mkern-1mu},\mkern-1mu}}
17 \DeclareOption{medp}{\renewcommand{\derpint}{\mathrel{\mkern-1mu};\mkern-1mu}}
18 \DeclareOption{bigp}{\renewcommand{\derpint}{\mathrel{\mkern-1mu}:\mkern-1mu}}
19 \DeclareOption{thinc}{\renewcommand{\croisint}{\mathrel{\mkern-1mu},\mkern-1mu}}
20 \DeclareOption{medc}{\renewcommand{\croisint}{\mathrel{\mkern-1mu};\mkern-1mu}}
```

```

21 \DeclareOption{bigc}{\renewcommand{\croisint}{\ensuremath{\backslash :}}}
22 \ProcessOptions\relax

```

4.1 Derivative

Test of star version.

```
23 \def\diff{\@ifstar{\diffstar}{\diffnostar}}
```

Star version. The subscript is given.

```
24 \def\diffstar{\@ifnextchar[\{@diffstar}{\@@diffstar}}
```

The ordre is given in square brakets, and there is a subscript.

```

25 \def\@diffstar[#1]#2#3#4{\mathchoice{\left(\frac{\dop^{\#1}\difint{\#2}}{\dop\difint{\#3^{\#1}}}\right)_{{\mkern-7mu#4}}}{%
26 {\taille{\left(\frac{\dop^{\#1}\difint{\#2}}{\dop\difint{\#3^{\#1}}}\right)}_{{\mkern-7mu#4}}}}{%
27 {\scriptstyle{\left(\frac{\dop^{\#1}\difint{\#2}}{\dop\difint{\#3^{\#1}}}\right)}_{{\mkern-7mu#4}}}}{%
28 {\scriptstyle{\left(\frac{\dop^{\#1}\difint{\#2}}{\dop\difint{\#3^{\#1}}}\right)}_{{\mkern-7mu#4}}}}}}{%
29 {\scriptstyle{\left(\frac{\dop^{\#1}\difint{\#2}}{\dop\difint{\#3^{\#1}}}\right)}_{{\mkern-7mu#4}}}}{%
30 {\scriptstyle{\left(\frac{\dop^{\#1}\difint{\#2}}{\dop\difint{\#3^{\#1}}}\right)}_{{\mkern-7mu#4}}}}{%
31 {\scriptstyle{\left(\frac{\dop^{\#1}\difint{\#2}}{\dop\difint{\#3^{\#1}}}\right)}_{{\mkern-7mu#4}}}}{%
32 {\scriptstyle{\left(\frac{\dop^{\#1}\difint{\#2}}{\dop\difint{\#3^{\#1}}}\right)}_{{\mkern-7mu#4}}}}}}}
```

There is only a subscript.

```

33 \def\@@diffstar#1#2#3{\mathchoice{\left(\frac{\dop\difint{\#1}}{\dop\difint{\#2}}\right)_{{\mkern-7mu#3}}}{%
34 {\taille{\left(\frac{\dop\difint{\#1}}{\dop\difint{\#2}}\right)}_{{\mkern-7mu#3}}}}{%
35 {\scriptstyle{\left(\frac{\dop\difint{\#1}}{\dop\difint{\#2}}\right)}_{{\mkern-7mu#3}}}}{%
36 {\scriptstyle{\left(\frac{\dop\difint{\#1}}{\dop\difint{\#2}}\right)}_{{\mkern-7mu#3}}}}}}{%
37 {\scriptstyle{\left(\frac{\dop\difint{\#1}}{\dop\difint{\#2}}\right)}_{{\mkern-7mu#3}}}}{%
38 {\scriptstyle{\left(\frac{\dop\difint{\#1}}{\dop\difint{\#2}}\right)}_{{\mkern-7mu#3}}}}}}{%
39 {\scriptstyle{\left(\frac{\dop\difint{\#1}}{\dop\difint{\#2}}\right)}_{{\mkern-7mu#3}}}}{%
40 {\scriptstyle{\left(\frac{\dop\difint{\#1}}{\dop\difint{\#2}}\right)}_{{\mkern-7mu#3}}}}}}
```

No star version (no subscript).

```
41 \def\diffnostar{\@ifnextchar[\{@diffnostar}{\@@diffnostar}}
```

The ordre is given in square brackets.

```

42 \def\@diffnostar[#1]#2#3{\mathchoice{\frac{\dop^{\#1}\difint{\#2}}{\dop\difint{\#3^{\#1}}}}{%
43 {\taille{\frac{\dop^{\#1}\difint{\#2}}{\dop\difint{\#3^{\#1}}}}}}{%
44 {\scriptstyle{\frac{\dop^{\#1}\difint{\#2}}{\dop\difint{\#3^{\#1}}}}}}{%
45 {\scriptstyle{\frac{\dop^{\#1}\difint{\#2}}{\dop\difint{\#3^{\#1}}}}}}}}{%
46 {\scriptstyle{\frac{\dop^{\#1}\difint{\#2}}{\dop\difint{\#3^{\#1}}}}}}}}
```

Basic notation.

```

47 \def\@@diffnostar#1#2{\mathchoice{%
48 {\frac{\dop\difint{\#1}}{\dop\difint{\#2}}}}{%
49 {\taille{\frac{\dop\difint{\#1}}{\dop\difint{\#2}}}}}}{%
50 {\scriptstyle{\frac{\dop\difint{\#1}}{\dop\difint{\#2}}}}}}{%
51 {\scriptstyle{\frac{\dop\difint{\#1}}{\dop\difint{\#2}}}}}}
```

4.2 Partial derivatives

Test of the star version.

```
52 \def\diffp{\@ifstar{\diffpstar}{\diffpnostar}}
```

Star version: a subscript is given.

```
53 \def\diffpstar{\@ifnextchar[\{@diffpstar}{\@@diffpstar}}
```

Ordre of derivative is given, and there is a subscript.

```
54 \def\@diffpstar[#1]#2#3#4{\mathchoice{\left(\frac{\partial^{\#1}}{\partial x^{\#2}}\right.\left.\frac{\partial^{\#3}}{\partial x^{\#4}}\right)_{{\mkern-7mu#4}}}{\left(\frac{\partial^{\#1}}{\partial x^{\#2}}\right.\left.\frac{\partial^{\#3}}{\partial x^{\#4}}\right)_{{\mkern-7mu#4}}}{\left(\frac{\partial^{\#1}}{\partial x^{\#2}}\right.\left.\frac{\partial^{\#3}}{\partial x^{\#4}}\right)_{{\mkern-7mu#4}}}{\left(\frac{\partial^{\#1}}{\partial x^{\#2}}\right.\left.\frac{\partial^{\#3}}{\partial x^{\#4}}\right)_{{\mkern-7mu#4}}}}
```

There is only a subscript.

```
64 \def\@@diffpstar#1#2#3{\mathchoice{\left(\{\begin{array}{l}\begin{array}{l}\toks0=\{}\count0=0\\\degree #2\\\degree\\\frac{\partial}{\partial x}\ifnum\count0>1^{\the\count0}\fi\partial^{#1}\\\{\the\toks0}\end{array}\end{array}\right.\left.\frac{\partial^{\#3}}{\partial x^{\#4}}\right)_{{\mkern-7mu#3}}}{\left(\{\begin{array}{l}\begin{array}{l}\toks0=\{}\count0=0\\\degree #2\\\degree\\\frac{\partial}{\partial x}\ifnum\count0>1^{\the\count0}\fi\partial^{#1}\\\{\the\toks0}\end{array}\end{array}\right.\left.\frac{\partial^{\#3}}{\partial x^{\#4}}\right)_{{\mkern-7mu#3}}}{\left(\{\begin{array}{l}\begin{array}{l}\toks0=\{}\count0=0\\\degree #2\\\degree\\\frac{\partial}{\partial x}\ifnum\count0>1^{\the\count0}\fi\partial^{#1}\\\{\the\toks0}\end{array}\end{array}\right.\left.\frac{\partial^{\#3}}{\partial x^{\#4}}\right)_{{\mkern-7mu#3}}}{\left(\{\begin{array}{l}\begin{array}{l}\toks0=\{}\count0=0\\\degree #2\\\degree\\\frac{\partial}{\partial x}\ifnum\count0>1^{\the\count0}\fi\partial^{#1}\\\{\the\toks0}\end{array}\end{array}\right.\left.\frac{\partial^{\#3}}{\partial x^{\#4}}\right)_{{\mkern-7mu#3}}}}
```

No star version (no subscript is given).

```
88 \def\diffpnostar{\@ifnextchar[\{@diffpnostar}{\@@diffpnostar}}
```

The ordre of derivative is given.

```
89 \def\@diffpnostar[#1]#2#3{\mathchoice{\frac{\partial^{\#1}}{\partial x^{\#2}}\frac{\partial^{\#3}}{\partial x^{\#4}}}{\frac{\partial^{\#1}}{\partial x^{\#2}}\frac{\partial^{\#3}}{\partial x^{\#4}}}{\frac{\partial^{\#1}}{\partial x^{\#2}}\frac{\partial^{\#3}}{\partial x^{\#4}}}{\frac{\partial^{\#1}}{\partial x^{\#2}}\frac{\partial^{\#3}}{\partial x^{\#4}}}}
```

Basic notation.

```
94 \def\@@diffpnostar#1#2{\mathchoice{\begin{array}{l}\toks0=\{}\count0=0\\\degree #2\\\degree\\\frac{\partial}{\partial x}\ifnum\count0>1^{\the\count0}\fi\partial^{#1}\\\{\the\toks0}\end{array}}{\begin{array}{l}\toks0=\{}\count0=0\\\degree #2\\\degree\\\frac{\partial}{\partial x}\ifnum\count0>1^{\the\count0}\fi\partial^{#1}\\\{\the\toks0}\end{array}}{\begin{array}{l}\toks0=\{}\count0=0\\\degree #2\\\degree\\\frac{\partial}{\partial x}\ifnum\count0>1^{\the\count0}\fi\partial^{#1}\\\{\the\toks0}\end{array}}{\begin{array}{l}\toks0=\{}\count0=0\\\degree #2\\\degree\\\frac{\partial}{\partial x}\ifnum\count0>1^{\the\count0}\fi\partial^{#1}\\\{\the\toks0}\end{array}}}
```

```

100      {\taille{\begingroup
101      \toks0={} \count0=0
102      \degree #2\degree
103      \frac{\partial\ifnum\count0>1^{\the\count0 }\fi\derpint#1}%
104      {\the\toks0}%
105      \endgroup} }%
106      {\scriptstyle{\begingroup
107      \toks0={} \count0=0
108      \degree #2\degree
109      \frac{\partial\ifnum\count0>1^{\the\count0 }\fi\derpint#1}%
110      {\the\toks0}%
111      \endgroup} }%
112      {\scriptstyle{\begingroup
113      \toks0={} \count0=0
114      \degree #2\degree
115      \frac{\partial\ifnum\count0>1^{\the\count0 }\fi\derpint#1}%
116      {\the\toks0}%
117      \endgroup}}}

```

Macros used for crossed derivatives.

```

118 \def\degree #1{\ifx #1\degree \expandafter\stopd
119                           \else \expandafter\addd \fi #1^1##1\addd}
120 \def\stopd #1\addd{ }
121 \def\addd #1^#2#3##4\addd{\advance\count0 #2
122                               \toks0=\expandafter{\the\toks0%
123                               {\partial\derpint #4}%
124                               \croisint}\degree}
125 
```