

etextools examples

Examples for some macros provided by the etextools package

Florent Chervet

July 22, 2009

Contents

1 \expandnext examples

1.1 Test if the replacement text of macro is really empty

```
\def\xx{ }

→ \edef \expandnextTest {\string \xx \ is \expandnext \ifempty {\xx }{}{not} empty}
\expandnextTest= macro:->\xx\ is not empty
```

```
\def\xx{}

→ \edef \expandnextTest {\string \xx \ is \expandnext \ifempty {\xx }{}{not} empty}
\expandnextTest= macro:->\xx\ is empty
```

1.2 Test if the replacement text of a macro is blank (empty or spaces)

```
\def\xx{something}
```

→ `\edef \expandnextTest {\string \xx \ is \expandnext \ifblank {\xx }{}{not} blank}`
 `\expandnextTest= macro:->\xx\ is not blank`

```
\def\xx{ }
```

→ `\edef \expandnextTest {\string \xx \ is \expandnext \ifblank {\xx }{}{not} blank}`
 `\expandnextTest= macro:->\xx\ is blank`

1.3 Detokenize the replacement text of a named-sequence

```
\def\detokenizecs#1{\expandnext \expandnext \detokenize {\csname #1\endcsname }}
```

→ `\edef \expandnextTest {\detokenizecs {document}}`
 `\expandnextTest= macro:->@latex@error {Can be used only in preamble}@eha`

2 Testing characters

2.1 `\ifsinglechar` versus `\iffirstchar`

→ `\edef \ifsinglecharTest {\ifsinglechar {*}{"hello"}{ single star }{ something else }}`
 `\ifsinglecharTest= macro:-> something else`

→ `\edef \ifsinglecharTest {\ifsinglechar {*}{*}{ single star }{ something else }}`
 `\ifsinglecharTest= macro:-> something else`

→ `\edef \ifsinglecharTest {\ifsinglechar {*}{*}{ single star }{ something else }}`
 `\ifsinglecharTest= macro:-> something else`

Note the space **after** the star ↑.

→ `\edef \iffirstcharTest {\iffirstchar {*}{"hello"}{ first char is star }{ something else }}`
 `\iffirstcharTest= macro:-> first char is star`

2.2 Fully Expandable starred macros

```
\def\starmacro#1{\FE@ifstar {\#1}\starred \notstarred }
```

```
\def\starred#1{your "#1" will be processed by the STAR form}
```

```
\def\notstarred#1{your "#1" will be processed by the NORMAL form}
```

→ `\edef \FE@ifstarTest {\starmacro {sample text}}`
 `\FE@ifstarTest= macro:->your "sample text" will be processed by the NORMAL form`

→ `\edef \FE@ifstarTest {\starmacro *{sample text}}`
 `\FE@ifstarTest= macro:->your "sample text" will be processed by the STAR form`

2.3 Fully Expandable macros with options

```
\def\optmacro#1{\FE@testopt {#1}\OPTmacro {Mr.}}  
\def\OPTmacro[#1]#2{#1 #2}
```

→ `\edef \FE@testoptTest {\optmacro {Woody Allen}}`
 `\FE@testoptTest= macro:->Mr. Woody Allen`

→ `\edef \FE@testoptTest {\optmacro [Ms.]{Vanessa Paradis}}`
 `\FE@testoptTest= macro:->Ms. Vanessa Paradis`

3 Lists management

3.1 `\csvloop` and `\csvloop*` examples

3.1.1 `\makequotes`

```
\def\makequotes#1{"#1"\space }  
→ \edef \csvloopTest {\csvloop *[{\makequotes} ]{hello,world}}  
  \csvloopTest= macro:->"hello" "world"
```

3.1.2 `\detokenize`

→ `\edef \csvloopTest {\csvloop *[{\detokenize}]{\un ,\deux }}`
 `\csvloopTest= macro:->\un \deux`

3.1.3 `\numexpr`

```
\def\mylist{1,2,3,4,5}  
\def\BySeven#1{$#1\times 7 = \number \numexpr #1*7\relax \$\par }  
→ \edef \csvloopTest {\csvloop [\BySeven ]\mylist }  
  \csvloopTest= macro:->$1\times 7 = 7$\par $2\times 7 = 14$\par $3\times 7 = 21$\par  
             $4\times 7 = 28$\par $5\times 7 = 35$\par
```

3.1.4 `protected \textbf`

→ `\protected@edef \csvloopTest {\csvloop *[{\textbf}]{hello ,my ,friends}}`
 `\csvloopTest= macro:->\protect \textbf {hello }\protect \textbf {my }\protect \textbf {friends}`

3.2 Index in lists and items by index

3.2.1 `\getlistitem`

```
\csvtolist*\mylist{one,two,three,four,five,alpha,beta,gamma}
```

→ `\edef \getlistitemTest {\getlistitem {4}\mylist }`
`\getlistitemTest= macro:->four`

3.2.2 `\getlistindex`

Require the `\pdfstrcmp` primitive (`pdfTeX`):

```
\csvtolist*\mylist{one,two,three,four,five,alpha,beta,gamma}
```

→ `\edef \getlistindexTest {\getlistindex {alpha}\mylist }`
`\getlistindexTest= macro:->6`

Require the `\pdfstrcmp` primitive (`pdfTeX`):

→ `\edef \getlistindexTest {\getcsvlistindex *{alpha}{one,two,three,four,five,alpha,beta}}`
`\getlistindexTest= macro:->6`

→ `\getlistindex[\myindex]{alpha}\mylist`
`\myindex= macro:->6`

`\newcount\myindex`
→ `\getcsvlistindex*[\myindex]{alpha}{one,two,three,four,five,alpha,beta}`
`\the\myindex= 6`

3.2.3 `\xgetlistindex`

Require the `\pdfstrcmp` primitive (`pdfTeX`):

```
\csvtolist*\mylist{one,two,three,four,five,alpha,beta,gamma}
```

```
\def\x{beta}
```

→ `\edef \xgetlistindexTest {\xgetlistindex {\x }\mylist }`
`\xgetlistindexTest= macro:->7`

3.2.4 `\getlistindex` with `\ifcase`

Always purely expandable (no need of `\pdfstrcmp`, comparison done by `\ifx`):

→ `\ifcase \gettokslistindex*{D}{LRDF}\relax 0`
 Problem
 `\or What do to if L`
 `\or What do to if R`
 `\or What do to if D`
 `\or What do to if F`
 `\or What do to if \relax`
 `\or What do to if 0`
 `\fi`
 Result= `What do to if D`
