

exercise.sty : a package to typeset exercises

Paul Pichaureau
paul.pichaureau@alcandre.net

November 27, 2010

Abstract

This package offers a simple environment to typeset exercises, and their questions, sub-questions, indications, answers and so on.

The layout of the exercises is fully customisable. Moreover, the answers of the exercise could be typeset immediately or later in the document.

Contents

1	Options of the package	2
2	Commands	2
2.1	Exercises and answers	2
2.2	Parts and questions	4
2.3	Exercise selection	5
2.4	Extra stuff	5
3	Customisation	6
3.1	Internationalisation	6
3.2	Layout	6
3.2.1	Exercises, answers and parts	6
3.2.2	Questions, sub-questions and sub-sub-questions	8
3.3	Lengths	8
3.4	The <code>\renewcounter</code> command	9
4	Known problems	9
5	Implementation	10
5.1	Package options	10
5.2	Customisation	11
5.2.1	Internationalisation	11
5.2.2	Layout	12
5.3	Macros definition	14
5.3.1	Definition of <code>Exercise</code>	15
5.3.2	Definition of <code>questions</code>	18

5.3.3	Definition of <code>sub-questions</code> and <code>sub-sub-questions</code> . . .	19
5.3.4	Presentation of part (within an exercise)	22
5.3.5	Presentation of answers	23
5.3.6	Exercises selection	25
5.3.7	Some extra stuff	27
5.3.8	Secret stuff	27
5.4	The <code>\renewcounter</code> command	28

1 Options of the package

Here we list the options of the package `exercise.sty`:

`noexercise` hide all the exercises of a document.

`noanswer` hide all the answers of a document. The default behaviour is to show both the exercises and the answers.

`exercisely` is a synonym of `noanswer`.

`answeronly` is a synonym of `noexercise`.

`nothing` hide answers and exercises (synonym of `noanswer` and `noexercise`).

`answerdelayed` save the answers instead of typeset them. The answers can be included later in the document with the command `\shipoutAnswer`. More precisely, the answers are stored in a vertical box. When `\shipoutAnswer` is encountered, this box is emptied and its contents is placed in the main vertical list. The answers defined later are placed in this emptied vertical box. In this way, you can have many group of answers in the same document.

`exercisedelayed` saves the exercises instead of typeset them. The exercises can be included later with the command `\shipoutExercise`.

`lastexercise` if no references is given for an answer, then the answer is supposed to refer to the last exercise (see section 2.1).

2 Commands

2.1 Exercises and answers

```
\begin{Exercise} [<key val list>] ... \end{Exercise}
\begin{Exercise*} [<key val list>] ... \end{Exercise*}
```

Exercise The `Exercise` environment is used to typeset just one exercise. We use the `keyval` package to give different informations about an exercise.

The `Exercise*` environment typeset an exercise without number, and without putting it in the `listofexercises`.

```

label={\langle string \rangle}
title={\langle string \rangle}
difficulty={\langle number \rangle}
origin={\langle string \rangle}
name={\langle string \rangle}
counter={\langle counter \rangle}
number={\langle string \rangle}

```

All these keys define commands that will be available later to typeset the exercise. They are all optional.

label The label of the exercise. This label can be used later in cross-reference, or to link an answer to this exercise.

title The title of the exercise. It will be available later with the command `\ExerciseTitle`.

difficulty The difficulty of the exercise (a number). It will be available later with the counter `\ExerciseDifficulty`.

origin The origin of the exercise. It will be available later with the command `\ExerciseOrigin`.

name In document, exercises can have multiple denomination, like problem, exam, or even question. This key allows to change the denomination.

counter Use the given counter to number this exercise. Here, `{\langle counter \rangle}` must be a pre-defined counter.

number Use the given number for the exercise. In fact, this number is a string, so you can number the exercise with letters.

As an example, with the default definitions, the following code:

```

\begin{Exercise}[title={Euler's constant}, difficulty=2, label=ex1,
                 origin={P.Paelw}]
\end{Exercise}

```

will give

**** Exercise 1 Euler's constant (*P.Paelw*)**

Problem It is possible to define different type of exercise. For example, you can define a **Problem** environment with the two lines:

```

\newcounter{Problem}
\newenvironment{Problem}{\begin{Exercise}[name={Problem},
                                         counter={Problem}]}
                        {\end{Exercise}}

```

Anyway, all type of exercise will have the same layout in the document.

`\begin{Answer} [key val list] ... \end{Answer}`

Answer The **Answer** environment is used to typeset the answer of an exercise. To determine which the exercise this answer is attributed to, you can use the two following keys.

`ref={\string}`
`number={\string}`

This is the description of these keys:

ref a L^AT_EX reference. *Must* correspond to the **label** key of an exercise.

number if the answer refers to an exercise in another document, you can set the number of the exercise with this key. It is in fact a string.

If the package is loaded with the option **lastexercise** and if no **ref** and no **number** key is given, then the last exercise is taken as a reference for the answer.

If no **ref** and no **number** key is given and the option **lastexercise** is not activated, a Package Warning is displayed.

`\begin{ExerciseList}`
`\Exercise[key val list]`
`\Answer[key val list]`
`\end{ExerciseList}`

ExerciseList The **ExerciseList** environment is a convenience to typeset a list of small exercises. In **ExerciseList**, everything between two **\Exercise** or **\Answer** tags is interpreted as the body of an exercise (or an answer).

\Exercise The command **\Exercise** inside **ExerciseList** accepts the same keys than **\Exercise*** the **Exercise** environment. The command **\Answer** inside **ExerciseList** accepts the same keys than the **Answer** environment and behaves in the same way.

2.2 Parts and questions

`\ExePart[key val list]`
`\ExePart*[key val list]`

\ExePart It is common to split large exercise in parts: it is the purpose of the **\ExePart**
\ExePart* command. The keys **title**, **name** and **difficulty** are available for this command. For example, a non-numbered preliminary part is obtained with

`\ExePart*[name={Preliminary}]`

<code>\Question[⟨key val list⟩]</code> <code>\subQuestion[⟨key val list⟩]</code> <code>\subsubQuestion[⟨key val list⟩]</code>

`\Question` These three commands define the hierarchy of questions. A `\subsubQuestion`
`\subQuestion` cannot be preceded by a `\Question` or a `\begin{Exercise}`. A `\subQuestion`
`\subsubQuestion` cannot be preceded by a `\begin{Exercise}`. If one of these cases is detected, a
Package Error is displayed.

Two keys are available for these commands: `title` and `difficulty`.

<code>\ExeText</code>

`\ExeText` The text following this command has the same status that the first indications
of the exercise. So, the next level of the hierarchy must be a `\ExePart` or a
`\Question`.

2.3 Exercise selection

<code>\ExerciseSelect[⟨key val list⟩]</code> <code>\ExerciseSelect*[⟨key val list⟩]</code> <code>\ExerciseStopSelect</code>

`\ExerciseSelect`
`\ExerciseStopSelect`

A very basic exercise selection mechanism is provided. When `\ExerciseSelect`
is used, an exercise is printed if and only if the value of its keys are within the
values specified after `\ExerciseSelect`. For example, the following command

`\ExerciseSelect[type={short}, difficulty={0,1}]`

selects the short exercises of difficulties 0 and 1, whereas

`\ExerciseSelect[label={exe1, exe10, exe11}]`

selects the exercises with label `exe1`, `exe10` and `exe11`.

With `\ExerciseStartSelect*`, the exercises which fit the conditions are
omited instead of selected.

Last, `\ExerciseStopSelect` stops the processus of selection: every exercise
will be displayed later.

The purpose of these commands is to select exercises within a long list stored
on an auxiliary file.

2.4 Extra stuff

`\marker` The difficulty of an exercise is represented by a certain amount of stars. The
`\DifficultyMarker` command `\marker` is used to typeset the difficulty of an exercise.

`\marker<symbol><counter>`

displays `<symbol>` repeated `<counter>` times. For example `\marker*2` gives **, and `\marker+{14}` gives ++++++

By default, the difficulty is symbolized by star. You can customise this by redefining the command `\DifficultyMarker`.

`\listofexercises` This command add a list of all the exercise in your document.

`\ListOfExerciseInToc`
`\ExerciseLevelInToc{<level of exercises>}`

`\ListOfExerciseInToc` If you prefer to display this list of exercises in the table of contents, then use
`\ExerciseLevelInToc` the command `\ListOfExerciseInToc`.

By default, the exercises appear in the table of content at the same level as the paragraphs. The command `\ExerciseLevelInToc` is used to customize this behaviour. For example with the command `\ExerciseLevelInToc{subsection}` the exercises will appear at the same level as the subsections. Available levels are: section, subsection, subsubsection, paragraph and subparagraph.

3 Customisation

3.1 Internationalisation

`\ExerciseName`
`\ExerciseListName`
`\AnswerName`
`\AnswerListName`
`\ExePartName`

`\ExerciseName` These commands store various hard-wired string. `\ExerciseListName` is used
`\ExerciseListName` in the `ExerciseList` environment: it is possibly an abbreviation of the word
`\AnswerName` “Exercise”.

`\AnswerListName` `Exercise.sty` automatically detects the usage of `babel` and translate these terms
`\ExePartName` in the language loaded... if I (the author) know the translation! As my skills in
`\ExePartListName` foreign language are quite weak, only English and French are currently supported.

If you sent me the translations in your language, I will be happy to add them in the package. Anyway, you can redefine these commands (with a `\renewcommand`).

You must load the exercise package *after* `babel` to activate this option.

3.2 Layout

3.2.1 Exercises, answers and parts

For the layout of the exercises, two levels of customisation are available. First, you can customise the way the informations will be typeset, and then you can customise the way these pieces of informations are typeset together.

<code>\ExerciseHeaderTitle</code> <code>\ExerciseHeaderDifficulty</code> <code>\ExerciseHeaderOrigin</code> <code>\ExerciseHeaderNB</code>

<code>\ExerciseHeaderTitle</code>	These commands are used to typeset the corresponding information:
<code>\ExerciseHeaderDifficulty</code>	<code>\ExerciseHeaderTitle</code> corresponds to the <code>title</code> key,
<code>\ExerciseHeaderOrigin</code>	<code>\ExerciseHeaderDifficulty</code> to the <code>difficulty</code> key, <code>\ExerciseHeaderOrigin</code>
<code>\ExerciseHeaderNB</code>	to the <code>origin</code> key and <code>\ExerciseHeaderNB</code> to the number of the exercise.

In these commands, you specify the fonts to use, the space around the information, some symbols (like dash or dot) you want to put here, and so on. If the key is not present in the definition of the exercise, then the corresponding part of the header will be emptied by the package.

For example the default definition of `\ExerciseHeaderTitle` is

```
\newcommand{\ExerciseHeaderTitle}{\quad---\quad\ExerciseTitle}
```

If an exercise has a title, then this title will be displayed preceded by an emdash (as you can see in exercise 1 of this document). If an exercise doesn't have a title, then this command is set to nothing (precisely to `{}`) during the exercise.

These commands can be redefined with a `\renewcommand`. You don't have to worry about the "undefinition" mechanism: the package manages that by itself.

<code>\ExerciseHeader</code> <code>\ExerciseListHeader</code>
--

<code>\ExerciseHeader</code>	When the layout of all the elements has been fixed, they are collected in the
<code>\ExerciseListHeader</code>	<code>\ExerciseHeader</code> command (or in <code>\ExerciseListHeader</code>). Here, you specify the way the different elements are mixed together.

The default definition of `\ExerciseHeader` is

```
\newcommand{\ExerciseHeader}{\centerline{\textbf{\large
\ExerciseName\ExerciseHeaderNB\ExerciseHeaderTitle
\ExerciseHeaderOrigin\medskip}}}
```

which displays all the informations in a centered line, using a large bold default font.

<code>\AnswerHeader</code> <code>\AnswerListHeader</code>
--

<code>\AnswerHeader</code>	The same mechanism is implemented for the answers. <code>\AnswerHeader</code> and
<code>\AnswerListHeader</code>	<code>\AnswerListHeader</code> specifies the way the header of answers are typeset. In the definition of these commands, you can use freely the informations of the related exercise. For example, this is the default definition of <code>\AnswerHeader</code> :

```
\newcommand{\AnswerHeader}{\medskip\centerline{\textbf{
Answer of \ExerciseName\ \ExerciseHeaderNB}\smallskip}}
```

<code>\ExePartHeaderTitle</code>
<code>\ExePartHeaderDifficulty</code>
<code>\ExePartHeaderNB</code>
<code>\ExePartHeader</code>
<code>\ExePartListHeader</code>

<code>\ExePartHeaderTitle</code>	The same kind of customisation is available for the <code>\ExePart</code> command:
<code>\ExePartHeaderDifficulty</code>	<code>\ExePartHeaderTitle</code> , <code>\ExePartHeaderDifficulty</code> and <code>\ExePartHeaderNB</code>
<code>\ExePartHeaderNB</code>	control the way the title (<code>\ExePartTitle</code>), the difficulty (<code>\ExePartdifficulty</code>)
<code>\ExePartHeader</code>	and the number (<code>\theExePart</code>) of the part are displayed.
<code>\ExePartListHeader</code>	These pieces are collected in the command <code>\ExePartHeader</code> or <code>\ExePartListHeader</code> .

3.2.2 Questions, sub-questions and sub-sub-questions

The layout of the questions is a little more rigid. Somehow, it can be customised.

<code>\QuestionHeaderTitle</code>
<code>\QuestionHeaderDifficulty</code>
<code>\QuestionHeaderNB</code>

<code>\QuestionHeaderTitle</code>	These commands plays the same role that the corresponding command relating
<code>\QuestionHeaderDifficulty</code>	to exercises. But here, no <code>\QuestionHeader</code> is defined.
<code>\QuestionHeaderNB</code>	The <code>subQuestion</code> and <code>subsubQuestion</code> versions of these commands are also
<code>\subQuestionHeaderTitle</code>	defined.
<code>\subQuestionHeaderDifficulty</code>	All of these commands can be changed using <code>\renewcommand</code> .
<code>\subQuestionHeaderNB</code>	
<code>\subsubQuestionHeaderTitle</code>	
<code>\subsubQuestionHeaderDifficulty</code>	
<code>\subsubQuestionHeaderNB</code>	

3.3 Lengths

<code>\ExerciseSkipBefore</code>
<code>\ExerciseSkipAfter</code>

<code>ExerciseSkipBefore</code>	Before every <code>Exercise</code> environment the vertical skip <code>ExerciseSkipBefore</code> is
<code>ExerciseSkipAfter</code>	added. The corresponding <code>ExerciseSkipAfter</code> vertical skip is added after every
	<code>Exercise</code> environment.

<code>\Exesep</code>	<code>\Exetopsep</code>	<code>\Exeparsep</code>	<code>\Exepartopsep</code>
<code>\Exeleftmargin</code>	<code>\Exerightmargin</code>	<code>\Exelabelwidth</code>	<code>\Exelabelsep</code>

<code>Exesep</code>	These lengths have an effect only inside an <code>ExerciseList</code> environment. This
<code>Exetopsep</code>	environment is nothing more than a <code>list</code> environment. All the parameters of
<code>Exeparsep</code>	L ^A T _E X's lists are available. Please consult your favourite source of information to
<code>Exepartopsep</code>	have the exact definitions of these lengths.
<code>Exeleftmargin</code>	
<code>Exerightmargin</code>	
<code>Exelabelsep</code>	

<code>\QuestionBefore</code>	<code>\QuestionIndent</code>
<code>\subQuestionBefore</code>	<code>\subQuestionIndent</code>
<code>\subsubQuestionBefore</code>	<code>\subsubQuestionIndent</code>

`QuestionBefore` Here, `\QuestionBefore` is the vertical space above `\Question`, and
`QuestionIndent` `\QuestionIndent` it the horizontal distance added to the margin in question.
`subQuestionBefore` Same thing for `\subQuestion` and `\subsubQuestion`.
`subQuestionIndent`
`subsubQuestionBefore`
`subsubQuestionIndent`

3.4 The `\renewcounter` command

In a document, you will probably want to customise the way the `Exercise` counter will reseted. Strangely, it is impossible to redefined counter with \LaTeX . There is no equivalent of the `\renewcommand` command for the counters.

`\renewcounter` We provide such an equivalent with the command `\renewcounter`.

<code>\renewcounter{foo}[\counter]</code>

The `\renewcounter` command defines a new counter named `foo`. The counter is initialized to zero.

The optional argument `[\counter]` causes the counter `foo` to be reset whenever the counter named in the optional argument is incremented.

If the counter `foo` was not previously defined, a \LaTeX error occurs.

4 Known problems

The commands `\Question`, `\subQuestion`, etc. are heavily based on `list` environment. These lists are hidden (I know it's bad!) to simplify the syntax of the source file (I think it's nice!).

In fact, every `\Question` is like the beginning of an environment, which is closed at the next `\Question` (the exact mechanism is a little bit more complicated).

Consequently it's dangerous to put questions inside environment. The following code will lead to an error:

```

\begin{Exercise}
  \begin{multicols}{2}
    \Question ...
    \Question ...
  \end{multicols}
\end{Exercise}

```

Of course, you can put entire exercise inside other environment (like `minipage`). The following code will work:

```

\begin{multicols}{2}
  \begin{Exercise}
    \Question ...
    \Question ...
  \end{Exercise}
\end{multicols}

```

```

\EndCurrentQuestion
\EndCurrentsubQuestion
\EndCurrentsubsubQuestion

```

`\EndCurrentQuestion` If you really need to put some questions inside environment, you must use
`\EndCurrentsubQuestion` the command `\EndCurrentQuestion` just before ending the environment. This
`\EndCurrentsubsubQuestion` command ends the question's "environment". So, this code will work:

```

\begin{Exercise}
  \begin{multicols}{2}
    \Question ...
    \Question ...
  \EndCurrentQuestion
  \end{multicols}
\end{Exercise}

```

In `ExerciseList` environment, the command `\Exercise` shouldn't be followed by an empty line.

5 Implementation

5.1 Package options

This part deals with the package options. Nothing more than an affair of boolean.

```

\newif\if@AnswerOutput      \@AnswerOutputtrue
\newif\if@AnswerDelay       \@AnswerDelayfalse
\newif\if@ExerciseOutput    \@ExerciseOutputtrue
\newif\if@ExerciseDelay     \@ExerciseDelayfalse
\newif\if@AswLastExe        \@AswLastExefalse

\DeclareOption{noanswer}    {\@AnswerOutputfalse}
\DeclareOption{answeronly}  {\@AnswerOutputtrue\@ExerciseOutputfalse}
\DeclareOption{noexercise}  {\@ExerciseOutputfalse}
\DeclareOption{exerciseonly}{\@AnswerOutputfalse}
\DeclareOption{outputnothing}{\@ExerciseOutputfalse\@AnswerOutputfalse}
\DeclareOption{exercisedelayed}{\@ExerciseDelaytrue}
\DeclareOption{answerdelayed}{\@AnswerDelaytrue}
\DeclareOption{lastexercise}{\@AswLastExetrue}

```

The following option, which displays the exercise label in margin, is not implemented yet.

```

\newif\if@ShowLabel         \@ShowLabelfalse
\DeclareOption{showlabel}    {\@ShowLabeltrue}

```

```

\ProcessOptions

```

The only required package are `keyval` and `ifthen`.

```

\RequirePackage{keyval, ifthen}

```

5.2 Customisation

5.2.1 Internationalisation

```
\def\listexercisename{List of exercises}%
\def\ExerciseName{Exercise}%
\def\AnswerName{Answer of exercise}%
\def\ExerciseListName{Ex.}%
\def\AnswerListName{Answer}%
\def\ExePartName{Part}%
\def\ArticleOf{of\ }%
\@ifpackageloaded{babel}{
\addto\captionsfrenchb{
\def\listexercisename{Liste des exercices}%
\def\ExerciseName{Exercice}%
\def\AnswerName{Solution de l'exercice}%
\def\ExerciseListName{Ex.}%
\def\AnswerListName{Solution}%
\def\ExePartName{Partie}%
}
\addto\captionsspanish{
\def\listexercisename{\`{I}ndice de \es@uclc Eejercicios}%
\def\ExerciseName{Ejercicio}%
\def\AnswerName{Soluci\'on del ejercicio}%
\def\ExerciseListName{Ej.}%
\def\AnswerListName{Soluci\'on}%
\def\ExePartName{Parte}%
\def\ArticleOf{del\ }%
}
\addto\captionsitalian{
\def\listexercisename{Indice degli esercizi}
\def\ExerciseName{Esercizio}%
\def\AnswerName{Soluzione dell'esercizio}%
\def\ExerciseListName{Es.}%
\def\AnswerListName{Soluzione}%
\def\ExePartName{Parte}%
}
\addto\captionsdutch{
\def\listexercisename{Lijst van opdrachten}
\def\ExerciseName{Opdracht}
\def\AnswerName{Oplossing van opdracht}
\def\ExerciseListName{Opg.}
\def\AnswerListName{Oplossing}
\def\ExePartName{Deel}
\def\ArticleOf{van\ }
}
\addto\captionsgerman{
\def\listexercisename{Liste der {\\"U}bungen}%
\def\ExerciseName{{\"U}bung}%
\def\AnswerName{L{\\"o}sung zu den {\\"U}bung}%
}
```

```

\def\ExerciseListName{{\ "U}b.}%
\def\AnswerListName{L{\ "o}sung}%
\def\ExePartName{Teil}%
\def\ArticleOf{von\ }%
}
\addto\captionsngerman{%
\def\listexercisename{Liste der {\ "U}bungen}%
\def\ExerciseName{{\ "U}bung}%
\def\AnswerName{L{\ "o}sung zu den {\ "U}bung}%
\def\ExerciseListName{{\ "U}b.}%
\def\AnswerListName{L{\ "o}sung}%
\def\ExePartName{Teil}%
\def\ArticleOf{von\ }%
}
}{}

```

5.2.2 Layout

First a bunch of length definitions.

```

\newlength{\ExerciseSkipBefore}
\setlength{\ExerciseSkipBefore}{1\baselineskip}
\newlength{\ExerciseSkipAfter}
\setlength{\ExerciseSkipAfter}{0\baselineskip}
\newlength{\Exesep}
\setlength{\Exesep}{1\baselineskip}
\newlength{\Exetopsep}
\setlength{\Exetopsep}\z@
\newlength{\Exeparsep}
\setlength{\Exeparsep}{\parskip}
\newlength{\Exepartopsep}
\setlength{\Exepartopsep}\z@
\newlength{\Exeleftmargin}
\setlength{\Exeleftmargin}\z@
\newlength{\Exerightmargin}
\setlength{\Exerightmargin}\z@
\newlength{\Exelabelwidth}
\setlength{\Exelabelwidth}\z@
\newlength{\Exelabelsep}
\setlength{\Exelabelsep}\z@
\newlength{\ExerciseBefore}
\setlength{\ExerciseBefore}{0em}
\newlength{\QuestionBefore}
\setlength{\QuestionBefore}{.25em}
\newlength{\subQuestionBefore}
\setlength{\subQuestionBefore}{0em}
\newlength{\subsubQuestionBefore}
\setlength{\subsubQuestionBefore}{0em}
\newlength{\QuestionIndent}
\setlength{\QuestionIndent}{3em}
\newlength{\subQuestionIndent}

```

```

\setlength{\subQuestionIndent}{2em}
\newlength{\subsubQuestionIndent}
\setlength{\subsubQuestionIndent}{2.5em}

```

Now the counters

```

\newcounter{Exercise}
\gdef\@ExerciseCounter{Exercise}          %default exercise counter
\newcounter{ExePart}[Exercise]
\newcounter{Question}[Exercise]
\newcounter{subQuestion}[Question]
\newcounter{subsubQuestion}[subQuestion]

```

Presentation of these labels in cross references

```

\renewcommand{\theExercise}{\if@ExeStared\else\arabic{\@ExerciseCounter}\fi}
\renewcommand{\theExePart}{\Roman{ExePart}}
\renewcommand{\theQuestion}{\arabic{Question}}
\renewcommand{\thesubQuestion}{\alph{subQuestion}}
\renewcommand{\thesubsubQuestion}{\roman{subsubQuestion}}

```

For internal purposes

```

\newcounter{savedQuestion}
\newcounter{savedsubQuestion}
\newcounter{savedsubsubQuestion}

```

The \marker command.

```

\def\marker#1#2{\@tempcnta#2\whiledo{\@tempcnta>0}{#1\advance
\@tempcnta by -1 }}

```

Symbol used to indicate the difficulty of an exercise or a question

```

\def\DifficultyMarker{*}

```

Presentation of informations in the header of exercises

```

\newcommand{\ExerciseHeaderTitle}{\quad\ExerciseTitle}
\newcommand{\ExerciseHeaderConcours}{\ExerciseConcours}
\newcommand{\ExerciseHeaderAnnee}{\ \ExerciseAnnee}
\newcommand{\ExerciseHeaderDifficulty}{\theExerciseDifficulty\ }
\newcommand{\ExerciseHeaderOrigin}{%
\ ({\usefont{\encodingdefault}{\rmdefault}{m}{it}\ExerciseOrigin})}
\newcommand{\ExerciseHeaderNB}{\theExercise}
\newcommand{\ExerciseHeaderLabel}{\fbox{\textsc{\ExerciseLabel}}}

```

The header itself

```

\newcommand{\ExerciseHeader}{\centerline{%
\textbf{\large\ExerciseHeaderDifficulty\ExerciseName\ }
\ExerciseHeaderNB\ExerciseHeaderTitle\ExerciseHeaderOrigin}}\medskip}

```

The header of exercise in ExerciseList environment

```

\newcommand{\ExerciseListHeader}{\ExerciseHeaderDifficulty%
\textbf{\ExerciseListName\ \ExerciseHeaderNB%
\ --- \ \ExerciseHeaderTitle}%
\ExerciseHeaderOrigin\ignorespaces}

```

Presentation of informations in the header of ExePart

```
\newcommand{\ExePartHeaderNB}{\ \theExePart}
\newcommand{\ExePartHeaderTitle}{\quad --- \quad {\ExePartTitle}}
\newcommand{\ExePartHeaderDifficulty}{\theExePartDifficulty\ }
```

The header of ExePart

```
\newcommand{\ExePartHeader}{%
\medskip\centerline{\emph{\large\ExePartHeaderDifficulty\ExePartName%
\ExePartHeaderNB\ExePartHeaderTitle}}}%
\newcommand{\ExePartListHeader}{\bigskip%
\emph{\ExePartHeaderDifficulty\ExePartName%
\ExePartHeaderNB\ExePartHeaderTitle}\par\medskip}
```

Presentation of Questions

```
\newcommand{\QuestionNB}{\arabic{Question}.\ }
\newcommand{\QuestionHeaderTitle}{\emph{(\QuestionTitle)}\ }
\newcommand{\QuestionHeaderDifficulty}{\theQuestionDifficulty\ }
\newcommand{\theQuestionDifficulty}{\marker{\DifficultyMarker}%
{\QuestionDifficulty}}
\newcommand{\subQuestionNB}{\alph{subQuestion}}
\newcommand{\subQuestionHeaderTitle}{\emph{(\subQuestionTitle)}\ }
\newcommand{\subQuestionHeaderDifficulty}{\thesubQuestionDifficulty\ }
\newcommand{\subQuestionHeader}{\subQuestionHeaderDifficulty%
\subQuestionNB)\ \emph{\subQuestionHeaderTitle}}
\newcommand{\thesubQuestionDifficulty}{\marker{\DifficultyMarker}%
{\subQuestionDifficulty}}
\newcommand{\subsubQuestionNB}{\roman{subsubQuestion} -- }
\newcommand{\subsubQuestionHeaderTitle}{\emph{(\subsubQuestionTitle)}\ }
\newcommand{\subsubQuestionHeaderDifficulty}{\thesubsubQuestionDifficulty\ }
\newcommand{\subsubQuestionHeader}{\subsubQuestionHeaderDifficulty%
\subsubQuestionNB \emph{\subsubQuestionHeaderTitle} --}
\newcommand{\thesubsubQuestionDifficulty}{%
\marker{\DifficultyMarker}{\subsubQuestionDifficulty}}
```

5.3 Macros definition

```
\newcount\@QuestionLevel \@QuestionLevel=0
\newcommand{\the@QuestionLevel}{\number\@QuestionLevel}
\newbox\@Exercisebox
\newbox\all@Exercisebox
\newbox\temp@Exercisebox
\newbox\all@Answerbox
\newbox\temp@Answerbox
\newif\if@echapq \@echapqfalse
\newif\if@Answer \@Answerfalse
\def\termineliste#1{\global\@echapqfalse%
\whileof{\@QuestionLevel>#1}%
{\ifnum\@QuestionLevel=\colonnesLevel\end{multicols}\colonnesLevel=-10\fi%
\end{list}\advance\@QuestionLevel by -1}%
\ifnum\@QuestionLevel=\colonnesLevel\end{multicols}\colonnesLevel=-10\fi}
```

5.3.1 Definition of Exercise

The keyval package is used to specify various information about an exercise.

```

\newif\if@ExeTitle \@ExeTitlefalse
\newif\if@ExeConcours \@ExeConcoursfalse
\newif\if@ExeAnnee \@ExeAnneefalse
\newif\if@ExeReName \@ExeReNamefalse
\global\newcount\ExerciseDifficulty \ExerciseDifficulty=0
\newif\if@ExeDifficulty \@ExeDifficultyfalse
\newif\if@ExeOrigin \@ExeOriginfalse
\newif\if@ExeType \@ExeTypefalse
\newif\if@ExeLabel \@ExeLabelfalse
\newif\if@ExeNB \@ExeNBfalse
%
\def\theExerciseDifficulty{\marker{\DifficultyMarker}{\ExerciseDifficulty}}
%
\define@key{PPExercise}{title}%
{\global\@ExeTitletrue\gdef\ExerciseTitle{#1}}
\define@key{PPExercise}{concours}%
{\global\@ExeConcourstrue\gdef\ExerciseConcours{#1}}
\define@key{PPExercise}{annee}%
{\global\@ExeAnneetrue\gdef\ExerciseAnnee{#1}}
\define@key{PPExercise}{difficulty}%
{\global\@ExeDifficultytrue\global\ExerciseDifficulty=\number#1}
\define@key{PPExercise}{name}%
{\global\@ExeReNametrue\gdef\@ExerciseName{#1}}
\define@key{PPExercise}{origin}%
{\global\@ExeOrigintrue\gdef\ExerciseOrigin{#1}}
\define@key{PPExercise}{type}%
{\global\@ExeTypetrue\gdef\ExerciseType{#1}}
\define@key{PPExercise}{counter}%
{\gdef\@ExerciseCounter{#1}}
\define@key{PPExercise}{label}%
{\global\@ExeLabeltrue\gdef\ExerciseLabel{#1}\gdef\ExerciseTrueLabel{#1}}
\define@key{PPExercise}{number}%
{\global\@ExeNBtrue\gdef\ExerciseLocalNB{#1}}
\define@key{PPExercise}{class}%
{\gdef\ExerciseClass{#1}}
%
\newif\if@ExeStared
\@ExeStaredfalse
%
\def\@InitExe{\@savemathindent\global\@echapqfalse%
\gdef\ExerciseTitle{}%
\gdef\ExerciseConcours{}%
\gdef\ExerciseAnnee{}%
\gdef\@ExerciseName{}%
\gdef\ExerciseOrigin{}%
\gdef\ExerciseType{}%
\gdef\ExerciseTrueLabel{}%

```

```

\global\ExerciseDifficulty=0%
\global\@ExeTitlefalse%
\global\@ExeConcoursfalse%
\global\@ExeAnneefalse%
\global\@ExeReNamefalse%
\global\@ExeDifficultyfalse%
\global\@ExeOriginfalse%
\global\@ExeTypefalse%
\global\@ExeNBfalse%
\gdef\@ExerciseCounter{Exercise}%
\setcounter{ExePart}{0}%
\setcounter{Question}{0}%
\global\@ExeLabelfalse%
}
%
\def\@getExerciseInfo{%
\if@ExeReName\def\ExerciseName{\@ExerciseName}\fi%
\if@ExeTitle\else\def\ExerciseHeaderTitle{}\fi%
\if@ExeConcours\else\def\ExerciseHeaderConcours{}\fi%
\if@ExeAnnee\else\def\ExerciseHeaderAnnee{}\fi%
\if@ExeOrigin\else\def\ExerciseHeaderOrigin{}\fi%
\if@ExeType\else\def\ExerciseHeaderType{}\fi%
\if@ExeNB\setcounter{Exercise}{\ExerciseLocalNB}%
\protected@edef\@currentlabel{\p@Exercise\theExercise}%
\fi%
\if@ExeDifficulty\else\def\ExerciseHeaderDifficulty{}\fi%
\if@ExeStared\def\ExerciseHeaderNB{}\fi%
\if@ExeLabel\recordExerciseLabel{\ExerciseLabel}\else\def\ExerciseHeaderLabel{}\fi%
}
%
\def\refstepExecounter{\if@ShipThisExercise\if@ExeStared\else\if@ExeNB\else%
\refstepcounter{\@ExerciseCounter}\fi\fi\fi}
%
\def\recordExerciseLabel#1{\label{#1}}
%
\def\@BeginExeBox{\global\setbox\@Exercisebox\vbox\bgroup}
\def\@EndExeBox{\egroup\if@Answer\if@AnswerOutput\@DelayAnswerBox\fi%
\else\if@ExerciseOutput\@DelayExerciseBox\fi\fi}
%
\def\@DelayAnswerBox{%
\if@ShipThisAnswer\if@AnswerDelay\global\setbox\temp@Answerbox%
\vbox{\unvbox\all@Answerbox\vskip\Exesep\unvbox\@Exercisebox\vskip\z@}%
\global\setbox\all@Answerbox\copy\temp@Answerbox%
\else\unvbox\@Exercisebox\fi\fi}
%
\def\@DelayExerciseBox{\if@ShipThisExercise\if@ExerciseDelay%
\global\setbox\temp@Exercisebox%
\vbox{\unvbox\all@Exercisebox\vskip\Exesep\unvbox\@Exercisebox\vskip\z@}%
\global\setbox\all@Exercisebox\copy\temp@Exercisebox%
\else\unvbox\@Exercisebox\fi\fi}

```



```
%
\newcommand{\shipoutAnswer}{\if@AnswerOutput\unvbox\all@Answerbox\fi}
\newcommand{\shipoutExercise}{\if@ExerciseOutput\unvbox\all@Exercisebox\fi}
```

The commands for the Exercise environment.

```
\def\beginExerciseEnv{\@InitExe\@ifnextchar[\@@ExeEnv{\@@ExeEnv[]}}%
%
\def\@@ExeEnv[#1]{\setkeys{PPEExercise}{#1}%
\@selectExercise\global\@Answerfalse\@BeginExeBox\@@ExeEnv}
%
\newcommand{\@@ExeEnv}{%
\vskip\ExerciseSkipBefore
\@QuestionLevel1
\refstepExecounter
\begingroup\@getExerciseInfo\ExerciseHeader
\if@ExeStared\else%
\addcontentsline{\ext@exercise}{\toc@exercise}{\ExerciseName\
\theExercise\ \expandafter{\itshape \ExerciseTitle}\hspace{.66em}}
\fi%
\endgroup}
%
%
\def\endExerciseEnv{\termineliste{1}\@EndExeBox%
\vskip\ExerciseSkipAfter}
```

The commands for exercise within `jExerciseList` environment

```
\def\ExerciseCmd{\@InitExe\@ifstar{\global\@ExeStaredtrue\@ExeCmd}%
{\global\@ExeStaredfalse\@ExeCmd}}
%
\def\@ExeCmd{\@ifnextchar[\@@ExeCmd{\@@ExeCmd[]}}%] for emacs
%
\def\@@ExeCmd[#1]{\setkeys{PPEExercise}{#1}\@@ExeCmd}
%
\newcommand{\@@ExeCmd}{%
\ifnum\@QuestionLevel=0
\advance \@QuestionLevel by 1
\begin{list}{\@getExerciseInfo\ExerciseListHeader}%
{\partopsep\Exepartopsep \labelsep\Exelabelsep \itemsep \Exesep%
\parsep\Exeparsep \topsep\Exetopsep \labelwidth\Exelabelwidth%
\leftmargin\Exeleftmargin \rightmargin\Exerightmargin}
\else
\termineliste{1}\@EndExeBox
\fi
\@selectExercise
\global\@Answerfalse\@BeginExeBox\refstepExecounter%
\if@ExeStared\else%
\addcontentsline{\ext@exercise}{\toc@exercise}{\ExerciseName\
\theExercise\ \expandafter{\itshape \ExerciseTitle}\hspace{.66em}}
\fi%
\item\ignorespaces
}
```

```

%
\def\defineExePartInEnv{\def\@ExePartHeader{\ExePartHeader}}
\def\defineExePartInList{\def\@ExePartHeader{\ExePartListHeader}}
\def\defineExerciseEnv{%
  \defineExePartInEnv
  \renewenvironment{Exercise}{\global\beginExerciseEnv}%
  {\@ExeStaredfalse\endExerciseEnv}
  \renewenvironment{Exercise*}{\global\@ExeStaredtrue\beginExerciseEnv}%
  {\@ExeStaredfalse\endExerciseEnv}
}
\newenvironment{Exercise}{}{}
\newenvironment{Exercise*}{}{}
%
\def\defineExerciseCmd{\def\Exercise{\ExerciseCmd}}
%
\renewcommand{\Exercise}{}
%
\defineExerciseEnv
%
\def\beginExerciseListEnv{\defineExerciseCmd\defineAnswerCmd%
\defineExePartInList}
%
\def\endExerciseListEnv{\termineliste{1}\@EndExeBox\termineliste{0}}%
\defineExerciseEnv\defineAnswerEnv}
%
\newenvironment{ExerciseList}{\beginExerciseListEnv}{\endExerciseListEnv}

```

5.3.2 Definition of questions

```

\def\QuestionTitle{}
\newif\if@QuestionTitle \@QuestionTitlefalse
\global\newcount\QuestionDifficulty \QuestionDifficulty=0
\newif\if@QuestionDifficulty \@QuestionDifficultyfalse
%
\define@key{PPQuestion}{title}{%
\global\@QuestionTitletrue\gdef\QuestionTitle{#1}}
\define@key{PPQuestion}{difficulty}{%
\global\@QuestionDifficultytrue\global\QuestionDifficulty=\number#1}
%
\def\@InitQuestion{\nopagebreak
\gdef\QuestionTitle{}%
\global\QuestionDifficulty=0%
\global\@QuestionTitlefalse%
\global\@QuestionDifficultyfalse}
%
\def\@getQuestionInfo{%
\if@QuestionTitle\else\def\QuestionHeaderTitle{}\fi
\if@QuestionDifficulty\else\def\QuestionHeaderDifficulty{}\fi
}
%

```

```

\def\EndCurrentQuestion{\termineliste{1}}
%
\def\Question{\@InitQuestion\@ifnextchar[\@@Question{\@@Question[]}}%
%
\def\@@Question[#1]{\setkeys{PPQuestion}{#1}\@@@Question}
%
\def\@QuestionHeader{\item[\makebox[0cm][r]{\begingroup\@getQuestionInfo%
\QuestionHeaderDifficulty\QuestionNB\endgroup}}}%
\begingroup\@getQuestionInfo\QuestionHeaderTitle\endgroup\ignorespaces}
\newcommand{\@@@Question}{%
  \ifnum\@QuestionLevel=1
  \advance \@QuestionLevel by 1
  \begin{list}{\leftmargin \QuestionIndent
    \partopsepOpt \parsep\parskip \topsep \QuestionBefore
    \itemsep \QuestionBefore \labelwidth 2em
    \labelsep .33em
    \usecounter{Question}}
    \if@echapq
      \setcounter{Question}{\value{savedQuestion}}\global\@echapqfalse
    \fi
    \refstepcounter{Question}
    \@restoremathindent
    \@decalemathindent{\QuestionIndent}
    \@QuestionHeader
  \else
    \ifnum\@QuestionLevel=2
      \refstepcounter{Question}
      \@QuestionHeader
    \else
      \ifnum\@QuestionLevel>2
        \termineliste{2}
        \refstepcounter{Question}
        \@QuestionHeader
      \else
        \PackageError{exercise}{You don't respect the hierarchy of
          questions}{Verify the Question}
      \fi
    \fi
  \fi
}

```

5.3.3 Definition of sub-questions and sub-sub-questions

Here a good factorization is possible, but I prefer readability over efficacy.

```

\def\subQuestionTitle{}
\newif\if@subQuestionTitle\@subQuestionTitlefalse
\global\newcount\subQuestionDifficulty\subQuestionDifficulty=0
\newif\if@subQuestionDifficulty\@subQuestionDifficultyfalse
%
\define@key{PPsubQuestion}{title}{%

```

```

\gdef\subQuestionTitle{#1}\global\@subQuestionTitletrue}
\define@key{PPsubQuestion}{difficulty}{%
\global\@subQuestionDifficultytrue\global\subQuestionDifficulty=\number#1}
%
\def\@InitsubQuestion{\gdef\subQuestionTitle{%
\global\subQuestionDifficulty=0%
\global\@subQuestionTitlefalse%
\global\@subQuestionDifficultyfalse}
%
\def\@getsubQuestionInfo{%
\if@subQuestionTitle\else\def\subQuestionHeaderTitle{}\fi
\if@subQuestionDifficulty\else\def\subQuestionHeaderDifficulty{}\fi
}
%
\def\EndCurrentsubQuestion{\termineliste{2}}
%
\def\subQuestion{\@InitsubQuestion%
\@ifnextchar[{\@subQuestion{\@subQuestion[]}}%]
\def\@subQuestion[#1]{\setkeys{PPsubQuestion}{#1}\@subQuestion}
%
\def\@subQuestionHeader{\item[\makebox[0cm]{r}%
{\begingroup\@getsubQuestionInfo\subQuestionHeaderDifficulty%
\subQuestionNB\endgroup}}}%
\begingroup\@getsubQuestionInfo\subQuestionHeaderTitle\endgroup%
\ignorespaces}
\newcommand{\@@@subQuestion}{%
\ifnum\@QuestionLevel=2
\advance \@QuestionLevel by 1
\begin{list}{\leftmargin \subQuestionIndent
\partopsepOpt \parsep\parskip \topsep \subQuestionBefore
\itemsep \subQuestionBefore \labelwidth 2em
\labelsep .33em
\usecounter{subQuestion}}
\if@echapq
\setcounter{subQuestion}{\value{savedsubQuestion}}%
\global\@echapqfalse
\fi
\refstepcounter{subQuestion}
\@restoremathindent
\@decalemathindent{\subQuestionIndent}
\@subQuestionHeader
\else
\ifnum\@QuestionLevel=3
\refstepcounter{subQuestion}
\@subQuestionHeader
\else
\ifnum\@QuestionLevel>3
\termineliste{3}
\refstepcounter{subQuestion}
\@subQuestionHeader

```

```

\else
\PackageError{exercise}{You don't respect the hierarchy of
subQuestion}{Verify the subQuestion}
\fi
\fi
\fi
}
%
\def\subsubQuestionTitle{}
\newif\if@subsubQuestionTitle\@subsubQuestionTitlefalse
\global\newcount\subsubQuestionDifficulty\subsubQuestionDifficulty=0
\newif\if@subsubQuestionDifficulty\@subsubQuestionDifficultyfalse
%
\define@key{PPsubsubQuestion}{title}{%
\gdef\subsubQuestionTitle{#1}\global\@subsubQuestionTitletrue}
\define@key{PPsubsubQuestion}{difficulty}{%
\global\@subsubQuestionDifficultytrue%
\global\subsubQuestionDifficulty=\number#1}
%
\def\@InitsubsubQuestion{\gdef\subsubQuestionTitle{}%
\global\subsubQuestionDifficulty=0%
\global\@subsubQuestionTitlefalse%
\global\@subsubQuestionDifficultyfalse}
%
\def\@getsubsubQuestionInfo{%
\if@subsubQuestionTitle\else\def\subsubQuestionHeaderTitle{}\fi
\if@subsubQuestionDifficulty\else\def\subsubQuestionHeaderDifficulty{}\fi
}
%
\def\EndCurrentsubsubQuestion{\termineliste{3}}
\def\subsubQuestion{\@InitsubsubQuestion%
\@ifnextchar[\@@subsubQuestion{\@@subsubQuestion[]}}%
\def\@@subsubQuestion[#1]{\setkeys{PPsubsubQuestion}{#1}\@@subsubQuestion}
%
\def\@subsubQuestionHeader{\item[{\makebox[0cm][r]%
{\begingroup\@getsubsubQuestionInfo\subsubQuestionHeaderDifficulty%
\subsubQuestionNB\endgroup}}}%
\begingroup\@getsubsubQuestionInfo\subsubQuestionHeaderTitle\endgroup%
\ignorespaces}
\newcommand{\@@@subsubQuestion}{%
\ifnum\@QuestionLevel=3
\advance \@QuestionLevel by 1
\begin{list}{\leftmargin \subsubQuestionIndent
\partopsepOpt \parsep\parskip \topsep \subsubQuestionBefore
\itemsep \subsubQuestionBefore \labelwidth 2em
\labelsep .33em
\usecounter{subsubQuestion}}
\if@echapq
\setcounter{subsubQuestion}{\value{savedsubsubQuestion}}%
\global\@echapqfalse

```

```

\fi
\refstepcounter{subsubQuestion}
\@restoremathindent
\@decalemathindent{\subsubQuestionIndent}
\@subsubQuestionHeader
\else
\ifnum\@QuestionLevel=4
\refstepcounter{subsubQuestion}
\@subsubQuestionHeader
\else
\ifnum\@QuestionLevel>4
\termineliste{4}
\refstepcounter{subsubQuestion}
\@subsubQuestionHeader
\else
\PackageError{exercise}{You don't respect the hierarchy of
subsubQuestion}{Verify the subsubQuestion}
\fi
\fi
\fi
}

```

5.3.4 Presentation of part (within an exercise)

```

\newif\if@ExePartStared \@ExePartStaredfalse
\newif\if@ExePartTitle \@ExePartTitlefalse
\newif\if@ExePartReName \@ExePartReNamefalse
\newif\if@ExePartDifficulty \@ExePartDifficultyfalse
\global\newcount\ExePartDifficulty \ExePartDifficulty=0
%
\def\theExePartDifficulty{\marker{\DifficultyMarker}{\ExePartDifficulty}}
%
\def\@InitExePart{\global\@echapqfalse%
\gdef\ExePartTitle{}%
\gdef\@ExePartName{}%
\global\ExePartDifficulty=0%
\global\@ExePartTitlefalse%
\global\@ExePartReNamefalse%
\global\@ExePartDifficultyfalse%
\setcounter{Question}{0}\termineliste{1}}
%
\define@key{PPExePart}{title}{\gdef\ExePartTitle{#1}%
\global\@ExePartTitletrue}
\define@key{PPExePart}{name}{\gdef\@ExePartName{#1}%
\global\@ExePartReNametrue}
\define@key{PPExePart}{difficulty}{\global\@ExePartDifficultytrue%
\global\ExePartDifficulty=\number#1}
%
\def\@getExePartInfo{%
\if@ExePartReName\def\ExePartName{\@ExePartName}\fi

```

```

\if@ExePartTitle\else\def\ExePartHeaderTitle{}\fi
\if@ExePartDifficulty\else\def\ExePartHeaderDifficulty{}\fi
\if@ExePartStared\def\ExePartHeaderNB{}\fi
}
%
\def\ExePart{\@InitExePart\@ifstar{\global\@ExePartStaredtrue\@ExePart}%
{\global\@ExePartStaredfalse\@ExePart}}
%
\def\@ExePart{\@ifnextchar[\@@ExePart{\@@ExePart[]}}%] for emacs
%
\def\@@ExePart[#1]{\setkeys{PPExePart}{#1}\@@@ExePart}
%
\newcommand{\@@@ExePart}{%
  \if@ExePartStared\else\refstepcounter{ExePart}\fi
  \begingroup\@getExePartInfo\@ExePartHeader\endgroup}
%

```

5.3.5 Presentation of answers

```

\newbox\@Answerbox
%
%\changes{v1.3}{2009/03/26}{Header of answers are now correct.}
%
\newcommand{\AnswerHeader}{\medskip\centerline{\textbf{\AnswerName\ %
\ExerciseHeaderNB}}\smallskip}}
%
\newcommand{\AnswerListHeader}{\textbf{\AnswerListName\
(\ExerciseListName\ \ExerciseHeaderNB)\ ---\ }}
%
% The commands for <Exercise> environment
%
\def\@InitAnswer{\@savemathindent\global\@echapqfalse%
\gdef\AnswerRef{}%
\global\@AnswerReffalse%
\gdef\AnswerNB{}%
\global\@AnswerNBfalse%
\setcounter{ExePart}{0}%
\setcounter{Question}{0}}
%
\def\@getAnswerInfo{%
\if@AnswerRef%
\def\theExercise{\ref{\AnswerRef}}%
\def\AnswerListHeader{\@AnswerHeaderRef}
\else
\if@AnswerNB
\def\ExerciseTitle{%
\def\ExerciseName{%
\def\ExerciseOrigin{%
\def\ExerciseType{%
\ExerciseDifficulty=0%
\def\theExercise{\AnswerNB}%

```

```

\else
\if@AswLastExe
\else
\PackageWarning{Exercise}%
{An answer has no reference and no number}{}%
\def\AnswerHeaderRef{\AnswerName\ ???}%
\def\AnswerListHeaderRef{\AnswerName\ ???}%
\fi\fi\fi}
%
\newif\if@AnswerRef          \@AnswerReffalse
\newif\if@AnswerNB          \@AnswerNBfalse
%
\define@key{PPAnswer}{ref}{\global\@AnswerReftrue\gdef\AnswerRef{\string#1}}
\define@key{PPAnswer}{number}{\global\@AnswerNBtrue\gdef\AnswerNB{\string#1}}
%
\def\beginAnswerEnv{\@InitAnswer\@ifnextchar[\@@AnswerEnv{\@@AnswerEnv[]}}%
%
\def\@@AnswerEnv[#1]{\setkeys{PPAnswer}{#1}%
\global\@Answertrue\@selectAnswer\@BeginExeBox\@@AnswerEnv}
%
\newcommand{\@@@AnswerEnv}{%
\@QuestionLevel1
\begingroup\@getAnswerInfo\AnswerHeader\endgroup}
%
\def\endAnswerEnv{\termineliste{1}\@EndExeBox\termineliste{0}}
%
\newenvironment{Answer}{}{}
\def\defineAnswerEnv{
\gdef\@AnswerHeaderRef{\AnswerHeader}
\renewenvironment{Answer}{\beginAnswerEnv}{\endAnswerEnv}}
%
\defineAnswerEnv
%
\def\AnswerCmd{\@InitAnswer\@ifnextchar[\@@AnswerCmd{\@@AnswerCmd[]}}
%
\def\@@AnswerCmd[#1]{\setkeys{PPAnswer}{#1}\@@@AnswerCmd}
%
\newcommand{\@@@AnswerCmd}{%
\ifnum\@QuestionLevel=0
\advance \@QuestionLevel by 1
\begin{list}{}{\partopsep\Exepartopsep \labelsep\Exelabelsep
\itemsep \Exesep \parsep\Exeparsep
\topsep\Exetopsep \labelwidth\Exelabelwidth
\leftmargin\Exeleftmargin
\rightmargin\Exerightmargin }
%%
\refstepExecounter
\else
\termineliste{1}\@EndExeBox
\fi
\global\@Answertrue\@selectAnswer\@BeginExeBox%

```



```

\item[\bgroup\@getAnswerInfo\AnswerListHeader\egroup]\ignorespaces
}
%
\def\defineAnswerCmd{\gdef\@AnswerHeaderRef{\AnswerListHeader}%
\gdef\Answer{\AnswerCmd}}

```

5.3.6 Exercises selection

```

\newif\if@ShipThisExercise      \@ShipThisExercisetrue
\newif\if@@ShipThisExercise     \@@ShipThisExercisetrue
\newif\if@ExerciseSelected      \@ExerciseSelectedtrue
\newif\if@ShipThisAnswer        \@ShipThisAnswertrue
\newif\if@@ShipThisAnswer       \@@ShipThisAnswertrue
\newif\if@ExeSelectConcours     \@ExeSelectConcoursfalse
\newif\if@ExeSelectAnnee        \@ExeSelectAnneefalse
%% \newif\if@ExeSelectDifficulty \@ExeSelectDifficultyfalse
\newif\if@ExeSelectOrigin       \@ExeSelectOriginfalse
\newif\if@ExeSelectClass        \@ExeSelectClassfalse
\newif\if@ExeSelectType         \@ExeSelectTypfalse
\newif\if@ExeSelectLabel        \@ExeSelectLabelfalse

```

```

\define@key{PPExerciseSelect}{concours}%
{\global\@ExeSelectConcourstrue\gdef\ExerciseSelectConcours{#1}}
\define@key{PPExerciseSelect}{annee}%
{\global\@ExeSelectAnneetrue\gdef\ExerciseSelectAnnee{#1}}
\define@key{PPExerciseSelect}{type}%
{\global\@ExeSelectTypetrue\gdef\ExerciseSelectType{#1}}
\define@key{PPExerciseSelect}{origin}%
{\global\@ExeSelectOrigintrue\gdef\ExerciseSelectOrigin{#1}}
\define@key{PPExerciseSelect}{class}%
{\global\@ExeSelectClasstrue\gdef\ExerciseSelectClass{#1}}
\define@key{PPExerciseSelect}{label}%
{\global\@ExeSelectLabeltrue\gdef\ExerciseSelectLabel{#1}}

```

```

\newcommand{\ExerciseStopSelect}{
  \@ExeSelectConcoursfalse
  \@ExeSelectAnneefalse
  \@ExeSelectTypfalse
  \@ExeSelectOriginfalse
  \@ExeSelectClassfalse
  \@ExeSelectLabelfalse
  \@ExeSelectTypfalse
}

```

```

\newcommand{\ExerciseSelect}{\@ifstar{\global\@ExerciseSelectedfalse\@ExerciseSelect}{\global\@
\newcommand{\@ExerciseSelect}[1][\setkeys{PPExerciseSelect}{#1}}

```

```

\def\@selectExercise{%
  \global\@ShipThisExercisetrue

```

```

\global\@@ShipThisExercisefalse
\if@ExeSelectConcours
\@for\@concours:=\ExerciseSelectConcours\do
{\ifthenelse{\equal{\@concours}{\ExerciseConcours}}{
\global\@@ShipThisExercisetrue
}{}}
}
\if@@ShipThisExercise\else\@ShipThisExercisefalse\fi
\global\@@ShipThisExercisefalse
\fi
%
\if@ExeSelectAnnee
\@for\@annee:=\ExerciseSelectAnnee\do
{ \ifthenelse{\equal{\@annee}{\ExerciseAnnee}}{
\global\@@ShipThisExercisetrue
}{}}
}
\if@@ShipThisExercise\else\@ShipThisExercisefalse\fi
\global\@@ShipThisExercisefalse
\fi
%
\if@ExeSelectOrigin
\@for\@origin:=\ExerciseSelectOrigin\do
{ \ifthenelse{\equal{\@origin}{\ExerciseOrigin}}{
\global\@@ShipThisExercisetrue
}{}}
}
\if@@ShipThisExercise\else\@ShipThisExercisefalse\fi
\global\@@ShipThisExercisefalse
\fi
%
\if@ExeSelectClass
\@for\@origin:=\ExerciseSelectClass\do
{ \ifthenelse{\equal{\@origin}{\ExerciseClass}}{
\global\@@ShipThisExercisetrue
}{}}
}
\if@@ShipThisExercise\else\@ShipThisExercisefalse\fi
\global\@@ShipThisExercisefalse
\fi
%
\if@ExeSelectLabel
\@for\@label:=\ExerciseSelectLabel\do
{ \ifthenelse{\equal{\@label}{\ExerciseLabel}}{
\global\@@ShipThisExercisetrue
}{}}
}
\if@@ShipThisExercise\else\@ShipThisExercisefalse\fi
\global\@@ShipThisExercisefalse
\fi

```

```

%
\if@ExeSelectType
\@for\@type:=\ExerciseSelectType\do
{ \ifthenelse{\equal{\@type}{\ExerciseType}}{
    \global\@ShipThisExercisetrue
  }{}}
}
\if@ShipThisExercise\else\@ShipThisExercisefalse\fi
\global\@ShipThisExercisefalse
\fi
\if@ExerciseSelected\else\if@ShipThisExercise\global\@ShipThisExercisefalse\else\global\@Sh
}
\def\@selectAnswer{%
  \global\@ShipThisAnswertrue
  \global\@ShipThisAnswerfalse
  %
  \if@ExeSelectLabel
  \@for\@label:=\ExerciseSelectLabel\do
  { \ifthenelse{\equal{\@label}{\AnswerRef}}{
    \global\@ShipThisAnswertrue
  }{}}
  }
  \if@ShipThisAnswer\else\@ShipThisAnswerfalse\fi
  \global\@ShipThisAnswerfalse
  \fi
  \if@ExerciseSelected\else\if@ShipThisAnswer\global\@ShipThisAnswerfalse\else\global\@ShipTh
}

```

5.3.7 Some extra stuff

```

\newcommand{\ExeText}{\setcounter{savedQuestion}{\value{Question}}%
\termineliste{1}\@echapqtrue}

```

5.3.8 Secret stuff

```

%
% Il est possible de présenter un niveau de sectionnement sur
% deux colonnes avec la commande \colonnesLevel
%
\newcount\colonnesLevel \colonnesLevel=-10
\newskip\tempskipa
\newskip\tempskipb
\def\deuxcolonnes{\tempskipa=\multicolsep\colonnesLevel=\@QuestionLevel
\ifcase\@QuestionLevel \multicolsep=\QuestionBefore %
\or
\multicolsep=\subQuestionBefore\or\multicolsep=\subsubQuestionBefore\fi%
\begin{multicols}{2}}
%
% Tenir compte de l'option fleqn
%
\@ifundefined{if@fleqn}{\newif\if@fleqn\@fleqnfalse}{%
%

```

```

\newlength{\@savedmathindent}
\newcommand{\@savemathindent}{\relax}
\newcommand{\@decalemathindent}[1]{\relax}
\newcommand{\@restoremathindent}{\relax}
\if@fleqn %
  \renewcommand{\@savemathindent}{\setlength{\@savedmathindent}{\mathindent}}
  \renewcommand{\@decalemathindent}[1]{\addtolength{\mathindent}{#1}}
  \renewcommand{\@restoremathindent}{\setlength{\mathindent}{\@savedmathindent}}
\else
  \renewcommand{\@savemathindent}{\relax}
  \renewcommand{\@decalemathindent}[1]{\relax}
  \renewcommand{\@restoremathindent}{\relax}
\fi

```

5.4 The `\renewcounter` command

This commands is the equivalent of the well-known `\renewcommand`, but for counter. It allows you to redefine the Exercise counter, in order to reset it at each chapter (for example).

```

\def\renewcounter#1{%
  \ifundefined{c@#1}
  {\@latex@error{counter #1 undefined}\@ehc}%
  \relax
  \let\@ifdefinable\@rc@ifdefinable
  \@ifnextchar[{\@newctr{#1}}{}]}

\def\ext@exercise{loe}
\newcommand{\ExerciseLevelInToc}[1]{\def\toc@exercise{#1}}
\ExerciseLevelInToc{exercise}
\newcommand{\ListOfExerciseInToc}{\def\ext@exercise{toc}\ExerciseLevelInToc{paragraph}}
\newcommand\listofexercises{%
  \section*{\listexercisename}%
  \@mkboth{\MakeUppercase\listexercisename}%
  {\MakeUppercase\listexercisename}%
  \@starttoc{\ext@exercise}%
}
\newcommand*{\l@exercise}{\@dottedtocline{2}{1.5em}{2.3em}}

```

Index

For entries in type-writer font, numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the definition; numbers in roman refer to the pages where the entry is used.

Symbols		<code>\@@@ExeCmd</code>	17
<code>\"</code>	11, 12	<code>\@@@ExeEnv</code>	17
<code>\'</code>	11	<code>\@@@ExePart</code>	23
<code>\@@@AnswerCmd</code>	24	<code>\@@@Question</code>	19
<code>\@@@AnswerEnv</code>	24	<code>\@@@subQuestion</code>	20

\@@@subsubQuestion	21	\@ExePartReName>true	22
\@@AnswerCmd	24	\@ExePartStared>false	22, 23
\@@AnswerEnv	24	\@ExePartStared>true	23
\@@ExeCmd	17	\@ExePartTitle>false	22
\@@ExeEnv	17	\@ExePartTitle>true	22
\@@ExePart	23	\@ExeReName>false	15, 16
\@@Question	19	\@ExeReName>true	15
\@@ShipThisAnswer>false	27	\@ExeSelectAnneefalse	25
\@@ShipThisAnswer>true	25, 27	\@ExeSelectAnneetrue	25
\@@ShipThisExercisefalse	26, 27	\@ExeSelectClassfalse	25
\@@ShipThisExercisetrue	25-27	\@ExeSelectClasstrue	25
\@subQuestion	20	\@ExeSelectConcoursfalse	25
\@subsubQuestion	21	\@ExeSelectConcourstrue	25
\@AnswerDelay>false	10	\@ExeSelectDifficultyfalse	25
\@AnswerDelay>true	10	\@ExeSelectLabelfalse	25
\@AnswerHeaderRef	23-25	\@ExeSelectLabeltrue	25
\@AnswerNB>false	23, 24	\@ExeSelectOriginfalse	25
\@AnswerNB>true	24	\@ExeSelectOrigintrue	25
\@AnswerOutput>false	10	\@ExeSelectTypefalse	25
\@AnswerOutput>true	10	\@ExeSelectTypetrue	25
\@AnswerReffalse	23, 24	\@ExeStared>false	15, 17, 18
\@AnswerRef>true	24	\@ExeStared>true	17, 18
\@Answerbox	23	\@ExeTitlefalse	15, 16
\@Answerfalse	14, 17	\@ExeTitltrue	15
\@Answertrue	24	\@ExeTypefalse	15, 16
\@AswLastExefalse	10	\@ExeTypetrue	15
\@AswLastExetrue	10	\@ExerciseCounter	13, 15, 16
\@BeginExebox	16, 17, 24	\@ExerciseDelayfalse	10
\@DelayAnswerBox	16	\@ExerciseDelaytrue	10
\@DelayExerciseBox	16	\@ExerciseName	15, 16
\@EndExebox	16-18, 24	\@ExerciseOutputfalse	10
\@ExeAnneefalse	15, 16	\@ExerciseOutputtrue	10
\@ExeAnneetrue	15	\@ExerciseSelect	25
\@ExeCmd	17	\@ExerciseSelectedfalse	25
\@ExeConcoursfalse	15, 16	\@ExerciseSelectedtrue	25
\@ExeConcourstrue	15	\@Exercisebox	14, 16
\@ExeDifficultyfalse	15, 16	\@InitAnswer	23, 24
\@ExeDifficultytrue	15	\@InitExe	15, 17
\@ExeLabelfalse	15, 16	\@InitExePart	22, 23
\@ExeLabeltrue	15	\@InitQuestion	18, 19
\@ExeNB>false	15, 16	\@InitsubQuestion	20
\@ExeNB>true	15	\@InitsubsubQuestion	21
\@ExeOriginfalse	15, 16	\@QuestionDifficultyfalse	18
\@ExeOrigintrue	15	\@QuestionDifficultytrue	18
\@ExePart	23	\@QuestionHeader	19
\@ExePartDifficultyfalse	22	\@QuestionLevel	14, 17, 19-22, 24, 27
\@ExePartDifficultytrue	22	\@QuestionTitlefalse	18
\@ExePartHeader	18, 23	\@QuestionTitltrue	18
\@ExePartName	22	\@ShipThisAnswerfalse	27
\@ExePartReName>false	22	\@ShipThisAnswertrue	25, 27

\@ShipThisExercisefalse	26, 27		
\@ShipThisExercisetrue	25, 27		
\@ShowLabelfalse	10		
\@ShowLabeltrue	10		
\@annee	26		
\@concours	26		
\@currentlabel	16		
\@decalemathindent	19, 20, 22, 28		
\@dottedtocline	28		
\@echapqfalse	14, 15, 19–23		
\@echapqtrue	27		
\@ehc	28		
\@for	26, 27		
\@getAnswerInfo	23–25		
\@getExePartInfo	22, 23		
\@getExerciseInfo	16, 17		
\@getQuestionInfo	18, 19		
\@getsubQuestionInfo	20		
\@getsubsubQuestionInfo	21		
\@ifdefinable	28		
\@ifpackageloaded	11		
\@label	26, 27		
\@latex@error	28		
\@mkboth	28		
\@newctr	28		
\@origin	26		
\@rc@ifdefinable	28		
\@restoremathindent	19, 20, 22, 28		
\@savedmathindent	28		
\@savemathindent	15, 23, 28		
\@selectAnswer	24, 27		
\@selectExercise	17, 25		
\@starttoc	28		
\@subQuestionDifficultyfalse	19, 20		
\@subQuestionDifficultyttrue	20		
\@subQuestionHeader	20		
\@subQuestionTitlefalse	19, 20		
\@subQuestionTitltrue	20		
\@subsubQuestionDifficultyfalse	21		
\@subsubQuestionDifficultyttrue	21		
\@subsubQuestionHeader	21, 22		
\@subsubQuestionTitlefalse	21		
\@subsubQuestionTitltrue	21		
\@tempcnta	13		
\@type	27		
A			
\addcontentsline	17		
\all@Answerbox	14, 16, 17		
\all@Exercisebox	14, 16, 17		
\Answer	25		
\AnswerCmd	24, 25		
\AnswerHeader	23, 24		
\AnswerHeaderRef	24		
\AnswerListHeader	23, 25		
\AnswerListHeaderRef	24		
\AnswerListName	11, 12, 23		
\AnswerName	11, 12, 23, 24		
\AnswerNB	23, 24		
\AnswerRef	23, 24, 27		
\ArticleOf	11, 12		
B			
\baselineskip	12		
\beginAnswerEnv	24		
\beginExerciseEnv	17, 18		
\beginExerciseListEnv	18		
\bigskip	14		
C			
\captionsdutch	11		
\captionsfrenchb	11		
\captionsgerman	11		
\captionsitalian	11		
\captionsngerman	12		
\captionsspanish	11		
\centerline	13, 14, 23		
\changes	23		
\colonnesLevel	14, 27		
D			
\DeclareOption	10		
\define@key	15, 18–22, 24, 25		
\defineAnswerCmd	18, 25		
\defineAnswerEnv	18, 24		
\defineExePartInEnv	18		
\defineExePartInList	18		
\defineExerciseCmd	18		
\defineExerciseEnv	18		
\deuxcolonnes	27		
\DifficultyMarker	13–15, 22		
\do	26, 27		
E			
\encodingdefault	13		
\endAnswerEnv	24		
_	11–14, 17, 23, 24		

\EndCurrentQuestion	19	\ExerciseSelectOrigin	25, 26
\EndCurrentsubQuestion	20	\ExerciseSelectType	25, 27
\EndCurrentsubsubQuestion	21	\ExerciseSkipAfter	12, 17
\endExerciseEnv	17, 18	\ExerciseSkipBefore	12, 17
\endExerciseListEnv	18	\ExerciseStopSelect	25
\equal	26, 27	\ExerciseTitle	13, 15, 17, 23
\es@uclc	11	\ExerciseTrueLabel	15
example	3	\ExerciseType	15, 23, 27
\Exelabelsep	12, 17, 24	\Exerightmargin	12, 17, 24
\Exelabelwidth	12, 17, 24	\Exesep	12, 16, 17, 24
\Exeleftmargin	12, 17, 24	\ExeText	27
\Exeparsep	12, 17, 24	\Exetopsep	12, 17, 24
\ExePart	23	\ext@exercise	17, 28
\ExePartDifficulty	22		
\ExePartHeader	14, 18	H	
\ExePartHeaderDifficulty	14, 23	\hspace	17
\ExePartHeaderNB	14, 23		
\ExePartHeaderTitle	14, 23	I	
\ExePartListHeader	14, 18	\if@@ShipThisAnswer	25, 27
\ExePartName	11, 12, 14, 22	\if@@ShipThisExercise	25–27
\Exeparttopsep	12, 17, 24	\if@Answer	14, 16
\ExePartTitle	14, 22	\if@AnswerDelay	10, 16
\Exercise	18	\if@AnswerNB	23, 24
\ExerciseAnnee	13, 15, 26	\if@AnswerOutput	10, 16, 17
\ExerciseBefore	12	\if@AnswerRef	23, 24
\ExerciseClass	15, 26	\if@AswLastExe	10, 24
\ExerciseCmd	17, 18	\if@echapq	14, 19–21
\ExerciseConcours	13, 15, 26	\if@ExeAnnee	15, 16
\ExerciseDifficulty	15, 16, 23	\if@ExeConcours	15, 16
\ExerciseHeader	13, 17	\if@ExeDifficulty	15, 16
\ExerciseHeaderAnnee	13, 16	\if@ExeLabel	15, 16
\ExerciseHeaderConcours	13, 16	\if@ExeNB	15, 16
\ExerciseHeaderDifficulty	13, 16	\if@ExeOrigin	15, 16
\ExerciseHeaderLabel	13, 16	\if@ExePartDifficulty	22, 23
\ExerciseHeaderNB	13, 16, 23	\if@ExePartReName	22
\ExerciseHeaderOrigin	13, 16	\if@ExePartStared	22, 23
\ExerciseHeaderTitle	13, 16	\if@ExePartTitle	22, 23
\ExerciseHeaderType	16	\if@ExerciseDelay	10, 16
\ExerciseLabel	13, 15, 16, 26	\if@ExerciseOutput	10, 16, 17
\ExerciseLevelInToc	28	\if@ExerciseSelected	25, 27
\ExerciseListHeader	13, 17	\if@ExeReName	15, 16
\ExerciseListName	11–13, 23	\if@ExeSelectAnnee	25, 26
\ExerciseLocalNB	15, 16	\if@ExeSelectClass	25, 26
\ExerciseName	11–13, 16, 17, 23	\if@ExeSelectConcours	25, 26
\ExerciseOrigin	13, 15, 23, 26	\if@ExeSelectDifficulty	25
\ExerciseSelect	25	\if@ExeSelectLabel	25–27
\ExerciseSelectAnnee	25, 26	\if@ExeSelectOrigin	25, 26
\ExerciseSelectClass	25, 26	\if@ExeSelectType	25, 27
\ExerciseSelectConcours	25, 26	\if@ExeStared	13, 15–17
\ExerciseSelectLabel	25–27	\if@ExeTitle	15, 16

\subQuestionIndent	12, 13, 20	\tempskipa	27
\subQuestionNB	14, 20	\tempskipb	27
\subQuestionTitle	14, 19, 20	\termineliste	14, 17–22, 24, 27
\subsubQuestion	21	\the@QuestionLevel	14
\subsubQuestionBefore	12, 21, 27	\theExePart	13, 14
\subsubQuestionDifficulty	14, 21	\theExePartDifficulty	14, 22
\subsubQuestionHeader	14	\theExercise	13, 16, 17, 23
\subsubQuestionHeaderDifficulty .		\theExerciseDifficulty	13, 15
.....	14, 21	\theQuestion	13
\subsubQuestionHeaderTitle ...	14, 21	\theQuestionDifficulty	14
\subsubQuestionIndent	13, 21, 22	\thesubQuestion	13
\subsubQuestionNB	14, 21	\thesubQuestionDifficulty	14
\subsubQuestionTitle	14, 21	\thesubsubQuestion	13
		\thesubsubQuestionDifficulty ...	14
T			
\temp@Answerbox	14, 16	\toc@exercise	17, 28
\temp@Exercisebox	14, 16	\topsep	17, 19–21, 24

Contents