

# The L<sup>A</sup>T<sub>E</sub>X3 Sources

The L<sup>A</sup>T<sub>E</sub>X3 Project\*

January 14, 2010

## Abstract

This is the reference documentation for the `expl3` programming environment. The `expl3` modules set up an experimental naming scheme for L<sup>A</sup>T<sub>E</sub>X commands, which allow the L<sup>A</sup>T<sub>E</sub>X programmer to systematically name functions and variables, and specify the argument types of functions.

The T<sub>E</sub>X and  $\varepsilon$ -T<sub>E</sub>X primitives are all given a new name according to these conventions. However, in the main direct use of the primitives is not required or encouraged: the `expl3` modules define an independent low-level L<sup>A</sup>T<sub>E</sub>X3 programming language.

At present, the `expl3` modules are designed to be loaded on top of L<sup>A</sup>T<sub>E</sub>X 2 $\varepsilon$ . In time, a L<sup>A</sup>T<sub>E</sub>X3 format will be produced based on this code. This allows the code to be used in L<sup>A</sup>T<sub>E</sub>X 2 $\varepsilon$  packages *now* while a stand-alone L<sup>A</sup>T<sub>E</sub>X3 is developed.

**While `expl3` is still experimental, the bundle is now regarded as broadly stable. The syntax conventions and functions provided are now ready for wider use. There may still be changes to some functions, but these will be minor when compared to the scope of `expl3`.**

**New modules will be added to the distributed version of `expl3` as they reach maturity.**

---

\*Frank Mittelbach, Denys Duchier, Chris Rowley, Rainer Schöpf, Johannes Braams, Michael Downes, David Carlisle, Alan Jeffrey, Morten Høgholm, Thomas Lotze, Javier Bezos, Will Robertson, Joseph Wright

# Contents

<b>I</b>	<b>Introduction to <code>expl3</code> and this document</b>	<b>1</b>
<b>1</b>	<b>Naming functions and variables</b>	<b>1</b>
1.0.1	Terminological inexactitude . . . . .	3
<b>2</b>	<b>Documentation conventions</b>	<b>3</b>
<b>II</b>	<b>The <code>l3names</code> package: A systematic naming scheme for <code>TeX</code></b>	<b>5</b>
<b>3</b>	<b>Setting up the <code>LaTeX3</code> programming language</b>	<b>5</b>
<b>4</b>	<b>Using the modules</b>	<b>5</b>
<b>III</b>	<b>The <code>l3basics</code> package: Basic Definitions</b>	<b>6</b>
<b>5</b>	<b>Predicates and conditionals</b>	<b>7</b>
5.1	Primitive conditionals . . . . .	8
5.2	Non-primitive conditionals . . . . .	10
5.3	Applications . . . . .	11
<b>6</b>	<b>Control sequences</b>	<b>11</b>
<b>7</b>	<b>Selecting and discarding tokens from the input stream</b>	<b>12</b>
7.1	Extending the interface . . . . .	13
7.2	Selecting tokens from delimited arguments . . . . .	14
<b>8</b>	<b>That which belongs in other modules but needs to be defined earlier</b>	<b>14</b>
<b>9</b>	<b>Defining functions</b>	<b>15</b>
9.1	Defining new functions using primitive parameter text . . . . .	16
9.2	Defining new functions using the signature . . . . .	18
9.3	Defining functions using primitive parameter text . . . . .	19

9.4	Defining functions using the signature (no checks)	21
9.5	Undefining functions	22
9.6	Copying function definitions	23
9.7	Internal functions	23
<b>10</b>	<b>The innards of a function</b>	<b>24</b>
<b>11</b>	<b>Grouping and scanning</b>	<b>25</b>
<b>12</b>	<b>Checking the engine</b>	<b>25</b>
<b>IV</b>	<b>The <code>l3expan</code> package: Controlling Expansion of Function Arguments</b>	<b>26</b>
<b>13</b>	<b>Brief overview</b>	<b>26</b>
<b>14</b>	<b>Defining new variants</b>	<b>26</b>
14.1	Methods for defining variants	27
<b>15</b>	<b>Introducing the variants</b>	<b>28</b>
<b>16</b>	<b>Manipulating the first argument</b>	<b>29</b>
<b>17</b>	<b>Manipulating two arguments</b>	<b>30</b>
<b>18</b>	<b>Manipulating three arguments</b>	<b>31</b>
<b>19</b>	<b>Preventing expansion</b>	<b>32</b>
<b>20</b>	<b>Unbraced expansion</b>	<b>33</b>
<b>V</b>	<b>The <code>l3prg</code> package: Program control structures</b>	<b>33</b>
<b>21</b>	<b>Conditionals and logical operations</b>	<b>33</b>
<b>22</b>	<b>Defining a set of conditional functions</b>	<b>34</b>

<b>23 The boolean data type</b>	<b>35</b>
<b>24 Boolean expressions</b>	<b>37</b>
<b>25 Case switches</b>	<b>38</b>
<b>26 Generic loops</b>	<b>39</b>
<b>27 Choosing modes</b>	<b>39</b>
<b>28 Alignment safe grouping and scanning</b>	<b>40</b>
<b>29 Producing <math>n</math> copies</b>	<b>40</b>
<b>30 Sorting</b>	<b>41</b>
30.1 Variable type and scope . . . . .	42
<b>VI The l3quark package: “Quarks”</b>	<b>42</b>
<b>31 Functions</b>	<b>43</b>
<b>32 Recursion</b>	<b>44</b>
<b>33 Constants</b>	<b>44</b>
<b>VII The l3token package: A token of my appreciation...</b>	<b>45</b>
<b>34 Character tokens</b>	<b>45</b>
<b>35 Generic tokens</b>	<b>48</b>
35.1 Useless code: because we can! . . . . .	52
<b>36 Peeking ahead at the next token</b>	<b>52</b>
<b>VIII The l3int package: Integers/counters</b>	<b>54</b>
<b>37 Functions</b>	<b>54</b>

<b>38 Formatting a counter value</b>	<b>56</b>
38.1 Internal functions . . . . .	56
<b>39 Variable and constants</b>	<b>57</b>
<b>40 Conversion</b>	<b>59</b>
 <b>IX The l3num package: Integers in macros</b>	 <b>59</b>
<b>41 Functions</b>	<b>59</b>
<b>42 Formatting a counter value</b>	<b>61</b>
<b>43 Variable and constants</b>	<b>61</b>
<b>44 Primitive functions</b>	<b>61</b>
 <b>X The l3intexpr package: Integer expressions</b>	 <b>62</b>
<b>45 Functions</b>	<b>62</b>
<b>46 Primitive functions</b>	<b>64</b>
 <b>XI The l3skip package: Dimension and skip registers</b>	 <b>65</b>
<b>47 Skip registers</b>	<b>65</b>
47.1 Functions . . . . .	65
47.2 Formatting a skip register value . . . . .	67
47.3 Variable and constants . . . . .	67
<b>48 Dim registers</b>	<b>68</b>
48.1 Functions . . . . .	68
48.2 Variable and constants . . . . .	70
<b>49 Muskip</b>	<b>71</b>

<b>XII The l3tl package: Token Lists</b>	<b>71</b>
50 Functions	72
51 Predicates and conditionals	76
52 Working with the contents of token lists	78
53 Variables and constants	79
54 Searching for and replacing tokens	80
55 Heads or tails?	81
<b>XIII The l3toks package: Token Registers</b>	<b>82</b>
56 Allocation and use	82
57 Adding to the contents of token registers	84
58 Predicates and conditionals	85
59 Variable and constants	86
<b>XIV The l3seq package: Sequences</b>	<b>86</b>
60 Functions for creating/initialising sequences	87
61 Adding data to sequences	88
62 Working with sequences	89
63 Predicates and conditionals	90
64 Internal functions	91
65 Functions for ‘Sequence Stacks’	91

<b>XV The l3clist package: Comma separated lists</b>	<b>92</b>
66 Functions for creating/initialising comma-lists	92
67 Putting data in	93
68 Getting data out	94
69 Mapping functions	95
70 Predicates and conditionals	96
71 Higher level functions	97
72 Functions for ‘comma-list stacks’	98
73 Internal functions	98
<b>XVI The l3prop package: Property Lists</b>	<b>99</b>
74 Functions	99
75 Predicates and conditionals	101
76 Internal functions	102
<b>XVII The l3io package: Low-level file i/o</b>	<b>103</b>
77 Functions for output streams	103
77.1 Immediate writing . . . . .	104
77.2 Deferred writing . . . . .	105
77.3 Special characters for writing . . . . .	105
78 Functions for input streams	106
79 Constants	107

<b>XVIII The <code>l3msg</code> package: Communicating with the user</b>	<b>107</b>
80 Creating new messages	108
81 Message classes	108
82 Redirecting messages	110
83 Support functions for output	110
84 Low-level functions	111
85 Kernel-specific functions	112
86 Variables and constants	113
<b>XIX The <code>l3box</code> package: Boxes</b>	<b>114</b>
87 Generic functions	114
88 Horizontal mode	117
89 Vertical mode	118
<b>XX The <code>l3xref</code> package: Cross references</b>	<b>119</b>
<b>XXI The <code>l3keyval</code> package: Key-value parsing</b>	<b>120</b>
90 Functions	121
<b>XXII The <code>l3keys</code> package: Key–value support</b>	<b>122</b>
90.1 Creating keys . . . . .	123
90.2 Sub-dividing keys . . . . .	126
90.3 Multiple choices . . . . .	126
90.4 Setting keys . . . . .	127



90.5 Examining keys: internal representation . . . . .	128
90.6 Internal functions . . . . .	128
90.7 Variables and constants . . . . .	130
<b>XXIII The l3calc package: Infix notation arithmetic in L<sup>A</sup>T<sub>E</sub>X3</b>	<b>131</b>
<b>91 User functions</b>	<b>132</b>
<b>XXIV The l3file package: File Loading</b>	<b>134</b>
<b>92 Loading files</b>	<b>134</b>
<b>93 Variables and constants</b>	<b>135</b>
<b>XXV Implementation</b>	<b>135</b>
<b>94 l3names implementation</b>	<b>135</b>
94.1 Internal functions . . . . .	136
94.2 Package loading . . . . .	136
94.3 Catcode assignments . . . . .	136
94.4 Setting up primitive names . . . . .	137
94.5 Reassignment of primitives . . . . .	138
94.6 expl3 code switches . . . . .	149
94.7 Package loading . . . . .	150
94.8 Finishing up . . . . .	154
94.9 Showing memory usage . . . . .	156
<b>95 l3basics implementation</b>	<b>156</b>
95.1 Renaming some T <sub>E</sub> X primitives (again) . . . . .	156
95.2 Defining functions . . . . .	158
95.3 Selecting tokens . . . . .	159
95.4 Gobbling tokens from input . . . . .	160

95.5	Expansion control from l3expan . . . . .	160
95.6	Conditional processing and definitions . . . . .	161
95.7	Dissecting a control sequence . . . . .	165
95.8	Exist or free . . . . .	167
95.9	Defining and checking (new) functions . . . . .	169
95.10	More new definitions . . . . .	172
95.11	Copying definitions . . . . .	174
95.12	Undefining functions . . . . .	175
95.13	Engine specific definitions . . . . .	175
95.14	Scratch functions . . . . .	176
95.15	Defining functions from a given number of arguments . . . . .	176
95.16	Using the signature to define functions . . . . .	178
<b>96</b>	<b>l3expan implementation</b>	<b>181</b>
96.1	Internal functions and variables . . . . .	181
96.2	Module code . . . . .	182
96.3	General expansion . . . . .	182
96.4	Hand-tuned definitions . . . . .	186
96.5	Definitions with the ‘general’ technique . . . . .	187
96.6	Preventing expansion . . . . .	188
96.7	Defining function variants . . . . .	189
96.8	Last-unbraced versions . . . . .	191
<b>97</b>	<b>l3prg implementation</b>	<b>192</b>
97.1	Variables . . . . .	192
97.2	Module code . . . . .	192
97.3	Choosing modes . . . . .	192
97.4	Producing $n$ copies . . . . .	194
97.5	Booleans . . . . .	197
97.6	Parsing boolean expressions . . . . .	199
97.7	Case switch . . . . .	204
97.8	Sorting . . . . .	205
97.9	Variable type and scope . . . . .	208

<b>98 l3quark implementation</b>	<b>209</b>
<b>99 l3token implementation</b>	<b>212</b>
99.1 Documentation of internal functions . . . . .	212
99.2 Module code . . . . .	213
99.3 Character tokens . . . . .	213
99.4 Generic tokens . . . . .	215
99.5 Peeking ahead at the next token . . . . .	223
<b>100 l3int implementation</b>	<b>229</b>
100.1 Internal functions and variables . . . . .	229
100.2 Module loading and primitives definitions . . . . .	230
100.3 Allocation and setting . . . . .	230
100.4 Defining constants . . . . .	237
100.5 Scanning and conversion . . . . .	238
<b>101 l3num implementation</b>	<b>241</b>
<b>102 l3intexpr implementation</b>	<b>243</b>
<b>103 l3skip implementation</b>	<b>248</b>
103.1 Skip registers . . . . .	248
103.2 Dimen registers . . . . .	252
103.3 Muskips . . . . .	254
<b>104 l3tl implementation</b>	<b>255</b>
104.1 Functions . . . . .	255
104.2 Variables and constants . . . . .	261
104.3 Predicates and conditionals . . . . .	261
104.4 Working with the contents of token lists . . . . .	266
104.5 Checking for and replacing tokens . . . . .	271
104.6 Heads or tails? . . . . .	274

<b>1053toks implementation</b>	<b>275</b>
105.1Allocation and use . . . . .	276
105.2Adding to token registers' contents . . . . .	278
105.3Predicates and conditionals . . . . .	279
105.4Variables and constants . . . . .	280
<b>1063seq implementation</b>	<b>281</b>
106.1Allocating and initialisation . . . . .	281
106.2Predicates and conditionals . . . . .	282
106.3Getting data out . . . . .	283
106.4Putting data in . . . . .	284
106.5Mapping . . . . .	285
106.6Manipulation . . . . .	286
106.7Sequence stacks . . . . .	286
<b>1073clist implementation</b>	<b>287</b>
107.1Allocation and initialisation . . . . .	287
107.2Predicates and conditionals . . . . .	288
107.3Retrieving data . . . . .	289
107.4Storing data . . . . .	290
107.5Mapping . . . . .	291
107.6Higher level functions . . . . .	293
107.7Stack operations . . . . .	295
<b>1083prop implementation</b>	<b>295</b>
108.1Functions . . . . .	296
108.2Predicates and conditionals . . . . .	299
108.3Mapping functions . . . . .	300
<b>1093io implementation</b>	<b>302</b>
109.1Output streams . . . . .	302
109.2Input streams . . . . .	305

<b>1103msg implementation</b>	<b>306</b>
110.1Variables and constants . . . . .	306
110.2Output helper functions . . . . .	308
110.3Generic functions . . . . .	309
110.4General functions . . . . .	311
110.5Redirection functions . . . . .	315
110.6Kernel-specific functions . . . . .	315
<b>1113box implementation</b>	<b>318</b>
111.1Generic boxes . . . . .	318
111.2Vertical boxes . . . . .	320
111.3Horizontal boxes . . . . .	321
<b>1123xref implementation</b>	<b>323</b>
112.1Internal functions and variables . . . . .	323
112.2Module code . . . . .	323
<b>1133xref test file</b>	<b>326</b>
<b>1143keyval implementation</b>	<b>327</b>
114.1Internal functions and variables . . . . .	327
114.2Module code . . . . .	328
114.2.1 Variables and constants . . . . .	335
114.2.2 Internal functions . . . . .	336
114.2.3 Properties . . . . .	344
114.2.4 Messages . . . . .	347
<b>1153calc implementation</b>	<b>348</b>
115.1Variables . . . . .	348
115.2Internal functions . . . . .	349
115.3Module code . . . . .	349
115.4Higher level commands . . . . .	359
<b>1163file implementation</b>	<b>362</b>
<b>Index</b>	<b>366</b>

## Part I

# Introduction to expl3 and this document

This document is intended to act as a comprehensive reference manual for the `expl3` language. A general guide to the `LATEX3` programming language is found in [expl3.pdf](#).

## 1 Naming functions and variables

`LATEX3` does not use `@` as a “letter” for defining internal macros. Instead, the symbols `_` and `:` are used in internal macro names to provide structure. The name of each *function* is divided into logical units using `_`, while `:` separates the *name* of the function from the *argument specifier* (“arg-spec”). This describes the arguments expected by the function. In most cases, each argument is represented by a single letter. The complete list of arg-spec letters for a function is referred to as the *signature* of the function.

Each function name starts with the *module* to which it belongs. Thus apart from a small number of very basic functions, all `expl3` function names contain at least one underscore to divide the module name from the descriptive name of the function. For example, all functions concerned with comma lists are in module `clist` and begin `\clist_`.

Every function must include an argument specifier. For functions which take no arguments, this will be blank and the function name will end `:`. Most functions take one or more arguments, and use the following argument specifiers:

- D** The `D` specifier means *do not use*. All of the `TEX` primitives are initially `\let` to a `D` name, and some are then given a second name. Only the kernel team should use anything with a `D` specifier!
- N and n** These mean *no manipulation*, of a single token for `N` and of a set of tokens given in braces for `n`. Both pass the argument though exactly as given. Usually, if you use a single token for an `n` argument, all will be well.
- c** This means *csname*, and indicates that the argument will be turned into a `csname` before being used. So `\foo:c {ArgumentOne}` will act in the same way as `\foo:N \ArgumentOne`.
- V and v** These mean *value of variable*. The `V` and `v` specifiers are used to get the content of a variable without needing to worry about the underlying `TEX` structure containing the data. A `V` argument will be a single token (similar to `N`), for example `\foo:V \MyVariable`; on the other hand, using `v` a `csname` is constructed first, and then the value is recovered, for example `\foo:v {MyVariable}`.

- o This means *expansion once*. In general, the **V** and **v** specifiers are favoured over **o** for recovering stored information. However, **o** is useful for correctly processing information with delimited arguments.
- x The **x** specifier stands for *exhaustive expansion*: the plain TeX `\edef`.
- f The **f** specifier stands for *full expansion*, and in contrast to *x* stops at the first non-expandable item without trying to execute it.
- T and F** For logic tests, there are the branch specifiers **T** (*true*) and **F** (*false*). Both specifiers treat the input in the same way as **n** (no change), but make the logic much easier to see.
- p The letter **p** indicates TeX *parameters*. Normally this will be used for delimited functions as `expl3` provides better methods for creating simple sequential arguments.
- w Finally, there is the **w** specifier for *weird* arguments. This covers everything else, but mainly applies to delimited values (where the argument must be terminated by some arbitrary string).

Notice that the argument specifier describes how the argument is processed prior to being passed to the underlying function. For example, `\foo:c` will take its argument, convert it to a control sequence and pass it to `\foo:N`.

Variables are named in a similar manner to functions, but begin with a single letter to define the type of variable:

- c** Constant: global parameters whose value should not be changed.
- g** Parameters whose value should only be set globally.
- l** Parameters whose value should only be set locally.

Each variable name is then build up in a similar way to that of a function, typically starting with the module<sup>1</sup> name and then a descriptive part. Variables end with a short identifier to show the variable type:

**bool** Either true or false.

**box** Box register.

**clist** Comma separated list.

**dim** ‘Rigid’ lengths.

**int** Integer-valued count register.

---

<sup>1</sup>The module names are not used in case of generic scratch registers defined in the data type modules, e.g., the **int** module contains some scratch variables called `\l_tmpa_int`, `\l_tmpb_int`, and so on. In such a case adding the module name up front to denote the module and in the back to indicate the type, as in `\l_int_tmpa_int` would be very unreadable.

**num** A ‘fake’ integer type using only macros. Useful for setting up allocation routines.

**prop** Property list.

**skip** ‘Rubber’ lengths.

**seq** ‘Sequence’: a data-type used to implement lists (with access at both ends) and stacks.

**stream** An input or output stream (for reading from or writing to, respectively).

**t1** Token list variables: placeholder for a token list.

**toks** Token register.

### 1.0.1 Terminological inexactitude

A word of warning. In this document, and others referring to the `expl3` programming modules, we often refer to ‘variables’ and ‘functions’ as if they were actual constructs from a real programming language. In truth,  $\text{\TeX}$  is a macro processor, and functions are simply macros that may or mayn’t take arguments and expand to their replacement text. Many of the common variables are *also* macros, and if placed into the input stream will simply expand to their definition as well — a ‘function’ with no arguments and a ‘token list variable’ are in truth one and the same. On the other hand, some ‘variables’ are actually registers that must be initialised and their values set and retrieved with specific functions.

The conventions of the `expl3` code are designed to clearly separate the ideas of ‘macros that contain data’ and ‘macros that contain code’, and a consistent wrapper is applied to all forms of ‘data’ whether they be macros or actually registers. This means that sometimes we will use phrases like ‘the function returns a value’, when actually we just mean ‘the macro expands to something’. Similarly, the term ‘execute’ might be used in place of ‘expand’ or it might refer to the more specific case of ‘processing in  $\text{\TeX}$ ’s stomach’ (if you are familiar with the  $\text{\TeX}$ book parlance).

If in doubt, please ask; chances are we’ve been hasty in writing certain definitions and need to be told to tighten up our terminology.

## 2 Documentation conventions

This document is typeset with the experimental `l3doc` class; several conventions are used to help describe the features of the code. A number of conventions are used here to make the documentation clearer.

Each group of related functions is given in a box. For a function with a “user” name, this might read:



<code>\ExplSyntaxOn</code> <code>\ExplSyntaxOff</code>	<code>\ExplSyntaxOn ... \ExplSyntaxOff</code>
---	---

The textual description of how the function works would appear here. The syntax of the function is shown in mono-spaced text to the right of the box. In this example, the function takes no arguments and so the name of the function is simply reprinted.

For programming functions, which use `_` and `:` in their name there are a few additional conventions: If two related functions are given with identical names but different argument specifiers, these are termed *variants* of each other, and the latter functions are printed in grey to show this more clearly. They will carry out the same function but will take different types of argument:

<code>\seq_new:N</code> <code>\seq_new:c</code>	<code>\seq_new:N &lt;sequence&gt;</code>
--	--

When a number of variants are described, the arguments are usually illustrated only for the base function. Here, `<sequence>` indicates that `\seq_new:N` expects the name of a sequence. From the argument specifier, `\seq_new:c` also expects a sequence name, but as a name rather than as a control sequence. Each argument given in the illustration should be described in the following text.

Some functions are fully expandable, which allows it to be used within an `x`-type argument (in plain  $\TeX$  terms, inside an `\edef`). These fully expandable functions are indicated in the documentation by a star:

<code>\cs_to_str:N *</code>	<code>\cs_to_str:N &lt;cs&gt;</code>
-----------------------------	--------------------------------------

As with other functions, some text should follow which explains how the function works. Usually, only the star will indicate that the function is expandable. In this case, the function expects a `<cs>`, shorthand for a `<control sequence>`.

Conditional (if) functions are normally defined in three variants, with `T`, `F` and `TF` argument specifiers. This allows them to be used for different ‘true’/‘false’ branches, depending on which outcome the conditional is being used to test. To indicate this without repetition, this information is given in a shortened form:

<code>\xetex_if_engine:TF *</code>	<code>\xetex_if_engine:TF &lt;true code&gt; &lt;&gt;false code&gt;</code>
------------------------------------	---

The underlining and italic of `TF` indicates that `\xetex_if_engine:T`, `\xetex_if_engine:F` and `\xetex_if_engine:TF` are all available. Usually, the illustration will use the `TF` variant, and so both `<true code>` and `<>false code>` will be shown. The two variant forms `T` and `F` take only `<true code>` and `<>false code>`, respectively. Here, the star also shows that this function is expandable. With some minor exceptions, *all* conditional functions in the `expl3` modules should be defined in this way.

Variables, constants and so on are described in a similar manner:

`\l_tmpa_tl` A short piece of text will describe the variable: there is no syntax illustration in this case.

In some cases, the function is similar to one in  $\text{\LaTeX} 2_{\epsilon}$  or plain  $\text{\TeX}$ . In these cases, the text will include an extra ‘ **$\text{\TeX}$ hackers note**’ section:

`\token_to_str:N *` `\token_to_str:N` *\token*

The normal description text.

**$\text{\TeX}$ hackers note:** Detail for the experienced  $\text{\TeX}$  or  $\text{\LaTeX} 2_{\epsilon}$  programmer. In this case, it would point out that this function is the  $\text{\TeX}$  primitive `\string`.

## Part II

# The `l3names` package

## A systematic naming scheme for $\text{\TeX}$

### 3 Setting up the $\text{\LaTeX} 3$ programming language

This module is at the core of the  $\text{\LaTeX} 3$  programming language. It performs the following tasks:

- defines new names for all  $\text{\TeX}$  primitives;
- defines catcode regimes for programming;
- provides settings for when the code is used in a format;
- provides tools for when the code is used as a package within a  $\text{\LaTeX} 2_{\epsilon}$  context.

### 4 Using the modules

The modules documented in `source3` are designed to be used on top of  $\text{\LaTeX} 2_{\epsilon}$  and are loaded all as one with the usual `\usepackage{expl3}` or `\RequirePackage{expl3}` instructions. These modules will also form the basis of the  $\text{\LaTeX} 3$  format, but work in this area is incomplete and not included in this documentation.

As the modules use a coding syntax different from standard  $\text{\LaTeX}$  it provides a few functions for setting it up.

<code>\ExplSyntaxOn</code> <code>\ExplSyntaxOff</code>	<code>\ExplSyntaxOn &lt;code&gt; \ExplSyntaxOff</code>
---	--

Issues a catcode regime where spaces are ignored and colon and underscore are letters. A space character may be input with ~ instead.

<code>\ExplSyntaxNamesOn</code> <code>\ExplSyntaxNamesOff</code>	<code>\ExplSyntaxNamesOn &lt;code&gt; \ExplSyntaxNamesOff</code>
---	--

Issues a catcode regime where colon and underscore are letters, but spaces remain the same.

<code>\ProvidesExplPackage</code> <code>\ProvidesExplClass</code> <code>\ProvidesExplFile</code>	<code>\RequirePackage{expl3}</code> <code>\ProvidesExplPackage {&lt;package&gt;}</code> <code>{&lt;date&gt;} {&lt;version&gt;} {&lt;description&gt;}</code>
--	---

The package `l3names` (this module) provides `\ProvidesExplPackage` which is a wrapper for `\ProvidesPackage` and sets up the  $\text{\LaTeX}$ 3 catcode settings for programming automatically. Similar for the relationship between `\ProvidesExplClass` and `\ProvidesClass`. Spaces are not ignored in the arguments of these commands.

<code>\GetIdInfo</code> <code>\filename</code> <code>\filenameext</code> <code>\filedate</code> <code>\fileversion</code> <code>\filetimestamp</code> <code>\fileauthor</code> <code>\filedescription</code>	<code>\RequirePackage{l3names}</code> <code>\GetIdInfo \$Id: &lt; cvs or svn info field&gt; \$ {&lt;description&gt;}</code>
---	--

Extracts all information from a CVS or SVN field. Spaces are not ignored in these fields. The information pieces are stored in separate control sequences with `\filename` for the part of the file name leading up to the period, `\filenameext` for the extension, `\filedate` for date, `\fileversion` for version, `\filetimestamp` for the time and `\fileauthor` for the author.

To summarize: Every single package using this syntax should identify itself using one of the above methods. Special care is taken so that every package or class file loaded with `\RequirePackage` or alike are loaded with usual  $\text{\LaTeX}$  catcodes and the  $\text{\LaTeX}$ 3 catcode scheme is reloaded when needed afterwards. See implementation for details. If you use the `\GetIdInfo` command you can use the information when loading a package with

```
\ProvidesExplPackage{\filename}{\filedate}{\fileversion}{\filedescription}
```

## Part III

# The l3basics package

## Basic Definitions

As the name suggest this package holds some basic definitions which are needed by most or all other packages in this set.

Here we describe those functions that are used all over the place. With that we mean functions dealing with the construction and testing of control sequences. Furthermore the basic parts of conditional processing are covered; conditional processing dealing with specific data types is described in the modules specific for the respective data types.

## 5 Predicates and conditionals

L<sup>A</sup>T<sub>E</sub>X3 has three concepts for conditional flow processing:

**Branching conditionals** Functions that carry out a test and then execute, depending on its result, either the code supplied in the  $\langle true\ arg \rangle$  or the  $\langle false\ arg \rangle$ . These arguments are denoted with T and F repectively. An example would be

```
\cs_if_free:cTF{abc} {\langle true code \rangle} {\langle false code \rangle}
```

a function that will turn the first argument into a control sequence (since it's marked as c) then checks whether this control sequence is still free and then depending on the result carry out the code in the second argument (true case) or in the third argument (false case).

These type of functions are known as 'conditionals'; whenever a TF function is defined it will usually be accompanied by T and F functions as well. These are provided for convenience when the branch only needs to go a single way. Package writers are free to choose which types to define but the kernel definitions will always provide all three versions.

Important to note is that these branching conditionals with  $\langle true\ code \rangle$  and/or  $\langle false\ code \rangle$  are always defined in a way that the code of the chosen alternative can operate on following tokens in the input stream.

These conditional functions may or may not be fully expandable, but if they are expandable they will be accompanied by a 'predicate' for the same test as described below.

**Predicates** 'Predicates' are functions that return a special type of boolean value which can be tested by the function `\if_predicate:w` or in the boolean expression parser. All functions of this type are expandable and have names that end with `_p` in the description part. For example,

`\cs_if_free_p:N`

would be a predicate function for the same type of test as the conditional described above. It would return ‘true’ if its argument (a single token denoted by `N`) is still free for definition. It would be used in constructions like

```
\if_predicate:w \cs_if_free_p:N \l_tmpz_tl <true code> \else:
<false code> \fi:
```

or in expressions utilizing the boolean logic parser:

```
\bool_if:nTF {
  \cs_if_free_p:N \l_tmpz_tl || \cs_if_free_p:N \g_tmpz_tl
} {(true code)} {(false code)}
```

Like their branching cousins, predicate functions ensure that all underlying primitive `\else:` or `\fi:` have been removed before returning the boolean true or false values.<sup>2</sup>

For each predicate defined, a ‘predicate conditional’ will also exist that behaves like a conditional described above.

**Primitive conditionals** There is a third variety of conditional, which is the original concept used in plain `TEX` and `LATEX`. Their use is discouraged in `expl3` (although still used in low-level definitions) because they are more fragile and in many cases require more expansion control (hence more code) than the two types of conditionals described above.

## 5.1 Primitive conditionals

The `ε-TEX` engine itself provides many different conditionals. Some expand whatever comes after them and others don’t. Hence the names for these underlying functions will often contain a `:w` part but higher level functions are often available. See for instance `\intexpr_compare_p:nNn` which is a wrapper for `\if_num:w`.

Certain conditionals deal with specific data types like boxes and fonts and are described there. The ones described below are either the universal conditionals or deal with control sequences. We will prefix primitive conditionals with `\if_`.

<code>\if_true:</code>	★	
<code>\if_false:</code>	★	
<code>\or:</code>	★	
<code>\else:</code>	★	
<code>\fi:</code>	★	<code>\if_true: &lt;true code&gt; \else: &lt;false code&gt; \fi:</code>
<code>\reverse_if:N</code>	★	<code>\if_false: &lt;true code&gt; \else: &lt;false code&gt; \fi:</code>
		<code>\reverse_if:N &lt;primitive conditional&gt;</code>

`\if_true:` always executes `<true code>`, while `\if_false:` always executes `<false code>`.

<sup>2</sup>If defined using the interface provided.

`\reverse_if:N` reverses any two-way primitive conditional. `\else:` and `\fi:` delimit the branches of the conditional. `\or:` is used in case switches, see `l3intexpr` for more.

**T<sub>E</sub>Xhackers note:** These are equivalent to their corresponding T<sub>E</sub>X primitive conditionals; `\reverse_if:N` is  $\varepsilon$ -T<sub>E</sub>X's `\unless`.

<code>\if_meaning:w</code> *	<code>\if_meaning:w</code> $\langle arg_1 \rangle$ $\langle arg_2 \rangle$ $\langle true\ code \rangle$ <code>\else:</code> $\langle false\ code \rangle$ <code>\fi:</code>
------------------------------	---

`\if_meaning:w` executes  $\langle true\ code \rangle$  when  $\langle arg_1 \rangle$  and  $\langle arg_2 \rangle$  are the same, otherwise it executes  $\langle false\ code \rangle$ .  $\langle arg_1 \rangle$  and  $\langle arg_2 \rangle$  could be functions, variables, tokens; in all cases the *unexpanded* definitions are compared.

**T<sub>E</sub>Xhackers note:** This is T<sub>E</sub>X's `\ifx`.

<code>\if:w</code> *	<code>\if:w</code> $\langle token_1 \rangle$ $\langle token_2 \rangle$ $\langle true\ code \rangle$ <code>\else:</code> $\langle false\ code \rangle$ <code>\fi:</code>
<code>\if_charcode:w</code> *	
<code>\if_catcode:w</code> *	

`\if_catcode:w`  $\langle token_1 \rangle$   $\langle token_2 \rangle$   $\langle true\ code \rangle$  `\else:`  $\langle false\ code \rangle$  `\fi:`

These conditionals will expand any following tokens until two unexpandable tokens are left. If you wish to prevent this expansion, prefix the token in question with `\exp_not:N`. `\if_catcode:w` tests if the category codes of the two tokens are the same whereas `\if:w` tests if the character codes are identical. `\if_charcode:w` is an alternative name for `\if:w`.

<code>\if_predicate:w</code> *	<code>\if_predicate:w</code> $\langle predicate \rangle$ $\langle true\ code \rangle$ <code>\else:</code> $\langle false\ code \rangle$ <code>\fi:</code>
--------------------------------	---

This function takes a predicate function and branches according to the result. (In practice this function would also accept a single boolean variable in place of the  $\langle predicate \rangle$  but to make the coding clearer this should be done through `\if_bool:N`.)

<code>\if_bool:N</code> *	<code>\if_bool:N</code> $\langle boolean \rangle$ $\langle true\ code \rangle$ <code>\else:</code> $\langle false\ code \rangle$ <code>\fi:</code>
---------------------------	--

This function takes a boolean variable and branches according to the result.

<code>\if_cs_exist:N</code> *	<code>\if_cs_exist:N</code> $\langle cs \rangle$ $\langle true\ code \rangle$ <code>\else:</code> $\langle false\ code \rangle$ <code>\fi:</code>
<code>\if_cs_exist:w</code> *	

`\if_cs_exist:w`  $\langle tokens \rangle$  `\cs_end:`  $\langle true\ code \rangle$  `\else:`  $\langle false\ code \rangle$  `\fi:`

Check if  $\langle cs \rangle$  appears in the hash table or if the control sequence that can be formed from  $\langle tokens \rangle$  appears in the hash table. The latter function does not turn the control sequence in question into `\scan_stop:!` This can be useful when dealing with control sequences which cannot be entered as a single token.

<code>\if_mode_horizontal:</code>	<code>*</code>
<code>\if_mode_vertical:</code>	<code>*</code>
<code>\if_mode_math:</code>	<code>*</code>
<code>\if_mode_inner:</code>	<code>*</code>

`\if_mode_horizontal: <true code> \else: <false code> \fi:`

Execute *<true code>* if currently in horizontal mode, otherwise execute *<false code>*. Similar for the other functions.

## 5.2 Non-primitive conditionals

<code>\cs_if_eq_name_p:NN</code>
----------------------------------

`\cs_if_eq_name_p:NN <cs1> <cs2>`

Returns ‘true’ if *<cs<sub>1</sub>>* and *<cs<sub>2</sub>>* are textually the same, i.e. have the same name, otherwise it returns ‘false’.

<code>\cs_if_eq_p:NN</code>	<code>*</code>
<code>\cs_if_eq_p:cN</code>	<code>*</code>
<code>\cs_if_eq_p:Nc</code>	<code>*</code>
<code>\cs_if_eq_p:cc</code>	<code>*</code>
<code>\cs_if_eq:NTF</code>	<code>*</code>
<code>\cs_if_eq:cNTF</code>	<code>*</code>
<code>\cs_if_eq:NcTF</code>	<code>*</code>
<code>\cs_if_eq:ccTF</code>	<code>*</code>

`\cs_if_eq_p:NNTF <cs1> <cs2>`  
`\cs_if_eq:NNTF <cs1> <cs2> {\<true code>} {\<false code>}`

These functions check if *<cs<sub>1</sub>>* and *<cs<sub>2</sub>>* have same meaning.

<code>\cs_if_free_p:N</code>	<code>*</code>
<code>\cs_if_free_p:c</code>	<code>*</code>
<code>\cs_if_free:NTF</code>	<code>*</code>
<code>\cs_if_free:cTF</code>	<code>*</code>

`\cs_if_free_p:N <cs>`  
`\cs_if_free:NTF <cs> {\<true code>} {\<false code>}`

Returns ‘true’ if *<cs>* is either undefined or equal to `\tex_relax:D` (the function that is assigned to newly created control sequences by T<sub>E</sub>X when `\cs:w ... \cs_end:` is used). In addition to this, ‘true’ is only returned if *<cs>* does not have a signature equal to D, i.e., ‘do not use’ functions are not free to be redefined.

<code>\cs_if_exist_p:N</code>	<code>*</code>
<code>\cs_if_exist_p:c</code>	<code>*</code>
<code>\cs_if_exist:NTF</code>	<code>*</code>
<code>\cs_if_exist:cTF</code>	<code>*</code>

`\cs_if_exist_p:N <cs>`  
`\cs_if_exist:NTF <cs> {\<true code>} {\<false code>}`

These functions check if *<cs>* exists, i.e., if *<cs>* is present in the hash table and is not the primitive `\tex_relax:D`.

<code>\cs_if_do_not_use_p:N</code>	<code>*</code>
------------------------------------	----------------

`\cs_if_do_not_use_p:N <cs>`

These functions check if  $\langle cs \rangle$  has the arg spec D for ‘do not use’. There are no TF-type conditionals for this function as it is only used internally and not expected to be widely used. (For now, anyway.)

<code>\chk_if_free_cs:N</code>
<code>\chk_if_free_cs:c</code>

`\chk_if_free_cs:N  $\langle cs \rangle$` 

This function checks that  $\langle cs \rangle$  is  $\langle free \rangle$  according to the criteria for `\cs_if_free_p:N` above. If not, an error is generated.

<code>\chk_if_exist_cs:N</code>
<code>\chk_if_exist_cs:c</code>

`\chk_if_exist_cs:N  $\langle cs \rangle$` 

This function checks that  $\langle cs \rangle$  is defined. If it is not an error is generated.

<code>\c_true_bool</code>
<code>\c_false_bool</code>

Constants that represent ‘true’ or ‘false’, respectively. Used to implement predicates.

## 5.3 Applications

<code>\str_if_eq_p:nn *</code>
--------------------------------

`\str_if_eq_p:nn { $\langle string_1 \rangle$ } { $\langle string_2 \rangle$ }`

Expands to ‘true’ if  $\langle string_1 \rangle$  is the same as  $\langle string_2 \rangle$ , otherwise ‘false’. Ignores spaces within the strings.

<code>\str_if_eq_var_p:nf *</code>
------------------------------------

`\str_if_eq_var_p:nf { $\langle string_1 \rangle$ } { $\langle string_2 \rangle$ }`

A variant of `\str_if_eq_p:nn` which has the advantage of obeying spaces in at least the second argument.

## 6 Control sequences

<code>\cs:w</code>	<code>*</code>
<code>\cs_end:</code>	<code>*</code>

`\cs:w  $\langle tokens \rangle$  \cs_end:`

This is the  $\text{\TeX}$  internal way of generating a control sequence from some token list.  $\langle tokens \rangle$  get expanded and must ultimately result in a sequence of characters.

**$\text{\TeX}$ hackers note:** These functions are the primitives `\csname` and `\endcsname`. `\cs:w` is considered weird because it expands tokens until it reaches `\cs_end:`.



<code>\cs_show:N</code>	<code>\cs_show:N &lt;cs&gt;</code>
<code>\cs_show:c</code>	<code>\cs_show:c {&lt;arg&gt;}</code>

This function shows in the console output the *meaning* of the control sequence  $\langle cs \rangle$  or that created by  $\langle arg \rangle$ .

**TeXhackers note:** This is TeX's `\show` and associated csname version of it.

<code>\cs_meaning:N *</code>	<code>\cs_meaning:N &lt;cs&gt;</code>
<code>\cs_meaning:c *</code>	<code>\cs_meaning:c {&lt;arg&gt;}</code>

This function expands to the *meaning* of the control sequence  $\langle cs \rangle$  or that created by  $\langle arg \rangle$ .

**TeXhackers note:** This is TeX's `\meaning` and associated csname version of it.

## 7 Selecting and discarding tokens from the input stream

The conditional processing cannot be implemented without being able to gobble and select which tokens to use from the input stream.

<code>\use:n</code>	<code>*</code>	
<code>\use:nn</code>	<code>*</code>	
<code>\use:nnn</code>	<code>*</code>	
<code>\use:nnnn</code>	<code>*</code>	<code>\use:n {&lt;arg&gt;}</code>

Functions that returns all of their arguments to the input stream after removing the surrounding braces around each argument.

**TeXhackers note:** `\use:n` is L<sup>A</sup>TeX 2<sub>ε</sub>'s `\@firstofone/\@iden`.

<code>\use:c *</code>	<code>\use:c {&lt;cs&gt;}</code>
-----------------------	----------------------------------

Function that returns to the input stream the control sequence created from its argument. Requires two expansions before a control sequence is returned.

**TeXhackers note:** `\use:c` is L<sup>A</sup>TeX 2<sub>ε</sub>'s `\@nameuse`.

<code>\use_none:n</code>	*	
<code>\use_none:nn</code>	*	
<code>\use_none:nnn</code>	*	
<code>\use_none:nnnn</code>	*	
<code>\use_none:nnnnn</code>	*	
<code>\use_none:nnnnnn</code>	*	
<code>\use_none:nnnnnnn</code>	*	
<code>\use_none:nnnnnnnn</code>	*	<code>\use_none:n</code> $\{\langle arg_1 \rangle\}$
<code>\use_none:nnnnnnnnn</code>	*	<code>\use_none:nn</code> $\{\langle arg_1 \rangle\}$ $\{\langle arg_2 \rangle\}$

These functions gobble the tokens or brace groups from the input stream.

**TeXhackers note:** `\use_none:n`, `\use_none:nn`, `\use_none:nnnn` are L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub>'s `\@gobble`, `\@gobbletwo`, and `\@gobblefour`.

<code>\use_i:nn</code>	*	
<code>\use_ii:nn</code>	*	<code>\use_i:nn</code> $\{\langle code_1 \rangle\}$ $\{\langle code_2 \rangle\}$

Functions that execute the first or second argument respectively, after removing the surrounding braces. Primarily used to implement conditionals.

**TeXhackers note:** These are L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub>'s `\@firstoftwo` and `\@secondoftwo`, respectively.

<code>\use_i:nnn</code>	*	
<code>\use_ii:nnn</code>	*	
<code>\use_iii:nnn</code>	*	<code>\use_i:nnn</code> $\{\langle arg_1 \rangle\}$ $\{\langle arg_2 \rangle\}$ $\{\langle arg_3 \rangle\}$

Functions that pick up one of three arguments and execute them after removing the surrounding braces.

**TeXhackers note:** L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> has only `\@thirdofthree`.

<code>\use_i:nnnn</code>	*	
<code>\use_ii:nnnn</code>	*	
<code>\use_iii:nnnn</code>	*	
<code>\use_iv:nnnn</code>	*	<code>\use_i:nnnn</code> $\{\langle arg_1 \rangle\}$ $\{\langle arg_2 \rangle\}$ $\{\langle arg_3 \rangle\}$ $\{\langle arg_4 \rangle\}$

Functions that pick up one of four arguments and execute them after removing the surrounding braces.

## 7.1 Extending the interface

<code>\use_i_ii:nnn</code>	*	<code>\use_i_ii:nnn</code> $\{\langle arg_1 \rangle\}$ $\{\langle arg_2 \rangle\}$ $\{\langle arg_3 \rangle\}$
----------------------------	---	--

This function used in the expansion module reads three arguments and returns (without

braces) the first and second argument while discarding the third argument.

If you wish to select multiple arguments while discarding others, use a syntax like this. Its definition is

```
\cs_set:Npn \use_i_ii:nnn #1#2#3 {#1#2}
```

## 7.2 Selecting tokens from delimited arguments

A different kind of function for selecting tokens from the token stream are those that use delimited arguments.

\use_none_delimit_by_q_nil:w	★
\use_none_delimit_by_q_stop:w	★
\use_none_delimit_by_q_recursion_stop:w	★

```
\use_none_delimit_by_q_nil:w <balanced text> \q_nil
```

Gobbles *<balanced text>*. Useful in gobbling the remainder in a list structure or terminating recursion.

\use_i_delimit_by_q_nil:nw	★
\use_i_delimit_by_q_stop:nw	★
\use_i_delimit_by_q_recursion_stop:nw	★

```
\use_i_delimit_by_q_nil:nw {<arg>} <balanced text> \q_
```

Gobbles *<balanced text>* and executes *<arg>* afterwards. This can also be used to get the first item in a token list.

\use_i_after_fi:nw	★	\use_i_after_fi:nw {<arg>} \fi:
\use_i_after_else:nw	★	\use_i_after_else:nw {<arg>} \else: <balanced text> \fi:
\use_i_after_or:nw	★	\use_i_after_or:nw {<arg>} \or: <balanced text> \fi:
\use_i_after_orelse:nw	★	\use_i_after_orelse:nw {<arg>} \or:/\else: <balanced text> \fi:

Executes *<arg>* after executing closing out *\fi:*. *\use\_i\_after\_orelse:nw* can be used anywhere where *\use\_i\_after\_else:nw* or *\use\_i\_after\_or:nw* are used.

## 8 That which belongs in other modules but needs to be defined earlier

\exp_after:wN	★
---------------	---

```
\exp_after:wN <token12

```

Expands *<token<sub>2 once and then continues processing from *<token<sub>1.</sub>*</sub>*

**T<sub>E</sub>Xhackers note:** This is T<sub>E</sub>X's `\expandafter`.

<code>\exp_not:N</code> *	<code>\exp_not:N</code> $\langle token \rangle$
<code>\exp_not:n</code> *	<code>\exp_not:n</code> $\{\langle tokens \rangle\}$

In an expanding context, this function prevents  $\langle token \rangle$  or  $\langle tokens \rangle$  from expanding.

**T<sub>E</sub>Xhackers note:** These are T<sub>E</sub>X's `\noexpand` and  $\varepsilon$ -T<sub>E</sub>X's `\unexpanded`, respectively.

<code>\prg_do_nothing:</code> *	This is as close as we get to a null operation or no-op.
---------------------------------	--

**T<sub>E</sub>Xhackers note:** Definition as in L<sup>A</sup>T<sub>E</sub>X's `\empty` but not used for the same thing.

<code>\iow_log:x</code>	<code>\iow_log:x</code> $\{\langle message \rangle\}$
<code>\iow_term:x</code>	
<code>\iow_shipout_x:Nn</code>	
	<code>\iow_shipout_x:Nn</code> $\langle write\_stream \rangle$ $\{\langle message \rangle\}$

Writes  $\langle message \rangle$  to either to log or the terminal.

<code>\msg_kernel_bug:x</code>	<code>\msg_kernel_bug:x</code> $\{\langle message \rangle\}$
--------------------------------	--

Internal function for calling errors in our code.

<code>\cs_record_meaning:N</code>	Placeholder for a function to be defined by <code>l3chk</code> .
-----------------------------------	--

<code>\c_minus_one</code>	Numeric constants.
<code>\c_zero</code>	
<code>\c_sixteen</code>	

## 9 Defining functions

There are two types of function definitions in L<sup>A</sup>T<sub>E</sub>X3: versions that check if the function name is still unused, and versions that simply make the definition. The latter are used for internal scratch functions that get new meanings all over the place.

For each type there is an additional choice to be made: Does the function to be defined contain delimited arguments? The answer in 99% of the cases is no. For this type the programmer will know the number of arguments and in most cases use the argument signature to signal this, e.g., `\foo_bar:nnn` presumably takes three arguments. We therefore also provide functions that automatically detect how many arguments are required and construct the parameter text on the fly.

A definition of a new function can be done locally and globally. Currently nearly all function definitions are done locally on top level, in other words they are global but don't show it. Therefore I think it may be better to remove the local variants in the future and declare all checked function definitions global.

**T<sub>E</sub>Xhackers note:** While T<sub>E</sub>X makes all definition functions directly available to the user L<sup>A</sup>T<sub>E</sub>X3 hides them very carefully to avoid the problems with definitions that are overwritten accidentally. Many functions that are in T<sub>E</sub>X a combination of prefixes and definition functions are provided as individual functions.

A slew of functions are defined in the following sections for defining new functions.  
Here's a quick summary to get an idea of what's available:

`\cs_(g)(new/set)(_protected)(_nopar):(N/c)(p)(n/x)`

That stands for, respectively, the following variations:

**g** Global or local;

**new/set** Define a new function or re-define an existing one;

**protected** Prevent expansion of the function in **x** arguments;

**nopar** Restrict the argument(s) from containing `\par`;

**N/c** Either a control sequence or a 'c<sub>s</sub>name';

**p** Either the a primitive T<sub>E</sub>X argument or the number of arguments is detected from the argument signature, i.e., `\foo:nnn` is assumed to have three arguments `#1#2#3`;

**n/x** Either an unexpanded or an expanded definition.

That adds up to 128 variations (!). However, the system is very logical and only a handful will usually be required often.

## 9.1 Defining new functions using primitive parameter text

<code>\cs_new:Npn</code> <code>\cs_new:Npx</code> <code>\cs_new:cpn</code> <code>\cs_new:cpx</code>	<code>\cs_new:Npn &lt;cs&gt; &lt;parms&gt; {&lt;code&gt;}</code>
--	--

Defines a function that may contain `\par` tokens in the argument(s) when called. This is not allowed for normal functions.

<code>\cs_gnew:Npn</code>
<code>\cs_gnew:Npx</code>
<code>\cs_gnew:cpn</code>
<code>\cs_gnew:cpx</code>

`\cs_gnew:Npn <cs> <parms> {<code>}`

Global versions of the above functions.

<code>\cs_new_nopar:Npn</code>
<code>\cs_new_nopar:Npx</code>
<code>\cs_new_nopar:cpn</code>
<code>\cs_new_nopar:cpx</code>

`\cs_new_nopar:Npn <cs> <parms> {<code>}`

Defines a new function, making sure that `<cs>` is unused so far. `<parms>` may consist of arbitrary parameter specification in T<sub>E</sub>X syntax. It is under the responsibility of the programmer to name the new function according to the rules laid out in the previous section. `<code>` is either passed literally or may be subject to expansion (under the `x` variants).

<code>\cs_gnew_nopar:Npn</code>
<code>\cs_gnew_nopar:Npx</code>
<code>\cs_gnew_nopar:cpn</code>
<code>\cs_gnew_nopar:cpx</code>

`\cs_gnew_nopar:Npn <cs> <parms> {<code>}`

Like `\cs_new_nopar:Npn` but defines the new function globally. See comments above.

<code>\cs_new_protected:Npn</code>
<code>\cs_new_protected:Npx</code>
<code>\cs_new_protected:cpn</code>
<code>\cs_new_protected:cpx</code>

`\cs_new_protected:Npn <cs> <parms> {<code>}`

Defines a function that is both robust and may contain `\par` tokens in the argument(s) when called.

<code>\cs_gnew_protected:Npn</code>
<code>\cs_gnew_protected:Npx</code>
<code>\cs_gnew_protected:cpn</code>
<code>\cs_gnew_protected:cpx</code>

`\cs_gnew_protected:Npn <cs> <parms> {<code>}`

Global versions of the above functions.

<code>\cs_new_protected_nopar:Npn</code>
<code>\cs_new_protected_nopar:Npx</code>
<code>\cs_new_protected_nopar:cpn</code>
<code>\cs_new_protected_nopar:cpx</code>

`\cs_new_protected_nopar:Npn <cs> <parms> {<code>}`

Defines a function that does not expand when inside an `x` type expansion.

<code>\cs_gnew_protected_nopar:Npn</code>
<code>\cs_gnew_protected_nopar:Npx</code>
<code>\cs_gnew_protected_nopar:cpn</code>
<code>\cs_gnew_protected_nopar:cpx</code>

`\cs_gnew_protected_nopar:Npn <cs> <parms> {<code>}`

Global versions of the above functions.

## 9.2 Defining new functions using the signature

<code>\cs_new:Nn</code>
<code>\cs_new:Nx</code>
<code>\cs_new:cn</code>
<code>\cs_new:cx</code>

`\cs_new:Nn <cs> {<code>}`

Defines a new function, making sure that `<cs>` is unused so far. The parameter text is automatically detected from the length of the function signature. If `<cs>` is missing a colon in its name, an error is raised. It is under the responsibility of the programmer to name the new function according to the rules laid out in the previous section. `<code>` is either passed literally or may be subject to expansion (under the x variants).

**T<sub>E</sub>Xhackers note:** Internally, these use T<sub>E</sub>X's `\long`. These forms are recommended for low-level definitions as experience has shown that `\par` tokens often turn up in programming situations that wouldn't have been expected.

<code>\cs_gnew:Nn</code>
<code>\cs_gnew:Nx</code>
<code>\cs_gnew:cn</code>
<code>\cs_gnew:cx</code>

`\cs_gnew:Nn <cs> {<code>}`

Global versions of the above functions.

<code>\cs_new_nopar:Nn</code>
<code>\cs_new_nopar:Nx</code>
<code>\cs_new_nopar:cn</code>
<code>\cs_new_nopar:cx</code>

`\cs_new_nopar:Nn <cs> {<code>}`

Version of the above in which `\par` is not allowed to appear within the argument(s) of the defined functions.

<code>\cs_gnew_nopar:Nn</code>
<code>\cs_gnew_nopar:Nx</code>
<code>\cs_gnew_nopar:cn</code>
<code>\cs_gnew_nopar:cx</code>

`\cs_gnew_nopar:Nn <cs> {<code>}`

Global versions of the above functions.

<code>\cs_new_protected:Nn</code>
<code>\cs_new_protected:Nx</code>
<code>\cs_new_protected:cn</code>
<code>\cs_new_protected:cx</code>

`\cs_new_protected:Nn <cs> {\code}`

Defines a function that is both robust and may contain `\par` tokens in the argument(s) when called.

<code>\cs_gnew_protected:Nn</code>
<code>\cs_gnew_protected:Nx</code>
<code>\cs_gnew_protected:cn</code>
<code>\cs_gnew_protected:cx</code>

`\cs_gnew_protected:Nn <cs> {\code}`

Global versions of the above functions.

<code>\cs_new_protected_nopar:Nn</code>
<code>\cs_new_protected_nopar:Nx</code>
<code>\cs_new_protected_nopar:cn</code>
<code>\cs_new_protected_nopar:cx</code>

`\cs_new_protected_nopar:Nn <cs> {\code}`

Defines a function that does not expand when inside an `x` type expansion. `\par` is not allowed in the argument(s) of the defined function.

<code>\cs_gnew_protected_nopar:Nn</code>
<code>\cs_gnew_protected_nopar:Nx</code>
<code>\cs_gnew_protected_nopar:cn</code>
<code>\cs_gnew_protected_nopar:cx</code>

`\cs_gnew_protected_nopar:Nn <cs> {\code}`

Global versions of the above functions.

### 9.3 Defining functions using primitive parameter text

Besides the function definitions that check whether or not their argument is an unused function we need function definitions that overwrite currently used definitions. The following functions are provided for this purpose.

<code>\cs_set:Npn</code>
<code>\cs_set:Npx</code>
<code>\cs_set:cpn</code>
<code>\cs_set:cpx</code>

`\cs_set:Npn <cs> <parms> {\code}`

Like `\cs_set_nopar:Npn` but allows `\par` tokens in the arguments of the function being defined.



**T<sub>E</sub>Xhackers note:** These are equivalent to T<sub>E</sub>X’s `\long\def` and so on. These forms are recommended for low-level definitions as experience has shown that `\par` tokens often turn up in programming situations that wouldn’t have been expected.

<code>\cs_gset:Npn</code>
<code>\cs_gset:Npx</code>
<code>\cs_gset:cpn</code>
<code>\cs_gset:cpx</code>

`\cs_gset:Npn <cs> <parms> {<code>}`  
 Global variant of `\cs_set:Npn`.

<code>\cs_set_nopar:Npn</code>
<code>\cs_set_nopar:Npx</code>
<code>\cs_set_nopar:cpn</code>
<code>\cs_set_nopar:cpx</code>

`\cs_set_nopar:Npn <cs> <parms> {<code>}`  
 Like `\cs_new_nopar:Npn` etc. but does not check the `<cs>` name.

**T<sub>E</sub>Xhackers note:** `\cs_set_nopar:Npn` is the L<sup>A</sup>T<sub>E</sub>X3 name for T<sub>E</sub>X’s `\def` and `\cs_set_nopar:Npx` corresponds to the primitive `\edef`. The `\cs_set_nopar:cpn` function was known in L<sup>A</sup>T<sub>E</sub>X2 as `\@namedef`. `\cs_set_nopar:cpx` has no equivalent.

<code>\cs_gset_nopar:Npn</code>
<code>\cs_gset_nopar:Npx</code>
<code>\cs_gset_nopar:cpn</code>
<code>\cs_gset_nopar:cpx</code>

`\cs_gset_nopar:Npn <cs> <parms> {<code>}`  
 Like `\cs_set_nopar:Npn` but defines the `<cs>` globally.

**T<sub>E</sub>Xhackers note:** `\cs_gset_nopar:Npn` and `\cs_gset_nopar:Npx` are T<sub>E</sub>X’s `\gdef` and `\xdef`.

<code>\cs_set_protected:Npn</code>
<code>\cs_set_protected:Npx</code>
<code>\cs_set_protected:cpn</code>
<code>\cs_set_protected:cpx</code>

`\cs_set_protected:Npn <cs> <parms> {<code>}`

Naturally robust macro that won’t expand in an `x` type argument. These varieties allow `\par` tokens in the arguments of the function being defined.

<code>\cs_gset_protected:Npn</code>
<code>\cs_gset_protected:Npx</code>
<code>\cs_gset_protected:cpn</code>
<code>\cs_gset_protected:cpx</code>

`\cs_gset_protected:Npn <cs> <parms> {<code>}`

Global versions of the above functions.

<code>\cs_set_protected_nopar:Npn</code> <code>\cs_set_protected_nopar:Npx</code> <code>\cs_set_protected_nopar:cpn</code> <code>\cs_set_protected_nopar:cpx</code>	<code>\cs_set_protected_nopar:Npn &lt;cs&gt; &lt;parms&gt; {\code}</code>
--	---

Naturally robust macro that won't expand in an `x` type argument. If you want for some reason to expand it inside an `x` type expansion, prefix it with `\exp_after:wN \prg_do_nothing:.`

<code>\cs_gset_protected_nopar:Npn</code> <code>\cs_gset_protected_nopar:Npx</code> <code>\cs_gset_protected_nopar:cpn</code> <code>\cs_gset_protected_nopar:cpx</code>	<code>\cs_gset_protected_nopar:Npn &lt;cs&gt; &lt;parms&gt; {\code}</code>
--	--

Global versions of the above functions.

## 9.4 Defining functions using the signature (no checks)

As above but now detecting the parameter text from inspecting the signature.

<code>\cs_set:Nn</code> <code>\cs_set:Nx</code> <code>\cs_set:cn</code> <code>\cs_set:cx</code>	<code>\cs_set:Nn &lt;cs&gt; {\code}</code>
--	--

Like `\cs_set_nopar:Nn` but allows `\par` tokens in the arguments of the function being defined.

<code>\cs_gset:Nn</code> <code>\cs_gset:Nx</code> <code>\cs_gset:cn</code> <code>\cs_gset:cx</code>	<code>\cs_gset:Nn &lt;cs&gt; {\code}</code>
--	---

Global variant of `\cs_set:Nn`.

<code>\cs_set_nopar:Nn</code> <code>\cs_set_nopar:Nx</code> <code>\cs_set_nopar:cn</code> <code>\cs_set_nopar:cx</code>	<code>\cs_set_nopar:Nn &lt;cs&gt; {\code}</code>
--	--

Like `\cs_new_nopar:Nn` etc. but does not check the `<cs>` name.

<code>\cs_gset_nopar:Nn</code>
<code>\cs_gset_nopar:Nx</code>
<code>\cs_gset_nopar:cn</code>
<code>\cs_gset_nopar:cx</code>

`\cs_gset_nopar:Nn <cs> {<code>}`

Like `\cs_set_nopar:Nn` but defines the `<cs>` globally.

<code>\cs_set_protected:Nn</code>
<code>\cs_set_protected:cn</code>
<code>\cs_set_protected:Nx</code>
<code>\cs_set_protected:cx</code>

`\cs_set_protected:Nn <cs> {<code>}`

Naturally robust macro that won't expand in an `x` type argument. These varieties also allow `\par` tokens in the arguments of the function being defined.

<code>\cs_gset_protected:Nn</code>
<code>\cs_gset_protected:cn</code>
<code>\cs_gset_protected:Nx</code>
<code>\cs_gset_protected:cx</code>

`\cs_gset_protected:Nn <cs> {<code>}`

Global versions of the above functions.

<code>\cs_set_protected_nopar:Nn</code>
<code>\cs_set_protected_nopar:cn</code>
<code>\cs_set_protected_nopar:Nx</code>
<code>\cs_set_protected_nopar:cx</code>

`\cs_set_protected_nopar:Nn <cs> {<code>}`

Naturally robust macro that won't expand in an `x` type argument. This also comes as a `long` version. If you for some reason want to expand it inside an `x` type expansion, prefix it with `\exp_after:wN \prg_do_nothing:.`

<code>\cs_gset_protected_nopar:Nn</code>
<code>\cs_gset_protected_nopar:cn</code>
<code>\cs_gset_protected_nopar:Nx</code>
<code>\cs_gset_protected_nopar:cx</code>

`\cs_gset_protected_nopar:Nn <cs> {<code>}`

Global versions of the above functions.

## 9.5 Undefining functions

<code>\cs_gundefine:N</code>
<code>\cs_gundefine:c</code>

`\cs_gundefine:N <cs>`

Undefines the control sequence globally.

## 9.6 Copying function definitions

<code>\cs_new_eq:NN</code>
<code>\cs_new_eq:cN</code>
<code>\cs_new_eq:Nc</code>
<code>\cs_new_eq:cc</code>
<code>\cs_gnew_eq:NN</code>
<code>\cs_gnew_eq:cN</code>
<code>\cs_gnew_eq:Nc</code>
<code>\cs_gnew_eq:cc</code>

`\cs_new_eq:NN <cs1> <cs2>`

Gives the function  $\langle cs_1 \rangle$  locally or globally the current meaning of  $\langle cs_2 \rangle$ . If  $\langle cs_1 \rangle$  already exists then an error is called.

<code>\cs_set_eq:NN</code>
<code>\cs_set_eq:cN</code>
<code>\cs_set_eq:Nc</code>
<code>\cs_set_eq:cc</code>
<code>\cs_gset_eq:NN</code>
<code>\cs_gset_eq:cN</code>
<code>\cs_gset_eq:Nc</code>
<code>\cs_gset_eq:cc</code>

`\cs_set_eq:cN <cs1> <cs2>`

Gives the function  $\langle cs_1 \rangle$  the current meaning of  $\langle cs_2 \rangle$ . Again, we may always do this globally.

<code>\cs_set_eq:NwN</code>
-----------------------------

`\cs_set_eq:NwN <cs1> <cs2>`  
`\cs_set_eq:NwN <cs1> = <cs2>`

These functions assign the meaning of  $\langle cs_2 \rangle$  locally or globally to the function  $\langle cs_1 \rangle$ . Because the  $\text{\TeX}$  primitive operation is being used which may have an equal sign and (a certain number of) spaces between  $\langle cs_1 \rangle$  and  $\langle cs_2 \rangle$  the name contains a `w`. (Not happy about this convention!).

**$\text{\TeX}$ hackers note:** `\cs_set_eq:NwN` is the  $\text{\LaTeX}$ 3 name for  $\text{\TeX}$ 's `\let`.

## 9.7 Internal functions

<code>\pref_global:D</code>
<code>\pref_long:D</code>
<code>\pref_protected:D</code>

`\pref_global:D \cs_set_nopar:Npn`

Prefix functions that can be used in front of some definition functions (namely ...). The result of prefixing a function definition with `\pref_global:D` makes the definition global, `\pref_long:D` change the argument scanning mechanism so that it allows `\par` tokens

in the argument of the prefixed function, and `\pref_protected:D` makes the definition robust in `\writes` etc.

None of these internal functions should be used by a programmer since the necessary combinations are all available as separate function, e.g., `\cs_set:Npn` is internally implemented as `\pref_long:D \cs_set_nopar:Npn`.

**T<sub>E</sub>Xhackers note:** These prefixes are the primitives `\global`, `\long`, and `\protected`. The `\outer` prefix isn't used at all within L<sup>A</sup>T<sub>E</sub>X3 because ... (it causes more hassle than it's worth? It's never proved useful in any meaningful way?)

## 10 The innards of a function

<code>\cs_to_str:N *</code>	<code>\cs_to_str:N</code> $\langle cs \rangle$
-----------------------------	--

This function returns the name of  $\langle cs \rangle$  as a sequence of letters with the escape character removed.

<code>\token_to_str:N *</code>	<code>\token_to_str:N</code> $\langle arg \rangle$
<code>\token_to_str:c *</code>	

This function return the name of  $\langle arg \rangle$  as a sequence of letters including the escape character.

**T<sub>E</sub>Xhackers note:** This is T<sub>E</sub>X's `\string`.

<code>\token_to_meaning:N *</code>	<code>\token_to_meaning:N</code> $\langle arg \rangle$
------------------------------------	--

This function returns the type and definition of  $\langle arg \rangle$  as a sequence of letters.

**T<sub>E</sub>Xhackers note:** This is T<sub>E</sub>X's `\meaning`.

<code>\cs_get_function_name:N *</code>	
<code>\cs_get_function_signature:N *</code>	<code>\cs_get_function_name:N</code> $\backslash \langle fn \rangle : \langle args \rangle$

The **name** variant strips off the leading escape character and the trailing argument specification (including the colon) to return  $\langle fn \rangle$ . The **signature** variants does the same but returns the signature  $\langle args \rangle$  instead.

<code>\cs_split_function:NN *</code>	<code>\cs_split_function:NN</code> $\backslash \langle fn \rangle : \langle args \rangle$ $\langle post\ process \rangle$
--------------------------------------	---

Strips off the leading escape character, splits off the signature without the colon, informs whether or not a colon was present and then prefixes these results with  $\langle post\ process \rangle$ , i.e.,  $\langle post\ process \rangle \{ \langle name \rangle \} \{ \langle signature \rangle \} \langle true \rangle / \langle false \rangle$ . For example,  $\backslash cs\_get\_function\_name:N$  is nothing more than  $\backslash cs\_split\_function:NN \backslash \langle fn \rangle : \langle args \rangle \backslash use\_i:nnn$ .

$\backslash cs\_get\_arg\_count\_from\_signature:N \star$
---

 $\backslash cs\_get\_arg\_count\_from\_signature:N \backslash \langle fn \rangle : \langle args \rangle$ 

Returns the number of chars in  $\langle args \rangle$ , signifying the number of arguments that the function uses.

Other functions regarding arbitrary tokens can be found in the `l3token` module.

## 11 Grouping and scanning

$\backslash scan\_stop:$
--------------------------

 $\backslash scan\_stop:$ 

This function stops T<sub>E</sub>X's scanning ahead when ending a number.

**T<sub>E</sub>Xhackers note:** This is the T<sub>E</sub>X primitive  $\backslash relax$  renamed.

$\backslash group\_begin:$
$\backslash group\_end:$

 $\backslash group\_begin: \langle \dots \rangle \backslash group\_end:$ 

Encloses  $\langle \dots \rangle$  inside a group.

**T<sub>E</sub>Xhackers note:** These are the T<sub>E</sub>X primitives  $\backslash begingroup$  and  $\backslash endgroup$  renamed.

$\backslash group\_execute\_after:N$
--------------------------------------

 $\backslash group\_execute\_after:N \langle token \rangle$ 

Adds  $\langle token \rangle$  to the list of tokens to be inserted after the current group ends (through an explicit or implicit  $\backslash group\_end:$ ).

**T<sub>E</sub>Xhackers note:** This is T<sub>E</sub>X's  $\backslash aftergroup$ .

## 12 Checking the engine

$\backslash xetex\_if\_engine:TF \star$
---

 $\backslash xetex\_if\_engine:TF \{ \langle true\ code \rangle \} \{ \langle false\ code \rangle \}$ 

This function detects if we're running a XeT<sub>E</sub>X-based format.

<code>\luatex_if_engine:TF *</code>	<code>\luatex_if_engine:TF {\true code} {\false code}</code>
-------------------------------------	--

This function detects if we’re running a LuaTeX-based format.

<code>\c_xetex_is_engine_bool</code> <code>\c_luatex_is_engine_bool</code>	Boolean variables used for the above functions.
---	---

## Part IV

# The l3expan package

## Controlling Expansion of Function Arguments

### 13 Brief overview

The functions in this module all have prefix `exp`.

Not all possible variations are implemented for every base function. Instead only those that are used within the L<sup>A</sup>T<sub>E</sub>X3 kernel or otherwise seem to be of general interest are implemented. Consult the module description to find out which functions are actually defined. The next section explains how to define missing variants.

### 14 Defining new variants

The definition of variant forms for base functions may be necessary when writing new functions or when applying a kernel function in a situation that we haven’t thought of before.

Internally preprocessing of arguments is done with functions from the `\exp_` module. They all look alike, an example would be `\exp_args:NNo`. This function has three arguments, the first and the second are a single tokens the third argument gets expanded once. If `\seq_gpush:No` wouldn’t be defined the example above could be coded in the following way:

```
\exp_args:NNo\seq_gpush:Nn
  \g_file_name_stack
  \l_tmpa_tl
```

In other words, the first argument to `\exp_args:NNo` is the base function and the other arguments are preprocessed and then passed to this base function. In the example the first argument to the base function should be a single token which is left unchanged while the second argument is expanded once. From this example we can also see how the variants are defined. They just expand into the appropriate `\exp_` function followed by the desired base function, e.g.

```
\cs_new_nopar:Npn\seq_gpush:No{\exp_args:NNo\seq_gpush:Nn}
```

Providing variants in this way in style files is uncritical as the `\cs_new_nopar:Npn` function will silently accept definitions whenever the new definition is identical to an already given one. Therefore adding such definition to later releases of the kernel will not make such style files obsolete.

The steps above may be automated by using the function `\cs_generate_variant:Nn`, described next.

## 14.1 Methods for defining variants

```
\cs_generate_variant:Nn <function> <variant argument>
\cs_generate_variant:Nn \foo:Nn {c}
\cs_generate_variant:Nn \foo:Nn {c,Nx,cx}
```

This function greatly simplify the task of defining variations on a base function with differing expansion control. The first example is equivalent to writing

```
\cs_set_nopar:Npn \foo:cn { \exp_args:Nc \foo:Nn }
```

If used with a comma-separated list of variants, it does so for each variant form, i.e., the second example is equivalent to

```
\cs_set_nopar:Npn \foo:cn { \exp_args:Nc \foo:Nn }
\cs_set_nopar:Npn \foo:Nx { \exp_args:NNx \foo:Nn }
\cs_set_nopar:Npn \foo:cx { \exp_args:Ncx \foo:Nn }
```

### Internal functions

```
\cs_generate_internal_variant:n \cs_generate_internal_variant:n {\<args>}
```

Defines the appropriate `\exp_args:N<args>` function, if necessary, to perform the expansion control specified by `<args>`.



## 15 Introducing the variants

The available internal functions for argument expansion come in two flavours, some of them are faster than others. Therefore it is usually best to follow the following guidelines when defining new functions that are supposed to come with variant forms:

- Arguments that might need expansion should come first in the list of arguments to make processing faster.
- Arguments that should consist of single tokens should come first.
- Arguments that need full expansion (i.e., are denoted with `x`) should be avoided if possible as they can not be processed very fast.
- In general `n`, `x`, and `o` (if not in the last position) will need special processing which is not fast and not expandable, i.e., functions of this type may not work correctly in arguments that are itself subject to `x` expansion. Therefore it is best to use the “expandable” functions (i.e., those that contain only `c`, `N`, `o` or `f` in the last position) whenever possible.

The `V` type returns the value of a register, which can be one of `tl`, `num`, `int`, `skip`, `dim`, `toks`, or built-in `TEX` registers. The `v` type is the same except it first creates a control sequence out of its argument before returning the value. This recent addition to the argument specifiers may shake things up a bit as most places where `o` is used will be replaced by `V`. The documentation you are currently reading will therefore require a fair bit of re-writing.

In general, the programmer should not need to be concerned with expansion control. When simply using the content of a variable, functions with a `V` specifier should be used. For those referred to by `(cs)name`, the `v` specifier is available for the same purpose. Only when specific expansion steps are needed, such as when using delimited arguments, should the lower-level functions with `o` specifiers be employed.

The `f` type is so special that it deserves an example. Let’s pretend we want to set `\aaa` equal to the control sequence stemming from turning `b \l_tmpa_tl b` into a control sequence. Furthermore we want to store the execution of it in a `<toks>` register. In this example we assume `\l_tmpa_tl` contains the text string `lur`. The straight forward approach is

```
\toks_set:No \l_tmpa_toks {\cs_set_eq:Nc \aaa {b \l_tmpa_tl b}}
```

Unfortunately this only puts `\exp_args:NNc \cs_set_eq:NN \aaa {b \l_tmpa_tl b}` into `\l_tmpa_toks` and not `\cs_set_eq:NwN \aaa = \blurb` as we probably wanted. Using `\toks_set:Nx` is not an option as that will die horribly. Instead we can do a

```
\toks_set:Nf \l_tmpa_toks {\cs_set_eq:Nc \aaa {b \l_tmpa_tl b}}
```

which puts the desired result in `\l_tmpa_toks`. It requires `\toks_set:Nf` to be defined as

```
\cs_set_nopar:Npn \toks_set:Nf {\exp_args:NNf \toks_set:Nn}
```

If you use this type of expansion in conditional processing then you should stick to using TF type functions only as it does not try to finish any `\if... \fi:` itself!

`\exp_arg:x` `\exp_arg:x {⟨arg⟩}`  
`⟨arg⟩` is expanded fully using an `x` expansion.

When pdfTeX 1.50 arrives, it will contain a primitive for performing the equivalent of an `x` expansion after only one expansion and most importantly: as an expandable operation.

However, we will not be using the expandable command `\expanded` until it is broadly available; note that as of TeX Live 2009, only LuaTeX supports this primitive. Until further notice, `\exp_arg:x` will remain *unexpandable*.

## 16 Manipulating the first argument

`\exp_args:No *` `\exp_args:No ⟨funct⟩ ⟨arg1⟩ ⟨arg2⟩ ...`

The first argument of `⟨funct⟩` (i.e., `⟨arg1⟩`) is expanded once, the result is surrounded by braces and passed to `⟨funct⟩`. `⟨funct⟩` may have more than one argument—all others are passed unchanged.

`\exp_args:Nc *`  
`\exp_args:cc *` `\exp_args:Nc ⟨funct⟩ ⟨arg1⟩ ⟨arg2⟩ ...`

The first argument of `⟨funct⟩` (i.e., `⟨arg1⟩`) is expanded until only characters remain. (An internal error occurs if something else is the result of this expansion.) Then the result is turned into a control sequence and passed to `⟨funct⟩` as the first argument. `⟨funct⟩` may have more than one argument—all others are passed unchanged.

In the `:cc` variant, the `⟨funct⟩` control sequence itself is constructed (with the same process as described above) before `⟨arg1⟩` is turned into a control sequence and passed as its argument.

`\exp_args:NV *` `\exp_args:NV ⟨funct⟩ ⟨register⟩`

The first argument of `⟨funct⟩` (i.e., `⟨register⟩`) is expanded to its value. By value we mean a number stored in an `int` or `num` register, the length value of a `dim`, `skip` or `muskip` register, the contents of a `toks` register or the unexpanded contents of a `tl var.` register. The value is passed onto `⟨funct⟩` in braces.

<code>\exp_args:Nv</code> ★
-----------------------------

`\exp_args:Nv <funct> {<register>}`

Like the `V` type except the register is given by a list of characters from which a control sequence name is generated.

<code>\exp_args:Nx</code>
---------------------------

`\exp_args:Nx <funct> <arg1> <arg2> ...`

The first argument of `<funct>` (i.e., `<arg1>`) is fully expanded until only unexpandable tokens remain, the result is surrounded by braces and passed to `<funct>`. `<funct>` may have more than one argument—all others are passed unchanged. As mentioned before, this type of function is relatively slow.

<code>\exp_args:Nf</code> ★
-----------------------------

`\exp_args:Nf <funct> <arg1> <arg2> ...`

The first argument of `<funct>` (i.e., `<arg1>`) undergoes full expansion until the first unexpandable token is encountered, the result is surrounded by braces and passed to `<funct>`. `<funct>` may have more than one argument—all others are passed unchanged. Beware of its special behavior as explained above.

## 17 Manipulating two arguments

<code>\exp_args:NNx</code> <code>\exp_args:Nnx</code> <code>\exp_args:Ncx</code> <code>\exp_args:Nox</code> <code>\exp_args:Nxo</code> <code>\exp_args:Nxx</code>
--

`\exp_args:Nnx <funct> <arg1> <arg2> ...`

The above functions all manipulate the first two arguments of `<funct>`. They are all slow and non-expandable.

<code>\exp_args:NNo</code>	<code>*</code>
<code>\exp_args:NNc</code>	<code>*</code>
<code>\exp_args:NNv</code>	<code>*</code>
<code>\exp_args:NNV</code>	<code>*</code>
<code>\exp_args:NNf</code>	<code>*</code>
<code>\exp_args:Nno</code>	<code>*</code>
<code>\exp_args:NnV</code>	<code>*</code>
<code>\exp_args:Nnf</code>	<code>*</code>
<code>\exp_args:Noo</code>	<code>*</code>
<code>\exp_args:Noc</code>	<code>*</code>
<code>\exp_args:Nco</code>	<code>*</code>
<code>\exp_args:Ncf</code>	<code>*</code>
<code>\exp_args:Ncc</code>	<code>*</code>
<code>\exp_args:Nff</code>	<code>*</code>
<code>\exp_args:Nfo</code>	<code>*</code>
<code>\exp_args:NVV</code>	<code>*</code>

`\exp_args:NNo`  $\langle funct \rangle$   $\langle arg_1 \rangle$   $\langle arg_2 \rangle$  ...

These are the fast and expandable functions for the first two arguments.

## 18 Manipulating three arguments

So far not all possible functions are provided and even the selection below may be reduced in the future as far as the non-expandable functions are concerned.

<code>\exp_args:NNnx</code>
<code>\exp_args:NNox</code>
<code>\exp_args:Nnnx</code>
<code>\exp_args:Nnox</code>
<code>\exp_args:Noox</code>
<code>\exp_args:Ncnx</code>
<code>\exp_args:Nccx</code>

`\exp_args:Nnnx`  $\langle funct \rangle$   $\langle arg_1 \rangle$   $\langle arg_2 \rangle$   $\langle arg_3 \rangle$  ...

All the above functions are non-expandable.

<code>\exp_args:NNNo</code>	<code>*</code>
<code>\exp_args:NNNV</code>	<code>*</code>
<code>\exp_args:NNoo</code>	<code>*</code>
<code>\exp_args:NNno</code>	<code>*</code>
<code>\exp_args:Nnno</code>	<code>*</code>
<code>\exp_args:Nnnc</code>	<code>*</code>
<code>\exp_args:Nooo</code>	<code>*</code>
<code>\exp_args:Nccc</code>	<code>*</code>
<code>\exp_args:NcNc</code>	<code>*</code>
<code>\exp_args:NcNo</code>	<code>*</code>
<code>\exp_args:Ncco</code>	<code>*</code>

`\exp_args:NNoo`  $\langle funct \rangle$   $\langle arg_1 \rangle$   $\langle arg_2 \rangle$   $\langle arg_3 \rangle$  ...

These are the fast and expandable functions for the first three arguments.

## 19 Preventing expansion

<code>\exp_not:N</code>
<code>\exp_not:c</code>
<code>\exp_not:n</code>

`\exp_not:N`  $\langle token \rangle$   
`\exp_not:n`  $\{ \langle token list \rangle \}$

This function will prohibit the expansion of  $\langle token \rangle$  in situation where  $\langle token \rangle$  would otherwise be replaced by its definition, e.g., inside an argument that is handled by the `x` convention.

**T<sub>E</sub>Xhackers note:** `\exp_not:N` is the primitive `\noexpand` renamed and `\exp_not:n` is the  $\varepsilon$ -T<sub>E</sub>X primitive `\unexpanded`.

<code>\exp_not:o</code>
<code>\exp_not:d</code>
<code>\exp_not:f</code>

`\exp_not:o`  $\{ \langle token list \rangle \}$

Same as `\exp_not:n` except  $\langle token list \rangle$  is expanded once for the `o` type and twice for the `d` type and the result of this expansion is then prohibited from being expanded further.

<code>\exp_not:V</code>
<code>\exp_not:v</code>

`\exp_not:V`  $\langle register \rangle$   
`\exp_not:v`  $\{ \langle token list \rangle \}$

The value of  $\langle register \rangle$  is retrieved and then passed on to `\exp_not:n` which will prohibit further expansion. The `v` type first creates a control sequence from  $\langle token list \rangle$  but is otherwise identical to `V`.

<code>\exp_stop_f:</code>
---------------------------

$\langle f expansion \rangle$  ... `\exp_stop_f:`

This function stops an `f` type expansion. An example use is one such as

```

\tl_set:Nf \l_tmpa_tl {
  \if_case:w \l_tmpa_int
    \or: \use_i_after_orelse:nw {\exp_stop_f: \textbullet}
    \or: \use_i_after_orelse:nw {\exp_stop_f: \textendash}
    \else: \use_i_after_fi:nw {\exp_stop_f: else-item}
  \fi:
}

```

This ensures the expansion is stopped right after finishing the conditional but without expanding `\textbullet` etc.

**T<sub>E</sub>Xhackers note:** This function is a space token but it is better to distinguish this expansion stopping token from a desired space token when writing code.

## 20 Unbraced expansion

<code>\exp_last_unbraced:Nf</code>
<code>\exp_last_unbraced:NV</code>
<code>\exp_last_unbraced:Nv</code>
<code>\exp_last_unbraced:NcV</code>
<code>\exp_last_unbraced:NNNo</code>
<code>\exp_last_unbraced:NNV</code>
<code>\exp_last_unbraced:NNNo</code>

`\exp_last_unbraced:NV <token> <variable name>`

There are a small number of occasions where the last argument in an expansion run must be expanded unbraced. These functions should only be used inside functions, *not* for creating variants.

## Part V

# The l3prg package

## Program control structures

## 21 Conditionals and logical operations

Conditional processing in L<sup>A</sup>T<sub>E</sub>X3 is defined as something that performs a series of tests, possibly involving assignments and calling other functions that do not read further ahead

in the input stream. After processing the input, a *state* is returned. The typical states returned are  $\langle true \rangle$  and  $\langle false \rangle$  but other states are possible, say an  $\langle error \rangle$  state for erroneous input, e.g., text as input in a function comparing integers.

L<sup>A</sup>T<sub>E</sub>X3 has two primary forms of conditional flow processing based on these states. One type is predicate functions that turn the returned state into a boolean  $\langle true \rangle$  or  $\langle false \rangle$ . For example, the function `\cs_if_free_p:N` checks whether the control sequence given as its argument is free and then returns the boolean  $\langle true \rangle$  or  $\langle false \rangle$  values to be used in testing with `\if_predicate:w` or in functions to be described below. The other type is the kind of functions choosing a particular argument from the input stream based on the result of the testing as in `\cs_if_free:NTF` which also takes one argument (the N) and then executes either  $\langle true \rangle$  or  $\langle false \rangle$  depending on the result. Important to note here is that the arguments are executed after exiting the underlying `\if...\fi:` structure

## 22 Defining a set of conditional functions

<code>\prg_return_true:</code> <code>\prg_return_false:</code>
---

These functions exit conditional processing when used in conjunction with the generating functions listed below.

<code>\prg_set_conditional:Nnn</code> <code>\prg_set_conditional:Npnn</code> <code>\prg_new_conditional:Nnn</code> <code>\prg_new_conditional:Npnn</code> <code>\prg_set_protected_conditional:Nnn</code> <code>\prg_set_protected_conditional:Npnn</code> <code>\prg_new_protected_conditional:Nnn</code> <code>\prg_new_protected_conditional:Npnn</code> <code>\prg_set_eq_conditional:NNn</code> <code>\prg_new_eq_conditional:NNn</code>	<code>\prg_set_conditional:Nnn &lt;test&gt; &lt;conds&gt; &lt;code&gt;</code> <code>\prg_set_conditional:Npnn &lt;test&gt; &lt;param&gt; &lt;conds&gt; &lt;code&gt;</code>
--	---

This defines a conditional *base function* which upon evaluation using `\prg_return_true:` and `\prg_return_false:` to finish branches, returns a state. Currently the states are either  $\langle true \rangle$  or  $\langle false \rangle$  although this can change as more states may be introduced, say an  $\langle error \rangle$  state.  $\langle conds \rangle$  is a comma separated list possibly consisting of `p` for denoting a predicate function returning the boolean  $\langle true \rangle$  or  $\langle false \rangle$  values and `TF`, `T` and `F` for the functions that act on the tokens following in the input stream. The `:Nnn` form implicitly determines the number of arguments from the function being defined whereas the `:Npnn` form expects a primitive parameter text.

An example can easily clarify matters here:

```
\prg_set_conditional:Nnn \foo_if_bar:NN {p,TF,T} {
```

```

\if_meaning:w \l_tmpa_tl #1
  \prg_return_true:
\else:
  \if_meaning:w \l_tmpa_tl #2
    \prg_return_true:
  \else:
    \prg_return_false:
  \fi:
\fi:
}

```

This defines the function `\foo_if_bar_p:NN`, `\foo_if_bar:NNTF`, `\foo_if_bar:NNT` but not `\foo_if_bar:NNF` (because `F` is missing from the `<conds>` list). The return statements take care of resolving the remaining `\else:` and `\fi:` before returning the state. There must be a return statement for each branch, failing to do so will result in an error if that branch is executed.

## 23 The boolean data type

This section describes a boolean data type which is closely connected to conditional processing as sometimes you want to execute some code depending on the value of a switch (e.g., draft/final) and other times you perhaps want to use it as a predicate function in an `\if_predicate:w` test. The problem of the primitive `\if_false:` and `\if_true:` tokens is that it is not always safe to pass them around as they may interfere with scanning for termination of primitive conditional processing. Therefore, we employ two canonical booleans: `\c_true_bool` or `\c_false_bool`. Besides preventing problems as described above, it also allows us to implement a simple boolean parser supporting the logical operations And, Or, Not, etc. which can then be used on both the boolean type and predicate functions.

All conditional `\bool_` functions are expandable and expect the input to also be fully expandable (which will generally mean being constructed from predicate functions, possibly nested).

<code>\bool_new:N</code>
<code>\bool_new:c</code>

`\bool_new:N <bool>`

Define a new boolean variable. The initial value is `<false>`. A boolean is actually just either `\c_true_bool` or `\c_false_bool`.



<code>\bool_set_true:N</code>
<code>\bool_set_true:c</code>
<code>\bool_set_false:N</code>
<code>\bool_set_false:c</code>
<code>\bool_gset_true:N</code>
<code>\bool_gset_true:c</code>
<code>\bool_gset_false:N</code>
<code>\bool_gset_false:c</code>

`\bool_gset_false:N <bool>`

Set  $\langle bool \rangle$  either  $\langle true \rangle$  or  $\langle false \rangle$ . We can also do this globally.

<code>\bool_set_eq:NN</code>
<code>\bool_set_eq:Nc</code>
<code>\bool_set_eq:cN</code>
<code>\bool_set_eq:cc</code>
<code>\bool_gset_eq:NN</code>
<code>\bool_gset_eq:Nc</code>
<code>\bool_gset_eq:cN</code>
<code>\bool_gset_eq:cc</code>

`\bool_set_eq:NN <bool1> <bool2>`

Set  $\langle bool_1 \rangle$  equal to the value of  $\langle bool_2 \rangle$ .

<code>\bool_if_p:N *</code>
<code>\bool_if:NTF *</code>
<code>\bool_if_p:c *</code>
<code>\bool_if:cTF *</code>

`\bool_if:NNTF <bool> {<true>} {<false>}`  
`\bool_if_p:N <bool>`

Test the truth value of  $\langle bool \rangle$  and execute the  $\langle true \rangle$  or  $\langle false \rangle$  code. `\bool_if_p:N` is a predicate function for use in `\if_predicate:w` tests or `\bool_if:nTF`-type functions described below.

<code>\bool_while_do:Nn</code>
<code>\bool_while_do:cn</code>
<code>\bool_until_do:Nn</code>
<code>\bool_until_do:cn</code>
<code>\bool_do_while:Nn</code>
<code>\bool_do_while:cn</code>
<code>\bool_do_until:Nn</code>
<code>\bool_do_until:cn</code>

`\bool_while_do:Nn <bool> {<code>}`  
`\bool_until_do:Nn <bool> {<code>}`

The ‘while’ versions execute  $\langle code \rangle$  as long as the boolean is true and the ‘until’ versions execute  $\langle code \rangle$  as long as the boolean is false. The `while_do` functions execute the body after testing the boolean and the `do_while` functions executes the body first and then tests the boolean.

## 24 Boolean expressions

As we have a boolean datatype and predicate functions returning boolean  $\langle true \rangle$  or  $\langle false \rangle$  values, it seems only fitting that we also provide a parser for  $\langle boolean\ expressions \rangle$ .

A boolean expression is an expression which given input in the form of predicate functions and boolean variables, return boolean  $\langle true \rangle$  or  $\langle false \rangle$ . It supports the logical operations And, Or and Not as the well-known infix operators  $\&\&$ ,  $||$  and  $!$ . In addition to this, parentheses can be used to isolate sub-expressions. For example,

```
\intexpr_compare_p:n {1=1} &&
(
  \intexpr_compare_p:n {2=3} ||
  \intexpr_compare_p:n {4=4} ||
  \intexpr_compare_p:n {1=\error} % is skipped
) &&
!(\intexpr_compare_p:n {2=4})
```

is a valid boolean expression. Note that minimal evaluation is carried out whenever possible so that whenever a truth value cannot be changed anymore, the remaining tests within the current group are skipped.

$\backslash\text{bool\_if\_p:n} \star$ $\backslash\text{bool\_if:nTF} \star$	$\backslash\text{bool\_if:nTF} \{ \langle boolean\ expression \rangle \} \{ \langle true \rangle \}$ $\{ \langle false \rangle \}$
---	---

The functions evaluate the truth value of  $\langle boolean\ expression \rangle$  where each predicate is separated by  $\&\&$  or  $||$  denoting logical ‘And’ and ‘Or’ functions. ( and ) denote grouping of sub-expressions while  $!$  is used to as a prefix to either negate a single expression or a group. Hence

```
\bool_if_p:n{
  \intexpr_compare_p:n {1=1} &&
  (
    \intexpr_compare_p:n {2=3} ||
    \intexpr_compare_p:n {4=4} ||
    \intexpr_compare_p:n {1=\error} % is skipped
  ) &&
  !(\intexpr_compare_p:n {2=4})
}
```

from above returns  $\langle true \rangle$ .

Logical operators take higher precedence the later in the predicate they appear. “ $\langle x \rangle || \langle y \rangle \&\& \langle z \rangle$ ” is interpreted as the equivalent of “ $\langle x \rangle$  OR [  $\langle y \rangle$  AND  $\langle z \rangle$  ]” (but now we have grouping you shouldn’t write this sort of thing, anyway).

`\bool_not_p:n *` `\bool_not_p:n {<boolean expression>}`

Longhand for writing `!(<boolean expression>)` within a boolean expression. Might not stick around.

`\bool_xor_p:nn *` `\bool_xor_p:nn {<boolean expression>} {<boolean expression>}`

Implements an ‘exclusive or’ operation between two boolean expressions. There is no infix operation for this.

`\bool_set:Nn`  
`\bool_set:cn`  
`\bool_gset:Nn`  
`\bool_gset:cn` `\bool_set:Nn <bool> {<boolean expression>}`

Sets `<bool>` to the logical outcome of evaluating `<boolean expression>`.

## 25 Case switches

`\prg_case_int:nnn {<integer expr>} {`  
`{<integer expr1>} {<code1>}`  
`{<integer expr2>} {<code2>}`  
`...`  
`{<integer exprn>} {<coden>}`  
`\prg_case_int:nnn *} {<else case>}`

This function evaluates the first `<integer expr>` and then compares it to the values found in the list. Thus the expression

```
\prg_case_int:nnn{2*5}{
  {5}{Small} {4+6}{Medium} {-2*10}{Negative}
}{Other}
```

evaluates first the term to look for and then tries to find this value in the list of values. If the value is found, the code on its right is executed after removing the remainder of the list. If the value is not found, the `<else case>` is executed. The example above will return “Medium”.

The function is expandable and is written in such a way that `f` style expansion can take place cleanly, i.e., no tokens from within the function are left over.

`\prg_case_int:nnn {<dim expr>} {`  
`{<dim expr1>} {<code1>}`  
`{<dim expr2>} {<code2>}`  
`...`  
`{<dim exprn>} {<coden>}`  
`\prg_case_dim:nnn *} {<else case>}`

This function works just like `\prg_case_int:nnn` except it works for `<dim>` registers.

```

\prg_case_str:nnn {\string} {
  {\string_1} {\code_1}
  {\string_2} {\code_2}
  ...
  {\string_n} {\code_n}
\prg_case_str:nnn * } {\else case}

```

This function works just like `\prg_case_int:nnn` except it compares strings. Each string is evaluated fully using `x` style expansion.

The function is expandable<sup>3</sup> and is written in such a way that `f` style expansion can take place cleanly, i.e., no tokens from within the function are left over.

```

\prg_case_tl:Nnn <tl var.> {
  <tl var._1> {\code_1} <tl var._2> {\code_2} ... <tl var._n>
  {\code_n}
\prg_case_tl:Nnn * } {\else case}

```

This function works just like `\prg_case_int:nnn` except it compares token list variables.

The function is expandable<sup>4</sup> and is written in such a way that `f` style expansion can take place cleanly, i.e., no tokens from within the function are left over.

## 26 Generic loops

```

\bool_while_do:nn
\bool_until_do:nn
\bool_do_while:nn
\bool_do_until:nn
\bool_while_do:nn {\boolean expression} {\code}
\bool_until_do:nn {\boolean expression} {\code}

```

The ‘while’ versions execute the code as long as `\boolean expression` is true and the ‘until’ versions execute `\code` as long as `\boolean expression` is false. The `\while_do` functions execute the body after testing the boolean and the `\do_while` functions executes the body first and then tests the boolean.

## 27 Choosing modes

```

\mode_if_vertical_p: *
\mode_if_vertical:TF * \mode_if_vertical:TF {\true code} {\false code}

```

Determines if `TEX` is in vertical mode or not and executes either `\true code` or `\false code` accordingly.

<sup>3</sup>Provided you use pdfTeX v1.30 or later

<sup>4</sup>Provided you use pdfTeX v1.30 or later

<code>\mode_if_horizontal_p: *</code> <code>\mode_if_horizontal:TF *</code>	<code>\mode_if_horizontal:TF {⟨true code⟩} {⟨false code⟩}</code>
--	--

Determines if T<sub>E</sub>X is in horizontal mode or not and executes either *⟨true code⟩* or *⟨false code⟩* accordingly.

<code>\mode_if_inner_p: *</code> <code>\mode_if_inner:TF *</code>	<code>\mode_if_inner:TF {⟨true code⟩} {⟨false code⟩}</code>
--	---

Determines if T<sub>E</sub>X is in inner mode or not and executes either *⟨true code⟩* or *⟨false code⟩* accordingly.

<code>\mode_if_math_p: *</code> <code>\mode_if_math:TF *</code>	<code>\mode_if_math:TF {⟨true code⟩} {⟨false code⟩}</code>
--	--

Determines if T<sub>E</sub>X is in math mode or not and executes either *⟨true code⟩* or *⟨false code⟩* accordingly.

**T<sub>E</sub>Xhackers note:** This version will choose the right branch even at the beginning of an alignment cell.

## 28 Alignment safe grouping and scanning

<code>\scan_align_safe_stop:</code>	<code>\scan_align_safe_stop:</code>
-------------------------------------	-------------------------------------

This function gets T<sub>E</sub>X on the right track inside an alignment cell but without destroying any kerning.

<code>\group_align_safe_begin:</code> <code>\group_align_safe_end:</code>	<code>\group_align_safe_begin: ⟨...⟩ \group_align_safe_end:</code>
--	--

Encloses *⟨...⟩* inside a group but is safe inside an alignment cell. See the implementation of `\peek_token_generic:NNTF` for an application.

## 29 Producing *n* copies

There are often several different requirements for producing multiple copies of something. Sometimes one might want to produce a number of identical copies of a sequence of tokens whereas at other times the goal is to simulate a for loop as known from most real programming languages.

<code>\prg_replicate:nn *</code>
----------------------------------

`\prg_replicate:nn {<number>} {<arg>}`  
 Creates <number> copies of <arg>. Note that it is expandable.

<code>\prg_stepwise_function:nnnN *</code>
--

`\prg_stepwise_function:nnnN {<start>} {<step>} {<end>} {<function>}`

This function performs <action> once for each step starting at <start> and ending once <end> is passed. <function> is placed directly in front of a brace group holding the current number so it should usually be a function taking one argument.

<code>\prg_stepwise_inline:nnnn</code>
--

`\prg_stepwise_inline:nnnn {<start>} {<step>} {<end>} {<action>}`

Same as `\prg_stepwise_function:nnnN` except here <action> is performed each time with `##1` as a placeholder for the number currently being tested. This function is not expandable and it is nestable.

<code>\prg_stepwise_variable:nnnNn</code>
---

`\prg_stepwise_variable:nnnn {<start>} {<step>} {<end>} {<temp-var>} {<action>}`

Same as `\prg_stepwise_inline:nnnn` except here the current value is stored in <temp-var> and the programmer can use it in <action>. This function is not expandable.

## 30 Sorting

<code>\prg_quicksort:n</code>
-------------------------------

`\prg_quicksort:n { {<item1>} {<item2>} ... {<itemn>} }`  
 Performs a Quicksort on the token list. The comparisons are performed by the function `\prg_quicksort_compare:nnTF` which is up to the programmer to define. When the sorting process is over, all items are given as argument to the function `\prg_quicksort_function:n` which the programmer also controls.

<code>\prg_quicksort_function:n</code> <code>\prg_quicksort_compare:nnTF</code>
--

`\prg_quicksort_function:n {<element>}`  
`\prg_quicksort_compare:nnTF {<element1>} {<element2>}`

The two functions the programmer must define before calling `\prg_quicksort:n`. As an example we could define

```
\cs_set_nopar:Npn\prg_quicksort_function:n #1{{#1}}
\cs_set_nopar:Npn\prg_quicksort_compare:nnTF #1#2#3#4 {\intexpr_compare:nNnTF{#1}>{#2}}
```

Then the function call

```
\prg_quicksort:n {876234520}
```

would return {0}{2}{2}{3}{4}{5}{6}{7}{8}. An alternative example where one sorts a list of words, `\prg_quicksort_compare:nnTF` could be defined as

```
\cs_set_nopar:Npn\prg_quicksort_compare:nnTF #1#2 {
  \intexpr_compare:nNnTF{\tl_compare:nn{#1}{#2}}>\c_zero }
```

### 30.1 Variable type and scope

```
\prg_variable_get_scope:N * \prg_variable_get_scope:N <variable>
```

Returns the scope (g for global, blank otherwise) for the *<variable>*.

```
\prg_variable_get_type:N * \prg_variable_get_type:N <variable>
```

Returns the type of *<variable>* (tl, int, etc.)

## Part VI

# The l3quark package

## “Quarks”

A special type of constants in L<sup>A</sup>T<sub>E</sub>X3 are ‘quarks’. These are control sequences that expand to themselves and should therefore NEVER be executed directly in the code. This would result in an endless loop!

They are meant to be used as delimiter is weird functions (for example as the stop token (i.e., `\q_stop`). They also permit the following ingenious trick: when you pick up a token in a temporary, and you want to know whether you have picked up a particular quark, all you have to do is compare the temporary to the quark using `\if_meaning:w`. A set of special quark testing functions is set up below. All the quark testing functions are expandable although the ones testing only single tokens are much faster.

By convention all constants of type quark start out with `\q_`.

The documentation needs some updating.

## 31 Functions

<code>\quark_new:N</code>
---------------------------

`\quark_new:N <quark>`

Defines `<quark>` to be a new constant of type `quark`.

<code>\quark_if_no_value_p:n *</code>	<code>\quark_if_no_value:nTF {&lt;token list&gt;} {&lt;true code&gt;} {&lt;&gt;false code&gt;}</code> <code>\quark_if_no_value_p:N *</code> <code>\quark_if_no_value:NTF *</code>
<code>\quark_if_no_value:nTF *</code>	
<code>\quark_if_no_value_p:N *</code>	
<code>\quark_if_no_value:NTF *</code>	

`\quark_if_no_value:NTF <tl var.> {<true code>} {<>false code>}`

This tests whether or not `<token list>` contains only the quark `\q_no_value`.

If `<token list>` to be tested is stored in a token list variable use `\quark_if_no_value:NTF`, or `\quark_if_no_value:NF` or check the value directly with `\if_meaning:w`. All those cases are faster than `\quark_if_no_value:nTF` so should be preferred.<sup>5</sup>

**TeXhackers note:** But be aware of the fact that `\if_meaning:w` can result in an overflow of TeX's parameter stack since it leaves the corresponding `\fi:` on the input until the whole replacement text is processed. It is therefore better in recursions to use `\quark_if_no_value:NTF` as it will remove the conditional prior to processing the T or F case and so allows tail-recursion.

<code>\quark_if_nil_p:N *</code>	<code>\quark_if_nil:NTF &lt;token&gt; {&lt;true code&gt;} {&lt;&gt;false code&gt;}</code>
<code>\quark_if_nil:NTF *</code>	

This tests whether or not `<token>` is equal to the quark `\q_nil`.

This is a useful test for recursive loops which typically has `\q_nil` as an end marker.

<code>\quark_if_nil_p:n *</code>	<code>\quark_if_nil:NTF {&lt;tokens&gt;} {&lt;true code&gt;} {&lt;&gt;false code&gt;}</code>
<code>\quark_if_nil_p:V *</code>	
<code>\quark_if_nil_p:o *</code>	
<code>\quark_if_nil:nTF *</code>	
<code>\quark_if_nil:VTF *</code>	
<code>\quark_if_nil:oTF *</code>	

This tests whether or not `<tokens>` is equal to the quark `\q_nil`.

This is a useful test for recursive loops which typically has `\q_nil` as an end marker.

---

<sup>5</sup>Clarify semantic of the “n” case ... i think it is not implement according to what we originally intended /FMi



## 32 Recursion

This module provides a uniform interface to intercepting and terminating loops as when one is doing tail recursion. The building blocks follow below.

`\q_recursion_tail` This quark is appended to the data structure in question and appears as a real element there. This means it gets any list separators around it.

`\q_recursion_stop` This quark is added *after* the data structure. Its purpose is to make it possible to terminate the recursion at any point easily.

<code>\quark_if_recursion_tail_stop:N *</code> <code>\quark_if_recursion_tail_stop:n *</code> <code>\quark_if_recursion_tail_stop:o *</code>	<code>\quark_if_recursion_tail_stop:n {⟨list element⟩}</code> <code>\quark_if_recursion_tail_stop:N ⟨list element⟩</code>
--	--

This tests whether or not  $\langle list\ element \rangle$  is equal to `\q_recursion_tail` and then exits, i.e., it gobbles the remainder of the list up to and including `\q_recursion_stop` which *must* be present.

If  $\langle list\ element \rangle$  is not under your complete control it is advisable to use the `n`. If you wish to use the `N` form you *must* ensure it is really a single token such as if you have

`\tl_set:Nn \l_tmpa_tl { ⟨list element⟩ }`

<code>\quark_if_recursion_tail_stop_do:Nn *</code> <code>\quark_if_recursion_tail_stop_do:nn *</code> <code>\quark_if_recursion_tail_stop_do:on *</code>	<code>\quark_if_recursion_tail_stop_do:nn {⟨list element⟩} {⟨post action⟩}</code> <code>\quark_if_recursion_tail_stop_do:Nn ⟨list element⟩ {⟨post action⟩}</code>
--	--

Same as `\quark_if_recursion_tail_stop:N` except here the second argument is executed after the recursion has been terminated.

## 33 Constants

`\q_no_value` The canonical ‘missing value quark’ that is returned by certain functions to denote that a requested value is not found in the data structure.

`\q_stop` This constant is used as a a marker in parameter text. This allows a scanning function to find the end of some input string.

`\q_nil` This constant represent the nil pointer in pointer structures.

`\q_error` Delimits the end of the computation for purposes of error recovery.

`\q_mark` Used in parameter text when we need a scanning boundary that is distinct from `\q_stop`.

## Part VII

# The l3token package

## A token of my appreciation...

This module deals with tokens. Now this is perhaps not the most precise description so let's try with a better description: When programming in T<sub>E</sub>X, it is often desirable to know just what a certain token is: is it a control sequence or something else. Similarly one often needs to know if a control sequence is expandable or not, a macro or a primitive, how many arguments it takes etc. Another thing of great importance (especially when it comes to document commands) is looking ahead in the token stream to see if a certain character is present and maybe even remove it or disregard other tokens while scanning. This module provides functions for both and as such will have two primary function categories: `\token` for anything that deals with tokens and `\peek` for looking ahead in the token stream.

Most of the time we will be using the term 'token' but most of the time the function we're describing can equally well be used on a control sequence as such one is one token as well.

We shall refer to list of tokens as `tlists` and such lists represented by a single control sequence is a 'token list variable' `tl var`. Functions for these two types are found in the `l3tl` module.

## 34 Character tokens

<code>\char_set_catcode:nn</code>	<code>\char_set_catcode:nn {&lt;char number&gt;} {&lt;number&gt;}</code>
<code>\char_set_catcode:w</code>	<code>\char_set_catcode:w &lt;char&gt; = &lt;number&gt;</code>
<code>\char_value_catcode:n</code>	<code>\char_value_catcode:n {&lt;char number&gt;}</code>
<code>\char_value_catcode:w</code>	<code>\char_value_catcode:w {&lt;char number&gt;}</code>
<code>\char_show_value_catcode:n</code>	<code>\char_show_value_catcode:n {&lt;char number&gt;}</code>
<code>\char_show_value_catcode:w</code>	<code>\char_show_value_catcode:w {&lt;char number&gt;}</code>

`\char_set_catcode:n` sets the category code of a character, `\char_value_catcode:n` returns its value for use in integer tests and `\char_show_value_catcode:n` pausing the typesetting and prints the value on the terminal and in the log file. The `:w` form should be avoided. (Will: should we then just not mention it?)

`\char_set_catcode` is more usefully abstracted below.

**T<sub>E</sub>Xhackers note:** `\char_set_catcode:w` is the T<sub>E</sub>X primitive `\catcode` renamed.

<code>\char_make_escape:n</code>	
<code>\char_make_begin_group:n</code>	
<code>\char_make_end_group:n</code>	
<code>\char_make_math_shift:n</code>	
<code>\char_make_alignment:n</code>	
<code>\char_make_end_line:n</code>	
<code>\char_make_parameter:n</code>	
<code>\char_make_math_superscript:n</code>	
<code>\char_make_math_subscript:n</code>	
<code>\char_make_ignore:n</code>	
<code>\char_make_space:n</code>	
<code>\char_make_letter:n</code>	
<code>\char_make_other:n</code>	
<code>\char_make_active:n</code>	
<code>\char_make_comment:n</code>	<code>\char_make_letter:n {⟨character number⟩}</code>
<code>\char_make_invalid:n</code>	<code>\char_make_letter:n {64}</code>
	<code>\char_make_letter:n {'\@}</code>

Sets the catcode of the character referred to by its *⟨character number⟩*.

<code>\char_make_escape:N</code>	
<code>\char_make_begin_group:N</code>	
<code>\char_make_end_group:N</code>	
<code>\char_make_math_shift:N</code>	
<code>\char_make_alignment:N</code>	
<code>\char_make_end_line:N</code>	
<code>\char_make_parameter:N</code>	
<code>\char_make_math_superscript:N</code>	
<code>\char_make_math_subscript:N</code>	
<code>\char_make_ignore:N</code>	
<code>\char_make_space:N</code>	
<code>\char_make_letter:N</code>	
<code>\char_make_other:N</code>	
<code>\char_make_active:N</code>	
<code>\char_make_comment:N</code>	<code>\char_make_letter:N {⟨character⟩}</code>
<code>\char_make_invalid:N</code>	<code>\char_make_letter:N @</code>
	<code>\char_make_letter:N \%</code>

Sets the catcode of the  $\langle character \rangle$ , which may have to be escaped.

**T<sub>E</sub>Xhackers note:** `\char_make_other:N` is L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub>'s `\@makeother`.

<code>\char_set_lccode:nn</code>	<code>\char_set_lccode:nn {<math>\langle char \rangle</math>} {<math>\langle number \rangle</math>}</code>
<code>\char_set_lccode:w</code>	<code>\char_set_lccode:w {<math>\langle char \rangle</math>} = {<math>\langle number \rangle</math>}</code>
<code>\char_value_lccode:n</code>	<code>\char_value_lccode:n {<math>\langle char \rangle</math>}</code>
<code>\char_value_lccode:w</code>	<code>\char_value_lccode:w {<math>\langle char \rangle</math>}</code>
<code>\char_show_value_lccode:n</code>	<code>\char_show_value_lccode:n {<math>\langle char \rangle</math>}</code>
<code>\char_show_value_lccode:w</code>	<code>\char_show_value_lccode:w {<math>\langle char \rangle</math>}</code>

Set the lower case representation of  $\langle char \rangle$  for when  $\langle char \rangle$  is being converted in `\tl_to_lowercase:n`. As above, the `:w` form is only for people who really, really know what they are doing.

**T<sub>E</sub>Xhackers note:** `\char_set_lccode:w` is the T<sub>E</sub>X primitive `\lccode` renamed.

<code>\char_set_uccode:nn</code>	<code>\char_set_uccode:nn {<math>\langle char \rangle</math>} {<math>\langle number \rangle</math>}</code>
<code>\char_set_uccode:w</code>	<code>\char_set_uccode:w {<math>\langle char \rangle</math>} = {<math>\langle number \rangle</math>}</code>
<code>\char_value_uccode:n</code>	<code>\char_value_uccode:n {<math>\langle char \rangle</math>}</code>
<code>\char_value_uccode:w</code>	<code>\char_value_uccode:w {<math>\langle char \rangle</math>}</code>
<code>\char_show_value_uccode:n</code>	<code>\char_show_value_uccode:n {<math>\langle char \rangle</math>}</code>
<code>\char_show_value_uccode:w</code>	<code>\char_show_value_uccode:w {<math>\langle char \rangle</math>}</code>

Set the uppercase representation of  $\langle char \rangle$  for when  $\langle char \rangle$  is being converted in `\tl_to_uppercase:n`. As above, the `:w` form is only for people who really, really know what they are doing.

**T<sub>E</sub>Xhackers note:** `\char_set_uccode:w` is the T<sub>E</sub>X primitive `\uccode` renamed.

<code>\char_set_sfcode:nn</code>	<code>\char_set_sfcode:nn {<math>\langle char \rangle</math>} {<math>\langle number \rangle</math>}</code>
<code>\char_set_sfcode:w</code>	<code>\char_set_sfcode:w {<math>\langle char \rangle</math>} = {<math>\langle number \rangle</math>}</code>
<code>\char_value_sfcode:n</code>	<code>\char_value_sfcode:n {<math>\langle char \rangle</math>}</code>
<code>\char_value_sfcode:w</code>	<code>\char_value_sfcode:w {<math>\langle char \rangle</math>}</code>
<code>\char_show_value_sfcode:n</code>	<code>\char_show_value_sfcode:n {<math>\langle char \rangle</math>}</code>
<code>\char_show_value_sfcode:w</code>	<code>\char_show_value_sfcode:w {<math>\langle char \rangle</math>}</code>

Set the space factor for  $\langle char \rangle$ .

**T<sub>E</sub>Xhackers note:** `\char_set_sfcode:w` is the T<sub>E</sub>X primitive `\sfcode` renamed.

<code>\char_set_mathcode:nn</code>	
<code>\char_set_mathcode:w</code>	
<code>\char_gset_mathcode:nn</code>	
<code>\char_gset_mathcode:w</code>	
<code>\char_value_mathcode:n</code>	<code>\char_set_mathcode:nn {&lt;char&gt;} {&lt;number&gt;}</code>
<code>\char_value_mathcode:w</code>	<code>\char_set_mathcode:w &lt;char&gt; = &lt;number&gt;</code>
<code>\char_show_value_mathcode:n</code>	<code>\char_value_mathcode:n {&lt;char&gt;}</code>
<code>\char_show_value_mathcode:w</code>	<code>\char_show_value_mathcode:n {&lt;char&gt;}</code>

Set the math code for  $\langle char \rangle$ .

**TeXhackers note:** `\char_set_mathcode:w` is the TeX primitive `\mathcode` renamed.

## 35 Generic tokens

<code>\token_new:Nn</code>	<code>\token_new:Nn &lt;token<sub>1</sub>&gt; {&lt;token<sub>2</sub>&gt;}</code>
----------------------------	--

Defines  $\langle token_1 \rangle$  to globally be a snapshot of  $\langle token_2 \rangle$ . This will be an implicit representation of  $\langle token_2 \rangle$ .

<code>\c_group_begin_token</code>
<code>\c_group_end_token</code>
<code>\c_math_shift_token</code>
<code>\c_alignment_tab_token</code>
<code>\c_parameter_token</code>
<code>\c_math_superscript_token</code>
<code>\c_math_subscript_token</code>
<code>\c_space_token</code>
<code>\c_letter_token</code>
<code>\c_other_char_token</code>
<code>\c_active_char_token</code>

Some useful constants. They have category codes 1, 2, 3, 4, 6, 7, 8, 10, 11, 12, and 13 respectively. They are all implicit tokens.

<code>\token_if_group_begin_p:N *</code>	
<code>\token_if_group_begin:NTF *</code>	<code>\token_if_group_begin:NTF &lt;token&gt; {&lt;true&gt;} {&lt;false&gt;}</code>

Check if  $\langle token \rangle$  is a begin group token.

<code>\token_if_group_end_p:N *</code>	
<code>\token_if_group_end:NTF *</code>	<code>\token_if_group_end:NTF &lt;token&gt; {&lt;true&gt;} {&lt;false&gt;}</code>

Check if  $\langle token \rangle$  is an end group token.

$\backslash token\_if\_math\_shift\_p:N \star$ $\backslash token\_if\_math\_shift:N\overline{TF} \star$	$\backslash token\_if\_math\_shift:N\overline{TF} \langle token \rangle \{\langle true \rangle\} \{\langle false \rangle\}$
--	---

Check if  $\langle token \rangle$  is a math shift token.

$\backslash token\_if\_alignment\_tab\_p:N \star$ $\backslash token\_if\_alignment\_tab:N\overline{TF} \star$	$\backslash token\_if\_alignment\_tab:N\overline{TF} \langle token \rangle \{\langle true \rangle\} \{\langle false \rangle\}$
--	--

Check if  $\langle token \rangle$  is an alignment tab token.

$\backslash token\_if\_parameter\_p:N \star$ $\backslash token\_if\_parameter:N\overline{TF} \star$	$\backslash token\_if\_parameter:N\overline{TF} \langle token \rangle \{\langle true \rangle\} \{\langle false \rangle\}$
--	---

Check if  $\langle token \rangle$  is a parameter token.

$\backslash token\_if\_math\_superscript\_p:N \star$ $\backslash token\_if\_math\_superscript:N\overline{TF} \star$	$\backslash token\_if\_math\_superscript:N\overline{TF} \langle token \rangle \{\langle true \rangle\} \{\langle false \rangle\}$
--	---

Check if  $\langle token \rangle$  is a math superscript token.

$\backslash token\_if\_math\_subscript\_p:N \star$ $\backslash token\_if\_math\_subscript:N\overline{TF} \star$	$\backslash token\_if\_math\_subscript:N\overline{TF} \langle token \rangle \{\langle true \rangle\} \{\langle false \rangle\}$
--	---

Check if  $\langle token \rangle$  is a math subscript token.

$\backslash token\_if\_space\_p:N \star$ $\backslash token\_if\_space:N\overline{TF} \star$	$\backslash token\_if\_space:N\overline{TF} \langle token \rangle \{\langle true \rangle\} \{\langle false \rangle\}$
--	---

Check if  $\langle token \rangle$  is a space token.

$\backslash token\_if\_letter\_p:N \star$ $\backslash token\_if\_letter:N\overline{TF} \star$	$\backslash token\_if\_letter:N\overline{TF} \langle token \rangle \{\langle true \rangle\} \{\langle false \rangle\}$
--	--

Check if  $\langle token \rangle$  is a letter token.

$\backslash token\_if\_other\_char\_p:N \star$ $\backslash token\_if\_other\_char:N\overline{TF} \star$	$\backslash token\_if\_other\_char:N\overline{TF} \langle token \rangle \{\langle true \rangle\} \{\langle false \rangle\}$
--	---

Check if  $\langle token \rangle$  is an other char token.

<code>\token_if_active_char_p:N *</code> <code>\token_if_active_char:NTF *</code>	<code>\token_if_active_char:NTF &lt;token&gt; {\true} {\false}</code>
--	---

Check if  $\langle token \rangle$  is an active char token.

<code>\token_if_eq_meaning_p:NN *</code> <code>\token_if_eq_meaning:NNTF *</code>	<code>\token_if_eq_meaning:NNTF &lt;token<sub>1</sub>&gt; &lt;token<sub>2</sub>&gt; {\true} {\false}</code>
--	---

Check if the meaning of two tokens are identical.

<code>\token_if_eq_catcode_p:NN *</code> <code>\token_if_eq_catcode:NNTF *</code>	<code>\token_if_eq_catcode:NNTF &lt;token<sub>1</sub>&gt; &lt;token<sub>2</sub>&gt; {\true} {\false}</code>
--	---

Check if the category codes of two tokens are equal. If both tokens are control sequences the test will be true.

<code>\token_if_eq_charcode_p:NN *</code> <code>\token_if_eq_charcode:NNTF *</code>	<code>\token_if_eq_catcode:NNTF &lt;token<sub>1</sub>&gt; &lt;token<sub>2</sub>&gt; {\true} {\false}</code>
--	---

Check if the character codes of two tokens are equal. If both tokens are control sequences the test will be true.

<code>\token_if_macro_p:N *</code> <code>\token_if_macro:NTF *</code>	<code>\token_if_macro:NTF &lt;token&gt; {\true} {\false}</code>
--	---

Check if  $\langle token \rangle$  is a macro.

<code>\token_if_cs_p:N *</code> <code>\token_if_cs:NTF *</code>	<code>\token_if_cs:NTF &lt;token&gt; {\true} {\false}</code>
--	--

Check if  $\langle token \rangle$  is a control sequence or not. This can be useful for situations where the next token in the input stream is being looked at and you want to determine what should be done to it.

<code>\token_if_expandable_p:N *</code> <code>\token_if_expandable:NTF *</code>	<code>\token_if_expandable:NTF &lt;token&gt; {\true} {\false}</code>
--	--

Check if  $\langle token \rangle$  is expandable or not. Note that  $\langle token \rangle$  can very well be an active character.

The next set of functions here are for picking apart control sequences. Sometimes it is useful to know if a control sequence has arguments and if so, how many. Similarly its status with respect to `\long` or `\protected` is good to have. Finally it can be very useful

to know if a control sequence is of a certain type: Is this  $\langle toks \rangle$  register we’re trying to to something with really a  $\langle toks \rangle$  register at all?

$\backslash token\_if\_long\_macro\_p:N \star$ $\backslash token\_if\_long\_macro:N\mathit{TF} \star$	$\backslash token\_if\_long\_macro:N\mathit{TF} \langle toks \rangle \{ \langle true \rangle \} \{ \langle false \rangle \}$
--	--

Check if  $\langle toks \rangle$  is a “long” macro.

$\backslash token\_if\_protected\_macro\_p:N \star$ $\backslash token\_if\_protected\_macro:N\mathit{TF} \star$	$\backslash token\_if\_long\_macro:N\mathit{TF} \langle toks \rangle \{ \langle true \rangle \} \{ \langle false \rangle \}$
--	--

Check if  $\langle toks \rangle$  is a “protected” macro. This test does *not* return  $\langle true \rangle$  if the macro is also “long”, see below.

$\backslash token\_if\_protected\_long\_macro\_p:N \star$ $\backslash token\_if\_protected\_long\_macro:N\mathit{TF} \star$	$\backslash token\_if\_protected\_long\_macro:N\mathit{TF} \langle toks \rangle \{ \langle true \rangle \} \{ \langle false \rangle \}$
--	---

Check if  $\langle toks \rangle$  is a “protected long” macro.

$\backslash token\_if\_chardef\_p:N \star$ $\backslash token\_if\_chardef:N\mathit{TF} \star$	$\backslash token\_if\_chardef:N\mathit{TF} \langle toks \rangle \{ \langle true \rangle \} \{ \langle false \rangle \}$
--	--

Check if  $\langle toks \rangle$  is defined to be a chardef.

$\backslash token\_if\_mathchardef\_p:N \star$ $\backslash token\_if\_mathchardef:N\mathit{TF} \star$	$\backslash token\_if\_mathchardef:N\mathit{TF} \langle toks \rangle \{ \langle true \rangle \} \{ \langle false \rangle \}$
--	--

Check if  $\langle toks \rangle$  is defined to be a mathchardef.

$\backslash token\_if\_int\_register\_p:N \star$ $\backslash token\_if\_int\_register:N\mathit{TF} \star$	$\backslash token\_if\_int\_register:N\mathit{TF} \langle toks \rangle \{ \langle true \rangle \} \{ \langle false \rangle \}$
--	--

Check if  $\langle toks \rangle$  is defined to be an integer register.

$\backslash token\_if\_dim\_register\_p:N \star$ $\backslash token\_if\_dim\_register:N\mathit{TF} \star$	$\backslash token\_if\_dim\_register:N\mathit{TF} \langle toks \rangle \{ \langle true \rangle \} \{ \langle false \rangle \}$
--	--

Check if  $\langle toks \rangle$  is defined to be a dimension register.



<code>\token_if_skip_register_p:N *</code> <code>\token_if_skip_register:N<math>\underline{TF}</math> *</code>
---

`\token_if_skip_register:N $\underline{TF}$  <token> {\<true>} {\<false>}`

Check if  $\langle token \rangle$  is defined to be a skip register.

<code>\token_if_toks_register_p:N *</code> <code>\token_if_toks_register:N<math>\underline{TF}</math> *</code>
---

`\token_if_toks_register:N $\underline{TF}$  <token> {\<true>} {\<false>}`

Check if  $\langle token \rangle$  is defined to be a toks register.

<code>\token_get_prefix_spec:N *</code> <code>\token_get_arg_spec:N *</code> <code>\token_get_replacement_spec:N *</code>
---

`\token_get_arg_spec:N <token>`

If token is a macro with definition `\cs_set:Npn\next #1#2{x'#1--#2'y}`, the `prefix` function will return the string `\long`, the `arg` function returns the string `#1#2` and the `replacement` function returns the string `x'#1--#2'y`. If  $\langle token \rangle$  isn't a macro, these functions return the `\scan_stop:` token.

If the `arg_spec` contains the string `->`, then the `spec` function will produce incorrect results.

### 35.1 Useless code: because we can!

<code>\token_if_primitive_p:N *</code> <code>\token_if_primitive:N<math>\underline{TF}</math> *</code>
---

`\token_if_primitive:N $\underline{TF}$  <token> {\<true>} {\<false>}`

Check if  $\langle token \rangle$  is a primitive. Probably not a very useful function.

## 36 Peeking ahead at the next token

<code>\l_peek_token</code> <code>\g_peek_token</code> <code>\l_peek_search_token</code>
---

Some useful variables. Initially they are set to ?.

<code>\peek_after:NN</code> <code>\peek_gafter:NN</code>
---

`\peek_after:NN <function><token>`

Assign  $\langle token \rangle$  to `\l_peek_token` and then run  $\langle function \rangle$  which should perform some

sort of test on this token. Leaves  $\langle token \rangle$  in the input stream.  $\backslash peek\_gafter:NN$  does this globally to the token  $\backslash g\_peek\_token$ .

**T<sub>E</sub>Xhackers note:** This is the primitive  $\backslash futurelet$  turned into a function.

$\backslash peek\_meaning:N\overline{T}\overline{F}$ $\backslash peek\_meaning\_ignore\_spaces:N\overline{T}\overline{F}$ $\backslash peek\_meaning\_remove:N\overline{T}\overline{F}$ $\backslash peek\_meaning\_remove\_ignore\_spaces:N\overline{T}\overline{F}$	$\backslash peek\_meaning:N\overline{T}\overline{F} \langle token \rangle \{ \langle true \rangle \} \{ \langle false \rangle \}$
--	---

$\backslash peek\_meaning:N\overline{T}\overline{F}$  checks (by using  $\backslash if\_meaning:w$ ) if  $\langle token \rangle$  equals the next token in the input stream and executes either  $\langle true\ code \rangle$  or  $\langle false\ code \rangle$  accordingly.  $\backslash peek\_meaning\_remove:N\overline{T}\overline{F}$  does the same but additionally removes the token if found. The  $ignore\_spaces$  versions skips blank spaces before making the decision.

**T<sub>E</sub>Xhackers note:** This is equivalent to L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub>'s  $\backslash @ifnextchar$ .

$\backslash peek\_charcode:N\overline{T}\overline{F}$ $\backslash peek\_charcode\_ignore\_spaces:N\overline{T}\overline{F}$ $\backslash peek\_charcode\_remove:N\overline{T}\overline{F}$ $\backslash peek\_charcode\_remove\_ignore\_spaces:N\overline{T}\overline{F}$	$\backslash peek\_charcode:N\overline{T}\overline{F} \langle token \rangle \{ \langle true \rangle \} \{ \langle false \rangle \}$
--	--

Same as for the  $\backslash peek\_meaning:N\overline{T}\overline{F}$  functions above but these use  $\backslash if\_charcode:w$  to compare the tokens.

$\backslash peek\_catcode:N\overline{T}\overline{F}$ $\backslash peek\_catcode\_ignore\_spaces:N\overline{T}\overline{F}$ $\backslash peek\_catcode\_remove:N\overline{T}\overline{F}$ $\backslash peek\_catcode\_remove\_ignore\_spaces:N\overline{T}\overline{F}$	$\backslash peek\_catcode:N\overline{T}\overline{F} \langle token \rangle \{ \langle true \rangle \} \{ \langle false \rangle \}$
--	---

Same as for the  $\backslash peek\_meaning:N\overline{T}\overline{F}$  functions above but these use  $\backslash if\_catcode:w$  to compare the tokens.

$\backslash peek\_token\_generic:NN\overline{T}\overline{F}$ $\backslash peek\_token\_remove\_generic:NN\overline{T}\overline{F}$	$\backslash peek\_token\_generic:NN\overline{T}\overline{F} \langle token \rangle \langle function \rangle \{ \langle true \rangle \} \{ \langle false \rangle \}$
--	--

$\backslash peek\_token\_generic:NN\overline{T}\overline{F}$  looks ahead and checks if the next token in the input stream is equal to  $\langle token \rangle$ . It uses  $\langle function \rangle$  to make that decision.  $\backslash peek\_token\_remove\_generic:NN\overline{T}\overline{F}$  does the same thing but additionally removes  $\langle token \rangle$  from the input stream if it is found. This also works if  $\langle token \rangle$  is either  $\backslash c\_group\_begin\_token$  or  $\backslash c\_group\_end\_token$ .

<code>\peek_execute_branches_meaning:</code> <code>\peek_execute_branches_charcode:</code> <code>\peek_execute_branches_catcode:</code>	<code>\peek_execute_branches_meaning:</code>
---	--

These functions compare the token we are searching for with the token found (after optional ignoring of specific tokens). They come in the usual three versions when  $\text{\TeX}$  is comparing tokens: meaning, character code, and category code.

## Part VIII

# The `l3int` package

## Integers/counters

$\text{\LaTeX}3$  maintains two type of integer registers for internal use. One (associated with the name `num`) for low level uses in the allocation mechanism using macros only and `int`: the one described here.

The `int` type uses the built-in counter registers of  $\text{\TeX}$  and is therefore relatively fast compared to the `num` type and should be preferred in all cases as there is little chance we should ever run out of registers when being based on at least  $\varepsilon\text{-}\text{\TeX}$ .

## 37 Functions

<code>\int_new:N</code> <code>\int_new:c</code>	<code>\int_new:N</code> $\langle int \rangle$
--	---

Globally defines  $\langle int \rangle$  to be a new variable of type `int` although you can still choose if it should be a an `\l_` or `\g_` type. There is no way to define constant counters with these functions.

**$\text{\TeX}$ hackers note:** `\int_new:N` is the equivalent to plain  $\text{\TeX}$ 's `\newcount`. However, the internal register allocation is done differently.

<code>\int_incr:N</code> <code>\int_incr:c</code> <code>\int_gincr:N</code> <code>\int_gincr:c</code>	<code>\int_incr:N</code> $\langle int \rangle$
--	--

Increments  $\langle int \rangle$  by one. For global variables the global versions should be used.

<code>\int_decr:N</code>
<code>\int_decr:c</code>
<code>\int_gdecr:N</code>
<code>\int_gdecr:c</code>

`\int_decr:N    <int>`

Decrements  $\langle int \rangle$  by one. For global variables the global versions should be used.

<code>\int_set:Nn</code>
<code>\int_set:cn</code>
<code>\int_gset:Nn</code>
<code>\int_gset:cn</code>

`\int_set:Nn    <int> {<integer expr>}`

These functions will set the  $\langle int \rangle$  register to the  $\langle integer\ expr \rangle$  value. This value can contain simple calc-like expressions as provided by  $\varepsilon$ -TeX.

<code>\int_zero:N</code>
<code>\int_zero:c</code>
<code>\int_gzero:N</code>
<code>\int_gzero:c</code>

`\int_zero:N    <int>`

These functions sets the  $\langle int \rangle$  register to zero either locally or globally.

<code>\int_add:Nn</code>
<code>\int_add:cn</code>
<code>\int_gadd:Nn</code>
<code>\int_gadd:cn</code>

`\int_add:Nn    <int> {<integer expr>}`

These functions will add to the  $\langle int \rangle$  register the value  $\langle integer\ expr \rangle$ . If the second argument is a  $\langle int \rangle$  register too, the surrounding braces can be left out.

<code>\int_sub:Nn</code>
<code>\int_sub:cn</code>
<code>\int_gsub:Nn</code>
<code>\int_gsub:cn</code>

`\int_gsub:Nn    <int> {<integer expr>}`

These functions will subtract from the  $\langle int \rangle$  register the value  $\langle integer\ expr \rangle$ . If the second argument is a  $\langle int \rangle$  register too, the surrounding braces can be left out.

<code>\int_use:N</code>
<code>\int_use:c</code>

`\int_use:N    <int>`

This function returns the integer value kept in  $\langle int \rangle$  in a way suitable for further processing.

**TeXhackers note:** The function `\int_use:N` could be implemented directly as the TeX primitive `\tex_the:D` which is also responsible to produce the values for other internal quantities. We have chosen to use individual functions for counters, dimensions etc. to allow checks and to make the code more self-explaining.

<code>\int_show:N</code> <code>\int_show:c</code>	<code>\int_show:N &lt;int&gt;</code>
--	--------------------------------------

This function pauses the compilation and displays the integer value kept in `<int>` in the console output and log file.

**T<sub>E</sub>Xhackers note:** The function `\int_show:N` could be implemented directly as the T<sub>E</sub>X primitive `\tex_showthe:D` which is also responsible to produce the values for other internal quantities. We have chosen to use individual functions for counters, dimensions etc. to allow checks and to make the code more self-explaining.

## 38 Formatting a counter value

<code>\int_to_arabic:n *</code> <code>\int_to_alph:n *</code> <code>\int_to_Alph:n *</code> <code>\int_to_roman:n *</code> <code>\int_to_Roman:n *</code> <code>\int_to_symbol:n *</code>	<code>\int_to_alph:n {&lt;integer&gt;}</code> <code>\int_to_alph:n &lt;int&gt;</code>
--	--

If some `<integer>` or the the current value of a `<int>` should be displayed or typeset in a special ways (e.g., as uppercase roman numerals) these function can be used. We need braces if the argument is a simple `<integer>`, they can be omitted in case of a `<int>`. By default the letters produced by `\int_to_roman:n` and `\int_to_Roman:n` have catcode 11.

All functions are fully expandable and will therefore produce the correct output when used inside of deferred writes, etc. In case the number in an `alph` or `Alph` function is greater than the default base number (26) it follows a simple conversion rule so that 27 is turned into `aa`, 50 into `ax` and so on and so forth. These two functions can be modified quite easily to take a different base number and conversion rule so that other languages can be supported.

**T<sub>E</sub>Xhackers note:** These are more or less the internal L<sup>A</sup>T<sub>E</sub>X2 functions `\@arabic`, `\@alph`, `\@Alph`, `\@roman`, `\@Roman`, and `\@fnsymbol` except that `\int_to_symbol:n` is also allowed outside math mode.

### 38.1 Internal functions

<code>\int_to_roman:w *</code>	<code>\int_to_roman:w &lt;integer&gt; &lt;space&gt; or &lt;non-expandable token&gt;</code>
--------------------------------	--

Converts `<integer>` to it lowercase roman representation. Note that it produces a string of letters with catcode 12.

**T<sub>E</sub>Xhackers note:** This is the T<sub>E</sub>X primitive `\romannumeral` renamed.

<code>\int_to_number:w *</code>	<code>\int_to_number:w &lt;integer&gt; &lt;space&gt;</code>
---------------------------------	---

Converts *<integer>* to its numerical string. Note that it produces a string of letters with catcode 12.

**T<sub>E</sub>Xhackers note:** This is the T<sub>E</sub>X primitive `\number` renamed.

<code>\int_roman_lcuc_mapping:Nnn</code>	<code>\int_roman_lcuc_mapping:Nnn &lt;roman_char&gt; {\&lt;licr&gt;}</code>
<code>\int_to_roman_lcuc:NN</code>	<code>\int_to_roman_lcuc:NN {\&lt;LICR&gt;}</code>

`\int_roman_lcuc_mapping:Nnn` specifies how the roman numeral *<roman\_char>* (i, v, x, l, c, d, or m) should be interpreted when converting the number. *<licr>* is the lower case and *<LICR>* is the uppercase mapping. `\int_to_roman_lcuc:NN` is a recursive function converting the roman numerals.

<code>\int_convert_number_with_rule:nnN</code>	<code>\int_convert_number_with_rule:nnN {\&lt;int<sub>1</sub>&gt;} {\&lt;int<sub>2</sub>&gt;}</code> <code>&lt;function&gt;</code> <code>\int_alph_default_conversion_rule:n {\&lt;int&gt;}</code>
<code>\int_alph_default_conversion_rule:n</code>	
<code>\int_Alph_default_conversion_rule:n</code>	
<code>\int_symbol_math_conversion_rule:n</code>	
<code>\int_symbol_text_conversion_rule:n</code>	

`\int_convert_number_with_rule:nnN` converts *<int<sub>1</sub>>* into letters, symbols, whatever as defined by *<function>*. *<int<sub>2</sub>>* denotes the base number for the conversion.

## 39 Variable and constants

<code>\int_const:Nn</code>	<code>\int_const:Nn \c_&lt;value&gt; {\&lt;value&gt;}</code>
----------------------------	--

Defines an integer constant of a certain *<value>*. If the constant is negative or very large it internally uses an *<int>* register.

```

\c_minus_one
\c_zero
\c_one
\c_two
\c_three
\c_four
\c_five
\c_six
\c_seven
\c_eight
\c_nine
\c_ten
\c_eleven
\c_twelve
\c_thirteen
\c_fourteen
\c_fifteen
\c_sixteen
\c_thirty_two
\c_hundred_one
\c_twohundred_fifty_five
\c_twohundred_fifty_six
\c_thousand
\c_ten_thousand
\c_ten_thousand_one
\c_ten_thousand_two
\c_ten_thousand_three
\c_ten_thousand_four
\c_twenty_thousand

```

Set of constants denoting useful values.

**T<sub>E</sub>Xhackers note:** Some of these constants have been available under L<sup>A</sup>T<sub>E</sub>X2 under names like `\m@ne`, `\z@`, `\@ne`, `\tw@`, `\thr@@`, etc.

```
\c_max_int
```

Constant that denote the maximum value which can be stored in an *int* register.

```

\l_tmpa_int
\l_tmpb_int
\l_tmpc_int
\g_tmpa_int
\g_tmpb_int

```

Scratch register for immediate use. They are not used by conditionals or predicate functions.

## 40 Conversion

<code>\int_convert_from_base_ten:nn</code>
--

`\int_convert_from_base_ten:nn {<number>} {<base>}`

Converts the base 10 number  $\langle number \rangle$  into its equivalent representation written in base  $\langle base \rangle$ . Expandable.

<code>\int_convert_to_base_ten:nn</code>
--

`\int_convert_to_base_ten:nn {<number>} {<base>}`

Converts the base  $\langle base \rangle$  number  $\langle number \rangle$  into its equivalent representation written in base 10.  $\langle number \rangle$  can consist of digits and ascii letters. Expandable.

## Part IX

# The l3num package

## Integers in macros

Instead of using counter registers for manipulation of integer values it is sometimes useful to keep such values in macros. For this L<sup>A</sup>T<sub>E</sub>X3 offers the type “num”.

One reason is the limited number of registers inside T<sub>E</sub>X. However, when using  $\varepsilon$ -T<sub>E</sub>X this is no longer an issue. It remains to be seen if there are other compelling reasons to keep this module.

It turns out there might be as with a  $\langle num \rangle$  data type, the allocation module can do its bookkeeping without the aid of  $\langle int \rangle$  registers.

## 41 Functions

<code>\num_new:N</code>
<code>\num_new:c</code>

`\num_new:N     <num>`

Defines  $\langle num \rangle$  to be a new variable of type num (initialized to zero). There is no way to define constant counters with these functions.

<code>\num_incr:N</code>
<code>\num_incr:c</code>
<code>\num_gincr:N</code>
<code>\num_gincr:c</code>

`\num_incr:N     <num>`

Increments  $\langle num \rangle$  by one. For global variables the global versions should be used.



<code>\num_decr:N</code>
<code>\num_decr:c</code>
<code>\num_gdecr:N</code>
<code>\num_gdecr:c</code>

`\num_decr:N     $\langle num \rangle$`

Decrements  $\langle num \rangle$  by one. For global variables the global versions should be used.

<code>\num_zero:N</code>
<code>\num_zero:c</code>
<code>\num_gzero:N</code>
<code>\num_gzero:c</code>

`\num_zero:N     $\langle num \rangle$`

Resets  $\langle num \rangle$  to zero. For global variables the global versions should be used.

<code>\num_set:Nn</code>
<code>\num_set:cn</code>
<code>\num_gset:Nn</code>
<code>\num_gset:cn</code>

`\num_set:Nn     $\langle num \rangle$   $\{ \langle integer \rangle \}$`

These functions will set the  $\langle num \rangle$  register to the  $\langle integer \rangle$  value.

<code>\num_set_eq:NN</code>
<code>\num_set_eq:cN</code>
<code>\num_set_eq:Nc</code>
<code>\num_set_eq:cc</code>

`\num_gset_eq:NN     $\langle num_1 \rangle$   $\langle num_2 \rangle$`

These functions will set the  $\langle num_1 \rangle$  register equal to  $\langle num_2 \rangle$ .

<code>\num_gset_eq:NN</code>
<code>\num_gset_eq:cN</code>
<code>\num_gset_eq:Nc</code>
<code>\num_gset_eq:cc</code>

`\num_gset_eq:NN     $\langle num_1 \rangle$   $\langle num_2 \rangle$`

These functions will globally set the  $\langle num_1 \rangle$  register equal to  $\langle num_2 \rangle$ .

<code>\num_add:Nn</code>
<code>\num_add:cn</code>
<code>\num_gadd:Nn</code>
<code>\num_gadd:cn</code>

`\num_add:Nn     $\langle num \rangle$   $\{ \langle integer \rangle \}$`

These functions will add to the  $\langle num \rangle$  register the value  $\langle integer \rangle$ . If the second argument is a  $\langle num \rangle$  register too, the surrounding braces can be left out.

<code>\num_use:N</code>
<code>\num_use:c</code>

`\num_use:N     $\langle num \rangle$`

This function returns the integer value kept in  $\langle num \rangle$  in a way suitable for further processing.

**T<sub>E</sub>Xhackers note:** Since these  $\langle num \rangle$ s are implemented as macros, the function `\num_use:N` is effectively a noop and mainly there for consistency with similar functions in other modules.

<code>\num_show:N</code>	<code>\num_show:N <math>\langle num \rangle</math></code>
<code>\num_show:c</code>	

This function pauses the compilation and displays the integer value kept in  $\langle num \rangle$  on the console output.

<code>\num_elt_count:n</code>	<code>\num_elt_count:n    {<math>\langle balanced\ text \rangle</math>}</code>
<code>\num_elt_count_prop:Nn</code>	

`\num_elt_count_prop:Nn  $\langle prop \rangle$  { $\langle balanced\ text \rangle$ }`

Discards their arguments and puts a +1 in the input stream. Used to count elements in a token list.

## 42    Formatting a counter value

See the `l3int` module for ways of doing this.

## 43    Variable and constants

<code>\c_max_register_num</code>	Maximum number of registers; possibly engine-specific.
----------------------------------	--

<code>\l_tmpa_num</code>	Scratch register for immediate use. They are not used by conditionals or predicate functions.
<code>\l_tmpb_num</code>	
<code>\l_tmpc_num</code>	
<code>\g_tmpa_num</code>	
<code>\g_tmpb_num</code>	
<code>\g_tmppb_num</code>	

## 44    Primitive functions

<code>\if_num:w</code>	<code>\if_num:w <math>\langle number_1 \rangle</math> <math>\langle rel \rangle</math> <math>\langle number_2 \rangle</math> <math>\langle true \rangle</math> <math>\langle false \rangle</math></code>
<code>\fi:</code>	

Compare two numbers. It is recommended to use `\intexpr_eval:n` to correctly evaluate and terminate these numbers.  $\langle rel \rangle$  is one of  $<$ ,  $=$  or  $>$  with catcode 12.

**T<sub>E</sub>Xhackers note:** This is the T<sub>E</sub>X primitive `\ifnum`.

<code>\if_case:w</code> <code>\or:</code>	<code>\if_case:w &lt;number&gt; &lt;case<sub>0</sub>&gt; \or: &lt;case<sub>1</sub>&gt; \or: ... \else:</code> <code>&lt;default&gt; \fi:</code>
--	--

Chooses case  $\langle number \rangle$ . If you wish to use negative numbers as well, you can offset them with `\intexpr_eval:n`.

**T<sub>E</sub>Xhackers note:** These are the T<sub>E</sub>X primitives `\ifcase` and `\or`.

## Part X

# The l3intexpr package

## Integer expressions

This module sets up evaluation of integer expressions and allows mixing `int` and `num` registers.

An integer expression is one that contains integers in the form of numbers, registers containing numbers, i.e., `int` and `num` registers plus constants like `\c_one`, standard operators `+`, `-`, `/` and `*` and parentheses to group sub-expressions.

## 45 Functions

<code>\intexpr_eval:n *</code>	<code>\intexpr_eval:n {&lt;int expr&gt;}</code>
--------------------------------	---

The result of this expansion is a properly terminated  $\langle number \rangle$ , i.e., one that can be used with `\if_case:w` and others. For example,

`\intexpr_eval:n{ 5 + 4*3 - (3+4*5) }`

evaluates to  $-6$ . The result is returned after two expansions so if you find that you need to pass on the result to another function using the expansion engine, the recommendation is to use an `f` type expansion if in an expandable context or `x` otherwise.

<code>\intexpr_compare_p:n *</code> <code>\intexpr_compare:nTF *</code>	<code>\intexpr_compare_p:n {&lt;&lt;int expr<sub>1</sub>&gt; &lt;rel&gt; &lt;int expr<sub>2</sub>&gt;&gt;}</code>
--	---

Compares  $\langle int\ expr_1 \rangle$  with  $\langle int\ expr_2 \rangle$  using C-like relational operators, i.e.

Less than	<code>&lt;</code>	Less than or equal	<code>&lt;=</code>
Greater than	<code>&gt;</code>	Greater than or equal	<code>&gt;=</code>
Equal	<code>==</code> or <code>=</code>	Not equal	<code>!=</code>

Both integer expressions are evaluated fully in the process. Note the syntax, which allows natural input in the style of

```
\intexpr_compare_p:n {5+3 != \l_tmpb_int}
```

= is added for the sake of T<sub>E</sub>X users accustomed to using a single equal sign.

<pre>\intexpr_compare_p:nNn * \intexpr_compare:nNnTF *</pre>	<pre>\intexpr_compare_p:nNn {&lt;int expr<sub>1</sub>&gt;}&lt;rel&gt;{&lt;int expr<sub>2</sub>&gt;}</pre>
--	---

Compares  $\langle int\ expr_1 \rangle$  with  $\langle int\ expr_2 \rangle$  using one of the relations =, > or <. This is faster than the variant above but at the cost of requiring a little more typing and not supporting the extended set of relational operators. Note that if both expressions are normal integer variables as in

```
\intexpr_compare:nNnTF \l_temp_int < \c_zero {negative}{non-negative}
```

you can safely omit the braces.

<pre>\intexpr_max:nn * \intexpr_min:nn *</pre>	<pre>\intexpr_max:nn {&lt;int expr<sub>1</sub>&gt;} {&lt;int expr<sub>2</sub>&gt;}</pre>
--	--

Return the largest or smallest of two integer expressions.

<pre>\intexpr_abs:n *</pre>	<pre>\intexpr_abs:n {&lt;int expr&gt;}</pre>
-----------------------------	--

Return the numerical value of an integer expression.

<pre>\intexpr_if_odd:nTF * \intexpr_if_odd_p:n * \intexpr_if_even:nTF * \intexpr_if_even_p:n *</pre>	<pre>\intexpr_if_odd:nTF {&lt;int expr&gt;} {&lt;true&gt;} {&lt;false&gt;}</pre>
--	--

These functions test if an integer expression is even or odd.

<pre>\intexpr_div_truncate:nn * \intexpr_div_round:nn * \intexpr_mod:nn *</pre>	<pre>\intexpr_div_truncate:n {&lt;int expr&gt;} {&lt;int expr&gt;} \intexpr_mod:nn {&lt;int expr&gt;} {&lt;int expr&gt;}</pre>
---	--

If you want the result of a division to be truncated use `\intexpr_div_truncate:nn`. `\intexpr_div_round:nn` is added for completeness. `\intexpr_mod:nn` returns the remainder of a division.

## 46 Primitive functions

<code>\intexpr_value:w</code>
-------------------------------

`\intexpr_value:w <integer>`  
`\intexpr_value:w <tokens> <optional space>`

Expands *<tokens>* until an *<integer>* is formed. One space may be gobbled in the process.

**T<sub>E</sub>Xhackers note:** This is the T<sub>E</sub>X primitive `\number`.

<code>\intexpr_eval:w</code> <code>\intexpr_eval_end:</code>
---

`\intexpr_eval:w <int expr> \intexpr_eval_end:`

Evaluates *<int expr>*. The evaluation stops when an unexpandable token of catcode other than 12 is reached or `\intexpr_end:` is read. The latter is gobbled by the scanner mechanism.

**T<sub>E</sub>Xhackers note:** This is the  $\varepsilon$ -T<sub>E</sub>X primitive `\numexpr`.

<code>\if_intexpr_compare:w</code>
------------------------------------

`\if_intexpr_compare:w <number12  
\else: <false> \fi:`

Compare two numbers. It is recommended to use `\intexpr_eval:n` to correctly evaluate and terminate these numbers. *<rel>* is one of *<*, *=* or *>* with catcode 12.

**T<sub>E</sub>Xhackers note:** This is the T<sub>E</sub>X primitive `\ifnum`.

<code>\if_intexpr_odd:w</code>
--------------------------------

`\if_intexpr_odd:w <number> <true> \else: <false> \fi:`  
Execute *<true>* if *<number>* is odd, *<false>* otherwise.

**T<sub>E</sub>Xhackers note:** This is the T<sub>E</sub>X primitive `\ifodd`.

<code>\if_intexpr_case:w</code> <code>\or:</code>
--

`\if_intexpr_case:w <number> <case01  
\else:  
<default> \fi:`

Chooses case *<number>*. If you wish to use negative numbers as well, you can offset them with `\intexpr_eval:n`.

**T<sub>E</sub>Xhackers note:** These are the T<sub>E</sub>X primitives `\ifcase` and `\or`.

<code>\intexpr_while_do:nn</code> <code>\intexpr_until_do:nn</code> <code>\intexpr_do_while:nn</code> <code>\intexpr_do_until:nn</code>	<code>\intexpr_while_do:nn    {&lt;int expr<sub>1</sub>&gt; &lt;rel&gt; &lt;int expr<sub>2</sub>&gt;}&amp;#92;</code> <code>{&lt;code&gt;}</code>
--	--

`\intexpr_while_do:nn` tests the integer expressions against each other using a C-like `<rel>` as in `\intexpr_compare_p:n` and if true performs the `<code>` until the test fails. `\intexpr_do_while:nn` is similar but executes the `<code>` first and then performs the check, thus ensuring that the body is executed at least once. The ‘until’ versions are similar but continue the loop as long as the test is false. They could be omitted as it is just a matter of switching the arguments in the test.

<code>\intexpr_while_do:nNnn</code> <code>\intexpr_until_do:nNnn</code> <code>\intexpr_do_while:nNnn</code> <code>\intexpr_do_until:nNnn</code>	<code>\intexpr_while_do:nNnn    &lt;int expr&gt; &lt;rel&gt; &lt;int expr&gt; {&lt;code&gt;}</code>
--	---

Exactly as above but instead using the syntax of `\intexpr_compare_p:nNn`.

## Part XI

# The l3skip package

## Dimension and skip registers

L<sup>A</sup>T<sub>E</sub>X3 knows about two types of length registers for internal use: rubber lengths (`skips`) and rigid lengths (`dims`).

## 47 Skip registers

### 47.1 Functions

<code>\skip_new:N</code> <code>\skip_new:c</code>	<code>\skip_new:N    &lt;skip&gt;</code>
--	--

Defines `<skip>` to be a new variable of type `skip`.

**T<sub>E</sub>Xhackers note:** `\skip_new:N` is the equivalent to plain T<sub>E</sub>X’s `\newskip`. However, the internal register allocation is done differently.

<code>\skip_zero:N</code>
<code>\skip_zero:c</code>
<code>\skip_gzero:N</code>
<code>\skip_gzero:c</code>

`\skip_zero:N    <skip>`

Locally or globally reset  $\langle skip \rangle$  to zero. For global variables the global versions should be used.

<code>\skip_set:Nn</code>
<code>\skip_set:cn</code>
<code>\skip_gset:Nn</code>
<code>\skip_gset:cn</code>

`\skip_set:Nn    <skip> {<skip value>}`

These functions will set the  $\langle skip \rangle$  register to the  $\langle length \rangle$  value.

<code>\skip_add:Nn</code>
<code>\skip_add:cn</code>
<code>\skip_gadd:Nn</code>
<code>\skip_gadd:cn</code>

`\skip_add:Nn    <skip> {<length>}`

These functions will add to the  $\langle skip \rangle$  register the value  $\langle length \rangle$ . If the second argument is a  $\langle skip \rangle$  register too, the surrounding braces can be left out.

<code>\skip_sub:Nn</code>
<code>\skip_gsub:Nn</code>

`\skip_gsub:Nn    <skip> {<length>}`

These functions will subtract from the  $\langle skip \rangle$  register the value  $\langle length \rangle$ . If the second argument is a  $\langle skip \rangle$  register too, the surrounding braces can be left out.

<code>\skip_use:N</code>
<code>\skip_use:c</code>

`\skip_use:N    <skip>`

This function returns the length value kept in  $\langle skip \rangle$  in a way suitable for further processing.

**T<sub>E</sub>Xhackers note:** The function `\skip_use:N` could be implemented directly as the T<sub>E</sub>X primitive `\tex_the:D` which is also responsible to produce the values for other internal quantities. We have chosen to use individual functions for counters, dimensions etc. to allow checks and to make the code more self-explanatory.

<code>\skip_show:N</code>
<code>\skip_show:c</code>

`\skip_show:N    <skip>`

This function pauses the compilation and displays the length value kept in  $\langle skip \rangle$  in the console output and log file.

**T<sub>E</sub>Xhackers note:** The function `\skip_show:N` could be implemented directly as the T<sub>E</sub>X primitive `\tex_showthe:D` which is also responsible to produce the values for other internal

quantities. We have chosen to use individual functions for counters, dimensions etc. to allow checks and to make the code more self-explaining.

<code>\skip_horizontal:N</code>
<code>\skip_horizontal:c</code>
<code>\skip_horizontal:n</code>
<code>\skip_vertical:N</code>
<code>\skip_vertical:c</code>
<code>\skip_vertical:n</code>

`\skip_horizontal:N <skip>`  
`\skip_horizontal:n {<length>}`

The **hor** functions insert  $\langle skip \rangle$  or  $\langle length \rangle$  with the  $\text{\TeX}$  primitive `\hskip`. The **vertical** variants do the same with `\vskip`. The **n** versions evaluate  $\langle length \rangle$  with `\skip_eval:n`.

<code>\skip_if_infinite_glue_p:n</code>
<code>\skip_if_infinite_glue:nTF</code>

`\skip_if_infinite_glue:nTF {<skip>} {<true>} {<false>}`

Checks if  $\langle skip \rangle$  contains infinite stretch or shrink components and executes either  $\langle true \rangle$  or  $\langle false \rangle$ . Also works on input like `3pt plus .5in`.

<code>\skip_split_finite_else_action:nnNN</code>
--

`\skip_split_finite_else_action:nnNN {<skip>} {<action>}`  
`<dimen1> <dimen2>`

Checks if  $\langle skip \rangle$  contains finite glue. If it does then it assigns  $\langle dimen_1 \rangle$  the stretch component and  $\langle dimen_2 \rangle$  the shrink component. If it contains infinite glue set  $\langle dimen_1 \rangle$  and  $\langle dimen_2 \rangle$  to zero and execute `#2` which is usually an error or warning message of some sort.

<code>\skip_eval:n *</code>
-----------------------------

`\skip_eval:n {<skip expr>}`

Evaluates the value of  $\langle skip\ expr \rangle$  so that `\skip_eval:n {5pt plus 3fil + 3pt minus 1fil}` puts `8.0pt plus 3.0fil minus 1.0fil` back into the input stream. Expandable.

**$\text{\TeX}$ hackers note:** This is the  $\varepsilon$ - $\text{\TeX}$  primitive `\glueexpr` turned into a function taking an argument.

## 47.2 Formatting a skip register value

## 47.3 Variable and constants

<code>\c_max_skip</code>
--------------------------

Constant that denotes the maximum value which can be stored in a  $\langle skip \rangle$  register.



<code>\c_zero_skip</code>	Set of constants denoting useful values.
---------------------------	--

<code>\l_tmpa_skip</code> <code>\l_tmpb_skip</code> <code>\l_tmpc_skip</code> <code>\g_tmpa_skip</code> <code>\g_tmpb_skip</code>	Scratch register for immediate use.
---	-------------------------------------

## 48 Dim registers

### 48.1 Functions

<code>\dim_new:N</code> <code>\dim_new:c</code>	<code>\dim_new:N</code> $\langle dim \rangle$
--	---

Defines  $\langle dim \rangle$  to be a new variable of type `dim`.

**T<sub>E</sub>Xhackers note:** `\dim_new:N` is the equivalent to plain T<sub>E</sub>X's `\newdimen`. However, the internal register allocation is done differently.

<code>\dim_zero:N</code> <code>\dim_zero:c</code> <code>\dim_gzero:N</code> <code>\dim_gzero:c</code>	<code>\dim_zero:N</code> $\langle dim \rangle$
--	--

Locally or globally reset  $\langle dim \rangle$  to zero. For global variables the global versions should be used.

<code>\dim_set:Nn</code> <code>\dim_set:Nc</code> <code>\dim_set:cn</code> <code>\dim_gset:Nn</code> <code>\dim_gset:Nc</code> <code>\dim_gset:cn</code> <code>\dim_gset:cc</code>	<code>\dim_set:Nn</code> $\langle dim \rangle$ $\{\langle dim\ value \rangle\}$
--	---

These functions will set the  $\langle dim \rangle$  register to the  $\langle dim\ value \rangle$  value.

<code>\dim_add:Nn</code> <code>\dim_add:Nc</code> <code>\dim_add:cn</code> <code>\dim_gadd:Nn</code> <code>\dim_gadd:cn</code>	<code>\dim_add:Nn</code> $\langle dim \rangle$ $\{\langle length \rangle\}$
--	---

These functions will add to the  $\langle dim \rangle$  register the value  $\langle length \rangle$ . If the second argument

is a  $\langle dim \rangle$  register too, the surrounding braces can be left out.

<code>\dim_sub:Nn</code>
<code>\dim_sub:Nc</code>
<code>\dim_sub:cn</code>
<code>\dim_gsub:Nn</code>
<code>\dim_gsub:cn</code>

`\dim_gsub:Nn     $\langle dim \rangle$  { $\langle length \rangle$ }`

These functions will subtract from the  $\langle dim \rangle$  register the value  $\langle length \rangle$ . If the second argument is a  $\langle dim \rangle$  register too, the surrounding braces can be left out.

<code>\dim_use:N</code>
<code>\dim_use:c</code>

`\dim_use:N     $\langle dim \rangle$` 

This function returns the length value kept in  $\langle dim \rangle$  in a way suitable for further processing.

**T<sub>E</sub>Xhackers note:** The function `\dim_use:N` could be implemented directly as the T<sub>E</sub>X primitive `\tex_the:D` which is also responsible to produce the values for other internal quantities. We have chosen to use individual functions for counters, dimensions etc. to allow checks and to make the code more self-explanatory.

<code>\dim_show:N</code>
<code>\dim_show:c</code>

`\dim_show:N     $\langle skip \rangle$` 

This function pauses the compilation and displays the length value kept in  $\langle skip \rangle$  in the console output and log file.

**T<sub>E</sub>Xhackers note:** The function `\dim_show:N` could be implemented directly as the T<sub>E</sub>X primitive `\tex_showthe:D` which is also responsible to produce the values for other internal quantities. We have chosen to use individual functions for counters, dimensions etc. to allow checks and to make the code more self-explaining.

<code>\dim_eval:n</code>
--------------------------

`\dim_eval:n    { $\langle dim \ expr \rangle$ }`

Evaluates the value of a dimension expression so that `\dim_eval:n {5pt+3pt}` puts 8pt back into the input stream. Expandable.

**T<sub>E</sub>Xhackers note:** This is the  $\varepsilon$ -T<sub>E</sub>X primitive `\dimexpr` turned into a function taking an argument.

<code>\if_dim:w</code>
------------------------

`\if_dim:w     $\langle dimen_1 \rangle$   $\langle rel \rangle$   $\langle dimen_2 \rangle$   $\langle true \rangle$  \else:  $\langle false \rangle$  \fi:`

Compare two dimensions. It is recommended to use `\dim_eval:n` to correctly evaluate and terminate these numbers.  $\langle rel \rangle$  is one of  $<$ ,  $=$  or  $>$  with catcode 12.

**T<sub>E</sub>Xhackers note:** This is the T<sub>E</sub>X primitive `\ifdim`.

<code>\dim_compare:nNnTF *</code>	<code>\dim_compare:nNnTF</code>	<code>{\dim expr}</code>	<code>\rel</code>	<code>{\dim expr}</code>
<code>\dim_compare_p:nNn *</code>	<code>{\true}</code>	<code>{\false}</code>		

These functions test two dimension expressions against each other. They are both evaluated by `\dim_eval:n`. Note that if both expressions are normal dimension variables as in

```
\dim_compare:nNnTF \l_temp_dim < \c_zero_skip {negative}{non-negative}
```

you can safely omit the braces.

**T<sub>E</sub>Xhackers note:** This is the T<sub>E</sub>X primitive `\ifdim` turned into a function.

<code>\dim_while_do:nNnn</code>	<code>\dim_while_do:nNnn</code>	<code>\dim expr</code>	<code>\rel</code>	<code>\dim expr</code>	<code>\code</code>
<code>\dim_until_do:nNnn</code>					
<code>\dim_do_while:nNnn</code>					
<code>\dim_do_until:nNnn</code>					

`\dim_while_do:nNnn` tests the dimension expressions and if true performs `\code` repeatedly while the test remains true. `\dim_do_while:nNnn` is similar but executes the body first and then performs the check, thus ensuring that the body is executed at least once. The ‘until’ versions are similar but continue the loop as long as the test is false.

## 48.2 Variable and constants

<code>\c_max_dim</code>	Constant that denotes the maximum value which can be stored in a <code>\dim</code> register.
-------------------------	--

<code>\c_zero_dim</code>	Set of constants denoting useful values.
--------------------------	--

<code>\l_tmpa_dim</code>	Scratch register for immediate use.
<code>\l_tmpp_dim</code>	
<code>\l_tmpe_dim</code>	
<code>\l_tmpe_dim</code>	
<code>\g_tmpa_dim</code>	
<code>\g_tmpp_dim</code>	

## 49 Muskips

<code>\muskip_new:N</code>
----------------------------

`\muskip_new:N     $\langle muskip \rangle$` 

Defines  $\langle muskip \rangle$  to be a new variable of type `muskip`.

**T<sub>E</sub>Xhackers note:** `\muskip_new:N` is the equivalent to plain T<sub>E</sub>X's `\newmuskip`. However, the internal register allocation is done differently.

<code>\muskip_set:Nn</code>
<code>\muskip_gset:Nn</code>

`\muskip_set:Nn     $\langle muskip \rangle$  { $\langle muskip \text{ value} \rangle$ }`

These functions will set the  $\langle muskip \rangle$  register to the  $\langle length \rangle$  value.

<code>\muskip_add:Nn</code>
<code>\muskip_gadd:Nn</code>

`\muskip_add:Nn     $\langle muskip \rangle$  { $\langle length \rangle$ }`

These functions will add to the  $\langle muskip \rangle$  register the value  $\langle length \rangle$ . If the second argument is a  $\langle muskip \rangle$  register too, the surrounding braces can be left out.

<code>\muskip_sub:Nn</code>
<code>\muskip_gsub:Nn</code>

`\muskip_gsub:Nn     $\langle muskip \rangle$  { $\langle length \rangle$ }`

These functions will subtract from the  $\langle muskip \rangle$  register the value  $\langle length \rangle$ . If the second argument is a  $\langle muskip \rangle$  register too, the surrounding braces can be left out.

<code>\muskip_use:N</code>
----------------------------

`\muskip_use:N     $\langle muskip \rangle$` 

This function returns the length value kept in  $\langle muskip \rangle$  in a way suitable for further processing.

**T<sub>E</sub>Xhackers note:** See note for `\dim_use:N`.

## Part XII

# The l3tl package

## Token Lists

L<sup>A</sup>T<sub>E</sub>X3 stores token lists in variables also called ‘token lists’. Variables of this type get the suffix `tl` and functions of this type have the prefix `tl`. To use a token list variable you simply call the corresponding variable.

Often you find yourself with not a token list variable but an arbitrary token list which has to undergo certain tests. We will *also* prefix these functions with `tl`. While token list variables are always single tokens, token lists are always surrounded by braces.

## 50 Functions

<code>\tl_new:N</code> <code>\tl_new:c</code> <code>\tl_new:Nn</code> <code>\tl_new:cn</code> <code>\tl_new:Nx</code>	<code>\tl_new:Nn &lt;tl var.&gt; {&lt;initial token list&gt;}</code>
---	--

Defines `<tl var.>` to be a new variable to store a token list. `<initial token list>` is the initial value of `<tl var.>`. This makes it possible to assign values to a constant token list variable.

The form `\tl_new:N` initializes the token list variable with an empty value.

<code>\tl_use:N</code> <code>\tl_use:c</code>	<code>\tl_use:N &lt;tl var.&gt;</code>
--	--

Function that inserts the `<tl var.>` into the processing stream. Instead of `\tl_use:N` simply placing the `<tl var.>` into the input stream is also supported. `\tl_use:c` will complain if the `<tl var.>` hasn't been declared previously!

<code>\tl_show:N</code> <code>\tl_show:c</code> <code>\tl_show:n</code>	<code>\tl_show:N &lt;tl var.&gt;</code> <code>\tl_show:n {&lt;token list&gt;}</code>
---	---

Function that pauses the compilation and displays the `<tl var.>` or `<token list>` on the console output and in the log file.

<code>\tl_set:Nn</code>
<code>\tl_set:Nc</code>
<code>\tl_set:NV</code>
<code>\tl_set:No</code>
<code>\tl_set:Nv</code>
<code>\tl_set:Nf</code>
<code>\tl_set:Nx</code>
<code>\tl_set:cn</code>
<code>\tl_set:co</code>
<code>\tl_set:cV</code>
<code>\tl_set:cx</code>
<code>\tl_gset:Nn</code>
<code>\tl_gset:Nc</code>
<code>\tl_gset:No</code>
<code>\tl_gset:NV</code>
<code>\tl_gset:Nv</code>
<code>\tl_gset:Nx</code>
<code>\tl_gset:cn</code>
<code>\tl_gset:cx</code>

`\tl_set:Nn <tl var.> {<token list>}`

Defines  $\langle tl\ var.\rangle$  to hold the token list  $\langle token\ list\rangle$ . Global variants of this command assign the value globally the other variants expand the  $\langle token\ list\rangle$  up to a certain level before the assignment or interpret the  $\langle token\ list\rangle$  as a character list and form a control sequence out of it.

<code>\tl_clear:N</code>
<code>\tl_clear:c</code>
<code>\tl_gclear:N</code>
<code>\tl_gclear:c</code>

`\tl_clear:N <tl var.>`

The  $\langle tl\ var.\rangle$  is locally or globally cleared. The `c` variants will generate a control sequence name which is then interpreted as  $\langle tl\ var.\rangle$  before clearing.

<code>\tl_clear_new:N</code>
<code>\tl_clear_new:c</code>
<code>\tl_gclear_new:N</code>
<code>\tl_gclear_new:c</code>

`\tl_clear_new:N <tl var.>`

These functions check if  $\langle tl\ var.\rangle$  exists. If it does it will be cleared; if it doesn't it will be allocated.

<code>\tl_put_left:Nn</code>
<code>\tl_put_left:NV</code>
<code>\tl_put_left:No</code>
<code>\tl_put_left:Nx</code>
<code>\tl_put_left:cn</code>
<code>\tl_put_left:cV</code>
<code>\tl_put_left:co</code>

`\tl_put_left:Nn <tl var.> {<token list>}`

These functions will append *<token list>* to the left of *<tl var.>*. *<token list>* might be subject to expansion before assignment.

<code>\tl_put_right:Nn</code>
<code>\tl_put_right:NV</code>
<code>\tl_put_right:No</code>
<code>\tl_put_right:Nx</code>
<code>\tl_put_right:cn</code>
<code>\tl_put_right:cV</code>
<code>\tl_put_right:co</code>

`\tl_put_right:Nn <tl var.> {<token list>}`

These functions append *<token list>* to the right of *<tl var.>*.

<code>\tl_gput_left:Nn</code>
<code>\tl_gput_left:No</code>
<code>\tl_gput_left:NV</code>
<code>\tl_gput_left:Nx</code>
<code>\tl_gput_left:cn</code>
<code>\tl_gput_left:co</code>
<code>\tl_gput_left:cV</code>

`\tl_gput_left:Nn <tl var.> {<token list>}`

These functions will append *<token list>* globally to the left of *<tl var.>*.

<code>\tl_gput_right:Nn</code>
<code>\tl_gput_right:No</code>
<code>\tl_gput_right:NV</code>
<code>\tl_gput_right:Nx</code>
<code>\tl_gput_right:cn</code>
<code>\tl_gput_right:co</code>
<code>\tl_gput_right:cV</code>

`\tl_gput_right:Nn <tl var.> {<token list>}`

These functions will globally append *<token list>* to the right of *<tl var.>*.

A word of warning is appropriate here: Token list variables are implemented as macros and as such currently inherit some of the peculiarities of how T<sub>E</sub>X handles #s in the argument of macros. In particular, the following actions are legal

```

\tl_set:Nn \l_tmpa_tl{##1}
\tl_put_right:Nn \l_tmpa_tl{##2}
\tl_set:No \l_tmpb_tl{\l_tmpa_tl ##3}

```

x type expansions where macros being expanded contain #s do not work and will not work until there is an `\expanded` primitive in the engine. If you want them to work you must double #s another level.

<code>\tl_set_eq:NN</code>
<code>\tl_set_eq:Nc</code>
<code>\tl_set_eq:cN</code>
<code>\tl_set_eq:cc</code>
<code>\tl_gset_eq:NN</code>
<code>\tl_gset_eq:Nc</code>
<code>\tl_gset_eq:cN</code>
<code>\tl_gset_eq:cc</code>

`\tl_set_eq:NN <tl var.1> <tl var.2>`

Fast form for `\tl_set:No <tl var.1> {\<tl var.2>}`  
when `<tl var.2>` is known to be a variable of type `tl`.

<code>\tl_to_str:N</code>
<code>\tl_to_str:c</code>

`\tl_to_str:N <tl var.>`

This function returns the token list kept in `<tl var.>` as a string list with all characters catcoded to ‘other’.

<code>\tl_to_str:n</code>
---------------------------

`\tl_to_str:n {\<token list>}`

This function turns its argument into a string where all characters have catcode ‘other’.

**TeXhackers note:** This is the  $\varepsilon$ -TeX primitive `\detokenize`.

<code>\tl_rescan:nn</code>
----------------------------

`\tl_rescan:nn {\<catcode setup>} {\<token list>}`

Returns the result of re-tokenising `<token list>` with the catcode setup (and whatever other redefinitions) specified. This is useful because the catcodes of characters are ‘frozen’ when first tokenised; this allows their meaning to be changed even after they’ve been read as an argument. Also see `\tl_set_rescan:Nnn` below.

**TeXhackers note:** This is a wrapper around  $\varepsilon$ -TeX’s `\scantokens`.

<code>\tl_set_rescan:Nnn</code>
<code>\tl_set_rescan:Nnx</code>
<code>\tl_gset_rescan:Nnn</code>
<code>\tl_gset_rescan:Nnx</code>

`\tl_set_rescan:Nnn <tl var.> {\<catcode setup>} {\<token list>}`

Sets `<tl var.>` to the result of re-tokenising `<token list>` with the catcode setup (and whatever other redefinitions) specified.

**TeXhackers note:** This is a wrapper around  $\varepsilon$ -TeX’s `\scantokens`.



## 51 Predicates and conditionals

<code>\tl_if_empty_p:N *</code> <code>\tl_if_empty_p:c *</code>	<code>\tl_if_empty_p:N &lt;tl var.&gt;</code>
--	---

This predicate returns ‘true’ if  $\langle tl\ var.\rangle$  is ‘empty’ i.e., doesn’t contain any tokens.

<code>\tl_if_empty:NTF *</code> <code>\tl_if_empty:cTF *</code>	<code>\tl_if_empty:NTF &lt;tl var.&gt; {\langle true code\rangle} {\langle false code\rangle}</code>
--	--

Execute  $\langle true\ code\rangle$  if  $\langle tl\ var.\rangle$  is empty and  $\langle false\ code\rangle$  if it contains any tokens.

<code>\tl_if_eq_p:NN *</code> <code>\tl_if_eq_p:cN *</code> <code>\tl_if_eq_p:Nc *</code> <code>\tl_if_eq_p:cc *</code>	<code>\tl_if_eq_p:NN &lt;tl var._1&gt; &lt;tl var._2&gt;</code>
--	---

Predicate function which returns ‘true’ if the two token list variables are identical and ‘false’ otherwise.

<code>\tl_if_eq:NNTF *</code> <code>\tl_if_eq:cNTF *</code> <code>\tl_if_eq:NcTF *</code> <code>\tl_if_eq:ccTF *</code>	<code>\tl_if_eq:NNTF &lt;tl var._1&gt; &lt;tl var._2&gt; {\langle true code\rangle} {\langle false code\rangle}</code>
--	--

Execute  $\langle true\ code\rangle$  if  $\langle tl\ var._1\rangle$  holds the same token list as  $\langle tl\ var._2\rangle$  and  $\langle false\ code\rangle$  otherwise.

<code>\tl_if_eq:nnTF *</code> <code>\tl_if_eq:nVTF *</code> <code>\tl_if_eq:noTF *</code> <code>\tl_if_eq:VnTF *</code> <code>\tl_if_eq:onTF *</code> <code>\tl_if_eq:VVTF *</code> <code>\tl_if_eq:ooTF *</code> <code>\tl_if_eq:xxTF *</code> <code>\tl_if_eq:xnTF *</code> <code>\tl_if_eq:nxTF *</code> <code>\tl_if_eq:xVTF *</code> <code>\tl_if_eq:xoTF *</code> <code>\tl_if_eq:VxTF *</code> <code>\tl_if_eq:oxTF *</code>	<code>\tl_if_eq:nnTF {\langle tlist_1\rangle} {\langle tlist_2\rangle} {\langle true code\rangle} {\langle false code\rangle}</code>
--	--

Execute  $\langle true\ code\rangle$  if the two token lists  $\langle tlist_1\rangle$  and  $\langle tlist_2\rangle$  are identical. These functions are expandable if a new enough version of pdfTeX is being used.

<code>\tl_if_eq_p:nn</code>	<code>*</code>
<code>\tl_if_eq_p:nV</code>	<code>*</code>
<code>\tl_if_eq_p:no</code>	<code>*</code>
<code>\tl_if_eq_p:Vn</code>	<code>*</code>
<code>\tl_if_eq_p:on</code>	<code>*</code>
<code>\tl_if_eq_p:VV</code>	<code>*</code>
<code>\tl_if_eq_p:oo</code>	<code>*</code>
<code>\tl_if_eq_p:xx</code>	<code>*</code>
<code>\tl_if_eq_p:xn</code>	<code>*</code>
<code>\tl_if_eq_p:nx</code>	<code>*</code>
<code>\tl_if_eq_p:xV</code>	<code>*</code>
<code>\tl_if_eq_p:xo</code>	<code>*</code>
<code>\tl_if_eq_p:Vx</code>	<code>*</code>
<code>\tl_if_eq_p:ox</code>	<code>*</code>

`\tl_if_eq_p:nn {<tlst1>} {<tlst2>}`

Predicates function which returns ‘true’ if the two token list are identical and ‘false’ otherwise. These are only defined if a new enough version of pdf<sub>T</sub><sub>E</sub>X is in use.

<code>\tl_if_empty_p:n</code>	<code>*</code>
<code>\tl_if_empty_p:V</code>	<code>*</code>
<code>\tl_if_empty_p:o</code>	<code>*</code>
<code>\tl_if_empty:nTF</code>	
<code>\tl_if_empty:VTF</code>	
<code>\tl_if_empty:oTF</code>	

`\tl_if_empty:nTF {<token list>} {<true code>} {<false code>}`

Execute *<true code>* if *<token list>* doesn’t contain any tokens and *<false code>* otherwise.

<code>\tl_if_blank_p:n</code>	<code>*</code>
<code>\tl_if_blank:nTF</code>	<code>*</code>
<code>\tl_if_blank_p:V</code>	<code>*</code>
<code>\tl_if_blank_p:o</code>	<code>*</code>
<code>\tl_if_blank:VTF</code>	<code>*</code>
<code>\tl_if_blank:oTF</code>	<code>*</code>

`\tl_if_blank:nTF {<token list>} {<true code>} {<false code>}`

Execute *<true code>* if *<token list>* is blank meaning that it is either empty or contains only blank spaces.

<code>\tl_to_lowercase:n</code>	
<code>\tl_to_uppercase:n</code>	

`\tl_to_lowercase:n {<token list>}`

`\tl_to_lowercase:n` converts all tokens in *<token list>* to their lower case representation. Similar for `\tl_to_uppercase:n`.

**T<sub>E</sub>Xhackers note:** These are the T<sub>E</sub>X primitives `\lowercase` and `\uppercase` renamed.

## 52 Working with the contents of token lists

<code>\tl_map_function:nN *</code> <code>\tl_map_function:NN</code> <code>\tl_map_function:cN</code>	<code>\tl_map_function:nN {&lt;token list&gt;} &lt;function&gt;</code> <code>\tl_map_function:NN &lt;tl var.&gt; &lt;function&gt;</code>
--	---

Runs through all elements in a  $\langle token\ list \rangle$  from left to right and places  $\langle function \rangle$  in front of each element. As this function will also pick up elements in brace groups, the element is returned with braces and hence  $\langle function \rangle$  should be a function with a `:n` suffix even though it may very well only deal with a single token.

This function uses a purely expandable loop function and will stay so as long as  $\langle function \rangle$  is expandable too.

<code>\tl_map_inline:nn</code> <code>\tl_map_inline:Nn</code> <code>\tl_map_inline:cn</code>	<code>\tl_map_inline:nn {&lt;token list&gt;} {&lt;inline function&gt;}</code> <code>\tl_map_inline:Nn &lt;tl var.&gt; {&lt;inline function&gt;}</code>
--	---

Allows a syntax like `\tl_map_inline:nn {<token list>} {\token_to_str:N ##1}`. This renders it non-expandable though. Remember to double the `#`s for each level.

<code>\tl_map_variable:nNn</code> <code>\tl_map_variable:NNn</code> <code>\tl_map_variable:cNn</code>	<code>\tl_map_variable:nNn {&lt;token list&gt;} &lt;temp&gt; {&lt;action&gt;}</code> <code>\tl_map_variable:NNn &lt;tl var.&gt; &lt;temp&gt; {&lt;action&gt;}</code>
---	---

Assigns  $\langle temp \rangle$  to each element on  $\langle token\ list \rangle$  and executes  $\langle action \rangle$ . As there is an assignment in this process it is not expandable.

**TeXhackers note:** This is the L<sup>A</sup>T<sub>E</sub>X2 function `\@tfor` but with a more sane syntax. Also it works by tail recursion and so is faster as lists grow longer.

<code>\tl_map_break:</code>	<code>\tl_map_break:</code>
-----------------------------	-----------------------------

For breaking out of a loop. Must not be nested inside a primitive `\if` structure.

<code>\tl_reverse:n</code> <code>\tl_reverse:V</code> <code>\tl_reverse:o</code> <code>\tl_reverse:N</code>	<code>\tl_reverse:n {&lt;token<sub>1</sub>&gt;&lt;token<sub>2</sub>&gt;...&lt;token<sub>n</sub>&gt;}</code> <code>\tl_reverse:N &lt;tl var.&gt;</code>
--	---

Reverse the token list (or the token list in the  $\langle tl\ var. \rangle$ ) to result in  $\langle token_n \rangle \dots \langle token_2 \rangle \langle token_1 \rangle$ . Note that spaces in this token list are gobbled in the process.

Note also that braces are lost in the process of reversing a  $\langle tl\ var.\rangle$ . That is,  $\backslash\mathrm{tl\_set:Nn}\ \backslash\mathrm{l\_tmpa\_tl}\ \{\mathrm{a}\{\mathrm{bcd}\}\mathrm{e}\}\ \backslash\mathrm{tl\_reverse:N}\ \backslash\mathrm{l\_tmpa\_tl}$  will result in `ebcda`. This behaviour is probably more of a bug than a feature.

$\backslash\mathrm{tl\_elt\_count:n}\ \star$	
$\backslash\mathrm{tl\_elt\_count:V}\ \star$	
$\backslash\mathrm{tl\_elt\_count:o}\ \star$	$\backslash\mathrm{tl\_elt\_count:n}\ \{\langle token\ list\rangle\}$
$\backslash\mathrm{tl\_elt\_count:N}\ \star$	$\backslash\mathrm{tl\_elt\_count:N}\ \langle tl\ var.\rangle$

Returns the number of elements in the token list. Brace groups encountered count as one element. Note that spaces in this token list are gobbled in the process.

## 53 Variables and constants

$\backslash\mathrm{c\_job\_name\_tl}$
---------------------------------------

Constant that gets the ‘job name’ assigned when  $\mathrm{T}_{\mathrm{E}}\mathrm{X}$  starts.

**$\mathrm{T}_{\mathrm{E}}\mathrm{X}$ hackers note:** This is the new name for the primitive  $\backslash\mathrm{jobname}$ . It is a constant that is set by  $\mathrm{T}_{\mathrm{E}}\mathrm{X}$  and should not be overwritten by the package.

$\backslash\mathrm{c\_empty\_tl}$
-----------------------------------

Constant that is always empty.

**$\mathrm{T}_{\mathrm{E}}\mathrm{X}$ hackers note:** This was named  $\backslash\mathrm{@empty}$  in  $\mathrm{L}^{\mathrm{A}}\mathrm{T}_{\mathrm{E}}\mathrm{X}2$  and  $\backslash\mathrm{empty}$  in plain  $\mathrm{T}_{\mathrm{E}}\mathrm{X}$ .

$\backslash\mathrm{l\_tmpa\_tl}$ $\backslash\mathrm{l\_tmpb\_tl}$ $\backslash\mathrm{g\_tmpa\_tl}$ $\backslash\mathrm{g\_tmpb\_tl}$
--

Scratch register for immediate use. They are not used by conditionals or predicate functions.

$\backslash\mathrm{l\_tl\_replace\_toks}$
---

Internal register used in the replace functions.

$\backslash\mathrm{l\_testa\_tl}$ $\backslash\mathrm{l\_testb\_tl}$ $\backslash\mathrm{g\_testa\_tl}$ $\backslash\mathrm{g\_testb\_tl}$
--

Registers used for conditional processing if the engine doesn’t support arbitrary string comparison.

$\backslash\mathrm{g\_tl\_inline\_level\_int}$
--

Internal register used in the inline map functions.

## 54 Searching for and replacing tokens

<code>\tl_if_in:NnTF</code> <code>\tl_if_in:cnTF</code> <code>\tl_if_in:nnTF</code> <code>\tl_if_in:VnTF</code> <code>\tl_if_in:onTF</code>	<code>\tl_if_in:NnTF &lt;tl var.&gt; {&lt;item&gt;} {&lt;true code&gt;} {&lt;false code&gt;}</code>
---	---

Function that tests if  $\langle item \rangle$  is in  $\langle tl var. \rangle$ . Depending on the result either  $\langle true code \rangle$  or  $\langle false code \rangle$  is executed. Note that  $\langle item \rangle$  cannot contain brace groups nor  $\#_6$  tokens.

<code>\tl_replace_in:Nnn</code> <code>\tl_replace_in:cnn</code> <code>\tl_greplace_in:Nnn</code> <code>\tl_greplace_in:cnn</code>	<code>\tl_replace_in:Nnn &lt;tl var.&gt; {&lt;item<sub>1</sub>&gt;} {&lt;item<sub>2</sub>&gt;}</code>
--	---

Replaces the leftmost occurrence of  $\langle item_1 \rangle$  in  $\langle tl var. \rangle$  with  $\langle item_2 \rangle$  if present, otherwise the  $\langle tl var. \rangle$  is left untouched. Note that  $\langle item_1 \rangle$  cannot contain brace groups nor  $\#_6$  tokens, and  $\langle item_2 \rangle$  cannot contain  $\#_6$  tokens.

<code>\tl_replace_all_in:Nnn</code> <code>\tl_replace_all_in:cnn</code> <code>\tl_greplace_all_in:Nnn</code> <code>\tl_greplace_all_in:cnn</code>	<code>\tl_replace_all_in:Nnn &lt;tl var.&gt; {&lt;item<sub>1</sub>&gt;} {&lt;item<sub>2</sub>&gt;}</code>
--	---

Replaces *all* occurrences of  $\langle item_1 \rangle$  in  $\langle tl var. \rangle$  with  $\langle item_2 \rangle$ . Note that  $\langle item_1 \rangle$  cannot contain brace groups nor  $\#_6$  tokens, and  $\langle item_2 \rangle$  cannot contain  $\#_6$  tokens.

<code>\tl_remove_in:Nn</code> <code>\tl_remove_in:cn</code> <code>\tl_gremove_in:Nn</code> <code>\tl_gremove_in:cn</code>	<code>\tl_remove_in:Nn &lt;tl var.&gt; {&lt;item&gt;}</code>
--	--

Removes the leftmost occurrence of  $\langle item \rangle$  from  $\langle tl var. \rangle$  if present. Note that  $\langle item \rangle$  cannot contain brace groups nor  $\#_6$  tokens.

<code>\tl_remove_all_in:Nn</code> <code>\tl_remove_all_in:cn</code> <code>\tl_gremove_all_in:Nn</code> <code>\tl_gremove_all_in:cn</code>	<code>\tl_remove_all_in:Nn &lt;tl var.&gt; {&lt;item&gt;}</code>
--	--

Removes *all* occurrences of  $\langle item \rangle$  from  $\langle tl var. \rangle$ . Note that  $\langle item \rangle$  cannot contain brace groups nor  $\#_6$  tokens.

## 55 Heads or tails?

Here are some functions for grabbing either the head or tail of a list and perform some tests on it.

<code>\tl_head:n</code>	<code>*</code>	
<code>\tl_head:V</code>	<code>*</code>	
<code>\tl_tail:n</code>	<code>*</code>	
<code>\tl_tail:V</code>	<code>*</code>	
<code>\tl_tail:f</code>	<code>*</code>	
<code>\tl_head_i:n</code>	<code>*</code>	
<code>\tl_head_iii:n</code>	<code>*</code>	
<code>\tl_head_iii:f</code>	<code>*</code>	
<code>\tl_head:w</code>	<code>*</code>	
<code>\tl_tail:w</code>	<code>*</code>	
<code>\tl_head_i:w</code>	<code>*</code>	<code>\tl_head:n { &lt;token<sub>1</sub>&gt;&lt;token<sub>2</sub>&gt;...&lt;token<sub>n</sub>&gt; }</code>
<code>\tl_head_iii:w</code>	<code>*</code>	<code>\tl_tail:n { &lt;token<sub>1</sub>&gt;&lt;token<sub>2</sub>&gt;...&lt;token<sub>n</sub>&gt; }</code>
		<code>\tl_head:w &lt;token<sub>1</sub>&gt;&lt;token<sub>2</sub>&gt;...&lt;token<sub>n</sub>&gt; \q_nil</code>

These functions return either the head or the tail of a list, thus in the above example `\tl_head:n` would return `<token1>` and `\tl_tail:n` would return `<token2>...<tokenn>`. `\tl_head_iii:n` returns the first three tokens. The `:w` versions require some care as they use a delimited argument internally.

**T<sub>E</sub>Xhackers note:** These are the Lisp functions `car` and `cdr` but with L<sup>A</sup>T<sub>E</sub>X3 names.

<code>\tl_if_head_eq_meaning_p:nN</code>	<code>*</code>	
<code>\tl_if_head_eq_meaning:nNTF</code>	<code>*</code>	<code>\tl_if_head_eq_meaning:nNTF {&lt;token list&gt;} &lt;token&gt;</code>
		<code>{&lt;true&gt;} {&lt;false&gt;}</code>

Returns `<true>` if the first token in `<token list>` is equal to `<token>` and `<false>` otherwise. The `meaning` version compares the two tokens with `\if_meaning:w`.

<code>\tl_if_head_eq_charcode_p:nN</code>	<code>*</code>	
<code>\tl_if_head_eq_charcode_p:fN</code>	<code>*</code>	
<code>\tl_if_head_eq_charcode:nNTF</code>	<code>*</code>	<code>\tl_if_head_eq_charcode:nNTF {&lt;token list&gt;} &lt;token&gt;</code>
<code>\tl_if_head_eq_charcode:fNTF</code>	<code>*</code>	<code>{&lt;true&gt;} {&lt;false&gt;}</code>

Returns `<true>` if the first token in `<token list>` is equal to `<token>` and `<false>` otherwise. The `meaning` version compares the two tokens with `\if_charcode:w` but it prevents expansion of them. If you want them to expand, you can use an `f` type expansion first (define `\tl_if_head_eq_charcode:fNTF` or similar).

<code>\tl_if_head_eq_catcode_p:nN</code>	<code>*</code>	
<code>\tl_if_head_eq_catcode:nNTF</code>	<code>*</code>	<code>\tl_if_head_eq_catcode:nNTF {&lt;token list&gt;} &lt;token&gt;</code>
		<code>{&lt;true&gt;} {&lt;false&gt;}</code>

Returns  $\langle true \rangle$  if the first token in  $\langle token\ list \rangle$  is equal to  $\langle token \rangle$  and  $\langle false \rangle$  otherwise. This version uses `\if_catcode:w` for the test but is otherwise identical to the `charcode` version.

## Part XIII

# The l3toks package

## Token Registers

There is a second form beside token list variables in which L<sup>A</sup>T<sub>E</sub>X3 stores token lists, namely the internal T<sub>E</sub>X token registers. Functions dealing with these registers got the prefix `\toks_`. Unlike token list variables we have an accessing function as one can see below.

The main difference between  $\langle toks \rangle$  (token registers) and  $\langle tl\ var. \rangle$  (token list variable) is their behavior regarding expansion. While  $\langle tl\ vars \rangle$  expand fully (i.e., until only unexpandable tokens are left) inside an argument that is subject to expansion (i.e., denoted by  $\mathfrak{x}$ )  $\langle toks \rangle$ 's expand always only up to one level, i.e., passing their contents without further expansion.

There are fewer restrictions on the contents of a token register over a token list variable. So while  $\langle token\ list \rangle$  is used to describe the contents of both of these, bear in mind that slightly different lists of tokens are allowed in each case. The best (only?) example is that a  $\langle toks \rangle$  can contain the `#` character (i.e., characters of catcode 6), whereas a  $\langle tl\ var. \rangle$  will require its input to be sanitised before that is possible.

If you're not sure which to use between a  $\langle tl\ var. \rangle$  or a  $\langle toks \rangle$ , consider what data you're trying to hold. If you're dealing with function parameters involving `#`, or building some sort of data structure then you probably want a  $\langle toks \rangle$  (e.g., `l3prop` uses  $\langle toks \rangle$  to store its property lists).

If you're storing ad-hoc data for later use (possibly from direct user input) then usually a  $\langle tl\ var. \rangle$  will be what you want.

## 56 Allocation and use

<code>\toks_new:N</code>
<code>\toks_new:c</code>

`\toks_new:N \langle toks \rangle`

Defines  $\langle toks \rangle$  to be a new token list register.

**T<sub>E</sub>Xhackers note:** This is the L<sup>A</sup>T<sub>E</sub>X3 allocation for what was called `\newtoks` in plain T<sub>E</sub>X.

<code>\toks_use:N</code> <code>\toks_use:c</code>	<code>\toks_use:N &lt;toks&gt;</code>
--	---------------------------------------

Accesses the contents of  $\langle toks \rangle$ . Contrary to token list variables  $\langle toks \rangle$  can't be access simply by calling them directly.

**T<sub>E</sub>Xhackers note:** Something like `\the <toks>`.

<code>\toks_set:Nn</code> <code>\toks_set:NV</code> <code>\toks_set:Nv</code> <code>\toks_set:No</code> <code>\toks_set:Nx</code> <code>\toks_set:Nf</code> <code>\toks_set:cn</code> <code>\toks_set:co</code> <code>\toks_set:cV</code> <code>\toks_set:cv</code> <code>\toks_set:cx</code> <code>\toks_set:cf</code>	<code>\toks_set:Nn &lt;toks&gt; {&lt;token list&gt;}</code>
--	---

Defines  $\langle toks \rangle$  to hold the token list  $\langle token list \rangle$ .

**T<sub>E</sub>Xhackers note:** `\toks_set:Nn` could have been specified in plain T<sub>E</sub>X by  $\langle toks \rangle = \{ \langle token list \rangle \}$  but all other functions have no counterpart in plain T<sub>E</sub>X. Additionally the functions above the global variants described below will check for correct local and global assignments, something that isn't available in plain T<sub>E</sub>X.

<code>\toks_gset:Nn</code> <code>\toks_gset:NV</code> <code>\toks_gset:No</code> <code>\toks_gset:Nx</code> <code>\toks_gset:cn</code> <code>\toks_gset:cV</code> <code>\toks_gset:co</code> <code>\toks_gset:cx</code>	<code>\toks_gset:Nn &lt;toks&gt; {&lt;token list&gt;}</code>
--	--

Defines  $\langle toks \rangle$  to globally hold the token list  $\langle token list \rangle$ .

<code>\toks_set_eq:NN</code> <code>\toks_set_eq:cN</code> <code>\toks_set_eq:Nc</code> <code>\toks_set_eq:cc</code>	<code>\toks_set_eq:NN &lt;toks<sub>12 </sub></code>
--	---

Set  $\langle toks_1 \rangle$  to the value of  $\langle toks_2 \rangle$ . Don't try to use `\toks_set:Nn` for this purpose if the second argument is also a token register.



<code>\toks_gset_eq:NN</code>
<code>\toks_gset_eq:cN</code>
<code>\toks_gset_eq:Nc</code>
<code>\toks_gset_eq:cc</code>

`\toks_gset_eq:NN <toks1> <toks2>`

The  $\langle toks_1 \rangle$  globally set to the value of  $\langle toks_2 \rangle$ . Don't try to use `\toks_gset:Nn` for this purpose if the second argument is also a token register.

<code>\toks_clear:N</code>
<code>\toks_clear:c</code>
<code>\toks_gclear:N</code>
<code>\toks_gclear:c</code>

`\toks_clear:N <toks>`

The  $\langle toks \rangle$  is locally or globally cleared.

<code>\toks_use_clear:N</code>
<code>\toks_use_clear:c</code>
<code>\toks_use_gclear:N</code>
<code>\toks_use_gclear:c</code>

`\toks_use_clear:N <toks>`

Accesses the contents of  $\langle toks \rangle$  and clears (locally or globally) it afterwards. Actually the clearing operation is done in a way that does not prohibit the access of the following tokens in the input stream with functions stored in the token register. In other words this function is not exactly the same as calling `\toks_use:N <toks> \toks_clear:N <toks>` in sequence.

<code>\toks_show:N</code>
<code>\toks_show:c</code>

`\toks_show:N <toks>`

Displays the contents of  $\langle toks \rangle$  in the terminal output and log file. # signs in the  $\langle toks \rangle$  will be shown doubled.

**T<sub>E</sub>Xhackers note:** Something like `\showthe <toks>`.

## 57 Adding to the contents of token registers

<code>\toks_put_left:Nn</code>
<code>\toks_put_left:NV</code>
<code>\toks_put_left:No</code>
<code>\toks_put_left:Nx</code>
<code>\toks_put_left:cn</code>
<code>\toks_put_left:cV</code>
<code>\toks_put_left:co</code>

`\toks_put_left:Nn <toks> {\langle token list \rangle}`

These functions will append  $\langle token list \rangle$  to the left of  $\langle toks \rangle$ . Assignment is done locally. If possible append to the right since this operation is faster.

<code>\toks_gput_left:Nn</code>
<code>\toks_gput_left:NV</code>
<code>\toks_gput_left:No</code>
<code>\toks_gput_left:Nx</code>
<code>\toks_gput_left:cn</code>
<code>\toks_gput_left:cV</code>
<code>\toks_gput_left:co</code>

`\toks_gput_left:Nn <toks> {<token list>}`

These functions will append *<token list>* to the left of *<toks>*. Assignment is done globally. If possible append to the right since this operation is faster.

<code>\toks_put_right:Nn</code>
<code>\toks_put_right:NV</code>
<code>\toks_put_right:No</code>
<code>\toks_put_right:Nx</code>
<code>\toks_put_right:cV</code>
<code>\toks_put_right:cn</code>
<code>\toks_put_right:co</code>

`\toks_put_right:Nn <toks> {<token list>}`

These functions will append *<token list>* to the right of *<toks>*. Assignment is done locally.

<code>\toks_put_right:Nf</code>
---------------------------------

`\toks_put_right:Nf <toks> {<token list>}`

Variant of the above. `:Nf` is used by `template.dtx` and will perhaps be moved to that package.

<code>\toks_gput_right:Nn</code>
<code>\toks_gput_right:NV</code>
<code>\toks_gput_right:No</code>
<code>\toks_gput_right:Nx</code>
<code>\toks_gput_right:cn</code>
<code>\toks_gput_right:cV</code>
<code>\toks_gput_right:co</code>

`\toks_gput_right:Nn <toks> {<token list>}`

These functions will append *<token list>* to the right of *<toks>*. Assignment is done globally.

## 58 Predicates and conditionals

<code>\toks_if_empty_p:N *</code>
<code>\toks_if_empty:N<math>\overline{TF}</math> *</code>
<code>\toks_if_empty_p:c *</code>
<code>\toks_if_empty:c<math>\overline{TF}</math> *</code>

`\toks_if_empty:N $\overline{TF}$  <toks> {<true code>} {<false code>}`

Expandable test for whether *<toks>* is empty.

<code>\toks_if_eq:NNTF</code>	<code>*</code>
<code>\toks_if_eq:NcTF</code>	<code>*</code>
<code>\toks_if_eq:cNTF</code>	<code>*</code>
<code>\toks_if_eq:ccTF</code>	<code>*</code>
<code>\toks_if_eq_p:NN</code>	<code>*</code>
<code>\toks_if_eq_p:cN</code>	<code>*</code>
<code>\toks_if_eq_p:Nc</code>	<code>*</code>
<code>\toks_if_eq_p:cc</code>	<code>*</code>

`\toks_if_eq:NNTF`  $\langle toks_1 \rangle$   $\langle toks_2 \rangle$   $\{\langle true\ code \rangle\}$   $\{\langle false\ code \rangle\}$

Expandably tests if  $\langle toks_1 \rangle$  and  $\langle toks_2 \rangle$  are equal.

## 59 Variable and constants

<code>\c_empty_toks</code>
----------------------------

Constant that is always empty.

<code>\l_tmpa_toks</code>
<code>\l_tmpb_toks</code>
<code>\l_tmpc_toks</code>
<code>\g_tmpa_toks</code>
<code>\g_tmpb_toks</code>
<code>\g_tmpc_toks</code>

Scratch register for immediate use. They are not used by conditionals or predicate functions.

<code>\l_tl_replace_toks</code>
---------------------------------

A placeholder for contents of functions replacing contents of strings.

## Part XIV

# The l3seq package

## Sequences

L<sup>A</sup>T<sub>E</sub>X3 implements a data type called ‘sequences’. These are special token lists that can be accessed via special function on the ‘left’. Appending tokens is possible at both ends. Appended token lists can be accessed only as a union. The token lists that form the individual items of a sequence might contain any tokens except two internal functions that are used to structure sequences (see section internal functions below). It is also possible to map functions on such sequences so that they are executed for every item on the sequence.

All functions that return items from a sequence in some  $\langle tl\ var.\rangle$  assume that the  $\langle tl\ var.\rangle$  is local. See remarks below if you need a global returned value.

The defined functions are not orthogonal in the sense that every possible variation possible is actually available. If you need a new variant use the expansion functions described in the package `l3expan` to build it.

Adding items to the left of a sequence can currently be done with either something like `\seq_put_left:Nn` or with a “stack” function like `\seq_push:Nn` which has the same effect. Maybe one should therefore remove the “left” functions totally.

## 60 Functions for creating/initialising sequences

<code>\seq_new:N</code> <code>\seq_new:c</code>	<code>\seq_new:N</code> $\langle sequence \rangle$
--	--

Defines  $\langle sequence \rangle$  to be a variable of type `seq`.

<code>\seq_clear:N</code> <code>\seq_clear:c</code> <code>\seq_gclear:N</code> <code>\seq_gclear:c</code>	<code>\seq_clear:N</code> $\langle sequence \rangle$
--	--

These functions locally or globally clear  $\langle sequence \rangle$ .

<code>\seq_clear_new:N</code> <code>\seq_clear_new:c</code> <code>\seq_gclear_new:N</code> <code>\seq_gclear_new:c</code>	<code>\seq_clear_new:N</code> $\langle sequence \rangle$
--	--

These functions locally or globally clear  $\langle sequence \rangle$  if it exists or otherwise allocates it.

<code>\seq_set_eq:NN</code> <code>\seq_set_eq:cN</code> <code>\seq_set_eq:Nc</code> <code>\seq_set_eq:cc</code>	<code>\seq_set_eq:NN</code> $\langle seq_1 \rangle$ $\langle seq_2 \rangle$
--	---

Function that locally makes  $\langle seq_1 \rangle$  identical to  $\langle seq_2 \rangle$ .

<code>\seq_gset_eq:NN</code> <code>\seq_gset_eq:cN</code> <code>\seq_gset_eq:Nc</code> <code>\seq_gset_eq:cc</code>	<code>\seq_gset_eq:NN</code> $\langle seq_1 \rangle$ $\langle seq_2 \rangle$
--	--

Function that globally makes  $\langle seq_1 \rangle$  identical to  $\langle seq_2 \rangle$ .

<code>\seq_gconcat:NNN</code> <code>\seq_gconcat:ccc</code>
--

`\seq_gconcat:NNN`  $\langle seq_1 \rangle$   $\langle seq_2 \rangle$   $\langle seq_3 \rangle$ 

Function that concatenates  $\langle seq_2 \rangle$  and  $\langle seq_3 \rangle$  and globally assigns the result to  $\langle seq_1 \rangle$ .

## 61 Adding data to sequences

<code>\seq_put_left:Nn</code> <code>\seq_put_left:NV</code> <code>\seq_put_left:No</code> <code>\seq_put_left:Nx</code> <code>\seq_put_left:cn</code> <code>\seq_put_left:cV</code> <code>\seq_put_left:co</code>
---

`\seq_put_left:Nn`  $\langle sequence \rangle$   $\langle token list \rangle$ 

Locally appends  $\langle token list \rangle$  as a single item to the left of  $\langle sequence \rangle$ .  $\langle token list \rangle$  might get expanded before appending according to the variant.

<code>\seq_put_right:Nn</code> <code>\seq_put_right:NV</code> <code>\seq_put_right:No</code> <code>\seq_put_right:Nx</code> <code>\seq_put_right:cn</code> <code>\seq_put_right:cV</code> <code>\seq_put_right:co</code>
--

`\seq_put_right:Nn`  $\langle sequence \rangle$   $\langle token list \rangle$ 

Locally appends  $\langle token list \rangle$  as a single item to the right of  $\langle sequence \rangle$ .  $\langle token list \rangle$  might get expanded before appending according to the variant.

<code>\seq_gput_left:Nn</code> <code>\seq_gput_left:NV</code> <code>\seq_gput_left:No</code> <code>\seq_gput_left:Nx</code> <code>\seq_gput_left:cn</code> <code>\seq_gput_left:cV</code> <code>\seq_gput_left:co</code>
--

`\seq_gput_left:Nn`  $\langle sequence \rangle$   $\langle token list \rangle$ 

Globally appends  $\langle token list \rangle$  as a single item to the left of  $\langle sequence \rangle$ .

<code>\seq_gput_right:Nn</code> <code>\seq_gput_right:NV</code> <code>\seq_gput_right:No</code> <code>\seq_gput_right:Nx</code> <code>\seq_gput_right:cn</code> <code>\seq_gput_right:cV</code> <code>\seq_gput_right:co</code>
---

`\seq_gput_right:Nn`  $\langle sequence \rangle$   $\langle token list \rangle$

Globally appends  $\langle token\ list \rangle$  as a single item to the right of  $\langle sequence \rangle$ .

<code>\seq_gput_right:Nc</code>	Variant of the above used in the <code>xor</code> package. Will probably be moved soon to that package. (Sep 2008)
---------------------------------	--

## 62 Working with sequences

<code>\seq_get:NN</code>	<code>\seq_get:NN</code> $\langle sequence \rangle$ $\langle tl\ var. \rangle$
<code>\seq_get:cN</code>	

Functions that locally assign the left-most item of  $\langle sequence \rangle$  to the token list variable  $\langle tl\ var. \rangle$ . Item is not removed from  $\langle sequence \rangle$ ! If you need a global return value you need to code something like this:

```
\seq_get:NN  $\langle sequence \rangle$  \l_tmpa_tl
\tl_gset_eq:NN  $\langle global\ tl\ var. \rangle$  \l_tmpa_tl
```

But if this kind of construction is used often enough a separate function should be provided.

<code>\seq_map_variable:NNn</code>	<code>\seq_map_variable:NNn</code> $\langle sequence \rangle$ $\langle tl\ var. \rangle$ $\{ \langle code\ using\ tl\ var. \rangle \}$
<code>\seq_map_variable:cNn</code>	

Every element in  $\langle sequence \rangle$  is assigned to  $\langle tl\ var. \rangle$  and then  $\langle code\ using\ tl\ var. \rangle$  is executed. The operation is not expandable which means that it can't be used within write operations etc. However, this function can be nested which the others can't.

<code>\seq_map_function:NN</code>	<code>\seq_map_function:NN</code> $\langle sequence \rangle$ $\langle function \rangle$
<code>\seq_map_function:cN</code>	

This function applies  $\langle function \rangle$  (which must be a function with one argument) to every item of  $\langle sequence \rangle$ .  $\langle function \rangle$  is not executed within a sub-group so that side effects can be achieved locally. The operation is not expandable which means that it can't be used within write operations etc.

In the current implementation the next functions are more efficient and should be preferred.

<code>\seq_map_inline:Nn</code>	<code>\seq_map_inline:Nn</code> $\langle sequence \rangle$ $\{ \langle inline\ function \rangle \}$
<code>\seq_map_inline:cn</code>	

Applies  $\langle inline\ function \rangle$  (which should be the direct coding for a function with one

argument (i.e. use `#1` as the place holder for this argument)) to every item of  $\langle sequence \rangle$ .  $\langle inline function \rangle$  is not executed within a sub-group so that side effects can be achieved locally. The operation is not expandable which means that it can't be used within write operations etc.

<code>\seq_show:N</code>
<code>\seq_show:c</code>

`\seq_show:N  $\langle sequence \rangle$` 

Function that pauses the compilation and displays  $\langle seq \rangle$  in the terminal output and in the log file. (Usually used for diagnostic purposes.)

<code>\seq_display:N</code>
<code>\seq_display:c</code>

`\seq_display:N  $\langle sequence \rangle$` 

As with `\seq_show:N` but pretty prints the output one line per element.

<code>\seq_remove_duplicates:N</code>
<code>\seq_gremove_duplicates:N</code>

`\seq_gremove_duplicates:N  $\langle seq \rangle$` 

Function that removes any duplicate entries in  $\langle seq \rangle$ .

## 63 Predicates and conditionals

<code>\seq_if_empty_p:N *</code>
<code>\seq_if_empty_p:c *</code>

`\seq_if_empty_p:N  $\langle sequence \rangle$` 

This predicate returns 'true' if  $\langle sequence \rangle$  is 'empty' i.e., doesn't contain any items. Note that this is 'false' even if the  $\langle sequence \rangle$  only contains a single empty item.

<code>\seq_if_empty:N<math>\overline{TF}</math></code>
<code>\seq_if_empty:c<math>\overline{TF}</math></code>

`\seq_if_empty:N $\overline{TF}$   $\langle sequence \rangle$   $\{ \langle true code \rangle \} \{ \langle false code \rangle \}$` 

Set of conditionals that test whether or not a particular  $\langle sequence \rangle$  is empty and if so executes either  $\langle true code \rangle$  or  $\langle false code \rangle$ .

<code>\seq_if_in:Nn<math>\overline{TF}</math></code>
<code>\seq_if_in:NV<math>\overline{TF}</math></code>
<code>\seq_if_in:cn<math>\overline{TF}</math></code>
<code>\seq_if_in:cV<math>\overline{TF}</math></code>
<code>\seq_if_in:co<math>\overline{TF}</math></code>
<code>\seq_if_in:cx<math>\overline{TF}</math></code>

`\seq_if_in:Nn $\overline{TF}$   $\langle sequence \rangle$   $\{ \langle item \rangle \} \{ \langle true code \rangle \} \{ \langle false code \rangle \}$` 

Functions that test if  $\langle item \rangle$  is in  $\langle sequence \rangle$ . Depending on the result either  $\langle true code \rangle$  or  $\langle false code \rangle$  is executed.

## 64 Internal functions

<code>\seq_if_empty_err:N</code>
----------------------------------

`\seq_if_empty_err:N <sequence>`

Signals an L<sup>A</sup>T<sub>E</sub>X3 error if *<sequence>* is empty.

<code>\seq_pop_aux:nnNN</code>
--------------------------------

`\seq_pop_aux:nnNN <assign1> <assign2> <sequence> <tl var.>`

Function that assigns the left-most item of *<sequence>* to *<tl var.>* using *<assign<sub>1</sub>>* and assigns the tail to *<sequence>* using *<assign<sub>2</sub>>*. This function could be used to implement a global return function.

<code>\seq_get_aux:w</code>
<code>\seq_pop_aux:w</code>
<code>\seq_put_aux:Nnn</code>
<code>\seq_put_aux:w</code>

Functions used to implement put and get operations. They are not for meant for direct use.

<code>\seq_map_break:</code>
<code>\seq_map_break:n</code>

Functions used to implement mapping operations. They are not for meant for direct use.

<code>\seq_elt:w</code>
<code>\seq_elt_end:</code>

Functions (usually used as constants) that separates items within a sequence. They might get special meaning during mapping operations and are not supposed to show up as tokens within an item appended to a sequence.

## 65 Functions for ‘Sequence Stacks’

Special sequences in L<sup>A</sup>T<sub>E</sub>X3 are ‘stacks’ with their usual operations of ‘push’, ‘pop’, and ‘top’. They are internally implemented as sequences and share some of the functions (like `\seq_new:N` etc.)

<code>\seq_push:Nn</code>
<code>\seq_push:NV</code>
<code>\seq_push:No</code>
<code>\seq_push:cn</code>
<code>\seq_gpush:Nn</code>
<code>\seq_gpush:NV</code>
<code>\seq_gpush:No</code>
<code>\seq_gpush:Nv</code>
<code>\seq_gpush:cn</code>

`\seq_push:Nn <stack> {<token list>}`

Locally or globally pushes *<token list>* as a single item onto the *<stack>*.



<code>\seq_pop:NN</code>
<code>\seq_pop:cN</code>
<code>\seq_gpop:NN</code>
<code>\seq_gpop:cN</code>

`\seq_pop:NN`  $\langle stack \rangle$   $\langle tl\ var. \rangle$

Functions that assign the top item of  $\langle stack \rangle$  to  $\langle tl\ var. \rangle$  and removes it from  $\langle stack \rangle$ !

<code>\seq_top:NN</code>
<code>\seq_top:cN</code>

`\seq_top:NN`  $\langle stack \rangle$   $\langle tl\ var. \rangle$

Functions that locally assign the top item of  $\langle stack \rangle$  to the  $\langle tl\ var. \rangle$ . Item is *not* removed from  $\langle stack \rangle$ !

## Part XV

# The l3clist package

## Comma separated lists

L<sup>A</sup>T<sub>E</sub>X3 implements a data type called ‘clist (comma-lists)’. These are special token lists that can be accessed via special function on the ‘left’. Appending tokens is possible at both ends. Appended token lists can be accessed only as a union. The token lists that form the individual items of a comma-list might contain any tokens except for commas that are used to structure comma-lists (braces are need if commas are part of the value). It is also possible to map functions on such comma-lists so that they are executed for every item of the comma-list.

All functions that return items from a comma-list in some  $\langle tl\ var. \rangle$  assume that the  $\langle tl\ var. \rangle$  is local. See remarks below if you need a global returned value.

The defined functions are not orthogonal in the sense that every possible variation possible is actually available. If you need a new variant use the expansion functions described in the package `l3expan` to build it.

Adding items to the left of a comma-list can currently be done with either something like `\clist_put_left:Nn` or with a “stack” function like `\clist_push:Nn` which has the same effect. Maybe one should therefore remove the “left” functions totally.

## 66 Functions for creating/initialising comma-lists

<code>\clist_new:N</code>
<code>\clist_new:c</code>

`\clist_new:N`  $\langle comma-list \rangle$

Defines  $\langle comma-list \rangle$  to be a variable of type clist.

<code>\clist_clear:N</code>
<code>\clist_clear:c</code>
<code>\clist_gclear:N</code>
<code>\clist_gclear:c</code>

`\clist_clear:N <comma-list>`

These functions locally or globally clear  $\langle comma-list \rangle$ .

<code>\clist_clear_new:N</code>
<code>\clist_clear_new:c</code>
<code>\clist_gclear_new:N</code>
<code>\clist_gclear_new:c</code>

`\clist_clear_new:N <comma-list>`

These functions locally or globally clear  $\langle comma-list \rangle$  if it exists or otherwise allocates it.

<code>\clist_set_eq:NN</code>
<code>\clist_set_eq:cN</code>
<code>\clist_set_eq:Nc</code>
<code>\clist_set_eq:cc</code>

`\clist_set_eq:NN <clist1> <clist2>`

Function that locally makes  $\langle clist_1 \rangle$  identical to  $\langle clist_2 \rangle$ .

<code>\clist_gset_eq:NN</code>
<code>\clist_gset_eq:cN</code>
<code>\clist_gset_eq:Nc</code>
<code>\clist_gset_eq:cc</code>

`\clist_gset_eq:NN <clist1> <clist2>`

Function that globally makes  $\langle clist_1 \rangle$  identical to  $\langle clist_2 \rangle$ .

## 67 Putting data in

<code>\clist_put_left:Nn</code>
<code>\clist_put_left:NV</code>
<code>\clist_put_left:No</code>
<code>\clist_put_left:Nx</code>
<code>\clist_put_left:cn</code>
<code>\clist_put_left:co</code>
<code>\clist_put_left:cV</code>

`\clist_put_left:Nn <comma-list> <token list>`

Locally appends  $\langle token list \rangle$  as a single item to the left of  $\langle comma-list \rangle$ .  $\langle token list \rangle$  might get expanded before appending according to the variant used.

<code>\clist_put_right:Nn</code>
<code>\clist_put_right:No</code>
<code>\clist_put_right:NV</code>
<code>\clist_put_right:Nx</code>
<code>\clist_put_right:cn</code>
<code>\clist_put_right:co</code>
<code>\clist_put_right:cV</code>

`\clist_put_right:Nn`  $\langle comma-list \rangle$   $\langle token list \rangle$

Locally appends  $\langle token list \rangle$  as a single item to the right of  $\langle comma-list \rangle$ .  $\langle token list \rangle$  might get expanded before appending according to the variant used.

<code>\clist_gput_left:Nn</code>
<code>\clist_gput_left:NV</code>
<code>\clist_gput_left:No</code>
<code>\clist_gput_left:Nx</code>
<code>\clist_gput_left:cn</code>
<code>\clist_gput_left:cV</code>
<code>\clist_gput_left:co</code>

`\clist_gput_left:Nn`  $\langle comma-list \rangle$   $\langle token list \rangle$

Globally appends  $\langle token list \rangle$  as a single item to the right of  $\langle comma-list \rangle$ .

<code>\clist_gput_right:Nn</code>
<code>\clist_gput_right:NV</code>
<code>\clist_gput_right:No</code>
<code>\clist_gput_right:Nx</code>
<code>\clist_gput_right:cn</code>
<code>\clist_gput_right:cV</code>
<code>\clist_gput_right:co</code>

`\clist_gput_right:Nn`  $\langle comma-list \rangle$   $\langle token list \rangle$

Globally appends  $\langle token list \rangle$  as a single item to the right of  $\langle comma-list \rangle$ .

## 68 Getting data out

<code>\clist_use:N</code>
<code>\clist_use:c</code>

`\clist_use:N`  $\langle clist \rangle$

Function that inserts the  $\langle clist \rangle$  into the processing stream. Mainly useful if one knows what the  $\langle clist \rangle$  contains, e.g., for displaying the content of template parameters.

<code>\clist_show:N</code>
<code>\clist_show:c</code>

`\clist_show:N`  $\langle clist \rangle$

Function that pauses the compilation and displays  $\langle clist \rangle$  in the terminal output and in the log file. (Usually used for diagnostic purposes.)

<code>\clist_display:N</code>
<code>\clist_display:c</code>

`\clist_display:N <clist>`

As with `\clist_show:N` but pretty prints the output one line per element.

<code>\clist_get:NN</code>
<code>\clist_get:cN</code>

`\clist_get:NN <comma-list> <tl var.>`

Functions that locally assign the left-most item of `<comma-list>` to the token list variable `<tl var.>`. Item is not removed from `<comma-list>`! If you need a global return value you need to code something like this:

```
\clist_get:NN <comma-list> \l_tmpa_tl
\l_gset_eq:NN <global tl var.> \l_tmpa_tl
```

But if this kind of construction is used often enough a separate function should be provided.

## 69 Mapping functions

We provide three types of mapping functions, each with their own strengths. The `\clist_map_function:NN` is expandable whereas `\clist_map_inline:Nn` type uses `##1` as a placeholder for the current item in `<clist>`. Finally we have the `\clist_map_variable:NNn` type which uses a user-defined variable as placeholder. Both the `_inline` and `_variable` versions are nestable.

<code>\clist_map_function:NN</code>
<code>\clist_map_function:cN</code>
<code>\clist_map_function:nN</code>

`\clist_map_function:NN <comma-list> <function>`

This function applies `<function>` (which must be a function with one argument) to every item of `<comma-list>`. `<function>` is not executed within a sub-group so that side effects can be achieved locally. The operation is expandable which means that it can be used within write operations etc.

<code>\clist_map_inline:Nn</code>
<code>\clist_map_inline:cn</code>
<code>\clist_map_inline:nn</code>

`\clist_map_inline:Nn <comma-list> {<inline function>}`

Applies `<inline function>` (which should be the direct coding for a function with one argument (i.e. use `##1` as the placeholder for this argument)) to every item of `<comma-list>`. `<inline function>` is not executed within a sub-group so that side effects can be achieved locally. The operation is not expandable which means that it can't be used within write operations etc. These functions can be nested.

<code>\clist_map_variable:NNn</code> <code>\clist_map_variable:cNn</code> <code>\clist_map_variable:nNn</code>	<code>\clist_map_variable:NNn &lt;comma-list&gt; &lt;temp-var&gt; {\&lt;action&gt;}</code>
--	--

Assigns  $\langle temp-var \rangle$  to each element in  $\langle clist \rangle$  and then executes  $\langle action \rangle$  which should contain  $\langle temp-var \rangle$ . As the operation performs an assignment, it is not expandable.

**TeXhackers note:** These functions resemble the L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> function `\@for` but does not borrow the somewhat strange syntax.

<code>\clist_map_break:</code>	<code>\clist_map_break:</code>
--------------------------------	--------------------------------

For breaking out of a loop. To be used inside TF type functions as in the example below.

```
\cs_new_nopar:Npn \test_function:n #1 {
  \intexpr_compare:nTF {#1 > 3} {\clist_map_break:}{‘‘#1’’}
}
\clist_map_function:nN {1,2,3,4,5,6,7,8}\test_function:n
```

This would return ‘‘1’’‘‘2’’‘‘3’’.

## 70 Predicates and conditionals

<code>\clist_if_empty_p:N</code> <code>\clist_if_empty_p:c</code>	<code>\clist_if_empty_p:N &lt;comma-list&gt;</code>
--	---

This predicate returns ‘true’ if  $\langle comma-list \rangle$  is ‘empty’ i.e., doesn’t contain any tokens.

<code>\clist_if_empty:NTF *</code> <code>\clist_if_empty:cTF *</code>	<code>\clist_if_empty:NTF &lt;comma-list&gt; {\&lt;true code&gt;} {\&lt;false code&gt;}</code>
--	--

Set of conditionals that test whether or not a particular  $\langle comma-list \rangle$  is empty and if so executes either  $\langle true code \rangle$  or  $\langle false code \rangle$ .

<code>\clist_if_eq_p:NN *</code> <code>\clist_if_eq_p:cN *</code> <code>\clist_if_eq_p:Nc *</code> <code>\clist_if_eq_p:cc *</code>	<code>\clist_if_eq_p:N &lt;comma-list<sub>12 </sub></code>
--	--

This predicate returns ‘true’ if the two comma lists are identical.

<code>\clist_if_eq:NNTF *</code>	
<code>\clist_if_eq:cNTF *</code>	
<code>\clist_if_eq:NcTF *</code>	<code>\clist_if_eq:NNTF &lt;comma-list<sub>1</sub>&gt; &lt;comma-list<sub>2</sub>&gt; {&lt;true code&gt;}</code>
<code>\clist_if_eq:ccTF *</code>	<code>{&lt;false code&gt;}</code>

Check if  $\langle comma-list_1 \rangle$  and  $\langle comma-list_2 \rangle$  are equal and execute either  $\langle true code \rangle$  or  $\langle false code \rangle$  accordingly.

<code>\clist_if_in:NnTF</code>	
<code>\clist_if_in:NVTF</code>	
<code>\clist_if_in:NoTF</code>	
<code>\clist_if_in:cnTF</code>	
<code>\clist_if_in:cVTF</code>	<code>\clist_if_in:NnTF &lt;comma-list&gt; {&lt;item&gt;} {&lt;true code&gt;} {&lt;false</code>
<code>\clist_if_in:coTF</code>	<code>code&gt;}</code>

Function that tests if  $\langle item \rangle$  is in  $\langle comma-list \rangle$ . Depending on the result either  $\langle true code \rangle$  or  $\langle false code \rangle$  is executed.

## 71 Higher level functions

<code>\clist_concat:NNN</code>	
<code>\clist_concat:ccc</code>	
<code>\clist_gconcat:NNN</code>	
<code>\clist_gconcat:ccc</code>	<code>\clist_gconcat:NNN &lt;clist<sub>1</sub>&gt; &lt;clist<sub>2</sub>&gt; &lt;clist<sub>3</sub>&gt;</code>

Function that concatenates  $\langle clist_2 \rangle$  and  $\langle clist_3 \rangle$  and locally or globally assigns the result to  $\langle clist_1 \rangle$ .

<code>\clist_remove_duplicates:N</code>	
<code>\clist_gremove_duplicates:N</code>	<code>\clist_gremove_duplicates:N &lt;clist&gt;</code>

Function that removes any duplicate entries in  $\langle clist \rangle$ .

<code>\clist_remove_element:Nn</code>	
<code>\clist_gremove_element:Nn</code>	<code>\clist_gremove_element:Nn &lt;clist&gt; &lt;element&gt;</code>

Function that removes  $\langle element \rangle$  from  $\langle clist \rangle$ , if present.

**T<sub>E</sub>Xhackers note:** This is similar in concept to `\@removeelement`, except that the syntax is clearer and the initial and final lists have the same name automatically.

## 72 Functions for ‘comma-list stacks’

Special comma-lists in L<sup>A</sup>T<sub>E</sub>X3 are ‘stacks’ with their usual operations of ‘push’, ‘pop’, and ‘top’. They are internally implemented as comma-lists and share some of the functions (like `\clist_new:N` etc.)

<code>\clist_push:Nn</code>
<code>\clist_push:NV</code>
<code>\clist_push:No</code>
<code>\clist_push:cn</code>
<code>\clist_gpush:Nn</code>
<code>\clist_gpush:NV</code>
<code>\clist_gpush:No</code>
<code>\clist_gpush:cn</code>

`\clist_push:Nn <stack> {<token list>}`

Locally or globally pushes *<token list>* as a single item onto the *<stack>*. *<token list>* might get expanded before the operation.

<code>\clist_pop:NN</code>
<code>\clist_pop:cn</code>
<code>\clist_gpop:NN</code>
<code>\clist_gpop:cn</code>

`\clist_pop:NN <stack> <tl var.>`

Functions that assign the top item of *<stack>* to the token list variable *<tl var.>* and removes it from *<stack>*!

<code>\clist_top:NN</code>
<code>\clist_top:cn</code>

`\clist_top:NN <stack> <tl var.>`

Functions that locally assign the top item of *<stack>* to the token list variable *<tl var.>*. Item is not removed from *<stack>*!

## 73 Internal functions

<code>\clist_if_empty_err:N</code>
------------------------------------

`\clist_if_empty_err:N <comma-list>`

Signals an L<sup>A</sup>T<sub>E</sub>X3 error if *<comma-list>* is empty.

<code>\clist_pop_aux:nnNN</code>
----------------------------------

`\clist_pop_aux:nnNN <assign1> <assign2> <comma-list> <tl var.>`

Function that assigns the left-most item of *<comma-list>* to *<tl var.>* using *<assign<sub>1</sub>>* and assigns the tail to *<comma-list>* using *<assign<sub>2</sub>>*. This function could be used to implement a global return function.

<code>\clist_get_aux:w</code>
<code>\clist_pop_aux:w</code>
<code>\clist_pop_auxi:w</code>
<code>\clist_put_aux:NNnnNn</code>

Functions used to implement put and get operations. They are not for meant for direct use.

## Part XVI

# The l3prop package

## Property Lists

L<sup>A</sup>T<sub>E</sub>X3 implements a data structure called a ‘property list’ which allows arbitrary information to be stored and accessed using keywords rather than numerical indexing.

A property list might contain a set of keys such as **name**, **age**, and **ID**, which each have individual values that can be saved and retrieved.

## 74 Functions

<code>\prop_new:N</code>
<code>\prop_new:c</code>

`\prop_new:N <prop>`

Defines *<prop>* to be a variable of type *<prop>*.

<code>\prop_clear:N</code>
<code>\prop_clear:c</code>
<code>\prop_gclear:N</code>
<code>\prop_gclear:c</code>

`\prop_clear:N <prop>`

These functions locally or globally clear *<prop>*.



```

\prop_put:Nnn
\prop_put:NnV
\prop_put:NVn
\prop_put:NVV
\prop_put:cnn
\prop_gput:Nnn
\prop_gput:Nno
\prop_gput:NnV
\prop_gput:Nnx
\prop_gput:cnn
\prop_gput:ccx

```

```
\prop_put:Nnn <prop> {<key>} {<token list>}
```

Locally or globally associates *<token list>* with *<key>* in the *<prop>* *<prop>*. If *<key>* has already a meaning within *<prop>* this value is overwritten.

The *<key>* must not contain unescaped # tokens but the *<token list>* may.

```
\prop_gput_if_new:Nnn
```

```
\prop_gput_if_new:Nnn <prop> {<key>} {<token list>}
```

Globally associates *<token list>* with *<key>* in the *<prop>* *<prop>* but only if *<key>* has so far no meaning within *<prop>*. Silently ignored if *<key>* is already set in the *<prop>*.

```

\prop_get:NnN
\prop_get:NVN
\prop_get:cnN
\prop_get:cVN
\prop_gget:NnN
\prop_gget:NVN
\prop_gget:cnN
\prop_gget:cVN

```

```
\prop_get:NnN <prop> {<key>} <tl var.>
```

If *<info>* is the information associated with *<key>* in the *<prop>* *<prop>* then the token list variable *<tl var.>* gets *<info>* assigned. Otherwise its value is the special quark *\q\_no\_value*. The assignment is done either locally or globally.

```

\prop_set_eq:NN
\prop_set_eq:cN
\prop_set_eq:Nc
\prop_set_eq:cc
\prop_gset_eq:NN
\prop_gset_eq:cN
\prop_gset_eq:Nc
\prop_gset_eq:cc

```

```
\prop_set_eq:NN <prop1> <prop2>
```

A fast assignment of *<prop>*s.

```
\prop_get_gdel:NnN
```

```
\prop_get_gdel:NnN <prop> {<key>} <tl var.>
```

Like *\prop\_get:NnN* but additionally removes *<key>* (and its *<info>*) from *<prop>*.

<code>\prop_del:Nn</code>
<code>\prop_del:NV</code>
<code>\prop_gdel:Nn</code>
<code>\prop_gdel:NV</code>

`\prop_del:Nn <prop> {<key>}`

Locally or globally deletes *<key>* and its *<info>* from *<prop>* if found. Otherwise does nothing.

<code>\prop_map_function:NN *</code>
<code>\prop_map_function:cN *</code>
<code>\prop_map_function:Nc *</code>
<code>\prop_map_function:cc *</code>

`\prop_map_function:NN <prop> <function>`

Maps *<function>* which should be a function with two arguments (*<key>* and *<info>*) over every *<key>* *<info>* pair of *<prop>*. Property lists do not have any intrinsic “order” when stored. As a result, you should not expect any particular order to apply when using these mapping functions, even with newly-created properly lists.

<code>\prop_map_inline:Nn</code>
<code>\prop_map_inline:cn</code>

`\prop_map_inline:Nn <prop> {<inline function>}`

Just like `\prop_map_function:NN` but with the function of two arguments supplied as inline code. Within *<inline function>* refer to the arguments via #1 (*<key>*) and #2 (*<info>*). Nestable. Property lists do not have any intrinsic “order” when stored. As a result, you should not expect any particular order to apply when using these mapping functions, even with newly-created properly lists.

<code>\prop_map_break:</code>
-------------------------------

`\prop_map_inline:Nn <prop> {  
... \<break test>:T {\prop_map_break:} }`

For breaking out of a loop. To be used inside TF-type functions as shown in the example above.

<code>\prop_show:N</code>
<code>\prop_show:c</code>

`\prop_show:N <prop>`

Pauses the compilation and shows *<prop>* on the terminal output and in the log file.

<code>\prop_display:N</code>
<code>\prop_display:c</code>

`\prop_display:N <prop>`

As with `\prop_show:N` but pretty prints the output one line per property pair.

## 75 Predicates and conditionals

<code>\prop_if_empty_p:N</code>
<code>\prop_if_empty_p:c</code>

`\prop_if_empty_p:N <prop> {<true code>} {<false code>}`

Predicates to test whether or not a particular  $\langle prop \rangle$  is empty.

$\backslash prop\_if\_empty:N\overline{TF} \star$ $\backslash prop\_if\_empty:c\overline{TF} \star$	$\backslash prop\_if\_empty:N\overline{TF} \langle prop \rangle \{ \langle true\ code \rangle \} \{ \langle false\ code \rangle \}$
--	---

Set of conditionals that test whether or not a particular  $\langle prop \rangle$  is empty.

$\backslash prop\_if\_eq\_p:NN \star$ $\backslash prop\_if\_eq\_p:cN \star$ $\backslash prop\_if\_eq\_p:Nc \star$ $\backslash prop\_if\_eq\_p:cc \star$ $\backslash prop\_if\_eq:NN\overline{TF} \star$ $\backslash prop\_if\_eq:cN\overline{TF} \star$ $\backslash prop\_if\_eq:Nc\overline{TF} \star$ $\backslash prop\_if\_eq:cc\overline{TF} \star$	$\backslash prop\_if\_eq:N\overline{TF} \langle prop_1 \rangle \langle prop_2 \rangle \{ \langle false\ code \rangle \}$
--	--

Execute  $\langle false\ code \rangle$  if  $\langle prop_1 \rangle$  doesn't hold the same token list as  $\langle prop_2 \rangle$ . Only expandable for new versions of pdfTeX.

$\backslash prop\_if\_in:Nn\overline{TF}$ $\backslash prop\_if\_in:N\overline{V}\overline{TF}$ $\backslash prop\_if\_in:No\overline{TF}$ $\backslash prop\_if\_in:cn\overline{TF}$ $\backslash prop\_if\_in:cc\overline{TF}$	$\backslash prop\_if\_in:Nn\overline{TF} \langle prop \rangle \{ \langle key \rangle \} \{ \langle true\ code \rangle \} \{ \langle false\ code \rangle \}$
--	---

Tests if  $\langle key \rangle$  is used in  $\langle prop \rangle$  and then either executes  $\langle true\ code \rangle$  or  $\langle false\ code \rangle$ .

## 76 Internal functions

$\backslash q\_prop$	Quark used to delimit property lists internally.
----------------------	--

$\backslash prop\_put\_aux:w$ $\backslash prop\_put\_if\_new\_aux:w$	Internal functions implementing the put operations.
---	---

$\backslash prop\_get\_aux:w$ $\backslash prop\_gget\_aux:w$ $\backslash prop\_get\_del\_aux:w$ $\backslash prop\_del\_aux:w$	Internal functions implementing the get and delete operations.
--	--

$\backslash prop\_if\_in\_aux:w$	Internal function implementing the key test operation.
----------------------------------	--

`\prop_map_function_aux:w` Internal function implementing the map operations.

`\g_prop_inline_level_int` Integer used in internal name for function used inside `\prop_map_inline:NN`.

`\prop_split_aux:Nnn` `\prop_split_aux:Nnn <prop> <key> <cmd>`  
Internal function that invokes `<cmd>` with 3 arguments: 1st is the beginning of `<prop>` before `<key>`, 2nd is the value associated with `<key>`, 3rd is the rest of `<prop>` after `<key>`. If there is no key `<key>` in `<prop>`, then the 2 arg is `\q_no_value` and the 3rd arg is empty; otherwise the 3rd argument has the two extra tokens `<key> \q_no_value` at the end.  
This function is used to implement various get operations.

## Part XVII

# The l3io package

## Low-level file i/o

TeX is capable of reading from and writing up to 16 individual streams. These i/o operations are accessible in L<sup>A</sup>T<sub>E</sub>X3 with functions from the `\io..` modules. In most cases it will be sufficient for the programmer to use the functions provided by the auxiliary file module, but here are the necessary functions for manipulating private streams.

Sometimes it is not known beforehand how much text is going to be written with a single call. As a result some internal TeX buffer may overflow. To avoid this kind of problem, L<sup>A</sup>T<sub>E</sub>X3 maintains beside direct write operations like `\iow_now:Nx` also so called “long” writes where the output is broken into individual lines on every blank in the text to be written. The resulting files are difficult to read for humans but since they usually serve only as internal storage this poses no problem.

Beside the functions that immediately act (e.g., `\iow_now:Nx`, etc.) we also have deferred operations that are saved away until the next page is finished. This allow to expand the `<tokens>` at the right time to get correct page numbers etc.

## 77 Functions for output streams

`\iow_new:N`  
`\iow_new:c` `\iow_new:N <stream>`

Defines `<stream>` to be a new identifier denoting an output stream for use in subsequent functions.

**T<sub>E</sub>Xhackers note:** `\iow_new:N` corresponds to the plain T<sub>E</sub>X `\newwrite` allocation routine.

<code>\iow_open:Nn</code> <code>\iow_open:cn</code>
--

`\iow_open:Nn <stream> {<file name>}`

Opens output stream `<stream>` to write to `<file name>`. The output stream is immediately available for use. If the `<stream>` was already used as an output stream to some other file, this file gets closed first.<sup>6</sup> Also, all output streams still open at the end of the T<sub>E</sub>X run will be automatically closed.

<code>\iow_close:N</code>
---------------------------

`\iow_close:N <stream>`

Closes output stream `<stream>`.

## 77.1 Immediate writing

<code>\iow_now:Nx</code> <code>\iow_now:Nn</code>
--

`\iow_now:Nx <stream> {<tokens>}`

`\iow_now:Nx` immediately writes the expansion of `<tokens>` to the output stream `<stream>`. If `<stream>` is not open output goes to the terminal. The variant `\iow_now:Nn` writes out `<tokens>` without any further expansion.

**T<sub>E</sub>Xhackers note:** These are the equivalent of T<sub>E</sub>X's `\immediate\write` with and without expansion control.

<code>\iow_log:n</code> <code>\iow_log:x</code> <code>\iow_term:x</code> <code>\iow_term:n</code>
--

`\iow_log:x {<tokens>}`

These functions write to the log file (also known as the transcript file) or to the terminal respectively. They are equivalent to `\iow_now:Nx` where `<stream>` is the transcript file (`\c_iow_log_stream`) or the terminal (`\c_iow_term_stream`).

<code>\iow_now_buffer_safe:Nn</code> <code>\iow_now_buffer_safe:Nx</code>
--

`\iow_now_buffer_safe:Nn <stream> {<tokens>}`

Like `\iow_now:Nx` but splits `<tokens>` at every blank into separate lines. When potentially (very) long token lists are being written, this avoids the problem of buffer overflow when reading back the file.

---

<sup>6</sup>This is a precaution since on some OS it is possible to open the same file for output more than once which then results in some internal errors at the end of the run.

<code>\iow_now_when_avail:Nn</code>
<code>\iow_now_when_avail:cn</code>

`\iow_now_when_avail:Nn <stream> {<tokens>}`

This special function first checks if the  $\langle stream \rangle$  is open for writing. If not it does nothing otherwise it behaves like `\iow_now:Nn`.

## 77.2 Deferred writing

<code>\iow_shipout:Nn</code>
<code>\iow_shipout:Nx</code>

`\iow_shipout_x:Nn <stream> {<tokens>}`

These functions write  $\langle tokens \rangle$  to the specified  $\langle stream \rangle$ , but unlike with `\iow_now:Nn` which write the material immediately, `\iow_shipout:Nn` waits until the processing of the current page has finished.

<code>\iow_shipout_x:Nn</code>
<code>\iow_shipout_x:Nx</code>

`\iow_shipout_x:Nn <stream> {<tokens>}`

More useful than the `\iow_shipout:Nn` functions, these functions also write  $\langle tokens \rangle$  to  $\langle stream \rangle$  at the end of the processing of the current page; however, before  $\langle tokens \rangle$  are written they are subjected to a further `x` expansion stage.

This is useful for writing messages that depend on counters (such as the page number) that are not known until the page has been completed.

`\iow_shipout_x:Nn` always needs `{}` around the second argument.

**T<sub>E</sub>Xhackers note:** `\iow_shipout_x:Nn` is equivalent to T<sub>E</sub>X's `\write`.

## 77.3 Special characters for writing

<code>\iow_newline:</code>
----------------------------

`\iow_newline:`

Function that produces a new line when used within the  $\langle token list \rangle$  that gets written some output stream in non-verbatim mode.

<code>\iow_space:</code>
--------------------------

`\iow_space:`

Function that produces a space when used within the  $\langle token list \rangle$  that gets written to some output stream in an expanding mode.

<code>\iow_char:N</code>
--------------------------

`\iow_space:N \<char>`  
`\iow_space:N \%`

Inserts  $\langle char \rangle$  into the output stream. Useful when trying to write difficult characters such as `%`, `{`, `}`, etc., in messages.

## 78 Functions for input streams

`\ior_new:N` `\ior_new:N`  $\langle stream \rangle$

This function defines  $\langle stream \rangle$  to be a new input stream constant.

**T<sub>E</sub>Xhackers note:** This is the new name and new implementation for plain T<sub>E</sub>X's `\newread`.

`\ior_open:Nn` `\ior_open:Nn`  $\langle stream \rangle$   $\{\langle file name \rangle\}$

This function opens  $\langle stream \rangle$  as an input stream for the external file  $\langle file name \rangle$ . If  $\langle file name \rangle$  doesn't exist or is an empty file the stream is considered to be fully read, a condition which can be tested with `\ior_if_eof:NTF` etc. If  $\langle stream \rangle$  was already used to read from some other file this file will be closed first. The input stream is ready for immediate use.

`\ior_close:N` `\ior_close:N`  $\langle stream \rangle$

This function closes the read stream  $\langle stream \rangle$ .

**T<sub>E</sub>Xhackers note:** This is a new name for `\closein` but it is considered bad practice to make use of this knowledge :-)

`\ior_if_eof_p:N *`  
`\ior_if_eof:NTF *` `\ior_if_eof:NTF`  $\langle stream \rangle$   $\{\langle true code \rangle\}$   $\{\langle false code \rangle\}$

Conditional that tests if some input stream is fully read. The condition is also true if the input stream is not open.

`\if_eof:w` `\if_eof:w`  $\langle stream \rangle$   $\langle true code \rangle$  `\else:`  $\langle false code \rangle$  `\fi:`

**T<sub>E</sub>Xhackers note:** This is the primitive `\ifeof` but we allow only a  $\langle stream \rangle$  and not a plain number after it.

`\ior_to:NN`  
`\ior_gto:NN` `\ior_to:NN`  $\langle stream \rangle$   $\langle tl var. \rangle$

Functions that reads one or more lines (until an equal number of left and right braces are found) from the input stream  $\langle stream \rangle$  and places the result locally or globally into the token list variable. If  $\langle stream \rangle$  is not open, input is requested from the terminal.

## 79 Constants

<code>\c_iow_comment_char</code>
<code>\c_iow_lbrace_char</code>
<code>\c_iow_rbrace_char</code>

Constants that can be used to represent comment character, left and right brace in token lists that should be written to a file.

<code>\c_iow_term_stream</code>
<code>\c_ior_term_stream</code>

Input or output stream denoting the terminal. If used as an input stream the user is prompted with the name of the token list variable (that is used in the call `\ior_to:NN` or `\ior_gto:NN`) followed by an equal sign. If you don't want an automatic prompt of this sort "misuse" `\c_iow_log_stream` as an input stream.

<code>\c_iow_log_stream</code>
<code>\c_ior_log_stream</code>

Output stream that writes only to the transcript file (e.g., the `.log` file on most systems). You may "misuse" this stream as an input stream. In this case it acts as a terminal stream without user prompting.

## Part XVIII

# The `l3msg` package

## Communicating with the user

Messages need to be passed to the user by modules, either when errors occur or to indicate how the code is proceeding. The `l3msg` module provides a consistent method for doing this (as opposed to writing directly to the terminal or log).

The system used by `l3msg` to create messages divides the process into two distinct parts. Named messages are created in the first part of the process; at this stage, no decision is made about the type output that the message will produce. The second part of the process is actually producing a message. At this stage a choice of message *class* has to be made, for example **error**, **warning** or **info**.

By separating out the creation and use of messages, several benefits are available. First, the messages can be altered later without needing details of where they are used in the code. This makes it possible to alter the language used, the detail level and so on. Secondly, the output which results from a given message can be altered. This can be done on a message class, module or message name basis. In this way, message behaviour can be altered and messages can be entirely suppressed.



## 80 Creating new messages

All messages have to be created before they can be used. Inside the message text, spaces are *not* ignored. A space where T<sub>E</sub>X would normally gobble one can be created using `\`, and a new line with `\\`. New lines may have “continuation” text added by the output system.

<pre>\msg_new:nnnn \msg_new:nnn \msg_set:nnnn \msg_set:nnn</pre>	<pre>\msg_new:nnnn {&lt;module&gt;} {&lt;name&gt;} {&lt;text&gt;} {&lt;more text&gt;}</pre>
--	---

Creates new message `<name>` for `<module>` to produce `<text>` initially and `<more text>` if requested by the user. `<text>` and `<more text>` can use up to four macro parameters (#1 to #4), which are supplied by the message system. Inside `<text>` and `<more text>` spaces are not ignored.

## 81 Message classes

Creating message output requires the message to be given a class.

<pre>\msg_class_new:nn \msg_class_set:nn</pre>	<pre>\msg_class_new:nn {&lt;class&gt;} {&lt;code&gt;}</pre>
--	---

Creates new `<class>` to output a message, using `<code>` to process the message text.

The module defines several common message classes. The following describes the standard behaviour of each class if no redirection of the class or message is active.

<pre>\msg_fatal:nnxxxx \msg_fatal:nnxxx \msg_fatal:nnxx \msg_fatal:nnx \msg_fatal:nn</pre>	<pre>\msg_fatal:nnxxxx {&lt;module&gt;} {&lt;name&gt;} {&lt;arg one&gt;} {&lt;arg two&gt;} {&lt;arg three&gt;} {&lt;arg four&gt;}</pre>
--	---

Issues `<module>` error message `<name>`, passing `<arg one>` to `<arg four>` to the text-creating functions. The T<sub>E</sub>X run then halts.

<pre>\msg_error:nnxxxx \msg_error:nnxxx \msg_error:nnxx \msg_error:nnx \msg_error:nn</pre>	<pre>\msg_error:nnxxxx {&lt;module&gt;} {&lt;name&gt;} {&lt;arg one&gt;} {&lt;arg two&gt;} {&lt;arg three&gt;} {&lt;arg four&gt;}</pre>
--	---

Issues `<module>` error message `<name>`, passing `<arg one>` to `<arg four>` to the text-creating functions.

**T<sub>E</sub>Xhackers note:** The standard output here is similar to `\PackageError`.

<pre>\msg_warning:nnxxxx \msg_warning:nnxxx \msg_warning:nnxx \msg_warning:nnx \msg_warning:nn</pre>	<pre>\msg_warning:nnxxxx {&lt;module&gt;} {&lt;name&gt;} {&lt;arg one&gt;} {&lt;arg two&gt;} {&lt;arg three&gt;} {&lt;arg four&gt;}</pre>
--	---

Prints *<module>* message *<name>* to the terminal, passing *<arg one>* to *<arg four>* to the text-creating functions.

**T<sub>E</sub>Xhackers note:** The standard output here is similar to `\PackageWarningNoLine`.

<pre>\msg_info:nnxxxx \msg_info:nnxxx \msg_info:nnxx \msg_info:nnx \msg_info:nn</pre>	<pre>\msg_info:nnxxxx {&lt;module&gt;} {&lt;name&gt;} {&lt;arg one&gt;} {&lt;arg two&gt;} {&lt;arg three&gt;} {&lt;arg four&gt;}</pre>
---	--

Prints *<module>* message *<name>* to the log, passing *<arg one>* to *<arg four>* to the text-creating functions.

**T<sub>E</sub>Xhackers note:** The standard output here is similar to `\PackageInfoNoLine`.

<pre>\msg_log:nnxxxx \msg_log:nnxxx \msg_log:nnxx \msg_log:nnx \msg_log:nn</pre>	<pre>\msg_log:nnxxxx {&lt;module&gt;} {&lt;name&gt;} {&lt;arg one&gt;} {&lt;arg two&gt;} {&lt;arg three&gt;} {&lt;arg four&gt;}</pre>
--	---

Prints *<module>* message *<name>* to the log, passing *<arg one>* to *<arg four>* to the text-creating functions. No continuation text is added.

<pre>\msg_trace:nnxxxx \msg_trace:nnxxx \msg_trace:nnxx \msg_trace:nnx \msg_trace:nn</pre>	<pre>\msg_trace:nnxxxx {&lt;module&gt;} {&lt;name&gt;} {&lt;arg one&gt;} {&lt;arg two&gt;} {&lt;arg three&gt;} {&lt;arg four&gt;}</pre>
--	---

Prints *<module>* message *<name>* to the log, passing *<arg one>* to *<arg four>* to the text-creating functions. No continuation text is added.

```

\msg_none:nnxxxx
\msg_none:nnxxx
\msg_none:nnxx
\msg_none:nnx
\msg_none:nn

```

```

\msg_none:nnxxxx {<module>} {<name>} {<arg one>}
{<arg two>} {<arg three>} {<arg four>}

```

Does nothing: used for redirecting other message classes. Gobbles arguments given.

## 82 Redirecting messages

```

\msg_redirect_class:nn

```

```

\msg_redirect_class:nn {<class one>} {<class two>}

```

Redirect all messages of *<class one>* to appear as those of *<class two>*.

```

\msg_redirect_module:nnn

```

```

\msg_redirect_module:nnn {<module>} {<class one>}
{<class two>}

```

Redirect *<module>* messages of *<class one>* to appear in *<class two>*.

**T<sub>E</sub>Xhackers note:** This function can be used to make some messages “silent” by default. For example, all of the `trace` messages of *<module>* could be turned off with:

```

\msg_redirect_module:nnn { module } { trace } { none }

```

```

\msg_redirect_name:nnn

```

```

\msg_redirect_name:nnn {<module>} {<message>} {<class>}

```

Redirect *<module>* *<message>* to appear using *<class>*.

## 83 Support functions for output

```

\msg_line_context:

```

```

\msg_line_context:

```

Prints the current line number preceded by `\c_msg_on_line_tl`.

```

\msg_line_number:

```

```

\msg_line_number:

```

Prints the current line number.

<code>\msg_newline:</code> <code>\msg_two_newlines:</code>	<code>\msg_newline:</code>
---	----------------------------

Print one or two newlines with no continuation information.

<code>\msg_space:</code> <code>\msg_two_spaces:</code> <code>\msg_four_spaces:</code>	<code>\msg_space:</code>
---	--------------------------

Print one, two or four spaces: needed where a literal space would otherwise be gobbled by T<sub>E</sub>X.

## 84 Low-level functions

The low-level functions do not make assumptions about module names. The output functions here produce messages directly, and do not respond to redirection.

<code>\msg_generic_new:nnn</code> <code>\msg_generic_new:nn</code> <code>\msg_generic_set:nnn</code> <code>\msg_generic_set:nn</code>	<code>\msg_generic_new:nnn</code> $\langle name \rangle$ $\langle text \rangle$ $\langle more text \rangle$
--	---

Creates new message  $\langle name \rangle$  to produce  $\langle text \rangle$  initially and  $\langle more text \rangle$  if requested by the user.  $\langle text \rangle$  and  $\langle more text \rangle$  can use up to four macro parameters (#1 to #4), which are supplied by the message system. Inside  $\langle text \rangle$  and  $\langle more text \rangle$  spaces are not ignored.

<code>\msg_direct_interrupt:xxxx</code>	<code>\msg_direct_interrupt:xxxxn</code> $\langle first line \rangle$ $\langle text \rangle$ $\langle continuation \rangle$ $\langle more text \rangle$
---	--

Executes a T<sub>E</sub>X error, interrupting compilation. The  $\langle first line \rangle$  is displayed followed by  $\langle text \rangle$  and the input prompt.  $\langle more text \rangle$  is displays if requested by the user. If  $\langle more text \rangle$  is blank a default is supplied. Each line of  $\langle text \rangle$  (broken with `\\`) begins with  $\langle continuation \rangle$ .

<code>\msg_direct_log:xx</code> <code>\msg_direct_term:xx</code>	<code>\msg_direct_log:xx</code> $\langle text \rangle$ $\langle continuation \rangle$
---	---

Prints  $\langle text \rangle$  to either the log or terminal. New lines (broken with `\\`) start with  $\langle continuation \rangle$ .

## 85 Kernel-specific functions

<pre>\msg_kernel_new:nnnn \msg_kernel_new:nnn \msg_kernel_set:nnnn \msg_kernel_set:nnn</pre>	<pre>\msg_kernel_new:nnnn {&lt;division&gt;} {&lt;name&gt;} {&lt;text&gt;} {&lt;more text&gt;}</pre>
--	--

Creates new kernel message  $\langle name \rangle$  to produce  $\langle text \rangle$  initially and  $\langle more\ text \rangle$  if requested by the user.  $\langle text \rangle$  and  $\langle more\ text \rangle$  can use up to four macro parameters (#1 to #4), which are supplied by the message system. Kernel messages are divided into  $\langle divisions \rangle$ , roughly equivalent to the L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> package names used.

<pre>\msg_kernel_fatal:nnxxxx \msg_kernel_fatal:nnxxx \msg_kernel_fatal:nnxx \msg_kernel_fatal:nnx \msg_kernel_fatal:nn</pre>	<pre>\msg_kernel_fatal:nnxx {&lt;division&gt;} {&lt;name&gt;} {&lt;arg one&gt;} {&lt;arg two&gt;} {&lt;arg three&gt;} {&lt;arg four&gt;}</pre>
---	--

Issues kernel error message  $\langle name \rangle$  for  $\langle division \rangle$ , passing  $\langle arg\ one \rangle$  to  $\langle arg\ four \rangle$  to the text-creating functions. The T<sub>E</sub>X run then halts. Cannot be redirected.

<pre>\msg_kernel_error:nnxxxx \msg_kernel_error:nnxxx \msg_kernel_error:nnxx \msg_kernel_error:nnx \msg_kernel_error:nn</pre>	<pre>\msg_kernel_error:nnxx {&lt;division&gt;} {&lt;name&gt;} {&lt;arg one&gt;} {&lt;arg two&gt;} {&lt;arg three&gt;} {&lt;arg four&gt;}</pre>
---	--

Issues kernel error message  $\langle name \rangle$  for  $\langle division \rangle$ , passing  $\langle arg\ one \rangle$  to  $\langle arg\ four \rangle$  to the text-creating functions. Cannot be redirected.

<pre>\msg_kernel_warning:nnxxxx \msg_kernel_warning:nnxxx \msg_kernel_warning:nnxx \msg_kernel_warning:nnx \msg_kernel_warning:nn</pre>	<pre>\msg_kernel_warning:nnxx {&lt;division&gt;} {&lt;name&gt;} {&lt;arg one&gt;} {&lt;arg two&gt;} {&lt;arg three&gt;} {&lt;arg four&gt;}</pre>
---	--

Prints kernel message  $\langle name \rangle$  for  $\langle division \rangle$  to the terminal, passing  $\langle arg\ one \rangle$  to  $\langle arg\ four \rangle$  to the text-creating functions.

<pre> \msg_kernel_info:nnxxxx \msg_kernel_info:nnxxx \msg_kernel_info:nnxx \msg_kernel_info:nnx \msg_kernel_info:nn </pre>	<pre> \msg_kernel_info:nxx {&lt;division&gt;} {&lt;name&gt;} {&lt;arg one&gt;} {&lt;arg two&gt;} {&lt;arg three&gt;} {&lt;arg four&gt;} </pre>
--	--

Prints kernel message  $\langle name \rangle$  for  $\langle division \rangle$  to the log, passing  $\langle arg one \rangle$  to  $\langle arg four \rangle$  to the text-creating functions.

<pre> \msg_kernel_bug:x </pre>	<pre> \msg_kernel_bug:x {&lt;text&gt;} </pre>
--------------------------------	---

Short-cut for “This is a LaTeX bug: check coding” errors.

## 86 Variables and constants

<pre> \c_msg_fatal_tl \c_msg_error_tl \c_msg_warning_tl \c_msg_info_tl </pre>
---

Simple headers for errors.

<pre> \c_msg_fatal_text_tl \c_msg_help_text_tl \c_msg_kernel_bug_text_tl \c_msg_kernel_bug_more_text_tl \c_msg_no_info_text_tl \c_msg_return_text_tl </pre>
---

Various pieces of text for use in messages, which are not changed by the code here although they could be to alter the language.

<pre> \c_msg_on_line_tl </pre>	<p>The “on line” phrase for line numbers.</p>
--------------------------------	---

<pre> \c_msg_text_prefix_tl \c_msg_more_text_prefix_tl </pre>
---

Header information for storing the “paths” to parts of a message.

<pre> \l_msg_class_tl \l_msg_current_class_tl </pre>
--

Information about message method, used for filtering.

<pre> \l_msg_names_clist </pre>
---------------------------------

List of all of the message names defined.

<code>\l_msg_redirect_classes_prop</code> <code>\l_msg_redirect_names_prop</code>
--

Re-direction lists containing the class of message to convert an different one.

<code>\l_msg_redirect_classes_clist</code>
--

List so that filtering does not loop.

## Part XIX

# The l3box package

## Boxes

There are three kinds of box operations: horizontal mode denoted with prefix `\hbox_`, vertical mode with prefix `\vbox_`, and the generic operations working in both modes with prefix `\box_`.

## 87 Generic functions

<code>\box_new:N</code> <code>\box_new:c</code>
--

`\box_new:N`  $\langle box \rangle$   
 Defines  $\langle box \rangle$  to be a new variable of type `box`.

**T<sub>E</sub>Xhackers note:** `\box_new:N` is the equivalent of plain T<sub>E</sub>X's `\newbox`. However, the internal register allocation is done differently.

<code>\if_hbox:N</code> <code>\if_vbox:N</code> <code>\if_box_empty:N</code>
--

`\if_hbox:N`  $\langle box \rangle$   $\langle true\ code \rangle$  `\else:`  $\langle false\ code \rangle$  `\fi:`  
`\if_box_empty:N`  $\langle box \rangle$   $\langle true\ code \rangle$  `\else:`  $\langle false\ code \rangle$  `\fi:`  
`\if_hbox:N` and `\if_vbox:N` check if  $\langle box \rangle$  is an horizontal or vertical box resp.  
`\if_box_empty:N` tests if  $\langle box \rangle$  is empty (void) and executes `code` according to the test outcome.

**T<sub>E</sub>Xhackers note:** These are the T<sub>E</sub>X primitives `\ifhbox`, `\ifvbox` and `\ifvoid`.

<code>\box_if_horizontal_p:N</code> <code>\box_if_horizontal_p:c</code> <code>\box_if_horizontal:NTF</code> <code>\box_if_horizontal:cTF</code>
--

`\box_if_horizontal:NTF`  $\langle box \rangle$   $\{ \langle true\ code \rangle \}$   $\{ \langle false\ code \rangle \}$

Tests if  $\langle box \rangle$  is an horizontal box and executes  $\langle code \rangle$  accordingly.

$\backslash\text{box\_if\_vertical\_p:N}$ $\backslash\text{box\_if\_vertical\_p:c}$ $\backslash\text{box\_if\_vertical:N}\textit{TF}$ $\backslash\text{box\_if\_vertical:c}\textit{TF}$	$\backslash\text{box\_if\_vertical:N}\textit{TF} \quad \langle box \rangle \{ \langle true\ code \rangle \} \{ \langle false\ code \rangle \}$
--	--

Tests if  $\langle box \rangle$  is a vertical box and executes  $\langle code \rangle$  accordingly.

$\backslash\text{box\_if\_empty\_p:N}$ $\backslash\text{box\_if\_empty\_p:c}$ $\backslash\text{box\_if\_empty:N}\textit{TF}$ $\backslash\text{box\_if\_empty:c}\textit{TF}$	$\backslash\text{box\_if\_empty:N}\textit{TF} \quad \langle box \rangle \{ \langle true\ code \rangle \} \{ \langle false\ code \rangle \}$
--	---

Tests if  $\langle box \rangle$  is empty (void) and executes `code` according to the test outcome.

**T<sub>E</sub>Xhackers note:**  $\backslash\text{box\_if\_empty:N}\textit{TF}$  is the L<sup>A</sup>T<sub>E</sub>X3 function name for  $\backslash\text{ifvoid}$ .

$\backslash\text{box\_set\_eq:NN}$ $\backslash\text{box\_set\_eq:cN}$ $\backslash\text{box\_set\_eq:Nc}$ $\backslash\text{box\_set\_eq:cc}$	$\backslash\text{box\_set\_eq:NN} \quad \langle box_1 \rangle \langle box_2 \rangle$
--	--

Sets  $\langle box_1 \rangle$  equal to  $\langle box_2 \rangle$ . Note that this eradicates the contents of  $\langle box_2 \rangle$  afterwards.

$\backslash\text{box\_gset\_eq:NN}$ $\backslash\text{box\_gset\_eq:cN}$ $\backslash\text{box\_gset\_eq:Nc}$ $\backslash\text{box\_gset\_eq:cc}$	$\backslash\text{box\_gset\_eq:NN} \quad \langle box_1 \rangle \langle box_2 \rangle$
--	---

Globally sets  $\langle box_1 \rangle$  equal to  $\langle box_2 \rangle$ .

$\backslash\text{box\_set\_to\_last:N}$ $\backslash\text{box\_set\_to\_last:c}$ $\backslash\text{box\_gset\_to\_last:N}$ $\backslash\text{box\_gset\_to\_last:c}$	$\backslash\text{box\_set\_to\_last:N} \quad \langle box \rangle$
--	---

Sets  $\langle box \rangle$  equal to the previous box  $\backslash\text{l\_last\_box}$  and removes  $\backslash\text{l\_last\_box}$  from the current list (unless in outer vertical or math mode).

$\backslash\text{box\_move\_right:nn}$ $\backslash\text{box\_move\_left:nn}$ $\backslash\text{box\_move\_up:nn}$ $\backslash\text{box\_move\_down:nn}$	$\backslash\text{box\_move\_left:nn} \quad \{ \langle dimen \rangle \} \{ \langle box\ function \rangle \}$
---	---

Moves  $\langle box\ function \rangle \langle dimen \rangle$  in the direction specified.  $\langle box\ function \rangle$  is either an operation on a box such as  $\backslash\text{box\_use:N}$  or a “raw” box specification like  $\backslash\text{vbox:n}\{\text{xyz}\}$ .



<code>\box_clear:N</code>
<code>\box_clear:c</code>
<code>\box_gclear:N</code>
<code>\box_gclear:c</code>

`\box_clear:N     $\langle box \rangle$` 

Clears  $\langle box \rangle$  by setting it to the constant `\c_void_box`. `\box_gclear:N` does it globally.

<code>\box_use:N</code>
<code>\box_use:c</code>
<code>\box_use_clear:N</code>
<code>\box_use_clear:c</code>

`\box_use:N     $\langle box \rangle$`   
`\box_use_clear:N    $\langle box \rangle$` 

`\box_use:N` puts a copy of  $\langle box \rangle$  on the current list while `\box_use_clear:N` puts the box on the current list and then eradicates the contents of it.

**T<sub>E</sub>Xhackers note:** `\box_use:N` and `\box_use_clear:N` are the T<sub>E</sub>X primitives `\copy` and `\box` with new (descriptive) names.

<code>\box_ht:N</code>
<code>\box_ht:c</code>
<code>\box_dp:N</code>
<code>\box_dp:c</code>
<code>\box_wd:N</code>
<code>\box_wd:c</code>

`\box_ht:N     $\langle box \rangle$` 

Returns the height, depth, and width of  $\langle box \rangle$  for use in dimension settings.

**T<sub>E</sub>Xhackers note:** These are the T<sub>E</sub>X primitives `\ht`, `\dp` and `\wd`.

<code>\box_show:N</code>
<code>\box_show:c</code>

`\box_show:N     $\langle box \rangle$` 

Writes the contents of  $\langle box \rangle$  to the log file.

**T<sub>E</sub>Xhackers note:** This is the T<sub>E</sub>X primitive `\showbox`.

<code>\c_empty_box</code>
<code>\l_tmpa_box</code>
<code>\l_tmpb_box</code>

`\c_empty_box` is the constantly empty box. The others are scratch boxes.

<code>\l_last_box</code>
--------------------------

`\l_last_box` is more or less a read-only box register managed by the engine. It denotes

the last box on the current list if there is one, otherwise it is void. You can set other boxes to this box, with the result that the last box on the current list is removed at the same time (so it is with variable with side-effects).

## 88 Horizontal mode

<code>\hbox:n</code>	<code>\hbox:n {&lt;contents&gt;}</code>
----------------------	---

Places a `hbox` of natural size.

<code>\hbox_set:Nn</code> <code>\hbox_set:cn</code> <code>\hbox_gset:Nn</code> <code>\hbox_gset:cn</code>	<code>\hbox_set:Nn &lt;box&gt; {&lt;contents&gt;}</code>
--	--

Sets `<box>` to be a vertical mode box containing `<contents>`. It has it's natural size. `\hbox_gset:Nn` does it globally.

<code>\hbox_set_to_wd:Nnn</code> <code>\hbox_set_to_wd:cnn</code> <code>\hbox_gset_to_wd:Nnn</code> <code>\hbox_gset_to_wd:cnn</code>	<code>\hbox_set_to_wd:Nnn &lt;box&gt; {&lt;dimen&gt;} {&lt;contents&gt;}</code>
--	---

Sets `<box>` to contain `<contents>` and have width `<dimen>`. `\hbox_gset_to_wd:Nn` does it globally.

<code>\hbox_to_wd:nn</code> <code>\hbox_to_zero:n</code>	<code>\hbox_to_wd:nn {&lt;dimen&gt;} &lt;contents&gt;</code> <code>\hbox_to_zero:n &lt;contents&gt;</code>
---	---

Places a `<box>` of width `<dimen>` containing `<contents>`. `\hbox_to_zero:n` is a shorthand for a width of zero.

<code>\hbox_set_inline_begin:N</code> <code>\hbox_set_inline_begin:c</code> <code>\hbox_set_inline_end:</code> <code>\hbox_gset_inline_begin:N</code> <code>\hbox_gset_inline_begin:c</code> <code>\hbox_gset_inline_end:</code>	<code>\hbox_set_inline_begin:N &lt;box&gt; &lt;contents&gt;</code> <code>\hbox_set_inline_end:</code>
---	--

Sets `<box>` to contain `<contents>`. This type is useful for use in environment definitions.

<code>\hbox_unpack:N</code> <code>\hbox_unpack:c</code> <code>\hbox_unpack_clear:N</code> <code>\hbox_unpack_clear:c</code>	<code>\hbox_unpack:N</code> $\langle box \rangle$
--	---

`\hbox_unpack:N` unpacks the contents of the  $\langle box \rangle$  register and `\hbox_unpack_clear:N` also clears the  $\langle box \rangle$  after unpacking it.

**T<sub>E</sub>Xhackers note:** These are the T<sub>E</sub>X primitives `\unhcopy` and `\unhbox`.

## 89 Vertical mode

<code>\vbox:n</code>	<code>\vbox:n</code> $\{\langle contents \rangle\}$
----------------------	---

Places a `vbox` of natural size with baseline equal to the baseline of the last line in the box.

<code>\vbox_set:Nn</code> <code>\vbox_set:cn</code> <code>\vbox_gset:Nn</code> <code>\vbox_gset:cn</code>	<code>\vbox_set:Nn</code> $\langle box \rangle$ $\{\langle contents \rangle\}$
--	--

Sets  $\langle box \rangle$  to be a vertical mode box containing  $\langle contents \rangle$ . It has its natural size. `\vbox_gset:Nn` does it globally.

<code>\vbox_set_to_ht:Nnn</code> <code>\vbox_set_to_ht:cnn</code> <code>\vbox_gset_to_ht:Nnn</code> <code>\vbox_gset_to_ht:cnn</code> <code>\vbox_gset_to_ht:ccn</code>	<code>\vbox_set_to_ht:Nnn</code> $\langle box \rangle$ $\{\langle dimen \rangle\}$ $\{\langle contents \rangle\}$
---	---

Sets  $\langle box \rangle$  to contain  $\langle contents \rangle$  and have total height  $\langle dimen \rangle$ . `\vbox_gset_to_ht:Nn` does it globally.

<code>\vbox_set_inline_begin:N</code> <code>\vbox_set_inline_end:</code> <code>\vbox_gset_inline_begin:N</code> <code>\vbox_gset_inline_end:</code>	<code>\vbox_set_inline_begin:N</code> $\langle box \rangle$ $\langle contents \rangle$ <code>\vbox_set_inline_end:</code>
--	--

Sets  $\langle box \rangle$  to contain  $\langle contents \rangle$ . This type is useful for use in environment definitions.

<code>\vbox_set_split_to_ht:NNn</code>	<code>\vbox_set_split_to_ht:NNn &lt;box<sub>1</sub>&gt; &lt;box<sub>2</sub>&gt; {&lt;dimen&gt;}</code>
--	--

Sets  $\langle box_1 \rangle$  to contain the top  $\langle dimen \rangle$  part of  $\langle box_2 \rangle$ .

**T<sub>E</sub>Xhackers note:** This is the T<sub>E</sub>X primitive `\vsplit`.

<code>\vbox_to_ht:nn</code>	<code>\vbox_to_ht:nn {&lt;dimen&gt;} &lt;contents&gt;</code>
<code>\vbox_to_zero:n</code>	<code>\vbox_to_zero:n &lt;contents&gt;</code>

Places a  $\langle box \rangle$  of size  $\langle dimen \rangle$  containing  $\langle contents \rangle$ .

<code>\vbox_unpack:N</code>	<code>\vbox_unpack:N &lt;box&gt;</code>
<code>\vbox_unpack:c</code>	
<code>\vbox_unpack_clear:N</code>	
<code>\vbox_unpack_clear:c</code>	

`\vbox_unpack:N` unpacks the contents of the  $\langle box \rangle$  register and `\vbox_unpack_clear:N` also clears the  $\langle box \rangle$  after unpacking it.

**T<sub>E</sub>Xhackers note:** These are the T<sub>E</sub>X primitives `\unvcopy` and `\unvbox`.

## Part XX

# The l3xref package

## Cross references

<code>\xref_set_label:n</code>	<code>\xref_set_label:n {&lt;name&gt;}</code>
--------------------------------	---

Sets a label in the text. Note that this function does not do anything else than setting the correct labels. In particular, it does not try to fix any spacing around the write node; this is a task for the `galley2` module.

<code>\xref_new:nn</code>	<code>\xref_new:nn {&lt;type&gt;} {&lt;value&gt;}</code>
---------------------------	--

Defines a new cross reference type  $\langle type \rangle$ . This defines the token list variable `\l_xref_curr_<type>_tl` with default value  $\langle value \rangle$  which gets written fully expanded when `\xref_set_label:n` is called.

<code>\xref_deferred_new:nn</code>	<code>\xref_deferred_new:nn {&lt;type&gt;} {&lt;value&gt;}</code>
------------------------------------	---

Same as `\xref_new:n` except for this one, the value written happens when TeX ships out the page. Page numbers use this one obviously.

<code>\xref_get_value:nn *</code>	<code>\xref_get_value:nn {&lt;type&gt;} {&lt;name&gt;}</code>
-----------------------------------	---

Extracts the cross reference information of type `<type>` for the label `<name>`. This operation is expandable.

## Part XXI

# The l3keyval package

## Key-value parsing

This module only provides functions for extracting keys and values from a list. How this information is used is up to the programmer. The `l3keys` module provides a higher-level interface for managing run-time key-value input.

A `<keyval list>` is a list consisting of

```
key 1 = value 1 ,
key 2      ,
key 3 = value 3 ,
```

The function names for retrieving the keys and values are long but explain what they do. All these functions start with the name `\KV_parse_`. If a value is surrounded by braces, one level (and only one) is removed from the value. This is useful if you need to input a value which contains `=` or `,.` There are two primary actions we can take on a `<keyval list>`.

- A `<keyval list>` can be sanitized so that top level active commas or equal signs are converted into catcode 12. When declaring templates in the preamble one can probably safely assume that there are no active commas or equals; these things should only be active in the document. The name for this is either `no_sanitize` or `sanitize`.
- Spaces on either side of a key or value can be trimmed. When using the LaTeX3 programming interface, spaces are automatically ignored so there it would be a waste of time to search for extra spaces since there would be none. At the document level however, spaces must be removed. The name for this is either `no_space_removal` or `space_removal`. Note that when `space_removal` is called you get an additional option where you can decide if one level of braces should be stripped from the key and/or value; see the description of the boolean `\l_KV_remove_one_level_of_braces_bool` for details.

During the parsing process, keys or values are not expanded and no #s are doubled. When the parsing process is over, the keys and values are executed in the form

```
\KV_key_value_elt:nn{key 1}{value 1}
\KV_key_no_value_elt:n{key 2}
\KV_key_value_elt:nn{key 3}{value 3}
```

It is up to the programmer to provide a suitable definition of these two functions before starting the parsing process.

## 90 Functions

<code>\KV_parse_no_space_removal_no_sanitize:n</code>	<code>\KV_parse_no_space_removal_no_sanitize:n {&lt;keyval list&gt;}</code>
---	---

Parses the keys and values literally. For use when spaces are ignored and = and , have normal catcodes.

<code>\KV_parse_space_removal_no_sanitize:n</code>	<code>\KV_parse_space_removal_no_sanitize:n {&lt;keyval list&gt;}</code>
--	--

As above but also removes spaces around keys and values. For use when spaces are not ignored.

<code>\KV_parse_space_removal_sanitize:n</code>	<code>\KV_parse_space_removal_sanitize:n {&lt;keyval list&gt;}</code>
---	---

As above but additionally also replaces top-level active = and , with harmless versions.

<code>\l_KV_remove_one_level_of_braces_bool</code>
--

This boolean controls whether or not one level of braces is stripped from the key and value. The default value for this boolean is *true* so that exactly one level of braces is stripped. For certain applications it is desirable to keep the braces in which case the programmer just has to set the boolean false temporarily. Setting this boolean has no effect when you call the `no_space_removal` functions since not stripping braces is a rare request and would clutter the otherwise elegant code of the `no_space_removal` functions for very little gain. If you need to preserve braces choose the slower `space_removal` functions.

<code>\KV_key_no_value_elt:n</code>	<code>\KV_key_no_value_elt:n {&lt;key&gt;}</code>
<code>\KV_key_value_elt:nn</code>	<code>\KV_key_value_elt:n {&lt;key&gt;} {&lt;value&gt;}</code>

Functions returned by the `\KV_parse_` functions. The default definition of these two functions is an error message!

## Part XXII

# The l3keys package

## Key–value support

The key–value method is a popular system for creating large numbers of settings for controlling function or package behaviour. For the user, the system normally results in input of the form

```
\PackageControlMacro{
  key-one = value one,
  key-two = value two
}
```

or

```
\PackageMacro[
  key-one = value one,
  key-two = value two
]{argument}.
```

For the programmer, the original keyval package gives only the most basic interface for this work. All key macros have to be created one at a time, and as a result the kvoptions and xkeyval packages have been written to extend the ease of creating keys. A very different approach has been provided by the pgfkeys package, which uses a key–value list to generate keys.

The l3keys package is aimed at creating a programming interface for key–value controls in L<sup>A</sup>T<sub>E</sub>X3. Keys are created using a key–value interface, in a similar manner to pgfkeys. Each key is created by setting one or more *properties* of the key:

```
\keys_define:nn { module }
  key-one .code:n = code including parameter #1,
  key-two .set   = \l_module_store_tl
}
```

These values can then be set as with other key–value approaches:

```
\keys_set:nn { module }
  key-one = value one,
  key-two = value two
}
```

At a document level, `\keys_set:nn` is used within a document function. For L<sup>A</sup>T<sub>E</sub>X2<sub>ε</sub>, a generic set up function could be created with

```

\newcommand*\SomePackageSetup[1]{%
  \@nameuse{keys_set:nn}{module}{#1}%
}

```

or to use key–value input as the optional argument for a macro:

```

\newcommand*\SomePackageMacro[2][{}]{%
  \begingroup
    \@nameuse{keys_set:nn}{module}{#1}%
    % Main code for \SomePackageMacro
  \endgroup
}

```

The same concepts using `xparse` for L<sup>A</sup>T<sub>E</sub>X3 use:

```

\DeclareDocumentCommand \SomePackageSetup { m } {
  \keys_set:nn { module } { #1 }
}
\DeclareDocumentCommand \SomePackageMacro { o m } {
  \group_begin:
    \keys_set:nn { module } { #1 }
    % Main code for \SomePackageMacro
  \group_end:
}

```

Key names may contain any tokens, as they are handled internally using `\tl_to_str:n`. As will be discussed in section 90.2, it is suggested that the character “/” is reserved for sub-division of keys into logical groups. Macros are *not* expanded when creating key names, and so

```

\tl_set:Nn \l_module_tmp_tl { key }
\keys_define:nn { module } {
  \l_module_tmp_tl .code:n = code
}

```

will create a key called `\l_module_tmp_tl`, and not one called `key`.

## 90.1 Creating keys

`\keys_define:nn` `\keys_define:nn {<module>} {<keyval list>}`

Parses the *<keyval list>* and defines the keys listed there for *<module>*. This function is designed for use in code, and therefore does not check the category codes of characters or ignore spaces.



Setting up and altering keys is carried out using one or more properties. The properties determine how a key acts, and may require zero, one or two argument: this is indicated by an argument specifier, in the same way as a standard L<sup>A</sup>T<sub>E</sub>X3 function.

<code>.bool_set:N</code> <code>.bool_gset:N</code>	$\langle key \rangle$ <code>.bool_set:N</code> = $\langle bool \rangle$
---	---

Defines  $\langle key \rangle$  to set  $\langle bool \rangle$  to  $\langle value \rangle$  (which must be either `true` or `false`).

<code>.choice:</code>	$\langle key \rangle$ <code>.choice:</code>
-----------------------	---

Sets  $\langle key \rangle$  to act as a multiple choice key. Creating choices is discussed in section 90.3.

<code>.choice_code:n</code> <code>.choice_code:x</code>	$\langle key \rangle$ <code>.choice_code:n</code> = $\langle code \rangle$
--	--

Stores  $\langle code \rangle$  for use when `.generate_choices:n` creates one or more choice sub-keys of the current key. Inside  $\langle code \rangle$ , `\l_keys_choice_tl` contains the name of the choice made, and `\l_keys_choice_int` is the position of the choice in the list given to `.generate_choices:n`.

<code>.code:n</code> <code>.code:x</code>	$\langle key \rangle$ <code>.code:n</code> = $\langle code \rangle$
--	---

Stores the  $\langle code \rangle$  for execution when  $\langle key \rangle$  is called. The  $\langle code \rangle$  can include one parameter (#1), which will be the  $\langle value \rangle$  given for the  $\langle key \rangle$ .

<code>.default:n</code> <code>.default:V</code>	$\langle key \rangle$ <code>.default:n</code> = $\langle default \rangle$
--	---

Creates a  $\langle default \rangle$  value for  $\langle key \rangle$ , which is used if no value is given. This will be used if only the key name is given, but not if a blank  $\langle value \rangle$  is given:

```

\keys_define:nn { module } {
  key .code:n      = Hello #1,
  key .default:n = World
}
\keys_set:nn { module} {
  key = Fred, % Prints "Hello Fred"
  key,      % Prints "Hello World"
  key = ,    % Prints "Hello "
}

```

**T<sub>E</sub>Xhackers note:** The  $\langle default \rangle$  is stored as a token list variable.

```
.dim_set:N
.dim_set:c
.dim_gset:N
.dim_gset:c
```

$\langle key \rangle$  .dim\_set:N =  $\langle dimension \rangle$

Sets  $\langle key \rangle$  to store the value it is given in  $\langle dimension \rangle$ , which is created if it does not already exist.

```
.generate_choices:n
```

$\langle key \rangle$  .generate\_choices:n =  $\langle comma list \rangle$

Makes  $\langle key \rangle$  a multiple choice key, accepting the choices specified in  $\langle comma list \rangle$ . Each choice will execute code which should previously have been defined using .choice\_code:n or .choice\_code:x.

```
.int_set:N
.int_set:c
.int_gset:N
.int_gset:c
```

$\langle key \rangle$  .int\_set:N =  $\langle integer \rangle$

Sets  $\langle key \rangle$  to store the value it is given in  $\langle integer \rangle$ , which is created if it does not already exist.

```
.meta:n
.meta:x
```

$\langle key \rangle$  .meta:n =  $\langle keys \rangle$

Makes  $\langle key \rangle$  a meta-key, which will set several other  $\langle keys \rangle$  in one go. If  $\langle key \rangle$  is given with a value, it is passed through to the subsidiary  $\langle keys \rangle$  for processing.

```
.skip_set:N
.skip_set:c
.skip_gset:N
.skip_gset:c
```

$\langle key \rangle$  .skip\_set:N =  $\langle skip \rangle$

Sets  $\langle key \rangle$  to store the value it is given in  $\langle skip \rangle$ , which is created if it does not already exist.

```
.tl_set:N
.tl_set:c
.tl_set_x:N
.tl_set_x:c
.tl_gset:N
.tl_gset:c
.tl_gset_x:N
.tl_gset_x:c
```

$\langle key \rangle$  .tl\_set:N =  $\langle token list variable \rangle$

Sets  $\langle key \rangle$  to store the value it is given in  $\langle token list variable \rangle$ , which is created if it does not already exist. The x type properties perform an expansion as well as storing the value.

<code>.value_forbidden:</code> <code>.value_required:</code>	<code>&lt;key&gt; .value_forbidden:</code>
---	--

Flags for forbidding and requiring a *<value>* for *<key>*. Any *<value>* given will be ignored.

## 90.2 Sub-dividing keys

When creating large numbers of keys, it may be desirable to divide them into several sub-groups for a given module. This can be achieved either by adding a sub-division to the module name:

```
\keys_define:nn { module / subgroup } {
  key .code:n = code
}
```

or to the key name:

```
\keys_define:nn { module } {
  subgroup / key .code:n = code
}
```

As illustrated, the best choice of token for sub-dividing keys in this way is “/”. This is because of the method that is used to represent keys internally. Both of the above code fragments set the same key, which has full name `module/subgroup/key`.

As will be illustrated in the next section, this subdivision is particularly relevant to making multiple choices.

## 90.3 Multiple choices

Multiple choices are created by setting the `.choice:` property:

```
\keys_define:nn { module } {
  key .choice:
}
```

For keys which are set up as choices, the valid choices are generated by creating sub-keys of the choice key. This can be carried out in two ways.

In many cases, choices execute similar code which is dependant only on the name of the choice or the position of the choice in the list of choices. Here, the keys can share the same code, and can be rapidly created using the `.choice_code:n` and `.generate_choices:n` properties:

```
\keys_define:nn { module } {
  key .choice_code:n = {
```

```

    You~gave~choice~‘‘\l_keys_choice_tl’’,~
    which~is~in~position~
    \int_use:N\l_keys_choice_int\space
    in~the~list.
  },
  key .generate_choices:n = {
    choice-a, choice-b, choice-c
  }
}

```

Following common computing practice, `\l_keys_choice_int` starts from 0 for the first choice. This means that it can be used directly with `\if_case:w` and so on.

<code>\l_keys_choice_tl</code> <code>\l_keys_choice_int</code>
---

Inside the code block, the variables `\l_keys_choice_tl` and `\l_keys_choice_int` are available to indicate the name of the current choice, and its position in the comma list. The position is indexed from 1.

On the other hand, it is sometimes useful to create choices which use entirely different code from one another. This can be achieved by setting the `.choice:` property of a key, then manually defining sub-keys.

```

\keys_define:nn { module } {
  key .choice:n,
  key / choice-a .code:n = code-a,
  key / choice-b .code:n = code-b,
  key / choice-c .code:n = code-c,
}

```

It is possible to mix the two methods, but manually-created choices should *not* use `\l_keys_choice_tl` or `\l_keys_choice_int`.

## 90.4 Setting keys

<code>\keys_set:nn</code> <code>\keys_set:nV</code> <code>\keys_set:nv</code>
---

`\keys_set:nn {<module>} {<keyval list>}`  
 Parses the `<keyval list>`, and sets those keys which are defined for `<module>`. The behaviour on finding an unknown key can be set by defining a special `unknown` key: this will be illustrated later. In contrast to `\keys_define:nn`, this function does check category codes and ignore spaces, and is therefore suitable for user input.

If a key is not known, `\keys_set:nn` will look for a special `unknown` key for the same module. This mechanism can be used to create new keys from user input.

```

\keys_define:nn { module } {
  unknown .code:n =
    You~tried~to~set~key~'\l_keys_path_tl'~to~'#1'
}

```

`\l_keys_key_tl` When processing an unknown key, the name of the key is available as `\l_keys_key_tl`. Note that this will have been processed using `\tl_to_str:N`. The value passed to the key (if any) is available as the macro parameter `#1`.

## 90.5 Examining keys: internal representation

`\keys_if_exist:nnTF` `\keys_if_exist:nnTF {<module>} {<key>} {<true code>} {<false code>}`

Tests if `<key>` exists for `<module>`, by checking for the existence of the internal function `\keys > <module>/<key>.cmd:n`.

`\keys_show:nn` `\keys_show:nn {<module>} {<key>}`

Shows the internal representation of a `<key>`. The function which executes a `<key>` is called `\keys > <module>/<key>.cmd:n`.

## 90.6 Internal functions

`\keys_bool_set:NN` `\keys_bool_set:NN <bool> <scope>`

Creates code to set `<bool>` when `<key>` is given, with setting using `<scope>`.

`\keys_choice_code_store:x` `\keys_choice_code_store:x <code>`

Stores `<code>` for later use by `.generate_code:n`.

`\keys_choice_make:` `\keys_choice_make:`

Makes `<key>` a choice key.

`\keys_choices_generate:n` `\keys_choices_generate:n {<comma list>}`

Makes `<comma list>` choices for `<key>`.

`\keys_choice_find:n` `\keys_choice_find:n {<choice>}`

Searches for `<choice>` as a sub-key of `<key>`.

<code>\keys_cmd_set:nn</code>
<code>\keys_cmd_set:nx</code>

`\keys_cmd_set:nn {⟨path⟩} {⟨code⟩}`  
 Creates a function for *⟨path⟩* using *⟨code⟩*.

<code>\keys_default_set:n</code>
<code>\keys_default_set:V</code>

`\keys_default_set:n {⟨default⟩}`  
 Sets *⟨default⟩* for *⟨key⟩*.

<code>\keys_define_elt:n</code>
<code>\keys_define_elt:nn</code>

`\keys_define_elt:nn {⟨key⟩} {⟨value⟩}`  
 Processing functions for key–value pairs when defining keys.

<code>\keys_define_key:n</code>
---------------------------------

`\keys_define_key:n {⟨key⟩}`  
 Defines *⟨key⟩*.

<code>\keys_execute:</code>
-----------------------------

`\keys_execute:`  
 Executes *⟨key⟩*.

<code>\keys_execute_unknown:</code>
-------------------------------------

`\keys_execute_unknown:`

Handles unknown *⟨key⟩* names.

<code>\keys_if_value_requirement:nTF</code>
---

`\keys_if_value_requirement:nTF {⟨requirement⟩} {⟨true code⟩} {⟨false code⟩}`

Check if *⟨requirement⟩* applies to *⟨key⟩*.

<code>\keys_meta_make:n</code>
<code>\keys_meta_make:x</code>

`\keys_meta_make:n {⟨keys⟩}`  
 Makes *⟨key⟩* a meta-key to set *⟨keys⟩*.

<code>\keys_property_find:n</code>
------------------------------------

`\keys_property_find:n {⟨key⟩}`

Separates *⟨key⟩* from *⟨property⟩*.

<code>\keys_property_new:nn</code>
<code>\keys_property_new_arg:nn</code>

`\keys_property_new:nn {⟨property⟩} {⟨code⟩}`

Makes a new  $\langle property \rangle$  expanding to  $\langle code \rangle$ . The **arg** version makes properties with one argument.

<code>\keys_property_undefine:n</code>	<code>\keys_property_undefine:n {<math>\langle property \rangle</math>}</code>
--	--

Deletes  $\langle property \rangle$  of  $\langle key \rangle$ .

<code>\keys_set_elt:n</code>	<code>\keys_set_elt:nn {<math>\langle key \rangle</math>} {<math>\langle value \rangle</math>}</code>
<code>\keys_set_elt:nn</code>	

Processing functions for key–value pairs when setting keys.

<code>\keys_tmp:w</code>	<code>\keys_tmp:w <math>\langle args \rangle</math></code>
--------------------------	--

Used to store  $\langle code \rangle$  to execute a  $\langle key \rangle$ .

<code>\keys_value_or_default:n</code>	<code>\keys_value_or_default:n {<math>\langle value \rangle</math>}</code>
---------------------------------------	--

Sets `\l_keys_value_toks` to  $\langle value \rangle$ , or  $\langle default \rangle$  if  $\langle value \rangle$  was not given and if  $\langle default \rangle$  is available.

<code>\keys_value_requirement:n</code>	<code>\keys_value_requirement:n {<math>\langle requirement \rangle</math>}</code>
--	---

Sets  $\langle key \rangle$  to have  $\langle requirement \rangle$  concerning  $\langle value \rangle$ .

<code>\keys_variable_set:NnNN</code>	<code>\keys_variable_set:NnNN <math>\langle var \rangle</math> <math>\langle type \rangle</math> <math>\langle scope \rangle</math> <math>\langle expansion \rangle</math></code>
<code>\keys_variable_set:cnNN</code>	

Sets  $\langle key \rangle$  to assign  $\langle value \rangle$  to  $\langle variable \rangle$ . The  $\langle scope \rangle$  (blank for local, **g** for global) and  $\langle type \rangle$  (**tl**, **int**, etc.) are given explicitly.

## 90.7 Variables and constants

<code>\c_keys_properties_root_tl</code>	The root paths for keys and properties.
<code>\c_keys_root_tl</code>	

<code>\c_keys_value_forbidden_tl</code>	Marker text containers.
<code>\c_keys_value_required_tl</code>	

<code>\l_keys_choice_code_tl</code>	Used to transfer code from storage when making multiple choices.
-------------------------------------	--

<code>\l_keys_module_tl</code> <code>\l_keys_path_tl</code> <code>\l_keys_property_tl</code>
--

Various key paths need to be stored.

<code>\l_keys_nesting_seq</code> <code>\l_keys_nesting_tl</code>
---

To allow safe nesting of `\keys_define:nn` and `\keys_set:nn`.

<code>\l_keys_no_value_bool</code>
------------------------------------

A marker for “no value” as key input.

<code>\l_keys_value_toks</code>
---------------------------------

Holds the currently supplied value.

## Part XXIII

# The l3calc package

## Infix notation arithmetic in L<sup>A</sup>T<sub>E</sub>X3

This is pretty much a straight adaption of the `calc` package and as such has same syntax for the *calc expression*. However, there are some noticeable differences.

- The `calc` expression is expanded fully, which means there are no problems with unfinished conditionals. However, the contents of `\widthof` etc. is not expanded at all. This includes uses in traditional L<sup>A</sup>T<sub>E</sub>X as in the `array` package, which tries to do an `\edef` several times. The code used in `l3calc` provides self-protection for these cases.
- Muskip registers are supported although they can only be used in `\ratio` if already evaluating a muskip expression. For the other three register types, you can use points.
- All results are rounded, not truncated. More precisely, the primitive T<sub>E</sub>X operations `\divide` and `\multiply` are not used. The only instance where one will observe an effect is when dividing integers.

This version of `l3calc` is now a complete replacement for the original `calc` package providing the same functionality and will prevent the original `calc` package from loading.



## 91 User functions

<code>\maxof</code>
<code>\minof</code>
<code>\widthof</code>
<code>\heightof</code>
<code>\depthof</code>
<code>\totalheightof</code>
<code>\ratio</code>
<code>\real</code>
<code>\setlength</code>
<code>\gsetlength</code>
<code>\addtolength</code>
<code>\gaddtolength</code>
<code>\setcounter</code>
<code>\addtocounter</code>
<code>\stepcounter</code>

See documentation for L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> package `calc`.

<code>\calc_maxof:nn</code>
<code>\calc_minof:nn</code>
<code>\calc_widthof:n</code>
<code>\calc_heightof:n</code>
<code>\calc_depthof:n</code>
<code>\calc_totalheightof:n</code>
<code>\calc_ratio:nn</code>
<code>\calc_real:n</code>
<code>\calc_setcounter:nn</code>
<code>\calc_addtocounter:nn</code>
<code>\calc_stepcounter:n</code>

Equivalent commands as the above in the `expl3` namespace.

<code>\calc_int_set:Nn</code>
<code>\calc_int_gset:Nn</code>
<code>\calc_int_add:Nn</code>
<code>\calc_int_gadd:Nn</code>
<code>\calc_int_sub:Nn</code>
<code>\calc_int_gsub:Nn</code>

`\calc_int_set:Nn` *<int>* {*<calc expression>*}

Evaluates *<calc expression>* and either adds or subtracts it from *<int>* or sets *<int>* to it. These operations can also be global.

<code>\calc_dim_set:Nn</code>
<code>\calc_dim_gset:Nn</code>
<code>\calc_dim_add:Nn</code>
<code>\calc_dim_gadd:Nn</code>
<code>\calc_dim_sub:Nn</code>
<code>\calc_dim_gsub:Nn</code>

`\calc_dim_set:Nn <dim> {<calc expression>}`

Evaluates  $\langle calc\ expression \rangle$  and either adds or subtracts it from  $\langle dim \rangle$  or sets  $\langle dim \rangle$  to it. These operations can also be global.

<code>\calc_skip_set:Nn</code>
<code>\calc_skip_gset:Nn</code>
<code>\calc_skip_add:Nn</code>
<code>\calc_skip_gadd:Nn</code>
<code>\calc_skip_sub:Nn</code>
<code>\calc_skip_gsub:Nn</code>

`\calc_skip_set:Nn <skip> {<calc expression>}`

Evaluates  $\langle calc\ expression \rangle$  and either adds or subtracts it from  $\langle skip \rangle$  or sets  $\langle skip \rangle$  to it. These operations can also be global.

<code>\calc_muskip_set:Nn</code>
<code>\calc_muskip_gset:Nn</code>
<code>\calc_muskip_add:Nn</code>
<code>\calc_muskip_gadd:Nn</code>
<code>\calc_muskip_sub:Nn</code>
<code>\calc_muskip_gsub:Nn</code>

`\calc_muskip_set:Nn <muskip> {<calc expression>}`

Evaluates  $\langle calc\ expression \rangle$  and either adds or subtracts it from  $\langle muskip \rangle$  or sets  $\langle muskip \rangle$  to it. These operations can also be global.

<code>\calc_calculate_box_size:nnn</code>
---

`\calc_calculate_box_size:nnn {<dim-set>}`  
`{<item1> <item2> ... <itemn>} {<contents>}`

Sets  $\langle contents \rangle$  in a temporary box `\l_tmpa_box`. Then  $\langle dim-set \rangle$  is put in front of a loop that inserts  $+ \langle item_i \rangle$  in front of `\l_tmpa_box` and this is evaluated. For instance, if we wanted to determine the total height of the text `xyz` and store it in `\l_tmpa_dim`, we would call it as.

```
\calc_calculate_box_size:nnn
  {\dim_set:Nn\l_tmpa_dim}{\box_ht:N\box_dp:N}{xyz}
```

Similarly, if we wanted the difference between height and depth, we could call it as

```
\calc_calculate_box_size:nnn
  {\dim_set:Nn\l_tmpa_dim}{\box_ht:N{-\box_dp:N}}{xyz}
```

## Part XXIV

# The l3file package

## File Loading

### 92 Loading files

The need to test if a file is available and to load a file if found is covered at a low level here.

```
\file_if_exist_p:n  
\file_if_exist:nTF \file_if_exist:nTF <file> <true code> <false code>
```

Tests if *<file>* exists.

**T<sub>E</sub>Xhackers note:** This is L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub>'s `\IfFileExists`, although it does not return name of the file (*cf.* `\@filef@und`).

```
\file_add_path:nN \file_add_path:nN <file> <tl var.>
```

Searches for *<file>* on the T<sub>E</sub>X path and using `\l_file_search_path_clist`. If *<file>* is found, *<tl var.>* is set to the file name plus any path information needed. If *<file>* is not found, *<tl var.>* will be blank.

**T<sub>E</sub>Xhackers note:** This is similar to obtaining `\@filef@und` from L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub>'s `\IfFileExists`.

```
\file_input:n \file_input:n <file>
```

Inputs *<file>* if it found (according to the same rule as for `\file_if_exist:n`).

**T<sub>E</sub>Xhackers note:** This acts in a similar way to L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub>'s `\input`, as it will not lead to a T<sub>E</sub>X loop if the file is not found.

```
\file_input_no_record:n \file_input_no_record:n <file>
```

Inputs *<file>* if it found (according to the same rule as for `\file_if_exist:n`, but does not add it to `\g_file_record_clist`. The file is still added to `\g_file_record_full_clist`.

**T<sub>E</sub>Xhackers note:** This is similar to L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub>'s `\@input@`.

<code>\file_input_no_check:n</code> <code>\file_input_no_check_no_record:n</code>	<code>\file_input_no_check:n</code> $\langle file \rangle$
--	--

Inputs  $\langle file \rangle$  directly without checking if it exists. The `no_record` version does not record the input in

**T<sub>E</sub>Xhackers note:** `\g_file_record_clist`. These are simple wrappers around the T<sub>E</sub>X `\input` primitive

<code>\file_list:</code> <code>\file_list_full:</code>	<code>\file_list:</code> $\langle file \rangle$
---	---

Lists files loaded in current L<sup>A</sup>T<sub>E</sub>X run: the `full` version lists all files.

## 93 Variables and constants

<code>\g_file_record_clist</code> <code>\g_file_record_full_clist</code>	Used to track the files that have been loaded.
---	--

<code>\l_file_search_path_clist</code>	List of paths to search for a file in addition to those searched by T <sub>E</sub> X.
--	---

**T<sub>E</sub>Xhackers note:** This is `\input@path` in L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub>.

<code>\l_file_test_read_stream</code>	Input stream used to carry out file tests.
---------------------------------------	--

<code>\l_file_tmp_bool</code>	Internal scratch switch.
-------------------------------	--------------------------

<code>\l_file_tmp_tl</code>	Internal scratch token list variable.
-----------------------------	---------------------------------------

## Part XXV

# Implementation

## 94 l3names implementation

This is the base part of L<sup>A</sup>T<sub>E</sub>X 3 defining things like `catcodes` and redefining the T<sub>E</sub>X primitives, as well as setting up the code to load `expl3` modules in L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub>.

## 94.1 Internal functions

<code>\ExplSyntaxStatus</code> <code>\ExplSyntaxPopStack</code> <code>\ExplSyntaxStack</code>
---

Functions used to track the state of the catcode regime.

<code>\@pushfilename</code> <code>\@popfilename</code>
---

Re-definitions of L<sup>A</sup>T<sub>E</sub>X's file-loading functions to support `\ExplSyntax`.

## 94.2 Package loading

Before anything else, check that we're using  $\varepsilon$ -T<sub>E</sub>X; no point continuing otherwise.

```

1 <*initex | package>
2 \begingroup
3 \def\firstoftwo#1#2{#1}
4 \def\secondoftwo#1#2{#2}
5 \def\etexmissingerror{Not running under e-TeX}
6 \def\etexmissinghelp{%
7   This package requires e-TeX.^^J%
8   Try compiling the document with 'elatex' instead of 'latex'.^^J%
9   When using pdfTeX, try 'pdfelatex' instead of 'pdflatex'%
10 }%
11 \expandafter\ifx\csname eTeXversion\endcsname\relax
12   \expandafter\secondoftwo\else\expandafter\firstoftwo\fi
13   {\endgroup}{%
14 <initex>      \expandafter\errhelp\expandafter{\etexmissinghelp}%
15 <initex>      \expandafter\errmessage\expandafter{\etexmissingerror}%
16 <package>    \PackageError{13names}{\etexmissingerror}{\etexmissinghelp}%
17   \endgroup
18   \endinput
19 }
20 </initex | package>
```

## 94.3 Catcode assignments

Catcodes for `\begingroup`, `\endgroup`, macro parameter, superscript, and `\tab`, are all assigned before the start of the documented code. (See the beginning of `13names.dtx`.)

Reason for `\endlinechar=32` is that a line ending with a backslash will be interpreted as the token `\_` which seems most natural and since spaces are ignored it works as we intend elsewhere.

Before we do this we must however record the settings for the catcode regime as it was when we start changing it.

```

21 <*initex | package>
22 \edef\ExplSyntaxOff{
23   \unexpanded{\ifodd \ExplSyntaxStatus\relax
24     \def\ExplSyntaxStatus{0}
25   }
26   \catcode 126=\the \catcode 126 \relax
27   \catcode 32=\the \catcode 32 \relax
28   \catcode 9=\the \catcode 9 \relax
29   \endlinechar =\the \endlinechar \relax
30   \catcode 95=\the \catcode 95 \relax
31   \catcode 58=\the \catcode 58 \relax
32   \noexpand\fi
33 }
34 \catcode126=10\relax % tilde is a space char.
35 \catcode32=9\relax   % space is ignored
36 \catcode9=9\relax    % tab also ignored
37 \endlinechar=32\relax % newline is space
38 \catcode95=11\relax  % underscore letter
39 \catcode58=11\relax  % colon letter

```

## 94.4 Setting up primitive names

Here is the function that renames T<sub>E</sub>X’s primitives.

Normally the old name is left untouched, but the possibility of undefining the original names is made available by `docstrip` and package options. If nothing else, this gives a way of checking what ‘old code’ a package depends on...

If the package option ‘`removeoldnames`’ is used then some trick code is run after the end of this file, to skip past the code which has been inserted by L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> to manage the file name stack, this code would break if run once the T<sub>E</sub>X primitives have been undefined. (What a surprise!) **The option has been temporarily disabled.**

To get things started, give a new name for `\let`.

```

40 \let \tex_let:D \let
41 </initex | package>

```

and now an internal function to possibly remove the old name: for the moment.

```

42 <*initex>
43 \long \def \name_undefine:N #1 {
44   \tex_let:D #1 \c_undefined
45 }
46 </initex>

```

```

47 <*package>
48 \DeclareOption{removeoldnames}{
49   \long\def\name_undefine:N#1{
50     \tex_let:D#1\c_undefined}}

51 \DeclareOption{keepoldnames}{
52   \long\def\name_undefine:N#1{}}

53 \ExecuteOptions{keepoldnames}

54 \ProcessOptions
55 </package>

```

The internal function to give the new name and possibly undefine the old name.

```

56 <*initex | package>
57 \long \def \name_primitive:NN #1#2 {
58   \tex_let:D #2 #1
59   \name_undefine:N #1
60 }

```

## 94.5 Reassignment of primitives

In the current incarnation of this package, all T<sub>E</sub>X primitives are given a new name of the form `\tex_<oldname>:D`. But first three special cases which have symbolic original names. These are given modified new names, so that they may be entered without catcode tricks.

```

61 \name_primitive:NN \          \tex_space:D
62 \name_primitive:NN \/        \tex_italiccor:D
63 \name_primitive:NN \-        \tex_hyphen:D

```

Now all the other primitives.

```

64 \name_primitive:NN \let      \tex_let:D
65 \name_primitive:NN \def      \tex_def:D
66 \name_primitive:NN \edef     \tex_edef:D
67 \name_primitive:NN \gdef     \tex_gdef:D
68 \name_primitive:NN \xdef     \tex_xdef:D
69 \name_primitive:NN \chardef  \tex_chardef:D
70 \name_primitive:NN \countdef \tex_countdef:D
71 \name_primitive:NN \dimendef \tex_dimendef:D
72 \name_primitive:NN \skipdef  \tex_skipdef:D
73 \name_primitive:NN \muskipdef \tex_muskipdef:D
74 \name_primitive:NN \mathchardef \tex_mathchardef:D
75 \name_primitive:NN \toksdef  \tex_toksdef:D
76 \name_primitive:NN \futurelet \tex_futurelet:D
77 \name_primitive:NN \advance  \tex_advance:D
78 \name_primitive:NN \divide   \tex_divide:D
79 \name_primitive:NN \multiply \tex_multiply:D

```

80	\name_primitive:NN \font	\tex_font:D
81	\name_primitive:NN \fam	\tex_fam:D
82	\name_primitive:NN \global	\tex_global:D
83	\name_primitive:NN \long	\tex_long:D
84	\name_primitive:NN \outer	\tex_outer:D
85	\name_primitive:NN \setlanguage	\tex_setlanguage:D
86	\name_primitive:NN \globaldefs	\tex_globaldefs:D
87	\name_primitive:NN \afterassignment	\tex_afterassignment:D
88	\name_primitive:NN \aftergroup	\tex_aftergroup:D
89	\name_primitive:NN \expandafter	\tex_expandafter:D
90	\name_primitive:NN \noexpand	\tex_noexpand:D
91	\name_primitive:NN \begingroup	\tex_begingroup:D
92	\name_primitive:NN \endgroup	\tex_endgroup:D
93	\name_primitive:NN \halign	\tex_halign:D
94	\name_primitive:NN \valign	\tex_valign:D
95	\name_primitive:NN \cr	\tex_cr:D
96	\name_primitive:NN \crcr	\tex_crcr:D
97	\name_primitive:NN \noalign	\tex_noalign:D
98	\name_primitive:NN \omit	\tex_omit:D
99	\name_primitive:NN \span	\tex_span:D
100	\name_primitive:NN \tabskip	\tex_tabskip:D
101	\name_primitive:NN \everycr	\tex_everycr:D
102	\name_primitive:NN \if	\tex_if:D
103	\name_primitive:NN \ifcase	\tex_ifcase:D
104	\name_primitive:NN \ifcat	\tex_ifcat:D
105	\name_primitive:NN \ifnum	\tex_ifnum:D
106	\name_primitive:NN \ifodd	\tex_ifodd:D
107	\name_primitive:NN \ifdim	\tex_ifdim:D
108	\name_primitive:NN \ifeof	\tex_ifeof:D
109	\name_primitive:NN \ifhbox	\tex_ifhbox:D
110	\name_primitive:NN \ifvbox	\tex_ifvbox:D
111	\name_primitive:NN \ifvoid	\tex_ifvoid:D
112	\name_primitive:NN \ifx	\tex_ifx:D
113	\name_primitive:NN \iffalse	\tex_iffalse:D
114	\name_primitive:NN \iftrue	\tex_iftrue:D
115	\name_primitive:NN \ifhmode	\tex_ifhmode:D
116	\name_primitive:NN \ifmmode	\tex_ifmmode:D
117	\name_primitive:NN \ifvmode	\tex_ifvmode:D
118	\name_primitive:NN \ifinner	\tex_ifinner:D
119	\name_primitive:NN \else	\tex_else:D
120	\name_primitive:NN \fi	\tex_fi:D
121	\name_primitive:NN \or	\tex_or:D
122	\name_primitive:NN \immediate	\tex_immediate:D
123	\name_primitive:NN \closeout	\tex_closeout:D
124	\name_primitive:NN \openin	\tex_openin:D
125	\name_primitive:NN \openout	\tex_openout:D
126	\name_primitive:NN \read	\tex_read:D
127	\name_primitive:NN \write	\tex_write:D
128	\name_primitive:NN \closein	\tex_closein:D
129	\name_primitive:NN \newlinechar	\tex_newlinechar:D



130	\name_primitive:NN	\input	\tex_input:D
131	\name_primitive:NN	\endinput	\tex_endinput:D
132	\name_primitive:NN	\inputlineno	\tex_inputlineno:D
133	\name_primitive:NN	\errmessage	\tex_errmessage:D
134	\name_primitive:NN	\message	\tex_message:D
135	\name_primitive:NN	\show	\tex_show:D
136	\name_primitive:NN	\showthe	\tex_showthe:D
137	\name_primitive:NN	\showbox	\tex_showbox:D
138	\name_primitive:NN	\showlists	\tex_showlists:D
139	\name_primitive:NN	\errhelp	\tex_errhelp:D
140	\name_primitive:NN	\errorcontextlines	\tex_errorcontextlines:D
141	\name_primitive:NN	\tracingcommands	\tex_tracingcommands:D
142	\name_primitive:NN	\tracinglostchars	\tex_tracinglostchars:D
143	\name_primitive:NN	\tracingmacros	\tex_tracingmacros:D
144	\name_primitive:NN	\tracingonline	\tex_tracingonline:D
145	\name_primitive:NN	\tracingoutput	\tex_tracingoutput:D
146	\name_primitive:NN	\tracingpages	\tex_tracingpages:D
147	\name_primitive:NN	\tracingparagraphs	\tex_tracingparagraphs:D
148	\name_primitive:NN	\tracingrestores	\tex_tracingrestores:D
149	\name_primitive:NN	\tracingstats	\tex_tracingstats:D
150	\name_primitive:NN	\pausing	\tex_pausing:D
151	\name_primitive:NN	\showboxbreadth	\tex_showboxbreadth:D
152	\name_primitive:NN	\showboxdepth	\tex_showboxdepth:D
153	\name_primitive:NN	\batchmode	\tex_batchmode:D
154	\name_primitive:NN	\errorstopmode	\tex_errorstopmode:D
155	\name_primitive:NN	\nonstopmode	\tex_nonstopmode:D
156	\name_primitive:NN	\scrollmode	\tex_scrollmode:D
157	\name_primitive:NN	\end	\tex_end:D
158	\name_primitive:NN	\csname	\tex_csname:D
159	\name_primitive:NN	\endcsname	\tex_endcsname:D
160	\name_primitive:NN	\ignorespaces	\tex_ignorespaces:D
161	\name_primitive:NN	\relax	\tex_relax:D
162	\name_primitive:NN	\the	\tex_the:D
163	\name_primitive:NN	\mag	\tex_mag:D
164	\name_primitive:NN	\language	\tex_language:D
165	\name_primitive:NN	\mark	\tex_mark:D
166	\name_primitive:NN	\topmark	\tex_topmark:D
167	\name_primitive:NN	\firstmark	\tex_firstmark:D
168	\name_primitive:NN	\botmark	\tex_botmark:D
169	\name_primitive:NN	\splitfirstmark	\tex_splitfirstmark:D
170	\name_primitive:NN	\splitbotmark	\tex_splitbotmark:D
171	\name_primitive:NN	\fontname	\tex_fontname:D
172	\name_primitive:NN	\escapechar	\tex_escapechar:D
173	\name_primitive:NN	\endlinechar	\tex_endlinechar:D
174	\name_primitive:NN	\mathchoice	\tex_mathchoice:D
175	\name_primitive:NN	\delimiter	\tex_delimiter:D
176	\name_primitive:NN	\mathaccent	\tex_mathaccent:D
177	\name_primitive:NN	\mathchar	\tex_mathchar:D
178	\name_primitive:NN	\mskip	\tex_mskip:D
179	\name_primitive:NN	\radical	\tex_radical:D

180	\name_primitive:NN	\vcenter	\tex_vcenter:D
181	\name_primitive:NN	\mkern	\tex_mkern:D
182	\name_primitive:NN	\above	\tex_above:D
183	\name_primitive:NN	\abovewithdelims	\tex_abovewithdelims:D
184	\name_primitive:NN	\atop	\tex_atop:D
185	\name_primitive:NN	\atopwithdelims	\tex_atopwithdelims:D
186	\name_primitive:NN	\over	\tex_over:D
187	\name_primitive:NN	\overwithdelims	\tex_overwithdelims:D
188	\name_primitive:NN	\displaystyle	\tex_displaystyle:D
189	\name_primitive:NN	\textstyle	\tex_textstyle:D
190	\name_primitive:NN	\scriptstyle	\tex_scriptstyle:D
191	\name_primitive:NN	\scriptscriptstyle	\tex_scriptscriptstyle:D
192	\name_primitive:NN	\nonscript	\tex_nonscript:D
193	\name_primitive:NN	\eqno	\tex_eqno:D
194	\name_primitive:NN	\leqno	\tex_leqno:D
195	\name_primitive:NN	\abovedisplayshortskip	\tex_abovedisplayshortskip:D
196	\name_primitive:NN	\abovedisplayskip	\tex_abovedisplayskip:D
197	\name_primitive:NN	\belowdisplayshortskip	\tex_belowdisplayshortskip:D
198	\name_primitive:NN	\belowdisplayskip	\tex_belowdisplayskip:D
199	\name_primitive:NN	\displaywidowpenalty	\tex_displaywidowpenalty:D
200	\name_primitive:NN	\displayindent	\tex_displayindent:D
201	\name_primitive:NN	\displaywidth	\tex_displaywidth:D
202	\name_primitive:NN	\everydisplay	\tex_everydisplay:D
203	\name_primitive:NN	\predisplaysize	\tex_predisplaysize:D
204	\name_primitive:NN	\predisplaypenalty	\tex_predisplaypenalty:D
205	\name_primitive:NN	\postdisplaypenalty	\tex_postdisplaypenalty:D
206	\name_primitive:NN	\mathbin	\tex_mathbin:D
207	\name_primitive:NN	\mathclose	\tex_mathclose:D
208	\name_primitive:NN	\mathinner	\tex_mathinner:D
209	\name_primitive:NN	\mathop	\tex_mathop:D
210	\name_primitive:NN	\displaylimits	\tex_displaylimits:D
211	\name_primitive:NN	\limits	\tex_limits:D
212	\name_primitive:NN	\nolimits	\tex_nolimits:D
213	\name_primitive:NN	\mathopen	\tex_mathopen:D
214	\name_primitive:NN	\mathord	\tex_mathord:D
215	\name_primitive:NN	\mathpunct	\tex_mathpunct:D
216	\name_primitive:NN	\mathrel	\tex_mathrel:D
217	\name_primitive:NN	\overline	\tex_overline:D
218	\name_primitive:NN	\underline	\tex_underline:D
219	\name_primitive:NN	\left	\tex_left:D
220	\name_primitive:NN	\right	\tex_right:D
221	\name_primitive:NN	\binoppenalty	\tex_binoppenalty:D
222	\name_primitive:NN	\relpenalty	\tex_relpenalty:D
223	\name_primitive:NN	\delimitershortfall	\tex_delimitershortfall:D
224	\name_primitive:NN	\delimiterfactor	\tex_delimiterfactor:D
225	\name_primitive:NN	\nulldelimiterspace	\tex_nulldelimiterspace:D
226	\name_primitive:NN	\everymath	\tex_everymath:D
227	\name_primitive:NN	\mathsurround	\tex_mathsurround:D
228	\name_primitive:NN	\medmuskip	\tex_medmuskip:D
229	\name_primitive:NN	\thinmuskip	\tex_thinmuskip:D

230	\name_primitive:NN	\thickmuskip	\tex_thickmuskip:D
231	\name_primitive:NN	\scriptspace	\tex_scriptspace:D
232	\name_primitive:NN	\noboundary	\tex_noboundary:D
233	\name_primitive:NN	\accent	\tex_accent:D
234	\name_primitive:NN	\char	\tex_char:D
235	\name_primitive:NN	\discretionary	\tex_discretionary:D
236	\name_primitive:NN	\hfil	\tex_hfil:D
237	\name_primitive:NN	\hfilneg	\tex_hfilneg:D
238	\name_primitive:NN	\hfill	\tex_hfill:D
239	\name_primitive:NN	\hskip	\tex_hskip:D
240	\name_primitive:NN	\hss	\tex_hss:D
241	\name_primitive:NN	\vfil	\tex_vfil:D
242	\name_primitive:NN	\vfilneg	\tex_vfilneg:D
243	\name_primitive:NN	\vfill	\tex_vfill:D
244	\name_primitive:NN	\vskip	\tex_vskip:D
245	\name_primitive:NN	\vss	\tex_vss:D
246	\name_primitive:NN	\unskip	\tex_unskip:D
247	\name_primitive:NN	\kern	\tex_kern:D
248	\name_primitive:NN	\unkern	\tex_unkern:D
249	\name_primitive:NN	\hrule	\tex_hrule:D
250	\name_primitive:NN	\vrule	\tex_vrule:D
251	\name_primitive:NN	\leaders	\tex_leaders:D
252	\name_primitive:NN	\cleaders	\tex_cleaders:D
253	\name_primitive:NN	\xleaders	\tex_xleaders:D
254	\name_primitive:NN	\lastkern	\tex_lastkern:D
255	\name_primitive:NN	\lastskip	\tex_lastskip:D
256	\name_primitive:NN	\indent	\tex_indent:D
257	\name_primitive:NN	\par	\tex_par:D
258	\name_primitive:NN	\noindent	\tex_noindent:D
259	\name_primitive:NN	\vadjust	\tex_vadjust:D
260	\name_primitive:NN	\baselineskip	\tex_baselineskip:D
261	\name_primitive:NN	\lineskip	\tex_lineskip:D
262	\name_primitive:NN	\lineskiplimit	\tex_lineskiplimit:D
263	\name_primitive:NN	\clubpenalty	\tex_clubpenalty:D
264	\name_primitive:NN	\widowpenalty	\tex_widowpenalty:D
265	\name_primitive:NN	\exhyphenpenalty	\tex_exhyphenpenalty:D
266	\name_primitive:NN	\hyphenpenalty	\tex_hyphenpenalty:D
267	\name_primitive:NN	\linepenalty	\tex_linepenalty:D
268	\name_primitive:NN	\doublehyphendemerits	\tex_doublehyphendemerits:D
269	\name_primitive:NN	\finalhyphendemerits	\tex_finalhyphendemerits:D
270	\name_primitive:NN	\adjdemerits	\tex_adjdemerits:D
271	\name_primitive:NN	\hangafter	\tex_hangafter:D
272	\name_primitive:NN	\hangindent	\tex_hangindent:D
273	\name_primitive:NN	\parshape	\tex_parshape:D
274	\name_primitive:NN	\hsize	\tex_hsize:D
275	\name_primitive:NN	\lefthyphenmin	\tex_lefthyphenmin:D
276	\name_primitive:NN	\righthyphenmin	\tex_righthyphenmin:D
277	\name_primitive:NN	\leftskip	\tex_leftskip:D
278	\name_primitive:NN	\rightskip	\tex_rightskip:D
279	\name_primitive:NN	\looseness	\tex_looseness:D

280	\name_primitive:NN	\parskip	\tex_parskip:D
281	\name_primitive:NN	\parindent	\tex_parindent:D
282	\name_primitive:NN	\uchyph	\tex_uchyph:D
283	\name_primitive:NN	\emergencystretch	\tex_emergencystretch:D
284	\name_primitive:NN	\pretolerance	\tex_pretolerance:D
285	\name_primitive:NN	\tolerance	\tex_tolerance:D
286	\name_primitive:NN	\spaceskip	\tex_spaceskip:D
287	\name_primitive:NN	\xspaceskip	\tex_xspaceskip:D
288	\name_primitive:NN	\parfillskip	\tex_parfillskip:D
289	\name_primitive:NN	\everypar	\tex_everypar:D
290	\name_primitive:NN	\prevgraf	\tex_prevgraf:D
291	\name_primitive:NN	\spacefactor	\tex_spacefactor:D
292	\name_primitive:NN	\shipout	\tex_shipout:D
293	\name_primitive:NN	\vsize	\tex_vsize:D
294	\name_primitive:NN	\interlinepenalty	\tex_interlinepenalty:D
295	\name_primitive:NN	\brokenpenalty	\tex_brokenpenalty:D
296	\name_primitive:NN	\topskip	\tex_topskip:D
297	\name_primitive:NN	\maxdeadcycles	\tex_maxdeadcycles:D
298	\name_primitive:NN	\maxdepth	\tex_maxdepth:D
299	\name_primitive:NN	\output	\tex_output:D
300	\name_primitive:NN	\deadcycles	\tex_deadcycles:D
301	\name_primitive:NN	\pagedepth	\tex_pagedepth:D
302	\name_primitive:NN	\pagestretch	\tex_pagestretch:D
303	\name_primitive:NN	\pagefilstretch	\tex_pagefilstretch:D
304	\name_primitive:NN	\pagefillstretch	\tex_pagefillstretch:D
305	\name_primitive:NN	\pagefilllstretch	\tex_pagefilllstretch:D
306	\name_primitive:NN	\pageshrink	\tex_pageshrink:D
307	\name_primitive:NN	\pagegoal	\tex_pagegoal:D
308	\name_primitive:NN	\pagetotal	\tex_pagetotal:D
309	\name_primitive:NN	\outputpenalty	\tex_outputpenalty:D
310	\name_primitive:NN	\hoffset	\tex_hoffset:D
311	\name_primitive:NN	\voffset	\tex_voffset:D
312	\name_primitive:NN	\insert	\tex_insert:D
313	\name_primitive:NN	\holdinginserts	\tex_holdinginserts:D
314	\name_primitive:NN	\floatingpenalty	\tex_floatingpenalty:D
315	\name_primitive:NN	\insertpenalties	\tex_insertpenalties:D
316	\name_primitive:NN	\lower	\tex_lower:D
317	\name_primitive:NN	\moveleft	\tex_moveleft:D
318	\name_primitive:NN	\moveright	\tex_moveright:D
319	\name_primitive:NN	\raise	\tex_raise:D
320	\name_primitive:NN	\copy	\tex_copy:D
321	\name_primitive:NN	\lastbox	\tex_lastbox:D
322	\name_primitive:NN	\vsplit	\tex_vsplit:D
323	\name_primitive:NN	\unhbox	\tex_unhbox:D
324	\name_primitive:NN	\unhcopy	\tex_unhcopy:D
325	\name_primitive:NN	\unvbox	\tex_unvbox:D
326	\name_primitive:NN	\unvcopy	\tex_unvcopy:D
327	\name_primitive:NN	\setbox	\tex_setbox:D
328	\name_primitive:NN	\hbox	\tex_hbox:D
329	\name_primitive:NN	\vbox	\tex_vbox:D

330	\name_primitive:NN	\vtop	\tex_vtop:D
331	\name_primitive:NN	\prevdepth	\tex_prevdepth:D
332	\name_primitive:NN	\badness	\tex_badness:D
333	\name_primitive:NN	\hbadness	\tex_hbadness:D
334	\name_primitive:NN	\vbadness	\tex_vbadness:D
335	\name_primitive:NN	\hfuzz	\tex_hfuzz:D
336	\name_primitive:NN	\vfuzz	\tex_vfuzz:D
337	\name_primitive:NN	\overfullrule	\tex_overfullrule:D
338	\name_primitive:NN	\boxmaxdepth	\tex_boxmaxdepth:D
339	\name_primitive:NN	\splitmaxdepth	\tex_splitmaxdepth:D
340	\name_primitive:NN	\splittopskip	\tex_splittopskip:D
341	\name_primitive:NN	\everyhbox	\tex_everyhbox:D
342	\name_primitive:NN	\everyvbox	\tex_everyvbox:D
343	\name_primitive:NN	\nullfont	\tex_nullfont:D
344	\name_primitive:NN	\textfont	\tex_textfont:D
345	\name_primitive:NN	\scriptfont	\tex_scriptfont:D
346	\name_primitive:NN	\scriptscriptfont	\tex_scriptscriptfont:D
347	\name_primitive:NN	\fontdimen	\tex_fontdimen:D
348	\name_primitive:NN	\hyphenchar	\tex_hyphenchar:D
349	\name_primitive:NN	\skewchar	\tex_skewchar:D
350	\name_primitive:NN	\defaultthyphenchar	\tex_defaultthyphenchar:D
351	\name_primitive:NN	\defaultskewchar	\tex_defaultskewchar:D
352	\name_primitive:NN	\number	\tex_number:D
353	\name_primitive:NN	\romannumeral	\tex_romannumeral:D
354	\name_primitive:NN	\string	\tex_string:D
355	\name_primitive:NN	\lowercase	\tex_lowercase:D
356	\name_primitive:NN	\uppercase	\tex_uppercase:D
357	\name_primitive:NN	\meaning	\tex_meaning:D
358	\name_primitive:NN	\penalty	\tex_penalty:D
359	\name_primitive:NN	\unpenalty	\tex_unpenalty:D
360	\name_primitive:NN	\lastpenalty	\tex_lastpenalty:D
361	\name_primitive:NN	\special	\tex_special:D
362	\name_primitive:NN	\dump	\tex_dump:D
363	\name_primitive:NN	\patterns	\tex_patterns:D
364	\name_primitive:NN	\hyphenation	\tex_hyphenation:D
365	\name_primitive:NN	\time	\tex_time:D
366	\name_primitive:NN	\day	\tex_day:D
367	\name_primitive:NN	\month	\tex_month:D
368	\name_primitive:NN	\year	\tex_year:D
369	\name_primitive:NN	\jobname	\tex_jobname:D
370	\name_primitive:NN	\everyjob	\tex_everyjob:D
371	\name_primitive:NN	\count	\tex_count:D
372	\name_primitive:NN	\dimen	\tex_dimen:D
373	\name_primitive:NN	\skip	\tex_skip:D
374	\name_primitive:NN	\toks	\tex_toks:D
375	\name_primitive:NN	\muskip	\tex_muskip:D
376	\name_primitive:NN	\box	\tex_box:D
377	\name_primitive:NN	\wd	\tex_wd:D
378	\name_primitive:NN	\ht	\tex_ht:D
379	\name_primitive:NN	\dp	\tex_dp:D

380	<code>\name_primitive:NN \catcode</code>	<code>\tex_catcode:D</code>
381	<code>\name_primitive:NN \delcode</code>	<code>\tex_delcode:D</code>
382	<code>\name_primitive:NN \sfcode</code>	<code>\tex_sfcode:D</code>
383	<code>\name_primitive:NN \lccode</code>	<code>\tex_lccode:D</code>
384	<code>\name_primitive:NN \uccode</code>	<code>\tex_uccode:D</code>
385	<code>\name_primitive:NN \mathcode</code>	<code>\tex_mathcode:D</code>

Since L<sup>A</sup>T<sub>E</sub>X3 requires at least the  $\varepsilon$ -T<sub>E</sub>X extensions, we also rename the additional primitives. These are all given the prefix `\etex_`.

386	<code>\name_primitive:NN \ifdefined</code>	<code>\etex_ifdefined:D</code>
387	<code>\name_primitive:NN \ifcsname</code>	<code>\etex_ifcsname:D</code>
388	<code>\name_primitive:NN \unless</code>	<code>\etex_unless:D</code>
389	<code>\name_primitive:NN \eTeXversion</code>	<code>\etex_eTeXversion:D</code>
390	<code>\name_primitive:NN \eTeXrevision</code>	<code>\etex_eTeXrevision:D</code>
391	<code>\name_primitive:NN \marks</code>	<code>\etex_marks:D</code>
392	<code>\name_primitive:NN \topmarks</code>	<code>\etex_topmarks:D</code>
393	<code>\name_primitive:NN \firstmarks</code>	<code>\etex_firstmarks:D</code>
394	<code>\name_primitive:NN \botmarks</code>	<code>\etex_botmarks:D</code>
395	<code>\name_primitive:NN \splitfirstmarks</code>	<code>\etex_splitfirstmarks:D</code>
396	<code>\name_primitive:NN \splitbotmarks</code>	<code>\etex_splitbotmarks:D</code>
397	<code>\name_primitive:NN \unexpanded</code>	<code>\etex_unexpanded:D</code>
398	<code>\name_primitive:NN \detokenize</code>	<code>\etex_detokenize:D</code>
399	<code>\name_primitive:NN \scantokens</code>	<code>\etex_scantokens:D</code>
400	<code>\name_primitive:NN \showtokens</code>	<code>\etex_showtokens:D</code>
401	<code>\name_primitive:NN \readline</code>	<code>\etex_readline:D</code>
402	<code>\name_primitive:NN \tracingassigns</code>	<code>\etex_tracingassigns:D</code>
403	<code>\name_primitive:NN \tracingscantokens</code>	<code>\etex_tracingscantokens:D</code>
404	<code>\name_primitive:NN \tracingnesting</code>	<code>\etex_tracingnesting:D</code>
405	<code>\name_primitive:NN \tracingifs</code>	<code>\etex_tracingifs:D</code>
406	<code>\name_primitive:NN \currentiflevel</code>	<code>\etex_currentiflevel:D</code>
407	<code>\name_primitive:NN \currentifbranch</code>	<code>\etex_currentifbranch:D</code>
408	<code>\name_primitive:NN \currentiftyp</code>	<code>\etex_currentiftyp:D</code>
409	<code>\name_primitive:NN \tracinggroups</code>	<code>\etex_tracinggroups:D</code>
410	<code>\name_primitive:NN \currentgrouplevel</code>	<code>\etex_currentgrouplevel:D</code>
411	<code>\name_primitive:NN \currentgroup</code>	<code>\etex_currentgroup:D</code>
412	<code>\name_primitive:NN \showgroups</code>	<code>\etex_showgroups:D</code>
413	<code>\name_primitive:NN \showifs</code>	<code>\etex_showifs:D</code>
414	<code>\name_primitive:NN \interactionmode</code>	<code>\etex_interactionmode:D</code>
415	<code>\name_primitive:NN \lastnodetype</code>	<code>\etex_lastnodetype:D</code>
416	<code>\name_primitive:NN \iffontchar</code>	<code>\etex_iffontchar:D</code>
417	<code>\name_primitive:NN \fontcharht</code>	<code>\etex_fontcharht:D</code>
418	<code>\name_primitive:NN \fontchardp</code>	<code>\etex_fontchardp:D</code>
419	<code>\name_primitive:NN \fontcharwd</code>	<code>\etex_fontcharwd:D</code>
420	<code>\name_primitive:NN \fontcharic</code>	<code>\etex_fontcharic:D</code>
421	<code>\name_primitive:NN \parshapeindent</code>	<code>\etex_parshapeindent:D</code>
422	<code>\name_primitive:NN \parshapelength</code>	<code>\etex_parshapelength:D</code>
423	<code>\name_primitive:NN \parshapedimen</code>	<code>\etex_parshapedimen:D</code>
424	<code>\name_primitive:NN \numexpr</code>	<code>\etex_numexpr:D</code>
425	<code>\name_primitive:NN \dimexpr</code>	<code>\etex_dimexpr:D</code>

426	\name_primitive:NN	\glueexpr	\etex_glueexpr:D
427	\name_primitive:NN	\muexpr	\etex_muexpr:D
428	\name_primitive:NN	\gluestretch	\etex_gluestretch:D
429	\name_primitive:NN	\glueshrink	\etex_glueshrink:D
430	\name_primitive:NN	\gluestretchorder	\etex_gluestretchorder:D
431	\name_primitive:NN	\glueshrinkorder	\etex_glueshrinkorder:D
432	\name_primitive:NN	\gluetomu	\etex_gluetomu:D
433	\name_primitive:NN	\mutoglu	\etex_mutoglu:D
434	\name_primitive:NN	\lastlinefit	\etex_lastlinefit:D
435	\name_primitive:NN	\interlinepenalties	\etex_interlinepenalties:D
436	\name_primitive:NN	\clubpenalties	\etex_clubpenalties:D
437	\name_primitive:NN	\widowpenalties	\etex_widowpenalties:D
438	\name_primitive:NN	\displaywidowpenalties	\etex_displaywidowpenalties:D
439	\name_primitive:NN	\middle	\etex_middle:D
440	\name_primitive:NN	\savinghyphcodes	\etex_savinghyphcodes:D
441	\name_primitive:NN	\savingvdiscards	\etex_savingvdiscards:D
442	\name_primitive:NN	\pagediscards	\etex_pagediscards:D
443	\name_primitive:NN	\splitdiscards	\etex_splitdiscards:D
444	\name_primitive:NN	\TeXETstate	\etex_TeXXETstate:D
445	\name_primitive:NN	\beginL	\etex_beginL:D
446	\name_primitive:NN	\endL	\etex_endL:D
447	\name_primitive:NN	\beginR	\etex_beginR:D
448	\name_primitive:NN	\endR	\etex_endR:D
449	\name_primitive:NN	\predisplaydirection	\etex_predisplaydirection:D
450	\name_primitive:NN	\everyeof	\etex_everyeof:D
451	\name_primitive:NN	\protected	\etex_protected:D

All major distributions use pdf $\epsilon$ -TeX as engine so we add these names as well. Since the pdfTeX team has been very good at prefixing most primitives with pdf (so far only five do not start with pdf) we do not give them a double pdf prefix. The list below covers pdfTeXv 1.30.4.

452	%% integer registers:		
453	\name_primitive:NN	\pdfoutput	\pdf_output:D
454	\name_primitive:NN	\pdfminorversion	\pdf_minorversion:D
455	\name_primitive:NN	\pdfcompresslevel	\pdf_compresslevel:D
456	\name_primitive:NN	\pdfdecimaldigits	\pdf_decimaldigits:D
457	\name_primitive:NN	\pdfimageresolution	\pdf_imageresolution:D
458	\name_primitive:NN	\pdfpkresolution	\pdf_pkresolution:D
459	\name_primitive:NN	\pdftracingfonts	\pdf_tracingfonts:D
460	\name_primitive:NN	\pdfuniqueresname	\pdf_uniqueresname:D
461	\name_primitive:NN	\pdfadjustspacing	\pdf_adjustspacing:D
462	\name_primitive:NN	\pdfprotrudechars	\pdf_protrudechars:D
463	\name_primitive:NN	\efcode	\pdf_efcode:D
464	\name_primitive:NN	\lpcode	\pdf_lpcode:D
465	\name_primitive:NN	\rpcode	\pdf_rpcode:D
466	\name_primitive:NN	\pdfforcepagebox	\pdf_forcepagebox:D
467	\name_primitive:NN	\pdfoptionalwaysusepdfpagebox	\pdf_optionalwaysusepdfpagebox:D
468	\name_primitive:NN	\pdfinclusionerrorlevel	\pdf_inclusionerrorlevel:D
469	\name_primitive:NN	\pdfoptionpdfinclusionerrorlevel	\pdf_optionpdfinclusionerrorlevel:D

470	\name_primitive:NN	\pdfimagehicolor	\pdf_imagehicolor:D
471	\name_primitive:NN	\pdfimageapplygamma	\pdf_imageapplygamma:D
472	\name_primitive:NN	\pdfgamma	\pdf_gamma:D
473	\name_primitive:NN	\pdfimagegamma	\pdf_imagegamma:D
474	%% dimen registers:		
475	\name_primitive:NN	\pdfhorigin	\pdf_horigin:D
476	\name_primitive:NN	\pdfvorigin	\pdf_vorigin:D
477	\name_primitive:NN	\pdfpagewidth	\pdf_pagewidth:D
478	\name_primitive:NN	\pdfpageheight	\pdf_pageheight:D
479	\name_primitive:NN	\pdflinkmargin	\pdf_linkmargin:D
480	\name_primitive:NN	\pdfdestmargin	\pdf_destmargin:D
481	\name_primitive:NN	\pdfthreadmargin	\pdf_threadmargin:D
482	%% token registers:		
483	\name_primitive:NN	\pdfpagesattr	\pdf_pagesattr:D
484	\name_primitive:NN	\pdfpageattr	\pdf_pageattr:D
485	\name_primitive:NN	\pdfpageresources	\pdf_pageresources:D
486	\name_primitive:NN	\pdfpkmode	\pdf_pkmode:D
487	%% expandable commands:		
488	\name_primitive:NN	\pdftexrevision	\pdf_texrevision:D
489	\name_primitive:NN	\pdftexbanner	\pdf_texbanner:D
490	\name_primitive:NN	\pdfcreationdate	\pdf_creationdate:D
491	\name_primitive:NN	\pdfpageref	\pdf_pageref:D
492	\name_primitive:NN	\pdfxformname	\pdf_xformname:D
493	\name_primitive:NN	\pdffontname	\pdf_fontname:D
494	\name_primitive:NN	\pdffontobjnum	\pdf_fontobjnum:D
495	\name_primitive:NN	\pdffontsize	\pdf_fontsize:D
496	\name_primitive:NN	\pdfincludechars	\pdf_includechars:D
497	\name_primitive:NN	\leftmarginkern	\pdf_leftmarginkern:D
498	\name_primitive:NN	\rightmarginkern	\pdf_rightmarginkern:D
499	\name_primitive:NN	\pdfescapestring	\pdf_escapestring:D
500	\name_primitive:NN	\pdfescapename	\pdf_escapename:D
501	\name_primitive:NN	\pdfescapehex	\pdf_escapehex:D
502	\name_primitive:NN	\pdfunescapehex	\pdf_unescapehex:D
503	\name_primitive:NN	\pdfstrcmp	\pdf_strcmp:D
504	\name_primitive:NN	\pdfuniformdeviate	\pdf_uniformdeviate:D
505	\name_primitive:NN	\pdfnormaldeviate	\pdf_normaldeviate:D
506	\name_primitive:NN	\pdfmdfivesum	\pdf_mdfivesum:D
507	\name_primitive:NN	\pdffilemoddate	\pdf_filemoddate:D
508	\name_primitive:NN	\pdffilesize	\pdf_filesize:D
509	\name_primitive:NN	\pdffiledump	\pdf_filedump:D
510	%% read-only integers:		
511	\name_primitive:NN	\pdftexversion	\pdf_texversion:D
512	\name_primitive:NN	\pdflastobj	\pdf_lastobj:D
513	\name_primitive:NN	\pdflastxform	\pdf_lastxform:D
514	\name_primitive:NN	\pdflastximage	\pdf_lastximage:D
515	\name_primitive:NN	\pdflastximagepages	\pdf_lastximagepages:D
516	\name_primitive:NN	\pdflastannot	\pdf_lastannot:D
517	\name_primitive:NN	\pdflastxpos	\pdf_lastxpos:D
518	\name_primitive:NN	\pdflastypos	\pdf_lastypos:D
519	\name_primitive:NN	\pdflastdemerits	\pdf_lastdemerits:D



```

520 \name_primitive:NN \pdfelapsedtime      \pdf_elapsedtime:D
521 \name_primitive:NN \pdfrandomseed       \pdf_randomseed:D
522 \name_primitive:NN \pdfshellescape      \pdf_shellescape:D
523 %% general commands:
524 \name_primitive:NN \pdfobj              \pdf_obj:D
525 \name_primitive:NN \pdfrefobj           \pdf_refobj:D
526 \name_primitive:NN \pdfxform            \pdf_xform:D
527 \name_primitive:NN \pdfrefxform         \pdf_refxform:D
528 \name_primitive:NN \pdfximage           \pdf_ximage:D
529 \name_primitive:NN \pdfrefximage        \pdf_refximage:D
530 \name_primitive:NN \pdfannot            \pdf_annot:D
531 \name_primitive:NN \pdfstartlink        \pdf_startlink:D
532 \name_primitive:NN \pdfendlink          \pdf_endlink:D
533 \name_primitive:NN \pdfoutline          \pdf_outline:D
534 \name_primitive:NN \pdfdest             \pdf_dest:D
535 \name_primitive:NN \pdfthread           \pdf_thread:D
536 \name_primitive:NN \pdfstartthread      \pdf_startthread:D
537 \name_primitive:NN \pdfendthread        \pdf_endthread:D
538 \name_primitive:NN \pdfsavepos          \pdf_savepos:D
539 \name_primitive:NN \pdfinfo             \pdf_info:D
540 \name_primitive:NN \pdfcatalog          \pdf_catalog:D
541 \name_primitive:NN \pdfnames            \pdf_names:D
542 \name_primitive:NN \pdfmapfile          \pdf_mapfile:D
543 \name_primitive:NN \pdfmapline          \pdf_mapline:D
544 \name_primitive:NN \pdffontattr         \pdf_fontattr:D
545 \name_primitive:NN \pdftrailer          \pdf_trailer:D
546 \name_primitive:NN \pdffontexpand       \pdf_fontexpand:D
547 %%\name_primitive:NN \vadjust [<pre spec>] <filler> { <vertical mode material> } (h, m)
548 \name_primitive:NN \pdfliteral          \pdf_literal:D
549 %%\name_primitive:NN \special <pdfspecial spec>
550 \name_primitive:NN \pdfresettimer       \pdf_resettimer:D
551 \name_primitive:NN \pdfsetrandomseed    \pdf_setrandomseed:D
552 \name_primitive:NN \pdfnoligatures      \pdf_noligatures:D

```

We're ignoring XeTeX and LuaTeX right now except for a check whether they're in use:

```

553 \name_primitive:NN \XeTeXversion        \xetex_version:D
554 \name_primitive:NN \directlua           \luatex_directlua:D

```

XeTeX adds `\strcmp` to the set of primitives, with the same implementation as `\pdfstrcmp` but a different name. To avoid having to worry about this later, the same internal name is used.

```

555 \etex_ifdefined:D \strcmp
556   \etex_ifdefined:D \xetex_version:D
557     \name_primitive:NN \strcmp \pdf_strcmp:D
558   \tex_fi:D
559 \tex_fi:D

```

## 94.6 expl3 code switches

`\ExplSyntaxOn` Here we define functions that are used to turn on and off the special conventions used in the kernel of L<sup>A</sup>T<sub>E</sub>X3.  
`\ExplSyntaxOff`  
`\ExplSyntaxStatus` First of all, the space, tab and the return characters will all be ignored inside L<sup>A</sup>T<sub>E</sub>X3 code, the latter because `endline` is set to a space instead. When space characters are needed in L<sup>A</sup>T<sub>E</sub>X3 code the `~` character will be used for that purpose.

Specification of the desired behavior:

- `ExplSyntax` can be either On or Off.
- The On switch is `<null>` if `ExplSyntax` is on.
- The Off switch is `<null>` if `ExplSyntax` is off.
- If the On switch is issued and not `<null>`, it records the current catcode scheme just prior to it being issued.
- An Off switch restores the catcode scheme to what it was just prior to the previous On switch.

```

560 \tex_def:D \ExplSyntaxOn {
561   \tex_ifodd:D \ExplSyntaxStatus \tex_relax:D
562   \tex_else:D
563     \tex_edef:D \ExplSyntaxOff {
564       \etex_unexpanded:D{
565         \tex_ifodd:D \ExplSyntaxStatus \tex_relax:D
566         \tex_def:D \ExplSyntaxStatus{0}
567       }
568       \tex_catcode:D 126=\tex_the:D \tex_catcode:D 126 \tex_relax:D
569       \tex_catcode:D 32=\tex_the:D \tex_catcode:D 32 \tex_relax:D
570       \tex_catcode:D 9=\tex_the:D \tex_catcode:D 9 \tex_relax:D
571       \tex_endlinechar:D =\tex_the:D \tex_endlinechar:D \tex_relax:D
572       \tex_catcode:D 95=\tex_the:D \tex_catcode:D 95 \tex_relax:D
573       \tex_catcode:D 58=\tex_the:D \tex_catcode:D 58 \tex_relax:D
574       \tex_noexpand:D \tex_fi:D
575     }
576     \tex_def:D \ExplSyntaxStatus { 1 }
577     \tex_catcode:D 126=10 \tex_relax:D % tilde is a space char.
578     \tex_catcode:D 32=9 \tex_relax:D % space is ignored
579     \tex_catcode:D 9=9 \tex_relax:D % tab also ignored
580     \tex_endlinechar:D =32 \tex_relax:D % endline is space
581     \tex_catcode:D 95=11 \tex_relax:D % underscore letter
582     \tex_catcode:D 58=11 \tex_relax:D % colon letter
583   \tex_fi:D
584 }

```

At this point we better set the status.

```

585 \tex_def:D \ExplSyntaxStatus { 1 }

```

`\ExplSyntaxNamesOn` Sometimes we need to be able to use names from the kernel of L<sup>A</sup>T<sub>E</sub>X3 without adhering it's  
`\ExplSyntaxNamesOff` conventions according to space characters. These macros provide the necessary settings.

```

586 \tex_def:D \ExplSyntaxNamesOn {
587   \tex_catcode:D '\_ =11\tex_relax:D
588   \tex_catcode:D '\: =11\tex_relax:D
589 }
590 \tex_def:D \ExplSyntaxNamesOff {
591   \tex_catcode:D '\_ =8\tex_relax:D
592   \tex_catcode:D '\: =12\tex_relax:D
593 }

```

## 94.7 Package loading

`\GetIdInfo` Extract all information from a cvs or svn field. The formats are slightly different but  
`\filedescription` at least the information is in the same positions so we check in the date format so see  
`\filename` if it contains a / after the four-digit year. If it does it is cvs else svn and we extract  
`\fileversion` information. To be on the safe side we ensure that spaces in the argument are seen.

```

\fileauthor
\filedate
\filenameext
\filetimestamp
\GetIdInfoAuxI:w
\GetIdInfoAuxII:w
\GetIdInfoAuxCVS:w
\GetIdInfoAuxSVN:w
594 \tex_def:D \GetIdInfo {
595   \tex_begingroup:D
596   \tex_catcode:D 32=10 \tex_relax:D % needed? Probably for now.
597   \GetIdInfoMaybeMissing:w
598 }
599 \tex_def:D\GetIdInfoMaybeMissing:w$#1$#2{
600   \tex_def:D \l_tmpa_tl {#1}
601   \tex_def:D \l_tmpb_tl {Id}
602   \tex_ifx:D \l_tmpa_tl \l_tmpb_tl
603     \tex_def:D \l_tmpa_tl {
604       \tex_endgroup:D
605       \tex_def:D\filedescription{#2}
606       \tex_def:D\filename      {[unknown~name]}
607       \tex_def:D\fileversion   {000}
608       \tex_def:D\fileauthor    {[unknown~author]}
609       \tex_def:D\filedate      {0000/00/00}
610       \tex_def:D\filenameext   {[unknown~ext]}
611       \tex_def:D\filetimestamp {[unknown~timestamp]}
612     }
613   \tex_else:D
614     \tex_def:D \l_tmpa_tl {\GetIdInfoAuxI:w$#1$#2}
615   \tex_fi:D
616   \l_tmpa_tl
617 }

618 \tex_def:D\GetIdInfoAuxI:w$#1~#2.#3~#4~#5~#6~#7~#8$#9{
619   \tex_endgroup:D
620   \tex_def:D\filename{#2}
621   \tex_def:D\fileversion{#4}

```

```

622 \tex_def:D\filedescription{#9}
623 \tex_def:D\fileauthor{#7}
624 \GetIdInfoAuxii:w #5\tex_relax:D
625 #3\tex_relax:D#5\tex_relax:D#6\tex_relax:D
626 }

627 \tex_def:D\GetIdInfoAuxii:w #1#2#3#4#5#6\tex_relax:D{
628 \tex_ifx:D#5/
629 \tex_expandafter:D\GetIdInfoAuxCVS:w
630 \tex_else:D
631 \tex_expandafter:D\GetIdInfoAuxSVN:w
632 \tex_fi:D
633 }

634 \tex_def:D\GetIdInfoAuxCVS:w #1,v\tex_relax:D
635 #2\tex_relax:D#3\tex_relax:D{
636 \tex_def:D\filedate{#2}
637 \tex_def:D\filenameext{#1}
638 \tex_def:D\filetimestamp{#3}

```

When creating the format we want the information in the log straight away.

```

639 <initex>\tex_immediate:D\tex_write:D-1
640 <initex> {\filename;~ v\fileversion,~\filedate;~\filedescription}
641 }
642 \tex_def:D\GetIdInfoAuxSVN:w #1\tex_relax:D#2-#3-#4
643 \tex_relax:D#5Z\tex_relax:D{
644 \tex_def:D\filenameext{#1}
645 \tex_def:D\filedate{#2/#3/#4}
646 \tex_def:D\filetimestamp{#5}
647 <-package>\tex_immediate:D\tex_write:D-1
648 <-package> {\filename;~ v\fileversion,~\filedate;~\filedescription}
649 }
650 </initex | package>

```

Finally some corrections in the case we are running over  $\text{\LaTeX} 2_{\epsilon}$ .

We want to set things up so that experimental packages and regular packages can coexist with the former using the  $\text{\LaTeX} 3$  programming catcode settings. Since it cannot be the task of the end user to know how a package is constructed under the hood we make it so that the experimental packages have to identify themselves. As an example it can be done as

```

\RequirePackage{l3names}
\ProvidesExplPackage{agent}{2007/08/28}{007}{bonding module}

```

or by using the `\file{field}` informations from `\GetIdInfo` as the packages in this distribution do like this:

```

\RequirePackage{l3names}
\GetIdInfo$Id: l3names.dtx 1751 2009-11-26 08:36:12Z joseph $
    {L3 Experimental Box module}
\ProvidesExplPackage
    {\filename}{\filedate}{\fileversion}{\filedescription}

```

`\ProvidesExplPackage` First up is the identification. Rather trivial as we don't allow for options just yet.

```

\ProvidesExplClass
\ProvidesExplFile
651 <*package>
652 \tex_def:D \ProvidesExplPackage#1#2#3#4{
653     \ProvidesPackage{#1}[#2~v#3~#4]
654     \ExplSyntaxOn
655 }
656 \tex_def:D \ProvidesExplClass#1#2#3#4{
657     \ProvidesClass{#1}[#2~v#3~#4]
658     \ExplSyntaxOn
659 }
660 \tex_def:D \ProvidesExplFile#1#2#3#4{
661     \ProvidesFile{#1}[#2~v#3~#4]
662     \ExplSyntaxOn
663 }

```

`\@pushfilename` The idea behind the code is to record whether or not the  $\text{\LaTeX}$ 3 syntax is on or off when  
`\@popfilename` about to load a file with class or package extension. This status stored in the parameter `\ExplSyntaxStatus` and set by `\ExplSyntaxOn` and `\ExplSyntaxOff` to 1 and 0 respectively is pushed onto the stack `\ExplSyntaxStack`. Then the catcodes are set back to normal, the file loaded with its options and finally the stack is popped again. The whole thing is a bit problematical. So let's take a look at what the desired behavior is: A package or class which declares itself of Expl type by using `\ProvidesExplClass` or `\ProvidesExplPackage` should automatically ensure the correct catcode scheme as soon as the identification part is over. Similarly, a package or class which uses the traditional `\ProvidesClass` or `\ProvidesPackage` commands should go back to the traditional catcode scheme. An example:

```

\RequirePackage{l3names}
\ProvidesExplPackage{foobar}{2009/05/07}{0.1}{Foobar package}
\cs_new:Npn \foo_bar:nn #1#2 {#1,#2}
...
\RequirePackage{array}
...
\cs_new:Npn \foo_bar:nnn #1#2#3 {#3,#2,#1}

```

Inside the `array` package, everything should behave as normal under traditional  $\text{\LaTeX}$  but as soon as we are back at the top level, we should use the new catcode regime.

Whenever  $\text{\LaTeX}$  inputs a package file or similar, it calls upon `\@pushfilename` to push the name, the extension and the catcode of `@` of the file it was currently processing onto

a file name stack. Similarly, after inputting such a file, this file name stack is popped again and the catcode of @ is set to what it was before. If it is a package within package, @ maintains catcode 11 whereas if it is package within document preamble @ is reset to what it was in the preamble (which is usually catcode 12). We wish to adopt a similar technique. Every time an Expl package or class is declared, they will issue an ExplSyntaxOn. Then whenever we are about to load another file, we will first push this status onto a stack and then turn it off again. Then when done loading a file, we pop the stack and if ExplSyntax was On right before, so should it be now. The only problem with this is that we cannot guarantee that we get to the file name stack very early on. Therefore, if the ExplSyntaxStack is empty when trying to pop it, we ensure to turn ExplSyntax off again.

\@pushfilename is prepended with a small function pushing the current ExplSyntaxStatus (true/false) onto a stack. Then the current catcode regime is recorded and ExplSyntax is switched off.

\@popfilename is appended with a function for popping the ExplSyntax stack. However, chances are we didn't get to hook into the file stack early enough so L<sup>A</sup>T<sub>E</sub>X might try to pop the file name stack while the ExplSyntaxStack is empty. If the latter is empty, we just switch off ExplSyntax.

```

664 \tex_edef:D \@pushfilename{
665   \etex_unexpanded:D{
666     \tex_edef:D \ExplSyntaxStack{ \ExplSyntaxStatus \ExplSyntaxStack }
667     \ExplSyntaxOff
668   }
669   \etex_unexpanded:D\tex_expandafter:D{\@pushfilename }
670 }
671 \tex_edef:D \@popfilename{
672   \etex_unexpanded:D\tex_expandafter:D{\@popfilename
673     \tex_if:D 2\ExplSyntaxStack 2
674       \ExplSyntaxOff
675     \tex_else:D
676       \tex_expandafter:D\ExplSyntaxPopStack\ExplSyntaxStack\q_nil
677     \tex_fi:D
678   }
679 }
```

\ExplSyntaxPopStack Popping the stack is simple: Take the first token which is either 0 (false) or 1 (true) and  
\ExplSyntaxStack test if it is odd. Save the rest. The stack is initially empty set to 0 signalling that before  
l3names was loaded, the ExplSyntax was off.

```

680 \tex_def:D\ExplSyntaxPopStack#1#2\q_nil{
681   \tex_def:D\ExplSyntaxStack{#2}
682   \tex_ifodd:D#1\tex_relax:D
683     \ExplSyntaxOn
684   \tex_else:D
685     \ExplSyntaxOff
686   \tex_fi:D

```

```

687 }
688 \tex_def:D \ExplSyntaxStack{0}

```

## 94.8 Finishing up

A few of the ‘primitives’ assigned above have already been stolen by L<sup>A</sup>T<sub>E</sub>X, so assign them by hand to the saved real primitive.

```

689 \tex_let:D\tex_input:D      \@@input
690 \tex_let:D\tex_underline:D  \@@underline
691 \tex_let:D\tex_end:D        \@@end
692 \tex_let:D\tex_everymath:D  \frozen@everymath
693 \tex_let:D\tex_everydisplay:D \frozen@everydisplay
694 \tex_let:D\tex_italiccorr:D \@@italiccorr
695 \tex_let:D\tex_hyphen:D     \@@hyph

```

T<sub>E</sub>X has a nasty habit of inserting a command with the name `\par` so we had better make sure that that command at least has a definition.

```

696 \tex_let:D\par              \tex_par:D

```

This is the end for `l3names` when used on top of L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub>:

```

697 \tex_ifx:D\name_undefine:N\@gobble
698   \tex_def:D\name_pop_stack:w{}
699 \tex_else:D

```

But if traditional T<sub>E</sub>X code is disabled, do this...

As mentioned above, The L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> package mechanism will insert some code to handle the filename stack, and reset the package options, this code will die if the T<sub>E</sub>X primitives have gone, so skip past it and insert some equivalent code that will work.

First a version of `\ProvidesPackage` that can cope.

```

700 \tex_def:D\ProvidesPackage{
701   \tex_begingroup:D
702   \ExplSyntaxOff
703   \package_provides:w}

704 \tex_def:D\package_provides:w#1#2[#3]{
705   \tex_endgroup:D
706   \tex_immediate:D\tex_write:D-1{Package:~#1#2~#3}
707   \tex_expandafter:D\tex_xdef:D
708   \tex_csname:D ver@#1.sty\tex_endcsname:D{#1}}

```

In this case the catcode preserving stack is not maintained and `\ExplSyntaxOn` conventions stay in force once on. You’ll need to turn then off explicitly with `\ExplSyntaxOff` (although as currently built on 2e, nothing except very experimental code will run in this

mode!) Also note that `\RequirePackage` is a simple definition, just for one file, with no options.

```

709 \tex_def:D\name_pop_stack:w#1\relax{%
710   \ExplSyntaxOff
711   \tex_expandafter:D\@p@pfilename\@currnamestack\@nil
712   \tex_let:D\default@ds\@unknownoptionerror
713   \tex_global:D\tex_let:D\ds@\empty
714   \tex_global:D\tex_let:D\@declaredoptions\empty}

715 \tex_def:D\@p@pfilename#1#2#3#4\@nil{%
716   \tex_gdef:D\@currname{#1}%
717   \tex_gdef:D\@currentx{#2}%
718   \tex_catcode:D'\@#3%
719   \tex_gdef:D\@currnamestack{#4}}

720 \tex_def:D\NeedsTeXFormat#1{}
721 \tex_def:D\RequirePackage#1{
722   \tex_expandafter:D\tex_ifx:D
723     \tex_csname:D ver@#1.sty\tex_endcsname:D\tex_relax:D
724     \ExplSyntaxOn
725     \tex_input:D#1.sty\tex_relax:D
726   \tex_fi:D}
727 \tex_fi:D

```

The `\futurelet` just forces the special end of file marker to vanish, so the argument of `\name_pop_stack:w` does not cause an end-of-file error. (Normally I use `\expandafter` for this trick, but here the next token is in fact `\let` and that may be undefined.)

```

728 \tex_futurelet:D\name_tmp:\name_pop_stack:w

```

**expl3 dependency checks** We want the `expl3` bundle to be loaded ‘as one’; this command is used to ensure that one of the 13 packages isn’t loaded on its own.

```

729 <!\initex>
730 \tex_def:D \package_check_loaded_expl: {
731   \ifpackageloaded{expl3}{}{
732     \PackageError{expl3}{Cannot~load~the~expl3~modules~separately}{
733       The~expl3~modules~cannot~be~loaded~separately;\MessageBreak
734       please~\protect\usepackage{expl3}~instead.
735     }
736   }
737 }
738 </!\initex>

739 </package>

```



## 94.9 Showing memory usage

This section is from some old code from 1993; it'd be good to work out how it should be used in our code today.

During the development of the L<sup>A</sup>T<sub>E</sub>X3 kernel we need to be able to keep track of the memory usage. Therefore we generate empty pages while loading the kernel code, just to be able to check the memory usage.

```
740 <*showmemory>
741 \g_trace_statistics_status=2\scan_stop:
742 \cs_set_nopar:Npn\showMemUsage{
743   \if_horizontal_mode:
744     \tex_errmessage:D{Wrong~ mode~ H:~ something~ triggered~
745                       hmode~ above}
746   \else:
747     \tex_message:D{Mode ~ okay}
748   \fi:
749   \tex_shipout:D\hbox:w{ }
750 }
751 \showMemUsage
752 </showmemory>
```

## 95 l3basics implementation

We need l3names to get things going but we actually need it very early on, so it is loaded at the very top of the file l3basics.dtx. Also, most of the code below won't run until l3expan has been loaded.

### 95.1 Renaming some T<sub>E</sub>X primitives (again)

`\cs_set_eq:NwN` Having given all the tex primitives a consistent name, we need to give sensible names to the ones we actually want to use. These will be defined as needed in the appropriate modules, but do a few now, just to get started.<sup>7</sup>

```
753 <*package>
754 \ProvidesExplPackage
755   {\filename}{\filedate}{\fileversion}{\filedescription}
756 \package_check_loaded_expl:
757 </package>
758 <*initex | package>
759 \tex_let:D \cs_set_eq:NwN          \tex_let:D
```

---

<sup>7</sup>This renaming gets expensive in terms of csname usage, an alternative scheme would be to just use the “tex...D” name in the cases where no good alternative exists.

`\if_true:` Then some conditionals.

<code>\if_false:</code>	760 <code>\cs_set_eq:NwN</code>	<code>\if_true:</code>	<code>\tex_iftrue:D</code>
<code>\or:</code>	761 <code>\cs_set_eq:NwN</code>	<code>\if_false:</code>	<code>\tex_iffalse:D</code>
<code>\else:</code>	762 <code>\cs_set_eq:NwN</code>	<code>\or:</code>	<code>\tex_or:D</code>
<code>\fi:</code>	763 <code>\cs_set_eq:NwN</code>	<code>\else:</code>	<code>\tex_else:D</code>
<code>\reverse_if:N</code>	764 <code>\cs_set_eq:NwN</code>	<code>\fi:</code>	<code>\tex_fi:D</code>
<code>\if:w</code>	765 <code>\cs_set_eq:NwN</code>	<code>\reverse_if:N</code>	<code>\etex_unless:D</code>
<code>\if_bool:N</code>	766 <code>\cs_set_eq:NwN</code>	<code>\if:w</code>	<code>\tex_if:D</code>
<code>\if_predicate:w</code>	767 <code>\cs_set_eq:NwN</code>	<code>\if_bool:N</code>	<code>\tex_ifodd:D</code>
<code>\if_charcode:w</code>	768 <code>\cs_set_eq:NwN</code>	<code>\if_predicate:w</code>	<code>\tex_ifodd:D</code>
<code>\if_catcode:w</code>	769 <code>\cs_set_eq:NwN</code>	<code>\if_charcode:w</code>	<code>\tex_if:D</code>
	770 <code>\cs_set_eq:NwN</code>	<code>\if_catcode:w</code>	<code>\tex_ifcat:D</code>

<code>\if_meaning:w</code>	771 <code>\cs_set_eq:NwN</code>	<code>\if_meaning:w</code>	<code>\tex_ifx:D</code>
----------------------------	---------------------------------	----------------------------	-------------------------

`\if_mode_math:` T<sub>E</sub>X lets us detect some if its modes.

<code>\if_mode_horizontal:</code>	772 <code>\cs_set_eq:NwN</code>	<code>\if_mode_math:</code>	<code>\tex_ifmmode:D</code>
<code>\if_mode_vertical:</code>	773 <code>\cs_set_eq:NwN</code>	<code>\if_mode_horizontal:</code>	<code>\tex_ifhmode:D</code>
<code>\if_mode_inner:</code>	774 <code>\cs_set_eq:NwN</code>	<code>\if_mode_vertical:</code>	<code>\tex_ifvmode:D</code>
	775 <code>\cs_set_eq:NwN</code>	<code>\if_mode_inner:</code>	<code>\tex_ifinner:D</code>

<code>\if_cs_exist:N</code>			
<code>\if_cs_exist:w</code>	776 <code>\cs_set_eq:NwN</code>	<code>\if_cs_exist:N</code>	<code>\etex_ifdefined:D</code>
	777 <code>\cs_set_eq:NwN</code>	<code>\if_cs_exist:w</code>	<code>\etex_ifcsname:D</code>

`\exp_after:wN` The three `\exp_` functions are used in the l3expan module where they are described.

<code>\exp_not:N</code>			
<code>\exp_not:n</code>	778 <code>\cs_set_eq:NwN</code>	<code>\exp_after:wN</code>	<code>\tex_expandafter:D</code>
	779 <code>\cs_set_eq:NwN</code>	<code>\exp_not:N</code>	<code>\tex_noexpand:D</code>
	780 <code>\cs_set_eq:NwN</code>	<code>\exp_not:n</code>	<code>\etex_unexpanded:D</code>

<code>\iow_shipout_x:Nn</code>			
<code>\token_to_meaning:N</code>			
<code>\token_to_str:N</code>	781 <code>\cs_set_eq:NwN</code>	<code>\iow_shipout_x:Nn</code>	<code>\tex_write:D</code>
<code>\token_to_str:c</code>	782 <code>\cs_set_eq:NwN</code>	<code>\token_to_meaning:N</code>	<code>\tex_meaning:D</code>
<code>\cs:w</code>	783 <code>\cs_set_eq:NwN</code>	<code>\token_to_str:N</code>	<code>\tex_string:D</code>
<code>\cs_end:</code>	784 <code>\cs_set_eq:NwN</code>	<code>\cs:w</code>	<code>\tex_csname:D</code>
<code>\cs_meaning:N</code>	785 <code>\cs_set_eq:NwN</code>	<code>\cs_end:</code>	<code>\tex_endcsname:D</code>
<code>\cs_meaning:c</code>	786 <code>\cs_set_eq:NwN</code>	<code>\cs_meaning:N</code>	<code>\tex_meaning:D</code>
<code>\cs_show:N</code>	787 <code>\tex_def:D</code>	<code>\cs_meaning:c</code>	<code>{\exp_args:Nc\cs_meaning:N}</code>
<code>\cs_show:c</code>	788 <code>\cs_set_eq:NwN</code>	<code>\cs_show:N</code>	<code>\tex_show:D</code>
	789 <code>\tex_def:D</code>	<code>\cs_show:c</code>	<code>{\exp_args:Nc\cs_show:N}</code>
	790 <code>\tex_def:D</code>	<code>\token_to_str:c</code>	<code>{\exp_args:Nc\token_to_str:N}</code>

`\scan_stop:` The next three are basic functions for which there also exist versions that are safe inside  
`\group_begin:` alignments. These safe versions are defined in the `l3prg` module.  
`\group_end:`

```
791 \cs_set_eq:NwN \scan_stop: \tex_relax:D
792 \cs_set_eq:NwN \group_begin: \tex_begingroup:D
793 \cs_set_eq:NwN \group_end: \tex_endgroup:D
```

`\group_execute_after:N`

```
794 \cs_set_eq:NwN \group_execute_after:N \tex_aftergroup:D
```

`\pref_global:D`

`\pref_long:D`

`\pref_protected:D`

```
795 \cs_set_eq:NwN \pref_global:D \tex_global:D
796 \cs_set_eq:NwN \pref_long:D \tex_long:D
797 \cs_set_eq:NwN \pref_protected:D \etex_protected:D
```

## 95.2 Defining functions

We start by providing functions for the typical definition functions. First the local ones.

`\cs_set_nopar:Npn`

`\cs_set_nopar:Npx`

`\cs_set:Npn`

`\cs_set:Npx`

`\cs_set_protected_nopar:Npn`

`\cs_set_protected_nopar:Npx`

`\cs_set_protected:Npn`

`\cs_set_protected:Npx`

All assignment functions in L<sup>A</sup>T<sub>E</sub>X3 should be naturally robust; after all, the T<sub>E</sub>X primitives for assignments are and it can be a cause of problems if others aren't.

```
798 \cs_set_eq:NwN \cs_set_nopar:Npn \tex_def:D
799 \cs_set_eq:NwN \cs_set_nopar:Npx \tex_edef:D
800 \pref_protected:D \cs_set_nopar:Npn \cs_set:Npn {
801   \pref_long:D \cs_set_nopar:Npn
802 }
803 \pref_protected:D \cs_set_nopar:Npn \cs_set:Npx {
804   \pref_long:D \cs_set_nopar:Npx
805 }
806 \pref_protected:D \cs_set_nopar:Npn \cs_set_protected_nopar:Npn {
807   \pref_protected:D \cs_set_nopar:Npn
808 }
809 \pref_protected:D \cs_set_nopar:Npn \cs_set_protected_nopar:Npx {
810   \pref_protected:D \cs_set_nopar:Npx
811 }
812 \cs_set_protected_nopar:Npn \cs_set_protected:Npn {
813   \pref_protected:D \pref_long:D \cs_set_nopar:Npn
814 }
815 \cs_set_protected_nopar:Npn \cs_set_protected:Npx {
816   \pref_protected:D \pref_long:D \cs_set_nopar:Npx
817 }
```

`\cs_gset_nopar:Npn`

`\cs_gset_nopar:Npx`

`\cs_gset:Npn`

`\cs_gset:Npx`

`\cs_gset_protected_nopar:Npn`

`\cs_gset_protected_nopar:Npx`

`\cs_gset_protected:Npn`

`\cs_gset_protected:Npx`

Global versions of the above functions.

```
818 \cs_set_eq:NwN \cs_gset_nopar:Npn \tex_gdef:D
```

```

819 \cs_set_eq:NwN \cs_gset_nopar:Npx \tex_xdef:D
820 \cs_set_protected_nopar:Npn \cs_gset:Npn {
821   \pref_long:D \cs_gset_nopar:Npn
822 }
823 \cs_set_protected_nopar:Npn \cs_gset:Npx {
824   \pref_long:D \cs_gset_nopar:Npx
825 }
826 \cs_set_protected_nopar:Npn \cs_gset_protected_nopar:Npn {
827   \pref_protected:D \cs_gset_nopar:Npn
828 }
829 \cs_set_protected_nopar:Npn \cs_gset_protected_nopar:Npx {
830   \pref_protected:D \cs_gset_nopar:Npx
831 }
832 \cs_set_protected_nopar:Npn \cs_gset_protected:Npn {
833   \pref_protected:D \pref_long:D \cs_gset_nopar:Npn
834 }
835 \cs_set_protected_nopar:Npn \cs_gset_protected:Npx {
836   \pref_protected:D \pref_long:D \cs_gset_nopar:Npx
837 }

```

### 95.3 Selecting tokens

`\use:c` This macro grabs its argument and returns a csname from it.

```

838 \cs_set:Npn \use:c #1 { \cs:w#1\cs_end: }

```

`\use:n` These macro grabs its arguments and returns it back to the input (with outer braces removed). `\use:n` is defined earlier for bootstrapping.

```

\use:nnn
\use:nnnn
839 \cs_set:Npn \use:n #1 {#1}
840 \cs_set:Npn \use:nn #1#2 {#1#2}
841 \cs_set:Npn \use:nnn #1#2#3 {#1#2#3}
842 \cs_set:Npn \use:nnnn #1#2#3#4 {#1#2#3#4}

```

`\use_i:nn` These macros are needed to provide functions with true and false cases, as introduced by Michael some time ago. By using `\exp_after:wN \use_i:nn \else:` constructions it is possible to write code where the true or false case is able to access the following tokens from the input stream, which is not possible if the `\c_true_bool` syntax is used.

```

843 \cs_set:Npn \use_i:nn #1#2 {#1}
844 \cs_set:Npn \use_ii:nn #1#2 {#2}

```

`\use_i:nnn` We also need something for picking up arguments from a longer list.

```

\use_ii:nnn
\use_iii:nnn
\use_i:nnnn
\use_ii:nnnn
\use_iii:nnnn
\use_iv:nnnn
\use_i_ii:nnn
845 \cs_set:Npn \use_i:nnn #1#2#3{#1}
846 \cs_set:Npn \use_ii:nnn #1#2#3{#2}
847 \cs_set:Npn \use_iii:nnn #1#2#3{#3}
848 \cs_set:Npn \use_i:nnnn #1#2#3#4{#1}

```

```

849 \cs_set:Npn \use_ii:nnnn #1#2#3#4{#2}
850 \cs_set:Npn \use_iii:nnnn #1#2#3#4{#3}
851 \cs_set:Npn \use_iv:nnnn #1#2#3#4{#4}
852 \cs_set:Npn \use_i_ii:nnn #1#2#3{#1#2}

```

`\use_none_delimit_by_q_nil:w` Functions that gobble everything until they see either `\q_nil` or `\q_stop` resp.

```

\use_none_delimit_by_q_stop:w
\use_none_delimit_by_q_recursion_stop:w
853 \cs_set:Npn \use_none_delimit_by_q_nil:w #1\q_nil{}
854 \cs_set:Npn \use_none_delimit_by_q_stop:w #1\q_stop{}
855 \cs_set:Npn \use_none_delimit_by_q_recursion_stop:w #1 \q_recursion_stop {}

```

`\use_i_delimit_by_q_nil:nw` Same as above but execute first argument after gobbling. Very useful when you need to skip the rest of a mapping sequence but want an easy way to control what should be expanded next.

```

\use_i_delimit_by_q_stop:nw
\use_i_delimit_by_q_recursion_stop:nw
856 \cs_set:Npn \use_i_delimit_by_q_nil:nw #1#2\q_nil{#1}
857 \cs_set:Npn \use_i_delimit_by_q_stop:nw #1#2\q_stop{#1}
858 \cs_set:Npn \use_i_delimit_by_q_recursion_stop:nw #1#2 \q_recursion_stop {#1}

```

`\use_i_after_fi:nw` Returns the first argument after ending the conditional.

```

\use_i_after_else:nw
\use_i_after_or:nw
\use_i_after_orelse:nw
859 \cs_set:Npn \use_i_after_fi:nw #1\fi:{\fi: #1}
860 \cs_set:Npn \use_i_after_else:nw #1\else:#2\fi:{\fi: #1}
861 \cs_set:Npn \use_i_after_or:nw #1\or: #2\fi: {\fi:#1}
862 \cs_set:Npn \use_i_after_orelse:nw #1 #2#3\fi: {\fi:#1}

```

## 95.4 Gobbling tokens from input

`\use_none:n` To gobble tokens from the input we use a standard naming convention: the number of tokens gobbled is given by the number of `n`'s following the `:` in the name. Although defining `\use_none:nnn` and above as separate calls of `\use_none:n` and `\use_none:nn` is slightly faster, this is very non-intuitive to the programmer who will assume that expanding such a function once will take care of gobbling all the tokens in one go.

```

\use_none:nn
\use_none:nnn
\use_none:nnnn
\use_none:nnnnn
\use_none:nnnnnn
\use_none:nnnnnnn
\use_none:nnnnnnnn
\use_none:nnnnnnnnn
863 \cs_set:Npn \use_none:n #1{}
864 \cs_set:Npn \use_none:nn #1#2{}
865 \cs_set:Npn \use_none:nnn #1#2#3{}
866 \cs_set:Npn \use_none:nnnn #1#2#3#4{}
867 \cs_set:Npn \use_none:nnnnn #1#2#3#4#5{}
868 \cs_set:Npn \use_none:nnnnnn #1#2#3#4#5#6{}
869 \cs_set:Npn \use_none:nnnnnnn #1#2#3#4#5#6#7{}
870 \cs_set:Npn \use_none:nnnnnnnn #1#2#3#4#5#6#7#8{}
871 \cs_set:Npn \use_none:nnnnnnnnn #1#2#3#4#5#6#7#8#9{}

```

## 95.5 Expansion control from `l3expan`

`\exp_args:Nc` Moved here for now as it is going to be used right away.

```

872 \cs_set:Npn \exp_args:Nc #1#2{\exp_after:wN#1\cs:w#2\cs_end:}

```

## 95.6 Conditional processing and definitions

Underneath any predicate function (`_p`) or other conditional forms (TF, etc.) is a built-in logic saying that it after all of the testing and processing must return the *state* this leaves T<sub>E</sub>X in. Therefore, a simple user interface could be something like

```
\if_meaning:w #1#2 \prg_return_true: \else:
\if_meaning:w #1#3 \prg_return_true: \else:
\prg_return_false:
\fi: \fi:
```

Usually, a T<sub>E</sub>X programmer would have to insert a number of `\exp_after:wN`s to ensure the state value is returned at exactly the point where the last conditional is finished. However, that obscures the code and forces the T<sub>E</sub>X programmer to prove that he/she knows the  $2^n - 1$  table. We therefore provide the simpler interface.

`\prg_return_true:` These break statements put T<sub>E</sub>X in a *true* or *false* state. The idea is that the expansion of `\tex_romannumeral:D \c_zero` is *null* so we set off a `\tex_romannumeral:D`. It will on its way expand any `\else:` or `\fi:` that are waiting to be discarded anyway before finally arriving at the `\c_zero` we will place right after the conditional. After this expansion has terminated, we issue either `\if_true:` or `\if_false:` to put T<sub>E</sub>X in the correct state.

```
873 \cs_set:Npn \prg_return_true: { \exp_after:wN\if_true:\tex_romannumeral:D }
874 \cs_set:Npn \prg_return_false: { \exp_after:wN\if_false:\tex_romannumeral:D }
```

An extended state space could instead utilize `\tex_ifcase:D`:

```
\cs_set:Npn \prg_return_true: {
\exp_after:wN\tex_ifcase:D \exp_after:wN \c_zero \tex_romannumeral:D
}
\cs_set:Npn \prg_return_false: {
\exp_after:wN\tex_ifcase:D \exp_after:wN \c_one \tex_romannumeral:D
}
\cs_set:Npn \prg_return_error: {
\exp_after:wN\tex_ifcase:D \exp_after:wN \c_two \tex_romannumeral:D
}
```

`\prg_set_conditional:Npnn` The user functions for the types using parameter text from the programmer. Call aux function to grab parameters, split the base function into name and signature and then use, e.g., `\cs_set:Npn` to define it with.

```
875 \cs_set:Npn \prg_set_conditional:Npnn #1{
876 \prg_get_parm_aux:nw{
877 \cs_split_function:NN #1 \prg_generate_conditional_aux:nnNNnnnn
878 \cs_set:Npn {parm}
```

```

879 }
880 }
881 \cs_set:Npn \prg_new_conditional:Npnn #1{
882   \prg_get_parm_aux:nw{
883     \cs_split_function:NN #1 \prg_generate_conditional_aux:nnNNnnnn
884     \cs_new:Npn {parm}
885   }
886 }
887 \cs_set:Npn \prg_set_protected_conditional:Npnn #1{
888   \prg_get_parm_aux:nw{
889     \cs_split_function:NN #1 \prg_generate_conditional_aux:nnNNnnnn
890     \cs_set_protected:Npn {parm}
891   }
892 }
893 \cs_set:Npn \prg_new_protected_conditional:Npnn #1{
894   \prg_get_parm_aux:nw{
895     \cs_split_function:NN #1 \prg_generate_conditional_aux:nnNNnnnn
896     \cs_new_protected:Npn {parm}
897   }
898 }

```

\prg\_set\_conditional:Nnn  
 \prg\_new\_conditional:Nnn  
 \prg\_set\_protected\_conditional:Nnn  
 \prg\_new\_protected\_conditional:Nnn

The user functions for the types automatically inserting the correct parameter text based on the signature. Call aux function after calculating number of arguments, split the base function into name and signature and then use, e.g., \cs\_set:Npn to define it with.

```

899 \cs_set:Npn \prg_set_conditional:Nnn #1{
900   \exp_args:Nnf \prg_get_count_aux:nn{
901     \cs_split_function:NN #1 \prg_generate_conditional_aux:nnNNnnnn
902     \cs_set:Npn {count}
903   }{\cs_get_arg_count_from_signature:N #1}
904 }
905 \cs_set:Npn \prg_new_conditional:Nnn #1{
906   \exp_args:Nnf \prg_get_count_aux:nn{
907     \cs_split_function:NN #1 \prg_generate_conditional_aux:nnNNnnnn
908     \cs_new:Npn {count}
909   }{\cs_get_arg_count_from_signature:N #1}
910 }
911
912 \cs_set:Npn \prg_set_protected_conditional:Nnn #1{
913   \exp_args:Nnf \prg_get_count_aux:nn{
914     \cs_split_function:NN #1 \prg_generate_conditional_aux:nnNNnnnn
915     \cs_set_protected:Npn {count}
916   }{\cs_get_arg_count_from_signature:N #1}
917 }
918
919 \cs_set:Npn \prg_new_protected_conditional:Nnn #1{
920   \exp_args:Nnf \prg_get_count_aux:nn{
921     \cs_split_function:NN #1 \prg_generate_conditional_aux:nnNNnnnn
922     \cs_new_protected:Npn {count}
923   }{\cs_get_arg_count_from_signature:N #1}

```

924 }

\prg\_set\_eq\_conditional:NNn The obvious setting-equal functions.  
\prg\_new\_eq\_conditional:NNn

```
925 \cs_set:Npn \prg_set_eq_conditional:NNn #1#2#3 {
926   \prg_set_eq_conditional_aux:NNNn \cs_set_eq:cc #1#2 {#3}
927 }
928 \cs_set:Npn \prg_new_eq_conditional:NNn #1#2#3 {
929   \prg_set_eq_conditional_aux:NNNn \cs_new_eq:cc #1#2 {#3}
930 }
```

\prg\_get\_parm\_aux:nw For the Npnn type we must grab the parameter text before continuing. We make this  
\prg\_get\_count\_aux:nn a very generic function that takes one argument before reading everything up to a left  
brace. Something similar for the Nnn type.

```
931 \cs_set:Npn \prg_get_count_aux:nn #1#2 {#1{#2}}
932 \cs_set:Npn \prg_get_parm_aux:nw #1#2#{#1{#2}}
```

e\_conditional\_parm\_aux:nnNNnnnn The workhorse here is going through a list of desired forms, i.e., p, TF, T and F. The first  
generate\_conditional\_parm\_aux:nw three arguments come from splitting up the base form of the conditional, which gives the  
name, signature and a boolean to signal whether or not there was a colon in the name.  
For the time being, we do not use this piece of information but could well throw an error.  
The fourth argument is how to define this function, the fifth is the text **parm** or **count** for  
which version to use to define the functions, the sixth is the parameters to use (possibly  
empty) or number of arguments, the seventh is the list of forms to define, the eight is the  
replacement text which we will augment when defining the forms.

```
933 \cs_set:Npn \prg_generate_conditional_aux:nnNNnnnn #1#2#3#4#5#6#7#8{
934   \prg_generate_conditional_aux:nnw{#5}{
935     #4{#1}{#2}{#6}{#8}
936   }#7,?, \q_recursion_stop
937 }
```

Looping through the list of desired forms. First is the text **parm** or **count**, second is five  
arguments packed together and third is the form. Use text and form to call the correct  
type.

```
938 \cs_set:Npn \prg_generate_conditional_aux:nnw #1#2#3,{
939   \if:w ?#3
940     \exp_after:wN \use_none_delimit_by_q_recursion_stop:w
941   \fi:
942   \use:c{prg_generate_#3_form_#1:Nnnnn} #2
943   \prg_generate_conditional_aux:nnw{#1}{#2}
944 }
```

\prg\_generate\_p\_form\_parm:Nnnnn How to generate the various forms. The **parm** types here takes the following arguments:  
\prg\_generate\_TF\_form\_parm:Nnnnn 1: how to define (an N-type), 2: name, 3: signature, 4: parameter text (or empty), 5:  
\prg\_generate\_T\_form\_parm:Nnnnn replacement.  
\prg\_generate\_F\_form\_parm:Nnnnn



```

945 \cs_set:Npn \prg_generate_p_form_parm:Nnnnn #1#2#3#4#5{
946   \exp_args:Nc #1 {#2_p:#3}#4{#5 \c_zero
947     \exp_after:wN\c_true_bool\else:\exp_after:wN\c_false_bool\fi:
948   }
949 }
950 \cs_set:Npn \prg_generate_TF_form_parm:Nnnnn #1#2#3#4#5{
951   \exp_args:Nc#1 {#2:#3TF}#4{#5 \c_zero
952     \exp_after:wN \use_i:nn \else: \exp_after:wN \use_ii:nn \fi:
953   }
954 }
955 \cs_set:Npn \prg_generate_T_form_parm:Nnnnn #1#2#3#4#5{
956   \exp_args:Nc#1 {#2:#3T}#4{#5 \c_zero
957     \else:\exp_after:wN\use_none:nn\fi:\use:n
958   }
959 }
960 \cs_set:Npn \prg_generate_F_form_parm:Nnnnn #1#2#3#4#5{
961   \exp_args:Nc#1 {#2:#3F}#4{#5 \c_zero
962     \exp_after:wN\use_none:nn\fi:\use:n
963   }
964 }

```

```

prg_generate_p_form_count:Nnnnn
prg_generate_TF_form_count:Nnnnn
prg_generate_T_form_count:Nnnnn
prg_generate_F_form_count:Nnnnn

```

How to generate the various forms. The count types here use a number to insert the correct parameter text, otherwise like the parm functions above.

```

965 \cs_set:Npn \prg_generate_p_form_count:Nnnnn #1#2#3#4#5{
966   \cs_generate_from_arg_count:cNnn {#2_p:#3} #1 {#4}{#5 \c_zero
967     \exp_after:wN\c_true_bool\else:\exp_after:wN\c_false_bool\fi:
968   }
969 }
970 \cs_set:Npn \prg_generate_TF_form_count:Nnnnn #1#2#3#4#5{
971   \cs_generate_from_arg_count:cNnn {#2:#3TF} #1 {#4}{#5 \c_zero
972     \exp_after:wN\use_i:nn\else:\exp_after:wN\use_ii:nn\fi:
973   }
974 }
975 \cs_set:Npn \prg_generate_T_form_count:Nnnnn #1#2#3#4#5{
976   \cs_generate_from_arg_count:cNnn {#2:#3T} #1 {#4}{#5 \c_zero
977     \else:\exp_after:wN\use_none:nn\fi:\use:n
978   }
979 }
980 \cs_set:Npn \prg_generate_F_form_count:Nnnnn #1#2#3#4#5{
981   \cs_generate_from_arg_count:cNnn {#2:#3F} #1 {#4}{#5 \c_zero
982     \exp_after:wN\use_none:nn\fi:\use:n
983   }
984 }

```

```

prg_set_eq_conditional_aux:NNNn
prg_set_eq_conditional_aux:NNNw

```

```

985 \cs_set:Npn \prg_set_eq_conditional_aux:NNNn #1#2#3#4 {
986   \prg_set_eq_conditional_aux:NNNw #1#2#3#4,?,\q_recursion_stop
987 }

```

Manual clist loop over argument #4.

```

988 \cs_set:Npn \prg_set_eq_conditional_aux:NNNw #1#2#3#4, {
989   \if:w ? #4 \scan_stop:
990     \exp_after:wN \use_none_delimit_by_q_recursion_stop:w
991   \fi:
992   #1 {
993     \exp_args:NNc \cs_split_function:NN #2 {prg_conditional_form_#4:nnn}
994   }{
995     \exp_args:NNc \cs_split_function:NN #3 {prg_conditional_form_#4:nnn}
996   }
997   \prg_set_eq_conditional_aux:NNNw #1{#2}{#3}
998 }

999 \cs_set:Npn \prg_conditional_form_p:nnn #1#2#3 {#1_p:#2}
1000 \cs_set:Npn \prg_conditional_form_TF:nnn #1#2#3 {#1:#2TF}
1001 \cs_set:Npn \prg_conditional_form_T:nnn #1#2#3 {#1:#2T}
1002 \cs_set:Npn \prg_conditional_form_F:nnn #1#2#3 {#1:#2F}

```

All that is left is to define the canonical boolean true and false. I think Michael originated the idea of expandable boolean tests. At first these were supposed to expand into either TT or TF to be tested using `\if:w` but this was later changed to 00 and 01, so they could be used in logical operations. Later again they were changed to being numerical constants with values of 1 for true and 0 for false. We need this from the get-go.

```

\c_true_bool Here are the canonical boolean values.
\c_false_bool
1003 \tex_chardef:D \c_true_bool = 1~
1004 \tex_chardef:D \c_false_bool = 0~

```

## 95.7 Dissecting a control sequence

```

\cs_to_str:N This converts a control sequence into the character string of its name, removing the
\cs_to_str_aux:w leading escape character. This turns out to be a non-trivial matter as there are different
cases:

```

- The usual case of a printable escape character;
- the case of a non-printable escape characters, e.g., when the value of `\tex_escapechar:D` is negative;
- when the escape character is a space.

The route chosen is this: If `\token_to_str:N \a` produces a non-space escape char, then this will produce two tokens. If the escape char is non-printable, only one token is produced. If the escape char is a space, then a space token plus one token character token is produced. If we augment the result of this expansion with the letters `ax` we get the following three scenarios (with  $\langle X \rangle$  being a printable non-space escape character):

- $\langle X \rangle$ aax
- aax
- aax

In the second and third case, putting an auxiliary function in front reading undelimited arguments will treat them the same, removing the space token for us automatically. Therefore, if we test the second and third argument of what such a function reads, in case 1 we will get true and in cases 2 and 3 we will get false. If we choose to optimize for the usual case of a printable escape char, we can do it like this (again getting TeX to remove the leading space for us):

```

1005 \cs_set_nopar:Npn \cs_to_str:N {
1006   \if:w \exp_after:wN \cs_str_aux:w\token_to_str:N \a ax\q_nil
1007   \else:
1008     \exp_after:wN \exp_after:wN\exp_after:wN \use_ii:nn
1009   \fi:
1010   \exp_after:wN \use_none:n \token_to_str:N
1011 }
1012 \cs_set:Npn \cs_str_aux:w #1#2#3#4\q_nil{#2#3}

```

```

\cs_split_function:NN
\cs_split_function_aux:w
\cs_split_function_auxii:w

```

This function takes a function name and splits it into name with the escape char removed and argument specification. In addition to this, a third argument, a boolean  $\langle true \rangle$  or  $\langle false \rangle$  is returned with  $\langle true \rangle$  for when there is a colon in the function and  $\langle false \rangle$  if there is not. Lastly, the second argument of `\cs_split_function:NN` is supposed to be a function taking three variables, one for name, one for signature, and one for the boolean. For example, `\cs_split_function:NN\foo_bar:cnx\use_i:nnn` as input becomes `\use_i:nnn {foo_bar}{cnx}\c_true_bool`.

Can't use a literal `:` because it has the wrong catcode here, so it's transformed from `@` with `\tex_lowercase:D`.

```

1013 \group_begin:
1014   \tex_lccode:D '\@ = '\: \scan_stop:
1015   \tex_catcode:D '\@ = 12~
1016   \tex_lowercase:D {
1017     \group_end:

```

First ensure that we actually get a properly evaluated str as we don't know how many expansions `\cs_to_str:N` requires. Insert extra colon to catch the error cases.

```

1018 \cs_set:Npn \cs_split_function:NN #1#2{
1019   \exp_after:wN \cs_split_function_aux:w
1020   \tex_romannumeral:D -'\q \cs_to_str:N #1 @a \q_nil #2
1021 }

```

If no colon in the name, #2 is a with catcode 11 and #3 is empty. If colon in the name, then either #2 is a colon or the first letter of the signature. The letters here have catcode 12.

If a colon was given we need to a) split off the colon and quark at the end and b) ensure we return the name, signature and boolean true We can't use `\quark_if_no_value:NTF` yet but this is very safe anyway as all tokens have catcode 12.

```

1022 \cs_set:Npn \cs_split_function_aux:w #1@#2#3\q_nil#4{
1023   \if_meaning:w a#2
1024     \exp_after:wN \use_i:nn
1025   \else:
1026     \exp_after:wN\use_ii:nn
1027   \fi:
1028   {#4{#1}{}}\c_false_bool}
1029   {\cs_split_function_auxii:w#2#3\q_nil #4{#1}}
1030 }
1031 \cs_set:Npn \cs_split_function_auxii:w #1@a\q_nil#2#3{
1032   #2{#3}{#1}\c_true_bool
1033 }

```

End of lowercase

```

1034 }

```

`\cs_get_function_name:N` Now returning the name is trivial: just discard the last two arguments. Similar for  
`\cs_get_function_signature:N` signature.

```

1035 \cs_set:Npn \cs_get_function_name:N #1 {
1036   \cs_split_function:NN #1\use_i:nnn
1037 }
1038 \cs_set:Npn \cs_get_function_signature:N #1 {
1039   \cs_split_function:NN #1\use_ii:nnn
1040 }

```

## 95.8 Exist or free

A control sequence is said to *exist* (to be used) if has an entry in the hash table and its meaning is different from the primitive `\tex_relax:D` token. A control sequence is said to be *free* (to be defined) if it does not already exist and also meets the requirement that it does not contain a D signature. The reasoning behind this is that most of the time, a check for a free control sequence is when we wish to make a new control sequence and we do not want to let the user define a new “do not use” control sequence.

`\cs_if_exist_p:N` Two versions for checking existence. For the N form we firstly check for `\tex_relax:D`  
`\cs_if_exist_p:c` and then if it is in the hash table. There is no problem when inputting something like  
`\cs_if_exist:NTF` `\else:` or `\fi:` as  $\TeX$  will only ever skip input in case the token tested against is  
`\cs_if_exist:cTF` `\tex_relax:D`.

```

1041 \prg_set_conditional:Npnn \cs_if_exist:N #1 {p,TF,T,F}{
1042   \if_meaning:w #1\tex_relax:D
1043   \prg_return_false:

```

```

1044 \else:
1045   \if_cs_exist:N #1
1046   \prg_return_true:
1047 \else:
1048   \prg_return_false:
1049 \fi:
1050 \fi:
1051 }

```

For the `c` form we firstly check if it is in the hash table and then for `\tex_relax:D` so that we do not add it to the hash table unless it was already there. Here we have to be careful as the text to be skipped if the first test is false may contain tokens that disturb the scanner. Therefore, we ensure that the second test is performed after the first one has concluded completely.

```

1052 \prg_set_conditional:Npnn \cs_if_exist:c #1 {p,TF,T,F}{
1053   \if_cs_exist:w #1 \cs_end:
1054   \exp_after:wN \use_i:nn
1055 \else:
1056   \exp_after:wN \use_ii:nn
1057 \fi:
1058 {
1059   \exp_after:wN \if_meaning:w \cs:w #1\cs_end: \tex_relax:D
1060   \prg_return_false:
1061 \else:
1062   \prg_return_true:
1063 \fi:
1064 }
1065 \prg_return_false:
1066 }

```

```

\cs_if_do_not_use_p:N
\cs_if_do_not_use_aux:nnN

```

```

1067 \cs_set:Npn \cs_if_do_not_use_p:N #1{
1068   \cs_split_function:NN #1 \cs_if_do_not_use_aux:nnN
1069 }
1070 \cs_set:Npn \cs_if_do_not_use_aux:nnN #1#2#3{
1071   \exp_after:wN\str_if_eq_p:nn \token_to_str:N D {#2}
1072 }

```

`\cs_if_free_p:N` The simple implementation is one using the boolean expression parser: If it exists or  
`\cs_if_free_p:c` is do not use, then return false.

`\cs_if_free:N $\underline{TF}$`

```

\cs_if_free:c $\underline{TF}$  \prg_set_conditional:Npnn \cs_if_free:N #1{p,TF,T,F}{
  \bool_if:nTF {\cs_if_exist_p:N #1 || \cs_if_do_not_use_p:N #1}
  {\prg_return_false:}{\prg_return_true:}
}

```

However, this functionality may not be available this early on. We do something similar: The numerical values of true and false is one and zero respectively, which we can use. The problem again here is that the token we are checking may in fact be something that can disturb the scanner, so we have to be careful. We would like to do minimal evaluation so we ensure this.

```

1073 \prg_set_conditional:Npnn \cs_if_free:N #1{p,TF,T,F}{
1074   \tex_ifnum:D \cs_if_exist_p:N #1 =\c_zero
1075   \exp_after:wN \use_i:nn
1076   \else:
1077   \exp_after:wN \use_ii:nn
1078   \fi:
1079   {
1080   \tex_ifnum:D \cs_if_do_not_use_p:N #1 =\c_zero
1081   \prg_return_true:
1082   \else:
1083   \prg_return_false:
1084   \fi:
1085   }
1086   \prg_return_false:
1087 }
1088 \cs_set_nopar:Npn \cs_if_free_p:c{\exp_args:Nc\cs_if_free_p:N}
1089 \cs_set_nopar:Npn \cs_if_free:cTF{\exp_args:Nc\cs_if_free:NTF}
1090 \cs_set_nopar:Npn \cs_if_free:cT{\exp_args:Nc\cs_if_free:NT}
1091 \cs_set_nopar:Npn \cs_if_free:cF{\exp_args:Nc\cs_if_free:NF}

```

## 95.9 Defining and checking (new) functions

`\c_minus_one` We need the constants `\c_minus_one` and `\c_sixteen` now for writing information to the log and the terminal and `\c_zero` which is used by some functions in the `l3nummodule`.  
`\c_zero` The rest are defined in the `l3int` module – at least for the ones that can be defined with `\tex_chardef:D` or `\tex_mathchardef:D`. For other constants the `l3int` module is required but it can't be used until the allocation has been set up properly! The actual allocation mechanism is in `l3alloc` and as  $\text{\TeX}$  wants to reserve count registers 0–9, the first available one is 10 so we use that for `\c_minus_one`.  
`\c_sixteen`

```

1092 <!*initex>
1093 \cs_set_eq:NwN \c_minus_one\m@ne
1094 </!*initex>
1095 <!*package>
1096 \tex_countdef:D \c_minus_one = 10 ~
1097 \c_minus_one = -1 ~
1098 </!*package>
1099 \tex_chardef:D \c_sixteen = 16~
1100 \tex_chardef:D \c_zero = 0~

```

We provide two kinds of functions that can be used to define control sequences. On the one hand we have functions that check if their argument doesn't already exist, they are

called `\..._new`. The second type of defining functions doesn't check if the argument is already defined.

Before we can define them, we need some auxiliary macros that allow us to generate error messages. The definitions here are only temporary, they will be redefined later on.

`\iow_log:x` We define a routine to write only to the log file. And a similar one for writing to both  
`\iow_term:x` the log file and the terminal.

```
1101 \cs_set_nopar:Npn \iow_log:x {
1102   \tex_immediate:D \iow_shipout_x:Nn \c_minus_one
1103 }
1104 \cs_set_nopar:Npn \iow_term:x {
1105   \tex_immediate:D \iow_shipout_x:Nn \c_sixteen
1106 }
```

`\msg_kernel_bug:x` This will show internal errors.

```
1107 \cs_set_nopar:Npn \msg_kernel_bug:x #1 {
1108   \iow_term:x { This~is~a~LaTeX~bug:~check~coding! }
1109   \tex_errmessage:D {#1}
1110 }
```

`\cs_record_meaning:N` This macro will be used later on for tracing purposes. But we need some more modules to define it, so we just give some dummy definition here.

```
1111 <*trace>
1112 \cs_set:Npn \cs_record_meaning:N #1{}
1113 </trace>
```

`\chk_if_free_cs:N` This command is called by `\cs_new_nopar:Npn` and `\cs_new_eq:NN` etc. to make sure  
`\chk_if_free_cs:c` that the argument sequence is not already in use. If it is, an error is signalled. It checks if `<cname>` is undefined or `\scan_stop:.` Otherwise an error message is issued. We have to make sure we don't put the argument into the conditional processing since it may be an `\if...` type function!

```
1114 \cs_set_nopar:Npn \chk_if_free_cs:N #1{
1115   \cs_if_free:NF #1
1116   {
1117     \msg_kernel_bug:x {Command~name~'\token_to_str:N #1'~
1118                       already~defined!~
1119                       Current~meaning:~\token_to_meaning:N #1
1120                       }
1121   }
1122 <*trace>
1123   \cs_record_meaning:N#1
1124 %   \iow_term:x{Defining~\token_to_str:N #1~on~%}
1125   \iow_log:x{Defining~\token_to_str:N #1~on~
1126             line~\tex_the:D \tex_inputlineno:D}
```

```

1127 </trace>
1128 }
1129 \cs_set_nopar:Npn \chk_if_free_cs:c { \exp_args:Nc \chk_if_free_cs:N }

```

`\chk_if_exist_cs:N` This function issues a warning message when the control sequence in its argument does not exist.

`\chk_if_exist_cs:c`

```

1130 \cs_set_nopar:Npn \chk_if_exist_cs:N #1 {
1131   \cs_if_exist:NF #1
1132   {
1133     \msg_kernel_bug:x {Command~ '\token_to_str:N #1'~
1134                       not~ yet~ defined!}
1135   }
1136 }
1137 \cs_set_nopar:Npn \chk_if_exist_cs:c {\exp_args:Nc \chk_if_exist_cs:N }

```

`\str_if_eq_p:nn` Takes 2 lists of characters as arguments and expands into `\c_true_bool` if they are equal, and `\c_false_bool` otherwise. Note that in the current implementation spaces in these strings are ignored.<sup>8</sup>

`\str_if_eq_p_aux:w`

```

1138 \prg_set_conditional:Npnn \str_if_eq:nn #1#2{p}{
1139   \str_if_eq_p_aux:w #1\scan_stop:\#2\scan_stop:\
1140 }
1141 \cs_set_nopar:Npn \str_if_eq_p_aux:w #1#2\#3#4\#{
1142   \if_meaning:w#1#3
1143   \if_meaning:w#1\scan_stop:\prg_return_true: \else:
1144   \if_meaning:w#3\scan_stop:\prg_return_false: \else:
1145   \str_if_eq_p_aux:w #2\#4\#fi:\fi:
1146   \else:\prg_return_false: \fi:}

```

`\cs_if_eq_name_p:NN` An application of the above function, already streamlined for speed, so I put it in here. It takes two control sequences as arguments and expands into true iff they have the same name. We make it long in case one of them is `\par`!

```

1147 \prg_set_conditional:Npnn \cs_if_eq_name:NN #1#2{p}{
1148   \exp_after:wN\exp_after:wN
1149   \exp_after:wN\str_if_eq_p_aux:w
1150   \exp_after:wN\token_to_str:N
1151   \exp_after:wN#1
1152   \exp_after:wN\scan_stop:
1153   \exp_after:wN\
1154   \token_to_str:N#2\scan_stop:\}

```

`\str_if_eq_var_p:nf` A variant of `\str_if_eq_p:nn` which has the advantage of obeying spaces in at least the second argument. See l3quark for an application. From the hand of David Kastrup with slight modifications to make it fit with the remainder of the expl3 language.

`\str_if_eq_var_start:nnN`

`\str_if_eq_var_stop:w`

---

<sup>8</sup>This is a function which could use `\tlist_compare:xx`.



The macro builds a string of `\if:w \fi:` pairs from the first argument. The idea is to turn the comparison of `ab` and `cde` into

```
\tex_number:D
  \if:w \scan_stop: \if:w b\if:w a cde\scan_stop: '\fi: \fi: \fi:
13
```

The `'` is important here. If all tests are true, the `'` is read as part of the number in which case the returned number is 13 in octal notation so `\tex_number:D` returns 11. If one test returns false the `'` is never seen and then we get just 13. We wrap the whole process in an external `\if:w` in order to make it return either `\c_true_bool` or `\c_false_bool` since some parts of `l3prg` expect a predicate to return one of these two tokens.

```
1155 \prg_set_conditional:Npnn \str_if_eq_var:nf #1#2 {p} {
1156   \if:w \tex_number:D\str_if_eq_var_start:nnN{}-{}#1\scan_stop:{#2}
1157 }
1158 \cs_set_nopar:Npn\str_if_eq_var_start:nnN#1#2#3{
1159   \if:w#3\scan_stop:\exp_after:wN\str_if_eq_var_stop:w\fi:
1160   \str_if_eq_var_start:nnN{\if:w#3#1}{#2\fi:}
1161 }
1162 \cs_set:Npn\str_if_eq_var_stop:w\str_if_eq_var_start:nnN#1#2#3{
1163   #1#3\scan_stop:'#213~\prg_return_true:\else:\prg_return_false:\fi:
1164 }
```

## 95.10 More new definitions

`\cs_new_nopar:Npn` These are like `\cs_set_nopar:Npn` and `\cs_set_eq:NN`, but they first check that the argument command is not already in use. You may use `\pref_global:D`, `\pref_long:D`, `\pref_protected:D`, and `\tex_outer:D` as prefixes.

```
\cs_new_nopar:Npn
\cs_new_nopar:Npx
  \cs_new:Npn
  \cs_new:Npx
\cs_new_protected_nopar:Npn
\cs_new_protected_nopar:Npx
  \cs_new_protected:Npn
  \cs_new_protected:Npx
1165 \cs_set:Npn \cs_tmp:w #1#2{
1166   \cs_set_protected_nopar:Npn #1 ##1 {
1167     \chk_if_free_cs:N ##1
1168     #2 ##1
1169   }
1170 }
1171 \cs_tmp:w \cs_new_nopar:Npn \cs_set_nopar:Npn
1172 \cs_tmp:w \cs_new_nopar:Npx\cs_set_nopar:Npx
1173 \cs_tmp:w \cs_new:Npn \cs_set:Npn
1174 \cs_tmp:w \cs_new:Npx\cs_set:Npx
1175 \cs_tmp:w \cs_new_protected_nopar:Npn \cs_set_protected_nopar:Npn
1176 \cs_tmp:w \cs_new_protected_nopar:Npx\cs_set_protected_nopar:Npx
1177 \cs_tmp:w \cs_new_protected:Npn \cs_set_protected:Npn
1178 \cs_tmp:w \cs_new_protected:Npx\cs_set_protected:Npx
```

`\cs_gnew_nopar:Npn` Global versions of the above functions.

```
\cs_gnew_nopar:Npn
\cs_gnew_nopar:Npx
  \cs_gnew:Npn
  \cs_gnew:Npx
\cs_gnew_protected_nopar:Npn
\cs_gnew_protected_nopar:Npx
  \cs_gnew_protected:Npn
  \cs_gnew_protected:Npx
```

```

1179 \cs_tmp:w \cs_gnew_nopar:Npn \cs_gset_nopar:Npn
1180 \cs_tmp:w \cs_gnew_nopar:Npx \cs_gset_nopar:Npx
1181 \cs_tmp:w \cs_gnew:Npn \cs_gset:Npn
1182 \cs_tmp:w \cs_gnew:Npx \cs_gset:Npx
1183 \cs_tmp:w \cs_gnew_protected_nopar:Npn \cs_gset_protected_nopar:Npn
1184 \cs_tmp:w \cs_gnew_protected_nopar:Npx \cs_gset_protected_nopar:Npx
1185 \cs_tmp:w \cs_gnew_protected:Npn \cs_gset_protected:Npn
1186 \cs_tmp:w \cs_gnew_protected:Npx \cs_gset_protected:Npx

```

`\cs_set_nopar:cpn` Like `\cs_set_nopar:Npn` and `\cs_new_nopar:Npn`, except that the first argument consists of the sequence of characters that should be used to form the name of the desired control sequence (the `c` stands for `csname` argument, see the expansion module). Global versions are also provided.

`\cs_set_nopar:cpn`  $\langle string \rangle \langle rep-text \rangle$  will turn  $\langle string \rangle$  into a `csname` and then assign  $\langle rep-text \rangle$  to it by using `\cs_set_nopar:Npn`. This means that there might be a parameter string between the two arguments.

```

1187 \cs_set:Npn \cs_tmp:w #1#2{
1188   \cs_new_nopar:Npn #1 { \exp_args:Nc #2 }
1189 }
1190 \cs_tmp:w \cs_set_nopar:cpn \cs_set_nopar:Npn
1191 \cs_tmp:w \cs_set_nopar:cpx \cs_set_nopar:Npx
1192 \cs_tmp:w \cs_gset_nopar:cpn \cs_gset_nopar:Npn
1193 \cs_tmp:w \cs_gset_nopar:cpx \cs_gset_nopar:Npx
1194 \cs_tmp:w \cs_new_nopar:cpn \cs_new_nopar:Npn
1195 \cs_tmp:w \cs_new_nopar:cpx \cs_new_nopar:Npx
1196 \cs_tmp:w \cs_gnew_nopar:cpn \cs_gnew_nopar:Npn
1197 \cs_tmp:w \cs_gnew_nopar:cpx \cs_gnew_nopar:Npx

```

`\cs_set:cpn` Variants of the `\cs_set:Npn` versions which make a `csname` out of the first arguments. We may also do this globally.

```

1198 \cs_tmp:w \cs_set:cpn \cs_set:Npn
1199 \cs_tmp:w \cs_set:cpx \cs_set:Npx
1200 \cs_tmp:w \cs_gset:cpn \cs_gset:Npn
1201 \cs_tmp:w \cs_gset:cpx \cs_gset:Npx
1202 \cs_tmp:w \cs_new:cpn \cs_new:Npn
1203 \cs_tmp:w \cs_new:cpx \cs_new:Npx
1204 \cs_tmp:w \cs_gnew:cpn \cs_gnew:Npn
1205 \cs_tmp:w \cs_gnew:cpx \cs_gnew:Npx

```

`\cs_set_protected_nopar:cpn` Variants of the `\cs_set_protected_nopar:Npn` versions which make a `csname` out of the first arguments. We may also do this globally.

```

1206 \cs_tmp:w \cs_set_protected_nopar:cpn \cs_set_protected_nopar:Npn
1207 \cs_tmp:w \cs_set_protected_nopar:cpx \cs_set_protected_nopar:Npx
1208 \cs_tmp:w \cs_gset_protected_nopar:cpn \cs_gset_protected_nopar:Npn
1209 \cs_tmp:w \cs_gset_protected_nopar:cpx \cs_gset_protected_nopar:Npx

```

```

1210 \cs_tmp:w \cs_new_protected_nopar:cpn \cs_new_protected_nopar:Npn
1211 \cs_tmp:w \cs_new_protected_nopar:cpx \cs_new_protected_nopar:Npx
1212 \cs_tmp:w \cs_gnew_protected_nopar:cpn \cs_gnew_protected_nopar:Npn
1213 \cs_tmp:w \cs_gnew_protected_nopar:cpx \cs_gnew_protected_nopar:Npx

```

\cs\_set\_protected:cpn Variants of the \cs\_set\_protected:Npn versions which make a csname out of the first arguments. We may also do this globally.

```

\cs_set_protected:cpx
\cs_gset_protected:cpn
\cs_gset_protected:cpx
\cs_new_protected:cpn
\cs_new_protected:cpx
\cs_gnew_protected:cpn
\cs_gnew_protected:cpx
1214 \cs_tmp:w \cs_set_protected:cpn \cs_set_protected:Npn
1215 \cs_tmp:w \cs_set_protected:cpx \cs_set_protected:Npx
1216 \cs_tmp:w \cs_gset_protected:cpn \cs_gset_protected:Npn
1217 \cs_tmp:w \cs_gset_protected:cpx \cs_gset_protected:Npx
1218 \cs_tmp:w \cs_new_protected:cpn \cs_new_protected:Npn
1219 \cs_tmp:w \cs_new_protected:cpx \cs_new_protected:Npx
1220 \cs_tmp:w \cs_gnew_protected:cpn \cs_gnew_protected:Npn
1221 \cs_tmp:w \cs_gnew_protected:cpx \cs_gnew_protected:Npx

```

\use\_0\_parameter: For using parameters, i.e., when you need to define a function to process three parameters. See xparse for an application.

```

\use_1_parameter:
\use_2_parameter:
\use_3_parameter:
\use_4_parameter:
\use_5_parameter:
\use_6_parameter:
\use_7_parameter:
\use_8_parameter:
\use_9_parameter:
1222 \cs_set_nopar:cpn{use_0_parameter:}{}
1223 \cs_set_nopar:cpn{use_1_parameter:}{{##1}}
1224 \cs_set_nopar:cpn{use_2_parameter:}{{##1}{##2}}
1225 \cs_set_nopar:cpn{use_3_parameter:}{{##1}{##2}{##3}}
1226 \cs_set_nopar:cpn{use_4_parameter:}{{##1}{##2}{##3}{##4}}
1227 \cs_set_nopar:cpn{use_5_parameter:}{{##1}{##2}{##3}{##4}{##5}}
1228 \cs_set_nopar:cpn{use_6_parameter:}{{##1}{##2}{##3}{##4}{##5}{##6}}
1229 \cs_set_nopar:cpn{use_7_parameter:}{{##1}{##2}{##3}{##4}{##5}{##6}{##7}}
1230 \cs_set_nopar:cpn{use_8_parameter:}{{
1231   {##1}{##2}{##3}{##4}{##5}{##6}{##7}{##8}}
1232 \cs_set_nopar:cpn{use_9_parameter:}{{
1233   {##1}{##2}{##3}{##4}{##5}{##6}{##7}{##8}{##9}}

```

## 95.11 Copying definitions

\cs\_set\_eq:NN These macros allow us to copy the definition of a control sequence to another control sequence.

\cs\_set\_eq:cN  
\cs\_set\_eq:Nc  
\cs\_set\_eq:cc  
The = sign allows us to define funny char tokens like = itself or  $\sqcup$  with this function. For the definition of \c\_space\_chartok{~} to work we need the ~ after the =.

\cs\_set\_eq:NN is long to avoid problems with a literal argument of \par. While \cs\_new\_eq:NN will probably never be correct with a first argument of \par, define it long in order to throw an ‘already defined’ error rather than ‘runaway argument’.

The c variants are not protected in order for their arguments to be constructed in the correct context.

```

1234 \cs_set_protected:Npn \cs_set_eq:NN #1 { \cs_set_eq:NwN #1=~ }

```

```

1235 \cs_set_nopar:Npn \cs_set_eq:cN { \exp_args:Nc \cs_set_eq:NN }
1236 \cs_set_nopar:Npn \cs_set_eq:Nc { \exp_args:NNc \cs_set_eq:NN }
1237 \cs_set_nopar:Npn \cs_set_eq:cc { \exp_args:Ncc \cs_set_eq:NN }

\cs_new_eq:NN
\cs_new_eq:cN
\cs_new_eq:Nc
\cs_new_eq:cc
1238 \cs_new_protected:Npn \cs_new_eq:NN #1 {
1239   \chk_if_free_cs:N #1
1240   \cs_set_eq:NN #1
1241 }
1242 \cs_new_nopar:Npn \cs_new_eq:cN { \exp_args:Nc \cs_new_eq:NN }
1243 \cs_new_nopar:Npn \cs_new_eq:Nc { \exp_args:NNc \cs_new_eq:NN }
1244 \cs_new_nopar:Npn \cs_new_eq:cc { \exp_args:Ncc \cs_new_eq:NN }

\cs_gset_eq:NN
\cs_gset_eq:cN
\cs_gset_eq:Nc
\cs_gset_eq:cc
1245 \cs_new_protected:Npn \cs_gset_eq:NN { \pref_global:D \cs_set_eq:NN }
1246 \cs_new_nopar:Npn \cs_gset_eq:Nc { \exp_args:NNc \cs_gset_eq:NN }
1247 \cs_new_nopar:Npn \cs_gset_eq:cN { \exp_args:Nc \cs_gset_eq:NN }
1248 \cs_new_nopar:Npn \cs_gset_eq:cc { \exp_args:Ncc \cs_gset_eq:NN }

\cs_gnew_eq:NN
\cs_gnew_eq:cN
\cs_gnew_eq:Nc
\cs_gnew_eq:cc
1249 \cs_new_protected:Npn \cs_gnew_eq:NN #1 {
1250   \chk_if_free_cs:N #1
1251   \pref_global:D \cs_set_eq:NN #1
1252 }
1253 \cs_new_nopar:Npn \cs_gnew_eq:cN { \exp_args:Nc \cs_gnew_eq:NN }
1254 \cs_new_nopar:Npn \cs_gnew_eq:Nc { \exp_args:NNc \cs_gnew_eq:NN }
1255 \cs_new_nopar:Npn \cs_gnew_eq:cc { \exp_args:Ncc \cs_gnew_eq:NN }

```

## 95.12 undefining functions

`\cs_gundefine:N` The following function is used to free the main memory from the definition of some function that isn't in use any longer.

```

1256 \cs_new_nopar:Npn \cs_gundefine:N #1{\cs_gset_eq:NN #1\c_undefined:D}
1257 \cs_new_nopar:Npn \cs_gundefine:c #1{
1258   \cs_gset_eq:cN {#1} \c_undefined:D
1259 }

```

## 95.13 Engine specific definitions

`\c_xetex_is_engine_bool` In some cases it will be useful to know which engine we're running. Don't provide a `_p` predicate because the `_bool` is used for the same thing.

```

\c luatex_is_engine_bool
\c_xetex_is_engine_bool
\c_luatex_is_engine_bool
\c_xetex_if_engine:TF
\c_luatex_if_engine:TF
1260 \if_cs_exist:N \xetex_version:D

```

```

1261 \cs_new_eq:NN \c_xetex_is_engine_bool \c_true_bool
1262 \else:
1263 \cs_new_eq:NN \c_xetex_is_engine_bool \c_false_bool
1264 \fi:
1265 \prg_new_conditional:Npnn \xetex_if_engine: {TF,T,F} {
1266 \if_bool:N \c_xetex_is_engine_bool
1267 \prg_return_true: \else: \prg_return_false: \fi:
1268 }

1269 \if_cs_exist:N \luatex_directlua:D
1270 \cs_new_eq:NN \c_luatex_is_engine_bool \c_true_bool
1271 \else:
1272 \cs_new_eq:NN \c_luatex_is_engine_bool \c_false_bool
1273 \fi:
1274 \prg_set_conditional:Npnn \xetex_if_engine: {TF,T,F}{
1275 \if_bool:N \c_xetex_is_engine_bool \prg_return_true:
1276 \else: \prg_return_false: \fi:
1277 }
1278 \prg_set_conditional:Npnn \luatex_if_engine: {TF,T,F}{
1279 \if_bool:N \c_luatex_is_engine_bool \prg_return_true:
1280 \else: \prg_return_false: \fi:
1281 }

```

## 95.14 Scratch functions

`\prg_do_nothing:` I don't think this function belongs here, but one place is as good as any other. I want to use this function when I want to express 'no operation'. It is for example used in templates where depending on the users settings we have to either select an function that does something, or one that does nothing.

```

1282 \cs_new_nopar:Npn \prg_do_nothing: {}

```

## 95.15 Defining functions from a given number of arguments

`\get_arg_count_from_signature:N` Counting the number of tokens in the signature, i.e., the number of arguments the function should take. If there is no signature, we return that there is  $-1$  arguments to signal an error. Otherwise we insert the string 9876543210 after the signature. If the signature is empty, the number we want is 0 so we remove the first nine tokens and return the tenth. Similarly, if the signature is `nnn` we want to remove the nine tokens `nnn987654` and return 3. Therefore, we simply remove the first nine tokens and then return the tenth.

```

1283 \cs_set:Npn \cs_get_arg_count_from_signature:N #1{
1284 \cs_split_function:NN #1 \cs_get_arg_count_from_signature_aux:nnN
1285 }
1286 \cs_set:Npn \cs_get_arg_count_from_signature_aux:nnN #1#2#3{
1287 \if_predicate:w #3 % \bool_if:NTF here

```

```

1288 \exp_after:wN \use_i:nn
1289 \else:
1290 \exp_after:wN\use_ii:nn
1291 \fi:
1292 {
1293 \exp_after:wN \cs_get_arg_count_from_signature_auxii:w
1294 \use_none:nnnnnnnn #2 9876543210\q_nil
1295 }
1296 {-1}
1297 }
1298 \cs_set:Npn \cs_get_arg_count_from_signature_auxii:w #1#2\q_nil{#1}

```

A variant form we need right away.

```

1299 \cs_set_nopar:Npn \cs_get_arg_count_from_signature:c {
1300 \exp_args:Nc \cs_get_arg_count_from_signature:N
1301 }

```

```

\cs_generate_from_arg_count:NNnn
\cs_get_arg_count_error_msg:Nn

```

We provide a constructor function for defining functions with a given number of arguments. For this we need to choose the correct parameter text and then use that when defining. Since  $\text{\TeX}$  supports from zero to nine arguments, we use a simple switch to choose the correct parameter text, ensuring the result is returned after finishing the conditional. If it is not between zero and nine, we throw an error.

1: function to define, 2: with what to define it, 3: the number of args it requires and 4: the replacement text

```

1302 \cs_set:Npn \cs_generate_from_arg_count:NNnn #1#2#3#4{
1303 \tex_ifcase:D \etex_numexpr:D #3\tex_relax:D
1304 \use_i_after_orelse:nw{#2#1}
1305 \or:
1306 \use_i_after_orelse:nw{#2#1 ##1}
1307 \or:
1308 \use_i_after_orelse:nw{#2#1 ##1##2}
1309 \or:
1310 \use_i_after_orelse:nw{#2#1 ##1##2##3}
1311 \or:
1312 \use_i_after_orelse:nw{#2#1 ##1##2##3##4}
1313 \or:
1314 \use_i_after_orelse:nw{#2#1 ##1##2##3##4##5}
1315 \or:
1316 \use_i_after_orelse:nw{#2#1 ##1##2##3##4##5##6}
1317 \or:
1318 \use_i_after_orelse:nw{#2#1 ##1##2##3##4##5##6##7}
1319 \or:
1320 \use_i_after_orelse:nw{#2#1 ##1##2##3##4##5##6##7##8}
1321 \or:
1322 \use_i_after_orelse:nw{#2#1 ##1##2##3##4##5##6##7##8##9}
1323 \else:
1324 \use_i_after_fi:nw{

```

```

1325     \cs_generate_from_arg_count_error_msg:Nn#1{#3}
1326     \use_none:n % to remove replacement text
1327   }
1328   \fi:
1329   {#4}
1330 }

```

A variant form we need right away.

```

1331 \cs_set_nopar:Npn \cs_generate_from_arg_count:cNnn {
1332   \exp_args:Nc \cs_generate_from_arg_count:NNnn
1333 }

```

The error message. Elsewhere we use the value of  $-1$  to signal a missing colon in a function, so provide a hint for help on this.

```

1334 \cs_set:Npn \cs_generate_from_arg_count_error_msg:Nn #1#2 {
1335   \msg_kernel_bug:x {
1336     You're~ trying~ to~ define~ the~ command~ '\token_to_str:N #1'~
1337     with~ \use:n{\tex_the:D\etex_numexpr:D #2\tex_relax:D} ~
1338     arguments~ but~ I~ only~ allow~ 0-9~arguments.~Perhaps~you~
1339     forgot~to~use~a~colon~in~the~function~name?~
1340     I~ can~ probably~ not~ help~ you~ here
1341   }
1342 }

```

## 95.16 Using the signature to define functions

We can now combine some of the tools we have to provide a simple interface for defining functions. We define some simpler functions with user interface `\cs_set:Nn \foo_bar:nn {#1,#2}`, i.e., the number of arguments is read from the signature.

```

\cs_set:Nn We want to define \cs_set:Nn as
\cs_set:Nx
\cs_set_nopar:Nn \cs_set_protected:Npn \cs_set:Nn #1#2{
\cs_set_nopar:Nx \cs_generate_from_arg_count:NNnn #1\cs_set:Npn
\cs_set_protected:Nn {\cs_get_arg_count_from_signature:N #1}{#2}
\cs_set_protected:Nx }
\cs_set_protected_nopar:Nn
\cs_set_protected_nopar:Nx
\cs_gset:Nn In short, to define \cs_set:Nn we need just use \cs_set:Npn, everything else is the same
\cs_gset:Nx for each variant. Therefore, we can make it simpler by temporarily defining a function
\cs_gset_nopar:Nn to do this for us.
\cs_gset_nopar:Nx
\cs_gset_protected:Nn 1343 \cs_set:Npn \cs_tmp:w #1#2#3{
\cs_gset_protected:Nx 1344 \cs_set_protected:cpx {cs_#1:#2}##1##2{
1345   \exp_not:N \cs_generate_from_arg_count:NNnn ##1
\cs_gset_protected_nopar:Nn 1346   \exp_after:wN \exp_not:N \cs:w cs_#1:#3 \cs_end:
\cs_gset_protected_nopar:Nx

```

```

1347         {\exp_not:N\cs_get_arg_count_from_signature:N ##1}{##2}
1348     }
1349 }

```

Then we define the 32 variants beginning with N.

```

1350 \cs_tmp:w {set}{Nn}{Npn}
1351 \cs_tmp:w {set}{Nx}{Npx}
1352 \cs_tmp:w {set_nopar}{Nn}{Npn}
1353 \cs_tmp:w {set_nopar}{Nx}{Npx}
1354 \cs_tmp:w {set_protected}{Nn}{Npn}
1355 \cs_tmp:w {set_protected}{Nx}{Npx}
1356 \cs_tmp:w {set_protected_nopar}{Nn}{Npn}
1357 \cs_tmp:w {set_protected_nopar}{Nx}{Npx}
1358 \cs_tmp:w {gset}{Nn}{Npn}
1359 \cs_tmp:w {gset}{Nx}{Npx}
1360 \cs_tmp:w {gset_nopar}{Nn}{Npn}
1361 \cs_tmp:w {gset_nopar}{Nx}{Npx}
1362 \cs_tmp:w {gset_protected}{Nn}{Npn}
1363 \cs_tmp:w {gset_protected}{Nx}{Npx}
1364 \cs_tmp:w {gset_protected_nopar}{Nn}{Npn}
1365 \cs_tmp:w {gset_protected_nopar}{Nx}{Npx}

```

```

\cs_new:Nn
\cs_new:Nx
\cs_new_nopar:Nn
\cs_new_nopar:Nx
\cs_new_protected:Nn
\cs_new_protected:Nx
\cs_new_protected_nopar:Nn
\cs_new_protected_nopar:Nx
\cs_gnew:Nn
\cs_gnew:Nx
\cs_gnew_nopar:Nn
\cs_gnew_nopar:Nx
\cs_gnew_protected:Nn
\cs_gnew_protected:Nx
\cs_gnew_protected_nopar:Nn
\cs_gnew_protected_nopar:Nx
1366 \cs_tmp:w {new}{Nn}{Npn}
1367 \cs_tmp:w {new}{Nx}{Npx}
1368 \cs_tmp:w {new_nopar}{Nn}{Npn}
1369 \cs_tmp:w {new_nopar}{Nx}{Npx}
1370 \cs_tmp:w {new_protected}{Nn}{Npn}
1371 \cs_tmp:w {new_protected}{Nx}{Npx}
1372 \cs_tmp:w {new_protected_nopar}{Nn}{Npn}
1373 \cs_tmp:w {new_protected_nopar}{Nx}{Npx}
1374 \cs_tmp:w {gnew}{Nn}{Npn}
1375 \cs_tmp:w {gnew}{Nx}{Npx}
1376 \cs_tmp:w {gnew_nopar}{Nn}{Npn}
1377 \cs_tmp:w {gnew_nopar}{Nx}{Npx}
1378 \cs_tmp:w {gnew_protected}{Nn}{Npn}
1379 \cs_tmp:w {gnew_protected}{Nx}{Npx}
1380 \cs_tmp:w {gnew_protected_nopar}{Nn}{Npn}
1381 \cs_tmp:w {gnew_protected_nopar}{Nx}{Npx}

```

Then something similar for the c variants.

```

\cs_set_protected:Npn \cs_set:cn #1#2{
  \cs_generate_from_arg_count:cNnn {#1}\cs_set:Npn
    {\cs_get_arg_count_from_signature:c {#1}}{#2}
}

```



```

1382 \cs_set:Npn \cs_tmp:w #1#2#3{
1383   \cs_set_protected:cpx {cs_#1:#2}##1##2{
1384     \exp_not:N\cs_generate_from_arg_count:cNnn {##1}
1385     \exp_after:wN \exp_not:N \cs:w cs_#1:#3 \cs_end:
1386     {\exp_not:N\cs_get_arg_count_from_signature:c {##1}}{##2}
1387   }
1388 }

```

The 32 c variants.

```

\cs_set:cn
\cs_set:cx
\cs_set_nopar:cn
\cs_set_nopar:cx
\cs_set_protected:cn
\cs_set_protected:cx
\cs_set_protected_nopar:cn
\cs_set_protected_nopar:cx
\cs_gset:cn
\cs_gset:cx
\cs_gset_nopar:cn
\cs_gset_nopar:cx
\cs_gset_protected:cn
\cs_gset_protected:cx
\cs_gset_protected_nopar:cn
\cs_gset_protected_nopar:cx

1389 \cs_tmp:w {set}{cn}{Npn}
1390 \cs_tmp:w {set}{cx}{Npx}
1391 \cs_tmp:w {set_nopar}{cn}{Npn}
1392 \cs_tmp:w {set_nopar}{cx}{Npx}
1393 \cs_tmp:w {set_protected}{cn}{Npn}
1394 \cs_tmp:w {set_protected}{cx}{Npx}
1395 \cs_tmp:w {set_protected_nopar}{cn}{Npn}
1396 \cs_tmp:w {set_protected_nopar}{cx}{Npx}
1397 \cs_tmp:w {gset}{cn}{Npn}
1398 \cs_tmp:w {gset}{cx}{Npx}
1399 \cs_tmp:w {gset_nopar}{cn}{Npn}
1400 \cs_tmp:w {gset_nopar}{cx}{Npx}
1401 \cs_tmp:w {gset_protected}{cn}{Npn}
1402 \cs_tmp:w {gset_protected}{cx}{Npx}
1403 \cs_tmp:w {gset_protected_nopar}{cn}{Npn}
1404 \cs_tmp:w {gset_protected_nopar}{cx}{Npx}

\cs_new:cn
\cs_new:cx
\cs_new_nopar:cn
\cs_new_nopar:cx
\cs_new_protected:cn
\cs_new_protected:cx
\cs_new_protected_nopar:cn
\cs_new_protected_nopar:cx
\cs_gnew:cn
\cs_gnew:cx
\cs_gnew_nopar:cn
\cs_gnew_nopar:cx
\cs_gnew_protected:cn
\cs_gnew_protected:cx
\cs_gnew_protected_nopar:cn
\cs_gnew_protected_nopar:cx

1405 \cs_tmp:w {new}{cn}{Npn}
1406 \cs_tmp:w {new}{cx}{Npx}
1407 \cs_tmp:w {new_nopar}{cn}{Npn}
1408 \cs_tmp:w {new_nopar}{cx}{Npx}
1409 \cs_tmp:w {new_protected}{cn}{Npn}
1410 \cs_tmp:w {new_protected}{cx}{Npx}
1411 \cs_tmp:w {new_protected_nopar}{cn}{Npn}
1412 \cs_tmp:w {new_protected_nopar}{cx}{Npx}
1413 \cs_tmp:w {gnew}{cn}{Npn}
1414 \cs_tmp:w {gnew}{cx}{Npx}
1415 \cs_tmp:w {gnew_nopar}{cn}{Npn}
1416 \cs_tmp:w {gnew_nopar}{cx}{Npx}
1417 \cs_tmp:w {gnew_protected}{cn}{Npn}
1418 \cs_tmp:w {gnew_protected}{cx}{Npx}
1419 \cs_tmp:w {gnew_protected_nopar}{cn}{Npn}
1420 \cs_tmp:w {gnew_protected_nopar}{cx}{Npx}

```

Check if two control sequences are identical.

```

\cs_if_eq_p:NN
\cs_if_eq_p:cN
\cs_if_eq_p:Nc
\cs_if_eq_p:cc
\cs_if_eq:NN $\overline{TF}$ 
\cs_if_eq:cN $\overline{TF}$ 
\cs_if_eq:Nc $\overline{TF}$ 
\cs_if_eq:cc $\overline{TF}$ 

1421 \prg_set_conditional:Npnn \cs_if_eq:NN #1#2{p,TF,T,F}{

```

```

1422 \if_meaning:w #1#2
1423 \prg_return_true: \else: \prg_return_false: \fi:
1424 }
1425 \cs_new_nopar:Npn \cs_if_eq_p:cN {\exp_args:Nc \cs_if_eq_p:NN}
1426 \cs_new_nopar:Npn \cs_if_eq:cNTF {\exp_args:Nc \cs_if_eq:NNTF}
1427 \cs_new_nopar:Npn \cs_if_eq:cNT {\exp_args:Nc \cs_if_eq:NNT}
1428 \cs_new_nopar:Npn \cs_if_eq:cNF {\exp_args:Nc \cs_if_eq:NNF}
1429 \cs_new_nopar:Npn \cs_if_eq_p:Nc {\exp_args:NNc \cs_if_eq_p:NN}
1430 \cs_new_nopar:Npn \cs_if_eq:NcTF {\exp_args:NNc \cs_if_eq:NNTF}
1431 \cs_new_nopar:Npn \cs_if_eq:NcT {\exp_args:NNc \cs_if_eq:NNT}
1432 \cs_new_nopar:Npn \cs_if_eq:NcF {\exp_args:NNc \cs_if_eq:NNF}
1433 \cs_new_nopar:Npn \cs_if_eq_p:cc {\exp_args:Ncc \cs_if_eq_p:NN}
1434 \cs_new_nopar:Npn \cs_if_eq:ccTF {\exp_args:Ncc \cs_if_eq:NNTF}
1435 \cs_new_nopar:Npn \cs_if_eq:ccT {\exp_args:Ncc \cs_if_eq:NNT}
1436 \cs_new_nopar:Npn \cs_if_eq:ccF {\exp_args:Ncc \cs_if_eq:NNF}

1437 </initex | package>

1438 <*showmemory>
1439 \showMemUsage
1440 </showmemory>

```

## 96 l3expan implementation

### 96.1 Internal functions and variables

`\exp_after:wN` `\exp_after:wN <token1> <token2>`

This will expand `<token2>` once before processing `<token1>`. This is similar to `\exp_args:No` except that no braces are put around the result of expanding `<token2>`.

**TeXhackers note:** This is the primitive `\expandafter` which was renamed to fit into the naming conventions of L<sup>A</sup>T<sub>E</sub>X3.

`\l_exp_tl`

The `\exp_` module has its private variables to temporarily store results of the argument expansion. This is done to avoid interference with other functions using temporary variables.

`\exp_eval_register:N *`  
`\exp_eval_register:c *` `\exp_eval_register:N <register>`

These functions evaluates a register as part of a `V` or `v` expansion (respectively). A register might exist as one of two things: A parameter-less non-long, non-protected macro or a built-in  $\TeX$  register such as `\count`.

<code>\exp_eval_error_msg:w</code>	<code>\exp_eval_error_msg:w</code> <i>&lt;register&gt;</i>
------------------------------------	--

Used to generate an error message if a variable called as part of a `v` or `V` expansion is defined as `\scan_stop:`. This typically indicates that an incorrect cs name has been used.

<code>\n::</code>
<code>\N::</code>
<code>\c::</code>
<code>\o::</code>
<code>\f::</code>
<code>\x::</code>
<code>\v::</code>
<code>\V::</code>
<code>\:::</code>

`\cs_set_nopar:Npn \exp_args:Ncof {\::c\::o\::f\:::}`

Internal forms for the base expansion types.

## 96.2 Module code

We start by ensuring that the required packages are loaded.

```

1441 <*package>
1442 \ProvidesExplPackage
1443   {\filename}{\filedate}{\fileversion}{\filedescription}
1444 \package_check_loaded_expl:
1445 </package>
1446 <*initex | package>

```

`\exp_after:wN` These are defined in `l3basics`.

`\exp_not:N`  
`\exp_not:n`

```

1447 <*bootstrap>
1448 \cs_set_eq:NwN \exp_after:wN \tex_expandafter:D
1449 \cs_set_eq:NwN \exp_not:N \tex_noexpand:D
1450 \cs_set_eq:NwN \exp_not:n \etex_unexpanded:D
1451 </bootstrap>

```

## 96.3 General expansion

In this section a general mechanism for defining functions to handle argument handling is defined. These general expansion functions are expandable unless `x` is used. (Any version

of `x` is going to have to use one of the L<sup>A</sup>T<sub>E</sub>X3 names for `\cs_set_nopar:Npx` at some point, and so is never going to be expandable.<sup>9)</sup>

The definition of expansion functions with this technique happens in section 96.5. In section 96.4 some common cases are coded by a more direct method for efficiency, typically using calls to `\exp_after:wN`.

`\l_exp_tl` We need a scratch token list variable. We don't use `tl` methods so that `l3expan` can be loaded earlier.

```
1452 \cs_new_nopar:Npn \l_exp_tl {}
```

This code uses internal functions with names that start with `\::` to perform the expansions. All macros are `long` as this turned out to be desirable since the tokens undergoing expansion may be arbitrary user input.

An argument manipulator `\::⟨Z⟩` always has signature `#1\:::#2#3` where `#1` holds the remaining argument manipulations to be performed, `\:::` serves as an end marker for the list of manipulations, `#2` is the carried over result of the previous expansion steps and `#3` is the argument about to be processed.

`\exp_arg_next:nnn` `#1` is the result of an expansion step, `#2` is the remaining argument manipulations and `#3` is the current result of the expansion chain. This auxilliary function moves `#1` back after `#3` in the input stream and checks if any expansion is left to be done by calling `#2`. In by far the most cases we will require to add a set of braces to the result of an argument manipulation so it is more effective to do it directly here. Actually, so far only the `c` of the final argument manipulation variants does not require a set of braces.

`\exp_arg_next_nobrace:nnn`

```
1453 \cs_new:Npn\exp_arg_next:nnn#1#2#3{
1454   #2\:::{#3{#1}}
1455 }
1456 \cs_new:Npn\exp_arg_next_nobrace:nnn#1#2#3{
1457   #2\:::{#3#1}
1458 }
```

`\:::` The end marker is just another name for the identity function.

```
1459 \cs_new:Npn\:::#1{#1}
```

`\:::n` This function is used to skip an argument that doesn't need to be expanded.

```
1460 \cs_new:Npn\:::n#1\:::#2#3{
1461   #1\:::{#2{#3}}
1462 }
```

---

<sup>9</sup>However, some primitives have certain characteristics that means that their arguments undergo an `x` type expansion but the primitive is in fact still expandable. We shall make it very clear when such a function is expandable.

`\::N` This function is used to skip an argument that consists of a single token and doesn't need to be expanded.

```
1463 \cs_new:Npn\::N#1\:::#2#3{
1464   #1\:::#2#3}
1465 }
```

`\::c` This function is used to skip an argument that is turned into as control sequence without expansion.

```
1466 \cs_new:Npn\::c#1\:::#2#3{
1467   \exp_after:wN\exp_arg_next_nobrace:nnn\cs:w #3\cs_end:{#1}{#2}
1468 }
```

`\::o` This function is used to expand an argument once.

```
1469 \cs_new:Npn\::o#1\:::#2#3{
1470   \exp_after:wN\exp_arg_next:nnn\exp_after:wN{#3}{#1}{#2}
1471 }
```

`\::f` This function is used to expand a token list until the first unexpandable token is found.  
`\exp_stop_f:` The underlying `\tex_romannumeral:D -'0` expands everything in its way to find something terminating the number and thereby expands the function in front of it. This scanning procedure is terminated once the expansion hits something non-expandable or a space. We introduce `\exp_stop_f:` to mark such an end of expansion marker; in case the scanner hits a number, this number also terminates the scanning and is left untouched. In the example shown earlier the scanning was stopped once  $\TeX$  had fully expanded `\cs_set_eq:Nc \aaa {b \l_tmpa_tl b}` into `\cs_set_eq:NwN \aaa = \blurb` which then turned out to contain the non-expandable token `\cs_set_eq:NwN`. Since the expansion of `\tex_romannumeral:D -'0` is  $\langle null \rangle$ , we wind up with a fully expanded list, only  $\TeX$  has not tried to execute any of the non-expandable tokens. This is what differentiates this function from the `x` argument type.

```
1472 \cs_new:Npn\::f#1\:::#2#3{
1473   \exp_after:wN\exp_arg_next:nnn
1474   \exp_after:wN{\tex_romannumeral:D -'0 #3}
1475   {#1}{#2}
1476 }
1477 \cs_new_nopar:Npn \exp_stop_f: {~}
```

`\::x` This function is used to expand an argument fully. We could use the new expandable primitive `\expanded` here, but we don't want to create incompatibilities between engines.

```
1478 %%\cs_new_eq:NN \exp_arg:x \expanded % Move eventually.
1479 %%\cs_if_free:NTF\exp_arg:x{
1480   \cs_new:Npn \::x #1 \:::#2#3 {
1481     \cs_set_nopar:Npx \l_exp_tl {#{#3}}
1482     \exp_after:wN \exp_arg_next:nnn \l_exp_tl {#1}{#2}
```

```

1483   }
1484   %%}
1485   %%{
1486   %% \cs_new:Npn \::x#1\:::#2#3{
1487   %% \exp_after:wN\exp_arg_next:nnn
1488   %% \exp_after:wN{\exp_arg:x{#3}}{#1}{#2}
1489   %% }
1490   %%}

```

`\::v` These functions return the value of a register, i.e., one of `tl`, `num`, `int`, `skip`, `dim` and `muskip`. The `V` version expects a single token whereas `v` like `c` creates a csname from its argument given in braces and then evaluates it as if it was a `V`. The sequence `\tex_romannumeral:D -'0` sets off an `f` type expansion. The argument is returned in braces.

```

1491 \cs_new:Npn \::V#1\:::#2#3{
1492   \exp_after:wN\exp_arg_next:nnn
1493   \exp_after:wN{
1494     \tex_romannumeral:D -'0
1495     \exp_eval_register:N #3
1496   }
1497   {#1}{#2}
1498 }
1499 \cs_new:Npn \::v#1\:::#2#3{
1500   \exp_after:wN\exp_arg_next:nnn
1501   \exp_after:wN{
1502     \tex_romannumeral:D -'0
1503     \exp_eval_register:c {#3}
1504   }
1505   {#1}{#2}
1506 }

```

`\exp_eval_register:N` This function evaluates a register. Now a register might exist as one of two things: A parameter-less macro or a built-in T<sub>E</sub>X register such as `\count`. For the T<sub>E</sub>X registers `\exp_eval_register:c` we have to utilize a `\tex_the:D` whereas for the macros we merely have to expand them once. The trick is to find out when to use `\tex_the:D` and when not to. What we do here is try to find out whether the token will expand to something else when hit with `\exp_after:wN`. The technique is to compare the meaning of the register in question when it has been prefixed with `\exp_not:N` and the register itself. If it is a macro, the prefixed `\exp_not:N` will temporarily turn it into the primitive `\tex_relax:D`.

```

1507 \cs_set_nopar:Npn \exp_eval_register:N #1{
1508   \exp_after:wN \if_meaning:w \exp_not:N #1#1

```

If the token was not a macro it may be a malformed variable from a `c` expansion in which case it is equal to the primitive `\tex_relax:D`. In that case we throw an error. We could let T<sub>E</sub>X do it for us but that would result in the rather obscure

! You can't use '`\relax`' after `\the`.

which while quite true doesn't give many hints as to what actually went wrong. We provide something more sensible.

```

1509     \if_meaning:w \tex_relax:D #1
1510         \exp_eval_error_msg:w
1511     \fi:

```

The next bit requires some explanation. The function must be initiated by the sequence `\tex_romannumeral:D -'0` and we want to terminate this expansion chain by inserting an `\exp_stop_f:` token. However, we have to expand the register `#1` before we do that. If it is a T<sub>E</sub>X register, we need to execute the sequence `\exp_after:wN\exp_stop_f:\tex_the:D #1` and if it is a macro we need to execute `\exp_after:wN\exp_stop_f: #1`. We therefore issue the longer of the two sequences and if the register is a macro, we remove the `\tex_the:D`.

```

1512     \else:
1513         \exp_after:wN \use_i_ii:nnn
1514     \fi:
1515     \exp_after:wN \exp_stop_f: \tex_the:D #1
1516 }
1517 \cs_set_nopar:Npn \exp_eval_register:c #1{
1518     \exp_after:wN\exp_eval_register:N\cs:w #1\cs_end:
1519 }

```

Clean up nicely, then call the undefined control sequence. The result is an error message looking like this:

```

! Undefined control sequence.
\exp_eval_error_msg:w ...erroneous variable used!

```

```

1.55 \tl_set:Nv \l_tmpa_tl {undefined_tl}

```

```

1520 \group_begin:%
1521 \tex_catcode:D'\!=11\tex_relax:D%
1522 \tex_catcode:D'\ =11\tex_relax:D%
1523 \cs_gset:Npn\exp_eval_error_msg:w#1\tex_the:D#2{%
1524     \fi:\fi:\erroneous variable used!}%
1525 \group_end:%

```

## 96.4 Hand-tuned definitions

One of the most important features of these functions is that they are fully expandable and therefore allow to prefix them with `\pref_global:D` for example. This together with the fact that the ‘general’ concept above is slower means that we should convert whenever possible and perhaps remove all remaining occurrences by hand-encoding in the end.

```

\exp_args:No
\exp_args:NNo
\exp_args:NNNo
1526 \cs_new:Npn \exp_args:No #1#2{\exp_after:wN#1\exp_after:wN{#2}}
1527 \cs_new:Npn \exp_args:NNo #1#2#3{\exp_after:wN#1\exp_after:wN#2
1528   \exp_after:wN{#3}}
1529 \cs_new:Npn \exp_args:NNNo #1#2#3#4{\exp_after:wN#1\exp_after:wN#2
1530   \exp_after:wN#3\exp_after:wN{#4}}

```

Here are the functions that turn their argument into csnames but are expandable.

```

\exp_args:Nc
\exp_args:cc
\exp_args:NNc
\exp_args:Ncc
\exp_args:Nccc
1531 \cs_set:Npn \exp_args:Nc #1#2{\exp_after:wN#1\cs:w#2\cs_end:}
1532 \cs_new:Npn \exp_args:cc #1#2{\cs:w #1\exp_after:wN\cs_end:\cs:w #2\cs_end:}
1533 \cs_new:Npn \exp_args:NNc #1#2#3{\exp_after:wN#1\exp_after:wN#2
1534   \cs:w#3\cs_end:}
1535 \cs_new:Npn \exp_args:Ncc #1#2#3{\exp_after:wN#1
1536   \cs:w#2\exp_after:wN\cs_end:\cs:w#3\cs_end:}
1537 \cs_new:Npn \exp_args:Nccc #1#2#3#4{\exp_after:wN#1
1538   \cs:w#2\exp_after:wN\cs_end:\cs:w#3\exp_after:wN
1539   \cs_end:\cs:w #4\cs_end:}

```

If we force that the third argument always has braces, we could implement this function with less tokens and only two arguments.

```

1540 \cs_new:Npn \exp_args:Nco #1#2#3{\exp_after:wN#1\cs:w#2\exp_after:wN
1541   \cs_end:\exp_after:wN{#3}}

```

## 96.5 Definitions with the ‘general’ technique

```

\exp_args:Nf
\exp_args:Nv
\exp_args:Nv
\exp_args:Nx
1542 \cs_set_nopar:Npn \exp_args:Nf {\:f\:::}
1543 \cs_set_nopar:Npn \exp_args:Nv {\:v\:::}
1544 \cs_set_nopar:Npn \exp_args:Nv {\:V\:::}
1545 \cs_set_nopar:Npn \exp_args:Nx {\:x\:::}

```

Here are the actual function definitions, using the helper functions above.

```

\exp_args:NNV
\exp_args:NNv
1546 \cs_set_nopar:Npn \exp_args:NNf {\:N\::f\:::}
1547 \cs_set_nopar:Npn \exp_args:NNv {\:N\::v\:::}
1548 \cs_set_nopar:Npn \exp_args:NNV {\:N\::V\:::}
1549 \cs_set_nopar:Npn \exp_args:NNx {\:N\::x\:::}
1550
1551 \cs_set_nopar:Npn \exp_args:Ncx {\:c\::x\:::}
1552 \cs_set_nopar:Npn \exp_args:Nfo {\:f\::o\:::}
1553 \cs_set_nopar:Npn \exp_args:Nff {\:f\::f\:::}
1554 \cs_set_nopar:Npn \exp_args:Ncf {\:c\::f\:::}
1555 \cs_set_nopar:Npn \exp_args:Nnf {\:n\::f\:::}
1556 \cs_set_nopar:Npn \exp_args:Nno {\:n\::o\:::}
\exp_args:NnV
\exp_args:Nnx
\exp_args:Noo
\exp_args:Noc
\exp_args:Nox
\exp_args:Nxo
\exp_args:Nxx

```



```

1557 \cs_set_nopar:Npn \exp_args:NnV {\:n\:V\:::}
1558 \cs_set_nopar:Npn \exp_args:Nnx {\:n\:x\:::}
1559
1560 \cs_set_nopar:Npn \exp_args:Noc {\:o\:c\:::}
1561 \cs_set_nopar:Npn \exp_args:Noo {\:o\:o\:::}
1562 \cs_set_nopar:Npn \exp_args:Nox {\:o\:x\:::}
1563
1564 \cs_set_nopar:Npn \exp_args:NVV {\:V\:V\:::}
1565
1566 \cs_set_nopar:Npn \exp_args:Nxo {\:x\:o\:::}
1567 \cs_set_nopar:Npn \exp_args:Nxx {\:x\:x\:::}

\exp_args:Ncco
\exp_args:Nccx
\exp_args:Ncnx
1568 \cs_set_nopar:Npn \exp_args:NNNV {\:N\:N\:V\:::}
1569
1570 \cs_set_nopar:Npn \exp_args:NNno {\:N\:n\:o\:::}
1571 \cs_set_nopar:Npn \exp_args:NNnx {\:N\:n\:x\:::}
1572 \cs_set_nopar:Npn \exp_args:NNoo {\:N\:o\:o\:::}
1573 \cs_set_nopar:Npn \exp_args:NNox {\:N\:o\:x\:::}
1574
1575 \cs_set_nopar:Npn \exp_args:Nnnc {\:n\:n\:c\:::}
1576 \cs_set_nopar:Npn \exp_args:Nnno {\:n\:n\:o\:::}
1577 \cs_set_nopar:Npn \exp_args:Nnnx {\:n\:n\:x\:::}
1578 \cs_set_nopar:Npn \exp_args:Nnox {\:n\:o\:x\:::}
1579
1580 \cs_set_nopar:Npn \exp_args:NcNc {\:c\:N\:c\:::}
1581 \cs_set_nopar:Npn \exp_args:NcNo {\:c\:N\:o\:::}
1582 \cs_set_nopar:Npn \exp_args:Ncco {\:c\:c\:o\:::}
1583 \cs_set_nopar:Npn \exp_args:Ncco {\:c\:c\:o\:::}
1584 \cs_set_nopar:Npn \exp_args:Nccx {\:c\:c\:x\:::}
1585 \cs_set_nopar:Npn \exp_args:Ncnx {\:c\:n\:x\:::}
1586
1587 \cs_set_nopar:Npn \exp_args:Noox {\:o\:o\:x\:::}
1588 \cs_set_nopar:Npn \exp_args:Nooo {\:o\:o\:o\:::}

```

## 96.6 Preventing expansion

```

\exp_not:o
\exp_not:d
\exp_not:f
\exp_not:v
\exp_not:V
1589 \cs_new:Npn\exp_not:o#1{\exp_not:n\exp_after:wN{#1}}
1590 \cs_new:Npn\exp_not:d#1{
1591   \exp_not:n\exp_after:wN\exp_after:wN\exp_after:wN{#1}
1592 }
1593 \cs_new:Npn\exp_not:f#1{
1594   \exp_not:n\exp_after:wN{\tex_romannumeral:D -‘0 #1}
1595 }
1596 \cs_new:Npn\exp_not:v#1{
1597   \exp_not:n\exp_after:wN{\tex_romannumeral:D -‘0 \exp_eval_register:c {#1}}

```

```

1598 }
1599 \cs_new:Npn\exp_not:V#1{
1600   \exp_not:n\exp_after:wN{\tex_romannumeral:D -'0 \exp_eval_register:N #1}
1601 }

```

`\exp_not:c` A helper function.

```

1602 \cs_new:Npn\exp_not:c#1{\exp_after:wN\exp_not:N\cs:w#1\cs_end:}

```

## 96.7 Defining function variants

```

\cs_generate_variant:Nn #1 : Base form of a function; e.g., \tl_set:Nn
\cs_generate_variant_aux:nnNn #2 : One or more variant argument specifiers; e.g., {Nx,c,cx}
\cs_generate_variant_aux:nnw
\cs_generate_variant_aux:N

```

Split up the original base function to grab its name and signature consisting of  $k$  letters. Then we wish to iterate through the list of variant argument specifiers, and for each one construct a new function name using the original base name, the variant signature consisting of  $l$  letters and the last  $k - l$  letters of the base signature. For example, for a base function `\tl_set:Nn` which needs a `c` variant form, we want the new signature to be `cn`.

```

1603 \cs_new:Npn \cs_generate_variant:Nn #1 {
1604   \chk_if_exist_cs:N #1
1605   \cs_split_function:NN #1 \cs_generate_variant_aux:nnNn
1606 }

```

We discard the boolean and then set off a loop through the desired variant forms.

```

1607 \cs_set:Npn \cs_generate_variant_aux:nnNn #1#2#3#4{
1608   \cs_generate_variant_aux:nnw {#1}{#2} #4,?,\q_recursion_stop
1609 }

```

Next is the real work to be done. We now have 1: base name, 2: base signature, 3: beginning of variant signature. To construct the new csname and the `\exp_args:Ncc` form, we need the variant signature. In our example, we wanted to discard the first two letters of the base signature because the variant form started with `cc`. This is the same as putting first `cc` in the signature and then `\use_none:nn` followed by the base signature `NNn`. We therefore call a small loop that outputs an `n` for each letter in the variant signature and use this to call the correct `\use_none:` variant. Firstly though, we check whether to terminate the loop.

```

1610 \cs_set:Npn \cs_generate_variant_aux:nnw #1 #2 #3, {
1611   \if:w ? #3
1612     \exp_after:wN \use_none_delimit_by_q_recursion_stop:w
1613   \fi:

```

Then check if the variant form has already been defined.

```

1614   \cs_if_free:cTF {

```

```

1615     #1:#3\use:c {use_none:\cs_generate_variant_aux:N #3 ?}#2
1616   }
1617   {

```

If not, then define it and then additionally check if the `\exp_args:N` form needed is defined.

```

1618   \cs_new_nopar:cpx {
1619     #1:#3 \use:c{use_none:\cs_generate_variant_aux:N #3 ?}#2
1620   }
1621   {
1622     \exp_not:c { exp_args:N #3} \exp_not:c {#1:#2}
1623   }
1624   \cs_generate_internal_variant:n {#3}
1625 }

```

Otherwise tell that it was already defined.

```

1626   {
1627     \iow_log:x{
1628       Variant~\token_to_str:c {
1629         #1:#3\use:c {use_none:\cs_generate_variant_aux:N #3 ?}#2
1630       }~already~defined;~ not~ changing~ it~on~line~
1631       \tex_the:D \tex_inputlineno:D
1632     }
1633   }

```

Recurse.

```

1634   \cs_generate_variant_aux:nnw{#1}{#2}
1635 }

```

The small loop for defining the required number of ns. Break when seeing a ?.

```

1636 \cs_set:Npn \cs_generate_variant_aux:N #1{
1637   \if:w ?#1 \exp_after:wN\use_none:nn \fi: n \cs_generate_variant_aux:N
1638 }

```

`\cs_generate_internal_variant:n` Test if `\exp_args:N #1` is already defined and if not define it via the `\::` commands using the chars in `#1`

```

1639 \cs_new:Npn \cs_generate_internal_variant:n #1 {
1640   \cs_if_free:cT { exp_args:N #1 }{

```

We use `new` to log the definition if we have to make one.

```

1641     \cs_new:cpx { exp_args:N #1 }
1642         { \cs_generate_internal_variant_aux:n #1 : }
1643   }
1644 }

```

`\generate_internal_variant_aux:n` This command grabs char by char outputting `\::#1` (not expanded further) until we see a `::`. That colon is in fact also turned into `\:::` so that the required structure for `\exp_args...` commands is correctly terminated.

```

1645 \cs_new:Npn \cs_generate_internal_variant_aux:n #1 {
1646   \exp_not:c{::#1}
1647   \if_meaning:w #1 :
1648     \exp_after:wN \use_none:n
1649   \fi:
1650   \cs_generate_internal_variant_aux:n
1651 }

```

## 96.8 Last-unbraced versions

`\exp_arg_last_unbraced:nn` There are a few places where the last argument needs to be available unbraced. First some helper macros.

```

\::f_unbraced
\::o_unbraced
\::V_unbraced
\::v_unbraced
1652 \cs_new:Npn \exp_arg_last_unbraced:nn #1#2 { #2#1 }
1653 \cs_new:Npn \::f_unbraced \:::#1#2 {
1654   \exp_after:wN \exp_arg_last_unbraced:nn
1655   \exp_after:wN { \tex_romannumeral:D -'0 #2 } {#1}
1656 }
1657 \cs_new:Npn \::o_unbraced \:::#1#2 {
1658   \exp_after:wN \exp_arg_last_unbraced:nn \exp_after:wN {#2 }{#1}
1659 }
1660 \cs_new:Npn \::V_unbraced \:::#1#2 {
1661   \exp_after:wN \exp_arg_last_unbraced:nn
1662   \exp_after:wN { \tex_romannumeral:D -'0 \exp_eval_register:N #2 } {#1}
1663 }
1664 \cs_new:Npn \::v_unbraced \:::#1#2 {
1665   \exp_after:wN \exp_arg_last_unbraced:nn
1666   \exp_after:wN {
1667     \tex_romannumeral:D -'0 \exp_eval_register:c {#2}
1668   } {#1}
1669 }

```

`\exp_last_unbraced:NV` Now the business end.

```

\exp_last_unbraced:Nv
\exp_last_unbraced:Nf
\exp_last_unbraced:NcV
\exp_last_unbraced:NNo
\exp_last_unbraced:NNV
\exp_last_unbraced:NNNo
1670 \cs_new_nopar:Npn \exp_last_unbraced:Nf { \::f_unbraced \::: }
1671 \cs_new_nopar:Npn \exp_last_unbraced:Nv { \::V_unbraced \::: }
1672 \cs_new_nopar:Npn \exp_last_unbraced:Nv { \::v_unbraced \::: }
1673 \cs_new_nopar:Npn \exp_last_unbraced:NcV {
1674   \::c \::V_unbraced \:::
1675 }
1676 \cs_new:Npn \exp_last_unbraced:NNo #1#2#3 {
1677   \exp_after:wN #1 \exp_after:wN #2 #3
1678 }
1679 \cs_new_nopar:Npn \exp_last_unbraced:NNV {
1680   \::N \::V_unbraced \:::

```

```

1681 }
1682 \cs_new:Npn \exp_last_unbraced:NNNo #1#2#3#4 {
1683   \exp_after:wN #1 \exp_after:wN #2 \exp_after:wN #3 #4
1684 }

1685 </initex | package>

```

Show token usage:

```

1686 <*showmemory>
1687 \showMemUsage
1688 </showmemory>

```

## 97 l3prg implementation

### 97.1 Variables

<pre> \l_tmpa_bool \g_tmpa_bool </pre>	Reserved booleans.
--	--------------------

<pre> \g_prg_inline_level_int </pre>	Global variable to track the nesting of the stepwise inline loop.
--------------------------------------	---

### 97.2 Module code

We start by ensuring that the required packages are loaded.

```

1689 <*package>
1690 \ProvidesExplPackage
1691   {\filename}{\filedate}{\fileversion}{\filedescription}
1692 \package_check_loaded_expl:
1693 </package>
1694 <*initex | package>

```

<pre> \prg_return_true: \prg_return_false: \prg_set_conditional:Npnn \prg_new_conditional:Npnn \prg_set_protected_conditional:Npnn \prg_new_protected_conditional:Npnn \prg_set_eq_conditional:Nnn \prg_new_eq_conditional:Nnn </pre>	These are all defined in l3basics, as they are needed “early”. This is just a reminder that that is the case!
---	---

### 97.3 Choosing modes

<pre> \prg_set_conditional:Npnn \prg_new_conditional:Npnn \prg_set_protected_conditional:Npnn \prg_new_protected_conditional:Npnn \prg_set_eq_conditional:Nnn \prg_new_eq_conditional:Nnn </pre>	For testing vertical mode. Strikes me here on the bus with David, that as long as we are just talking about returning true and false states, we can just use the primitive conditionals for this and gobbling the <code>\c_zero</code> in the input stream. However this requires
--	---

knowledge of the implementation so we keep things nice and clean and use the return statements.

```
1695 \prg_set_conditional:Npnn \mode_if_vertical: {p,TF,T,F}{
1696   \if_mode_vertical:
1697   \prg_return_true: \else: \prg_return_false: \fi:
1698 }
```

`\mode_if_horizontal_p:` For testing horizontal mode.

```
\mode_if_horizontal:TF
1699 \prg_set_conditional:Npnn \mode_if_horizontal: {p,TF,T,F}{
1700   \if_mode_horizontal:
1701   \prg_return_true: \else: \prg_return_false: \fi:
1702 }
```

`\mode_if_inner_p:` For testing inner mode.

```
\mode_if_inner:TF
1703 \prg_set_conditional:Npnn \mode_if_inner: {p,TF,T,F}{
1704   \if_mode_inner:
1705   \prg_return_true: \else: \prg_return_false: \fi:
1706 }
```

`\mode_if_math_p:` For testing math mode. Uses the kern-save `\scan_align_safe_stop:`.

```
\mode_if_math:TF
1707 \prg_set_conditional:Npnn \mode_if_math: {p,TF,T,F}{
1708   \scan_align_safe_stop: \if_mode_math:
1709   \prg_return_true: \else: \prg_return_false: \fi:
1710 }
```

## Alignment safe grouping and scanning

`\group_align_safe_begin:` `\group_align_safe_end:` T<sub>E</sub>X’s alignment structures present many problems. As Knuth says himself in *T<sub>E</sub>X: The Program*: “It’s sort of a miracle whenever `\halign` or `\valign` work, [...]” One problem relates to commands that internally issues a `\cr` but also peek ahead for the next character for use in, say, an optional argument. If the next token happens to be a `&` with category code 4 we will get some sort of weird error message because the underlying `\tex_futurelet:D` will store the token at the end of the alignment template. This could be a `&_4` giving a message like `! Misplaced \cr.` or even worse: it could be the `\endtemplate` token causing even more trouble! To solve this we have to open a special group so that T<sub>E</sub>X still thinks it’s on safe ground but at the same time we don’t want to introduce any brace group that may find its way to the output. The following functions help with this by using code documented only in Appendix D of *The T<sub>E</sub>Xbook*...

```
1711 \cs_new_nopar:Npn \group_align_safe_begin: {
1712   \if_false:{\fi:\if_num:w'=\c_zero\fi:}
1713 \cs_new_nopar:Npn \group_align_safe_end:   {\if_num:w'=\c_zero\fi:}
```

`\scan_align_safe_stop:` When TeX is in the beginning of an align cell (right after the `\cr`) it is in a somewhat strange mode as it is looking ahead to find an `\tex_omit:D` or `\tex_noalign:D` and hasn't looked at the preamble yet. Thus an `\tex_ifmmode:D` test will always fail unless we insert `\scan_stop:` to stop TeX's scanning ahead. On the other hand we don't want to insert a `\scan_stop:` every time as that will destroy kerning between letters<sup>10</sup> Unfortunately there is no way to detect if we're in the beginning of an alignment cell as they have different characteristics depending on column number etc. However we *can* detect if we're in an alignment cell by checking the current group type and we can also check if the previous node was a character or ligature. What is done here is that `\scan_stop:` is only inserted iff a) we're in the outer part of an alignment cell and b) the last node *wasn't* a char node or a ligature node.

```

1714 \cs_new_nopar:Npn \scan_align_safe_stop: {
1715   \intexpr_compare:nNnT \etex_currentgrouptype:D = \c_six
1716   {
1717     \intexpr_compare:nNnF \etex_lastnodetype:D = \c_zero
1718     {
1719       \intexpr_compare:nNnF \etex_lastnodetype:D = \c_seven
1720       \scan_stop:
1721     }
1722   }
1723 }
```

## 97.4 Producing $n$ copies

```

\prg_replicate:nn
\prg_replicate_aux:N
\prg_replicate_first_aux:N
```

This function uses a cascading csname technique by David Kastrup (who else :-)

The idea is to make the input 25 result in first adding five, and then 20 copies of the code to be replicated. The technique uses cascading csnames which means that we start building several csnames so we end up with a list of functions to be called in reverse order. This is important here (and other places) because it means that we can for instance make the function that inserts five copies of something to also hand down ten to the next function in line. This is exactly what happens here: in the example with 25 then the next function is the one that inserts two copies but it sees the ten copies handed down by the previous function. In order to avoid the last function to insert say, 100 copies of the original argument just to gobble them again we define separate functions to be inserted first. Finally we must ensure that the cascade comes to a peaceful end so we make it so that the original csname TeX is creating is simply `\prg_do_nothing:` expanding to nothing.

This function has one flaw though: Since it constantly passes down ten copies of its previous argument it will severely affect the main memory once you start demanding hundreds of thousands of copies. Now I don't think this is a real limitation for any ordinary use. An alternative approach is to create a string of m's with `\int_to_roman:w` which can be done with just four macros but that method has its own problems since it

<sup>10</sup>Unless we enforce an extra pass with an appropriate value of `\pretolerance`.

can exhaust the string pool. Also, it is considerably slower than what we use here so the few extra csnames are well spent I would say.

```

1724 \cs_new_nopar:Npn \prg_replicate:nn #1{
1725   \cs:w prg_do_nothing:
1726   \exp_after:wN\prg_replicate_first_aux:N
1727   \tex_romannumeral:D -'\q \intexpr_eval:n{#1} \cs_end:
1728   \cs_end:
1729 }
1730 \cs_new_nopar:Npn \prg_replicate_aux:N#1{
1731   \cs:w prg_replicate_#1:n\prg_replicate_aux:N
1732 }
1733 \cs_new_nopar:Npn \prg_replicate_first_aux:N#1{
1734   \cs:w prg_replicate_first_#1:n\prg_replicate_aux:N
1735 }

```

Then comes all the functions that do the hard work of inserting all the copies.

```

1736 \cs_new_nopar:Npn \prg_replicate_ :n #1{}% no, this is not a typo!
1737 \cs_new:cpn {prg_replicate_0:n}#1{\cs_end:{#1#1#1#1#1#1#1#1#1}}
1738 \cs_new:cpn {prg_replicate_1:n}#1{\cs_end:{#1#1#1#1#1#1#1#1#1}#1}
1739 \cs_new:cpn {prg_replicate_2:n}#1{\cs_end:{#1#1#1#1#1#1#1#1#1}#1#1}
1740 \cs_new:cpn {prg_replicate_3:n}#1{
1741   \cs_end:{#1#1#1#1#1#1#1#1#1}#1#1#1}
1742 \cs_new:cpn {prg_replicate_4:n}#1{
1743   \cs_end:{#1#1#1#1#1#1#1#1#1}#1#1#1#1}
1744 \cs_new:cpn {prg_replicate_5:n}#1{
1745   \cs_end:{#1#1#1#1#1#1#1#1#1}#1#1#1#1#1}
1746 \cs_new:cpn {prg_replicate_6:n}#1{
1747   \cs_end:{#1#1#1#1#1#1#1#1#1}#1#1#1#1#1#1}
1748 \cs_new:cpn {prg_replicate_7:n}#1{
1749   \cs_end:{#1#1#1#1#1#1#1#1#1}#1#1#1#1#1#1#1}
1750 \cs_new:cpn {prg_replicate_8:n}#1{
1751   \cs_end:{#1#1#1#1#1#1#1#1#1}#1#1#1#1#1#1#1#1}
1752 \cs_new:cpn {prg_replicate_9:n}#1{
1753   \cs_end:{#1#1#1#1#1#1#1#1#1}#1#1#1#1#1#1#1#1#1}

```

Users shouldn't ask for something to be replicated once or even not at all but...

```

1754 \cs_new:cpn {prg_replicate_first_0:n}#1{\cs_end: }
1755 \cs_new:cpn {prg_replicate_first_1:n}#1{\cs_end: #1}
1756 \cs_new:cpn {prg_replicate_first_2:n}#1{\cs_end: #1#1}
1757 \cs_new:cpn {prg_replicate_first_3:n}#1{\cs_end: #1#1#1}
1758 \cs_new:cpn {prg_replicate_first_4:n}#1{\cs_end: #1#1#1#1}
1759 \cs_new:cpn {prg_replicate_first_5:n}#1{\cs_end: #1#1#1#1#1}
1760 \cs_new:cpn {prg_replicate_first_6:n}#1{\cs_end: #1#1#1#1#1#1}
1761 \cs_new:cpn {prg_replicate_first_7:n}#1{\cs_end: #1#1#1#1#1#1#1}
1762 \cs_new:cpn {prg_replicate_first_8:n}#1{\cs_end: #1#1#1#1#1#1#1#1}
1763 \cs_new:cpn {prg_replicate_first_9:n}#1{\cs_end: #1#1#1#1#1#1#1#1#1}

```



`\prg_stepwise_function:nnnN` A stepwise function. Firstly we check the direction of the steps #2 since that will depend on which test we should use. If the step is positive we use a greater than test, otherwise  
`\prg_stepwise_function_incr:nnnN` a less than test. If the test comes out true exit, otherwise perform #4, add the step to  
`\prg_stepwise_function_decr:nnnN` #1 and try again with this new value of #1.

```

1764 \cs_new:Npn \prg_stepwise_function:nnnN #1#2{
1765   \intexpr_compare:nNnTF{#2}<\c_zero
1766     {\exp_args:Nf\prg_stepwise_function_decr:nnnN }
1767     {\exp_args:Nf\prg_stepwise_function_incr:nnnN }
1768     {\intexpr_eval:n{#1}}{#2}
1769 }
1770 \cs_new:Npn \prg_stepwise_function_incr:nnnN #1#2#3#4{
1771   \intexpr_compare:nNnF {#1}>{#3}
1772   {
1773     #4{#1}
1774     \exp_args:Nf \prg_stepwise_function_incr:nnnN
1775     {\intexpr_eval:n{#1 + #2}}
1776     {#2}{#3}{#4}
1777   }
1778 }
1779 \cs_new:Npn \prg_stepwise_function_decr:nnnN #1#2#3#4{
1780   \intexpr_compare:nNnF {#1}<{#3}
1781   {
1782     #4{#1}
1783     \exp_args:Nf \prg_stepwise_function_decr:nnnN
1784     {\intexpr_eval:n{#1 + #2}}
1785     {#2}{#3}{#4}
1786   }
1787 }

```

`\g_prg_inline_level_int` This function uses the same approach as for instance `\clist_map_inline:Nn` to allow  
`\prg_stepwise_inline:nnnn` arbitrary nesting. First construct the special function and then call an auxiliary one  
`\prg_stepwise_inline_decr:nnnn` which just carries the newly constructed csname. Must make assignments global when  
`\prg_stepwise_inline_incr:nnnn` we maintain our own stack.

```

1788 \int_new:N\g_prg_inline_level_int
1789 \cs_new:Npn\prg_stepwise_inline:nnnn #1#2#3#4{
1790   \int_gincr:N \g_prg_inline_level_int
1791   \cs_gset_nopar:cpn{prg_stepwise_inline\_int_use:N\g_prg_inline_level_int :n}##1{#4}
1792   \intexpr_compare:nNnTF {#2}<\c_zero
1793     {\exp_args:Ncf \prg_stepwise_inline_decr:Nnnn }
1794     {\exp_args:Ncf \prg_stepwise_inline_incr:Nnnn }
1795     {prg_stepwise_inline\_int_use:N\g_prg_inline_level_int :n}
1796     {\intexpr_eval:n{#1}} {#2} {#3}
1797   \int_gdecr:N \g_prg_inline_level_int
1798 }
1799 \cs_new:Npn \prg_stepwise_inline_incr:Nnnn #1#2#3#4{
1800   \intexpr_compare:nNnF {#2}>{#4}
1801   {

```

```

1802     #1{#2}
1803     \exp_args:Nnf \prg_stepwise_inline_incr:Nnnn #1
1804     {\intexpr_eval:n{#2 + #3}} {#3}{#4}
1805   }
1806 }
1807 \cs_new:Npn \prg_stepwise_inline_decr:Nnnn #1#2#3#4{
1808   \intexpr_compare:nNnF {#2}<{#4}
1809   {
1810     #1{#2}
1811     \exp_args:Nnf \prg_stepwise_inline_decr:Nnnn #1
1812     {\intexpr_eval:n{#2 + #3}} {#3}{#4}
1813   }
1814 }

```

```

\prg_stepwise_variable:nnnNn
\prg_stepwise_variable_decr:nnnNn
\prg_stepwise_variable_incr:nnnNn

```

Almost the same as above. Just store the value in #4 and execute #5.

```

1815 \cs_new:Npn \prg_stepwise_variable:nnnNn #1#2 {
1816   \intexpr_compare:nNnTF {#2}<\c_zero
1817   {\exp_args:Nf\prg_stepwise_variable_decr:nnnNn}
1818   {\exp_args:Nf\prg_stepwise_variable_incr:nnnNn}
1819   {\intexpr_eval:n{#1}}{#2}
1820 }
1821 \cs_new:Npn \prg_stepwise_variable_incr:nnnNn #1#2#3#4#5 {
1822   \intexpr_compare:nNnF {#1}>{#3}
1823   {
1824     \cs_set_nopar:Npn #4{#1} #5
1825     \exp_args:Nf \prg_stepwise_variable_incr:nnnNn
1826     {\intexpr_eval:n{#1 + #2}}{#2}{#3}#4{#5}
1827   }
1828 }
1829 \cs_new:Npn \prg_stepwise_variable_decr:nnnNn #1#2#3#4#5 {
1830   \intexpr_compare:nNnF {#1}<{#3}
1831   {
1832     \cs_set_nopar:Npn #4{#1} #5
1833     \exp_args:Nf \prg_stepwise_variable_decr:nnnNn
1834     {\intexpr_eval:n{#1 + #2}}{#2}{#3}#4{#5}
1835   }
1836 }

```

## 97.5 Booleans

For normal booleans we set them to either `\c_true_bool` or `\c_false_bool` and then use `\if_bool:N` to choose the right branch. The functions return either the TF, T, or F case *after* ending the `\if_bool:N`. We only define the N versions here as the c versions can easily be constructed with the expansion module.

```

\bool_new:N      Defining and setting a boolean is easy.
\bool_new:c
\bool_set_true:N
\bool_set_true:c
\bool_set_false:N
\bool_set_false:c
\bool_gset_true:N
\bool_gset_true:c
\bool_gset_false:N
\bool_gset_false:c

```

```

1837 \cs_new_nopar:Npn \bool_new:N #1 { \cs_new_eq:NN #1 \c_false_bool }
1838 \cs_new_nopar:Npn \bool_new:c #1 { \cs_new_eq:cN {#1} \c_false_bool }
1839 \cs_new_nopar:Npn \bool_set_true:N #1 { \cs_set_eq:NN #1 \c_true_bool }
1840 \cs_new_nopar:Npn \bool_set_true:c #1 { \cs_set_eq:cN {#1} \c_true_bool }
1841 \cs_new_nopar:Npn \bool_set_false:N #1 { \cs_set_eq:NN #1 \c_false_bool }
1842 \cs_new_nopar:Npn \bool_set_false:c #1 { \cs_set_eq:cN {#1} \c_false_bool }
1843 \cs_new_nopar:Npn \bool_gset_true:N #1 { \cs_gset_eq:NN #1 \c_true_bool }
1844 \cs_new_nopar:Npn \bool_gset_true:c #1 { \cs_gset_eq:cN {#1} \c_true_bool }
1845 \cs_new_nopar:Npn \bool_gset_false:N #1 { \cs_gset_eq:NN #1 \c_false_bool }
1846 \cs_new_nopar:Npn \bool_gset_false:c #1 { \cs_gset_eq:cN {#1} \c_false_bool }

```

\bool\_set\_eq:NN Setting a boolean to another is also pretty easy.

```

\bool_set_eq:Nc
\bool_set_eq:cN
\bool_set_eq:cc
\bool_gset_eq:NN
\bool_gset_eq:Nc
\bool_gset_eq:cN
\bool_gset_eq:cc
1847 \cs_new_eq:NN \bool_set_eq:NN \cs_set_eq:NN
1848 \cs_new_eq:NN \bool_set_eq:Nc \cs_set_eq:Nc
1849 \cs_new_eq:NN \bool_set_eq:cN \cs_set_eq:cN
1850 \cs_new_eq:NN \bool_set_eq:cc \cs_set_eq:cc
1851 \cs_new_eq:NN \bool_gset_eq:NN \cs_gset_eq:NN
1852 \cs_new_eq:NN \bool_gset_eq:Nc \cs_gset_eq:Nc
1853 \cs_new_eq:NN \bool_gset_eq:cN \cs_gset_eq:cN
1854 \cs_new_eq:NN \bool_gset_eq:cc \cs_gset_eq:cc

```

\l\_tmpa\_bool A few booleans just if you need them.

```

\g_tmpa_bool
1855 \bool_new:N \l_tmpa_bool
1856 \bool_new:N \g_tmpa_bool

```

\bool\_if\_p:N Straight forward here. We could optimize here if we wanted to as the boolean can just be input directly.

```

\bool_if:N $\overline{TF}$ 
\bool_if:c $\overline{TF}$ 
1857 \prg_set_conditional:Npnn \bool_if:N #1 {p,TF,T,F}{
1858   \if_bool:N #1 \prg_return_true: \else: \prg_return_false: \fi:
1859 }
1860 \cs_generate_variant:Nn \bool_if_p:N {c}
1861 \cs_generate_variant:Nn \bool_if:N $\overline{TF}$  {c}
1862 \cs_generate_variant:Nn \bool_if:NT {c}
1863 \cs_generate_variant:Nn \bool_if:N $\overline{F}$  {c}

```

\bool\_while\_do:Nn A while loop where the boolean is tested before executing the statement. The ‘while’ version executes the code as long as the boolean is true; the ‘until’ version executes the code as long as the boolean is false.

```

\bool_while_do:cn
\bool_until_do:Nn
\bool_until_do:cn
1864 \cs_new:Npn \bool_while_do:Nn #1 #2 {
1865   \bool_if:NT #1 {#2 \bool_while_do:Nn #1 {#2}}
1866 }
1867 \cs_generate_variant:Nn \bool_while_do:Nn {c}

1868 \cs_new:Npn \bool_until_do:Nn #1 #2 {
1869   \bool_if:N $\overline{F}$  #1 {#2 \bool_until_do:Nn #1 {#2}}
1870 }
1871 \cs_generate_variant:Nn \bool_until_do:Nn {c}

```

<pre> \bool_do_while:Nn \bool_do_while:cn \bool_do_until:Nn \bool_do_until:cn </pre>	<p>A <b>do-while</b> loop where the body is performed at least once and the boolean is tested after executing the body. Otherwise identical to the above functions.</p> <pre> 1872 \cs_new:Npn \bool_do_while:Nn #1 #2 { 1873     #2 \bool_if:NT #1 {\bool_do_while:Nn #1 {#2}} 1874 } 1875 \cs_generate_variant:Nn \bool_do_while:Nn {c}  1876 \cs_new:Npn \bool_do_until:Nn #1 #2 { 1877     #2 \bool_if:NF #1 {\bool_do_until:Nn #1 {#2}} 1878 } 1879 \cs_generate_variant:Nn \bool_do_until:Nn {c} </pre>
--	---

## 97.6 Parsing boolean expressions

<pre> \bool_if_p:n \bool_if:nTF \bool_get_next:N \bool_cleanup:N \bool_choose:NN   \bool_!:w   \bool_(:w   \bool_p:w   \bool_8_1:w   \bool_I_1:w   \bool_8_0:w   \bool_I_0:w   \bool_)_0:w   \bool_)_1:w   \bool_S_0:w   \bool_S_1:w </pre>	<p>Evaluating the truth value of a list of predicates is done using an input syntax somewhat similar to the one found in other programming languages with ( and ) for grouping, ! for logical ‘Not’, &amp;&amp; for logical ‘And’ and    for logical Or. We shall use the terms Not, And, Or, Open and Close for these operations.</p> <p>Any expression is terminated by a Close operation. Evaluation happens from left to right in the following manner using a GetNext function:</p> <ul style="list-style-type: none"> <li>• If an Open is seen, start evaluating a new expression using the Eval function and call GetNext again.</li> <li>• If a Not is seen, insert a negating function (if-even in this case) and call GetNext.</li> <li>• If none of the above, start evaluating a new expression by reinserting the token found (this is supposed to be a predicate function) in front of Eval.</li> </ul> <p>The Eval function then contains a post-processing operation which grabs the instruction following the predicate. This is either And, Or or Close. In each case the truth value is used to determine where to go next. The following situations can arise:</p>
---	--

**<true>And** Current truth value is true, logical And seen, continue with GetNext to examine truth value of next boolean (sub-)expression.

**<false>And** Current truth value is false, logical And seen, stop evaluating the predicates within this sub-expression and break to the nearest Close. Then return *<false>*.

**<true>Or** Current truth value is true, logical Or seen, stop evaluating the predicates within this sub-expression and break to the nearest Close. Then return *<true>*.

**<false>Or** Current truth value is false, logical Or seen, continue with GetNext to examine truth value of next boolean (sub-)expression.

**<true>Close** Current truth value is true, Close seen, return *<true>*.

**$\langle false \rangle$ Close** Current truth value is false, Close seen, return  $\langle false \rangle$ .

We introduce an additional Stop operation with the following semantics:

**$\langle true \rangle$ Stop** Current truth value is true, return  $\langle true \rangle$ .

**$\langle false \rangle$ Stop** Current truth value is false, return  $\langle false \rangle$ .

The reasons for this follow below.

Now for how these works in practice. The canonical true and false values have numerical values 1 and 0 respectively. We evaluate this using the primitive `\tex_number:D` operation. First we issue a `\group_align_safe_begin:` as we are using `&&` as syntax shorthand for the And operation and we need to hide it for `TEX`. We also need to finish this special group before finally returning a `\c_true_bool` or `\c_false_bool` as there might otherwise be something left in front in the input stream. For this we call the Stop operation, denoted simply by a `S` following the last Close operation.

```

1880 \cs_set:Npn \bool_if_p:n #1{
1881   \group_align_safe_begin:
1882   \bool_get_next:N ( #1 )S
1883 }
```

The GetNext operation. We make it a switch: If not a `!` or `(`, we assume it is a predicate.

```

1884 \cs_set:Npn \bool_get_next:N #1{
1885   \use:c {
1886     bool_
1887     \if_meaning:w !#1 ! \else: \if_meaning:w (#1 ( \else: p \fi: \fi:
1888     :w
1889   } #1
1890 }
```

The Not operation. Discard the token read and reverse the truth value of the next expression using `\intexpr_if_even_p:n`.

```

1891 \cs_set:cpn {bool_!:w}#1{
1892   \exp_after:wN \intexpr_if_even_p:n \tex_number:D \bool_get_next:N
1893 }
```

The Open operation. Discard the token read and start a sub-expression.

```

1894 \cs_set:cpn {bool_( :w}#1{
1895   \exp_after:wN \bool_cleanup:N \tex_number:D \bool_get_next:N
1896 }
```

Otherwise just evaluate the predicate and look for And, Or or Close afterward.

```

1897 \cs_set:cpn {bool_p:w}{\exp_after:wN \bool_cleanup:N \tex_number:D }
```

This cleanup function can be omitted once predicates return their true/false booleans outside the conditionals.

```

1898 \cs_new_nopar:Npn \bool_cleanup:N #1{
1899   \exp_after:wN \bool_choose:NN \exp_after:wN #1
1900   \int_to_roman:w-'\q
1901 }

```

Branching the six way switch.

```

1902 \cs_new_nopar:Npn \bool_choose:NN #1#2{ \use:c{bool_#2_#1:w} }

```

Continues scanning. Must remove the second & or |.

```

1903 \cs_new_nopar:cpn{bool_&_1:w}&{\bool_get_next:N}
1904 \cs_new_nopar:cpn{bool_|_0:w}|{\bool_get_next:N}

```

Closing a group is just about returning the result. The Stop operation is similar except it closes the special alignment group before returning the boolean.

```

1905 \cs_new_nopar:cpn{bool_)_0:w}{ \c_false_bool }
1906 \cs_new_nopar:cpn{bool_)_1:w}{ \c_true_bool }
1907 \cs_new_nopar:cpn{bool_S_0:w}{\group_align_safe_end: \c_false_bool }
1908 \cs_new_nopar:cpn{bool_S_1:w}{\group_align_safe_end: \c_true_bool }

```

When the truth value has already been decided, we have to throw away the remainder of the current group as we are doing minimal evaluation. This is slightly tricky as there are no braces so we have to play match the () manually.

```

1909 \cs_set:cpn{bool_&_0:w}&{\bool_eval_skip_to_end:Nw \c_false_bool}
1910 \cs_set:cpn{bool_|_1:w}|{\bool_eval_skip_to_end:Nw \c_true_bool}

```

```

\bool_eval_skip_to_end:Nw
\bool_eval_skip_to_end_aux:Nw
\bool_eval_skip_to_end_auxii:Nw

```

There is always at least one ) waiting, namely the outer one. However, we are facing the problem that there may be more than one that need to be finished off and we have to detect the correct number of them. Here is a complicated example showing how this is done. After evaluating the following, we realize we must skip everything after the first And. Note the extra Close at the end.

```

\c_false_bool  && ((abc) && xyz) && ((xyz) && (def)))

```

First read up to the first Close. This gives us the list we first read up until the first right parenthesis so we are looking at the token list

```

((abc

```

This contains two Open markers so we must remove two groups. Since no evaluation of the contents is to be carried out, it doesn't matter how we remove the groups as long as we wind up with the correct result. We therefore first remove a () pair and what preceded the Open – but leave the contents as it may contain Open tokens itself – leaving

```
(abc && xyz) && ((xyz) && (def)))
```

Another round of this gives us

```
(abc && xyz
```

which still contains an Open so we remove another () pair, giving us

```
abc && xyz && ((xyz) && (def)))
```

Again we read up to a Close and again find Open tokens:

```
abc && xyz && ((xyz
```

Further reduction gives us

```
(xyz && (def)))
```

and then

```
(xyz && (def
```

with reduction to

```
xyz && (def))
```

and ultimately we arrive at no Open tokens being skipped and we can finally close the group nicely.

This whole operation could be made a lot simpler if we were allowed to do simple pattern matching. With a new enough pdfTeX one can do that sort of thing to test for existence of particular tokens.

```
1911 \cs_set:Npn \bool_eval_skip_to_end:Nw #1#2){
1912   \bool_eval_skip_to_end_aux:Nw #1 #2(\q_no_value\q_nil{#2}
1913 }
```

If no right parenthesis, then #3 is no\_value and we are done, return the boolean #1. If there is, we need to grab a () pair and then recurse

```
1914 \cs_set:Npn \bool_eval_skip_to_end_aux:Nw #1#2(#3#4\q_nil#5{
1915   \quark_if_no_value:NTF #3
1916   { #1 }
1917   { \bool_eval_skip_to_end_auxii:Nw #1 #5 }
1918 }
```

keep the boolean, throw away anything up to the ( as it is irrelevant, remove a () pair but remember to reinsert #3 as it may contain ( tokens!

```
1919 \cs_set:Npn \bool_eval_skip_to_end_auxii:Nw #1#2(#3){
1920   \bool_eval_skip_to_end:Nw #1#3 )
1921 }
```

\bool\_set:Nn This function evaluates a boolean expression and assigns the first argument the meaning  
\bool\_set:cn \c\_true\_bool or \c\_false\_bool.

```
\bool_gset:Nn
\bool_gset:cn
1922 \cs_new:Npn \bool_set:Nn #1#2 {\tex_chardef:D #1 = \bool_if_p:n {#2}}
1923 \cs_new:Npn \bool_gset:Nn #1#2 {
1924   \tex_global:D \tex_chardef:D #1 = \bool_if_p:n {#2}
1925 }
1926 \cs_generate_variant:Nn \bool_set:Nn {c}
1927 \cs_generate_variant:Nn \bool_gset:Nn {c}
```

\bool\_not\_p:n The not variant just reverses the outcome of \bool\_if\_p:n. Can be optimized but this is nice and simple and according to the implementation plan. Not even particularly useful to have it when the infix notation is easier to use.

```
1928 \cs_new:Npn \bool_not_p:n #1{ \bool_if_p:n{!(#1)} }
```

\bool\_xor\_p:nn Exclusive or. If the boolean expressions have same truth value, return false, otherwise return true.

```
1929 \cs_new:Npn \bool_xor_p:nn #1#2 {
1930   \intexpr_compare:nNnTF {\bool_if_p:n { #1 }} = {\bool_if_p:n { #2 }}
1931   {\c_false_bool}{\c_true_bool}
1932 }
1933 \prg_set_conditional:Npnn \bool_if:n #1 {TF,T,F}{
1934   \if_predicate:w \bool_if_p:n{#1}
1935   \prg_return_true: \else: \prg_return_false: \fi:
1936 }
```

\bool\_while\_do:nn #1 : Predicate test  
\bool\_until\_do:nn #2 : Code to execute

```
\bool_do_while:nn
\bool_do_until:nn
1937 \cs_new:Npn \bool_while_do:nn #1#2 {
1938   \bool_if:nT {#1} { #2 \bool_while_do:nn {#1}{#2} }
1939 }
1940 \cs_new:Npn \bool_until_do:nn #1#2 {
1941   \bool_if:nF {#1} { #2 \bool_until_do:nn {#1}{#2} }
1942 }
1943 \cs_new:Npn \bool_do_while:nn #1#2 {
1944   #2 \bool_if:nT {#1} { \bool_do_while:nn {#1}{#2} }
1945 }
1946 \cs_new:Npn \bool_do_until:nn #1#2 {
1947   #2 \bool_if:nF {#1} { \bool_do_until:nn {#1}{#2} }
1948 }
```



## 97.7 Case switch

`\prg_case_int:nnn`  
`\prg_case_int_aux:nnn`

This case switch is in reality quite simple. It takes three arguments:

1. An integer expression you wish to find.
2. A list of pairs of  $\{\langle integer\ expr\rangle\} \{\langle code\rangle\}$ . The list can be as long as is desired and  $\langle integer\ expr\rangle$  can be negative.
3. The code to be executed if the value wasn't found.

We don't need the else case here yet, so leave it dangling in the input stream.

```
1949 \cs_new:Npn \prg_case_int:nnn #1 #2 {
```

We will be parsing on #1 for each step so we might as well evaluate it first in case it is complicated.

```
1950   \exp_args:Nf \prg_case_int_aux:nnn { \intexpr_eval:n{#1}} #2
```

The ? below is just so there are enough arguments when we reach the end. And it made you look. ;-)

```
1951   \q_recursion_tail ? \q_recursion_stop
1952 }
1953 \cs_new:Npn \prg_case_int_aux:nnn #1#2#3{
```

If we reach the end, return the else case. We just remove braces.

```
1954   \quark_if_recursion_tail_stop_do:nn{#2}{\use:n}
```

Otherwise we compare (which evaluates #2 for us)

```
1955   \intexpr_compare:nNnTF{#1}={#2}
```

If true, we want to remove the remainder of the list, the else case and then execute the code specified. `\prg_end_case:nw {#3}` does just that in one go. This means f style expansion works the way one wants it to work.

```
1956   { \prg_end_case:nw {#3} }
1957   { \prg_case_int_aux:nnn {#1}}
1958 }
```

`\prg_case_dim:nnn`  
`\prg_case_dim_aux:nnn`

Same as `\prg_case_dim:nnn` except it is for  $\langle dim\rangle$  registers.

```
1959 \cs_new:Npn \prg_case_dim:nnn #1 #2 {
1960   \exp_args:No \prg_case_dim_aux:nnn {\dim_use:N \dim_eval:n{#1}} #2
1961   \q_recursion_tail ? \q_recursion_stop
1962 }
1963 \cs_new:Npn \prg_case_dim_aux:nnn #1#2#3{
1964   \quark_if_recursion_tail_stop_do:nn{#2}{\use:n}
```

```

1965 \dim_compare:nNnTF{#1}={#2}
1966 { \prg_end_case:nw {#3} }
1967 { \prg_case_dim_aux:nnn {#1}}
1968 }

```

`\prg_case_str:nnn` Same as `\prg_case_dim:nnn` except it is for strings.  
`\prg_case_str_aux:nnn`

```

1969 \cs_new:Npn \prg_case_str:nnn #1 #2 {
1970   \prg_case_str_aux:nnn {#1} #2
1971   \q_recursion_tail ? \q_recursion_stop
1972 }
1973 \cs_new:Npn \prg_case_str_aux:nnn #1#2#3{
1974   \quark_if_recursion_tail_stop_do:nn{#2}{\use:n}
1975   \tl_if_eq:xxTF{#1}{#2}
1976   { \prg_end_case:nw {#3} }
1977   { \prg_case_str_aux:nnn {#1}}
1978 }

```

`\prg_case_tl:Nnn` Same as `\prg_case_dim:nnn` except it is for token list variables.  
`\prg_case_tl_aux:NNn`

```

1979 \cs_new:Npn \prg_case_tl:Nnn #1 #2 {
1980   \prg_case_tl_aux:NNn #1 #2
1981   \q_recursion_tail ? \q_recursion_stop
1982 }
1983 \cs_new:Npn \prg_case_tl_aux:NNn #1#2#3{
1984   \quark_if_recursion_tail_stop_do:Nn #2{\use:n}
1985   \tl_if_eq:NNTF #1 #2
1986   { \prg_end_case:nw {#3} }
1987   { \prg_case_tl_aux:NNn #1}
1988 }

```

`\prg_end_case:nw` Ending a case switch is always performed the same way so we optimize for this. `#1` is the code to execute, `#2` the remainder, and `#3` the dangling else case.

```

1989 \cs_new:Npn \prg_end_case:nw #1#2\q_recursion_stop#3{#1}

```

## 97.8 Sorting

`\prg_define_quicksort:nnn` `#1` is the name, `#2` and `#3` are the tokens enclosing the argument. For the somewhat strange *<clist>* type which doesn't enclose the items but uses a separator we define it by hand afterwards. When doing the first pass, the algorithm wraps all elements in braces and then uses a generic quicksort which works on token lists.

As an example

```

\prg_define_quicksort:nnn{seq}{\seq_elt:w}{\seq_elt_end:w}

```

defines the user function `\seq_quicksort:n` and furthermore expects to use the two functions `\seq_quicksort_compare:nnTF` which compares the items and `\seq_quicksort_function:n` which is placed before each sorted item. It is up to the programmer to define these functions when needed. For the `seq` type a sequence is a token list variable, so one additionally has to define

```
\cs_set_nopar:Npn \seq_quicksort:N{\exp_args:No\seq_quicksort:n}
```

For details on the implementation see “Sorting in T<sub>E</sub>X’s Mouth” by Bernd Raichle. Firstly we define the function for parsing the initial list and then the braced list afterwards.

```
1990 \cs_new_nopar:Npn \prg_define_quicksort:nnn #1#2#3 {
1991   \cs_set:cpx{#1_quicksort:n}##1{
1992     \exp_not:c{#1_quicksort_start_partition:w} ##1
1993     \exp_not:n{#2\q_nil#3\q_stop}
1994   }
1995   \cs_set:cpx{#1_quicksort_braced:n}##1{
1996     \exp_not:c{#1_quicksort_start_partition_braced:n} ##1
1997     \exp_not:N\q_nil\exp_not:N\q_stop
1998   }
1999   \cs_set:cpx {#1_quicksort_start_partition:w} #2 ##1 #3{
2000     \exp_not:N \quark_if_nil:nT {##1}\exp_not:N \use_none_delimit_by_q_stop:w
2001     \exp_not:c{#1_quicksort_do_partition_i:nnnw} {##1}{-}{-}
2002   }
2003   \cs_set:cpx {#1_quicksort_start_partition_braced:n} ##1 {
2004     \exp_not:N \quark_if_nil:nT {##1}\exp_not:N \use_none_delimit_by_q_stop:w
2005     \exp_not:c{#1_quicksort_do_partition_i_braced:nnnn} {##1}{-}{-}
2006   }
```

Now for doing the partitions.

```
2007   \cs_set:cpx {#1_quicksort_do_partition_i:nnnw} ##1##2##3 #2 ##4 #3 {
2008     \exp_not:N \quark_if_nil:nTF {##4} \exp_not:c {#1_do_quicksort_braced:nnnw}
2009     {
2010       \exp_not:c{#1_quicksort_compare:nnTF}{##1}{##4}
2011       \exp_not:c{#1_quicksort_partition_greater_ii:nnnn}
2012       \exp_not:c{#1_quicksort_partition_less_ii:nnnn}
2013     }
2014     {##1}{##2}{##3}{##4}
2015   }
2016   \cs_set:cpx {#1_quicksort_do_partition_i_braced:nnnn} ##1##2##3##4 {
2017     \exp_not:N \quark_if_nil:nTF {##4} \exp_not:c {#1_do_quicksort_braced:nnnw}
2018     {
2019       \exp_not:c{#1_quicksort_compare:nnTF}{##1}{##4}
2020       \exp_not:c{#1_quicksort_partition_greater_ii_braced:nnnn}
2021       \exp_not:c{#1_quicksort_partition_less_ii_braced:nnnn}
2022     }
2023     {##1}{##2}{##3}{##4}
2024   }
```

```

2025 \cs_set:cpx {#1_quicksort_do_partition_ii:nnnw} ##1##2##3 #2 ##4 #3 {
2026   \exp_not:N \quark_if_nil:nTF {##4} \exp_not:c {#1_do_quicksort_braced:nnnnw}
2027   {
2028     \exp_not:c{#1_quicksort_compare:nnTF}{##4}{##1}
2029     \exp_not:c{#1_quicksort_partition_less_i:nnnn}
2030     \exp_not:c{#1_quicksort_partition_greater_i:nnnn}
2031   }
2032   {##1}{##2}{##3}{##4}
2033 }
2034 \cs_set:cpx {#1_quicksort_do_partition_ii_braced:nnnn} ##1##2##3##4 {
2035   \exp_not:N \quark_if_nil:nTF {##4} \exp_not:c {#1_do_quicksort_braced:nnnnw}
2036   {
2037     \exp_not:c{#1_quicksort_compare:nnTF}{##4}{##1}
2038     \exp_not:c{#1_quicksort_partition_less_i_braced:nnnn}
2039     \exp_not:c{#1_quicksort_partition_greater_i_braced:nnnn}
2040   }
2041   {##1}{##2}{##3}{##4}
2042 }

```

This part of the code handles the two branches in each sorting. Again we will also have to do it braced.

```

2043 \cs_set:cpx {#1_quicksort_partition_less_i:nnnn} ##1##2##3##4{
2044   \exp_not:c{#1_quicksort_do_partition_i:nnnw}{##1}{##2}{##4}{##3}
2045 \cs_set:cpx {#1_quicksort_partition_less_ii:nnnn} ##1##2##3##4{
2046   \exp_not:c{#1_quicksort_do_partition_ii:nnnw}{##1}{##2}{##3}{##4}}
2047 \cs_set:cpx {#1_quicksort_partition_greater_i:nnnn} ##1##2##3##4{
2048   \exp_not:c{#1_quicksort_do_partition_i:nnnw}{##1}{##4}{##2}{##3}
2049 \cs_set:cpx {#1_quicksort_partition_greater_ii:nnnn} ##1##2##3##4{
2050   \exp_not:c{#1_quicksort_do_partition_ii:nnnw}{##1}{##2}{##4}{##3}
2051 \cs_set:cpx {#1_quicksort_partition_less_i_braced:nnnn} ##1##2##3##4{
2052   \exp_not:c{#1_quicksort_do_partition_i_braced:nnnn}{##1}{##2}{##4}{##3}
2053 \cs_set:cpx {#1_quicksort_partition_less_ii_braced:nnnn} ##1##2##3##4{
2054   \exp_not:c{#1_quicksort_do_partition_ii_braced:nnnn}{##1}{##2}{##3}{##4}}
2055 \cs_set:cpx {#1_quicksort_partition_greater_i_braced:nnnn} ##1##2##3##4{
2056   \exp_not:c{#1_quicksort_do_partition_i_braced:nnnn}{##1}{##4}{##2}{##3}
2057 \cs_set:cpx {#1_quicksort_partition_greater_ii_braced:nnnn} ##1##2##3##4{
2058   \exp_not:c{#1_quicksort_do_partition_ii_braced:nnnn}{##1}{##2}{##4}{##3}

```

Finally, the big kahuna! This is where the sub-lists are sorted.

```

2059 \cs_set:cpx {#1_do_quicksort_braced:nnnnw} ##1##2##3##4\q_stop {
2060   \exp_not:c{#1_quicksort_braced:n}{##2}
2061   \exp_not:c{#1_quicksort_function:n}{##1}
2062   \exp_not:c{#1_quicksort_braced:n}{##3}
2063 }
2064 }

```

`\prg_quicksort:n` A simple version. Sorts a list of tokens, uses the function `\prg_quicksort_compare:nnTF` to compare items, and places the function `\prg_quicksort_function:n` in front of each

of them.

```
2065 \prg_define_quicksort:nnn {prg}{-}{-}
```

```
\prg_quicksort_function:n  
\prg_quicksort_compare:nnTF
```

```
2066 \cs_set:Npn \prg_quicksort_function:n {\ERROR}
```

```
2067 \cs_set:Npn \prg_quicksort_compare:nnTF {\ERROR}
```

## 97.9 Variable type and scope

```
\prg_variable_get_scope:N  
\prg_variable_get_scope_aux:w  
\prg_variable_get_type:N  
\prg_variable_get_type:w
```

Expandable functions to find the type of a variable, and to return g if the variable is global. The trick for `\prg_variable_get_scope:N` is the same as that in `\cs_split_function:NN`, but it can be simplified as the requirements here are less complex.

```
2068 \group_begin:  
2069   \tex_lccode:D '\& = '\g \tex_relax:D  
2070   \tex_catcode:D '\& = \c_twelve \tex_relax:D  
2071 \tl_to_lowercase:n {  
2072   \group_end:  
2073   \cs_new_nopar:Npn \prg_variable_get_scope:N #1 {  
2074     \exp_last_unbraced:Nf \prg_variable_get_scope_aux:w  
2075     { \cs_to_str:N #1 \exp_stop_f: \q_nil }  
2076   }  
2077   \cs_new_nopar:Npn \prg_variable_get_scope_aux:w #1#2 \q_nil {  
2078     \token_if_eq_meaning:NNT & #1 {g}  
2079   }  
2080 }  
2081 \group_begin:  
2082   \tex_lccode:D '\& = '\_ \tex_relax:D  
2083   \tex_catcode:D '\& = \c_twelve \tex_relax:D  
2084 \tl_to_lowercase:n {  
2085   \group_end:  
2086   \cs_new_nopar:Npn \prg_variable_get_type:N #1 {  
2087     \exp_after:wN \p;rg_variable_get_type_aux:w  
2088     \token_to_str:N #1 & a \q_nil  
2089   }  
2090   \cs_new_nopar:Npn \prg_variable_get_type_aux:w #1 & #2#3 \q_nil {  
2091     \token_if_eq_meaning:NNTF a #2 {  
2092       #1  
2093     }{  
2094       \prg_variable_get_type_aux:w #2#3 \q_nil  
2095     }  
2096   }  
2097 }
```

That's it (for now).

```
2098 </initex | package>
```

```

2099 <*showmemory>
2100 \showMemUsage
2101 </showmemory>

```

## 98 l3quark implementation

We start by ensuring that the required packages are loaded. We check for `l3expan` since this a basic package that is essential for use of any higher-level package.

```

2102 <*package>
2103 \ProvidesExplPackage
2104   {\filename}{\filedate}{\fileversion}{\filedescription}
2105 \package_check_loaded_expl:
2106 </package>
2107 <*initex | package>

```

`\quark_new:N` Allocate a new quark.

```

2108 \cs_new_nopar:Npn \quark_new:N #1{\tl_new:Nn #1{#1}}

```

`\q_stop` `\q_stop` is often used as a marker in parameter text, `\q_no_value` is the canonical missing value, and `\q_nil` represents a nil pointer in some data structures.

```

2109 \quark_new:N \q_stop
2110 \quark_new:N \q_no_value
2111 \quark_new:N \q_nil

```

`\q_error` `\q_error` We need two additional quarks. `\q_error` delimits the end of the computation for purposes of error recovery. `\q_mark` is used in parameter text when we need a scanning boundary that is distinct from `\q_stop`.

```

2112 \quark_new:N\q_error
2113 \quark_new:N\q_mark

```

`\q_recursion_tail` `\q_recursion_stop` Quarks for ending recursions. Only ever used there! `\q_recursion_tail` is appended to whatever list structure we are doing recursion on, meaning it is added as a proper list item with whatever list separator is in use. `\q_recursion_stop` is placed directly after the list.

```

2114 \quark_new:N\q_recursion_tail
2115 \quark_new:N\q_recursion_stop

```

`\quark_if_recursion_tail_stop:n` `\quark_if_recursion_tail_stop:N` `\quark_if_recursion_tail_stop:o` When doing recursions it is easy to spend a lot of time testing if we found the end marker. To avoid this, we use a recursion end marker every time we do this kind of task. Also, if the recursion end marker is found, we wrap things up and finish.

```

2116 \cs_new:Npn \quark_if_recursion_tail_stop:n #1 {
2117   \exp_after:wN\if_meaning:w
2118   \quark_if_recursion_tail_aux:w #1?\q_nil\q_recursion_tail\q_recursion_tail
2119   \exp_after:wN \use_none_delimit_by_q_recursion_stop:w
2120   \fi:
2121 }
2122 \cs_new:Npn \quark_if_recursion_tail_stop:N #1 {
2123   \if_meaning:w#1\q_recursion_tail
2124   \exp_after:wN \use_none_delimit_by_q_recursion_stop:w
2125   \fi:
2126 }
2127 \cs_generate_variant:Nn \quark_if_recursion_tail_stop:n {o}

```

rk\_if\_recursion\_tail\_stop\_do:nn  
 rk\_if\_recursion\_tail\_stop\_do:Nn  
 rk\_if\_recursion\_tail\_stop\_do:on

```

2128 \cs_new:Npn \quark_if_recursion_tail_stop_do:nn #1#2 {
2129   \exp_after:wN\if_meaning:w
2130   \quark_if_recursion_tail_aux:w #1?\q_nil\q_recursion_tail\q_recursion_tail
2131   \exp_after:wN \use_i_delimit_by_q_recursion_stop:nw
2132   \else:
2133     \exp_after:wN\use_none:n
2134   \fi:
2135   {#2}
2136 }
2137 \cs_new:Npn \quark_if_recursion_tail_stop_do:Nn #1#2 {
2138   \if_meaning:w #1\q_recursion_tail
2139   \exp_after:wN \use_i_delimit_by_q_recursion_stop:nw
2140   \else:
2141     \exp_after:wN\use_none:n
2142   \fi:
2143   {#2}
2144 }
2145 \cs_generate_variant:Nn \quark_if_recursion_tail_stop_do:nn {on}

```

\quark\_if\_recursion\_tail\_aux:w

```

2146 \cs_new:Npn \quark_if_recursion_tail_aux:w #1#2 \q_nil \q_recursion_tail {#1}

```

\quark\_if\_no\_value\_p:N Here we test if we found a special quark as the first argument. We better start with  
 \quark\_if\_no\_value\_p:n \q\_no\_value as the first argument since the whole thing may otherwise loop if #1 is  
 \quark\_if\_no\_value:N $\overline{TF}$  wrongly given a string like aabc instead of a single token.<sup>11</sup>  
 \quark\_if\_no\_value:n $\overline{TF}$

```

2147 \prg_new_conditional:Nnn \quark_if_no_value:N {p,TF,T,F} {
2148   \if_meaning:w \q_no_value #1
2149   \prg_return_true: \else: \prg_return_false: \fi:
2150 }

```

---

<sup>11</sup>It may still loop in special circumstances however!

We also provide an `n` type. If run under a sufficiently new pdf $\epsilon$ -T<sub>E</sub>X, it uses a built-in primitive for string comparisons, otherwise it uses the slower `\str_if_eq_var_p:nf` function. In the latter case it would be faster to use a temporary token list variable but it would render the function non-expandable. Using the pdf $\epsilon$ -T<sub>E</sub>X primitive is the preferred approach. Note that we have to add a manual space token in the first part of the comparison, otherwise it is gobbled by `\str_if_eq_var_p:nf`. The reason for using this function instead of `\str_if_eq_p:nn` is that a sequence like `\q_no_value` will test equal to `\q_no_value` using the latter test function and unfortunately this example turned up in one application.

```

2151 \cs_if_exist:cTF {pdf_strcmp:D}
2152 {
2153   \prg_new_conditional:Nnn \quark_if_no_value:n {p,TF,T,F} {
2154     \if_num:w \pdf_strcmp:D
2155       {\exp_not:N \q_no_value}
2156       {\exp_not:n{#1}} = \c_zero
2157     \prg_return_true: \else: \prg_return_false:
2158     \fi:
2159   }
2160 }
2161 {
2162   \prg_new_conditional:Nnn \quark_if_no_value:n {p,TF,T,F} {
2163     \exp_args:NNo
2164     \if_predicate:w \str_if_eq_var_p:nf
2165       {\token_to_str:N\q_no_value\iow_space:}
2166       {\tl_to_str:n{#1}}
2167     \prg_return_true: \else: \prg_return_false:
2168     \fi:
2169   }
2170 }

```

`\quark_if_nil_p:N` A function to check for the presence of `\q_nil`.

`\quark_if_nil:N $\underline{TF}$`

```

2171 \prg_new_conditional:Nnn \quark_if_nil:N {p,TF,T,F} {
2172   \if_meaning:w \q_nil #1 \prg_return_true: \else: \prg_return_false: \fi:
2173 }

```

`\quark_if_nil_p:n` A function to check for the presence of `\q_nil`.

`\quark_if_nil_p:V`

`\quark_if_nil_p:o`

`\quark_if_nil:n $\underline{TF}$`

`\quark_if_nil:V $\underline{TF}$`

`\quark_if_nil:o $\underline{TF}$`

```

2174 \cs_if_exist:cTF {pdf_strcmp:D} {
2175   \prg_new_conditional:Nnn \quark_if_nil:n {p,TF,T,F} {
2176     \if_num:w \pdf_strcmp:D
2177       {\exp_not:N \q_nil}
2178       {\exp_not:n{#1}} = \c_zero
2179     \prg_return_true: \else: \prg_return_false:
2180     \fi:
2181   }
2182 }
2183 {

```



```

2184 \prg_new_conditional:Nnn \quark_if_nil:n {p,TF,T,F} {
2185   \exp_args:NNo
2186   \if_predicate:w \str_if_eq_var_p:nf
2187     {\token_to_str:N\q_nil\iow_space:}
2188     {\tl_to_str:n{#1}}
2189   \prg_return_true: \else: \prg_return_false:
2190   \fi:
2191 }
2192 }
2193 \cs_generate_variant:Nn \quark_if_nil_p:n {V}
2194 \cs_generate_variant:Nn \quark_if_nil:nTF {V}
2195 \cs_generate_variant:Nn \quark_if_nil:nT {V}
2196 \cs_generate_variant:Nn \quark_if_nil:nF {V}
2197 \cs_generate_variant:Nn \quark_if_nil_p:n {o}
2198 \cs_generate_variant:Nn \quark_if_nil:nTF {o}
2199 \cs_generate_variant:Nn \quark_if_nil:nT {o}
2200 \cs_generate_variant:Nn \quark_if_nil:nF {o}

```

Show token usage:

```

2201
2202 <*showmemory>
2203 \showMemUsage
2204 </showmemory>

```

## 99 l3token implementation

### 99.1 Documentation of internal functions

\l_peek_true_tl \l_peek_false_tl
-------------------------------------

These token list variables are used internally when choosing either the true or false branches of a test.

\l_peek_search_tl
-------------------

Used to store \l\_peek\_search\_token.

\peek_tmp:w
-------------

Scratch function used to gobble tokens from the input stream.

\l_peek_true_aux_tl \c_peek_true_remove_next_tl
--

These token list variables are used internally when choosing either the true or false branches of a test.

```
\peek_ignore_spaces_execute_branches:
\peek_ignore_spaces_aux:
```

Functions used to ignore space tokens in the input stream.

## 99.2 Module code

First a few required packages to get this going.

```
2205 \<package>
2206 \ProvidesExplPackage
2207   {\filename}{\filedate}{\fileversion}{\filedescription}
2208 \package_check_loaded_expl:
2209 \</package>
2210 \<initex | package>
```

## 99.3 Character tokens

```
\char_set_catcode:w
\char_set_catcode:nn
\char_value_catcode:w
\char_value_catcode:n
\char_show_value_catcode:w
\char_show_value_catcode:n
2211 \cs_new_eq:NN \char_set_catcode:w \tex_catcode:D
2212 \cs_new_nopar:Npn \char_set_catcode:nn #1#2 {
2213   \char_set_catcode:w #1 = \intexpr_eval:w #2\intexpr_eval_end:
2214 }
2215 \cs_new_nopar:Npn \char_value_catcode:w { \int_use:N \tex_catcode:D }
2216 \cs_new_nopar:Npn \char_value_catcode:n #1 {
2217   \char_value_catcode:w \intexpr_eval:w #1\intexpr_eval_end:
2218 }
2219 \cs_new_nopar:Npn \char_show_value_catcode:w {
2220   \tex_showthe:D \tex_catcode:D
2221 }
2222 \cs_new_nopar:Npn \char_show_value_catcode:n #1 {
2223   \char_show_value_catcode:w \intexpr_eval:w #1\intexpr_eval_end:
2224 }
```

```
\char_make_escape:N
\char_make_begin_group:N
\char_make_end_group:N
\char_make_math_shift:N
\char_make_alignment:N
\char_make_end_line:N
\char_make_parameter:N
\char_make_math_superscript:N
\char_make_math_subscript:N
\char_make_ignore:N
\char_make_space:N
\char_make_letter:N
\char_make_other:N
\char_make_active:N
\char_make_comment:N
\char_make_invalid:N
2225 \cs_new_nopar:Npn \char_make_escape:N #1 { \char_set_catcode:nn {'#1} {\c_zero} }
2226 \cs_new_nopar:Npn \char_make_begin_group:N #1 { \char_set_catcode:nn {'#1} {\c_one} }
2227 \cs_new_nopar:Npn \char_make_end_group:N #1 { \char_set_catcode:nn {'#1} {\c_two} }
2228 \cs_new_nopar:Npn \char_make_math_shift:N #1 { \char_set_catcode:nn {'#1} {\c_three} }
2229 \cs_new_nopar:Npn \char_make_alignment:N #1 { \char_set_catcode:nn {'#1} {\c_four} }
2230 \cs_new_nopar:Npn \char_make_end_line:N #1 { \char_set_catcode:nn {'#1} {\c_five} }
2231 \cs_new_nopar:Npn \char_make_parameter:N #1 { \char_set_catcode:nn {'#1} {\c_six} }
2232 \cs_new_nopar:Npn \char_make_math_superscript:N #1 { \char_set_catcode:nn {'#1} {\c_seven} }
2233 \cs_new_nopar:Npn \char_make_math_subscript:N #1 { \char_set_catcode:nn {'#1} {\c_eight} }
2234 \cs_new_nopar:Npn \char_make_ignore:N #1 { \char_set_catcode:nn {'#1} {\c_nine} }
2235 \cs_new_nopar:Npn \char_make_space:N #1 { \char_set_catcode:nn {'#1} {\c_ten} }
```

```

2236 \cs_new_nopar:Npn \char_make_letter:N          #1 { \char_set_catcode:nn {'#1} {\c_eleven}
2237 \cs_new_nopar:Npn \char_make_other:N           #1 { \char_set_catcode:nn {'#1} {\c_twelve}
2238 \cs_new_nopar:Npn \char_make_active:N          #1 { \char_set_catcode:nn {'#1} {\c_thirteen}
2239 \cs_new_nopar:Npn \char_make_comment:N         #1 { \char_set_catcode:nn {'#1} {\c_fourteen}
2240 \cs_new_nopar:Npn \char_make_invalid:N         #1 { \char_set_catcode:nn {'#1} {\c_fifteen}

```

```

\char_make_escape:n
\char_make_begin_group:n
\char_make_end_group:n
\char_make_math_shift:n
\char_make_alignment:n
\char_make_end_line:n
\char_make_parameter:n
\char_make_math_superscript:n
\char_make_math_subscript:n
\char_make_ignore:n
\char_make_space:n
\char_make_letter:n
\char_make_other:n
\char_make_active:n
\char_make_comment:n
\char_make_invalid:n
2241 \cs_new_nopar:Npn \char_make_escape:n          #1 { \char_set_catcode:nn {'#1} {\c_zero} }
2242 \cs_new_nopar:Npn \char_make_begin_group:n      #1 { \char_set_catcode:nn {'#1} {\c_one} }
2243 \cs_new_nopar:Npn \char_make_end_group:n        #1 { \char_set_catcode:nn {'#1} {\c_two} }
2244 \cs_new_nopar:Npn \char_make_math_shift:n      #1 { \char_set_catcode:nn {'#1} {\c_three} }
2245 \cs_new_nopar:Npn \char_make_alignment:n        #1 { \char_set_catcode:nn {'#1} {\c_four} }
2246 \cs_new_nopar:Npn \char_make_end_line:n         #1 { \char_set_catcode:nn {'#1} {\c_five} }
2247 \cs_new_nopar:Npn \char_make_parameter:n        #1 { \char_set_catcode:nn {'#1} {\c_six} }
2248 \cs_new_nopar:Npn \char_make_math_superscript:n #1 { \char_set_catcode:nn {'#1} {\c_seven} }
2249 \cs_new_nopar:Npn \char_make_math_subscript:n   #1 { \char_set_catcode:nn {'#1} {\c_eight} }
2250 \cs_new_nopar:Npn \char_make_ignore:n          #1 { \char_set_catcode:nn {'#1} {\c_nine} }
2251 \cs_new_nopar:Npn \char_make_space:n           #1 { \char_set_catcode:nn {'#1} {\c_ten} }
2252 \cs_new_nopar:Npn \char_make_letter:n          #1 { \char_set_catcode:nn {'#1} {\c_eleven} }
2253 \cs_new_nopar:Npn \char_make_other:n           #1 { \char_set_catcode:nn {'#1} {\c_twelve} }
2254 \cs_new_nopar:Npn \char_make_active:n          #1 { \char_set_catcode:nn {'#1} {\c_thirteen} }
2255 \cs_new_nopar:Npn \char_make_comment:n         #1 { \char_set_catcode:nn {'#1} {\c_fourteen} }
2256 \cs_new_nopar:Npn \char_make_invalid:n         #1 { \char_set_catcode:nn {'#1} {\c_fifteen} }

```

Math codes.

```

\char_set_mathcode:w
\char_set_mathcode:nn
\char_gset_mathcode:w
\char_gset_mathcode:nn
\char_value_mathcode:w
\char_value_mathcode:n
\char_show_value_mathcode:w
\char_show_value_mathcode:n
2257 \cs_new_eq:NN \char_set_mathcode:w \tex_mathcode:D
2258 \cs_new_nopar:Npn \char_set_mathcode:nn #1#2 {
2259   \char_set_mathcode:w #1 = \intexpr_eval:w #2\intexpr_eval_end:
2260 }
2261 \cs_new_protected_nopar:Npn \char_gset_mathcode:w { \pref_global:D \tex_mathcode:D }
2262 \cs_new_nopar:Npn \char_gset_mathcode:nn #1#2 {
2263   \char_gset_mathcode:w #1 = \intexpr_eval:w #2\intexpr_eval_end:
2264 }
2265 \cs_new_nopar:Npn \char_value_mathcode:w { \int_use:N \tex_mathcode:D }
2266 \cs_new_nopar:Npn \char_value_mathcode:n #1 {
2267   \char_value_mathcode:w \intexpr_eval:w #1\intexpr_eval_end:
2268 }
2269 \cs_new_nopar:Npn \char_show_value_mathcode:w { \tex_showthe:D \tex_mathcode:D }
2270 \cs_new_nopar:Npn \char_show_value_mathcode:n #1 {
2271   \char_show_value_mathcode:w \intexpr_eval:w #1\intexpr_eval_end:
2272 }

```

```

\char_set_lccode:w
\char_set_lccode:nn
\char_value_lccode:w
\char_value_lccode:n
\char_show_value_lccode:w
\char_show_value_lccode:n
2273 \cs_new_eq:NN \char_set_lccode:w \tex_lccode:D
2274 \cs_new_nopar:Npn \char_set_lccode:nn #1#2{
2275   \char_set_lccode:w #1 = \intexpr_eval:w #2\intexpr_eval_end:

```

```

2276 }
2277 \cs_new_nopar:Npn \char_value_lccode:w {\int_use:N\tex_lccode:D}
2278 \cs_new_nopar:Npn \char_value_lccode:n #1{\char_value_lccode:w
2279   \intexpr_eval:w #1\intexpr_eval_end:}
2280 \cs_new_nopar:Npn \char_show_value_lccode:w {\tex_showthe:D\tex_lccode:D}
2281 \cs_new_nopar:Npn \char_show_value_lccode:n #1{
2282   \char_show_value_lccode:w \intexpr_eval:w #1\intexpr_eval_end:}

\char_set_uccode:w
\char_set_uccode:nn
\char_value_uccode:w 2283 \cs_new_eq:NN \char_set_uccode:w \tex_uccode:D
\char_value_uccode:n 2284 \cs_new_nopar:Npn \char_set_uccode:nn #1#2{
\char_show_value_uccode:w 2285   \char_set_uccode:w #1 = \intexpr_eval:w #2\intexpr_eval_end:
\char_show_value_uccode:n 2286 }
2287 \cs_new_nopar:Npn \char_value_uccode:w {\int_use:N\tex_uccode:D}
2288 \cs_new_nopar:Npn \char_value_uccode:n #1{\char_value_uccode:w
2289   \intexpr_eval:w #1\intexpr_eval_end:}
2290 \cs_new_nopar:Npn \char_show_value_uccode:w {\tex_showthe:D\tex_uccode:D}
2291 \cs_new_nopar:Npn \char_show_value_uccode:n #1{
2292   \char_show_value_uccode:w \intexpr_eval:w #1\intexpr_eval_end:}

\char_set_sfcodes:w
\char_set_sfcodes:nn
\char_value_sfcodes:w 2293 \cs_new_eq:NN \char_set_sfcodes:w \tex_sfcodes:D
\char_value_sfcodes:n 2294 \cs_new_nopar:Npn \char_set_sfcodes:nn #1#2 {
\char_show_value_sfcodes:w 2295   \char_set_sfcodes:w #1 = \intexpr_eval:w #2\intexpr_eval_end:
\char_show_value_sfcodes:n 2296 }
2297 \cs_new_nopar:Npn \char_value_sfcodes:w { \int_use:N \tex_sfcodes:D }
2298 \cs_new_nopar:Npn \char_value_sfcodes:n #1 {
2299   \char_value_sfcodes:w \intexpr_eval:w #1\intexpr_eval_end:
2300 }
2301 \cs_new_nopar:Npn \char_show_value_sfcodes:w { \tex_showthe:D \tex_sfcodes:D }
2302 \cs_new_nopar:Npn \char_show_value_sfcodes:n #1 {
2303   \char_show_value_sfcodes:w \intexpr_eval:w #1\intexpr_eval_end:
2304 }

```

## 99.4 Generic tokens

`\token_new:Nn` Creates a new token. (Will: why can't this just be `\cs_new_eq:NN \token_new:Nn \cs_gnew_eq:NN?` Seriously, that doesn't work!)

```

2305 \cs_new_nopar:Npn \token_new:Nn #1#2 {\cs_gnew_eq:NN #1#2}

```

`\c_group_begin_token` We define these useful tokens. We have to do it by hand with the brace tokens for obvious reasons.

```

\c_group_end_token
\c_math_shift_token
\c_alignment_tab_token
\c_parameter_token
\c_math_superscript_token
\c_math_subscript_token
\c_space_token
\c_letter_token
\c_other_char_token
\c_active_char_token

```

```

2306 \cs_new_eq:NN \c_group_begin_token {
2307 \cs_new_eq:NN \c_group_end_token }

```

```

2308 \group_begin:
2309 \char_set_catcode:nn{'\*}{3}
2310 \token_new:Nn \c_math_shift_token {*}
2311 \char_set_catcode:nn{'\*}{4}
2312 \token_new:Nn \c_alignment_tab_token {*}
2313 \token_new:Nn \c_parameter_token {#}
2314 \token_new:Nn \c_math_superscript_token {^}
2315 \char_set_catcode:nn{'\*}{8}
2316 \token_new:Nn \c_math_subscript_token {*}
2317 \token_new:Nn \c_space_token {~}
2318 \token_new:Nn \c_letter_token {a}
2319 \token_new:Nn \c_other_char_token {1}
2320 \char_set_catcode:nn{'\*}{13}
2321 \cs_gset_nopar:Npn \c_active_char_token {\exp_not:N*}
2322 \group_end:

```

`\token_if_group_begin_p:N` Check if token is a begin group token. We use the constant `\c_group_begin_token` for this.  
`\token_if_group_begin:NTF`

```

2323 \prg_new_conditional:Nnn \token_if_group_begin:N {p,TF,T,F} {
2324   \if_catcode:w \exp_not:N #1\c_group_begin_token
2325     \prg_return_true: \else: \prg_return_false: \fi:
2326 }

```

`\token_if_group_end_p:N` Check if token is a end group token. We use the constant `\c_group_end_token` for this.  
`\token_if_group_end:NTF`

```

2327 \prg_new_conditional:Nnn \token_if_group_end:N {p,TF,T,F} {
2328   \if_catcode:w \exp_not:N #1\c_group_end_token
2329     \prg_return_true: \else: \prg_return_false: \fi:
2330 }

```

`\token_if_math_shift_p:N` Check if token is a math shift token. We use the constant `\c_math_shift_token` for this.  
`\token_if_math_shift:NTF`

```

2331 \prg_new_conditional:Nnn \token_if_math_shift:N {p,TF,T,F} {
2332   \if_catcode:w \exp_not:N #1\c_math_shift_token
2333     \prg_return_true: \else: \prg_return_false: \fi:
2334 }

```

`\token_if_alignment_tab_p:N` Check if token is an alignment tab token. We use the constant `\c_alignment_tab_token` for this.  
`\token_if_alignment_tab:NTF`

```

2335 \prg_new_conditional:Nnn \token_if_alignment_tab:N {p,TF,T,F} {
2336   \if_catcode:w \exp_not:N #1\c_alignment_tab_token
2337     \prg_return_true: \else: \prg_return_false: \fi:
2338 }

```

`\token_if_parameter_p:N` Check if token is a parameter token. We use the constant `\c_parameter_token` for this.  
`\token_if_parameter:NTF` We have to trick  $\TeX$  a bit to avoid an error message.

```

2339 \prg_new_conditional:Nnn \token_if_parameter:N {p,TF,T,F} {
2340   \exp_after:wN\if_catcode:w \cs:w c_parameter_token\cs_end:\exp_not:N #1
2341   \prg_return_true: \else: \prg_return_false: \fi:
2342 }

```

`\token_if_math_superscript_p:N` Check if token is a math superscript token. We use the constant `\c_math_superscript_token`  
`\token_if_math_superscript:N $\underline{TF}$`  for this.

```

2343 \prg_new_conditional:Nnn \token_if_math_superscript:N {p,TF,T,F} {
2344   \if_catcode:w \exp_not:N #1\c_math_superscript_token
2345   \prg_return_true: \else: \prg_return_false: \fi:
2346 }

```

`\token_if_math_subscript_p:N` Check if token is a math subscript token. We use the constant `\c_math_subscript_token`  
`\token_if_math_subscript:N $\underline{TF}$`  for this.

```

2347 \prg_new_conditional:Nnn \token_if_math_subscript:N {p,TF,T,F} {
2348   \if_catcode:w \exp_not:N #1\c_math_subscript_token
2349   \prg_return_true: \else: \prg_return_false: \fi:
2350 }

```

`\token_if_space_p:N` Check if token is a space token. We use the constant `\c_space_token` for this.  
`\token_if_space:N $\underline{TF}$`

```

2351 \prg_new_conditional:Nnn \token_if_space:N {p,TF,T,F} {
2352   \if_catcode:w \exp_not:N #1\c_space_token
2353   \prg_return_true: \else: \prg_return_false: \fi:
2354 }

```

`\token_if_letter_p:N` Check if token is a letter token. We use the constant `\c_letter_token` for this.  
`\token_if_letter:N $\underline{TF}$`

```

2355 \prg_new_conditional:Nnn \token_if_letter:N {p,TF,T,F} {
2356   \if_catcode:w \exp_not:N #1\c_letter_token
2357   \prg_return_true: \else: \prg_return_false: \fi:
2358 }

```

`\token_if_other_char_p:N` Check if token is an other char token. We use the constant `\c_other_char_token` for  
`\token_if_other_char:N $\underline{TF}$`  this.

```

2359 \prg_new_conditional:Nnn \token_if_other_char:N {p,TF,T,F} {
2360   \if_catcode:w \exp_not:N #1\c_other_char_token
2361   \prg_return_true: \else: \prg_return_false: \fi:
2362 }

```

`\token_if_active_char_p:N` Check if token is an active char token. We use the constant `\c_active_char_token` for  
`\token_if_active_char:N $\underline{TF}$`  this.

```

2363 \prg_new_conditional:Nnn \token_if_active_char:N {p,TF,T,F} {
2364   \if_catcode:w \exp_not:N #1\c_active_char_token
2365   \prg_return_true: \else: \prg_return_false: \fi:
2366 }

```

`\token_if_eq_meaning_p:NN` Check if the tokens #1 and #2 have same meaning.

`\token_if_eq_meaning:NNTF`

```

2367 \prg_new_conditional:Nnn \token_if_eq_meaning:NN {p,TF,T,F} {
2368   \if_meaning:w #1 #2
2369   \prg_return_true: \else: \prg_return_false: \fi:
2370 }

```

`\token_if_eq_catcode_p:NN` Check if the tokens #1 and #2 have same category code.

`\token_if_eq_catcode:NNTF`

```

2371 \prg_new_conditional:Nnn \token_if_eq_catcode:NN {p,TF,T,F} {
2372   \if_catcode:w \exp_not:N #1 \exp_not:N #2
2373   \prg_return_true: \else: \prg_return_false: \fi:
2374 }

```

`\token_if_eq_charcode_p:NN` Check if the tokens #1 and #2 have same character code.

`\token_if_eq_charcode:NNTF`

```

2375 \prg_new_conditional:Nnn \token_if_eq_charcode:NN {p,TF,T,F} {
2376   \if_charcode:w \exp_not:N #1 \exp_not:N #2
2377   \prg_return_true: \else: \prg_return_false: \fi:
2378 }

```

`\token_if_macro_p:N` When a token is a macro, `\token_to_meaning:N` will always output something like  
`\token_if_macro:N` `\long macro:#1->#1` so we simply check to see if the meaning contains `->`. Argument  
`\token_if_macro_p_aux:w` #2 in the code below will be empty if the string `->` isn't present, proof that the token was  
not a macro (which is why we reverse the emptiness test). However this function will fail  
on its own auxiliary function (and a few other private functions as well) but that should  
certainly never be a problem!

```

2379 \prg_new_conditional:Nnn \token_if_macro:N {p,TF,T,F} {
2380   \exp_after:wN \token_if_macro_p_aux:w \token_to_meaning:N #1 -> \q_nil
2381 }
2382 \cs_new_nopar:Npn \token_if_macro_p_aux:w #1 -> #2 \q_nil{
2383   \if_predicate:w \tl_if_empty_p:n{#2}
2384   \prg_return_false: \else: \prg_return_true: \fi:
2385 }

```

`\token_if_cs_p:N` Check if token has same catcode as a control sequence. We use `\scan_stop:` for this.

`\token_if_cs:NTF`

```

2386 \prg_new_conditional:Nnn \token_if_cs:N {p,TF,T,F} {
2387   \if_predicate:w \token_if_eq_catcode_p:NN \scan_stop: #1
2388   \prg_return_true: \else: \prg_return_false: \fi:}

```

`\token_if_expandable_p:N` Check if token is expandable. We use the fact that TeX will temporarily convert  
`\token_if_expandable:NTF` `\exp_not:N <token>` into `\scan_stop:` if `<token>` is expandable.

```

2389 \prg_new_conditional:Nnn \token_if_expandable:N {p,TF,T,F} {
2390   \cs_if_exist:NTF #1 {
2391     \exp_after:wN \if_meaning:w \exp_not:N #1 #1
2392     \prg_return_false: \else: \prg_return_true: \fi:

```

```

2393 } {
2394   \prg_return_false:
2395 }
2396 }

```

Most of these functions have to check the meaning of the token in question so we need to do some checkups on which characters are output by `\token_to_meaning:N`. As usual, these characters have catcode 12 so we must do some serious substitutions in the code below...

```

2397 \group_begin:
2398   \char_set_lccode:nn {'\T}{'\T}
2399   \char_set_lccode:nn {'\F}{'\F}
2400   \char_set_lccode:nn {'\X}{'\n}
2401   \char_set_lccode:nn {'\Y}{'\t}
2402   \char_set_lccode:nn {'\Z}{'\d}
2403   \char_set_lccode:nn {'\?}{'\}
2404   \tl_map_inline:nn{\X\Y\Z\M\C\H\A\R\O\U\S\K\I\P\L\G\P\E}
2405     {\char_set_catcode:nn {'#1}{12}}
\token_if_chardef_p:N
\token_if_mathchardef_p:N
\token_if_int_register_p:N
\token_if_skip_register_p:N
\token_if_dim_register_p:N
\token_if_toks_register_p:N
\token_if_protected_macro_p:N
\token_if_long_macro_p:N
\token_if_protected_long_macro_p:N
\token_if_chardef:NTF
\token_if_mathchardef:NTF
\token_if_long_macro:NTF
\token_if_protected_macro:NTF
\token_if_protected_long_macro:NTF
\token_if_dim_register:NTF
\token_if_skip_register:NTF
\token_if_int_register:NTF
\token_if_toks_register:NTF
\token_if_chardef_p_aux:w
\token_if_mathchardef_p_aux:w
\token_if_int_register_p_aux:w
\token_if_skip_register_p_aux:w
\token_if_dim_register_p_aux:w
\token_if_toks_register_p_aux:w
\token_if_protected_macro_p_aux:w
\token_if_long_macro_p_aux:w
\token_if_protected_long_macro_p_aux:w

```

We convert the token list to lowercase and restore the catcode and lowercase code changes.

```

2406 \tl_to_lowercase:n{
2407   \group_end:

```

First up is checking if something has been defined with `\tex_chardef:D` or `\tex_mathchardef:D`. This is easy since TeX thinks of such tokens as hexadecimal so it stores them as `\char"⟨hex number⟩` or `\mathchar"⟨hex number⟩`.

```

2408 \prg_new_conditional:Nnn \token_if_chardef:N {p,TF,T,F} {
2409   \exp_after:wN \token_if_chardef_aux:w
2410   \token_to_meaning:N #1?CHAR"q_nil
2411 }
2412 \cs_new_nopar:Npn \token_if_chardef_aux:w #1?CHAR"#2q_nil{
2413   \tl_if_empty:nTF {#1} {\prg_return_true:} {\prg_return_false:}
2414 }

2415 \prg_new_conditional:Nnn \token_if_mathchardef:N {p,TF,T,F} {
2416   \exp_after:wN \token_if_mathchardef_aux:w
2417   \token_to_meaning:N #1?MAYHCHAR"q_nil
2418 }
2419 \cs_new_nopar:Npn \token_if_mathchardef_aux:w #1?MAYHCHAR"#2q_nil{
2420   \tl_if_empty:nTF {#1} {\prg_return_true:} {\prg_return_false:}
2421 }

```

Integer registers are a little more difficult since they expand to `\count⟨number⟩` and there is also a primitive `\countdef`. So we have to check for that primitive as well.

```

2422 \prg_new_conditional:Nnn \token_if_int_register:N {p,TF,T,F} {
2423   \if_meaning:w \tex_countdef:D #1

```



```

2424 \prg_return_false:
2425 \else:
2426 \exp_after:wN \token_if_int_register_aux:w
2427 \token_to_meaning:N #1?COUXY\q_nil
2428 \fi:
2429 }
2430 \cs_new_nopar:Npn \token_if_int_register_aux:w #1?COUXY#2\q_nil{
2431 \tl_if_empty:nTF {#1} {\prg_return_true:} {\prg_return_false:}
2432 }

```

Skip registers are done the same way as the integer registers.

```

2433 \prg_new_conditional:Nnn \token_if_skip_register:N {p,TF,T,F} {
2434 \if_meaning:w \tex_skipdef:D #1
2435 \prg_return_false:
2436 \else:
2437 \exp_after:wN \token_if_skip_register_aux:w
2438 \token_to_meaning:N #1?SKIP\q_nil
2439 \fi:
2440 }
2441 \cs_new_nopar:Npn \token_if_skip_register_aux:w #1?SKIP#2\q_nil{
2442 \tl_if_empty:nTF {#1} {\prg_return_true:} {\prg_return_false:}
2443 }

```

Dim registers. No news here

```

2444 \prg_new_conditional:Nnn \token_if_dim_register:N {p,TF,T,F} {
2445 \if_meaning:w \tex_dimendef:D #1
2446 \c_false_bool
2447 \else:
2448 \exp_after:wN \token_if_dim_register_aux:w
2449 \token_to_meaning:N #1?ZIMEX\q_nil
2450 \fi:
2451 }
2452 \cs_new_nopar:Npn \token_if_dim_register_aux:w #1?ZIMEX#2\q_nil{
2453 \tl_if_empty:nTF {#1} {\prg_return_true:} {\prg_return_false:}
2454 }

```

Toks registers.

```

2455 \prg_new_conditional:Nnn \token_if_toks_register:N {p,TF,T,F} {
2456 \if_meaning:w \tex_toksdef:D #1
2457 \prg_return_false:
2458 \else:
2459 \exp_after:wN \token_if_toks_register_aux:w
2460 \token_to_meaning:N #1?YOKS\q_nil
2461 \fi:
2462 }
2463 \cs_new_nopar:Npn \token_if_toks_register_aux:w #1?YOKS#2\q_nil{
2464 \tl_if_empty:nTF {#1} {\prg_return_true:} {\prg_return_false:}
2465 }

```

Protected macros.

```

2466 \prg_new_conditional:Nnn \token_if_protected_macro:N {p,TF,T,F} {
2467   \exp_after:wN \token_if_protected_macro_aux:w
2468   \token_to_meaning:N #1?PROYECYEEZ~MACRO\q_nil
2469 }
2470 \cs_new_nopar:Npn \token_if_protected_macro_aux:w #1?PROYECYEEZ~MACRO#2\q_nil{
2471   \tl_if_empty:nTF {#1} {\prg_return_true:} {\prg_return_false:}
2472 }

```

Long macros.

```

2473 \prg_new_conditional:Nnn \token_if_long_macro:N {p,TF,T,F} {
2474   \exp_after:wN \token_if_long_macro_aux:w
2475   \token_to_meaning:N #1?LOXG~MACRO\q_nil
2476 }
2477 \cs_new_nopar:Npn \token_if_long_macro_aux:w #1?LOXG~MACRO#2\q_nil{
2478   \tl_if_empty:nTF {#1} {\prg_return_true:} {\prg_return_false:}
2479 }

```

Finally protected long macros where we for once don't have to add an extra test since there is no primitive for the combined prefixes.

```

2480 \prg_new_conditional:Nnn \token_if_protected_long_macro:N {p,TF,T,F} {
2481   \exp_after:wN \token_if_protected_long_macro_aux:w
2482   \token_to_meaning:N #1?PROYECYEEZ?LOXG~MACRO\q_nil
2483 }
2484 \cs_new_nopar:Npn \token_if_protected_long_macro_aux:w #1
2485   ?PROYECYEEZ?LOXG~MACRO#2\q_nil{
2486   \tl_if_empty:nTF {#1} {\prg_return_true:} {\prg_return_false:}
2487 }

```

Finally the `\tl_to_lowercase:n` ends!

```

2488 }

```

We do not provide a function for testing if a control sequence is “outer” since we don't use that in L<sup>A</sup>T<sub>E</sub>X3.

```

\et_prefix_arg_replacement_aux:w
\token_get_prefix_spec:N
\token_get_arg_spec:N
\token_get_replacement_spec:N

```

In the `xparse` package we sometimes want to test if a control sequence can be expanded to reveal a hidden value. However, we cannot just expand the macro blindly as it may have arguments and none might be present. Therefore we define these functions to pick either the prefix(es), the argument specification, or the replacement text from a macro. All of this information is returned as characters with catcode 12. If the token in question isn't a macro, the token `\scan_stop:` is returned instead.

```

2489 \group_begin:
2490 \char_set_lccode:nn {'\?}{'\:}
2491 \char_set_catcode:nn{'\M}{12}
2492 \char_set_catcode:nn{'\A}{12}

```

```

2493 \char_set_catcode:nn{'\C}{12}
2494 \char_set_catcode:nn{'\R}{12}
2495 \char_set_catcode:nn{'\O}{12}
2496 \tl_to_lowercase:n{
2497   \group_end:
2498   \cs_new_nopar:Npn \token_get_prefix_arg_replacement_aux:w #1MACRO?#2->#3\q_nil#4{
2499     #4{#1}{#2}{#3}
2500   }
2501   \cs_new_nopar:Npn \token_get_prefix_spec:N #1{
2502     \token_if_macro:NTF #1{
2503       \exp_after:wN \token_get_prefix_arg_replacement_aux:w
2504       \token_to_meaning:N #1\q_nil\use_i:nnn
2505     }{\scan_stop:}
2506   }
2507   \cs_new_nopar:Npn \token_get_arg_spec:N #1{
2508     \token_if_macro:NTF #1{
2509       \exp_after:wN \token_get_prefix_arg_replacement_aux:w
2510       \token_to_meaning:N #1\q_nil\use_ii:nnn
2511     }{\scan_stop:}
2512   }
2513   \cs_new_nopar:Npn \token_get_replacement_spec:N #1{
2514     \token_if_macro:NTF #1{
2515       \exp_after:wN \token_get_prefix_arg_replacement_aux:w
2516       \token_to_meaning:N #1\q_nil\use_iii:nnn
2517     }{\scan_stop:}
2518   }
2519 }

```

Useless code: because we can!

<pre> \token_if_primitive_p:N \token_if_primitive_p_aux:N \token_if_primitive:NTF </pre>	<p>It is rather hard to determine if a token is a primitive. First we can check if it is a control sequence or active character. If either, we check if it is a macro. Then we can go through a tedious process of testing for different register types... I don't actually think this function is useful but you never know.</p>
--	---

```

2520 \prg_new_conditional:Nnn \token_if_primitive:N {p,TF,T,F} {
2521   \if_predicate:w \token_if_cs_p:N #1
2522   \if_predicate:w \token_if_macro_p:N #1
2523     \prg_return_false:
2524   \else:
2525     \token_if_primitive_p_aux:N #1
2526   \fi:
2527 \else:
2528   \if_predicate:w \token_if_active_char_p:N #1
2529   \if_predicate:w \token_if_macro_p:N #1
2530     \prg_return_false:
2531   \else:
2532     \token_if_primitive_p_aux:N #1
2533   \fi:

```

```

2534     \else:
2535         \prg_return_false:
2536     \fi:
2537 \fi:
2538 }
2539 \cs_new_nopar:Npn \token_if_primitive_p_aux:N #1{
2540     \if_predicate:w \token_if_chardef_p:N #1 \c_false_bool
2541     \else:
2542         \if_predicate:w \token_if_mathchardef_p:N #1 \prg_return_false:
2543     \else:
2544         \if_predicate:w \token_if_int_register_p:N #1 \prg_return_false:
2545     \else:
2546         \if_predicate:w \token_if_skip_register_p:N #1 \prg_return_false:
2547     \else:
2548         \if_predicate:w \token_if_dim_register_p:N #1 \prg_return_false:
2549     \else:
2550         \if_predicate:w \token_if_toks_register_p:N #1 \prg_return_false:
2551     \else:

```

We made it!

```

2552         \prg_return_true:
2553     \fi:
2554 \fi:
2555 \fi:
2556 \fi:
2557 \fi:
2558 \fi:
2559 }

```

## 99.5 Peeking ahead at the next token

```

\l_peek_token
\g_peek_token
\l_peek_search_token

```

We define some other tokens which will initially be the character ?.

```

2560 \token_new:Nn \l_peek_token {?}
2561 \token_new:Nn \g_peek_token {?}
2562 \token_new:Nn \l_peek_search_token {?}

```

`\peek_after:NN` `\peek_gafter:NN` takes two argument where the first is a function acting on `\l_peek_token` and the second is the next token in the input stream which `\l_peek_token` is set equal to. `\peek_gafter:NN` does the same globally to `\g_peek_token`.

```

2563 \cs_new_nopar:Npn \peek_after:NN {\tex_futurelet:D \l_peek_token }
2564 \cs_new_nopar:Npn \peek_gafter:NN {
2565     \pref_global:D \tex_futurelet:D \g_peek_token
2566 }

```

For normal purposes there are four main cases:

1. peek at the next token.
2. peek at the next non-space token.
3. peek at the next token and remove it.
4. peek at the next non-space token and remove it.

The generic functions will take four arguments: The token to search for, the test function to run on it and the true/false cases. The general algorithm is this:

1. Store the token to search for in `\l_peek_search_token`.
2. In order to avoid doubling of hash marks where it seems unnatural we put the `\true` and `\false` cases through an `x` type expansion but using `\exp_not:n` to avoid any expansion. This has the same effect as putting it through a `\toks` register but is faster. Also put in a special alignment safe group end.
3. Put in an alignment safe group begin.
4. Peek ahead and call the function which will act on the next token in the input stream.

`\l_peek_true_tl` Two dedicated token list variables that store the true and false cases.  
`\l_peek_false_tl`

```

2567 \tl_new:Nn \l_peek_true_tl {}
2568 \tl_new:Nn \l_peek_false_tl {}

```

`\peek_tmp:w` Scratch function used for storing the token to be removed if found.

```

2569 \cs_new_nopar:Npn \peek_tmp:w {}

```

`\l_peek_search_tl` We also use this token list variable for storing the token we want to compare. This turns out to be useful.

```

2570 \tl_new:Nn \l_peek_search_tl {}

```

`\peek_token_generic:NNTF` #1 : the function to execute (obey or ignore spaces, etc.),  
#2 : the special token we're looking for.

```

2571 \cs_new:Npn \peek_token_generic:NNTF #1#2#3#4 {
2572   \cs_set_eq:NN \l_peek_search_token #2
2573   \tl_set:Nn \l_peek_search_tl {#2}
2574   \tl_set:Nx \l_peek_true_tl {\exp_not:n{\group_align_safe_end: #3}}
2575   \tl_set:Nx \l_peek_false_tl {\exp_not:n{\group_align_safe_end: #4}}
2576   \group_align_safe_begin:
2577     \peek_after:NN #1
2578 }
2579 \cs_new:Npn \peek_token_generic:NNT #1#2#3 {

```

```

2580 \peek_token_generic:NNTF #1#2 {#3} {}
2581 }
2582 \cs_new:Npn \peek_token_generic:NNF #1#2#3 {
2583 \peek_token_generic:NNTF #1#2 {} {#3}
2584 }

```

`\peek_token_remove_generic:NNTF` If we want to be able to remove any character from the input stream we might as well do it the same way for all characters so we define this as little differently from above.

```

2585 \cs_new:Npn \peek_token_remove_generic:NNTF #1#2#3#4 {
2586 \cs_set_eq:NN \l_peek_search_token #2
2587 \tl_set:Nn \l_peek_search_tl {#2}
2588 \tl_set:Nx \l_peek_true_aux_tl { \exp_not:n{ #3 } }
2589 \tl_set_eq:NN \l_peek_true_tl \c_peek_true_remove_next_tl
2590 \tl_set:Nx \l_peek_false_tl { \exp_not:n{ \group_align_safe_end: #4 } }
2591 \group_align_safe_begin:
2592 \peek_after:NN #1
2593 }
2594 \cs_new:Npn \peek_token_remove_generic:NNT #1#2#3 {
2595 \peek_token_remove_generic:NNTF #1#2 {#3} {}
2596 }
2597 \cs_new:Npn \peek_token_remove_generic:NNF #1#2#3 {
2598 \peek_token_remove_generic:NNTF #1#2 {} {#3}
2599 }

```

`\l_peek_true_aux_tl`  
`\c_peek_true_remove_next_tl`

Two token list variables to help with removing the character from the input stream.

```

2600 \tl_new:Nn \l_peek_true_aux_tl {}
2601 \tl_new:Nn \c_peek_true_remove_next_tl { \group_align_safe_end:
2602 \tex_afterassignment:D \l_peek_true_aux_tl \cs_set_eq:NN \peek_tmp:w
2603 }

```

`\peek_execute_branches_meaning:` There are three major tests between tokens in TeX: meaning, catcode and charcode.  
`\peek_execute_branches_catcode:` Hence we define three basic test functions that set in after the ignoring phase is over and  
`\peek_execute_branches_charcode:` done with.  
`\execute_branches_charcode_aux:NN`

```

2604 \cs_new_nopar:Npn \peek_execute_branches_meaning: {
2605 \if_meaning:w \l_peek_token \l_peek_search_token
2606 \exp_after:wN \l_peek_true_tl
2607 \else:
2608 \exp_after:wN \l_peek_false_tl
2609 \fi:
2610 }
2611 \cs_new_nopar:Npn \peek_execute_branches_catcode: {
2612 \if_catcode:w \exp_not:N \l_peek_token \exp_not:N \l_peek_search_token
2613 \exp_after:wN \l_peek_true_tl
2614 \else:
2615 \exp_after:wN \l_peek_false_tl
2616 \fi:
2617 }

```

For the charcode version we do things a little differently. We want to check the token directly but if we do this we face problems if the next thing in the input stream is a braced group or a space token. The braced group would be read as a complete argument and the space would be gobbled by T<sub>E</sub>X's argument reading routines. Hence we test for both of these and if one of them is found we just execute the false result directly since no one should ever try to use the `charcode` function for searching for `\c_group_begin_token` or `\c_space_token`. The same is true for `\c_group_end_token`, as this can only occur if the function is at the end of a group.

```

2618 \cs_new_nopar:Npn \peek_execute_branches_charcode: {
2619   \bool_if:nTF {
2620     \token_if_eq_catcode_p:NN \l_peek_token \c_group_begin_token ||
2621     \token_if_eq_catcode_p:NN \l_peek_token \c_group_end_token ||
2622     \token_if_eq_meaning_p:NN \l_peek_token \c_space_token
2623   }
2624   { \l_peek_false_tl }

```

Otherwise we call a small auxiliary function that just grabs the next token. We can do that because it really is a single token; we just have insert it again afterwards. Also we stored the token we were looking for in the token list variable `\l_peek_search_tl` so we unpack it again for this function.

```

2625   { \exp_after:wN \peek_execute_branches_charcode_aux:NN \l_peek_search_tl }
2626 }

```

Then we just do the usual `\if_charcode:w` comparison. We also remember to insert `#2` again after executing the true or false branches.

```

2627 \cs_new:Npn \peek_execute_branches_charcode_aux:NN #1#2{
2628   \if_charcode:w \exp_not:N #1\exp_not:N#2
2629     \exp_after:wN \l_peek_true_tl
2630   \else:
2631     \exp_after:wN \l_peek_false_tl
2632   \fi:
2633   #2
2634 }

```

`\peek_def_aux:nnnn`  
`\peek_def_aux_ii:nnnnn`

This function aids defining conditional variants without too much repeated code. I hope that it doesn't detract too much from the readability.

```

2635 \cs_new_nopar:Npn \peek_def_aux:nnnn #1#2#3#4 {
2636   \peek_def_aux_ii:nnnnn {#1} {#2} {#3} {#4} { TF }
2637   \peek_def_aux_ii:nnnnn {#1} {#2} {#3} {#4} { T }
2638   \peek_def_aux_ii:nnnnn {#1} {#2} {#3} {#4} { F }
2639 }
2640 \cs_new_nopar:Npn \peek_def_aux_ii:nnnnn #1#2#3#4#5 {
2641   \cs_new_nopar:cpx { #1 #5 } {
2642     \tl_if_empty:nF {#2} {
2643       \exp_not:n { \cs_set_eq:NN \peek_execute_branches: #2 }

```

```

2644     }
2645     \exp_not:c { #3 #5 }
2646     \exp_not:n { #4 }
2647   }
2648 }

```

\peek\_meaning:NTF Here we use meaning comparison with \if\_meaning:w.

```

2649 \peek_def_aux:nnnn
2650 { peek_meaning:N }
2651 {}
2652 { peek_token_generic:NN }
2653 { \peek_execute_branches_meaning: }

```

\peek\_meaning\_ignore\_spaces:NTF

```

2654 \peek_def_aux:nnnn
2655 { peek_meaning_ignore_spaces:N }
2656 { \peek_execute_branches_meaning: }
2657 { peek_token_generic:NN }
2658 { \peek_ignore_spaces_execute_branches: }

```

\peek\_meaning\_remove:NTF

```

2659 \peek_def_aux:nnnn
2660 { peek_meaning_remove:N }
2661 {}
2662 { peek_token_remove_generic:NN }
2663 { \peek_execute_branches_meaning: }

```

eaning\_remove\_ignore\_spaces:NTF

```

2664 \peek_def_aux:nnnn
2665 { peek_meaning_remove_ignore_spaces:N }
2666 { \peek_execute_branches_meaning: }
2667 { peek_token_remove_generic:NN }
2668 { \peek_ignore_spaces_execute_branches: }

```

\peek\_catcode:NTF Here we use catcode comparison with \if\_catcode:w.

```

2669 \peek_def_aux:nnnn
2670 { peek_catcode:N }
2671 {}
2672 { peek_token_generic:NN }
2673 { \peek_execute_branches_catcode: }

```

\peek\_catcode\_ignore\_spaces:NTF

```

2674 \peek_def_aux:nnnn

```



```

2675 { peek_catcode_ignore_spaces:N }
2676 { \peek_execute_branches_catcode: }
2677 { peek_token_generic:NN }
2678 { \peek_ignore_spaces_execute_branches: }

```

\peek\_catcode\_remove:N $\underline{TF}$

```

2679 \peek_def_aux:nnnn
2680 { peek_catcode_remove:N }
2681 {}
2682 { peek_token_remove_generic:NN }
2683 { \peek_execute_branches_catcode: }

```

atcode\_remove\_ignore\_spaces:N $\underline{TF}$

```

2684 \peek_def_aux:nnnn
2685 { peek_catcode_remove_ignore_spaces:N }
2686 { \peek_execute_branches_catcode: }
2687 { peek_token_remove_generic:NN }
2688 { \peek_ignore_spaces_execute_branches: }

```

\peek\_charcode:N $\underline{TF}$  Here we use charcode comparison with \if\_charcode:w.

```

2689 \peek_def_aux:nnnn
2690 { peek_charcode:N }
2691 {}
2692 { peek_token_generic:NN }
2693 { \peek_execute_branches_charcode: }

```

peek\_charcode\_ignore\_spaces:N $\underline{TF}$

```

2694 \peek_def_aux:nnnn
2695 { peek_charcode_ignore_spaces:N }
2696 { \peek_execute_branches_charcode: }
2697 { peek_token_generic:NN }
2698 { \peek_ignore_spaces_execute_branches: }

```

\peek\_charcode\_remove:N $\underline{TF}$

```

2699 \peek_def_aux:nnnn
2700 { peek_charcode_remove:N }
2701 {}
2702 { peek_token_remove_generic:NN }
2703 { \peek_execute_branches_charcode: }

```

arcode\_remove\_ignore\_spaces:N $\underline{TF}$

```

2704 \peek_def_aux:nnnn
2705 { peek_charcode_remove_ignore_spaces:N }

```

```

2706 { \peek_execute_branches_charcode: }
2707 { peek_token_remove_generic:NN }
2708 { \peek_ignore_spaces_execute_branches:}

```

`\peek_ignore_spaces_aux:` Throw away a space token and search again. We could define this in a more devious way where the auxiliary function gobbles the space token but then what do we do if we decide that a certain function should ignore more than one specific token? For example someone might find it interesting to define a `\peek_` function that ignores `a`'s and `b`'s! Or maybe different kinds of “funny spaces”... Therefore I have decided to use this version which uses `\tex_afterassignment:D` to call the auxiliary function after the next token has been removed by `\cs_set_eq:NN`. That way it is easily extensible.

```

2709 \cs_new_nopar:Npn \peek_ignore_spaces_aux: {
2710   \peek_after:NN \peek_ignore_spaces_execute_branches:
2711 }
2712 \cs_new_nopar:Npn \peek_ignore_spaces_execute_branches: {
2713   \token_if_eq_meaning:NNTF \l_peek_token \c_space_token
2714   { \tex_afterassignment:D \peek_ignore_spaces_aux:
2715     \cs_set_eq:NN \peek_tmp:w
2716   }
2717   \peek_execute_branches:
2718 }

2719 </initex | package>

2720 <*showmemory>
2721 \showMemUsage
2722 </showmemory>

```

## 100 l3int implementation

### 100.1 Internal functions and variables

`\int_advance:w` `\int_advance:w` *<int register>* *<optional ‘by’>* *<number>* *<space>*  
 Increments the count register by the specified amount.

**T<sub>E</sub>Xhackers note:** This is T<sub>E</sub>X’s `\advance`.

`\int_convert_number_to_letter:n *` `\int_convert_number_to_letter:n` *{<integer expression>}*

Internal function for turning a number for a different base into a letter or digit.

<code>\int_pre_eval_one_arg:Nn</code> <code>\int_pre_eval_two_args:Nnn</code>	<code>\int_pre_eval_one_arg:Nn &lt;function&gt; {\langle integer expression \rangle}</code> <code>\int_pre_eval_one_arg:Nnn &lt;function&gt; {\langle int expr_1 \rangle}</code> <code>{\langle int expr_2 \rangle}</code>
--	--

These are expansion helpers; they evaluate their integer expressions before handing them off to the specified *<function>*.

<code>\int_get_sign_and_digits:n *</code> <code>\int_get_sign:n *</code> <code>\int_get_digits:n *</code>	<code>\int_get_sign_and_digits:n {\langle number \rangle}</code>
---	--

From an argument that may or may not include a + or - sign, these functions expand to the respective components of the number.

## 100.2 Module loading and primitives definitions

We start by ensuring that the required packages are loaded.

```

2723 <*package>
2724 \ProvidesExplPackage
2725   {\filename}{\filedate}{\fileversion}{\filedescription}
2726 \package_check_loaded_expl:
2727 </package>
2728 <*initex | package>

```

<code>\int_to_roman:w</code> <code>\int_to_number:w</code> <code>\int_advance:w</code>	A new name for the primitives.  <pre> 2729 \cs_new_eq:NN \int_to_roman:w \tex_romannumeral:D 2730 \cs_new_eq:NN \int_to_number:w \tex_number:D 2731 \cs_new_eq:NN \int_advance:w \tex_advance:D </pre>
--	--

Functions that support L<sup>A</sup>T<sub>E</sub>X's user accessible counters should be added here, too. But first the internal counters.

## 100.3 Allocation and setting

<code>\int_new:N</code> <code>\int_new:c</code>	Allocation of a new internal counter is already done above. Here we define the next likely variant.
--	---

For the L<sup>A</sup>T<sub>E</sub>X3 format:

```

2732 <*initex>
2733 \alloc_setup_type:nnn {int} {11} \c_max_register_num
2734 \cs_new_nopar:Npn \int_new:N #1 {\alloc_reg:NnNN g {int} \tex_countdef:D#1}
2735 \cs_new_nopar:Npn \int_new_l:N #1 {\alloc_reg:NnNN l {int} \tex_countdef:D#1}
2736 </initex>

```

For ‘l3in2e’:

```

2737 <*package>
2738 \cs_new_nopar:Npn \int_new:N #1 {
2739   \chk_if_free_cs:N #1
2740   \newcount #1
2741 }
2742 </package>

2743 \cs_generate_variant:Nn \int_new:N {c}

```

\int\_set:Nn Setting counters is again something that I would like to make uniform at the moment to get a better overview.

```

\int_set:cn
\int_gset:Nn
\int_gset:cn
2744 \cs_new_nopar:Npn \int_set:Nn #1#2{#1 \intexpr_eval:w #2\intexpr_eval_end:
2745 <*check>
2746 \chk_local_or_pref_global:N #1
2747 </check>
2748 }
2749 \cs_new_nopar:Npn \int_gset:Nn {
2750 <*check>
2751   \pref_global_chk:
2752 </check>
2753 <-check> \pref_global:D
2754   \int_set:Nn }
2755 \cs_generate_variant:Nn\int_set:Nn {cn}
2756 \cs_generate_variant:Nn\int_gset:Nn {cn}

```

\int\_incr:N Incrementing and decrementing of integer registers is done with the following functions.

```

\int_decr:N
\int_gincr:N
\int_gdecr:N
\int_incr:c
\int_decr:c
\int_gincr:c
\int_gdecr:c
2757 \cs_new_nopar:Npn \int_incr:N #1{\int_advance:w#1\c_one
2758 <*check>
2759   \chk_local_or_pref_global:N #1
2760 </check>
2761 }
2762 \cs_new_nopar:Npn \int_decr:N #1{\int_advance:w#1\c_minus_one
2763 <*check>
2764   \chk_local_or_pref_global:N #1
2765 </check>
2766 }
2767 \cs_new_nopar:Npn \int_gincr:N {

```

We make sure that a local variable is not updated globally by changing the internal test (i.e. \chk\_local\_or\_pref\_global:N) before making the assignment. This is done by \pref\_global\_chk: which also issues the necessary \pref\_global:D. This is not very efficient, but this code will be only included for debugging purposes. Using \pref\_global:D in front of the local function is better in the production versions.

```

2768 <*check>
2769   \pref_global_chk:

```

```

2770 </check>
2771 <-check> \pref_global:D
2772         \int_incr:N}
2773 \cs_new_nopar:Npn \int_gdecr:N {
2774 <*check>
2775         \pref_global_chk:
2776 </check>
2777 <-check> \pref_global:D
2778         \int_decr:N}

```

With the `\int_add:Nn` functions we can shorten the above code. If this makes it too slow ...

```

2779 \cs_set_nopar:Npn \int_incr:N #1{\int_add:Nn#1\c_one}
2780 \cs_set_nopar:Npn \int_decr:N #1{\int_add:Nn#1\c_minus_one}
2781 \cs_set_nopar:Npn \int_gincr:N #1{\int_gadd:Nn#1\c_one}
2782 \cs_set_nopar:Npn \int_gdecr:N #1{\int_gadd:Nn#1\c_minus_one}

2783 \cs_generate_variant:Nn \int_incr:N {c}
2784 \cs_generate_variant:Nn \int_decr:N {c}
2785 \cs_generate_variant:Nn \int_gincr:N {c}
2786 \cs_generate_variant:Nn \int_gdecr:N {c}

```

`\int_zero:N` Functions that reset an `<int>` register to zero.

```

\int_zero:c
\int_gzero:N
\int_gzero:c
2787 \cs_new_nopar:Npn \int_zero:N #1 {#1=\c_zero}
2788 \cs_generate_variant:Nn \int_zero:N {c}

2789 \cs_new_nopar:Npn \int_gzero:N #1 {\pref_global:D #1=\c_zero}
2790 \cs_generate_variant:Nn \int_gzero:N {c}

```

`\int_add:Nn` Adding and subtracting to and from a counter ... We should think of using these functions

```

\int_add:cn
\int_gadd:Nn
\int_gadd:cn
2791 \cs_new_nopar:Npn \int_add:Nn #1#2{

```

`\int_sub:Nn` We need to say by in case the first argument is a register accessed by its number, e.g., `\count23`. Not that it should ever happen but...

```

\int_sub:cn
\int_gsub:Nn
\int_gsub:cn
2792         \int_advance:w #1 by \intexpr_eval:w #2\intexpr_eval_end:
2793 <*check>
2794         \chk_local_or_pref_global:N #1
2795 </check>
2796 }
2797 \cs_new_nopar:Npn \int_sub:Nn #1#2{
2798         \int_advance:w #1-\intexpr_eval:w #2\intexpr_eval_end:
2799 <*check>
2800         \chk_local_or_pref_global:N #1
2801 </check>
2802 }

```

```

2803 \cs_new_nopar:Npn \int_gadd:Nn {
2804   \*check
2805   \pref_global_chk:
2806   \*check
2807   \<-check \pref_global:D
2808   \int_add:Nn }
2809 \cs_new_nopar:Npn \int_gsub:Nn {
2810   \*check
2811   \pref_global_chk:
2812   \*check
2813   \<-check \pref_global:D
2814   \int_sub:Nn }
2815 \cs_generate_variant:Nn \int_add:Nn {cn}
2816 \cs_generate_variant:Nn \int_gadd:Nn {cn}
2817 \cs_generate_variant:Nn \int_sub:Nn {cn}
2818 \cs_generate_variant:Nn \int_gsub:Nn {cn}

```

`\int_use:N` Here is how counters are accessed:

```

\int_use:c
2819 \cs_new_eq:NN \int_use:N \tex_the:D
2820 \cs_new_nopar:Npn \int_use:c #1{\int_use:N \cs:w#1\cs_end:}

```

`\int_show:N` Diagnostics.

```

\int_show:c
2821 \cs_new_eq:NN \int_show:N \tex_showthe:D
2822 \cs_new_nopar:Npn \int_show:c {\exp_args:Nc \int_show:N }

```

`\int_to_arabic:n` Nothing exciting here.

```

2823 \cs_new_nopar:Npn \int_to_arabic:n #1{ \intexpr_eval:n{#1}}

```

`\int_roman_lcuc_mapping:Nnn` Using TeX's built-in feature for producing roman numerals has some surprising features. One is the the characters resulting from `\int_to_roman:w` have category code 12 so they may fail in certain comparison tests. Therefore we use a mapping from the character TeX produces to the character we actually want which will give us letters with category code 11.

```

2824 \cs_new_nopar:Npn \int_roman_lcuc_mapping:Nnn #1#2#3{
2825   \cs_set_nopar:cpn {int_to_lc_roman_#1:}{#2}
2826   \cs_set_nopar:cpn {int_to_uc_roman_#1:}{#3}
2827 }

```

Here are the default mappings. I haven't found any examples of say Turkish doing the mapping `i \i I` but at least there is a possibility for it if needed. Note: I have now asked a Turkish person and he tells me they do the `i I` mapping.

```

2828 \int_roman_lcuc_mapping:Nnn i i I
2829 \int_roman_lcuc_mapping:Nnn v v V

```

```

2830 \int_roman_lcuc_mapping:Nnn x x X
2831 \int_roman_lcuc_mapping:Nnn l l L
2832 \int_roman_lcuc_mapping:Nnn c c C
2833 \int_roman_lcuc_mapping:Nnn d d D
2834 \int_roman_lcuc_mapping:Nnn m m M

```

For the delimiter we cheat and let it gobble its arguments instead.

```

2835 \int_roman_lcuc_mapping:Nnn Q \use_none:nn \use_none:nn

```

`\int_to_roman:n` The commands for producing the lower and upper case roman numerals run a loop on one character at a time and also carries some information for upper or lower case with `\int_to_Roman:n` it. We put it through `\intexpr_eval:n` first which is safer and more flexible.

```

2836 \cs_new_nopar:Npn \int_to_roman:n #1 {
2837   \exp_after:wN \int_roman_lcuc:NN \exp_after:wN l
2838   \int_to_roman:w \intexpr_eval:n {#1} Q
2839 }
2840 \cs_new_nopar:Npn \int_to_Roman:n #1 {
2841   \exp_after:wN \int_roman_lcuc:NN \exp_after:wN u
2842   \int_to_roman:w \intexpr_eval:n {#1} Q
2843 }
2844 \cs_new_nopar:Npn \int_to_roman_lcuc:NN #1#2{
2845   \use:c {int_to_#1c_roman_#2:}
2846   \int_to_roman_lcuc:NN #1
2847 }

```

`\int_convert_number_with_rule:nnN` This is our major workhorse for conversions. `#1` is the number we want converted, `#2` is the base number, and `#3` is the function converting the number. This function expects to receive a non-negative integer and as such is ideal for something using `\if_case:w` internally.

The basic example is this: We want to convert the number 50 (`#1`) into an alphabetic equivalent `ax`. For the English language our list contains 26 elements so this is our argument `#2` while the function `#3` just turns 1 into `a`, 2 into `b`, etc. Hence our goal is to turn 50 into the sequence `#3{1}#1{24}` so what we do is to first divide 50 by 26 and truncating the result returning 1. Then before we execute this we call the function again but this time on the result of the remainder of the division. This goes on until the remainder is less than or equal to the base number where we just call the function `#3` directly on the number.

We do a little pre-expansion of the arguments below as they otherwise have a tendency to grow quite large.

```

2848 \cs_set_nopar:Npn \int_convert_number_with_rule:nnN #1#2#3{
2849   \intexpr_compare:nNnTF {#1}>{#2}
2850   {
2851     \exp_args:Nf \int_convert_number_with_rule:nnN
2852     { \intexpr_div_truncate:nn {#1-1}{#2} }{#2}
2853     #3

```

Note that we have to nudge our modulus function so it won't return 0 as that wouldn't work with `\if_case:w` when that expects a positive number to produce a letter.

```

2854 \exp_args:Nf #3 { \intexpr_eval:n{1+\intexpr_mod:nn {#1-1}{#2}} }
2855 }
2856 { \exp_args:Nf #3{ \intexpr_eval:n{#1} } }
2857 }

```

As can be seen it is even simpler to convert to number systems that contain 0, since then we don't have to add or subtract 1 here and there.

`\alph_default_conversion_rule:n` Now we just set up a default conversion rule. Ideally every language should have one such rule, as say in Danish there are 29 letters in the alphabet.

```

2858 \cs_new_nopar:Npn \int_alph_default_conversion_rule:n #1{
2859   \if_case:w #1
2860     \or: a\or: b\or: c\or: d\or: e\or: f
2861     \or: g\or: h\or: i\or: j\or: k\or: l
2862     \or: m\or: n\or: o\or: p\or: q\or: r
2863     \or: s\or: t\or: u\or: v\or: w\or: x
2864     \or: y\or: z
2865   \fi:
2866 }
2867 \cs_new_nopar:Npn \int_Alph_default_conversion_rule:n #1{
2868   \if_case:w #1
2869     \or: A\or: B\or: C\or: D\or: E\or: F
2870     \or: G\or: H\or: I\or: J\or: K\or: L
2871     \or: M\or: N\or: O\or: P\or: Q\or: R
2872     \or: S\or: T\or: U\or: V\or: W\or: X
2873     \or: Y\or: Z
2874   \fi:
2875 }

```

`\int_to_alph:n` The actual functions are just instances of the generic function. The second argument of `\int_convert_number_with_rule:nnN` should of course match the number of `\or:s` in the conversion rule.

```

2876 \cs_new_nopar:Npn \int_to_alph:n #1{
2877   \int_convert_number_with_rule:nnN {#1}{26}
2878   \int_alph_default_conversion_rule:n
2879 }
2880 \cs_new_nopar:Npn \int_to_Alph:n #1{
2881   \int_convert_number_with_rule:nnN {#1}{26}
2882   \int_Alph_default_conversion_rule:n
2883 }

```

`\int_to_symbol:n` Turning a number into a symbol is also easy enough.

```

2884 \cs_new_nopar:Npn \int_to_symbol:n #1{

```



```

2885 \mode_if_math:TF
2886 {
2887   \int_convert_number_with_rule:nnN {#1}{9}
2888   \int_symbol_math_conversion_rule:n
2889 }
2890 {
2891   \int_convert_number_with_rule:nnN {#1}{9}
2892   \int_symbol_text_conversion_rule:n
2893 }
2894 }

```

$\int\_symbol\_math\_conversion\_rule:n$   
 $\int\_symbol\_text\_conversion\_rule:n$

Nothing spectacular here.

```

2895 \cs_new_nopar:Npn \int_symbol_math_conversion_rule:n #1 {
2896   \if_case:w #1
2897     \or: *
2898     \or: \dagger
2899     \or: \ddagger
2900     \or: \mathsection
2901     \or: \mathparagraph
2902     \or: \l
2903     \or: **
2904     \or: \dagger\dagger
2905     \or: \ddagger\ddagger
2906   \fi:
2907 }
2908 \cs_new_nopar:Npn \int_symbol_text_conversion_rule:n #1 {
2909   \if_case:w #1
2910     \or: \textasteriskcentered
2911     \or: \textdagger
2912     \or: \textdaggerdbl
2913     \or: \textsection
2914     \or: \textparagraph
2915     \or: \textbardbl
2916     \or: \textasteriskcentered\textasteriskcentered
2917     \or: \textdagger\textdagger
2918     \or: \textdaggerdbl\textdaggerdbl
2919   \fi:
2920 }

```

$\l\_tmpa\_int$   
 $\l\_tmpb\_int$   
 $\l\_tmpc\_int$   
 $\g\_tmpa\_int$   
 $\g\_tmpb\_int$

We provide four local and two global scratch counters, maybe we need more or less.

```

2921 \int_new:N \l_tmpa_int
2922 \int_new:N \l_tmpb_int
2923 \int_new:N \l_tmpc_int
2924 \int_new:N \g_tmpa_int
2925 \int_new:N \g_tmpb_int

```

$\int\_pre\_eval\_one\_arg:Nn$   
 $\int\_pre\_eval\_two\_args:Nnn$

These are handy when handing down values to other functions. All they do is evaluate the number in advance.

```

2926 \cs_set_nopar:Npn \int_pre_eval_one_arg:Nn #1#2{
2927   \exp_args:Nf#1{\intexpr_eval:n{#2}}
2928 \cs_set_nopar:Npn \int_pre_eval_two_args:Nnn #1#2#3{
2929   \exp_args:Nff#1{\intexpr_eval:n{#2}}{\intexpr_eval:n{#3}}
2930 }

```

## 100.4 Defining constants

`\int_const:Nn` As stated, most constants can be defined as `\tex_chardef:D` or `\tex_mathchardef:D` but that's engine dependent.

```

2931 \cs_new_nopar:Npn \int_const:Nn #1#2 {
2932   \intexpr_compare:nNnTF {#2} > \c_minus_one {
2933     \intexpr_compare:nNnTF {#2} > \c_max_register_num {
2934       \int_new:N #1 \int_set:Nn #1{#2}
2935     } {
2936       \chk_if_free_cs:N #1 \tex_mathchardef:D #1 = \intexpr_eval:n{#2}
2937     }
2938   } {
2939     \int_new:N #1 \int_set:Nn #1{#2}
2940   }
2941 }

```

`\c_minus_one` And the usual constants, others are still missing. Please, make every constant a real constant at least for the moment. We can easily convert things in the end when we have found what constants are used in critical places and what not.

```

\c_zero
\c_one
\c_two
\c_three 2942 %% \tex_countdef:D \c_minus_one = 10 \scan_stop:
\c_four   2943 %% \c_minus_one = -1 \scan_stop:      %% in l3basics
\c_five   2944 %\int_const:Nn \c_zero {0}
\c_six     2945 \int_const:Nn \c_one {1}
\c_seven   2946 \int_const:Nn \c_two {2}
\c_eight   2947 \int_const:Nn \c_three {3}
\c_nine    2948 \int_const:Nn \c_four {4}
\c_ten     2949 \int_const:Nn \c_five {5}
\c_eleven  2950 \int_const:Nn \c_six {6}
\c_twelve  2951 \int_const:Nn \c_seven {7}
\c_thirteen 2952 \int_const:Nn \c_eight {8}
\c_fourteen 2953 \int_const:Nn \c_nine {9}
\c_fifteen  2954 \int_const:Nn \c_ten {10}
\c_sixteen  2955 \int_const:Nn \c_eleven {11}
\c_seventeen 2956 \int_const:Nn \c_twelve {12}
\c_eighteen 2957 \int_const:Nn \c_thirteen {13}
\c_nineteen 2958 \int_const:Nn \c_fourteen {14}
\c_twenty   2959 \int_const:Nn \c_fifteen {15}
\c_twentyone 2960 %% \tex_chardef:D \c_sixteen = 16\scan_stop: %% in l3basics
\c_twentytwo 2961 \int_const:Nn \c_thirty_two {32}
\c_thousand
\c_ten_thousand
\c_ten_thousand_one
\c_ten_thousand_two
\c_ten_thousand_three
\c_ten_thousand_four
\c_twenty_thousand

```

The next one may seem a little odd (obviously!) but is useful when dealing with logical operators.

```

2962 \int_const:Nn \c_hundred_one {101}
2963 \int_const:Nn \c_twohundred_fifty_five{255}
2964 \int_const:Nn \c_twohundred_fifty_six {256}
2965 \int_const:Nn \c_thousand {1000}
2966 \int_const:Nn \c_ten_thousand {10000}
2967 \int_const:Nn \c_ten_thousand_one {10001}
2968 \int_const:Nn \c_ten_thousand_two {10002}
2969 \int_const:Nn \c_ten_thousand_three {10003}
2970 \int_const:Nn \c_ten_thousand_four {10004}
2971 \int_const:Nn \c_twenty_thousand {20000}

```

`\c_max_int` The largest number allowed is  $2^{31} - 1$

```

2972 \int_const:Nn \c_max_int {2147483647}

```

## 100.5 Scanning and conversion

Conversion between different numbering schemes requires meticulous work. A number can be preceded by any number of + and/or -. We define a generic function which will return the sign and/or the remainder.

```

\int_get_sign_and_digits:n A number may be preceded by any number of +s and -s. Start out by assuming we have
\int_get_sign:n a positive number.
\int_get_digits:n
\int_get_sign_and_digits_aux:nNNN
\int_get_sign_and_digits_aux:oNNN
2973 \cs_new_nopar:Npn \int_get_sign_and_digits:n #1{
2974   \int_get_sign_and_digits_aux:nNNN {#1} \c_true_bool \c_true_bool \c_true_bool
2975 }
2976 \cs_new_nopar:Npn \int_get_sign:n #1{
2977   \int_get_sign_and_digits_aux:nNNN {#1} \c_true_bool \c_true_bool \c_false_bool
2978 }
2979 \cs_new_nopar:Npn \int_get_digits:n #1{
2980   \int_get_sign_and_digits_aux:nNNN {#1} \c_true_bool \c_false_bool \c_true_bool
2981 }

```

Now check the first character in the string. Only a - can change if a number is positive or negative, hence we reverse the boolean governing this. Then gobble the - and start over.

```

2982 \cs_new_nopar:Npn \int_get_sign_and_digits_aux:nNNN #1#2#3#4{
2983   \tl_if_head_eq_charcode:fNTF {#1} -
2984   {
2985     \bool_if:NTF #2
2986     { \int_get_sign_and_digits_aux:oNNN {\use_none:n #1} \c_false_bool #3#4 }
2987     { \int_get_sign_and_digits_aux:oNNN {\use_none:n #1} \c_true_bool #3#4 }
2988   }

```

The other cases are much simpler since we either just have to gobble the + or exit immediately and insert the correct sign.

```

2989 {
2990   \tl_if_head_eq_charcode:fNTF {#1} +
2991   { \int_get_sign_and_digits_aux:oNNN {\use_none:n #1} #2#3#4}
2992   {

```

The boolean #3 is for printing the sign while #4 is for printing the digits.

```

2993     \bool_if:NT #3 { \bool_if:NF #2 - }
2994     \bool_if:NT #4 {#1}
2995   }
2996 }
2997 }
2998 \cs_generate_variant:Nn \int_get_sign_and_digits_aux:nNNN {\oNNN}

```

`\int_convert_from_base_ten:nn` #1 is the base 10 number to be converted to base #2. We split off the sign first, print if there and then convert only the number. Since this is supposedly a base 10 number we can let TeX do the reading of + and -.

```

2999 \cs_set_nopar:Npn \int_convert_from_base_ten:nn#1#2{
3000   \intexpr_compare:nNnTF {#1}<\c_zero
3001   {
3002     - \int_convert_from_base_ten_aux:nfn {}
3003     { \intexpr_eval:n {-#1} }
3004   }
3005   {
3006     \int_convert_from_base_ten_aux:nfn {}
3007     { \intexpr_eval:n {#1} }
3008   }
3009   {#2}
3010 }

```

The algorithm runs like this:

1. If the number  $\langle num \rangle$  is greater than  $\langle base \rangle$ , calculate modulus of  $\langle num \rangle$  and  $\langle base \rangle$  and carry that over for next round. The remainder is calculated as a truncated division of  $\langle num \rangle$  and  $\langle base \rangle$ . Start over with these new values.
2. If  $\langle num \rangle$  is less than or equal to  $\langle base \rangle$  convert it to the correct symbol, print the previously calculated digits and exit.

#1 is the carried over result, #2 the remainder and #3 the base number.

```

3011 \cs_new_nopar:Npn \int_convert_from_base_ten_aux:nnn#1#2#3{
3012   \intexpr_compare:nNnTF {#2}<{#3}
3013   { \int_convert_number_to_letter:n{#2} #1 }
3014   {
3015     \int_convert_from_base_ten_aux:ffn

```

```

3016 {
3017   \int_convert_number_to_letter:n {\intexpr_mod:nn {#2}{#3}}
3018   #1
3019 }
3020 { \intexpr_div_truncate:nn{#2}{#3}}
3021 {#3}
3022 }
3023 }
3024 \cs_generate_variant:Nn \int_convert_from_base_ten_aux:nnn {nfn}
3025 \cs_generate_variant:Nn \int_convert_from_base_ten_aux:nnn {ffn}

```

`\int_convert_number_to_letter:n` Turning a number for a different base into a letter or digit.

```

3026 \cs_set_nopar:Npn \int_convert_number_to_letter:n #1{
3027   \if_case:w \intexpr_eval:w #1-10\intexpr_eval_end:
3028   \exp_after:wN A \or: \exp_after:wN B \or:
3029   \exp_after:wN C \or: \exp_after:wN D \or: \exp_after:wN E \or:
3030   \exp_after:wN F \or: \exp_after:wN G \or: \exp_after:wN H \or:
3031   \exp_after:wN I \or: \exp_after:wN J \or: \exp_after:wN K \or:
3032   \exp_after:wN L \or: \exp_after:wN M \or: \exp_after:wN N \or:
3033   \exp_after:wN O \or: \exp_after:wN P \or: \exp_after:wN Q \or:
3034   \exp_after:wN R \or: \exp_after:wN S \or: \exp_after:wN T \or:
3035   \exp_after:wN U \or: \exp_after:wN V \or: \exp_after:wN W \or:
3036   \exp_after:wN X \or: \exp_after:wN Y \or: \exp_after:wN Z \else:
3037   \use_i_after_fi:nw{ #1 }\fi: }

```

`\int_convert_to_base_ten:nn` #1 is the number, #2 is its base. First we get the sign, then use only the digits/letters from it and pass that onto a new function.

```

3038 \cs_set_nopar:Npn \int_convert_to_base_ten:nn #1#2 {
3039   \intexpr_eval:n{
3040     \int_get_sign:n{#1}
3041     \exp_args:Nf\int_convert_to_base_ten_aux:nn {\int_get_digits:n{#1}}{#2}
3042   }
3043 }

```

This is an intermediate function to get things started.

```

3044 \cs_new_nopar:Npn \int_convert_to_base_ten_aux:nn #1#2{
3045   \int_convert_to_base_ten_auxi:nnN {0}{#2} #1 \q_nil
3046 }

```

Here we check each letter/digit and calculate the next number. #1 is the previously calculated result (to be multiplied by the base), #2 is the base and #3 is the next letter/digit to be added.

```

3047 \cs_new_nopar:Npn \int_convert_to_base_ten_auxi:nnN#1#2#3{
3048   \quark_if_nil:NTF #3
3049   {#1}
3050   {\exp_args:Nf\int_convert_to_base_ten_auxi:nnN

```

```

3051     {\intexpr_eval:n{ #1*#2+\int_convert_letter_to_number:N #3} }
3052     {#2}
3053   }
3054 }

```

This is for turning a letter or digit into a number. This function also takes care of handling lowercase and uppercase letters. Hence `a` is turned into 11 and so is `A`.

```

3055 \cs_set_nopar:Npn \int_convert_letter_to_number:N #1{
3056   \intexpr_compare:nNnTF{‘#1}<{58}{#1}
3057   {
3058     \intexpr_eval:n{ ‘#1 -
3059       \intexpr_compare:nNnTF{‘#1}<{91}{ 55 }{ 87 }
3060   }
3061 }
3062 }

```

Needed from the `tl` module:

```

3063 \int_new:N \g_tl_inline_level_int
3064 \</initex | package>

```

Show token usage:

```

3065 <*showmemory>
3066 \showMemUsage
3067 </showmemory>

```

## 101 l3num implementation

We start by ensuring that the required packages are loaded.

```

3068 <*package>
3069 \ProvidesExplPackage
3070   {\filename}{\filedate}{\fileversion}{\filedescription}
3071 \package_check_loaded_expl:
3072 </package>
3073 <*initex | package>

```

`\if_num:w` Here are the remaining primitives for number comparisons and expressions.  
`\if_case:w`

```

3074 \cs_new_eq:NN \if_num:w \tex_ifnum:D
3075 \cs_new_eq:NN \if_case:w \tex_ifcase:D

```

Functions that support L<sup>A</sup>T<sub>E</sub>X’s user accessible counters should be added here, too. But first the internal counters.

`\num_incr:N` Incrementing and decrementing of integer registers is done with the following functions.  
`\num_decr:N`  
`\num_gincr:N` 3076 `\cs_set_nopar:Npn \num_incr:N #1{\num_add:Nn#1 1}`  
`\num_gdecr:N` 3077 `\cs_set_nopar:Npn \num_decr:N #1{\num_add:Nn#1 \c_minus_one}`  
3078 `\cs_set_nopar:Npn \num_gincr:N #1{\num_gadd:Nn#1 1}`  
3079 `\cs_set_nopar:Npn \num_gdecr:N #1{\num_gadd:Nn#1 \c_minus_one}`

`\num_incr:c` We also need ...  
`\num_decr:c`  
`\num_gincr:c` 3080 `\cs_generate_variant:Nn \num_incr:N {c}`  
`\num_gdecr:c` 3081 `\cs_generate_variant:Nn \num_decr:N {c}`  
3082 `\cs_generate_variant:Nn \num_gincr:N {c}`  
3083 `\cs_generate_variant:Nn \num_gdecr:N {c}`

`\num_zero:N` We also need ...  
`\num_zero:c`  
`\num_gzero:N` 3084 `\cs_new_nopar:Npn \num_zero:N #1 {\num_set:Nn #1 0}`  
`\num_gzero:c` 3085 `\cs_new_nopar:Npn \num_gzero:N #1 {\num_gset:Nn #1 0}`  
3086 `\cs_generate_variant:Nn \num_zero:N {c}`  
3087 `\cs_generate_variant:Nn \num_gzero:N {c}`

`\num_new:N` Allocate a new  $\langle num \rangle$  variable and initialize it with zero.  
`\num_new:c` 3088 `\cs_new_nopar:Npn \num_new:N #1{\tl_new:Nn #1{0}}`  
3089 `\cs_generate_variant:Nn \num_new:N {c}`

`\num_set:Nn` Assigning values to  $\langle num \rangle$  registers.  
`\num_set:cn`  
`\num_gset:Nn` 3090 `\cs_new_nopar:Npn \num_set:Nn #1#2{`  
`\num_gset:cn` 3091 `\tl_set:No #1{ \tex_number:D \intexpr_eval:n {#2} }`  
3092 `}`  
3093 `\cs_generate_variant:Nn \num_set:Nn {c}`  
3094 `\cs_new_nopar:Npn \num_gset:Nn {\pref_global:D \num_set:Nn}`  
3095 `\cs_generate_variant:Nn \num_gset:Nn {c}`

`\num_set_eq:NN` Setting  $\langle num \rangle$  registers equal to each other.  
`\num_set_eq:cN`  
`\num_set_eq:Nc` 3096 `\cs_new_eq:NN \num_set_eq:NN \tl_set_eq:NN`  
`\num_set_eq:cc` 3097 `\cs_generate_variant:Nn \num_set_eq:NN {c,Nc,cc}`

`\num_gset_eq:NN` Setting  $\langle num \rangle$  registers equal to each other.  
`\num_gset_eq:cN`  
`\num_gset_eq:Nc` 3098 `\cs_new_eq:NN \num_gset_eq:NN \tl_gset_eq:NN`  
`\num_gset_eq:cc` 3099 `\cs_generate_variant:Nn \num_gset_eq:NN {c,Nc,cc}`

`\num_add:Nn` Adding is easily done as the second argument goes through `\intexpr_eval:n`.  
`\num_add:cn`  
`\num_gadd:Nn` 3100 `\cs_new_nopar:Npn \num_add:Nn #1#2 {\num_set:Nn #1{#1+#2}}`  
`\num_gadd:cn` 3101 `\cs_generate_variant:Nn \num_add:Nn {c}`

```

3102 \cs_new_nopar:Npn \num_gadd:Nn {\pref_global:D \num_add:Nn}
3103 \cs_generate_variant:Nn\num_gadd:Nn {c}

```

\num\_use:N Here is how num macros are accessed:

```

\num_use:c
3104 \cs_new_eq:NN\num_use:N \use:n
3105 \cs_new_eq:NN\num_use:c \use:c

```

\num\_show:N Here is how num macros are diagnosed:

```

\num_show:c
3106 \cs_new_eq:NN\num_show:N \cs_show:N
3107 \cs_new_eq:NN\num_show:c \cs_show:c

```

\num\_elt\_count:n Helper function for counting elements in a list.

```

\num_elt_count_prop:Nn
3108 \cs_new:Npn \num_elt_count:n #1 { + 1 }
3109 \cs_new:Npn \num_elt_count_prop:Nn #1#2 { + 1 }

```

\l\_tmpa\_num We provide an number local and two global  $\langle num \rangle$ s, maybe we need more or less.

```

\l_tmpb_num
\l_tmpc_num
\g_tmpa_num
\g_tmpb_num
3110 \num_new:N \l_tmpa_num
3111 \num_new:N \l_tmpb_num
3112 \num_new:N \l_tmpc_num
3113 \num_new:N \g_tmpa_num
3114 \num_new:N \g_tmpb_num

```

\c\_max\_register\_num

```

3115 \tex_mathchardef:D \c_max_register_num = 32767 \scan_stop:
3116 \</initex | package>

```

## 102 l3intexpr implementation

We start by ensuring that the required packages are loaded.

```

3117 <*package>
3118 \ProvidesExplPackage
3119   {\filename}{\filedate}{\fileversion}{\filedescription}
3120 \package_check_loaded_expl:
3121 \</package>
3122 <*initex | package>

```

\intexpr\_value:w Here are the remaining primitives for number comparisons and expressions.

```

\intexpr_eval:n
\intexpr_eval:w
\intexpr_eval_end:
\if_intexpr_compare:w
\if_intexpr_odd:w
\if_intexpr_case:w
3123 \cs_set_eq:NN \intexpr_value:w \tex_number:D
3124 \cs_set_eq:NN \intexpr_eval:w \etex_numexpr:D

```



```

3125 \cs_set_protected:Npn \intexpr_eval_end: {\tex_relax:D}
3126 \cs_set_eq:NN \if_intexpr_compare:w \tex_ifnum:D
3127 \cs_set_eq:NN \if_intexpr_odd:w \tex_ifodd:D
3128 \cs_set_eq:NN \if_intexpr_case:w \tex_ifcase:D
3129 \cs_set:Npn \intexpr_eval:n #1{
3130   \intexpr_value:w \intexpr_eval:w #1\intexpr_eval_end:
3131 }

```

`\intexpr_compare_p:n` Comparison tests using a simple syntax where only one set of braces is required and  
`\intexpr_compare:nTF` additional operators such as `!=` and `>=` are supported. First some notes on the idea behind this. We wish to support writing code like

```
\intexpr_compare_p:n { 5 + \l_tmpa_int != 4 - \l_tmpb_int }
```

In other words, we want to somehow add the missing `\intexpr_eval:w` where required. We can start evaluating from the left using `\intexpr:w`, and we know that since the relation symbols `<`, `>`, `=` and `!` are not allowed in such expressions, they will terminate the expression. Therefore, we first let T<sub>E</sub>X evaluate this left hand side of the (in)equality.

```

3132 \prg_set_conditional:Npnn \intexpr_compare:n #1{p,TF,T,F}{
3133   \exp_after:wN \intexpr_compare_auxi:w \intexpr_value:w
3134   \intexpr_eval:w #1\q_stop
3135 }

```

Then the next step is to figure out which relation we should use, so we have to somehow get rid of the first evaluation so that we can see what stopped it. `\tex_romannumeral:D` is handy here since its expansion given a non-positive number is `<null>`. We therefore simply check if the first token of the left hand side evaluation is a minus. If not, we insert it and issue `\tex_romannumeral:D`, thereby ridding us of the left hand side evaluation. We do however save it for later.

```

3136 \cs_set:Npn \intexpr_compare_auxi:w #1#2\q_stop{
3137   \exp_after:wN \intexpr_compare_auxii:w \tex_romannumeral:D
3138   \if:w #1- \else: -\fi: #1#2 \q_stop #1#2 \q_nil
3139 }

```

This leaves the first relation symbol in front and assuming the right hand side has been input, at least one other token as well. We support the following forms: `=`, `<`, `>` and the extended `!=`, `==`, `<=` and `>=`. All the extended forms have an extra `=` so we check if that is present as well. Then use specific function to perform the test.

```

3140 \cs_set:Npn \intexpr_compare_auxii:w #1#2#3\q_stop{
3141   \use:c{
3142     \intexpr_compare_
3143     #1 \if_meaning:w =#2 = \fi:
3144     :w}
3145 }

```

The actual comparisons are then simple function calls, using the relation as delimiter for a delimited argument. Equality is easy:

```

3146 \cs_set:cpn {intexpr_compare_=:w} #1=#2\q_nil{
3147   \if_intexpr_compare:w #1=\intexpr_eval:w #2 \intexpr_eval_end:
3148   \prg_return_true: \else: \prg_return_false: \fi:
3149 }

```

So is the one using == – we just have to use == in the parameter text.

```

3150 \cs_set:cpn {intexpr_compare_==:w} #1==#2\q_nil{
3151   \if_intexpr_compare:w #1=\intexpr_eval:w #2 \intexpr_eval_end:
3152   \prg_return_true: \else: \prg_return_false: \fi:
3153 }

```

Not equal is just about reversing the truth value.

```

3154 \cs_set:cpn {intexpr_compare_!=:w} #1!=#2\q_nil{
3155   \if_intexpr_compare:w #1=\intexpr_eval:w #2 \intexpr_eval_end:
3156   \prg_return_false: \else: \prg_return_true: \fi:
3157 }

```

Less than and greater than are also straight forward.

```

3158 \cs_set:cpn {intexpr_compare_<:w} #1<#2\q_nil{
3159   \if_intexpr_compare:w #1<\intexpr_eval:w #2 \intexpr_eval_end:
3160   \prg_return_true: \else: \prg_return_false: \fi:
3161 }
3162 \cs_set:cpn {intexpr_compare_>:w} #1>#2\q_nil{
3163   \if_intexpr_compare:w #1>\intexpr_eval:w #2 \intexpr_eval_end:
3164   \prg_return_true: \else: \prg_return_false: \fi:
3165 }

```

The less than or equal operation is just the opposite of the greater than operation. Vice versa for less than or equal.

```

3166 \cs_set:cpn {intexpr_compare_<=:w} #1<=#2\q_nil{
3167   \if_intexpr_compare:w #1>\intexpr_eval:w #2 \intexpr_eval_end:
3168   \prg_return_false: \else: \prg_return_true: \fi:
3169 }
3170 \cs_set:cpn {intexpr_compare_>=:w} #1>=#2\q_nil{
3171   \if_intexpr_compare:w #1<\intexpr_eval:w #2 \intexpr_eval_end:
3172   \prg_return_false: \else: \prg_return_true: \fi:
3173 }

```

\intexpr\_compare\_p:nNn More efficient but less natural in typing.

\intexpr\_compare:nNnTF

```

3174 \prg_set_conditional:Npnn \intexpr_compare:nNn #1#2#3{p,TF,T,F}{
3175   \if_intexpr_compare:w \intexpr_eval:w #1 #2 \intexpr_eval:w #3
3176   \intexpr_eval_end:
3177   \prg_return_true: \else: \prg_return_false: \fi:
3178 }

```

`\intexpr_max:nn` Functions for min, max, and absolute value.

`\intexpr_min:nn`

`\intexpr_abs:n`

```

3179 \cs_set:Npn \intexpr_abs:n #1{
3180   \intexpr_value:w
3181   \if_intexpr_compare:w \intexpr_eval:w #1<\c_zero
3182   -
3183   \fi:
3184   \intexpr_eval:w #1\intexpr_eval_end:
3185 }
3186 \cs_set:Npn \intexpr_max:nn #1#2{
3187   \intexpr_value:w \intexpr_eval:w
3188   \if_intexpr_compare:w
3189     \intexpr_eval:w #1>\intexpr_eval:w #2\intexpr_eval_end:
3190     #1
3191   \else:
3192     #2
3193   \fi:
3194   \intexpr_eval_end:
3195 }
3196 \cs_set:Npn \intexpr_min:nn #1#2{
3197   \intexpr_value:w \intexpr_eval:w
3198   \if_intexpr_compare:w
3199     \intexpr_eval:w #1<\intexpr_eval:w #2\intexpr_eval_end:
3200     #1
3201   \else:
3202     #2
3203   \fi:
3204   \intexpr_eval_end:
3205 }

```

`\intexpr_div_truncate:nn`

`\intexpr_div_round:nn`

`\intexpr_mod:nn`

As `\intexpr_eval:w` rounds the result of a division we also provide a version that truncates the result.

Initial version didn't work correctly with eTeX's implementation.

```

3206 %\cs_set:Npn \intexpr_div_truncate_raw:nn #1#2 {
3207 %  \intexpr_eval:n{ (2*#1 - #2) / (2* #2) }
3208 %}

```

New version by Heiko:

```

3209 \cs_set:Npn \intexpr_div_truncate:nn #1#2 {
3210   \intexpr_value:w \intexpr_eval:w
3211   \if_intexpr_compare:w \intexpr_eval:w #1 = \c_zero
3212   0
3213   \else:
3214     (#1
3215     \if_intexpr_compare:w \intexpr_eval:w #1 < \c_zero
3216     \if_intexpr_compare:w \intexpr_eval:w #2 < \c_zero

```

```

3217         -( #2 +
3218         \else:
3219         +( #2 -
3220         \fi:
3221     \else:
3222         \if_intexpr_compare:w \intexpr_eval:w #2 < \c_zero
3223         +( #2 +
3224         \else:
3225         -( #2 -
3226         \fi:
3227         \fi:
3228         1)/2)
3229     \fi:
3230     /(#2)
3231 \intexpr_eval_end:
3232 }

```

For the sake of completeness:

```

3233 \cs_set:Npn \intexpr_div_round:nn #1#2 {\intexpr_eval:n{(#1)/(#2)}}

```

Finally there's the modulus operation.

```

3234 \cs_set:Npn \intexpr_mod:nn #1#2 {
3235     \intexpr_value:w
3236     \intexpr_eval:w
3237     #1 - \intexpr_div_truncate:nn {#1}{#2} * (#2)
3238     \intexpr_eval_end:
3239 }

```

`\intexpr_if_odd_p:n` A predicate function.

`\intexpr_if_odd:nTF`

`\intexpr_if_even_p:n`

`\intexpr_if_even:nTF`

```

3240 \prg_set_conditional:Npnn \intexpr_if_odd:n #1 {p,TF,T,F} {
3241     \if_intexpr_odd:w \intexpr_eval:w #1\intexpr_eval_end:
3242     \prg_return_true: \else: \prg_return_false: \fi:
3243 }
3244 \prg_set_conditional:Npnn \intexpr_if_even:n #1 {p,TF,T,F} {
3245     \if_intexpr_odd:w \intexpr_eval:w #1\intexpr_eval_end:
3246     \prg_return_false: \else: \prg_return_true: \fi:
3247 }

```

`\intexpr_while_do:nn`

`\intexpr_until_do:nn`

`\intexpr_do_while:nn`

`\intexpr_do_until:nn`

These are quite easy given the above functions. The `while` versions test first and then execute the body. The `do_while` does it the other way round.

```

3248 \cs_set:Npn \intexpr_while_do:nn #1#2{
3249     \intexpr_compare:nT {#1}{#2} \intexpr_while_do:nn {#1}{#2}}
3250 }
3251 \cs_set:Npn \intexpr_until_do:nn #1#2{
3252     \intexpr_compare:nF {#1}{#2} \intexpr_until_do:nn {#1}{#2}}
3253 }

```

```

3254 \cs_set:Npn \intexpr_do_while:nn #1#2{
3255   #2 \intexpr_compare:nT {#1}{\intexpr_do_while:nNnn {#1}{#2}}
3256 }
3257 \cs_set:Npn \intexpr_do_until:nn #1#2{
3258   #2 \intexpr_compare:nF {#1}{\intexpr_do_until:nn {#1}{#2}}
3259 }

```

\intexpr\_while\_do:nNnn  
\intexpr\_until\_do:nNnn  
\intexpr\_do\_while:nNnn  
\intexpr\_do\_until:nNnn

As above but not using the more natural syntax.

```

3260 \cs_set:Npn \intexpr_while_do:nNnn #1#2#3#4{
3261   \intexpr_compare:nNnT {#1}#2{#3}{#4} \intexpr_while_do:nNnn {#1}#2{#3}{#4}}
3262 }
3263 \cs_set:Npn \intexpr_until_do:nNnn #1#2#3#4{
3264   \intexpr_compare:nNnF {#1}#2{#3}{#4} \intexpr_until_do:nNnn {#1}#2{#3}{#4}}
3265 }
3266 \cs_set:Npn \intexpr_do_while:nNnn #1#2#3#4{
3267   #4 \intexpr_compare:nNnT {#1}#2{#3}{\intexpr_do_while:nNnn {#1}#2{#3}{#4}}
3268 }
3269 \cs_set:Npn \intexpr_do_until:nNnn #1#2#3#4{
3270   #4 \intexpr_compare:nNnF {#1}#2{#3}{\intexpr_do_until:nNnn {#1}#2{#3}{#4}}
3271 }
3272 \</initex | package>

```

## 103 l3skip implementation

We start by ensuring that the required packages are loaded.

```

3273 <*package>
3274 \ProvidesExplPackage
3275   {\filename}{\filedate}{\fileversion}{\filedescription}
3276 \package_check_loaded_expl:
3277 </package>
3278 <*initex | package>

```

### 103.1 Skip registers

\skip\_new:N Allocation of a new internal registers.  
\skip\_new:c

```

3279 <*initex>
3280 \alloc_setup_type:nnn {skip} \c_zero \c_max_register_num
3281 \cs_new_nopar:Npn \skip_new:N #1 { \alloc_reg:NnNN g {skip} \tex_skipdef:D #1 }
3282 \cs_new_nopar:Npn \skip_new_l:N #1 { \alloc_reg:NnNN l {skip} \tex_skipdef:D #1 }
3283 </initex>
3284 <*package>
3285 \cs_new_nopar:Npn \skip_new:N #1 {
3286   \chk_if_free_cs:N #1

```

```

3287 \newskip #1
3288 }
3289 \</package>
3290 \cs_generate_variant:Nn \skip_new:N {c}

```

\skip\_set:Nn Setting skips is again something that I would like to make uniform at the moment to get a better overview.

```

\skip_set:cn
\skip_gset:Nn
\skip_gset:cn
3291 \cs_new_nopar:Npn \skip_set:Nn #1#2 {
3292   #1\skip_eval:n{#2}
3293   \< *check>
3294   \chk_local_or_pref_global:N #1
3295   \< /check>
3296   }
3297 \cs_new_nopar:Npn \skip_gset:Nn {
3298   \< *check>
3299   \pref_global_chk:
3300   \< /check>
3301   \< -check> \pref_global:D
3302   \skip_set:Nn
3303   }
3304 \cs_generate_variant:Nn \skip_set:Nn {cn}
3305 \cs_generate_variant:Nn \skip_gset:Nn {cn}

```

\skip\_zero:N Reset the register to zero.

```

\skip_gzero:N
\skip_zero:c
\skip_gzero:c
3306 \cs_new_nopar:Npn \skip_zero:N #1{
3307   #1\c_zero_skip \scan_stop:
3308   \< *check>
3309   \chk_local_or_pref_global:N #1
3310   \< /check>
3311   }
3312 \cs_new_nopar:Npn \skip_gzero:N {

```

We make sure that a local variable is not updated globally by changing the internal test (i.e. \chk\_local\_or\_pref\_global:N) before making the assignment. This is done by \pref\_global\_chk: which also issues the necessary \pref\_global:D. This is not very efficient, but this code will be only included for debugging purposes. Using \pref\_global:D in front of the local function is better in the production versions.

```

3313 \< *check>
3314   \pref_global_chk:
3315   \< /check>
3316   \< -check> \pref_global:D
3317   \skip_zero:N
3318   }
3319 \cs_generate_variant:Nn \skip_zero:N {c}
3320 \cs_generate_variant:Nn \skip_gzero:N {c}

```

<code>\skip_add:Nn</code>	Adding and subtracting to and from <skip>s
<code>\skip_add:cn</code>	
<code>\skip_gadd:Nn</code>	<pre>3321 \cs_new_nopar:Npn \skip_add:Nn #1#2 {</pre>
<code>\skip_gadd:cn</code>	We need to say by in case the first argument is a register accessed by its number, e.g.,
<code>\skip_sub:Nn</code>	<code>\skip23.</code>
<code>\skip_gsub:Nn</code>	<pre> 3322   \tex_advance:D#1 by \skip_eval:n{#2} 3323   &lt;*check&gt; 3324   \chk_local_or_pref_global:N #1 3325   &lt;/check&gt; 3326   } 3327   \cs_generate_variant:Nn \skip_add:Nn {cn}  3328   \cs_new_nopar:Npn \skip_sub:Nn #1#2{ 3329     \tex_advance:D#1-\skip_eval:n{#2} 3330     &lt;*check&gt; 3331     \chk_local_or_pref_global:N #1 3332     &lt;/check&gt; 3333     }  3334   \cs_new_nopar:Npn \skip_gadd:Nn { 3335     &lt;*check&gt; 3336     \pref_global_chk: 3337     &lt;/check&gt; 3338     &lt;-check&gt; \pref_global:D 3339     \skip_add:Nn 3340     } 3341   \cs_generate_variant:Nn \skip_gadd:Nn {cn}  3342   \cs_new_nopar:Npn \skip_gsub:Nn { 3343     &lt;*check&gt; 3344     \pref_global_chk: 3345     &lt;/check&gt; 3346     &lt;-check&gt; \pref_global:D 3347     \skip_sub:Nn 3348     } </pre>
<code>\skip_horizontal:N</code>	Inserting skips.
<code>\skip_horizontal:c</code>	
<code>\skip_horizontal:n</code>	<pre>3349 \cs_new_eq:NN \skip_horizontal:N \tex_hskip:D</pre>
<code>\skip_vertical:N</code>	<pre>3350 \cs_generate_variant:Nn \skip_horizontal:N {c}</pre>
<code>\skip_vertical:c</code>	<pre>3351 \cs_new_nopar:Npn \skip_horizontal:n #1 { \skip_horizontal:N \skip_eval:n{#1} }</pre>
<code>\skip_vertical:n</code>	<pre> 3352 \cs_new_eq:NN \skip_vertical:N \tex_vskip:D 3353 \cs_generate_variant:Nn \skip_vertical:N {c} 3354 \cs_new_nopar:Npn \skip_vertical:n #1 { \skip_vertical:N \skip_eval:n{#1} } </pre>
<code>\skip_use:N</code>	Here is how skip registers are accessed:
<code>\skip_use:c</code>	<pre> 3355 \cs_new_eq:NN \skip_use:N \tex_the:D 3356 \cs_generate_variant:Nn \skip_use:N {c} </pre>

`\skip_show:N` Diagnostics.

`\skip_show:c`

```

3357 \cs_new_eq:NN \skip_show:N \tex_showthe:D
3358 \cs_new_nopar:Npn \skip_show:c #1 { \skip_show:N \cs:w #1 \cs_end: }

```

`\skip_eval:n` Evaluating a calc expression.

```

3359 \cs_new_nopar:Npn \skip_eval:n #1 { \etex_glueexpr:D #1 \scan_stop: }

```

`\l_tmpa_skip` We provide three local and two global scratch registers, maybe we need more or less.

`\l_tmpb_skip`

`\l_tmpc_skip`

`\g_tmpa_skip`

`\g_tmpb_skip`

```

3360 %%\chk_if_free_cs:N \l_tmpa_skip
3361 %%\tex_skipdef:D\l_tmpa_skip 255 %currently taken up by \skip@
3362 \skip_new:N \l_tmpa_skip
3363 \skip_new:N \l_tmpb_skip
3364 \skip_new:N \l_tmpc_skip
3365 \skip_new:N \g_tmpa_skip
3366 \skip_new:N \g_tmpb_skip

```

`\c_zero_skip`

`\c_max_skip`

```

3367 \!package
3368 \skip_new:N \c_zero_skip
3369 \skip_set:Nn \c_zero_skip {0pt}
3370 \skip_new:N \c_max_skip
3371 \skip_set:Nn \c_max_skip {16383.99999pt}
3372 \!package
3373 \!initex
3374 \cs_set_eq:NN \c_zero_skip \z@
3375 \cs_set_eq:NN \c_max_skip \maxdimen
3376 \!initex

```

`\skip_if_infinite_glue_p:n` With  $\varepsilon$ -TeX we all of a sudden get access to a lot information we should otherwise consider

`\skip_if_infinite_glue:nTF` ourselves lucky to get. One is the stretch and shrink components of a skip register and the order of those components. `\skip_if_infinite_glue:nTF` tests it directly by looking at the stretch and shrink order. If either of the predicate functions return  $\langle true \rangle$  `\bool_if:nTF` will return  $\langle true \rangle$  and the logic test will take the true branch.

```

3377 \prg_new_conditional:Nnn \skip_if_infinite_glue:n {p,TF,T,F} {
3378   \bool_if:nTF {
3379     \intexpr_compare_p:nNn {\etex_gluestretchorder:D #1 } > \c_zero ||
3380     \intexpr_compare_p:nNn {\etex_glueshrinkorder:D #1 } > \c_zero
3381   } {\prg_return_true:} {\prg_return_false:}
3382 }

```

`\p_split_finite_else_action:nnNN` This macro is useful when performing error checking in certain circumstances. If the  $\langle skip \rangle$  register holds finite glue it sets #3 and #4 to the stretch and shrink component



resp. If it holds infinite glue set #3 and #4 to zero and issue the special action #2 which is probably an error message. Assignments are global.

```

3383 \cs_new_nopar:Npn \skip_split_finite_else_action:nnNN #1#2#3#4{
3384   \skip_if_infinite_glue:nTF {#1}
3385   {
3386     #3 = \c_zero_skip
3387     #4 = \c_zero_skip
3388     #2
3389   }
3390   {
3391     #3 = \etex_gluestretch:D #1 \scan_stop:
3392     #4 = \etex_glueshrink:D #1 \scan_stop:
3393   }
3394 }

```

## 103.2 Dimen registers

`\dim_new:N` Allocating  $\langle dim \rangle$  registers...

```

\dim_new:c
3395 \<initex>
3396 \alloc_setup_type:nnn {dimen} \c_zero \c_max_register_num
3397 \cs_new_nopar:Npn \dim_new:N #1 {\alloc_reg:NnNN g {dimen} \tex_dimendef:D #1 }
3398 \cs_new_nopar:Npn \dim_new_l:N #1 {\alloc_reg:NnNN l {dimen} \tex_dimendef:D #1 }
3399 \</initex>
3400 \<package>
3401 \cs_new_nopar:Npn \dim_new:N #1 {
3402   \chk_if_free_cs:N #1
3403   \newdimen #1
3404 }
3405 \</package>
3406 \cs_generate_variant:Nn \dim_new:N {c}

```

`\dim_set:Nn` We add `\dim_eval:n` in order to allow simple arithmetic and a space just for those using `\dimen1` or alike. See OR!

```

\dim_set:cn
\dim_set:Nc
3407 \cs_new_nopar:Npn \dim_set:Nn #1#2 { #1~ \dim_eval:n{#2} }
\dim_gset:Nn
3408 \cs_generate_variant:Nn \dim_set:Nn {cn,Nc}
\dim_gset:cn
\dim_gset:Nc
3409 \cs_new_nopar:Npn \dim_gset:Nn { \pref_global:D \dim_set:Nn }
\dim_gset:cc
3410 \cs_generate_variant:Nn \dim_gset:Nn {cn,Nc,cc}

```

`\dim_zero:N` Resetting.

```

\dim_gzero:N
\dim_zero:c
3411 \cs_new_nopar:Npn \dim_zero:N #1 { #1\c_zero_skip }
\dim_gzero:c
3412 \cs_generate_variant:Nn \dim_zero:N {c}

3413 \cs_new_nopar:Npn \dim_gzero:N { \pref_global:D \dim_zero:N }
3414 \cs_generate_variant:Nn \dim_gzero:N {c}

```

`\dim_add:Nn` Addition.

`\dim_add:cn` 3415 `\cs_new_nopar:Npn \dim_add:Nn #1#2{`

`\dim_add:Nc`

`\dim_gadd:Nn` We need to say by in case the first argument is a register accessed by its number, e.g.,

`\dim_gadd:cn` `\dimen23.`

3416 `\tex_advance:D#1 by \dim_eval:n{#2}\scan_stop:`

3417 `}`

3418 `\cs_generate_variant:Nn \dim_add:Nn {cn,Nc}`

3419 `\cs_new_nopar:Npn \dim_gadd:Nn { \pref_global:D \dim_add:Nn }`

3420 `\cs_generate_variant:Nn \dim_gadd:Nn {cn}`

`\dim_sub:Nn` Subtracting.

`\dim_sub:cn`

`\dim_sub:Nc` 3421 `\cs_new_nopar:Npn \dim_sub:Nn #1#2 { \tex_advance:D#1-#2\scan_stop: }`

`\dim_gsub:Nn` 3422 `\cs_generate_variant:Nn \dim_sub:Nn {cn,Nc}`

`\dim_gsub:cn` 3423 `\cs_new_nopar:Npn \dim_gsub:Nn { \pref_global:D \dim_sub:Nn }`

3424 `\cs_generate_variant:Nn \dim_gsub:Nn {cn}`

`\dim_use:N` Accessing a  $\langle dim \rangle$ .

`\dim_use:c` 3425 `\cs_new_eq:NN \dim_use:N \tex_the:D`

3426 `\cs_generate_variant:Nn \dim_use:N {c}`

`\dim_show:N` Diagnostics.

`\dim_show:c` 3427 `\cs_new_eq:NN \dim_show:N \tex_showthe:D`

3428 `\cs_new_nopar:Npn \dim_show:c #1 { \dim_show:N \cs:w #1 \cs_end: }`

`\l_tmpa_dim` Some scratch registers.

`\l_tmpb_dim`

`\l_tmpc_dim` 3429 `\dim_new:N \l_tmpa_dim`

`\l_tmpd_dim` 3430 `\dim_new:N \l_tmpb_dim`

`\g_tmpa_dim` 3431 `\dim_new:N \l_tmpc_dim`

`\g_tmpb_dim` 3432 `\dim_new:N \l_tmpd_dim`

3433 `\dim_new:N \g_tmpa_dim`

3434 `\dim_new:N \g_tmpb_dim`

`\c_zero_dim` Just aliases.

`\c_max_dim` 3435 `\cs_new_eq:NN \c_zero_dim \c_zero_skip`

3436 `\cs_new_eq:NN \c_max_dim \c_max_skip`

`\dim_eval:n` Evaluating a calc expression.

3437 `\cs_new_nopar:Npn \dim_eval:n #1 { \etex_dimexpr:D #1 \scan_stop: }`

`\if_dim:w` The comparison primitive.

```
3438 \cs_new_eq:NN \if_dim:w \tex_ifdim:D
```

`\dim_compare_p:nNn`  
`\dim_compare:nNnTF`

```
3439 \prg_new_conditional:Nnn \dim_compare:nNn {p,TF,T,F} {
3440   \if_dim:w \dim_eval:n {#1} #2 \dim_eval:n {#3}
3441   \prg_return_true: \else: \prg_return_false: \fi:
3442 }
```

`\dim_while_do:nNnn` while\_do and do\_while functions for dimensions. Same as for the int type only the names have changed.  
`\dim_until_do:nNnn`  
`\dim_do_while:nNnn`  
`\dim_do_until:nNnn`

```
3443 \cs_new_nopar:Npn \dim_while_do:nNnn #1#2#3#4{
3444   \dim_compare:nNnT {#1}#2{#3}{#4} \dim_while_do:nNnn {#1}#2{#3}{#4}}
3445 }
3446 \cs_new_nopar:Npn \dim_until_do:nNnn #1#2#3#4{
3447   \dim_compare:nNnF {#1}#2{#3}{#4} \dim_until_do:nNnn {#1}#2{#3}{#4}}
3448 }
3449 \cs_new_nopar:Npn \dim_do_while:nNnn #1#2#3#4{
3450   #4 \dim_compare:nNnT {#1}#2{#3}{\dim_do_while:nNnn {#1}#2{#3}{#4}}
3451 }
3452 \cs_new_nopar:Npn \dim_do_until:nNnn #1#2#3#4{
3453   #4 \dim_compare:nNnF {#1}#2{#3}{\dim_do_until:nNnn {#1}#2{#3}{#4}}
3454 }
```

### 103.3 Muskips

`\muskip_new:N` And then we add muskips.

```
3455 ⟨*initex⟩
3456 \alloc_setup_type:nnn {muskip} \c_zero \c_max_register_num
3457 \cs_new_nopar:Npn \muskip_new:N #1{\alloc_reg:NnNN g {muskip} \tex_muskipdef:D #1}
3458 \cs_new_nopar:Npn \muskip_new_l:N #1{\alloc_reg:NnNN l {muskip} \tex_muskipdef:D #1}
3459 ⟨/initex⟩
3460 ⟨*package⟩
3461 \cs_new_nopar:Npn \muskip_new:N #1 {
3462   \chk_if_free_cs:N #1
3463   \newmuskip #1
3464 }
3465 ⟨/package⟩
```

`\muskip_set:Nn` Simple functions for muskips.

`\muskip_gset:Nn`  
`\muskip_add:Nn`  
`\muskip_gadd:Nn`  
`\muskip_sub:Nn`  
`\muskip_gsub:Nn`

```
3466 \cs_new_nopar:Npn \muskip_set:Nn#1#2{\etex_muexpr:D#2\scan_stop:}
3467 \cs_new_nopar:Npn \muskip_gset:Nn{\pref_global:D\muskip_set:Nn}
3468 \cs_new_nopar:Npn \muskip_add:Nn#1#2{\tex_advance:D#1\etex_muexpr:D#2\scan_stop:}
```

```

3469 \cs_new_nopar:Npn \muskip_gadd:Nn{\pref_global:D\muskip_add:Nn}
3470 \cs_new_nopar:Npn \muskip_sub:Nn#1#2{\tex_advance:D#1-\etex_muexpr:D#2\scan_stop:}
3471 \cs_new_nopar:Npn \muskip_gsub:Nn{\pref_global:D\muskip_sub:Nn}

```

`\muskip_use:N` Accessing a  $\langle muskip \rangle$ .

```

3472 \cs_new_eq:NN \muskip_use:N \tex_the:D
3473 \</initex | package>

```

## 104 l3tl implementation

We start by ensuring that the required packages are loaded.

```

3474 \*package>
3475 \ProvidesExplPackage
3476   {\filename}{\filedate}{\fileversion}{\filedescription}
3477 \package_check_loaded_expl:
3478 \</package>

3479 \*initex | package>

```

A token list variable is a control sequence that holds tokens. The interface is similar to that for token registers, but beware that the behavior vis á vis `\cs_set_nopar:Npx` etc. ... is different. (You see this comes from Denys' implementation.)

### 104.1 Functions

`\tl_new:N` We provide one allocation function (which checks that the name is not used) and two clear functions that locally or globally clear the token list. The allocation function has two arguments to specify an initial value. This is the only way to give values to constants.

`\tl_new:c`

`\tl_new:Nn`

`\tl_new:cn`

`\tl_new:Nx`

```

3480 \cs_new:Npn \tl_new:Nn #1#2{
3481   \chk_if_free_cs:N #1

```

If checking we don't allow constants to be defined.

```

3482 \*check>
3483   \chk_var_or_const:N #1
3484 \</check>

```

Otherwise any variable type is allowed.

```

3485   \cs_gset_nopar:Npn #1{#2}
3486 }
3487 \cs_generate_variant:Nn \tl_new:Nn {cn}
3488 \cs_new:Npn \tl_new:Nx #1#2{

```

```

3489 \chk_if_free_cs:N #1
3490 <check> \chk_var_or_const:N #1
3491 \cs_gset_nopar:Npx #1{#2}
3492 }
3493 \cs_new_nopar:Npn \tl_new:N #1{\tl_new:Nn #1{}}
3494 \cs_new_nopar:Npn \tl_new:c #1{\tl_new:cn {#1}{}}

```

\tl\_use:N Perhaps this should just be enabled when checking?

```

\tl_use:c
3495 \cs_new_nopar:Npn \tl_use:N #1 {
3496 \if_meaning:w #1 \tex_relax:D

```

If  $\langle tl\ var.\rangle$  equals  $\tex_relax:D$  it is probably stemming from a  $\cs:w\dots\cs_end:$  that was created by mistake somewhere.

```

3497 \msg_kernel_bug:x {Token~list~variable~ '\token_to_str:N #1'~
3498 has~ an~ erroneous~ structure!}
3499 \else:
3500 \exp_after:wN #1
3501 \fi:
3502 }
3503 \cs_generate_variant:Nn \tl_use:N {c}

```

\tl\_show:N Showing a  $\langle tl\ var.\rangle$  is just  $\showing$  it and I don't really care about checking that it's malformed at this stage.

```

\tl_show:c
\tl_show:n
3504 \cs_new_nopar:Npn \tl_show:N #1 { \cs_show:N #1 }
3505 \cs_generate_variant:Nn \tl_show:N {c}
3506 \cs_set_eq:NN \tl_show:n \etex_showtokens:D

```

\tl\_set:Nn To set token lists to a specific value to type of functions are available:  $\tl\_set\_eq:NN$  takes two token-lists as its arguments assign the first the contents of the second;  $\tl\_set:Nn$  has as its second argument a 'real' list of tokens. One can view  $\tl\_set:Nv$   $\tl\_set\_eq:NN$  as a special form of  $\tl\_set:No$ . Both functions have global counterparts.

\tl\_set:Nx During development we check if the token list that is being assigned to exists. If not, a warning will be issued.

```

\tl_set:cn
\tl_set:cV
\tl_set:co
\tl_set:cx
3507 <*check>
3508 \cs_new:Npn \tl_set:Nn #1#2{
3509 \chk_exist_cs:N #1 \cs_set_nopar:Npn #1{#2}

```

\tl\_gset:Nn We use  $\chk\_local\_or\_pref\_global:N$  after the assignment to allow constructs with  $\pref\_global\_chk:.$  But one should note that this is less efficient then using the real global variant since they are built-in.

```

\tl_gset:Nx
\tl_gset:cn
\tl_gset:cx
3510 \chk_local_or_pref_global:N #1
3511 }
3512 \cs_new:Npn \tl_set:Nx #1#2{
3513 \chk_exist_cs:N #1 \cs_set_nopar:Npx #1{#2} \chk_local:N #1
3514 }

```

The the global versions.

```

3515 \cs_new:Npn \tl_gset:Nn #1#2{
3516   \chk_exist_cs:N #1 \cs_gset_nopar:Npn #1{#2} \chk_global:N #1
3517 }
3518 \cs_new:Npn \tl_gset:Nx #1#2{
3519   \chk_exist_cs:N #1 \cs_gset_nopar:Npx #1{#2} \chk_global:N #1
3520 }
3521 </check>

```

For some functions like `\tl_set:Nn` we need to define the ‘non-check’ version with arguments since we want to allow constructions like `\tl_set:Nn\l_tmpa_tl\foo` and so we can’t use the primitive `\TeX` command.

```

3522 <!*check>
3523 \cs_new:Npn \tl_set:Nn#1#2{\cs_set_nopar:Npn#1{#2}}
3524 \cs_new:Npn \tl_set:Nx#1#2{\cs_set_nopar:Npx#1{#2}}
3525 \cs_new:Npn \tl_gset:Nn#1#2{\cs_gset_nopar:Npn#1{#2}}
3526 \cs_new:Npn \tl_gset:Nx#1#2{\cs_gset_nopar:Npx#1{#2}}
3527 </!check>

```

The remaining functions can just be defined with help from the expansion module.

```

3528 \cs_generate_variant:Nn \tl_set:Nn {NV,No,Nv,Nf,cn,cV,co,cx}
3529 \cs_generate_variant:Nn \tl_gset:Nn {NV,No,Nv,cn,cx}

```

<pre> \tl_set_eq:NN \tl_set_eq:Nc \tl_set_eq:cN \tl_set_eq:cc \tl_gset_eq:NN \tl_gset_eq:Nc \tl_gset_eq:cN \tl_gset_eq:cc </pre>	<p>For setting token list variables equal to each other. First checking:</p> <pre> 3530 &lt;*check&gt; 3531 \cs_new_nopar:Npn \tl_set_eq:NN #1#2{ 3532   \chk_exist_cs:N #1 \cs_set_eq:NN #1#2 3533   \chk_local_or_pref_global:N #1 \chk_var_or_const:N #2 3534 } 3535 \cs_new_nopar:Npn \tl_gset_eq:NN #1#2{ 3536   \chk_exist_cs:N #1 \cs_gset_eq:NN #1#2 3537   \chk_global:N #1 \chk_var_or_const:N #2 3538 } 3539 &lt;/check&gt; </pre>
--	---

Non-checking versions are easy.

```

3540 <!*check>
3541 \cs_new_eq:NN \tl_set_eq:NN \cs_set_eq:NN
3542 \cs_new_eq:NN \tl_gset_eq:NN \cs_gset_eq:NN
3543 </!check>

```

The rest again with the expansion module.

```

3544 \cs_generate_variant:Nn \tl_set_eq:NN {Nc,c,cc}
3545 \cs_generate_variant:Nn \tl_gset_eq:NN {Nc,c,cc}

```

```

\tl_clear:N      Clearing a token list variable.
\tl_clear:c
\tl_gclear:N     3546 \cs_new_nopar:Npn \tl_clear:N #1{\tl_set_eq:NN #1\c_empty_tl}
\tl_gclear:c     3547 \cs_generate_variant:Nn \tl_clear:N {c}
                 3548 \cs_new_nopar:Npn \tl_gclear:N #1{\tl_gset_eq:NN #1\c_empty_tl}
                 3549 \cs_generate_variant:Nn \tl_gclear:N {c}

\tl_clear_new:N  These macros check whether a token list exists. If it does it is cleared, if it doesn't it is
\tl_clear_new:c  allocated.

                 3550 <*check>
                 3551 \cs_new_nopar:Npn \tl_clear_new:N #1{
                 3552   \chk_var_or_const:N #1
                 3553   \if_predicate:w \cs_if_exist_p:N #1
                 3554     \tl_clear:N #1
                 3555   \else:
                 3556     \tl_new:Nn #1{}
                 3557   \fi:
                 3558 }
                 3559 </check>
                 3560 <-check>\cs_new_eq:NN \tl_clear_new:N \tl_clear:N
                 3561 \cs_generate_variant:Nn \tl_clear_new:N {c}

\tl_gclear_new:N These are the global versions of the above.
\tl_gclear_new:c

                 3562 <*check>
                 3563 \cs_new_nopar:Npn \tl_gclear_new:N #1{
                 3564   \chk_var_or_const:N #1
                 3565   \if_predicate:w \cs_if_exist_p:N #1
                 3566     \tl_gclear:N #1
                 3567   \else:
                 3568     \tl_new:Nn #1{}
                 3569   \fi:}
                 3570 </check>
                 3571 <-check>\cs_new_eq:NN \tl_gclear_new:N \tl_gclear:N
                 3572 \cs_generate_variant:Nn \tl_gclear_new:N {c}

\tl_put_left:Nn  We can add tokens to the left (either globally or locally). It is not quite as easy as we
\tl_put_left:NV  would like because we have to ensure the assignments
\tl_put_left:No
\tl_put_left:Nx  \tl_set:Nn \l_tmpa_tl{##1abc##2def}
\tl_put_left:cn  \tl_set:Nn \l_tmpb_tl{##1abc}
\tl_put_left:cV  \tl_put_right:Nn \l_tmpb_tl {##2def}
\tl_put_left:co

\tl_gput_left:Nn cause \l_tmpa_tl and \l_tmpb_tl to be identical. The old code did not succeed in
\tl_gput_left:NV doing this (it gave an error) and so we use a different technique where the item(s) to be
\tl_gput_left:No added are first stored in a temporary variable and then added using an x type expansion
\tl_gput_left:Nx
\tl_gput_left:cn
\tl_gput_left:cV
\tl_gput_left:co

```

combined with the appropriate level of non-expansion. Putting the tokens directly into one assignment does not work unless we want full expansion. Note (according to the warning earlier) T<sub>E</sub>X does not allow us to treat #s the same in all cases. Tough.

```

3573 \cs_new:Npn \tl_put_left:Nn #1#2 {
3574   \tl_set:Nn \l_exp_tl {#2}
3575   \tl_set:Nx #1 { \exp_not:V \l_exp_tl \exp_not:V #1 }
3576   <check> \chk_local_or_pref_global:N #1
3577 }
3578 \cs_new:Npn \tl_put_left:NV #1#2 {
3579   \tl_set:Nx #1 { \exp_not:V #2 \exp_not:V #1 }
3580 }
3581 \cs_new:Npn \tl_put_left:No #1#2{
3582   \tl_set:No \l_exp_tl {#2}
3583   \tl_set:Nx #1 { \exp_not:V \l_exp_tl \exp_not:V #1 }
3584   <check> \chk_local_or_pref_global:N #1
3585 }
3586 \cs_new:Npn \tl_put_left:Nx #1#2{
3587   \tl_set:Nx #1 { #2 \exp_not:V #1 }
3588   <check> \chk_local_or_pref_global:N #1
3589 }
3590 \cs_new:Npn \tl_gput_left:Nn #1#2{
3591   \tl_set:Nn \l_exp_tl{#2}
3592   \tl_gset:Nx #1 { \exp_not:V \l_exp_tl \exp_not:V #1 }
3593   <check> \chk_local_or_pref_global:N #1
3594 }
3595 \cs_new:Npn \tl_gput_left:NV #1#2 {
3596   \tl_gset:Nx #1 { \exp_not:V #2 \exp_not:V #1 }
3597 }
3598 \cs_new:Npn \tl_gput_left:No #1#2{
3599   \tl_set:No \l_exp_tl {#2}
3600   \tl_gset:Nx #1 { \exp_not:V \l_exp_tl \exp_not:V #1 }
3601   <check> \chk_local_or_pref_global:N #1
3602 }
3603 \cs_new:Npn \tl_gput_left:Nx #1#2{
3604   \tl_gset:Nx #1 { #2 \exp_not:V #1 }
3605   <check> \chk_local_or_pref_global:N #1
3606 }
3607 \cs_generate_variant:Nn \tl_put_left:Nn {cn,co,cV}

3608 \cs_generate_variant:Nn \tl_gput_left:Nn {cn,co}
3609 \cs_generate_variant:Nn \tl_gput_left:NV {cV}

```

\tl\_put\_right:Nn  
\tl\_put\_right:NV  
\tl\_put\_right:No  
\tl\_put\_right:Nx  
\tl\_put\_right:cn  
\tl\_put\_right:cV  
\tl\_put\_right:co  
\tl\_gput\_right:Nn  
\tl\_gput\_right:NV  
\tl\_gput\_right:No  
\tl\_gput\_right:Nx  
\tl\_gput\_right:cn  
\tl\_gput\_right:cV  
\tl\_gput\_right:co

These are variants of the functions above, but for adding tokens to the right.

```

3610 \cs_new:Npn \tl_put_right:Nn #1#2 {
3611   \tl_set:Nn \l_exp_tl {#2}
3612   \tl_set:Nx #1 { \exp_not:V #1 \exp_not:V \l_exp_tl }
3613   <check> \chk_local_or_pref_global:N #1
3614 }

```



```

3615 \cs_new:Npn \tl_gput_right:Nn #1#2{
3616   \tl_set:Nn \l_exp_tl {#2}
3617   \tl_gset:Nx #1 { \exp_not:V #1 \exp_not:V \l_exp_tl }
3618   <check> \chk_local_or_pref_global:N #1
3619 }
3620 \cs_new:Npn \tl_put_right:NV #1#2 {
3621   \tl_set:Nx #1 { \exp_not:V #1 \exp_not:V #2 }
3622 }
3623 \cs_new:Npn \tl_put_right:No #1#2 {
3624   \tl_set:No \l_exp_tl {#2}
3625   \tl_set:Nx #1 { \exp_not:V #1 \exp_not:V \l_exp_tl }
3626   <check> \chk_local_or_pref_global:N #1
3627 }
3628 \cs_new:Npn \tl_gput_right:NV #1#2 {
3629   \tl_gset:Nx #1 { \exp_not:V #1 \exp_not:V #2 }
3630 }
3631 \cs_new:Npn \tl_gput_right:No #1#2 {
3632   \tl_set:No \l_exp_tl {#2}
3633   \tl_gset:Nx #1 { \exp_not:V #1 \exp_not:V \l_exp_tl }
3634   <check> \chk_local_or_pref_global:N #1
3635 }
3636 \cs_set:Npn \tl_put_right:Nx #1#2 {
3637   \tl_set:Nx #1 { \exp_not:V #1 #2 }
3638   <check> \chk_local_or_pref_global:N #1
3639 }
3640 \cs_set:Npn \tl_gput_right:Nx #1#2 {
3641   \tl_gset:Nx #1 { \exp_not:V #1 #2 }
3642   <check> \chk_local_or_pref_global:N #1
3643 }
3644 \cs_generate_variant:Nn \tl_put_right:Nn {cn,co}
3645 \cs_generate_variant:Nn \tl_put_right:NV {cV}
3646 \cs_generate_variant:Nn \tl_gput_right:Nn {cn,co,cV}

```

\tl\_gset:Nc These two functions are included because they are necessary in Denys' implementations.  
\tl\_set:Nc The :Nc convention (see the expansion module) is very unusual at first sight, but it works nicely over all modules, so we would like to keep it.

Construct a control sequence on the fly from #2 and save it in #1.

```

3647 \cs_new_nopar:Npn \tl_gset:Nc {
3648   <*check>
3649   \pref_global_chk:
3650   </check>
3651   <-check> \pref_global:D
3652   \tl_set:Nc}

```

\pref\_global\_chk: will turn the variable check in \tl\_set:No into a global check.

```

3653 \cs_new_nopar:Npn \tl_set:Nc #1#2{\tl_set:No #1{\cs:w#2\cs_end:}}

```

## 104.2 Variables and constants

`\c_job_name_tl` Inherited from the `expl3` name for the primitive.

```
3654 \tl_new:Nn \c_job_name_tl {\tex_jobname:D}
```

`\c_empty_tl` Two constants which are often used.

```
3655 \tl_new:Nn \c_empty_tl {}
```

`\g_tmpa_tl` Global temporary token list variables. They are supposed to be set and used immediately, with no delay between the definition and the use because you can't count on other macros not to redefine them from under you.

```
3656 \tl_new:Nn \g_tmpa_tl {}
```

```
3657 \tl_new:Nn \g_tmpb_tl {}
```

`\l_testa_tl` Global and local temporaries. These are the ones for test routines. This means that one can safely use other temporaries when calling test routines.

`\l_testb_tl`

`\g_testa_tl`

`\g_testb_tl`

```
3658 \tl_new:Nn \l_testa_tl {}
```

```
3659 \tl_new:Nn \l_testb_tl {}
```

```
3660 \tl_new:Nn \g_testa_tl {}
```

```
3661 \tl_new:Nn \g_testb_tl {}
```

`\l_tmpa_tl` These are local temporary token list variables.

`\l_tmpb_tl`

```
3662 \tl_new:Nn \l_tmpa_tl {}
```

```
3663 \tl_new:Nn \l_tmpb_tl {}
```

## 104.3 Predicates and conditionals

We also provide a few conditionals, both in expandable form (with `\c_true_bool`) and in ‘brace-form’, the latter are denoted by **TF** at the end, as explained elsewhere.

`\tl_if_empty_p:N` These functions check whether the token list in the argument is empty and execute the proper code from their argument(s).

`\tl_if_empty_p:c`

`\tl_if_empty:NTF`

`\tl_if_empty:cTF`

```
3664 \prg_set_conditional:Npnn \tl_if_empty:N #1 {p,TF,T,F} {
```

```
3665   \if_meaning:w #1 \c_empty_tl
```

```
3666   \prg_return_true: \else: \prg_return_false: \fi:
```

```
3667 }
```

```
3668 \cs_generate_variant:Nn \tl_if_empty_p:N {c}
```

```
3669 \cs_generate_variant:Nn \tl_if_empty:NTF {c}
```

```
3670 \cs_generate_variant:Nn \tl_if_empty:NT {c}
```

```
3671 \cs_generate_variant:Nn \tl_if_empty:NF {c}
```

\tl\_if\_eq\_p:NN Returns \c\_true\_bool iff the two token list variables are equal.

```

\tl_if_eq_p:Nc
\tl_if_eq_p:cN
\tl_if_eq_p:cc
\tl_if_eq:NNTF
\tl_if_eq:NcTF
\tl_if_eq:cNTF
\tl_if_eq:ccTF

```

```

3672 \prg_new_conditional:Npnn \tl_if_eq:NN #1#2 {p,TF,T,F} {
3673   \if_meaning:w #1 #2 \prg_return_true: \else: \prg_return_false: \fi:
3674 }
3675 \cs_generate_variant:Nn \tl_if_eq_p:NN {Nc,c,cc}
3676 \cs_generate_variant:Nn \tl_if_eq:NNTF {Nc,c,cc}
3677 \cs_generate_variant:Nn \tl_if_eq:NNT {Nc,c,cc}
3678 \cs_generate_variant:Nn \tl_if_eq:NNTF {Nc,c,cc}

```

\tl\_if\_empty\_p:n It would be tempting to just use \if\_meaning:w\q\_nil#1\q\_nil as a test since this works really well. However it fails on a token list starting with \q\_nil of course but more troubling is the case where argument is a complete conditional such as \if\_true: a \else: b \fi: because then \if\_true: is used by \if\_meaning:w, the test turns out false, the \else: executes the false branch, the \fi: ends it and the \q\_nil at the end starts executing... A safer route is to convert the entire token list into harmless characters first and then compare that. This way the test will even accept \q\_nil as the first token.

```

3679 \prg_new_conditional:Npnn \tl_if_empty:n #1 {p,TF,T,F} {
3680   \exp_after:wN \if_meaning:w \exp_after:wN \q_nil \tl_to_str:n {#1} \q_nil
3681   \prg_return_true: \else: \prg_return_false: \fi:
3682 }
3683 \cs_generate_variant:Nn \tl_if_empty_p:n {V}
3684 \cs_generate_variant:Nn \tl_if_empty:nTF {V}
3685 \cs_generate_variant:Nn \tl_if_empty:nT {V}
3686 \cs_generate_variant:Nn \tl_if_empty:nF {V}
3687 \cs_generate_variant:Nn \tl_if_empty_p:n {o}
3688 \cs_generate_variant:Nn \tl_if_empty:nTF {o}
3689 \cs_generate_variant:Nn \tl_if_empty:nT {o}
3690 \cs_generate_variant:Nn \tl_if_empty:nF {o}

```

\tl\_if\_blank\_p:n This is based on the answers in “Around the Bend No 2” but is safer as the tests listed there all have one small flaw: If the input in the test is two tokens with the same meaning as the internal delimiter, they will fail since one of them is mistaken for the actual delimiter. In our version below we make sure to pass the input through \tl\_to\_str:n which ensures that all the tokens are converted to catcode 12. However we use an a with catcode 11 as delimiter so we can *never* get into the same problem as the solutions in “Around the Bend No 2”.

```

3691 \prg_new_conditional:Npnn \tl_if_blank:n #1 {p,TF,T,F} {
3692   \exp_after:wN \tl_if_blank_p_aux:w \tl_to_str:n {#1} aa.\q_nil
3693 }
3694 \cs_new:Npn \tl_if_blank_p_aux:w #1#2 a #3#4 \q_nil {
3695   \if_meaning:w #3 #4 \prg_return_true: \else: \prg_return_false: \fi:
3696 }
3697 \cs_generate_variant:Nn \tl_if_blank_p:n {V}
3698 \cs_generate_variant:Nn \tl_if_blank:nTF {V}
3699 \cs_generate_variant:Nn \tl_if_blank:nT {V}

```

```

3700 \cs_generate_variant:Nn \tl_if_blank:nF {V}
3701 \cs_generate_variant:Nn \tl_if_blank_p:n {o}
3702 \cs_generate_variant:Nn \tl_if_blank:nTF {o}
3703 \cs_generate_variant:Nn \tl_if_blank:nT {o}
3704 \cs_generate_variant:Nn \tl_if_blank:nF {o}

```

\tl\_if\_eq:xxTF Test if two token lists are identical. pdfTeX contains a most interesting primitive for expandable string comparison so we make use of it if available. Presumably it will be in the final version.

\tl\_if\_eq:nnTF Firstly we give it an appropriate name. Note that this primitive actually performs an x type expansion but it is still expandable! Hence we must program these functions backwards to add \exp\_not:n. We provide the combinations for the types n, o and x.

```

\tl_if_eq:xxTF 3705 \cs_new_eq:NN \tl_compare:xx \pdf_strcmp:D
\tl_if_eq:nnTF 3706 \cs_new:Npn \tl_compare:nn #1#2{
\tl_if_eq:VVTF 3707   \tl_compare:xx{\exp_not:n{#1}}{\exp_not:n{#2}}
\tl_if_eq:ooTF 3708 }
\tl_if_eq:xnTF 3709 \cs_new:Npn \tl_compare:nx #1{
\tl_if_eq:nxTF 3710   \tl_compare:xx{\exp_not:n{#1}}
\tl_if_eq:onTF 3711 }
\tl_if_eq:noTF 3712 \cs_new:Npn \tl_compare:xn #1#2{
\tl_if_eq_p:xx 3713   \tl_compare:xx{#1}{\exp_not:n{#2}}
\tl_if_eq_p:nn 3714 }
\tl_if_eq_p:VV 3715 \cs_new:Npn \tl_compare:nV #1#2 {
\tl_if_eq_p:oo 3716   \tl_compare:xx { \exp_not:n {#1} } { \exp_not:V #2 }
\tl_if_eq_p:xn 3717 }
\tl_if_eq_p:nx 3718 \cs_new:Npn \tl_compare:no #1#2{
\tl_if_eq_p:Vn 3719   \tl_compare:xx{\exp_not:n{#1}}{\exp_not:n\exp_after:wN{#2}}
\tl_if_eq_p:on 3720 }
\tl_if_eq_p:nV 3721 \cs_new:Npn \tl_compare:Vn #1#2 {
\tl_if_eq_p:no 3722   \tl_compare:xx { \exp_not:V #1 } { \exp_not:n {#2} }
\tl_if_eq_p:xV 3723 }
\tl_if_eq_p:Vx 3724 \cs_new:Npn \tl_compare:on #1#2{
\tl_if_eq_p:xo 3725   \tl_compare:xx{\exp_not:n\exp_after:wN{#1}}{\exp_not:n{#2}}
\tl_if_eq_p:ox 3726 }
3727 \cs_new:Npn \tl_compare:VV #1#2 {
3728   \tl_compare:xx { \exp_not:V #1 } { \exp_not:V #2 }
3729 }
3730 \cs_new:Npn \tl_compare:oo #1#2{
3731   \tl_compare:xx{\exp_not:n\exp_after:wN{#1}}{\exp_not:n\exp_after:wN{#2}}
3732 }
3733 \cs_new:Npn \tl_compare:xV #1#2 {
3734   \tl_compare:xx {#1} { \exp_not:V #2 }
3735 }
3736 \cs_new:Npn \tl_compare:xo #1#2{
3737   \tl_compare:xx{#1}{\exp_not:n\exp_after:wN{#2}}
3738 }
3739 \cs_new:Npn \tl_compare:Vx #1#2 {
3740   \tl_compare:xx { \exp_not:V #1 } {#2}

```

```

3741 }
3742 \cs_new:Npn \tl_compare:ox #1#2{
3743   \tl_compare:xx{\exp_not:n\exp_after:wN{#1}}{#2}
3744 }

```

Since we have a lot of basically identical functions to define we define one to define the rest. Unfortunately we aren't quite set up to use the new `\tl_map_inline:nn` function yet.

```

3745 \cs_set_nopar:Npn \tl_tmp:w #1 {
3746   \tl_set:Nx \l_tmpa_tl {
3747     \exp_not:N \prg_new_conditional:Npnn \exp_not:c {tl_if_eq:#1}
3748       #####1 #####2 {p,TF,T,F} {
3749         \exp_not:N \tex_ifnum:D
3750         \exp_not:c {tl_compare:#1} {#####1}{#####2}
3751         \exp_not:n{ =\c_zero \prg_return_true: \else: \prg_return_false: \fi: }
3752       }
3753   }
3754   \l_tmpa_tl
3755 }
3756 \tl_tmp:w{xx} \tl_tmp:w{nx} \tl_tmp:w{ox} \tl_tmp:w{Vx}
3757 \tl_tmp:w{xn} \tl_tmp:w{nn} \tl_tmp:w{on} \tl_tmp:w{Vn}
3758 \tl_tmp:w{xo} \tl_tmp:w{no} \tl_tmp:w{oo}
3759 \tl_tmp:w{xV} \tl_tmp:w{nV} \tl_tmp:w{VV}

```

However all of this only makes sense if we actually have that primitive. Therefore we disable it again if it is not there and define `\tl_if_eq:nn` the old fashioned (and unexpandable) way.

In some cases below, since arbitrary token lists could be being used in this function, you can't assume (as token list variables usually do) that there won't be any `#` tokens. Therefore, `\tl_set:Nx` and `\exp_not:n` is used instead of plain `\tl_set:Nn`.

```

3760 \cs_if_exist:cF{pdf_strcmp:D}{
3761   \prg_set_protected_conditional:Npnn \tl_if_eq:nn #1#2 {TF,T,F} {
3762     \tl_set:Nx \l_testa_tl {\exp_not:n{#1}}
3763     \tl_set:Nx \l_testb_tl {\exp_not:n{#2}}
3764     \if_meaning:w\l_testa_tl \l_testb_tl
3765       \prg_return_true: \else: \prg_return_false:
3766     \fi:
3767   }
3768   \prg_set_protected_conditional:Npnn \tl_if_eq:nV #1#2 {TF,T,F} {
3769     \tl_set:Nx \l_testa_tl { \exp_not:n {#1} }
3770     \tl_set:Nx \l_testb_tl { \exp_not:V #2 }
3771     \if_meaning:w \l_testa_tl \l_testb_tl
3772       \prg_return_true: \else: \prg_return_false:
3773     \fi:
3774   }
3775   \prg_set_protected_conditional:Npnn \tl_if_eq:no #1#2 {TF,T,F} {
3776     \tl_set:Nx \l_testa_tl {\exp_not:n{#1}}

```

```

3777     \tl_set:Nx \l_testb_tl {\exp_not:o{#2}}
3778     \if_meaning:w\l_testa_tl \l_testb_tl
3779         \prg_return_true: \else: \prg_return_false:
3780     \fi:
3781 }
3782 \prg_set_protected_conditional:Npnn \tl_if_eq:nx #1#2 {TF,T,F} {
3783     \tl_set:Nx \l_testa_tl {\exp_not:n{#1}}
3784     \tl_set:Nx \l_testb_tl {#2}
3785     \if_meaning:w\l_testa_tl \l_testb_tl
3786         \prg_return_true: \else: \prg_return_false:
3787     \fi:
3788 }
3789 \prg_set_protected_conditional:Npnn \tl_if_eq:Vn #1#2 {TF,T,F} {
3790     \tl_set:Nx \l_testa_tl { \exp_not:V #1 }
3791     \tl_set:Nx \l_testb_tl { \exp_not:n{#2} }
3792     \if_meaning:w \l_testa_tl \l_testb_tl
3793         \prg_return_true: \else: \prg_return_false:
3794     \fi:
3795 }
3796 \prg_set_protected_conditional:Npnn \tl_if_eq:on #1#2 {TF,T,F} {
3797     \tl_set:Nx \l_testa_tl {\exp_not:o{#1}}
3798     \tl_set:Nx \l_testb_tl {\exp_not:n{#2}}
3799     \if_meaning:w\l_testa_tl \l_testb_tl
3800         \prg_return_true: \else: \prg_return_false:
3801     \fi:
3802 }
3803 \prg_set_protected_conditional:Npnn \tl_if_eq:VV #1#2 {TF,T,F} {
3804     \tl_set:Nx \l_testa_tl { \exp_not:V #1 }
3805     \tl_set:Nx \l_testb_tl { \exp_not:V #2 }
3806     \if_meaning:w \l_testa_tl \l_testb_tl
3807         \prg_return_true: \else: \prg_return_false:
3808     \fi:
3809 }
3810 \prg_set_protected_conditional:Npnn \tl_if_eq:oo #1#2 {TF,T,F} {
3811     \tl_set:Nx \l_testa_tl {\exp_not:o{#1}}
3812     \tl_set:Nx \l_testb_tl {\exp_not:o{#2}}
3813     \if_meaning:w\l_testa_tl \l_testb_tl
3814         \prg_return_true: \else: \prg_return_false:
3815     \fi:
3816 }
3817 \prg_set_protected_conditional:Npnn \tl_if_eq:Vx #1#2 {TF,T,F} {
3818     \tl_set:Nx \l_testa_tl { \exp_not:V #1 }
3819     \tl_set:Nx \l_testb_tl {#2}
3820     \if_meaning:w \l_testa_tl \l_testb_tl
3821         \prg_return_true: \else: \prg_return_false:
3822     \fi:
3823 }
3824 \prg_set_protected_conditional:Npnn \tl_if_eq:ox #1#2 {TF,T,F} {
3825     \tl_set:Nx \l_testa_tl {\exp_not:o{#1}}
3826     \tl_set:Nx \l_testb_tl {#2}

```

```

3827 \if_meaning:w\l_testa_tl \l_testb_tl
3828 \prg_return_true: \else: \prg_return_false:
3829 \fi:
3830 }
3831 \prg_set_protected_conditional:Npnn \tl_if_eq:xn #1#2 {TF,T,F} {
3832 \tl_set:Nx \l_testa_tl {#1}
3833 \tl_set:Nx \l_testb_tl {\exp_not:n{#2}}
3834 \if_meaning:w\l_testa_tl \l_testb_tl
3835 \prg_return_true: \else: \prg_return_false:
3836 \fi:
3837 }
3838 \prg_set_protected_conditional:Npnn \tl_if_eq:xV #1#2 {TF,T,F} {
3839 \tl_set:Nx \l_testa_tl {#1}
3840 \tl_set:Nx \l_testb_tl { \exp_not:V #2 }
3841 \if_meaning:w \l_testa_tl \l_testb_tl
3842 \prg_return_true: \else: \prg_return_false:
3843 \fi:
3844 }
3845 \prg_set_protected_conditional:Npnn \tl_if_eq:xo #1#2 {TF,T,F} {
3846 \tl_set:Nx \l_testa_tl {#1}
3847 \tl_set:Nx \l_testb_tl {\exp_not:o{#2}}
3848 \if_meaning:w\l_testa_tl \l_testb_tl
3849 \prg_return_true: \else: \prg_return_false:
3850 \fi:
3851 }
3852 \prg_set_protected_conditional:Npnn \tl_if_eq:xx #1#2 {TF,T,F} {
3853 \tl_set:Nx \l_testa_tl {#1}
3854 \tl_set:Nx \l_testb_tl {#2}
3855 \if_meaning:w\l_testa_tl \l_testb_tl
3856 \prg_return_true: \else: \prg_return_false:
3857 \fi:
3858 }
3859 }

```

## 104.4 Working with the contents of token lists

`\tl_to_lowercase:n` Just some names for a few primitives.

`\tl_to_uppercase:n`

```
3860 \cs_new_eq:NN \tl_to_lowercase:n \tex_lowercase:D
```

```
3861 \cs_new_eq:NN \tl_to_uppercase:n \tex_uppercase:D
```

`\tl_to_str:n` Another name for a primitive.

```
3862 \cs_new_eq:NN \tl_to_str:n \etex_detokenize:D
```

`\tl_to_str:N` These functions return the replacement text of a token list as a string list with all characters catcoded to ‘other’.

`\tl_to_str:c`

`\tl_to_str_aux:w`

```

3863 \cs_new_nopar:Npn \tl_to_str:N {\exp_after:wN\tl_to_str_aux:w
3864   \token_to_meaning:N}
3865 \cs_new_nopar:Npn \tl_to_str_aux:w #1>{\}
3866 \cs_generate_variant:Nn \tl_to_str:N {c}

```

`\tl_map_function:nn` Expandable loop macro for token lists. These have the advantage of not needing to test if the argument is empty, because if it is, the stop marker will be read immediately and the loop terminated.  
`\tl_map_function:NN`  
`\tl_map_function:cN`

`\tl_map_function_aux:NN`

```

3867 \cs_new:Npn \tl_map_function:nn #1#2{
3868   \tl_map_function_aux:Nn #2 #1 \q_recursion_tail \q_recursion_stop
3869 }
3870 \cs_new_nopar:Npn \tl_map_function:NN #1#2{
3871   \exp_after:wN \tl_map_function_aux:Nn
3872   \exp_after:wN #2 #1 \q_recursion_tail \q_recursion_stop
3873 }
3874 \cs_new:Npn \tl_map_function_aux:Nn #1#2{
3875   \quark_if_recursion_tail_stop:n{#2}
3876   #1{#2} \tl_map_function_aux:Nn #1
3877 }
3878 \cs_generate_variant:Nn \tl_map_function:NN {cN}

```

`\tl_map_inline:nn` The inline functions are straight forward by now. We use a little trick with the counter `\g_tl_inline_level_int` to make them nestable. We can also make use of `\tl_map_function:Nn` from before.  
`\tl_map_inline:Nn`  
`\tl_map_inline:cn`

`\tl_map_inline_aux:n`  
`\g_tl_inline_level_int`

```

3879 \cs_new:Npn \tl_map_inline:nn #1#2{
3880   \int_gincr:N \g_tl_inline_level_int
3881   \cs_gset:cpn {tl_map_inline_ \int_use:N \g_tl_inline_level_int :n}
3882   ##1{#2}
3883   \exp_args:Nc \tl_map_function_aux:Nn
3884   {tl_map_inline_ \int_use:N \g_tl_inline_level_int :n}
3885   #1 \q_recursion_tail\q_recursion_stop
3886   \int_gdecr:N \g_tl_inline_level_int
3887 }
3888 \cs_new:Npn \tl_map_inline:Nn #1#2{
3889   \int_gincr:N \g_tl_inline_level_int
3890   \cs_gset:cpn {tl_map_inline_ \int_use:N \g_tl_inline_level_int :n}
3891   ##1{#2}
3892   \exp_last_unbraced:NcV \tl_map_function_aux:Nn
3893   {tl_map_inline_ \int_use:N \g_tl_inline_level_int :n}
3894   #1 \q_recursion_tail\q_recursion_stop
3895   \int_gdecr:N \g_tl_inline_level_int
3896 }
3897 \cs_generate_variant:Nn \tl_map_inline:Nn {c}

```

`\tl_map_variable:nnNn` `\tl_map_variable:nnNn`  $\langle token\ list \rangle$   $\langle temp \rangle$   $\langle action \rangle$  assigns  $\langle temp \rangle$  to each element and executes  $\langle action \rangle$ .  
`\tl_map_variable:NNn`  
`\tl_map_variable:cNn`



```

3898 \cs_new:Npn \tl_map_variable:nNn #1#2#3{
3899   \tl_map_variable_aux:Nnn #2 {#3} #1 \q_recursion_tail \q_recursion_stop
3900 }

```

Next really has to be v/V args

```

3901 \cs_new_nopar:Npn \tl_map_variable:NNn {\exp_args:No \tl_map_variable:nNn}
3902 \cs_generate_variant:Nn \tl_map_variable:NNn {c}

```

`\tl_map_variable_aux:NnN` The general loop. Assign the temp variable #1 to the current item #3 and then check if that's the stop marker. If it is, break the loop. If not, execute the action #2 and continue.

```

3903 \cs_new:Npn \tl_map_variable_aux:Nnn #1#2#3{
3904   \tl_set:Nn #1{#3}
3905   \quark_if_recursion_tail_stop:N #1
3906   #2 \tl_map_variable_aux:Nnn #1{#2}
3907 }

```

`\tl_map_break:` The break statement.

```

3908 \cs_new_eq:NN \tl_map_break: \use_none_delimit_by_q_recursion_stop:w

```

`\tl_reverse:n` Reversal of a token list is done by taking one token at a time and putting it in front of the ones before it.

`\tl_reverse:V`  
`\tl_reverse:o`

```

\tl_reverse_aux:nN 3909 \cs_new:Npn \tl_reverse:n #1{
3910   \tl_reverse_aux:nN {} #1 \q_recursion_tail\q_recursion_stop
3911 }
3912 \cs_new:Npn \tl_reverse_aux:nN #1#2{
3913   \quark_if_recursion_tail_stop_do:nn {#2}{ #1 }
3914   \tl_reverse_aux:nN {#2#1}
3915 }
3916 \cs_generate_variant:Nn \tl_reverse:n {V,o}

```

`\tl_reverse:N` This reverses the list, leaving `\exp_stop_f:` in front, which in turn is removed by the `f` expansion which comes to a halt.

```

3917 \cs_new_nopar:Npn \tl_reverse:N #1 {
3918   \tl_set:Nf #1 { \tl_reverse:o { #1 \exp_stop_f: } }
3919 }

```

`\tl_elt_count:n` Count number of elements within a token list or token list variable. Brace groups within the list are read as a single element. `\num_elt_count:n` grabs the element and replaces it by +1. The 0 to ensure it works on an empty list.

`\tl_elt_count:V`  
`\tl_elt_count:o`  
`\tl_elt_count:N`

```

3920 \cs_new:Npn \tl_elt_count:n #1{
3921   \intexpr_eval:n {
3922     \tl_map_function:nN {#1}\num_elt_count:n
3923   }

```

```

3924 }
3925 \cs_generate_variant:Nn \tl_elt_count:n {V,o}
3926 \cs_new_nopar:Npn \tl_elt_count:N #1{
3927   \intexpr_eval:n {
3928     \tl_map_function:NN #1 \num_elt_count:n
3929   }
3930 }

```

`\tl_set_rescan:Nnn` These functions store the  $\{\langle token\ list\rangle\}$  in  $\langle tl\ var.\rangle$  after redefining catcodes, etc., in  
`\tl_gset_rescan:Nnn` argument #2.

```

#1 :  $\langle tl\ var.\rangle$ 
#2 :  $\{\langle catcode\ setup,\ etc.\rangle\}$ 
#3 :  $\{\langle token\ list\rangle\}$ 

```

```

3931 \cs_new:Npn \tl_set_rescan:Nnn { \tl_set_rescan_aux:NNnn \tl_set:Nn }
3932 \cs_new:Npn \tl_gset_rescan:Nnn { \tl_set_rescan_aux:NNnn \tl_gset:Nn }

```

`\tl_set_rescan_aux:NNnn` This macro uses a trick to extract an unexpanded token list after it's rescanned with `\etex_scantokens:D`. This technique was first used (as far as I know) by Heiko Oberdiek in his `catchfile` package, albeit for real files rather than the ‘fake’ `\scantokens` one.

The basic problem arises because `\etex_scantokens:D` emulates a file read, which inserts an EOF marker into the expansion; the simplistic

```
\exp_args:NNo \cs_set:Npn \tmp:w { \etex_scantokens:D {some text} }
```

unfortunately doesn't work, calling the error:

```
! File ended while scanning definition of \tmp:w.
```

(LuaTeX works around this problem with its `\scantextokens` primitive.)

Usually, we'd define `\etex_everyeof:D` to be `\exp_not:N` to gobble the EOF marker, but since we're not expanding the token list, it gets left in there and we have the same basic problem.

Instead, we define `\etex_everyeof:D` to contain a marker that's impossible to occur within the scanned text; that is, the same char twice with different catcodes. (For some reason, we *don't* need to insert a `\exp_not:N` token after it to prevent the EOF marker to expand. Anyone know why?)

A helper function is can be used to save the token list delimited by the special marker, keeping the catcode redefinitions hidden away in a group.

`\c_two_ats_with_two_catcodes_tl` A tl with two @ characters with two different catcodes. Used as a special marker for delimited text.

```

3933 \group_begin:
3934   \tex_lccode:D '\A = '\@ \scan_stop:
3935   \tex_lccode:D '\B = '\@ \scan_stop:
3936   \tex_catcode:D '\A = 8 \scan_stop:
3937   \tex_catcode:D '\B = 3 \scan_stop:

```

```

3938 \tl_to_lowercase:n {
3939   \group_end:
3940   \tl_new:Nn \c_two_ats_with_two_catcodes_tl {AB}
3941 }

```

```

#1 : \tl_set function
#2 : <tl var.>
#3 : {<catcode setup, etc.>}
#4 : {<token list>}

```

Note that if you change `\etex_everyeof:D` in #3 then you'd better do it correctly!

```

3942 \cs_new:Npn \tl_set_rescan_aux:NNnn #1#2#3#4 {
3943   \group_begin:
3944   \toks_set:NV \etex_everyeof:D \c_two_ats_with_two_catcodes_tl
3945   \tex_endlinechar:D = \c_minus_one
3946   #3
3947   \exp_after:wN \tl_rescan_aux:w \etex_scantokens:D {#4}
3948   \exp_args:NNNV
3949   \group_end:
3950   #1 #2 \l_tmpa_toks
3951 }

```

`\tl_rescan_aux:w`

```

3952 \exp_after:wN \cs_set:Npn
3953 \exp_after:wN \tl_rescan_aux:w
3954 \exp_after:wN #
3955 \exp_after:wN 1 \c_two_ats_with_two_catcodes_tl {
3956   \tl_set:Nn \l_tmpa_toks {#1}
3957 }

```

`\tl_set_rescan:Nnx` These functions store the full expansion of `{<token list>}` in `<tl var.>` after redefining  
`\tl_gset_rescan:Nnx` catcodes, etc., in argument #2.

```

#1 : <tl var.>
#2 : {<catcode setup, etc.>}
#3 : {<token list>}

```

The expanded versions are much simpler because the `\etex_scantokens:D` can occur within the expansion.

```

3958 \cs_new:Npn \tl_set_rescan:Nnx #1#2#3 {
3959   \group_begin:
3960   \etex_everyeof:D { \exp_not:N }
3961   \tex_endlinechar:D = \c_minus_one
3962   #2
3963   \tl_set:Nx \l_tmpa_tl { \etex_scantokens:D {#3} }
3964   \exp_args:NNNV
3965   \group_end:
3966   \tl_set:Nn #1 \l_tmpa_tl
3967 }

```

Globally is easier again:

```

3968 \cs_new:Npn \tl_gset_rescan:Nnx #1#2#3 {
3969   \group_begin:
3970     \etex_everyeof:D { \exp_not:N }
3971     \tex_endlinechar:D = \c_minus_one
3972     #2
3973     \tl_gset:Nx #1 { \etex_scantokens:D {#3} }
3974   \group_end:
3975 }

```

`\tl_rescan:nn` The inline wrapper for `\etex_scantokens:D`.

**#1** : Catcode changes (etc.)

**#2** : Token list to re-tokenise

```

3976 \cs_new:Npn \tl_rescan:nn #1#2 {
3977   \group_begin:
3978     \toks_set:NV \etex_everyeof:D \c_two_at_with_two_catcodes_tl
3979     \tex_endlinechar:D = \c_minus_one
3980     #1
3981     \exp_after:wN \tl_rescan_aux:w \etex_scantokens:D {#2}
3982   \exp_args:NV \group_end:
3983   \l_tmpa_toks
3984 }

```

## 104.5 Checking for and replacing tokens

`\tl_if_in:NnTF` See the replace functions for further comments. In this part we don't care too much about brace stripping since we are not interested in passing on the tokens which are split off in the process.

`\tl_if_in:cnTF`

```

3985 \prg_new_protected_conditional:Npnn \tl_if_in:Nn #1#2 {TF,T,F} {
3986   \cs_set:Npn \tl_tmp:w ##1 #2 ##2 \q_stop {
3987     \quark_if_no_value:nTF {##2} {\prg_return_false:} {\prg_return_true:}
3988   }
3989   \exp_after:wN \tl_tmp:w #1 #2 \q_no_value \q_stop
3990 }
3991 \cs_generate_variant:Nn \tl_if_in:NnTF {c}
3992 \cs_generate_variant:Nn \tl_if_in:NnT {c}
3993 \cs_generate_variant:Nn \tl_if_in:NnF {c}

```

`\tl_if_in:nnTF`

`\tl_if_in:VnTF`

`\tl_if_in:onTF`

```

3994 \prg_new_protected_conditional:Npnn \tl_if_in:nn #1#2 {TF,T,F} {
3995   \cs_set:Npn \tl_tmp:w ##1 #2 ##2 \q_stop {
3996     \quark_if_no_value:nTF {##2} {\prg_return_false:} {\prg_return_true:}
3997   }

```

```

3998 \tl_tmp:w #1 #2 \q_no_value \q_stop
3999 }
4000 \cs_generate_variant:Nn \tl_if_in:nnTF {V}
4001 \cs_generate_variant:Nn \tl_if_in:nnT {V}
4002 \cs_generate_variant:Nn \tl_if_in:nnF {V}
4003 \cs_generate_variant:Nn \tl_if_in:nnTF {o}
4004 \cs_generate_variant:Nn \tl_if_in:nnT {o}
4005 \cs_generate_variant:Nn \tl_if_in:nnF {o}

```

`\l_tl_replace_toks` A temp variable for the replace operations.

```

4006 %%\l_tl_replace_toks % moved to l3token as alloc not set up yet.

```

`\tl_replace_in:Nnn` Replacing the first item in a token list variable goes like this: Define a temporary function with delimited arguments containing the search term and take a closer look at what is left. We append the expansion of the token list with the search term plus the quark `\q_no_value`. If the search term isn't present this last one is found and the following token is the quark, so we test for that. If the search term is present we will have to split off the `#3\q_no_value` we had, so we define yet another function with delimited arguments to do this. The advantage here is that now we have a special end sequence so there is no problem if the search term appears more than once. Only problem left is to prevent brace stripping in both ends, so we prepend the expansion of the token list with `\prg_do_nothing:` later to be expanded and also prepend the remainder of the first split operation with `\prg_do_nothing:` also to be expanded again later on.

```

\tl_replace_in_aux:NNnn #1 : \tl_set:Nx or \tl_gset:Nx
#2 : <tl var.>
#3 : item to find
#4 : replacement text

4007 \cs_new:Npn \tl_replace_in_aux:NNnn #1#2#3#4{
4008   \cs_set:Npn \tl_tmp:w ##1#3##2\q_stop{
4009     \quark_if_no_value:nF{##2}
4010     {

```

At this point `##1` starts with a `\prg_do_nothing:` so we expand it to remove it.

```

4011   \toks_set:No\l_tl_replace_toks{##1#4}
4012   \cs_set:Npn \tl_tmp:w ###1#3\q_no_value{
4013     \toks_put_right:No \l_tl_replace_toks { ###1 }
4014   }
4015   \tl_tmp:w \prg_do_nothing: ##2

```

Now all that is done is setting the token list variable equal to the expansion of the token register.

```

4016   #1#2{\toks_use:N\l_tl_replace_toks}
4017 }
4018 }

```

Here is where we start the process. Note that the token list might start with a space token so we use this little trick with `\use:n` to prevent it from being removed.

```
4019 \use:n{\exp_after:wN \tl_tmp:w\exp_after:wN\prg_do_nothing:}
4020 #2#3 \q_no_value\q_stop
4021 }
```

Now the various versions doing the replacement either globally or locally.

```
4022 \cs_new_nopar:Npn \tl_replace_in:Nnn {\tl_replace_in_aux:NNnn \tl_set:Nx}
4023 \cs_generate_variant:Nn\tl_replace_in:Nnn {cnn}

4024 \cs_new_nopar:Npn \tl_greplace_in:Nnn {\tl_replace_in_aux:NNnn \tl_gset:Nx}
4025 \cs_generate_variant:Nn\tl_greplace_in:Nnn {cnn}
```

The version for replacing *all* occurrences of the search term is fairly easy since we just have to keep doing the replacement on the split-off part until all are replaced. Otherwise it is pretty much the same as above.

```
\tl_replace_all_in:Nnn
\tl_replace_all_in:cnn
\tl_greplace_all_in:Nnn
\tl_greplace_all_in:cnn
\tl_replace_all_in_aux:NNnn
4026 \cs_set:Npn \tl_replace_all_in_aux:NNnn #1#2#3#4{
4027   \toks_clear:N \l_tl_replace_toks
4028   \cs_set:Npn \tl_tmp:w ##1#3##2\q_stop{
4029     \quark_if_no_value:nTF{##2}
4030     {
4031       \toks_put_right:No \l_tl_replace_toks {##1}
4032     }
4033     {
4034       \toks_put_right:No \l_tl_replace_toks {##1 #4}
4035       \tl_tmp:w \prg_do_nothing: ##2 \q_stop
4036     }
4037   }
4038   \use:n{\exp_after:wN \tl_tmp:w \exp_after:wN \prg_do_nothing:}
4039   #2#3 \q_no_value\q_stop
4040   #1#2{\toks_use:N\l_tl_replace_toks}
4041 }
```

Now the various forms.

```
4042 \cs_new_nopar:Npn \tl_replace_all_in:Nnn {
4043   \tl_replace_all_in_aux:NNnn \tl_set:Nx}
4044 \cs_generate_variant:Nn \tl_replace_all_in:Nnn {cnn}

4045 \cs_new_nopar:Npn \tl_greplace_all_in:Nnn {
4046   \tl_replace_all_in_aux:NNnn \tl_gset:Nx}
4047 \cs_generate_variant:Nn \tl_greplace_all_in:Nnn {cnn}
```

Next comes a series of removal functions. I have just implemented them as subcases of the replace functions for now (I'm lazy).

```
\tl_remove_in:Nn
\tl_remove_in:cn
\tl_gremove_in:Nn
\tl_gremove_in:cn
4048 \cs_new:Npn \tl_remove_in:Nn #1#2{\tl_replace_in:Nnn #1{#2}{}}
```

```

4049 \cs_new:Npn \tl_gremove_in:Nn #1#2{\tl_greplace_in:Nnn #1{#2}{}}
4050 \cs_generate_variant:Nn \tl_remove_in:Nn {cn}
4051 \cs_generate_variant:Nn \tl_gremove_in:Nn {cn}

```

\tl\_remove\_all\_in:Nn Same old, same old.

```

\tl_remove_all_in:cn
\tl_remove_all_in:cn
\tl_gremove_all_in:Nn
\tl_gremove_all_in:cn
4052 \cs_new:Npn \tl_remove_all_in:Nn #1#2{
4053   \tl_replace_all_in:Nnn #1{#2}{}}
4054 }
4055 \cs_new:Npn \tl_gremove_all_in:Nn #1#2{
4056   \tl_greplace_all_in:Nnn #1{#2}{}}
4057 }
4058 \cs_generate_variant:Nn \tl_remove_all_in:Nn {cn}
4059 \cs_generate_variant:Nn \tl_gremove_all_in:Nn {cn}

```

## 104.6 Heads or tails?

\tl\_head:n These functions pick up either the head or the tail of a list. \tl\_head\_iii:n returns the first three items on a list.

```

\tl_head:n
\tl_head:V
\tl_head_i:n
\tl_tail:n
\tl_tail:V
\tl_tail:f
\tl_head_iii:n
\tl_head_iii:f
\tl_head:w
\tl_head_i:w
\tl_tail:w
\tl_head_iii:w
4060 \cs_new:Npn \tl_head:n #1{\tl_head:w #1\q_nil}
4061 \cs_new_eq:NN \tl_head_i:n \tl_head:n
4062 \cs_new:Npn \tl_tail:n #1{\tl_tail:w #1\q_nil}
4063 \cs_generate_variant:Nn \tl_tail:n {f}
4064 \cs_new:Npn \tl_head_iii:n #1{\tl_head_iii:w #1\q_nil}
4065 \cs_generate_variant:Nn \tl_head_iii:n {f}
4066 \cs_new_eq:NN \tl_head:w \use_i_delimit_by_q_nil:nw
4067 \cs_new_eq:NN \tl_head_i:w \tl_head:w
4068 \cs_new:Npn \tl_tail:w #1#2\q_nil{#2}
4069 \cs_new:Npn \tl_head_iii:w #1#2#3#4\q_nil{#1#2#3}
4070 \cs_generate_variant:Nn \tl_head:n { V }
4071 \cs_generate_variant:Nn \tl_tail:n { V }

```

\tl\_if\_head\_eq\_meaning\_p:nN When we want to check if the first token of a list equals something specific it is usually either to see if it is a control sequence or a character. Hence we make two different functions as the internal test is different. \tl\_if\_head\_meaning\_eq:nNTF uses \if\_meaning:w and will consider the tokens  $b_{11}$  and  $b_{12}$  different. \tl\_if\_head\_char\_eq:nNTF on the other hand only compares character codes so would regard  $b_{11}$  and  $b_{12}$  as equal but would also regard two primitives as equal.

```

\tl_if_head_eq_meaning_p:nN
\tl_if_head_eq_meaning:nNTF
\tl_if_head_eq_charcode_p:nN
\tl_if_head_eq_charcode_p:fN
\tl_if_head_eq_charcode:nNTF
\tl_if_head_eq_charcode:fNTF
\tl_if_head_eq_catcode_p:nN
\tl_if_head_eq_catcode:nNTF
4072 \prg_new_conditional:Npnn \tl_if_head_eq_meaning:nN #1#2 {p,TF,T,F} {
4073   \exp_after:wN \if_meaning:w \tl_head:w #1 \q_nil #2
4074   \prg_return_true: \else: \prg_return_false: \fi:
4075 }

```

For the charcode and catcode versions we insert \exp\_not:N in front of both tokens. If you need them to expand fully as TeX does itself with these you can use an f type expansion.

```

4076 \prg_new_conditional:Npnn \tl_if_head_eq_charcode:nN #1#2 {p,TF,T,F} {
4077   \exp_after:wN \if:w \exp_after:wN \exp_not:N
4078     \tl_head:w #1 \q_nil \exp_not:N #2
4079   \prg_return_true: \else: \prg_return_false: \fi:
4080 }

```

Actually the default is already an f type expansion.

```

4081 %% \cs_new:Npn \tl_if_head_eq_charcode_p:fN #1#2{
4082 %%   \exp_after:wN\if_charcode:w \tl_head:w #1\q_nil\exp_not:N#2
4083 %%   \c_true_bool
4084 %%   \else:
4085 %%   \c_false_bool
4086 %%   \fi:
4087 %% }
4088 %% \def_long_test_function_new:npn {tl_if_head_eq_charcode:fN}#1#2{
4089 %%   \if_predicate:w \tl_if_head_eq_charcode_p:fN {#1}#2}

```

These :fN variants are broken; temporary patch:

```

4090 \cs_generate_variant:Nn \tl_if_head_eq_charcode_p:nN {f}
4091 \cs_generate_variant:Nn \tl_if_head_eq_charcode:nNTF {f}
4092 \cs_generate_variant:Nn \tl_if_head_eq_charcode:nNT {f}
4093 \cs_generate_variant:Nn \tl_if_head_eq_charcode:nNF {f}

```

And now catcodes:

```

4094 \prg_new_conditional:Npnn \tl_if_head_eq_catcode:nN #1#2 {p,TF,T,F} {
4095   \exp_after:wN \if_catcode:w \exp_after:wN \exp_not:N
4096     \tl_head:w #1 \q_nil \exp_not:N #2
4097   \prg_return_true: \else: \prg_return_false: \fi:
4098 }

```

Show token usage:

```

4099 <*showmemory>
4100 \showMemUsage
4101 </showmemory>

```

## 105 l3toks implementation

We start by ensuring that the required packages are loaded.

```

4102 <*package>
4103 \ProvidesExplPackage
4104   {\filename}{\filedate}{\fileversion}{\filedescription}
4105 \package_check_loaded_expl:
4106 </package>
4107 <*initex | package>

```



## 105.1 Allocation and use

`\toks_new:N` Allocates a new token register.

```
\toks_new:c
4108 \<initex>
4109 \alloc_setup_type:nnn {toks} \c_zero \c_max_register_num
4110 \cs_new_nopar:Npn \toks_new:N #1 { \alloc_reg:NnNN g {toks} \tex_toksdef:D #1 }
4111 \cs_new_nopar:Npn \toks_new_l:N #1 { \alloc_reg:NnNN l {toks} \tex_toksdef:D #1 }
4112 \</initex>
4113 \<package>\cs_set_eq:NN \toks_new:N \newtoks % nick from LaTeX for the moment
4114 \cs_generate_variant:Nn \toks_new:N {c}
```

`\toks_use:N` This function returns the contents of a token register.

```
\toks_use:c
4115 \cs_new_eq:NN \toks_use:N \tex_the:D
4116 \cs_generate_variant:Nn \toks_use:N {c}
```

`\toks_set:Nn` `\toks_set:Nn<toks><stuff>` stores `<stuff>` without expansion in `<toks>`. `\toks_set:No` and `\toks_set:Nx` expand `<stuff>` once and fully.

```
\toks_set:Nv
4117 \<check>
4118 \cs_new_nopar:Npn \toks_set:Nn #1 { \chk_local:N #1 #1 }
4119 \cs_generate_variant:Nn \toks_set:Nn {No,Nf}
4120 \</check>
```

`\toks_set:cn` If we don't check if `<toks>` is a local register then the `\toks_set:Nn` function has nothing to do. We implement `\toks_set:No/d/f` by hand when not checking because this is going to be used *extensively* in keyval processing! TODO: (Will) Can we get some numbers published on how necessary this is? On the other hand I'm happy to believe Morten :)

```
\toks_set:co
4121 \<!check>
4122 \cs_new_eq:NN \toks_set:Nn \prg_do_nothing:
4123 \cs_new:Npn \toks_set:Nv #1#2 {
4124   #1 \exp_after:wN { \int_to_roman:w -'0 \exp_eval_register:N #2 }
4125 }
4126 \cs_new:Npn \toks_set:Nv #1#2 {
4127   #1 \exp_after:wN { \int_to_roman:w -'0 \exp_eval_register:c {#2} }
4128 }
4129 \cs_new:Npn \toks_set:No #1#2 { #1 \exp_after:wN {#2} }
4130 \cs_new:Npn \toks_set:Nf #1#2 {
4131   #1 \exp_after:wN { \int_to_roman:w -'0#2 }
4132 }
4133 \</!check>
4134 \cs_generate_variant:Nn \toks_set:Nn {Nx,cn,cV,cv,co,cx,cf}
```

`\toks_gset:Nn` These functions are the global variants of the above.

```
\toks_gset:Nv
4135 \<check>\cs_new_nopar:Npn \toks_gset:Nn #1 { \chk_global:N #1 \pref_global:D #1 }
4136 \<!check>\cs_new_eq:NN \toks_gset:Nn \pref_global:D
4137 \cs_generate_variant:Nn \toks_gset:Nn {NV,No,Nx,cn,cV,co,cx}
\toks_gset:cn
\toks_gset:cV
\toks_gset:co
\toks_gset:cx
```

\toks\_set\_eq:NN \toks\_set\_eq:NN<toks1><toks2> copies the contents of <toks2> in <toks1>.

```

\toks_set_eq:Nc
\toks_set_eq:cN
\toks_set_eq:cc
\toks_gset_eq:NN
\toks_gset_eq:Nc
\toks_gset_eq:cN
\toks_gset_eq:cc
4138 <*check>
4139 \cs_new_nopar:Npn\toks_set_eq:NN #1#2 {
4140   \chk_local:N #1
4141   \chk_var_or_const:N #2
4142   #1 #2
4143 }
4144 \cs_new_nopar:Npn\toks_gset_eq:NN #1#2 {
4145   \chk_global:N #1
4146   \chk_var_or_const:N #2
4147   \pref_global:D #1 #2
4148 }
4149 </check>
4150 <!*check>
4151 \cs_new_eq:NN \toks_set_eq:NN \prg_do_nothing:
4152 \cs_new_eq:NN \toks_gset_eq:NN \pref_global:D
4153 </!check>
4154 \cs_generate_variant:Nn \toks_set_eq:NN {Nc,cN,cc}
4155 \cs_generate_variant:Nn \toks_gset_eq:NN {Nc,cN,cc}

```

\toks\_clear:N These functions clear a token register, either locally or globally.

```

\toks_gclear:N
\toks_clear:c
\toks_gclear:c
4156 \cs_new_nopar:Npn \toks_clear:N #1 {
4157   #1\c_empty_toks
4158 <check>\chk_local_or_pref_global:N #1
4159 }
4160 \cs_new_nopar:Npn \toks_gclear:N {
4161 <check> \pref_global_chk:
4162 <!check> \pref_global:D
4163   \toks_clear:N
4164 }
4165 \cs_generate_variant:Nn \toks_clear:N {c}
4166 \cs_generate_variant:Nn \toks_gclear:N {c}

```

\toks\_use\_clear:N These functions clear a token register (locally or globally) after returning the contents.

\toks\_use\_clear:c They make sure that clearing the register does not interfere with following tokens. In  
\toks\_use\_gclear:N other words, the contents of the register might operate on what follows in the input  
\toks\_use\_gclear:c stream.

```

4167 \cs_new_nopar:Npn \toks_use_clear:N #1 {
4168   \exp_last_unbraced:NNV \toks_clear:N #1 #1
4169 }
4170 \cs_new_nopar:Npn \toks_use_gclear:N {
4171 <check> \pref_global_chk:
4172 <!check> \pref_global:D
4173   \toks_use_clear:N
4174 }

```

```

4175 \cs_generate_variant:Nn \toks_use_clear:N {c}
4176 \cs_generate_variant:Nn \toks_use_gclear:N {c}

```

`\toks_show:N` This function shows the contents of a token register on the terminal. TODO: this is not pretty when the argument is a control sequence that doesn't exist!

`\toks_show:c`

```

4177 \cs_new_eq:NN \toks_show:N \tex_showthe:D
4178 \cs_generate_variant:Nn \toks_show:N {c}

```

## 105.2 Adding to token registers' contents

```

\toks_put_left:Nn \toks_put_left:Nn <toks><stuff> adds the tokens of stuff on the 'left-side' of the token
\toks_put_left:NV register <toks>. \toks_put_left:No does the same, but expands the tokens once. We
\toks_put_left:No need to look out for brace stripping so we add a token, which is then later removed.
\toks_put_left:Nx
\toks_put_left:cn 4179 \cs_new_nopar:Npn \toks_put_left:Nn #1 {
\toks_put_left:cV 4180 \exp_after:wN \toks_put_left_aux:w \exp_after:wN \q_mark
\toks_put_left:co 4181 \toks_use:N #1 \q_stop #1
4182 }
\toks_gput_left:Nn
\toks_gput_left:NV 4183 \cs_generate_variant:Nn \toks_put_left:Nn {NV,No,Nx,cn,co,cV}
\toks_gput_left:No
\toks_gput_left:Nx 4184 \cs_new_nopar:Npn \toks_gput_left:Nn {
\toks_gput_left:cn 4185 <check> \pref_global_chk:
\toks_gput_left:cV 4186 <!check> \pref_global:D
\toks_gput_left:co 4187 \toks_put_left:Nn
4188 }
\toks_put_left_aux:w 4189 \cs_generate_variant:Nn \toks_gput_left:Nn {NV,No,Nx,cn,cV,co}

```

A helper function for `\toks_put_left:Nn`. Its arguments are subsequently the tokens of `<stuff>`, the token register `<toks>` and the current contents of `<toks>`. We make sure to remove the token we inserted earlier.

```

4190 \cs_new:Npn \toks_put_left_aux:w #1\q_stop #2#3 {
4191 #2 \exp_after:wN { \use_i:nn {#3} #1 }
4192 <check> \chk_local_or_pref_global:N #2
4193 }

```

`\toks_put_right:Nn` These macros add a list of tokens to the right of a token register.

`\toks_put_right:NV`

`\toks_put_right:No`

`\toks_put_right:Nx`

`\toks_put_right:cn`

`\toks_put_right:cV`

`\toks_put_right:co`

`\toks_gput_right:Nn`

`\toks_gput_right:NV`

`\toks_gput_right:No`

`\toks_gput_right:Nx`

`\toks_gput_right:cn`

`\toks_gput_right:cV`

`\toks_gput_right:co`

```

4198 \cs_new_nopar:Npn \toks_gput_right:Nn {
4199   \check   \pref_global_chk:
4200   \!check \pref_global:D
4201   \toks_put_right:Nn
4202 }

```

A couple done by hand for speed.

```

4203 {check}\cs_generate_variant:Nn \toks_put_right:Nn {No}
4204 {*\check}
4205 \cs_new:Npn \toks_put_right:NV #1#2 {
4206   #1 \exp_after:wN \exp_after:wN \exp_after:wN {
4207     \exp_after:wN \toks_use:N \exp_after:wN #1
4208     \int_to_roman:w -'0 \exp_eval_register:N #2
4209   }
4210 }
4211 \cs_new:Npn \toks_put_right:No #1#2 {
4212   #1 \exp_after:wN \exp_after:wN \exp_after:wN {
4213     \exp_after:wN \toks_use:N \exp_after:wN #1 #2
4214   }
4215 }
4216 </!\check>
4217 \cs_generate_variant:Nn \toks_put_right:Nn {Nx,cn,cV,co}
4218 \cs_generate_variant:Nn \toks_gput_right:Nn {NV,No,Nx,cn,cV,co}

```

<code>\toks_put_right:Nf</code>	We implement <code>\toks_put_right:Nf</code> by hand because I think I might use it in the <code>l3keyval</code> module in which case it is going to be used a lot.
---------------------------------	---

```

4219 <check>\cs_generate_variant:Nn \toks_put_right:Nn {Nf}
4220 <*/!check>
4221 \cs_new:Npn \toks_put_right:Nf #1#2 {
4222   #1 \exp_after:wN \exp_after:wN \exp_after:wN {
4223     \exp_after:wN \toks_use:N \exp_after:wN #1 \int_to_roman:w -'0#2
4224   }
4225 }
4226 </!check>

```

### 105.3 Predicates and conditionals

$\backslash\text{toks\_if\_empty\_p:N}$ $\backslash\text{toks\_if\_empty\_p:c}$ $\backslash\text{toks\_if\_empty:N}\overline{TF}$ $\backslash\text{toks\_if\_empty:c}\overline{TF}$	$\backslash\text{toks\_if\_empty:N}\overline{TF}\langle\textit{toks}\rangle\langle\textit{true code}\rangle\langle\textit{false code}\rangle$ tests if a token register is empty and executes either $\langle\textit{true code}\rangle$ or $\langle\textit{false code}\rangle$ . This test had the advantage of being expandable. Otherwise one has to do an x type expansion in order to prevent problems with parameter tokens.
--	---

```
4227 \prg_new_conditional:Nnn \toks_if_empty:N {p,TF,T,F} {
4228   \tl_if_empty:VTF #1 {\prg_return_true:} {\prg_return_false:}
4229 }
```

```

4230 \cs_generate_variant:Nn \toks_if_empty_p:N {c}
4231 \cs_generate_variant:Nn \toks_if_empty:NTF {c}
4232 \cs_generate_variant:Nn \toks_if_empty:NT {c}
4233 \cs_generate_variant:Nn \toks_if_empty:NF {c}

```

`\toks_if_eq_p:NN` This function test whether two token registers have the same contents.

```

\toks_if_eq_p:cN
\toks_if_eq_p:Nc
\toks_if_eq_p:cc
\toks_if_eq:NNTF
\toks_if_eq:NcTF
\toks_if_eq:cNTF
\toks_if_eq:ccTF
4234 \prg_new_conditional:Nnn \toks_if_eq:NN {p,TF,T,F} {
4235   \tl_if_eq:xxTF {\toks_use:N #1} {\toks_use:N #2}
4236   {\prg_return_true:} {\prg_return_false:}
4237 }
4238 \cs_generate_variant:Nn \toks_if_eq_p:NN {Nc,c,cc}
4239 \cs_generate_variant:Nn \toks_if_eq:NNTF {Nc,c,cc}
4240 \cs_generate_variant:Nn \toks_if_eq:NNT {Nc,c,cc}
4241 \cs_generate_variant:Nn \toks_if_eq:NNF {Nc,c,cc}

```

## 105.4 Variables and constants

`\l_tmpa_toks` Some scratch registers ...

```

\l_tmpb_toks
\l_tmpc_toks
\g_tmpa_toks
\g_tmpb_toks
\g_tmpc_toks
4242 \tex_toksdef:D \l_tmpa_toks = 255\scan_stop:
4243 \initex\seq_put_right:Nn \g_toks_allocation_seq {255}
4244 \toks_new:N \l_tmpb_toks
4245 \toks_new:N \l_tmpc_toks
4246 \toks_new:N \g_tmpa_toks
4247 \toks_new:N \g_tmpb_toks
4248 \toks_new:N \g_tmpc_toks

```

`\c_empty_toks` And here is a constant, which is a (permanently) empty token register.

```

4249 \toks_new:N \c_empty_toks

```

`\l_tl_replace_toks` And here is one for tl vars. Can't define it there as the allocation isn't set up at that point.

```

4250 \toks_new:N \l_tl_replace_toks
4251 \</initex | package>

```

Show token usage:

```

4252 \showmemory>
4253 \showMemUsage
4254 \showmemory>

```

## 106 l3seq implementation

```

4255 <*package>
4256 \ProvidesExplPackage
4257   {\filename}{\filedate}{\fileversion}{\filedescription}
4258 \package_check_loaded_expl:
4259 </package>

```

A sequence is a control sequence whose top-level expansion is of the form ‘`\seq_elt:w`  $\langle text_1 \rangle$  `\seq_elt_end: ... \seq_elt:w`  $\langle text_n \rangle$  ...’. We use explicit delimiters instead of braces around  $\langle text \rangle$  to allow efficient searching for an item in the sequence.

`\seq_elt:w` We allocate the delimiters and make them errors if executed.  
`\seq_elt_end:`

```

4260 <*initex | package>
4261 \cs_new:Npn \seq_elt:w {\ERROR}
4262 \cs_new:Npn \seq_elt_end: {\ERROR}

```

### 106.1 Allocating and initialisation

`\seq_new:N` Sequences are implemented using token lists.

`\seq_new:c`

```

4263 \cs_new_eq:NN \seq_new:N \tl_new:N
4264 \cs_new_eq:NN \seq_new:c \tl_new:c

```

`\seq_clear:N` Clearing a sequence is the same as clearing a token list.

`\seq_clear:c`

```

4265 \cs_new_eq:NN \seq_clear:N \tl_clear:N
4266 \cs_new_eq:NN \seq_clear:c \tl_clear:c
4267 \cs_new_eq:NN \seq_gclear:N \tl_gclear:N
4268 \cs_new_eq:NN \seq_gclear:c \tl_gclear:c

```

`\seq_clear_new:N` Clearing a sequence is the same as clearing a token list.

`\seq_clear_new:c`

```

4269 \cs_new_eq:NN \seq_clear_new:N \tl_clear_new:N
4270 \cs_new_eq:NN \seq_clear_new:c \tl_clear_new:c
4271 \cs_new_eq:NN \seq_gclear_new:N \tl_gclear_new:N
4272 \cs_new_eq:NN \seq_gclear_new:c \tl_gclear_new:c

```

`\seq_set_eq:NN` We can set one seq equal to another.

`\seq_set_eq:Nc`

```

4273 \cs_new_eq:NN \seq_set_eq:NN \cs_set_eq:NN
4274 \cs_new_eq:NN \seq_set_eq:cN \cs_set_eq:cN
4275 \cs_new_eq:NN \seq_set_eq:Nc \cs_set_eq:Nc
4276 \cs_new_eq:NN \seq_set_eq:cc \cs_set_eq:cc

```

`\seq_gset_eq:NN` And of course globally which seems to be needed far more often.<sup>12</sup>

```
\seq_gset_eq:cN
\seq_gset_eq:Nc
\seq_gset_eq:cc
4277 \cs_new_eq:NN \seq_gset_eq:NN \cs_gset_eq:NN
4278 \cs_new_eq:NN \seq_gset_eq:cN \cs_gset_eq:cN
4279 \cs_new_eq:NN \seq_gset_eq:Nc \cs_gset_eq:Nc
4280 \cs_new_eq:NN \seq_gset_eq:cc \cs_gset_eq:cc
```

`\seq_gconcat:NNN` `\seq_gconcat:NNN`  $\langle seq\ 1 \rangle$   $\langle seq\ 2 \rangle$   $\langle seq\ 3 \rangle$  will globally assign  $\langle seq\ 1 \rangle$  the concatenation of  $\langle seq\ 2 \rangle$  and  $\langle seq\ 3 \rangle$ .

```
4281 \cs_new_nopar:Npn \seq_gconcat:NNN #1#2#3 {
4282   \tl_gset:Nx #1 { \exp_not:V #2 \exp_not:V #3 }
4283 }
4284 \cs_generate_variant:Nn \seq_gconcat:NNN {ccc}
```

## 106.2 Predicates and conditionals

`\seq_if_empty_p:N` A predicate which evaluates to `\c_true_bool` iff the sequence is empty.

```
\seq_if_empty_p:c
\seq_if_empty:N $\underline{TF}$ 
\seq_if_empty:c $\underline{TF}$ 
4285 \prg_new_eq_conditional:NNn \seq_if_empty:N \tl_if_empty:N {p,TF,T,F}
4286 \prg_new_eq_conditional:NNn \seq_if_empty:c \tl_if_empty:c {p,TF,T,F}
```

`\seq_if_empty_err:N` Signals an error if the sequence is empty.

```
4287 \cs_new_nopar:Npn \seq_if_empty_err:N #1 {
4288   \if_meaning:w #1 \c_empty_tl
```

As I said before, I don't think we need to provide checks for this kind of error, since it is a severe internal macro package error that can not be produced by the user directly. Can it? So the next line of code should be probably removed. (Will: I have no idea what this comment means.)

```
4289   \tl_clear:N \l_testa_tl % catch prefixes
4290   \msg_kernel_bug:x {Empty~sequence~'\token_to_str:N#1'}
4291   \fi:
4292 }
```

`\seq_if_in:Nn $\underline{TF}$`  `\seq_if_in:Nn $\underline{TF}$`   $\langle seq \rangle$   $\langle item \rangle$   $\langle true\ case \rangle$   $\langle false\ case \rangle$  will check whether  $\langle item \rangle$  is in  $\langle seq \rangle$  and then either execute the  $\langle true\ case \rangle$  or the  $\langle false\ case \rangle$ .  $\langle true\ case \rangle$  and  $\langle false\ case \rangle$  may contain incomplete `\if_charcode:w` statements.

`\seq_if_in:cn $\underline{TF}$`  `\seq_if_in:c $\underline{VTF}$`  `\seq_if_in:co $\underline{TF}$`  `\seq_if_in:cx $\underline{TF}$`  Note that ##2 in the definition below for `\seq_tmp:w` contains exactly one token which we can compare with `\q_no_value`.

```
4293 \prg_new_conditional:Nnn \seq_if_in:Nn {TF,T,F} {
4294   \cs_set:Npn \seq_tmp:w ##1 \seq_elt:w #2 \seq_elt_end: ##2##3 \q_stop {
4295     \if_meaning:w \q_no_value ##2
```

<sup>12</sup>To save a bit of space these functions could be made identical to those from the `tl` or `clist` module.

```

4296     \prg_return_false: \else: \prg_return_true: \fi:
4297 }
4298 \exp_after:wN \seq_tmp:w #1 \seq_elt:w #2 \seq_elt_end: \q_no_value \q_stop
4299 }

4300 \cs_generate_variant:Nn \seq_if_in:NnTF { NV, cV, co, c, cx}
4301 \cs_generate_variant:Nn \seq_if_in:NnT { NV, cV, co, c, cx}
4302 \cs_generate_variant:Nn \seq_if_in:NnF { NV, cV, co, c, cx}

```

### 106.3 Getting data out

```

\seq_get:NN \seq_get:NN <sequence><cmd> defines <cmd> to be the left-most element of <sequence>.
\seq_get:cN
\seq_get_aux:w
4303 \cs_new_nopar:Npn \seq_get:NN #1 {
4304     \seq_if_empty_err:N #1
4305     \exp_after:wN \seq_get_aux:w #1 \q_stop
4306 }
4307 \cs_new:Npn \seq_get_aux:w \seq_elt:w #1 \seq_elt_end: #2 \q_stop #3 {
4308     \tl_set:Nn #3 {#1}
4309 }
4310 \cs_generate_variant:Nn \seq_get:NN {c}

\seq_pop_aux:nnNN \seq_pop_aux:nnNN <def1> <def2> <sequence> <cmd> assigns the left_most element of
\seq_pop_aux:w <sequence> to <cmd> using <def2>, and assigns the tail of <sequence> to <sequence> using
<def1>.

4311 \cs_new:Npn \seq_pop_aux:nnNN #1#2#3 {
4312     \seq_if_empty_err:N #3
4313     \exp_after:wN \seq_pop_aux:w #3 \q_stop #1#2#3
4314 }
4315 \cs_new:Npn \seq_pop_aux:w
4316     \seq_elt:w #1 \seq_elt_end: #2\q_stop #3#4#5#6 {
4317     #3 #5 {#2}
4318     #4 #6 {#1}
4319 }

\seq_show:N
\seq_show:c
4320 \cs_new_eq:NN \seq_show:N \tl_show:N
4321 \cs_new_eq:NN \seq_show:c \tl_show:c

\seq_display:N
\seq_display:c
4322 \cs_new_nopar:Npn \seq_display:N #1 {
4323     \iow_term:x { Sequence~\token_to_str:N #1~contains~
4324         the~elements~(without~outer~braces): }
4325     \toks_clear:N \l_tmpa_toks
4326     \seq_map_inline:Nn #1 {

```



```

4327 \toks_if_empty:NF \l_tmpa_toks {
4328 \toks_put_right:Nx \l_tmpa_toks {^^J>~}
4329 }
4330 \toks_put_right:Nx \l_tmpa_toks {
4331 \iow_space: \iow_char:N \{ \exp_not:n {##1} \iow_char:N \}
4332 }
4333 }
4334 \toks_show:N \l_tmpa_toks
4335 }
4336 \cs_generate_variant:Nn \seq_display:N {c}

```

## 106.4 Putting data in

`\seq_put_aux:Nnn` `\seq_put_aux:w` `\seq_put_aux:Nnn`  $\langle sequence \rangle$   $\langle left \rangle$   $\langle right \rangle$  adds the elements specified by  $\langle left \rangle$  to the left of  $\langle sequence \rangle$ , and those specified by  $\langle right \rangle$  to the right.

```

4337 \cs_new:Npn \seq_put_aux:Nnn #1 {
4338 \exp_after:wN \seq_put_aux:w #1 \q_stop #1
4339 }
4340 \cs_new:Npn \seq_put_aux:w #1\q_stop #2#3#4 { \tl_set:Nn #2 {#3#1#4} }

```

`\seq_put_left:Nn` Here are the usual operations for adding to the left and right.

```

\seq_put_left:NV
\seq_put_left:No
\seq_put_left:Nx
\seq_put_left:cn
\seq_put_left:cV
\seq_put_left:co
\seq_put_right:Nn
\seq_put_right:No
\seq_put_right:NV
\seq_put_right:Nx
\seq_put_right:cn
\seq_put_right:cV
\seq_put_right:co

```

```

4341 \cs_new:Npn \seq_put_left:Nn #1#2 {
4342 \seq_put_aux:Nnn #1 {\seq_elt:w #2\seq_elt_end:} {}
4343 }

```

We can't put in a `\prg_do_nothing:` instead of `{}` above since this argument is passed literally (and we would end up with many `\prg_do_nothing:s` inside the sequences).

```

4344 \cs_generate_variant:Nn \seq_put_left:Nn {NV,No,Nx,c,cV,co}
4345 \cs_new:Npn \seq_put_right:Nn #1#2{
4346 \seq_put_aux:Nnn #1{\seq_elt:w #2\seq_elt_end:}}
4347 \cs_generate_variant:Nn \seq_put_right:Nn {NV,No,Nx,c,cV,co}

```

```

\seq_gput_left:Nn
\seq_gput_left:NV
\seq_gput_left:No
\seq_gput_left:Nx
\seq_gput_left:cn
\seq_gput_left:cV
\seq_gput_left:co
\seq_gput_right:Nn
\seq_gput_right:NV
\seq_gput_right:No
\seq_gput_right:Nx
\seq_gput_right:cn
\seq_gput_right:cV
\seq_gput_right:co

```

```

4348 \cs_new:Npn \seq_gput_left:Nn {
4349 \*check
4350 \pref_global_chk:
4351 \*check
4352 \*!check
4353 \pref_global:D
4354 \*!check
4355 \seq_put_left:Nn
4356 }

```

```

4357 \cs_new:Npn \seq_gput_right:Nn {
4358   <*check>
4359   \pref_global_chk:
4360   </check>
4361   <!*check>
4362   \pref_global:D
4363   </!check>
4364   \seq_put_right:Nn
4365 }

4366 \cs_generate_variant:Nn \seq_gput_left:Nn {NV,No,Nx,c,cV,co}

4367 \cs_generate_variant:Nn \seq_gput_right:Nn {NV,No,Nx,c,cV,co}

\seq_gput_right:Nc TODO: move to xor (Sep 2008)

4368 \cs_generate_variant:Nn \seq_gput_right:Nn {Nc}

```

## 106.5 Mapping

\seq\_map\_variable:NNn Nothing spectacular here.

```

\seq_map_variable:cNn
\seq_map_variable_aux:Nnw
  \seq_map_break:
  \seq_map_break:n
4369 \cs_new:Npn \seq_map_variable_aux:Nnw #1#2 \seq_elt:w #3 \seq_elt_end: {
4370   \tl_set:Nx #1{\exp_not:n{#3}}
4371   \quark_if_nil:NT #1 \seq_map_break:
4372   #2
4373   \seq_map_variable_aux:Nnw #1{#2}
4374 }
4375 \cs_new:Npn \seq_map_variable:NNn #1#2#3 {
4376   \tl_set:Nx #2 {\exp_not:n{\seq_map_variable_aux:Nnw #2{#3}}}
4377   \exp_after:wN #2 #1 \seq_elt:w \q_nil\seq_elt_end: \q_stop
4378 }
4379 \cs_generate_variant:Nn \seq_map_variable:NNn {c}
4380
4381 \cs_new_eq:NN \seq_map_break: \use_none_delimit_by_q_stop:w
4382 \cs_new_eq:NN \seq_map_break:n \use_i_delimit_by_q_stop:nw

\seq_map_function:NN \seq_map_function:NN <sequence> <cmd> applies <cmd> to each element of <sequence>,
\seq_map_function:cN from left to right. Since we don't have braces, this implementation is not very efficient. It
might be better to say that <cmd> must be a function with one argument that is delimited
by \seq_elt_end:.

```

```

4383 \cs_new_nopar:Npn \seq_map_function:NN #1#2 {
4384   \cs_set:Npn \seq_elt:w ##1 \seq_elt_end: {#2{##1}}
4385   #1
4386   \cs_set_eq:NN \seq_elt:w \ERROR
4387 }
4388 \cs_generate_variant:Nn \seq_map_function:NN {c}

```

`\seq_map_inline:Nn` When no braces are used, this version of mapping seems more natural.  
`\seq_map_inline:cn`

```

4389 \cs_new_nopar:Npn \seq_map_inline:Nn #1#2 {
4390   \cs_set:Npn \seq_elt:w ##1 \seq_elt_end: {#2}
4391   #1
4392   \cs_set_eq:NN \seq_elt:w \ERROR
4393 }
4394 \cs_generate_variant:Nn \seq_map_inline:Nn {c}

```

## 106.6 Manipulation

`\l_clist_remove_clist` A common scratch space for the removal routines.

```

4395 \seq_new:N \l_seq_remove_seq

```

`\seq_remove_duplicates_aux:NN` Copied from `\clist_remove_duplicates`.

```

\seq_remove_duplicates_aux:n
  \seq_remove_duplicates:N
  \seq_gremove_duplicates:N
4396 \cs_new:Npn \seq_remove_duplicates_aux:NN #1#2 {
4397   \seq_clear:N \l_seq_remove_seq
4398   \seq_map_function:NN #2 \seq_remove_duplicates_aux:n
4399   #1 #2 \l_seq_remove_seq
4400 }
4401 \cs_new:Npn \seq_remove_duplicates_aux:n #1 {
4402   \seq_if_in:NnF \l_seq_remove_seq {#1} {
4403     \seq_put_right:Nn \l_seq_remove_seq {#1}
4404   }
4405 }
4406 \cs_new_nopar:Npn \seq_remove_duplicates:N {
4407   \seq_remove_duplicates_aux:NN \seq_set_eq:NN
4408 }
4409 \cs_new_nopar:Npn \seq_gremove_duplicates:N {
4410   \seq_remove_duplicates_aux:NN \seq_gset_eq:NN
4411 }

```

## 106.7 Sequence stacks

`\seq_push:Nn` Since sequences can be used as stacks, we ought to have both ‘push’ and ‘pop’. In most cases they are nothing more than new names for old functions.

```

\seq_push:NV
\seq_push:No
\seq_push:cn
\seq_pop:NN
\seq_pop:cN
4412 \cs_new_eq:NN \seq_push:Nn \seq_put_left:Nn
4413 \cs_new_eq:NN \seq_push:NV \seq_put_left:NV
4414 \cs_new_eq:NN \seq_push:No \seq_put_left:No
4415 \cs_new_eq:NN \seq_push:cn \seq_put_left:cn
4416 \cs_new_nopar:Npn \seq_pop:NN { \seq_pop_aux:nnNN \tl_set:Nn \tl_set:Nn }
4417 \cs_generate_variant:Nn \seq_pop:NN {c}

```

`\seq_gpush:Nn` I don't agree with Denys that one needs only local stacks, actually I believe that one will probably need the functions here more often. In case of `\seq_gpop:NN` the value is nevertheless returned locally.

```

\seq_gpush:Nv
\seq_gpush:cn
\seq_gpush:Nv
\seq_gpop:NN
\seq_gpop:cN
4418 \cs_new_eq:NN \seq_gpush:Nn \seq_gput_left:Nn
4419 \cs_new_nopar:Npn \seq_gpop:NN { \seq_pop_aux:nnNN \tl_gset:Nn \tl_set:Nn }
4420 \cs_generate_variant:Nn \seq_gpush:Nn {NV,No,c,Nv}
4421 \cs_generate_variant:Nn \seq_gpop:NN {c}

```

`\seq_top:NN` Looking at the top element of the stack without removing it is done with this operation.

```

\seq_top:cN
4422 \cs_new_eq:NN \seq_top:NN \seq_get:NN
4423 \cs_new_eq:NN \seq_top:cN \seq_get:cN

```

```

4424 </initex | package>

```

Show token usage:

```

4425 <*showmemory>
4426 %\showMemUsage
4427 </showmemory>

```

## 107 l3clist implementation

We start by ensuring that the required packages are loaded.

```

4428 <*package>
4429 \ProvidesExplPackage
4430 { \filename } { \filedate } { \fileversion } { \filedescription }
4431 \package_check_loaded_expl:
4432 </package>
4433 <*initex | package>

```

### 107.1 Allocation and initialisation

`\clist_new:N` Comma-Lists are implemented using token lists.

```

\clist_new:c
4434 \cs_new_eq:NN \clist_new:N \tl_new:N
4435 \cs_generate_variant:Nn \clist_new:N {c}

```

`\clist_clear:N` Clearing a comma-list is the same as clearing a token list.

```

\clist_clear:c
\clist_gclear:N
\clist_gclear:c
4436 \cs_new_eq:NN \clist_clear:N \tl_clear:N
4437 \cs_generate_variant:Nn \clist_clear:N {c}
4438 \cs_new_eq:NN \clist_gclear:N \tl_gclear:N
4439 \cs_generate_variant:Nn \clist_gclear:N {c}

```

`\clist_clear_new:N` Clearing a comma-list is the same as clearing a token list.

```

\clist_clear_new:c
\clist_gclear_new:N
\clist_gclear_new:c
4440 \cs_new_eq:NN \clist_clear_new:N \tl_clear_new:N
4441 \cs_generate_variant:Nn \clist_clear_new:N {c}
4442 \cs_new_eq:NN \clist_gclear_new:N \tl_gclear_new:N
4443 \cs_generate_variant:Nn \clist_gclear_new:N {c}

```

`\clist_set_eq:NN` We can set one  $\langle\textit{clist}\rangle$  equal to another.

```

\clist_set_eq:cN
\clist_set_eq:Nc
\clist_set_eq:cc
4444 \cs_new_eq:NN \clist_set_eq:NN \cs_set_eq:NN
4445 \cs_new_eq:NN \clist_set_eq:cN \cs_set_eq:cN
4446 \cs_new_eq:NN \clist_set_eq:Nc \cs_set_eq:Nc
4447 \cs_new_eq:NN \clist_set_eq:cc \cs_set_eq:cc

```

`\clist_gset_eq:NN` An of course globally which seems to be needed far more often.

```

\clist_gset_eq:cN
\clist_gset_eq:Nc
\clist_gset_eq:cc
4448 \cs_new_eq:NN \clist_gset_eq:NN \cs_gset_eq:NN
4449 \cs_new_eq:NN \clist_gset_eq:cN \cs_gset_eq:cN
4450 \cs_new_eq:NN \clist_gset_eq:Nc \cs_gset_eq:Nc
4451 \cs_new_eq:NN \clist_gset_eq:cc \cs_gset_eq:cc

```

## 107.2 Predicates and conditionals

```

\clist_if_empty_p:N
\clist_if_empty_p:c
\clist_if_empty:N $\underline{TF}$ 
\clist_if_empty:c $\underline{TF}$ 
4452 \prg_new_eq_conditional:NNn \clist_if_empty:N \tl_if_empty:N {p,TF,T,F}
4453 \prg_new_eq_conditional:NNn \clist_if_empty:c \tl_if_empty:c {p,TF,T,F}

```

`\clist_if_empty_err:N` Signals an error if the comma-list is empty.

```

4454 \cs_new_nopar:Npn \clist_if_empty_err:N #1 {
4455   \if_meaning:w #1 \c_empty_tl
4456   \tl_clear:N \l_testa_tl % catch prefixes
4457   \msg_kernel_bug:x {Empty~comma-list~'\token_to_str:N #1'}
4458   \fi:
4459 }

```

`\clist_if_eq_p:NN` Returns `\c_true` iff the two comma-lists are equal.

```

\clist_if_eq_p:Nc
\clist_if_eq_p:cN
\clist_if_eq_p:cc
\clist_if_eq:NN $\underline{TF}$ 
\clist_if_eq:cN $\underline{TF}$ 
\clist_if_eq:Nc $\underline{TF}$ 
\clist_if_eq:cc $\underline{TF}$ 
\clist_if_eq:Nc $\underline{TF}$ 
4460 \prg_new_eq_conditional:NNn \clist_if_eq:NN \tl_if_eq:NN {p,TF,T,F}
4461 \prg_new_eq_conditional:NNn \clist_if_eq:cN \tl_if_eq:cN {p,TF,T,F}
4462 \prg_new_eq_conditional:NNn \clist_if_eq:Nc \tl_if_eq:Nc {p,TF,T,F}
4463 \prg_new_eq_conditional:NNn \clist_if_eq:cc \tl_if_eq:cc {p,TF,T,F}

```

`\clist_if_in:NnTF`  $\langle\textit{clist}\rangle\langle\textit{item}\rangle\langle\textit{true case}\rangle\langle\textit{false case}\rangle$  will check whether  $\langle\textit{item}\rangle$  is in  $\langle\textit{clist}\rangle$  and then either execute the  $\langle\textit{true case}\rangle$  or the  $\langle\textit{false case}\rangle$ .  $\langle\textit{true case}\rangle$  and  $\langle\textit{false case}\rangle$  may contain incomplete `\if_charcode:w` statements.

```

\clist_if_in:Nc $\underline{TF}$ 
\clist_if_in:cN $\underline{TF}$ 
\clist_if_in:Nc $\underline{TF}$ 
\clist_if_in:cc $\underline{TF}$ 
\clist_if_in:Nc $\underline{TF}$ 
\clist_if_in:cc $\underline{TF}$ 

```

```

4464 \prg_new_conditional:Nnn \clist_if_in:Nn {TF,T,F} {
4465   \cs_set:Npn \clist_tmp:w ##1,##2,##3 \q_stop {
4466     \if_meaning:w \q_no_value ##2
4467     \prg_return_false: \else: \prg_return_true: \fi:
4468   }
4469   \exp_last_unbraced:NNo \clist_tmp:w , #1 , #2 , \q_no_value \q_stop
4470 }

4471 \cs_generate_variant:Nn \clist_if_in:NnTF {NV,No,cn,cV,co}
4472 \cs_generate_variant:Nn \clist_if_in:NnT {NV,No,cn,cV,co}
4473 \cs_generate_variant:Nn \clist_if_in:NnF {NV,No,cn,cV,co}

```

### 107.3 Retrieving data

`\clist_use:N` Using a  $\langle\textit{clist}\rangle$  is just executing it but if  $\langle\textit{clist}\rangle$  equals `\scan_stop:` it is probably stemming from a `\cs:w ... \cs_end:` that was created by mistake somewhere.

```

4474 \cs_new_nopar:Npn \clist_use:N #1 {
4475   \if_meaning:w #1 \scan_stop:
4476   \msg_kernel_bug:x {
4477     Comma~list~ '\token_to_str:N #1'~ has~ an~ erroneous~ structure!}
4478   \else:
4479   \exp_after:wN #1
4480   \fi:
4481 }
4482 \cs_generate_variant:Nn \clist_use:N {c}

```

`\clist_get:NN`  $\langle\textit{comma-list}\rangle\langle\textit{cmd}\rangle$  defines  $\langle\textit{cmd}\rangle$  to be the left-most element of  $\langle\textit{comma-list}\rangle$ .  
`\clist_get:cN`  
`\clist_get_aux:w`

```

4483 \cs_new_nopar:Npn \clist_get:NN #1 {
4484   \clist_if_empty_err:N #1
4485   \exp_after:wN \clist_get_aux:w #1,\q_stop
4486 }

4487 \cs_new:Npn \clist_get_aux:w #1,##2\q_stop #3 { \tl_set:Nn #3{#1} }

4488 \cs_generate_variant:Nn \clist_get:NN {cN}

```

`\clist_pop_aux:nnNN`  $\langle\textit{def}_1\rangle\langle\textit{def}_2\rangle\langle\textit{comma-list}\rangle\langle\textit{cmd}\rangle$  assigns the left-most element of  $\langle\textit{comma-list}\rangle$  to  $\langle\textit{cmd}\rangle$  using  $\langle\textit{def}_2\rangle$ , and assigns the tail of  $\langle\textit{comma-list}\rangle$  to  $\langle\textit{comma-list}\rangle$  using  $\langle\textit{def}_1\rangle$ .  
`\clist_pop_aux:w`  
`\clist_pop_auxi:w`

```

4489 \cs_new:Npn \clist_pop_aux:nnNN #1#2#3 {
4490   \clist_if_empty_err:N #3
4491   \exp_after:wN \clist_pop_aux:w #3,\q_nil\q_stop #1#2#3
4492 }

```

After the assignments below, if there was only one element in the original *clist*, it now contains only `\q_nil`.

```

4493 \cs_new:Npn \clist_pop_aux:w #1,#2\q_stop #3#4#5#6 {
4494     #4 #6 {#1}
4495     #3 #5 {#2}
4496     \quark_if_nil:NTF #5 { #3 #5 {} }{ \clist_pop_auxi:w #2 #3#5 }
4497 }

4498 \cs_new:Npn \clist_pop_auxi:w #1,\q_nil #2#3 { #2#3{#1} }

\clist_show:N
\clist_show:c

4499 \cs_new_eq:NN \clist_show:N \tl_show:N
4500 \cs_new_eq:NN \clist_show:c \tl_show:c

\clist_display:N
\clist_display:c

4501 \cs_new_nopar:Npn \clist_display:N #1 {
4502     \iow_term:x { Comma-list~\token_to_str:N #1~contains~
4503                 the~elements~(without~outer~braces): }
4504     \toks_clear:N \l_tmpa_toks
4505     \clist_map_inline:Nn #1 {
4506         \toks_if_empty:NF \l_tmpa_toks {
4507             \toks_put_right:Nx \l_tmpa_toks {^^J>~}
4508         }
4509         \toks_put_right:Nx \l_tmpa_toks {
4510             \iow_space: \iow_char:N \{ \exp_not:n {##1} \iow_char:N \}
4511         }
4512     }
4513     \toks_show:N \l_tmpa_toks
4514 }
4515 \cs_generate_variant:Nn \clist_display:N {c}

```

## 107.4 Storing data

`\clist_put_aux:NNnnNn` The generic put function. When adding we have to distinguish between an empty *<clist>* and one that contains at least one item (otherwise we accumulate commas).

MH says: Perhaps we should make sure that empty arguments don't get on the stack as that is probably a mistake. That's what I've implemented here. Since `\tl_if_empty:nF` is expandable prefixes are still allowed.

```

4516 \cs_new:Npn \clist_put_aux:NNnnNn #1#2#3#4#5#6 {
4517     \clist_if_empty:NTF #5 { #1 #5 {#6} } {
4518         \tl_if_empty:nF {#6} { #2 #5{#3#6#4} }
4519     }
4520 }

```

`\clist_put_left:Nn` The operations for adding to the left.  
`\clist_put_left:NV`  
`\clist_put_left:No` 4521 `\cs_new_nopar:Npn \clist_put_left:Nn {`  
`\clist_put_left:Nx` 4522 `\clist_put_aux:NNnnNn \tl_set:Nn \tl_put_left:Nn {} ,`  
`\clist_put_left:cn` 4523 `}`  
`\clist_put_left:cV` 4524 `\cs_generate_variant:Nn \clist_put_left:Nn {NV,No,Nx,cn,cV,co}`

`\clist_put_left:co` Global versions.  
`\clist_gput_left:Nn`  
`\clist_gput_left:NV` 4525 `\cs_new_nopar:Npn \clist_gput_left:Nn {`  
`\clist_gput_left:No` 4526 `\clist_put_aux:NNnnNn \tl_gset:Nn \tl_gput_left:Nn {} ,`  
`\clist_gput_left:Nx` 4527 `}`  
`\clist_gput_left:cn` 4528 `\cs_generate_variant:Nn \clist_gput_left:Nn {NV,No,Nx,cn,cV,co}`  
`\clist_gput_left:cV`

`\clist_gput_left:co` Adding something to the right side is almost the same.  
`\clist_put_right:Nn`  
`\clist_put_right:NV` 4529 `\cs_new_nopar:Npn \clist_put_right:Nn {`  
`\clist_put_right:No` 4530 `\clist_put_aux:NNnnNn \tl_set:Nn \tl_put_right:Nn , {}`  
`\clist_put_right:Nx` 4531 `}`  
`\clist_put_right:cn` 4532 `\cs_generate_variant:Nn \clist_put_right:Nn {NV,No,Nx,cn,cV,co}`  
`\clist_put_right:cV`

`\clist_gput_right:Nn` And here the global variants.  
`\clist_gput_right:NV` 4533 `\cs_new_nopar:Npn \clist_gput_right:Nn {`  
`\clist_gput_right:No` 4534 `\clist_put_aux:NNnnNn \tl_gset:Nn \tl_gput_right:Nn , {}`  
`\clist_gput_right:Nx` 4535 `}`  
`\clist_gput_right:cn` 4536 `\cs_generate_variant:Nn \clist_gput_right:Nn {NV,No,Nx,cn,cV,co}`  
`\clist_gput_right:cV`  
`\clist_gput_right:co`

## 107.5 Mapping

`\clist_map_function:NN` `\clist_map_function:NN`  $\langle comma-list \rangle$   $\langle cmd \rangle$  applies  $\langle cmd \rangle$  to each element of  $\langle comma-list \rangle$ ,  
`\clist_map_function:cN` from left to right.  
`\clist_map_function:nN`

4537 `\cs_new_nopar:Npn \clist_map_function:NN #1#2 {`  
4538 `\clist_if_empty:NF #1 {`  
4539 `\exp_after:wN \clist_map_function_aux:Nw`  
4540 `\exp_after:wN #2 #1 , \q_recursion_tail , \q_recursion_stop`  
4541 `}`  
4542 `}`  
4543 `\cs_generate_variant:Nn \clist_map_function:NN {cN}`  
  
4544 `\cs_new:Npn \clist_map_function:nN #1#2 {`  
4545 `\tl_if_blank:nF {#1} {`  
4546 `\clist_map_function_aux:Nw #2 #1 , \q_recursion_tail , \q_recursion_stop`  
4547 `}`  
4548 `}`



`\clist_map_function_aux:Nw` The general loop. Tests if we hit the first stop marker and exits if we did. If we didn't, place the function #1 in front of the element #2, which is surrounded by braces.

```

4549 \cs_new:Npn \clist_map_function_aux:Nw #1#2,{
4550   \quark_if_recursion_tail_stop:n{#2}
4551   #1{#2}
4552   \clist_map_function_aux:Nw #1
4553 }

```

`\clist_map_break:` The break statement is easy. Same as in other modules, gobble everything up to the special recursion stop marker.

```

4554 \cs_new_eq:NN \clist_map_break: \use_none_delimit_by_q_recursion_stop:w

```

`\clist_map_inline:Nn` The inline type is faster but not expandable. In order to make it nestable, we use a counter to keep track of the nesting level so that all of the functions called have distinct names. A simpler approach would of course be to use grouping and thus the save stack but then you lose the ability to do things locally.

`\clist_map_inline:cn`

`\clist_map_inline:nn`

A funny little thing occurred in one document: The command setting up the first call of `\clist_map_inline:Nn` was used in a tabular cell and the inline code used `\` so the loop broke as soon as this happened. Lesson to be learned from this: If you wish to have group like structure but not using the groupings of  $\TeX$ , then do every operation globally.

```

4555 \int_new:N \g_clist_inline_level_int
4556 \cs_new:Npn \clist_map_inline:Nn #1#2 {
4557   \clist_if_empty:NF #1 {
4558     \int_gincr:N \g_clist_inline_level_int
4559     \cs_gset:cpn {clist_map_inline_ \int_use:N \g_clist_inline_level_int :n}
4560     ##1{#2}

```

It is a lot more efficient to carry over the special function rather than constructing the same csname over and over again, so we just do it once. We reuse `\clist_map_function_aux:Nw` for the actual loop.

```

4561   \exp_last_unbraced:NcV \clist_map_function_aux:Nw
4562   {clist_map_inline_ \int_use:N \g_clist_inline_level_int :n}
4563   #1 , \q_recursion_tail , \q_recursion_stop
4564   \int_gdecr:N \g_clist_inline_level_int
4565 }
4566 }
4567 \cs_generate_variant:Nn \clist_map_inline:Nn {c}
4568 \cs_new:Npn \clist_map_inline:nn #1#2 {
4569   \tl_if_empty:nF {#1} {
4570     \int_gincr:N \g_clist_inline_level_int
4571     \cs_gset:cpn {clist_map_inline_ \int_use:N \g_clist_inline_level_int :n}
4572     ##1{#2}
4573     \exp_args:Nc \clist_map_function_aux:Nw

```

```

4574 {clist_map_inline_ \int_use:N \g_clist_inline_level_int :n}
4575 #1 , \q_recursion_tail , \q_recursion_stop
4576 \int_gdecr:N \g_clist_inline_level_int
4577 }
4578 }

```

`\clist_map_variable:nNn` `\clist_map_variable:NNn`  $\langle comma-list \rangle$   $\langle temp \rangle$   $\langle action \rangle$  assigns  $\langle temp \rangle$  to each element and executes  $\langle action \rangle$ .

`\clist_map_variable:NNn`

```

4579 \cs_new:Npn \clist_map_variable:NNn #1#2#3 {
4580   \tl_if_empty:nF {#1} {
4581     \clist_map_variable_aux:Nnw #2 {#3} #1
4582     , \q_recursion_tail , \q_recursion_stop
4583   }
4584 }

```

Something for v/V

```

4585 \cs_new_nopar:Npn \clist_map_variable:NNn {\exp_args:No \clist_map_variable:nNn}
4586 \cs_generate_variant:Nn\clist_map_variable:NNn {cNn}

```

`\clist_map_variable_aux:Nnw`

The general loop. Assign the temp variable #1 to the current item #3 and then check if that's the stop marker. If it is, break the loop. If not, execute the action #2 and continue.

```

4587 \cs_new:Npn \clist_map_variable_aux:Nnw #1#2#3,{
4588   \cs_set_nopar:Npn #1{#3}
4589   \quark_if_recursion_tail_stop:N #1
4590   #2 \clist_map_variable_aux:Nnw #1{#2}
4591 }

```

## 107.6 Higher level functions

`\clist_concat_aux:NNNN`

`\clist_concat:NNN`

`\clist_concat:ccc`

`\clist_gconcat:NNN`

`\clist_gconcat:ccc`

`\clist_gconcat:NNN`  $\langle clist 1 \rangle$   $\langle clist 2 \rangle$   $\langle clist 3 \rangle$  will globally assign  $\langle clist 1 \rangle$  the concatenation of  $\langle clist 2 \rangle$  and  $\langle clist 3 \rangle$ .

Again the situation is a bit more complicated because of the use of commas between items, so if either list is empty we have to avoid adding a comma.

```

4592 \cs_new_nopar:Npn \clist_concat_aux:NNNN #1#2#3#4 {
4593   \toks_set:No \l_tmpa_toks {#3}
4594   \toks_set:No \l_tmpb_toks {#4}
4595   #1 #2 {
4596     \toks_use:N \l_tmpa_toks
4597     \toks_if_empty:NF \l_tmpa_toks { \toks_if_empty:NF \l_tmpb_toks , }
4598     \toks_use:N \l_tmpb_toks
4599   }
4600 }
4601 \cs_new_nopar:Npn \clist_concat:NNN { \clist_concat_aux:NNNN \tl_set:Nx }
4602 \cs_new_nopar:Npn \clist_gconcat:NNN { \clist_concat_aux:NNNN \tl_gset:Nx }
4603 \cs_generate_variant:Nn \clist_concat:NNN {ccc}
4604 \cs_generate_variant:Nn \clist_gconcat:NNN {ccc}

```

`\l_clist_remove_clist` A common scratch space for the removal routines.

```
4605 \clist_new:N \l_clist_remove_clist
```

`\clist_remove_duplicates_aux:NN` Removing duplicate entries in a *<clist>* is fairly straight forward. We use a temporary variable and then go through the list from left to right. For each element check if the element is already present in the list.

`\clist_remove_duplicates_aux:n`  
`\clist_remove_duplicates:N`  
`\clist_gremove_duplicates:N`

```
4606 \cs_new:Npn \clist_remove_duplicates_aux:NN #1#2 {
4607   \clist_clear:N \l_clist_remove_clist
4608   \clist_map_function:NN #2 \clist_remove_duplicates_aux:n
4609   #1 #2 \l_clist_remove_clist
4610 }
4611 \cs_new:Npn \clist_remove_duplicates_aux:n #1 {
4612   \clist_if_in:NnF \l_clist_remove_clist {#1} {
4613     \clist_put_right:Nn \l_clist_remove_clist {#1}
4614   }
4615 }
```

The high level functions are just for telling if it should be a local or global setting.

```
4616 \cs_new_nopar:Npn \clist_remove_duplicates:N {
4617   \clist_remove_duplicates_aux:NN \clist_set_eq:NN
4618 }
4619 \cs_new_nopar:Npn \clist_gremove_duplicates:N {
4620   \clist_remove_duplicates_aux:NN \clist_gset_eq:NN
4621 }
```

`\clist_remove_element:Nn` The same general idea is used for removing elements: the parent functions just set things up for the internal ones.

`\clist_gremove_element:Nn`  
`\clist_remove_element_aux:NNn`  
`\clist_remove_element_aux:n`

```
4622 \cs_new_nopar:Npn \clist_remove_element:Nn {
4623   \clist_remove_element_aux:NNn \clist_set_eq:NN
4624 }
4625 \cs_new_nopar:Npn \clist_gremove_element:Nn {
4626   \clist_remove_element_aux:NNn \clist_gset_eq:NN
4627 }
4628 \cs_new:Npn \clist_remove_element_aux:NNn #1#2#3 {
4629   \clist_clear:N \l_clist_remove_clist
4630   \cs_set:Npn \clist_remove_element_aux:n ##1 {
4631     \tl_if_eq:nnF {#3} {##1} {
4632       \clist_put_right:Nn \l_clist_remove_clist {##1}
4633     }
4634   }
4635   \clist_map_function:NN #2 \clist_remove_element_aux:n
4636   #1 #2 \l_clist_remove_clist
4637 }
4638 \cs_new:Npn \clist_remove_element_aux:n #1 { }
```

## 107.7 Stack operations

We build stacks from comma-lists, but here we put the specific functions together.

`\clist_push:Nn` Since comma-lists can be used as stacks, we ought to have both ‘push’ and ‘pop’. In most cases they are nothing more than new names for old functions.

`\clist_push:No`

`\clist_push:NV`

`\clist_push:cn` 4639 `\cs_new_eq:NN \clist_push:Nn \clist_put_left:Nn`

`\clist_pop:NN` 4640 `\cs_new_eq:NN \clist_push:NV \clist_put_left:NV`

`\clist_pop:cN` 4641 `\cs_new_eq:NN \clist_push:No \clist_put_left:No`

4642 `\cs_new_eq:NN \clist_push:cn \clist_put_left:cn`

4643 `\cs_new_nopar:Npn \clist_pop:NN {\clist_pop_aux:nnNN \tl_set:Nn \tl_set:Nn}`

4644 `\cs_generate_variant:Nn \clist_pop:NN {cN}`

`\clist_gpush:Nn` I don’t agree with Denys that one needs only local stacks, actually I believe that one will probably need the functions here more often. In case of `\clist_gpop:NN` the value is nevertheless returned locally.

`\clist_gpush:No`

`\clist_gpush:NV`

`\clist_gpush:cn`

`\clist_gpop:NN` 4645 `\cs_new_eq:NN \clist_gpush:Nn \clist_gput_left:Nn`

`\clist_gpop:cN` 4646 `\cs_new_eq:NN \clist_gpush:NV \clist_gput_left:NV`

4647 `\cs_new_eq:NN \clist_gpush:No \clist_gput_left:No`

4648 `\cs_generate_variant:Nn \clist_gpush:Nn {cn}`

4649 `\cs_new_nopar:Npn \clist_gpop:NN {\clist_pop_aux:nnNN \tl_gset:Nn \tl_set:Nn}`

4650 `\cs_generate_variant:Nn \clist_gpop:NN {cN}`

`\clist_top:NN` Looking at the top element of the stack without removing it is done with this operation.

`\clist_top:cN`

4651 `\cs_new_eq:NN \clist_top:NN \clist_get:NN`

4652 `\cs_new_eq:NN \clist_top:cN \clist_get:cN`

4653 `\</initex | package>`

Show token usage:

4654 `< *showmemory>`

4655 `% \showMemUsage`

4656 `< /showmemory>`

## 108 l3prop implementation

A property list is a token register whose contents is of the form

$$\backslash\mathbf{q\_prop}\langle key_1\rangle\backslash\mathbf{q\_prop}\{\langle info_1\rangle\}\dots\backslash\mathbf{q\_prop}\langle key_n\rangle\backslash\mathbf{q\_prop}\{\langle info_n\rangle\}$$

The property  $\langle key\rangle$ s and  $\langle info\rangle$ s might be arbitrary token lists; each  $\langle info\rangle$  is surrounded by braces.

We start by ensuring that the required packages are loaded.

```

4657 <*package>
4658 \ProvidesExplPackage
4659   {\filename}{\filedate}{\fileversion}{\filedescription}
4660 \package_check_loaded_expl:
4661 </package>
4662 <*initex | package>

```

`\q_prop` The separator between  $\langle key \rangle$ s and  $\langle info \rangle$ s and  $\langle key \rangle$ s.

```

4663 \quark_new:N\q_prop

```

To get values from property-lists, token lists should be passed to the appropriate functions.

## 108.1 Functions

`\prop_new:N` Property lists are implemented as token registers.

`\prop_new:c`

```

4664 \cs_new_eq:NN \prop_new:N \toks_new:N
4665 \cs_new_eq:NN \prop_new:c \toks_new:c

```

`\prop_clear:N` The same goes for clearing a property list, either locally or globally.

`\prop_clear:c`

`\prop_gclear:N`

`\prop_gclear:c`

```

4666 \cs_new_eq:NN \prop_clear:N \toks_clear:N
4667 \cs_new_eq:NN \prop_clear:c \toks_clear:c
4668 \cs_new_eq:NN \prop_gclear:N \toks_gclear:N
4669 \cs_new_eq:NN \prop_gclear:c \toks_gclear:c

```

`\prop_set_eq:NN` This makes two  $\langle prop \rangle$ s have the same contents.

`\prop_set_eq:Nc`

`\prop_set_eq:cN`

`\prop_set_eq:cc`

`\prop_gset_eq:NN`

`\prop_gset_eq:Nc`

`\prop_gset_eq:cN`

`\prop_gset_eq:cc`

```

4670 \cs_new_eq:NN \prop_set_eq:NN \toks_set_eq:NN
4671 \cs_new_eq:NN \prop_set_eq:Nc \toks_set_eq:Nc
4672 \cs_new_eq:NN \prop_set_eq:cN \toks_set_eq:cN
4673 \cs_new_eq:NN \prop_set_eq:cc \toks_set_eq:cc
4674 \cs_new_eq:NN \prop_gset_eq:NN \toks_gset_eq:NN
4675 \cs_new_eq:NN \prop_gset_eq:Nc \toks_gset_eq:Nc
4676 \cs_new_eq:NN \prop_gset_eq:cN \toks_gset_eq:cN
4677 \cs_new_eq:NN \prop_gset_eq:cc \toks_gset_eq:cc

```

`\prop_show:N` Show on the console the raw contents of a property list's token register.

`\prop_show:c`

```

4678 \cs_new_eq:NN \prop_show:N \toks_show:N
4679 \cs_new_eq:NN \prop_show:c \toks_show:c

```

`\prop_display:N` Pretty print the contents of a property list on the console.

`\prop_display:c`

```

4680 \cs_new_nopar:Npn \prop_display:N #1 {
4681   \iow_term:x { Property-list~\token_to_str:N #1~contains~
4682             the~pairs~(without~outer~braces): }
4683   \toks_clear:N \l_tmpa_toks
4684   \prop_map_inline:Nn #1 {
4685     \toks_if_empty:NF \l_tmpa_toks {
4686       \toks_put_right:Nx \l_tmpa_toks {^^J>~}
4687     }
4688     \toks_put_right:Nx \l_tmpa_toks {
4689       \iow_space: \iow_char:N \{ \exp_not:n {##1} \iow_char:N \} \iow_space:
4690       \iow_space: => \iow_space:
4691       \iow_space: \iow_char:N \{ \exp_not:n {##2} \iow_char:N \}
4692     }
4693   }
4694   \toks_show:N \l_tmpa_toks
4695 }
4696 \cs_generate_variant:Nn \prop_display:N {c}

```

`\prop_split_aux:Nnn` `\prop_split_aux:Nnn<prop><key><cmd>` invokes `<cmd>` with 3 arguments: 1st is the beginning of `<prop>` before `<key>`, 2nd is the value associated with `<key>`, 3rd is the rest of `<prop>` after `<key>`. If there is no property `<key>` in `<prop>`, then the 2nd argument will be `\q_no_value` and the 3rd argument is empty; otherwise the 3rd argument has the extra tokens `\q_prop <key> \q_prop \q_no_value` at the end.

```

4697 \cs_new:Npn \prop_split_aux:Nnn #1#2#3{
4698   \cs_set:Npn \prop_tmp:w ##1 \q_prop #2 \q_prop ##2##3 \q_stop {
4699     #3 {##1}{##2}{##3}
4700   }
4701   \exp_after:wN \prop_tmp:w \toks_use:N #1 \q_prop #2 \q_prop \q_no_value \q_stop
4702 }

```

`\prop_get:NnN` `\prop_get:NnN <prop><key><tl var.>` defines `<tl var.>` to be the value associated with `<key>` in `<prop>`, `\q_no_value` if not found.

`\prop_get:cnN`

`\prop_get:cVN`

`\prop_get_aux:w`

```

4703 \cs_new:Npn \prop_get:NnN #1#2 {
4704   \prop_split_aux:Nnn #1{#2}\prop_get_aux:w
4705 }
4706 \cs_new:Npn \prop_get_aux:w #1#2#3#4 { \tl_set:Nx #4 {\exp_not:n{#2}} }
4707 \cs_generate_variant:Nn \prop_get:NnN { NVN, cnN, cVN }

```

`\prop_gget:NnN` The global version of the previous function.

`\prop_gget:NVN`

`\prop_gget:NnN`

`\prop_gget:NVN`

`\prop_gget_aux:w`

```

4708 \cs_new:Npn \prop_gget:NnN #1#2{
4709   \prop_split_aux:Nnn #1{#2}\prop_gget_aux:w}
4710 \cs_new:Npn \prop_gget_aux:w #1#2#3#4{\tl_gset:Nx#4{\exp_not:n{#2}}}
4711 \cs_generate_variant:Nn \prop_gget:NnN { NVN, cnN, cVN }

```

`\prop_get_gdel:NnN` `\prop_get_gdel:NnN` is the same as `\prop_get:NnN` but the  $\langle key \rangle$  and its value are afterwards globally removed from  $\langle property\_list \rangle$ . One probably also needs the local variants or only the local one, or... We decide this later.

```

4712 \cs_new:Npn \prop_get_gdel:NnN #1#2#3{
4713   \prop_split_aux:Nnn #1{#2}{\prop_get_del_aux:w #3{\toks_gset:Nn #1}{#2}}}
4714 \cs_new:Npn \prop_get_del_aux:w #1#2#3#4#5#6{
4715   \tl_set:Nx #1{\exp_not:n{#5}}
4716   \quark_if_no_value:NF #1 {
4717     \cs_set_nopar:Npn \prop_tmp:w ##1\q_prop#3\q_prop\q_no_value {#2{#4##1}}
4718     \prop_tmp:w #6}
4719 }

```

`\prop_put:Nnn` `\prop_put:Nnn { $\langle prop \rangle$ } { $\langle key \rangle$ } { $\langle info \rangle$ }` adds/changes the value associated with  $\langle key \rangle$  in  $\langle prop \rangle$  to  $\langle info \rangle$ .

```

4720 \cs_new:Npn \prop_put:Nnn #1#2{
4721   \prop_split_aux:Nnn #1{#2}{
4722     \prop_clear:N #1
4723     \prop_put_aux:w {\toks_put_right:Nn #1}{#2}
4724   }
4725 }
4726 \cs_new:Npn \prop_gput:Nnn #1#2{
4727   \prop_split_aux:Nnn #1{#2}{
4728     \prop_gclear:N #1
4729     \prop_put_aux:w {\toks_gput_right:Nn #1}{#2}
4730   }
4731 }

```

```

4732 \cs_new:Npn \prop_put_aux:w #1#2#3#4#5#6{
4733   #1{\q_prop#2\q_prop{#6}#3}
4734   \tl_if_empty:nF{#5}
4735   {
4736     \cs_set_nopar:Npn \prop_tmp:w ##1\q_prop#2\q_prop\q_no_value {#1{##1}}
4737     \prop_tmp:w #5
4738   }
4739 }

```

```

4740 \cs_generate_variant:Nn \prop_put:Nnn { NnV, NVn, NVV, cnn }
4741 \cs_generate_variant:Nn \prop_gput:Nnn { NnV, Nno, Nnx, Nox, cnn, ccx }

```

`\prop_del:Nn` `\prop_del:Nn  $\langle prop \rangle$   $\langle key \rangle$`  deletes the entry for  $\langle key \rangle$  in  $\langle prop \rangle$ , if any.

```

4742 \cs_new:Npn \prop_del:Nn #1#2{
4743   \prop_split_aux:Nnn #1{#2}{\prop_del_aux:w {\toks_set:Nn #1}{#2}}}
4744 \cs_new:Npn \prop_gdel:Nn #1#2{
4745   \prop_split_aux:Nnn #1{#2}{\prop_del_aux:w {\toks_gset:Nn #1}{#2}}}
4746 \cs_new:Npn \prop_del_aux:w #1#2#3#4#5{

```

```

4747 \cs_set_nopar:Npn \prop_tmp:w {#4}
4748 \quark_if_no_value:NF \prop_tmp:w {
4749   \cs_set_nopar:Npn \prop_tmp:w ##1\q_prop#2\q_prop\q_no_value {#1{#3##1}}
4750   \prop_tmp:w #5
4751 }
4752 }
4753 \cs_generate_variant:Nn \prop_del:Nn { NV }
4754 \cs_generate_variant:Nn \prop_gdel:Nn { NV }
4755 %

```

\prop\_gput\_if\_new:Nnn \prop\_gput\_if\_new:Nnn  $\langle prop \rangle$   $\langle key \rangle$   $\langle info \rangle$  is equivalent to  
\prop\_put\_if\_new\_aux:w

```

\prop_if_in:NnTF  $\langle prop \rangle$   $\langle key \rangle$ 
  {}%
  {\prop_gput:Nnn
     $\langle property\_list \rangle$ 
     $\langle key \rangle$ 
     $\langle info \rangle$ }

```

Here we go (listening to Porgy & Bess in a recording with Ella F. and Louis A. which makes writing macros sometimes difficult; I find myself humming instead of working):

```

4756 \cs_new:Npn \prop_gput_if_new:Nnn #1#2{
4757   \prop_split_aux:Nnn #1{#2}{\prop_put_if_new_aux:w #1{#2}}
4758 \cs_new:Npn \prop_put_if_new_aux:w #1#2#3#4#5#6{
4759   \tl_if_empty:nT {#5}{#1{\q_prop#2\q_prop{#6}#3}}

```

## 108.2 Predicates and conditionals

\prop\_if\_empty\_p:N This conditional takes a  $\langle prop \rangle$  as its argument and evaluates either the true or the false case, depending on whether or not  $\langle prop \rangle$  contains any properties.

```

\prop_if_empty_p:c
\prop_if_empty:N $\underline{TF}$ 
\prop_if_empty:c $\underline{TF}$ 
4760 \prg_new_eq_conditional:Nnn \prop_if_empty:N \toks_if_empty:N {p,TF,T,F}
4761 \prg_new_eq_conditional:Nnn \prop_if_empty:c \toks_if_empty:c {p,TF,T,F}

```

\prop\_if\_eq\_p:NN These functions test whether two property lists are equal.

```

\prop_if_eq_p:cN
\prop_if_eq_p:Nc
4762 \prg_new_eq_conditional:Nnn \prop_if_eq:NN \toks_if_eq:NN {p,TF,T,F}
4763 \prg_new_eq_conditional:Nnn \prop_if_eq:cN \toks_if_eq:cN {p,TF,T,F}
4764 \prg_new_eq_conditional:Nnn \prop_if_eq:Nc \toks_if_eq:Nc {p,TF,T,F}
4765 \prg_new_eq_conditional:Nnn \prop_if_eq:cc \toks_if_eq:cc {p,TF,T,F}
\prop_if_eq:NN $\underline{TF}$ 
\prop_if_eq:Nc $\underline{TF}$ 
\prop_if_eq:cN $\underline{TF}$ 
\prop_if_eq:cc $\underline{TF}$ 
\prop_if_in:NV $\underline{TF}$ 

```

\prop\_if\_in:NnTF  $\langle property\_list \rangle$   $\langle key \rangle$   $\langle true\_case \rangle$   $\langle false\_case \rangle$  will check whether or not  $\langle key \rangle$  is on the  $\langle property\_list \rangle$  and then select either the true or false case.

```

\prop_if_in:No $\underline{TF}$ 
\prop_if_in:cN $\underline{TF}$ 
\prop_if_in:cc $\underline{TF}$ 
\prop_if_in:NV $\underline{TF}$ 
4766 \prg_new_conditional:Nnn \prop_if_in:Nn {TF,T,F} {
4767   \prop_split_aux:Nnn #1 {#2} {\prop_if_in_aux:w}

```



```

4768 }
4769 \cs_new_nopar:Npn \prop_if_in_aux:w #1#2#3 {
4770   \quark_if_no_value:nTF {#2} {\prg_return_false:} {\prg_return_true:}
4771 }

4772 \cs_generate_variant:Nn \prop_if_in:NnTF {NV,No,cn,cc}
4773 \cs_generate_variant:Nn \prop_if_in:NnT {NV,No,cn,cc}
4774 \cs_generate_variant:Nn \prop_if_in:NnF {NV,No,cn,cc}

```

### 108.3 Mapping functions

\prop\_map\_function:NN Maps a function on every entry in the property list. The function must take 2 arguments: a key and a value.  
 \prop\_map\_function:cN  
 \prop\_map\_function:Nc First, some failed attempts:  
 \prop\_map\_function:cc  
 \prop\_map\_function\_aux:w

```

\cs_new_nopar:Npn \prop_map_function:NN #1#2{
  \exp_after:wN \prop_map_function_aux:w
  \exp_after:wN #2 \toks_use:N #1 \q_prop{}\q_prop \q_no_value \q_stop
}
\cs_new_nopar:Npn \prop_map_function_aux:w #1\q_prop#2\q_prop#3{
  \if_predicate:w \tl_if_empty_p:n{#2}
  \exp_after:wN \prop_map_break:
  \fi:
  #1{#2}{#3}
  \prop_map_function_aux:w #1
}

```

problem with the above implementation is that an empty key stops the mapping but all other functions in the module allow the use of empty keys (as one value)

```

\cs_set_nopar:Npn \prop_map_function:NN #1#2{
  \exp_after:wN \prop_map_function_aux:w
  \exp_after:wN #2 \toks_use:N #1 \q_prop \q_no_value \q_prop \q_no_value
}
\cs_set_nopar:Npn \prop_map_function_aux:w #1\q_prop#2\q_prop#3{
  \quark_if_no_value:nF{#2}
  {
    #1{#2}{#3}
    \prop_map_function_aux:w #1
  }
}

```

problem with the above implementation is that \quark\_if\_no\_value:nF is fairly slow and if \quark\_if\_no\_value:NF is used instead we have to do an assignment thus making the mapping not expandable (is that important?)

Here's the current version of the code:

```

4775 \cs_set_nopar:Npn \prop_map_function:NN #1#2 {
4776   \exp_after:wN \prop_map_function_aux:w
4777   \exp_after:wN #2 \toks_use:N #1 \q_prop \q_nil \q_prop \q_no_value \q_stop
4778 }
4779 \cs_set:Npn \prop_map_function_aux:w #1 \q_prop #2 \q_prop #3 {
4780   \if_meaning:w \q_nil #2
4781   \exp_after:wN \prop_map_break:
4782   \fi:
4783   #1{#2}{#3}
4784   \prop_map_function_aux:w #1
4785 }

```

(potential) problem with the above implementation is that it will return true if #2 contains more than just \q\_nil thus executing whatever follows. Claim: this can't happen :-)  
so we should be ok

```

4786 \cs_generate_variant:Nn \prop_map_function:NN {c,Nc,cc}

```

\prop\_map\_inline:Nn  
\prop\_map\_inline:cn  
\g\_prop\_inline\_level\_int

The inline functions are straight forward. It takes longer to test if the list is empty than to run it on an empty list so we don't waste time doing that.

```

4787 \int_new:N \g_prop_inline_level_int
4788 \cs_new_nopar:Npn \prop_map_inline:Nn #1#2 {
4789   \int_gincr:N \g_prop_inline_level_int
4790   \cs_gset:cpn {prop_map_inline_ \int_use:N \g_prop_inline_level_int :n}
4791   ##1##2{#2}
4792   \prop_map_function:Nc #1
4793   {prop_map_inline_ \int_use:N \g_prop_inline_level_int :n}
4794   \int_gdecr:N \g_prop_inline_level_int
4795 }
4796 \cs_generate_variant:Nn \prop_map_inline:Nn {cn}

```

\prop\_map\_break: The break statement.

```

4797 \cs_new_eq:NN \prop_map_break: \use_none_delimit_by_q_stop:w
4798 </initex | package>

```

Show token usage:

```

4799 <*showmemory>
4800 %\showMemUsage
4801 </showmemory>

```

## 109 l3io implementation

We start by ensuring that the required packages are loaded.

```
4802 <*package>
4803 \ProvidesExplPackage
4804   {\filename}{\filedate}{\fileversion}{\filedescription}
4805 \package_check_loaded_expl:
4806 </package>
4807 <*initex | package>
```

This section is primarily concerned with input and output streams. The naming conventions for i/o streams is `ior` (for read) and `iow` (for write) as module names. e.g. `\c_ior_test_stream` is an input stream variable called ‘test’.

### 109.1 Output streams

`\iow_new:N` Allocation of new output streams is done by these functions. As we currently do not  
`\iow_new:c` distribute a new allocation module we nick the `\newwrite` function.

```
4808 <*initex>
4809 \alloc_setup_type:nnn {iow} \c_zero \c_sixteen
4810 \cs_new_nopar:Npn \iow_new:N #1 {\alloc_reg:NnNN g {iow} \tex_chardef:D #1}
4811 </initex>
4812 <*package>
4813 \cs_set_eq:NN \iow_new:N \newwrite
4814 </package>
4815 \cs_generate_variant:Nn \iow_new:N {c}
```

`\iow_open:Nn` To open streams for reading or writing the following two functions are provided. The  
`\iow_open:cn` streams are opened immediately.

From some bad experiences on the mainframe, I learned that it is better to force the close before opening a dataset for writing. We have to check whether this is also necessary in case of `\tex_openin:D`.

```
4816 \cs_new_nopar:Npn \iow_open:Nn #1#2 {
4817   \iow_close:N #1
4818   \tex_immediate:D \tex_openout:D #1#2 \scan_stop:
4819 }
4820 \cs_generate_variant:Nn \iow_open:Nn {c}
```

`\iow_close:N` Since we close output streams prior to opening, a separate closing operation is probably not necessary. But here it is, just in case... Actually you will need this if you intend to write and then read in the same pass from a stream.

```
4821 \cs_new_nopar:Npn \iow_close:N { \tex_immediate:D \tex_closeout:D }
```

`\c_iow_term_stream` Here we allocate two output streams for writing to the transcript file only (`\c_iow_log_stream`)  
`\c_ior_term_stream` and to both the terminal and transcript file (`\c_iow_term_stream`). Both can be used  
`\c_iow_log_stream` to read from and have equivalent `\c_ior` versions.  
`\c_ior_log_stream`

```
4822 \cs_new_eq:NN \c_iow_term_stream \c_sixteen
4823 \cs_new_eq:NN \c_ior_term_stream \c_sixteen
4824 \cs_new_eq:NN \c_iow_log_stream \c_minus_one
4825 \cs_new_eq:NN \c_ior_log_stream \c_minus_one
```

## Immediate writing

`\iow_now:Nx` An abbreviation for an often used operation, which immediately writes its second argument expanded to the output stream.

```
4826 \cs_new_nopar:Npn \iow_now:Nx { \tex_immediate:D \iow_shipout_x:Nn }
```

`\iow_now:Nn` This routine writes the second argument onto the output stream without expansion. If this stream isn't open, the output goes to the terminal instead. If the first argument is no output stream at all, we get an internal error.

```
4827 \cs_new_nopar:Npn \iow_now:Nn #1#2 {
4828   \iow_now:Nx #1 { \exp_not:n {#2} }
4829 }
```

`\iow_log:n` Now we redefine two functions for which we needed a definition very early on.

```
\iow_log:x
\iow_term:n
\iow_term:x
4830 \cs_set_nopar:Npn \iow_log:x { \iow_now:Nx \c_iow_log_stream }
4831 \cs_new_nopar:Npn \iow_log:n { \iow_now:Nn \c_iow_log_stream }
4832 \cs_set_nopar:Npn \iow_term:x { \iow_now:Nx \c_iow_term_stream }
4833 \cs_new_nopar:Npn \iow_term:n { \iow_now:Nn \c_iow_term_stream }
```

`\iow_term:x` isn't exactly equivalent to the old `\typeout` since we need to control expansion in the function we provide for the user.

`\iow_now_when_avail:Nn` `\iow_now_when_avail:Nn`  $\langle stream \rangle$   $\langle code \rangle$ . This routine writes its second argument  
`\iow_now_when_avail:cn` unexpanded to the stream given by the first argument, provided that this stream was  
opened for writing. Note, that # characters get doubled within  $\langle code \rangle$ .

In this routine we have to check whether or not the output stream that was requested is defined at all. So we check if the name is still free.

```
4834 \cs_new_nopar:Npn \iow_now_when_avail:Nn #1 {
4835   \cs_if_free:NTF #1 {\use_none:n} {\iow_now:Nn #1}
4836 }
4837 \cs_generate_variant:Nn \iow_now_when_avail:Nn {c}
```

`\iow_now_buffer_safe:Nn` Another type of writing onto an output stream is used for potentially long token sequences. We break the output lines at every blank in the second argument. This avoids the problem of buffer overflow when reading back, or badly broken lines on systems with limited file records. The only thing we have to take care of, is the danger of two blanks in succession since these get converted into a `\par` when we read the stuff back. But this can happen only if things like two spaces find their way into the second argument. Usually, multiple spaces are removed by  $\text{\TeX}$ 's scanner.

```

4838 \cs_new_nopar:Npn \iow_now_buffer_safe_aux:w #1#2#3 {
4839   \group_begin: \tex_newlinechar:D'\ #1#2{#3} \group_end:
4840 }
4841 \cs_new_nopar:Npn \iow_now_buffer_safe:Nx {
4842   \iow_now_buffer_safe_aux:w \iow_now:Nx
4843 }
4844 \cs_new_nopar:Npn \iow_now_buffer_safe:Nn {
4845   \iow_now_buffer_safe_aux:w \iow_now:Nn
4846 }

```

### Deferred writing

`\iow_shipout_x:Nn` First the easy part, this is the primitive.  
`\iow_shipout_x:Nx`

```

4847 \cs_set_eq:NN \iow_shipout_x:Nn \tex_write:D
4848 \cs_generate_variant:Nn \iow_shipout_x:Nn {Nx}

```

`\iow_shipout:Nn` With  $\varepsilon\text{-}\text{\TeX}$  available deferred writing is easy.  
`\iow_shipout:Nx`

```

4849 \cs_new_nopar:Npn \iow_shipout:Nn #1#2{
4850   \iow_shipout_x:Nn #1 { \exp_not:n {#2} }
4851 }
4852 \cs_generate_variant:Nn \iow_shipout:Nn {Nx}

```

‘Buffer safe’ forms of these functions are not possible since the deferred writing will restore the value of `\tex_newlinechar:D` before it will have a chance to act. But on the other hand it is nevertheless possible to make all deferred writes long by setting the `\tex_newlinechar:D` inside the output routine just before the `\tex_shipout:D`. The only disadvantage of this method is the fact that messages to the terminal during this time will also then break at spaces. But we should consider this.

### Special characters for writing

`\iow_newline:` Global variable holding the character that forces a new line when something is written to an output stream.

```

4853 \cs_new_nopar:Npn \iow_newline: {^^J}

```

`\iow_space:` Global variable holding the character that inserts a space char when writing to an output stream.

```
4854 \cs_new_nopar:Npn \iow_space: {~}
```

`\iow_char:N` Function to write any escaped char to an output stream.

```
4855 \cs_new:Npn \iow_char:N #1 { \cs_to_str:N #1 }
```

`\c_iow_comment_char` TODO: remove these in favour of `\iow_char:N` (Will, Apr 2009)

`\c_iow_lbrace_char`  
`\c_iow_rbrace_char`

We also need to be able to write braces and the comment character. We achieve this by defining global constants to expand into a version of these characters with `\tex_catcode:D = 12`.

```
4856 \tl_new:Nx \c_iow_comment_char {\cs_to_str:N\%}
```

To avoid another allocation function which is probably only necessary here we use the `\cs_set_nopar:Npx` command directly.

```
4857 \tl_new:Nx \c_iow_lbrace_char{\cs_to_str:N\{}
```

```
4858 \tl_new:Nx \c_iow_rbrace_char{\cs_to_str:N\}}
```

## 109.2 Input streams

`\ior_new:N` Allocation of new input streams is done by this function. As we currently do not distribute a new allocation module we nick the `\newwread` function.

```
4859 {*initex}
4860 \alloc_setup_type:nnn {ior} \c_zero \c_sixteen
4861 \cs_new_nopar:Npn \ior_new:N #1 {\alloc_reg:NnNN g {ior} \tex_chardef:D #1}
4862 \}/initex}
4863 {package}\cs_set_eq:NN \ior_new:N \newwread
```

`\ior_open:Nn` Processing of input-streams (via `\tex_openin:D` and `closein`) is always ‘immediate’ as far as  $\TeX$  is concerned. An extra `\tex_immediate:D` is silently ignored.

`\ior_close:N`

```
4864 \cs_set_eq:NN \ior_close:N \tex_closein:D
4865 \cs_new_nopar:Npn \ior_open:Nn #1#2 {
4866   \ior_close:N #1 \scan_stop:
4867   \tex_openin:D #1#2 \scan_stop:
4868 }
```

`\if_eof:w`

```
4869 \cs_new_eq:NN \if_eof:w \tex_ifeof:D
```

`\ior_if_eof_p:N` `\ior_if_eof:N`NTF  $\langle stream \rangle$   $\langle true\ case \rangle$   $\langle false\ case \rangle$ . To test if some particular input stream is exhausted the following conditional is provided:

```
4870 \prg_new_conditional:Nnn \ior_if_eof:N {p,TF,T,F} {
4871   \tex_ifeof:D #1 \prg_return_true: \else: \prg_return_false: \fi:
4872 }
```

`\ior_to:NN` And here we read from files.

```
\ior_gto:NN
4873 \cs_new_nopar:Npn \ior_to:NN #1#2 {
4874   \tex_read:D #1 to #2
4875   \check \chk_local_or_pref_global:N #2
4876 }
4877 \cs_new_nopar:Npn \ior_gto:NN {
4878   \+check \pref_global_chk:
4879   \-check \pref_global:D
4880   \ior_to:NN
4881 }

4882 \</initex | package>
```

Show token usage:

```
4883 \*showmemory>
4884 \showMemUsage
4885 \</showmemory>
```

## 110 l3msg implementation

The usual lead-off.

```
4886 \*package>
4887 \ProvidesExplPackage
4888   {\filename}{\filedate}{\fileversion}{\filedescription}
4889 \package_check_loaded_expl:
4890 \</package>
4891 \*initex | package>
```

L<sup>A</sup>T<sub>E</sub>X is handling context, so the T<sub>E</sub>X “noise” is turned down.

```
4892 \int_set:Nn \tex_errorcontextlines:D { \c_minus_one }
```

### 110.1 Variables and constants

```
\c_msg_fatal_tl Header information.
\c_msg_error_tl
\c_msg_warning_tl
\c_msg_info_tl
4893 \tl_new:Nn \c_msg_fatal_tl { Fatal~Error }
4894 \tl_new:Nn \c_msg_error_tl { Error }
4895 \tl_new:Nn \c_msg_warning_tl { Warning }
4896 \tl_new:Nn \c_msg_info_tl { Info }
```

<code>\c_msg_fatal_text_tl</code> <code>\c_msg_help_text_tl</code> <code>\c_msg_kernel_bug_text_tl</code> <code>\c_msg_kernel_bug_more_text_tl</code> <code>\c_msg_no_info_text_tl</code> <code>\c_msg_return_text_tl</code>	<p>Simple pieces of text for messages.</p> <pre> 4897 \tl_new:Nn \c_msg_fatal_text_tl { 4898   This-is-a-fatal-error:-LaTeX-will~abort 4899 } 4900 \tl_new:Nn \c_msg_help_text_tl { 4901   For~immediate~help~type~H~&lt;return&gt; 4902 } 4903 \tl_new:Nn \c_msg_kernel_bug_text_tl { 4904   This-is-a-LaTeX-bug:~check~coding! 4905 } 4906 \tl_new:Nn \c_msg_kernel_bug_more_text_tl { 4907   There-is-a~coding~bug~somewhere~around~here. 4908   \msg_newline: 4909   This~probably~needs~examining~by~an~expert. 4910   \c_msg_return_text_tl 4911 } 4912 \tl_new:Nn \c_msg_no_info_text_tl { 4913   LaTeX~does~not~know~anything~more~about~this~error,~sorry. 4914   \c_msg_return_text_tl 4915 } 4916 \tl_new:Nn \c_msg_return_text_tl { 4917   \msg_two_newlines: 4918   Try~typing~&lt;return&gt;~to~proceed. 4919   \msg_newline: 4920   If~that~doesn't~work,~type~X~&lt;return&gt;~to~quit 4921 } </pre>
<code>\c_msg_hide_tl&lt;spaces&gt;</code>	<p>An empty variable with a number of (category code 11) spaces at the end of its name. This is used to push the T<sub>E</sub>X part of an error message “off the screen”.</p> <p>No indentation here as <code>␣</code> is a letter!</p> <pre> 4922 \group_begin: 4923 \char_make_letter:N\ % 4924 \tl_to_lowercase:n{% 4925 \group_end:% 4926 \tl_new:Nn% 4927 \c_msg_hide_tl 4928 }% 4929 }% </pre>
<code>\c_msg_on_line_tl</code>	<p>Text for “on line”.</p> <pre> 4930 \tl_new:Nn \c_msg_on_line_tl { on~line } </pre>
<code>\c_msg_text_prefix_tl</code> <code>\c_msg_more_text_prefix_tl</code>	<p>Prefixes for storage areas.</p> <pre> 4931 \tl_new:Nn \c_msg_text_prefix_tl { msg_text ~&gt;~ } 4932 \tl_new:Nn \c_msg_more_text_prefix_tl { msg_text_more ~&gt;~ } </pre>



`\l_msg_class_tl` For holding the current message method and that for redirection.  
`\l_msg_current_class_tl`

```
4933 \tl_new:N \l_msg_class_tl
4934 \tl_new:N \l_msg_current_class_tl
```

`\l_msg_names_clist` Lists used for filtering.

```
4935 \clist_new:N \l_msg_names_clist
```

`\l_msg_redirect_classes_prop` For filtering messages, a list of all messages and of those which have to be modified is  
`\l_msg_redirect_names_prop` required.

```
4936 \prop_new:N \l_msg_redirect_classes_prop
4937 \prop_new:N \l_msg_redirect_names_prop
```

`\l_msg_redirect_classes_clist` To prevent an infinite loop.

```
4938 \clist_new:N \l_msg_redirect_classes_clist
```

## 110.2 Output helper functions

`\msg_line_number:` For writing the line number nicely.

`\msg_line_context:`

```
4939 \cs_new_nopar:Npn \msg_line_number: {
4940   \toks_use:N \tex_inputlineno:D
4941 }
4942 \cs_new_nopar:Npn \msg_line_context: {
4943   \c_msg_on_line_tl
4944   \msg_space:
4945   \msg_line_number:
4946 }
```

`\msg_newline:` Always forces a new line.

`\msg_two_newlines:`

```
4947 \cs_new_nopar:Npn \msg_newline: { ^^J }
4948 \cs_new_nopar:Npn \msg_two_newlines: { ^^J ^^J }
```

`\msg_space:` For printing spaces, some very simple functions.

`\msg_two_spaces:`

`\msg_four_spaces:`

```
4949 \cs_new_nopar:Npn \msg_space: { ~ }
4950 \cs_new_nopar:Npn \msg_two_spaces: { \msg_space: \msg_space: }
4951 \cs_new_nopar:Npn \msg_four_spaces: {
4952   \msg_two_spaces: \msg_two_spaces:
4953 }
```

### 110.3 Generic functions

The lowest level functions make no assumptions about modules, *etc.*

`\msg_generic_new:nnn`    Creating a new message is basically the same as the non-checking version, and so after a  
`\msg_generic_new:nn`    check everything hands over.

```
4954 \cs_new_nopar:Npn \msg_generic_new:nnn #1 {
4955   \chk_if_free_cs:c { \c_msg_text_prefix_tl #1 :xxxx }
4956   \msg_generic_set:nnn {#1}
4957 }
4958 \cs_new_nopar:Npn \msg_generic_new:nn #1 {
4959   \chk_if_free_cs:c { \c_msg_text_prefix_tl #1 :xxxx }
4960   \msg_generic_set:nn {#1}
4961 }
```

`\msg_generic_set:nnn`    Creating a message is quite simple. There must be a short text part, while the longer  
`\msg_generic_set:nn`    text may or may not be available.

```
\msg_generic_set_clist:n
\msg_generic_set_text:n
\msg_generic_set_more_text:n
4962 \cs_new_nopar:Npn \msg_generic_set:nnn #1 {
4963   \msg_generic_set_clist:n {#1}
4964   \char_make_space:N \
4965   \msg_generic_set_more_text:nnn {#1}
4966 }
4967 \cs_new_nopar:Npn \msg_generic_set:nn #1 {
4968   \msg_generic_set_clist:n {#1}
4969   \char_make_space:N \
4970   \msg_generic_set_text:nn {#1}
4971 }
4972 \cs_new_nopar:Npn \msg_generic_set_clist:n #1 {
4973   \clist_if_in:NnF \l_msg_names_clist { // #1 / } {
4974     \clist_put_right:Nn \l_msg_names_clist { // #1 / }
4975   }
4976 }
4977 \cs_new:Npn \msg_generic_set_text:nn #1#2 {
4978   \cs_set:cpn { \c_msg_text_prefix_tl #1 :xxxx } ##1##2##3##4 {#2}
4979   \cs_set_eq:cN { \c_msg_more_text_prefix_tl #1 :xxxx } \c_undefined
4980   \char_make_ignore:N \
4981 }
4982 \cs_new:Npn \msg_generic_set_more_text:nnn #1#2#3 {
4983   \cs_set:cpn { \c_msg_text_prefix_tl #1 :xxxx } ##1##2##3##4 {#2}
4984   \cs_set:cpn { \c_msg_more_text_prefix_tl #1 :xxxx } ##1##2##3##4 {#3}
4985   \char_make_ignore:N \
4986 }
```

`\msg_direct_interrupt:xxxx`    The low-level interruption macro is rather opaque, unfortunately. The idea here is to  
`\msg_direct_interrupt:n`    create a a message which hides all of TeX's own information by filling the output up  
                                  with spaces. To achieve this, spaces have to be letters: hence no indentation. The odd

`\c_msg_hide_tl<spaces>` actually does the hiding: it is the large run of spaces in the name that is important here. The meaning of `\\` is altered so that the explanation text is a simple run whilst the initial error has line-continuation shown.

```

4987 \group_begin:
4988   \char_set_lccode:nn {'\&} {'\ } % {
4989   \char_set_lccode:w '\} = '\ \scan_stop:
4990   \char_make_active:N \&
4991   \char_make_letter:N\ %
4992   \tl_to_lowercase:n{%
4993   \group_end:%
4994   \cs_new_protected:Npn\msg_direct_interrupt:xxxx#1#2#3#4{%
4995   \group_begin:%
4996   \cs_set_eq:NN\\ \msg_newline:%
4997   \cs_set_eq:NN\ \msg_space:%
4998   \msg_direct_interrupt_aux:n{#4}%
4999   \cs_set_nopar:Npn\\{\msg_newline:#3}%
5000   \tex_errhelp:D\l_msg_tmp_tl%
5001   \cs_set:Npn&{%
5002   \tex_errmessage:D{%
5003   #1\msg_newline:%
5004   #2\msg_two_newlines:%
5005   \c_msg_help_text_tl%
5006   \c_msg_hide_tl                                     %
5007   }%
5008   }%
5009   &%
5010   \group_end:%
5011   }%
5012   }%
5013   \cs_new:Npn \msg_direct_interrupt_aux:n #1 {
5014     \tl_if_empty:nTF {#1} {
5015       \tl_set:Nx \l_msg_tmp_tl { { \c_msg_no_info_text_tl } }
5016     }{
5017       \tl_set:Nx \l_msg_tmp_tl { {#1} }
5018     }
5019   }

```

`\msg_direct_log:xx` Printing to the log or terminal without a stop is rather easier.  
`\msg_direct_term:xx`

```

5020 \cs_new_protected:Npn \msg_direct_log:xx #1#2 {
5021   \group_begin:
5022     \cs_set:Npn \\ { \msg_newline: #2 }
5023     \cs_set_eq:NN \ \msg_space:
5024     \iow_log:x { #1 \msg_newline: }
5025   \group_end:
5026 }
5027 \cs_new_protected:Npn \msg_direct_term:xx #1#2 {
5028   \group_begin:
5029     \cs_set:Npn \\ { \msg_newline: #2 }

```

```

5030     \cs_set_eq:NN \ \msg_space:
5031     \iow_term:x { #1 \msg_newline: }
5032   \group_end:
5033 }

```

## 110.4 General functions

The main functions for messaging are built around the separation of module from the message name. These have short names as they will be widely used.

```

\msg_new:nnnn For making messages: all aliases.
\msg_new:nnn
\msg_set:nnnn
\msg_set:nnn
5034 \cs_new_nopar:Npn \msg_new:nnnn #1#2 {
5035   \msg_generic_new:nnn { #1 / #2 }
5036 }
5037 \cs_new_nopar:Npn \msg_new:nnn #1#2 {
5038   \msg_generic_new:nn { #1 / #2 }
5039 }
5040 \cs_new_nopar:Npn \msg_set:nnnn #1#2 {
5041   \msg_generic_set:nnn { #1 / #2 }
5042 }
5043 \cs_new_nopar:Npn \msg_set:nnn #1#2 {
5044   \msg_generic_set:nn { #1 / #2 }
5045 }

```

```

\msg_class_new:nn Creating a new class produces three new functions, with varying numbers of arguments.
\msg_class_set:nn The \msg_class_loop:n function is set up so that redirection will work as desired.

```

```

5046 \cs_new_nopar:Npn \msg_class_new:nn #1 {
5047   \chk_if_free_cs:c { msg_ #1 :nnxxxx }
5048   \prop_new:c { l_msg_redirect_ #1 _prop }
5049   \msg_class_set:nn {#1}
5050 }
5051 \cs_new_nopar:Npn \msg_class_set:nn #1#2 {
5052   \prop_clear:c { l_msg_redirect_ #1 _prop }
5053   \cs_set_protected:cpn { msg_ #1 :nnxxxx } ##1##2##3##4##5##6 {
5054     \msg_use:nnnnxxxx {#1} {#2} {##1} {##2} {##3} {##4} {##5} {##6}
5055   }
5056   \cs_set_protected:cpx { msg_ #1 :nnxxx } ##1##2##3##4##5 {
5057     \exp_not:c { msg_ #1 :nnxxxx } {##1} {##2} {##3} {##4} {##5} { }
5058   }
5059   \cs_set_protected:cpx { msg_ #1 :nnxx } ##1##2##3##4 {
5060     \exp_not:c { msg_ #1 :nnxxxx } {##1} {##2} {##3} {##4} { } { }
5061   }
5062   \cs_set_protected:cpx { msg_ #1 :nnx } ##1##2##3 {
5063     \exp_not:c { msg_ #1 :nnxxxx } {##1} {##2} {##3} { } { } { }
5064   }
5065   \cs_set_protected:cpx { msg_ #1 :nn } ##1##2 {

```

```

5066     \exp_not:c { msg_ #1 :nnxxxx } {##1} {##2} { } { } { } { }
5067   }
5068 }

```

`\msg_use:nnnnxxxx` The main message-using macro creates two auxiliary functions: one containing the code for the message, and the second a loop function. There is then a hand-off to the system for checking if redirection is needed.

```

5069 \cs_new:Npn \msg_use:nnnnxxxx #1#2#3#4#5#6#7#8 {
5070   \cs_set_nopar:Npn \msg_use_code: {
5071     \clist_clear:N \l_msg_redirect_classes_clist
5072     #2
5073   }
5074   \cs_set:Npn \msg_use_loop:n ##1 {
5075     \clist_if_in:NnTF \l_msg_redirect_classes_clist {#1} {
5076       \msg_kernel_error:nn { msg } { redirect-loop } {#1}
5077     }{
5078       \clist_put_right:Nn \l_msg_redirect_classes_clist {#1}
5079       \cs_if_exist:cTF { msg_ ##1 :nnxxxx } {
5080         \use:c { msg_ ##1 :nnxxxx } {#3} {#4} {#5} {#6} {#7} {#8}
5081       }{
5082         \msg_kernel_error:nnx { msg } { message-class-unknown } {##1}
5083       }
5084     }
5085   }
5086   \cs_if_exist:cTF { \c_msg_text_prefix_tl #3 / #4 :xxxx } {
5087     \msg_use_aux:nnn {#1} {#3} {#4}
5088   }{
5089     \msg_kernel_error:nnxx { msg } { message-unknown } {#3} {#4}
5090   }
5091 }

```

`\msg_use_code:` Blank definitions are initially created for these functions.

`\msg_use_loop:`

```

5092 \cs_new_nopar:Npn \msg_use_code: { }
5093 \cs_new:Npn \msg_use_loop:n #1 { }

```

`\msg_use_aux:nnn` The first auxiliary macro looks for a match by name: the most restrictive check.

```

5094 \cs_new_nopar:Npn \msg_use_aux:nnn #1#2#3 {
5095   \tl_set:Nn \l_msg_current_class_tl {#1}
5096   \tl_set:Nn \l_msg_current_module_tl {#2}
5097   \prop_if_in:NnTF \l_msg_redirect_names_prop { // #2 / #3 / } {
5098     \msg_use_loop_check:nn { names } { // #2 / #3 / }
5099   }{
5100     \msg_use_aux:nn {#1} {#2}
5101   }
5102 }

```

`\msg_use_aux:nn` The second function checks for general matches by module or for all modules.

```

5103 \cs_new_nopar:Npn \msg_use_aux:nn #1#2 {
5104   \prop_if_in:cnTF { l_msg_redirect_ #1 _prop } {#2} {
5105     \msg_use_loop_check:nn {#1} {#2}
5106   }{
5107     \prop_if_in:cnTF { l_msg_redirect_ #1 _prop } { * } {
5108       \msg_use_loop_check:nn {#1} { * }
5109     }{
5110       \msg_use_code:
5111     }
5112   }
5113 }

```

`\msg_use_loop_check:nn` When checking whether to loop, the same code is needed in a few places.

```

5114 \cs_new:Npn \msg_use_loop_check:nn #1#2 {
5115   \prop_get:cnN { l_msg_redirect_ #1 _prop } {#2} \l_msg_class_tl
5116   \tl_if_eq:NNTF \l_msg_current_class_tl \l_msg_class_tl {
5117     \msg_use_code:
5118   }{
5119     \msg_use_loop:n { \l_msg_class_tl }
5120   }
5121 }

```

`\msg_fatal:nnxxxx` For fatal errors, after the error message TeX bails out.

```

\msg_fatal:nnxxx
\msg_fatal:nnxxx
\msg_fatal:nnxx
\msg_fatal:nnx
\msg_fatal:nn
5122 \msg_class_new:nn { fatal } {
5123   \msg_direct_interrupt:xxxx
5124   { \c_msg_fatal_tl \msg_two_newlines: }
5125   {
5126     ( \c_msg_fatal_tl ) \msg_space:
5127     \use:c { \c_msg_text_prefix_tl #1 / #2 :xxxx } {#3} {#4} {#5} {#6}
5128   }
5129   { ( \c_msg_fatal_tl ) \msg_space: }
5130   { \c_msg_fatal_text_tl }
5131   \tex_end:D
5132 }

```

`\msg_error:nnxxxx` For an error, the interrupt routine is called, then any recovery code is tried.

```

\msg_error:nnxxx
\msg_error:nnxxx
\msg_error:nnxx
\msg_error:nnx
\msg_error:nn
5133 \msg_class_new:nn { error } {
5134   \msg_direct_interrupt:xxxx
5135   { #1~\c_msg_error_tl \msg_newline: }
5136   {
5137     ( #1 ) \msg_space:
5138     \use:c { \c_msg_text_prefix_tl #1 / #2 :xxxx } {#3} {#4} {#5} {#6}
5139   }
5140   { ( #1 ) \msg_space: }
5141   {

```

```

5142     \cs_if_exist:cTF { \c_msg_more_text_prefix_tl #1 / #2 :xxxx }
5143     {
5144         \use:c { \c_msg_more_text_prefix_tl #1 / #2 :xxxx }
5145         {#3} {#4} {#5} {#6}
5146     }
5147     { \c_msg_no_info_text_tl }
5148 }
5149 }

```

\msg\_warning:nnxxxx Warnings are printed to the terminal.

```

\msg_warning:nnxxxx
\msg_warning:nnxxx
\msg_warning:nnxx
\msg_warning:nnx
\msg_warning:nn
5150 \msg_class_new:nn { warning } {
5151     \msg_direct_term:xx {
5152         \msg_space: #1 ~ \c_msg_warning_tl :~
5153         \use:c { \c_msg_text_prefix_tl #1 / #2 :xxxx } {#3} {#4} {#5} {#6}
5154     }
5155     { ( #1 ) \msg_two_spaces: }
5156 }

```

\msg\_info:nnxxxx Information only goes into the log.

```

\msg_info:nnxxxx
\msg_info:nnxxx
\msg_info:nnxx
\msg_info:nnx
\msg_info:nn
5157 \msg_class_new:nn { info } {
5158     \msg_direct_log:xx {
5159         \msg_space: #1~\c_msg_info_tl :~
5160         \use:c { \c_msg_text_prefix_tl #1 / #2 :xxxx } {#3} {#4} {#5} {#6}
5161     }
5162     { ( #1 ) \msg_two_spaces: }
5163 }

```

\msg\_log:nnxxxx “Log” data is very similar to information, but with no extras added.

```

\msg_log:nnxxxx
\msg_log:nnxxx
\msg_log:nnxx
\msg_log:nnx
\msg_log:nn
5164 \msg_class_new:nn { log } {
5165     \msg_direct_log:xx {
5166         \use:c { \c_msg_text_prefix_tl #1 / #2 :xxxx } {#3} {#4} {#5} {#6}
5167     }
5168     { }
5169 }

```

\msg\_trace:nnxxxx Trace data is the same as log data, more or less

```

\msg_trace:nnxxxx
\msg_trace:nnxxx
\msg_trace:nnxx
\msg_trace:nnx
\msg_trace:nn
5170 \msg_class_new:nn { trace } {
5171     \msg_direct_log:xx {
5172         \use:c { \c_msg_text_prefix_tl #1 / #2 :xxxx } {#3} {#4} {#5} {#6}
5173     }
5174     { }
5175 }

```

\msg\_none:nnxxxx The none message type is needed so that input can be gobbled.

```

\msg_none:nnxxxx
\msg_none:nnxxx
\msg_none:nnxx
\msg_none:nnx
\msg_none:nn
5176 \msg_class_new:nn { none } { }

```

## 110.5 Redirection functions

`\msg_redirect_class:nn` Converts class one into class two.

```
5177 \cs_new_nopar:Npn \msg_redirect_class:nn #1#2 {
5178   \prop_put:cnn { l_msg_redirect_ #1 _prop } { * } {#2}
5179 }
```

`\msg_redirect_module:nnn` For when all messages of a class should be altered for a given module.

```
5180 \cs_new_nopar:Npn \msg_redirect_module:nnn #1#2#3 {
5181   \prop_put:cnn { l_msg_redirect_ #2 _prop } {#1} {#3}
5182 }
```

`\msg_redirect_name:nnn` Named message will always use the given class.

```
5183 \cs_new_nopar:Npn \msg_redirect_name:nnn #1#2#3 {
5184   \prop_put:Nnn \l_msg_redirect_names_prop { // #1 / #2 / } {#3}
5185 }
```

## 110.6 Kernel-specific functions

`\msg_kernel_new:nnnn` The kernel needs some messages of its own. These are created using pre-built functions.  
`\msg_kernel_new:nnn` Two functions are provided: one more general and one which only has the short text  
`\msg_kernel_set:nnnn` part.  
`\msg_kernel_set:nnn`

```
5186 \cs_new_nopar:Npn \msg_kernel_new:nnnn #1#2 {
5187   \msg_new:nnnn { LaTeX } { #1 / #2 }
5188 }
5189 \cs_new_nopar:Npn \msg_kernel_new:nnn #1#2 {
5190   \msg_new:nnn { LaTeX } { #1 / #2 }
5191 }
5192 \cs_new_nopar:Npn \msg_kernel_set:nnnn #1#2 {
5193   \msg_set:nnnn { LaTeX } { #1 / #2 }
5194 }
5195 \cs_new_nopar:Npn \msg_kernel_set:nnn #1#2 {
5196   \msg_set:nnn { LaTeX } { #1 / #2 }
5197 }
```

`\msg_kernel_classes_new:n` Quickly make the fewer-arguments versions.

```
5198 \cs_new_nopar:Npn \msg_kernel_classes_new:n #1 {
5199   \cs_new_protected:cpx { msg_kernel_ #1 :nnxxx } ##1##2##3##4##5
5200   {
5201     \exp_not:c { msg_kernel_ #1 :nnxxxx }
5202     {##1} {##2} {##3} {##4} {##5} { }
5203   }
5204   \cs_new_protected:cpx { msg_kernel_ #1 :nnxx } ##1##2##3##4
```



```

5205 {
5206   \exp_not:c { msg_kernel_ #1 :nnxxxx }
5207   {##1} {##2} {##3} {##4} { } { }
5208 }
5209 \cs_new_protected:cpx { msg_kernel_ #1 :nnx } ##1##2##3
5210 {
5211   \exp_not:c { msg_kernel_ #1 :nnxxxx } {##1} {##2} {##3} { } { } { }
5212 }
5213 \cs_new_protected:cpx { msg_kernel_ #1 :nn } ##1##2
5214 {
5215   \exp_not:c { msg_kernel_ #1 :nnxxxx } {##1} {##2} { } { } { } { }
5216 }
5217 }

```

\msg\_kernel\_fatal:nnxxxx Fatal kernel errors cannot be re-defined.

```

\msg_kernel_fatal:nnxxxx
\msg_kernel_fatal:nnxxx
\msg_kernel_fatal:nnxx
\msg_kernel_fatal:nnx
\msg_kernel_fatal:nn
5218 \cs_new_protected:Npn \msg_kernel_fatal:nnxxxx #1#2#3#4#5#6 {
5219   \msg_direct_interrupt:xxxx
5220   { \c_msg_fatal_tl \msg_two_newlines: }
5221   {
5222     ( LaTeX ) \msg_space:
5223     \use:c { \c_msg_text_prefix_tl LaTeX / #1 / #2 :xxxx }
5224     {#3} {#4} {#5} {#6}
5225   }
5226   { ( LaTeX ) \msg_space: }
5227   { \c_msg_fatal_text_tl }
5228   \tex_end:D
5229 }
5230 \msg_kernel_classes_new:n { fatal }

```

\msg\_kernel\_error:nnxxxx Neither can kernel errors.

```

\msg_kernel_error:nnxxxx
\msg_kernel_error:nnxxx
\msg_kernel_error:nnxx
\msg_kernel_error:nnx
\msg_kernel_error:nn
5231 \cs_new_protected:Npn \msg_kernel_error:nnxxxx #1#2#3#4#5#6 {
5232   \msg_direct_interrupt:xxxx
5233   { LaTeX~\c_msg_error_tl \msg_newline: }
5234   {
5235     ( LaTeX ) \msg_space:
5236     \use:c { \c_msg_text_prefix_tl LaTeX / #1 / #2 :xxxx }
5237     {#3} {#4} {#5} {#6}
5238   }
5239   { ( LaTeX ) \msg_space: }
5240   {
5241     \cs_if_exist:cTF
5242     { \c_msg_more_text_prefix_tl LaTeX / #1 / #2 :xxxx }
5243     {
5244       \use:c { \c_msg_more_text_prefix_tl LaTeX / #1 / #2 :xxxx }
5245       {#3} {#4} {#5} {#6}
5246     }
5247     { \c_msg_no_info_text_tl }
5248   }

```

```

5249 }
5250 \msg_kernel_classes_new:n { error }

```

`\msg_kernel_warning:nnxxxx` Life is much more simple for warnings and information messages, as these are just short-cuts to the standard classes.

```

\msg_kernel_warning:nnxxx
\msg_kernel_warning:nnxx
\msg_kernel_warning:nnx
\msg_kernel_warning:nn
\msg_kernel_info:nnxxxx
\msg_kernel_info:nnxxx
\msg_kernel_info:nnxx
\msg_kernel_info:nnx
\msg_kernel_info:nn
5251 \cs_new_protected_nopar:Npn \msg_kernel_warning:nnxxxx #1#2 {
5252   \msg_warning:nnxxxx { LaTeX } { #1 / #2 }
5253 }
5254 \msg_kernel_classes_new:n { warning }
5255 \cs_new_protected_nopar:Npn \msg_kernel_info:nnxxxx #1#2 {
5256   \msg_info:nnxxxx { LaTeX } { #1 / #2 }
5257 }
5258 \msg_kernel_classes_new:n { info }

```

Error messages needed to actually implement the message system itself.

```

5259 \msg_kernel_new:nnnn { msg } { message-unknown }
5260 {Unknown message ‘#2’ for module ‘#1’..}
5261 {%
5262   LaTeX was asked to display a message by the ‘#1’ module.\%
5263   The message was supposed to be called ‘#2’, but I can’t\%
5264   find a message with that name.%
5265   \c_msg_return_text_tl
5266 }
5267 \msg_kernel_new:nnnn { msg } { message-class-unknown }
5268 {Unknown message class ‘#1’..}
5269 {%
5270   You have asked for a message to be redirected to class ‘#1’.\%
5271   The message class ‘#1’ has not been set up:\%
5272   perhaps this is a typing error.%
5273   \c_msg_return_text_tl
5274 }
5275 \msg_kernel_new:nnnn { msg } { redirect-loop }
5276 {Message redirection loop for message class ‘#1’..}
5277 {%
5278   You have asked for a message to be redirected,\%
5279   but the redirection instructions form a loop:\%
5280   you’ve lost the message.%
5281   \c_msg_return_text_tl
5282 }

```

`\msg_kernel_bug:x` The L<sup>A</sup>T<sub>E</sub>X coding bug error gets re-visited here.

```

5283 \cs_set_protected:Npn \msg_kernel_bug:x #1 {
5284   \msg_direct_interrupt:xxxx
5285   { \c_msg_kernel_bug_text_tl }
5286   { !~#1 }
5287   { ! }

```

```

5288     { \c_msg_kernel_bug_more_text_tl }
5289 }

5290 </initex | package>

```

## 111 l3box implementation

Announce and ensure that the required packages are loaded.

```

5291 <*package>
5292 \ProvidesExplPackage
5293   {\filename}{\filedate}{\fileversion}{\filedescription}
5294 \package_check_loaded_expl:
5295 </package>
5296 <*initex | package>

```

The code in this module is very straight forward so I'm not going to comment it very extensively.

### 111.1 Generic boxes

`\box_new:N` Defining a new  $\langle box \rangle$  register.  
`\box_new:c`

```

5297 <*initex>
5298 \alloc_setup_type:nnn {box} \c_zero \c_max_register_num

```

Now, remember that `\box255` has a special role in  $\text{\TeX}$ , it shouldn't be allocated...

```

5299 \seq_put_right:Nn \g_box_allocation_seq {255}
5300 \cs_new_nopar:Npn \box_new:N #1 {\alloc_reg:NnNN g {box} \tex_mathchardef:D #1}
5301 \cs_new_nopar:Npn \box_new_l:N #1 {\alloc_reg:NnNN l {box} \tex_mathchardef:D #1}
5302 </initex>

```

When we run on top of  $\text{\LaTeX}$ , we just use its allocation mechanism.

```

5303 <*package>
5304 \cs_new:Npn \box_new:N #1 {
5305   \chk_if_free_cs:N #1
5306   \newbox #1
5307 }
5308 </package>

5309 \cs_generate_variant:Nn \box_new:N {c}

```

`\if_hbox:N` The primitives for testing if a  $\langle box \rangle$  is empty/void or which type of box it is.  
`\if_vbox:N`  
`\if_box_empty:N`

```

5310 \cs_new_eq:NN \if_hbox:N \tex_ifhbox:D
5311 \cs_new_eq:NN \if_vbox:N \tex_ifvbox:D
5312 \cs_new_eq:NN \if_box_empty:N \tex_ifvoid:D

```

```

\box_if_horizontal_p:N
\box_if_horizontal_p:c
  \box_if_vertical_p:N
  \box_if_vertical_p:c
\box_if_horizontal:N\TF
\box_if_horizontal:c\TF
  \box_if_vertical:N\TF
  \box_if_vertical:c\TF
5313 \prg_new_conditional:Nnn \box_if_horizontal:N {p,TF,T,F} {
5314   \tex_ifhbox:D #1 \prg_return_true: \else: \prg_return_false: \fi:
5315 }
5316 \prg_new_conditional:Nnn \box_if_vertical:N {p,TF,T,F} {
5317   \tex_ifvbox:D #1 \prg_return_true: \else: \prg_return_false: \fi:
5318 }
5319 \cs_generate_variant:Nn \box_if_horizontal_p:N {c}
5320 \cs_generate_variant:Nn \box_if_horizontal:N\TF {c}
5321 \cs_generate_variant:Nn \box_if_horizontal:NT {c}
5322 \cs_generate_variant:Nn \box_if_horizontal:NF {c}
5323 \cs_generate_variant:Nn \box_if_vertical_p:N {c}
5324 \cs_generate_variant:Nn \box_if_vertical:N\TF {c}
5325 \cs_generate_variant:Nn \box_if_vertical:NT {c}
5326 \cs_generate_variant:Nn \box_if_vertical:NF {c}

\box_if_empty_p:N Testing if a  $\langle box \rangle$  is empty/void.
\box_if_empty_p:c
\box_if_empty:N\TF
\box_if_empty:c\TF
5327 \prg_new_conditional:Nnn \box_if_empty:N {p,TF,T,F} {
5328   \tex_ifvoid:D #1 \prg_return_true: \else: \prg_return_false: \fi:
5329 }
5330 \cs_generate_variant:Nn \box_if_empty_p:N {c}
5331 \cs_generate_variant:Nn \box_if_empty:N\TF {c}
5332 \cs_generate_variant:Nn \box_if_empty:NT {c}
5333 \cs_generate_variant:Nn \box_if_empty:NF {c}

\box_set_eq:NN Assigning the contents of a box to be another box. This clears the second box globally
\box_set_eq:cN (that's how TeX does it).
\box_set_eq:Nc
\box_set_eq:cc
5334 \cs_new_nopar:Npn \box_set_eq:NN #1#2 {\tex_setbox:D #1 \tex_box:D #2}
5335 \cs_generate_variant:Nn \box_set_eq:NN {cN,Nc,cc}

\box_gset_eq:NN Global version of the above.
\box_gset_eq:cN
\box_gset_eq:Nc
\box_gset_eq:cc
5336 \cs_new_nopar:Npn \box_gset_eq:NN {\pref_global:D\box_set_eq:NN}
5337 \cs_generate_variant:Nn \box_gset_eq:NN {cN,Nc,cc}

\l_last_box A different name for this read-only primitive.
5338 \cs_new_eq:NN \l_last_box \tex_lastbox:D

\box_set_to_last:N Set a box to the previous box.
\box_set_to_last:c
\box_gset_to_last:N
\box_gset_to_last:c
5339 \cs_new_nopar:Npn \box_set_to_last:N #1{\tex_setbox:D#1\l_last_box}
5340 \cs_generate_variant:Nn \box_set_to_last:N {c}
5341 \cs_new_nopar:Npn \box_gset_to_last:N {\pref_global:D \box_set_to_last:N}
5342 \cs_generate_variant:Nn \box_gset_to_last:N {c}

```

<code>\box_move_left:nn</code>	Move box material in different directions.
<code>\box_move_right:nn</code>	
<code>\box_move_up:nn</code>	5343 <code>\cs_new:Npn \box_move_left:nn #1#2{\tex_moveleft:D\dim_eval:n{#1}{#2}}</code>
<code>\box_move_down:nn</code>	5344 <code>\cs_new:Npn \box_move_right:nn #1#2{\tex_moveright:D\dim_eval:n{#1}{#2}}</code>
	5345 <code>\cs_new:Npn \box_move_up:nn #1#2{\tex_raise:D\dim_eval:n{#1}{#2}}</code>
	5346 <code>\cs_new:Npn \box_move_down:nn #1#2{\tex_lower:D\dim_eval:n{#1}{#2}}</code>
 <code>\box_clear:N</code>	Clear a $\langle box \rangle$ register.
<code>\box_clear:c</code>	
<code>\box_gclear:N</code>	5347 <code>\cs_new_nopar:Npn \box_clear:N #1{\box_set_eq:NN #1 \c_empty_box }</code>
<code>\box_gclear:c</code>	5348 <code>\cs_generate_variant:Nn \box_clear:N {c}</code>
	5349 <code>\cs_new_nopar:Npn \box_gclear:N {\pref_global:D\box_clear:N}</code>
	5350 <code>\cs_generate_variant:Nn \box_gclear:N {c}</code>
 <code>\box_ht:N</code>	Accessing the height, depth, and width of a $\langle box \rangle$ register.
<code>\box_ht:c</code>	
<code>\box_dp:N</code>	5351 <code>\cs_new_eq:NN \box_ht:N \tex_ht:D</code>
<code>\box_dp:c</code>	5352 <code>\cs_new_eq:NN \box_dp:N \tex_dp:D</code>
<code>\box_wd:N</code>	5353 <code>\cs_new_eq:NN \box_wd:N \tex_wd:D</code>
<code>\box_wd:c</code>	5354 <code>\cs_generate_variant:Nn \box_ht:N {c}</code>
	5355 <code>\cs_generate_variant:Nn \box_dp:N {c}</code>
	5356 <code>\cs_generate_variant:Nn \box_wd:N {c}</code>
 <code>\box_use_clear:N</code>	Using a $\langle box \rangle$ . These are just T <sub>E</sub> X primitives with meaningful names.
<code>\box_use_clear:c</code>	
<code>\box_use:N</code>	5357 <code>\cs_new_eq:NN \box_use_clear:N \tex_box:D</code>
<code>\box_use:c</code>	5358 <code>\cs_generate_variant:Nn \box_use_clear:N {c}</code>
	5359 <code>\cs_new_eq:NN \box_use:N \tex_copy:D</code>
	5360 <code>\cs_generate_variant:Nn \box_use:N {c}</code>
 <code>\box_show:N</code>	Show the contents of a box and write it into the log file.
<code>\box_show:c</code>	
	5361 <code>\cs_set_eq:NN \box_show:N \tex_showbox:D</code>
	5362 <code>\cs_generate_variant:Nn \box_show:N {c}</code>
 <code>\c_empty_box</code>	We allocate some $\langle box \rangle$ registers here (and borrow a few from L <sup>A</sup> T <sub>E</sub> X).
<code>\l_tmpa_box</code>	
<code>\l_tmpb_box</code>	5363 <code>\(package)\cs_set_eq:NN \c_empty_box \voidb@x</code>
	5364 <code>\(package)\cs_new_eq:NN \l_tmpa_box \@tempboxa</code>
	5365 <code>\(initex)\box_new:N \c_empty_box</code>
	5366 <code>\(initex)\box_new:N \l_tmpa_box</code>
	5367 <code>\box_new:N \l_tmpb_box</code>

## 111.2 Vertical boxes

`\vbox:n` Put a vertical box directly into the input stream.

5368 `\cs_new_nopar:Npn \vbox:n {\tex_vbox:D \scan_stop:}`

`\vbox_set:Nn` Storing material in a vertical box with a natural height.  
`\vbox_set:cn`  
`\vbox_gset:Nn` 5369 `\cs_new:Npn \vbox_set:Nn #1#2 {\tex_setbox:D #1 \tex_vbox:D {#2}}`  
`\vbox_gset:cn` 5370 `\cs_generate_variant:Nn \vbox_set:Nn {cn}`  
5371 `\cs_new_nopar:Npn \vbox_gset:Nn {\pref_global:D \vbox_set:Nn}`  
5372 `\cs_generate_variant:Nn \vbox_gset:Nn {cn}`

`\vbox_set_to_ht:Nnn` Storing material in a vertical box with a specified height.  
`\vbox_set_to_ht:cnn`  
`\vbox_gset_to_ht:Nnn` 5373 `\cs_new:Npn \vbox_set_to_ht:Nnn #1#2#3 {`  
`\vbox_gset_to_ht:cnn` 5374 `\tex_setbox:D #1 \tex_vbox:D to #2 {#3}`  
`\vbox_gset_to_ht:ccn` 5375 `}`  
5376 `\cs_generate_variant:Nn \vbox_set_to_ht:Nnn {cnn}`  
5377 `\cs_new_nopar:Npn \vbox_gset_to_ht:Nnn {\pref_global:D \vbox_set_to_ht:Nnn }`  
5378 `\cs_generate_variant:Nn \vbox_gset_to_ht:Nnn {cnn,ccn}`

`\vbox_set_inline_begin:N` Storing material in a vertical box. This type is useful in environment definitions.  
`\vbox_set_inline_end:`  
`\vbox_gset_inline_begin:N` 5379 `\cs_new_nopar:Npn \vbox_set_inline_begin:N #1 {`  
`\vbox_gset_inline_end:` 5380 `\tex_setbox:D #1 \tex_vbox:D \c_group_begin_token }`  
5381 `\cs_new_eq:NN \vbox_set_inline_end: \c_group_end_token`  
5382 `\cs_new_nopar:Npn \vbox_gset_inline_begin:N {`  
5383 `\pref_global:D \vbox_set_inline_begin:N }`  
5384 `\cs_new_eq:NN \vbox_gset_inline_end: \c_group_end_token`

`\vbox_to_ht:nn` Put a vertical box directly into the input stream.  
`\vbox_to_zero:n` 5385 `\cs_new:Npn \vbox_to_ht:nn #1#2{\tex_vbox:D to \dim_eval:n{#1}{#2}}`  
5386 `\cs_new:Npn \vbox_to_zero:n #1 {\tex_vbox:D to \c_zero_dim {#1}}`

`\vbox_set_split_to_ht:NNn` Splitting a vertical box in two.  
5387 `\cs_new_nopar:Npn \vbox_set_split_to_ht:NNn #1#2#3{`  
5388 `\tex_setbox:D #1 \tex_vsplit:D #2 to #3`  
5389 `}`

`\vbox_unpack:N` Unpacking a box and if requested also clear it.  
`\vbox_unpack:c`  
`\vbox_unpack_clear:N` 5390 `\cs_new_eq:NN \vbox_unpack:N \tex_unvcopy:D`  
`\vbox_unpack_clear:c` 5391 `\cs_generate_variant:Nn \vbox_unpack:N {c}`  
5392 `\cs_new_eq:NN \vbox_unpack_clear:N \tex_unvbox:D`  
5393 `\cs_generate_variant:Nn \vbox_unpack_clear:N {c}`

### 111.3 Horizontal boxes

`\hbox:n` Put a horizontal box directly into the input stream.  
5394 `\cs_new_nopar:Npn \hbox:n {\tex_hbox:D \scan_stop:}`

<code>\hbox_set:Nn</code> <code>\hbox_set:cn</code> <code>\hbox_gset:Nn</code> <code>\hbox_gset:cn</code>	<p>Assigning the contents of a box to be another box. This clears the second box globally (that's how <math>\TeX</math> does it).</p> <pre> 5395 \cs_new:Npn \hbox_set:Nn #1#2 {\tex_setbox:D #1 \tex_hbox:D {#2}} 5396 \cs_generate_variant:Nn \hbox_set:Nn {cn} 5397 \cs_new_nopar:Npn \hbox_gset:Nn {\pref_global:D \hbox_set:Nn} 5398 \cs_generate_variant:Nn \hbox_gset:Nn {cn} </pre>
<code>\hbox_set_to_wd:Nnn</code> <code>\hbox_set_to_wd:cnn</code> <code>\hbox_gset_to_wd:Nnn</code> <code>\hbox_gset_to_wd:cnn</code>	<p>Storing material in a horizontal box with a specified width.</p> <pre> 5399 \cs_new:Npn \hbox_set_to_wd:Nnn #1#2#3 { 5400   \tex_setbox:D #1 \tex_hbox:D to \dim_eval:n{#2} {#3} 5401 } 5402 \cs_generate_variant:Nn \hbox_set_to_wd:Nnn {cnn} 5403 \cs_new_nopar:Npn \hbox_gset_to_wd:Nnn {\pref_global:D \hbox_set_to_wd:Nnn } 5404 \cs_generate_variant:Nn \hbox_gset_to_wd:Nnn {cnn} </pre>
<code>\hbox_set_inline_begin:N</code> <code>\hbox_set_inline_begin:c</code> <code>\hbox_set_inline_end:</code> <code>\hbox_gset_inline_begin:N</code> <code>\hbox_gset_inline_begin:c</code> <code>\hbox_gset_inline_end:</code>	<p>Storing material in a horizontal box. This type is useful in environment definitions.</p> <pre> 5405 \cs_new_nopar:Npn \hbox_set_inline_begin:N #1 { 5406   \tex_setbox:D #1 \tex_hbox:D \c_group_begin_token 5407 } 5408 \cs_generate_variant:Nn \hbox_set_inline_begin:N {c} 5409 \cs_new_eq:NN \hbox_set_inline_end: \c_group_end_token 5410 \cs_new_nopar:Npn \hbox_gset_inline_begin:N { 5411   \pref_global:D \hbox_set_inline_begin:N 5412 } 5413 \cs_generate_variant:Nn \hbox_gset_inline_begin:N {c} 5414 \cs_new_eq:NN \hbox_gset_inline_end: \c_group_end_token </pre>
<code>\hbox_to_wd:nn</code> <code>\hbox_to_zero:n</code>	<p>Put a horizontal box directly into the input stream.</p> <pre> 5415 \cs_new:Npn \hbox_to_wd:nn #1#2 {\tex_hbox:D to #1 {#2}} 5416 \cs_new:Npn \hbox_to_zero:n #1 {\tex_hbox:D to \c_zero_skip {#1}} </pre>
<code>\hbox_unpack:N</code> <code>\hbox_unpack:c</code> <code>\hbox_unpack_clear:N</code> <code>\hbox_unpack_clear:c</code>	<p>Unpacking a box and if requested also clear it.</p> <pre> 5417 \cs_new_eq:NN \hbox_unpack:N \tex_unhcopy:D 5418 \cs_generate_variant:Nn \hbox_unpack:N {c} 5419 \cs_new_eq:NN \hbox_unpack_clear:N \tex_unhbox:D 5420 \cs_generate_variant:Nn \hbox_unpack_clear:N {c}  5421 \&lt;/initex   package&gt;  5422 \&lt;showmemory&gt; 5423 \showMemUsage 5424 \&lt;/showmemory&gt; </pre>

## 112 l3xref implementation

### 112.1 Internal functions and variables

`\g_xref_all_curr_immediate_fields_prop`  
`\g_xref_all_curr_deferred_fields_prop` What they say they are :)

`\xref_write` A stream for writing cross references, although they are not required to be in a separate file.

`\xref_define_label:nn` `\xref_define_label:nn {<name>} {<plist contents>}`

Define the property list for each label; used internally by `\xref_set_label:n`.

### 112.2 Module code

We start by ensuring that the required packages are loaded.

```

5425 <*package>
5426 \ProvidesExplPackage
5427   {\filename}{\filedate}{\fileversion}{\filedescription}
5428 \package_check_loaded_expl:
5429 </package>
5430 <*initex | package>

```

There are two kinds of information, namely information which is *immediate* like a section title and then there's *deferred* information like page numbers. Each reference type belong to one of these categories, which we save internally as the property lists `\g_xref_all_curr_immediate_fields_prop` and `\g_xref_all_curr_deferred_fields_prop` and the reference type `<xyz>` exists as the key-info pair `\xref-<xyz>-key {\l_xref_curr-<xyz>-tl}` on one of these lists. This way each new entry type is just added as another key-info pair.

When the cross references are generated at the beginning of the document each will turn into a control sequence. Thus `\label{mylab}` will internally refer to the property list `\g_xref_mylab_prop`.

The extraction of values from this property list can be done in several different ways but we want to keep the operation expandable. Therefore we use a dedicated function for each type of cross reference, which looks like this:

```
\xref_get_value_xyz_aux:w -> #1 \xref_xyz_key #2#3\q_nil{#2}
```



This will throw away all the bits we don't need. In case `xyz` is the first on the `mylab` property list `#1` is empty, if it's the last key-info pair `#3` is empty. The value of the field can be extracted with the function `\xref_get_value:nn` where the first argument is the type and the second the label name so here it would be `\xref_get_value:nn {xyz} {mylab}`.

`_all_curr_immediate_fields_prop` `_all_curr_deferred_fields_prop` The two main property lists for storing information. They contain key-info pairs for all known types.

```
5431 \prop_new:N \g_xref_all_curr_immediate_fields_prop
5432 \prop_new:N \g_xref_all_curr_deferred_fields_prop
```

`\xref_new:nn` `\xref_deferred_new:nn` `\xref_new_aux:nnn` Setting up a new cross reference type is fairly straight forward when we follow the game plan mentioned earlier.

```
5433 \cs_new_nopar:Npn \xref_new:nn {\xref_new_aux:nnn{immediate}}
5434 \cs_new_nopar:Npn \xref_deferred_new:nn {\xref_new_aux:nnn{deferred}}
5435 \cs_new_nopar:Npn \xref_new_aux:nnn #1#2#3{
```

First put the new type in the relevant property list.

```
5436 \prop_gput:ccx {g_xref_all_curr_ #1 _fields_prop}
5437 { xref_ #2 _key }
5438 { \exp_not:c {l_xref_curr_#2_tl } }
```

Then define the key to be a protected macro.<sup>13</sup>

```
5439 \cs_set_protected_nopar:cpn { xref_#2_key }{ }
5440 \tl_new:cn{l_xref_curr_#2_tl}{#3}
```

Now for the function extracting the value of a reference. We could do this with a simple `\prop_if_in` thing put since we want to do things in an expandable way we make a separate grabber for each type—this is also faster. The grabber function can be defined by using an intricate construction of `\exp_after:wN` and other goodies but I prefer readable code. The end result for the input `xyz` is

```
\cs_set_nopar:Npn\xref_get_value_xyz_aux:w #1\xref_xyz_key #2#3\q_nil{#2}
```

```
5441 \toks_set:Nx \l_tmpa_toks {
5442   \exp_not:n { \cs_set_nopar:cpn {xref_get_value_#2_aux:w} ##1 }
5443   \exp_not:N \q_prop
5444   \exp_not:c { xref_#2_key }
5445   \exp_not:N \q_prop
5446 }
5447 \toks_use:N \l_tmpa_toks ##2 ##3\q_nil {##2}
5448 }
```

---

<sup>13</sup>We could also set it equal to `\scan_stop:` but this just feels “cleaner”.

`\xref_get_value:nn` Getting the correct value for a given label-type pair is a matter of connecting the correct grabber functions and property list.

```
5449 \cs_new_nopar:Npn \xref_get_value:nn #1#2 {
5450   \cs_if_exist:cTF{g_xref_#2_prop}
5451   {
```

This next expansion may look a little weird but it isn't if you think about it!

```
5452     \exp_args:NcNc \exp_after:wN {xref_get_value_#1_aux:w}
5453     \toks_use:N {g_xref_#2_prop}
```

Better put in the stop marker.

```
5454     \q_nil
5455   }
5456   {??}
5457 }
```

Temporary! We expand the property list and so we can't have the `\q_prop` marker just expand!

```
5458 \cs_set_nopar:Npn \exp_after:cc #1#2 {
5459   \exp_after:wN \exp_after:wN
5460   \cs:w #1\exp_after:wN\cs_end: \cs:w #2\cs_end:
5461 }
5462 \cs_set_protected:Npn \q_prop {\q_prop}
```

`\xref_define_label:nn` Define the property list for each label. We better do this in two steps because the special catcode regime is in effect and since some of the info fields are very likely to contain actual text, we better make sure spaces aren't ignored! As for the meaning of other characters then it is a possibility to also have a field containing catcode instructions which can then be activated with `\etex_scantokens:D`.

```
5463 \cs_new_protected_nopar:Npn \xref_define_label:nn {
5464   \group_begin:
5465   \char_set_catcode:nn {'\ } \c_ten
5466   \xref_define_label_aux:nn
5467 }
```

If the label is already taken we have a multiply defined label and we should do something about it. For now we don't do anything spectacular.

```
5468 \cs_new_nopar:Npn \xref_define_label_aux:nn #1#2 {
5469   \cs_if_free:cTF{g_xref_#1_prop}
5470   {\prop_new:c{g_xref_#1_prop}}{\WARNING}
5471   \toks_gset:cn{g_xref_#1_prop}{#2}
5472   \group_end:
5473 }
```

`\xref_set_label:n` Then the generic command for setting a label. We expand the immediate labels fully before calling the write function but make sure the deferred fields aren't expanded just yet. Due to property lists being implemented as token list registers we must expand the 'immediate' fields twice.

```

5474 \cs_set_nopar:Npn \xref_set_label:n #1{
5475   \cs_set_nopar:Npx \xref_tmp:w{\toks_use:N\g_xref_all_curr_immediate_fields_prop}
5476   \exp_args:NNx\iow_shipout_x:Nn \xref_write{
5477     \xref_define_label:nn {#1} {
5478       \xref_tmp:w
5479       \toks_use:N \g_xref_all_curr_deferred_fields_prop
5480     }
5481   }
5482 }

```

`\xref_write` A stream for writing cross references although they do not require to be in a separate file.

```

5483 \iow_new:N \xref_write

```

That's it (for now).

```

5484 </initex | package>
5485 <*showmemory>
5486 \showMemUsage
5487 </showmemory>

```

## 113 l3xref test file

```

5488 <*testfile>
5489 \documentclass{article}
5490 \usepackage{l3xref}
5491 \ExplSyntaxOn
5492 \cs_set_nopar:Npn \startrecording {\iow_open:Nn \xref_write {\jobname.xref}}
5493 \cs_set_nopar:Npn \DefineCrossReferences {
5494   \group_begin:
5495     \ExplSyntaxNamesOn
5496     \InputIfFileExists{\jobname.xref}{\}{}
5497   \group_end:
5498 }
5499 \AtBeginDocument{\DefineCrossReferences\startrecording}
5500
5501 \xref_new:nn {name}{\}
5502 \cs_set_nopar:Npn \setname{\tl_set:Nn\l_xref_curr_name_tl}
5503 \cs_set_nopar:Npn \getname{\xref_get_value:nn{name}}
5504
5505 \xref_deferred_new:nn {page}{\thepage}

```

```

5506 \cs_set_nopar:Npn \getpage{\xref_get_value:nn{page}}
5507
5508 \xref_deferred_new:nn {valuepage}{\number\value{page}}
5509 \cs_set_nopar:Npn \getvaluepage{\xref_get_value:nn{valuepage}}
5510
5511 \cs_set_eq:NN \setlabel \xref_set_label:n
5512
5513 \ExplSyntaxOff
5514 \begin{document}
5515 \pagenumbering{roman}
5516
5517 Text\setname{This is a name}\setlabel{testlabel1}. More
5518 text\setname{This is another name}\setlabel{testlabel2}. \clearpage
5519
5520 Text\setname{This is a third name}\setlabel{testlabel3}. More
5521 text\setname{Hello World!}\setlabel{testlabel4}. \clearpage
5522
5523 \pagenumbering{arabic}
5524
5525 Text\setname{Name 5}\setlabel{testlabel5}. More text\setname{Name
5526 6}\setlabel{testlabel6}. \clearpage
5527
5528 Text\setname{Name 7}\setlabel{testlabel 7}. More text\setname{Name
5529 8}\setlabel{testlabel8}. \clearpage
5530
5531 Now let's extract some values. \getname{testlabel1} on page
5532 \getpage{testlabel1} with value \getvaluepage{testlabel1}.
5533
5534 Now let's extract some values. \getname{testlabel 7} on page
5535 \getpage{testlabel 7} with value \getvaluepage{testlabel 7}.
5536 \end{document}
5537 </testfile>

```

## 114 l3keyval implementation

### 114.1 Internal functions and variables

```

\l_KV_tmpa_tl
\l_KV_tmpp_tl
\c_KV_single_equal_sign_tl
\l_KV_parse_toks
\l_KV_currkey_toks
\l_KV_currval_toks

```

Token list variables and token registers used internally.

```

\KV_sanitize_outerlevel_active_equals:N
\KV_sanitize_outerlevel_active_commas:N
\KV_sanitize_outerlevel_active_equals:N <tl var.>

```

Replaces catcode other = and , within a  $\langle tl\ var.\rangle$  with active characters.

<code>\KV_remove_surrounding_spaces:nw</code>	<code>\KV_remove_surrounding_spaces:nw <math>\langle toks \rangle</math> <math>\langle token\ list \rangle</math> \q</code>
<code>\KV_remove_surrounding_spaces_auxi:w *</code>	<code>\KV_remove_surrounding_spaces_auxi:w <math>\langle token\ list \rangle</math> \Q<sub>3</sub></code>

Removes a possible leading space plus a possible ending space from a  $\langle token\ list \rangle$ . The first version (which is not used in the code) stores it in  $\langle toks \rangle$ .

<code>\KV_add_value_element:w</code>	<code>\KV_set_key_element:w <math>\langle token\ list \rangle</math> \q_nil</code>
<code>\KV_set_key_element:w</code>	<code>\KV_add_value_element:w \q_stop <math>\langle token\ list \rangle</math> \q_nil</code>

Specialised functions to strip spaces from their input and set the token registers `\l_KV_currkey_toks` or `\l_KV_currval_toks` respectively.

<code>\KV_split_key_value_current:w</code>	<code>\KV_split_key_value_current:w ...</code>
<code>\KV_split_key_value_space_removal:w</code>	
<code>\KV_split_key_value_space_removal_detect_error:wTF</code>	
<code>\KV_split_key_value_no_space_removal:w</code>	

These functions split keyval lists into chunks depending which sanitising method is being used. `\KV_split_key_value_current:w` is `\cs_set_eq:NN` to whichever is appropriate.

## 114.2 Module code

We start by ensuring that the required packages are loaded.

```

5538 <*package>
5539 \ProvidesExplPackage
5540   {\filename}{\filedate}{\fileversion}{\filedescription}
5541 \package_check_loaded_expl:
5542 </package>
5543 <*initex | package>

```

<code>\l_KV_tmpa_tl</code>	Various useful things.
<code>\l_KV_tmpp_tl</code>	
<code>\c_KV_single_equal_sign_tl</code>	

```

5544 \tl_new:N \l_KV_tmpa_tl
5545 \tl_new:N \l_KV_tmpp_tl
5546 \tl_new:Nn \c_KV_single_equal_sign_tl{=}

```

<code>\l_KV_parse_toks</code>	Some more useful things.
<code>\l_KV_currkey_toks</code>	
<code>\l_KV_currval_toks</code>	

```

5547 \toks_new:N \l_KV_parse_toks
5548 \toks_new:N \l_KV_currkey_toks
5549 \toks_new:N \l_KV_currval_toks

```

`\remove_one_level_of_braces_bool` A boolean to control

```
5550 \bool_new:N \l_KV_remove_one_level_of_braces_bool
5551 \bool_set_true:N \l_KV_remove_one_level_of_braces_bool
```

`\size_outterlevel_active_equals:N` Some functions for sanitizing top level equals and commas. Replace `=13` and `,13` with `=12`  
`\size_outterlevel_active_commas:N` and `,12` resp.

```
5552 \group_begin:
5553 \char_set_catcode:nn{'\={}{13}
5554 \char_set_catcode:nn{'\,}{13}
5555 \char_set_lccode:nn{'\8}{'\= }
5556 \char_set_lccode:nn{'\9}{'\, }
5557 \tl_to_lowercase:n{\group_end:
5558 \cs_new_nopar:Npn \KV_sanitize_outterlevel_active_equals:N #1{
5559   \tl_replace_all_in:Nnn #1 = 8
5560 }
5561 \cs_new_nopar:Npn \KV_sanitize_outterlevel_active_commas:N #1{
5562   \tl_replace_all_in:Nnn #1 , 9
5563 }
5564 }
```

`\KV_remove_surrounding_spaces:nw` The macro `\KV_remove_surrounding_spaces:nw` removes a possible leading space plus  
`\remove_surrounding_spaces_auxi:w` a possible ending space from its second argument and stores it in the token register #1.

`\remove_surrounding_spaces_auxii:w` Based on Around the Bend No. 15 but with some enhancements. For instance, this  
`\KV_set_key_element:w` definition is purely expandable.  
`\KV_add_value_element:w`

We use a funny token  $Q_3$  as a delimiter.

```
5565 \group_begin:
5566 \char_set_catcode:nn{'\Q}{3}

5567 \cs_gnew:Npn \KV_remove_surrounding_spaces:nw#1#2\q_nil{
```

The idea in this processing is to use a  $Q$  with strange catcode to remove a trailing space. But first, how to get this expansion going?

If you have read the fine print in the `l3expan` module, you'll know that the `f` type expansion will expand until the first non-expandable token is seen and if this token is a space, it will be gobbled. Sounds useful for removing a leading space but we also need to make sure that it does nothing but removing that space! Therefore we prepend the argument to be trimmed with an `\exp_not:N`. Now why is that? `\exp_not:N` in itself is an expandable command so will allow the `f` expansion to continue. If the first token in the argument to be trimmed is a space, it will be gobbled and the expansion stop. If the first token isn't a space, the `\exp_not:N` turns it temporarily into `\scan_stop:` which is unexpandable. The processing stops but the token following directly after `\exp_not:N` is now back to normal.

The function here allows you to insert arbitrary functions in the first argument but they should all be with an `f` type expansion. For the application in this module, we use `\toks_set:Nf`.

Once the expansion has been kick-started, we apply `\KV_remove_surrounding_spaces_auxi:w` to the replacement text of `#2`, adding a leading `\exp_not:N`. Note that no braces are stripped off of the original argument.

```
5568   #1{\KV_remove_surrounding_spaces_auxi:w \exp_not:N#2Q~Q}
5569 }
```

`\KV_remove_surrounding_spaces_auxi:w` removes a trailing space if present, then calls `\KV_remove_surrounding_spaces_auxii:w` to clean up any leftover bizarre Qs. In order for `\KV_remove_surrounding_spaces_auxii:w` to work properly we need to put back a Q first.

```
5570 \cs_gnew:Npn\KV_remove_surrounding_spaces_auxi:w#1~Q{
5571   \KV_remove_surrounding_spaces_auxii:w #1 Q
5572 }
```

Now all that is left to do is remove a leading space which should be taken care of by the function used to initiate the expansion. Simply return the argument before the funny Q.

```
5573 \cs_gnew:Npn\KV_remove_surrounding_spaces_auxii:w#1Q#2{#1}
```

Here are some specialized versions of the above. They do exactly what we want in one go. First trim spaces from the value and then put the result surrounded in braces onto `\l_KV_parse_toks`.

```
5574 \cs_gnew:Npn\KV_add_value_element:w\q_stop#1\q_nil{
5575   \toks_set:Nf\l_KV_currval_toks {
5576     \KV_remove_surrounding_spaces_auxi:w \exp_not:N#1Q~Q
5577   }
5578   \toks_put_right:No\l_KV_parse_toks{
5579     \exp_after:wN {\toks_use:N \l_KV_currval_toks}
5580   }
5581 }
```

When storing the key we firstly remove spaces plus the prepended `\q_no_value`.

```
5582 \cs_gnew:Npn\KV_set_key_element:w#1\q_nil{
5583   \toks_set:Nf\l_KV_currkey_toks
5584   {
5585     \exp_last_unbraced:NNo \KV_remove_surrounding_spaces_auxi:w
5586     \exp_not:N \use_none:n #1Q~Q
5587   }
```

Afterwards we gobble an extra level of braces if that's what we are asked to do.

```
5588 \bool_if:NT \l_KV_remove_one_level_of_braces_bool
5589 {
```

```

5590 \exp_args:NNo \toks_set:N \l_KV_currkey_toks {
5591 \exp_after:wN \KV_add_element_aux:w
5592 \toks_use:N \l_KV_currkey_toks \q_nil
5593 }
5594 }
5595 }
5596 \group_end:

```

`\KV_add_element_aux:w` A helper function for fixing braces around keys and values.

```

5597 \cs_new:Npn \KV_add_element_aux:w#1\q_nil{#1}

```

Parse a list of keyvals, put them into list form with entries like `\KV_key_no_value_elt:n{key1}` and `\KV_key_value_elt:nn{key2}{val2}`.

`\KV_parse_sanitiz_aux:n` The slow parsing algorithm sanitizes active commas and equal signs at the top level first. Then uses `#1` as inspector of each element in the comma list.

```

5598 \cs_new:Npn \KV_parse_sanitiz_aux:n #1 {
5599 \group_begin:
5600 \toks_clear:N \l_KV_parse_toks
5601 \tl_set:Nx \l_KV_tmpa_tl { \exp_not:n {#1} }
5602 \KV_sanitiz_outerlevel_active_equals:N \l_KV_tmpa_tl
5603 \KV_sanitiz_outerlevel_active_commas:N \l_KV_tmpa_tl
5604 \exp_last_unbraced:NNV \KV_parse_elt:w \q_no_value
5605 \l_KV_tmpa_tl , \q_nil ,

```

We evaluate the parsed keys and values outside the group so the token register is restored to its previous value.

```

5606 \exp_last_unbraced:NV \group_end:
5607 \l_KV_parse_toks
5608 }

```

`\KV_parse_no_sanitiz_aux:n` Like above but we don't waste time sanitizing. This is probably the one we will use for preamble parsing where catcodes of `=` and `,` are as expected!

```

5609 \cs_new:Npn \KV_parse_no_sanitiz_aux:n #1{
5610 \group_begin:
5611 \toks_clear:N \l_KV_parse_toks
5612 \KV_parse_elt:w \q_no_value #1 , \q_nil ,
5613 \exp_last_unbraced:NV \group_end:
5614 \l_KV_parse_toks
5615 }

```

`\KV_parse_elt:w` This function will always have a `\q_no_value` stuffed in as the rightmost token in `#1`. In case there was a blank entry in the comma separated list we just run it again. The



`\use_none:n` makes sure to gobble the quark `\q_no_value`. A similar test is made to check if we hit the end of the recursion.

```
5616 \cs_set:Npn \KV_parse_elt:w #1,{
5617   \tl_if_blank:oTF{\use_none:n #1}
5618   { \KV_parse_elt:w \q_no_value }
5619   {
5620     \quark_if_nil:oF {\use_ii:nn #1 }

```

If we made it to here we can start parsing the key and value. When done try, try again.

```
5621   {
5622     \KV_split_key_value_current:w #1==\q_nil
5623     \KV_parse_elt:w \q_no_value
5624   }
5625 }
5626 }
```

`\KV_split_key_value_current:w` The function called to split the keys and values.

```
5627 \cs_new:Npn \KV_split_key_value_current:w {\ERROR}
```

We provide two functions for splitting keys and values. The reason being that most of the time, we should probably be in the special coding regime where spaces are ignored. Hence it makes no sense to spend time searching for extra space tokens and we can do the settings directly. When comparing these two versions (neither doing any sanitizing) the `no_space_removal` version is more than 40% faster than `space_removal`.

It is up to functions like `\DeclareTemplate` to check which catcode regime is active and then pick up the version best suited for it.

`\KV_split_key_value_space_removal:w` The code below removes extraneous spaces around the keys and values plus one set of braces around the entire value.

`\KV_split_key_value_space_removal_detect_error:wTF`

`\KV_split_key_value_space_removal_aux:w`

Unlike the version to be used when spaces are ignored, this one only grabs the key which is everything up to the first `=` and save the rest for closer inspection. Reason is that if a user has entered `mykey={myval}`, then the outer braces have already been removed before we even look at what might come after the key. So this is slightly more tedious (but only slightly) but at least it always removes only one level of braces.

```
5628 \cs_new:Npn \KV_split_key_value_space_removal:w #1 = #2\q_nil{
```

First grab the key.

```
5629   \KV_set_key_element:w#1\q_nil
```

Then we start checking. If only a key was entered, `#2` contains `=` and nothing else, so we test for that first.

```
5630   \tl_set:Nx\l_KV_tmpa_tl{\exp_not:n{#2}}
5631   \tl_if_eq:NNTF\l_KV_tmpa_tl\c_KV_single_equal_sign_tl
```

Then we just insert the default key.

```

5632 {
5633   \toks_put_right:No\l_KV_parse_toks{
5634     \exp_after:wN \KV_key_no_value_elt:n
5635     \exp_after:wN {\toks_use:N\l_KV_currkey_toks}
5636   }
5637 }

```

Otherwise we must take a closer look at what is left. The remainder of the original list up to the comma is now stored in #2 plus an additional ==, which wasn't gobbled during the initial reading of arguments. If there is an error then we can see at least one more = so we call an auxiliary function to check for this.

```

5638 {
5639   \KV_split_key_value_space_removal_detect_error:wTF#2\q_no_value\q_nil
5640   {\KV_split_key_value_space_removal_aux:w \q_stop #2}
5641   {\ERROR}
5642 }
5643 }

```

The error test.

```

5644 \cs_new:Npn
5645   \KV_split_key_value_space_removal_detect_error:wTF#1=#2#3\q_nil{
5646   \tl_if_head_eq_meaning:nNTF{#3}\q_no_value
5647 }

```

Now we can start extracting the value. Recall that #1 here starts with \q\_stop so all braces are still there! First we try to see how much is left if we gobble three brace groups from #1. If #1 is empty or blank, all three quarks are gobbled. If #1 consists of exactly one token or brace group, only the latter quark is left.

```

5648 \cs_new:Npn \KV_val_preserve_braces:NnN #1#2#3{{#2}}
5649 \cs_new:Npn\KV_split_key_value_space_removal_aux:w #1=={
5650   \tl_set:Nx\l_KV_tmpa_tl{\exp_not:o{\use_none:nnn#1\q_nil\q_nil}}
5651   \toks_put_right:No\l_KV_parse_toks{
5652     \exp_after:wN \KV_key_value_elt:nn
5653     \exp_after:wN {\toks_use:N\l_KV_currkey_toks}
5654   }

```

If there a blank space or nothing at all, \l\_KV\_tmpa\_tl is now completely empty.

```

5655   \tl_if_empty:NTF\l_KV_tmpa_tl

```

We just put an empty value on the stack.

```

5656   { \toks_put_right:Nn\l_KV_parse_toks{}} }
5657   {

```

If there was exactly one brace group or token in #1, \l\_KV\_tmpa\_tl is now equal to \q\_nil. Then we can just pick it up as the second argument of #1. This will also take care of any spaces which might surround it.

```

5658 \quark_if_nil:NTF\l_KV_tmpa_tl
5659 {
5660   \bool_if:NTF \l_KV_remove_one_level_of_braces_bool
5661   {
5662     \toks_put_right:No\l_KV_parse_toks{
5663       \exp_after:wN{\use_ii:nnn #1\q_nil}
5664     }
5665   }
5666   {
5667     \toks_put_right:No\l_KV_parse_toks{
5668       \exp_after:wN{KV_val_preserve_braces:NnN #1\q_nil}
5669     }
5670   }
5671 }

```

Otherwise we grab the value.

```

5672 { \KV_add_value_element:w #1\q_nil }
5673 }
5674 }

```

it\_key\_value\_no\_space\_removal:w This version is for when in the special coding regime where spaces are ignored so there is no need to do any fancy space hacks, however fun they may be. Since there are no spaces, a set of braces around a value is automatically stripped by T<sub>E</sub>X.

```

5675 \cs_new:Npn \KV_split_key_value_no_space_removal:w #1#2=#3=#4\q_nil{
5676   \tl_set:Nn\l_KV_tmpa_tl{#4}
5677   \tl_if_empty:NTF \l_KV_tmpa_tl
5678   {
5679     \toks_put_right:Nn\l_KV_parse_toks{KV_key_no_value_elt:n{#2}}
5680   }
5681   {
5682     \tl_if_eq:NNTF\c_KV_single_equal_sign_tl\l_KV_tmpa_tl
5683     {
5684       \toks_put_right:Nn\l_KV_parse_toks{KV_key_value_elt:nn{#2}{#3}}
5685     }
5686     {\ERROR}
5687   }
5688 }

```

\KV\_key\_no\_value\_elt:n  
 \KV\_key\_value\_elt:nn

```

5689 \cs_new:Npn \KV_key_no_value_elt:n #1{\ERROR}
5690 \cs_new:Npn \KV_key_value_elt:nn #1#2{\ERROR}

```

`\no_space_removal_no_sanitize:n` Finally we can put all the things together. `\KV_parse_no_space_removal_no_sanitize:n` is the version that disallows unmatched conditional and does no space removal.

```
5691 \cs_new_nopar:Npn \KV_parse_no_space_removal_no_sanitize:n {
5692   \cs_set_eq:NN \KV_split_key_value_current:w \KV_split_key_value_no_space_removal:w
5693   \KV_parse_no_sanitize_aux:n
5694 }
```

`\KV_parse_space_removal_sanitize:n` The other varieties can be defined in a similar manner. For the version needed at the document level, we can use this one.

```
5695 \cs_new_nopar:Npn \KV_parse_space_removal_sanitize:n {
5696   \cs_set_eq:NN \KV_split_key_value_current:w \KV_split_key_value_space_removal:w
5697   \KV_parse_sanitize_aux:n
5698 }
```

For preamble use by the non-programmer this is probably best.

```
5699 \cs_new_nopar:Npn \KV_parse_space_removal_no_sanitize:n {
5700   \cs_set_eq:NN \KV_split_key_value_current:w \KV_split_key_value_space_removal:w
5701   \KV_parse_no_sanitize_aux:n
5702 }

5703 </initex | package>

5704 <*showmemory>
5705 \showMemUsage
5706 </showmemory>
```

The usual preliminaries.

```
5707 <*package>
5708 \ProvidesExplPackage
5709   {\filename}{\filedate}{\fileversion}{\filedescription}
5710 \package_check_loaded_expl:
5711 </package>
5712 <*initex | package>
```

### 114.2.1 Variables and constants

`\c_keys_root_tl` Where the keys are really stored.  
`\c_keys_properties_root_tl`

```
5713 \tl_new:Nn \c_keys_root_tl { keys~>~ }
5714 \tl_new:Nn \c_keys_properties_root_tl { keys_properties }
```

`\c_keys_value_forbidden_tl` Two marker token lists.  
`\c_keys_value_required_tl`

```
5715 \tl_new:Nn \c_keys_value_forbidden_tl { forbidden }
5716 \tl_new:Nn \c_keys_value_required_tl { required }
```

<code>\l_keys_choice_int</code>	Used for the multiple choice system.
<code>\l_keys_choice_tl</code>	<pre> 5717 \int_new:N \l_keys_choice_int 5718 \tl_new:N \l_keys_choice_tl </pre>
<code>\l_keys_choice_code_tl</code>	When creating multiple choices, the code is stored here.
	<pre> 5719 \tl_new:N \l_keys_choice_code_tl </pre>
<code>\l_keys_key_tl</code>	Storage for the current key name and the path of the key (key name plus module name).
<code>\l_keys_path_tl</code>	
<code>\l_keys_property_tl</code>	<pre> 5720 \tl_new:N \l_keys_key_tl 5721 \tl_new:N \l_keys_path_tl 5722 \tl_new:N \l_keys_property_tl </pre>
<code>\l_keys_module_tl</code>	The module for an entire set of keys.
	<pre> 5723 \tl_new:N \l_keys_module_tl </pre>
<code>\l_keys_nesting_seq</code>	For nesting.
<code>\l_keys_nesting_tl</code>	<pre> 5724 \seq_new:N \l_keys_nesting_seq 5725 \tl_new:Nn \l_keys_nesting_tl { none } </pre>
<code>\l_keys_no_value_bool</code>	To indicate that no value has been given.
	<pre> 5726 \bool_new:N \l_keys_no_value_bool </pre>
<code>\l_keys_value_toks</code>	A token register for the given value.
	<pre> 5727 \toks_new:N \l_keys_value_toks </pre>

## 114.2.2 Internal functions

`\keys_bool_set:NN` Boolean keys are really just choices, but all done by hand.

```

5728 \cs_new_nopar:Npn \keys_bool_set:NN #1#2 {
5729   \keys_cmd_set:nx { \l_keys_path_tl / true } {
5730     \exp_not:c { bool_ #2 set_true:N }
5731     \exp_not:N #1
5732   }
5733   \keys_cmd_set:nx { \l_keys_path_tl / false } {
5734     \exp_not:N \use:c
5735       { bool_ #2 set_false:N }
5736     \exp_not:N #1
5737   }
5738   \keys_choice_make:
5739   \cs_if_exist:NF #1 {

```

```

5740     \bool_new:N #1
5741   }
5742   \keys_default_set:n { true }
5743 }

```

`\keys_choice_code_store:x` The code for making multiple choices is stored in a token list as there should not be any # tokens.

```

5744 \cs_new:Npn \keys_choice_code_store:x #1 {
5745   \tl_set:cx { \c_keys_root_tl \l_keys_path_tl .choice_code_tl } {#1}
5746 }

```

`\keys_choice_find:n` Executing a choice has two parts. First, try the choice given, then if that fails call the unknown key. That will exist, as it is created when a choice is first made. So there is no need for any escape code.

```

5747 \cs_new_nopar:Npn \keys_choice_find:n #1 {
5748   \keys_execute_aux:nn { \l_keys_path_tl / #1 } {
5749     \keys_execute_aux:nn { \l_keys_path_tl / unknown } { }
5750   }
5751 }

```

`\keys_choice_make:` To make a choice from a key, two steps: set the code, and set the unknown key.

```

5752 \cs_new_nopar:Npn \keys_choice_make: {
5753   \keys_cmd_set:nn { \l_keys_path_tl } {
5754     \keys_choice_find:n {##1}
5755   }
5756   \keys_cmd_set:nn { \l_keys_path_tl / unknown } {
5757     \msg_kernel_error:nnxx { keys } { choice-unknown }
5758     { \l_keys_path_tl } {##1}
5759   }
5760 }

```

`\keys_choices_generate:n` Creating multiple-choices means setting up the “indicator” code, then applying whatever the user wanted.

```

5761 \cs_new:Npn \keys_choices_generate:n #1 {
5762   \keys_choice_make:
5763   \int_zero:N \l_keys_choice_int
5764   \cs_if_exist:cTF {
5765     \c_keys_root_tl \l_keys_path_tl .choice_code_tl
5766   } {
5767     \tl_set:Nv \l_keys_choice_code_tl {
5768       \c_keys_root_tl \l_keys_path_tl .choice_code_tl
5769     }
5770   }{
5771     \msg_kernel_error:nnx { keys } { generate-choices-before-code }
5772     { \l_keys_path_tl }

```

```

5773 }
5774 \clist_map_function:nN {#1} \keys_choices_generate_aux:n
5775 }
5776 \cs_new_nopar:Npn \keys_choices_generate_aux:n #1 {
5777   \keys_cmd_set:nx { \l_keys_path_tl / #1 } {
5778     \exp_not:n { \tl_set:Nn \l_keys_choice_tl } {#1}
5779     \exp_not:n { \int_set:Nn \l_keys_choice_int }
5780       { \int_use:N \l_keys_choice_int }
5781     \exp_not:V \l_keys_choice_code_tl
5782   }
5783   \int_incr:N \l_keys_choice_int
5784 }

```

\keys\_cmd\_set:nn Creating a new command means setting properties and then creating a function with the correct number of arguments.

\keys\_cmd\_set:nx

```

\keys_cmd_set_aux:n
5785 \cs_new:Npn \keys_cmd_set:nn #1#2 {
5786   \keys_cmd_set_aux:n {#1}
5787   \cs_generate_from_arg_count:cNnn { \c_keys_root_tl #1 .cmd:n }
5788     \cs_set:Npn 1 {#2}
5789 }
5790 \cs_new:Npn \keys_cmd_set:nx #1#2 {
5791   \keys_cmd_set_aux:n {#1}
5792   \cs_generate_from_arg_count:cNnn { \c_keys_root_tl #1 .cmd:n }
5793     \cs_set:Npx 1 {#2}
5794 }
5795 \cs_new_nopar:Npn \keys_cmd_set_aux:n #1 {
5796   \keys_property_undefine:n { #1 .default_tl }
5797   \tl_set:cn { \c_keys_root_tl #1 .req_tl } { }
5798 }

```

\keys\_default\_set:n Setting a default value is easy.

\keys\_default\_set:V

```

5799 \cs_new:Npn \keys_default_set:n #1 {
5800   \tl_set:cn { \c_keys_root_tl \l_keys_path_tl .default_tl } {#1}
5801 }
5802 \cs_generate_variant:Nn \keys_default_set:n { V }

```

\keys\_define:nn The main key-defining function mainly sets up things for l3keyval to use.

```

5803 \cs_new:Npn \keys_define:nn #1#2 {
5804   \tl_set:Nn \l_keys_module_tl {#1}
5805   \cs_set_eq:NN \KV_key_no_value_elt:n \keys_define_elt:n
5806   \cs_set_eq:NN \KV_key_value_elt:nn \keys_define_elt:nn
5807   \seq_push:NV \l_keys_nesting_seq \l_keys_nesting_tl
5808   \tl_set:Nn \l_keys_nesting_tl { define }
5809   \KV_parse_no_space_removal_no_sanitization:n {#2}
5810   \seq_pop:NN \l_keys_nesting_seq \l_keys_nesting_tl
5811   \cs_set_eq:Nc \KV_key_no_value_elt:n

```

```

5812     { keys_ \l_keys_nesting_tl _elt:n }
5813     \cs_set_eq:Nc \KV_key_value_elt:nn
5814     { keys_ \l_keys_nesting_tl _elt:nn }
5815 }

```

`\keys_define_elt:n` The element processors for defining keys.  
`\keys_define_elt:nn`

```

5816 \cs_new_nopar:Npn \keys_define_elt:n #1 {
5817     \bool_set_true:N \l_keys_no_value_bool
5818     \keys_define_elt_aux:nn {#1} { }
5819 }
5820 \cs_new:Npn \keys_define_elt:nn #1#2 {
5821     \bool_set_false:N \l_keys_no_value_bool
5822     \keys_define_elt_aux:nn {#1} {#2}
5823 }

```

`\keys_define_elt_aux:nn` The auxiliary function does most of the work.

```

5824 \cs_new:Npn \keys_define_elt_aux:nn #1#2 {
5825     \keys_property_find:n {#1}
5826     \cs_set_eq:Nc \keys_tmp:w
5827     { \c_keys_properties_root_tl \l_keys_property_tl }
5828     \cs_if_exist:NTF \keys_tmp:w {
5829         \keys_define_key:n {#2}
5830     }{
5831         \msg_kernel_error:nxxx { keys } { property-unknown }
5832         { \l_keys_property_tl } { \l_keys_path_tl }
5833     }
5834 }

```

`\keys_define_key:n` Defining a new key means finding the code for the appropriate property then running it. As properties have signatures, a check can be made for required values without needing anything set explicitly.

```

5835 \cs_new:Npn \keys_define_key:n #1 {
5836     \bool_if:NTF \l_keys_no_value_bool {
5837         \intexpr_compare:nTF {
5838             \exp_args:Nc \cs_get_arg_count_from_signature:N
5839             { \l_keys_property_tl } = \c_zero
5840         } {
5841             \keys_tmp:w
5842         }{
5843             \msg_kernel_error:nxxx { key } { property-requires-value }
5844             { \l_keys_property_tl } { \l_keys_path_tl }
5845         }
5846     }{
5847         \keys_tmp:w {#1}
5848     }
5849 }

```



`\keys_execute:` Actually executing a key is done in two parts. First, look for the key itself, then look for  
`\keys_execute_unknown:` the **unknown** key with the same path. If both of these fail, complain!  
`\keys_execute_aux:nn`

```

5850 \cs_new_nopar:Npn \keys_execute: {
5851   \keys_execute_aux:nn { \l_keys_path_tl } {
5852     \keys_execute_unknown:
5853   }
5854 }
5855 \cs_new_nopar:Npn \keys_execute_unknown: {
5856   \keys_execute_aux:nn { \l_keys_module_tl / unknown } {
5857     \msg_kernel_error:nnxx { keys } { key-unknown } { \l_keys_path_tl }
5858     { \l_keys_module_tl }
5859   }
5860 }

```

If there is only one argument required, it is wrapped in braces so that everything is passed through properly. On the other hand, if more than one is needed it is down to the user to have put things in correctly! The use of `\q_keys_stop` here means that arguments do not run away (hence the nine empty groups), but that the module can clean up the spare groups at the end of executing the key.

```

5861 \cs_new_nopar:Npn \keys_execute_aux:nn #1#2 {
5862   \cs_set_eq:Nc \keys_tmp:w { \c_keys_root_tl #1 .cmd:n }
5863   \cs_if_exist:NTF \keys_tmp:w {
5864     \exp_args:NV \keys_tmp:w \l_keys_value_toks
5865   }{
5866     #2
5867   }
5868 }

```

`\keys_if_exist:nnTF` A check for the existence of a key. This works by looking for the command function for the key (which ends `.cmd:n`).

```

5869 \prg_set_conditional:Nnn \keys_if_exist:nn {TF,T,F} {
5870   \cs_if_exist:cTF { \c_keys_root_tl #1 / #2 .cmd:n } {
5871     \prg_return_true:
5872   }{
5873     \prg_return_false:
5874   }
5875 }

```

`\keys_if_value_requirement:nTF` To test if a value is required or forbidden. Only one version is needed, so done by hand.

```

5876 \cs_new_nopar:Npn \keys_if_value_requirement:nTF #1 {
5877   \tl_if_eq:ccTF { c_keys_value_ #1 _tl } {
5878     \c_keys_root_tl \l_keys_path_tl .req_tl
5879   }
5880 }

```

`\keys_meta_make:n` To create a met-key, simply set up to pass data through.

`\keys_meta_make:x`

```
5881 \cs_new_nopar:Npn \keys_meta_make:n #1 {  
5882   \exp_last_unbraced:NNo \keys_cmd_set:nn \l_keys_path_tl  
5883   \exp_after:wN { \exp_after:wN \keys_set:nn \exp_after:wN { \l_keys_module_tl } {#1} }  
5884 }  
5885 \cs_new_nopar:Npn \keys_meta_make:x #1 {  
5886   \keys_cmd_set:nx { \l_keys_path_tl } {  
5887     \exp_not:N \keys_set:nn { \l_keys_module_tl } {#1}  
5888   }  
5889 }
```

`\keys_property_find:n` Searching for a property means finding the last “.” in the input, and storing the text before and after it.

`\keys_property_find_aux:n`

`\keys_property_find_aux:w`

```
5890 \cs_new_nopar:Npn \keys_property_find:n #1 {  
5891   \tl_set:Nx \l_keys_path_tl { \l_keys_module_tl / }  
5892   \tl_if_in:nnTF {#1} {.} {  
5893     \keys_property_find_aux:n {#1}  
5894   }{  
5895     \msg_kernel_error:nnx { keys } { key-no-property } {#1}  
5896   }  
5897 }  
5898 \cs_new_nopar:Npn \keys_property_find_aux:n #1 {  
5899   \keys_property_find_aux:w #1 \q_stop  
5900 }  
5901 \cs_new_nopar:Npn \keys_property_find_aux:w #1 . #2 \q_stop {  
5902   \tl_if_in:nnTF {#2} { . } {  
5903     \tl_set:Nx \l_keys_path_tl {  
5904       \l_keys_path_tl \tl_to_str:n {#1} .  
5905     }  
5906     \keys_property_find_aux:w #2 \q_stop  
5907   }{  
5908     \tl_set:Nx \l_keys_path_tl { \l_keys_path_tl \tl_to_str:n {#1} }  
5909     \tl_set:Nn \l_keys_property_tl { . #2 }  
5910   }  
5911 }
```

`\keys_property_new:nn` Creating a new property is simply a case of making the correctly-named function.

`\keys_property_new_arg:nn`

```
5912 \cs_new_nopar:Npn \keys_property_new:nn #1#2 {  
5913   \cs_new:cpn { \c_keys_properties_root_tl #1 } {#2}  
5914 }  
5915 \cs_new_nopar:Npn \keys_property_new_arg:nn #1#2 {  
5916   \cs_new:cpn { \c_keys_properties_root_tl #1 } ##1 {#2}  
5917 }
```

`\keys_property_undefine:n` Removing a property means undefining it.

```

5918 \cs_new_nopar:Npn \keys_property_undefine:n #1 {
5919   \cs_set_eq:cN { \c_keys_root_tl #1 } \c_undefined
5920 }

```

\keys\_set:nn The main setting function just does the set up to get l3keyval to do the hard work.

\keys\_set:nV  
\keys\_set:nv

```

5921 \cs_new:Npn \keys_set:nn #1#2 {
5922   \tl_set:Nn \l_keys_module_tl {#1}
5923   \cs_set_eq:NN \KV_key_no_value_elt:n \keys_set_elt:n
5924   \cs_set_eq:NN \KV_key_value_elt:nn \keys_set_elt:nn
5925   \seq_push:NV \l_keys_nesting_seq \l_keys_nesting_tl
5926   \tl_set:Nn \l_keys_nesting_tl { set }
5927   \KV_parse_space_removal_sanitization:n {#2}
5928   \seq_pop:NN \l_keys_nesting_seq \l_keys_nesting_tl
5929   \cs_set_eq:Nc \KV_key_no_value_elt:n
5930     { keys_ \l_keys_nesting_tl _elt:n }
5931   \cs_set_eq:Nc \KV_key_value_elt:nn
5932     { keys_ \l_keys_nesting_tl _elt:nn }
5933 }
5934 \cs_generate_variant:Nn \keys_set:nn { nV, nv }

```

\keys\_set\_elt:n The two element processors are almost identical, and pass the data through to the underlying auxiliary, which does the work.

\keys\_set\_elt:nn

```

5935 \cs_new_nopar:Npn \keys_set_elt:n #1 {
5936   \bool_set_true:N \l_keys_no_value_bool
5937   \keys_set_elt_aux:nn {#1} { }
5938 }
5939 \cs_new:Npn \keys_set_elt:nn #1#2 {
5940   \bool_set_false:N \l_keys_no_value_bool
5941   \keys_set_elt_aux:nn {#1} {#2}
5942 }

```

\keys\_set\_elt\_aux:nn

\keys\_set\_elt\_aux:

First, set the current path and add a default if needed. There are then checks to see if the a value is required or forbidden. If everything passes, move on to execute the code.

```

5943 \cs_new:Npn \keys_set_elt_aux:nn #1#2 {
5944   \tl_set:Nx \l_keys_key_tl { \tl_to_str:n {#1} }
5945   \tl_set:Nx \l_keys_path_tl { \l_keys_module_tl / \l_keys_key_tl }
5946   \keys_value_or_default:n {#2}
5947   \keys_if_value_requirement:nTF { required } {
5948     \bool_if:NTF \l_keys_no_value_bool {
5949       \msg_kernel_error:nnx { keys } { value-required }
5950       { \l_keys_path_tl }
5951     }{
5952       \keys_set_elt_aux:
5953     }
5954   }{
5955     \keys_set_elt_aux:

```

```

5956     }
5957 }
5958 \cs_new_nopar:Npn \keys_set_elt_aux: {
5959   \keys_if_value_requirement:nTF { forbidden } {
5960     \bool_if:NTF \l_keys_no_value_bool {
5961       \keys_execute:
5962     }{
5963       \msg_kernel_error:nxx { keys } { value-forbidden }
5964       { \l_keys_path_tl } { \toks_use:N \l_keys_value_toks }
5965     }
5966   }{
5967     \keys_execute:
5968   }
5969 }

```

**\keys\_show:nn** Showing a key is just a question of using the correct name.

```

5970 \cs_new_nopar:Npn \keys_show:nn #1#2 {
5971   \cs_show:c { \c_keys_root_tl #1 / \tl_to_str:n {#2} .cmd:n }
5972 }

```

**\keys\_tmp:w** This scratch function is used to actually execute keys.

```

5973 \cs_new:Npn \keys_tmp:w {}

```

**\keys\_value\_or\_default:n** If a value is given, return it as #1, otherwise send a default if available.

```

5974 \cs_new:Npn \keys_value_or_default:n #1 {
5975   \toks_set:Nn \l_keys_value_toks {#1}
5976   \bool_if:NT \l_keys_no_value_bool {
5977     \cs_if_exist:cT { \c_keys_root_tl \l_keys_path_tl .default_tl } {
5978       \toks_set:Nv \l_keys_value_toks {
5979         \c_keys_root_tl \l_keys_path_tl .default_tl
5980       }
5981     }
5982   }
5983 }

```

**\keys\_value\_requirement:n** Values can be required or forbidden by having the appropriate marker set.

```

5984 \cs_new_nopar:Npn \keys_value_requirement:n #1 {
5985   \tl_set_eq:cc { \c_keys_root_tl \l_keys_path_tl .req_tl }
5986   { c_keys_value_ #1 _tl }
5987 }

```

**\keys\_variable\_set:NnNN** Setting a variable takes the type and scope separately so that it is easy to make a new variable if needed.

```

5988 \cs_new_nopar:Npn \keys_variable_set:NnNN #1#2#3#4 {

```

```

5989 \cs_if_exist:Nf #1 {
5990   \use:c { #2 _new:N } #1
5991 }
5992 \keys_cmd_set:nx { \l_keys_path_tl } {
5993   \exp_not:c { #2 _ #3 set:N #4 } \exp_not:N #1 {##1}
5994 }
5995 }
5996 \cs_generate_variant:Nn \keys_variable_set:NnNN { c }

```

### 114.2.3 Properties

`.bool_set:N` One function for this.

```

5997 \keys_property_new_arg:nn { .bool_set:N } {
5998   \keys_bool_set:NN #1 { }
5999 }
6000 \keys_property_new_arg:nn { .bool_gset:N } {
6001   \keys_bool_set:NN #1 n
6002 }

```

`.choice:` Making a choice is handled internally, as it is also needed by `.generate_choices:n`.

```

6003 \keys_property_new:nn { .choice: } {
6004   \keys_choice_make:
6005 }

```

`.choice_code:n` Storing the code for choices, using `\exp_not:n` to avoid needing two internal functions.

```

6006 \keys_property_new_arg:nn { .choice_code:n } {
6007   \keys_choice_code_store:x { \exp_not:n {#1} }
6008 }
6009 \keys_property_new_arg:nn { .choice_code:x } {
6010   \keys_choice_code_store:x {#1}
6011 }

```

`.code:n` Creating code is simply a case of passing through to the underlying `set` function.

```

6012 \keys_property_new_arg:nn { .code:n } {
6013   \keys_cmd_set:nn { \l_keys_path_tl } {#1}
6014 }
6015 \keys_property_new_arg:nn { .code:x } {
6016   \keys_cmd_set:nx { \l_keys_path_tl } {#1}
6017 }

```

`.default:n` Expansion is left to the internal functions.

```

6018 \keys_property_new_arg:nn { .default:n } {
6019   \keys_default_set:n {#1}

```

```

6020 }
6021 \keys_property_new_arg:nn { .default:V } {
6022   \keys_default_set:V #1
6023 }

```

`.dim_set:N` Setting a variable is very easy: just pass the data along.

```

        .dim_set:c
        .dim_gset:N
        .dim_gset:c
6024 \keys_property_new_arg:nn { .dim_set:N } {
6025   \keys_variable_set:NnNN #1 { dim } { } n
6026 }
6027 \keys_property_new_arg:nn { .dim_set:c } {
6028   \keys_variable_set:cnNN {#1} { dim } { } n
6029 }
6030 \keys_property_new_arg:nn { .dim_gset:N } {
6031   \keys_variable_set:NnNN #1 { dim } g n
6032 }
6033 \keys_property_new_arg:nn { .dim_gset:c } {
6034   \keys_variable_set:cnNN {#1} { dim } g n
6035 }

```

`.generate_choices:n` Making choices is easy.

```

6036 \keys_property_new_arg:nn { .generate_choices:n } {
6037   \keys_choices_generate:n {#1}
6038 }

```

`.int_set:N` Setting a variable is very easy: just pass the data along.

```

        .int_set:c
        .int_gset:N
        .int_gset:c
6039 \keys_property_new_arg:nn { .int_set:N } {
6040   \keys_variable_set:NnNN #1 { int } { } n
6041 }
6042 \keys_property_new_arg:nn { .int_set:c } {
6043   \keys_variable_set:cnNN {#1} { int } { } n
6044 }
6045 \keys_property_new_arg:nn { .int_gset:N } {
6046   \keys_variable_set:NnNN #1 { int } g n
6047 }
6048 \keys_property_new_arg:nn { .int_gset:c } {
6049   \keys_variable_set:cnNN {#1} { int } g n
6050 }

```

`.meta:n` Making a meta is handled internally.

```

        .meta:x
6051 \keys_property_new_arg:nn { .meta:n } {
6052   \keys_meta_make:n {#1}
6053 }
6054 \keys_property_new_arg:nn { .meta:x } {
6055   \keys_meta_make:x {#1}
6056 }

```

.skip\_set:N Setting a variable is very easy: just pass the data along.

```
.skip_set:c
.skip_gset:N
.skip_gset:c
6057 \keys_property_new_arg:nn { .skip_set:N } {
6058   \keys_variable_set:NnNN #1 { skip } { } n
6059 }
6060 \keys_property_new_arg:nn { .skip_set:c } {
6061   \keys_variable_set:cnNN {#1} { skip } { } n
6062 }
6063 \keys_property_new_arg:nn { .skip_gset:N } {
6064   \keys_variable_set:NnNN #1 { skip } g n
6065 }
6066 \keys_property_new_arg:nn { .skip_gset:c } {
6067   \keys_variable_set:cnNN {#1} { skip } g n
6068 }
```

.tl\_set:N Setting a variable is very easy: just pass the data along.

```
.tl_set:c
.tl_set_x:N
.tl_set_x:c
.tl_gset:N
.tl_gset:c
.tl_gset_x:N
.tl_gset_x:c
6069 \keys_property_new_arg:nn { .tl_set:N } {
6070   \keys_variable_set:NnNN #1 { tl } { } n
6071 }
6072 \keys_property_new_arg:nn { .tl_set:c } {
6073   \keys_variable_set:cnNN {#1} { tl } { } n
6074 }
6075 \keys_property_new_arg:nn { .tl_set_x:N } {
6076   \keys_variable_set:NnNN #1 { tl } { } x
6077 }
6078 \keys_property_new_arg:nn { .tl_set_x:c } {
6079   \keys_variable_set:cnNN {#1} { tl } { } x
6080 }
6081 \keys_property_new_arg:nn { .tl_gset:N } {
6082   \keys_variable_set:NnNN #1 { tl } g n
6083 }
6084 \keys_property_new_arg:nn { .tl_gset:c } {
6085   \keys_variable_set:cnNN {#1} { tl } g n
6086 }
6087 \keys_property_new_arg:nn { .tl_gset_x:N } {
6088   \keys_variable_set:NnNN #1 { tl } g x
6089 }
6090 \keys_property_new_arg:nn { .tl_gset_x:c } {
6091   \keys_variable_set:cnNN {#1} { tl } g x
6092 }
```

.value\_forbidden: These are very similar, so both call the same function.

```
.value_required:
6093 \keys_property_new:nn { .value_forbidden: } {
6094   \keys_value_requirement:n { forbidden }
6095 }
6096 \keys_property_new:nn { .value_required: } {
6097   \keys_value_requirement:n { required }
6098 }
```

#### 114.2.4 Messages

For when there is a need to complain.

```
6099 \msg_kernel_new:nnnn { keys } { choice-unknown }
6100 {%
6101     Choice '#2' unknown for key '#1':\\%
6102     the key is being ignored.%
6103 }
6104 {%
6105     The key '#1' takes a limited number of values.\\%
6106     The input you gave, '#2', was not on the list accepted.\\%
6107     Perhaps this is a typing error?%
6108 }
6109 \msg_kernel_new:nnnn { keys } { generate-choices-before-code }
6110 {%
6111     Cannot create choices for key '#1':\\%
6112     no code has been defined.%
6113 }
6114 {%
6115     Code for use by .generate_choices:n should first be defined\\%
6116     using .choice_code:n or .choice_code:x.%
6117 }
6118 \msg_kernel_new:nnnn { keys } { key-no-property }
6119 {No property given in definition of key '#1'.}
6120 {%
6121     Inside \token_to_str:N \keys_define:nn \msg_space: each key name
6122     needs a property:\\%
6123     \msg_two_spaces: #1 .<property>:\\%
6124     I did not find a ‘.’ to indicate the start of a property.%
6125 }
6126 \msg_kernel_new:nnnn { keys } { key-unknown }
6127 {The key '#1' is unknown and is being ignored.}
6128 {%
6129     The module '#2' does not seem to implement a key called '#1'.\\%
6130     I also checked for code to handle a unknown key, and did not
6131     find any.%
6132     Check that you have spelled the key name correctly.%
6133 }
6134 \msg_kernel_new:nnnn { keys } { property-unknown }
6135 {The key property '#1' is unknown.}
6136 {%
6137     You have asked for key '#2' to have the property '#1'.\\%
6138     However, I don't know the property '#1': this line will be ignored.%
6139 }
6140 \msg_kernel_new:nnnn { keys } { property-requires-value }
6141 {The property '#1' requires a value.}
6142 {%
6143     You have tried to set the property '#2' for key '#1'.\\%
6144     However, you did not give a value for this property, and one is
```



```

6145   needed.\\%
6146   The entire line will be ignored.%
6147 }
6148 \msg_kernel_new:nnnn { keys } { value-forbidden }
6149 {The key '#1' does not taken a value.}
6150 {%
6151   The key '#1' should be given without a value.\\%
6152   You gave '#1 = #2'; I will ignore '#2' and carry out whatever\\%
6153   key '#1' is supposed to do.%
6154 }
6155 \msg_kernel_new:nnnn { keys } { value-required }
6156 {The key '#1' requires a value.}
6157 {%
6158   The key '#1' should be given with a value.\\%
6159   You gave '#1', but should have given '#1 = <value>'.\\%
6160   I will ignore the key entirely.\\%
6161 }
6162 </initex | package>

```

## 115 l3calc implementation

### 115.1 Variables

```

\l_calc_expression_tl
\g_calc_A_register
\l_calc_B_register
\l_calc_current_type_int
\g_calc_A_int
\l_calc_B_int
\l_calc_C_int
\g_calc_A_dim
\l_calc_B_dim
\l_calc_C_dim
\g_calc_A_skip
\l_calc_B_skip
\l_calc_C_skip
\g_calc_A_muskip
\l_calc_B_muskip
\l_calc_C_muskip

```

Internal registers.

## 115.2 Internal functions

```
\calc_assign_generic:NNNNnn
\calc_pre_scan:N
\calc_open:w
\calc_init_B:
\calc_numeric:
\calc_close:
\calc_post_scan:N
\calc_multiply:N
\calc_divide:N
\calc_generic_add_or_subtract:N
\calc_add:
\calc_subtract:
\calc_add_A_to_B:
\calc_subtract_A_from_B:
\calc_generic_multiply_or_divide:N
\calc_multiply_B_by_A:
\calc_divide_B_by_A:
\calc_multiply:
\calc_divide:
\calc_textsize:Nn
\calc_ratio_multiply:nn
\calc_ratio_divide:nn
\calc_real_evaluate:nn
\calc_real_multiply:n
\calc_real_divide:n
\calc_maxmin_operation:Nnn
\calc_maxmin_generic:Nnn
\calc_maxmin_div_or_mul:NNnn
\calc_maxmin_multiply:
\calc_maxmin_multiply:
\calc_error:N
\calc_chk_document_counter:nn
```

Awaiting better documentation :)

## 115.3 Module code

Since this is basically a re-worked version of the `calc` package, I haven't bothered with too many comments except for in the places where this package differs. This may (and should) change at some point.

We start by ensuring that the required packages are loaded.

```
6163 ⟨*package⟩
6164 \ProvidesExplPackage
```

```

6165 {\filename}{\filedate}{\fileversion}{\filedescription}
6166 \package_check_loaded_expl:
6167 </package>
6168 <*initex | package>

```

\l\_calc\_expression\_tl Here we define some registers and pointers we will need.

```

\g_calc_A_register
\l_calc_B_register
\l_calc_current_type_int
6169 \tl_new:Nn\l_calc_expression_tl{}
6170 \cs_new_nopar:Npn \g_calc_A_register{}
6171 \cs_new_nopar:Npn \l_calc_B_register{}
6172 \int_new:N \l_calc_current_type_int

```

\g\_calc\_A\_int For each type of register we will need three registers to do our manipulations.

```

\l_calc_B_int
\l_calc_C_int
\g_calc_A_dim
\l_calc_B_dim
\l_calc_C_dim
\g_calc_A_skip
\l_calc_B_skip
\l_calc_C_skip
\g_calc_A_muskip
\l_calc_B_muskip
\l_calc_C_muskip
6173 \int_new:N \g_calc_A_int
6174 \int_new:N \l_calc_B_int
6175 \int_new:N \l_calc_C_int
6176 \dim_new:N \g_calc_A_dim
6177 \dim_new:N \l_calc_B_dim
6178 \dim_new:N \l_calc_C_dim
6179 \skip_new:N \g_calc_A_skip
6180 \skip_new:N \l_calc_B_skip
6181 \skip_new:N \l_calc_C_skip
6182 \muskip_new:N \g_calc_A_muskip
6183 \muskip_new:N \l_calc_B_muskip
6184 \muskip_new:N \l_calc_C_muskip

```

\calc\_assign\_generic:NNNNnn The generic function. #1 is a number denoting which type we are doing. (0=int, 1=dim, 2=skip, 3=muskip), #2 = temp register A, #3 = temp register B, #4 is a function acting on #5 which is the register to be set. #6 is the calc expression. We do a little extra work so that \real and \ratio can still be used by the user.

```

6185 \cs_new:Npn \calc_assign_generic:NNNNnn#1#2#3#4#5#6{
6186   \cs_set_eq:NN\g_calc_A_register#2
6187   \cs_set_eq:NN\l_calc_B_register#3
6188   \int_set:Nn \l_calc_current_type_int {#1}
6189   \group_begin:
6190     \cs_set_eq:NN \real \calc_real:n
6191     \cs_set_eq:NN \ratio\calc_ratio:nn
6192     \tl_set:Nx\l_calc_expression_tl{#6}
6193     \exp_after:wN
6194   \group_end:
6195   \exp_after:wN\calc_open:w\exp_after:wN(\l_calc_expression_tl !
6196   \pref_global:D\g_calc_A_register\l_calc_B_register
6197   \group_end:
6198   #4{#5}\l_calc_B_register
6199 }

```

A simpler version relying on \real and \ratio having our definition is

```

\cs_new:Npn \calc_assign_generic:NNNNnn#1#2#3#4#5#6{
  \cs_set_eq:NN\g_calc_A_register#2\cs_set_eq:NN\l_calc_B_register#3
  \int_set:Nn \l_calc_current_type_int {#1}
  \tl_set:Nx\l_calc_expression_tl{#6}
  \exp_after:wN\calc_open:w\exp_after:wN(\l_calc_expression_tl !
  \pref_global:D\g_calc_A_register\l_calc_B_register
  \group_end:
  #4{#5}\l_calc_B_register
}

```

\calc\_int\_set:Nn Here are the individual versions for the different register types. First integer registers.

```

\calc_int_gset:Nn
\calc_int_add:Nn 6200 \cs_new_nopar:Npn\calc_int_set:Nn{
\calc_int_gadd:Nn 6201   \calc_assign_generic:NNNNnn\c_zero\g_calc_A_int\l_calc_B_int\int_set:Nn
\calc_int_sub:Nn 6202 }
\calc_int_gsub:Nn 6203 \cs_new_nopar:Npn\calc_int_gset:Nn{
6204   \calc_assign_generic:NNNNnn\c_zero\g_calc_A_int\l_calc_B_int\int_gset:Nn
6205 }
6206 \cs_new_nopar:Npn\calc_int_add:Nn{
6207   \calc_assign_generic:NNNNnn\c_zero\g_calc_A_int\l_calc_B_int\int_add:Nn
6208 }
6209 \cs_new_nopar:Npn\calc_int_gadd:Nn{
6210   \calc_assign_generic:NNNNnn\c_zero\g_calc_A_int\l_calc_B_int\int_gadd:Nn
6211 }
6212 \cs_new_nopar:Npn\calc_int_sub:Nn{
6213   \calc_assign_generic:NNNNnn\c_zero\g_calc_A_int\l_calc_B_int\int_sub:Nn
6214 }
6215 \cs_new_nopar:Npn\calc_int_gsub:Nn{
6216   \calc_assign_generic:NNNNnn\c_zero\g_calc_A_int\l_calc_B_int\int_gsub:Nn
6217 }

```

\calc\_dim\_set:Nn Dimens.

```

\calc_dim_gset:Nn
\calc_dim_add:Nn 6218 \cs_new_nopar:Npn\calc_dim_set:Nn{
\calc_dim_gadd:Nn 6219   \calc_assign_generic:NNNNnn\c_one\g_calc_A_dim\l_calc_B_dim\dim_set:Nn
6220 }
\calc_dim_sub:Nn 6221 \cs_new_nopar:Npn\calc_dim_gset:Nn{
\calc_dim_gsub:Nn 6222   \calc_assign_generic:NNNNnn\c_one\g_calc_A_dim\l_calc_B_dim\dim_gset:Nn
6223 }
6224 \cs_new_nopar:Npn\calc_dim_add:Nn{
6225   \calc_assign_generic:NNNNnn\c_one\g_calc_A_dim\l_calc_B_dim\dim_add:Nn
6226 }
6227 \cs_new_nopar:Npn\calc_dim_gadd:Nn{
6228   \calc_assign_generic:NNNNnn\c_one\g_calc_A_dim\l_calc_B_dim\dim_gadd:Nn
6229 }
6230 \cs_new_nopar:Npn\calc_dim_sub:Nn{
6231   \calc_assign_generic:NNNNnn\c_one\g_calc_A_int\l_calc_B_int\dim_sub:Nn
6232 }
6233 \cs_new_nopar:Npn\calc_dim_gsub:Nn{

```

```

6234 \calc_assign_generic:NNNNnn\c_one\g_calc_A_int\l_calc_B_int\dim_gsub:Nn
6235 }

```

\calc\_skip\_set:Nn Skips.

```

\calc_skip_gset:Nn
\calc_skip_add:Nn
\calc_skip_gadd:Nn
\calc_skip_sub:Nn
\calc_skip_gsub:Nn
6236 \cs_new_nopar:Npn\calc_skip_set:Nn{
6237   \calc_assign_generic:NNNNnn\c_two\g_calc_A_skip\l_calc_B_skip\skip_set:Nn
6238 }
6239 \cs_new_nopar:Npn\calc_skip_gset:Nn{
6240   \calc_assign_generic:NNNNnn\c_two\g_calc_A_skip\l_calc_B_skip\skip_gset:Nn
6241 }
6242 \cs_new_nopar:Npn\calc_skip_add:Nn{
6243   \calc_assign_generic:NNNNnn\c_two\g_calc_A_skip\l_calc_B_skip\skip_add:Nn
6244 }
6245 \cs_new_nopar:Npn\calc_skip_gadd:Nn{
6246   \calc_assign_generic:NNNNnn\c_two\g_calc_A_skip\l_calc_B_skip\skip_gadd:Nn
6247 }
6248 \cs_new_nopar:Npn\calc_skip_sub:Nn{
6249   \calc_assign_generic:NNNNnn\c_two\g_calc_A_skip\l_calc_B_skip\skip_sub:Nn
6250 }
6251 \cs_new_nopar:Npn\calc_skip_gsub:Nn{
6252   \calc_assign_generic:NNNNnn\c_two\g_calc_A_skip\l_calc_B_skip\skip_gsub:Nn
6253 }

```

\calc\_muskip\_set:Nn Muskips.

```

\calc_muskip_gset:Nn
\calc_muskip_add:Nn
\calc_muskip_gadd:Nn
\calc_muskip_sub:Nn
\calc_muskip_gsub:Nn
6254 \cs_new_nopar:Npn\calc_muskip_set:Nn{
6255   \calc_assign_generic:NNNNnn\c_three\g_calc_A_muskip\l_calc_B_muskip
6256   \muskip_set:Nn
6257 }
6258 \cs_new_nopar:Npn\calc_muskip_gset:Nn{
6259   \calc_assign_generic:NNNNnn\c_three\g_calc_A_muskip\l_calc_B_muskip
6260   \muskip_gset:Nn
6261 }
6262 \cs_new_nopar:Npn\calc_muskip_add:Nn{
6263   \calc_assign_generic:NNNNnn\c_three\g_calc_A_muskip\l_calc_B_muskip
6264   \muskip_add:Nn
6265 }
6266 \cs_new_nopar:Npn\calc_muskip_gadd:Nn{
6267   \calc_assign_generic:NNNNnn\c_three\g_calc_A_muskip\l_calc_B_muskip
6268   \muskip_gadd:Nn
6269 }
6270 \cs_new_nopar:Npn\calc_muskip_sub:Nn{
6271   \calc_assign_generic:NNNNnn\c_three\g_calc_A_muskip\l_calc_B_muskip
6272   \muskip_sub:Nn
6273 }
6274 \cs_new_nopar:Npn\calc_muskip_gsub:Nn{
6275   \calc_assign_generic:NNNNnn\c_three\g_calc_A_muskip\l_calc_B_muskip
6276   \muskip_gadd:Nn
6277 }

```

`\calc_pre_scan:N` In case we found one of the special operations, this should just be executed.

```

6278 \cs_new_nopar:Npn \calc_pre_scan:N #1{
6279   \if_meaning:w(#1
6280     \exp_after:wN\calc_open:w
6281   \else:
6282     \if_meaning:w \calc_textsize:Nn #1
6283   \else:
6284     \if_meaning:w \calc_maxmin_operation:Nnn #1
6285   \else:

```

`\calc_numeric:` uses a primitive assignment so doesn't care about these dangling `\fi:s`.

```

6286   \calc_numeric:
6287   \fi:
6288   \fi:
6289   \fi:
6290   #1}

```

`\calc_open:w`

```

6291 \cs_new_nopar:Npn \calc_open:w{
6292   \group_begin:\group_execute_after:N\calc_init_B:
6293   \group_begin:\group_execute_after:N\calc_init_B:
6294   \calc_pre_scan:N
6295 }

```

`\calc_init_B:`

`\calc_numeric:`

`\calc_close:`

```

6296 \cs_new_nopar:Npn\calc_init_B:{\l_calc_B_register\g_calc_A_register}
6297 \cs_new_nopar:Npn\calc_numeric:{
6298   \tex_afterassignment:D\calc_post_scan:N
6299   \pref_global:D\g_calc_A_register
6300 }
6301 \cs_new_nopar:Npn\calc_close:{
6302   \group_end:\pref_global:D\g_calc_A_register\l_calc_B_register
6303   \group_end:\pref_global:D\g_calc_A_register\l_calc_B_register
6304   \calc_post_scan:N}

```

`\calc_post_scan:N` Look at what token we have and decide where to go.

```

6305 \cs_new_nopar:Npn\calc_post_scan:N#1{
6306   \if_meaning:w#1!\cs_set_eq:NN\calc_next:w\group_end: \else:
6307     \if_meaning:w#1+\cs_set_eq:NN\calc_next:w\calc_add: \else:
6308       \if_meaning:w#1-\cs_set_eq:NN\calc_next:w\calc_subtract: \else:
6309         \if_meaning:w#1*\cs_set_eq:NN\calc_next:w\calc_multiply:N \else:
6310         \if_meaning:w#1/\cs_set_eq:NN\calc_next:w\calc_divide:N \else:
6311         \if_meaning:w#1)\cs_set_eq:NN\calc_next:w\calc_close: \else:
6312         \if_meaning:w#1\scan_stop:\cs_set_eq:NN\calc_next:w\calc_post_scan:N
6313         \else:

```

If we get here, there is an error but let's also disable `\calc_next:w` since it is otherwise undefined. No need to give extra errors just for that.

```

6314             \cs_set_eq:NN \calc_next:w \prg_do_nothing:
6315             \calc_error:N#1
6316         \fi:
6317     \fi:
6318 \fi:
6319 \fi:
6320 \fi:
6321 \fi:
6322 \fi:
6323 \calc_next:w}

```

`\calc_multiply:N` The switches for multiplication and division.

`\calc_divide:N`

```

6324 \cs_new_nopar:Npn \calc_multiply:N #1{
6325     \if_meaning:w \calc_maxmin_operation:Nnn #1
6326     \cs_set_eq:NN \calc_next:w \calc_maxmin_multiply:
6327 \else:
6328     \if_meaning:w \calc_ratio_multiply:nn #1
6329     \cs_set_eq:NN \calc_next:w \calc_ratio_multiply:nn
6330 \else:
6331     \if_meaning:w \calc_real_evaluate:nn #1
6332     \cs_set_eq:NN \calc_next:w \calc_real_multiply:n
6333 \else:
6334     \cs_set_nopar:Npn \calc_next:w{\calc_multiply: #1}
6335 \fi:
6336 \fi:
6337 \fi:
6338 \calc_next:w
6339 }
6340 \cs_new_nopar:Npn \calc_divide:N #1{
6341     \if_meaning:w \calc_maxmin_operation:Nnn #1
6342     \cs_set_eq:NN \calc_next:w \calc_maxmin_divide:
6343 \else:
6344     \if_meaning:w \calc_ratio_multiply:nn #1
6345     \cs_set_eq:NN \calc_next:w \calc_ratio_divide:nn
6346 \else:
6347     \if_meaning:w \calc_real_evaluate:nn #1
6348     \cs_set_eq:NN \calc_next:w \calc_real_divide:n
6349 \else:
6350     \cs_set_nopar:Npn \calc_next:w{\calc_divide: #1}
6351 \fi:
6352 \fi:
6353 \fi:
6354 \calc_next:w
6355 }

```

`\calc_generic_add_or_subtract:N` Here is how we add and subtract.

`\calc_add:`

`\calc_subtract:`

`\calc_add_A_to_B:`

`\calc_subtract_A_from_B:`

```

6356 \cs_new_nopar:Npn\calc_generic_add_or_subtract:N#1{
6357   \group_end:
6358   \pref_global:D\g_calc_A_register\l_calc_B_register\group_end:
6359   \group_begin:\group_execute_after:N#1\group_begin:
6360   \group_execute_after:N\calc_init_B:
6361   \calc_pre_scan:N}
6362 \cs_new_nopar:Npn\calc_add:{\calc_generic_add_or_subtract:N\calc_add_A_to_B:}
6363 \cs_new_nopar:Npn\calc_subtract:{
6364   \calc_generic_add_or_subtract:N\calc_subtract_A_from_B:}

```

Don't use `\tex_advance:D` since it allows overflows.

```

6365 \cs_new_nopar:Npn\calc_add_A_to_B:{
6366   \l_calc_B_register
6367   \if_case:w\l_calc_current_type_int
6368   \etex_numexpr:D\or:
6369   \etex_dimexpr:D\or:
6370   \etex_glueexpr:D\or:
6371   \etex_muexpr:D\fi:
6372   \l_calc_B_register + \g_calc_A_register\scan_stop:
6373 }
6374 \cs_new_nopar:Npn\calc_subtract_A_from_B:{
6375   \l_calc_B_register
6376   \if_case:w\l_calc_current_type_int
6377   \etex_numexpr:D\or:
6378   \etex_dimexpr:D\or:
6379   \etex_glueexpr:D\or:
6380   \etex_muexpr:D\fi:
6381   \l_calc_B_register - \g_calc_A_register\scan_stop:
6382 }

```

`\calc_generic_multiply_or_divide:N` And here is how we multiply and divide. Note that we do not use the primitive  $\TeX$  operations but the expandable operations provided by  $\varepsilon\text{-}\TeX$ . This means that all results are rounded not truncated!

```

\calc_multiply_B_by_A:
\calc_divide_B_by_A:
\calc_multiply:
\calc_divide:

```

```

6383 \cs_new_nopar:Npn\calc_generic_multiply_or_divide:N#1{
6384   \group_end:
6385   \group_begin:
6386   \cs_set_eq:NN\g_calc_A_register\g_calc_A_int
6387   \cs_set_eq:NN\l_calc_B_register\l_calc_B_int
6388   \int_zero:N \l_calc_current_type_int
6389   \group_execute_after:N#1\calc_pre_scan:N
6390 }
6391 \cs_new_nopar:Npn\calc_multiply_B_by_A:{
6392   \l_calc_B_register
6393   \if_case:w\l_calc_current_type_int
6394   \etex_numexpr:D\or:
6395   \etex_dimexpr:D\or:
6396   \etex_glueexpr:D\or:
6397   \etex_muexpr:D\fi:

```



```

6398 \l_calc_B_register*\g_calc_A_int\scan_stop:
6399 }
6400 \cs_new_nopar:Npn\calc_divide_B_by_A:{
6401   \l_calc_B_register
6402   \if_case:w\l_calc_current_type_int
6403   \etex_numexpr:D\or:
6404   \etex_dimexpr:D\or:
6405   \etex_glueexpr:D\or:
6406   \etex_muexpr:D\fi:
6407   \l_calc_B_register/\g_calc_A_int\scan_stop:
6408 }
6409 \cs_new_nopar:Npn\calc_multiply:{
6410   \calc_generic_multiply_or_divide:N\calc_multiply_B_by_A:}
6411 \cs_new_nopar:Npn\calc_divide:{
6412   \calc_generic_multiply_or_divide:N\calc_divide_B_by_A:}

```

`\calc_calculate_box_size:nnn` Put something in a box and measure it. #1 is a list of `\box_ht:N` etc., #2 should be `\dim_set:Nn<dim register>` or `\dim_gset:Nn<dim register>` and #3 is the contents.

```

6413 \cs_new:Npn \calc_calculate_box_size:nnn #1#2#3{
6414   \hbox_set:Nn \l_tmpa_box {{#3}}
6415   #2{\c_zero_dim \tl_map_function:nn{#1}\calc_calculate_box_size_aux:n}
6416 }

```

Helper for calculating the final dimension.

```

6417 \cs_set_nopar:Npn \calc_calculate_box_size_aux:n#1{ + #1\l_tmpa_box}

```

`\calc_textsize:Nn` Now we can define `\calc_textsize:Nn`.

```

6418 \cs_set_protected:Npn \calc_textsize:Nn#1#2{
6419   \group_begin:
6420   \cs_set_eq:NN\calc_widthof_aux:n\box_wd:N
6421   \cs_set_eq:NN\calc_heightof_aux:n\box_ht:N
6422   \cs_set_eq:NN\calc_depthof_aux:n\box_dp:N
6423   \cs_set_nopar:Npn\calc_totalheightof_aux:n{\box_ht:N\box_dp:N}
6424   \exp_args:No\calc_calculate_box_size:nnn{#1}
6425   {\dim_gset:Nn\g_calc_A_register}

```

Restore the four user commands here since there might be a recursive call.

```

6426 {
6427   \cs_set_eq:NN \calc_depthof_aux:n \calc_depthof_auxi:n
6428   \cs_set_eq:NN \calc_widthof_aux:n \calc_widthof_auxi:n
6429   \cs_set_eq:NN \calc_heightof_aux:n \calc_heightof_auxi:n
6430   \cs_set_eq:NN \calc_totalheightof_aux:n \calc_totalheightof_auxi:n
6431   #2
6432 }
6433 \group_end:
6434 \calc_post_scan:N
6435 }

```

`\calc_ratio_multiply:nn` Evaluate a ratio. If we were already evaluation a  $\langle muskip \rangle$  register, the ratio is probably  
`\calc_ratio_divide:nn` also done with this type and we'll have to convert them to regular points.

```

6436 \cs_set_protected:Npn\calc_ratio_multiply:nn#1#2{
6437   \group_end:\group_begin:
6438   \if_num:w\l_calc_current_type_int < \c_three
6439     \calc_dim_set:Nn\l_calc_B_int{#1}
6440     \calc_dim_set:Nn\l_calc_C_int{#2}
6441   \else:
6442     \calc_dim_muskip:Nn{\l_calc_B_int\etex_mutogluue:D}{#1}
6443     \calc_dim_muskip:Nn{\l_calc_C_int\etex_mutogluue:D}{#2}
6444   \fi:

```

Then store the ratio as a fraction, which we just pass on.

```

6445 \cs_gset_nopar:Npx\calc_calculated_ratio:{
6446   \int_use:N\l_calc_B_int/\int_use:N\l_calc_C_int
6447 }
6448 \group_end:

```

Here we set the new value of `\l_calc_B_register` and remember to evaluate it as the correct type. Note that the intermediate calculation is a scaled operation (meaning the intermediate value is 64-bit) so we don't get into trouble when first multiplying by a large number and then dividing.

```

6449 \l_calc_B_register
6450 \if_case:w\l_calc_current_type_int
6451 \etex_numexpr:D\or:
6452 \etex_dimexpr:D\or:
6453 \etex_glueexpr:D\or:
6454 \etex_muexpr:D\fi:
6455 \l_calc_B_register*\calc_calculated_ratio:\scan_stop:
6456 \group_begin:
6457 \calc_post_scan:N}

```

Division is just flipping the arguments around.

```

6458 \cs_new:Npn \calc_ratio_divide:nn#1#2{\calc_ratio_multiply:nn{#2}{#1}}

```

`\calc_real_evaluate:nn` Although we could define the `\real` function as a subcase of `\ratio`, this is horribly  
`\calc_real_multiply:n` inefficient since we just want to convert the decimal to a fraction.  
`\calc_real_divide:n`

```

6459 \cs_new_protected_nopar:Npn\calc_real_evaluate:nn #1#2{
6460   \group_end:
6461   \l_calc_B_register
6462   \if_case:w\l_calc_current_type_int
6463   \etex_numexpr:D\or:
6464   \etex_dimexpr:D\or:
6465   \etex_glueexpr:D\or:
6466   \etex_muexpr:D\fi:

```

```

6467 \l_calc_B_register *
6468 \tex_number:D \dim_eval:n{#1pt}/
6469 \tex_number:D\dim_eval:n{#2pt}
6470 \scan_stop:
6471 \group_begin:
6472 \calc_post_scan:N}
6473 \cs_new_nopar:Npn \calc_real_multiply:n #1{\calc_real_evaluate:nn{#1}{1}}
6474 \cs_new_nopar:Npn \calc_real_divide:n {\calc_real_evaluate:nn{1}}

```

```

\calc_maxmin_operation:Nnn
\calc_maxmin_generic:Nnn
\calc_maxmin_div_or_mul:NNnn
\calc_maxmin_multiply:
\calc_maxmin_multiply:

```

The max and min functions.

```

6475 \cs_set_protected:Npn \calc_maxmin_operation:Nnn#1#2#3{
6476 \group_begin:
6477 \calc_maxmin_generic:Nnn#1{#2}{#3}
6478 \group_end:
6479 \calc_post_scan:N
6480 }

```

#1 is either > or < and was expanded into this initially.

```

6481 \cs_new_protected:Npn \calc_maxmin_generic:Nnn#1#2#3{
6482 \group_begin:
6483 \if_case:w\l_calc_current_type_int
6484 \calc_int_set:Nn\l_calc_C_int{#2}%
6485 \calc_int_set:Nn\l_calc_B_int{#3}%
6486 \pref_global:D\g_calc_A_register
6487 \if_num:w\l_calc_C_int#1\l_calc_B_int
6488 \l_calc_C_int\else:\l_calc_B_int\fi:
6489 \or:
6490 \calc_dim_set:Nn\l_calc_C_dim{#2}%
6491 \calc_dim_set:Nn\l_calc_B_dim{#3}%
6492 \pref_global:D\g_calc_A_register
6493 \if_dim:w\l_calc_C_dim#1\l_calc_B_dim
6494 \l_calc_C_dim\else:\l_calc_B_dim\fi:
6495 \or:
6496 \calc_skip_set:Nn\l_calc_C_skip{#2}%
6497 \calc_skip_set:Nn\l_calc_B_skip{#3}%
6498 \pref_global:D\g_calc_A_register
6499 \if_dim:w\l_calc_C_skip#1\l_calc_B_skip
6500 \l_calc_C_skip\else:\l_calc_B_skip\fi:
6501 \else:
6502 \calc_muskip_set:Nn\l_calc_C_muskip{#2}%
6503 \calc_muskip_set:Nn\l_calc_B_muskip{#3}%
6504 \pref_global:D\g_calc_A_register
6505 \if_dim:w\l_calc_C_muskip#1\l_calc_B_muskip
6506 \l_calc_C_muskip\else:\l_calc_B_muskip\fi:
6507 \fi:
6508 \group_end:
6509 }
6510 \cs_new:Npn \calc_maxmin_div_or_mul:NNnn#1#2#3#4{

```

```

6511 \group_end:
6512 \group_begin:
6513 \int_zero:N\l_calc_current_type_int
6514 \group_execute_after:N#1
6515 \calc_maxmin_generic:Nnn#2{#3}{#4}
6516 \group_end:
6517 \group_begin:
6518 \calc_post_scan:N
6519 }
6520 \cs_new_nopar:Npn\calc_maxmin_multiply:{
6521   \calc_maxmin_div_or_mul:NNnn\calc_multiply_B_by_A:}
6522 \cs_new_nopar:Npn\calc_maxmin_divide: {
6523   \calc_maxmin_div_or_mul:NNnn\calc_divide_B_by_A:}

```

`\calc_error:N` The error message.

```

6524 \cs_new_nopar:Npn\calc_error:N#1{
6525   \PackageError{calc}
6526   {'\token_to_str:N#1'~ invalid~ at~ this~ point}
6527   {I~ expected~ to~ see~ one~ of:~ +~ -- *~ /~ )}
6528 }

```

## 115.4 Higher level commands

The various operations allowed.

`\calc_maxof:nn` Max and min operations

`\calc_minof:nn`

`\maxof`

`\minof`

```

6529 \cs_new:Npn \calc_maxof:nn#1#2{
6530   \calc_maxmin_operation:Nnn > \exp_not:n{#{#1}{#2}}
6531 }
6532 \cs_new:Npn \calc_minof:nn#1#2{
6533   \calc_maxmin_operation:Nnn < \exp_not:n{#{#1}{#2}}
6534 }
6535 \cs_set_eq:NN \maxof \calc_maxof:nn
6536 \cs_set_eq:NN \minof \calc_minof:nn

```

`\calc_widthof:n` Text dimension commands.

`\calc_widthof_aux:n`

`\calc_widthof_auxi:n`

`\calc_heightof:n`

`\calc_heightof_aux:n`

`\calc_heightof_auxi:n`

`\calc_depthof:n`

`\calc_depthof_aux:n`

`\calc_depthof_auxi:n`

`\calc_totalheightof:n`

`\calc_totalheightof_aux:n`

`\calc_totalheightof_auxi:n`

```

6537 \cs_new:Npn \calc_widthof:n#1{
6538   \calc_textsize:Nn \exp_not:N\calc_widthof_aux:n\exp_not:n{#{#1}}
6539 }
6540 \cs_new:Npn \calc_heightof:n#1{
6541   \calc_textsize:Nn \exp_not:N\calc_heightof_aux:n\exp_not:n{#{#1}}
6542 }
6543 \cs_new:Npn \calc_depthof:n#1{
6544   \calc_textsize:Nn \exp_not:N\calc_depthof_aux:n\exp_not:n{#{#1}}
6545 }

```

```

6546 \cs_new:Npn \calc_totalheightof:n#1{
6547   \calc_textsize:Nn \exp_not:N\calc_totalheightof_aux:n \exp_not:n{{#1}}
6548 }
6549 \cs_new:Npn \calc_widthof_aux:n #1{
6550   \exp_not:N\calc_widthof_aux:n\exp_not:n{{#1}}
6551 }
6552 \cs_new_eq:NN \calc_widthof_auxi:n \calc_widthof_aux:n
6553 \cs_new:Npn \calc_depthof_aux:n #1{
6554   \exp_not:N\calc_depthof_aux:n\exp_not:n{{#1}}
6555 }
6556 \cs_new_eq:NN \calc_depthof_auxi:n \calc_depthof_aux:n
6557 \cs_new:Npn \calc_heightof_aux:n #1{
6558   \exp_not:N\calc_heightof_aux:n\exp_not:n{{#1}}
6559 }
6560 \cs_new_eq:NN \calc_heightof_auxi:n \calc_heightof_aux:n
6561 \cs_new:Npn \calc_totalheightof_aux:n #1{
6562   \exp_not:N\calc_totalheightof_aux:n\exp_not:n{{#1}}
6563 }
6564 \cs_new_eq:NN \calc_totalheightof_auxi:n \calc_totalheightof_aux:n

```

`\calc_ratio:nn` Ratio and real.

`\calc_real:n`

```

6565 \cs_new:Npn \calc_ratio:nn#1#2{
6566   \calc_ratio_multiply:nn\exp_not:n{{#1}{#2}}}
6567 \cs_new_nopar:Npn \calc_real:n {\calc_real_evaluate:nn}

```

We can implement real and ratio without actually using these names. We'll see.

`\widthof` User commands.

```

\heightof
\depthof
\totalheightof
\ratio
\real
6568 \cs_set_eq:NN \depthof\calc_depthof:n
6569 \cs_set_eq:NN \widthof\calc_widthof:n
6570 \cs_set_eq:NN \heightof\calc_heightof:n
6571 \cs_set_eq:NN \totalheightof\calc_totalheightof:n
6572 %%\cs_set_eq:NN \ratio\calc_ratio:nn
6573 %%\cs_set_eq:NN \real\calc_real:n

```

```

\setlength
\gsetlength
\addtolength
\gaddtolength
6574 \cs_set_protected_nopar:Npn \setlength{\calc_skip_set:Nn}
6575 \cs_set_protected_nopar:Npn \gsetlength{\calc_skip_gset:Nn}
6576 \cs_set_protected_nopar:Npn \addtolength{\calc_skip_add:Nn}
6577 \cs_set_protected_nopar:Npn \gaddtolength{\calc_skip_gadd:Nn}

```

`\calc_setcounter:nn` Document commands for L<sup>A</sup>T<sub>E</sub>X<sub>2 $\epsilon$</sub>  counters. Also add support for `amstext`. Note that when `l3breqn` is used, `\mathchoice` will no longer need this switch as the argument is only executed once.

```

\calc_addtocounter:nn
\calc_stepcounter:n
\setcounter
\addtocounter
\stepcounter
\calc_chk_document_counter:nn

```

```

6578 </initex | package>
6579 <*package>
6580 \newif\iffirstchoice@ \firstchoice@true
6581 </package>
6582 <*initex | package>
6583 \cs_set_protected_nopar:Npn \calc_setcounter:nn#1#2{
6584   \calc_chk_document_counter:nn{#1}{
6585     \exp_args:Nc\calc_int_gset:Nn {c@#1}{#2}
6586   }
6587 }
6588 \cs_set_protected_nopar:Npn \calc_addtocounter:nn#1#2{
6589 </initex | package>
6590 <*package>
6591 \iffirstchoice@
6592 </package>
6593 <*initex | package>
6594   \calc_chk_document_counter:nn{#1}{
6595     \exp_args:Nc\calc_int_gadd:Nn {c@#1}{#2}
6596   }
6597 </initex | package>
6598 <*package>
6599 \fi:
6600 </package>
6601 <*initex | package>
6602 }
6603 \cs_set_protected_nopar:Npn \calc_stepcounter:n#1{
6604 </initex | package>
6605 <*package>
6606 \iffirstchoice@
6607 </package>
6608 <*initex | package>
6609   \calc_chk_document_counter:nn{#1}{
6610     \int_gincr:c {c@#1}
6611     \group_begin:
6612       \cs_set_eq:NN \@elt\@stpelt \use:c{cl@#1}
6613     \group_end:
6614   }
6615 </initex | package>
6616 <*package>
6617 \fi:
6618 </package>
6619 <*initex | package>
6620 }
6621 \cs_new_nopar:Npn \calc_chk_document_counter:nn#1{
6622   \cs_if_free:cTF{c@#1}{\@nocounterr {#1}}
6623 }
6624 \cs_set_eq:NN \setcounter \calc_setcounter:nn
6625 \cs_set_eq:NN \addtocounter \calc_addtocounter:nn
6626 \cs_set_eq:NN \stepcounter \calc_stepcounter:n
6627 </initex | package>

```

```

6628 <*package>
6629 \AtBeginDocument{
6630   \cs_set_eq:NN \setcounter \calc_setcounter:nn
6631   \cs_set_eq:NN \addtocounter \calc_addtocounter:nn
6632   \cs_set_eq:NN \stepcounter \calc_stepcounter:n
6633 }

```

Prevent the usual calc from loading.

```

6634 \cs_set_nopar:cpn{ver@calc.sty}{2005/08/06}
6635 </package>

6636 <*showmemory>
6637 \showMemUsage
6638 </showmemory>

```

## 116 l3file implementation

The usual lead-off.

```

6639 <*package>
6640 \ProvidesExplPackage
6641   {\filename}{\filedate}{\fileversion}{\filedescription}
6642 \package_check_loaded_expl:
6643 </package>
6644 <*initex | package>

```

`\g_file_record_clist`    When files are read with logging, the names are added here. There are two lists, one  
`\g_file_record_full_clist`    for everything and one for only those items which might later be listed (as in L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub>'s  
`\listfiles`).

```

6645 \clist_new:N \g_file_record_clist
6646 \clist_new:N \g_file_record_full_clist

```

`\l_file_search_path_clist`    Checking input needs a stream to work with

```

6647 \clist_new:N \l_file_search_path_clist

```

`\l_file_test_read_stream`    Checking input needs a stream to work with

```

6648 \ior_new:N \l_file_test_read_stream

```

`\l_file_tmp_bool`    A flag is needed for internal purposes.

```

6649 \bool_new:N \l_file_tmp_bool

```

`\l_file_tmp_tl`    A scratch token list variable.

```

6650 \tl_new:N \l_file_tmp_tl

```

<pre> \file_if_exist_p:n \file_if_exist:nTF \file_if_exist_path:n \file_if_exist_aux:n </pre>	<p>Checking if a file exists takes place in two parts. First, there is a simple check “here”. If that fails, then there is a loop over the current search path.</p> <pre> 6651 \prg_new_conditional:Nnn \file_if_exist:n {p,TF,T,F} { 6652   \ior_open:Nn \l_file_test_read_stream {#1} 6653   \ior_if_eof:NTF \l_file_test_read_stream { 6654     \file_if_exist_path:n {#1} 6655   }{ 6656     \ior_close:N \l_file_test_read_stream 6657     \prg_return_true: 6658   } 6659 } 6660 \cs_new_nopar:Npn \file_if_exist_path:n #1 { 6661   \bool_set_false:N \l_file_tmp_bool 6662   \cs_set_nopar:Npn \file_if_exist_aux:n ##1 { 6663     \ior_open:Nn \l_file_test_read_stream { #1 ##1 } 6664     \ior_if_eof:NF \l_file_test_read_stream { 6665       \bool_set_true:N \l_file_tmp_bool 6666       \clist_map_break: 6667     } 6668   } 6669 &lt;/initex   package&gt; 6670 &lt;*package&gt; 6671   \cs_if_exist:NT \input@path { 6672     \cs_set_eq:NN \l_file_search_path_clist \input@path 6673   } 6674 &lt;/package&gt; 6675 &lt;*initex   package&gt; 6676   \clist_map_function:NN \l_file_search_path_clist \file_if_exist_aux:n 6677   \ior_close:N \l_file_test_read_stream 6678   \bool_if:NTF \l_file_tmp_bool { 6679     \prg_return_true: 6680   }{ 6681     \prg_return_false: 6682   } 6683 } 6684 \cs_new_nopar:Npn \file_if_exist_aux:n #1 { } </pre>
<pre> \file_add_path:nN \file_add_path_search:n \file_add_path_aux:n </pre>	<p>Checking if a file exists takes place in two parts. First, there is a simple check “here”. If that fails, then there is a loop over the current search path.</p> <pre> 6685 \cs_new_nopar:Npn \file_add_path:nN #1#2 { 6686   \tl_clear:N #2 6687   \ior_open:Nn \l_file_test_read_stream {#1} 6688   \ior_if_eof:NTF \l_file_test_read_stream { 6689     \file_add_path_search:nN {#1} #2 6690   }{ 6691     \tl_set:Nn #2 {#1} 6692   } 6693   \ior_close:N \l_file_test_read_stream </pre>



```

6694 }
6695 \cs_new_nopar:Npn \file_add_path_search:nN #1#2 {
6696   \cs_set_nopar:Npn \file_add_path_aux:n ##1 {
6697     \ior_open:Nn \l_file_test_read_stream { ##1 #1 }
6698     \ior_if_eof:NF \l_file_test_read_stream {
6699       \tl_set:Nn #2 { ##1 #1 }
6700       \clist_map_break:
6701     }
6702   }
6703 </initex | package>
6704 <*package>
6705   \cs_if_exist:NT \input@path {
6706     \cs_set_eq:NN \l_file_search_path_clist \input@path
6707   }
6708 </package>
6709 <*initex | package>
6710   \clist_map_function:NN \l_file_search_path_clist \file_add_path_aux:n
6711 }
6712 \cs_new_nopar:Npn \file_add_path_aux:n #1 { }

```

`\file_input:n` `\file_add_path:nN` will return an empty token list variable if the file is not found. This is used rather than `\file_if_exist:nT` here as it saves running the same loop twice.

```

6713 \cs_new:Npn \file_input:n #1 {
6714   \file_add_path:nN {#1} \l_file_tmp_tl
6715   \tl_if_empty:NF \l_file_tmp_tl {
6716     \file_input_no_check:n \l_file_tmp_tl
6717   }
6718 }
6719 \cs_new:Npn \file_input_no_record:n #1 {
6720   \file_add_path:nN {#1} \l_file_tmp_tl
6721   \tl_if_empty:NF \l_file_tmp_tl {
6722     \file_input_no_check_no_record:n \l_file_tmp_tl
6723   }
6724 }

```

`\file_input_no_check:n` File input records what is going on before setting to work.

```

6725 \cs_new_nopar:Npn \file_input_no_check:n #1 {
6726   \clist_gput_right:Nx \g_file_record_clist {#1}
6727   \wlog{ADDING: #1}
6728 </initex | package>
6729 <*package>
6730   \@addtofilelist {#1}
6731 </package>
6732 <*initex | package>
6733   \clist_gput_right:Nx \g_file_record_full_clist {#1}
6734   \tex_input:D #1 ~
6735 }

```

`\file_input_no_check_no_record:n` Inputting a file without adding to the main record is basically the same: even in this case the file goes on the full log.

```
6736 \cs_new_nopar:Npn \file_input_no_check_no_record:n #1 {
6737   \clist_gput_right:Nx \g_file_record_full_clist {#1}
6738   \tex_input:D #1 ~
6739 }
```

`\file_list:` Two functions to list all files used to the log: the full version includes everything whereas  
`\file_list_full:` the standard version uses the shorter record.

```
\file_list:N
6740 \cs_new_nopar:Npn \file_list: {
6741   \file_list:N \g_file_record_clist
6742 }
6743 \cs_new_nopar:Npn \file_list_full: {
6744   \file_list:N \g_file_record_full_clist
6745 }
6746 \cs_new_nopar:Npn \file_list:N #1 {
6747   \clist_remove_duplicates:N #1
6748   \iow_log:x { ~File~List~ }
6749   \clist_map_function:NN #1 \file_list_aux:n
6750   \iow_log:x { ***** }
6751 }
6752 \cs_new_nopar:Npn \file_list_aux:n #1 {
6753   \iow_log:x { #1 }
6754 }
```

When used as a package, there is a need to hold onto the standard file list as well as the new one here.

```
6755 </initex | package>
6756 <*package>
6757 % \begin{macrocode}
6758 \AtBeginDocument{
6759   \clist_put_right:NV \g_file_record_clist \@filelist
6760   \clist_put_right:NV \g_file_record_full_clist \@filelist
6761 }
6762 </package>
```

# Index

The italic numbers denote the pages where the corresponding entry is described, numbers underlined point to the definition, all others indicate the places where it is used.

Symbols	
\!	1521
\%	4856
\	2069, 2070, 2082, 2083, 4988, 4990
\*	2309, 2311, 2315, 2320
\,	5554, 5556
\-	63
\.bool_gset:N	5997
\.bool_set:N	5997
\.choice:	6003
\.choice_code:n	6006
\.choice_code:x	6006
\.code:n	6012
\.code:x	6012
\.default:V	6018
\.default:n	6018
\.dim_gset:N	6024
\.dim_gset:c	6024
\.dim_set:N	6024
\.dim_set:c	6024
\.generate_choices:n	6036
\.int_gset:N	6039
\.int_gset:c	6039
\.int_set:N	6039
\.int_set:c	6039
\.meta:n	6051
\.meta:x	6051
\.skip_gset:N	6057
\.skip_gset:c	6057
\.skip_set:N	6057
\.skip_set:c	6057
\.tl_gset:N	6069
\.tl_gset:c	6069
\.tl_gset_x:N	6069
\.tl_gset_x:c	6069
\.tl_set:N	6069
\.tl_set:c	6069
\.tl_set_x:N	6069
\.tl_set_x:c	6069
\.value_forbidden:	6093
\.value_required:	6093
\/	62
\:	588, 592, 1014, 2490
\:::	182, 1454, 1457, 1459, 1459–1461, 1463, 1464, 1466, 1469, 1472, 1480, 1486, 1491, 1499, 1542–1549, 1551–1558, 1560–1562, 1564, 1566–1568, 1570–1573, 1575–1578, 1580–1585, 1587, 1588, 1653, 1657, 1660, 1664, 1670–1672, 1674, 1680
\::N	182, 1463, 1463, 1546–1549, 1568, 1570–1573, 1580, 1581, 1680
\::V	182, 1491, 1491, 1544, 1548, 1557, 1564, 1568
\::V_unbraced	1652, 1660, 1671, 1674, 1680
\::c	182, 1466, 1466, 1551, 1554, 1560, 1575, 1580–1585, 1674
\::f	182, 1472, 1472, 1542, 1546, 1552–1555
\::f_unbraced	1652, 1653, 1670
\::n	182, 1460, 1460, 1555–1558, 1570, 1571, 1575–1578, 1585
\::o	182, 1469, 1469, 1552, 1556, 1560–1562, 1566, 1570, 1572, 1573, 1576, 1578, 1581–1583, 1587, 1588
\::o_unbraced	1652, 1657
\::v	182, 1491, 1499, 1543, 1547
\::v_unbraced	1652, 1664, 1672
\::x	182, 1478, 1480, 1486, 1545, 1549, 1551, 1558, 1562, 1566, 1567, 1571, 1573, 1577, 1578, 1584, 1585, 1587
\=	5553, 5555
\?	2403, 2490
\@	718, 1014, 1015, 3934, 3935
\@end	691
\@hyph	695
\@input	689
\@italiccorr	694
\@underline	690
\@addtofilelist	6730
\@current	717
\@currname	716
\@currnamestack	711, 719
\@declaredoptions	714
\@elt	6612
\@empty	713, 714
\@filelist	6759, 6760

\@gobble .....	697	\atop .....	184
\@ifpackageloaded .....	731	\atopwithdelims .....	185
\@nil .....	711, 715		
\@nocounterr .....	6622		
\@p@pfilename .....	711, 715		
\@popfilename .....	136, 664, 671, 672		
\@pushfilename .....	136, 664, 664, 669		
\@stpelt .....	6612		
\@tempboxa .....	5364		
\@unknownoptionerror .....	712		
\\ .....	1139,		
	1141, 1145, 1153, 1154, 2403, 4996,		
	4999, 5022, 5029, 5262, 5263, 5270,		
	5271, 5278, 5279, 6101, 6105, 6106,		
	6111, 6115, 6122, 6123, 6129, 6137,		
	6143, 6145, 6151, 6152, 6158–6160		
\{ .....	4331, 4510, 4689, 4691, 4857		
\} .....	4331, 4510, 4689, 4691, 4858, 4989		
\_ .....	587, 591, 2082		
\  .....	2902		
	<b>Numbers</b>		
\8 .....	5555		
\9 .....	5556		
\_ .....	61, 1522, 4839,		
	4923, 4964, 4969, 4980, 4985, 4988,		
	4989, 4991, 4997, 5023, 5030, 5465		
	<b>A</b>		
\A .....	2404, 2492, 3934, 3936		
\a .....	1006		
\above .....	182		
\abovedisplayshortskip .....	195		
\abovedisplayskip .....	196		
\abovewithdelims .....	183		
\accent .....	233		
\addtocounter .....	132, 6578, 6625, 6631		
\addtolength .....	132, 6574, 6576		
\adjdemerits .....	270		
\advance .....	77		
\afterassignment .....	87		
\aftergroup .....	88		
\alloc_reg:NnNN .....	2734, 2735,		
	3281, 3282, 3397, 3398, 3457, 3458,		
	4110, 4111, 4810, 4861, 5300, 5301		
\alloc_setup_type:nnn ...	2733, 3280,		
	3396, 3456, 4109, 4809, 4860, 5298		
\AtBeginDocument .....	5499, 6629, 6758		
		<b>B</b>	
		\B .....	3935, 3937
		\badness .....	332
		\baselineskip .....	260
		\batchmode .....	153
		\begin .....	5514, 6757
		\begingroup .....	2, 91
		\beginL .....	445
		\beginR .....	447
		\belowdisplayshortskip .....	197
		\belowdisplayskip .....	198
		\binoppenalty .....	221
		\bool(:w .....	1880
		\bool_)_0:w .....	1880
		\bool_)_1:w .....	1880
		\bool_8_0:w .....	1880
		\bool_8_1:w .....	1880
		\bool_:w .....	1880
		\bool_choose:NN .....	1880, 1899, 1902
		\bool_cleanup:N ..	1880, 1895, 1897, 1898
		\bool_do_until:cn .....	36, 1872
		\bool_do_until:Nn 36, 1872, 1876, 1877, 1879	
		\bool_do_until:nn ..	39, 1937, 1946, 1947
		\bool_do_while:cn .....	36, 1872
		\bool_do_while:Nn 36, 1872, 1872, 1873, 1875	
		\bool_do_while:nn ..	39, 1937, 1943, 1944
		\bool_eval_skip_to_end:Nw .....	
			1909, 1910, 1911, 1911, 1920
		\bool_eval_skip_to_end_aux:Nw .....	
			1911, 1912, 1914
		\bool_eval_skip_to_end_auxii:Nw .....	
			1911, 1917, 1919
		\bool_get_next:N .....	1880,
			1882, 1884, 1892, 1895, 1903, 1904
		\bool_gset:cn .....	38, 1922
		.bool_gset:N .....	124
		\bool_gset:Nn .....	38, 1922, 1923, 1927
		\bool_gset_eq:cc .....	36, 1847, 1854
		\bool_gset_eq:cN .....	36, 1847, 1853
		\bool_gset_eq:Nc .....	36, 1847, 1852
		\bool_gset_eq:NN .....	36, 1847, 1851
		\bool_gset_false:c .....	36, 1837, 1846
		\bool_gset_false:N .....	36, 1837, 1845
		\bool_gset_true:c .....	36, 1837, 1844
		\bool_gset_true:N .....	36, 1837, 1843
		\bool_I_0:w .....	1880
		\bool_I_1:w .....	1880

\bool\_if:cTF ..... 36, 1857  
\bool\_if:N ..... 1857  
\bool\_if:n ..... 1933  
\bool\_if:Nf ..... 1863, 1869, 1877, 2993  
\bool\_if:nf ..... 1941, 1947  
\bool\_if:NT ..... 1862,  
1865, 1873, 2993, 2994, 5588, 5976  
\bool\_if:nT ..... 1938, 1944  
\bool\_if:NTF ..... 36, 1287, 1857, 1861,  
2985, 5660, 5836, 5948, 5960, 6678  
\bool\_if:nTF ..... 37, 1880, 2619, 3378  
\bool\_if\_p:c ..... 36, 1857  
\bool\_if\_p:N ..... 36, 1857, 1860  
\bool\_if\_p:n ..... 37, 1880,  
1880, 1922, 1924, 1928, 1930, 1934  
\bool\_new:c ..... 35, 1837, 1838  
\bool\_new:N ..... 35, 1837, 1837,  
1855, 1856, 5550, 5726, 5740, 6649  
\bool\_not\_p:n ..... 38, 1928, 1928  
\bool\_p:w ..... 1880  
\bool\_S\_0:w ..... 1880  
\bool\_S\_1:w ..... 1880  
\bool\_set:cn ..... 38, 1922  
\bool\_set:N ..... 124  
\bool\_set:Nn ..... 38, 1922, 1922, 1926  
\bool\_set\_eq:cc ..... 36, 1847, 1850  
\bool\_set\_eq:cN ..... 36, 1847, 1849  
\bool\_set\_eq:Nc ..... 36, 1847, 1848  
\bool\_set\_eq:NN ..... 36, 1847, 1847  
\bool\_set\_false:c ..... 36, 1837, 1842  
\bool\_set\_false:N .....  
.... 36, 1837, 1841, 5821, 5940, 6661  
\bool\_set\_true:c ..... 36, 1837, 1840  
\bool\_set\_true:N .....  
36, 1837, 1839, 5551, 5817, 5936, 6665  
\bool\_until\_do:cn ..... 36, 1864  
\bool\_until\_do:Nn 36, 1864, 1868, 1869, 1871  
\bool\_until\_do:nn .. 39, 1937, 1940, 1941  
\bool\_while\_do:cn ..... 36, 1864  
\bool\_while\_do:Nn 36, 1864, 1864, 1865, 1867  
\bool\_while\_do:nn .. 39, 1937, 1937, 1938  
\bool\_xor\_p:nn ..... 38, 1929, 1929  
\botmark ..... 168  
\botmarks ..... 394  
\box ..... 376  
\box\_clear:c ..... 116, 5347  
\box\_clear:N ..... 116, 5347, 5347–5349  
\box\_dp:c ..... 116, 5351  
\box\_dp:N 116, 5351, 5352, 5355, 6422, 6423  
\box\_gclear:c ..... 116, 5347  
\box\_gclear:N ..... 116, 5347, 5349, 5350  
\box\_gset\_eq:cc ..... 115, 5336  
\box\_gset\_eq:cN ..... 115, 5336  
\box\_gset\_eq:Nc ..... 115, 5336  
\box\_gset\_eq:NN ... 115, 5336, 5336, 5337  
\box\_gset\_to\_last:c ..... 115, 5339  
\box\_gset\_to\_last:N 115, 5339, 5341, 5342  
\box\_ht:c ..... 116, 5351  
\box\_ht:N 116, 5351, 5351, 5354, 6421, 6423  
\box\_if\_empty:cTF ..... 115, 5327  
\box\_if\_empty:N ..... 5327  
\box\_if\_empty:Nf ..... 5333  
\box\_if\_empty:NT ..... 5332  
\box\_if\_empty:NTF ..... 115, 5327, 5331  
\box\_if\_empty\_p:c ..... 115, 5327  
\box\_if\_empty\_p:N ..... 115, 5327, 5330  
\box\_if\_horizontal:cTF ..... 114, 5313  
\box\_if\_horizontal:N ..... 5313  
\box\_if\_horizontal:Nf ..... 5322  
\box\_if\_horizontal:NT ..... 5321  
\box\_if\_horizontal:NTF . 114, 5313, 5320  
\box\_if\_horizontal\_p:c ..... 114, 5313  
\box\_if\_horizontal\_p:N . 114, 5313, 5319  
\box\_if\_vertical:cTF ..... 115, 5313  
\box\_if\_vertical:N ..... 5316  
\box\_if\_vertical:Nf ..... 5326  
\box\_if\_vertical:NT ..... 5325  
\box\_if\_vertical:NTF ... 115, 5313, 5324  
\box\_if\_vertical\_p:c ..... 115, 5313  
\box\_if\_vertical\_p:N ... 115, 5313, 5323  
\box\_move\_down:nn ..... 115, 5343, 5346  
\box\_move\_left:nn ..... 115, 5343, 5343  
\box\_move\_right:nn ..... 115, 5343, 5344  
\box\_move\_up:nn ..... 115, 5343, 5345  
\box\_new:c ..... 114, 5297  
\box\_new:N .....  
114, 5297, 5300, 5304, 5309, 5365–5367  
\box\_new\_l:N ..... 5301  
\box\_set\_eq:cc ..... 115, 5334  
\box\_set\_eq:cN ..... 115, 5334  
\box\_set\_eq:Nc ..... 115, 5334  
\box\_set\_eq:NN 115, 5334, 5334–5336, 5347  
\box\_set\_to\_last:c ..... 115, 5339  
\box\_set\_to\_last:N . 115, 5339, 5339–5341  
\box\_show:c ..... 116, 5361  
\box\_show:N ..... 116, 5361, 5361, 5362  
\box\_use:c ..... 116, 5357  
\box\_use:N ..... 116, 5357, 5359, 5360  
\box\_use\_clear:c ..... 116, 5357  
\box\_use\_clear:N .. 116, 5357, 5357, 5358

- `\box_wd:c` ..... [116](#), [5351](#)
- `\box_wd:N` .... [116](#), [5351](#), [5353](#), [5356](#), [6420](#)
- `\boxmaxdepth` ..... [338](#)
- `\brokenpenalty` ..... [295](#)
- C**
- `\C` ..... [2404](#), [2493](#)
- `\c_active_char_token` [48](#), [2306](#), [2321](#), [2364](#)
- `\c_alignment_tab_token` [48](#), [2306](#), [2312](#), [2336](#)
- `\c_eight` ..... [58](#), [2233](#), [2249](#), [2942](#), [2952](#)
- `\c_eleven` ..... [58](#), [2236](#), [2252](#), [2942](#), [2955](#)
- `\c_empty_box` .. [116](#), [5347](#), [5363](#), [5363](#), [5365](#)
- `\c_empty_tl` ..... [79](#), [3546](#),  
[3548](#), [3655](#), [3655](#), [3665](#), [4288](#), [4455](#)
- `\c_empty_toks` ..... [86](#), [4157](#), [4249](#), [4249](#)
- `\c_false_bool` .....  
... [11](#), [947](#), [967](#), [1003](#), [1004](#), [1028](#),  
[1263](#), [1272](#), [1837](#), [1838](#), [1841](#), [1842](#),  
[1845](#), [1846](#), [1905](#), [1907](#), [1909](#), [1931](#),  
[2446](#), [2540](#), [2977](#), [2980](#), [2986](#), [4085](#)
- `\c_fifteen` .... [58](#), [2240](#), [2256](#), [2942](#), [2959](#)
- `\c_five` ..... [58](#), [2230](#), [2246](#), [2942](#), [2949](#)
- `\c_four` ..... [58](#), [2229](#), [2245](#), [2942](#), [2948](#)
- `\c_fourteen` .... [58](#), [2239](#), [2255](#), [2942](#), [2958](#)
- `\c_group_begin_token` .....  
[48](#), [2306](#), [2306](#), [2324](#), [2620](#), [5380](#), [5406](#)
- `\c_group_end_token` ... [48](#), [2306](#), [2307](#),  
[2328](#), [2621](#), [5381](#), [5384](#), [5409](#), [5414](#)
- `\c_hundred_one` ..... [58](#), [2942](#), [2962](#)
- `\c_ior_log_stream` ..... [107](#), [4822](#), [4825](#)
- `\c_ior_term_stream` ..... [107](#), [4822](#), [4823](#)
- `\c_iow_comment_char` .... [107](#), [4856](#), [4856](#)
- `\c_iow_lbrace_char` .... [107](#), [4856](#), [4857](#)
- `\c_iow_log_stream` .....  
... [107](#), [4822](#), [4824](#), [4830](#), [4831](#)
- `\c_iow_rbrace_char` .... [107](#), [4856](#), [4858](#)
- `\c_iow_term_stream` .....  
... [107](#), [4822](#), [4822](#), [4832](#), [4833](#)
- `\c_job_name_tl` ..... [79](#), [3654](#), [3654](#)
- `\c_keys_properties_root_tl` .....  
... [130](#), [5713](#), [5714](#), [5827](#), [5913](#), [5916](#)
- `\c_keys_root_tl` .....  
[130](#), [5713](#), [5713](#), [5745](#), [5765](#), [5768](#),  
[5787](#), [5792](#), [5797](#), [5800](#), [5862](#), [5870](#),  
[5878](#), [5919](#), [5971](#), [5977](#), [5979](#), [5985](#)
- `\c_keys_value_forbidden_tl` .....  
... [130](#), [5715](#), [5715](#)
- `\c_keys_value_required_tl` [130](#), [5715](#), [5716](#)
- `\c_KV_single_equal_sign_tl` .....  
... [327](#), [5544](#), [5546](#), [5631](#), [5682](#)
- `\c_letter_token` .... [48](#), [2306](#), [2318](#), [2356](#)
- `\c_luatex_is_engine_bool` .....  
... [26](#), [1260](#), [1270](#), [1272](#), [1279](#)
- `\c_math_shift_token` . [48](#), [2306](#), [2310](#), [2332](#)
- `\c_math_subscript_token` .....  
... [48](#), [2306](#), [2316](#), [2348](#)
- `\c_math_superscript_token` .....  
... [48](#), [2306](#), [2314](#), [2344](#)
- `\c_max_dim` ..... [70](#), [3435](#), [3436](#)
- `\c_max_int` ..... [58](#), [2972](#), [2972](#)
- `\c_max_register_num` .....  
... [61](#), [2733](#), [2933](#), [3115](#),  
[3115](#), [3280](#), [3396](#), [3456](#), [4109](#), [5298](#)
- `\c_max_skip` [67](#), [3367](#), [3370](#), [3371](#), [3375](#), [3436](#)
- `\c_minus_one` . [15](#), [58](#), [1092](#), [1093](#), [1096](#),  
[1097](#), [1102](#), [2762](#), [2780](#), [2782](#), [2932](#),  
[2942](#), [2942](#), [2943](#), [3077](#), [3079](#), [3945](#),  
[3961](#), [3971](#), [3979](#), [4824](#), [4825](#), [4892](#)
- `\c_msg_error_tl` [113](#), [4893](#), [4894](#), [5135](#), [5233](#)
- `\c_msg_fatal_text_tl` .....  
... [113](#), [4897](#), [4897](#), [5130](#), [5227](#)
- `\c_msg_fatal_tl` .....  
[113](#), [4893](#), [4893](#), [5124](#), [5126](#), [5129](#), [5220](#)
- `\c_msg_help_text_tl` [113](#), [4897](#), [4900](#), [5005](#)
- `\c_msg_hide_tl` ..... [4927](#), [5006](#)
- `\c_msg_hide_tl<spaces>` ..... [4922](#)
- `\c_msg_info_tl` .... [113](#), [4893](#), [4896](#), [5159](#)
- `\c_msg_kernel_bug_more_text_tl` ....  
... [113](#), [4897](#), [4906](#), [5288](#)
- `\c_msg_kernel_bug_text_tl` .....  
... [113](#), [4897](#), [4903](#), [5285](#)
- `\c_msg_more_text_prefix_tl` .....  
... [113](#), [4931](#), [4932](#),  
[4979](#), [4984](#), [5142](#), [5144](#), [5242](#), [5244](#)
- `\c_msg_no_info_text_tl` .....  
... [113](#), [4897](#), [4912](#), [5015](#), [5147](#), [5247](#)
- `\c_msg_on_line_tl` . [113](#), [4930](#), [4930](#), [4943](#)
- `\c_msg_return_text_tl` .... [113](#), [4897](#),  
[4910](#), [4914](#), [4916](#), [5265](#), [5273](#), [5281](#)
- `\c_msg_text_prefix_tl` .....  
... [113](#), [4931](#), [4931](#), [4955](#),  
[4959](#), [4978](#), [4983](#), [5086](#), [5127](#), [5138](#),  
[5153](#), [5160](#), [5166](#), [5172](#), [5223](#), [5236](#)
- `\c_msg_warning_tl` . [113](#), [4893](#), [4895](#), [5152](#)
- `\c_nine` ..... [58](#), [2234](#), [2250](#), [2942](#), [2953](#)
- `\c_one` ..... [58](#), [2226](#),  
[2242](#), [2757](#), [2779](#), [2781](#), [2942](#), [2945](#),  
[6219](#), [6222](#), [6225](#), [6228](#), [6231](#), [6234](#)
- `\c_other_char_token` . [48](#), [2306](#), [2319](#), [2360](#)
- `\c_parameter_token` ..... [48](#), [2306](#), [2313](#)

- \c\_peek\_true\_remove\_next\_tl ..... 212, 2589, 2600, 2601
- \c\_seven . 58, 1719, 2232, 2248, 2942, 2951
- \c\_six ... 58, 1715, 2231, 2247, 2942, 2950
- \c\_sixteen .. 15, 58, 1092, 1099, 1105, 2942, 2960, 4809, 4822, 4823, 4860
- \c\_space\_token ..... 48, 2306, 2317, 2352, 2622, 2713
- \c\_ten ... 58, 2235, 2251, 2942, 2954, 5465
- \c\_ten\_thousand ..... 58, 2942, 2966
- \c\_ten\_thousand\_four .... 58, 2942, 2970
- \c\_ten\_thousand\_one ..... 58, 2942, 2967
- \c\_ten\_thousand\_three ... 58, 2942, 2969
- \c\_ten\_thousand\_two ..... 58, 2942, 2968
- \c\_thirteen .... 58, 2238, 2254, 2942, 2957
- \c\_thirty\_two ..... 58, 2942, 2961
- \c\_thousand ..... 58, 2942, 2965
- \c\_three 58, 2228, 2244, 2942, 2947, 6255, 6259, 6263, 6267, 6271, 6275, 6438
- \c\_true\_bool ..... 11, 947, 967, 1003, 1003, 1032, 1261, 1270, 1839, 1840, 1843, 1844, 1906, 1908, 1910, 1931, 2974, 2977, 2980, 2987, 4083
- \c\_twelve ..... 58, 2070, 2083, 2237, 2253, 2942, 2956
- \c\_twenty\_thousand ..... 58, 2942, 2971
- \c\_two .... 58, 2227, 2243, 2942, 2946, 6237, 6240, 6243, 6246, 6249, 6252
- \c\_two\_ats\_with\_two\_catcodes\_tl .... 3933, 3940, 3944, 3955, 3978
- \c\_twohundred\_fifty\_five . 58, 2942, 2963
- \c\_twohundred\_fifty\_six . 58, 2942, 2964
- \c\_undefined ..... 44, 50, 4979, 5919
- \c\_undefined:D ..... 1256, 1258
- \c\_xetex\_is\_engine\_bool ..... 26, 1260, 1261, 1263, 1266, 1275
- \c\_zero ..... 15, 58, 946, 951, 956, 961, 966, 971, 976, 981, 1074, 1080, 1092, 1100, 1712, 1713, 1717, 1765, 1792, 1816, 2156, 2178, 2225, 2241, 2787, 2789, 2942, 2944, 3000, 3181, 3211, 3215, 3216, 3222, 3280, 3379, 3380, 3396, 3456, 3751, 4109, 4809, 4860, 5298, 5839, 6201, 6204, 6207, 6210, 6213, 6216
- \c\_zero\_dim .... 70, 3435, 3435, 5386, 6415
- \c\_zero\_skip 68, 3307, 3367, 3368, 3369, 3374, 3386, 3387, 3411, 3435, 5416
- \calc\_add: ..... 349, 6307, 6356, 6362
- \calc\_add\_A\_to\_B: . 349, 6356, 6362, 6365
- \calc\_addtocounter:nn ..... 132, 6578, 6588, 6625, 6631
- \calc\_assign\_generic:NNNNnn ..... 349, 6185, 6185, 6201, 6204, 6207, 6210, 6213, 6216, 6219, 6222, 6225, 6228, 6231, 6234, 6237, 6240, 6243, 6246, 6249, 6252, 6255, 6259, 6263, 6267, 6271, 6275
- \calc\_calculate\_box\_size:nnn ..... 133, 6413, 6413, 6424
- \calc\_calculate\_box\_size\_aux:n .... 6413, 6415, 6417
- \calc\_calculated\_ratio: .... 6445, 6455
- \calc\_chk\_document\_counter:nn .... 349, 6578, 6584, 6594, 6609, 6621
- \calc\_close: ..... 349, 6296, 6301, 6311
- \calc\_depthof:n ... 132, 6537, 6543, 6568
- \calc\_depthof\_aux:n ..... 6422, 6427, 6537, 6544, 6553, 6554, 6556
- \calc\_depthof\_auxi:n ... 6427, 6537, 6556
- \calc\_dim\_add:Nn ..... 133, 6218, 6224
- \calc\_dim\_gadd:Nn ..... 133, 6218, 6227
- \calc\_dim\_gset:Nn ..... 133, 6218, 6221
- \calc\_dim\_gsub:Nn ..... 133, 6218, 6233
- \calc\_dim\_muskip:Nn ..... 6442, 6443
- \calc\_dim\_set:Nn ..... 133, 6218, 6218, 6439, 6440, 6490, 6491
- \calc\_dim\_sub:Nn ..... 133, 6218, 6230
- \calc\_divide: ..... 349, 6350, 6383, 6411
- \calc\_divide:N .... 349, 6310, 6324, 6340
- \calc\_divide\_B\_by\_A: ..... 349, 6383, 6400, 6412, 6523
- \calc\_error:N ..... 349, 6315, 6524, 6524
- \calc\_generic\_add\_or\_subtract:N .... 349, 6356, 6356, 6362, 6364
- \calc\_generic\_multiply\_or\_divide:N . 349, 6383, 6383, 6410, 6412
- \calc\_heightof:n .. 132, 6537, 6540, 6570
- \calc\_heightof\_aux:n ..... 6421, 6429, 6537, 6541, 6557, 6558, 6560
- \calc\_heightof\_auxi:n .. 6429, 6537, 6560
- \calc\_init\_B: ..... 349, 6292, 6293, 6296, 6296, 6360
- \calc\_int\_add:Nn ..... 132, 6200, 6206
- \calc\_int\_gadd:Nn . 132, 6200, 6209, 6595
- \calc\_int\_gset:Nn . 132, 6200, 6203, 6585
- \calc\_int\_gsub:Nn ..... 132, 6200, 6215
- \calc\_int\_set:Nn 132, 6200, 6200, 6484, 6485
- \calc\_int\_sub:Nn ..... 132, 6200, 6212

`\calc_maxmin_div_or_mul:Nnn` .....  
         349, 6475, 6510, 6521, 6523  
`\calc_maxmin_divide:` ..... 6342, 6522  
`\calc_maxmin_generic:Nnn` .....  
         349, 6475, 6477, 6481, 6515  
`\calc_maxmin_multiply:` .....  
         349, 6326, 6475, 6520  
`\calc_maxmin_operation:Nnn` 349, 6284,  
         6325, 6341, 6475, 6475, 6530, 6533  
`\calc_maxof:nn` .... 132, 6529, 6529, 6535  
`\calc_minof:nn` .... 132, 6529, 6532, 6536  
`\calc_multiply:` ... 349, 6334, 6383, 6409  
`\calc_multiply:N` .. 349, 6309, 6324, 6324  
`\calc_multiply_B_by_A:` .....  
         349, 6383, 6391, 6410, 6521  
`\calc_muskip_add:Nn` .... 133, 6254, 6262  
`\calc_muskip_gadd:Nn` ... 133, 6254, 6266  
`\calc_muskip_gset:Nn` ... 133, 6254, 6258  
`\calc_muskip_gsub:Nn` ... 133, 6254, 6274  
`\calc_muskip_set:Nn` .....  
         133, 6254, 6254, 6502, 6503  
`\calc_muskip_sub:Nn` .... 133, 6254, 6270  
`\calc_next:w` ..... 6306–6312,  
         6314, 6323, 6326, 6329, 6332, 6334,  
         6338, 6342, 6345, 6348, 6350, 6354  
`\calc_numeric:` .... 349, 6286, 6296, 6297  
`\calc_open:w` .. 349, 6195, 6280, 6291, 6291  
`\calc_post_scan:N` .....  
         349, 6298, 6304, 6305, 6305,  
         6312, 6434, 6457, 6472, 6479, 6518  
`\calc_pre_scan:N` .....  
         349, 6278, 6278, 6294, 6361, 6389  
`\calc_ratio:nn` 132, 6191, 6565, 6565, 6572  
`\calc_ratio_divide:nn` 349, 6345, 6436, 6458  
`\calc_ratio_multiply:nn` .. 349, 6328,  
         6329, 6344, 6436, 6436, 6458, 6566  
`\calc_real:n` .. 132, 6190, 6565, 6567, 6573  
`\calc_real_divide:n` 349, 6348, 6459, 6474  
`\calc_real_evaluate:nn` ... 349, 6331,  
         6347, 6459, 6459, 6473, 6474, 6567  
`\calc_real_multiply:n` 349, 6332, 6459, 6473  
`\calc_setcounter:nn` .....  
         132, 6578, 6583, 6624, 6630  
`\calc_skip_add:Nn` . 133, 6236, 6242, 6576  
`\calc_skip_gadd:Nn` . 133, 6236, 6245, 6577  
`\calc_skip_gset:Nn` . 133, 6236, 6239, 6575  
`\calc_skip_gsub:Nn` ..... 133, 6236, 6251  
`\calc_skip_set:Nn` .....  
         133, 6236, 6236, 6496, 6497, 6574  
`\calc_skip_sub:Nn` ..... 133, 6236, 6248  
`\calc_stepcounter:n` .....  
         132, 6578, 6603, 6626, 6632  
`\calc_subtract:` ... 349, 6308, 6356, 6363  
`\calc_subtract_A_from_B:` .....  
         349, 6356, 6364, 6374  
`\calc_textsize:Nn` ..... 349, 6282,  
         6418, 6418, 6538, 6541, 6544, 6547  
`\calc_totalheightof:n` 132, 6537, 6546, 6571  
`\calc_totalheightof_aux:n` .... 6423,  
         6430, 6537, 6547, 6561, 6562, 6564  
`\calc_totalheightof_auxi:n` .....  
         6430, 6537, 6564  
`\calc_widthof:n` ... 132, 6537, 6537, 6569  
`\calc_widthof_aux:n` ..... 6420,  
         6428, 6537, 6538, 6549, 6550, 6552  
`\calc_widthof_auxi:n` ... 6428, 6537, 6552  
`\catcode` . 26–28, 30, 31, 34–36, 38, 39, 380  
`\char` ..... 234  
`\char_gset_mathcode:nn` .. 48, 2257, 2262  
`\char_gset_mathcode:w` 48, 2257, 2261, 2263  
`\char_make_active:N` . 46, 2225, 2238, 4990  
`\char_make_active:n` .... 46, 2241, 2254  
`\char_make_alignment:N` .. 46, 2225, 2229  
`\char_make_alignment:n` .. 46, 2241, 2245  
`\char_make_begin_group:N` . 46, 2225, 2226  
`\char_make_begin_group:n` . 46, 2241, 2242  
`\char_make_comment:N` .... 46, 2225, 2239  
`\char_make_comment:n` .... 46, 2241, 2255  
`\char_make_end_group:N` .. 46, 2225, 2227  
`\char_make_end_group:n` .. 46, 2241, 2243  
`\char_make_end_line:N` ... 46, 2225, 2230  
`\char_make_end_line:n` ... 46, 2241, 2246  
`\char_make_escape:N` .... 46, 2225, 2225  
`\char_make_escape:n` .... 46, 2241, 2241  
`\char_make_ignore:N` .....  
         46, 2225, 2234, 4980, 4985  
`\char_make_ignore:n` .... 46, 2241, 2250  
`\char_make_invalid:N` .... 46, 2225, 2240  
`\char_make_invalid:n` .... 46, 2241, 2256  
`\char_make_letter:N` .....  
         46, 2225, 2236, 4923, 4991  
`\char_make_letter:n` .... 46, 2241, 2252  
`\char_make_math_shift:N` . 46, 2225, 2228  
`\char_make_math_shift:n` . 46, 2241, 2244  
`\char_make_math_subscript:N` .....  
         46, 2225, 2233  
`\char_make_math_subscript:n` .....  
         46, 2241, 2249  
`\char_make_math_superscript:N` .....  
         46, 2225, 2232



<code>\char_make_math_superscript:n</code> . . . . .	<code>\chardef</code> . . . . . 69
. . . . . 46, 2241, 2248	<code>\chk_exist_cs:N</code> . . . . .
<code>\char_make_other:N</code> . . . . . 46, 2225, 2237	. . . . . 3509, 3513, 3516, 3519, 3532, 3536
<code>\char_make_other:n</code> . . . . . 46, 2241, 2253	<code>\chk_global:N</code> 3516, 3519, 3537, 4135, 4145
<code>\char_make_parameter:N</code> . . . . . 46, 2225, 2231	<code>\chk_if_exist_cs:c</code> . . . . . 11, 1130, 1137
<code>\char_make_parameter:n</code> . . . . . 46, 2241, 2247	<code>\chk_if_exist_cs:N</code> . . . . .
<code>\char_make_space:N</code> . . . . .	. . . . . 11, 1130, 1130, 1137, 1604
. . . . . 46, 2225, 2235, 4964, 4969	<code>\chk_if_free_cs:c</code> . . . . .
<code>\char_make_space:n</code> . . . . . 46, 2241, 2251	. . . . . 11, 1114, 1129, 4955, 4959, 5047
<code>\char_set_catcode:nn</code> . . . . .	<code>\chk_if_free_cs:N</code> 11, 1114, 1114, 1129,
. . . . . 45, 2211, 2212, 2225–	1167, 1239, 1250, 2739, 2936, 3286,
2256, 2309, 2311, 2315, 2320, 2405,	3360, 3402, 3462, 3481, 3489, 5305
2491–2495, 5465, 5553, 5554, 5566	<code>\chk_local:N</code> . . . . . 3513, 4118, 4140
<code>\char_set_catcode:w</code> . . . . . 45, 2211, 2211, 2213	<code>\chk_local_or_pref_global:N</code> . . . . .
<code>\char_set_lccode:nn</code> . . . . . 47, 2273, 2274,	. . . . . 2746, 2759, 2764,
2398–2403, 2490, 4988, 5555, 5556	2794, 2800, 3294, 3309, 3324, 3331,
<code>\char_set_lccode:w</code> . . . . .	3510, 3533, 3576, 3584, 3588, 3593,
. . . . . 47, 2273, 2273, 2275, 4989	3601, 3605, 3613, 3618, 3626, 3634,
<code>\char_set_mathcode:nn</code> . . . . . 48, 2257, 2258	3638, 3642, 4158, 4192, 4196, 4875
<code>\char_set_mathcode:w</code> 48, 2257, 2257, 2259	<code>\chk_var_or_const:N</code> . . . . . 3483, 3490,
<code>\char_set_sfcode:nn</code> . . . . . 47, 2293, 2294	3533, 3537, 3552, 3564, 4141, 4146
<code>\char_set_sfcode:w</code> . . . . . 47, 2293, 2293, 2295	<code>.choice:</code> . . . . . 124
<code>\char_set_uccode:nn</code> . . . . . 47, 2283, 2284	<code>.choice_code:n</code> . . . . . 124
<code>\char_set_uccode:w</code> . . . . . 47, 2283, 2283, 2285	<code>.choice_code:x</code> . . . . . 124
<code>\char_show_value_catcode:n</code> 45, 2211, 2222	<code>\cleaders</code> . . . . . 252
<code>\char_show_value_catcode:w</code> . . . . .	<code>\clearpage</code> . . . . . 5518, 5521, 5526, 5529
. . . . . 45, 2211, 2219, 2223	<code>\clist_clear:c</code> . . . . . 93, 4436
<code>\char_show_value_lccode:n</code> 47, 2273, 2281	<code>\clist_clear:N</code> . . . . .
<code>\char_show_value_lccode:w</code> . . . . .	93, 4436, 4436, 4437, 4607, 4629, 5071
. . . . . 47, 2273, 2280, 2282	<code>\clist_clear_new:c</code> . . . . . 93, 4440
<code>\char_show_value_mathcode:n</code> . . . . .	<code>\clist_clear_new:N</code> . . . . . 93, 4440, 4440, 4441
. . . . . 48, 2257, 2270	<code>\clist_concat:ccc</code> . . . . . 97, 4592
<code>\char_show_value_mathcode:w</code> . . . . .	<code>\clist_concat:NNN</code> . . . . . 97, 4592, 4601, 4603
. . . . . 48, 2257, 2269, 2271	<code>\clist_concat_aux:NNNN</code> . . . . .
<code>\char_show_value_sfcode:n</code> 47, 2293, 2302	. . . . . 4592, 4592, 4601, 4602
<code>\char_show_value_sfcode:w</code> . . . . .	<code>\clist_display:c</code> . . . . . 95, 4501
. . . . . 47, 2293, 2301, 2303	<code>\clist_display:N</code> . . . . . 95, 4501, 4501, 4515
<code>\char_show_value_uccode:n</code> 47, 2283, 2291	<code>\clist_gclear:c</code> . . . . . 93, 4436
<code>\char_show_value_uccode:w</code> . . . . .	<code>\clist_gclear:N</code> . . . . . 93, 4436, 4438, 4439
. . . . . 47, 2283, 2290, 2292	<code>\clist_gclear_new:c</code> . . . . . 93, 4440
<code>\char_value_catcode:n</code> . . . . . 45, 2211, 2216	<code>\clist_gclear_new:N</code> . . . . . 93, 4440, 4442, 4443
<code>\char_value_catcode:w</code> 45, 2211, 2215, 2217	<code>\clist_gconcat:ccc</code> . . . . . 97, 4592
<code>\char_value_lccode:n</code> . . . . . 47, 2273, 2278	<code>\clist_gconcat:NNN</code> . . . . . 97, 4592, 4602, 4604
<code>\char_value_lccode:w</code> 47, 2273, 2277, 2278	<code>\clist_get:cN</code> . . . . . 95, 4483, 4652
<code>\char_value_mathcode:n</code> . . . . . 48, 2257, 2266	<code>\clist_get:NN</code> . . . . . 95, 4483, 4483, 4488, 4651
<code>\char_value_mathcode:w</code> 48, 2257, 2265, 2267	<code>\clist_get_aux:w</code> . . . . . 99, 4483, 4485, 4487
<code>\char_value_sfcode:n</code> . . . . . 47, 2293, 2298	<code>\clist_gpop:cN</code> . . . . . 98, 4645
<code>\char_value_sfcode:w</code> 47, 2293, 2297, 2299	<code>\clist_gpop:NN</code> . . . . . 98, 4645, 4649, 4650
<code>\char_value_uccode:n</code> . . . . . 47, 2283, 2288	<code>\clist_gpush:cn</code> . . . . . 98, 4645
<code>\char_value_uccode:w</code> 47, 2283, 2287, 2288	<code>\clist_gpush:Nn</code> . . . . . 98, 4645, 4645, 4648

\clist\_gpush:No ..... 98, [4645](#), [4647](#)  
\clist\_gpush:Nv ..... 98, [4645](#), [4646](#)  
\clist\_gput\_left:cn ..... 94, [4525](#)  
\clist\_gput\_left:co ..... 94, [4525](#)  
\clist\_gput\_left:cV ..... 94, [4525](#)  
\clist\_gput\_left:Nn .....  
..... 94, [4525](#), [4525](#), [4528](#), [4645](#)  
\clist\_gput\_left:No ..... 94, [4525](#), [4647](#)  
\clist\_gput\_left:Nv ..... 94, [4525](#), [4646](#)  
\clist\_gput\_left:Nx ..... 94, [4525](#)  
\clist\_gput\_right:cn ..... 94, [4533](#)  
\clist\_gput\_right:co ..... 94, [4533](#)  
\clist\_gput\_right:cV ..... 94, [4533](#)  
\clist\_gput\_right:Nn 94, [4533](#), [4533](#), [4536](#)  
\clist\_gput\_right:No ..... 94, [4533](#)  
\clist\_gput\_right:Nv ..... 94, [4533](#)  
\clist\_gput\_right:Nx .....  
..... 94, [4533](#), [6726](#), [6733](#), [6737](#)  
\clist\_gremove\_duplicates:N .....  
..... 97, [4606](#), [4619](#)  
\clist\_gremove\_element:Nn 97, [4622](#), [4625](#)  
\clist\_gset\_eq:cc ..... 93, [4448](#), [4451](#)  
\clist\_gset\_eq:cN ..... 93, [4448](#), [4449](#)  
\clist\_gset\_eq:Nc ..... 93, [4448](#), [4450](#)  
\clist\_gset\_eq:NN 93, [4448](#), [4448](#), [4620](#), [4626](#)  
\clist\_if\_empty:c ..... [4453](#)  
\clist\_if\_empty:cTF ..... 96, [4452](#)  
\clist\_if\_empty:N ..... [4452](#)  
\clist\_if\_empty:Nf ..... [4538](#), [4557](#)  
\clist\_if\_empty:Ntf ..... 96, [4452](#), [4517](#)  
\clist\_if\_empty\_err:N .....  
..... 98, [4454](#), [4454](#), [4484](#), [4490](#)  
\clist\_if\_empty\_p:c ..... 96, [4452](#)  
\clist\_if\_empty\_p:N ..... 96, [4452](#)  
\clist\_if\_eq:cc ..... [4463](#)  
\clist\_if\_eq:ccTF ..... 97, [4460](#)  
\clist\_if\_eq:cN ..... [4461](#)  
\clist\_if\_eq:cNTF ..... 97, [4460](#)  
\clist\_if\_eq:Nc ..... [4462](#)  
\clist\_if\_eq:NcTF ..... 97, [4460](#)  
\clist\_if\_eq:NN ..... [4460](#)  
\clist\_if\_eq:NNTF ..... 97, [4460](#)  
\clist\_if\_eq\_p:cc ..... 96, [4460](#)  
\clist\_if\_eq\_p:cN ..... 96, [4460](#)  
\clist\_if\_eq\_p:Nc ..... 96, [4460](#)  
\clist\_if\_eq\_p:NN ..... 96, [4460](#)  
\clist\_if\_in:cnTF ..... 97, [4464](#)  
\clist\_if\_in:coTF ..... 97, [4464](#)  
\clist\_if\_in:cVTF ..... 97, [4464](#)  
\clist\_if\_in:Nn ..... [4464](#)  
\clist\_if\_in:NnF ..... [4473](#), [4612](#), [4973](#)  
\clist\_if\_in:NnT ..... [4472](#)  
\clist\_if\_in:NnTF .. 97, [4464](#), [4471](#), [5075](#)  
\clist\_if\_in:NoTF ..... 97, [4464](#)  
\clist\_if\_in:NvTF ..... 97, [4464](#)  
\clist\_map\_break: 96, [4554](#), [4554](#), [6666](#), [6700](#)  
\clist\_map\_function:cn ..... 95, [4537](#)  
\clist\_map\_function:NN 95, [4537](#), [4537](#),  
[4543](#), [4608](#), [4635](#), [6676](#), [6710](#), [6749](#)  
\clist\_map\_function:nN 95, [4537](#), [4544](#), [5774](#)  
\clist\_map\_function\_aux:Nw ... [4539](#),  
[4546](#), [4549](#), [4549](#), [4552](#), [4561](#), [4573](#)  
\clist\_map\_inline:cn ..... 95, [4555](#)  
\clist\_map\_inline:Nn .....  
..... 95, [4505](#), [4555](#), [4556](#), [4567](#)  
\clist\_map\_inline:nn ... 95, [4555](#), [4568](#)  
\clist\_map\_variable:cNn ..... 96, [4579](#)  
\clist\_map\_variable:NNn .....  
..... 96, [4579](#), [4585](#), [4586](#)  
\clist\_map\_variable:nNn .....  
..... 96, [4579](#), [4579](#), [4585](#)  
\clist\_map\_variable\_aux:Nnw .....  
..... [4581](#), [4587](#), [4587](#), [4590](#)  
\clist\_new:c ..... 92, [4434](#)  
\clist\_new:N ..... 92, [4434](#), [4434](#),  
[4435](#), [4605](#), [4935](#), [4938](#), [6645](#)–[6647](#)  
\clist\_pop:cn ..... 98, [4639](#)  
\clist\_pop:NN ..... 98, [4639](#), [4643](#), [4644](#)  
\clist\_pop\_aux:nnNN .....  
..... 98, [4489](#), [4489](#), [4643](#), [4649](#)  
\clist\_pop\_aux:w ... 99, [4489](#), [4491](#), [4493](#)  
\clist\_pop\_auxi:w .. 99, [4489](#), [4496](#), [4498](#)  
\clist\_push:cn ..... 98, [4639](#), [4642](#)  
\clist\_push:Nn ..... 98, [4639](#), [4639](#)  
\clist\_push:No ..... 98, [4639](#), [4641](#)  
\clist\_push:Nv ..... 98, [4639](#), [4640](#)  
\clist\_put\_aux:NNnnNn .....  
..... 99, [4516](#), [4516](#), [4522](#), [4526](#), [4530](#), [4534](#)  
\clist\_put\_left:cn ..... 93, [4521](#), [4642](#)  
\clist\_put\_left:co ..... 93, [4521](#)  
\clist\_put\_left:cV ..... 93, [4521](#)  
\clist\_put\_left:Nn .....  
..... 93, [4521](#), [4521](#), [4524](#), [4639](#)  
\clist\_put\_left:No ..... 93, [4521](#), [4641](#)  
\clist\_put\_left:Nv ..... 93, [4521](#), [4640](#)  
\clist\_put\_left:Nx ..... 93, [4521](#)  
\clist\_put\_right:cn ..... 94, [4529](#)  
\clist\_put\_right:co ..... 94, [4529](#)  
\clist\_put\_right:cV ..... 94, [4529](#)

- \clist\_put\_right:Nn ..... 94, 4529, 4529, 4532, 4613, 4632, 4974, 5078
- \clist\_put\_right:No ..... 94, 4529
- \clist\_put\_right:Nv . 94, 4529, 6759, 6760
- \clist\_put\_right:Nx ..... 94, 4529
- \clist\_remove\_duplicates:N ..... 97, 4606, 4616, 6747
- \clist\_remove\_duplicates\_aux:n ..... 4606, 4608, 4611
- \clist\_remove\_duplicates\_aux:NN ..... 4606, 4606, 4617, 4620
- \clist\_remove\_element:Nn . 97, 4622, 4622
- \clist\_remove\_element\_aux:n ..... 4622, 4630, 4635, 4638
- \clist\_remove\_element\_aux:NNn ..... 4622, 4623, 4626, 4628
- \clist\_set\_eq:cc ..... 93, 4444, 4447
- \clist\_set\_eq:cN ..... 93, 4444, 4445
- \clist\_set\_eq:Nc ..... 93, 4444, 4446
- \clist\_set\_eq:NN 93, 4444, 4444, 4617, 4623
- \clist\_show:c ..... 94, 4499, 4500
- \clist\_show:N ..... 94, 4499, 4499
- \clist\_tmp:w ..... 4465, 4469
- \clist\_top:cN ..... 98, 4651, 4652
- \clist\_top:NN ..... 98, 4651, 4651
- \clist\_use:c ..... 94, 4474
- \clist\_use:N ..... 94, 4474, 4474, 4482
- \closein ..... 128
- \closeout ..... 123
- \clubpenalties ..... 436
- \clubpenalty ..... 263
- .code:n ..... 124
- .code:x ..... 124
- \copy ..... 320
- \count ..... 371
- \countdef ..... 70
- \cr ..... 95
- \crrc ..... 96
- \cs:w ..... 11, 781, 784, 838, 872, 1059, 1346, 1385, 1467, 1518, 1531, 1532, 1534, 1536, 1538–1540, 1602, 1725, 1731, 1734, 2340, 2820, 3358, 3428, 3653, 5460
- \cs\_end: ..... 11, 781, 785, 838, 872, 1053, 1059, 1346, 1385, 1467, 1518, 1531, 1532, 1534, 1536, 1538, 1539, 1541, 1602, 1727, 1728, 1737–1739, 1741, 1743, 1745, 1747, 1749, 1751, 1753–1763, 2340, 2820, 3358, 3428, 3653, 5460
- \cs\_generate\_from\_arg\_count:cNnn 966, 971, 976, 981, 1331, 1384, 5787, 5792
- \cs\_generate\_from\_arg\_count:NNnn ... 1302, 1302, 1332, 1345
- \cs\_generate\_from\_arg\_count\_error\_msg:Nn ..... 1302, 1325, 1334
- \cs\_generate\_internal\_variant:n .... 27, 1624, 1639, 1639
- \cs\_generate\_internal\_variant\_aux:n ..... 1642, 1645, 1645, 1650
- \cs\_generate\_variant:Nn ... 27, 1603, 1603, 1860–1863, 1867, 1871, 1875, 1879, 1926, 1927, 2127, 2145, 2193–2200, 2743, 2755, 2756, 2783–2786, 2788, 2790, 2815–2818, 2998, 3024, 3025, 3080–3083, 3086, 3087, 3089, 3093, 3095, 3097, 3099, 3101, 3103, 3290, 3304, 3305, 3319, 3320, 3327, 3341, 3350, 3353, 3356, 3406, 3408, 3410, 3412, 3414, 3418, 3420, 3422, 3424, 3426, 3487, 3503, 3505, 3528, 3529, 3544, 3545, 3547, 3549, 3561, 3572, 3607–3609, 3644–3646, 3668–3671, 3675–3678, 3683–3690, 3697–3704, 3866, 3878, 3897, 3902, 3916, 3925, 3991–3993, 4000–4005, 4023, 4025, 4044, 4047, 4050, 4051, 4058, 4059, 4063, 4065, 4070, 4071, 4090–4093, 4114, 4116, 4119, 4134, 4137, 4154, 4155, 4165, 4166, 4175, 4176, 4178, 4183, 4189, 4203, 4217–4219, 4230–4233, 4238–4241, 4284, 4300–4302, 4310, 4336, 4344, 4347, 4366–4368, 4379, 4388, 4394, 4417, 4420, 4421, 4435, 4437, 4439, 4441, 4443, 4471–4473, 4482, 4488, 4515, 4524, 4528, 4532, 4536, 4543, 4567, 4586, 4603, 4604, 4644, 4648, 4650, 4696, 4707, 4711, 4740, 4741, 4753, 4754, 4772–4774, 4786, 4796, 4815, 4820, 4837, 4848, 4852, 5309, 5319–5326, 5330–5333, 5335, 5337, 5340, 5342, 5348, 5350, 5354–5356, 5358, 5360, 5362, 5370, 5372, 5376, 5378, 5391, 5393, 5396, 5398, 5402, 5404, 5408, 5413, 5418, 5420, 5802, 5934, 5996
- \cs\_generate\_variant\_aux:N ..... 1603, 1615, 1619, 1629, 1636, 1637
- \cs\_generate\_variant\_aux:nnNn ..... 1603, 1605, 1607

- \cs\_generate\_variant\_aux:nnw ..... 1603, 1608, 1610, 1634
- \cs\_get\_arg\_count\_from\_signature:c ..... 1299, 1386
- \cs\_get\_arg\_count\_from\_signature:N ..... 25, 903, 909, 916, 923, 1283, 1283, 1300, 1347, 5838
- \cs\_get\_arg\_count\_from\_signature\_aux:nnN ..... 1283, 1284, 1286
- \cs\_get\_arg\_count\_from\_signature\_auxii:w ..... 1283, 1293, 1298
- \cs\_get\_function\_name:N ..... 24, 1035, 1035
- \cs\_get\_function\_signature:N ..... 24, 1035, 1038
- \cs\_gnew:cn ..... 18, 1405
- \cs\_gnew:cpn ..... 17, 1198, 1204
- \cs\_gnew:cpx ..... 17, 1198, 1205
- \cs\_gnew:cx ..... 18, 1405
- \cs\_gnew:Nn ..... 18, 1366
- \cs\_gnew:Npn ..... 17, 1179, 1181, 1204, 5567, 5570, 5573, 5574, 5582
- \cs\_gnew:Npx ..... 17, 1179, 1182, 1205
- \cs\_gnew:Nx ..... 18, 1366
- \cs\_gnew\_eq:cc ..... 23, 1249, 1255
- \cs\_gnew\_eq:cN ..... 23, 1249, 1253
- \cs\_gnew\_eq:Nc ..... 23, 1249, 1254
- \cs\_gnew\_eq:NN ..... 23, 1249, 1249, 1253–1255, 2305
- \cs\_gnew\_nopar:cn ..... 18, 1405
- \cs\_gnew\_nopar:cpn ..... 17, 1187, 1196
- \cs\_gnew\_nopar:cpx ..... 17, 1187, 1197
- \cs\_gnew\_nopar:cx ..... 18, 1405
- \cs\_gnew\_nopar:Nn ..... 18, 1366
- \cs\_gnew\_nopar:Npn ..... 17, 1179, 1179, 1196
- \cs\_gnew\_nopar:Npx ..... 17, 1179, 1180, 1197
- \cs\_gnew\_nopar:Nx ..... 18, 1366
- \cs\_gnew\_protected:cn ..... 19, 1405
- \cs\_gnew\_protected:cpn ..... 17, 1214, 1220
- \cs\_gnew\_protected:cpx ..... 17, 1214, 1221
- \cs\_gnew\_protected:cx ..... 19, 1405
- \cs\_gnew\_protected:Nn ..... 19, 1366
- \cs\_gnew\_protected:Npn ..... 17, 1179, 1185, 1220
- \cs\_gnew\_protected:Npx ..... 17, 1179, 1186, 1221
- \cs\_gnew\_protected:Nx ..... 19, 1366
- \cs\_gnew\_protected\_nopar:cn ..... 19, 1405
- \cs\_gnew\_protected\_nopar:cpn ..... 18, 1206, 1212
- \cs\_gnew\_protected\_nopar:cpx ..... 18, 1206, 1213
- \cs\_gnew\_protected\_nopar:cx ..... 19, 1405
- \cs\_gnew\_protected\_nopar:Nn ..... 19, 1366
- \cs\_gnew\_protected\_nopar:Npn ..... 18, 1179, 1183, 1212
- \cs\_gnew\_protected\_nopar:Npx ..... 18, 1179, 1184, 1213
- \cs\_gnew\_protected\_nopar:Nx ..... 19, 1366
- \cs\_gset:cn ..... 21, 1389
- \cs\_gset:cpn ..... 20, 1198, 1200, 3881, 3890, 4559, 4571, 4790
- \cs\_gset:cpx ..... 20, 1198, 1201
- \cs\_gset:cx ..... 21, 1389
- \cs\_gset:Nn ..... 21, 1343
- \cs\_gset:Npn ..... 20, 818, 820, 1181, 1200, 1523
- \cs\_gset:Npx ..... 20, 818, 823, 1182, 1201
- \cs\_gset:Nx ..... 21, 1343
- \cs\_gset\_eq:cc ..... 23, 1245, 1248, 1854, 4280, 4451
- \cs\_gset\_eq:cN ..... 23, 1245, 1247, 1258, 1844, 1846, 1853, 4278, 4449
- \cs\_gset\_eq:Nc ..... 23, 1245, 1246, 1852, 4279, 4450
- \cs\_gset\_eq:NN ..... 23, 1245, 1245–1248, 1256, 1843, 1845, 1851, 3536, 3542, 4277, 4448
- \cs\_gset\_nopar:cn ..... 22, 1389
- \cs\_gset\_nopar:cpn ..... 20, 1187, 1192, 1791
- \cs\_gset\_nopar:cpx ..... 20, 1187, 1193
- \cs\_gset\_nopar:cx ..... 22, 1389
- \cs\_gset\_nopar:Nn ..... 22, 1343
- \cs\_gset\_nopar:Npn ..... 20, 818, 818, 821, 827, 833, 1179, 1192, 2321, 3485, 3516, 3525
- \cs\_gset\_nopar:Npx ..... 20, 818, 819, 824, 830, 836, 1180, 1193, 3491, 3519, 3526, 6445
- \cs\_gset\_nopar:Nx ..... 22, 1343
- \cs\_gset\_protected:cn ..... 22, 1389
- \cs\_gset\_protected:cpn ..... 20, 1214, 1216
- \cs\_gset\_protected:cpx ..... 20, 1214, 1217
- \cs\_gset\_protected:cx ..... 22, 1389
- \cs\_gset\_protected:Nn ..... 22, 1343
- \cs\_gset\_protected:Npn ..... 20, 818, 832, 1185, 1216
- \cs\_gset\_protected:Npx ..... 20, 818, 835, 1186, 1217
- \cs\_gset\_protected:Nx ..... 22, 1343
- \cs\_gset\_protected\_nopar:cn ..... 22, 1389
- \cs\_gset\_protected\_nopar:cpn ..... 21, 1206, 1208

\cs_gset_protected_nopar:cpx	.....	\cs_if_free:NT	.....	1090
.....	21, 1206, 1209	\cs_if_free:NTF	10, 1073, 1089, 1479, 4835	
\cs_gset_protected_nopar:cx	... 22, 1389	\cs_if_free_p:c	.....	10, 1073, 1088
\cs_gset_protected_nopar:Nn	... 22, 1343	\cs_if_free_p:N	.....	10, 1073, 1088
\cs_gset_protected_nopar:Npn	.....	\cs_meaning:c	.....	12, 781, 787
.....	21, 818, 826, 1183, 1208	\cs_meaning:N	.....	12, 781, 786, 787
\cs_gset_protected_nopar:Npx	.....	\cs_new:cn	.....	18, 1405
.....	21, 818, 829, 1184, 1209	\cs_new:cpn	.....	16, 1198, 1202, 1737–1740, 1742, 1744, 1746, 1748, 1750, 1752, 1754–1763, 5913, 5916
\cs_gset_protected_nopar:Nx	... 22, 1343	\cs_new:cpx	.....	16, 1198, 1203, 1641
\cs_gundefine:c	..... 22, 1256, 1257	\cs_new:cx	.....	18, 1405
\cs_gundefine:N	..... 22, 1256, 1256	\cs_new:Nn	.....	18, 1366
\cs_if_do_not_use_aux:nnN	1067, 1068, 1070	\cs_new:Npn	.....	16, 884, 908, 1165, 1173, 1202, 1453, 1456, 1459, 1460, 1463, 1466, 1469, 1472, 1480, 1486, 1491, 1499, 1526, 1527, 1529, 1532, 1533, 1535, 1537, 1540, 1589, 1590, 1593, 1596, 1599, 1602, 1603, 1639, 1645, 1652, 1653, 1657, 1660, 1664, 1676, 1682, 1764, 1770, 1779, 1789, 1799, 1807, 1815, 1821, 1829, 1864, 1868, 1872, 1876, 1922, 1923, 1928, 1929, 1937, 1940, 1943, 1946, 1949, 1953, 1959, 1963, 1969, 1973, 1979, 1983, 1989, 2116, 2122, 2128, 2137, 2146, 2571, 2579, 2582, 2585, 2594, 2597, 2627, 3108, 3109, 3480, 3488, 3508, 3512, 3515, 3518, 3523–3526, 3573, 3578, 3581, 3586, 3590, 3595, 3598, 3603, 3610, 3615, 3620, 3623, 3628, 3631, 3694, 3706, 3709, 3712, 3715, 3718, 3721, 3724, 3727, 3730, 3733, 3736, 3739, 3742, 3867, 3874, 3879, 3888, 3898, 3903, 3909, 3912, 3920, 3931, 3932, 3942, 3958, 3968, 3976, 4007, 4048, 4049, 4052, 4055, 4060, 4062, 4064, 4068, 4069, 4081, 4123, 4126, 4129, 4130, 4190, 4194, 4205, 4211, 4221, 4261, 4262, 4307, 4311, 4315, 4337, 4340, 4341, 4345, 4348, 4357, 4369, 4375, 4396, 4401, 4487, 4489, 4493, 4498, 4516, 4544, 4549, 4556, 4568, 4579, 4587, 4606, 4611, 4628, 4638, 4697, 4703, 4706, 4708, 4710, 4712, 4714, 4720, 4726, 4732, 4742, 4744, 4746, 4756, 4758, 4855, 4977, 4982, 5013, 5069, 5093, 5114, 5304, 5343–5346, 5369, 5373, 5385, 5386, 5395, 5399, 5415, 5416,
\cs_if_do_not_use_p:N	10, 1067, 1067, 1080			
\cs_if_eq:ccF	..... 1436			
\cs_if_eq:ccT	..... 1435			
\cs_if_eq:ccTF	..... 10, 1421, 1434			
\cs_if_eq:cNF	..... 1428			
\cs_if_eq:cNT	..... 1427			
\cs_if_eq:cNTF	..... 10, 1421, 1426			
\cs_if_eq:NcF	..... 1432			
\cs_if_eq:NcT	..... 1431			
\cs_if_eq:NcTF	..... 10, 1421, 1430			
\cs_if_eq:NN	..... 1421			
\cs_if_eq:NNF	..... 1428, 1432, 1436			
\cs_if_eq:NNT	..... 1427, 1431, 1435			
\cs_if_eq:NNTF	. 10, 1421, 1426, 1430, 1434			
\cs_if_eq_name:NN	..... 1147			
\cs_if_eq_name_p:NN	..... 10, 1147			
\cs_if_eq_p:cc	..... 10, 1421, 1433			
\cs_if_eq_p:cN	..... 10, 1421, 1425			
\cs_if_eq_p:Nc	..... 10, 1421, 1429			
\cs_if_eq_p:NN	. 10, 1421, 1425, 1429, 1433			
\cs_if_exist:c	..... 1052			
\cs_if_exist:cF	..... 3760			
\cs_if_exist:cT	..... 5977			
\cs_if_exist:cTF	.....			
.....	10, 1041, 2151, 2174, 5079, 5086, 5142, 5241, 5450, 5764, 5870			
\cs_if_exist:N	..... 1041			
\cs_if_exist:Nf	..... 1131, 5739, 5989			
\cs_if_exist:NT	..... 6671, 6705			
\cs_if_exist:NTF	10, 1041, 2390, 5828, 5863			
\cs_if_exist_p:c	..... 10, 1041			
\cs_if_exist_p:N	10, 1041, 1074, 3553, 3565			
\cs_if_free:cF	..... 1091			
\cs_if_free:cT	..... 1090, 1640			
\cs_if_free:cTF	.....			
.....	10, 1073, 1089, 1614, 5469, 6622			
\cs_if_free:N	..... 1073			
\cs_if_free:Nf	..... 1091, 1115			

- 5597, 5598, 5609, 5627, 5628, 5644,  
 5648, 5649, 5675, 5689, 5690, 5744,  
 5761, 5785, 5790, 5799, 5803, 5820,  
 5824, 5835, 5921, 5939, 5943, 5973,  
 5974, 6185, 6413, 6458, 6510, 6529,  
 6532, 6537, 6540, 6543, 6546, 6549,  
 6553, 6557, 6561, 6565, 6713, 6719  
 \cs\_new:Npx . . . . . 16, 1165, 1174, 1203  
 \cs\_new:Nx . . . . . 18, 1366  
 \cs\_new\_eq:cc . . . . . 23, 929, 1238, 1244  
 \cs\_new\_eq:cN . . . . . 23, 1238, 1242, 1838  
 \cs\_new\_eq:Nc . . . . . 23, 1238, 1243  
 \cs\_new\_eq:NN . . . . . 23, 1238,  
 1238, 1242–1244, 1261, 1263, 1270,  
 1272, 1478, 1837, 1847–1854, 2211,  
 2257, 2273, 2283, 2293, 2306, 2307,  
 2729–2731, 2819, 2821, 3074, 3075,  
 3096, 3098, 3104–3107, 3349, 3352,  
 3355, 3357, 3425, 3427, 3435, 3436,  
 3438, 3472, 3541, 3542, 3560, 3571,  
 3705, 3860–3862, 3908, 4061, 4066,  
 4067, 4115, 4122, 4136, 4151, 4152,  
 4177, 4263–4280, 4320, 4321, 4381,  
 4382, 4412–4415, 4418, 4422, 4423,  
 4434, 4436, 4438, 4440, 4442, 4444–  
 4451, 4499, 4500, 4554, 4639–4642,  
 4645–4647, 4651, 4652, 4664–4679,  
 4797, 4822–4825, 4869, 5310–5312,  
 5338, 5351–5353, 5357, 5359, 5364,  
 5381, 5384, 5390, 5392, 5409, 5414,  
 5417, 5419, 6552, 6556, 6560, 6564  
 \cs\_new\_nopar:cn . . . . . 18, 1405  
 \cs\_new\_nopar:cpn 17, 1187, 1194, 1903–1908  
 \cs\_new\_nopar:cpx 17, 1187, 1195, 1618, 2641  
 \cs\_new\_nopar:cx . . . . . 18, 1405  
 \cs\_new\_nopar:Nn . . . . . 18, 1366  
 \cs\_new\_nopar:Npn 17, 1165, 1171, 1188,  
 1194, 1242–1244, 1246–1248, 1253–  
 1257, 1282, 1425–1436, 1452, 1477,  
 1670–1673, 1679, 1711, 1713, 1714,  
 1724, 1730, 1733, 1736, 1837–1846,  
 1898, 1902, 1990, 2073, 2077, 2086,  
 2090, 2108, 2212, 2215, 2216, 2219,  
 2222, 2225–2256, 2258, 2262, 2265,  
 2266, 2269, 2270, 2274, 2277, 2278,  
 2280, 2281, 2284, 2287, 2288, 2290,  
 2291, 2294, 2297, 2298, 2301, 2302,  
 2305, 2382, 2412, 2419, 2430, 2441,  
 2452, 2463, 2470, 2477, 2484, 2498,  
 2501, 2507, 2513, 2539, 2563, 2564,  
 2569, 2604, 2611, 2618, 2635, 2640,  
 2709, 2712, 2734, 2735, 2738, 2744,  
 2749, 2757, 2762, 2767, 2773, 2787,  
 2789, 2791, 2797, 2803, 2809, 2820,  
 2822–2824, 2836, 2840, 2844, 2858,  
 2867, 2876, 2880, 2884, 2895, 2908,  
 2931, 2973, 2976, 2979, 2982, 3011,  
 3044, 3047, 3084, 3085, 3088, 3090,  
 3094, 3100, 3102, 3281, 3282, 3285,  
 3291, 3297, 3306, 3312, 3321, 3328,  
 3334, 3342, 3351, 3354, 3358, 3359,  
 3383, 3397, 3398, 3401, 3407, 3409,  
 3411, 3413, 3415, 3419, 3421, 3423,  
 3428, 3437, 3443, 3446, 3449, 3452,  
 3457, 3458, 3461, 3466–3471, 3493–  
 3495, 3504, 3531, 3535, 3546, 3548,  
 3551, 3563, 3647, 3653, 3863, 3865,  
 3870, 3901, 3917, 3926, 4022, 4024,  
 4042, 4045, 4110, 4111, 4118, 4135,  
 4139, 4144, 4156, 4160, 4167, 4170,  
 4179, 4184, 4198, 4281, 4287, 4303,  
 4322, 4383, 4389, 4406, 4409, 4416,  
 4419, 4454, 4474, 4483, 4501, 4521,  
 4525, 4529, 4533, 4537, 4585, 4592,  
 4601, 4602, 4616, 4619, 4622, 4625,  
 4643, 4649, 4680, 4769, 4788, 4810,  
 4816, 4821, 4826, 4827, 4831, 4833,  
 4834, 4838, 4841, 4844, 4849, 4853,  
 4854, 4861, 4865, 4873, 4877, 4939,  
 4942, 4947–4951, 4954, 4958, 4962,  
 4967, 4972, 5034, 5037, 5040, 5043,  
 5046, 5051, 5092, 5094, 5103, 5177,  
 5180, 5183, 5186, 5189, 5192, 5195,  
 5198, 5300, 5301, 5334, 5336, 5339,  
 5341, 5347, 5349, 5368, 5371, 5377,  
 5379, 5382, 5387, 5394, 5397, 5403,  
 5405, 5410, 5433–5435, 5449, 5468,  
 5558, 5561, 5691, 5695, 5699, 5728,  
 5747, 5752, 5776, 5795, 5816, 5850,  
 5855, 5861, 5876, 5881, 5885, 5890,  
 5898, 5901, 5912, 5915, 5918, 5935,  
 5958, 5970, 5984, 5988, 6170, 6171,  
 6200, 6203, 6206, 6209, 6212, 6215,  
 6218, 6221, 6224, 6227, 6230, 6233,  
 6236, 6239, 6242, 6245, 6248, 6251,  
 6254, 6258, 6262, 6266, 6270, 6274,  
 6278, 6291, 6296, 6297, 6301, 6305,  
 6324, 6340, 6356, 6362, 6363, 6365,  
 6374, 6383, 6391, 6400, 6409, 6411,  
 6473, 6474, 6520, 6522, 6524, 6567,

- 6621, 6660, 6684, 6685, 6695, 6712,  
6725, 6736, 6740, 6743, 6746, 6752
- \cs\_new\_nopar:Npx . . . 17, 1165, 1172, 1195
- \cs\_new\_nopar:Nx . . . . . 18, 1366
- \cs\_new\_protected:cn . . . . . 19, 1405
- \cs\_new\_protected:cpn . . . 17, 1214, 1218
- \cs\_new\_protected:cpx . . . . .
- 17, 1214, 1219, 5199, 5204, 5209, 5213
- \cs\_new\_protected:cx . . . . . 19, 1405
- \cs\_new\_protected:Nn . . . . . 19, 1366
- \cs\_new\_protected:Npn . . . 17, 896, 922,  
1165, 1177, 1218, 1238, 1245, 1249,  
4994, 5020, 5027, 5218, 5231, 6481
- \cs\_new\_protected:Npx 17, 1165, 1178, 1219
- \cs\_new\_protected:Nx . . . . . 19, 1366
- \cs\_new\_protected\_nopar:cn . . . . 19, 1405
- \cs\_new\_protected\_nopar:cpn . . . . .
- . . . . . 17, 1206, 1210
- \cs\_new\_protected\_nopar:cpx . . . . .
- . . . . . 17, 1206, 1211
- \cs\_new\_protected\_nopar:cx . . . . 19, 1405
- \cs\_new\_protected\_nopar:Nn . . . . 19, 1366
- \cs\_new\_protected\_nopar:Npn . . . . .
- . . . . . 17, 1165, 1175,  
1210, 2261, 5251, 5255, 5463, 6459
- \cs\_new\_protected\_nopar:Npx . . . . .
- . . . . . 17, 1165, 1176, 1211
- \cs\_new\_protected\_nopar:Nx . . . . 19, 1366
- \cs\_record\_meaning:N 15, 1111, 1112, 1123
- \cs\_set:cn . . . . . 21, 1389
- \cs\_set:cpn . . . . .
- . 19, 1198, 1198, 1891, 1894, 1897,  
1909, 1910, 3146, 3150, 3154, 3158,  
3162, 3166, 3170, 4978, 4983, 4984
- \cs\_set:cpx . . . . . 19, 1198,  
1199, 1991, 1995, 1999, 2003, 2007,  
2016, 2025, 2034, 2043, 2045, 2047,  
2049, 2051, 2053, 2055, 2057, 2059
- \cs\_set:cx . . . . . 21, 1389
- \cs\_set:Nn . . . . . 21, 1343
- \cs\_set:Npn . . . . . 19, 798, 800,  
838–875, 878, 881, 887, 893, 899,  
902, 905, 912, 919, 925, 928, 931–  
933, 938, 945, 950, 955, 960, 965,  
970, 975, 980, 985, 988, 999–1002,  
1012, 1018, 1022, 1031, 1035, 1038,  
1067, 1070, 1112, 1162, 1165, 1173,  
1187, 1198, 1283, 1286, 1298, 1302,  
1334, 1343, 1382, 1531, 1607, 1610,  
1636, 1880, 1884, 1911, 1914, 1919,  
2066, 2067, 3129, 3136, 3140, 3179,  
3186, 3196, 3206, 3209, 3233, 3234,  
3248, 3251, 3254, 3257, 3260, 3263,  
3266, 3269, 3636, 3640, 3952, 3986,  
3995, 4008, 4012, 4026, 4028, 4294,  
4384, 4390, 4465, 4630, 4698, 4779,  
5001, 5022, 5029, 5074, 5616, 5788
- \cs\_set:Npx . 19, 798, 803, 1174, 1199, 5793
- \cs\_set:Nx . . . . . 21, 1343
- \cs\_set\_eq:cc . . . . .
- 23, 926, 1234, 1237, 1850, 4276, 4447
- \cs\_set\_eq:cn . . . . 23, 1234, 1235, 1840,  
1842, 1849, 4274, 4445, 4979, 5919
- \cs\_set\_eq:Nc . . . . .
- . 23, 1234, 1236, 1848, 4275, 4446,  
5811, 5813, 5826, 5862, 5929, 5931
- \cs\_set\_eq:NN 23, 1234, 1234–1237, 1240,  
1245, 1251, 1839, 1841, 1847, 2572,  
2586, 2602, 2643, 2715, 3123, 3124,  
3126–3128, 3374, 3375, 3506, 3532,  
3541, 4113, 4273, 4386, 4392, 4444,  
4813, 4847, 4863, 4864, 4996, 4997,  
5023, 5030, 5361, 5363, 5511, 5692,  
5696, 5700, 5805, 5806, 5923, 5924,  
6186, 6187, 6190, 6191, 6306–6312,  
6314, 6326, 6329, 6332, 6342, 6345,  
6348, 6386, 6387, 6420–6422, 6427–  
6430, 6535, 6536, 6568–6573, 6612,  
6624–6626, 6630–6632, 6672, 6706
- \cs\_set\_eq:NwN . . . . .
- . . . . . 23, 753, 759–786, 788, 791–  
799, 818, 819, 1093, 1234, 1448–1450
- \cs\_set\_nopar:cn . . . . . 21, 1389
- \cs\_set\_nopar:cpn 20, 1187, 1190, 1222–  
1230, 1232, 2825, 2826, 5442, 6634
- \cs\_set\_nopar:cpx . . . . . 20, 1187, 1191
- \cs\_set\_nopar:cx . . . . . 21, 1389
- \cs\_set\_nopar:Nn . . . . . 21, 1343
- \cs\_set\_nopar:Npn . . . . . 20, 742, 798,  
798, 800, 801, 803, 806, 807, 809,  
813, 1005, 1088–1091, 1101, 1104,  
1107, 1114, 1129, 1130, 1137, 1141,  
1158, 1171, 1190, 1235–1237, 1299,  
1331, 1507, 1517, 1542–1549, 1551–  
1558, 1560–1562, 1564, 1566–1568,  
1570–1573, 1575–1578, 1580–1585,  
1587, 1588, 1824, 1832, 2779–2782,  
2848, 2926, 2928, 2999, 3026, 3038,  
3055, 3076–3079, 3509, 3523, 3745,  
4588, 4717, 4736, 4747, 4749, 4775,



- 4830, 4832, 4999, 5070, 5458, 5474,  
 5492, 5493, 5502, 5503, 5506, 5509,  
 6334, 6350, 6417, 6423, 6662, 6696  
 \cs\_set\_nopar:Npx 20, [798](#), 799, 804, 810,  
 816, 1172, 1191, 1481, 3513, 3524, 5475  
 \cs\_set\_nopar:Nx ..... [21](#), [1343](#)  
 \cs\_set\_protected:cn ..... [22](#), [1389](#)  
 \cs\_set\_protected:cpn 20, [1214](#), 1214, 5053  
 \cs\_set\_protected:cpx 20, [1214](#), 1215,  
 1344, 1383, 5056, 5059, 5062, 5065  
 \cs\_set\_protected:cx ..... [22](#), [1389](#)  
 \cs\_set\_protected:Nn ..... [22](#), [1343](#)  
 \cs\_set\_protected:Npn ..... 20, [798](#),  
 812, 890, 915, 1177, 1214, 1234,  
 3125, 5283, 5462, 6418, 6436, 6475  
 \cs\_set\_protected:Npx .....  
 ..... 20, [798](#), 815, 1178, 1215  
 \cs\_set\_protected:Nx ..... [22](#), [1343](#)  
 \cs\_set\_protected\_nopar:cn .... [22](#), [1389](#)  
 \cs\_set\_protected\_nopar:cpn .....  
 ..... [21](#), [1206](#), 1206, 5439  
 \cs\_set\_protected\_nopar:cpx .....  
 ..... [21](#), [1206](#), 1207  
 \cs\_set\_protected\_nopar:cx .... [22](#), [1389](#)  
 \cs\_set\_protected\_nopar:Nn .... [22](#), [1343](#)  
 \cs\_set\_protected\_nopar:Npn .....  
 ..... [21](#), [798](#), 806, 812, 815, 820,  
 823, 826, 829, 832, 835, 1166, 1175,  
 1206, 6574–6577, 6583, 6588, 6603  
 \cs\_set\_protected\_nopar:Npx .....  
 ..... [21](#), [798](#), 809, 1176, 1207  
 \cs\_set\_protected\_nopar:Nx .... [22](#), [1343](#)  
 \cs\_show:c ..... [12](#), [781](#), 789, 3107, 5971  
 \cs\_show:N .. [12](#), [781](#), 788, 789, 3106, 3504  
 \cs\_split\_function:NN .....  
 ..... [24](#), 877, 883, 889, 895,  
 901, 907, 914, 921, 993, 995, [1013](#),  
 1018, 1036, 1039, 1068, 1284, 1605  
 \cs\_split\_function\_aux:w [1013](#), 1019, 1022  
 \cs\_split\_function\_auxii:w .....  
 ..... [1013](#), 1029, 1031  
 \cs\_str\_aux:w ..... 1006, 1012  
 \cs\_tmp:w .... 1165, 1171–1187, 1190–  
 1221, 1343, 1350–1382, 1389–1420  
 \cs\_to\_str:N ..... 4,  
 24, [1005](#), 1005, 1020, 2075, 4855–4858  
 \cs\_to\_str\_aux:w ..... [1005](#)  
 \csname ..... 11, 158  
 \currentgrouplevel ..... 410  
 \currentgrouptype ..... 411  
 \currentifbranch ..... 407  
 \currentiflevel ..... 406  
 \currentifttype ..... 408  
 D  
 \d ..... 2402  
 \dagger ..... 2898, 2904  
 \day ..... 366  
 \ddagger ..... 2899, 2905  
 \deadcycles ..... 300  
 \DeclareOption ..... 48, 51  
 \def ..... 3–6, 24, 43, 49, 52, 57, 65  
 \def\_long\_test\_function\_new:npn .. 4088  
 .default:n ..... 124  
 .default:V ..... 124  
 \default@ds ..... 712  
 \defaultthyphenchar ..... 350  
 \defaultskewchar ..... 351  
 \DefineCrossReferences ..... 5493, 5499  
 \delcode ..... 381  
 \delimiter ..... 175  
 \delimiterfactor ..... 224  
 \delimitershortfall ..... 223  
 \depthof ..... 132, 6568, 6568  
 \detokenize ..... 398  
 \dim\_add:cn ..... 68, [3415](#)  
 \dim\_add:Nc ..... 68, [3415](#)  
 \dim\_add:Nn 68, [3415](#), 3415, 3418, 3419, 6225  
 \dim\_compare:nNn ..... 3439  
 \dim\_compare:nNnF ..... 3447, 3453  
 \dim\_compare:nNnT ..... 3444, 3450  
 \dim\_compare:nNnTF ..... 70, 1965, [3439](#)  
 \dim\_compare\_p:nNn ..... 70, [3439](#)  
 \dim\_do\_until:nNnn .. 70, [3443](#), 3452, 3453  
 \dim\_do\_while:nNnn .. 70, [3443](#), 3449, 3450  
 \dim\_eval:n ..... 69,  
 1960, 3407, 3416, [3437](#), 3437, 3440,  
 5343–5346, 5385, 5400, 6468, 6469  
 \dim\_gadd:cn ..... 68, [3415](#)  
 \dim\_gadd:Nn ... 68, [3415](#), 3419, 3420, 6228  
 .dim\_gset:c ..... 125  
 \dim\_gset:cc ..... 68, [3407](#)  
 \dim\_gset:cn ..... 68, [3407](#)  
 .dim\_gset:N ..... 125  
 \dim\_gset:Nc ..... 68, [3407](#)  
 \dim\_gset:Nn 68, [3407](#), 3409, 3410, 6222, 6425  
 \dim\_gsub:cn ..... 69, [3421](#)  
 \dim\_gsub:Nn ... 69, [3421](#), 3423, 3424, 6234  
 \dim\_gzero:c ..... 68, [3411](#)  
 \dim\_gzero:N ..... 68, [3411](#), 3413, 3414



<code>\dim_new:c</code> .....	68, <a href="#">3395</a>	2167, 2172, 2179, 2189, 2325, 2329,
<code>\dim_new:N</code> .....	68, <a href="#">3395</a> , 3397,	2333, 2337, 2341, 2345, 2349, 2353,
	<a href="#">3401</a> , <a href="#">3406</a> , <a href="#">3429–3434</a> , 6176–6178	2357, 2361, 2365, 2369, 2373, 2377,
<code>\dim_new_l:N</code> .....	3398	2384, 2388, 2392, 2425, 2436, 2447,
<code>.dim_set:c</code> .....	<a href="#">125</a>	2458, 2524, 2527, 2531, 2534, 2541,
<code>\dim_set:cn</code> .....	68, <a href="#">3407</a>	2543, 2545, 2547, 2549, 2551, 2607,
<code>.dim_set:N</code> .....	<a href="#">125</a>	2614, 2630, 3036, 3138, 3148, 3152,
<code>\dim_set:Nc</code> .....	68, <a href="#">3407</a>	3156, 3160, 3164, 3168, 3172, 3177,
<code>\dim_set:Nn</code> ....	68, <a href="#">3407</a> , 3407–3409, 6219	3191, 3201, 3213, 3218, 3221, 3224,
<code>\dim_show:c</code> .....	69, <a href="#">3427</a> , 3428	3242, 3246, 3441, 3499, 3555, 3567,
<code>\dim_show:N</code> .....	69, <a href="#">3427</a> , 3427, 3428	3666, 3673, 3681, 3695, 3751, 3765,
<code>\dim_sub:cn</code> .....	69, <a href="#">3421</a>	3772, 3779, 3786, 3793, 3800, 3807,
<code>\dim_sub:Nc</code> .....	69, <a href="#">3421</a>	3814, 3821, 3828, 3835, 3842, 3849,
<code>\dim_sub:Nn</code> ....	69, <a href="#">3421</a> , 3421–3423, 6231	3856, 4074, 4079, 4084, 4097, 4296,
<code>\dim_until_do:nNnn</code> ..	70, <a href="#">3443</a> , 3446, 3447	4467, 4478, 4871, 5314, 5317, 5328,
<code>\dim_use:c</code> .....	69, <a href="#">3425</a>	6281, 6283, 6285, 6306–6311, 6313,
<code>\dim_use:N</code> ....	69, 1960, <a href="#">3425</a> , 3425, 3426	6327, 6330, 6333, 6343, 6346, 6349,
<code>\dim_while_do:nNnn</code> ..	70, <a href="#">3443</a> , 3443, 3444	6441, 6488, 6494, 6500, 6501, 6506
<code>\dim_zero:c</code> .....	68, <a href="#">3411</a>	<code>\emergencystretch</code> .....
<code>\dim_zero:N</code> .....	68, <a href="#">3411</a> , 3411–3413	<code>\end</code> .....
<code>\dimen</code> .....	372	<code>\endcsname</code> .....
<code>\dimendef</code> .....	71	<code>\endgroup</code> .....
<code>\dimexpr</code> .....	425	<code>\endinput</code> .....
<code>\directlua</code> .....	554	<code>\endL</code> .....
<code>\discretionary</code> .....	235	<code>\endlinechar</code> .....
<code>\displayindent</code> .....	200	<code>\endR</code> .....
<code>\displaylimits</code> .....	210	<code>\eqno</code> .....
<code>\displaystyle</code> .....	188	<code>\errhelp</code> .....
<code>\displaywidowpenalties</code> .....	438	<code>\errmessage</code> .....
<code>\displaywidowpenalty</code> .....	199	<code>\erroneous</code> .....
<code>\displaywidth</code> .....	201	<code>\ERROR</code> ...
<code>\divide</code> .....	78	4392, 5627, 5641, 5686, 5689, 5690
<code>\documentclass</code> .....	5489	<code>\errorcontextlines</code> .....
<code>\doublehyphendemerits</code> .....	268	<code>\errorstopmode</code> .....
<code>\dp</code> .....	379	<code>\escapechar</code> .....
<code>\ds@</code> .....	713	<code>\etex_beginL:D</code> .....
<code>\dump</code> .....	362	<code>\etex_beginR:D</code> .....
<b>E</b>		<code>\etex_botmarks:D</code> .....
<code>\E</code> .....	2404	<code>\etex_clubpenalties:D</code> .....
<code>\edef</code> .....	22, 66	<code>\etex_currentgrouplevel:D</code> .....
<code>\efcode</code> .....	463	<code>\etex_currentgrouptype:D</code> .....
<code>\else</code> .....	12, 119	<code>\etex_currentifbranch:D</code> .....
<code>\else:</code> ....	8, 746, <a href="#">760</a> , 763, 860, 947,	<code>\etex_currentiflevel:D</code> .....
	952, 957, 967, 972, 977, 1007, 1025,	<code>\etex_currentiftype:D</code> .....
	1044, 1047, 1055, 1061, 1076, 1082,	<code>\etex_detokenize:D</code> .....
	1143, 1144, 1146, 1163, 1262, 1267,	<code>\etex_dimexpr:D</code> .....
	1271, 1276, 1280, 1289, 1323, 1423,	6369, 6378, 6395, 6404, 6452, 6464
	1512, 1697, 1701, 1705, 1709, 1858,	<code>\etex_displaywidowpenalties:D</code> ....
	1887, 1935, 2132, 2140, 2149, 2157,	<code>\etex_endL:D</code> .....
		<code>\etex_endR:D</code> .....

<code>\etex_eTeXrevision:D</code> .....	390	<code>\etex_tracingifs:D</code> .....	405		
<code>\etex_eTeXversion:D</code> .....	389	<code>\etex_tracingnesting:D</code> .....	404		
<code>\etex_everyeof:D</code> 450, 3944, 3960, 3970, 3978		<code>\etex_tracingscantokens:D</code> .....	403		
<code>\etex_firstmarks:D</code> .....	393	<code>\etex_unexpanded:D</code> .....			
<code>\etex_fontchardp:D</code> .....	418	... 397, 564, 665, 669, 672, 780, 1450			
<code>\etex_fontcharht:D</code> .....	417	<code>\etex_unless:D</code> .....	388, 765		
<code>\etex_fontcharic:D</code> .....	420	<code>\etex_widowpenalties:D</code> .....	437		
<code>\etex_fontcharwd:D</code> .....	419	<code>\etexmissingerror</code> .....	5, 15, 16		
<code>\etex_glueexpr:D</code> .....	426, 3359, 6370, 6379, 6396, 6405, 6453, 6465	<code>\etexmissinghelp</code> .....	6, 14, 16		
<code>\etex_glueshrink:D</code> .....	429, 3392	<code>\eTeXrevision</code> .....	390		
<code>\etex_glueshrinkorder:D</code> .....	431, 3380	<code>\eTeXversion</code> .....	389		
<code>\etex_gluestretch:D</code> .....	428, 3391	<code>\everycr</code> .....	101		
<code>\etex_gluestretchorder:D</code> .....	430, 3379	<code>\everydisplay</code> .....	202		
<code>\etex_gluetomu:D</code> .....	432	<code>\everyeof</code> .....	450		
<code>\etex_ifcsname:D</code> .....	387, 777	<code>\everyhbox</code> .....	341		
<code>\etex_ifdefined:D</code> .... 386, 555, 556, 776		<code>\everyjob</code> .....	370		
<code>\etex_iffontchar:D</code> .....	416	<code>\everymath</code> .....	226		
<code>\etex_interactionmode:D</code> .....	414	<code>\everypar</code> .....	289		
<code>\etex_interlinepenalties:D</code> .....	435	<code>\everyvbox</code> .....	342		
<code>\etex_lastlinefit:D</code> .....	434	<code>\ExecuteOptions</code> .....	53		
<code>\etex_lastnodetype:D</code> .... 415, 1717, 1719		<code>\exhyphenpenalty</code> .....	265		
<code>\etex_marks:D</code> .....	391	<code>\exp_after:cc</code> .....	5458		
<code>\etex_middle:D</code> .....	439	<code>\exp_after:wN</code> .....	14, 181, 778, 778, 872–874, 940, 947, 952, 957, 962, 967, 972, 977, 982, 990, 1006, 1008, 1010, 1019, 1024, 1026, 1054, 1056, 1059, 1071, 1075, 1077, 1148–1153, 1159, 1288, 1290, 1293, 1346, 1385, 1447, 1448, 1467, 1470, 1473, 1474, 1482, 1487, 1488, 1492, 1493, 1500, 1501, 1508, 1513, 1515, 1518, 1526–1533, 1535–1538, 1540, 1541, 1589, 1591, 1594, 1597, 1600, 1602, 1612, 1637, 1648, 1654, 1655, 1658, 1661, 1662, 1665, 1666, 1677, 1683, 1726, 1892, 1895, 1897, 1899, 2087, 2117, 2119, 2124, 2129, 2131, 2133, 2139, 2141, 2340, 2380, 2391, 2409, 2416, 2426, 2437, 2448, 2459, 2467, 2474, 2481, 2503, 2509, 2515, 2606, 2608, 2613, 2615, 2625, 2629, 2631, 2837, 2841, 3028–3036, 3133, 3137, 3500, 3680, 3692, 3719, 3725, 3731, 3737, 3743, 3863, 3871, 3872, 3947, 3952–3955, 3981, 3989, 4019, 4038, 4073, 4077, 4082, 4095, 4124, 4127, 4129, 4131, 4180, 4191, 4195, 4206, 4207, 4212, 4213, 4222, 4223, 4298, 4305, 4313, 4338, 4377, 4479, 4485, 4491, 4539, 4540, 4701,		
<code>\etex_muexpr:D</code> . 427, 3466, 3468, 3470, 6371, 6380, 6397, 6406, 6454, 6466					
<code>\etex_mutoglue:D</code> .....	433, 6442, 6443				
<code>\etex_numexpr:D</code> 424, 1303, 1337, 3124, 6368, 6377, 6394, 6403, 6451, 6463					
<code>\etex_pagediscards:D</code> .....	442				
<code>\etex_parshapedimen:D</code> .....	423				
<code>\etex_parshapeindent:D</code> .....	421				
<code>\etex_parshapelength:D</code> .....	422				
<code>\etex_predisplaydirection:D</code> .....	449				
<code>\etex_protected:D</code> .....	451, 797				
<code>\etex_readline:D</code> .....	401				
<code>\etex_savinghyphcodes:D</code> .....	440				
<code>\etex_savingvdiscards:D</code> .....	441				
<code>\etex_scantokens:D</code> .....	399, 3947, 3963, 3973, 3981				
<code>\etex_showgroups:D</code> .....	412				
<code>\etex_showifs:D</code> .....	413				
<code>\etex_showtokens:D</code> .....	400, 3506				
<code>\etex_splitbotmarks:D</code> .....	396				
<code>\etex_splitdiscards:D</code> .....	443				
<code>\etex_splitfirstmarks:D</code> .....	395				
<code>\etex_TeXETstate:D</code> .....	444				
<code>\etex_topmarks:D</code> .....	392				
<code>\etex_tracingassigns:D</code> .....	402				
<code>\etex_tracinggroups:D</code> .....	409				

- 4776, 4777, 4781, 5452, 5459, 5460,  
 5579, 5591, 5634, 5635, 5652, 5653,  
 5663, 5668, 5883, 6193, 6195, 6280  
 \exp\_arg:x . . . . 29, 1478, 1478, 1479, 1488  
 \exp\_arg\_last\_unbraced:nn . . . . .  
 . . 1652, 1652, 1654, 1658, 1661, 1665  
 \exp\_arg\_next:nnn . . . . . 1453, 1453,  
 1470, 1473, 1482, 1487, 1492, 1500  
 \exp\_arg\_next\_nobrace:nnn 1453, 1456, 1467  
 \exp\_args:cc . . . . . 29, 1531, 1532  
 \exp\_args:Nc 29, 787, 789, 790, 872, 872,  
 946, 951, 956, 961, 1088–1091, 1129,  
 1137, 1188, 1235, 1242, 1247, 1253,  
 1300, 1332, 1425–1428, 1531, 1531,  
 2822, 3883, 4573, 5838, 6585, 6595  
 \exp\_args:Ncc . . . . . 31, 1237, 1244,  
 1248, 1255, 1433–1436, 1531, 1535  
 \exp\_args:Nccc . . . . . 32, 1531, 1537  
 \exp\_args:Ncco . . . . . 32, 1568, 1582, 1583  
 \exp\_args:Nccx . . . . . 31, 1568, 1584  
 \exp\_args:Ncf . . 31, 1546, 1554, 1793, 1794  
 \exp\_args:NcNc . . . . . 32, 1568, 1580, 5452  
 \exp\_args:NcNo . . . . . 32, 1568, 1581  
 \exp\_args:Ncnx . . . . . 31, 1568, 1585  
 \exp\_args:Nco . . . . . 31, 1540, 1540, 1546  
 \exp\_args:Ncx . . . . . 30, 1546, 1551  
 \exp\_args:Nf . . . . .  
 . 30, 1542, 1542, 1766, 1767, 1774,  
 1783, 1817, 1818, 1825, 1833, 1950,  
 2851, 2854, 2856, 2927, 3041, 3050  
 \exp\_args:Nff . . . . . 31, 1546, 1553, 2929  
 \exp\_args:Nfo . . . . . 31, 1546, 1552  
 \exp\_args:NNc 31, 993, 995, 1236, 1243,  
 1246, 1254, 1429–1432, 1531, 1533  
 \exp\_args:NNf . . 31, 1546, 1546, 1803, 1811  
 \exp\_args:Nnf . . . . .  
 . . . 31, 900, 906, 913, 920, 1546, 1555  
 \exp\_args:Nnnc . . . . . 32, 1568, 1575  
 \exp\_args:NNNo . . . . . 32, 1526, 1529  
 \exp\_args:NNno . . . . . 32, 1568, 1570  
 \exp\_args:Nnno . . . . . 32, 1568, 1576  
 \exp\_args:NNNV . 32, 1568, 1568, 3948, 3964  
 \exp\_args:NNnx . . . . . 31, 1568, 1571  
 \exp\_args:Nnnx . . . . . 31, 1568, 1577  
 \exp\_args:NNo . . . . .  
 . . . . 31, 1526, 1527, 2163, 2185, 5590  
 \exp\_args:Nno . . . . . 31, 1546, 1556  
 \exp\_args:NNoo . . . . . 32, 1568, 1572  
 \exp\_args:NNox . . . . . 31, 1568, 1573  
 \exp\_args:Nnox . . . . . 31, 1568, 1578  
 \exp\_args:NNV . . . . . 31, 1546, 1548  
 \exp\_args:NNv . . . . . 31, 1546, 1547  
 \exp\_args:NnV . . . . . 31, 1546, 1557  
 \exp\_args:NNx . . . . . 30, 1546, 1549, 5476  
 \exp\_args:Nnx . . . . . 30, 1546, 1558  
 \exp\_args:No . . . . .  
 29, 1526, 1526, 1960, 3901, 4585, 6424  
 \exp\_args:Noc . . . . . 31, 1546, 1560  
 \exp\_args:Noo . . . . . 31, 1546, 1561  
 \exp\_args:Nooo . . . . . 32, 1568, 1588  
 \exp\_args:Noox . . . . . 31, 1568, 1587  
 \exp\_args:Nox . . . . . 30, 1546, 1562  
 \exp\_args:NV . . . 29, 1542, 1544, 3982, 5864  
 \exp\_args:Nv . . . . . 30, 1542, 1543  
 \exp\_args:NVV . . . . . 31, 1546, 1564  
 \exp\_args:Nx . . . . . 30, 1542, 1545  
 \exp\_args:Nxo . . . . . 30, 1546, 1566  
 \exp\_args:Nxx . . . . . 30, 1546, 1567  
 \exp\_eval\_error\_msg:w 182, 1507, 1510, 1523  
 \exp\_eval\_register:c . . . . .  
 181, 1503, 1507, 1517, 1597, 1667, 4127  
 \exp\_eval\_register:N 181, 1495, 1507,  
 1507, 1518, 1600, 1662, 4124, 4208  
 \exp\_last\_unbraced:NcV . . . . .  
 . . . . . 33, 1670, 1673, 3892, 4561  
 \exp\_last\_unbraced:Nf 33, 1670, 1670, 2074  
 \exp\_last\_unbraced:NNNo . 33, 1670, 1682  
 \exp\_last\_unbraced:NNo . . . . .  
 . . . . 33, 1670, 1676, 4469, 5585, 5882  
 \exp\_last\_unbraced:NNV . . . . .  
 . . . . . 33, 1670, 1679, 4168, 5604  
 \exp\_last\_unbraced:NV . . . . .  
 . . . . . 33, 1670, 1671, 5606, 5613  
 \exp\_last\_unbraced:Nv . . . 33, 1670, 1672  
 \exp\_not:c . . . . . 32, 1602, 1602, 1622,  
 1646, 1992, 1996, 2001, 2005, 2008,  
 2010–2012, 2017, 2019–2021, 2026,  
 2028–2030, 2035, 2037–2039, 2044,  
 2046, 2048, 2050, 2052, 2054, 2056,  
 2058, 2060–2062, 2645, 3747, 3750,  
 5057, 5060, 5063, 5066, 5201, 5206,  
 5211, 5215, 5438, 5444, 5730, 5993  
 \exp\_not:d . . . . . 32, 1589, 1590  
 \exp\_not:f . . . . . 32, 1589, 1593  
 \exp\_not:N . . . 15, 32, 778, 779, 1345–  
 1347, 1384–1386, 1447, 1449, 1508,  
 1602, 1997, 2000, 2004, 2008, 2017,  
 2026, 2035, 2155, 2177, 2321, 2324,  
 2328, 2332, 2336, 2340, 2344, 2348,  
 2352, 2356, 2360, 2364, 2372, 2376,

- 2391, 2612, 2628, 3747, 3749, 3960,  
3970, 4077, 4078, 4082, 4095, 4096,  
5443, 5445, 5568, 5576, 5586, 5731,  
5734, 5736, 5887, 5993, 6538, 6541,  
6544, 6547, 6550, 6554, 6558, 6562
- \exp\_not:n .....  
15, 32, 778, 780, 1447, 1450, 1589,  
1591, 1594, 1597, 1600, 1993, 2156,  
2178, 2574, 2575, 2588, 2590, 2643,  
2646, 3707, 3710, 3713, 3716, 3719,  
3722, 3725, 3731, 3737, 3743, 3751,  
3762, 3763, 3769, 3776, 3783, 3791,  
3798, 3833, 4331, 4370, 4376, 4510,  
4689, 4691, 4706, 4710, 4715, 4828,  
4850, 5442, 5601, 5630, 5778, 5779,  
6007, 6530, 6533, 6538, 6541, 6544,  
6547, 6550, 6554, 6558, 6562, 6566
- \exp\_not:o ..... 32, 1589, 1589, 3777,  
3797, 3811, 3812, 3825, 3847, 5650
- \exp\_not:V ..... 32, 1589,  
1599, 3575, 3579, 3583, 3587, 3592,  
3596, 3600, 3604, 3612, 3617, 3621,  
3625, 3629, 3633, 3637, 3641, 3716,  
3722, 3728, 3734, 3740, 3770, 3790,  
3804, 3805, 3818, 3840, 4282, 5781
- \exp\_not:v ..... 32, 1589, 1596
- \exp\_stop\_f: 32, 1472, 1477, 1515, 2075, 3918
- \expandafter ..... 11, 12, 14, 15, 89
- \expanded ..... 1478
- \ExplSyntaxNamesOff ..... 6, 586, 590
- \ExplSyntaxNamesOn .... 6, 586, 586, 5495
- \ExplSyntaxOff ..... 4, 6, 22,  
560, 563, 667, 674, 685, 702, 710, 5513
- \ExplSyntaxOn ..... 4, 6,  
560, 560, 654, 658, 662, 683, 724, 5491
- \ExplSyntaxPopStack ... 136, 676, 680, 680
- \ExplSyntaxStack .....  
.... 136, 666, 673, 676, 680, 681, 688
- \ExplSyntaxStatus ..... 23, 24,  
136, 560, 561, 565, 566, 576, 585, 666
- F**
- \F ..... 2399
- \fam ..... 81
- \fi ..... 12, 32, 120
- \fi: ..... 8, 748, 760, 764, 859–862,  
941, 947, 952, 957, 962, 967, 972,  
977, 982, 991, 1009, 1027, 1049,  
1050, 1057, 1063, 1078, 1084, 1145,  
1146, 1159, 1160, 1163, 1264, 1267,  
1273, 1276, 1280, 1291, 1328, 1423,  
1511, 1514, 1524, 1613, 1637, 1649,  
1697, 1701, 1705, 1709, 1712, 1713,  
1858, 1887, 1935, 2120, 2125, 2134,  
2142, 2149, 2158, 2168, 2172, 2180,  
2190, 2325, 2329, 2333, 2337, 2341,  
2345, 2349, 2353, 2357, 2361, 2365,  
2369, 2373, 2377, 2384, 2388, 2392,  
2428, 2439, 2450, 2461, 2526, 2533,  
2536, 2537, 2553–2558, 2609, 2616,  
2632, 2865, 2874, 2906, 2919, 3037,  
3138, 3143, 3148, 3152, 3156, 3160,  
3164, 3168, 3172, 3177, 3183, 3193,  
3203, 3220, 3226, 3227, 3229, 3242,  
3246, 3441, 3501, 3557, 3569, 3666,  
3673, 3681, 3695, 3751, 3766, 3773,  
3780, 3787, 3794, 3801, 3808, 3815,  
3822, 3829, 3836, 3843, 3850, 3857,  
4074, 4079, 4086, 4097, 4291, 4296,  
4458, 4467, 4480, 4782, 4871, 5314,  
5317, 5328, 6287–6289, 6316–6322,  
6335–6337, 6351–6353, 6371, 6380,  
6397, 6406, 6444, 6454, 6466, 6488,  
6494, 6500, 6506, 6507, 6599, 6617
- \file\_add\_path:nN .....  
..... 134, 6685, 6685, 6714, 6720
- \file\_add\_path\_aux:n 6685, 6696, 6710, 6712
- \file\_add\_path\_search:n ..... 6685
- \file\_add\_path\_search:nN .... 6689, 6695
- \file\_if\_exist:n ..... 6651
- \file\_if\_exist:nTF ..... 134, 6651
- \file\_if\_exist\_aux:n 6651, 6662, 6676, 6684
- \file\_if\_exist\_p:n ..... 134, 6651
- \file\_if\_exist\_path:n .. 6651, 6654, 6660
- \file\_input:n ..... 134, 6713, 6713
- \file\_input\_no\_check:n .....  
..... 135, 6716, 6725, 6725
- \file\_input\_no\_check\_no\_record:n ...  
..... 135, 6722, 6736, 6736
- \file\_input\_no\_record:n 134, 6713, 6719
- \file\_list: ..... 135, 6740, 6740
- \file\_list:N ..... 6740, 6741, 6744, 6746
- \file\_list\_aux:n ..... 6749, 6752
- \file\_list\_full: ..... 135, 6740, 6743
- \fileauthor ..... 6, 594, 608, 623
- \filedate ..... 6, 594, 609, 636, 640,  
645, 648, 755, 1443, 1691, 2104,  
2207, 2725, 3070, 3119, 3275, 3476,  
4104, 4257, 4430, 4659, 4804, 4888,  
5293, 5427, 5540, 5709, 6165, 6641

- \filedescription . . . 6, 594, 605, 622,  
640, 648, 755, 1443, 1691, 2104,  
2207, 2725, 3070, 3119, 3275, 3476,  
4104, 4257, 4430, 4659, 4804, 4888,  
5293, 5427, 5540, 5709, 6165, 6641
  - \filename . . . . . 6, 594, 606, 620,  
640, 648, 755, 1443, 1691, 2104,  
2207, 2725, 3070, 3119, 3275, 3476,  
4104, 4257, 4430, 4659, 4804, 4888,  
5293, 5427, 5540, 5709, 6165, 6641
  - \filenameext . . . . . 6, 594, 610, 637, 644
  - \filetimestamp . . . . . 6, 594, 611, 638, 646
  - \fileversion . . . . . 6, 594, 607, 621,  
640, 648, 755, 1443, 1691, 2104,  
2207, 2725, 3070, 3119, 3275, 3476,  
4104, 4257, 4430, 4659, 4804, 4888,  
5293, 5427, 5540, 5709, 6165, 6641
  - \finalhyphendemerits . . . . . 269
  - \firstchoice@true . . . . . 6580
  - \firstmark . . . . . 167
  - \firstmarks . . . . . 393
  - \firstoftwo . . . . . 3, 12
  - \floatingpenalty . . . . . 314
  - \font . . . . . 80
  - \fontchardp . . . . . 418
  - \fontcharht . . . . . 417
  - \fontcharic . . . . . 420
  - \fontcharwd . . . . . 419
  - \fontdimen . . . . . 347
  - \fontname . . . . . 171
  - \frozen@everydisplay . . . . . 693
  - \frozen@everymath . . . . . 692
  - \futurelet . . . . . 76
- G**
- \G . . . . . 2404
  - \g . . . . . 2069
  - \g\_box\_allocation\_seq . . . . . 5299
  - \g\_calc\_A\_dim . . . . .  
348, 6173, 6176, 6219, 6222, 6225, 6228
  - \g\_calc\_A\_int . . . . . 348, 6173,  
6173, 6201, 6204, 6207, 6210, 6213,  
6216, 6231, 6234, 6386, 6398, 6407
  - \g\_calc\_A\_muskip . . . 348, 6173, 6182,  
6255, 6259, 6263, 6267, 6271, 6275
  - \g\_calc\_A\_register . . . . .  
348, 6169, 6170, 6186, 6196, 6296,  
6299, 6302, 6303, 6358, 6372, 6381,  
6386, 6425, 6486, 6492, 6498, 6504
  - \g\_calc\_A\_skip . . . . . 348, 6173, 6179,  
6237, 6240, 6243, 6246, 6249, 6252
  - \g\_clist\_inline\_level\_int . . . . .  
4555, 4558, 4559,  
4562, 4564, 4570, 4571, 4574, 4576
  - \g\_file\_record\_clist . . . . .  
... 135, 6645, 6645, 6726, 6741, 6759
  - \g\_file\_record\_full\_clist . . . . .  
135, 6645, 6646, 6733, 6737, 6744, 6760
  - \g\_peek\_token . . . . . 52, 2560, 2561, 2565
  - \g\_prg\_inline\_level\_int . . . . .  
192, 1788, 1788, 1790, 1791, 1795, 1797
  - \g\_prop\_inline\_level\_int . . . . .  
103, 4787, 4787, 4789, 4790, 4793, 4794
  - \g\_testa\_tl . . . . . 79, 3658, 3660
  - \g\_testb\_tl . . . . . 79, 3658, 3661
  - \g\_tl\_inline\_level\_int . . . . .  
79, 3063, 3879, 3880, 3881,  
3884, 3886, 3889, 3890, 3893, 3895
  - \g\_tmpa\_bool . . . . . 192, 1855, 1856
  - \g\_tmpa\_dim . . . . . 70, 3429, 3433
  - \g\_tmpa\_int . . . . . 58, 2921, 2924
  - \g\_tmpa\_num . . . . . 61, 3110, 3113
  - \g\_tmpa\_skip . . . . . 68, 3360, 3365
  - \g\_tmpa\_tl . . . . . 79, 3656, 3656
  - \g\_tmpa\_toks . . . . . 86, 4242, 4246
  - \g\_tmpb\_dim . . . . . 70, 3429, 3434
  - \g\_tmpb\_int . . . . . 58, 2921, 2925
  - \g\_tmpb\_num . . . . . 61, 3110, 3114
  - \g\_tmpb\_skip . . . . . 68, 3360, 3366
  - \g\_tmpb\_tl . . . . . 79, 3656, 3657
  - \g\_tmpb\_toks . . . . . 86, 4242, 4247
  - \g\_tmpe\_toks . . . . . 86, 4242, 4248
  - \g\_toks\_allocation\_seq . . . . . 4243
  - \g\_trace\_statistics\_status . . . . . 741
  - \g\_xref\_all\_curr\_deferred\_fields\_prop  
. . . . . 323, 5431, 5432, 5479
  - \g\_xref\_all\_curr\_immediate\_fields\_prop  
. . . . . 323, 5431, 5431, 5475
  - \gaddtolength . . . . . 132, 6574, 6577
  - \gdef . . . . . 67
  - .generate\_choices:n . . . . . 125
  - \GetIdInfo . . . . . 6, 594, 594
  - \GetIdInfoAuxCVS:w . . . . . 594, 629, 634
  - \GetIdInfoAuxi:w . . . . . 594, 614, 618
  - \GetIdInfoAuxii:w . . . . . 594, 624, 627
  - \GetIdInfoAuxSVN:w . . . . . 594, 631, 642
  - \GetIdInfoMaybeMissing:w . . . . . 597, 599
  - \getname . . . . . 5503, 5531, 5534
  - \getpage . . . . . 5506, 5532, 5535

<code>\getvaluepage</code> .....	5509, 5532, 5535	<code>\hbox_set:Nn</code> ..	117, 5395, 5395–5397, 6414
<code>\global</code> .....	82	<code>\hbox_set_inline_begin:c</code> .....	117, 5405
<code>\globaldefs</code> .....	86	<code>\hbox_set_inline_begin:N</code> .....	117, 5405, 5405, 5408, 5411
<code>\glueexpr</code> .....	426	<code>\hbox_set_inline_end:</code> ..	117, 5405, 5409
<code>\glueshrink</code> .....	429	<code>\hbox_set_to_wd:cnn</code> .....	117, 5399
<code>\glueshrinkorder</code> .....	431	<code>\hbox_set_to_wd:Nnn</code> .....	117, 5399, 5399, 5402, 5403
<code>\gluestretch</code> .....	428	<code>\hbox_to_wd:nn</code> .....	117, 5415, 5415
<code>\gluestretchorder</code> .....	430	<code>\hbox_to_zero:n</code> .....	117, 5415, 5416
<code>\gluetomu</code> .....	432	<code>\hbox_unpack:c</code> .....	118, 5417
<code>\group_align_safe_begin:</code> .....	40, 1711, 1711, 1881, 2576, 2591	<code>\hbox_unpack:N</code> ....	118, 5417, 5417, 5418
<code>\group_align_safe_end:</code> 40, 1711, 1713,	1907, 1908, 2574, 2575, 2590, 2601	<code>\hbox_unpack_clear:c</code> .....	118, 5417
<code>\group_begin:</code> 25, 791, 792, 1013, 1520,	2068, 2081, 2308, 2397, 2489, 3933,	<code>\hbox_unpack_clear:N</code> 118, 5417, 5419, 5420	
	3943, 3959, 3969, 3977, 4839, 4922,	<code>\heightof</code> .....	132, 6568, 6570
	4987, 4995, 5021, 5028, 5464, 5494,	<code>\hfil</code> .....	236
	5552, 5565, 5599, 5610, 6189, 6292,	<code>\hfill</code> .....	238
	6293, 6359, 6385, 6419, 6437, 6456,	<code>\hfilneg</code> .....	237
	6471, 6476, 6482, 6512, 6517, 6611	<code>\hfuzz</code> .....	335
<code>\group_end:</code> .....	25, 791,	<code>\hoffset</code> .....	310
	793, 1017, 1525, 2072, 2085, 2322,	<code>\holdinginserts</code> .....	313
	2407, 2497, 3939, 3949, 3965, 3974,	<code>\hrule</code> .....	249
	3982, 4839, 4925, 4993, 5010, 5025,	<code>\hsize</code> .....	274
	5032, 5472, 5497, 5557, 5596, 5606,	<code>\hskip</code> .....	239
	5613, 6194, 6197, 6302, 6303, 6306,	<code>\hss</code> .....	240
	6357, 6358, 6384, 6433, 6437, 6448,	<code>\ht</code> .....	378
	6460, 6478, 6508, 6511, 6516, 6613	<code>\hyphenation</code> .....	364
<code>\group_execute_after:N</code> ....	25, 794,	<code>\hyphenchar</code> .....	348
	794, 6292, 6293, 6359, 6360, 6389, 6514	<code>\hyphenpenalty</code> .....	266
<code>\gsetlength</code> .....	132, 6574, 6575		
<b>H</b>			
<code>\H</code> .....	2404	<b>I</b>	
<code>\halign</code> .....	93	<code>\I</code> .....	2404
<code>\hangafter</code> .....	271	<code>\if</code> .....	102
<code>\hangindent</code> .....	272	<code>\if:w</code> . 9, 760, 766, 939, 989, 1006, 1156,	
<code>\hbadness</code> .....	333		1159, 1160, 1611, 1637, 3138, 4077
<code>\hbox</code> .....	328	<code>\if_bool:N</code> 9, 760, 767, 1266, 1275, 1279, 1858	
<code>\hbox:n</code> .....	117, 5394, 5394	<code>\if_box_empty:N</code> .....	114, 5310, 5312
<code>\hbox:w</code> .....	749	<code>\if_case:w</code> .....	62, 2859, 2868,
<code>\hbox_gset:cn</code> .....	117, 5395		2896, 2909, 3027, 3074, 3075, 6367,
<code>\hbox_gset:Nn</code> ....	117, 5395, 5397, 5398		6376, 6393, 6402, 6450, 6462, 6483
<code>\hbox_gset_inline_begin:c</code> ....	117, 5405	<code>\if_catcode:w</code> . 9, 760, 770, 2324, 2328,	
<code>\hbox_gset_inline_begin:N</code> .....	117, 5405, 5410, 5413		2332, 2336, 2340, 2344, 2348, 2352,
<code>\hbox_gset_inline_end:</code> .	117, 5405, 5414		2356, 2360, 2364, 2372, 2612, 4095
<code>\hbox_gset_to_wd:cnn</code> .....	117, 5399	<code>\if_charcode:w</code> 9, 760, 769, 2376, 2628, 4082	
<code>\hbox_gset_to_wd:Nnn</code> 117, 5399, 5403, 5404		<code>\if_cs_exist:N</code> 9, 776, 776, 1045, 1260, 1269	
<code>\hbox_set:cn</code> .....	117, 5395	<code>\if_cs_exist:w</code> .....	9, 776, 777, 1053
		<code>\if_dim:w</code> .....	69, 3438, 3438, 3440, 6493, 6499, 6505
		<code>\if_eof:w</code> .....	106, 4869, 4869
		<code>\if_false:</code> .....	8, 760, 761, 874, 1712

<code>\if_hbox:N</code> .....	114, 5310, 5310	<code>\ifx</code> .....	11, 112
<code>\if_horizontal_mode:</code> .....	743	<code>\ignorespaces</code> .....	160
<code>\if_intexpr_case:w</code> .....	64, 3123, 3128	<code>\immediate</code> .....	122
<code>\if_intexpr_compare:w</code> .....	64, 3123, 3126, 3147, 3151, 3155, 3159, 3163, 3167, 3171, 3175, 3181, 3188, 3198, 3211, 3215, 3216, 3222	<code>\indent</code> .....	256
<code>\if_intexpr_odd:w</code> 64, 3123, 3127, 3241, 3245		<code>\input</code> .....	130
<code>\if_meaning:w</code> .....	9, 771, 771, 1023, 1042, 1059, 1142–1144, 1422, 1508, 1509, 1647, 1887, 2117, 2123, 2129, 2138, 2148, 2172, 2368, 2391, 2423, 2434, 2445, 2456, 2605, 3143, 3496, 3665, 3673, 3680, 3695, 3764, 3771, 3778, 3785, 3792, 3799, 3806, 3813, 3820, 3827, 3834, 3841, 3848, 3855, 4073, 4288, 4295, 4455, 4466, 4475, 4780, 6279, 6282, 6284, 6306–6312, 6325, 6328, 6331, 6341, 6344, 6347	<code>\input@path</code> .....	6671, 6672, 6705, 6706
<code>\if_mode_horizontal:</code> ..	10, 772, 773, 1700	<code>\InputIfFileExists</code> .....	5496
<code>\if_mode_inner:</code> .....	10, 772, 775, 1704	<code>\inputlineno</code> .....	132
<code>\if_mode_math:</code> .....	10, 772, 772, 1708	<code>\insert</code> .....	312
<code>\if_mode_vertical:</code> ....	10, 772, 774, 1696	<code>\insertpenalties</code> .....	315
<code>\if_num:w</code> .....	61, 1712, 1713, 2154, 2176, 3074, 3074, 6438, 6487	<code>\int_add:cn</code> .....	55, 2791
<code>\if_predicate:w</code> ...	9, 760, 768, 1287, 1934, 2164, 2186, 2383, 2387, 2521, 2522, 2528, 2529, 2540, 2542, 2544, 2546, 2548, 2550, 3553, 3565, 4089	<code>\int_add:Nn</code> .....	55, 2779, 2780, 2791, 2791, 2808, 2815, 6207
<code>\if_true:</code> .....	8, 760, 760, 873	<code>\int_advance:w</code> .....	229, 2729, 2731, 2757, 2762, 2792, 2798
<code>\if_vbox:N</code> .....	114, 5310, 5311	<code>\int_Alph_default_conversion_rule:n</code> .....	57, 2858, 2867, 2882
<code>\ifcase</code> .....	103	<code>\int_alph_default_conversion_rule:n</code> .....	57, 2858, 2858, 2878
<code>\ifcat</code> .....	104	<code>\int_const:Nn</code> .....	57, 2931, 2931, 2944–2959, 2961–2972
<code>\ifcsname</code> .....	387	<code>\int_convert_from_base_ten:nn</code> .....	59, 2999, 2999
<code>\ifdefined</code> .....	386	<code>\int_convert_from_base_ten_aux:ffn</code>	3015
<code>\ifdim</code> .....	107	<code>\int_convert_from_base_ten_aux:fon</code>	2999
<code>\ifeof</code> .....	108	<code>\int_convert_from_base_ten_aux:nfn</code> .	3002, 3006
<code>\iffalse</code> .....	113	<code>\int_convert_from_base_ten_aux:nnn</code> .	2999, 3011, 3024, 3025
<code>\iffirstchoice@</code> .....	6580, 6591, 6606	<code>\int_convert_from_base_ten_aux:non</code>	2999
<code>\iffontchar</code> .....	416	<code>\int_convert_letter_to_number:N</code> ....	3051, 3055
<code>\ifhbox</code> .....	109	<code>\int_convert_number_to_letter:n</code> ....	229, 3013, 3017, 3026, 3026
<code>\ifhmode</code> .....	115	<code>\int_convert_number_with_rule:nnN</code> ..	57, 2848, 2848, 2851, 2877, 2881, 2887, 2891
<code>\ifinner</code> .....	118	<code>\int_convert_to_base_ten:nn</code> .....	59, 3038, 3038
<code>\ifmmode</code> .....	116	<code>\int_convert_to_base_ten_aux:nn</code> ....	3041, 3044
<code>\ifnum</code> .....	105	<code>\int_convert_to_base_ten_auxi:nnN</code> ..	3045, 3047, 3050
<code>\ifodd</code> .....	23, 106	<code>\int_decr:c</code> .....	55, 2757
<code>\iftrue</code> .....	114	<code>\int_decr:N</code> 55, 2757, 2762, 2778, 2780, 2784	
<code>\ifvbox</code> .....	110	<code>\int_gadd:cn</code> .....	55, 2791
<code>\ifvmode</code> .....	117	<code>\int_gadd:Nn</code> .....	55, 2781, 2782, 2791, 2803, 2816, 6210
<code>\ifvoid</code> .....	111	<code>\int_gdecr:c</code> .....	55, 2757



- \int\_gdecr:N [55](#), [1797](#), [2757](#), [2773](#), [2782](#),  
[2786](#), [3886](#), [3895](#), [4564](#), [4576](#), [4794](#)
- \int\_get\_digits:n . [230](#), [2973](#), [2979](#), [3041](#)
- \int\_get\_sign:n . . . [230](#), [2973](#), [2976](#), [3040](#)
- \int\_get\_sign\_and\_digits:n . . . . .  
. . . . . [230](#), [2973](#), [2973](#)
- \int\_get\_sign\_and\_digits\_aux:nNNN . .  
. . [2973](#), [2974](#), [2977](#), [2980](#), [2982](#), [2998](#)
- \int\_get\_sign\_and\_digits\_aux:oNNN . .  
. . . . . [2973](#), [2986](#), [2987](#), [2991](#)
- \int\_gincr:c . . . . . [54](#), [2757](#), [6610](#)
- \int\_gincr:N [54](#), [1790](#), [2757](#), [2767](#), [2781](#),  
[2785](#), [3880](#), [3889](#), [4558](#), [4570](#), [4789](#)
- .int\_gset:c . . . . . [125](#)
- \int\_gset:cn . . . . . [55](#), [2744](#)
- .int\_gset:N . . . . . [125](#)
- \int\_gset:Nn . . . [55](#), [2744](#), [2749](#), [2756](#), [6204](#)
- \int\_gsub:cn . . . . . [55](#), [2791](#)
- \int\_gsub:Nn . . . [55](#), [2791](#), [2809](#), [2818](#), [6216](#)
- \int\_gzero:c . . . . . [55](#), [2787](#)
- \int\_gzero:N . . . . . [55](#), [2787](#), [2789](#), [2790](#)
- \int\_incr:c . . . . . [54](#), [2757](#)
- \int\_incr:N . . . . .  
[54](#), [2757](#), [2757](#), [2772](#), [2779](#), [2783](#), [5783](#)
- \int\_new:c . . . . . [54](#), [2732](#)
- \int\_new:N . . . . . [54](#), [1788](#), [2732](#), [2734](#),  
[2738](#), [2743](#), [2921](#)–[2925](#), [2934](#), [2939](#),  
[3063](#), [4555](#), [4787](#), [5717](#), [6172](#)–[6175](#)
- \int\_new\_l:N . . . . . [2735](#)
- \int\_pre\_eval\_one\_arg:Nn [230](#), [2926](#), [2926](#)
- \int\_pre\_eval\_two\_args:Nnn . . . . .  
. . . . . [230](#), [2926](#), [2928](#)
- \int\_roman\_lcuc\_mapping:Nnn . . . . .  
. . . . . [57](#), [2824](#), [2824](#), [2828](#)–[2835](#)
- .int\_set:c . . . . . [125](#)
- \int\_set:cn . . . . . [55](#), [2744](#)
- .int\_set:N . . . . . [125](#)
- \int\_set:Nn [55](#), [2744](#), [2744](#), [2754](#), [2755](#),  
[2934](#), [2939](#), [4892](#), [5779](#), [6188](#), [6201](#)
- \int\_show:c . . . . . [56](#), [2821](#), [2822](#)
- \int\_show:N . . . . . [56](#), [2821](#), [2821](#), [2822](#)
- \int\_sub:cn . . . . . [55](#), [2791](#)
- \int\_sub:Nn [55](#), [2791](#), [2797](#), [2814](#), [2817](#), [6213](#)
- \int\_symbol\_math\_conversion\_rule:n .  
. . . . . [57](#), [2888](#), [2895](#), [2895](#)
- \int\_symbol\_text\_conversion\_rule:n .  
. . . . . [57](#), [2892](#), [2895](#), [2908](#)
- \int\_to\_Alph:n . . . . . [56](#), [2876](#), [2880](#)
- \int\_to\_alph:n . . . . . [56](#), [2876](#), [2876](#)
- \int\_to\_arabic:n . . . . . [56](#), [2823](#), [2823](#)
- \int\_to\_number:w . . . . . [57](#), [2729](#), [2730](#)
- \int\_to\_Roman:n . . . . . [56](#), [2836](#), [2840](#)
- \int\_to\_roman:n . . . . . [56](#), [2836](#), [2836](#)
- \int\_to\_roman:w . . . . .  
. . . . . [56](#), [1900](#), [2729](#), [2729](#), [2838](#),  
[2842](#), [4124](#), [4127](#), [4131](#), [4208](#), [4223](#)
- \int\_to\_roman\_lcuc:NN . . . . .  
. . . . . [57](#), [2836](#), [2837](#), [2841](#), [2844](#), [2846](#)
- \int\_to\_symbol:n . . . . . [56](#), [2884](#), [2884](#)
- \int\_use:c . . . . . [55](#), [2819](#), [2820](#)
- \int\_use:N [55](#), [1791](#), [1795](#), [2215](#), [2265](#),  
[2277](#), [2287](#), [2297](#), [2819](#), [2819](#), [2820](#),  
[3881](#), [3884](#), [3890](#), [3893](#), [4559](#), [4562](#),  
[4571](#), [4574](#), [4790](#), [4793](#), [5780](#), [6446](#)
- \int\_zero:c . . . . . [55](#), [2787](#)
- \int\_zero:N . . . . .  
[55](#), [2787](#), [2787](#), [2788](#), [5763](#), [6388](#), [6513](#)
- \interactionmode . . . . . [414](#)
- \interlinepenalties . . . . . [435](#)
- \interlinepenalty . . . . . [294](#)
- \intexpr\_abs:n . . . . . [63](#), [3179](#), [3179](#)
- \intexpr\_compare:n . . . . . [3132](#)
- \intexpr\_compare:nF . . . . . [3252](#), [3258](#)
- \intexpr\_compare:nNn . . . . . [3174](#)
- \intexpr\_compare:nNnF . . . . .  
. . . . . [1717](#), [1719](#), [1771](#), [1780](#),  
[1800](#), [1808](#), [1822](#), [1830](#), [3264](#), [3270](#)
- \intexpr\_compare:nNnT . . [1715](#), [3261](#), [3267](#)
- \intexpr\_compare:nNnTF . . . . [63](#), [1765](#),  
[1792](#), [1816](#), [1930](#), [1955](#), [2849](#), [2932](#),  
[2933](#), [3000](#), [3012](#), [3056](#), [3059](#), [3174](#)
- \intexpr\_compare:nT . . . . . [3249](#), [3255](#)
- \intexpr\_compare:nTF . . . . [62](#), [3132](#), [5837](#)
- \intexpr\_compare\_auxi:w . . . . [3133](#), [3136](#)
- \intexpr\_compare\_auxii:w . . . . [3137](#), [3140](#)
- \intexpr\_compare\_p:n . . . . . [62](#), [3132](#)
- \intexpr\_compare\_p:nNn [63](#), [3174](#), [3379](#), [3380](#)
- \intexpr\_div\_round:nn . . . [63](#), [3206](#), [3233](#)
- \intexpr\_div\_truncate:nn . . . . .  
. . . . . [63](#), [2852](#), [3020](#), [3206](#), [3209](#), [3237](#)
- \intexpr\_div\_truncate\_raw:nn . . . . [3206](#)
- \intexpr\_do\_until:nn [65](#), [3248](#), [3257](#), [3258](#)
- \intexpr\_do\_until:nNnn [65](#), [3260](#), [3269](#), [3270](#)
- \intexpr\_do\_while:nn . . . . [65](#), [3248](#), [3254](#)
- \intexpr\_do\_while:nNnn . . . . .  
. . . . . [65](#), [3255](#), [3260](#), [3266](#), [3267](#)
- \intexpr\_eval:n . . . . . [62](#), [1727](#),  
[1768](#), [1775](#), [1784](#), [1796](#), [1804](#), [1812](#),  
[1819](#), [1826](#), [1834](#), [1950](#), [2823](#), [2838](#),  
[2842](#), [2854](#), [2856](#), [2927](#), [2929](#), [2936](#),



- 3003, 3007, 3039, 3051, 3058, 3091,  
 3123, 3129, 3207, 3233, 3921, 3927  
 \intexpr\_eval:w .....  
 ..... 64, 2213, 2217, 2223, 2259,  
 2263, 2267, 2271, 2275, 2279, 2282,  
 2285, 2289, 2292, 2295, 2299, 2303,  
 2744, 2792, 2798, 3027, 3123, 3124,  
 3130, 3134, 3147, 3151, 3155, 3159,  
 3163, 3167, 3171, 3175, 3181, 3184,  
 3187, 3189, 3197, 3199, 3210, 3211,  
 3215, 3216, 3222, 3236, 3241, 3245  
 \intexpr\_eval\_end: .....  
 ..... 64, 2213, 2217, 2223, 2259,  
 2263, 2267, 2271, 2275, 2279, 2282,  
 2285, 2289, 2292, 2295, 2299, 2303,  
 2744, 2792, 2798, 3027, 3123, 3125,  
 3130, 3147, 3151, 3155, 3159, 3163,  
 3167, 3171, 3176, 3184, 3189, 3194,  
 3199, 3204, 3231, 3238, 3241, 3245  
 \intexpr\_if\_even:n ..... 3244  
 \intexpr\_if\_even:nTF ..... 63, 3240  
 \intexpr\_if\_even\_p:n .... 63, 1892, 3240  
 \intexpr\_if\_odd:n ..... 3240  
 \intexpr\_if\_odd:nTF ..... 63, 3240  
 \intexpr\_if\_odd\_p:n ..... 63, 3240  
 \intexpr\_max:nn ..... 63, 3179, 3186  
 \intexpr\_min:nn ..... 63, 3179, 3196  
 \intexpr\_mod:nn 63, 2854, 3017, 3206, 3234  
 \intexpr\_until\_do:nn 65, 3248, 3251, 3252  
 \intexpr\_until\_do:nNnn 65, 3260, 3263, 3264  
 \intexpr\_value:w 64, 3123, 3123, 3130,  
 3133, 3180, 3187, 3197, 3210, 3235  
 \intexpr\_while\_do:nn 65, 3248, 3248, 3249  
 \intexpr\_while\_do:nNnn 65, 3260, 3260, 3261  
 \ior\_close:N .....  
 106, 4864, 4864, 4866, 6656, 6677, 6693  
 \ior\_gto:NN ..... 106, 4873, 4877  
 \ior\_if\_eof:N ..... 4870  
 \ior\_if\_eof:Nf ..... 6664, 6698  
 \ior\_if\_eof:Ntf ... 106, 4870, 6653, 6688  
 \ior\_if\_eof\_p:N ..... 106, 4870  
 \ior\_new:N ... 106, 4859, 4861, 4863, 6648  
 \ior\_open:Nn .....  
 106, 4864, 4865, 6652, 6663, 6687, 6697  
 \ior\_to:NN ..... 106, 4873, 4873, 4880  
 \iow\_char:N .....  
 105, 4331, 4510, 4689, 4691, 4855, 4855  
 \iow\_close:N ..... 104, 4817, 4821, 4821  
 \iow\_log:n ..... 104, 4830, 4831  
 \iow\_log:x .....  
 . 15, 104, 1101, 1101, 1125, 1627,  
 4830, 4830, 5024, 6748, 6750, 6753  
 \iow\_new:c ..... 103, 4808  
 \iow\_new:N 103, 4808, 4810, 4813, 4815, 5483  
 \iow\_newline: ..... 105, 4853, 4853  
 \iow\_now:Nn .....  
 104, 4827, 4827, 4831, 4833, 4835, 4845  
 \iow\_now:Nx .....  
 104, 4826, 4826, 4828, 4830, 4832, 4842  
 \iow\_now\_buffer\_safe:Nn 104, 4838, 4844  
 \iow\_now\_buffer\_safe:Nx 104, 4838, 4841  
 \iow\_now\_buffer\_safe\_aux:w .....  
 ..... 4838, 4842, 4845  
 \iow\_now\_buffer\_safe\_expanded\_aux:w .....  
 ..... 4838  
 \iow\_now\_when\_avail:cn ..... 105, 4834  
 \iow\_now\_when\_avail:Nn .....  
 ..... 105, 4834, 4834, 4837  
 \iow\_open:cn ..... 104, 4816  
 \iow\_open:Nn .. 104, 4816, 4816, 4820, 5492  
 \iow\_shipout:Nn ... 105, 4849, 4849, 4852  
 \iow\_shipout:Nx ..... 105, 4849  
 \iow\_shipout\_x:Nn .....  
 ... 15, 105, 781, 781, 1102, 1105,  
 4826, 4847, 4847, 4848, 4850, 5476  
 \iow\_shipout\_x:Nx ..... 105, 4847  
 \iow\_space: ..... 105, 2165, 2187,  
 4331, 4510, 4689-4691, 4854, 4854  
 \iow\_term:n ..... 104, 4830, 4833  
 \iow\_term:x .....  
 . 15, 104, 1101, 1104, 1108, 1124,  
 4323, 4502, 4681, 4830, 4832, 5031
- ## J
- \jobname ..... 369, 5492, 5496
- ## K
- \K ..... 2404  
 \kern ..... 247  
 \keys\_bool\_set:NN .....  
 ..... 128, 5728, 5728, 5998, 6001  
 \keys\_choice\_code\_store:x .....  
 ..... 128, 5744, 5744, 6007, 6010  
 \keys\_choice\_find:n 128, 5747, 5747, 5754  
 \keys\_choice\_make: .....  
 ... 128, 5738, 5752, 5752, 5762, 6004  
 \keys\_choices\_generate:n .....  
 ..... 128, 5761, 5761, 6037

\keys_choices_generate_aux:n . . . . .	\keys_show:nn . . . . . 128, 5970, 5970
. . . . . 5761, 5774, 5776	\keys_tmp:w . . . . . 130, 5826, 5828,
\keys_cmd_set:nn . . . . .	5841, 5847, 5862–5864, 5973, 5973
129, 5753, 5756, 5785, 5785, 5882, 6013	\keys_value_or_default:n . . . . .
\keys_cmd_set:nx . . . 129, 5729, 5733,	. . . . . 130, 5946, 5974, 5974
5777, 5785, 5790, 5886, 5992, 6016	\keys_value_requirement:n . . . . .
\keys_cmd_set_aux:n 5785, 5786, 5791, 5795	. . . . . 130, 5984, 5984, 6094, 6097
\keys_default_set:n . . . . .	\keys_variable_set:cnNN . . . . .
. . . 129, 5742, 5799, 5799, 5802, 6019	130, 5988, 6028, 6034, 6043, 6049,
\keys_default_set:V . . . . 129, 5799, 6022	6061, 6067, 6073, 6079, 6085, 6091
\keys_define:nn . . . 123, 5803, 5803, 6121	\keys_variable_set:NnNN . . 130, 5988,
\keys_define_elt:n . 129, 5805, 5816, 5816	5988, 5996, 6025, 6031, 6040, 6046,
\keys_define_elt:nn 129, 5806, 5816, 5820	6058, 6064, 6070, 6076, 6082, 6088
\keys_define_elt_aux:nn . . . . .	\KV_add_element_aux:w . . 5591, 5597, 5597
. . . . . 5818, 5822, 5824, 5824	\KV_add_value_element:w . . . . .
\keys_define_key:n . 129, 5829, 5835, 5835	. . . . . 328, 5565, 5574, 5672
\keys_execute: 129, 5850, 5850, 5961, 5967	\KV_key_no_value_elt:n 121, 5634, 5679,
\keys_execute_aux:nn . . . . .	5689, 5689, 5805, 5811, 5923, 5929
. . 5748, 5749, 5850, 5851, 5856, 5861	\KV_key_value_elt:nn 121, 5652, 5684,
\keys_execute_unknown: . . . . .	5689, 5690, 5806, 5813, 5924, 5931
. . . . . 129, 5850, 5852, 5855	\KV_parse_elt:w . . . . .
\keys_if_exist:nn . . . . . 5869	. . 5604, 5612, 5616, 5616, 5618, 5623
\keys_if_exist:nnTF . . . . . 128, 5869	\KV_parse_no_sanitize_aux:n . . . . .
\keys_if_value_requirement:nTF . . . . .	. . . . . 5609, 5609, 5693, 5701
. . . . . 129, 5876, 5876, 5947, 5959	\KV_parse_no_space_removal_no_sanitize:n
\keys_meta_make:n . 129, 5881, 5881, 6052	. . . . . 121, 5691, 5691, 5809
\keys_meta_make:x . 129, 5881, 5885, 6055	\KV_parse_sanitize_aux:n 5598, 5598, 5697
\keys_property_find:n 129, 5825, 5890, 5890	\KV_parse_space_removal_no_sanitize:n
\keys_property_find_aux:n 5890, 5893, 5898	. . . . . 121, 5695, 5699
\keys_property_find_aux:w . . . . .	\KV_parse_space_removal_sanitize:n .
. . . . . 5890, 5899, 5901, 5906	. . . . . 121, 5695, 5695, 5927
\keys_property_new:nn . . . . .	\KV_remove_surrounding_spaces:nw . . .
. . . 129, 5912, 5912, 6003, 6093, 6096	. . . . . 328, 5565, 5567
\keys_property_new_arg:nn . . . . .	\KV_remove_surrounding_spaces_auxi:w
. . . . . 129, 5912, 5915, 5997,	. . . 328, 5565, 5568, 5570, 5576, 5585
6000, 6006, 6009, 6012, 6015, 6018,	\KV_remove_surrounding_spaces_auxii:w
6021, 6024, 6027, 6030, 6033, 6036,	. . . . . 5565, 5571, 5573
6039, 6042, 6045, 6048, 6051, 6054,	\KV_sanitize_outerlevel_active_commas:N
6057, 6060, 6063, 6066, 6069, 6072,	. . . . . 327, 5552, 5561, 5603
6075, 6078, 6081, 6084, 6087, 6090	\KV_sanitize_outerlevel_active_equals:N
\keys_property_undefine:n . . . . .	. . . . . 327, 5552, 5558, 5602
. . . . . 130, 5796, 5918, 5918	\KV_set_key_element:w 328, 5565, 5582, 5629
\keys_set:nn . . . . .	\KV_split_key_value_current:w . . . . .
. . . 127, 5883, 5887, 5921, 5921, 5934	328, 5622, 5627, 5627, 5692, 5696, 5700
\keys_set:nV . . . . . 127, 5921	\KV_split_key_value_no_space_removal:w
\keys_set:nv . . . . . 127, 5921	. . . . . 328, 5675, 5675, 5692
\keys_set_elt:n . . . 130, 5923, 5935, 5935	\KV_split_key_value_space_removal:w
\keys_set_elt:nn . . 130, 5924, 5935, 5939	. . . . . 328, 5628, 5628, 5696, 5700
\keys_set_elt_aux: 5943, 5952, 5955, 5958	\KV_split_key_value_space_removal_aux:w
\keys_set_elt_aux:nn 5937, 5941, 5943, 5943	. . . . . 5628, 5640, 5649

- \KV\_split\_key\_value\_space\_removal\_detect\_errorfile\_tmp\_tl ..... 328, 5628, 5639, 5645
- \KV\_val\_preserve\_braces:NnN . 5648, 5668
- L**
- \L ..... 2404
- \l\_calc\_B\_dim .. 348, 6173, 6177, 6219, 6222, 6225, 6228, 6491, 6493, 6494
- \l\_calc\_B\_int ..... 348, 6173, 6174, 6201, 6204, 6207, 6210, 6213, 6216, 6231, 6234, 6387, 6439, 6442, 6446, 6485, 6487, 6488
- \l\_calc\_B\_muskip ..... 348, 6173, 6183, 6255, 6259, 6263, 6267, 6271, 6275, 6503, 6505, 6506
- \l\_calc\_B\_register ..... 348, 6169, 6171, 6187, 6196, 6198, 6296, 6302, 6303, 6358, 6366, 6372, 6375, 6381, 6387, 6392, 6398, 6401, 6407, 6449, 6455, 6461, 6467
- \l\_calc\_B\_skip ..... 348, 6173, 6180, 6237, 6240, 6243, 6246, 6249, 6252, 6497, 6499, 6500
- \l\_calc\_C\_dim ..... 348, 6173, 6178, 6490, 6493, 6494
- \l\_calc\_C\_int ..... 348, 6173, 6175, 6440, 6443, 6446, 6484, 6487, 6488
- \l\_calc\_C\_muskip ..... 348, 6173, 6184, 6502, 6505, 6506
- \l\_calc\_C\_skip ..... 348, 6173, 6181, 6496, 6499, 6500
- \l\_calc\_current\_type\_int .. 348, 6169, 6172, 6188, 6367, 6376, 6388, 6393, 6402, 6438, 6450, 6462, 6483, 6513
- \l\_calc\_expression\_tl ..... 348, 6169, 6169, 6192, 6195
- \l\_clist\_remove\_clist ..... 4395, 4605, 4605, 4607, 4609, 4612, 4613, 4629, 4632, 4636
- \l\_exp\_tl ..... 181, 1452, 1452, 1481, 1482, 3574, 3575, 3582, 3583, 3591, 3592, 3599, 3600, 3611, 3612, 3616, 3617, 3624, 3625, 3632, 3633
- \l\_file\_search\_path\_clist ..... 135, 6647, 6647, 6672, 6676, 6706, 6710
- \l\_file\_test\_read\_stream .. 135, 6648, 6648, 6652, 6653, 6656, 6663, 6664, 6677, 6687, 6688, 6693, 6697, 6698
- \l\_file\_tmp\_bool ..... 135, 6649, 6649, 6661, 6665, 6678
- \l\_keys\_choice\_code\_tl ..... 135, 6650, 6650, 6714–6716, 6720–6722
- \l\_keys\_choice\_int ..... 130, 5719, 5719, 5767, 5781
- \l\_keys\_choice\_tl . 127, 5717, 5717, 5763, 5779, 5780, 5783
- \l\_keys\_key\_tl 128, 5720, 5720, 5944, 5945
- \l\_keys\_module\_tl ..... 131, 5723, 5723, 5804, 5856, 5858, 5883, 5887, 5891, 5922, 5945
- \l\_keys\_nesting\_seq ..... 131, 5724, 5724, 5807, 5810, 5925, 5928
- \l\_keys\_nesting\_tl ..... 131, 5724, 5725, 5807, 5808, 5810, 5812, 5814, 5925, 5926, 5928, 5930, 5932
- \l\_keys\_no\_value\_bool ..... 131, 5726, 5726, 5817, 5821, 5836, 5936, 5940, 5948, 5960, 5976
- \l\_keys\_path\_tl ..... 131, 5720, 5721, 5729, 5733, 5745, 5748, 5749, 5753, 5756, 5758, 5765, 5768, 5772, 5777, 5800, 5832, 5844, 5851, 5857, 5878, 5882, 5886, 5891, 5903, 5904, 5908, 5945, 5950, 5964, 5977, 5979, 5985, 5992, 6013, 6016
- \l\_keys\_property\_tl ..... 131, 5720, 5722, 5827, 5832, 5839, 5844, 5909
- \l\_keys\_value\_toks ..... 131, 5727, 5727, 5864, 5964, 5975, 5978
- \l\_KV\_currkey\_toks ..... 327, 5547, 5548, 5583, 5590, 5592, 5635, 5653
- \l\_KV\_currval\_toks ..... 327, 5547, 5549, 5575, 5579
- \l\_KV\_parse\_toks ... 327, 5547, 5547, 5578, 5600, 5607, 5611, 5614, 5633, 5651, 5656, 5662, 5667, 5679, 5684
- \l\_KV\_remove\_one\_level\_of\_braces\_bool ... 121, 5550, 5550, 5551, 5588, 5660
- \l\_KV\_tmpa\_tl ..... 327, 5544, 5544, 5601–5603, 5605, 5630, 5631, 5650, 5655, 5658, 5676, 5677, 5682
- \l\_KV\_tmpb\_tl ..... 327, 5544, 5545
- \l\_last\_box ..... 116, 5338, 5338, 5339
- \l\_msg\_class\_tl ..... 113, 4933, 4933, 5115, 5116, 5119
- \l\_msg\_current\_class\_tl ..... 113, 4933, 4934, 5095, 5116
- \l\_msg\_current\_module\_tl ..... 5096

- \l\_msg\_names\_clist ..... 4509, 4513, 4593, 4596, 4597, 4683,  
..... 113, 4935, 4935, 4973, 4974 4685, 4686, 4688, 4694, 5441, 5447
- \l\_msg\_redirect\_classes\_clist ..... \l\_tmpb\_box ..... 116, 5363, 5367
- ... 114, 4938, 4938, 5071, 5075, 5078 \l\_tmpb\_dim ..... 70, 3429, 3430
- \l\_msg\_redirect\_classes\_prop ..... \l\_tmpb\_int ..... 58, 2921, 2922
- ..... 114, 4936, 4936 \l\_tmpb\_num ..... 61, 3110, 3111
- \l\_msg\_redirect\_names\_prop ..... \l\_tmpb\_skip ..... 68, 3360, 3363
- ..... 114, 4936, 4937, 5097, 5184 \l\_tmpb\_tl ..... 79, 601, 602, 3662, 3663
- \l\_msg\_tmp\_tl ..... 5000, 5015, 5017 \l\_tmpb\_toks 86, 4242, 4244, 4594, 4597, 4598
- \l\_peek\_false\_tl ... 212, 2567, 2568, \l\_tmpc\_dim ..... 70, 3429, 3431
- 2575, 2590, 2608, 2615, 2624, 2631 \l\_tmpc\_int ..... 58, 2921, 2923
- \l\_peek\_search\_tl ..... \l\_tmpc\_num ..... 61, 3110, 3112
- ... 212, 2570, 2570, 2573, 2587, 2625 \l\_tmpc\_skip ..... 68, 3360, 3364
- \l\_peek\_search\_token ..... \l\_tmpc\_toks ..... 86, 4242, 4245
- 52, 2560, 2562, 2572, 2586, 2605, 2612 \l\_tmpd\_dim ..... 70, 3429, 3432
- \l\_peek\_token ..... 52, 2560, 2560, \l\_xref\_curr\_name\_tl ..... 5502
- 2563, 2605, 2612, 2620–2622, 2713
- \l\_peek\_true\_aux\_tl ..... \language ..... 164
- ..... 212, 2588, 2600, 2600, 2602 \lastbox ..... 321
- \l\_peek\_true\_tl ..... 212, 2567, \lastkern ..... 254
- 2567, 2574, 2589, 2606, 2613, 2629 \lastlinefit ..... 434
- \l\_seq\_remove\_seq ..... \lastnodetype ..... 415
- ..... 4395, 4397, 4399, 4402, 4403 \lastpenalty ..... 360
- \l\_testa\_tl ..... 79, 3658, 3658, \lastskip ..... 255
- 3762, 3764, 3769, 3771, 3776, 3778, \lccode ..... 383
- 3783, 3785, 3790, 3792, 3797, 3799, \leaders ..... 251
- 3804, 3806, 3811, 3813, 3818, 3820, \left ..... 219
- 3825, 3827, 3832, 3834, 3839, 3841, \lefthyphenmin ..... 275
- 3846, 3848, 3853, 3855, 4289, 4456 \leftmargin kern ..... 497
- \l\_testb\_tl ..... 79, \leftskip ..... 277
- 3658, 3659, 3763, 3764, 3770, 3771, \leqno ..... 194
- 3777, 3778, 3784, 3785, 3791, 3792, \let ..... 40, 64
- 3798, 3799, 3805, 3806, 3812, 3813, \limits ..... 211
- 3819, 3820, 3826, 3827, 3833, 3834, \linepenalty ..... 267
- 3840, 3841, 3847, 3848, 3854, 3855 \lineskip ..... 261
- \l\_tl\_replace\_toks ..... 79, \lineskiplimit ..... 262
- 86, 4006, 4006, 4011, 4013, 4016, \long ..... 43, 49, 52, 57, 83
- 4027, 4031, 4034, 4040, 4250, 4250 \looseness ..... 279
- \l\_tmpa\_bool ..... 192, 1855, 1855 \lower ..... 316
- \l\_tmpa\_box 116, 5363, 5364, 5366, 6414, 6417 \lowercase ..... 355
- \l\_tmpa\_dim ..... 70, 3429, 3429 \lrcode ..... 464
- \l\_tmpa\_int ..... 58, 2921, 2921 \luatex\_directlua:D ..... 554, 1269
- \l\_tmpa\_num ..... 61, 3110, 3110 \luatex\_if\_engine: ..... 1278
- \l\_tmpa\_skip ..... 68, 3360, 3360–3362 \luatex\_if\_engine:TF ..... 26, 1260
- \l\_tmpa\_tl .. 5, 79, 600, 602, 603, 614, \M ..... 2404, 2491
- 616, 3662, 3662, 3746, 3754, 3963, 3966 \m@ne ..... 1093
- \l\_tmpa\_toks ..... 86, 3950, \mag ..... 163
- 3956, 3983, 4242, 4242, 4325, 4327, \mark ..... 165
- 4328, 4330, 4334, 4504, 4506, 4507, \marks ..... 391

<code>\mathaccent</code> .....	176	<code>\msg_direct_interrupt_aux:n</code> ..	4998, 5013
<code>\mathbin</code> .....	206	<code>\msg_direct_log:xx</code> .....	
<code>\mathchar</code> .....	177	... <a href="#">111</a> , <a href="#">5020</a> , 5020, 5158, 5165, 5171	
<code>\mathchardef</code> .....	74	<code>\msg_direct_term:xx</code> <a href="#">111</a> , <a href="#">5020</a> , 5027, 5151	
<code>\mathchoice</code> .....	174	<code>\msg_error:nn</code> .....	<a href="#">108</a> , <a href="#">5133</a>
<code>\mathclose</code> .....	207	<code>\msg_error:nnx</code> .....	<a href="#">108</a> , <a href="#">5133</a>
<code>\mathcode</code> .....	385	<code>\msg_error:nnxx</code> .....	<a href="#">108</a> , <a href="#">5133</a>
<code>\mathinner</code> .....	208	<code>\msg_error:nnxxx</code> .....	<a href="#">108</a> , <a href="#">5133</a>
<code>\mathop</code> .....	209	<code>\msg_error:nnxxx</code> .....	<a href="#">108</a> , <a href="#">5133</a>
<code>\mathopen</code> .....	213	<code>\msg_fatal:nn</code> .....	<a href="#">108</a> , <a href="#">5122</a>
<code>\mathord</code> .....	214	<code>\msg_fatal:nnx</code> .....	<a href="#">108</a> , <a href="#">5122</a>
<code>\mathparagraph</code> .....	2901	<code>\msg_fatal:nnxx</code> .....	<a href="#">108</a> , <a href="#">5122</a>
<code>\mathpunct</code> .....	215	<code>\msg_fatal:nnxxx</code> .....	<a href="#">108</a> , <a href="#">5122</a>
<code>\mathrel</code> .....	216	<code>\msg_fatal:nnxxx</code> .....	<a href="#">108</a> , <a href="#">5122</a>
<code>\mathsection</code> .....	2900	<code>\msg_four_spaces:</code> ....	<a href="#">111</a> , <a href="#">4949</a> , 4951
<code>\mathsurround</code> .....	227	<code>\msg_generic_new:nn</code> <a href="#">111</a> , <a href="#">4954</a> , 4958, 5038	
<code>\maxdeadcycles</code> .....	297	<code>\msg_generic_new:nnn</code> <a href="#">111</a> , <a href="#">4954</a> , 4954, 5035	
<code>\maxdepth</code> .....	298	<code>\msg_generic_set:nn</code> .....	
<code>\maxdimen</code> .....	3375	..... <a href="#">111</a> , 4960, <a href="#">4962</a> , 4967, 5044	
<code>\maxof</code> .....	<a href="#">132</a> , <a href="#">6529</a> , 6535	<code>\msg_generic_set:nnn</code> .....	
<code>\meaning</code> .....	357	..... <a href="#">111</a> , 4956, <a href="#">4962</a> , 4962, 5041	
<code>\medmuskip</code> .....	228	<code>\msg_generic_set_clist:n</code> .....	
<code>\message</code> .....	134	..... <a href="#">4962</a> , 4963, 4968, 4972	
<code>\MessageBreak</code> .....	733	<code>\msg_generic_set_more_text:n</code> ....	<a href="#">4962</a>
<code>.meta:n</code> .....	<a href="#">125</a>	<code>\msg_generic_set_more_text:nnn</code> ....	
<code>.meta:x</code> .....	<a href="#">125</a>	..... <a href="#">4965</a> , 4982	
<code>\middle</code> .....	439	<code>\msg_generic_set_text:n</code> .....	<a href="#">4962</a>
<code>\minof</code> .....	<a href="#">132</a> , <a href="#">6529</a> , 6536	<code>\msg_generic_set_text:nn</code> ....	4970, 4977
<code>\mkern</code> .....	181	<code>\msg_info:nn</code> .....	<a href="#">109</a> , <a href="#">5157</a>
<code>\mode_if_horizontal:</code> .....	1699	<code>\msg_info:nnx</code> .....	<a href="#">109</a> , <a href="#">5157</a>
<code>\mode_if_horizontal:TF</code> .....	<a href="#">40</a> , <a href="#">1699</a>	<code>\msg_info:nnxx</code> .....	<a href="#">109</a> , <a href="#">5157</a>
<code>\mode_if_horizontal_p:</code> .....	<a href="#">40</a> , <a href="#">1699</a>	<code>\msg_info:nnxxx</code> .....	<a href="#">109</a> , <a href="#">5157</a>
<code>\mode_if_inner:</code> .....	1703	<code>\msg_info:nnxxx</code> .....	<a href="#">109</a> , <a href="#">5157</a> , 5256
<code>\mode_if_inner:TF</code> .....	<a href="#">40</a> , <a href="#">1703</a>	<code>\msg_kernel_bug:x</code> .....	15,
<code>\mode_if_inner_p:</code> .....	<a href="#">40</a> , <a href="#">1703</a>	..... <a href="#">113</a> , <a href="#">1107</a> , 1107, 1117, 1133, 1335,	
<code>\mode_if_math:</code> .....	1707	3497, 4290, 4457, 4476, <a href="#">5283</a> , 5283	
<code>\mode_if_math:TF</code> .....	<a href="#">40</a> , <a href="#">1707</a> , 2885	<code>\msg_kernel_classes_new:n</code> .....	
<code>\mode_if_math_p:</code> .....	<a href="#">40</a> , <a href="#">1707</a>	.. <a href="#">5198</a> , 5198, 5230, 5250, 5254, 5258	
<code>\mode_if_vertical:</code> .....	1695	<code>\msg_kernel_error:nn</code> ...	<a href="#">112</a> , 5076, <a href="#">5231</a>
<code>\mode_if_vertical:TF</code> .....	<a href="#">39</a> , <a href="#">1695</a>	<code>\msg_kernel_error:nnx</code> .....	
<code>\mode_if_vertical_p:</code> .....	<a href="#">39</a> , <a href="#">1695</a>	... <a href="#">112</a> , 5082, <a href="#">5231</a> , 5771, 5895, 5949	
<code>\month</code> .....	367	<code>\msg_kernel_error:nnxx</code> ...	<a href="#">112</a> , 5089,
<code>\moveleft</code> .....	317	<a href="#">5231</a> , 5757, 5831, 5843, 5857, 5963	
<code>\moveright</code> .....	318	<code>\msg_kernel_error:nnxxx</code> .....	<a href="#">112</a> , <a href="#">5231</a>
<code>\msg_class_new:nn</code> <a href="#">108</a> , <a href="#">5046</a> , 5046, 5122,		<code>\msg_kernel_error:nnxxx</code> <a href="#">112</a> , <a href="#">5231</a> , 5231	
<a href="#">5133</a> , 5150, 5157, 5164, 5170, 5176		<code>\msg_kernel_fatal:nn</code> .....	<a href="#">112</a> , <a href="#">5218</a>
<code>\msg_class_set:nn</code> ..	<a href="#">108</a> , <a href="#">5046</a> , 5049, 5051	<code>\msg_kernel_fatal:nnx</code> .....	<a href="#">112</a> , <a href="#">5218</a>
<code>\msg_direct_interrupt:n</code> .....	<a href="#">4987</a>	<code>\msg_kernel_fatal:nnxx</code> .....	<a href="#">112</a> , <a href="#">5218</a>
<code>\msg_direct_interrupt:xxxx</code> <a href="#">111</a> , <a href="#">4987</a> ,		<code>\msg_kernel_fatal:nnxxx</code> .....	<a href="#">112</a> , <a href="#">5218</a>
<a href="#">4994</a> , 5123, 5134, 5219, 5232, 5284		<code>\msg_kernel_fatal:nnxxx</code> <a href="#">112</a> , <a href="#">5218</a> , 5218	

<code>\msg_kernel_info:nn</code> .....	<a href="#">113</a> , <a href="#">5251</a>	<code>\msg_two_spaces:</code> .....	
<code>\msg_kernel_info:nnx</code> .....	<a href="#">113</a> , <a href="#">5251</a>		<a href="#">111</a> , <a href="#">4949</a> , <a href="#">4950</a> , <a href="#">4952</a> , <a href="#">5155</a> , <a href="#">5162</a> , <a href="#">6123</a>
<code>\msg_kernel_info:nnxx</code> .....	<a href="#">113</a> , <a href="#">5251</a>	<code>\msg_use:nnnnxxxx</code> .....	<a href="#">5054</a> , <a href="#">5069</a> , <a href="#">5069</a>
<code>\msg_kernel_info:nnxxx</code> .....	<a href="#">113</a> , <a href="#">5251</a>	<code>\msg_use_aux:nn</code> .....	<a href="#">5100</a> , <a href="#">5103</a> , <a href="#">5103</a>
<code>\msg_kernel_info:nnxxxx</code> .....	<a href="#">113</a> , <a href="#">5251</a> , <a href="#">5255</a>	<code>\msg_use_aux:nnn</code> .....	<a href="#">5087</a> , <a href="#">5094</a> , <a href="#">5094</a>
<code>\msg_kernel_new:nnn</code> ....	<a href="#">112</a> , <a href="#">5186</a> , <a href="#">5189</a>	<code>\msg_use_code:</code> .....	<a href="#">5070</a> , <a href="#">5092</a> , <a href="#">5092</a> , <a href="#">5110</a> , <a href="#">5117</a>
<code>\msg_kernel_new:nnnn</code> .....	<a href="#">112</a> , <a href="#">5186</a> , <a href="#">5186</a> , <a href="#">5259</a> , <a href="#">5267</a> , <a href="#">5275</a> , <a href="#">6099</a> , <a href="#">6109</a> , <a href="#">6118</a> , <a href="#">6126</a> , <a href="#">6134</a> , <a href="#">6140</a> , <a href="#">6148</a> , <a href="#">6155</a>	<code>\msg_use_loop:</code> .....	<a href="#">5092</a>
<code>\msg_kernel_set:nnn</code> ....	<a href="#">112</a> , <a href="#">5186</a> , <a href="#">5195</a>	<code>\msg_use_loop:n</code> .....	<a href="#">5074</a> , <a href="#">5093</a> , <a href="#">5119</a>
<code>\msg_kernel_set:nnnn</code> ...	<a href="#">112</a> , <a href="#">5186</a> , <a href="#">5192</a>	<code>\msg_use_loop_check:nn</code> .....	<a href="#">5098</a> , <a href="#">5105</a> , <a href="#">5108</a> , <a href="#">5114</a> , <a href="#">5114</a>
<code>\msg_kernel_warning:nn</code> .....	<a href="#">112</a> , <a href="#">5251</a>	<code>\msg_warning:nn</code> .....	<a href="#">109</a> , <a href="#">5150</a>
<code>\msg_kernel_warning:nnx</code> .....	<a href="#">112</a> , <a href="#">5251</a>	<code>\msg_warning:nnx</code> .....	<a href="#">109</a> , <a href="#">5150</a>
<code>\msg_kernel_warning:nnxx</code> .....	<a href="#">112</a> , <a href="#">5251</a>	<code>\msg_warning:nnxx</code> .....	<a href="#">109</a> , <a href="#">5150</a>
<code>\msg_kernel_warning:nnxxx</code> .....	<a href="#">112</a> , <a href="#">5251</a>	<code>\msg_warning:nnxxx</code> .....	<a href="#">109</a> , <a href="#">5150</a>
<code>\msg_kernel_warning:nnxxxx</code> .....	<a href="#">112</a> , <a href="#">5251</a>	<code>\msg_warning:nnxxxx</code> ....	<a href="#">109</a> , <a href="#">5150</a> , <a href="#">5252</a>
<code>\msg_line_context:</code> .....	<a href="#">110</a> , <a href="#">4939</a> , <a href="#">4942</a>	<code>\mskip</code> .....	<a href="#">178</a>
<code>\msg_line_number:</code> .	<a href="#">110</a> , <a href="#">4939</a> , <a href="#">4939</a> , <a href="#">4945</a>	<code>\muexpr</code> .....	<a href="#">427</a>
<code>\msg_log:nn</code> .....	<a href="#">109</a> , <a href="#">5164</a>	<code>\multiply</code> .....	<a href="#">79</a>
<code>\msg_log:nnx</code> .....	<a href="#">109</a> , <a href="#">5164</a>	<code>\muskip</code> .....	<a href="#">375</a>
<code>\msg_log:nnxx</code> .....	<a href="#">109</a> , <a href="#">5164</a>	<code>\muskip_add:Nn</code> .....	
<code>\msg_log:nnxxx</code> .....	<a href="#">109</a> , <a href="#">5164</a>		<a href="#">71</a> , <a href="#">3466</a> , <a href="#">3468</a> , <a href="#">3469</a> , <a href="#">6264</a> , <a href="#">6272</a>
<code>\msg_log:nnxxxx</code> .....	<a href="#">109</a> , <a href="#">5164</a>	<code>\muskip_gadd:Nn</code> .....	<a href="#">71</a> , <a href="#">3466</a> , <a href="#">3469</a> , <a href="#">6268</a> , <a href="#">6276</a>
<code>\msg_new:nnn</code> .....	<a href="#">108</a> , <a href="#">5034</a> , <a href="#">5037</a> , <a href="#">5190</a>	<code>\muskip_gset:Nn</code> ....	<a href="#">71</a> , <a href="#">3466</a> , <a href="#">3467</a> , <a href="#">6260</a>
<code>\msg_new:nnnn</code> .....	<a href="#">108</a> , <a href="#">5034</a> , <a href="#">5034</a> , <a href="#">5187</a>	<code>\muskip_gsub:Nn</code> .....	<a href="#">71</a> , <a href="#">3466</a> , <a href="#">3471</a>
<code>\msg_newline:</code> .....	<a href="#">111</a> , <a href="#">4908</a> , <a href="#">4919</a> , <a href="#">4947</a> , <a href="#">4947</a> , <a href="#">4996</a> , <a href="#">4999</a> , <a href="#">5003</a> , <a href="#">5022</a> , <a href="#">5024</a> , <a href="#">5029</a> , <a href="#">5031</a> , <a href="#">5135</a> , <a href="#">5233</a>	<code>\muskip_new:N</code> .....	
<code>\msg_none:nn</code> .....	<a href="#">110</a> , <a href="#">5176</a>		<a href="#">71</a> , <a href="#">3455</a> , <a href="#">3457</a> , <a href="#">3461</a> , <a href="#">6182</a> – <a href="#">6184</a>
<code>\msg_none:nnx</code> .....	<a href="#">110</a> , <a href="#">5176</a>	<code>\muskip_new_l:N</code> .....	<a href="#">3458</a>
<code>\msg_none:nnxx</code> .....	<a href="#">110</a> , <a href="#">5176</a>	<code>\muskip_set:Nn</code> .	<a href="#">71</a> , <a href="#">3466</a> , <a href="#">3466</a> , <a href="#">3467</a> , <a href="#">6256</a>
<code>\msg_none:nnxxx</code> .....	<a href="#">110</a> , <a href="#">5176</a>	<code>\muskip_sub:Nn</code> .....	<a href="#">71</a> , <a href="#">3466</a> , <a href="#">3470</a> , <a href="#">3471</a>
<code>\msg_none:nnxxxx</code> .....	<a href="#">110</a> , <a href="#">5176</a>	<code>\muskip_use:N</code> .....	<a href="#">71</a> , <a href="#">3472</a> , <a href="#">3472</a>
<code>\msg_redirect_class:nn</code> .	<a href="#">110</a> , <a href="#">5177</a> , <a href="#">5177</a>	<code>\muskipdef</code> .....	<a href="#">73</a>
<code>\msg_redirect_module:nnn</code> .	<a href="#">110</a> , <a href="#">5180</a> , <a href="#">5180</a>	<code>\mutoglu</code> .....	<a href="#">433</a>
<code>\msg_redirect_name:nnn</code> .	<a href="#">110</a> , <a href="#">5183</a> , <a href="#">5183</a>		
<code>\msg_set:nnn</code> .....	<a href="#">108</a> , <a href="#">5034</a> , <a href="#">5043</a> , <a href="#">5196</a>		
<code>\msg_set:nnnn</code> .....	<a href="#">108</a> , <a href="#">5034</a> , <a href="#">5040</a> , <a href="#">5193</a>		
<code>\msg_space:</code> .....	<a href="#">111</a> , <a href="#">4944</a> , <a href="#">4949</a> , <a href="#">4949</a> , <a href="#">4950</a> , <a href="#">4997</a> , <a href="#">5023</a> , <a href="#">5030</a> , <a href="#">5126</a> , <a href="#">5129</a> , <a href="#">5137</a> , <a href="#">5140</a> , <a href="#">5152</a> , <a href="#">5159</a> , <a href="#">5222</a> , <a href="#">5226</a> , <a href="#">5235</a> , <a href="#">5239</a> , <a href="#">6121</a>		
<code>\msg_trace:nn</code> .....	<a href="#">109</a> , <a href="#">5170</a>		
<code>\msg_trace:nnx</code> .....	<a href="#">109</a> , <a href="#">5170</a>		
<code>\msg_trace:nnxx</code> .....	<a href="#">109</a> , <a href="#">5170</a>		
<code>\msg_trace:nnxxx</code> .....	<a href="#">109</a> , <a href="#">5170</a>		
<code>\msg_trace:nnxxxx</code> .....	<a href="#">109</a> , <a href="#">5170</a>		
<code>\msg_two_newlines:</code> .....	<a href="#">111</a> , <a href="#">4917</a> , <a href="#">4947</a> , <a href="#">4948</a> , <a href="#">5004</a> , <a href="#">5124</a> , <a href="#">5220</a>		

## N

<code>\n</code> .....	<a href="#">2400</a>
<code>\name_pop_stack:w</code> .....	<a href="#">698</a> , <a href="#">709</a> , <a href="#">728</a>
<code>\name_primitive:NN</code> .....	<a href="#">57</a> , <a href="#">61</a> – <a href="#">451</a> , <a href="#">453</a> – <a href="#">473</a> , <a href="#">475</a> – <a href="#">481</a> , <a href="#">483</a> – <a href="#">486</a> , <a href="#">488</a> – <a href="#">509</a> , <a href="#">511</a> – <a href="#">522</a> , <a href="#">524</a> – <a href="#">554</a> , <a href="#">557</a>
<code>\name_tmp:</code> .....	<a href="#">728</a>
<code>\name_undefine:N</code> ....	<a href="#">43</a> , <a href="#">49</a> , <a href="#">52</a> , <a href="#">59</a> , <a href="#">697</a>
<code>\NeedsTeXFormat</code> .....	<a href="#">720</a>
<code>\newbox</code> .....	<a href="#">5306</a>
<code>\newcount</code> .....	<a href="#">2740</a>
<code>\newdimen</code> .....	<a href="#">3403</a>
<code>\newif</code> .....	<a href="#">6580</a>
<code>\newlinechar</code> .....	<a href="#">129</a>
<code>\newmuskip</code> .....	<a href="#">3463</a>
<code>\newread</code> .....	<a href="#">4863</a>
<code>\newskip</code> .....	<a href="#">3287</a>

\newtoks	4113		
\newwrite	4813		
\noalign	97		
\noboundary	232		
\noexpand	32, 90		
\noindent	258		
\nolimits	212		
\nonscript	192		
\nonstopmode	155		
\nulldelimiter space	225		
\nullfont	343		
\num_add:cn	60, 3100		
\num_add:Nn	60, 3076, 3077, 3100, 3100–3102		
\num_decr:c	60, 3080		
\num_decr:N	60, 3076, 3077, 3081		
\num_elt_count:n	61, 3108, 3108, 3922, 3928		
\num_elt_count_prop:Nn	61, 3108, 3109		
\num_gadd:cn	60, 3100		
\num_gadd:Nn	60, 3078, 3079, 3100, 3102, 3103		
\num_gdecr:c	60, 3080		
\num_gdecr:N	60, 3076, 3079, 3083		
\num_gincr:c	59, 3080		
\num_gincr:N	59, 3076, 3078, 3082		
\num_gset:cn	60, 3090		
\num_gset:Nn	60, 3085, 3090, 3094, 3095		
\num_gset_eq:cc	60, 3098		
\num_gset_eq:cN	60, 3098		
\num_gset_eq:Nc	60, 3098		
\num_gset_eq:NN	60, 3098, 3098, 3099		
\num_gzero:c	60, 3084		
\num_gzero:N	60, 3084, 3085, 3087		
\num_incr:c	59, 3080		
\num_incr:N	59, 3076, 3076, 3080		
\num_new:c	59, 3088		
\num_new:N	59, 3088, 3088, 3089, 3110–3114		
\num_set:cn	60, 3090		
\num_set:Nn	60, 3084, 3090, 3090, 3093, 3094, 3100		
\num_set_eq:cc	60, 3096		
\num_set_eq:cN	60, 3096		
\num_set_eq:Nc	60, 3096		
\num_set_eq:NN	60, 3096, 3096, 3097		
\num_show:c	61, 3106, 3107		
\num_show:N	61, 3106, 3106		
\num_use:c	60, 3104, 3105		
\num_use:N	60, 3104, 3104		
\num_zero:c	60, 3084		
\num_zero:N	60, 3084, 3084, 3086		
\number	352, 5508		
\numexpr	424		
<b>O</b>			
\O	2404, 2495		
\omit	98		
\openin	124		
\openout	125		
\or	121		
\or:	8, 62, 64, 760, 762, 861, 1305, 1307, 1309, 1311, 1313, 1315, 1317, 1319, 1321, 2860–2864, 2869–2873, 2897–2905, 2910–2918, 3028–3036, 6368–6370, 6377–6379, 6394–6396, 6403–6405, 6451–6453, 6463–6465, 6489, 6495		
\outer	84		
\output	299		
\outputpenalty	309		
\over	186		
\overfullrule	337		
\overline	217		
\overwithdelims	187		
<b>P</b>			
\P	2404		
\p	2087		
\package_check_loaded_expl:	730, 756, 1444, 1692, 2105, 2208, 2726, 3071, 3120, 3276, 3477, 4105, 4258, 4431, 4660, 4805, 4889, 5294, 5428, 5541, 5710, 6166, 6642		
\package_provides:w	703, 704		
\PackageError	16, 732, 6525		
\pagedepth	301		
\pagediscards	442		
\pagefilllstretch	305		
\pagefillstretch	304		
\pagefilstretch	303		
\pagegoal	307		
\pagenumbering	5515, 5523		
\pageshrink	306		
\pagestretch	302		
\pagetotal	308		
\par	257, 696		
\parfillskip	288		
\parindent	281		
\parshape	273		
\parshapedimen	423		
\parshapeindent	421		
\parshapelength	422		
\parskip	280		
\patterns	363		



\pausing	150	\pdf_names:D	541
\pdf_adjustspacing:D	461	\pdf_noligatures:D	552
\pdf_annot:D	530	\pdf_normaldeviate:D	505
\pdf_catalog:D	540	\pdf_obj:D	524
\pdf_compresslevel:D	455	\pdf_optionalwaysusepdfpagebox:D	467
\pdf_creationdate:D	490	\pdf_optionpdfinclusionerrorlevel:D	469
\pdf_decimaldigits:D	456	\pdf_outline:D	533
\pdf_dest:D	534	\pdf_output:D	453
\pdf_destmargin:D	480	\pdf_pageattr:D	484
\pdf_efcode:D	463	\pdf_pageheight:D	478
\pdf_elapsedtime:D	520	\pdf_pageref:D	491
\pdf_endlink:D	532	\pdf_pageresources:D	485
\pdf_endthread:D	537	\pdf_pagesattr:D	483
\pdf_escapehex:D	501	\pdf_pagewidth:D	477
\pdf_escapename:D	500	\pdf_pkmode:D	486
\pdf_escapestring:D	499	\pdf_pkresolution:D	458
\pdf_filedump:D	509	\pdf_protrudechars:D	462
\pdf_filemoddate:D	507	\pdf_randomseed:D	521
\pdf_filesize:D	508	\pdf_refobj:D	525
\pdf_fontattr:D	544	\pdf_refxform:D	527
\pdf_fontexpand:D	546	\pdf_refximage:D	529
\pdf_fontname:D	493	\pdf_resettimer:D	550
\pdf_fontobjnum:D	494	\pdf_rightmarginkern:D	498
\pdf_fontsize:D	495	\pdf_rpcode:D	465
\pdf_forcepagebox:D	466	\pdf_savepos:D	538
\pdf_gamma:D	472	\pdf_setrandomseed:D	551
\pdf_horigin:D	475	\pdf_shellescape:D	522
\pdf_imageapplygamma:D	471	\pdf_startlink:D	531
\pdf_imagegamma:D	473	\pdf_startthread:D	536
\pdf_imagehicolor:D	470	\pdf_strcmp:D	503, 557, 2154, 2176, 3705
\pdf_imageresolution:D	457	\pdf_textrbanner:D	489
\pdf_includechars:D	496	\pdf_texrevision:D	488
\pdf_inclusionerrorlevel:D	468	\pdf_texversion:D	511
\pdf_info:D	539	\pdf_thread:D	535
\pdf_lastannot:D	516	\pdf_threadmargin:D	481
\pdf_lastdemerits:D	519	\pdf_tracingfonts:D	459
\pdf_lastobj:D	512	\pdf_trailer:D	545
\pdf_lastxform:D	513	\pdf_unescapehex:D	502
\pdf_lastximage:D	514	\pdf_uniformdeviate:D	504
\pdf_lastximagepages:D	515	\pdf_uniqueresname:D	460
\pdf_lastxpos:D	517	\pdf_vorigin:D	476
\pdf_lastypos:D	518	\pdf_xform:D	526
\pdf_leftmarginkern:D	497	\pdf_xformname:D	492
\pdf_linkmargin:D	479	\pdf_ximage:D	528
\pdf_literal:D	548	\pdfadjustspacing	461
\pdf_lpcode:D	464	\pdfannot	530
\pdf_mapfile:D	542	\pdfcatalog	540
\pdf_mapline:D	543	\pdfcompresslevel	455
\pdf_mdffivesum:D	506	\pdfcreationdate	490
\pdf_minorversion:D	454	\pdfdecimaldigits	456



<code>\pdfdest</code> .....	534	<code>\pdfpageref</code> .....	491
<code>\pdfdestmargin</code> .....	480	<code>\pdfpageresources</code> .....	485
<code>\pdfelapseddtime</code> .....	520	<code>\pdfpagesattr</code> .....	483
<code>\pdfendlink</code> .....	532	<code>\pdfpagewidth</code> .....	477
<code>\pdfendthread</code> .....	537	<code>\pdfpkmode</code> .....	486
<code>\pdfescapehex</code> .....	501	<code>\pdfpkresolution</code> .....	458
<code>\pdfescapename</code> .....	500	<code>\pdfprotrudechars</code> .....	462
<code>\pdfescapestring</code> .....	499	<code>\pdfrandomseed</code> .....	521
<code>\pdffiledump</code> .....	509	<code>\pdfrefobj</code> .....	525
<code>\pdffilemoddate</code> .....	507	<code>\pdfrefxform</code> .....	527
<code>\pdffilesize</code> .....	508	<code>\pdfrefximage</code> .....	529
<code>\pdffontattr</code> .....	544	<code>\pdfresettimer</code> .....	550
<code>\pdffontexpand</code> .....	546	<code>\pdfsavepos</code> .....	538
<code>\pdffontname</code> .....	493	<code>\pdfsetrandomseed</code> .....	551
<code>\pdffontobjnum</code> .....	494	<code>\pdfshellescape</code> .....	522
<code>\pdffontsize</code> .....	495	<code>\pdfstartlink</code> .....	531
<code>\pdfforcepagebox</code> .....	466	<code>\pdfstartthread</code> .....	536
<code>\pdfgamma</code> .....	472	<code>\pdfstrcmp</code> .....	503
<code>\pdfhorigin</code> .....	475	<code>\pdftexbanner</code> .....	489
<code>\pdfimageapplygamma</code> .....	471	<code>\pdftexrevision</code> .....	488
<code>\pdfimagegamma</code> .....	473	<code>\pdftexversion</code> .....	511
<code>\pdfimagehicolor</code> .....	470	<code>\pdfthread</code> .....	535
<code>\pdfimageresolution</code> .....	457	<code>\pdfthreadmargin</code> .....	481
<code>\pdfincludechars</code> .....	496	<code>\pdftracingfonts</code> .....	459
<code>\pdfinclusionerrorlevel</code> .....	468	<code>\pdftrailer</code> .....	545
<code>\pdfinfo</code> .....	539	<code>\pdfunescapehex</code> .....	502
<code>\pdflastannot</code> .....	516	<code>\pdfuniformdeviate</code> .....	504
<code>\pdflastdemerits</code> .....	519	<code>\pdfuniquestname</code> .....	460
<code>\pdflastobj</code> .....	512	<code>\pdfvorigin</code> .....	476
<code>\pdflastxform</code> .....	513	<code>\pdfxform</code> .....	526
<code>\pdflastximage</code> .....	514	<code>\pdfxformname</code> .....	492
<code>\pdflastximagepages</code> .....	515	<code>\pdfximage</code> .....	528
<code>\pdflastxpos</code> .....	517	<code>\peek_after:NN</code> .....	
<code>\pdflastypos</code> .....	518	..... 52, <a href="#">2563</a> , 2563, 2577, 2592, 2710	
<code>\pdflinkmargin</code> .....	479	<code>\peek_catcode:NTF</code> .....	53, <a href="#">2669</a>
<code>\pdfliteral</code> .....	548	<code>\peek_catcode_ignore_spaces:NTF</code> .....	53, <a href="#">2674</a>
<code>\pdfmapfile</code> .....	542	<code>\peek_catcode_remove:NTF</code> .....	53, <a href="#">2679</a>
<code>\pdfmapline</code> .....	543	<code>\peek_catcode_remove_ignore_spaces:NTF</code>	
<code>\pdfmdfivesum</code> .....	506	..... 53, <a href="#">2684</a>	
<code>\pdfminorversion</code> .....	454	<code>\peek_charcode:NTF</code> .....	53, <a href="#">2689</a>
<code>\pdfnames</code> .....	541	<code>\peek_charcode_ignore_spaces:NTF</code> ...	
<code>\pdfnoligatures</code> .....	552	..... 53, <a href="#">2694</a>	
<code>\pdfnormaldeviate</code> .....	505	<code>\peek_charcode_remove:NTF</code> .....	53, <a href="#">2699</a>
<code>\pdfobj</code> .....	524	<code>\peek_charcode_remove_ignore_spaces:NTF</code>	
<code>\pdfoptionalwaysusepdfpagebox</code> ....	467	..... 53, <a href="#">2704</a>	
<code>\pdfoptionpdfinclusionerrorlevel</code> ..	469	<code>\peek_def_aux:nnnn</code> .....	<a href="#">2635</a> , <a href="#">2635</a> ,
<code>\pdfoutline</code> .....	533	..... <a href="#">2649</a> , <a href="#">2654</a> , <a href="#">2659</a> , <a href="#">2664</a> , <a href="#">2669</a> , <a href="#">2674</a> ,	
<code>\pdfoutput</code> .....	453	..... <a href="#">2679</a> , <a href="#">2684</a> , <a href="#">2689</a> , <a href="#">2694</a> , <a href="#">2699</a> , <a href="#">2704</a>	
<code>\pdfpageattr</code> .....	484	<code>\peek_def_aux_ii:nnnnn</code> .....	
<code>\pdfpageheight</code> .....	478	..... <a href="#">2635</a> , <a href="#">2636</a> – <a href="#">2638</a> , <a href="#">2640</a>	

- \peek\_execute\_branches: . . . . . 2643, 2717
- \peek\_execute\_branches\_catcode: . . . . . 54, 2604, 2611, 2673, 2676, 2683, 2686
- \peek\_execute\_branches\_charcode: . . . . . 54, 2604, 2618, 2693, 2696, 2703, 2706
- \peek\_execute\_branches\_charcode\_aux:NN . . . . . 2604, 2625, 2627
- \peek\_execute\_branches\_meaning: . . . . . 54, 2604, 2604, 2653, 2656, 2663, 2666
- \peek\_gafter:NN . . . . . 52, 2563, 2564
- \peek\_ignore\_spaces\_aux: . . . . . 213, 2709, 2709, 2714
- \peek\_ignore\_spaces\_execute\_branches: . . . . . 213, 2658, 2668, 2678, 2688, 2698, 2708, 2709, 2710, 2712
- \peek\_meaning:NTF . . . . . 53, 2649
- \peek\_meaning\_ignore\_spaces:NTF . . . . . 53, 2654
- \peek\_meaning\_remove:NTF . . . . . 53, 2659
- \peek\_meaning\_remove\_ignore\_spaces:NTF . . . . . 53, 2664
- \peek\_tmp:w . . . . . 212, 2569, 2569, 2602, 2715
- \peek\_token\_generic:NNF . . . . . 2582
- \peek\_token\_generic:NNT . . . . . 2579
- \peek\_token\_generic:NNTF . . . . . 53, 2571, 2571, 2580, 2583
- \peek\_token\_remove\_generic:NNF . . . . . 2597
- \peek\_token\_remove\_generic:NNT . . . . . 2594
- \peek\_token\_remove\_generic:NNTF . . . . . 53, 2585, 2585, 2595, 2598
- \penalty . . . . . 358
- \postdisplaypenalty . . . . . 205
- \predisplaydirection . . . . . 449
- \predisdisplaypenalty . . . . . 204
- \predisplaysize . . . . . 203
- \pref\_global:D . . . . . 23, 795, 795, 1245, 1251, 2261, 2565, 2753, 2771, 2777, 2789, 2807, 2813, 3094, 3102, 3301, 3316, 3338, 3346, 3409, 3413, 3419, 3423, 3467, 3469, 3471, 3651, 4135, 4136, 4147, 4152, 4162, 4172, 4186, 4200, 4353, 4362, 4879, 5336, 5341, 5349, 5371, 5377, 5383, 5397, 5403, 5411, 6196, 6299, 6302, 6303, 6358, 6486, 6492, 6498, 6504
- \pref\_global\_chk: . . . . . 2751, 2769, 2775, 2805, 2811, 3299, 3314, 3336, 3344, 3649, 4161, 4171, 4185, 4199, 4350, 4359, 4878
- \pref\_long:D . . . . . 23, 795, 796, 801, 804, 813, 816, 821, 824, 833, 836
- \pref\_protected:D . . . . . 23, 795, 797, 800, 803, 806, 807, 809, 810, 813, 816, 827, 830, 833, 836
- \pretolerance . . . . . 284
- \prevdepth . . . . . 331
- \prevgraf . . . . . 290
- \prg\_case\_dim:nnn . . . . . 38, 1959, 1959
- \prg\_case\_dim\_aux:nnn . . . . . 1959, 1960, 1963, 1967
- \prg\_case\_int:nnn . . . . . 38, 1949, 1949
- \prg\_case\_int\_aux:nnn . . . . . 1949, 1950, 1953, 1957
- \prg\_case\_str:nnn . . . . . 39, 1969, 1969
- \prg\_case\_str\_aux:nnn . . . . . 1969, 1970, 1973, 1977
- \prg\_case\_tl:Nnn . . . . . 39, 1979, 1979
- \prg\_case\_tl\_aux:Nnn 1979, 1980, 1983, 1987
- \prg\_conditional\_form\_F:nnn . . . . . 1002
- \prg\_conditional\_form\_p:nnn . . . . . 999
- \prg\_conditional\_form\_T:nnn . . . . . 1001
- \prg\_conditional\_form\_TF:nnn . . . . . 1000
- \prg\_define\_quicksort:nnn 1990, 1990, 2065
- \prg\_do\_nothing: 15, 1282, 1282, 4015, 4019, 4035, 4038, 4122, 4151, 6314
- \prg\_end\_case:nw . . . . . 1956, 1966, 1976, 1986, 1989, 1989
- \prg\_generate\_conditional\_aux:nnNNnnnn . . . . . 877, 883, 889, 895, 901, 907, 914, 921, 933
- \prg\_generate\_conditional\_aux:nnw . . . . . 934, 938, 943
- \prg\_generate\_conditional\_parm\_aux:nnNNnnnn . . . . . 933
- \prg\_generate\_conditional\_parm\_aux:nw . . . . . 933
- \prg\_generate\_F\_form\_count:Nnnnn . . . . . 965, 980
- \prg\_generate\_F\_form\_parm:Nnnnn 945, 960
- \prg\_generate\_p\_form\_count:Nnnnn . . . . . 965, 965
- \prg\_generate\_p\_form\_parm:Nnnnn 945, 945
- \prg\_generate\_T\_form\_count:Nnnnn . . . . . 965, 975
- \prg\_generate\_T\_form\_parm:Nnnnn 945, 955
- \prg\_generate\_TF\_form\_count:Nnnnn . . . . . 965, 970
- \prg\_generate\_TF\_form\_parm:Nnnnn . . . . . 945, 950
- \prg\_get\_count\_aux:nn . . . . . 900, 906, 913, 920, 931, 931

- \prg\_get\_parm\_aux:nw ..... 876, 882, 888, 894, 931, 932
- \prg\_new\_conditional:Nnn ..... 34, 899, 905, 1695, 2147, 2153, 2162, 2171, 2175, 2184, 2323, 2327, 2331, 2335, 2339, 2343, 2347, 2351, 2355, 2359, 2363, 2367, 2371, 2375, 2379, 2386, 2389, 2408, 2415, 2422, 2433, 2444, 2455, 2466, 2473, 2480, 2520, 3377, 3439, 4227, 4234, 4293, 4464, 4766, 4870, 5313, 5316, 5327, 6651
- \prg\_new\_conditional:Npnn ..... .. 34, 875, 881, 1265, 1695, 3672, 3679, 3691, 3747, 4072, 4076, 4094
- \prg\_new\_eq\_conditional:Nnn ..... .. 34, 925, 928, 1695, 4285, 4286, 4452, 4453, 4460–4463, 4760–4765
- \prg\_new\_protected\_conditional:Nnn . ..... 34, 899, 919, 1695
- \prg\_new\_protected\_conditional:Npnn ..... 34, 875, 893, 1695, 3985, 3994
- \prg\_quicksort:n ..... 41, 2065
- \prg\_quicksort\_compare:nnTF ..... 41, 2066, 2067
- \prg\_quicksort\_function:n 41, 2066, 2066
- \prg\_replicate:nn ..... 41, 1724, 1724
- \prg\_replicate\_ ..... 1736
- \prg\_replicate\_aux:N 1724, 1730, 1731, 1734
- \prg\_replicate\_first\_aux:N ..... 1724, 1726, 1733
- \prg\_return\_false: ..... .. 34, 873, 874, 1043, 1048, 1060, 1065, 1083, 1086, 1144, 1146, 1163, 1267, 1276, 1280, 1423, 1695, 1697, 1701, 1705, 1709, 1858, 1935, 2149, 2157, 2167, 2172, 2179, 2189, 2325, 2329, 2333, 2337, 2341, 2345, 2349, 2353, 2357, 2361, 2365, 2369, 2373, 2377, 2384, 2388, 2392, 2394, 2413, 2420, 2424, 2431, 2435, 2442, 2453, 2457, 2464, 2471, 2478, 2486, 2523, 2530, 2535, 2542, 2544, 2546, 2548, 2550, 3148, 3152, 3156, 3160, 3164, 3168, 3172, 3177, 3242, 3246, 3381, 3441, 3666, 3673, 3681, 3695, 3751, 3765, 3772, 3779, 3786, 3793, 3800, 3807, 3814, 3821, 3828, 3835, 3842, 3849, 3856, 3987, 3996, 4074, 4079, 4097, 4228, 4236, 4296, 4467, 4770, 4871, 5314, 5317, 5328, 5873, 6681
- \prg\_return\_true: 34, 873, 873, 1046, 1062, 1081, 1143, 1163, 1267, 1275, 1279, 1423, 1695, 1697, 1701, 1705, 1709, 1858, 1935, 2149, 2157, 2167, 2172, 2179, 2189, 2325, 2329, 2333, 2337, 2341, 2345, 2349, 2353, 2357, 2361, 2365, 2369, 2373, 2377, 2384, 2388, 2392, 2413, 2420, 2431, 2442, 2453, 2464, 2471, 2478, 2486, 2552, 3148, 3152, 3156, 3160, 3164, 3168, 3172, 3177, 3242, 3246, 3381, 3441, 3666, 3673, 3681, 3695, 3751, 3765, 3772, 3779, 3786, 3793, 3800, 3807, 3814, 3821, 3828, 3835, 3842, 3849, 3856, 3987, 3996, 4074, 4079, 4097, 4228, 4236, 4296, 4467, 4770, 4871, 5314, 5317, 5328, 5871, 6657, 6679
- \prg\_set\_conditional:Nnn ..... 34, 899, 899, 1695, 5869
- \prg\_set\_conditional:Npnn ..... .. 34, 875, 875, 1041, 1052, 1073, 1138, 1147, 1155, 1274, 1278, 1421, 1695, 1695, 1699, 1703, 1707, 1857, 1933, 3132, 3174, 3240, 3244, 3664
- \prg\_set\_eq\_conditional:Nnn ..... 34, 925, 925, 1695
- \prg\_set\_eq\_conditional\_aux:NNNn ... 926, 929, 985, 985
- \prg\_set\_eq\_conditional\_aux:NNNw ... 985, 986, 988, 997
- \prg\_set\_protected\_conditional:Nnn . ..... 34, 899, 912, 1695
- \prg\_set\_protected\_conditional:Npnn ..... 34, 875, 887, 1695, 3761, 3768, 3775, 3782, 3789, 3796, 3803, 3810, 3817, 3824, 3831, 3838, 3845, 3852
- \prg\_stepwise\_function:nnnN ..... 41, 1764, 1764
- \prg\_stepwise\_function\_decr:nnnN ... 1764, 1766, 1779, 1783
- \prg\_stepwise\_function\_incr:nnnN ... 1764, 1767, 1770, 1774
- \prg\_stepwise\_inline:nnnn 41, 1788, 1789
- \prg\_stepwise\_inline\_decr:Nnnn .... 1793, 1807, 1811
- \prg\_stepwise\_inline\_decr:nnnn .. 1788
- \prg\_stepwise\_inline\_incr:Nnnn .... 1794, 1799, 1803
- \prg\_stepwise\_inline\_incr:nnnn .. 1788

<code>\prg_stepwise_variable:nnnNn</code> .....	<code>\prop_if_empty:Nc</code> .....	102, 4760
..... 41, 1815, 1815	<code>\prop_if_empty_p:c</code> .....	101, 4760
<code>\prg_stepwise_variable_decr:nnnNn</code> ..	<code>\prop_if_empty_p:N</code> .....	101, 4760
..... 1815, 1817, 1829, 1833	<code>\prop_if_eq:cc</code> .....	4765
<code>\prg_stepwise_variable_incr:nnnNn</code> ..	<code>\prop_if_eq:ccTF</code> .....	102, 4762
..... 1815, 1818, 1821, 1825	<code>\prop_if_eq:cN</code> .....	4763
<code>\prg_variable_get_scope:N</code> 42, 2068, 2073	<code>\prop_if_eq:cNTF</code> .....	102, 4762
<code>\prg_variable_get_scope_aux:w</code> .....	<code>\prop_if_eq:Nc</code> .....	4764
..... 2068, 2074, 2077	<code>\prop_if_eq:NcTF</code> .....	102, 4762
<code>\prg_variable_get_type:N</code> . 42, 2068, 2086	<code>\prop_if_eq:NN</code> .....	4762
<code>\prg_variable_get_type:w</code> .....	<code>\prop_if_eq:NNTF</code> .....	102, 4762
..... 2068	<code>\prop_if_eq_p:cc</code> .....	102, 4762
<code>\prg_variable_get_type_aux:w</code> 2090, 2094	<code>\prop_if_eq_p:cN</code> .....	102, 4762
<code>\ProcessOptions</code> .....	<code>\prop_if_eq_p:Nc</code> .....	102, 4762
..... 54	<code>\prop_if_eq_p:NN</code> .....	102, 4762
<code>\prop_clear:c</code> .....	<code>\prop_if_in:ccTF</code> .....	102, 4766
..... 99, 4666, 4667, 5052	<code>\prop_if_in:cnTF</code> ..	102, 4766, 5104, 5107
<code>\prop_clear:N</code> .....	<code>\prop_if_in:Nn</code> .....	4766
..... 99, 4666, 4666, 4722	<code>\prop_if_in:NnF</code> .....	4774
<code>\prop_del:Nn</code> .....	<code>\prop_if_in:NnT</code> .....	4773
..... 101, 4742, 4742, 4753	<code>\prop_if_in:NnTF</code> ..	102, 4766, 4772, 5097
<code>\prop_del:NV</code> .....	<code>\prop_if_in:NoTF</code> .....	102, 4766
..... 101, 4742	<code>\prop_if_in:NVTf</code> .....	102, 4766
<code>\prop_del_aux:w</code> 102, 4742, 4743, 4745, 4746	<code>\prop_if_in_aux:w</code> .	102, 4766, 4767, 4769
<code>\prop_display:c</code> .....	<code>\prop_map_break:</code> ..	101, 4781, 4797, 4797
..... 101, 4680	<code>\prop_map_function:cc</code> .....	101, 4775
<code>\prop_display:N</code> ... 101, 4680, 4680, 4696	<code>\prop_map_function:cN</code> .....	101, 4775
<code>\prop_gclear:c</code> .....	<code>\prop_map_function:Nc</code> ..	101, 4775, 4792
..... 99, 4666, 4669	<code>\prop_map_function:NN</code> 101, 4775, 4775, 4786	
<code>\prop_gclear:N</code> .....	<code>\prop_map_function_aux:w</code> .....	
..... 99, 4666, 4668, 4728	..... 103, 4775, 4776, 4779, 4784	
<code>\prop_gdel:Nn</code> .....	<code>\prop_map_inline:cn</code> .....	101, 4787
..... 101, 4742	..... 101, 4684, 4787, 4788, 4796	
<code>\prop_gdel:NV</code> .....	<code>\prop_new:c</code> .... 99, 4664, 4665, 5048, 5470	
..... 101, 4742	<code>\prop_new:N</code> .....	
<code>\prop_get:cnN</code> .....	..... 99, 4664, 4664, 4936, 4937, 5431, 5432	
..... 100, 4703, 5115	<code>\prop_put:cnn</code> .....	100, 4720, 5178, 5181
<code>\prop_get:cVN</code> .....	<code>\prop_put:Nnn</code> .	100, 4720, 4720, 4740, 5184
..... 100, 4703, 4703, 4707	<code>\prop_put:NnV</code> .....	100, 4720
<code>\prop_get:NVN</code> .....	<code>\prop_put:NVn</code> .....	100, 4720
..... 100, 4703	<code>\prop_put:NVV</code> .....	100, 4720
<code>\prop_get_aux:w</code> ... 102, 4703, 4704, 4706	<code>\prop_put_aux:w</code> 102, 4720, 4723, 4729, 4732	
<code>\prop_get_del_aux:w</code> 102, 4712, 4713, 4714	<code>\prop_put_if_new_aux:w</code> .....	
<code>\prop_get_gdel:NnN</code> .....	..... 102, 4756, 4757, 4758	
..... 100, 4712, 4712	<code>\prop_set_eq:cc</code> .....	100, 4670, 4673
<code>\prop_gget:cnN</code> .....	<code>\prop_set_eq:cN</code> .....	100, 4670, 4672
..... 100	<code>\prop_set_eq:Nc</code> .....	100, 4670, 4671
<code>\prop_gget:cVN</code> .....	<code>\prop_set_eq:NN</code> .....	100, 4670, 4670
..... 100	<code>\prop_show:c</code> .....	101, 4678, 4679
<code>\prop_gget:NnN</code> .... 100, 4708, 4708, 4711		
<code>\prop_gget:NVN</code> .....		
..... 100, 4708		
<code>\prop_gget_aux:w</code> .. 102, 4708, 4709, 4710		
<code>\prop_gput:ccx</code> .....		
..... 100, 4720, 5436		
<code>\prop_gput:cnn</code> .....		
..... 100, 4720		
<code>\prop_gput:Nnn</code> .....		
..... 100, 4720, 4726, 4741		
<code>\prop_gput:Nno</code> .....		
..... 100, 4720		
<code>\prop_gput:NnV</code> .....		
..... 100, 4720		
<code>\prop_gput:Nnx</code> .....		
..... 100, 4720		
<code>\prop_gput_if_new:Nnn</code> .. 100, 4756, 4756		
<code>\prop_gset_eq:cc</code> .....		
..... 100, 4670, 4677		
<code>\prop_gset_eq:cN</code> .....		
..... 100, 4670, 4676		
<code>\prop_gset_eq:Nc</code> .....		
..... 100, 4670, 4675		
<code>\prop_gset_eq:NN</code> .....		
..... 100, 4670, 4674		
<code>\prop_if_empty:c</code> .....		
..... 4761		
<code>\prop_if_empty:cTF</code> .....		
..... 102, 4760		
<code>\prop_if_empty:N</code> .....		
..... 4760		

`\prop_show:N` ..... 101, 4678, 4678  
`\prop_split_aux:Nnn` .....  
    103, 4697, 4697, 4704, 4709, 4713,  
    4721, 4727, 4743, 4745, 4757, 4767  
`\prop_tmp:w` ..... 4698, 4701,  
    4717, 4718, 4736, 4737, 4747–4750  
`\protect` ..... 734  
`\protected` ..... 451  
`\ProvidesClass` ..... 657  
`\ProvidesExplClass` ..... 6, 651, 656  
`\ProvidesExplFile` ..... 6, 651, 660  
`\ProvidesExplPackage` ..... 6,  
    651, 652, 754, 1442, 1690, 2103,  
    2206, 2724, 3069, 3118, 3274, 3475,  
    4103, 4256, 4429, 4658, 4803, 4887,  
    5292, 5426, 5539, 5708, 6164, 6640  
`\ProvidesFile` ..... 661  
`\ProvidesPackage` ..... 653, 700

**Q**

`\Q` ..... 5566  
`\q` ..... 1020, 1727, 1900  
`\q_error` ..... 45, 2112, 2112  
`\q_mark` ..... 45, 2112, 2113, 4180  
`\q_nil` ..... 45, 676, 680,  
    853, 856, 1006, 1012, 1020, 1022,  
    1029, 1031, 1294, 1298, 1912, 1914,  
    1993, 1997, 2075, 2077, 2088, 2090,  
    2094, 2109, 2111, 2118, 2130, 2146,  
    2172, 2177, 2187, 2380, 2382, 2410,  
    2412, 2417, 2419, 2427, 2430, 2438,  
    2441, 2449, 2452, 2460, 2463, 2468,  
    2470, 2475, 2477, 2482, 2485, 2498,  
    2504, 2510, 2516, 3045, 3138, 3146,  
    3150, 3154, 3158, 3162, 3166, 3170,  
    3680, 3692, 3694, 4060, 4062, 4064,  
    4068, 4069, 4073, 4078, 4082, 4096,  
    4377, 4491, 4498, 4777, 4780, 5447,  
    5454, 5567, 5574, 5582, 5592, 5597,  
    5605, 5612, 5622, 5628, 5629, 5639,  
    5645, 5650, 5663, 5668, 5672, 5675  
`\q_no_value` ..... 44, 1912, 2109,  
    2110, 2148, 2155, 2165, 3989, 3998,  
    4012, 4020, 4039, 4295, 4298, 4466,  
    4469, 4701, 4717, 4736, 4749, 4777,  
    5604, 5612, 5618, 5623, 5639, 5646  
`\q_prop` ..... 102, 4663, 4663,  
    4698, 4701, 4717, 4733, 4736, 4749,  
    4759, 4777, 4779, 5443, 5445, 5462

`\q_recursion_stop` .....  
    44, 855, 858, 936, 986, 1608,  
    1951, 1961, 1971, 1981, 1989, 2114,  
    2115, 3868, 3872, 3885, 3894, 3899,  
    3910, 4540, 4546, 4563, 4575, 4582  
`\q_recursion_tail` .....  
    44, 1951, 1961, 1971, 1981,  
    2114, 2114, 2118, 2123, 2130, 2138,  
    2146, 3868, 3872, 3885, 3894, 3899,  
    3910, 4540, 4546, 4563, 4575, 4582  
`\q_stop` ..... 44, 854, 857, 1993,  
    1997, 2059, 2109, 2109, 3134, 3136,  
    3138, 3140, 3986, 3989, 3995, 3998,  
    4008, 4020, 4028, 4035, 4039, 4181,  
    4190, 4294, 4298, 4305, 4307, 4313,  
    4316, 4338, 4340, 4377, 4465, 4469,  
    4485, 4487, 4491, 4493, 4698, 4701,  
    4777, 5574, 5640, 5899, 5901, 5906  
`\quark_if_nil:N` ..... 2171  
`\quark_if_nil:n` ..... 2175, 2184  
`\quark_if_nil:nF` ..... 2196, 2200  
`\quark_if_nil:NT` ..... 4371  
`\quark_if_nil:nT` . 2000, 2004, 2195, 2199  
`\quark_if_nil:NTF` 43, 2171, 3048, 4496, 5658  
`\quark_if_nil:nTF` ..... 43, 2008,  
    2017, 2026, 2035, 2174, 2194, 2198  
`\quark_if_nil:oF` ..... 5620  
`\quark_if_nil:oTF` ..... 43, 2174  
`\quark_if_nil:VTF` ..... 43, 2174  
`\quark_if_nil_p:N` ..... 43, 2171  
`\quark_if_nil_p:n` .. 43, 2174, 2193, 2197  
`\quark_if_nil_p:o` ..... 43, 2174  
`\quark_if_nil_p:V` ..... 43, 2174  
`\quark_if_no_value:N` ..... 2147  
`\quark_if_no_value:n` ..... 2153, 2162  
`\quark_if_no_value:NF` ..... 4716, 4748  
`\quark_if_no_value:nF` ..... 4009  
`\quark_if_no_value:NTF` .. 43, 1915, 2147  
`\quark_if_no_value:nTF` .....  
    43, 2147, 3987, 3996, 4029, 4770  
`\quark_if_no_value_p:N` ..... 43, 2147  
`\quark_if_no_value_p:n` ..... 43, 2147  
`\quark_if_recursion_tail_aux:w` ....  
    2118, 2130, 2146, 2146  
`\quark_if_recursion_tail_stop:N` ....  
    44, 2116, 2122, 3905, 4589  
`\quark_if_recursion_tail_stop:n` ....  
    44, 2116, 2116, 2127, 3875, 4550  
`\quark_if_recursion_tail_stop:o` 44, 2116

- `\quark_if_recursion_tail_stop_do:Nn` ..... 44, 1984, 2128, 2137  
`\quark_if_recursion_tail_stop_do:nn` ..... 44, 1954, 1964, 1974, 2128, 2128, 2145, 3913  
`\quark_if_recursion_tail_stop_do:on` ..... 44, 2128  
`\quark_new:N` ... 43, 2108, 2108–2115, 4663
- ### R
- `\R` ..... 2404, 2494  
`\radical` ..... 179  
`\raise` ..... 319  
`\ratio` ..... 132, 6191, 6568, 6572  
`\read` ..... 126  
`\readline` ..... 401  
`\real` ..... 132, 6190, 6568, 6573  
`\relax` .... 11, 23, 26–31, 34–39, 161, 709  
`\relpenalty` ..... 222  
`\RequirePackage` ..... 721  
`\reverse_if:N` ..... 8, 760, 765  
`\right` ..... 220  
`\righthyphenmin` ..... 276  
`\rightmargin` ..... 498  
`\rightskip` ..... 278  
`\romannumeral` ..... 353  
`\rptcode` ..... 465
- ### S
- `\S` ..... 2404  
`\savinghyphcodes` ..... 440  
`\savingvdiscards` ..... 441  
`\scan_align_safe_stop:` 40, 1708, 1714, 1714  
`\scan_stop:` ..... 25, 741, 791, 791, 989, 1014, 1139, 1143, 1144, 1152, 1154, 1156, 1159, 1163, 1720, 2387, 2505, 2511, 2517, 2942, 2943, 2960, 3115, 3307, 3359, 3391, 3392, 3416, 3421, 3437, 3466, 3468, 3470, 3934–3937, 4242, 4475, 4818, 4866, 4867, 4989, 5368, 5394, 6312, 6372, 6381, 6398, 6407, 6455, 6470  
`\scantokens` ..... 399  
`\scriptfont` ..... 345  
`\scriptscriptfont` ..... 346  
`\scriptscriptstyle` ..... 191  
`\scriptspace` ..... 231  
`\scriptstyle` ..... 190  
`\scrollmode` ..... 156  
`\secondoftwo` ..... 4, 12  
`\seq_clear:c` ..... 87, 4265, 4266  
`\seq_clear:N` ..... 87, 4265, 4265, 4397  
`\seq_clear_new:c` ..... 87, 4269, 4270  
`\seq_clear_new:N` ..... 87, 4269, 4269  
`\seq_display:c` ..... 90, 4322  
`\seq_display:N` ..... 90, 4322, 4322, 4336  
`\seq_elt:w` ..... 91, 4260, 4261, 4294, 4298, 4307, 4316, 4342, 4346, 4369, 4377, 4384, 4386, 4390, 4392  
`\seq_elt_end:` ..... 91, 4260, 4262, 4294, 4298, 4307, 4316, 4342, 4346, 4369, 4377, 4384, 4390  
`\seq_gclear:c` ..... 87, 4265, 4268  
`\seq_gclear:N` ..... 87, 4265, 4267  
`\seq_gclear_new:c` ..... 87, 4269, 4272  
`\seq_gclear_new:N` ..... 87, 4269, 4271  
`\seq_gconcat:ccc` ..... 88, 4281  
`\seq_gconcat:NNN` ... 88, 4281, 4281, 4284  
`\seq_get:cN` ..... 89, 4303, 4423  
`\seq_get:NN` ... 89, 4303, 4303, 4310, 4422  
`\seq_get_aux:w` ..... 91, 4303, 4305, 4307  
`\seq_gpop:cN` ..... 92, 4418  
`\seq_gpop:NN` ..... 92, 4418, 4419, 4421  
`\seq_gpush:cn` ..... 91, 4418  
`\seq_gpush:Nn` ..... 91, 4418, 4418, 4420  
`\seq_gpush:No` ..... 91, 4418  
`\seq_gpush:Nv` ..... 91, 4418  
`\seq_gpush:Nv` ..... 91, 4418  
`\seq_gput_left:cn` ..... 88, 4348  
`\seq_gput_left:co` ..... 88, 4348  
`\seq_gput_left:cV` ..... 88, 4348  
`\seq_gput_left:Nn` 88, 4348, 4348, 4366, 4418  
`\seq_gput_left:No` ..... 88, 4348  
`\seq_gput_left:Nv` ..... 88, 4348  
`\seq_gput_left:Nx` ..... 88, 4348  
`\seq_gput_right:cn` ..... 88, 4348  
`\seq_gput_right:co` ..... 88, 4348  
`\seq_gput_right:cV` ..... 88, 4348  
`\seq_gput_right:Nc` ..... 89, 4368  
`\seq_gput_right:Nn` ..... 88, 4348, 4357, 4367, 4368  
`\seq_gput_right:No` ..... 88, 4348  
`\seq_gput_right:Nv` ..... 88, 4348  
`\seq_gput_right:Nx` ..... 88, 4348  
`\seq_gremove_duplicates:N` 90, 4396, 4409  
`\seq_gset_eq:cc` ..... 87, 4277, 4280  
`\seq_gset_eq:cN` ..... 87, 4277, 4278  
`\seq_gset_eq:Nc` ..... 87, 4277, 4279  
`\seq_gset_eq:NN` ... 87, 4277, 4277, 4410  
`\seq_if_empty:c` ..... 4286

- \seq\_if\_empty:cTF ..... 90, [4285](#)
- \seq\_if\_empty:N ..... [4285](#)
- \seq\_if\_empty:NTF ..... 90, [4285](#)
- \seq\_if\_empty\_err:N .....  
..... 91, [4287](#), [4287](#), [4304](#), [4312](#)
- \seq\_if\_empty\_p:c ..... 90, [4285](#)
- \seq\_if\_empty\_p:N ..... 90, [4285](#)
- \seq\_if\_in:cnTF ..... 90, [4293](#)
- \seq\_if\_in:coTF ..... 90, [4293](#)
- \seq\_if\_in:cVTF ..... 90, [4293](#)
- \seq\_if\_in:cxTF ..... 90, [4293](#)
- \seq\_if\_in:Nn ..... [4293](#)
- \seq\_if\_in:NnF ..... [4302](#), [4402](#)
- \seq\_if\_in:NnT ..... [4301](#)
- \seq\_if\_in:NnTF ..... 90, [4293](#), [4300](#)
- \seq\_if\_in:NVTF ..... 90, [4293](#)
- \seq\_map\_break: .... 91, [4369](#), [4371](#), [4381](#)
- \seq\_map\_break:n ..... 91, [4369](#), [4382](#)
- \seq\_map\_function:cN ..... 89, [4383](#)
- \seq\_map\_function:NN .....  
..... 89, [4383](#), [4383](#), [4388](#), [4398](#)
- \seq\_map\_inline:cn ..... 89, [4389](#)
- \seq\_map\_inline:Nn .....  
..... 89, [4326](#), [4389](#), [4389](#), [4394](#)
- \seq\_map\_variable:cNn ..... 89, [4369](#)
- \seq\_map\_variable:NNn 89, [4369](#), [4375](#), [4379](#)
- \seq\_map\_variable\_aux:Nnw .....  
..... [4369](#), [4369](#), [4373](#), [4376](#)
- \seq\_new:c ..... 4, 87, [4263](#), [4264](#)
- \seq\_new:N .. 4, 87, [4263](#), [4263](#), [4395](#), [5724](#)
- \seq\_pop:cN ..... 92, [4412](#)
- \seq\_pop:NN 92, [4412](#), [4416](#), [4417](#), [5810](#), [5928](#)
- \seq\_pop\_aux:nnNN 91, [4311](#), [4311](#), [4416](#), [4419](#)
- \seq\_pop\_aux:w ..... 91, [4311](#), [4313](#), [4315](#)
- \seq\_push:cn ..... 91, [4412](#), [4415](#)
- \seq\_push:Nn ..... 91, [4412](#), [4412](#)
- \seq\_push:No ..... 91, [4412](#), [4414](#)
- \seq\_push:NV ... 91, [4412](#), [4413](#), [5807](#), [5925](#)
- \seq\_put\_aux:Nnn 91, [4337](#), [4337](#), [4342](#), [4346](#)
- \seq\_put\_aux:w ..... 91, [4337](#), [4338](#), [4340](#)
- \seq\_put\_left:cn ..... 88, [4341](#), [4415](#)
- \seq\_put\_left:co ..... 88, [4341](#)
- \seq\_put\_left:cV ..... 88, [4341](#)
- \seq\_put\_left:Nn .....  
..... 88, [4341](#), [4341](#), [4344](#), [4355](#), [4412](#)
- \seq\_put\_left:No ..... 88, [4341](#), [4414](#)
- \seq\_put\_left:NV ..... 88, [4341](#), [4413](#)
- \seq\_put\_left:Nx ..... 88, [4341](#)
- \seq\_put\_right:cn ..... 88, [4341](#)
- \seq\_put\_right:co ..... 88, [4341](#)
- \seq\_put\_right:cV ..... 88, [4341](#)
- \seq\_put\_right:Nn ..... 88, [4243](#),  
[4341](#), [4345](#), [4347](#), [4364](#), [4403](#), [5299](#)
- \seq\_put\_right:No ..... 88, [4341](#)
- \seq\_put\_right:NV ..... 88, [4341](#)
- \seq\_put\_right:Nx ..... 88, [4341](#)
- \seq\_remove\_duplicates:N . 90, [4396](#), [4406](#)
- \seq\_remove\_duplicates\_aux:n .....  
..... [4396](#), [4398](#), [4401](#)
- \seq\_remove\_duplicates\_aux:NN .....  
..... [4396](#), [4396](#), [4407](#), [4410](#)
- \seq\_set\_eq:cc ..... 87, [4273](#), [4276](#)
- \seq\_set\_eq:cN ..... 87, [4273](#), [4274](#)
- \seq\_set\_eq:Nc ..... 87, [4273](#), [4275](#)
- \seq\_set\_eq:NN ..... 87, [4273](#), [4273](#), [4407](#)
- \seq\_show:c ..... 90, [4320](#), [4321](#)
- \seq\_show:N ..... 90, [4320](#), [4320](#)
- \seq\_tmp:w ..... [4294](#), [4298](#)
- \seq\_top:cN ..... 92, [4422](#), [4423](#)
- \seq\_top:NN ..... 92, [4422](#), [4422](#)
- \setbox ..... 327
- \setcounter ..... 132, [6578](#), [6624](#), [6630](#)
- \setlabel ..... 5511, [5517](#), [5518](#),  
[5520](#), [5521](#), [5525](#), [5526](#), [5528](#), [5529](#)
- \setlanguage ..... 85
- \setlength ..... 132, [6574](#), [6574](#)
- \setname ..... 5502,  
[5517](#), [5518](#), [5520](#), [5521](#), [5525](#), [5528](#)
- \sfcode ..... 382
- \shipout ..... 292
- \show ..... 135
- \showbox ..... 137
- \showboxbreadth ..... 151
- \showboxdepth ..... 152
- \showgroups ..... 412
- \showifs ..... 413
- \showlists ..... 138
- \showMemUsage .....  
. 742, 751, 1439, 1687, 2100, 2203,  
[2721](#), [3066](#), [4100](#), [4253](#), [4426](#), [4655](#),  
[4800](#), [4884](#), [5423](#), [5486](#), [5705](#), [6637](#)
- \showthe ..... 136
- \showtokens ..... 400
- \skewchar ..... 349
- \skip ..... 373
- \skip@ ..... 3361
- \skip\_add:cn ..... 66, [3321](#)
- \skip\_add:Nn 66, [3321](#), [3321](#), [3327](#), [3339](#), [6243](#)
- \skip\_eval:n ..... 67, [3292](#),  
[3322](#), [3329](#), [3351](#), [3354](#), [3359](#), [3359](#)



\skip_gadd:cn	66, 3321	\str_if_eq:nn	1138
\skip_gadd:Nn	66, 3321, 3334, 3341, 6246	\str_if_eq_p:nn	11, 1071, 1138
.skip_gset:c	125	\str_if_eq_p_aux:w	1138, 1139, 1141, 1145, 1149
\skip_gset:cn	66, 3291		1155
.skip_gset:N	125	\str_if_eq_var:nf	1155
\skip_gset:Nn	66, 3291, 3297, 3305, 6240	\str_if_eq_var_p:nf	11, 1155, 2164, 2186
\skip_gsub:Nn	66, 3321, 3342, 6252	\str_if_eq_var_start:nnN	1155, 1156, 1158, 1160, 1162
\skip_gzero:c	66, 3306	\str_if_eq_var_stop:w	1155, 1159, 1162
\skip_gzero:N	66, 3306, 3312, 3320	\strcmp	555, 557
\skip_horizontal:c	67, 3349	\string	354
\skip_horizontal:N	67, 3349, 3349–3351		
\skip_horizontal:n	67, 3349, 3351		
\skip_if_infinite_glue:n	3377	T	
\skip_if_infinite_glue:nTF	67, 3377, 3384	\T	2398
\skip_if_infinite_glue_p:n	67, 3377	\t	2401
\skip_new:c	65, 3279	\tabskip	100
\skip_new:N	65, 3279, 3281, 3285, 3290, 3362–3366, 3368, 3370, 6179–6181	\tex_above:D	182
\skip_new_l:N	3282	\tex_abovedisplayshortskip:D	195
.skip_set:c	125	\tex_abovedisplayskip:D	196
\skip_set:cn	66, 3291	\tex_abovewithdelims:D	183
.skip_set:N	125	\tex_accent:D	233
\skip_set:Nn	66, 3291,	\tex_adjdemerits:D	270
	3291, 3302, 3304, 3369, 3371, 6237	\tex_advance:D	77, 2731, 3322, 3329, 3416, 3421, 3468, 3470
\skip_show:c	66, 3357, 3358	\tex_afterassignment:D	87, 2602, 2714, 6298
\skip_show:N	66, 3357, 3357, 3358	\tex_aftergroup:D	88, 794
\skip_split_finite_else_action:nnNN	67, 3383, 3383	\tex_atop:D	184
\skip_sub:Nn	66, 3321, 3328, 3347, 6249	\tex_atopwithdelims:D	185
\skip_use:c	66, 3355	\tex_badness:D	332
\skip_use:N	66, 3355, 3355, 3356	\tex_baselineskip:D	260
\skip_vertical:c	67, 3349	\tex_batchmode:D	153
\skip_vertical:N	67, 3349, 3352–3354	\tex_begingroup:D	91, 595, 701, 792
\skip_vertical:n	67, 3349, 3354	\tex_belowdisplayshortskip:D	197
\skip_zero:c	66, 3306	\tex_belowdisplayskip:D	198
\skip_zero:N	66, 3306, 3306, 3317, 3319	\tex_binoppenalty:D	221
\skipdef	72	\tex_botmark:D	168
\spacefactor	291	\tex_box:D	376, 5334, 5357
\spaceskip	286	\tex_boxmaxdepth:D	338
\span	99	\tex_brokenpenalty:D	295
\special	361, 549	\tex_catcode:D	380, 568–570, 572, 573, 577– 579, 581, 582, 587, 588, 591, 592, 596, 718, 1015, 1521, 1522, 2070, 2083, 2211, 2215, 2220, 3936, 3937
\splitbotmark	170	\tex_char:D	234
\splitbotmarks	396	\tex_chardef:D	69, 1003, 1004, 1099, 1100, 1922, 1924, 2960, 4810, 4861
\splitdiscards	443	\tex_cleaders:D	252
\splitfirstmark	169	\tex_closein:D	128, 4864
\splitfirstmarks	395	\tex_closeout:D	123, 4821
\splitmaxdepth	339		
\splittopskip	340		
\startrecording	5492, 5499		
\stepcounter	132, 6578, 6626, 6632		



<code>\tex_clubpenalty:D</code> .....	263	<code>\tex_everycr:D</code> .....	101
<code>\tex_copy:D</code> .....	320, 5359	<code>\tex_everydisplay:D</code> .....	202, 693
<code>\tex_count:D</code> .....	371	<code>\tex_everyhbox:D</code> .....	341
<code>\tex_countdef:D</code> .....		<code>\tex_everyjob:D</code> .....	370
.....	70, 1096, 2423, 2734, 2735, 2942	<code>\tex_everymath:D</code> .....	226, 692
<code>\tex_cr:D</code> .....	95	<code>\tex_everypar:D</code> .....	289
<code>\tex_crcr:D</code> .....	96	<code>\tex_everyvbox:D</code> .....	342
<code>\tex_csname:D</code> .....	158, 708, 723, 784	<code>\tex_exhyphenpenalty:D</code> .....	265
<code>\tex_day:D</code> .....	366	<code>\tex_expandafter:D</code> .....	89, 629, 631, 669, 672, 676, 707, 711, 722, 778, 1448
<code>\tex_deadcycles:D</code> .....	300	<code>\tex_fam:D</code> .....	81
<code>\tex_def:D</code> .....	65, 560, 566, 576, 585, 586, 590, 594, 599–601, 603, 605–611, 614, 618, 620–623, 627, 634, 636– 638, 642, 644–646, 652, 656, 660, 680, 681, 688, 698, 700, 704, 709, 715, 720, 721, 730, 787, 789, 790, 798	<code>\tex_fi:D</code> .....	120, 558, 559, 574, 583, 615, 632, 677, 686, 726, 727, 764
<code>\tex_defaulthyphenchar:D</code> .....	350	<code>\tex_finalhyphendemerits:D</code> .....	269
<code>\tex_defaultskewchar:D</code> .....	351	<code>\tex_firstmark:D</code> .....	167
<code>\tex_delcode:D</code> .....	381	<code>\tex_floatingpenalty:D</code> .....	314
<code>\tex_delimiter:D</code> .....	175	<code>\tex_font:D</code> .....	80
<code>\tex_delimiterfactor:D</code> .....	224	<code>\tex_fontdimen:D</code> .....	347
<code>\tex_delimitershortfall:D</code> .....	223	<code>\tex_fontname:D</code> .....	171
<code>\tex_dimen:D</code> .....	372	<code>\tex_futurelet:D</code> .....	76, 728, 2563, 2565
<code>\tex_dimendef:D</code> .....	71, 2445, 3397, 3398	<code>\tex_gdef:D</code> .....	67, 716, 717, 719, 818
<code>\tex_discretionary:D</code> .....	235	<code>\tex_global:D</code> .....	82, 713, 714, 795, 1924
<code>\tex_displayindent:D</code> .....	200	<code>\tex_globaldefs:D</code> .....	86
<code>\tex_displaylimits:D</code> .....	210	<code>\tex_halign:D</code> .....	93
<code>\tex_displaystyle:D</code> .....	188	<code>\tex_hangafter:D</code> .....	271
<code>\tex_displaywidowpenalty:D</code> .....	199	<code>\tex_hangindent:D</code> .....	272
<code>\tex_displaywidth:D</code> .....	201	<code>\tex_hbadness:D</code> .....	333
<code>\tex_divide:D</code> .....	78	<code>\tex_hbox:D</code> .....	
<code>\tex_doublehyphendemerits:D</code> .....	268	.....	328, 5394, 5395, 5400, 5406, 5415, 5416
<code>\tex_dp:D</code> .....	379, 5352	<code>\tex_hfil:D</code> .....	236
<code>\tex_dump:D</code> .....	362	<code>\tex_hfill:D</code> .....	238
<code>\tex_edef:D</code> ...	66, 563, 664, 666, 671, 799	<code>\tex_hfilneg:D</code> .....	237
<code>\tex_else:D</code> .....		<code>\tex_hfuzz:D</code> .....	335
.....	119, 562, 613, 630, 675, 684, 699, 763	<code>\tex_hoffset:D</code> .....	310
<code>\tex_emergencystretch:D</code> .....	283	<code>\tex_holdinginserts:D</code> .....	313
<code>\tex_end:D</code> .....	157, 691, 5131, 5228	<code>\tex_hruler:D</code> .....	249
<code>\tex_endcsname:D</code> .....	159, 708, 723, 785	<code>\tex_hsize:D</code> .....	274
<code>\tex_endgroup:D</code> ...	92, 604, 619, 705, 793	<code>\tex_hskip:D</code> .....	239, 3349
<code>\tex_endinput:D</code> .....	131	<code>\tex_hss:D</code> .....	240
<code>\tex_endlinechar:D</code> .....		<code>\tex_ht:D</code> .....	378, 5351
.....	173, 571, 580, 3945, 3961, 3971, 3979	<code>\tex_hyphen:D</code> .....	63, 695
<code>\tex_eqno:D</code> .....	193	<code>\tex_hyphenation:D</code> .....	364
<code>\tex_errhelp:D</code> .....	139, 5000	<code>\tex_hyphenchar:D</code> .....	348
<code>\tex_errmessage:D</code> ..	133, 744, 1109, 5002	<code>\tex_hyphenpenalty:D</code> .....	266
<code>\tex_errorcontextlines:D</code> .....	140, 4892	<code>\tex_if:D</code> .....	102, 673, 766, 769
<code>\tex_errorstopmode:D</code> .....	154	<code>\tex_ifcase:D</code> .....	103, 1303, 3075, 3128
<code>\tex_escapechar:D</code> .....	172	<code>\tex_ifcat:D</code> .....	104, 770
		<code>\tex_ifdim:D</code> .....	107, 3438
		<code>\tex_ifeof:D</code> .....	108, 4869, 4871
		<code>\tex_iffalse:D</code> .....	113, 761

<code>\tex_ifhbox:D</code> . . . . .	109, 5310, 5314	<code>\tex_mathbin:D</code> . . . . .	206
<code>\tex_ifhmode:D</code> . . . . .	115, 773	<code>\tex_mathchar:D</code> . . . . .	177
<code>\tex_ifinner:D</code> . . . . .	118, 775	<code>\tex_mathchardef:D</code> . . . . .	
<code>\tex_ifmmode:D</code> . . . . .	116, 772	74, 2936, 3115, 5300, 5301	
<code>\tex_ifnum:D</code> . . . . .		<code>\tex_mathchoice:D</code> . . . . .	174
. . . 105, 1074, 1080, 3074, 3126, 3749		<code>\tex_mathclose:D</code> . . . . .	207
<code>\tex_ifodd:D</code> . . . . .		<code>\tex_mathcode:D</code> 385, 2257, 2261, 2265, 2269	
. . . 106, 561, 565, 682, 767, 768, 3127		<code>\tex_mathinner:D</code> . . . . .	208
<code>\tex_iftrue:D</code> . . . . .	114, 760	<code>\tex_mathop:D</code> . . . . .	209
<code>\tex_ifvbox:D</code> . . . . .	110, 5311, 5317	<code>\tex_mathopen:D</code> . . . . .	213
<code>\tex_ifvmode:D</code> . . . . .	117, 774	<code>\tex_mathord:D</code> . . . . .	214
<code>\tex_ifvoid:D</code> . . . . .	111, 5312, 5328	<code>\tex_mathpunct:D</code> . . . . .	215
<code>\tex_ifx:D</code> . . . 112, 602, 628, 697, 722, 771		<code>\tex_mathrel:D</code> . . . . .	216
<code>\tex_ignorespaces:D</code> . . . . .	160	<code>\tex_mathsurround:D</code> . . . . .	227
<code>\tex_immediate:D</code> . . . . .	122, 639,	<code>\tex_maxdeadcycles:D</code> . . . . .	297
647, 706, 1102, 1105, 4818, 4821, 4826		<code>\tex_maxdepth:D</code> . . . . .	298
<code>\tex_indent:D</code> . . . . .	256	<code>\tex_meaning:D</code> . . . . .	357, 782, 786
<code>\tex_input:D</code> . . . 130, 689, 725, 6734, 6738		<code>\tex_medmskip:D</code> . . . . .	228
<code>\tex_inputlineno:D</code> . . 132, 1126, 1631, 4940		<code>\tex_message:D</code> . . . . .	134, 747
<code>\tex_insert:D</code> . . . . .	312	<code>\tex_mkern:D</code> . . . . .	181
<code>\tex_insertpenalties:D</code> . . . . .	315	<code>\tex_month:D</code> . . . . .	367
<code>\tex_interlinepenalty:D</code> . . . . .	294	<code>\tex_moveleft:D</code> . . . . .	317, 5343
<code>\tex_italiccor:D</code> . . . . .	62, 694	<code>\tex_moveright:D</code> . . . . .	318, 5344
<code>\tex_jobname:D</code> . . . . .	369, 3654	<code>\tex_mskip:D</code> . . . . .	178
<code>\tex_kern:D</code> . . . . .	247	<code>\tex_multiply:D</code> . . . . .	79
<code>\tex_language:D</code> . . . . .	164	<code>\tex_muskip:D</code> . . . . .	375
<code>\tex_lastbox:D</code> . . . . .	321, 5338	<code>\tex_muskipdef:D</code> . . . . .	73, 3457, 3458
<code>\tex_lastkern:D</code> . . . . .	254	<code>\tex_newlinechar:D</code> . . . . .	129, 4839
<code>\tex_lastpenalty:D</code> . . . . .	360	<code>\tex_noalign:D</code> . . . . .	97
<code>\tex_lastskip:D</code> . . . . .	255	<code>\tex_noboundary:D</code> . . . . .	232
<code>\tex_lccode:D</code> . . . . .	383, 1014, 2069,	<code>\tex_noexpand:D</code> . . . . .	90, 574, 779, 1449
2082, 2273, 2277, 2280, 3934, 3935		<code>\tex_noindent:D</code> . . . . .	258
<code>\tex_leaders:D</code> . . . . .	251	<code>\tex_nolimits:D</code> . . . . .	212
<code>\tex_left:D</code> . . . . .	219	<code>\tex_nonscript:D</code> . . . . .	192
<code>\tex_lefthyphenmin:D</code> . . . . .	275	<code>\tex_nonstopmode:D</code> . . . . .	155
<code>\tex_leftskip:D</code> . . . . .	277	<code>\tex_nulldelimiterspace:D</code> . . . . .	225
<code>\tex_leqno:D</code> . . . . .	194	<code>\tex_nullfont:D</code> . . . . .	343
<code>\tex_let:D</code> . . . . .	40,	<code>\tex_number:D</code> . . 352, 1156, 1892, 1895,	
44, 50, 58, 64, 689–696, 712–714, 759		1897, 2730, 3091, 3123, 6468, 6469	
<code>\tex_limits:D</code> . . . . .	211	<code>\tex_omit:D</code> . . . . .	98
<code>\tex_linepenalty:D</code> . . . . .	267	<code>\tex_openin:D</code> . . . . .	124, 4867
<code>\tex_lineskip:D</code> . . . . .	261	<code>\tex_openout:D</code> . . . . .	125, 4818
<code>\tex_lineskiplimit:D</code> . . . . .	262	<code>\tex_or:D</code> . . . . .	121, 762
<code>\tex_long:D</code> . . . . .	83, 796	<code>\tex_outer:D</code> . . . . .	84
<code>\tex_looseness:D</code> . . . . .	279	<code>\tex_output:D</code> . . . . .	299
<code>\tex_lower:D</code> . . . . .	316, 5346	<code>\tex_outputpenalty:D</code> . . . . .	309
<code>\tex_lowercase:D</code> . . . . .	355, 1016, 3860	<code>\tex_over:D</code> . . . . .	186
<code>\tex_mag:D</code> . . . . .	163	<code>\tex_overfullrule:D</code> . . . . .	337
<code>\tex_mark:D</code> . . . . .	165	<code>\tex_overline:D</code> . . . . .	217
<code>\tex_mathaccent:D</code> . . . . .	176	<code>\tex_overwithdelims:D</code> . . . . .	187

<code>\tex_pagedepth:D</code> .....	301	<code>\tex_showbox:D</code> .....	137, 5361
<code>\tex_pagefillllstretch:D</code> .....	305	<code>\tex_showboxbreadth:D</code> .....	151
<code>\tex_pagefillstretch:D</code> .....	304	<code>\tex_showboxdepth:D</code> .....	152
<code>\tex_pagefilstretch:D</code> .....	303	<code>\tex_showlists:D</code> .....	138
<code>\tex_pagegoal:D</code> .....	307	<code>\tex_showthe:D</code> .	136, 2220, 2269, 2280, 2290, 2301, 2821, 3357, 3427, 4177
<code>\tex_pageshrink:D</code> .....	306	<code>\tex_skewchar:D</code> .....	349
<code>\tex_pagestretch:D</code> .....	302	<code>\tex_skip:D</code> .....	373
<code>\tex_pagetotal:D</code> .....	308	<code>\tex_skipdef:D</code> .	72, 2434, 3281, 3282, 3361
<code>\tex_par:D</code> .....	257, 696	<code>\tex_space:D</code> .....	61
<code>\tex_parfillskip:D</code> .....	288	<code>\tex_spacefactor:D</code> .....	291
<code>\tex_parindent:D</code> .....	281	<code>\tex_spaceskip:D</code> .....	286
<code>\tex_parshape:D</code> .....	273	<code>\tex_span:D</code> .....	99
<code>\tex_parskip:D</code> .....	280	<code>\tex_special:D</code> .....	361
<code>\tex_patterns:D</code> .....	363	<code>\tex_splitbotmark:D</code> .....	170
<code>\tex_pausing:D</code> .....	150	<code>\tex_splitfirstmark:D</code> .....	169
<code>\tex_penalty:D</code> .....	358	<code>\tex_splitmaxdepth:D</code> .....	339
<code>\tex_postdisplaypenalty:D</code> .....	205	<code>\tex_splittopskip:D</code> .....	340
<code>\tex_predisplaypenalty:D</code> .....	204	<code>\tex_string:D</code> .....	354, 783
<code>\tex_predisplaysize:D</code> .....	203	<code>\tex_tabskip:D</code> .....	100
<code>\tex_pretolerance:D</code> .....	284	<code>\tex_textfont:D</code> .....	344
<code>\tex_prevdepth:D</code> .....	331	<code>\tex_textstyle:D</code> .....	189
<code>\tex_prevgraf:D</code> .....	290	<code>\tex_the:D</code> .....	162, 568–573, 1126, 1337, 1515, 1523, 1631, 2819, 3355, 3425, 3472, 4115
<code>\tex_radical:D</code> .....	179	<code>\tex_thickmuskip:D</code> .....	230
<code>\tex_raise:D</code> .....	319, 5345	<code>\tex_thinmuskip:D</code> .....	229
<code>\tex_read:D</code> .....	126, 4874	<code>\tex_time:D</code> .....	365
<code>\tex_relax:D</code> .....	161, 561, 565, 568–573, 577–582, 587, 588, 591, 592, 596, 624, 625, 627, 634, 635, 642, 643, 682, 723, 725, 791, 1042, 1059, 1303, 1337, 1509, 1521, 1522, 2069, 2070, 2082, 2083, 3125, 3496	<code>\tex_toks:D</code> .....	374
<code>\tex_relpenalty:D</code> .....	222	<code>\tex_toksdef:D</code> .	75, 2456, 4110, 4111, 4242
<code>\tex_right:D</code> .....	220	<code>\tex_tolerance:D</code> .....	285
<code>\tex_righthyphenmin:D</code> .....	276	<code>\tex_topmark:D</code> .....	166
<code>\tex_rightskip:D</code> .....	278	<code>\tex_topskip:D</code> .....	296
<code>\tex_romannumeral:D</code>	353, 873, 874, 1020, 1474, 1494, 1502, 1594, 1597, 1600, 1655, 1662, 1667, 1727, 2729, 3137	<code>\tex_tracingcommands:D</code> .....	141
<code>\tex_scriptfont:D</code> .....	345	<code>\tex_tracinglostchars:D</code> .....	142
<code>\tex_scriptscriptfont:D</code> .....	346	<code>\tex_tracingmacros:D</code> .....	143
<code>\tex_scriptscriptstyle:D</code> .....	191	<code>\tex_tracingonline:D</code> .....	144
<code>\tex_scriptspace:D</code> .....	231	<code>\tex_tracingoutput:D</code> .....	145
<code>\tex_scriptstyle:D</code> .....	190	<code>\tex_tracingpages:D</code> .....	146
<code>\tex_scrollmode:D</code> .....	156	<code>\tex_tracingparagraphs:D</code> .....	147
<code>\tex_setbox:D</code> .	327, 5334, 5339, 5369, 5374, 5380, 5388, 5395, 5400, 5406	<code>\tex_tracingrestores:D</code> .....	148
<code>\tex_setlanguage:D</code> .....	85	<code>\tex_tracingstats:D</code> .....	149
<code>\tex_sfcode:D</code> .	382, 2293, 2297, 2301	<code>\tex_uccode:D</code> .	384, 2283, 2287, 2290
<code>\tex_shipout:D</code> .....	292, 749	<code>\tex_uchyph:D</code> .....	282
<code>\tex_show:D</code> .....	135, 788	<code>\tex_underline:D</code> .....	218, 690
		<code>\tex_unhbox:D</code> .....	323, 5419
		<code>\tex_unhcopy:D</code> .....	324, 5417
		<code>\tex_unkern:D</code> .....	248
		<code>\tex_unpenalty:D</code> .....	359
		<code>\tex_unskip:D</code> .....	246

<code>\tex_unvbox:D</code> .....	325, 5392	<code>\tl_compare:nx</code> .....	3709
<code>\tex_unvcopy:D</code> .....	326, 5390	<code>\tl_compare:on</code> .....	3724
<code>\tex_uppercase:D</code> .....	356, 3861	<code>\tl_compare:oo</code> .....	3730
<code>\tex_vadjust:D</code> .....	259	<code>\tl_compare:ox</code> .....	3742
<code>\tex_valign:D</code> .....	94	<code>\tl_compare:Vn</code> .....	3721
<code>\tex_vbadness:D</code> .....	334	<code>\tl_compare:VV</code> .....	3727
<code>\tex_vbox:D</code> .....	329, 5368, 5369, 5374, 5380, 5385, 5386	<code>\tl_compare:Vx</code> .....	3739
<code>\tex_vcenter:D</code> .....	180	<code>\tl_compare:xn</code> .....	3712
<code>\tex_vfil:D</code> .....	241	<code>\tl_compare:xo</code> .....	3736
<code>\tex_vfill:D</code> .....	243	<code>\tl_compare:xV</code> .....	3733
<code>\tex_vfilneg:D</code> .....	242	<code>\tl_compare:xx</code> .....	3705, 3707, 3710, 3713, 3716, 3719, 3722, 3725, 3728, 3731, 3734, 3737, 3740, 3743
<code>\tex_vfuzz:D</code> .....	336	<code>\tl_elt_count:N</code> .....	79, 3920, 3926
<code>\tex_voffset:D</code> .....	311	<code>\tl_elt_count:n</code> ....	79, 3920, 3920, 3925
<code>\tex_vrule:D</code> .....	250	<code>\tl_elt_count:o</code> .....	79, 3920
<code>\tex_vsize:D</code> .....	293	<code>\tl_elt_count:V</code> .....	79, 3920
<code>\tex_vskip:D</code> .....	244, 3352	<code>\tl_gclear:c</code> .....	73, 3546, 4268
<code>\tex_vsplit:D</code> .....	322, 5388	<code>\tl_gclear:N</code> .....	73, 3546, 3548, 3549, 3566, 3571, 4267, 4438
<code>\tex_vss:D</code> .....	245	<code>\tl_gclear_new:c</code> .....	73, 3562, 4272
<code>\tex_vtop:D</code> .....	330	<code>\tl_gclear_new:N</code> .....	73, 3562, 3563, 3571, 3572, 4271, 4442
<code>\tex_wd:D</code> .....	377, 5353	<code>\tl_gput_left:cn</code> .....	74, 3573
<code>\tex_widowpenalty:D</code> .....	264	<code>\tl_gput_left:co</code> .....	74, 3573
<code>\tex_write:D</code> . 127, 639, 647, 706, 781, 4847		<code>\tl_gput_left:cV</code> .....	74, 3573
<code>\tex_xdef:D</code> .....	68, 707, 819	<code>\tl_gput_left:Nn</code> 74, 3573, 3590, 3608, 4526	
<code>\tex_xleaders:D</code> .....	253	<code>\tl_gput_left:No</code> .....	74, 3573, 3598
<code>\tex_xspaceskip:D</code> .....	287	<code>\tl_gput_left:NV</code> ...	74, 3573, 3595, 3609
<code>\tex_year:D</code> .....	368	<code>\tl_gput_left:Nx</code> .....	74, 3573, 3603
<code>\textasteriskcentered</code> .....	2910, 2916	<code>\tl_gput_right:cn</code> .....	74, 3610
<code>\textbardbl</code> .....	2915	<code>\tl_gput_right:co</code> .....	74, 3610
<code>\textdagger</code> .....	2911, 2917	<code>\tl_gput_right:cV</code> .....	74, 3610
<code>\textdaggerdbl</code> .....	2912, 2918	<code>\tl_gput_right:Nn</code> 74, 3610, 3615, 3646, 4534	
<code>\textfont</code> .....	344	<code>\tl_gput_right:No</code> .....	74, 3610, 3631
<code>\textparagraph</code> .....	2914	<code>\tl_gput_right:NV</code> .....	74, 3610, 3628
<code>\textsection</code> .....	2913	<code>\tl_gput_right:Nx</code> .....	74, 3610, 3640
<code>\textstyle</code> .....	189	<code>\tl_gremove_all_in:cn</code> .....	80, 4052
<code>\TeXETstate</code> .....	444	<code>\tl_gremove_all_in:Nn</code> 80, 4052, 4055, 4059	
<code>\the</code> .....	26–31, 162	<code>\tl_gremove_in:cn</code> .....	80, 4048
<code>\thepage</code> .....	5505	<code>\tl_gremove_in:Nn</code> ..	80, 4048, 4049, 4051
<code>\thickmuskip</code> .....	230	<code>\tl_greplace_all_in:cnn</code> .....	80, 4026
<code>\thinmuskip</code> .....	229	<code>\tl_greplace_all_in:Nnn</code> .....	80, 4026, 4045, 4047, 4056
<code>\time</code> .....	365	<code>\tl_greplace_in:cnn</code> .....	80, 4007
<code>\tl_clear:c</code> .....	73, 3546, 4266	<code>\tl_greplace_in:Nnn</code> .....	80, 4007, 4024, 4025, 4049
<code>\tl_clear:N</code> 73, 3546, 3546, 3547, 3554, 3560, 4265, 4289, 4436, 4456, 6686		<code>.tl_gset:c</code> .....	125
<code>\tl_clear_new:c</code> .....	73, 3550, 4270	<code>\tl_gset:cn</code> .....	73, 3507
<code>\tl_clear_new:N</code> .....	73, 3550, 3551, 3560, 3561, 4269, 4440	<code>\tl_gset:cx</code> .....	73, 3507
<code>\tl_compare:nn</code> .....	3706		
<code>\tl_compare:no</code> .....	3718		
<code>\tl_compare:nV</code> .....	3715		

.tl_gset:N	125	\tl_if_empty:nTF	77, 2413,
\tl_gset:Nc	73, 3647, 3647	2420, 2431, 2442, 2453, 2464, 2471,	
\tl_gset:Nn	73, 3507, 3515, 3525,	2478, 2486, 3679, 3684, 3688, 5014	
3529, 3932, 4419, 4526, 4534, 4649		\tl_if_empty:oTF	77, 3679
\tl_gset:No	73, 3507	\tl_if_empty:VTF	77, 3679, 4228
\tl_gset:Nv	73, 3507	\tl_if_empty_p:c	76, 3664
\tl_gset:Nv	73, 3507	\tl_if_empty_p:N	76, 3664, 3668
\tl_gset:Nx	73, 3507, 3518, 3526, 3592, 3596,	\tl_if_empty_p:n	77, 2383, 3679, 3683, 3687
3600, 3604, 3617, 3629, 3633, 3641,		\tl_if_empty_p:o	77, 3679
3973, 4024, 4046, 4282, 4602, 4710		\tl_if_empty_p:V	77, 3679
\tl_gset_eq:cc	75, 3530	\tl_if_eq:cc	4463
\tl_gset_eq:cN	75, 3530	\tl_if_eq:ccTF	76, 3672, 5877
\tl_gset_eq:Nc	75, 3530	\tl_if_eq:cN	4461
\tl_gset_eq:NN	75, 3098, 3530, 3535, 3542, 3545, 3548	\tl_if_eq:cNTF	76, 3672
\tl_gset_rescan:Nnn	75, 3931, 3932	\tl_if_eq:Nc	4462
\tl_gset_rescan:Nnx	75, 3958, 3968	\tl_if_eq:NcTF	76, 3672
.tl_gset_x:c	125	\tl_if_eq:NN	3672, 4460
.tl_gset_x:N	125	\tl_if_eq:nn	3761
\tl_head:n	81, 4060, 4060, 4061, 4070	\tl_if_eq:NNF	3678
\tl_head:V	81, 4060	\tl_if_eq:nnF	4631
\tl_head:w	81, 4060, 4060,	\tl_if_eq:NNT	3677
4066, 4067, 4073, 4078, 4082, 4096		\tl_if_eq:NNTF	76, 1985, 3672, 3676, 5116, 5631, 5682
\tl_head_i:n	81, 4060, 4061	\tl_if_eq:nnTF	76, 3705
\tl_head_i:w	81, 4060, 4067	\tl_if_eq:no	3775
\tl_head_iii:f	81, 4060	\tl_if_eq:noTF	76, 3705
\tl_head_iii:n	81, 4060, 4064, 4065	\tl_if_eq:nV	3768
\tl_head_iii:w	81, 4060, 4064, 4069	\tl_if_eq:nVTF	76, 3705
\tl_if_blank:n	3691	\tl_if_eq:nx	3782
\tl_if_blank:nF	3700, 3704, 4545	\tl_if_eq:nxTF	76, 3705
\tl_if_blank:nT	3699, 3703	\tl_if_eq:on	3796
\tl_if_blank:nTF	77, 3691, 3698, 3702	\tl_if_eq:onTF	76, 3705
\tl_if_blank:oTF	77, 3691, 5617	\tl_if_eq:oo	3810
\tl_if_blank:VTF	77, 3691	\tl_if_eq:ooTF	76, 3705
\tl_if_blank_p:n	77, 3691, 3697, 3701	\tl_if_eq:ox	3824
\tl_if_blank_p:o	77, 3691	\tl_if_eq:oxTF	76, 3705
\tl_if_blank_p:V	77, 3691	\tl_if_eq:Vn	3789
\tl_if_blank_p_aux:w	3691, 3692, 3694	\tl_if_eq:VnTF	76, 3705
\tl_if_empty:c	4286, 4453	\tl_if_eq:VV	3803
\tl_if_empty:cTF	76, 3664	\tl_if_eq:VVTF	76, 3705
\tl_if_empty:N	3664, 4285, 4452	\tl_if_eq:Vx	3817
\tl_if_empty:n	3679	\tl_if_eq:VxTF	76, 3705
\tl_if_empty:NF	3671, 6715, 6721	\tl_if_eq:xn	3831
\tl_if_empty:nF	2642,	\tl_if_eq:xnTF	76, 3705
3686, 3690, 4518, 4569, 4580, 4734		\tl_if_eq:xo	3845
\tl_if_empty:NT	3670	\tl_if_eq:xoTF	76, 3705
\tl_if_empty:nT	3685, 3689, 4759	\tl_if_eq:xV	3838
\tl_if_empty:NTF	76, 3664, 3669, 5655, 5677	\tl_if_eq:xVTF	76, 3705
		\tl_if_eq:xx	3852
		\tl_if_eq:xxTF	76, 1975, 3705, 4235

<code>\tl_if_eq_p:cc</code> .....	<a href="#">76</a> , <a href="#">3672</a>	<code>\tl_map_function:NN</code> .....	
<code>\tl_if_eq_p:cN</code> .....	<a href="#">76</a> , <a href="#">3672</a>	.....	<a href="#">78</a> , <a href="#">3867</a> , <a href="#">3870</a> , <a href="#">3878</a> , <a href="#">3928</a>
<code>\tl_if_eq_p:Nc</code> .....	<a href="#">76</a> , <a href="#">3672</a>	<code>\tl_map_function:nN</code> .....	
<code>\tl_if_eq_p:NN</code> .....	<a href="#">76</a> , <a href="#">3672</a> , <a href="#">3675</a>	.....	<a href="#">78</a> , <a href="#">3867</a> , <a href="#">3867</a> , <a href="#">3922</a> , <a href="#">6415</a>
<code>\tl_if_eq_p:nn</code> .....	<a href="#">77</a> , <a href="#">3705</a>	<code>\tl_map_function_aux:NN</code> .....	<a href="#">3867</a>
<code>\tl_if_eq_p:no</code> .....	<a href="#">77</a> , <a href="#">3705</a>	<code>\tl_map_function_aux:Nn</code> .....	
<code>\tl_if_eq_p:nV</code> .....	<a href="#">77</a> , <a href="#">3705</a>	..	<a href="#">3868</a> , <a href="#">3871</a> , <a href="#">3874</a> , <a href="#">3876</a> , <a href="#">3883</a> , <a href="#">3892</a>
<code>\tl_if_eq_p:nx</code> .....	<a href="#">77</a> , <a href="#">3705</a>	<code>\tl_map_inline:cn</code> .....	<a href="#">78</a> , <a href="#">3879</a>
<code>\tl_if_eq_p:on</code> .....	<a href="#">77</a> , <a href="#">3705</a>	<code>\tl_map_inline:Nn</code> ..	<a href="#">78</a> , <a href="#">3879</a> , <a href="#">3888</a> , <a href="#">3897</a>
<code>\tl_if_eq_p:oo</code> .....	<a href="#">77</a> , <a href="#">3705</a>	<code>\tl_map_inline:nn</code> ..	<a href="#">78</a> , <a href="#">2404</a> , <a href="#">3879</a> , <a href="#">3879</a>
<code>\tl_if_eq_p:ox</code> .....	<a href="#">77</a> , <a href="#">3705</a>	<code>\tl_map_inline_aux:n</code> .....	<a href="#">3879</a>
<code>\tl_if_eq_p:Vn</code> .....	<a href="#">77</a> , <a href="#">3705</a>	<code>\tl_map_variable:cNn</code> .....	<a href="#">78</a> , <a href="#">3898</a>
<code>\tl_if_eq_p:VV</code> .....	<a href="#">77</a> , <a href="#">3705</a>	<code>\tl_map_variable:NnN</code> ..	<a href="#">78</a> , <a href="#">3898</a> , <a href="#">3901</a> , <a href="#">3902</a>
<code>\tl_if_eq_p:Vx</code> .....	<a href="#">77</a> , <a href="#">3705</a>	<code>\tl_map_variable:nNn</code> ..	<a href="#">78</a> , <a href="#">3898</a> , <a href="#">3898</a> , <a href="#">3901</a>
<code>\tl_if_eq_p:xn</code> .....	<a href="#">77</a> , <a href="#">3705</a>	<code>\tl_map_variable_aux:NnN</code> .....	<a href="#">3903</a>
<code>\tl_if_eq_p:xo</code> .....	<a href="#">77</a> , <a href="#">3705</a>	<code>\tl_map_variable_aux:Nnn</code> ..	<a href="#">3899</a> , <a href="#">3903</a> , <a href="#">3906</a>
<code>\tl_if_eq_p:xV</code> .....	<a href="#">77</a> , <a href="#">3705</a>	<code>\tl_new:c</code> .....	<a href="#">72</a> , <a href="#">3480</a> , <a href="#">3494</a> , <a href="#">4264</a>
<code>\tl_if_eq_p:xx</code> .....	<a href="#">77</a> , <a href="#">3705</a>	<code>\tl_new:cn</code> .....	<a href="#">72</a> , <a href="#">3480</a> , <a href="#">3494</a> , <a href="#">5440</a>
<code>\tl_if_head_eq_catcode:nN</code> .....	<a href="#">4094</a>	<code>\tl_new:N</code> .....	
<code>\tl_if_head_eq_catcode:nNTF</code> ..	<a href="#">81</a> , <a href="#">4072</a>	..	<a href="#">72</a> , <a href="#">3480</a> , <a href="#">3493</a> , <a href="#">4263</a> , <a href="#">4434</a> , <a href="#">4933</a> , <a href="#">4934</a> , <a href="#">5544</a> , <a href="#">5545</a> , <a href="#">5718</a> – <a href="#">5723</a> , <a href="#">6650</a>
<code>\tl_if_head_eq_catcode_p:nN</code> ..	<a href="#">81</a> , <a href="#">4072</a>	<code>\tl_new:Nn</code> .....	<a href="#">72</a> , <a href="#">2108</a> , <a href="#">2567</a> , <a href="#">2568</a> , <a href="#">2570</a> , <a href="#">2600</a> , <a href="#">2601</a> , <a href="#">3088</a> , <a href="#">3480</a> , <a href="#">3480</a> , <a href="#">3487</a> , <a href="#">3493</a> , <a href="#">3556</a> , <a href="#">3568</a> , <a href="#">3654</a> – <a href="#">3663</a> , <a href="#">3940</a> , <a href="#">4893</a> – <a href="#">4897</a> , <a href="#">4900</a> , <a href="#">4903</a> , <a href="#">4906</a> , <a href="#">4912</a> , <a href="#">4916</a> , <a href="#">4926</a> , <a href="#">4930</a> – <a href="#">4932</a> , <a href="#">5546</a> , <a href="#">5713</a> – <a href="#">5716</a> , <a href="#">5725</a> , <a href="#">6169</a>
<code>\tl_if_head_eq_charcode:fNTF</code> .....	<a href="#">81</a> , <a href="#">2983</a> , <a href="#">2990</a> , <a href="#">4072</a>	<code>\tl_new:Nx</code> ....	<a href="#">72</a> , <a href="#">3480</a> , <a href="#">3488</a> , <a href="#">4856</a> – <a href="#">4858</a>
<code>\tl_if_head_eq_charcode:nN</code> .....	<a href="#">4076</a>	<code>\tl_put_left:cn</code> .....	<a href="#">74</a> , <a href="#">3573</a>
<code>\tl_if_head_eq_charcode:nNF</code> .....	<a href="#">4093</a>	<code>\tl_put_left:co</code> .....	<a href="#">74</a> , <a href="#">3573</a>
<code>\tl_if_head_eq_charcode:nNT</code> .....	<a href="#">4092</a>	<code>\tl_put_left:cV</code> .....	<a href="#">74</a> , <a href="#">3573</a>
<code>\tl_if_head_eq_charcode:nNTF</code> .....		<code>\tl_put_left:Nn</code> ..	<a href="#">74</a> , <a href="#">3573</a> , <a href="#">3573</a> , <a href="#">3607</a> , <a href="#">4522</a>
.....	<a href="#">81</a> , <a href="#">4072</a> , <a href="#">4091</a>	<code>\tl_put_left:No</code> .....	<a href="#">74</a> , <a href="#">3573</a> , <a href="#">3581</a>
<code>\tl_if_head_eq_charcode_p:fN</code> .....	<a href="#">81</a> , <a href="#">4072</a> , <a href="#">4081</a> , <a href="#">4089</a>	<code>\tl_put_left:NV</code> .....	<a href="#">74</a> , <a href="#">3573</a> , <a href="#">3578</a>
<code>\tl_if_head_eq_charcode_p:nN</code> .....	<a href="#">81</a> , <a href="#">4072</a> , <a href="#">4090</a>	<code>\tl_put_left:Nx</code> .....	<a href="#">74</a> , <a href="#">3573</a> , <a href="#">3586</a>
<code>\tl_if_head_eq_meaning:nN</code> .....	<a href="#">4072</a>	<code>\tl_put_right:cn</code> .....	<a href="#">74</a> , <a href="#">3610</a>
<code>\tl_if_head_eq_meaning:nNTF</code> .....	<a href="#">81</a> , <a href="#">4072</a> , <a href="#">5646</a>	<code>\tl_put_right:co</code> .....	<a href="#">74</a> , <a href="#">3610</a>
<code>\tl_if_head_eq_meaning_p:nN</code> ..	<a href="#">81</a> , <a href="#">4072</a>	<code>\tl_put_right:cV</code> .....	<a href="#">74</a> , <a href="#">3610</a>
<code>\tl_if_in:cnTF</code> .....	<a href="#">80</a> , <a href="#">3985</a>	<code>\tl_put_right:Nn</code> ..	<a href="#">74</a> , <a href="#">3610</a> , <a href="#">3610</a> , <a href="#">3644</a> , <a href="#">4530</a>
<code>\tl_if_in:Nn</code> .....	<a href="#">3985</a>	<code>\tl_put_right:No</code> .....	<a href="#">74</a> , <a href="#">3610</a> , <a href="#">3623</a>
<code>\tl_if_in:nn</code> .....	<a href="#">3994</a>	<code>\tl_put_right:NV</code> ..	<a href="#">74</a> , <a href="#">3610</a> , <a href="#">3620</a> , <a href="#">3645</a>
<code>\tl_if_in:NnF</code> .....	<a href="#">3993</a>	<code>\tl_put_right:Nx</code> .....	<a href="#">74</a> , <a href="#">3610</a> , <a href="#">3636</a>
<code>\tl_if_in:nnF</code> .....	<a href="#">4002</a> , <a href="#">4005</a>	<code>\tl_remove_all_in:cn</code> .....	<a href="#">80</a> , <a href="#">4052</a>
<code>\tl_if_in:NnT</code> .....	<a href="#">3992</a>	<code>\tl_remove_all_in:Nn</code> ..	<a href="#">80</a> , <a href="#">4052</a> , <a href="#">4052</a> , <a href="#">4058</a>
<code>\tl_if_in:nnT</code> .....	<a href="#">4001</a> , <a href="#">4004</a>	<code>\tl_remove_in:cn</code> .....	<a href="#">80</a> , <a href="#">4048</a>
<code>\tl_if_in:NnTF</code> .....	<a href="#">80</a> , <a href="#">3985</a> , <a href="#">3991</a>	<code>\tl_remove_in:Nn</code> ..	<a href="#">80</a> , <a href="#">4048</a> , <a href="#">4048</a> , <a href="#">4050</a>
<code>\tl_if_in:nnTF</code> .....	<a href="#">80</a> , <a href="#">3994</a> , <a href="#">4000</a> , <a href="#">4003</a> , <a href="#">5892</a> , <a href="#">5902</a>	<code>\tl_replace_all_in:cn</code> .....	<a href="#">80</a> , <a href="#">4026</a>
<code>\tl_if_in:onTF</code> .....	<a href="#">80</a> , <a href="#">3994</a>	<code>\tl_replace_all_in:Nnn</code> .....	<a href="#">80</a> , <a href="#">4026</a> , <a href="#">4042</a> , <a href="#">4044</a> , <a href="#">4053</a> , <a href="#">5559</a> , <a href="#">5562</a>
<code>\tl_if_in:VnTF</code> .....	<a href="#">80</a> , <a href="#">3994</a>		
<code>\tl_map_break:</code> .....	<a href="#">78</a> , <a href="#">3908</a> , <a href="#">3908</a>		
<code>\tl_map_function:cN</code> .....	<a href="#">78</a> , <a href="#">3867</a>		

- \tl\_replace\_all\_in\_aux:NNnn ..... [4026](#), [4026](#), [4043](#), [4046](#)
- \tl\_replace\_in:cn ..... [80](#), [4007](#)
- \tl\_replace\_in:Nnn ..... [80](#), [4007](#), [4022](#), [4023](#), [4048](#)
- \tl\_replace\_in\_aux:NNnn ..... [4007](#), [4007](#), [4022](#), [4024](#)
- \tl\_rescan:nn ..... [75](#), [3976](#), [3976](#)
- \tl\_rescan\_aux:w ..... [3947](#), [3952](#), [3953](#), [3981](#)
- \tl\_reverse:N ..... [78](#), [3917](#), [3917](#)
- \tl\_reverse:n ..... [78](#), [3909](#), [3909](#), [3916](#)
- \tl\_reverse:o ..... [78](#), [3909](#), [3918](#)
- \tl\_reverse:V ..... [78](#), [3909](#)
- \tl\_reverse\_aux:nN [3909](#), [3910](#), [3912](#), [3914](#)
- .tl\_set:c ..... [125](#)
- \tl\_set:cn ..... [73](#), [3507](#), [5797](#), [5800](#)
- \tl\_set:co ..... [73](#), [3507](#)
- \tl\_set:cV ..... [73](#), [3507](#)
- \tl\_set:cx ..... [73](#), [3507](#), [5745](#)
- .tl\_set:N ..... [125](#)
- \tl\_set:Nc ..... [73](#), [3647](#), [3652](#), [3653](#)
- \tl\_set:Nf ..... [73](#), [3507](#), [3918](#)
- \tl\_set:Nn ..... [73](#), [2573](#), [2587](#), [3507](#), [3508](#), [3523](#), [3528](#), [3574](#), [3591](#), [3611](#), [3616](#), [3904](#), [3931](#), [3956](#), [3966](#), [4308](#), [4340](#), [4416](#), [4419](#), [4487](#), [4522](#), [4530](#), [4643](#), [4649](#), [5095](#), [5096](#), [5502](#), [5676](#), [5778](#), [5804](#), [5808](#), [5909](#), [5922](#), [5926](#), [6691](#), [6699](#)
- \tl\_set:No ..... [73](#), [3091](#), [3507](#), [3582](#), [3599](#), [3624](#), [3632](#), [3653](#)
- \tl\_set:NV ..... [73](#), [3507](#)
- \tl\_set:Nv ..... [73](#), [3507](#), [5767](#)
- \tl\_set:Nx ..... [73](#), [2574](#), [2575](#), [2588](#), [2590](#), [3507](#), [3512](#), [3524](#), [3575](#), [3579](#), [3583](#), [3587](#), [3612](#), [3621](#), [3625](#), [3637](#), [3746](#), [3762](#), [3763](#), [3769](#), [3770](#), [3776](#), [3777](#), [3783](#), [3784](#), [3790](#), [3791](#), [3797](#), [3798](#), [3804](#), [3805](#), [3811](#), [3812](#), [3818](#), [3819](#), [3825](#), [3826](#), [3832](#), [3833](#), [3839](#), [3840](#), [3846](#), [3847](#), [3853](#), [3854](#), [3963](#), [4022](#), [4043](#), [4370](#), [4376](#), [4601](#), [4706](#), [4715](#), [5015](#), [5017](#), [5601](#), [5630](#), [5650](#), [5891](#), [5903](#), [5908](#), [5944](#), [5945](#), [6192](#)
- \tl\_set\_eq:cc ..... [75](#), [3530](#), [5985](#)
- \tl\_set\_eq:cN ..... [75](#), [3530](#)
- \tl\_set\_eq:Nc ..... [75](#), [3530](#)
- \tl\_set\_eq:NN ..... [75](#), [2589](#), [3096](#), [3530](#), [3531](#), [3541](#), [3544](#), [3546](#)
- \tl\_set\_rescan:Nnn ..... [75](#), [3931](#), [3931](#)
- \tl\_set\_rescan:Nnx ..... [75](#), [3958](#), [3958](#)
- \tl\_set\_rescan\_aux:NNnn ..... [3931](#), [3932](#), [3933](#), [3942](#)
- .tl\_set\_x:c ..... [125](#)
- .tl\_set\_x:N ..... [125](#)
- \tl\_show:c ..... [72](#), [3504](#), [4321](#), [4500](#)
- \tl\_show:N [72](#), [3504](#), [3504](#), [3505](#), [4320](#), [4499](#)
- \tl\_show:n ..... [72](#), [3504](#), [3506](#)
- \tl\_tail:f ..... [81](#), [4060](#)
- \tl\_tail:n ..... [81](#), [4060](#), [4062](#), [4063](#), [4071](#)
- \tl\_tail:V ..... [81](#), [4060](#)
- \tl\_tail:w ..... [81](#), [4060](#), [4062](#), [4068](#)
- \tl\_tmp:w ..... [3745](#), [3756](#)–[3759](#), [3986](#), [3989](#), [3995](#), [3998](#), [4008](#), [4012](#), [4015](#), [4019](#), [4028](#), [4035](#), [4038](#)
- \tl\_to\_lowercase:n ..... [77](#), [2071](#), [2084](#), [2406](#), [2496](#), [3860](#), [3860](#), [3938](#), [4924](#), [4992](#), [5557](#)
- \tl\_to\_str:c ..... [75](#), [3863](#)
- \tl\_to\_str:N ..... [75](#), [3863](#), [3863](#), [3866](#)
- \tl\_to\_str:n [75](#), [2166](#), [2188](#), [3680](#), [3692](#), [3862](#), [3862](#), [5904](#), [5908](#), [5944](#), [5971](#)
- \tl\_to\_str\_aux:w ..... [3863](#), [3863](#), [3865](#)
- \tl\_to\_uppercase:n ..... [77](#), [3860](#), [3861](#)
- \tl\_use:c ..... [72](#), [3495](#)
- \tl\_use:N ..... [72](#), [3495](#), [3495](#), [3503](#)
- \token\_get\_arg\_spec:N ... [52](#), [2489](#), [2507](#)
- \token\_get\_prefix\_arg\_replacement\_aux:w ..... [2489](#), [2498](#), [2503](#), [2509](#), [2515](#)
- \token\_get\_prefix\_spec:N . [52](#), [2489](#), [2501](#)
- \token\_get\_replacement\_spec:N ..... [52](#), [2489](#), [2513](#)
- \token\_if\_active\_char:N ..... [2363](#)
- \token\_if\_active\_char:NTF ..... [50](#), [2363](#)
- \token\_if\_active\_char\_p:N [50](#), [2363](#), [2528](#)
- \token\_if\_alignment\_tab:N ..... [2335](#)
- \token\_if\_alignment\_tab:NTF ... [49](#), [2335](#)
- \token\_if\_alignment\_tab\_p:N ... [49](#), [2335](#)
- \token\_if\_chardef:N ..... [2408](#)
- \token\_if\_chardef:NTF ..... [51](#), [2397](#)
- \token\_if\_chardef\_aux:w .... [2409](#), [2412](#)
- \token\_if\_chardef\_p:N ... [51](#), [2397](#), [2540](#)
- \token\_if\_chardef\_p\_aux:w ..... [2397](#)
- \token\_if\_cs:N ..... [2386](#)
- \token\_if\_cs:NTF ..... [50](#), [2386](#)
- \token\_if\_cs\_p:N ..... [50](#), [2386](#), [2521](#)
- \token\_if\_dim\_register:N ..... [2444](#)
- \token\_if\_dim\_register:NTF .... [51](#), [2397](#)
- \token\_if\_dim\_register\_aux:w [2448](#), [2452](#)
- \token\_if\_dim\_register\_p:N [51](#), [2397](#), [2548](#)



<code>\token_if_dim_register_p_aux:w</code> ..	<a href="#">2397</a>	<code>\token_if_mathchardef:NTF</code> .....	<a href="#">51</a> , <a href="#">2397</a>
<code>\token_if_eq_catcode:NN</code> .....	<a href="#">2371</a>	<code>\token_if_mathchardef_aux:w</code> .	<a href="#">2416</a> , <a href="#">2419</a>
<code>\token_if_eq_catcode:NNTF</code> .....	<a href="#">50</a> , <a href="#">2371</a>	<code>\token_if_mathchardef_p:N</code> .....	<a href="#">51</a> , <a href="#">2397</a> , <a href="#">2542</a>
<code>\token_if_eq_catcode_p:NN</code> .....		<code>\token_if_mathchardef_p_aux:w</code> ...	<a href="#">2397</a>
.....	<a href="#">50</a> , <a href="#">2371</a> , <a href="#">2387</a> , <a href="#">2620</a> , <a href="#">2621</a>	<code>\token_if_other_char:N</code> .....	<a href="#">2359</a>
<code>\token_if_eq_charcode:NN</code> .....	<a href="#">2375</a>	<code>\token_if_other_char:NTF</code> .....	<a href="#">49</a> , <a href="#">2359</a>
<code>\token_if_eq_charcode:NNTF</code> ....	<a href="#">50</a> , <a href="#">2375</a>	<code>\token_if_other_char_p:N</code> .....	<a href="#">49</a> , <a href="#">2359</a>
<code>\token_if_eq_charcode_p:NN</code> ....	<a href="#">50</a> , <a href="#">2375</a>	<code>\token_if_parameter:N</code> .....	<a href="#">2339</a>
<code>\token_if_eq_meaning:NN</code> .....	<a href="#">2367</a>	<code>\token_if_parameter:NTF</code> .....	<a href="#">49</a> , <a href="#">2339</a>
<code>\token_if_eq_meaning:NNT</code> .....	<a href="#">2078</a>	<code>\token_if_parameter_p:N</code> .....	<a href="#">49</a> , <a href="#">2339</a>
<code>\token_if_eq_meaning:NNTF</code> .....		<code>\token_if_primitive:N</code> .....	<a href="#">2520</a>
.....	<a href="#">50</a> , <a href="#">2091</a> , <a href="#">2367</a> , <a href="#">2713</a>	<code>\token_if_primitive:NTF</code> .....	<a href="#">52</a> , <a href="#">2520</a>
<code>\token_if_eq_meaning_p:NN</code> .....	<a href="#">50</a> , <a href="#">2367</a> , <a href="#">2622</a>	<code>\token_if_primitive_p:N</code> .....	<a href="#">52</a> , <a href="#">2520</a>
<code>\token_if_expandable:N</code> .....	<a href="#">2389</a>	<code>\token_if_primitive_p_aux:N</code> .....	
<code>\token_if_expandable:NTF</code> .....	<a href="#">50</a> , <a href="#">2389</a>	.....	<a href="#">2520</a> , <a href="#">2525</a> , <a href="#">2532</a> , <a href="#">2539</a>
<code>\token_if_expandable_p:N</code> .....	<a href="#">50</a> , <a href="#">2389</a>	<code>\token_if_protected_long_macro:N</code> .	<a href="#">2480</a>
<code>\token_if_group_begin:N</code> .....	<a href="#">2323</a>	<code>\token_if_protected_long_macro:NTF</code> .	
<code>\token_if_group_begin:NTF</code> .....	<a href="#">48</a> , <a href="#">2323</a>	.....	<a href="#">51</a> , <a href="#">2397</a>
<code>\token_if_group_begin_p:N</code> .....	<a href="#">48</a> , <a href="#">2323</a>	<code>\token_if_protected_long_macro_aux:w</code>	
<code>\token_if_group_end:N</code> .....	<a href="#">2327</a>	.....	<a href="#">2481</a> , <a href="#">2484</a>
<code>\token_if_group_end:NTF</code> .....	<a href="#">48</a> , <a href="#">2327</a>	<code>\token_if_protected_long_macro_p:N</code> .	
<code>\token_if_group_end_p:N</code> .....	<a href="#">48</a> , <a href="#">2327</a>	.....	<a href="#">51</a> , <a href="#">2397</a>
<code>\token_if_int_register:N</code> .....	<a href="#">2422</a>	<code>\token_if_protected_long_macro_p_aux:w</code>	
<code>\token_if_int_register:NTF</code> ....	<a href="#">51</a> , <a href="#">2397</a>	.....	<a href="#">2397</a>
<code>\token_if_int_register_aux:w</code> .....	<a href="#">2426</a> , <a href="#">2430</a>	<code>\token_if_protected_macro:N</code> .....	<a href="#">2466</a>
<code>\token_if_int_register_p:N</code> .....	<a href="#">51</a> , <a href="#">2397</a> , <a href="#">2544</a>	<code>\token_if_protected_macro:NTF</code> .	<a href="#">51</a> , <a href="#">2397</a>
<code>\token_if_int_register_p_aux:w</code> ..	<a href="#">2397</a>	<code>\token_if_protected_macro_aux:w</code> ....	
<code>\token_if_letter:N</code> .....	<a href="#">2355</a>	.....	<a href="#">2467</a> , <a href="#">2470</a>
<code>\token_if_letter:NTF</code> .....	<a href="#">49</a> , <a href="#">2355</a>	<code>\token_if_protected_macro_p:N</code> .	<a href="#">51</a> , <a href="#">2397</a>
<code>\token_if_letter_p:N</code> .....	<a href="#">49</a> , <a href="#">2355</a>	<code>\token_if_protected_macro_p_aux:w</code>	<a href="#">2397</a>
<code>\token_if_long_macro:N</code> .....	<a href="#">2473</a>	<code>\token_if_skip_register:N</code> .....	<a href="#">2433</a>
<code>\token_if_long_macro:NTF</code> .....	<a href="#">51</a> , <a href="#">2397</a>	<code>\token_if_skip_register:NTF</code> ...	<a href="#">52</a> , <a href="#">2397</a>
<code>\token_if_long_macro_aux:w</code> ..	<a href="#">2474</a> , <a href="#">2477</a>	<code>\token_if_skip_register_aux:w</code>	<a href="#">2437</a> , <a href="#">2441</a>
<code>\token_if_long_macro_p:N</code> .....	<a href="#">51</a> , <a href="#">2397</a>	<code>\token_if_skip_register_p:N</code> .....	
<code>\token_if_long_macro_p_aux:w</code> ....	<a href="#">2397</a>	.....	<a href="#">52</a> , <a href="#">2397</a> , <a href="#">2546</a>
<code>\token_if_macro:N</code> .....	<a href="#">2379</a>	<code>\token_if_skip_register_p_aux:w</code> ..	<a href="#">2397</a>
<code>\token_if_macro:NTF</code> .....		<code>\token_if_space:N</code> .....	<a href="#">2351</a>
.....	<a href="#">50</a> , <a href="#">2379</a> , <a href="#">2502</a> , <a href="#">2508</a> , <a href="#">2514</a>	<code>\token_if_space:NTF</code> .....	<a href="#">49</a> , <a href="#">2351</a>
<code>\token_if_macro_p:N</code> .	<a href="#">50</a> , <a href="#">2379</a> , <a href="#">2522</a> , <a href="#">2529</a>	<code>\token_if_space_p:N</code> .....	<a href="#">49</a> , <a href="#">2351</a>
<code>\token_if_macro_p_aux:w</code> .....	<a href="#">2379</a> , <a href="#">2380</a> , <a href="#">2382</a>	<code>\token_if_toks_register:N</code> .....	<a href="#">2455</a>
<code>\token_if_math_shift:N</code> .....	<a href="#">2331</a>	<code>\token_if_toks_register:NTF</code> ...	<a href="#">52</a> , <a href="#">2397</a>
<code>\token_if_math_shift:NTF</code> .....	<a href="#">49</a> , <a href="#">2331</a>	<code>\token_if_toks_register_aux:w</code>	<a href="#">2459</a> , <a href="#">2463</a>
<code>\token_if_math_shift_p:N</code> .....	<a href="#">49</a> , <a href="#">2331</a>	<code>\token_if_toks_register_p:N</code> .....	
<code>\token_if_math_subscript:N</code> .....	<a href="#">2347</a>	.....	<a href="#">52</a> , <a href="#">2397</a> , <a href="#">2550</a>
<code>\token_if_math_subscript:NTF</code> ..	<a href="#">49</a> , <a href="#">2347</a>	<code>\token_if_toks_register_p_aux:w</code> ..	<a href="#">2397</a>
<code>\token_if_math_subscript_p:N</code> ..	<a href="#">49</a> , <a href="#">2347</a>	<code>\token_new:Nn</code> ...	<a href="#">48</a> , <a href="#">2305</a> , <a href="#">2305</a> , <a href="#">2310</a> , <a href="#">2312</a> – <a href="#">2314</a> , <a href="#">2316</a> – <a href="#">2319</a> , <a href="#">2560</a> – <a href="#">2562</a>
<code>\token_if_math_superscript:N</code> ....	<a href="#">2343</a>	<code>\token_to_meaning:N</code> .....	
<code>\token_if_math_superscript:NTF</code>	<a href="#">49</a> , <a href="#">2343</a>	..	<a href="#">24</a> , <a href="#">781</a> , <a href="#">782</a> , <a href="#">1119</a> , <a href="#">2380</a> , <a href="#">2410</a> ,
<code>\token_if_math_superscript_p:N</code>	<a href="#">49</a> , <a href="#">2343</a>		
<code>\token_if_mathchardef:N</code> .....	<a href="#">2415</a>		



- 2417, 2427, 2438, 2449, 2460, 2468,  
 2475, 2482, 2504, 2510, 2516, 3864  
 \token\_to\_str:c ..... 24, [781](#), 790, 1628  
 \token\_to\_str:N ..... 5, 24, [781](#),  
 783, 790, 1006, 1010, 1071, 1117,  
 1124, 1125, 1133, 1150, 1154, 1336,  
 2088, 2165, 2187, 3497, 4290, 4323,  
 4457, 4477, 4502, 4681, 6121, 6526  
 \toks ..... 374  
 \toks\_clear:c ..... 84, [4156](#), 4667  
 \toks\_clear:N ..... 84,  
 4027, [4156](#), 4156, 4163, 4165, 4168,  
 4325, 4504, 4666, 4683, 5600, 5611  
 \toks\_gclear:c ..... 84, [4156](#), 4669  
 \toks\_gclear:N . 84, [4156](#), 4160, 4166, 4668  
 \toks\_gput\_left:cn ..... 85, [4179](#)  
 \toks\_gput\_left:co ..... 85, [4179](#)  
 \toks\_gput\_left:cV ..... 85, [4179](#)  
 \toks\_gput\_left:Nn .. 85, [4179](#), 4184, 4189  
 \toks\_gput\_left:No ..... 85, [4179](#)  
 \toks\_gput\_left:NV ..... 85, [4179](#)  
 \toks\_gput\_left:Nx ..... 85, [4179](#)  
 \toks\_gput\_right:cn ..... 85, [4194](#)  
 \toks\_gput\_right:co ..... 85, [4194](#)  
 \toks\_gput\_right:cV ..... 85, [4194](#)  
 \toks\_gput\_right:Nn .....  
 ..... 85, [4194](#), 4198, 4218, 4729  
 \toks\_gput\_right:No ..... 85, [4194](#)  
 \toks\_gput\_right:NV ..... 85, [4194](#)  
 \toks\_gput\_right:Nx ..... 85, [4194](#)  
 \toks\_gset:cn ..... 83, [4135](#), 5471  
 \toks\_gset:co ..... 83, [4135](#)  
 \toks\_gset:cV ..... 83, [4135](#)  
 \toks\_gset:cx ..... 83, [4135](#)  
 \toks\_gset:Nn .....  
 ..... 83, [4135](#), 4135–4137, 4713, 4745  
 \toks\_gset:No ..... 83, [4135](#)  
 \toks\_gset:NV ..... 83, [4135](#)  
 \toks\_gset:Nx ..... 83, [4135](#)  
 \toks\_gset\_eq:cc ..... 84, [4138](#), 4677  
 \toks\_gset\_eq:cN ..... 84, [4138](#), 4676  
 \toks\_gset\_eq:Nc ..... 84, [4138](#), 4675  
 \toks\_gset\_eq:NN .....  
 ..... 84, [4138](#), 4144, 4152, 4155, 4674  
 \toks\_if\_empty:c ..... 4761  
 \toks\_if\_empty:cTF ..... 85, [4227](#)  
 \toks\_if\_empty:N ..... 4227, 4760  
 \toks\_if\_empty:Nf .....  
 ..... 4233, 4327, 4506, 4597, 4685  
 \toks\_if\_empty:NT ..... 4232  
 \toks\_if\_empty:Ntf ..... 85, [4227](#), 4231  
 \toks\_if\_empty\_p:c ..... 85, [4227](#)  
 \toks\_if\_empty\_p:N ..... 85, [4227](#), 4230  
 \toks\_if\_eq:cc ..... 4765  
 \toks\_if\_eq:ccTF ..... 86, [4234](#)  
 \toks\_if\_eq:cN ..... 4763  
 \toks\_if\_eq:cNTF ..... 86, [4234](#)  
 \toks\_if\_eq:Nc ..... 4764  
 \toks\_if\_eq:NcTF ..... 86, [4234](#)  
 \toks\_if\_eq:NN ..... 4234, 4762  
 \toks\_if\_eq:Nf ..... 4241  
 \toks\_if\_eq:NNT ..... 4240  
 \toks\_if\_eq:NNTF ..... 86, [4234](#), 4239  
 \toks\_if\_eq\_p:cc ..... 86, [4234](#)  
 \toks\_if\_eq\_p:cN ..... 86, [4234](#)  
 \toks\_if\_eq\_p:Nc ..... 86, [4234](#)  
 \toks\_if\_eq\_p:NN ..... 86, [4234](#), 4238  
 \toks\_new:c ..... 82, [4108](#), 4665  
 \toks\_new:N 82, [4108](#), 4110, 4113, 4114,  
 4244–4250, 4664, 5547–5549, 5727  
 \toks\_new\_l:N ..... 4111  
 \toks\_put\_left:cn ..... 84, [4179](#)  
 \toks\_put\_left:co ..... 84, [4179](#)  
 \toks\_put\_left:cV ..... 84, [4179](#)  
 \toks\_put\_left:Nn 84, [4179](#), 4179, 4183, 4187  
 \toks\_put\_left:No ..... 84, [4179](#)  
 \toks\_put\_left:NV ..... 84, [4179](#)  
 \toks\_put\_left:Nx ..... 84, [4179](#)  
 \toks\_put\_left\_aux:w ... [4179](#), 4180, 4190  
 \toks\_put\_right:cn ..... 85, [4194](#)  
 \toks\_put\_right:co ..... 85, [4194](#)  
 \toks\_put\_right:cV ..... 85, [4194](#)  
 \toks\_put\_right:Nf ..... 85, [4219](#), 4221  
 \toks\_put\_right:Nn .....  
 ..... 85, [4194](#), 4194, 4201, 4203,  
 4217, 4219, 4723, 5656, 5679, 5684  
 \toks\_put\_right:No .....  
 ..... 85, 4013, 4031, 4034, [4194](#),  
 4211, 5578, 5633, 5651, 5662, 5667  
 \toks\_put\_right:NV ..... 85, [4194](#), 4205  
 \toks\_put\_right:Nx ..... 85, [4194](#),  
 4328, 4330, 4507, 4509, 4686, 4688  
 \toks\_set:cf ..... 83, [4117](#)  
 \toks\_set:cn ..... 83, [4117](#)  
 \toks\_set:co ..... 83, [4117](#)  
 \toks\_set:cV ..... 83, [4117](#)  
 \toks\_set:cv ..... 83, [4117](#)  
 \toks\_set:cx ..... 83, [4117](#)  
 \toks\_set:Nf ... 83, [4117](#), 4130, 5575, 5583

<code>\toks_set:Nn</code> . . . . .	83, <a href="#">4117</a> , <a href="#">4118</a> , <a href="#">4119</a> , <a href="#">4122</a> , <a href="#">4134</a> , <a href="#">4743</a> , <a href="#">5975</a>	<code>\underline</code> . . . . .	218
<code>\toks_set:No</code> . . . . .	83, <a href="#">4011</a> , <a href="#">4117</a> , <a href="#">4129</a> , <a href="#">4593</a> , <a href="#">4594</a> , <a href="#">5590</a>	<code>\unexpanded</code> . . . . .	23, <a href="#">397</a>
<code>\toks_set:Nv</code> . . . . .	83, <a href="#">3944</a> , <a href="#">3978</a> , <a href="#">4117</a> , <a href="#">4123</a>	<code>\unhbox</code> . . . . .	323
<code>\toks_set:Nx</code> . . . . .	83, <a href="#">4117</a> , <a href="#">5441</a>	<code>\unhcopy</code> . . . . .	324
<code>\toks_set_eq:cc</code> . . . . .	83, <a href="#">4138</a> , <a href="#">4673</a>	<code>\unkern</code> . . . . .	248
<code>\toks_set_eq:cN</code> . . . . .	83, <a href="#">4138</a> , <a href="#">4672</a>	<code>\unless</code> . . . . .	388
<code>\toks_set_eq:Nc</code> . . . . .	83, <a href="#">4138</a> , <a href="#">4671</a>	<code>\unpenalty</code> . . . . .	359
<code>\toks_set_eq:NN</code> . . . . .	83, <a href="#">4138</a> , <a href="#">4139</a> , <a href="#">4151</a> , <a href="#">4154</a> , <a href="#">4670</a>	<code>\unskip</code> . . . . .	246
<code>\toks_show:c</code> . . . . .	84, <a href="#">4177</a> , <a href="#">4679</a>	<code>\unvbox</code> . . . . .	325
<code>\toks_show:N</code> . . . . .	84, <a href="#">4177</a> , <a href="#">4177</a> , <a href="#">4178</a> , <a href="#">4334</a> , <a href="#">4513</a> , <a href="#">4678</a> , <a href="#">4694</a>	<code>\unvcopy</code> . . . . .	326
<code>\toks_use:c</code> . . . . .	83, <a href="#">4115</a>	<code>\uppercase</code> . . . . .	356
<code>\toks_use:N</code> . . . . .	83, <a href="#">4016</a> , <a href="#">4040</a> , <a href="#">4115</a> , <a href="#">4115</a> , <a href="#">4116</a> , <a href="#">4181</a> , <a href="#">4195</a> , <a href="#">4207</a> , <a href="#">4213</a> , <a href="#">4223</a> , <a href="#">4235</a> , <a href="#">4596</a> , <a href="#">4598</a> , <a href="#">4701</a> , <a href="#">4777</a> , <a href="#">4940</a> , <a href="#">5447</a> , <a href="#">5453</a> , <a href="#">5475</a> , <a href="#">5479</a> , <a href="#">5579</a> , <a href="#">5592</a> , <a href="#">5635</a> , <a href="#">5653</a> , <a href="#">5964</a>	<code>\use:c</code> . . . . .	12, <a href="#">838</a> , 838, 942, 1615, 1619, 1629, 1885, 1902, 2845, 3105, 3141, 5080, 5127, 5138, 5144, 5153, 5160, 5166, 5172, 5223, 5236, 5244, 5734, 5990, 6612
<code>\toks_use_clear:c</code> . . . . .	84, <a href="#">4167</a>	<code>\use:n</code> . . . . .	12, <a href="#">839</a> , 839, 957, 962, 977, 982, 1337, 1954, 1964, 1974, 1984, 3104, 4019, 4038
<code>\toks_use_clear:N</code> 84, <a href="#">4167</a> , <a href="#">4167</a> , <a href="#">4173</a> , <a href="#">4175</a>		<code>\use:nn</code> . . . . .	12, <a href="#">839</a> , <a href="#">840</a>
<code>\toks_use_gclear:c</code> . . . . .	84, <a href="#">4167</a>	<code>\use:nnn</code> . . . . .	12, <a href="#">839</a> , <a href="#">841</a>
<code>\toks_use_gclear:N</code> . . 84, <a href="#">4167</a> , <a href="#">4170</a> , <a href="#">4176</a>		<code>\use:nnnn</code> . . . . .	12, <a href="#">839</a> , <a href="#">842</a>
<code>\toksdef</code> . . . . .	75	<code>\use_0_parameter:</code> . . . . .	<a href="#">1222</a>
<code>\tolerance</code> . . . . .	285	<code>\use_1_parameter:</code> . . . . .	<a href="#">1222</a>
<code>\topmark</code> . . . . .	166	<code>\use_2_parameter:</code> . . . . .	<a href="#">1222</a>
<code>\topmarks</code> . . . . .	392	<code>\use_3_parameter:</code> . . . . .	<a href="#">1222</a>
<code>\topskip</code> . . . . .	296	<code>\use_4_parameter:</code> . . . . .	<a href="#">1222</a>
<code>\totalheightof</code> . . . . .	132, <a href="#">6568</a> , <a href="#">6571</a>	<code>\use_5_parameter:</code> . . . . .	<a href="#">1222</a>
<code>\tracingassigns</code> . . . . .	402	<code>\use_6_parameter:</code> . . . . .	<a href="#">1222</a>
<code>\tracingcommands</code> . . . . .	141	<code>\use_7_parameter:</code> . . . . .	<a href="#">1222</a>
<code>\tracinggroups</code> . . . . .	409	<code>\use_8_parameter:</code> . . . . .	<a href="#">1222</a>
<code>\tracingifs</code> . . . . .	405	<code>\use_9_parameter:</code> . . . . .	<a href="#">1222</a>
<code>\tracinglostchars</code> . . . . .	142	<code>\use_i:nn</code> . . . . .	13, <a href="#">843</a> , <a href="#">843</a> , 952, 972, 1024, 1054, 1075, 1288, 4191
<code>\tracingmacros</code> . . . . .	143	<code>\use_i:nnn</code> . . . . .	13, <a href="#">845</a> , <a href="#">845</a> , 1036, 2504
<code>\tracingnesting</code> . . . . .	404	<code>\use_i:nnnn</code> . . . . .	13, <a href="#">845</a> , <a href="#">848</a>
<code>\tracingonline</code> . . . . .	144	<code>\use_i_after_else:nw</code> . . . . .	14, <a href="#">859</a> , <a href="#">860</a>
<code>\tracingoutput</code> . . . . .	145	<code>\use_i_after_fi:nw</code> 14, <a href="#">859</a> , <a href="#">859</a> , <a href="#">1324</a> , <a href="#">3037</a>	
<code>\tracingpages</code> . . . . .	146	<code>\use_i_after_or:nw</code> . . . . .	14, <a href="#">859</a> , <a href="#">861</a>
<code>\tracingparagraphs</code> . . . . .	147	<code>\use_i_after_orelse:nw</code> . . . . .	14, <a href="#">859</a> , <a href="#">862</a> , <a href="#">1304</a> , <a href="#">1306</a> , <a href="#">1308</a> , <a href="#">1310</a> , <a href="#">1312</a> , <a href="#">1314</a> , <a href="#">1316</a> , <a href="#">1318</a> , <a href="#">1320</a> , <a href="#">1322</a>
<code>\tracingrestores</code> . . . . .	148	<code>\use_i_delimit_by_q_nil:nw</code> . . . . .	14, <a href="#">856</a> , <a href="#">856</a> , <a href="#">4066</a>
<code>\tracingscantokens</code> . . . . .	403	<code>\use_i_delimit_by_q_recursion_stop:nw</code> . . . . .	14, <a href="#">856</a> , <a href="#">858</a> , <a href="#">2131</a> , <a href="#">2139</a>
<code>\tracingstats</code> . . . . .	149	<code>\use_i_delimit_by_q_stop:nw</code> . . . . .	14, <a href="#">856</a> , <a href="#">857</a> , <a href="#">4382</a>
U		<code>\use_i_ii:nnn</code> . . . . .	13, <a href="#">845</a> , <a href="#">852</a> , <a href="#">1513</a>
<code>\U</code> . . . . .	2404		
<code>\uccode</code> . . . . .	384		
<code>\uchyph</code> . . . . .	282		

- \use\_ii:nn ..... 13, 843, 844, 952,  
972, 1008, 1026, 1056, 1077, 1290, 5620
  - \use\_ii:nnn . 13, 845, 846, 1039, 2510, 5663
  - \use\_ii:nnnn ..... 13, 845, 849
  - \use\_iii:nnn ..... 13, 845, 847, 2516
  - \use\_iii:nnnn ..... 13, 845, 850
  - \use\_iv:nnnn ..... 13, 845, 851
  - \use\_none:n ..... 13, 863,  
863, 1010, 1326, 1648, 2133, 2141,  
2986, 2987, 2991, 4835, 5586, 5617
  - \use\_none:nn ..... 13,  
863, 864, 957, 962, 977, 982, 1637, 2835
  - \use\_none:nnn ..... 13, 863, 865, 5650
  - \use\_none:nnnn ..... 13, 863, 866
  - \use\_none:nnnnn ..... 13, 863, 867
  - \use\_none:nnnnnn ..... 13, 863, 868
  - \use\_none:nnnnnnn ..... 13, 863, 869
  - \use\_none:nnnnnnnn ..... 13, 863, 870
  - \use\_none:nnnnnnnnn ... 13, 863, 871, 1294
  - \use\_none\_delimit\_by\_q\_nil:w 14, 853, 853
  - \use\_none\_delimit\_by\_q\_recursion\_stop:w  
..... 14, 853, 855,  
940, 990, 1612, 2119, 2124, 3908, 4554
  - \use\_none\_delimit\_by\_q\_stop:w .....  
. 14, 853, 854, 2000, 2004, 4381, 4797
  - \usepackage ..... 734, 5490
- V**
- \vadjust ..... 259, 547
  - \valign ..... 94
  - \value ..... 5508
  - .value\_forbidden: ..... 126
  - .value\_required: ..... 126
  - \vbadness ..... 334
  - \vbox ..... 329
  - \vbox:n ..... 118, 5368, 5368
  - \vbox\_gset:cn ..... 118, 5369
  - \vbox\_gset:Nn ..... 118, 5369, 5371, 5372
  - \vbox\_gset\_inline\_begin:N 118, 5379, 5382
  - \vbox\_gset\_inline\_end: . 118, 5379, 5384
  - \vbox\_gset\_to\_ht:ccn ..... 118, 5373
  - \vbox\_gset\_to\_ht:cnn ..... 118, 5373
  - \vbox\_gset\_to\_ht:Nnn 118, 5373, 5377, 5378
  - \vbox\_set:cn ..... 118, 5369
  - \vbox\_set:Nn ..... 118, 5369, 5369–5371
  - \vbox\_set\_inline\_begin:N .....  
..... 118, 5379, 5379, 5383
  - \vbox\_set\_inline\_end: .. 118, 5379, 5381
  - \vbox\_set\_split\_to\_ht:NNn 119, 5387, 5387
  - \vbox\_set\_to\_ht:cnn ..... 118, 5373
  - \vbox\_set\_to\_ht:Nnn .....  
..... 118, 5373, 5373, 5376, 5377
  - \vbox\_to\_ht:nn ..... 119, 5385, 5385
  - \vbox\_to\_zero:n ..... 119, 5385, 5386
  - \vbox\_unpack:c ..... 119, 5390
  - \vbox\_unpack:N .... 119, 5390, 5390, 5391
  - \vbox\_unpack\_clear:c ..... 119, 5390
  - \vbox\_unpack\_clear:N 119, 5390, 5392, 5393
  - \vcenter ..... 180
  - \vfil ..... 241
  - \vfill ..... 243
  - \vfilneg ..... 242
  - \vfuzz ..... 336
  - \voffset ..... 311
  - \voidb@x ..... 5363
  - \vrule ..... 250
  - \vsize ..... 293
  - \vskip ..... 244
  - \vsplit ..... 322
  - \vss ..... 245
  - \vtop ..... 330
- W**
- \WARNING ..... 5470
  - \wd ..... 377
  - \widowpenalties ..... 437
  - \widowpenalty ..... 264
  - \widthof ..... 132, 6568, 6569
  - \wlog ..... 6727
  - \write ..... 127
- X**
- \X ..... 2400, 2404
  - \xdef ..... 68
  - \xetex\_if\_engine: ..... 1265, 1274
  - \xetex\_if\_engine:TF ..... 4, 25, 1260
  - \xetex\_version:D ..... 553, 556, 1260
  - \XeTeXversion ..... 553
  - \xleaders ..... 253
  - \xref\_deferred\_new:nn .....  
..... 119, 5433, 5434, 5505, 5508
  - \xref\_define\_label:nn 323, 5463, 5463, 5477
  - \xref\_define\_label\_aux:nn 5463, 5466, 5468
  - \xref\_get\_value:nn .....  
... 120, 5449, 5449, 5503, 5506, 5509
  - \xref\_new:nn ..... 119, 5433, 5433, 5501
  - \xref\_new\_aux:nnn ..... 5433, 5433–5435
  - \xref\_set\_label:n . 119, 5474, 5474, 5511
  - \xref\_tmp:w ..... 5475, 5478
  - \xref\_write ... 323, 5476, 5483, 5483, 5492

<code>\xspaceskip</code> .....	287	<b>Z</b>	
	<b>Y</b>	<code>\Z</code> .....	2402, 2404
<code>\Y</code> .....	2401, 2404	<code>\z@</code> .....	3374
<code>\year</code> .....	368		