

The ExSOL package*

Walter Daems (walter.daems@quantwerpen.be)

1 Introduction

1.1 Package goal

The package EXSOL provides macros to allow embedding exercises and solutions in the L^AT_EX source of an instructional text (e.g., a book or a course text) while keeping the exercises and the solutions apart in the typeset result.

In *global mode* (the default), this corresponds to generating the following separate documents:

- your original text that only contains the exercises, and
- a solution book that only contains the solutions to the exercises (a package option exists to also copy the exercises themselves to the solution book).

The former is generated when running L^AT_EX on your document. This run writes the solutions to a secondary file that can be included into a simple document harness, such that when running L^AT_EX on the latter, you can generate a nice solution book.

In *local mode* (invoked by specifying the package option 'local'), this corresponds to reading in the saved solutions in the current document at a later stage in the text.

1.2 Why use ExSol?

- It allows to keep the L^AT_EX source of your exercises and their solutions together in a single file, next to each other. Away with the nightmare to keep your solutions in sync with the exercises.
- It separates exercises and solutions, allowing you
 - to only release the solution book to the instructors of the course (using global mode);
 - to encourage students that you provide with the solutions separated from the exercises to first try solving the exercises without peeking into the list of solutions (or the solution book).

*This document corresponds to exsol 1.2, dated 2016/05/05.

1.3 Credits

The code of the EXSOL package was taken almost literally from `fancyvrb` [1]. Therefore, all credits go to the authors/maintainers of `fancyvrb`.

Thanks to Paul Levrie, Pieter Pareit, Pekka Pere, Benjamin Grinstein and Philippe Marti for signaling problems and making suggestions for the improvement of the package and the documentation.

1.4 Note

As of version 1.2, the package also contains facilities for generating a formula collection. The only limitation is that exercises and solutions cannot be part of the formula collection. Though this is a restriction, it is not a severe one in my opinion. Formula collections should be as concise as they can be.

Though generating formula collections goes beyond exercises and solutions, I chose not to change the package's name EXSOL. Einstein's name was also not changed into Relativistic Einstein when he got to understand the theory of relativity.

2 Installation

Either you are a package manager and then you'll know how to prepare an installation package for EXSOL.

Either you are a normal user and then you have two options. First, check if there is a package that your favorite L^AT_EX distributor has prepared for you. Second, grab the TDS package from CTAN [2] (`exsol.tds.zip`) and unzip it somewhere in your own TDS tree, regenerate your filename database and off you go. In any case, make sure that L^AT_EX finds the `exsol.sty` file.

The EXSOL package uses some auxiliary packages: `fancyvrb`, `ifthen`, `kvoptions` and, optionally, `babel`. Fetch them from CTAN [2] if your T_EX distributor does not provide them.

3 Usage

3.1 Preparing your document source

3.1.1 Loading the package

The macro package `exsol` can be loaded with:

```
\usepackage{exsol}
```

Your first choice to make is where you want your solutions to appear. The primary objective of the `exsol` package was 'global mode', i.e. separating your solutions

from the exercises, gathering the solutions in a separate book. To this end, don't specify the package option '[`local`]', or specify '[`local=false`]'.

A second mode of operation is 'local mode'. This allows grouping your exercises in series and including them later in your text. Gathering exercises in (numbered) series and 'loading' them locally in your text, allows for simplifying the individual exercise numbers (omitting their prefix containing, chapter number, section number, subsection number a.s.o.).

3.1.2 Global mode - flat grouping exercises

Adding exercises together with their solutions in your document is easy. Just embed them in a `exercise` and a corresponding `solution` environment. Optionally, you may embed several of them in a `exercises` environment to make them stand out in your text.

```
\begin{exercises}[columns=2]

\begin{exercise}
Calculate $y = 5 + 7$
\end{exercise}
\begin{solution}
$y = 12$
\end{solution}

\begin{exercise}
Calculate $y = 7 - 12$
\end{exercise}
\begin{solution}
$y = -5$
\end{solution}

\end{exercises}
```

The optional argument of the `exercises` environment allows specifying the typesetting in multiple columns.

On how to generate a solution book, take a look at the examples in section 3.2.1.

3.1.3 Local mode - grouping of exercises in series

One might also consider to keep the solutions in the same text, in local mode. In this case, we advise to gather the exercises in series (e.g. according to their degree of difficulty). This can be done by using the `exerciseseries` environment instead of the `exercises` environment. This environment takes and also takes a mandatory label argument. In addition it takes two optional arguments:

- `columns` to specify the amount of columns

- **exsubrule** to specify the creation of a horizontal rule below the exercise series.
- **solsubrule** to specify the creation of a horizontal rule below the solution series.
- **subrule** to specify the creation of a horizontal rule below the exercise and the solution series.

```
\begin{exerciseseries}[columns=2,subrule=\hrule]{Easy exercises}

\begin{exercise}
Calculate $y = 5 + 7$\\
\end{exercise}
\begin{solution}
$y = 12$\\
\end{solution}

\begin{exercise}
Calculate $y = 7 - 12$\\
\end{exercise}
\begin{solution}
$y = -5$\\
\end{solution}

\end{exerciseseries}

\begin{exerciseseries}{Difficult exercises}

\begin{exercise}
Calculate $y = 5 \cdot 7$\\
\end{exercise}
\begin{solution}
$y = 35$\\
\end{solution}

\begin{exercise}
Calculate $y = 8 / 4$\\
\end{exercise}
\begin{solution}
$y = 2$\\
\end{solution}

\end{exerciseseries}
```

3.2 Examples

3.2.1 Global mode

Below, you can find an example of a file that contains a number of exercises and solutions, with the goal to generate a separate solution book.

```
%<*example>
\documentclass[a4paper,10pt]{article}

\usepackage{a4wide}
\usepackage[english]{babel}
\usepackage[copyexercisesinsolutions]{exsol}

\titl{Gobal example, from the \textsf{ExSol} package}
\author{Walter Daems}
\setlength{\parindent}{0em}
\begin{document}
\maketitle

\section{Introduction}

In this text we explain how to solve second-order polynomial
equations.

\section{Solving second-order polynomial equations}

\begin{in formulacollectiononly}
\section*{Solving second-order polynomial equations}
\end{in formulacollectiononly}
\begin{in formulacollection}
The roots of the following equation
\begin{equation}
a x^2 + b x + c = 0
\end{equation}
can be determined as:
\begin{equation}
x_{1,2} = \frac{-b \pm \sqrt{b^2 - 4 a c}}{2 a}
\end{equation}
\end{in formulacollection}

\begin{exercises}[columns = 2]

\begin{exercise}
Solve the following equation for $x$ in $\mathbb{C}$, with $\mathbb{C}$ the set of
complex numbers:
\begin{equation}
5 x^2 - 3 x = 5
\end{equation}
\end{exercise}
\begin{solution}
Let's start by rearranging the equation, a bit:
\begin{eqnarray}
5.7 x^2 - 3.1 x &=& 5.3 \\
5.7 x^2 - 3.1 x - 5.3 &=& 0
\end{eqnarray}
The equation is now in the standard form:
\begin{equation}
a x^2 + b x + c = 0
\end{equation}
For quadratic equations in the standard form, we know that two
solutions exist:
\begin{equation}
x_{1,2} = \frac{-b \pm \sqrt{d}}{2a}
\end{equation}
with
\begin{equation}
d = b^2 - 4 a c
\end{equation}



```

```

If we apply this to our case, we obtain:
\begin{equation}
d = (-3.1)^2 - 4 \cdot 5.7 \cdot (-5.3) = 130.45
\end{equation}
and
\begin{eqnarray}
x_1 &=& \frac{3.1 + \sqrt{130.45}}{11.4} = 1.27 \\
x_2 &=& \frac{3.1 - \sqrt{130.45}}{11.4} = -0.73
\end{eqnarray}
The proposed values  $x = x_1, x_2$  are solutions to the given equation.
\end{solution}
\begin{exercise}
Consider a 2-dimensional vector space equipped with a Euclidean
distance function. Given a right-angled triangle, with the sides
$A$ and $B$ adjacent to the right angle having lengths, $3$ and
$4$, calculate the length of the hypotenuse, labeled $C$.
\end{exercise}
\begin{solution}
This calls for application of Pythagoras' theorem, which
tells us:
\begin{equation}
\left|A\right|^2 + \left|B\right|^2 = \left|C\right|^2
\end{equation}
and therefore:
\begin{eqnarray}
\left|C\right|^2 \\
&=& \sqrt{\left|A\right|^2 + \left|B\right|^2} \\
&=& \sqrt{3^2 + 4^2} \\
&=& \sqrt{25} = 5
\end{eqnarray}
Therefore, the length of the hypotenuse equals $5$.
\end{solution}
\end{exercises}
\end{document}
%</example>

```

The result in the original document, can be seen in the file `example.pdf`. As you can see, the `formulacollection` entry and the exercise appear. There's no trace of the solution.

When running `LATEX` on your document (e.g., the file `example.tex` as part of the `exsol` package, as a side effect files with the extension `.sol.tex` and `.fc.tex` have been written to disk (in our case, the files `example.sol.tex` and `example.fc.tex`), containing all solutions and entries for the formula collection in sequence.

Generating a solution book is as simple as including the solution file into a simple `LATEX` harness, that allows you giving it a proper title page and to add other bells and whistles. This can be seen below:

```

%<*examplesol>
\documentclass[a4paper,10pt]{article}

\usepackage{a4wide}
\usepackage[english]{babel}
\usepackage{exsol}

```

```

\setlength{\parindent}{0em}

\titulo{Solutions to the exercises, specified in the example of the
    \textsf{ExSol} package}
\autor{Walter Daems}

\begin{document}
\maketitle
\input{example.sol.tex}

\end{document}
%</examplesol>

```

Generating a formula collection is as simple as including the formula collectoin file into a simple L^AT_EX harness, that allows you giving it a proper title page and to add other bells and whistles. This can be seen below:

```

%<*examplefor>
\documentclass[a4paper,10pt]{article}

\usepackage{a4wide}
\usepackage[english]{babel}
\usepackage{exsol}

\setlength{\parindent}{0em}

\titulo{Formula collection, specified in the example of the
    \textsf{ExSol} package}
\autor{Walter Daems}

\begin{document}
\maketitle
\input{example.fc.tex}

\end{document}
%</examplefor>

```

3.2.2 Local mode

Below, you can find an example of a file that contains a number of exercises and solutions, with the goal to include them later in the same document. This is done by issuing the `loadSolutions` macro at the very end of the file. This macro can be called multiple times and will gobble up and include all solutions so far. As a consequence the solutions file is emptied and can be filled again by specifying new exercise/solution pairs.

```

%<*example-local>
\documentclass[a4paper,10pt]{article}

\usepackage{a4wide}
\usepackage[german]{babel}
\usepackage[local,nolabels,exerciseaslist]{exsol}
\usepackage{enumitem}

```

```

\setlength{\exsolexercisetopbottomsep}{0pt plus 0pt minus 1pt}
\setlength{\exsolexerciseleftmargin}{2em}
\setlength{\exsolexerciserightmargin}{1em}
\setlength{\exsolexerciseparindent}{0em}
\setlength{\exsolexerciselabelsep}{1ex}
\setlength{\exsolexerciselabelwidth}{30pt}
\setlength{\exsolexercisitemindent}{0pt}
\setlength{\exsolexerciseparsep}{\parskip}

\titl{Local example, from the \textsf{ExSol} package}
\author{Philippe Marti}
\setlength{\parindent}{0em}
\begin{document}
\maketitle

\section{\exercisesname}

\begin{exercisseries}[columns=2,solsubrule=\hrule]{Gleichungen $|$ Gleichungssysteme}

\begin{exercise}
Die Summe zweier Zahlen ist 17 und ihre Differenz 7. Bestimme die beiden Zahlen!
\end{exercise}
\begin{solution}
5 und 12
\end{solution}

\begin{exercise}
Die Differenz einer Zahl und dem Dreifachen einer zweiten Zahl ist 14. Bestimme die beiden Zahlen, falls die zweite Zahl ein Zehntel der ersten ist.
\end{exercise}
\begin{solution}
20 und 2
\end{solution}

\end{exercisseries}

\begin{exercisseries}[columns=2]{Geraden}

\begin{exercise}
Berechne den Schnittpunkt von  $y=3x+1$  und  $y=3x-7$ .
\end{exercise}
\begin{solution}
Es gibt keinen Schnittpunkt
\end{solution}

\begin{exercise}
Die Familie Meier fordert Offerten f\"ur eine Heizungsreparatur ein. Firma A berechnet f\"ur die Fahrtkosten Fr. 42.- und f\"ur jede Arbeitsstunde 76.-. Bei der Firma B sind die Fahrtkosten Fr. 35.- und jede Arbeitsstunde wird mit Fr. 80.- berechnet.
\begin{enumerate}[label=\alph*]
\item Welche Kosten entstehen f\"ur beide Firmen, wenn ein Monteur 3.5 Stunden f\"ur die Arbeit benötigt? Welche Firma ist in diesem Fall kostengünstiger?
\item Wie lauten die Gleichungen derjenigen zwei linearen Funktionen, die jeder Arbeitszeit  $x$  (in Stunden) die entstehenden Kosten  $y$  (in Franken) zuordnet?
\end{enumerate}
\end{exercise}

```

```

\item Berechne, bei welcher Arbeitszeit die Kosten bei beiden
Firmen gleich sind.
\end{enumerate}
\end{exercise}
\begin{solution}
\begin{enumerate}[label=\alph*]
\item Firma A: 308.- \$|\$ Firma B: 315.-
\item A:  $y=76x+42$  \$|\$ B:  $y=80x+35$ 
\item Bei  $\frac{3}{4}$  Stunden
\end{enumerate}
\end{solution}
\end{exerciseseries}

\section{\solutionsname}
\loadSolutions

\end{document}
%</example-local>

```

3.3 Fiddling with the spacing

The default spacing provided by the `ExSol` package should be fine for most users. However, if you like to tweak, below you can find the controls.

As the formula collection generation is intended to interfere as little as possible with the flow of the main document, you will notice that it is impossible to control the extra spacing, as no extra spacing should originate from using the `informulacollection` environment.

3.3.1 Spacing before and after the `exercises` environment

The lengths below control the spacing of the `exercises` environment:

- `exsolexerciseaboveskip`: rubber length controlling the vertical space after the top marker line of the environment
- `exsolexercisebelowskip`: rubber length controlling the vertical space before the bottom marker line of the environment

You can simply specify them like:

```

\setlength{\exsolexerciseaboveskip}{1ex plus 1pt minus 1pt}
\setlength{\exsolexercisebelowskip}{1ex plus 1pt minus 1pt}

```

The spacings specified here are the package defaults.

3.3.2 Spacing of the individual exercises

Caution: the spacing can only be tuned, when one invokes the `exerciseaslist` package option!

Then lengths below control the spacing of the `exercise` environment:

- **`exercisetopbottomsep`**: rubber length controlling the vertical space before and after individual exercises
- **`exerciseleftmargin`**: length controlling the horizontal space between the surrounding environment's left margin (most often the page margin) and the left edge of the exercise environment
- **`exerciseleftmargin`**: length controlling the horizontal space between the surrounding environment's right margin (most often the page margin) and the right edge of the exercise environment
- **`exerciseitemindent`**: length controlling the first-line indentation of the first paragraph in the exercise environment (actually, the label is set w.r.t. this position, that we will conveniently call position 'x')
- **`exercisesepindent`**: length controlling the first-line indentation of the other paragraphs in the exercise environment.
- **`exerciselabelsep`**: length controlling the distance between the label and position 'x'
- **`exerciselabelwidth`**: minimal width of the (internally right-alligned) box to use for the exercises label; if the box is not sufficiently big, position 'x' is shifted to the right
- **`exercisesepsep`**: internal paragraph separation (vertically)

You can simply specify them like:

```
\setlength{\exsolexercisetopbottomsep}{0pt plus 0pt minus 1pt}
\setlength{\exsolexerciseleftmargin}{1em}
\setlength{\exsolexerciserightmargin}{1em}
\setlength{\exsolexercisepindent}{0em}
\setlength{\exsolexerciselabelsep}{0.5em}
\setlength{\exsolexerciselabelwidth}{0pt}
\setlength{\exsolexerciseitemindent}{0pt}
\setlength{\exsolexercisepsep}{\parskip}
```

The spacings specified here are the package defaults.

3.4 Tips and tricks

If you want to include the solutions all at the end of the current document in global mode, you need to explicitly close the solution stream before including it:

```
\closeout\solutionstream\input{\jobname.sol.tex}
```

If you want to avoid exercises being split by a page boundary, then provide the package option 'minipage'. This causes the exercises to be wrapped in a minipage environment.

4 Implementation

1 `(*package)`

4.1 Auxiliary packages

The package uses some auxiliary packages:

2 `\RequirePackage{ifmtarg}`
3 `\RequirePackage{fancyvrb}`
4 `\RequirePackage{ifthen}`
5 `\RequirePackage{kvoptions}`
6 `\RequirePackage{multicol}`

4.2 Package options

The package offers some options:

- local** This boolean option (true, false) allows setting the mode of the package into local, i.e. that the numbering of the exercises is not related to the position in the document, but uses it's own local counter in combination with a exerciseseries counter.

7 `\DeclareBoolOption[false]{local}`

- nolabels** This boolean option (true, false) allows suppressing the 'Exercise' and 'Solution' label that normally appear before the exercise and solution number.

8 `\DeclareBoolOption[false]{nolabels}`

- exercisesfontsize** This option allows setting the font of the `exercises` environment. You may chose one of tiny, scriptsize, footnotesize, small, normalsize, large, etc.
E.g., `[exercisesfontsize=small]`.

9 `\DeclareStringOption[normalsize]{exercisesfontsize}`

- exerciseaslist** This boolean option (true, false) allows setting the typesetting of the `exercises` in a list environment. This causes the exercises to be typeset in a more compact fashion, with indented left and right margin.

10 `\DeclareBoolOption[false]{exerciseaslist}`

- copyexercisesinsolutions** This boolean option (true, false) allows copying the exercises in the solutions file, to allow for making a complete stand-alone exercises bundle.

11 `\DeclareBoolOption[false]{copyexercisesinsolutions}`

- `minipage` This boolean option (true, false) causes the exercises to be wrapped in minipages. This avoids them getting split by a page boundary.

```
12 \DeclareBoolOption[false]{minipage}
```

The options are processed using:

```
13 \ProcessKeyvalOptions*
```

The options are subsequently handled

```
14 \newcommand{\exercisesfontsize}{\csname \exsol@exercisesfontsize\endcsname}
```

4.3 Customization of lengths

The commands below allow customizing many lengths that control the typesetting of the exercises.

First some lengths to control the spacing before and after `exercises`.

```
15 \newlength{\exsolexercisaboveskip}
16 \setlength{\exsolexercisaboveskip}{0ex plus 1pt minus 1pt}
17 \newlength{\exsolexerciselowskip}
18 \setlength{\exsolexerciselowskip}{0ex plus 1pt minus 1pt}
```

Then some lengths to control the spacing for a single exercise. These lengths only work when the `exerciseaslist` package option has been specified. Sensible defaults have been set.

```
19 \newlength{\exsolexercisetopbottomsep}
20 \setlength{\exsolexercisetopbottomsep}{0pt plus 0pt minus 1pt}
21 \newlength{\exsolexerciseleftmargin}
22 \setlength{\exsolexerciseleftmargin}{1em}
23 \newlength{\exsolexerciserightmargin}
24 \setlength{\exsolexerciserightmargin}{1em}
25 \newlength{\exsolexerciseparindent}
26 \setlength{\exsolexerciseparindent}{0em}
27 \newlength{\exsolexerciselabelsep}
28 \setlength{\exsolexerciselabelsep}{0.5em}
29 \newlength{\exsolexerciselabelwidth}
30 \setlength{\exsolexerciselabelwidth}{0pt}
31 \newlength{\exsolexerciseitemindent}
32 \setlength{\exsolexerciseitemindent}{0pt}
33 \newlength{\exsolexerciseparsep}
34 \setlength{\exsolexerciseparsep}{\parskip}
```

4.4 Con- and destruction of the auxiliary streams

At the beginning of your document, we start by opening a stream to a file that will be used to write the solutions to. At the end of your document, the package closes the stream.

```

35 \AtBeginDocument{
36   \typeout{Writing solutions to solution file \jobname.sol.tex}
37   \newwrite\solutionstream
38   \immediate\openout\solutionstream=\jobname.sol.tex
39   \typeout{Using intermediate exercise file \jobname.exc.tex}
40   \newwrite\exercisestream
41   \typeout{Writing formulae to formula collection file \jobname.fc.tex}
42   \newwrite\formulacollectionstream
43   \immediate\openout\formulacollectionstream=\jobname.fc.tex
44   \typeout{Using intermediate formula file \jobname.for.tex}
45   \newwrite\formulastream
46 }
47 \AtEndDocument{
48   \immediate\closeout\formulacollectionstream
49   \immediate\closeout\solutionstream
50 }

```

In local mode we also want to close the solutionstream, read it and open it again:

```

51 \newcommand\loadSolutions{
52   \immediate\closeout\solutionstream
53   \input{\jobname.sol.tex}
54 % \immediate\openout\solutionstream=\jobname.sol.tex
55 }

```

4.5 Series counter

By providing an exerciseseries counter, proper numbering of the exercise series is provided. Note that separate series, render the numbering of the exercises from document-global, to series-local, therefore hindering the concordance of solutions to exercises.

```

56 \newcounter{exerciseseries}[subsubsection]
57 \setcounter{exerciseseries}{0}
58 \renewcommand{\theexerciseseries}{\arabic{exerciseseries}}

```

4.6 Exercise counter

By providing an exercise counter, proper numbering of the exercises is provided to allow for good cross referencing of the solutions to the exercises.

```

59 \newcounter{exercise}[exerciseseries]
60 \setcounter{exercise}{0}
61 \renewcommand{\theexercise}{%
62   \ifx\sol@local
63   \arabic{exerciseseries}.\arabic{exercise}%
64   \else
65   \@ifundefined{c@chapter}{}{\if0\arabic{chapter}\else\arabic{chapter}.\fi}%
66   \if0\arabic{section}\else\arabic{section}\fi%
67   \if0\arabic{subsection}\else.\arabic{subsection}\fi%
68   \if0\arabic{subsubsection}\else.\arabic{subsubsection}\fi%
69   \if0\arabic{exercise}\else%

```

```

70  \@ifundefined{c@chapter}%
71  { \if0\arabic{section}\else-\fi }%
72  {-}%
73  \arabic{exercise}%
74  \fi
75  \fi
76 }

```

4.7 Detokenization in order to cope with utf8

Combining old-school L^AT_EX (before X_ET_EX and LuaT_EX) and UTF-8 is a pain. Detokenization has been suggested by Geoffrey Poore to solve issues with UTF-8 characters messing up the `fancyvrb` internals.

```

77 \newcommand{\GPES@write@detok}[1]{%
78   \immediate\write\exercisestream{\detokenize{\#1}}}%
79 \newcommand{\GPSS@write@detok}[1]{%
80   \immediate\write\solutionstream{\detokenize{\#1}}}%
81 \newcommand{\GPESS@write@detok}[1]{%
82   \GPES@write@detok{\#1}%
83   \GPSS@write@detok{\#1}}%
84 \newcommand{\GPFORCOL@write@detok}[1]{%
85   \immediate\write\formulacollectionstream{\detokenize{\#1}}}%
86   \immediate\write\formulastream{\detokenize{\#1}}}%
87 \newcommand{\GPFORCOLONLY@write@detok}[1]{%
88   \immediate\write\formulacollectionstream{\detokenize{\#1}}}%

```

5 The user environments

- exercise** The `exercise` environment is used to typeset your exercises, provide them with a nice label and allow for copying the exercise to the solutions file (if the package option `copyexercisesinsolution`) is set. The label can be set by redefining the `\exercisename` macro, or by relying on the Babel provisions. The code is almost litteraly taken from the `fancyvrb` package.

```

89 \def\exercise{\FV@Environment{}{exercise}}
90 \def\FVB@exercise{%
91   \refstepcounter{exercise}%
92   \immediate\openout\exercisestream=\jobname.exc.tex
93   \ifexsol@local
94 %   \immediate\write\solutionstream{}%
95   \else
96 %   \immediate\write\solutionstream{\string\vspace*\string{2ex}\string}%
97 %   \string\quad\string\newline}
98   \fi
99   \ifexsol@copyexercisesinsolutions
100   % WDSC tofix
101   % \typeout{Writing exercise to \jobname.sol.tex}
102   \immediate\write\solutionstream{\string\begin{exsol@exercise}{\theexercise}}
103   \fi
104   \immediate\write\exercisestream{\string\begin{exsol@exercise}{\theexercise}}%

```

```

105  \@bsphack
106  \begingroup
107    \FV@UseKeyValues
108    \FV@DefineWhiteSpace
109    \def\FV@Space{\space}%
110    \FV@DefineTabOut
111    \ifexsol@copyexercisesinsolutions
112      \let\FV@ProcessLine\GPESST@write@detok %
113    \else
114      \let\FV@ProcessLine\GPES@write@detok %
115    \fi
116    \relax
117    \let\FV@FontScanPrep\relax
118    \let\@noligs\relax
119    \FV@Scan
120  }
121 \def\FVE@exercise{
122   \endgroup\@esphack
123   \immediate\write\exercisestream{\string\end{exsol@exercise}}
124   \ifexsol@copyexercisesinsolutions
125     \immediate\write\solutionstream{\string\end{exsol@exercise}}
126   \fi
127   \immediate\closeout\exercisestream
128   \input{\jobname.exc.tex}
129 }
130 \DefineVerbatimEnvironment{exercise}{exercise}{}

```

exsol@exercise The `exsol@exercise` environment is an internal macro used to typeset your exercises and provide them with a nice label and number. Do not use it directly. Use the proper environment `exercise` instead.

```

131 \newenvironment{exsol@exercise}[1]
132 {%
133   \ifthenelse{\boolean{exsol@minipage}}{\begin{minipage}[t]{\textwidth}}{}%
134   \ifthenelse{\boolean{exsol@exerciseaslist}}
135     {\begin{list}%
136       {%
137       }%
138       {%
139         \setlength{\topsep}{\exsolexercisetopbottomsep}%
140         \setlength{\leftmargin}{\exsolexerciseleftmargin}%
141         \setlength{\rightmargin}{\exsolexicerightmargin}%
142         \setlength{\listparindent}{\exsolexerciseparindent}%
143         \setlength{\itemindent}{\exsolexerciseitemindent}%
144         \setlength{\parsep}{\exsolexerciseparsep}%
145         \setlength{\labelsep}{\exsolexerciselabelsep}%
146         \setlength{\labelwidth}{\exsolexerciselabelwidth}%
147         \item[\ifexsol@nolabels~#1:\else%
148           \subparagraph{\exercisename{}~#1:}\fi]%
149         }%
150         \ifexsol@nolabels~#1:\else%
151           \subparagraph{\exercisename{}~#1:}\fi%
152       }%
153     {%

```

```

154 \ifthenelse{\boolean{exsol@exerciseaslist}}%
155   {\end{list}}{}%
156 \ifthenelse{\boolean{exsol@minipage}}{\end{minipage}}{\par}%
157 }

```

solution The **solution** environment is used to typeset your solutions and provide them with a nice label and number that corresponds to the exercise that preceded this solution. The label can be set by redefining the **\solutionname** macro, or by relying on the **Babel** provisions. The code is almost literally taken from the **fancyvrb** package.

```

158 \def\solution{\FV@Environment{}{solution}}
159 \def\FVB@solution{%
160   \%typeout{Writing solution to \jobname.sol.tex}
161   \ifexsol@copyexercisesinsolutions
162     \immediate\write\solutionstream{\string\begin{exsol@solution}{}}
163   \else
164     \immediate\write\solutionstream{\string\begin{exsol@solution}{\theexercise}}
165   \fi
166   \@bsphack
167   \begingroup
168     \FV@UseKeyValues
169     \FV@DefineWhiteSpace
170     \def\FV@Space{\space}%
171     \FV@DefineTabOut
172     \let\FV@ProcessLine\GPSS@write@detok %
173     \relax
174     \let\FV@FontScanPrep\relax
175     \let\@noligs\relax
176     \FV@Scan
177   }
178 \def\FVE@solution{
179   \endgroup\@esphack
180   \immediate\write\solutionstream{\string\end{exsol@solution}}
181 }
182 \DefineVerbatimEnvironment{solution}{solution}{}

```

exsol@solution The **exsol@solution** environment is an internal macro used to typeset your solutions. Do not use it directly. Use the proper environment **solution** instead.

```

183 \newenvironment{exsol@solution}[1]
184 {%
185   \ifthenelse{\boolean{exsol@minipage}}{\begin{minipage}[t]{\textwidth}}{}%
186   \ifthenelse{\boolean{exsol@exerciseaslist}}%
187   {\begin{list}%
188     {%
189     }%
190     {%
191       \setlength{\topsep}{\exsolexercisetopbottomsep}%
192       \setlength{\leftmargin}{\exsolexerciseleftmargin}%
193       \setlength{\rightmargin}{\exsolexerciserightmargin}%
194       \setlength{\listparindent}{\exsolexerciseparindent}%

```

```

195      \setlength{\itemindent}{\exsolexerciseitemindent}%
196      \setlength{\parsep}{\exsolexerciseparsep}
197      \setlength{\labelsep}{\exsolexerciselabelsep}
198      \setlength{\labelwidth}{\exsolexerciselabelwidth}%
199      \item[{\ifexsol@nolabels #1:\else%
200          \subparagraph{\solutionname{}@\ifmtarg{#1}{}{~}#1:}\fi}]
201      }%
202      {\ifexsol@nolabels #1:\else%
203          \subparagraph{\solutionname{}@\ifmtarg{#1}{}{~}#1:}\fi}
204      }%
205      {%
206          \ifthenelse{\boolean{exsol@exerciseaslist}}{%
207              {\end{list}}{}}%
208          \ifthenelse{\boolean{exsol@minipage}}{%
209              {\end{minipage}}{\par}%
209 }

```

- exercises** The `exercises` environment helps typesetting your exercises to stand out from the rest of the text. You may use it at the end of a chapter, or just to group some exercises in the text.

```

210 \define@key{exercises}{columns}{\renewcommand\columncount{#1}}
211 \define@key{exercises}{exsubrule}{\renewcommand\exsubrule{#1}}
212 \define@key{exercises}{solsubrule}{\renewcommand\solsubrule{#1}}
213 \define@key{exercises}{subrule}{\renewcommand\exsubrule{#1}\renewcommand\solsubrule{#1}}
214 \newenvironment{exercises}[1] []
215 {
216     \newcommand\columncount{1} % default
217     \newcommand\exsubrule{} % default
218     \newcommand\solsubrule{} % default
219     \setkeys{exercises}{#1}
220     \par\exercisesfont\size\rule{.25\linewidth}{0.15mm}%
221     \vspace*{\exsolexercisesaboveskip}%
222     \paragraph{\exercisesname}~\par
223     \ifthenelse{\columncount > 1}{\begin{multicols}{\columncount}}{%
224     }%
225     {%
226     \ifthenelse{\columncount > 1}{\end{multicols}}{}\relax
227     \vspace*{-\baselineskip}\vspace*{\exsolexercisesbelowskip}%
228     \rule{.25\linewidth}{0.15mm}%
229     \exsubrule\par}

```

- exerciseseries** The `exerciseseries` environment helps typesetting your exercises in series.

```

230 \define@key{exerciseseries}{columns}{\renewcommand\columncount{#1}}
231 \define@key{exerciseseries}{exsubrule}{\renewcommand\exsubrule{#1}}
232 \define@key{exerciseseries}{solsubrule}{\renewcommand\solsubrule{#1}}
233 \define@key{exerciseseries}{subrule}{\renewcommand\exsubrule{#1}\renewcommand\solsubrule{#1}}
234 \newenvironment{exerciseseries}[2] []
235 {
236     \refstepcounter{exerciseseries}%
237     \newcommand\columncount{1} % default
238     \newcommand\exsubrule{} % default
239     \newcommand\solsubrule{} % default

```

```

240 \setkeys{exerciseseries}{#1}
241 \paragraph{\seriesname~\theexerciseseries:#2}\par
242 \ifthenelse{\columncount > 1}{\begin{multicols}{\columncount}}{}
243   \immediate\write\solutionstream{\string\begin\string{solutionseries}\string%
244     \string[#1\string]\string{#2\string}\string{\theexerciseseries\string}}
245 }
246 {
247   \ifthenelse{\columncount > 1}{\end{multicols}}{}\relax
248   \exsubrule\par
249   \immediate\write\solutionstream{\string\end\string{solutionseries}\string}
250 }
251 \newenvironment{solutionseries}[3] []
252 {
253   \newcommand\columncount{1} % default
254   \newcommand\exsubrule{} % default
255   \newcommand\solsubrule{} % default
256   \setkeys{exercises}{#1}
257   \paragraph{\seriesname:#3}\par
258   \ifthenelse{\columncount > 1}{\begin{multicols}{\columncount}}{}
259 }
260 {
261   \ifthenelse{\columncount > 1}{\end{multicols}}{}\relax
262   \solsubrule\par
263 }

```

informulacollection The **informulacollection** environment is used to write its contents to the formula collection stream and load back into the main text for typesetting. The code is almost litteraly taken from the **fancyvrb** package.

```

264 \def\informulacollection{\FV@Environment{\informulacollection}}
265 \def\FVB@informulacollection{%
266   \immediate\openout\formulastream=\jobname.for.tex
267   %\typeout{Writing formula to \jobname.for.tex and \jobname.fc.tex}
268   \@bsphack
269   \begingroup
270     \FV@UseKeyValues
271     \FV@DefineWhiteSpace
272     \def\FV@Space{\space}%
273     \FV@DefineTabOut
274     \let\FV@ProcessLine\GPFORCOL@write@detok %
275     \relax
276     \let\FV@FontScanPrep\relax
277     \let\@noligs\relax
278     \FV@Scan
279   }
280 \def\FVE@informulacollection{
281   \endgroup\@espshack
282   \immediate\closeout\formulastream
283   \input{\jobname.for.tex}
284 }
285 \DefineVerbatimEnvironment{informulacollection}{informulacollection}{}

```

informulacollectiononly The **informulacollectiononly** environment is used to write its contents to the

formula collection stream *without* loading it back into the main text for typesetting. The code is almost litteraly taken from the `fancyvrb` package.

```

286 \def\informulacollectiononly{\FV@Environment{}{informulacollectiononly}}
287 \def\FVB@informulacollectiononly{%
288   \%typeout{Writing special to \jobname.fc.tex}
289   \@bsphack
290   \begingroup
291     \FV@UseKeyValues
292     \FV@DefineWhiteSpace
293     \def\FV@Space{\space}%
294     \FV@DefineTabOut
295     \let\FV@ProcessLine\GPFORCOLONLY@write@detok %
296     \relax
297     \let\FV@FontScanPrep\relax
298     \let\@noligs\relax
299     \FV@Scan
300   }
301 \def\FVE@informulacollectiononly{%
302   \endgroup\@esphack
303 }
304 \DefineVerbatimEnvironment{informulacollectiononly}{informulacollectiononly}{}

```

5.1 Some Babel provisions

```

305 \newcommand{\exercisename}{Exercise}
306 \newcommand{\exercisesname}{Exercises}
307 \newcommand{\solutionname}{Solution}
308 \newcommand{\solutionsname}{Solutions}
309 \newcommand{\seriesname}{Series}

```

You may redefine these macros, but to help you out a little bit, we provide with some basic Babel auxiliaries. If you're a true polyglot and are willing to help me out by providing translations for other languages, I'm very willing to incorporate them into the code.

```

310 \addto\captionsdutch{%
311   \renewcommand{\exercisename}{Oefening}%
312   \renewcommand{\exercisesname}{Oefeningen}%
313   \renewcommand{\solutionname}{Oplossing}%
314   \renewcommand{\solutionsname}{Oplossingen}%
315   \renewcommand{\seriesname}{Reeks}%
316 }
317 \addto\captionsgerman{%
318   \renewcommand{\exercisename}{Aufgabe}%
319   \renewcommand{\exercisesname}{Aufgaben}%
320   \renewcommand{\solutionname}{L\"osung}%
321   \renewcommand{\solutionsname}{L\"osungen}%
322   \renewcommand{\seriesname}{Serie}%
323 }
324 \addto\captionsngerman{%
325   \renewcommand{\exercisename}{Aufgabe}%
326   \renewcommand{\exercisesname}{Aufgaben}%

```

```

327 \renewcommand{\solutionname}{L\"osung}%
328 \renewcommand{\solutionsname}{L\"osungen}%
329 \renewcommand{\seriesname}{Serie}%
330 }
331 \addto\captionsfrench{%
332 \renewcommand{\exercisename}{Exercice}%
333 \renewcommand{\exercisesname}{Exercices}%
334 \renewcommand{\solutionname}{Solution}%
335 \renewcommand{\solutionsname}{Solutions}%
336 \renewcommand{\seriesname}{Serie}%
337 }
338 \addto\captionsfinnish{%
339 \renewcommand{\exercisename}{Teht\"av\"a}%
340 \renewcommand{\exercisesname}{Teht\"avi\"a}%
341 \renewcommand{\solutionname}{Ratkaisu}%
342 \renewcommand{\solutionsname}{Ratkaisut}%
343 \renewcommand{\seriesname}{Sarja}%
344 }
345 \addto\captionsspanish{%
346 \renewcommand{\exercisename}{Ejercicio}%
347 \renewcommand{\exercisesname}{Ejercicios}%
348 \renewcommand{\solutionname}{Soluci\'on}%
349 \renewcommand{\solutionsname}{Soluciones}%
350 \renewcommand{\seriesname}{Serie}%
351 }

```

Now the final hack overloads the basic sectioning commands to make sure that they are copied into your solution book.

```

352 \ifexsol@local
353 \else
354 \let\exsol@@makechapterhead\@makechapterhead
355 \def\@makechapterhead#1{%
356   \exsol@@makechapterhead{#1}
357   \immediate\write\solutionstream{\string\setcounter{chapter}{\arabic{chapter}}\%
358     \string\chapter{#1}\%}
359 }
360 \ifdefined\frontmatter
361   \let\exsol@frontmatter\frontmatter
362   \def\frontmatter{%
363     \immediate\write\solutionstream{\string\frontmatter}\%
364     \exsol@@frontmatter
365   }
366 \fi
367 \ifdefined\frontmatter
368   \let\exsol@mainmatter\mainmatter
369   \def\mainmatter{%
370     \immediate\write\solutionstream{\string\mainmatter}\%
371     \exsol@@mainmatter
372   }
373 \fi
374 \ifdefined\backmatter
375   \let\exsol@backmatter\backmatter
376   \def\backmatter{%

```

```

377     \immediate\write\solutionstream{\string\backmatter}%
378     \exsol@@backmatter
379   }
380 \fi
381 \ifdefinable\appendix
382   \let\exsol@@appendix\appendix
383   \def\appendix{%
384     \immediate\write\solutionstream{\string\appendix}%
385     \exsol@@appendix
386   }
387 \fi
388 \fi

```

`\noexercisesinchapter` If you have chapters without exercises, you may want to indicate this clearly into your source. Otherwise empty chapters may appear in your solution book.

```

389 \newcommand{\noexercisesinchapter}{%
390 {
391   \immediate\write\solutionstream{No exercises in this chapter}
392 }
393 </package>

```

References

- [1] Timothy Van Zandt, Herbert Voß, Denis Girou, Sebastian Rahtz, Niall Mansfield The `fancyvrb` package. <http://ctan.org/pkg/fancyvrb>. online, accessed in January 2012.
- [2] The Comprehensive TeX Archive Network. <http://www.ctan.org>. online, accessed in January 2012.

Change History

	v0.1	v0.3	
	General: Initial version	1	
v0.2	General: Minor bug fixes based on first use by Paul Levrie	1	
	Added option <code>exercisesfont</code> ...	11	
	Fixed babel errors	19	
	Removed dash in counter when in document without sectioning commands	13	
	<code>exercises</code> : Attempted to fix MiK- TeX formatting problems ...	17	
	<code>exsol@exercise</code> : Attempted to fix MiKTeX formatting problems	15	
		v0.4	
		General: Minor bug fixes based on second use by Paul	1
		<code>exercises</code> : Added some extra whitespace below <code>exercises-</code> name	17
		<code>exsol@exercise</code> : Fixed <code>labelsep</code> to avoid cluttered <code>itemize</code> environ- ments	15
		General: Allowed for non-list for- matting of exercises (as de- fault)	1
		Added option <code>exercisesinlist</code> ...	11
		Changed name of option to exer-	

cisesfontsize	11	v0.91
exsol@exercise: Added option exercisesinlist such that default results in non list formatting of exercise	15	
v0.5		
General: Added option to also send exercises to solutions file	1	
Added option copyexercisesinsolutions	11	
Changed option exercisesinlist to exerciseaslist	11	
exsol@exercise: Changed implementation to allow for copying the exercises to the solutions file.	15	
v0.6		
General: Prepared for CTAN publication	1	
v0.7		
General: Fixed UTF8 compatibility issues	1	
Added detokenized writing	14	
Added Finnish language support	19	
v0.8		
General: Fixed missing babel tag and running out of write handles	1	
moved newwrite of exercise stream to this spot to avoid consuming all handles	12	
v0.9		
General: . Changed default behavior w.r.t. minipage-wrapping of exercises	11	
Changed default behavior w.r.t. minipage-wrapping of exercises	1	
		v1.0
General: Corrected minipage dependence, made	1	
added user-accessible lengths	12	
v1.1		
General: First stable release	1	
Added congruence of chaptercounter of main document and chapter counter of exercises document	20	
Added detokenized writing of formula and formula collection stream	14	
v1.2		
General: Bugfix release	1	
Corrected congruence of chaptercounter of main document and chapter counter of exercises document (taking into account alphanumbered chapters)	20	
General: Implemented multicolumn option for exercises, introduced new options (local, nolabels), separate counter for exerciseseries (only for use local mode), introduced local mode	1	
Added exerciseseries environment	17	
Added option local	11	
Added option nolabels	11	
Added series counter	13	
Added Spanish language support	19	
Completed German language support (i.e. new spelling ngerman) support	19	
exercises: Added multicolumn feature	17	

Index

Numbers written in italic refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

Symbols		
\\"	320, 321, 327, 328, 339, 340	\@esphack \@ifmtarg \@ifundefined \@makechapterhead
\'	348	122, 179, 281, 302 200, 203 65, 70 354, 355
\@bsphack	105, 166, 268, 289	\@noligs \addto A 310, 317, 324, 331, 338, 345

<pre> \appendix 381–384 \arabic 58, 63, 65–69, 71, 73, 357 \AtBeginDocument .. 35 \AtEndDocument 47 </pre> <p>B</p> <pre> \backmatter 374–377 \baselineskip 227 \begin 102, 104, 133, 135, 162, 164, 185, 187, 223, 242, 243, 258 \begingroup 106, 167, 269, 290 \boolean 133, 134, 154, 156, 185, 186, 206, 208 </pre> <p>C</p> <pre> \captionsdutch 310 \captionsfinnish .. 338 \captionsfrench .. 331 \captionsgerman .. 317 \captionsngerman .. 324 \captionsspanish .. 345 \chapter 358 \closeout 48, 49, 52, 127, 282 \columncount .. 210, 216, 223, 226, 230, 237, 242, 247, 253, 258, 261 \copyexercisesinsolutions 11 \csname 14 </pre> <p>D</p> <pre> \DeclareBoolOption 7, 8, 10–12 \DeclareStringOption 9 \def 89, 90, 109, 121, 158, 159, 170, 178, 264, 265, 272, 280, 286, 287, 293, 301, 355, 362, 369, 376, 383 \define@key 210–213, 230–233 \DefineVerbatimEnvironment\exsolexerciseparsep . 130, 182, 285, 304 \detokenize 78, 80, 85, 86, 88 </pre> <p>E</p> <pre> \else . 64–69, 71, 95, 113, 147, 150, 163, 199, 202, 353 \end 123, 125, 155, 156, 180, 207, 208, 226, 247, 249, 261 \endcsname 14 \endgroup 122, 179, 281, 302 \exercise 89, 89 \exerciseaslist ... 10 \exercisename 148, 151, 305, 311, 318, 325, 332, 339, 346 \exercises 210 \exerciseseries ... 230 \exercisesfontsize 9, 14, 220 \exercisesname 222, 306, 312, 319, 326, 333, 340, 347 \exercisestream 40, 78, 92, 104, 123, 127 \exsol@appendix 382, 385 \exsol@backmatter 375, 378 \exsol@frontmatter 361, 364 \exsol@mainmatter 368, 371 \exsol@makechapterhead 354, 356 \exsol@exercise ... 131 \exsol@exercisesfontsize 14 \exsol@solution ... 183 \exsolexerciseminent 31, 32, 143, 195 \exsolexerciselabelsep 27, 28, 145, 197 \exsolexerciselabelwidth 29, 30, 146, 198 \exsolexerciseleftmargin 21, 22, 140, 192 \exsolexerciseparindent 25, 26, 142, 194 \exsolexerciserightmargin \GPES@write@detok 33, 34, 144, 196 \exsolexerciserightmargin \GPES@write@detok 23, 24, 141, 193 </pre> <p>F</p> <pre> \fif 65–68, 71, 74, 75, 98, 103, 115, 126, 148, 151, 165, 200, 203, 366, 373, 380, 387, 388 \formulacollectionstream . 42, 43, 48, 85, 88 \formulaistream 45, 86, 266, 282 \frontmatter 360–363, 367 \FV@DefineTabOut 110, 171, 273, 294 \FV@DefineWhiteSpace . 108, 169, 271, 292 \FV@Environment 89, 158, 264, 286 \FV@FontScanPrep 117, 174, 276, 297 \FV@ProcessLine 112, 114, 172, 274, 295 \FV@Scan 119, 176, 278, 299 \FV@Space 109, 170, 272, 293 \FV@UseKeyValues 107, 168, 270, 291 \FVB@exercise 90 \FVB@informulacollection 265 \FVB@informulacollectiononly 287 \FVB@solution 159 \FVE@exercise 121 \FVE@informulacollection 280 \FVE@informulacollectiononly 301 \FVE@solution 178 </pre> <p>G</p> <pre> \GPES@write@detok 77, 82, 114 </pre>	<pre> \exsolexercisesaboveskip 15, 16, 221 \exsolexercisesbelowskip 17, 18, 227 \exsolexercisetopbottomsep .. 19, 20, 139, 191 \exsubrule 211, 213, 217, 229, 231, 233, 238, 248, 254 </pre>
--	---

<pre>\GPESS@write@detok 81, 112 \GPFORCOL@write@detok 84, 274 \GPFORCOLONLY@write@detok \linewidth 220, 228 87, 295 \GPSS@write@detok 79, 83, 172</pre> <p>I</p> <pre>\if 65–69, 71 \ifdefined 360, 367, 374, 381 \ifexsol@copyexercisesinsolutions 99, 111, 124, 161 \ifexsol@local 62, 93, 352 \ifexsol@nolabels 147, 150, 199, 202 \ifthenelse 133, 134, 154, 156, 185, 186, 206, 208, 223, 226, 242, 247, 258, 261 \immediate 38, 43, 48, 49, 52, 54, 78, 80, 85, 86, 88, 92, 94, 96, 102, 104, 123, 125, 127, 162, 164, 180, 243, 249, 266, 282, 357, 363, 370, 377, 384, 391 \informulacollection 264, 264 \informulacollectiononly 286, 286 \input 53, 128, 283 \item 147, 199 \itemindent 143, 195</pre> <p>J</p> <pre>\jobname 36, 38, 39, 41, 43, 44, 53, 54, 92, 101, 128, 160, 266, 267, 283, 288</pre> <p>L</p> <pre>\labelsep 145, 197 \labelwidth 146, 198 \leftmargin 140, 192 \let 112, 114, 117, 118, 172,</pre> <p>M</p> <pre>\mainmatter 368–370 \minipage 12 \newcounter 56, 59 \newlength 15, 17, 19, 21, 23, 25, 27, 29, 31, 33 \newline 97 \newwrite 37, 40, 42, 45 \noexercisesinchapter 389 \nolabels 8</pre> <p>N</p> <p>O</p> <pre>\openout 38, 43, 54, 92, 266</pre> <p>P</p> <pre>\par 156, 208, 220, 222, 229, 241, 248, 257, 262 \paragraph 222, 241, 257 \parsep 144, 196 \parskip 34 \ProcessKeyvalOptions 13</pre> <p>Q</p> <pre>\quad 97</pre> <p>R</p> <pre>\refstepcounter 91, 236 \relax 116–118, 173–175, 226, 247, 275–277, 296–298 \renewcommand 58, 61, 210–213, 230–233, 311–315, 318–322, 325–329, 332–336, 339–343, 346–350 \RequirePackage 2–6</pre> <p>S</p> <pre>\seriesname 241, 257, 309, 315, 322, 329, 336, 343, 350 \setcounter 57, 60, 357 \setkeys 219, 240, 256 \setlength 16, 18, 20, 22, 24, 26, 28, 30, 32, 34, 139–146, 191–198 \solsubrule 212, 213, 218, 232, 233, 239, 255, 262 \solution 158, 158 \solutionname 200, 203, 307, 313, 320, 327, 334, 341, 348 \solutionsname 308, 314, 321, 328, 335, 342, 349 \solutionstream 37, 38, 49, 52, 54, 80, 94, 96, 102, 125, 162, 164, 180, 243, 249, 357, 363, 370, 377, 384, 391 \space 109, 170, 272, 293 \string 96, 97, 102, 104, 123, 125, 162, 164, 180, 243, 244, 249, 357, 358, 363, 370, 377, 384 \subparagraph 148, 151, 200, 203</pre> <p>T</p> <pre>\textwidth 133, 185 \theexercise 61, 102, 104, 164 \theexerciseseries 58, 241, 244</pre> <p>V</p> <pre>\vspace 96, 221, 227</pre> <p>W</p> <pre>\write 78, 80, 85, 86, 88,</pre>	<p>S</p> <p>M</p> <p>N</p> <p>O</p> <p>P</p> <p>Q</p> <p>R</p> <p>T</p> <p>V</p> <p>W</p>
---	---

94, 96, 102, 104,
123, 125, 162,
164, 180, 243,
249, 357, 363,
370, 377, 384, 391