

# The **fgruler** package

v1.2 (2020/10/26)

Tibor Tómács  
tomacs.tibor@uni-eszterhazy.hu

## 1 Introduction

The **fgruler** is an abbreviation for the *foreground ruler*. This package draws a horizontal and a vertical ruler on the foreground of every (or a given) page at absolute position. In this way, you can check the page layout dimensions.

Besides, you can draw various rulers in the text, too.

The **fgruler** package requires the services of the following packages: `kvoptions`, `etoolbox`, `xcolor`, `graphicx`, `eso-pic`.

## 2 Loading package

Load the package with

```
\usepackage[<options>]{fgruler}
```

or

```
\usepackage{fgruler}
\setfgruler{<options>}
```

The `\setfgruler` command is usable in the `document` environment, too.

## 3 Options

By default, the **fgruler** package draws a square ruler on the foreground of every page. The following package options set the parameters of these rulers.

`unit=<unit>`

Ruler unit.

`<unit>` values:

`cm` Metric ruler (centimeter). Default value.

`in` English ruler (inch).

`type=<type name>`

Origin and directions.

`<type name>` values:

`upperleft` Origin: upper left corner. Directions: down and right. Default value.

`upperright` Origin: upper right corner. Directions: down and left.

`lowerleft` Origin: lower left corner. Directions: up and right.

`lowerright` Origin: lower right corner. Directions: up and left.

`none` Not drawing ruler.

**user**      Each  $\langle unit \rangle - \langle type\ name \rangle$  pair activates an  $\text{\fgruler@}\langle unit \rangle @\langle type\ name \rangle @\text{fg}$  command. You can control the effect of this option by redefining the  $\text{\fgruler@}\langle unit \rangle @\text{user}@fg$  commands, which are empty in the default case. (See 7.7, 7.8 and 7.9 examples.)

#### **hshift=** $\langle length \rangle$

Horizontal shift. The shift direction is right, if the  $\langle type\ name \rangle$  is `upperleft` or `lowerleft`, otherwise it is left.

Default: `hshift=0cm`.

The  $\langle length \rangle$  is saved in `\fgruler@hshift`.

#### **vshift=** $\langle length \rangle$

Vertical shift. The shift direction is down, if the  $\langle type\ name \rangle$  is `upperleft` or `uppright`, otherwise it is up.

Default: `vshift=0cm`.

The  $\langle length \rangle$  is saved in `\fgruler@vshift`.

#### **color=** $\langle color\ name \rangle$

Ruler color (see `xcolor` package).

Default: `color=black`.

The  $\langle color\ name \rangle$  is saved in `\fgruler@color`.

#### **numsep=** $\langle length \rangle$

Separation between number and ruler.

Default: `numsep=3pt`.

The  $\langle length \rangle$  is saved in `\fgruler@numsep`.

#### **markthick=** $\langle length \rangle$

Mark thickness.

Default: `markthick=0.4pt`.

The  $\langle length \rangle$  is saved in `\fgruler@markthick`.

#### **marklength=** $\langle length \rangle$

Mark length at integer units: 0 1 2 3

Default: `marklength=2mm`.

The  $\langle length \rangle$  is saved in `\fgruler@marklength`.

See the length of the other marks in Section 6.

#### **numfont=** $\langle font\ type \rangle$

Number font type.

You can use this option only in `\setfgruler` command.

Default: `numfont=\scriptsize\sffamily`.

The  $\langle font\ type \rangle$  is saved in `\fgruler@numfont`.

#### **showframe** or **showframe=true**

It draws visible frames for the text and margin area, and lines for the head and foot. Their color and thickness are determined by the `color` and the `markthick` options.

#### **showframe=false**

It deactivates the `showframe` option.

#### **nonefgrulers**

It kills all of the rulers on the foreground, including also those, which are generated by `\fgruler` (see Section 4). But the rulers, which were drawn by `\ruler` and `\squareruler` (see Section 5), do not disappear. Furthermore it deactivates the `showframe` option, too. In this case the `fgruler` package does not load the `eso-pic` package. This option works only in preamble.

It is recommended to use in two cases:

- To draw rulers only in text, there is no need for the checking function.
- To halt the checking function temporarily.

The `type=none` is not identical with `nonefgrulers` option. The differences:

- `type=none` does not kill the `\fgruler` command and the `showframe` option.
- `type=none` is alterable in any point of the document.
- `type=none` works in document environment, too.
- The `fgruler` package loads the `eso-pic` package, if you use the `type=none` option without `nonefgrulers`.

## 4 Drawing square rulers on the foreground of a given page

`\fgruler[<unit>]{<type name>}{<hshift>}{<vshift>}`

It draws a square ruler on the foreground of that page, where this command is expanded. You can use more `\fgruler` commands in the same page.

The package options (see Section 3) also work on this command, except for `unit`, `type`, `hshift` and `vshift`, since these are the parameters of the `\fgruler`.

If you use `nonefgrulers` option in preamble, then this command is effectless.

`<unit>` options:

`cm` Metric ruler (centimeter). Default option.

`in` English ruler (inch).

`<type name>` parameters:

`upperleft` Origin: upper left corner. Directions: down and right.

`upperright` Origin: upper right corner. Directions: down and left.

`lowerleft` Origin: lower left corner. Directions: up and right.

`lowerright` Origin: lower right corner. Directions: up and left.

`<hshift>` Horizontal shift. The shift direction is right, if the `<type name>` is `upperleft` or `lowerleft`, otherwise it is left.

`<vshift>` Vertical shift. The shift direction is down, if the `<type name>` is `upperleft` or `upperright`, otherwise it is up.

Example: `\fgruler[in]{upperright}{1in}{2.5in}`

## 5 Drawing rulers in the text

`\ruler[<unit>]{<type name>}{<length>}`

It draws a horizontal or a vertical ruler. The bottom of the ruler is aligned to the baseline of the surrounding text. The package options (see Section 3) do not work on this command.

`<unit>` options:

`cm` Metric ruler (centimeter). Default option.

`in` English ruler (inch).

`<type name>` parameters:

`downright` Direction: down. The numbers are on the right side.

`downleft` Direction: down. The numbers are on the left side.

`upright` Direction: up. The numbers are on the right side.

`upleft` Direction: up. The numbers are on the left side.

`rightdown` Direction: right. The numbers are on the down side.

`rightup` Direction: right. The numbers are on the up side.

`leftdown` Direction: left. The numbers are on the down side.

`leftup` Direction: left. The numbers are on the up side.

`<length>` Ruler length.

Example: `\ruler[rightdown]{5cm}`

`\ruler*[<unit>]{<type name>}{<length>}`

It works like `\ruler`, but the top of the ruler is aligned to the baseline of the surrounding text.

Example: `\ruler*[rightdown]{5cm}`

`\squareruler[unit]{type name}{width}{height}`

It draws a square ruler. The bottom of the square ruler is aligned to the baseline of the surrounding text. The package options (see Section 3) do not work on this command.

*{unit}* options:

`cm` Metric ruler (centimeter). Default option.

`in` English ruler (inch).

*{type name}* parameters:

`upperleft` Directions: down and right.

`upperright` Directions: down and left.

`lowerleft` Directions: up and right.

`lowerright` Directions: up and left.

*{width}* Square ruler width.

*{height}* Square ruler height.



Example: `\squareruler{upperleft}{5cm}{1cm}`

`\squareruler*[unit]{type name}{width}{height}`

It works like `\squareruler`, but the top of the square ruler is aligned to the baseline of the surrounding text.

Example: `\squareruler*{upperleft}{5cm}{1cm}`



`\rulerparams{markthick}{numfont}{color}{marklength}{numsep}`

It sets the parameters of the rulers, which are drawn by `\ruler` or `\squareruler`. If an argument is empty, then that parameter will not be changed.

*{markthick}* Mark thickness. Default: `0.4pt`

*{numfont}* Number font type. Default: `\scriptsize\sffamily`

*{color}* Ruler line color. Default: `black`

*{marklength}* Mark length at integer units. Default: `2mm`

*{numsep}* Separation between number and ruler. Default: `3pt`

For example, `\rulerparams{}{}{red}{}{}` changes the ruler color to red.

`\rulernorotatenum`

By default, the numbers of the vertical rulers (which were generated by `\ruler` or `\squareruler`) are rotated by  $90^\circ$ . It kills this action. This command is usable only in `document` environment.



Example: `\ruler{upright}{1cm}`



but `\rulernorotatenum\ruler{upright}{1cm}`

`\rulerrotatenum`

After `\rulernorotatenum`, it reactivates the number rotating. This command is usable only in `document` environment.

## 6 Additional setting commands

The following commands can work on all of the rulers, which are drawn by `fgruler` package.

`\fgrulerstartnum{num}`

The *{num}* is a nonnegative integer, which will be the starting number on the ruler. Default:

`\fgrulerstartnum{0}`

Example: `\fgrulerstartnum{5}\ruler{rightup}{3cm}`



### \fgrulernoborderline

By default, there is a borderline on one side of the ruler. It disappears by this command.

Example: \ruler{rightup}{3cm}  but {\fgrulernoborderline\ruler{rightup}{3cm}} 

### \fgrulerborderline

After \fgrulernoborderline, it reactivates the previous default effect.

### \fgrulercaptioncm{(caption)}

Unit caption in metric ruler. Default: \fgrulercaptioncm{cm}

Example: \ruler{rightup}{3cm}  but {\fgrulercaptioncm{} \ruler{rightup}{3cm}} 

### \fgrulercaptionin{(caption)}

Unit caption in English ruler. Default: \fgrulercaptionin{inch}

### \fgrulerdefnum{(definition)}

The ruler numbers are determined by the `fgrulernum` counter. Its current value is printed by the `\the\fgroulernum`. Its default definition is `\def\the\fgroulernum{\arabic{fgrulernum}}`, which is equivalent to `\fgrulerdefnum{\arabic{fgrulernum}}`.

Example:

{\fgrulerdefnum{} \fgrulercaptioncm{} \ruler{rightdown}{2cm}} 

### \fgrulerratiocm{(ratio1)}{(ratio2)}

Mark length ratios in metric rulers. If an argument is empty, then that parameter will not be changed.

*(ratio1)* Mark length ratio at  $k/10$  cm, where  $k$  is positive integer and not divisible by 5.



For example, if this ratio is 0.5 and the mark length at integer unit is 2 mm, then this mark length will be  $0.5 \cdot 2$  mm = 1 mm.

*(ratio2)* Mark length ratio at  $k/2$  cm, where  $k$  is positive odd integer.



Default: \fgrulerratiocm{0.5}{0.75}


### \fgrulerratioin{(ratio1)}{(ratio2)}{(ratio3)}{(ratio4)}

Mark length ratios in English rulers. If an argument is empty, then that parameter will not be changed.


*(ratio1)* Mark length ratio at  $k/16$  inch, where  $k$  is positive odd integer.




*(ratio2)* Mark length ratio at  $k/8$  inch, where  $k$  is positive odd integer.



*(ratio3)* Mark length ratio at  $k/4$  inch, where  $k$  is positive odd integer.



*(ratio4)* Mark length ratio at  $k/2$  inch, where  $k$  is positive odd integer.



Default: \fgrulerratioin{0.25}{0.375}{0.625}{0.75}

### \fgrulerthickcm{(thick1)}{(thick2)}{(thick3)}

Mark thicknesses in metric rulers. If an argument is empty, then that parameter will not be changed.

*(thick1)* Mark thickness at  $k/10$  cm, where  $k$  is positive integer and not divisible by 5.

*(thick2)* Mark thickness at  $k/2$  cm, where  $k$  is positive odd integer.

*(thick3)* Mark thickness at integer units.

The default values are given by `\markthick` of `\rulerparams`, respectively by `markthick` option.

Example:

```
{\fgrulerthickcm{}{}{2pt}
 \rulerparams{}{}{}{5mm}{}
 \fgrulernoborderline
 \ruler[rightdown]{3cm}}
```



### `\fgrulerthickin{<thick1>}{<thick2>}...{<thick5>}`

Mark thicknesses in English rulers. If an argument is empty, then that parameter will not be changed.

`<thick1>` Mark thickness at  $k/16$  inch, where  $k$  is positive odd integer.

`<thick2>` Mark thickness at  $k/8$  inch, where  $k$  is positive odd integer.

`<thick3>` Mark thickness at  $k/4$  inch, where  $k$  is positive odd integer.

`<thick4>` Mark thickness at  $k/2$  inch, where  $k$  is positive odd integer.

`<thick5>` Mark thickness at integer units.

The default values are given by `\markthick` of `\rulerparams`, respectively by `markthick` option.

Example:

```
{\fgrulerthickin{}{}{}{}{2pt}
 \rulerparams{}{}{}{5mm}{}
 \fgrulernoborderline
 \ruler[in]{rightdown}{3in}}
```



### `\fgrulercolorcm{<color1>}{<color2>}...{<color3>}`

Mark colors in metric rulers. If an argument is empty, then that parameter will not be changed.

`<color1>` Mark color at  $k/10$  cm, where  $k$  is positive integer and not divisible by 5.


`<color2>` Mark color at  $k/2$  cm, where  $k$  is positive odd integer.

`<color3>` Mark color at integer units.

The default values are given by `\color` of `\rulerparams`, respectively by `color` option.

Example:

```
{\fgrulercolorcm{green}{blue}{red}
 \rulerparams{1pt}{}{}{5mm}{}
 \fgrulernoborderline
 \ruler[rightdown]{3cm}}
```



### `\fgrulercolorin{<color1>}{<color2>}...{<color5>}`

Mark color in English rulers. If an argument is empty, then that parameter will not be changed.

`<color1>` Mark color at  $k/16$  inch, where  $k$  is positive odd integer.

`<color2>` Mark color at  $k/8$  inch, where  $k$  is positive odd integer.

`<color3>` Mark color at  $k/4$  inch, where  $k$  is positive odd integer.

`<color4>` Mark color at  $k/2$  inch, where  $k$  is positive odd integer.

`<color5>` Mark color at integer units.

The default values are given by `\color` of `\rulerparams`, respectively by `color` option.

Example:

```
{\fgruler{colorin{yellow}{orange}{green}{blue}{red}}
\rulerparams{1pt}{}{}{5mm}{}
\fgruler[noborderline]
\ruler[in]{rightdown}{3in}}
```



### \fgrulerreset

It sets all options and parameters to default values. This command is usable only in `document` environment.

**A** All setting commands<sup>1</sup> obey the normal scoping rules, i.e. if you use them inside a group, then the changing of the parameters is not valid outside the group.

---


<sup>1</sup>Namely `\setfgruler`, `\rulerparams`, `\rulernorotate`, `\rulerrotate`, furthermore all commands in this section.

## 7 Examples

### 7.1 Default case

The output of the following code is the ruler in this page. It is the default case.

```
5 \documentclass{article}
6 \usepackage{fgruler}
7 \begin{document}
8 ...
9 \end{document}
```



### 7.3 Shifting in default case

```
1 \documentclass{article}
2 \usepackage[hshift=1cm,vshift=2cm]{fgruler}
3 \begin{document}
4 ...
5 \end{document}
```



25   **7.5 Shifting in case ‘type=lowerleft’ option**

```
24 \documentclass{article}
25 \usepackage[type=lowerleft,hshift=1cm,vshift=2cm]{fgruler}
26 \begin{document}
27 ...
28 \end{document}
```

21

20

19

18

17

16

15

14

13

12

11

10

9

8

7

6

5

4

3

2

1

cm 1    2    3    4    5    6    7    8    9    10    11    12    13    14    15    16    17    18    19    20

27  
26  
25  
24  
23  
22  
21  
20  
19  
18  
17  
16  
15  
14  
13  
12  
11  
10  
9  
8  
7  
6  
5  
4  
3  
2  
1

## 7.6 Shifting in case ‘type=lowerright’ option

```
\documentclass{article}
\usepackage[type=lowerright,hshift=1cm,vshift=2cm]{fgruler}
\begin{document}
...
\end{document}
```

0 19 18 17 16 15 14 13 12 11 10 9 8 7 6 5 4 3 2 1 cm

## 7.7 An example for the ‘type=user’ option

```
\documentclass{article}
\usepackage[type=user]{fgruler}
\makeatletter
\def\fgruler@cm@user@fg{%
    \ifodd\value{page}\fgruler@cm@upperright@fg%
        \else\fgruler@cm@upperleft@fg\fi}
\def\fgruler@in@user@fg{%
    \ifodd\value{page}\fgruler@in@upperright@fg%
        \else\fgruler@in@upperleft@fg\fi}
\makeatother
\begin{document}
...
\end{document}
```

In this case the `type=upperright` option will be activated, if the page number is odd. Otherwise `type=upperleft` will be activated.



## 7.8 An other example for the ‘type=user’ option

```


1 \documentclass{article}
2 \usepackage[type=user,color=red]{fgruler}
3 \makeatletter
4 \newlength{\fgruler@tempdim}
5 \newcommand{\fgruler@user}[1]{%
6   \AtTextLowerLeft% See eso-pic package!
7     \rulerparams{\fgruler@markthick}{\fgruler@numfont}{\fgruler@color}%
8       {\fgruler@marklength}{\fgruler@numsep}%
9     \settowidth{\fgruler@tempdim}{\ruler[#1]{downleft}{\textheight}}%
10    \put(-\fgruler@tempdim,0){%
11      \rulernorotateenum%
12      \fgrulercaptioncm{}%
13      \fgrulercaptionin{}%
14      \ruler[#1]{downleft}{\textheight}%
15    }%
16    \put(0,\textheight){%
17      \ruler[#1]{rightup}{\textwidth}%
18    }%
19  }%
20 }
21 \renewcommand{\fgruler@cm@user@fg}{\fgruler@user{cm}}
22 \renewcommand{\fgruler@in@user@fg}{\fgruler@user{in}}
23 \makeatother
24 \begin{document}
...
\end{document}

```

This code places rulers at the left and the top border of the body. In this case the `hshift` and `vshift` options don't work.


14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24





*Remark.* The \rotatebox command is defined in the **graphicx** package.

## 7.11 Ruler types in text




```
\documentclass{article}
\usepackage[nonefgrulers]{fgruler}
\begin{document}
\noindent
\rulerparams{}{}{red}{}{1pt}
\ruler{rightdown}{3cm}
\hfill
\ruler{rightup}{3cm}
\hfill
\ruler{leftup}{3cm}
\hfill
\ruler{leftdown}{3cm}

\bigskip\noindent
\rulerparams{}{}{green}{}{}
{\rulernorotatenum\ruler{upright}{3cm}}
\hfill
\ruler{downright}{3cm}
\hfill
\ruler{upleft}{3cm}
\hfill
\ruler{downleft}{3cm}


\bigskip\noindent
\rulerparams{}{}{blue!50!black}{}{}
{\rulernorotatenum\fgrulercaptioncm{}\sqruler{upperleft}{2cm}{3cm}}
\hfill
\sqruler{lowerright}{2cm}{3cm}
\hfill
\sqruler{lowerleft}{2cm}{3cm}
\hfill
\sqruler{upperright}{2cm}{3cm}
\hfill
{\rulerparams{}{\footnotesize\bfseries\color{red}}{}{5mm}{-8pt}
\sqruler[in]{lowerleft}{2in}{3cm}}
\end{document}
```

## 7.12 Mark length and rotating




```
\documentclass{article}
\usepackage[nonefgrulers]{fgruler}
\begin{document}
\noindent
\fgrulerdefnum{\rotatebox{45}{\arabic{fgrulernum}\,cm}}
\fgrulercaptioncm{}
\rulerparams{}{\tiny\color{red}}{\blue}{8mm}{}%
\fgrulercolorcm{}{}{black}
\rotatebox{-45}{\ruler{rightup}{10cm}}\\
\ruler{rightup}{5cm}
\end{document}
```

### 7.13 Coordinate system




```
\documentclass{article}
\usepackage[nonefgrulers]{fgruler}
\begin{document}
    \noindent
    \rulernorotatenum
    \fgrulercaptioncm{}
    \fgrulercolorcm{}{}{red}
    \rulerparams{}{\scriptsize\color{red}}{}{}{%
        {\fgrulerdefnum{$-\arabic{fgrulernum}$}\sqruler*{uppright}{3cm}{3cm}}%
        \sqruler{lowerleft}{13cm}{6cm}}
\end{document}
```

## 7.14 Tape measure



```
\documentclass{article}
\usepackage[a4paper,margin=25mm]{geometry}
\usepackage[nonefgrulers]{fgruler}
\newcommand{\tapemeasure}[1]{%
\parbox{#1}{%
\fgruleredefnum{}\fgrulercaptioncm{}\ruler{rightdown}{#1}\\"[2pt]
\ruler{rightup}{#1}}}
\begin{document}
\noindent
\tapemeasure{\textwidth}\\"[2pt]
\rotatebox[origin=br]{-90}{\tapemeasure{3cm}}
\tapemeasure{10cm}
\end{document}
```

### 7.15 A new square ruler



```
\documentclass{article}
\usepackage[type=none]{fgruler}
\makeatletter
\newcommand{\usersquareruler}[2]{%
    \begin{picture} (#1+1em+\fgruler@marklength,#2+1em+\fgruler@marklength)%
        {\fgrulercaption{}% 
         \ruler{downleft}{#2}}%
        \put(0,#2){\ruler{rightup}{#1}}%
    \end{picture}}
\makeatother
\begin{document}
\usersquareruler{3cm}{5cm}
\end{document}
```