

Documented Source Code for flowfram.sty v1.10

Nicola L. C. Talbot

20th Aug 2007

This is the documented source code for the flowfram package. For a user manual, see [ffuserguide.pdf](#).

Contents

Glossary	1
1 The Code	2
1.1 Package Initialisation	2
1.2 Flow Frames	6
1.3 Static Frames	17
1.4 Dynamic Frames	25
1.5 Determining Dimensions and Locations	33
1.6 Initialise Flow Frames	37
1.7 Output Routine	39
1.8 Static versions of floats	58
1.9 Standard Layouts	59
1.9.1 Column Styles	59
1.9.2 Backdrop Effects	69
1.9.3 Lines Between Frames	75
1.10 Putting Chapter Headings in Dynamic Frames	80
1.11 Thumbtabs	80
1.12 Minitocs	88
Index	94

Glossary

bounding box

The smallest possible rectangle that completely encompasses the object.

dynamic frame

Frames in which text is fixed in place, but the contents are re-typeset after each page.

flow frame

The frames in a document such that the contents of the **document** environment flow from one frame to the next in the order that they were defined. There must be at least one flow frame on every page.

frame

A rectangular area of the page in which text can be placed (not to be confused with a frame making command). There are three types: flow, static and dynamic.

frame making command

A \LaTeX command which places some kind of border around its argument. For example: `\fbox`.

identification label (IDL)

A unique label which can be assigned to a frame, enabling you to refer to the frame by label instead of by its IDN.

identification number (IDN)

A unique number assigned to each frame, which you can use to identify the frame when modifying its appearance. Example: if you have defined 3 flow frames, 2 static frames and 1 dynamic frame, the flow frames will have IDNs 1, 2 and 3, the static frames will have IDNs 1 and 2, and the dynamic frame will have IDN 1.

page list

A list of pages. This can either be a single keyword: `all`, `odd`, `even` or `none`, or it can be a comma-separated list of individual page numbers or page ranges. For example: `<3,5,7-11,>15` indicates pages 1,2,5,7,8,9,10,11 and all pages after page 15. Note that these numbers refer to the actual value of the page counter, not the absolute physical page number.

page range

Page ranges can be closed, e.g. 5-10, or open, e.g. `<7` or `>9`.

static frame

Frames in which text is fixed in place. The contents are fixed until explicitly changed.

typeblock

The area of the page where the main body of the text goes. The width and height of this area are given by `\textwidth` and `\textheight`.

1 The Code

1.1 Package Initialisation

Declare package, and identify it as a $\text{\LaTeX} 2_{\epsilon}$ package.

```
\NeedsTeXFormat{LaTeX2e}
\ProvidesPackage{flowfram}[2007/08/21 v1.10]
```

Load packages needed by this package

```
\RequirePackage{ifthen}
\RequirePackage{keyval}
\RequirePackage{graphics}
\RequirePackage{afterpage}
\ifundefined{@ldc@l@r}{\RequirePackage{color}}{}
```

The colour of the **bounding box** borders when the draft option is specified is given by the commands:

```
\newcommand{\setffdraftcolor}{\color[gray]{0.8}}
\newcommand{\setffdrafttypeblockcolor}{\color[gray]{0.9}}
```

`\fflabelsep` In draft mode, each **bounding box** (apart from the one indicating the **typeblock**), has a label positioned to the right of the box, at a distance of `\fflabelsep` from the right hand border.

```
\newlength\fflabelsep
\fflabelsep=1pt
```

`\fflabelfont` The appearance of the label is set by the declaration:

```
\newcommand*{\fflabelfont}{\small\sffamily}
```

The command `\@ffdraft` is used to switch to draft mode. Allow user the option to show particular types of bounding boxes.

```
\newif\ifshowtypeblock
\newif\ifshowmargins
\newif\ifshowframebbox
```

`\@ffdraft` Set all draft settings.

```
\newcommand*{\@ffdraft}{%
\showtypeblocktrue
\showmarginstrue
\showframebboxtrue
}
```

`\@ffnodraft` Unset all draft settings.

```
\newcommand*{\@ffnodraft}{%
\showtypeblockfalse
\showmarginsfalse
\showframebboxfalse
}
```

`\@fr@meifdraft` Draw **bounding box**.

```
\newcommand*{\@fr@meifdraft}[3][\setffdraftcolor]{%
\def\ff@backcol{\none}}%
\@ifundefined{color}{\frame{#2}}{#1\frame{#2}}%
\ifthenelse{\equal{#3}{}}{}{%
\makebox[0pt][l]{\hskip\fflabelsep\fflabelfont{[#3]}}}%
}
```

Colour setting commands, do nothing by default:

```
\newcommand*{\s@tffcol}{}
\newcommand*{\s@tffttextcol}{}

```

`\@ffbackground` Deal with **frame** background colour. Note that the background colour only extends to the limit of the **frame's bounding box**. If you want the background colour to be flush with the **frames** border, you will have to create your own customised border.

```
\newcommand*{\@ffbackground}[1]{#1}
```

Now declare the options. If draft, switch to draft definitions.

```
\DeclareOption{draft}{\@ffdraft}
```

If not draft, reset commands so that no **bounding boxes** are drawn.

```
\DeclareOption{final}{\@ffnodraft}
```

`\if@ttb@rotate` Allow provision to prevent rotation in the thumbtabs. If no rotation, thumbtab text will be stacked vertically. This will also affect whether or not to rotate **frames**.

```
\newif\if@ttb@rotate
\@ttb@rotate>true
\DeclareOption{rotate}{\@ttb@rotate>true}
\DeclareOption{norotate}{\@ttb@rotate>false}
```

`\rotateframe` Define command that will only rotate box if rotate option set.

```
\newcommand{\rotateframe}[2]{\if@ttb@rotate
\rotatebox{#1}{#2}%
\else
#2\relax
\fi}
```

Should the thumbtabs include number, title, both or neither?

```
\newif\if@ttb@num
\newif\if@ttb@title
\@ttb@num=false
\@ttb@title=true
\DeclareOption{ttbtitle}{\@ttb@title=true}
\DeclareOption{ttbnotitle}{\@ttb@title=false}
\DeclareOption{ttbnum}{\@ttb@num=true}
\DeclareOption{ttbnonum}{\@ttb@num=false}
```

If color option specified, set up the default colours for the borders and text for all **frame** types. Note that the colour name has to be grouped within the definition of `\flowframecol` and `\flowframetextcol`. This was done so that you could do, for example, `\renewcommand{\flowframecol}{[rgb]{1,1,0}}` so that you can specify the colour model as well. The commands `\@s@tffcol` and `\@s@tffttextcol` switch to the border and text colour, respectively. They both assume that `\ff@col` has been set to the relevant colour before use.

```
\DeclareOption{color}{%
\def\flowframecol{{black}}\def\flowframetextcol{{black}}
\renewcommand*\@s@tffcol{\ifthenelse{equal{\ff@col}{}}{}{%
\expandafter\color\ff@col}}
\renewcommand*\@s@tffttextcol{\ifthenelse{equal{\ff@txtcol}{}}{}{%
\expandafter\color\ff@txtcol}}
\renewcommand*\@ffbackground[1]{%
\ifthenelse{equal{\ff@backcol}{none}}{}{%
#1}{\fboxsep=0pt\expandafter\colorbox\ff@backcol{#1}}}%
}
```

If `nocolor` is specified, ensure that the colour changing commands do nothing.

```
\DeclareOption{nocolor}{%
\def\flowframetextcol{}%
\def\flowframecol{}%
\renewcommand{\@s@tffcol}{}\renewcommand{\@s@tffttextcol}{}
\renewcommand{\@ffbackground}[1]{#1}
}
```

Check to see if the document class has the draft option set. The easiest way to do this is to check the length of `\overfullrule` (the marker that indicates overfull hboxes).

```
\ifdim\overfullrule=0pt
\ExecuteOptions{final}
\else
\ExecuteOptions{draft}
\fi
```

If the `\normalcolor` command is something other than `\relax`, then implement the color option as the default, otherwise implement the `nocolor` option as the default.

```
\ifx\normalcolor\relax
\ExecuteOptions{nocolor}
\else
\ExecuteOptions{color}
\fi
```

Now the defaults have all been set, the package options specified by the user can be processed:

```
\ProcessOptions
```

If color option has been specified, but no color package has been loaded yet, load `color.sty`

```
\ifx\normalcolor\relax
\ifthenelse{\equal{\flowframetextcol}{}}{}{%
\RequirePackage{color}}
\fi
```

User may want a non standard style for the first page of each chapter, so modify chapter commands to take this into account.

`\chapterfirstpagestyle`

```
\@ifundefined{chapter}{}{%
\newcommand*\chapterfirstpagestyle{plain}
\let\@ff@OLD@chapter\@chapter
\let\@ff@OLD@schapter\@schapter
\renewcommand{\@chapter}{%
\thispagestyle{\chapterfirstpagestyle}\@ff@OLD@chapter}
\renewcommand{\@schapter}{%
\thispagestyle{\chapterfirstpagestyle}\@ff@OLD@schapter}
}
```

Now get on with the package. First we need to set up a count register to store the number of **flow frames**, and one to store the id number of the current **flow frame**:

```
\newcounter{maxflow}
\newcounter{thisframe}
\c@maxflow=0\relax
\c@thisframe=0\relax
```

Define a counter to store the total number of **static frames**:

```
\newcounter{maxstatic}
\c@maxstatic=0\relax
```

Define a counter to store the total number of **dynamic frames**:

```
\newcounter{maxdynamic}
\c@maxdynamic=0\relax
```

Define some temporary variables

```
\newcount\@colN
\newcount\@ff@tmpN
\newcount\ff@id
\newlength\@ff@offset
\newlength\@ff@tmp@x
\newlength\@ff@tmp@x@even
\newlength\@ff@tmp@y
```

`\sdfparindent` Define a length to govern paragraph indentation within static and dynamic frames. This is 0pt by default.

```
\newlength\sdfparindent
```

1.2 Flow Frames

`\flowframesep` Set up default lengths. The gap between the text and the border is given by:

```
\newlength\flowframesep
\flowframesep=\fboxsep
```

`\flowframerule` The width of the frame is given by:

```
\newlength\flowframerule
\flowframerule=\fboxrule
```

`\flowframeshowlayout` Define command to show page layout. This finishes the current page, temporarily sets draft mode, and prints an empty page. Only the **frames** for that page will be shown.

```
\newcommand*\flowframeshowlayout}{%
\finishthispage
{\@ffdraft\mbox{}}\finishthispage\clearpage}}
```

`\framebreak` If the **flow frames** are not all of the same width, the change in `\hsize` will not come into effect until the end of the paragraph. Provide a command to simulate a paragraph break, without making it look as though there is a paragraph. Provides an optional argument that is passed to `\pagebreak`. Make sure it is grouped to localise the change in `\parfillskip` and `\parskip`.

```
\newif\ifusedframebreak
\newcommand{\framebreak}[1][4]{%
\usedframebreaktrue
{\parfillskip=0pt\pagebreak[#1]\parskip=0pt\par\noindent}}
```

`\finishthispage` The commands `\newpage` and `\pagebreak` can be used to move on to the next **flow frame**, but to finish the entire page, use `\finishthispage`.

```
\newcommand{\finishthispage}{%
\@colN=\c@thisframe
\newpage
\whiledo{\@colN<\c@maxflow}{\advance\@colN by 1\relax
\@ff@chckifthispg{\c@page}{\@colN}%
\if@notthiscol\else
\mbox{}\newpage%
\fi
}}
```

`\cleardoublepage` Modify the definition of `\cleardoublepage`. This may or may not be defined so use `\def`.

```

\def\cleardoublepage{\finishthispage
\if@twoside
\ifodd\c@page
\else
\hbox{}\finishthispage
\fi
\fi}

```

Disable `@twocolumn` flag, as it makes no sense.

```

\@twocolumnfalse

```

Disable `@mparswitch` flag, as each **flow frame** has its own predefined margin setting.

```

\@mparswitchfalse

```

`\globalreversemargin` The margins get switched during the output routine, so need the effect to be global.

```

\newcommand{\globalreversemargin}{%
\global\@mparbottom\z@\global\@reversemargintrue}
\newcommand{\globalnormalmargin}{%
\global\@mparbottom\z@\global\@reversemarginfalse}

```

`\@getmarginpos` Determine whether the margin should be on the right or left. This depends on the setting, which can either be **right** or **left** (self explanatory) or **inner** (on the spine side, so left for odd pages and right for even pages) or **outer** (on the outside of the page, so right for odd pages and left for even pages.) When `\@getmarginpos` is finished, the setting is stored in `\ff@margin`.

```

\newcommand{\@getmarginpos}[1]{%
\ifthenelse{\equal{#1}{inner}}{%
\if@twoside
\ifodd\c@page\def\ff@margin{left}\else\def\ff@margin{right}\fi
\else
\def\ff@margin{left}%
\fi
}{%
\ifthenelse{\equal{#1}{outer}}{%
\if@twoside
\ifodd\c@page\def\ff@margin{right}\else\def\ff@margin{left}\fi
\else
\def\ff@margin{right}%
\fi
}{%
\def\ff@margin{#1}}}%
}

```

`\setmargin` Set the margin for current **flow frame**.

```

\newcommand{\setmargin}{%
\@getmarginpos{%
\csname @ff@margin@\romannumeral\c@thisframe\endcsname}%
\ifthenelse{\equal{\ff@margin}{left}}{%
{\globalreversemargin}{\globalnormalmargin}%
}
}

```

`\newflowframe` Create a new **flow frame**. Syntax:
`\newflowframe[⟨pages⟩]{⟨width⟩}{⟨height⟩}{⟨x⟩}{⟨y⟩}[⟨label⟩]`
First increment `\c@maxflow`, and define boolean to indicate whether or not the **flow frame** has a border, Then check to see whether or not the starred version is begin used. All the settings must be global: the output routine will create a new **flow frame**, if there are no more defined, and since changes made in the output routine are localised, the new **frame** will be lost unless it is globally defined. Flow frames should only be set up in the preamble, but if there are not enough **frames** to fit all the document text, the output routine will create a new **flow frame**. So, define `\newflowframe` so that it calls `\@n@wflowframe`

```
\newcommand{\newflowframe}{\@n@wflowframe}
```

Set the external command for use only in the preamble, and make the output routine use the internal command

```
\@onlypreamble{\newflowframe}
```

`\@n@wflowframe`

```
\newcommand{\@n@wflowframe}{%
\global\advance\c@maxflow by 1\relax
\expandafter\global\expandafter
\newif\csname ifcolumnframe\romannumeral\c@maxflow\endcsname
\@ifstar\@snewflowframe\@newflowframe
}
```

`\@snewflowframe` Starred version sets boolean flag to indicate a border

```
\newcommand{\@snewflowframe}{%
\expandafter\global\expandafter
\let\csname ifcolumnframe\romannumeral\c@maxflow\endcsname\iftrue
\@@newflowframe}
```

`\@newflowframe` The unstarred version unsets boolean flag to indicate no border.

```
\newcommand{\@newflowframe}{%
\expandafter\global\expandafter
\let\csname ifcolumnframe\romannumeral\c@maxflow\endcsname\iffalse
\@@newflowframe}
```

`\@@newflowframe` Now get on with initialising the **flow frame**. By default, it will apply the **flow frame** to all pages, the optional argument can override this.

```
\newcommand{\@@newflowframe}[5][all]{%
\expandafter\global\expandafter
\newbox\csname column\romannumeral\c@maxflow\endcsname
\expandafter\global\expandafter
\newlength\csname colwidth\romannumeral\c@maxflow\endcsname
\expandafter\global\expandafter
\newlength\csname colheight\romannumeral\c@maxflow\endcsname
\expandafter\global\expandafter
\newlength\csname col@romannumeral\c@maxflow @posx\endcsname
\expandafter\global\expandafter
\newlength\csname col@romannumeral\c@maxflow @posy\endcsname
\expandafter\global\expandafter
\setlength\csname colwidth\romannumeral\c@maxflow\endcsname{#2}
\expandafter\global\expandafter
```

```

\setlength\csname colheight\romannumeral\c@maxflow\endcsname{#3}
\expandafter\global\expandafter
\setlength\csname col@\romannumeral\c@maxflow @posx\endcsname{#4}
\expandafter\global\expandafter
\setlength\csname col@\romannumeral\c@maxflow @posy\endcsname{#5}
\expandafter\global\expandafter
\newlength\csname col@\romannumeral\c@maxflow @evenx\endcsname
\expandafter\global\expandafter
\newlength\csname col@\romannumeral\c@maxflow @eveny\endcsname
\expandafter\global\expandafter
\setlength\csname col@\romannumeral\c@maxflow @evenx\endcsname{#4}
\expandafter\global\expandafter
\setlength\csname col@\romannumeral\c@maxflow @eveny\endcsname{#5}
\expandafter
\gdef\csname @ff@frametype@\romannumeral\c@maxflow\endcsname{fbox}%
\expandafter
\gdef\csname @ff@col@\romannumeral\c@maxflow\endcsname{\flowframecol}
\expandafter
\gdef\csname @ff@txtcol@\romannumeral\c@maxflow\endcsname{%
\flowframetextcol}
\expandafter
\gdef\csname @ff@backcol@\romannumeral\c@maxflow\endcsname{{none}}
\expandafter
\gdef\csname @ff@pages@\romannumeral\c@maxflow\endcsname{#1}
\expandafter
\gdef\csname @ff@offset@\romannumeral\c@maxflow\endcsname{compute}
\expandafter
\gdef\csname @ff@angle@\romannumeral\c@maxflow\endcsname{0}%
\expandafter
\gdef\csname @ff@margin@\romannumeral\c@maxflow\endcsname{right}
\ifnum\c@thisframe=0\relax
\ifthenelse{equal{#1}{all}}\TEor\equal{#1}{odd}}{%
\c@thisframe=\c@maxflow
\global\setlength{\hspace}{#2}%
\global\usedframebreaktrue
}{\ifthenelse{equal{#1}{even}}\TEor\equal{#1}{none}}}{%
\def\ff@pages{#1}%
\@for\@ff@pp:=\ff@pages\do{%
\def\@ff@numstart{0}\def\@ff@numend{0}%
\@ff@getrange{\@ff@pp}%
\ifnum\@ff@numstart=0\def\@ff@numstart{1}\fi
\ifnum\@ff@numstart=1\relax
\c@thisframe=\c@maxflow
\global\setlength{\hspace}{#2}%
\global\usedframebreaktrue
\fi
}}}%
\fi
\@ifnextchar[{\@s@tflowframeid{\c@maxflow}}{%
\@s@tflowframeid{\c@maxflow}[\number\c@maxflow]}

```

\@s@tflowframeid If square brackets occur after \newflowframe, take the contents to be the label, otherwise the label will be the **flow frame** number.

```

\def\@s@tflowframeid#1[#2]{%

```

```

\edef\ff@label{#2}%
\@ff@checkuniqueidl{#1}{\ff@label}%
\expandafter
\xdef\csname @col@id@\romannumeral#1\endcsname{\ff@label}%
}

```

`\@ff@checkuniqueidl` Check **identification label (IDL)** #2 for **flow frame** #1 is unique

```

\newcommand*{\@ff@checkuniqueidl}[2]{%
{\@colN=0\relax
\whiledo{\@colN<\c@maxflow}{%
\advance\@colN by 1\relax
\ifnum\@colN=#1\relax
\else
\ifthenelse{\equal{#2}{%
\csname @col@id@\romannumeral\@colN\endcsname}}{%
\PackageError{flowfram}{Flow frame IDL '#2' already defined}{%
You can't assign this label, as it is already defined
for flow frame \number\@colN}}}%
\fi
}}

```

`\@flowframeid` Work out the **flow frame identification number (IDN)** from the label. This iterates through the **flow frames**, so if you have a lot of them it is quicker to identify them by their **IDN** rather than their **IDL**. The **IDN** stored in `\ff@id`.

```

\newcommand*{\@flowframeid}[1]{\@colN=0\relax
\ff@id=0\relax
\whiledo{\@colN<\c@maxflow}{\advance\@colN by 1\relax
\ifthenelse{%
\equal{#1}{\csname @col@id@\romannumeral\@colN\endcsname}}{%
\ff@id=\@colN\relax
% break out of loop
\@colN=\c@maxflow}{}}%
\ifnum\ff@id=0\relax
\PackageError{flowfram}{Can't find flow frame id '#1'}{\fi}

```

Set up the keys for use with `\setflowframe`, `\setstaticframe` and `\setdynamicframe`.
Frame width is stored in `\ff@width`.

```

\define@key{flowframe}{width}{\ifthenelse{\equal{#1}{}}{%
\PackageError{flowfram}{Missing value for 'width' key}{}}{%
\def\ff@width{#1}}

```

Frame height is stored in `\ff@height`.

```

\define@key{flowframe}{height}{\ifthenelse{\equal{#1}{}}{%
\PackageError{flowfram}{Missing value for 'height' key}{}}{%
\def\ff@height{#1}}

```

Frame *x* co-ordinate (odd and even pages) is stored in `\ff@x`.

```

\define@key{flowframe}{x}{\ifthenelse{\equal{#1}{}}{%
\PackageError{flowfram}{Missing value for 'x' key}{}}{%
\def\ff@x{#1}}

```

Frame *y* co-ordinate (odd and even pages) is stored in `\ff@y`.

```

\define@key{flowframe}{y}{\ifthenelse{\equal{#1}{}}{%
\PackageError{flowfram}{Missing value for 'y' key}{}}{%
\def\ff@y{#1}}

```

Frame x co-ordinate (even pages only) is stored in `\ff@evenx`.

```
\define@key{flowframe}{evenx}{\ifthenelse{\equal{#1}{}}{ }{%
\PackageError{flowfram}{Missing value for 'evenx' key}{ } }{%
\def\ff@evenx{#1}}}
```

Frame y co-ordinate (even pages only) is stored in `\ff@eveny`.

```
\define@key{flowframe}{eveny}{\ifthenelse{\equal{#1}{}}{ }{%
\PackageError{flowfram}{Missing value for 'eveny' key}{ } }{%
\def\ff@eveny{#1}}}
```

Frame x co-ordinate (odd pages only if twoside implemented) is stored in `\ff@oddx`.

```
\define@key{flowframe}{oddx}{\ifthenelse{\equal{#1}{}}{ }{%
\PackageError{flowfram}{Missing value for 'oddx' key}{ } }{%
\def\ff@oddx{#1}}}
```

Frame y co-ordinate (odd pages only if twoside implemented) is stored in `\ff@oddy`.

```
\define@key{flowframe}{oddy}{\ifthenelse{\equal{#1}{}}{ }{%
\PackageError{flowfram}{Missing value for 'oddy' key}{ } }{%
\def\ff@oddy{#1}}}
```

New IDL for `frame` is stored in `\ff@label`.

```
\define@key{flowframe}{label}{\ifthenelse{\equal{#1}{}}{ }{%
\PackageError{flowfram}{Missing value for 'label' key}{ } }{%
\def\ff@label{#1}}}
```

Frame border. If none, define `\ff@frame` as false, otherwise define `\ff@frame` as true. If plain, define `\ff@frametype` as fbox, otherwise define it to be the specified type, which should be the name of a `frame making command` without the preceding backslash.

```
\define@key{flowframe}{border}[plain]{\ifthenelse{\equal{#1}{}}{ }{%
\PackageError{flowfram}{Missing value for 'border' key - use
'none' for no border}{ } }{%
\ifthenelse{\equal{#1}{none}}{ }{%
\def\ff@frame{false}}{\def\ff@frame{true}}%
\ifthenelse{\equal{#1}{plain}}{\def\ff@frametype{fbox}}{%
\def\ff@frametype{#1}}}
```

Frame's border colour. (This may not work for non-standard `frame making commands`.)

```
\define@key{flowframe}{bordercolor}{\ifthenelse{\equal{#1}{}}{ }{%
\PackageError{flowfram}{Missing value for 'bordercolor' key}{ } }{%
\def\ff@col{#1}}}
```

Frame's text colour.

```
\define@key{flowframe}{textcolor}{\ifthenelse{\equal{#1}{}}{ }{%
\PackageError{flowfram}{Missing value for 'textcolor' key}{ } }{%
\def\ff@txtcol{#1}}}
```

The background colour of the `frame`. Note this only covers the region of the `bounding box`, not any extra space between the `bounding box` and the border. If you want the background colour to go right up to the border, you will need to define your own customised border.

```
\define@key{flowframe}{backcolor}{\ifthenelse{\equal{#1}{}}{ }{%
\PackageError{flowfram}{Missing value for 'backcolor' key}{ } }{%
\def\ff@backcol{#1}}}
```

Page list for which the frame should appear.

```
\define@key{flowframe}{pages}{\ifthenelse{\equal{#1}{}}{%
\PackageError{flowframe}{Missing value for 'pages' key}{}}{%
\def\ff@pages{#1}}}
```

The border takes up extra space, which needs to be adjusted. This can be done for standard border types, but non-standard borders may require some help.

```
\define@key{flowframe}{offset}{\def\ff@offset{#1}%
\ifthenelse{\equal{#1}{}}{\PackageError{flowframe}{%
Invalid value for key 'offset'}{%
'offset' can either be 'compute' (to compute it according
to certain pre-defined rules) or a length}}{}}
```

Angle to rotate flow frame:

```
\define@key{flowframe}{angle}{\def\ff@angle{#1}%
}
```

This key is only for flow frames:

```
\define@key{flowframe}{margin}{%
\ifthenelse{\equal{#1}{left} \or \equal{#1}{right}
\or \equal{#1}{inner} \or \equal{#1}{outer}}{%
\def\ff@margin{#1}}{\PackageError{flowframe}{invalid value of
'margin' key}{Key 'margin' can only take the values
'left' or 'right'}}}
```

This key is only for static frames:

```
\define@key{flowframe}{clear}[true]{%
\ifthenelse{\equal{#1}{true}\or\equal{#1}{false}}{%
\def\ff@clear{#1}}{\PackageError{flowframe}{Key 'clear' is
boolean}{You can only specify the values 'true' or 'false'}}}
```

This key is only for dynamic frames:

```
\define@key{flowframe}{style}{\ifthenelse{\equal{#1}{}}{%
\PackageError{flowframe}{Missing value for 'style' key}{}}{%
\ifthenelse{\equal{#1}{none}}{\def\ff@style{relax}}{\def\ff@style{#1}}}
```

This key is only for static frames and dynamic frames.

```
\define@key{flowframe}{shape}{\def\ff@shape{#1}%
}
```

This key is only for static frames and dynamic frames.

```
\define@key{flowframe}{valign}{\ifthenelse{\equal{#1}{c} \or
\equal{#1}{t} \or \equal{#1}{b}}{\def\ff@valign{#1}}{%
\PackageError{flowframe}{Invalid value for 'valign' key}{You
may only specify 'c', 't' or 'b'}}}
```

\setallflowframes Provide a command to change the settings for all flow frames. This just iterates through all the flow frames, and sets each one in turn.

```
\newcommand*\setallflowframes[1]{%
\@colN=0\whiledo{\@colN<\c@maxflow}{\advance\@colN by 1\relax
\@@setflowframe{\@colN}{#1}}}
```

\setflowframe Define \setflowframe command. Check to see whether or not the starred version is being used.

```
\newcommand*\setflowframe{\@ifstar\@ssetflowframe\setflowframe}
```

`\@ssetflowframe` This is the starred version. It finds the IDN for each label in the comma-separated list (first argument), and applies the setting for that numbered flow frame.

```

\newcommand{\@ssetflowframe}[2]{%
  \@for\@ff@id:=#1\do{%
    \@flowframeid{\@ff@id}%
    \@setflowframe{\@ff@id}{#2}}

```

`\@setflowframe` This is the unstarred version. It iterates through each IDN in the comma-separated list passed as the first argument, but it also checks for number ranges, and sets the values for that flow frame. Ensures that number ranges do not lie out of bounds.

```

\newcommand*{\@setflowframe}[2]{%
  \ifthenelse{\equal{#1}{all}}{%
    \setallflowframes{#2}}{%
    \ifthenelse{\equal{#1}{odd} \TEor \equal{#1}{even}}{%
      \ifthenelse{\equal{#1}{odd}}{\@colN=1}{\@colN=2}%
      \whiledo{\@colN<\c@maxflow\TEor\@colN=\c@maxflow}{%
        \@setflowframe{\@colN}{#2}%
        \advance\@colN by 2\relax}%
      }{%
        \@for\@ff@id:=#1\do{%
          \def\@ff@numstart{0}\def\@ff@numend{10000}%
          \@ff@getrange{\@ff@id}%
          \ifnum\@ff@numstart=0\relax
            \def\@ff@numstart{1}%
          \fi
          \ifnum\@ff@numend>\c@maxflow
            \def\@ff@numend{\c@maxflow}%
          \fi
          \@colN=\@ff@numstart
          \whiledo{\@colN<\@ff@numend \TEor \@colN=\@ff@numend}{%
            \@setflowframe{\@colN}{#2}%
            \advance\@colN by 1\relax
          }}}}

```

`\@@setflowframe` This is the command that actually sets the values for the flow frame whose IDN is specified by the first parameter.

```

\newcommand*{\@@setflowframe}[2]{%
  \def\@ff@frame{}\def\@ff@width{}\def\@ff@height{}\def\@ff@margin{%
  \def\@ff@x{}\def\@ff@y{}\def\@ff@frametype{}\def\@ff@col{%
  \def\@ff@valign{}\def\@ff@style{%
  \def\@ff@txtcol{}\def\@ff@clear{}\def\@ff@offset{}\def\@ff@pages{%
  \def\@ff@label{}\def\@ff@backcol{}\def\@ff@evenx{}\def\@ff@eveny{%
  \def\@ff@oddx{}\def\@ff@oddy{}\def\@ff@angle{}\def\@ff@shape{\empty}%
  \setkeys{flowframe}{#2}%
  \ifthenelse{\equal{\@ff@frame}{} }{}{%
    \setboolean{columnframe\romannumeral#1}{\@ff@frame}%
  \ifthenelse{\equal{\@ff@width}{} }{}{%
    \expandafter\setlength\csname colwidth\romannumeral#1\endcsname
      {\@ff@width}%
    \ifthenelse{\equal{\@ff@height}{} }{}{%
      \expandafter\setlength\csname colheight\romannumeral#1\endcsname
        {\@ff@height}%
    \ifthenelse{\equal{\@ff@x}{} }{}{%

```

```

\expandafter\setlength\csname col@romannumeral#1@posx\endcsname
{\ff@x}%
\expandafter\setlength\csname col@romannumeral#1@evenx\endcsname
{\ff@x}}
\ifthenelse{\equal{\ff@y}{}}{}{%
\expandafter\setlength\csname col@romannumeral#1@posy\endcsname
{\ff@y}%
\expandafter\setlength\csname col@romannumeral#1@eveny\endcsname
{\ff@y}}
\ifthenelse{\equal{\ff@evenx}{}}{}{%
\expandafter\setlength\csname col@romannumeral#1@evenx\endcsname
{\ff@evenx}}
\ifthenelse{\equal{\ff@eveny}{}}{}{%
\expandafter\setlength\csname col@romannumeral#1@eveny\endcsname
{\ff@eveny}}
\ifthenelse{\equal{\ff@oddx}{}}{}{%
\expandafter\setlength\csname col@romannumeral#1@posx\endcsname
{\ff@oddx}}
\ifthenelse{\equal{\ff@oddy}{}}{}{%
\expandafter\setlength\csname col@romannumeral#1@posy\endcsname
{\ff@oddy}}
\ifthenelse{\equal{\ff@label}{}}{}{%
\@s@tflowframeid{#1}[\ff@label]}
\ifthenelse{\equal{\ff@frametype}{}}{}{%
\expandafter\edef\csname @ff@frametype@romannumeral#1\endcsname
{\ff@frametype}}
\ifthenelse{\equal{\ff@col}{}}{}{%
\expandafter\@setframecol\ff@col\end{#1}{col}{ff}}
\ifthenelse{\equal{\ff@txtcol}{}}{}{%
\expandafter\@setframecol\ff@txtcol\end{#1}{txtcol}{ff}}%
\ifthenelse{\equal{\ff@backcol}{}}{}{%
\expandafter\@setframecol\ff@backcol\end{#1}{backcol}{ff}}%
\ifthenelse{\equal{\ff@margin}{}}{}{%
\expandafter\xdef\csname @ff@margin@romannumeral#1\endcsname
{\ff@margin}}%
\ifthenelse{\equal{\ff@pages}{}}{}{%
\expandafter\xdef\csname @ff@pages@romannumeral#1\endcsname
{\ff@pages}}%
\ifthenelse{\equal{\ff@offset}{}}{}{%
\expandafter\xdef\csname @ff@offset@romannumeral#1\endcsname
{\ff@offset}}%
\ifthenelse{\equal{\ff@angle}{}}{}{%
\expandafter\xdef\csname @ff@angle@romannumeral#1\endcsname
{\ff@angle}}%
\ifthenelse{\equal{\ff@clear}{}}{}{%
\PackageError{flowfram}%
{Key 'clear' not available for flow frames}{}%
\ifthenelse{\equal{\ff@style}{}}{}{%
\PackageError{flowfram}%
{Key 'style' not available for flow frames}{}%
\if\ff@shape\empty
\else
\PackageError{flowfram}%
{Key 'shape' not available for flow frames}{}%

```

```

\fi
\ifthenelse{\equal{\ff@valign}{}}{}{%
\PackageError{flowfram}%
{Key 'valign' not available for flow frames}{}%
}

```

`\ffswapoddeven` Swap odd and even offsets for a given **flow frame**. Do the main stuff for a given **flow frame IDN**.

```

\newcommand*{\@@flowframeswapcoords}[1]{%
\setlength{\@ff@tmp@x}{%
\csname col@romannumeral#1@evenx\endcsname}
\expandafter\setlength\csname col@romannumeral#1@evenx\endcsname
{\csname col@romannumeral#1@posx\endcsname}%
\expandafter\setlength\csname col@romannumeral#1@posx\endcsname
{\@ff@tmp@x}%
\setlength{\@ff@tmp@y}{%
\csname col@romannumeral#1@eveny\endcsname}
\expandafter\setlength\csname col@romannumeral#1@eveny\endcsname
{\csname col@romannumeral#1@posy\endcsname}%
\expandafter\setlength\csname col@romannumeral#1@posy\endcsname
{\@ff@tmp@y}%
}

```

`\ffswapoddeven` Allow user to specify **flow frame** either by **IDN** or **IDL**:

```

\newcommand*{\ffswapoddeven}{%
\ifstar\@sflowframeswapcoords\@flowframeswapcoords}

```

`\@sflowframeswapcoords` Starred form

```

\newcommand*{\@sflowframeswapcoords}[1]{%
\@for\@ff@id:=#1\do{%
\@flowframeid{\@ff@id}%
\@@flowframeswapcoords{\ff@id}}

```

`\@flowframeswapcoords` Unstarred form:

```

\newcommand*{\@flowframeswapcoords}[1]{%
\ifthenelse{\equal{#1}{all}}{%
\ff@id=0\relax
\whiledo{\ff@id<\c@maxflow}{\advance\ff@id by 1\relax
\@@flowframeswapcoords{\ff@id}}%
}%
\ifthenelse{\equal{#1}{odd} \TEor \equal{#1}{even}}{%
\ifthenelse{\equal{#1}{odd}}{\@colN=1}{\@colN=2}%
\whiledo{\@colN<\c@maxflow\TEor\@colN=\c@maxflow}{%
\@@flowframeswapcoords{\@colN}%
\advance\@colN by 2\relax}%
}%
\@for\@ff@id:=#1\do{%
\def\@ff@numstart{0}\def\@ff@numend{10000}%
\@ff@getrange{\@ff@id}%
\ifnum\@ff@numstart=0\relax
\def\@ff@numstart{1}%
\fi
\ifnum\@ff@numend>\c@maxflow
\def\@ff@numend{\c@maxflow}%

```

```

\fi
\@colN=\@ff@numstart
\whiledo{\@colN<\@ff@numend \TE@or \@colN=\@ff@numend}{\%
\@@flowframeswapcoords{\@colN}%
\advance\@colN by 1\relax
}}}}

```

Allow user to get the dimensions of **flow frame** (useful for **flow frames** created using `\Ncolumns` etc.) Only the **IDN** can be used for these commands.

```

\flowframex
\newcommand*\flowframex[1]{%
\csname col@romannumeral#1@posx\endcsname}

\flowframey
\newcommand*\flowframey[1]{%
\csname col@romannumeral#1@posy\endcsname}

\flowframeevenx
\newcommand*\flowframeevenx[1]{%
\csname col@romannumeral#1@evenx\endcsname}

\flowframeeveny
\newcommand*\flowframeeveny[1]{%
\csname col@romannumeral#1@eveny\endcsname}

\flowframewidth
\newcommand*\flowframewidth[1]{%
\csname colwidth\romannumeral#1\endcsname}

\flowframeheight
\newcommand*\flowframeheight[1]{%
\csname colheight\romannumeral#1\endcsname}

\@setframecol Set the colour of the frame, this is a little tricky because the model may need
to be specified in square brackets. First check to see if a colour model has been
specified
\def\@setframecol{\@ifnextchar[\@setframecol\@setfr@mecol}

\@@setframecol A colour model has been specified.
\def\@@setframecol[#1]#2\end#3#4#5{%
\expandafter\edef\csname @#5@#4@\romannumeral#3\endcsname{%
[#1]{#2}}}}

\@@setfr@mecol A colour model has not been specified.
\def\@@setfr@mecol#1\end#2#3#4{%
\expandafter\edef\csname @#4@#3@\romannumeral#2\endcsname{{#1}}}}

```

1.3 Static Frames

`\newstaticframe` Now deal with setting up the **static frames**. This is similar to the **flow frames**, except it has an associated L^AT_EX savebox rather than a T_EX box. Syntax:
`\newstaticframe[⟨pages⟩]{⟨width⟩}{⟨height⟩}{⟨x⟩}{⟨y⟩}[⟨label⟩]`
 As with `\newflowframe`, the final optional argument is dealt with at the end.
`\newcommand*{\newstaticframe}{\@n@wstaticframe}`

`\@n@wstaticframe`

```
\newcommand*{\@n@wstaticframe}{%
\global\advance\c@maxstatic by 1\relax
\newboolean{staticframe\romannumeral\c@maxstatic}%
\@ifstar{\@snewstaticframe\@newstaticframe
}
```

`\@snewstaticframe` Starred version (has a border):

```
\newcommand{\@snewstaticframe}{%
\setboolean{staticframe\romannumeral\c@maxstatic}{true}%
\@@newstaticframe}
```

`\@newstaticframe` Unstarred version (no border):

```
\newcommand{\@newstaticframe}{%
\setboolean{staticframe\romannumeral\c@maxstatic}{false}%
\@@newstaticframe}
```

`\@@newstaticframe` Now set up the **static frame**:

```
\newcommand*{\@@newstaticframe}[5][all]{%
\expandafter
\newbox\csname @staticframe@\romannumeral\c@maxstatic\endcsname
\expandafter
\newlength\csname @sf@\romannumeral\c@maxstatic @posx\endcsname
\expandafter
\newlength\csname @sf@\romannumeral\c@maxstatic @posy\endcsname
\expandafter\setlength
\csname @sf@\romannumeral\c@maxstatic @posx\endcsname{#4}%
\expandafter\setlength
\csname @sf@\romannumeral\c@maxstatic @posy\endcsname{#5}%
\expandafter\newlength
\csname @sf@\romannumeral\c@maxstatic @evenx\endcsname
\expandafter\newlength
\csname @sf@\romannumeral\c@maxstatic @eveny\endcsname
\expandafter\setlength
\csname @sf@\romannumeral\c@maxstatic @evenx\endcsname{#4}%
\expandafter\setlength
\csname @sf@\romannumeral\c@maxstatic @eveny\endcsname{#5}%
{\@ff@tmp@x=#2\relax
\@ff@tmp@y=#3\relax
\expandafter
\xdef\csname @sf@dim@\romannumeral\c@maxstatic\endcsname{%
[c][\the\@ff@tmp@y][c]{\the\@ff@tmp@x}}}%
\expandafter
\def\csname @sf@col@\romannumeral\c@maxstatic\endcsname{%
\flowframecol}%
```

```

\expandafter
\def\csname @sf@txtcol@\romannumeral\c@maxstatic\endcsname{%
\flowframetextcol}%
\expandafter
\def\csname @sf@backcol@\romannumeral\c@maxstatic\endcsname{%
{none}}}%
\expandafter
\xdef\csname @sf@pages@\romannumeral\c@maxstatic\endcsname{#1}%
\expandafter
\gdef\csname @sf@offset@\romannumeral\c@maxstatic\endcsname{%
compute}%
\expandafter
\gdef\csname @sf@angle@\romannumeral\c@maxstatic\endcsname{0}%
\expandafter
\gdef\csname @sf@shape@\romannumeral\c@maxstatic\endcsname{\relax}%
\expandafter
\def\csname @sf@frametype@\romannumeral\c@maxstatic\endcsname{%
fbox}%
\newboolean{@sf@clear@\romannumeral\c@maxstatic}%
\setboolean{@sf@clear@\romannumeral\c@maxstatic}{false}
\@ifnextchar[{\@s@tstaticframeid{\c@maxstatic}}%
{\@s@tstaticframeid{\c@maxstatic}[\number\c@maxstatic]}}

```

`\@s@tstaticframeid` Set the label for the **static frame**:

```

\def\@s@tstaticframeid#1[#2]{%
\edef\ff@label{#2}%
\@sf@checkuniqueidl{#1}{\ff@label}%
\expandafter
\xdef\csname @sf@id@\romannumeral#1\endcsname{\ff@label}}

```

`\@sf@checkuniqueidl` Check **IDL #2** for **static frame #1** is unique

```

\newcommand*{\@sf@checkuniqueidl}[2]{%
\@colN=0\relax
\whiledo{\@colN<\c@maxstatic}{%
\advance\@colN by 1\relax
\ifnum\@colN=#1\relax
\else
\ifthenelse{%
\equal{#2}{\csname @sf@id@\romannumeral\@colN\endcsname}}{%
\PackageError{flowfram}{Static frame IDL '#2' already defined}{%
You can't assign this label, as it is already defined
for static frame \number\@colN}}}%
\fi
}}

```

`\@staticframeid` Work out the **IDN** of the **static frame** with the given label. This iterates through each **static frame**, so if there are a lot of **static frames**, it may take a while. The **IDN** stored in `\ff@id`.

```

\newcommand*{\@staticframeid}[1]{\@colN=0\relax
\ff@id=0\relax
\whiledo{\@colN<\c@maxstatic}{\advance\@colN by 1\relax
\ifthenelse{%
\equal{#1}{\csname @sf@id@\romannumeral\@colN\endcsname}}{%
\ff@id=\@colN\relax

```

```
% break out of loop
\@colN=\c@maxstatic}{})%
\ifnum\ff@id=0\PackageError{flowfram}{Can't find static frame
id '#1'}{}\fi}
```

Make it easier to get the x and y values for static frames. (Width and height stored differently.)

```
\staticframex
\newcommand*\staticframex[1]{%
\csname @sf@romannumeral#1@posx\endcsname}

\staticframey
\newcommand*\staticframey[1]{%
\csname @sf@romannumeral#1@posy\endcsname}

\staticframeevenx
\newcommand*\staticframeevenx[1]{%
\csname @sf@romannumeral#1@evenx\endcsname}

\staticframeeveny
\newcommand*\staticframeeveny[1]{%
\csname @sf@romannumeral#1@eveny\endcsname}

\setallstaticframes Modify the settings for all the static frames:
\newcommand*\setallstaticframes[1]{%
\@colN=0\whiledo{\@colN<\c@maxstatic}{\advance\@colN by 1\relax
\@setstaticframe{\@colN}{#1}}

\setstaticframe Modify the settings for the specified static frames:
\newcommand*\setstaticframe{%
\ifstar\@ssetstaticframe\setstaticframe}

\@ssetstaticframe Starred version: Iterate through the comma-separated list of labels.
\newcommand*\@ssetstaticframe[2]{%
\@for\@ff@id:=#1\do{%
\@staticframeid{\@ff@id}%
\@setstaticframe{\@ff@id}{#2}}}

\@setstaticframe Unstarred version. Iterate through the comma-separated list of IDNs, and check
for number ranges. Ensures that number ranges do not lie out of bounds.
\newcommand*\@setstaticframe[2]{%
\ifthenelse{\equal{#1}{all}}{%
\setallstaticframes{#2}}{%
\ifthenelse{\equal{#1}{odd} \TEor \equal{#1}{even}}{%
\ifthenelse{\equal{#1}{odd}}{\@colN=1}{\@colN=2}%
\whiledo{\@colN<\c@maxstatic\TEor\@colN=\c@maxstatic}{%
\@setstaticframe{\@colN}{#2}%
\advance\@colN by 2\relax}%
}%
\@for\@ff@id:=#1\do{%
\def\@ff@numstart{0}\def\@ff@numend{10000}%
\@ff@getrange{\@ff@id}%
```

```

\ifnum\@ff@numstart=0\relax
  \def\@ff@numstart{1}%
\fi
\ifnum\@ff@numend>\c@maxstatic
  \def\@ff@numend{\c@maxstatic}%
\fi
\@colN=\@ff@numstart
\whiledo{\@colN<\@ff@numend \TEor \@colN=\@ff@numend}{%
\@@setstaticframe{\@colN}{#2}%
\advance\@colN by 1\relax
}}}}

```

`\@@setstaticframe` Modify the settings for the **static frame** whose **IDN** is given by the first argument.

```

\newcommand*{\@@setstaticframe}[2]{%
\expandafter\expandafter\expandafter
\@ff@getstaticpos\csname @sf@dim@romannumeral#1\endcsname
\def\ff@frame{}\edef\ff@width{\the\@ff@tmp@x}\def\ff@angle{}%
\edef\ff@height{\the\@ff@tmp@y}\def\ff@style{}\def\ff@frametype{}%
\def\ff@x{}\def\ff@y{}\def\ff@col{}\def\ff@txtcol{}%
\def\ff@backcol{}\def\ff@shape{0}%
\def\ff@clear{}\def\ff@margin{}\def\ff@offset{}\def\ff@pages{}%
\def\ff@label{}\def\ff@evenx{}\def\ff@eveny{}%
\def\ff@oddx{}\def\ff@oddy{}%
\setkeys{flowframe}{#2}%
\ifthenelse{\equal{\ff@frame}{}}{ }{%
\setboolean{staticframe\romannumeral#1}{\ff@frame}}%
\ifthenelse{\equal{\ff@x}{}}{ }{%
\expandafter\global
\expandafter\setlength\csname @sf@romannumeral#1@posx\endcsname
{\ff@x}%
\expandafter\global
\expandafter\setlength\csname @sf@romannumeral#1@evenx\endcsname
{\ff@x}%
\ifthenelse{\equal{\ff@y}{}}{ }{%
\expandafter\global
\expandafter\setlength\csname @sf@romannumeral#1@posy\endcsname
{\ff@y}%
\expandafter\global
\expandafter\setlength\csname @sf@romannumeral#1@eveny\endcsname
{\ff@y}%
\ifthenelse{\equal{\ff@evenx}{}}{ }{%
\expandafter\global
\expandafter\setlength\csname @sf@romannumeral#1@evenx\endcsname
{\ff@evenx}%
\ifthenelse{\equal{\ff@eveny}{}}{ }{%
\expandafter\global
\expandafter\setlength\csname @sf@romannumeral#1@eveny\endcsname
{\ff@eveny}%
\ifthenelse{\equal{\ff@oddx}{}}{ }{%
\expandafter\global
\expandafter\setlength\csname @sf@romannumeral#1@posx\endcsname
{\ff@oddx}%
\ifthenelse{\equal{\ff@oddy}{}}{ }{%
\expandafter\global

```

```

\expandafter\setlength\csname @sf@romannumeral#1@posy\endcsname
{\ff@oddy}}%
\expandafter
\xdef\csname @sf@dim@romannumeral#1\endcsname{%
[c][\ff@height][\ff@valign]{\ff@width}}%
\ifthenelse{\equal{\ff@frametype}{}}{}{}%
\expandafter
\xdef\csname @sf@frametype@romannumeral#1\endcsname{%
\ff@frametype}}%
\ifthenelse{\equal{\ff@label}{}}{}{}%
\@s@tstaticframeid{#1}[\ff@label]}
\ifthenelse{\equal{\ff@col}{}}{}{}%
\expandafter\@setframecol\ff@col\end{#1}{col}{sf}}%
\ifthenelse{\equal{\ff@txtcol}{}}{}{}%
\expandafter\@setframecol\ff@txtcol\end{#1}{txtcol}{sf}}%
\ifthenelse{\equal{\ff@backcol}{}}{}{}%
\expandafter\@setframecol\ff@backcol\end{#1}{backcol}{sf}}%
\ifthenelse{\equal{\ff@offset}{}}{}{}%
\expandafter
\xdef\csname @sf@offset@romannumeral#1\endcsname{\ff@offset}}%
\ifthenelse{\equal{\ff@angle}{}}{}{}%
\expandafter
\xdef\csname @sf@angle@romannumeral#1\endcsname{\ff@angle}}%
\if0\ff@shape
\else
\expandafter\global\expandafter
\let\csname @sf@shape@romannumeral#1\endcsname\ff@shape
\fi
\ifthenelse{\equal{\ff@pages}{}}{}{}%
\expandafter
\xdef\csname @sf@pages@romannumeral#1\endcsname{\ff@pages}}%
\ifthenelse{\equal{\ff@clear}{}}{}{}%
\setboolean{@sf@clear@romannumeral#1}{\ff@clear}}%
\ifthenelse{\equal{\ff@margin}{}}{}{}%
\PackageError{flowfram}{Key 'margin' not available for
static frames}{Static frames don't have marginal notes}}%
\ifthenelse{\equal{\ff@style}{}}{}{}%
\PackageError{flowfram}{Key 'style' not available for
static frames}{}}%
}

\simpar Simulate paragraph break inside \shapepar
% \newcommand*{\simpar}{\hfil\vadjust{\vskip\parskip}\break\indent}
\newcommand*{\simpar}{\hfill\\ \indent\mbox{}}

\ffpshpar Provide means to allow parshape to be carried over a paragraph break.
\let\FLForgpar\par
\newcommand{\ffpshpar}{\edef\flf@next{\hangafter=\the\hangafter
\hangindent=\the\hangindent}\FLForgpar\flf@next
\edef\flf@next{\prevgraf=\the\prevgraf}\@ff@parshape\indent\mbox{}\flf@next}

Provide a means to have section headings within \parshape.

\@ff@parshape
\def\@ff@parshape{\parshape=0}

```

```

\@ff@sectionhead
    \newcommand*{\@ff@sectionhead}[1]{%
    \def\ff@sehead{#1}%
    \ffpshpar
    \@ifstar{\@s@ff@heading}{\@dblarg\@ff@heading}}

\@s@ff@heading
    \def\@s@ff@heading#1{%
    \@ifundefined{\ff@old\ff@sehead}{\PackageError{flowfram}{Unknown
heading command '\ff@sehead'}}{}{%
    \begingroup
    \edef\flf@next{\hangafter=\the\hangafter
    \hangindent=\the\hangindent}\FLForgpar\flf@next
    \let\par=\FLForgpar
    \edef\flf@next{\prevgraf=\the\prevgraf}%
    \csname @ff@old\ff@sehead\endcsname*{\@ff@parshape\flf@next
    #1}%
    \xdef\flf@next{\@ff@parshape
    \prevgraf=\the\prevgraf}%
    \endgroup
    }%
    \mbox{}\flf@next\let\flf@next\undefined}

\@ff@heading
    \def\@ff@heading[#1]#2{%
    \@ifundefined{\ff@old\ff@sehead}{\PackageError{flowfram}{Unknown
heading command '\ff@sehead'}}{}{%
    \begingroup
    \edef\flf@next{\hangafter=\the\hangafter
    \hangindent=\the\hangindent}\FLForgpar\flf@next
    \let\par=\FLForgpar
    \edef\flf@next{\prevgraf=\the\prevgraf}%
    \csname @ff@old\ff@sehead\endcsname[#1]{\@ff@parshape\flf@next
    #2}%
    \xdef\flf@next{\@ff@parshape
    \prevgraf=\the\prevgraf}%
    \endgroup}%
    \mbox{}\flf@next\let\flf@next\undefined}

\@ff@setsecthead Define command to switch to adjusted section headings:
    \newcommand*{\@ff@setsecthead}{%
    \let\@ff@oldsection=\section
    \let\@ff@oldsubsection=\subsection
    \let\@ff@oldsubsubsection=\subsubsection
    \let\@ff@oldparagraph=\paragraph
    \let\@ff@oldsubparagraph=\subparagraph
    \def\section{\@ff@sectionhead{section}}%
    \def\subsection{\@ff@sectionhead{subsection}}%
    \def\subsubsection{\@ff@sectionhead{subsubsection}}%
    \def\paragraph{\@ff@sectionhead{paragraph}}%
    \def\subparagraph{\@ff@sectionhead{subparagraph}}%
    }

```

`\@ff@getshape` Determine what shape command is being used:

```
\def\@ff@getshape#1#2\relax{%
\ifx#1\parshape
\def\ff@shape{1}%
\else
\ifx#1\shapepar
\def\ff@shape{2}%
\else
\ifx#1\relax
\def\ff@shape{0}%
\else
\PackageError{flowfram}{Unknown shape \string#1}{}%
\def\ff@shape{2}%
\fi
\fi
\fi}
```

`\@ff@disablesec` Disable sectioning commands

```
\newcommand*\@ff@disablesec{%
\def\section{\PackageError{flowfram}{You can't have
sectioning commands within a \string\shapepar}{}}%
\def\subsection{\PackageError{flowfram}{You can't have
sectioning commands within a \string\shapepar}{}}%
\def\subsubsection{\PackageError{flowfram}{You can't have
sectioning commands within a \string\shapepar}{}}%
\def\paragraph{\PackageError{flowfram}{You can't have
sectioning commands within a \string\shapepar}{}}%
\def\subparagraph{\PackageError{flowfram}{You can't have
sectioning commands within a \string\shapepar}{}}%
}
```

`staticcontents` Set the contents of the **static frame** given by its **IDN**. Syntax: `\begin{staticcontents}{<idn>}`.

```
\newbox\staticframe
\newenvironment{staticcontents}[1]{%
\@ifundefined{@staticframe@romannumeral#1}{%
\PackageError{flowfram}{Static frame '#1' not defined}{}}{%
\expandafter\let\expandafter\@ff@parshape\csname @sf@shape@romannumeral#1\endcsname
\expandafter\@ff@getshape\@ff@parshape\relax
\ifcase\ff@shape
% no shape
\edef\@sf@mpg{%
\noexpand
\begin{minipage}\csname @sf@dim@romannumeral#1\endcsname
\noexpand\begin{group}
\noexpand\let\noexpand\FLForgpar=\noexpand\par
}%
\or
% \parshape
\edef\@sf@mpg{%
\noexpand
\begin{minipage}\csname @sf@dim@romannumeral#1\endcsname
\@ff@parshape
\noexpand\begin{group}
\noexpand\let\noexpand\FLForgpar=\noexpand\par
```

```

\noexpand\let\noexpand\par=\noexpand\ffpshpar
\noexpand\@ff@setsecthead
}%
\or
% \shapepar
\edef\@sf@mpg{%
\noexpand
\begin{minipage}\csname @sf@dim@\romannumeral#1\endcsname
\noexpand\begin{group}
\noexpand\@ff@disablesec
\noexpand\@ff@parshape
}%
\fi
\edef\@sf@thisframe{\csname @staticframe@\romannumeral#1\endcsname}%
\begin{lrbox}{\staticframe}%
\edef\ff@txtcol{\csname @sf@txtcol@\romannumeral#1\endcsname}%
\@s@tfftextcol\noindent
\@sf@mpg
\setlength\parindent\sdfparindent
}{\ifnum\ff@shape=2\par
\else\FLFor\par\fi\endgroup\end{minipage}\end{lrbox}%
\expandafter\global\expandafter\sbox\@sf@thisframe{%
\usebox\staticframe}\ignorespaces
}

```

staticcontents* Set the contents of the **static frame** given by its **IDL**. Syntax: `\begin{staticcontents*}{\langle label \rangle}`.
`\newenvironment{staticcontents*}[1]{\@staticframeid{#1}%`
`\begin{staticcontents}{\ff@id}}{\end{staticcontents}}`

\setstaticcontents Provide a command version. Syntax: `\setstaticcontents{\langle idn \rangle}{\langle text \rangle}`.
`\newcommand{\setstaticcontents}{\%`
`\@ifstar\@sstaticconts\@staticconts}`

\@sstaticconts Starred version: **static frame** identified by label.
`\newcommand{\@sstaticconts}[1]{\@staticframeid{#1}%`
`\@staticconts{\ff@id}}`

\@staticconts Unstarred version: **static frame** identified by **IDN**.
`\newcommand{\@staticconts}[2]{\begin{staticcontents}{#1}%`
`#2\end{staticcontents}}`

\@@staticframeswapcoords Swap odd and even offsets for a given **static frame**. Do the main stuff for a given **static frame IDN**.

```

\newcommand*\@@staticframeswapcoords[1]{%
\setlength{\ff@tmp@x}%
{\csname @sf@\romannumeral#1@evenx\endcsname}
\expandafter\setlength\csname @sf@\romannumeral#1@evenx\endcsname
{\csname @sf@\romannumeral#1@posx\endcsname}%
\expandafter\setlength\csname @sf@\romannumeral#1@posx\endcsname
{\ff@tmp@x}%
\setlength{\ff@tmp@y}%
{\csname @sf@\romannumeral#1@eveny\endcsname}
\expandafter\setlength\csname @sf@\romannumeral#1@eveny\endcsname

```

```
{\csname @sf@romannumeral#1@posy\endcsname}%
\expandafter\setlength\csname @sf@romannumeral#1@posy\endcsname
{\@ff@tmp@y}%
}
```

`\sfswapoddeven` Allow user to specify **flow frame** either by **IDN** or **IDL**:

```
\newcommand*\sfswapoddeven{%
\ifstar\@sstaticframeswapcoords\@staticframeswapcoords}
```

`\@sstaticframeswapcoords` Starred form

```
\newcommand*\@sstaticframeswapcoords[1]{%
\@for\@ff@id:=#1\do{%
\@staticframeid{\@ff@id}%
\@staticframeswapcoords{\@ff@id}}}
```

`\@staticframeswapcoords` Unstarred form:

```
\newcommand*\@staticframeswapcoords[1]{%
\ifthenelse{equal{#1}{all}}{%
\@ff@id=0\relax
\whiledo{\@ff@id<\c@maxflow}{\advance\@ff@id by 1\relax
\@staticframeswapcoords{\@ff@id}}%
}%
\ifthenelse{equal{#1}{odd} \TE@or \equal{#1}{even}}{%
\ifthenelse{equal{#1}{odd}}{\@colN=1}{\@colN=2}%
\whiledo{\@colN<\c@maxflow\TE@or\@colN=\c@maxflow}{%
\@staticframeswapcoords{\@colN}%
\advance\@colN by 2\relax}%
}%
\@for\@ff@id:=#1\do{%
\def\@ff@numstart{0}\def\@ff@numend{10000}%
\@ff@getrange{\@ff@id}%
\ifnum\@ff@numstart=0\relax
\def\@ff@numstart{1}%
\fi
\ifnum\@ff@numend>\c@maxflow
\def\@ff@numend{\c@maxflow}%
\fi
\@colN=\@ff@numstart
\whiledo{\@colN<\@ff@numend \TE@or \@colN=\@ff@numend}{%
\@staticframeswapcoords{\@colN}%
\advance\@colN by 1\relax
}}}}}
```

1.4 Dynamic Frames

Now deal with the **dynamic frames**. These are very similar to the **static frames**, but instead of having a savebox, the contents of the **dynamic frame** are stored in a macro.

`\newdynamicframe` Syntax:

```
\newdynamicframe[⟨pages⟩]{⟨width⟩}{⟨height⟩}{⟨x⟩}{⟨y⟩}[⟨label⟩]
\newcommand*\newdynamicframe{%
\@n@wdynamicframe}
```

```

\newcommand*{\@newdynamicframe}{%
\global\advance\c@maxdynamic by 1\relax
\newboolean{dynamicframe\romannumeral\c@maxdynamic}
\@ifstar\@snewdynamicframe\@newdynamicframe
}

\@snewdynamicframe Starred version: has a border.
\newcommand*{\@snewdynamicframe}{%
\setboolean{dynamicframe\romannumeral\c@maxdynamic}{true}%
\@@newdynamicframe}

\@newdynamicframe Unstarred version: no border.
\newcommand*{\@newdynamicframe}{%
\setboolean{dynamicframe\romannumeral\c@maxdynamic}{false}%
\@@newdynamicframe}

\@@newdynamicframe Create new dynamic frame:
\newcommand*{\@@newdynamicframe}[5][all]{%
\expandafter
\gdef\csname @dynamicframe@\romannumeral\c@maxdynamic\endcsname{%
\expandafter
\newlength\csname @df@\romannumeral\c@maxdynamic @posx\endcsname
\expandafter
\newlength\csname @df@\romannumeral\c@maxdynamic @posy\endcsname
\expandafter\setlength
\csname @df@\romannumeral\c@maxdynamic @posx\endcsname{#4}%
\expandafter\setlength
\csname @df@\romannumeral\c@maxdynamic @posy\endcsname{#5}%
\expandafter\newlength
\csname @df@\romannumeral\c@maxdynamic @evenx\endcsname
\expandafter\setlength
\csname @df@\romannumeral\c@maxdynamic @eveny\endcsname
\expandafter\setlength
\csname @df@\romannumeral\c@maxdynamic @evenx\endcsname{#4}%
\expandafter\setlength
\csname @df@\romannumeral\c@maxdynamic @eveny\endcsname{#5}%
{\@ff@tmp@x=#2\relax
\@ff@tmp@y=#3\relax
\expandafter
\xdef\csname @df@dim@\romannumeral\c@maxdynamic\endcsname{%
[c] [\the\@ff@tmp@y] [t]{\the\@ff@tmp@x}}}%
\expandafter
\gdef\csname @df@col@\romannumeral\c@maxdynamic\endcsname{%
\flowframecol}%
\expandafter
\gdef\csname @df@txtcol@\romannumeral\c@maxdynamic\endcsname{%
\flowframetextcol}%
\expandafter
\gdef\csname @df@backcol@\romannumeral\c@maxdynamic\endcsname{%
{none}}}%
\expandafter
\gdef\csname @df@pages@\romannumeral\c@maxdynamic\endcsname{#1}%
\expandafter
\gdef\csname @df@frametype@\romannumeral\c@maxdynamic\endcsname{%

```

```

fbox}%
\expandafter
\gdef\csname @df@style@\romannumeral\c@maxdynamic\endcsname{relax}%
\expandafter
\gdef\csname @df@offset@\romannumeral\c@maxdynamic\endcsname{compute}%
\expandafter
\gdef\csname @df@angle@\romannumeral\c@maxdynamic\endcsname{0}%
\expandafter
\gdef\csname @df@shape@\romannumeral\c@maxdynamic\endcsname{relax}%
\newboolean{@df@clear@\romannumeral\c@maxdynamic}%
\setboolean{@df@clear@\romannumeral\c@maxdynamic}{false}%
\@ifnextchar[{\@s@tdynamicframeid{\c@maxdynamic}}%
{\@s@tdynamicframeid{\c@maxdynamic}[number\c@maxdynamic]}%

```

`\@s@tdynamicframeid` Set the label for the given **dynamic frame**:

```

\def\@s@tdynamicframeid#1[#2]{%
\edef\ff@label{#2}%
\@df@checkuniqueidl{#1}{\ff@label}%
\expandafter
\xdef\csname @df@id@\romannumeral#1\endcsname{\ff@label}%

```

`\@df@checkuniqueidl` Check **IDL #2** for **static frame #1** is unique

```

\newcommand*{\@df@checkuniqueidl}[2]{%
\@colN=0\relax
\whiledo{\@colN<\c@maxdynamic}{%
\advance\@colN by 1\relax
\ifnum\@colN=#1\relax
\else
\ifthenelse{equal{#2}}%
{\csname @df@id@\romannumeral\@colN\endcsname}}{%
\PackageError{flowfram}{Dynamic frame IDL '#2' already defined}{%
You can't assign this label, as it is already defined
for dynamic frame \number\@colN}}}%
\fi
}}

```

`\@dynamicframeid` Determine the **IDN** of the **dynamic frame** from its label. The **IDN** is stored in `\ff@id`.

```

\newcommand*{\@dynamicframeid}[1]{\@colN=0\relax
\ff@id=0\relax
\whiledo{\@colN<\c@maxdynamic}{\advance\@colN by 1\relax
\ifthenelse{%
equal{#1}{\csname @df@id@\romannumeral\@colN\endcsname}}{%
\ff@id=\@colN\relax
% break out of loop
\@colN=\c@maxdynamic}}}%
\ifnum\ff@id=0\PackageError{flowfram}{Can't find dynamic frame
id '#1'}{\fi}

```

Make it easier to get the x and y values for dynamic frames. (Width and height stored differently.)

`\dynamicframex`

```

\newcommand*{\dynamicframex}[1]{%
\csname @df@\romannumeral#1@posx\endcsname}

```

`\dynamicframey`

```

\newcommand*\dynamicframey}[1]{%
\csname @df@romannumeral#1@posy\endcsname}

```

`\dynamicframeevenx`

```

\newcommand*\dynamicframeevenx}[1]{%
\csname @df@romannumeral#1@evenx\endcsname}

```

`\dynamicframeeveny`

```

\newcommand*\dynamicframeeveny}[1]{%
\csname @df@romannumeral#1@eveny\endcsname}

```

`\setalldynamicframes` Change the settings for all the **dynamic frames**:

```

\newcommand*\setalldynamicframes}[1]{%
\@colN=0\whiledo{\@colN<\c@maxdynamic}{\advance\@colN by 1\relax
\@@setdynamicframe{\@colN}{#1}}

```

`\setdynamicframe` Change the settings for specified **dynamic frames**:

```

\newcommand*\setdynamicframe}{%
\ifstar\@ssetdynamicframe\setdynamicframe}

```

`\@ssetdynamicframe` Starred version: iterate through comma-separated list of labels.

```

\newcommand*\@ssetdynamicframe}[2]{%
\@for\@ff@id:=#1\do{%
\@dynamicframeid{\@ff@id}%
\@@setdynamicframe{\@ff@id}{#2}}}

```

`\@setdynamicframe` Unstarred version: iterate through comma-separated list of ID numbers. Include provision for number ranges. If necessary, modify number ranges to ensure they are valid.

```

\newcommand*\@setdynamicframe}[2]{%
\ifthenelse{\equal{#1}{all}}{%
\setalldynamicframes{#2}}{%
\ifthenelse{\equal{#1}{odd} \TE@or \equal{#1}{even}}{%
\ifthenelse{\equal{#1}{odd}}{\@colN=1}{\@colN=2}%
\whiledo{\@colN<\c@maxdynamic\TE@or\@colN=\c@maxdynamic}{%
\@@setdynamicframe{\@colN}{#2}%
\advance\@colN by 2\relax}%
}%}
\@for\@ff@id:=#1\do{%
\def\@ff@numstart{0}\def\@ff@numend{10000}%
\@ff@getrange{\@ff@id}%
\ifnum\@ff@numstart=0\relax
\def\@ff@numstart{1}%
\fi
\ifnum\@ff@numend>\c@maxdynamic
\def\@ff@numend{\c@maxdynamic}%
\fi
\@colN=\@ff@numstart
\whiledo{\@colN<\@ff@numend \TE@or \@colN=\@ff@numend}{%
\@@setdynamicframe{\@colN}{#2}%
\advance\@colN by 1\relax
}}}}

```

\@@setdynamicframe Change the setting for the **dynamic frame** given by its IDN.

```

\newcommand*{\@@setdynamicframe}[2]{%
\expandafter\expandafter\expandafter
\@ff@getstaticpos\csname @df@dim@\romannumeral#1\endcsname
\def\ff@frame{}\edef\ff@width{\the\@ff@tmp@x}%
\edef\ff@height{\the\@ff@tmp@y}\def\ff@style{}\def\ff@frametype{%
\def\ff@x{}\def\ff@y{}\def\ff@col{}\def\ff@txtcol{}\def\ff@backcol}%
\def\ff@clear{}\def\ff@margin{}\def\ff@offset{}\def\ff@pages{%
\def\ff@label{}\def\ff@evenx{}\def\ff@eveny}%
\def\ff@oddx{}\def\ff@oddy{}\def\ff@angle{}\def\ff@shape{0}%
\setkeys{flowframe}{#2}%
\ifthenelse{\equal{\ff@frame}{}}{}{%
\setboolean{dynamicframe\romannumeral#1}{\ff@frame}}%
\ifthenelse{\equal{\ff@x}{}}{}{%
\expandafter\global\expandafter\setlength
\csname @df@\romannumeral#1@posx\endcsname{\ff@x}%
\expandafter\global\expandafter\setlength
\csname @df@\romannumeral#1@evenx\endcsname{\ff@x}}%
\ifthenelse{\equal{\ff@y}{}}{}{%
\expandafter\global\expandafter\setlength
\csname @df@\romannumeral#1@posy\endcsname{\ff@y}%
\expandafter\global\expandafter\setlength
\csname @df@\romannumeral#1@eveny\endcsname{\ff@y}}%
\ifthenelse{\equal{\ff@evenx}{}}{}{%
\expandafter\global\expandafter\setlength
\csname @df@\romannumeral#1@evenx\endcsname{\ff@evenx}}%
\ifthenelse{\equal{\ff@eveny}{}}{}{%
\expandafter\global\expandafter\setlength
\csname @df@\romannumeral#1@eveny\endcsname{\ff@eveny}}%
\ifthenelse{\equal{\ff@oddx}{}}{}{%
\expandafter\global\expandafter\setlength
\csname @df@\romannumeral#1@posx\endcsname{\ff@oddx}}%
\ifthenelse{\equal{\ff@oddy}{}}{}{%
\expandafter\global\expandafter\setlength
\csname @df@\romannumeral#1@posy\endcsname{\ff@oddy}}%
\expandafter\xdef\csname @df@dim@\romannumeral#1\endcsname{%
[c][\ff@height][\ff@valign]{\ff@width}}%
\ifthenelse{\equal{\ff@label}{}}{}{%
\@s@tdynamicframeid{#1}[\ff@label]}
\ifthenelse{\equal{\ff@frametype}{}}{}{%
\expandafter
\xdef\csname @df@frametype@\romannumeral#1\endcsname{%
\ff@frametype}}%
\ifthenelse{\equal{\ff@col}{}}{}{%
\expandafter\@setframecol\ff@col\end{#1}{col}{df}}%
\ifthenelse{\equal{\ff@txtcol}{}}{}{%
\expandafter\@setframecol\ff@txtcol\end{#1}{txtcol}{df}}%
\ifthenelse{\equal{\ff@backcol}{}}{}{%
\expandafter\@setframecol\ff@backcol\end{#1}{backcol}{df}}%
\ifthenelse{\equal{\ff@offset}{}}{}{%
\expandafter
\xdef\csname @df@offset@\romannumeral#1\endcsname{\ff@offset}}%
\ifthenelse{\equal{\ff@angle}{}}{}{%
\expandafter

```

```

\edef\csname @df@angle@\romannumeral#1\endcsname{\ff@angle}}%
\if0\ff@shape
\else
\expandafter\global\expandafter
\let\csname @df@shape@\romannumeral#1\endcsname\ff@shape
\fi
\ifthenelse{\equal{\ff@pages}{}}{}{}{%
\expandafter\edef\csname @df@pages@\romannumeral#1\endcsname{%
\ff@pages}}%
\ifthenelse{\equal{\ff@style}{}}{}{}{%
\@ifundefined{\ff@style}{\PackageError{flowfram}%
{Unknown style '\ff@style'}{The command \expandafter
\string\csname\ff@style\endcsname\space has not been defined}}{}%
\expandafter
\edef\csname @df@style@\romannumeral#1\endcsname{\ff@style}}}%
\ifthenelse{\equal{\ff@clear}{}}{}{}{%
\setboolean{@df@clear@\romannumeral#1\c@maxdynamic}{true}}%
}%
\ifthenelse{\equal{\ff@margin}{}}{}{}{%
\PackageError{flowfram}{Key 'margin' not available for dynamic
frames}{dynamic frames don't have marginal notes}}%
}

```

`\@@dynamicframeswapcoords` Swap odd and even offsets for a given **static frame**. Do the main stuff for a given **static frame IDN**.

```

\newcommand*{\@@dynamicframeswapcoords}[1]{%
\setlength{\@ff@tmp@x}{%
\csname @df@\romannumeral#1@evenx\endcsname}%
\expandafter\setlength
\csname @df@\romannumeral#1@evenx\endcsname
{\csname @df@\romannumeral#1@posx\endcsname}%
\expandafter\setlength
\csname @df@\romannumeral#1@posx\endcsname{\@ff@tmp@x}%
\setlength{\@ff@tmp@y}{%
\csname @df@\romannumeral#1@eveny\endcsname}%
\expandafter\setlength
\csname @df@\romannumeral#1@eveny\endcsname
{\csname @df@\romannumeral#1@posy\endcsname}%
\expandafter\setlength\csname @df@\romannumeral#1@posy\endcsname
{\@ff@tmp@y}%
}

```

`\dfswapoddeven` Allow user to specify **flow frame** either by **IDN** or **IDL**:

```

\newcommand*{\dfswapoddeven}{%
\ifstar\@sdynamicframeswapcoords\@dynamicframeswapcoords}

```

`\@sdynamicframeswapcoords` Starred form

```

\newcommand*{\@sdynamicframeswapcoords}[1]{%
\@for\@ff@id:=#1\do{%
\@dynamicframeid{\@ff@id}%
\@dynamicframeswapcoords{\ff@id}}}

```

`\@dynamicframeswapcoords` Unstarred form:

```

\newcommand*{\@dynamicframeswapcoords}[1]{%
\ifthenelse{\equal{#1}{all}}{%
\ff@id=0\relax
\whiledo{\ff@id<\c@maxflow}{\advance\ff@id by 1\relax
\@dynamicframeswapcoords{\ff@id}}%
}{%
\ifthenelse{\equal{#1}{odd} \TE@or \equal{#1}{even}}{%
\ifthenelse{\equal{#1}{odd}}{\@colN=1}{\@colN=2}%
\whiledo{\@colN<\c@maxflow\TE@or \@colN=\c@maxflow}{%
\@dynamicframeswapcoords{\@colN}%
\advance\@colN by 2\relax}%
}{%
\@for\@ff@id:=#1\do{%
\def\@ff@numstart{0}\def\@ff@numend{10000}%
\@ff@getrange{\@ff@id}%
\ifnum\@ff@numstart=0\relax
\def\@ff@numstart{1}%
\fi
\ifnum\@ff@numend>\c@maxflow
\def\@ff@numend{\c@maxflow}%
\fi
\@colN=\@ff@numstart
\whiledo{\@colN<\@ff@numend \TE@or \@colN=\@ff@numend}{%
\@dynamicframeswapcoords{\@colN}%
\advance\@colN by 1\relax
}}}}

```

Set the contents of a **dynamic frame**.

dynamiccontents Syntax: `\begin{dynamiccontents}⟨idn⟩`

The contents of the `dynamiccontents` environment needs to be stored in the control sequence `\@dynamicframe@⟨rn⟩` (where `⟨rn⟩` is the `⟨idn⟩` as a roman numeral.) Start of the environment (unstarred):

```

\def\dynamiccontents#1{%
\edef\@flf@{\@currenvir}%
\def\@flf@idn{#1}%
\toks@{\@flf@get@body
}

```

Get the body of the environment:

```

\long\def\@flf@get@body#1\end
{\toks@\expandafter{\the\toks@#1}\@flf@find@end}

```

Find the end of the environment:

```

\def\@flf@find@end#1{%
\def\@tempa{#1}%
\ifx\@tempa\@flf@
\expandafter\@flf@enddynamiccontents
\else
\toks@\expandafter
{\the\toks@\end{#1}}\expandafter\@flf@get@body\fi
}

```

End of the environment:

```

\let\enddynamiccontents\relax

```

```

\def\@flf@enddynamiccontents{%
\ifnum\@flf@idn>\c@maxdynamic
\PackageError{flowfram}{Dynamic frame \number\@flf@idn\ does not exist}{%
You have specified dynamic frame number \number\@flf@idn, but there are
only \number\c@maxdynamic\space dynamic frames currently defined}%
\else
\expandafter
\xdef\csname @dynamicframe@\romannumeral\@flf@idn\endcsname{\the\toks@}%
\expandafter
\fi
\expandafter\end\expandafter{\@flf@}}

```

`dynamiccontents*` Starred version:

```

\expandafter\def\csname dynamiccontents*\endcsname#1{%
\edef\@flf@{\@currentvir}%
\@dynamicframeid{#1}%
\edef\@flf@idn{\number\ff@id}%
\toks@{\}\@flf@get@body
}

```

`\setdynamiccontents`

```

\newcommand{\setdynamiccontents}{%
\ifstar\@ssetdynamiccontents\setdynamiccontents}

```

`\@ssetdynamiccontents` Starred version: identify **dynamic frame** by its **IDL**:

```

\newcommand{\@ssetdynamiccontents}[2]{%
\@dynamicframeid{#1}\setdynamiccontents{\ff@id}{#2}}

```

`\@setdynamiccontents` Unstarred version: identify **dynamic frame** by its **IDN**:

```

\newcommand{\@setdynamiccontents}[2]{%
\ifnum#1>\c@maxdynamic
\PackageError{flowfram}{Dynamic frame \number#1\ does not exist}{%
You have specified dynamic frame number \number#1, but there are
only \number\c@maxdynamic\space dynamic frames currently defined}%
\else
\expandafter
\gdef\csname @dynamicframe@\romannumeral#1\endcsname{#2}%
\fi}

```

`\appenddynamiccontents` Append information to **dynamic frame**. First check to see if starred or unstarred version is being used.

```

\newcommand{\appenddynamiccontents}{%
\ifstar\@sappenddynamic\appenddynamic}

```

`\@sappenddynamic` Starred version: find the **IDN** and pass it to the unstarred version.

```

\newcommand{\@sappenddynamic}[2]{%
\@dynamicframeid{#1}\@appenddynamic{\ff@id}{#2}}

```

`\@appenddynamic` Unstarred version.

```

\newcommand{\@appenddynamic}[2]{%
\ifnum#1>\c@maxdynamic
\PackageError{flowfram}{Dynamic frame \number#1 does not exist}{%
You have specified dynamic frame number \number#1,

```

```

but there are only
\number\c@maxdynamic\space dynamic frames currently defined}%
\else
\expandafter\@ff@addtolist
\csname @dynamicframe@\romannumeral#1\endcsname\entry{#2}%
\fi}

\@ff@addtolist Append #2 onto the end of #1.
\newtoks\flf@ta \newtoks\flf@tb
\long\def\@ff@addtolist#1\entry#2{\flf@ta={#2}}%
\flf@tb=\expandafter{#1}%
\xdef#1{\the\flf@tb\the\flf@ta}}

```

1.5 Determining Dimensions and Locations

```

\computeleftedgeodd Compute the position of the left most edge of the page, relative to the left
side of the typeblock. Since odd and even pages may have a different offset if
\oddsidemargin and \evensidemargin have different values, it is necessary to
have two separate commands for odd and even pages. First the odd pages.
\newcommand*\computeleftedgeodd[1]{%
\setlength{#1}{-1in}%
\addtolength{#1}{-\hoffset}%
\addtolength{#1}{-\oddsidemargin}}

\computeleftedgeeven Now for the even pages
\newcommand*\computeleftedgeeven[1]{%
\setlength{#1}{-1in}%
\addtolength{#1}{-\hoffset}%
\addtolength{#1}{-\evensidemargin}}

\computetopedge Compute the top edge of the page, relative to the bottom of the typeblock.
\newcommand*\computetopedge[1]{%
\setlength{#1}{\textheight}%
\addtolength{#1}{\headheight}%
\addtolength{#1}{\headsep}%
\addtolength{#1}{1in}%
\addtolength{#1}{\voffset}%
\addtolength{#1}{\topmargin}}

\computebottomedge Compute the bottom edge of the page, relative to the bottom of the typeblock.
\newcommand*\computebottomedge[1]{%
\computetopedge{#1}%
\addtolength{#1}{-\paperheight}}

\computerightedgeodd Compute the right edge of the page, relative to the left edge of the typeblock.
Again, two commands are needed for odd and even pages. First the odd pages.
\newcommand*\computerightedgeodd[1]{%
\computeleftedgeodd{#1}%
\addtolength{#1}{\paperwidth}}

\computerightedgeeven Now for the even pages.
\newcommand*\computerightedgeeven[1]{%
\computeleftedgeeven{#1}%
\addtolength{#1}{\paperwidth}}

```

Compute the minimum area surrounding the listed **flow frames**. Values stored in `\ffareawidth`, `\ffareaheight`, `\ffareax` and `\ffareay`

```
\newlength\ffareawidth
\newlength\ffareaheight
\newlength\ffareax
\newlength\ffareay
```

`\computeffareax` Starred version identifies frame by **IDL**, unstarred version identifies frame by **IDN**.

```
\newcommand*\computeffareax{%
\ifstar\@computeffareax\@computeffareax}
```

`\@computeffareax` Starred version.

```
\newcommand*\@computeffareax[1]{%
\setlength{\ffareax}{\paperwidth}%
\setlength{\ffareay}{\paperheight}%
\setlength{\@ff@tmp@x}{0pt}%
\setlength{\@ff@tmp@y}{0pt}%
\@for\@ff@id:=#1\do{\@flowframeid{\@ff@id}%
%\ff@id is the IDN
\ifnum\ffareax>\flowframex{\ff@id}%
\setlength{\ffareax}{\flowframex{\ff@id}}%
\fi
\ifnum\ffareay>\flowframey{\ff@id}%
\setlength{\ffareay}{\flowframey{\ff@id}}%
\fi
\setlength{\@ff@offset}{\flowframex{\ff@id}}%
\addtolength{\@ff@offset}{\flowframewidth{\ff@id}}%
\ifnum\@ff@tmp@x<\@ff@offset
\setlength{\@ff@tmp@x}{\@ff@offset}%
\fi
\setlength{\@ff@offset}{\flowframey{\ff@id}}%
\addtolength{\@ff@offset}{\flowframeheight{\ff@id}}%
\ifnum\@ff@tmp@y<\@ff@offset
\setlength{\@ff@tmp@y}{\@ff@offset}%
\fi
}%
\setlength{\ffareawidth}{\@ff@tmp@x}%
\addtolength{\ffareawidth}{-\ffareax}%
\setlength{\ffareaheight}{\@ff@tmp@y}%
\addtolength{\ffareaheight}{-\ffareay}}
```

`\@computeffareax` Unstarred version.

```
\newcommand*\@computeffareax[1]{%
\setlength{\ffareax}{\paperwidth}%
\setlength{\ffareay}{\paperheight}%
\setlength{\@ff@tmp@x}{0pt}%
\setlength{\@ff@tmp@y}{0pt}%
\@for\@ff@id:=#1\do{%
\ff@id=\@ff@id\relax
\setlength{\@ff@offset}{\flowframex{\ff@id}}%
\ifdim\ffareax>\@ff@offset
\setlength{\ffareax}{\@ff@offset}%
\fi
}
```

```

\setlength{\@ff@offset}{\flowframey{\ff@id}}%
\ifdim\ffareay>\@ff@offset
\setlength{\ffareay}{\@ff@offset}%
\fi
\setlength{\@ff@offset}{\flowframex{\ff@id}}%
\addtolength{\@ff@offset}{\flowframewidth{\ff@id}}%
\ifdim\@ff@tmp@x<\@ff@offset
\setlength{\@ff@tmp@x}{\@ff@offset}%
\fi
\setlength{\@ff@offset}{\flowframey{\ff@id}}%
\addtolength{\@ff@offset}{\flowframeheight{\ff@id}}%
\ifdim\@ff@tmp@y<\@ff@offset
\setlength{\@ff@tmp@y}{\@ff@offset}%
\fi
}%
\setlength{\ffareawidth}{\@ff@tmp@x}%
\addtolength{\ffareawidth}{-\ffareax}%
\setlength{\ffareaheight}{\@ff@tmp@y}%
\addtolength{\ffareaheight}{-\ffareay}}

\@ff@swaplen Swap the values of two lengths
\newcommand*\@ff@swaplen[2]{%
\setlength{\@ff@tmp@x}{#1}%
\setlength{#1}{#2}%
\setlength{#2}{\@ff@tmp@x}}

\@ff@getdim Get the dimensions for the given type of frame. The first parameter should be a
number indicating type of frame : 1 (flow), 2 (static), 3 (dynamic). The second
number is its IDN. Values are stored in \ffareax, \ffareay, \ffareawidth and
\ffareaheight.
\newcommand*\@ff@getdim[2]{%
\ifnum#2<1\relax
\PackageError{flowfram}{Frame IDNs start from 1}{%
You have specified a frame IDN of '\number#2'}%
\fi
\ifcase#1
\PackageError{flowfram}{Unknown frame ID type '#1'}{%
Frame ID types are: 1 (flow), 2 (static) and 3 (dynamic)}
\or
\ifnum#2>\c@maxflow
\PackageError{flowfram}{Invalid flow frame IDN '\number#2'}{%
Flow frame IDNs go from 1 to \number\c@maxflow}
\else
\setlength{\ffareax}{\flowframex{#2}}
\setlength{\ffareay}{\flowframey{#2}}
\setlength{\ffareawidth}{\flowframewidth{#2}}
\setlength{\ffareaheight}{\flowframeheight{#2}}
\fi
\or
\ifnum#2>\c@maxstatic
\PackageError{flowfram}{Invalid static frame IDN '\number#2'}{%
Static frame IDNs go from 1 to \number\c@maxstatic}
\else
\setlength{\ffareax}{\staticframex{#2}}

```

```

\setlength{\ffareay}{\staticframey{#2}}
\expandafter\expandafter\expandafter
\@ff@getstaticpos
\csname @sf@dim@\romannumeral#2\endcsname
\setlength{\ffareawidth}{\@ff@tmp@x}%
\setlength{\ffareaheight}{\@ff@tmp@y}%
\fi
\or
\ifnum#2>\c@maxdynamic
\PackageError{flowfram}{Invalid dynamic frame IDN '\number#2'}{%
Dynamic frame IDNs go from 1 to \number\c@maxdynamic}
\else
\setlength{\ffareax}{\dynamicframex{#2}}
\setlength{\ffareay}{\dynamicframey{#2}}
\expandafter\expandafter\expandafter
\@ff@getstaticpos
\csname @df@dim@\romannumeral#2\endcsname
\setlength{\ffareawidth}{\@ff@tmp@x}%
\setlength{\ffareaheight}{\@ff@tmp@y}%
\fi
\else
\PackageError{flowfram}{Unknown frame ID type '#1'}{%
Frame ID types are: 1 (flow), 2 (static) and 3 (dynamic)}
\fi
}

```

`\getstaticbounds` Convenience method for calling the above. Firstly for static frames:

```

\newcommand*\getstaticbounds{%
\ifstar\sgetstaticbounds\getstaticbounds}

```

`\sgetstaticbounds` Starred version (specify by **IDL**):

```

\newcommand*\sgetstaticbounds[1]{%
\staticframeid{#1}\getstaticbounds{\ff@id}}

```

`\getstaticbounds` Unstarred version (specify by **IDN**):

```

\newcommand*\getstaticbounds[1]{\@ff@getdim{1}{#1}}

```

`\getflowbounds` Next flow frames:

```

\newcommand*\getflowbounds{%
\ifstar\sgetflowbounds\getflowbounds}

```

`\sgetflowbounds` Starred version (specify by **IDL**):

```

\newcommand*\sgetflowbounds[1]{%
\flowframeid{#1}\getflowbounds{\ff@id}}

```

`\getflowbounds` Unstarred version (specify by **IDN**):

```

\newcommand*\getflowbounds[1]{\@ff@getdim{2}{#1}}

```

`\getdynamicbounds` Next dynamic frames:

```

\newcommand*\getdynamicbounds{%
\ifstar\sgetdynamicbounds\getdynamicbounds}

```

`\@sgetdynamicbounds` Starred version (specify by **IDL**):
`\newcommand*{\@sgetdynamicbounds}[1]{%`
`\@dynamicframeid{#1}\@getdynamicbounds{\ff@id}}`

`\@getdynamicbounds` Unstarred version (specify by **IDN**):
`\newcommand*{\@getdynamicbounds}[1]{\@ff@getdim{3}{#1}}`

1.6 Initialise Flow Frames

`\setinitialframe` Specify initial frame. This should be the first flow frame that is defined on the first page of the document. Having another **flow frame** as the initial frame is not a good idea, and may have unexpected results.

```
\newcommand*{\setinitialframe}[1]{\c@thisframe=#1%
\global\usedframebreaktrue
\global\setlength{\hsize}{%
\c@thisframe\romannumeral\c@thisframe\endcsname}}
```

`\setframes` Set the initial frame.

```
\newif\if@setfr@mes
\@setfr@mesfalse
\newcommand*{\setframes}{%
\ifnum\c@thisframe=0\relax
\PackageWarning{flowfram}{Can't find a flow frame on page 1.
\MessageBreak
Attempting to find the first page with a flow frame}%
\@nxtcol=1\relax
\c@curpg=1\relax
\@g@tnextcol{\@nxtcol}%
shipout pages without flow frames
\advance\c@curpg by -1\relax
\whiledo{\c@curpg>0}{\advance\c@curpg by -1\relax
\setbox\@outputbox\vbox{\hbox to \textwidth{\@ff@do@allframes}}}%
\@outputpage}%
\c@thisframe=\@nxtcol
\fi
\@setcol{\c@thisframe}\relax
\@setfr@mestrue
\edef\ff@txtcol{%
\c@thisframe\romannumeral\c@thisframe\endcsname}%
\@s@tffttextcol
}
```

`\emulatetwocolumn` Emulate original `\twocolumn` declaration. This is provided for backward compatibility, and may be removed in later versions.

```
\newcommand{\emulatetwocolumn}[1][0]{%
\finishthispage
\setallflowframes{pages=none}%
\settoheight{\@ff@staticH}{#1}%
\settodepth{\@ff@tmp@y}{#1}%
\addtolength{\@ff@staticH}{\@ff@tmp@y}%
\ifdim\@ff@staticH>0pt\relax
\twocolumnStop[\c@page]{\@ff@staticH}%
}
```

```

\c@thisframe=\c@maxflow
\advance\c@thisframe by -1\relax
\@twocolumn[>\c@page]%
\setstaticcontents{\c@maxstatic}{#1}%
\else
\@twocolumn
\c@thisframe=\c@maxflow
\advance\c@thisframe by -1\relax
\fi
\@setcol{\c@thisframe}\relax
}

```

`\emulateonecolumn` Emulate original `\onecolumn` declaration. This is provided for backward compatibility, and may be removed in later versions.

```

\newcommand{\emulateonecolumn}[1][]{%
\finishthispage
\setallflowframes{pages=none}%
\settoheight{\@ff@staticH}{#1}%
\settodepth{\@ff@tmp@y}{#1}%
\addtolength{\@ff@staticH}{\@ff@tmp@y}%
\ifdim\@ff@staticH>0pt\relax
\onecolumnStop[\c@page]{\@ff@staticH}%
\c@thisframe=\c@maxflow
\advance\c@thisframe by -1\relax
\@onecolumn[>\c@page]%
\setstaticcontents{\c@maxstatic}{#1}%
\else
\@twocolumn
\c@thisframe=\c@maxflow
\advance\c@thisframe by -1\relax
\fi
\@setcol{\c@thisframe}\relax
}

```

If no flow frames have been defined, create one big one the size of the `typeblock`, and initialise the frames.

```

\AtBeginDocument{%
\ifnum\c@maxflow=0\relax
\PackageWarning{flowfram}{No flow frames, adding one}%
\@onecolumn
\fi
\setframes
\renewcommand{\onecolumn}[1][]{\PackageWarning{flowfram}{%
Ignoring \string\onecolumn\space found in document environment.
Frames must be defined in the preamble}#1}%
\renewcommand{\twocolumn}[1][]{\PackageWarning{flowfram}{%
Ignoring \string\twocolumn\space found in document environment.
Frames must be defined in the preamble}#1}%
}

```

If the document finishes before the last frame on the last page, need to finish off to ensure the final page is shipped out, otherwise the text on the last page will be lost.

```

%\AtEndDocument{\finishthispage}

```

1.7 Output Routine

`\@setcol` Set up the output box so it has the correct dimensions for specified **flow frame**. This is used by the output routine.

```
\newcommand{\@setcol}[1]{%
\ifnum\c@maxflow<#1\relax
\PackageError{flowfram}{Can't set frame '\number#1', doesn't
exist}{}%
\else
\expandafter\global\expandafter\columnwidth
\csname colwidth\romannumeral#1\endcsname
\ifdim\hsize=\columnwidth
\else
\ifusedframebreak
\else
\PackageWarning{flowfram}{Moving to flow frame of unequal
width,\MessageBreak use of \string\framebreak\space advised,
or text might not appear correctly}%
\fi
\fi
\global\usedframebreakfalse
\global\hsize\columnwidth
\expandafter\global
\expandafter\vsizel\csname colheight\romannumeral#1\endcsname
\global\@colht\vsizel
\global\@colroom\@colht
\global\linewidth\columnwidth
\setmargin
\fi
}
```

Modify the output routine so that it uses `\vsizel` instead of `\textheight`.

```
\output={\let\par\@par
\ifnum\outputpenalty <-\@M
\@specialoutput
\else
\@makecol
\@opcol \@startcolumn
\@whilesw \if@fcolmade \fi {\@opcol \@startcolumn }%
\fi
\ifnum\outputpenalty>-\@Miv
\ifdim\@colroom<1.5\baselineskip
\ifdim\@colroom<\vsizel
\@latex@warning@no@line{Text page \thepage \space
contains only floats}\@emptycol
\else
\global\vsizel\@colroom
\fi
\else
\global\vsizel\@colroom
\fi
\else
\global\vsizel\maxdimen
\fi
}
```

}

`\@doclearpage` Modify `\@doclearpage`, again replace `\textheight` with `\vsize`, and only use the twocolumn stuff.

```
\def\@doclearpage{%
\ifvoid\footins
\setbox\@tempboxa\vsplit\@cclv to\z@
\unvbox\@tempboxa
\setbox\@tempboxa\box\@cclv
\xdef\@deferlist{\@toplist\@botlist\@deferlist}%
\global\let\@toplist\@empty
\global\let\@botlist\@empty
\global\@colroom\@colht
\ifx\@currlist\@empty
\else
\@latexerr{Float(s) lost}\@ehb
\global\let\@currlist\@empty
\fi
\@makefcolumn
\@deferlist
\@whilesw \if@fcolmade \fi {\@opcol
\@makefcolumn
\@deferlist}%
\if@firstcolumn
\xdef\@dbldeferlist{\@dbltoplist\@dbldeferlist}%
\global\let\@dbltoplist\@empty
\global\@colht\vsize
\beginingroup
\@dblfloatplacement
\@makefcolumn
\@dbldeferlist
\@whilesw \if@fcolmade \fi {\@outputpage
\@makefcolumn\@dbldeferlist}%
\endgroup
\else
\vbox{}\clearpage
\fi
\else
\setbox\@cclv\vbox{\box\@cclv\vfil}%
\@makecol\@opcol\clearpage\fi}
```

Modify `\@outputpage` slightly. Add provision for turning headers and footers into **dynamic frames**.

`\@dothehead` First define macro to do the header. This will be modified if it is turned into a **dynamic frame**.

```
\newcommand{\@dothehead}{\vbox to \headheight{%
\color@hbox\normalcolor\hbox to \textwidth{%
\@thehead}\color@endbox}}
```

`\@dothefoot` Same again for the footer.

```
\newcommand{\@dothefoot}{%
\color@hbox\normalcolor\hbox to \textwidth{%
\@thefoot}\color@endbox}
```

```
\newcommand{\@dodynamicthehead}{%}
\newcommand{\@dodynamicthefoot}{%}
```

\@outputpage Now for the modified version of \@outputpage. The page style stuff has been moved to \@outputdblcol so that the headers and footers can be set in **dynamic frames** before the **dynamic frames** are put on the page.

```
\def\@outputpage{%
\begingroup
\let\protect\noexpand
\@resetactivechars
\global\let\@if@newlist@if@newlist
\global\@newlistfalse\@parboxrestore
\shipout\vbox{\set@typeset@protect
\aftergroup
\endgroup
\aftergroup
\set@typeset@protect
\reset@font\normalsize\normalsfcodes
\let\label\@gobble
\let\index\@gobble
\let\glossary\@gobble
\baselineskip\z@skip
\lineskip\z@skip
\lineskiplimit\z@
\vskip\topmargin\moveright\@themargin
\vbox{%
\vskip\headheight
\vskip\headsep
\box\@outputbox
}}\global\let@if@newlist\@if@newlist
\stepcounter{page}\let\firstmark\botmark}
```

\makedfheaderfooter Make the headers and footers be in **dynamic frames**. There will initially be no difference in appearance until the settings are changed using \setdynamicframe. The header frame is given the **IDL header**, and the footer is given the **IDL footer**.

```
\newcommand*\makedfheaderfooter{%
% create dynamic frames at the standard location
\setlength{\@ff@tmp@y}{\textheight}%
\addtolength{\@ff@tmp@y}{\headsep}%
\newdynamicframe{\textwidth}{\headheight}{0pt}{\@ff@tmp@y}[header]%
\newdynamicframe{\textwidth}{\headheight}{0pt}{-\footskip}[footer]%
\renewcommand{\@dothehead}{%}
\renewcommand{\@dothefoot}{%}
\renewcommand{\@dodynamicthehead}{%
\@dynamicframeid{header}%
\expandafter
\def\csname @dynamicframe@romannumeral\ff@id\endcsname{%
\vfill\@thehead\vfill}%
}%
\renewcommand{\@dodynamicthefoot}{%
\@dynamicframeid{footer}%
\expandafter
\def\csname @dynamicframe@romannumeral\ff@id\endcsname{%
\vfill\@thefoot\vfill}%
}
```

```
}%
}
```

This should only be done in the preamble.

```
\@onlypreamble{\makedfheaderfooter}
```

`\footnotecolor` Set footnotes in `\footnotecolor` rather than `\normalcolor` This ensures that the footnotes appear in the same colour as the text colour for the **flow frame** to which they belong.

```
\newcommand{\footnotecolor}{%
\@ifundefined{ff@txtcol@romannumeral@c@thisframe}{%
\normalcolor}{%
\edef\ff@txtcol{%
\csname @ff@txtcol@romannumeral@c@thisframe\endcsname}%
\@s@tffttextcol}}
```

`\@makecol` Modify `\@makecol` so that the footnotes, and the footnote rule are in the colour for that frame.

```
\renewcommand{\@makecol}{%
\ifvoid\footins
\setbox\@outputbox\box\@cclv
\else
\setbox\@outputbox\vbox{%
\boxmaxdepth\@maxdepth\@tempdima\dp\@cclv
\unvbox\@cclv
\vskip\skip\footins
\color@begingroup
\footnotecolor
\footnoterule
\unvbox\footins
\color@endgroup
}\fi
\xdef\@freelist{\@freelist \@midlist }%
\global\let\@midlist\@empty
\@combinefloats
\ifvbox\@kludgeins
\@makespecialcolbox
\else
\setbox\@outputbox\vbox to\@colht{%
\@texttop\dimen@\dp\@outputbox
\unvbox \@outputbox
\vskip -\dimen@\@textbottom
}\fi
\global\maxdepth\@maxdepth}
```

`\@opcol` Modify `\@opcol`, as `\if@twocolumn` is now irrelevant.

```
\def\@opcol{\@outputdblcol
\global\@mparbottom\z@
\global\@textfloatsheight\z@
\@floatplacement
}
```

`\@ff@checkifmoreframes` Check to see if there are more **flow frames** defined, and set `\if@ff@moreframes` as appropriate. This involves iterating through all **flow frames**, and through each frame's **page list**.

```
\newif\if@ff@moreframes
\newcommand*{\@ff@checkifmoreframes}{%
\@ff@moreframesfalse
\@colN=\c@thisframe
\whiledo{\@colN<\c@maxflow}{%
\advance\@colN by 1\relax
\edef\ff@pages{\csname @ff@pages@\romannumeral\@colN\endcsname}%
\@ff@checkpages{\ff@pages}%
}%
\if@ff@moreframes
\else
\@ff@tmpN=\c@page
\advance\@ff@tmpN by 1\relax
\@colN=0\relax
\whiledo{\@colN<\c@thisframe}{%
\advance\@colN by 1\relax
\edef\ff@pages{\csname @ff@pages@\romannumeral\@colN\endcsname}%
\@ff@checkpages[\@ff@tmpN]{\ff@pages}%
}%
\fi
}
```

`\@ff@checkpages` Check to see if the current page lies in the **page list** given by #1.

```
\newcommand*{\@ff@checkpages}[2][\c@page]{%
\@for\@ff@pp:=#2\do{%
\@ff@checkthispage{#1}{\@ff@pp}}}
```

`\@ff@checkthispage` Check to see if the current page lies in the **page range** given by #1. If the **page range** is specified by **all**, **odd** or **even** then there are definitely more frames available, otherwise check to see if the current page lies within the number range. If the **page range** is **none**, ignore it.

```
\newcommand*{\@ff@checkthispage}[2]{%
\ifthenelse{equal{#2}{all}\or\equal{#2}{even}\or\equal{#2}{odd}}{%
\@ff@moreframestrue}{%
\ifthenelse{equal{#2}{none}}{}{%
\@ff@checknumrange{#1}{#2}}}
```

`\@ff@checknumrange` The number range could be a single number, a closed range (e.g. 2-6) or an open range (e.g. <4 or >10). Use `\@ff@getrange` to find the start and end ranges. For open ended ranges assume a maximum value of 10000. If the current page is less than or equal to the maximum, there are still more **flow frames** available.

```
\newcommand*{\@ff@checknumrange}[2]{%
\def\@ff@numstart{0}\def\@ff@numend{10000}%
\@ff@getrange{#2}%
\ifnum\@ff@numend>#1\relax
\@ff@moreframestrue
\else
\ifnum\@ff@numend=#1\relax
\@ff@moreframestrue
\fi
}
```

```
\fi
}
```

Work out the minimum and maximum values of a number range which could either be a single number, a closed number range or an open number range. If the first character is < or > then it is an open range, otherwise it is a closed range or a single number. Define a counter to use whilst determining the range.

```
\newcount\c@ffrangenum
```

`\@ff@getrange` Now to find out what kind of range it is. If it is a single number, e.g. 24, then it will do, e.g. `\@ff@getrange24-\relax`. If it is a closed range, e.g. 30-40, it will do, e.g. `\@ff@getrange30-40-\relax`. If it is an open range, e.g. >25, it will do, e.g. `\@ff@getrange>25-\relax`.

```
\newcommand*\@ff@getrange}[1]{%
\expandafter\@ff@getrange#1-\relax\end{}
```

`\@ff@getrange` The ranges can now be picked out. If the first character is a < or > it is an open ended range, otherwise it is either a single value, or a close ended range.

```
\def\@ff@getrange#1#2\end{%
\ifx#1<\relax
\@ff@getrangeless#1#2\end
\else
\ifx#1>\relax
\@ff@getrangegreater#1#2\end
\else
\@ff@getrange#1#2\end
\fi
\fi
}
```

`\@ff@getrangeless` Get the values for an open ended range with an upper bound. A minimum value of 0 is assumed.

```
\def\@ff@getrangeless<#1-\relax\end{%
\c@ffrangenum=#1\relax
\advance\c@ffrangenum by -1\relax
\def\@ff@numstart{0}%
\edef\@ff@numend{\number\c@ffrangenum}}
```

`\@ff@getrangegreater` Get the values for an open ended range with a lower bound. A maximum value of 10000 is assumed.

```
\def\@ff@getrangegreater>#1-\relax\end{%
\c@ffrangenum=#1\relax
\advance\c@ffrangenum by 1\relax
\edef\@ff@numstart{\number\c@ffrangenum}%
\def\@ff@numend{10000}}
```

`\@ff@getrange` Determine whether we have a single number or a closed range. If #2 is `\relax`, it is a single value, otherwise it is a range.

```
\def\@ff@getrange#1-#2\end{%
\ifx\relax#2\relax
\def\@ff@numstart{#1}\def\@ff@numend{#1}%
\else
```

```

\def\@ff@numstart{#1}%
\@@@ff@getrange#2\end
\fi
}

\@@@ff@getrange Extract the end value from the closed range.
\def\@@@ff@getrange#1-\relax\end{%
\def\@ff@numend{#1}}

\@g@tnextcol Find the next flow frame. If there are no more flow frames, define a new one the
size of the typeblock. (Otherwise the remaining document text will be lost.)
\newif\if@notthiscol
\newif\if@ff@nwpg
\newcount\c@curpg
\newcommand*\@g@tnextcol}[1]{%
\@ff@checkifmoreframes
\if@ff@moreframes
\else
% No more frames, add new frame
\PackageWarning{flowfram}{Run out of flows frames,
adding new one}%
\@onecolumn
#1=\c@maxflow
\fi
\@notthiscoltrue
\@ff@nwpgfalse
\@colN=#1\relax
\c@curpg=\c@page
\loop
\ifnum\@colN=\c@maxflow
\@colN=1\@ff@nwpgtrue
\advance\c@curpg by 1\relax
\else
\advance\@colN by 1\relax
\fi
\@ff@chkifthispg{\c@curpg}{\@colN}%
\if@notthiscol
\repeat
#1=\@colN
}

\@ff@chkifthispg This is used to determine the next flow frame, since not all flow frames may be
defined on every page. Checks to see if flow frame #2 is defined on page #1. First
set up some variables.
\newcommand*\@ff@chkifthispg}[2]{%
\@notthiscoltrue
\edef\ff@pages{\csname @ff@pages@\romannumeral#2\endcsname}%
\@ff@chkifthispg{#1}%
}

\@@ff@chkifthispg Now go ahead and check.
\newcommand*\@ff@chkifthispg}[1]{%
\ifthenelse{equal{\ff@pages}{none}}{ }{%

```

```

\ifthenelse{\equal{\ff@pages}{all}}{\@notthiscolfalse}{%
\ifthenelse{\equal{\ff@pages}{odd}}{%
\ifodd#1\@notthiscolfalse\fi}{%
\ifthenelse{\equal{\ff@pages}{even}}{%
\ifodd#1\else\@notthiscolfalse\fi}{%
% check through list of page numbers
\@for\@ff@pp:=\ff@pages\do{%
\def\@ff@numstart{0}\def\@ff@numend{0}%
\@ff@getrange{\@ff@pp}%
\ifthenelse{#1<\@ff@numstart \or #1>\@ff@numend}{-}{%
\@notthiscolfalse}%
}%
}}}%
}

```

`\@sf@chckifthispg` Checks to see if **static frame** #1 is defined on the current page.

```

\newcommand*\@sf@chckifthispg}[1]{%
\@notthiscoltrue
\edef\ff@pages{\csname @sf@pages@\romannumeral#1\endcsname}%
\@ff@chckifthispg{\c@page}%
}

```

`\@df@chckifthispg` Checks to see if **dynamic frame** #1 is defined on the current page.

```

\newcommand*\@df@chckifthispg}[1]{%
\@notthiscoltrue
\edef\ff@pages{\csname @df@pages@\romannumeral#1\endcsname}%
\@ff@chckifthispg{\c@page}%
}

```

`\@setcolbox` Sets the TeX box defining the **flow frame** to the output box. This saves the output until the page is shipped out after all the **flow frames** have been filled for that page.

```

\newcommand*\@setcolbox}[1]{%
\expandafter\global\expandafter\setbox
\csname column\romannumeral#1\endcsname\box\@outputbox
}

```

`\@docolbox` Put **flow frame** on the page with the correct border, if it has one.

```

\newcommand*\@docolbox}[1]{%
\edef\ff@frametype{%
\csname @ff@frametype@\romannumeral#1\endcsname}%
\edef\ff@col{\csname @ff@col@\romannumeral#1\endcsname}%
\edef\ff@txtcol{\csname @ff@txtcol@\romannumeral#1\endcsname}%
\edef\ff@backcol{\csname @ff@backcol@\romannumeral#1\endcsname}%
\@ff@setoffset{#1}%
\rotateframe{\csname @ff@angle@\romannumeral#1\endcsname}{%
\ifthenelse{\boolean{columnframe\romannumeral#1}}{%
\@ff@fbox{\csname colwidth\romannumeral#1\endcsname}%
{\csname colheight\romannumeral#1\endcsname}{%
\expandafter\box\csname column\romannumeral#1\endcsname}{%
\csname\ff@frametype\endcsname}%
}}}%
\@ff@box{\csname colwidth\romannumeral#1\endcsname}%
{\csname colheight\romannumeral#1\endcsname}{%
\expandafter\box\csname column\romannumeral#1\endcsname}%
}

```

}}}

`\@docolbbox` Do the **bounding box** for given **flow frame**.

```
\newcommand*{\@docolbbox}[1]{%
\@ff@setoffset{#1}%
\def\ff@col{}\def\ff@txtcol{}%
\@fr@meifdraft{%
\@ff@box{\csname colwidth\romannumeral#1\endcsname}%
{\csname colheight\romannumeral#1\endcsname}{%
\expandafter\box\csname column\romannumeral#1\endcsname}}%
{F:\number#1;\csname @col@id@\romannumeral#1\endcsname}}
```

`\@ff@fbox` Put the $\mathrm{T}_\mathrm{E}\mathrm{X}$ box #3 of width #1 and height #2, and frame making command specified by #4.

```
\newcommand{\@ff@fbox}[4]{%
\fbboxsep=\flowframesep\fbboxrule=\flowframerule\@s@tffcol
\kern\@ff@offset
#4{\@ff@box{#1}{#2}{#3}}}
```

`\@ff@box` Put the $\mathrm{T}_\mathrm{E}\mathrm{X}$ box #3 of width #1 and height #2 on the page.

```
\newcommand{\@ff@box}[3]{\@ffbackground{\vbox to#2
{\hb@xt@ #1{\hss{\@s@tffttextcol #3}\hss}\vss\kern\z@}}}
```

`\@putcolbbox` Display the **flow frame** on the page, at its given position. If the document is two-sided, need to check whether the current page is odd or even to determine the correct location.

```
\newcommand*{\@putcolbbox}[1]{%
\@ff@chckifthispg{\c@page}{#1}%
\if@notthiscol
\else
\@killglue
\if@twoside
\ifodd\c@page
\expandafter\raise\csname col@\romannumeral#1@posy\endcsname
\hb@xt@\z@{%
\expandafter\kern \csname col@\romannumeral#1@posx\endcsname
\@docolbox{#1}\hss}%
\else
\expandafter\raise\csname col@\romannumeral#1@eveny\endcsname
\hb@xt@\z@{%
\expandafter\kern \csname col@\romannumeral#1@evenx\endcsname
\@docolbox{#1}\hss}%
\fi
\else
\expandafter\raise\csname col@\romannumeral#1@posy\endcsname
\hb@xt@\z@{%
\expandafter\kern \csname col@\romannumeral#1@posx\endcsname
\@docolbox{#1}\hss}%
\fi
\fi
}
```

`\@putcolbbox` Same for **flow frame bounding box**:

```

\newcommand*{\@putcolbbox}[1]{%
\@ff@chckifthispg{\c@page}{#1}%
\if@notthiscol
\else
\@killglue
\if@twoside
\ifodd\c@page
\expandafter\raise\csname col@romannumeral#1@posy\endcsname
\hb@xt@\z@{%
\expandafter\kern\csname col@romannumeral#1@posx\endcsname
\@docolbbox{#1}\hss}%
\else
\expandafter\raise\csname col@romannumeral#1@eveny\endcsname
\hb@xt@\z@{%
\expandafter\kern\csname col@romannumeral#1@evenx\endcsname
\@docolbbox{#1}\hss}%
\fi
\else
\expandafter\raise\csname col@romannumeral#1@posy\endcsname
\hb@xt@\z@{%
\expandafter\kern\csname col@romannumeral#1@posx\endcsname
\@docolbbox{#1}\hss}%
\fi
\fi
}

```

If an offset hasn't been specified, compute it. If the frame making command is known (e.g. `doublebox`), compute the offset according to known specifications, otherwise set the negative offset to `\flowframesep` plus `\flowframerule`, which may or may not be correct.

```

\@ff@s@t@doubleboxoffset Compute offset for \doublebox:
\newcommand*{\@ff@s@t@doubleboxoffset}{%
\setlength{\@ff@offset}{-\flowframesep}%
\addtolength{\@ff@offset}{-3.75\flowframerule}%
\addtolength{\@ff@offset}{-.5pt}%
}

```

```

\@ff@s@t@ovalboxoffset Compute offset for \ovalbox:
\newcommand*{\@ff@s@t@ovalboxoffset}{%
\@ff@offset=-\fontdimen 8\tenln\relax
\advance\@ff@offset by -\flowframesep\relax
}

```

```

\@ff@s@t@0valboxoffset Compute offset for \ovalbox:
\newcommand*{\@ff@s@t@0valboxoffset}{%
\@ff@offset=-\fontdimen 8\tenln\relax
\advance\@ff@offset by -\flowframesep\relax
}

```

```

\@ff@s@t@defaultoffset Compute default offset:
\newcommand*{\@ff@s@t@defaultoffset}{%
\@ff@offset=-\flowframesep\relax
}

```

```

\addtolength{\@ff@offset}{-\flowframerule}%
}

```

\@ff@setoffset Compute offset for **flow frame** #1. Stores offset value in \@ff@offset.

```

\newcommand*\@ff@setoffset}[1]{%
\ifthenelse{\equal{\csname @ff@offset@\romannumeral#1\endcsname}%
{compute}}{%
\ifthenelse{\boolean{columnframe\romannumeral#1}}{%
\ifthenelse{%
\equal{\csname @ff@frametype@\romannumeral#1\endcsname}%
{doublebox}}{%
\@ff@s@t@doubleboxoffset
}{%
\ifthenelse{%
\equal{\csname @ff@frametype@\romannumeral#1\endcsname}%
{ovalbox}}{%
\@ff@s@t@ovalboxoffset
}{%
\ifthenelse{%
\equal{\csname @ff@frametype@\romannumeral#1\endcsname}%
{0valbox}}{%
\@ff@s@t@0valboxoffset}{%
\@ff@s@t@defaultoffset
}}}%
}{}%
}{%
\setlength{\@ff@offset}%
{\csname @ff@offset@\romannumeral#1\endcsname}}%
}

```

\@sf@setoffset Compute offset for **static frame** #1. Stores offset value in \@ff@offset.

```

\newcommand*\@sf@setoffset}[1]{%
\ifthenelse{%
\equal{\csname @sf@offset@\romannumeral#1\endcsname}%
{compute}}{%
\ifthenelse{\boolean{staticframe\romannumeral#1}}{%
\ifthenelse{%
\equal{\csname @sf@frametype@\romannumeral#1\endcsname}%
{doublebox}}{%
\@ff@s@t@doubleboxoffset
}{%
\ifthenelse{%
\equal{\csname @sf@frametype@\romannumeral#1\endcsname}%
{ovalbox}}{%
\@ff@s@t@ovalboxoffset
}{%
\ifthenelse{%
\equal{\csname @sf@frametype@\romannumeral#1\endcsname}%
{0valbox}}{%
\@ff@s@t@0valboxoffset
}{%
\@ff@s@t@defaultoffset
}}}%
}{}%
}{%

```

```

}{%
\setlength{\@ff@offset}{%
{\csname @sf@offset@romannumeral#1\endcsname}}%
}

```

`\@df@setoffset` Compute offset for **dynamic frame #1**. Stores offset value in `\ff@offset`.

```

\newcommand*{\@df@setoffset}[1]{%
\ifthenelse{%
\equal{\csname @df@offset@romannumeral#1\endcsname}%
{compute}}{%
\setlength{\@ff@offset}{0pt}%
\ifthenelse{\boolean{dynamicframe\romannumeral#1}}{%
\ifthenelse{%
\equal{\csname @df@frametype@romannumeral#1\endcsname}%
{doublebox}}{%
\@ff@s@t@doubleboxoffset
}{%
\ifthenelse{%
\equal{\csname @df@frametype@romannumeral#1\endcsname}%
{ovalbox}}{%
\@ff@s@t@ovalboxoffset
}{%
\ifthenelse{%
\equal{\csname @df@frametype@romannumeral#1\endcsname}%
{0valbox}}{%
\@ff@s@t@0valboxoffset}{%
\@ff@s@t@defaultoffset
}}}%
}{}%
}{%
\setlength{\@ff@offset}{%
{\csname @df@offset@romannumeral#1\endcsname}}%
}

```

`\@putmarginbox` Draw box representing the margin for **flow frame #1**.

```

\newcommand*{\@putmarginbox}[1]{%
\@ff@chkifthispg{\c@page}{#1}%
\if@notthiscol
\else
\@killglue
\if@twoside
\ifodd\c@page
\edef\ff@x{\csname col@romannumeral#1@posx\endcsname}%
\edef\ff@y{\csname col@romannumeral#1@posy\endcsname}%
\else
\edef\ff@x{\csname col@romannumeral#1@evenx\endcsname}%
\edef\ff@y{\csname col@romannumeral#1@eveny\endcsname}%
\fi
\else
\edef\ff@x{\csname col@romannumeral#1@posx\endcsname}%
\edef\ff@y{\csname col@romannumeral#1@posy\endcsname}%
\fi
\setlength{\@ff@tmp@x}{\ff@x}%
\setlength{\@ff@tmp@y}{\ff@y}%

```

```

\@getmarginpos{\csname @ff@margin@romannumeral#1\endcsname}%
\ifthenelse{\equal{\ff@margin}{left}}{%
\addtolength{\ff@tmp@x}{-\marginparwidth}%
\addtolength{\ff@tmp@x}{-\marginparsep}%
\ifthenelse{\boolean{columnframe\romannumeral#1}}{%
}%}%
}%%
\addtolength{\ff@tmp@x}%
{\csname colwidth\romannumeral#1\endcsname}%
\addtolength{\ff@tmp@x}{\marginparsep}%
\ifthenelse{\boolean{columnframe\romannumeral#1}}{%
}%}%
}%%
\raise\ff@tmp@y
\hb@xt@\z@{%
\expandafter\kern\ff@tmp@x
\@fr@meifdraft{\ff@box{\marginparwidth}%
{\csname colheight\romannumeral#1\endcsname}}}%%
{M:\number#1}\hss}\fi
\ignorespaces}

```

`\@ff@drawmargins` Draw all the margins associated with the **flow frames** defined on the current page.

```

\newcommand*{\@ff@drawmargins}{%
\@colN=0\relax
\whiledo{\@colN<\c@maxflow}{%
\advance\@colN by 1\relax
\makebox[0pt][l]{\@putmarginbox{\@colN}}}%
}%
}

```

`\@ff@getstaticpos` Extract the width and height for static or **dynamic frame** specified in the form `[< c >] [< height >] [< valign >] [< width >]`

```

\def\@ff@getstaticpos[#1][#2][#3]#4{\@ff@tmp@x=#4\relax
\@ff@tmp@y=#2\relax
\def\ff@valign{#3}}

```

`\@dostaticbox` Display the savebox associated with **static frame** #1

```

\newcommand*{\@dostaticbox}[1]{%
\edef\ff@frametype{%
\csname @sf@frametype@romannumeral#1\endcsname}%
\edef\ff@col{\csname @sf@col@romannumeral#1\endcsname}%
\edef\ff@backcol{\csname @sf@backcol@romannumeral#1\endcsname}%
\@sf@setoffset{#1}%
\expandafter\expandafter\expandafter
\@ff@getstaticpos\csname @sf@dim@romannumeral#1\endcsname
\rotateframe{\csname @sf@angle@romannumeral#1\endcsname}{%
\ifthenelse{\boolean{staticframe\romannumeral#1}}{%
\@ff@fbox{\@ff@tmp@x}{\@ff@tmp@y}{%
\expandafter\usebox\csname @staticframe@romannumeral#1\endcsname}
{\csname\ff@frametype\endcsname}%
}%}%
\@ff@box{\@ff@tmp@x}{\@ff@tmp@y}%
\expandafter\usebox\csname @staticframe@romannumeral#1\endcsname}%
}}

```

`\@dostaticbbox` Now for the **bounding box**:

```
\newcommand*{\@dostaticbbox}[1]{%
\edef\ff@col{%
\@sf@setoffset{#1}%
\expandafter\expandafter\expandafter
\@ff@getstaticpos\csname @sf@dim@\romannumeral#1\endcsname
\@fr@meifdraft{%
\@ff@box{\@ff@tmp@x}{\@ff@tmp@y}%
{\expandafter\usebox\csname @staticframe@\romannumeral#1\endcsname}%
}{S:\number#1;\csname @sf@id@\romannumeral#1\endcsname}}
```

`\@putstaticbbox` Put the static box #1 at its given position, with its associated border.

```
\newcommand*{\@putstaticbbox}[1]{%
\@sf@chkifthispg{#1}%
\if@notthiscol\else
\@killglue
\if@twoside
\ifodd\c@page
\expandafter\raise\csname @sf@\romannumeral#1@posy\endcsname
\hb@xt@\z@{%
\expandafter\kern \csname @sf@\romannumeral#1@posx\endcsname
\@dostaticbox{#1}\hss}%
\else
\expandafter\raise\csname @sf@\romannumeral#1@eveny\endcsname
\hb@xt@\z@{%
\expandafter\kern \csname @sf@\romannumeral#1@evenx\endcsname
\@dostaticbox{#1}\hss}%
\fi
\else
\expandafter\raise\csname @sf@\romannumeral#1@posy\endcsname
\hb@xt@\z@{%
\expandafter\kern \csname @sf@\romannumeral#1@posx\endcsname
\@dostaticbox{#1}\hss}%
\fi
\fi}
```

`\@putstaticbbox` Now for the **bounding box**:

```
\newcommand*{\@putstaticbbox}[1]{%
\@sf@chkifthispg{#1}%
\if@notthiscol\else
\@killglue
\if@twoside
\ifodd\c@page
\expandafter\raise\csname @sf@\romannumeral#1@posy\endcsname
\hb@xt@\z@{%
\expandafter\kern \csname @sf@\romannumeral#1@posx\endcsname
\@dostaticbbox{#1}\hss}\ignorespaces
\else
\expandafter\raise\csname @sf@\romannumeral#1@eveny\endcsname
\hb@xt@\z@{%
\expandafter\kern \csname @sf@\romannumeral#1@evenx\endcsname
\@dostaticbbox{#1}\hss}\ignorespaces
\fi
\else
```

```

\expandafter\raise\csname @sf@romannumeral#1@posy\endcsname
\hb@xt@z@{%
\expandafter\kern\csname @sf@romannumeral#1@posx\endcsname
\@dostaticbbox{#1}\hss}\ignorespaces
\fi
\fi}

\@resetst@tics Clear the contents of all the static frames that have the clear option set.
\newcommand*{\@resetst@tics}{%
\@colN=0\relax
\whiledo{\@colN<\c@maxstatic}{\advance\@colN by 1\relax
\ifthenelse{\boolean{@sf@clear@romannumeral\@colN}}{%
\global\sbox{%
\csname @staticframe@romannumeral\@colN\endcsname}{}}{}}}

\@resetdyn@mics Clear the contents of the dynamic frames that have the clear option set.
\newcommand*{\@resetdyn@mics}{%
\@colN=0\relax
\whiledo{\@colN<\c@maxdynamic}{\advance\@colN by 1\relax
\ifthenelse{\boolean{@df@clear@romannumeral\@colN}}{%
\expandafter\global\expandafter
\gdef\csname @dynamicframe@romannumeral\@colN\endcsname}{}}{}}}

\@dodfparbox Display contents of dynamic box (contents stored in \ff@contents, style given by
\ff@style):
\newcommand*{\@dodfparbox}[1]{%
\expandafter\let\expandafter
\@ff@parshape\csname @df@shape@romannumeral#1\endcsname
\expandafter\@ff@getshape\@ff@parshape\relax
\ifcase\ff@shape
% no shape
\expandafter\expandafter\expandafter
\parbox\csname @df@dim@romannumeral#1\endcsname
{%
\setlength\parindent\sdfparindent
\csname\ff@style\endcsname{\ff@contents}}%
\or
% \parshape
\expandafter\expandafter\expandafter
\parbox\csname @df@dim@romannumeral#1\endcsname
{%
\setlength\parindent\sdfparindent
\csname\ff@style\endcsname{%
\let\oldpar=\par
\let\par=\ffpshpar
\@ff@setsecthead
\@ff@parshape
\ff@contents\oldpar}}}%
\or
% \shapepar
\expandafter\expandafter\expandafter
\parbox\csname @df@dim@romannumeral#1\endcsname
{%
\setlength\parindent\sdfparindent

```

```

\csname\ff@style\endcsname{\@ff@disablesec\@ff@parshape
\ff@contents\par}}}%
\fi
}

```

\@dodynamicbox Typeset the dynamic box with its associated border.

```

\newcommand*{\@dodynamicbox}[1]{%
\edef\ff@frametype{%
\csname @df@frametype@romannumeral#1\endcsname}%
\edef\ff@col{\csname @df@col@romannumeral#1\endcsname}%
\edef\ff@txtcol{\csname @df@txtcol@romannumeral#1\endcsname}%
\edef\ff@backcol{\csname @df@backcol@romannumeral#1\endcsname}%
\edef\ff@style{\csname @df@style@romannumeral#1\endcsname}%
\def\ff@contents{\csname @dynamicframe@romannumeral#1\endcsname}%
\@df@setoffset{#1}%
\expandafter\expandafter\expandafter
\@ff@getstaticpos\csname @df@dim@romannumeral#1\endcsname
\rotateframe{\csname @df@angle@romannumeral#1\endcsname}{%
\ifthenelse{\boolean{dynamicframe@romannumeral#1}}{%
\@ff@fbox{\@ff@tmp@x}{\@ff@tmp@y}%
{\@dodfparbox{#1}}}%
{\csname\ff@frametype\endcsname}%
}{%
\@ff@box{\@ff@tmp@x}{\@ff@tmp@y}{%
\@dodfparbox{#1}}}%
}}}

```

\@dodynamicbbox Now for the **bounding box**:

```

\newcommand*{\@dodynamicbbox}[1]{%
\edef\ff@col{%
\@df@setoffset{#1}%
\expandafter\expandafter\expandafter
\@ff@getstaticpos\csname @df@dim@romannumeral#1\endcsname
\@fr@meifdraft{%
\@ff@box{\@ff@tmp@x}{\@ff@tmp@y}{%
\expandafter\expandafter\expandafter
\parbox\csname @df@dim@romannumeral#1\endcsname
{}}%
}{D:\number#1;\csname @df@id@romannumeral#1\endcsname}}

```

\@putdynamicbox Put the **dynamic frame #1** at its given position

```

\newcommand*{\@putdynamicbox}[1]{%
\@df@chkifthispg{#1}%
\if@notthiscol\else
\@killglue
\if@twoside
\ifodd\c@page
\expandafter\raise\csname @df@romannumeral#1@posy\endcsname
\hb@xt@\z@{%
\expandafter\kern\csname @df@romannumeral#1@posx\endcsname
\@dodynamicbox{#1}\hss}\ignorespaces
\else
\expandafter\raise\csname @df@romannumeral#1@eveny\endcsname
\hb@xt@\z@{%

```

```

\expandafter\kern \csname @df@romannumeral#1@evenx\endcsname
\@dodynamicbox{#1}\hss\ignorespaces
\fi
\else
\expandafter\raise\csname @df@romannumeral#1@posy\endcsname
\hb@xt@\z@{%
\expandafter\kern \csname @df@romannumeral#1@posx\endcsname
\@dodynamicbox{#1}\hss\ignorespaces
\fi
\fi}

\@putdynamicbbox Bounding box:
\newcommand*{\@putdynamicbbox}[1]{%
\@df@chkifthispg{#1}%
\if@notthiscol\else
\@killglue
\if@twoside
\ifodd\c@page
\expandafter\raise\csname @df@romannumeral#1@posy\endcsname
\hb@xt@\z@{%
\expandafter\kern \csname @df@romannumeral#1@posx\endcsname
\@dodynamicbbox{#1}\hss\ignorespaces
\else
\expandafter\raise\csname @df@romannumeral#1@eveny\endcsname
\hb@xt@\z@{%
\expandafter\kern \csname @df@romannumeral#1@evenx\endcsname
\@dodynamicbbox{#1}\hss\ignorespaces
\fi
\else
\expandafter\raise\csname @df@romannumeral#1@posy\endcsname
\hb@xt@\z@{%
\expandafter\kern \csname @df@romannumeral#1@posx\endcsname
\@dodynamicbbox{#1}\hss\ignorespaces
\fi
\fi}

\@doheader Do standard header in the standard place.
\newcommand*{\@doheader}{%
\setlength\@ff@tmp@y{\textheight}%
\addtolength{\@ff@tmp@y}{\headsep}%
\def\ff@col{}%
\def\ff@txtcol{}%
\def\ff@backcol{{none}}%
\@ff@box{0pt}{\@ff@tmp@y}{\makebox[0pt][l]{\@dothehead}}%
}

\@dofooter Do standard footer in the standard place.
\newcommand*{\@dofooter}{%
\setlength\@ff@tmp@y{-\footskip}%
\def\ff@col{}%
\def\ff@txtcol{}%
\def\ff@backcol{{none}}%
\@ff@box{0pt}{\@ff@tmp@y}{\makebox[0pt][l]{\@dothefoot}}%
}

```

`\s@tfr@mes` This is a modified version of the way the picture environment works:

```

\newcommand{\s@tfr@mes}[1]{\@picht\textheight
\setbox\@picbox\hb@xt@ \textwidth
\bggroup \hbox \bggroup #1\relax
\egroup
\hss \egroup
\ht\@picbox\@picht \dp\@picbox
\z@ \mbox{\box \@picbox}}

```

`\ff@doallflowframes` Puts all the **flow frames** defined on the current page

```

\newcommand*\ff@doallflowframes{%
\@colN=0\relax
\whiledo{\@colN<\c@maxflow}{\advance\@colN by 1\relax
\@putcolbox{\@colN}}%
}

```

`\ff@doallflowframesbbox` Flow frame **bounding boxes**:

```

\newcommand*\ff@doallflowframesbbox{%
\@colN=0\relax
\whiledo{\@colN<\c@maxflow}{\advance\@colN by 1\relax
\@putcolbbox{\@colN}}%
}

```

`\ff@doallstatics` Puts all **static frames** defined on the current page

```

\newcommand*\ff@doallstatics{%
\@colN=0\relax
\whiledo{\@colN<\c@maxstatic}{\advance\@colN by 1\relax
\@putstaticbox{\@colN}}%
}

```

`\ff@doallstaticsbbox` Static frame **bounding boxes**:

```

\newcommand*\ff@doallstaticsbbox{%
\@colN=0\relax
\whiledo{\@colN<\c@maxstatic}{\advance\@colN by 1\relax
\@putstaticbbox{\@colN}}%
}

```

`\ff@doalldynamics` Puts all the **dynamic frames** defined on the current page

```

\newcommand*\ff@doalldynamics{%
\@colN=0\relax
\whiledo{\@colN<\c@maxdynamic}{\advance\@colN by 1\relax
\@putdynamicbox{\@colN}}%
}

```

`\ff@doalldynamicsbbox` Dynamic frame **bounding boxes**:

```

\newcommand*\ff@doalldynamicsbbox{%
\@colN=0\relax
\whiledo{\@colN<\c@maxdynamic}{\advance\@colN by 1\relax
\@putdynamicbbox{\@colN}}%
}

```

`\ff@dotypeblock` Draw **typeblock** frame if draft.

```

\newcommand*\ff@dotypeblock{%
\makebox[0pt][l]{\@fr@meifdraft[\setffdrafttypeblockcolor]{%
\vbox to \textheight{\hbox to \textwidth{}}{}}}

```

```

\@ff@do@allframes Put all frames defined on the current page.
    \newlength\ffevenoffset
    \newcommand*{\@ff@do@allframes}{%
    \ffevenoffset=0pt\relax
    \if@twoside
        \ifodd\c@page
        \else
            \ffevenoffset=-\oddsidemargin\relax
            \advance\ffevenoffset by \evensidemargin\relax
            \kern\ffevenoffset\relax
        \fi
    \fi
    \setlength{\@ff@tmp@x}{\textwidth}%
    \advance\@ff@tmp@x by -\ffevenoffset\relax
    \makebox[\@ff@tmp@x][l]{%
    \@s@tfr@mes{%
    \@ff@doallstatics
    \@@doheader
    \@@dofooter
    \@ff@doallflowframes
    \@ff@doalldynamics
    \ifshowtypeblock
        \@ff@dotypeblock
    \fi
    \ifshowframebbox
        \@ff@doallstaticsbbox
        \@ff@doallflowframesbbox
        \@ff@doalldynamicsbbox
    \fi
    \ifshowmargins
        \@ff@drawmargins
    \fi
    }}}

```

`\@outputdblcol` This was modified from the output routine for standard two column format. After `\@g@tnextcol`, the register `\c@curpg` contains the page that the next **flow frame** is on. If `\c@curpg` minus `\c@page` is greater than 1, then there is at least one page without a **flow frame**. These pages will have to be shipped before \TeX can continue with the rest of the document.

```

    \newcount\@nxtcol
    \def\@outputdblcol{%
    \@nxtcol=\c@thisframe
    \c@curpg=\c@page
    \@g@tnextcol{\@nxtcol}%
    \if@ff@nwpg % next flow frame starts on new page
        \global\@firstcolumntrue
        \setcolbox\c@thisframe
        \if@specialpage
            \global\@specialpagefalse
            \@nameuse{ps@\@specialstyle}\relax
        \fi
        \if@twoside
            \ifodd\count\z@
                \let\@thehead\@oddhead

```

```

        \let\@thehead\@oddhead
    \else
        \let\@thehead\@evenhead
        \let\@thefoot\@evenfoot
    \fi
\else
    \let\@thehead\@oddhead
    \let\@thefoot\@oddfoot
\fi
\@beginndvi
\@dodynamicthehead\@dodynamicthefoot
\vbaddness=\@M
\setbox\@outputbox\vbox{\hbox to \textwidth{\@ffdo@allframes}}%
\@combinedblfloats
\@outputpage
%shipout pages without flow frames
\advance\c@curpg by -\c@page\relax
\whiledo{\c@curpg>0}{\advance\c@curpg by -1\relax
\setbox\@outputbox\vbox{\hbox to \textwidth{\@ffdo@allframes}}}%
\@outputpage}
\beginingroup
\@dblfloatplacement
\@startdblcolumn
\@whilesw \if@fcolmade \fi
{\@outputpage \@startdblcolumn }\endgroup
\@resetst@tics
\@resetdyn@tics
\else % still on same page, save contents of box255
\global\@firstcolumnfalse
\@setcolbox\c@thisframe
\fi
\global\c@thisframe=\@nxtcol
\@setcol{\c@thisframe}\relax
\global\@colht\vsiz
}

```

`\@dblfloatplacement` Modify `\@dblfloatplacement` replacing `\textheight` with `\vsiz`.

```

\def\@dblfloatplacement{%
\global\@dbltopnum\c@dbltopnumber
\global\@dbltoproom\dbltopfraction\@colht\@textmin
\@colht\advance\@textmin -\@dbltoproom
\@fpmin\dblfloatpagefraction\vsiz
\@fptop \@dblftop \@fpsep \@dblfpsep \@fpbot \@dblfpbot}

```

1.8 Static versions of floats

Floats can not go in saveboxes or minipages, so define static versions to go in static and **dynamic frames**. These just set `\@capttype` so that the `\caption` command may be used.

`statictable`

```

\newenvironment{statictable}{\def\@capttype{table}}{}

```

`staticfigure`

```
\newenvironment{staticfigure}{\def\@capttype{figure}}{}
```

1.9 Standard Layouts

1.9.1 Column Styles

Redefine `\twocolumn` and `\onecolumn` to set up **flow frames** from the dimensions of the **typeblock**. Ignore the optional argument. The **flow frame** height will be adjusted to make sure that it is an integer multiple of `\baselineskip`, unless `\ffvadjustfalse` is used.

```
\newif\iffvadjust
\ffvadjusttrue
```

`\onecolumn` `\onecolumn` will make a single **flow frame** that takes up the entire area of the **typeblock** (adjusted according to `\iffvadjust`.) Frames should only be created in the preamble, otherwise the next **flow frame** may not be detected by the output routine. The exception to this is when the output routine can't find any more **flow frames** to use, in which case it creates a single **flow frame** using `\@onecolumn`. Therefore, make `\onecolumn` use `\@onecolumn`, and then set `\onecolumn` as a preamble command, so it can't be used in the document, but the output routine can use `\@onecolumn`. Syntax: `\onecolumn[⟨pages⟩]`, where `⟨pages⟩` is the **page list** for which the new **flow frame** is defined.

```
\renewcommand*{\onecolumn}{\@onecolumn}
```

`\@onecolumn`

```
\newcommand*{\@onecolumn}[1][all]{%
\onecolumninarea[#1]{\textwidth}{\textheight}{0pt}{0pt}}
```

Need a length to store the height of the **flow frame** so that it can be adjusted.

```
\newlength\columnheight
```

`\onecolumninarea` `\onecolumn` is in fact a special case of `\onecolumninarea` which sets up one **flow frame** in the specified area, given by bottom left corner (`⟨x⟩`, `⟨y⟩`), relative to the **typeblock**, with width `⟨w⟩` and height `⟨h⟩`. The only difference between `\onecolumninarea` and explicitly creating the **flow frame** using `\newflowframe` is the `\onecolumninarea` will adjust the vertical height to ensure it is a multiple of `\baselineskip`. There is also no starred version, so if you want a border, you will need to set it explicitly using `\setflowframe`. Syntax:

```
\onecolumninarea[⟨pages⟩]{⟨w⟩}{⟨h⟩}{⟨x⟩}{⟨y⟩}.
```

```
\newcommand*{\onecolumninarea}{\@onecolumninarea}
\@onlypreamble{\onecolumninarea}
```

`\@onecolumninarea`

```
\newcommand*{\@onecolumninarea}[5][all]{%
\setlength{\columnheight}{#3}%
\iffvadjust\adjustheight{\columnheight}\fi%
\@newflowframe[#1]{#2}{\columnheight}{#4}{#5}}
```

`\twocolumn` Set up two **flow frames** parallel to each other with a distance of `\columnsep` between them, to fill the entire **typeblock** (although the frames may end up marginally shorter than `\textheight` after they have been adjusted.) Again, these

commands may only be used in the preamble. Note that unlike the standard `\twocolumn` command, this one has an optional argument that indicates which pages the two **flow frames** should appear on. Syntax: `\twocolumn[⟨pages⟩]`.

```
\renewcommand*{\twocolumn}{\@twocolumn}
```

`\@twocolumn`

```
\newcommand*{\@twocolumn}[1][all]{%
\@twocolumninarea[#1]{\textwidth}{\textheight}{0pt}{0pt}}
```

`\twocolumninarea` Again, `\twocolumn` is actually a special case of `\twocolumninarea`. Syntax:

```
\twocolumninarea[⟨pages⟩]{⟨w⟩}{⟨h⟩}{⟨x⟩}{⟨y⟩}.
```

```
\newcommand*{\twocolumninarea}{\@twocolumninarea}
\@onlypreamble{\twocolumninarea}
```

`\@twocolumninarea`

```
\newcommand*{\@twocolumninarea}[5][all]{%
\setlength{\columnheight}{#3}%
\iffvadjust\adjustheight{\columnheight}\fi%
\setlength{\columnwidth}{#2}%
\addtolength{\columnwidth}{-\columnsep}%
\divide\columnwidth by 2\relax
\setlength{\@ff@tmp@x}{#4}%
\addtolength{\@ff@tmp@x}{\columnwidth}%
\addtolength{\@ff@tmp@x}{\columnsep}%
\@n@wflowframe[#1]{\columnwidth}{\columnheight}{#4}{#5}%
\setflowframe{\c@maxflow}{margin=left}%
\@n@wflowframe[#1]{\columnwidth}{\columnheight}{\@ff@tmp@x}{#5}%
\setflowframe{\c@maxflow}{margin=right}%
}
```

`\Ncolumn` Again for an arbitrary number of columns ($\langle n \rangle$). Syntax: `\Ncolumn[⟨pages⟩]{⟨n⟩}`.

```
\newcommand*{\Ncolumn}[2][all]{%
\Ncolumninarea[#1]{#2}{\textwidth}{\textheight}{0pt}{0pt}}
\@onlypreamble{\Ncolumn}
```

`\Ncolumninarea` Check the number of **flow frames** requested, and do one of the special cases if available. Syntax:

```
\Ncolumninarea[⟨pages⟩]{⟨n⟩}{⟨w⟩}{⟨h⟩}{⟨x⟩}{⟨y⟩}.
```

```
\newcommand*{\Ncolumninarea}[6][all]{%
\ifnum#2>2\relax
\@Ncolumninarea[#1]{#2}{#3}{#4}{#5}{#6}%
\else
\ifcase#2\relax
\PackageError{flowfram}{%
You have requested 0 flowframes!}{%
It does not make much sense to ask to create 0 flow frames}%
\or
\onecolumninarea[#1]{#3}{#4}{#5}{#6}%
\or
\twocolumninarea[#1]{#3}{#4}{#5}{#6}%
\else
\PackageError{flowfram}{%
Can't create a negative number of flow frames!}{%
}
```

```

        You have asked for \number#2 \space flow frames
        which really doesn't make sense}%
    \fi
\fi
}

\@onlypreamble{\Ncolumninarea}

\Ncolumninarea Set up  $\langle n \rangle$  columns in the area specified. There is a horizontal distance of
\columnsep between them all.
    \newcommand*{\Ncolumninarea}[6][all]{%
    \@colN=#2\relax
    \advance\@colN by -1\relax
    \setlength{\columnwidth}{#3}%
    \addtolength{\columnwidth}{-\@colN\columnsep}%
    \divide\columnwidth by #2\relax
    \setlength{\@ff@tmp@x}{#5}%
    \setlength{\columnheight}{#4}%
    \iffvadjust\adjustheight{\columnheight}\fi%
    \@colN=0\relax
    \loop
    \advance\@colN by 1\relax
    \newflowframe[#1]{\columnwidth}{\columnheight}{\@ff@tmp@x}{#6}%
    \addtolength{\@ff@tmp@x}{\columnwidth}%
    \addtolength{\@ff@tmp@x}{\columnsep}%
    \ifnum\@colN<#2
    \repeat
    }

    Set up something similar but have another frame (of type  $\langle type \rangle$ ) at the top of
    the other frames.

\vcolumnsep The vertical distance between the top frames and column flow frames when created
using \Ncolumnhead etc is given by:
    \newlength{\vcolumnsep}
    \setlength{\vcolumnsep}{\columnsep}

\onecolumnntop \onecolumnntop makes one flow frame, and one  $\langle type \rangle$  frame in the area specified,
where the  $\langle type \rangle$  frame is  $\langle H \rangle$  high. The distance between the top frame and the
column flow frame will be approximately \vcolumnsep. (The height of flow frame
may be adjusted to make it an integer multiple of \baselineskip.)
    First the special case where the area is the typeblock. Syntax:
    \onecolumnntop[ $\langle pages \rangle$ ]{ $\langle type \rangle$ }{ $\langle H \rangle$ }
    \newcommand*{\onecolumnntop}[3][all]{%
    \onecolumnntopinarea[#1]{#2}{#3}{\textwidth}{\textheight}{0pt}{0pt}}
    \@onlypreamble{\onecolumnntop}

\onecolumnnStop Special case for static frame. Syntax: \onecolumnnStop[ $\langle pages \rangle$ ]{ $\langle H \rangle$ }
    \newcommand*{\onecolumnnStop}[2][all]{%
    \onecolumnntopinarea[#1]{static}{#2}{\textwidth}{\textheight}{0pt}{0pt}}

\onecolumnnDtop Special case for dynamic frame. Syntax: \onecolumnnDtop[ $\langle pages \rangle$ ]{ $\langle H \rangle$ }
    \newcommand*{\onecolumnnDtop}[2][all]{%
    \onecolumnntopinarea[#1]{dynamic}{#2}{\textwidth}{\textheight}{0pt}{0pt}}

```

`\newframe` Create a frame of given type. Syntax:
`\newframe[⟨pages⟩]{⟨type⟩}{⟨w⟩}{⟨h⟩}{⟨x⟩}{⟨y⟩}.`
`\newcommand*{\newframe}[6][all]{%`
`\ifthenelse{equal{#2}{flow}}{%`
`\@n@wflowframe[#1]{#3}{#4}{#5}{#6}%`
`}{%`
`\ifthenelse{equal{#2}{dynamic}}{%`
`\@n@wdynamicframe[#1]{#3}{#4}{#5}{#6}{#7}%`
`\ifthenelse{equal{#2}{static}}{%`
`\@n@wstaticframe[#1]{#3}{#4}{#5}{#6}{#7}%`
`\PackageError{flowfram}{Unknown frame type ‘#2’}{%`
`Available frame types are: ‘flow’, ‘static’ and ‘dynamic’}}}`

`\onecolumnntopinarea` Now for a specified area. Syntax:
`\onecolumnntopinarea[⟨pages⟩]{⟨type⟩}{⟨H⟩}{⟨w⟩}{⟨h⟩}{⟨x⟩}{⟨y⟩}.`
`\newlength{\@ff@staticH}`
`\newcommand*{\onecolumnntopinarea}[7][all]{%`
`\setlength{\@ff@staticH}{#3}%`
`\setlength{\@ff@tmp@y}{#5}%`
`\addtolength{\@ff@tmp@y}{- \@ff@staticH}%`
`\setlength{\columnheight}{\@ff@tmp@y}%`
`\addtolength{\columnheight}{- \vcolumnsep}%`
`\ifffvadjust\adjustheight{\columnheight}\fi%`
`\addtolength{\@ff@tmp@y}{#7}%`
`\newframe[#1]{#2}{#4}{\@ff@staticH}{#6}{\@ff@tmp@y}%`
`\@n@wflowframe[#1]{#4}{\columnheight}{#6}{#7}%`
`}`
`\@onlypreamble{\onecolumnntopinarea}`

`\onecolumnStopinarea` Special case for **static frame**. Syntax:
`\onecolumnStopinarea[⟨pages⟩]{⟨H⟩}{⟨w⟩}{⟨h⟩}{⟨x⟩}{⟨y⟩}.`
`\newcommand*{\onecolumnStopinarea}[6][all]{%`
`\onecolumnntopinarea[#1]{static}{#2}{#3}{#4}{#5}{#6}}`

`\onecolumnDtopinarea` Special case for **dynamic frame**. Syntax:
`\onecolumnDtopinarea[⟨pages⟩]{⟨H⟩}{⟨w⟩}{⟨h⟩}{⟨x⟩}{⟨y⟩}.`
`\newcommand*{\onecolumnDtopinarea}[6][all]{%`
`\onecolumnntopinarea[#1]{dynamic}{#2}{#3}{#4}{#5}{#6}}`

`\twocolumntop` Now for two **flow frames**, with a single *type* frame above both of them. Syntax:
`\twocolumntop[⟨pages⟩]{⟨type⟩}{⟨H⟩}`
First the special case where the area is the entire **typeblock**:
`\newcommand*{\twocolumntop}[3][all]{%`
`\twocolumntopinarea[#1]{#2}{#3}{\textwidth}{\textheight}{0pt}{0pt}}`
`\@onlypreamble{\twocolumntop}`

`\twocolumnStop` Special case for **static frame**.
`\newcommand*{\twocolumnStop}[2][all]{%`
`\@twocolumntopinarea[#1]{static}{#2}{\textwidth}{\textheight}{0pt}{0pt}}`

`\twocolumnDtop` Special case for **dynamic frame**.

```
\newcommand*\twocolumnDtop}[2][all]{%
\twocolumntop[#1]{dynamic}{#2}}
```

Now for a general area.

`\twocolumntopinarea` Syntax:

```
\twocolumntopinarea[⟨pages⟩]{⟨type⟩}{⟨H⟩}{⟨w⟩}{⟨h⟩}{⟨x⟩}{⟨y⟩}.
\newcommand*\twocolumntopinarea{\@twocolumntopinarea}
\newcommand*\@twocolumntopinarea[7][all]{%
\setlength{\off@staticH}{#3}%
% work out where to put the static frame
\setlength{\off@tmp@y}{#5}%
\addtolength{\off@tmp@y}{-\off@staticH}%
\setlength{\columnheight}{\off@tmp@y}%
\addtolength{\off@tmp@y}{#7}%
\newframe[#1]{#2}{#4}{\off@staticH}{#6}{\off@tmp@y}%
% work out height of the flow frames
\addtolength{\columnheight}{-\vcolumnsep}%
\iffvadjust\adjustheight{\columnheight}\fi%
% work out the widths of the flow frames
\setlength{\columnwidth}{#4}%
\addtolength{\columnwidth}{-\columnsep}%
\divide\columnwidth by 2\relax
% work out the offset of the second column
\setlength{\off@tmp@x}{\columnwidth}%
\addtolength{\off@tmp@x}{\columnsep}%
\addtolength{\off@tmp@x}{#6}%
\@n@wflowframe[#1]{\columnwidth}{\columnheight}{#6}{#7}%
\setflowframe{\c@maxflow}{margin=left}%
\@n@wflowframe[#1]{\columnwidth}{\columnheight}{\off@tmp@x}{#7}%
\setflowframe{\c@maxflow}{margin=right}%
}
\@onlypreamble{\twocolumntopinarea}
```

`\twocolumnStopinarea` Special case for **static frame**.

```
\newcommand*\twocolumnStopinarea}[6][all]{%
\twocolumntopinarea[#1]{static}{#2}{#3}{#4}{#5}{#6}}
```

`\twocolumnDtopinarea` Special case for **dynamic frame**.

```
\newcommand*\twocolumnDtopinarea}[6][all]{%
\twocolumntopinarea[#1]{dynamic}{#2}{#3}{#4}{#5}{#6}}
```

`\Ncolumnntop` Similarly for an arbitrary number of **flow frames**. Special case where the area is the **typeblock**.

Syntax:

```
\Ncolumnntop[⟨pages⟩]{⟨type⟩}{⟨n⟩}{⟨H⟩}
\newcommand*\Ncolumnntop}[4][all]{%
\Ncolumnntopinarea[#1]{#2}{#3}{#4}{\textwidth}{\textheight}{0pt}{0pt}}
\@onlypreamble{\Ncolumnntop}
```

`\NcolumnStop` Special case for **static frame**.

```
\newcommand*\NcolumnStop}[3][all]{%
\Ncolumnntop[#1]{static}{#2}{#3}}
```

`\NcolumnDtop` Special case for **dynamic frame**.

```

\newcommand*{\NcolumnDtop}[3][all]{%
\NcolumnDtop[#1]{dynamic}{#2}{#3}}

```

`\NcolumnDtopinarea` Again test to make sure the user requested a sensible number.

```

\newcommand*{\NcolumnDtopinarea}[8][all]{%
\ifnum#3>2\relax
\@NcolumnDtopinarea[#1]{#2}{#3}{#4}{#5}{#6}{#7}{#8}%
\else
\ifcase#3\relax
\PackageError{flowfram}{%
You have requested 0 flowframes!}{%
It does not make much sense to ask to create 0 flow frames}
\or
\onecolumnDtopinarea[#1]{#2}{#4}{#5}{#6}{#7}{#8}%
\or
\twocolumnDtopinarea[#1]{#2}{#4}{#5}{#6}{#7}{#8}%
\else
\PackageError{flowfram}{%
Can't create a negative number of flow frames!}{%
You have asked for \number#3 \space flow frames
which really doesn't make sense}%
\fi
\fi
}
\@onlypreamble{\NcolumnDtopinarea}

```

`\@NcolumnDtopinarea` Fit the frames into specified area. Syntax:

```

\NcolumnDtopinarea[⟨pages⟩]{⟨type⟩}{⟨n⟩}{⟨H⟩}{⟨w⟩}{⟨h⟩}{⟨x⟩}{⟨y⟩}.
\newcommand*{\@NcolumnDtopinarea}[8][all]{%
\setlength{\@ff@staticH}{#4}%

```

work out where to put the static frame

```

\setlength{\@ff@tmp@y}{#6}%
\addtolength{\@ff@tmp@y}{-\@ff@staticH}%
\setlength{\columnheight}{\@ff@tmp@y}%
\addtolength{\@ff@tmp@y}{#8}%
\newframe[#1]{#2}{#5}{\@ff@staticH}{#7}{\@ff@tmp@y}%

```

work out height of the flow frames

```

\addtolength{\columnheight}{-\vcolumnsep}%

```

adjust the flow frame height so that it is a multiple of `\baselineskip`

```

\iffvadjust\adjustheight{\columnheight}\fi%

```

work out the widths of the flow frames

```

\@colN=#3\relax
\advance\@colN by -1\relax
\setlength{\columnwidth}{#5}%
\addtolength{\columnwidth}{-\@colN\columnsep}%
\divide\columnwidth by #3\relax
\setlength{\@ff@tmp@x}{#7}%
\@colN=0\relax
\loop
\advance\@colN by 1\relax

```

```

\newflowframe[#1]{\columnwidth}{\columnheight}{\@ff@tmp@x}{#8}%
% work out the offset for the next column
\addtolength{\@ff@tmp@x}{\columnwidth}%
\addtolength{\@ff@tmp@x}{\columnsep}%
\ifnum\@colN<#3
\repeat
}

```

`\NcolumnStopinarea` Specific case for **static frame**.

```

\newcommand*\NcolumnStopinarea[7][all]{%
\Ncolumnstopinarea[#1]{static}{#2}{#3}{#4}{#5}{#6}{#7}}

```

`\NcolumnDtopinarea` Specific case for **dynamic frame**.

```

\newcommand*\NcolumnDtopinarea[7][all]{%
\Ncolumnstopinarea[#1]{dynamic}{#2}{#3}{#4}{#5}{#6}{#7}}

```

Now the same kind of thing but with the $\langle type \rangle$ frame at the bottom. Firstly, a single **flow frame** with a $\langle type \rangle$ frame below it.

```

\onecolumnbottom Syntax:
\onecolumnbottom[\langle pages \rangle]{\langle type \rangle}{\langle H \rangle}
\newcommand*\onecolumnbottom[3][all]{%
\onecolumnSbottominarea[#1]{#2}{#3}{\textwidth}{\textheight}{0pt}{0pt}}

```

This command may only be used in the preamble.

```

\@onlypreamble{\onecolumnbottom}

```

`\onecolumnSbottom` Special case for **static frame**.

```

\newcommand*\onecolumnSbottom[2][all]{%
\onecolumnbottom[#1]{static}{#2}}

```

`\onecolumnDbottom` Special case for **dynamic frame**.

```

\newcommand*\onecolumnDbottom[2][all]{%
\onecolumnbottom[#1]{dynamic}{#2}}

```

General case of the above, but fit in specified area.

```

\onecolumnbottominarea Syntax:
\onecolumnbottominarea[\langle pages \rangle]{\langle type \rangle}{\langle H \rangle}{\langle w \rangle}{\langle h \rangle}{\langle x \rangle}{\langle y \rangle},
where \langle H \rangle is the \langle type \rangle frame's height. The area is defined by bottom left co-
ordinates (\langle x \rangle, \langle y \rangle) width \langle w \rangle, and height \langle h \rangle.
\newcommand*\onecolumnbottominarea[7][all]{%
\setlength{\@ff@staticH}{#3}%
\setlength{\columnheight}{#5}%
\addtolength{\columnheight}{-\@ff@staticH}%
\addtolength{\columnheight}{-\vcolumnsep}%
\iffvadjust\adjustheight{\columnheight}\fi%
\setlength{\@ff@tmp@y}{#5}%
\addtolength{\@ff@tmp@y}{-\columnheight}%
\addtolength{\@ff@tmp@y}{#7}%
\newframe[#1]{#2}{#4}{\@ff@staticH}{#6}{#7}%
\newflowframe[#1]{#4}{\columnheight}{#6}{\@ff@tmp@y}%
}

```

Again, this command may only be used in the preamble.

```
\@onlypreamble{\onecolumnbottominarea}
```

`\onecolumnSbottominarea` Special case for **static frame**.

```
\newcommand*{\onecolumnSbottominarea}[6][all]{%
\onecolumnbottominarea[#1]{static}{#2}{#3}{#4}{#5}{#6}}
```

`\onecolumnDbottominarea` Special case for **dynamic frame**.

```
\newcommand*{\onecolumnDbottominarea}[6][all]{%
\onecolumnbottominarea[#1]{dynamic}{#2}{#3}{#4}{#5}{#6}}
```

`\twocolumnbottom` Now for two **flow frames** side by side with a static frame underneath both of them. Firstly, the specific case where the area is the entire **typeblock**. Syntax:

```
\twocolumnbottom[⟨pages⟩]{⟨type⟩}{⟨H⟩}.
\newcommand*{\twocolumnbottom}[3][all]{%
\twocolumnSbottominarea[#1]{#2}{#3}{\textwidth}{\textheight}{0pt}{0pt}}
\@onlypreamble{\twocolumnbottom}
```

`\twocolumnSbottom` Special case for **static frame**.

```
\newcommand*{\twocolumnSbottom}[2][all]{%
\twocolumnbottom[#1]{static}{#2}}
```

`\twocolumnDbottom` Special case for **dynamic frame**.

```
\newcommand*{\twocolumnDbottom}[2][all]{%
\twocolumnbottom[#1]{dynamic}{#2}}
```

`\twocolumnbottominarea` Now for a general area. Syntax:

```
\twocolumnbottominarea[⟨pages⟩]{⟨type⟩}{⟨H⟩}{⟨w⟩}{⟨h⟩}{⟨x⟩}{⟨y⟩}.
\newcommand*{\twocolumnbottominarea}[7][all]{%
\setlength{\off@staticW}{#4}%
\setlength{\off@staticH}{#3}%
```

work out height of the flow frames

```
\setlength{\columnheight}{#5}%
\addtolength{\columnheight}{-\off@staticH}%
\addtolength{\columnheight}{-\vcolumnsep}%
\iffvadjust\adjustheight{\columnheight}\fi%
\newframe[#1]{#2}{\off@staticW}{\off@staticH}{#6}{#7}%
```

work out the *y* position of the flow frames

```
\setlength{\off@tmp@y}{#5}%
\addtolength{\off@tmp@y}{-\columnheight}%
\addtolength{\off@tmp@y}{#7}%
```

work out the widths of the flow frames

```
\setlength{\columnwidth}{\off@staticW}%
\addtolength{\columnwidth}{-\columnsep}%
\divide\columnwidth by 2\relax
```

work out the *x* offset of the second column

```
\setlength{\off@tmp@x}{\columnwidth}%
\addtolength{\off@tmp@x}{\columnsep}%
\addtolength{\off@tmp@x}{#6}%
\newflowframe[#1]{\columnwidth}{\columnheight}{#6}{\off@tmp@y}%
```

```

\setflowframe{\c@maxflow}{margin=left}%
\newflowframe[#1]{\columnwidth}{\columnheight}{\@ff@tmp@x}{\@ff@tmp@y}%
\setflowframe{\c@maxflow}{margin=right}%
}
\@onlypreamble{\twocolumnbottominarea}

```

`\twocolumnSbottominarea` Special case for **static frame**.

```

\newcommand*\twocolumnSbottominarea[6][all]{%
\twocolumnbottominarea[#1]{static}{#2}{#3}{#4}{#5}{#6}}

```

`\twocolumnDbottominarea` Special case for **dynamic frame**.

```

\newcommand*\twocolumnDbottominarea[6][all]{%
\twocolumnbottominarea[#1]{dynamic}{#2}{#3}{#4}{#5}{#6}}

```

Now for an arbitrary number of parallel **flow frames** with a **static frame** beneath all of them.

`\Ncolumnbottom` First make them fill the entire **typeblock**. Syntax:

```

\Ncolumnbottom[<pages>]{<type>}{<H>}.
\newcommand*\Ncolumnbottom[4][all]{%
\Ncolumnbottominarea[#1]{#2}{#3}{#4}{\textwidth}{\textheight}{Opt}{Opt}}
\@onlypreamble{\Ncolumnbottom}

```

`\NcolumnSbottom` Special case for **static frame**.

```

\newcommand*\NcolumnSbottom[3][all]{%
\Ncolumnbottom[#1]{static}{#2}{#3}}

```

`\NcolumnDbottom` Special case for **dynamic frame**.

```

\newcommand*\NcolumnDbottom[3][all]{%
\Ncolumnbottom[#1]{dynamic}{#2}{#3}}

```

`\Ncolumnbottominarea` Again check the user has requested a sensible number.

```

\newcommand*\Ncolumnbottominarea[8][all]{%
\ifnum#3>2\relax
\@Ncolumnbottominarea[#1]{#2}{#3}{#4}{#5}{#6}{#7}{#8}%
\else
\ifcase#3\relax
\PackageError{flowfram}{%
You have requested 0 flowframes!}{%
It does not make much sense to ask to create 0 flow frames}
\or
\onecolumnbottominarea[#1]{#2}{#4}{#5}{#6}{#7}{#8}%
\or
\twocolumnbottominarea[#1]{#2}{#4}{#5}{#6}{#7}{#8}%
\else
\PackageError{flowfram}{%
Can't create a negative number of flow frames!}{%
You have asked for \number#3 \space flow frames
which really doesn't make sense}%
\fi
\fi
}
\@onlypreamble{\Ncolumnbottominarea}

```

`\NcolumnSbottominarea` An arbitrary number of columns with a **static frame** underneath them all, filling the specified area.

```

\newcommand*{\NcolumnSbottominarea}[8][all]{%
\setlength{\off@staticH}{#4}%
work out height of the flow frames
\setlength{\columnheight}{#6}%
\addtolength{\columnheight}{-\off@staticH}%
\addtolength{\columnheight}{-\vcolumnsep}%
adjust the flow frame height so that it is a multiple of \baselineskip
\iffvadjust\adjustheight{\columnheight}\fi
\newframe[#1]{#2}{#5}{\off@staticH}{#7}{#8}%
work out the y offset of the flow frames
\setlength{\off@tmp@y}{#6}%
\addtolength{\off@tmp@y}{-\columnheight}%
\addtolength{\off@tmp@y}{#8}%
work out the widths of the flow frames
\@colN=#3\relax
\advance\@colN by -1\relax
\setlength{\columnwidth}{#5}%
\addtolength{\columnwidth}{-\@colN\columnsep}%
\divide\columnwidth by #3\relax
\setlength{\off@tmp@x}{#7}%
\@colN=0\relax
\loop
\advance\@colN by 1\relax
\newflowframe[#1]{\columnwidth}{\columnheight}{\off@tmp@x}{\off@tmp@y}%
work out the offset for the next column
\addtolength{\off@tmp@x}{\columnwidth}%
\addtolength{\off@tmp@x}{\columnsep}%
\ifnum\@colN<#3
\repeat
}

```

`\NcolumnSbottominarea` Specific case for **static frame**.

```

\newcommand*{\NcolumnSbottominarea}[1][all]{%
\Ncolumnbottominarea[#1]{static}}

```

`\NcolumnDbottominarea` Specific case for **dynamic frame**.

```

\newcommand*{\NcolumnDbottominarea}[1][all]{%
\Ncolumnbottominarea[#1]{dynamic}}

```

`\adjustheight` Given a height **#1** (a length), adjust it so that it is a multiple of `\baselineskip`.

```

\newcount\off@adjh
\newcommand*{\adjustheight}[1]{%
convert to an integer
\off@adjh=#1\relax
\divide\off@adjh by \baselineskip\relax
#1=\baselineskip\relax
\multiply#1 by \off@adjh\relax
}

```

`\adjustcolsep` Adjust the value of `\columnsep` so that the margins will fit between columns.

```

\newcommand*\adjustcolsep{%
\multiply\columnsep by 2\relax
\addtolength{\columnsep}{\marginparwidth}}

```

1.9.2 Backdrop Effects

Set up some commands to make **static frames** for different styles of backdrop.

`\vtwotone` Syntax:

```

\vtwotone[⟨pages⟩][⟨xoffset⟩]{⟨W1⟩}{⟨C1⟩}{⟨L1⟩}{⟨W2⟩}{⟨C2⟩}{⟨L2⟩}

```

where the first frame has width $\langle W1 \rangle$ with background colour $\langle C1 \rangle$ and label $\langle L1 \rangle$. The second frame has width $\langle W2 \rangle$ with background colour $\langle C2 \rangle$ and label $\langle L2 \rangle$. Unlike earlier commands, the x -offset is relative to the left page edge *not* the **typeblock**. This is because they are designed for backdrops, which tend to span the entire page. Note that the colour specs must be completely enclosed in braces. e.g. `{[gray]{0.5}}` *not* `[gray]{0.5}`.

Need a length to store the width of the **static frame**.

```

\newlength\@ff@staticW

```

Vertical two tone effect where the height of the static frames is equal to the paper height.

```

\newcommand*\vtwotone[1][all]{%
\def\ff@pages{#1}\vtwotone}

```

```

\newcommand*\@vtwotone[1][0pt]{\@vtwotonebottom{#1}{\paperheight}}

```

`\vtwotonebottom` Vertical two tone effect along the bottom of the page, of height $\langle H \rangle$. Syntax:

```

\vtwotonebottom[⟨pages⟩][⟨xoffset⟩]{⟨H⟩}{⟨W1⟩}{⟨C1⟩}{⟨L1⟩}{⟨W2⟩}{⟨C2⟩}{⟨L2⟩}

```

where the first frame starts at $\langle xoffset \rangle$.

```

\newcommand*\@vtwotonebottom[8]{%
\computeleftedgeodd{\ff@tmp@x}%
\if@twoside
\computeleftedgeeven{\ff@tmp@x@even}%
\else
\setlength{\ff@tmp@x@even}{\ff@tmp@x}%
\fi
\computebottomedge{\ff@tmp@y}%
\addtolength{\ff@tmp@x}{#1}%
\addtolength{\ff@tmp@x@even}{#1}%
\@nextvband{\ff@pages}{#2}{#3}{#4}{#5}%
\@nextvband{\ff@pages}{#2}{#6}{#7}{#8}%
}

```

```

\@onlypreamble{\vtwotone}

```

`\vtwotonebottom` Border strip along the bottom of the page

```

\newcommand*\vtwotonebottom[1][all]{%
\def\ff@pages{#1}\@vtwotonebottom}

```

```

\@onlypreamble{\vtwotonebottom}

```

```

\newcommand*\@vtwotonebottom[2][0pt]{\@vtwotonebottom{#1}{#2}}

```

`\vtwotonetop` Border strip along the top of the page

```

\newcommand*\vtwotonetop[1][all]{%
\def\ff@pages{#1}\@vtwotonetop

\newcommand*\@vtwotonetop[2][Opt]{\@vtwotonetop{#1}{#2}}

\newcommand*\@vtwotonetop[8]{%
\computeleftedgeodd{\ff@tmp@x}%
\if@twoside
\computeleftedgeeven{\ff@tmp@x@even}%
\else
\setlength{\ff@tmp@x@even}{\ff@tmp@x}%
\fi
\computetopedge{\ff@tmp@y}%
\addtolength{\ff@tmp@y}{-#2}%
\addtolength{\ff@tmp@x}{#1}%
\addtolength{\ff@tmp@x@even}{#1}%
\@nextvband{\ff@pages}{#2}{#3}{#4}{#5}%
\@nextvband{\ff@pages}{#2}{#6}{#7}{#8}%
}

```

`\@nextvband` Make next **static frame**. Syntax:

```

\@nextvband{<pages>}{<height>}{<width>}{<colour specs>}{<label>}

```

x and y offsets are given by `\ff@tmp@x` and `\ff@tmp@y`. On exit, `\ff@tmp@x` is set to the right border.

```

\newcommand*\@nextvband[5]{%
\setlength{\ff@staticW}{#3}%
\ifthenelse{equal{#5}{}}{%
\newstaticframe[#1]{\ff@staticW}{#2}{\ff@tmp@x}{\ff@tmp@y}}%
{\newstaticframe[#1]{\ff@staticW}{#2}{\ff@tmp@x}{\ff@tmp@y}[#5]}%
\expandafter\global\expandafter\setlength
\csname @sf@romannumeral@c@maxstatic @evenx@endcsname{%
\ff@tmp@x@even}%
\@setframecol#4\end{\c@maxstatic}{backcol}{sf}%
\addtolength{\ff@tmp@x}{\ff@staticW}%
\addtolength{\ff@tmp@x@even}{\ff@staticW}%
}

```

`\vNtone` Similarly for N colours. Syntax:

```

\vNtone[<pages>][<xoffset>]{<n>}{<W1>}{<C1>}{<L1>}\dots{<Wn>}{<Cn>}{<Ln>}

```

where the first frame has width $\langle W1 \rangle$ with background colour $\langle C1 \rangle$ and label $\langle L1 \rangle$ all the way up to the $\langle n \rangle$ th frame which has width $\langle Wn \rangle$, background colour $\langle Cn \rangle$ and **IDL** $\langle Ln \rangle$.

Keep track of which strip we are doing.

```

\newcount\@thisstrip

```

This command needs two optional arguments, so store first optional argument, and look for the next.

```

\newcommand*\vNtone[1][all]{%
\def\ff@pages{#1}\@vNtone}

```

`\@vNtone` Got the first argument, now get the next.

```

\newcommand*\@vNtone[2][Opt]{%
\@vNtone{#1}{#2}{\paperheight}}

```

`\@@vNtone` Vertical $\langle n \rangle$ tone aligned along the bottom of the page with height #3.

```

\newcommand*{\@@vNtone}[3]{%
\computeleftedgeodd{\@ff@tmp@x}%
\if@twoside
\computeleftedgeeven{\@ff@tmp@x@even}%
\else
\setlength{\@ff@tmp@x@even}{\@ff@tmp@x}%
\fi
\computebottomedge{\@ff@tmp@y}%
\addtolength{\@ff@tmp@x}{#1}%
\addtolength{\@ff@tmp@x@even}{#1}%
\@thisstrip=#2\relax
\setlength{\@ff@staticH}{#3}%
\@nextvNband%
}

```

`\@nextvNband` Recursively do the next strip.

```

\newcommand*{\@nextvNband}{%
\ifnum\@thisstrip>0\relax
\let\flf@next\@nextvNband
\else
\let\flf@next\relax
\fi
\advance\@thisstrip by -1\relax
\flf@next}

```

`\@@nextvNband` Do current strip, and go on to next one.

```

\newcommand*{\@@nextvNband}[3]{%
\@nextvband{\ff@pages}{\@ff@staticH}{#1}{#2}{#3}\@nextvNband}

\@onlypreamble{\vNtone}

```

`\vNtonebottom` Border strip along the bottom of the page. Same as above but user specifies the height.

```

\newcommand*{\vNtonebottom}[1][all]{%
\def\ff@pages{#1}\vNtonebottom}
\@onlypreamble{\vNtonebottom}

```

`\@vNtonebottom`

```

\newcommand*{\@vNtonebottom}[3][0pt]{%
\@@vNtone{#1}{#2}{#3}}

```

`\vNtonetop` Border strip along the top of the page. Again two optional arguments are required. Get first optional argument.

```

\newcommand*{\vNtonetop}[1][all]{%
\def\ff@pages{#1}\vNtonetop}
\@onlypreamble{\vNtonetop}

```

`\@vNtonetop` Get next optional argument.

```

\newcommand*{\@vNtonetop}[3][0pt]{%
\@@vNtonetop{#1}{#2}{#3}}

```

`\@@vNtonetop` Now get on with it. Again, it has to be done recursively.

```

\newcommand*{\@@vNtonetop}[3]{%
\computeleftedgeodd{\@ff@tmp@x}%
\if@twoside
\computeleftedgeeven{\@ff@tmp@x@even}%
\else
\setlength{\@ff@tmp@x@even}{\@ff@tmp@x}%
\fi
\computetopedge{\@ff@tmp@y}%
\addtolength{\@ff@tmp@y}{-#3}%
\addtolength{\@ff@tmp@x}{#1}%
\addtolength{\@ff@tmp@x@even}{#1}%
\@thisstrip=#2\relax
\setlength{\@ff@staticH}{#3}%
\@nextvNband%
}

```

`\htwotone` Now do horizontal strips. Syntax:

```

\htwotone[⟨pages⟩][⟨y offset⟩]{⟨H1⟩}{⟨C1⟩}{⟨L1⟩}{⟨H2⟩}{⟨C2⟩}{⟨L2⟩}
\newcommand*{\htwotone}[1][all]{%
\def\ff@pages{#1}\@htwotone}

```

`\@htwotone`

```

\newcommand*{\@htwotone}[1][Opt]{\@@htwotoneleft{#1}{\paperwidth}}

```

`\@@htwotoneleft` This is all done in much the same way as the vertical strips.

```

\newcommand*{\@@htwotoneleft}[8]{%
\computeleftedgeodd{\@ff@tmp@x}%
\if@twoside
\computeleftedgeeven{\@ff@tmp@x@even}%
\else
\setlength{\@ff@tmp@x@even}{\@ff@tmp@x}%
\fi
\computebottomedge{\@ff@tmp@y}%
\addtolength{\@ff@tmp@y}{#1}%
\@nexthband{\ff@pages}{#2}{#3}{#4}{#5}%
\@nexthband{\ff@pages}{#2}{#6}{#7}{#8}%
}

\@onlypreamble{\htwotone}

```

`\htwotoneleft` Two tone horizontal strips along left border Syntax: `\htwotoneleft[⟨pages⟩][⟨y offset⟩]{⟨width⟩}{⟨H1⟩}{⟨C1⟩}{⟨L1⟩}{⟨H2⟩}{⟨C2⟩}{⟨L2⟩}`

```

\newcommand*{\htwotoneleft}[1][all]{%
\def\ff@pages{#1}\@htwotoneleft}
\@onlypreamble{\htwotoneleft}

```

`\@htwotoneleft`

```

\newcommand*{\@htwotoneleft}[2][Opt]{\@@htwotoneleft{#1}{#2}}

```

`\htwotoneright` Two tone horizontal strips along right border

```

\newcommand*{\htwotoneright}[1][all]{%
\def\ff@pages{#1}\@htwotoneright}
\@onlypreamble{\htwotoneright}

```

```

\@htwotoneright
\newcommand*{\@htwotoneright}[2][Opt]{\@htwotoneright{#1}{#2}}

\@htwotoneright
\newcommand*{\@htwotoneright}[8]{%
\computerightedgeodd{\@ff@tmp@x}%
\if@twoside
\computerightedgeeven{\@ff@tmp@x@even}%
\else
\setlength{\@ff@tmp@x@even}{\@ff@tmp@x}%
\fi
\computebottomedge{\@ff@tmp@y}%
\addtolength{\@ff@tmp@y}{#1}%
\addtolength{\@ff@tmp@x}{-#2}%
\addtolength{\@ff@tmp@x@even}{-#2}%
\@nexthband{\ff@pages}{#2}{#3}{#4}{#5}%
\@nexthband{\ff@pages}{#2}{#6}{#7}{#8}%
}

\hNtone Now for  $\langle N \rangle$  coloured horizontal strips
\newcommand*{\hNtone}[1][all]{%
\def\ff@pages{#1}\@hNtone}
\@onlypreamble{\hNtone}

\@hNtone
\newcommand*{\@hNtone}[2][Opt]{%
\@hNtone{#1}{#2}{\paperwidth}}

\@hNtone
\newcommand*{\@hNtone}[3]{%
\computeleftedgeodd{\@ff@tmp@x}%
\if@twoside
\computeleftedgeeven{\@ff@tmp@x@even}%
\else
\setlength{\@ff@tmp@x@even}{\@ff@tmp@x}%
\fi
\computebottomedge{\@ff@tmp@y}%
\addtolength{\@ff@tmp@y}{#1}%
\@thisstrip=#2\relax
\setlength{\@ff@staticW}{#3}%
\@nexthNband%
}

\hNtoneleft Now for the N tone strips along the left border
\newcommand*{\hNtoneleft}[1][all]{%
\def\ff@pages{#1}\@hNtoneleft}
\@onlypreamble{\hNtoneleft}

\@hNtoneleft
\newcommand*{\@hNtoneleft}[3][Opt]{%
\@hNtone{#1}{#2}{#3}}

```

```

\hNtoneright  Border strip along the right border
               \newcommand*{\hNtoneright}[1][all]{%
               \def\ff@pages{#1}\hNtoneright}
               \@onlypreamble{\hNtoneright}

\@hNtoneright
               \newcommand*{\@hNtoneright}[3][Opt]{%
               \@@hNtoneright{#1}{#2}{#3}}

\@@hNtoneright
               \newcommand*{\@@hNtoneright}[3]{%
               \computerightedgeodd{\ff@tmp@x}%
               \if@twoside
               \computerightedgeeven{\ff@tmp@x@even}%
               \else
               \setlength{\ff@tmp@x@even}{\ff@tmp@x}%
               \fi
               \computebottomedge{\ff@tmp@y}%
               \addtolength{\ff@tmp@y}{#1}%
               \addtolength{\ff@tmp@x}{-#3}%
               \addtolength{\ff@tmp@x@even}{-#3}%
               \@thisstrip=#2\relax
               \setlength{\ff@staticW}{#3}%
               \@nexthNband%
               }

\@nexthband  Make next static frame. Syntax:
\@nexthband{<pages>}{<width>}{<height>}{<colour specs>}{<label>}
x and y offsets are given by \ff@tmp@x and \ff@tmp@y. On exit, \ff@tmp@y
is set to the top border.
               \newcommand*{\@nexthband}[5]{%
               \setlength{\ff@staticH}{#3}%
               \ifthenelse{equal{#5}{}}{%
               \newstaticframe[#1]{#2}{\ff@staticH}{\ff@tmp@x}{\ff@tmp@y}}%
               {\newstaticframe[#1]{#2}{\ff@staticH}{\ff@tmp@x}{\ff@tmp@y}[#5]}%
               \expandafter\global\expandafter
               \setlength\c@sf@romannumeral\c@maxstatic @evenx\endcsname{%
               \ff@tmp@x@even}%
               \@setframecol#4\end{\c@maxstatic}{backcol}{sf}%
               \addtolength{\ff@tmp@y}{\ff@staticH}%
               }

\@nexthNband  Get next horizontal strip recursively.
               \newcommand*{\@nexthNband}{%
               \ifnum\@thisstrip>0\relax
               \let\flf@next\@nexthNband%
               \else
               \let\flf@next\relax%
               \fi
               \advance\@thisstrip by -1\relax
               \flf@next}

\@@nexthNband

```

```
\newcommand*{\@nexthNband}[3]{%
\@nexthband{\ff@pages}{\@ff@staticW}{#1}{#2}{#3}\@nexthNband}
```

`\makebackgroundframe` Make one big **static frame** that covers the entire page. This command should come before all other commands that create **static frames**, otherwise it will obscure all the ones defined before it. Syntax:

```
\makebackgroundframe[\langle pages \rangle][\langle label \rangle].
\newcommand*{\makebackgroundframe}[1][all]{%
\ifnum\c@maxstatic>0\relax
\PackageWarning{flowfram}{Background frame is not
first static frame to be defined. All previously defined
static frames may be obscured.}%
\fi
\computeleftedgeodd{\@ff@tmp@x}%
\if@twoside
\computeleftedgeeven{\@ff@tmp@x@even}%
\else
\setlength{\@ff@tmp@x@even}{\@ff@tmp@x}%
\fi
\computebottomedge{\@ff@tmp@y}%
\newstaticframe[#1]{\paperwidth}{\paperheight}{\@ff@tmp@x}%
{\@ff@tmp@y}%
\expandafter\global\expandafter
\setlength\csname @sf@romannumeral\c@maxstatic @evenx\endcsname
{\@ff@tmp@x@even}}
```

1.9.3 Lines Between Frames

`\insertvrule` Insert a **static frame** between two frames with a vertical rule that goes from the maximum height of the highest to the minimum height of the lowest, equidistant from both frames. Syntax:
`\insertvrule[\langle y top \rangle][\langle y bottom \rangle]{\langle frame1 type \rangle}{\langle IDN2 \rangle}{\langle frame2 type \rangle}{\langle IDN2 \rangle}`.
The starred version uses **IDLs** instead of **IDNs**. The optional arguments indicate to continue above the highest point by `\langle y top \rangle` or continue below the lowest point by `\langle y bottom \rangle`.

`\ffcolumseprule` This has changed in v1.09. Define `\ffcolumseprule` and use instead of `\columnseprule`

```
\newlength\ffcolumseprule
\setlength{\ffcolumseprule}{2pt}
```

`\insertvrule` Determine whether or not the starred version is being used.
`\newcommand*{\insertvrule}{\@ifstar\@sinsertvrule\@insertvrule}`

`\@insertvrule` Two optional arguments required.
`\newcommand*{\@insertvrule}[1][0pt]{%
\@ifnextchar[{\@@insertvrule[#1]}{\@@insertvrule[#1][0pt]}}`

Need some lengths:

```
\newlength\@ff@left@x
\newlength\@ff@left@y
\newlength\@ff@left@evenx
```

```

\newlength\@ff@left@eveny
\newlength\@ff@left@width
\newlength\@ff@left@height

```

`\@@insertvrule` Arguments all accounted for. Convert the frame type into a number to make life easier

```

\def\@@insertvrule[#1][#2]#3#4#5#6{%
\ifthenelse{\equal{#3}{flow}}{%
\def\@ff@type@i{1}}{\ifthenelse{\equal{#3}{static}}{%
\def\@ff@type@i{2}}{\ifthenelse{\equal{#3}{dynamic}}{%
\def\@ff@type@i{3}}{\PackageError{flowfram}{Unknown frame
type '3'}{Available frame types are: 'flow', 'static'
or 'dynamic'}}}%
\ifthenelse{\equal{#5}{flow}}{%
\def\@ff@type@ii{1}}{\ifthenelse{\equal{#5}{static}}{%
\def\@ff@type@ii{2}}{\ifthenelse{\equal{#5}{dynamic}}{%
\def\@ff@type@ii{3}}{\PackageError{flowfram}{Unknown frame
type '5'}{Available frame types are: 'flow', 'static'
or 'dynamic'}}}%
\@@insert@vrule{#1}{#2}{\@ff@type@i}{#4}{\@ff@type@ii}{#6}%
}

```

`\@@insert@vrule` Insert a new **static frame** between the two specified frames. Check to make sure which one is on the left and which one is on the right. Syntax:

`\@@insert@vrule{<y top>}{<y bottom>}{<type ID>}{<IDN>}{<type ID>}{<IDN>}`.

```

\newcommand*\@@insert@vrule}[6]{%
\@ff@getdim{#3}{#4}%
\setlength{\@ff@left@x}{\ffareax}%
\setlength{\@ff@left@y}{\ffareay}%
\setlength{\@ff@left@width}{\ffareawidth}%
\setlength{\@ff@left@height}{\ffareaheight}%
\@ff@getdim{#5}{#6}%
\ifnum\@ff@left@x>\ffareax\relax
\@ff@swaplen{\@ff@left@x}{\ffareax}%
\@ff@swaplen{\@ff@left@y}{\ffareay}%
\@ff@swaplen{\@ff@left@evenx}{\ffareaevenx}%
\@ff@swaplen{\@ff@left@eveny}{\ffareaeveny}%
\@ff@swaplen{\@ff@left@width}{\ffareawidth}%
\@ff@swaplen{\@ff@left@height}{\ffareaheight}%
\fi
\setlength{\@ff@tmp@x}{\@ff@left@x}
\addtolength{\@ff@tmp@x}{\@ff@left@width}%
\setlength{\@ff@staticW}{\ffareax}%
\addtolength{\@ff@staticW}{-\@ff@tmp@x}%
\setlength{\@ff@staticH}{\@ff@left@y}%
\addtolength{\@ff@staticH}{\@ff@left@height}%
\setlength{\@ff@tmp@y}{\ffareay}%
\addtolength{\@ff@tmp@y}{\ffareaheight}%
\ifnum\@ff@tmp@y>\@ff@staticH
\setlength{\@ff@staticH}{\@ff@tmp@y}%
\fi
\ifnum\@ff@left@y<\ffareay\relax
\setlength{\@ff@tmp@y}{\@ff@left@y}%
\else

```

```

\setlength{\@ff@tmp@y}{\ff@areay}%
\fi
\addtolength{\@ff@staticH}{-\@ff@tmp@y}%
\newstaticframe{\@ff@staticW}{\@ff@staticH}%
{\@ff@tmp@x}{\@ff@tmp@y}%
\addtolength{\@ff@staticH}{#1}%
\addtolength{\@ff@staticH}{#2}%
\setstaticcontents{\c@maxstatic}{\hfill
\rule[-#2]{\ff@columnseprule}{\@ff@staticH}\hfill\mbox{}}%
\ifcase#3\relax
\or \edef\@ff@pages{\csname @ff@pages@\romannumeral#4\endcsname}%
\or \edef\@ff@pages{\csname @sf@pages@\romannumeral#4\endcsname}%
\or \edef\@ff@pages{\csname @df@pages@\romannumeral#4\endcsname}%
\fi
\setstaticframe{\c@maxstatic}{pages=\@ff@pages}%

```

check the difference between odd and even page co-ordinates and shift new frame in same direction. (Assumes the two original frames stay in the same relative position.)

```

\addtolength{\@ff@tmp@x}{\@ff@left@evenx}%
\addtolength{\@ff@tmp@x}{-\@ff@left@x}%
\addtolength{\@ff@tmp@y}{\@ff@left@eveny}%
\addtolength{\@ff@tmp@y}{-\@ff@left@y}%
\setstaticframe{\c@maxstatic}{evenx=\@ff@tmp@x,eveny=\@ff@tmp@y}%
}

```

`\@sinsertvrule` Starred version. Two optional arguments required.

```

\newcommand*{\@sinsertvrule}[1][0pt]{%
\@ifnextchar[{\@@sinsertvrule[#1]}{\@@sinsertvrule[#1][0pt]}}

```

`\@@sinsertvrule` Find out the frame types and their IDN.

```

\def\@@sinsertvrule[#1][#2]#3#4#5#6{%
\ifthenelse{\equal{#3}{flow}}{%
\def\@ff@type@i{1}\@flowframeid{#4}\@ff@tmpN=\ff@id}{%
\ifthenelse{\equal{#3}{static}}{%
\def\@ff@type@i{2}\@staticframeid{#4}\@ff@tmpN=\ff@id}{%
\ifthenelse{\equal{#3}{dynamic}}{%
\def\@ff@type@i{3}\@dynamicframeid{#4}\@ff@tmpN=\ff@id}{%
\PackageError{flowfram}{Unknown frame
type '#3'}{Available frame types are: 'flow', 'static'
or 'dynamic'}}}%
\ifthenelse{\equal{#5}{flow}}{%
\def\@ff@type@ii{1}\@flowframeid{#6}}{%
\ifthenelse{\equal{#5}{static}}{%
\def\@ff@type@ii{2}\@staticframeid{#6}}{%
\ifthenelse{\equal{#5}{dynamic}}{%
\def\@ff@type@ii{3}\@dynamicframeid{#6}}{%
\PackageError{flowfram}{Unknown frame
type '#5'}{Available frame types are: 'flow', 'static'
or 'dynamic'}}}%
\@@insertvrule{#1}{#2}{\@ff@type@i}{\@ff@tmpN}%
{\@ff@type@ii}{\ff@id}%
}

```

`\inserthrule` Now for a horizontal rule. Syntax similar to `\insertvrule`. Determine whether or not the starred version is being used.

```

\newcommand*{\inserthrule}{\@ifstar\@sinserthrule\@inserthrule}

```

`\@inserthrule` Two optional arguments required.

```

\newcommand*{\@inserthrule}[1][Opt]{%
\@ifnextchar[{\@@inserthrule[#1]}{\@@inserthrule[#1][Opt]}}

```

`\@@inserthrule` Arguments all accounted for. Convert the frame type into a number to make life easier

```

\def\@@inserthrule[#1][#2]#3#4#5#6{%
\ifthenelse{equal{#3}{flow}}{%
\def\@ff@type@i{1}}{\ifthenelse{equal{#3}{static}}{%
\def\@ff@type@i{2}}{\ifthenelse{equal{#3}{dynamic}}{%
\def\@ff@type@i{3}}{\PackageError{flowfram}{Unknown frame
type '#3'}{Available frame types are: 'flow', 'static'
or 'dynamic'}}}%
\ifthenelse{equal{#5}{flow}}{%
\def\@ff@type@ii{1}}{\ifthenelse{equal{#5}{static}}{%
\def\@ff@type@ii{2}}{\ifthenelse{equal{#5}{dynamic}}{%
\def\@ff@type@ii{3}}{\PackageError{flowfram}{Unknown frame
type '#5'}{Available frame types are: 'flow', 'static'
or 'dynamic'}}}%
\@insert@hrule{#1}{#2}{\@ff@type@i}{#4}{\@ff@type@ii}{#6}%
}

```

`\@@insert@hrule` Insert a new **static frame** between the two specified frames. Check to make sure which one is on the top and which one is on the bottom. Syntax:

```

\@@insert@hrule{<x left>}{<x right>}{<type ID>}{<IDN>}{<type ID>}{<IDN>}.
\newcommand*{\@@insert@hrule}[6]{%
\@ff@getdim{#3}{#4}%
\setlength{\@ff@left@x}{\ffareax}%
\setlength{\@ff@left@y}{\ffareay}%
\setlength{\@ff@left@width}{\ffareawidth}%
\setlength{\@ff@left@height}{\ffareaheight}%
\@ff@getdim{#5}{#6}%
\ifnum\@ff@left@y>\ffareay\relax
\@ff@swaplen{\@ff@left@x}{\ffareax}%
\@ff@swaplen{\@ff@left@y}{\ffareay}%
\@ff@swaplen{\@ff@left@width}{\ffareawidth}%
\@ff@swaplen{\@ff@left@height}{\ffareaheight}%
\fi
\setlength{\@ff@tmp@y}{\@ff@left@y}%
\addtolength{\@ff@tmp@y}{\@ff@left@height}%
\setlength{\@ff@staticH}{\ffareay}%
\addtolength{\@ff@staticH}{-\@ff@tmp@y}%
\setlength{\@ff@staticW}{\@ff@left@x}%
\addtolength{\@ff@staticW}{\@ff@left@width}%
\setlength{\@ff@tmp@x}{\ffareax}%
\addtolength{\@ff@tmp@x}{\ffareawidth}%
\ifnum\@ff@tmp@x>\@ff@staticW\relax
\setlength{\@ff@staticW}{\@ff@tmp@x}%
\fi

```

```

\ifnum\@ff@left@x<\ffareax\relax
  \setlength{\@ff@tmp@x}{\@ff@left@x}%
\else
  \setlength{\@ff@tmp@x}{\ffareax}%
\fi
\addtolength{\@ff@staticW}{-\@ff@tmp@x}%
\newstaticframe{\@ff@staticW}{\@ff@staticH}%
{\@ff@tmp@x}{\@ff@tmp@y}%
\addtolength{\@ff@staticW}{#1}%
\addtolength{\@ff@staticW}{#2}%
\setstaticcontents{\c@maxstatic}{%
\hspace*{-#1}\rule{\@ff@staticW}{\ffcolumnseprule}}%
\ifcase#3\relax
\or \edef\@ff@pages{\csname @ff@pages@romannumeral#4\endcsname}%
\or \edef\@ff@pages{\csname @sf@pages@romannumeral#4\endcsname}%
\or \edef\@ff@pages{\csname @df@pages@romannumeral#4\endcsname}%
\fi
\setstaticframe{\c@maxstatic}{pages=\@ff@pages}%
\addtolength{\@ff@tmp@x}{\@ff@left@evenx}%
\addtolength{\@ff@tmp@x}{-\@ff@left@x}%
\addtolength{\@ff@tmp@y}{\@ff@left@eveny}%
\addtolength{\@ff@tmp@y}{-\@ff@left@y}%
\setstaticframe{\c@maxstatic}{evenx=\@ff@tmp@x,eveny=\@ff@tmp@y}%
}

```

\@sinserthrule Starred version. Two optional arguments required.

```

\newcommand*{\@sinserthrule}[1][Opt]{%
\@ifnextchar[{\@@sinserthrule[#1]}{\@@sinserthrule[#1][Opt]}}

```

\@@sinserthrule Find out the frame types and their IDN.

```

\def\@@sinserthrule[#1][#2]#3#4#5#6{%
\ifthenelse{\equal{#3}{flow}}{%
\def\@ff@type@i{1}\@flowframeid{#4}\@ff@tmpN=\ff@id}{%
\ifthenelse{\equal{#3}{static}}{%
\def\@ff@type@i{2}\@staticframeid{#4}\@ff@tmpN=\ff@id}{%
\ifthenelse{\equal{#3}{dynamic}}{%
\def\@ff@type@i{3}\@dynamicframeid{#4}\@ff@tmpN=\ff@id}{%
\PackageError{flowfram}{Unknown frame
type '#3'}{Available frame types are: 'flow', 'static'
or 'dynamic'}}}%
\ifthenelse{\equal{#5}{flow}}{%
\def\@ff@type@ii{1}\@flowframeid{#6}}{%
\ifthenelse{\equal{#5}{static}}{%
\def\@ff@type@ii{2}\@staticframeid{#6}}{%
\ifthenelse{\equal{#5}{dynamic}}{%
\def\@ff@type@ii{3}\@dynamicframeid{#6}}{%
\PackageError{flowfram}{Unknown frame
type '#5'}{Available frame types are: 'flow', 'static'
or 'dynamic'}}}%
\@@insert@hrule[#1]{#2}{\@ff@type@i}{\@ff@tmpN}%
{\@ff@type@ii}{\ff@id}%
}

```

1.10 Putting Chapter Headings in Dynamic Frames

`\dfchaphead` Provide facility to make chapter headings appear in specified **dynamic frame**. I originally called this macro `\putchapterheadingsindynamicframe` which was descriptive, but overly long, so I changed it to the rather more cryptic name `\dfchaphead`. If the starred form is used, the frame is identified by **IDL**, the unstarred form identifies the frame **IDN**.

```
\newcommand*\dfchaphead}{%
\@ifstar\@sdynamicchap\@dynamicchap}
```

Define style for the chapter heading. These commands are should only be used when `\dfchaphead` has been used.

`\DFchapterstyle`

```
\newcommand{\DFchapterstyle}[1]{#1}
```

`\DFschapterstyle`

```
\newcommand{\DFschapterstyle}[1]{#1}
```

`\@dynamicchap` Unstarred version.

```
\newcommand{\@dynamicchap}[1]{%
\@ifundefined{chapter}{\PackageError{flowfram}{Chapters aren't
defined}{The document
class you are using does not define chapters}}{%
\let\@ff@OLDmakechapterhead\@makechapterhead
\let\@ff@OLDmakeschapterhead\@makeschapterhead
\renewcommand{\DFchapterstyle}[1]{\@ff@OLDmakechapterhead{##1}}%
\renewcommand{\DFschapterstyle}[1]{\@ff@OLDmakeschapterhead{##1}}%
}%
\edef\@makechapterhead##1{%
\noexpand\@setdynamiccontents{\number#1}{%
\noexpand\DFchapterstyle{##1}}}%
\edef\@makeschapterhead##1{%
\noexpand\@setdynamiccontents{\number#1}{%
\noexpand\DFschapterstyle{##1}}}%
}}
```

`\@sdynamicchap` Starred form.

```
\newcommand{\@sdynamicchap}[1]{%
\@dynamicframeid{#1}\@dynamicchap{\ff@id}}
```

There is no facility for placing other sectional types in **dynamic frames**. This is because, either (1) the sectioning command does not start a new page, in which case there is no way of telling where exactly the new section will start, and having a section title in some other location on the page is ambiguous, and would really confuse the reader, or (2) in the case of `\part` in report or book class files, the title appears on a page of its own, so where is the point in putting it in a **dynamic frame**?

1.11 Thumbtabs

Define counter to keep track of total number of thumbtabs.

```
\newcounter{maxthumbtabs}
```

`\defaultthumbtabtype` Check to see if chapters are defined, if they are make thumbtabs correspond to chapters, otherwise make thumbtabs correspond to sections.

```

\ifundefined{chapter}{%
\newcommand*\defaultthumbtabtype{section}}{
\newcommand*\defaultthumbtabtype{chapter}
}

```

`\@ttb@type` Section type to assign to thumbtabs.

```

\newcommand*\@ttb@type{\defaultthumbtabtype}

```

`\makethumbtabs` Make the thumbtabs. Read in information from .ttb file, and open it for output.
Syntax:
`\makethumbtabs[y offset][height][sec type]`.
First check to see if there is a second optional argument.

```

\newcommand*\makethumbtabs[2][0pt]{%
\@ifnextchar[{\@makethumbtabs[#1]{#2}}{%
\@makethumbtabs[#1]{#2}[\defaultthumbtabtype]}%
}

```

`\@makethumbtabs` Now all arguments are known, first redefine the appropriate sectioning command, then input the ttb file, and create the thumbtabs.

```

\def\@makethumbtabs[#1]#2[#3]{%
\@ifundefined{#3}{\PackageError{flowfram}{%
Unknown section type '#3'}{}}{%
\renewcommand*\@ttb@type{#3}%
\ifthenelse{\equal{#3}{chapter}}{\@makethumbchapter}{%
\ifthenelse{\equal{#3}{part}}{\@makethumbpart}{%
\@makethumbsection{#3}}}%
\@starttoc{ttb}%
\@dothumbtabs{#1}{#2}%
}

```

`\@makethumbchapter` If thumbtabs correspond to chapters, redefine `\@chapter` so that each unstarred chapter writes an entry to the .ttb file.

```

\newcommand*\@makethumbchapter{%
\let\@ttb@old@chapter\@chapter
\def\@chapter[#1]##2{%
\@ttb@old@chapter[#1]{##2}%
\addtocontents{ttb}{\protect\thumbtab
{\thepage}{\thechapter}{##1}{chapter.\thechapter}}%
\@afterheading
}}

```

`\@makethumbpart` For parts in books or reports, the thumbtab needs to be saved after the part counter has been incremented, but before the page break so that the page number and part numbers are correct. If `\@endpart` is not defined, then the document class probably does not start a new page after `\part`. (This can't be guaranteed for non standard class files, but there's nothing that can be done about that.) If this happens, just redefine `\@part`, and hope for the best.

```

\newcommand*\@makethumbpart{%
\let\@ttb@old@part\@part
\ifundefined{endpart}{%

```

```

\def\@part[##1]##2{\@ttb@old@part[##1]{##2}%
\addtocontents{ttb}{\protect\thumbtab
  {\thepage}{\thepart}{##1}{part.\thepage}}%
\@afterheading}{}%
\let\@ttb@old@endpart\@endpart
\def\@part[##1]##2{%
\def\@parttitle{##1}%
\@ttb@old@part[##1]{##2}%
}%
\def\@endpart{%
\addtocontents{ttb}{%
\protect\thumbtab{\thepage}%
{\thepart}{\@parttitle}{part.\thepage}}%
\@ttb@old@endpart
}}

```

`\@makethumbsection` Thumbtabs defined for one of the remaining standard sectioning commands. Since these commands use `\@startsection`, it is necessary to redefine `\@sect` to add the thumbtab information to the .ttb file.

```

\newcommand*\@makethumbsection[1]{%
\let\@ttb@old@sect=\@sect
\def\@sect##1##2##3##4##5##6[##7]##8{%
\@ttb@old@sect{##1}{##2}{##3}{##4}{##5}{##6}[##7]{##8}%
\ifthenelse{\equal{##1}{#1}}{%
\addtocontents{ttb}{%
\protect\thumbtab{\thepage}{\csname the#1\endcsname}%
{##7}{#1.\csname the#1\endcsname}}%
\@afterheading}{}%
}}

```

`\thumbtab` The thumbtab file, .ttb, will have a series of `\thumbtab` commands, when this file is read in, just store the information for now.

```

\newcommand{\thumbtab}[4]{%
\stepcounter{maxthumbtabs}%
\expandafter
\gdef\csname thumbtab@pages@\romannumeral\c@maxthumbtabs\endcsname
{#1}%
\expandafter
\gdef\csname thumbtab@num@\romannumeral\c@maxthumbtabs\endcsname
{#2}%
\expandafter
\gdef\csname thumbtab@title@\romannumeral\c@maxthumbtabs\endcsname
{#3}%
\expandafter
\gdef\csname thumbtab@link@\romannumeral\c@maxthumbtabs\endcsname
{#4}}

```

`\@dothumbtabs` Once the thumbtab information has been read in and stored in the thumbtab macros, create the thumbtabs using this information. First need to work out the **page ranges** between each thumbtab. If the following thumbtab starts on the same page as the previous one, leave the page variable as a single number (this may happen if the thumbtabs correspond to sections rather than chapters). If the following thumbtab starts on a different page to the one before it, the

preceding thumbtab page variable so be a range from its own initial page up to the page before the next thumbtab starts. The final thumbtab has an open ended range. This final thumbtab will continue to be displayed until cancelled by `\disablethumbtabs`.

Syntax: `\@dothumbtabs{<y offset>}{<height>}`.

```
\newcommand*{\@dothumbtabs}[2]{%
\@colN=0\relax
\whiledo{\@colN<\c@maxthumbtabs}{%
\advance\@colN by 1\relax
\edef\ff@pages{%
\csname thumbtab@pages@\romannumeral\@colN\endcsname}%
\ifnum\@colN=\c@maxthumbtabs
\expandafter
\xdef\csname thumbtab@pages@\romannumeral\@colN\endcsname{%
\ff@pages,>\ff@pages}%
\else
\advance\@colN by 1\relax
\edef\ff@endpage{%
\csname thumbtab@pages@\romannumeral\@colN\endcsname}%
\advance\@colN by -1\relax
\@ff@tmpN=\ff@endpage\relax
\advance\@ff@tmpN by -1\relax
\ifnum\@ff@tmpN>\ff@pages
\expandafter
\xdef\csname thumbtab@pages@\romannumeral\@colN\endcsname{%
\ff@pages-\number\@ff@tmpN}%
\fi
\fi
}%
\@dothumbtabs{#1}{#2}%
}
```

`\thumbtabwidth` Default thumbtab width.

```
\newlength{\thumbtabwidth}
\setlength{\thumbtabwidth}{1cm}
```

`\thumbtabindexformat` Thumbtab format. If hyperlinks have been defined, use a hyperlink in the thumbtab index. Syntax: `\thumbtabindexformat{<link>}{<text>}{<height>}`

```
\@ifundefined{hyperlink}{%
\newcommand{\thumbtabindexformat}[3]{%
\thumbtabformat{#2}{#3}}{%
\newcommand{\thumbtabindexformat}[3]{%
\hyperlink{#1}{\thumbtabformat{#2}{#3}}}
}
```

`\thumbtabformat` Individual thumbtab format. If rotating has been disabled, stack the letters vertically (this doesn't look very good). Syntax: `\thumbtabformat{<text>}{<height>}`

```
\newcommand{\thumbtabformat}[2]{%
\if@ttb@rotate
\rotatebox{-90}{\parbox[c][\thumbtabwidth]{#2}{%
\centering#1}}%
\else
\parbox[c][#2]{\thumbtabwidth}{%
\centering#1}}%
```

```

\centering\@ttb@stack{#1}}%
\fi}

\@flf@subsp Substutute spaces for \space. Stores resulting text in \@flf@subsptext which
should be set to empty before use.
\def\@flf@subsp#1 #2{%
\expandafter\flf@ta\expandafter{\@flf@subsptext}%
\flf@tb{#1}%
\edef\@flf@subsptext{\the\flf@ta\the\flf@tb}%
\def\@flf@tmp{#2}%
\ifx\@flf@tmp\@nnil
\let\@flf@donextsubsp=\@gobble
\else
\expandafter\flf@ta\expandafter{\@flf@subsptext}%
\edef\@flf@subsptext{\the\flf@ta\noexpand\space}%
\let\@flf@donextsubsp=\@flf@subsp
\fi
\@flf@donextsubsp{#2}%
}

\@ttb@stack Stack letters vertically. Any spaces first need to be substituted with \space,
otherwise they will be ignored.
\newcommand{\@ttb@stack}[1]{%
\def\@flf@subsptext{}%
\expandafter\@flf@subsp#1 \@nil\relax
\begin{tabular}{l}%
\expandafter\@ttb@stack\@flf@subsptext\@nil\relax
\end{tabular}}

\@@ttb@stack
\def\@@ttb@stack#1#2{%
\def\@flf@tmp{#1}%
\ifx\@flf@tmp\@nnil
\let\flf@next\relax
\else
#1\\%
\def\@flf@tmp{#2}%
\ifx\@nnil#2\relax
\let\flf@next\@gobble
\else
\let\flf@next\@@ttb@stack
\fi
\fi
\flf@next{#2}}

\@greyscale Count register to compute the grey scale.
\newcount\@greyscale

\@@dothumbtabs Once the page range have been sorted, create the dynamic frames associated with
each thumbtab. Thumbtabs will initially have a grey background, but this can
be changed by the user. Each thumbtab is given an IDL thumbtab $\langle n \rangle$  where  $\langle n \rangle$ 
is the index of the thumbtab (starting from 1 for the topmost thumbtab.) Each

```

frame in the thumbtab index is given an **IDL** thumbtabindex $\langle n \rangle$, where $\langle n \rangle$ is as before.

```
\newcommand{\@@dothumbtabs}[2]{%
\setlength{\@ff@tmp@y}{\textheight}%
\addtolength{\@ff@tmp@y}{-#2}%
\addtolength{\@ff@tmp@y}{-#1}%
\computerightedgeodd{\@ff@tmp@x}%
\addtolength{\@ff@tmp@x}{-\thumbtabwidth}%
\computeleftedgeeven{\@ff@tmp@x@even}%
\@ff@tmpN=0\relax
\whiledo{\@ff@tmpN<\c@maxthumbtabs}{%
\advance\@ff@tmpN by 1\relax
\@greyscale=\@ff@tmpN\relax
\multiply\@greyscale by 60\relax
\divide\@greyscale by \c@maxthumbtabs
\advance\@greyscale by 25\relax
\edef\@ff@greyscale{0.\number\@greyscale}%
```

Thumbtab

```
\newdynamicframe[none]{\thumbtabwidth}{#2}%
{\@ff@tmp@x}{\@ff@tmp@y}[thumbtab\@number\@ff@tmpN]%
\expandafter\global\expandafter
\setlength\csname @df@romannumeral\c@maxdynamic @evenx\endcsname
{\@ff@tmp@x@even}%
```

set the contents of the dynamic frame

```
\ifthenelse{\boolean{@ttb@title}\and\boolean{@ttb@num}}{%
\expandafter
\xdef\csname @dynamicframe@romannumeral\c@maxdynamic\endcsname{%
\noexpand\thumbtabformat{%
\csname thumbtab@num@romannumeral\@ff@tmpN\endcsname\
\csname thumbtab@title@romannumeral\@ff@tmpN\endcsname
}{#2}}}%
}%
\if@ttb@title
\expandafter
\xdef\csname @dynamicframe@romannumeral\c@maxdynamic\endcsname{%
\noexpand\thumbtabformat{%
\csname thumbtab@title@romannumeral\@ff@tmpN\endcsname
}{#2}}}%
\fi
\if@ttb@num
\expandafter
\xdef\csname @dynamicframe@romannumeral\c@maxdynamic\endcsname{%
\noexpand\thumbtabformat{%
\csname thumbtab@num@romannumeral\@ff@tmpN\endcsname
}{#2}}}%
\fi
}%
\expandafter
\xdef\csname @df@backcol@romannumeral\c@maxdynamic\endcsname
{[gray]{\@ff@greyscale}}
```

Thumbtab index

```
\newdynamicframe[none]{\thumbtabwidth}{#2}%
```

```

    {\@ff@tmp@x}{\@ff@tmp@y}[thumbtabindex\number\@ff@tmpN]%
\expandafter\global\expandafter
\setlength\csname @df@romannumeral\c@maxdynamic @evenx\endcsname
{\@ff@tmp@x@even}%
\expandafter
set the contents of the dynamic frame
\ifthenelse{\boolean{@ttb@title}\and\boolean{@ttb@num}}{%
\expandafter
\xdef\csname @dynamicframe@romannumeral\c@maxdynamic\endcsname{%
\noexpand\thumbtabindexformat{%
\csname thumbtab@link@romannumeral\@ff@tmpN\endcsname}{%
\csname thumbtab@num@romannumeral\@ff@tmpN\endcsname\
\csname thumbtab@title@romannumeral\@ff@tmpN\endcsname
}{#2}}%
}%
\if@ttb@title
\expandafter
\xdef\csname @dynamicframe@romannumeral\c@maxdynamic\endcsname{%
\noexpand\thumbtabindexformat{%
\csname thumbtab@link@romannumeral\@ff@tmpN\endcsname}{%
\csname thumbtab@title@romannumeral\@ff@tmpN\endcsname
}{#2}}%
\fi
\if@ttb@num
\expandafter
\xdef\csname @dynamicframe@romannumeral\c@maxdynamic\endcsname{%
\noexpand\thumbtabindexformat{%
\csname thumbtab@link@romannumeral\@ff@tmpN\endcsname}{%
\csname thumbtab@num@romannumeral\@ff@tmpN\endcsname
}{#2}}%
\fi
}%
\expandafter
\xdef\csname @df@backcol@romannumeral\c@maxdynamic\endcsname
{[gray]{\@ff@greyscale}}
\addtolength{\@ff@tmp@y}{-#2}%
}%
}%

```

`\enablethumbtabs` Enable thumbtabs. Once the IDN is obtained for the first thumbtab, the rest can be found by incrementing the number by 2 (the frames in between correspond to the thumbtab index.)

```

\newcommand*{\enablethumbtabs}{%
\ifnum\c@maxthumbtabs>0
\@ff@tmpN=0\relax
\@dynamicframeid{thumbtab1}%
\whiledo{\@ff@tmpN<\c@maxthumbtabs}{%
\advance\@ff@tmpN by 1\relax
thumbtab
\edef\@ff@pages{\csname thumbtab@pages@romannumeral\@ff@tmpN\endcsname}%
\@setdynamicframe{\ff@id}{pages=\@ff@pages}%
\advance\ff@id by 2\relax
}%

```

```

\else\PackageWarning{flowfram}{No thumb tabs defined}\fi}

\disablethumbtabs Disable all thumbtabs.
\newcommand*{\disablethumbtabs}{%
\ifnum\c@maxthumbtabs>0
\ff@tmpN=0\relax
\@dynamicframeid{thumbtab1}%
\whiledo{\ff@tmpN<\c@maxthumbtabs}{%
\advance\ff@tmpN by 1\relax
thumbtab
\expandafter\xdef\csname @df@pages@\romannumeral\ff@id\endcsname
{none}%
\advance\ff@id by 1\relax
thumbtab index
\expandafter\xdef\csname @df@pages@\romannumeral\ff@id\endcsname
{none}%
\advance\ff@id by 1\relax
}\fi}

\thumbtabindex Show thumbtab index on current page. The \ff@doafter bit circumvents the
problem of duplicate page numbers, as the table of contents is quite frequently on
page i while the first chapter starts on page 1.
\newcommand*{\thumbtabindex}{%
\ifnum\c@maxthumbtabs>0\relax
\ff@tmpN=0\relax
\@dynamicframeid{thumbtabindex1}%
\whiledo{\ff@tmpN<\c@maxthumbtabs}{%
\advance\ff@tmpN by 1\relax
\expandafter
\xdef\csname @df@pages@\romannumeral\ff@id\endcsname{\c@page}%
\edef\ff@doafter{%
\noexpand\afterpage{%
\noexpand\setdynamicframe{\number\ff@id}{pages=none}}
\ff@doafter
\advance\ff@id by 2\relax
}\fi}

\setthumbtab Modify the settings for all the thumbtabs (including thumbtab index). Since the
thumbtabs are dynamic frames you could just use \setdynamicframe, however,
the thumbtabs will not be generated on the first run, as there will be no information
in the ttb file, so \setdynamicframe would generate an error. \setthumbtab will
only give a warning message if it can not find the thumbtab. The argument #1 is
the index of the thumbtab (starting from 1), the second argument #2 is the frame
settings.
\newcommand{\setthumbtab}[2]{%
\ifthenelse{\equal{#1}{all}}{%
\ff@tmpN=0\relax
\whiledo{\ff@tmpN<\c@maxthumbtabs}{%
\advance\ff@tmpN by 1\relax
\@setthumbtab{\ff@tmpN}{#2}}{%
\for\@ttb@id:=#1\do{\@setthumbtab{\@ttb@id}{#2}}}}

```

<code>\setthumtab</code>	Set individual thumtab and its index tab. <pre> \newcommand{\setthumtab}[2]{% % check if this thumtab exists \ifthenelse{(\c@maxthumtaps<#1\)\ or \(#1<1\)}{% \PackageWarning{flowfram}{Can't find thumtab number '#1', ttb file may not be up-to-date}}{% \@dynamicframeid{thumtab\number#1}% \@setdynamicframe{\ff@id}{#2}% \@dynamicframeid{thumtabindex\number#1}% \@setdynamicframe{\ff@id}{#2}}} </pre>
<code>\setthumtabindex</code>	Only change settings for the thumtab index. This can take a comma-separated number list. <pre> \newcommand{\setthumtabindex}[2]{% \ifthenelse{\equal{#1}{all}}{% \@ff@tmpN=0\relax \whiledo{\@ff@tmpN<\c@maxthumtaps}{% \advance\@ff@tmpN by 1\relax \setthumtabindex{\@ff@tmpN}{#2}}}% \for\@ttb@id:=#1\do{\setthumtabindex{\@ttb@id}{#2}}} </pre>
<code>\@setthumtabindex</code>	Change setting for individual thumtab index entry. <pre> \newcommand{\@setthumtabindex}[2]{% % check if this thumtab exists \ifthenelse{(\c@maxthumtaps<#1\)\ or \(#1<1\)}{% \PackageWarning{flowfram}{Can't find thumtab number '\number#1', ttb file may not be up-to-date}}{% \@dynamicframeid{thumtabindex\number#1}% \@setdynamicframe{\ff@id}{#2}}} </pre>
<code>\tocandhumtabindex</code>	Do both the table of contents and the thumtab index <pre> \newcommand*{\tocandthumtabindex}{% \aligntoctrue \tableofcontents \thumtabindex \aligntofalse } </pre>

1.12 Minitocs

<code>\@ttb@minitoc</code>	Sectioning type for the minitoc, by default it is the same as the thumtaps <pre> \newcommand*{\@ttb@minitoc}{\@ttb@type} </pre>
<code>\@starttoc</code>	In order to align the table of contents with the thumtaps, or to use minitocs, the toc information must be stored, rather than simply input. Therefore, modify <code>\@starttoc</code> so that it can store the contents of the file. <code>\if@storetoc</code> is used to determine whether to store the contents, or act as normal. <pre> \let\@ttb@old@starttoc\@starttoc \newif\if@storetoc \@storetocfalse \renewcommand*{\@starttoc}[1]{% \if@storetoc \@ttb@storetoc{#1}% </pre>

```

\else
  \@ttb@old@starttoc{#1}%
\fi}

\@ttb@storetoc store the contents of the file with the given extension
  \newcommand*{\@ttb@storetoc}[1]{%
    \begingroup
    \makeatletter
    \@storefileconts{\jobname.#1}%
    \if@filesw
      \expandafter\newwrite\csname tf@#1\endcsname
      \immediate\openout\csname tf@#1\endcsname\jobname.#1\relax
    \fi
    \@nobreakfalse
    \endgroup}

\@storefileconts store the contents of named file, if it exists.
  \newcommand*{\@storefileconts}[1]{\IfFileExists{#1}{%
    \@storefileconts\@filef@und}{%
    \PackageInfo{flowfram}{No file #1.}}}

store the number of units corresponding to the thumbtab type, and minitoc units.
These will usually have the same value, but this is not always guaranteed.

\c@maxtocunits Total number of toc units
  \newcount\c@maxtocunits

\c@maxminitoc Total number of minitoc units
  \newcount\c@maxminitoc

@@storefileconts Read each line in from the file, and add to the contents list.
  \newcommand{\@@storefileconts}[1]{%
    \@ifundefined{\@ttb@minitoclevel}{\@ttb@minitoclevel=6\relax}{%
    \expandafter\@ttb@minitoclevel\expandafter
      =\csname @ttb@\@ttb@minitoclevel\endcsname}%
    \newread\@ttb@toc
    \openin\@ttb@toc=#1\relax
    \c@maxtocunits=0\relax
    \c@maxminitoc=0\relax
    \whiledo{\not\boolean{eof}}{\@ttb@toc}{%
      \read\@ttb@toc to\tocline
      \@addtotoclist{\tocline}{\c@maxtocunits}%
    }%
    \closein\@ttb@toc}

\@addtotoclist Before each line is added to the contents list, it is first checked to see whether
the line starts with \contentsline. If it does, then check to see if the sectioning
type corresponds to the thumbtab level. If it does, then start a new list. There
will be \c@maxtocunits lists, each one corresponding to each thumbtab group. In
addition, each contents line needs to be added to the minitoclists, but only if the
sectioning type level is greater than \@ttb@minitoclevel. The number of minitoc
lists is given by \c@maxminitoc.
  \newif\if@contentsline

```

```

\newcount\@ttb@level
\newcount\@ttb@minitoclevel

\newcommand{\@addtotoclist}[2]{%
\expandafter\@checkcontentsline#1\end
\if@contentsline
\expandafter\@gettype#1\end
\ifthenelse{\equal{\@ttb@contstype}{\@ttb@type}}{%
\global\advance#2 by 1\relax
}{%
}%
\fi
\@ifundefined{toc@\romannumeral#2}{%
\flf@ta=\expandafter{#1}%
\expandafter\xdef\csname @toc@\romannumeral#2\endcsname{\the\flf@ta}}{%
\flf@ta=\expandafter{#1}%
\flf@tb=\expandafter\expandafter\expandafter{\csname @toc@\romannumeral#2\endcsname}%
\expandafter\xdef\csname @toc@\romannumeral#2\endcsname{\the\flf@tb\the\flf@ta}}%

```

now do minitoc stuff. If the sectioning type is unknown, assume it comes last

```

\if@minitoc
\if@contentsline
\@ifundefined{\@ttb@contstype}{\@ttb@level=6}{%
\@ttb@level=\csname @ttb@\@ttb@contstype @level\endcsname}%
\relax
\ifnum\@ttb@level=\@ttb@minitoclevel
\global\advance\c@maxminitoc by 1\relax
\expandafter
\gdef\csname @minitoc@\romannumeral\c@maxminitoc\endcsname{}%
}else
\ifnum\@ttb@level>\@ttb@minitoclevel
\flf@ta=\expandafter{#1}\relax
\flf@tb=\expandafter\expandafter\expandafter
{\csname @minitoc@\romannumeral\c@maxminitoc\endcsname}\relax
\expandafter
\xdef\csname @minitoc@\romannumeral\c@maxminitoc\endcsname{%
\the\flf@tb\the\flf@ta}
\fi
\fi
\fi
\fi
}

```

Is there already a way of determining the sectioning level from its name?

```

\def\@ttb@part@level{-1}
\def\@ttb@chapter@level{0}
\def\@ttb@section@level{1}
\def\@ttb@subsection@level{2}
\def\@ttb@subsubsection@level{3}
\def\@ttb@paragraph@level{4}
\def\@ttb@subparagraph@level{5}

```

```

\@checkcontentsline Check to see if line starts with \contentsline
\long\def\@checkcontentsline#1#2\end{%

```

```

\ifx#1\contentsline
  \@contsline>true
\else
  \@contsline>false
\fi}

\@gettype Given that the line starts with \contentsline, extract the first argument of
\contentsline to get the sectioning type.
\def\@gettype\contentsline#1#2\end{%
\def\@ttb@contstype{#1}}

\tableofcontents Modify \tableofcontents. It first stores the contents of the toc file, and then,
either simply prints it on the page (so it appears no different to the standard
\tableofcontents), or it prints it out so that each thumbtab unit has the same
height as the thumbtabs. Note: this assumes that the actual table of contents
starts at the same height as the thumbtabs. The thumbtab vertical position may
need to be adjusted to compensate for space taken up by the contents title.

\newif\ifaligntoc
\aligntocfalse

\let\@ttb@old@tableofcontents\tableofcontents
\renewcommand{\tableofcontents}{%
\@storetoctrue
\@ttb@old@tableofcontents
\ifaligntoc
  \@printalignedtoc
\else
  \@printtoc
\fi
\@storetocfalse
\global\c@minitoc=0\relax}

\beforeminitocskip Vertical space to add before minitoc.
\newlength\beforeminitocskip
\setlength{\beforeminitocskip}{0pt}

\afterminitocskip Vertical space to add after minitoc.
\newlength\afterminitocskip
\setlength{\afterminitocskip}{\baselineskip}

\dominitoc Do the minitoc for unit #1. Check first that minitocs have been enabled.
\newcommand*{\dominitoc}[1]{%
\if@minitoc \dominitoc{#1}\fi}
\newcommand*{\dominitoc}[1]{\dominitoc{#1}}

\minitocstyle Style in which to display the minitoc.
\newcommand{\minitocstyle}[1]{\normalfont\normalsize\normalcolor
#1}

\@@dominitoc Now do the actual minitoc for unit #1.
\newcommand*{\@@dominitoc}[1]{%
{\minitocstyle{%
\vskip\beforeminitocskip

```

```

\csname @minitoc@romannumeral#1\endcsname}}
\vskip\afterminitocskip}

\appenddfminitoc Modify \dominitoc so that the minitoc is appended to specified dynamic frame.
Starred version uses dynamic frame IDL, unstarred version uses dynamic frame IDN. I originally called this macro \appendminitocdynamicframe but decided
it was too long, for I've opted instead for a slightly more cryptic name.

\newcommand*\appenddfminitoc{%
\renewcommand{\beforeminitocskip}{\baselineskip}%
\@ifstar\@sappendminitocdf\@appendminitocdf}

\@sappendminitocdf Starred version

\newcommand*\@sappendminitocdf[1]{%
\renewcommand{\@dominitoc}[1]{%
\@sappenddynamic{#1}{\@dominitoc{##1}}}}

\@appendminitocdf Unstarred version

\newcommand*\@appendminitocdf[1]{%
\renewcommand{\@dominitoc}[1]{%
\@appenddynamic{#1}{\@dominitoc{##1}}}}

\@printtoc Do the table of contents, which has been stored in \c@maxtocunits macros. (or
possibly \c@maxtocunits + 1, if information was added before the first group—
which corresponds to \colN=0.)

\newcommand*\@printtoc{%
\colN=0\relax
\csname @toc@romannumeral\colN\endcsname
\whiledo{\colN<\c@maxtocunits}{%
\advance\colN by 1\relax
\csname @toc@romannumeral\colN\endcsname}}

\@printalignedtoc Print the table of contents so that each unit is has vertical height the same as the
height of the thumbtabs. Note that you may have to adjust the vertical offset of
the thumbtabs (in \makethumbtabs) in order to make them correctly aligned.

\newcommand*\@printalignedtoc{%
\@ff@tmpN=0\relax
\@ifundefined{toc@romannumeral\@ff@tmpN}{%
}%
\csname @toc@romannumeral\@ff@tmpN\endcsname
\par\noindent\hrulefill
}%
\whiledo{\@ff@tmpN<\c@maxtocunits}{%
\advance\@ff@tmpN by 1\relax
\ifnum\@ff@tmpN>\c@maxthumbtabs
\csname @toc@romannumeral\@ff@tmpN\endcsname
\else
\@dynamicframeid{thumbtabindex\@ff@tmpN}%
\expandafter\expandafter\expandafter
\@ff@getstaticpos\csname @df@dim@romannumeral\@ff@id\endcsname
\vbox to \@ff@tmp@y{%
\noindent\parbox{\linewidth}{%
\csname @toc@romannumeral\@ff@tmpN\endcsname}%
\vfill

```

```

\par\noindent\hrulefill
}%
\fi}}

```

`\enableminitoc` Make mini tocs appear at the start of given sectional unit.

```

\newcounter{minitoc}
\newif\if@minitoc
\@minitocfalse

\newcommand*{\enableminitoc}[1][\@ttb@type]{%
\@minitoctrue
\setcounter{minitoc}{0}%
\@ifundefined{#1}{%
\PackageError{flowfram}{Sectioning type ‘#1’ not defined}{}{}%
\renewcommand{\@ttb@minitoc@type}{#1}%
\ifthenelse{equal{#1}{chapter}}{\@makeminitocchapter}{%
\ifthenelse{equal{#1}{part}}{\@makeminitocpart}{%
\@makeminitocsection{#1}}}%
}

```

This command should only appear in the preamble. (This ensures that it is used before `\tableofcontents`.)

```

\@onlypreamble{\enableminitoc}

```

`\@makeminitocchapter` If minitocs are associated with chapters, redefine `\@chapter` so that the minitoc appears after the chapter heading.

```

\newcommand{\@makeminitocchapter}{%
\let\@mtoc@old@chapter\@chapter
\def\@chapter[##1]##2{%
\@mtoc@old@chapter[##1]{##2}%
\stepcounter{minitoc}%
\dominitoc{\c@minitoc}%
\@afterheading
}}

```

`\@makeminitocpart` Again, for parts. As before, need to redefine `\@endpart` if it exists, otherwise redefine `\@part`.

```

\newcommand{\@makeminitocpart}{%
\@ifundefined{@endpart}{%
\let\@mtoc@old@part\@part
\def\@part[##1]##2{%
\@mtoc@old@part[##1]{##2}%
\stepcounter{minitoc}%
\dominitoc{\c@minitoc}%
\@afterheading
}}{%
\let\@mtoc@old@endpart\@endpart
\def\@endpart{%
\stepcounter{minitoc}%
\dominitoc{\c@minitoc}%
\@mtoc@old@endpart
}}}

```

```

\@makeminitocsection Now for the remaining sectional units.
\newcommand{\@makeminitocsection}[1]{%
\let\@mtoc@old@sect=\@sect
\def\@sect##1##2###3###4###5###6[##7]##8{%
\@mtoc@old@sect{##1}{##2}{##3}{##4}{##5}{##6}[##7]{##8}%
\ifthenelse{\equal{##1}{#1}}{%
\stepcounter{minitoc}%
\dominitoc{\c@minitoc}\@afterheading}{}%
}}

```

Index

Symbols			
\@@@ff@getrange . . .	45	\@addtotoclist . . .	89
\@@dofooter	55	\@appenddynamic . . .	32
\@@doheader	55	\@appendminitocdf . .	92
\@@dominitoc	91	\@checkcontentsline .	90
\@@dothumbtabs	84	\@compteffarea . . .	34
\@@dynamicframeswapcoords		\@dblfloatplacement .	58
	30	\@df@chckifthispg . .	46
\@@ff@chckifthispg . .	45	\@df@checkuniqueidl .	27
\@@ff@getrange	44	\@df@setoffset	50
\@@hNtone	73	\@doclearpage	40
\@@hNtoneright	74	\@docolbbox	47
\@@htwotoneleft	72	\@docolbox	46
\@@htwotoneright . . .	73	\@dodfparbox	53
\@@insert@hrule	78	\@dodynamicbbox . . .	54
\@@insert@vrule	76	\@dodynamicbox	54
\@@inserthrule	78	\@dostaticbbox	52
\@@insertvrule	76	\@dostaticbox	51
\@@newdynamicframe . .	26	\@dothefoot	40
\@@newflowframe	8	\@dothehead	40
\@@newstaticframe . . .	17	\@dothumbtabs	82
\@@nextNband	74	\@dynamicchap	80
\@@nextvNband	71	\@dynamicframeid . . .	27
\@@setdynamicframe . .	29	\@dynamicframeswapcoords	
\@@setflowframe	13		30
\@@setfr@mecol	16	\@ff@getrange	44
\@@setframecol	16	\@ff@addtolist	33
\@@setstaticframe . . .	20	\@ff@box	47
\@@sinserthrle	79	\@ff@chckifthispg . .	45
\@@sininsertvrle . . .	77	\@ff@checkifmoreframes	
\@@staticframeswapcoords			43
	24	\@ff@checknumrange . .	43
\@@storefileconts . . .	89	\@ff@checkpages . . .	43
\@@ttb@stack	84	\@ff@checkthispage . .	43
\@@vNtone	71	\@ff@checkuniqueidl .	10
\@@vNtonetop	72	\@ff@disablesec	23
\@NcolumnSbbottominarea		\@ff@do@allframes . .	57
	68	\@ff@doalldynamics . .	56
\@Ncolumninarea	61	\@ff@doalldynamicsbbox	
\@Ncolumnntopinarea . .	64		56
		\@ff@doallflowframes .	56
		\@ff@doallflowframesbbox	
			56
		\@ff@doallstatics . . .	56
		\@ff@doallstaticsbbox .	
			56
		\@ff@dotypeblock . . .	56
		\@ff@drawmargins . . .	51
		\@ff@fbox	47
		\@ff@getdim	35
		\@ff@getrange	44
		\@ff@getrangegreater .	44
		\@ff@getrangeless . . .	44
		\@ff@getshape	23
		\@ff@getstaticpos . . .	51
		\@ff@heading	22
		\@ff@parshape	21
		\@ff@s@t@Ovalboxoffset	
			48
		\@ff@s@t@defaultoffset	
			48
		\@ff@s@t@doubleboxoffset	
			48
		\@ff@s@t@ovalboxoffset	
			48
		\@ff@sectionhead . . .	22
		\@ff@setoffset	49
		\@ff@setsecthead . . .	22
		\@ff@swaplen	35
		\@ffbackground	3
		\@ffdraft	3
		\@ffnodraft	3
		\@flf@subsp	84
		\@flowframeid	10
		\@flowframeswapcoords	
			15
		\@fr@meifdraft	3
		\@g@tnextcol	45
		\@getdynamicbounds . .	37
		\@getflowbounds	36
		\@getmarginpos	7

\@getstaticbounds .	36	\@sdynamicframeswapcoords	\appenddynamiccontents
\@gettype	91	30
\@greyscale	84	\@setcol	39
\@hNtone	73	\@setcolbox	46
\@hNtoneleft	73	\@setdynamiccontents	32
\@hNtoneright	74	\@setdynamicframe .	28
\@htwotone	72	\@setflowframe	13
\@htwotoneleft	72	\@setframecol	16
\@htwotoneright	73	\@setstaticframe . .	19
\@inserthrule	78	\@setthumbtab	88
\@insertvrule	75	\@setthumbtabindex .	88
\@makecol	42	\@sf@chckifthispg .	46
\@makeminitocchapter	93	\@sf@checkuniqueidl	18
\@makeminitocpart .	93	\@sf@setoffset	49
\@makeminitocsection	94	\@sflowframeswapcoords
\@makethumbchapter .	81	15
\@makethumbpart . . .	81	\@sgetdynamicbounds	37
\@makethumbsection .	82	\@sgetflowbounds . .	36
\@makethumbtabs . . .	81	\@sgetstaticbounds .	36
\@n@wflowframe	8	\@sinserthrule	79
\@n@wstaticframe . . .	17	\@sinsertvrule	77
\@newdynamicframe .	26	\@snewdynamicframe .	26
\@newflowframe	8	\@snewflowframe	8
\@newstaticframe . .	17	\@snewstaticframe .	17
\@nexthNband	74	\@ssetdynamiccontents
\@nexthband	74	32
\@nextvNband	71	\@ssetdynamicframe .	28
\@nextvband	70	\@ssetflowframe . . .	13
\@onecolumn	59	\@ssetstaticframe .	19
\@onecolumninarea .	59	\@sstaticcnts	24
\@opcol	42	\@sstaticframeswapcoords
\@outputdblcol	57	25
\@outputpage	41	\@starttoc	88
\@printalignedtoc .	92	\@staticcnts	24
\@printtoc	92	\@staticframeid	18
\@putcolbbox	47	\@staticframeswapcoords
\@putcolbox	47	25
\@putdynamicbbox . .	55	\@storefilecnts . .	89
\@putdynamicbox . . .	54	\@ttb@minitoc type .	88
\@putmarginbox	50	\@ttb@stack	84
\@putstaticbbox . . .	52	\@ttb@storetoc	89
\@putstaticbox	52	\@ttb@type	81
\@resetdyn@mics . . .	53	\@twocolumn	60
\@resetst@tics	53	\@twocolumninarea .	60
\@s@ff@heading	22	\@vNtone	70
\@s@tdynamicframeid	27	\@vNtonebottom	71
\@s@tflowframeid . . .	9	\@vNtonetop	71
\@s@tfr@mes	56		
\@s@tstaticframeid .	18		
\@sappenddynamic . .	32	A	
\@sappendminitocdf .	92	\adjustcolsep	69
\@scomputeffarea . .	34	\adjustheight	68
\@sdynamicchap	80	\afterminitocskip .	91
		\appenddfminitoc . .	92
		B	
		\beforeminitocskip .	91
		C	
		\c@maxminitoc	89
		\c@maxtocunits	89
		\chapterfirstpagestyle
		5
		\cleardoublepage . . .	7
		\computebottomedge .	33
		\computeeflowframearea
		34
		\computeleftedgeeven	33
		\computeleftedgeodd	33
		\computerightedgeeven
		33
		\computerightedgeodd	33
		\computetopedge . . .	33
		D	
		\defaultthumbtabtype	81
		\dfchaphead	80
		\DFchapterstyle . . .	80
		\DFSchapterstyle . .	80
		\dfswapoddeven	30
		\disablethumbtabs .	87
		\dominitoc	91
		dynamiccontents (envi-	ronment)
		31
		dynamiccontents* (en-	vironment) . . .
		32
		\dynamicframeevenx .	28
		\dynamicframeeveny .	28
		\dynamicframex	27
		\dynamicframey	28
		E	
		\emulateonecolumn .	38
		\emulatetwocolumn .	37
		\enableminitoc	93
		\enablethumbtabs . .	86
		environments:	
		dynamiccontents	31
		dynamiccontents*	32
		staticcontents .	23
		staticcontents*	24
		staticfigure	58
		statictable	58
		F	
		\ffcolumnseprule . .	75
		\fflabelfont	3

\fflabelsep	3, 3	\NcolumnDtopinarea .	65	\setthumbtabindex .	88
\ffpshpar	21	\Ncolumninarea	60	\sfswapoddeven	25
\ffswapoddeven	15	\NcolumnSbottom	67	\simpar	21
\finishthispage	6	\NcolumnSbottominarea		staticcontents (envi-	
\flowframeevenx	16	68	ronment)	23
\flowframeeveny	16	\NcolumnStop	63	staticcontents* (envi-	
\flowframeheight	16	\NcolumnStopinarea .	65	ronment)	24
\flowframerule	6	\Ncolumntop	63	staticfigure (environ-	
\flowframesep	6	\Ncolumntopinarea .	64	ment)	58
\flowframeshowlayout		\newdynamicframe . . .	25	\staticframeevenx .	19
.	6, 6	\newflowframe	8	\staticframeeveny .	19
\flowframewidth	16	\newframe	62	\staticframex	19
\flowframex	16	\newstaticframe	17	\staticframey	19
\flowframey	16			statictable (environ-	
\footnotecolor	42			ment)	58
\framebreak	6				
		O		T	
G		\onecolumn	59	\tableofcontents . .	91
\getdynamicbounds . . .	36	\onecolumnbottom . . .	65	\thumbtab	82
\getflowbounds	36	\onecolumnbottominarea		\thumbtabformat . . .	83
\getstaticbounds	36	65	\thumbtabindex	87
\globalreversemargin .	7	\onecolumnDbottom . . .	65	\thumbtabindexformat	83
		\onecolumnDbottominarea		83
		66	\thumbtabwidth	83
H		\onecolumnDtop	61	\tocandthumbtabindex	88
\hNtone	73	\onecolumnDtopinarea	62	\twocolumn	59
\hNtoneleft	73	\onecolumninarea . . .	59	\twocolumnbottom . .	66
\hNtoneright	74	\onecolumnSbottom . . .	65	\twocolumnbottominarea	
\htwotone	72	\onecolumnSbottominarea		66
\htwotoneleft	72	66	\twocolumnDbottom . .	66
\htwotoneright	72	\onecolumnStop	61	\twocolumnDbottominarea	
		\onecolumnStopinarea	62	67
I		\onecolumntop	61	\twocolumnDtop	63
\if@ttb@rotate	4	\onecolumntopinarea	62	\twocolumnDtopinarea	63
\inserthrulerule	78			\twocolumninarea . .	60
\insertvrule	75, 75	R		\twocolumnSbottom . .	66
		\rotateframe	4	\twocolumnSbottominarea	
				67
M		S		\twocolumnStop	62
\makebackgroundframe	75	\sdfparindent	6	\twocolumnStopinarea	63
\makedfheaderfooter	41	\setalldynamicframes	28	\twocolumntop	62
\makethumbtabs	81	\setallflowframes . .	12	\twocolumntopinarea	63
\minitocstyle	91	\setallstaticframes	19		
		\setdynamiccontents	32		
N		\setdynamicframe . . .	28	V	
\Ncolumn	60	\setflowframe	12	\vcolumnsep	61
\Ncolumnbottom	67	\setframes	37	\vNtone	70
\Ncolumnbottominarea	67	\setinitialframe . . .	37	\vNtonebottom	71
\NcolumnDbottom	67	\setmargin	7	\vNtonetop	71
\NcolumnDbottominarea		\setstaticcontents . .	24	\vtwotone	69
.	68	\setstaticframe	19	\vtwotonebottom . . .	69
\NcolumnDtop	64	\setthumbtab	87	\vtwotonetop	70