

# Axes, axes, axes

Andreas Bühmann      Michael Ummels

v1.0a – 2011/10/05

## Abstract

The fontaxes package simulates multiple independent font selection axes on top of certain single NFSS axes: *base family*, *figure style*, and *figure alignment* on top of *family*; *primary shape* and *secondary shape* on top of *shape*; and *math weight* and *math figure alignment* on top of *math version*.

## Contents

<b>1</b>	<b>Introduction</b>	<b>1</b>
<b>2</b>	<b>Usage</b>	<b>2</b>
2.1	Shape . . . . .	2
2.2	Figure version . . . . .	2
2.3	Math version . . . . .	3
2.4	Additional commands . . . . .	3
<b>3</b>	<b>Implementation</b>	<b>4</b>
3.1	High-level author commands (Level 1) . . . . .	4
3.1.1	Shape . . . . .	4
3.1.2	Figure version . . . . .	5
3.1.3	Math version . . . . .	6
3.2	Low-level author commands (Level 2) . . . . .	7
3.3	Internals (Layer 3) . . . . .	7
3.4	Encoding . . . . .	9
3.5	Decoding . . . . .	11
3.6	Compatibility . . . . .	12
3.7	Tools . . . . .	13
3.8	Tests . . . . .	14

## 1 Introduction

The introduction of the New Font Selection Scheme (NFSS) has greatly simplified the usage of L<sup>A</sup>T<sub>E</sub>X with fonts different from the Computer Modern fonts originally

designed for TeX. However, the NFSS has some limitations. In particular, it defines only one axis for the font shape, which caters for both the actual *shape* of the font (e.g. upright, italic or slanted) and the *case* of the font (e.g. upper-lower case and small-caps). For example, if the current font shape is italic, then selecting small capitals using `\scshape` or `\textsc` will revert to an upright shape, even if the font has italic small capitals.

The `fontaxes` package alleviates the deficiencies of the NFSS by simulating multiple axes on top of single NFSS axes. In particular, it replaces the single NFSS shape axis by a primary and a secondary shape axis, catering for the shape and the case of the font, respectively. Moreover, the package introduces three new axes to deal with different *figure versions*, which are provided by many professional fonts.

## 2 Usage

You can load this package by adding

```
\usepackage{fontaxes}
```

to the preamble of your document. This redefines and makes available certain font selection commands, which are described in the rest of this section.

### 2.1 Shape

The `fontaxes` package splits the NFSS's single shape axis into two: the primary shape axis (`n`, `it`, etc.) and the secondary shape axis (`ulc`, `sc`, etc.).

The commands `\upshape`, `\itshape`, and `\slshape` are redefined to access the primary axis only. For access to a swash shape, the command `\swshape` has been added.

The commands `\scshape` and `\sscshape` (spaced small caps) access the secondary axis. To return from any small-caps shape to upper-lower case, you can use the command `\ulcshape`.

All these commands update the two shape axes using the low-level commands `\fontprimaryshape{<value>}` and `\fontsecondaryshape{<value>}`.

If you want to change which values are used by the various commands `\<abbr>shape`, redefine the corresponding `\<abbr>default`. The additional commands `\swdefault`, `\sscdefault`, and `\ulcdefault` are provided with their default values `sw`, `ssc`, and `ulc`, respectively.

### 2.2 Figure version

Different figure versions are usually implemented as different font families (e.g. `MinionPro-{OsF,LF,T0sF,TLF}` or `ppl{j,x}`). The `fontaxes` package splits off the axes *figure style* and *figure alignment*, which leaves the *base family* (e.g. `MinionPro` or `ppl`).

```
\txfigures
\lnfigures
\tbffigures
\prffigures
\fontfigurestyle{<value>}
\fontfigurealignment{<value>}
\fontbasefamily
```

The fontaxes package knows two figure styles, *text* and *lining* (accessible via `\txfigures` and `\lnfigures`), and two modes of figure alignment, *tabular* and *proportional* (accessible via the switches `\tbffigures` and `\prffigures`).

Additionally, you can access both axes directly using the low-level commands `\fontfigurestyle{<value>}` and `\fontfigurealignment{<value>}`.

If you want to change the font family without changing the figure version, use `\fontbasefamily{<value>}`. (All these commands require a successive `\selectfont` to make the changes take effect.)

For choosing the figure versions to be used in math mode, you can use the corresponding axis *math figure alignment*. Note that there is currently no means for changing the figure style used in math.

## 2.3 Math version

```
\boldmath
\unboldmath
\tabularmath
\proportionalmath
\mathweight
\mathfigurealignment
```

By default, L<sup>A</sup>T<sub>E</sub>X provides two math versions, *normal* and *bold*, as well as commands `\boldmath` and `\unboldmath` for switching between them. The fontaxes packages redefines these commands to operate on the axis *math weight*.

A second axis *math figure alignment* is introduced that allows you to switch between *tabular* and *proportional* figures using `\tabularmath` and `\proportionalmath`. (This assumes the presence of additional math versions *tabular* and *boldtabular*; the package will copy the setups of math versions *normal* and *bold* at the end of the preamble in case you do not provide your own declarations.)

You can directly assign values to the axes using the low-level commands `\mathweight{<value>}` and `\mathfigurealignment{<value>}`.

Table 1 summarizes which commands set which values on which axes.

## 2.4 Additional commands

```
\textsw
\textssc
\textulc
\textfigures
\liningfigures
\tabularfigures
\proportionalfigures
\figureversion
```

Similar to the well-known `\textit`, `\textsc`, etc. this package provides commands `\textsw`, `\textssc`, `\textulc`, `\textfigures`, `\liningfigures`, `\tabularfigures` and `\proportionalfigures` that take one argument and apply the font change only to the argument. For example, `\textsw{<text>}` is roughly equivalent to `\swshape{<text>}` (but automatically adds italic corrections).

The command `\figureversion{<options>}` allows easy switching of multiple aspects of figures simultaneously. It takes as an argument a comma-separated list of one or more of the following options:

<code>text, osf</code>	for text figures,
<code>lining, lf</code>	for lining figures,
<code>tabular, tab</code>	for tabular figures,
<code>proportional, prop</code>	for proportional figures.

For example, `\figureversion{lf, tab}` selects tabular lining figures.

Table 1: Summary of commands

Command	Axis	Value	Default
\upshape	\fontprimaryshape	\updefault	n
\itshape		\itdefault	it
\slshape		\sldefault	sl
\swshape		\swdefault	sw
\ulcshape	\fontsecondaryshape	\ulcdefault	ulc
\scshape		\scdefault	sc
\sscshape		\sscdefault	ssc
\txfigures	\fontfigurestyle	text	
\lnfigures		lining	
\tbfigures	\fontfigurealignment	tabular	
\prfigures		proportional	
<i>&lt;none&gt;</i>	\fontbasefamily	<i>{font-dependent}</i>	
\boldmath	\mathweight	bold	
\unboldmath		normal	
\tabularmath	\mathfigurealignment	tabular	
\proportionalmath		proportional	

### 3 Implementation

#### 3.1 High-level author commands (Level 1)

##### 3.1.1 Shape

```

\upshape Axis 1: primary shape
\itshape 1 (*package)
\slshape 2 \DeclareRobustCommand\upshape{\not@math@\alphabet\upshape\relax
\swshape 3 \fontprimaryshape\updefault\selectfont}
          4 \DeclareRobustCommand\itshape{\not@math@\alphabet\itshape\mathit
          5 \fontprimaryshape\itdefault\selectfont}
          6 \DeclareRobustCommand\slshape{\not@math@\alphabet\slshape\relax
          7 \fontprimaryshape\sldefault\selectfont}
          8 \DeclareRobustCommand\swshape{\not@math@\alphabet\swshape\relax
          9 \fontprimaryshape\swdefault\selectfont}

\scshape Axis 2: secondary shape
\sscshape 10 \DeclareRobustCommand\scshape{\not@math@\alphabet\scshape\relax
\ulcshape 11 \fontsecondaryshape\scdefault\selectfont}
          12 \DeclareRobustCommand\sscshape{\not@math@\alphabet\sscshape\relax
          13 \fontsecondaryshape\sscdefault\selectfont}
          14 \DeclareRobustCommand\ulcshape{\not@math@\alphabet\ulcshape\relax
          15 \fontsecondaryshape\ulcdefault\selectfont}

```

```

\noscshape Provide an alias for compatibility with the slantsc package.
16 \let\noscshape\ulcshape

\swdefault
\ulcdefault 17 \providecommand\swdefault{sw}
\sscdefault 18 \providecommand\ulcdefault{ulc}
19 \providecommand\sscdefault{ssc}

\textrm{sw}
\textrm{ssc} 20 \DeclareTextFontCommand{\textrm{sw}}{\swshape}
\textrm{ulc} 21 \DeclareTextFontCommand{\textrm{ssc}}{\sscshape}
22 \DeclareTextFontCommand{\textrm{ulc}}{\ulcshape}

```

### 3.1.2 Figure version

```

\txfigures Axis 1: figure style
\lnfigures 23 \def\txfigures{@nomath\txfigures
24   \fontfigurestyle{text}\selectfont}
25 \def\lnfigures{@nomath\lnfigures
26   \fontfigurestyle{lining}\selectfont}

\tbfigures Axis 2: figure alignment
\prfigures 27 \def\tbfigures{@nomath\tbfigures
28   \fontfigurealignment{tabular}\selectfont}
29 \def\prfigures{@nomath\prfigures
30   \fontfigurealignment{proportional}\selectfont}

\figureversion This code originally appeared in the package MinionPro. We have adapted it to
work within fontaxes' framework and also changed some option names.

```

```

31 \newcommand\fontaxes@fv@prefix{\fontaxes@fv@switch@}
32 \newcommand*\fontaxes@fv@newoption[1]{%
33   {\expandafter\newcommand\csname\fontaxes@fv@prefix #1\endcsname}%
34 \fontaxes@fv@newoption{text}{\txfigures}
35 \fontaxes@fv@newoption{osf}{\txfigures}
36 \fontaxes@fv@newoption{lining}{\lnfigures}
37 \fontaxes@fv@newoption{lf}{\lnfigures}
38 \fontaxes@fv@newoption{tabular}{\tbfigures\tabularmath}
39 \fontaxes@fv@newoption{tab}{\tbfigures\tabularmath}
40 \fontaxes@fv@newoption{proportional}{\prfigures\proportionalmath}
41 \fontaxes@fv@newoption{prop}{\prfigures\proportionalmath}

```

We simply iterate over the list of figure versions specified in the argument to `\figureversion` and check if we have specified a matching option.

```

42 \newcommand\fontaxes@fv@list{}
43 \newcommand\fontaxes@fv@list{}%
44 \DeclareRobustCommand*\figureversion[1]{%
45   \edef\fontaxes@fv@list{\zap@space#1 \empty}%
46   \@for\fontaxes@fv@list:=\fontaxes@fv@list\do{%

```

```

47  \@ifundefined{\fontaxes@fv@prefix\fontaxes@fv}{%
48    \PackageWarning{fontaxes}%
49    {Unknown figure style ‘\fontaxes@fv’\MessageBreak
50      specified as the argument to \string\figureversion.\MessageBreak
51      Figure style not changed}%
52  }{%
53    \nameuse{\fontaxes@fv@prefix\fontaxes@fv}%
54  }%
55 }%
56 }

```

We have made `\figureversion` robust to protect it in moving arguments (e.g., section titles). Additionally, we want it to simply be ignored when `hyperref` is building PDF strings (e.g., for bookmarks). The same is true for similar commands, but we only include a selection of them (only the forms with arguments).

```

57 \AtBeginDocument{%
58   \@ifpackageloaded{hyperref}{%
59     \pdfstringdefDisableCommands{%
60       \let\figureversion\gobble
61       \let\textfigures\@firstofone
62       \let\liningfigures\@firstofone
63       \let\tabularfigures\@firstofone
64       \let\proportionalfigures\@firstofone
65       \let\textsw\@firstofone
66       \let\textssc\@firstofone
67       \let\textulc\@firstofone
68     }%
69   }{}%
70 }

```

Axis 3: base family `\fontbasefamily{...}`

```

\textfigures
\liningfigures
\tabularfigures
\proportionalfigures
71 \DeclareTextFontCommand{\textfigures}{\txfigures}
72 \DeclareTextFontCommand{\liningfigures}{\lnfigures}
73 \DeclareTextFontCommand{\tabularfigures}{\tbfigures\tabularmath}
74 \DeclareTextFontCommand{\proportionalfigures}{%
75   \prfigures\proportionalmath}

```

### 3.1.3 Math version

<code>\boldmath</code>	Axis 1: weight
<code>\unboldmath</code>	76 \def\boldmath{@nomath\boldmath 77   \mathweight{bold}}% 78 \def\unboldmath{@nomath\unboldmath 79   \mathweight{normal}}
<code>\tabularmath</code>	Axis 2: figure alignment
<code>\proportionalmath</code>	80 \def\tabularmath{@nomath\tabularmath}

```

81  \mathfigurealignment{tabular}
82 \def\proportionalmath{\@nomath\proportionalmath
83  \mathfigurealignment{proportional}}
```

**3.2 Low-level author commands (Level 2)**

```

\mathweight{bold,normal} sets \mathversion;
\mathfigurealignment{tabular,proportional} sets \mathversion;
\fontfigurestyle{text,lining} sets \fontfamily;
\fontfigurealignment{tabular,proportional} sets \fontfamily;
\fontbasefamily{...} sets \fontfamily;
\fontprimaryshape{n,it,sl,sw} sets \fontshape;
\fontsecondaryshape{ulc,sc,ssc} sets \fontshape.
```

```

\mathweight
\mathfigurealignment 84 \DeclareRobustCommand\mathweight[1]{%
85   \fontaxes@get@math \edef\fontaxes@math@weight{\#1}\fontaxes@set@math}
86 \DeclareRobustCommand\mathfigurealignment[1]{%
87   \fontaxes@get@math \edef\fontaxes@math@align{\#1}\fontaxes@set@math}
```

```

\fontfigurestyle
\fontfigurealignment 88 \DeclareRobustCommand\fontfigurestyle[1]{%
89   \fontaxes@get@family \edef\fontaxes@figure@style{\#1}\fontaxes@set@family}
90 \DeclareRobustCommand\fontfigurealignment[1]{%
91   \fontaxes@get@family \edef\fontaxes@figure@align{\#1}\fontaxes@set@family}
92 \DeclareRobustCommand\fontbasefamily[1]{%
93   \fontaxes@get@family \edef\fontaxes@family@base{\#1}\fontaxes@set@family}
```

```

\fontprimaryshape
\fontsecondaryshape 94 \DeclareRobustCommand\fontprimaryshape[1]{%
95   \fontaxes@get@shape \edef\fontaxes@shape@one{\#1}\fontaxes@set@shape}
96 \DeclareRobustCommand\fontsecondaryshape[1]{%
97   \fontaxes@get@shape \edef\fontaxes@shape@two{\#1}\fontaxes@set@shape}
```

### 3.3 Internals (Layer 3)

```

\fontaxes@set@math sets \mathversion;
\fontaxes@set@family sets \fontfamily;
\fontaxes@set@shape sets \fontshape.
```

The macros that hold the current values of the axes (here with some default values that will most certainly be overwritten during initialization; see `\fontaxes@get@...`).

```

98 \newcommand*\fontaxes@math@weight{normal}
99 \newcommand*\fontaxes@math@align{proportional}
100 \newcommand*\fontaxes@family@base{cmr}
101 \newcommand*\fontaxes@figure@style{lining}
```



Do not overwrite align (does not occur in alternative naming scheme).

```
146      \fi
147      \else
148      Store values.
149      \edef\fontaxes@family@base{\fontaxes@split@prefix}%
150      \edef\fontaxes@figure@style{\expandafter\@firstoftwo\fontaxes@edoc}%
151      \fi
152  }{}%
153 }

154 \newcommand*\fontaxes@get@shape{%
155   \iffontaxes@changed\f@shape{%
156     \fontaxes@decode@{shape}{\f@shape}%
157     \ifx\fontaxes@edoc\relax\else
158       \edef\fontaxes@shape@one{\expandafter\@firstoftwo\fontaxes@edoc}%
159       \edef\fontaxes@shape@two{\expandafter\@secondoftwo\fontaxes@edoc}%
160     \fi
161     \fontaxes@save\f@shape
162  }{}%
163 }
```

### 3.4 Encoding

```
\fontaxes@encode@math
\fontaxes@encode@family
\fontaxes@encode@figures
\fontaxes@encode@figuresalt
\fontaxes@encode@shape
Default is concatenation.
164 \newcommand*\fontaxes@encode@math{%
165   \fontaxes@encode@{math}{{\fontaxes@math@weight}{\fontaxes@math@align}}%
166 }
```

```
167 \newcommand*\fontaxes@encode@math@default{%
168   \edef\fontaxes@code{\fontaxes@math@weight\fontaxes@math@align}}
169 \newcommand*\fontaxes@encode@family{%
170   \fontaxes@encode@{family}
171   {{\fontaxes@family@base}{\fontaxes@figure@style}{\fontaxes@figure@align}}}%
172 }
```

Try different naming conventions.

```
173 \newcommand*\fontaxes@encode@family@default{%
174   \fontaxes@encode@figures
175   \edef\fontaxes@code{\fontaxes@family@base-\fontaxes@code}%
176   \fontaxes@check@family\fontaxes@code
177   \iffontaxes@exists\else
178     \fontaxes@encode@figuresalt
179     \edef\fontaxes@code{\fontaxes@family@base\fontaxes@code}%
180     \fontaxes@check@family\fontaxes@code
181   \iffontaxes@exists\else
182     \edef\fontaxes@code{\fontaxes@family@base}%
183   \fi
```

```

184 \fi
185 }

186 \newcommand*\fontaxes@encode@figures{%
187   \fontaxes@encode@{figures}{{\fontaxes@figure@style}{\fontaxes@figure@align}}%
188 }
189 \newcommand*\fontaxes@encode@figures@default{%
190   \edef\fontaxes@code{0sF}%
191   \PackageWarning{\fontaxes}{Unknown figure version
192     '\fontaxes@figure@style\space + \fontaxes@figure@align'\MessageBreak
193     Encoding to '\fontaxes@code'}%
194 }

195 \newcommand*\fontaxes@encode@figuresalt{%
196   \fontaxes@encode@{figuresalt}{{\fontaxes@figure@style}{\fontaxes@figure@align}}%
197 }
198 \newcommand*\fontaxes@encode@figuresalt@default{%
199   \PackageWarning{\fontaxes}{Unknown figure version
200     '\fontaxes@figure@style\space + \fontaxes@figure@align'\MessageBreak
201     Encoding to '\fontaxes@code'}%
202   \edef\fontaxes@code{j}%
203 }

204 \newcommand*\fontaxes@encode@shape{%
205   \fontaxes@encode@{shape}{{\fontaxes@shape@one}{\fontaxes@shape@two}}%
206 }

Default is (reverse) concatenation.

207 \newcommand*\fontaxes@encode@shape@default{%
208   \edef\fontaxes@code{\fontaxes@shape@two\fontaxes@shape@one}%
209 }

\fontaxes@encode@

210 \newcommand*\fontaxes@encode@[2]{%
211   \@ifundefined{\fontaxes@encode@#1#2}%
212     {@nameuse{\fontaxes@encode@#1@default}}%
213     {\edef\fontaxes@code{@nameuse{\fontaxes@encode@#1#2}}}%
214 }

\fontaxes@naming@exception To do: Add a user interface to specify naming exceptions.

215 \newcommand*\fontaxes@naming@exception[3]{%
216   \expandafter\edef\csname fontaxes@encode@#1#2\endcsname{#3}%
217 }

The defaults n and ulc disappear when combined.

218 \fontaxes@naming@exception{shape}{{n}{ulc}}{n}
219 \fontaxes@naming@exception{shape}{{n}{sc}}{sc}
220 \fontaxes@naming@exception{shape}{{n}{ssc}}{ssc}
221 \fontaxes@naming@exception{shape}{{it}{ulc}}{it}
222 \fontaxes@naming@exception{shape}{{sl}{ulc}}{sl}
223 \fontaxes@naming@exception{shape}{{sw}{ulc}}{sw}

```

The defaults disappear in the concatenation. `boldtabular` is formed regularly.

```
224 \fontaxes@naming@exception{math}{{normal}{proportional}}{normal}
225 \fontaxes@naming@exception{math}{{normal}{tabular}}{tabular}
226 \fontaxes@naming@exception{math}{{bold}{proportional}}{bold}
```

Provide abbreviations for font family suffixes.

```
227 \fontaxes@naming@exception{figures}{{text}{proportional}}{OsF}
228 \fontaxes@naming@exception{figures}{{text}{tabular}}{T0sF}
229 \fontaxes@naming@exception{figures}{{lining}{proportional}}{LF}
230 \fontaxes@naming@exception{figures}{{lining}{tabular}}{TLF}
```

The `j/x` naming convention does not know about different figure alignments; let us silently ignore these.

```
231 \fontaxes@naming@exception{figuresalt}{{text}{proportional}}{j}
232 \fontaxes@naming@exception{figuresalt}{{text}{tabular}}{j}
233 \fontaxes@naming@exception{figuresalt}{{lining}{proportional}}{x}
234 \fontaxes@naming@exception{figuresalt}{{lining}{tabular}}{x}
```

### 3.5 Decoding

Detect if `\mathversion`, `\fontshape`, `\fontfamily` have been used not under control of this package.

```
\fontaxes@figure@style@domain
\fontaxes@figure@align@domain
  \fontaxes@shape@one@domain
  \fontaxes@shape@two@domain
\fontaxes@math@weight@domain
\fontaxes@math@align@domain
```

Assuming an injective encoding function, we can construct decoding tables when we know the function's domain. To do: Warn if decoding entries are overwritten (if the function is not injective).

```
235 \newcommand*\fontaxes@figure@style@domain{text,lining}
236 \newcommand*\fontaxes@figure@align@domain{proportional,tabular}
237 \newcommand*\fontaxes@shape@one@domain{n,it,sl,sw}
238 \newcommand*\fontaxes@shape@two@domain{ulc,sc,ssc}
239 \newcommand*\fontaxes@math@weight@domain{normal,bold}
240 \newcommand*\fontaxes@math@align@domain{proportional,tabular}
```

```
\fontaxes@create@decode@table #1 name, #2 list of axes
241 \newcommand*\fontaxes@create@decode@table[2]{%
242   \begingroup
243   \fontaxes@foreach{\#2}{%
244     @nameuse{fontaxes@encode@\#1}%
245     \global\expandafter
246     \edef\csname fontaxes@decode@\#1{\fontaxes@code}\endcsname{\#2}%
247   }%
248   \endgroup
249 }

250 \AtEndOfPackage{
251   \fontaxes@create@decode@table{figures}
252   {{\fontaxes@figure@style}{\fontaxes@figure@align}}
253   \fontaxes@create@decode@table{figuresalt}
254   {{\fontaxes@figure@style}{\fontaxes@figure@align}}
```

```

255   \fontaxes@create@decode@table{shape}
256     {{\fontaxes@shape@one}{\fontaxes@shape@two}}
257 \fontaxes@create@decode@table{math}
258   {{\fontaxes@math@weight}{\fontaxes@math@align}}
259 }

\fontaxes@warn@undecodable
260 \newcommand*\fontaxes@warn@undecodable[1]{%
261   \PackageWarning{fontaxes}{I don't know how to decode\MessageBreak #1}%

\fontaxes@decode@ Interpret the decoding tables.
262 \newcommand*\fontaxes@decode@[2]{%
263   \@ifundefined{fontaxes@decode@#1{#2}}{%
264     \let\fontaxes@edoc\relax
265     \fontaxes@warn@undecodable{#1 '#2}%
266   }{\edef\fontaxes@edoc{\@nameuse{fontaxes@decode@#1{#2}}}}%
267 }

\fontaxes@save Save states of macros for future comparison.
\iffontaxes@changed
268 \newcommand*\iffontaxes@changed[1]{%
269   \expandafter\ifx\csname fontaxes@last@\string#1\endcsname#1%
270     \expandafter\@secondoftwo
271   \else
272     \expandafter\@firstoftwo
273   \fi
274 }
275 \newcommand*\fontaxes@save[1]{%
276   \expandafter\let\csname fontaxes@last@\string#1\endcsname#1%
277 }

```

### 3.6 Compatibility

If no math versions `tabular` and `boldtabular` are defined in the preamble, we provide defaults by copying the states of `normal` and `bold` (assuming, in turn, that these two exist).

```

278 \AtBeginDocument{%
279   \fontaxes@provide@mv@copy{tabular}{normal}%
280   \fontaxes@provide@mv@copy{boldtabular}{bold}%
281 }

```

`\fontaxes@provide@mv@copy` Declare math version #1 to be a copy of math version #2 if #1 does not exist already. To accomplish this, we have to know that a math version's configuration is basically stored in a macro `\mv@<name>` (which makes us dependent on the NFSS implementation; sigh ...).

```

282 \newcommand*\fontaxes@provide@mv@copy[2]{%
283   \@ifundefined{mv@#1}{%
284     \DeclareMathVersion{#1}%
285     \expandafter\let\csname mv@#1\expandafter\endcsname

```

```

286      \csname mv@#2\endcsname
287  }{ }%
288 }

```

### 3.7 Tools

\fontaxes@check@family	Check if family switching would yield an existing shape.
\iffontaxes@exists	<pre> 289 \newif\iffontaxes@exists 290 \newcommand*\fontaxes@check@family[1]{% 291   \begingroup 292   \fontfamily{\#1}\try@load@fontshape 293   \expandafter 294   \ifx\csname\curr@fontshape\endcsname\relax 295     \aftergroup\fontaxes@existsfalse 296   \else 297     \aftergroup\fontaxes@existstrue 298   \fi 299   \endgroup 300 } </pre>
\fontaxes@split@prefix	The results of splitting a family name.
\fontaxes@split@suffix	<pre> 301 \newcommand*\fontaxes@split@prefix{} 302 \newcommand*\fontaxes@split@suffix{} </pre>
\fontaxes@split@family	Font name contains one hyphen; split there.
	<pre> 303 \newcommand*\fontaxes@split@family{} 304 \def\fontaxes@split@family#1-#2-#3\@nnil{% 305   \let\fontaxes@split@prefix\relax 306   \let\fontaxes@split@suffix\relax 307   \def\@tempa{#3}% 308   \ifx\@tempa\empty\else 309     \def\fontaxes@split@suffix{#2}% 310     \ifx\fontaxes@split@suffix\empty 311       \let\fontaxes@split@suffix\relax 312     \else 313       \def\fontaxes@split@prefix{#1}% 314     \fi 315   \fi 316 } </pre>
\fontaxes@split@familyalt	Name consists of four characters; split off the last one. If there are just three characters, the default suffix is ‘x’.
	<pre> 317 \newcommand*\fontaxes@split@familyalt{} 318 \def\fontaxes@split@familyalt#1#2#3#4#5\@nnil{% 319   \let\fontaxes@split@prefix\relax 320   \let\fontaxes@split@suffix\relax 321   \edef\@tempa{#5}% 322   \ifx\@tempa\empty </pre>

```

323   \ifx\@empty#4%
324     \def\fontaxes@split@prefix{\#1#2#3}%
325     \def\fontaxes@split@suffix{x}%
326   \else
327     \def\fontaxes@split@prefix{\#1#2#3}%
328     \def\fontaxes@split@suffix{\#4}%
329   \fi
330 \fi
331 }

\fontaxes@foreach Execute #2 for each combination of values of the axes given in #1 (in the form
{\cs}{\cs}...).
332 \newcommand\fontaxes@foreach[2]{%
333   \begingroup
334   \def\fontaxes@foreach@{\#2}%
335   \atfor{@tempa:=#1\do{%
336     \temptokena\expandafter{\fontaxes@foreach@}%
337     \edef\fontaxes@foreach@{%
338       \noexpand\@for
339       \expandafter\noexpand\@tempa:=%
340       \expandafter\noexpand\csname
341       \expandafter\expandafter
342       \expandafter\@gobble
343       \expandafter\string\@tempa
344       @domain%
345       \endcsname
346       \noexpand\do{\the\@temptokena}%
347     }%
348   }%
349   \expandafter\endgroup\fontaxes@foreach@
350 }
351 </package>

```

### 3.8 Tests

The file `test-fontaxes.tex` (docstrip target `test`) exercises some features of `fontaxes`. Since it is rather ad-hoc code, it is not shown here. (It also requires the `MinionPro` package.)