

# The fonts package

WILL ROBERTSON and KHALED HOSNY

2010/05/27 v2.0b1

## Contents

<b>1 History</b>	<b>2</b>	<b>7.5 Different features for different font sizes</b>	<b>13</b>
<b>2 Introduction</b>	<b>3</b>	<b>8 Font independent options</b>	<b>14</b>
2.1 About this manual	3	8.1 Color	14
<b>3 Package loading and options</b>	<b>3</b>	8.2 Scale	15
3.1 Maths fonts adjustments	4	8.3 Interword space	15
3.2 Configuration	4	8.4 Post-punctuation space	16
3.3 Warnings	4	8.5 The hyphenation character	16
		8.6 Optical font sizes	16
<b>I General font selection</b>	<b>6</b>		
<b>4 Font selection</b>	<b>6</b>	<b>II OpenType</b>	<b>18</b>
4.1 By font name	6	<b>9 Introduction</b>	18
4.2 By file name	6	<b>10 Complete listing of OpenType font features</b>	18
<b>5 Default font families</b>	<b>8</b>	10.1 Ligatures	18
<b>6 New commands to select font families</b>	<b>8</b>	10.2 Letters	19
6.1 More control over font shape selection	9	10.3 Numbers	19
6.2 Math(s) fonts	10	10.4 Contextuals	20
6.3 Miscellaneous font selecting details	11	10.5 Vertical Position	20
<b>7 Selecting font features</b>	<b>11</b>	10.6 Fractions	21
7.1 Default settings	11	10.7 StylisticSet	22
7.2 Changing the currently selected features	12	10.8 Alternates	22
7.3 Priority of feature selection	12	10.9 Style	23
7.4 Different features for different font shapes	12	10.10 Diacritics	24
		10.11 Kerning	24
		10.12 CJK shape	24
		10.13 Character width	25
		10.14 Vertical typesetting	26
		10.15 OpenType scripts and languages	26

<b>III Fonts and features with X<sub>E</sub>T<sub>E</sub>X</b>	<b>29</b>	<b>V The patching/improvement of L<sub>A</sub>T<sub>E</sub>X2<sub>E</sub> and other packages</b>	<b>40</b>
<b>11 X<sub>E</sub>T<sub>E</sub>X-only font features</b>	<b>29</b>	<b>18 Inner emphasis</b>	<b>40</b>
11.1 Mapping	29	<b>19 Unicode footnote symbols</b>	<b>40</b>
11.2 Letter spacing	29	<b>20 Verbatim</b>	<b>40</b>
11.3 Font transformations	29	<b>21 Discretionary hyphenation: \-</b>	<b>40</b>
11.4 Different font technologies: AAT and ICU	30		
11.5 Optical font sizes	30		
<b>12 Mac OS X's AAT fonts</b>	<b>30</b>	<b>VI fontspec.sty</b>	<b>41</b>
12.1 Ligatures	31	<b>22 Implementation</b>	<b>41</b>
12.2 Letters	31	22.1 Bits and pieces	41
12.3 Numbers	31	22.2 Error/warning messages	42
12.4 Contextuals	31	22.3 Option processing	45
12.5 Vertical position	32	22.4 Packages	45
12.6 Fractions	32	22.5 Encodings	45
12.7 Variants	33	22.6 User commands	46
12.8 Alternates	33	22.7 Programmer's interface	51
12.9 Style	33	22.8 Internal macros	54
12.10 CJK shape	34	22.9 keyval definitions	69
12.11 Character width	34	22.10 Italic small caps	86
12.12 Annotation	35	22.11 Selecting maths fonts	87
12.13 Vertical typesetting	35	22.12 Finishing up	91
12.14 Diacritics	35		
12.15 Annotation	36		
<b>13 AAT &amp; Multiple Master font axes</b>	<b>36</b>	<b>VII fontspec.lua</b>	<b>92</b>
<b>IV Programming interface</b>	<b>37</b>	<b>VIII fontspec-patches.sty</b>	<b>96</b>
<b>14 Defining new features</b>	<b>37</b>	22.13 Unicode footnote symbols	96
<b>15 Going behind fonts spec's back</b>	<b>38</b>	22.14 Emph	96
<b>16 Renaming existing features &amp; options</b>	<b>38</b>	22.15 \-	96
<b>17 Programming details</b>	<b>38</b>	22.16 Verbatims	96
		<b>IX fontspec.cfg</b>	<b>99</b>
		<b>X Example documents</b>	<b>100</b>

## 1 History

This package began life as a L<sub>A</sub>T<sub>E</sub>X interface to select system-installed Mac OS X fonts in Jonathan Kew's X<sub>E</sub>T<sub>E</sub>X, the first widely-used unicode extension to T<sub>E</sub>X.

Over time,  $\text{\XeTeX}$  was extended to support OpenType fonts and then was ported into a cross-platform program to run also on Windows and Linux.

More recently,  $\text{\LuaTeX}$  is fast becoming the  $\text{\TeX}$  engine of the day; it supports unicode encodings and OpenType fonts and opens up the internals of  $\text{\TeX}$  via the Lua programming language. Hans Hagen's  $\text{\ConTeXt}$  Mk. IV is a re-write of his powerful typesetting system, taking full advantage of  $\text{\LuaTeX}$ 's features including font support; a kernel of his work in this area has been extracted to be useful for other  $\text{\TeX}$  macro systems as well, and this has enabled `fontspec` to be adapted for  $\text{\LaTeX}$  when run with the  $\text{\LuaTeX}$  engine. Elie Roux and Khaled Hosny have been instrumental and invaluable with this development work.

## 2 Introduction

The `fontspec` package allows users of either  $\text{\XeTeX}$  or  $\text{\LuaTeX}$  to load OpenType fonts in a  $\text{\LaTeX}$  document. No font installation is necessary, and font features can be selected and used as desired throughout the document.

Without `fontspec`, it is necessary to write cumbersome font definition files for  $\text{\LaTeX}$ , since  $\text{\LaTeX}$ 's font selection scheme (known as the '`nfss`') has a lot going on behind the scenes to allow easy commands like `\emph` or `\bfseries`. With an uncountable number of fonts now available for use, however, it becomes less desirable to have to write these font definition (`.fd`) files for every font one wishes to use.

Because `fontspec` is designed to work in a variety of modes, this user documentation is split into separate sections that are designed to be relatively independent. Nonetheless, the basic functionality all behaves in the same way, so previous users of `fontspec` under  $\text{\XeTeX}$  should have little or no difficulty switching over to  $\text{\LuaTeX}$ .

This manual can get rather in-depth, as there are a lot of details to cover. See the example documents `fontspec-xetex.tex` and `fontspec-luatex.tex` for a complete minimal example with each engine.

### 2.1 About this manual

As of version 2.0 with the addition of  $\text{\LuaTeX}$  support, this manual is still in the process of being re-written. It currently contains no typeset examples. Your patience and feedback is appreciated!

## 3 Package loading and options

For basic use, no package options are required:

```
\usepackage{fontspec}
```

In brief, `fontspec`'s package options are  
`no-math` Don't change any maths fonts;  
`no-config` Don't load `fontspec.cfg`; and,  
`quiet` Output `fontspec` warnings in the log file rather than the console output.  
These are described in more detail below.

**X<sub>E</sub>T<sub>E</sub>X users only** Ross Moore’s `xunicode` package is recommended for providing backwards compatibility with L<sup>A</sup>T<sub>E</sub>X’s methods for accessing extra characters and accents (for example, `\%`, `\$`, `\textbullet`, `\texttt{u}`, and so on), plus many more unicode characters. The `xltxtra` package adds a couple of general improvements to L<sup>A</sup>T<sub>E</sub>X under X<sub>E</sub>T<sub>E</sub>X; it also provides the `\XeTeX` macro to typeset the X<sub>E</sub>T<sub>E</sub>X logo.

**LuaT<sub>E</sub>X users only** In order to load fonts by their name rather than by their file-name (*e.g.*, ‘Latin Modern Roman’ instead of ‘ec-lmr10’), you may need to run the script `mkluatexfontdb.lua`, which is distributed with the `luatofload` package. Please see its documentation for more information. Note that the `xunicode` package is not required as it has been incorporated directly into the unicode font definitions (see the `euenc` package for more information).

`babel` *The babel package is not really supported!* Especially Vietnamese, Greek, and Hebrew at least might not work correctly, as far as I can tell. There’s a better chance with Cyrillic and Latin-based languages, however—`fontspec` ensures at least that fonts should load correctly, but hyphenation and other matters aren’t guaranteed. Under X<sub>E</sub>T<sub>E</sub>X, the `polyglossia` package is recommended instead as a modern replacement for `babel`.

### 3.1 Maths fonts adjustments

By default, `fontspec` adjusts L<sup>A</sup>T<sub>E</sub>X’s default maths setup in order to maintain the correct Computer Modern symbols when the roman font changes. However, it will attempt to avoid doing this if another maths font package is loaded (such as `mathpazo` or my upcoming `unicode-math` package).

If you find that it is incorrectly changing the maths font when it should be leaving well enough alone, apply the `[no-math]` package option to manually suppress its maths font.

### 3.2 Configuration

If you wish to customise any part of the `fontspec` interface (see later in this manual, [Section 14 on page 37](#) and [Section 16](#)), this should be done by creating your own `fontspec.cfg` file,<sup>1</sup> which will be automatically loaded if it is found by X<sub>E</sub>T<sub>E</sub>X. Either place it in the same folder as the main document for isolated cases, or in a location that X<sub>E</sub>T<sub>E</sub>X or LuaT<sub>E</sub>X searches by default; *e.g.* in MacT<sub>E</sub>X: `~/Library/texmf/tex/latex/`. The package option `[no-config]` will suppress this behaviour under all circumstances.

### 3.3 Warnings

This package can give many warnings that can be harmless if you know what you’re doing. Use the `[quiet]` package option to write these warnings to the transcript (`.log`) file instead.

---

<sup>1</sup>An example is distributed with the package.

Use the [`silent`] package option to completely suppress these warnings if you don't even want the `.log` file cluttered up.

# Part I

## General font selection

This section concerns the variety of commands that can be used to select fonts.

```
\fontspec [⟨font features⟩] {⟨font name⟩}  
\setmainfont [⟨font features⟩] {⟨font name⟩}  
\setsansfont [⟨font features⟩] {⟨font name⟩}  
\setmonofont [⟨font features⟩] {⟨font name⟩}  
\newfontfamily ⟨cmd⟩ [⟨font features⟩] {⟨font name⟩}
```

These are the main font-selecting commands of this package. The `\fontspec` command selects a font for one-time use; all others should be used to define the standard fonts used in a document. They will be described later in this section.

The font features argument accepts comma separated `⟨font feature⟩=⟨option⟩` lists; these are described in later:

- For general font features, see [Section 8 on page 14](#)
- For OpenType fonts, see [Part II on page 18](#)
- For  $\text{\XeTeX}$ -only general font features, see [Part III on page 29](#)
- For features for `AAT` fonts in  $\text{\XeTeX}$ , see [Part Section 12 on page 30](#)

## 4 Font selection

In both  $\text{\LaTeX}$  and  $\text{\XeTeX}$ , fonts can be selected either by ‘font name’ or by ‘file name’.

### 4.1 By font name

Fonts known to  $\text{\LaTeX}$  or  $\text{\XeTeX}$  may be loaded by their names. ‘Known to’ in this case generally means ‘exists in a standard fonts location’ such as `~/Library/Fonts` on Mac OS X, or `C://WINNT/Fonts` on Windows.

The simplest example might be something like

```
\fontspec[ ... ]{Cambria}
```

in which the bold and italic fonts will be found automatically (if they exist) and are immediately accessible with the usual `\textit` and `\textbf` commands.

TODO: add explanation for how to find out what the ‘font name’ is.

### 4.2 By file name

When selecting fonts by file name, any font that can be found in the default search paths may be used directly (including in the current directory) without having to explicitly define the location of the font file on disk.

Note that  $\text{\XeTeX}$  with the `xdvipdfmx` driver and  $\text{\LaTeX}$  can both select fonts in this way, but  $\text{\XeTeX}$  with the `xdv2pdf` driver can only select fonts by name and not

by file name. The `xdvipdfmx` driver is default for X<sub>E</sub>T<sub>E</sub>X; the `xdv2pdf` driver is only available on Mac OS X.

Fonts selected by filename must include bold and italic variants explicitly.

```
\fontspec
  [ BoldFont      = texgyrepagella-bold.otf ,
    ItalicFont    = texgyrepagella-italic.otf ,
    BoldItalicFont = texgyrepagella-bolditalic.otf ]
  {texgyrepagella-regular.otf}
```

`fontspec` knows that the font is to be selected by file name by the presence of the ‘.otf’ extension. An alternative is to specify the extension separately, as shown following:

```
\fontspec
  [ Extension     = .otf ,
    BoldFont      = texgyrepagella-bold ,
    ...
  {texgyrepagella-regular}
```

If desired, an abbreviation can be applied to the font names based on the mandatory ‘font name’ argument:

```
\fontspec
  [ Extension     = .otf ,
    UprightFont   = *-regular ,
    BoldFont      = *-bold ,
    ...
  {texgyrepagella}
```

In this case ‘texgyrepagella’ is no longer the name of an actual font, but is used to construct the font names for each shape; the \* is replaced by ‘texgyrepagella’. Note in this case that `UprightFont` is required for constructing the font name of the normal font to use.

To load a font that is not in one of the default search paths, its location in the filesystem must be specified with the `Path` feature:

```
\fontspec
  [ Path          = /Users/will/Fonts/ ,
    UprightFont   = *-regular ,
    BoldFont      = *-bold ,
    ...
  {texgyrepagella}
```

Note that X<sub>E</sub>T<sub>E</sub>X and LuaT<sub>E</sub>X are able to load the font without giving an extension, but `fontspec` must know to search for the file; this can be indicated by declaring the font exists in an ‘ExternalLocation’:

```
\fontspec
  [ ExternalLocation ,
    BoldFont      = texgyrepagella-bold ,
    ...
  {texgyrepagella-regular}
```

To be honest, Path and ExternalLocation are actually the same feature with different names. The former can be given without an argument and the latter can be given with one; the different names are just for clarity.

## 5 Default font families

```
\setmainfont [\langle font features \rangle] {\langle font name \rangle}
\setsansfont [\langle font features \rangle] {\langle font name \rangle}
\setmonofont [\langle font features \rangle] {\langle font name \rangle}
```

These commands are used to select the default font families for the entire document. They take the same arguments as \fontspec. For example:

```
\setmainfont{Baskerville}
\setsansfont[Scale=MatchLowercase]{Skia}
\setmonofont[Scale=MatchLowercase]{Monaco}
\rmfamily\pangram\par
\sffamily\pangram\par
\ttfamily\pangram
```

Here, the scales of the fonts have been chosen to equalise their lowercase letter heights. The Scale font feature will be discussed further in [Section 8 on page 14](#), including methods for automatic scaling.

## 6 New commands to select font families

```
\newfontfamily \langle font-switch \rangle [\langle font features \rangle] {\langle font name \rangle}
\newfontface \langle font-switch \rangle [\langle font features \rangle] {\langle font name \rangle}
```

For cases when a specific font with a specific feature set is going to be re-used many times in a document, it is inefficient to keep calling \fontspec for every use. While the command does not define a new font instance after the first call, the feature options must still be parsed and processed.

\newfontfamily For this reason, new commands can be created for loading a particular font family with the \newfontfamily command:

```
\newfontfamily\notefont{Didot}
\notefont This is a \emph{note}.
```

This macro should be used to create commands that would be used in the same way as \rmfamily, for example.

\newfontface Sometimes only a specific font face is desired, without accompanying italic or bold variants begin automatically selected. This is common when selecting a fancy italic font, say, that has swash features unavailable in the upright forms. \newfontface is used for this purpose:

```
\newfontface\fancy
[Contextuals={WordInitial,WordFinal}]
{Hoefler Text Italic}
\fancy where is all the vegemite
```

This example is repeated in [Section 12.4 on page 31](#).

## 6.1 More control over font shape selection

```
  BoldFont = <font name>
  ItalicFont = <font name>
  BoldItalicFont = <font name>
  SlantedFont = <font name>
  BoldSlantedFont = <font name>
  SmallCapsFont = <font name>
```

The automatic bold, italic, and bold italic font selections will not be adequate for the needs of every font: while some fonts mayn't even have bold or italic shapes, in which case a skilled (or lucky) designer may be able to chose well-matching accompanying shapes from a different font altogether, others can have a range of bold and italic fonts to chose between. The `BoldFont` and `ItalicFont` features are provided for these situations. If only one of these is used, the bold italic font is requested as the default from the *new* font.

```
\fontspec[BoldFont={Helvetica Neue}]
            {Helvetica Neue UltraLight}
            Helvetica Neue UltraLight      \\
{\itshape    Helvetica Neue UltraLight Italic} \\
{\bfseries   Helvetica Neue        } \\
{\bfseries\itshape Helvetica Neue Italic} \\
```

If a bold italic shape is not defined, or you want to specify *both* custom bold and italic shapes, the `BoldItalicFont` feature is provided.

### 6.1.1 Input shorthands

For those cases that the base font name is repeated, you can replace it with an asterisk. For example, some space can be saved instead of writing ‘Baskerville SemiBold’:

```
\fontspec[BoldFont={* SemiBold}]{Baskerville}
          Baskerville \textit{Italic}
\bfseries SemiBold \textit{Italic}
```

As a matter of fact, this feature can also be used for the upright font too:

```
\fontspec[UprightFont={* SemiBold},
          BoldFont={* Bold}]{Baskerville}
          Upright \textit{Italic}
\bfseries Bold \textit{Bold Italic}
```

### 6.1.2 Small caps and slanted font shapes

For the rare situations where a font family will have slanted *and* italic shapes, these may be specified separately using the analogous features `SlantedFont` and `BoldSlantedFont`. Without these, however, the L<sup>A</sup>T<sub>E</sub>X font switches for slanted (`\textsl`, `\slshape`) will default to the italic shape.

Old-fashioned font families used to distribute their small caps glyphs in separate fonts due to the limitations on the number of glyphs allowed in the PostScript Type 1 format. Such fonts may be used by declaring the `SmallCapsFont` of the family you are specifying:

```
\fontspec[
  SmallCapsFont={Minion MM Small Caps & Oldstyle Figures},
  ]{Minion MM Roman}
Roman 123 \textsc{Small caps 456}
```

All of the bold, italic, and small caps fonts can be loaded with different font features from the main font. See ?? for details.

## 6.2 Math(s) fonts

When `\setmainfont`, `\setsansfont` and `\setmonofont` are used in the preamble, they also define the fonts to be used in maths mode inside the `\mathrm`-type commands. This only occurs in the preamble because L<sup>A</sup>T<sub>E</sub>X freezes the maths fonts after this stage of the processing. The `fontspec` package must also be loaded after any maths font packages (*e.g.*, `euler`) to be successful. (Actually, it is *only* `euler` that is the problem.<sup>2</sup>)

Note that you may find that loading some maths packages won't be as smooth as you expect since `fontspec` (and X<sub>E</sub>T<sub>E</sub>X in general) breaks many of the assumptions of T<sub>E</sub>X as to where maths characters and accents can be found. Contact me if you have troubles, but I can't guarantee to be able to fix any incompatibilities. The Lucida and Euler maths fonts should be fine; for all others keep an eye out for problems.

```
\setmathrmfont [⟨font features⟩] {⟨font name⟩}
\setmathsffont [⟨font features⟩] {⟨font name⟩}
\setmathttfont [⟨font features⟩] {⟨font name⟩}
\setboldmathrmfont [⟨font features⟩] {⟨font name⟩}
```

However, the default text fonts may not necessarily be the ones you wish to use when typesetting maths (especially with the use of fancy ligatures and so on). For this reason, you may optionally use those commands listed in the margin (in the same way as our other `\fontspec`-like commands) to explicitly state which fonts to use inside such commands as `\mathrm`. Additionally, the `\setboldmathrm` command allows you define the font used for `\mathrm` when in bold maths mode (which is activated with, among others, `\boldmath`).

For example, if you were using Optima with the Euler maths font, you might have this in your preamble:

```
\usepackage{mathpazo}
\usepackage{fontspec,xunicode}
\setmainfont{Optima}
\setmathrm{Optima}
\setboldmathrm[BoldFont=Optima ExtraBlack]{Optima Bold}
```

---

<sup>2</sup>Speaking of `euler`, if you want to use its `[mathbf]` option, it won't work, and you'll need to put this after `fontspec` is loaded instead: `\AtBeginDocument{\DeclareMathAlphabet\mathbf{U}{eur}{b}{n}}`

and this would allow you to typeset something like this:

```
\setmainfont{Optima Regular}
$ X \rightarrow \mathrm{X} \rightarrow \mathbf{X} $
\\boldmath
$ X \rightarrow \mathrm{X} \rightarrow \mathbf{X} $
```

(TODO: this example obviously doesn't work without the graphic.)

### 6.3 Miscellaneous font selecting details

**Spaces** `\fontspec` and `\addfontfeatures` ignore trailing spaces as if it were a 'naked' control sequence; e.g., '`M. \fontspec{...} N`' and '`M. \fontspec{...}N`' are the same.

**Italic small caps** Note that this package redefines the `\itshape` and `\scshape` commands in order to allow them to select italic small caps in conjunction.

**Emphasis and nested emphasis** You may specify the behaviour of the `\emph` command by setting the `\emshape` command. E.g., for bold emphasis:

```
\renewcommand\emshape{\bfseries}
```

Nested emphasis is controlled by the `\eminnershape` command. For example, for `\emph{\emph{...}}` to produce small caps:

```
\renewcommand\eminnershape{\scshape}
```

X<sub>E</sub>T<sub>E</sub>X users will need to load the `xltextra` package before the advice above works.

## 7 Selecting font features

The commands discussed so far each take an optional argument for accessing the font features of the requested font. These features are generally unavailable or harder to access in regular L<sub>A</sub>T<sub>E</sub>X.

### 7.1 Default settings

```
\defaultfontfeatures{<font features>}
```

It is desirable to define options that are applied to every subsequent font selection command: a default feature set, so to speak. This may be defined with the `\defaultfontfeatures` command. New calls of `\defaultfontfeatures` overwrite previous ones.

```
\fontspec{Didot}
Some 'default' Didot 0123456789          \\
\defaultfontfeatures{Numbers=OldStyle, Color=888888}
\fontspec{Didot}
Now grey, with old-style figures: 0123456789
```

## 7.2 Changing the currently selected features

```
\addfontfeatures{<font features>}
```

This command allows font features to be changed without knowing what features are currently selected or even what font is being used. A good example of this could be to add a hook to all tabular material to use monospaced numbers, as shown in the following example:

```
\fontspec[Numbers=OldStyle]{Skia}
‘In 1842, 999 people sailed 97 miles in
13 boats. In 1923, 111 people sailed 54
miles in 56 boats.’ \bigskip

{\addfontfeatures{Numbers={Monospaced,Lining}}
\begin{tabular}{@{} cccc @{}}
\toprule Year & People & Miles & Boats \\
\midrule 1842 & 999 & 75 & 13 \\
& 1923 & 111 & 54 & 56 \\
\bottomrule
\end{tabular}}
```

\addfontfeature

This command may also be executed under the alias \addfontfeature.

## 7.3 Priority of feature selection

Features defined with \addfontfeatures override features specified by \fontspec, which in turn override features specified by \defaultfontfeatures. If in doubt, whenever a new font is chosen for the first time, an entry is made in the transcript (.log) file displaying the font name and the features requested.

## 7.4 Different features for different font shapes

```
    BoldFeatures{<features>}
    ItalicFeatures{<features>}
    BoldItalicFeatures{<features>}
    SlantedFeatures{<features>}
    BoldSlantedFeatures{<features>}
    SmallCapsFeatures{<features>}
```

It is entirely possible that separate fonts in a family will require separate options; *e.g.*, Hoefler Text Italic contains various swash feature options that are completely unavailable in the upright shapes.

The font features defined at the top level of the optional \fontspec argument are applied to *all* shapes of the family. Using Upright-, SmallCaps-, Bold-, Italic-, and BoldItalicFeatures, separate font features may be defined to their respective shapes *in addition* to, and with precedence over, the ‘global’ font features.

```
\fontspec{Hoefler Text} \itshape \scshape
Attention All Martini Drinkers \\
\addfontfeature{ItalicFeatures={Alternate = 1}}
Attention All Martini Drinkers \\
```

Combined with the options for selecting arbitrary *fonts* for the different shapes, these separate feature options allow the selection of arbitrary weights in the Skia typeface, for example:

```
\fontspec[BoldFont={Skia},
          BoldFeatures={Weight=2}]{Skia}
Skia \\ \bfseries Skia 'Bold'
```

Note that because most fonts include their small caps glyphs within the main font, features specified with `SmallCapsFeatures` are applied *in addition* to any other shape-specific features as defined above, and hence `SmallCapsFeatures` can be nested within `ItalicFeatures` and friends. Every combination of upright, italic, bold and small caps can thus be assigned individual features, as shown in the following ludicrous example.

```
\fontspec[
    UprightFeatures={Color = 220022,
                     SmallCapsFeatures = {Color=115511}},
    ItalicFeatures={Color = 2244FF,
                   SmallCapsFeatures = {Color=112299}},
    BoldFeatures={Color = FF4422,
                 SmallCapsFeatures = {Color=992211}},
    BoldItalicFeatures={Color = 888844,
                       SmallCapsFeatures = {Color=444422}},
    ]{Hoefler Text}
Upright {\scshape Small Caps}\\
\itshape Italic {\scshape Italic Small Caps}\\
\upshape\bfseries Bold {\scshape Bold Small Caps}\\
\itshape Bold Italic {\scshape Bold Italic Small Caps}
```

## 7.5 Different features for different font sizes

```
SizeFeatures = {
    ...
    { Size = <size range>, <font features> }
    { Size = <size range>, Font = <font name>, <font features> }
    ...
}
```

The `SizeFeature` feature is a little more complicated than the previous features discussed. It allows different fonts and different font features to be selected for a given font family as the point size varies.

It takes a comma separated list of braced, comma separated lists of features for each size range. Each sub-list must contain the `Size` option to declare the size range, and optionally `Font` to change the font based on size. Other (regular) `fontspec` features that are added are used on top of the font features that would be used anyway.

Input	Font size, s
Size = X-	$s \geq X$
Size = -Y	$s < Y$
Size = X-Y	$X \leq s < Y$
Size = X	$s = X$

Table 1: Syntax for specifying the size to apply custom font features.

```
\fontspec[ SizeFeatures={  
    {Size={-8}, Font=Apple Chancery, Color=AA0000},  
    {Size={8-14}, Color=00AA00},  
    {Size={14-}, Color=0000AA} }{Skia}  
    {\scriptsize Small\par} Normal size\par {\Large Large\par}
```

A less trivial example is shown in the context of optical font sizes in [Section 11.5 on page 30](#).

To be precise, the `Size` sub-feature accepts arguments in the form shown in [Table 1](#). Braces around the size range are optional. For an exact font size (`Size=X`) font sizes chosen near that size will ‘snap’. For example, for size definitions at exactly 11pt and 14pt, if a 12pt font is requested *actually* the 11pt font will be selected. This is a remnant of the past when fonts were designed in metal (at obviously rigid sizes) and later when bitmap fonts were similarly designed for fixed sizes.

If additional features are only required for a single size, the other sizes must still be specified. As in:

```
SizeFeatures={  
    {Size=-10,Numbers=Uppercase},  
    {Size=10-}}
```

Otherwise, the font sizes greater than 10 won’t be defined!

## 8 Font independent options

Features introduced in this section may be used with any font.

### 8.1 Color

`Color` (or `Colour`), also shown in [Section 7.1 on page 11](#) and elsewhere, uses  $\text{\LaTeX}$  font specifications to set the color of the text. The color is defined as a triplet of two-digit Hex RGB values, with optionally another value for the transparency (where 00 is completely transparent and FF is opaque.)

```
\fontsize{48}{48}  
\fontspec{Hoefler Text Black}  
\addfontfeature{Color=FF000099}W}\kern-1ex  
\addfontfeature{Color=0000FF99}S}\kern-0.8ex  
\addfontfeature{Color=DDBB2299}P}\kern-0.8ex  
\addfontfeature{Color=00BB3399}R}
```

## 8.2 Scale

```
Scale = <number>
Scale = MatchLowercase
Scale = MatchUppercase
```

In its explicit form, Scale takes a single numeric argument for linearly scaling the font, as demonstrated in [Section 5 on page 8](#). It is now possible to measure the correct dimensions of the fonts loaded and calculate values to scale them automatically.

As well as a numerical argument, Scale feature also accepts options MatchLowercase and MatchUppercase, which will scale the font being selected to match the current default roman font to either the height of the lowercase or uppercase letters, respectively.

```
\setmainfont{Georgia}
\newfontfamily\lc[Scale=MatchLowercase]{Verdana}
The perfect match {\lc is hard to find.}\
\newfontfamily\uc[Scale=MatchUppercase]{Arial}
L O G O \uc F O N T
```

The amount of scaling used in each instance is reported in the .log file. Since there is some subjectivity about the exact scaling to be used, these values should be used to fine-tune the results.

## 8.3 Interword space

While the space between words can be varied on an individual basis with the  $\text{\TeX}$  primitive \spaceskip command, it is more convenient to specify this information when the font is first defined.

The space in between words in a paragraph will be chosen automatically by  $\text{\XeTeX}$ , and generally will not need to be adjusted. For those times when the precise details are important, the WordSpace features is provided, which takes either a single scaling factor to scale the value that  $\text{\XeTeX}$  has already chosen, or a triplet of comma-separated values for the nominal value, the stretch, and the shrink of the interword space, respectively. *I.e.*, WordSpace=0.8 is the same as WordSpace={0.8, 0.8, 0.8}.

For example, I believe that the Cochin font, as distributed with Mac OS X, is too widely spaced. Now, this can be rectified, as shown below.

```
\fontspec{Cochin}
\fillertext
\vspace{1em}

\fontspec[ WordSpace = {0.7 , 0.8 , 0.9 } ]{Cochin}
\fillertext
```

Be careful with the unpredictable things that the  $\text{AAT}$  font renderer can do with the text! Unlike  $\text{\TeX}$ , Mac OS X will allow fonts to letterspace themselves, which can be seen above; OpenType fonts, however, will not show this tendency, as they do not support this arguably dubious feature.

## 8.4 Post-punctuation space

If `\frenchspacing` is *not* in effect, TeX will allow extra space after some punctuation in its goal of justifying the lines of text. Generally, this is considered old-fashioned, but occasionally in small amounts the effect can be justified, pardon the pun.

The `PunctuationSpace` feature takes a scaling factor by which to adjust the nominal value chosen for the font. Note that `PunctuationSpace=0` is *not* equivalent to `\frenchspacing`, although the difference will only be apparent when a line of text is under-full.

```
\nonfrenchspacing
\fontspec{Baskerville}
Letters, Words. Sentences. \par
\fontspec[PunctuationSpace=0.5]{Baskerville}
Letters, Words. Sentences. \par
\fontspec[PunctuationSpace=0]{Baskerville}
Letters, Words. Sentences.
```

Also be aware that the above caveat for interword space also applies here, so after the last line in the above example, the `PunctuationSpace` for *all* Baskerville instances will be 0.

## 8.5 The hyphenation character

The letter used for hyphenation may be chosen with the `HyphenChar` feature. It takes three types of input, which are chosen according to some simple rules. If the input is the string `None`, then hyphenation is suppressed for this font. If the input is a single character, then this character is used. Finally, if the input is longer than a single character it must be the UTF-8 slot number of the hyphen character you desire.

Below, Adobe Garamond Pro's uppercase hyphenation character is used to demonstrate a possible use for this feature. The second example redundantly demonstrates the default behaviour of using the hyphen as the hyphenation character.

```
\def\text
{A MULTITUDE OF OBSTREPEROUSLY HYPHENATED ENTITIES
 \par\vspace{1ex}}
\fontspec[HyphenChar=None]{Adobe Garamond Pro} \text
\fontspec[HyphenChar={-}]{Adobe Garamond Pro} \text
\fontspec[HyphenChar="F6BA]{Adobe Garamond Pro} \text
```

Note that in an actual situation, the Uppercase option of the `Letters` feature would probably supply this for you (see [Section 12.2 on page 31](#)).

This package (or the `xltextra` package for XeTeX users) redefines L<sup>A</sup>T<sub>E</sub>X's `\-` macro such that it adjusts along with the above changes.

## 8.6 Optical font sizes

Optically scaled fonts thicken out as the font size decreases in order to make the glyph shapes more robust (less prone to losing detail), which improves legibility.

Conversely, at large optical sizes the serifs and other small details may be more delicately rendered.

OpenType fonts with optical scaling will exist in several discrete sizes, and these will be selected by  $\text{\TeX}$  automatically determined by the current font size. The `OpticalSize` option may be used to specify a different optical size.

For the OpenType font Warnock Pro, we have three optically sized variants: caption, subhead, and display. With `OpticalSize` set to zero, no optical size font substitution is performed:

```
\fontspec[OpticalSize=0]{Warnock Pro Caption}
  Warnock Pro optical sizes          \\
\fontspec[OpticalSize=0]{Warnock Pro}
  Warnock Pro optical sizes          \\
\fontspec[OpticalSize=0]{Warnock Pro Subhead}
  Warnock Pro optical sizes          \\
\fontspec[OpticalSize=0]{Warnock Pro Display}
  Warnock Pro optical sizes
```

Automatic OpenType optical scaling is shown in the following example, in which we've scaled down some large text in order to be able to compare the difference for equivalent font sizes: (this gives the same output as we saw in the previous example for Warnock Pro Display)

```
\fontspec{Warnock Pro}
  Automatic optical size          \\
\scalebox{0.4}{\Huge
  Automatic optical size}
```

The `SizeFeatures` feature ( [Section 7.5 on page 13](#) ) can be used to specify exactly which optical sizes will be used for ranges of font size. For example, something like

```
\fontspec[
  SizeFeatures={
    {Size=-10,      OpticalSize=8 },
    {Size= 10-14,   OpticalSize=10},
    {Size= 14-18,   OpticalSize=14},
    {Size= 18-,     OpticalSize=18}}
  ]{Warnock Pro}
```

Feature	Option	Tag
Ligatures	= Required	* rlig
	NoRequired	rlig ( <i>deactivate</i> )
	Common	* liga
	NoCommon	liga ( <i>deactivate</i> )
	Contextual	* clig
	NoContextual	clig ( <i>deactivate</i> )
	Rare/Discretionary	dlig
	Historical	hlig
	TeX	tlig/trep

\* This feature is activated by default.

Table 2: Options for the OpenType font feature ‘Ligatures’.

## Part II

# OpenType

### 9 Introduction

TODO: explain OpenType font features.

Some examples of font features have already be seen in previous sections.

Multiple options may be given to any feature that accepts non-numerical input, although doing so will not always work. Some options will override others in generally obvious ways; `Numbers={OldStyle,Lining}` doesn’t make much sense because the two options are mutually exclusive, and `XETEX` will simply use the last option that is specified (in this case using `Lining` over `OldStyle`).

If a feature or an option is requested that the font does not have, a warning is given in the console output. As mentioned in [Section 3.3 on page 4](#) these warnings can be suppressed by selecting the `[quiet]` package option.

### 10 Complete listing of OpenType font features

#### 10.1 Ligatures

Ligatures refer to the replacement of two separate characters with a specially drawn glyph for functional or æsthetic reasons. The list of options, of which multiple may be selected at one time, is shown in [Table 2](#).

```
\fontspec[Ligatures=Rare]{Adobe Garamond Pro}
\textit{strict firefly} \\ 
\fontspec[Ligatures=NoCommon]{Adobe Garamond Pro}
\textit{strict firefly}
```

Feature	Option	Tag
Letters = Uppercase	case	
SmallCaps	smcp	
PetiteCaps	pcap	
UppercaseSmallCaps	c2sc	
UppercasePetiteCaps	c2pc	
Unicase	unic	

Table 3: Options for the OpenType font feature ‘Letters’.

## 10.2 Letters

The Letters feature specifies how the letters in the current font will look. OpenType fonts have options: Uppercase, SmallCaps, PetiteCaps, UppercaseSmallCaps, UppercasePetiteCaps, and Unicase.

Petite caps are smaller than small caps. SmallCaps and PetiteCaps turn lowercase letters into the smaller caps letters, whereas the Uppercase... options turn the *capital* letters into the smaller caps (good, e.g., for applying to already uppercase acronyms like ‘NASA’). ‘Unicase’ is a weird hybrid of upper and lower case letters.

```
\fontspec[Letters=SmallCaps]{TeX Gyre Adventor}
THIS SENTENCE no verb
\fontspec[Letters=UppercaseSmallCaps]{TeX Gyre Adventor}
THIS SENTENCE no verb
```

Note that The Uppercase option will (probably) not actually map letters to uppercase.<sup>3</sup> It is designed select various uppercase forms for glyphs such as accents and dashes.

```
\fontspec{Warnock Pro}
UPPER-CASE EXAMPLE \\
\addfontfeature{Letters=Uppercase}
UPPER-CASE EXAMPLE
```

The Kerning feature also contains an Uppercase option, which adds a small amount of spacing in between letters (see [Section 10.11 on page 24](#)).

## 10.3 Numbers

The Numbers feature defines how numbers will look in the selected font, accepting options shown in [Table 4](#).

The synonyms Uppercase and Lowercase are equivalent to Lining and OldStyle, respectively. The differences have been shown previously in [Section 7.2 on page 12](#). The Monospaced option is useful for tabular material when digits need to be vertically aligned.

The SlashedZero option replaces the default zero with a slashed version to prevent confusion with an uppercase ‘O’.

---

<sup>3</sup>If you want automatic uppercase letters, look to LATEX’s \MakeUppercase command.

Feature	Option	Tag
Numbers =	Uppercase/Lining	lnum
	Lowercase/OldStyle	onum
	Proportional	pnum
	Monospaced	tnum
	SlashedZero	zero
	Remap	anum

Table 4: Options for the OpenType font feature ‘Numbers’.

Feature	Option	Tag
Contextuals =	Swash	cswh
	Alternate	* calt
	NoAlternate	calt ( <i>deactivate</i> )
	WordInitial	init
	WordFinal	fina
	LineFinal	falt
	Inner	medi

\* This feature is activated by default.

Table 5: Options for the OpenType font feature ‘Contextuals’.

The Remap option maps numerals to their Arabic or Farsi equivalents based on the current Language setting (see [Section 10.15 on page 26](#)). This is based on a LuaTeX feature of the luatofloat package, not an OpenType feature.

```
\fontspec[Numbers=Lining]{TeX Gyre Bonum}
0123456789
\fontspec[Numbers=SlashedZero]{TeX Gyre Bonum}
0123456789
```

## 10.4 Contextuals

This feature refers to glyph substitution that vary by their position; things like contextual swashes are accessed here.

```
\fontspec{Warnock Pro} \itshape
Without Contextual Swashes           \\
\fontspec[Contextuals=Swash]{Warnock Pro}
With Contextual Swashes; cf. W C S
```

Historic forms are accessed in OpenType fonts via the feature `Style=Historic`; this is generally *not* contextual in OpenType, which is why it is not included here.

## 10.5 Vertical Position

The `VerticalPosition` feature is used to access things like subscript (Inferior) and superscript (Superior) numbers and letters (and a small amount of punctu-

Feature	Option	Tag
VerticalPosition	= Superior	sups
	Inferior	subs
	Numerator	numr
	Denominator	dnom
	ScientificInferior	sinf
	Ordinal	ordn

Table 6: Options for the OpenType font feature ‘VerticalPosition’.

ation, sometimes). The `Ordinal` option will only raise characters that are used in some languages directly after a number.

The `ScientificInferior` feature will move glyphs further below the baseline than the `Inferior` feature.

`Numerator` and `Denominator` should only be used for creating arbitrary fractions (see next section).

```
\fontspec{Skia}
Normal
\fontspec[VerticalPosition=Superior]{Skia}
Superior
\fontspec[VerticalPosition=Inferior]{Skia}
Inferior \\ 
\fontspec[VerticalPosition=Ordinal]{Skia}
1st 2nd 3rd 4th 0th 8abcde

\fontspec[VerticalPosition=Superior]{Warnock Pro}
Sup: abdehilmnorst (-\$12,345.67) \\
\fontspec[VerticalPosition=Numerator]{Warnock Pro}
Numerator: 12345 \\
\fontspec[VerticalPosition=Denominator]{Warnock Pro}
Denominator: 12345 \\
\fontspec[VerticalPosition=ScientificInferior]{Warnock Pro}
Scientific Inferior: 12345 \\
\fontspec[VerticalPosition=Ordinal]{Warnock Pro}
‘Ordinals’: 1st 2nd 3rd 4th 0th
```

The `realscripts` package (yet to be released) (or `xltextra` for X<sub>E</sub>T<sub>E</sub>X) redefines the `\textsubscript` and `\textsuperscript` commands to use the above font features.

## 10.6 Fractions

For OpenType fonts use a regular text slash to create fractions:

```
\fontspec{Hiragino Maru Gothic Pro W4}
1/2 \quad 1/4 \quad 5/6 \quad 13579/24680 \\
\addfontfeature{Fractions=On}
1/2 \quad 1/4 \quad 5/6 \quad 13579/24680 \\
```

Some (Asian fonts predominantly) also provide for the `Alternate` feature:

Feature	Option	Tag
Fractions	= On	frac
	Alternate	afrc

Table 7: Options for the OpenType font feature ‘Fractions’.

```
\fontspec{Hiragino Maru Gothic Pro W4}
 1/2 \quad 1/4 \quad 5/6 \quad 13579/24680 \\
\addfontfeature{Fractions=Alternate}
 1/2 \quad 1/4 \quad 5/6 \quad 13579/24680 \\
```

## 10.7 StylisticSet

This feature selects a ‘Stylistic Set’ variation, specified numerically. These correspond to OpenType features ss01, ss02, etc.

Here are two examples from the Junicode font<sup>4</sup>; thanks to Adam Buchbinder for the suggestion. This example shows insular (ancient) letterforms:

```
\fontspec{Junicode}
  Insular forms. \\
\addfontfeature{StylisticSet=2}
  Insular forms. \\
```

And here is shown enlarged minuscules: (capital letters remain unchanged)

```
\fontspec{Junicode}
  ENLARGED Minuscules. \\
\addfontfeature{StylisticSet=6}
  ENLARGED Minuscules. \\
```

(This is a synonym of the Variant feature for AAT fonts.) See [Section 14 on page 37](#) for a way to assign names to stylistic sets, which should be done on a per-font basis.

## 10.8 Alternates

Selection of the Alternate feature again must be done numerically.

For OpenType fonts, this option is used to access numerical variations of the raw salt feature. I can’t show an example, but here’s how it would be used:

```
\fontspec[Alternate=1]{Garamond Premier Pro}
```

Numbering starts from 0 for the first stylistic alternate. Note that the Style=Alternate option is equivalent to Alternate=0 to access the default case.

See [Section 14 on page 37](#) for a way to assign names to alternates, which should be done on a per-font basis.

Feature Option	Tag
Style = Alternate	salt
Italic	ital
Ruby	ruby
Swash	swsh
Historic	hist
TitlingCaps	titl
HorizontalKana	hkna
VerticalKana	vkna

Table 8: Options for the OpenType font feature ‘Style’.

## 10.9 Style

‘Ruby’ refers to a small optical size, used in Japanese typography for annotations. For fonts with multiple salt OpenType features, use the `fontspec` `Alternate` feature instead.

```
\fontspec{Warnock Pro}
  K Q R k v w y
  \addfontfeature{Style=Alternate}
  K Q R k v w y
```

Note the occasional inconsistency with which font features are labelled; a long-tailed ‘Q’ could turn up anywhere!

```
\fontspec{Adobe Jenson Pro}
  M Q Z
  \addfontfeature{Style=Historic}
  M Q Z

\fontspec{Adobe Garamond Pro}
  TITLING CAPS
  \addfontfeature{Style=TitlingCaps}
  TITLING CAPS
```

Two features in one example; Italic affects the Latin text and Ruby the Japanese:

```
\fontspec{Hiragino Mincho Pro W3}
  Latin
  \addfontfeature{Style={Italic, Ruby}}
  Latin
```

Note the difference here between the default and the horizontal style kana:

```
\fontspec{Hiragino Mincho Pro}
  \\
  {\addfontfeature{Style=HorizontalKana}
  } \\
  {\addfontfeature{Style=VerticalKana}
  }
```

---

<sup>4</sup><http://junicode.sf.net>

Feature	Option	Tag
Diacritics =	MarkToBase	* mark
	NoMarkToBase	mark ( <i>deactivate</i> )
	MarkToMark	* mkmk
	NoMarkToMark	mkmk ( <i>deactivate</i> )
	AboveBase	* abvm
	NoAboveBase	abvm ( <i>deactivate</i> )
	BelowBase	* blwm
	NoBelowBase	blwm ( <i>deactivate</i> )

\* This feature is activated by default.

Table 9: Options for the OpenType font feature ‘Diacritics’.

Feature	Option	Tag
Kerning =	Uppercase	cpsp
	On	* kern
	Off	kern ( <i>deactivate</i> )

\* This feature is activated by default.

Table 10: Options for the OpenType font feature ‘Kerning’.

## 10.10 Diacritics

Specifies how diacritics should be placed. These will usually be controlled automatically according to the Script setting.

## 10.11 Kerning

Specifies how inter-glyph spacing should behave.

As briefly mentioned previously at the end of [Section 12.2 on page 31](#), the Uppercase option will add a small amount of tracking between uppercase letters:

```
\fontspec{Warnock_Pro}
UPPER-CASE EXAMPLE \\
\addfontfeature{Kerning=Uppercase}
UPPER-CASE EXAMPLE
```

## 10.12 CJK shape

There have been many standards for how CJK ideographic glyphs are ‘supposed’ to look. Some fonts will contain many alternate glyphs available in order to be able to display these glyphs correctly in whichever form is appropriate. Both AAT and OpenType fonts support the following CJKShape options: Traditional, Simplified, JIS1978, JIS1983, JIS1990, and Expert. OpenType also supports the NLC option.

Feature	Option	Tag
CJKShape =	Traditional	trad
	Simplified	smpl
	JIS1978	jp78
	JIS1983	jp83
	JIS1990	jp90
	Expert	expt
	NLC	nlck

Table 11: Options for the OpenType font feature ‘CJKShape’.

Feature	Option	Tag
CharacterWidth =	Proportional	pwid
	Full	fwid
	Half	hwid
	Third	twid
	Quarter	qwid
	AlternateProportional	palt
	AlternateHalf	halt

Table 12: Options for the OpenType font feature ‘CharacterWidth’.

```
\fontspec{Hiragino Mincho Pro}
{\addfontfeature{CJKShape=Traditional}
  }
  \\
{\addfontfeature{CJKShape=NLC}
  }
  \\
{\addfontfeature{CJKShape=Expert}
  }
```

### 10.13 Character width

Many Asian fonts are equipped with variously spaced characters for shoe-horning into their generally monospaced text. These are accessed through the `CharacterWidth` feature.

Japanese alphabetic glyphs (in Hiragana or Katakana) may be typeset proportionally, to better fit horizontal measures, or monospaced, to fit into the rigid grid imposed by ideographic typesetting. In this latter case, there are also half-width forms for squeezing more kana glyphs (which are less complex than the kanji they are amongst) into a given block of space. The same features are given to roman letters in Japanese fonts, for typesetting foreign words in the same style as the surrounding text.

```
\def\test{\makebox[2cm][l]{\%} %           \makebox[2.5cm][l]{\%} %           \makebox[2.5cm][l]{abcdef}}
\fontspec{Hiragino Mincho Pro}
{\addfontfeature{CharacterWidth=Proportional}\test} \\
{\addfontfeature{CharacterWidth=Full}\test} \\
{\addfontfeature{CharacterWidth=Half}\test}
```

The same situation occurs with numbers, which are provided in increasingly illegible compressed forms:

```
\fontspec[Renderer=AAT]{Hiragino Mincho Pro}
{\addfontfeature{CharacterWidth=Full}
---12321---} \\
{\addfontfeature{CharacterWidth=Half}
---1234554321---} \\
{\addfontfeature{CharacterWidth=Third}
---123456787654321---} \\
{\addfontfeature{CharacterWidth=Quarter}
---12345678900987654321---}
```

The option `CharacterWidth=Full` doesn't work with the default OpenType font renderer (ICU) due to a bug in the Hiragino fonts.

## 10.14 Vertical typesetting

TODO!

## 10.15 OpenType scripts and languages

When dealing with fonts that include glyphs for various languages, they may contain different font features for the different character sets and languages it supports. These may be selected with the `Script` and `Language` features. The possible options are tabulated in [Table 13 on the following page](#) and [Table 14 on page 28](#), respectively. When a script or language is requested that is not supported by the current font, a warning is printed in the console output.

Because these font features can change which features are able to be selected for the font, they are selected by `fontspec` before all others and will specifically select the ICU renderer for this font, as described in [Section 11.4 on page 30](#).

### 10.15.1 Defining new scripts and languages

`\newfontscript` `\newfontlanguage` Further scripts and languages may be added with the `\newfontscript` and `\newfontlanguage` commands. For example,

```
\newfontscript{Arabic}{arab}
\newfontlanguage{Turkish}{TUR}
```

The first argument is the `fontspec` name, the second the OpenType definition. The advantage to using these commands rather than `\newfontfeature` (see [Section 14 on page 37](#)) is the error-checking that is performed when the script or language is requested.

Arabic	Ethiopic	Limbu	Sumero-Akkadian
Armenian	Georgian	Linear B	Cuneiform
Balinese	Glagolitic	Malayalam	Sylozi Nagri
Bengali	Gothic	¶Math	Syriac
Bopomofo	Greek	¶Maths	Tagalog
Braille	Gujarati	Mongolian	Tagbanwa
Buginese	Gurmukhi	Musical Symbols	Tai Le
Buhid	Hangul Jamo	Myanmar	Tai Lu
Byzantine Music	Hangul	N'ko	Tamil
Canadian Syllabics	Hanunoo	Ogham	Telugu
Cherokee	Hebrew	Old Italic	Thaan
CJK	¶Hiragana and Katakana	Old Persian Cuneiform	Thai
CJK Ideographic	¶Kana	Oriya	Tibetan
Coptic	Javanese	Osmanya	Tifinagh
Cypriot Syllabary	Kannada	Phags-pa	Ugaritic Cuneiform
Cyrillic	Kharosthi	Phoenician	Yi
Default	Khmer	Runic	
Deseret	Lao	Shavian	
Devanagari	Latin	Sinhala	

Table 13: Defined Scripts for OpenType fonts. Aliased names are shown in adjacent positions marked with red pilcrows (¶), defined in `fontspec.cfg`.

Abaza	Default	Ilokano	Lahuli	Niuean	South Slavay
Abkhazian	Dogri	Indonesian	Lak	Nkole	Southern Sami
Adyghe	Divehi	Ingush	Lambani	N'ko	Suri
Afrikaans	Djerma	Inuktitut	Lao	Dutch	Svan
Afar	Dangme	Irish	Latin	Nogai	Swedish
Agaw	Dinka	Irish Traditional	Laz	Norwegian	Swadaya Aramaic
Altai	Dungan	Icelandic	L-Cree	Northern Sami	Swahili
Amharic	Dzongkha	Inari Sami	Ladakhi	Northern Tai	Swazi
Arabic	Ebira	Italian	Lezgi	Esperanto	Sutu
Aari	Eastern Cree	Hebrew	Lingala	Nynorsk	Syriac
Arakanese	Edo	Javanese	Low Mari	Oji-Cree	Tabasaran
Assamese	Efik	Yiddish	Limbu	Ojibway	Tajiki
Athapaskan	Greek	Japanese	Lomwe	Oriya	Tamil
Avar	English	Judezmo	Lower Sorbian	Oromo	Tatar
Awadhi	Erzya	Jula	Lule Sami	Ossetian	TH-Cree
Aymara	Spanish	Kabardian	Lithuanian	Palestinian	Telugu
Azeri	Estonian	Kachchi	Luba	Aramaic	Tongan
Badaga	Basque	Kalenjin	Luganda	Pali	Tigre
Baghelkhandi	Evenki	Kannada	Luhya	Punjabi	Tigrinya
Balkar	Even	Karachay	Luo	Palpa	Thai
Baule	Ewe	Georgian	Latvian	Pashto	Tahitian
Berber	French Antillean	Kazakh	Majang	Polytonic Greek	Tibetan
Bench	Farsi	Kebena	Makua	Pilipino	Turkmen
Bible Cree	Finnish	Khutsuri Georgian	Malayalam	Palaung	Temne
Belarussian	Fijian	Khakass	Traditional	Polish	Tswana
Bemba	Flemish	Khanty-Kazim	Mansi	Provencal	Tundra Nenets
Bengali	Forest Nenets	Khmer	Marathi	Portuguese	Tonga
Bulgarian	Fon	Khanty-Shurishkar	Marwari	Chin	Todo
Bhili	Faroese	Khanty-Vakhi	Mbundu	Rajasthani	Turkish
Bhojpuri	French	Khowar	Manchu	R-Cree	Tsonga
Bikol	Frisian	Kikuyu	Moose Cree	Russian Buriat	Turoyo Aramaic
Bilen	Friulian	Kirghiz	Mende	Riang	Tulu
Blackfoot	Futa	Kisii	Me'en	Rhaeto-Romanic	Tuvin
Balochi	Fulani	Kokni	Mizo	Romanian	Twi
Balante	Ga	Kalmyk	Macedonian	Romany	Udmurt
Balti	Gaelic	Kamba	Male	Rusyn	Ukrainian
Bambara	Gagauz	Kumaoni	Malagasy	Ruanda	Urdu
Bamileke	Galician	Komo	Malinke	Russian	Upper Sorbian
Breton	Garshuni	Komso	Malayalam	Sadri	Uyghur
Brahui	Garhwali	Kanuri	Reformed	Sanskrit	Uzbek
Braj Bhasha	Ge'ez	Kodagu	Malay	Santali	Venda
Burmese	Gilyak	Korean Old Hangul	Mandinka	Sayisi	Vietnamese
Bashkir	Gumuz	Konkani	Mongolian	Sekota	Wa
Beti	Gondi	Kikongo	Manipuri	Selkup	Wagdi
Catalan	Greenlandic	Komi-Permyak	Maninka	Sango	West-Cree
Cebuano	Garo	Korean	Manx Gaelic	Shan	Welsh
Chechen	Guarani	Komi-Zyrian	Moksha	Sibe	Wolof
Chaha Gurage	Gujarati	Kpelle	Moldavian	Sidamo	Tai Lue
Chattisgarhi	Haitian	Krio	Mon	Silte Gurage	Xhosa
Chicewa	Halam	Karakalpak	Moroccan	Skolt Sami	Yakut
Chukchi	Harauti	Karelian	Maori	Slovak	Yoruba
Chipewyan	Hausa	Karaim	Maithili	Slavey	Y-Cree
Cherokee	Hawaiin	Karen	Maltese	Slovenian	Yi Classic
Chuvash	Hammer-Banna	Koorete	Mundari	Somali	Yi Modern
Comorian	Hiligaynon	Kashmiri	Naga-Assamese	Samoan	Chinese Hong Kong
Coptic	Hindi	Khasi	Nanai	Sena	Chinese Phonetic
Cree	High Mari	Kildin Sami	Naskapi	Sindhi	Chinese Simplified
Carrier	Hindko	Kui	N-Cree	Sinhalese	Chinese Traditional
Crimean Tatar	Ho	Kulvi	Ndebele	Soninke	Zande
Church Slavonic	Harari	Kumyk	Ndonga	Sodo Gurage	Zulu
Czech	Croatian	Kurdish	Nepali	Sotho	
Danish	Hungarian	Kurukh	Newari	Albanian	
Dargwa	Armenian	Kuy	Nagari	Serbian	
Woods Cree	Igbo	Koryak	Norway House Cree	Saraiki	
German	Ijo	Ladin	Nisi	Serer	

Table 14: Defined Languages for OpenType fonts. Note that they are sorted alphabetically *not* by name but by OpenType tag, which is a little irritating, really.

# Part III

## Fonts and features with X<sub>E</sub>T<sub>E</sub>X

### 11 X<sub>E</sub>T<sub>E</sub>X-only font features

The features described here are available for any font selected by `fontspec`.

#### 11.1 Mapping

Mapping enables a X<sub>E</sub>T<sub>E</sub>X text-mapping scheme.

```
\fontspec[Mapping=tex-text]{Cochin}
  '!`A small amount of---text!''
```

Using the `tex-text` mapping is also equivalent to writing `Ligatures=TeX`. The use of the latter syntax is recommended for better compatibility with Lua<sub>T</sub>E<sub>X</sub> documents.

#### 11.2 Letter spacing

Letter spacing, or tracking, is the term given to adding (or subtracting) a small amount of horizontal space in between adjacent characters. It is specified with the `LetterSpace`, which takes a numeric argument.

The letter spacing parameter is a normalised additive factor (not a scaling factor); it is defined as a percentage of the font size. That is, for a 10 pt font, a letter spacing parameter of ‘1.0’ will add 0.1 pt between each letter.

```
\fontspec{Didot}
\addfontfeature{LetterSpace=0.0}
  USE TRACKING FOR DISPLAY CAPS TEXT \\
\addfontfeature{LetterSpace=2.0}
  USE TRACKING FOR DISPLAY CAPS TEXT
```

This functionality *should not be used for lowercase text*, which is spacing correctly to begin with, but it can be very useful, in small amounts, when setting small caps or all caps titles. Also see the OpenType Uppercase option of the Letters feature ([Section 12.2 on page 31](#)).

#### 11.3 Font transformations

In rare situations users may want to mechanically distort the shapes of the glyphs in the current font. Please don’t overuse these features; they can be extremely ugly if overused.

```
\fontspec[Charis SIL] \emph{ABCxyz} \quad
\fontspec[FakeSlant=0.2]{Charis SIL} ABCxyz
```

```
\fontspec[Charis SIL] ABCxyz \quad
\fontspec[FakeStretch=1.2]{Charis SIL} ABCxyz
```

```
\fontspec{Charis SIL} \textbf{ABCxyz} \quad
\fontspec[FakeBold=1.5]{Charis SIL} ABCxyz
```

If values are omitted, their defaults are as shown above.

## 11.4 Different font technologies: AAT and ICU

X<sub>E</sub>T<sub>E</sub>X supports two rendering technologies for typesetting, selected with the Renderer font feature. The first, AAT, is that provided (only) by Mac OS X itself. The second, ICU, is an open source OpenType interpreter. It provides much greater support for OpenType features, notably contextual arrangement, over AAT.

In general, this feature will not need to be explicitly called: for OpenType fonts, the ICU renderer is used automatically, and for AAT fonts, AAT is chosen by default. Some fonts, however, will contain font tables for *both* rendering technologies, such as the Hiragino Japanese fonts distributed with Mac OS X, and in these cases the choice may be required.

Among some other font features only available through a specific renderer, ICU provides for the Script and Language features, which allow different font behaviour for different alphabets and languages; see [Section 10.15 on page 26](#) for the description of these features. *Because these font features can change which features are able to be selected for the font instance, they are selected by fontspec before all others and will automatically and without warning select the ICU renderer.*

## 11.5 Optical font sizes

Multiple Master fonts are parameterised over orthogonal font axes, allowing continuous selection along such features as weight, width, and optical size (see [Section 13 on page 36](#) for further details). Whereas an OpenType font will have only a few separate optical sizes, a Multiple Master font's optical size can be specified over a continuous range. Unfortunately, this flexibility makes it harder to create an automatic interface through L<sub>A</sub>T<sub>E</sub>X, and the optical size for a Multiple Master font must always be specified explicitly.

```
\fontspec[OpticalSize=11]{Minion MM Roman}
  MM optical size test          \\
\fontspec[OpticalSize=47]{Minion MM Roman}
  MM optical size test          \\
\fontspec[OpticalSize=71]{Minion MM Roman}
  MM optical size test          \\
```

## 12 Mac OS X's AAT fonts

Mac OS X's font technology began life before the ubiquitous-OpenType era and revolved around the Apple-invented 'AAT' font format. This format had some advantages (and other disadvantages) but it never became widely popular in the font world.

Nonetheless, this is the font format that was first supported by X<sub>E</sub>T<sub>E</sub>X (due to its pedigree on Mac OS X in the first place) and was the first font format supported by fontspec. A number of fonts distributed with Mac OS X are still in the AAT format, such as ‘Skia’. Documents that use these fonts should be compiled with X<sub>E</sub>L<sub>A</sub>T<sub>E</sub>X using the xdv2pdf driver, as opposed to the default xdvipdfmx. E.g.,

```
xelatex -output-driver="xdv2pdf" filename.tex
```

Mac OS X also supports Multiple Master fonts, which are discussed in [Section 13](#).

## 12.1 Ligatures

Ligatures refer to the replacement of two separate characters with a specially drawn glyph for functional or æsthetic reasons. For AAT fonts, you may choose from any combination of Required, Common, Rare (or Discretionary), Logos, Rebus, Diphthong, Squared, AbbrevSquared, and Icelandic.

Some other Apple AAT fonts have those ‘Rare’ ligatures contained in the Icelandic feature. Notice also that the old T<sub>E</sub>X trick of splitting up a ligature with an empty brace pair does not work in X<sub>E</sub>T<sub>E</sub>X; you must use a 0pt kern or \hbox (e.g., \null) to split the characters up.

## 12.2 Letters

The Letters feature specifies how the letters in the current font will look. For AAT fonts, you may choose from Normal, Uppercase, Lowercase, SmallCaps, and InitialCaps.

## 12.3 Numbers

The Numbers feature defines how numbers will look in the selected font. For both AAT, they may be a combination of Lining or OldStyle and Proportional or Monospaced (the latter is good for tabular material). The synonyms Uppercase and Lowercase are equivalent to Lining and OldStyle, respectively. The differences have been shown previously in [Section 7.2 on page 12](#).

## 12.4 Contextuals

This feature refers to glyph substitution that vary by their position; things like contextual swashes are implemented here. The options for AAT fonts are WordInitial, WordFinal, LineInitial, LineFinal, and Inner (also called ‘non-final’ sometimes). As non-exclusive selectors, like the ligatures, you can turn them off by prefixing their name with No.

```
\newfontface\fancy
[Contextuals={WordInitial,WordFinal}]
{Hoefler Text Italic}
\fancy where is all the vegemite
```

```
\fontspec[Contextuals=Inner]{Hoefler Text}
'Inner' swashes can \emph{sometimes} \\ 
contain the archaic long~s.
```

## 12.5 Vertical position

The `VerticalPosition` feature is used to access things like subscript (`Inferior`) and superscript (`Superior`) numbers and letters (and a small amount of punctuation, sometimes). The `Ordinal` option is (supposed to be) contextually sensitive to only raise characters that appear directly after a number.

```
\fontspec{Skia}
Normal
\fontspec[VerticalPosition=Superior]{Skia}
Superior
\fontspec[VerticalPosition=Inferior]{Skia}
Inferior \\ 
\fontspec[VerticalPosition=Ordinal]{Skia}
1st 2nd 3rd 4th 0th 8abcde
```

The `xltxtra` package redefines the `\textsubscript` and `\textsuperscript` commands to use the above font features.

## 12.6 Fractions

Many fonts come with the capability to typeset various forms of fractional material. This is accessed in `fontspec` with the `Fractions` feature, which may be turned On or Off in both AAT and OpenType fonts.

In AAT fonts, the ‘fraction slash’ or solidus character, is to be used to create fractions. When `Fractions` are turned On, then only pre-drawn fractions will be used.

```
\fontspec[Fractions=On]{Skia}
12 \quad 56 \\ % fraction slash
1/2 \quad 5/6   % regular slash
```

Using the `Diagonal` option (AAT only), the font will attempt to create the fraction from superscript and subscript characters. This is shown in the following example:

```
\fontspec[Fractions=Diagonal]{Skia}
1357924680 \\ % fraction slash
\quad 13579/24680 % regular slash
```

Some (Asian fonts predominantly) also provide for the `Alternate` feature:

```
\fontspec{Hiragino Maru Gothic Pro W4}
1/2 \quad 1/4 \quad 5/6 \quad 13579/24680 \\
\addfontfeature{Fractions=Alternate}
1/2 \quad 1/4 \quad 5/6 \quad 13579/24680 \\
```

The `xltxtra` package provides a `\vfrac` command for creating arbitrary so-called ‘vulgar’ fractions:

```
\fontspec{Warnock Pro}
\vfrac{13579}{24680}
```

## 12.7 Variants

The Variant feature takes a single numerical input for choosing different alphabetic shapes. Don't mind my fancy example :) I'm just looping through the nine (!) variants of Zapfino.

```
\whiledo{\value{var}9}{% % \stepcounter{trans}% % \fontspec[Variant=\thevar, Color=005599\thetrans\thetrans]{Zapfino}% % \makebox[0.75\width]{d}% % \stepcounter{var}}
```

See [Section 14 on page 37](#) for a way to assign names to variants, which should be done on a per-font basis.

## 12.8 Alternates

Selection of Alternates *again* must be done numerically. Here's an example with an AAT font:

```
\fontspec[Alternate=0]{Hoefler Text Italic}
Sphinx Of Black Quartz, {\scshape Judge My Vow} \\
\fontspec[Alternate=1]{Hoefler Text Italic}
Sphinx Of Black Quartz, {\scshape Judge My Vow}
```

See [Section 14 on page 37](#) for a way to assign names to alternates, which should be done on a per-font basis.

## 12.9 Style

The options of the Style feature are defined in AAT as one of the following: Display, Engraved, IlluminatedCaps, Italic, Ruby,<sup>5</sup> TallCaps, or TitlingCaps.

```
\fontspec{Warnock Pro}
K Q R k v w y \\
\addfontfeature{Style=Alternate}
K Q R k v w y
```

Note the occasional inconsistency with which font features are labelled; a long-tailed 'Q' could turn up anywhere!

```
\fontspec{Adobe Jenson Pro}
M Q Z \\
\addfontfeature{Style=Historic}
M Q Z

\fontspec{Adobe Garamond Pro}
TITLING CAPS \\
\addfontfeature{Style=TitlingCaps}
TITLING CAPS
```

Two features in one example; Italic affects the Latin text and Ruby the Japanese:

---

<sup>5</sup>'Ruby' refers to a small optical size, used in Japanese typography for annotations.

```
\fontspec{Hiragino Mincho Pro W3}
    Latin      \\
\addfontfeature{Style={Italic, Ruby}}
    Latin
```

Note the difference here between the default and the horizontal style kana:

```
\fontspec{Hiragino Mincho Pro}
    \\
{\addfontfeature{Style=HorizontalKana}
} \\
{\addfontfeature{Style=VerticalKana}
}
```

## 12.10 CJK shape

There have been many standards for how CJK ideographic glyphs are ‘supposed’ to look. Some fonts will contain many alternate glyphs available in order to be able to display these glyphs correctly in whichever form is appropriate. Both AAT and OpenType fonts support the following CJKShape options: Traditional, Simplified, JIS1978, JIS1983, JIS1990, and Expert. OpenType also supports the NLC option.

## 12.11 Character width

Many Asian fonts are equipped with variously spaced characters for shoe-horning into their generally monospaced text. These are accessed through the CharacterWidth feature.<sup>6</sup> For now, OpenType and AAT share the same six options for this feature: Proportional, Full, Half, Third, Quarter, AlternateProportional, and AlternateHalf. AAT also allows Default to return to whatever was originally specified.

Japanese alphabetic glyphs (in Hiragana or Katakana) may be typeset proportionally, to better fit horizontal measures, or monospaced, to fit into the rigid grid imposed by ideographic typesetting. In this latter case, there are also half-width forms for squeezing more kana glyphs (which are less complex than the kanji they are amongst) into a given block of space. The same features are given to roman letters in Japanese fonts, for typesetting foreign words in the same style as the surrounding text.

```
\def\test{\makebox[2cm][1]{}} %           \makebox[2.5cm][1]{ }%           \makebox[2.5cm][1]{abcdef}%
\fontspec{Hiragino Mincho Pro}
{\addfontfeature{CharacterWidth=Proportional}\test}\\
{\addfontfeature{CharacterWidth=Full}\test}\\
{\addfontfeature{CharacterWidth=Half}\test}
```

---

<sup>6</sup>Apple seems to be adapting its AAT features in this regard (at least in the fonts it distributes with Mac OS X) to have a one-to-one correspondence with the equivalent OpenType features. Previously AAT was more fine grained, but naturally they’re not documenting their AAT tables any more, so if the following features don’t work for a specific font let me know and I’ll try and see if anything can be salvaged from the situation.

The same situation occurs with numbers, which are provided in increasingly illegible compressed forms:

```
\fontspec[Renderer=AAT]{Hiragino Mincho Pro}
{\addfontfeature{CharacterWidth=Full}
 ---12321---}\\
{\addfontfeature{CharacterWidth=Half}
 ---1234554321---}\\
{\addfontfeature{CharacterWidth=Third}
 ---123456787654321---}\\
{\addfontfeature{CharacterWidth=Quarter}
 ---12345678900987654321---}
```

The option `CharacterWidth=Full` doesn't work with the default OpenType font renderer (ICU) due to a bug in the Hiragino fonts.

## 12.12 Annotation

Various Asian fonts are equipped with a more extensive range of numbers and numerals in different forms. For OpenType fonts, the only option supported is `On` and `Off`:

```
\fontspec{Hiragino Maru Gothic Pro}
 1 2 3 4 5 6 7 8 9 \\ 
 \addfontfeature{Annotation=On}
 1 2 3 4 5 6 7 8 9
```

I'm not sure if X<sub>E</sub>T<sub>E</sub>X can access alternate annotation forms, even if they exist (as in this case) in the font.

## 12.13 Vertical typesetting

X<sub>E</sub>T<sub>E</sub>X provides for vertical typesetting simply with the ability to rotate the individual glyphs as a font is used for typesetting.

```
\fontspec{Hiragino Mincho Pro}
```

```
\fontspec[Renderer=AAT,Vertical=RotatedGlyphs]{Hiragino Mincho Pro}
\rotatebox{-90}{}% requires the graphicx package
```

No actual provision is made for typesetting top-to-bottom languages; for an example of how to do this, see the vertical Chinese example provided in the X<sub>E</sub>T<sub>E</sub>X documentation.

## 12.14 Diacritics

Diacritics refer to characters that include extra marks that usually indicate pronunciation; *e.g.*, accented letters. You may either choose to `Show`, `Hide` or `Decompose` them in AAT fonts.

Some fonts include Ø etc. as diacritics for writing Ø. You'll want to turn this feature off (imagine typing hello/goodbye and getting 'helløgoodbye' instead!) by

decomposing the two characters in the diacritic into the ones you actually want. I would recommend using the proper `\TeX` input conventions for obtaining such characters instead.

The `Hide` option is for Arabic-like fonts which may be displayed either with or without vowel markings.

## 12.15 Annotation

Various Asian fonts are equipped with a more extensive range of numbers and numerals in different forms. These are accessed through the `Annotation` feature with the following options: `Off`, `Box`, `RoundedBox`, `Circle`, `BlackCircle`, `Parenthesis`, `Period`, `RomanNumerals`, `Diamond`, `BlackSquare`, `BlackRoundSquare`, and `DoubleCircle`.

```
\fontspec{Hei Regular}
  1 2 3 4 5 6 7 8 9
\fontspec[Annotation=Circle]{Hei Regular}
  1 2 3 4 5 6 7 8 9
\fontspec[Annotation=Parenthesis]{Hei Regular}
  1 2 3 4 5 6 7 8 9
\fontspec[Annotation=Period]{Hei Regular}
  1 2 3 4 5 6 7 8 9
```

## 13 AAT & Multiple Master font axes

Multiple Master and `AAT` font specifications both provide continuous variation along font parameters. For example, they don't have just regular and bold weights, they can have any bold weight you like between the two extremes.

`Weight`, `Width`, and `OpticalSize` are supported by this package. `Skia`, which is distributed with Mac OS X, has two of these variable parameters, allowing for a demonstration:

```
\fontspec[Weight=0.5,Width=3]{Skia}
  Really light and extended Skia      \\
\fontspec[Weight=2,Width=0.5]{Skia}
  Really fat and condensed Skia
```

Variations along a multiple master font's optical size axis has been shown previously in [Section 11.5 on page 30](#).

# Part IV

# Programming interface

This is the beginning of some work to provide some hooks that use `fontspec` for various macro programming purposes.

## 14 Defining new features

This package cannot hope to contain every possible font feature. Three commands are provided for selecting font features that are not provided for out of the box. If you are using them a lot, chances are I've left something out, so please let me know.

`\newAATfeature`

New AAT features may be created with this command:

```
\newAATfeature{<feature>}{{<option>}}{<feature code>}{{<selector code>}}
```

Use the `XeTeX` file `AAT-info.tex` to obtain the code numbers. For example:

```
\newAATfeature{Alternate}{HoeflerSwash}{17}{1}
\fontspec[Alternate=HoeflerSwash]{Hoefler Text Italic}
This is XeTeX by Jonathan Kew.
```

This command replaces `\newfeaturecode`, which is provided for backwards compatibility via `fontspec.cfg`.

New OpenType features may be created with this command:

```
\newICUfeature{<feature>}{{<option>}}{<feature tag>}
```

The synonym `\newopentypefeature` is provided for `LuaTeX` users. In the following example, the Moldavian language (see [Section 10.15 on page 26](#)) must be activated to achieve the effect shown.

```
\newICUfeature{Style}{NoLocalForms}{-locl}
\fontspec[Language=Moldavian]{FPL Neu}
 \\
\addfontfeature{Style=NoLocalForms}
```

`\newfontfeature`

In case the above commands do not accommodate the desired font feature (perhaps a new `XeTeX` feature that `fontspec` hasn't been updated to support), a command is provided to pass arbitrary input into the font selection string:

```
\newfontfeature{<name>}{{<input string>}}
```

For example, Zapfino contains the feature 'Avoid d-collisions'. To access it with this package, you could do the following:

```
\newfontfeature{AvoidD}{Special=Avoid d-collisions}
\newfontfeature{NoAvoidD}{Special=!Avoid d-collisions}
\fontspec[AvoidD,Variant=1]{Zapfino}
  sockdolager rubdown
  \\\
\fontspec[NoAvoidD,Variant=1]{Zapfino}
  sockdolager rubdown
```

The advantage to using the `\newAATfeature` and `\newICUfeature` commands is that they check if the selected font actually contains the font feature. By contrast, `\newfontfeature` will not give a warning for improper input.

## 15 Going behind fontspec's back

Expert users may wish not to use fontspec's feature handling at all, while still taking advantage of its L<sup>A</sup>T<sub>E</sub>X font selection conveniences. The RawFeature font feature allows literal X<sub>H</sub>T<sub>E</sub>X font feature selection when you happen to have the OpenType feature tag memorised.

```
\fontspec[RawFeature=+smcp]{FPL Neu}
FPL Neu small caps
```

Multiple features can either be included in a single declaration:

```
[RawFeature=+smcp;+onum]
```

or with multiple declarations:

```
[RawFeature=+smcp, RawFeature=+onum]
```

## 16 Renaming existing features & options

`\aliasfontfeature` If you don't like the name of a particular font feature, it may be aliased to another with the `\aliasfontfeature{<existing name>}{<new name>}` command:

```
\aliasfontfeature{ItalicFeatures}{IF}
\fontspec[IF = {Alternate=1}]{Hoefler Text}
Roman Letters \itshape And Swash
```

Spaces in feature (and option names, see below) *are* allowed. (You may have noticed this already in the lists of OpenType scripts and languages).

`\aliasfontfeatureoption` If you wish to change the name of a font feature option, it can be aliased to another with the command `\aliasfontfeatureoption{<font feature>}{<existing name>}{<new name>}`:

```
\aliasfontfeature{VerticalPosition}{Vert Pos}
\aliasfontfeatureoption{VerticalPosition}{ScientificInferior}{Sci Inf}
\fontspec[Vert Pos=Sci Inf]{Warnock Pro}
Scientific Inferior: 12345
```

This example demonstrates an important point: when aliasing the feature options, the *original* feature name must be used when declaring to which feature the option belongs.

Only feature options that exist as sets of fixed strings may be altered in this way. That is, Proportional can be aliased to Prop in the Letters feature, but 550099BB cannot be substituted for Purple in a Color specification. For this type of thing, the `\newfontfeature` command should be used to declare a new, e.g., PurpleColor feature:

```
\newfontfeature{PurpleColor}{color=550099BB}
```

## 17 Programming details

In some cases, it is useful to know what the L<sup>A</sup>T<sub>E</sub>X font family of a specific fontspec font is. After a `\fontspec`-like command, this is stored inside the `\zf@family`

macro. Otherwise, L<sup>A</sup>T<sub>E</sub>X's own \f@family macro can be useful here, too. The raw T<sub>E</sub>X font that is defined is stored temporarily in \zf@basefont.

The following commands in expl3 syntax may be used for writing codes that interface with fontspec-loaded fonts. All of the following conditionals also exist with T and F suffices as well as TF.

\fontspec_if_fontsypc_font:TF	Test whether the currently selected font has been loaded by fontsypc.
\fontspec_if_aat_feature:nnTF	Test whether the currently selected font contains the AAT feature (#1,#2).
\fontspec_if_opentype:TF	Test whether the currently selected font is an OpenType font. Always true for L <sup>A</sup> T <sub>E</sub> X fonts.
\fontspec_if_feature:nTF	Test whether the currently selected font contains the raw OpenType feature #1. E.g.: \fontspec_if_feature:nTF {pnum} {True} {False}. Returns false if the font is not loaded by fontsypc or is not an OpenType font.
\fontspec_if_feature:nnnTF	Test whether the currently selected font with raw OpenType script tag #1 and raw OpenType language tag #2 contains the raw OpenType feature tag #3. E.g.: \fontspec_if_feature:nTF {latn} {ROM} {pnum} {True} {False}. Returns false if the font is not loaded by fontsypc or is not an OpenType font.
\fontspec_if_script:nTF	Returns whether the currently selected font contains the raw OpenType script #1. E.g.: \fontspec_if_script:nTF {latn} {True} {False}. Returns false if the font is not loaded by fontsypc or is not an OpenType font.
\fontspec_if_language:nTF	Test whether the currently selected font contains the raw OpenType feature #1. E.g.: \fontspec_if_feature:nTF {pnum} {True} {False}. Returns false if the font is not loaded by fontsypc or is not an OpenType font.
\fontspec_if_language:nnTF	Test whether the currently selected font contains the raw OpenType feature #2 in script #1. E.g.: \fontspec_if_feature:nTF {latn} {pnum} {True} {False}. Returns false if the font is not loaded by fontsypc or is not an OpenType font.
\fontspec_if_current_script:nTF	Test whether the currently loaded font is using the specified raw OpenType script tag #1.
\fontspec_if_current_language:nTF	Test whether the currently loaded font is using the specified raw OpenType language tag #1.

## Part V

# The patching/improvement of L<sup>A</sup>T<sub>E</sub>X 2<sub>&</sub> and other packages

Derived originally from `xltxtra`, this package contains patches to various L<sup>A</sup>T<sub>E</sub>X components and third-party packages to improve the default behaviour.

## 18 Inner emphasis

`fixltx2e`'s method for checking for “inner” emphasis is a little fragile in X<sub>E</sub>T<sub>E</sub>X, because font slant information might be missing from the font. Therefore, we use L<sup>A</sup>T<sub>E</sub>X's NFSS information, which is more likely to be correct.

## 19 Unicode footnote symbols

By default L<sup>A</sup>T<sub>E</sub>X defines symbolic footnote characters in terms of commands that don't resolve well; better results can be achieved by using specific unicode characters or proper LICRs with the `xunicode` package.

This problem has been solved by loading the `fixltx2e` and `xunicode` packages in `xltxtra`.

## 20 Verbatim

Many verbatim mechanisms assume the existence of a ‘visible space’ character that exists in the ASCII space slot of the typewriter font. This character is known in unicode as U+2434: BOX OPEN, which looks like this: ‘\_’.

When a unicode typewriter font is used, L<sup>A</sup>T<sub>E</sub>X no longer prints visible spaces for the `\verb*` environment and `\verb*` command. `xltxtra` fixes this problem by using the correct unicode glyph, and patches the following packages to do the same: `listings`, `fancyvrb`, `moreverb`, and `verbatim`.

In the case that the typewriter font does not contain ‘\_’, the Latin Modern Mono font is used as a fallback.

## 21 Discretionary hyphenation: \-

L<sup>A</sup>T<sub>E</sub>X defines the macro `\-` to insert discretionary hyphenation points. However, it is hard-coded in L<sup>A</sup>T<sub>E</sub>X to use the hyphen - character. Since `fontspec` makes it easy to change the hyphenation character on a per font basis, it would be nice if `\-` adjusted automatically and now it does.

# Part VI

## fontspec.sty

### 22 Implementation

Herein lie the implementation details of this package. Welcome! It was my first.

For some reason, I decided to prefix all the package internal command names and variables with zf. I don't know why I chose those letters, but I guess I just liked the look/feel of them together at the time. (Possibly inspired by Hermann Zapf.)

```
1 \RequirePackage{expl3,xparse}
2 \ExplSyntaxOn
3 \msg_new:nnn {fontspec} {not-pdfTeX}
4 {
5   Requires XeTeX or LuaTeX to function!
6 }
7 \xetex_if_engine:F {
8   \luatex_if_engine:TF {
9     \RequirePackage{luatextra}[2010/05/10]
10    \luatexRequireModule{fontspec}
11  }
12  \msg_error:nn {fontspec} {not-pdfTeX}
13 }
14 }
```

\xetex\_or\_luatex:nn Use #1 if X<sub>E</sub>T<sub>E</sub>X or #2 if LuaT<sub>E</sub>X.

```
15 \xetex_if_engine:TF
16 { \cs_new_eq:NN \xetex_or_luatex:nn \use_i:nn }
17 { \luatex_if_engine:T
18   { \cs_new_eq:NN \xetex_or_luatex:nn \use_ii:nn }
19 }
```

\xetex\_or\_luatex:nnn Use #1 and (#2) if X<sub>E</sub>T<sub>E</sub>X or (#3) if LuaT<sub>E</sub>X.

```
20 \xetex_if_engine:TF
21 { \cs_new:Npn \xetex_or_luatex:nnn #1#2#3 {\#1{\#2}} }
22 {
23   \luatex_if_engine:T
24   { \cs_new:Npn \xetex_or_luatex:nnn #1#2#3 {\#1{\#3}} }
25 }
```

#### 22.1 Bits and pieces

##### Conditionals

```
26 \newif\ifzf@firsttime
27 \newif\ifzf@nobf
28 \newif\ifzf@noit
29 \newif\ifzf@nosc
30 \newif\ifzf@tfm
```

```

31 \newif\ifzf@atsui
32 \newif\ifzf@icu
33 \newif\ifzf@mml
34 \newif\ifzf@graphite

```

For dealing with legacy maths

```

35 \newif\ifzf@math@euler
36 \newif\ifzf@math@lucida
37 \newif\ifzf@package@euler@loaded

```

For package options:

```

38 \newif\ifzf@configfile
39 \newif\ifzf@math

```

## Counters

```

40 \newcount\c@zf@newff
41 \newcount\c@zf@index
42 \newcount\c@zf@script
43 \newcount\c@zf@language
44 \int_new:N \l_fonts_spec_strnum_int

```

Temporary definition until expl3 has been updated to include this:

```

45 \cs_set:Npn \use:x #1 { \edef\@tempa{#1}\@tempa }
46 \cs_new:Npn \fontspec_setkeys:xx #1#2
47 {
48   \use:x { \exp_not:N \setkeys*[zf]{#1}{#2} }
49 }
50 \cs_new:Npn \fontspec_setkeys:xxx #1#2#3
51 {
52   \use:x { \exp_not:N \setkeys*[zf@#1]{#2}{#3} }
53 }

```

## 22.2 Error/warning messages

Shorthands for messages:

```

54 \cs_new:Npn \fontspec_error:n      { \msg_error:nn      {fontspec} }
55 \cs_new:Npn \fontspec_error:nx     { \msg_error:nnx     {fontspec} }
56 \cs_new:Npn \fontspec_warning:n    { \msg_warning:nn    {fontspec} }
57 \cs_new:Npn \fontspec_warning:nx   { \msg_warning:nnx   {fontspec} }
58 \cs_new:Npn \fontspec_warning:nxx  { \msg_warning:nnxx  {fontspec} }
59 \cs_new:Npn \fontspec_info:n       { \msg_info:nn       {fontspec} }
60 \cs_new:Npn \fontspec_info:nx      { \msg_info:nnx      {fontspec} }
61 \cs_new:Npn \fontspec_info:nxx    { \msg_info:nnxx    {fontspec} }
62 \cs_new:Npn \fontspec_trace:n     { \msg_trace:nn     {fontspec} }

```

Errors:

```

63 \msg_new:nnn {fontspec} {no-size-info}
64 {
65   Size~ information~ must~ be~ supplied.\\
66   For~ example,~ SizeFeatures={Size={8-12},...}.
67 }
68 \msg_new:nnnn {fontspec} {rename-feature-not-exist}

```

```

69 {
70   The~ feature~ #1~ doesn't~ appear~ to~ be~ defined.
71 }
72 {
73   It~ looks~ like~ you're~ trying~ to~ rename~ a~ feature~ that~ doesn't~ exist.
74 }
75 \msg_new:nnn {fontspec} {no-glyph}
76 {
77   '\zf@fontname'~ doesn't~ appear~ to~ have~ the~ glyph~ corresponding~ to~ '#1'.
78 }
79 \msg_new:nnnn {fontspec} {unknown-options}
80 {
81   The~ following~ font~ options~ are~ not~ recognised:\\
82   \space\space\space\space #1
83 }
84 {
85   There~ is~ probably~ a~ typo~ in~ the~ font~ feature~ selection.
86 }
87 \msg_new:nnnn {fontspec} {euler-too-late}
88 {
89   The~ euler~ package~ must~ be~ loaded~ BEFORE~ fontspec.
90 }
91 {
92   fontspec~ only~ overwrites~ euler's~ attempt~ to\\
93   define~ the~ maths~ text~ fonts~ if~ fontspec~ is\\
94   loaded~ after~ euler.~ Type~ return~ to~ proceed\\
95   with~ incorrect~ \string\mathit{,}~ \string\mathbf{,}~ etc.
96 }
97

```

### Warnings:

```

98 \msg_new:nnn {fontspec} {addfontfeatures-ignored}
99 {
100  \string\addfontfeature (s)~ ignored;\\
101  it~ cannot~ be~ used~ with~ a~ font~ that~ wasn't~ selected~ by~ fontspec.
102 }
103 \msg_new:nnn {fontspec} {feature-option-overwrite}
104 {
105  Option~ '#2'~ of~ font~ feature~ '#1'~ overwritten.
106 }
107 \msg_new:nnn {fontspec} {script-not-exist}
108 {
109  Font~ '\zf@fontname'~ does~ not~ contain~ script~ '#1'.
110 }
111 \msg_new:nnn {fontspec} {aat-feature-not-exist}
112 {
113  '\XKV@tfam=\XKV@tkey'~ feature~ not~ supported\\
114  for~ AAT~ font~ '\zf@fontname'.
115 }
116 \msg_new:nnn {fontspec} {aat-feature-not-exist-in-font}
117 {
118  AAT~ feature~ '\XKV@tfam=\XKV@tkey'~ (#1)~ not~ available\\

```

```

119  in~ font~ '\zf@fontname'.
120 }
121 \msg_new:nnn {fontspec} {icu-feature-not-exist}
122 {
123   '\XKV@tfam=\XKV@tkey'~ feature~ not~ supported\\
124   for~ ICU~ font~ '\zf@fontname'
125 }
126 \msg_new:nnn {fontspec} {icu-feature-not-exist-in-font}
127 {
128   OpenType~ feature~ '\XKV@tfam=\XKV@tkey'~ (#1)~ not~ available\\
129   for~ font~ '\zf@fontname', \\
130   with~ script~ '\l_fontsname_t1',~ and~ language~ '\l_fontsname_t1'.
131 }
132 \msg_new:nnn {fontspec} {no-opticals}
133 {
134   '\zf@fontname'~ doesn't~ appear~ to~ have~ an~ Optical~ Size~ axis.
135 }
136 \msg_new:nnn {fontspec} {language-not-exist}
137 {
138   Language~ '#1'~ not~ available\\
139   for~ font~ '\zf@fontname'\\
140   with~ script~ '\l_fontsname_t1'.
141 }
142 \msg_new:nnn {fontspec} {only-xetex-feature}
143 {
144   Ignored~ XeTeX~ only~ feature:~ '#1'.
145 }
146 \msg_new:nnn {fontspec} {only-luatex-feature}
147 {
148   Ignored~ LuaTeX~ only~ feature:~ '#1'.
149 }
150 \msg_new:nnn {fontspec} {no-mapping}
151 {
152   Input~ mapping~ not~ (yet?)~ supported~ in~ LaTeX.
153 }
154 \msg_new:nnn {fontspec} {no-mapping-ligtex}
155 {
156   Input~ mapping~ not~ (yet?)~ supported~ in~ LaTeX.\\
157   Use~ "Ligatures=TeX"~ instead~ of~ "Mapping=tex-text".
158 }
159 \msg_new:nnn {fontspec} {cm-default-obsolete}
160 {
161   The~ "cm-default"~ package~ option~ is~ obsolete.
162 }

Info messages:
163 \msg_new:nnn {fontspec} {defining-font}
164 {
165   Defining~ font~ family~ for~ '#2'~ with~ options~ [\zf@default@options #1].
166 }
167 \msg_new:nnn {fontspec} {no-font-shape}
168 {

```

```

169 Could~ not~ resolve~ font~ #1~ (it~ probably~ doesn't~ exist).
170 }
171 \msg_new:nnn {fontspec} {set-scale}
172 {
173   \zf@fontname\space scale ~=~ \l_fonts表白_scale_tl.
174 }
175 \msg_new:nnn {fontspec} {setup-math}
176 {
177   Adjusting~ the~ maths~ setup~ (use~ [no-math]~ to~ avoid~ this).
178 }

```

## 22.3 Option processing

```

179 \DeclareOption{cm-default}{
180   \fontspec_warning:n {cm-default-obsolete}
181 }
182 \DeclareOption{math}{\@zf@mathtrue}
183 \DeclareOption{no-math}{\@zf@mathfalse}
184 \DeclareOption{config}{\@zf@configfiletrue}
185 \DeclareOption{no-config}{\@zf@configfilefalse}
186 \DeclareOption{quiet}{
187   \msg_redirect_module:nnn { fontspec } { warning } { info }
188   \msg_redirect_module:nnn { fontspec } { info } { none }
189 }
190 \DeclareOption{silent}{
191   \msg_redirect_module:nnn { fontspec } { warning } { none }
192   \msg_redirect_module:nnn { fontspec } { info } { none }
193 }
194 \ExecuteOptions{config,math}
195 \ProcessOptions*

```

## 22.4 Packages

We require the calc package for autoscaling and a recent version of the xkeyval package for option processing.

```

196 \RequirePackage{calc}
197 \RequirePackage{xkeyval}[2005/05/07]

```

New for LuaTeX, we load a new package called ‘fontspec-patches’ designed to incorporate the hidden but useful parts of the old xltextra package.

```
198 \luatex_if_engine:T { \RequirePackage{fontspec-patches} }
```

## 22.5 Encodings

Frank Mittelbach has recommended using the ‘EUx’ family of font encodings to experiment with unicode. Now that XeTeX can find fonts in the texmf tree, the Latin Modern OpenType fonts can be used as the defaults. See the euenc collection of files for how this is implemented.

```

199 \xetex_or_luatex:nnn {\tl_set:Nn \zf@enc} {EU1} {EU2}
200 \tl_set:Nn \rmdefault {lmr}
201 \tl_set:Nn \sfdefault {lmss}

```

```

202 \tl_set:Nn \ttdefault {lmtt}
203 \RequirePackage[\zf@enc]{fontenc}
204 \tl_set_eq:NN \UTFencname \zf@enc % for xunicode

```

Dealing with a couple of the problems introduced by babel:

```

205 \tl_set_eq:NN \cyrillicencoding \zf@enc
206 \tl_set_eq:NN \latinencoding \zf@enc
207 \g@addto@macro \document {
208   \tl_set_eq:NN \cyrillicencoding \zf@enc
209   \tl_set_eq:NN \latinencoding \zf@enc
210 }

```

That latin encoding definition is repeated to suppress font warnings. Something to do with \select@language ending up in the .aux file which is read at the beginning of the document.

## 22.6 User commands

This section contains the definitions of the commands detailed in the user documentation. Only the ‘top level’ definitions of the commands are contained herein; they all use or define macros which are defined or used later on in [Section 22.8 on page 54](#).

### 22.6.1 Font selection

\fontspec This is the main command of the package that selects fonts with various features. It takes two arguments: the Mac OS X font name and the optional requested features of that font. It simply runs \zf@fontspec, which takes the same arguments as the top level macro and puts the new-fangled font family name into the global \zf@family. Then this new font family is selected.

```

211 \DeclareDocumentCommand \fontspec { O{} m } {
212   \fontspec_select:nn{#1}{#2}
213   \fontfamily\zf@family\selectfont
214   \ignorespaces
215 }

```

\setmainfont \setsansfont \setmonofont The following three macros perform equivalent operations setting the default font (using \let rather than \renewcommand because \zf@family will change in the future) for a particular family: ‘roman’, sans serif, or typewriter (monospaced). I end them with \normalfont so that if they’re used in the document, the change registers immediately.

```

216 \DeclareDocumentCommand \setmainfont { O{} m } {
217   \fontspec_select:nn{#1}{#2}
218   \tl_set_eq:NN \rmdefault \zf@family
219   \normalfont
220 }
221 \DeclareDocumentCommand \setsansfont { O{} m } {
222   \fontspec_select:nn{#1}{#2}
223   \tl_set_eq:NN \sfdefault \zf@family
224   \normalfont
225 }

```

```

226 \DeclareDocumentCommand \setmonofont { O{} m } {
227   \fontspec_select:nn{#1}{#2}
228   \tl_set_eq:NN \ttdefault \zf@family
229   \normalfont
230 }

\setromanfont This is the old name for \setmainfont, retained for backwards compatibility.
231 \cs_set_eq:NN \setromanfont \setmainfont

\setmathrm These commands are analogous to \setromanfont and others, but for selecting the
\setmathsf font used for \mathrm, etc. They can only be used in the preamble of the document.
\setboldmathrm \setboldmathrm is used for specifying which fonts should be used in \boldmath.

\setmathtt 232 \DeclareDocumentCommand \setmathrm { O{} m } {
233   \fontspec_select:nn{#1}{#2}
234   \let\zf@rmmaths\zf@family
235 }
236 \DeclareDocumentCommand \setboldmathrm { O{} m } {
237   \fontspec_select:nn{#1}{#2}
238   \let\zf@rboldmaths\zf@family
239 }
240 \DeclareDocumentCommand \setmathsf { O{} m } {
241   \fontspec_select:nn{#1}{#2}
242   \let\zf@sffmaths\zf@family
243 }
244 \DeclareDocumentCommand \setmathtt { O{} m } {
245   \fontspec_select:nn{#1}{#2}
246   \let\zf@ttmaths\zf@family
247 }
248 \@onlypreamble\setmathrm
249 \@onlypreamble\setboldmathrm
250 \@onlypreamble\setmathsf
251 \@onlypreamble\setmathtt

If the commands above are not executed, then \rmdefault (etc.) will be used.

252 \def\zf@rmmaths{\rmdefault}
253 \def\zf@sffmaths{\sfdefault}
254 \def\zf@ttmaths{\ttdefault}

\newfontfamily \newfontfamily This macro takes the arguments of \fontspec with a prepended <instance cmd>
\newfontface (code for middle optional argument generated by Scott Pakin's newcommand.py).
This command is used when a specific font instance needs to be referred to repetitively (e.g., in a section heading) since continuously calling \zf@fontspec is inefficient because it must parse the option arguments every time.

\zf@fontspec defines a font family and saves its name in \zf@family. This family is then used in a typical NFSS \fontfamily declaration, saved in the macro name specified.

255 \DeclareDocumentCommand \newfontfamily { m O{} m } {
256   \fontspec_select:nn{#2}{#3}
257   \use:x {
258     \exp_not:N \DeclareRobustCommand \exp_not:N #1 {
259       \exp_not:N \fontfamily {\zf@family} \exp_not:N \selectfont

```

```

260      }
261  }
262 }

\newfontface uses an undocumented feature of the BoldFont feature; if its argument is empty (i.e., BoldFont={}), then no bold font is searched for.

263 \DeclareDocumentCommand \newfontface { m O{} m } {
264   \newfontfamily #1 [ BoldFont={},ItalicFont={},SmallCapsFont={},#2 ] {#3}
265 }
```

### 22.6.2 Font feature selection

\defaultfontfeatures	This macro takes one argument that consists of all of feature options that will be applied by default to all subsequent \fontspec, et al., commands. It stores its value in \zf@default@options (initialised empty), which is concatenated with the individual macro choices in the \zf@get@feature@requests macro.
\addfontfeatures	<p>In order to be able to extend the feature selection of a given font, two things need to be known: the currently selected features, and the currently selected font. Every time a font family is created, this information is saved inside a control sequence with the name of the font family itself.</p> <p>This macro extracts this information, then appends the requested font features to add to the already existing ones, and calls the font again with the top level \fontspec command.</p> <p>The default options are <i>not</i> applied (which is why \zf@default@options is emptied inside the group; this is allowed as \zf@family is globally defined in \fontspec_select:nn), so this means that the only added features to the font are strictly those specified by this command.</p> <p>\addfontfeature is defined as an alias, as I found that I often typed this instead when adding only a single font feature.</p> <pre> 268 \DeclareDocumentCommand \addfontfeatures {m} { 269   \ifcsname zf@family@fontdef\f@family\endcsname 270   \begingroup 271     \let\zf@default@options\empty 272     \use:x { 273       \exp_not:N\fontspec_select:nn 274       {\csname zf@family@options\f@family\endcsname,#1} 275       {\csname zf@family@fontname\f@family\endcsname} 276     } 277   \endgroup 278   \fontfamily\zf@family\selectfont 279 \else 280   \fontspec_warning:n {addfontfeatures-ignored} 281 \fi 282 \ignorespaces 283 } 284 \let\addfontfeature\addfontfeatures</pre>

### 22.6.3 Defining new font features

\newfontfeature \newfontfeature takes two arguments: the name of the feature tag by which to reference it, and the string that is used to select the font feature. It uses a counter to keep track of the number of new features introduced; every time a new feature is defined, a control sequence is defined made up of the concatenation of +zf- and the new feature tag. This long-winded control sequence is then called upon to update the font family string when a new instance is requested.

```
285 \DeclareDocumentCommand \newfontfeature {mm} {  
286   \stepcounter{zf@newff}  
287   \cs_set:cpx{+zf-\#1}{+zf-\the\c@zf@newff}  
288   \define@key[zf]{options}{#1}[]{  
289     \zf@update@family{\csname+zf-\#1\endcsname}  
290     \zf@update@ff{#2}  
291   }  
292 }
```

\newAATfeature This command assigns a new AAT feature by its code (#2,#3) to a new name (#1). Better than \newfontfeature because it checks if the feature exists in the font it's being used for.

```
293 \DeclareDocumentCommand \newAATfeature {mmmm} {  
294   \unless\ifcsname zf@options@\#1\endcsname  
295     \zf@define@font@feature{#1}  
296   \fi  
297   \key@ifundefined[zf]{#1}{#2}{}{  
298     \fontspec_warning:nxx {feature-option-overwrite}{#1}{#2}  
299   }  
300   \zf@define@feature@option{#1}{#2}{#3}{#4}{}  
301 }
```

\newICUfeature This command assigns a new OpenType feature by its abbreviation (#2) to a new name (#1). Better than \newfontfeature because it checks if the feature exists in the font it's being used for.

```
302 \DeclareDocumentCommand \newICUfeature {mm} {  
303   \unless\ifcsname zf@options@\#1\endcsname  
304     \zf@define@font@feature{#1}  
305   \fi  
306   \key@ifundefined[zf]{#1}{#2}{}{  
307     \fontspec_warning:nxx {feature-option-overwrite}{#1}{#2}  
308   }  
309   \zf@define@feature@option{#1}{#2}{}{}{#3}  
310 }  
311 \cs_set_eq:NN \newopentypefeature \newICUfeature
```

\aliasfontfeature \aliasfontfeatureoption User commands for renaming font features and font feature options. Provided I've been consistent, they should work for everything.

```
312 \DeclareDocumentCommand \aliasfontfeature {mm} {\multi@alias@key{#1}{#2}}  
313 \DeclareDocumentCommand \aliasfontfeatureoption {mmm} {  
314   \keyval@alias@key[zf@feat]{#1}{#2}{#3}  
315 }
```

\newfontscript Mostly used internally, but also possibly useful for users, to define new OpenType ‘scripts’, mapping logical names to OpenType script tags. Iterates though the scripts in the selected font to check that it’s a valid feature choice, and then prepends the (X)TeX \font feature string with the appropriate script selection tag.

```

316 \DeclareDocumentCommand \newfontscript {mm}
317 {
318   \fontspec_new_script:nn {#1} {#2}
319   \fontspec_new_script:nn {#2} {#2}
320 }

321 \cs_new:Npn \fontspec_new_script:nn #1#2
322 {
323   \define@key[zf@feat]{Script}{#1}[]{%
324     \fontspec_check_script:nTF {#2} {
325       \zf@update@family{+script=#1}
326       \tl_set:Nn \l_fontspec_script_tl {#2}
327       \c@zf@script=\l_fontspec_strnum_int\relax
328     }{
329       \fontspec_warning:nx {script-not-exist} {#1}
330     }
331   }
332 }
```

\newfontlanguage Mostly used internally, but also possibly useful for users, to define new OpenType ‘languages’, mapping logical names to OpenType language tags. Iterates though the languages in the selected font to check that it’s a valid feature choice, and then prepends the (X)TeX \font feature string with the appropriate language selection tag.

```

333 \DeclareDocumentCommand \newfontlanguage {mm}
334 {
335   \fontspec_new_lang:nn {#1} {#2}
336   \fontspec_new_lang:nn {#2} {#2}
337 }

338 \cs_new:Npn \fontspec_new_lang:nn #1#2
339 {
340   \define@key[zf@feat]{Lang}{#1}[]{%
341     \fontspec_check_lang:nTF {#2} {
342       \zf@update@family{+lang=#1}
343       \tl_set:Nn \l_fontspec_lang_tl {#2}
344       \c@zf@language=\l_fontspec_strnum_int\relax
345     }{
346       \fontspec_warning:nx {language-not-exist} {#1}
347     }
348   }
349 }
```

\DeclareFontsExtensions dfont would never be uppercase, right?

```

350 \DeclareDocumentCommand \DeclareFontsExtensions {m}
351 {
352   \tl_set:Nx \l_fontspec_extensions_clist { \zap@space #1^{\emptyset} }
```

```

353 }
354 \DeclareFontsExtensions{.otf,.ttf,.OTF,.TTF,.ttc,.TTC,.dfont}

```

## 22.7 Programmer's interface

These functions are not used directly by fontspec when defining fonts; they are designed to be used by other packages who wish to do font-related things on top of fontspec itself.

Because I haven't fully explored how these functions will behave in practise, I am not giving them user-level names. As it becomes more clear which of these should be accessible by document writers, I'll open them up a little more.

All functions are defined assuming that the font to be queried is currently selected as a fontspec font. (I.e., via \fontspec or from a \newfontfamily macro or from \setmainfont and so on.)

\fontspec\_if\_fontspec\_font:TF Returns whether the currently selected font has been loaded by fontspec.

```

355 \prg_new_conditional:Nnn \fontspec_if_fontspec_font: {TF,T,F} {
356   \ifcsname zf@family@fontdef\f@family\endcsname
357     \prg_return_true:
358   \else
359     \prg_return_false:
360   \fi
361 }

```

\fontspec\_if\_aat\_feature:nnTF Conditional to test if the currently selected font contains the AAT feature (#1,#2).

```

362 \prg_new_conditional:Nnn \fontspec_if_aat_feature:nn {TF,T,F} {
363   \ifcsname zf@family@fontdef\f@family\endcsname
364     \font\zf@basefont="\use:c{zf@family@fontdef\f@family}"^at~\f@size pt
365     \ifzf@atsui
366       \fontspec_make_AAT_feature_string:nn{#1}{#2}
367       \ifx\@tempa\@empty
368         \prg_return_false:
369       \else
370         \prg_return_true:
371       \fi
372     \else
373       \prg_return_false:
374     \fi
375   \else
376     \prg_return_false:
377   \fi
378 }

```

\fontspec\_if\_opentype:TF Returns whether the currently selected font is an OpenType font. Always true for LuaTeX fonts.

```

379 \prg_new_conditional:Nnn \fontspec_if_opentype: {TF,T,F} {
380   \ifcsname zf@family@fontdef\f@family\endcsname
381     \font\zf@basefont="\csname zf@family@fontdef\f@family\endcsname"^at~\f@size pt
382     \fontspec_set_font_type:
383     \ifzf@icu

```

```

384     \prg_return_true:
385     \else
386         \prg_return_false:
387     \fi
388 \else
389     \prg_return_false:
390 \fi
391 }

```

\fontspec\_if\_feature:nTF Returns whether the currently selected font contains the raw OpenType feature #1. E.g.: \fontspec\_if\_feature:nTF {pnum} {True} {False} Returns false if the font is not loaded by fontspec or is not an OpenType font.

```

392 \prg_new_conditional:Nnn \fontspec_if_feature:n {TF,T,F} {
393     \ifcsname zf@family@fontdef\f@family\endcsname
394         \font\zf@basefont="\csname zf@family@fontdef\f@family\endcsname"~at`f@size pt
395         \fontspec_set_font_type:
396         \ifzf@icu
397             \int_set:Nn \c@zf@script
398                 {\use:c {g_fonts_spec_script_num_(\zf@family)_tl}}
399             \int_set:Nn \c@zf@language
400                 {\use:c {g_fonts_spec_lang_num_(\zf@family)_tl}}
401             \tl_set:Nv \l_fonts_spec_script_tl {\g_fonts_spec_script_(\zf@family)_tl}
402             \tl_set:Nv \l_fonts_spec_lang_tl {\g_fonts_spec_lang_(\zf@family)_tl}
403             \fontspec_check_ot_feat:nTF {#1} \prg_return_true: \prg_return_false:
404         \else
405             \prg_return_false:
406         \fi
407     \else
408         \prg_return_false:
409     \fi
410 }

```

\fontspec\_if\_feature:nnnTF Returns whether the currently selected font with raw OpenType script tag #1 and raw OpenType language tag #2 contains the raw OpenType feature tag #3. E.g.: \fontspec\_if\_feature:nTF {latn} {ROM} {pnum} {True} {False} Returns false if the font is not loaded by fontspec or is not an OpenType font.

```

411 \prg_new_conditional:Nnn \fontspec_if_feature:nnn {TF,T,F} {
412     \ifcsname zf@family@fontdef\f@family\endcsname
413         \font\zf@basefont="\csname zf@family@fontdef\f@family\endcsname"~at`f@size pt
414         \fontspec_set_font_type:
415         \ifzf@icu
416             \fontspec_iv_str_to_num:n{#1} \c@zf@script = \l_fonts_spec_strnum_int \relax
417             \fontspec_iv_str_to_num:n{#2} \c@zf@language = \l_fonts_spec_strnum_int \relax
418             \fontspec_check_ot_feat:nTF {#3} \prg_return_true: \prg_return_false:
419         \else
420             \prg_return_false:
421         \fi
422     \else
423         \prg_return_false:
424     \fi
425 }

```

\fontspec\_if\_script:nTF Returns whether the currently selected font contains the raw OpenType script #1.  
 E.g.: \fontspec\_if\_script:nTF {latn} {True} {False} Returns false if the font is not loaded by fontspec or is not an OpenType font.

```

426 \prg_new_conditional:Nnn \fontspec_if_script:n {TF,T,F} {
427   \ifcsname zf@family@fontdef\f@family\endcsname
428     \font\zf@basefont="\csname zf@family@fontdef\f@family\endcsname"~at~\f@size pt
429     \fontspec_set_font_type:
430     \ifzf@icu
431       \fontspec_check_script:nTF {#1} \prg_return_true: \prg_return_false:
432     \else
433       \prg_return_false:
434     \fi
435   \else
436     \prg_return_false:
437   \fi
438 }
```

\fontspec\_if\_language:nTF Returns whether the currently selected font contains the raw OpenType feature #1. E.g.: \fontspec\_if\_feature:nTF {+pnum} {True} {False} Returns false if the font is not loaded by fontspec or is not an OpenType font.

```

439 \prg_new_conditional:Nnn \fontspec_if_language:n {TF,T,F} {
440   \ifcsname zf@family@fontdef\f@family\endcsname
441     \font\zf@basefont="\csname zf@family@fontdef\f@family\endcsname"~at~\f@size pt
442     \fontspec_set_font_type:
443     \ifzf@icu
444       \tl_set:Nv \l_fonts此_script_tl {g_fonts此_script_(\zf@family)_tl}
445       \int_set:Nn \c@zf@script
446         {\use:c {g_fonts此_script_num_(\zf@family)_tl}}
447       \fontspec_check_lang:nTF {#1} \prg_return_true: \prg_return_false:
448     \else
449       \prg_return_false:
450     \fi
451   \else
452     \prg_return_false:
453   \fi
454 }
```

\fontspec\_if\_language:nnTF Returns whether the currently selected font contains the raw OpenType feature #2 in script #1. E.g.: \fontspec\_if\_feature:nTF {+pnum} {True} {False} Returns false if the font is not loaded by fontspec or is not an OpenType font.

```

455 \prg_new_conditional:Nnn \fontspec_if_language:nn {TF,T,F} {
456   \ifcsname zf@family@fontdef\f@family\endcsname
457     \font\zf@basefont="\csname zf@family@fontdef\f@family\endcsname"~at~\f@size pt
458     \fontspec_set_font_type:
459     \ifzf@icu
460       \tl_set:Nn \l_fonts此_script_tl {#1}
461       \fontspec_iv_str_to_num:n{#1} \c@zf@script = \l_fonts此_strnum_int \relax
462       \fontspec_check_lang:nTF {#2} \prg_return_true: \prg_return_false:
463     \else
464       \prg_return_false:
465     \fi
```

```

466 \else
467   \prg_return_false:
468 \fi
469 }

\fontspec_if_current_script:nTF Returns whether the currently loaded font is using the specified raw OpenType
script tag #1.

470 \prg_new_conditional:Nnn \fontspec_if_current_script:n {TF,T,F} {
471   \ifcsname zf@family@fontdef\f@family\endcsname
472     \font\zf@basefont=\csname zf@family@fontdef\f@family\endcsname"~at`\f@size pt
473     \fontspec_set_font_type:
474     \ifzf@icu
475       \tl_if_eq:nnTF {\#1} {g_fonts此_script_({zf@family})_tl}
476       {\prg_return_true:} {\prg_return_false:}
477     \else
478       \prg_return_false:
479     \fi
480   \else
481     \prg_return_false:
482   \fi
483 }

\fontspec_if_current_language:nTF Returns whether the currently loaded font is using the specified raw OpenType
language tag #1.

484 \prg_new_conditional:Nnn \fontspec_if_current_language:n {TF,T,F} {
485   \ifcsname zf@family@fontdef\f@family\endcsname
486     \font\zf@basefont=\csname zf@family@fontdef\f@family\endcsname"~at`\f@size pt
487     \fontspec_set_font_type:
488     \ifzf@icu
489       \tl_if_eq:nnTF {\#1} {g_fonts此_lang_({zf@family})_tl}
490       {\prg_return_true:} {\prg_return_false:}
491     \else
492       \prg_return_false:
493     \fi
494   \else
495     \prg_return_false:
496   \fi
497 }

```

Need this:

```
498 \cs_generate_variant:Nn \tl_if_eq:nnTF {nv}
```

## 22.8 Internal macros

The macros from here in are used internally by all those defined above. They are not designed to remain consistent between versions.

\fontspec\_select:nn This is the command that defines font families for use, the underlying procedure of all \fontspec-like commands. Given a list of font features (#1) for a requested font (#2, stored in \zf@fontname globally for the \zf@make@aat@feature@string

macro), it will define an NFSS family for that font and put the family name into `\zf@family`.

This macro does its processing inside a group, but it's a bit worthless coz there's all sorts of `\global` action going on. Pity. Anyway, lots of things are branched out for the pure reason of splitting the code up into logical chunks. Some of it is never even re-used, so it all might be a bit obfuscating. (E.g., `\fontspec_init:` and `\fontspec_set_font_type:..`)

First off, initialise some bits and pieces and run the preparse feature processing. This catches font features such as Renderer that can change the way subsequent features are processed. All font features that 'slip through' this stage are saved in the `\zf@font@feat` macro for future processing.

```
499 \cs_set:Npn \fontspec_select:nn #1#2 {
500   \begingroup
501   \fontspec_init:
```

`\zf@fontname` is used as the generic name of the font being defined. `\zf@family@long` is the unique identifier of the font with all its features. `\zf@up` is the font specifically to be used as the upright font.

```
502   \edef\zf@fontname{\#2}
503   \let\zf@family@long\zf@fontname
504   \let\zf@up\zf@fontname
```

Detect if external fonts are to be used, possibly automatically, and parse fontspec features for bold/italic fonts and their features.

```
505 \fontspec_if_detect_external:nT {\#2}
506   { \setkeys[\zf]{preparse-external}{ExternalLocation} }
507 \fontspec_setkeys:xx {preparse-external} {\zf@default@options #1}
```

When `\zf@fontname` is augmented with a prefix or whatever to create the name of the upright font (`\zf@up`), this latter is the new 'general font name' to use.

```
508 \let\zf@fontname\zf@up
509 \fontspec_setkeys:xx {preparse} {\XKV@rm}
510 \let\zf@font@feat\XKV@rm
511 \global\font\zf@basefont="\fontspec_fullname:n {\zf@up}"^at^~\f@size pt
512 \fontspec_set_font_type:
513 \global\font\zf@basefont="\fontspec_fullname:n {\zf@up}"^at^~\f@size pt
```

Now convert the remaining requested features to font definition strings. This is performed with `\zf@get@feature@requests`, in which `\setkeys` retrieves the requested font features and processes them. To build up the complex family name, it concatenates each font feature with the family name of the font. So since `\setkeys` is run more than once (since different font faces may have different feature names), we only want the complex family name to be built up once, hence the `\zf@firsttime` conditionals.

```
514 \zf@firsttimetrue
515   \ifzf@icu
516     \fontspec_setkeys:xxx {feat} {Script} {\l_fontspec_script_name_t1}
517     \fontspec_setkeys:xxx {feat} {Lang} {\l_fontspec_lang_name_t1}
518   \fi
519   \fontspec_get_features:n{\zf@font@feat}
520 \zf@firsttimefalse
```

Now we have a unique (in fact, too unique!) string that contains the family name and every option in abbreviated form. This is used with a counter to create a simple NFSS family name for the font we're selecting.

The font name is fully expanded, in case it's defined in terms of macros, before having its spaces zapped.

```

521 \unless\ifcsname zf@UID@\zf@family@long\endcsname
522   \ifcsname c@zf@famc@#2\endcsname
523     \expandafter\global\expandafter\advance
524       \csname c@zf@famc@#2\endcsname\@ne
525   \else
526     \expandafter\global\expandafter\newcount
527       \csname c@zf@famc@#2\endcsname
528   \fi
529   \edef\@tempa{\#2~}
530   \cs_gset:cpx{zf@UID@\zf@family@long}{
531     \expandafter\zap@space\@tempa\@empty
532     (\expandafter\the\csname c@zf@famc@#2\endcsname)
533   }
534 \fi
535 \xdef\zf@family{\@nameuse{zf@UID@\zf@family@long}}

```

Now that we have the family name, we can check to see if the family has already been defined, and if not, do so. Once the family name is created, use it to create global macros to save the user string of the requested options and font name, primarily for use with \addfontfeatures.

```

536 \unless\ifcsname zf@family@fontname\zf@family\endcsname
537   \fontspec_info:nxx {defining-font} {#1} {#2}
538   \tl_gset:cx {zf@family@fontname\zf@family} {#2}
539   \tl_gset:cx {zf@family@options\zf@family} {\zf@default@options #1}
540   \tl_gset:cx {zf@family@fontdef\zf@family} {
541     \fontspec_fullname:n {\zf@fontname} : \l_fontspec_pre_feat_tl \l_fontspec_rawfeatures_sclist
542   }
543   \tl_gset:cx {g_fontspec_script_num_(\zf@family)_tl}
544   { \int_use:N \c@zf@script }
545   \tl_gset:cx {g_fontspec_lang_num_(\zf@family)_tl}
546   { \int_use:N \c@zf@language }
547   \tl_gset_eq:cN {g_fontspec_script_(\zf@family)_tl} \l_fontspec_script_tl
548   \tl_gset_eq:cN {g_fontspec_lang_(\zf@family)_tl} \l_fontspec_lang_tl

```

Next the font family and its shapes are defined in the NFSS.

All NFSS specifications take their default values, so if any of them are redefined, the shapes will be selected to fit in with the current state. For example, if \bfdefault is redefined to b, all bold shapes defined by this package will also be assigned to b.

The macros \zf@bf, et al., are used to store the name of the custom bold, et al., font, if requested as user options. If they are empty, the default fonts are used.

First we define the font family and define the normal shape: (any shape-specific features are appended to the generic font features requested in the last argument of \zf@make@font@shapes.)

```

549   \DeclareFontFamily{\zf@enc}{\zf@family}{}
550   \zf@make@font@shapes{\zf@fontname}

```

```
551      {\mddefault}{\updefault}{\zf@font@feat\zf@up@feat}
```

And the different shapes are set accordingly.

```
552      \fontspec_set_bold:
553      \fontspec_set_italic:
554      \fontspec_set_slanted:
555      \fontspec_set_bold_italic:
556      \fontspec_set_bold_slanted:
557      \fi
558      \endgroup
559 }
```

\fontspec\_if\_detect\_external:nT Check if either the fontname ends with a known font extension.

```
560 \prg_new_conditional:Nnn \fontspec_if_detect_external:n {T}
561 {
562   \clist_map_inline:Nn \l_fontspec_extensions_clist
563   {
564     \bool_set_false:N \l_tmpa_bool
565     \tl_if_in:nnT {#1 = end_of_string} {##1 = end_of_string}
566     { \bool_set_true:N \l_tmpa_bool \clist_map_break: }
567   }
568   \bool_if:NTF \l_tmpa_bool \prg_return_true: \prg_return_false:
569 }
```

\fontspec\_fullname:n Constructs the complete font name based on a common piece of info.

```
570 \cs_set:Npn \fontspec_fullname:n #1 {
571   \fontspec_namewrap:n { #1 \l_fontspec_extension_tl }
572   \l_fontspec_renderer_tl
573   \l_fontspec_optical_size_tl
574 }
```

\fontspec\_set\_bold: Again, the extra bold options defined with BoldFeatures are appended to the generic font features. Then, the bold font is defined either as the ATS default (\zf@make@font@shapes' optional argument is to check if there actually is one; if not, the bold NFSS series is left undefined) or with the font specified with the BoldFont feature.

```
575 \cs_new:Npn \fontspec_set_bold: {
576   \unless\ifzf@nobf
577     \ifx\zf@bf\empty
578       \zf@make@font@shapes[\zf@fontname]{/B}
579       {\bfdefault}{\updefault}{\zf@font@feat\zf@bf@feat}
580     \else
581       \zf@make@font@shapes{\zf@bf}
582       {\bfdefault}{\updefault}{\zf@font@feat\zf@bf@feat}
583     \fi
584   \fi
585 }
```

\fontspec\_set\_italic: And italic in the same way:

```
586 \cs_new:Npn \fontspec_set_italic: {
587   \unless\ifzf@noit
```

```

588     \ifx\zf@it\@empty
589         \zf@make@font@shapes[\zf@fontname]{/I}
590             {\mddefault}{\itdefault}{\zf@font@feat\zf@it@feat}
591     \else
592         \zf@make@font@shapes{\zf@it}
593             {\mddefault}{\itdefault}{\zf@font@feat\zf@it@feat}
594     \fi
595 \fi
596 }

```

\fontspec\_set\_slanted: And slanted but only if requested:

```

597 \cs_new:Npn \fontspec_set_slanted: {
598     \ifx\zf@sl\@empty\else
599         \zf@make@font@shapes{\zf@sl}
600             {\mddefault}{\sldefault}{\zf@font@feat\zf@sl@feat}
601     \fi
602 }

```

\fontspec\_set\_bold\_italic: If requested, the custom fonts take precedence when choosing the bold italic font. When both italic and bold fonts are requested and the bold italic font hasn't been explicitly specified (a rare occurrence, presumably), the new bold font is used to define the new bold italic font.

```

603 \cs_new:Npn \fontspec_set_bold_italic: {
604     \tempswatru
605     \ifzf@nobf\@tempswafalse\fi
606     \ifzf@noit\@tempswafalse\fi
607     \if@tempswa
608         \ifx\zf@bfit\@empty
609             \ifx\zf@bf\@empty
610                 \ifx\zf@it\@empty
611                     \zf@make@font@shapes[\zf@fontname]{/BI}
612                         {\bfdefault}{\itdefault}{\zf@font@feat\zf@bfit@feat}
613                 \else
614                     \zf@make@font@shapes[\zf@it]{/B}
615                         {\bfdefault}{\itdefault}{\zf@font@feat\zf@bfit@feat}
616                 \fi
617             \else
618                 \zf@make@font@shapes[\zf@bf]{/I}
619                     {\bfdefault}{\itdefault}{\zf@font@feat\zf@bfit@feat}
620             \fi
621         \else
622             \zf@make@font@shapes{\zf@bfit}
623                 {\bfdefault}{\itdefault}{\zf@font@feat\zf@bfit@feat}
624         \fi
625     \fi
626 }

```

\fontspec\_set\_bold\_slanted: And bold slanted, again, only if requested:

```

627 \cs_new:Npn \fontspec_set_bold_slanted: {
628     \ifx\zf@bfsl\@empty
629         \ifx\zf@sl\@empty\else

```

```

630     \zf@make@font@shapes[\zf@s1]{/B}
631     {\bfdefault}{\sldefault}{\zf@font@feat\zf@bfsl@feat}
632     \fi
633 \else
634     \zf@make@font@shapes{\zf@bfsl}
635     {\bfdefault}{\sldefault}{\zf@font@feat\zf@bfsl@feat}
636     \fi
637 }

```

### 22.8.1 Fonts

\fontspec\_set\_font\_type: Now check if the font is to be rendered with ATSUI or ICU. This will either be automatic (based on the font type), or specified by the user via a font feature.

This macro sets \zf@atsui or \zf@icu or \zf@mm booleans accordingly depending if the font in \zf@basefont is an AAT font or an OpenType font or a font with feature axes (either AAT or Multiple Master), respectively.

```

638 \xetex_or_luatex:n { \cs_new:Npn \fontspec_set_font_type: }
639   {
640     \zf@tfmfalse \zf@atsuifalse \zf@icufalse \zf@mmfalse \zf@graphitefalse
641     \ifcase\XeTeXfonttype\zf@basefont
642       \zf@tfmtrue
643     \or
644       \zf@atsuitrue
645       \ifnum\XeTeXcountvariations\zf@basefont \c_zero
646         \zf@mmtrue
647       \fi
648     \or
649       \zf@icutrue
650     \fi

```

If automatic, the \l\_fonts\_spec\_renderer\_t1 token list will still be empty (other suffices that could be added will be later in the feature processing), and if it is indeed still empty, assign it a value so that the other weights of the font are specifically loaded with the same renderer.

```

651   \tl_if_empty:NT \l_fonts_spec_renderer_t1 {
652     \ifzf@atsui
653       \tl_set:Nn \l_fonts_spec_renderer_t1{/AAT}
654     \else\ifzf@icu
655       \tl_set:Nn \l_fonts_spec_renderer_t1{/ICU}
656     \fi\fi
657   }
658 }
659 {
660   \zf@icutrue
661 }

```

\zf@make@font@shapes [#1]: Font name prefix  
#2 : Font name  
#3 : Font series  
#4 : Font shape  
#5 : Font features

This macro eventually uses `\DeclareFontShape` to define the font shape in question.

The optional first argument is used when making the font shapes for bold, italic, and bold italic fonts using X<sub>E</sub>T<sub>E</sub>X's auto-recognition with #2 as `/B`, `/I`, and `/BI` font name suffixes. If no such font is found, it falls back to the original font name, in which case this macro doesn't proceed and the font shape is not created for the NFSS.

```

662 \newcommand*\zf@make@font@shapes[5][]{
663   \begingroup
664     \edef\@tempa{#1}
665     \unless\ifx\@tempa\empty
666       \font\@tempfonta="\fontspec_fullname:n {#1}"`at`\f@size pt
667       \edef\@tempa{\fontname\@tempfonta}
668     \fi
669     \font\@tempfontb="\fontspec_fullname:n {#1#2}"`at`\f@size pt
670     \edef\@tempb{\fontname\@tempfontb}
671     \ifx\@tempa\@tempb
672       \fontspec_info:nx {no-font-shape} {#1#2}
673     \else
674       \edef\zf@fontname{#1#2}
675       \let\zf@basefont\@tempfontb
676       \zf@DeclareFontShape{#3}{#4}{#5}

```

Next, the small caps are defined. `\zf@make@smallcaps` is used to define the appropriate string for activating small caps in the font, if they exist. If we are defining small caps for the upright shape, then the small caps shape default is used. For an *italic* font, however, the shape parameter is overloaded and we must call italic small caps by their own identifier. See [Section 22.10 on page 86](#) for the code that enables this usage.

```

677     \ifx\zf@sc\empty
678       \unless\ifzf@nosc
679         \zf@make@smallcaps
680       \unless\ifx\zf@smallcaps\empty
681         \zf@DeclareFontShape[\zf@smallcaps]{#3}
682           {\ifx#4\itdefault\sidefault\else\scdefault\fi}{#5\zf@sc@feat}
683       \fi
684     \fi
685   \else
686     \edef\zf@fontname{\zf@sc}
687     \zf@DeclareFontShape{#3}
688       {\ifx#4\itdefault\sidefault\else\scdefault\fi}{#5\zf@sc@feat}
689     \fi
690   \fi
691 \endgroup
692 }

```

Note that the test for italics to choose the `\sidefault` shape only works while `\fontspec_select:nn` passes single tokens to this macro...

`\zf@DeclareFontShape` [#1]: Raw appended font feature  
#2 : Font series

```

#3 : Font shape
#4 : Font features
    Wrapper for \DeclareFontShape.

693 \newcommand\zf@DeclareFontShape[4][]{%
694   \clist_if_empty:NNTF \l_fonts表白_sizefeat_clist
695   {
696     \fonts表白_get_features:n{#4}
697     \tl_set:Nx \l_fonts表白_nfss_tl {
698       - \l_fonts表白_scale_tl "
699       \fonts表白_fullname:n {\zf@fontname} :
700         \l_fonts表白_pre_feat_tl \l_fonts表白_rawfeatures_sclist #1 "
701     }
702   }

```

Default code, above, sets things up for no optical size fonts or features. On the other hand, loop through `SizeFeatures` arguments, which are of the form

`SizeFeatures={{one},{two},{three}}.`

```

703   {
704     \tl_clear:N \l_fonts表白_nfss_tl
705     \clist_map_inline:Nn \l_fonts表白_sizefeat_clist {
706       \tl_clear:N \l_fonts表白_size_tl
707       \tl_set_eq:NN \l_fonts表白_sizedfont_tl \zf@fontname
708       \fonts表白_setkeys:xx {sizing} { \expandafter \@firstofone ##1 }
709       \tl_if_empty:NT \l_fonts表白_size_tl { \fonts表白_error:n {no-size-info} }
710       \fonts表白_get_features:n{#4,\XKV@rm}
711       \tl_put_right:Nx \l_fonts表白_nfss_tl {
712         \l_fonts表白_size_tl \l_fonts表白_scale_tl
713         " \fonts表白_fullname:n { \l_fonts表白_sizedfont_tl }
714         : \l_fonts表白_pre_feat_tl \l_fonts表白_rawfeatures_sclist #1 "
715     }
716   }
717 }

```

And finally the actual font shape declaration using `\l_fonts表白_nfss_tl` defined above. `\zf@adjust` is defined in various places to deal with things like the hyphenation character and interword spacing.

```

718 \use:x{
719   \exp_not:N\DeclareFontShape{\zf@enc}{\zf@family}{#2}{#3}
720   {\l_fonts表白_nfss_tl}{\zf@adjust}
721 }

```

This extra stuff for the slanted shape substitution is a little bit awkward, but I'd rather have it here than break out yet another macro. Alternatively, one day I might just redefine `\slshape`. Why not, eh?

```

722 \tl_if_eq:xxT {#3} {\itdefault}
723 {
724   \use:x {
725     \exp_not:N \DeclareFontShape {\zf@enc}{\zf@family}{#2}{\sldefault}
726     {-sub*\zf@family/#2/\itdefault}{\zf@adjust}
727   }
728 }
729 }

```

\l\_fonts\_spec\_pre\_feat\_tl These are the features always applied to a font selection before other features.

```

730 \xetex_or_luatex:n { \tl_set:Nn \l_fonts_spec_pre_feat_tl }
731 {
732   \ifzf@icu
733     script = \l_fonts_spec_script_tl ;
734     language = \l_fonts_spec_lang_tl ;
735   \fi
736 }
737 {
738   mode = \l_fonts_spec_mode_tl ;
739   script = \l_fonts_spec_script_tl ;
740   language = \l_fonts_spec_lang_tl ;
741 }
```

\zf@update@family This macro is used to build up a complex family name based on its features.  
\zf@firsttime is set true in \fonts\_spec\_select:nn only the first time \f@get@feature@requests is called, so that the family name is only created once.

```

742 \newcommand*{\zf@update@family}[1]{
743   \ifzf@firsttime
744     \xdef\zf@family@long{\zf@family@long#1}
745   \fi
746 }
```

### 22.8.2 Features

\fonts\_spec\_get\_features:n This macro is a wrapper for \setkeys which expands and adds a default specification to the original passed options. It begins by initialising the commands used to hold font-feature specific strings.

```

747 \cs_set:Npn \fonts_spec_get_features:n #1 {
748   \let\l_fonts_spec_rawfeatures_sclist \empty
749   \tl_clear:N \l_fonts_spec_scale_tl
750   \let\zf@adjust \empty
751   \fonts_spec_setkeys:xx {options} {#1}
752   \tl_if_empty:NF \XKV@rm {
753     \fonts_spec_error:nx {unknown-options} { \exp_not:V \XKV@rm }
754   }
755   \PackageInfo{fontspec}{Raw~ font~ features~ "\l_fonts_spec_rawfeatures_sclist"}
756 }
```

\fonts\_spec\_init: Initialisations that either need to occur globally: (all setting of these variables is done locally inside a group)

```

757 \tl_clear:N \zf@bf
758 \tl_clear:N \zf@it
759 \tl_clear:N \zf@bfit
760 \tl_clear:N \zf@sl
761 \tl_clear:N \zf@bfsl
762 \tl_clear:N \zf@sc
763 \tl_clear:N \zf@up@feat
764 \tl_clear:N \zf@bf@feat
765 \tl_clear:N \zf@it@feat
```

```

766 \tl_clear:N \zf@bfit@feat
767 \tl_clear:N \zf@sl@feat
768 \tl_clear:N \zf@bfsl@feat
769 \tl_clear:N \zf@sc@feat
770 \clist_clear:N \l_fonts表白feat_clist

```

Or once per fonts表白 font invocation: (Some of these may be redundant. Check whether they're assigned to globally or not.)

```

771 \newcommand*\fonts表白_init:{%
772   \zf@icufalse
773   \cs_set_eq:NN \fonts表白_namewrap:n \use:n
774   \tl_clear:N \l_fonts表白_optical_size_tl
775   \tl_clear:N \l_fonts表白_renderer_tl
776   \tl_set:Nn \l_fonts表白_script_name_tl {Latin}
777   \tl_set:Nn \l_fonts表白_script_tl      {latn}
778   \tl_set:Nn \l_fonts表白_lang_name_tl {Default}
779   \tl_set:Nn \l_fonts表白_lang_tl      {DFLT}
780   \luatex_if_engine:T {
781     \tl_set:Nn \l_fonts表白_mode_tl {node}
782     \luatexprehyphenchar = '\- % fixme
783     \luatexposthyphenchar = 0 % fixme
784     \luatexpreexhyphenchar = 0 % fixme
785     \luatexpostexhyphenchar= 0 % fixme
786   }
787 }

```

\zf@make@smallcaps This macro checks if the font contains small caps, and if so creates the string for accessing them in \zf@smallcaps.

```

788 \newcommand*\zf@make@smallcaps{%
789   \let\zf@smallcaps@\empty
790   \xetex_or_luatex:nn
791   {
792     \ifzf@atsui
793       \fonts表白_make_AAT_feature_string:nn{3}{3}
794       \unless\ifx\@tempa\empty
795         \edef\zf@smallcaps{\@tempa;}
796       \fi
797     \fi
798     \ifzf@icu
799       \fonts表白_check_ot_feat:nT {+smcp} {\edef\zf@smallcaps{+smcp;}}
800     \fi
801   }
802   {
803     \fonts表白_check_ot_feat:nT {+smcp} {\edef\zf@smallcaps{+smcp;}}
804   }
805 }

```

\sclist\_put\_right:Nn I'm hardly going to write an 'sclist' module but a couple of functions are necessary.

```

806 \cs_new:Npn \sclist_put_right:Nn #1#2 {
807   \tl_if_empty:NT #1 {
808
809 }

```

```

810 }

\zf@update@ff \l_fontsfeature_sclist is the string used to define the list of specific
font features. Each time another font feature is requested, this macro is used to
add that feature to the list. Font features are separated by semicolons.
811 \newcommand*\zf@update@ff[1]{
812   \unless\ifzf@firsttime
813     \xdef\l_fontsfeature_sclist{\l_fontsfeature_sclist #1;}
814   \fi
815 }

\fntspec_make_feature:n This macro is called by each feature key selected, and runs according to which
type of font is selected.
816 \cs_new:Npn \fntspec_make_feature:n #1#2#3 {
817   \xetex_or_luatex:n
818   {
819     \ifzf@atsui
820       \fntspec_make_AAT_feature:nn {#1}{#2}
821     \fi
822     \ifzf@icu
823       \fntspec_make_ICU_feature:n {#3}
824     \fi
825   }
826   {
827     \fntspec_make_ICU_feature:n {#3}
828   }
829 }

830 \cs_new:Npn \fntspec_make_AAT_feature:nn #1#2 {
831   \tl_if_empty:nTF {#1}
832   {
833     \fntspec_warning:n {aat-feature-not-exist}
834   }
835   {
836     \fntspec_make_AAT_feature_string:nn {#1}{#2}
837     \ifx@\tempa@\empty
838       \fntspec_warning:nx {aat-feature-not-exist-in-font} {#1,#2}
839     \else
840       \zf@update@family{+#1,#2}
841       \zf@update@ff@\tempa
842     \fi
843   }
844 }

845 \cs_new:Npn \fntspec_make_ICU_feature:n #1 {
846   \tl_if_empty:nTF {#1}
847   {
848     \fntspec_warning:n {icu-feature-not-exist}
849   }
850   {
851     \fntspec_check_ot_feat:nTF {#1} {
852       \zf@update@family{#1}
853       \zf@update@ff{#1}

```

```

854     }{
855         \fontspec_warning:nx {icu-feature-not-exist-in-font} {#1}
856     }
857 }
858 }

\zf@define@font@feature These macros are used in order to simplify font feature definition later on.
\zf@define@feature@option
859 \newcommand*\zf@define@font@feature[1]{
860     \define@key[zf]{options}{#1}{{\setkeys[zf@feat]{#1}{##1}}}
861 }
862 \newcommand*\zf@define@feature@option[5]{
863     \define@key[zf@feat]{#1}{#2}[]{\fontspec_make_feature:nnn{#3}{#4}{#5}}
864 }

\keyval@alias@key This macro maps one xkeyval key to another.
865 \newcommand*\keyval@alias@key[4][KV]{
866     \cs_set_eq:cc{#1@#2@#4}{#1@#2@#3}
867     \cs_set_eq:cc{#1@#2@#4@default}{#1@#2@#3@default}
868 }

\multi@alias@key This macro iterates through families to map one key to another, regardless of which family it's contained within.
869 \newcommand*\multi@alias@key[2]{
870     \key@ifundefined[zf]{options}{#1}
871     {
872         \key@ifundefined[zf]{preparse}{#1}
873         {
874             \key@ifundefined[zf]{preparse-external}{#1}
875             { \fontspec_warning:nx {rename-feature-not-exist} {#1} }
876             { \keyval@alias@key[zf]{preparse-external}{#1}{#2} }
877         }
878         { \keyval@alias@key[zf]{preparse}{#1}{#2} }
879     }
880     { \keyval@alias@key[zf]{options}{#1}{#2} }
881 }

\fontspec_make_AAT_feature_string:nn This macro takes the numerical codes for a font feature and creates a specified macro containing the string required in the font definition to turn that feature on or off. Used primarily in \zf@make@aat@feature, but also used to check if small caps exists in the requested font (see page 63).
882 \cs_new:Npn \fontspec_make_AAT_feature_string:nn #1#2 {
883     \edef@\tempa{\XeTeXfeaturename\zf@basefont #1}
884     \unless\ifx@\tempa@\empty

For exclusive selectors, it's easy; just grab the string:
885     \ifnum\XeTeXisexclusivefeature\zf@basefont #10
886         \edef@\tempb{\XeTeXselectorname\zf@basefont #1\space #2}

For non-exclusive selectors, it's a little more complex. If the selector is even, it corresponds to switching the feature on:
887     \else

```

```

888     \unless\ifodd #2
889         \edef\@tempb{\XeTeXselectorname\zf@basefont #1\space #2}

```

If the selector is *odd*, it corresponds to switching the feature off. But X<sub>E</sub>T<sub>E</sub>X doesn't return a selector string for this number, since the feature is defined for the 'switching on' value. So we need to check the selector of the previous number, and then prefix the feature string with ! to denote the switch.

```

890     \else
891         \edef\@tempb{
892             \XeTeXselectorname\zf@basefont #1\space \numexpr#2-1\relax
893         }
894         \unless\ifx\@tempb\empty
895             \edef\@tempb{!\@tempb}
896         \fi
897     \fi
898 \fi

```

Finally, save out the complete feature string in \@tempa. If the selector doesn't exist, re-initialise the feature string to empty.

```

899     \unless\ifx\@tempb\empty
900         \edef\@tempa{\@tempa\@tempb}
901     \else
902         \let\@tempa\empty
903     \fi
904 \fi
905 }

```

\fontspec\_iv\_str\_to\_num:n This macro takes a four character string and converts it to the numerical representation required for X<sub>E</sub>T<sub>E</sub>X OpenType script/language/feature purposes. The output is stored in \l\_fontspec\_strnum\_int.

The reason it's ugly is because the input can be of the form of any of these: 'abcd', 'abc', 'abc ', 'ab ', 'ab', etc. (It is assumed the first two chars are *always* not spaces.) So this macro reads in the string, delimited by a space; this input is padded with \@emptys and anything beyond four chars is snipped. The \@emptys then are used to reconstruct the spaces in the string to number calculation.

The variant \fontspec\_v\_str\_to\_num:n is used when looking at features, which are passed around with prepended plus and minus signs (e.g., +liga, -dlig); it simply strips off the first char of the input before calling the normal \fontspec\_iv\_str\_to\_num:n.

It's probable that all OpenType features *are* in fact four characters long, but not impossible that they aren't. So I'll leave the less efficient parsing stage in there even though it's not strictly necessary for now.

```

906 \cs_set:Npn \fontspec_iv_str_to_num:n #1 {
907   \fontspec_iv_str_to_num:w #1 \@empty \@empty \q_nil
908 }
909 \cs_set:Npn \fontspec_iv_str_to_num:w #1#2#3#4#5 \q_nil {
910   \int_set:Nn \l_fontspec_strnum_int {
911     '#1 * "1000000
912     + '#2 * "10000
913     + \ifx \@empty #3 32 \else '#3 \fi * "100
914     + \ifx \@empty #4 32 \else '#4 \fi

```

```

915  }
916 }
917 \cs_set:Npn \fontspec_v_str_to_num:n #1 {
918   \bool_if:nTF
919   {
920     \tl_if_head_eq_charcode_p:nN {#1} {+} ||
921     \tl_if_head_eq_charcode_p:nN {#1} {-}
922   }
923   {
924     \exp_after:wN \fontspec_iv_str_to_num:n
925     \exp_after:wN { \use_none:n #1 }
926   }
927   { \fontspec_iv_str_to_num:n {#1} }
928 }
```

\fontspec\_check\_script:nTF This macro takes an OpenType script tag and checks if it exists in the current font. The output boolean is \tempswattrue. \l\_fontsnum\_int is used to store the number corresponding to the script tag string.

```

929 \xetex_or_luatex:nnn {\prg_new_conditional:Nnn \fontspec_check_script:n {TF}}
930 {
931   \fontspec_iv_str_to_num:n{#1}
932   \tempcntb\XeTeXOTcountscripts\zf@basefont
933   \c@zf@index\z@ \tempswafalse
934   \loop\ifnum\c@zf@index\tempcntb
935     \ifnum\XeTeXOTscripttag\zf@basefont\c@zf@index=\l_fontsnum_int
936       \tempswattrue
937       \c@zf@index\tempcntb
938     \else
939       \advance\c@zf@index\ne
940     \fi
941   \repeat
942   \if@tempswa \prg_return_true: \else: \prg_return_false: \fi:
943 }
944 {
945   \directlua{\fontspec.check_ot_script("zf@basefont", "#1")}
946   \if@tempswa \prg_return_true: \else: \prg_return_false: \fi:
947 }
```

\fontspec\_check\_lang:nTF This macro takes an OpenType language tag and checks if it exists in the current font/script. The output boolean is \tempswattrue. \l\_fontsnum\_int is used to store the number corresponding to the language tag string. The script used is whatever's held in \c@zf@script. By default, that's the number corresponding to 'latn'.

```

948 \xetex_or_luatex:nnn {\prg_new_conditional:Nnn \fontspec_check_lang:n {TF}}
949 {
950   \fontspec_iv_str_to_num:n{#1}
951   \tempcntb\XeTeXOTcountlanguages\zf@basefont\c@zf@script
952   \c@zf@index\z@
953   \tempswafalse
954   \loop\ifnum\c@zf@index\tempcntb
955     \ifnum\XeTeXOTlanguagegetag\zf@basefont\c@zf@script\c@zf@index=\l_fontsnum_int
```

```

956     \atempswatrue
957     \c@zf@index\atempcntb
958     \else
959     \advance\c@zf@index\@ne
960     \fi
961     \repeat
962     \if@tempswa \prg_return_true: \else: \prg_return_false: \fi:
963 }
964 {
965     \directlua{
966         fontspec.check_ot_lang( "zf@basefont", "#1", "\l_fonts_spec_script_t1" )
967     }
968     \if@tempswa \prg_return_true: \else: \prg_return_false: \fi:
969 }

```

\fontspec\_check\_ot\_feat:nTF This macro takes an OpenType feature tag and checks if it exists in the current font/script/language. The output boolean is \atempswa. \l\_fonts\_spec\_strnum\_int is used to store the number corresponding to the feature tag string. The script used is whatever's held in \c@zf@script. By default, that's the number corresponding to 'latn'. The language used is \c@zf@language, by default 0, the 'default language'.

```

970 \xetex_or_luatex:nnn
971 { \prg_new_conditional:Nnn \fontspec_check_ot_feat:n {TF,T} }
972 {
973     \atempcntb\XeTeXOTcountfeatures\zf@basefont\c@zf@script\c@zf@language
974     \fontspec_v_str_to_num:n {\#1}
975     \c@zf@index\z@
976     \atempswafalse
977     \loop\ifnum\c@zf@index\atempcntb
978         \ifnum\XeTeXOTfeaturetag\zf@basefont\c@zf@script\c@zf@language
979             \c@zf@index=\l_fonts_spec_strnum_int
980         \atempswatrue
981         \c@zf@index\atempcntb
982     \else
983         \advance\c@zf@index\@ne
984     \fi
985     \repeat
986     \if@tempswa \prg_return_true: \else: \prg_return_false: \fi:
987 }
988 {
989     \directlua{
990         fontspec.check_ot_feat(
991             "zf@basefont", "#1",
992             "\l_fonts_spec_lang_t1", "\l_fonts_spec_script_t1"
993         )
994     }
995     \if@tempswa \prg_return_true: \else: \prg_return_false: \fi:
996 }

```

## 22.9 keyval definitions

This is the tedious section where we correlate all possible (eventually) font feature requests with their X<sub>E</sub>T<sub>X</sub> representations.

### 22.9.1 Pre-parsing naming information

These features are extracted from the font feature list before all others, using xkeyval's \setkeys\*.

**ExternalLocation** For fonts that aren't installed in the system. If no argument is given, the font is located with kpsewhich; it's either in the current directory or the T<sub>E</sub>X tree. Otherwise, the argument given defines the file path of the font.

```
997 \bool_new:N \l_fonts杵_external_bool
998 \define@key[zf]{preparse-external}{ExternalLocation}[]{%
999   \zf@nobftrue
1000  \zf@noittrue
1001  \bool_set_true:N \l_fonts杵_external_bool
1002  \cs_gset:Npn \fonts杵_namewrap:n ##1 { [ #1 ##1 ] }
1003  \xetex_if_engine:T { \setkeys[zf]{preparse}{Renderer=ICU} }
1004 }
1005 \aliasfontfeature{ExternalLocation}{Path}
```

**Extension** For fonts that aren't installed in the system. Specifies the font extension to use.

```
1006 \define@key[zf]{preparse-external}{Extension}{%
1007   \tl_set:Nn \l_fonts杵_extension_tl {#1}
1008   \bool_if:NF \l_fonts杵_external_bool {
1009     \setkeys*[zf]{preparse-external}{ExternalLocation}
1010   }
1011 }
1012 \tl_clear:N \l_fonts杵_extension_tl
```

### 22.9.2 Pre-parsed features

After the font name(s) have been sorted out, now need to extract any renderer/font configuration features that need to be processed before all other font features.

**Renderer** This feature must be processed before all others (the other font shape and features options are also pre-parsed for convenience) because the renderer determines the format of the features and even whether certain features are available.

```
1013 \define@choicekey[zf]{preparse}{Renderer}[\l_tmpa_tl\l_tmpa_num]
1014   {AAT,ICU,Graphite,Full,Basic}{%
1015   \zf@update@family{+rend:#1}
1016   \intexpr_compare:nTF {\l_tmpa_num} 3 {
1017     \xetex_or_luatex:nn
1018   }
```

```

1019     \tl_set:Nv \l_fonts_spec_renderer_tl {g_fonts_spec_renderer_tag_\l_tmpa_tl}
1020 }
1021 {
1022     \fontspec_warning:nx {only-xetex-feature} {Renderer=AAT/ICU/Graphite}
1023 }
1024 }{
1025     \xetex_or_luatex:nn
1026     { \fontspec_warning:nx {only-luatex-feature} {Renderer=Full/Basic} }
1027     { \tl_set:Nv \l_fonts_spec_mode_tl {g_fonts_spec_mode_tag_\l_tmpa_tl} }
1028 }
1029 }
1030 \tl_set:cn {g_fonts_spec_renderer_tag_AAT} {/AAT}
1031 \tl_set:cn {g_fonts_spec_renderer_tag_ICU} {/ICU}
1032 \tl_set:cn {g_fonts_spec_renderer_tag_Graphite} {/GR}
1033 \tl_set:cn {g_fonts_spec_mode_tag_Full} {node}
1034 \tl_set:cn {g_fonts_spec_mode_tag_Basic} {base}

```

**OpenType script/language** See later for the resolutions from fontspec features to OpenType definitions.

```

1035 \define@key[zf]{preparse}{Script}{
1036     \xetex_if_engine:T { \setkeys[zf]{preparse}{Renderer=ICU} }
1037     \tl_set:Nn \l_fonts_spec_script_name_tl {\#1}
1038     \zf@update@family{+script:#1}
1039 }

```

Exactly the same:

```

1040 \define@key[zf]{preparse}{Language}{
1041     \xetex_if_engine:T { \setkeys[zf]{preparse}{Renderer=ICU} }
1042     \tl_set:Nn \l_fonts_spec_lang_name_tl {\#1}
1043     \zf@update@family{+language:#1}
1044 }

```

### 22.9.3 Bold/italic choosing options

The `Bold`, `Italic`, and `BoldItalic` features are for defining explicitly the bold and italic fonts used in a font family.

**Fonts Upright:**

```

1045 \define@key[zf]{preparse-external}{UprightFont}{
1046     \fontspec_complete_fontname:Nn \zf@up {\#1}
1047     \zf@update@family{up:#1}
1048 }

```

**Bold:**

```

1049 \define@key[zf]{preparse-external}{BoldFont}{
1050     \edef\@tempa{\#1}
1051     \ifx\@tempa\empty
1052         \zf@nobftrue
1053         \zf@update@family{nobf}
1054     \else
1055         \zf@nobffalse

```

```

1056     \fontspec_complete_fontname:Nn \zf@bf {#1}
1057     \zf@update@family{bf:#1}
1058 \fi
1059 }

```

Same for italic:

```

1060 \define@key[zf]{preparse-external}{ItalicFont}{
1061   \edef\@tempa{#1}
1062   \ifx\@tempa\empty
1063     \zf@noittrue
1064     \zf@update@family{noit}
1065   \else
1066     \zf@noitfalse
1067   \fontspec_complete_fontname:Nn \zf@it {#1}
1068   \zf@update@family{it:#1}
1069 \fi
1070 }

```

Simpler for bold+italic & slanted:

```

1071 \define@key[zf]{preparse-external}{BoldItalicFont}{
1072   \fontspec_complete_fontname:Nn \zf@bfit {#1}
1073   \zf@update@family{bfit:#1}
1074 }
1075 \define@key[zf]{preparse-external}{SlantedFont}{
1076   \fontspec_complete_fontname:Nn \zf@s1 {#1}
1077   \zf@update@family{s1:#1}
1078 }
1079 \define@key[zf]{preparse-external}{BoldSlantedFont}{
1080   \fontspec_complete_fontname:Nn \zf@bfs1 {#1}
1081   \zf@update@family{bfs1:#1}
1082 }

```

Small caps isn't pre-parsed because it can vary with others above:

```

1083 \define@key[zf]{options}{SmallCapsFont} {
1084   \edef\@tempa{#1}
1085   \ifx\@tempa\empty
1086     \zf@nosctrue
1087     \zf@update@family{nosc}
1088   \else
1089     \zf@noscfalse
1090     \fontspec_complete_fontname:Nn \zf@sc {#1}
1091     \zf@update@family{sc:\zap@space #1~\empty}
1092 \fi
1093 }

```

\fontspec\_complete\_fontname:Nn This macro defines #1 as the input with any \* tokens of its input replaced by the font name. This lets us define supplementary fonts in full ("Baskerville Semibold") or in abbreviation ("\* Semibold").

```

1094 \cs_set:Npn \fontspec_complete_fontname:Nn #1#2 {
1095   \tl_set:Nn #1 {#2}
1096   \tl_replace_all_in:Nnx #1 {*} {\zf@fontname}
1097 }
1098 \cs_generate_variant:Nn \tl_replace_all_in:Nnn {Nnx}

```

## Features

```
1099 \define@key[zf]{preparse}{UprightFeatures}{

1100   \def\zf@up@feat{, #1}

1101   \zf@update@family{rmfeat:#1}

1102 }

1103 \define@key[zf]{preparse}{BoldFeatures}{

1104   \def\zf@bf@feat{, #1}

1105   \zf@update@family{bffeat:#1}

1106 }

1107 \define@key[zf]{preparse}{ItalicFeatures}{

1108   \def\zf@it@feat{, #1}

1109   \zf@update@family{itfeat:#1}

1110 }

1111 \define@key[zf]{preparse}{BoldItalicFeatures}{

1112   \def\zf@bfit@feat{, #1}

1113   \zf@update@family{bfitfeat:#1}

1114 }

1115 \define@key[zf]{preparse}{SlantedFeatures}{

1116   \def\zf@sl@feat{, #1}

1117   \zf@update@family{slfeat:#1}

1118 }

1119 \define@key[zf]{preparse}{BoldSlantedFeatures}{

1120   \def\zf@bfsl@feat{, #1}

1121   \zf@update@family{bfslfeat:#1}

1122 }
```

Note that small caps features can vary by shape, so these in fact *aren't* pre-parsed.

```
1123 \define@key[zf]{options}{SmallCapsFeatures}{

1124   \unless\ifzf@firsttime\def\zf@sc@feat{, #1}\fi

1125   \zf@update@family{scfeat:\zap@space #1`@\empty}

1126 }
```

paragraphFeatures varying by size TODO: sizefeatures and italicfont (etc) don't play nice

```
1127 \define@key[zf]{preparse}{SizeFeatures}{

1128   \unless\ifzf@firsttime\def\l_fontsing_sizefeat_clist{#1}\fi

1129   \zf@update@family{sizefeat:\zap@space #1`@\empty}

1130 }

1131 \define@key[zf]{sizing}{Size}{ \tl_set:Nn \l_fontsing_size_tl {#1} }

1132 \define@key[zf]{sizing}{Font}{ \fontsing_complete_fontname:Nn \l_fontsing_sizedfont_t1 {#1} }

1133 \fontsing_complete_fontname:Nn \l_fontsing_sizedfont_t1 {#1}

1134 }
```

### 22.9.4 Font-independent features

These features can be applied to any font.

**Scale** If the input isn't one of the pre-defined string options, then it's gotta be numerical. `\fontsing_calc_scale:n` does all the work in the auto-scaling cases.

```
1135 \define@key[zf]{options}{Scale}{

1136   \prg_case_str:nnn {#1}
```

```

1137  {
1138      {MatchLowercase} { \fontspec_calc_scale:n {5} }
1139      {MatchUppercase} { \fontspec_calc_scale:n {8} }
1140  }
1141  { \tl_set:Nx \l_fontspec_scale_tl {\#1} }
1142  \zf@update@family{+scale:\l_fontspec_scale_tl}
1143  \tl_set:Nx \l_fontspec_scale_tl { s*[\l_fontspec_scale_tl] }
1144 }
```

`\fontspec_calc_scale:n` This macro calculates the amount of scaling between the default roman font and the (default shape of) the font being selected such that the font dimension that is input is equal for both. The only font dimensions that justify this are 5 (lowercase height) and 8 (uppercase height in X<sub>E</sub>T<sub>X</sub>).

This script is executed for every extra shape, which seems wasteful, but allows alternate italic shapes from a separate font, say, to be loaded and to be auto-scaled correctly. Even if this would be ugly.

```

1145 \cs_new:Npn \fontspec_calc_scale:n #1 {
1146     \group_begin:
1147         \rmfamily
1148         \fontspec_set_font_dimen:NnN \@tempdima {\#1} \font
1149         \fontspec_set_font_dimen:NnN \@tempdimb {\#1} \zf@basefont
1150         \dim_set:Nn \@tempdimc { 1pt*\@tempdima/\@tempdimb }
1151         \tl_gset:Nx \l_fontspec_scale_tl {\strip@pt\@tempdimc}
1152         \fontspec_info:n {set-scale}
1153     \group_end:
1154 }
```

This function sets the dimension #1 (for font #3) to what would be known as the ‘fontdimen’ #2 in T<sub>E</sub>X but apparently isn’t set that way in Lu<sub>A</sub>T<sub>X</sub>.

```

1155 \xetex_or_luatex:nnn { \cs_new:Npn \fontspec_set_font_dimen:NnN #1#2#3 } 
1156 {
1157     \dim_set:Nn #1 { \fontdimen #2 #3 }
1158 }
1159 {
1160     \dim_set:Nn #1 { \directlua{ fontspec.get_dimen(#2, "\cs_to_str:N #3") } }
1161 }
```

**Inter-word space** These options set the relevant \fontdimens for the font being loaded.

```

1162 \define@key[zf]{options}{WordSpace}{
1163     \zf@update@family{+wordspace:#1}
1164     \unless\ifzf@firsttime
1165         \zf@wordspace@parse#1,\zf@ii,\zf@iii,\zf@o
1166     \fi
1167 }
```

`\zf@wordspace@parse` This macro determines if the input to WordSpace is of the form {X} or {X,Y,Z} and executes the font scaling. If the former input, it executes {X,X,X}.

```

1168 \def\zf@wordspace@parse#1,#2,#3,#4\zf@{@
1169     \def\@tempa{#4}
```

```

1170 \ifx\@tempa\empty
1171   \setlength\@tempdima{\#1\fontdimen2\zf@basefont}
1172   \@tempdimb\@tempdima
1173   \@tempdimc\@tempdima
1174 \else
1175   \setlength\@tempdima{\#1\fontdimen2\zf@basefont}
1176   \setlength\@tempdimb{\#2\fontdimen3\zf@basefont}
1177   \setlength\@tempdimc{\#3\fontdimen4\zf@basefont}
1178 \fi
1179 \edef\zf@adjust{
1180   \zf@adjust
1181   \fontdimen2\font\the\@tempdima
1182   \fontdimen3\font\the\@tempdimb
1183   \fontdimen4\font\the\@tempdimc
1184 }
1185 }

```

**Punctuation space** Scaling factor for the nominal \fontdimen#7.

```

1186 \define@key[zf]{options}{PunctuationSpace}{
1187   \zf@update@family{+punctspace:#1}
1188   \setlength\@tempdima{\#1\fontdimen7\zf@basefont}
1189   \edef\zf@adjust{\zf@adjust\fontdimen7\font\the\@tempdima}
1190 }

```

### Letterspacing

```

1191 \define@key[zf]{options}{LetterSpace}{
1192   \zf@update@family{+tracking:#1}
1193   \zf@update@ff{letterspace=#1}
1194 }

```

**Hyphenation character** This feature takes one of three arguments: ‘None’, *<glyph>*, or *<slot>*. If the input isn’t the first, and it’s one character, then it’s the second; otherwise, it’s the third.

```

1195 \define@key[zf]{options}{HyphenChar}%
1196   \zf@update@family{+hyphenchar:#1}
1197   \edef\@tempa{\#1}
1198   \edef\@tempb{None}
1199   \ifx\@tempa\@tempb
1200     \xetex_or_luatex:nnn { \g@addto@macro\zf@adjust }
1201     { \hyphenchar\font-1\relax }
1202     { \luatexprehyphenchar=-1\relax }
1203   \else
1204     \zf@check@one@char#1\zf@@
1205     \ifx\@tempb\empty
1206       \xetex_or_luatex:nn {
1207         \zf@basefont\expandafter\ifnum\expandafter\XeTeXcharglyph
1208           \expandafter‘#1 \z@
1209           \g@addto@macro\zf@adjust{%
1210             \expandafter\hyphenchar\expandafter
1211             \font\expandafter‘#1}}%

```

```

1212     \else
1213         \fontspec_error:nx {no-glyph}{#1}
1214     \fi}%
1215 }{
1216     \ifnum\directlua{
1217         fontspec.print(fontspec.charglyph('#1', 'zf@basefont'))
1218     } \z@
1219         \g@addto@macro\zf@adjust{\luatexprehyphenchar='#1\relax}
1220     \else
1221         \fontspec_error:nx {no-glyph}{#1}
1222     \fi
1223 }
1224 \else
1225     \xetex_or_luatex:nn {
1226         {\zf@basefont\ifnum\XeTeXcharglyph#1 \z@
1227             \g@addto@macro\zf@adjust{\hyphenchar\font#1\relax}%
1228         \else
1229             \fontspec_error:nx {no-glyph}{#1}
1230         \fi}%
1231 }{
1232     \ifnum\directlua{
1233         fontspec.print(fontspec.charglyph('#1', 'zf@basefont'))
1234     } \z@
1235         \g@addto@macro\zf@adjust{\luatexprehyphenchar=#1\relax}
1236     \else
1237         \fontspec_error:nx {no-glyph}{#1}
1238     \fi
1239 }
1240     \fi
1241 \fi
1242 }
1243 \def\zf@check@one@char#1#2\zf@@{\def\@tempb{#2}}

```

## Color

```

1244 \define@key[zf]{options}{Color}{
1245   \zf@update@family{+col:#1}
1246   \zf@update@ff{color=#1}
1247 }
1248 \keyval@alias@key[zf]{options}{Color}{Colour}

```

## Mapping

```

1249 \xetex_or_luatex:nnn {
1250   \define@key[zf]{options}{Mapping}
1251 }{
1252   \zf@update@family{+map:#1}
1253   \zf@update@ff{mapping=#1}
1254 }{
1255   \tl_if_eq:nnTF {#1} {tex-text} {
1256     \fontspec_warning:n {no-mapping-ligtex}
1257     \msg_redirect_name:nnn {fontspec} {no-mapping-ligtex} {none}

```

```

1258     \setkeys[zf]{options}{ Ligatures=TeX }
1259     }{
1260     \fontspec_warning:n {no-mapping}
1261   }
1262 }
```

### FeatureFile

```

1263 \define@key[zf]{options}{FeatureFile}{
1264   \zf@update@family{+fea:#1}
1265   \zf@update@ff{featurefile=#1}
1266 }
```

### 22.9.5 Continuous font axes

```

1267 \define@key[zf]{options}{Weight}{
1268   \zf@update@family{+weight:#1}
1269   \zf@update@ff{weight=#1}
1270 }
1271 \define@key[zf]{options}{Width}{
1272   \zf@update@family{+width:#1}
1273   \zf@update@ff{width=#1}
1274 }
1275 \define@key[zf]{options}{OpticalSize}{
1276   \xetex_or_luatex:nn {
1277     \ifzf@icu
1278       \tl_set:Nn \l_fonts表白_size_tl {/ S = #1}
1279       \zf@update@family{+size:#1}
1280     \fi
1281     \ifzf@mm
1282       \zf@update@family{+size:#1}
1283       \zf@update@ff{optical size=#1}
1284     \fi
1285     \ifzf@icu\else
1286       \ifzf@mm\else
1287         \ifzf@firsttime
1288           \fontspec_warning:n {no-opticals}
1289         \fi
1290       \fi
1291     \fi
1292   }
1293   \tl_set:Nn \l_fonts表白_size_tl {/ S = #1}
1294   \zf@update@family{+size:#1}
1295 }
1296 }
```

### 22.9.6 Font transformations

```

1297 \define@key[zf]{options}{FakeSlant}{
1298   \zf@update@family{+slant:#1}
1299   \zf@update@ff{slant=#1}
1300 }
1301 \define@key[zf]{options}{FakeStretch}{
```

```

1302 \zf@update@family{+extend:#1}
1303 \zf@update@ff{extend=#1}
1304 }
1305 \define@key[zf]{options}{FakeBold}{
1306 \zf@update@family{+embolden:#1}
1307 \zf@update@ff{embolden=#1}
1308 }

```

### 22.9.7 Ligatures

The call to the nested keyval family must be wrapped in braces to hide the parent list (this later requires the use of global definitions (\xdef) in \zf@update@...). Both AAT and OpenType names are offered to chose Rare/Discretionary ligatures.

```

1309 \zf@define@font@feature{Ligatures}
1310 \zf@define@feature@option{Ligatures}{Required} {1}{0}{+rlig}
1311 \zf@define@feature@option{Ligatures}{NoRequired} {1}{1}{-rlig}
1312 \zf@define@feature@option{Ligatures}{Common} {1}{2}{+liga}
1313 \zf@define@feature@option{Ligatures}{NoCommon} {1}{3}{-liga}
1314 \zf@define@feature@option{Ligatures}{Rare} {1}{4}{+dlig}
1315 \zf@define@feature@option{Ligatures}{NoRare} {1}{5}{-dlig}
1316 \zf@define@feature@option{Ligatures}{Discretionary} {1}{4}{+dlig}
1317 \zf@define@feature@option{Ligatures}{NoDiscretionary}{1}{5}{-dlig}
1318 \zf@define@feature@option{Ligatures}{Contextual} {}{} {+clig}
1319 \zf@define@feature@option{Ligatures}{NoContextual} {}{} {-clig}
1320 \zf@define@feature@option{Ligatures}{Historical} {}{} {+hlig}
1321 \zf@define@feature@option{Ligatures}{NoHistorical} {}{} {-hlig}
1322 \zf@define@feature@option{Ligatures}{Logos} {1}{6} {}
1323 \zf@define@feature@option{Ligatures}{NoLogos} {1}{7} {}
1324 \zf@define@feature@option{Ligatures}{Rebus} {1}{8} {}
1325 \zf@define@feature@option{Ligatures}{NoRebus} {1}{9} {}
1326 \zf@define@feature@option{Ligatures}{Diphthong} {1}{10} {}
1327 \zf@define@feature@option{Ligatures}{NoDiphthong} {1}{11} {}
1328 \zf@define@feature@option{Ligatures}{Squared} {1}{12} {}
1329 \zf@define@feature@option{Ligatures}{NoSquared} {1}{13} {}
1330 \zf@define@feature@option{Ligatures}{AbbrevSquared} {1}{14} {}
1331 \zf@define@feature@option{Ligatures}{NoAbbrevSquared}{1}{15} {}
1332 \zf@define@feature@option{Ligatures}{Icelandic} {1}{32} {}
1333 \zf@define@feature@option{Ligatures}{NoIcelandic} {1}{33} {}

```

Emulate CM extra ligatures.

```

1334 \define@key[zf@feat]{Ligatures}{TeX}[]{ 
1335 \xetex_or_luatex:nn {
1336   \zf@update@family{+map:tex-text}
1337   \zf@update@ff{mapping=tex-text}
1338 }
1339   \zf@update@family{+tlig+trep}
1340   \zf@update@ff{+tlig;+trep}
1341 }
1342 }

```

### 22.9.8 Letters

```

1343 \zf@define@font@feature{Letters}
1344 \zf@define@feature@option{Letters}{Normal}           {3}{0}{}
1345 \zf@define@feature@option{Letters}{Uppercase}       {3}{1}{+case}
1346 \zf@define@feature@option{Letters}{Lowercase}       {3}{2}{}
1347 \zf@define@feature@option{Letters}{SmallCaps}        {3}{3}{+smcp}
1348 \zf@define@feature@option{Letters}{PetiteCaps}        {} {} {+pcap}
1349 \zf@define@feature@option{Letters}{UppercaseSmallCaps} {} {} {+c2sc}
1350 \zf@define@feature@option{Letters}{UppercasePetiteCaps} {} {} {+c2pc}
1351 \zf@define@feature@option{Letters}{InitialCaps}       {3}{4}{}
1352 \zf@define@feature@option{Letters}{Unicase}          {} {} {+unic}

```

### 22.9.9 Numbers

These were originally separated into NumberCase and NumberSpacing following AAT, but it makes more sense to combine them.

Both naming conventions are offered to select the number case.

```

1353 \zf@define@font@feature{Numbers}
1354 \zf@define@feature@option{Numbers}{Monospaced}   {6} {0}{+tnum}
1355 \zf@define@feature@option{Numbers}{Proportional} {6} {1}{+pnum}
1356 \zf@define@feature@option{Numbers}{Lowercase}    {21}{0}{+onum}
1357 \zf@define@feature@option{Numbers}{OldStyle}     {21}{0}{+onum}
1358 \zf@define@feature@option{Numbers}{Uppercase}    {21}{1}{+lnum}
1359 \zf@define@feature@option{Numbers}{Lining}       {21}{1}{+lnum}
1360 \zf@define@feature@option{Numbers}{SlashedZero}  {14}{5}{+zero}
1361 \zf@define@feature@option{Numbers}{NoSlashedZero}{14}{4}{-zero}

```

luatoload provides a custom anum feature for replacing Latin (AKA Arabic) numbers with Arabic (AKA Indic-Arabic). The same feature maps to Farsi (Persian) numbers if font language is Farsi.

```

1362 \luatex_if_engine:T {
1363   \zf@define@feature@option{Numbers}{Arabic}{}{}{+anum}
1364   \zf@define@feature@option{Numbers}{Farsi}{}{}{+anum}
1365 }

```

### 22.9.10 Contextuals

```

1366 \zf@define@font@feature {Contextuals}
1367 \zf@define@feature@option{Contextuals}{Swash}      {} {} {+cswh}
1368 \zf@define@feature@option{Contextuals}{NoSwash}     {} {} {-cswh}
1369 \zf@define@feature@option{Contextuals}{Alternate}   {} {} {+calt}
1370 \zf@define@feature@option{Contextuals}{NoAlternate} {} {} {-calt}
1371 \zf@define@feature@option{Contextuals}{WordInitial} {8}{0}{+init}
1372 \zf@define@feature@option{Contextuals}{NoWordInitial}{8}{1}{-init}
1373 \zf@define@feature@option{Contextuals}{WordFinal}    {8}{2}{+fina}
1374 \zf@define@feature@option{Contextuals}{NoWordFinal}  {8}{3}{-fina}
1375 \zf@define@feature@option{Contextuals}{LineInitial}  {8}{4}{}
1376 \zf@define@feature@option{Contextuals}{NoLineInitial}{8}{5}{}
1377 \zf@define@feature@option{Contextuals}{LineFinal}    {8}{6}{+falt}
1378 \zf@define@feature@option{Contextuals}{NoLineFinal}  {8}{7}{-falt}
1379 \zf@define@feature@option{Contextuals}{Inner}         {8}{8}{+medi}
1380 \zf@define@feature@option{Contextuals}{NoInner}       {8}{9}{-medi}

```

### 22.9.11 Diacritics

```
1381 \zf@define@font@feature{Diacritics}
1382 \zf@define@feature@option{Diacritics}{Show}      {9}{0}{}
1383 \zf@define@feature@option{Diacritics}{Hide}      {9}{1}{}
1384 \zf@define@feature@option{Diacritics}{Decompose} {9}{2}{}
1385 \zf@define@feature@option{Diacritics}{MarkToBase} {}{}{+mark}
1386 \zf@define@feature@option{Diacritics}{NoMarkToBase}{}{}{-mark}
1387 \zf@define@feature@option{Diacritics}{MarkToMark}  {}{}{+mkmk}
1388 \zf@define@feature@option{Diacritics}{NoMarkToMark}{}{}{-mkmk}
1389 \zf@define@feature@option{Diacritics}{AboveBase}   {}{}{+abvm}
1390 \zf@define@feature@option{Diacritics}{NoAboveBase} {}{}{-abvm}
1391 \zf@define@feature@option{Diacritics}{BelowBase}   {}{}{+blwm}
1392 \zf@define@feature@option{Diacritics}{NoBelowBase} {}{}{-blwm}
```

### 22.9.12 Kerning

```
1393 \zf@define@font@feature{Kerning}
1394 \zf@define@feature@option{Kerning}{Uppercase}{}{}{+cpsp}
1395 \zf@define@feature@option{Kerning}{On}        {}{}{+kern}
1396 \zf@define@feature@option{Kerning}{Off}       {}{}{-kern}
1397 %\zf@define@feature@option{Kerning}{Vertical}{}{}{+vkrn}
1398 %\zf@define@feature@option{Kerning}
1399 %  {VerticalAlternateProportional}{}{}{+vpal}
1400 %\zf@define@feature@option{Kerning}{VerticalAlternateHalfWidth}{}{}{+vhal}
```

### 22.9.13 Vertical position

```
1401 \zf@define@font@feature{VerticalPosition}
1402 \zf@define@feature@option{VerticalPosition}{Normal}    {10}{0}{}
1403 \zf@define@feature@option{VerticalPosition}{Superior}  {10}{1}{+sups}
1404 \zf@define@feature@option{VerticalPosition}{Inferior}  {10}{2}{+subs}
1405 \zf@define@feature@option{VerticalPosition}{Ordinal}   {10}{3}{+ordn}
1406 \zf@define@feature@option{VerticalPosition}{Numerator} {} {} {+numr}
1407 \zf@define@feature@option{VerticalPosition}{Denominator}{} {} {+dnom}
1408 \zf@define@feature@option{VerticalPosition}{ScientificInferior}{}{}{+sinf}
```

### 22.9.14 Fractions

```
1409 \zf@define@font@feature{Fractions}
1410 \zf@define@feature@option{Fractions}{On}      {11}{1}{+frac}
1411 \zf@define@feature@option{Fractions}{Off}     {11}{0}{-frac}
1412 \zf@define@feature@option{Fractions}{Diagonal} {11}{2}{}
1413 \zf@define@feature@option{Fractions}{Alternate}{} {} {+afrc}
```

### 22.9.15 Alternates and variants

Selected numerically because they don't have standard names. Very easy to process, very annoying for the user!

```
1414 \define@key[zf]{options}{Alternate}[0]{
1415   \setkeys*[zf@feat]{Alternate}{#1}
1416   \unless\ifx\XKV@rm\empty
1417     \def\XKV@tfam{Alternate}
1418     \fontspec_make_feature:nnn{17}{#1}{+salt=#1}
1419   \fi
```

```

1420 }
1421 \define@key[zf]{options}{Variant}{
1422   \setkeys*[zf@feat]{Variant}{#1}
1423   \unless\ifx\XKV@rm\@empty
1424     \def\XKV@tfam{Variant}
1425     \fontspec_make_feature:nnn{18}{#1}{+ss\two@digits{#1}}
1426   \fi
1427 }
1428 \aliasfontfeature{Variant}{StylisticSet}

```

### 22.9.16 Style

```

1429 \zf@define@font@feature{Style}
1430 \zf@define@feature@option{Style}{Alternate} {} {} {+salt}
1431 \zf@define@feature@option{Style}{Italic} {32}{2}{+ital}
1432 \zf@define@feature@option{Style}{Ruby} {28}{2}{+ruby}
1433 \zf@define@feature@option{Style}{Swash} {} {} {+swsh}
1434 \zf@define@feature@option{Style}{Historic} {} {} {+hist}
1435 \zf@define@option{Style}{Display} {19}{1}{}
1436 \zf@define@option{Style}{Engraved} {19}{2}{}
1437 \zf@define@option{Style}{TitlingCaps} {19}{4}{+titl}
1438 \zf@define@option{Style}{TallCaps} {19}{5}{}
1439 \zf@define@option{Style}{HorizontalKana}{} {} {+hkna}
1440 \zf@define@option{Style}{VerticalKana} {} {} {+vkna}

```

### 22.9.17 CJK shape

```

1441 \zf@define@font@feature{CJKShape}
1442 \zf@define@feature@option{CJKShape}{Traditional}{20}{0} {+trad}
1443 \zf@define@feature@option{CJKShape}{Simplified} {20}{1} {+smpl}
1444 \zf@define@feature@option{CJKShape}{JIS1978} {20}{2} {+jp78}
1445 \zf@define@feature@option{CJKShape}{JIS1983} {20}{3} {+jp83}
1446 \zf@define@feature@option{CJKShape}{JIS1990} {20}{4} {+jp90}
1447 \zf@define@feature@option{CJKShape}{Expert} {20}{10}{+expt}
1448 \zf@define@feature@option{CJKShape}{NLC} {20}{13}{+nlck}

```

### 22.9.18 Character width

```

1449 \zf@define@font@feature{CharacterWidth}
1450 \zf@define@feature@option{CharacterWidth}{Proportional}{22}{0}{+pwid}
1451 \zf@define@feature@option{CharacterWidth}{Full}{22}{1}{+fwid}
1452 \zf@define@feature@option{CharacterWidth}{Half}{22}{2}{+hwid}
1453 \zf@define@feature@option{CharacterWidth}{Third}{22}{3}{+twid}
1454 \zf@define@feature@option{CharacterWidth}{Quarter}{22}{4}{+qwid}
1455 \zf@define@feature@option{CharacterWidth}{AlternateProportional}{22}{5}{+palt}
1456 \zf@define@feature@option{CharacterWidth}{AlternateHalf}{22}{6}{+halt}
1457 \zf@define@feature@option{CharacterWidth}{Default}{22}{7}{}

```

### 22.9.19 Annotation

```

1458 \zf@define@font@feature{Annotation}
1459 \zf@define@feature@option{Annotation}{Off}{24}{0}{-nalt}
1460 \zf@define@feature@option{Annotation}{On}{}{}{+nalt}
1461 \zf@define@option{Annotation}{Box}{24}{1}{}

```

```

1462 \zf@define@feature@option{Annotation}{RoundedBox}{24}{2}{}
1463 \zf@define@feature@option{Annotation}{Circle}{24}{3}{}
1464 \zf@define@feature@option{Annotation}{BlackCircle}{24}{4}{}
1465 \zf@define@feature@option{Annotation}{Parenthesis}{24}{5}{}
1466 \zf@define@feature@option{Annotation}{Period}{24}{6}{}
1467 \zf@define@feature@option{Annotation}{RomanNumerals}{24}{7}{}
1468 \zf@define@feature@option{Annotation}{Diamond}{24}{8}{}
1469 \zf@define@feature@option{Annotation}{BlackSquare}{24}{9}{}
1470 \zf@define@feature@option{Annotation}{BlackRoundSquare}{24}{10}{}
1471 \zf@define@feature@option{Annotation}{DoubleCircle}{24}{11}{}

```

### 22.9.20 Vertical

```

1472 \zf@define@font@feature{Vertical}
1473 \define@key[zf@feat]{Vertical}{RotatedGlyphs}[]{}
1474   \ifzf@icu
1475     \fontspec_make_feature:nnn{}{}{+vrt2}
1476     \zf@update@family{+vert}
1477     \zf@update@ff{vertical}
1478   \else
1479     \zf@update@family{+vert}
1480     \zf@update@ff{vertical}
1481   \fi
1482 }

```

### 22.9.21 Script

1483 \newfontscript{Arabic}{arab}	\newfontscript{Armenian}{armn}
1484 \newfontscript{Balinese}{bali}	\newfontscript{Bengali}{beng}
1485 \newfontscript{Bopomofo}{bopo}	\newfontscript{Braille}{brai}
1486 \newfontscript{Buginese}{bugi}	\newfontscript{Buhid}{buhd}
1487 \newfontscript{Byzantine~Music}{byzm}	\newfontscript{Canadian~Syllabics}{cans}
1488 \newfontscript{Cherokee}{cher}	
1489 \newfontscript{CJK~Ideographic}{hani}	\newfontscript{Coptic}{copt}
1490 \newfontscript{Cypriot~Syllabary}{cpri}	\newfontscript{Cyrillic}{cyrl}
1491 \newfontscript{Default}{DFLT}	\newfontscript{Deseret}{dsrt}
1492 \newfontscript{Devanagari}{deva}	\newfontscript{Ethiopic}{ethi}
1493 \newfontscript{Georgian}{geor}	\newfontscript{Glagolitic}{glag}
1494 \newfontscript{Gothic}{goth}	\newfontscript{Greek}{grek}
1495 \newfontscript{Gujarati}{gujr}	\newfontscript{Gurmukhi}{guru}
1496 \newfontscript{Hangul~Jamo}{jamo}	\newfontscript{Hangul}{hang}
1497 \newfontscript{Hanunoo}{hano}	\newfontscript{Hebrew}{hebr}
1498 \newfontscript{Hiragana~and~Katakana}{kana}	
1499 \newfontscript{Javanese}{java}	\newfontscript{Kannada}{knnda}
1500 \newfontscript{Kharosthi}{khar}	\newfontscript{Khmer}{khmr}
1501 \newfontscript{Lao}{lao~}	\newfontscript{Latin}{latn}
1502 \newfontscript{Limbu}{limb}	\newfontscript{Linear~B}{linb}
1503 \newfontscript{Malayalam}{mlym}	\newfontscript{Math}{math}
1504 \newfontscript{Mongolian}{mong}	
1505 \newfontscript{Musical~Symbols}{musc}	\newfontscript{Myanmar}{mymr}
1506 \newfontscript{N'ko}{nko~}	\newfontscript{Ogham}{ogam}
1507 \newfontscript{Old~Italic}{ital}	
1508 \newfontscript{Old~Persian~Cuneiform}{xpeo}	
1509 \newfontscript{Oriya}{orya}	\newfontscript{Osmanya}{osma}

```

1510 \newfontscript{Phags-pa}{phag}          \newfontscript{Phoenician}{phnx}
1511 \newfontscript{Runic}{runr}             \newfontscript{Shavian}{shaw}
1512 \newfontscript{Sinhala}{sinh}
1513 \newfontscript{Sumero-Akkadian~Cuneiform}{xsux}
1514 \newfontscript{Syloti~Nagri}{sylo}       \newfontscript{Syriac}{syrc}
1515 \newfontscript{Tagalog}{tglg}           \newfontscript{Tagbanwa}{tagb}
1516 \newfontscript{Tai~Le}{tale}            \newfontscript{Tai~Lu}{talu}
1517 \newfontscript{Tamil}{taml}
1518 \newfontscript{Thaana}{thaan}
1519 \newfontscript{Tibetan}{tibt}
1520 \newfontscript{Ugaritic~Cuneiform}{ugar}\newfontscript{Yi}{yi~~}

```

For convenience:

```

1521 \newfontscript{Kana}{kana}
1522 \newfontscript{Maths}{math}
1523 \newfontscript{CJK}{hani}

```

### 22.9.22 Language

```

1524 \newfontlanguage{Abaza}{ABA}\newfontlanguage{Abkhazian}{ABK}
1525 \newfontlanguage{Adyghe}{ADY}\newfontlanguage{Afrikaans}{AFK}
1526 \newfontlanguage{Afar}{AFR}\newfontlanguage{Agaw}{AGW}
1527 \newfontlanguage{Altai}{ALT}\newfontlanguage{Amharic}{AMH}
1528 \newfontlanguage{Arabic}{ARA}\newfontlanguage{Aari}{ARI}
1529 \newfontlanguage{Arakanese}{ARK}\newfontlanguage{Assamese}{ASM}
1530 \newfontlanguage{Athapaskan}{ATH}\newfontlanguage{Avar}{AVR}
1531 \newfontlanguage{Awadhi}{AWA}\newfontlanguage{Aymara}{AYM}
1532 \newfontlanguage{Azeri}{AZE}\newfontlanguage{Badaga}{BAD}
1533 \newfontlanguage{Baghelkhandi}{BAG}\newfontlanguage{Balkar}{BAL}
1534 \newfontlanguage{Baule}{BAU}\newfontlanguage{Berber}{BBR}
1535 \newfontlanguage{Bench}{BCH}\newfontlanguage{Bible~Cree}{BCR}
1536 \newfontlanguage{Belarusian}{BEL}\newfontlanguage{Bemba}{BEM}
1537 \newfontlanguage{Bengali}{BEN}\newfontlanguage{Bulgarian}{BGR}
1538 \newfontlanguage{Bhili}{BHI}\newfontlanguage{Bhojpuri}{BHO}
1539 \newfontlanguage{Bikol}{BIK}\newfontlanguage{Bilen}{BIL}
1540 \newfontlanguage{Blackfoot}{BKF}\newfontlanguage{Balochi}{BLI}
1541 \newfontlanguage{Balante}{BLN}\newfontlanguage{Balti}{BLT}
1542 \newfontlanguage{Bambara}{BMB}\newfontlanguage{Bamileke}{BML}
1543 \newfontlanguage{Breton}{BRE}\newfontlanguage{Brahui}{BRH}
1544 \newfontlanguage{Braj~Bhasha}{BRI}\newfontlanguage{Burmese}{BRM}
1545 \newfontlanguage{Bashkir}{BSH}\newfontlanguage{Beti}{BTI}
1546 \newfontlanguage{Catalan}{CAT}\newfontlanguage{Cebuano}{CEB}
1547 \newfontlanguage{Chechen}{CHE}\newfontlanguage{Chaha~Gurage}{CHG}
1548 \newfontlanguage{Chattisgarhi}{CHH}\newfontlanguage{Chichewa}{CHI}
1549 \newfontlanguage{Chukchi}{CHK}\newfontlanguage{Chipewyan}{CHP}
1550 \newfontlanguage{Cherokee}{CHR}\newfontlanguage{Chuvash}{CHU}
1551 \newfontlanguage{Comorian}{CMR}\newfontlanguage{Coptic}{COP}
1552 \newfontlanguage{Cree}{CRE}\newfontlanguage{Carrier}{CRR}
1553 \newfontlanguage{Crimean~Tatar}{CRT}\newfontlanguage{Church~Slavonic}{CSL}
1554 \newfontlanguage{Czech}{CSY}\newfontlanguage{Danish}{DAN}
1555 \newfontlanguage{Dargwa}{DAR}\newfontlanguage{Woods~Cree}{DCR}
1556 \newfontlanguage{German}{DEU}
1557 \newfontlanguage{Dogri}{DGR}\newfontlanguage{Divehi}{DIV}

```

```

1558 \newfontlanguage{Djerma}{DJR}\newfontlanguage{Dangme}{DNG}
1559 \newfontlanguage{Dinka}{DNK}\newfontlanguage{Dungan}{DUN}
1560 \newfontlanguage{Dzongkha}{DZN}\newfontlanguage{Ebira}{EBI}
1561 \newfontlanguage{Eastern~Cree}{ECR}\newfontlanguage{Edo}{EDO}
1562 \newfontlanguage{Efik}{EFI}\newfontlanguage{Greek}{ELL}
1563 \newfontlanguage{English}{ENG}\newfontlanguage{Erzya}{ERZ}
1564 \newfontlanguage{Spanish}{ESP}\newfontlanguage{Estonian}{ETI}
1565 \newfontlanguage{Basque}{EUQ}\newfontlanguage{Evenki}{EVK}
1566 \newfontlanguage{Even}{EVN}\newfontlanguage{Ewe}{EWE}
1567 \newfontlanguage{French~Antillean}{FAN}\newfontlanguage{Farsi}{FAR}
1568 \newfontlanguage{Finnish}{FIN}\newfontlanguage{Fijian}{FJI}
1569 \newfontlanguage{Flemish}{FLE}\newfontlanguage{Forest~Nenets}{FNE}
1570 \newfontlanguage{Fon}{FON}\newfontlanguage{Faroese}{FOS}
1571 \newfontlanguage{French}{FRA}\newfontlanguage{Frisian}{FRI}
1572 \newfontlanguage{Friulian}{FRL}\newfontlanguage{Futa}{FTA}
1573 \newfontlanguage{Fulani}{FUL}\newfontlanguage{Ga}{GAD}
1574 \newfontlanguage{Gaelic}{GAE}\newfontlanguage{Gagauz}{GAG}
1575 \newfontlanguage{Galician}{GAL}\newfontlanguage{Garshuni}{GAR}
1576 \newfontlanguage{Garhwali}{GAW}\newfontlanguage{Ge'ez}{GEZ}
1577 \newfontlanguage{Gilyak}{GIL}\newfontlanguage{Gumuz}{GMZ}
1578 \newfontlanguage{Gondi}{GON}\newfontlanguage{Greenlandic}{GRN}
1579 \newfontlanguage{Garo}{GRO}\newfontlanguage{Guarani}{GUA}
1580 \newfontlanguage{Gujarati}{GUJ}\newfontlanguage{Haitian}{HAI}
1581 \newfontlanguage{Halam}{HAL}\newfontlanguage{Harauti}{HAR}
1582 \newfontlanguage{Hausa}{HAU}\newfontlanguage{Hawaiin}{HAW}
1583 \newfontlanguage{Hammer-Banna}{HBN}\newfontlanguage{Hiligaynon}{HIL}
1584 \newfontlanguage{Hindi}{HIN}\newfontlanguage{High~Mari}{HMA}
1585 \newfontlanguage{Hindko}{HND}\newfontlanguage{Ho}{HO}
1586 \newfontlanguage{Harari}{HRI}\newfontlanguage{Croatian}{HRV}
1587 \newfontlanguage{Hungarian}{HUN}\newfontlanguage{Armenian}{HYE}
1588 \newfontlanguage{Igbo}{IBO}\newfontlanguage{Ijo}{IJO}
1589 \newfontlanguage{Ilokano}{ILO}\newfontlanguage{Indonesian}{IND}
1590 \newfontlanguage{Ingush}{ING}\newfontlanguage{Inuktitut}{INU}
1591 \newfontlanguage{Irish}{IRI}\newfontlanguage{Irish~Traditional}{IRT}
1592 \newfontlanguage{Icelandic}{ISL}\newfontlanguage{Inari~Sami}{ISM}
1593 \newfontlanguage{Italian}{ITA}\newfontlanguage{Hebrew}{IWR}
1594 \newfontlanguage{Javanese}{JAV}\newfontlanguage{Yiddish}{JII}
1595 \newfontlanguage{Japanese}{JAN}\newfontlanguage{Judezmo}{JUD}
1596 \newfontlanguage{Jula}{JUL}\newfontlanguage{Kabardian}{KAB}
1597 \newfontlanguage{Kachchi}{KAC}\newfontlanguage{Kalenjin}{KAL}
1598 \newfontlanguage{Kannada}{KAN}\newfontlanguage{Karachay}{KAR}
1599 \newfontlanguage{Georgian}{KAT}\newfontlanguage{Kazakh}{KAZ}
1600 \newfontlanguage{Kebena}{KEB}\newfontlanguage{Khutsuri~Georgian}{KGE}
1601 \newfontlanguage{Khakass}{KHA}\newfontlanguage{Khanty-Kazim}{KHK}
1602 \newfontlanguage{Khmer}{KHM}\newfontlanguage{Khanty-Shurishkar}{KHS}
1603 \newfontlanguage{Khanty-Vakhi}{KHV}\newfontlanguage{Khowar}{KHW}
1604 \newfontlanguage{Kikuyu}{KIK}\newfontlanguage{Kirghiz}{KIR}
1605 \newfontlanguage{Kisii}{KIS}\newfontlanguage{Kokni}{KKN}
1606 \newfontlanguage{Kalmyk}{KLM}\newfontlanguage{Kamba}{KMB}
1607 \newfontlanguage{Kumaoni}{KMN}\newfontlanguage{Komo}{KMO}
1608 \newfontlanguage{Komso}{KMS}\newfontlanguage{Kanuri}{KNR}

```

1609 \newfontlanguage{Kodagu}{KOD}\newfontlanguage{Korean~Old~Hangul}{KOH}  
1610 \newfontlanguage{Konkani}{KOK}\newfontlanguage{Kikongo}{KON}  
1611 \newfontlanguage{Komi-Permyak}{KOP}\newfontlanguage{Korean}{KOR}  
1612 \newfontlanguage{Komi-Zyrian}{KOZ}\newfontlanguage{Kpelle}{KPL}  
1613 \newfontlanguage{Krio}{KRI}\newfontlanguage{Karakalpak}{KRK}  
1614 \newfontlanguage{Karelian}{KRL}\newfontlanguage{Karaim}{KRM}  
1615 \newfontlanguage{Karen}{KRN}\newfontlanguage{Koorete}{KRT}  
1616 \newfontlanguage{Kashmiri}{KSH}\newfontlanguage{Khasi}{KSI}  
1617 \newfontlanguage{Kildin~Sami}{KSM}\newfontlanguage{Kui}{KUI}  
1618 \newfontlanguage{Kulvi}{KUL}\newfontlanguage{Kumyk}{KUM}  
1619 \newfontlanguage{Kurdish}{KUR}\newfontlanguage{Kurukh}{KUU}  
1620 \newfontlanguage{Kuy}{KUY}\newfontlanguage{Koryak}{KYK}  
1621 \newfontlanguage{Ladin}{LAD}\newfontlanguage{Lahuli}{LAH}  
1622 \newfontlanguage{Lak}{LAK}\newfontlanguage{Lambani}{LAM}  
1623 \newfontlanguage{Lao}{LAO}\newfontlanguage{Latin}{LAT}  
1624 \newfontlanguage{Laz}{LAZ}\newfontlanguage{L-Cree}{LCR}  
1625 \newfontlanguage{Ladakhi}{LDK}\newfontlanguage{Lezgi}{LEZ}  
1626 \newfontlanguage{Lingala}{LIN}\newfontlanguage{Low~Mari}{LMA}  
1627 \newfontlanguage{Limbu}{LMB}\newfontlanguage{Lomwe}{LMW}  
1628 \newfontlanguage{Lower~Sorbian}{LSB}\newfontlanguage{Lule~Sami}{LSM}  
1629 \newfontlanguage{Lithuanian}{LTH}\newfontlanguage{Luba}{LUB}  
1630 \newfontlanguage{Luganda}{LUG}\newfontlanguage{Luhya}{LUH}  
1631 \newfontlanguage{Luo}{LUO}\newfontlanguage{Latvian}{LVI}  
1632 \newfontlanguage{Majang}{MAJ}\newfontlanguage{Makua}{MAK}  
1633 \newfontlanguage{Malayalam~Traditional}{MAL}\newfontlanguage{Mansi}{MAN}  
1634 \newfontlanguage{Marathi}{MAR}\newfontlanguage{Marwari}{MAW}  
1635 \newfontlanguage{Mbundu}{MBN}\newfontlanguage{Manchu}{MCH}  
1636 \newfontlanguage{Moose~Cree}{MCR}\newfontlanguage{Mende}{MDE}  
1637 \newfontlanguage{Me'en}{MEN}\newfontlanguage{Mizo}{MIZ}  
1638 \newfontlanguage{Macedonian}{MKD}\newfontlanguage{Male}{MLE}  
1639 \newfontlanguage{Malagasy}{MLG}\newfontlanguage{Malinke}{MLN}  
1640 \newfontlanguage{Malayalam~Reformed}{MLR}\newfontlanguage{Malay}{MLY}  
1641 \newfontlanguage{Mandinka}{MND}\newfontlanguage{Mongolian}{MNG}  
1642 \newfontlanguage{Manipuri}{MNI}\newfontlanguage{Maninka}{MNK}  
1643 \newfontlanguage{Manx~Gaelic}{MNX}\newfontlanguage{Moksha}{MOK}  
1644 \newfontlanguage{Moldavian}{MOL}\newfontlanguage{Mon}{MON}  
1645 \newfontlanguage{Moroccan}{MOR}\newfontlanguage{Maori}{MRI}  
1646 \newfontlanguage{Maithili}{MTH}\newfontlanguage{Maltese}{MTS}  
1647 \newfontlanguage{Mundari}{MUN}\newfontlanguage{Naga-Assamese}{NAG}  
1648 \newfontlanguage{Nanai}{NAN}\newfontlanguage{Naskapi}{NAS}  
1649 \newfontlanguage{N-Cree}{NCR}\newfontlanguage{Ndebele}{NDB}  
1650 \newfontlanguage{Ndonga}{NDG}\newfontlanguage{Nepali}{NEP}  
1651 \newfontlanguage{Newari}{NEW}\newfontlanguage{Nagari}{NGR}  
1652 \newfontlanguage{Norway~House~Cree}{NHC}\newfontlanguage{Nisi}{NIS}  
1653 \newfontlanguage{Niuean}{NIU}\newfontlanguage{Nkole}{NKL}  
1654 \newfontlanguage{N'ko}{NKO}\newfontlanguage{Dutch}{NLD}  
1655 \newfontlanguage{Nogai}{NOG}\newfontlanguage{Norwegian}{NOR}  
1656 \newfontlanguage{Northern~Sami}{NSM}\newfontlanguage{Northern~Tai}{NTA}  
1657 \newfontlanguage{Esperanto}{NTO}\newfontlanguage{Nynorsk}{NYN}  
1658 \newfontlanguage{Oji-Cree}{OCR}\newfontlanguage{Ojibway}{OJB}  
1659 \newfontlanguage{Oriya}{ORI}\newfontlanguage{Oromo}{ORO}

1660 \newfontlanguage{Ossetian}{OSS}\newfontlanguage{Palestinian~Aramaic}{PAA}  
1661 \newfontlanguage{Pali}{PAL}\newfontlanguage{Punjabi}{PAN}  
1662 \newfontlanguage{Palpa}{PAP}\newfontlanguage{Pashto}{PAS}  
1663 \newfontlanguage{Polytonic~Greek}{PGR}\newfontlanguage{Pilipino}{PIL}  
1664 \newfontlanguage{Palaung}{PLG}\newfontlanguage{Polish}{PLK}  
1665 \newfontlanguage{Provencal}{PRO}\newfontlanguage{Portuguese}{PTG}  
1666 \newfontlanguage{Chin}{QIN}\newfontlanguage{Rajasthani}{RAJ}  
1667 \newfontlanguage{R-Cree}{RCR}\newfontlanguage{Russian~Buriat}{RBU}  
1668 \newfontlanguage{Riang}{RIA}\newfontlanguage{Rhaeto-Romanic}{RMS}  
1669 \newfontlanguage{Romanian}{ROM}\newfontlanguage{Romany}{ROY}  
1670 \newfontlanguage{Rusyn}{RSY}\newfontlanguage{Ruanda}{RUA}  
1671 \newfontlanguage{Russian}{RUS}\newfontlanguage{Sadri}{SAD}  
1672 \newfontlanguage{Sanskrit}{SAN}\newfontlanguage{Santali}{SAT}  
1673 \newfontlanguage{Sayisi}{SAY}\newfontlanguage{Sekota}{SEK}  
1674 \newfontlanguage{Selkup}{SEL}\newfontlanguage{Sango}{SGO}  
1675 \newfontlanguage{Shan}{SHN}\newfontlanguage{Sibe}{SIB}  
1676 \newfontlanguage{Sidamo}{SID}\newfontlanguage{Silte~Gurage}{SIG}  
1677 \newfontlanguage{Skolt~Sami}{SKS}\newfontlanguage{Slovak}{SKY}  
1678 \newfontlanguage{Slavey}{SLA}\newfontlanguage{Slovenian}{SLV}  
1679 \newfontlanguage{Somali}{SML}\newfontlanguage{Samoan}{SMO}  
1680 \newfontlanguage{Sena}{SNA}\newfontlanguage{Sindhi}{SND}  
1681 \newfontlanguage{Sinhalese}{SNH}\newfontlanguage{Soninke}{SNK}  
1682 \newfontlanguage{Sodo~Gurage}{SOG}\newfontlanguage{Sotho}{SOT}  
1683 \newfontlanguage{Albanian}{SQI}\newfontlanguage{Serbian}{SRB}  
1684 \newfontlanguage{Saraiki}{SRK}\newfontlanguage{Serer}{SRR}  
1685 \newfontlanguage{South~Slavey}{SSL}\newfontlanguage{Southern~Sami}{SSM}  
1686 \newfontlanguage{Suri}{SUR}\newfontlanguage{Svan}{SVA}  
1687 \newfontlanguage{Swedish}{SVE}\newfontlanguage{Swadaya~Aramaic}{SWA}  
1688 \newfontlanguage{Swahili}{SWK}\newfontlanguage{Swazi}{SWZ}  
1689 \newfontlanguage{Sutu}{SXT}\newfontlanguage{Syriac}{SYR}  
1690 \newfontlanguage{Tabasaran}{TAB}\newfontlanguage{Tajiki}{TAJ}  
1691 \newfontlanguage{Tamil}{TAM}\newfontlanguage{Tatar}{TAT}  
1692 \newfontlanguage{TH-Cree}{TCR}\newfontlanguage{Telugu}{TEL}  
1693 \newfontlanguage{Tongan}{TGN}\newfontlanguage{Tigre}{TGR}  
1694 \newfontlanguage{Tigrinya}{TGY}\newfontlanguage{Thai}{THA}  
1695 \newfontlanguage{Tahitian}{THT}\newfontlanguage{Tibetan}{TIB}  
1696 \newfontlanguage{Turkmen}{TKM}\newfontlanguage{Temne}{TMN}  
1697 \newfontlanguage{Tswana}{TNA}\newfontlanguage{Tundra~Nenets}{TNE}  
1698 \newfontlanguage{Tonga}{TNG}\newfontlanguage{Todo}{TOD}  
1699 \newfontlanguage{Tsonga}{TSG}\newfontlanguage{Turoyo~Aramaic}{TUA}  
1700 \newfontlanguage{Tulu}{TUL}\newfontlanguage{Tuvin}{TUV}  
1701 \newfontlanguage{Twi}{TWI}\newfontlanguage{Udmurt}{UDM}  
1702 \newfontlanguage{Ukrainian}{UKR}\newfontlanguage{Urdu}{URD}  
1703 \newfontlanguage{Upper~Sorbian}{USB}\newfontlanguage{Uyghur}{UYG}  
1704 \newfontlanguage{Uzbek}{UZB}\newfontlanguage{Venda}{VEN}  
1705 \newfontlanguage{Vietnamese}{VIT}\newfontlanguage{Wa}{WA}  
1706 \newfontlanguage{Wagdi}{WAG}\newfontlanguage{West-Cree}{WCR}  
1707 \newfontlanguage{Welsh}{WEL}\newfontlanguage{Wolof}{WLF}  
1708 \newfontlanguage{Tai~Lue}{XBD}\newfontlanguage{Xhosa}{XHS}  
1709 \newfontlanguage{Yakut}{YAK}\newfontlanguage{Yoruba}{YBA}  
1710 \newfontlanguage{Y-Cree}{YCR}\newfontlanguage{Yi~Classic}{YIC}

```

1711 \newfontlanguage{Yi~Modern}{YIM}\newfontlanguage{Chinese~Hong~Kong}{ZHH}
1712 \newfontlanguage{Chinese~Phonetic}{ZHP}\newfontlanguage{Chinese~Simplified}{ZHS}
1713 \newfontlanguage{Chinese~Traditional}{ZHT}\newfontlanguage{Zande}{ZND}
1714 \newfontlanguage{Zulu}{ZUL}

```

**Turkish** Turns out that many fonts use ‘TUR’ as their Turkish language tag rather than the specified ‘TRK’. So we check for both:

```

1715 \define@key[zf@feat]{Lang}{Turkish}[]{%
1716   \fontspec_check_lang:nTF {TRK} {%
1717     \c@zf@language\l_fontspec_strnum_int\relax
1718     \zf@update@family{+lang=Turkish}
1719     \tl_set:Nn \l_fontspec_lang_tl {TRK}
1720   }%
1721   \fontspec_check_lang:nTF {TUR} {%
1722     \c@zf@language\l_fontspec_strnum_int\relax
1723     \zf@update@family{+lang=Turkish}
1724     \tl_set:Nn \l_fontspec_lang_tl {TUR}
1725   }%
1726   \fontspec_warning:nx {language-not-exist} {#1}
1727 }
1728 }
1729 }

```

## Default

```

1730 \define@key[zf@feat]{Lang}{Default}[]{%
1731   \zf@update@family{+lang=dflt}
1732   \tl_set:Nn \l_fontspec_lang_tl {DFLT}
1733   \c@zf@language=0\relax
1734 }

```

### 22.9.23 Raw feature string

This allows savvy X<sub>E</sub>T<sub>E</sub>X-ers to input font features manually if they have already memorised the OpenType abbreviations and don’t mind not having error checking.

```

1735 \define@key[zf]{options}{RawFeature}{%
1736   \zf@update@family{+Raw:#1}
1737   \zf@update@ff{#1}
1738 }

```

## 22.10 Italic small caps

The following code for utilising italic small caps sensibly is inspired from Philip Lehman’s *The Font Installation Guide*. Note that `\upshape` needs to be used *twice* to get from italic small caps to regular upright (it always goes to small caps, then regular upright).

`\sishape` First, the commands for actually selecting italic small caps are defined. I use `si` as the NFSS shape for italic small caps, but I have seen `itsc` and `s1sc` also used. `\sdefault` may be redefined to one of these if required for compatibility.

```

1739 \providecommand*{\sideset}{\sideset}
1740 \DeclareRobustCommand{\sideset}{%
1741   \not@math@alphabet\sideset\relax
1742   \fontshape\sideset\selectfont
1743 }
1744 \DeclareTextFontCommand{\textset}{\sideset}

\zf@merge@shape This is the macro which enables the overload on the \.. shape commands. It takes three such arguments. In essence, the macro selects the first argument, unless the second argument is already selected, in which case it selects the third.
1745 \newcommand*{\zf@merge@shape}[3]{%
1746   \edef\@tempa{\#1}%
1747   \edef\@tempb{\#2}%
1748   \ifx\f@shape\@tempb
1749     \ifcsname\f@encoding/\f@family/\f@series/#3\endcsname
1750       \edef\@tempa{\#3}%
1751     \fi
1752   \fi
1753   \fontshape{\@tempa}\selectfont
1754 }

\itshape Here the original \.. shape commands are redefined to use the merge shape
\scshape macro.
\upshape 1755 \DeclareRobustCommand \itshape {
1756   \not@math@alphabet\itshape\mathit
1757   \zf@merge@shape\itdefault\scdefault\sideset
1758 }
1759 \DeclareRobustCommand \slshape {
1760   \not@math@alphabet\slshape\relax
1761   \zf@merge@shape\sldefault\scdefault\sideset
1762 }
1763 \DeclareRobustCommand \scshape {
1764   \not@math@alphabet\scshape\relax
1765   \zf@merge@shape\scdefault\itdefault\sideset
1766 }
1767 \DeclareRobustCommand \upshape {
1768   \not@math@alphabet\upshape\relax
1769   \zf@merge@shape\updefault\sideset\scdefault
1770 }

```

## 22.11 Selecting maths fonts

Here, the fonts used in math mode are redefined to correspond to the default roman, sans serif and typewriter fonts. Unfortunately, you can only define maths fonts in the preamble, otherwise I'd run this code whenever `\setmainfont` and friends was run.

`\zf@math` Everything here is performed `\AtBeginDocument` in order to overwrite euler's attempt. This means `fontspec` must be loaded *after* euler. We set up a conditional to return an error if this rule is violated.

Since every maths setup is slightly different, we also take different paths for defining various math glyphs depending which maths font package has been loaded.

```

1771 \@ifpackageloaded{euler}{\zf@package@euler@loadedtrue}
1772                                     {\zf@package@euler@loadedfalse}
1773 \def\zf@math{
1774   \let\zf@font@warning\@font@warning
1775   \let\@font@warning\@font@info
1776   \@ifpackageloaded{euler}{
1777     \ifzf@package@euler@loaded
1778       \zf@math@eulertrue
1779     \else
1780       \fontspec_error:n {euler-too-late}
1781     \fi
1782   }{}}
1783 \@ifpackageloaded{lucbmath}{\zf@math@lucidatruen}{}
1784 \@ifpackageloaded{lucidabr}{\zf@math@lucidatruen}{}
1785 \@ifpackageloaded{lucimatx}{\zf@math@lucidatruen}{}

```

Knuth's CM fonts fonts are all squashed together, combining letters, accents, text symbols and maths symbols all in the one font, cmr, plus other things in other fonts. Because we are changing the roman font in the document, we need to redefine all of the maths glyphs in L<sup>A</sup>T<sub>E</sub>X's operators maths font to still go back to the legacy cmr font for all these random glyphs, unless a separate maths font package has been loaded instead.

In every case, the maths accents are always taken from the operators font, which is generally the main text font. (Actually, there is a \hat accent in EulerFractur, but it's *ugly*. So I ignore it. Sorry if this causes inconvenience.)

```

1786 \DeclareSymbolFont{legacymaths}{OT1}{cmr}{m}{n}
1787 \SetSymbolFont{legacymaths}{bold}{OT1}{cmr}{bx}{n}
1788 \DeclareMathAccent{\acute}{\mathalpha}{legacymaths}{19}
1789 \DeclareMathAccent{\grave}{\mathalpha}{legacymaths}{18}
1790 \DeclareMathAccent{\ddot}{\mathalpha}{legacymaths}{127}
1791 \DeclareMathAccent{\tilde}{\mathalpha}{legacymaths}{126}
1792 \DeclareMathAccent{\bar}{\mathalpha}{legacymaths}{22}
1793 \DeclareMathAccent{\breve}{\mathalpha}{legacymaths}{21}
1794 \DeclareMathAccent{\check}{\mathalpha}{legacymaths}{20}
1795 \DeclareMathAccent{\hat}{\mathalpha}{legacymaths}{94} % too bad, euler
1796 \DeclareMathAccent{\dot}{\mathalpha}{legacymaths}{95}
1797 \DeclareMathAccent{\mathring}{\mathalpha}{legacymaths}{23}

```

**\colon: what's going on?** Okay, so : and \colon in maths mode are defined in a few places, so I need to work out what does what. Respectively, we have:

```

% fontmath.ltx:
\DeclareMathSymbol{\colon}{\mathpunct}{operators}{":3A}
\DeclareMathSymbol{:}{\mathrel}{operators}{":3A}

% amsmath.sty:
\renewcommand{\colon}{\nobreak\mskip2mu\mathpunct{}\nonscript

```

```

\mkern-\thinmuskip{:\!}\mskip6mu plus1mu\relax}

% euler.sty:
\DeclareMathSymbol{:\!}{\mathrel}{EulerFraktur}{3A}

% lucbmath.sty:
\DeclareMathSymbol{\@tempb}{\mathpunct}{operators}{58}
\ifx\colon\@tempb
    \DeclareMathSymbol{\colon}{\mathpunct}{operators}{58}
\fi
\DeclareMathSymbol{:\!}{\mathrel}{operators}{58}

```

(3A<sub>16</sub> = 58<sub>10</sub>) So I think, based on this summary, that it is fair to tell fontspec to ‘replace’ the operators font with legacymaths for this symbol, except when amsmath is loaded since we want to keep its definition.

```

1798 \begingroup
1799   \mathchardef\tempa="603A \relax
1800   \let\next\egroup
1801   \ifx\colon\@tempa
1802     \DeclareMathSymbol{\colon}{\mathpunct}{legacymaths}{58}
1803   \fi
1804 \endgroup

```

The following symbols are only defined specifically in euler, so skip them if that package is loaded.

```

1805 \ifzf@math@euler\else
1806   \DeclareMathSymbol{!}{\mathclose}{legacymaths}{33}
1807   \DeclareMathSymbol{:\!}{\mathrel}{legacymaths}{58}
1808   \DeclareMathSymbol{;}{\mathpunct}{legacymaths}{59}
1809   \DeclareMathSymbol{?}{\mathclose}{legacymaths}{63}

```

And these ones are defined both in euler and lucbmath, so we only need to run this code if no extra maths package has been loaded.

```

1810 \ifzf@math@lucida\else
1811   \DeclareMathSymbol{0}{\mathalpha}{legacymaths}{'0}
1812   \DeclareMathSymbol{1}{\mathalpha}{legacymaths}{'1}
1813   \DeclareMathSymbol{2}{\mathalpha}{legacymaths}{'2}
1814   \DeclareMathSymbol{3}{\mathalpha}{legacymaths}{'3}
1815   \DeclareMathSymbol{4}{\mathalpha}{legacymaths}{'4}
1816   \DeclareMathSymbol{5}{\mathalpha}{legacymaths}{'5}
1817   \DeclareMathSymbol{6}{\mathalpha}{legacymaths}{'6}
1818   \DeclareMathSymbol{7}{\mathalpha}{legacymaths}{'7}
1819   \DeclareMathSymbol{8}{\mathalpha}{legacymaths}{'8}
1820   \DeclareMathSymbol{9}{\mathalpha}{legacymaths}{'9}
1821   \DeclareMathSymbol{\Gamma}{\mathalpha}{legacymaths}{0}
1822   \DeclareMathSymbol{\Delta}{\mathalpha}{legacymaths}{1}
1823   \DeclareMathSymbol{\Theta}{\mathalpha}{legacymaths}{2}
1824   \DeclareMathSymbol{\Lambda}{\mathalpha}{legacymaths}{3}
1825   \DeclareMathSymbol{\Xi}{\mathalpha}{legacymaths}{4}
1826   \DeclareMathSymbol{\Pi}{\mathalpha}{legacymaths}{5}
1827   \DeclareMathSymbol{\Sigma}{\mathalpha}{legacymaths}{6}

```

```

1828 \DeclareMathSymbol{\Upsilon}{\mathalpha}{legacymaths}{7}
1829 \DeclareMathSymbol{\Phi}{\mathalpha}{legacymaths}{8}
1830 \DeclareMathSymbol{\Psi}{\mathalpha}{legacymaths}{9}
1831 \DeclareMathSymbol{\Omega}{\mathalpha}{legacymaths}{10}
1832 \DeclareMathSymbol{+}{\mathbin}{legacymaths}{43}
1833 \DeclareMathSymbol{=}{\mathrel}{legacymaths}{61}
1834 \DeclareMathDelimiter{()}{\mathopen}{legacymaths}{40}{largesymbols}{0}
1835 \DeclareMathDelimiter{}{\mathclose}{legacymaths}{41}{largesymbols}{1}
1836 \DeclareMathDelimiter{[]}{\mathopen}{legacymaths}{91}{largesymbols}{2}
1837 \DeclareMathDelimiter{}{\mathclose}{legacymaths}{93}{largesymbols}{3}
1838 \DeclareMathDelimiter{/}{\mathord}{legacymaths}{47}{largesymbols}{14}
1839 \DeclareMathSymbol{\mathdollar}{\mathord}{legacymaths}{36}
1840 \fi
1841 \fi

```

Finally, we change the font definitions for `\mathrm` and so on. These are defined using the `\zf@rmmaths(...)` macros, which default to `\rmdefault` but may be specified with the `\setmathrm(...)` commands in the preamble.

Since L<sup>A</sup>T<sub>E</sub>X only generally defines one level of boldness, we omit `\mathbf` in the bold maths series. It can be specified as per usual with `\setboldmathrm`, which stores the appropriate family name in `\zf@rboldmaths`.

```

1842 \DeclareSymbolFont{operators}\zf@enc\zf@rmmaths\mddefault\updefault
1843 \SetSymbolFont{operators}{normal}\zf@enc\zf@rmmaths\mddefault\updefault
1844 \SetMathAlphabet\mathrm{normal}\zf@enc\zf@rmmaths\mddefault\updefault
1845 \SetMathAlphabet\mathit{normal}\zf@enc\zf@rmmaths\mddefault\itdefault
1846 \SetMathAlphabet\mathbf{normal}\zf@enc\zf@rmmaths\bfdefault\updefault
1847 \SetMathAlphabet\mathsf{normal}\zf@enc\zf@sfmaths\mddefault\updefault
1848 \SetMathAlphabet\mathtt{normal}\zf@enc\zf@ttmaths\mddefault\updefault
1849 \SetSymbolFont{operators}{bold}\zf@enc\zf@rmmaths\bfdefault\updefault
1850 \ifdefined\zf@rboldmaths
1851   \SetMathAlphabet\mathrm{bold}\zf@enc\zf@rboldmaths\mddefault\updefault
1852   \SetMathAlphabet\mathbf{bold}\zf@enc\zf@rboldmaths\bfdefault\updefault
1853   \SetMathAlphabet\mathit{bold}\zf@enc\zf@rboldmaths\mddefault\itdefault
1854 \else
1855   \SetMathAlphabet\mathrm{bold}\zf@enc\zf@rmmaths\bfdefault\updefault
1856   \SetMathAlphabet\mathit{bold}\zf@enc\zf@rmmaths\bfdefault\itdefault
1857 \fi
1858 \SetMathAlphabet\mathsf{bold}\zf@enc\zf@sfmaths\bfdefault\updefault
1859 \SetMathAlphabet\mathtt{bold}\zf@enc\zf@ttmaths\bfdefault\updefault
1860 \let\font@warning\zf@font@warning

```

`\zf@math@maybe` We're a little less sophisticated about not executing the `\zf@maths` macro if various other maths font packages are loaded. This list is based on the wonderful 'L<sup>A</sup>T<sub>E</sub>X Font Catalogue': <http://www.tug.dk/FontCatalogue/mathfonts.html>. I'm sure there are more I've missed. Do the T<sub>E</sub>X Gyre fonts have maths support yet?

Untested: would `\unless\ifnum\Gamma=28672\relax\zf@mathfalse\fi` be a better test? This needs more cooperation with euler and lucida, I think.

```

1861 \def\zf@math@maybe{
1862   \@ifpackageloaded{anttor}{
1863     \ifx\define@antt@mathversions a\@zf@mathfalse\fi}{}}
1864   \@ifpackageloaded{arev}{\@zf@mathfalse}{}}

```

```

1865 \ifpackageloaded{eulervm}{\@zf@mathfalse}{}
1866 \ifpackageloaded{mathdesign}{\@zf@mathfalse}{}
1867 \ifpackageloaded{concmath}{\@zf@mathfalse}{}
1868 \ifpackageloaded{cmbright}{\@zf@mathfalse}{}
1869 \ifpackageloaded{mathesf}{\@zf@mathfalse}{}
1870 \ifpackageloaded{gfsartemisia}{\@zf@mathfalse}{}
1871 \ifpackageloaded{gfsneohellenic}{\@zf@mathfalse}{}
1872 \ifpackageloaded{iwona}{
1873   \ifx\define@iwona@mathversions a\@zf@mathfalse\fi}{}
1874 \ifpackageloaded{kpfonts}{\@zf@mathfalse}{}
1875 \ifpackageloaded{kmath}{\@zf@mathfalse}{}
1876 \ifpackageloaded{kurier} {
1877   \ifx\define@kurier@mathversions a\@zf@mathfalse\fi}{}
1878 \ifpackageloaded{fouriernc}{\@zf@mathfalse}{}
1879 \ifpackageloaded{fourier}{\@zf@mathfalse}{}
1880 \ifpackageloaded{mathpazo}{\@zf@mathfalse}{}
1881 \ifpackageloaded{mathptmx}{\@zf@mathfalse}{}
1882 \ifpackageloaded{MinionPro}{\@zf@mathfalse}{}
1883 \ifpackageloaded{unicode-math}{\@zf@mathfalse}{}
1884 \ifpackageloaded{breqn}{\@zf@mathfalse}{}
1885 \if@zf@math
1886   \fontspec_info:n {setup-math}
1887   \zf@math
1888 \fi
1889 }
1890 \AtBeginDocument{\zf@math@maybe}

```

## 22.12 Finishing up

Now we just want to set up loading the .cfg file, if it exists.

```

1891 \if@zf@configfile
1892   \InputIfFileExists{fontspec.cfg}
1893     {\typeout{fontspec.cfg~ loaded.}}
1894     {\typeout{No~ fontspec.cfg~ file~ found;~ no~ configuration~ loaded.}}
1895 \fi

```

The end! Thanks for coming.

## Part VII

# fontspec.lua

First we define some metadata.

```
1 fontspec      = { }
2
3 fontspec.module = {
4     name        = "fontspec",
5     version     = 2.0,
6     date        = "2009/12/04",
7     description = "Advanced font selection for LuaTeX.",
8     author      = "Khaled Hosny",
9     copyright   = "Khaled Hosny",
10    license     = "LPPL"
11}
12
13 luatexbase.provides_module(fontspec.module)
14
```

Some utility functions

```
15
16 utf = unicode.utf8
17
18 function fontspec.log (...) luatexbase.module_log (fontspec.module.name, string.format(...))
19 function fontspec.warning(...) luatexbase.module_warning(fontspec.module.name, string.format(...))
20 function fontspec.error  (...) luatexbase.module_error (fontspec.module.name, string.format(...))
21
22 function fontspec.print (...) tex.print(luatexbase.catcodetables['latex-package'], ...) end
23
```

The following functions check for exsistence of certain script, language or feature in a given font.

```
24
25 local function check_script(id, script)
26     local s = string.lower(script)
27     if id and id > 0 then
28         local otfdata = fonts.ids[id].shared.otfdata
29         if otfdata then
30             local features = otfdata.luatex.features
31             for i,_ in pairs(features) do
32                 for j,_ in pairs(features[i]) do
33                     if features[i][j][s] then
34                         fontspec.log("script '%s' exists in font '%s'", 
35                                     script, fonts.ids[id].fullname)
36                     return true
37                 end
38             end
39         end
40     end
41 end
```

```

42 end
43
44 local function check_language(id, language, script)
45     local s = string.lower(script)
46     local l = string.lower(language)
47     if id and id > 0 then
48         local otfdata = fonts.ids[id].shared.otfdata
49         if otfdata then
50             local features = otfdata.luatex.features
51             for i,_ in pairs(features) do
52                 for j,_ in pairs(features[i]) do
53                     if features[i][j][s] and features[i][j][s][l] then
54                         fontspec.log("language '%s' for script '%s' exists in font '%s'",
55                                     language, script, fonts.ids[id].fullname)
56                         return true
57                     end
58                 end
59             end
60         end
61     end
62 end
63
64 local function check_feature(id, feature, language, script)
65     local s = string.lower(script)
66     local l = string.lower(language)
67     local f = string.lower(feature:gsub("^[-]", ""))
68     if id and id > 0 then
69         local otfdata = fonts.ids[id].shared.otfdata
70         if otfdata then
71             local features = otfdata.luatex.features
72             for i,_ in pairs(features) do
73                 if features[i][f] and features[i][f][s] then
74                     if features[i][f][s][l] == true then
75                         fontspec.log("feature '%s' for language '%s' and script '%s' exists in font '%s'",
76                                     feature, language, script, fonts.ids[id].fullname)
77                         return true
78                     end
79                 end
80             end
81         end
82     end
83 end
84

```

This function takes a font csname (without the leading slash) and returns its internal font id. Since  $\text{\LaTeX}$  0.47, there is a built in `font.id()` function.

```

85
86 local function font_id(str)
87     local id
88     if tex.luatexversion = 47 then
89         id = font.id(str)
90     else

```

```

91         id = token.create(str)[2]
92     end
93     return id
94 end
95

```

The following are the function that get called from TeX end.

```

96
97 local function tempswatrue()  fontspec.sprint([[\\@tempswatrue]])  end
98 local function tempswafalse() fontspec.sprint([[\\@tempswafalse]]) end
99
100 function fontspec.check_ot_script(fnt, script)
101     if check_script(font_id(fnt), script) then
102         tempswatrue()
103     else
104         tempswafalse()
105     end
106 end
107
108 function fontspec.check_ot_lang(fnt, lang, script)
109     if check_language(font_id(fnt), lang, script) then
110         tempswatrue()
111     else
112         tempswafalse()
113     end
114 end
115
116 function fontspec.check_ot_feat(fnt, feat, lang, script)
117     for _, f in ipairs { "+trep", "+tlig", "+anum" } do
118         if feat == f then
119             tempswatrue()
120             return
121         end
122     end
123     if check_feature(font_id(fnt), feat, lang, script) then
124         tempswatrue()
125     else
126         tempswafalse()
127     end
128 end
129

```

Get font dimens for \fontspec\_calc\_scale:n (despite the name of this function, it doesn't return any arbitrary font dimen, only \dimen5 and \dimen8.)

```

130
131 function fontspec.get_dimen(fontdimen, csname)
132     local id, h, em, pt
133     if csname == "font" then
134         id = font.current()
135     else
136         id = font_id(csname)
137     end

```

```

138     if fontdimen == 8 then
139         h = fonts.ids[id].shared.otfdata.pfminfo.os2_capheight
140     elseif fontdimen == 5 then
141         h = fonts.ids[id].shared.otfdata.pfminfo.os2_xheight
142     end
143     em = fonts.ids[id].shared.otfdata.metadata.units_per_em
144     pt = fonts.ids[id].size / 65536
145     tex.print(string.format("%spt", (h/em)*pt))
146 end
147
148 function fonts.spec.charglyph(char, csname)
149     local id, c
150     if char then
151         if utf.len(char) == 1 then
152             c = utf.byte(utf.char(char:gsub("'", '0x'))))
153         else
154             c = utf.byte(char)
155         end
156
157         if csname then
158             id = font_id(csname)
159         else
160             id = font.current()
161         end
162
163         if font.fonts[id]["characters"][c] then
164             return font.fonts[id]["characters"][c].index
165         else
166             return 0
167         end
168     else
169         return 0
170     end
171 end
172

```

## Part VIII

# fontspec-patches.sty

1 \ExplSyntaxOn

### 22.13 Unicode footnote symbols

2 \RequirePackage{fixltx2e}[2006/03/24]

### 22.14 Emph

\em Redefinition of {\em ...} and \emph{...} to use NFSS info to detect when the inner shape should be used.

\emshape 3 \DeclareRobustCommand \em {

\eminnershape 4 \nomath\em

5 \tl\_if\_eq:xxTF \f@shape \itdefault \eminnershape \emshape

6 }

7 \DeclareTextFontCommand{\emph}{\em}

8 \let\emshape\itshape

9 \let\eminnershape\upshape

### 22.15 \-

\- This macro is courtesy of Frank Mittelbach and the L<sup>A</sup>T<sub>E</sub>X 2<sub>&</sub> source code.

10 \DeclareRobustCommand{\-}{%

11 \discretionary{%

12 \char\ifnum\hyphenchar\font\z@

13 \else\def\xlx@defaulthyphenchar

14 \else\hyphenchar\font

15 \fi}{}}{}}

17 \def\xlx@defaulthyphenchar{'-`}

### 22.16 Verbatims

Many thanks to Apostolos Syropoulos for discovering this problem and writing the redefinition of L<sup>A</sup>T<sub>E</sub>X's verbatim environment and \verb\* command.

\xxt@visiblespace Print U+2434: OPEN BOX, which is used to visibly display a space character.

18 \def\xxt@visiblespace{

19 \iffontchar\font"2423

20 \expandafter\textvisiblespace

21 \else\expandafter\xxt@visiblespace@fallback

22 \fi

24 }

\xxt@visiblespace@fallback If the current font doesn't have u2434, use Latin Modern Mono instead.

25 \def\xxt@visiblespace@fallback{

26 {

```

27     \usefont{EU1}{lmtt}{\f@series}{\f@shape}
28     \textvisiblespace
29 }
30 }

\xxt@vprintspaces Helper macro to turn spaces active and print visible space instead.
31 \begingroup
32   \catcode`\~=active
33   \gdef\xxt@vprintspaces{\catcode`\~active\let \xxt@visiblespace}
34 \endgroup

\verb Redefine \verb to use \xxt@vprintspaces.
\verb* 35 \def\verb{
36   \relax\ifmmode\hbox\else\leavevmode\null\fi
37   \bgroup
38     \verb@eol@error \let\do\@makeother \dospecials
39     \verbatim@font\@noligs
40     \@ifstar\@@sverb\@verb
41 }
42 \def\@@sverb{\xxt@vprintspaces\@sverb}

It's better to put small things into \AtBeginDocument, so here we go:
43 \AtBeginDocument{
44   \fontspec_patch_verbatim:
45   \fontspec_patch_moreverb:
46   \fontspec_patch_fancyverb:
47   \fontspec_patch_listings:
48 }

verbatim* With the verbatim package.
49 \cs_set:Npn \fontspec_patch_verbatim: {
50   \@ifpackageloaded{verbatim}{
51     \namedef{verbatim*}{
52       \begingroup\@verbatim\xxt@vprintspaces\verbatim@start
53     }
54   }{

This is for vanilla LaTeX.
55   \namedef{verbatim*}{\@verbatim\xxt@vprintspaces\@sxverbatim}
56 }
57 }

listingcont* This is for moreverb. The main listing* environment inherits this definition.
58 \cs_set:Npn \fontspec_patch_moreverb: {
59   \@ifpackageloaded{moreverb}{
60     \namedef{listingcont*}{
61       \def\verbatim@processline{
62         \the\listing@line \global\advance\listing@line\c_one
63         \the\verbatim@line\par
64       }
65       \@verbatim\xxt@vprintspaces\verbatim@start
66     }
67   }{}}

```

listings and fancyvrb make things nice and easy:

```
68 \cs_set:Npn \fontspec_patch_fancyvrb: {
69   \@ifpackageloaded{fancyvrb}{
70     \let\FancyVerbSpace\xxt@visiblespace
71   }{}
72 }

73 \cs_set:Npn \fontspec_patch_listings: {
74   \@ifpackageloaded{listings}{
75     \let\lst@visiblespace\xxt@visiblespace
76   }{}
77 }
```

## Part IX

# **fontspec.cfg**

As an example, and to avoid upsetting people as much as possible, I'm populating the default `fontspec.cfg` file with backwards compatibility feature aliases.

```
1
2 %%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
3 %% FOR BACKWARDS COMPATIBILITY WITH PREVIOUS VERSIONS %%
4
5 % Nothing here!
6 % I have absolutely no idea whether backwards compatibility,
7 % of the sort that was previously populated here, is important
8 % for version 2.
9
```

## Part X

# Example documents

```
1 ⟨lualatex⟩% !TEX TS-program = LuaLaTeX
2 ⟨xetex⟩% !TEX TS-program = XeLaTeX
3
4 \documentclass{article}
5
6 ⟨lualatex⟩\usepackage{fontspec}
7 ⟨xetex⟩\usepackage{xltextra}
8
9 \setmainfont[Ligatures=TeX]{TeX Gyre Pagella}
10 \setsansfont[Ligatures=TeX,Scale=MatchLowercase]{TeX Gyre Heros}
11 \setmonofont[Scale=MatchLowercase]{Inconsolata}
12
13 \frenchspacing % TeX's default is a little old-fashioned...
14
15 \begin{document}
16 \pagestyle{empty}
17
18 \section*{The basics of the \textsf{fontspec} package}
19
20 The \textsf{fontspec} package enables automatic font selection
21 for \LaTeX{} documents typeset with XeTeX{} or \LuaTeX{}.
22 The basic command is
23
24 {\centering \verb|\fontspec[font features]{font display name}|.\par}
25
26 The default, sans serif, and typewriter fonts may be set with the
27 \verb|\setmainfont|, \verb|\setsansfont| and \verb|\setmonofont|
28 commands, respectively, as shown in the preamble. They take the
29 same syntax as the \verb|\fontspec| package. All expected font
30 shapes are available:
31
32 \begin{center}
33   {\itshape Italics and \scshape small caps\dotsof}
34   {\sffamily\bfseries Bold sans serif and \itshape bold italic sans serif\dotsof}
35 \end{center}
36
37 Text fonts in maths mode are also changed (e.g., notice the cosine function in
38 '$\cos(n\pi)=\pm 1$') but only if the roman and sans serif fonts are set in
39 the preamble; \verb|\setmainfont| will not affect these maths mode fonts when
40 called mid-document.
41 Maths symbols themselves are not affected.
42
43 Notice the font features used to load the default fonts in the preamble.
44 The first, \verb|Ligatures=TeX|, enables regular \TeX{} ligatures like
45 \verb|‘---’| for ‘---’.
46 The second, \verb|Scale=MatchLowercase|, automatically scales the fonts to
47 the same x-height.
```

48

49 Please see the complete \textsf{fontspec} documentation for further  
50 information.

51

52 \end{document}

# Change History

v1.0		
General: Initial version.		29
v1.1		
General: Name change to fontspec.		29
\setmainfont: Implemented (with friends).		32
v1.10		
General: Color brought back into the .sty		51
New feature LetterSpace.		50
Some babel encoding problems resolved.		31
\addfontfeatures: Saved family information macro changes.		33
\zf@fontspec: Saved family info split into two (now three) macros.		38
Space zapped from L <sup>A</sup> T <sub>E</sub> X family name due to various problems.		38
\zf@make@feature: Removed embarrassing space after warnings.		43
\zf@math: Added lucimatx checking. (Not really tested, though.)		61
Fixed Lucida bug (missing \else)		61
v1.11		
General: HyphenChar checks its input now.		50
Added better support for Turkish language selection.		60
OpenType Variant fixed.		54
\emph: Redefinitions moved to xltextra.		61
\newfontface: Name change from \newfontfamily.		33
\newfontlanguage: Fixed \c@zf@language setting not being global.		35
\newfontscript: Fixed \c@zf@script setting not being global.		35
\zf@fontspec: Ensure bold/italic fonts are loaded with the same renderer as the regular font even if unspecified.		38
\zf@wordspace@parse: Improved saving \fontdimen stuff to \zd@adjust(also see PunctuationSpace).		50
v1.12		
General: BoldFont, etc., flags \zf@nobf conditional false rather than assuming it implicitly. This allows, e.g., empty BoldFont to be overloaded.		47
Finally, use the EU1 font encoding.		31
New feature ExternalLocation for loading external fonts.		46
Package option for disabling the EU1 encoding.		30
\addfontfeatures: Now use grouping to restore \zf@default@option change.	33	
\zf@make@aat@feature@string: Fixed result of \XeTeXfeaturename output change (empty string if odd non-exclusive selector).	44	
Removed \@thisfontfeature macro; replaced with \@tempa.	44	
v1.13		
General: RawFeature added		60
SizeFeatures: Beginnings of support for different font features for different font sizes, required by unicode-math.		48
\zf@DeclareFontShape: New feature SizeFeatures implemented.		40
\zf@make@feature: Warns (and fixes bug) when an AAT feature is requested for an ICU font and vice versa.		43
\zf@partial@fontname: Folded in the \@tempa \let command, changing the syntax.		48
v1.15		
General: RotatedGlyphs now works for ICU fonts.		55
v1.16		
\zf@math@maybe: Maths setup warning sent to the log file instead.		64

v1.17	
General: [quiet] now suppresses warnings.	30
New features <code>FakeSlant</code> , <code>FakeStretch</code> , <code>FakeBold</code> .	51
New package option [ <code>silent</code> ].	30
<code>\zf@DeclareFontShape</code> : slshape substitution bug fix (thanks Ulrike).	40
slshape substitution is now silent.	40
<code>\zf@fontspec</code> : New feature: <code>UprightFont</code> .	38
v1.2	
General: Initial OpenType support.	29
Support for <code>Scale</code> .	49
v1.3	
General: More OpenType support.	29
Support for <code>Mapping</code> and <code>Colour</code> .	51
<code>\defaultfontfeatures</code> : Implemented.	33
<code>\newAATfeature</code> : Implemented.	34
<code>\newfontfeature</code> : Implemented.	34
v1.3a	
General: Bug fix for OpenType small caps.	52
v1.4	
General: Support for <code>Weight</code> and <code>Width</code> AAT features.	51
<code>\defaultfontfeatures</code> : Name changed from <code>\setdefaultoptions</code> .	33
<code>\zf@math</code> : Selects the default <code>\mathXX</code> fonts.	61
v1.5	
General: New options for arbitrary bold/italic shapes.	47
<code>\addfontfeatures</code> : Implemented.	33
<code>\zf@fontspec</code> : Added code for choosing arbitrary bold/italic fonts.	38
Checks if the font family has already been defined.	38
NFSS specifiers now take the default values.	38
<code>\zf@make@font@shapes</code> : Absorbed font-checking from <code>\zf@fontspec</code> .	39
v1.5a	
<code>\zf@math</code> : Added fix for Computer Modern maths.	61
v1.6	
General: <code>Bold</code> option aliased to <code>BoldFont</code> .	47
<code>LetterCase</code> is now <code>Letters</code> and options changed appropriately.	52
<code>Scale</code> feature now updates family name.	49
All AAT Fractions features offered.	54
New OpenType feature: <code>Language</code>	56
New OpenType feature: <code>Script</code>	55
OpenType letters features: <code>PetiteCaps</code> and <code>PETITECAPS</code> .	52
OpenType ligature features: <code>Contextual</code> and <code>Historical</code> .	52
OpenType stylistic sets supports under the <code>Variant</code> option.	54
<code>\addfontfeatures</code> : Removed <code>\relaxing</code> of temporary macros.	33
<code>\fontspec</code> : Removed <code>\zf@currenfont</code> (unnecessary)	31
<code>\newfontface</code> : Implemented.	33
<code>\newfontfeature</code> : newff counter now uses LaTeX methods rather than primitive TeX. I don't know if there is any advantage to this.	34
<code>\setmainfont</code> : Changed <code>\rmdefault</code> , etc., assigning to use <code>\let</code> directly.	32
<code>\zf@fontspec</code> : Added code for choosing arbitrary bold/italic font features.	38
Writes some info to the <code>.log</code> file	38
<code>\zf@get@feature@requests</code> : Removed the space between the comma and <code>\zf@options</code> when it's concatenated with the defaults.	41

\zf@math: Removed mathtime support since XeTeX doesn't handle virtual fonts. Why did I put it in in the first place?	61
v1.7	
General: Style feature renamed from StyleOptions.	54
AAT Numbers:SlashedZero.	53
New feature: Annotation	55
New feature: CharacterShape	55
New feature: CharacterWidth	55
New feature: OpticalSize; works with both OpenType and MM fonts.	51
OpenType Alternate Fractions feature.	54
OpenType Alternate now only AAT.	54
Removed AAT check for weight/width axes (could also be Multiple Master)	51
\zf@define@feature@option: Implemented for the bulk of the feature processing code.	43
\zf@fontspec: Optional argument now mandatory.	38
\zf@make@aat@feature@string: Changed some \edefs to \let	44
Removed third argument; always saves the feature string in \zf@thisfontfeature	44
\zf@make@feature: Accommodation of the \zf@thisfontfeature change.	43
\zf@make@font@shapes: Changed some \edefs to \let.	39
Support for the OpticalSize feature.	39
\zf@make@smallcaps: Accommodation of the \zf@thisfontfeature change.	42
\zf@set@font@type: Added 'MM' font type; tests true, e.g., with Skia & Minion MM. Used with the OpticalSize feature.	38
Removed exclusivity from font type (AAT, OpenType) check, since fonts can be both.	38
Removed various \count255s.	38
\zf@update@ff: Fix for featureless fonts (e.g., the MS fonts) being ignored.	42
v1.8	
\setmathrm: Implemented (with friends).	32
\zf@math: Added support for user-specified \mathrm and others.	61
Finally fixed legacy maths font issues. Also checks that euler.sty is loaded in the right order.	61
v1.8a	
\zf@math: Added conditional to \colon math symbol (incompatibility with lucida and amsmath)	61
v1.9	
General: CharacterShape now CJKShape	55
SMALLCAPS option changed to UppercaseSmallCaps to facilitate option normalisation (to come). Similarly for PETITECAPS.	52
Swashes feature changed to Contextuals. Option of this feature Contextual changed to Swash, for obvious reasons.	53
TextSpacing now CharacterWidth, with associated option names' change.	55
Alternate/Variant options can be assigned names.	54
New Scale options: MatchLowercase and MatchUppercase.	49
New feature HyphenChar.	50
New feature Kerning.	53
New feature PunctuationSpace.	50
New feature UprightFeatures.	47
New feature Vertical.	55
New feature WordSpace.	49
New features SmallCapsFont and SmallCapsFeatures.	47

Package options (no)config, quiet implemented.	65
\addfontfeatures: Added \ignorespaces to make it invisible.	33
Changed \fontspec call to \@fontspec so that \ignorespaces isn't called unnecessarily.	33
\aliasfontfeature: Implemented.	34
\aliasfontfeatureoption: Implemented.	34
\emph: Redefined \em in order for nested emphases to work.	61
\fontspec: Added \ignorespaces to make it invisible.	31
\keyval@alias@key: Implemented.	43
\multi@alias@key: Implemented for \aliasfontfeature.	43
\newAATfeature: Replacement for \newfeaturecode.	34
\newfontlanguage: Implemented.	35
\newfontscript: Implemented.	35
\newICUfeature: Implemented.	34
\zf@calc@scale: Implemented for auto-scaling options.	49
\zf@check@ot@feat: Implemented.	46
\zf@check@ot@lang: Implemented.	45
\zf@check@ot@script: Implemented.	45
\zf@DeclareFontShape: Implemented as wrapper for \DeclareFontShape.	40
Slanted/italic shape substitution implemented.	40
\zf@fontspec: Absorbed the comma into \zf@..@options as to be more efficient when they are not defined.	38
Abstracted the long family name so the NFSS family is simple.	38
Incorporated \zf@get@feature@requests argument change.	38
Incorporated \zf@make@font@shapes change; removed \zf@options storage macro.	38
\zf@get@feature@requests: Absorbed comma into \zf@default@options, making \zf@current@options redundant.	41
Added an argument to eliminate the \zf@options macro.	41
Removed init stuff.	41
\zf@init: Taken from \zf@get@feature@requests.	41
\zf@make@feature: Now checks for OpenType feature.	43
\zf@make@font@shapes: \zf@scale@str eliminated.	39
Absorbed \IfEqFonts.	39
Added argument for \zf@get@feature@requests change.	39
Added code for SmallCaps... features.	39
Added logging of /B, /I, /BI failure.	39
Changed input syntax.	39
Incorporated \sidefault test into the \DeclareFontShape argument directly now that it's fully expanded.	39
Made local to hide \zf@fontname changes.	39
Removed \zf@scshape macro.	39
Removed \nfss@catcodes wrapper.	39
\zf@make@smallcaps: Now uses \zf@check@ot@feat.	42
\zf@math: Maths hex numbers converted to decimal.	61
Suppresses harmless maths font encoding warnings.	64
\zf@partial@fontname: Implemented.	48
\zf@update@family: Now fully expands arguments.	41
\zf@update@ff: Removed ridiculous \zf@feature@separator code.	42
\zf@v@strnum: Implemented.	45
\zf@wordspace@parse: Implemented.	50

# Index

Numbers written in italic refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

Symbols	
\-	10, 782
\@sverb	40, 42
\empty	267, 271, 352, 367, 531, 577, 588, 598, 608–610, 628, 629, 665, 677, 680, 748, 750, 789, 794, 837, 884, 894, 899, 902, 907, 913, 914, 1051, 1062, 1085, 1091, 1125, 1129, 1170, 1205, 1416, 1423
\firstofone	708
\font@info	1775
\font@warning	1774, 1775
\ifpackageloaded	50, 59, 69, 74, 1771, 1776, 1783–1785, 1862, 1864–1872, 1874–1876, 1878–1884
\ifstar	40
\makeother	38
\namedef	51, 55, 60
\nameuse	535
\ne	524, 939, 959, 983
\noligs	39
\nomath	4
\onlypreamble	248–251
\sverb	42
\sxverbatim	55
\tempa	45, 367, 529, 531, 664, 665, 667, 671, 794, 795, 837, 841, 883, 884, 900, 902, 1050, 1051, 1061, 1062, 1084, 1085, 1169, 1170, 1197, 1199, 1746, 1750, 1753, 1799, 1801
\tempb	670, 671, 886, 889, 891, 894, 895, 899, 900, 1198, 1199, 1205, 1243, 1747, 1748
\tempcntb	932, 934, 937, 951, 954, 957, 973, 977, 981
\tempdima	1148, 1150, 1171–1173, 1175, 1181, 1188, 1189
\tempdimb	1149, 1150, 1172, 1176, 1182
\tempdimc	1150, 1151, 1173, 1177, 1183
\tempfonta	666, 667
\tempfontb	669, 670, 675
\tempswafalse	98, 605, 606, 933, 953, 976
\tempswatrue	97, 604, 936, 956, 980
\verb	40
\verbatim	52, 55, 65
\@zf@configfilefalse	185
\@zf@configfiletrue	184
\@zf@mathfalse	183, 1863–1871, 1873–1875, 1877–1884
\@zf@mathtrue	182
\`	33, 65, 81, 92–94, 100, 113, 118, 123, 128, 129, 138, 139, 156
\~	32, 33
<b>A</b>	
\active	32, 33
\acute	1788
\addfontfeature	100, 284
\addfontfeatures	268
\advance	62, 523, 939, 959, 983
\aliasfontfeature	312, 1005, 1428
\aliasfontfeatureoption	312
\AtBeginDocument	43, 1890
<b>B</b>	
\bar	1792
\begin	15, 32
\begingroup	31, 52, 270, 500, 663, 1798
\bfdefault	579, 582, 612, 615, 619, 623, 631, 635, 1846, 1849, 1852, 1855, 1856, 1858, 1859
\bfseries	34
\bgroup	37
\bool_if:NF	1008
\bool_if:NTF	568
\bool_if:nTF	918
\bool_new:N	997
\bool_set_false:N	564
\bool_set_true:N	566, 1001
\breve	1793
<b>C</b>	
\c@zf@index	. 41, 933–935, 937, 939, 952, 954, 955, 957, 959, 975, 977, 979, 981, 983
\c@zf@language	43, 344, 399, 417, 546, 973, 978, 1717, 1722, 1733
\c@zf@newff	40, 287
\c@zf@script	42, 327, 397, 416, 445, 461, 544, 951, 955, 973, 978
\c_one	62

\c_zero .....	645	\define@choicekey .....	1013
\catcode .....	32, 33	\define@iwona@mathversions .....	1873
\centering .....	24	\define@key ..	288, 323, 340, 860, 863,
\char .....	12	998, 1006, 1035, 1040, 1045, 1049,	
\check .....	1794	1060, 1071, 1075, 1079, 1083,	
\clist_clear:N .....	770	1099, 1103, 1107, 1111, 1115,	
\clist_if_empty:NTF .....	694	1119, 1123, 1127, 1131, 1132,	
\clist_map_break: .....	566	1135, 1162, 1186, 1191, 1195,	
\clist_map_inline:Nn .....	562, 705	1244, 1250, 1263, 1267, 1271,	
\colon .....	1801, 1802	1275, 1297, 1301, 1305, 1334,	
\cos .....	38	1414, 1421, 1473, 1715, 1730, 1735	
\cs_generate_variant:Nn .....	498, 1098	\define@kurier@mathversions .....	1877
\cs_gset:cpx .....	530	\Delta .....	1822
\cs_gset:Npn .....	1002	\dim_set:Nn .....	1150, 1157, 1160
\cs_new:Npn .....	21, 24, 46, 50, 54–62, 321, 338, 575, 586, 597, 603, 627, 638, 806, 816, 830, 845, 882, 1145, 1155	\directlua .....	945, 965, 989, 1160, 1216, 1232
\cs_new_eq:NN .....	16, 18	\discretionary .....	11
\cs_set:cpx .....	287	\do .....	38
\cs_set:Npn .....	45, 49, 58, 68, 73, 499, 570, 747, 906, 909, 917, 1094	\document .....	207
\cs_set_eq:cc .....	866, 867	\documentclass .....	4
\cs_set_eq:NN .....	231, 311, 773	\dospecials .....	38
\cs_to_str:N .....	1160	\dot .....	1796
\csname .....	274, 275, 289, 381, 394, 413, 428, 441, 457, 472, 486, 524, 527, 532	\dots .....	33, 34
\cyrillicencoding .....	205, 208		
<b>D</b>			
\ddot .....	1790		
\DeclareDocumentCommand .....		\edef .....	45,
.....	211, 216, 221, 226, 232, 236, 240, 244, 255, 263, 266, 268, 285, 293, 302, 312, 313, 316, 333, 350	502, 529, 664, 667, 670, 674, 686, 795, 799, 803, 883, 886, 889, 891, 895, 900, 1050, 1061, 1084, 1179, 1189, 1197, 1198, 1746, 1747, 1750	
\DeclareFontFamily .....	549	\egroup .....	1800
\DeclareFontsExtensions .....	350	\else .....	14, 21, 36, 279, 358, 369, 372, 375, 385, 388, 404, 407, 419, 422, 432, 435, 448, 451, 463, 466, 477, 480, 491, 494, 525, 580, 591, 598, 613, 617, 621, 629, 633, 654, 673, 682, 685, 688, 839, 887, 890, 901, 913, 914, 938, 958, 982, 1054, 1065, 1088, 1174, 1203, 1212, 1220, 1224, 1228, 1236, 1285, 1286, 1478, 1779, 1805, 1810, 1854
\DeclareFontShape .....	719, 725	\else: .....	942, 946, 962, 968, 986, 995
\DeclareMathAccent .....	1788–1797	\em .....	3
\DeclareMathDelimiter .....	1834–1838	\eminnershape .....	3
\DeclareMathSymbol .....		\emph .....	3
.....	1802, 1806–1809, 1811–1833, 1839	\emshape .....	3
\DeclareOption .....	179, 182–186, 190	\end .....	35, 52
\DeclareRobustCommand .....	3, 10, 258, 1740, 1755, 1759, 1763, 1767	\endcsname .....	269, 274,
\DeclareSymbolFont .....	1786, 1842	275, 289, 294, 303, 356, 363, 380, 381, 393, 394, 412, 413, 427, 428,	
\DeclareTextFontCommand .....	7, 1744	440, 441, 456, 457, 471, 472, 485, 486, 521, 522, 524, 527, 532, 536, 1749	
\def .....	17, 18, 25, 35, 42, 61, 252– 254, 266, 1100, 1104, 1108, 1112, 1116, 1120, 1124, 1128, 1168, 1169, 1243, 1417, 1424, 1773, 1861	\endgroup .....	34, 277, 558, 691, 1804
\defaultfontfeatures .....	266		
\define@antt@mathversions .....	1863		

environments:	
listingcont* .....	58
verbatim* .....	49
\ExecuteOptions .....	194
\exp_after:wN .....	924, 925
\exp_not:N .	48, 52, 258, 259, 273, 719, 725
\exp_not:V .....	753
\expandafter .....	20, 22, 523, 526, 531, 532, 708, 1207, 1208, 1210, 1211
\ExplSyntaxOn .....	1, 2
F	
\f@encoding .....	1749
\f@family .....	269, 274, 275, 356, 363, 364, 380, 381, 393, 394, 412, 413, 427, 428, 440, 441, 456, 457, 471, 472, 485, 486, 1749
\f@series .....	27, 1749
\f@shape .....	5, 27, 1748
\f@size .....	364, 381, 394, 413, 428, 441, 457, 472, 486, 511, 513, 666, 669
\FancyVerbSpace .....	70
\fi .....	16, 23, 36, 281, 296, 305, 360, 371, 374, 377, 387, 390, 406, 409, 421, 424, 434, 437, 450, 453, 465, 468, 479, 482, 493, 496, 518, 528, 534, 557, 583, 584, 594, 595, 601, 605, 606, 616, 620, 624, 625, 632, 636, 647, 650, 656, 668, 682–684, 688–690, 735, 745, 796, 797, 800, 814, 821, 824, 842, 896–898, 903, 904, 913, 914, 940, 960, 984, 1058, 1069, 1092, 1124, 1128, 1166, 1178, 1214, 1222, 1230, 1238, 1240, 1241, 1280, 1284, 1289– 1291, 1419, 1426, 1481, 1751, 1752, 1781, 1803, 1840, 1841, 1857, 1863, 1873, 1877, 1888, 1895
\fi: .....	942, 946, 962, 968, 986, 995
\font .....	12, 15, 19, 364, 381, 394, 413, 428, 441, 457, 472, 486, 511, 513, 666, 669, 1148, 1181–1183, 1189, 1201, 1211, 1227
\font@warning .....	1860
\fontdimen .....	1157, 1171, 1175–1177, 1181–1183, 1188, 1189
\fontfamily .....	213, 259, 278
\fontname .....	667, 670
\fontshape .....	1742, 1753
\fontspec .....	24, 29, 211
\fontspec_calc_scale:n	1138, 1139, 1145
\fontspec_check_lang:n .....	948
\fontspec_check_lang:nTF .....	341, 447, 462, 948, 1716, 1721
\fontspec_check_ot_feat:n .....	971
\fontspec_check_ot_feat:nT	799, 803, 970
\fontspec_check_ot_feat:nTF .....	403, 418, 851, 970
\fontspec_check_script:n .....	929
\fontspec_check_script:nTF	324, 431, 929
\fontspec_complete_fontname:Nn .....	1046, 1056, 1067, 1072, 1076, 1080, 1090, 1094, 1133
\fontspec_error:n .....	54, 709, 1780
\fontspec_error:nx .....	55, 753, 1213, 1221, 1229, 1237
\fontspec_fullname:n .....	511, 513, 541, 570, 666, 669, 699, 713
\fontspec_get_features:n .....	519, 696, 710, 747
\fontspec_if_aat_feature:nn .....	362
\fontspec_if_aat_feature:nnTF ..	1, 362
\fontspec_if_current_language:n ..	484
\fontspec_if_current_language:nTF .....	1, 484
\fontspec_if_current_script:n .....	470
\fontspec_if_current_script:nTF ..	1, 470
\fontspec_if_detect_external:n ..	560
\fontspec_if_detect_external:nT .....	505, 560
\fontspec_if_feature:n .....	392
\fontspec_if_feature:nnn .....	411
\fontspec_if_feature:nnnTF .....	1, 411
\fontspec_if_feature:nTF .....	1, 392
\fontspec_if_fontsfont: .....	355
\fontspec_if_fontsfont:TF ..	1, 355
\fontspec_if_language:n .....	439
\fontspec_if_language:nn .....	455
\fontspec_if_language:nnTF .....	1, 455
\fontspec_if_language:nTF .....	1, 439
\fontspec_if_opentype: .....	379
\fontspec_if_opentype:TF .....	1, 379
\fontspec_if_script:n .....	426
\fontspec_if_script:nTF .....	1, 426
\fontspec_info:n .....	59, 1152, 1886
\fontspec_info:nx .....	60, 672
\fontspec_info:nxx .....	61, 537
\fontspec_init: .....	501, 757
\fontspec_iv_str_to_num:n .....	416, 417, 461, 906, 931, 950
\fontspec_iv_str_to_num:w ..	907, 909
\fontspec_make_AAT_feature:nn ..	820, 830

\fontspec_make_AAT_feature_string:nn	366, 793, 836, <u>882</u>	\if@zf@configfile .....	38, 1891
\fontspec_make_feature:nnn .....	<u>816</u> , 863, 1418, 1425, 1475	\if@zf@math .....	39, 1885
\fontspec_make_ICU_feature:n .....	823, 827, 845	\ifcase .....	641
\fontspec_namewrap:n ...	571, 773, 1002	\ifcsname .....	269, 294,
\fontspec_new_lang:nn ...	335, 336, 338	303, 356, 363, 380, 393, 412, 427,	
\fontspec_new_script:nn ..	318, 319, 321	440, 456, 471, 485, 521, 522, 536, 1749	
\fontspec_patch_fancyvrb: .....	46, 68	\ifdefined .....	1850
\fontspec_patch_listings: .....	47, 73	\iffontchar .....	19
\fontspec_patch_moreverb: .....	45, 58	\ifmmode .....	36
\fontspec_patch_verbatim: .....	44, 49	\ifnum ...	12, 645, 885, 934, 935, 954,
\fontspec_select:nn ..	212, 217, 222,	955, 977, 978, 1207, 1216, 1226, 1232	
227, 233, 237, 241, 245, 256, 273, <u>499</u>		\ifodd .....	888
\fontspec_set_bold: .....	552, <u>575</u>	\ifx .....	367, 577, 588,
\fontspec_set_bold_italic: ...	555, <u>603</u>	598, 608–610, 628, 629, 665, 671,	
\fontspec_set_bold_slanted: ...	556, <u>627</u>	677, 680, 682, 688, 794, 837, 884,	
\fontspec_set_font_dimen:NnN .....	1148, 1149, 1155	894, 899, 913, 914, 1051, 1062,	
\fontspec_set_font_type: .	382, 395,	1085, 1170, 1199, 1205, 1416,	
414, 429, 442, 458, 473, 487, 512, <u>638</u>		1423, 1748, 1801, 1863, 1873, 1877	
\fontspec_set_italic: .....	553, <u>586</u>	\ifzf@atsui .....	31, 365, 652, 792, 819
\fontspec_set_slanted: .....	554, <u>597</u>	\ifzf@firstime .....	26, 743, 812, 1124, 1128, 1164, 1287
\fontspec_setkeys:xx	46, 507, 509, 708, 751	\ifzf@graphite .....	34
\fontspec_setkeys:xxx .....	50, 516, 517	\ifzf@icu .....	32, 383, 396,
\fontspec_trace:n .....	62	415, 430, 443, 459, 474, 488, 515,	
\fontspec_v_str_to_num:n ...	<u>906</u> , 974	654, 732, 798, 822, 1277, 1285, 1474	
\fontspec_warning:n .....	56,	\ifzf@math@euler .....	35, 1805
180, 280, 833, 848, 1256, 1260, 1288		\ifzf@math@lucida .....	36, 1810
\fontspec_warning:nx .....	57, 329,	\ifzf@mm .....	33, 1281, 1286
346, 838, 855, 875, 1022, 1026, 1726		\ifzf@nobf .....	27, 576, 605
\fontspec_warning:nxx .....	58, 298, 307	\ifzf@noit .....	28, 587, 606
\frenchspacing .....	13	\ifzf@nosc .....	29, 678
<b>G</b>			
\g@addto@macro .....	207, 1200, 1209, 1219, 1227, 1235	\ifzf@package@euler@loaded ..	37, 1777
\Gamma .....	1821	\ifzf@tfm .....	30
\gdef .....	33	\ignorespaces .....	214, 282
\global .....	62, 511, 513, 523, 526	\InputIfFileExists .....	1892
\grave .....	1789	\int_new:N .....	44
\group_begin: .....	1146	\int_set:Nn .....	397, 399, 445, 910
\group_end: .....	1153	\int_use:N .....	544, 546
<b>H</b>			
\hat .....	1795	\intexpr_compare:nTF .....	1016
\hbox .....	36	\itdefault .....	5, 590,
\hyphenchar .....	12, 15, 1201, 1210, 1227	593, 612, 615, 619, 623, 682, 688,	
<b>I</b>			
\if@tempswa	607, 942, 946, 962, 968, 986, 995	\itshape .....	722, 726, 1757, 1765, 1845, 1853, 1856
<b>K</b>			
\key@undefined .	297, 306, 870, 872, 874	\itshape .....	<u>1755</u>
\keyval@alias@key .....		\key .....	
		\keyval .....	314, <u>865</u> , 876, 878, 880, 1248
<b>L</b>			
\l_fontspec_extension_t1	571, 1007, 1012	\l_fontspec_extensions_clist .	352, 562

\l_fontsdesc_external_bool . . . . .		<b>M</b>
. . . . .	997, 1001, 1008	\mathalpha . . . . . 1788–1797, 1811–1831
\l_fontsdesc_lang_name_tl . . . . .	130, 517, 778, 1042	\mathbf . . . . . 95, 1846, 1852
\l_fontsdesc_lang_tl . . . . .	343, 402, 548,	\mathbin . . . . . 1832
734, 740, 779, 992, 1719, 1724, 1732		\mathchardef . . . . . 1799
\l_fontsdesc_mode_tl . . . . .	738, 781, 1027	\mathclose . . . . . 1806, 1809, 1835, 1837
\l_fontsdesc_nfss_tl . . . . .	697, 704, 711, 720	\mathdollar . . . . . 1839
\l_fontsdesc_optical_size_tl . . . . .	573, 774, 1278, 1293	\mathit . . . . . 95, 1756, 1845, 1853, 1856
\l_fontsdesc_pre_feat_tl . . . . .	541, 700, 714, <u>730</u>	\mathopen . . . . . 1834, 1836
\l_fontsdesc_rawfeatures_sclist . . . . .	541, 700, 714, 748, 755, 813	\mathord . . . . . 1838, 1839
\l_fontsdesc_renderer_tl . . . . .	572, 651, 653, 655, 775, 1019	\mathpunct . . . . . 1802, 1808
\l_fontsdesc_scale_tl . . . . .	173, 698, 712, 749, 1141–1143, 1151	\mathrel . . . . . 1807, 1833
\l_fontsdesc_script_name_tl . . . . .	130, 140, 516, 776, 1037	\mathring . . . . . 1797
\l_fontsdesc_script_tl . . . . .	326, 401,	\mathrm . . . . . 1844, 1851, 1855
444, 460, 547, 733, 739, 777, 966, 992		\mathsf . . . . . 1847, 1858
\l_fontsdesc_size_tl . . . . .	706, 709, 712, 1131	\mathtt . . . . . 1848, 1859
\l_fontsdesc_sizedfont_tl . . . . .	707, 713, 1133	\mddefault . . . . . 551, 590, 593, 600,
\l_fontsdesc_sizefeat_clist . . . . .	694, 705, 770, 1128	1842–1845, 1847, 1848, 1851, 1853
\l_fontsdesc_strnum_int . . . . .	44, 327, 344, 416, 417,	\msg_error:nn . . . . . 12, 54
461, 910, 935, 955, 979, 1717, 1722		\msg_error:nnx . . . . . 55
\l_tmpa_bool . . . . .	564, 566, 568	\msg_info:nn . . . . . 59
\l_tmpa_num . . . . .	1013, 1016	\msg_info:nnx . . . . . 60
\l_tmpa_tl . . . . .	1013, 1019, 1027	\msg_info:nnxx . . . . . 61
\Lambda . . . . .	1824	\msg_new:nn . . . . . 3, 63, 75, 98, 103, 107,
\LaTeX . . . . .	21	111, 116, 121, 126, 132, 136, 142,
\latinencoding . . . . .	206, 209	146, 150, 154, 159, 163, 167, 171, 175
\leavevmode . . . . .	36	\msg_new:nnn . . . . . 68, 79, 87
\let . . . . .	8, 9, 33, 38, 70,	\msg_redirect_module:nn . . . . .
75, 234, 238, 242, 246, 267, 271,		187, 188, 191, 192
284, 503, 504, 508, 510, 675, 748,		\msg_redirect_name:nn . . . . . 1257
750, 789, 902, 1774, 1775, 1800, 1860		\msg_trace:nn . . . . . 62
\listing@line . . . . .	62	\msg_warning:nn . . . . . 56
\listingcont* (environment) . . . . .	58	\msg_warning:nnx . . . . . 57
\loop . . . . .	934, 954, 977	\msg_warning:nnxx . . . . . 58
\lst@visiblespace . . . . .	75	\multi@alias@key . . . . . 312, <u>869</u>
\LuaTeX . . . . .	21	
\luatex_if_engine:T . . . . .	17, 23, 198, 780, 1362	<b>N</b>
\luatex_if_engine:TF . . . . .	8	\newAATfeature . . . . . <u>293</u>
\luatexpostexhyphenchar . . . . .	785	\newcommand . . . . . 662, 693, 742,
\luatexposthyphenchar . . . . .	783	771, 788, 811, 859, 862, 865, 869, 1745
\luatexpreehyphenchar . . . . .	784	\newcount . . . . . 40–43, 526
\luatexprehyphenchar . . . . .	782, 1202, 1219, 1235	\newfontface . . . . . <u>255</u>
\luatexRequireModule . . . . .	10	\newfontfamily . . . . . <u>255</u>
		\newfontfeature . . . . . <u>285</u>
		\newfontlanguage . . . . . <u>333</u> , 1524–1714
		\newfontscript . . . . . <u>316</u> , 1483–1523
		\newICUfeature . . . . . <u>302</u>
		\newif . . . . . 26–39
		\newopentypefeature . . . . . <u>302</u>
		\next . . . . . 1800
		\normalfont . . . . . 219, 224, 229

\not@math@alphabet . . . . .	1741, 1756, 1760, 1764, 1768	\selectfont . . . . . 213, 259, 278, 1742, 1753		
\null . . . . .	36	\setboldmathrm . . . . . 232		
\numexpr . . . . .	892	\setkeys . . . . . 48, 52, 506, 860, 1003, 1009, 1036, 1041, 1258, 1415, 1422		
<b>O</b>				
\Omega . . . . .	1831	\setlength . . . . . 1171, 1175–1177, 1188		
\or . . . . .	643, 648	\setmainfont . . . . . 9, 27, 39, 216, 231		
<b>P</b>				
\PackageInfo . . . . .	755	\SetMathAlphabet . . . . . 1844–1848, 1851–1853, 1855, 1856, 1858, 1859		
\pagestyle . . . . .	16	\setmathrm . . . . . 232		
\par . . . . .	24, 63	\setmathsf . . . . . 232		
\Phi . . . . .	1829	\setmathtt . . . . . 232		
\Pi . . . . .	1826	\setmonofont . . . . . 11, 27, 216		
\pi . . . . .	38	\setromanfont . . . . . 231		
\pm . . . . .	38	\setsansfont . . . . . 10, 27, 216		
\prg_case_str:nnn . . . . .	1136	\SetSymbolFont . . . . . 1787, 1843, 1849		
\prg_new_conditional:Nnn . . . . .		\sfdefault . . . . . 201, 223, 253		
... 355, 362, 379, 392, 411, 426,		\sffamily . . . . . 34		
439, 455, 470, 484, 560, 929, 948, 971		\sidefault . . . . . 682, 688, 1739, 1742, 1757, 1761, 1765, 1769		
\prg_return_false: . . . . .		\Sigma . . . . . 1827		
... 359, 368, 373, 376, 386,		\sishape . . . . . 1739		
389, 403, 405, 408, 418, 420, 423,		\sldefault . . . . . 600, 631, 635, 725, 1761		
431, 433, 436, 447, 449, 452, 462,		\slshape . . . . . 1759, 1760		
464, 467, 476, 478, 481, 490, 492,		\space . . . . . 82, 173, 886, 889, 892		
495, 568, 942, 946, 962, 968, 986, 995		\stepcounter . . . . . 286		
\prg_return_true: . . . . .	357, 370,	\string . . . . . 95, 100		
384, 403, 418, 431, 447, 462, 476,		\strip@pt . . . . . 1151		
490, 568, 942, 946, 962, 968, 986, 995		<b>T</b>		
\ProcessOptions . . . . .	195	\TeX . . . . . 21, 44		
\providecommand . . . . .	1739	\textsf . . . . . 18, 20, 49		
\Psi . . . . .	1830	\textsi . . . . . 1739		
<b>Q</b>				
\q_nil . . . . .	907, 909	\textvisibleinspace . . . . . 20, 28		
<b>R</b>				
\relax . . . . .	36, 327, 344,	\the . . . . . 63, 287, 532, 1181–1183, 1189		
416, 417, 461, 892, 1201, 1202,		\thelisting@line . . . . . 62		
1219, 1227, 1235, 1717, 1722,		\Theta . . . . . 1823		
1733, 1741, 1760, 1764, 1768, 1799		\tilde . . . . . 1791		
\repeat . . . . .	941, 961, 985	\tl_clear:N . . . . .		
\RequirePackage . . . . .	1, 2, 9, 196–198, 203	704, 706, 749, 757–769, 774, 775, 1012		
\rmdefault . . . . .	200, 218, 252	\tl_gset:cx . . . . . 538–540, 543, 545		
\rmfamily . . . . .	1147	\tl_gset:Nx . . . . . 1151		
<b>S</b>				
\scdefault . . . . .	682, 688, 1757, 1761, 1765, 1769	\tl_gset_eq:cN . . . . . 547, 548		
\sclist_put_right:Nn . . . . .	806	\tl_if_empty:NF . . . . . 752		
\scshape . . . . .	33, 1755	\tl_if_empty:NT . . . . . 651, 709, 807		
\section . . . . .	18	\tl_if_empty:nTF . . . . . 831, 846		
		\tl_if_eq:nnTF . . . . . 498, 1255		
		\tl_if_eq:nvTF . . . . . 475, 489		
		\tl_if_eq:xxT . . . . . 722		
		\tl_if_eq:xxTF . . . . . 5		
		\tl_if_head_eq_charcode_p:nN . . . . . 920, 921		
		\tl_if_in:nnT . . . . . 565		
		\tl_put_right:Nx . . . . . 711		

\tl_replace_all_in:Nnn .....	1098	\xetex_or_luatex:nnn .....	20, 199, 638, 730, 929, 948, 970, 1155, 1200, 1249
\tl_replace_all_in:Nnx .....	1096	\XeTeXcharglyph .....	1207, 1226
\tl_set:cn .....	1030–1034	\XeTeXcountvariations .....	645
\tl_set:Nn .....	199–202, 326, 343, 460, 653, 655, 730, 776– 779, 781, 1007, 1037, 1042, 1095, 1131, 1278, 1293, 1719, 1724, 1732	\XeTeXfeaturename .....	883
\tl_set:Nv .....	401, 402, 444, 1019, 1027	\XeTeXfonttype .....	641
\tl_set:Nx .....	352, 697, 1141, 1143	\XeTeXisexclusivefeature .....	885
\tl_set_eq:NN .....	204–206, 208, 209, 218, 223, 228, 707	\XeTeXOTcountfeatures .....	973
\ttdefault .....	202, 228, 254	\XeTeXOTcountlanguages .....	951
\two@digits .....	1425	\XeTeXOTcountsscripts .....	932
\typeout .....	1893, 1894	\XeTeXOTfeaturetag .....	978
<b>U</b>			
\unless ..	294, 303, 521, 536, 576, 587, 665, 678, 680, 794, 812, 884, 888, 894, 899, 1124, 1128, 1164, 1416, 1423	\XeTeXOTlanguagetag .....	955
\updefault .....	551, 579, 582, 1769, 1842–1844, 1846– 1849, 1851, 1852, 1855, 1858, 1859	\XeTeXOTscripttag .....	935
\upshape .....	9, <u>1755</u>	\XeTeXselectorname .....	886, 889, 892
\Upsilon .....	1828	\Xi .....	1825
\use:c .....	364, 398, 400, 446	\XKV@rm ..	509, 510, 710, 752, 753, 1416, 1423
\use:n .....	773	\XKV@tfam ..	113, 118, 123, 128, 1417, 1424
\use:x .....	45, 48, 52, 257, 272, 718, 724	\XKV@tkey .....	113, 118, 123, 128
\use_i:nn .....	16	\xlx@defaulthyphenchar .....	13, 17
\use_ii:nn .....	18	\xxt@visiblespace .....	<u>18</u> , 33, 70, 75
\use_none:n .....	925	\xxt@visiblespace@fallback .....	22, <u>25</u>
\usefont .....	27	\xxt@vprintspaces .....	<u>31</u> , 42, 52, 55, 65
\usepackage .....	6, 7		
\UTFencname .....	204		
<b>V</b>			
\verb .....	24, 27, 29, <u>35</u> , 39, 44–46		
\verb* .....	<u>35</u>		
\verb@eol@error .....	38		
\verbatim* (environment) .....	49		
\verbatim@font .....	39		
\verbatim@line .....	63		
\verbatim@processline .....	61		
\verbatim@start .....	52, 65		
<b>X</b>			
\xdef .....	535, 744, 813		
\xetex_if_engine:F .....	7		
\xetex_if_engine:T ..	1003, 1036, 1041		
\xetex_if_engine:TF .....	15, 20		
\xetex_or_luatex:nn ..	15, 790, 817, 1017, 1025, 1206, 1225, 1276, 1335	\zf@bf .....	577, 581, 609, 618, 757, 1056
		\zf@bf@feat .....	579, 582, 764, 1104
		\zf@bfit .....	608, 622, 759, 1072
		\zf@bfit@feat ..	612, 615, 619, 623, 766, 1112
		\zf@bfs1 .....	628, 634, 761, 1080
		\zf@bfs1@feat .....	631, 635, 768, 1120
		\zf@check@one@char .....	1204, 1243
		\zf@DeclareFontShape ..	676, 681, 687, <u>693</u>
		\zf@default@options .....	..... 165, 266, 267, 271, 507, 539
		\zf@define@feature@option .....	..... 300, 309, 859, 1310– 1333, 1344–1352, 1354–1361,

1363, 1364, 1367–1380, 1382–	\zf@mmfalse .....
1392, 1394–1398, 1400, 1402–	\zf@mmtrue .....
1408, 1410–1413, 1430–1440,	\zf@nobffalse .....
1442–1448, 1450–1457, 1459–1471	\zf@nobftrue .....
\zf@define@font@feature .....	\zf@noitfalse .....
..... 295, 304, <u>859</u> , 1309, 1343,	\zf@noittrue .....
1353, 1366, 1381, 1393, 1401,	\zf@noscffalse .....
1409, 1429, 1441, 1449, 1458, 1472	\zf@nosctrue .....
\zf@enc .....	\zf@package@euler@loadedfalse ...
199, 203–206, 208,	\zf@package@euler@loadedtrue ...
209, 549, 719, 725, 1842–1849,	\zf@rmboldmaths .....
1851–1853, 1855, 1856, 1858, 1859	\zf@rmmath .....
\zf@family 213, 218, 223, 228, 234, 238,	234, 252, 1842–1846, 1849, 1855, 1856
242, 246, 259, 278, 398, 400–402,	\zf@sc .....
444, 446, 475, 489, 535, 536, 538–	677, 686, 762, 1090
540, 543, 545, 547–549, 719, 725, 726	\zf@sc@feat .....
\zf@family@long .. 503, 521, 530, 535, 744	682, 688, 769, 1124
\zf@firsttimefalse .....	\zf@sfmaths .....
\zf@firsttimetrue .....	242, 253, 1847, 1858
\zf@font@feat .....	\zf@s1 .....
... 510, 519, 551, 579, 582, 590,	598, 599, 629, 630, 760, 1076
593, 600, 612, 615, 619, 623, 631, 635	\zf@s1@feat .....
\zf@font@warning .....	600, 767, 1116
\zf@fontname .....	\zf@smallcaps .....
. 77, 109, 114, 119, 124, 129, 134,	680, 681, 789, 795, 799, 803
139, 173, 502–504, 508, 541, 550,	\zf@tfmfalse .....
578, 589, 611, 674, 686, 699, 707, 1096	640
\zf@graphitefalse .....	\zf@tfmtrue .....
640	642
\zf@icufalse .....	\zf@ttmaths .....
640, 772	246, 254, 1848, 1859
\zf@icutrue .....	\zf@up .....
649, 660	504, 508, 511, 513, 1046
\zf@it .....	\zf@up@feat .....
588, 592, 610, 614, 758, 1067	551, 763, 1100
\zf@it@feat .....	\zf@update@family .....
590, 593, 765, 1108	289, 325, 342, <u>742</u> ,
\zf@make@font@shapes .....	840, 852, 1015, 1038, 1043, 1047,
..... 550, 578, 581, 589, 592,	1053, 1057, 1064, 1068, 1073,
599, 611, 614, 618, 622, 630, 634, 662	1077, 1081, 1087, 1091, 1101,
\zf@make@smallcaps .....	1105, 1109, 1113, 1117, 1121,
679, <u>788</u>	1125, 1129, 1142, 1163, 1187,
\zf@math .....	1192, 1196, 1245, 1252, 1264,
<u>1771</u> , 1887	1268, 1272, 1279, 1282, 1294,
\zf@math@eulertrue .....	1298, 1302, 1306, 1336, 1339,
1778	1476, 1479, 1718, 1723, 1731, 1736
\zf@math@lucidatrue .....	\zf@update@eff .....
1783–1785	290, <u>811</u> ,
\zf@math@maybe .....	841, 853, 1193, 1246, 1253, 1265,
<u>1861</u>	1269, 1273, 1283, 1299, 1303,
\zf@merge@shape .....	1307, 1337, 1340, 1477, 1480, 1737
..... <u>1745</u> , 1757, 1761, 1765, 1769	\zf@wordspace@parse .....
	1165, <u>1168</u>