

The fontspec package

Font selection for X_YL^AT_EX and LuaL^AT_EX

WILL ROBERTSON and KHALED HOSNY
will.robertson@latex-project.org

2016/02/01 v2.5a

Contents

I	Getting started	2
1	History	2
2	Introduction	2
2.1	Acknowledgements	2
3	Package loading and options	3
3.1	Maths fonts adjustments	4
3.2	Configuration	4
3.3	Warnings	4
II	General font selection	4
4	Font selection	5
4.1	By font name	5
4.2	By file name	6
5	Commands to select font families	7
5.1	More control over font shape selection	8
5.2	Specifically choosing the NFSS family	9
5.3	Choosing additional NFSS font faces	10
5.4	Math(s) fonts	11
6	Miscellaneous font selecting details	12
7	Selecting font features	14
7.1	Default settings	14
7.2	Default settings from a file	15
7.3	Changing the currently selected features	16

7.4	Priority of feature selection	16
7.5	Different features for different font shapes	17
7.6	Different features for different font sizes	17
8	Font independent options	19
8.1	Colour	19
8.2	Scale	20
8.3	Interword space	21
8.4	Post-punctuation space	21
8.5	The hyphenation character	22
8.6	Optical font sizes	22
III	OpenType	23
9	Introduction	23
9.1	How to select font features	24
9.2	How do I know what font features are supported by my fonts?	24
10	Complete listing of OpenType font features	26
10.1	Ligatures	26
10.2	Letters	26
10.3	Numbers	27
10.4	Contextuals	28
10.5	Vertical Position	29
10.6	Fractions	30
10.7	Stylistic Set variations	30
10.8	Character Variants	31
10.9	Alternates	32
10.10	Style	32
10.11	Diacritics	34
10.12	Kerning	34
10.13	Font transformations	34
10.14	Annotation	35
10.15	CJK shape	35
10.16	Character width	37
10.17	Vertical typesetting	37
10.18	OpenType scripts and languages	37
IV	Lua\TeX-only font features	39
11	OpenType font feature files	41
V	Fonts and features with X\TeX	41
12	X\TeX-only font features	42
12.1	Mapping	42

12.2	Letter spacing	42
12.3	Different font technologies: AAT and OpenType	43
12.4	Optical font sizes	43
13	Mac OS X's AAT fonts	44
13.1	Ligatures	44
13.2	Letters	44
13.3	Numbers	44
13.4	Contextuals	45
13.5	Vertical position	45
13.6	Fractions	46
13.7	Variants	46
13.8	Alternates	46
13.9	Style	47
13.10	CJK shape	47
13.11	Character width	47
13.12	Vertical typesetting	47
13.13	Diacritics	48
13.14	Annotation	48
VI	Programming interface	48
14	Defining new features	49
15	Going behind fontspec's back	50
16	Renaming existing features & options	50
17	Programming details	51
17.1	Variables	51
17.2	Functions for loading new fonts and families	51
17.3	Functions for querying font families	51
VII	The 'improvement' of L^AT_EX 2_ε and other packages	52
18	Verbatim	52
19	Discretionary hyphenation: \-	53
20	Commands for old-style and lining numbers	53
VIII	Implementation	53
21	Loading	53
22	Declaration of variables	55

23	Opening code	56
23.1	Package options	56
23.2	Encodings	56
24	expl3 interface for font loading	57
25	User commands	58
26	Programmer’s interface	65
27	Internals	70
27.1	Internal macros	70
28	Font loading (keyval) definitions	89
29	Selecting maths fonts	115
30	Closing code	119
30.1	Compatibility	119
30.2	Finishing up	119
31	Lua module	119
32	Patching code	121
32.1	Italic small caps and so on	121
32.2	Emphasis	122
32.3	\-	122
32.4	Verbatims	123
32.5	\oldstylenums	125
33	Error/warning/info messages	125
33.1	Errors	125
33.2	Warnings	127

Part I

Getting started

1 History

This package began life as a \LaTeX interface to select system-installed Mac OS X fonts in Jonathan Kew's $X_{\text{}}\TeX$, the first widely-used Unicode extension to \TeX . Over time, $X_{\text{}}\TeX$ was extended to support OpenType fonts and then was ported into a cross-platform program to run also on Windows and Linux.

More recently, $\text{Lua}\TeX$ is fast becoming the \TeX engine of the day; it supports Unicode encodings and OpenType fonts and opens up the internals of \TeX via the Lua programming language. Hans Hagen's $\text{Con}\TeX\text{t Mk. IV}$ is a re-write of his powerful typesetting system, taking full advantage of $\text{Lua}\TeX$'s features including font support; a kernel of his work in this area has been extracted to be useful for other \TeX macro systems as well, and this has enabled `fontspec` to be adapted for \LaTeX when run with the $\text{Lua}\TeX$ engine.

2 Introduction

The `fontspec` package allows users of either $X_{\text{}}\TeX$ or $\text{Lua}\TeX$ to load OpenType fonts in a \LaTeX document. No font installation is necessary, and font features can be selected and used as desired throughout the document.

Without `fontspec`, it is necessary to write cumbersome font definition files for \LaTeX , since \LaTeX 's font selection scheme (known as the 'NFSS') has a lot going on behind the scenes to allow easy commands like `\emph` or `\bfseries`. With an uncountable number of fonts now available for use, however, it becomes less desirable to have to write these font definition (`.fd`) files for every font one wishes to use.

Because `fontspec` is designed to work in a variety of modes, this user documentation is split into separate sections that are designed to be relatively independent. Nonetheless, the basic functionality all behaves in the same way, so previous users of `fontspec` under $X_{\text{}}\TeX$ should have little or no difficulty switching over to $\text{Lua}\TeX$.

This manual can get rather in-depth, as there are a lot of details to cover. See the documents `fontspec-example.tex` for a complete minimal example to get started quickly.

2.1 Acknowledgements

This package could not have been possible without the early and continued support the author of $X_{\text{}}\TeX$, Jonathan Kew. When I started this package, he steered me many times in the right direction.

I've had great feedback over the years on feature requests, documentation queries, bug reports, font suggestions, and so on from lots of people all around the world. Many thanks to you all.

Thanks to David Perry and Markus Böhning for numerous documentation improvements and David Perry again for contributing the text for one of the sections of this manual.

Special thanks to Khaled Hosny, who was the driving force behind the support for Lua \LaTeX , ultimately leading to version 2.0 of the package.

3 Package loading and options

For basic use, no package options are required:

```
\usepackage{fontspec}
```

Package options will be introduced below; some preliminary details are discussed first.

UPDATE!

Font encodings The 2016 release of fontspec initiates some changes for font encodings and the loading of xunicode.

A new package option, tuenc, which is selected by default, switches the NFSS font encoding to TU. TU is a new Unicode font encoding, intended for both X \TeX and Lua \TeX engines, and automatically contains support for symbols covered by \LaTeX 's traditional T1 and TS1 font encodings (for example, $\%$, \textbullet , $\"u$, and so on). As a result, with this package option, Ross Moore's xunicode package is **not** loaded.

The old behaviour can be achieved by loading the euenc package option. This selects the EU1 or EU2 encoding (X \TeX /Lua \TeX , resp.) and loads the xunicode package. Package authors and users who have referred explicitly to the encoding names EU1 or EU2 should update their code or documents. (See internal variable names described in [Section 17 on page 51](#) for how to do this properly.)

While fontspec is providing the TU encoding, its interface should be considered EXPERIMENTAL; feedback welcome. Once TU is incorporated into the $\LaTeX 2_{\epsilon}$ kernel directly (later in 2016), it will be considered stable.

Lua \TeX users only In order to load fonts by their name rather than by their file-name (e.g., 'Latin Modern Roman' instead of 'ec-lmr10'), you may need to run the script luaotfload-tool, which is distributed with the luaotfload package. Note that if you do not execute this script beforehand, the first time you attempt to typeset the process will pause for (up to) several minutes. (But only the first time.) Please see the luaotfload documentation for more information.

babel *The babel package is only supported for certain languages.* Especially Vietnamese, Greek, and Hebrew at least might not work correctly, as far as I can tell. There's a better chance with Cyrillic and Latin-based languages, however—fontspec ensures at least that fonts should load correctly. The polyglossia package is recommended instead as a modern replacement for babel.

3.1 Maths fonts adjustments

By default, fontspec adjusts L^AT_EX's default maths setup in order to maintain the correct Computer Modern symbols when the roman font changes. However, it will attempt to avoid doing this if another maths font package is loaded (such as mathpazo or the unicode-math package).

If you find that fontspec is incorrectly changing the maths font when it shouldn't be, apply the no-math package option to manually suppress its selection of the maths fonts.

3.2 Configuration

If you wish to customise any part of the fontspec interface, this should be done by creating your own fontspec.cfg file, which will be automatically loaded if it is found by X_YL^AT_EX or Lua^AT_EX. A fontspec.cfg file is distributed with fontspec with a small number of defaults set up within it.

To customise fontspec to your liking, use the standard .cfg file as a starting point or write your own from scratch, then either place it in the same folder as the main document for isolated cases, or in a location that X_YL^AT_EX or Lua^AT_EX searches by default; e.g. in Mac^AT_EX: ~/Library/texmf/tex/latex/.

The package option no-config will suppress the loading of the fontspec.cfg file under all circumstances.

3.3 Warnings

This package can give some warnings that can be harmless if you know what you're doing. Use the quiet package option to write these warnings to the transcript (.log) file instead.

Use the silent package option to completely suppress these warnings if you don't even want the .log file cluttered up.

Part II

General font selection

This section concerns the variety of commands that can be used to select fonts.

```
\fontspec{<font name>}[<font features>]  
\setmainfont{<font name>}[<font features>]  
\setsansfont{<font name>}[<font features>]  
\setmonofont{<font name>}[<font features>]  
\newfontfamily<cmd>{<font name>}[<font features>]
```

These are the main font-selecting commands of this package. The \fontspec command selects a font for one-time use; all others should be used to define the standard fonts used in a document, as shown in Example 1. Here, the scales of the fonts have been chosen to equalise their lowercase letter heights. The Scale font

Example 1: Loading the default, sans serif, and monospaced fonts.

```
\setmainfont{texgyrebonum-regular.otf}
\setsansfont{lmsans10-regular.otf}[Scale=MatchLowercase]
\setmonofont{Inconsolata.otf}[Scale=MatchLowercase]
```

```
Pack my box with five dozen liquor jugs \rmfamily Pack my box with five dozen liquor jugs\par
Pack my box with five dozen liquor jugs \sffamily Pack my box with five dozen liquor jugs\par
Pack my box with five dozen liquor jugs \ttfamily Pack my box with five dozen liquor jugs
```

feature will be discussed further in [Section 8 on page 19](#), including methods for automatic scaling.

The font features argument accepts comma separated $\langle font\ feature \rangle = \langle option \rangle$ lists; these are described in later:

- For general font features, see [Section 8 on page 19](#)
- For OpenType fonts, see [Part III on page 23](#)
- For \XeTeX -only general font features, see [Part V on page 42](#)
- For \LuaTeX -only general font features, see [Part IV on page 41](#)
- For features for AAT fonts in \XeTeX , see [Section 13 on page 44](#)

4 Font selection

In both \LuaTeX and \XeTeX , fonts can be selected either by ‘font name’ or by ‘file name’, but there are some differences in how each engine finds and selects fonts — don’t be too surprised if a font invocation in one engine needs correction to work in the other.

4.1 By font name

Fonts known to \LuaTeX or \XeTeX may be loaded by their standard names as you’d speak them out loud, such as *Times New Roman* or *Adobe Garamond*. ‘Known to’ in this case generally means ‘exists in a standard fonts location’ such as \sim /Library/Fonts on Mac OS X, or C:\Windows\Fonts on Windows. In \LuaTeX , fonts found in the TEXMF tree can also be loaded by name.

The simplest example might be something like

```
\setmainfont{Cambria}[ ... ]
```

in which the bold and italic fonts will be found automatically (if they exist) and are immediately accessible with the usual \textit and \textbf commands.

The ‘font name’ can be found in various ways, such as by looking in the name listed in a application like *Font Book* on Mac OS X. Alternatively, \TeX Live contains the `otfinfo` command line program, which can query this information; for example:

```
otfinfo -a `kpsewhich lmroman10-regular.otf`
```

results in ‘LM Roman 10’.

4.2 By file name

X_ƎT_ƎX and LuaT_ƎX also allow fonts to be loaded by file name instead of font name. When you have a very large collection of fonts, you will sometimes not wish to have them all installed in your system’s font directories. In this case, it is more convenient to load them from a different location on your disk. This technique is also necessary in X_ƎT_ƎX when loading OpenType fonts that are present within your T_ƎX distribution, such as /usr/local/texlive/2013/texmf-dist/fonts/opentype/public. Fonts in such locations are visible to X_ƎT_ƎX but cannot be loaded by font name, only file name; LuaT_ƎX does not have this restriction.

When selecting fonts by file name, any font that can be found in the default search paths may be used directly (including in the current directory) without having to explicitly define the location of the font file on disk.

Fonts selected by filename must include bold and italic variants explicitly.

```
\setmainfont{texgyrepagella-regular.otf}[
  BoldFont      = texgyrepagella-bold.otf ,
  ItalicFont     = texgyrepagella-italic.otf ,
  BoldItalicFont = texgyrepagella-bolditalic.otf ]
```

fontspec knows that the font is to be selected by file name by the presence of the ‘.otf’ extension. An alternative is to specify the extension separately, as shown following:

```
\setmainfont{texgyrepagella-regular}[
  Extension      = .otf ,
  BoldFont       = texgyrepagella-bold ,
  ... ]
```

If desired, an abbreviation can be applied to the font names based on the mandatory ‘font name’ argument:

```
\setmainfont{texgyrepagella}[
  Extension      = .otf ,
  UprightFont    = *-regular ,
  BoldFont       = *-bold ,
  ... ]
```

In this case ‘texgyrepagella’ is no longer the name of an actual font, but is used to construct the font names for each shape; the * is replaced by ‘texgyrepagella’. Note in this case that UprightFont is required for constructing the font name of the normal font to use.

To load a font that is not in one of the default search paths, its location in the filesystem must be specified with the Path feature:

```
\setmainfont{texgyrepagella}[
  Path           = /Users/will/Fonts/ ,
```

Example 2: Defining new font families.

This is a <i>note</i> .	<code>\newfontfamily\notefont{Kurier}</code> <code>\notefont This is a \emph{note}.</code>
-------------------------	---

```
UprightFont = *-regular ,
BoldFont    = *-bold ,
... ]
```

Note that X_YTeX and Lua_YTeX are able to load the font without giving an extension, but fontspec must know to search for the file; this can be indicated by using the Path option without an argument:

```
\setmainfont{texgyrepagella-regular}[
  Path, BoldFont = texgyrepagella-bold,
... ]
```

In previous versions of the package, the alias ExternalLocation was documented for this purpose, but this is now deprecated and may be removed in the future.

5 Commands to select font families

<code>\newfontfamily\<font-switch>\{font name\}[\<font features\]]</code> <code>\newfontface\<font-switch>\{font name\}[\<font features\]]</code>
--

For cases when a specific font with a specific feature set is going to be re-used many times in a document, it is inefficient to keep calling `\fontspec` for every use. While the `\fontspec` command does not define a new font instance after the first call, the feature options must still be parsed and processed.

`\newfontfamily` For this reason, new commands can be created for loading a particular font family with the `\newfontfamily` command, demonstrated in Example 2. This macro should be used to create commands that would be used in the same way as `\rmfamily`, for example. If you would like to create a command that only changes the font inside its argument (i.e., the same behaviour as `\emph`) define it using regular L^AT_EX commands:

```
\newcommand\textnote[1]{\{\notefont #1\}}
\textnote{This is a note.}
```

Note that the double braces are intentional; the inner pair are used to delimit the scope of the font change.

`\newfontface` Sometimes only a specific font face is desired, without accompanying italic or bold variants being automatically selected. This is common when selecting a fancy italic font, say, that has swash features unavailable in the upright forms. `\newfontface` is used for this purpose, shown in Example 3, which is repeated in [Section 13.4 on page 45](#).

Comment for advanced users: The commands defined by `\newfontface` and `\newfontfamily` include their encoding information, so even if the document is

Example 3: Defining a single font face.

```
\newfontface\fancy{Hoefler Text Italic}%
  [Contextuals={WordInitial,WordFinal}]
\fancy where is all the vegemite
% \emph, \textbf, etc., all don't work
```

Example 4: Explicit selection of the bold font.

```
\fontspec{Helvetica Neue UltraLight}%
[BoldFont={Helvetica Neue}]
Helvetica Neue UltraLight
Helvetica Neue UltraLight Italic
Helvetica Neue
{\itshape Helvetica Neue UltraLight Italic} \\
Helvetica Neue Italic
{\bfseries Helvetica Neue } \\
{\bfseries\itshape Helvetica Neue Italic} \\
```

set to use a legacy T_EX encoding, such commands will still work correctly. For example,

```
\documentclass{article}
\usepackage{fontspec}
\newfontfamily\unicodfont{Lucida Grande}
\usepackage{mathpazo}
\usepackage[T1]{fontenc}
\begin{document}
A legacy \TeX\ font. {\unicodfont A unicode font.}
\end{document}
```

5.1 More control over font shape selection

<pre>BoldFont = <i></i> ItalicFont = <i></i> BoldItalicFont = <i></i> SlantedFont = <i></i> BoldSlantedFont = <i></i> SmallCapsFont = <i></i></pre>

The automatic bold, italic, and bold italic font selections will not be adequate for the needs of every font: while some fonts mayn't even have bold or italic shapes, in which case a skilled (or lucky) designer may be able to chose well-matching accompanying shapes from a different font altogether, others can have a range of bold and italic fonts to chose among. The `BoldFont` and `ItalicFont` features are provided for these situations. If only one of these is used, the bold italic font is requested as the default from the *new* font. See Example 4.

If a bold italic shape is not defined, or you want to specify *both* custom bold and italic shapes, the `BoldItalicFont` feature is provided.

5.1.1 Small caps and slanted font shapes

When a font family has both slanted *and* italic shapes, these may be specified separately using the analogous features `SlantedFont` and `BoldSlantedFont`. Without these, however, the \LaTeX font switches for slanted (`\textsl`, `\slshape`) will default to the italic shape.

Pre-OpenType, it was common for font families to be distributed with small caps glyphs in separate fonts, due to the limitations on the number of glyphs allowed in the PostScript Type 1 format. Such fonts may be used by declaring the `SmallCapsFont` of the family you are specifying:

```
\setmainfont{Minion MM Roman}[
  SmallCapsFont={Minion MM Small Caps & Oldstyle Figures}
]
Roman 123 \ \textsc{Small caps 456}
```

In fact, you should specify the small caps font for each individual bold and italic shape as in

```
\setmainfont{ <upright> }[
  UprightFeatures = { SmallCapsFont={ <sc> } } ,
  BoldFeatures    = { SmallCapsFont={ <bf sc> } } ,
  ItalicFeatures  = { SmallCapsFont={ <it sc> } } ,
  BoldItalicFeatures = { SmallCapsFont={ <bf it sc> } } ,
]
Roman 123 \ \textsc{Small caps 456}
```

For most modern fonts that have small caps as a font feature, this level of control isn't generally necessary.

All of the bold, italic, and small caps fonts can be loaded with different font features from the main font. See [Section 7.5](#) for details. When an OpenType font is selected for `SmallCapsFont`, the small caps font feature is *not* automatically enabled. In this case, users should write instead, if necessary,

```
\setmainfont{...}[
  SmallCapsFont={...},
  SmallCapsFeatures={Letters=SmallCaps},
]
```

5.2 Specifically choosing the NFSS family

In \LaTeX 's NFSS, font families are defined with names such as 'ppl' (Palatino), 'lmr' (Latin Modern Roman), and so on, which are selected with the `\fontfamily` command:

```
\fontfamily{ppl}\selectfont
```

In `fontspec`, the family names are auto-generated based on the `fontname` of the font; for example, writing `\fontspec{Times New Roman}` for the first time would generate an internal font family name of 'TimesNewRoman(1)'. Please note that should not rely on the name that is generated.

In certain cases it is desirable to be able to choose this internal font family name so it can be re-used elsewhere for interacting with other packages that use the L^AT_EX's font selection interface; an example might be

```
\usepackage{fancyvrb}
\fvset{fontfamily=myverbatimfont}
```

To select a font for use in this way in fontspec use the NFSSFamily feature:¹

```
\newfontfamily\verbatimfont[NFSSFamily=myverbatimfont]{Inconsolata}
```

It is then possible to write commands such as:

```
\fontfamily{myverbatimfont}\selectfont
```

which is essentially the same as writing `\verbatimfont`, or to go back to the original example:

```
\fvset{fontfamily=myverbatimfont}
```

Only use this feature when necessary; the in-built font switching commands that fontspec generates (such as `\verbatimfont` in the example above) are recommended in all other cases.

If you don't wish to explicitly set the NFSS family but you would like to know what it is, an alternative mechanism for package writers is introduced as part of the fontspec programming interface; see the function `\fontspec_set_family:Nnn` for details ([Section 17 on page 51](#)).

5.3 Choosing additional NFSS font faces

L^AT_EX's font selection scheme (NFSS) is more flexible than the fontspec interface discussed up until this point. It assigns to each font face a *family* (discussed above), a *series* such as bold or light or condensed, and a *shape* such as italic or slanted or small caps. The fontspec features such as `BoldFont` and so on all assign faces for the default series and shapes of the NFSS, but it's not uncommon to have font families that have multiple weights and shapes and so on.

If you set up a regular font family with the 'standard four' (upright, bold, italic, and bold italic) shapes and then want to use, say, a light font for a certain document element, many users will be perfectly happy to use `\newfontface\switch` and use the resulting font `\switch`. In other cases, however, it is more convenient or even necessary to load additional fonts using additional NFSS specifiers.

<pre>FontFace = {<series>}{<shape>} { Font = , <features> } FontFace = {<series>}{<shape>}{}</pre>

The font thus specified will inherit the font features of the main font, with optional additional `<features>` as requested. (Note that the optional `{<features>}` argument is still surrounded with curly braces.) Multiple `FontFace` commands may be used in a single declaration to specify multiple fonts. As an example:

¹Thanks to Luca Fascione for the example and motivation for finally implementing this feature.

```

\setmainfont{font1.otf}[
  FontFace = {c}{\updefault}{ font2.otf } ,
  FontFace = {c}{m}{ Font = font3.otf , Color = red }
]

```

Writing `\fontseries{c}\selectfont` will result in `font2` being selected, which then followed by `\fontshape{m}\selectfont` will result in `font3` being selected (in red). A font face that is defined in terms of a different series but an upright shape (`\updefault`, as shown above) will attempt to find a matching small caps feature and define that face as well. Conversely, a font face defined in terms of a non-standard font shape will not.

There are some standards for choosing shape and series codes; the $\LaTeX 2_{\epsilon}$ font selection guide² lists series `m` for medium, `b` for bold, `bx` for bold extended, `sb` for semi-bold, and `c` for condensed. A far more comprehensive listing is included in Appendix A of Philipp Lehman's 'The Font Installation Guide'³ covering 14 separate weights and 12 separate widths.

The `FontFace` command also interacts properly with the `SizeFeatures` command as follows: (nonsense set of font selection choices)

```

FontFace = {c}{n}{
  Font = Times ,
  SizeFeatures = {
    { Size = -10 , Font = Georgia } ,
    { Size = 10-15} , % default "Font = Times"
    { Size = 15- , Font = Cochin } ,
  },
},

```

Note that if the first Font feature is omitted then each size needs its own inner Font declaration.

5.4 Math(s) fonts

When `\setmainfont`, `\setsansfont` and `\setmonofont` are used in the preamble, they also define the fonts to be used in maths mode inside the `\mathrm`-type commands. This only occurs in the preamble because \LaTeX freezes the maths fonts after this stage of the processing. The `fontspec` package must also be loaded after any maths font packages (*e.g.*, `euler`) to be successful. (Actually, it is *only* `euler` that is the problem.⁴)

Note that `fontspec` will not change the font for general mathematics; only the upright and bold shapes will be affected. To change the font used for the mathematical symbols, see either the `mathspec` package or the `unicode-math` package.

Note that you may find that loading some maths packages won't be as smooth as you expect since `fontspec` (and \XeTeX in general) breaks many of the assumptions of \TeX as to where maths characters and accents can be found. Contact me

²`texdoc fntguide`

³`texdoc fontinstallationguide`

⁴Speaking of `euler`, if you want to use its `[mathbf]` option, it won't work, and you'll need to put this after `fontspec` is loaded instead: `\AtBeginDocument{\DeclareMathAlphabet\mathbf{U}{eur}{b}{n}}`

if you have troubles, but I can't guarantee to be able to fix any incompatibilities. The Lucida and Euler maths fonts should be fine; for all others keep an eye out for problems.

```
\setmathrm{<font name>}[<font features>]
\setmathsf{<font name>}[<font features>]
\setmathtt{<font name>}[<font features>]
\setboldmathrm{<font name>}[<font features>]
```

However, the default text fonts may not necessarily be the ones you wish to use when typesetting maths (especially with the use of fancy ligatures and so on). For this reason, you may optionally use the commands above (in the same way as our other `\fontspec`-like commands) to explicitly state which fonts to use inside such commands as `\mathrm`. Additionally, the `\setboldmathrm` command allows you define the font used for `\mathrm` when in bold maths mode (which is activated with, among others, `\boldmath`).

For example, if you were using Optima with the Euler maths font, you might have this in your preamble:

```
\usepackage{mathpazo}
\usepackage{fontspec}
\setmainfont{Optima}
\setmathrm{Optima}
\setboldmathrm[BoldFont={Optima ExtraBlack}]{Optima Bold}
```

These commands are compatible with the `unicode-math` package. Having said that, `unicode-math` also defines a more general way of defining fonts to use in maths mode, so you can ignore this subsection if you're already using that package.

6 Miscellaneous font selecting details

The optional argument — from v2.4 For the first decade of `fontspec`'s life, optional font features were selected with a bracketed argument before the font name, as in:

```
\setmainfont[
  lots and lots ,
  and more and more ,
  an excessive number really ,
  of font features could go here
]{myfont.otf}
```

This always looked like ugly syntax to me, because the most important detail — the name of the font — was tucked away at the end. The order of these arguments has now been reversed:

```
\setmainfont{myfont.otf}[
  lots and lots ,
  and more and more ,
  an excessive number really ,
```

```
of font features could go here  
]
```

I hope this doesn't cause any problems.

1. Backwards compatibility has been preserved, so either input method works. (In fact, in the next version of fontspec you will be able to write

```
\fontspec[Ligatures=Rare]{myfont.otf}[Color=red]
```

if you really felt like it and both sets of features would be applied.)

2. Following standard xparse behaviour, there must be no space before the opening bracket; writing

```
\fontspec{myfont.otf}_[Color=red]
```

will result in `[Color=red]` not being recognised an argument and therefore it will be typeset as text. When breaking over lines, write either of:

```
\fontspec{myfont.otf}%           \fontspec{myfont.otf}[  
[Color=red]                       Color=Red]
```

Spaces `\fontspec` and `\addfontfeatures` ignore trailing spaces as if it were a 'naked' control sequence; e.g., 'M. `\fontspec{...}` N' and 'M. `\fontspec{...}`N' are the same.

Italic small caps Note that this package redefines the `\itshape`, `\slshape`, and `\scshape` commands in order to allow them to select italic small caps in conjunction. With these changes, writing `\itshape\scshape` will lead to italic small caps, and `\upshape` subsequently then moves back to small caps only. `\upshape` again returns from small caps to upright regular. (And similarly for `\slshape`. In addition, once italic small caps are selected then `\slshape` will switch to slanted small caps, and vice versa.)

Emphasis and nested emphasis $\LaTeX 2_\epsilon$ allows you to specify the behaviour of `\emph` nested within `\emph` by setting the `\eminnershape` command. For example, `\renewcommand\eminnershape{\upshape\scshape}` will produce small caps within `\emph{\emph{...}}`.

The `fontspec` package takes this idea one step further to allow arbitrary font changes (e.g., boldness) and arbitrary levels of nesting within emphasis. This is performed using the `\emfontdeclare` command, which takes a comma-separated list of font switches corresponding to increasing levels of emphasis. Two examples:

1. `\emfontdeclare{\itshape,\upshape\scshape,\itshape}` will lead to 'italics', 'small caps', then 'italic small caps' as the level of emphasis increases, as long as italic small caps are defined for the font. Note that `\upshape` is required because the font changes are cascading.
2. `\emfontdeclare{\bfseries,\fontseries{h}\selectfont,\fontseries{x}\selectfont}` could lead to (if fonts are set up correctly) 'bold', 'heavy', and 'extra bold'.

Example 5: A demonstration of the `\defaultfontfeatures` command.

```
\fontspec{texgyreadventor-regular.otf}
Some default text 0123456789 \
\defaultfontfeatures{
  Numbers=OldStyle, Color=888888
}
\fontspec{texgyreadventor-regular.otf}
Now grey, with old-style figures:
0123456789
```

Some default text 0123456789
Now grey, with old-style figures: 0123456789

7 Selecting font features

The commands discussed so far such as `\fontspec` each take an optional argument for accessing the font features of the requested font. Commands are provided to set default features to be applied for all fonts, and even to change the features that a font is presently loaded with. Different font shapes can be loaded with separate features, and different features can even be selected for different sizes that the font appears in. This section discusses these options.

7.1 Default settings

```
\defaultfontfeatures{<font features>}
```

It is sometimes useful to define font features that are applied to every subsequent font selection command. This may be defined with the `\defaultfontfeatures` command, shown in Example 5. New calls of `\defaultfontfeatures` overwrite previous ones, and defaults can be reset by calling the command with an empty argument.

```
\defaultfontfeatures[<font name>]{<font features>}
```

Default font features can be specified on a per-font and per-face basis by using the optional argument to `\defaultfontfeatures` as shown.⁵

```
\defaultfontfeatures[texgyreadventor-regular.otf]{Color=blue}
\setmainfont{texgyreadventor-regular.otf}% will be blue
```

Multiple fonts may be affected by using a comma separated list of font names.

```
\defaultfontfeatures[<font-switch>]{<font features>}
```

New in v2.4. Defaults can also be applied to symbolic families such as those created with the `\newfontfamily` command and for `\rmfamily`, `\sffamily`, and `\ttfamily`:

```
\defaultfontfeatures[\rmfamily,\sffamily]{Ligatures=TeX}
\setmainfont{texgyreadventor-regular.otf}% will use standard TeX ligatures
```

⁵Internally, `` has all spaces removed and is converted to lowercase.

The line above to set T_EX-like ligatures is now activated by *default* in `fontspec.cfg`. To reset default font features, simply call the command with an empty argument:

```
\defaultfontfeatures[\rmfamily,\sffamily]{}
\setmainfont{texgyreadventor-regular.otf}% will no longer use standard TeX ligatures
```

```
\defaultfontfeatures+{<font features>}
\defaultfontfeatures+[<font name>]{<font features>}
```

New in v2.4. Using the + form of the command appends the ** to any already-selected defaults.

7.2 Default settings from a file

In addition to the defaults that may be specified in the document as described above, when a font is first loaded, a configuration file is searched for with the name '*<fontname>.fontspec*'.⁶

The contents of this file can be used to specify default font features without having to have this information present within each document. *<fontname>* is stripped of spaces and file extensions are omitted; for example, the line above for T_EX Gyre Adventor could be placed in a file called `TeXGyreAdventor.fontspec`, or for specifying options for `texgyreadventor-regular.otf` (when loading by filename), the configuration file would be `texgyreadventor-regular.fontspec`. (N.B. the letter-case of the names should match.)

This mechanism can be used to define custom names or aliases for your font collections. If you create a file `MyCharis.fontspec` containing, say,

```
\defaultfontfeatures[My Charis]
{
  Extension = .ttf ,
  UprightFont = CharisSILR,
  BoldFont = CharisSILB,
  ItalicFont = CharisSILI,
  BoldItalicFont = CharisSILBI,
  % <any other desired options>
}
```

you can load that custom family with `\fontspec{My Charis}` and similar. The optional argument to `\defaultfontfeatures` must match that requested by the font loading command (`\fontspec`, etc.), else the options won't take effect.

Finally, note that options for font faces can also be defined in this way. To continue the example above, here we colour the different faces:

```
\defaultfontfeatures[CharisSILR]{Color=blue}
\defaultfontfeatures[CharisSILB]{Color=red}
```

And such configuration lines can be stored either inline inside `My Charis.fontspec` or within their own `.fontspec` files; in this way, `fontspec` is designed to handle 'nested' configuration options as well.

⁶Located in the current folder or within a standard `texmf` location.

Example 6: A demonstration of the `\addfontfeatures` command. Note the caveat listed in the text regarding such usage.

```

\fontspec{texgyreadventor-regular.otf}%
  [Numbers={Proportional,OldStyle}]
`In 1842, 999 people sailed 97 miles in
  13 boats. In 1923, 111 people sailed 54
  miles in 56 boats.' \bigskip

`In 1842, 999 people sailed 97 miles in 13 boats. In
1923, 111 people sailed 54 miles in 56 boats.`
\addfontfeatures{Numbers={Monospaced,Lining}}
\begin{tabular}{@{} cccc @{}}
  Year & People & Miles & Boats \\
\hline
1842 & 999 & 75 & 13 \\
1923 & 111 & 54 & 56
\end{tabular}

```

7.3 Changing the currently selected features

```
\addfontfeatures{<font features>}
```

This command allows font features to be changed without knowing what features are currently selected or even what font is being used. A good example of this could be to add a hook to all tabular material to use monospaced numbers, as shown in Example 6. Note however that the behaviour in this regard will be unreliable (subject to the font itself) if you attempt to *change* an already selected feature. *E.g.*, this sort of thing can cause troubles:

```

\addfontfeature{Numbers=OldStyle}...
\addfontfeature{Numbers=Lining}...
123

```

With both features active, how will the font render ‘123’? Depends on the font. In the distant future this functionality will be re-written to avoid this issue (giving ‘Numbers=OldStyle’ the smarts to know to explicitly de-activate any previous instances of ‘Numbers=Lining’, and vice-versa, but as I hope you can imagine this requires a fair degree of elbow grease which I haven’t had available for some time now.

`\addfontfeature` This command may also be executed under the alias `\addfontfeature`.

7.4 Priority of feature selection

Features defined with `\addfontfeatures` override features specified by `\fontspec`, which in turn override features specified by `\defaultfontfeatures`. If in doubt, whenever a new font is chosen for the first time, an entry is made in the transcript (`.log`) file displaying the font name and the features requested.

Example 7: Features for, say, just italics.

<i>Don't Ask Victoria!</i>	<code>\fontspec{EBGaramond12-Regular.otf}%</code>
<i>Don't Ask Victoria!</i>	<code>[ItalicFont=EBGaramond12-Italic.otf]</code>
<i>Don't Ask Victoria!</i>	<code>\itshape Dont Ask Victoria! \</code>
<i>Don't Ask Victoria!</i>	<code>\addfontfeature{ItalicFeatures={Style=Swash}}</code>
<i>Don't Ask Victoria!</i>	<code>Dont Ask Victoria! \</code>

7.5 Different features for different font shapes

```
BoldFeatures={\features}  
ItalicFeatures={\features}  
BoldItalicFeatures={\features}  
SlantedFeatures={\features}  
BoldSlantedFeatures={\features}  
SmallCapsFeatures={\features}
```

It is entirely possible that separate fonts in a family will require separate options; e.g., Hoefler Text Italic contains various swash feature options that are completely unavailable in the upright shapes.

The font features defined at the top level of the optional `\fontspec` argument are applied to *all* shapes of the family. Using `Upright-`, `SmallCaps-`, `Bold-`, `Italic-`, and `BoldItalicFeatures`, separate font features may be defined to their respective shapes *in addition* to, and with precedence over, the 'global' font features. See Example 7.

Note that because most fonts include their small caps glyphs within the main font, features specified with `SmallCapsFeatures` are applied *in addition* to any other shape-specific features as defined above, and hence `SmallCapsFeatures` can be nested within `ItalicFeatures` and friends. Every combination of upright, italic, bold and small caps can thus be assigned individual features, as shown in the somewhat ludicrous Example 8.

7.6 Different features for different font sizes

```
SizeFeatures = {  
  ...  
  { Size = <size range>, <font features> },  
  { Size = <size range>, Font = <font name>, <font features> },  
  ...  
}
```

The `SizeFeature` feature is a little more complicated than the previous features discussed. It allows different fonts and different font features to be selected for a given font family as the point size varies.

It takes a comma separated list of braced, comma separated lists of features for each size range. Each sub-list must contain the `Size` option to declare the size range, and optionally `Font` to change the font based on size. Other (regular) `fontspec` features that are added are used on top of the font features that would

Example 8: An example of setting the SmallCapsFeatures separately for each font shape.

```

\fontspec{texgyreterms}[
  Extension = {.otf},
  UprightFont = {*-regular}, ItalicFont = {*-italic},
  BoldFont = {*-bold}, BoldItalicFont = {*-bolditalic},
  UprightFeatures={Color = 220022,
    SmallCapsFeatures = {Color=115511}},
  ItalicFeatures={Color = 2244FF,
    SmallCapsFeatures = {Color=112299}},
  BoldFeatures={Color = FF4422,
    SmallCapsFeatures = {Color=992211}},
  BoldItalicFeatures={Color = 888844,
    SmallCapsFeatures = {Color=444422}},
]
Upright SMALL CAPS           Upright {\scshape Small Caps}\
Italic ITALIC SMALL CAPS   \itshape Italic {\scshape Italic Small Caps}\
Bold BOLD SMALL CAPS       \upshape\bfseries Bold {\scshape Bold Small Caps}\
Bold Italic BOLD ITALIC SMALL CAPS \itshape Bold Italic {\scshape Bold Italic Small Caps}

```

Example 9: An example of specifying different font features for different sizes of font with SizeFeatures.

```

\fontspec{texgyrechorus-mediumitalic.otf}[
  SizeFeatures={
    {Size={-8}, Font=texgyrebonum-italic.otf, Color=AA0000},
    {Size={8-14}, Color=00AA00},
    {Size={14-}, Color=0000AA}} ]
Small
Normal size
Large
{\scriptsize Small\par} Normal size\par {\Large Large\par}

```

be used anyway. A demonstration to clarify these details is shown in Example 9. A less trivial example is shown in the context of optical font sizes in Section 8.6 on page 22.

To be precise, the Size sub-feature accepts arguments in the form shown in Table 1 on the following page. Braces around the size range are optional. For an exact font size (Size=X) font sizes chosen near that size will ‘snap’. For example, for size definitions at exactly 11pt and 14pt, if a 12pt font is requested *actually* the 11pt font will be selected. This is a remnant of the past when fonts were designed in metal (at obviously rigid sizes) and later when bitmap fonts were similarly designed for fixed sizes.

If additional features are only required for a single size, the other sizes must still be specified. As in:

```

SizeFeatures={
  {Size=-10,Numbers=Uppercase},
  {Size=10-}}

```

Table 1: Syntax for specifying the size to apply custom font features.

Input	Font size, s
Size = X-	$s \geq X$
Size = -Y	$s < Y$
Size = X-Y	$X \leq s < Y$
Size = X	$s = X$

Otherwise, the font sizes greater than 10 won't be defined at all!

Interaction with other features For SizeFeatures to work with ItalicFeatures, BoldFeatures, etc., and SmallCapsFeatures, a strict heirarchy is required:

```
UprightFeatures =
{
  SizeFeatures =
  {
    {
      Size = -10,
      Font = ..., % if necessary
      SmallCapsFeatures = {...},
      ... % other features for this size range
    },
    ... % other size ranges
  }
}
```

Suggestions on simplifying this interface welcome.

8 Font independent options

Features introduced in this section may be used with any font.

8.1 Colour

Color (or Colour), also shown in [Section 7.1 on page 14](#) and elsewhere, uses font specifications to set the colour of the text. The colour is defined as a triplet of two-digit Hex RGB values, with optionally another value for the transparency (where 00 is completely transparent and FF is opaque.) Transparency is supported by Lua_{La}T_EX; X_{La}T_EX with the xdvipdfmx driver does not support this feature.

If you load the xcolor package, you may use any named colour instead of writing the colours in hexadecimal.

```
\usepackage{xcolor}
...
\fontspec[Color=red]{Verdana} ...
```

Example 10: Selecting colour with transparency. N.B. due to a conflict between fontspec and the preview package, this example currently does not show any transparency!



```
\fontsize{48}{48}
\fontspec{texgyrebonum-bold.otf}
{\addfontfeature{Color=FF000099}W}\kern-0.5ex
{\addfontfeature{Color=0000FF99}S}\kern-0.4ex
{\addfontfeature{Color=DDBB2299}P}\kern-0.4ex
{\addfontfeature{Color=00BB3399}R}
```

Example 11: Automatically calculated scale values.

```
\setmainfont{Georgia}
\newfontfamily\lc[Scale=MatchLowercase]{Verdana}
The perfect match {\lc is hard to find.}\
LOGO FONT \newfontfamily\uc[Scale=MatchUppercase]{Arial}
LOGO \uc FONT
```

```
\definecolor{Foo}{rgb}{0.3,0.4,0.5}
\fontspec[Color=Foo]{Verdana} ...
```

The color package is *not* supported; use xcolor instead.

You may specify the transparency with a named colour using the `Opacity` feature which takes an decimal from zero to one corresponding to transparent to opaque respectively:

```
\fontspec[Color=red,Opacity=0.7]{Verdana} ...
```

It is still possible to specify a colour in six-char hexadecimal form while defining opacity in this way, if you like.

8.2 Scale

Scale = <i>(number)</i>
Scale = MatchLowercase
Scale = MatchUppercase

In its explicit form, `Scale` takes a single numeric argument for linearly scaling the font, as demonstrated in Example 1. It is now possible to measure the correct dimensions of the fonts loaded and calculate values to scale them automatically.

As well as a numerical argument, the `Scale` feature also accepts options `MatchLowercase` and `MatchUppercase`, which will scale the font being selected to match the current default roman font to either the height of the lowercase or uppercase letters, respectively; these features are shown in Example 11.

The amount of scaling used in each instance is reported in the `.log` file. Since there is some subjectivity about the exact scaling to be used, these values should be used to fine-tune the results.

Example 12: Scaling the default interword space. An exaggerated value has been chosen to emphasise the effects here.

<p>Some text for our example to take up some space, and to demonstrate the default interword space.</p>	<pre>\fontspec{texgyretermes-regular.otf} Some text for our example to take up some space, and to demonstrate the default interword space. \bigskip</pre>
<p>Some text for our example to take up some space, and to demonstrate the default interword space.</p>	<pre>\fontspec{texgyretermes-regular.otf}% [WordSpace = 0.3] Some text for our example to take up some space, and to demonstrate the default interword space.</pre>

Note that when `Scale=MatchLowercase` is used with `\setmainfont`, the new ‘main’ font of the document will be scaled to match the old default. This may be undesirable in some cases, so to achieve ‘natural’ scaling for the main font but automatically scale all other fonts selected, you may write

```
\defaultfontfeatures{ Scale = MatchLowercase }
\defaultfontfeatures[\rmfamily]{ Scale = 1 }
```

One or both of these lines may be placed into a local `fontspec.cfg` file (see [Section 3.2 on page 4](#)) for this behaviour to be effected in your own documents automatically. (Also see [Section 7.1 on page 14](#) for more information on setting font defaults.)

8.3 Interword space

While the space between words can be varied on an individual basis with the \TeX primitive `\spaceskip` command, it is more convenient to specify this information when the font is first defined.

The space in between words in a paragraph will be chosen automatically, and generally will not need to be adjusted. For those times when the precise details are important, the `WordSpace` feature is provided, which takes either a single scaling factor to scale the default value, or a triplet of comma-separated values to scale the nominal value, the stretch, and the shrink of the interword space by, respectively. (`WordSpace={x}` is the same as `WordSpace={x,x,x}`.)

8.4 Post-punctuation space

If `\frenchspacing` is *not* in effect, \TeX will allow extra space after some punctuation in its goal of justifying the lines of text. Generally, this is considered old-fashioned, but occasionally in small amounts the effect can be justified, pardon the pun.

The `PunctuationSpace` feature takes a scaling factor by which to adjust the nominal value chosen for the font; this is demonstrated in [Example 13](#). Note that

Example 13: Scaling the default post-punctuation space.

	<code>\nonfrenchspacing</code>
	<code>\fontspec{texgyreschola-regular.otf}</code>
	Letters, Words. Sentences. <code>\par</code>
Letters, Words. Sentences.	<code>\fontspec{texgyreschola-regular.otf}[PunctuationSpace=2]</code>
Letters, Words. Sentences.	Letters, Words. Sentences. <code>\par</code>
Letters, Words. Sentences.	<code>\fontspec{texgyreschola-regular.otf}[PunctuationSpace=0]</code>
	Letters, Words. Sentences.

Example 14: Explicitly choosing the hyphenation character.

EXAMPLE HYPHENATION	<code>\def\text{\fbox{\parbox{1.55cm}{% EXAMPLE HYPHENATION% }}\quad\quad\null\par\bigskip}</code>
EXAMPLE HYPHEN+ ATION	<code>\fontspec{Linux Libertine 0}[HyphenChar=None] \text \fontspec{Linux Libertine 0}[HyphenChar={+}] \text</code>

`PunctuationSpace=0` is *not* equivalent to `\frenchspacing`, although the difference will only be apparent when a line of text is under-full.

8.5 The hyphenation character

The letter used for hyphenation may be chosen with the `HyphenChar` feature. It takes three types of input, which are chosen according to some simple rules. If the input is the string `None`, then hyphenation is suppressed for this font. If the input is a single character, then this character is used. Finally, if the input is longer than a single character it must be the UTF-8 slot number of the hyphen character you desire.

This package redefines L^AT_EX's `\-` macro such that it adjusts along with the above changes.

Note that T_EX's optimisations in how it loads fonts means that you cannot use this feature in `\addfontfeatures`.

8.6 Optical font sizes

Optically scaled fonts thicken out as the font size decreases in order to make the glyph shapes more robust (less prone to losing detail), which improves legibility. Conversely, at large optical sizes the serifs and other small details may be more delicately rendered.

OpenType fonts with optical scaling will exist in several discrete sizes, and these will be selected by X_FT_EX and LuaT_EX *automatically* determined by the cur-

Example 15: A demonstration of automatic optical size selection.

	<code>\fontspec{Latin Modern Roman}</code>	
Automatic optical size	Automatic optical size	\\
Automatic optical size	<code>\scalebox{0.4}{\Huge</code>	
	Automatic optical size}	

Example 16: Optical size substitution is suppressed when set to zero.

	<code>\fontspec{Latin Modern Roman 5 Regular}[OpticalSize=0]</code>	
	Latin Modern optical sizes	\\
	<code>\fontspec{Latin Modern Roman 8 Regular}[OpticalSize=0]</code>	
	Latin Modern optical sizes	\\
Latin Modern optical sizes	<code>\fontspec{Latin Modern Roman 12 Regular}[OpticalSize=0]</code>	
Latin Modern optical sizes	Latin Modern optical sizes	\\
Latin Modern optical sizes	<code>\fontspec{Latin Modern Roman 17 Regular}[OpticalSize=0]</code>	
Latin Modern optical sizes	Latin Modern optical sizes	

rent font size as in Example 15, in which we've scaled down some large text in order to be able to compare the difference for equivalent font sizes.

The `OpticalSize` option may be used to specify a different optical size. With `OpticalSize` set to zero, no optical size font substitution is performed, as shown in Example 16.

The `SizeFeatures` feature (Section 7.6 on page 17) can be used to specify exactly which optical sizes will be used for ranges of font size. For example, something like:

```
\fontspec{Latin Modern Roman}[
  UprightFeatures = { SizeFeatures = {
    {Size=-10,   OpticalSize=8 },
    {Size= 10-14, OpticalSize=10},
    {Size= 14-18, OpticalSize=14},
    {Size= 18-,  OpticalSize=18}}
  ]
```

Part III

OpenType

9 Introduction

OpenType fonts (and other 'smart' font technologies such as AAT and Graphite) can change the appearance of text in many different ways. These changes are referred to as font features. When the user applies a feature — for example, small

capitals — to a run of text, the code inside the font makes appropriate substitutions and small capitals appear in place of lowercase letters. However, the use of such features does not affect the underlying text. In our small caps example, the lowercase letters are still stored in the document; only the appearance has been changed by the OpenType feature. This makes it possible to search and copy text without difficulty. If the user selected a different font that does not support small caps, the ‘plain’ lowercase letters would appear instead.

Some OpenType features are required to support particular scripts, and these features are often applied automatically. The Indic scripts, for example, often require that characters be reshaped and reordered after they are typed by the user, in order to display them in the traditional ways that readers expect. Other features can be applied to support a particular language. The Junicode font for medievalists uses by default the Old English shape of the letter thorn, while in modern Icelandic thorn has a more rounded shape. If a user tags some text as being in Icelandic, Junicode will automatically change to the Icelandic shape through an OpenType feature that localises the shapes of letters.

There are a large group of OpenType features, designed to support high quality typography a multitude of languages and writing scripts. Examples of some font features have already been shown in previous sections; the complete set of OpenType font features supported by fontspec is described below in [Section 10](#).

The OpenType specification provides four-letter codes (e.g., `smcp` for small capitals) for each feature. The four-letter codes are given below along with the fontspec names for various features, for the benefit of people who are already familiar with OpenType. You can ignore the codes if they don’t mean anything to you.

9.1 How to select font features

Font features are selected by a series of $\langle feature \rangle = \langle option \rangle$ selections. Features are (usually) grouped logically; for example, all font features relating to ligatures are accessed by writing `Ligatures={...}` with the appropriate argument(s), which could be `TeX`, `Rare`, etc., as shown below in [Section 10.1](#).

Multiple options may be given to any feature that accepts non-numerical input, although doing so will not always work. Some options will override others in generally obvious ways; `Numbers={OldStyle,Lining}` doesn’t make much sense because the two options are mutually exclusive, and \XeTeX will simply use the last option that is specified (in this case using `Lining` over `OldStyle`).

If a feature or an option is requested that the font does not have, a warning is given in the console output. As mentioned in [Section 3.3 on page 4](#) these warnings can be suppressed by selecting the `[quiet]` package option.

9.2 How do I know what font features are supported by my fonts?

Although I’ve long desired to have a feature within fontspec to display the OpenType features within a font, it’s never been high on my priority list. One reason for that is the existence of the document `opentype-info.tex`, which is available on CTAN or typing `kpsewhich opentype-info.tex` in a Terminal window. Make a

copy of this file and place it somewhere convenient. Then open it in your regular \TeX editor and change the font name to the font you'd like to query; after running through plain $X_{\text{E}}\TeX$, the output PDF will look something like this:

OpenType Layout features found in '[Asana-Math.otf]'

```
script = 'DFLT'
  language = <default>
    features = 'onum' 'salt' 'kern'
script = 'cher'
  language = <default>
    features = 'onum' 'salt' 'kern'
script = 'grek'
  language = <default>
    features = 'onum' 'salt' 'kern'
script = 'latn'
  language = <default>
    features = 'onum' 'salt' 'kern'
script = 'math'
  language = <default>
    features = 'dtls' 'onum' 'salt' 'ssty' 'kern'
```

I intentionally picked a font that by design needs few font features; 'regular' text fonts such as Latin Modern Roman contain many more, and I didn't want to clutter up the document too much. You'll then need to cross-check the OpenType feature tags with the 'logical' names used by fontspec.

otfinfo Alternatively, and more simply, you can use the command line tool `otfinfo`, which is distributed with \TeX Live. Simply type in a Terminal window, say:

```
otfinfo -f `kpsewhich lmromandunh10-oblique.otf`
```

which results in:

aalt	Access All Alternates
csp	Capital Spacing
dlig	Discretionary Ligatures
frac	Fractions
kern	Kerning
liga	Standard Ligatures
lnum	Lining Figures
onum	Oldstyle Figures
pnum	Proportional Figures
size	Optical Size
tnum	Tabular Figures
zero	Slashed Zero

Table 2: Options for the OpenType font feature ‘Ligatures’.

Feature	Option	Tag
Ligatures =	Required	* rlig
	NoRequired	rlig (<i>deactivate</i>)
	Common	* liga
	NoCommon	liga (<i>deactivate</i>)
	Contextual	* clig
	NoContextual	clig (<i>deactivate</i>)
	Rare/Discretionary	dlig
	Historic	hlig
	TeX	tlig/trep

* This feature is activated by default.

Table 3: Options for the OpenType font feature ‘Letters’.

Feature	Option	Tag
Letters =	Uppercase	case
	SmallCaps	smcp
	PetiteCaps	pcap
	UppercaseSmallCaps	c2sc
	UppercasePetiteCaps	c2pc
	Unicase	unic

10 Complete listing of OpenType font features

10.1 Ligatures

Ligatures refer to the replacement of two separate characters with a specially drawn glyph for functional or æsthetic reasons. The list of options, of which multiple may be selected at one time, is shown in [Table 2](#). A demonstration with the Linux Libertine fonts⁷ is shown in [Example 17](#).

Note the additional features accessed with `Ligatures=TeX`. These are not actually real OpenType features, but additions provided by `luaotfload` (i.e., `LuaTeX` only) to emulate `TeX`’s behaviour for `ASCII` input of curly quotes and punctuation. In `XYTeX` this is achieved with the Mapping feature (see [Section 12.1 on page 42](#)) but for consistency `Ligatures=TeX` will perform the same function as `Mapping=tex-text`.

10.2 Letters

The Letters feature specifies how the letters in the current font will look. OpenType fonts may contain the following options: `Uppercase`, `SmallCaps`, `PetiteCaps`, `UppercaseSmallCaps`, `UppercasePetiteCaps`, and `Unicase`.

⁷<http://www.linuxlibertine.org/>

Example 17: An example of the Ligatures feature.

strict	→	ſtrict	
wurtzite	→	wurtzite	<code>\def\test#1#2{%</code>
firefly	→	firefly	<code>#2 \$\to\$ {\addfontfeature{#1} #2}\}</code>

```
\fontspec{Linux Libertine O}
\test{Ligatures=Historic}{strict}
\test{Ligatures=Rare}{wurtzite}
\test{Ligatures=NoCommon}{firefly}
```

Example 18: Small caps from lowercase or uppercase letters.

```
\fontspec{texgyreadventor-regular.otf}[Letters=SmallCaps]
THIS SENTENCE NO VERB THIS SENTENCE no verb \\
THIS SENTENCE NO VERB \fontspec{texgyreadventor-regular.otf}[Letters=UppercaseSmallCaps]
THIS SENTENCE NO VERB THIS SENTENCE no verb
```

Petite caps are smaller than small caps. `SmallCaps` and `PetiteCaps` turn lowercase letters into the smaller caps letters, whereas the `Uppercase...` options turn the *capital* letters into the smaller caps (good, *e.g.*, for applying to already uppercase acronyms like ‘NASA’). This difference is shown in Example 18. ‘Unicase’ is a weird hybrid of upper and lower case letters.

Note that the `Uppercase` option will (probably) not actually map letters to uppercase.⁸ It is designed to select various uppercase forms for glyphs such as accents and dashes, such as shown in Example 19; note the raised position of the hyphen to better match the surrounding letters.

The Kerning feature also contains an `Uppercase` option, which adds a small amount of spacing in between letters (see [Section 10.12 on page 34](#)).

10.3 Numbers

The `Numbers` feature defines how numbers will look in the selected font, accepting options shown in [Table 4](#).

⁸If you want automatic uppercase letters, look to L^AT_EX’s `\MakeUppercase` command.

Example 19: An example of the `Uppercase` option of the `Letters` feature.

UPPER-CASE example	<code>\fontspec{Linux Libertine O}</code>
UPPER-CASE example	<code>UPPER-CASE example \\</code>
	<code>\addfontfeature{Letters=Uppercase}</code>
	<code>UPPER-CASE example</code>

Table 4: Options for the OpenType font feature ‘Numbers’.

Feature	Option	Tag
Numbers =	Uppercase/Lining	lnum
	Lowercase/OldStyle	onum
	Proportional	pnum
	Monospaced	tnum
	SlashedZero	zero
	Arabic	anum

Example 20: The effect of the SlashedZero option.

```

\fontspec[Numbers=Lining]{texgyrebonum-regular.otf}
0123456789
\fontspec[Numbers=SlashedZero]{texgyrebonum-regular.otf}
0123456789 Q123456789

```

The synonyms `Uppercase` and `Lowercase` are equivalent to `Lining` and `OldStyle`, respectively. The differences have been shown previously in [Section 7.3 on page 16](#). The `Monospaced` option is useful for tabular material when digits need to be vertically aligned.

The `SlashedZero` option replaces the default zero with a slashed version to prevent confusion with an uppercase ‘O’, shown in [Example 20](#).

The `Arabic` option (with tag `anum`) maps regular numerals to their Arabic script or Persian equivalents based on the current Language setting (see [Section 10.18 on page 37](#)). This option is based on a LuaTeX feature of the `luaotfload` package, not an OpenType feature. (Thus, this feature is unavailable in XeTeX.)

10.4 Contextuals

This feature refers to substitutions of glyphs that vary ‘contextually’ by their relative position in a word or string of characters; features such as contextual swashes are accessed via the options shown in [Table 5](#).

Table 5: Options for the OpenType font feature ‘Contextuals’.

Feature	Option	Tag
Contextuals =	Swash	csw
	Alternate	calt
	WordInitial	init
	WordFinal	fina
	LineFinal	falt
	Inner	medi

Table 6: Options for the OpenType font feature ‘VerticalPosition’.

Feature	Option	Tag
VerticalPosition =	Superior	sup
	Inferior	sub
	Numerator	numr
	Denominator	dnom
	ScientificInferior	sinf
	Ordinal	ordn

Example 21: The VerticalPosition feature.

	<code>\fontspec{LibreCaslonText-Regular.otf}[VerticalPosition=Superior]</code>
Superior: 1234567890	Superior: 1234567890
	<code>\fontspec{LibreCaslonText-Regular.otf}[VerticalPosition=Numerator]</code>
Numerator: 12345	Numerator: 12345
	<code>\fontspec{LibreCaslonText-Regular.otf}[VerticalPosition=Denominator]</code>
Denominator: 12345	Denominator: 12345
	<code>\fontspec{LibreCaslonText-Regular.otf}[VerticalPosition=ScientificInferior]</code>
Scientific Inferior: 12345	Scientific Inferior: 12345

Historic forms are accessed in OpenType fonts via the feature `Style=Historic`; this is generally *not* contextual in OpenType, which is why it is not included in this feature.

10.5 Vertical Position

The `VerticalPosition` feature is used to access things like subscript (`Inferior`) and superscript (`Superior`) numbers and letters (and a small amount of punctuation, sometimes). The `Ordinal` option will only raise characters that are used in some languages directly after a number. The `ScientificInferior` feature will move glyphs further below the baseline than the `Inferior` feature. These are shown in [Example 21](#)

Numerator and Denominator should only be used for creating arbitrary fractions (see next section).

The `realscripts` package (which is also loaded by `xltextra` for $\text{X}_{\text{L}}\text{T}_{\text{E}}\text{X}$) redefines the `\textsubscript` and `\textsuperscript` commands to use the above font features automatically, including for use in footnote labels. If this is the only feature of `xltextra` you wish to use, consider loading `realscripts` on its own instead.

10.6 Fractions

For OpenType fonts use a regular text slash to create fractions, but the `Fraction` feature must be explicitly activated. Some (Asian fonts predominantly) also provide for the `Alternate` feature. These are both shown in [Example 22](#).

Table 7: Options for the OpenType font feature ‘Fractions’.

Feature	Option	Tag
Fractions	= On	frac
	Alternate	afrc

Example 22: The Fractions feature.

				<code>\fontspec{Hiragino Maru Gothic Pro W4}</code>
				<code>1/2 \quad 1/4 \quad 5/6 \quad 13579/24680 \quad \backslash</code>
				<code>\addfontfeature{Fractions=On}</code>
				<code>1/2 \quad 1/4 \quad 5/6 \quad 13579/24680 \quad \backslash</code>
				<code>\addfontfeature{Fractions=Alternate}</code>
				<code>1/2 \quad 1/4 \quad 5/6 \quad 13579/24680 \quad \backslash</code>

10.7 Stylistic Set variations

This feature selects a ‘Stylistic Set’ variation, which usually corresponds to an alternate glyph style for a range of characters (usually an alphabet or subset thereof). This feature is specified numerically. These correspond to OpenType features `ss01`, `ss02`, etc.

Two demonstrations from the Junicode font⁹ are shown in Example 23 and Example 24; thanks to Adam Buchbinder for the suggestion.

Multiple stylistic sets may be selected simultaneously by writing, e.g., `StylisticSet={1,2,3}`.

The `StylisticSet` feature is a synonym of the `Variant` feature for `AAT` fonts. See Section 14 on page 49 for a way to assign names to stylistic sets, which should be done on a per-font basis.

10.8 Character Variants

Similar to the ‘Stylistic Sets’ above, ‘Character Variations’ are selected numerically to adjust the output of (usually) a single character for the particular font. These correspond to the OpenType features `cv01` to `cv99`.

For each character that can be varied, it is possible to select among possible options for that particular glyph. For example, in Example 25 a variety of glyphs for

⁹<http://junicode.sf.net>

Example 23: Insular letterforms, as used in medieval Northern Europe, for the Junicode font accessed with the `StylisticSet` feature.

Insular forms.	<code>\fontspec{Junicode}</code>
Inſular ꝑoꝑmꝑ.	<code>Insular forms. \backslash</code>
	<code>\addfontfeature{StylisticSet=2}</code>
	<code>Insular forms. \backslash</code>

Example 24: Enlarged minuscules (capital letters remain unchanged) for the Junicode font, accessed with the StylisticSet feature.

ENLARGED Minuscules.	<code>\fontspec{Junicode}</code>
ENLARGED Minuscules.	<code>ENLARGED Minuscules. \</code>
ENLARGED Minuscules.	<code>\addfontfeature{StylisticSet=6}</code>
	<code>ENLARGED Minuscules. \</code>

Example 25: The CharacterVariant feature showing off Georg Duffner’s open source Garamond revival font.

<i>very</i>	
<i>very</i>	
<i>very</i>	
<i>very</i>	<code>\fontspec{EB Garamond 12 Italic} very \</code>
<i>very</i>	<code>\fontspec{EB Garamond 12 Italic}[CharacterVariant=5] very \</code>
<i>very</i>	<code>\fontspec{EB Garamond 12 Italic}[CharacterVariant=5:0] very \</code>
<i>very</i>	<code>\fontspec{EB Garamond 12 Italic}[CharacterVariant=5:1] very \</code>
<i>very</i>	<code>\fontspec{EB Garamond 12 Italic}[CharacterVariant=5:2] very \</code>
<i>very</i>	<code>\fontspec{EB Garamond 12 Italic}[CharacterVariant=5:3] very</code>

the character ‘v’ are selected, in which 5 corresponds to the character ‘v’ for this font feature, and the trailing $\langle n \rangle$ corresponds to which variety to choose. Georg Duffner’s open source Garamond revival font¹⁰ is used in this example. Character variants are specifically designed not to conflict with each other, so you can enable them individually per character as shown in Example 26. (Unlike stylistic alternates, say.)

Note that the indexing starts from zero.

¹⁰<http://www.georgduffner.at/ebgaramond/>

Example 26: The CharacterVariant feature selecting multiple variants simultaneously.

<i>É violet</i>	
<i>É violet</i>	
<i>É violet</i>	<code>\fontspec{EB Garamond 12 Italic} \& violet \</code>
<i>É violet</i>	<code>\fontspec{EB Garamond 12 Italic}[CharacterVariant={4}] \& violet \</code>
<i>É violet</i>	<code>\fontspec{EB Garamond 12 Italic}[CharacterVariant={5:2}] \& violet \</code>
<i>É violet</i>	<code>\fontspec{EB Garamond 12 Italic}[CharacterVariant={4,5:2}] \& violet</code>

Example 27: The Alternate feature.

A & h	<code>\fontspec{Linux Libertine O}</code> <code>\textsc{a} \& h \</code>
A & h	<code>\addfontfeature{Alternate=0}</code> <code>\textsc{a} \& h</code>

Table 8: Options for the OpenType font feature ‘Style’.

Feature Option	Tag
Style = Alternate	salt
Italic	ital
Ruby	ruby
Swash	swsh
Historic	hist
TitlingCaps	titl
HorizontalKana	hkna
VerticalKana	vkna

10.9 Alternates

The `Alternate` feature (for the raw OpenType feature `salt`) is used to access alternate font glyphs when variations exist in the font, such as in Example 27. It uses a numerical selection, starting from zero, that will be different for each font. Note that the `Style=Alternate` option is equivalent to `Alternate=0` to access the default case.

Note that the indexing starts from zero.

See Section 14 on page 49 for a way to assign names to alternates, which must be done on a per-font basis.

10.10 Style

‘Ruby’ refers to a small optical size, used in Japanese typography for annotations. For fonts with multiple `salt` OpenType features, use the `fontspec Alternate` feature instead.

Example 28 and Example 29 both contain glyph substitutions with similar characteristics. Note the occasional inconsistency with which font features are labelled; a long-tailed ‘Q’ could turn up anywhere!

In other features, larger breadths of changes can be seen, covering the style of an entire alphabet. See Example 30 and Example 31; in the latter, the `Italic` option affects the Latin text and the `Ruby` option the Japanese.

Note the difference here between the default and the horizontal style kana in Example 32: the horizontal style is slightly wider.

Example 28: Example of the Alternate option of the Style feature.

M Q W	<code>\fontspec{Quattrocento Roman}</code>
M Q W	<code>M Q W \</code>
M Q W	<code>\addfontfeature{Style=Alternate}</code>
M Q W	<code>M Q W</code>

Example 29: Example of the Historic option of the Style feature.

M Q Z	<code>\fontspec{Adobe Jenson Pro}</code>
M Q Z	<code>M Q Z \</code>
M Q Z	<code>\addfontfeature{Style=Historic}</code>
M Q Z	<code>M Q Z</code>

Example 30: Example of the TitlingCaps option of the Style feature.

TITLING CAPS	<code>\fontspec{Adobe Garamond Pro}</code>
TITLING CAPS	<code>TITLING CAPS \</code>
TITLING CAPS	<code>\addfontfeature{Style=TitlingCaps}</code>
TITLING CAPS	<code>TITLING CAPS</code>

Example 31: Example of the Italic and Ruby options of the Style feature.

Latin ようこそ ワカヨタレソ	<code>\fontspec{Hiragino Mincho Pro}</code>
Latin ようこそ ワカヨタレソ	<code>Latin \kana \</code>
Latin ようこそ ワカヨタレソ	<code>\addfontfeature{Style={Italic, Ruby}}</code>
Latin ようこそ ワカヨタレソ	<code>Latin \kana</code>

Example 32: Example of the HorizontalKana and VerticalKana options of the Style feature.

ようこそ ワカヨタレソ	<code>\fontspec{Hiragino Mincho Pro}</code>
ようこそ ワカヨタレソ	<code>\kana \</code>
ようこそ ワカヨタレソ	<code>{\addfontfeature{Style=HorizontalKana}</code>
ようこそ ワカヨタレソ	<code>\kana } \</code>
ようこそ ワカヨタレソ	<code>{\addfontfeature{Style=VerticalKana}</code>
ようこそ ワカヨタレソ	<code>\kana }</code>

Table 9: Options for the OpenType font feature ‘Diacritics’.

Feature	Option	Tag
Diacritics =	MarkToBase	* mark
	NoMarkToBase	mark <i>(deactivate)</i>
	MarkToMark	* mkmk
	NoMarkToMark	mkmk <i>(deactivate)</i>
	AboveBase	* abvm
	NoAboveBase	abvm <i>(deactivate)</i>
	BelowBase	* blwm
	NoBelowBase	blwm <i>(deactivate)</i>

* This feature is activated by default.

Table 10: Options for the OpenType font feature ‘Kerning’.

Feature	Option	Tag
Kerning =	Uppercase	csp
	On	* kern
	Off	kern <i>(deactivate)</i>

* This feature is activated by default.

10.11 Diacritics

Specifies how combining diacritics should be placed. These will usually be controlled automatically according to the Script setting.

10.12 Kerning

Specifies how inter-glyph spacing should behave. Well-made fonts include information for how differing amounts of space should be inserted between separate character pairs. This kerning space is inserted automatically but in rare circumstances you may wish to turn it off.

As briefly mentioned previously at the end of [Section 10.2 on page 26](#), the Uppercase option will add a small amount of tracking between uppercase letters, seen in [Example 33](#), which uses the Romande fonts¹¹ (thanks to Clea F. Rees for the suggestion). The Uppercase option acts separately to the regular kerning controlled by the On/Off options.

10.13 Font transformations

In rare situations users may want to mechanically distort the shapes of the glyphs in the current font such as shown in [Example 34](#). Please don’t overuse these features; they are *not* a good alternative to having the real shapes.

If values are omitted, their defaults are as shown above.

¹¹<http://arkandis.tuxfamily.org/adffonts.html>

Example 33: Adding extra kerning for uppercase letters. (The difference is usually very small.)

UPPERCASE EXAMPLE
UPPERCASE EXAMPLE

```
\fontspec{Romande ADF Std Bold}
UPPERCASE EXAMPLE \\
\addfontfeature{Kerning=Uppercase}
UPPERCASE EXAMPLE
```

Example 34: Artificial font transformations.

		<code>\fontspec{Charis SIL} \emph{ABCxyz} \quad</code>
		<code>\fontspec{Charis SIL}[FakeSlant=0.2] ABCxyz</code>
<i>ABCxyz</i>	<i>ABCxyz</i>	<code>\fontspec{Charis SIL} ABCxyz \quad</code>
ABCxyz	ABCxyz	<code>\fontspec{Charis SIL}[FakeStretch=1.2] ABCxyz</code>
<i>ABCxyz</i>	<i>ABCxyz</i>	<code>\fontspec{Charis SIL} \textbf{ABCxyz} \quad</code>
		<code>\fontspec{Charis SIL}[FakeBold=1.5] ABCxyz</code>

If you want the bold shape to be faked automatically, or the italic shape to be slanted automatically, use the `AutoFakeBold` and `AutoFakeSlant` features. For example, the following two invocations are equivalent:

```
\fontspec[AutoFakeBold=1.5]{Charis SIL}
\fontspec[BoldFeatures={FakeBold=1.5}]{Charis SIL}
```

If both of the `AutoFake...` features are used, then the bold italic font will also be faked.

The `FakeBold` and `AutoFakeBold` features are only available with the $X_{\text{}}\text{T}_{\text{E}}\text{X}$ engine and will be ignored in $\text{LuaT}_{\text{E}}\text{X}$.

10.14 Annotation

Some fonts are equipped with an extensive range of numbers and numerals in different forms. These are accessed with the Annotation feature (OpenType feature `nalt`), selected numerically as shown in Example 35.

Note that the indexing starts from zero.

10.15 CJK shape

There have been many standards for how CJK ideographic glyphs are ‘supposed’ to look. Some fonts will contain many alternate glyphs available in order to be able to display these glyphs correctly in whichever form is appropriate. Both `AAT` and OpenType fonts support the following `CJKShape` options: `Traditional`, `Simplified`, `JIS1978`, `JIS1983`, `JIS1990`, and `Expert`. OpenType also supports the `NLC` option.

Example 35: Annotation forms for OpenType fonts.

1 2 3 4 5 6 7 8 9	
(1) (2) (3) (4) (5) (6) (7) (8) (9)	
(1 (2 (3 (4 (5 (6 (7 (8 (9	
1) 2) 3) 4) 5) 6) 7) 8) 9)	
① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨	
Ⓛ Ⓜ Ⓨ Ⓩ ⓐ ⓑ ⓓ ⓔ ⓖ	
Ⓢ Ⓣ Ⓥ Ⓦ Ⓧ Ⓨ Ⓩ ⓐ ⓑ	
Ⓘ Ⓚ Ⓛ Ⓜ Ⓨ Ⓩ ⓐ ⓑ ⓓ	
Ⓙ Ⓛ Ⓜ Ⓨ Ⓩ ⓐ ⓑ ⓓ ⓔ	
Ⓙ Ⓛ Ⓜ Ⓨ Ⓩ ⓐ ⓑ ⓓ ⓔ	
Ⓙ Ⓛ Ⓜ Ⓨ Ⓩ ⓐ ⓑ ⓓ ⓔ	
1. 2. 3. 4. 5. 6. 7. 8. 9.	
	<pre> \fontspec{Hiragino Maru Gothic Pro} 1 2 3 4 5 6 7 8 9 \def\x#1{\{\{\addfontfeature{Annotation=#1} 1 2 3 4 5 6 7 8 9 }\}} \x0\x1\x2\x3\x4\x5\x6\x7\x8\x9 </pre>

Table 11: Options for the OpenType font feature ‘CJKShape’.

Feature	Option	Tag
CJKShape =	Traditional	trad
	Simplified	smp1
	JIS1978	jp78
	JIS1983	jp83
	JIS1990	jp90
	Expert	expt
	NLC	n1ck

Example 36: Different standards for CJK ideograph presentation.

啞嚙軀 妍并訝	<pre> \fontspec{Hiragino Mincho Pro} {\addfontfeature{CJKShape=Traditional} \text } \ \ </pre>
啞嚙軀 妍并訝	<pre> {\addfontfeature{CJKShape=NLC} \text } \ \ </pre>
啞嚙軀 妍并訝	<pre> {\addfontfeature{CJKShape=Expert} \text } </pre>

Table 12: Options for the OpenType font feature ‘CharacterWidth’.

Feature	Option	Tag
CharacterWidth =	Proportional	pwid
	Full	fwid
	Half	hwid
	Third	twid
	Quarter	qwid
	AlternateProportional	palt
	AlternateHalf	halt

Example 37: Proportional or fixed width forms.

			<pre> \def\test{\makebox[2cm][1]{\texta}% \makebox[2.5cm][1]{\textb}% \makebox[2.5cm][1]{abcdef}} \fontspec{Hiragino Mincho Pro} {\addfontfeature{CharacterWidth=Proportional}\test}\ {\addfontfeature{CharacterWidth=Full}\test}\ {\addfontfeature{CharacterWidth=Half}\test} </pre>
ようこそ	ワカヨタレソ	abcdef	
ようこそ	ワカヨタレソ	a b c d e f	
ようこそ	ワカヨタレソ	abcdef	

10.16 Character width

Many Asian fonts are equipped with variously spaced characters for shoe-horning into their generally monospaced text. These are accessed through the `CharacterWidth` feature.

Japanese alphabetic glyphs (in Hiragana or Katakana) may be typeset proportionally, to better fit horizontal measures, or monospaced, to fit into the rigid grid imposed by ideographic typesetting. In this latter case, there are also half-width forms for squeezing more kana glyphs (which are less complex than the kanji they are amongst) into a given block of space. The same features are given to roman letters in Japanese fonts, for typesetting foreign words in the same style as the surrounding text.

The same situation occurs with numbers, which are provided in increasingly illegible compressed forms seen in Example 38.

10.17 Vertical typesetting

TODO!

10.18 OpenType scripts and languages

Fonts that include glyphs for various scripts and languages may contain different font features for the different character sets and languages they support, and different font features may behave differently depending on the script or language

Example 38: Numbers can be compressed significantly.

	<code>\fontspec[Renderer=AAT]{Hiragino Mincho Pro}</code>
	<code>{\addfontfeature{CharacterWidth=Full}}</code>
	<code>---12321---}\</code>
	<code>{\addfontfeature{CharacterWidth=Half}}</code>
	<code>---1234554321---}\</code>
<code>— 1 2 3 2 1 —</code>	<code>{\addfontfeature{CharacterWidth=Third}}</code>
<code>-1234554321-</code>	<code>---123456787654321---}\</code>
<code>-123456787654321-</code>	<code>{\addfontfeature{CharacterWidth=Quarter}}</code>
<code>-12345678900987654321-</code>	<code>---12345678900987654321---}</code>

chosen. When multilingual fonts are used, it is important to select which language they are being used for, and more importantly what script is being used.

The ‘script’ refers to the alphabet in use; for example, both English and French use the Latin script. Similarly, the Arabic script can be used to write in both the Arabic and Persian languages.

The `Script` and `Language` features are used to designate this information. The possible options are tabulated in [Table 13 on the next page](#) and [Table 14 on page 40](#), respectively. When a script or language is requested that is not supported by the current font, a warning is printed in the console output.

Because these font features can change which features are able to be selected for the font, they are automatically selected by `fontspec` before all others and, if Xe_{La}TeX is being used, will specifically select the OpenType renderer for this font, as described in [Section 12.3 on page 43](#).

10.18.1 Script and Language examples

In the examples shown in [Example 39](#), the Code2000 font¹² is used to typeset various input texts with and without the OpenType Script applied for various alphabets. The text is only rendered correctly in the second case; many examples of incorrect diacritic spacing as well as a lack of contextual ligatures and rearrangement can be seen. Thanks to Jonathan Kew, Yves Codet and Gildas Hamel for their contributions towards these examples.

10.18.2 Defining new scripts and languages

`\newfontscript`
`\newfontlanguage`

While the scripts and languages listed in [Table 13](#) and [Table 14](#) are intended to be comprehensive, there may be some missing; alternatively, you might wish to use different names to access scripts/languages that are already listed. Adding scripts and languages can be performed with the `\newfontscript` and `\newfontlanguage` commands. For example,

```
\newfontscript{Arabic}{arab}
\newfontlanguage{Zulu}{ZUL}
```

¹²<http://www.code2000.net/>

Example 39: An example of various Scripts and Languages.

العربي	العربي		<code>\testfeature{Script=Arabic}{\arabictext}</code>
हिन्दी	हिन्दी		<code>\testfeature{Script=Devanagari}{\devanagaritext}</code>
লেখ	লেখ		<code>\testfeature{Script=Bengali}{\bengalitext}</code>
ਮੁਘਾਣ-ਸੁਘਕ ਨਿਵੇਣ	ਮੁਘਾਣ-ਸੁਘਕ ਨਿਵੇਣ		<code>\testfeature{Script=Gujarati}{\gujaratitext}</code>
നമമുടറെ പാരബരയ്	നമമുടറെ പാരബരയ്		<code>\testfeature{Script=Malayalam}{\malayalamtext}</code>
ਆਦਿ ਸਚੁ ਜੁਗਾਦਿ ਸਚੁ	ਆਦਿ ਸਚੁ ਜੁਗਾਦਿ ਸਚੁ		<code>\testfeature{Script=Gurmukhi}{\gurmukhitext}</code>
தமிழ் துடே	தமிழ் துடே		<code>\testfeature{Script=Tamil}{\tamiltext}</code>
אָפּ	אָפּ		<code>\testfeature{Script=Hebrew}{\hebrewtext}</code>
cáp số mõi	cáp số mõi		<code>\def\examplefont{Doulos SIL}</code>
			<code>\testfeature{Language=Vietnamese}{\vietnamesetext}</code>

The first argument is the fontspec name, the second the OpenType tag. The advantage to using these commands rather than `\newfontfeature` (see [Section 14 on page 49](#)) is the error-checking that is performed when the script or language is requested.

Table 13: Defined Scripts for OpenType fonts. Aliased names are shown in adjacent positions marked with red pilcrows (¶).

Arabic	Ethiopic	Limbu	Sumero-Akkadian
Armenian	Georgian	Linear B	Cuneiform
Balinese	Glagolitic	Malayalam	Syloiti Nagri
Bengali	Gothic	¶Math	Syriac
Bopomofo	Greek	¶Maths	Tagalog
Braille	Gujarati	Mongolian	Tagbanwa
Buginese	Gurmukhi	Musical Symbols	Tai Le
Buhid	Hangul Jamo	Myanmar	Tai Lu
Byzantine Music	Hangul	N'ko	Tamil
Canadian Syllabics	Hanunoo	Ogham	Telugu
Cherokee	Hebrew	Old Italic	Thaana
¶CJK	¶Hiragana and Katakana	Old Persian Cuneiform	Thai
¶CJK Ideographic	¶Kana	Oriya	Tibetan
Coptic	Javanese	Osmanya	Tifinagh
Cypriot Syllabary	Kannada	Phags-pa	Ugaritic Cuneiform
Cyrillic	Kharosthi	Phoenician	Yi
Default	Khmer	Runic	
Deseret	Lao	Shavian	
Devanagari	Latin	Sinhala	

Table 14: Defined Languages for OpenType fonts. Aliased names are shown in adjacent positions marked with red pilcrows (⌘).

Abaza	Default	Igbo	Koryak	Norway House Cree	Saraiki
Abkhazian	Dogri	Ijo	Ladin	Nisi	Serer
Adyghe	Divehi	Ilokano	Lahuli	Niuean	South Slavey
Afrikaans	Djerma	Indonesian	Lak	Nkole	Southern Sami
Afar	Dangme	Ingush	Lambani	N'ko	Suri
Agaw	Dinka	Inuktitut	Lao	Dutch	Svan
Altai	Dungan	Irish	Latin	Nogai	Swedish
Amharic	Dzongkha	Irish Traditional	Laz	Norwegian	Swadaya Aramaic
Arabic	Ebira	Icelandic	L-Cree	Northern Sami	Swahili
Aari	Eastern Cree	Inari Sami	Ladakhi	Northern Tai	Swazi
Arakanese	Edo	Italian	Lezgi	Esperanto	Sutu
Assamese	Efik	Hebrew	Lingala	Nynorsk	Syriac
Athapaskan	Greek	Javanese	Low Mari	Oji-Cree	Tabasaran
Avar	English	Yiddish	Limbu	Ojibway	Tajiki
Awadhi	Erzya	Japanese	Lomwe	Oriya	Tamil
Aymara	Spanish	Judezmo	Lower Sorbian	Oromo	Tatar
Azeri	Estonian	Jula	Lule Sami	Ossetian	TH-Cree
Badaga	Basque	Kabardian	Lithuanian	Palestinian	Telugan
Baghelkhandi	Evenki	Kachchi	Luba	Aramaic	Tongan
Balkar	Even	Kalenjin	Luganda	Pali	Tigre
Baule	Ewe	Kannada	Luhya	Punjabi	Tigrinya
Berber	French Antillean	Karachay	Luo	Palpa	Thai
Bench	⌘Farsi	Georgian	Latvian	Pashto	Tahitian
Bible Cree	⌘Parsi	Kazakh	Majang	Polytonic Greek	Tibetan
Belarussian	⌘Persian	Kevena	Makua	Pilipino	Turkmen
Bemba	Finnish	Khutsuri Georgian	Malayalam	Palaung	Temne
Bengali	Fijian	Khakass	Traditional	Polish	Tswana
Bulgarian	Flemish	Khanty-Kazim	Mansi	Provençal	Tundra Nenets
Bhili	Forest Nenets	Khmer	Marathi	Portuguese	Tonga
Bhojpuri	Fon	Khanty-Shurishkar	Marwari	Chin	Todo
Bikol	Faroese	Khanty-Vakhi	Mbundu	Rajasthani	Turkish
Bilen	French	Khowar	Manchu	R-Cree	Tsonga
Blackfoot	Frisian	Kikuyu	Moose Cree	Russian Buriat	Turoyo Aramaic
Balochi	Friulian	Kirghiz	Mende	Riang	Tulu
Balante	Futa	Kisii	Me'en	Rhaeto-Romanic	Tuvin
Balti	Fulani	Kokni	Mizo	Romanian	Twi
Bambara	Ga	Kalmyk	Macedonian	Romany	Udmurt
Bamileke	Gaelic	Kamba	Male	Rusyn	Ukrainian
Breton	Gagauz	Kumaoni	Malagasy	Ruanda	Urdu
Brahui	Galician	Komo	Malinke	Russian	Upper Sorbian
Braj Bhasha	Garshuni	Komso	Malayalam	Sadri	Uyghur
Burmese	Garhwali	Kanuri	Reformed	Sanskrit	Uzbek
Bashkir	Ge'ez	Kodagu	Malay	Santali	Venda
Beti	Gilyak	Korean Old Hangul	Mandinka	Sayisi	Vietnamese
Catalan	Gumuz	Konkani	Mongolian	Sekota	Wa
Cebuano	Gondi	Kikongo	Manipuri	Selkup	Wagdi
Chechen	Greenlandic	Komi-Permyak	Maninka	Sango	West-Cree
Chaha Gurage	Garo	Korean	Manx Gaelic	Shan	Welsh
Chattisgarhi	Guarani	Komi-Zyrian	Moksha	Sibe	Wolof
Chichewa	Gujarati	Kpelle	Moldavian	Sidamo	Tai Lue
Chukchi	Haitian	Krio	Mon	Silte Gurage	Xhosa
Chipewyan	Halam	Karakalpak	Moroccan	Skolt Sami	Yakut
Cherokee	Harauti	Karelian	Maori	Slovak	Yoruba
Chuvash	Hausa	Karaim	Maithili	Slavey	Y-Cree
Comorian	Hawaiian	Karen	Maltese	Slovenian	Yi Classic
Coptic	Hammer-Banna	Koorete	Mundari	Somali	Yi Modern
Cree	Hiligaynon	Kashmiri	Naga-Assamese	Samoan	Chinese Hong Kong
Carrier	Hindi	Khasi	Nanai	Sena	Chinese Phonetic
Crimean Tatar	High Mari	Kildin Sami	Naskapi	Sindhi	Chinese Simplified
Church Slavonic	Hindko	Kui	N-Cree	Sinhalese	Chinese Traditional
Czech	Ho	Kulvi	Ndebele	Soninke	Zande
Danish	Harari	Kumyk	Ndonga	Sodo Gurage	Zulu
Dargwa	Croatian	Kurdish	Nepali	Sotho	
Woods Cree	Hungarian	Kurukh	Newari	Albanian	
German	Armenian	Kuy	Nagari	Serbian	

Part IV

Lua \TeX -only font features

11 OpenType font feature files

An OpenType font feature file is a plain text file describing OpenType layout feature of a font in a human-readable format. The syntax of OpenType feature files is defined by Adobe¹³.

Feature files can be used to add or customize OpenType features of a font on the fly without editing the font file itself.

Adding a new OpenType feature is as creating a plain text file defining the new feature and then loading it by passing its name or path to `FeatureFile`, then OpenType features defined in the file can be activated as usual.

For example, when adding one of the default features like `kern` or `liga`, no special activation is needed. On the other hand, an optional feature like `onum` or `smcp` will be activated when old style numbers or small capitals are activated, respectively. However, OpenType feature in the feature file can have any and that can be used to selectively activate the feature; for example defining a ligature feature called `mlig` and then activating it using `RawFeature` option without activating other ligatures in the font.

Figure 1 shows an example feature file. The first two lines set the script and language under which the defined features will be available, which the default language in both default and Latin scripts, respectively.

Then it defines a `liga` feature, which is a glyph substitution feature. The names starting with backslash are glyph names that is to be substituted and while the leading backslash is optional, it is used to escape glyph names when they interfere with preserved keywords. It should also be noted that glyph names are font specific and the same glyph can be named differently in different fonts.

Glyph positioning features like kerning can be defined in a similar way, but instead of the keyword `sub(stitute)` the keyword `pos(ition)` is used instead. Figure 1 shows an example of adding kerning between `AY` and `ay`¹⁴.

Lines starting with `#` are comments and will be ignored.

An OpenType feature file can have any number of features and can have a mix of substitution and positioning features, please refer to the full feature file specification for further documentation.

¹³http://www.adobe.com/devnet/opentype/afdko/topic.feature_file_syntax.html

¹⁴ The kerning is expressed in font design units which are fractions of em depending on the *units per em* value of the font, usually 1000 for PostScript fonts and 2048 for TrueType fonts.

Figure 1: An example font feature file.

```
languagesystem DFLT dflt;
languagesystem latn dflt;

# Ligatures
feature liga {
  sub \f \i by \fi;
  sub \f \l by \fl;
} liga;

# Kerning
feature kern {
  pos \A \Y -200;
  pos \a \y -80;
} kern;
```

Example 40: X_YTeX's Mapping feature.

<code>"iA small amount of—text!"</code>	<code>\fontspec{Cochin}[Mapping=TeX-text]</code>
	<code>^^!`A small amount of---text!''</code>

Part V

Fonts and features with X_YTeX

12 X_YTeX-only font features

The features described here are available for any font selected by `fontspec`.

12.1 Mapping

Mapping enables a X_YTeX text-mapping scheme, shown in Example 40.

Using the `TeX-text` mapping is also equivalent to writing `Ligatures=TeX`. The use of the latter syntax is recommended for better compatibility with LuaTeX documents.

12.2 Letter spacing

Letter spacing, or tracking, is the term given to adding (or subtracting) a small amount of horizontal space in between adjacent characters. It is specified with the `LetterSpace`, which takes a numeric argument, shown in Example 41.

The letter spacing parameter is a normalised additive factor (not a scaling factor); it is defined as a percentage of the font size. That is, for a 10 pt font, a letter spacing parameter of `'1.0'` will add 0.1 pt between each letter.

Example 41: The LetterSpace feature.

```
USE TRACKING FOR DISPLAY CAPS TEXT \fontspec{Didot}
USE TRACKING FOR DISPLAY CAPS TEXT \addfontfeature{LetterSpace=0.0}
USE TRACKING FOR DISPLAY CAPS TEXT USE TRACKING FOR DISPLAY CAPS TEXT \
USE TRACKING FOR DISPLAY CAPS TEXT \addfontfeature{LetterSpace=2.0}
USE TRACKING FOR DISPLAY CAPS TEXT USE TRACKING FOR DISPLAY CAPS TEXT
```

This functionality *should not be used for lowercase text*, which is spacing correctly to begin with, but it can be very useful, in small amounts, when setting small caps or all caps titles. Also see the OpenType uppercase option of the Letters feature ([Section 10.2 on page 26](#)).

12.3 Different font technologies: AAT and OpenType

X_YTeX supports two rendering technologies for typesetting, selected with the `Renderer` font feature. The first, AAT, is that provided (only) by Mac OS X itself. The second, OpenType, is an open source OpenType interpreter.¹⁵ It provides greater support for OpenType features, notably contextual arrangement, over AAT.

In general, this feature will not need to be explicitly called: for OpenType fonts, the OpenType renderer is used automatically, and for AAT fonts, AAT is chosen by default. Some fonts, however, will contain font tables for *both* rendering technologies, such as the Hiragino Japanese fonts distributed with Mac OS X, and in these cases the choice may be required.

Among some other font features only available through a specific renderer, OpenType provides for the `Script` and `Language` features, which allow different font behaviour for different alphabets and languages; see [Section 10.18 on page 37](#) for the description of these features. *Because these font features can change which features are able to be selected for the font instance, they are selected by fontspec before all others and will automatically and without warning select the OpenType renderer.*

12.4 Optical font sizes

Multiple Master fonts are parameterised over orthogonal font axes, allowing continuous selection along such features as weight, width, and optical size (see ?? on page ?? for further details). Whereas an OpenType font will have only a few separate optical sizes, a Multiple Master font's optical size can be specified over a continuous range. Unfortunately, this flexibility makes it harder to create an automatic interface through L^AT_EX, and the optical size for a Multiple Master font must always be specified explicitly.

```
\fontspec{Minion MM Roman}[OpticalSize=11]
MM optical size test \
\fontspec{Minion MM Roman}[OpticalSize=47]
```

¹⁵v2.4: This was called 'ICU' in previous versions of X_YTeX and fontspec. Backwards compatibility is preserved.

```
MM optical size test          \\  
\fontspec{Minion MM Roman}[OpticalSize=71]  
MM optical size test          \\  

```

13 Mac OS X's AAT fonts

Warning! X_YTeX's implementation on Mac OS X is currently in a state of flux and the information contained below may well be wrong from 2013 onwards. There is a good chance that the features described in this section will not be available any more as X_YTeX's completes its transition to a cross-platform-only application.

Mac OS X's font technology began life before the ubiquitous-OpenType era and revolved around the Apple-invented 'AAT' font format. This format had some advantages (and other disadvantages) but it never became widely popular in the font world.

Nonetheless, this is the font format that was first supported by X_YTeX (due to its pedigree on Mac OS X in the first place) and was the first font format supported by fontspec. A number of fonts distributed with Mac OS X are still in the AAT format, such as 'Skia'.

13.1 Ligatures

Ligatures refer to the replacement of two separate characters with a specially drawn glyph for functional or aesthetic reasons. For AAT fonts, you may choose from any combination of Required, Common, Rare (or Discretionary), Logos, Rebus, Diphthong, Squared, AbbrevSquared, and Icelandic.

Some other Apple AAT fonts have those 'Rare' ligatures contained in the Icelandic feature. Notice also that the old TeX trick of splitting up a ligature with an empty brace pair does not work in X_YTeX; you must use a 0 pt kern or \hbox (e.g., \null) to split the characters up if you do not want a ligature to be performed (the usual examples for when this might be desired are words like 'shelffull').

13.2 Letters

The Letters feature specifies how the letters in the current font will look. For AAT fonts, you may choose from Normal, Uppercase, Lowercase, SmallCaps, and InitialCaps.

13.3 Numbers

The Numbers feature defines how numbers will look in the selected font. For AAT fonts, they may be a combination of Lining or OldStyle and Proportional or Monospaced (the latter is good for tabular material). The synonyms Uppercase and Lowercase are equivalent to Lining and OldStyle, respectively. The differences have been shown previously in [Section 7.3 on page 16](#).

Example 42: Contextual glyph for the beginnings and ends of words.

<code>[Contextuals=WordInitial,WordFinal]</code> <i>where is all the veg-</i> <i>emite</i>	<code>\newfontface\fancy{Hoefler Text Italic}</code> <code>[Contextuals={WordInitial,WordFinal}]</code> <code>\fancy where is all the vegemite</code>
---	---

Example 43: A contextual feature for the ‘long s’ can be convenient as the character does not need to be marked up explicitly.

‘Inner’ fwashes can <i>fometimes</i> contain the archaic long s.	<code>\fontspec{Hoefler Text}[Contextuals=Inner]</code> <code>\Inner’ swashes can \emph{sometimes}</code> <code>\\</code> contain the archaic long~s.
---	---

13.4 Contextuals

This feature refers to glyph substitution that vary by their position; things like contextual swashes are implemented here. The options for AAT fonts are `WordInitial`, `WordFinal` (Example 42), `LineInitial`, `LineFinal`, and `Inner` (Example 43, also called ‘non-final’ sometimes). As non-exclusive selectors, like the ligatures, you can turn them off by prefixing their name with `No`.

13.5 Vertical position

The `VerticalPosition` feature is used to access things like subscript (Inferior) and superscript (Superior) numbers and letters (and a small amount of punctuation, sometimes). The `Ordinal` option is (supposed to be) contextually sensitive to only raise characters that appear directly after a number. These are shown in Example 44.

The `realscripts` package (also loaded by `xltxtra`) redefines the `\textsubscript` and `\textsuperscript` commands to use the above font features, including for use in footnote labels.

Example 44: Vertical position for AAT fonts.

Normal ^{superior} _{inferior} 1 st 2 nd 3 rd 4 th 0 th 8 ^{abcde}	<code>\fontspec{Skia}</code> Normal <code>\fontspec{Skia}[VerticalPosition=Superior]</code> Superior <code>\fontspec{Skia}[VerticalPosition=Inferior]</code> Inferior <code>\\</code> <code>\fontspec{Skia}[VerticalPosition=Ordinal]</code> 1 st 2 nd 3 rd 4 th 0 th 8 ^{abcde}
--	--

Example 45: Fractions in AAT fonts. The $\frac{1}{2}$ glyph is the ‘fraction slash’ that may be typed in Mac OS X with `OPT+SHIFT+1`; not shown literally here due to font constraints.

	<code>\fontspec[Fractions=On]{Skia}</code>
	<code>1{^^^2044}2 \quad 5{^^^2044}6 \\ % fraction slash</code>
$\frac{1}{2}$ $\frac{5}{6}$	<code>1/2 \quad 5/6 % regular slash</code>
$\frac{1}{2}$ $\frac{5}{6}$	<code>\fontspec[Fractions=Diagonal]{Skia}</code>
$\frac{13579}{24680}$	<code>13579{^^^2044}24680 \\ % fraction slash</code>
$\frac{13579}{24680}$	<code>\quad 13579/24680 % regular slash</code>

Example 46: Alternate design of pre-composed fractions.

	<code>\fontspec{Hiragino Maru Gothic Pro}</code>
	<code>1/2 \quad 1/4 \quad 5/6 \quad 13579/24680 \\</code>
$\frac{1}{2}$ $\frac{1}{4}$ $\frac{5}{6}$ $\frac{13579}{24680}$	<code>\addfontfeature{Fractions=Alternate}</code>
$\frac{1}{2}$ $\frac{1}{4}$ $\frac{5}{6}$ $\frac{13579}{24680}$	<code>1/2 \quad 1/4 \quad 5/6 \quad 13579/24680</code>

13.6 Fractions

Many fonts come with the capability to typeset various forms of fractional material. This is accessed in `fontspec` with the `Fractions` feature, which may be turned On or Off in both AAT and OpenType fonts.

In AAT fonts, the ‘fraction slash’ or solidus character, is to be used to create fractions. When `Fractions` are turned On, then only pre-drawn fractions will be used. See [Example 45](#).

Using the `Diagonal` option (AAT only), the font will attempt to create the fraction from superscript and subscript characters.

Some (Asian fonts predominantly) also provide for the `Alternate` feature shown in [Example 46](#).

13.7 Variants

The `Variants` feature takes a single numerical input for choosing different alphabetic shapes. Don’t mind my fancy [Example 47](#) :) I’m just looping through the nine (!) variants of Zapfino.

See [Section 14 on page 49](#) for a way to assign names to variants, which should be done on a per-font basis.

13.8 Alternates

Selection of Alternates *again* must be done numerically; see [Example 48](#). See [Section 14 on page 49](#) for a way to assign names to alternates, which should be done on a per-font basis.

Example 47: Nine variants of Zapfino.



```
\newcounter{var}
\whiledo{\value{var}<9}{%
  \edef\1{%
    \noexpand\fontspec[Variant=\thevar,
      Color=0099\thevar\thevar]{Zapfino}}\1%
  \makebox[0.75\width]{d}%
  \stepcounter{var}}
\hspace*{2cm}
```

Example 48: Alternate shape selection must be numerical.

Sphinx Of Black Quartz, JUDGE My Vow
Sphinx Of Black Quartz, JUDGE My Vow

```
\fontspec{Hoefler Text Italic}[Alternate=0]
Sphinx Of Black Quartz, {\scshape Judge My Vow} \
\fontspec{Hoefler Text Italic}[Alternate=1]
Sphinx Of Black Quartz, {\scshape Judge My Vow}
```

13.9 Style

The options of the Style feature are defined in AAT as one of the following: Display, Engraved, IlluminatedCaps, Italic, Ruby,¹⁶ TallCaps, or TitlingCaps.

Typical examples for these features are shown in [Section 10.10](#).

13.10 CJK shape

There have been many standards for how CJK ideographic glyphs are ‘supposed’ to look. Some fonts will contain many alternate glyphs in order to be able to display these glyphs correctly in whichever form is appropriate. Both AAT and OpenType fonts support the following CJKShape options: Traditional, Simplified, JIS1978, JIS1983, JIS1990, and Expert. OpenType also supports the NLC option.

13.11 Character width

See [Section 10.16 on page 37](#) for relevant examples; the features are the same between OpenType and AAT fonts. AAT also allows CharacterWidth=Default to return to the original font settings.

13.12 Vertical typesetting

TODO: improve!

X_YTeX provides for vertical typesetting simply with the ability to rotate the individual glyphs as a font is used for typesetting, as shown in [Example 49](#).

¹⁶‘Ruby’ refers to a small optical size, used in Japanese typography for annotations.

共産主義者は

共 産 主 義 者 ：	<code>\fontspec{Hiragino Mincho Pro}</code>
	<code>\verttext</code>
	<code>\fontspec{Hiragino Mincho Pro}[Renderer=AAT,Vertical=RotatedGlyphs]</code>
	<code>\rotatebox{-90}{\verttext}% requires the graphicx package</code>

No actual provision is made for typesetting top-to-bottom languages; for an example of how to do this, see the vertical Chinese example provided in the \XeTeX documentation.

13.13 Diacritics

Diacritics are marks, such as the acute accent or the tilde, applied to letters; they usually indicate a change in pronunciation. In Arabic scripts, diacritics are used to indicate vowels. You may either choose to Show, Hide or Decompose them in AAT fonts. The Hide option is for scripts such as Arabic which may be displayed either with or without vowel markings. E.g., `\fontspec[Diacritics=Hide]{...}`

Some older fonts distributed with Mac OS X included ‘Ø’ *etc.* as shorthand for writing ‘Ø’ under the label of the Diacritics feature. If you come across such fonts, you’ll want to turn this feature off (imagine typing hello/goodbye and getting ‘helløgoodbye’ instead!) by decomposing the two characters in the diacritic into the ones you actually want. I recommend using the proper \LaTeX input conventions for obtaining such characters instead.

13.14 Annotation

Various Asian fonts are equipped with a more extensive range of numbers and numerals in different forms. These are accessed through the Annotation feature with the following options: Off, Box, RoundedBox, Circle, BlackCircle, Parenthesis, Period, RomanNumerals, Diamond, BlackSquare, BlackRoundSquare, and DoubleCircle.

Part VI

Programming interface

This is the beginning of some work to provide some hooks that use `fontspec` for various macro programming purposes.

Example 50: Assigning new AAT features.

```
\newAATfeature{Alternate}{HoeflerSwash}{17}{1}
\fontspec{Hoefler Text Italic}[Alternate=HoeflerSwash]
This is XeTeX by Jonathan Kew.      This is XeTeX by Jonathan Kew.
```

Example 51: Assigning new arbitrary features.

```
\newfontfeature{AvoidD}{Special=Avoid d-collisions}
\newfontfeature{NoAvoidD}{Special=!Avoid d-collisions}
\fontspec{Zapfino}[AvoidD,Variant=1]
sockdolager rubdown                \
\fontspec{Zapfino}[NoAvoidD,Variant=1]
sockdolager rubdown                \
sockdolager rubdown
```

14 Defining new features

This package cannot hope to contain every possible font feature. Three commands are provided for selecting font features that are not provided for out of the box. If you are using them a lot, chances are I've left something out, so please let me know.

`\newAATfeature` New AAT features may be created with this command:

```
\newAATfeature{<feature>}{<option>}{<feature code>}{<selector code>}
```

Use the X_YTeX file `AAT-info.tex` to obtain the code numbers. See Example 50.

`\newopentypefeature` New OpenType features may be created with this command:

```
\newopentypefeature{<feature>}{<option>}{<feature tag>}
```

The synonym `\newICUfeature` is deprecated.

Here's what it would look like in practise:

```
\newopentypefeature{Style}{NoLocalForms}{-loc1}
```

`\newfontfeature` In case the above commands do not accommodate the desired font feature (perhaps a new X_YTeX feature that `fontspec` hasn't been updated to support), a command is provided to pass arbitrary input into the font selection string:

```
\newfontfeature{<name>}{<input string>}
```

For example, Zapfino contains the feature 'Avoid d-collisions'. To access it with this package, you could do some like that shown in Example 51. (For some reason this feature doesn't appear to be working although `fontspec` is doing the right thing. To be investigated.)

The advantage to using the `\newAATfeature` and `\newopentypefeature` commands instead of `\newfontfeature` is that they check if the selected font actually contains the desired font feature at load time. By contrast, `\newfontfeature` will not give a warning for improper input.

Example 52: Using raw font features directly.

```
PAGELLA SMALL CAPS    \fontspec{texgyrepagella-regular.otf}[RawFeature=+smcp]
                       Pagella small caps
```

Example 53: Renaming font features.

```
Roman Letters And Swash  \aliasfontfeature{ItalicFeatures}{IF}
                          \fontspec{Hoefler Text}[IF = {Alternate=1}]
                          Roman Letters \itshape And Swash
```

15 Going behind fontspec's back

Expert users may wish not to use fontspec's feature handling at all, while still taking advantage of its L^AT_EX font selection conveniences. The RawFeature font feature allows literal X_YL^AT_EX font feature selection when you happen to have the OpenType feature tag memorised.

Multiple features can either be included in a single declaration:

```
[RawFeature=+smcp;+onum]
```

or with multiple declarations:

```
[RawFeature=+smcp, RawFeature=+onum]
```

16 Renaming existing features & options

`\aliasfontfeature` If you don't like the name of a particular font feature, it may be aliased to another with the `\aliasfontfeature{<existing name>}{<new name>}` command, such as shown in Example 53.

Spaces in feature (and option names, see below) *are* allowed. (You may have noticed this already in the lists of OpenType scripts and languages).

`\aliasfontfeatureoption` If you wish to change the name of a font feature option, it can be aliased to another with the command `\aliasfontfeatureoption{}{<existing name>}{<new name>}`, such as shown in Example 54.

This example demonstrates an important point: when aliasing the feature options, the *original* feature name must be used when declaring to which feature the option belongs.

Example 54: Renaming font feature options.

```
Scientific Inferior: 12345  \aliasfontfeature{VerticalPosition}{Vert Pos}
                          \aliasfontfeatureoption{VerticalPosition}{ScientificInferior}{Sci Inf}
                          \fontspec{LinLibertine_R.otf}[Vert Pos=Sci Inf]
                          Scientific Inferior: 12345
```

Only feature options that exist as sets of fixed strings may be altered in this way. That is, Proportional can be aliased to Prop in the Letters feature, but 550099BB cannot be substituted for Purple in a Color specification. For this type of thing, the `\newfontfeature` command should be used to declare a new, *e.g.*, PurpleColor feature:

```
\newfontfeature{PurpleColor}{color=550099BB}
```

Except that this example was written before support for named colours was implemented. But you get the idea.

17 Programming details

17.1 Variables

<code>\l_fontspec_family_tl</code>	In some cases, it is useful to know what the \LaTeX font family of a specific fontspec font is. After a fontspec-like command, this is stored inside the <code>\l_fontspec_family_tl</code> macro. Otherwise, \LaTeX 's own <code>\f@family</code> macro can be useful here, too. The raw \TeX font that is defined from the 'base' font in the family is stored in <code>\l_fontspec_font</code> .
<code>\g_fontspec_encoding_tl</code>	Package authors who need to load fonts with legacy \LaTeX <code>\fontspec</code> commands may also need to know what the default font encoding is. Since this has changed from EU1/EU2 to TU, it is best to use the variables <code>\g_fontspec_encoding_tl</code> or <code>\UTFencname</code> instead.

17.2 Functions for loading new fonts and families

<code>\fontspec_set_family:Nnn</code>	<p>#1 : \LaTeX family #2 : fontspec features #3 : font name</p> <p>Defines a new <code>\fontspec</code> family from given <i>features</i> and <i>font</i>, and stores the family name in the variable <i>family</i>. This font family can then be selected with standard \LaTeX commands <code>\fontfamily{family}\selectfont</code>. See the standard fontspec user commands for applications of this function.</p>
---------------------------------------	--

<code>\fontspec_set_fontface:NNnn</code>	<p>#1 : primitive font #2 : \LaTeX family #3 : fontspec features #4 : font name</p> <p>Variant of the above in which the primitive \TeX font command is stored in the variable <i>primitive font</i>. If a family is loaded (with bold and italic shapes) the primitive font command will only select the regular face. This feature is designed for \LaTeX programmers who need to perform subsequent font-related tests on the <i>primitive font</i>.</p>
--	---

17.3 Functions for querying font families

The following functions in `expl3` syntax may be used for writing code that interfaces with fontspec-loaded fonts. All of the following conditionals also exist with

T and F as well as TF suffixes.

<code>\fontspec_if_fontspec_font:TF</code>	Test whether the currently selected font has been loaded by fontspec.
<code>\fontspec_if_aat_feature:nnTF</code>	Test whether the currently selected font contains the AAT feature (#1,#2).
<code>\fontspec_if_opentype:TF</code>	Test whether the currently selected font is an OpenType font. Always true for Lua \TeX fonts.
<code>\fontspec_if_feature:nTF</code>	Test whether the currently selected font contains the raw OpenType feature #1. E.g.: <code>\fontspec_if_feature:nTF {pnum} {True} {False}</code> . Returns false if the font is not loaded by fontspec or is not an OpenType font.
<code>\fontspec_if_feature:nnnTF</code>	Test whether the currently selected font with raw OpenType script tag #1 and raw OpenType language tag #2 contains the raw OpenType feature tag #3. E.g.: <code>\fontspec_if_feature:nTF {latn} {ROM} {pnum} {True} {False}</code> . Returns false if the font is not loaded by fontspec or is not an OpenType font.
<code>\fontspec_if_script:nTF</code>	Test whether the currently selected font contains the raw OpenType script #1. E.g.: <code>\fontspec_if_script:nTF {latn} {True} {False}</code> . Returns false if the font is not loaded by fontspec or is not an OpenType font.
<code>\fontspec_if_language:nTF</code>	Test whether the currently selected font contains the raw OpenType language tag #1. E.g.: <code>\fontspec_if_language:nTF {ROM} {True} {False}</code> . Returns false if the font is not loaded by fontspec or is not an OpenType font.
<code>\fontspec_if_language:nnTF</code>	Test whether the currently selected font contains the raw OpenType language tag #2 in script #1. E.g.: <code>\fontspec_if_language:nnTF {cyr1} {SRB} {True} {False}</code> . Returns false if the font is not loaded by fontspec or is not an OpenType font.
<code>fontspec_if_current_script:nTF</code>	Test whether the currently loaded font is using the specified raw OpenType script tag #1.
<code>fontspec_if_current_language:nTF</code>	Test whether the currently loaded font is using the specified raw OpenType language tag #1.

Part VII

The ‘improvement’ of \LaTeX 2 ϵ and other packages

This part of the package code contains patches to various \LaTeX components and third-party packages to improve the default behaviour.

18 Verbatim

Many verbatim mechanisms assume the existence of a ‘visible space’ character that exists in the ASCII space slot of the typewriter font. This character is known in Unicode as U+2423: BOX OPEN, which looks like this: ‘`␣`’.

When a Unicode typewriter font is used, \LaTeX no longer prints visible spaces for the `verbatim*` environment and `\verb*` command. This problem is fixed by using the correct Unicode glyph, and the following packages are patched to do the same: `listings`, `fancyvrb`, `moreverb`, and `verbatim`.

In the case that the typewriter font does not contain ‘`’`’, the Latin Modern Mono font is used as a fallback.

19 Discretionary hyphenation: `\-`

\LaTeX defines the macro `\-` to insert discretionary hyphenation points. However, it is hard-coded in \LaTeX to use the hyphen `-` character. Since `fontspec` makes it easy to change the hyphenation character on a per font basis, it would be nice if `\-` adjusted automatically — and now it does.

20 Commands for old-style and lining numbers

`\oldstylenums` \LaTeX ’s definition of `\oldstylenums` relies on strange font encodings. We provide a `fontspec`-compatible alternative and while we’re at it also throw in the reverse option as well. Use `\oldstylenums{<text>}` to explicitly use old-style (or lowercase) numbers in `<text>`, and the reverse for `\liningnums{<text>}`.

Part VIII

Implementation

21 Loading

The `expl3` module is `fontspec`.

```
1 <@@=fontspec>
```

Check engine and load specific modules. For $\text{Lua}\TeX$, load `luaotfload`.

```
2 <{*load}>
3 \sys_if_engine luatex:T
4 { \RequirePackage{luaotfload}
5   \directlua{require("fontspec")}}
6   \RequirePackageWithOptions{fontspec-luatex} \endinput }
7 \sys_if_engine xetex:T
8 { \RequirePackageWithOptions{fontspec-xetex} \endinput }
```

If not one of the above, error:

```
9 \msg_new:nnn {fontspec} {cannot-use-pdfTeX}
10 {
11   The~ fontspec~ package~ requires~ either~ XeTeX~ or~ LuaTeX.\\
12   You~ must~ change~ your~ typesetting~ engine~ to,~ e.g.,~ "xelatex"~ or~ "lualatex"~ instead~ of~ pl
13 }
14 \msg_fatal:nn {fontspec} {cannot-use-pdfTeX}
15 \endinput
```

16 </load>

Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

Symbols	
\-	1124, <u>2754</u>
\@@_DeclareFontShape:nnnnn	976, 984
\@@_DeclareFontShape:xxxxxx	957, 965, 993
\@@_add_nfsfont:nnnn	795–800, 1624, <u>1627</u>
\@@_aff_error:n	1377, 1686, 1727, 1766
\@@_alias_font_feature:nnn	373, 381
\@@_calc_scale:n	1645, 1646, <u>1651</u>
\@@_combo_sc_shape:n	966, 969, 1013, 1021
\@@_declare_shape:nnnn	<u>885</u>
\@@_declare_shape:nxxx	873
\@@_declare_shape_loginfo:nn	935, 997
\@@_declare_shape_slanted:nn	934, 985
\@@_declare_shapes_normal:nn	932, 955
\@@_declare_shapes_smcaps:nn	933, 961
\@@_define_feature_option:nnnn	349, 357, <u>1207</u> , 1944–1967, 1981–1990, 1992–1999, 2002, 2005–2018, 2020–2030, 2032–2036, 2038, 2040–2046, 2048–2051, 2096–2106, 2110–2116, 2118–2137
\@@_define_font_feature:n	346, 354, <u>1207</u> , 1943, 1980, 1991, 2004, 2019, 2031, 2039, 2047, 2052, 2063, 2074, 2095, 2109, 2117, 2138
\@@_error:n	898, 2490, 2856
\@@_error:nx 677, 883, 1380, 1739, 1763, 2857
\@@_extract_all_features:n	594, 632
\@@_extract_features:	<u>632</u>
\@@_find_autofonts:	605, <u>772</u>
\@@_font_gset:Nnn	134, 679
\@@_font_if_null:N	122
\@@_font_if_null:NT	677, 883
\@@_font_set:Nnn 130, 412, 431, 444, 472, 489, 504, 523, 540, 557, 675, 862, 863, 882
\@@_font_suppress_not_found_error: 117, 586
\@@_fontspec:nn	155, 157
\@@_fontwrap:n	106, 132, 136, 947
\@@_fullname:n 676, 680, <u>694</u> , 763, 862, 863, 882, 949
\@@_get_features:Nn	599, 941, <u>1054</u>
\@@_if_autofont:nn	860
\@@_if_autofont:nnTF	852
\@@_if_detect_external:VT	661
\@@_if_detect_external:n	683
\@@_if_detect_external:nT	693
\@@_if_detect_external:nnT	<u>683</u>
\@@_info:n	717, 1662, 2607, 2861
\@@_info:nx	854, 2862
\@@_info:nxx	608, 2863
\@@_init:	587, <u>1075</u>
\@@_int_mult_truncate:Nn	<u>54</u> , 1801
\@@_keys_define_code:nnn 1373, 1379, 1383, 1394, 1434, 1439, 1445, 1450, 1454, 1460, 1486, 1497, 1501, 1505, 1509, 1527, 1531, 1538, 1542, 1546, 1550, 1554, 1561, 1566, 1572, 1576, 1580, 1584, 1588, 1592, 1596, 1604, 1641, 1681, 1707, 1728, 1732, 1736, 1767, 1798, 1813, 1830, 1834, 1838, 1842, 2468, 2473
\@@_load_external_fontoptions:Nn 593, <u>621</u> , 879
\@@_load_font:	597, <u>673</u>
\@@_load_fontname:n	872, 877, 901, 922
\@@_make_font_shapes:Nnnnn	807, <u>868</u>
\@@_make_smallcaps:TF	912, <u>1130</u>
\@@_namewrap:n	696, 1106, 1388
\@@_newfontface:Nnn	253, 255
\@@_newfontfamily:Nnn	237, 239
\@@_pass_args:nnn	146, 155, 165, 175, 185, 199, 207, 215, 223, 237, 253
\@@_post_arg:w	149, 152
\@@_preparse_features:	595, <u>659</u>
\@@_primitive_font_gset:Nnn	112, 136
\@@_primitive_font_set:Nnn	107, 132
\@@_sanitise_fontname:Nn	279, <u>295</u> , 623
\@@_save_family:n	730
\@@_save_family:nTF	602, <u>730</u>
\@@_save_fontinfo:	604, 756
\@@_save_fontinfo:nn	<u>756</u>
\@@_set_autofont:Nnn 776–778, 783, 788, 791, <u>843</u>
\@@_set_default_features:nn	264, 268
\@@_set_faces:	607, <u>793</u>
\@@_set_faces_aux:nnnn	802, 804

<code>\@@_set_font_default_features:nnn</code> .	<code>\addfontfeatures</code>
.
<code>\@@_set_font_dimen:NnN</code> 1655, 1656, <u>1665</u>	<code>\advance</code>
<code>\@@_set_font_type:</code>	<code>\aliasfontfeature</code>
473, 490, 505, 524, 541, 558, 678, <u>809</u>	<code>\aliasfontfeatureoption</code>
<code>\@@_set_scriptlang:</code>	<code>\AtBeginDocument</code>
<code>\@@_setboldmathrm:nn</code>	
<code>\@@_setmainfont:nn</code>	B
<code>\@@_setmathrm:nn</code>	<code>\bar</code>
<code>\@@_setmathsf:nn</code>	<code>\bfdefault</code>
<code>\@@_setmathtt:nn</code>
<code>\@@_setmonofont:nn</code>
<code>\@@_setsansfont:nn</code>
<code>\@@_setup_nfss:Nnn</code>	<code>\bgroup</code>
<code>\@@_shape_merge:nn</code>	<code>\bool_if:NF</code>
971, 972, 2690–2698, 2703, 2707, 2710
<code>\@@_trace:n</code>
<code>\@@_update_featstr:n</code> 339, 1070, <u>1152</u> ,	<code>\bool_if:nF</code>
1181, 1193, 1202, 1734, 1816, 1832,
1836, 1840, 1852, 1871, 1879,	<code>\bool_if:NT</code>
1888, 1973, 1976, 2155, 2158, 2475
<code>\@@_warning:n</code>	<code>\bool_if:nT</code>
1189, 1823, 1827, 1858, 1896, 2858
<code>\@@_warning:nx</code>	<code>\bool_if:NTF</code>
1195, 1204, 1414, 1419, 1781, 1792,
1805, 2177, 2181, 2246, 2462, 2859	<code>\bool_if:nTF</code>
<code>\@@_warning:nxx</code>
<code>\@sverb</code>	<code>\bool_new:N</code>
<code>\@ifpackageloaded</code>	<code>\bool_set_false:N</code>
.
2477, 2486, 2493–2495,
2575, 2579–2587, 2591–2593,
2597–2604, 2804, 2820, 2834, 2841
<code>\@ifstar</code>	<code>\bool_set_true:N</code>
<code>\@makeother</code>
<code>\@noligs</code>
<code>\@nomath</code>
<code>\@onlypreamble</code>	<code>\bool_until_do:nn</code>
<code>\@sverb</code>
<code>\@sxverbatim</code>	<code>\breve</code>
<code>\@tempa</code>	
<code>\@verb</code>	C
<code>\@verbatim</code>	<code>\c_colon_str</code>
<code>\ 11, 1012, 1026, 2867, 2875, 2876, 2929–</code>	<code>\c_empty_tl</code>
2931, 2942, 2978, 2995, 3004,	<code>\c_minus_one</code>
3010–3012, 3033, 3038, 3044–3046	<code>\c_one</code>
<code>__dim_eval:w</code>	<code>\c_zero</code>
<code>__dim_eval_end:</code>	<code>\char</code>
<code>_fontspec_parse_wordspace:w</code> 1684, <u>1687</u>	<code>\char_set_catcode_active:n</code>
	<code>\check</code>
A	<code>\clist_clear:N</code>
<code>\acute</code>	<code>\clist_count:N</code>
<code>\addfontfeature</code>	<code>\clist_count:n</code>
.	
332, 2848, 2852, 2928	

<code>\clist_map_break:</code>	305, 689, 2172	<code>\cyrillicencoding</code>	92, 96
<code>\clist_map_inline:Nn</code>	299, 685	D	
<code>\clist_map_inline:nn</code>	275, 365, 891, 2058, 2069, 2087, 2166, 2738	<code>\ddot</code>	2500
<code>\clist_new:N</code>	259	<code>\DeclareDocumentCommand</code>	164, 174, 184, 198, 206, 214, 222, 236, 252, 261, 310, 333, 343, 351, 361, 387, 389, 393, 397
<code>\clist_put_left:Nn</code>	915	<code>\DeclareFontFamily</code>	606
<code>\clist_put_right:Nn</code> 270, 1564, 1906, 1928		<code>\DeclareFontsExtensions</code>	<u>397</u>
<code>\clist_put_right:Nx</code> 1912, 1914, 1934, 1936		<code>\DeclareFontShape</code>	982
<code>\clist_set:Nn</code>	270, 399, 1031, 1097, 1529, 1533, 1540, 1544, 1548, 1552, 1558, 1563, 1568, 1632	<code>\DeclareMathAccent</code>	2498–2507
<code>\clist_set:Nx</code>	636, 646	<code>\DeclareMathDelimiter</code>	2545–2549
<code>\clist_set_eq:NN</code>	905	<code>\DeclareMathSymbol</code>	2511, 2516–2519, 2522–2544, 2550
<code>\colon</code>	2510, 2511	<code>\DeclareOption</code>	59, 61–67, 72
<code>\color@</code>	1769	<code>\DeclareRobustCommand</code>	244, 2684, 2713, 2718, 2723, 2728, 2744, 2754
<code>\convertcolorspec</code>	1771	<code>\DeclareSymbolFont</code>	2496, 2553
<code>\cs:w</code>	278	<code>\DeclareSymbolFontAlphabet</code>	2555
<code>\cs_end:</code>	278	<code>\DeclareTextFontCommand</code>	2689, 2750
<code>\cs_generate_variant:Nn</code>	47–53, 575, 693, 843, 937, 984, 1030, 1151, 1173, 1206, 1271, 1458, 1459, 1526	<code>\def</code>	2765, 2786, 2794
<code>\cs_gset:Npn</code>	2781	<code>\defaultfontfeatures</code>	<u>259</u>
<code>\cs_if_exist:cF</code>	737	<code>\define@antt@mathversions</code>	2577
<code>\cs_if_exist:cTF</code>	405, 743, 753, 1769	<code>\define@iwona@mathversions</code>	2589
<code>\cs_if_exist:NT</code>	733	<code>\define@kurier@mathversions</code>	2595
<code>\cs_if_exist_p:c</code>	2704	<code>\Delta</code>	2533
<code>\cs_new:Nn</code>	54, 130, 134, 146, 157, 167, 177, 187, 201, 209, 217, 225, 239, 255, 268, 273, 295, 569, 576, 621, 632, 659, 673, 700, 756, 772, 793, 804, 809, 844, 868, 877, 885, 939, 955, 961, 969, 976, 985, 997, 1149, 1152, 1159, 1174, 1186, 1207, 1211, 1218, 1373, 1377, 1627, 1651, 1665, 2163, 2237, 2573, 2690, 2699, 2766, 2772	<code>\dim_compare:nNnT</code>	1668
<code>\cs_new:Npn</code>	23, 24, 2077, 2856–2864	<code>\dim_new:N</code>	41–43
<code>\cs_new_protected:Nn</code>	1198	<code>\dim_set:Nn</code>	1667
<code>\cs_new_protected:Npn</code>	2735	<code>\dim_to_fp:n</code>	1659, 1660
<code>\cs_set:cpn</code>	2741, 2806, 2812, 2821	<code>\directlua</code>	5, 1303, 1329, 1363
<code>\cs_set:Nn</code> 106, 381, 583, 694, 1054, 1130, 1135, 1257, 1272, 1520, 2062, 2484		<code>\discretionary</code>	2756
<code>\cs_set:Npn</code>	45, 46, 102, 107, 112, 117, 1102, 1106, 1261, 1388, 1687, 1786, 2613, 2751, 2752, 2802, 2818, 2823, 2832, 2839	<code>\do</code>	2790
<code>\cs_set_eq:cN</code>	735	<code>\dospecials</code>	2790
<code>\cs_set_eq:NN</code>	101, 104, 193, 332, 359, 1146, 1148, 2783, 2836, 2843	<code>\dot</code>	2506
<code>\cs_to_str:N</code>	241, 246, 278	E	
<code>\cs_undefine:c</code>	980, 1599, 1601	<code>\else</code>	126, 1267, 1268, 1294, 1320, 1354, 2760, 2788
		<code>\else:</code>	142
		<code>\em</code>	<u>2733</u>
		<code>\emfontdeclare</code>	<u>2733</u>
		<code>\emminnershape</code>	<u>2733</u>
		<code>\emph</code>	<u>2733</u>
		<code>\emshape</code>	<u>2733</u>
		<code>\endinput</code>	6, 8, 15
		environments:	
		<code>listingcont*</code>	<u>2818</u>
		<code>verbatim*</code>	<u>2802</u>
		<code>\etex_iffontchar:D</code>	140
		<code>\ExecuteOptions</code>	77

\exp_after:wN	896	\fontspec_define_numbered_feat:nnnn	1207, 2107, 2108
\exp_args:No	628	\fontspec_if_aat_feature:nn	407
\exp_args:NV	1115	\fontspec_if_aat_feature:nnTF	1, 407
\exp_args:Nx	891	\fontspec_if_current_language:n	552
\exp_not:N	244, 246–248, 321, 1001, 1013, 1026, 2077, 2078, 2081, 2089, 2090	\fontspec_if_current_language:nTF	1, 552
\exp_not:n	1012	\fontspec_if_current_script:n	535
		\fontspec_if_current_script:nTF	1, 535
		\fontspec_if_feature:n	439
		\fontspec_if_feature:nnn	467
		\fontspec_if_feature:nnTF	1, 467
		\fontspec_if_feature:nTF	1, 439
		\fontspec_if_fontspec_font:	403
		\fontspec_if_fontspec_font:TF	1, 312, 403, 409, 428, 441, 469, 486, 501, 520, 537, 554
		\fontspec_if_language:n	499
		\fontspec_if_language:nn	518
		\fontspec_if_language:nnTF	1, 518
		\fontspec_if_language:nTF	1, 499
		\fontspec_if_opentype:	426
		\fontspec_if_opentype:TF	1, 426
		\fontspec_if_script:n	484
		\fontspec_if_script:nTF	1, 484
		\fontspec_iv_str_to_num:Nn	476, 477, 528, 1257, 1285, 1310
		\fontspec_iv_str_to_num:No	1279
		\fontspec_iv_str_to_num:w	1259, 1261
		\fontspec_make_AAT_feature:nn	1166, 1174
		\fontspec_make_AAT_feature_string:nn	1226
		\fontspec_make_AAT_feature_string:nnTF	415, 1141, 1179, 1226
		\fontspec_make_feature:nnn	1159, 1215, 2154
		\fontspec_make_feature:nnx	2059, 2070, 2144
		\fontspec_make_numbered_feature:nn	1198, 1206, 1223
		\fontspec_make_numbered_feature:xn	2080
		\fontspec_make_OT_feature:n	1163, 1171, 1186
		\fontspec_make_ot_smallcaps:TF	1130, 1138, 1146
		\fontspec_maybe_setup_maths:	2573
		\fontspec_merge_shape:n	2699, 2716, 2721, 2726, 2731
		\fontspec_new_lang:nn	395, 2237
		\fontspec_new_script:nn	391, 2163
		\fontspec_parse_colour:viii	1778, 1786
F			
\f@encoding	2706		
\f@family	159, 316, 317, 405, 411, 430, 443, 448, 451, 454, 455, 471, 488, 503, 508, 510, 522, 539, 544, 556, 561, 2706		
\f@series	2706, 2775		
\f@shape	2703, 2707, 2710, 2775		
\f@size	412, 431, 444, 472, 489, 504, 523, 540, 557, 676, 680, 862, 863, 882, 980		
\FancyVerbSpace	2836		
\fi	128, 823, 826, 1267, 1268, 1296, 1322, 1356, 2512, 2577, 2589, 2595, 2762, 2788		
\fi:	144		
\file_if_exist:nF	80		
\file_if_exist:nT	628		
\file_input:n	629		
\font	109, 114, 1655, 1672, 1693–1695, 1701–1703, 1714, 1719, 1724, 1744, 1754, 1758, 2758, 2761, 2768		
\font_glyph_if_exist:Nn	138		
\font_glyph_if_exist:NnTF	138, 1750, 2768		
\fontdimen	1667, 1693– 1695, 1701–1703, 1714, 1719, 1724		
\fontencoding	160, 247		
\fontfamily	246, 325		
\fontname	864		
\fontshape	2687, 2710, 2711		
\fontspec	154		
\fontspec_check_lang:n	1307		
\fontspec_check_lang:nTF	512, 529, 1307, 2240, 2450, 2456		
\fontspec_check_ot_feat:n	1336		
\fontspec_check_ot_feat:nT	1336		
\fontspec_check_ot_feat:nTF	457, 478, 1132, 1191, 1200, 1336		
\fontspec_check_script:n	1282		
\fontspec_check_script:nTF	493, 706, 1282, 2168, 2175		
\fontspec_complete_fontname:Nn	806, 1452, 1456, 1468, 1494, 1499, 1503, 1507, 1517, 1520, 1590		

<code>\fontspec_parse_cv:w</code>	2077, 2089	<code>\g_@_opacity_tl</code>	
<code>\fontspec_patch_fancyvrb:</code> . . .	2799, 2832	. 1058, 1068, 1099, 1101, 1789, 1802	
<code>\fontspec_patch_listings:</code> . . .	2800, 2839	<code>\g_@_pkg_euler_loaded_bool</code>	
<code>\fontspec_patch_moreverb:</code> . . .	2798, 2818 32, 2479, 2482, 2488	
<code>\fontspec_patch_verbatim:</code> . . .	2797, 2802	<code>\g_@_postadjust_tl</code>	1060, 1095
<code>\fontspec_print_visible_spaces:</code> . . .		<code>\g_@_rmfamily_family</code>	1117
. 2779, 2794, 2808, 2814, 2828		<code>\g_@_sffamily_family</code>	1118
<code>\fontspec_salt:n</code>	2059, 2062	<code>\g_@_ttfamily_family</code>	1119
<code>\fontspec_select:nn</code>		<code>\g_fontspec_encoding_tl</code>	79, 83,
. 321, 572, 579, 583, 2615		84, 89, 90, 92, 93, 96, 97, 1111,	
<code>\fontspec_set:Nnn, \fontspec_gset:Nnn</code>		2553, 2554, 2556–2560, 2563,	
.	130	2566–2568, 2570, 2571, 2612, 2775	
<code>\fontspec_set_family:cnn</code>	241	<code>\Gamma</code>	2532
<code>\fontspec_set_family:Nnn</code> . . .	1, 159,	<code>\global</code>	114, 2825
169, 179, 189, 203, 211, 219, 227, 569		<code>\grave</code>	2499
<code>\fontspec_set_fontface:NNnn</code>	1, 576	<code>\group_begin:</code>	314,
<code>\fontspec_setup_maths:</code>	2477, 2608	585, 870, 978, 1653, 2508, 2779, 2808	
<code>\fontspec_tmp:</code>	101, 104	<code>\group_end:</code>	
<code>\fontspec_v_str_to_num:Nn</code> . . .	1257, 1345	324, 619, 874, 981, 1663, 2513, 2785	
<code>\fontspec_visible_space:</code>			
. 2766, 2783, 2836, 2843		H	
<code>\fontspec_visible_space:@fallback</code> 2772		<code>\hat</code>	2505
<code>\fontspec_visible_space_fallback:</code> .		<code>\hbox</code>	2788
. 2770, 2772		<code>\hyphenchar</code>	1744, 1754, 1758, 2758, 2761
<code>\FontspecSetCheckBoolFalse</code> . . .	24, 2643		
<code>\FontspecSetCheckBoolTrue</code>	23, 2642	I	
<code>\fp_eval:n</code>	1659	<code>\IfBooleanTF</code>	270, 281
<code>\fp_new:N</code>	39, 40	<code>\ifcase</code>	817
		<code>\ifmmode</code>	2788
G		<code>\IfNoValueTF</code>	148, 263
<code>\g_@_bf_series_seq</code> 1444, 1448, 1470, 1473		<code>\ifnum</code>	821, 1291, 1317, 1350, 2758
<code>\g_@_bfmathrm_tl</code>		<code>\ifx</code> 124, 1267, 1268, 2510, 2577, 2589, 2595	
. 195, 211, 2561, 2566–2568		<code>\ignorespaces</code>	162, 171, 181, 191, 266, 330
<code>\g_@_cfg_bool</code>	33, 63, 64, 2619	<code>\InputIfFileExists</code>	2621
<code>\g_@_curr_series_tl</code>	1110,	<code>\int_case:nnn</code>	1673
1447, 1472, 1475, 1478, 1481, 1536		<code>\int_compare:nT</code>	1609, 1809
<code>\g_@_default_fontopts_clist</code>		<code>\int_compare:nTF</code>	
. 259, 271, 648	 1232, 1408, 1774, 1777, 2932	
<code>\g_@_euenc_bool</code>	35, 65, 66, 80, 81, 99	<code>\int_compare_p:nNn</code>	1289, 1315, 1348
<code>\g_@_fontopts_prop</code>	260,	<code>\int_gincr:c</code>	744
283, 286, 290, 291, 626, 639, 642, 880		<code>\int_if_even:nTF</code>	1237
<code>\g_@_hexcol_tl</code>	1059, 1068, 1098, 1100	<code>\int_incr:N</code>	1295, 1321, 1355, 2740, 2747
<code>\g_@_math_bool</code>		<code>\int_new:c</code>	745
. 34, 61, 62, 2577, 2579–2586,		<code>\int_new:N</code>	36–38, 1797, 2733, 2734
2589, 2591, 2592, 2595, 2597–2605		<code>\int_set:Nn</code>	
<code>\g_@_math_euler_bool</code>	30, 2489, 2514	48, 56, 449, 452, 509, 1124, 1263,	
<code>\g_@_math_lucida_bool</code>		1286, 1293, 1311, 1319, 1339, 1353,	
. 31, 2493–2495, 2520		1759, 1800, 2171, 2243, 2452, 2458	
<code>\g_@_mathrm_tl</code>	194, 203, 233,	<code>\int_set_eq:NN</code>	119
2553, 2554, 2556, 2557, 2560, 2563		<code>\int_to_hex:n</code>	1810
<code>\g_@_mathsf_tl</code>	196, 219, 234, 2558, 2570	<code>\int_use:c</code>	749
<code>\g_@_mathtt_tl</code>	197, 227, 235, 2559, 2571	<code>\int_use:N</code>	2741, 2748

\int_zero:N	1125–1127, 1287, 1313, 1346, 2471, 2737	\l_@_fontdef_tl	411, 412, 430, 431, 443, 444, 471, 472, 488, 489, 503, 504, 522, 523, 539, 540, 556, 557
\itdefault	797, 799, 989, 990, 994, 1005, 1007, 2556, 2563, 2568, 2682, 2691, 2693, 2695, 2716	\l_@_fontfeat_bf_clist	796, 1085, 1533, 1928
\itscdefault	1017, 1018, 2682, 2687, 2691, 2693, 2695–2697	\l_@_fontfeat_bfit_clist	799, 1087, 1544, 1912, 1914, 1934, 1936
\itshape	2713, 2751	\l_@_fontfeat_bfsl_clist	800, 1089, 1552
K		\l_@_fontfeat_clist	671, 1064
\keys_define:nn	335, 383, 388, 1209, 1213, 1220, 1375, 1403, 1867, 1875, 1884, 1894, 1899, 1921, 1968, 2053, 2064, 2083, 2139, 2147, 2162, 2165, 2236, 2239, 2446	\l_@_fontfeat_curr_clist	905, 915, 927
\keys_if_choice_exist:nnnT	347, 355	\l_@_fontfeat_it_clist	797, 1086, 1540, 1906
\keys_if_exist:nnF	345, 353	\l_@_fontfeat_sc_clist	905, 1090, 1558
\keys_if_exist:nnT	370	\l_@_fontfeat_sl_clist	798, 1088, 1548
\keys_set:nn	49, 304, 384, 662, 1390, 1399, 1436, 1441, 1825, 2178, 2247, 2463	\l_@_fontfeat_up_clist	795, 1084, 1529, 1564
\keys_set:nx	713, 714, 725, 726, 1066	\l_@_fontid_tl	610, 616, 654, 656, 735, 737, 747, 752, 1599
\keys_set_known:nnN	50, 315	\l_@_fontname_tl	317, 322
\keys_set_known:noN	1633	\l_@_fontopts_clist	639, 640, 650, 873, 880, 881
\keys_set_known:nxN	664, 668, 670, 871, 896, 1064	\l_@_graphite_bool	29, 816
L		\l_@_hexcol_tl	1059, 1067, 1070, 1771, 1775, 1788
\l_@@_addfontfeatures_bool	1738	\l_@_keys_leftover_clist	666, 668–670, 1065, 1066
\l_@@_alias_bool	360, 363, 372, 377	\l_@_lang_name_tl	709, 711, 714, 721, 723, 726, 1093, 1442, 2968
\l_@@_all_features_clist	636, 646, 654, 665, 760, 3010	\l_@_leftover_clist	871, 873
\l_@@_arg_tl	1606, 1607, 1609, 1614, 1619	\l_@@_mm_bool	28, 815, 822, 1850, 1855
\l_@@_atsui_bool	26, 413, 813, 820, 829, 1140, 1165	\l_@@_nfss_enc_tl	160, 247, 606, 957, 965, 993, 1111, 1594
\l_@@_basename_tl	591, 661, 759, 1523	\l_@@_nfss_fam_tl	733, 735, 1598
\l_@@_curr_bfname_tl	1468, 1476, 1478, 1481, 1536	\l_@@_nfss_prop	1480, 1485, 1535
\l_@@_curr_fontname_tl	806, 807	\l_@@_nfss_sc_tl	888, 927, 966, 1023
\l_@@_disable_defaults_bool	309, 318, 634	\l_@@_nfss_tl	887, 902, 958, 1011
\l_@@_em_int	2733, 2747, 2748	\l_@@_nfssfont_prop	802, 1603, 1637
\l_@@_emdef_int	2734, 2737, 2740, 2741	\l_@@_nobf_bool	19, 774, 781, 1385, 1464, 1467, 1930
\l_@@_ext_filename_tl	624, 625, 628, 629	\l_@@_noit_bool	20, 774, 786, 1386, 1490, 1493, 1908
\l_@@_extension_tl	696, 1396, 1402	\l_@@_nosc_bool	21, 907, 919, 925, 963, 1513, 1516
\l_@@_extensions_clist	299, 399, 400, 685	\l_@@_opacity_tl	1058, 1067, 1070, 1789, 1794, 1802, 1807
\l_@@_external_bool	846, 1382, 1387, 1397	\l_@@_optical_size_tl	698, 1107, 1847, 1864
\l_@@_family_fontopts_clist	642, 643, 649	\l_@@_options_tl	316, 322
\l_@@_family_label_tl	571, 578, 642, 644, 1075, 1115, 1117–1119	\l_@@_ot_bool	27, 433, 446, 474, 491, 506, 525,
\l_@@_firsttime_bool	18, 600, 702, 1105, 1154, 1556, 1683, 1780, 1791, 1804, 1857, 1903, 1925		

542, 559, 814, 825, 832, 840, 1034, 1104, 1137, 1162, 1845, 1855, 2152	\l_fontspec_font
\l_@@_postadjust_tl . . . 958, 966, 994, 1024, 1026, 1060, 1730, 1743, 1752	. . . 412, 431, 444, 472, 489, 504, 523, 540, 557, 580, 675, 677, 679, 681, 817, 821, 882, 883, 1228, 1232, 1234, 1239, 1244, 1286, 1291, 1312, 1317, 1341, 1350, 1656, 1750, 2617
\l_@@_pre_feat_sclist . . . 764, 950, 1031	\l_fontspec_fontname_bf_tl
\l_@@_punctspace_adjust_tl 777, 783, 796, 1076, 1476, 1929
. 1062, 1095, 1713, 1718, 1723	\l_fontspec_fontname_bfit_tl
\l_@@_rawfeatures_sclist 776–778, 799, 1080, 1499, 1915, 1937
. 599, 764, 941, 950, 1056, 1073, 1156	\l_fontspec_fontname_bfsl_tl
\l_@@_saved_fontname_tl 889, 894 791, 800, 1082, 1507
\l_@@_scale_tl	\l_fontspec_fontname_it_tl
. . . 946, 1057, 1648, 1649, 1657, 3021 776, 788, 797, 1077, 1494, 1907
\l_@@_script_name_tl 704, 708, 713, 725, 1091, 1437, 2968, 2978	\l_fontspec_fontname_sc_tl
\l_@@_size_tl 893, 898, 946, 1586 909, 922, 1083, 1517
\l_@@_sizedfont_tl 894, 901, 1590	\l_fontspec_fontname_sl_tl
\l_@@_sizefeat_clist 791, 798, 1081, 1503
. 1097, 1563, 1568, 1632, 1638	\l_fontspec_fontname_tl
\l_@@_sizing_leftover_clist . . 897, 942 589, 593, 639, 654, 667, 763, 778, 783, 788, 795, 879, 880, 882, 889, 949, 1907, 1915, 1929, 1937, 2888, 2942, 2947, 2952, 2957, 2962, 2967, 2972, 2977, 3021, 3029
\l_@@_tfm_bool 25, 812, 818	\l_fontspec_fontname_up_tl
\l_@@_this_feat_tl . . . 1607, 1620, 1625	. . . 590, 667, 676, 677, 680, 1452, 1456
\l_@@_this_font_tl 1569, 1570, 1574, 1608, 1619, 1625, 1629, 1635, 1638	\l_fontspec_hyphenchar_tl
\l_@@_tmp_int 1797, 1800, 1801, 1809, 1810 1748–1750, 1754, 1759
\l_@@_tmp_tl 278, 279, 283, 286, 290, 291, 315, 448, 449, 451, 452, 508, 509, 544, 545, 561, 562, 740, 741, 743–745, 749, 1633	\l_fontspec_lang_tl
\l_@@_tmpa_bool 687, 689, 691 455, 769, 1039, 1050, 1094, 1367, 2242, 2453, 2459, 2470
\l_@@_tmpa_dim 41, 1655, 1659	\l_fontspec_language_int
\l_@@_tmpa_fp 39 37, 452, 477, 767, 1343, 1350, 2243, 2452, 2458, 2471
\l_@@_tmpb_dim 42, 1656, 1660	\l_fontspec_mode_tl . . . 1046, 1123, 1422
\l_@@_tmpb_fp 40	\l_fontspec_renderer_tl
\l_@@_tmpb_tl 283–286 697, 827, 830, 833, 1108, 1410
\l_@@_tmpc_dim 43	\l_fontspec_script_int
\l_@@_wordspace_adjust_tl 36, 449, 476, 509, 528, 766, 1312, 1317, 1342, 1350, 2171
. 1061, 1095, 1691, 1699	\l_fontspec_script_tl
\l_@_fontspec_check_bool . . . 22–24, 1288, 1292, 1298, 1304, 1314, 1318, 1324, 1333, 1347, 1352, 1358, 1370	. . . 454, 510, 527, 768, 1036, 1038, 1047, 1049, 1092, 1331, 1367, 2170
\l_fontspec_defined_shapes_tl	\l_fontspec_strnum_int
. 999, 1109, 3013 38, 1285, 1291, 1310, 1317, 1345, 1351, 2171, 2243, 2452, 2458
\l_fontspec_fake_embolden_tl	\l_keys_choice_int 1408
. 1079, 1910, 1913, 1927	\l_keys_choice_tl 1411, 1423
\l_fontspec_fake_slant_tl	\l_keys_key_tl . . . 2951, 2956, 2961, 2966
. 1078, 1905, 1932, 1935	\l_keys_value_tl . 2951, 2956, 2961, 2966
\l_fontspec_family_tl	\l_tmpa_font 862, 864
. 325, 573, 581, 606, 752, 753, 758–761, 766–769, 957, 965, 993, 994, 1600, 1601, 2616, 3009	
\l_fontspec_feature_string_tl 1181, 1252	

<code>\l_tmpa_int</code>	1287, 1289, 1291, 1293, 1295, 1313, 1315, 1317, 1319, 1321, 1346, 1348, 1351, 1353, 1355		
<code>\l_tmpa_tl</code>	1228, 1229, 1252		
<code>\l_tmpb_font</code>	863, 864		
<code>\l_tmpb_int</code>	1286, 1289, 1293, 1311, 1315, 1319, 1339, 1348, 1353		
<code>\l_tmpb_tl</code>	1234, 1239, 1242, 1246, 1249, 1252		
<code>\Lambda</code>	2535		
<code>\latinencoding</code>	93, 97		
<code>\leavevmode</code>	2788		
<code>\let</code>	2790		
<code>\liningnums</code>	<u>2846</u>		
<code>\listing@line</code>	2825		
<code>listingcont*</code> (environment)	<u>2818</u>		
<code>\lst@visiblespace</code>	2843		
<code>\luatex_if_engine:T</code>	2000		
<code>\luatex_postexhyphenchar:D</code>	1127		
<code>\luatex_postthyphenchar:D</code>	1125		
<code>\luatex_preexhyphenchar:D</code>	1126		
<code>\luatex_prehyphenchar:D</code>	1124, 1759		
M			
<code>\mathalpha</code>	2498–2507, 2522–2542		
<code>\mathbf</code>	2557, 2567, 2898		
<code>\mathbin</code>	2543		
<code>\mathchardef</code>	2509		
<code>\mathclose</code>	2516, 2519, 2546, 2548		
<code>\mathdollar</code>	2550		
<code>\mathit</code>	2556, 2563, 2568, 2715, 2898		
<code>\mathopen</code>	2545, 2547		
<code>\mathord</code>	2549, 2550		
<code>\mathpunct</code>	2511, 2518		
<code>\mathrel</code>	2517, 2544		
<code>\mathring</code>	2507		
<code>\mathrm</code>	2555, 2566		
<code>\mathsf</code>	2558, 2570		
<code>\mathtt</code>	2559, 2571		
<code>\mddefault</code>	795, 797, 798, 1003, 1005, 1006, 1015, 1017, 1019, 2553, 2554, 2556, 2558, 2559, 2566, 2568		
<code>\msg_error:nn</code>	2856		
<code>\msg_error:nnx</code>	2857		
<code>\msg_fatal:nn</code>	14		
<code>\msg_info:nn</code>	2861		
<code>\msg_info:nnx</code>	2862		
<code>\msg_info:nxxx</code>	2863		
<code>\msg_line_context:</code>	2928		
<code>\msg_new:nnn</code>	9, 2865, 2886, 2926, 2936, 2940, 2945, 2949, 2954, 2959, 2964,	2970, 2974, 2981, 2985, 2989, 2993, 2998, 3002, 3007, 3015, 3019, 3023, 3027, 3031, 3036, 3041	
<code>\msg_new:nxxx</code>	2870, 2879, 2890, 2900, 2908, 2916		
<code>\msg_redirect_module:nnn</code>	69, 70, 74, 75		
<code>\msg_redirect_name:nnn</code>	1824		
<code>\msg_trace:nn</code>	2864		
<code>\msg_warning:nn</code>	2858		
<code>\msg_warning:nxx</code>	2859		
<code>\msg_warning:nxxx</code>	2860		
N			
<code>\newAATfeature</code>	<u>343</u>		
<code>\NewDocumentCommand</code>	152, 154, 2850		
<code>\newfontface</code>	<u>236</u>		
<code>\newfontfamily</code>	<u>236</u>		
<code>\newfontfeature</code>	<u>333</u>		
<code>\newfontlanguage</code>	<u>393</u> , 2251–2445		
<code>\newfontscript</code>	<u>389</u> , 2187–2235		
<code>\newICUfeature</code>	<u>351</u>		
<code>\newopentypefeature</code>	<u>351</u>		
<code>\normalfont</code>	170, 180, 190		
<code>\normalsize</code>	91, 979		
<code>\not@math@alphabet</code>	2686, 2715, 2720, 2725, 2730		
<code>\null</code>	2788		
<code>\nullfont</code>	124		
<code>\numexpr</code>	1244		
O			
<code>\oldstylenums</code>	<u>2846</u>		
<code>\Omega</code>	2542		
<code>\or</code>	819, 824		
P			
<code>\par</code>	2826		
<code>\Phi</code>	2540		
<code>\Pi</code>	2537		
<code>\prg_new_conditional:Nnn</code>	138, 403, 407, 426, 439, 467, 484, 499, 518, 535, 552, 683, 730, 860, 1226, 1282, 1307, 1336		
<code>\prg_return_false:</code>	127, 143, 405, 416, 419, 423, 433, 436, 457, 460, 464, 478, 480, 482, 493, 495, 497, 512, 514, 516, 529, 531, 533, 546, 548, 550, 563, 565, 567, 691, 754, 865, 1230, 1250, 1298, 1304, 1324, 1333, 1358, 1370		
<code>\prg_return_true:</code>	125, 141, 405, 416, 433, 457, 478, 493, 512,		

529, 546, 563, 691, 754, 866, 1253,	
1298, 1304, 1324, 1333, 1358, 1370	
\prg_set_conditional:Nnn	122
\ProcessOptions	78
\prop_get:cnN	316, 317, 411, 430,
443, 448, 451, 454, 455, 471, 488,	
503, 508, 510, 522, 539, 544, 556, 561	
\prop_get:NVNF	283, 639, 642, 880
\prop_gput:cnV	766–769
\prop_gput:cnx	759–761
\prop_gput:NVV	286
\prop_gremove:NV	290
\prop_if_in:NVF	626
\prop_map_inline:Nn	802
\prop_new:c	758
\prop_new:N	260, 1485, 1603
\prop_put:Nnn	53, 1459
\prop_put:NVn	291
\prop_put:NxV	1480, 1535
\prop_put:Nxx	1637
\providecommand	2682, 2683
\Psi	2541
Q	
\q_nil	1259, 1261, 2078, 2090
\q_stop	1684, 1687
R	
\relax	1244,
2509, 2686, 2720, 2725, 2730, 2788	
\RenewDocumentCommand	2846
\RequirePackage	4, 89, 103
\RequirePackageWithOptions	6, 8
\rmdefault	86, 169, 233, 1117
\rmfamily	1654, 1672
S	
\scan_stop:	109, 114, 140, 1754, 2769
\scdefault	971–973, 1015, 1016, 2682,
2683, 2691–2694, 2697, 2698, 2726	
\sclist_clear:N	1056, 1148
\sclist_gput_right:Nn	1149, 1151
\sclist_gput_right:Nx	1156
\sclist_put_right:Nn	<u>1148</u>
\scshape	<u>2713</u>
\selectfont	161, 248, 325, 2687, 2710, 2711
\seq_gput_right:Nx	1448
\seq_if_empty:NT	1470
\seq_new:N	1444
\seq_put_right:Nx	1473
\setboldmathrm	<u>194</u>
\setmainfont	<u>164</u> , 193
\SetMathAlphabet	2556–
2559, 2563, 2566–2568, 2570, 2571	
\setmathrm	<u>194</u>
\setmathsf	<u>194</u>
\setmathtt	<u>194</u>
\setmonofont	<u>164</u>
\setromanfont	<u>193</u>
\setsansfont	<u>164</u>
\SetSymbolFont	2497, 2554, 2560
\settoheight	1670
\sfdefault	87, 179, 234, 1118
\Sigma	2538
\sishape	<u>2682</u>
\sldefault	798, 800, 990, 993, 1006,
1008, 2683, 2692, 2694, 2696, 2721	
\slscdefault	1019,
1020, 2683, 2692, 2694–2696, 2698	
\slshape	<u>2713</u>
\space	1234, 1239, 1244, 3021, 3029
\str_case:nn	1001, 1013
\str_case:nnF	1115, 1643
\str_case_x:nnF	1709
\str_if_eq:nnTF	47, 1672, 1741, 1821
\str_if_eq:nVTF	545, 562
\str_if_eq_x:nnF	1067
\str_if_eq_x:nnTF	864
\str_if_eq_x_p:nn	989, 990
\string	2898, 2918, 2928
\sys_if_engine luatex:T	3
\sys_if_engine xetex:T	7
T	
\textsi	<u>2682</u>
\textvisiblespace	2776
\the	2826
\thelisting@line	2825
\Theta	2534
\tilde	2501
\tl_clear:N	284, 644, 887, 888,
893, 1057, 1061, 1062, 1075–1094,	
1107–1110, 1148, 1402, 1608, 1620	
\tl_const:cn	2691–2698
\tl_count:n	1774, 1777
\tl_gput_right:Nn	1150
\tl_gput_right:Nx	999
\tl_gset:cx	747
\tl_gset:Nv	752
\tl_gset:Nx	1447, 1472, 1594, 1657
\tl_gset_eq:NN	1111
\tl_if_empty:ff	1024
\tl_if_empty:NF	
1036, 1047, 1246, 1635, 1910, 1932	

<code>\tl_if_empty:nF</code>	843, 1030	<code>\typeout</code>	610, 616, 656, 732, 911, 914, 918, 1478, 1612, 1617, 2623
<code>\tl_if_empty:NT</code>	709, 721, 827, 850, 898, 1569	U	
<code>\tl_if_empty:NTF</code> 704, 909, 1229, 1249, 2561		<code>\updefault</code>	795, 796, 1003, 1004, 2553, 2554, 2557–2560, 2566, 2567, 2570, 2571, 2697, 2698, 2731
<code>\tl_if_empty:nTF</code>	51, 52, 289, 1176, 1188, 1462, 1488, 1511, 1689	<code>\upshape</code>	<u>2713</u> , <u>2752</u>
<code>\tl_if_empty:xF</code>	848	<code>\Upsilon</code>	2539
<code>\tl_if_empty:xTF</code>	1631	<code>\use:c</code>	246, 2748, 2931
<code>\tl_if_eq:NNF</code>	1789, 1802	<code>\use:n</code>	896
<code>\tl_if_eq:nnT</code>	1458	<code>\use:x</code>	242, 319, 2075
<code>\tl_if_eq:oxT</code>	1475	<code>\use_i:nnn</code>	1625
<code>\tl_if_exist:cTF</code>	971	<code>\use_ii:nnn</code>	1625
<code>\tl_if_exist:NT</code>	1600	<code>\use_iii:nnn</code>	1606
<code>\tl_if_exist_p:c</code>	2703	<code>\use_iv:nnnnn</code>	46
<code>\tl_if_head_eq_charcode_p:nN</code> 1276, 1277		<code>\use_none:n</code>	1279
<code>\tl_if_in:NnF</code>	1614	<code>\use_v:nnnnn</code>	45
<code>\tl_if_in:NnT</code>	301	<code>\usefont</code>	2775
<code>\tl_if_in:nnT</code>	688	<code>\UTFencname</code>	90
<code>\tl_if_single:nTF</code>	277, 1747	V	
<code>\tl_new:N</code>	194–197, 1098, 1099	<code>\verb</code>	<u>2786</u>
<code>\tl_put_left:Nn</code>	1246	<code>\verb*</code>	<u>2786</u>
<code>\tl_put_right:Nn</code>	285, 1743, 1752	<code>\verb@eol@error</code>	2790
<code>\tl_put_right:Nx</code>	944, 1730	<code>verbatim* (environment)</code>	<u>2802</u>
<code>\tl_remove_all:Nn</code> 298, 400, 625, 741, 1524		<code>\verbatim@font</code>	2791
<code>\tl_remove_once:Nn</code>	303	<code>\verbatim@line</code>	2826
<code>\tl_replace_all:Nnn</code>	1526	<code>\verbatim@processline</code>	2823
<code>\tl_replace_all:Nnx</code>	1523	<code>\verbatim@start</code>	2808, 2828
<code>\tl_set:cn</code>	1428–1433	X	
<code>\tl_set:Nn</code> 79, 83, 84, 86–88, 233– 235, 527, 571, 578, 708, 711, 723, 830, 833, 1095, 1100, 1101, 1117– 1119, 1123, 1396, 1437, 1442, 1570, 1574, 1586, 1691, 1699, 1713, 1718, 1723, 1748, 1749, 1775, 1788, 1794, 1847, 1864, 1905, 1927, 2170, 2242, 2453, 2459, 2470, 2612, 2616, 2617		<code>\xetex_suppressfontnotfounderror:D</code> 119	
<code>\tl_set:No</code>	278, 1606	<code>\XeTeXcountvariations</code>	821
<code>\tl_set:Nv</code>	1410, 1422	<code>\XeTeXfeaturename</code>	1228
<code>\tl_set:Nx</code>	44, 297, 589–591, 624, 654, 740, 853, 1228, 1234, 1239, 1242, 1252, 1522, 1598, 1629, 1648, 1649, 1807	<code>\XeTeXfonttype</code>	817
<code>\tl_set_eq:NN</code>	90, 92, 93, 96, 97, 573, 580, 581, 667, 889, 894, 1058–1060, 1073, 1476, 1607, 1619, 1907, 1915, 1929, 1937	<code>\XeTeXisexclusivefeature</code>	1232
<code>\tl_to_str:N</code>	44, 654	<code>\XeTeXOTcountfeatures</code>	1341
<code>\tl_use:c</code>	972, 2707, 2710	<code>\XeTeXOTcountlanguages</code>	1312
<code>\token_to_str:N</code>	1769	<code>\XeTeXOTcountscripts</code>	1286
<code>\ttdefault</code>	88, 189, 235, 1119	<code>\XeTeXOTfeaturetag</code>	1350
<code>\two@digits</code>	2070, 2081	<code>\XeTeXOTlanguagetag</code>	1317
		<code>\XeTeXOTscripttag</code>	1291
		<code>\XeTeXpicfile</code>	101, 102, 104
		<code>\XeTeXselectorname</code> ...	1234, 1239, 1244
		<code>\Xi</code>	2536
		<code>\xlx@defaulthyphenchar</code>	2759, 2765
		Z	
		<code>\z@</code>	2758
		<code>\zf@basefont</code>	<u>2612</u>
		<code>\zf@enc</code>	<u>2612</u>

22 Declaration of variables

17 (*vars)

Conditionals

firsttime As \keys_set:nn is run multiple times, some of its information storing only occurs once while we decide if the font family has been defined or not. When the later processing is occurring per-shape this no longer needs to happen; this is indicated by the ‘firsttime’ conditional (initialised true).

```
18 \bool_new:N \l_@@_firsttime_bool
19 \bool_new:N \l_@@_nobf_bool
20 \bool_new:N \l_@@_noit_bool
21 \bool_new:N \l_@@_nosc_bool
22 \bool_new:N \l__fontspec_check_bool
23 \cs_new:Npn \FontspecSetCheckBoolTrue { \bool_set_true:N \l__fontspec_check_bool }
24 \cs_new:Npn \FontspecSetCheckBoolFalse { \bool_set_false:N \l__fontspec_check_bool }
25 \bool_new:N \l_@@_tfm_bool
26 \bool_new:N \l_@@_atsui_bool
27 \bool_new:N \l_@@_ot_bool
28 \bool_new:N \l_@@_mm_bool
29 \bool_new:N \l_@@_graphite_bool
```

For dealing with legacy maths

```
30 \bool_new:N \g_@@_math_euler_bool
31 \bool_new:N \g_@@_math_lucida_bool
32 \bool_new:N \g_@@_pkg_euler_loaded_bool
```

For package options:

```
33 \bool_new:N \g_@@_cfg_bool
34 \bool_new:N \g_@@_math_bool
35 \bool_new:N \g_@@_euenc_bool
```

Counters

```
36 \int_new:N \l_fontspec_script_int
37 \int_new:N \l_fontspec_language_int
38 \int_new:N \l_fontspec_strnum_int
```

Other variables

```
39 \fp_new:N \l_@@_tmpa_fp
40 \fp_new:N \l_@@_tmpb_fp
41 \dim_new:N \l_@@_tmpa_dim
42 \dim_new:N \l_@@_tmpb_dim
43 \dim_new:N \l_@@_tmpc_dim
44 \tl_set:Nx \c_colon_str { \tl_to_str:N : }
45 \cs_set:Npn \use_v:nnnnn #1#2#3#4#5 {#5}
46 \cs_set:Npn \use_iv:nnnnn #1#2#3#4#5 {#4}
```

Need these:

```
47 \cs_generate_variant:Nn \str_if_eq:nnTF {nv}
48 \cs_generate_variant:Nn \int_set:Nn {Nv}
49 \cs_generate_variant:Nn \keys_set:nn {nx}
50 \cs_generate_variant:Nn \keys_set_known:nnN {nx}
51 \cs_generate_variant:Nn \tl_if_empty:nTF {x}
52 \cs_generate_variant:Nn \tl_if_empty:nTF {x}
53 \cs_generate_variant:Nn \prop_put:Nnn {Nxx}
```

\@@_int_mult_truncate:Nn Missing in expl3, IMO.

```
54 \cs_new:Nn \@@_int_mult_truncate:Nn
55 {
56   \int_set:Nn #1 { \__dim_eval:w #2 #1 \__dim_eval_end: }
57 }
58 </vars>
```

23 Opening code

23.1 Package options

```
59 \DeclareOption{cm-default}
60 { \@@_warning:n {cm-default-obsolete} }
61 \DeclareOption{math}{\bool_set_true:N \g_@@_math_bool}
62 \DeclareOption{no-math}{\bool_set_false:N \g_@@_math_bool}
63 \DeclareOption{config}{\bool_set_true:N \g_@@_cfg_bool}
64 \DeclareOption{no-config}{\bool_set_false:N \g_@@_cfg_bool}
65 \DeclareOption{euenc}{\bool_set_true:N \g_@@_euenc_bool}
66 \DeclareOption{tuenc}{\bool_set_false:N \g_@@_euenc_bool}
67 \DeclareOption{quiet}
68 {
69   \msg_redirect_module:nnn { fontspec } { warning } { info }
70   \msg_redirect_module:nnn { fontspec } { info } { none }
71 }
72 \DeclareOption{silent}
73 {
74   \msg_redirect_module:nnn { fontspec } { warning } { none }
75   \msg_redirect_module:nnn { fontspec } { info } { none }
76 }
77 \ExecuteOptions{config,math,euenc}
78 \ProcessOptions*
```

23.2 Encodings

Soon to be the default, with a just-in-case check:

```
79 \tl_set:Nn \g_fontspec_encoding_tl {TU}
80 \file_if_exist:nF {tuenc.def} { \bool_set_true:N \g_@@_euenc_bool }
81 \bool_if:NT \g_@@_euenc_bool
82 {
83   \xetexx \tl_set:Nn \g_fontspec_encoding_tl {EU1}
84   \luatex \tl_set:Nn \g_fontspec_encoding_tl {EU2}
85 }
```

```

86\l_set:Nn \rmdefault {lmr}
87\l_set:Nn \sfdefault {lmss}
88\l_set:Nn \ttdefault {lmtt}
89\RequirePackage[\g_fontspec_encoding_tl]{fontenc}
90\l_set_eq:NN \UTFencname \g_fontspec_encoding_tl % for xunicode if needed
91\normalize % to overcome the encoding changing the current font size

```

Dealing with a couple of the problems introduced by babel:

```

92\l_set_eq:NN \cyrillicencoding \g_fontspec_encoding_tl
93\l_set_eq:NN \latinencoding \g_fontspec_encoding_tl
94\AtBeginDocument
95 {
96 \l_set_eq:NN \cyrillicencoding \g_fontspec_encoding_tl
97 \l_set_eq:NN \latinencoding \g_fontspec_encoding_tl
98 }

```

That latin encoding definition is repeated to suppress font warnings. Something to do with `\select@language` ending up in the `.aux` file which is read at the beginning of the document.

```

99\bool_if:NT \g_@@_euenc_bool
100 {
101\luatex \cs_set_eq:NN \fontspec_tmp: \XeTeXpicfile
102\luatex \cs_set:Npn \XeTeXpicfile {}
103 \RequirePackage{xunicode}
104\luatex \cs_set_eq:NN \XeTeXpicfile \fontspec_tmp:
105 }

```

24 expl3 interface for font loading

```

106\cs_set:Nn \@@_fontwrap:n { "#1" }
107\cs_set:Npn \@@_primitive_font_set:Nnn #1#2#3
108 {
109 \font #1 = #2 ~at~ #3 \scan_stop:
110 }
111
112\cs_set:Npn \@@_primitive_font_gset:Nnn #1#2#3
113 {
114 \global \font #1 = #2 ~at~ #3 \scan_stop:
115 }
116
117\cs_set:Npn \@@_font_suppress_not_found_error:
118 {
119 \int_set_eq:NN \xetex_suppressfontnotfounderror:D \c_one
120 }
121
122\prg_set_conditional:Nnn \@@_font_if_null:N {p,TF,T,F}
123 {
124 \ifx #1 \nullfont
125 \prg_return_true:
126 \else
127 \prg_return_false:

```

```

128   \fi
129 }

\fontspec_set:Nnn,\fontspec_gset:Nnn Wrapper around \font_set:Nnn and \font_gset:Nnn.
130 \cs_new:Nn \@@_font_set:Nnn
131 {
132   \@@_primitive_font_set:Nnn #1 { \@@_fontwrap:n {#2} } {#3}
133 }
134 \cs_new:Nn \@@_font_gset:Nnn
135 {
136   \@@_primitive_font_gset:Nnn #1 { \@@_fontwrap:n {#2} } {#3}
137 }

\font_glyph_if_exist:NnTF
138 \prg_new_conditional:Nnn \font_glyph_if_exist:Nn {p,TF,T,F}
139 {
140   \etex_iffontchar:D #1 #2 \scan_stop:
141   \prg_return_true:
142   \else:
143   \prg_return_false:
144   \fi:
145 }

```

25 User commands

This section contains the definitions of the commands detailed in the user documentation. Only the ‘top level’ definitions of the commands are contained herein; they all use or define macros which are defined or used later on in [Section 27.1 on page 70](#).

25.0.1 Helper macros for argument mangling

```

146 \cs_new:Nn \@@_pass_args:nnn
147 {
148   \IfNoValueTF {#2}
149   { \@@_post_arg:w {#1} {#3} }
150   { #1 {#2} {#3} }
151 }
152 \NewDocumentCommand \@@_post_arg:w { m m O{} }
153 { #1 {#3} {#2} }

```

25.0.2 Font selection

`\fontspec` This is the main command of the package that selects fonts with various features. It takes two arguments: the font name and the optional requested features of that font. Then this new font family is selected.

```

154 \NewDocumentCommand \fontspec { o m }
155 { \@@_pass_args:nnn \@@_fontspec:nn {#1} {#2} }
156
157 \cs_new:Nn \@@_fontspec:nn
158 {

```

```

159 \fontspec_set_family:Nnn \f@family {#1} {#2}
160 \fontencoding { \l_@@_nfss_enc_tl }
161 \selectfont
162 \ignorespaces
163 }

```

`\setmainfont` `\setsansfont` `\setmonofont` The following three macros perform equivalent operations setting the default font for a particular family: ‘roman’, sans serif, or typewriter (monospaced). I end them with `\normalfont` so that if they’re used in the document, the change registers immediately.

```

164 \DeclareDocumentCommand \setmainfont { o m }
165 { \@@_pass_args:nnn \@@_setmainfont:nn {#1} {#2} }
166
167 \cs_new:Nn \@@_setmainfont:nn
168 {
169   \fontspec_set_family:Nnn \rmdefault {#1}{#2}
170   \normalfont
171   \ignorespaces
172 }
173
174 \DeclareDocumentCommand \setsansfont { o m }
175 { \@@_pass_args:nnn \@@_setsansfont:nn {#1} {#2} }
176
177 \cs_new:Nn \@@_setsansfont:nn
178 {
179   \fontspec_set_family:Nnn \sfdefault {#1}{#2}
180   \normalfont
181   \ignorespaces
182 }
183
184 \DeclareDocumentCommand \setmonofont { o m }
185 { \@@_pass_args:nnn \@@_setmonofont:nn {#1} {#2} }
186
187 \cs_new:Nn \@@_setmonofont:nn
188 {
189   \fontspec_set_family:Nnn \ttdefault {#1}{#2}
190   \normalfont
191   \ignorespaces
192 }

```

`\setromanfont` This is the old name for `\setmainfont`, retained for backwards compatibility.

```

193 \cs_set_eq:NN \setromanfont \setmainfont

```

`\setmathrm` `\setmathsf` `\setboldmathrm` These commands are analogous to `\setmainfont` and others, but for selecting the font used for `\mathrm`, *etc.* They can only be used in the preamble of the document. `\setboldmathrm` is used for specifying which fonts should be used in `\boldmath`.

```

\setmathtt
194 \tl_new:N \g_@@_mathrm_tl
195 \tl_new:N \g_@@_bfmathrm_tl
196 \tl_new:N \g_@@_mathsf_tl
197 \tl_new:N \g_@@_mathtt_tl
198 \DeclareDocumentCommand \setmathrm { o m }

```

```

199 { \@@_pass_args:nnn \@@_setmathrm:nn {#1} {#2} }
200
201 \cs_new:Nn \@@_setmathrm:nn
202 {
203   \fontspec_set_family:Nnn \g_@@_mathrm_tl {#1} {#2}
204 }
205
206 \DeclareDocumentCommand \setboldmathrm { o m }
207 { \@@_pass_args:nnn \@@_setboldmathrm:nn {#1} {#2} }
208
209 \cs_new:Nn \@@_setboldmathrm:nn
210 {
211   \fontspec_set_family:Nnn \g_@@_bfmathrm_tl {#1} {#2}
212 }
213
214 \DeclareDocumentCommand \setmathsf { o m }
215 { \@@_pass_args:nnn \@@_setmathsf:nn {#1} {#2} }
216
217 \cs_new:Nn \@@_setmathsf:nn
218 {
219   \fontspec_set_family:Nnn \g_@@_mathsf_tl {#1} {#2}
220 }
221
222 \DeclareDocumentCommand \setmathtt { o m }
223 { \@@_pass_args:nnn \@@_setmathtt:nn {#1} {#2} }
224
225 \cs_new:Nn \@@_setmathtt:nn
226 {
227   \fontspec_set_family:Nnn \g_@@_mathtt_tl {#1} {#2}
228 }
229 \@onlypreamble\setmathrm
230 \@onlypreamble\setboldmathrm
231 \@onlypreamble\setmathsf
232 \@onlypreamble\setmathtt

```

If the commands above are not executed, then `\rmdefault` (*etc.*) will be used.

```

233 \tl_set:Nn \g_@@_mathrm_tl {\rmdefault}
234 \tl_set:Nn \g_@@_mathsf_tl {\sfdefault}
235 \tl_set:Nn \g_@@_mathtt_tl {\ttdefault}

```

`\newfontfamily` This macro takes the arguments of `\fontspec` with a prepended *instance cmd*.

`\newfontface` This command is used when a specific font instance needs to be referred to repetitively (*e.g.*, in a section heading) since continuously calling `\fontspec_select:nn` is inefficient because it must parse the option arguments every time.

`\fontspec_select:nn` defines a font family and saves its name in `\l_fontspec_family_tl`.

This family is then used in a typical NFSS `\fontfamily` declaration, saved in the macro name specified.

```

236 \DeclareDocumentCommand \newfontfamily { m o m }
237 { \@@_pass_args:nnn { \@@_newfontfamily:Nnn #1 } {#2} {#3} }
238
239 \cs_new:Nn \@@_newfontfamily:Nnn

```

```

240 {
241   \fontspec_set_family:cnn { g_@_ \cs_to_str:N #1 _family } {#2} {#3}
242   \use:x
243   {
244     \exp_not:N \DeclareRobustCommand \exp_not:N #1
245     {
246       \exp_not:N \fontfamily { \use:c {g_@_ \cs_to_str:N #1 _family} }
247       \exp_not:N \fontencoding { \l_@_nfss_enc_tl }
248       \exp_not:N \selectfont
249     }
250   }
251 }

```

`\newfontface` uses the fact that if the argument to `BoldFont`, etc., is empty (*i.e.*, `BoldFont={}`), then no bold font is searched for.

```

252 \DeclareDocumentCommand \newfontface { m o m }
253 { \@@_pass_args:nnn { \@@_newfontface:Nnn #1 } {#2} {#3} }
254
255 \cs_new:Nn \@@_newfontface:Nnn
256 {
257   \newfontfamily #1 [ BoldFont={},ItalicFont={},SmallCapsFont={},#2 ] {#3}
258 }

```

25.0.3 Font feature selection

`\defaultfontfeatures` This macro takes one argument that consists of all of feature options that will be applied by default to all subsequent `\fontspec`, et al., commands. It stores its value in `\g_fontspec_default_fontopts_tl` (initialised empty), which is concatenated with the individual macro choices in the [...] macro.

```

259 \clist_new:N \g_@@_default_fontopts_clist
260 \prop_new:N \g_@@_fontopts_prop
261 \DeclareDocumentCommand \defaultfontfeatures { t+ o m }
262 {
263   \IfNoValueTF {#2}
264   { \@@_set_default_features:nn {#1} {#3} }
265   { \@@_set_font_default_features:nnn {#1} {#2} {#3} }
266   \ignorespaces
267 }
268 \cs_new:Nn \@@_set_default_features:nn
269 {
270   \IfBooleanTF {#1} \clist_put_right:Nn \clist_set:Nn
271   \g_@@_default_fontopts_clist {#2}
272 }

```

The optional argument specifies a font identifier. Branch for either (a) single token input such as `\rmdefault`, or (b) otherwise assume its a fontname. In that case, strip spaces and file extensions and lower-case to ensure consistency.

```

273 \cs_new:Nn \@@_set_font_default_features:nnn
274 {
275   \clist_map_inline:nn {#2}
276   {

```

```

277 \tl_if_single:nTF {##1}
278 { \tl_set:No \l_@@_tmp_tl { \cs:w g_@@_ \cs_to_str:N ##1 _family\cs_end: } }
279 { \@@_sanitise_fontname:Nn \l_@@_tmp_tl {##1} }
280
281 \IfBooleanTF {#1}
282 {
283   \prop_get:NVNF \g_@@_fontopts_prop \l_@@_tmp_tl \l_@@_tmpb_tl
284   { \tl_clear:N \l_@@_tmpb_tl }
285   \tl_put_right:Nn \l_@@_tmpb_tl {#3,}
286   \prop_gput:NVV \g_@@_fontopts_prop \l_@@_tmp_tl \l_@@_tmpb_tl
287 }
288 {
289   \tl_if_empty:nTF {#3}
290   { \prop_gremove:NV \g_@@_fontopts_prop \l_@@_tmp_tl }
291   { \prop_put:NVn \g_@@_fontopts_prop \l_@@_tmp_tl {#3,} }
292 }
293 }
294 }

```

`\@@_sanitise_fontname:Nn` Assigns font name #2 to token list variable #1 and strips extension(s) from it in the case of an external font. We strip spaces for luatex for consistency with luaotfload, although I'm not sure this is necessary any more. At one stage this also lowercased the name, but this step has been removed unless someone can remind me why it was necessary.

```

295 \cs_new:Nn \@@_sanitise_fontname:Nn
296 {
297   \tl_set:Nx #1 {#2}
298 (luatex) \tl_remove_all:Nn #1 {~}
299   \clist_map_inline:Nn \l_@@_extensions_clist
300   {
301     \tl_if_in:NnT #1 {##1}
302     {
303       \tl_remove_once:Nn #1 {##1}
304 %       \keys_set:nn {fontspec-prepare-external} { Extension = ##1 }
305       \clist_map_break:
306     }
307   }
308 }

```

`\addfontfeatures` In order to be able to extend the feature selection of a given font, two things need to be known: the currently selected features, and the currently selected font. Every time a font family is created, this information is saved inside a control sequence with the name of the font family itself.

This macro extracts this information, then appends the requested font features to add to the already existing ones, and calls the font again with the top level `\fontspec` command.

The default options are *not* applied (which is why `\g_fontspec_default_fontopts_tl` is emptied inside the group; this is allowed as `\l_fontspec_family_tl` is globally defined in `\fontspec_select:nn`), so this means that the only added features to the font are strictly those specified by this command.

`\addfontfeature` is defined as an alias, as I found that I often typed this instead when adding only a single font feature.

```

309 \bool_new:N \l_@@_disable_defaults_bool
310 \DeclareDocumentCommand \addfontfeatures {m}
311 {
312   \fontspec_if_fontspec_font:TF
313   {
314     \group_begin:
315       \keys_set_known:nnN {fontspec-addfeatures} {#1} \l_@@_tmp_tl
316       \prop_get:cnN {g_@@_ \f@family _prop} {options} \l_@@_options_tl
317       \prop_get:cnN {g_@@_ \f@family _prop} {fontname} \l_@@_fontname_tl
318       \bool_set_true:N \l_@@_disable_defaults_bool
319       \use:x
320       {
321         \exp_not:N \fontspec_select:nn
322         { \l_@@_options_tl , #1 } { \l_@@_fontname_tl }
323       }
324     \group_end:
325     \fontfamily\l_@@_fontspec_family_tl\selectfont
326   }
327   {
328     \@@_warning:nx {addfontfeatures-ignored} {#1}
329   }
330   \ignorespaces
331 }
332 \cs_set_eq:NN \addfontfeature \addfontfeatures

```

25.0.4 Defining new font features

`\newfontfeature` `\newfontfeature` takes two arguments: the name of the feature tag by which to reference it, and the string that is used to select the font feature.

```

333 \DeclareDocumentCommand \newfontfeature {mm}
334 {
335   \keys_define:nn { fontspec }
336   {
337     #1 .code:n =
338     {
339       \@@_update_featstr:n {#2}
340     }
341   }
342 }

```

`\newAATfeature` This command assigns a new AAT feature by its code (#2,#3) to a new name (#1). Better than `\newfontfeature` because it checks if the feature exists in the font it's being used for.

```

343 \DeclareDocumentCommand \newAATfeature {mmm}
344 {
345   \keys_if_exist:nnF { fontspec } {#1}
346   { \@@_define_font_feature:n {#1} }
347   \keys_if_choice_exist:nnnT {fontspec} {#1} {#2}
348   { \@@_warning:nxx {feature-option-overwrite} {#1} {#2} }

```

```

349 \@@_define_feature_option:nnnn {#1}{#2}{#3}{#4}{ }
350 }

```

`\newopentypefeature` This command assigns a new OpenType feature by its abbreviation (#2) to a new name (#1). Better than `\newfontfeature` because it checks if the feature exists in the font it's being used for.

`\newICUfeature`

```

351 \DeclareDocumentCommand \newopentypefeature {mmm}
352 {
353   \keys_if_exist:nnF { fontspec / options } {#1}
354   { \@@_define_font_feature:n {#1} }
355   \keys_if_choice_exist:nnnT {fontspec} {#1} {#2}
356   { \@@_warning:nxx {feature-option-overwrite} {#1} {#2} }
357   \@@_define_feature_option:nnnn {#1}{#2}{ } {#3}
358 }
359 \cs_set_eq:NN \newICUfeature \newopentypefeature % deprecated

```

`\aliasfontfeature` User commands for renaming font features and font feature options.

`\aliasfontfeatureoption`

```

360 \bool_new:N \l_@@_alias_bool
361 \DeclareDocumentCommand \aliasfontfeature {mm}
362 {
363   \bool_set_false:N \l_@@_alias_bool
364
365   \clist_map_inline:nn
366   { fontspec, fontspec-prepare, fontspec-prepare-external,
367     fontspec-prepare-nested, fontspec-renderer }
368   {
369
370     \keys_if_exist:nnT {##1} {#1}
371     {
372       \bool_set_true:N \l_@@_alias_bool
373       \@@_alias_font_feature:nnn {##1} {#1} {#2}
374     }
375   }
376
377   \bool_if:NF \l_@@_alias_bool
378   { \@@_warning:nx {rename-feature-not-exist} {#1} }
379 }
380
381 \cs_set:Nn \@@_alias_font_feature:nnn
382 {
383   \keys_define:nn {#1}
384   { #3 .code:n = { \keys_set:nn {#1} { #2 = {##1} } } }
385 }
386
387 \DeclareDocumentCommand \aliasfontfeatureoption {mmm}
388 { \keys_define:nn { fontspec / #1 } { #3 .meta:n = {#2} } }

```

`\newfontscript` Mostly used internally, but also possibly useful for users, to define new OpenType ‘scripts’, mapping logical names to OpenType script tags.

```

389 \DeclareDocumentCommand \newfontscript {mm}
390 {

```

```

391 \fontspec_new_script:nn {#1} {#2}
392 }

```

`\newfontlanguage` Mostly used internally, but also possibly useful for users, to define new OpenType ‘languages’, mapping logical names to OpenType language tags.

```

393 \DeclareDocumentCommand \newfontlanguage {mm}
394 {
395 \fontspec_new_lang:nn {#1} {#2}
396 }

```

`\DeclareFontsExtensions` `dfont` would never be uppercase, right?

```

397 \DeclareDocumentCommand \DeclareFontsExtensions {m}
398 {
399 \clist_set:Nn \l_@@_extensions_clist { #1 }
400 \tl_remove_all:Nn \l_@@_extensions_clist {~}
401 }
402 \DeclareFontsExtensions{.otf,.ttf,.OTF,.TTF,.ttc,.TTC,.dfont}

```

26 Programmer’s interface

These functions are not used directly by `fontspec` when defining fonts; they are designed to be used by other packages who wish to do font-related things on top of `fontspec` itself.

Because I haven’t fully explored how these functions will behave in practise, I am not giving them user-level names. As it becomes more clear which of these should be accessible by document writers, I’ll open them up a little more.

All functions are defined assuming that the font to be queried is currently selected as a `fontspec` font. (I.e., via `\fontspec` or from a `\newfontfamily` macro or from `\setmainfont` and so on.)

`\fontspec_if_fontspec_font:TF` Test whether the currently selected font has been loaded by `fontspec`.

```

403 \prg_new_conditional:Nnn \fontspec_if_fontspec_font: {TF,T,F}
404 {
405 \cs_if_exist:cTF {g_@@_ \f@family _prop} \prg_return_true: \prg_return_false:
406 }

```

`\fontspec_if_aat_feature:nnTF` Conditional to test if the currently selected font contains the AAT feature (#1,#2).

```

407 \prg_new_conditional:Nnn \fontspec_if_aat_feature:nn {TF,T,F}
408 {
409 \fontspec_if_fontspec_font:TF
410 {
411 \prop_get:cnN {g_@@_ \f@family _prop} {fontdef} \l_@@_fontdef_tl
412 \@@_font_set:Nnn \l_fontspec_font {\l_@@_fontdef_tl} {\f@size pt}
413 \bool_if:NTF \l_@@_atsui_bool
414 {
415 \fontspec_make_AAT_feature_string:nnTF {#1}{#2}
416 \prg_return_true: \prg_return_false:
417 }
418 {

```

```

419     \prg_return_false:
420   }
421 }
422 {
423   \prg_return_false:
424 }
425 }

```

`\fontspec_if_opentype:TF` Test whether the currently selected font is an OpenType font. Always true for LuaTeX fonts.

```

426 \prg_new_conditional:Nnn \fontspec_if_opentype: {TF,T,F}
427 {
428   \fontspec_if_fontspec_font:TF
429   {
430     \prop_get:cnN {g_@_ \f@family _prop} {fontdef} \l_@@_fontdef_tl
431     \@@_font_set:Nnn \l_fontspec_font {\l_@@_fontdef_tl} {\f@size pt}
432     \@@_set_font_type:
433     \bool_if:NTF \l_@@_ot_bool \prg_return_true: \prg_return_false:
434   }
435   {
436     \prg_return_false:
437   }
438 }

```

`\fontspec_if_feature:nTF` Test whether the currently selected font contains the raw OpenType feature #1. E.g.: `\fontspec_if_feature:nTF {pnum} {True} {False}` Returns false if the font is not loaded by fontspec or is not an OpenType font.

```

439 \prg_new_conditional:Nnn \fontspec_if_feature:n {TF,T,F}
440 {
441   \fontspec_if_fontspec_font:TF
442   {
443     \prop_get:cnN {g_@_ \f@family _prop} {fontdef} \l_@@_fontdef_tl
444     \@@_font_set:Nnn \l_fontspec_font {\l_@@_fontdef_tl} {\f@size pt}
445     \@@_set_font_type:
446     \bool_if:NTF \l_@@_ot_bool
447     {
448       \prop_get:cnN {g_@_ \f@family _prop} {script-num} \l_@@_tmp_tl
449       \int_set:Nn \l_fontspec_script_int {\l_@@_tmp_tl}
450
451       \prop_get:cnN {g_@_ \f@family _prop} {lang-num} \l_@@_tmp_tl
452       \int_set:Nn \l_fontspec_language_int {\l_@@_tmp_tl}
453
454       \prop_get:cnN {g_@_ \f@family _prop} {script-tag} \l_fontspec_script_tl
455       \prop_get:cnN {g_@_ \f@family _prop} {lang-tag} \l_fontspec_lang_tl
456
457       \fontspec_check_ot_feat:nTF {#1} {\prg_return_true:} {\prg_return_false:}
458     }
459     {
460       \prg_return_false:
461     }
462   }

```

```

463 {
464   \prg_return_false:
465 }
466 }

```

`\fontspec_if_feature:nnnTF` Test whether the currently selected font with raw OpenType script tag #1 and raw OpenType language tag #2 contains the raw OpenType feature tag #3. E.g.: `\fontspec_if_feature:nTF {latn} {ROM} {pnum} {True} {False}` Returns false if the font is not loaded by fontspec or is not an OpenType font.

```

467 \prg_new_conditional:Nnn \fontspec_if_feature:nnn {TF,T,F}
468 {
469   \fontspec_if_fontspec_font:TF
470   {
471     \prop_get:cnN {g_@_ \f@family _prop} {fontdef} \l_@@_fontdef_tl
472     \@@_font_set:Nnn \l_fontspec_font {\l_@@_fontdef_tl} {\f@size pt}
473     \@@_set_font_type:
474     \bool_if:NTF \l_@@_ot_bool
475     {
476       \fontspec_iv_str_to_num:Nn \l_fontspec_script_int {#1}
477       \fontspec_iv_str_to_num:Nn \l_fontspec_language_int {#2}
478       \fontspec_check_ot_feat:nTF {#3} \prg_return_true: \prg_return_false:
479     }
480     { \prg_return_false: }
481   }
482   { \prg_return_false: }
483 }

```

`\fontspec_if_script:nTF` Test whether the currently selected font contains the raw OpenType script #1. E.g.: `\fontspec_if_script:nTF {latn} {True} {False}` Returns false if the font is not loaded by fontspec or is not an OpenType font.

```

484 \prg_new_conditional:Nnn \fontspec_if_script:n {TF,T,F}
485 {
486   \fontspec_if_fontspec_font:TF
487   {
488     \prop_get:cnN {g_@_ \f@family _prop} {fontdef} \l_@@_fontdef_tl
489     \@@_font_set:Nnn \l_fontspec_font {\l_@@_fontdef_tl} {\f@size pt}
490     \@@_set_font_type:
491     \bool_if:NTF \l_@@_ot_bool
492     {
493       \fontspec_check_script:nTF {#1} \prg_return_true: \prg_return_false:
494     }
495     { \prg_return_false: }
496   }
497   { \prg_return_false: }
498 }

```

`\fontspec_if_language:nTF` Test whether the currently selected font contains the raw OpenType language tag #1. E.g.: `\fontspec_if_language:nTF {ROM} {True} {False}`. Returns false if the font is not loaded by fontspec or is not an OpenType font.

```

499 \prg_new_conditional:Nnn \fontspec_if_language:n {TF,T,F}
500 {

```

```

501 \fontspec_if_fontspec_font:TF
502 {
503   \prop_get:cnN {g_@_ \f@family _prop} {fontdef} \l_@@_fontdef_tl
504   \@@_font_set:Nnn \l_fontspec_font {\l_@@_fontdef_tl} {\f@size pt}
505   \@@_set_font_type:
506   \bool_if:NTF \l_@@_ot_bool
507   {
508     \prop_get:cnN {g_@_ \f@family _prop} {script-num} \l_@@_tmp_tl
509     \int_set:Nn \l_fontspec_script_int {\l_@@_tmp_tl}
510     \prop_get:cnN {g_@_ \f@family _prop} {script-tag} \l_fontspec_script_tl
511
512     \fontspec_check_lang:nTF {#1} \prg_return_true: \prg_return_false:
513   }
514   { \prg_return_false: }
515 }
516 { \prg_return_false: }
517 }

```

`\fontspec_if_language:nnTF` Test whether the currently selected font contains the raw OpenType language tag #2 in script #1. E.g.: `\fontspec_if_language:nnTF {cyr1} {SRB} {True} {False}`. Returns false if the font is not loaded by fontspec or is not an OpenType font.

```

518 \prg_new_conditional:Nnn \fontspec_if_language:nn {TF,T,F}
519 {
520   \fontspec_if_fontspec_font:TF
521   {
522     \prop_get:cnN {g_@_ \f@family _prop} {fontdef} \l_@@_fontdef_tl
523     \@@_font_set:Nnn \l_fontspec_font {\l_@@_fontdef_tl} {\f@size pt}
524     \@@_set_font_type:
525     \bool_if:NTF \l_@@_ot_bool
526     {
527       \tl_set:Nn \l_fontspec_script_tl {#1}
528       \fontspec_iv_str_to_num:Nn \l_fontspec_script_int {#1}
529       \fontspec_check_lang:nTF {#2} \prg_return_true: \prg_return_false:
530     }
531     { \prg_return_false: }
532   }
533   { \prg_return_false: }
534 }

```

`\fontspec_if_current_script:nTF` Test whether the currently loaded font is using the specified raw OpenType script tag #1.

```

535 \prg_new_conditional:Nnn \fontspec_if_current_script:n {TF,T,F}
536 {
537   \fontspec_if_fontspec_font:TF
538   {
539     \prop_get:cnN {g_@_ \f@family _prop} {fontdef} \l_@@_fontdef_tl
540     \@@_font_set:Nnn \l_fontspec_font {\l_@@_fontdef_tl} {\f@size pt}
541     \@@_set_font_type:
542     \bool_if:NTF \l_@@_ot_bool
543     {
544       \prop_get:cnN {g_@_ \f@family _prop} {script-tag} \l_@@_tmp_tl

```

```

545     \str_if_eq:nVTF {#1} \l_@@_tmp_tl
546         {\prg_return_true:} {\prg_return_false:}
547     }
548     { \prg_return_false: }
549 }
550 { \prg_return_false: }
551 }

```

`\fontspec_if_current_language:nTF` Test whether the currently loaded font is using the specified raw OpenType language tag #1.

```

552 \prg_new_conditional:Nnn \fontspec_if_current_language:n {TF,T,F}
553 {
554   \fontspec_if_fontspec_font:TF
555   {
556     \prop_get:cnN {g_@@_ \f@family _prop} {fontdef} \l_@@_fontdef_tl
557     \@@_font_set:Nnn \l_fontspec_font {\l_@@_fontdef_tl} {\f@size pt}
558     \@@_set_font_type:
559     \bool_if:NTF \l_@@_ot_bool
560     {
561       \prop_get:cnN {g_@@_ \f@family _prop} {lang-tag} \l_@@_tmp_tl
562       \str_if_eq:nVTF {#1} \l_@@_tmp_tl
563       {\prg_return_true:} {\prg_return_false:}
564     }
565     { \prg_return_false: }
566   }
567   { \prg_return_false: }
568 }

```

`\fontspec_set_family:Nnn` #1 : family
 #2 : fontspec features
 #3 : font name

Defines a new font family from given *features* and *font*, and stores the name in the variable *family*. See the standard fontspec user commands for applications of this function.

We want to store the actual name of the font family within the *family* variable because the actual L^AT_EX family name is automatically generated by fontspec and it's easier to keep it that way.

Please use `\fontspec_set_family:Nnn` instead of `\fontspec_select:nn`, which may change in the future.

```

569 \cs_new:Nn \fontspec_set_family:Nnn
570 {
571   \tl_set:Nn \l_@@_family_label_tl { #1 }
572   \fontspec_select:nn {#2}{#3}
573   \tl_set_eq:NN #1 \l_fontspec_family_tl
574 }
575 \cs_generate_variant:Nn \fontspec_set_family:Nnn {c}

```

`\fontspec_set_fontface:NNnn`

```

576 \cs_new:Nn \fontspec_set_fontface:NNnn
577 {

```

```

578 \tl_set:Nn \l_@@_family_label_tl { #1 }
579 \fontspec_select:nn {#3}{#4}
580 \tl_set_eq:NN #1 \l_fontspec_font
581 \tl_set_eq:NN #2 \l_fontspec_family_tl
582 }

```

27 Internals

27.1 Internal macros

The macros from here in are used internally by all those defined above. They are not designed to remain consistent between versions.

`\fontspec_select:nn` This is the command that defines font families for use, the underlying procedure of all `\fontspec`-like commands. Given a list of font features (#1) for a requested font (#2), it will define an NFSS family for that font and put the family name (globally) into `\l_fontspec_family_tl`. The \TeX `\font` command is (globally) stored in `\l_fontspec_font`.

This macro does its processing inside a group to attempt to restrict the scope of its internal processing. This works to some degree to insulate the internal commands from having to be manually cleared.

Some often-used variables to know about:

- `\l_fontspec_fontname_tl` is used as the generic name of the font being defined.
- `\l_@@_fontid_tl` is the unique identifier of the font with all its features.
- `\l_fontspec_fontname_up_tl` is the font specifically to be used as the upright font.
- `\l_@@_basename_tl` is the (immutable) original argument used for `*`-replacing.
- `\l_fontspec_font` is the plain \TeX font of the upright font requested.

```

583 \cs_set:Nn \fontspec_select:nn
584 {
585   \group_begin:
586   \@@_font_suppress_not_found_error:
587   \@@_init:
588
589   \tl_set:Nx \l_fontspec_fontname_tl   {#2}
590   \tl_set:Nx \l_fontspec_fontname_up_tl {#2}
591   \tl_set:Nx \l_@@_basename_tl        {#2}
592
593   \@@_load_external_fontoptions:Nn \l_fontspec_fontname_tl {#2}
594   \@@_extract_all_features:n {#1}
595   \@@_preparse_features:
596
597   \@@_load_font:
598   \@@_set_scriptlang:
599   \@@_get_features:Nn \l_@@_rawfeatures_sclist {}

```

```

600 \bool_set_false:N \l_@@_firsttime_bool
601
602 \@@_save_family:nTF {#2}
603 {
604   \@@_save_fontinfo:
605   \@@_find_autofonts:
606   \DeclareFontFamily{\l_@@_nfss_enc_tl}{\l_fontspeg_family_tl}{}
607   \@@_set_faces:
608   \@@_info:nxx {defining-font} {#1} {#2}
609 (*debug)
610   \typeout{"\l_@@_fontid_tl"~ defined.}
611   \@@_warning:nxx {defining-font} {#1} {#2}
612 </debug>
613 }
614 {
615 (*debug)
616   \typeout{"\l_@@_fontid_tl"~ already~ defined~ apparently.}
617 </debug>
618 }
619 \group_end:
620 }

```

\load_external_fontoptions:Nn Load a possible .fontspec font configuration file. This file could set font-specific options for the font about to be loaded.

```

621 \cs_new:Nn \@@_load_external_fontoptions:Nn
622 {
623   \@@_sanitise_fontname:Nn #1 {#2}
624   \tl_set:Nx \l_@@_ext_filename_tl {#1.fontspec}
625   \tl_remove_all:Nn \l_@@_ext_filename_tl {~}
626   \prop_if_in:NVF \g_@@_fontopts_prop #1
627   {
628     \exp_args:No \file_if_exist:nT { \l_@@_ext_filename_tl }
629     { \file_input:n { \l_@@_ext_filename_tl } }
630   }
631 }

```

\@@_extract_features:

```

632 \cs_new:Nn \@@_extract_all_features:n
633 {
634   \bool_if:NTF \l_@@_disable_defaults_bool
635   {
636     \clist_set:Nx \l_@@_all_features_clist {#1}
637   }
638   {
639     \prop_get:NVNF \g_@@_fontopts_prop \l_fontspeg_fontname_tl \l_@@_fontopts_clist
640     { \clist_clear:N \l_@@_fontopts_clist }
641   }
642   \prop_get:NVNF \g_@@_fontopts_prop \l_@@_family_label_tl \l_@@_family_fontopts_clist
643   { \clist_clear:N \l_@@_family_fontopts_clist }
644   \tl_clear:N \l_@@_family_label_tl
645 }

```

```

646 \clist_set:Nx \l_@@_all_features_clist
647 {
648   \g_@@_default_fontopts_clist,
649   \l_@@_family_fontopts_clist,
650   \l_@@_fontopts_clist,
651   #1
652 }
653 }
654 \tl_set:Nx \l_@@_fontid_tl { \tl_to_str:N \l_fontspec_fontname_tl-:\tl_to_str:N \l_@@_all_features_clist }
655 (*debug)
656 \typeout{fontid: \l_@@_fontid_tl}
657 (/debug)
658 }

```

\@@_preparse_features: #1 : feature options

#2 : font name

Perform the (multi-step) feature parsing process.

Convert the requested features to font definition strings. First the features are parsed for information about font loading (whether it's a named font or external font, etc.), and then information is extracted for the names of the other shape fonts.

```
659 \cs_new:Nn \@@_preparse_features:
```

```
660 {
```

Detect if external fonts are to be used, possibly automatically, and parse fontspec features for bold/italic fonts and their features.

```
661 \@@_if_detect_external:VT \l_@@_basename_tl
```

```
662 { \keys_set:nn {fontspec-preparse-external} {ExternalLocation} }
```

```
663
```

```
664 \keys_set_known:nxN {fontspec-preparse-external}
```

```
665 { \l_@@_all_features_clist }
```

```
666 \l_@@_keys_leftover_clist
```

When `\l_fontspec_fontname_tl` is augmented with a prefix or whatever to create the name of the upright font (`\l_fontspec_fontname_up_tl`), this latter is the new 'general font name' to use.

```
667 \tl_set_eq:NN \l_fontspec_fontname_tl \l_fontspec_fontname_up_tl
```

```
668 \keys_set_known:nxN {fontspec-renderer} {\l_@@_keys_leftover_clist}
```

```
669 \l_@@_keys_leftover_clist
```

```
670 \keys_set_known:nxN {fontspec-preparse} {\l_@@_keys_leftover_clist}
```

```
671 \l_@@_fontfeat_clist
```

```
672 }
```

\@@_load_font:

```
673 \cs_new:Nn \@@_load_font:
```

```
674 {
```

```
675 \@@_font_set:Nnn \l_fontspec_font
```

```
676 { \@@_fullname:n {\l_fontspec_fontname_up_tl} } {\f@size pt}
```

```
677 \@@_font_if_null:NT \l_fontspec_font { \@@_error:nx {font-not-found} {\l_fontspec_fontname_up_tl}
```

```
678 \@@_set_font_type:
```

```
679 \@@_font_gset:Nnn \l_fontspec_font
```

```
680 { \@@_fullname:n {\l_fontspec_fontname_up_tl} } {\f@size pt}
```

```
681 \l_fontspec_font % this is necessary for LuaLaTeX to check the scripts properly
```

```
682 }
```

`\@@_if_detect_external:nnT` Check if either the fontname ends with a known font extension.

```
683 \prg_new_conditional:Nnn \@@_if_detect_external:n {T}
684 {
685   \clist_map_inline:Nn \l_@@_extensions_clist
686   {
687     \bool_set_false:N \l_@@_tmpa_bool
688     \tl_if_in:nnT {#1 <= end_of_string} {##1 <= end_of_string}
689     { \bool_set_true:N \l_@@_tmpa_bool \clist_map_break: }
690   }
691   \bool_if:NTF \l_@@_tmpa_bool \prg_return_true: \prg_return_false:
692 }
693 \cs_generate_variant:Nn \@@_if_detect_external:nT {V}
```

`\@@_fullname:n` Constructs the complete font name based on a common piece of info.

```
694 \cs_set:Nn \@@_fullname:n
695 {
696   \@@_namewrap:n { #1 \l_@@_extension_tl }
697   \l_fontspec_renderer_tl
698   \l_@@_optical_size_tl
699 }
```

`\@@_set_scriptlang:` Only necessary for OpenType fonts. First check if the font supports scripts, then apply defaults if none are explicitly requested. Similarly with the language settings.

```
700 \cs_new:Nn \@@_set_scriptlang:
701 {
702   \bool_if:NT \l_@@_firsttime_bool
703   {
704     \tl_if_empty:NTF \l_@@_script_name_tl
705     {
706       \fontspec_check_script:nTF {latn}
707       {
708         \tl_set:Nn \l_@@_script_name_tl {Latin}
709         \tl_if_empty:NT \l_@@_lang_name_tl
710         {
711           \tl_set:Nn \l_@@_lang_name_tl {Default}
712         }
713         \keys_set:nx {fontspec} {Script=\l_@@_script_name_tl}
714         \keys_set:nx {fontspec} {Language=\l_@@_lang_name_tl}
715       }
716     }
717     \@@_info:n {no-scripts}
718   }
719 }
720 {
721   \tl_if_empty:NT \l_@@_lang_name_tl
722   {
723     \tl_set:Nn \l_@@_lang_name_tl {Default}
724   }
}
```

```

725     \keys_set:nx {fontspec} {Script=\l_@@_script_name_tl}
726     \keys_set:nx {fontspec} {Language=\l_@@_lang_name_tl}
727   }
728 }
729 }

```

`\@@_save_family:nTF` Check if the family is unique and, if so, save its information. (`\addfontfeature` and other macros use this data.) Then the font family and its shapes are defined in the NFSS.

Now we have a unique (in fact, too unique!) string that contains the family name and every option in abbreviated form. This is used with a counter to create a simple NFSS family name for the font we're selecting.

```

730 \prg_new_conditional:Nnn \@@_save_family:n {TF}
731 {
732 (debug)\typeout{save~ family:~ #1}
733   \cs_if_exist:NT \l_@@_nfss_fam_tl
734   {
735     \cs_set_eq:cn {g_@@_UID_\l_@@_fontid_tl} \l_@@_nfss_fam_tl
736   }
737   \cs_if_exist:cF {g_@@_UID_\l_@@_fontid_tl}
738   {
739     % The font name is fully expanded, in case it's defined in terms of macros, before having its space
740     \tl_set:Nx \l_@@_tmp_tl {#1}
741     \tl_remove_all:Nn \l_@@_tmp_tl {~}
742
743     \cs_if_exist:cTF {g_@@_family_ \l_@@_tmp_tl _int}
744     { \int_gincr:c {g_@@_family_ \l_@@_tmp_tl _int} }
745     { \int_new:c {g_@@_family_ \l_@@_tmp_tl _int} }
746
747     \tl_gset:cx {g_@@_UID_\l_@@_fontid_tl}
748     {
749       \l_@@_tmp_tl ( \int_use:c {g_@@_family_ \l_@@_tmp_tl _int} )
750     }
751   }
752   \tl_gset:Nv \l_fontspeg_family_tl {g_@@_UID_\l_@@_fontid_tl}
753   \cs_if_exist:cTF {g_@@_ \l_fontspeg_family_tl _prop}
754   \prg_return_false: \prg_return_true:
755 }

```

`\@@_save_fontinfo:nn` Saves the relevant font information for future processing.

```

756 \cs_new:Nn \@@_save_fontinfo:
757 {
758   \prop_new:c {g_@@_ \l_fontspeg_family_tl _prop}
759   \prop_gput:cnx {g_@@_ \l_fontspeg_family_tl _prop} {fontname} { \l_@@_basename_tl }
760   \prop_gput:cnx {g_@@_ \l_fontspeg_family_tl _prop} {options} { \l_@@_all_features_clist }
761   \prop_gput:cnx {g_@@_ \l_fontspeg_family_tl _prop} {fontdef}
762   {
763     \@@_fullname:n { \l_fontspeg_fontname_tl } :
764     \l_@@_pre_feat_sclist \l_@@_rawfeatures_sclist
765   }
766   \prop_gput:cnv {g_@@_ \l_fontspeg_family_tl _prop} {script-num} \l_fontspeg_script_int

```

```

767 \prop_gput:cnV {g_@_ \l_fontspec_family_tl _prop} {lang-num} \l_fontspec_language_int
768 \prop_gput:cnV {g_@_ \l_fontspec_family_tl _prop} {script-tag} \l_fontspec_script_tl
769 \prop_gput:cnV {g_@_ \l_fontspec_family_tl _prop} {lang-tag} \l_fontspec_lang_tl
770
771 }

```

27.1.1 Setting font shapes in a family

All NFSS specifications take their default values, so if any of them are redefined, the shapes will be selected to fit in with the current state. For example, if `\bfdefault` is redefined to `b`, all bold shapes defined by this package will also be assigned to `b`.

The combination shapes are searched first because they use information that may be redefined in the single cases. E.g., if no bold font is specified then `set_autofont` will attempt to set it. This has subtle/small ramifications on the logic of choosing the bold italic font.

`\@@_find_autofonts:`

```

772 \cs_new:Nn \@@_find_autofonts:
773 {
774   \bool_if:nF {\l_@@_noit_bool || \l_@@_nobf_bool}
775   {
776     \@@_set_autofont:Nnn \l_fontspec_fontname_bfit_tl {\l_fontspec_fontname_it_tl} {/B}
777     \@@_set_autofont:Nnn \l_fontspec_fontname_bfit_tl {\l_fontspec_fontname_bf_tl} {/I}
778     \@@_set_autofont:Nnn \l_fontspec_fontname_bfit_tl {\l_fontspec_fontname_tl} {/BI}
779   }
780
781   \bool_if:NF \l_@@_nobf_bool
782   {
783     \@@_set_autofont:Nnn \l_fontspec_fontname_bf_tl {\l_fontspec_fontname_tl} {/B}
784   }
785
786   \bool_if:NF \l_@@_noit_bool
787   {
788     \@@_set_autofont:Nnn \l_fontspec_fontname_it_tl {\l_fontspec_fontname_tl} {/I}
789   }
790
791   \@@_set_autofont:Nnn \l_fontspec_fontname_bfsl_tl {\l_fontspec_fontname_sl_tl} {/B}
792 }

```

`\@@_set_faces:`

```

793 \cs_new:Nn \@@_set_faces:
794 {
795   \@@_add_nfssfont:nnnn \mddefault \updefault \l_fontspec_fontname_tl \l_@@_fontfeat_up_clist
796   \@@_add_nfssfont:nnnn \bfdefault \updefault \l_fontspec_fontname_bf_tl \l_@@_fontfeat_bf_clist
797   \@@_add_nfssfont:nnnn \mddefault \itdefault \l_fontspec_fontname_it_tl \l_@@_fontfeat_it_clist
798   \@@_add_nfssfont:nnnn \mddefault \sldefault \l_fontspec_fontname_sl_tl \l_@@_fontfeat_sl_clist
799   \@@_add_nfssfont:nnnn \bfdefault \itdefault \l_fontspec_fontname_bfit_tl \l_@@_fontfeat_bfit_clis
800   \@@_add_nfssfont:nnnn \bfdefault \sldefault \l_fontspec_fontname_bfsl_tl \l_@@_fontfeat_bfsl_clis
801
802   \prop_map_inline:Nn \l_@@_nfssfont_prop { \@@_set_faces_aux:nnnn ##2 }

```

```

803 }
804 \cs_new:Nn \@@_set_faces_aux:nnnn
805 {
806   \fontspec_complete_fontname:Nn \l_@@_curr_fontname_tl {#3}
807   \@@_make_font_shapes:Nnnn \l_@@_curr_fontname_tl {#1} {#2} {#4} {#5}
808 }

```

27.1.2 Fonts

`\@@_set_font_type:` Now check if the font is to be rendered with `ATSUI` or `Harfbuzz`. This will either be automatic (based on the font type), or specified by the user via a font feature.

This macro sets booleans accordingly depending if the font in `\l_fontspec_font` is an AAT font or an OpenType font or a font with feature axes (either AAT or Multiple Master), respectively.

```

809 \cs_new:Nn \@@_set_font_type:
810 (*xetexx)
811 {
812   \bool_set_false:N \l_@@_tfm_bool
813   \bool_set_false:N \l_@@_atsui_bool
814   \bool_set_false:N \l_@@_ot_bool
815   \bool_set_false:N \l_@@_mm_bool
816   \bool_set_false:N \l_@@_graphite_bool
817   \ifcase\XeTeXfonttype\l_fontspec_font
818     \bool_set_true:N \l_@@_tfm_bool
819   \or
820     \bool_set_true:N \l_@@_atsui_bool
821     \ifnum\XeTeXcountvariations\l_fontspec_font > \c_zero
822       \bool_set_true:N \l_@@_mm_bool
823     \fi
824   \or
825     \bool_set_true:N \l_@@_ot_bool
826   \fi

```

If automatic, the `\l_fontspec_renderer_tl` token list will still be empty (other suffixes that could be added will be later in the feature processing), and if it is indeed still empty, assign it a value so that the other weights of the font are specifically loaded with the same renderer.

```

827   \tl_if_empty:NT \l_fontspec_renderer_tl
828     {
829       \bool_if:NTF \l_@@_atsui_bool
830         { \tl_set:Nn \l_fontspec_renderer_tl {/AAT} }
831       {
832         \bool_if:NT \l_@@_ot_bool
833           { \tl_set:Nn \l_fontspec_renderer_tl {/OT} }
834       }
835     }
836 }
837 /xetexx
838 *luatex
839 {
840   \bool_set_true:N \l_@@_ot_bool

```

```
841 }
842 </luatex>
```

```
\@@_set_autofont:Nnn #1 : Font name tl
#2 : Base font name
#3 : Font name modifier
```

This function looks for font with $\langle name \rangle$ and $\langle modifier \rangle$ #2#3, and if found (i.e., different to font with name #2) stores it in tl #1. A modifier is something like /B to look for a bold font, for example.

We can't match external fonts in this way (in $X_{\text{E}}\text{TeX}$ anyway; todo: test with LuaTeX). If $\langle font\ name\ tl \rangle$ is not empty, then it's already been specified by the user so abort. If $\langle Base\ font\ name \rangle$ is not given, we also abort for obvious reasons.

If $\langle font\ name\ tl \rangle$ is empty, then proceed. If not found, $\langle font\ name\ tl \rangle$ remains empty. Otherwise, we have a match.

```
843 \cs_generate_variant:Nn \tl_if_empty:nF {x}
844 \cs_new:Nn \@@_set_autofont:Nnn
845 {
846   \bool_if:NF \l_@@_external_bool
847   {
848     \tl_if_empty:xF {#2}
849     {
850       \tl_if_empty:NT #1
851       {
852         \@@_if_autofont:nnTF {#2} {#3}
853         { \tl_set:Nx #1 {#2#3} }
854         { \@@_info:nx {no-font-shape} {#2#3} }
855       }
856     }
857   }
858 }
859
860 \prg_new_conditional:Nnn \@@_if_autofont:nn {T,TF}
861 {
862   \@@_font_set:Nnn \l_tmpa_font { \@@_fullname:n {#1} } {\f@size pt}
863   \@@_font_set:Nnn \l_tmpb_font { \@@_fullname:n {#1#2} } {\f@size pt}
864   \str_if_eq_x:nnTF { \fontname \l_tmpa_font } { \fontname \l_tmpb_font }
865   { \prg_return_false: }
866   { \prg_return_true: }
867 }
```

```
\@@_make_font_shapes:Nnnnn #1 : Font name
#2 : Font series
#3 : Font shape
#4 : Font features
#5 : Size features
```

This macro eventually uses `\DeclareFontShape` to define the font shape in question.

```
868 \cs_new:Nn \@@_make_font_shapes:Nnnnn
869 {
870   \group_begin:
```

```

871 \keys_set_known:nxN {fontspec-preparse-external} { #4 } \l_@@_leftover_clist
872 \l_@@_load_fontname:n {#1}
873 \l_@@_declare_shape:nxxx {#2} {#3} { \l_@@_fontopts_clist, \l_@@_leftover_clist } {#5}
874 \group_end:
875 }
876
877 \cs_new:Nn \l_@@_load_fontname:n
878 {
879 \l_@@_load_external_fontoptions:Nn \l_fontspect_fontname_tl {#1}
880 \prop_get:NVNF \g_@@_fontopts_prop \l_fontspect_fontname_tl \l_@@_fontopts_clist
881 { \clist_clear:N \l_@@_fontopts_clist }
882 \l_@@_font_set:Nnn \l_fontspect_font { \l_@@_fullname:n { \l_fontspect_fontname_tl } } { \f@size pt }
883 \l_@@_font_if_null:NT \l_fontspect_font { \l_@@_error:nx {font-not-found} {#1} }
884 }

```

```

\l_@@_declare_shape:nnnn #1 : Font series
                        #2 : Font shape
                        #3 : Font features
                        #4 : Size features

```

Wrapper for `\DeclareFontShape`. And finally the actual font shape declaration using `\l_@@_nfss_tl` defined above. `\l_@@_postadjust_tl` is defined in various places to deal with things like the hyphenation character and interword spacing.

The main part is to loop through `SizeFeatures` arguments, which are of the form

$$\text{SizeFeatures}=\{\langle\text{one}\rangle,\langle\text{two}\rangle,\langle\text{three}\rangle\}.$$

```

885 \cs_new:Nn \l_@@_declare_shape:nnnn
886 {
887 \tl_clear:N \l_@@_nfss_tl
888 \tl_clear:N \l_@@_nfss_sc_tl
889 \tl_set_eq:NN \l_@@_saved_fontname_tl \l_fontspect_fontname_tl
890
891 \exp_args:Nx \clist_map_inline:nn {#4}
892 {
893 \tl_clear:N \l_@@_size_tl
894 \tl_set_eq:NN \l_@@_sizedfont_tl \l_@@_saved_fontname_tl % in case not spec'ed
895
896 \keys_set_known:nxN {fontspec-sizing} { \exp_after:wN \use:n ##1 }
897 \l_@@_sizing_leftover_clist
898 \tl_if_empty:NT \l_@@_size_tl { \l_@@_error:n {no-size-info} }
899
900 % "normal"
901 \l_@@_load_fontname:n { \l_@@_sizedfont_tl }
902 \l_@@_setup_nfss:Nnn \l_@@_nfss_tl {#3} {}
903
904 % small caps
905 \clist_set_eq:NN \l_@@_fontfeat_curr_clist \l_@@_fontfeat_sc_clist
906
907 \bool_if:NF \l_@@_nosc_bool
908 {
909 \tl_if_empty:NTF \l_fontspect_fontname_sc_tl
910 {

```

```

911 <debug>      \typeout{Attempting~ small~ caps?}
912      \@@_make_smallcaps:TF
913      {
914 <debug>      \typeout{Small~ caps~ found.}
915      \clist_put_left:Nn \l_@@_fontfeat_curr_clist {Letters=SmallCaps}
916      }
917      {
918 <debug>      \typeout{Small~ caps~ not~ found.}
919      \bool_set_true:N \l_@@_nosc_bool
920      }
921      }
922      { \@@_load_fontname:n { \l_fontspeg_fontname_sc_tl } }% local for each size
923      }
924
925      \bool_if:NF \l_@@_nosc_bool
926      {
927      \@@_setup_nfss:Nnn \l_@@_nfss_sc_tl {#3} { \l_@@_fontfeat_curr_clist }
928      }
929
930      }
931
932      \@@_declare_shapes_normal:nn {#1} {#2}
933      \@@_declare_shapes_smcaps:nn {#1} {#2}
934      \@@_declare_shape_slanted:nn {#1} {#2}
935      \@@_declare_shape_loginfo:nn {#1} {#2}
936      }
937 \cs_generate_variant:Nn \@@_declare_shape:nnnn {nnxx}
938
939 \cs_new:Nn \@@_setup_nfss:Nnn
940 {
941   \@@_get_features:Nn \l_@@_rawfeatures_sclist
942   { #2 , \l_@@_sizing_leftover_clist , #3 }
943
944   \tl_put_right:Nx #1
945   {
946     <\l_@@_size_tl> \l_@@_scale_tl
947     \@@_fontwrap:n
948     {
949       \@@_fullname:n { \l_fontspeg_fontname_tl }
950       : \l_@@_pre_feat_sclist \l_@@_rawfeatures_sclist
951     }
952   }
953 }
954
955 \cs_new:Nn \@@_declare_shapes_normal:nn
956 {
957   \@@_DeclareFontShape:xxxxxx { \l_@@_nfss_enc_tl } { \l_fontspeg_family_tl }
958   {#1} {#2} { \l_@@_nfss_tl } { \l_@@_postadjust_tl }
959 }
960
961 \cs_new:Nn \@@_declare_shapes_smcaps:nn

```

```

962 {
963   \bool_if:NF \l_@@_nosc_bool
964   {
965     \@@_DeclareFontShape:xxxxxx {\l_@@_nfss_enc_tl} {\l_fontspeg_family_tl} {#1}
966     { \@@_combo_sc_shape:n {#2} } {\l_@@_nfss_sc_tl} {\l_@@_postadjust_tl}
967   }
968 }
969 \cs_new:Nn \@@_combo_sc_shape:n
970 {
971   \tl_if_exist:cTF { \@@_shape_merge:nn {#1} {\scdefault} }
972   { \tl_use:c { \@@_shape_merge:nn {#1} {\scdefault} } }
973   { \scdefault }
974 }
975
976 \cs_new:Nn \@@_DeclareFontShape:nnnnnn
977 {
978   \group_begin:
979   \normalsize
980   \cs_undefine:c {#1/#2/#3/#4/\f@size}
981   \group_end:
982   \DeclareFontShape{#1}{#2}{#3}{#4}{#5}{#6}
983 }
984 \cs_generate_variant:Nn \@@_DeclareFontShape:nnnnnn {xxxxxx}

```

This extra stuff for the slanted shape substitution is a little bit awkward. We define the slanted shape to be a synonym for it when (a) we're defining an italic font, but also (b) when the default slanted shape isn't 'it'. (Presumably this turned up once in a test and I realised it caused problems. I doubt this would happen much.)

We should test when a slanted font has been specified and not run this code if so, but the \@@_set_slanted: code will overwrite this anyway if necessary.

```

985 \cs_new:Nn \@@_declare_shape_slanted:nn
986 {
987   \bool_if:nT
988   {
989     \str_if_eq_x_p:nn {#2} {\itdefault} &&
990     !(\str_if_eq_x_p:nn {\itdefault} {\sldefault})
991   }
992   {
993     \@@_DeclareFontShape:xxxxxx {\l_@@_nfss_enc_tl}{\l_fontspeg_family_tl}{#1}{\sldefault}
994     {<->ssub*\l_fontspeg_family_tl/#1/\itdefault}{\l_@@_postadjust_tl}
995   }
996 }

```

Lastly some informative messaging.

```

997 \cs_new:Nn \@@_declare_shape_loginfo:nn
998 {
999   \tl_gput_right:Nx \l_fontspeg_defined_shapes_tl
1000   {
1001     ~ \exp_not:N \str_case:nn {#1/#2}
1002     {
1003       {\mddefault/\updefault} {'normal'~}
1004       {\bfdefault/\updefault} {'bold'~}

```

```

1005     {\mddefault/\itdefault} {'italic'~}
1006     {\mddefault/\sldefault} {'slanted'~}
1007     {\bfdefault/\itdefault} {'bold~ italic'~}
1008     {\bfdefault/\sldefault} {'bold~ slanted'~}
1009   } (#1/#2)~
1010 with~ NFSS~ spec.:~
1011 \l_@@_nfss_tl
1012 \exp_not:n { \ }
1013 -~ \exp_not:N \str_case:nn { #1 / \@@_combo_sc_shape:n {#2} }
1014 {
1015   {\mddefault/\scdefault} {'small~ caps'~}
1016   {\bfdefault/\scdefault} {'bold~ small~ caps'~}
1017   {\mddefault/\itscdefault} {'italic~ small~ caps'~}
1018   {\bfdefault/\itscdefault} {'bold~ italic~ small~ caps'~}
1019   {\mddefault/\slscdefault} {'slanted~ small~ caps'~}
1020   {\bfdefault/\slscdefault} {'bold~ slanted~ small~ caps'~}
1021 }~( #1 / \@@_combo_sc_shape:n {#2} )~
1022 with~ NFSS~ spec.:~
1023 \l_@@_nfss_sc_tl
1024 \tl_if_empty:FF {\l_@@_postadjust_tl}
1025 {
1026   \exp_not:N \ and~ font~ adjustment~ code: \exp_not:N \ \l_@@_postadjust_tl
1027 }
1028 }
1029 }
1030 \cs_generate_variant:Nn \tl_if_empty:nF {f}
  Maybe \str_if_eq_x:nnF would be better?

```

`\l_@@_pre_feat_sclist` These are the features always applied to a font selection before other features.

```

1031 \clist_set:Nn \l_@@_pre_feat_sclist
1032 <*xetex>
1033 {
1034   \bool_if:NT \l_@@_ot_bool
1035   {
1036     \tl_if_empty:NF \l_fontspeg_script_tl
1037     {
1038       script = \l_fontspeg_script_tl ;
1039       language = \l_fontspeg_lang_tl ;
1040     }
1041   }
1042 }
1043 </xetex>
1044 <*luatex>
1045 {
1046   mode = \l_fontspeg_mode_tl ;
1047   \tl_if_empty:NF \l_fontspeg_script_tl
1048   {
1049     script = \l_fontspeg_script_tl ;
1050     language = \l_fontspeg_lang_tl ;
1051   }
1052 }

```

1053 \langle /luatex \rangle

27.1.3 Features

\backslash @_get_features:Nn This macro is a wrapper for \backslash keys_set:n which expands and adds a default specification to the original passed options. It begins by initialising the commands used to hold font-feature specific strings. Its argument is any additional features to prepend to the default.

```
1054 \cs_set:Nn \@@_get_features:Nn
1055 {
1056   \sclist_clear:N \l_@@_rawfeatures_sclist
1057   \tl_clear:N \l_@@_scale_tl
1058   \tl_set_eq:NN \l_@@_opacity_tl \g_@@_opacity_tl
1059   \tl_set_eq:NN \l_@@_hexcol_tl \g_@@_hexcol_tl
1060   \tl_set_eq:NN \l_@@_postadjust_tl \g_@@_postadjust_tl
1061   \tl_clear:N \l_@@_wordspace_adjust_tl
1062   \tl_clear:N \l_@@_punctspace_adjust_tl
1063
1064   \keys_set_known:nxN {fontspec-renderer} {\l_@@_fontfeat_clist,#2}
1065   \l_@@_keys_leftover_clist
1066   \keys_set:nx {fontspec} {\l_@@_keys_leftover_clist}
```

Finish the colour specification. Do not set the colour if not explicitly spec'd else \backslash color (using specials) will not work.

```
1067   \str_if_eq:x:nNF { \l_@@_hexcol_tl \l_@@_opacity_tl }
1068     { \g_@@_hexcol_tl \g_@@_opacity_tl }
1069   {
1070     \@@_update_featstr:n { color = \l_@@_hexcol_tl\l_@@_opacity_tl }
1071   }
1072
1073   \tl_set_eq:NN #1 \l_@@_rawfeatures_sclist
1074 }
```

\backslash @_init: Initialisations that either need to occur globally: (all setting of these variables is done locally inside a group)

```
1075 \tl_clear:N \l_@@_family_label_tl
1076 \tl_clear:N \l_fontspec_fontname_bf_tl
1077 \tl_clear:N \l_fontspec_fontname_it_tl
1078 \tl_clear:N \l_fontspec_fake_slant_tl
1079 \tl_clear:N \l_fontspec_fake_embolden_tl
1080 \tl_clear:N \l_fontspec_fontname_bfit_tl
1081 \tl_clear:N \l_fontspec_fontname_sl_tl
1082 \tl_clear:N \l_fontspec_fontname_bfsl_tl
1083 \tl_clear:N \l_fontspec_fontname_sc_tl
1084 \tl_clear:N \l_@@_fontfeat_up_clist
1085 \tl_clear:N \l_@@_fontfeat_bf_clist
1086 \tl_clear:N \l_@@_fontfeat_it_clist
1087 \tl_clear:N \l_@@_fontfeat_bfit_clist
1088 \tl_clear:N \l_@@_fontfeat_sl_clist
1089 \tl_clear:N \l_@@_fontfeat_bfsl_clist
1090 \tl_clear:N \l_@@_fontfeat_sc_clist
```

```

1091 \tl_clear:N \l_@@_script_name_tl
1092 \tl_clear:N \l_fontspeg_script_tl
1093 \tl_clear:N \l_@@_lang_name_tl
1094 \tl_clear:N \l_fontspeg_lang_tl
1095 \tl_set:Nn \g_@@_postadjust_tl { \l_@@_wordspace_adjust_tl \l_@@_punctspace_adjust_tl }
1096
1097 \clist_set:Nn \l_@@_sizefeat_clist {Size={-}}
1098 \tl_new:N \g_@@_hexcol_tl
1099 \tl_new:N \g_@@_opacity_tl
1100 \tl_set:Nn \g_@@_hexcol_tl {000000}
1101 \tl_set:Nn \g_@@_opacity_tl {FF~}

```

Or once per fontspec font invocation: (Some of these may be redundant. Check whether they're assigned to globally or not.)

```

1102 \cs_set:Npn \@@_init:
1103 {
1104   \bool_set_false:N \l_@@_ot_bool
1105   \bool_set_true:N \l_@@_firsttime_bool
1106   \cs_set:Npn \@@_namewrap:n ##1 { ##1 }
1107   \tl_clear:N \l_@@_optical_size_tl
1108   \tl_clear:N \l_fontspeg_renderer_tl
1109   \tl_clear:N \l_fontspeg_defined_shapes_tl
1110   \tl_clear:N \g_@@_curr_series_tl
1111   \tl_gset_eq:NN \l_@@_nfss_enc_tl \g_fontspeg_encoding_tl
1112
1113   % This is for detecting font families when assigning default features.
1114   % Replace defaults for the standard families because they're not set in the usual way:
1115   \exp_args:NV \str_case:nnF {\l_@@_family_label_tl}
1116     {
1117       {\rmdefault} { \tl_set:Nn \l_@@_family_label_tl {\g_@@_rmfamily_family} }
1118       {\sfdefault} { \tl_set:Nn \l_@@_family_label_tl {\g_@@_sffamily_family} }
1119       {\ttdefault} { \tl_set:Nn \l_@@_family_label_tl {\g_@@_ttfamily_family} }
1120     }{}
1121
1122   \<lua>
1123   \tl_set:Nn \l_fontspeg_mode_tl {node}
1124   \int_set:Nn \luatex_prehyphenchar:D { '\- } % fixe
1125   \int_zero:N \luatex_posthyphenchar:D      % fixe
1126   \int_zero:N \luatex_preexhyphenchar:D     % fixe
1127   \int_zero:N \luatex_postexhyphenchar:D    % fixe
1128   \</lua>
1129 }

```

\@@_make_smallcaps:TF This macro checks if the font contains small caps.

```

1130 \cs_set:Nn \fontspec_make_ot_smallcaps:TF
1131 {
1132   \fontspec_check_ot_feat:nTF {+smcp} {#1} {#2}
1133 }
1134 \<xtex>
1135 \cs_set:Nn \@@_make_smallcaps:TF
1136 {
1137   \bool_if:NTF \l_@@_ot_bool

```

```

1138 { \fontspec_make_ot_smallcaps:TF {#1} {#2} }
1139 {
1140   \bool_if:NT \l_@@_atsui_bool
1141   { \fontspec_make_AAT_feature_string:nnTF {3}{3} {#1} {#2} }
1142 }
1143 }
1144 </xetex>
1145 <*luatex>
1146 \cs_set_eq:NN \@@_make_smallcaps:TF \fontspec_make_ot_smallcaps:TF
1147 </luatex>

```

`\sclist_put_right:Nn` I'm hardly going to write an 'sclist' module but a couple of functions are useful. Here, items in semi-colon lists are always followed by a semi-colon (as opposed to the s.-c's being placed between elements) so we can append sclists without worrying about it.

```

1148 \cs_set_eq:NN \sclist_clear:N \tl_clear:N
1149 \cs_new:Nn \sclist_gput_right:Nn
1150 { \tl_gput_right:Nn #1 {#2;} }
1151 \cs_generate_variant:Nn \sclist_gput_right:Nn {Nx}

```

`\@@_update_featstr:n` `\l_@@_rawfeatures_sclist` is the string used to define the list of specific font features. Each time another font feature is requested, this macro is used to add that feature to the list. Font features are separated by semicolons.

```

1152 \cs_new:Nn \@@_update_featstr:n
1153 {
1154   \bool_if:NF \l_@@_firsttime_bool
1155   {
1156     \sclist_gput_right:Nx \l_@@_rawfeatures_sclist {#1}
1157   }
1158 }

```

`\fontspec_make_feature:nnn` This macro is called by each feature key selected, and runs according to which type of font is selected.

```

1159 \cs_new:Nn \fontspec_make_feature:nnn
1160 <*xetex>
1161 {
1162   \bool_if:NTF \l_@@_ot_bool
1163   { \fontspec_make_OT_feature:n {#3} }
1164   {
1165     \bool_if:NT \l_@@_atsui_bool
1166     { \fontspec_make_AAT_feature:nn {#1}{#2} }
1167   }
1168 }
1169 </xetex>
1170 <*luatex>
1171 { \fontspec_make_OT_feature:n {#3} }
1172 </luatex>
1173 \cs_generate_variant:Nn \fontspec_make_feature:nnn {nnx}
1174 \cs_new:Nn \fontspec_make_AAT_feature:nn
1175 {

```

```

1176 \tl_if_empty:nTF {#1}
1177 { \@@_warning:n {aat-feature-not-exist} }
1178 {
1179   \fontspec_make_AAT_feature_string:nnTF {#1}{#2}
1180   {
1181     \@@_update_featstr:n {\l_fontspec_feature_string_tl}
1182   }
1183   { \@@_warning:nx {aat-feature-not-exist-in-font} {#1,#2} }
1184 }
1185 }
1186 \cs_new:Nn \fontspec_make_OT_feature:n
1187 {
1188   \tl_if_empty:nTF {#1}
1189   { \@@_warning:n {icu-feature-not-exist} }
1190   {
1191     \fontspec_check_ot_feat:nTF {#1}
1192     {
1193       \@@_update_featstr:n {#1}
1194     }
1195     { \@@_warning:nx {icu-feature-not-exist-in-font} {#1} }
1196   }
1197 }
1198 \cs_new_protected:Nn \fontspec_make_numbered_feature:nn
1199 {
1200   \fontspec_check_ot_feat:nTF {#1}
1201   {
1202     \@@_update_featstr:n { #1 = #2 }
1203   }
1204   { \@@_warning:nx {icu-feature-not-exist-in-font} {#1} }
1205 }
1206 \cs_generate_variant:Nn \fontspec_make_numbered_feature:nn {xn}

```

\@@_define_font_feature:n These macros are used in order to simplify font feature definition later on.

```

\@@_define_feature_option:nnnnn 1207 \cs_new:Nn \@@_define_font_feature:n
spec_define_numbered_feat:nnnn 1208 {
1209   \keys_define:nn {fontspec} { #1 .multichoice: }
1210 }
1211 \cs_new:Nn \@@_define_feature_option:nnnnn
1212 {
1213   \keys_define:nn {fontspec}
1214   {
1215     #1/#2 .code:n = { \fontspec_make_feature:nnn{#3}{#4}{#5} }
1216   }
1217 }
1218 \cs_new:Nn \fontspec_define_numbered_feat:nnnn
1219 {
1220   \keys_define:nn {fontspec}
1221   {
1222     #1/#2 .code:n =
1223     { \fontspec_make_numbered_feature:nn {#3}{#4} }
1224   }
1225 }

```

`\fontspec_iv_str_to_num:Nn` This macro takes the numerical codes for a font feature and creates a specified macro containing the string required in the font definition to turn that feature on or off. Used primarily in [...], but also used to check if small caps exists in the requested font (see page 83).

For exclusive selectors, it's easy; just grab the string: For *non*-exclusive selectors, it's a little more complex. If the selector is even, it corresponds to switching the feature on. If the selector is *odd*, it corresponds to switching the feature off. But XeTeX doesn't return a selector string for this number, since the feature is defined for the 'switching on' value. So we need to check the selector of the previous number, and then prefix the feature string with ! to denote the switch.

Finally, save out the complete feature string in `\l_fontspec_feature_string_tl`.

```

1226 \prg_new_conditional:Nnn \fontspec_make_AAT_feature_string:nn {TF,T,F}
1227 {
1228   \tl_set:Nx \l_tmpa_tl { \XeTeXfeaturename \l_fontspec_font #1 }
1229   \tl_if_empty:NTF \l_tmpa_tl
1230   { \prg_return_false: }
1231   {
1232     \int_compare:NTF { \XeTeXisexclusivefeature\l_fontspec_font #1 > 0 }
1233     {
1234       \tl_set:Nx \l_tmpb_tl { \XeTeXselectorname\l_fontspec_font #1\space #2}
1235     }
1236     {
1237       \int_if_even:NTF {#2}
1238       {
1239         \tl_set:Nx \l_tmpb_tl { \XeTeXselectorname\l_fontspec_font #1\space #2}
1240       }
1241       {
1242         \tl_set:Nx \l_tmpb_tl
1243         {
1244           \XeTeXselectorname\l_fontspec_font #1\space \numexpr#2-1\relax
1245         }
1246         \tl_if_empty:NF \l_tmpb_tl { \tl_put_left:Nn \l_tmpb_tl {!} }
1247       }
1248     }
1249     \tl_if_empty:NTF \l_tmpb_tl
1250     { \prg_return_false: }
1251     {
1252       \tl_set:Nx \l_fontspec_feature_string_tl { \l_tmpa_tl = \l_tmpb_tl }
1253       \prg_return_true:
1254     }
1255   }
1256 }

```

`\fontspec_iv_str_to_num:Nn` This macro takes a four character string and converts it to the numerical representation required for XeTeX OpenType script/language/feature purposes. The output is stored in `\l_fontspec_strnum_int`.

The reason it's ugly is because the input can be of the form of any of these: 'abcd', 'abc', 'abc ', 'ab', 'ab ', etc. (It is assumed the first two chars are *always* not spaces.) So this macro reads in the string, delimited by a space; this input is padded with `\@empty`s and anything beyond four chars is snipped. The `\@empty`

s then are used to reconstruct the spaces in the string to number calculation.

The variant `\fontspec_v_str_to_num:n` is used when looking at features, which are passed around with prepended plus and minus signs (*e.g.*, `+liga`, `-dlig`); it simply strips off the first char of the input before calling the normal `\fontspec_iv_str_to_num:n`.

```

1257 \cs_set:Nn \fontspec_iv_str_to_num:Nn
1258 {
1259   \fontspec_iv_str_to_num:w #1 \q_nil #2 \c_empty_tl \c_empty_tl \q_nil
1260 }
1261 \cs_set:Npn \fontspec_iv_str_to_num:w #1 \q_nil #2#3#4#5#6 \q_nil
1262 {
1263   \int_set:Nn #1
1264   {
1265     '#2 * "1000000
1266     + '#3 * "10000
1267     + \ifx \c_empty_tl #4 32 \else '#4 \fi * "100
1268     + \ifx \c_empty_tl #5 32 \else '#5 \fi
1269   }
1270 }
1271 \cs_generate_variant:Nn \fontspec_iv_str_to_num:Nn {No}
1272 \cs_set:Nn \fontspec_v_str_to_num:Nn
1273 {
1274   \bool_if:nTF
1275   {
1276     \tl_if_head_eq_charcode_p:nN {#2} {+} ||
1277     \tl_if_head_eq_charcode_p:nN {#2} {-}
1278   }
1279   { \fontspec_iv_str_to_num:No #1 { \use_none:n #2 } }
1280   { \fontspec_iv_str_to_num:Nn #1 {#2} }
1281 }

```

`\fontspec_check_script:nTF` This macro takes an OpenType script tag and checks if it exists in the current font. The output boolean is `\@tempwatrue`. `\l_fontspec_strnum_int` is used to store the number corresponding to the script tag string.

```

1282 \prg_new_conditional:Nnn \fontspec_check_script:n {TF}
1283 (*xetexx)
1284 {
1285   \fontspec_iv_str_to_num:Nn \l_fontspec_strnum_int {#1}
1286   \int_set:Nn \l_tmpb_int { \XeTeXOTcountscrits \l_fontspec_font }
1287   \int_zero:N \l_tmpa_int
1288   \bool_set_false:N \l__fontspec_check_bool
1289   \bool_until_do:nn { \int_compare_p:nNn \l_tmpa_int = \l_tmpb_int }
1290   {
1291     \ifnum \XeTeXOTscripttag\l_fontspec_font \l_tmpa_int = \l_fontspec_strnum_int
1292       \bool_set_true:N \l__fontspec_check_bool
1293       \int_set:Nn \l_tmpa_int {\l_tmpb_int}
1294     \else
1295       \int_incr:N \l_tmpa_int
1296     \fi
1297   }
1298   \bool_if:NTF \l__fontspec_check_bool \prg_return_true: \prg_return_false:
1299 }

```

```

1300 </xetex>
1301 <*luatex>
1302 {
1303   \directlua{fontspec.check_ot_script("l_fontspec_font", "#1")}
1304   \bool_if:NTF \l__fontspec_check_bool \prg_return_true: \prg_return_false:
1305 }
1306 </luatex>

```

`\fontspec_check_lang:nTF` This macro takes an OpenType language tag and checks if it exists in the current font/script. The output boolean is `\@tempswattrue`. `\l_fontspec_strnum_int` is used to store the number corresponding to the language tag string. The script used is whatever's held in `\l_fontspec_script_int`. By default, that's the number corresponding to 'latn'.

```

1307 \prg_new_conditional:Nnn \fontspec_check_lang:n {TF}
1308 <*xetex>
1309 {
1310   \fontspec_iv_str_to_num:Nn \l_fontspec_strnum_int {#1}
1311   \int_set:Nn \l_tmpb_int
1312   { \XeTeXOTcountlanguages \l_fontspec_font \l_fontspec_script_int }
1313   \int_zero:N \l_tmpa_int
1314   \bool_set_false:N \l__fontspec_check_bool
1315   \bool_until_do:nn { \int_compare_p:nNn \l_tmpa_int = \l_tmpb_int }
1316   {
1317     \ifnum\XeTeXOTlanguage\l_fontspec_font\l_fontspec_script_int \l_tmpa_int =\l_fontspec_strnum
1318     \bool_set_true:N \l__fontspec_check_bool
1319     \int_set:Nn \l_tmpa_int {\l_tmpb_int}
1320   }
1321   \int_incr:N \l_tmpa_int
1322   \fi
1323 }
1324 \bool_if:NTF \l__fontspec_check_bool \prg_return_true: \prg_return_false:
1325 }
1326 </xetex>
1327 <*luatex>
1328 {
1329   \directlua
1330   {
1331     fontspec.check_ot_lang( "l_fontspec_font", "#1", "\l_fontspec_script_tl" )
1332   }
1333   \bool_if:NTF \l__fontspec_check_bool \prg_return_true: \prg_return_false:
1334 }
1335 </luatex>

```

`\fontspec_check_ot_feat:nTF` This macro takes an OpenType feature tag and checks if it exists in the current font/script/language. `\l_fontspec_strnum_int` is used to store the number corresponding to the feature tag string. The script used is whatever's held in `\l_fontspec_script_int`. By default, that's the number corresponding to 'latn'. The language used is `\l_fontspec_language_int`, by default 0, the 'default language'.

```

1336 \prg_new_conditional:Nnn \fontspec_check_ot_feat:n {TF,T}
1337 <*xetex>

```

```

1338 {
1339   \int_set:Nn \l_tmpb_int
1340   {
1341     \XeTeXOTcountfeatures \l_fontspec_font
1342                           \l_fontspec_script_int
1343                           \l_fontspec_language_int
1344   }
1345   \fontspec_v_str_to_num:Nn \l_fontspec_strnum_int {#1}
1346   \int_zero:N \l_tmpa_int
1347   \bool_set_false:N \l__fontspec_check_bool
1348   \bool_until_do:nn { \int_compare_p:nNn \l_tmpa_int = \l_tmpb_int }
1349   {
1350     \ifnum\XeTeXOTfeaturetag\l_fontspec_font\l_fontspec_script_int\l_fontspec_language_int
1351       \l_tmpa_int =\l_fontspec_strnum_int
1352       \bool_set_true:N \l__fontspec_check_bool
1353       \int_set:Nn \l_tmpa_int {\l_tmpb_int}
1354     \else
1355       \int_incr:N \l_tmpa_int
1356     \fi
1357   }
1358   \bool_if:NTF \l__fontspec_check_bool \prg_return_true: \prg_return_false:
1359 }
1360 </xetex>
1361 <*luatex>
1362 {
1363   \directlua
1364   {
1365     fontspec.check_ot_feat(
1366       "l_fontspec_font", "#1",
1367       "\l_fontspec_lang_tl", "\l_fontspec_script_tl"
1368     )
1369   }
1370   \bool_if:NTF \l__fontspec_check_bool \prg_return_true: \prg_return_false:
1371 }
1372 </luatex>

```

28 Font loading (keyval) definitions

This is the tedious section where we correlate all possible (eventually) font feature requests with their $\text{X}_{\text{E}}\text{T}_{\text{E}}\text{X}$ representations.

```

1373 \cs_new:Nn \@@_keys_define_code:nnn
1374 {
1375   \keys_define:nn {#1} { #2 .code:n = {#3} }
1376 }

```

For catching features that cannot be used in `\addfontfeatures`:

```

1377 \cs_new:Nn \@@_aff_error:n
1378 {
1379   \@@_keys_define_code:nnn {fontspec-addfontfeatures} {#1}
1380   { \@@_error:nx {not-in-addfontfeatures} {#1} }
1381 }

```

28.0.1 Pre-parsing naming information

These features are extracted from the font feature list before all others.

ExternalLocation For fonts that aren't installed in the system. If no argument is given, the font is located with `kpsewhich`; it's either in the current directory or the \TeX tree. Otherwise, the argument given defines the file path of the font.

```
1382 \bool_new:N \l_@@_external_bool
1383 \@@_keys_define_code:nnn {fontspec-preparse-external} {ExternalLocation}
1384 {
1385   \bool_set_true:N \l_@@_nobf_bool
1386   \bool_set_true:N \l_@@_noit_bool
1387   \bool_set_true:N \l_@@_external_bool
1388   \cs_set:Npn \@@_namewrap:n ##1 { [ #1 ##1 ] }
1389 <*\xetex>
1390   \keys_set:nn {fontspec-renderer} {Renderer=OpenType}
1391 </\xetex>
1392 }
1393 \aliasfontfeature{ExternalLocation}{Path}
```

Extension For fonts that aren't installed in the system. Specifies the font extension to use.

```
1394 \@@_keys_define_code:nnn {fontspec-preparse-external} {Extension}
1395 {
1396   \tl_set:Nn \l_@@_extension_tl {#1}
1397   \bool_if:NF \l_@@_external_bool
1398   {
1399     \keys_set:nn {fontspec-preparse-external} {ExternalLocation}
1400   }
1401 }
1402 \tl_clear:N \l_@@_extension_tl
```

28.0.2 Pre-parsed features

After the font name(s) have been sorted out, now need to extract any renderer/font configuration features that need to be processed before all other font features.

Renderer This feature must be processed before all others (the other font shape and features options are also pre-parsed for convenience) because the renderer determines the format of the features and even whether certain features are available.

```
1403 \keys_define:nn {fontspec-renderer}
1404 {
1405   Renderer .choices:nn =
1406     {AAT,ICU,OpenType,Graphite,Full,Basic}
1407   {
1408     \int_compare:nTF {\l_keys_choice_int <= 4} {
1409 <*\xetex>
```

```

1410     \tl_set:Nv \l_fontspec_renderer_tl
1411         { g_fontspec_renderer_tag_ \l_keys_choice_tl }
1412 \</xetexx>
1413 \<*/luatex>
1414     \@@_warning:nx {only-xetex-feature} {Renderer=AAT/OpenType/Graphite}
1415 \</luatex>
1416     }
1417     {
1418 \<*/xetexx>
1419     \@@_warning:nx {only-luatex-feature} {Renderer=Full/Basic}
1420 \</xetexx>
1421 \<*/luatex>
1422     \tl_set:Nv \l_fontspec_mode_tl
1423         { g_fontspec_mode_tag_ \l_keys_choice_tl }
1424 \</luatex>
1425     }
1426 }
1427 }
1428 \tl_set:cn {g_fontspec_renderer_tag_AAT} {/AAT}
1429 \tl_set:cn {g_fontspec_renderer_tag_ICU} {/OT}
1430 \tl_set:cn {g_fontspec_renderer_tag_OpenType} {/OT}
1431 \tl_set:cn {g_fontspec_renderer_tag_Graphite} {/GR}
1432 \tl_set:cn {g_fontspec_mode_tag_Full} {node}
1433 \tl_set:cn {g_fontspec_mode_tag_Basic} {base}

```

OpenType script/language See later for the resolutions from fontspec features to OpenType definitions.

```

1434 \@@_keys_define_code:nnn {fontspec-prepare} {Script}
1435 {
1436 \<xetexx>     \keys_set:nn {fontspec-renderer} {Renderer=OpenType}
1437     \tl_set:Nn \l_@@_script_name_tl {#1}
1438 }

```

Exactly the same:

```

1439 \@@_keys_define_code:nnn {fontspec-prepare} {Language}
1440 {
1441 \<xetexx>     \keys_set:nn {fontspec-renderer} {Renderer=OpenType}
1442     \tl_set:Nn \l_@@_lang_name_tl {#1}
1443 }

```

28.0.3 Bold/italic choosing options

The Bold, Italic, and BoldItalic features are for defining explicitly the bold and italic fonts used in a font family.

Bold (NFSS) Series By default, fontspec uses the default bold series, `\bfdefault`. We want to be able to make this extensible.

```

1444 \seq_new:N \g_@@_bf_series_seq
1445 \@@_keys_define_code:nnn {fontspec-prepare-external} {BoldSeries}
1446 {

```

```

1447 \tl_gset:Nx \g_@@_curr_series_tl { #1 }
1448 \seq_gput_right:Nx \g_@@_bf_series_seq { #1 }
1449 }

```

Fonts Upright:

```

1450 \@@_keys_define_code:nnn {fontspec-preparse-external} {UprightFont}
1451 {
1452 \fontspec_complete_fontname:Nn \l_fontspec_fontname_up_tl {#1}
1453 }
1454 \@@_keys_define_code:nnn {fontspec-preparse-external} {FontName}
1455 {
1456 \fontspec_complete_fontname:Nn \l_fontspec_fontname_up_tl {#1}
1457 }

```

Bold:

```

1458 \cs_generate_variant:Nn \tl_if_eq:nnT {ox}
1459 \cs_generate_variant:Nn \prop_put:Nnn {NxV}
1460 \@@_keys_define_code:nnn {fontspec-preparse-external} {BoldFont}
1461 {
1462 \tl_if_empty:nTF {#1}
1463 {
1464 \bool_set_true:N \l_@@_nobf_bool
1465 }
1466 {
1467 \bool_set_false:N \l_@@_nobf_bool
1468 \fontspec_complete_fontname:Nn \l_@@_curr_bfname_tl {#1}
1469
1470 \seq_if_empty:NT \g_@@_bf_series_seq
1471 {
1472 \tl_gset:Nx \g_@@_curr_series_tl {\bfdefault}
1473 \seq_put_right:Nx \g_@@_bf_series_seq {\bfdefault}
1474 }
1475 \tl_if_eq:oxT \g_@@_curr_series_tl {\bfdefault}
1476 { \tl_set_eq:NN \l_fontspec_fontname_bf_tl \l_@@_curr_bfname_tl }
1477
1478 <debug>\typeout{Setting~bold~font~"\l_@@_curr_bfname_tl"~with~series~"\g_@@_curr_series_tl"}
1479
1480 \prop_put:NxV \l_@@_nfss_prop
1481 {BoldFont-\g_@@_curr_series_tl} \l_@@_curr_bfname_tl
1482
1483 }
1484 }
1485 \prop_new:N \l_@@_nfss_prop

```

Same for italic:

```

1486 \@@_keys_define_code:nnn {fontspec-preparse-external} {ItalicFont}
1487 {
1488 \tl_if_empty:nTF {#1}
1489 {
1490 \bool_set_true:N \l_@@_noit_bool
1491 }
1492 {

```

```

1493 \bool_set_false:N \l_@@_noit_bool
1494 \fontspec_complete_fontname:Nn \l_fontspec_fontname_it_tl {#1}
1495 }
1496 }

```

Simpler for bold+italic & slanted:

```

1497 \@@_keys_define_code:nnn {fontspec-prepare-external} {BoldItalicFont}
1498 {
1499 \fontspec_complete_fontname:Nn \l_fontspec_fontname_bfit_tl {#1}
1500 }
1501 \@@_keys_define_code:nnn {fontspec-prepare-external} {SlantedFont}
1502 {
1503 \fontspec_complete_fontname:Nn \l_fontspec_fontname_sl_tl {#1}
1504 }
1505 \@@_keys_define_code:nnn {fontspec-prepare-external} {BoldSlantedFont}
1506 {
1507 \fontspec_complete_fontname:Nn \l_fontspec_fontname_bfsl_tl {#1}
1508 }

```

Small caps isn't pre-parsed because it can vary with others above:

```

1509 \@@_keys_define_code:nnn {fontspec} {SmallCapsFont}
1510 {
1511 \tl_if_empty:nTF {#1}
1512 {
1513 \bool_set_true:N \l_@@_nosc_bool
1514 }
1515 {
1516 \bool_set_false:N \l_@@_nosc_bool
1517 \fontspec_complete_fontname:Nn \l_fontspec_fontname_sc_tl {#1}
1518 }
1519 }

```

`\fontspec_complete_fontname:Nn` This macro defines #1 as the input with any * tokens of its input replaced by the font name. This lets us define supplementary fonts in full ("Baskerville Semibold") or in abbreviation ("* Semibold").

```

1520 \cs_set:Nn \fontspec_complete_fontname:Nn
1521 {
1522 \tl_set:Nx #1 {#2}
1523 \tl_replace_all:Nnx #1 {*} {\l_@@_basename_tl}
1524 \luatex \tl_remove_all:Nn #1 {~}
1525 }
1526 \cs_generate_variant:Nn \tl_replace_all:Nnn {Nnx}

```

Features

```

1527 \@@_keys_define_code:nnn {fontspec-prepare} {UprightFeatures}
1528 {
1529 \clist_set:Nn \l_@@_fontfeat_up_clist {#1}
1530 }
1531 \@@_keys_define_code:nnn {fontspec-prepare} {BoldFeatures}
1532 {
1533 \clist_set:Nn \l_@@_fontfeat_bf_clist {#1}
1534 }

```

```

1535% \prop_put:NxV \l_@@_nfss_prop
1536%   {BoldFont-\g_@@_curr_series_tl} \l_@@_curr_bfname_tl
1537 }
1538 \@@_keys_define_code:nnn {fontspec-preparse} {ItalicFeatures}
1539 {
1540   \clist_set:Nn \l_@@_fontfeat_it_clist {#1}
1541 }
1542 \@@_keys_define_code:nnn {fontspec-preparse} {BoldItalicFeatures}
1543 {
1544   \clist_set:Nn \l_@@_fontfeat_bfit_clist {#1}
1545 }
1546 \@@_keys_define_code:nnn {fontspec-preparse} {SlantedFeatures}
1547 {
1548   \clist_set:Nn \l_@@_fontfeat_sl_clist {#1}
1549 }
1550 \@@_keys_define_code:nnn {fontspec-preparse} {BoldSlantedFeatures}
1551 {
1552   \clist_set:Nn \l_@@_fontfeat_bfsl_clist {#1}
1553 }

```

Note that small caps features can vary by shape, so these in fact *aren't* pre-parsed.

```

1554 \@@_keys_define_code:nnn {fontspec} {SmallCapsFeatures}
1555 {
1556   \bool_if:NF \l_@@_firsttime_bool
1557   {
1558     \clist_set:Nn \l_@@_fontfeat_sc_clist {#1}
1559   }
1560 }

```

paragraphFeatures varying by size

```

1561 \@@_keys_define_code:nnn {fontspec-preparse} {SizeFeatures}
1562 {
1563   \clist_set:Nn \l_@@_sizefeat_clist {#1}
1564   \clist_put_right:Nn \l_@@_fontfeat_up_clist { SizeFeatures = {#1} }
1565 }
1566 \@@_keys_define_code:nnn {fontspec-preparse-nested} {SizeFeatures}
1567 {
1568   \clist_set:Nn \l_@@_sizefeat_clist {#1}
1569   \tl_if_empty:NT \l_@@_this_font_tl
1570   { \tl_set:Nn \l_@@_this_font_tl { -- } } % needs to be non-empty as a flag
1571 }
1572 \@@_keys_define_code:nnn {fontspec-preparse-nested} {Font}
1573 {
1574   \tl_set:Nn \l_@@_this_font_tl {#1}
1575 }
1576 \@@_keys_define_code:nnn {fontspec} {SizeFeatures}
1577 {
1578   % dummy
1579 }
1580 \@@_keys_define_code:nnn {fontspec} {Font}
1581 {
1582   % dummy
1583 }

```

```

1584 \@@_keys_define_code:nnn {fontspec-sizing} {Size}
1585 {
1586   \tl_set:Nn \l_@@_size_tl {#1}
1587 }
1588 \@@_keys_define_code:nnn {fontspec-sizing} {Font}
1589 {
1590   \fontspec_complete_fontname:Nn \l_@@_sizedfont_tl {#1}
1591 }

```

28.0.4 Font-independent features

These features can be applied to any font.

NFSS encoding For the very brave.

```

1592 \@@_keys_define_code:nnn {fontspec-prepare} {NFSSEncoding}
1593 {
1594   \tl_gset:Nx \l_@@_nfss_enc_tl { #1 }
1595 }

```

NFSS family Interactions with other packages will sometimes require setting the NFSS family explicitly. (By default fontspec auto-generates one based on the font name.)

```

1596 \@@_keys_define_code:nnn {fontspec-prepare} {NFSSFamily}
1597 {
1598   \tl_set:Nx \l_@@_nfss_fam_tl { #1 }
1599   \cs_undefine:c {g_@@_UID_\l_@@_fontid_tl}
1600   \tl_if_exist:NT \l_fontspec_family_tl
1601   { \cs_undefine:c {g_@@_ \l_fontspec_family_tl _prop} }
1602 }

```

NFSS series/shape This option looks similar in name but has a very different function.

```

1603 \prop_new:N \l_@@_nfssfont_prop
1604 \@@_keys_define_code:nnn {fontspec} {FontFace}
1605 {
1606   \tl_set:No \l_@@_arg_tl { \use_iii:nnn #1 }
1607   \tl_set_eq:NN \l_@@_this_feat_tl \l_@@_arg_tl
1608   \tl_clear:N \l_@@_this_font_tl
1609   \int_compare:nT { \clist_count:N \l_@@_arg_tl = 1 }
1610   {
1611     \*debug
1612     \typeout{FontFace~ parsing:~ one~ clist~ item}
1613     \*debug
1614     \tl_if_in:NnF \l_@@_arg_tl {=}
1615     {
1616       \*debug
1617       \typeout{FontFace~ parsing:~ no~ equals~ =>~ font~ name~ only}
1618       \*debug
1619       \tl_set_eq:NN \l_@@_this_font_tl \l_@@_arg_tl

```

```

1620     \tl_clear:N \l_@@_this_feat_tl
1621   }
1622 }
1623
1624 \@@_add_nfssfont:nnnn
1625   {\use_i:nnn #1}{\use_ii:nnn #1}{\l_@@_this_font_tl}{\l_@@_this_feat_tl}
1626 }

```

```

\@@_add_nfssfont:nnnn #1 : series
                      #2 : shape
                      #3 : fontname
                      #4 : fontspec features

```

```

1627 \cs_new:Nn \@@_add_nfssfont:nnnn
1628 {
1629   \tl_set:Nx \l_@@_this_font_tl {#3}
1630
1631   \tl_if_empty:xTF {#4}
1632     { \clist_set:Nn \l_@@_sizefeat_clist {Size={-}} }
1633     { \keys_set_known:noN {fontspec-preparse-nested} {#4} \l_@@_tmp_tl }
1634
1635   \tl_if_empty:NF \l_@@_this_font_tl
1636     {
1637       \prop_put:Nxx \l_@@_nfssfont_prop {#1/#2}
1638       { {#1}{#2}{\l_@@_this_font_tl}{#4}{\l_@@_sizefeat_clist} }
1639     }
1640 }

```

Scale If the input isn't one of the pre-defined string options, then it's gotta be numerical. `\fontspec_calc_scale:n` does all the work in the auto-scaling cases.

```

1641 \@@_keys_define_code:nnn {fontspec} {Scale}
1642 {
1643   \str_case:nnF {#1}
1644     {
1645       {MatchLowercase} { \@@_calc_scale:n {5} }
1646       {MatchUppercase} { \@@_calc_scale:n {8} }
1647     }
1648     { \tl_set:Nx \l_@@_scale_tl {#1} }
1649     \tl_set:Nx \l_@@_scale_tl { s*[\l_@@_scale_tl] }
1650 }

```

`\@@_calc_scale:n` This macro calculates the amount of scaling between the default roman font and the (default shape of) the font being selected such that the font dimension that is input is equal for both. The only font dimensions that justify this are 5 (lowercase height) and 8 (uppercase height in X_YTeX).

This script is executed for every extra shape, which seems wasteful, but allows alternate italic shapes from a separate font, say, to be loaded and to be auto-scaled correctly. Even if this would be ugly.

```

1651 \cs_new:Nn \@@_calc_scale:n
1652 {
1653   \group_begin:

```

```

1654 \rmfamily
1655 \@@_set_font_dimen:NnN \l_@@_tmpa_dim {#1} \font
1656 \@@_set_font_dimen:NnN \l_@@_tmpb_dim {#1} \l_fontspec_font
1657 \tl_gset:Nx \l_@@_scale_tl
1658 {
1659   \fp_eval:n { \dim_to_fp:n {\l_@@_tmpa_dim} /
1660             \dim_to_fp:n {\l_@@_tmpb_dim} }
1661 }
1662 \@@_info:n {set-scale}
1663 \group_end:
1664 }

```

`\@@_set_font_dimen:NnN` This function sets the dimension #1 (for font #3) to ‘fontdimen’ #2 for either font dimension 5 (x-height) or 8 (cap-height). If, for some reason, these return an incorrect ‘zero’ value (as `\fontdimen8` might for a .tfm font), then we cheat and measure the height of a glyph. We assume in this case that the font contains either an ‘X’ or an ‘x’.

```

1665 \cs_new:Nn \@@_set_font_dimen:NnN
1666 {
1667   \dim_set:Nn #1 { \fontdimen #2 #3 }
1668   \dim_compare:nNnT #1 = {0pt}
1669   {
1670     \settoheight #1
1671     {
1672       \str_if_eq:nnTF {#3} {\font} \rmfamily #3
1673       \int_case:nnn #2
1674       {
1675         {5} {x} % x-height
1676         {8} {X} % cap-height
1677       } {?} % "else" clause; never reached.
1678     }
1679   }
1680 }

```

Inter-word space These options set the relevant `\fontdimens` for the font being loaded.

```

1681 \@@_keys_define_code:nnn {fontspec} {WordSpace}
1682 {
1683   \bool_if:NF \l_@@_firsttime_bool
1684   { \_fontspec_parse_wordspace:w #1,,,\q_stop }
1685 }
1686 \@@_aff_error:n {WordSpace}

```

`_fontspec_parse_wordspace:w` This macro determines if the input to `WordSpace` is of the form `{X}` or `{X,Y,Z}` and executes the font scaling. If the former input, it executes `{X,X,X}`.

```

1687 \cs_set:Npn \_fontspec_parse_wordspace:w #1,#2,#3,#4 \q_stop
1688 {
1689   \tl_if_empty:nTF {#4}
1690   {
1691     \tl_set:Nn \l_@@_wordspace_adjust_tl

```

```

1692 {
1693   \fontdimen 2 \font = #1 \fontdimen 2 \font
1694   \fontdimen 3 \font = #1 \fontdimen 3 \font
1695   \fontdimen 4 \font = #1 \fontdimen 4 \font
1696 }
1697 }
1698 {
1699   \tl_set:Nn \l_@@_wordspace_adjust_tl
1700   {
1701     \fontdimen 2 \font = #1 \fontdimen 2 \font
1702     \fontdimen 3 \font = #2 \fontdimen 3 \font
1703     \fontdimen 4 \font = #3 \fontdimen 4 \font
1704   }
1705 }
1706 }

```

Punctuation space Scaling factor for the nominal \fontdimen#7.

```

1707 \@@_keys_define_code:nnn {fontspec} {PunctuationSpace}
1708 {
1709   \str_case:x:nnF {#1}
1710   {
1711     {WordSpace}
1712     {
1713       \tl_set:Nn \l_@@_punctspace_adjust_tl
1714       { \fontdimen 7 \font = 0 \fontdimen 2 \font }
1715     }
1716     {TwiceWordSpace}
1717     {
1718       \tl_set:Nn \l_@@_punctspace_adjust_tl
1719       { \fontdimen 7 \font = 1 \fontdimen 2 \font }
1720     }
1721   }
1722   {
1723     \tl_set:Nn \l_@@_punctspace_adjust_tl
1724     { \fontdimen 7 \font = #1 \fontdimen 7 \font }
1725   }
1726 }
1727 \@@_aff_error:n {PunctuationSpace}

```

Secret hook into the font-adjustment code

```

1728 \@@_keys_define_code:nnn {fontspec} {FontAdjustment}
1729 {
1730   \tl_put_right:Nx \l_@@_postadjust_tl {#1}
1731 }

```

Letterspacing

```

1732 \@@_keys_define_code:nnn {fontspec} {LetterSpace}
1733 {
1734   \@@_update_featstr:n {letterspace=#1}
1735 }

```

Hyphenation character This feature takes one of three arguments: ‘None’, *<glyph>*, or *<slot>*. If the input isn’t the first, and it’s one character, then it’s the second; otherwise, it’s the third.

```

1736 \@@_keys_define_code:nnn {fontspec} {HyphenChar}
1737 {
1738   \bool_if:NT \l_@@_addfontfeatures_bool
1739   { \@@_error:nx {not-in-addfontfeatures} {HyphenChar} }
1740
1741   \str_if_eq:nnTF {#1} {None}
1742   {
1743     \tl_put_right:Nn \l_@@_postadjust_tl
1744     { \hyphenchar \font = \c_minus_one }
1745   }
1746   {
1747     \tl_if_single:nTF {#1}
1748     { \tl_set:Nn \l_fontspeg_hyphenchar_tl {'#1} }
1749     { \tl_set:Nn \l_fontspeg_hyphenchar_tl { #1} }
1750     \font_glyph_if_exist:NnTF \l_fontspeg_font {\l_fontspeg_hyphenchar_tl}
1751     {
1752       \tl_put_right:Nn \l_@@_postadjust_tl
1753 (*xetexx)
1754       { \hyphenchar \font = \l_fontspeg_hyphenchar_tl \scan_stop: }
1755 (/xetexx)
1756 (*luatex)
1757       {
1758         \hyphenchar \font = \c_zero
1759         \int_set:Nn \luatex_prehyphenchar:D { \l_fontspeg_hyphenchar_tl }
1760       }
1761 (/luatex)
1762     }
1763     { \@@_error:nx {no-glyph}{#1} }
1764   }
1765 }
1766 \@@_aff_error:n {HyphenChar}

```

Color Hooks into `pkgxcolor`, which names its colours `\color@<name>`.

```

1767 \@@_keys_define_code:nnn {fontspec} {Color}
1768 {
1769   \cs_if_exist:cTF { \token_to_str:N \color@ #1 }
1770   {
1771     \convertcolorspec{named}{#1}{HTML}\l_@@_hexcol_tl
1772   }
1773   {
1774     \int_compare:nTF { \tl_count:n {#1} == 6 }
1775     { \tl_set:Nn \l_@@_hexcol_tl {#1} }
1776     {
1777       \int_compare:nTF { \tl_count:n {#1} == 8 }
1778       { \fontspec_parse_colour:viii #1 }
1779       {
1780         \bool_if:NF \l_@@_firsttime_bool
1781         { \@@_warning:nx {bad-colour} {#1} }

```

```

1782     }
1783   }
1784 }
1785 }
1786 \cs_set:Npn \fontspec_parse_colour:viii #1#2#3#4#5#6#7#8
1787 {
1788   \tl_set:Nn \l_@@_hexcol_tl {#1#2#3#4#5#6}
1789   \tl_if_eq:NNF \l_@@_opacity_tl \g_@@_opacity_tl
1790   {
1791     \bool_if:NF \l_@@_firsttime_bool
1792     { \@@_warning:nx {opa-twice-col} {#7#8} }
1793   }
1794   \tl_set:Nn \l_@@_opacity_tl {#7#8}
1795 }
1796 \aliasfontfeature{Color}{Colour}

1797 \int_new:N \l_@@_tmp_int
1798 \@@_keys_define_code:nnn {fontspec} {Opacity}
1799 {
1800   \int_set:Nn \l_@@_tmp_int {255}
1801   \@@_int_mult_truncate:Nn \l_@@_tmp_int { #1 }
1802   \tl_if_eq:NNF \l_@@_opacity_tl \g_@@_opacity_tl
1803   {
1804     \bool_if:NF \l_@@_firsttime_bool
1805     { \@@_warning:nx {opa-twice} {#1} }
1806   }
1807   \tl_set:Nx \l_@@_opacity_tl
1808   {
1809     \int_compare:nT { \l_@@_tmp_int <= "F } {0} % zero pad
1810     \int_to_hex:n { \l_@@_tmp_int }
1811   }
1812 }

```

Mapping

```

1813 \@@_keys_define_code:nnn {fontspec} {Mapping}
1814 < *xetex >
1815 {
1816   \@@_update_featstr:n { mapping = #1 }
1817 }
1818 < /xetex >
1819 < *luatex >
1820 {
1821   \str_if_eq:nnTF {#1} {tex-text}
1822   {
1823     \@@_warning:n {no-mapping-ligtext}
1824     \msg_redirect_name:nnn {fontspec} {no-mapping-ligtext} {none}
1825     \keys_set:nn {fontspec} { Ligatures=TeX }
1826   }
1827   { \@@_warning:n {no-mapping} }
1828 }
1829 < /luatex >

```

FeatureFile

```
1830 \@@_keys_define_code:nnn {fontspec} {FeatureFile}
1831 {
1832   \@@_update_featstr:n { featurefile = #1 }
1833 }
```

28.0.5 Continuous font axes

```
1834 \@@_keys_define_code:nnn {fontspec} {Weight}
1835 {
1836   \@@_update_featstr:n{weight=#1}
1837 }
1838 \@@_keys_define_code:nnn {fontspec} {Width}
1839 {
1840   \@@_update_featstr:n{width=#1}
1841 }
1842 \@@_keys_define_code:nnn {fontspec} {OpticalSize}
1843 ⟨*xetex⟩
1844 {
1845   \bool_if:NTF \l_@@_ot_bool
1846   {
1847     \tl_set:Nn \l_@@_optical_size_tl {/ S = #1}
1848   }
1849   {
1850     \bool_if:NT \l_@@_mm_bool
1851     {
1852       \@@_update_featstr:n { optical size = #1 }
1853     }
1854   }
1855   \bool_if:nT { !\l_@@_ot_bool && !\l_@@_mm_bool }
1856   {
1857     \bool_if:NT \l_@@_firsttime_bool
1858     { \@@_warning:n {no-opticals} }
1859   }
1860 }
1861 ⟨/xetex⟩
1862 ⟨*luatex⟩
1863 {
1864   \tl_set:Nn \l_@@_optical_size_tl {/ S = #1}
1865 }
1866 ⟨/luatex⟩
```

28.0.6 Font transformations

These are to be specified to apply directly to a font shape:

```
1867 \keys_define:nn {fontspec}
1868 {
1869   FakeSlant .code:n =
1870   {
1871     \@@_update_featstr:n{slant=#1}
1872   },
1873   FakeSlant .default:n = {0.2}
```

```

1874 }
1875 \keys_define:nn {fontspec}
1876 {
1877   FakeStretch .code:n =
1878     {
1879       \@@_update_featstr:n{extend=#1}
1880     },
1881   FakeStretch .default:n = {1.2}
1882 }
1883 <*/xetex>
1884 \keys_define:nn {fontspec}
1885 {
1886   FakeBold .code:n =
1887     {
1888       \@@_update_featstr:n {embolden=#1}
1889     },
1890   FakeBold .default:n = {1.5}
1891 }
1892 </xetex>
1893 <*/luatex>
1894 \keys_define:nn {fontspec}
1895 {
1896   FakeBold .code:n = { \@@_warning:n {fakebold-only-xetex} }
1897 }
1898 </luatex>

```

These are to be given to a shape that has no real bold/italic to signal that fontspec should automatically create ‘fake’ shapes.

The behaviour is currently that only if both `AutoFakeSlant` and `AutoFakeBold` are specified, the bold italic is also faked.

These features presently *override* real shapes found in the font; in the future I’d like these features to be ignored in this case, instead. (This is just a bit harder to program in the current design of fontspec.)

```

1899 \keys_define:nn {fontspec}
1900 {
1901   AutoFakeSlant .code:n =
1902     {
1903       \bool_if:NT \l_@@_firsttime_bool
1904       {
1905         \tl_set:Nn \l_fontspec_fake_slant_tl {#1}
1906         \clist_put_right:Nn \l_@@_fontfeat_it_clist {FakeSlant=#1}
1907         \tl_set_eq:NN \l_fontspec_fontname_it_tl \l_fontspec_fontname_tl
1908         \bool_set_false:N \l_@@_noit_bool
1909       }
1910       \tl_if_empty:NF \l_fontspec_fake_embolden_tl
1911       {
1912         \clist_put_right:Nx \l_@@_fontfeat_bfit_clist
1913           {FakeBold=\l_fontspec_fake_embolden_tl}
1914         \clist_put_right:Nx \l_@@_fontfeat_bfit_clist {FakeSlant=#1}
1915         \tl_set_eq:NN \l_fontspec_fontname_bfit_tl \l_fontspec_fontname_tl
1916       }

```

```

1917     }
1918   },
1919   AutoFakeSlant .default:n = {0.2}
1920 }

```

Same but reversed:

```

1921 \keys_define:nn {fontspec}
1922 {
1923   AutoFakeBold .code:n =
1924   {
1925     \bool_if:NT \l_@@_firsttime_bool
1926     {
1927       \tl_set:Nn \l_fontspec_fake_embolden_tl {#1}
1928       \clist_put_right:Nn \l_@@_fontfeat_bf_clist {FakeBold=#1}
1929       \tl_set_eq:NN \l_fontspec_fontname_bf_tl \l_fontspec_fontname_tl
1930       \bool_set_false:N \l_@@_nobf_bool
1931     }
1932     \tl_if_empty:NF \l_fontspec_fake_slant_tl
1933     {
1934       \clist_put_right:Nx \l_@@_fontfeat_bfit_clist
1935         {FakeSlant=\l_fontspec_fake_slant_tl}
1936       \clist_put_right:Nx \l_@@_fontfeat_bfit_clist {FakeBold=#1}
1937       \tl_set_eq:NN \l_fontspec_fontname_bfit_tl \l_fontspec_fontname_tl
1938     }
1939   }
1940 },
1941   AutoFakeBold .default:n = {1.5}
1942 }

```

28.0.7 Ligatures

The call to the nested keyval family must be wrapped in braces to hide the parent list (this later requires the use of global definitions (`\xdef`) in [...]). Both `AAT` and `OpenType` names are offered to chose Rare/Discretionary ligatures.

```

1943 \@@_define_font_feature:n{Ligatures}
1944 \@@_define_feature_option:nnnnn{Ligatures}{Required}      {1}{0}{+rlig}
1945 \@@_define_feature_option:nnnnn{Ligatures}{NoRequired}   {1}{1}{-rlig}
1946 \@@_define_feature_option:nnnnn{Ligatures}{Common}       {1}{2}{+liga}
1947 \@@_define_feature_option:nnnnn{Ligatures}{NoCommon}    {1}{3}{-liga}
1948 \@@_define_feature_option:nnnnn{Ligatures}{Rare}        {1}{4}{+dlig}
1949 \@@_define_feature_option:nnnnn{Ligatures}{NoRare}      {1}{5}{-dlig}
1950 \@@_define_feature_option:nnnnn{Ligatures}{Discretionary}{1}{4}{+dlig}
1951 \@@_define_feature_option:nnnnn{Ligatures}{NoDiscretionary}{1}{5}{-dlig}
1952 \@@_define_feature_option:nnnnn{Ligatures}{Contextual}   {}{} {+clig}
1953 \@@_define_feature_option:nnnnn{Ligatures}{NoContextual} {}{} {-clig}
1954 \@@_define_feature_option:nnnnn{Ligatures}{Historic}     {}{} {+hlig}
1955 \@@_define_feature_option:nnnnn{Ligatures}{NoHistoric}   {}{} {-hlig}
1956 \@@_define_feature_option:nnnnn{Ligatures}{Logos}        {1}{6} {}
1957 \@@_define_feature_option:nnnnn{Ligatures}{NoLogos}     {1}{7} {}
1958 \@@_define_feature_option:nnnnn{Ligatures}{Rebus}       {1}{8} {}
1959 \@@_define_feature_option:nnnnn{Ligatures}{NoRebus}     {1}{9} {}
1960 \@@_define_feature_option:nnnnn{Ligatures}{Diphthong}    {1}{10} {}

```

```

1961 \@@_define_feature_option:nnnnn{Ligatures}{NoDiphthong}    {1}{11}{}
1962 \@@_define_feature_option:nnnnn{Ligatures}{Squared}      {1}{12}{}
1963 \@@_define_feature_option:nnnnn{Ligatures}{NoSquared}    {1}{13}{}
1964 \@@_define_feature_option:nnnnn{Ligatures}{AbbrevSquared} {1}{14}{}
1965 \@@_define_feature_option:nnnnn{Ligatures}{NoAbbrevSquared}{1}{15}{}
1966 \@@_define_feature_option:nnnnn{Ligatures}{Icelandic}    {1}{32}{}
1967 \@@_define_feature_option:nnnnn{Ligatures}{NoIcelandic}  {1}{33}{}

```

Emulate CM extra ligatures.

```

1968 \keys_define:nn {fontspec}
1969 {
1970   Ligatures / TeX .code:n =
1971   {
1972     \*xetexx
1973     \@@_update_featstr:n { mapping = tex-text }
1974   } /xetexx
1975   \*luatex
1976   \@@_update_featstr:n { +tlig }
1977 } /luatex
1978 }
1979 }

```

28.0.8 Letters

```

1980 \@@_define_font_feature:n{Letters}
1981 \@@_define_feature_option:nnnnn{Letters}{Normal}          {3}{0}{}
1982 \@@_define_feature_option:nnnnn{Letters}{Uppercase}      {3}{1}{+case}
1983 \@@_define_feature_option:nnnnn{Letters}{Lowercase}      {3}{2}{}
1984 \@@_define_feature_option:nnnnn{Letters}{SmallCaps}      {3}{3}{+smcp}
1985 \@@_define_feature_option:nnnnn{Letters}{PetiteCaps}     {} {} {+pcap}
1986 \@@_define_feature_option:nnnnn{Letters}{UppercaseSmallCaps} {} {} {+c2sc}
1987 \@@_define_feature_option:nnnnn{Letters}{UppercasePetiteCaps} {} {} {+c2pc}
1988 \@@_define_feature_option:nnnnn{Letters}{InitialCaps}    {3}{4}{}
1989 \@@_define_feature_option:nnnnn{Letters}{Unicase}        {} {} {+unic}
1990 \@@_define_feature_option:nnnnn{Letters}{Random}         {} {} {+rand}

```

28.0.9 Numbers

These were originally separated into `NumberCase` and `NumberSpacing` following AAT, but it makes more sense to combine them.

Both naming conventions are offered to select the number case.

```

1991 \@@_define_font_feature:n{Numbers}
1992 \@@_define_feature_option:nnnnn{Numbers}{Monospaced}     {6} {0}{+tnum}
1993 \@@_define_feature_option:nnnnn{Numbers}{Proportional}   {6} {1}{+pnum}
1994 \@@_define_feature_option:nnnnn{Numbers}{Lowercase}      {21}{0}{+onum}
1995 \@@_define_feature_option:nnnnn{Numbers}{OldStyle}       {21}{0}{+onum}
1996 \@@_define_feature_option:nnnnn{Numbers}{Uppercase}      {21}{1}{+lnum}
1997 \@@_define_feature_option:nnnnn{Numbers}{Lining}        {21}{1}{+lnum}
1998 \@@_define_feature_option:nnnnn{Numbers}{SlashedZero}    {14}{5}{+zero}
1999 \@@_define_feature_option:nnnnn{Numbers}{NoSlashedZero}  {14}{4}{-zero}

```

`luaotload` provides a custom `anum` feature for replacing Latin (AKA Arabic)

numbers with Arabic (AKA Indic-Arabic). The same feature maps to Farsi (Persian) numbers if font language is Farsi.

```
2000 \luatex_if_engine:T
2001 {
2002   \@@_define_feature_option:nnnnn{Numbers}{Arabic}{+anum}
2003 }
```

28.0.10 Contextuals

```
2004 \@@_define_font_feature:n {Contextuals}
2005 \@@_define_feature_option:nnnnn{Contextuals}{Swash}      {} {} {+csw}
2006 \@@_define_feature_option:nnnnn{Contextuals}{NoSwash}   {} {} {-csw}
2007 \@@_define_feature_option:nnnnn{Contextuals}{Alternate}  {} {} {+calt}
2008 \@@_define_feature_option:nnnnn{Contextuals}{NoAlternate} {} {} {-calt}
2009 \@@_define_feature_option:nnnnn{Contextuals}{WordInitial} {} {} {+init}
2010 \@@_define_feature_option:nnnnn{Contextuals}{NoWordInitial} {} {} {-init}
2011 \@@_define_feature_option:nnnnn{Contextuals}{WordFinal}  {} {} {+fina}
2012 \@@_define_feature_option:nnnnn{Contextuals}{NoWordFinal} {} {} {-fina}
2013 \@@_define_feature_option:nnnnn{Contextuals}{LineInitial} {} {} {+linit}
2014 \@@_define_feature_option:nnnnn{Contextuals}{NoLineInitial} {} {} {-linit}
2015 \@@_define_feature_option:nnnnn{Contextuals}{LineFinal}  {} {} {+falt}
2016 \@@_define_feature_option:nnnnn{Contextuals}{NoLineFinal} {} {} {-falt}
2017 \@@_define_feature_option:nnnnn{Contextuals}{Inner}      {} {} {+medi}
2018 \@@_define_feature_option:nnnnn{Contextuals}{NoInner}    {} {} {-medi}
```

28.0.11 Diacritics

```
2019 \@@_define_font_feature:n{Diacritics}
2020 \@@_define_feature_option:nnnnn{Diacritics}{Show}      {} {} {+show}
2021 \@@_define_feature_option:nnnnn{Diacritics}{Hide}      {} {} {-hide}
2022 \@@_define_feature_option:nnnnn{Diacritics}{Decompose} {} {} {+decomp}
2023 \@@_define_feature_option:nnnnn{Diacritics}{MarkToBase} {} {} {+mark}
2024 \@@_define_feature_option:nnnnn{Diacritics}{NoMarkToBase} {} {} {-mark}
2025 \@@_define_feature_option:nnnnn{Diacritics}{MarkToMark} {} {} {+mkmk}
2026 \@@_define_feature_option:nnnnn{Diacritics}{NoMarkToMark} {} {} {-mkmk}
2027 \@@_define_feature_option:nnnnn{Diacritics}{AboveBase}  {} {} {+abvm}
2028 \@@_define_feature_option:nnnnn{Diacritics}{NoAboveBase} {} {} {-abvm}
2029 \@@_define_feature_option:nnnnn{Diacritics}{BelowBase}  {} {} {+blwm}
2030 \@@_define_feature_option:nnnnn{Diacritics}{NoBelowBase} {} {} {-blwm}
```

28.0.12 Kerning

```
2031 \@@_define_font_feature:n{Kerning}
2032 \@@_define_feature_option:nnnnn{Kerning}{Uppercase} {} {} {+csp}
2033 \@@_define_feature_option:nnnnn{Kerning}{On}      {} {} {+kern}
2034 \@@_define_feature_option:nnnnn{Kerning}{Off}     {} {} {-kern}
2035 %\@@_define_feature_option:nnnnn{Kerning}{Vertical} {} {} {+vkrn}
2036 %\@@_define_feature_option:nnnnn{Kerning}
2037 %   {VerticalAlternateProportional} {} {} {+vpal}
2038 %\@@_define_feature_option:nnnnn{Kerning}{VerticalAlternateHalfWidth} {} {} {+vhal}
```

28.0.13 Vertical position

```
2039 \@@_define_font_feature:n{VerticalPosition}
```

```

2040 \@@_define_feature_option:nnnnn{VerticalPosition}{Normal} {10}{0}{}
2041 \@@_define_feature_option:nnnnn{VerticalPosition}{Superior} {10}{1}{+sup}
2042 \@@_define_feature_option:nnnnn{VerticalPosition}{Inferior} {10}{2}{+sub}
2043 \@@_define_feature_option:nnnnn{VerticalPosition}{Ordinal} {10}{3}{+ordn}
2044 \@@_define_feature_option:nnnnn{VerticalPosition}{Numerator} {} {} {+numr}
2045 \@@_define_feature_option:nnnnn{VerticalPosition}{Denominator}{} {} {+dnom}
2046 \@@_define_feature_option:nnnnn{VerticalPosition}{ScientificInferior}{}{}{+sinf}

```

28.0.14 Fractions

```

2047 \@@_define_font_feature:n{Fractions}
2048 \@@_define_feature_option:nnnnn{Fractions}{On} {11}{1}{+frac}
2049 \@@_define_feature_option:nnnnn{Fractions}{Off} {11}{0}{-frac}
2050 \@@_define_feature_option:nnnnn{Fractions}{Diagonal} {11}{2}{}
2051 \@@_define_feature_option:nnnnn{Fractions}{Alternate}{} {} {+afrc}

```

28.0.15 Alternates and variants

Selected numerically because they don't have standard names. Very easy to process, very annoying for the user!

```

2052 \@@_define_font_feature:n { Alternate }
2053 \keys_define:nn {fontspec}
2054 {
2055   Alternate .default:n = {0} ,
2056   Alternate / unknown .code:n =
2057     {
2058       \clist_map_inline:nn {#1}
2059         { \fontspec_make_feature:nnx {17}{##1} { \fontspec_salt:n {##1} } }
2060     }
2061 }

2062 \cs_set:Nn \fontspec_salt:n { +salt = #1 }

2063 \@@_define_font_feature:n {Variant}
2064 \keys_define:nn {fontspec}
2065 {
2066   Variant .default:n = {0} ,
2067   Variant / unknown .code:n =
2068     {
2069       \clist_map_inline:nn {#1}
2070         { \fontspec_make_feature:nnx {18}{##1} { +ss \two@digits {##1} } }
2071     }
2072 }
2073 \aliasfontfeature{Variant}{StylisticSet}

2074 \@@_define_font_feature:n { CharacterVariant }
2075 \use:x
2076 {
2077   \cs_new:Npn \exp_not:N \fontspec_parse_cv:w
2078     ##1 \c_colon_str ##2 \c_colon_str ##3 \exp_not:N \q_nil
2079     {
2080       \fontspec_make_numbered_feature:xn
2081         { +cv \exp_not:N \two@digits {##1} } {##2}
2082     }
2083   \keys_define:nn {fontspec}

```

```

2084 {
2085   CharacterVariant / unknown .code:n =
2086   {
2087     \clist_map_inline:nn {##1}
2088     {
2089       \exp_not:N \fontspec_parse_cv:w
2090       #####1 \c_colon_str 0 \c_colon_str \exp_not:N \q_nil
2091     }
2092   }
2093 }
2094 }

```

Possibilities: a:0:\q_nil or a:b:0:\q_nil.

28.0.16 Style

```

2095 \@@_define_font_feature:n{Style}
2096 \@@_define_feature_option:nnnnn{Style}{Alternate}      {} {} {+salt}
2097 \@@_define_feature_option:nnnnn{Style}{Italic}        {32}{2}{+ital}
2098 \@@_define_feature_option:nnnnn{Style}{Ruby}          {28}{2}{+ruby}
2099 \@@_define_feature_option:nnnnn{Style}{Swash}         {} {} {+swsh}
2100 \@@_define_feature_option:nnnnn{Style}{Historic}     {} {} {+hist}
2101 \@@_define_feature_option:nnnnn{Style}{Display}      {19}{1}{}
2102 \@@_define_feature_option:nnnnn{Style}{Engraved}     {19}{2}{}
2103 \@@_define_feature_option:nnnnn{Style}{TitlingCaps}  {19}{4}{+titl}
2104 \@@_define_feature_option:nnnnn{Style}{TallCaps}     {19}{5}{}
2105 \@@_define_feature_option:nnnnn{Style}{HorizontalKana}{ } {} {+hkna}
2106 \@@_define_feature_option:nnnnn{Style}{VerticalKana} {} {} {+vkna}
2107 \fontspec_define_numbered_feat:nnnn {Style} {MathScript}      {+ssty} {0}
2108 \fontspec_define_numbered_feat:nnnn {Style} {MathScriptScript} {+ssty} {1}

```

28.0.17 CJK shape

```

2109 \@@_define_font_feature:n{CJKShape}
2110 \@@_define_feature_option:nnnnn{CJKShape}{Traditional}{20}{0} {+trad}
2111 \@@_define_feature_option:nnnnn{CJKShape}{Simplified} {20}{1} {+smp1}
2112 \@@_define_feature_option:nnnnn{CJKShape}{JIS1978}   {20}{2} {+jp78}
2113 \@@_define_feature_option:nnnnn{CJKShape}{JIS1983}   {20}{3} {+jp83}
2114 \@@_define_feature_option:nnnnn{CJKShape}{JIS1990}   {20}{4} {+jp90}
2115 \@@_define_feature_option:nnnnn{CJKShape}{Expert}    {20}{10}{+expt}
2116 \@@_define_feature_option:nnnnn{CJKShape}{NLC}       {20}{13}{+nlck}

```

28.0.18 Character width

```

2117 \@@_define_font_feature:n{CharacterWidth}
2118 \@@_define_feature_option:nnnnn{CharacterWidth}{Proportional}{22}{0}{+pwid}
2119 \@@_define_feature_option:nnnnn{CharacterWidth}{Full}{22}{1}{+fwid}
2120 \@@_define_feature_option:nnnnn{CharacterWidth}{Half}{22}{2}{+hwid}
2121 \@@_define_feature_option:nnnnn{CharacterWidth}{Third}{22}{3}{+twid}
2122 \@@_define_feature_option:nnnnn{CharacterWidth}{Quarter}{22}{4}{+qwid}
2123 \@@_define_feature_option:nnnnn{CharacterWidth}{AlternateProportional}{22}{5}{+palt}
2124 \@@_define_feature_option:nnnnn{CharacterWidth}{AlternateHalf}{22}{6}{+halt}
2125 \@@_define_feature_option:nnnnn{CharacterWidth}{Default}{22}{7}{}

```

28.0.19 Annotation

```
2126 \@@_define_feature_option:nnnnn{Annotation}{Off}{24}{0}{}
2127 \@@_define_feature_option:nnnnn{Annotation}{Box}{24}{1}{}
2128 \@@_define_feature_option:nnnnn{Annotation}{RoundedBox}{24}{2}{}
2129 \@@_define_feature_option:nnnnn{Annotation}{Circle}{24}{3}{}
2130 \@@_define_feature_option:nnnnn{Annotation}{BlackCircle}{24}{4}{}
2131 \@@_define_feature_option:nnnnn{Annotation}{Parenthesis}{24}{5}{}
2132 \@@_define_feature_option:nnnnn{Annotation}{Period}{24}{6}{}
2133 \@@_define_feature_option:nnnnn{Annotation}{RomanNumerals}{24}{7}{}
2134 \@@_define_feature_option:nnnnn{Annotation}{Diamond}{24}{8}{}
2135 \@@_define_feature_option:nnnnn{Annotation}{BlackSquare}{24}{9}{}
2136 \@@_define_feature_option:nnnnn{Annotation}{BlackRoundSquare}{24}{10}{}
2137 \@@_define_feature_option:nnnnn{Annotation}{DoubleCircle}{24}{11}{}

2138 \@@_define_font_feature:n { Annotation }
2139 \keys_define:nn {fontspec}
2140 {
2141   Annotation .default:n = {0} ,
2142   Annotation / unknown .code:n =
2143   {
2144     \fontspec_make_feature:nxx {}{}{ +nalt=#1 }
2145   }
2146 }
```

28.0.20 Vertical

```
2147 \keys_define:nn {fontspec}
2148 {
2149   Vertical .choice: ,
2150   Vertical / RotatedGlyphs .code:n =
2151   {
2152     \bool_if:NTF \l_@@_ot_bool
2153     {
2154       \fontspec_make_feature:nnn{}{}{+vrt2}
2155       \@@_update_featstr:n {vertical}
2156     }
2157     {
2158       \@@_update_featstr:n {vertical}
2159     }
2160   }
2161 }
```

28.0.21 Script

```
2162 \keys_define:nn { fontspec } { Script .choice: }
2163 \cs_new:Nn \fontspec_new_script:nn
2164 {
2165   \keys_define:nn { fontspec } { Script / #1 .code:n =
2166     \clist_map_inline:nn {#2}
2167     {
2168       \fontspec_check_script:nTF {###1}
2169       {
2170         \tl_set:Nn \l_fontspec_script_tl {###1}
2171         \int_set:Nn \l_fontspec_script_int {\l_fontspec_strnum_int}
```

```

2172     \clist_map_break:
2173     }
2174     {
2175     \fontspec_check_script:nTF {latn}
2176     {
2177     \@@_warning:nx {script-not-exist-latn} {#1}
2178     \keys_set:nn {fontspec} {Script=Latin}
2179     }
2180     {
2181     \@@_warning:nx {script-not-exist} {#1}
2182     }
2183     }
2184   }
2185 }
2186 }

2187 \newfontscript{Arabic}{arab}           \newfontscript{Armenian}{armn}
2188 \newfontscript{Balinese}{bali}
2189 \newfontscript{Bengali}{bng2,beng}
2190 \newfontscript{Bopomofo}{bopo}       \newfontscript{Braille}{brai}
2191 \newfontscript{Buginese}{bugi}       \newfontscript{Buhid}{buhd}
2192 \newfontscript{Byzantine~Music}{byzm}
2193 \newfontscript{Canadian~Syllabics}{cans}
2194 \newfontscript{Cherokee}{cher}
2195 \newfontscript{CJK~Ideographic}{hani} \newfontscript{Coptic}{copt}
2196 \newfontscript{Cypriot~Syllabary}{cpri} \newfontscript{Cyrillic}{cyr1}
2197 \newfontscript{Default}{DFLT}        \newfontscript{Deseret}{dsrt}
2198 \newfontscript{Devanagari}{dev2,deva}
2199 \newfontscript{Ethiopic}{ethi}
2200 \newfontscript{Georgian}{geor}       \newfontscript{Glagolitic}{glag}
2201 \newfontscript{Gothic}{goth}        \newfontscript{Greek}{grek}
2202 \newfontscript{Gujarati}{gjr2,gujr}
2203 \newfontscript{Gurmukhi}{gur2,guru}
2204 \newfontscript{Hangul~Jamo}{jamo}    \newfontscript{Hangul}{hang}
2205 \newfontscript{Hanunoo}{hano}        \newfontscript{Hebrew}{hebr}
2206 \newfontscript{Hiragana~and~Katakana}{kana}
2207 \newfontscript{Javanese}{java}
2208 \newfontscript{Kannada}{knd2,knda}
2209 \newfontscript{Kharosthi}{khar}     \newfontscript{Khmer}{khmr}
2210 \newfontscript{Lao}{lao~}          \newfontscript{Latin}{latn}
2211 \newfontscript{Limbu}{limb}        \newfontscript{Linear~B}{linb}
2212 \newfontscript{Malayalam}{mlm2,mlym}
2213 \newfontscript{Math}{math}
2214 \newfontscript{Mongolian}{mong}
2215 \newfontscript{Musical~Symbols}{musc} \newfontscript{Myanmar}{mymr}
2216 \newfontscript{N'ko}{nko~}        \newfontscript{Ogham}{ogam}
2217 \newfontscript{Old~Italic}{ital}
2218 \newfontscript{Old~Persian~Cuneiform}{xpeo}
2219 \newfontscript{Oriya}{ory2,orya}
2220 \newfontscript{Osmanya}{osma}
2221 \newfontscript{Phags-pa}{phag}     \newfontscript{Phoenician}{phnx}
2222 \newfontscript{Runic}{runr}        \newfontscript{Shavian}{shaw}

```

```

2223 \newfontscript{Sinhala}{sinh}
2224 \newfontscript{Sumero-Akkadian~Cuneiform}{xsux}
2225 \newfontscript{Syloti~Nagri}{sylo}      \newfontscript{Syriac}{syr}
2226 \newfontscript{Tagalog}{tglg}          \newfontscript{Tagbanwa}{tagb}
2227 \newfontscript{Tai~Le}{tale}          \newfontscript{Tai~Lu}{tal}
2228 \newfontscript{Tamil}{tml2,taml}
2229 \newfontscript{Telugu}{tel2,telu}
2230 \newfontscript{Thaana}{thaa}          \newfontscript{Thai}{thai}
2231 \newfontscript{Tibetan}{tib}         \newfontscript{Tifinagh}{tfn}
2232 \newfontscript{Ugaritic~Cuneiform}{ugar}\newfontscript{Yi}{yi}

```

For convenience:

```

2233 \newfontscript{Kana}{kana}
2234 \newfontscript{Maths}{math}
2235 \newfontscript{CJK}{hani}

```

28.0.22 Language

```

2236 \keys_define:nn { fontspec } { Language .choice: }
2237 \cs_new:Nn \fontspec_new_lang:nn
2238 {
2239   \keys_define:nn { fontspec } { Language / #1 .code:n =
2240     \fontspec_check_lang:nTF {#2}
2241     {
2242       \tl_set:Nn \l_fontspec_lang_tl {#2}
2243       \int_set:Nn \l_fontspec_language_int {\l_fontspec_strnum_int}
2244     }
2245     {
2246       \@@_warning:nx {language-not-exist} {#1}
2247       \keys_set:nn { fontspec } { Language = Default }
2248     }
2249 }
2250 }

2251 \newfontlanguage{Abaza}{ABA}\newfontlanguage{Abkhazian}{ABK}
2252 \newfontlanguage{Aadyghe}{ADY}\newfontlanguage{Afrikaans}{AFK}
2253 \newfontlanguage{Afar}{AFR}\newfontlanguage{Agaw}{AGW}
2254 \newfontlanguage{Altai}{ALT}\newfontlanguage{Amharic}{AMH}
2255 \newfontlanguage{Arabic}{ARA}\newfontlanguage{Aari}{ARI}
2256 \newfontlanguage{Arakanese}{ARK}\newfontlanguage{Assamese}{ASM}
2257 \newfontlanguage{Athapaskan}{ATH}\newfontlanguage{Avar}{AVR}
2258 \newfontlanguage{Awadhi}{AWA}\newfontlanguage{Aymara}{AYM}
2259 \newfontlanguage{Azeri}{AZE}\newfontlanguage{Badaga}{BAD}
2260 \newfontlanguage{Baghelkhandi}{BAG}\newfontlanguage{Balkar}{BAL}
2261 \newfontlanguage{Baule}{BAU}\newfontlanguage{Berber}{BBR}
2262 \newfontlanguage{Bench}{BCH}\newfontlanguage{Bible~Cree}{BCR}
2263 \newfontlanguage{Belarussian}{BEL}\newfontlanguage{Bemba}{BEM}
2264 \newfontlanguage{Bengali}{BEN}\newfontlanguage{Bulgarian}{BGR}
2265 \newfontlanguage{Bhili}{BHI}\newfontlanguage{Bhojpuri}{BHO}
2266 \newfontlanguage{Bikol}{BIK}\newfontlanguage{Bilen}{BIL}
2267 \newfontlanguage{Blackfoot}{BKF}\newfontlanguage{Balochi}{BLI}
2268 \newfontlanguage{Balante}{BLN}\newfontlanguage{Balti}{BLT}
2269 \newfontlanguage{Bambara}{BMB}\newfontlanguage{Bamileke}{BML}
2270 \newfontlanguage{Breton}{BRE}\newfontlanguage{Brahui}{BRH}

```

2271 \newfontlanguage{Braj~Bhasha}{BRI}\newfontlanguage{Burmese}{BRM}
2272 \newfontlanguage{Bashkir}{BSH}\newfontlanguage{Beti}{BTI}
2273 \newfontlanguage{Catalan}{CAT}\newfontlanguage{Cebuano}{CEB}
2274 \newfontlanguage{Chechen}{CHE}\newfontlanguage{Chaha~Gurage}{CHG}
2275 \newfontlanguage{Chattisgarhi}{CHH}\newfontlanguage{Chichewa}{CHI}
2276 \newfontlanguage{Chukchi}{CHK}\newfontlanguage{Chipewyan}{CHP}
2277 \newfontlanguage{Cherokee}{CHR}\newfontlanguage{Chuvash}{CHU}
2278 \newfontlanguage{Comorian}{CMR}\newfontlanguage{Coptic}{COP}
2279 \newfontlanguage{Cree}{CRE}\newfontlanguage{Carrier}{CRR}
2280 \newfontlanguage{Crimean~Tatar}{CRT}\newfontlanguage{Church~Slavonic}{CSL}
2281 \newfontlanguage{Czech}{CSY}\newfontlanguage{Danish}{DAN}
2282 \newfontlanguage{Dargwa}{DAR}\newfontlanguage{Woods~Cree}{DCR}
2283 \newfontlanguage{German}{DEU}
2284 \newfontlanguage{Dogri}{DGR}\newfontlanguage{Divehi}{DIV}
2285 \newfontlanguage{Djerma}{DJR}\newfontlanguage{Dangme}{DNG}
2286 \newfontlanguage{Dinka}{DNK}\newfontlanguage{Dungan}{DUN}
2287 \newfontlanguage{Dzongkha}{DZN}\newfontlanguage{Ebira}{EBI}
2288 \newfontlanguage{Eastern~Cree}{ECR}\newfontlanguage{Edo}{EDO}
2289 \newfontlanguage{Efik}{EFI}\newfontlanguage{Greek}{ELL}
2290 \newfontlanguage{English}{ENG}\newfontlanguage{Erzya}{ERZ}
2291 \newfontlanguage{Spanish}{ESP}\newfontlanguage{Estonian}{ETI}
2292 \newfontlanguage{Basque}{EUQ}\newfontlanguage{Evenki}{EVK}
2293 \newfontlanguage{Even}{EVN}\newfontlanguage{Ewe}{EWE}
2294 \newfontlanguage{French~Antillean}{FAN}
2295 \newfontlanguage{Farsi}{FAR}
2296 \newfontlanguage{Persi}{FAR}
2297 \newfontlanguage{Persian}{FAR}
2298 \newfontlanguage{Finnish}{FIN}\newfontlanguage{Fijian}{FJI}
2299 \newfontlanguage{Flemish}{FLE}\newfontlanguage{Forest~Nenets}{FNE}
2300 \newfontlanguage{Fon}{FON}\newfontlanguage{Faroese}{FOS}
2301 \newfontlanguage{French}{FRA}\newfontlanguage{Frisian}{FRI}
2302 \newfontlanguage{Friulian}{FRL}\newfontlanguage{Futa}{FTA}
2303 \newfontlanguage{Fulani}{FUL}\newfontlanguage{Ga}{GAD}
2304 \newfontlanguage{Gaelic}{GAE}\newfontlanguage{Gagauz}{GAG}
2305 \newfontlanguage{Galician}{GAL}\newfontlanguage{Garshuni}{GAR}
2306 \newfontlanguage{Garhwali}{GAW}\newfontlanguage{Ge'ez}{GEZ}
2307 \newfontlanguage{Gilyak}{GIL}\newfontlanguage{Gumuz}{GMZ}
2308 \newfontlanguage{Gondi}{GON}\newfontlanguage{Greenlandic}{GRN}
2309 \newfontlanguage{Garo}{GRO}\newfontlanguage{Guarani}{GUA}
2310 \newfontlanguage{Gujarati}{GUJ}\newfontlanguage{Haitian}{HAI}
2311 \newfontlanguage{Halam}{HAL}\newfontlanguage{Harauti}{HAR}
2312 \newfontlanguage{Hausa}{HAU}\newfontlanguage{Hawaiin}{HAW}
2313 \newfontlanguage{Hammer-Banna}{HBN}\newfontlanguage{Hiligaynon}{HIL}
2314 \newfontlanguage{Hindi}{HIN}\newfontlanguage{High~Mari}{HMA}
2315 \newfontlanguage{Hindko}{HND}\newfontlanguage{Ho}{HO}
2316 \newfontlanguage{Harari}{HRI}\newfontlanguage{Croatian}{HRV}
2317 \newfontlanguage{Hungarian}{HUN}\newfontlanguage{Armenian}{HYE}
2318 \newfontlanguage{Igbo}{IBO}\newfontlanguage{Ijo}{IJO}
2319 \newfontlanguage{Ilokano}{ILO}\newfontlanguage{Indonesian}{IND}
2320 \newfontlanguage{Ingush}{ING}\newfontlanguage{Inuktitut}{INU}
2321 \newfontlanguage{Irish}{IRI}\newfontlanguage{Irish~Traditional}{IRT}

2322 \newfontlanguage{Icelandic}{ISL}\newfontlanguage{Inari~Sami}{ISM}
2323 \newfontlanguage{Italian}{ITA}\newfontlanguage{Hebrew}{IWR}
2324 \newfontlanguage{Javanese}{JAV}\newfontlanguage{Yiddish}{JII}
2325 \newfontlanguage{Japanese}{JAN}\newfontlanguage{Judezmo}{JUD}
2326 \newfontlanguage{Jula}{JUL}\newfontlanguage{Kabardian}{KAB}
2327 \newfontlanguage{Kachchi}{KAC}\newfontlanguage{Kalenjin}{KAL}
2328 \newfontlanguage{Kannada}{KAN}\newfontlanguage{Karachay}{KAR}
2329 \newfontlanguage{Georgian}{KAT}\newfontlanguage{Kazakh}{KAZ}
2330 \newfontlanguage{Kebena}{KEB}\newfontlanguage{Khutsuri~Georgian}{KGE}
2331 \newfontlanguage{Khakass}{KHA}\newfontlanguage{Khanty-Kazim}{KHK}
2332 \newfontlanguage{Khmer}{KHM}\newfontlanguage{Khanty-Shurishkar}{KHS}
2333 \newfontlanguage{Khanty-Vakhi}{KHV}\newfontlanguage{Khowar}{KHW}
2334 \newfontlanguage{Kikuyu}{KIK}\newfontlanguage{Kirghiz}{KIR}
2335 \newfontlanguage{Kisii}{KIS}\newfontlanguage{Kokni}{KKN}
2336 \newfontlanguage{Kalmyk}{KLM}\newfontlanguage{Kamba}{KMB}
2337 \newfontlanguage{Kumaoni}{KMN}\newfontlanguage{Komo}{KMO}
2338 \newfontlanguage{Komso}{KMS}\newfontlanguage{Kanuri}{KNR}
2339 \newfontlanguage{Kodagu}{KOD}\newfontlanguage{Korean~Old~Hangul}{KOH}
2340 \newfontlanguage{Konkani}{KOK}\newfontlanguage{Kikongo}{KON}
2341 \newfontlanguage{Komi-Permyak}{KOP}\newfontlanguage{Korean}{KOR}
2342 \newfontlanguage{Komi-Zyrian}{KOZ}\newfontlanguage{Kpelle}{KPL}
2343 \newfontlanguage{Krio}{KRI}\newfontlanguage{Karakalpak}{KPK}
2344 \newfontlanguage{Karelian}{KRL}\newfontlanguage{Karaim}{KRM}
2345 \newfontlanguage{Karen}{KRN}\newfontlanguage{Koorete}{KRT}
2346 \newfontlanguage{Kashmiri}{KSH}\newfontlanguage{Khasi}{KSI}
2347 \newfontlanguage{Kildin~Sami}{KSM}\newfontlanguage{Kui}{KUI}
2348 \newfontlanguage{Kulvi}{KUL}\newfontlanguage{Kumyk}{KUM}
2349 \newfontlanguage{Kurdish}{KUR}\newfontlanguage{Kurukh}{KUU}
2350 \newfontlanguage{Kuy}{KUY}\newfontlanguage{Koryak}{KYK}
2351 \newfontlanguage{Ladin}{LAD}\newfontlanguage{Lahuli}{LAH}
2352 \newfontlanguage{Lak}{LAK}\newfontlanguage{Lambani}{LAM}
2353 \newfontlanguage{Lao}{LAO}\newfontlanguage{Latin}{LAT}
2354 \newfontlanguage{Laz}{LAZ}\newfontlanguage{L-Cree}{LCR}
2355 \newfontlanguage{Ladakhi}{LDK}\newfontlanguage{Lezgi}{LEZ}
2356 \newfontlanguage{Lingala}{LIN}\newfontlanguage{Low~Mari}{LMA}
2357 \newfontlanguage{Limbu}{LMB}\newfontlanguage{Lomwe}{LMW}
2358 \newfontlanguage{Lower~Sorbian}{LSB}\newfontlanguage{Lule~Sami}{LSM}
2359 \newfontlanguage{Lithuanian}{LTH}\newfontlanguage{Luba}{LUB}
2360 \newfontlanguage{Luganda}{LUG}\newfontlanguage{Luhya}{LUH}
2361 \newfontlanguage{Luo}{LUO}\newfontlanguage{Latvian}{LVI}
2362 \newfontlanguage{Majang}{MAJ}\newfontlanguage{Makua}{MAK}
2363 \newfontlanguage{Malayalam~Traditional}{MAL}\newfontlanguage{Mansi}{MAN}
2364 \newfontlanguage{Marathi}{MAR}\newfontlanguage{Marwari}{MAW}
2365 \newfontlanguage{Mbundu}{MBN}\newfontlanguage{Manchu}{MCH}
2366 \newfontlanguage{Moose~Cree}{MCR}\newfontlanguage{Mende}{MDE}
2367 \newfontlanguage{Me'en}{MEN}\newfontlanguage{Mizo}{MIZ}
2368 \newfontlanguage{Macedonian}{MKD}\newfontlanguage{Male}{MLE}
2369 \newfontlanguage{Malagasy}{MLG}\newfontlanguage{Malinke}{MLN}
2370 \newfontlanguage{Malayalam~Reformed}{MLR}\newfontlanguage{Malay}{MLY}
2371 \newfontlanguage{Mandinka}{MND}\newfontlanguage{Mongolian}{MNG}
2372 \newfontlanguage{Manipuri}{MNI}\newfontlanguage{Maninka}{MNK}

2373 \newfontlanguage{Manx~Gaelic}{MNX}\newfontlanguage{Moksha}{MOK}
2374 \newfontlanguage{Moldavian}{MOL}\newfontlanguage{Mon}{MON}
2375 \newfontlanguage{Moroccan}{MOR}\newfontlanguage{Maori}{MRI}
2376 \newfontlanguage{Mraithili}{MTH}\newfontlanguage{Maltese}{MTS}
2377 \newfontlanguage{Mundari}{MUN}\newfontlanguage{Naga-Assamese}{NAG}
2378 \newfontlanguage{Nanai}{NAN}\newfontlanguage{Naskapi}{NAS}
2379 \newfontlanguage{N-Cree}{NCR}\newfontlanguage{Ndebele}{NDB}
2380 \newfontlanguage{Ndonga}{NDG}\newfontlanguage{Nepali}{NEP}
2381 \newfontlanguage{Newari}{NEW}\newfontlanguage{Nagari}{NGR}
2382 \newfontlanguage{Norway~House~Cree}{NHC}\newfontlanguage{Nisi}{NIS}
2383 \newfontlanguage{Niuean}{NIU}\newfontlanguage{Nkole}{NKL}
2384 \newfontlanguage{N'ko}{NKO}\newfontlanguage{Dutch}{NLD}
2385 \newfontlanguage{Nogai}{NOG}\newfontlanguage{Norwegian}{NOR}
2386 \newfontlanguage{Northern~Sami}{NSM}\newfontlanguage{Northern~Tai}{NTA}
2387 \newfontlanguage{Esperanto}{NTO}\newfontlanguage{Nynorsk}{NYN}
2388 \newfontlanguage{Oji-Cree}{OCR}\newfontlanguage{Ojibway}{OBJ}
2389 \newfontlanguage{Oriya}{ORI}\newfontlanguage{Oromo}{ORO}
2390 \newfontlanguage{Ossetian}{OSS}\newfontlanguage{Palestinian~Aramaic}{PAA}
2391 \newfontlanguage{Pali}{PAL}\newfontlanguage{Punjabi}{PAN}
2392 \newfontlanguage{Palpa}{PAP}\newfontlanguage{Pashto}{PAS}
2393 \newfontlanguage{Polytonic~Greek}{PGR}\newfontlanguage{Pilipino}{PIL}
2394 \newfontlanguage{Palaung}{PLG}\newfontlanguage{Polish}{PLK}
2395 \newfontlanguage{Provencal}{PRO}\newfontlanguage{Portuguese}{PTG}
2396 \newfontlanguage{Chin}{QIN}\newfontlanguage{Rajasthani}{RAJ}
2397 \newfontlanguage{R-Cree}{RCR}\newfontlanguage{Russian~Buriat}{RBU}
2398 \newfontlanguage{Riang}{RIA}\newfontlanguage{Rhaeto-Romanic}{RMS}
2399 \newfontlanguage{Romanian}{ROM}\newfontlanguage{Romany}{ROY}
2400 \newfontlanguage{Rusyn}{RSY}\newfontlanguage{Ruanda}{RUA}
2401 \newfontlanguage{Russian}{RUS}\newfontlanguage{Sadri}{SAD}
2402 \newfontlanguage{Sanskrit}{SAN}\newfontlanguage{Santali}{SAT}
2403 \newfontlanguage{Sayisi}{SAY}\newfontlanguage{Sekota}{SEK}
2404 \newfontlanguage{Selkup}{SEL}\newfontlanguage{Sango}{SGO}
2405 \newfontlanguage{Shan}{SHN}\newfontlanguage{Sibe}{SIB}
2406 \newfontlanguage{Sidamo}{SID}\newfontlanguage{Silte~Gurage}{SIG}
2407 \newfontlanguage{Skolt~Sami}{SKS}\newfontlanguage{Slovak}{SKY}
2408 \newfontlanguage{Slavey}{SLA}\newfontlanguage{Slovenian}{SLV}
2409 \newfontlanguage{Somali}{SML}\newfontlanguage{Samoan}{SMO}
2410 \newfontlanguage{Sena}{SNA}\newfontlanguage{Sindhi}{SND}
2411 \newfontlanguage{Sinhalese}{SNH}\newfontlanguage{Soninke}{SNK}
2412 \newfontlanguage{Sodo~Gurage}{SOG}\newfontlanguage{Sotho}{SOT}
2413 \newfontlanguage{Albanian}{SQI}\newfontlanguage{Serbian}{SRB}
2414 \newfontlanguage{Saraiki}{SRK}\newfontlanguage{Serer}{SRR}
2415 \newfontlanguage{South~Slavey}{SSL}\newfontlanguage{Southern~Sami}{SSM}
2416 \newfontlanguage{Suri}{SUR}\newfontlanguage{Svan}{SVA}
2417 \newfontlanguage{Swedish}{SVE}\newfontlanguage{Swadaya~Aramaic}{SWA}
2418 \newfontlanguage{Swahili}{SWK}\newfontlanguage{Swazi}{SWZ}
2419 \newfontlanguage{Sutu}{SXT}\newfontlanguage{Syriac}{SYR}
2420 \newfontlanguage{Tabasaran}{TAB}\newfontlanguage{Tajiki}{TAJ}
2421 \newfontlanguage{Tamil}{TAM}\newfontlanguage{Tatar}{TAT}
2422 \newfontlanguage{TH-Cree}{TCR}\newfontlanguage{Telugu}{TEL}
2423 \newfontlanguage{Tongan}{TGN}\newfontlanguage{Tigre}{TGR}

```

2424 \newfontlanguage{Tigrinya}{TGY}\newfontlanguage{Thai}{THA}
2425 \newfontlanguage{Tahitian}{THT}\newfontlanguage{Tibetan}{TIB}
2426 \newfontlanguage{Turkmen}{TKM}\newfontlanguage{Temne}{TMN}
2427 \newfontlanguage{Tswana}{TNA}\newfontlanguage{Tundra~Nenets}{TNE}
2428 \newfontlanguage{Tonga}{TNG}\newfontlanguage{Todo}{TOD}
2429 \newfontlanguage{Tsonga}{TSG}\newfontlanguage{Turoyo~Aramaic}{TUA}
2430 \newfontlanguage{Tulu}{TUL}\newfontlanguage{Tuvini}{TUV}
2431 \newfontlanguage{Twi}{TWI}\newfontlanguage{Udmurt}{UDM}
2432 \newfontlanguage{Ukrainian}{UKR}\newfontlanguage{Urdu}{URD}
2433 \newfontlanguage{Upper~Sorbian}{USB}\newfontlanguage{Uyghur}{UYG}
2434 \newfontlanguage{Uzbek}{UZB}\newfontlanguage{Venda}{VEN}
2435 \newfontlanguage{Vietnamese}{VIT}\newfontlanguage{Wa}{WA}
2436 \newfontlanguage{Wagdi}{WAG}\newfontlanguage{West-Cree}{WCR}
2437 \newfontlanguage{Welsh}{WEL}\newfontlanguage{Wolof}{WLF}
2438 \newfontlanguage{Tai~Lue}{XBD}\newfontlanguage{Xhosa}{XHS}
2439 \newfontlanguage{Yakut}{YAK}\newfontlanguage{Yoruba}{YBA}
2440 \newfontlanguage{Y-Cree}{YCR}\newfontlanguage{Yi~Classic}{YIC}
2441 \newfontlanguage{Yi~Modern}{YIM}\newfontlanguage{Chinese~Hong~Kong}{ZHH}
2442 \newfontlanguage{Chinese~Phonetic}{ZHP}
2443 \newfontlanguage{Chinese~Simplified}{ZHS}
2444 \newfontlanguage{Chinese~Traditional}{ZHT}\newfontlanguage{Zande}{ZND}
2445 \newfontlanguage{Zulu}{ZUL}

```

Turkish Turns out that many fonts use ‘TUR’ as their Turkish language tag rather than the specified ‘TRK’. So we check for both:

```

2446 \keys_define:nn {fontspec}
2447 {
2448   Language / Turkish .code:n =
2449   {
2450     \fontspec_check_lang:nTF {TRK}
2451     {
2452       \int_set:Nn \l_fontspec_language_int {\l_fontspec_strnum_int}
2453       \tl_set:Nn \l_fontspec_lang_tl {TRK}
2454     }
2455     {
2456       \fontspec_check_lang:nTF {TUR}
2457       {
2458         \int_set:Nn \l_fontspec_language_int {\l_fontspec_strnum_int}
2459         \tl_set:Nn \l_fontspec_lang_tl {TUR}
2460       }
2461       {
2462         \@_warning:nx {language-not-exist} {Turkish}
2463         \keys_set:nn {fontspec} {Language=Default}
2464       }
2465     }
2466   }
2467 }

```

Default

```

2468 \@_keys_define_code:nnn {fontspec}{ Language / Default }
2469 {

```

```

2470 \tl_set:Nn \l_fontspec_lang_tl {DFLT}
2471 \int_zero:N \l_fontspec_language_int
2472 }

```

28.0.23 Raw feature string

This allows savvy X_YTeX-ers to input font features manually if they have already memorised the OpenType abbreviations and don't mind not having error checking.

```

2473 \@@_keys_define_code:nnn {fontspec} {RawFeature}
2474 {
2475   \@@_update_featstr:n {#1}
2476 }

```

29 Selecting maths fonts

Here, the fonts used in math mode are redefined to correspond to the default roman, sans serif and typewriter fonts. Unfortunately, you can only define maths fonts in the preamble, otherwise I'd run this code whenever `\setmainfont` and `friends` was run.

`\fontspec_setup_maths:` Everything here is performed `\AtBeginDocument` in order to overwrite euler's attempt. This means `fontspec` must be loaded *after* `euler`. We set up a conditional to return an error if this rule is violated.

Since every maths setup is slightly different, we also take different paths for defining various math glyphs depending which maths font package has been loaded.

```

2477 \ifpackageloaded{euler}
2478 {
2479   \bool_set_true:N \g_@@_pkg_euler_loaded_bool
2480 }
2481 {
2482   \bool_set_false:N \g_@@_pkg_euler_loaded_bool
2483 }
2484 \cs_set:Nn \fontspec_setup_maths:
2485 {
2486   \ifpackageloaded{euler}
2487   {
2488     \bool_if:NTF \g_@@_pkg_euler_loaded_bool
2489     { \bool_set_true:N \g_@@_math_euler_bool }
2490     { \@@_error:n {euler-too-late} }
2491   }
2492   {}
2493   \ifpackageloaded{luabmath}{\bool_set_true:N \g_@@_math_lucida_bool}{}
2494   \ifpackageloaded{lucidabr}{\bool_set_true:N \g_@@_math_lucida_bool}{}
2495   \ifpackageloaded{lucimatx}{\bool_set_true:N \g_@@_math_lucida_bool}{}

```

Knuth's CM fonts are all squashed together, combining letters, accents, text symbols and maths symbols all in the one font, `cmr`, plus other things in other

fonts. Because we are changing the roman font in the document, we need to redefine all of the maths glyphs in L^AT_EX's operators maths font to still go back to the legacy cmr font for all these random glyphs, unless a separate maths font package has been loaded instead.

In every case, the maths accents are always taken from the operators font, which is generally the main text font. (Actually, there is a \hat accent in EulerFraktur, but it's *ugly*. So I ignore it. Sorry if this causes inconvenience.)

```

2496 \DeclareSymbolFont{legacymaths}{OT1}{cmr}{m}{n}
2497 \SetSymbolFont{legacymaths}{bold}{OT1}{cmr}{bx}{n}
2498 \DeclareMathAccent{\acute} {\mathalpha}{legacymaths}{19}
2499 \DeclareMathAccent{\grave} {\mathalpha}{legacymaths}{18}
2500 \DeclareMathAccent{\ddot} {\mathalpha}{legacymaths}{127}
2501 \DeclareMathAccent{\tilde} {\mathalpha}{legacymaths}{126}
2502 \DeclareMathAccent{\bar} {\mathalpha}{legacymaths}{22}
2503 \DeclareMathAccent{\breve} {\mathalpha}{legacymaths}{21}
2504 \DeclareMathAccent{\check} {\mathalpha}{legacymaths}{20}
2505 \DeclareMathAccent{\hat} {\mathalpha}{legacymaths}{94} % too bad, euler
2506 \DeclareMathAccent{\dot} {\mathalpha}{legacymaths}{95}
2507 \DeclareMathAccent{\mathring}{\mathalpha}{legacymaths}{23}

```

\colon: what's going on? Okay, so $:$ and \colon in maths mode are defined in a few places, so I need to work out what does what. Respectively, we have:

```

% % fontmath.ltx:
% \DeclareMathSymbol{\colon}{\mathpunct}{operators}{"3A}
% \DeclareMathSymbol{:}{\mathrel}{operators}{"3A}
%
% % amsmath.sty:
% \renewcommand{\colon}{\nobreak\mskip2mu\mathpunct{}\nonscript
% \mkern-\thinmuskip{:}\mskip6mu\plus1mu\relax}
%
% % euler.sty:
% \DeclareMathSymbol{:}{\mathrel} {EulerFraktur}{"3A}
%
% % lucbmath.sty:
% \DeclareMathSymbol{\@tempb}{\mathpunct}{operators}{58}
% \ifx\colon\@tempb
% \DeclareMathSymbol{\colon}{\mathpunct}{operators}{58}
% \fi
% \DeclareMathSymbol{:}{\mathrel}{operators}{58}

```

(3A.16 = 58.10) So I think, based on this summary, that it is fair to tell fontspec to 'replace' the operators font with legacymaths for this symbol, except when amsmath is loaded since we want to keep its definition.

```

2508 \group_begin:
2509 \mathchardef\@tempa="603A \relax
2510 \ifx\colon\@tempa
2511 \DeclareMathSymbol{\colon}{\mathpunct}{legacymaths}{58}
2512 \fi

```

2513 `\group_end:`

The following symbols are only defined specifically in euler, so skip them if that package is loaded.

```
2514 \bool_if:NF \g_@@_math_euler_bool
2515 {
2516   \DeclareMathSymbol{!}{\mathclose}{legacymaths}{33}
2517   \DeclareMathSymbol{:}{\mathrel}{legacymaths}{58}
2518   \DeclareMathSymbol{;}{\mathpunct}{legacymaths}{59}
2519   \DeclareMathSymbol{?}{\mathclose}{legacymaths}{63}
```

And these ones are defined both in euler and lucbmath, so we only need to run this code if no extra maths package has been loaded.

```
2520 \bool_if:NF \g_@@_math_lucida_bool
2521 {
2522   \DeclareMathSymbol{0}{\mathalpha}{legacymaths}{'0}
2523   \DeclareMathSymbol{1}{\mathalpha}{legacymaths}{'1}
2524   \DeclareMathSymbol{2}{\mathalpha}{legacymaths}{'2}
2525   \DeclareMathSymbol{3}{\mathalpha}{legacymaths}{'3}
2526   \DeclareMathSymbol{4}{\mathalpha}{legacymaths}{'4}
2527   \DeclareMathSymbol{5}{\mathalpha}{legacymaths}{'5}
2528   \DeclareMathSymbol{6}{\mathalpha}{legacymaths}{'6}
2529   \DeclareMathSymbol{7}{\mathalpha}{legacymaths}{'7}
2530   \DeclareMathSymbol{8}{\mathalpha}{legacymaths}{'8}
2531   \DeclareMathSymbol{9}{\mathalpha}{legacymaths}{'9}
2532   \DeclareMathSymbol{\Gamma}{\mathalpha}{legacymaths}{0}
2533   \DeclareMathSymbol{\Delta}{\mathalpha}{legacymaths}{1}
2534   \DeclareMathSymbol{\Theta}{\mathalpha}{legacymaths}{2}
2535   \DeclareMathSymbol{\Lambda}{\mathalpha}{legacymaths}{3}
2536   \DeclareMathSymbol{\Xi}{\mathalpha}{legacymaths}{4}
2537   \DeclareMathSymbol{\Pi}{\mathalpha}{legacymaths}{5}
2538   \DeclareMathSymbol{\Sigma}{\mathalpha}{legacymaths}{6}
2539   \DeclareMathSymbol{\Upsilon}{\mathalpha}{legacymaths}{7}
2540   \DeclareMathSymbol{\Phi}{\mathalpha}{legacymaths}{8}
2541   \DeclareMathSymbol{\Psi}{\mathalpha}{legacymaths}{9}
2542   \DeclareMathSymbol{\Omega}{\mathalpha}{legacymaths}{10}
2543   \DeclareMathSymbol{+}{\mathbin}{legacymaths}{43}
2544   \DeclareMathSymbol{=}{\mathrel}{legacymaths}{61}
2545   \DeclareMathDelimiter{()}{\mathopen}{legacymaths}{40}{largesymbols}{0}
2546   \DeclareMathDelimiter{)}{\mathclose}{legacymaths}{41}{largesymbols}{1}
2547   \DeclareMathDelimiter{[}{\mathopen}{legacymaths}{91}{largesymbols}{2}
2548   \DeclareMathDelimiter{]}{\mathclose}{legacymaths}{93}{largesymbols}{3}
2549   \DeclareMathDelimiter{/}{\mathord}{legacymaths}{47}{largesymbols}{14}
2550   \DeclareMathSymbol{\mathdollar}{\mathord}{legacymaths}{36}
2551 }
2552 }
```

Finally, we change the font definitions for `\mathrm` and so on. These are defined using the `\g_@@_mathrm`tl (...)` macros, which default to `\rmdefault` but may be specified with the `\setmathrm (...)` commands in the preamble.

Since L^AT_EX only generally defines one level of boldness, we omit `\mathbf` in the bold maths series. It can be specified as per usual with `\setboldmathrm`, which

stores the appropriate family name in `\g_@@_bfmathrm_tl`.

```
2553 \DeclareSymbolFont{operators}\g_fontspeg_encoding_tl\g_@@_mathrm_tl\mddefault\updefault
2554 \SetSymbolFont{operators}{normal}\g_fontspeg_encoding_tl\g_@@_mathrm_tl\mddefault\updefault
2555 \DeclareSymbolFontAlphabet\mathrm{operators}
2556 \SetMathAlphabet\mathit{normal}\g_fontspeg_encoding_tl\g_@@_mathrm_tl\mddefault\itdefault
2557 \SetMathAlphabet\mathbf{normal}\g_fontspeg_encoding_tl\g_@@_mathrm_tl\bfdefault\updefault
2558 \SetMathAlphabet\mathsf{normal}\g_fontspeg_encoding_tl\g_@@_mathsf_tl\mddefault\updefault
2559 \SetMathAlphabet\mathtt{normal}\g_fontspeg_encoding_tl\g_@@_mathtt_tl\mddefault\updefault
2560 \SetSymbolFont{operators}{bold}\g_fontspeg_encoding_tl\g_@@_mathrm_tl\bfdefault\updefault
2561 \tl_if_empty:NTF \g_@@_bfmathrm_tl
2562 {
2563   \SetMathAlphabet\mathit{bold}\g_fontspeg_encoding_tl\g_@@_mathrm_tl\bfdefault\itdefault
2564 }
2565 {
2566   \SetMathAlphabet\mathrm{bold}\g_fontspeg_encoding_tl\g_@@_bfmathrm_tl\mddefault\updefault
2567   \SetMathAlphabet\mathbf{bold}\g_fontspeg_encoding_tl\g_@@_bfmathrm_tl\bfdefault\updefault
2568   \SetMathAlphabet\mathit{bold}\g_fontspeg_encoding_tl\g_@@_bfmathrm_tl\mddefault\itdefault
2569 }
2570 \SetMathAlphabet\mathsf{bold}\g_fontspeg_encoding_tl\g_@@_mathsf_tl\bfdefault\updefault
2571 \SetMathAlphabet\mathtt{bold}\g_fontspeg_encoding_tl\g_@@_mathtt_tl\bfdefault\updefault
2572 }
```

`\fontspec_maybe_setup_maths`: We're a little less sophisticated about not executing the maths setup if various other maths font packages are loaded. This list is based on the wonderful 'L^AT_EX Font Catalogue': <http://www.tug.dk/FontCatalogue/mathfonts.html>. I'm sure there are more I've missed. Do the T_EX Gyre fonts have maths support yet?

Untested: would `\unless\ifnum\Gamma=28672\relax\bool_set_false:N \g_@@_math_bool\fi` be a better test? This needs more cooperation with euler and lucida, I think.

```
2573 \cs_new:Nn \fontspec_maybe_setup_maths:
2574 {
2575   \@ifpackageloaded{anttor}
2576   {
2577     \ifx\define@antt@mathversions a\bool_set_false:N \g_@@_math_bool\fi
2578   }{}
2579   \@ifpackageloaded{arevmath}{\bool_set_false:N \g_@@_math_bool}{}
2580   \@ifpackageloaded{eulervm}{\bool_set_false:N \g_@@_math_bool}{}
2581   \@ifpackageloaded{mathdesign}{\bool_set_false:N \g_@@_math_bool}{}
2582   \@ifpackageloaded{concmath}{\bool_set_false:N \g_@@_math_bool}{}
2583   \@ifpackageloaded{cmbright}{\bool_set_false:N \g_@@_math_bool}{}
2584   \@ifpackageloaded{mathesf}{\bool_set_false:N \g_@@_math_bool}{}
2585   \@ifpackageloaded{gfsartemisla}{\bool_set_false:N \g_@@_math_bool}{}
2586   \@ifpackageloaded{gfsneohellenic}{\bool_set_false:N \g_@@_math_bool}{}
2587   \@ifpackageloaded{iwona}
2588   {
2589     \ifx\define@iwona@mathversions a\bool_set_false:N \g_@@_math_bool\fi
2590   }{}
2591   \@ifpackageloaded{kpfonts}{\bool_set_false:N \g_@@_math_bool}{}
2592   \@ifpackageloaded{kmath}{\bool_set_false:N \g_@@_math_bool}{}
2593   \@ifpackageloaded{kurier}
2594   {
2595     \ifx\define@kurier@mathversions a\bool_set_false:N \g_@@_math_bool\fi
```

```

2596   {}
2597   \ifpackageloaded{fouriernc}{\bool_set_false:N \g_@@_math_bool}{}
2598   \ifpackageloaded{fourier}{\bool_set_false:N \g_@@_math_bool}{}
2599   \ifpackageloaded{lmodern}{\bool_set_false:N \g_@@_math_bool}{}
2600   \ifpackageloaded{mathpazo}{\bool_set_false:N \g_@@_math_bool}{}
2601   \ifpackageloaded{mathptmx}{\bool_set_false:N \g_@@_math_bool}{}
2602   \ifpackageloaded{MinionPro}{\bool_set_false:N \g_@@_math_bool}{}
2603   \ifpackageloaded{unicode-math}{\bool_set_false:N \g_@@_math_bool}{}
2604   \ifpackageloaded{breqn}{\bool_set_false:N \g_@@_math_bool}{}
2605   \bool_if:NT \g_@@_math_bool
2606   {
2607     \@@_info:n {setup-math}
2608     \fontspec_setup_maths:
2609   }
2610 }
2611 \AtBeginDocument{\fontspec_maybe_setup_maths:}

```

30 Closing code

30.1 Compatibility

`\zf@enc` Old interfaces. These are needed by, at least, the `mathspec` package.

```

\zf@family 2612 \tl_set:Nn \zf@enc { \g_fontspec_encoding_tl }
\zf@basefont 2613 \cs_set:Npn \zf@fontspec #1 #2
\zf@fontspec 2614 {
2615   \fontspec_select:nn {#1} {#2}
2616   \tl_set:Nn \zf@family { \l_fontspec_family_tl }
2617   \tl_set:Nn \zf@basefont { \l_fontspec_font }
2618 }

```

30.2 Finishing up

Now we just want to set up loading the `.cfg` file, if it exists.

```

2619 \bool_if:NT \g_@@_cfg_bool
2620 {
2621   \InputIfFileExists{fontspec.cfg}
2622   {}
2623   {\typeout{No~ fontspec.cfg~ file~ found;~ no~ configuration~ loaded.}}
2624 }

```

31 Lua module

```

2625 (*lua)

First we define some metadata.
2626 fontspec          = fontspec or {}
2627 local fontspec    = fontspec
2628 fontspec.module   = {
2629   name             = "fontspec",
2630   version          = "2.5a",

```

```

2631   date          = "2016/02/01",
2632   description   = "Advanced font selection for LuaLaTeX.",
2633   author        = "Khaled Hosny, Philipp Gesang, Will Robertson",
2634   copyright     = "Khaled Hosny, Philipp Gesang, Will Robertson",
2635   license       = "LPPL"
2636 }
2637
2638 local err, warn, info, log = luatexbase.provides_module(fontspec.module)

  Some utility functions
2639 fontspec.log      = log or (function (s) luatexbase.module_info("fontspec", s) end)
2640 fontspec.warning = warn or (function (s) luatexbase.module_warning("fontspec", s) end)
2641 fontspec.error   = err or (function (s) luatexbase.module_error("fontspec", s) end)

  The following are the function that get called from TEX end.
2642 local function tempswattrue() tex.sprint([[\\FontspecSetCheckBoolTrue]]) end
2643 local function tempswafalse() tex.sprint([[\\FontspecSetCheckBoolFalse]]) end
2644 function fontspec.check_ot_script(fnt, script)
2645   if luaotfload.aux.provides_script(font.id(fnt), script) then
2646     tempswattrue()
2647   else
2648     tempswafalse()
2649   end
2650 end
2651 function fontspec.check_ot_lang(fnt, lang, script)
2652   if luaotfload.aux.provides_language(font.id(fnt), script, lang) then
2653     tempswattrue()
2654   else
2655     tempswafalse()
2656   end
2657 end
2658 function fontspec.check_ot_feat(fnt, feat, lang, script)
2659   for _, f in ipairs { "+trep", "+tlig", "+anum" } do
2660     if feat == f then
2661       tempswattrue()
2662       return
2663     end
2664   end
2665   if luaotfload.aux.provides_feature(font.id(fnt), script, lang, feat) then
2666     tempswattrue()
2667   else
2668     tempswafalse()
2669   end
2670 end
2671 function fontspec.mathfontdimen(fnt, str)
2672   local mathdimens = luaotfload.aux.get_math_dimension(fnt, str)
2673   if mathdimens then
2674     tex.sprint(mathdimens)
2675     tex.sprint("sp")
2676   else
2677     tex.sprint("0pt")
2678   end

```

```
2679 end
2680 </lua>
```

32 Patching code

```
2681 <*patches>
```

32.1 Italic small caps and so on

`\sishape` These commands for actually selecting italic small caps have been defined for
`\textsi` many years; I'm inclined to drop them. They're probably used very infrequently; I personally prefer just writing `\textit{\textsc{...}}` instead.

```
2682 \providecommand*\itscdefault{\itdefault\scdefault}
2683 \providecommand*\slscdefault{\sldefault\scdefault}
2684 \DeclareRobustCommand{\sishape}
2685 {
2686   \not@math@alphabet\sishape\relax
2687   \fontshape{\itscdefault}\selectfont
2688 }
2689 \DeclareTextFontCommand{\textsi}{\sishape}
```

L^AT_EX's 'shape' font axis needs to be overloaded to support italic small caps and slanted small caps. These are the combinations to support:

```
2690 \cs_new:Nn \@@_shape_merge:nn { c_@@_shape_#1_#2_tl }
2691 \tl_const:cn { \@@_shape_merge:nn \itdefault \scdefault } {\itscdefault}
2692 \tl_const:cn { \@@_shape_merge:nn \sldefault \scdefault } {\slscdefault}
2693 \tl_const:cn { \@@_shape_merge:nn \scdefault \itdefault } {\itscdefault}
2694 \tl_const:cn { \@@_shape_merge:nn \scdefault \sldefault } {\slscdefault}
2695 \tl_const:cn { \@@_shape_merge:nn \slscdefault \itdefault } {\itscdefault}
2696 \tl_const:cn { \@@_shape_merge:nn \itscdefault \sldefault } {\slscdefault}
2697 \tl_const:cn { \@@_shape_merge:nn \itscdefault \updefault } {\scdefault}
2698 \tl_const:cn { \@@_shape_merge:nn \slscdefault \updefault } {\scdefault}
```

`\fontspec_merge_shape:n` These macros enable the overload on the `\..shape` commands. First, a shape 'new+current' (prefix) or 'current+new' (suffix) is tried. If not found, fall back on the 'new' shape.

```
2699 \cs_new:Nn \fontspec_merge_shape:n
2700 {
2701   \bool_if:nTF
2702     {
2703       \tl_if_exist_p:c { \@@_shape_merge:nn {\f@shape} {#1} } &&
2704       \cs_if_exist_p:c
2705         {
2706           \f@encoding/\f@family/\f@series/
2707           \tl_use:c { \@@_shape_merge:nn {\f@shape} {#1} }
2708         }
2709     }
2710     { \fontshape { \tl_use:c { \@@_shape_merge:nn {\f@shape} {#1} } } \selectfont }
2711     { \fontshape {#1} \selectfont }
2712 }
```

`\itshape` The original `\. . shape` commands are redefined to use the merge shape macro.

```
\scshape 2713 \DeclareRobustCommand \itshape
\upshape 2714 {
\slshape 2715 \not@math@alphabet\itshape\mathit
          2716 \fontspec_merge_shape:n\itdefault
          2717 }
          2718 \DeclareRobustCommand \slshape
          2719 {
          2720 \not@math@alphabet\slshape\relax
          2721 \fontspec_merge_shape:n\sldefault
          2722 }
          2723 \DeclareRobustCommand \scshape
          2724 {
          2725 \not@math@alphabet\scshape\relax
          2726 \fontspec_merge_shape:n\scdefault
          2727 }
          2728 \DeclareRobustCommand \upshape
          2729 {
          2730 \not@math@alphabet\upshape\relax
          2731 \fontspec_merge_shape:n\updefault
          2732 }
```

32.2 Emphasis

`\em` Redefinition of `{\em . . .}` and `\emph{. . .}` to allow nesting of emphases.

```
\emph 2733 \int_new:N \l_@@_em_int
\emshape 2734 \int_new:N \l_@@_emdef_int
\emminnershape 2735 \cs_new_protected:Npn \emfontdeclare #1
\emfontdeclare 2736 {
          2737 \int_zero:N \l_@@_emdef_int
          2738 \clist_map_inline:nn {#1}
          2739 {
          2740 \int_incr:N \l_@@_emdef_int
          2741 \cs_set:cpn {@@_em_font_ \int_use:N \l_@@_emdef_int _switch:} {##1}
          2742 }
          2743 }
          2744 \DeclareRobustCommand \em
          2745 {
          2746 \@nomath\em
          2747 \int_incr:N \l_@@_em_int
          2748 \use:c {@@_em_font_ \int_use:N \l_@@_em_int _switch:}
          2749 }
          2750 \DeclareTextFontCommand{\emph}{\em}
          2751 \cs_set:Npn \emshape { \itshape }
          2752 \cs_set:Npn \emminnershape { \upshape }
          2753 \emfontdeclare{ \emshape, \emminnershape }
```

32.3 \-

`\-` This macro is courtesy of Frank Mittelbach and the $\text{\LaTeX}2_{\epsilon}$ source code.

```

2754 \DeclareRobustCommand{\-}
2755 {
2756   \discretionary
2757   {
2758     \char\ifnum\hyphenchar\font<\z@
2759       \xlx@defaulthyphenchar
2760     \else
2761       \hyphenchar\font
2762     \fi
2763   }{}{}
2764 }
2765 \def\xlx@defaulthyphenchar{'\-}

```

32.4 Verbatims

Many thanks to Apostolos Syropoulos for discovering this problem and writing the redefinition of L^AT_EX's `verbatim` environment and `\verb*` command.

`\fontspec_visible_space:` Print U+2434: OPEN BOX, which is used to visibly display a space character.

```

2766 \cs_new:Nn \fontspec_visible_space:
2767 {
2768   \font_glyph_if_exist:NnTF \font {"2423}
2769   { \char"2423\scan_stop: }
2770   { \fontspec_visible_space_fallback: }
2771 }

```

`\fontspec_visible_space:@fallback` If the current font doesn't have U+2434: OPEN BOX, use Latin Modern Mono instead.

```

2772 \cs_new:Nn \fontspec_visible_space_fallback:
2773 {
2774   {
2775     \usefont{\g_fontspec_encoding_tl}{lmtt}{\f@series}{\f@shape}
2776     \textvisiblespace
2777   }
2778 }

```

`\fontspec_print_visible_spaces:` Helper macro to turn spaces (^^20) active and print visible space instead.

```

2779 \group_begin:
2780 \char_set_catcode_active:n{"20}%
2781 \cs_gset:Npn\fontspec_print_visible_spaces:{%
2782 \char_set_catcode_active:n{"20}%
2783 \cs_set_eq:NN^20\fontspec_visible_space:%
2784 }%
2785 \group_end:

```

`\verb` Redefine `\verb` to use `\fontspec_print_visible_spaces:`.

```

\verb* 2786 \def\verb
2787 {
2788   \relax\ifmmode\hbox\else\leavevmode\null\fi
2789   \bgroup
2790   \verb@eol@error \let\do\makeother \dospecials
2791   \verbatim@font\@noligs

```

```

2792 \ifstar\@sverb\@verb
2793 }
2794 \def\@sverb{\fontspec_print_visible_spaces:\@sverb}

```

It's better to put small things into `\AtBeginDocument`, so here we go:

```

2795 \AtBeginDocument
2796 {
2797 \fontspec_patch_verbatim:
2798 \fontspec_patch_moreverb:
2799 \fontspec_patch_fancyvrb:
2800 \fontspec_patch_listings:
2801 }

```

`verbatim*` With the `verbatim` package.

```

2802 \cs_set:Npn \fontspec_patch_verbatim:
2803 {
2804 \ifpackageloaded{verbatim}
2805 {
2806 \cs_set:cpn {verbatim*}
2807 {
2808 \group_begin: \@verbatim \fontspec_print_visible_spaces: \verbatim@start
2809 }
2810 }

```

This is for vanilla \LaTeX .

```

2811 {
2812 \cs_set:cpn {verbatim*}
2813 {
2814 \@verbatim \fontspec_print_visible_spaces: \@sxverbatim
2815 }
2816 }
2817 }

```

`listingcont*` This is for `moreverb`. The main `listing*` environment inherits this definition.

```

2818 \cs_set:Npn \fontspec_patch_moreverb:
2819 {
2820 \ifpackageloaded{moreverb}{
2821 \cs_set:cpn {listingcont*}
2822 {
2823 \cs_set:Npn \verbatim@processline
2824 {
2825 \thelisting@line \global\advance\listing@line\c_one
2826 \the\verbatim@line\par
2827 }
2828 \@verbatim \fontspec_print_visible_spaces: \verbatim@start
2829 }
2830 }{}
2831 }

```

`listings` and `fancyvrb` make things nice and easy:

```

2832 \cs_set:Npn \fontspec_patch_fancyvrb:
2833 {

```

```

2834 \@ifpackageloaded{fancyvrb}
2835 {
2836   \cs_set_eq:NN \FancyVerbSpace \fontspec_visible_space:
2837   }{}
2838 }

2839 \cs_set:Npn \fontspec_patch_listings:
2840 {
2841   \@ifpackageloaded{listings}
2842   {
2843     \cs_set_eq:NN \lst@visiblespace \fontspec_visible_space:
2844     }{}
2845 }

```

32.5 \oldstylenums

`\oldstylenums` This command obviously needs a redefinition. And we may as well provide the
`\liningnums` reverse command.

```

2846 \RenewDocumentCommand \oldstylenums {m}
2847 {
2848   { \addfontfeature{Numbers=OldStyle} #1 }
2849 }
2850 \NewDocumentCommand \liningnums {m}
2851 {
2852   { \addfontfeature{Numbers=Lining} #1 }
2853 }

2854 </patches>

```

33 Error/warning/info messages

2855 < *msg >

Shorthands for messages:

```

2856 \cs_new:Npn \@_error:n { \msg_error:nn {fontspec} }
2857 \cs_new:Npn \@_error:nx { \msg_error:nxx {fontspec} }
2858 \cs_new:Npn \@_warning:n { \msg_warning:nn {fontspec} }
2859 \cs_new:Npn \@_warning:nx { \msg_warning:nxx {fontspec} }
2860 \cs_new:Npn \@_warning:nxx { \msg_warning:nxxx {fontspec} }
2861 \cs_new:Npn \@_info:n { \msg_info:nn {fontspec} }
2862 \cs_new:Npn \@_info:nx { \msg_info:nxx {fontspec} }
2863 \cs_new:Npn \@_info:nxx { \msg_info:nxxx {fontspec} }
2864 \cs_new:Npn \@_trace:n { \msg_trace:nn {fontspec} }

```

33.1 Errors

```

2865 \msg_new:nnn {fontspec} {no-size-info}
2866 {
2867   Size~ information~ must~ be~ supplied.\
2868   For~ example,~ SizeFeatures={Size={8-12},...}.
2869 }
2870 \msg_new:nnnn {fontspec} {font-not-found}

```

```

2871 {
2872 The font "#1" cannot be found.
2873 }
2874 {
2875 A font might not be found for many reasons.\\
2876 Check the spelling, where the font is installed etc. etc.\\ \\
2877 When in doubt, ask someone for help!
2878 }
2879 \msg_new:nnnn {fontspec} {rename-feature-not-exist}
2880 {
2881 The feature #1 doesn't appear to be defined.
2882 }
2883 {
2884 It looks like you're trying to rename a feature that doesn't exist.
2885 }
2886 \msg_new:nnn {fontspec} {no-glyph}
2887 {
2888 '\l_fontspec_fontname_tl' does not contain glyph #1.
2889 }
2890 \msg_new:nnnn {fontspec} {euler-too-late}
2891 {
2892 The euler package must be loaded BEFORE fontspec.
2893 }
2894 {
2895 fontspec only overwrites euler's attempt to
2896 define the maths text fonts if fontspec is
2897 loaded after euler. Type <return> to proceed
2898 with incorrect \string\mathit, \string\mathbf, etc.
2899 }
2900 \msg_new:nnnn {fontspec} {no-xcolor}
2901 {
2902 Cannot load named colours without the xcolor package.
2903 }
2904 {
2905 Sorry, I can't do anything to help. Instead of loading
2906 the color package, use xcolor instead. It's better.
2907 }
2908 \msg_new:nnnn {fontspec} {unknown-color-model}
2909 {
2910 Error loading colour '#1'; unknown colour model.
2911 }
2912 {
2913 Sorry, I can't do anything to help. Please report this error
2914 to my developer with a minimal example that causes the problem.
2915 }
2916 \msg_new:nnnn {fontspec} {not-in-addfontfeatures}
2917 {
2918 The "#1" font feature cannot be used in \string\addfontfeatures.
2919 }
2920 {
2921 This is due to how TeX loads fonts; such settings

```

```

2922 are~ global~ so~ adding~ them~ mid-document~ within~ a~ group~ causes~
2923 confusion.~ You'll~ need~ to~ define~ multiple~ font~ families~ to~ achieve~
2924 what~ you~ want.
2925 }

```

33.2 Warnings

```

2926 \msg_new:nnn {fontspec} {addfontfeatures-ignored}
2927 {
2928   \string\addfontfeature (s)~ ignored~ \msg_line_context:;~
2929   it~ cannot~ be~ used~ with~ a~ font~ that~ wasn't~ selected~ by~ a~ fontspec~ command.\\
2930   \\
2931   The~ current~ font~ is~ "\use:c{font@name}".\\
2932   \int_compare:nTF { \clist_count:n {#1} = 1 }
2933     { The~ requested~ feature~ is~ "#1". }
2934     { The~ requested~ features~ are~ "#1". }
2935 }
2936 \msg_new:nnn {fontspec} {feature-option-overwrite}
2937 {
2938   Option~ '#2'~ of~ font~ feature~ '#1'~ overwritten.
2939 }
2940 \msg_new:nnn {fontspec} {script-not-exist-latn}
2941 {
2942   Font~ '\l_fontspec_fontname_tl'~ does~ not~ contain~ script~ '#1'.\\
2943   'Latin'~ script~ used~ instead.
2944 }
2945 \msg_new:nnn {fontspec} {script-not-exist}
2946 {
2947   Font~ '\l_fontspec_fontname_tl'~ does~ not~ contain~ script~ '#1'.
2948 }
2949 \msg_new:nnn {fontspec} {aat-feature-not-exist}
2950 {
2951   '\l_keys_key_tl=\l_keys_value_tl'~ feature~ not~ supported~
2952   for~ AAT~ font~ '\l_fontspec_fontname_tl'.
2953 }
2954 \msg_new:nnn {fontspec} {aat-feature-not-exist-in-font}
2955 {
2956   AAT~ feature~ '\l_keys_key_tl=\l_keys_value_tl'~ (#1)~ not~ available~
2957   in~ font~ '\l_fontspec_fontname_tl'.
2958 }
2959 \msg_new:nnn {fontspec} {icu-feature-not-exist}
2960 {
2961   '\l_keys_key_tl=\l_keys_value_tl'~ feature~ not~ supported~
2962   for~ OpenType~ font~ '\l_fontspec_fontname_tl'
2963 }
2964 \msg_new:nnn {fontspec} {icu-feature-not-exist-in-font}
2965 {
2966   OpenType~ feature~ '\l_keys_key_tl=\l_keys_value_tl'~ (#1)~ not~ available~
2967   for~ font~ '\l_fontspec_fontname_tl'~
2968   with~ script~ '\l_@@_script_name_tl'~ and~ language~ '\l_@@_lang_name_tl'.
2969 }
2970 \msg_new:nnn {fontspec} {no-opticals}

```

```

2971 {
2972 '\l_fontspec_fontname_tl'~ doesn't~ appear~ to~ have~ an~ Optical~ Size~ axis.
2973 }
2974 \msg_new:nnn {fontspec} {language-not-exist}
2975 {
2976 Language~ '#1'~ not~ available~
2977 for~ font~ '\l_fontspec_fontname_tl'~
2978 with~ script~ '\l_@_script_name_tl'.\
2979 'Default'~ language~ used~ instead.
2980 }
2981 \msg_new:nnn {fontspec} {only-xetex-feature}
2982 {
2983 Ignored~ XeTeX~ only~ feature:~ '#1'.
2984 }
2985 \msg_new:nnn {fontspec} {only-luatex-feature}
2986 {
2987 Ignored~ LuaTeX~ only~ feature:~ '#1'.
2988 }
2989 \msg_new:nnn {fontspec} {no-mapping}
2990 {
2991 Input~ mapping~ not~ (yet?)~ supported~ in~ LuaTeX.
2992 }
2993 \msg_new:nnn {fontspec} {no-mapping-ligtext}
2994 {
2995 Input~ mapping~ not~ (yet?)~ supported~ in~ LuaTeX.\
2996 Use~ "Ligatures=TeX"~ instead~ of~ "Mapping=tex-text".
2997 }
2998 \msg_new:nnn {fontspec} {cm-default-obsolete}
2999 {
3000 The~ "cm-default"~ package~ option~ is~ obsolete.
3001 }
3002 \msg_new:nnn {fontspec} {fakebold-only-xetex}
3003 {
3004 The~ "FakeBold"~ and~ "AutoFakeBold"~ options~ are~ only~ available~ with~ XeLaTeX.\
3005 Option~ ignored.
3006 }

```

Info messages:

```

3007 \msg_new:nnn {fontspec} {defining-font}
3008 {
3009 Font~ family~'\l_fontspec_family_tl'~ created~ for~ font~ '#2'~
3010 with~ options~ [\l_@_all_features_clist].\
3011 \
3012 This~ font~ family~ consists~ of~ the~ following~ NFSS~ series/shapes:\
3013 \l_fontspec_defined_shapes_tl
3014 }
3015 \msg_new:nnn {fontspec} {no-font-shape}
3016 {
3017 Could~ not~ resolve~ font~ #1~ (it~ probably~ doesn't~ exist).
3018 }
3019 \msg_new:nnn {fontspec} {set-scale}
3020 {

```

```

3021 \l_fontspec_fontname_tl\space scale ~= \l_@_scale_tl.
3022 }
3023 \msg_new:nnn {fontspec} {setup-math}
3024 {
3025 Adjusting~ the~ maths~ setup~ (use~ [no-math]~ to~ avoid~ this).
3026 }
3027 \msg_new:nnn {fontspec} {no-scripts}
3028 {
3029 Font~ \l_fontspec_fontname_tl\space does~ not~ contain~ any~ OpenType~ 'Script'~ information.
3030 }
3031 \msg_new:nnn {fontspec} {opa-twice}
3032 {
3033 Opacity~ set~ twice,~ in~ both~ Colour~ and~ Opacity.\
3034 Using~ specification~ "Opacity=#1".
3035 }
3036 \msg_new:nnn {fontspec} {opa-twice-col}
3037 {
3038 Opacity~ set~ twice,~ in~ both~ Opacity~ and~ Colour.\
3039 Using~ an~ opacity~ specification~ in~ hex~ of~ "#1/FF".
3040 }
3041 \msg_new:nnn {fontspec} {bad-colour}
3042 {
3043 Bad~ colour~ declaration~ "#1".~
3044 Colour~ must~ be~ one~ of:\
3045 *~ a~ named~ xcolor~ colour\
3046 *~ a~ six-digit~ hex~ colour~ RRGGBB\
3047 *~ an~ eight-digit~ hex~ colour~ RRGGBBTT~ with~ opacity
3048 }
3049 \msg

```