

The `getfiledate` Package

Version 1.0

Ahmed Musa
University of Central Lancashire
Preston, United Kingdom
a.musa@rocketmail.com

August 7, 2009

Contents		3 Examples	3
1 User interface	1	4 Postamble	8
2 Package options	2		

Summary

The `getfiledate` package fetches from the system the date of last modification or opening of a resident file. It is based on an idea by Heiko Oberdiek <oberdiek@uni-freiburg.de> that appeared in February 2009 on the discussion/newsgroup website comp.text.tex, namely, using the `\pdffilemoddate` command of pdfTeX. This package creates a user-friendly interface for obtaining and presenting the needed filedate in several formats.

1 User interface

The package may be loaded without options as in

```
1 \usepackage{getfiledate}
```

or with options as in

```
2 \usepackage[option=value]{getfiledate}
```

The options include the filename for which you want to print the date of last modification. The options and their default values are described in section 2. It is advisable to first load the package by `\usepackage{getfiledate}` and then use the macro

`\getfiledate` to dynamically determine and print the date of last modification of the filename. This macro sets the various options.

2 Package options

The package options are listed in Table 1 below.

Table 1: Package options

Option	Default	Meaning
<code>file</code>	<code>getfiledate.sty</code>	The file for which the date of last modification is required.
<code>prefix</code>	The date of last modification of file	The prefix of filename.
<code>postfix</code>	<code>was</code>	The postfix of filename, not that of filedate. It has been necessary to provide both prefix and postfix following user requests.
<code>width</code>	<code>\hsize</code>	The width of the parbox or boxedminipage containing the filedate.
<code>head</code>	<code>0ex</code>	The vertical separation between the paragraph before the filedate and the filedate itself. When this option is passed to package without value, its default becomes the <code>\baselineskip</code> .
<code>foot</code>	<code>0ex</code>	The vertical skip between the filedate's line and the paragraph after filedate. When this option is passed to package without value, its default becomes the <code>\baselineskip</code> .
<code>marker</code>	<code>\blacktriangle-right</code>	The mark before the filename, on the same line with the filedate.
<code>markercolor</code>	<code>blue</code>	The color of the marker.
<code>filenamecolor</code>	<code>blue</code>	The color of the filename.
<code>datecolor</code>	<code>blue</code>	The color of filedate.
<code>inlinespace</code>	<code>1em</code>	The horizontal separation between the marker and the filedate.
<code>separator</code>	<code>\textbullet</code>	The marker between the filedate and filetime.
<code>separatorcolor</code>	<code>black</code>	The color of the separator.
<code>framecolor</code>	<code>black</code>	The color of the boxrule for the boxedminipage.
<code>framesep</code>	<code>3pt</code>	The <code>\fboxsep</code> for the boxedminipage.
<code>framerule</code>	<code>0.4pt</code>	The <code>\fboxrule</code> for the boxedminipage.
<code>align</code>	<code>justified</code>	Alignment of the boxedminipage (possible values are <code>center</code> , <code>left</code> , <code>right</code> and <code>justified</code>).

Continued on next page

Continued from last page		
Option	Default	Meaning
putprefix	false	The boolean switch for placing prefix and postfix before the filedate. If this option is not entered in the call to <code>\getfiledate</code> , no prefix and no postfix will be inserted (even if the user specifies prefix and postfix in the call to <code>\getfiledate</code>). This option has been necessitated by users who just want to get filedate without any prefix, postfix or filename.
notime	false	The boolean switch for turning the display of time on or off.
boxed	false	The boolean switch for enclosing the filedate in a box. If the user simply enters this option without value, it will be assumed to be <code>true</code> . If it doesn't appear in the options list, its value is <code>false</code> .

3 Examples

Example 3.1

The simplest example is to use the `\getfiledate` macro in the following way:

```
3 \getfiledate[putprefix]{dir/filename.ext}
```

for which the default values of the package options will be used. For the sample file `misc-test1.tex`, the outcome of this will be:

► The date of last modification of file `misc-test1.tex` was 2008-12-10 • 20:21:14.

The prefix and postfix can be turned off as follows:

```
4 \getfiledate[putprefix=false]{dir/filename.ext}
```

which gives

2008-12-10 • 20:21:14.

If the user needs the prefix and postfix in subsequent calls to `\getfiledate`, he has to turn them on again—through `putprefix` as follows. Once turned on, they remain in effect until switched off later.

```
5 \getfiledate[putprefix,marker={${\star$}}]{dir/filename.ext}
```

which gives

★ The date of last modification of file `misc-test1.tex` was 2008-12-10 • 20:21:14.

The ability to change both the prefix and postfix automatically provides a `babel` (i.e., multilingual) support. For example, if I want the postfix to be `\mrule`, I can simply enter

```
6 \new\def\mrule{\rule[.5ex]{1cm}{2pt}}
7 \getfiledate[putprefix,marker={$\star$},
8   postfix=\mrule]{dir/filename.ext}
```

to get

★ The date of last modification of file `misc-test1.tex` — 2008-12-10 • 20:21:14.

You can use all package options to customize the format of the result. The following examples illustrate the most important issues in using this package.

Example 3.2

The example in this section was obtained with the following settings. There are values specified for `head` and `foot`.

```
9 \getfiledate[putprefix,postfix,head=.1\baselineskip,
10   foot=2\baselineskip,markercolor=magenta,
11   filenamecolor=purple,datecolor=orange,
12   inlinespace=.5em,marker=$\blacktriangleright$,separator
13 ]{misc-test1.tex}
```

The outcome of this is

► The date of last modification of file `misc-test1.tex` was 2008-12-10 • 20:21:14.

If you don't need the `marker`, you can set `marker={}` as follows

```
14 \getfiledate[head=\baselineskip,
15   foot=\baselineskip,width=.6\hsize,filenamecolor=xgreen10,
16   prefix=The date of final changes to file,
17   datecolor=orange,inlinespace=.5em,boxed=false,
18   separator=$\spadesuit$,separatorcolor=green,
19   marker={},align=center
20 ]{misc-test1.tex}
```

to get

The date of final changes to file `misc-test1.tex` was
2008-12-10 ♠ 20:21:14.

The same trick can be applied to other keys. If you simply remove `marker` from the key-value list, the `marker` will retain the last value you assigned to it rather than the default value (which is `nil`).

The user should note the following:

- The inclusion of the `width (=0.6\hsize)` in the above example. The `width` will maintain this value until it is changed again, as in the following examples.
- The assignment to keys can be localized by enclosing the `\getfiledate` command in a group (e.g., `\bgroup ... \egroup`).
- The change of `prefix` here. The default value of `prefix` is `The date of last modification of file`. The `prefix` will maintain this value until it is changed in the next call (see the next example).
- The ability to change the `prefix` and `postfix` provides a babel (i.e., multi-lingual) support, since the user can specify suitable values of these keys.
- The use of the key-value `align=center` above. The key `align` can assume values of `center`, `left`, `right`, and `justified`. Any other value for `align` will be rejected by the package.
- Some of the package options (e.g., `notime`) can be submitted via the options list of `\documentclass`.

Example 3.3

The example in this section was obtained with the following settings:

```
21 \getfiledate[head=0ex,foot=\baselineskip,
22   prefix,width=\hsize,markercolor=magenta,filenamecolor=red,
23   datecolor=violet,inlinespace=.5em,marker=$\triangleright$,
24   separator=$\clubsuit$,separatorcolor=xbgreen1
25 ]{misc-test2.tex}
```

The outcome is:

▷ The date of last modification of file `misc-test2.tex` was 2008-11-03 ♣ 16:58:16.

Here we simply passed the `prefix` without value so that its default value was used.

Example 3.4

The example in this section was obtained with the following settings:

```
26 \getfiledate[head=\baselineskip,foot=2\baselineskip,
27   markercolor=red!65,filenamecolor=blue,
28   datecolor=orange,inlinespace=.5em,marker={\star},
29   separator=$\Diamond$,separatorcolor=red
30 ]{misc-test3.tex}
```

The outcome is:

- ★ The date of last modification of file `misc-test3.tex` was 2009-07-05 ◇ 15:55:48.

Example 3.5

The example in this section was obtained with the following settings:

```

31 \getfiledate[head=\baselineskip,foot=2ex,
32   markercolor=cyan,filenamecolor=blue,datecolor=orange,
33   inlinespace=.5em,marker={\blacktriangleright},
34   markercolor=cyan,separator=$\heartsuit$,separatorcolor
35 ]{misc-test4.tex} % Use default separatorcolor

```

The outcome is:

- The date of last modification of file `misc-test4.tex` was 2009-07-05 ♥ 15:56:36.

Example 3.6

The example in this section was obtained with the following settings:

```

36 \getfiledate[head=1ex,foot=1ex,
37   markercolor=purple,filenamecolor=blue,
38   datecolor=orange,inlinespace=.5em,
39   marker={\blacktriangleright},separator={}
40 ]{misc-test5.tex} % The separator is nil here.

```

The outcome of this is:

- The date of last modification of file `misc-test5.tex` was 2009-04-25 04:38:14.

Example 3.7

Instead of keeping `head` and `foot`, you may instead decide to frame your result, as follows:

```

41 \getfiledate[head=.5\baselineskip,
42   foot=.5\baselineskip,width=12.5cm,framesep=5pt,framerule=.4pt,
43   align=center,markercolor=purple,filenamecolor=blue,
44   datecolor=orange,marker={\blacktriangleright},
45   separator=$\heartsuit$,boxed
46 ]{misc-test5.tex} % marker has no effect here.

```

The outcome is:

The date of last modification of file `misc-test5.tex` was 2009-04-25 ♡ 04:38:14.

The boolean option `boxed` has the default value of `true` when listed in the key-value list. If you set the key `boxed(=true)` in one call to the `\getfiledate` macro, and you don't want the filedate to be boxed subsequently, you have to turn it off (i.e., enter `boxed=false`) in the next call to `\getfiledate`. The choice `boxed(=true)` automatically turns off `marker` irrespective of whether or not you have submitted a value to this key in `\getfiledate` macro. In the above example, the reader will notice that the setting `marker=\blacktriangleright` has no effect on the outcome.

For the boxed filedates, you can set the options `framesep` and `framerule` (equivalents of L^AT_EX's native `\fboxsep` and `\fboxrule`) as follows:

```
47 \getfiledate[head=\baselineskip,
48   foot=1ex,marker={$\blacktriangleright$},markercolor=purple,
49   filenamecolor=blue,width=.9\hsize,datecolor=orange,
50   inlinespace=.5em,align=left,boxed,separator={$\blacklozenge$},
51   framesep=5pt,framerule=2pt
52 ]{misc-test5.tex} % marker has no effect here.
```

The outcome of this is:

The date of last modification of file `misc-test5.tex` was 2009-04-25 ◆ 04:38:14.

The default values of `framesep` and `framerule` are 3pt and 0.4pt (L^AT_EX's native values for `\fboxsep` and `\fboxrule`). The user should note that the keys `framesep` and `framerule` should, of course, be submitted without backslashes (e.g., `framesep=5pt` and `framerule=2pt`).

You can change the box frame color as in

```
53 \getfiledate[head=\baselineskip,
54   foot=\baselineskip,markercolor=purple,filenamecolor=blue,
55   datecolor=orange,width=8cm,align=right,boxed,framesep=5pt,
56   framerule=2pt,separator={$\Diamond$},framecolor=green
57 ]{misc-test5.tex}
```

The outcome of this is:

The date of last modification of file `misc-test5.tex` was 2009-04-25 ◇ 04:38:14.

This frame color will remain in force until it is changed again. The default value of

`framecolor` is `black`.

Example 3.8

The display of time can be avoided by using the switch `notime`, as follows.

```
58 \getfiledate[notime,head=\baselineskip,foot=1ex,  
59   markercolor=purple,filenamecolor=blue,datecolor=orange,  
60   inlinespace=.5em,marker={\blacktriangleright},width=.8\hsize,  
61   align=center,boxed,framecolor=olive!25  
62 ]{misc-test5.tex}
```

The outcome of this is:

The date of last modification of file `misc-test5.tex` was `2009-04-25`.

Notice here that the immediate past values of `framerule` and `framesep` are still in effect.

4 Postamble

The record of filedates can be logged in a file (say, `\jobname.fds`), but I haven't encountered a real need for it.