

glossaries-extra.sty v1.06: an extension to the glossaries package

Nicola L.C. Talbot

Dickimaw Books

<http://www.dickimaw-books.com/>

2016-06-18

Abstract

The glossaries-extra package is an extension to the glossaries package, providing additional features. Some of the features provided by this package are only available with glossaries version 4.19 (or above). This document assumes familiarity with the glossaries package.

Since glossaries-extra internally loads the glossaries package, you also need to have glossaries installed and all the packages that glossaries depends on (including, but not limited to, tracklang, mfirstuc, etoolbox, xkeyval (at least version dated 2006/11/18), textcase, xfor, datatool-base and amsgen. These packages are all available in the current TeX Live and MikTeX distributions. If any of them are missing, please update your TeX distribution using your update manager. (For help on this see, for example, [How do I update my TeX distribution?](#) or [Updating TeX on Linux](#).)

Contents

1	Introduction	4
1.1	Package Defaults	4
1.2	New or Modified Package Options	7
2	Modifications to Existing Commands and Styles	12
2.1	Entry Indexing	12
2.2	Entry Display Style Modifications	14
2.3	Entry Counting Modifications	17
2.4	Nested Links	18
2.5	Acronym Style Modifications	22
2.6	Glossary Style Modifications	22
2.6.1	Style Hooks	23
2.6.2	Number List	24
2.6.3	The <code>glossaries-extra-stylemods</code> Package	25
3	Abbreviations	29
3.1	Tagging Initials	32
3.2	Abbreviation Styles	33
3.3	Shortcut Commands	36
3.4	Predefined Abbreviation Styles	37
3.4.1	Predefined Abbreviation Styles that Set the Regular Attribute	40
3.4.2	Predefined Abbreviation Styles that Don't Set the Regular Attribute	42
3.5	Defining New Abbreviation Styles	46
4	Entries in Sectioning Titles, Headers, Captions and Contents	53
5	Categories	58
6	Entry Counting	65
7	Auto-Indexing	72
8	On-the-Fly Document Definitions	74
9	Supplemental Packages	76
9.1	Prefixes or Determiners	76
9.2	Accessibility Support	76
10	Sample Files	81

11 Multi-Lingual Support	83
Glossary	87
Index	88

1 Introduction

The glossaries package is a flexible package, but it's also a heavy-weight package that uses a lot of resources. As package developer, I'm caught between those users who complain about the drawbacks of a heavy-weight package with a large user manual and those users who want more features (which necessarily adds to the package weight and manual size).

The glossaries-extra package is an attempt to provide a compromise for this conflict. Version 4.22 of the glossaries package is the last version to incorporate new features.¹ Future versions of glossaries will just be bug fixes. New features will instead be added to glossaries-extra. This means that the base glossaries package won't increase in terms of package loading time and allocation of resources, but those users who do want extra features available will have more of a chance of getting their feature requests accepted.

1.1 Package Defaults

I'm not happy with some of the default settings assumed by the glossaries package, and, judging from code I've seen, other users also seem unhappy with them, as certain package options are often used in questions posted on various sites. I can't change the default behaviour of glossaries as it would break backward compatibility, but since glossaries-extra is a separate package, I have decided to implement some of these commonly-used options by default. You can switch them back if they're not appropriate.

The new defaults are:

- `toc=true` (add the glossaries to the table of contents). Use `toc=false` to switch this back off.
- `nopostdot=true` (suppress the terminating full stop after the description in the glossary). Use `nopostdot=false` to restore the terminating full stop (period).
- `noredefwarn=true` (suppress the warnings that occur when the `\glossary` environment and `\printglossary` are redefined while glossaries is loading). To restore the warnings, use `noredefwarn=false`. Note that this won't have any effect if the glossaries package has already been loaded before you use the glossaries-extra package.
- If `babel` has been loaded, the `translate=babel` option is switched on. To revert to using the translator interface, use `translate=true`. There is no change to the default if `babel` hasn't been loaded.

¹4.21 was originally intended as the last release of glossaries to incorporate new features, but a few new minor features slipped in with some bug fixes in v4.21.

Examples:

1. \documentclass{article}
 \usepackage{glossaries-extra}

This is like:

```
\documentclass{article}
\usepackage[toc,nopostdot]{glossaries}
\usepackage{glossaries-extra}
```

2. \documentclass[british]{article}
 \usepackage{babel}
 \usepackage{glossaries-extra}

This is like:

```
\documentclass[british]{article}
\usepackage{babel}
\usepackage[toc,nopostdot,translate=babel]{glossaries}
\usepackage{glossaries-extra}
```

3. \documentclass{memoir}
 \usepackage{glossaries-extra}

This is like:

```
\documentclass{memoir}
\usepackage[toc,nopostdot,noredefwarn]{glossaries}
\usepackage{glossaries-extra}
```

However

```
\documentclass{memoir}
\usepackage{glossaries}
\usepackage{glossaries-extra}
```

This is like:

```
\documentclass{memoir}
\usepackage[toc,nopostdot]{glossaries}
\usepackage{glossaries-extra}
```

Since by the time glossaries-extra has been loaded, glossaries has already redefined memoir's glossary-related commands.

Another noticeable change is that by default \printglossary will now display information text in the document if the external glossary file doesn't exist. This is explanatory text to help new users who can't work out what to do next to complete the document build. Once

the document is set up correctly and the external files have been generated, this text will disappear.

This change is mostly likely to be noticed by users with one or more redundant empty glossaries who ignore transcript messages, explicitly use `makeindex/xindy` on just the non-empty glossary (or glossaries) and use the iterative `\printglossaries` command instead of `\printglossary`. For example, consider the following:

```
\documentclass{article}

\usepackage[acronym]{glossaries}

\makeglossaries

\newacronym{laser}{laser}{light amplification by stimulated emission of radiation}

\begin{document}

\gls{laser}

\printglossaries

\end{document}
```

The above document will only display the list of acronyms at the place where `\printglossaries` occurs. However it will also attempt to input the `.gls` file associated with the main glossary.

If you use `makeglossaries`, you'll get the warning message:

```
Warning: File 'test.glo' is empty.
Have you used any entries defined in glossary 'main'?
Remember to use package option 'nomain' if you
don't want to use the main glossary.
```

(where the original file is called `test.tex`) but if you simply call `makeindex` directly to generate the `.acr` file (without attempting to create the `.gls` file) then the transcript file will always contain the message:

```
No file test.gls.
```

This doesn't occur with `makeglossaries` as it will create the `.gls` file containing the single command `\null`.

If you simply change from `glossaries` to `glossaries-extra` in this document, you'll find a change in the resulting PDF if you don't use `makeglossaries` and you only generate the `.acr` file with `makeindex`.

The transcript file will still contain the message about the missing `.gls`, but now you'll also see information in the actual PDF document. The simplest remedy is to follow the advice inserted into the document at that point, which is to add the `nomain` package option:

```
\documentclass{article}
```

```
\usepackage[nomain,acronym]{glossaries-extra}

\makeglossaries

\newacronym{laser}{laser}{light amplification by stimulated
emission of radiation}

\begin{document}

\gls{laser}

\printglossaries

\end{document}
```

1.2 New or Modified Package Options

If you haven't already loaded glossaries, you can use any of the package options provided by glossaries when you load glossaries-extra and they will automatically be passed to glossaries (which glossaries-extra will load). If glossaries has already been loaded, then those options will be passed to \setupglossaries, but remember that not all of the glossaries package options may be used in that command.

This section only lists options that are either unrecognised by the glossaries package or are a modified version of options of the same name provided by glossaries. See the glossaries user manual for details about the unmodified options.

The new and modified options provided by glossaries-extra are described below:

accsupp Load the glossaries-accsupp package (if not already loaded).

If you want to define styles that can interface with the accessibility support provided by glossaries-accsupp use the \glsaccess<xxx> type of commands instead of \glsentry<xxx> (for example, \glsaccesstext instead of \glsentrytext). If glossaries-accsupp hasn't been loaded those commands are equivalent (for example, \glsaccesstext just does \glsentrytext) but if it has been loaded, then the \glsaccess<xxx> commands will add the accessibility information. (See Section 9.2 for further details.)

Note that the accsupp option can only be used as a package option (not through \glossariesextrasetup) since the glossaries-accsupp package must be loaded before glossaries-extra if it's required.

stylemods This is a <key>=<value> option used to load the glossaries-extra-stylemods package. The value may be a comma-separated list of options to pass to that package. (Remem-

ber to group $\langle value \rangle$ if it contains any commas.) The value may be omitted if no options need to be passed. See Section 2.6 for further details.

undefaction This is a $\langle key \rangle=\langle value \rangle$ option, which has two allowed values: warn and error.

This indicates what to do if an undefined glossary entry is referenced. The default behaviour is undefaction=error, which produces an error message (the default for glossaries). You can switch this to a warning message (and ?? appearing in the text) with undefaction=warn.

docdef This option governs the use of `\newglossaryentry`. It was originally a boolean option, but as from version 1.06, it can now take one of three values (if the value is omitted, true is assumed):

`docdef=false` `\newglossaryentry` is not permitted in the document environment (default).

`docdef=true` `\newglossaryentry` behaves as it does in the base glossaries package. That is, where its use is permitted in the document environment, it uses the `.glsdefs` temporary file to store the entry definitions so that on the next L^AT_EX run the entries are defined at the beginning of the document environment. This allows the entry information to be referenced in the glossary, even if the glossary occurs before `\newglossaryentry`. (For example, when the glossary is displayed in the front matter.) This method of saving the definitions for the next L^AT_EX run has drawbacks that are detailed in the glossaries user manual.

`docdef=restricted` (new to version 1.06) `\newglossaryentry` is permitted in the document environment without using the `.glsdefs` file. This means that all entries must be defined before the glossary is displayed, but it avoids the complications associated with saving the entry details in a temporary file. You will still need to take care about any changes made to characters that are required by the $\langle key \rangle=\langle value \rangle$ mechanism (that is, the comma and equal sign) and any `makeindex` or `xindy` character that occurs in the sort key or label. If any of those characters are made active in the document, then it can cause problems with the entry definition. This option will allow `\newglossaryentry` to be used in the document with `\makenoidxglossaries`, but note that `\longnewglossaryentry` remains a preamble-only command.

With this option, if an entry appears in the glossary before it has been defined, an error will occur (or a warning if the `undefaction=warn` option is used.) If you edit your document and either remove an entry or change its label, you may need to delete the document's temporary files (such as the `.aux` and `.gls` files).

The glossaries package allows `\newglossaryentry` within the document environment (when used with `makeindex` or `xindy`) but the user manual warns against this usage. By default the glossaries-extra package *prohibits* this, only allowing definitions within the preamble. If you are really determined to define entries in the document environment, despite all the associated drawbacks, you can restore this with `docdef=true`. Note that this doesn't change the prohibitions that the glossaries package has in certain circumstances (for example, when using "option 1"). See the glossaries user manual for further

details. A better option if document definitions are required is `docdef=restricted`. Only use `docdef=true` if document definitions are necessary and one or more of the glossaries occurs in the front matter.

This option affects commands that internally use `\newglossaryentry`, such as `\newabbreviation`, but not the “on-the-fly” commands described in Section 8.

nomissingglostext This is a boolean option. If true, this will suppress the warning text that will appear in the document if the external glossary files haven’t been generated due to an incomplete document build. However, it’s probably simpler just to fix whatever has caused the failure to build the external file or files.

indexcrossrefs This is a boolean option. If true, this will automatically index any cross-referenced entries that haven’t been marked as used at the end of the document. Note that this necessarily adds to the overall document build time, especially if you have defined a large number of entries, so this defaults to false, but it will be automatically switched on if you use the `see` key in any entries. To force it off, even if you use the `see`, you need to explicitly set `indexcrossrefs` to false.

abbreviations This option has no value and can’t be cancelled. If used, it will automatically create a new glossary with the label `abbreviations` and redefines `\glsxtrabbrvtype` to this label. In addition, it defines a shortcut command

```
\printabbreviations
```

`\printabbreviations[<options>]`

which is equivalent to

```
\printglossary[type=\glsxtrabbrvtype,<options>]
```

The title of the new glossary is given by

```
\abbreviationsname
```

`\abbreviationsname`

If this command is already defined, it’s left unchanged. Otherwise it’s defined to “Abbreviations” if babel hasn’t been loaded or `\acronymname` if babel has been loaded. However, if you’re using babel it’s likely you will need to change this. (See Section 11 for further details.)

If you don’t use the abbreviations package option, the `\abbreviationsname` command won’t be defined (unless it’s defined by an included language file).

If the `abbreviations` option is used and the `acronym` option provided by the `glossaries` package hasn't been used, then `\acronymtype` will be set to `\glsxtrabbrvtype` so that acronyms defined with `\newacronym` can be added to the list of abbreviations. If you want acronyms in the `main` glossary and other abbreviations in the `abbreviations` glossary then you will need to redefine `\acronymtype` to `main`:

```
\renewcommand*\acronymtype{main}
```

Note that there are no analogous options to the `glossaries` package's `acronymlists` option (or associated commands) as the abbreviation mechanism is handled differently with `glossaries-extra`.

symbols This is passed to `glossaries` but will additionally define

```
\glsxtrnewsymbol
```

```
\glsxtrnewsymbol[<options>]{<label>}{<symbol>}
```

which is equivalent to

```
\newglossaryentry{<label>}{name={<symbol>},  
sort={<label>},type=symbols,category=symbol,<options>}
```

Note that the `sort` key is set to the `<label>` not the `<symbol>` as the symbol will likely contain commands.

numbers This is passed to `glossaries` but will additionally define

```
\glsxtrnewnumber
```

```
\glsxtrnewnumber[<options>]{<number>}
```

which is equivalent to

```
\newglossaryentry{<label>}{name={<number>},  
sort={<label>},type=numbers,category=number,<options>}
```

shortcuts Unlike the `glossaries` package option of the same name, this option isn't boolean but has multiple values:

- `shortcuts=acronyms` (or `shortcuts=acro`): set the shortcuts provided by the `glossaries` package for acronyms (such as `\ac`).
- `shortcuts=abbreviations` (or `shortcuts=abbr`): set the abbreviation shortcuts provided by `glossaries-extra`. (See Section 3.3.) These settings don't switch on the acronym shortcuts provided by the `glossaries` package.

- `shortcuts=other`: set the “other” shortcut commands, but not the shortcut commands for abbreviations or the acronym shortcuts provided by glossaries. The “other” shortcuts are:
 - `\newentry` equivalent to `\newglossaryentry`
 - `\newsym` equivalent to `\glsxtrnewsymbol` (see the `symbols` option).
 - `\newnum` equivalent to `\glsxtrnewnumber` (see the `numbers` option).
- `shortcuts=all` (or `shortcuts=true`): define all the shortcut commands.
- `shortcuts=none` (or `shortcuts=false`): don’t define any of the shortcut commands (default).

Note that multiple invocations of the `shortcuts` option *within the same option list* will override each other.

After the `glossaries-extra` package has been loaded, you can set available options using

```
\glossariesextrasetup
  \glossariesextrasetup{\{options\}}
```

The abbreviations and docdef options may only be used in the preamble. Additionally, docdef can’t be used after `\makenoidxglossaries`.

2 Modifications to Existing Commands and Styles

The commands used by glossaries to automatically produce an error if an entry is undefined (such as `\glsdoifexists`) are changed to take the `undefaction` option into account.

The `\newglossaryentry` command has a new key called `category`, which sets the category label for the given entry. By default this is `general`. See Section 5 for further information about categories.

The `\newterm` command (defined through the `index` package option) is modified so that the category defaults to `index`. The `\newacronym` command is modified to use the new abbreviation interface provided by `glossaries-extra`. (See Section 3.)

2.1 Entry Indexing

The `glossaries-extra` package provides an extra key for commands like `\gls` and `\glstext` called `noindex`. This is a boolean key. If true, this suppresses the indexing. (That is, it prevents `\gls` or whatever from adding a line to the external glossary file.) This is more useful than the `indexonlyfirst` package option provided by `glossaries`, as the `first use` might not be the most pertinent use. (If you want to apply `indexonlyfirst` to selected entries, rather than all of them, you can use the `indexonlyfirst` attribute, see Section 5 for further details.) Note that the `noindex` key isn't available for `\glsadd` (and `\glsaddall`) since the whole purpose of that command is to index an entry.

There is a new hook that's used each time indexing information is written to the external glossary files:

```
\glsxtrdowrglossaryhook
  \glsxtrdowrglossaryhook{\label}
```

where `\label` is the entry's label. This does nothing by default but may be redefined. (See, for example, the accompanying sample file `sample-indexhook.tex`, which uses this hook to determine which entries haven't been indexed.)

The value of the `see` key is now saved as a field. This isn't the case with `glossaries`, where the `see` attribute is simply used to directly write a line to the corresponding glossary file and is then discarded. This is why the `see` key can't be used before `\makeglossaries` (since the file hasn't been opened yet). It's also the reason why the `see` key doesn't have any effect when used in entries that are defined in the document environment. Since the value isn't saved, it's not available when the `.glsdefs` file is created at the end of the document and so isn't available at the start of the document environment on the next run.

This modification allows `glossaries-extra` to provide

```
\glsxtraddallcrossrefs
```

```
\glsxtraddallcrossrefs
```

which is used at the end of the document to automatically add any unused cross-references unless the package option `indexcrossrefs` was set to false.

As a by-product of this enhancement, the `see` key will now work for entries defined in the document environment, but it's still best to define entries in the preamble, and the `see` key still can't perform any indexing before the file has been opened by `\makeglossaries`. Note that `glossaries` v4.24 introduced the `seenoindex` package option, which can be used to suppress the error when the `see` key is used before `\makeglossaries`, so `seenoindex=ignore` will allow the `see` value to be stored even though it may not be possible to index it at that point.

As from version 1.06, you can display the cross-referenced information for a given entry using

```
\glsxtrusesee
```

```
\glsxtrusesee{\langle label \rangle}
```

This internally uses

```
\glsxtruseseeformat
```

```
\glsxtruseseeformat{\langle tag \rangle}{\langle xr list \rangle}
```

where `\langle tag \rangle` and `\langle xr list \rangle` are obtained from the value of the entry's `see` field (if non-empty). By default, this just does `\glsseefORMAT[\langle tag \rangle]{\langle xr list \rangle}{}{}`, which is how the cross-reference is displayed in the **number list**. Note that `\glsxtrusesee` does nothing if the `see` field hasn't been set for the entry given by `\langle label \rangle`.

Suppose you want to suppress the number list using `nonumberlist`. This will automatically prevent the cross-references from being displayed. The `seeautonumberlist` package option will automatically enable the number list for entries that have the `see` key set, but this will also show the rest of the number list.

Another approach in this situation is to use the post description hook with `\glsxtrusesee` to append the cross-reference after the description. For example:

```
\renewcommand*{\glsxtrpostdescgeneral}{%
  \ifglshasfield{see}{\glscurrententrylabel}
  {, \glsxtrusesee{\glscurrententrylabel}}%
}%
```

Now the cross-references can appear even though the number list has been suppressed.

2.2 Entry Display Style Modifications

Recall from the glossaries package that commands such as `\gls` display text at that point in the document (optionally with a hyperlink to the relevant line in the glossary). This text is referred to as the “[link-text](#)” regardless of whether or not it actually has a hyperlink. The actual text and the way it’s displayed depends on the command used (such as `\gls`) and the entry format.

The default entry format (`\glsentryfmt`) used in the [link-text](#) by commands like `\gls`, `\glsxtrfull`, `\glsxtrshort` and `\glsxtrlong` (but not commands like `\glslink`, `\glsfirst` and `\glisttext`) is changed by `glossaries-extra` to test for regular entries, which are determined as follows:

- If an entry is assigned to a category that has the `regular` attribute set (see Section 5), the entry is considered a regular entry, even if it has a value for the short key. In this case `\glsentryfmt` uses `\glsgenentryfmt` (provided by `glossaries`), which uses the first (or `firstplural`) value on [first use](#) and the text (or plural) value on subsequent use.
- An entry that doesn’t have a value for the short key is assumed to be a regular entry, even if the `regular` attribute isn’t set to “true” (since it can’t be an abbreviation without the short form). In this case `\glsentryfmt` uses `\glsgenentryfmt`.
- If an entry does have a value for the short key and hasn’t been marked as a regular entry through the `regular` attribute, it’s not considered a regular entry. In this case `\glsentryfmt` uses `\glsxtrgenabbrvfmt` (defined by `glossaries-extra`) which is governed by the abbreviation style (see Section 3.2).

This means that entries with a short form can be treated as regular entries rather than abbreviations if it’s more appropriate for the desired style.

As from version 1.04, `\glsentryfmt` now puts `\glsgenentry` in the argument of the new command

```
\glsxtrregularfont
  \glsxtrregularfont{\langle text \rangle}
```

This just does its argument `\langle text \rangle` by default. This means that if you want regular entries in a different font but don’t want that font to apply to abbreviations, then you can redefine `\glsxtrregularfont`. This is more precise than changing `\glisttextformat` which will be applied to all linking commands for all entries.

For example:

```
\renewcommand*{\glsxtrregularfont}[1]{\textsf{\#1}}
```

You can access the label through `\glslabel`. For example, you can query the category:

```
\renewcommand*{\glsxtrregularfont}[1]{%
  \glsifcategory{\glslabel}{general}{\textsf{\#1}}{\#1}}
```

or query the category attribute:

```
\glssetcategoryattribute{general}{font}{sf}  
  
\renewcommand*\glsxtrregularfont[1]{%  
  \glsifattribute{\glslabel}{font}{sf}{\textsf{\#1}}{\#1}}
```

or use the attribute to store the control sequence name:

```
\glssetcategoryattribute{general}{font}{textsf}  
\glssetcategoryattribute{acronym}{font}{emph}  
  
\renewcommand*\glsxtrregularfont[1]{%  
  \glshasattribute{\glslabel}{font} %  
  {\csuse{\glsgetattribute{\glslabel}{font}}{\#1}}%  
  {\#1} %  
}
```

(Remember the category and attribute settings will only queried here for regular entries, so if the abbreviation style for the acronym category in the above example changes the regular attribute to “false”, `\glsxtrregularfont` will no longer apply.)

The `\glspostlinkhook` provided by the `glossaries` package to insert information after the **link-text** produced by commands like `\gls` and `\glslink` is redefined to

```
\glsxtrpostlinkhook
```

```
\glsxtrpostlinkhook
```

This command will discard a following full stop (period) if the `discardperiod` attribute is set to “true” for the current entry’s category. It will also do

```
\glsxtrpostlink
```

```
\glsxtrpostlink
```

if a full stop hasn’t be discarded and

```
\glsxtrpostlinkendsentence
```

```
\glsxtrpostlinkendsentence
```

if a full stop has been discarded.

By default `\glsxtrpostlink` just does `\glsxtrpostlink<category>` if it exists, where `<category>` is the category label for the current entry. (For example, for the general category, `\glsxtrpostlinkgeneral` if it has been defined.)

The sentence-ending hook is slightly more complicated. If the command `\glsxtrpostlink<category>` is defined the hook will do that and then insert a full stop with the space factor adjusted to match the end of sentence. If `\glsxtrpostlink<category>` hasn’t been defined, the space factor is adjusted to match the end of sentence. This means that if you have, for example, an entry that ends with a full stop, a redundant following full

stop will be discarded and the space factor adjusted (in case the entry is in uppercase) unless the entry is followed by additional material, in which case the following full stop is no longer redundant and needs to be reinserted.

There are some convenient commands you might want to use when customizing the post-link-text category hooks:

```
\glsxtrpostlinkAddDescOnFirstUse
```

```
\glsxtrpostlinkAddDescOnFirstUse
```

This will add the description in parentheses on **first use**.

For example, suppose you want to append the description in parentheses on first use for entries in the symbol category:

```
\newcommand*{\glsxtrpostlinksymbol}{%
  \glsxtrpostlinkAddDescOnFirstUse
}
```

```
\glsxtrpostlinkAddSymbolOnFirstUse
```

```
\glsxtrpostlinkAddSymbolOnFirstUse
```

This will append the symbol (if defined) in parentheses on first use.

If you want to provide your own custom format be aware that you can't use `\ifglsused` within the post-link-text hook as by this point the **first use flag** will have been unset. Instead you can use

```
\glsxtrifwasfirstuse
```

```
\glsxtrifwasfirstuse{\langle true\rangle}{\langle false\rangle}
```

This will do `\langle true\rangle` if the last used entry was the first use for that entry, otherwise it will do `\langle false\rangle`. (Requires at least glossaries v4.19 to work properly.) This command is locally set by commands like `\gls`, so don't rely on it outside of the post-link-text hook.

Note that commands like `\glsfirst` and `\glsxtrfull` fake first use for the benefit of the post-link-text hooks by setting `\glsxtrifwasfirstuse` to `\@firstoftwo`. (Although, depending on the styles in use, they may not exactly match the text produced by `\gls`-like commands on first use.) However, the short-postfootnote style alters `\glsxtrfull` so that it fakes non-first use otherwise the inline full format would include the footnote, which is inappropriate.

For example, if you want to place the description in a footnote after the link-text on first use for the general category:

```
\newcommand*{\glsxtrpostlinkgeneral}{%
  \glsxtrifwasfirstuse{\footnote{\glsentrydesc{\glslabel}}}}{}%
```

The short-postfootnote abbreviation style uses the post-link-text hook to place the footnote after trailing punctuation characters.

You can set the default options used by `\glslink`, `\gls` etc with:

```
\GlsXtrSetDefaultGlsOpts
```

```
\GlsXtrSetDefaultGlsOpts{\<options>}
```

For example, if you mostly don't want to index entries then you can do:

```
\GlsXtrSetDefaultGlsOpts{noindex}
```

and then use, for example, `\gls[noindex=false]{sample}` when you actually want the location added to the **number list**. These defaults may be overridden by other settings (such as category attributes) in addition to any settings passed in the option argument of commands like `\glslink` and `\gls`.

Note that if you don't want *any* indexing, just omit `\makeglossaries` and `\printglossaries` (or analogous commands).

Commands like `\gls` have star (*) and plus (+) modifiers as a short cut for `hyper=false` and `hyper=true`. The `glossaries-extra` package provides a way to add a third modifier, if required, using

```
\GlsXtrSetAltModifier
```

```
\GlsXtrSetAltModifier{\<char>}{\<options>}
```

where `\<char>` is the character used as the modifier and `\<options>` is the default set of options (which may be overridden). Note that `\<char>` must be a single character (not a UTF-8 character, unless you are using X_ET_EX or LuaX_ET_EX).

When choosing the character `\<char>` take care of any changes in category code.

Example:

```
\GlsXtrSetAltModifier{!}{noindex}
```

This means that `\gls!{sample}` will be equivalent to `\gls[noindex]{sample}`. It's not possible to mix modifiers. For example, if you want to do

```
\gls[noindex,hyper=false]{sample}
```

you can use `\gls*[noindex]{sample}` or `\gls![hyper=false]{sample}` but you can't combine the * and ! modifiers.

2.3 Entry Counting Modifications

The `\glsenableentrycount` command is modified to allow for the `entrycount` attribute. This means that you not only need to enable entry counting with `\glsenableentrycount`, but you also need to set the appropriate attribute (see Section 5).

For example, instead of just doing:

```
\glsenableentrycount
```

you now need to do:

```
\glsenableentrycount  
\glssetcategoryattribute{abbreviation}{entrycount}{1}
```

This will enable the entry counting for entries in the abbreviation category, but any entries assigned to other categories will be unchanged.

Further information about entry counting, including the new per-unit feature, is described in Section 6.

2.4 Nested Links

Complications arise when you use `\gls` in the value of the name field (or text or first fields, if set). This tends to occur with abbreviations that extend other abbreviations. For example, SHTML is an abbreviation for SSI enabled HTML, where SSI is an abbreviation for Server Side Includes and HTML is an abbreviation for Hypertext Markup Language.

Things can go wrong if we try the following with the glossaries package:

```
\newacronym{ssi}{SSI}{Server Side Includes}  
\newacronym{html}{HTML}{Hypertext Markup Language}  
\newacronym{shtml}{S\gls{html}}{\gls{ssi} enabled \gls{html}}
```

The main problems are:

1. The first letter upper casing commands, such as `\Gls`, won't work for the `shtml` entry on **first use** if the long form is displayed before the short form (which is the default abbreviation style). This will attempt to do

```
\gls{\uppercase ssi} enabled \gls{html}
```

which just doesn't work. Grouping the `\gls{ssi}` doesn't work either as this will effectively try to do

```
\uppercase{\gls{ssi}} enabled \gls{html}
```

This will upper case the label `ssi` so the entry won't be recognised. This problem will also occur if you use the all capitals version, such as `\GLS`.

2. The long and abbreviated forms accessed through `\glsentrylong` and `\glsentryshort` are no longer expandable and so can't be used be used in contexts that require this, such as PDF bookmarks.
3. The nested commands may end up in the sort key, which will confuse the indexing.

4. The `shtml` entry produces inconsistent results depending on whether the `ssi` or `html` entries have been used. Suppose both `ssi` and `html` are used before `shtml`. For example:

```
This section discusses \gls{ssi}, \gls{html} and \gls{shtml}.
```

This produces:

This section discusses server side includes (SSI), hypertext markup language (HTML) and SSI enabled HTML (SHTML).

So the **first use** of the `shtml` entry produces “SSI enabled HTML (SHTML)”.

Now let's suppose the `html` entry is used before the `shtml` but the `ssi` entry is used after the `shtml` entry, for example:

```
The sample files are either \gls{html} or \gls{shtml}, but let's first discuss \gls{ssi}.
```

This produces:

The sample files are either hypertext markup language (HTML) or server side includes (SSI) enabled HTML (SHTML), but let's first discuss SSI.

So the first use of the `shtml` entry now produces “server side includes (SSI) enabled HTML (SHTML)”, which looks a bit strange.

Now let's suppose the `shtml` entry is used before (or without) the other two entries:

```
This article is an introduction to \gls{shtml}.
```

This produces:

This article is an introduction to server side includes (SSI) enabled hypertext markup language (HTML) (SHTML).

So the first use of the `shtml` entry now produces “server side includes (SSI) enabled hypertext markup language (HTML) (SHTML)”, which is even more strange.

This is all aggravated by setting the style using the `glossaries` package's `\setacronymstyle`. For example:

```
\setacronymstyle{long-short}
```

as this references the label through the use of `\glslabel` when displaying the long and short forms, but this value changes with each use of `\gls`, so instead of displaying “(SHTML)” at the end of the first use, it now displays “(HTML)”, since `\glslabel` has been changed to `html` by `\gls{html}`.

Another oddity occurs if you reset the `html` entry between uses of the `shtml` entry. For example:

```
\gls{shtml} ... \glsreset{html}\gls{shtml}
```

The next use of `shtml` produces “Shypertext markup language (HTML)”, which is downright weird.

Even without this, the short form has nested formatting commands, which amount to `\acronymfont{S\acronymfont{HTML}}`. This may not be a problem for some styles, but if you use one of the “sm” styles (that use `\textsmaller`), this will produce an odd result.

5. Each time the `shtml` entry is used, the `html` entry will also be indexed and marked as used, and on **first use** this will happen to both the `ssi` and `html` entries. This kind of duplication in the location list isn’t usually particularly helpful to the reader.
6. If `hyperref` is in use, you’ll get nested hyperlinks and there’s no consistent way of dealing with this across the available PDF viewers. If on the first use case, the user clicks on the “HTML” part of the “SSI enabled HTML (SHTML)” link, they may be directed to the `HTML` entry in the glossary or they may be directed to the `SHTML` entry in the glossary.

For these reasons it’s better to use the simple expandable commands like `\glsentrytext` or `\glsentryshort` in the definition of other entries (although that doesn’t fix the first problem). Alternatively use something like:

```
\newacronym
[description={\acrshort{ssi} enabled \acrshort{html}}]
{shtml}{SHTML}{SSI enabled HTML}
```

with `glossaries` or:

```
\newabbreviation
[description={\glsxtrshort{ssi} enabled \glsxtrshort{html}}]
{shtml}{SHTML}{SSI enabled HTML}
```

with `glossaries-extra`. This fixes all the above listed problems (as long as you don’t use `\glsdesc`). Note that replacing `\gls` with `\acrshort` in the original example may fix the first use issue, but it doesn’t fix any of the other problems listed above.

If it’s simply that you want to use the abbreviation font, you can use `\glsabbrvfont`:

```
\setabbreviationstyle{long-short-sc}

\newabbreviation{ssi}{ssi}{server-side includes}
\newabbreviation{html}{html}{hypertext markup language}
\newabbreviation{shtml}{shtml}{\glsabbrvfont{ssi} enabled
\glsabbrvfont{html}}
```

This will pick up the font style setting of the outer entry (`shtml`, in the above case). This isn’t a problem in the above example as all the abbreviations use the same style.

However if you’re really determined to use `\gls` in a field that may be included within some `link-text`, `glossaries-extra` patches internals used by the linking commands so that if `\gls` (or plural or case changing variants) occurs in the link-text it will behave as though you used `\glstext[hyper=false,noindex]` instead. Grouping is also added so that, for example, when `\gls{shtml}` is used for the first time the long form

```
\gls{ssi} enabled \gls{html}
```

is treated as

```
{\glstext[hyper=false,noindex]{ssi}} enabled  
\glstext[hyper=false,noindex]{html}}
```

This overcomes problems 4, 5 and 6 listed above, but still doesn't fix problems 1 and 2. Problem 3 usually won't be an issue as most abbreviation styles set the sort key to the short form, so using these commands in the long form but not the short form will only affect entries with a style that sorts according to the long form (such as `long-noshort-desc`).

Additionally, any instance of the long form commands, such as `\glsxtrlong` or `\acrlong` will be temporarily redefined to just use

```
{\glsentrylong{\label}{\insert}}
```

(or case-changing versions). Similarly the short form commands, such as `\glsxtrshort` or `\acrshort` will use `\glsentryshort` in the argument of either `\glsabbrvfont` (for `\glsxtrshort`) or `\acronymfont` (for `\acrshort`). So if the `shtml` entry had instead been defined as:

```
\newacronym{shtml}{SHTML}{\acrshort{ssi} enabled \acrshort{html}}
```

then (using the long-short style) the **first use** will be like

```
{\acronymfont{\glsentryshort{ssi}}} enabled  
\acronymfont{\glsentryshort{html}} (SHTML)
```

whereas if the entry is defined as:

```
\newabbreviation{shtml}{SHTML}{\glsxtrshort{ssi} enabled  
\glsxtrshort{html}}
```

then the first use will be like:

```
{\glsabbrvfont{\glsentryshort{ssi}}} enabled  
\glsabbrvfont{\glsentryshort{html}} (SHTML)
```

Note that the first optional argument of `\acrshort` or `\glsxtrshort` is ignored in this context. (The final optional argument will be inserted, if present.) The abbreviation style that governs `\glsabbrvfont` will be set for `\glsxtrshort`. Note that `\acrshort` doesn't set the abbreviation style.

If you use any of the case-changing commands, such as `\Gls` or `\Glstext`, (either all caps or first letter upper casing) don't use any of the linking commands, such as `\gls` or `\glstext`, in the definition of entries for any of the fields that may be used by those case-changing commands.

You can, with care, protect against issue 1 by inserting an empty group at the start if the long form starts with a command that breaks the first letter uppercasing commands like `\Gls`, but you still won't be able to use the all caps commands, such as `\GLS`.

2.5 Acronym Style Modifications

The glossaries-extra package provides a new way of dealing with abbreviations and redefines `\newacronym` to use `\newabbreviation` (see Section 3). If you want to restore the generic acronym function provided by glossaries you need to use

```
\RestoreAcronyms
```

```
\RestoreAcronyms
```

but be careful using this if you also want abbreviations as they will clash if you attempt to use them in the same glossary as generic acronyms from the glossaries package.

```
\glsacspace
```

```
\glsacspace{\<label>}
```

The space command `\glsacspace` used by the long-sp-short acronym style provided by glossaries is modified so that it uses

```
\glsacspacemax
```

```
\glsacspacemax
```

instead of the hard-coded 3em. This is a command not a length and so can be changed using `\renewcommand`.

The **first use** acronym font command

```
\firstacronymfont{\<text>}
```

is redefined to use the first use abbreviation font command `\glsfirstabbrvfont`. This will be reset if you use `\RestoreAcronyms`.

The subsequent use acronym font command

```
\acronymfont{\<text>}
```

is redefined to use the subsequent use abbreviation font command `\glsabbrvfont`. This will be reset if you use `\RestoreAcronyms`.

2.6 Glossary Style Modifications

The default value of `\glslistdottedwidth` is changed so that it's set at the start of the document (if it hasn't been changed in the preamble). This should take into account situations where `\hsize` isn't set until the start of the document.

2.6.1 Style Hooks

The commands `\glossentryname` and `\glossentrydesc` are modified to take into account the `glossname`, `glossdesc` and `glossdescfont` attributes (see Section 5). This means you can make simple case-changing modifications to the name and description without defining a new glossary style.

There is a hook after `\glossentryname` and `\Glossentryname`:

```
\glsxtrpostnamehook
```

```
\glsxtrpostnamehook{\label}
```

By default this checks the `indexname` attribute. If the attribute exists for the category to which the label belongs, then the name is automatically indexed using

```
\glsxtrdoautoindexname{\label}{indexname}
```

See Section 7 for further details.

As from version 1.04, the post-name hook `\glsxtrpostnamehook` will also use `\glsxtrpostname<category>` if it exists. You can use `\glscurrententrylabel` to obtain the entry label with the definition of this command. For example, suppose you are using a glossary style that doesn't display the symbol, you can insert the symbol after the name for a particular category, say, the "symbol" category:

```
\newcommand*{\glsxtrpostnamesymbol}{\space\nobreak(\glsentrysymbol\glscurrententrylabel)}
```

The post-description code used within the glossary is modified so that it also does

```
\glsxtrpostdescription
```

```
\glsxtrpostdescription
```

This occurs before the original `\glspostdescription`, so if the `nopostdot=false` option is used, it will be inserted before the terminating full stop.

This new command will do `\glsxtrpostdesc<category>` if it exists, where `<category>` is the category label associated with the current entry. For example `\glsxtrpostdescgeneral` for entries with the category set to general or `\glsxtrpostdescacronym` for entries with the category set to acronym.

Since both `\glossentry` and `\subglossentry` set

```
\glscurrententrylabel
```

```
\glscurrententrylabel
```

to the label for the current entry, you can use this within the definition of these post-description hooks if you need to reference the label.

For example, suppose you want to insert the plural form in brackets after the description in the glossary, but only for entries in the general category, then you could do:

```
\renewcommand{\glsxtrpostdescgeneral}{\space  
  (plural: \glsentryplural{\glscurrententrylabel})}
```

This means you don't have to define a custom glossary style, which you may find more complicated. (It also allows more flexibility if you decide to change the underlying glossary style.)

This feature can't be used for glossary styles that ignore `\glspostdescription` or if you redefine `\glspostdescription` without including `\glsxtrpostdescription`. (For example, if you redefine `\glspostdescription` to do nothing instead of using the `nopostdot` option to suppress the terminating full stop.) See Section 2.6.3 to patch the predefined styles provided by glossaries that are missing `\glspostdescription`.

2.6.2 Number List

The **number list** is now placed inside the argument of

```
\GlsXtrFormatLocationList
```

```
\GlsXtrFormatLocationList{\<number list>}
```

This is internally used by `\glossaryentrynumbers`. The `nonumberlist` option redefines `\glossaryentrynumbers` so that it doesn't display the number list, but it still saves the number list in case it's required.

If you want to suppress the number list always use the `nonumberlist` option instead of redefining `\glossaryentrynumbers` to do nothing.

If you want to, for example, change the font for the entire number list then redefine `\GlsXtrFormatLocationList` as appropriate. Don't modify `\glossaryentrynumbers`.

Sometimes users like to insert “page” or “pages” in front of the number list. This is quite fiddly to do with the base `glossaries` package, but `glossaries-extra` provides a way of doing this. First you need to enable this option and specify the text to display using:

```
\GlsXtrEnablePreLocationTag
```

```
\GlsXtrEnablePreLocationTag{\<page>}{\<pages>}
```

where `\<page>` is the text to display if the number list only contains a single location and `\<pages>` is the text to display otherwise. For example:

```
\GlsXtrEnablePreLocationTag{Page: }{Pages: }
```

An extra run is required when using this command.

Use `glsignore` not `@gobble` as the format if you want to suppress the page number (and only index the entry once).

See the accompanying sample file `sample-pages.tex`.

2.6.3 The `glossaries-extra-stylemods` Package

As from v1.02, `glossaries-extra` now includes the package `glossaries-extra-stylemods` that will redefine the predefined styles to include the post-description hook (for those that are missing it). You will need to make sure the styles have already been defined before loading `glossaries-extra`. For example:

```
\usepackage{glossaries-extra}
\usepackage{glossary-longragged}
\usepackage{glossaries-extra-stylemods}
```

Alternatively you can load `glossary-<name>.sty` at the same time by passing `<name>` as a package option to `glossaries-extra-stylemods`. For example:

```
\usepackage{glossaries-extra}
\usepackage[longragged]{glossaries-extra-stylemods}
```

Another option is to use the `stylemods` key when you load `glossaries-extra`. You can omit a value if you only want to use the predefined styles that are automatically loaded by `glossaries` (for example, the `long3col` style):

```
\usepackage[style=long3col,stylemods]{glossaries-extra}
```

Or the value of `stylemods` may be a comma-separated list of the style package identifiers. For example:

```
\usepackage[style=mcoltree,stylemods=mcols]{glossaries-extra}
```

Remember to group the value if it contains any commas:

```
\usepackage[stylemods={mcols,longbooktabs}]{glossaries-extra}
```

Note that the inline style is dealt with slightly differently. The original definition provided by the `glossary-inline` package uses `\glspostdescription` at the end of the glossary (not after each entry description) within the definition of `\glspostinline`. The style modification changes this so that `\glspostinline` just does a full stop followed by space factor adjustment, and the description `\glsinlinedescformat` and sub-entry description formats `\glsinlinesubdescformat` are redefined to include `\glsxtrpostdescription` (not `\glspostdescription`). This means that the modified inline style isn't affected by the `no-postdot` option, but the post-description category hook can still be used.

As from version 1.05, the `glossaries-extra-stylemods` package provides some additional commands for use with the `alttree` style to make it easier to modify. These commands are only defined if the `glossary-tree` package has already been loaded, which is typically the case unless the `notree` option has been used when loading `glossaries`.

```
\eglssetwidest
```

```
\eglssetwidest[<level>]{<name>}
```

This is like `\glssetwidest` (provided by glossary-tree) but performs a protected expansion on `<name>`. This has a localised effect. For a global setting, use

```
\xglssetwidest
```

```
\xglssetwidest[<level>]{<name>}
```

The widest entry value can later be retrieved using

```
\glsgetwidestname
```

```
\glsgetwidestname
```

for the top-level entries and

```
\glsgetwidestsubname
```

```
\glsgetwidestsubname{<level>}
```

for sub-entries, where `<level>` is the level number.

The command `\glsfindwidesttoplevelname` provided by glossary-tree has a CamelCase synonym:

```
\glsFindWidestTopLevelName
```

```
\glsFindWidestTopLevelName[<glossary list>]
```

Similar commands are also provided:

```
\glsFindWidestUsedTopLevelName
```

```
\glsFindWidestUsedTopLevelName[<glossary list>]
```

This has an additional check that the entry has been used. Naturally this is only useful if the glossaries that use the alttree style occur at the end of the document. This command should be placed just before the start of the glossary. (Alternatively, place it at the end of the document and save the value in the auxiliary file for the next run.)

```
\glsFindWidestUsedAnyName
```

```
\glsFindWidestUsedAnyName[<glossary list>]
```

This is like the previous command but it doesn't check the parent key. This is useful if all levels should have the same width for the name.

```
\glsFindWidestAnyName
```

```
\glsFindWidestAnyName[<glossary list>]
```

This is like the previous command but doesn't check if the entry has been used.

```
\glsFindWidestUsedLevelTwo
```

```
\glsFindWidestUsedLevelTwo[⟨glossary list⟩]
```

This is like `\glsFindWidestUsedTopLevelName` but also sets the first two sub-levels as well. Any entry that has a great-grandparent is ignored.

```
\glsFindWidestLevelTwo
```

```
\glsFindWidestLevelTwo[⟨glossary list⟩]
```

This is like the previous command but doesn't check if the entry has been used.

```
\glsFindWidestUsedAnyNameSymbol
```

```
\glsFindWidestUsedAnyNameSymbol[⟨glossary list⟩]{⟨register⟩}
```

This is like `\glsFindWidestUsedAnyName` but also measures the symbol. The length of the widest symbol is stored in `⟨register⟩`.

```
\glsFindWidestAnyNameSymbol
```

```
\glsFindWidestAnyNameSymbol[⟨glossary list⟩]{⟨register⟩}
```

This is like the previous command but it doesn't check if the entry has been used.

```
\glsFindWidestUsedAnyNameSymbolLocation
```

```
\glsFindWidestUsedAnyNameSymbolLocation[⟨glossary list⟩]{⟨symbol register⟩}{⟨location register⟩}
```

This is like `\glsFindWidestUsedAnyNameSymbol` but also measures the **number list**. This requires `\glsentrynumberlist` (see the glossaries user manual). The length of the widest symbol is stored in `⟨symbol register⟩` and the length of the widest number list is stored in `⟨location register⟩`.

```
\glsFindWidestAnyNameSymbolLocation
```

```
\glsFindWidestAnyNameSymbolLocation[⟨glossary list⟩]{⟨symbol register⟩}{⟨location register⟩}
```

This is like the previous command but it doesn't check if the entry has been used.

```
\glsFindWidestUsedAnyNameLocation
```

```
\glsFindWidestUsedAnyNameLocation[⟨glossary list⟩]{⟨register⟩}
```

This is like `\glsFindWidestUsedAnyNameSymbolLocation` but doesn't measure the symbol. The length of the widest number list is stored in `⟨register⟩`.

```
\glsFindWidestAnyNameLocation
```

```
  \glsFindWidestAnyNameLocation[glossary list]{register}
```

This is like the previous command but doesn't check if the entry has been used.

The layout of the symbol, description and **number list** is governed by

```
\glsxtralTreeSymbolDescLocation
```

```
  \glsxtralTreeSymbolDescLocation{label}{number list}
```

for top-level entries and

```
\glsxtralTreeSubSymbolDescLocation
```

```
  \glsxtralTreeSubSymbolDescLocation{label}{number list}
```

for sub-entries.

There is now a user level command that performs the initialisation for the alTree style:

```
\glsxtralTreeInit
```

```
  \glsxtralTreeInit
```

The paragraph indent for subsequent paragraphs in multi-paragraph descriptions is provided by the length

```
\glsxtrAltTreeIndent
```

```
  \glsxtrAltTreeIndent
```

For additional commands that are available with the alTree style, see the documented code (*glossaries-extra-code.pdf*). For examples, see the accompanying sample files *sample-alTree.tex*, *sample-alTree-sym.tex* and *sample-alTree-mARGINpar.tex*.

3 Abbreviations

Abbreviations include acronyms (words formed from initial letters, such as “laser”), initialisms (initial letters of a phrase, such as “html”, that aren’t pronounced as words) and contractions (where parts of words are omitted, often replaced by an apostrophe, such as “don’t”). The “acronym” code provided by the glossaries package is misnamed as it’s more often than not used for initialisms instead. Acronyms tend not to be *expanded* on **first use** (although they may need to be *described* for readers unfamiliar with the term). They are therefore more like a regular term, which may or may not require a description in the glossary.

The glossaries-extra package corrects this misnomer, and provides better abbreviation handling, with

```
\newabbreviation
```

```
\newabbreviation[<options>]{<label>}{<short>}{<long>}
```

This sets the category key to `abbreviation` by default, but that value may be overridden in `<options>`. The category may have attributes that modify the way abbreviations are defined. For example, the `insertdots` attribute will automatically insert full stops (periods) into `<short>` or the `noshortplural` attribute will set the default value of the `shortplural` key to just `<short>` (without appending the plural suffix). See Section 5 for further details.

See Section 2.4 regarding the pitfalls of using commands like `\gls` or `\glsxtrshort` within `<short>` or `<long>`.

Make sure that you set the category attributes before defining new abbreviations or they may not be correctly applied.

The `\newacronym` command provided by the glossaries package is redefined by glossaries-extra to use `\newabbreviation` with the category set to `acronym`. If you want to restore the original behaviour of acronyms (as implemented by the glossaries package’s `\newacronym`, `\setacronymstyle` and `\newacronymstyle`) you need to use

```
\RestoreAcronyms
```

```
\RestoreAcronyms
```

However, if you do this take care not to mix acronyms with other types of entries within the same glossary. (You may also need to redefine `\acronymtype`.)

The `\newabbreviation` command is superficially similar to the glossaries package’s `\newacronym` but you can apply different styles to different categories. The default style is `short-nolong` for entries in the `acronym` category and `short-long` for entries in the `abbreviation`

category. (These aren't the same as the acronym styles provided by the glossaries package, although they may produce similar results.)

The short form is displayed within commands like `\gls` using

```
\glsfirstabbrvfont
```

```
\glsfirstabbrvfont{\<short-form>}
```

on **first use** and

```
\glsabbrvfont
```

```
\glsabbrvfont{\<short-form>}
```

for subsequent use.

These commands (`\glsfirstabbrvfont` and `\glsabbrvfont`) are reset by the abbreviation styles and whenever an abbreviation is used by commands like `\gls` (but not by commands like `\glsentryshort`) so don't try redefining them outside of an abbreviation style.

If you use the long-short style, `\glsabbrvfont` is redefine to use

```
\glsabbrvdefaultfont
```

```
\glsabbrvdefaultfont{\<text>}
```

whereas the long-short-sc style redefines `\glsabbrvfont` to use `\glsxtrscfont`. If you want to use a different font-changing command you can either redefine `\glsabbrvdefaultfont` and use one of the base styles, such as long-short, or define a new style in a similar manner to the "sc", "sm" or "em" styles.

Similarly the basic styles redefine `\glsfirstabbrvfont` to use

```
\glsfirstabbrvdefaultfont
```

```
\glsfirstabbrvdefaultfont{\<short-form>}
```

whereas the font modifier styles, such as long-short-sc, use their own custom command, such as `\glsfirstscfont`.

The commands that display the full form for abbreviations use `\glsfirstabbrvfont` to display the short form and

```
\glsfirstlongfont
```

```
\glsfirstlongfont{\<long-form>}
```

to display the long form on first use or for the inline full format. Commands like `\glsxtrlong` use

```
\glslongfont
```

```
\glslongfont{\<long-form>}
```

instead.

As with `\glsabbrvfont`, this command is changed by all styles. Currently all predefined abbreviation styles, except the “long-em” (emphasize long form) versions, provided by `glossaries-extra` redefine `\glsfirstlongfont` to use

```
\glsfirstlongdefaultfont
```

```
\glsfirstlongdefaultfont{\<long-form>}
```

and `\glslongfont` to use

```
\glslongdefaultfont
```

```
\glslongdefaultfont{\<long-form>}
```

You can redefine these command if you want to change the font used by the long form for all your abbreviations (except for the emphasize-long styles), or you can define your own abbreviation style that provides a different format for only those abbreviations defined with that style.

The “long-em” (emphasize long) styles use

```
\glsfirstlongemfont
```

```
\glsfirstlongemfont{\<long-form>}
```

instead of `\glsfirstlongdefaultfont{\<long-form>}` and

```
\glslongemfont
```

```
\glslongemfont{\<long-form>}
```

instead of `\glslongdefaultfont{\<long-form>}`. The first form `\glsfirstlongemfont` is initialised to use `\glslongemfont`.

Note that by default inserted material (provided in the final optional argument of commands like `\gls`), is placed outside the font command in the predefined styles. To move it inside, use:

```
\glsxtrinsertinsidetrue
```

```
\glsxtrinsertinsidetrue
```

This applies to all the predefined styles. For example:

```
\setabbreviationstyle{long-short}
\renewcommand*\glsfirstlongdefaultfont[1]{\emph{#1}}
\glsxtrinsertinsidetrue
```

This will make the long form and in the inserted text emphasized, whereas the default (without `\glsxtrinsertinsidetrue`) would place the inserted text outside of the emphasized font.

Note that for some styles, such as the short-long, the inserted text would be placed inside the font command for the short form (rather than the long form in the above example).

There are two types of full forms. The display full form, which is used on **first use** by commands like `\gls` and the inline full form, which is used by commands like `\glsxtrfull`. For some of the abbreviation styles, such as long-short, the display and inline forms are the same. In the case of styles such as short-nolong or short-footnote, the display and inline full forms are different.

These formatting commands aren't stored in the short, shortplural, long or longplural fields, which means they won't be used within commands like `\glsentryshort` (but they are used within commands like `\glsxtrshort` and `\glsfmtshort`). Note that `\glsxtrlong` and the case-changing variants don't use `\glsfirstlongfont`.

3.1 Tagging Initials

If you would like to tag the initial letters in the long form such that those letters are underlined in the glossary but not in the main part of the document, you can use

```
\GlsXtrEnableInitialTagging
```

```
\GlsXtrEnableInitialTagging{\<categories>}{\<cs>}
```

before you define your abbreviations.

This command (robustly) defines `<cs>` (a control sequence) to accept a single argument, which is the letter (or letters) that needs to be tagged. The normal behaviour of this command within the document is to simply do its argument, but in the glossary it's activated for those categories that have the tagging attribute set to "true". For those cases it will use

```
\glsxtrtagfont
```

```
\glsxtrtagfont{\<text>}
```

This command defaults to `\underline{\<text>}` but may be redefined as required.

The control sequence `<cs>` can't already be defined when used with the unstarred version of `\GlsXtrEnableInitialTagging` for safety reasons. The starred version will overwrite any previous definition of `<cs>`. As with redefining any commands, ensure that you don't redefine something important. In fact, just forget the existence of the starred version and let's pretend I didn't mention it.

The first argument of `\GlsXtrEnableInitialTagging` is a comma-separated list of category names. The tagging attribute will automatically be set for those categories. You can later set this attribute for other categories (see Section 5) but this must be done before the glossary is displayed.

The accompanying sample file `sample-mixtures.tex` uses initial tagging for both the acronym and abbreviation categories:

```
\GlsXtrEnableInitialTagging{acronym,abbreviation}{\itag}
```

This defines the command `\itag` which can be used in the definitions. For example:

```
\newacronym
  [description={a system for detecting the location and
  speed of ships, aircraft, etc, through the use of radio
  waves}]{radar}{}
  []
  {radar}{%
    identifying label
    short form (i.e. the word)
    \itag{ra}dio \itag{d}etection \itag{a}nd \itag{r}anging}

\newabbreviation[xml]{XML}
  {e\itag{x}tensible \itag{m}arkup \itag{l}anguage}
```

The underlining of the tagged letters only occurs in the glossary and then only for entries with the `tagging` attribute set.

3.2 Abbreviation Styles

The abbreviation style must be set before abbreviations are defined using:

```
\setabbreviationstyle
```

```
\setabbreviationstyle[<category>]{<style-name>}
```

where `<style-name>` is the name of the style and `<category>` is the category label (abbreviation by default). New abbreviations will pick up the current style according to their given category. If there is no style set for the category, the fallback is the style for the abbreviation category. Some styles may automatically modify one or more of the attributes associated with the given category. For example, the `long-noshort` and `short-nolong` styles set the `regular` attribute to `true`.

If you want to apply different styles to groups of abbreviations, assign a different category to each group and set the style for the given category.

Note that `\setacronymstyle` is disabled by `glossaries-extra`. Use

```
\setabbreviationstyle[acronym]{<style-name>}
```

instead. The original acronym interface can be restored with `\RestoreAcronyms` (see Section 2.5).

Abbreviations can be used with the standard `glossaries` commands, such as `\gls`, but don't use the acronym commands like `\acrshort` (which use `\acronymfont`). The short form can be produced with:

\glsxtrshort

```
\glsxtrshort[<options>]{<label>}[<insert>]
```

(Use this instead of \acrshort.)

The long form can be produced with

\glsxtrlong

```
\glsxtrlong[<options>]{<label>}[<insert>]
```

(Use this instead of \acrlong.)

The *inline* full form can be produced with

\glsxtrfull

```
\glsxtrfull[<options>]{<label>}[<insert>]
```

(This this instead of \acrfull.)

As mentioned earlier, the inline full form may not necessarily match the format used on **first use** with \gls. For example, the short-nolong style only displays the short form on first use, but the full form will display the long form followed by the short form in parentheses.

If you want to use an abbreviation in a chapter or section title, use the commands described in Section 4 instead.

The arguments *<options>*, *<label>* and *<insert>* are the same as for commands such as \glstext. There are also analogous case-changing commands:

First letter upper case short form:

\Glsxtrshort

```
\Glsxtrshort[<options>]{<label>}[<insert>]
```

First letter upper case long form:

\Glsxtrlong

```
\Glsxtrlong[<options>]{<label>}[<insert>]
```

First letter upper case inline full form:

\Glsxtrfull

```
\Glsxtrfull[<options>]{<label>}[<insert>]
```

All upper case short form:

\Glsxtrshort

```
\GLSxtrshort[<options>]{<label>}[<insert>]
```

All upper case long form:

\Glsxtrlong

\GLSxtrlong[*options*]{*label*} [*insert*]

All upper case inline full form:

\GLSxtrfull

\GLSxtrfull[*options*]{*label*} [*insert*]

Plural forms are also available.

Short form plurals:

\glsxtrshortpl

\glsxtrshortpl[*options*]{*label*} [*insert*]

\Glsxtrshortpl

\Glsxtrshortpl[*options*]{*label*} [*insert*]

\GLSxtrshortpl

\GLSxtrshortpl[*options*]{*label*} [*insert*]

Long form plurals:

\glsxtrlongpl

\glsxtrlongpl[*options*]{*label*} [*insert*]

\Glsxtrlongpl

\Glsxtrlongpl[*options*]{*label*} [*insert*]

\GLSxtrlongpl

\GLSxtrlongpl[*options*]{*label*} [*insert*]

Full form plurals:

\glsxtrfullpl

\glsxtrfullpl[*options*]{*label*} [*insert*]

\Glsxtrfullpl

\Glsxtrfullpl[*options*]{*label*} [*insert*]

```
\GLSxtrfullpl
```

```
\GLSxtrfullpl[options]{label}[{insert}]
```

Be careful about using `\glsentryfull`, `\Glsentryfull`, `\glsentryfullpl` and `\Glsentryfullpl`. These commands will use the currently applied style rather than the style in use when the entry was defined. If you have mixed styles, you'll need to use `\glsxtrfull` instead. Similarly for `\glsentryshort` etc.

3.3 Shortcut Commands

The abbreviation shortcut commands can be enabled using the package option `shortcuts=abbreviation` (or `shortcuts=abbr`). This defines the commands listed in [table 3.1](#).

Table 3.1: Abbreviation Shortcut Commands

Shortcut	Equivalent Command
<code>\ab</code>	<code>\cgls</code>
<code>\abp</code>	<code>\cglsp</code>
<code>\as</code>	<code>\glsxtrshort</code>
<code>\asp</code>	<code>\glsxtrshortpl</code>
<code>\al</code>	<code>\glsxtrlong</code>
<code>\alp</code>	<code>\glsxtrlongpl</code>
<code>\af</code>	<code>\glsxtrfull</code>
<code>\fp</code>	<code>\glsxtrfullpl</code>
<code>\As</code>	<code>\Glsxtrshort</code>
<code>\Asp</code>	<code>\Glsxtrshortpl</code>
<code>\Al</code>	<code>\Glsxtrlong</code>
<code>\Alp</code>	<code>\Glsxtrlongpl</code>
<code>\Af</code>	<code>\Glsxtrfull</code>
<code>\Afp</code>	<code>\Glsxtrfullpl</code>
<code>\AS</code>	<code>\GLSxtrshort</code>
<code>\ASP</code>	<code>\GLSxtrshortpl</code>
<code>\AL</code>	<code>\GLSxtrlong</code>
<code>\ALP</code>	<code>\GLSxtrlongpl</code>
<code>\AF</code>	<code>\GLSxtrfull</code>
<code>\AFP</code>	<code>\GLSxtrfullpl</code>
<code>\newabbr</code>	<code>\newabbreviation</code>

3.4 Predefined Abbreviation Styles

There are two types of abbreviation styles: those that treat the abbreviation as a regular entry (so that `\gls` uses `\glsgenentryfmt`) and those that don't treat the abbreviation as a regular entry (so that `\gls` uses `\glsxtrgenabbrvfmt`).

The regular entry abbreviation styles set the `regular` attribute to “true” for the category assigned to each abbreviation with that style. This means that on **first use**, `\gls` uses the value of the first field and on subsequent use `\gls` uses the value of the text field (and analogously for the plural and case-changing versions). The short and long fields are set as appropriate and may be accessed through commands like `\glsxtrshort`.

The other abbreviation styles don't modify the `regular` attribute. The `first` and `text` fields (and their plural forms) are set and can be accessed through commands like `\glsfirst`, but they aren't used by commands like `\gls`, which instead use the short form (stored in the short key) and the display full format (through commands like `\glsxtrfullformat` that are defined by the style).

In both cases, the first use of `\gls` may not match the text produced by `\glsfirst` (and likewise for the plural and case-changing versions).

For the “sc” styles that use `\textsc`, be careful about your choice of fonts as some only have limited support. For example, you may not be able to combine bold and small-caps. I recommend that you at least use the `fontenc` package with the `T1` option or something similar.

The “sc” styles all use

```
\glsxtrscfont
```

```
\glsxtrscfont{\text{<text>}}
```

which is defined as

```
\newcommand*{\glsxtrscfont}[1]{\textsc{#1}}
```

and

```
\glsxtrfirstscfont
```

```
\glsxtrfirstscfont{\text{<text>}}
```

which is defined as

```
\newcommand*{\glsxtrfirstscfont}[1]{\glsxtrscfont{#1}}
```

The default plural suffix for the short form is set to

```
\glsxtrscsuffix
```

```
\glsxtrscsuffix
```

This just defined as

```
\newcommand*{\glsxtrscsuffix}{\glstextup{\glspluralsuffix}}
```

The `\glstextup` command is provided by glossaries and is used to switch off the small caps font for the suffix. If you override the default short plural using the `shortplural` key when you define the abbreviation you will need to make the appropriate adjustment if necessary. (Remember that the default plural suffix behaviour can be modified through the use of the `aposplural` and `noshortplural` attributes. See Section 5 for further details.)

Remember that `\textsc` renders *lowercase* letters as small capitals. Uppercase letters are rendered as normal uppercase letters, so if you specify the short form in uppercase, you won't get small capitals unless you redefine `\glsxtrscfont` to convert its argument to lowercase. For example:

```
\renewcommand*{\glsxtrscfont}[1]{\textsc{\MakeLowercase{#1}}}
```

The “sm” styles all use

```
\glsxtrsmfont
```

```
\glsxtrsmfont{\text{<text>}}
```

This is defined as:

```
\newcommand*{\glsxtrsmfont}[1]{\textsmaller{#1}}
```

and

```
\glsxtrfirstsmfont
```

```
\glsxtrfirstsmfont{\text{<text>}}
```

which is defined as

```
\newcommand*{\glsxtrfirstsmfont}[1]{\glsxtrsmfont{#1}}
```

If you want to use this style, you must explicitly load the `relsize` package which defines the `\textsmaller` command. If you want to easily switch between the “sc” and “sm” styles, you may find it easier to redefine this command to convert to upper case:

```
\renewcommand*{\glsxtrsmfont}[1]{\textsmaller{\MakeTextUppercase{#1}}}
```

The default plural suffix for the short form is set to

```
\glsxtrsmsuffix
```

```
\glsxtrsmsuffix
```

This just does `\glspluralsuffix`.

The “em” styles all use

```
\glsabbrvemfont
```

```
\glsabbrvemfont{\text{}}
```

which is defined as:

```
\newcommand*\glsabbrvemfont[1]{\emph{#1}}
```

and

```
\glsfirstabbrvemfont
```

```
\glsfirstabbrvemfont{\text{}}
```

which is defined as:

```
\newcommand*\glsfirstabbrvemfont[1]{\glsabbrvemfont{#1}}
```

Some of the styles use

```
\glsxtrfullsep
```

```
\glsxtrfullsep{\label{}}
```

as a separator between the long and short forms. This is defined as a space by default, but may be changed as required. For example:

```
\renewcommand*\glsxtrfullsep[1]{\sim}
```

or

```
\renewcommand*\glsxtrfullsep[1]{\glsacspace{#1}}
```

The new naming scheme for abbreviation styles is as follows:

- $\langle field1 \rangle[-\langle modifier1 \rangle]-\langle field2 \rangle[-\langle modifier2 \rangle][-user]$

This is for the parenthetical styles. The $-\langle modifier \rangle$ parts may be omitted. These styles display $\langle field1 \rangle$ followed by $\langle field2 \rangle$ in parentheses. If $\langle field2 \rangle$ starts with “no” then the parenthetical element is omitted from the display style but is included in the inline style.

If the $-\langle modifier \rangle$ part is present, then the field has a font changing command applied to it.

If the $-user$ part is present, then the $user1$ value, if provided, is inserted into the parenthetical material. (The field used for the inserted material may be changed.)

Examples:

- **long-noshort-sc**: $\langle field1 \rangle$ is the long form, the short form is set in smallcaps but omitted in the display style.
- **long-em-short-em**: both the long form and the short form are emphasized. The short form is in parentheses.

- long-short-em: the short form is emphasized but not the long form. The short form is in parentheses.
- long-short-user: if the `user1` key has been set, this produces the style `\langle long \rangle (\langle short \rangle, \langle user1 \rangle)` otherwise it just produces `\langle long \rangle (\langle short \rangle)`.

- `\langle field1 \rangle [-\langle modifier1 \rangle]-[post]footnote`

The display style uses `\langle field1 \rangle` followed by a footnote with the other field in it. If `post` is present then the footnote is placed after the **link-text** using the post-link hook. The inline style does `\langle field1 \rangle` followed by the other field in parentheses.

If `-\langle modifier1 \rangle` is present, `\langle field1 \rangle` has a font-changing command applied to it.

Examples:

- short-footnote: short form in the text with the long form in the footnote.
- short-sc-postfootnote: short form in smallcaps with the long form in the footnote outside of the link-text.

Take care with the footnote styles. Remember that there are some situations where `\footnote` doesn't work.

- `\langle style \rangle-desc`

Like `\langle style \rangle` but the `description` key must be provided when defining abbreviations with this style.

Examples:

- short-long-desc: like short-long but requires a description.
- short-em-footnote-desc: like short-em-footnote but requires a description.

Not all combinations that fit the above syntax are provided. Pre-version 1.04 styles that didn't fit this naming scheme are either provided with a synonym (where the former name wasn't ambiguous) or provided with a deprecated synonym (where the former name was confusing). The deprecated style names generate a warning using:

```
\GlsXtrWarnDeprecatedAbbrStyle
```

```
\GlsXtrWarnDeprecatedAbbrStyle{\langle old-name \rangle}{\langle new-name \rangle}
```

where `\langle old-name \rangle` is the deprecated name and `\langle new-name \rangle` is the preferred name. You can suppress these warnings by redefining this command to do nothing.

3.4.1 Predefined Abbreviation Styles that Set the Regular Attribute

The following abbreviation styles set the regular attribute to “true” for all categories that have abbreviations defined with any of these styles.

short-nolong This only displays the short form on **first use**. The name is set to the short form.

The description is set to the long form. The inline full form displays $\langle short \rangle (\langle long \rangle)$. The long form on its own can be displayed through commands like `\glsxtrlong`.

short A synonym for `short-nolong`.

short-sc-nolong Like `short-nolong` but redefines `\glsabbrvfont` to use `\glsxtrscfont`.

short-sc A synonym for `short-sc-nolong`

short-sm-nolong Like `short-nolong` but redefines `\glsabbrvfont` to use `\glsxtrsmfont`.

short-sm A synonym for `short-sm-nolong`.

short-em-nolong Like `short-nolong` but redefines `\glsabbrvfont` to use `\glsxtremfont`.

short-em A synonym for `short-em-nolong`

short-nolong-desc Like the `short-nolong` style, but the name is set to the full form and the description must be supplied by the user. You may prefer to use the `short-nolong` style with the post-description hook set to display the long form and override the description key. (See the sample file `sample-acronym-desc.tex`.)

short-desc A synonym for `short-nolong-desc`.

short-sc-nolong-desc Like `short-nolong` but redefines `\glsabbrvfont` to use `\glsxtrscfont`.

short-sc-desc A synonym for `short-sc-nolong-desc`.

short-sm-nolong-desc Like `short-nolong-desc` but redefines `\glsabbrvfont` to use `\glsxtrsmfont`.

short-sm-desc A synonym for `short-sm-nolong-desc`.

short-em-nolong-desc Like `short-nolong-desc` but redefines `\glsabbrvfont` to use `\glsxtremfont`.

short-em-desc A synonym for `short-em-nolong-desc`.

long-noshort-desc This style only displays the long form, regardless of first or subsequent use of commands `\gls`. The short form may be accessed through commands like `\glsxtrshort`. The inline full form displays $\langle long \rangle (\langle short \rangle)$.

The name and sort keys are set to the long form and the description must be provided by the user. The predefined glossary styles won't display the short form. You can use the post-description hook to automatically append the short form to the description. The inline full form will display $\langle long \rangle (\langle short \rangle)$.

long-desc A synonym for `long-noshort-desc`.

long-noshort-sc-desc Like the `long-noshort-desc` style but the short form (accessed through commands like `\glsxtrshort`) use `\glsxtrscfont`. (This style was originally called `long-desc-sc`. Renamed in version 1.04, but original name retained as a deprecated synonym for backward-compatibility.)

long-noshort-sm-desc Like long-noshort-desc but redefines `\glsabbrvfont` to use `\glsxtrsmfont`.

(This style was originally called long-desc-sm. Renamed in version 1.04, but original name retained as a deprecated synonym for backward-compatibility.)

long-noshort-em-desc Like long-noshort-desc but redefines `\glsabbrvfont` to use `\glsxtrtremfont`.

The long form isn't emphasized. (This style was originally called long-desc-em. Renamed in version 1.04, but original name retained as a deprecated synonym for backward-compatibility.)

long-em-noshort-em-desc New to version 1.04, like long-noshort-desc but redefines `\glsabbrvfont` to use `\glsxtrtremfont`. The long form uses `\glsfirstlongemfont` and `\glslongemfont`.

long-noshort This style doesn't really make sense if you don't use the short form anywhere in the document, but is provided for completeness. This is like the long-noshort-desc style, but the name and sort keys are set to the short form and the description is set to the long form.

long A synonym for long-noshort

long-noshort-sc Like the long-noshort style but the short form (accessed through commands like `\glsxtrshort`) use `\glsxtrscfont`. (This style was originally called long-sc. Renamed in version 1.04, but original name retained as a deprecated synonym for backward-compatibility.)

long-noshort-sm Like long-noshort but redefines `\glsabbrvfont` to use `\glsxtrsmfont`.

(This style was originally called long-sm. Renamed in version 1.04, but original name retained as a deprecated synonym for backward-compatibility.)

long-noshort-em This style is like long-noshort but redefines `\glsabbrvfont` to use `\glsxtrtremfont`.

The long form isn't emphasized. (This style was originally called long-em. Renamed in version 1.04, but original name retained as a deprecated synonym for backward-compatibility.)

long-em-noshort-em New to version 1.04, this style is like long-noshort but redefines `\glsabbrvfont` to use `\glsxtrtremfont`, `\glsfirstlongfont` to use `\glsfirstlongemfont` and `\glslongfont` to use `\glslongemfont`. The short form isn't used by commands like `\gls`, but can be obtained using `\glsxtrshort`.

3.4.2 Predefined Abbreviation Styles that Don't Set the Regular Attribute

The following abbreviation styles will set the regular attribute to "false" if it has previously been set. If it hasn't already been set, it's left unset. Other attributes may also be set, depending on the style.

long-short On **first use**, this style uses the format $\langle long \rangle (\langle short \rangle)$. The inline and display full forms are the same. The name and sort keys are set to the short form. (The name key additionally includes the font command `\glsabbrvfont`.) The description is set to the

long form. The long and short forms are separated by `\glsxtrfullsep`. If you want to insert material within the parentheses (such as a translation), try the long-short-user style.

long-short-sc Like long-short but redefines `\glsabbrvfont` to use `\glsxtrscfont`.

long-short-sm Like long-short but redefines `\glsabbrvfont` to use `\glsxtrsmfont`.

long-short-em Like long-short but redefines `\glsabbrvfont` to use `\glsxtremfont`.

long-em-short-em New to version 1.04, this style is like long-short-em but redefines `\glsfirstlongfont` to use `\glsfirstlongemfont`.

long-short-user This style was introduced in version 1.04. It's like the long-short style but additional information can be inserted into the parenthetical material. This checks the value of the field given by

`\glsxtruserfield`

```
\glsxtruserfield
```

(which defaults to `useri`) using `\ifglshasfield` (provided by `glossaries`). If the field hasn't been set, the style behaves like the long-short style and produces $\langle long \rangle (\langle short \rangle)$ but if the field has been set, the contents of that field are inserted within the parentheses in the form $\langle long \rangle (\langle short \rangle, \langle field-value \rangle)$. The format is governed by

`\glsxtruserparen`

```
\glsxtruserparen{\text}{\label}
```

where $\langle text \rangle$ is the short form (for the long-short-user style) or the long form (for the short-long-user style). This command first inserts a space using `\glsxtrfullsep` and then the parenthetical content. The $\langle text \rangle$ argument includes the font formatting command, `\glsfirstabbrvfont{\text}` in the case of the long-short-user style and `\glsfirstlongfont{\text}` in the case of the short-long-user style.

For example:

```
\setabbreviationstyle[acronym]{long-short-user}
\newacronym{tug}{TUG}{\TeX\ User Group}
\newacronym
  [user1={German Speaking \TeX\ User Group}]
  {dante}{Deutschsprachige Anwendervereinigung \TeX\ e.V.}
```

On first use, `\gls{tug}` will appear as:

`\glsabbrvuserfont`

whereas `\gls{dante}` will appear as:

Deutschsprachige Anwendervereinigung TeX e.V (DANTE, German Speaking TeX User Group)

The short form is formatted according to

```
\glsabbrvuserfont
```

```
\glsabbrvuserfont{\text{}}
```

and the plural suffix is given by

```
\glsxtrusersuffix
```

```
\glsxtrusersuffix
```

These may be redefined as appropriate. For example, if you want a `smallcaps` style, you can just set these commands to those used by the `long-short-sc` style:

```
\renewcommand{\glsabbrvuserfont}[1]{\glsxtrscfont{#1}}
\renewcommand{\glsxtrusersuffix}{\glsxtrscsuffix}
```

long-short-desc On **first use**, this style uses the format $\langle long \rangle \langle short \rangle$. The inline and display full forms are the same. The name is set to the full form. The sort key is set to $\langle long \rangle \langle short \rangle$. Before version 1.04, this was incorrectly set to the short form. If you want to revert back to this you can redefine

```
\glsxtrlongshortdescsort
```

```
\glsxtrlongshortdescsort
```

For example:

```
\renewcommand*{\glsxtrlongshortdescsort}{\the\glsshorttok}
```

The description must be supplied by the user. The long and short forms are separated by `\glsxtrfullsep`.

long-short-sc-desc Like `long-short-desc` but redefines `\glsabbrvfont` to use `\glsxtrscfont`.

long-short-sm-desc Like `long-short-desc` but redefines `\glsabbrvfont` to use `\glsxtrsmfont`.

long-short-em-desc Like `long-short-desc` but redefines `\glsabbrvfont` to use `\glsxtemfont`.

long-em-short-em-desc New to version 1.04, this style is like `long-short-em-desc` but redefines `\glsfirstlongfont` to use `\glsfirstlongemfont`.

long-short-user-desc New to version 1.04, this style is like a cross between the long-short-desc style and the long-short-user style. The display and inline forms are as for long-short-user and the name key is as long-short-desc. The description key must be supplied in the optional argument of \newabbreviation (or \newacronym). The sort key is set to $\langle long \rangle$ ($\langle short \rangle$) as per the long-short-desc style.

short-long On first use, this style uses the format $\langle short \rangle$ ($\langle long \rangle$). The inline and display full forms are the same. The name and sort keys are set to the short form. The description is set to the long form. The short and long forms are separated by \glsxtrfullsep. If you want to insert material within the parentheses (such as a translation), try the short-long-user style.

short-sc-long Like short-long but redefines \glsabbrvfont to use \glsxtrscfont.

short-sm-long Like short-long but redefines \glsabbrvfont to use \glsxtrsmfont.

short-em-long Like short-long but redefines \glsabbrvfont to use \glsxtremfont.

short-em-long-em New to version 1.04, this style is like short-em-long but redefines \glsfirstlongfont to use \glsfirstlongemfont.

short-long-user New to version 1.04. This style is like the long-short-user style but with the long and short forms switched. The parenthetical material is governed by the same command \glsxtruserparen, but the first argument supplied to it is the long form instead of the short form.

short-long-desc On first use, this style uses the format $\langle short \rangle$ ($\langle long \rangle$). The inline and display full forms are the same. The name is set to the full form. The description must be supplied by the user. The short and long forms are separated by \glsxtrfullsep.

short-sc-long-desc Like short-long-desc but redefines \glsabbrvfont to use \glsxtrscfont.

short-sm-long-desc Like short-long-desc but redefines \glsabbrvfont to use \glsxtrsmfont.

short-em-long-desc Like short-long-desc but redefines \glsabbrvfont to use \glsxtremfont.

short-em-long-em-desc New to version 1.04, this style is like short-em-long-desc but redefines \glsfirstlongfont to use \glsfirstlongemfont.

short-long-user-desc New to version 1.04, this style is like a cross between the short-long-desc style and the short-long-user style. The display and inline forms are as for short-long-user and the name key is as short-long-desc. The description key must be supplied in the optional argument of \newabbreviation (or \newacronym).

short-footnote On first use, this style displays the short form with the long form as a footnote. This style automatically sets the nohyperfirst attribute to “true” for the supplied category, so the first use won’t be hyperlinked (but the footnote marker may be, if the hyperref package is used).

The inline full form uses the `<short>` (`<long>`) style. The name is set to the short form. The description is set to the long form.

footnote A synonym for short-footnote.

short-sc-footnote Like short-footnote but redefines `\glsabbrvfont` to use `\glsxtrscfont`.
(This style was originally called footnote-sc. Renamed in version 1.04, but original name retained as a deprecated synonym for backward-compatibility.)

short-sm-footnote Like short-footnote but redefines `\glsabbrvfont` to use `\glsxtrsmfont`.
(This style was originally called footnote-sm. Renamed in version 1.04, but original name retained as a deprecated synonym for backward-compatibility.)

short-em-footnote Like short-footnote but redefines `\glsabbrvfont` to use `\glsxtremfont`.
(This style was originally called footnote-em. Renamed in version 1.04, but original name retained as a deprecated synonym for backward-compatibility.)

short-postfootnote This is similar to the short-footnote style but doesn't modify the category attribute. Instead it changes `\glsxtrpostlink<category>` to insert the footnote after the **link-text** on **first use**. This will also defer the footnote until after any following punctuation character that's recognised by `\glsxtrifnextpunc`.

The inline full form uses the `<short>` (`<long>`) style. The name is set to the short form. The description is set to the long form. Note that this style will change `\glsxtrfull` (and its variants) so that it fakes non-first use. (Otherwise the footnote would appear after the inline form.)

postfootnote A synonym for short-postfootnote.

short-sc-postfootnote Like short-postfootnote but redefines `\glsabbrvfont` to use `\glsxtrscfont`.
(This style was originally called postfootnote-sc. Renamed in version 1.04, but original name retained as a deprecated synonym for backward-compatibility.)

short-sm-postfootnote Like short-postfootnote but redefines `\glsabbrvfont` to use `\glsxtrsmfont`.
(This style was originally called postfootnote-sm. Renamed in version 1.04, but original name retained as a deprecated synonym for backward-compatibility.)

short-em-postfootnote Like short-postfootnote but redefines `\glsabbrvfont` to use `\glsxtremfont`.
(This style was originally called postfootnote-em. Renamed in version 1.04, but original name retained as a deprecated synonym for backward-compatibility.)

3.5 Defining New Abbreviation Styles

New abbreviation styles may be defined using:

```
\newabbreviationstyle  
  {\newabbreviationstyle{\{name\}}{\{setup\}}{\{fmts\}}}
```

where `<name>` is the name of the new style (as used in the mandatory argument of `\setabbreviationstyle`). This is similar but not identical to the `glossaries` package's `\newacronymstyle` command.

You can't use styles defined by `\newacronymstyle` with `glossaries-extra` unless you have reverted `\newacronym` back to its generic definition from `glossaries` (using `\RestoreAcronyms`). The acronym styles from the `glossaries` package can't be used with abbreviations defined with `\newabbreviation`.

The `<setup>` argument deals with the way the entry is defined and may set attributes for the given abbreviation category. This argument should redefine

```
\CustomAbbreviationFields
```

```
\CustomAbbreviationFields
```

to set the entry fields including the name (defaults to the short form if omitted), sort, first, firstplural. Other fields may also be set, such as text, plural and description.

`\CustomAbbreviationFields` is expanded by `\newabbreviation` so take care to protect commands that shouldn't be expanded.

For example, the long-short style has the following in `<setup>`:

```
\renewcommand*{\CustomAbbreviationFields}{%
    name={\protect\glsabbrvfont{\the\glsshorttok}},%
    sort={\the\glsshorttok},%
    first={\protect\glsfirstlongfont{\the\glslongtok}%
        \protect\glsxtrfullsep{\the\glslabeltok}%
        (\protect\glsfirstabbrvfont{\the\glsshorttok})},%
    firstplural={\protect\glsfirstlongfont{\the\glslongpltok}%
        \protect\glsxtrfullsep{\the\glslabeltok}%
        (\protect\glsfirstabbrvfont{\the\glsshortpltok})},%
    plural={\protect\glsabbvfont{\the\glsshortpltok}},%
    description={\the\glslongtok}}%
```

Note that the `first` and `firstplural` are set even though they're not used by `\gls`.

The `<setup>` argument may also redefine

```
\GlsXtrPostNewAbbreviation
```

```
\GlsXtrPostNewAbbreviation
```

which can be used to assign attributes. (This will automatically be initialised to do nothing.)

For example, the short-footnote includes the following in `<setup>`:

```
\renewcommand*{\GlsXtrPostNewAbbreviation}{%
    \glssetattribute{\the\glslabeltok}{nohyperfirst}{true}%
    \glssetattribute{\the\glslabeltok}{regular}%
}
```

```

{%
  \glssetattribute{\the\glslabeltok}{regular}{false}%
}%
{%
}%
}

```

This sets the `nohyperfirst` attribute to “true”. It also unsets the `regular` attribute if it has previously been set. Note that the `nohyperfirst` attribute doesn’t get unset by other styles, so take care not to switch styles for the same category.

You can access the short, long, short plural and long plural values through the following token registers.

Short value (defined by `glossaries`):

`\glsshorttok`

`\glsshorttok`

Short plural value (defined by `glossaries-extra`):

`\glsshortpltok`

`\glsshortpltok`

(This may be the default value or, if provided, the value provided by the user through the `shortplural` key in the optional argument of `\newabbreviation`.)

Long value (defined by `glossaries`):

`\glslongtok`

`\glslongtok`

Long plural value (defined by `glossaries-extra`):

`\glslongpltok`

`\glslongpltok`

(This may be the default value or, if provided, the value provided by the user through the `longplural` key in the optional argument of `\newabbreviation`.)

There are two other registers available that are defined by `glossaries`:

`\glslabeltok`

`\glslabeltok`

which contains the entry’s label and

`\glskeylisttok`

`\glskeylisttok`

which contains the values provided in the optional argument of `\newabbreviation`.

Remember put `\the` in front of the register command as in the examples above. The category label can be accessed through the command (not a register):

```
\glscategorylabel
```

```
\glscategorylabel
```

This may be used inside the definition of `\GlsXtrPostNewAbbreviation`.

If you want to base a style on an existing style, you can use

```
\GlsXtrUseAbbrStyleSetup
```

```
\GlsXtrUseAbbrStyleSetup{\<name>}
```

where `\<name>` is the name of the existing style. For example, the `short-sc-footnote` and `short-sm-footnote` styles both simply use

```
\GlsXtrUseAbbrStyleSetup{short-footnote}
```

within `\<setup>`.

The `\<fmts>` argument deals with the way the entry is displayed in the document. This argument should redefine the following commands:

The default suffix for the plural short form (if not overridden by the `shortplural` key):

```
\abbrvpluralsuffix
```

```
\abbrvpluralsuffix
```

(Note that this isn't used for the plural long form, which just uses the regular `\glspluralsuffix`.)

The font used for the short form on **first use** or in the full forms:

```
\glsfirstabbrvfont
```

```
\glsfirstabbrvfont{\<text>}
```

The font used for the short form on subsequent use or through commands like `\glsxtrshort`:

```
\glsabbrvfont
```

```
\glsabbrvfont{\<text>}
```

The font used for the long form on first use or in the full forms:

```
\glsfirstlongfont
```

```
\glsfirstlongfont{\<text>}
```

The font used for the long form in commands like `\glsxtrlong` use:

```
\glslongfont
```

```
\glslongfont{\<text>}
```

Display full form singular no case-change (used by \gls on first use for abbreviations without the regular attribute set):

```
\glsxtrfullformat
```

```
\glsxtrfullformat{\label}{\insert}
```

Display full form singular first letter converted to upper case (used by \Gls on **first use** for abbreviations without the regular attribute set):

```
\Glsxtrfullformat
```

```
\Glsxtrfullformat{\label}{\insert}
```

Display full form plural no case-change (used by \glspl on first use for abbreviations without the regular attribute set):

```
\glsxtrfullplformat
```

```
\glsxtrfullplformat{\label}{\insert}
```

Display full form plural first letter converted to upper case (used by \Glspl on first use for abbreviations without the regular attribute set):

```
\Glsxtrfullplformat
```

```
\Glsxtrfullplformat{\label}{\insert}
```

In addition *fmts* may also redefine the following commands that govern the inline full formats. If the style doesn't redefine them, they will default to the same as the display full forms.

Inline singular no case-change (used by \glsentryfull, \glsxtrfull and \GLSxtrfull):

```
\glsxtrinlinefullformat
```

```
\glsxtrinlinefullformat{\label}{\insert}
```

Inline singular first letter converted to upper case (used by \Glsentryfull and \Glsxtrfull):

```
\Glsxtrinlinefullformat
```

```
\Glsxtrinlinefullformat{\label}{\insert}
```

Inline plural no case-change (used by \glsentryfullpl, \glsxtrfullpl and \GLSxtrfullpl):

```
\glsxtrinlinefullplformat
```

```
\glsxtrinlinefullplformat{\label}{\insert}
```

Inline plural first letter converted to upper case (used by \Glsentryfullpl and \Glsxtrfullpl):

```
\Glsxtrinlinefullplformat
```

```
\Glsxtrinlinefullplformat{\label}{\insert}
```

If you want to provide support for glossaries-accsupp use the following `\glsaccess<xxx>` commands (Section 9.2) within the definitions of `\glsxtrfullformat` etc instead of the analogous `\glsentry<xxx>` commands. (If you don't use glossaries-accsupp, they will just do the corresponding `\glsentry<xxx>` command.)

For example, the short-long style has the following in `\fmts`:

```
\renewcommand*{\abbrvpluralsuffix}{\glspluralsuffix}%
\renewcommand*{\glsabbrvfont}[1]{\glsabbrvdefaultfont{##1}}%
\renewcommand*{\glsfirstabbrvfont}[1]{\glsfirstabbrvdefaultfont{##1}}%
\renewcommand*{\glsfirstlongfont}[1]{\glsfirstlongdefaultfont{##1}}%
\renewcommand*{\glslongfont}[1]{\glslongdefaultfont{##1}}%
\renewcommand*{\glsxtrfullformat}[2]{%
    \glsfirstabbrvfont{\glsaccessshort{##1}}##2\glsxtrfullsep{##1}%
    (\glsfirstlongfont{\glsaccesslong{##1}})}%
}%
\renewcommand*{\glsxtrfullplformat}[2]{%
    \glsfirstabbrvfont{\glsaccessshortpl{##1}}##2\glsxtrfullsep{##1}%
    (\glsfirstlongfont{\glsaccesslongpl{##1}})}%
}%
\renewcommand*{\Glsxtrfullformat}[2]{%
    \glsfirstabbrvfont{\Glsaccessshort{##1}}##2\glsxtrfullsep{##1}%
    (\glsfirstlongfont{\glsaccesslong{##1}})}%
}%
\renewcommand*{\Glsxtrfullplformat}[2]{%
    \glsfirstabbrvfont{\Glsaccessshortpl{##1}}##2\glsxtrfullsep{##1}%
    (\glsfirstlongfont{\glsaccesslongpl{##1}})}%
}%
```

Since the inline full commands aren't redefined, they default to the same as the display versions.

If you want to base a style on an existing style, you can use

```
\GlsXtrUseAbbrStyleFmts
```

```
\GlsXtrUseAbbrStyleFmts{\name}
```

within `\fmts`, where `\name` is the name of the existing style. For example, the short-sc-long style has the following in `\fmts`:

```
\GlsXtrUseAbbrStyleFmts{short-long}%
\renewcommand*{\abbrvpluralsuffix}{\protect\glsxtrscsuffix}%
\renewcommand*{\glsabbrvfont}[1]{\glsxtrscfont{##1}}%
```

and the short-sm-long style has:

```
\GlsXtrUseAbbrStyleFmts{short-long-desc}%
\renewcommand*{\glsabbrvfont}[1]{\glsxtrsmfont{##1}}%
\renewcommand*{\abbrvpluralsuffix}{\protect\glsxtrsmsuffix}%
```

The simplest examples of creating a new style based on an existing style are the “em” styles, such as the short-em-long style, which is defined as:

```
\newabbreviationstyle
{short-em-long}{label}
{%
  \GlsXtrUseAbbrStyleSetup{short-long}%
}%
{%
  \GlsXtrUseAbbrStyleFmts{short-long}%
  \renewcommand*{\glsabbrvfont}[1]{\glsxtrmfont{##1}}%
}
```

4 Entries in Sectioning Titles, Headers, Captions and Contents

The glossaries user manual cautions against using commands like `\gls` in chapter or section titles. The principle problems are:

- if you have a table of contents, the **first use flag** will be unset in the contents rather than later in the document;
- if you have the location lists displayed in the glossary, unwanted locations will be added to it corresponding to the table of contents (if present) and every page that contains the entry in the page header (if the page style in use adds the chapter or section title to the header);
- if the page style in use adds the chapter or section title to the header and attempts to convert it to upper case, the entry label (in the argument of `\gls` etc) will be converted to upper case and the entry won't be recognised;
- if you use `hyperref`, commands like `\gls` can't be expanded to a simple string and only the label will appear in the PDF bookmark (with a warning from `hyperref`);
- if you use `hyperref`, you will end up with nested hyperlinks in the table of contents.

Similar problems can also occur with captions (except for the page header and bookmark issues).

To get around all these problems, the glossaries user manual recommends using the expandable non-hyperlink commands, such as `\glsentrytext` (for regular entries) or `\glsentryshort` (for abbreviations). This is the simplest solution, but doesn't allow for special formatting that's applied to the entry through commands like `\gls` or `\glsxtrshort`. This means that if, for example, you are using one of the abbreviation styles that uses `\textsc` then the short form displayed with `\glsentryshort` won't use small caps. If you only have one abbreviation style in use, you can explicitly enclose `\glsentryshort{<label>}` in the argument of `\glsabbrvfont`, like this:

```
\chapter{A Chapter about \glsabbrvfont{\glsentryshort{html}}}
```

Or, if you are using `hyperref`:

```
\chapter{A Chapter about  
\texorpdfstring{\glsabbrvfont{\glsentryshort{html}}}{\glsentryshort{html}}}
```

Since this is a bit cumbersome, you might want to define a new command to do this for you. However, if you have mixed styles this won't work as commands like `\gls` and `\glsxtrshort` redefine `\glsabbrvfont` to match the entry's style before displaying it. In this case, the above example doesn't take into account the shifting definitions of `\glsabbrvfont` and will use whatever happens to be the last abbreviation style in use. More complicated solutions interfere with the upper casing used by the standard page styles that display the chapter or section title in the page header using `\MakeUppercase`.

The glossaries-extra package tries to resolve this by modifying `\markright` and `\markboth`. If you don't like this change, you can restore their former definitions using

```
\glsxtrRevertMarks
```

```
\glsxtrRevertMarks
```

In this case, you'll have to use the glossaries manual's recommendations of either simply using `\glsentryshort` (as above) or use the sectioning command's option argument to provide an alternative for the table of contents and page header. For example:

```
\chapter[A Chapter about \glsentryshort{html}]{A Chapter about \gls{html}}
```

If you don't revert the mark commands back with `\glsxtrRevertMarks`, you can use the commands described below in the argument of sectioning commands. You can still use them even if the mark commands have been reverted, but only where they don't conflict with the page style.

The commands listed below all use `\texorpdfstring` if hyperref has been loaded so that the expandable non-formatted version is added to the PDF bookmarks. Note that since the commands that convert the first letter to upper case aren't expandable, the non-case-changing version is used for the bookmarks.

These commands essentially behave as though you have used `\glsxtrshort` (or equivalent) with the options `noindex` and `hyper=false`. The text produced won't be converted to upper case in the page headings by default. If you want the text converted to upper case you need to set the `headuc` attribute to "true" for the appropriate category.

If you use one of the `\textsc` styles, be aware that the default fonts don't provide bold small-caps or italic small-caps. This means that if the chapter or section title style uses bold, this may override the small-caps setting, in which case the abbreviation will just appear as lower case bold. If the heading style uses italic, the abbreviation may appear in upright small-caps, *even if you have set the headuc attribute* since the all-captions form still uses `\glsabbrvfont`. You may want to consider using the `slantsc` package in this case.

Display the short form:

```
\glsfmtshort
```

```
\glsfmtshort{\label}
```

Display the plural short form:

```
\glsfmtshortpl
```

```
\glsfmtshortpl{\label}
```

First letter upper case singular short form:

```
\Glsfmtshort
```

```
\Glsfmtshort{\label}
```

(No case-change applied to PDF bookmarks.)

First letter upper case plural short form:

```
\Glsfmtshortpl
```

```
\Glsfmtshortpl{\label}
```

(No case-change applied to PDF bookmarks.)

Display the long form:

```
\glsfmtlong
```

```
\glsfmtlong{\label}
```

Display the plural long form:

```
\glsfmtlongpl
```

```
\glsfmtlongpl{\label}
```

First letter upper case singular long form:

```
\Glsfmtlong
```

```
\Glsfmtlong{\label}
```

(No case-change applied to PDF bookmarks.)

First letter upper case plural long form:

```
\Glsfmtlongpl
```

```
\Glsfmtlongpl{\label}
```

(No case-change applied to PDF bookmarks.)

There are similar commands for the full form, but note that these use the *inline* full form, which may be different from the full form used by \gls.

Display the full form:

```
\glsfmtfull
```

```
\glsfmtfull{\label}
```

Display the plural full form:

\glsfmtfullpl

\glsfmtfullpl{\label}

First letter upper case singular full form:

\Glsfmtfull

\Glsfmtfull{\label}

(No case-change applied to PDF bookmarks.)

First letter upper case plural full form:

\glsfmtfullpl

\glsfmtfullpl{\label}

(No case-change applied to PDF bookmarks.)

There are also equivalent commands for the value of the text field:

\glsfmttext

\glsfmttext{\label}

First letter converted to upper case:

\Glsfmttext

\Glsfmttext{\label}

(No case-change applied to PDF bookmarks.)

The plural equivalents:

\glsfmtplural

\glsfmtplural{\label}

and

\Glsfmtplural

\Glsfmtplural{\label}

Similarly for the value of the first field:

\glsfmtfirst

\glsfmtfirst{\label}

First letter converted to upper case:

```
\Glsfmtfirst
```

```
\Glsfmtfirst{\label}
```

(No case-change applied to PDF bookmarks.)

The plural equivalents:

```
\glsfmtfirstpl
```

```
\glsfmtfirstpl{\label}
```

and

```
\Glsfmtfirstpl
```

```
\Glsfmtfirstpl{\label}
```

5 Categories

Each entry defined by `\newglossaryentry` (or commands that internally use it such as `\newabbreviation`) is assigned a category through the `category` key. You may add any category that you like, but since the category is a label used in the creation of some control sequences, avoid problematic characters within the category label. (So take care if you have babel shorthands on that make some characters active.)

The use of categories can give you more control over the way entries are displayed in the text or glossary.

The default category assumed by `\newglossaryentry` is labelled general. Abbreviations defined with `\newabbreviation` have the category set to abbreviation by default. Abbreviations defined with `\newacronym` have the category set to acronym by default.

Additionally, if you have enabled `\newterm` with the index package option that command will set the category to index by default. If you have enabled `\glsxtrnewsymbol` with the symbols package option, that command will set the category to symbol. If you have enabled `\glsxtrnewnumber` with the numbers package option, that command will set the category to number.

You can obtain the category label for a given entry using

```
\glscategory
```

```
\glscategory{\label}
```

This is equivalent to commands like `\glsentryname` and so may be used in an expandable context. No error is generated if the entry doesn't exist.

You can test the category for a given entry using

```
\glsifcategory
```

```
\glsifcategory{\entry-label}{\category-label}{\true part}{\false part}
```

This is equivalent to

```
\ifglsfieldeq{\entry-label}{category}{\category-label}{\true part}{\false part}
```

so any restrictions that apply to `\ifglsfieldeq` also apply to `\glsifcategory`.

Each category may have a set of attributes. For example, the general and acronym categories have the attribute `regular` set to "true" to indicate that all entries with either of those categories are regular entries (as opposed to abbreviations). This attribute is accessed by `\glsentryfmt` to determine whether to use `\glsgenentryfmt` or `\glsxtrgenabbrvfmt`.

Other attributes recognised by glossaries-extra are:

nohyperfirst When using commands like `\gls` this will automatically suppress the hyperlink on **first use** for entries with a category that has this attribute set to “true”. (This settings can be overridden by explicitly setting the `hyper` key on or off in the optional argument of commands like `\gls`.)

nohyper When using commands like `\gls` this will automatically suppress the hyperlink for entries with a category that has this attribute set to “true”. (This settings can be overridden by explicitly setting the `hyper` key on or off in the optional argument of commands like `\gls`.)

indexonlyfirst This is similar to the `indexonlyfirst` package option but only for entries that have a category with this attribute set to “true”.

discardperiod If set to “true”, the `post-link-text` hook will discard a full stop (period) that follows *non-plural* commands like `\gls` or `\glstext`. (Provided for entries such as abbreviations that end with a full stop.)

Note that this can cause a problem if you access a field that doesn’t end with a full stop. For example:

```
\newabbreviation
  [user1={German Speaking \TeX\ User Group}]
  {dante}{DANTE e.V.}{Deutschsprachige Anwendervereinigung \TeX\
e.V.}
```

Here the short and long fields end with a full stop, but the `user1` field doesn’t. The simplest solution in this situation is to put the sentence terminator in the final optional argument. For example:

```
\glsuseri{dante} [.]
```

This will bring the punctuation character inside the link-text and it won’t be discarded.

pluraldiscardperiod If this attribute is set to “true” *and* the `discardperiod` attribute is set to “true”, this will behave as above for the plural commands like `\glsp{}` or `\glspl{}`.

retainfirstuseperiod If this attribute is set to “true” then the full stop won’t be discarded for **first use** instances, even if `discardperiod` or `pluraldiscardperiod` are set. This is useful for `<short> (<long>)` abbreviation styles where only the short form has a trailing full stop..

insertdots If this attribute is set to “true” any entry defined using `\newabbreviation` will automatically have full stops (periods) inserted after each letter. The entry will be defined with those dots present as though they had been present in the `<short>` argument of `\newabbreviation` (rather than inserting them every time the entry is used). The short plural form defaults to the new dotted version of the original `<short>` form with the plural suffix appended.

If you explicitly override the short plural using the `shortplural` key, you must explicitly insert the dots yourself (since there's no way for the code to determine if the plural has a suffix that shouldn't be followed by a dot).

This attribute is best used with the `discardperiod` attribute set to “true”.

aposplural If this attribute is set to “true”, `\newabbreviation` will insert an apostrophe (‘) before the plural suffix for the *short* plural form (unless explicitly overridden with the `shortplural` key). The long plural form is unaffected by this setting.

noshortplural If this attribute is set to “true”, `\newabbreviation` won’t append the plural suffix for the short plural form. This means the short and `shortplural` values will be the same unless explicitly overridden. *The `aposplural` attribute trumps the `noshortplural` attribute.*

headuc If this attribute is set to “true”, commands like `\glsfmtshort` will use the upper case version in the page headers.

tagging If this attribute is set to “true”, the tagging command defined by `\GlsXtrEnableInitialTagging` will be activated to use `\glsxtrtagfont` in the glossary (see Section 3.1).

entrycount Unlike the above attributes, this attribute isn’t boolean but instead must be an integer value and is used in combination with `\glsenableentrycount` (see Section 2.3). Leave blank or undefined for categories that shouldn’t have this facility enabled. The value of this attribute is used by `\glsxtrifcounttrigger` to determine how commands such as `\cgls` should behave.

With glossaries, commands like `\cgls` use `\cglsformat` only if the previous usage count for that entry was equal to 1. With glossaries-extra the test is now for entries that have the `entrycount` attribute set and where the previous usage count for that entry is less than or equal to the value of that attribute.

glossdesc The `\glossentrydesc` command (used in the predefined glossary styles) is modified by glossaries-extra to check for this attribute. If the attribute is set to “firstuc”, the first letter of the description will be converted to upper case (using `\Glsentrydesc`). If the attribute is set to “title”, the title casing command `\capitalisewords` (provided by `mfirstuc`) is used on the name. Any other values of this attribute are ignored.

glossdescfont (New to version 1.04) In addition to the above, the modified `\glossentrydesc` command also checks this attribute. If set, it should be the name of a control sequence (without the leading backslash) that takes one argument. This control sequence will be applied to the description text. For example:

```
\glssetcategoryattribute{general}{glossdescfont}{emph}
```

glossname As `glossdesc` but applies to `\glossentryname`. Additionally, if this attribute is set to “uc” the name is converted to all capitals.

indexname If set, the `\glsxtrpostnamehook` hook used at the end of `\glossentynname` will index the entry using `\index`. See Section 7 for further details.

glossnamefont (New to version 1.04) In addition to the above, the modified `\glossentryname` command also checks this attribute. If set, it should be the name of a control sequence (without the leading backslash) that takes one argument. This control sequence will be applied to the name text. For example:

```
\glssetcategoryattribute{general}{glossnamefont}{\emph}
```

Note that this overrides `\glsnamefont` which will only be used if this attribute hasn't been set.

Remember that glossary styles may additionally apply a font change, such as the list styles which put the name in the optional argument of `\item`.

dualindex If set, whenever a glossary entry has information written to the external glossary file through commands like `\gls` and `\glsadd`, a corresponding line will be written to the indexing file using `\index`. See Section 7 for further details.

An attribute can be set using:

```
\glssetcategoryattribute
```

```
\glssetcategoryattribute{\<category-label\>}{\<attribute-label\>}{\<value\>}
```

where `\<category-label\>` is the category label, `\<attribute-label\>` is the attribute label and `\<value\>` is the new value for the attribute.

There is a shortcut version to set the regular attribute to "true":

```
\glssetregularcategory
```

```
\glssetregularcategory{\<category-label\>}
```

If you need to lookup the category label for a particular entry, you can use the shortcut command:

```
\glssetattribute
```

```
\glssetattribute{\<entry-label\>}{\<attribute-label\>}{\<value\>}
```

This uses `\glssetcategoryattribute` with `\glscategory` to set the attribute. Note that this will affect all other entries that share this entry's category.

You can fetch the value of an attribute for a particular category using:

```
\glsgetcategoryattribute
```

```
\glsgetcategoryattribute{\<category-label\>}{\<attribute-label\>}
```

Again there is a shortcut if you need to lookup the category label for a given entry:

```
\glsgetattribute
```

```
\glsgetattribute{\<entry-label\>}{\<attribute-label\>}
```

You can test if an attribute has been assigned to a given category using:

```
\glshascategoryattribute
```

```
\glshascategoryattribute{\<category-label\>}{\<attribute-label\>}{{\<true code\>}}{\<false code\>}
```

This uses etoolbox's \ifcsvoid and does *<true code>* if the attribute has been set and isn't blank and isn't \relax. The shortcut if you need to lookup the category label from an entry is:

```
\glshasattribute
```

```
\glshasattribute{\<entry-label\>}{\<attribute-label\>}{{\<true code\>}}{\<false code\>}
```

You can test the value of an attribute for a particular category using:

```
\glsifcategoryattribute
```

```
\glsifcategoryattribute{\<category-label\>}{\<attribute-label\>}{{\<value\>}}{\<true-part\>}{\<false-part\>}
```

This tests if the attribute (given by *<attribute-label>*) for the category (given by *<category-label>*) is set and equal to *<value>*. If true, *<true-part>* is done. If the attribute isn't set or is set but isn't equal to *<value>*, *<false part>* is done.

For example:

```
\glsifcategoryattribute{general}{nohyper}{true}{NO HYPER}{HYPER}
```

This does "NO HYPER" if the general category has the nohyper attribute set to true otherwise it does "HYPER".

With boolean-style attributes like nohyper, make sure you always test for true not false in case the attribute hasn't been set.

Again there's a shortcut if you need to lookup the category label from a particular entry:

```
\glsifattribute
```

```
\glsifattribute{\<entry-label\>}{\<attribute-label\>}{{\<value\>}}{\<true-part\>}{\<false-part\>}
```

There's also a shortcut to determine if a particular category has the regular attribute set to "true":

```
\glsifregularcategory
```

```
\glsifregularcategory{\<category-label\>}{{\<true-part\>}}{\<false-part\>}
```

Alternatively, if you need to lookup the category for a particular entry:

```
\glsifregular
```

```
\glsifregular{\<entry-label\>}{\<true-part\>}{\<false-part\>}
```

Note that if the regular attribute hasn't be set, the above do *\<false-part\>*. There are also reverse commands that test if the regular attribute has been set to "false":

```
\glsifnotregularcategory
```

```
\glsifnotregularcategory{\<category-label\>}{\<true-part\>}{\<false-part\>}
```

or for a particular entry:

```
\glsifnotregular
```

```
\glsifnotregular{\<entry-label\>}{\<true-part\>}{\<false-part\>}
```

Again, if the regular attribute hasn't been set, the above do *\<false-part\>*, so these reverse commands aren't logically opposite in the strict sense.

You can iterate through all entries with a given category using:

```
\glsforeachincategory[\<glossary-labels\>]{\<category-label\>}  
\<glossary-cs\>{\<label-cs\>}{\<body\>}
```

This iterates through all entries in the glossaries identified by the comma-separated list *\<glossary-labels\>* that have the category given by *\<category-label\>* and performs *\<body\>* for each match. Within *\<body\>*, you can use *\<glossary-cs\>* and *\<label-cs\>* (which much be control sequences) to access the current glossary and entry label. If *\<glossary-labels\>* is omitted, all glossaries are assumed.

Similarly, you can iterate through all entries that have a category with a given attribute using:

```
\glsforeachwithattribute
```

```
\glsforeachwithattribute[\<glossary-labels\>]{\<attribute-label\>}  
\<attribute-value\>{\<glossary-cs\>}{\<label-cs\>}{\<body\>}
```

This will do *\<body\>* for each entry that has a category with the attribute *\<attribute-label\>* set to *\<attribute-value\>*. The remaining arguments are as the previous command.

You can change the category for a particular entry using the standard glossary field changing commands, such as `\glsfielddef`. Alternatively, you can use

```
\glsxtrsetcategory
```

```
\glsxtrsetcategory{\<entry-labels\>}{\<category-label\>}
```

This will change the category to $\langle \text{category-label} \rangle$ for each entry listed in the comma-separated list $\langle \text{entry-labels} \rangle$. This command uses `\glsfieldxdef` so it will expand $\langle \text{category-label} \rangle$ and make the change global.

You can also change the category for all entries with a glossary or glossaries using:

```
\glsxtrsetcategoryforall  
  \glsxtrsetcategoryforall{\langle glossary-labels \rangle}{\langle category-label \rangle}
```

where $\langle \text{glossary-labels} \rangle$ is a comma-separated list of glossary labels.

6 Entry Counting

As mentioned in Section 2.3, glossaries-extra modifies the `\glsenableentrycount` command to allow for the `entrycount` attribute. This means that you not only need to enable entry counting with `\glsenableentrycount`, but you also need to set the appropriate attribute (see Section 5). Remember that entry counting only counts the number of times an entry is used by commands that change the **first use flag**.

With glossaries-extra, you may use `\cglss` instead of `\gls` even if you haven't enabled entry counting. You will only get a warning if you use `\glsenableentrycount` without setting the `entrycount` attribute. (With glossaries, commands like `\cglss` will generate a warning if `\glsenableentrycount` hasn't been used.) The abbreviation shortcut `\ab` uses `\cglss` (see Section 3.3) unlike the acronym shortcut `\ac` which uses `\gls`.

All upper case versions (not provided by glossaries) are also available:

`\cGLS`

```
\cGLS[<options>]{<label>}[<insert>]
```

and

`\cGLSp1`

```
\cGLSp1[<options>]{<label>}[<insert>]
```

These are analogous to `\cglss` and `\cglsp1` but they use

`\cGLSformat`

```
\cGLSformat{<label>}{<insert>}
```

and

`\cGLSp1format`

```
\cGLSp1format{<label>}{<insert>}
```

which convert the analogous `\cglssformat` and `\cglsp1format` to upper case.

Just using glossaries:

```
\documentclass{article}  
\usepackage{glossaries}  
\makeglossaries
```

```
\glsenableentrycount  
\newacronym{html}{HTML}{hypertext markup language}  
\newacronym{xml}{XML}{extensible markup language}
```

```
\begin{document}
```

Used once: \cglshtml.

Used twice: \cglshxml and \cglshxml.

```
\printglossaries
```

```
\end{document}
```

If you switch to glossaries-extra you must set the entrycount attribute:

```
\documentclass{article}
```

```
\usepackage{glossaries-extra}
```

```
\makeglossaries
```

```
\glsenableentrycount
```

```
\glssetcategoryattribute{abbreviation}{entrycount}{1}
```

```
\newabbreviation{html}{HTML}{hypertext markup language}  
\newabbreviation{xml}{XML}{extensible markup language}
```

```
\begin{document}
```

Used once: \cglshhtml.

Used twice: \cglshxml and \cglshxml.

```
\printglossaries
```

```
\end{document}
```

When activated with \glsenableentrycount, commands such as \cglsh now use

```
\glsxtrifcounttrigger
```

```
\glsxtrifcounttrigger{\label}{\triggercode}{\normalcode}
```

to determine if the entry trips the entry count trigger. The *\triggercode* uses commands like \cglshformat and unsets the **first use flag**. The *\normalcode* is the code that would ordinarily be performed by whatever the equivalent command is (for example, \cglsh will use \cglshformat in *\triggercode* but the usual \gls behaviour in *\normalcode*).

The default definition is:

```
\newcommand*{\glsxtrifcounttrigger}[3]{%
  \glshasattribute{#1}{entrycount}%
  {%
    \ifnum\glsentryprevcount{#1}>\glsgetattribute{#1}{entrycount}\relax
      #3%
    \else
      #2%
    \fi
  }%
  {#3}%
}
```

This means that if an entry is assigned to a category that has the entrycount attribute then the *<trigger code>* will be used if the previous count value (the number of times the entry was used on the last run) is greater than the value of the attribute.

For example, to trigger normal use if the previous count value is greater than four:

```
\glssetcategoryattribute{abbreviation}{entrycount}{4}
```

There is a convenient command provided to enable entry counting, set the entrycount attribute and redefine \gls, etc to use \cglss etc:

```
\GlsXtrEnableEntryCounting
```

```
\GlsXtrEnableEntryCounting{{categories}}{value}
```

The first argument *<categories>* is a comma-separated list of categories. For each category, the entrycount attribute is set to *<value>*. In addition, this does:

```
\renewcommand*{\gls}{\cglss}%
\renewcommand*{\Gls}{\cGls}%
\renewcommand*{\glsp}{\cglsp}%
\renewcommand*{\Glsp}{\cGlsp}%
\renewcommand*{\GLS}{\cGLS}%
\renewcommand*{\GLSp}{\cGLSp}
```

This makes it easier to enable entry-counting on existing documents.

If you use \GlsXtrEnableEntryCounting more than once, subsequent uses will just set the entrycount attribute for each listed category.

The above example document can then become:

```
\documentclass{article}

\usepackage{glossaries-extra}

\makeglossaries

\GlsXtrEnableEntryCounting{abbreviation}{1}
```

```

\newabbreviation{html}{HTML}{hypertext markup language}
\newabbreviation{xml}{XML}{extensible markup language}

\begin{document}

Used once: \gls{html}.

Used twice: \gls{xml} and \gls{xml}.

\printglossaries

\end{document}

```

The standard entry-counting function described above counts the number of times an entry has been marked as used throughout the document. (The reset commands will reset the total back to zero.) If you prefer to count per sectional-unit, you can use

\GlsXtrEnableEntryUnitCounting

\GlsXtrEnableEntryUnitCounting{\<categories>}{\<value>}{\<counter-name>}

where *<categories>* is a comma-separated list of categories to which this feature should be applied, *<value>* is the trigger value and *<counter-name>* is the name of the counter used by the sectional unit.

Due to the asynchronous nature of TeX's output routine, discrepancies will occur in page spanning paragraphs if you use the page counter.

Note that you can't use both the document-wide counting and the per-unit counting in the same document.

The counter value is used as part of a label, which means that \the<counter-name> needs to be expandable. Since hyperref also has a similar requirement and provides \theH<counter-name> as an expandable alternative, glossaries-extra will use \theH<counter-name> if it exists otherwise it will use \the<counter-name>.

The per-unit counting function uses two attributes: entrycount (as before) and unitcount (the name of the counter).

Both the original document-wide counting mechanism and the per-unit counting mechanism provide a command that can be used to access the current count value for this run:

\glsentrycurrcount

\glsentrycurrcount{\<label>}

and the final value from the previous run:

\glsentryprevcount

\glsentryprevcount{\<label>}

In the case of the per-unit counting, this is the final value *for the current unit*. In both commands `\glsentryprevtotalcount` and `\glsentryprevmaxcount` the argument `{<label>}` is the entry's label.

The per-unit counting mechanism additionally provides:

```
\glsentryprevtotalcount
```

```
\glsentryprevtotalcount{{<label>}}
```

which gives the sum of all the per-unit totals from the previous run for the entry given by `{<label>}`, and

```
\glsentryprevmaxcount
```

```
\glsentryprevmaxcount{{<label>}}
```

which gives the maximum per-unit total from the previous run.

The above two commands are unavailable for the document-wide counting.

Example of per-unit counting, where the unit is the chapter:

```
\documentclass{report}
\usepackage{glossaries-extra}

\GlsXtrEnableEntryUnitCounting{abbreviation}{2}{chapter}

\makeglossaries

\newabbreviation{html}{HTML}{hypertext markup language}
\newabbreviation{css}{CSS}{cascading style sheet}

\newglossaryentry{sample}{name={sample},description={sample}}

\begin{document}
\chapter{Sample}
```

Used once: `\gls{html}`.

Used three times: `\gls{css}` and `\gls{css}` and `\gls{css}`.

Used once: `\gls{sample}`.

```
\chapter{Another Sample}
```

Used once: `\gls{css}`.

Used twice: `\gls{html}` and `\gls{html}`.

```
\printglossaries
\end{document}
```

In this document, the `css` entry is used three times in the first chapter. This is more than the trigger value of 2, so `\gls{css}` is expanded on **first use** with the short form used on

subsequent use, and the `css` entries in that chapter are added to the glossary. In the second chapter, the `css` entry is only used once, which trips the suppression trigger, so in that chapter, the long form is used and `\gls{css}` doesn't get a line added to the glossary file.

The `html` is used a total of three times, but the expansion and indexing suppression trigger is tripped in both chapters because the per-unit total (1 for the first chapter and 2 for the second chapter) is less than or equal to the trigger value.

The `sample` entry has only been used once, but it doesn't trip the indexing suppression because it's in the general category, which hasn't been listed in `\GlsXtrEnableEntryUnitCounting`.

The per-unit entry counting can be used for other purposes. In the following example document the trigger value is set to zero, which means the index suppression won't be triggered, but the unit entry count is used to automatically suppress the hyperlink for commands like `\gls` by modifying the hook

```
\glslinkcheckfirsthyperhook
\glslinkcheckfirsthyperhook
```

which is used at the end of the macro the determines whether or not to suppress the hyperlink.

```
\documentclass{article}

\usepackage[colorlinks]{hyperref}
\usepackage{glossaries-extra}

\makeglossaries

\GlsXtrEnableEntryUnitCounting{general}{0}{page}

\newglossaryentry{sample}{name={sample},description={an example}}


\renewcommand*\glslinkcheckfirsthyperhook{%
  \ifnum\glsentrycurrcount\glslabel>0
    \setkeys{glslink}{hyper=false}%
  \fi
}

\begin{document}

A \gls{sample} entry.
Next use: \gls{sample}.

\newpage

Next page: \gls{sample}.
Again: \gls{sample}.

\printglossaries
```

```
\end{document}
```

This only produces a hyperlink for the first instance of \gls{sample} on each page.

The earlier warning about using the page counter still applies. If the first instance of \gls occurs at the top of the page within a paragraph that started on the previous page, then the count will continue from the previous page.

7 Auto-Indexing

It's possible that you may also want a normal index as well as the glossary, and you may want entries to automatically be added to the index (as in this document). There are two attributes that govern this: `indexname` and `dualindex`.

The `\glsxtrpostnamehook` macro, used at the end of `\glossentryname` and `\Glossentryname`, checks the `indexname` attribute for the category associated with that entry. Since `\glossentryname` is used in the default glossary styles, this makes a convenient way of automatically indexing each entry name at its location in the glossary without fiddling around with the value of the `name` key.

The internal macro used by the `glossaries` package to write the information to the external glossary file is modified to check for the `dualindex` attribute.

In both cases, the indexing is done through

```
\glsxtrdoautoindexname  
  \glsxtrdoautoindexname{\label}{\attribute-label}
```

This uses the standard `\index` command with the sort value taken from the entry's `sort` key and the actual value set to `\glsentryname{\label}`. If the value of the attribute given by `\attribute-label` is “true”, no `encap` will be added, otherwise the `encap` will be the attribute value. For example:

```
\glssetcategoryattribute{general}{indexname}{textbf}
```

will set the `encap` to `textbf` which will display the relevant page number in bold whereas

```
\glssetcategoryattribute{general}{dualindex}{true}
```

won't apply any formatting to the page number in the index.

The location used in the index will always be the page number not the counter used in the glossary. (Unless some other loaded package has modified the definition of `\index` to use something else.)

By default the `format` key won't be used with the `dualindex` attribute. You can allow the `format` key to override the attribute value by using the preamble-only command:

```
\GlsXtrEnableIndexFormatOverride  
  \GlsXtrEnableIndexFormatOverride
```

If you use this command and `hyperref` has been loaded, then the `theindex` environment will be modified to redefine `\glshypernumber` to allow formats that use that command.

The `dualindex` attribute will still be used on subsequent use even if the `indexonlyfirst` attribute (or `indexonlyfirst` package option) is set. However, the `dualindex` attribute will honour the `noindex` key.

The `\glsxtrdoautoindexname` command will attempt to escape any of `\makeindex`'s special characters, but there may be special cases where it fails, so take care. This assumes the default `makeindex` actual, level, quote and encap values (unless any of the commands `\actualchar`, `\levelchar`, `\quotechar` or `\encapchar` have been defined before `glossaries-extra` is loaded).

If this isn't the case, you can use the following preamble-only commands to set the correct characters.

Be very careful of possible shifting category codes!

`\GlsXtrSetActualChar`

`\GlsXtrSetActualChar{\<char>}`

Set the actual character to `<char>`.

`\GlsXtrSetLevelChar`

`\GlsXtrSetLevelChar{\<char>}`

Set the level character to `<char>`.

`\GlsXtrSetEscChar`

`\GlsXtrSetEscChar{\<char>}`

Set the escape (quote) character to `<char>`.

`\GlsXtrSetEncapChar`

`\GlsXtrSetEncapChar{\<char>}`

Set the encap character to `<char>`.

8 On-the-Fly Document Definitions

The commands described here may superficially look like `\index{<word>}`, but they behave rather differently. If you want to use `\index` then just use `\index`.

The glossaries package advises against defining entries in the document environment. As mentioned in Section 1.2 above, this ability is disabled by default with `glossaries-extra` but can be enabled using the `docdefs` package options.

Although this can be problematic, the `glossaries-extra` package provides a way of defining and using entries within the document environment without the tricks used with the `docdefs` option. *There are limitations with this approach, so take care with it.* This function is disabled by default, but can be enabled using the preamble-only command:

```
\GlsXtrEnableOnTheFly
```

```
\GlsXtrEnableOnTheFly
```

When used, this defines the commands described below.

The commands `\glsxtr`, `\glsxtrpl`, `\Glsxtr` and `\Glsxtrpl` can't be used after the glossaries have been displayed (through `\printglossary` etc). It's best not to mix these commands with the standard glossary commands, such as `\gls` or there may be unexpected results.

```
\glsxtr
```

```
\glsxtr[<gls-options>] [<dfn-options>] {<label>}
```

If an entry with the label `<label>` has already been defined, this just does `\gls[<gls-options>] {<label>}`. If `<label>` hasn't been defined, this will define the entry using:

```
\newglossaryentry{<label>}{name={<label>}  
category=\glsxtrcat,  
description={\nopostdesc},  
<dfn-options>}
```

The `<label>` must contain any non-expandable commands, such as formatting commands or problematic characters. If the term requires any of these, they must be omitted from the `<label>` and placed in the `name` key must be provided in the optional argument `<dfn-options>`.

The second optional argument $\langle dfn-options \rangle$ should be empty if the entry has already been defined, since it's too late for them. If it's not empty, a warning will be generated with

```
\GlsXtrWarning
```

```
\GlsXtrWarning{\langle dfn-options \rangle}{\langle label \rangle}
```

For example, this warning will be generated on the second instance of `\glsxtr` below:

```
\glsxtr[] [plural=geese]{goose}
... later
\glsxtr[] [plural=geese]{goose}
```

If you are considering doing something like:

```
\newcommand*\{\goose\}{\glsxtr[] [plural=geese]{goose}}
\renewcommand*\{\GlsXtrWarning\}[2]{}
... later
\goose\ some more text here
```

then don't bother. It's simpler and less problematic to just define the entries in the preamble with `\newglossaryentry` and then use `\gls` in the document.

There are plural and case-changing alternatives to `\glsxtr`:

```
\glsxtrpl
```

```
\glsxtrpl[\langle gls-options \rangle][\langle dfn-options \rangle]{\langle label \rangle}
```

This is like `\glsxtr` but uses `\glsp{1}` instead of `\gls`.

```
\Glsxtr
```

```
\Glsxtr[\langle gls-options \rangle][\langle dfn-options \rangle]{\langle label \rangle}
```

This is like `\glsxtr` but uses `\Gls` instead of `\gls`.

```
\Glsxtrpl
```

```
\Glsxtrpl[\langle gls-options \rangle][\langle dfn-options \rangle]{\langle label \rangle}
```

This is like `\glsxtr` but uses `\Glspl{1}` instead of `\gls`.

If you use UTF-8 and don't want the inconvenient of needing to use an ASCII-only label, then it's better to use Xe^LT_EX or Lua^LT_EX instead of L^TE_X (or pdfL^TE_X). If you really desperately want to use UTF-8 entry labels without switching to Xe^LT_EX or Lua^LT_EX then there is a starred version of `\GlsXtrEnableOnTheFly` that allows you to use UTF-8 characters in $\langle label \rangle$, but it's experimental and may not work in some cases.

If you use the starred version of `\GlsXtrEnableOnTheFly` don't use any commands in $\langle label \rangle$, even if they expand to just text.

9 Supplemental Packages

The glossaries bundle provides additional support packages `glossaries-prefix` (for prefixing) and `glossaries-accsupp` (for accessibility support). These packages aren't automatically loaded.

9.1 Prefixes or Determiners

If prefixing is required, you can simply load `glossaries-prefix` after `glossaries-extra`. For example:

```
\documentclass{article}

\usepackage{glossaries-extra}
\usepackage{glossaries-prefix}

\makeglossaries

\newabbreviation
  [prefix={an\space},
  prefixfirst={a~}]
  {svm}{SVM}{support vector machine}

\begin{document}

First use: \pgls{svm}.
Next use: \pgls{svm}.

\printglossaries

\end{document}
```

9.2 Accessibility Support

The `glossaries-accsupp` needs to be loaded before `glossaries-extra` or through the `accsupp` package option:

```
\usepackage[accsupp]{glossaries-extra}
```

If you don't load `glossaries-accsupp` or you load `glossaries-accsupp` after `glossaries-extra` the new `\glsaccess<xxx>` commands described below will simply be equivalent to the corresponding `\glsentry<xxx>` commands.

The following `\glsaccess{xxx}` commands add accessibility information wrapped around the corresponding `\glsentry{xxx}` commands. There is no check for existence of the entry nor do any of these commands add formatting, hyperlinks or indexing information.

`\glsaccessname`

```
\glsaccessname{\label}
```

This displays the value of the name field for the entry identified by `\label`.

If the `glossaries-accsupp` package isn't loaded, this is simply defined as:

```
\newcommand*{\glsaccessname}[1]{\glsentryname{\#1}}
```

otherwise it's defined as:

```
\newcommand*{\glsaccessname}[1]{%
  \glsnameaccessdisplay
  {%
    \glsentryname{\#1}%
  }%
  {\#1}%
}
```

(`\glsnameaccessdisplay` is defined by the `glossaries-accsupp` package.) The first letter upper case version is:

`\Glsaccessname`

```
\Glsaccessname{\label}
```

Without the `glossaries-accsupp` package this is just defined as:

```
\newcommand*{\Glsaccessname}[1]{\Glsentryname{\#1}}
```

With the `glossaries-accsupp` package this is defined as:

```
\newcommand*{\Glsaccessname}[1]{%
  \glsnameaccessdisplay
  {%
    \Glsentryname{\#1}%
  }%
  {\#1}%
}
```

The following commands are all defined in an analogous manner.

`\glsaccesstext`

```
\glsaccesstext{\label}
```

This displays the value of the text field.

`\Glsaccesstext`

```
\Glsaccesstext{\label}
```

This displays the value of the text field with the first letter converted to upper case.

```
\glsaccessplural
```

```
\glsaccessplural{\label}
```

This displays the value of the plural field.

```
\Glsaccessplural
```

```
\Glsaccessplural{\label}
```

This displays the value of the plural field with the first letter converted to upper case.

```
\glsaccessfirst
```

```
\glsaccessfirst{\label}
```

This displays the value of the first field.

```
\Glsaccessfirst
```

```
\Glsaccessfirst{\label}
```

This displays the value of the first field with the first letter converted to upper case.

```
\glsaccessfirstplural
```

```
\glsaccessfirstplural{\label}
```

This displays the value of the firstplural field.

```
\Glsaccessfirstplural
```

```
\Glsaccessfirstplural{\label}
```

This displays the value of the firstplural field with the first letter converted to upper case.

```
\glsaccesssymbol
```

```
\glsaccesssymbol{\label}
```

This displays the value of the symbol field.

```
\Glsaccesssymbol
```

```
\Glsaccesssymbol{\label}
```

This displays the value of the symbol field with the first letter converted to upper case.

```
\glsaccesssymbolplural
```

```
\glsaccesssymbolplural{\label}
```

This displays the value of the symbolplural field.

```
\Glsaccesssymbolplural
```

```
\Glsaccesssymbolplural{\label}
```

This displays the value of the symbolplural field with the first letter converted to upper case.

```
\glsaccessdesc
```

```
\glsaccessdesc{\label}
```

This displays the value of the desc field.

```
\Glsaccessdesc
```

```
\Glsaccessdesc{\label}
```

This displays the value of the desc field with the first letter converted to upper case.

```
\glsaccessdescplural
```

```
\glsaccessdescplural{\label}
```

This displays the value of the descplural field.

```
\Glsaccessdescplural
```

```
\Glsaccessdescplural{\label}
```

This displays the value of the descplural field with the first letter converted to upper case.

```
\glsaccessshort
```

```
\glsaccessshort{\label}
```

This displays the value of the short field.

```
\Glsaccessshort
```

```
\Glsaccessshort{\label}
```

This displays the value of the short field with the first letter converted to upper case.

```
\glsaccessshortpl
```

```
\glsaccessshortpl{\label}
```

This displays the value of the shortplural field.

```
\Glsaccessshortpl
```

```
\Glsaccessshortpl{\label}
```

This displays the value of the shortplural field with the first letter converted to upper case.

```
\glsaccesslong
```

```
\glsaccesslong{\label}
```

This displays the value of the long field.

```
\Glsaccesslong
```

```
\Glsaccesslong{\label}
```

This displays the value of the long field with the first letter converted to upper case.

```
\glsaccesslongpl
```

```
\glsaccesslongpl{\label}
```

This displays the value of the longplural field.

```
\Glsaccesslongpl
```

```
\Glsaccesslongpl{\label}
```

This displays the value of the longplural field with the first letter converted to upper case.

10 Sample Files

The following sample files are provided with this package:

sample.tex Simple sample file that uses one of the dummy files provided by the glossaries package for testing.

sample-mixture.tex General entries, acronyms and initialisms all treated differently.

sample-name-font Categories and attributes are used to customize the way different entries appear.

sample-abbrev.tex General abbreviations.

sample-acronym.tex Acronyms aren't initialisms and don't expand on **first use**.

sample-acronym-desc.tex Acronyms that have a separate long form and description.

sample-crossref.tex Unused entries that have been cross-referenced automatically are added at the end of the document.

sample-indexhook.tex Use the index hook to track which entries have been indexed (and therefore find out which ones haven't been indexed).

sample-footnote.tex Footnote abbreviation style that moves the footnote marker outside of the hyperlink generated by \gls and moves it after certain punctuation characters for neatness.

sample-undef.tex Warn on undefined entries instead of generating an error.

sample-mixed-abbrev-styles.tex Different abbreviation styles for different entries.

sample-initialisms.tex Automatically insert dots into initialisms.

sample-postdot.tex Another initialisms example.

sample-postlink.tex Automatically inserting text after the **link-text** produced by commands like \gls (outside of hyperlink, if present).

sample-header.tex Using entries in section/chapter headings.

sample-autoindex.tex Using the dualindex and indexname attributes to automatically add glossary entries to the index (in addition to the glossary **location list**).

sample-autoindex-hyp.tex As previous but uses hyperref.

sample-nested.tex Using `\gls` within the value of the name key.

sample-entrycount.tex Enable entry-use counting (only index if used more than n times).

sample-unitentrycount.tex Enable use of per-unit entry-use counting.

sample-pages.tex Insert “page” or “pages” before the location list.

sample-onelink.tex Using the per-unit entry counting to only have one hyperlink per entry per page.

sample-altmodifier.tex Set the default options for commands like `\gls` and add an alternative modifier.

sample-alttree.tex Uses the `glossaries-extra-stylemods` package with the `alttree` style (see Section 2.6.3).

sample-alttree-sym.tex Another `alttree` example that measures the symbol widths.

sample-alttree-marginpar.tex Another `alttree` example that puts the **number list** in the margin.

sample-onthefly.tex Using on-the-fly commands. Terms with accents must have the name key explicitly set.

sample-onthefly-xetex.tex Using on-the-fly commands with X_ET_EX. Terms with UTF-8 characters don't need to have the name key explicitly set. Terms that contain commands must have the name key explicitly set with the commands removed from the label.

sample-onthefly-utf8.tex Tries to emulate the previous sample file for use with L_AT_EX through the starred version of `\GlsXtrEnableOnTheFly`. This is a bit iffy and may not always work. Terms that contain commands must have the name key explicitly set with the commands removed from the label.

sample-accsupp.tex Integrate `glossaries-accsupp`.

sample-prefix.tex Integrate `glossaries-prefix`.

11 Multi-Lingual Support

There's only one command provided by `glossaries-extra` that you're likely to want to change in your document and that's `\abbreviationsname` (Section 1.2) if you use the `abbreviations` package option to automatically create the glossary labelled abbreviations. If this command doesn't already exist, it will be defined to "Abbreviations" if `babel` hasn't been loaded, otherwise it will be defined as `\acronymname` (provided by `glossaries`).

You can redefine it in the usual way. For example:

```
\renewcommand*{\abbreviationsname}{List of Abbreviations}
```

Or using `babel` or `polyglossia` captions hook:

```
\appto\captionsenglish{%
  \renewcommand*{\abbreviationsname}{List of Abbreviations}%
}
```

Alternatively you can use the `title` key when you print the list of abbreviations. For example:

```
\printabbreviations[title={List of Abbreviations}]
```

or

```
\printglossary[type=abbreviations,title={List of Abbreviations}]
```

The other fixed text commands are the diagnostic messages, which shouldn't appear in the final draft of your document.

The `glossaries-extra` package has the facility to load language modules if they exist, but won't warn if they don't.

If you want to write your own language module, you just need to create a file called `glossariesxtr-lang.ldf`, where *lang* is the language name (see the `tracklang` package). For example, `glossariesxtr-french.ldf`.

The simplest code for this file is:

```
\ProvidesGlossariesExtraLang{french}[2015/12/09 v1.0]

\newcommand*{\glossariesxtrcaptionsfrench}{%
  \def\abbreviationsname{Abr\textit{e}viations}%
}
\glossariesxtrcaptionsfrench

\ifcsdef{captions\CurrentTrackedDialect}%
{%
  \csappto{captions\CurrentTrackedDialect}{%
```

```

{%
  \glossariesxtrcaptionsfrench
}%
{%
}%
{%
  \ifcsdef{captions\CurrentTrackedLanguage}
  {%
    \csappto{captions\CurrentTrackedLanguage}{%
    {%
      \glossariesxtrcaptionsfrench
    }%
  }%
  {%
  }%
  {%
    \glossariesxtrcaptionsfrench
  }
}

```

You can adapt this for other languages by replacing all instances of the language identifier `french` and the translated text `Abr\'eviations` as appropriate. This `.ldf` file then needs to be put somewhere on TeX's path so that it can be found by `glossaries-extra`. You might also want to consider uploading it to CTAN so that it can be useful to others. (Please don't send it to me. I already have more packages than I am able to maintain.)

If you additionally want to provide translations for the diagnostic messages used when a glossary is missing, you need to redefine the following commands:

```
\GlsXtrNoGlsWarningHead
\GlsXtrNoGlsWarningHead{\label}{file}
```

This produces the following text in English:

This document is incomplete. The external file associated with the glossary '`\label`' (which should be called `file`) hasn't been created.

```
\GlsXtrNoGlsWarningEmptyStart
\GlsXtrNoGlsWarningEmptyStart
```

This produces the following text in English:

This has probably happened because there are no entries defined in this glossary.

```
\GlsXtrNoGlsWarningEmptyMain
\GlsXtrNoGlsWarningEmptyMain
```

This produces the following text in English:

If you don't want this glossary, add `nomain` to your package option list when you load `glossaries-extra.sty`. For example:

```
\GlsXtrNoGlsWarningEmptyNotMain
```

```
  \GlsXtrNoGlsWarningEmptyNotMain{\label}
```

This produces the following text in English:

Did you forget to use `type=\label` when you defined your entries? If you tried to load entries into this glossary with `\loadglsentries` did you remember to use `[\label]` as the optional argument? If you did, check that the definitions in the file you loaded all had the type set to `\glsdefaulttype`.

```
\GlsXtrNoGlsWarningCheckFile
```

```
  \GlsXtrNoGlsWarningCheckFile{\file}
```

This produces the following text in English:

Check the contents of the file `\file`. If it's empty, that means you haven't indexed any of your entries in this glossary (using commands like `\gls` or `\glsadd`) so this list can't be generated. If the file isn't empty, the document build process hasn't been completed.

```
\GlsXtrNoGlsWarningMisMatch
```

```
  \GlsXtrNoGlsWarningMisMatch
```

This produces the following text in English:

You need to either replace `\makenoidxglossaries` with `\makeglossaries` or replace `\printglossary` (or `\printglossaries`) with `\printnoidxglossary` (or `\printnoidxglossaries`) and then rebuild this document.

```
\GlsXtrNoGlsWarningNoOut
```

```
  \GlsXtrNoGlsWarningNoOut{\file}
```

This produces the following text in English:

The file `\file` doesn't exist. This most likely means you haven't used `\makeglossaries` or you have used `\nofiles`. If this is just a draft version of the document, you can suppress this message using the `nomissingglstext` package option.

```
\GlsXtrNoGlsWarningTail
```

```
  \GlsXtrNoGlsWarningTail
```

This produces the following text in English:

This message will be removed once the problem has been fixed.

```
\GlsXtrNoGlsWarningBuildInfo
```

```
  \GlsXtrNoGlsWarningBuildInfo
```

This is advice on how to generate the glossary files. See the documented code (`glossaries-extra-code.pdf`) for further details.

```
\GlsXtrNoGlsWarningAutoMake
```

```
  \GlsXtrNoGlsWarningAutoMake{\langle label \rangle}
```

This is the message produced when the `automake` option is used, but the document needs a rerun or the shell escape setting doesn't permit the execution of the external application. This command also generates a warning in the transcript file. See the documented code for further details.

Glossary

entry location The location of the entry in the document. This defaults to the page number on which the entry appears. An entry may have multiple locations.

first use The first time a glossary entry is used (from the start of the document or after a reset) with one of the following commands: \gls, \Gls, \GLS, \glspl, \Glsp1, \GLSp1 or \glsdisp.

first use flag A conditional that determines whether or not the entry has been used according to the rules of **first use**.

first use text The text that is displayed on first use, which is governed by the first and first-plural keys of \newglossaryentry. (May be overridden by \glsdisp.)

link-text The text produced by commands such as \gls. It may or may not have a hyperlink to the glossary.

location list A list of **entry locations**. See **number list**.

makeglossaries A custom designed Perl script interface provided with the glossaries package to run **xindy** or **makeindex** according to the document settings.

makeindex An indexing application.

number list A list of entry locations (also called a location list). The number list can be suppressed using the **nonumberlist** package option.

xindy An flexible indexing application with multilingual support written in Perl.

Index

A

\ab	36, 65
abbreviation styles (deprecated):	
footnote-em	46
footnote-sc	46
footnote-sm	46
long-desc-em	42
long-desc-sc	41
long-desc-sm	42
long-em	42
long-sc	42
long-sm	42
postfootnote-em	46
postfootnote-sc	46
postfootnote-sm	46
abbreviation styles:	
footnote	46
long	42
long-desc	41
long-em-noshort-em	42
long-em-noshort-em-desc	42
long-em-short-em	39, 43
long-em-short-em-desc	44
long-noshort	33, 42
long-noshort-desc	21, 41, 42
long-noshort-em	42
long-noshort-em-desc	42
long-noshort-sc	39, 42
long-noshort-sc-desc	41
long-noshort-sm	42
long-noshort-sm-desc	42
long-short	21, 30, 32, 42, 43, 47
long-short-desc	44, 45
long-short-em	40, 43
long-short-em-desc	44
long-short-sc	30, 43, 44
long-short-sc-desc	44
long-short-sm	43
long-short-sm-desc	44
long-short-user	40, 43, 45
long-short-user-desc	45
postfootnote	46
short	41
short-desc	41
short-em	41
short-em-desc	41
short-em-footnote	40, 46
short-em-footnote-desc	40
short-em-long	45, 52
short-em-long-desc	45
short-em-long-em	45
short-em-long-em-desc	45
short-em-nolong	41
short-em-nolong-desc	41
short-em-postfootnote	46
short-footnote	32, 40, 45–47
short-long	29, 32, 40, 45, 51
short-long-desc	40, 45
short-long-user	43, 45
short-long-user-desc	45
short-nolong	29, 32–34, 41
short-nolong-desc	41
short-postfootnote	16, 17, 46
short-sc	41
short-sc-desc	41
short-sc-footnote	46, 49
short-sc-long	45, 51
short-sc-long-desc	45
short-sc-nolong	41
short-sc-nolong-desc	41
short-sc-postfootnote	40, 46
short-sm	41
short-sm-desc	41
short-sm-footnote	49
short-sm-long	45, 51
short-sm-long-desc	45
short-sm-nolong	41
short-sm-nolong-desc	41
short-sm-postfootnote	46
\abbreviationsname	9, 83

\abrvpluralsuffix	49	glossname	23, 60
\abp	36	glossnamefont	61
\ac	65	headuc	54, 60
\acrfull	34	indexname	23, 61, 72, 81
\acrlong	21, 34	indexonlyfirst	12, 59, 73
acronym styles (glossaries):		insertdots	29, 59
long-sp-short	22	nohyper	59, 62
\acronymfont	33	nohyperfirst	45, 48, 59
\acronymtype	10, 29	noshortplural	29, 38, 60
\acrshort	21, 33, 34	pluraldiscardperiod	59
\actualchar	73	regular	14, 15, 33, 37, 40, 42, 48, 50, 58, 61–63
\AF	36	retainfirstuseperiod	59
\Af	36	tagging	32, 33, 60
\af	36	unitcount	68
\AFP	36	\cGLS	65
\Afp	36	\cgls	36, 60, 65–67
\afp	36	\cGLSformat	65
\AL	36	\cGLSpl	65
\Al	36	\cglspl	36
\al	36	\cGLSplformat	65
\ALP	36	\CustomAbbreviationFields	47
\Alp	36		
\alp	36		
amsgen package	1	D	
\AS	36	datatool-base package	1
\As	36	document (environment)	8, 12, 13, 74
\as	36		
\ASP	36	E	
\Asp	36	\eglssetwidest	26
\asp	36	\encapchar	73
		entry location	87, 87
		environments:	
		document	8, 12, 13, 74
		theglossary	4
		theindex	72
		etoolbox package	1, 62
		F	
		first use	12, 14, 16, 18–22, 29, 30, 32, 34,
			37, 41, 42, 44–46, 49, 50, 59, 69, 81, 87, 87
		first use flag	16, 53, 65, 66, 87
		first use text	87, 94
		fontenc package	37
		\footnote	40
		G	
		glossaries-accsupp package	7, 51, 76, 77, 82
		glossaries-extra-stylemods package	7, 25, 82
		glossaries-prefix package	76, 82
		\glossariesextrasetup	7, 11

glossary styles:			
almtree	25, 26, 28, 82	\glscategorylabel	49
inline	25	\glscurrententrylabel	23, 23
long3col	25	\glsdesc	20
glossary-inline package	25	\glsdisp	87
glossary-tree package	25, 26	\glsdoifexists	12
\glossentrydesc	23, 60	\glsenableentrycount	17, 60, 65
\Glossentryname	23, 72	\glsentrycurrcount	68
\glossentryname	23, 60, 61, 72	\Glsentrydesc	60
\glossentryname	61	\glsentryfmt	14
\glossentryname	61	\Glsentryfull	50
\GLS	18, 87	\glsentryfull	50
\Gls	18, 21, 50, 87	\Glsentryfullpl	50
\gls	14, 16–18, 20, 21, 29, 32, 33, 37, 41, 42, 50, 59, 61, 65, 67, 70, 82, 87	\glsentryfullpl	50
\glsabbrvdefaultfont	30	\glsentrylong	18, 21
\glsabbrvemfont	38	\glsentrynumberlist	27
\glsabbrvfont	21, 22, 30, 31, 49	\glsentryprevcount	68
\glsabbrvuserfont	44	\glsentryprevmaxcount	69
\Glsaccessdesc	79	\glsentryprevtotalcount	69
\glsaccessdesc	79	\glsentryshort	18, 20, 21, 30, 53
\Glsaccessdescplural	79	\glsentrytext	7, 20, 53
\glsaccessdescplural	79	\glsfielddef	63
\glsaccessfirst	78	\glsfieldxdef	64
\glsaccessfirst	78	\glsFindWidestAnyName	26
\Glsaccessfirst	78	\glsFindWidestAnyNameLocation	28
\Glsaccessfirstplural	78	\glsFindWidestAnyNameSymbol	27
\glsaccessfirstplural	78	\glsFindWidestAnyNameSymbolLocation	27
\Glsaccesslong	80	\glsFindWidestLevelTwo	27
\glsaccesslong	80	\glsFindWidestTopLevelName	26
\Glsaccesslongpl	80	\glsFindWidestUsedAnyName	26
\glsaccesslongpl	80	\glsFindWidestUsedAnyNameLocation	27
\Glsaccessname	77	\glsFindWidestUsedAnyNameSymbol	27
\glsaccessname	77	\glsFindWidestUsedAnyNameSymbolLocation	27
\Glsaccessplural	78	\glsFindWidestUsedLevelTwo	27
\glsaccessplural	78	\glsFindWidestUsedTopLevelName	26
\Glsaccessshort	79	\glsfirst	14, 16, 37
\Glsaccessshortpl	79	\glsfirstabbrvdefaultfont	30
\glsaccessshortpl	79	\glsfirstabbrvemfont	39
\Glsaccesssymbol	78	\glsfirstabbrvfont	22, 30, 49
\glsaccesssymbol	78	\glsfirstlongdefaultfont	31
\Glsaccesssymbolplural	79	\glsfirstlongemfont	31, 42–45
\glsaccesssymbolplural	78	\glsfirstlongfont	30, 49
\Glsaccesstext	77	\Glsfmtfirst	57
\glsaccesstext	7, 77	\glsfmtfirst	56
\glsacspace	22	\Glsfmtfirstpl	57
\glsacspacemax	22	\glsfmtfirstpl	57
\glsadd	12, 61	\Glsfmtfull	56
\glsaddall	12	\glsfmtfull	55
\glscategory	58	\Glsfmtfullpl	56

\glsfmtfullpl	56	\glspluralsuffix	38
\Glsfmtlong	55	\glssetattribute	61
\glsfmtlong	55	\glssetcategoryattribute	61
\Glsfmtlongpl	55	\glssetregularcategory	61
\glsfmtlongpl	55	\glsshortpltok	48
\Glsfmtplural	56	\glsshorttok	48
\glsfmtplural	56	\Glstext	21
\Glsfmtshort	55	\glstext	20, 21
\glsfmtshort	54, 60	\glstextformat	14
\Glsfmtshortpl	55	\glstextup	38
\glsfmtshortpl	55	\Glsxtr	75
\Glsfmttext	56	\Glsxtr	74
\glsfmttext	56	\glsxtrabbrvtype	10
\glsforeachwithattribute	63	\glsxtraddallcrossrefs	13
\glsgenentry	14	\glsxtrAltTreeIndent	28
\glsgenentryfmt	14, 37	\glsxtralttreeInit	28
\glsgetattribute	62	\glsxtralttreeSubSymbolDescLocation	28
\glsgetcategoryattribute	61	\glsxtralttreeSymbolDescLocation	28
\glsgetwidestname	26	\glsxtrdoautoindexname	23, 72
\glsgetwidestsubname	26	\glsxtrdowrglossaryhook	12
\glshasattribute	62	\glsxtrremfont	41–46
\glshascategoryattribute	62	\GlsXtrEnableEntryCounting	67
\glshypernumber	72	\GlsXtrEnableEntryUnitCounting	68
\glsifattribute	62	\GlsXtrEnableIndexFormatOverride	72
\glsifcategory	58	\GlsXtrEnableInitialTagging	32, 60
\glsifcategoryattribute	62	\GlsXtrEnableOnTheFly	74, 82
\glsifnotregular	63	\GlsXtrEnablePreLocationTag	24
\glsifnotregularcategory	63	\glsxtrfirstsfont	37
\glsifregular	63	\glsxtrfirstsmfont	38
\glsifregularcategory	62	\GlsXtrFormatLocationList	24
\glskeylisttok	48	\GLSxtrfull	35, 36, 50
\glslabeltok	48	\Glsxtrfull	34, 36, 50
\glslink	14, 17	\glsxtrfull	14, 16, 32, 34, 36, 50
\glslink options		\Glsxtrfullformat	50
format	72	\glsxtrfullformat	37, 50
hyper	59	\GLSxtrfullpl	36, 36, 50
hyper=false	54	\Glsxtrfullpl	35, 36, 50
noindex	12, 54, 73	\glsxtrfullpl	35, 36, 50
\glslinkcheckfirsthyperhook	70	\Glsxtrfullplformat	50
\glslistdottedwidth	22	\glsxtrfullplformat	50
\glslongdefaultfont	31	\glsxtrfullsep	39
\glslongemfont	31, 42	\glsxtrgenabbrvfmt	14, 37
\glslongfont	30, 49	\glsxtrifcounttrigger	60, 66
\glslongpltok	48	\glsxtrifnextpunc	46
\glslongtok	48	\glsxtrifwasfirstuse	16
\glsnameaccessdisplay	77	\Glsxtrinlinefullformat	50
\GLSpl	87	\glsxtrinlinefullformat	50
\Gspl	50, 87	\Glsxtrinlinefullplformat	50
\gspel	50, 87	\glsxtrinlinefullplformat	50

\glsxtrinsertinsidetrue	31	\glsxtrsmfont	38, 41–46
\GLSxtrlong	36	\glsxtrsmsuffix	38
\Glsxtrlong	34, 35, 36	\glsxtrtagfont	32, 60
\glsxtrlong	14, 21, 32, 34, 36, 41	\GlsXtrUseAbbrStyleFmts	51
\GLSxtrlongpl	35, 36	\GlsXtrUseAbbrStyleSetup	49
\Glsxtrlongpl	35, 36	\glsxtruserfield	43
\glsxtrlongpl	35, 36	\glsxtruserparen	43, 45
\glsxtrlongshortdescsort	44	\glsxtrusersuffix	44
\glsxtrnewnumber	10, 11, 58	\glsxtrusesee	13
\glsxtrnewsymbol	10, 11, 58	\glsxtruseseeformat	13
\GlsXtrNoGlsWarningAutoMake	86	\GlsXtrWarnDeprecatedAbbrStyle	40
\GlsXtrNoGlsWarningBuildInfo	86	\GlsXtrWarning	75
\GlsXtrNoGlsWarningCheckFile	85		
\GlsXtrNoGlsWarningEmptyMain	84		
\GlsXtrNoGlsWarningEmptyNotMain	85	hyperref package	20, 45, 53, 54, 68, 72, 81
\GlsXtrNoGlsWarningEmptyStart	84		
\GlsXtrNoGlsWarningHead	84		
\GlsXtrNoGlsWarningMisMatch	85	\ifglsfieldeq	58
\GlsXtrNoGlsWarningNoOut	85	\ifglshasfield	43
\GlsXtrNoGlsWarningTail	85	\ifglsused	16
\Glsxtrpl	75	\index	61, 72
\glsxtrpl	75		
\glsxtrpostdescription	23		
\glsxtrpostlink	15	\levelchar	73
\glsxtrpostlinkAddDescOnFirstUse	16	link-text	14–17, 20, 40, 46, 59, 81, 87
\glsxtrpostlinkAddSymbolOnFirstUse	16	location list	81, 87
\glsxtrpostlink <category></category>	15, 46		
\glsxtrpostlinkendsentence	15		
\glsxtrpostlinkhook	15	makeglossaries	6, 87
\glsxtrpostnamehook	23, 72	\makeglossaries	12
\GlsXtrPostNewAbbreviation	47	makeindex	6, 8, 73, 87, 87
\glsxtrregularfont	14	\makeindex	73
\glsxtrRevertMarks	54	\makenoidxglossaries	11
\glsxtrscfont	37, 41–46	\MakeUppercase	54
\glsxtrscsuffix	37	\markboth	54
\GlsXtrSetActualChar	73	\markright	54
\GlsXtrSetAltModifier	17	memoir class	5
\glsxtrsetcategory	63	mfistuc package	1, 60
\glsxtrsetcategoryforall	64		
\GlsXtrSetDefaultGlsOpts	17		
\GlsXtrSetEncapChar	73	\newabbr	36
\GlsXtrSetEscChar	73	\newabbreviation	29, 36, 48, 58–60
\GlsXtrSetLevelChar	73	\newabbreviationstyle	46
\GLSxtrshort	36	\newacronym	10, 12, 22, 29, 47
\Glsxtrshort	34, 36	\newacronymstyle	29, 47
\glsxtrshort	14, 21, 29, 34, 36, 37, 41, 42, 49	\newentry	11
\GLSxtrshortpl	35, 36	\newglossaryentry	8, 11, 58, 75, 87
\Glsxtrshortpl	35, 36	\newglossaryentry options	
\glsxtrshortpl	35, 36	category	12, 29, 58
		desc	79

descplural	79
description	40–42, 44–47
first	14, 18, 37, 47, 56, 78, 87
firstplural	14, 47, 78, 87
long	32, 37, 59, 80
longplural	32, 48, 80
name	18, 41, 42, 44–47, 72, 74, 77, 82
parent	26
plural	14, 47, 78
see	9, 12, 13
short	14, 32, 37, 59, 60, 79
shortplural	29, 32, 38, 48, 49, 60, 79, 80
sort	8, 10, 18, 21, 41, 42, 44, 45, 47, 72
symbol	78
symbolplural	79
text	14, 18, 37, 47, 56, 77, 78
user1	39, 40, 59
\newnum	11
\newsym	11
\newterm	12, 58
number list	13, 17, 24, 27, 28, 82, 87, 87
P	
package options:	
abbreviations	9–11, 83
accsupp	7, 76
acronym	10
acronymlists	10
automake	86
docdef	8, 11
false	8
restricted	8, 9
true	8, 9
docdefs	74
index	12, 58
indexcrossrefs	9, 13
indexonlyfirst	12, 59, 73
nomain	6
nomissingglistext	9
nonumberlist	13, 24, 87
nopostdot	24, 25
false	4, 23
true	4
noredefwarn	
false	4
true	4
notree	25
numbers	10, 11, 58
seeautonumberlist	13
Q	
page (counter)	68, 71
polyglossia package	83
\printabbreviations	9
\printglossaries	6
\printglossary	6, 74
\printglossary options	
title	83
R	
relsize package	38
\RestoreAcronyms	22, 29, 47
S	
\setabbreviationstyle	33, 47
\setacronymstyle	29, 33
\setupglossaries	7
slantsc package	54
T	
\texorpdfstring	54
textcase package	1
\textsc	37, 53, 54
\textsmaller	20, 38

the glossary (environment)	4	X	
the index (environment)	72	xfor package	1
tracklang package	1, 83	\xglssetwidest	26
translator package	4	xindy	6, 8, 87, 87
U		xkeyval package	1
\underline	32		