

glossaries.sty v 1.2: L^AT_EX 2 _{ε} Package to Assist Generating Glossaries

Nicola L.C. Talbot

School of Computing Sciences
University of East Anglia
Norwich, Norfolk
NR4 7TJ, United Kingdom.

<http://theoval.cmp.uea.ac.uk/~nlct/>

16th April 2009

Contents

1	Introduction	3
1.1	Sample Documents	4
1.2	Multi-Lingual Support	9
1.2.1	Changing the Fixed Names	10
1.3	Generating the Associated Glossary Files	12
1.3.1	Using the makeglossaries Perl Script	13
1.3.2	Using xindy explicitly	13
1.3.3	Using makeindex explicitly	14
1.4	Troubleshooting	15
2	A Quick Guide For The Impatient	17
2.1	Package Order	18
2.2	Displaying Glossaries	18
2.3	Defining Additional Glossaries	20
2.4	Defining New Entries	20
2.5	Defining Sub-Entries	21
2.6	Changing the Sort Order	22
2.7	Accented or Non-Latin Characters	22
2.8	Cross-Referencing Entries	23
2.9	Plurals	23
2.10	Displaying Terms in the Document	23
2.11	Acronyms	24
3	Overview of User Commands	25
3.1	Package Options	25
3.2	Defining Glossary Entries	29
3.2.1	Plurals	32
3.2.2	Sub-Entries	32

3.2.3	Loading Entries From a File	34
3.3	Number lists	35
3.4	Links to Glossary Entries	36
3.4.1	Changing the format of the link text	41
3.4.2	Enabling and disabling hyperlinks to glossary entries	43
3.5	Adding an Entry to the Glossary Without Generating Text	43
3.6	Cross-Referencing Entries	43
3.7	Using Glossary Terms Without Links	44
3.8	Displaying a glossary	46
3.8.1	Changing the way the entry name appears in the glossary	47
3.8.2	Xindy	47
3.9	Defining New Glossaries	51
3.10	Acronyms	52
3.10.1	Upgrading From the glossary Package	59
3.11	Unsetting and Resetting Entry Flags	59
3.12	Glossary Styles	60
3.12.1	List Styles	62
3.12.2	Longtable Styles	63
3.12.3	Supertabular Styles	65
3.12.4	Tree-Like Styles	66
3.13	Defining your own glossary style	67
3.13.1	Example: creating a completely new style	69
3.13.2	Example: creating a new glossary style based on an existing style	70
3.14	Accessibility Support	70
4	Mfirstuc Package	71
5	Documented Code	72
5.1	Package Definition	72
5.2	Package Options	72
5.3	Default values	79
5.4	Xindy	85
5.5	Loops and conditionals	91
5.6	Defining new glossaries	92
5.7	Defining new entries	94
5.8	Resetting and unsetting entry flags	101
5.9	Loading files containing glossary entries	102
5.10	Using glossary entries in the text	103
5.10.1	Links to glossary entries	104
5.10.2	Displaying entry details without adding information to the glossary	131
5.11	Adding an entry to the glossary without generating text	134
5.12	Creating associated files	135
5.13	Writing information to associated files	142
5.14	Glossary Entry Cross-References	144
5.15	Displaying the glossary	145
5.16	Acronyms	153
5.17	Additional predefined acronym styles	156
5.18	Predefined Glossary Styles	166

6 Mfirstuc Documented Code	167
7 Glossary Styles	168
7.1 Glossary hyper-navigation definitions (glossary-hypernav package)	168
7.2 List Style (glossary-list.sty)	170
7.3 Glossary Styles using longtable (the glossary-long package)	172
7.4 Glossary Styles using supertabular environment (glossary-super package)	177
7.5 Tree Styles (glossary-tree.sty)	183
8 Accessibilty Support (glossaries-accsupp Code)	190
9 Multi-Lingual Support	196
9.1 Babel Captions	196
9.2 Brazilian Dictionary	201
9.3 Danish Dictionary	201
9.4 Dutch Dictionary	202
9.5 English Dictionary	202
9.6 French Dictionary	202
9.7 German Dictionary	202
9.8 Irish Dictionary	203
9.9 Italian Dictionary	203
9.10 Magyar Dictionary	203
9.11 Polish Dictionary	204
9.12 Spanish Dictionary	204
Index	205

1 Introduction

The `glossaries` package is provided to assist generating glossaries. It has a certain amount of flexibility, allowing the user to customize the format of the glossary and define multiple glossaries. It also supports acronyms and glossary styles that include symbols (in addition to a name and description) for glossary entries. There is provision for loading a database of glossary terms. Only those terms used¹ in the document will be added to the glossary.

This package replaces the `glossary` package which is now obsolete. Please see the file `glossary2glossaries.pdf` for assistance in upgrading.

The `glossaries` package comes with a Perl script called `makeglossaries`. This provides a convenient interface to `makeindex` or `xindy`. It is strongly recommended that you use this script, but *it is not essential*. If you are reluctant to install Perl, or for any other reason you don't want to use `makeglossaries`, you can called `makeindex` or `xindy` explicitly. See subsection 1.3 for further details.

¹that is, if the term has been referenced using any of the commands described in subsection 3.4, subsection 3.5 or via `\glsee` (or the `see` key)

One of the strengths of this package is its flexibility, however the drawback of this is the necessity of having a large manual that can cover all the various settings. The documentation is therefore structured as follows:

- **section 2** is for people who want a few quick pointers of how to get started creating a basic glossary, without having to read through lengthy descriptions.
- **section 3** gives an overview of the main user commands and their syntax.
- **section 4** describes the associated `mfirstruc` package.
- **section 5** contains the documented source code for those who want to know more about how the package works.
- **section 6** contains the documented code for the `mfirstruc` package.

The remainder of this introductory section covers the following:

- **subsection 1.1** lists the sample documents provided with this package.
- **subsection 1.2** provides information for users who wish to write in a language other than English.
- **subsection 1.3** describes how to use a post-processor to create the sorted glossaries for your document.
- **subsection 1.4** provides some assistance in the event that you encounter a problem.

1.1 Sample Documents

The `glossaries` package is provided with some sample documents that illustrate the various functions. These should be located in the `samples` subdirectory (folder) of the `glossaries` documentation directory. This location varies according to your operating system and `TeX` distribution. You can use `texdoc` to locate the main `glossaries` documentation. For example, in a terminal or command prompt, type:

```
texdoc -l glossaries
```

This should display the full pathname of the file `glossaries.pdf`. View the contents of that directory and see if it contains the `samples` subdirectory.

If you can't find the sample files, they are available in the `doc/latex/glossaries/samples/` subdirectory of the `glossaries.tds.zip` archive which can be downloaded from CTAN.

The sample documents are as follows:

minimalgls.tex This document is a minimal working example. You can test your installation using this file. To create the complete document you will need to do the following steps:

1. Run `minimalgls.tex` through L^AT_EX by either typing

```
latex minimalgls
```

in a terminal or by using the relevant button or menu item in your text editor or front-end. This will create the required associated files but you will not see the glossary. If you use PDFLATEX you will also get warnings about non-existent references. These warnings may be ignored on the first run.

If you get a Missing \begin{document} error, then it's most likely that your version of xkeyval is out of date. Check the log file for a warning of that nature. If this is the case, you will need to update the xkeyval package.

2. Run `makerglossaries` on the document. This can be done on a terminal by either typing

```
makerglossaries minimalgls
```

or by typing

```
perl makerglossaries minimalgls
```

If your system doesn't recognise the command `perl` then it's likely you don't have Perl installed. In which case you will need to use `makeindex` directly. You can do this in a terminal by typing (all on one line):

```
makeindex -s minimalgls.ist -t minimalgls.glg -o minimalgls.gls  
minimalgls.glo
```

(See [subsubsection 1.3.3](#) for further details on using `makeindex` explicitly.)

Note that if you need to specify the full path and the path contains spaces, you will need to delimit the file names with the double-quote character.

3. Run `minimalgls.tex` through LATEX again (as step 1)

You should now have a complete document. The number following each entry in the glossary is the location number. By default, this is the page number where the entry was referenced.

sample4col.tex This document illustrates a four column glossary where the entries have a symbol in addition to the name and description. To create the complete document, you need to do:

```
latex sample4col  
makerglossaries sample4col  
latex sample4col
```

As before, if you don't have Perl installed, you will need to use `makeindex` directly instead of using `makerglossaries`. The vertical gap between entries is the gap created at the start of each group. This can be suppressed by redefining `\glsgroupskip` after the glossary style has been set:

```
\renewcommand*{\glsgroupskip}{}
```

sampleAcr.tex This document has some sample acronyms. It also adds the glossary to the table of contents, so an extra run through LATEX is required to ensure the document is up to date:

```
latex sampleAcr
makeglossaries sampleAcr
latex sampleAcr
latex sampleAcr
```

sampleAcrDesc.tex This is similar to the previous example, except that the acronyms have an associated description. As with the previous example, the glossary is added to the table of contents, so an extra run through L^AT_EX is required:

```
latex sampleAcrDesc
makeglossaries sampleAcrDesc
latex sampleAcrDesc
latex sampleAcrDesc
```

sampleDesc.tex This is similar to the previous example, except that it defines the acronyms using `\newglossaryentry` instead of `\newacronym`. As with the previous example, the glossary is added to the table of contents, so an extra run through L^AT_EX is required:

```
latex sampleDesc
makeglossaries sampleDesc
latex sampleDesc
latex sampleDesc
```

sampleDB.tex This document illustrates how to load external files containing the glossary definitions. It also illustrates how to define a new glossary type. This document has the number list suppressed and uses `\glsaddall` to add all the entries to the glossaries without referencing each one explicitly. To create the document do:

```
latex sampleDB
makeglossaries sampleDB
latex sampleDB
```

The glossary definitions are stored in the accompanying files `database1.tex` and `database2.tex`. Note that if you don't have Perl installed, you will need to use `makeindex` twice instead of a single call to `makeglossaries`:

1. Create the main glossary:

```
makeindex -s sampleDB.ist -t sampleDB.glg -o sampleDB.gls sampleDB.glo
```

2. Create the secondary glossary:

```
makeindex -s sampleDB.ist -t sampleDB.nlg -o sampleDB.not sampleDB.ntn
```

sampleEq.tex This document illustrates how to change the location to something other than the page number. In this case, the `equation` counter is used since all glossary entries appear inside an `equation` environment. To create the document do:

```
latex sampleEq
makeglossaries sampleEq
latex sampleEq
```

sampleEqPg.tex This is similar to the previous example, but the number lists are a mixture of page numbers and equation numbers. This example adds the glossary to the table of contents, so an extra L^AT_EX run is required:

```
latex sampleEqPg
makeglossaries sampleEqPg
latex sampleEqPg
latex sampleEqPg
```

sampleSec.tex This document also illustrates how to change the location to something other than the page number. In this case, the `section` counter is used. This example adds the glossary to the table of contents, so an extra L^AT_EX run is required:

```
latex sampleSec
makeglossaries sampleSec
latex sampleSec
latex sampleSec
```

sampleNtn.tex This document illustrates how to create an additional glossary type. This example adds the glossary to the table of contents, so an extra L^AT_EX run is required:

```
latex sampleNtn
makeglossaries sampleNtn
latex sampleNtn
latex sampleNtn
```

Note that if you don't have Perl installed, you will need to use `makeindex` twice instead of a single call to `makeglossaries`:

1. Create the main glossary:

```
makeindex -s sampleNtn.ist -t sampleNtn.glg -o sampleNtn.gls sampleNtn.glo
```

2. Create the secondary glossary:

```
makeindex -s sampleNtn.ist -t sampleNtn.nlg -o sampleNtn.not sampleNtn.ntn
```

sample.tex This document illustrates some of the basics, including how to create child entries that use the same name as the parent entry. This example adds the glossary to the table of contents, so an extra L^AT_EX run is required:

```
latex sample
makeglossaries sample
latex sample
latex sample
```

You can see the difference between word and letter ordering if you substitute `order=word` with `order=letter`. (Note that this will only have an effect if you use `makeglossaries`. If you use `makeindex` explicitly, you will need to use the `-l` switch to indicate letter ordering.)

sampletree.tex This document illustrates a hierarchical glossary structure where child entries have different names to their corresponding parent entry. To create the document do:

```
latex sampletree  
makeglossaries sampletree  
latex sampletree
```

samplexdy.tex This document illustrates how to use the `glossaries` package with `xindy` instead of `makeindex`. The document uses UTF8 encoding (with the `inputenc` package). The encoding is picked up by `makeglossaries`. By default, this document will create a `xindy` style file called `samplexdy.xdy`, but if you uncomment the lines

```
\setStyleFile{samplexdy-mc}  
\noist  
\GlsSetXdyLanguage{}
```

it will set the style file to `samplexdy-mc.xdy` instead. This provides an additional letter group for entries starting with “Mc” or “Mac”. If you use `makeglossaries`, you don’t need to supply any additional information. If you don’t use `makeglossaries`, you will need to specify the required information. Note that if you set the style file to `samplexdy-mc.xdy` you must also specify `\noist`, otherwise the `glossaries` package will overwrite `samplexdy-mc.xdy` and you will lose the “Mc” letter group.

To create the document do:

```
latex samplexdy  
makeglossaries samplexdy  
latex samplexdy
```

If you don’t have Perl installed, you will have to call `xindy` explicitly instead of using `makeglossaries`. If you are using the default style file `samplexdy.xdy`, then do (no line breaks):

```
xindy -L english -C utf8 -I xindy -M samplexdy -t samplexdy.glg  
-o samplexdy.gls samplexdy.glo
```

otherwise, if you are using `samplexdy-mc.xdy`, then do (no line breaks):

```
xindy -I xindy -M samplexdy-mc -t samplexdy.glg -o samplexdy.gls  
samplexdy.glo
```

sampleutf8.tex This is another example that uses `xindy`. Unlike `makeindex`, `xindy` can cope with accented or non-Latin characters. This document uses UTF8 encoding. To create the document do:

```
latex sampleutf8  
makeglossaries sampleutf8  
latex sampleutf8
```

If you don't have Perl installed, you will have to call `xindy` explicitly instead of using `makeglossaries` (no line breaks):

```
xindy -L english -C utf8 -I xindy -M sampleutf8 -t sampleutf8.glg  
-o sampleutf8.gls sampleutf8.glo
```

If you remove the `xindy` option from `sampleutf8.tex` and do:

```
latex sampleutf8  
makeglossaries sampleutf8  
latex sampleutf8
```

you will see that the entries that start with a non-Latin character now appear in the symbols group, and the word "manoeuvre" is now after "manor" instead of before it. If you are unable to use `makeglossaries`, the call to `makeindex` is as follows (no line breaks):

```
makeindex -s sampleutf8.ist -t sampleutf8.glg -o sampleutf8.gls  
sampleutf8.glo
```

sampleaccsupp.tex This document uses the experimental `glossaries-accsupp` package. The symbol is set to the replacement text. Note that some PDF viewers don't use the accessibility support. Information about the `glossaries-accsupp` package can be found in [subsection 3.14](#).

1.2 Multi-Lingual Support

As from version 1.17, the `glossaries` package can now be used with `xindy` as well as `makeindex`. If you are writing in a language that uses accented characters or non-Latin characters it is recommended that you use `xindy` as `makeindex` is hard-coded for Latin languages. This means that you are not restricted to the A, ..., Z letter groups. If you want to use `xindy`, remember to use the `xindy` package option. For example:

```
\documentclass[frenchb]{article}  
\usepackage[utf8]{inputenc}  
\usepackage[T1]{fontenc}  
\usepackage{babel}  
\usepackage[xindy]{glossaries}
```

If you use an accented or non-Latin character at the start of an entry name, you must place it in a group, or it will cause a problem for commands that convert the first letter to uppercase (e.g. `\Gls`) due to expansion issues. For example:

```
\newglossaryentry{elite}{name={{\'e}lite},  
description={select group or class}}
```

If you use the `inputenc` package, `makeglossaries` will pick up the encoding from the auxiliary file. If you use `xindy` explicitly instead of via `makeglossaries`, you may need to specify the encoding using the `-C` option. Read the `xindy` manual for further details.

1.2.1 Changing the Fixed Names

As from version 1.08, the `glossaries` package now has limited multi-lingual support, thanks to all the people who have sent me the relevant translations either via email or via `comp.text.tex`. However you must load `babel` *before* `glossaries` to enable this. Note that if `babel` is loaded and the `translator` package is detected on T_EX's path, then the `translator` package will be loaded automatically, however, it may not pick up on the required languages, so if the predefined text is not translated, you may need to explicitly load the `translator` package with the required languages. For example:

```
\usepackage[spanish]{babel}
\usepackage[spanish]{translator}
\usepackage{glossaries}
```

Alternatively, specify the language as a class option rather than a package option. For example:

```
\documentclass[spanish]{report}

\usepackage{babel}
\usepackage{glossaries}
```

If you want to use `ngerman` or `german` instead of `babel`, you will need to include the `translator` package to provide the translations. For example:

```
\documentclass[ngerman]{article}
\usepackage{ngerman}
\usepackage{translator}
\usepackage{glossaries}
```

The following languages are currently supported by the `glossaries` package:

Language	As from version
Brazilian Portuguese	1.17
Danish	1.08
Dutch	1.08
English	1.08
French	1.08
German	1.08
Irish	1.08
Italian	1.08
Hungarian	1.08
Polish	1.13
Spanish	1.08

The language dependent commands and `translator` keys used by the `glossaries` package are listed in [table 1](#).

Due to the varied nature of `glossaries`, it's likely that the predefined translations may not be appropriate. If you are using the `babel` package and do not have the `translator` package installed, you need to be familiar with the advice given in <http://www.tex.ac.uk/cgi-bin/texfaq2html?label=latextwords>.

If you have the `translator` package installed, then it becomes much easier to change the default translations. For example, if you are writing in Irish and you

Table 1: Customised Text

Command Name	Translator Key Word	Purpose
\glossaryname	Glossary	Title of the main glossary.
\acronymname	Acronyms	Title of the list of acronyms (when used with package option <code>acronym</code>).
\entryname	Notation (glossaries)	Header for first column in the glossary (for 2, 3 or 4 column glossaries that support headers).
\descriptionname	Description (glossaries)	Header for second column in the glossary (for 2, 3 or 4 column glossaries that support headers).
\symbolname	Symbol (glossaries)	Header for symbol column in the glossary for glossary styles that support this option.
\pagelistname	Page List (glossaries)	Header for page list column in the glossary for glossaries that support this option.
\glssymbolsgroupname	Symbols (glossaries)	Header for symbols section of the glossary for glossary styles that support this option.
\glsnumbersgroupname	Numbers (glossaries)	Header for numbers section of the glossary for glossary styles that support this option.

want `\symbolname` to produce “Siombail” instead of “Comhartha”, then you can put the following in your document preamble:

```
\deftranslation[to=Irish]{Symbol (glossaries)}{Siombail}
```

Note that `xindy` provides much better multi-lingual support than `makeindex`, so it’s recommended that you use `xindy` if you have glossary entries that contain accented characters or non-Roman letters. See [subsubsection 3.8.2](#) for further details.

1.3 Generating the Associated Glossary Files

In order to generate a sorted glossary with compact location lists, it is necessary to use an external indexing application as an intermediate step. It is this application that creates the file containing the code that typesets the glossary. If this step is omitted, the glossaries will not appear in your document. The two indexing applications that are most commonly used with L^AT_EX are `makeindex` and `xindy`. As from version 1.17, the `glossaries` package can be used with either of these applications. Previous versions were designed to be used with `makeindex` only. Note that `xindy` has much better multi-lingual support than `makeindex`, so `xindy` is recommended if you’re not writing in English. Commands that only have an effect when `xindy` is used are described in [subsubsection 3.8.2](#).

The `glossaries` package comes with the Perl script `makeglossaries` which will run `makeindex` or `xindy` on all the glossary files using a customized style file (which is created by `\makeglossaries`). See [subsubsection 1.3.1](#) for further details. Perl is stable, cross-platform, open source software that is used by a number of T_EX-related applications. Further information is available at <http://www.perl.org/about.html>. However, whilst it is strongly recommended that you use the `makeglossaries` script, it is possible to use the `glossaries` package without having Perl installed. In which case, if you have used the `xindy` package option, you will need to use `xindy` (see [subsubsection 1.3.2](#)), otherwise you will need to use `makeindex` (see [subsubsection 1.3.3](#)). Note that some commands and package options have no effect if you don’t use `makeglossaries`. These are listed in [table 2](#).

Note that if any of your entries use an entry that is not referenced outside the glossary, you will need to do an additional `makeglossaries`, `makeindex` or `xindy` run, as appropriate. For example, suppose you have defined the following entries:

```
\newglossaryentry{citrusfruit}{name={citrus fruit},  
description={fruit of any citrus tree. (See also  
\gls{orange})}}  
  
\newglossaryentry{orange}{name={orange},  
description={an orange coloured fruit.}}
```

and suppose you have `\gls{citrusfruit}` in your document but don’t reference the `orange` entry, then the `orange` entry won’t appear in your glossary until you first create the glossary and then do another run of `makeglossaries`, `makeindex` or `xindy`. For example, if the document is called `myDoc.tex`, then you must do:

```
latex myDoc  
makeglossaries myDoc  
latex myDoc
```

```
makeglossaries myDoc
latex myDoc
```

Likewise, an additional `makeglossaries` and L^AT_EX run may be required if the document pages shift with re-runs. For example, if the page numbering is not reset after the table of contents, the insertion of the table of contents on the second L^AT_EX run may push glossary entries across page boundaries, which means that the number lists in the glossary may need updating.

The examples in this document assume that you are accessing `makeglossaries`, `xindy` or `makeindex` via a terminal. Windows users can use the MSDOS Prompt which is usually accessed via the Start→All Programs menu or Start→All Programs→Accessories menu. Alternatively, your text editor may have the facility to create a function that will call the required application. See your editor's user manual for further details.

If any problems occur, remember to check the transcript files (e.g. `.glg` or `.alg`) for messages.

Table 2: Commands and package options that have no effect when using `xindy` or `makeindex` explicitly

Command or Package Option	makeindex	xindy
<code>order=letter</code>	use -l	use -M <code>ord/letorder</code>
<code>order=word</code>	default	default
<code>xindy={language=<lang>,codename=<code>}</code>	N/A	use -L <code><lang></code> -C <code><code></code>
<code>\GlsSetXdyLanguage{<lang>}</code>	N/A	use -L <code><lang></code>
<code>\GlsSetXdyCodePage{<code>}</code>	N/A	use -C <code><code></code>

1.3.1 Using the `makeglossaries` Perl Script

The `makeglossaries` script picks up the relevant information from the auxiliary (`.aux`) file and will either call `xindy` or `makeindex`, depending on whether the indexing style file ends with `.xdy` or `.ist`. Therefore, you only need to pass the document's name without the extension to `makeglossaries`. For example, if your document is called `myDoc.tex`, type the following in your terminal:

```
latex myDoc
makeglossaries myDoc
latex myDoc
```

You may need to explicitly load `makeglossaries` into Perl:

```
perl makeglossaries myDoc
```

There is a batch file called `makeglossaries.bat` which does this for Windows users, but you must have Perl installed to be able to use it.

1.3.2 Using `xindy` explicitly

If you want to use `xindy` to process the glossary files, you must make sure you have used the `xindy` package option:

```
\usepackage[xindy]{glossaries}
```

This is required regardless of whether you use `xindy` explicitly or whether it's called implicitly via `makeglossaries`. This causes the glossary entries to be written in raw `xindy` format, so you need to use `-I xindy not -I tex`.

To run `xindy` type the following in your terminal (all on one line):

```
xindy -L <language> -C <encoding> -I xindy -M <style> -t <base>.glg  
-o <base>.gls <base>.glo
```

where `<language>` is the required language name, `<encoding>` is the encoding, `<base>` is the name of the document without the `.tex` extension and `<style>` is the name of the `xindy` style file without the `.xdy` extension. The default name for this style file is `<base>.xdy` but can be changed via `\setStyleFile{<style>}`. You may need to specify the full path name depending on the current working directory. If any of the file names contain spaces, you must delimit them using double-quotes.

For example, if your document is called `myDoc.tex` and you are using UTF8 encoding in English, then type the following in your terminal:

```
xindy -L english -C utf8 -I xindy -M myDoc -t myDoc.glg -o myDoc.gls myDoc.glo
```

Note that this just creates the main glossary. You need to do the same for each of the other glossaries (including the list of acronyms if you have used the `acronym` package option), substituting `.glg`, `.gls` and `.glo` with the relevant extensions. For example, if you have used the `acronym` package option, then you would need to do:

```
xindy -L english -C utf8 -I xindy -M myDoc -t myDoc.alg -o myDoc.acr myDoc.acn
```

For additional glossaries, the extensions are those supplied when you created the glossary with `\newglossary`.

Note that if you use `makeglossaries` instead, you can replace all those calls to `xindy` with just one call to `makeglossaries`:

```
makeglossaries myDoc
```

Note also that some commands and package options have no effect if you use `xindy` explicitly instead of using `makeglossaries`. These are listed in [table 2](#).

1.3.3 Using `makeindex` explicitly

If you want to use `makeindex` explicitly, you must make sure that you haven't used the `xindy` package option or the glossary entries will be written in the wrong format. To run `makeindex`, type the following in your terminal:

```
makeindex -s <style>.ist -t <base>.glg -o <base>.gls <base>.glo
```

where `<base>` is the name of your document without the `.tex` extension and `<style>.ist` is the name of the `makeindex` style file. By default, this is `<base>.ist`, but may be changed via `\setStyleFile{<style>}`. Note that there are other options, such as `-l` (letter ordering). See the `makeindex` manual for further details.

For example, if your document is called `myDoc.tex`, then type the following at the terminal:

```
makeindex -s myDoc.ist -t myDoc.glg -o myDoc.gls myDoc.glo
```

Note that this only creates the main glossary. If you have additional glossaries (for example, if you have used the `acronym` package option) then you must call `makeindex` for each glossary, substituting `.glg`, `.gls` and `.glo` with the relevant extensions. For example, if you have used the `acronym` package option, then you need to type the following in your terminal:

```
makeindex -s myDoc.ist -t myDoc.alg -o myDoc.acr myDoc.acn
```

For additional glossaries, the extensions are those supplied when you created the glossary with `\newglossary`.

Note that if you use `makerglossaries` instead, you can replace all those calls to `makeindex` with just one call to `makerglossaries`:

```
makerglossaries myDoc
```

Note also that some commands and package options have no effect if you use `makeindex` explicitly instead of using `makerglossaries`. These are listed in [table 2](#).

1.4 Troubleshooting

The `glossaries` package comes with a minimal file called `minimalgls.tex` which can be used for testing. This should be located in the `samples` subdirectory (folder) of the `glossaries` documentation directory. The location varies according to your operating system and `TeX` installation. For example, on my Linux partition it can be found in `/usr/local/texlive/2008/texmf-dist/doc/latex/glossaries/`. Further information on debugging `LATEX` code is available at <http://theoval.cmp.uea.ac.uk/~nlct/latex/minexample/>.

Below is a list of the most frequently asked questions. For other queries, consult the `glossaries` FAQ at <http://theoval.cmp.uea.ac.uk/~nlct/latex/packages/faq/glossariesfaq.html>.

1. **Q.** I get the error message:

```
Missing \begin{document}
```

A. Check you are using an up to date version of the `xkeyval` package.

2. **Q.** I've used the `smallcaps` option, but the acronyms are displayed in normal sized upper case letters.

A. The `smallcaps` package option uses `\textsc` to typeset the acronyms. This command converts lower case letters to small capitals, while upper case letters remain their usual size. Therefore you need to specify the acronym in lower case letters.

3. **Q.** How do I change the font that the acronyms are displayed in?

A. The easiest way to do this is to specify the `smaller` package option and redefine `\acronymfont` to use the required typesetting command. For example, suppose you would like the acronyms displayed in a sans-serif font, then you can do:

```
\usepackage[smaller]{glossaries}
\renewcommand*\acronymfont{\textsf{\#1}}
```

4. **Q.** How do I change the font that the acronyms are displayed in on first use?

A. The easiest way to do this is to specify the `smaller` package option and redefine `\firstacronymfont` to use the required command. Note that if you don't want the acronym on subsequent use to use `\textsmaller`, you will also need to redefine `\acronymfont`, as above. For example to make the acronym emphasized on first use, but use the surrounding font for subsequent use, you can do:

```
\usepackage[smaller]{glossaries}
\renewcommand*\firstacronymfont[1]{\emph{#1}}
\renewcommand*\acronymfont[1]{#1}
```

5. **Q.** I don't have Perl installed, do I have to use `makeglossaries`?

A. Although it is strongly recommended that you use `makeglossaries`, you don't have to use it. For further details, read [subsubsection 1.3.2](#) or [subsubsection 1.3.3](#), depending on whether you want to use `xindy` or `makeindex`.

6. **Q.** I'm used to using the `glossary` package: are there any instructions on migrating from the `glossary` package to the `glossaries` package?

A. Read the file `glossary2glossaries.pdf` which should be available from the same location as this document.

7. **Q.** I'm using `babel` but the fixed names haven't been translated.

A. The `glossaries` package currently only supports the following languages: Brazilian Portuguese, Danish, Dutch, English, French, German, Irish, Italian, Hungarian, Polish and Spanish. If you want to add another language, send me the translations, and I'll add them to the next version.

If you are using one of the above languages, but the text hasn't been translated, try adding the `translator` package with the required languages explicitly (before you load the `glossaries` package). For example:

```
\usepackage[ngerman]{babel}
\usepackage[ngerman]{translator}
\usepackage{glossaries}
```

Alternatively, you can add the language as a global option to the class file. Check the `translator` package documentation for further details.

8. **Q.** My acronyms contain strange characters when I use commands like `\acrlong`.

A. Switch off the sanitization:

```
\usepackage[sanitize=none]{glossaries}
```

and protect fragile commands.

9. **Q.** My glossaries haven't appeared.

A. Remember to do the following:

- Add `\makeglossaries` to the document preamble.

- Use either `\printglossary` for each glossary that has been defined or `\printglossaries`.
- Use the commands listed in [subsection 3.4](#), [subsection 3.5](#) or [subsection 3.6](#) for each entry that you want to appear in the glossary.
- Run L^AT_EX on your document, then run `makeglossaries`, then run L^AT_EX on your document again. If you want the glossaries to appear in the table of contents, you will need an extra L^AT_EX run. If any of your entries cross-reference an entry that's not referenced in the main body of the document, you will need to run `makeglossaries` after the second L^AT_EX run, followed by another L^AT_EX run.

Check the log files (`.log`, `.glg` etc) for any warnings.

10. **Q.** It is possible to change the rules used to sort the glossary entries?
11. **A.** If it's for an individual entry, then you can use the entry's `sort` key to sort it according to a different term. If it's for the entire alphabet, then you will need to use `xindy` (instead of `makeindex`) and use an appropriate `xindy` language module. Writing `xindy` modules or styles is beyond the scope of this manual. Further information about `xindy` can be found at the [Xindy Web Site](#).² There is also a link to the `xindy` mailing list from that site.

2 A Quick Guide For The Impatient

This section is for people who want a few quick pointers of how to get started. However it is recommended that you read [section 3](#) for additional commands and advice not listed here. There are also some sample files to help you get started, listed in [subsection 1.1](#). The following is a minimal example:

```
\documentclass{article}

% Load hyperref before glossaries
\usepackage[colorlinks]{hyperref}
\usepackage[acronym, % make a separate list of acronyms
           toc % put the glossaries into the table of contents
           ]{glossaries}

% Write glossary entries to external file so that they
% can be sorted and collated by another application.
\makeglossaries

% Define an entry whose label is 'xample':
\newglossaryentry{xample}{% unique label identifying this entry
  % Define the attributes for this entry:
  name=sample,% the name or term begin defined
  description={a sample entry}% a description of this entry
}

% Define an acronym whose label is 'ca':
\newacronym{ca}{label}
```

²<http://xindy.sourceforge.net/>

```

{CA}%
\begin{document}
\tableofcontents

A \gls{xample} entry and a \gls{ca}.

\printglossaries
\end{document}

```

2.1 Package Order

Load glossaries *after* hyperref:

```
\usepackage{hyperref}
\usepackage{glossaries}
```

Similarly for the html package:

```
\usepackage{html}
\usepackage{glossaries}
```

Likewise for babel and translator.

Note that if you are using the hyperref package and the glossaries are in chapters, you may need to redefine \glsclearpage to do \clearpage instead of \cleardoublepage to prevent an unwanted blank page appearing before the glossary:

```
\renewcommand*\glsclearpage{\clearpage}
```

2.2 Displaying Glossaries

Always use \makeglossaries if you want the glossary entries to be written to the glossary file:

```
\usepackage{glossaries}
\makeglossaries
```

If you don't use \makeglossaries, your glossaries will not appear in the document!

Use \printglossaries to make your glossaries appear in the document at that point. For example:

```
\maketitle
\printglossaries
\section{Introduction}
```

Note that only the glossary entries that have been used in the document text will appear in the glossary. See subsection 3.8 for further details.

To add the glossaries to the table of contents use the toc package option:

```
\usepackage[toc]{glossaries}
```

This will require an extra L^AT_EX run. Note that if the table of contents affects the subsequent page numbering (i.e. the page numbers are not reset after the table of contents) then you may need to rerun `\makeglossaries` and L^AT_EX.

The font used to display the entry name in the glossary is governed by `\glsnamefont`. This can be redefined as required. For example, to make the entry names appear in a medium sans-serif font do:

```
\renewcommand{\glsnamefont}[1]{\textsf{\mdseries #1}}
```

Note that the list-like glossary styles place the entry name in the optional argument to `\item`, so they will appear in bold, unless you redefine `\glsnamefont` to counteract the bold font. Similarly, the tree-like styles display the entry name in bold.

Glossary styles can be set using the `style` package option. For example:

```
\usepackage[style=long3col]{glossaries}
```

or using `\glossarystyle{<style>}`. For example:

```
\glossarystyle{altlist}
```

The predefined glossary styles provided by the `glossaries` bundle are listed in [subsection 3.12](#).

Each entry in the glossary has an associated list of numbers indicating whereabouts in the document that entry has been used. The number lists can be suppressed using package option `nonumberlist`:

```
\usepackage[nonumberlist]{glossaries}
```

See [subsection 3.3](#) for further details about number lists.

If your pages have a hyphen compositor (i.e. your page numbers appear in the form 2-1), use `\glsSetCompositor` before `\makeglossaries`:

```
\documentclass{article}
\usepackage{glossaries}
\glsSetCompositor{-}
\makeglossaries
```

By default, the glossary will appear in an unnumbered chapter if chapters are defined, otherwise in an unnumbered section. This can be changed using the `section` package option. For example, to make the glossaries appear in an unnumbered section, even if chapters are defined, do:

```
\usepackage[section]{glossaries}
```

Other sectional units can also be specified as `section=<value>`. For example, to make the glossaries appear in unnumbered subsections:

```
\usepackage[section=subsection]{glossaries}
```

When you have created your document, run L^AT_EX on it, then the Perl script `\makeglossaries`, then run L^AT_EX on it again:

```
latex myfile
makeglossaries myfile
latex myfile
```

(You need to run L^AT_EX again if you have used the toc package option. You may also need an extra `makeglossaries` run and another L^AT_EX run if an entry is only referenced in the glossary, or if including the glossary has caused the number lists to change.)

If you use Windows, there is a batch file called `makeglossaries.bat` which you can use, but you will still need Perl installed. Alternatively, you can call `makeindex` directly. See [subsection 1.3](#) for further details.

If you want to use `xindy` instead of `makeindex`, you must specify it in the package option:

```
\usepackage[xindy]{glossaries}
```

See [subsection 1.3](#) for further details.

2.3 Defining Additional Glossaries

New glossaries can be defined using:

```
\newglossary[⟨log-ext⟩]{⟨label⟩}{⟨in-ext⟩}{⟨out-ext⟩}{⟨title⟩}
```

where `⟨label⟩` is an identifying label, `⟨in-ext⟩` is the extension of the file to be created by `makeindex` or `xindy` (called by `makeglossaries`), `⟨out-ext⟩` is the extension of the file to be read by `makeindex` or `xindy` and `⟨title⟩` is the title for this new glossary. The first optional argument `⟨log-ext⟩` specifies the extension of the `makeindex` or `xindy` transcript file. Example:

```
\newglossary[nlg]{notation}{not}{ntn}{Notation}
```

This glossary's label is `notation` and its title will be `Notation`. If you use `makeglossaries`, the `makeindex` or `xindy` transcript will be written to a file with the extension `.nlg`. If `⟨log-ext⟩` is omitted, the extension `.glg` will be used.

Any new glossaries must be defined before `\makeglossaries`:

```
\usepackage{glossaries}
\newglossary{notation}{not}{ntn}{Notation}
\makeglossaries
```

If you use the `acronym` package option, the `glossaries` package will automatically create a new glossary type labelled `acronym`:

```
\usepackage[acronym]{glossaries}
```

2.4 Defining New Entries

A glossary term is defined using:

```
\newglossaryentry{⟨label⟩}{⟨key-val list⟩}
```

The `⟨key-val list⟩` must at least contain a `name` key and a `description` key. For example:

```
\newglossaryentry[perl]{name=Perl,
description=A scripting language}
```

In this example, I have given the entry the label `perl`. Whenever I want to use this entry, that is the label I need to use to identify it.

Only those terms that have actually been used in the document will be placed in the glossary. If you have defined a term that doesn't appear in the glossary,

then it means you haven't used it in the text (either via `\glslink` or `\gls` and related commands or via `\glsadd` or `\glsaddall` or via `\glssee`).

If you have multiple glossaries, use the `type` key to specify in which glossary the entry belongs. For example:

```
\newglossary{languages}{lan}{lng}{Index of Languages}

\makeglossaries

\newglossaryentry{perl}{name=Perl,
description=A scripting language,
type=languages}
```

If `type` is omitted, the default glossary is used.

Remember to group values that have a comma or equal sign. For example:

```
\newglossaryentry{pagelist}{name=page list,
description={A list of individual pages or page ranges
(e.g. \ 1,2,4,7--9)}}
```

Associated symbols can also be specified, but whether the symbol appears in the glossary depends on the glossary style. For example:

```
\newglossaryentry{metre}{name={metre},
description={A metric measurement of length},
symbol={m}}
```

See [subsection 3.12](#) for a list of predefined glossary styles.

See [subsection 3.2](#) for further details.

2.5 Defining Sub-Entries

To define a sub-entry, use the `parent` key. For example:

```
\newglossaryentry{fruit}{name={fruit}, % parent entry
description={tree product that contains seeds}}

\newglossaryentry{apple}{name={apple}, % sub-entry
description={firm, round fruit},
parent=fruit}
```

Sub-entries may have the same name as the parent entry:

```
\newglossaryentry{glossary}{name=glossary, % parent entry
description={\nopostdesc},
plural={glossaries}}

\newglossaryentry{glossarylist}{% first child entry
description={1) list of technical words},
sort={1},
parent={glossary}}

\newglossaryentry{glossarycol}{% second child entry
description={2) collection of glosses},
sort={2},
parent={glossary}}
```

Note that in this instance the `name` key is not required for the child entries, but the `sort` key is needed to sort the sub-entries. The parent entry has no description, so the description terminator is suppressed using `\nopostdesc`.

See [subsubsection 3.2.2](#) for further details.

2.6 Changing the Sort Order

To change the sorting order, use the `sort` key. For example:

```
\newglossaryentry{tex}{name={\TeX},  
description={A typesetting language},  
sort=tex}
```

This will put the entry in the “T” group (entries starting with the letter “t” or “T”) rather than the “symbols” group (entries starting with a symbol). Similarly, the following example puts the entry in the “U” group instead of the “symbol” group.

```
\newglossaryentry{universal}{name={\ensuremath{\mathcal{U}}}},  
description=The universal set,  
sort=U}
```

Unlike the old `glossary` package, you don’t need to escape `makeindex`’s special characters:

```
\newglossaryentry{quote}{name={"},  
description={Double quote character}}  
  
\newglossaryentry{exclam}{name={!},  
description={Exclamation mark}}  
  
\newacronym{rna}{RNA}{ribonukleins\"aure}
```

2.7 Accented or Non-Latin Characters

If the entry name starts with an accented letter or non-Latin character, you will need to group the first letter (otherwise it will cause a problem for commands like `\Gls` and `\Glspl`):

```
\newglossaryentry{elite}{name={{\'e}lite},  
sort=elite,  
description={select group or class}}
```

Likewise with commands such as `\ae` and `\oe`:

```
\newglossaryentry{oesophagus}{%  
name={{\oe}sophagus},  
sort=oesophagus,  
description={canal from mouth to stomach}}
```

If you use `xindy`, you can specify the accented or non-Latin character directly (in combination with the `inputenc` and `fontenc` packages) but you still need to group the first letter (otherwise it will cause a problem for commands like `\Gls` and `\Glspl` due to expansion issues):

```
\newglossaryentry{elite}{name={{\'e}lite},  
description={select group or class}}
```

Note that in this case the `sort` key is not required as `xindy` knows how to sort the letter é.

2.8 Cross-Referencing Entries

You can cross-reference an entry using the `see` key when you define it. For example, suppose you have defined an entry whose label is `taylorstheorem`, then you can cross-reference it:

```
\newglossaryentry{maclaurinseries}{name={Maclaurin series},  
description={Series expansion},  
see={taylorstheorem}}
```

Alternatively, you can use `\glssee` after you have defined the entry:

```
\glssee{maclaurinseries}{taylorstheorem}
```

(The final argument may be a comma-separated list of labels.) The “see” tag may be overridden for a given entry:

```
\glssee[see also]{maclaurinseries}{taylorstheorem}
```

or it can be changed for all entries by redefining `\seename`.

2.9 Plurals

Plural forms are assumed to be the singular form with an “s” appended, unless otherwise specified. To specify an irregular plural, use the `plural` key. For example:

```
\newglossaryentry{matrix}{name=matrix,  
description=rectangular array of quantities,  
plural=matrices}
```

The way the term appears in the main text can be different from the way the term appears in the glossary:

```
\newglossaryentry{matrix}{name=Matrix,  
description=rectangular array of quantities,  
text=matrix,  
plural=matrices}
```

In this example, the entry name appears as “Matrix” in the glossary, and either “matrix” or “matrices” in the text.

2.10 Displaying Terms in the Document

In the document use `\gls{<label>}` to use a term that has already been defined with `\newglossaryentry` (this will also enter the term into the associated glossary output file). For example:

A `\gls{singmtx}` is a matrix with a zero determinant.

Other variations:

- `\Gls{<label>}` : like `\gls`, but with first letter in upper case
- `\GLS{<label>}` : like `\gls`, but all upper case.
- `\glspl{<label>}` : use plural

- `\Glspl{<label>}` : use plural with first letter in upper case
- `\GLSpl{<label>}` : use plural but all upper case
- `\glslink{<label>}{<link text>}` : use `<link text>` to link to the given entry in the glossary.

For example, the following will produce the plural form with the first letter in uppercase:

```
\Glspl{singmtx} are matrices with a zero determinant.
```

Additional text can be appended to the link using the end optional argument. For example, to form the possessive:

```
The \gls{singmtx}[']s dimensions \ldots
```

See [subsection 3.4](#) for further details.

Entries can be added to the glossary without producing any text using `\glsadd{<label>}` or `\glsaddall`. For example

```
\glsadd{singmtx}
```

will add a line to the glossary file for the specified term, but will not produce any text where the command occurs.

A number range can be entered using `format=(` and `format=)` to mark the beginning and ending of the range. For example:

```
\glsadd[format=()]{singmtx}
This is a very long section all about \glspl{singmtx}.
```

```
% lots of text omitted
```

```
\glsadd[format=)]{singmtx}
```

This is equivalent to `makeindex`'s `| (` and `|)` formats or `xindy`'s `:open-range` and `:close-range` tags.

2.11 Acronyms

The way the term appears on first use can be different to the way it appears subsequently:

```
\newglossaryentry{singmtx}{name=Singular Matrix,
description=A matrix with a zero determinant,
first=singular matrix (SM),
text=SM,
firstplural=singular matrices (SMs)}
```

In this example, the entry name appears as “Singular Matrix” in the glossary, and in the text it appears as “singular matrix (SM)” or “singular matrices (SMs)” the first time the entry is used, and subsequently appears as “SM” or “SMs”.

The quick and easy way to define an acronym is to use:

```
\newacronym[<key-val list>]{<label>}{<abbrev>}{<long>}
```

For example:

```
\newacronym{svm}{SVM}{support vector machine}
```

This is equivalent to:

```
\newglossaryentry{svm}{type=\acronymtype,
  name={SVM},
  description={support vector machine},
  text={SVM},
  first={support vector machine (SVM)},
  plural={SVMs},
  firstplural={support vector machines (SVMs)})
```

(The value of `\acronymtype` varies depending on whether the `acronym` package option is used or not. The optional argument `<key-val list>` can be used to override any of the `\newglossaryentry` keys; for example, if the acronym has an irregular plural.)

You can reset an acronym with `\glsreset{<label>}` so that the next occurrence displays the long form with the acronym in brackets as though it hadn't been used. To do this for all defined terms, use `\glsresetall`. See [subsection 3.11](#) for further details.

3 Overview of User Commands

3.1 Package Options

The `glossaries` package options are as follows:

toc Add the glossaries to the table of contents. Note that an extra L^AT_EX run is required with this option.

numberline When used with `toc`, this will add `\numberline{}` in the final argument of `\addcontentsline`. This will align the table of contents entry with the numbered section titles. Note that this option has no effect if the `toc` option is omitted. If `toc` is used without `numberline`, the title will be aligned with the section numbers rather than the section titles.

acronym This creates a new glossary with the label `acronym`. This is equivalent to:

```
\newglossary[alg]{acronym}{acr}{acn}{\acronymname}
```

If the `acronym` package option is used, `\acronymtype` is set to `acronym` otherwise it is set to `main`.³ Entries that are defined using `\newacronym` are placed in the glossary whose label is given by `\acronymtype`, unless another glossary is explicitly specified.

section This is a `<key>=<value>` option. Its value should be the name of a sectional unit (e.g. chapter). This will make the glossaries appear in the named sectional unit, otherwise each glossary will appear in a chapter, if chapters exist, otherwise in a section. Unnumbered sectional units will be used by default. Example:

```
\usepackage[section=subsection]{glossaries}
```

³Actually it sets `\acronymtype` to `\glsdefaulttype` if the `acronym` package option is not used, but `\glsdefaulttype` usually has the value `main`.

You can omit the value if you want to use sections, i.e.

```
\usepackage[section]{glossaries}
```

is equivalent to

```
\usepackage[section=section]{glossaries}
```

You can change this value later in the document using

```
\setglossarysection
```

```
\setglossarysection{\langle name \rangle}
```

where *⟨name⟩* is the sectional unit.

Note that if you are using the `hyperref` package and the glossaries are put in chapters, you may need to redefine `\glsclearpage` to do `\clearpage` instead of `\cleardoublepage` to prevent an unwanted blank page appearing before the glossary:

```
\renewcommand*\glsclearpage{\clearpage}
```

numberedsection The glossaries are placed in unnumbered sectional units by default, but this can be changed using `numberedsection`. This option can take three possible values: `false` (no number, i.e. use starred form), `nolabel` (numbered, i.e. unstarred form, but not labelled) and `autolabel` (numbered with automatic labelling). If `numberedsection=autolabel` is used, each glossary is given a label that matches the glossary type, so the main (default) glossary is labelled `main`, the list of acronyms is labelled `acronym`⁴ and additional glossaries are labelled using the value specified in the first mandatory argument to `\newglossary`. For example, if you load `glossaries` using:

```
\usepackage[section, numberedsection=autolabel]{glossaries}
```

then each glossary will appear in a numbered section, and can be referenced using something like:

The `main` glossary is in section`\ref{main}` and the list of acronyms is in section`\ref{acronym}`.

If you can't decide whether to have the acronyms in the main glossary or a separate list of acronyms, you can use `\acronymtype` which is set to `main` if the `acronym` option is not used and is set to `acronym` if the `acronym` option is used. For example:

```
The list of acronyms is in section\ref{\acronymtype}.
```

As from version 1.14, you can add a prefix to the label by redefining `\glsautoprefix`. For example:

```
\renewcommand*\glsautoprefix{glo:}
```

⁴if the `acronym` option is used, otherwise the list of acronyms is the main glossary

will add `glo:` to the automatically generated label, so you can then, for example, refer to the list of acronyms as follows:

```
The list of acronyms is in section~\ref{glo:\acronymtype}.
```

Or, if you are undecided on a prefix:

```
The list of acronyms is in section~\ref{\glsautoprefix\acronymtype}.
```

style This is a $\langle key \rangle = \langle value \rangle$ option. Its value should be the name of the glossary style to use. Predefined glossary styles are listed in [subsection 3.12](#).

nolong This prevents the `glossaries` package from automatically loading `glossary-long` (which means that the `longtable` package also won't be loaded). This reduces overhead by not defining unwanted styles and commands. Note that if you use this option, you won't be able to use any of the glossary styles defined in the `glossary-long` package.

nosuper This prevents the `glossaries` package from automatically loading `glossary-super` (which means that the `supertabular` package also won't be loaded). This reduces overhead by not defining unwanted styles and commands. Note that if you use this option, you won't be able to use any of the glossary styles defined in the `glossary-super` package.

nolist This prevents the `glossaries` package from automatically loading `glossary-list`. This reduces overhead by not defining unwanted styles. Note that if you use this option, you won't be able to use any of the glossary styles defined in the `glossary-list` package. Note that since the default style is `list`, you will also need to use the `style` option to set the style to something else.

notree This prevents the `glossaries` package from automatically loading `glossary-tree`. This reduces overhead by not defining unwanted styles. Note that if you use this option, you won't be able to use any of the glossary styles defined in the `glossary-tree` package.

nostyles This prevents all the predefined styles from being loaded. This option is provided in the event that the user has custom styles that are not dependent on the styles provided by the `glossaries` package. Note that if you use this option, you can't use the `style` package option. Instead you must either use `\glossarystyle{\{style\}}` or the `style` key in the optional argument to `\printglossary`.

nonumberlist This option will suppress the associated number lists in the `glossaries` (see also [subsection 3.3](#)).

counter This is a $\langle key \rangle = \langle value \rangle$ option. The value should be the name of the default counter to use in the number lists.

sanitize This is a $\langle key \rangle = \langle value \rangle$ option whose value is also a $\langle key \rangle = \langle value \rangle$ list. By default, the `glossaries` package sanitizes the values of the `name`, `description` and `symbol` keys used when defining a new glossary entry. This may lead to unexpected results if you try to display these values within the document text. This sanitization can be switched off using the `sanitize` package option.

(See [subsection 5.2](#) and [subsection 5.7](#) for further details.) For example, to switch off the sanitization for the `description` and `name` keys, but not for the `symbol` key, do:

```
\usepackage[sanitize={name=false,description=false,%  
symbol=true}]{glossaries}
```

Note: this sanitization only applies to the `name`, `description` and `symbol` keys. It doesn't apply to any of the other keys (except the `sort` key which is always sanitized) so fragile commands contained in the value of the other keys must always be protected using `\protect`. Since the value of the `text` key is obtained from the `name` key, you will still need to protect fragile commands in the `name` key if you don't use the `text` key.

description This option changes the definition of `\newacronym` to allow a description. See [subsection 3.10](#) for further details.

footnote This option changes the definition of `\newacronym` and the way that acronyms are displayed. See [subsection 3.10](#) for further details.

smallcaps This option changes the definition of `\newacronym` and the way that acronyms are displayed. See [subsection 3.10](#) for further details.

smaller This option changes the definition of `\newacronym` and the way that acronyms are displayed. See [subsection 3.10](#) for further details.

dua This option changes the definition of `\newacronym` so that acronyms are always expanded. See [subsection 3.10](#) for further details.

shortcuts This option provides shortcut commands for acronyms. See [subsection 3.10](#) for further details.

makeindex (Default) The glossary information and indexing style file will be written in `makeindex` format. If you use `makeglossaries`, it will automatically detect that it needs to call `makeindex`. If you don't use `makeglossaries`, you need to remember to use `makeindex` not `xindy`. The indexing style file will be given a `.ist` extension.

xindy The glossary information and indexing style file will be written in `xindy` format. If you use `makeglossaries`, it will automatically detect that it needs to call `xindy`. If you don't use `makeglossaries`, you need to remember to use `xindy` not `makeindex`. The indexing style file will be given a `.xdy` extension.

The `xindy` package option may additionally have a value that is a $\langle key \rangle = \langle value \rangle$ comma-separated list to override the language and codepage. For example:

```
\usepackage[xindy={language=english,codepage=utf8}]{glossaries}
```

You can also specify whether you want a number group in the glossary. This defaults to true, but can be suppressed. For example:

```
\usepackage[xindy={glsnumbers=false}]{glossaries}
```

See [subsubsection 3.8.2](#) for further details on using `xindy` with the `glossaries` package.

order This may take two values: `word` or `letter`. The default is `word` ordering. Note that this option has no effect if you don't use `makeglossaries`.

3.2 Defining Glossary Entries

All glossary entries must be defined before they are used, so it is better to define them in the preamble to ensure this.⁵ However only those entries that occur in the document (using any of the commands described in [subsection 3.4](#), [subsection 3.5](#) or [subsection 3.6](#)) will appear in the glossary. Each time an entry is used in this way, a line is added to an associated glossary file (`.glo`), which then needs to be converted into a corresponding `.gls` file which contains the typeset glossary which is input by `\printglossary` or `\printglossaries`. The Perl script `makeglossaries` can be used to call `makeindex` or `xindy`, using a customised indexing style file, for each of the glossaries that are defined in the document. Note that there should be no need for you to explicitly edit or input any of these external files. See [subsection 1.3](#) for further details.

`\makeglossaries` The command `\makeglossaries` must be placed in the preamble in order to create the customised `makeindex` (`.ist`) or `xindy` (`.xdy`) style file and to ensure that glossary entries are written to the appropriate output files. If you omit `\makeglossaries` none of the glossaries will be created.

Note that some of the commands provided by the `glossaries` package must be placed before `\makeglossaries` as they are required when creating the customised style file. If you attempt to use those commands after `\makeglossaries` you will generate an error.

`\noist` You can suppress the creation of the customised `xindy` or `makeindex` style file using `\noist`. Note that this command must be used before `\makeglossaries`.

The default name for the customised style file is given by `\jobname.ist` (for `makeindex`) or `\jobname.xdy` (for `xindy`). This name may be changed using:

`\setStyleFile \setStyleFile{\<name>}`

where `\<name>` is the name of the style file without the extension. Note that this command must be used before `\makeglossaries`.

Each glossary entry is assigned a number list that lists all the locations in the document where that entry was used. By default, the location refers to the page number but this may be overridden using the `counter` package option. The default form of the location number assumes a full stop compositor (e.g. 1.2), but if your location numbers use a different compositor (e.g. 1-2) you need to set this using

`\glsSetCompositor \glsSetCompositor{\<symbol>}`

For example:

`\glsSetCompositor{-}`

⁵The only preamble restriction on `\newglossaryentry` and `\newacronym` was removed in version 1.13, but the restriction remains for `\loadglsentries`.

Note that this command must be used before `\makeglossaries`.

If you use `xindy`, you can have a different compositor for page numbers starting with an uppercase alphabetical character using:

```
\glssetalphacomposer \glssetalphacomposer{<symbol>}
```

Note that this command has no effect if you haven't used the `xindy` package option. For example, if you want number lists containing a mixture of A-1 and 2.3 style formats, then do:

```
\glssetcompositor{.}
\glssetalphacomposer{-}
```

See [subsection 3.3](#) for further information about number lists.

`\newglossaryentry` New glossary entries are defined using the command:

```
\newglossaryentry{<label>}{<key-val list>}
```

The first argument, `<label>`, must be a unique label with which to identify this entry. The second argument, `<key-val list>`, is a `<key>=<value>` list that supplies the relevant information about this entry. There are two required fields: `name` and `description`, except for sub-entries where the `name` field may be omitted. Available fields are listed below:

name The name of the entry (as it will appear in the glossary). If this key is omitted and the `parent` key is supplied, this value will be the same as the parent's name.

`\nopostdesc` **description** A brief description of this term (to appear in the glossary). Within this value, you can use `\nopostdesc` to suppress the description terminator for this entry. For example, if this entry is a parent entry that doesn't require a description, you can do `description={\nopostdesc}`. If you want a paragraph break in the description use `\glspar`. However, note that not all glossary styles support multi-line descriptions. If you are using one of the tabular-like glossary styles that permit multi-line descriptions, use `\newline` not `\\\` if you want to force a line break.

parent The label of the parent entry. Note that the parent entry must be defined before its sub-entries. See [subsubsection 3.2.2](#) for further details.

descriptionplural The plural form of the description (as passed to `\glsdisplay` and `\glsdisplayfirst` by `\glspl`, `\Glsp` and `\GLSp`). If omitted, the value is set to the same as the `description` key.

text How this entry will appear in the document text when using `\gls` (or one of its uppercase variants). If this field is omitted, the value of the `name` key is used.

first How the entry will appear in the document text the first time it is used with `\gls` (or one of its uppercase variants). If this field is omitted, the value of the `text` key is used.

plural How the entry will appear in the document text when using `\glspl` (or one of its uppercase variants). If this field is omitted, the value is obtained

by appending `\glspluralsuffix` to the value of the `text` field. The default value of `\glspluralsuffix` is the letter “s”.

firstplural How the entry will appear in the document text the first time it is used with `\glspl` (or one of its uppercase variants). If this field is omitted, the value is obtained from the `plural` key, if the `first` key is omitted, or by appending `\glspluralsuffix` to the value of the `first` field, if the `first` field is present.

Note: prior to version 1.13, the default value of `firstplural` was always taken by appending “s” to the `first` key, which meant that you had to specify both `plural` and `firstplural`, even if you hadn’t used the `first` key.

symbol This field is provided to allow the user to specify an associated symbol. If omitted, the value is set to `\relax`. Note that not all glossary styles display the symbol.

symbolplural This is the plural form of the symbol (as passed to `\glsdisplay` and `\glsdisplayfirst` by `\glspl`, `\Glspl` and `\GLSpl`). If omitted, the value is set to the same as the `symbol` key.

sort This value indicates how `makeindex` or `xindy` should sort this entry. If omitted, the value is given by the `name` field.

type This specifies the label of the glossary in which this entry belongs. If omitted, the default glossary is assumed. The list of acronyms type is given by `\acronymtype` which will either be `main` or `acronym`, depending on whether the `acronym` package option was used.

nonumberlist Suppress the number list for this entry.

see Cross-reference another entry. Using the `see` key will automatically add this entry to the glossary, but will not automatically add the cross-referenced entry. The referenced entry should be supplied as the value to this key. If you want to override the “see” tag, you can supply the new tag in square brackets before the label. For example `see=[see also]{anotherlabel}`. For further details, see [subsection 3.6](#).

Note that if the name starts with an accented letter or non-Latin character, you must group the accented letter, otherwise it will cause a problem for commands like `\Gls` and `\Glspl`. For example:

```
\newglossaryentry{elite}{name={{\'e}lite},  
description={select group or class}}
```

Note that the same applies if you are using the `inputenc` package:

```
\newglossaryentry{elite}{name={{\'e}lite},  
description={select group or class}}
```

Note that in both of the above examples, you will also need to supply the `sort` key if you are using `makeindex` whereas `xindy` is usually able to sort accented letters correctly.

3.2.1 Plurals

You may have noticed from above that you can specify the plural form when you define a term. If you omit this, the plural will be obtained by appending `\glspluralsuffix` to the singular form. This command defaults to the letter “s”. For example:

```
\newglossaryentry{cow}{name=cow,description={a fully grown  
female of any bovine animal}}
```

defines a new entry whose singular form is “cow” and plural form is “cows”. However, if you are writing in archaic English, you may want to use “kine” as the plural form, in which case you would have to do:

```
\newglossaryentry{cow}{name=cow,plural=kine,  
description={a fully grown female of any bovine animal}}
```

If you are writing in a language that supports multiple plurals (for a given term) then use the plural key for one of them (typically the one you are most likely to use) and for the others you will need to explicitly write the plural form using `\glslink` or `\glsdisp` rather than using `\glspl`. Returning to the cow example above, suppose you will mostly be using “cows” as the plural, but occasionally you want to use “kine” as the plural, then define the term as

```
\newglossaryentry{cow}{name=cow,description={a fully grown  
female of any bovine animal (plural cows, archaic plural kine)})}
```

and use `\glspl{cow}` to produce “cows” and use `\glslink{cow}{kine}` to produce “kine”.

If you are using a language that usually forms plurals by appending a different letter, or sequence of letters, you can redefine `\glspluralsuffix` as required. However, this must be done *before* the entries are defined. For languages that don’t form plurals by simply appending a suffix, all the plural forms must be specified using the plural key (and the `firstplural` key where necessary).

3.2.2 Sub-Entries

As from version 1.17, it is possible to specify sub-entries. These may be used to order the glossary into categories, in which case the sub-entry will have a different name to its parent entry, or it may be used to distinguish different definitions for the same word, in which case the sub-entries will have the same name as the parent entry. Note that not all glossary styles support hierarchical entries and may display all the entries in a flat format. Of the styles that support sub-entries, some display the sub-entry’s name whilst others don’t. Therefore you need to ensure that you use a suitable style. See [subsection 3.12](#) for a list of predefined styles.

Note that the parent entry will automatically be added to the glossary if any of its child entries are used in the document. If the parent entry is not referenced in the document, it will not have a number list.

Hierarchical Categories To arrange a glossary with hierarchical categories, you need to first define the category and then define the sub-entries using the relevant category entry as the value of the `parent` key. For example, suppose I

want a glossary of mathematical symbols that are divided into Greek letters and Roman letters. Then I can define the categories as follows:

```
\newglossaryentry{greekletter}{name={Greek letters},
description={\nopostdesc}}
\newglossaryentry{romanletter}{name={Roman letters},
description={\nopostdesc}}
```

Note that in this example, the category entries don't need a description so I have set the descriptions to `\nopostdesc`. This gives a blank description and suppresses the description terminator.

I can now define my sub-entries as follows:

```
\newglossaryentry{pi}{name={pi},
description={ratio of the circumference of a circle to the diameter},
parent=greekletter}
\newglossaryentry{C}{name=C,
description={Euler's constant},
parent=romanletter}
```

Homographs Sub-entries that have the same name as the parent entry, don't need to have the `name` key. For example, the word "glossary" can mean a list of technical words or a collection of glosses. In both cases the plural is "glossaries". So first define the parent entry:

```
\newglossaryentry{glossary}{name=glossary,
description={\nopostdesc},
plural={glossaries}}
```

Again, the parent entry has no description, so the description terminator needs to be suppressed using `\nopostdesc`.

Now define the two different meanings of the word:

```
\newglossaryentry{glossarylist}{
description={1) list of technical words},
sort={1},
parent={glossary}}
\newglossaryentry{glossarycol}{
description={2) collection of glosses},
sort={2},
parent={glossary}}
```

Note that if I reference the parent entry, the location will be added to the parent's number list, whereas if I reference any of the child entries, the location will be added to the child entry's number list. Note also that since the sub-entries have the same name, the `sort` key is required.

In the above example, the plural form for both of the child entries is the same as the parent entry, so the `plural` key was not required for the child entries. However, if the sub-entries have different plurals, they will need to be specified. For example:

```
\newglossaryentry{bravo}{name={bravo},
description={\nopostdesc}}
```

```

\newglossaryentry{bravocry}{description={1) cry of approval
(pl.\ bravos)},
sort={1},
plural={bravos},
parent=bravo}

\newglossaryentry{bravoruffian}{description={2) hired ruffian or
killer (pl.\ bravoes)},
sort={2},
plural={bravoes},
parent=bravo}

```

3.2.3 Loading Entries From a File

`\loadglsentries` You can store all your glossary entry definitions in another file and use:

```
\loadglsentries[<type>]{<filename>}
```

where `<filename>` is the name of the file containing all the `\newglossaryentry` commands. The optional argument `<type>` is the name of the glossary to which those entries should belong, for those entries where the `type` key has been omitted (or, more specifically, for those entries whose type has been specified by `\glsdefaulttype`, which is what `\newglossaryentry` uses by default). For example, suppose I have a file called `myentries.tex` which contains:

```

\newglossaryentry{perl}{type=main,
name={Perl},
description={A scripting language}}

\newglossaryentry{tex}{name={\TeX},
description={A typesetting language},sort={TeX}>

\newglossaryentry{html}{type=\glsdefaulttype,
name={html},
description={A mark up language}}

```

and suppose in my document preamble I use the command:

```
\loadglsentries[languages]{myentries}
```

then this will add the entries `tex` and `html` to the glossary whose type is given by `languages`, but the entry `perl` will be added to the main glossary, since it explicitly sets the type to `main`.

Note: if you use `\newacronym` (see subsection 3.10) the type is set as `type=\acronymtype` unless you explicitly override it. For example, if my file `myacronyms.tex` contains:

```
\newacronym{aca}{aca}{a contrived acronym}
```

then (supposing I have defined a new glossary type called `altacronym`)

```
\loadglsentries[altacronym]{myacronyms}
```

will add `aca` to the glossary type `acronym`, if the package option `acronym` has been specified, or will add `aca` to the glossary type `altacronym`, if the package option `acronym` is not specified.⁶ In this instance, it is better to change `myacronyms.tex` to:

```
\newacronym[type=\glsdefaulttype]{aca}{aca}{a contrived acronym}
```

and now

```
\loadglsentries[altacronym]{myacronyms}
```

will add `aca` to the glossary type `altacronym`, regardless of whether or not the package option `acronym` is used.

Note that only those entries that have been used in the text will appear in the relevant glossaries. Note also that `\loadglsentries` may only be used in the preamble.

3.3 Number lists

Each entry in the glossary has an associated *number list*. By default, these numbers refer to the pages on which that entry has been used (using any of the commands described in subsection 3.4 and subsection 3.5). The number list can be suppressed using the `nonumberlist` package option, or an alternative counter can be set as the default using the `counter` package option. The number list is also referred to as the location list.

Both `makeindex` and `xindy` concatenate a sequence of 3 or more consecutive pages into a range. With `xindy` you can vary the minimum sequence length using `\GlsSetXdyMinRangeLength{\langle n \rangle}` where $\langle n \rangle$ is either an integer or the keyword `none` which indicates that there should be no range formation.

Note that `\GlsSetXdyMinRangeLength` must be used before `\makeglossaries` and has no effect if `\noist` is used.

With both `makeindex` and `xindy`, you can replace the separator and the closing number in the range using:

```
\glsSetSuffixF  \glsSetSuffixF{\langle suffix \rangle}
\glsSetSuffixFF \glsSetSuffixFF{\langle suffix \rangle}
```

where the former command specifies the suffix to use for a 2 page list and the latter specifies the suffix to use for longer lists. For example:

```
\glsSetSuffixF{f.}
\glsSetSuffixFF{ff.}
```

Note that if you use `xindy`, you will also need to set the minimum range length to 1 if you want to change these suffixes:

```
\GlsSetXdyMinRangeLength{1}
```

⁶This is because `\acronymtype` is set to `\glsdefaulttype` if the `acronym` package option is not used.

Note that if you use the `hyperref` package, you will need to use `\nohyperpage` in the suffix to ensure that the hyperlinks work correctly. For example:

```
\glsSetSuffixF{\nohyperpage{f.}}
\glsSetSuffixFF{\nohyperpage{ff.}}
```

Note that `\glsSetSuffixF` and `\glsSetSuffixFF` must be used before `\makeglossaries` and have no effect if `\noist` is used.

3.4 Links to Glossary Entries

Once you have defined a glossary entry using `\newglossaryentry`, you can refer to that entry in the document using one of the commands listed in this section. The text which appears at that point in the document when using one of these commands is referred to as the *link text* (even if there are no hyperlinks). The commands in this section also add a line to an external file that is used by `makeindex` or `xindy` to generate the relevant entry in the glossary. This information includes an associated location that is added to the number list for that entry. By default, the location refers to the page number. For further information on number lists, see [subsection 3.3](#).

It is strongly recommended that you don't use the commands defined in this section in the arguments of sectioning or caption commands.

The above warning is particularly important if you are using the `glossaries` package in conjunction with the `hyperref` package. Instead, use one of the commands listed in [subsection 3.7](#) (such as `\glsentrytext`) or provide an alternative via the optional argument to the sectioning/caption command. Examples:

```
\section{An overview of \glsentrytext{perl}}
\section[An overview of Perl]{An overview of \gls{perl}}
```

The way the link text is displayed depends on `\glstextformat{<text>}`. For example, to make all link text appear in a sans-serif font, do:

```
\renewcommand*{\glstextformat}[1]{\textsf{#1}}
```

Each entry has an associated conditional referred to as the first use flag. This determines whether `\gls`, `\glspl` (and their uppercase variants) should use the value of the `first` or `text` keys. Note that an entry can be used without affecting the first use flag (for example, when used with `\glslink`). See [subsection 3.11](#) for commands that unset or reset this conditional.

`\glslink`

The command:

```
\glslink[<options>]{<label>}{<text>}
```

will place `\glstextformat{<text>}` in the document at that point and add a line into the associated glossary file for the glossary entry given by `<label>`. If hyperlinks are supported, `<text>` will be a hyperlink to the relevant line in the glossary. The optional argument `<options>` must be a `<key>=<value>` list which can take any of the following keys:

format This specifies how to format the associated location number for this entry in the glossary. This value is equivalent to the `makeindex` `encap` value, and (as with `\index`) the value needs to be the name of a command *without* the initial backslash. As with `\index`, the characters (and) can also be used to specify the beginning and ending of a number range. Again as with `\index`, the command should be the name of a command which takes an argument (which will be the associated location). Be careful not to use a declaration (such as `bfseries`) instead of a text block command (such as `textbf`) as the effect is not guaranteed to be localised. If you want to apply more than one style to a given entry (e.g. `bold` and `italic`) you will need to create a command that applies both formats, e.g.

```
\newcommand*{\textbfem}[1]{\textbf{\emph{#1}}}
```

and use that command.

In this document, the standard formats refer to the standard text block commands such as `\textbf` or `\emph` or any of the commands listed in [table 3](#).

If you use `xindy` instead of `makeindex`, you must specify any non-standard formats that you want to use with the `format` key using `\GlsAddXdyAttribute{<name>}`. So if you use `xindy` with the above example, you would need to add:

```
\GlsAddXdyAttribute{textbfem}
```

Note that unlike `\index`, you can't have anything following the command name, such as an asterisk or arguments. If you want to cross-reference another entry, either use the `see` key when you define the entry or use `\glssee` (described in [subsection 3.6](#)).

If you are using hyperlinks and you want to change the font of the hyperlinked location, don't use `\hyperpage` (provided by the `hyperref` package) as the locations may not refer to a page number. Instead, the `glossaries` package provides number formats listed in [table 3](#).

Table 3: Predefined Hyperlinked Location Formats

<code>hyperrm</code>	serif hyperlink
<code>hypersf</code>	sans-serif hyperlink
<code>hypertt</code>	monospaced hyperlink
<code>hyperbf</code>	bold hyperlink
<code>hypermd</code>	medium weight hyperlink
<code>hyperit</code>	italic hyperlink
<code>hypersl</code>	slanted hyperlink
<code>hyperup</code>	upright hyperlink
<code>hypersc</code>	small caps hyperlink
<code>hyperemph</code>	emphasized hyperlink

Note that if the `\hyperlink` command hasn't been defined, the `hyper<xx>` formats are equivalent to the analogous `text<xx>` font commands (and `hyperemph` is equivalent to `emph`). If you want to make a new format, you will need to define a command which takes one argument and use that; for example, if you want the location number to be in a bold sans-serif font, you can define a command called, say, `\hyperbsf`:

```
\newcommand{\hyperbsf}[1]{\textbf{\hypersetup{#1}}}
```

and then use `hyperbsf` as the value for the `format` key. (See also [subsection 5.15](#).) Remember that if you use `xindy`, you will need to add this to the list of location attributes:

```
\GlsAddXdyAttribute{hyperbsf}
```

counter This specifies which counter to use for this location. This overrides the default counter used by this entry. (See also [subsection 3.3](#).)

hyper This is a boolean key which can be used to enable/disable the hyperlink to the relevant entry in the glossary. (Note that setting `hyper=true` will have no effect if `\hyperlink` has not been defined.) The default value is `hyper=false`.

`\glslink*` There is also a starred version:

```
\glslink*[\langle options \rangle]{\langle label \rangle}{\langle text \rangle}
```

which is equivalent to `\glslink`, except it sets `hyper=false`.

`\gls` The command:

```
\gls[\langle options \rangle]{\langle label \rangle}{\langle insert \rangle}
```

is the same as `\glslink`, except that the link text is determined from the values of the `text` and `first` keys supplied when the entry was defined using `\newglossaryentry`. If the entry has been marked as having been used, the value of the `text` key will be used, otherwise the value of the `first` key will be used. On completion, `\gls` will mark the entry's first use flag as used.

There are two uppercase variants:

`\Gls` `\Gls[\langle options \rangle]{\langle label \rangle}{\langle insert \rangle}`

and

`\GLS` `\GLS[\langle options \rangle]{\langle label \rangle}{\langle insert \rangle}`

which make the first letter of the link text or all the link text uppercase, respectively.

The final optional argument `\langle insert \rangle`, allows you to insert some additional text into the link text. By default, this will append `\langle insert \rangle` at the end of the link text, but this can be changed (see [subsubsection 3.4.1](#)).

The first optional argument `\langle options \rangle` is the same as the optional argument to `\glslink`. As with `\glslink`, these commands also have a starred version that disable the hyperlink.

There are also analogous plural forms:

```
\glsp1  \glsp1[options]{label}[{insert}]  
\Glspl  \Glspl[options]{label}[{insert}]  
\GLSp1  \GLSp1[options]{label}[{insert}]
```

These determine the link text from the `plural` and `firstplural` keys supplied when the entry was first defined. As before, these commands also have a starred version that disable the hyperlink.

Note that `\glslink` doesn't use or affect the first use flag, nor does it use `\glsdisplay` or `\glsdisplayfirst` (see [subsubsection 3.4.1](#)). Instead, you can use:

```
\glsdisp \glsdisp[options]{label}{{link text}}
```

This behaves in the same way as `\gls`, except that it uses `{link text}` instead of the value of the `first` or `text` key. (Note that this command always sets `{insert}` to nothing.)

`\glstext` The command:

```
\glstext[options]{label}[{insert}]
```

is similar to `\gls` except that it always uses the value of the `text` key and does not affect the first use flag. Unlike `\gls`, the inserted text `{insert}` is always appended to the link text since `\glstext` doesn't use `\glsdisplay` or `\glsdisplayfirst`. (The same is true for all the following commands described in this section.)

There are also analogous commands:

```
\Glstext \Glstext[options]{text}[{insert}]  
\GLStext \GLStext[options]{text}[{insert}]
```

As before, these commands also have a starred version that disable the hyperlink.

`\glsfirst` The command:

```
\glsfirst[options]{label}[{insert}]
```

is similar to `\glstext` except that it always uses the value of the `first` key. Again, `{insert}` is always appended to the end of the link text and does not affect the first use flag.

There are also analogous commands:

```
\Glsfirst \Glsfirst[options]{text}[{insert}]  
\GLSfirst \GLSfirst[options]{text}[{insert}]
```

As before, these commands also have a starred version that disable the hyperlink.

`\glsplural` The command:

```
\glsplural[options]{label}[{insert}]
```

is similar to `\glstext` except that it always uses the value of the `plural` key. Again, `\langle insert \rangle` is always appended to the end of the link text and does not mark the entry as having been used.

There are also analogous commands:

```
\Glsplural  \Glsplural[⟨options⟩]{⟨text⟩}[⟨insert⟩]  
\GLSplural \GLSplural[⟨options⟩]{⟨text⟩}[⟨insert⟩]
```

As before, these commands also have a starred version that disable the hyperlink.

`\glsfirstplural`

The command:

```
\glsfirstplural[⟨options⟩]{⟨label⟩}[⟨insert⟩]
```

is similar to `\glstext` except that it always uses the value of the `firstplural` key. Again, `\langle insert \rangle` is always appended to the end of the link text and does not mark the entry as having been used.

There are also analogous commands:

```
\Glsfirstplural \Glsfirstplural[⟨options⟩]{⟨text⟩}[⟨insert⟩]  
\GLSfirstplural \GLSfirstplural[⟨options⟩]{⟨text⟩}[⟨insert⟩]
```

As before, these commands also have a starred version that disable the hyperlink.

`\glsname`

The command:

```
\glsname[⟨options⟩]{⟨label⟩}[⟨insert⟩]
```

is similar to `\glstext` except that it always uses the value of the `name` key. Again, `\langle insert \rangle` is always appended to the end of the link text and does not mark the entry as having been used. Note: if you want to use this command and the `name` key contains commands, you will have to disable the **sanitization** of the `name` key and protect fragile commands.

There are also analogous commands:

```
\Glsname  \Glsname[⟨options⟩]{⟨text⟩}[⟨insert⟩]  
\GLSname \GLSname[⟨options⟩]{⟨text⟩}[⟨insert⟩]
```

As before, these commands also have a starred version that disable the hyperlink.

`\glssymbol`

The command:

```
\glssymbol[⟨options⟩]{⟨label⟩}[⟨insert⟩]
```

is similar to `\glstext` except that it always uses the value of the `symbol` key. Again, `\langle insert \rangle` is always appended to the end of the link text and does not mark the entry as having been used. Note: if you want to use this command and the `symbol` key contains commands, you will have to disable the **sanitization** of the `symbol` key and protect fragile commands.

There are also analogous commands:

```
\Glssymbol \Glssymbol[⟨options⟩]{⟨text⟩}[⟨insert⟩]
```

```
\GLSsymbol \GLSsymbol[options]{text}[insert]
```

As before, these commands also have a starred version that disable the hyperlink.
`\glsdesc` The command:

```
\glsdesc[options]{label}[insert]
```

is similar to `\glostext` except that it always uses the value of the `description` key. Again, `<insert>` is always appended to the end of the link text and does not mark the entry as having been used. Note: if you want to use this command and the `description` key contains commands, you will have to disable the **sanitization** of the `description` key and protect fragile commands.

There are also analogous commands:

```
\Glsdesc \Glsdesc[options]{text}[insert]
```

```
\GLSdesc \GLSdesc[options]{text}[insert]
```

As before, these commands also have a starred version that disable the hyperlink.

3.4.1 Changing the format of the link text

The format of the link text for `\gls`, `\glspl` and their uppercase variants is governed by two commands: `\glsdisplayfirst`, which is used the first time a glossary entry is used in the text and `\glsdisplay`, which is used subsequently. Both commands take four arguments: the first is either the singular or plural form given by the `text`, `plural`, `first` or `firstplural` keys (set when the term was defined) depending on context; the second argument is the term's description (as supplied by the `description` or `descriptionplural` keys); the third argument is the symbol associated with the term (as supplied by the `symbol` or `symbolplural` keys) and the fourth argument is the additional text supplied in the final optional argument to `\gls` or `\glspl` (or their uppercase variants). The default definitions of `\glsdisplay` and `\glsdisplayfirst` simply print the first argument immediately followed by the fourth argument. The remaining arguments are ignored.

`\glslabel` If required, you can access the label for the given entry via `\glslabel`, so it is possible to use this label in the definition of `\glsdisplay` or `\glsdisplayfirst` to supply additional information using any of the commands described in [subsection 3.7](#), if required.

Note that `\glsdisplay` and `\glsdisplayfirst` are not used by `\glslink`. If you want to supply your own link text, you need to use `\glsdisp` instead.

For example, suppose you want a glossary of measurements and units, you can use the `symbol` key to store the unit:

```
\newglossaryentry{distance}{name=distance,  
description={The length between two points},  
symbol={km}}
```

and now suppose you want `\gls{distance}` to produce “distance (km)” on first use, then you can redefine `\glsdisplayfirst` as follows:

```
\renewcommand{\glsdisplayfirst}[4]{#1#4 (#3)}
```

Note that the additional text is placed after #1, so `\gls{distance}['s]` will produce “distance’s (km)” rather than “distance (km)’s” which looks a bit odd (even though it may be in the context of “the distance (km) is measured between the two points” — but in this instance it would be better not to use a contraction).

Note also that all of the link text will be formatted according to `\glstextformat` (described earlier). So if you do, say:

```
\renewcommand{\glstextformat}[1]{\textbf{\#1}}
\renewcommand{\glsdisplayfirst}[4]{\#1\#4 (#3)}
```

then `\gls{distance}` will produce “**distance (km)**”.

If you have multiple glossaries, changing `\glsdisplayfirst` and `\glsdisplay` will change the way entries for all of the glossaries appear when using the commands `\gls`, `\glsp` and their uppercase variants. If you only want the change to affect entries for a given glossary, then you need to use

```
\defglsdisplay \defglsdisplay[<type>]{<definition>}
```

and

```
\defglsdisplayfirst \defglsdisplayfirst[<type>]{<definition>}
```

instead of redefining `\glsdisplay` and `\glsdisplayfirst`.

Both `\defglsdisplay` and `\defglsdisplayfirst` take two arguments: the first (which is optional) is the glossary’s label⁷ and the second is how the term should be displayed when it is invoked using commands `\gls`, `\glsp` and their uppercase variants. This is similar to the way `\glsdisplayfirst` was redefined above.

For example, suppose you have created a new glossary called `notation` and you want to change the way the entry is displayed on first use so that it includes the symbol, you can do:

```
\defglsdisplayfirst[notation]{\#1\#4 (denoted \#3)}
```

Now suppose you have defined an entry as follows:

```
\newglossaryentry{set}{type=notation,
name=set,
description={A collection of objects},
symbol={$\$\$}
}
```

The first time you reference this entry using `\gls` it will be displayed as: “set (denoted *S*)” (similarly for `\glsp` and the uppercase variants).

Remember that if you use the `symbol` key, you need to use a glossary style that displays the symbol, as many of the styles ignore it. In addition, if you want either the description or symbol to appear in the link text, you will have to disable the `sanitization` of these keys and protect fragile commands.

⁷main for the main (default) glossary, `\acronymtype` for the list of acronyms, or the name supplied in the first mandatory argument to `\newglossary` for additional glossaries.

3.4.2 Enabling and disabling hyperlinks to glossary entries

If you load the `hyperref` or `html` packages prior to loading the `glossaries` package, commands such as `\glslink` and `\gls`, described above, will automatically have hyperlinks to the relevant glossary entry, unless the `hyper` option has been set to `false`. You can disable or enable links using:

```
\glsdisablehyper \glsenablehyper
```

and

```
\glsenablehyper \glsenablehyper
```

respectively. The effect can be localised by placing the commands within a group. Note that you should only use `\glsenablehyper` if the commands `\hyperlink` and `\hypertarget` have been defined (for example, by the `hyperref` package).

3.5 Adding an Entry to the Glossary Without Generating Text

`\glsadd` It is possible to add a line in the glossary file without generating any text at that point in the document using:

```
\glsadd[<options>]{<label>}
```

This is similar to `\glslink`, only it doesn't produce any text (so therefore, there is no `hyper` key available in `<options>` but all the other options that can be used with `\glslink` can be passed to `\glsadd`). For example, to add a page range to the glossary number list for the entry whose label is given by `set`:

```
\glsadd[format=()]{set}
Lots of text about sets spanning many pages.
\glsadd[format=()]{set}
```

`\glsaddall` To add all entries that have been defined, use:

```
\glsaddall[<options>]
```

The optional argument is the same as for `\glsadd`, except there is also a key `types` which can be used to specify which glossaries to use. This should be a comma separated list. For example, if you only want to add all the entries belonging to the list of acronyms (specified by the glossary type `\acronymtype`) and a list of notation (specified by the glossary type `notation`) then you can do:

```
\glsaddall[types={\acronymtype,notation}]
```

3.6 Cross-Referencing Entries

There are several ways of cross-referencing entries in the glossary:

1. You can use commands such as `\gls` in the entries description. For example:

```
\newglossaryentry{apple}{name=apple,
description={firm, round fruit. See also \gls{pear}}}
```

Note that with this method, if you don't use the cross-referenced term in the glossary, you will need two runs of `makeglossaries`:

```
latex filename  
makeglossaries filename  
latex filename  
makeglossaries filename  
latex filename
```

2. As described in [subsection 3.2](#), you can use the `see` key when you define the entry. For example:

```
\newglossaryentry{MaclaurinSeries}{name={Maclaurin series},  
description={Series expansion},  
see={TaylorsTheorem}}
```

Note that in this case, the entry with the `see` key will automatically be added to the glossary, but the cross-referenced entry won't. You therefore need to ensure that you use the cross-referenced term with the commands described in [subsection 3.4](#) or [subsection 3.5](#).

You can optionally override the "see" tag using square brackets at the start of the `see` value. For example:

```
\newglossaryentry{MaclaurinSeries}{name={Maclaurin series},  
description={Series expansion},  
see=[see also]{TaylorsTheorem}}
```

3. After you have defined the entry, use

```
\glssee
```

where $\langle xr\ label\ list \rangle$ is a comma-separated list of entry labels to be cross-referenced, $\langle label \rangle$ is the label of the entry doing the cross-referencing and $\langle tag \rangle$ is the "see" tag. For example:

```
\glssee[see also]{series}{FourierSeries,TaylorsTheorem}
```

Note that this automatically adds the entry given by $\langle label \rangle$ to the glossary but doesn't add the cross-referenced entries (specified by $\langle xr\ label\ list \rangle$) to the glossary.

In both cases 2 and 3 above, the cross-referenced information appears in the number list, whereas in case 1, the cross-referenced information appears in the description. In cases 2 and 3, the default text for the "see" tag is given by `\seename`.

3.7 Using Glossary Terms Without Links

The commands described in this section display entry details without adding any information to the glossary. They don't use `\glstextformat`, they don't have any optional arguments, they don't affect the first use flag and, apart from `\glshyperlink`, they don't produce hyperlinks.

```
\glsentryname \glsentryname{\langle label \rangle}  
\Glsentryname \Glsentryname{\langle label \rangle}
```

These commands display the name of the glossary entry given by *<label>*, as specified by the `name` key. `\Glsentryname` makes the first letter uppercase.

```
\glsentrytext \glsentrytext{\langle label \rangle}  
\Glsentrytext \Glsentrytext{\langle label \rangle}
```

These commands display the subsequent use text for the glossary entry given by *<label>*, as specified by the `text` key. `\Glsentrytext` makes the first letter uppercase.

```
\glsentryplural \glsentryplural{\langle label \rangle}  
\Glsentryplural \Glsentryplural{\langle label \rangle}
```

These commands display the subsequent use plural text for the glossary entry given by *<label>*, as specified by the `plural` key. `\Glsentryplural` makes the first letter uppercase.

```
\glsentryfirst \glsentryfirst{\langle label \rangle}  
\Glsentryfirst \Glsentryfirst{\langle label \rangle}
```

These commands display the first use text for the glossary entry given by *<label>*, as specified by the `first` key. `\Glsentryfirst` makes the first letter uppercase.

```
\glsentryfirstplural \glsentryfirstplural{\langle label \rangle}  
\Glsentryfirstplural \Glsentryfirstplural{\langle label \rangle}
```

These commands display the plural form of the first use text for the glossary entry given by *<label>*, as specified by the `firstplural` key. `\Glsentryfirstplural` makes the first letter uppercase.

```
\glsentrydesc \glsentrydesc{\langle label \rangle}  
\Glsentrydesc \Glsentrydesc{\langle label \rangle}
```

These commands display the description for the glossary entry given by *<label>*. `\Glsentrydesc` makes the first letter uppercase.

```
\glsentrydescplural \glsentrydescplural{\langle label \rangle}  
\Glsentrydescplural \Glsentrydescplural{\langle label \rangle}
```

These commands display the plural description for the glossary entry given by *<label>*. `\Glsentrydescplural` makes the first letter uppercase.

```
\glsentrysymbol \glsentrysymbol{\langle label \rangle}  
\Glsentrysymbol \Glsentrysymbol{\langle label \rangle}
```

These commands display the symbol for the glossary entry given by *<label>*. `\Glsentrysymbol` makes the first letter uppercase.

```
\glsentrysymbolplural \glsentrysymbolplural{\langle label \rangle}
```

\Glsentrysymbolplural \Glsentrysymbolplural{\label}

These commands display the plural symbol for the glossary entry given by `\label`. `\Glsentrysymbolplural` makes the first letter uppercase.

\glshyperlink \glshyperlink[\linktext]{\label}

This command provides a hyperlink to the glossary entry given by `\label` **but does not add any information to the glossary file**. The link text is given by `\glsentryname{\label}` by default, but can be overridden using the optional argument.

If you use `\glshyperlink`, you need to ensure that the relevant entry has been added to the glossary using any of the commands described in [subsection 3.4](#) or [subsection 3.5](#) otherwise you will end up with a broken link.

For further information see [subsubsection 5.10.2](#).

3.8 Displaying a glossary

\printglossaries The command `\printglossaries` will display all the glossaries in the order in which they were defined. Note that no glossaries will appear until you have either used the Perl script `makeglossaries` or have directly used `makeindex` or `xindy` (as described in [subsection 1.3](#)). If the glossary still does not appear after you re-L^AT_EX your document, check the `makeindex/xindy` log files to see if there is a problem. Remember that you also need to use the command `\makeglossaries` in the preamble to enable the glossaries.

\printglossary An individual glossary can be displayed using:

\printglossary[\options]

where `\options` is a `\key=\value` list of options. The following keys are available:

type The value of this key specifies which glossary to print. If omitted, the default glossary is assumed. For example, to print the list of acronyms:

\printglossary[type=\acronymtype]

title This is the glossary's title (overriding the title specified when the glossary was defined).

toctitle This is the title to use for the table of contents (if the `toc` package option has been used). If omitted, the glossary title is used.

style This specifies which glossary style to use for this glossary, overriding the effect of the `style` package option or `\glossarystyle`.

numberedsection This specifies whether to use a numbered section for this glossary, overriding the effect of the `numberedsection` package option. This key has the same syntax as the `numberedsection` package option, described in [subsection 3.1](#).

nonumberlist Unlike the package option of the same name, this key is a boolean key. If true (`nonumberlist=true`) the numberlist is suppressed for this glossary. If false (`nonumberlist=false`) the numberlist is displayed for this glossary. If no value is supplied, true is assumed.

\glossarypreamble

Information can be added to the start of the glossary (after the title and before the main body of the glossary) by redefining `\glossarypreamble`. For example:

```
\renewcommand{\glossarypreamble}{Numbers in italic indicate  
primary definitions.}
```

This needs to be done before the glossary is displayed using `\printglossaries` or `\printglossary`. Note that if you want a different preamble for each glossary, you will need to use a separate `\printglossary` for each glossary and change the definition of `\glossarypreamble` between each glossary. For example:

```
\renewcommand{\glossarypreamble}{Numbers in italic indicate  
primary definitions.}  
\printglossary  
\renewcommand{\glossarypreamble}{}  
\printglossary[type=acronym]
```

Alternatively, you can do something like:

```
\renewcommand{\glossarypreamble}{Numbers in italic indicate  
primary definitions.\gdef\glossarypreamble{}}  
\printglossaries
```

which will print the preamble text for the first glossary and change the preamble to do nothing for subsequent glossaries. (Note that `\gdef` is required as the glossary is placed within a group.)

There is an analogous command called `\glossarypostamble` which is placed at the end of each glossary.

3.8.1 Changing the way the entry name appears in the glossary

\glsnamefont

Within each glossary, each entry name is formatted according to `\glsnamefont` which takes one argument: the entry name. This command is always used regardless of the glossary style. By default, `\glsnamefont` simply displays its argument in whatever the surrounding font happens to be. This means that in the list-like glossary styles (defined in the `glossary-list` style file) the name will appear in bold, since the name is placed in the optional argument of `\item`, whereas in the tabular styles (defined in the `glossary-long` and `glossary-super` style files) the name will appear in the normal font. The hierarchical glossary styles (defined in the `glossary-tree` style file) also set the name in bold.

For example, suppose you want all the entry names to appear in medium weight small caps, then you can do:

```
\renewcommand{\glsnamefont}[1]{\textsc{\mdseries #1}}
```

3.8.2 Xindy

If you want to use `xindy` to sort the glossary, you must use the package option `xindy`:

```
\usepackage[xindy]{glossaries}
```

This ensures that the glossary information is written in `xindy` syntax.

Section 1.3 covers how to use the external indexing application. This section covers the commands provided by the `glossaries` package that allow you to adjust the `xindy` style file (`.xdy`) and parameters.

To assist writing information to the `xindy` style file, the `glossaries` package provides the following commands:

```
\glsopenbrace \glsopenbrace  
\glsclosebrace \glsclosebrace
```

which produce an open and closing brace. (This is needed because `\{` and `\}` don't expand to a simple brace character when written to a file.)

In addition, if you are using a package that makes the double quote character active (e.g. `ngerman`) you can use:

```
\glsquote \glsquote{\text{}}
```

which will produce "`\text{}`". Alternatively, you can use `\string` to write the double-quote character. This document assumes that the double quote character has not been made active, so the examples just use " for clarity.

If you want greater control over the `xindy` style file than is available through the L^AT_EX commands provided by the `glossaries` package, you will need to edit the `xindy` style file. In which case, you must use `\noist` to prevent the style file from being overwritten by the `glossaries` package. For additional information about `xindy`, read the `xindy` documentation.

Language and Encodings When you use `xindy`, you need to specify the language and encoding used (unless you have written your own custom `xindy` style file that defines the relevant alphabet and sort rules). If you use `makeglossaries`, this information is obtained from the document's auxiliary (`.aux`) file. The `glossaries` package attempts to find the root language, but in the event that it gets it wrong or if `xindy` doesn't support that language, then you can specify the language using:

```
\GlsSetXdyLanguage \GlsSetXdyLanguage[\text{glossary type}]{\text{language}}
```

where `\text{language}` is the name of the language. The optional argument can be used if you have multiple glossaries in different languages. If `\text{glossary type}` is omitted, it will be applied to all glossaries, otherwise the language setting will only be applied to the glossary given by `\text{glossary type}`.

If the `inputenc` package is used, the encoding will be obtained from the value of `\inputencodingname`. Alternatively, you can specify the encoding using:

```
\GlsSetXdyCodePage \GlsSetXdyCodePage{\text{code}}
```

where `\text{code}` is the name of the encoding. For example:

```
\GlsSetXdyCodePage{utf8}
```

Note that you can also specify the language and encoding using the package option `xindy={language=\text{lang}, codepage=\text{code}}`. For example:

```
\usepackage[xindy={language=english,codepage=utf8}]{glossaries}
```

If you write your own custom `xindy` style file that includes the language settings, you need to set the language to nothing:

```
\GlsSetXdyLanguage{}
```

(and remember to use `\noist` to prevent the style file from being overwritten).

The commands `\GlsSetXdyLanguage` and `\GlsSetXdyCodePage` have no effect if you don't use `makeglossaries`. If you call `xindy` without `makeglossaries` you need to remember to set the language and encoding using the `-L` and `-C` switches.

Locations and Number lists The most likely attributes used in the `format` key (`textrm`, `hyperrm` etc) are automatically added to the `xindy` style file, but if you want to use another attribute, you need to add it using:

```
\GlsAddXdyAttribute \GlsAddXdyAttribute{\langle name\rangle}
```

where `\langle name\rangle` is the name of the attribute, as used in the `format` key. For example, suppose I want a bold, italic, hyperlinked location. I first need to define a command that will do this:

```
\newcommand*{\hyperbfit}[1]{\textit{\hyperbf{#1}}}
```

but with `xindy`, I also need to add this as an allowed attribute:

```
\GlsAddXdyAttribute{\hyperbfit}
```

Note that `\GlsAddXdyAttribute` has no effect if `\noist` is used or if `\makeglossaries` is omitted.

`\GlsAddXdyAttribute` must be used before `\makeglossaries`.

If the location numbers don't get expanded to a simple Arabic or Roman number or a letter from a, ..., z or A, ..., Z, then you need to add a location style in the appropriate format.

For example, suppose you want the page numbers written as words rather than digits and you use the `fmtcount` package to do this. You can redefine `\thepage` as follows:

```
\renewcommand*{\thepage}{\Numberstring{page}}
```

This gets expanded to `\protect \Numberstringnum {\langle n\rangle}` where `\langle n\rangle` is the Arabic page number. This means that you need to define a new location that has that form:

```
\GlsAddXdyLocation{\Numberstring}{:sep "\string\protect\space
\string\Numberstringnum\space\glsclosebrace"
"arabic-numbers" :sep "\glsclosebrace"}
```

Note that it's necessary to use `\space` to indicate that spaces also appear in the format, since, unlike `TeX`, `xindy` doesn't ignore spaces after control sequences.

Note that `\GlsAddXdyLocation` has no effect if `\noist` is used or if `\makeglossaries` is omitted.
`\GlsAddXdyLocation` must be used before `\makeglossaries`.

In the number list, the locations are sorted according to type. The default ordering is: `roman-page-numbers` (e.g. i), `arabic-page-numbers` (e.g. 1), `arabic-section-numbers` (e.g. 1.1 if the compositor is a full stop or 1-1 if the compositor is a hyphen⁸), `alpha-page-numbers` (e.g. a), `Roman-page-numbers` (e.g. I), `Alpha-page-numbers` (e.g. A), `Appendix-page-numbers` (e.g. A.1 if the Alpha compositor is a full stop or A-1 if the Alpha compositor is a hyphen⁹), user defined location names (as specified by `\GlsAddXdyLocation` in the order in which they were defined), `see` (cross-referenced entries). This ordering can be changed using:

```
\GlsSetXdyLocationClassOrder \GlsSetXdyLocationClassOrder{\{location names\}}
```

where each location name is delimited by double quote marks and separated by white space. For example:

```
\GlsSetXdyLocationClassOrder{
    "arabic-page-numbers"
    "arabic-section-numbers"
    "roman-page-numbers"
    "Roman-page-numbers"
    "alpha-page-numbers"
    "Alpha-page-numbers"
    "Appendix-page-numbers"
    "see"
}
```

Note that `\GlsSetXdyLocationClassOrder` has no effect if `\noist` is used or if `\makeglossaries` is omitted.
`\GlsSetXdyLocationClassOrder` must be used before `\makeglossaries`.

If a number list consists of a sequence of consecutive numbers, the range will be concatenated. The number of consecutive locations that causes a range formation defaults to 2, but can be changed using:

```
\GlsSetXdyMinRangeLength \GlsSetXdyMinRangeLength{\{n\}}
```

For example:

```
\GlsSetXdyMinRangeLength{3}
```

The argument may also be the keyword `none`, to indicate that there should be no range formations. See the `xindy` manual for further details on range formations.

⁸see `\setCompositor` described in [subsection 3.2](#)

⁹see `\setAlphaCompositor` described in [subsection 3.2](#)

Note that `\GlsSetXdyMinRangeLength` has no effect if `\noist` is used or if `\makeglossaries` is omitted.
`\GlsSetXdyMinRangeLength` must be used before `\makeglossaries`.

See [subsection 3.3](#) for further details.

Glossary Groups The glossary is divided into groups according to the first letter of the sort key. The `glossaries` package also adds a number group by default, unless you suppress it in the `xindy` package option. For example:

```
\usepackage[xindy={glsnumbers=false}]{glossaries}
```

Any entry that doesn't go in one of the letter groups or the number group is placed in the default group.

If you have a number group, the default behaviour is to locate it before the "A" letter group. If you are not using a Roman alphabet, you can change this using

```
\GlsSetXdyFirstLetterAfterDigits{\langle letter\rangle}
```

Note that `\GlsSetXdyFirstLetterAfterDigits` has no effect if `\noist` is used or if `\makeglossaries` is omitted.

`\GlsSetXdyFirstLetterAfterDigits` must be used before `\makeglossaries`.

3.9 Defining New Glossaries

`\newglossary` A new glossary can be defined using:

```
\newglossary[\langle log-ext\rangle]{\langle name\rangle}{\langle in-ext\rangle}{\langle out-ext\rangle}{\langle title\rangle}{\langle counter\rangle}
```

where `\langle name\rangle` is the label to assign to this glossary. The arguments `\langle in-ext\rangle` and `\langle out-ext\rangle` specify the extensions to give to the input and output files for that glossary, `\langle title\rangle` is the default title for this new glossary and the final optional argument `\langle counter\rangle` specifies which counter to use for the associated number lists (see also [subsection 3.3](#)). The first optional argument specifies the extension for the `makeindex` or `xindy` transcript file (this information is only used by `\makeglossaries` which picks up the information from the auxiliary file).

Note that the main (default) glossary is automatically created as:

```
\newglossary{main}{gls}{glo}{\glossaryname}
```

so it can be identified by the label `main`. Using the `acronym` package option is equivalent to:

```
\newglossary[alg]{acronym}{acr}{acn}{\acronymname}
```

so it can be identified by the label `acronym`. If you are not sure whether the `acronym` option has been used, you can identify the list of acronyms by the command `\acronymtype` which is set to `acronym`, if the `acronym` option has been used, otherwise it is set to `main`.

All glossaries must be defined before `\makeglossaries` to ensure that the relevant output files are opened.

3.10 Acronyms

`\newacronym` You may have noticed in [subsection 3.2](#) that when you specify a new entry, you can specify alternate text to use when the term is first used in the document. This provides a useful means to define acronyms. For convenience, the `glossaries` package defines the command:

```
\newacronym[⟨key-val list⟩]{⟨label⟩}{⟨abbrv⟩}{⟨long⟩}
```

By default, this is equivalent to:

```
\newglossaryentry{⟨label⟩}{type=\acronymtype,
  name={⟨abbrv⟩},
  description={⟨long⟩},
  text={⟨abbrv⟩},
  first={⟨long⟩ ⟨⟨abbrv⟩⟩},
  plural={⟨abbrv⟩\glspluralsuffix},
  firstplural={⟨long⟩\glspluralsuffix\space ⟨⟨abbrv⟩\glspluralsuffix⟩},
  ⟨key-val list⟩}
```

As mentioned in the previous section, the command `\acronymtype` is the name of the glossary in which the acronyms should appear. If the `acronym` package option has been used, this will be `acronym`, otherwise it will be `main`. The acronyms can then be used in exactly the same way as any other glossary entry.

Note: since `\newacronym` sets `type=\acronymtype`, if you want to load a file containing acronym definitions using `\loadglsentries[⟨type⟩]{⟨filename⟩}`, the optional argument `⟨type⟩` will not have an effect unless you explicitly set the type as `type=\glsdefaulttype` in the optional argument to `\newacronym`. See [subsubsection 3.2.3](#).

For example, the following defines the acronym IDN:

```
\newacronym{idn}{IDN}{identification number}
```

This is equivalent to:

```
\newglossaryentry{idn}{type=\acronymtype,
  name={IDN},
  description={identification number},
  text={IDN},
  first={identification number (IDN)},
  plural={IDNs},
  firstplural={identification numbers (IDNs)}}
```

so `\gls{idn}` will produce “identification number (IDN)” on first use and “IDN” on subsequent uses.

This section describes acronyms that have been defined using `\newacronym`. If you prefer to define all your acronyms using `\newglossaryentry` explicitly, then you should skip this section and ignore the package options: `smallcaps`, `smaller`, `description`, `dua` and `footnote`, as these options change the definition of `\newacronym` for common acronym formats as well as the way that the link text is displayed (see [subsubsection 3.4.1](#)). Likewise you should ignore the package option `shortcuts`

and the new commands described in this section, such as `\acrshort`, as they vary according to the definition of `\newacronym`.

If you use any of the package options `smallcaps`, `smaller`, `description` or `footnote`, the acronyms will be displayed in the document using:

```
\acronymfont \acronymfont{\text{}}
```

and

```
\firstacronymfont \firstacronymfont{\text{}}
```

where `\firstacronymfont` is applied on first use and `\acronymfont` is applied on subsequent use. Note that if you don't use any of the above package options, changing the definition of `\acronymfont` or `\firstacronymfont` will have no effect. In this case, the recommended route is to use either the `smaller` or the `smallcaps` package option and redefine `\acronymfont` and `\firstacronymfont` as required. (The `smallcaps` option sets the default plural suffix in an upright font to cancel the effect of `\textsc`, whereas `smaller` sets the suffix in the surrounding font.) For example, if you want acronyms in a normal font on first use and emphasized on subsequent use, do:

```
\usepackage[smaller]{glossaries}
\renewcommand*\firstacronymfont[1]{\#1}
\renewcommand*\acronymfont[1]{\emph{\#1}}
```

(Note that it is for this reason that the `relsize` package is not automatically loaded when selecting the `smaller` package option.)

[Table 4](#) lists the package options that govern the acronym styles and how the `\newglossaryentry` keys are used to store `\long` (the long form) and `\abbrv` (the short form). Note that the `smallcaps` option redefines `\acronymfont` so that it sets its argument using `\textsc` (so you should use lower case characters in `\abbrv`) and the `smaller` option redefines `\acronymfont` to use `\textsmaller`,¹⁰ otherwise `\acronymfont` simply displays its argument in the surrounding font.

Table 4: Package options governing `\newacronym` and how the information is stored in the keys for `\newglossaryentry`

Package Option	first key	text key	description key	symbol key
<code>description,footnote</code>	<code>\abbrv</code>	<code>\abbrv</code>	user supplied	<code>\long</code>
<code>description,dua</code>	<code>\long</code>	<code>\long</code>	user supplied	<code>\abbrv</code>
<code>description</code>	<code>\long</code>	<code>\abbrv</code>	user supplied	<code>\abbrv</code>
<code>footnote</code>	<code>\abbrv</code>	<code>\abbrv</code>	<code>\long</code>	
<code>smallcaps</code>	<code>\long</code>	<code>\abbrv</code>	<code>\long</code>	<code>\abbrv</code>
<code>smaller</code>	<code>\long</code>	<code>\abbrv</code>	<code>\long</code>	<code>\abbrv</code>
<code>dua</code>	<code>\long</code>	<code>\long</code>	<code>\long</code>	<code>\abbrv</code>
None of the above	<code>\long</code> (<code>\abbrv</code>)	<code>\abbrv</code>	<code>\long</code>	

¹⁰you will need to load a package, such as `relsize`, that defines `\textsmaller` if you use this option.

In case you can't remember which key stores the long or short forms (or their plurals) the `glossaries` package provides the commands:

- | | |
|---------------------------------|---|
| <code>\glsshortkey</code> | • <code>\glsshortkey</code> The key used to store the short form. |
| <code>\glsshortpluralkey</code> | • <code>\glsshortpluralkey</code> The key used to store the plural version of the short form. |
| <code>\glslongkey</code> | • <code>\glslongkey</code> The key used to store the long form. |
| <code>\glslongpluralkey</code> | • <code>\glslongpluralkey</code> The key used to store the plural version of the long form. |

These can be used in the optional argument of `\newacronym` to override the defaults. For example:

```
\newacronym[\glslongpluralkey={diagonal matrices}]{dm}{DM}{diagonal matrix}
```

If the first use uses the plural form, `\glsp{dm}` will display: diagonal matrices (DMs).

Each of the package options `smallcaps`, `smaller`, `footnote`, `dua` and `description` use `\defglsdisplay` and `\defglsdisplayfirst` (described in [subsubsection 3.4.1](#)) to change the way the link text is displayed. This means that these package options only work for the glossary type given by `\acronymtype`. If you have multiple lists of acronyms, you will need to make the appropriate changes for each additional glossary type.

description,footnote

When these two package options are used together, the first use displays the entry as:

```
\firstacronymfont{\textit{abbrv}}\textit{insert}\footnote{\textit{long}}
```

while subsequent use displays the entry as:

```
\acronymfont{\textit{abbrv}}\textit{insert}
```

where `\textit{insert}` indicates the text supplied in the final optional argument to `\gls`, `\glsp` or their uppercase variants.

In this case, the long form is stored in the `symbol` key. This means that the long form will not be displayed in the list of acronyms unless you use a glossary style that displays the entry's symbol (for example, the `index` style). Entries will be sorted according to the short form.

Note also that when these two package options are used (in the given order), the `glossaries` package additionally implements the `sanitize` option using `sanitize={description=false,symbol=false}`, so remember to protect fragile commands when defining acronyms.

dua

The `dua` package option always displays the expanded form and so may not be used with `footnote`, `smaller` or `smallcaps`. Both first use and subsequent

use displays the entry in the form:

```
long< iinsert >
```

If the **description** package option is also used, the **name** key is set to the long form, otherwise the **name** key is set to the short form and the **description** key is set to the long form. In both cases the **symbol** is set to the short form. Therefore, if you use the **description** package option and you want the short form to appear in the list of acronyms, you will need to use a glossary style that displays the entry's symbol (for example, the **index** style). Entries will be sorted according to the long form if the **description** option is used, otherwise they will be sorted according to the short form (unless overridden by the **sort** key in the optional argument of **\newacronym**).

description

This package option displays the entry on first use as:

```
long< iinsert > (\firstacronymfont{\abrv})
```

while subsequent use displays the entry as:

```
\acronymfont{\abrv}< iinsert >
```

Note also that if this package option is used, the **glossaries** package additionally implements the option **sanitize={symbol=false}**, so remember to protect fragile commands when defining acronyms.

\acrnameformat

Note that with this option, you need to specify the description using the **description** key in the optional argument of **\newacronym**. When this option is used without the **footnote** or **dua** options, the name field is specified as **\acrnameformat{\short}{\long}**. This defaults to **\acronymfont{\short}**, which means that the long form will not appear in the list of acronyms by default. To change this, you need to redefine **\acrnameformat** as appropriate. For example, to display the long form followed by the short form in parentheses do:

```
\renewcommand*{\acrnameformat}[2]{#2 (\acronymfont{#1})}
```

Note that even if you redefine **\acrnameformat**, the entries will be sorted according to the short form, unless you override this using the **sort** key in the optional argument to **\newacronym**.

footnote

This package option displays the entry on first use as:

```
\firstacronymfont{\abrv}< iinsert >\footnote{\long}
```

while subsequent use displays the entry as:

```
\acronymfont{\abrv}< iinsert >
```

Acronyms will be sorted according to the short form.

Note also that if this package option is used, the `glossaries` package additionally implements the option `sanitize={description=false}`, so remember to protect fragile commands when defining acronyms.

Note that on first use, it is the long form in the footnote that links to the relevant glossary entry (where hyperlinks are enabled), whereas on subsequent use, the acronym links to the relevant glossary entry. It is possible to change this to make the acronym on first use have the hyperlink instead of the footnote, but since the footnote marker will also be a hyperlink, you will have two hyperlinks in immediate succession. This can be ambiguous where the hyperlinks are coloured rather than boxed. The code required to change the first use to make the acronym a hyperlink is as follows:

```
\def\glsdisplayfirst[\acronymtype]{%
\noexpand\protect\noexpand
  \glslink[@gls@link@opts]{\gls@link@label}{\firstacronymfont{\#1}\#4}%
\noexpand\protect\noexpand\footnote{\#2}}%
```

Note that this involves using internal commands (i.e. commands whose name contains an @ character), so if this code is placed in a `.tex` file it needs to be placed within a `\makeatletter ... \makeatother` pair. (See <http://www.tex.ac.uk/cgi-bin/texfaq2html?label=atsigns> for further details.)

smallcaps

If neither the `footnote` nor `description` options have been set, this option displays the entry on first use as:

`(long)<insert> (\firstacronymfont{(abbrv)})`

while subsequent use displays the entry as:

`\acronymfont{(abbrv)}<insert>`

where `\acronymfont` is set to `\textsc{#1}`.

Note that since the acronym is displayed using `\textsc`, the short form, `(abbrv)`, should be specified in lower case. (Recall that `\textsc{abc}` produces ABC whereas `\textsc{ABC}` produces ABC.)

Note also that if this package option is used, the `glossaries` package additionally implements the option `sanitize={symbol=false}`, so remember to protect fragile commands when defining acronyms.

smaller

If neither the `footnote` nor `description` options have been set, this option displays the entry on first use as:

`(long)<insert> (\firstacronymfont{(abbrv)})`

while subsequent use displays the entry as:

```
\acronymfont{\langle abrv \rangle} \langle insert \rangle
```

where `\acronymfont` is set to `\textsmaller{#1}`.¹¹ The entries will be sorted according to the short form.

Remember to load a package that defines `\textsmaller` (such as `relsize`) if you want to use this option, unless you want to redefine `\acronymfont` to use some other formatting command.

Note also that if this package option is used, the `glossaries` package additionally implements the option `sanitize={symbol=false}`, so remember to protect fragile commands when defining acronyms.

None of the above

If none of the package options `smallcaps`, `smaller`, `footnote`, `dua` or `description` are used, then on first use the entry is displayed as:

```
\langle long \rangle (\langle abrv \rangle) \langle insert \rangle
```

while subsequent use displays the entry as:

```
\langle abrv \rangle \langle insert \rangle
```

Entries will be sorted according to the short form. Note that if none of the acronym-related package options are used, the `sanitize` option will not be affected.

Recall from [subsection 3.4](#) that you can access the values of individual keys using commands like `\glstext`, so it is possible to use these commands to print just the long form or just the abbreviation without affecting the flag that determines whether the entry has been used. However the keys that store the long and short form vary depending on the acronym style, so the `glossaries` package provides commands that are set according to the package options. These are as follows:

```
\acrshort \acrshort[\langle options \rangle]{\langle label \rangle}[\langle insert \rangle]  
\Acrshort \ACRshort[\langle options \rangle]{\langle label \rangle}[\langle insert \rangle]  
\ACRshort \ACRshort[\langle options \rangle]{\langle label \rangle}[\langle insert \rangle]
```

Print the abbreviated version with (if required) a hyperlink to the relevant entry in the glossary. This is usually equivalent to `\glstext` (or its uppercase variants) but may additionally put the link text within the argument to `\acronymfont`.

```
\acrlong \acrlong[\langle options \rangle]{\langle label \rangle}[\langle insert \rangle]  
\Acrlong \ACRlong[\langle options \rangle]{\langle label \rangle}[\langle insert \rangle]  
\ACRlong \ACRlong[\langle options \rangle]{\langle label \rangle}[\langle insert \rangle]
```

Print the long version with (if required) a hyperlink to the relevant entry in the

¹¹not that this was change from using `\smaller` to `\textsmaller` as declarations cause a problem for `\makefirstuc`.

glossary. This is may be equivalent to `\glsdesc`, `\glssymbol` or `\glsfirst` (or their uppercase variants), depending on package options.

```
\acrfull  \acrfull[options]{label}[{insert}]
\Acrfull \ACRfull[options]{label}[{insert}]
\ACRfull \ACRfull[options]{label}[{insert}]
```

Print the long version followed by the abbreviation in brackets with (if required) a hyperlink to the relevant entry in the glossary.

Note that if any of the above commands produce unexpected output and you haven't used any of the acronym-related package options, you will need to switch off the sanitization. For example:

```
\usepackage[sanitize=none]{glossaries}
```

However, if you do this, you must remember to protect fragile commands when defining acronyms or glossary entries.

Note that if you change the definition of `\newacronym`, you may additionally need to change the above commands as well as changing the way the text is displayed using `\defglsdisplay` and `\defglsdisplayfirst`.

The package option `shortcuts` provides the synonyms listed in [table 5](#). If any of those commands generate an “undefined control sequence” error message, check that you have enabled the `shortcuts` package option. Note that there are no shortcuts for the commands that produce all upper case text.

Table 5: Synonyms provided by the package option `shortcuts`

Shortcut Command	Equivalent Command
<code>\acs</code>	<code>\acrshort</code>
<code>\Acs</code>	<code>\Acrshort</code>
<code>\acsp</code>	<code>\acrshortpl</code>
<code>\Acsp</code>	<code>\Acrshortpl</code>
<code>\acl</code>	<code>\acrlong</code>
<code>\Acl</code>	<code>\Acrlong</code>
<code>\aclp</code>	<code>\acrlongpl</code>
<code>\Aclp</code>	<code>\Acrlongpl</code>
<code>\acf</code>	<code>\acrfull</code>
<code>\Acf</code>	<code>\Acrfull</code>
<code>\acfp</code>	<code>\acrfullpl</code>
<code>\Acfp</code>	<code>\Acrfullpl</code>
<code>\ac</code>	<code>\gls</code>
<code>\Ac</code>	<code>\Gls</code>
<code>\ACP</code>	<code>\glspl</code>
<code>\Acp</code>	<code>\Glspl</code>

3.10.1 Upgrading From the glossary Package

Users of the obsolete `glossary` package may recall that the syntax used to define new acronyms has changed with the replacement `glossaries` package. In addition, the old `glossary` package created the command `\(\langle acr-name \rangle)` when defining the acronym `\(\langle acr-name \rangle)`.

In order to facilitate migrating from the old package to the new one, the `glossaries` package¹² provides the command:

```
\oldacronym \oldacronym[\langle label \rangle]{\langle abbrv \rangle}{\langle long \rangle}{\langle key-val list \rangle}
```

This uses the same syntax as the `glossary` package's method of defining acronyms. It is equivalent to:

```
\newacronym[\langle key-val list \rangle]{\langle label \rangle}{\langle abbrv \rangle}{\langle long \rangle}
```

In addition, `\oldacronym` also defines the commands `\(\langle label \rangle)`, which is equivalent to `\gls{\langle label \rangle}`, and `\(\langle label \rangle*`, which is equivalent to `\Gls{\langle label \rangle}`. If `\langle label \rangle` is omitted, `\langle abrv \rangle` is used. Since commands names must consist only of alphabetical characters, `\langle label \rangle` must also only consist of alphabetical characters. Note that `\(\langle label \rangle)` doesn't allow you to use the first optional argument of `\gls` or `\Gls` — you will need to explicitly use `\gls` or `\Gls` to change the settings.

Recall that, in general, L^AT_EX ignores spaces following command names consisting of alphabetical characters. This is also true for `\(\langle label \rangle)` unless you additionally load the `xspace` package.

The `glossaries` package doesn't load the `xspace` package since there are both advantages and disadvantages to using `\xspace` in `\(\langle label \rangle)`. If you don't use the `xspace` package you need to explicitly force a space using `_` (backslash space) however you can follow `\(\langle label \rangle)` with additional text in square brackets (the final optional argument to `\gls`). If you use the `xspace` package you don't need to escape the spaces but you can't use the optional argument to insert text (you will have to explicitly use `\gls`).

To illustrate this, suppose I define the acronym "abc" as follows:

```
\oldacronym{abc}{example acronym}{}{}
```

This will create the command `\abc` and its starred version `\abc*`. Table 6 illustrates the effect of `\abc` (on subsequent use) according to whether or not the `xspace` package has been loaded. As can be seen from the final row in the table, the `xspace` package prevents the optional argument from being recognised.

3.11 Unsetting and Resetting Entry Flags

When using `\gls`, `\glsp` and their uppercase variants it is possible that you may want to use the value given by the `first` key, even though you have already used the glossary entry. Conversely, you may want to use the value given by the `text` key, even though you haven't used the glossary entry. The former can be achieved by one of the following commands:

¹²as from version 1.18

Table 6: The effect of using `xspace` with `\oldacronym`

Code	With <code>xspace</code>	Without <code>xspace</code>
<code>\abc.</code>	abc.	abc.
<code>\abc xyz</code>	abc xyz	abcxyz
<code>\abc\ xyz</code>	abc xyz	abc xyz
<code>\abc* xyz</code>	Abc xyz	Abc xyz
<code>\abc['s] xyz</code>	abc ['s] xyz	abc's xyz

```
\glsreset \glsreset{<label>}
\glslocalreset \glslocalreset{<label>}
```

while the latter can be achieved by one of the following commands:

```
\glsunset \glsunset{<label>}
\glslocalunset \glslocalunset{<label>}
```

You can also reset or unset all entries for a given glossary or list of glossaries using:

```
\glsresetall \glsresetall[<glossary list>]
\glslocalresetall \glslocalresetall[<glossary list>]
\glsunsetall \glsunsetall[<glossary list>]
\glslocalunsetall \glslocalunsetall[<glossary list>]
```

where $\langle \text{glossary list} \rangle$ is a comma-separated list of glossary labels. If omitted, all defined glossaries are assumed. For example, to reset all entries in the main glossary and the list of acronyms:

```
\glsresetall[main,acronym]
```

You can determine whether an entry's first use flag is set using:

```
\ifglsused \ifglsused{<label>}{<true part>}{<false part>}
```

where $\langle \text{label} \rangle$ is the label of the required entry. If the entry has been used, $\langle \text{true part} \rangle$ will be done, otherwise $\langle \text{false part} \rangle$ will be done.

3.12 Glossary Styles

The `glossaries` package comes with some pre-defined glossary styles. Note that the styles are suited to different types of glossaries: some styles ignore the associated symbol; some styles are not designed for hierarchical entries, so they display sub-entries in the same way as they display top level entries; some styles are designed for homographs, so they ignore the name for sub-entries. You should therefore pick a style that suits your type of glossary. See [table 7](#) for a summary of the available styles.

The glossary style can be set using the `style` package option or using the `style` key in the optional argument to `\printglossary` or using the command:

```
\glossarystyle \glossarystyle{<style-name>}
```

Table 7: Glossary Styles. An asterisk in the style name indicates anything that matches that doesn't match any previously listed style (e.g. `long3col*` matches `long3col`, `long3colheader`, `long3colborder` and `long3colheaderborder`). A maximum level of 0 indicates a flat glossary (sub-entries are displayed in the same way as main entries). Where the maximum level is given as — there is no limit, but note that `makeindex` imposes a limit of 2 sub-levels. If the homograph column is checked, then the name is not displayed for sub-entries. If the symbol column is checked, then the symbol will be displayed if it has been defined.

Style	Maximum Level	Homograph	Symbol
<code>listdotted</code>	0		
<code>sublistdotted</code>	1		
<code>list*</code>	1	✓	
<code>altlist*</code>	1	✓	
<code>long3col*</code>	1	✓	
<code>long4col*</code>	1	✓	✓
<code>altsuper4col*</code>	1	✓	✓
<code>long*</code>	1	✓	
<code>super3col*</code>	1	✓	
<code>super4col*</code>	1	✓	✓
<code>altsuper4col*</code>	1	✓	✓
<code>super*</code>	1	✓	
<code>index*</code>	2		✓
<code>treenoname*</code>	—	✓	✓
<code>tree*</code>	—		✓
<code>alttree*</code>	—		✓

```
\glsdescwidth  
\glspagelistwidth
```

The tabular-like styles that allow multi-line descriptions and page lists use the length `\glsdescwidth` to set the width of the description column and the length `\glspagelistwidth` to set the width of the page list column.¹³ These will need to be changed using `\setlength` if the glossary is too wide. Note that the `long4col` and `super4col` styles (and their header and border variations) don't use these lengths as they are designed for single line entries. Instead you should use the analogous `altnlong4col` and `altsuper4col` styles. If you want to explicitly create a line-break within a multi-line description in a tabular-like style you should use `\newline` instead of `\\".`

Note that if you use the `style` key in the optional argument to `\printglossary`, it will override any previous style settings for the given glossary, so if, for example, you do

```
\renewcommand*\glsgroupskip{}  
\printglossary[style=long]
```

then the new definition of `\glsgroupskip` will not have an affect for this glossary, as `\glsgroupskip` is redefined by `style=long`. Likewise, `\glossarystyle` will also override any previous style definitions, so, again

```
\renewcommand*\glsgroupskip{}  
\glossarystyle{long}
```

will reset `\glsgroupskip` back to its default definition for the named glossary style (`long` in this case). If you want to modify the styles, either use `\newglossarystyle` (described in the next section) or make the modifications after `\glossarystyle`, e.g.:

```
\glossarystyle{long}  
\renewcommand*\glsgroupskip{}
```

`\glspostdescription`

All the styles except for the three- and four-column styles and the `listdotted` style use the command `\glspostdescription` after the description. This simply displays a full stop by default. To eliminate this full stop (or replace it with something else, say a comma) you will need to redefine `\glspostdescription` before the glossary is displayed. Alternatively, you can suppress it for a given entry by placing `\nopostdesc` in the entry's description.

3.12.1 List Styles

The styles described in this section are all defined in the package `glossary-list`. Since they all use the `description` environment, they are governed by the same parameters as that environment. These styles all ignore the entry's symbol. Note that these styles will not be available if you use either the `nolist` or `nostyles` package options.

list The `list` style uses the `description` environment. The entry name is placed in the optional argument of the `\item` command (so it will appear in bold by default). The description follows, and then the associated number list for that entry. The symbol is ignored. If the entry has child entries, the description and number list follows (but not the name) for each child entry. Groups are separated using `\indexspace`.

¹³these lengths will not be available if you use both the `nolong` and `nosuper` package options or if you use the `nostyles` package option.

`\glshypernavsep`

listgroup The `listgroup` style is like `list` but the glossary groups have headings.

listhypergroup The `listhypergroup` style is like `listgroup` but has a navigation line at the start of the glossary with links to each group that is present in the glossary. This requires an additional run through L^AT_EX to ensure the group information is up to date. In the navigation line, each group is separated by `\glshypernavsep` which defaults to a vertical bar with a space on either side. For example, to simply have a space separating each group, do:

```
\renewcommand*{\glshypernavsep}{\space}
```

Note that the hyper-navigation line is now (as from version 1.14) set inside the optional argument to `\item` instead of after it to prevent a spurious space at the start. This can be changed by redefining `\glossaryheader`, but note that this needs to be done *after* the glossary style has been set.

altlist The `altlist` style is like `list` but the description starts on the line following the name. (As with the `list` style, the symbol is ignored.) Each child entry starts a new line, but as with the `list` style, the name associated with each child entry is ignored.

altlistgroup The `altlistgroup` style is like `altlist` but the glossary groups have headings.

altlisthypergroup The `altlisthypergroup` style is like `altlistgroup` but has a set of links to the glossary groups. The navigation line is the same as that for `listhypergroup`, described above.

listdotted This style uses the `description` environment.¹⁴ Each entry starts with `\item[]`, followed by the name followed by a dotted line, followed by the description. Note that this style ignores both the number list and the symbol. The length `\glslistdottedwidth` governs where the description should start. This is a flat style, so child entries are formatted in the same way as the parent entries.

sublistdotted This is a variation on the `listdotted` style designed for hierarchical glossaries. The main entries have just the name displayed. The sub entries are displayed in the same manner as `listdotted`.

3.12.2 Longtable Styles

The styles described in this section are all defined in the package `glossary-long`. Since they all use the `longtable` environment, they are governed by the same parameters as that environment. Note that these styles will not be available if you use either the `nolong` or `nostyles` package options.

long The `long` style uses the `longtable` environment (defined by the `longtable` package). It has two columns: the first column contains the entry's name and the second column contains the description followed by the number list. The entry's symbol is ignored. Sub groups are separated with a blank row. The width of the first column is governed by the widest entry in that column.

¹⁴This style was supplied by Axel Menzel.

The width of the second column is governed by the length `\glsdescwidth`. Child entries have a similar format to the parent entries except that their name is suppressed.

longborder The `longborder` style is like `long` but has horizontal and vertical lines around it.

longheader The `longheader` style is like `long` but has a header row.

longheaderborder The `longheaderborder` style is like `longheader` but has horizontal and vertical lines around it.

long3col The `long3col` style is like `long` but has three columns. The first column contains the entry's name, the second column contains the description and the third column contains the number list. The entry's symbol is ignored. The width of the first column is governed by the widest entry in that column, the width of the second column is governed by the length `\glsdescwidth`, and the width of the third column is governed by the length `\glspagelistwidth`.

long3colborder The `long3colborder` style is like the `long3col` style but has horizontal and vertical lines around it.

long3colheader The `long3colheader` style is like `long3col` but has a header row.

long3colheaderborder The `long3colheaderborder` style is like `long3colheader` but has horizontal and vertical lines around it.

long4col The `long4col` style is like `long3col` but has an additional column in which the entry's associated symbol appears. This style is used for brief single line descriptions. The column widths are governed by the widest entry in the given column. Use `altslong4col` for multi-line descriptions.

long4colborder The `long4colborder` style is like the `long4col` style but has horizontal and vertical lines around it.

long4colheader The `long4colheader` style is like `long4col` but has a header row.

long4colheaderborder The `long4colheaderborder` style is like `long4colheader` but has horizontal and vertical lines around it.

altslong4col The `altslong4col` style is like `long4col` but allows multi-line descriptions and page lists. The width of the description column is governed by the length `\glsdescwidth` and the width of the page list column is governed by the length `\glspagelistwidth`. The widths of the name and symbol columns are governed by the widest entry in the given column.

altslong4colborder The `altslong4colborder` style is like the `long4colborder` but allows multi-line descriptions and page lists.

altslong4colheader The `altslong4colheader` style is like `long4colheader` but allows multi-line descriptions and page lists.

altslong4colheaderborder The `altslong4colheaderborder` style is like `long4colheaderborder` but allows multi-line descriptions and page lists.

3.12.3 Supertabular Styles

The styles described in this section are all defined in the package `glossary-super`. Since they all use the `supertabular` environment, they are governed by the same parameters as that environment. Note that these styles will not be available if you use either the `nosuper` or `nostyles` package options. In general, the `longtable` environment is better, but there are some circumstances where it is better to use `supertabular`.¹⁵

super The `super` style uses the `supertabular` environment (defined by the `supertabular` package). It has two columns: the first column contains the entry's name and the second column contains the description followed by the number list. The entry's symbol is ignored. Sub groups are separated with a blank row. The width of the first column is governed by the widest entry in that column. The width of the second column is governed by the length `\glsdescwidth`. Child entries have a similar format to the parent entries except that their name is suppressed.

superborder The `superborder` style is like `super` but has horizontal and vertical lines around it.

superheader The `superheader` style is like `super` but has a header row.

superheaderborder The `superheaderborder` style is like `superheader` but has horizontal and vertical lines around it.

super3col The `super3col` style is like `super` but has three columns. The first column contains the entry's name, the second column contains the description and the third column contains the number list. The entry's symbol is ignored. The width of the first column is governed by the widest entry in that column. The width of the second column is governed by the length `\glsdescwidth`. The width of the third column is governed by the length `\glspagelistwidth`.

super3colborder The `super3colborder` style is like the `super3col` style but has horizontal and vertical lines around it.

super3colheader The `super3colheader` style is like `super3col` but has a header row.

super3colheaderborder The `super3colheaderborder` style is like `super3colheader` but has horizontal and vertical lines around it.

super4col The `super4col` style is like `super3col` but has an additional column in which the entry's associated symbol appears. This style is designed for entries with brief single line descriptions. The column widths are governed by the widest entry in the given column. Use `altsuper4col` for multi-line descriptions.

super4colborder The `super4colborder` style is like the `super4col` style but has horizontal and vertical lines around it.

¹⁵e.g. with the `flowfram` package.

super4colheader The `super4colheader` style is like `super4col` but has a header row.

super4colheaderborder The `super4colheaderborder` style is like `super4colheader` but has horizontal and vertical lines around it.

altsuper4col The `altsuper4col` style is like `super4col` but allows multi-line descriptions and page lists. The width of the description column is governed by the length `\glsdescwidth` and the width of the page list column is governed by the length `\glspagelistwidth`. The width of the name and symbol columns is governed by the widest entry in the given column.

altsuper4colborder The `altsuper4colborder` style is like the `super4colborder` style but allows multi-line descriptions and page lists.

altsuper4colheader The `altsuper4colheader` style is like `super4colheader` but allows multi-line descriptions and page lists.

altsuper4colheaderborder The `altsuper4colheaderborder` style is like `super4colheaderborder` but allows multi-line descriptions and page lists.

3.12.4 Tree-Like Styles

The styles described in this section are all defined in the package `glossary-tree`. These styles are designed for hierarchical glossaries but can also be used with glossaries that don't have sub-entries. These styles will display the entry's symbol if it exists. Note that these styles will not be available if you use either the `notree` or `nostyles` package options.

index The `index` style is similar to the way indices are usually formatted in that it has a hierarchical structure up to three levels (the main level plus two sub-levels). The name is typeset in bold, and if the symbol is present it is set in parentheses after the name and before the description. Sub-entries are indented and also include the name, the symbol in brackets (if present) and the description. Groups are separated using `\indexspace`.

indexgroup The `indexgroup` style is similar to the `index` style except that each group has a heading.

indexhypergroup The `indexhypergroup` style is like `indexgroup` but has a set of links to the glossary groups. The navigation line is the same as that for `listhypergroup`, described above.

`\glstreeindent`

tree The `tree` style is similar to the `index` style except that it can have arbitrary levels. (Note that `makeindex` is limited to three levels, so you will need to use `xindy` if you want more than three levels.) Each sub-level is indented by `\glstreeindent`. Note that the name, symbol (if present) and description are placed in the same paragraph block. If you want the name to be apart from the description, use the `almtree` style instead. (See below.)

treegroup The `treegroup` style is similar to the `tree` style except that each group has a heading.

treehypergroup The treehypergroup style is like treegroup but has a set of links to the glossary groups. The navigation line is the same as that for listhypergroup, described above.

treenoname The treenoname style is like the tree style except that the name for each sub-entry is ignored.

treenonamegroup The treenonamegroup style is similar to the treenoname style except that each group has a heading.

treenonamehypergroup The treenonamehypergroup style is like treenonamegroup but has a set of links to the glossary groups. The navigation line is the same as that for listhypergroup, described above.

alttree The alttree style is similar to the tree style except that the indentation for each level is determined by the width of the text specified by

```
\glssetwidest \glssetwidest[<level>]{<text>}
```

The optional argument *<level>* indicates the level, where 0 indicates the top-most level, 1 indicates the first level sub-entries, etc. If `\glssetwidest` hasn't been used for a given sub-level, the level 0 widest text is used instead. If *<level>* is omitted, 0 is assumed.

For each level, the name is placed to the left of the paragraph block containing the symbol (optional) and the description. If the symbol is present, it is placed in parentheses before the description.

alttreegroup The alttreegroup is like the alttree style except that each group has a heading.

alttreehypergroup The alttreehypergroup style is like alttreegroup but has a set of links to the glossary groups. The navigation line is the same as that for listhypergroup, described above.

3.13 Defining your own glossary style

If the predefined styles don't fit your requirements, you can define your own style using:

```
\newglossarystyle{<name>}{<definitions>}
```

where *<name>* is the name of the new glossary style (to be used in `\glossarystyle`). The second argument *<definitions>*, needs to redefine all of the following:

```
theGLOSSARY theGLOSSARY
```

This environment defines how the main body of the glossary should be typeset. Note that this does not include the section heading, the glossary preamble (defined by `\glossarypreamble`) or the glossary postamble (defined by `\glossarypostamble`). For example, the list style uses the `description` environment, so the `theGLOSSARY` environment is simply redefined to begin and end the `description` environment.

<code>\glossaryheader</code>	<code>\glossaryheader</code>	This macro indicates what to do at the start of the main body of the glossary. Note that this is not the same as <code>\glossarypreamble</code> , which should not be affected by changes in the glossary style. The list glossary style redefines <code>\glossaryheader</code> to do nothing, whereas the <code>longheader</code> glossary style redefines <code>\glossaryheader</code> to do a header row.
<code>\glsgroupheading</code>	<code>\glsgroupheading{\langle label \rangle}</code>	This macro indicates what to do at the start of each logical block within the main body of the glossary. If you use <code>makeindex</code> the glossary is sub-divided into a maximum of twenty-eight logical blocks that are determined by the first character of the <code>sort</code> key (or <code>name</code> key if the <code>sort</code> key is omitted). The sub-divisions are in the following order: symbols, numbers, A, ..., Z. If you use <code>xindy</code> , the sub-divisions depend on the language settings. Note that the argument to <code>\glsgroupheading</code> is a label <i>not</i> the group title. The group title can be obtained via
<code>\glsgруппtitle</code>	<code>\glsgруппtitle{\langle label \rangle}</code>	This obtains the title as follows: if <code>\langle label \rangle</code> exists, this is taken to be the title, otherwise the title is just <code>\langle label \rangle</code> . A navigation hypertarget can be created using
<code>\glsnavhypertarget</code>	<code>\glsnavhypertarget{\langle label \rangle}{\langle text \rangle}</code>	For further details about <code>\glsnavhypertarget</code> , see subsection 7.1 . Most of the predefined glossary styles redefine <code>\glsgroupheading</code> to simply ignore its argument. The <code>listhypergroup</code> style redefines <code>\glsgroupheading</code> as follows:
		<pre>\renewcommand*{\glsgroupheading}[1]{% \item[\glsnavhypertarget{\#1}{\glsgруппtitle{\#1}}]}</pre>
		See also <code>\glsgroupskip</code> below. (Note that command definitions within <code>\newglossarystyle</code> must use <code>##1</code> instead of <code>#1</code> etc.)
<code>\glsgroupskip</code>	<code>\glsgroupskip</code>	This macro determines what to do after one logical group but before the header for the next logical group. The list glossary style simply redefines <code>\glsgroupskip</code> to be <code>\indexspace</code> , whereas the tabular-like styles redefine <code>\glsgroupskip</code> to produce a blank row.
<code>\glossaryentryfield</code>	<code>\glossaryentryfield{\langle label \rangle}{\langle formatted name \rangle}{\langle description \rangle}{\langle symbol \rangle}{\langle number list \rangle}</code>	This macro indicates what to do for a given glossary entry. Note that <code>\langle formatted name \rangle</code> will always be in the form <code>\glsnamefont{\langle name \rangle}</code> . This allows the user to set a given font for the entry name, regardless of the glossary style used. Note that <code>\langle label \rangle</code> is the label used when the glossary entry was defined via either <code>\newglossaryentry</code> or <code>\newacronym</code> . Each time you use a glossary entry it creates a hyperlink (if hyperlinks are enabled) to the relevant line in the glossary. Your new glossary style must

therefore redefine `\glossaryentryfield` to set the appropriate target. This is done using

```
\glstarget{\label}{\text}
```

where `\label` is the entry's label. Note that you don't need to worry about whether the `hyperref` package has been loaded, as `\glstarget` won't create a target if `\hypertarget` hasn't been defined.

For example, the list style defines `\glossaryentryfield` as follows:

```
\renewcommand*\glossaryentryfield[5]{%
  \item[\glstarget{\#\#1}{\#\#2}] ##3\glspostdescription\space ##5}
```

Note also that `\numberlist` will always be of the form

```
\glossaryentrynumbers{\relax
  \setentrycounter{\countername}\glsnumberformat{\numberlist}}
```

where `\numberlist` may contain `\delimN` (to delimit individual numbers) and/or `\delimR` (to indicate a range of numbers). There may be multiple occurrences of `\setentrycounter{\countername}\glsnumberformat{\numberlist}`, but note that the entire number list is enclosed within the argument to `\glossaryentrynumbers`. The user can redefine this to change the way the entire number list is formatted, regardless of the glossary style. However the most common use of `\glossaryentrynumbers` is to provide a means of suppressing the number list altogether. (In fact, the `nonumberlist` option redefines `\glossaryentrynumbers` to ignore its argument.) Therefore, when you define a new glossary style, you don't need to worry about whether the user has specified the `nonumberlist` package option.

```
\glossarysubentryfield \glossarysubentryfield{\level}{\label}{\formattedname}{\description}{\symbol}{\numberlist}
```

This is new to version 1.17, and is used to display sub-entries. The first argument, `\level`, indicates the sub-entry level. This must be an integer from 1 (first sub-level) onwards. The remaining arguments are analogous to those for `\glossaryentryfield` described above.

For further details of these commands, see [subsection 5.15](#).

3.13.1 Example: creating a completely new style

If you want a completely new style, you will need to redefine all of the commands and the environment listed above.

For example, suppose you want each entry to start with a bullet point. This means that the glossary should be placed in the `itemize` environment, so `theglossary` should start and end that environment. Let's also suppose that you don't want anything between the glossary groups (so `\glsgroupheading` and `\glsgroupskip` should do nothing) and suppose you don't want anything to appear immediately after `\begin{theglossary}` (so `\glossaryheader` should do nothing). In addition, let's suppose the symbol should appear in brackets after the name, followed by the description and last of all the number list should appear within square

brackets at the end. Then you can create this new glossary style, called, say, `mylist`, as follows:

```
\newglossarystyle{mylist}{%
% put the glossary in the itemize environment:
\renewenvironment{theglossary}{\begin{itemize}}{\end{itemize}}%
% have nothing after \begin{theglossary}:
\renewcommand*\{\glossaryheader\}{}
% have nothing between glossary groups:
\renewcommand*\{\glsgroupheading\}[1]{}
\renewcommand*\{\glsgroupskip\}{}
% set how each entry should appear:
\renewcommand*\{\glossaryentryfield\}[5]{%
\item % bullet point
\glstarget{\#\#1}{\#\#2} the entry name
\space (\#\#4) the symbol in brackets
\space \#\#3 the description
\space [\#\#5] the number list in square brackets
}%
% set how sub-entries appear:
\renewcommand*\{\glossarysubentryfield\}[6]{%
\glossaryentryfield{\#\#2}{\#\#3}{\#\#4}{\#\#5}{\#\#6}}%
}
```

Note that this style creates a flat glossary, where sub-entries are displayed in exactly the same way as the top level entries.

3.13.2 Example: creating a new glossary style based on an existing style

If you want to define a new style that is a slightly modified version of an existing style, you can use `\glossarystyle` within the second argument of `\newglossarystyle` followed by whatever alterations you require. For example, suppose you want a style like the `list` style but you don't want the extra vertical space created by `\indexspace` between groups, then you can create a new glossary style called, say, `mylist` as follows:

```
\newglossarystyle{mylist}{%
\glossarystyle{list}% base this style on the list style
\renewcommand*\{\glsgroupskip\}{}}% make nothing happen between groups
}
```

3.14 Accessibility Support

Limited accessibility support is provided by the accompanying `glossaries-accsupp` package, but note that this package is experimental and it requires the `accsupp` package which is also listed as experimental. The `symbol` key is used to specify the replacement text. For example:

```
\newglossaryentry{tex}{name={\TeX},description={Document preparation
language},symbol={TeX}}
```

When you reference this entry using `\gls`, `\glspl` or their uppercase variants, the `symbol` is used as the replacement text. For example, `\gls{tex}` would be equivalent to

```
\BeginAccSupp{ActualText=TeX}\TeX\EndAccSupp{}
```

See [section 8](#) for further details. It is recommended that you also read the `accsupp` documentation.

4 Mfirstuc Package

The `glossaries` bundle is supplied with the package `mfirstuc` which provides the command:

```
\makefirstuc \makefirstuc{\langle stuff\rangle}
```

which makes the first object of `\langle stuff\rangle` uppercase unless `\langle stuff\rangle` starts with a control sequence followed by a non-empty group, in which case the first object in the group is converted to uppercase. Examples:

- `\makefirstuc{abc}` produces `Abc`
- `\makefirstuc{\emph{abc}}` produces `Abc` (`\MakeUppercase` has been applied to the letter “`a`” rather than `\emph`.) Note however that `\makefirstuc{\{\em abc\}}` produces `ABC` and `\makefirstuc{\em abc}` produces `abc`.
- `\makefirstuc{\text{'a}bc}` produces `Ábc`
- `\makefirstuc{\ae bc}` produces `Æbc`
- `\makefirstuc{\{ae}bc}` produces `Æbc`
- `\makefirstuc{\{ä}bc}` produces `Äbc`

Note that non-Latin or accented characters appearing at the start of the text must be placed in a group (even if you are using the `inputenc` package) due to expansion issues.

In version 1.02 of `mfirstuc`, a bug fix resulted in a change in output if the first object is a control sequence followed by an empty group. Prior to version 1.02, `\makefirstuc{\ae{}bc}` produced `æBc`. However as from version 1.02, it now produces `Æbc`.

Note also that

```
\newcommand{\abc}{abc}
\makefirstuc{\abc}
```

produces: `ABC`. This is because the first object in the argument of `\makefirstuc` is `\abc`, so it does `\MakeUppercase\abc`. Whereas:

```
\newcommand{\abc}{abc}
\expandafter\makefirstuc\expandafter{\abc}
```

produces: `Abc`. There is a short cut command which will do this:

```
\xmakefirstuc \xmakefirstuc{\langle stuff\rangle}
```

This is equivalent to `\expandafter\makefirstuc\expandafter{\langle stuff\rangle}`. So

```
\newcommand{\abc}{abc}
\xmakefirstuc{\abc}
```

produces: Abc.

If you want to use an alternative command to convert to uppercase, for example `\MakeTextUppercase`,¹⁶ you can redefine the internal command `\@gls@makefirstuc`. For example:

```
\renewcommand{\@gls@makefirstuc}[1]{\MakeTextUppercase #1}
```

(Remember that command names that contain the @ character must either be placed in packages or be placed between `\makeatletter` and `\makeatother`.)

5 Documented Code

5.1 Package Definition

This package requires L^AT_EX 2_&.

```
1 \NeedsTeXFormat{LaTeX2e}
2 \ProvidesPackage{glossaries}[2009/04/16 v2.0 (NLCT)]
```

Required packages:

```
3 \RequirePackage{ifthen}
4 \RequirePackage{xkeyval}[2006/11/18]
5 \RequirePackage{mfirstuc}
6 \RequirePackage{xfor}
```

If babel package is loaded, check to see if translator is installed.

```
7 \@ifpackageloaded[babel]{\IfFileExists{translator.sty}{%
8   \RequirePackage{translator}}}{}}
```

Need to use `\new@ifnextchar` instead of `\@ifnextchar` in commands that have a final optional argument (such as `\gls`) so require amsgen. Thanks to Morten Høgholm for suggesting this. (This has replaced using the xspace package.)

```
9 \RequirePackage{amsgen}
```

5.2 Package Options

- toc** The toc package option will add the glossaries to the table of contents. This is a boolean key, if the value is omitted it is taken to be true.
10 \define@boolkey[glossaries.sty][gls]{toc}[true]{}
- numberline** The numberline package option adds `\numberline` to `\addcontentsline`. Note that this option only has an effect if used in with `toc=true`.
11 \define@boolkey[glossaries.sty][gls]{numberline}[true]{}

The sectional unit used to start the glossary is stored in `\@glossarysec`. If chapters are defined, this is initialised to `chapter`, otherwise it is initialised to `section`.

¹⁶defined in the textcase package

```

\@@glossarysec
12 \@ifundefined{chapter}{\newcommand*{\@@glossarysec}{\section}}{%
13 \newcommand*{\@@glossarysec}{\chapter}}

```

section The `section` key can be used to set the sectional unit. If no unit is specified, use `section` as the default. The starred form of the named sectional unit will be used. If you want some other way to start the glossary section (e.g. a numbered section) you will have to redefine `\glossarysection`.

```

14 \define@choicekey{glossaries.sty}{section}{part,chapter,section,%
15 subsection,subsubsection,paragraph,subparagraph}[section]{%
16 \renewcommand*{\@@glossarysec}{\#1}}

```

Determine whether or not to use numbered sections.

```

\@@glossarysecstar
17 \newcommand*{\@@glossarysecstar}{*}

```

```

\@@glossaryseclabel
18 \newcommand*{\@@glossaryseclabel}{}

```

```

\glsautoprefix Prefix to add before label if automatically generated:
19 \newcommand*{\glsautoprefix}{}

```

```

numberedsection
20 \define@choicekey{glossaries.sty}{numberedsection}{\val\nr}{%
21 false,nolabel,autolabel}[nolabel]{%
22 \ifcase\nr\relax
23   \renewcommand*{\@@glossarysecstar}{*}%
24   \renewcommand*{\@@glossaryseclabel}{*}%
25 \or
26   \renewcommand*{\@@glossarysecstar}{*}%
27   \renewcommand*{\@@glossaryseclabel}{*}%
28 \or
29   \renewcommand*{\@@glossarysecstar}{*}%
30   \renewcommand*{\@@glossaryseclabel}{\label{\glsautoprefix@\glo@type}}%
31 \fi}

```

The default glossary style is stored in `\@glossary@default@style`. This is initialised to `list`. (The `list` style is defined in the accompanying `glossary-list` package described in [subsection 5.18](#).)

```

\@glossary@default@style
32 \newcommand*{\@glossary@default@style}{list}

```

style The default glossary style can be changed using the `style` package option. The value can be the name of any defined glossary style. The glossary style is set at the beginning of the document, so you can still use the `style` key to set a style that is defined in another package. This package comes with some predefined styles that are defined in [subsection 5.18](#).

```

33 \define@key{glossaries.sty}{style}{%
34 \renewcommand*{\@glossary@default@style}{\#1}}

```

Each entry within a given glossary will have an associated number list. By default, this refers to the page numbers on which that entry has been used, but it can also refer to any counter used in the document (such as the section or equation counters). The default number list format displays the number list “as is”:

```
\glossaryentrynumbers
 35 \newcommand*{\glossaryentrynumbers}[1]{#1}

nonumberlist Note that the entire number list for a given entry will be passed to \glossaryentrynumbers so any font changes will also be applied to the delimiters. The nonumberlist package option suppresses the number lists (this simply redefines \glossaryentrynumbers to ignore its argument).
 36 \DeclareOptionX{nonumberlist}{%
 37 \renewcommand*{\glossaryentrynumbers}[1]{}}

\@gls@loadlong
 38 \newcommand*{\@gls@loadlong}{\RequirePackage{glossary-long}}

nolong This option prevents glossary-long from being loaded. This means that the glossary styles that use the longtable environment will not be available. This option is provided to reduce overhead caused by loading unrequired packages.
 39 \DeclareOptionX{nolong}{\renewcommand*{\@gls@loadlong}{}}

\@gls@loadsuper
 40 \IfFileExists{supertabular.sty}{%
 41   \newcommand*{\@gls@loadsuper}{\RequirePackage{glossary-super}}}{%
 42   \newcommand*{\@gls@loadsuper}{}}

nosuper This option prevents glossary-super from being loaded. This means that the glossary styles that use the supertabular environment will not be available. This option is provided to reduce overhead caused by loading unrequired packages.
 43 \DeclareOptionX{nosuper}{\renewcommand*{\@gls@loadsuper}{}}

\@gls@loadlist
 44 \newcommand*{\@gls@loadlist}{\RequirePackage{glossary-list}}

nolist This option prevents glossary-list from being loaded (to reduce overheads if required). Naturally, the styles defined in glossary-list will not be available if this option is used.
 45 \DeclareOptionX{nolist}{\renewcommand*{\@gls@loadlist}{}}

\@gls@loadtree
 46 \newcommand*{\@gls@loadtree}{\RequirePackage{glossary-tree}}

notree This option prevents glossary-tree from being loaded (to reduce overheads if required). Naturally, the styles defined in glossary-tree will not be available if this option is used.
 47 \DeclareOptionX{notree}{\renewcommand*{\@gls@loadtree}{}}
```

- nostyles** Provide an option to suppress all the predefined styles (in the event that the user has custom styles that are not dependent on the predefined styles).

```

48 \DeclareOptionX{nostyles}{%
49   \renewcommand*\{@gls@loadlong}{}%
50   \renewcommand*\{@gls@loadsuper}{}%
51   \renewcommand*\{@gls@loadlist}{}%
52   \renewcommand*\{@gls@loadtree}{}%
53   \let\@glossary@default@style\relax
54 }

```

Keep track of the default glossary. This is initialised to the main glossary, but can be changed if for some reason you want to make a secondary glossary the main glossary. This affects any commands that can optionally take a glossary name as an argument (or as the value of the `type` key in a key-value list). This was mainly done so that `\loadglsentries` can temporarily change `\glsdefaulttype` while it loads a file containing new glossary entries (see [subsection 5.9](#)).

`\glsdefaulttype`

```
55 \newcommand{\glsdefaulttype}{main}
```

Keep track of which glossary the acronyms are in. This is initialised to `\glsdefaulttype`, but is changed by the `acronym` package option.

`\acronymtype`

```
56 \newcommand{\acronymtype}{\glsdefaulttype}
```

- acronym** The `acronym` option sets an associated conditional which is used in [subsection 5.16](#) to determine whether or not to define a separate glossary for acronyms.

```
57 \define@boolkey{glossaries.sty}[gls]{acronym}[true]{}
```

The default counter associated with the numbers in the glossary is stored in `\glscounter`. This is initialised to the page counter. This is used as the default counter when a new glossary is defined, unless a different counter is specified in the optional argument to `\newglossary` (see [subsection 5.6](#)).

`\glscounter`

```
58 \newcommand{\glscounter}{page}
```

- counter** The `counter` option changes the default counter. (This just redefines `\glscounter`.)

```
59 \define@key{glossaries.sty}{counter}{%
60 \renewcommand*\{@glscounter}{#1}}
```

The glossary keys whose values are written to another file (i.e. `sort`, `name`, `description` and `symbol`) need to be sanitized, otherwise fragile commands would not be able to be used in `\newglossaryentry`. However, strange results will occur if you then use those fields in the document. As these fields are not normally used in the document, but are by default only used in the glossary, the default is to sanitize them. If however you want to use these values in the document (either by redefining commands like `\glsdisplay` or by using commands like `\glsentrydesc`) you will have to switch off the sanitization using the `sanitize` package option, but you will then have to use `\protect` to protect fragile commands when defining new glossary entries. The `sanitize` option takes a key-value list as its value, which can be used to switch individual values on and off. For example:

```
\usepackage[sanitize={description,name,symbol=false}]{glossaries}
```

will switch off the sanitization for the `symbol` key, but switch it on for the `description` and `name` keys. This would mean that you can use fragile commands in the `description` and `name` when defining a new glossary entry, but not for the `symbol`.

The default values are defined as:

```
\@gls@sanitizedesc
61 \newcommand*{\@gls@sanitizedesc}{\@onelvel@sanitize\@glo@desc}

\@gls@sanitizename
62 \newcommand*{\@gls@sanitizename}{\@onelvel@sanitize\@glo@name}

\@gls@sanitizesymbol
63 \newcommand*{\@gls@sanitizesymbol}{\@onelvel@sanitize\@glo@symbol}
```

(There is no equivalent for the `sort` key, since that is only provided for the benefit of `makeindex` or `xindy`, and so will always be sanitized.)

Before defining the `sanitize` package option, The key-value list for the `sanitize` value needs to be defined. These are all boolean keys. If they are not given a value, assume `true`.

Firstly the `description`. If set, it will redefine `\@gls@sanitizedesc` to use `\@onelvel@sanitize`, otherwise `\@gls@sanitizedesc` will do nothing.

```
64 \define@boolkey[gls]{sanitize}[description][true]{%
65 \ifgls@sanitize@description
66   \renewcommand*{\@gls@sanitizedesc}{\@onelvel@sanitize\@glo@desc}%
67 \else
68   \renewcommand*{\@gls@sanitizedesc}{}%
69 \fi
70 }
```

Similarly for the `name` key:

```
71 \define@boolkey[gls]{sanitize}[name][true]{%
72 \ifgls@sanitize@name
73   \renewcommand*{\@gls@sanitizename}{\@onelvel@sanitize\@glo@name}%
74 \else
75   \renewcommand*{\@gls@sanitizename}{}%
76 \fi}
```

and for the `symbol` key:

```
77 \define@boolkey[gls]{sanitize}[symbol][true]{%
78 \ifgls@sanitize@symbol
79   \renewcommand*{\@gls@sanitizesymbol}{%
80     \@onelvel@sanitize\@glo@symbol}%
81 \else
82   \renewcommand*{\@gls@sanitizesymbol}{}%
83 \fi}
```

sanitize Now define the `sanitize` option. It can either take a key-val list as its value, or it can take the keyword `none`, which is equivalent to `description=false`, `symbol=false`, `name=false`:

```
84 \define@key{glossaries.sty}{sanitize}[description=true,symbol=true,
85 name=true]{%
86 \ifthenelse{\equal{\#1}{none}}{%
87 \renewcommand*{\@gls@sanitizedesc}{}%
```

```

88 \renewcommand*{\@gls@sanitizename}{}
89 \renewcommand*{\@gls@sanitizesymbol}{}
90 }{\setkeys[gls]{sanitize}{#1}}%
91 }

translate Define translate option. If false don't set up multi-lingual support.
92 \define@boolkey{glossaries.sty}[gls]{translate}[true]{} 

Set the default value:
93 \glstranslatefalse
94 \@ifpackageloaded{translator}{\glstranslatetrue}{%
95 \ifpackageloaded{babel}{\glstranslatetrue}{}

footnote Set the long form of the acronym in footnote on first use.
96 \define@boolkey{glossaries.sty}[glsacr]{footnote}[true]{%
97 \ifthenelse{\boolean{glsacrdescription}}{}{%
98 {\renewcommand*{\@gls@sanitizedesc}{}}}%
99 }

description Allow acronyms to have a description (needs to be set using the description key in the optional argument of \newacronym).
100 \define@boolkey{glossaries.sty}[glsacr]{description}[true]{%
101 \renewcommand*{\@gls@sanitizesymbol}{}%
102 }

smallcaps Define \newacronym to set the short form in small capitals.
103 \define@boolkey{glossaries.sty}[glsacr]{smallcaps}[true]{%
104 \renewcommand*{\@gls@sanitizesymbol}{}%
105 }

smaller Define \newacronym to set the short form using \smaller which obviously needs to be defined by loading the appropriate package.
106 \define@boolkey{glossaries.sty}[glsacr]{smaller}[true]{%
107 \renewcommand*{\@gls@sanitizesymbol}{}%
108 }

dua Define \newacronym to always use the long forms (i.e. don't use acronyms)
109 \define@boolkey{glossaries.sty}[glsacr]{dua}[true]{%
110 \renewcommand*{\@gls@sanitizesymbol}{}%
111 }

shortcuts Define acronym shortcuts.
112 \define@boolkey{glossaries.sty}[glsacr]{shortcuts}[true]{} 

\glsorder Stores the glossary ordering. This may either be "word" or "letter". This passes the relevant information to makeglossaries. The default is word ordering.
113 \newcommand*{\glsorder}{word}

\@glsorder The ordering information is written to the auxiliary file for makeglossaries, so ignore the auxiliary information.
114 \newcommand*{\@glsorder}{1}{} 

```

```

order
115 \define@choicekey{glossaries.sty}{order}{word,letter}{%
116   \def\glsorder{\#1}%

\ifglsxindy Provide boolean to determine whether xindy or makeindex will be used to sort
the glossaries.
117 \newif\ifglsxindy

The default is makeindex:
118 \glsxindystylefalse

Define package option to specify that makeindex will be used to sort the glossaries:
119 \DeclareOptionX{makeindex}{\glsxindystylefalse}

The xindy package option may have a value which in turn can be a key=value
list. First define the keys for this sub-list. The boolean glsnumbers determines
whether to automatically add the glsnumbers letter group.
120 \define@boolkey[gls]{xindy}{glsnumbers}[true]{}
121 \gls{xindy@glsnumberstrue

\@xdy@main@language Define what language to use for each glossary type (if a language is not defined for
a particular glossary type the language specified for the main glossary is used.)
122 \def\@xdy@main@language{\rootlanguagename}%

Define key to set the language
123 \define@key[gls]{xindy}{language}{\def\@xdy@main@language{\#1}%

\gls@codepage Define the code page. If \inputencodingname is defined use that, otherwise have
initialise with no codepage.
124 \@ifundefined{inputencodingname}{%
125   \def\gls@codepage{}%}
126   \def\gls@codepage{\inputencodingname}
127 }

Define a key to set the code page.
128 \define@key[gls]{xindy}{codepage}{\def\gls@codepage{\#1}%

Define package option to specify that xindy will be used to sort the glossaries:
129 \define@key{glossaries.sty}{xindy}[]{%
130   \glsxindystyletrue
131   \setkeys[gls]{xindy}{\#1}%
132 }

Process package options:
133 \ProcessOptionsX

If chapters are defined and the user has requested the section counter as a
package option, \@chapter will be modified so that it adds a section.<n>.0
target, otherwise entries placed before the first section of a chapter will have
undefined links.

The same problem will also occur if a lower sectional unit is used, but
this is less likely to happen. If it does, or if you change \glscounter

```

to section later, you will have to specify a different counter for the entries that give rise to a `name{<section-level>.⟨n⟩.0}` non-existent warning (e.g. `\gls[counter=chapter]{label}`).

```
134 \ifthenelse{\equal{\glscounter}{section}}{%
135 \@ifundefined{chapter}{}{%
136 \let\gls@old@chapter\chapter
137 \def\chapter[#1]#2{\gls@old@chapter[#1]{#2}}%
138 \ifundefined{hyperdef}{}{\hyperdef{section}{\thesection}{}{}}}}
```

`\@gls@onlypremakeg` Some commands only have an effect when used before `\makeglossaries`. So define a list of commands that should be disabled after `\makeglossaries`

```
139 \newcommand*{\@gls@onlypremakeg}{}{}
```

`\@onlypremakeg` Adds the specified control sequence to the list of commands that must be disabled after `\makeglossaries`.

```
140 \newcommand*{\@onlypremakeg}[1]{%
141 \ifx\gls@onlypremakeg\empty
142 \def\gls@onlypremakeg[#1]{%
143 \else
144 \expandafter\toks@\expandafter{\gls@onlypremakeg}%
145 \edef\gls@onlypremakeg{\the\toks@\noexpand#1}%
146 \fi}
```

`\@disable@onlypremakeg` Disable all commands listed in `\@gls@onlypremakeg`

```
147 \newcommand*{\@disable@onlypremakeg}{}{%
148 \foreach\thiscs:=\gls@onlypremakeg\do{%
149 \expandafter\@disable@premakecs@\thiscs%}
150 }}
```

`\@disable@premakecs` Disables the given command.

```
151 \newcommand*{\@disable@premakecs}[1]{%
152 \def#1{\PackageError{glossaries}{\string#1\space may only be
153 used before \string\makeglossaries}{You can't use
154 \string#1\space after \string\makeglossaries}}%
155 }
```

5.3 Default values

This section sets up default values that are used by this package. Some of the names may already be defined (e.g. by `babel`) so `\providecommand` is used.

Main glossary title:

```
\glossaryname
156 \providecommand*{\glossaryname}{Glossary}
```

The title for the `acronym` glossary type (which is defined if `acronym` package option is used) is given by `\acronymname`. If the `acronym` package option is not used, `\acronymname` won't be used.

```
\acronymname
157 \providecommand*{\acronymname}{Acronyms}
```

`\glssettoctitle` Sets the TOC title for the given glossary.

```
158 \newcommand*{\glssettoctitle}[1]{%
159 \def\glossarytoctitle{\csname @gloctype@#1@title\endcsname}}
```

The following commands provide text for the headers used by some of the tabular-like glossary styles. Whether or not they get used in the glossary depends on the glossary style.

```
\entryname
160 \providecommand*{\entryname}{Notation}
```

```
\descriptionname
161 \providecommand*{\descriptionname}{Description}
```

```
\symbolname
162 \providecommand*{\symbolname}{Symbol}
```

```
\pagelistname
163 \providecommand*{\pagelistname}{Page List}
```

Labels for `makeindex`'s symbol and number groups:

```
\glosssymbolsgroupname
164 \providecommand*{\glosssymbolsgroupname}{Symbols}
```

```
\glossnumbersgroupname
165 \providecommand*{\glossnumbersgroupname}{Numbers}
```

`\glosspluralsuffix` The default plural is formed by appending `\glosspluralsuffix` to the singular form.

```
166 \newcommand*{\glosspluralsuffix}{s}
```

```
\seename
167 \providecommand*{\seename}{see}
```

```
\andname
168 \providecommand*{\andname}{\&}
```

Add multi-lingual support. Thanks to everyone who contributed to the translations from both `comp.text.tex` and via email.

```
169 \ifglstranslate
```

If `translator` is not installed, used standard `babel` captions, otherwise load `translator` dictionary.

```
170  \@ifpackageloaded{translator}{\usedictionary{glossaries-dictionary}}%
171    \renewcommand*{\glssettoctitle}[1]{%
172      \ifthenelse{\equal{#1}{main}}{%
173        \translatelet{\glossarytoctitle}{Glossary}}{%
174        \ifthenelse{\equal{#1}{acronym}}{%
175          \translatelet{\glossarytoctitle}{Acronyms}}{%
176            \def\glossarytoctitle{\csname @gloctype@#1@title\endcsname}}}}%
177    \renewcommand*{\glossaryname}{\translate{Glossary}}%
178    \renewcommand*{\acronymname}{\translate{Acronyms}}%
```

```

179   \renewcommand*\{\entryname}{\translate{Notation (glossaries)}}%
180   \renewcommand*\{\descriptionname}{%
181     \translate{Description (glossaries)}}%
182   \renewcommand*\{\symbolname}{\translate{Symbol (glossaries)}}%
183   \renewcommand*\{\pagelistname}{%
184     \translate{Page List (glossaries)}}%
185   \renewcommand*\{\glssymbolsgroupname}{%
186     \translate{Symbols (glossaries)}}%
187   \renewcommand*\{\glsnumbersgroupname}{%
188     \translate{Numbers (glossaries)}}%
189 }{%
190   \@ifpackageloaded{babel}{\RequirePackage{glossaries-babel}}{}}
191 \fi

\glspostdescription The description terminator is given by \glspostdescription (except for the 3 and 4 column styles). This is a full stop by default:
192 \newcommand*\{\glspostdescription}{.}

\nopostdesc Provide a means to suppress description terminator for a given entry. (Useful for entries with no description.) Has no effect outside the glossaries.
193 \newcommand*\{\nopostdesc}{}

@nopostdesc Suppress next description terminator.
194 \newcommand*\{@nopostdesc}{%
195   \let\org@glspostdescription\glspostdescription
196   \def\glspostdescription{%
197     \let\glspostdescription\org@glspostdescription}%
198 }

\glspar Provide means of having a paragraph break in glossary entries
199 \newcommand{\glspar}{\par}

\setStyleFile Sets the style file. The relevant extension is appended.
200 \@ifglsxindy
201   \newcommand{\setStyleFile}[1]{%
202     \renewcommand{\istfilename}{\#1.xdy}}
203 \else
204   \newcommand{\setStyleFile}[1]{%
205     \renewcommand{\istfilename}{\#1.ist}}
206 \fi

This command only has an effect prior to using \makeglossaries.
207 @onlypremakeg\setStyleFile

The name of the makeindex or xindy style file is given by \istfilename. This file is created by \writeist (which is used by \makeglossaries) so redefining this command will only have an effect if it is done before \makeglossaries. As from v1.17, use \setStyleFile instead of directly redefining \istfilename.

\istfilename
208 \@ifglsxindy
209   \def\istfilename{\jobname.xdy}
210 \else
211   \def\istfilename{\jobname.ist}
212 \fi

```

The `makeglossaries` Perl script picks up this name from the auxiliary file. If the name ends with `.xdy` it calls `xindy` otherwise it calls `makeindex`. Since its not required by L^AT_EX, `\@istfilename` ignores its argument.

```
\@istfilename
213 \newcommand*{\@istfilename}[1]{}
```

This command is the value of the `page_compositor` `makeindex` key. Again, any redefinition of this command must take place *before* `\writeist` otherwise it will have no effect. As from 1.17, use `\glsSetCompositor` instead of directly redefining `\glscompositor`.

```
\glscompositor
214 \newcommand*{\glscompositor}{.}

\glsSetCompositor Sets the compositor.
215 \newcommand*{\glsSetCompositor}[1]{%
216   \renewcommand*{\glscompositor}{#1}}
Only use before \makeglossaries
217 \@onlypremakeg\glsSetCompositor
```

(The page compositor is usually defined as a dash when using `makeindex`, but most of the standard counters used by L^AT_EX use a full stop as the compositor, which is why I have used it as the default.) If `xindy` is used `\glscompositor` only affects the `arabic-page-numbers` location class.

```
\@glsAlphacompositor This is only used by xindy. It specifies the compositor to use when location numbers are in the form <letter><compositor><number>. For example, if \@glsAlphacompositor is set to “.” then it allows locations such as A.1 whereas if \@glsAlphacompositor is set to “-” then it allows locations such as A-1.
218 \newcommand*{\@glsAlphacompositor}{\glscompositor}
```

```
\glsSetAlphaCompositor Sets the alpha compositor.
219 \ifglsxindy
220   \newcommand*{\glsSetAlphaCompositor}[1]{%
221     \renewcommand*{\@glsAlphacompositor}{#1}}
222 \else
223   \newcommand*{\glsSetAlphaCompositor}[1]{%
224     \glsnoxindywarning\glsSetAlphaCompositor}
225 \fi
Can only be used before \makeglossaries
226 \@onlypremakeg\glsSetAlphaCompositor
```

```
\gls@suffixF Suffix to use for a two page list. This overrides the separator and the closing page number if set to something other than an empty macro.
227 \newcommand*{\gls@suffixF}{}{}
```

```
\glsSetSuffixF Sets the suffix to use for a two page list.
228 \newcommand*{\glsSetSuffixF}[1]{%
229   \renewcommand*{\gls@suffixF}{#1}}
Only has an effect when used before \makeglossaries
230 \@onlypremakeg\glsSetSuffixF
```

```
\gls@suffixFF Suffix to use for a three page list. This overrides the separator and the closing  
page number if set to something other than an empty macro.
```

```
231 \newcommand*{\gls@suffixFF}{}{}
```

```
\glsSetSuffixFF Sets the suffix to use for a three page list.
```

```
232 \newcommand*{\glsSetSuffixFF}[1]{%  
233   \renewcommand*{\gls@suffixFF}{#1}}
```

The command `\glsnumberformat` indicates the default format for the page numbers in the glossary. (Note that this is not the same as `\glossaryentrynumbers`, but applies to individual numbers or groups of numbers within an entry’s associated number list.) If hyperlinks are defined, it will use `\glshypernumber`, otherwise it will simply display its argument “as is”.

```
\glsnumberformat
```

```
234 \@ifundefined{hyperlink}{%  
235   \newcommand*{\glsnumberformat}[1]{#1}{%  
236     \newcommand*{\glsnumberformat}[1]{\glshypernumber{#1}}}}
```

Individual numbers in an entry’s associated number list are delimited using `\delimN` (which corresponds to the `delim_n makeindex` keyword). The default value is a comma followed by a space.

```
\delimN
```

```
237 \newcommand{\delimN}{, }
```

A range of numbers within an entry’s associated number list is delimited using `\delimR` (which corresponds to the `delim_r makeindex` keyword). The default is an en-dash.

```
\delimR
```

```
238 \newcommand{\delimR}{--}
```

The glossary preamble is given by `\glossarypreamble`. This will appear after the glossary sectioning command, and before the `theglossary` environment. It is designed to allow the user to add information pertaining to the glossary (e.g. “page numbers in italic indicate the primary definition”) therefore `\glossarypreamble` shouldn’t be affected by the glossary style. (So if you define your own glossary style, don’t have it change `\glossarypreamble`.) The preamble is empty by default. If you have multiple glossaries, and you want a different preamble for each glossary, you will need to use `\printglossary` for each glossary type, instead of `\printglossaries`, and redefine `\glossarypreamble` before each `\printglossary`.

```
\glossarypreamble
```

```
239 \newcommand*{\glossarypreamble}{}{}
```

The glossary postamble is given by `\glossarypostamble`. This is provided to allow the user to add something after the end of the `theglossary` environment (again, this shouldn’t be affected by the glossary style). It is, of course, possible to simply add the text after `\printglossary`, but if you only want the postamble to appear after the first glossary, but not after subsequent glossaries, you can do something like:

```

\renewcommand{\glossarypostamble}{For a complete list of terms
see \cite{blah}\gdef\glossarypreamble{}}

\glossarypostamble
240 \newcommand*{\glossarypostamble}{}{}
```

The sectioning command that starts a glossary is given by `\glossarysection`. (This does not form part of the glossary style, and so should not be changed by a glossary style.) If `\phantomsection` is defined, it uses `\p@glossarysection`, otherwise it uses `\@glossarysection`.

```

\glossarysection
241 \newcommand*{\glossarysection}[2][\@gls@title]{%
242 \def\@gls@title{\#2}%
243 \@ifundefined{phantomsection}{%
244 \glossarysection{\#1}{\#2}}{\@p@glossarysection{\#1}{\#2}}%
245 \mkboth{\glossarytoctitle}{\glossarytoctitle}%
246 }
```

The required sectional unit is given by `\@@glossarysec` which was defined by the `section` package option. The starred form of the command is chosen. If you don't want any sectional command, you will need to redefine `\glossarysection`. The sectional unit can be changed, if different sectional units are required.

```

\setglossarysection
247 \newcommand*{\setglossarysection}[1]{%
248 \setkeys{glossaries.sty}{section=#1}}
```

The command `\@glossarysection` indicates how to start the glossary section if `\phantomsection` is not defined.

```

\@glossarysection
249 \newcommand*{\@glossarysection}[2]{%
250 \ifx\@@glossarysecstar\empty
251   \csname\@@glossarysec\endcsname{\#2}%
252 \else
253   \csname\@@glossarysec\endcsname*{\#2}%
254   \gls@toc{\#1}{\@@glossarysec}%
255 \fi
256 \@@glossaryseclabel}
```

As `\@glossarysection`, but put in `\phantomsection`, and swap where `\@gls@toc` goes. If using chapters do a `\clearpage`. This ensures that the hyper link from the table of contents leads to the line above the heading, rather than the line below it.

```

\@p@glossarysection
257 \newcommand*{\@p@glossarysection}[2]{%
258 \glsclearpage
259 \phantomsection
260 \ifx\@@glossarysecstar\empty
261   \csname\@@glossarysec\endcsname{\#2}%
262 \else
263   \gls@toc{\#1}{\@@glossarysec}%
```

```

264 \csname\@glossarysec\endcsname*{#2}%
265 \fi
266 \@@glossaryseclabel}

```

The `\gls@doclearpage` command is used to issue a `\clearpage` (or `\cleardoublepage`) depending on whether the glossary sectional unit is a chapter. If the sectional unit is something else, do nothing.

`\gls@doclearpage`

```

267 \newcommand*\{\gls@doclearpage}{%
268 \ifthenelse{\equal{\@glossarysec}{chapter}}{%
269 \GIfundefined{cleardoublepage}{\clearpage}{\cleardoublepage}}{}%
270 }

```

`\glsclearpage` This just calls `\gls@doclearpage`, but it makes it easier to have a user command so that the user can override it.

```
271 \newcommand*\{\glsclearpage}{\gls@doclearpage}
```

The glossary is added to the table of contents if `glstoc` flag set. If it is set, `\@gls@toc` will add a line to the `.toc` file, otherwise it will do nothing. (The first argument to `\@gls@toc` is the title for the table of contents, the second argument is the sectioning type.)

`\@gls@toc`

```

272 \newcommand*\{@gls@toc}[2]{%
273 \ifglstoc
274 \ifglsnumberline
275 \addcontentsline{toc}{#2}{\numberline{}#1}%
276 \else
277 \addcontentsline{toc}{#2}{#1}%
278 \fi
279 \fi}

```

5.4 Xindy

This section defines commands that only have an effect if `xindy` is used to sort the glossaries.

`\glsnoxindywarning` Issues a warning if `xindy` hasn't been specified. These warnings can be suppressed by redefining `\glsnoxindywarning` to ignore its argument

```

280 \newcommand*\{\glsnoxindywarning}[1]{%
281 \PackageWarning{glossaries}{Not in xindy mode --- ignoring
282 \string#1}}

```

`\@xdyattributes` Define list of attributes (`\string` is used in case the double quote character has been made active)

```

283 \ifglsxindy
284 \edef\@xdyattributes{\string"default\string"}%
285 \fi

```

`\@xdylocref` Define list of markup location references.

```

286 \ifglsxindy
287 \def\@xdylocref{}%
288 \fi

```

`\GlsAddXdyAttribute` Adds an attribute.

```
289 \ifglsxindy
290   \newcommand*\GlsAddXdyAttribute[1]{%
291     \edef\@xdyattributes{\@xdyattributes ^~J \string"\#1\string"}%
292     \expandafter\toks@\expandafter{\@xdylocref}%
293     \edef\@xdylocref{\the\toks@ ^~J%
294     (markup-locref
295     :open \string"\string~n\string\setentrycounter
296       {\noexpand\glscounter}%
297       \expandafter\string\csname#1\endcsname
298       \expandafter\@gobble\string\{\string" ^~J
299     :close \string"\expandafter\@gobble\string\}\string"\string" ^~J
300     :attr \string"\#1\string")}}
```

Only has an effect before `\writeist`:

```
301   \onlypremakeg\GlsAddXdyAttribute
302 \else
303   \newcommand*\GlsAddXdyAttribute[1]{%
304     \glsnoxindywarning\GlsAddXdyAttribute}
305 \fi
```

Add known attributes:

```
306 \ifglsxindy
307   \GlsAddXdyAttribute{glsnumberformat}
308   \GlsAddXdyAttribute{textrm}
309   \GlsAddXdyAttribute{textsf}
310   \GlsAddXdyAttribute{texttt}
311   \GlsAddXdyAttribute{textbf}
312   \GlsAddXdyAttribute{textmd}
313   \GlsAddXdyAttribute{textit}
314   \GlsAddXdyAttribute{textup}
315   \GlsAddXdyAttribute{textsl}
316   \GlsAddXdyAttribute{textsc}
317   \GlsAddXdyAttribute{emph}
318   \GlsAddXdyAttribute{glshypernumber}
319   \GlsAddXdyAttribute{hyperrm}
320   \GlsAddXdyAttribute{hypersf}
321   \GlsAddXdyAttribute{hypertt}
322   \GlsAddXdyAttribute{hyperbf}
323   \GlsAddXdyAttribute{hypermd}
324   \GlsAddXdyAttribute{hyperit}
325   \GlsAddXdyAttribute{hyperup}
326   \GlsAddXdyAttribute{hypersl}
327   \GlsAddXdyAttribute{hypersc}
328   \GlsAddXdyAttribute{hyperemph}
329 \fi
```

`\@xdyuseralphabets` List of additional alphabets

```
330 \def\@xdyuseralphabets{}
```

`\GlsAddXdyAlphabet` `\GlsAddXdyAlphabet{\{name\}}{\{definition\}}` adds a new alphabet called `{name}`.
The definition must use `xindy` syntax.

```
331 \ifglsxindy
332   \newcommand*{\GlsAddXdyAlphabet}[2]{%
```

```

333 \edef\@xdyuseralphabets{%
334   \@xdyuseralphabets ^~J
335   (define-alphabet "#1" (#2))}%
336 \else
337 \newcommand*\GlsAddXdyAlphabet}[2]{%
338   \glsnoxindywarning\GlsAddXdyAlphabet}%
339 \fi

\@xdyuserlocationdefs List of additional location definitions (separated by ^~J)
340 \def\@xdyuserlocationdefs{}

\@xdyuserlocationnames List of additional user location names
341 \def\@xdyuserlocationnames{}

\GlsAddXdyLocation \GlsAddXdyLocation{\langle name\rangle}{\langle definition\rangle} Define a new location called \langle name\rangle.
The definition must use xindy syntax. (Note that this doesn't check to see if the
location is already defined. That is left to xindy to complain about.)
342 \ifglsxindy
343 \newcommand*\GlsAddXdyLocation}[2]{%
344   \edef\@xdyuserlocationdefs{%
345     \@xdyuserlocationdefs ^~J%
346     (define-location-class \string"\#1\string" ^~J\space\space
347     \space(#2))}%
348 }%
349 \edef\@xdyuserlocationnames{%
350   \@xdyuserlocationnames ^~J\space\space\space\space
351   \string"\#1\string"}%
352 }

Only has an effect before \writeist:
353 \onlypremakeg\GlsAddXdyLocation
354 \else
355 \newcommand*\GlsAddXdyLocation}[2]{%
356   \glsnoxindywarning\GlsAddXdyLocation}
357 \fi

\@xdylocationclassorder Define location class order
358 \ifglsxindy
359 \edef\@xdylocationclassorder{^~J\space\space\space
360   \string"roman-page-numbers\string" ^~J\space\space\space\space
361   \string"arabic-page-numbers\string" ^~J\space\space\space\space
362   \string"arabic-section-numbers\string" ^~J\space\space\space\space
363   \string"alpha-page-numbers\string" ^~J\space\space\space\space
364   \string"Roman-page-numbers\string" ^~J\space\space\space\space
365   \string"Alpha-page-numbers\string" ^~J\space\space\space\space
366   \string"Appendix-page-numbers\string"
367   \@xdyuserlocationnames ^~J\space\space\space\space
368   \string"see\string"
369 }
370 \fi

```

Change the location order.

```

\GlsSetXdyLocationClassOrder
371 \ifglsxindy
372   \newcommand*\GlsSetXdyLocationClassOrder[1]{%
373     \def\@xdylocationclassorder{#1}}
374 \else
375   \newcommand*\GlsSetXdyLocationClassOrder[1]{%
376     \glsnoxindywarning\GlsSetXdyLocationClassOrder}
377 \fi

\@xdysortrules Define sort rules
378 \ifglsxindy
379   \def\@xdysortrules(){}
380 \fi

\GlsAddSortRule Add a sort rule
381 \ifglsxindy
382   \newcommand*\GlsAddSortRule[2]{%
383     \expandafter\toks@\expandafter{\@xdysortrules}%
384     \protected@edef\@xdysortrules{\the\toks@ ^~J
385       (sort-rule \string"#1\string" \string"#2\string")}%
386   }
387 \else
388   \newcommand*\GlsAddSortRule[2]{%
389     \glsnoxindywarning\GlsAddSortRule}
390 \fi

\@xdyrequiredstyles Define list of required styles (this should be a comma-separated list of xindy styles)
391 \ifglsxindy
392   \def\@xdyrequiredstyles{tex}
393 \fi

\GlsAddXdyStyle Add a xindy style to the list of required styles
394 \ifglsxindy
395   \newcommand*\GlsAddXdyStyle[1]{%
396     \edef\@xdyrequiredstyles{\@xdyrequiredstyles,#1}}%
397 \else
398   \newcommand*\GlsAddXdyStyle[1]{%
399     \glsnoxindywarning\GlsAddXdyStyle}
400 \fi

\GlsSetXdyStyles Reset the list of required styles
401 \ifglsxindy
402   \newcommand*\GlsSetXdyStyles[1]{%
403     \edef\@xdyrequiredstyles{#1}}
404 \else
405   \newcommand*\GlsSetXdyStyles[1]{%
406     \glsnoxindywarning\GlsSetXdyStyles}
407 \fi

\findrootlanguage The root language name is required by xindy. This information is for maketitle to pass to xindy. Since \languagename only stores the regional dialect rather than the root language name, some trickery is required to determine the root language.

```

```

408 \ifglsxindy
409   @ifpackageloaded{babel}{%
Need to parse babel.sty to determine the root language. This code was provided
by Enrico Gregorio.
410   \def\findrootlanguage{\begingroup
411     \escapechar=-1\relax
normalize \languagename to category 12 chars
412     \edef\languagename{%
413       \expandafter\string\csname\languagename\endcsname}%
disable babel.sty useless commands
414     \def\NeedsTeXFormat##1[##2]{}
415     \def\ProvidesPackage##1[##2]{}
416     \let\LdfInit\relax
417     \def\languageattribute##1##2{%
change the meaning of \DeclareOption
418     \def\DeclareOption##1##2{%
at \DeclareOption* we end
419       \ifx##1*\expandafter\endinput\else
else we build a string with the first argument
420       \edef\testlanguage{\expandafter\string\csname##1\endcsname}%
if \testlanguage and \languagename are the same we execute the second argu-
ment
421       \ifx\testlanguage\languagename##2\fi
422     \fi}
almost all options of babel are \input{<name>.ldf}
423   \def\input##1{\stripldf##1}%
we put the root language name in \rootlanguagename
424   \def\stripldf##1.ldf{\gdef\rootlanguagename{##1}}%
now input babel.sty, using the primitive \input
425   @@input babel.sty
426   \endgroup}%
427 }%
babel hasn't been loaded, so check if ngerman has been loaded
428   @ifpackageloaded{ngerman}{%
429     \def\findrootlanguage{%
430       \def\rootlanguagename{german}}%
431   }%
Neither babel nor ngerman have been loaded, so assume the root language is English
432     \def\findrootlanguage{%
433       \def\rootlanguagename{english}}%
434   }%
435   }%
436 \fi
\rootlanguagename Set default root language to English.
437 \def\rootlanguagename{english}

```

\@xdylanguage The `xindy` language setting is required by `makeglossaries`, so provide a command for `makeglossaries` to pick up the information from the auxiliary file. This command is not needed by the `glossaries` package, so define it to ignore its arguments.

```
438 \def\@xdylanguage#1#2{}
```

\GlsSetXdyLanguage Define a command that allows the user to set the language for a given glossary type. The first argument indicates the glossary type. If omitted the main glossary is assumed.

```
439 \ifglsxindy
440   \newcommand*\GlsSetXdyLanguage[2] [\"glsdefaulttype]{%
441     \ifglossaryexists{#1}{%
442       \expandafter\def\csname @xdy@#1@language\endcsname{#2}%
443     }%
444     \PackageError{glossaries}{Can't set language type for%
445       glossary type '#1' --- no such glossary}{%
446       You have specified a glossary type that doesn't exist}}}
447 \else
448   \newcommand*\GlsSetXdyLanguage[2] []{%
449     \glsnoxindywarning\GlsSetXdyLanguage}
450 \fi
```

\@gls@codepage The `xindy` codepage setting is required by `makeglossaries`, so provide a command for `makeglossaries` to pick up the information from the auxiliary file. This command is not needed by the `glossaries` package, so define it to ignore its arguments.

```
451 \def\@gls@codepage#1#2{}
```

\GlsSetXdyCodePage Define command to set the code page.

```
452 \ifglsxindy
453   \newcommand*\GlsSetXdyCodePage[1]{%
454     \renewcommand*\gls@codepage{#1}%
455   }
456 \else
457   \newcommand*\GlsSetXdyCodePage[1]{%
458     \glsnoxindywarning\GlsSetXdyCodePage}
459 \fi
```

\@xdylettergroups Store letter group definitions.

```
460 \ifglsxindy
461   \ifgls@xindy@glsnumbers
462     \def\@xdylettergroups{(\define-letter-group
463       \"string@glsnumbers\"string"^\~J\space\space\space
464       :prefixes (\\"string"0\"string" \\"string"1\"string"
465       \\"string"2\"string" \\"string"3\"string" \\"string"4\"string"
466       \\"string"5\"string" \\"string"6\"string" \\"string"7\"string"
467       \\"string"8\"string" \\"string"9\"string")^\~J\space\space\space
468       :before \\"string"\@glsfirstletter\"string"))
469   \else
470     \def\@xdylettergroups{}
471   \fi
472 \fi
473 % \end{macrocode}
```

```

474 %\end{macro}
475 %
476 %\begin{macro}{\GlsAddLetterGroup}
477 % Add a new letter group. The first argument is the name
478 % of the letter group. The second argument is the \appname{xindy}
479 % code specifying prefixes and ordering.
480 % \begin{macrocode}
481 \newcommand*\GlsAddLetterGroup[2]{%
482     \expandafter\toks@\expandafter{\@xdylettergroups}%
483     \protected@edef\@xdylettergroups{\the\toks@^~J}%
484     (define-letter-group \string"#1\string"~J\space\space\space#2)%
485 }

```

5.5 Loops and conditionals

To iterate through all glossaries (or comma-separated list of glossary names given in optional argument) use:

```
\forallglossaries[⟨glossary list⟩]{⟨cmd⟩}{⟨code⟩}
```

where $\langle cmd \rangle$ is a control sequence which will be set to the name of the glossary in the current iteration.

```
\forallglossaries
486 \newcommand*\forallglossaries[3][\@glo@types]{%
487 \for#2:=#1\do{\ifthenelse{\equal{#2}{} }{}{#3}}}
```

To iterate through all entries in a given glossary use:

```
\forglsentries[⟨type⟩]{⟨cmd⟩}{⟨code⟩}
```

where $\langle type \rangle$ is the glossary label and $\langle cmd \rangle$ is a control sequence which will be set to the entry label in the current iteration.

```
\forglsentries
488 \newcommand*\forglsentries[3][\glsdefaulttype]{%
489 \edef\@glo@list{\csname glolist@\#1\endcsname}%
490 \for#2:=\@glo@list\do{%
491 \ifthenelse{\equal{#2}{} }{}{#3}}}
```

To iterate through all glossary entries over all glossaries listed in the optional argument (the default is all glossaries) use:

```
\forallglsentries[⟨glossary list⟩]{⟨cmd⟩}{⟨code⟩}
```

Within `\forallglsentries`, the current glossary type is given by `\@@this@glo@`.

```
\forallglsentries
492 \newcommand*\forallglsentries[3][\@glo@types]{%
493 \expandafter\forallglossaries\expandafter[#1]{\@@this@glo@}{%
494 \forglsentries[\@@this@glo@]{#2}{#3}}}
```

To check to see if a glossary exists use:

```
\ifglossaryexists{⟨type⟩}{⟨true-text⟩}{⟨false-text⟩}
```

where $\langle type \rangle$ is the glossary's label.

```
\ifglossaryexists  
495 \newcommand{\ifglossaryexists}[3]{%  
496 \@ifundefined{glotype@\#1@out}{#3}{#2}}
```

To check to see if a glossary entry has been defined use:

```
\ifglsentryexists{\label}{\true}{\false}
```

where $\langle label \rangle$ is the entry's label.

```
\ifglsentryexists  
497 \newcommand{\ifglsentryexists}[3]{%  
498 \@ifundefined{glo@\#1@name}{#3}{#2}}
```

To determine if given glossary entry has been used in the document text yet use:

```
\ifglsused{\label}{\true}{\false}
```

where $\langle label \rangle$ is the entry's label. If true it will do $\langle true \text{ } text \rangle$ otherwise it will do $\langle false \text{ } text \rangle$.

```
\ifglsused  
499 \newcommand*{\ifglsused}[3]{\ifthenelse{\boolean{glo@\#1@flag}}{#2}{#3}}
```

The following two commands will cause an error if the given condition fails:

```
\glsdoifexists{\label}{\code}
```

Generate an error if entry specified by $\langle label \rangle$ doesn't exists, otherwise do $\langle code \rangle$.

```
\glsdoifexists  
500 \newcommand{\glsdoifexists}[2]{\ifglsentryexists{\#1}{\#2}{%  
501 \PackageError{glossaries}{Glossary entry '#1' has not been  
502 defined.}{You need to define a glossary entry before you  
503 can use it.}}
```

```
\glsdoifnoexists{\label}{\code}
```

The opposite: only do second argument if the entry doesn't exists. Generate an error message if it exists.

```
\glsdoifnoexists  
504 \newcommand{\glsdoifnoexists}[2]{\ifglsentryexists{\#1}{%  
505 \PackageError{glossaries}{Glossary entry '#1' has already  
506 been defined.}{}}{\#2}}
```

5.6 Defining new glossaries

A comma-separated list of glossary names is stored in $\@glo@types$. When a new glossary type is created, its identifying name is added to this list. This is used by commands that iterate through all glossaries (such as `\makeglossaries` and `\printglossaries`).

```
\@glo@types
```

```
507 \newcommand*{\@glo@types}{,}
```

A new glossary type is defined using `\newglossary`. Syntax:

```
\newglossary[⟨log-ext⟩]{⟨name⟩}{⟨in-ext⟩}{⟨out-ext⟩} {⟨title⟩}[⟨counter⟩]
```

where `⟨log-ext⟩` is the extension of the `makeindex` transcript file, `⟨in-ext⟩` is the extension of the glossary input file (read in by `\printglossary` and created by `makeindex`), `⟨out-ext⟩` is the extension of the glossary output file which is read in by `makeindex` (lines are written to this file by the `\glossary` command), `⟨title⟩` is the title of the glossary that is used in `\glossarysection` and `⟨counter⟩` is the default counter to be used by entries belonging to this glossary. The `makerglossaries` Perl script reads in the relevant extensions from the auxiliary file, and passes the appropriate file names and switches to `makeindex`.

```
\newglossary
```

```
508 \newcommand*{\newglossary}[5][glg]{%
```

```
509 \ifglossaryexists{#2}{%
```

```
510 \PackageError{glossaries}{Glossary type ‘#2’ already exists}{%
```

```
511 You can’t define a new glossary called ‘#2’ because it already
```

```
512 exists}{%
```

```
513 }{%
```

Add this to the list of glossary types:

```
514 \toks@{#2}\edef\@glo@types{\@glo@types\the\toks@,}{%
```

Define a comma-separated list of labels for this glossary type, so that all the entries for this glossary can be reset with a single command. When a new entry is created, its label is added to this list.

```
515 \expandafter\gdef\csname glolist@#2\endcsname{},}%
```

Store details of this new glossary type:

```
516 \expandafter\def\csname @glotype@#2@in\endcsname{#3}{%
```

```
517 \expandafter\def\csname @glotype@#2@out\endcsname{#4}{%
```

```
518 \expandafter\def\csname @glotype@#2@title\endcsname{#5}{%
```

```
519 \protected@write\@auxout{}{\string\@newglossary{#2}{#1}{#3}{#4}}{%
```

How to display this entry in the document text (uses `\glsdisplay` and `\glsdisplayfirst` by default). These can be redefined by the user later if required (see `\defglsdisplay` and `\defglsdisplayfirst`)

```
520 \expandafter\gdef\csname gls@#2@display\endcsname{%
```

```
521 \glsdisplay}{%
```

```
522 \expandafter\gdef\csname gls@#2@displayfirst\endcsname{%
```

```
523 \glsdisplayfirst}{%
```

Find out if the final optional argument has been specified, and use it to set the counter associated with this glossary. (Uses `\glscounter` if no optional argument is present.)

```
524 \@ifnextchar[{@\gls@setcounter{#2}}{\@gls@setcounter{#2}[\glscounter]}}{%
```

Only define new glossaries in the preamble:

```
525 \onlypreamble{\newglossary}
```

Only define new glossaries before `\makerglossaries`

```
526 \onlypremakeg\newglossary
```

\@newglossary is used to specify the file extensions for the `makeindex` input, output and transcript files. It is written to the auxiliary file by \newglossary. Since it is not used by L^AT_EX, \@newglossary simply ignores its arguments.

```
\@newglossary
527 \newcommand*{\@newglossary}[4]{}
```

Store counter to be used for given glossary type (the first argument is the glossary label, the second argument is the name of the counter):

```
\@gls@setcounter
528 \def\@gls@setcounter#1[#2]{%
529 \expandafter\def\csname @gloctype@#1@counter\endcsname{#2}%
530 }
```

Get counter associated with given glossary (the argument is the glossary label):

```
\@gls@getcounter
531 \newcommand*{\@gls@getcounter}[1]{%
532 \csname @gloctype@#1@counter\endcsname}
```

Define the main glossary. This will be the first glossary to be displayed when using \printglossaries.

```
533 \newglossary{main}{gls}{glo}{\glossaryname}
```

5.7 Defining new entries

New glossary entries are defined using \newglossaryentry. This command requires a label and a key-value list that defines the relevant information for that entry. The definition for these keys follows. Note that the `name`, `description` and `symbol` keys will be sanitized later, depending on the value of the package option `sanitize` (this means that if some of the keys haven't been defined, they can be constructed from the `name` and `description` key before they are sanitized).

- name** The `name` key indicates the name of the term being defined. This is how the term will appear in the glossary. The `name` key is required when defining a new glossary entry.

```
534 \define@key{glossentry}{name}{%
535 \def\@glo@name{#1}%
536 }
```

- description** The `description` key is usually only used in the glossary, but can be made to appear in the text by redefining `\glsdisplay` and `\glsdisplayfirst` (or using `\defglsdisplay` and `\defglsdisplayfirst`), however, you will have to disable the `sanitize` option (using the `sanitize` package option, `sanitize={description=false}`, and protect fragile commands). The `description` key is required when defining a new glossary entry. (Be careful not to make the description too long, because `makeindex` has a limited buffer. `\@glo@desc` is defined to be a short command to discourage lengthy descriptions for this reason. If you do have a very long description, or if you require paragraph breaks, define a separate command that contains the description, and use it as the value to the `description` key.)

```
537 \define@key{glossentry}{description}{%
538 \def\@glo@desc{#1}%
539 }
```

```

descriptionplural
540 \define@key{glossentry}{descriptionplural}{%
541 \def\@glo@descplural{\#1}%
542 }

sort The sort key needs to be sanitized here (the sort key is provided for makeindex's benefit, not for use in the document). The sort key is optional when defining a new glossary entry. If omitted, the value is given by (name) (description).
543 \define@key{glossentry}{sort}{%
544 \def\@glo@sort{\#1}%

text The text key determines how the term should appear when used in the document (i.e. outside of the glossary). If omitted, the value of the name key is used instead.
545 \define@key{glossentry}{text}{%
546 \def\@glo@text{\#1}%
547 }

plural The plural key determines how the plural form of the term should be displayed in the document. If omitted, the plural is constructed by appending \glspluralsuffix to the value of the text key.
548 \define@key{glossentry}{plural}{%
549 \def\@glo@plural{\#1}%
550 }

first The first key determines how the entry should be displayed in the document when it is first used. If omitted, it is taken to be the same as the value of the text key.
551 \define@key{glossentry}{first}{%
552 \def\@glo@first{\#1}%
553 }

firstplural The firstplural key is used to set the plural form for first use, in the event that the plural is required the first time the term is used. If omitted, it is constructed by appending \glspluralsuffix to the value of the first key.
554 \define@key{glossentry}{firstplural}{%
555 \def\@glo@firstplural{\#1}%
556 }

symbol The symbol key is ignored by most of the predefined glossary styles, and defaults to \relax if omitted. It is provided for glossary styles that require an associated symbol, as well as a name and description. To make this value appear in the glossary, you need to redefine \glossaryentryfield so that it uses its fourth parameter. If you want this value to appear in the text when the term is used by commands like \gls, you will need to change \glsdisplay and \glsdisplayfirst (either explicitly for all glossaries or via \defglsdisplay and \defglsdisplayfirst for individual glossaries).
557 \define@key{glossentry}{symbol}{%
558 \def\@glo@symbol{\#1}%
559 }

symbolplural
560 \define@key{glossentry}{symbolplural}{%
561 \def\@glo@symbolplural{\#1}%
562 }

```

type The type key specifies to which glossary this entry belongs. If omitted, the default glossary is used.

```
563 \define@key{glossentry}{type}{%
564 \def\@glo@type{\#1}}
```

counter The counter key specifies the name of the counter associated with this glossary entry:

```
565 \define@key{glossentry}{counter}{%
566 \@ifundefined{c@\#1}{\PackageError{glossaries}{There is no counter
567 called '\#1'}{\The counter key should have the name of a valid
568 counter as its value}}{%
569 \def\@glo@counter{\#1}}}
```

see The see key specifies a list of cross-references

```
570 \define@key{glossentry}{see}{%
571 \def\@glo@see{\#1}}
```

parent The parent key specifies the parent entry, if required.

```
572 \define@key{glossentry}{parent}{%
573 \def\@glo@parent{\#1}}
```

nonumberlist The nonumberlist key suppresses the number list for the given entry.

```
574 \define@key{glossentry}{nonumberlist}[none]{%
575 \def\@glo@prefix{\glsnonextpages}}
```

\@glsnoname Define command to generate error if name key is missing.

```
576 \newcommand*{\@glsnoname}{%
577   \PackageError{glossaries}{name key required in
578   \string\newglossaryentry\space for entry '\@glo@label'}{You
579   haven't specified the entry name}}
```

\@glsdefaultplural Define command to set default plural.

```
580 \newcommand*{\@glsdefaultplural}{\@glo@text\glspluralsuffix}
```

\@glsdefaultsort Define command to set default sort.

```
581 \newcommand*{\@glsdefaultsort}{\@glo@name}
```

\gls@level Register to increment entry levels.

```
582 \newcount\gls@level
```

Define `\newglossaryentry {<label>} {<key-val list>}`. There are two required fields in `<key-val list>`: name and description. (See above.)

\newglossaryentry

```
583 \DeclareRobustCommand{\newglossaryentry}[2]{%
  Check to see if this glossary entry has already been defined:
  584 \glsdoifnoexists{\#1}{%
    Store label
    585 \def\@glo@label{\#1}}
  Set up defaults. If the name or description keys are omitted, an error will be
  generated.
  586 \let\@glo@name\@glsnoname
```

```

587 \def\@glo@desc{\PackageError{glossaries}{description key required in
588 \string\newglossaryentry}{You haven't specified the entry description}}%
589 \def\@glo@descplural{\@glo@desc}%
590 \def\@glo@type{\glsdefaulttype}%
591 \def\@glo@symbol{\relax}%
592 \def\@glo@symbolplural{\@glo@symbol}%
593 \def\@glo@text{\@glo@name}%
594 \let\@glo@plural\glsdefaultplural

    Using \let instead of \def to make later comparison avoid expansion issues.
    (Thanks to Ulrich Diez for suggesting this.)
```

595 \let\@glo@first\relax

596 \let\@glo@firstplural\relax

Set the default sort:

597 \let\@glo@sort\glsdefaultsort

Set the default counter:

598 \def\@glo@counter{\gls@getcounter{\@glo@type}}%

599 \def\@glo@see{}%

600 \def\@glo@parent{}%

601 \def\@glo@prefix{}%

Extract key-val information from third parameter:

602 \setkeys{glossentry}{#2}%

 Check to see if this glossary type has been defined, if it has, add this label to the
 relevant list, otherwise generate an error.

603 \ifundefined{glolist@\@glo@type}{\PackageError{glossaries}{%
604 Glossary type '\@glo@type' has not been defined}}{%
605 You need to define a new glossary type, before making entries
606 in it}}{%
607 \protected@edef\glolist@{\csname glolist@\@glo@type\endcsname}%
608 \expandafter\xdef\csname glolist@\@glo@type\endcsname{\@glolist@{#1},}%
609 }%

Initialise level to 0.

610 \gls@level=0\relax

Has this entry been assigned a parent?

611 \ifx\@glo@parent\empty

Doesn't have a parent. Set \glo@*label*@parent to empty.

612 \expandafter\gdef\csname glo@#1@parent\endcsname{}%
613 \else

Has a parent. Check to ensure this entry isn't its own parent.

614 \ifthenelse{\equal{#1}{\@glo@parent}}{%
615 \PackageError{glossaries}{Entry '#1' can't be its own parent}}{%
616 \def\@glo@parent{}%
617 \expandafter\gdef\csname glo@#1@parent\endcsname{}%
618 }%

Check the parent exists:

```
619     \ifglsentryexists{\@glo@parent}{%
  Parent exists. Set \glo@<label>@parent.
620     \expandafter\xdef\csname glo@#1@parent\endcsname{\@glo@parent}%
Determine level.
```

```
621     \gls@level=\csname glo@ \@glo@parent @level\endcsname\relax
622     \advance\gls@level by 1\relax
```

If name hasn't been specified, use same as the parent name

```
623     \ifx\@glo@name\@glsnoname
624         \expandafter\let\expandafter\@glo@name
625             \csname glo@\@glo@parent @name\endcsname
```

If name and plural haven't been specified, use same as the parent

```
626     \ifx\@glo@plural\@glsdefaultplural
627         \expandafter\let\expandafter\@glo@plural
628             \csname glo@\@glo@parent @plural\endcsname
629         \fi
630     \fi
631 }%
```

Parent doesn't exist, so issue an error message and change this entry to have no parent

```
632     \PackageError{glossaries}{Invalid parent `@\glo@parent',
633         for entry '#1' - parent doesn't exist}{Parent entries
634         must be defined before their children}%
635     \def\@glo@parent{}%
636     \expandafter\gdef\csname glo@#1@parent\endcsname{}%
637 }%
638 }%
639 \fi
```

Set the level for this entry

```
640 \expandafter\xdef\csname glo@#1@level\endcsname{\number\gls@level}%
```

Check if first and firstplural have been used. If firstplural hasn't been specified, but first has been specified, then form firstplural by appending \glspluralsuffix to value of first key, otherwise obtain the value from the plural key. This now uses \ifx instead of \if to avoid expansion issues. (Thanks to Ulrich Diez for suggesting this.)

```
641 \ifx\relax\@glo@firstplural
642     \ifx\relax\@glo@first
643         \def\@glo@firstplural{\@glo@plural}%
644         \def\@glo@first{\@glo@text}%
645     \else
646         \def\@glo@firstplural{\@glo@first\glspluralsuffix}%
647     \fi
648 \else
649     \ifx\relax\@glo@first
650         \def\@glo@first{\@glo@text}%
651     \fi
652 \fi
```

Define commands associated with this entry:

```
653 \expandafter\protected@xdef\csname glo@#1@text\endcsname{\@glo@text}%
654 \expandafter\protected@xdef\csname glo@#1@plural\endcsname{\@glo@plural}%
655 \expandafter\protected@xdef\csname glo@#1@first\endcsname{\@glo@first}%
656 \expandafter\protected@xdef\csname glo@#1@firstpl\endcsname{\@glo@firstplural}%
657 \expandafter\protected@xdef\csname glo@#1@type\endcsname{\@glo@type}%
658 \expandafter\protected@xdef\csname glo@#1@counter\endcsname{\@glo@counter}%
659 \@gls@sanitizername
660 \expandafter\protected@xdef\csname glo@#1@name\endcsname{\@glo@name}%
```

The smaller and smallcaps options set the description to \@glo@first. Need to check for this, otherwise it won't get expanded if the description gets sanitized.

```
661 \def\@glo@@desc{\@glo@first}%
662 \ifx\@glo@desc\@glo@@desc
663   \let\@glo@desc\@glo@first
664 \fi
665 \@gls@sanitizedesc
666 \expandafter\protected@xdef\csname glo@#1@desc\endcsname{\@glo@desc}%
667 \expandafter\protected@xdef\csname glo@#1@descplural\endcsname{\@glo@descplural}%
Sanitize sort value:
```

```
668 \ifx\@glo@sort\@glsdefaultsort
669   \let\@glo@sort\@glo@name
670 \fi
671 \@onelevel@sanitize\@glo@sort
```

Set the sort key for this entry:

```
672 \expandafter\protected@xdef\csname glo@#1@sort\endcsname{\@glo@sort}%
673 \def\@glo@@symbol{\@glo@text}%
674 \ifx\@glo@symbol\@glo@@symbol
675   \let\@glo@symbol\@glo@text
676 \fi
677 \@gls@sanitizesymbol
678 \expandafter\protected@xdef\csname glo@#1@symbol\endcsname{\@glo@symbol}%
679 \expandafter\protected@xdef\csname glo@#1@symbolplural\endcsname{\@glo@symbolplural}%
Define an associated boolean variable to determine whether this entry has been used yet (needs to be defined globally):
```

```
680 \expandafter\gdef\csname glo@#1@flagfalse\endcsname{%
681 \expandafter\global\expandafter
682 \let\csname ifglo@#1@flag\endcsname\iffalse}%
683 \expandafter\gdef\csname glo@#1@flagtrue\endcsname{%
684 \expandafter\global\expandafter
685 \let\csname ifglo@#1@flag\endcsname\iftrue}%
686 \csname glo@#1@flagfalse\endcsname
```

Sort out any cross-referencing if required.

```
687 \ifx\@glo@see\@empty
688 \else
689   \protected@edef\@do@glssee{%
690     \noexpand\@gls@fixbraces\noexpand\@glo@list\@glo@see
691     \noexpand\@nil
692     \noexpand\expandafter\noexpand\@glssee\noexpand\@glo@list{#1}}%
693   \@do@glssee
694 \fi
695 }%
```

Determine and store main part of the entry's index format.

```
696  \@glo@storeentry{#1}%
697 }
```

\@glo@storeentry Determine the format to write the entry in the glossary output (.glo) file. The argument is the entry's label. The result is stored in \glo@⟨label⟩@entry, where ⟨label⟩ is the entry's label. (This doesn't include any formatting or location information.)

```
698 \newcommand{\@glo@storeentry}[1]{%
```

Get the sort string and escape any special characters

```
699 \protected@edef\glo@sort{\csname glo@#1@sort\endcsname}%
700 \@gls@checkmkidxchars\glo@sort
```

Same again for the name string.

```
701 \protected@edef\@glo@name{\csname glo@#1@name\endcsname}%
702 \@gls@checkmkidxchars\@glo@name
```

Add the font command. (The backslash needs to be escaped for xindy.)

```
703 \ifglsxindy
704  \protected@edef\glo@name{\string\\glsnamefont{\@glo@name}}%
705 \else
706  \protected@edef\glo@name{\string\glsnamefont{\@glo@name}}%
707 \fi
```

Get the description string and escape any special characters

```
708 \protected@edef\glo@desc{\csname glo@#1@desc\endcsname}%
709 \@gls@checkmkidxchars\glo@desc
```

Same again for the symbol

```
710 \protected@edef\glo@symbol{\csname glo@#1@symbol\endcsname}%
711 \@gls@checkmkidxchars\glo@symbol
```

Escape any special characters in the prefix

```
712 \@gls@checkmkidxchars\glo@prefix
```

Get the parent, if one exists

```
713 \edef\glo@parent{\csname glo@#1@parent\endcsname}%
```

Write the information to the glossary file.

```
714 \ifglsxindy
```

Store using xindy syntax.

```
715 \ifx\glo@parent\empty
```

Entry doesn't have a parent

```
716  \expandafter\protected@xdef\csname glo@#1@index\endcsname{%
717    (\string"\glo@sort\string" %
718     \string"\glo@prefix\string\\glossaryentryfield{#1}{\glo@name
719      }{\glo@desc}{\glo@symbol}\string") %
720  }%
721 \else
```

Entry has a parent

```
722  \expandafter\protected@xdef\csname glo@#1@index\endcsname{%
723    \csname glo@\glo@parent @index\endcsname
724    (\string"\glo@sort\string" %
```

```

725      \string"\@glo@prefix\string\\glossarysubentryfield%
726      {\csname glo@\#1@level\endcsname}{\#1}{\@glo@name
727      }{\@glo@desc}{\@glo@symbol}\string") %
728  }%
729  \fi
730 \else
    Store using makeindex syntax.
731  \ifx\@glo@parent\@empty
        Sanitize \@glo@prefix
732  \onelevel@sanitize\@glo@prefix
    Entry doesn't have a parent
733  \expandafter\protected@xdef\csname glo@\#1@index\endcsname{%
734      \@glo@sort\@gls@actualchar\@glo@prefix
735      \string\glossaryentryfield{\#1}{\@glo@name}{\@glo@desc
736      }{\@glo@symbol}%
737  }%
738 \else
    Entry has a parent
739  \expandafter\protected@xdef\csname glo@\#1@index\endcsname{%
740      \csname glo@\@glo@parent \@index\endcsname\@gls@levelchar
741      \@glo@sort\@gls@actualchar\@glo@prefix
742      \string\glossarysubentryfield
743      {\csname glo@\#1@level\endcsname}{\#1}{\@glo@name}{\@glo@desc
744      }{\@glo@symbol}%
745  }%
746  \fi
747 \fi
748 }

```

5.8 Resetting and unsetting entry flags

Each glossary entry is assigned a conditional of the form `\ifglo@⟨label⟩@flag` which determines whether or not the entry has been used (see also `\ifglsused` defined below). These flags can be set and unset using the following macros:

The command `\glsreset{⟨label⟩}` can be used to set the entry flag to indicate that it hasn't been used yet. The required argument is the entry label.

```

\glsreset
749 \newcommand*\glsreset}[1]{%
750 \glsdoifexists{#1}{%
751 \expandafter\global\csname glo@\#1@flagfalse\endcsname}}

```

As above, but with only a local effect:

```

\glslocalreset
752 \newcommand*\glslocalreset}[1]{%
753 \glsdoifexists{#1}{%
754 \expandafter\let\csname ifglo@\#1@flag\endcsname\iffalse}}

```

The command `\glsunset{⟨label⟩}` can be used to set the entry flag to indicate that it has been used. The required argument is the entry label.

```
\glsunset
755 \newcommand*{\glsunset}[1]{%
756 \glsdoifexists{#1}{%
757 \expandafter\global\csname glo@#1@flagtrue\endcsname}}
```

As above, but with only a local effect:

```
\glslocalunset
758 \newcommand*{\glslocalunset}[1]{%
759 \glsdoifexists{#1}{%
760 \expandafter\let\csname ifglo@#1@flag\endcsname\iftrue}}
```

Reset all entries for the named glossaries (supplied in a comma-separated list).
Syntax: `\glsresetall[<glossary-list>]`

```
\glsresetall
761 \newcommand*{\glsresetall}[1][\@glo@types]{%
762 \forallglsentries[#1]{\@glsentry}{%
763 \glsreset{\@glsentry}}}
```

As above, but with only a local effect:

```
\glslocalresetall
764 \newcommand*{\glslocalresetall}[1][\@glo@types]{%
765 \forallglsentries[#1]{\@glsentry}{%
766 \glslocalreset{\@glsentry}}}
```

Unset all entries for the named glossaries (supplied in a comma-separated list).
Syntax: `\glsunsetall[<glossary-list>]`

```
\glsunsetall
767 \newcommand*{\glsunsetall}[1][\@glo@types]{%
768 \forallglsentries[#1]{\@glsentry}{%
769 \glsunset{\@glsentry}}}
```

As above, but with only a local effect:

```
\glslocalunsetall
770 \newcommand*{\glslocalunsetall}[1][\@glo@types]{%
771 \forallglsentries[#1]{\@glsentry}{%
772 \glslocalunset{\@glsentry}}}
```

5.9 Loading files containing glossary entries

Glossary entries can be defined in an external file. These external files can contain `\newglossaryentry` and `\newacronym` commands.¹⁷

```
\loadglsentries[<type>]{<filename>}
```

This command will input the file using `\input`. The optional argument specifies to which glossary the entries should be assigned if they haven't used the `type` key. If the optional argument is not specified, the default glossary is used. Only those entries used in the document (via `\glslink`, `\gls`, `\glspl` and uppercase variants or `\glsadd` and `\glsaddall` will appear in the glossary). The mandatory argument is the filename (with or without .tex extension).

¹⁷and any other valid L^AT_EX code that can be used in the preamble.

```
\loadglsentries
773 \newcommand*{\loadglsentries}[2]{\@gls@default}{%
774 \let\@gls@default\glsdefaulttype
775 \def\glsdefaulttype{\#1}\input{\#2}%
776 \let\glsdefaulttype\@gls@default}

\loadglsentries can only be used in the preamble:
777 \onlypreamble{\loadglsentries}
```

5.10 Using glossary entries in the text

Any term that has been defined using `\newglossaryentry` (or `\newacronym`) can be displayed in the text (i.e. outside of the glossary) using one of the commands defined in this section. Unless you use `\glslink`, the way the term appears in the text is determined by `\glsdisplayfirst` (if it is the first time the term has been used) or `\glsdisplay` (for subsequent use). Any formatting commands (such as `\textbf`) is governed by `\glstextformat`. By default this just displays the link text “as is”.

```
\glstextformat
778 \newcommand*{\glstextformat}[1]{#1}
```

The first time an entry is used, the way in which it is displayed is governed by `\glsdisplayfirst`. This takes four parameters: #1 will be the value of the entry’s `first` or `firstplural` key, #2 will be the value of the entry’s `description` key, #3 will be the value of the entry’s `symbol` key and #4 is additional text supplied by the final optional argument to commands like `\gls` and `\glspl`. The default is to display the first parameter followed by the additional text.

```
\glsdisplayfirst
779 \newcommand*{\glsdisplayfirst}[4]{#1#4}
```

After the first use, the entry is displayed according to the format of `\glsdisplay`. Again, it takes four parameters: #1 will be the value of the entry’s `text` or `plural` key, #2 will be the value of the entry’s `description` key, #3 will be the value of the entry’s `symbol` key and #4 is additional text supplied by the final optional argument to commands like `\gls` and `\glspl`.

```
\glsdisplay
780 \newcommand*{\glsdisplay}[4]{#1#4}
```

When a new glossary is created it uses `\glsdisplayfirst` and `\glsdisplay` as the default way of displaying its entry in the text. This can be changed for the entries belonging to an individual glossary using `\defglsdisplay` and `\defglsdisplayfirst`.

```
\defglsdisplay[<type>]{<definition>}
```

The glossary type is given by `<type>` (the default glossary if omitted) and `<definition>` should have at most #1, #2, #3 and #4. These represent the same arguments as those described for `\glsdisplay`.

```
\defglsdisplay
781 \newcommand*{\defglsdisplay}[2][\glsdefaulttype]{%
782 \expandafter\def\csname gls@\#1@display\endcsname##1##2##3##4{#2}}
783 \defglsdisplayfirst[<type>]{<definition>}
```

The glossary type is given by *<type>* (the default glossary if omitted) and *<definition>* should have at most #1, #2, #3 and #4. These represent the same arguments as those described for `\glsdisplayfirst`.

```
\defglsdisplayfirst
783 \newcommand*{\defglsdisplayfirst}[2][\glsdefaulttype]{%
784 \expandafter\def\csname gls@\#1@displayfirst\endcsname##1##2##3##4{#2}}
```

5.10.1 Links to glossary entries

The links to glossary entries all have a first optional argument that can be used to change the format and counter of the associated entry number. Except for `\glslink`, the commands like `\gls` have a final optional argument that can be used to insert additional text in the link (this will usually be appended, but can be redefined using `\defglsdisplay` and `\defglsdisplayfirst`). It goes against the L^AT_EX norm to have an optional argument after the mandatory arguments, but it makes more sense to write, say, `\gls{label}'s` rather than, say, `\gls[append='s]{label}`. Since these control sequences are defined to include the final square bracket, spaces will be ignored after them. This is likely to lead to confusion as most users would not expect, say, `\gls{<label>}` to ignore following spaces, so `\new@ifnextchar` from the `amsgen` package is required.

The following keys can be used in the first optional argument. The `counter` key checks that the value is the name of a valid counter.

```
785 \define@key{glslink}{counter}{%
786 @ifundefined{c@#1}{\PackageError{glossaries}{There is no counter
787 called '#1'}{\The counter key should have the name of a valid
788 counter as its value}}{%
789 \def\@gls@counter{#1}}}
```

The value of the `format` key should be the name of a command (without the initial backslash) that has a single mandatory argument which can be used to format the associated entry number.

```
790 \define@key{glslink}{format}{%
791 \def\@glsnumberformat{#1}}
```

The `hyper` key is a boolean key, it can either have the value `true` or `false`, and indicates whether or not to make a hyperlink to the relevant glossary entry. If `hyper` is `false`, an entry will still be made in the glossary, but the given text won't be a hyperlink.

```
792 \define@boolkey{glslink}{hyper}{true}{}{}
```

Syntax:

```
\glslink[<options>]{<label>}{<text>}
```

Display *<text>* in the document, and add the entry information for *<label>* into

the relevant glossary. The optional argument should be a key value list using the `glslink` keys defined above.

There is also a starred version:

```
\glslink*[\langle options \rangle]{\langle label \rangle}{\langle text \rangle}
```

which is equivalent to `\glslink[hyper=false,\langle options \rangle]{\langle label \rangle}{\langle text \rangle}`

First determine whether or not we are using the starred version:

```
\glslink
793 \newcommand{\glslink}{%
794 \@ifstar@gls@link@gls@link}
```

Define the starred version:

```
\@gls@link
795 \newcommand*{\@gls@link}[1][]{\@gls@link[hyper=false,#1]}
```

Define the un-starred version:

```
\@gls@link
796 \newcommand*{\@gls@link}[3][]{%
797   \glsdoifexists{#2}%
798   {%
799     \def\glslabel{#2}%
800     \def\@glsnumberformat{\glsnumberformat}%
801     \edef\@gls@counter{\csname glo@#2@counter\endcsname}%
802     \KV@glslink@hypertrue
803     \setkeys[glslink]{#1}%
804     \edef\theglsentrycounter{\expandafter\noexpand
805       \csname the@gls@counter\endcsname}%
806     \ifKV@glslink@hyper
807       \glslink{glo:#2}{\glstextformat{#3}}%
808     \else
809       \glstextformat{#3}\relax
810     \fi
811     \do@wrglossary{#2}%
812   }%
813 }
```

Set the formatting information in the format required by `makeindex`. The first argument is the format specified by the user (via the `format` key), the second argument is the name of the counter used to indicate the location and the third argument is a control sequence which stores the required format.

```
\@set@glo@numformat
814 \def\@set@glo@numformat#1#2#3{%
815   \expandafter\@glo@check@mkidxrangechar#3\@nil
816   \protected@edef#1{\@glo@prefix setentrycounter{#2}%
817   \expandafter\string\csname\@glo@suffix\endcsname}%
818 \gls@checkmkidxchars#1}
```

Check to see if the given string starts with a (or). If it does set `\@glo@prefix` to the starting character, and `\@glo@suffix` to the rest (or `\glsnumberformat` if

there is nothing else), otherwise set \@glo@prefix to nothing and \@glo@suffix to all of it.

```

819 \def\@glo@check@mkidxrangechar#1#2\@nil{%
820 \if#1(\relax
821   \def\@glo@prefix{()%
822   \if\relax#2\relax
823     \def\@glo@suffix{glsnumberformat}%
824   \else
825     \def\@glo@suffix{#2}%
826   \fi
827 \else
828   \if#1)\relax
829     \def\@glo@prefix{}%
830     \if\relax#2\relax
831       \def\@glo@suffix{glsnumberformat}%
832     \else
833       \def\@glo@suffix{#2}%
834     \fi
835   \else
836     \def\@glo@prefix{}\def\@glo@suffix{#1#2}%
837   \fi
838 \fi}

```

\@gls@escbsdq Escape backslashes and double quote marks. The argument must be a control sequence.

```

839 \newcommand*\@gls@escbsdq}[1]{%
840   \def\@gls@checkedmkidx{}%
841   \let\gls@xdystring=#1\relax
842   \onelevel@sanitize\gls@xdystring
843   \edef\do@gls@xdycheckbackslash{%
844     \noexpand\gls@xdycheckbackslash\gls@xdystring\noexpand\@nil
845     \@backslashchar\@backslashchar\noexpand\null}%
846   \do@gls@xdycheckbackslash
847   \expandafter\gls@updatechecked\gls@checkedmkidx{\gls@xdystring}%
848   \def\@gls@checkedmkidx{}%
849   \expandafter\gls@xdycheckquote\gls@xdystring\@nil""\null
850   \expandafter\gls@updatechecked\gls@checkedmkidx{\gls@xdystring}%
851   \let#1=\gls@xdystring
852 }

```

Catch special characters(argument must be a control sequence):

```

\@gls@checkmkidxchars
853 \newcommand{\@gls@checkmkidxchars}[1]{%
854 \ifglsxindy
855   \gls@escbsdq{#1}%
856 \else
857   \def\@gls@checkedmkidx{}%
858   \expandafter\gls@checkquote#1\@nil""\null
859   \expandafter\gls@updatechecked\gls@checkedmkidx{#1}%
860   \def\@gls@checkedmkidx{}%
861   \expandafter\gls@checkescquote#1\@nil\""\null
862   \expandafter\gls@updatechecked\gls@checkedmkidx{#1}%
863   \def\@gls@checkedmkidx{}%

```

```

864 \expandafter\@gls@checkescactual#1\@nil\?\\?\null
865 \expandafter\@gls@updatechecked\@gls@checkedmidx{#1}%
866 \def\@gls@checkedmidx{}%
867 \expandafter\@gls@checkactual#1\@nil??\null
868 \expandafter\@gls@updatechecked\@gls@checkedmidx{#1}%
869 \def\@gls@checkedmidx{}%
870 \expandafter\@gls@checkbar#1\@nil||\null
871 \expandafter\@gls@updatechecked\@gls@checkedmidx{#1}%
872 \def\@gls@checkedmidx{}%
873 \expandafter\@gls@checkescbar#1\@nil\\|\|\null
874 \expandafter\@gls@updatechecked\@gls@checkedmidx{#1}%
875 \def\@gls@checkedmidx{}%
876 \expandafter\@gls@checklevel#1\@nil!!\null
877 \expandafter\@gls@updatechecked\@gls@checkedmidx{#1}%
878 \fi
879 }

```

Update the control sequence and strip trailing \@nil:

\@gls@updatechecked

```
880 \def\@gls@updatechecked#1\@nil#2{\def#2{#1}}
```

\@gls@tmpb Define temporary token

```
881 \newtoks\@gls@tmpb
```

\@gls@checkquote Replace " with "" since " is a makeindex special character.

```

882 \def\@gls@checkquote#1"#2"#3\null{%
883 \@gls@tmpb=\expandafter{\@gls@checkedmidx}%
884 \toks@={#1}%
885 \ifx\null#2\null
886 \ifx\null#3\null
887 \edef\@gls@checkedmidx{\the\@gls@tmpb\the\toks@}%
888 \def\@gls@checkquote{\relax}%
889 \else
890 \edef\@gls@checkedmidx{\the\@gls@tmpb\the\toks@%
891 \@gls@quotechar\@gls@quotechar\@gls@quotechar\@gls@quotechar}%
892 \def\@gls@checkquote{\@gls@checkquote#3\null}%
893 \fi
894 \else
895 \edef\@gls@checkedmidx{\the\@gls@tmpb\the\toks@%
896 \@gls@quotechar\@gls@quotechar}%
897 \ifx\null#3\null
898 \def\@gls@checkquote{\@gls@checkquote#2""\null}%
899 \else
900 \def\@gls@checkquote{\@gls@checkquote#2"#3\null}%
901 \fi
902 \fi
903 \@@gls@checkquote}
```

\@gls@checkescquote Do the same for ":"

```

904 \def\@gls@checkescquote#1"#2"#3\null{%
905 \@gls@tmpb=\expandafter{\@gls@checkedmidx}%
906 \toks@={#1}%
907 \ifx\null#2\null
```

```

908 \ifx\null#3\null
909 \edef\@gls@checkedmkidx{\the\@gls@tmpb\the\toks@}%
910 \def\@gls@checkescquote{\relax}%
911 \else
912 \edef\@gls@checkedmkidx{\the\@gls@tmpb\the\toks@%
913   \@gls@quotechar\string\"@\gls@quotechar
914   \@gls@quotechar\string\"@\gls@quotechar}%
915 \def\@gls@checkescquote{\@gls@checkescquote#3\null}%
916 \fi
917 \else
918 \edef\@gls@checkedmkidx{\the\@gls@tmpb\the\toks@%
919   \@gls@quotechar\string\"@\gls@quotechar}%
920 \ifx\null#3\null
921   \def\@gls@checkescquote{\@gls@checkescquote#2\""\null}%
922 \else
923   \def\@gls@checkescquote{\@gls@checkescquote#2\"#3\null}%
924 \fi
925 \fi
926 \@@gls@checkescquote}

```

\@gls@checkescactual Similarly for \? (which is replaces @ as `makeindex`'s special character):

```

927 \def\@gls@checkescactual#1\?#2\?#3\null{%
928 \@gls@tmpb=\expandafter{\@gls@checkedmkidx}%
929 \toks@={#1}%
930 \ifx\null#2\null
931 \ifx\null#3\null
932 \edef\@gls@checkedmkidx{\the\@gls@tmpb\the\toks@}%
933 \def\@gls@checkescactual{\relax}%
934 \else
935 \edef\@gls@checkedmkidx{\the\@gls@tmpb\the\toks@%
936   \@gls@quotechar\string\"@\gls@actualchar
937   \@gls@quotechar\string\"@\gls@actualchar}%
938 \def\@gls@checkescactual{\@gls@checkescactual#3\null}%
939 \fi
940 \else
941 \edef\@gls@checkedmkidx{\the\@gls@tmpb\the\toks@%
942   \@gls@quotechar\string\"@\gls@actualchar}%
943 \ifx\null#3\null
944 \def\@gls@checkescactual{\@gls@checkescactual#2\??\?}\null}%
945 \else
946 \def\@gls@checkescactual{\@gls@checkescactual#2\?#3\null}%
947 \fi
948 \fi
949 \@@gls@checkescactual}

```

\@gls@checkescbar Similarly for \|:

```

950 \def\@gls@checkescbar#1\|#2\|#3\null{%
951 \@gls@tmpb=\expandafter{\@gls@checkedmkidx}%
952 \toks@={#1}%
953 \ifx\null#2\null
954 \ifx\null#3\null
955 \edef\@gls@checkedmkidx{\the\@gls@tmpb\the\toks@}%
956 \def\@gls@checkescbar{\relax}%
957 \else

```

```

958 \edef\@gls@checkedmidx{\the\@gls@tmpb\the\toks@
959   \@gls@quotechar/string\"@\gls@encapchar
960   \@gls@quotechar/string\"@\gls@encapchar}%
961 \def\@@gls@checkescbar{\gls@checkescbar#3\null}%
962 \fi
963 \else
964 \edef\@gls@checkedmidx{\the\@gls@tmpb\the\toks@
965   \@gls@quotechar/string\"@\gls@encapchar}%
966 \ifx\null#3\null
967 \def\@@gls@checkescbar{\gls@checkescbar#2|\|\|\\null}%
968 \else
969 \def\@@gls@checkescbar{\gls@checkescbar#2\|#3\null}%
970 \fi
971 \fi
972 \@@gls@checkescbar}

```

\@gls@checkesclevel Similarly for \!:

```

973 \def\@gls@checkesclevel#1\!#2\!#3\null{%
974 \@gls@tmpb=\expandafter{\gls@checkedmidx}%
975 \toks@={#1}%
976 \ifx\null#2\null
977 \ifx\null#3\null
978 \edef\@gls@checkedmidx{\the\@gls@tmpb\the\toks@}%
979 \def\@@gls@checkesclevel{\relax}%
980 \else
981 \edef\@gls@checkedmidx{\the\@gls@tmpb\the\toks@
982   \@gls@quotechar/string\"@\gls@levelchar
983   \@gls@quotechar/string\"@\gls@levelchar}%
984 \def\@@gls@checkesclevel{\gls@checkesclevel#3\null}%
985 \fi
986 \else
987 \edef\@gls@checkedmidx{\the\@gls@tmpb\the\toks@
988   \@gls@quotechar/string\"@\gls@levelchar}%
989 \ifx\null#3\null
990 \def\@@gls@checkesclevel{\gls@checkesclevel#2\!\\!\|\\null}%
991 \else
992 \def\@@gls@checkesclevel{\gls@checkesclevel#2\!#3\null}%
993 \fi
994 \fi
995 \@@gls@checkesclevel}

```

\@gls@checkbar and for |:

```

996 \def\@gls@checkbar#1\!#2\!#3\null{%
997 \@gls@tmpb=\expandafter{\gls@checkedmidx}%
998 \toks@={#1}%
999 \ifx\null#2\null
1000 \ifx\null#3\null
1001 \edef\@gls@checkedmidx{\the\@gls@tmpb\the\toks@}%
1002 \def\@@gls@checkbar{\relax}%
1003 \else
1004 \edef\@gls@checkedmidx{\the\@gls@tmpb\the\toks@
1005   \@gls@quotechar\@gls@encapchar\@gls@quotechar\@gls@encapchar}%
1006 \def\@@gls@checkbar{\gls@checkbar#3\null}%
1007 \fi

```

```

1008 \else
1009  \edef\@gls@checkedmkidx{\the\@gls@tmpb\the\toks@%
1010    \gls@quotechar\gls@encapchar}%
1011 \ifx\null#3\null
1012  \def\@@gls@checkbar{\gls@checkbar#2||\null}%
1013 \else
1014  \def\@@gls@checkbar{\gls@checkbar#2|#3\null}%
1015 \fi
1016 \fi
1017 \@@gls@checkbar}

```

\@gls@checklevel and for !:

```

1018 \def\@gls@checklevel#1!#2#!#3\null{%
1019 \gls@tmpb=\expandafter{\gls@checkedmkidx}%
1020 \toks@={#1}%
1021 \ifx\null#2\null
1022 \ifx\null#3\null
1023 \edef\@gls@checkedmkidx{\the\@gls@tmpb\the\toks@}%
1024 \def\@@gls@checklevel{\relax}%
1025 \else
1026 \edef\@gls@checkedmkidx{\the\@gls@tmpb\the\toks@%
1027   \gls@quotechar\gls@levelchar\gls@quotechar\gls@levelchar}%
1028 \def\@@gls@checklevel{\gls@checklevel#3\null}%
1029 \fi
1030 \else
1031 \edef\@gls@checkedmkidx{\the\@gls@tmpb\the\toks@%
1032   \gls@quotechar\gls@levelchar}%
1033 \ifx\null#3\null
1034 \def\@@gls@checklevel{\gls@checklevel#2!!\null}%
1035 \else
1036 \def\@@gls@checklevel{\gls@checklevel#2#!#3\null}%
1037 \fi
1038 \fi
1039 \@@gls@checklevel}

```

\@gls@checkactual and for ?:

```

1040 \def\@gls@checkactual#1?#2?#3\null{%
1041 \gls@tmpb=\expandafter{\gls@checkedmkidx}%
1042 \toks@={#1}%
1043 \ifx\null#2\null
1044 \ifx\null#3\null
1045 \edef\@gls@checkedmkidx{\the\@gls@tmpb\the\toks@}%
1046 \def\@@gls@checkactual{\relax}%
1047 \else
1048 \edef\@gls@checkedmkidx{\the\@gls@tmpb\the\toks@%
1049   \gls@quotechar\gls@actualchar\gls@quotechar\gls@actualchar}%
1050 \def\@@gls@checkactual{\gls@checkactual#3\null}%
1051 \fi
1052 \else
1053 \edef\@gls@checkedmkidx{\the\@gls@tmpb\the\toks@%
1054   \gls@quotechar\gls@actualchar}%
1055 \ifx\null#3\null
1056 \def\@@gls@checkactual{\gls@checkactual#2??\null}%
1057 \else

```

```

1058   \def\@@gls@checkactual{\@gls@checkactual#2##3\null}%
1059 \fi
1060 \fi
1061 \@@gls@checkactual}

```

\@gls@xdycheckquote As before but for use with xindy

```

1062 \def\@gls@xdycheckquote#1"#2"#3\null{%
1063 \@gls@tmpb=\expandafter{\@gls@checkedmidx}%
1064 \toks@={#1}%
1065 \ifx\null#2\null
1066 \ifx\null#3\null
1067 \edef\@gls@checkedmidx{\the\@gls@tmpb\the\toks@}%
1068 \def\@@gls@xdycheckquote{\relax}%
1069 \else
1070 \edef\@gls@checkedmidx{\the\@gls@tmpb\the\toks@%
1071 \string"\string"}%
1072 \def\@@gls@xdycheckquote{\@gls@xdycheckquote#3\null}%
1073 \fi
1074 \else
1075 \edef\@gls@checkedmidx{\the\@gls@tmpb\the\toks@%
1076 \string"}%
1077 \ifx\null#3\null
1078 \def\@@gls@xdycheckquote{\@gls@xdycheckquote#2""\null}%
1079 \else
1080 \def\@@gls@xdycheckquote{\@gls@xdycheckquote#2##3\null}%
1081 \fi
1082 \fi
1083 \@@gls@xdycheckquote
1084 }

```

\@gls@xdycheckbackslash Need to escape all backslashes for xindy. Define command that will define
\@gls@xdycheckbackslash

```

1085 \edef\def@gls@xdycheckbackslash{%
1086 \noexpand\def\noexpand\@gls@xdycheckbackslash##1@\backslashchar
1087 ##2@\backslashchar##3\noexpand\null{%
1088 \noexpand\@gls@tmpb=\noexpand\expandafter
1089 {\noexpand\@gls@checkedmidx}%
1090 \noexpand\toks@={#1}%
1091 \noexpand\ifx\noexpand\null##2\noexpand\null
1092 \noexpand\ifx\noexpand\null##3\noexpand\null
1093 \noexpand\edef\noexpand\@gls@checkedmidx{%
1094 \noexpand\the\noexpand\@gls@tmpb\noexpand\the\noexpand\toks@}%
1095 \noexpand\def\noexpand\@gls@xdycheckbackslash{\relax}%
1096 \noexpand\else
1097 \noexpand\edef\noexpand\@gls@checkedmidx{%
1098 \noexpand\the\noexpand\@gls@tmpb\noexpand\the\noexpand\toks@%
1099 \backslashchar\backslashchar\backslashchar\backslashchar}%
1100 \noexpand\def\noexpand\@gls@xdycheckbackslash{%
1101 \noexpand\@gls@xdycheckbackslash##3\noexpand\null}%
1102 \noexpand\fi
1103 \noexpand\else
1104 \noexpand\edef\noexpand\@gls@checkedmidx{%
1105 \noexpand\the\noexpand\@gls@tmpb\noexpand\the\noexpand\toks@%
1106 \backslashchar\backslashchar}%

```

```

1107 \noexpand\ifx\noexpand\null##3\noexpand\null
1108   \noexpand\def\noexpand\@gls@xdycheckbackslash{%
1109     \noexpand\@gls@xdycheckbackslash##2\@backslashchar
1110     \@backslashchar\noexpand\null}%
1111   \noexpand\else
1112     \noexpand\def\noexpand\@gls@xdycheckbackslash{%
1113       \noexpand\@gls@xdycheckbackslash##2\@backslashchar
1114       ##3\noexpand\null}%
1115   \noexpand\fi
1116 \noexpand\fi
1117 \noexpand\@gls@xdycheckbackslash
1118 }%
1119 }

```

Now go ahead and define \gls@xdycheckbackslash

```
1120 \def@gls@xdycheckbackslash
```

\@glslink If \hyperlink is not defined \glslink ignores its first argument and just does the second argument, otherwise it is equivalent to \hyperlink.

```

1121 \@ifundefined{hyperlink}{%
1122   \gdef\@glslink#1#2{#2}%
1123 }{%
1124   \gdef\@glslink#1#2{\hyperlink{#1}{#2}}%
1125 }

```

\@glstarget If \hypertarget is not defined, \glstarget ignores its first argument and just does the second argument, otherwise it is equivalent to \hypertarget.

```

1126 \newlength\gls@tmpplen
1127 \@ifundefined{hypertarget}{%
1128   \gdef\@glstarget#1#2{#2}%
1129 }{%
1130   \gdef\@glstarget#1#2{%
1131     \settoheight{\gls@tmpplen}{#2}%
1132     \raisebox{\gls@tmpplen}{\hypertarget{#1}{}}#2}%
1133 }

```

Glossary hyperlinks can be disabled using \glsdisablehyper (effect can be localised):

```
\glsdisablehyper
1134 \newcommand{\glsdisablehyper}{%
1135 \renewcommand*{\glslink[2]##2}{%
1136 \renewcommand*{\glstarget[2]##2}{}}
```

Glossary hyperlinks can be enabled using \glsenablehyper (effect can be localised):

```
\glsenablehyper
1137 \newcommand{\glsenablehyper}{%
1138 \renewcommand*{\glslink[2]{\hyperlink{##1}{##2}}}{%
1139 \renewcommand*{\glstarget[2]}{%
1140 \settoheight{\gls@tmpplen}{##2}%
1141 \raisebox{\gls@tmpplen}{\hypertarget{##1}{}}##2}}
```

Syntax:

```
\gls[<options>]{<label>}[<insert text>]
```

Link to glossary entry using singular form. The link text is taken from the value of the `text` or `first` keys used when the entry was defined.

The first optional argument is a key-value list, the same as `\glslink`, the mandatory argument is the entry label. After the mandatory argument, there is another optional argument to insert extra text in the link text (the location of the inserted text is governed by `\glsdisplay` and `\glsdisplayfirst`). As with `\glslink` there is a starred version which is the same as the unstarred version but with the `hyper` key set to `false`. (Additional options can also be specified in the first optional argument.)

First determine if we are using the starred form:

```
\gls  
1142 \newcommand*{\gls}{\@ifstar\@sgls\@gls}
```

Define the starred form:

```
\@sgls  
1143 \newcommand*{\@sgls}[1][]{\@gls[hyper=false,#1]}
```

Defined the un-starred form. Need to determine if there is a final optional argument

```
\@gls  
1144 \newcommand*{\@gls}[2][]{%  
1145 \new@ifnextchar[\@gls@{\#1}{\#2}]{\@gls@{\#1}{\#2}[]}}
```

`\@gls@` Read in the final optional argument:

```
1146 \def\@gls@#1#2[#3]{%  
1147 \glsdoifexists{#2}{\edef\@glo@type{\glsentrytype{#2}}}{%
```

Save options in `\@gls@link@opts` and label in `\@gls@link@label`

```
1148 \def\@gls@link@opts{#1}{%  
1149 \def\@gls@link@label{#2}{%
```

Determine what the link text should be (this is stored in `\@glo@text`)

```
1150 \ifglsused{#2}{\protected@edef\@glo@text{  
1151 \csname gls@\@glo@type @display\endcsname  
1152 {\glsentrytext{#2}}{\glsentrydesc{#2}}{\glsentrysymbol{#2}}{#3}}}{%  
1153 \protected@edef\@glo@text{  
1154 \csname gls@\@glo@type @displayfirst\endcsname  
1155 {\glsentryfirst{#2}}{\glsentrydesc{#2}}{\glsentrysymbol{#2}}{#3}}}{%
```

Call `\@gls@link`. If footnote package option has been used, suppress hyperlink for first use.

```
1156 \ifglsused{#2}{%  
1157 \@gls@link[#1]{#2}{\@glo@text}{%  
1158 }{  
1159 \ifthenelse{\equal{\@glo@type}{\acronymtype}\and  
1160 \boolean{glsacrfootnote}}{  
1161 \gls@link[#1,hyper=false]{#2}{\@glo@text}{%  
1162 }{  
1163 }}
```

```

1163     \@gls@link[#1]{#2}{\@glo@text}%
1164   }%
1165 }%

```

Indicate that this entry has now been used

```

1166 \glsunset{#2}%
1167 }

```

\Gls behaves like \gls, but the first letter of the link text is converted to uppercase (note that if the first letter has an accent, the accented letter will need to be grouped when you define the entry). It is mainly intended for terms that start a sentence:

```
\Gls
1168 \newcommand*{\Gls}{\@ifstar\@sGls\@Gls}
```

Define the starred form:

```
1169 \newcommand*{\@sGls}[1][]{\@Gls[hyper=false,#1]}
```

Defined the un-starred form. Need to determine if there is a final optional argument

```
1170 \newcommand*{\@Gls}[2][]{%
1171 \new@ifnextchar[\{\@Gls@{\#1}{#2}\}{\@Gls@{\#1}{#2}[]}]}
```

\@Gls@ Read in the final optional argument:

```
1172 \def\@Gls@#1#2[#3]{%
1173 \glsdoifexists{#2}{\edef\@glo@type{\glsentrytype{#2}}}{%
```

Save options in \@gls@link@opts and label in \@gls@link@label

```
1174 \def\@gls@link@opts{#1}%
1175 \def\@gls@link@label{#2}%

```

Determine what the link text should be (this is stored in \@glo@text)

```
1176 \ifglsused{#2}{\protected\edef\@glo@text{%
1177 \csname gls@\@glo@type \display\endcsname
1178 {\glsentrytext{#2}}{\glsentrydesc{#2}}{\glsentrysymbol{#2}}{#3}}}{%
1179 \protected\edef\@glo@text{%
1180 \csname gls@\@glo@type \displayfirst\endcsname
1181 {\glsentryfirst{#2}}{\glsentrydesc{#2}}{\glsentrysymbol{#2}}{#3}}}{%
```

Call \@gls@link If footnote package option has been used, suppress hyperlink for first use.

```
1182 \ifglsused{#2}{%
1183   \@gls@link[#1]{#2}{%
1184     \expandafter\makefirststuc\expandafter{\@glo@text}}{%
1185   }{%
1186     \ifthenelse{\equal{\@glo@type}{\acronymtype}\and
1187       \boolean{glsacrfootnote}}{%
1188       \@gls@link[#1,hyper=false]{#2}{%
1189         \expandafter\makefirststuc\expandafter{\@glo@text}}{%
1190       }{%
1191         \@gls@link[#1]{#2}{%
1192           \expandafter\makefirststuc\expandafter{\@glo@text}}{%
1193         }{%
1194       }{%
1195     }{%
1196   }{%
1197 }
```

Indicate that this entry has now been used

```
1195 \glsunset{#2}%
1196 }
```

\GLS behaves like \gls, but the link text is converted to uppercase:

\GLS

```
1197 \newcommand*{\GLS}{\@ifstar\@sGLS\@GLS}
```

Define the starred form:

```
1198 \newcommand*{\@sGLS}[1][]{\@GLS[hyper=false,#1]}
```

Defined the un-starred form. Need to determine if there is a final optional argument

```
1199 \newcommand*{\@GLS}[2][]{%
1200 \new@ifnextchar[\{\@GLS@{#1}{#2}\}{\@GLS@{#1}{#2}[]}}
```

\@GLS@ Read in the final optional argument:

```
1201 \def\@GLS@#1#2[#3]{%
1202 \glsdoifexists{#2}{\edef\@glo@type{\glsentrytype{#2}}%
```

Save options in \@gls@link@opts and label in \@gls@link@label

```
1203 \def\@gls@link@opts{#1}%
1204 \def\@gls@link@label{#2}%
```

Determine what the link text should be (this is stored in \@glo@text).

```
1205 \ifglsused{#2}{\protected\edef\@glo@text{%
1206 \csname gls@\@glo@type\endcsname
1207 \glsentrytext{#2}\glsentrydesc{#2}\glsentrysymbol{#2}{#3}}%
1208 \protected\edef\@glo@text{%
1209 \csname gls@\@glo@type\endcsname
1210 \glsentryfirst{#2}\glsentrydesc{#2}\glsentrysymbol{#2}{#3}}%
```

Call \@gls@link If footnote package option has been used, suppress hyperlink for first use.

```
1211 \ifglsused{#2}{%
1212 \gls@link[#1]{#2}{\MakeUppercase{\@glo@text}}%
1213 }{%
1214 \ifthenelse{\equal{\@glo@type}{\acronymtype}\and
1215 \boolean{glsacrfootnote}}{%
1216 \gls@link[#1,hyper=false]{#2}{\MakeUppercase{\@glo@text}}%
1217 }{%
1218 \gls@link[#1]{#2}{\MakeUppercase{\@glo@text}}%
1219 }%
1220 }%
```

Indicate that this entry has now been used

```
1221 \glsunset{#2}%
1222 }
```

\glspol behaves in the same way as \gls except it uses the plural form.

\glspol

```
1223 \newcommand*{\glspol}{\@ifstar\@sglspol\@glspol}
```

Define the starred form:

```
1224 \newcommand*{\@sglsp1}[1] [] {\@glspl[hyper=false,#1]}
```

Defined the un-starred form. Need to determine if there is a final optional argument

```
1225 \newcommand*{\@glspl}[2] [] {%
```

```
1226 \new@ifnextchar[{\@glspl@{#1}{#2}}{\@glspl@{#1}{#2}[]}]}
```

\@glspl@ Read in the final optional argument:

```
1227 \def\@glspl@#1#2[#3]{%
```

```
1228 \glsdoifexists[#2]{\edef\@glo@type{\glsentrytype{#2}}}%
```

Save options in \@gls@link@opts and label in \@gls@link@label

```
1229 \def\@gls@link@opts{#1}%
```

```
1230 \def\@gls@link@label{#2}%
```

Determine what the link text should be (this is stored in \@glo@text)

```
1231 \ifglsused{#2}{\protected@edef\@glo@text{%
```

```
1232 \csname gls@\@glo@type \display\endcsname
```

```
1233 {\glsentryplural{#2}}{\glsentrydescplural{#2}}{%
```

```
1234 \glsentrysymbolplural{#2}{#3}}{%
```

```
1235 \protected@edef\@glo@text{%
```

```
1236 \csname gls@\@glo@type \displayfirst\endcsname
```

```
1237 {\glsentryfirstplural{#2}}{\glsentrydescplural{#2}}{%
```

```
1238 \glsentrysymbolplural{#2}{#3}}{%
```

Call \@gls@link If footnote package option has been used, suppress hyperlink for first use.

```
1239 \ifglsused{#2}{%
```

```
1240   \@gls@link[#1]{#2}{\@glo@text}%
```

```
1241 }{%
```

```
1242   \ifthenelse{\equal{\@glo@type}{\acronymtype}\and
```

```
1243     \boolean{glsacrfootnote}}{%
```

```
1244     \@gls@link[#1,hyper=false]{#2}{\@glo@text}%
```

```
1245   }{%
```

```
1246     \@gls@link[#1]{#2}{\@glo@text}%
```

```
1247   }%
```

```
1248 }%
```

Indicate that this entry has now been used

```
1249 \glsunset{#2}%
```

```
1250 }
```

\Glsp1 behaves in the same way as \glspl, except that the first letter of the link text is converted to uppercase (as with \Gls, if the first letter has an accent, it will need to be grouped).

\Glsp1

```
1251 \newcommand*{\Glsp1}{\@ifstar\@sGlsp1\@Glsp1}
```

Define the starred form:

```
1252 \newcommand*{\@sGlsp1}[1] [] {\@Glsp1[hyper=false,#1]}
```

Defined the un-starred form. Need to determine if there is a final optional argument

```
1253 \newcommand*{\@Glsp1}[2] [] {%
```

```
1254 \new@ifnextchar[{\@Glsp1@{#1}{#2}}{\@Glsp1@{#1}{#2}[]}]}
```

\@Glspl@ Read in the final optional argument:

```
1255 \def\@Glspl@#1#2[#3]{%
1256 \glsdoifexists{#2}{\edef\@glo@type{\glsentrytype{#2}}}{%
    Save options in \@gls@link@opts and label in \@gls@link@label
1257 \def\@gls@link@opts{#1}%
1258 \def\@gls@link@label{#2}%

```

Determine what the link text should be (this is stored in \@glo@text). This needs to be expanded so that the \@glo@text can be passed to \xmakefirststuc.

```
1259 \ifglsused{#2}{\protected@edef\@glo@text{%
1260 \csname gls@\@glo@type @display\endcsname
1261 {\glsentryplural{#2}}{\glsentrydescplural{#2}}{%
1262 \glsentrysymbolplural{#2}{#3}}}{%
1263 \protected@edef\@glo@text{%
1264 \csname gls@\@glo@type @displayfirst\endcsname
1265 {\glsentryfirstplural{#2}}{\glsentrydescplural{#2}}{%
1266 \glsentrysymbolplural{#2}{#3}}}{%

```

Call \@gls@link If footnote package option has been used, suppress hyperlink for first use.

```
1267 \ifglsused{#2}{%
1268   \@gls@link[#1]{#2}{%
1269     \expandafter\makefirststuc\expandafter{\@glo@text}}{%
1270 }{%
1271   \ifthenelse{\equal{\@glo@type}{\acronymtype}\and
1272   \boolean{glsacrfootnote}}{%
1273     \@gls@link[#1,hyper=false]{#2}{%
1274       \expandafter\makefirststuc\expandafter{\@glo@text}}{%
1275 }{%
1276     \@gls@link[#1]{#2}{%
1277       \expandafter\makefirststuc\expandafter{\@glo@text}}{%
1278 }{%
1279 }{%

```

Indicate that this entry has now been used

```
1280 \glsunset{#2}%
1281 }
```

\GLSp1 behaves like \glspl except that all the link text is converted to uppercase.

\GLSp1

```
1282 \newcommand*{\GLSp1}{\@ifstar{\sGLSp1}{\GLSp1}}
```

Define the starred form:

```
1283 \newcommand*{\sGLSp1}[1][]{\GLSp1[hyper=false,#1]}
```

Defined the un-starred form. Need to determine if there is a final optional argument

```
1284 \newcommand*{\GLSp1}[2][]{%
1285 \new@ifnextchar[\{\GLSp1[#1]{#2}\}{\GLSp1[#1]{#2}}[]]{}
```

\@GLSp1 Read in the final optional argument:

```
1286 \def\@GLSp1@#1#2[#3]{%
1287 \glsdoifexists{#2}{\edef\@glo@type{\glsentrytype{#2}}}{%
```

Save options in `\@gls@link@opts` and label in `\@gls@link@label`

```
1288 \def\@gls@link@opts{\#1}%
1289 \def\@gls@link@label{\#2}%
```

Determine what the link text should be (this is stored in `\@glo@text`)

```
1290 \ifglsused{\#2}{\protected@edef\@glo@text{%
1291 \csname gls@\@glo@type \display\endcsname
1292 {\glsentryplural{\#2}}{\glsentrydescplural{\#2}}{%
1293 \glsentrysymbolplural{\#2}}{\#3}}}{%
1294 \protected@edef\@glo@text{%
1295 \csname gls@\@glo@type \displayfirst\endcsname
1296 {\glsentryfirstplural{\#2}}{\glsentrydescplural{\#2}}{%
1297 \glsentrysymbolplural{\#2}}{\#3}}}{%
```

Call `\@gls@link` If footnote package option has been used, suppress hyperlink for first use.

```
1298 \ifglsused{\#2}{%
1299 \@gls@link[\#1]{\#2}{\MakeUppercase{\@glo@text}}}{%
1300 }{%
1301 \ifthenelse{\equal{\@glo@type}{\acronymtype}\and
1302 \boolean{glsacrfootnote}}{%
1303 \@gls@link[\#1,hyper=false]{\#2}{\MakeUppercase{\@glo@text}}}{%
1304 }{%
1305 \@gls@link[\#1]{\#2}{\MakeUppercase{\@glo@text}}}{%
1306 }{%
1307 }}
```

Indicate that this entry has now been used

```
1308 \glsunset{\#2}%
1309 }
```

`\glsdisp` `\glsdisp[<options>]{<label>}{<text>}` This is like `\gls` except that the link text is provided. This differs from `\glslink` in that it uses `\glsdisplay` or `\glsdisplayfirst` and unsets the first use flag.

First determine if we are using the starred form:

```
1310 \newcommand*{\glsdisp}{\@ifstar\sglsdisp\glsdisp}
```

Define the starred form:

```
\@sgls
1311 \newcommand*{\@sglsdisp}[1][]{\@glsdisp[hyper=false,#1]}
```

Defined the un-starred form.

```
\@glsdisp
1312 \newcommand*{\@glsdisp}[3][]{%
1313 \glsdoifexists{\#2}{\edef\@glo@type{\glsentrytype{\#2}}}{%
Save options in \@gls@link@opts and label in \@gls@link@label
1314 \def\@gls@link@opts{\#1}%
1315 \def\@gls@link@label{\#2}%
Determine what the link text should be (this is stored in \@glo@text)
1316 \ifglsused{\#2}{%
1317 }{%
1318 \def\@glo@text{%
```

```

1319      \csname gls@\@glo@type @display\endcsname
1320      {#3}{\glsentrydesc{#2}}{\glsentrysymbol{#2}}{}%
1321  }%
1322 {%
1323   \def\@glo@text{%
1324     \csname gls@\@glo@type @displayfirst\endcsname
1325     {#3}{\glsentrydesc{#2}}{\glsentrysymbol{#2}}{}%
1326   }%

```

Call \gls@link. If footnote package option has been used, suppress hyperlink for first use.

```

1327   \ifglsused{#2}%
1328   {%
1329     \gls@link[#1]{#2}{\@glo@text}%
1330   }%
1331   {%
1332     \ifthenelse{\equal{\@glo@type}{\acronymtype}\and
1333       \boolean{glsacrfootnote}}{%
1334     {%
1335       \gls@link[#1,hyper=false]{#2}{\@glo@text}%
1336     }%
1337     {%
1338       \gls@link[#1]{#2}{\@glo@text}%
1339     }%
1340   }%

```

Indicate that this entry has now been used

```

1341   \glsunset{#2}%
1342 }

```

\glstext behaves like \gls except it always uses the value given by the text key and it doesn't mark the entry as used.

```
\glstext
1343 \newcommand*{\glstext}{\@ifstar\sglstext\glstext}

Define the starred form:
1344 \newcommand*{\sglstext}[1][]{\glstext[hyper=false,#1]}

Defined the un-starred form. Need to determine if there is a final optional argument
1345 \newcommand*{\glstext}[2][]{%
1346 \new@ifnextchar[\{\glstext@{#1}{#2}\}{\glstext@{#1}{#2}[]}}%

Read in the final optional argument:
1347 \def\glstext@#1#2[#3]{%
1348 \glsdoifexists{#2}{\edef\@glo@type{\glsentrytype{#2}}}{}

Determine what the link text should be (this is stored in \@glo@text)
1349 \protected\edef\@glo@text{\glsentrytext{#2}}%

Call \gls@link
1350 \gls@link[#1]{#2}{\@glo@text#3}%
1351 }%
1352 }

\GLStext behaves like \glstext except the text is converted to uppercase.
```

```
\GLStext
1353 \newcommand*{\GLStext}{\@ifstar\@sGLStext\@GLStext}

Define the starred form:
1354 \newcommand*{\@sGLStext}[1] []{\@GLStext[hyper=false,#1]}

Defined the un-starred form. Need to determine if there is a final optional argument
1355 \newcommand*{\@GLStext}[2] []{%
1356 \new@ifnextchar[{\@GLStext@{\#1}{\#2}}{\@GLStext@{\#1}{\#2}[]}}}

Read in the final optional argument:
1357 \def\@GLStext@#1#2[#3]{%
1358 \glsdoifexists{#2}{\edef\@glo@type{\glsentrytype{#2}}}{}

Determine what the link text should be (this is stored in \@glo@text)
1359 \protected@edef\@glo@text{\glsentrytext{#2}}{%

Call \@gls@link
1360 \@gls@link[#1]{#2}{\MakeUppercase{\@glo@text#3}}{%
1361 }{%
1362 }

\Glstext behaves like \glstext except that the first letter of the text is converted to uppercase.
```

```
\Glstext
1363 \newcommand*{\Glstext}{\@ifstar\@sGlstext\@Glstext}

Define the starred form:
1364 \newcommand*{\@sGlstext}[1] []{\@Glstext[hyper=false,#1]}

Defined the un-starred form. Need to determine if there is a final optional argument
1365 \newcommand*{\@Glstext}[2] []{%
1366 \new@ifnextchar[{\@Glstext@{\#1}{\#2}}{\@Glstext@{\#1}{\#2}[]}}}

Read in the final optional argument:
1367 \def\@Glstext@#1#2[#3]{%
1368 \glsdoifexists{#2}{\edef\@glo@type{\glsentrytype{#2}}}{}

Determine what the link text should be (this is stored in \@glo@text)
1369 \protected@edef\@glo@text{\glsentrytext{#2}}{%

Call \@gls@link
1370 \@gls@link[#1]{#2}{%
1371 \expandafter\makefirstuc\expandafter{\@glo@text}#3}{%
1372 }{%
1373 }

\glsfirst behaves like \gls except it always uses the value given by the first key and it doesn't mark the entry as used.
```

```
\glsfirst
1374 \newcommand*{\glsfirst}{\@ifstar\@sglsfirst\@glsfirst}

Define the starred form:
1375 \newcommand*{\@sglsfirst}[1] []{\@glsfirst[hyper=false,#1]}
```

Defined the un-starred form. Need to determine if there is a final optional argument

```
1376 \newcommand*{\glsfirst}[2] []{%
1377 \new@ifnextchar[{\@glsfirst@{\#1}{\#2}}{\@glsfirst@{\#1}{\#2}[]}}}
```

Read in the final optional argument:

```
1378 \def\@glsfirst@#1#2[#3]{%
1379 \glsdoifexists{\#2}{\edef\@glo@type{\glsentrytype{\#2}}}{}}
```

Determine what the link text should be (this is stored in `\@glo@text`)

```
1380 \protected@edef\@glo@text{\glsentryfirst{\#2}}{}
```

Call `\@gls@link`

```
1381 \gls@link[#1]{\#2}{\@glo@text#3}%
1382 }%
1383 }
```

`\Glsfirst` behaves like `\glsfirst` except it displays the first letter in uppercase.

`\Glsfirst`

```
1384 \newcommand*{\Glsfirst}{\@ifstar\@sGlsfirst\@Glsfirst}
```

Define the starred form:

```
1385 \newcommand*{\@sGlsfirst}[1] []{\@Glsfirst[hyper=false,#1]}
```

Defined the un-starred form. Need to determine if there is a final optional argument

```
1386 \newcommand*{\@Glsfirst}[2] []{%
1387 \new@ifnextchar[{\@Glsfirst@{\#1}{\#2}}{\@Glsfirst@{\#1}{\#2}[]}}}
```

Read in the final optional argument:

```
1388 \def\@Glsfirst@#1#2[#3]{%
1389 \glsdoifexists{\#2}{\edef\@glo@type{\glsentrytype{\#2}}}{}}
```

Determine what the link text should be (this is stored in `\@glo@text`)

```
1390 \protected@edef\@glo@text{\glsentryfirst{\#2}}{}
```

Call `\@gls@link`

```
1391 \gls@link[#1]{\#2}{%
1392 \expandafter\makefirstuc\expandafter{\@glo@text}#3}%
1393 }%
1394 }
```

`\GLSfirst` behaves like `\Glsfirst` except it displays the text in uppercase.

`\GLSfirst`

```
1395 \newcommand*{\GLSfirst}{\@ifstar\@sGLSfirst\@GLSfirst}
```

Define the starred form:

```
1396 \newcommand*{\@sGLSfirst}[1] []{\@GLSfirst[hyper=false,#1]}
```

Defined the un-starred form. Need to determine if there is a final optional argument

```
1397 \newcommand*{\@GLSfirst}[2] []{%
1398 \new@ifnextchar[{\@GLSfirst@{\#1}{\#2}}{\@GLSfirst@{\#1}{\#2}[]}}}
```

Read in the final optional argument:

```
1399 \def\@GLSfirst@#1#2[#3]{%
1400 \glsdoifexists{#2}{\edef\@glo@type{\glsentrytype{#2}}}{%
    Determine what the link text should be (this is stored in \@glo@text)
1401 \protected@edef\@glo@text{\glsentryfirst{#2}}{%
    Call \@gls@link
1402 \@gls@link[#1]{#2}{\MakeUppercase{\@glo@text#3}}{%
1403 }{%
1404 }
```

\glsplural behaves like \gls except it always uses the value given by the plural key and it doesn't mark the entry as used.

\glsplural

```
1405 \newcommand*{\glsplural}{\@ifstar\sglspplural\glsplural}
```

Define the starred form:

```
1406 \newcommand*{\sglspplural}[1][]{\glsplural[hyper=false,#1]}
```

Defined the un-starred form. Need to determine if there is a final optional argument

```
1407 \newcommand*{\glsplural}[2][]{%
1408 \new@ifnextchar[{ \glsplural@#1}{#2}]{\glsplural@#1}{#2}[]}}
```

Read in the final optional argument:

```
1409 \def\@glsplural@#1#2[#3]{%
1410 \glsdoifexists{#2}{\edef\@glo@type{\glsentrytype{#2}}}{%
```

Determine what the link text should be (this is stored in \@glo@text)

```
1411 \protected@edef\@glo@text{\glsentryplural{#2}}{%
```

Call \@gls@link

```
1412 \@gls@link[#1]{#2}{\@glo@text#3}{%
1413 }{%
1414 }
```

\Glsplural behaves like \glsplural except that the first letter is converted to uppercase.

\Glsplural

```
1415 \newcommand*{\Glsplural}{\@ifstar\sglspplural\Glsplural}
```

Define the starred form:

```
1416 \newcommand*{\sglspplural}[1][]{\Glsplural[hyper=false,#1]}
```

Defined the un-starred form. Need to determine if there is a final optional argument

```
1417 \newcommand*{\Glsplural}[2][]{%
1418 \new@ifnextchar[{ \Glsplural@#1}{#2}]{\Glsplural@#1}{#2}[]}}
```

Read in the final optional argument:

```
1419 \def\@Glsplural@#1#2[#3]{%
1420 \glsdoifexists{#2}{\edef\@glo@type{\glsentrytype{#2}}}{%
```

Determine what the link text should be (this is stored in \@glo@text)

```
1421 \protected@edef\@glo@text{\glsentryplural{#2}}{%
```

```

Call \@gls@link
1422 \@gls@link[#1]{#2}{%
1423   \expandafter\makefirstuc\expandafter{\@glo@text}#3}%
1424 }%
1425 }

\GLSplural behaves like \glsplural except that the text is converted to uppercase.

```

```
\GLSplural
1426 \newcommand*{\GLSplural}{\@ifstar@sGLSplural@\GLSplural}
```

Define the starred form:

```
1427 \newcommand*{\sGLSplural}[1][]{\@GLSplural[hyper=false,#1]}
```

Defined the un-starred form. Need to determine if there is a final optional argument

```
1428 \newcommand*{\@GLSplural}[2][]{%
1429 \new@ifnextchar[{\@GLSplural@{#1}{#2}}{\@GLSplural@{#1}{#2}[]}}
```

Read in the final optional argument:

```
1430 \def\@GLSplural@#1#2[#3]{%
1431 \glsdoifexists{#2}{\edef\@glo@type{\glsentrytype{#2}}}{}}
```

Determine what the link text should be (this is stored in \@glo@text)

```
1432 \protected@edef\@glo@text{\glsentryplural{#2}}%
```

Call \@gls@link

```
1433 \@gls@link[#1]{#2}{\MakeUppercase{\@glo@text#3}}%
1434 }%
1435 }
```

\glsfirstplural behaves like \gls except it always uses the value given by the firstplural key and it doesn't mark the entry as used.

```
\glsfirstplural
1436 \newcommand*{\glsfirstplural}{\@ifstar@sGlsfirstplural@\glsfirstplural}
```

Define the starred form:

```
1437 \newcommand*{\sGlsfirstplural}[1][]{\@glsfirstplural[hyper=false,#1]}
```

Defined the un-starred form. Need to determine if there is a final optional argument

```
1438 \newcommand*{\@glsfirstplural}[2][]{%
1439 \new@ifnextchar[{\@glsfirstplural@{#1}{#2}}{\@glsfirstplural@{#1}{#2}[]}}
```

Read in the final optional argument:

```
1440 \def\@glsfirstplural@#1#2[#3]{%
1441 \glsdoifexists{#2}{\edef\@glo@type{\glsentrytype{#2}}}{}}
```

Determine what the link text should be (this is stored in \@glo@text)

```
1442 \protected@edef\@glo@text{\glsentryfirstplural{#2}}%
```

Call \@gls@link

```
1443 \@gls@link[#1]{#2}{\@glo@text#3}%
1444 }%
1445 }
```

\Glsfirstplural behaves like \glsfirstplural except that the first letter is converted to uppercase.

```
\Glsfirstplural
1446 \newcommand*{\Glsfirstplural}{\@ifstar@sGlsfirstplural@\Glsfirstplural}
    Define the starred form:
1447 \newcommand*{\sGlsfirstplural}[1][]{\Glsfirstplural[hyper=false,#1]}
    Defined the un-starred form. Need to determine if there is a final optional argument
1448 \newcommand*{\@Glsfirstplural}[2][]{%
1449 \new@ifnextchar[\sGlsfirstplural@{#1}{#2}]{\Glsfirstplural@{#1}{#2}[]}}
    Read in the final optional argument:
1450 \def\@Glsfirstplural@#1#2[#3]{%
1451 \glsdoifexists{#2}{\edef\@glo@type{\glsentrytype{#2}}}{%
    Determine what the link text should be (this is stored in \@glo@text)
1452 \protected@edef\@glo@text{\glsentryfirstplural{#2}}{%
    Call \@gls@link
1453 \@gls@link[#1]{#2}{%
1454 \expandafter\makefirstuc\expandafter{\@glo@text}#3}{%
1455 }{%
1456 }
    \GLSfirstplural behaves like \glsfirstplural except that the link text is converted to uppercase.

\GLSfirstplural
1457 \newcommand*{\GLSfirstplural}{\@ifstar@sGLSfirstplural@\GLSfirstplural}
    Define the starred form:
1458 \newcommand*{\sGLSfirstplural}[1][]{\GLSfirstplural[hyper=false,#1]}
    Defined the un-starred form. Need to determine if there is a final optional argument
1459 \newcommand*{\@GLSfirstplural}[2][]{%
1460 \new@ifnextchar[\sGLSfirstplural@{#1}{#2}]{\GLSfirstplural@{#1}{#2}[]}}
    Read in the final optional argument:
1461 \def\@GLSfirstplural@#1#2[#3]{%
1462 \glsdoifexists{#2}{\edef\@glo@type{\glsentrytype{#2}}}{%
    Determine what the link text should be (this is stored in \@glo@text)
1463 \protected@edef\@glo@text{\glsentryfirstplural{#2}}{%
    Call \@gls@link
1464 \@gls@link[#1]{#2}{\MakeUppercase{\@glo@text#3}}{%
1465 }{%
1466 }
    \glsname behaves like \gls except it always uses the value given by the name key and it doesn't mark the entry as used.

\glsname
1467 \newcommand*{\glsname}{\@ifstar@sname@\glsname}
```

Define the starred form:

```
1468 \newcommand*{\@sglsname}[1] []{\@glsname[hyper=false,#1]}
```

Defined the un-starred form. Need to determine if there is a final optional argument

```
1469 \newcommand*{\@glsname}[2] []{%
```

```
1470 \new@ifnextchar[{\@glsname@{#1}{#2}}{\@glsname@{#1}{#2}[]}]}
```

Read in the final optional argument:

```
1471 \def\@glsname@#1#2[#3]{%
```

```
1472 \glsdoifexists[#2]{\edef\@glo@type{\glsentrytype{#2}}}%
```

Determine what the link text should be (this is stored in \@glo@text)

```
1473 \protected@edef\@glo@text{\glsentryname{#2}}%
```

Call \@gls@link

```
1474 \@gls@link[#1]{#2}{\@glo@text#3}%
```

```
1475 }%
```

```
1476 }
```

\Glsname behaves like \glsname except that the first letter is converted to uppercase.

\Glsname

```
1477 \newcommand*{\Glsname}{\@ifstar\@sGlsname\@Glsname}
```

Define the starred form:

```
1478 \newcommand*{\@sGlsname}[1] []{\@Glsname[hyper=false,#1]}
```

Defined the un-starred form. Need to determine if there is a final optional argument

```
1479 \newcommand*{\@Glsname}[2] []{%
```

```
1480 \new@ifnextchar[{\@Glsname@{#1}{#2}}{\@Glsname@{#1}{#2}[]}]}
```

Read in the final optional argument:

```
1481 \def\@Glsname@#1#2[#3]{%
```

```
1482 \glsdoifexists[#2]{\edef\@glo@type{\glsentrytype{#2}}}%
```

Determine what the link text should be (this is stored in \@glo@text)

```
1483 \protected@edef\@glo@text{\glsentryname{#2}}%
```

Call \@gls@link

```
1484 \@gls@link[#1]{#2}{%
```

```
1485 \expandafter\makefirstuc\expandafter{\@glo@text}#3}%
```

```
1486 }%
```

```
1487 }
```

\GLSname behaves like \glsname except that the link text is converted to uppercase.

\GLSname

```
1488 \newcommand*{\GLSname}{\@ifstar\@sGLSname\@GLSname}
```

Define the starred form:

```
1489 \newcommand*{\@sGLSname}[1] []{\@GLSname[hyper=false,#1]}
```

Defined the un-starred form. Need to determine if there is a final optional argument

```
1490 \newcommand*{\@GLSname}[2] []{%
1491 \new@ifnextchar[{\@GLSname@{\#1}{\#2}}{\@GLSname@{\#1}{\#2}[]}}}
```

Read in the final optional argument:

```
1492 \def\@GLSname@#1#2[#3]{%
1493 \glsdoifexists{#2}{\edef\@glo@type{\glsentrytype{#2}}}{}}
```

Determine what the link text should be (this is stored in `\@glo@text`)

```
1494 \protected@edef\@glo@text{\glsentryname{#2}}{}
```

Call `\@gls@link`

```
1495 \gls@link[#1]{#2}{\MakeUppercase{\@glo@text#3}}{%
1496 }{%
1497 }
```

`\glsdesc` behaves like `\gls` except it always uses the value given by the `description` key and it doesn't mark the entry as used.

`\glsdesc`

```
1498 \newcommand*{\glsdesc}{\@ifstar{\sglsdesc}{\glsdesc}}
```

Define the starred form:

```
1499 \newcommand*{\@sglsdesc}[1] []{\@glsdesc[hyper=false,#1]}
```

Defined the un-starred form. Need to determine if there is a final optional argument

```
1500 \newcommand*{\@glsdesc}[2] []{%
1501 \new@ifnextchar[{\@glsdesc@{\#1}{\#2}}{\@glsdesc@{\#1}{\#2}[]}}}
```

Read in the final optional argument:

```
1502 \def\@glsdesc@#1#2[#3]{%
1503 \glsdoifexists{#2}{\edef\@glo@type{\glsentrytype{#2}}}{}}
```

Determine what the link text should be (this is stored in `\@glo@text`)

```
1504 \protected@edef\@glo@text{\glsentrydesc{#2}}{}
```

Call `\@gls@link`

```
1505 \gls@link[#1]{#2}{\@glo@text#3}{%
1506 }{%
1507 }
```

`\Glsdesc` behaves like `\glsdesc` except that the first letter is converted to uppercase.

`\Glsdesc`

```
1508 \newcommand*{\Glsdesc}{\@ifstar{\sGlsdesc}{\Glsdesc}}
```

Define the starred form:

```
1509 \newcommand*{\@sGlsdesc}[1] []{\@Glsdesc[hyper=false,#1]}
```

Defined the un-starred form. Need to determine if there is a final optional argument

```
1510 \newcommand*{\@Glsdesc}[2] []{%
1511 \new@ifnextchar[{\@Glsdesc@{\#1}{\#2}}{\@Glsdesc@{\#1}{\#2}[]}}}
```

Read in the final optional argument:

```
1512 \def\@Glsdesc@#1#2[#3]{%
1513 \glsdoifexists{#2}{\edef\@glo@type{\glsentrytype{#2}}}{%
Determine what the link text should be (this is stored in \@glo@text)
1514 \protected@edef\@glo@text{\glsentrydesc{#2}}{%
Call \@gls@link
1515 \@gls@link[#1]{#2}{%
1516 \expandafter\makefirstuc\expandafter{\@glo@text}#3}{%
1517 }{%
1518 }
\GLSdesc behaves like \glsdesc except that the link text is converted to uppercase.
```

\GLSdesc

```
1519 \newcommand*{\GLSdesc}{\@ifstar@sGLSdesc@\GLSdesc}
```

Define the starred form:

```
1520 \newcommand*{\sGLSdesc}[1][]{\@GLSdesc[hyper=false,#1]}
Defined the un-starred form. Need to determine if there is a final optional argument
```

```
1521 \newcommand*{\@GLSdesc}[2][]{%
1522 \new@ifnextchar[\{\@GLSdesc@{#1}{#2}\}{\@GLSdesc@{#1}{#2}[]}{}}
```

Read in the final optional argument:

```
1523 \def\@GLSdesc@#1#2[#3]{%
1524 \glsdoifexists{#2}{\edef\@glo@type{\glsentrytype{#2}}}{%
Determine what the link text should be (this is stored in \@glo@text)
1525 \protected@edef\@glo@text{\glsentrydesc{#2}}{%
Call \@gls@link
1526 \@gls@link[#1]{#2}{\MakeUppercase{\@glo@text#3}}{%
1527 }{%
1528 }
\glsdescplural behaves like \gls except it always uses the value given by the descriptionplural key and it doesn't mark the entry as used.
```

\glsdescplural

```
1529 \newcommand*{\glsdescplural}{\@ifstar@sdescplural@\glsdescplural}
```

Define the starred form:

```
1530 \newcommand*{\sdescplural}[1][]{\@glsdescplural[hyper=false,#1]}
Defined the un-starred form. Need to determine if there is a final optional argument
```

```
1531 \newcommand*{\@glsdescplural}[2][]{%
1532 \new@ifnextchar[\{\@glsdescplural@{#1}{#2}\}{\@glsdescplural@{#1}{#2}[]}{}}
```

Read in the final optional argument:

```
1533 \def\@glsdescplural@#1#2[#3]{%
1534 \glsdoifexists{#2}{\edef\@glo@type{\glsentrytype{#2}}}{%
Determine what the link text should be (this is stored in \@glo@text)
1535 \protected@edef\@glo@text{\glsentrydescplural{#2}}{}}
```

```

Call \@gls@link
1536 \@gls@link[#1]{#2}{\@glo@text#3}%
1537 }%
1538 }

\Glsdescplural behaves like \glsdescplural except that the first letter is
converted to uppercase.

```

```
\Glsdescplural
1539 \newcommand*{\Glsdescplural}{\@ifstar@sGlsdescplural\Glsdescplural}
```

Define the starred form:

```
1540 \newcommand*{\sGlsdescplural}[1][]{\Glsdescplural[hyper=false,#1]}
Defined the un-starred form. Need to determine if there is a final optional argument
1541 \newcommand*{\Glsdescplural}[2][]{%
1542 \new@ifnextchar[\sGlsdescplural@{#1}{#2}]{\Glsdescplural@{#1}{#2}[]}}
```

Read in the final optional argument:

```
1543 \def\Glsdescplural@#1#2[#3]{%
1544 \glsdoifexists{#2}{\edef\glo@type{\glsentrytype{#2}}}}
Determine what the link text should be (this is stored in \glo@text)
1545 \protected@edef\glo@text{\glsentrydescplural{#2}}%
```

Call \@gls@link

```
1546 \@gls@link[#1]{#2}{%
1547 \expandafter\makefirstuc\expandafter{\glo@text}#3}%
1548 }%
1549 }

\GLSdescplural behaves like \glsdescplural except that the link text is
converted to uppercase.
```

```
\GLSdescplural
1550 \newcommand*{\GLSdescplural}{\@ifstar@sGLSdescplural\GLSdescplural}
```

Define the starred form:

```
1551 \newcommand*{\sGLSdescplural}[1][]{\GLSdescplural[hyper=false,#1]}
Defined the un-starred form. Need to determine if there is a final optional argument
1552 \newcommand*{\GLSdescplural}[2][]{%
1553 \new@ifnextchar[\sGLSdescplural@{#1}{#2}]{\GLSdescplural@{#1}{#2}[]}}
```

Read in the final optional argument:

```
1554 \def\GLSdescplural@#1#2[#3]{%
1555 \glsdoifexists{#2}{\edef\glo@type{\glsentrytype{#2}}}}
Determine what the link text should be (this is stored in \glo@text)
1556 \protected@edef\glo@text{\glsentrydescplural{#2}}%
```

Call \@gls@link

```
1557 \@gls@link[#1]{#2}{\MakeUppercase{\glo@text}#3}%
1558 }%
1559 }
```

`\glssymbol` behaves like `\gls` except it always uses the value given by the `symbol` key and it doesn't mark the entry as used.

```
\glssymbol
1560 \newcommand*{\glssymbol}{\ifstar\sglssymbol\glssymbol}

    Define the starred form:
1561 \newcommand*{\sglssymbol}[1][]{\glssymbol[hyper=false,#1]}

    Defined the un-starred form. Need to determine if there is a final optional argument
1562 \newcommand*{\@glssymbol}[2][]{%
1563 \new@ifnextchar[\{\@glssymbol[#1]{#2}\}{\@glssymbol[#1]{#2}[]}]}

    Read in the final optional argument:
1564 \def\@glssymbol[#1#2[#3]{%
1565 \glsdoifexists[#2]{\edef\glo@type{\glsentrytype[#2]}}}

    Determine what the link text should be (this is stored in \glo@text)
1566 \protected\edef\glo@text{\glsentrysymbol[#2]}%

    Call \gls@link
1567 \gls@link[#1]{#2}{\glo@text#3}%
1568 }%
1569 }

    \Glssymbol behaves like \glssymbol except that the first letter is converted to uppercase.
```

```
\Glssymbol
1570 \newcommand*{\Glssymbol}{\ifstar\sGlssymbol\Glssymbol}

    Define the starred form:
1571 \newcommand*{\sGlssymbol}[1][]{\Glssymbol[hyper=false,#1]}

    Defined the un-starred form. Need to determine if there is a final optional argument
1572 \newcommand*{\@Glssymbol}[2][]{%
1573 \new@ifnextchar[\{\@Glssymbol[#1]{#2}\}{\@Glssymbol[#1]{#2}[]}]}

    Read in the final optional argument:
1574 \def\@Glssymbol[#1#2[#3]{%
1575 \glsdoifexists[#2]{\edef\glo@type{\glsentrytype[#2]}}}

    Determine what the link text should be (this is stored in \glo@text)
1576 \protected\edef\glo@text{\glsentrysymbol[#2]}%

    Call \gls@link
1577 \gls@link[#1]{#2}{%
1578   \expandafter\makefirstuc\expandafter{\glo@text}#3}%
1579 }%
1580 }

    \GLSsymbol behaves like \glssymbol except that the link text is converted to uppercase.
```

```
\GLSsymbol
1581 \newcommand*{\GLSsymbol}{\ifstar\sGLSsymbol\GLSsymbol}
```

Define the starred form:

```
1582 \newcommand*{\@GLSsymbol}[1][]{\@GLSsymbol[hyper=false,#1]}
```

Defined the un-starred form. Need to determine if there is a final optional argument

```
1583 \newcommand*{\@GLSsymbol}[2][]{%
```

```
1584 \new@ifnextchar[{\@GLSsymbol@{#1}{#2}}{\@GLSsymbol@{#1}{#2}[]}]}
```

Read in the final optional argument:

```
1585 \def\@GLSsymbol@#1#2[#3]{%
```

```
1586 \glsdoifexists{#2}{\edef\@glo@type{\glsentrytype{#2}}}%
```

Determine what the link text should be (this is stored in \@glo@text)

```
1587 \protected@edef\@glo@text{\glsentrysymbol{#2}}%
```

Call \@gls@link

```
1588 \@gls@link[#1]{#2}{\MakeUppercase{\@glo@text#3}}%
```

```
1589 }%
```

```
1590 }
```

\glssymbolplural behaves like \gls except it always uses the value given by the symbolplural key and it doesn't mark the entry as used.

\glssymbolplural

```
1591 \newcommand*{\glssymbolplural}{\@ifstar\sglssymbolplural\@glssymbolplural}
```

Define the starred form:

```
1592 \newcommand*{\@sglssymbolplural}[1][]{\@glssymbolplural[hyper=false,#1]}
```

Defined the un-starred form. Need to determine if there is a final optional argument

```
1593 \newcommand*{\@glssymbolplural}[2][]{%
```

```
1594 \new@ifnextchar[{\@glssymbolplural@{#1}{#2}}{\@glssymbolplural@{#1}{#2}[]}]}
```

Read in the final optional argument:

```
1595 \def\@glssymbolplural@#1#2[#3]{%
```

```
1596 \glsdoifexists{#2}{\edef\@glo@type{\glsentrytype{#2}}}%
```

Determine what the link text should be (this is stored in \@glo@text)

```
1597 \protected@edef\@glo@text{\glsentrysymbolplural{#2}}%
```

Call \@gls@link

```
1598 \@gls@link[#1]{#2}{\@glo@text#3}%
```

```
1599 }%
```

```
1600 }
```

\Glssymbolplural behaves like \glssymbolplural except that the first letter is converted to uppercase.

\Glssymbolplural

```
1601 \newcommand*{\Glssymbolplural}{\@ifstar\@sGlssymbolplural\@Glssymbolplural}
```

Define the starred form:

```
1602 \newcommand*{\@sGlssymbolplural}[1][]{\@Glssymbolplural[hyper=false,#1]}
```

Defined the un-starred form. Need to determine if there is a final optional argument

```
1603 \newcommand*{\@Glssymbolplural}[2][]{%
```

```
1604 \new@ifnextchar[{\@Glssymbolplural@{#1}{#2}}{\@Glssymbolplural@{#1}{#2}[]}]}
```

Read in the final optional argument:

```
1605 \def\@Glsymbolplural@#1#2[#3]{%
1606 \glsdoifexists{#2}{\edef\@glo@type{\glsentrytype{#2}}}{%
1607 \protected@edef\@glo@text{\glsentrysymbolplural{#2}}}{%
1608 \Call{\gls@link}{#1}{#2}{%
1609   \expandafter\makefirstuc\expandafter{\@glo@text}{#3}}}{%
1610 }{%
1611 }{%
1612 \GLSsymbolplural behaves like \glssymbolplural except that the link text
1613 is converted to uppercase.
```

\GLSsymbolplural

```
1612 \newcommand*{\GLSsymbolplural}{\@ifstar{\sGLSsymbolplural}{\GLSsymbolplural}}
```

Define the starred form:

```
1613 \newcommand*{\sGLSsymbolplural}[1]{\GLSsymbolplural[hyper=false,#1]}{%
1614 \newcommand*{\GLSsymbolplural}[2]{\GLSsymbolplural[hyper=false,#1]{#2}}{%
1615 \new@ifnextchar[\{\GLSsymbolplural@{#1}{#2}\}{\GLSsymbolplural@{#1}{#2}}]{}}
```

Read in the final optional argument:

```
1616 \def\@GLSsymbolplural@#1#2[#3]{%
1617 \glsdoifexists{#2}{\edef\@glo@type{\glsentrytype{#2}}}{%
1618 \protected@edef\@glo@text{\glsentrysymbolplural{#2}}}{%
1619 \Call{\gls@link}{#1}{#2}{\MakeUppercase{\@glo@text}{#3}}}{%
1620 }{%
1621 }}
```

5.10.2 Displaying entry details without adding information to the glossary

These commands merely display entry information without adding entries in the associated file or having hyperlinks.

Get the entry name (as specified by the `name` key when the entry was defined). The argument is the label associated with the entry. Note that unless you used `name=false` in the `sanitize` package option you may get unexpected results if the `name` key contains any commands.

\glsentryname

```
1622 \newcommand*{\glsentryname}[1]{\csname glo@#1@name\endcsname}
```

\Glsentryname

```
1623 \newcommand*{\Glsentryname}[1]{%
1624 \protected@edef\@glo@text{\csname glo@#1@name\endcsname}{%
1625 \expandafter\makefirstuc\expandafter{\@glo@text}}}
```

Get the entry description (as specified by the `description` when the entry was defined). The argument is the label associated with the entry. Note that unless you used `description=false` in the `sanitize` package option you may get unexpected results if the `description` key contained any commands.

```
\glsentrydesc
1626 \newcommand*{\glsentrydesc}[1]{\csname glo@#1@desc\endcsname}

\Glsentrydesc
1627 \newcommand*{\Glsentrydesc}[1]{%
1628 \protected@edef{\glo@text{\csname glo@#1@desc\endcsname}}{%
1629 \expandafter\makefirstuc\expandafter{\glo@text}}}
```

Plural form:

```
\glsentrydescplural
1630 \newcommand*{\glsentrydescplural}[1]{%
1631 \csname glo@#1@descplural\endcsname}

\Glsentrydescplural
1632 \newcommand*{\Glsentrydescplural}[1]{%
1633 \protected@edef{\glo@text{\csname glo@#1@descplural\endcsname}}{%
1634 \expandafter\makefirstuc\expandafter{\glo@text}}}
```

Get the entry text, as specified by the `text` key when the entry was defined. The argument is the label associated with the entry:

```
\glsentrytext
1635 \newcommand*{\glsentrytext}[1]{\csname glo@#1@text\endcsname}

\Glsentrytext
1636 \newcommand*{\Glsentrytext}[1]{%
1637 \protected@edef{\glo@text{\csname glo@#1@text\endcsname}}{%
1638 \expandafter\makefirstuc\expandafter{\glo@text}}}
```

Get the plural form:

```
\glsentryplural
1639 \newcommand*{\glsentryplural}[1]{\csname glo@#1@plural\endcsname}

\Glsentryplural
1640 \newcommand*{\Glsentryplural}[1]{%
1641 \protected@edef{\glo@text{\csname glo@#1@plural\endcsname}}{%
1642 \expandafter\makefirstuc\expandafter{\glo@text}}}
```

Get the symbol associated with this entry. The argument is the label associated with the entry. Note that unless you used `symbol=false` in the `sanitize` package option you may get unexpected results if the `symbol` key contained any commands.

```
\glsentrysymbol
1643 \newcommand*{\glsentrysymbol}[1]{\csname glo@#1@symbol\endcsname}
```

```
\Glsentrysymbol
1644 \newcommand*{\Glsentrysymbol}[1]{%
1645 \protected@edef{\glo@text{\csname glo@\#1@symbol\endcsname}}{%
1646 \expandafter\makefirstuc\expandafter{\glo@text}}
```

Plural form:

```
\glsentrysymbolplural
1647 \newcommand*{\glsentrysymbolplural}[1]{%
1648 \csname glo@\#1@symbolplural\endcsname}
```

```
\Glsentrysymbolplural
1649 \newcommand*{\Glsentrysymbolplural}[1]{%
1650 \protected@edef{\glo@text{\csname glo@\#1@symbolplural\endcsname}}{%
1651 \expandafter\makefirstuc\expandafter{\glo@text}}}
```

Get the entry text to be used when the entry is first used in the document (as specified by the `first` key when the entry was defined).

```
\glsentryfirst
1652 \newcommand*{\glsentryfirst}[1]{\csname glo@\#1@first\endcsname}
```

```
\Glsentryfirst
1653 \newcommand*{\Glsentryfirst}[1]{%
1654 \protected@edef{\glo@text{\csname glo@\#1@first\endcsname}}{%
1655 \expandafter\makefirstuc\expandafter{\glo@text}}}
```

Get the plural form (as specified by the `firstplural` key when the entry was defined).

```
\glsentryfirstplural
1656 \newcommand*{\glsentryfirstplural}[1]{%
1657 \csname glo@\#1@firstpl\endcsname}
```

```
\Glsentryfirstplural
1658 \newcommand*{\Glsentryfirstplural}[1]{%
1659 \protected@edef{\glo@text{\csname glo@\#1@firstpl\endcsname}}{%
1660 \expandafter\makefirstuc\expandafter{\glo@text}}}
```

Display the glossary type with which this entry is associated (as specified by the `type` key used when the entry was defined)

```
\glsentrytype
1661 \newcommand*{\glsentrytype}[1]{\csname glo@\#1@type\endcsname}
```

Display the sort text used for this entry. Note that the `sort` key is sanitize, so unexpected results may occur if the `sort` key contained commands.

```
\glsentrysort
1662 \newcommand*{\glsentrysort}[1]{\csname glo@\#1@sort\endcsname}
```

- \glshyperlink Provide a hyperlink to a glossary entry without adding information to the glossary file. The entry needs to be added using a command like \glslink or \glsadd to ensure that the target is defined. The first (optional) argument specifies the link text. The entry name is used by default. The second argument is the entry label.

```
1663 \newcommand*{\glshyperlink}[2]{\glsentryname{\glo@label}}{%
1664 \def\glo@label{\#2}%
1665 \glslink{\glo:#2}{\#1}}
```

5.11 Adding an entry to the glossary without generating text

The following keys are provided for \glsadd and \glsaddall:

```
1666 \define@key{glossadd}{counter}{\def\glo@counter{\#1}}%
1667 \define@key{glossadd}{format}{\def\glo@format{\#1}}
```

This key is only used by \glsaddall:

```
1668 \define@key{glossadd}{types}{\def\glo@type{\#1}}%
\glsadd[<options>]{<label>}
```

Add a term to the glossary without generating any link text. The optional argument indicates which counter to use, and how to format it (using a key-value list) the second argument is the entry label. Note that *<options>* only has two keys: counter and format (the types key will be ignored).

```
\glsadd
1669 \newcommand*{\glsadd}[2][]{%
1670 \glsdoifexists{\#2}{%
1671 \def\glsnumberformat{\glsnumberformat}%
1672 \edef\gls@counter{\csname glo@\#2@counter\endcsname}%
1673 \setkeys{glossadd}{\#1}%
1674 \edef\theglsentrycounter{\expandafter\noexpand
1675 \csname the\gls@counter\endcsname}%
1676 \odot@wrglossary{\#2}%
1677 }}
```

\glsaddall[<glossary list>]

Add all terms defined for the listed glossaries (without displaying any text). If types key is omitted, apply to all glossary types.

```
\glsaddall
1678 \newcommand*{\glsaddall}[1][]{%
1679 \edef\glo@type{\glo@types}%
1680 \setkeys{glossadd}{\#1}%
1681 \forallglsentries[\glo@type]{\glo@entry}{%
1682 \glsadd{\#1}{\glo@entry}}%
1683 }
```

5.12 Creating associated files

The `\writeist` command creates the associated customized `.ist makeindex` style file. While defining this command, some characters have their catcodes temporarily changed to ensure they get written to the `.ist` file correctly. The `makeindex` actual character (usually `@`) is redefined to be a `?`, to allow internal commands to be written to the glossary file output file.

The special characters are stored in `\@gls@actualchar`, `\@gls@encapchar`, `\@gls@levelchar` and `\@gls@quotechar` to make them easier to use later, but don't change these values, because the characters are encoded in the command definitions that are used to escape the special characters (which means that the user no longer needs to worry about `makeindex` special characters).

The symbols and numbers label for group headings are hardwired into the `.ist` file as `glossymbols` and `glsnumbers`, the group titles can be translated (so that `\glossymbolsgroupname` replaces `glossymbols` and `\glsnumbersgroupname` replaces `glsnumbers`) using the command `\glsgetgroupname` which is defined in `glossary-hypernav`. This is done to prevent any problem characters in `\glossymbolsgroupname` and `\glsnumbersgroupname` from breaking hyperlinks.

```
\glsopenbrace Define \glsopenbrace to make it easier to write an opening brace to a file.  
1684 \edef\glsopenbrace{\expandafter\gobble\string\{}  
  
\glsclosebrace Define \glsclosebrace to make it easier to write an opening brace to a file.  
1685 \edef\glsclosebrace{\expandafter\gobble\string\}}  
  
\glsquote Define command that makes it easier to write quote marks to a file in the event  
that the double quote character has been made active.  
1686 \edef\glsquote#1{\string"#1\string"}  
  
\glsfirstletter Define the first letter to come after the digits 0,...,9. Only required for xindy.  
1687 \ifglsxindy  
1688   \newcommand*{\glsfirstletter}{A}  
1689 \fi  
  
sSetXdyFirstLetterAfterDigits Sets the first letter to come after the digits 0,...,9.  
1690 \ifglsxindy  
1691   \newcommand*{\GlsSetXdyFirstLetterAfterDigits}[1]{%  
1692     \renewcommand*{\glsfirstletter}{#1}  
1693   }  
1694   \newcommand*{\GlsSetXdyFirstLetterAfterDigits}[1]{%  
1695     \glsnoxindywarning{\GlsSetXdyFirstLetterAfterDigits}  
1696 }  
  
\glsminrange Define the minimum number of successive location references to merge into a  
range.  
1697 \newcommand*{\glsminrange}{2}  
  
\GlsSetXdyMinRangeLength Set the minimum range length. The value must either be none or a positive integer.  
The glossaries package doesn't check if the argument is valid, that is left to xindy.  
1698 \ifglsxindy  
1699   \newcommand*{\GlsSetXdyMinRangeLength}[1]{%  
1700     \renewcommand*{\glsminrange}{#1}}
```

```

1701 \else
1702   \newcommand*\{GlsSetXdyMinRangeLength}[1]{%
1703     \glsnoxindywarning\GlsSetXdyMinRangeLength}
1704 \fi

\writeist
1705 \newwrite\istfile
1706 \ifglsxindy
  Code to use if xindy is required.
1707 \def\writeist{%
  Open the style file
1708   \openout\istfile=\istfilename
  Write header comment at the start of the file
1709   \write\istfile{;; xindy style file created by the glossaries
1710     package}%
1711   \write\istfile{;; for document '\jobname' on
1712     \the\year-\the\month-\the\day}%

  Specify the required styles
1713   \write\istfile{^^J; required styles^^J}
1714   \@for\@xdystyle:=\@xdyrequiredstyles\do{%
1715     \ifx\@xdystyle\@empty
1716     \else
1717       \protected\write\istfile{}{(require
1718         "string"\@xdystyle.xdy|string")}%
1719     \fi
1720   }%
  List the allowed attributes (possible values used by the format key)
1721   \write\istfile{^^J%
1722     ; list of allowed attributes (number formats)^^J}%
1723   \write\istfile{((define-attributes ((\@xdyattributes)))})%}

  Define any additional alphabets
1724   \write\istfile{^^J; user defined alphabets^^J}%
1725   \write\istfile{\@xdyuseralphabets}%

  Define location classes.
1726   \write\istfile{^^J; location class definitions^^J}%
  Lower case Roman numerals (i, ii, ...). In the event that \roman has been redefined to produce a fancy form of roman numerals, attempt to work out how it will be written to the output file.
1727   \protected\edef\@gls@roman{\@roman{0}string"
1728     string"roman-numbers-lowercase/string" :sep \string"}}%
1729   \onelevel@sanitize@gls@roman
1730   \edef\@tmp{\string" \string"roman-numbers-lowercase\string"
1731     :sep \string"}%
1732   \onelevel@sanitize@tmp
1733   \ifx@\tmp@gls@roman
1734     \write\istfile{((define-location-class
1735       string"roman-page-numbers/string"^^J\space\space\space
1736       (\string"roman-numbers-lowercase\string")
1737       :min-range-length \@glsminrange))}%

```

```

1738     \else
1739         \write\istfile{(\define-location-class
1740             \string"roman-page-numbers\string"^^J\space\space\space
1741             (:sep "\@gls@roman")
1742             :min-range-length \@glsminrange)}%
1743     \fi
1744     Upper case Roman numerals (I, II, ...)
1745     \write\istfile{(\define-location-class
1746         \string"Roman-page-numbers\string"^^J\space\space\space
1747         (\string"roman-numbers-uppercase\string")
1748         :min-range-length \@glsminrange)}%
1749     Arabic numbers (1, 2, ...)
1750     \write\istfile{(\define-location-class
1751         \string"arabic-page-numbers\string"^^J\space\space\space
1752         (\string"arabic-numbers\string")
1753         :min-range-length \@glsminrange)}%
1754     Lower case alphabetical locations (a, b, ...)
1755     \write\istfile{(\define-location-class
1756         \string"alpha-page-numbers\string"^^J\space\space\space
1757         (\string"alpha\string")
1758         :min-range-length \@glsminrange)}%
1759     Upper case alphabetical locations (A, B, ...)
1760     \write\istfile{(\define-location-class
1761         \string"Alpha-page-numbers\string"^^J\space\space\space
1762         (\string"ALPHA\string")
1763         :sep \string"\@glsAlphacompositor\string"
1764         \string"arabic-numbers\string")
1765         :min-range-length \@glsminrange)}%
1766     Appendix style locations (e.g. A-1, A-2, ..., B-1, B-2, ...). The separator is given
1767     by \@glsAlphacompositor.
1768     \write\istfile{(\define-location-class
1769         \string"Appendix-page-numbers\string"^^J\space\space\space
1770         (\string"ALPHA\string"
1771         :sep \string"\@glsAlphacompositor\string"
1772         \string"arabic-numbers\string")
1773         :min-range-length \@glsminrange)}%
1774     Section number style locations (e.g. 1.1, 1.2, ...). The compositor is given by
1775     \glscompositor.
1776     \write\istfile{(\define-location-class
1777         \string"arabic-section-numbers\string"^^J\space\space\space
1778         (\string"arabic-numbers\string"
1779         :sep \string"\glscompositor\string"
1780         \string"arabic-numbers\string")
1781         :min-range-length \@glsminrange)}%
1782     User defined location classes.
1783     \write\istfile{^^J; user defined location classes}%
1784     \write\istfile{\@xdyuserlocationdefs}%
1785     Cross-reference class. (The unverified option is used as the cross-references are sup-
1786     plied using the list of labels along with the optional argument for \glsseeformat
1787     which xindy won't recognise.)
1788     \write\istfile{^^J; define cross-reference class^^J}%

```

```
1775      \write\listfile{({define-crossref-class \string"see\string"
1776          :unverified })}%
```

Define how cross-references should be displayed. This adds an empty set of braces after the cross-referencing information allowing for the final argument of `\glsseeformat` which gets ignored. (When using `makeindex` this final argument contains the location information which is not required.)

```
1777      \write\listfile{({markup-crossref-list
1778          :class \string"see\string"^^J\space\space\space
1779          :open \string"\string\glsseeformat\string"
1780          :close \string"{}\string"})}%
```

List the order to sort the classes.

```
1781      \write\listfile{^^J; define the order of the location classes}%
1782      \write\listfile{({define-location-class-order
1783          (\@xdylocationclassorder)})}%
```

Specify what to write to the start and end of the glossary file.

```
1784      \write\listfile{^^J; define the glossary markup^^J}%
1785      \write\listfile{({markup-index^^J\space\space\space
1786          :open \string"\string
1787          \glossarysection[\string\glossarytoctitle]{\string
1788          \glossarytitle}\string\glossarypreamble\string^n\string\begin
1789          {theglossary}\string\glossaryheader\string^n\string" ^^J\space
1790          \space\space:close \string"\expandafter\@gobble
1791          \string%\string^n\string
1792          \end{theglossary}\string\glossarypostamble
1793          \string^n\string" ^^J\space\space\space
1794          :tree})}%
```

Specify what to put between letter groups

```
1795      \write\listfile{({markup-letter-group-list
1796          :sep \string"\string\glsgroupskip\string^n\string"})}%
```

Specify what to put between entries

```
1797      \write\listfile{({markup-indexentry
1798          :open \string"\string\relax \string\glsresetentrylist
1799          \string^n\string"})}%
```

Specify how to format entries

```
1800      \write\listfile{({markup-locclass-list :open
1801          \string"\glsopenbrace\string\glossaryentrynumbers
1802          \glsopenbrace\string\relax\space \string"^^J\space\space\space
1803          :sep \string", \string"
1804          :close \string"\glsclosebrace\glsclosebrace\string"})}%
```

Specify how to separate location numbers

```
1805      \write\listfile{({markup-locref-list
1806          :sep \string"\string\delimN\space\string"})}%
```

Specify how to indicate location ranges

```
1807      \write\listfile{({markup-range
1808          :sep \string"\string\delimR\space\string"})}%
```

Specify 2-page and 3-page suffixes, if defined. First, the values must be sanitized to write them explicitly.

```
1809      \@onellevel@sanitize\gls@suffixF
1810      \@onellevel@sanitize\gls@suffixFF
```

```

1811     \ifx\gls@suffixF\@empty
1812     \else
1813         \write\istfile{(\markup-range
1814             :close "\gls@suffixF" :length 1 :ignore-end)}%
1815     \fi
1816     \ifx\gls@suffixFF\@empty
1817     \else
1818         \write\istfile{(\markup-range
1819             :close "\gls@suffixFF" :length 2 :ignore-end)}%
1820     \fi

Specify how to format locations.

1821     \write\istfile{^\J; define format to use for locations^\J}%
1822     \write\istfile{\@xdylocref}%

Specify how to separate letter groups.

1823     \write\istfile{^\J; define letter group list format^\J}%
1824     \write\istfile{(\markup-letter-group-list
1825         :sep \string"\string\glsgroupskip\string~n\string")}%

Define letter group headings.

1826     \write\istfile{^\J; letter group headings^\J}%
1827     \write\istfile{(\markup-letter-group
1828         :open-head \string"\string\glsgroupheading
1829         \glsopenbrace\string"^\J\space\space\space
1830         :close-head \string"\glsclosebrace\string")}%

Define additional letter groups.

1831     \write\istfile{^\J; additional letter groups^\J}%
1832     \write\istfile{\@xdylettergroups}%

Define additional sort rules

1833     \write\istfile{^\J; additional sort rules^\J}
1834     \write\istfile{\@xdysortrules}%
1835     \noist
1836 \else

Code to use if makeindex is required.

1837     \edef\@gls@actualchar{\string?}
1838     \edef\@gls@encapchar{\string!}
1839     \edef\@gls@levelchar{\string!}
1840     \edef\@gls@quotechar{\string"}
1841     \def\writeist{\relax
1842         \openout\istfile=\istfilename
1843         \write\istfile{\expandafter\@gobble\string\% makeindex style file
1844             created by the glossaries package}
1845         \write\istfile{\expandafter\@gobble\string\% for document
1846             '\jobname' on \the\year-\the\month-\the\day}
1847         \write\istfile{actual '\@gls@actualchar'}
1848         \write\istfile{encap '\@gls@encapchar'}
1849         \write\istfile{level '\@gls@levelchar'}
1850         \write\istfile{quote '\@gls@quotechar'}
1851         \write\istfile{keyword \string"\string\"glossaryentry\string"}
1852         \write\istfile{preamble \string"\string\"glossarysection[\string
1853             \"glossarytoctitle]\{\string\"glossarytitle\}\string"
1854             \"glossarypreamble\string\string\string\begin{theglossary}\string"

```

```

1855      \\glossaryheader\string\n\string"
1856      \write\istfile{postamble \string"\string\"%\string\n\string
1857          \\end{theglossary}\string\"glossarypostamble\string\n
1858          \string"}
1859      \write\istfile{group_skip \string"\string\"glsgroups\string\n
1860          \string"}
1861      \write\istfile{item_0 \string"\string\"glsresetentrylist\string\n
1862          \string"}
1863      \write\istfile{item_1 \string"\string\"glsresetentrylist\string\n
1864          \string"}
1865      \write\istfile{item_x1
1866          \string"\string\"relax \string\"glsresetentrylist\string\n
1867          \string"}
1868      \write\istfile{item_02 \string"\string\"glsresetentrylist\string\n
1869          \string"}
1870      \write\istfile{item_x2
1871          \string"\string\"relax \string\"glsresetentrylist\string\n
1872          \string"}
1873      \write\istfile{delim_0 \string"\{\string"
1874          \string"\glossaryentrynumbers\{\string\"relax \string"
1875      \write\istfile{delim_1 \string"\{\string"
1876          \string"\glossaryentrynumbers\{\string\"relax \string"
1877      \write\istfile{delim_2 \string"\{\string"
1878          \string"\glossaryentrynumbers\{\string\"relax \string"
1879      \write\istfile{delim_t \string"\}\}\string"
1880      \write\istfile{delim_n \string"\string\"glsresetentrylist\string\n
1881          \string"}
1882      \write\istfile{delim_r \string"\string\"glsresetentrylist\string\n
1883          \string"}
1884      \write\istfile{headings_flag 1}
1885      \write\istfile{heading_prefix
1886          \string"\string\"glsgroupheading\{\string"
1887      \write\istfile{heading_suffix
1888          \string"\}\string\"relax
1889          \string"\string\"glsresetentrylist \string"
1890      \write\istfile{symhead_positive \string"\string\"glossy\string"
1891          \string"\string\"glossy\string"
1892      \write\istfile{numhead_positive \string"\string\"glossy\string"
1893          \string"\string\"glossy\string"
1894      \write\istfile{@gls@escbsdq\gls@suffixF
1895          \string"\string\"glossy\string"
1896      \write\istfile{@gls@escbsdq\gls@suffixFF
1897          \string"\string\"glossy\string"
1898      \ifx\gls@suffixF\empty
1899          \else
1900              \write\istfile{suffix_2p \string"\string\"gls@suffixF\string"
1901          \fi
1902      \ifx\gls@suffixFF\empty
1903          \else
1904              \write\istfile{suffix_3p \string"\string\"gls@suffixFF\string"
1905          \fi
1906      \noist
1907  }
1908 \fi

```

The command `\noist` will suppress the creation of the `.ist` file (it simply redefines `\writeist` to do nothing). Obviously you need to use this command before `\writeist` to have any effect. Since the `.ist` file should only be created once, `\noist` is called at the end of `\writeist`.

```
\noist
1904 \newcommand{\noist}{\let\writeist\relax}
```

\@makeglossary is an internal command that takes an argument indicating the glossary type. This command will create the glossary file required by `makeindex` for the given glossary type, using the extension supplied by the *<out-ext>* parameter used in `\newglossary` (and it will also activate the `\glossary` command, and create the customized `.ist` `makeindex` style file).

Note that you can't use `\@makeglossary` for only some of the defined glossaries. You either need to have a `\makeglossary` for all glossaries or none (otherwise you will end up with a situation where `TeX` is trying to write to a non-existent file). The relevant glossary must be defined prior to using `\@makeglossary`.

```
\@makeglossary
1905 \newcommand*{\@makeglossary}[1]{%
1906 \ifglossaryexists{#1}{%
1907 \edef\glo@out{\csname @glotype@#1@out\endcsname}%
1908 \expandafter\newwrite\csname glo@#1@file\endcsname
1909 \edef\@glo@file{\csname glo@#1@file\endcsname}%
1910 \immediate\openout\@glo@file=\jobname.\glo@out
1911 \gls@renewglossary
1912 \PackageInfo{glossaries}{Writing glossary file \jobname.\glo@out}
1913 \writeist
1914 }{\PackageError{glossaries}{%
1915 Glossary type '#1' not defined}{New glossaries must be defined before
1916 using \string\makeglossary}}}
```

`\warn@nomakeglossaries` Issue warning that `\makeglossaries` hasn't been used.

```
1917 \newcommand*{\warn@nomakeglossaries}{%
1918 \PackageWarningNoLine{glossaries}{\string\makeglossaries\space
1919 hasn't been used,^^Jthe glossaries will not be updated}%
1920 }
```

`\makeglossaries` will use `\@makeglossary` for each glossary type that has been defined. New glossaries need to be defined before using `\makeglossary`, so have `\makeglossaries` redefine `\newglossary` to prevent it being used afterwards.

```
\makeglossaries
1921 \newcommand*{\makeglossaries}{%
1922 % Write the name of the style file to the aux file
1923 % (needed by \appname{makeglossaries})
1924 % \begin{macrocode}
1925 \protected@write\@auxout{}{\string\@istfilename{\@istfilename}}%
1926 \protected@write\@auxout{}{\string\@glsorder{\@glsorder}}
```

Iterate through each glossary type and activate it.

```
1927 \@for\glo@type:=\glo@types\do{%
1928 \ifthenelse{\equal{\glo@type}{} }{%
1929 \@makeglossary{\glo@type}}%
1930 }%
```

New glossaries must be created before `\makeglossaries` so disable `\newglossary`.

```
1931 \renewcommand*\newglossary[4][]{%
1932 \PackageError{glossaries}{New glossaries
```

```

1933 must be created before \string\makeglossaries}{You need
1934 to move \string\makeglossaries\space after all your
1935 \string\newglossary\space commands}}%

```

Any subsequence instances of this command should have no effect

```

1936 \let\@makeglossary\relax
1937 \let\makeglossary\relax
1938 \let\makeglossaries\relax

```

Disable all commands that have no effect after \makeglossaries

```

1939 \@disable@onlypremakeg

```

Suppress warning about no \makeglossaries

```

1940 \let\warn@nomakeglossaries\relax
1941 }

```

The \makeglossary command is redefined to be identical to \makeglossaries.
 (This is done to reinforce the message that you must either use \@makeglossary
 for all the glossaries or for none of them.)

```
\makeglossary
1942 \let\makeglossary\makeglossaries
```

If \makeglossaries hasn't been used, issue a warning. Also issue a warning
 if neither \printglossaries nor \printglossary have been used.

```

1943 \AtEndDocument{%
1944   \warn@nomakeglossaries
1945   \warn@noprintglossary
1946 }

```

5.13 Writing information to associated files

The \glossary command is redefined so that it takes an optional argument *<type>*
 to specify the glossary type (use \glsdefaulttype glossary by default). This
 shouldn't be used at user level as \glslink sets the correct format. The associated
 number should be stored in \the\glsentrycounter before using \glossary.

```
\glossary
1947 \renewcommand*{\glossary}[1][\glsdefaulttype]{%
1948   \glossary[#1]}
```

Define internal \@glossary to ignore its argument. This gets redefined in
 \@makeglossary. This is defined to just \index as memoir changes the definition
 of \cindex. (Thanks to Dan Luecking for pointing this out.)

```
\@glossary
1949 \def\@glossary[#1]{\index}
```

This is a convenience command to set \@glossary. It is used by \@makeglossary
 and then redefined to do nothing, as it only needs to be done once.

```
@gls@renewglossary
1950 \newcommand{\@gls@renewglossary}{%
1951   \gdef\@glossary[##1]{\@bsphack\begingroup\@wrglossary{##1}\%}
1952   \let\@gls@renewglossary\@empty
1953 }
```

The `\@wrglossary` command is redefined to have two arguments. The first argument is the glossary type, the second argument is the glossary entry (the format of which is set in `\glslink`).

```
\@wrglossary
1954 \renewcommand*\@wrglossary}[2]{%
1955   \expandafter\protected@write\csname glo@#1@file\endcsname{}{#2}%
1956   \endgroup\@esphack
1957 }

\@do@wrglossary Write the glossary entry in the appropriate format. (Need to set glsnumberformat and gls@counter prior to use.) The argument is the entry's label.
1958 \newcommand{\@do@wrglossary}[1]{%
  Determine whether to use xindy or makeindex syntax
  1959 \ifglsxindy
    Need to determine if the formatting information starts with a ( or ) indicating a
    range.
    1960 \expandafter\glo@check@mkidxrangechar\glsnumberformat@nil
    1961 \def\glo@range{}%
    1962 \expandafter\if\glo@prefix(\relax
    1963   \def\glo@range{:open-range}%
    1964 \else
    1965   \expandafter\if\glo@prefix)\relax
    1966   \def\glo@range{:close-range}%
    1967 \fi
    1968 \fi
    Get the location and escape any special characters
    1969 \protected@edef\glslocref{\theglsentrycounter}%
    1970 \gls@checkmkidxchars@glslocref
    Write to the glossary file using xindy syntax.
    1971 \glossary[\csname glo@#1@type\endcsname]{%
      indexentry :tkey (\csname glo@#1@index\endcsname)
      :locref \string"\glslocref\string" %
      :attr \string"\glo@suffix\string" \glo@range
    }
    1976 }%
  1977 \else
    Convert the format information into the format required for makeindex
    1978 \set@glo@numformat@glo@numfmt@gls@counter@glsnumberformat
    Write to the glossary file using makeindex syntax.
    1979 \glossary[\csname glo@#1@type\endcsname]{%
      \string\glossaryentry{\csname glo@#1@index\endcsname
      \gls@encapchar\glo@numfmt}{\theglsentrycounter}}%
    1982 \fi
  1983 }
```

5.14 Glossary Entry Cross-References

\@do@seeglossary Write the glossary entry with a cross reference. The first argument is the entry's label, the second must be in the form [$\langle tag \rangle$] { $\langle list \rangle$ }, where $\langle tag \rangle$ is a tag such as "see" and $\langle list \rangle$ is a list of labels.

```

1984 \newcommand{\@do@seeglossary}[2]{%
1985 \ifglsxindy
1986   \glossary[\csname glo@\#1@type\endcsname]{%
1987     (indexentry
1988       :tkey (\csname glo@\#1@index\endcsname)
1989       :xref (\string"\#2\string")
1990       :attr \string"see\string"
1991     )
1992   }%
1993 \else
1994   \glossary[\csname glo@\#1@type\endcsname]{%
1995     \string\glossaryentry{\csname glo@\#1@index\endcsname
1996     \gls@encapchar glsseeformat#2}{Z}}%
1997 \fi
1998 }
```

\@gls@fixbraces If no optional argument is specified, list needs to be enclosed in a set of braces.

```

1999 \def\@gls@fixbraces#1#2#3@nil{%
2000   \ifx#2[\relax
2001     \def#1{#2#3}%
2002   \else
2003     \def#1{#2#3}%
2004   \fi
2005 }
```

```

\glssee \glssee{ $\langle label \rangle$ }{ $\langle cross-ref list \rangle$ }
2006 \newcommand*{\glssee}[3][\seenename]{%
2007   \@do@seeglossary{#2}{[#1]{#3}}}
2008 \newcommand*{\@glssee}[3][\seenename]{%
2009   \glssee[#1]{#3}{#2}}
2010 %   \end{macrocode}
2011 %\end{macro}
2012 %
2013 %\begin{macro}{\glsseeformat}
2014 %\changes{1.17}{2008 December 26}{new}
2015 % The first argument specifies what tag to use (e.g. \ ``see''),
2016 % the second argument is a comma-separated list of labels.
2017 % The final argument (the location) is ignored.
2018 %   \begin{macrocode}
2019 \newcommand*{\glsseeformat}[3][\seenename]{\emph{#1} \glsseelist{#2}}
```

\glsseelist \glsseelist{ $\langle list \rangle$ } formats list of entry labels.

```
2020 \newcommand*{\glsseelist}[1]{%
```

If there is only one item in the list, set the last separator to do nothing.

```
2021 \let\gls@dolast\relax
```

Don't display separator on the first iteration of the loop

```
2022 \let\gls@donext\relax
```

```

Iterate through the labels
2023  \@for\@gls@thislabel:=#1\do{%
    Check if on last iteration of loop
2024      \ifx\@xfor@nextelement\@nnil
2025          \@gls@doLast
2026      \else
2027          \@gls@doNext
2028      \fi
        display the entry for this label
2029      \glsseeitem{\@gls@thislabel}%
    Update separators
2030      \let\@gls@doLast\glsseeLastsep
2031      \let\@gls@doNext\glsseeSep
2032  }%
2033 }

\glsseeLastsep Separator to use between penultimate and ultimate entries in a cross-referencing
list.
2034 \newcommand*{\glsseeLastsep}{\space\andname\space}

\glsseeSep Separator to use between entries in a cross-referencing list.
2035 \newcommand*{\glsseeSep}{, }

\glsseeitem \glsseeitem{\langle label\rangle} formats individual entry in a cross-referencing list.
2036 \newcommand*{\glsseeitem}[1]{\glshyperlink{\#1}}

```

5.15 Displaying the glossary

An individual glossary is displayed in the text using `\printglossary[⟨key-val list⟩]`. If the `type` key is omitted, the default glossary is displayed. The optional argument can be used to specify an alternative glossary, and can also be used to set the style, title and entry in the table of contents. Available keys are defined below.

```

\warn@noprintglossary Warn the user if they have forgotten \printglossaries or \printglossary.
(Will be suppressed if there is at least one occurrence of \printglossary. There
is no check to ensure that there is a \printglossary for each defined glossary.)
2037 \def\warn@noprintglossary{\PackageWarningNoLine{glossaries}{No
2038   \string\printglossary\space or \string\printglossaries\space
2039   found.^^JThis document will not have a glossary.}}

\printglossary The TOC title needs to be processed in a different manner to the main title in
case the translator and hyperref packages are both being used.
2040 \@ifundefined{\printglossary}{}{%
    If \printglossary is already defined, issue a warning and undefine it.
2041 \PackageWarning{glossaries}{Overriding \string\printglossary}%
2042 \let\printglossary\undefined}
    \printglossary has an optional argument. The default value is to set the glossary
    type to the main glossary.
2043 \newcommand*{\printglossary}[1][type=\glsdefaulttype]{%

```

If `xindy` is being used, need to find the root language for `makeglossaries` to pass to `xindy`.

```
2044 \ifglsxindy\findrootlanguage\fi
      Set up defaults.
2045 \def\@glo@type{\glsdefaulttype}%
2046 \def\glossarytitle{\csname @glotype@\@glo@type @title\endcsname}%
2047 \def\@glossarystyle{}%
2048 \def\gls@dototitle{\glssettoctitle{@glo@type}}%
      Store current value of \glossaryentrynumbers. (This may be changed via the
      optional argument)
2049 \let\org@glossaryentrynumbers\glossaryentrynumbers
      Localise the effects of the optional argument
2050 \bgroup
      Determine settings specified in the optional argument.
2051 \setkeys{printgloss}{#1}%
      Enable individual number lists to be suppressed.
2052 \let\org@glossaryentrynumbers\glossaryentrynumbers
2053 \let\glsnonextpages\glsnonextpages
      Enable suppression of description terminators.
2054 \let\nopostdesc\nopostdesc
      Set up the entry for the TOC
2055 \gls@dototitle
      Set the glossary style
2056 \glossarystyle
      Some macros may end up being expanded into internals in the glossary, so need
      to make @ a letter.
2057 \makeatletter
      Input the glossary file, if it exists.
2058 \input{\jobname.\csname @glotype@\@glo@type @in\endcsname}%
      If xindy is being used, need to write the language dependent information to the
      .aux file for makeglossaries.
2059 \ifglsxindy
2060   \ifundefined{\xdy@\@glo@type @language}%
2061     \protected@write\auxout{}{%
2062       \string\xdylanguage{\@glo@type}{\xdy@main@language}}%
2063   }%
2064   \protected@write\auxout{}{%
2065     \string\xdylanguage{\@glo@type}{\csname @xdy@\@glo@type
2066       @language\endcsname}}%
2067   }%
2068   \protected@write\auxout{}{%
2069     \string\gls@codepage{\@glo@type}{\gls@codepage}}%
2070 \fi
2071 \egroup
      Reset \glossaryentrynumbers
2072 \global\let\glossaryentrynumbers\org@glossaryentrynumbers
```

```

    Suppress warning about no \printglossary
2073 \let\warn@noprintglossary\relax
2074 }

```

The `\printglossaries` command will do `\printglossary` for each glossary type that has been defined. It is better to use `\printglossaries` rather than individual `\printglossary` commands to ensure that you don't forget any new glossaries you may have created. It also makes it easier to chop and change the value of the `acronym` package option. However, if you want to list the glossaries in a different order, or if you want to set the title or table of contents entry, or if you want to use different glossary styles for each glossary, you will need to use `\printglossary` explicitly for each glossary type.

```

\printglossaries
2075 \newcommand*{\printglossaries}{%
2076 \forallglossaries{\@glo@type}{\printglossary[type=\@glo@type]}}

```

The keys that can be used in the optional argument to `\printglossary` are as follows: The `type` key sets the glossary type.

```
2077 \define@key{printgloss}{type}{\def\@glo@type{\#1}}
```

The `title` key sets the title used in the glossary section header. This overrides the title used in `\newglossary`.

```
2078 \define@key{printgloss}{title}{\def\glossarytitle{\#1}}
```

The `toctitle` sets the text used for the relevant entry in the table of contents.

```
2079 \define@key{printgloss}{toctitle}{\def\glossarytoctitle{\#1}%
2080 \let\gls@dotoc@title\relax
2081 }
```

The `style` key sets the glossary style (but only for the given glossary).

```
2082 \define@key{printgloss}{style}{%
2083 \@ifundefined{glsstyle@\#1}{\PackageError{glossaries}{Glossary
2084 style '#1' undefined}{}{}}%
2085 \def\glossarystyle{\csname glsstyle@\#1\endcsname}}
```

The `numberedsection` key determines if this glossary should be in a numbered section.

```
2086 \define@choicekey{printgloss}{numberedsection}{[val\nr]}{%
2087 false,nolabel,autolabel}[nolabel]{%
2088 \ifcase\nr\relax
2089   \renewcommand*{\@glossarysecstar}{*}%
2090   \renewcommand*{\@glossaryseclabel}{}
2091 \or
2092   \renewcommand*{\@glossarysecstar}{}
2093   \renewcommand*{\@glossaryseclabel}{}
2094 \or
2095   \renewcommand*{\@glossarysecstar}{}
2096   \renewcommand*{\@glossaryseclabel}{\label{\glsautoprefix\@glo@type}}%
2097 \fi}
```

The `nonumberlist` key determines if this glossary should have a number list.

```
2098 \define@boolkey{printgloss}{gls}{nonumberlist}{true}{%
2099 \ifglsnonumberlist
2100   \def\glossaryentrynumbers##1{}%
```

```

2101 \else
2102   \def\glossaryentrynumbers##1{##1}%
2103 \fi}

\@glsnonextpages Suppresses the next number list only. Global assignments required as it may
not occur in the same level of grouping as the next numberlist. (For example, if
\glsnonextpages is placed in the entry's description and 3 column tabular style
glossary is used.) \org@glossaryentrynumbers needs to be set at the start of
each glossary, in the event that \glossaryentrynumber is redefined.

2104 \newcommand*{\glsnonextpages}{%
2105   \gdef\glossaryentrynumbers##1{%
2106     \glsresetentrylist}%

\glsresetentrylist Resets \glossaryentrynumbers
2107 \newcommand*{\glsresetentrylist}{%
2108   \global\let\glossaryentrynumbers\org@glossaryentrynumbers}

\glsnonextpages Outside of \printglossary this does nothing.
2109 \newcommand*{\glsnonextpages}{}

\theglossary If the \theglossary environment has already been defined, a warning will be
issued. This environment should be redefined by glossary styles.

2110 \@ifundefined{\theglossary}{%
2111   \newenvironment{\theglossary}{}{}{%
2112     \PackageWarning{glossaries}{overriding 'theglossary' environment}%
2113   \renewenvironment{\theglossary}{}{}}

The glossary header is given by \glossaryheader. This forms part of the
glossary style, and must indicate what should appear immediately after the start
of the \theglossary environment. (For example, if the glossary uses a tabular-like
environment, it may be used to set the header row.) Note that if you don't want
a header row, the glossary style must redefine \glossaryheader to do nothing.

\glossaryheader
2114 \newcommand*{\glossaryheader}{}

\glstarget \glstarget{\langle label \rangle}{\langle name \rangle}

Provide user interface to \glstarget to make it easier to modify the glossary
style in the document.

2115 \newcommand*{\glstarget}[2]{\glstarget{\glo:#1}{\glo:#2}{}}

\glossaryentryfield \glossaryentryfield{\langle label \rangle}{\langle name \rangle}{\langle description \rangle}{\langle symbol \rangle}{\langle page-list \rangle}

This command governs how each entry row should be formatted in the glossary.
Glossary styles need to redefine this command. Most of the predefined styles
ignore \langle symbol \rangle.

2116 \newcommand*{\glossaryentryfield}[5]{%
2117   \noindent\textrm{bf}{\glstarget{\#1}{\#2}} \#4 \#3. \#5\par}

\glossarysubentryfield \glossarysubentryfield{\langle level \rangle}{\langle label \rangle}{\langle name \rangle}{\langle description \rangle}{\langle symbol \rangle}{\langle page-list \rangle}

This command governs how each subentry should be formatted in the glossary.

```

Glossary styles need to redefine this command. Most of the predefined styles ignore *<symbol>*. The first argument is a number indicating the level. (The level should be greater than or equal to 1.)

```
2118 \newcommand*{\glossarysubentryfield}[6]{%
2119 \glstarget{#2}{\strut}#4. #6\par}
```

Within each glossary, the entries form distinct groups which are determined by the first character of the `sort` key. When using `makeindex`, there will be a maximum of 28 groups: symbols, numbers, and the 26 alphabetical groups A, ..., Z. If you use `xindy` the groups will depend on whatever alphabet is used. This is determined by the language or custom alphabets can be created in the `xindy` style file. The command `\glsgroupskip` specifies what to do between glossary groups. Glossary styles must redefine this command. (Note that `\glsgroupskip` only occurs between groups, not at the start or end of the glossary.)

```
\glsgroupskip
2120 \newcommand*{\glsgroupskip}{}%
```

Each of the 28 glossary groups described above is preceded by a group heading. This is formatted by the command `\glsgroupheding` which takes one argument which is the *label* assigned to that group (not the title). The corresponding labels are: `glssymbols`, `glsnumbers`, A, ..., Z. Glossary styles must redefine this command. (In between groups, `\glsgroupheding` comes immediately after `\glsgroupskip`.)

```
\glsgroupheding
2121 \newcommand*{\glsgroupheding}[1]{}%
```

It is possible to “trick” `makeindex` into treating entries as though they belong to the same group, even if the terms don’t start with the same letter, by modifying the `sort` key. For example, all entries belonging to one group could be defined so that the `sort` key starts with an `a`, while entries belonging to another group could be defined so that the `sort` key starts with a `b`, and so on. If you want each group to have a heading, you would then need to modify the translation control sequences `\glsgetgroupitle` and `\glsgetgrouplabel` so that the label is translated into the required title (and vice-versa).

`\glsgetgroupitle{<label>}`

This command produces the title for the glossary group whose label is given by *<label>*. By default, the group labelled `glssymbols` produces `\glssymbolsgroupname`, the group labelled `glsnumbers` produces `\glsnumbersgroupname` and all the other groups simply produce their label. As mentioned above, the group labels are: `glssymbols`, `glsnumbers`, A, ..., Z. If you want to redefine the group titles, you will need to redefine this command.

```
\glsgetgroupitle
2122 \newcommand*{\glsgetgroupitle}[1]{%
2123 \@ifundefined{#1groupname}{#1}{\csname #1groupname\endcsname}}
```

`\glsgetgrouplabel{<title>}`

This command does the reverse to the previous command. The argument is

the group title, and it produces the group label. Note that if you redefine `\glsgroupname`, you will also need to redefine `\glsgrouplabel`.

```
\glsgrouplabel
2124 \newcommand*{\glsgrouplabel}[1]{%
2125 \ifthenelse{\equal{#1}{\glssymbolsgroupname}}{\glssymbols}{%
2126 \ifthenelse{\equal{#1}{\glsnumbersgroupname}}{\glsnumbers}{#1}}}
```

The command `\setentrycounter` sets the entry's associated counter (required by `\glshypernumber` etc.) `\glslink` and `\glsadd` encode the `\glossary` argument so that the relevant counter is set prior to the formatting command.

```
\setentrycounter
2127 \newcommand*{\setentrycounter}[1]{\def\glsentrycounter{#1}}
```

The current glossary style can be set using `\glossarystyle{<style>}`.

```
\glossarystyle
2128 \newcommand*{\glossarystyle}[1]{%
2129 \GIfundefined{\glsstyle@#1}{\PackageError{glossaries}{Glossary
2130 style '#1' undefined}{}{%
2131 \csname @glsstyle@#1\endcsname}}
```

`\newglossarystyle` New glossary styles can be defined using:

```
\newglossarystyle{<name>}{<definition>}
```

The `<definition>` argument should redefine `\glossary`, `\glossaryheader`, `\glossarygroupheading`, `\glossaryentryfield` and `\glossarygroupskip` (see [subsection 5.18](#) for the definitions of predefined styles). Glossary styles should not redefine `\glossarypreamble` and `\glossarypostamble`, as the user should be able to switch between styles without affecting the pre- and postambles.

```
2132 \newcommand{\newglossarystyle}[2]{%
2133 \GIfundefined{\glsstyle@#1}{%
2134 \expandafter\def\csname @glsstyle@#1\endcsname{#2}}{%
2135 \PackageError{glossaries}{Glossary style '#1' is already defined}{}}}
```

Glossary entries are encoded so that the second argument to `\glossaryentryfield` is always specified as `\glsnamefont{<name>}`. This allows the user to change the font used to display the name term without having to redefine `\glossaryentryfield`. The default uses the surrounding font, so in the list type styles (which place the name in the optional argument to `\item`) the name will appear in bold.

```
\glsnamefont
2136 \newcommand*{\glsnamefont}[1]{#1}
```

Each glossary entry has an associated number list (usually page numbers) that indicate where in the document the entry has been used. The format for these number lists can be changed using the `format` key in commands like `\glslink`. The default format is given by `\glshypernumber`. This takes a single argument which may be a single number, a number range or a number list. The number ranges are delimited with `\delimR`, the number lists are delimited with `\delimN`.

If the document doesn't have hyperlinks, the numbers can be displayed just as they are, but if the document supports hyperlinks, the numbers should link to the

relevant location. This means extracting the individual numbers from the list or ranges. The `hyperref` package does this with the `\hyperpage` command, but this is encoded for comma and dash delimiters and only for the page counter, but this code needs to be more general. So I have adapted the code used in the `hyperref` package.

```
\glshypernumber
2137 \@ifundefined{hyperlink}{%
2138 \def\glshypernumber#1{\#1}{%
2139 \def\glshypernumber#1{%
2140   \noexpand\glshypernumber#1\nohyperpage{}\@nil}}}
```

`\@glshypernumber` This code was provided by Heiko Oberdiek to allow material to be attached to the location.

```
2141 \def\@glshypernumber#1\nohyperpage#2#3\@nil{%
2142   \ifx\\#1\\%
2143   \else
2144     \expandafter\@delimR#1\delimR\delimR\\%
2145   \fi
2146   \ifx\\#2\\%
2147   \else
2148     \expandafter\#2%
2149   \fi
2150   \ifx\\#3\\%
2151   \else
2152     \expandafter\@glshypernumber#3\@nil
2153   \fi
2154 }
```

`\@delimR` displays a range of numbers for the counter whose name is given by `\gls@counter` (which must be set prior to using `\glshypernumber`).

```
\@delimR
2155 \def\@delimR#1\delimR #2\delimR #3\\{%
2156 \ifx\\#2\\%
2157   \expandafter\@delimN\#1%
2158 \else
2159   \gls@numberlink{\#1}\delimR\gls@numberlink{\#2}%
2160 \fi}
```

`\@delimN` displays a list of individual numbers, instead of a range:

```
\@delimN
2161 \def\@delimN#1{\expandafter\@delimN\#1\delimN \delimN\\}
2162 \def\@delimN#1\delimN #2\delimN#3\\{%
2163 \ifx\\#3\\%
2164   \gls@numberlink{\#1}%
2165 \else
2166   \gls@numberlink{\#1}\delimN\gls@numberlink{\#2}%
2167 \fi
2168 }
```

The following code is modified from `hyperref`'s `\HyInd@pagelink` where the name of the counter being used is given by `\gls@counter`.

```

2169 \def\@gls@numberlink#1{%
2170 \begingroup
2171 \toks@={}%
2172 \@gls@removespaces#1 \@nil
2173 \endgroup}

2174 \def\@gls@removespaces#1 #2\@nil{%
2175 \toks@=\expandafter{\the\toks@#1}%
2176 \ifx\\#2\\%
2177 \edef\x{\the\toks@}%
2178 \ifx\x\empty
2179 \else
2180 \hyperlink{\glsentrycounter.\the\toks@}{\the\toks@}%
2181 \fi
2182 \else
2183 \@gls@ReturnAfterFi{%
2184 \@gls@removespaces#2\@nil
2185 }%
2186 \fi
2187 }
2188 \long\def\@gls@ReturnAfterFi#1\fif{\fi#1}

```

The following commands will switch to the appropriate font, and create a hyperlink, if hyperlinks are supported. If hyperlinks are not supported, they will just display their argument in the appropriate font.

```

\hyperrm
2189 \newcommand*{\hyperrm}[1]{\textrm{\glshypernumber{#1}}}

\hypersf
2190 \newcommand*{\hypersf}[1]{\textsf{\glshypernumber{#1}}}

\hypertt
2191 \newcommand*{\hypertt}[1]{\texttt{\glshypernumber{#1}}}

\hyperbf
2192 \newcommand*{\hyperbf}[1]{\textbf{\glshypernumber{#1}}}

\hypermd
2193 \newcommand*{\hypermd}[1]{\textmd{\glshypernumber{#1}}}

\hyperit
2194 \newcommand*{\hyperit}[1]{\textit{\glshypernumber{#1}}}

\hypersl
2195 \newcommand*{\hypersl}[1]{\textsl{\glshypernumber{#1}}}

\hyperup
2196 \newcommand*{\hyperup}[1]{\textup{\glshypernumber{#1}}}

\hypersc
2197 \newcommand*{\hypersc}[1]{\textsc{\glshypernumber{#1}}}

\hyperemph
2198 \newcommand*{\hyperemph}[1]{\emph{\glshypernumber{#1}}}

```

5.16 Acronyms

If the `acronym` package option is used, a new glossary called `acronym` is created

```
2199 \ifglsacronym  
2200   \newglossary[alg]{acronym}{acr}{acn}{\acronymname}  
      and \acronymtype is set to the name of this new glossary.  
2201   \renewcommand{\acronymtype}{acronym}
```

In the event that the user redefines `\glsdisplay` and `\glsdisplayfirst`, the relevant commands for the new acronym glossary are set to match the format given by `\newacronym`. If you redefine `\newacronym` you may need to set these to something else.

```
2202   \defglsdisplay[acronym]{#1#4}  
2203   \defglsdisplayfirst[acronym]{#1#4}  
2204 \fi  
  
\newacronym[<key-val list>]{<label>}{<abbrev>}{<long>}
```

This is a quick way of defining acronyms, all it does is call `\newglossaryentry` with the appropriate values. It sets the glossary type to `\acronymtype` which will be `acronym` if the package option `acronym` has been used, otherwise it will be the default glossary. Since `\newacronym` merely calls `\newglossaryentry`, the acronym is treated like any other glossary entry.

If you prefer a different format, you can redefine `\newacronym` as required. The optional argument can be used to override any of the settings.

```
\newacronym  
2205 \newcommand{\newacronym}[4][]{%  
2206   \newglossaryentry[#2]{type=\acronymtype,%  
2207   name={#3},description={#4},text={#3},%  
2208   descriptionplural={#4\acrpluralsuffix},%  
2209   first={#4 (#3)},plural={#3\acrpluralsuffix},%  
2210   firstplural={\@glo@descplural\xspace (\@glo@plural)},%  
2211 #1}}
```



```
\oldacronym \oldacronym[<label>]{<abbrev>}{<long>}{<key-val list>}
```

This emulates the way the old `glossary` package defined acronyms. It is equivalent to `\newacronym[<key-val list>]{<label>}{<abbrev>}{<long>}` and it additionally defines the command `\<label>` which is equivalent to `\gls{<label>}` (thus `<label>` must only contain alphabetical characters). If `<label>` is omitted, `<abbrev>` is used. This only emulates the syntax of the old `glossary` package. The way the acronyms appear in the list of acronyms is determined by the definition of `\newacronym` and the glossary style.

Note that `\<label>` can't have an optional argument if the `xspace` package is loaded. If `xspace` hasn't been loaded then you can do `\<label> [<insert>]` but you can't do `\<label> [<key-val list>]`. For example if you define the acronym `svm`, then you can do `\svm['s]` but you can't do `\svm[format=textbf]`. If the `xspace` package is loaded, `\svm['s]` will appear as `svm ['s]` which is unlikely to be the desired result. In this case, you will need to use `\gls` explicitly, e.g. `\gls{svm}['s]`. Note that it is up to the user to load `xspace` if desired.

```
2212 \newcommand{\oldacronym}[4][\gls@label]{%
```

```

2213 \def\gls@label{#2}%
2214 \newacronym[#4]{#1}{#2}{#3}%
2215 \@ifundefined{xspace}{%
2216   \expandafter\edef\csname#1\endcsname{%
2217     \noexpand\ifstar{\noexpand\Gls{#1}}{\noexpand\gls{#1}}}%
2218 }{%
2219   \expandafter\edef\csname#1\endcsname{%
2220     \noexpand\ifstar{\noexpand\Gls{#1}\noexpand\xspace}{%
2221       \noexpand\gls{#1}\noexpand\xspace}}%
2222 }%
2223 }

```

Set up some convenient short cuts. These need to be changed if `\newacronym` is changed (or if the `description` key is changed).

`\acrpluralsuffix` Plural suffix used by `\newacronym`. This just defaults to `\glspluralsuffix` but is changed to include `\textup` if the `smallcaps` option is used, so that the suffix doesn't appear in small caps as it doesn't look right. For example, ABCS looks as though the "s" is part of the acronym, but ABCs looks as though the "s" is a plural suffix. Since the entire text `abcs` is set in `\textsc`, `\textup` is needed to cancel it out.

```
2224 \newcommand*{\acrpluralsuffix}{\glspluralsuffix}
```

Make a note of the keys that are used to store the long and short forms:

```

\glsshortkey
2225 \newcommand*{\glsshortkey}[text]

\glsshortpluralkey
2226 \newcommand*{\glsshortpluralkey}[plural]

\glslongkey
2227 \newcommand*{\glslongkey}[description]

\glslongpluralkey
2228 \newcommand*{\glslongpluralkey}[descriptionplural]

```

Using the default definitions, `\acrshort` is the same as `\glstext`, which means that it will print the abbreviation.

```

\acrshort
2229 \newcommand*{\acrshort}[2][]{%
2230 \new@ifnextchar[{\@acrshort{#1}{#2}}{\@acrshort{#1}{#2}[]}}
2231 \def\@acrshort#1#2[#3]{\@glstext0{#1}{#2}{#3}}

\Acrshort
2232 \newcommand*{\Acrshort}[2][]{%
2233 \new@ifnextchar[{\@Acrshort{#1}{#2}}{\@Acrshort{#1}{#2}[]}}
2234 \def\@Acrshort#1#2[#3]{\@GLStext0{#1}{#2}{#3}>

\ACRshort
2235 \newcommand*{\ACRshort}[2][]{%
2236 \new@ifnextchar[{\@ACRshort{#1}{#2}}{\@ACRshort{#1}{#2}[]}}
2237 \def\@ACRshort#1#2[#3]{\@GLStext0{#1}{#2}{#3}}

```

Plural:

```
\acrshortpl
2238 \newcommand*\acrshortpl[2][]{%
2239 \new@ifnextchar[{\@acrshortpl{#1}{#2}}{\@acrshortpl{#1}{#2}[]}]
2240 \def\@acrshortpl#1#2[#3]{\glsplural@{#1}{#2}{#3}}
\Acrshortpl
2241 \newcommand*\Acrshortpl[2][]{%
2242 \new@ifnextchar[{\@Acrshortpl{#1}{#2}}{\@Acrshortpl{#1}{#2}[]}]
2243 \def\@Acrshortpl#1#2[#3]{\glsplural@{#1}{#2}{#3}}
\ACRshortpl
2244 \newcommand*\ACRshortpl[2][]{%
2245 \new@ifnextchar[{\@ACRshortpl{#1}{#2}}{\@ACRshortpl{#1}{#2}[]}]
2246 \def\@ACRshortpl#1#2[#3]{\glsplural@{#1}{#2}{#3}}
```

`\acrlong` is set to `\glsdesc`, so it will print the long form, unless the description key has been set to something else.

```
\acrlong
2247 \newcommand*\acrlong[2][]{%
2248 \new@ifnextchar[{\@acrlong{#1}{#2}}{\@acrlong{#1}{#2}[]}]
2249 \def\@acrlong#1#2[#3]{\glsdesc@{#1}{#2}{#3}}
\Acrlong
2250 \newcommand*\Acrlong[2][]{%
2251 \new@ifnextchar[{\@Acrlong{#1}{#2}}{\@Acrlong{#1}{#2}[]}]
2252 \def\@Acrlong#1#2[#3]{\glsdesc@{#1}{#2}{#3}}
\ACRlong
2253 \newcommand*\ACRlong[2][]{%
2254 \new@ifnextchar[{\@ACRlong{#1}{#2}}{\@ACRlong{#1}{#2}[]}]
2255 \def\@ACRlong#1#2[#3]{\glsdesc@{#1}{#2}{#3}}
```

Plural:

```
\acrlongpl
2256 \newcommand*\acrlongpl[2][]{%
2257 \new@ifnextchar[{\@acrlongpl{#1}{#2}}{\@acrlongpl{#1}{#2}[]}]
2258 \def\@acrlongpl#1#2[#3]{\glsdescplural@{#1}{#2}{#3}}
\Acrlongpl
2259 \newcommand*\Acrlongpl[2][]{%
2260 \new@ifnextchar[{\@Acrlongpl{#1}{#2}}{\@Acrlongpl{#1}{#2}[]}]
2261 \def\@Acrlongpl#1#2[#3]{\glsdescplural@{#1}{#2}{#3}}
\ACRlongpl
2262 \newcommand*\ACRlongpl[2][]{%
2263 \new@ifnextchar[{\@ACRlongpl{#1}{#2}}{\@ACRlongpl{#1}{#2}[]}]
2264 \def\@ACRlongpl#1#2[#3]{\glsdescplural@{#1}{#2}{#3}}
```

`\acrfull` is set to `\glsfirst`, so it should display the full form.

```

\acrfull
2265 \newcommand*\acrfull{[2] [] {%
2266 \new@ifnextchar[{\@acrfull{#1}{#2}}{\@acrfull{#1}{#2}[]}]
2267 \def\@acrfull#1#2[#3]{\glsfirst@{#1}{#2}[#3]}

\Acrfull
2268 \newcommand*\Acrfull{[2] [] {%
2269 \new@ifnextchar[{\@Acrfull{#1}{#2}}{\@Acrfull{#1}{#2}[]}]
2270 \def\@Acrfull#1#2[#3]{\glsfirst@{#1}{#2}[#3]}

\ACRfull
2271 \newcommand*\ACRfull{[2] [] {%
2272 \new@ifnextchar[{\@ACRfull{#1}{#2}}{\@ACRfull{#1}{#2}[]}]
2273 \def\@ACRfull#1#2[#3]{\glsfirst@{#1}{#2}[#3]}

Plural:

\acrfullpl
2274 \newcommand*\acrfullpl{[2] [] {%
2275 \new@ifnextchar[{\@acrfullpl{#1}{#2}}{\@acrfullpl{#1}{#2}[]}]
2276 \def\@acrfullpl#1#2[#3]{\glsfirstplural@{#1}{#2}[#3]}

\Acrfullpl
2277 \newcommand*\Acrfullpl{[2] [] {%
2278 \new@ifnextchar[{\@Acrfullpl{#1}{#2}}{\@Acrfullpl{#1}{#2}[]}]
2279 \def\@Acrfullpl#1#2[#3]{\glsfirstplural@{#1}{#2}[#3]}

\ACRfullpl
2280 \newcommand*\ACRfullpl{[2] [] {%
2281 \new@ifnextchar[{\@ACRfullpl{#1}{#2}}{\@ACRfullpl{#1}{#2}[]}]
2282 \def\@ACRfullpl#1#2[#3]{\glsfirstplural@{#1}{#2}[#3]}

```

5.17 Additional predefined acronym styles

\acronymfont This is only used with the additional acronym styles:

```
2283 \newcommand{\acronymfont}[1]{#1}
```

\firstacronymfont This is only used with the additional acronym styles:

```
2284 \newcommand{\firstacronymfont}[1]{\acronymfont{#1}}
```

\acrnameformat The styles that allow an additional description use \acrnameformat{<short>}{<long>} to determine what information is displayed in the name.

```
2285 \newcommand*\acrnameformat[2]{\acronymfont{#1}}
```

2286 \ifglsacrdescription

If a description and footnote are both required, store the long form in the symbol key. Store the short form in text key. Note that since the long form is stored in the symbol key, if you want the long form to appear in the list of acronyms, you need to use a glossary style that displays the symbol key.

```
2287 \ifglsacrfootnote
2288   \renewcommand{\newacronym}[4][]{%
2289     \newglossaryentry{#2}{type=\acronymtype,%
```

```

2290     name={\acronymfont{#3}},%
2291     sort={#3},%
2292     text={#3},%
2293     plural={#3\acrpluralsuffix},%
2294     symbol={#4},%
2295     symbolplural={#4\acrpluralsuffix},%
2296     #1}%

```

Set up the commands to make a note of the keys to store the long and short forms:

```

2297     \def\glsshortkey{text}%
2298     \def\glsshortpluralkey{plural}%
2299     \def\glslongkey{symbol}%
2300     \def\glslongpluralkey{symbolplural}%

```

Set up short cuts. Short form:

```

2301     \def\@acrshort#1#2[#3]{\acronymfont{\@glstext{#1}{#2}{#3}}}
2302     \def\@Acrshort#1#2[#3]{\acronymfont{\@GlsText{#1}{#2}{#3}}}
2303     \def\@ACRshort#1#2[#3]{\acronymfont{\@GLStext{#1}{#2}{#3}}}

```

Plural form:

```

2304     \def\@acrshortpl#1#2[#3]{\acronymfont{\@glsplural{#1}{#2}{#3}}}
2305     \def\@Acrshortpl#1#2[#3]{\acronymfont{\@GlsPlural{#1}{#2}{#3}}}
2306     \def\@ACRshortpl#1#2[#3]{\acronymfont{\@GLSPlural{#1}{#2}{#3}}}

```

Long form:

```

2307     \def\@acrlong#1#2[#3]{\@glosssymbol{#1}{#2}{#3}}
2308     \def\@Acrlong#1#2[#3]{\@Glosssymbol{#1}{#2}{#3}}
2309     \def\@ACRlong#1#2[#3]{\@GLSsymbol{#1}{#2}{#3}}

```

Plural long form:

```

2310     \def\@acrlongpl#1#2[#3]{\@glosssymbolplural{#1}{#2}{#3}}
2311     \def\@Acrlongpl#1#2[#3]{\@Glosssymbolplural{#1}{#2}{#3}}
2312     \def\@ACRlongpl#1#2[#3]{\@GLSsymbolplural{#1}{#2}{#3}}

```

Full form:

```

2313     \def\@acrfull#1#2[#3]{\@glosssymbol{#1}{#2}{#3}%
2314         (\acronymfont{\@glstext{#1}{#2}{#3}})}%
2315     \def\@Acrfull#1#2[#3]{\@Glosssymbol{#1}{#2}{#3}%
2316         (\acronymfont{\@glstext{#1}{#2}{#3}})}%
2317     \def\@ACRfull#1#2[#3]{\@GLSsymbol{#1}{#2}{#3}%
2318         (\acronymfont{\@GLStext{#1}{#2}{#3}})}%

```

Plural full form:

```

2319     \def\@acrfullpl#1#2[#3]{\@glosssymbolplural{#1}{#2}{#3}%
2320         (\acronymfont{\@glsplural{#1}{#2}{#3}})}%
2321     \def\@Acrfullpl#1#2[#3]{\@Glosssymbolplural{#1}{#2}{#3}%
2322         (\acronymfont{\@glsplural{#1}{#2}{#3}})}%
2323     \def\@ACRfullpl#1#2[#3]{\@GLSsymbolplural{#1}{#2}{#3}%
2324         (\acronymfont{\@GLSPlural{#1}{#2}{#3}})}%

```

If footnote package option is specified, set the first use to append the long form (stored in `symbol`) as a footnote.

```

2325     \def\glsdisplayfirst[\acronymtype]{%
2326         \firstacronymfont{#1}\noexpand\protect\noexpand\footnote{%
2327             \noexpand\protect\noexpand\glslink{%
2328                 [\@gls@link@opts]{\@gls@link@label}{#3}}}}%
2329     \def\glsdisplay[\acronymtype]{\acronymfont{#1}\#4}%

```

Redefine \acronymfont if small caps required. The plural suffix is set in an upright font so that it remains in normal lower case, otherwise it looks as though it's part of the acronym.

```

2330  \ifglsacrsmallicaps
2331      \renewcommand*\{\acronymfont\}[1]{\textsc{\#1}}%
2332      \renewcommand*\{\acrpluralsuffix\}{%
2333          \textup{\glspluralsuffix}}%
2334  \else
2335      \ifglsacrsmaller
2336          \renewcommand*\{\acronymfont\}[1]{\textsmaller{\#1}}%
2337      \fi
2338  \fi

Check for package option clash

2339  \ifglsacrdua
2340      \PackageError{glossaries}{Option clash: 'footnote' and 'dua'
2341          can't both be set}{}%
2342  \fi
2343  \else

```

Footnote not required. Should the acronym always be expanded? Note that the short form is stored in the `symbol` key, so if the short form needs to be displayed in the glossary, use a style the displays the symbol.

```

2344  \ifglsacrdua
2345      \ifglsacrsmallicaps
2346          \PackageError{glossaries}{Option clash: 'smallicaps' and 'dua'
2347              can't both be set}{}%
2348  \else
2349      \ifglsacrsmaller
2350          \PackageError{glossaries}{Option clash: 'smaller' and 'dua'
2351              can't both be set}{}%
2352      \fi
2353  \fi
2354  \renewcommand{\newacronym}[4][]{%
2355      \newglossaryentry{\#2}{type=\acronymtype,%
2356          name=\#4,%
2357          sort=\#4,%
2358          text=\#4,%
2359          plural=\#4\acrpluralsuffix},%
2360      \symbol=\#3,%
2361      \symbolplural=\#3\acrpluralsuffix,%
2362      \#1}}

```

Set up the commands to make a note of the keys to store the long and short forms:

```

2363  \def\glsshortkey{\symbol}%
2364  \def\glsshortpluralkey{\symbolplural}%
2365  \def\glslongkey{\first}%
2366  \def\glslongpluralkey{\plural}%

```

Set up short cuts. Short form:

```

2367  \def\@acrshort{\#1\#2[\#3]{\acronymfont{\@glssymbol{\#1}{\#2}{\#3}}}}
2368  \def\@Acrshort{\#1\#2[\#3]{\acronymfont{\@Glsymbol{\#1}{\#2}{\#3}}}}
2369  \def\@ACRshort{\#1\#2[\#3]{\acronymfont{\@GLSsymbol{\#1}{\#2}{\#3}}}}

```

Plural short form:

```

2370      \def\@acrshortpl#1#2[#3]{%
2371          \acronymfont{\@glssymbolplural{#1}{#2}{#3}}}
2372      \def\@Acrshortpl#1#2[#3]{%
2373          \acronymfont{\@Glssymbolplural{#1}{#2}{#3}}}
2374      \def\@ACRshortpl#1#2[#3]{%
2375          \acronymfont{\@GLSsymbolplural{#1}{#2}{#3}}}
```

Long form:

```

2376      \def\@acrlong#1#2[#3]{\@glsfirst{#1}{#2}{#3}}
2377      \def\@Acrlong#1#2[#3]{\@Glsfirst{#1}{#2}{#3}}
2378      \def\@ACRLong#1#2[#3]{\@GLSfirst{#1}{#2}{#3}}
```

Plural long form:

```

2379      \def\@acrlongpl#1#2[#3]{\@glsfirstplural{#1}{#2}{#3}}
2380      \def\@Acrlongpl#1#2[#3]{\@Glsfirstplural{#1}{#2}{#3}}
2381      \def\@ACRLongpl#1#2[#3]{\@GLSfirstplural{#1}{#2}{#3}}
```

Full form:

```

2382      \def\@acrfull#1#2[#3]{\@glsfirst{#1}{#2}{#3}}
2383          (\acronymfont{\@glssymbol{#1}{#2}{#3}})
2384      \def\@Acrfull#1#2[#3]{\@Glsfirst{#1}{#2}{#3}}
2385          (\acronymfont{\@glssymbol{#1}{#2}{#3}})
2386      \def\@ACRfull#1#2[#3]{\@GLSfirst{#1}{#2}{#3}}
2387          (\acronymfont{\@GLSsymbol{#1}{#2}{#3}})
```

Plural full form:

```

2388      \def\@acrfullpl#1#2[#3]{\@glsfirstplural{#1}{#2}{#3}}
2389          (\acronymfont{\@glssymbolplural{#1}{#2}{#3}})
2390      \def\@Acrfullpl#1#2[#3]{\@Glsfirstplural{#1}{#2}{#3}}
2391          (\acronymfont{\@glssymbolplural{#1}{#2}{#3}})
2392      \def\@ACRfullpl#1#2[#3]{\@GLSfirstplural{#1}{#2}{#3}}
2393          (\acronymfont{\@GLSsymbolplural{#1}{#2}{#3}})
```

Set display.

```

2394      \def\glsdisplayfirst[\acronymtype]{#1#4}
2395      \def\glsdisplay[\acronymtype]{#1#4}
2396      \else
```

Option `description` is used, but not `dua` or `footnote`. Store long form in `first` key and short form in `text` and `symbol` key. The name is stored using `\acrnameformat` to allow the user to override the way the name is displayed in the list of acronyms.

```

2397      \renewcommand{\newacronym}[4][]{%
2398          \newglossaryentry{#2}{type=\acronymtype,%
2399              name={\acrnameformat{#3}{#4}},%
2400              sort={#3},%
2401              first={#4},%
2402              firstplural={#4\acrpluralsuffix},%
2403              text={#3},%
2404              plural={#3\acopluralsuffix},%
2405              symbol={\@glo@text},%
2406              symbolplural={\@glo@plural},%
2407              #1}}
```

Set up the commands to make a note of the keys to store the long and short forms:

```

2408      \def\glsshortkey{text}%
2409      \def\glsshortpluralkey{plural}%
2410      \def\glslongkey{first}%
```

```

2411      \def\glslongpluralkey{firstplural}%
Set up short cuts. Short form:
2412      \def\@acrshort#1#2[#3]{\acronymfont{\@glstext{#1}{#2}{#3}}}
2413      \def\@Acrshort#1#2[#3]{\acronymfont{\@Glstext{#1}{#2}{#3}}}
2414      \def\@ACRshort#1#2[#3]{\acronymfont{\@GLStext{#1}{#2}{#3}}}

Plural short form:
2415      \def\@acrshortpl#1#2[#3]{\acronymfont{\@glsplural{#1}{#2}{#3}}}
2416      \def\@Acrshortpl#1#2[#3]{\acronymfont{\@Glsplural{#1}{#2}{#3}}}
2417      \def\@ACRshortpl#1#2[#3]{\acronymfont{\@GLSplural{#1}{#2}{#3}}}

Long form:
2418      \def\@acrlong#1#2[#3]{\@glsfirst{#1}{#2}{#3}}
2419      \def\@Acrlong#1#2[#3]{\@Glsfirst{#1}{#2}{#3}}
2420      \def\@ACRlong#1#2[#3]{\@GLSfirst{#1}{#2}{#3}}

Plural long form:
2421      \def\@acrlongpl#1#2[#3]{\@glsfirstplural{#1}{#2}{#3}}
2422      \def\@Acrlongpl#1#2[#3]{\@Glsfirstplural{#1}{#2}{#3}}
2423      \def\@ACRlongpl#1#2[#3]{\@GLSfirstplural{#1}{#2}{#3}}

Full form:
2424      \def\@acrfull#1#2[#3]{\@glsfirst{#1}{#2}{#3}
2425          (\acronymfont{\@glssymbol{#1}{#2}{#3}})}
2426      \def\@Acrfull#1#2[#3]{\@Glsfirst{#1}{#2}{#3}
2427          (\acronymfont{\@glssymbol{#1}{#2}{#3}})}
2428      \def\@ACRfull#1#2[#3]{\@GLSfirst{#1}{#2}{#3}
2429          (\acronymfont{\@GLSSymbol{#1}{#2}{#3}})}

Plural full form:
2430      \def\@acrfullpl#1#2[#3]{\@glsfirstplural{#1}{#2}{#3}
2431          (\acronymfont{\@glssymbolplural{#1}{#2}{#3}})}
2432      \def\@Acrfullpl#1#2[#3]{\@Glsfirstplural{#1}{#2}{#3}
2433          (\acronymfont{\@glssymbolplural{#1}{#2}{#3}})}
2434      \def\@ACRfullpl#1#2[#3]{\@GLSfirstplural{#1}{#2}{#3}
2435          (\acronymfont{\@GLSSymbolplural{#1}{#2}{#3}})}

Set display.
2436      \def\glsdisplayfirst[\acronymtype]{#1#4 (\firstacronymfont{#3})}
2437      \def\glsdisplay[\acronymtype]{\acronymfont{#1}#4}

Redefine \acronymfont if small caps required. The plural suffix is set in an upright
font so that it remains in normal lower case, otherwise it looks as though it's part
of the acronym.
2438      \ifglsacrsmallcaps
2439          \renewcommand{\acronymfont}[1]{\textsc{#1}}
2440          \renewcommand*{\acrpluralsuffix}{%
2441              \textup{\glspluralsuffix}}%
2442      \else
2443          \ifglsacrsmaller
2444              \renewcommand*{\acronymfont}[1]{\textsmaller{#1}}%
2445          \fi
2446      \fi
2447      \fi
2448      \fi
2449 \else
```

If here, acronyms do not require additional description.

```
2450 \ifglsacrfootnote
```

If footnote package option is specified, set the first use to append the long form (stored in `description`) as a footnote. Use the `description` key to store the long form.

```
2451 \renewcommand{\newacronym}[4][]{%
2452   \newglossaryentry[#2]{type=\acronymtype,%
2453   name={\acronymfont{#3}},%
2454   sort={#3},%
2455   text={#3},%
2456   plural={#3\acrpluralsuffix},%
2457   description={#4},%
2458   descriptionplural={#4\acrpluralsuffix},%
2459   #1}}
```

Set up the commands to make a note of the keys to store the long and short forms:

```
2460 \def\glsshortkey{text}%
2461 \def\glsshortpluralkey{plural}%
2462 \def\glslongkey{description}%
2463 \def\glslongpluralkey{descriptionplural}%
```

Set display

```
2464 \def\glsdisplayfirst[\acronymtype]{%
2465   \firstacronymfont{#1}\#4\noexpand\protect\noexpand\footnote{%
2466     \noexpand\protect\noexpand\glslink{%
2467       [\@gls@link@opts]{\@gls@link@label}{#2}}}}%
2468 \def\glsdisplay[\acronymtype]{\acronymfont{#1}\#4}%
```

Set up short cuts. Short form:

```
2469 \def\@acrshort#1#2[#3]{\acronymfont{\@glstext{#1}{#2}{#3}}}
2470 \def\@Acrshort#1#2[#3]{\acronymfont{\@Glstext{#1}{#2}{#3}}}
2471 \def\@ACRshort#1#2[#3]{\acronymfont{\@GLStext{#1}{#2}{#3}}}
```

Plural short form:

```
2472 \def\@acrshortpl#1#2[#3]{\acronymfont{\@glsplural{#1}{#2}{#3}}}
2473 \def\@Acrshortpl#1#2[#3]{\acronymfont{\@Glsplural{#1}{#2}{#3}}}
2474 \def\@ACRshortpl#1#2[#3]{\acronymfont{\@GLSplural{#1}{#2}{#3}}}
```

Long form:

```
2475 \def\@acrlong#1#2[#3]{\glsdesc{#1}{#2}{#3}}
2476 \def\@Acrlong#1#2[#3]{\Glsdesc{#1}{#2}{#3}}
2477 \def\@ACRlong#1#2[#3]{\GLSdesc{#1}{#2}{#3}}
```

Plural long form:

```
2478 \def\@acrlongpl#1#2[#3]{\glsdescplural{#1}{#2}{#3}}
2479 \def\@Acrlongpl#1#2[#3]{\Glsdescplural{#1}{#2}{#3}}
2480 \def\@ACRlongpl#1#2[#3]{\GLSdescplural{#1}{#2}{#3}}
```

Full form:

```
2481 \def\@acrfull#1#2[#3]{\glsdesc{#1}{#2}{#3}%
2482   (\@glstext{#1}{#2}{#3})}%
2483 \def\@Acrfull#1#2[#3]{\Glsdesc{#1}{#2}{#3}%
2484   (\@Glstext{#1}{#2}{#3})}%
2485 \def\@ACRfull#1#2[#3]{\GLSdesc{#1}{#2}{#3}%
2486   (\@GLStext{#1}{#2}{#3})}
```

Plural full form:

```
2487 \def\@acrfullpl#1#2[#3]{\@glsdescplural{#1}{#2}[#3]
2488   (\@glsplural{#1}{#2}[#3])}
2489 \def\@Acrfullpl#1#2[#3]{\@Glsdesctext{#1}{#2}[#3]
2490   (\@glsplural{#1}{#2}[#3])}
2491 \def\@ACRfullpl#1#2[#3]{\@GLSdesctext{#1}{#2}[#3]
2492   (\@GLSplural{#1}{#2}[#3])}
```

Redefine `\acronymfont` if small caps required. The plural suffix is set in an upright font so that it remains in normal lower case, otherwise it looks as though it's part of the acronym.

```
2493 \ifglsacrsmalls
2494   \renewcommand*\acronymfont[1]{\textsc{#1}}%
2495   \renewcommand*\acrpluralsuffix{%
2496     \textup{\glspluralsuffix}}%
2497 \else
2498   \ifglsacrsmaller
2499     \renewcommand*\acronymfont[1]{\textsmaller{#1}}%
2500   \fi
2501 \fi
```

Check for option clash

```
2502 \ifglsacrdua
2503   \PackageError{glossaries}{Option clash: `footnote' and `dua'
2504   can't both be set}{}%
2505 \fi
2506 \else
```

No footnotes required.

```
2507 \ifthenelse{\boolean{glsacrsmalls}\or\boolean{glsacrsmaller}}{%
```

Neither footnote nor description required. Use the `symbol` key to store the short form and `first` to store the long form.

```
2508 \renewcommand{\newacronym}[4][]{%
2509   \newglossaryentry{#2}{type=\acronymtype,%
2510   name={\acronymfont{#3}},%
2511   sort={#3},%
2512   text={\@glo@symbol},%
2513   plural={\@glo@symbolplural},%
2514   first={#4},%
2515   firstplural={#4\acrpluralsuffix},%
2516   description={\@glo@first},%
2517   descriptionplural={\@glo@firstplural},%
2518   symbol={#3},%
2519   symbolplural={#3\acrpluralsuffix},%
2520   #1}}
```

Set up the commands to make a note of the keys to store the long and short forms:

```
2521 \def\glsshortkey{symbol}%
2522 \def\glsshortpluralkey{symbolplural}%
2523 \def\glslongkey{first}%
2524 \def\glslongpluralkey{firstplural}%
```

Change the display since `first` only contains long form.

```
2525 \def\glsdisplayfirst[\acronymtype]{#1#4 (\firstacronymfont{#3})}
2526 \def\glsdisplay[\acronymtype]{\acronymfont{#1}#4}
```

Redefine \acronymfont if small caps required. The plural suffix is set in an upright font so that it remains in normal lower case, otherwise it looks as though it's part of the acronym.

```

2527     \ifglsacrsmallsCaps
2528         \renewcommand*\acronymfont[1]{\textsc{#1}}
2529         \renewcommand*\acrpluralsuffix{%
2530             \textup{\glspuralsuffix}}%
2531     \else
2532         \renewcommand*\acronymfont[1]{\textsmaller{#1}}
2533     \fi

```

Set up short cuts. Short form:

```

2534     \def\acrshort#1#2[#3]{\acronymfont{\glstext0{#1}{#2}{#3}}}
2535     \def\Acrshort#1#2[#3]{\acronymfont{\Glstext0{#1}{#2}{#3}}}
2536     \def\ACRshort#1#2[#3]{\acronymfont{\GLSText0{#1}{#2}{#3}}}

```

Plural short form:

```

2537     \def\acrshortpl#1#2[#3]{\acronymfont{\glsplural{#1}{#2}{#3}}}
2538     \def\Acrshortpl#1#2[#3]{\acronymfont{\Glsplural{#1}{#2}{#3}}}
2539     \def\ACRshortpl#1#2[#3]{\acronymfont{\GLSplural{#1}{#2}{#3}}}

```

Long form:

```

2540     \def\acrlong#1#2[#3]{\glsfirst{#1}{#2}{#3}}
2541     \def\Acrlong#1#2[#3]{\Glsfirst{#1}{#2}{#3}}
2542     \def\ACRlong#1#2[#3]{\GLSfirst{#1}{#2}{#3}}

```

Plural long form:

```

2543     \def\acrlongpl#1#2[#3]{\glsfirstplural{#1}{#2}{#3}}
2544     \def\Acrlongpl#1#2[#3]{\Glsfirstplural{#1}{#2}{#3}}
2545     \def\ACRlongpl#1#2[#3]{\GLSfirstplural{#1}{#2}{#3}}

```

Full form:

```

2546     \def\acrfull#1#2[#3]{\glsfirst{#1}{#2}{#3}%
2547         (\acronymfont{\glstext0{#1}{#2}{#3}})}
2548     \def\Acrfull#1#2[#3]{\Glsfirst{#1}{#2}{#3}%
2549         (\acronymfont{\Glstext0{#1}{#2}{#3}})}
2550     \def\ACRfull#1#2[#3]{\GLSfirst{#1}{#2}{#3}%
2551         (\acronymfont{\GLSText0{#1}{#2}{#3}})}

```

Plural full form:

```

2552     \def\acrfullpl#1#2[#3]{\glsfirstplural{#1}{#2}{#3}%
2553         (\acronymfont{\glsplural{#1}{#2}{#3}})}
2554     \def\Acrfullpl#1#2[#3]{\Glsfirstplural{#1}{#2}{#3}%
2555         (\acronymfont{\Glsplural{#1}{#2}{#3}})}
2556     \def\ACRfullpl#1#2[#3]{\GLSfirstplural{#1}{#2}{#3}%
2557         (\acronymfont{\GLSplural{#1}{#2}{#3}})}

```

check for option clash

```

2558     \ifglsacrdua
2559         \ifglsacrsmallsCaps
2560             \PackageError{glossaries}{Option clash: `smallcaps' and `dua'
2561             can't both be set}{}
2562         \else
2563             \PackageError{glossaries}{Option clash: `smaller' and `dua'
2564             can't both be set}{}
2565         \fi

```

```

2566      \fi
2567  }{%

```

Should acronyms always be expanded?

```

2568  \ifglsacrdua
2569    \renewcommand{\newacronym}[4][]{%
2570      \newglossaryentry{#2}{type=\acronymtype,%
2571        name={#3},%
2572        text={#4},%
2573        plural={#4\acrpluralsuffix},%
2574        description={#4},%
2575        symbol={#3},%
2576        symbolplural={#3\acrpluralsuffix},%
2577        #1}%

```

Set up the commands to make a note of the keys to store the long and short forms:

```

2578  \def\glsshortkey{symbol}%
2579  \def\glsshortpluralkey{symbolplural}%
2580  \def\glslongkey{text}%
2581  \def\glslongpluralkey{plural}%

```

Set the display

```

2582  \def\glsdisplayfirst[\acronymtype]{#1#4}
2583  \def\glsdisplay[\acronymtype]{#1#4}

```

Set up short cuts. Short form:

```

2584  \def\@acrshort#1#2[#3]{\@glssymbol{#1}{#2}{#3}}
2585  \def\@Acrshort#1#2[#3]{\@Glssymbol{#1}{#2}{#3}}
2586  \def\@ACRshort#1#2[#3]{\@GLSsymbol{#1}{#2}{#3}}

```

Plural short form:

```

2587  \def\@acrshortpl#1#2[#3]{\@glssymbolplural{#1}{#2}{#3}}
2588  \def\@Acrshortpl#1#2[#3]{\@Glssymbolplural{#1}{#2}{#3}}
2589  \def\@ACRshortpl#1#2[#3]{\@GLSsymbolplural{#1}{#2}{#3}}

```

Long form:

```

2590  \def\@acrlong#1#2[#3]{\@glstext{#1}{#2}{#3}}
2591  \def\@Acrlong#1#2[#3]{\@Glstext{#1}{#2}{#3}}
2592  \def\@ACRlong#1#2[#3]{\@GLStext{#1}{#2}{#3}}

```

Plural long form:

```

2593  \def\@acrlongpl#1#2[#3]{\@glsplural{#1}{#2}{#3}}
2594  \def\@Acrlongpl#1#2[#3]{\@Glsplural{#1}{#2}{#3}}
2595  \def\@ACRlongpl#1#2[#3]{\@GLSplural{#1}{#2}{#3}}

```

Full form:

```

2596  \def\@acrfull#1#2[#3]{\@glstext{#1}{#2}{#3}%
2597    (\acronymfont{\@glssymbol{#1}{#2}{#3}})}
2598  \def\@Acrfull#1#2[#3]{\@Glstext{#1}{#2}{#3}%
2599    (\acronymfont{\@Glssymbol{#1}{#2}{#3}})}
2600  \def\@ACRfull#1#2[#3]{\@GLStext{#1}{#2}{#3}%
2601    (\acronymfont{\@GLSsymbol{#1}{#2}{#3}})}

```

Plural full form:

```

2602  \def\@acrfullpl#1#2[#3]{\@glsplural{#1}{#2}{#3}%
2603    (\acronymfont{\@glssymbolplural{#1}{#2}{#3}})}
2604  \def\@Acrfullpl#1#2[#3]{\@Glsplural{#1}{#2}{#3}%
2605    (\acronymfont{\@Glssymbolplural{#1}{#2}{#3}})}

```

```

2606      \def\@ACRfullpl#1#2[#3]{\@GLSplural@{#1}{#2}[#3]
2607          (\acronymfont{\@GLSsymbolplural@{#1}{#2}[#3]})}
2608          \fi
2609      }%
2610  \fi
2611 \fi

    Define synonyms if required

2612 \ifglsacrshortcuts
    Short form

\acs
2613 \let\acs\acrshort
    First letter uppercase short form

\Acs
2614 \let\Acs\Acrshort
    Plural short form

\acsp
2615 \let\acsp\acrshortpl
    First letter uppercase plural short form

\Acsp
2616 \let\Acsp\Acrshortpl
    Long form

\acl
2617 \let\acl\acrlong
    Plural long form

\aclp
2618 \let\aclp\acrlongpl
    First letter upper case long form

\Acl
2619 \let\Acl\Acrlong
    First letter upper case plural long form

\Acip
2620 \let\Acip\Acrlongpl
    Full form

\acf
2621 \let\acf\acrfull
    Plural full form

\acfp
2622 \let\acfp\acrfullpl

```

```

First letter upper case full form
\Acf
2623 \let\Acf\Acrfull

First letter upper case plural full form
\Acfp
2624 \let\Acfp\Acrfullpl

Standard form
\ac
2625 \let\ac\gls

First upper case standard form
\Ac
2626 \let\Ac\Gls

Standard plural form
\acp
2627 \let\acp\glsp

Standard first letter upper case plural form
\Acp
2628 \let\Acp\Glsp
2629 \fi

```

5.18 Predefined Glossary Styles

The `glossaries` bundle comes with some predefined glossary styles. These need to be loaded now for the `style` option to use them.

First, the glossary hyper-navigation commands need to be loaded.

```
2630 \RequirePackage{glossary-hypernav}
```

The styles that use list-like environments. These are not loaded if the `nolist` option is used:

```
2631 \@gls@loadlist
```

The styles that use the `longtable` environment. These are not loaded if the `nolong` package option is used.

```
2632 \@gls@loadlong
```

The styles that use the `supertabular` environment. These are not loaded if the `nosuper` package option is used or if the `supertabular` package isn't installed.

```
2633 \@gls@loadsper
```

The tree-like styles. These are not loaded if the `notree` package option is used.

```
2634 \@gls@loadtree
```

The default glossary style is set according to the `style` package option, but can be overridden by `\glossarystyle`. The style must be defined at this point.

```
2635 \ifx\@glossary@default@style\relax
```

```
2636 \else
```

```
2637 \glossarystyle{\@glossary@default@style}
```

```
2638 \fi
```

6 Mfirstuc Documented Code

```
2639 \NeedsTeXFormat{LaTeX2e}
2640 \ProvidesPackage{mfirstuc}[2008/12/22 v1.03 (NLCT)]
\makefirstuc Syntax:
\makefirstuc{\text}
Makes the first letter uppercase, but will skip initial control sequences if they
are followed by a group and make the first thing in the group uppercase,
unless the group is empty. Thus \makefirstuc{abc} will produce: Abc,
\makefirstuc{\ae bc} will produce: Äbc, but \makefirstuc{\emph{abc}} will
produce Abc. This is required by \Gls and \Glspl.

2641 \newif\if@gls@scs
2642 \def\makefirstuc#1{%
2643   \def\gls@argi{#1}%
2644   \ifx\gls@argi\empty
2645     \else
2646       \def\@gls@tmp{\ #1}%
2647       \onelevel@sanitize\@gls@tmp
2648       \expandafter\@gls@checkcs\@gls@tmp\relax\relax
2649       \if@gls@scs
2650         \gls@getbody #1{}\@nil
2651         \ifx\gls@rest\empty
2652           \gls@makefirstuc{#1}%
2653         \else
2654           \expandafter\@gls@split\@gls@rest\@nil
2655           \ifx\gls@first\empty
2656             \gls@makefirstuc{#1}%
2657           \else
2658             \gls@body{\expandafter\gls@makefirstuc\@gls@first}\@gls@rest%
2659           \fi
2660         \fi
2661       \else
2662         \gls@makefirstuc{#1}%
2663       \fi
2664     \fi
2665 }
```

Put first argument in \gls@first and second argument in \gls@rest:

```
2666 \def\@gls@split#1#2\@nil{\def\gls@first{#1}\def\gls@rest{#2}}
2667 \def\@gls@checkcs#1 #2#3\relax{%
2668   \def\gls@argi{#1}\def\gls@argii{#2}%
2669   \ifx\gls@argi\gls@argii
2670     \glscstrue
2671   \else
2672     \glscsfalse
2673   \fi
2674 }
```

Make first thing upper case:

```
2675 \def\gls@makefirstuc#1{\MakeUppercase #1}
```

Get the first grouped argument and stores in \gls@body.

```
2676 \def\gls@getbody#1{\def\gls@body{#1}\gls@gobbletonil}
```

Scoup up everything to \nil and store in \@gls@rest:

```
2677 \def\@gls@gobbletonil#1\@nil{\def\@gls@rest{#1}}
```

\xmakefirstuc Expand argument once before applying \makefirstuc (added v1.01).

```
2678 \newcommand*{\xmakefirstuc}[1]{%
2679 \expandafter\makefirstuc\expandafter{#1}}
```

7 Glossary Styles

7.1 Glossary hyper-navigation definitions (glossary-hypernav package)

Package Definition:

```
2680 \ProvidesPackage{glossary-hypernav}[2007/07/04 v1.01 (NLCT)]
```

The commands defined in this package are provided to help navigate around the groups within a glossary (see subsection 5.15.) \printglossary (and \printglossaries) set \@glo@type to the label of the current glossary. This is used to create a unique hypertarget in the event of multiple glossaries.

```
\glsnavhyperlink[<type>]{<label>}{<text>}
```

This command makes *<text>* a hyperlink to the glossary group whose label is given by *<label>* for the glossary given by *<type>*.

```
\glsnavhyperlink
2681 \newcommand*{\glsnavhyperlink}[3][\@glo@type]{%
2682   \edef\gls@grplabel{#2}\protected@edef\gls@grptitle{#3}%
2683   \glslink{glsn:#1@#2}{#3}}
```

```
\glsnavhypertarget[<type>]{<label>}{<text>}
```

This command makes *<text>* a hypertarget for the glossary group whose label is given by *<label>* in the glossary given by *<type>*. If *<type>* is omitted, \@glo@type is used which is set by \printglossary to the current glossary label.

```
\glsnavhypertarget
2684 \newcommand*{\glsnavhypertarget}[3][\@glo@type]{%
  Add this group to the aux file for re-run check.
2685   \protected@write\auxout{}{\string\gls@hypergroup{#1}{#2}}%
  Add the target.
2686   \glstarget{glsn:#1@#2}{#3}%
  Check list of known groups to determine if a re-run is required.
2687   \expandafter\let
2688     \expandafter\gls@list\csname\gls@hypergrouplist@#1\endcsname
  Iterate through list and terminate loop if this group is found.
2689   \for\gls@elem:=\gls@list\do{%
2690     \ifthenelse{\equal{\gls@elem}{#2}}{\endfor}{}}
```

Check if list terminated prematurely.

```
2691 \if@endfor  
2692 \else
```

This group was not included in the list, so issue a warning.

```
2693 \PackageWarningNoLine{glossaries}{Navigation panel  
2694     for glossary type '#1'^^Jmissing group '#2'}%  
2695 \gdef\gls@hypergrouprerun{  
2696     \PackageWarningNoLine{glossaries}{Navigation panel  
2697     has changed. Rerun LaTeX}}%  
2698 \fi  
2699 }
```

\gls@hypergrouprerun Give a warning at the end if re-run required

```
2700 \let\gls@hypergrouprerun\relax  
2701 \AtEndDocument{\gls@hypergrouprerun}
```

\@gls@hypergroup This adds to (or creates) the command \@gls@hypergrouplist@*<glossary type>* which lists all groups for a given glossary, so that the navigation bar only contains those groups that are present. However it requires at least 2 runs to ensure the information is up-to-date.

```
2702 \newcommand*{\@gls@hypergroup}[2]{%  
2703 \@ifundefined{\gls@hypergrouplist@#1}{%  
2704     \expandafter\xdef\csname@gls@hypergrouplist@#1\endcsname{#2}}%  
2705 }%  
2706 \expandafter\let\expandafter\@gls@tmp  
2707     \csname@gls@hypergrouplist@#1\endcsname  
2708 \expandafter\xdef\csname@gls@hypergrouplist@#1\endcsname{  
2709     \@gls@tmp, #2}}%  
2710 }%  
2711 }
```

The \glsnavigation command displays a simple glossary group navigation. The symbol and number elements are defined separately, so that they can be suppressed if need be. Note that this command will produce a link to all 28 groups, but some groups may not be defined if there are groups that do not contain any terms, in which case you will get an undefined hyperlink warning. Now for the whole navigation bit:

```
\glsnavigation  
2712 \newcommand*{\glsnavigation}{%  
2713 \def\@gls@between{}%  
2714 \@ifundefined{\gls@hypergrouplist@\glo@type}{%  
2715     \def\@gls@list{}%  
2716 }%  
2717 \expandafter\let\expandafter\@gls@list  
2718     \csname@gls@hypergrouplist@\glo@type\endcsname  
2719 }%  
2720 \foreach\gls@tmp:=\gls@list\do{  
2721     \gls@between  
2722     \glsnavhyperlink{\gls@tmp}{\glsgetgroupitle{\gls@tmp}}%  
2723     \let\@gls@between\glshypernavsep%  
2724 }%  
2725 }
```

\glshypernavsep Separator for the hyper navigation bar.

```
2726 \newcommand*\{glshypernavsep}{\space{textbar}\space}
```

The \glssymbolnav produces a simple navigation set of links for just the symbol and number groups. This used to be used at the start of \glsnavigation. This command is no longer needed.

\glssymbolnav

```
2727 \newcommand*\{glssymbolnav}{%
2728 \glsnavhyperlink{glssymbols}{\glsgetgroup{glssymbols}}%
2729 \glshypernavsep
2730 \glsnavhyperlink{glsnumbers}{\glsgetgroup{glsnumbers}}%
2731 \glshypernavsep
2732 }
```

7.2 List Style (glossary-list.sty)

The glossary-list style file defines glossary styles that use the `description` environment. Note that since the entry name is placed in the optional argument to the `\item` command, it will appear in a bold font by default.

```
2733 \ProvidesPackage{glossary-list}[2009/01/14 v1.05 (NLCT)]
```

list The list glossary style uses the `description` environment. The group separator `\glsgroupskip` is redefined as `\indexspace` which produces a gap between groups. The glossary heading and the group headings do nothing. Sub-entries immediately follow the main entry without the sub-entry name. This style does not use the entry's symbol. This is used as the default style for the `glossaries` package.

```
2734 \newglossarystyle{list}{%
```

Use `description` environment:

```
2735 \renewenvironment{theglossary}{%
2736   {\begin{description}}{\end{description}}}
```

No header at the start of the environment:

```
2737 \renewcommand*\{glossaryheader}{}
```

No group headings:

```
2738 \renewcommand*\{glsgroupheading}{[1]}
```

Main (level 0) entries start a new item in the list:

```
2739 \renewcommand*\{glossaryentryfield}{[5]}%
2740   \item[\glstarget{##1}{##2}] ##3\glspostdescription\space ##5}%
```

Sub-entries continue on the same line:

```
2741 \renewcommand*\{glossarysubentryfield}{[6]}%
2742   \glstarget{##2}{\strut}##4\glspostdescription\space ##6.}%
2743 % \end{macrocode}
2744 % Add vertical space between groups:
2745 % \begin{macrocode}
2746 \renewcommand*\{glsgroupskip}{\indexspace}%
2747 }
```

listgroup The `listgroup` style is like the `list` style, but the glossary groups have headings.

```
2748 \newglossarystyle{listgroup}{%
```

Base it on the `list` style:

```
2749 \glossarystyle{list}%
```

Each group has a heading:

```
2750 \renewcommand*\{\glsgroupheading}{1}{\item[\glsgroupname]}
```

listhypergroup The `listhypergroup` style is like the `listgroup` style, but has a set of links to the groups at the start of the glossary.

```
2751 \newglossarystyle{listhypergroup}{%
```

Base it on the `list` style:

```
2752 \glossarystyle{list}%
```

Add navigation links at the start of the environment:

```
2753 \renewcommand*\{\glossaryheader}{%
```

```
2754 \item[\glsnavigation]}
```

Each group has a heading with a hypertarget:

```
2755 \renewcommand*\{\glsgroupheading}{1}{%
```

```
2756 \item[\glshypertarget{\#\#1}{\glsgroupname}]}%
```

altlist The `altlist` glossary style is like the `list` style, but places the description on a new line. Sub-entries follow in separate paragraphs without the sub-entry name. This style does not use the entry's symbol.

```
2757 \newglossarystyle{altlist}{%
```

Base it on the `list` style:

```
2758 \glossarystyle{list}%
```

Main (level 0) entries start a new item in the list with a line break after the entry name:

```
2759 \renewcommand*\{\glossaryentryfield}{5}{%
```

```
2760 \item[\glstarget{\#\#1}{\#\#2}]\mbox{}\\
```

```
2761 ##3\glspostdescription\\space ##5}%
```

Sub-entries start a new paragraph:

```
2762 \renewcommand*\{\glossarysubentryfield}{6}{%
```

```
2763 \par\glstarget{\#\#2}{\strut}\\##4\glspostdescription\\space ##6}%
```

```
2764 }
```

altlistgroup The `altlistgroup` glossary style is like the `altlist` style, but the glossary groups have headings.

```
2765 \newglossarystyle{altlistgroup}{%
```

Base it on the `altlist` style:

```
2766 \glossarystyle{altlist}%
```

Each group has a heading:

```
2767 \renewcommand*\{\glsgroupheading}{1}{\item[\glsgroupname]}
```

altlisthypergroup The `altlisthypergroup` glossary style is like the `altlistgroup` style, but has a set of links to the groups at the start of the glossary.

```
2768 \newglossarystyle{altlisthypergroup}{%
```

Base it on the `altlist` style:

```
2769 \glossarystyle{altlist}%
```

Add navigation links at the start of the environment:

```
2770 \renewcommand*{\glossaryheader}{%
2771   \item[\glsnavigation]}%
```

Each group has a heading with a hypertarget:

```
2772 \renewcommand*{\glsgroupheading}[1]{%
2773   \item[\glsnavhypertarget{##1}{\glsgetgroupname{##1}}]}
```

- listdotted** The listdotted glossary style was supplied by Axel Menzel. I've modified it slightly so that the distance from the start of the name to the end of the dotted line is specified by `\glslistdottedwidth`. Note that this style ignores the page numbers as well as the symbol. Sub-entries are displayed in the same way as top-level entries.

```
2774 \newglossarystyle{listdotted}{%
```

Base it on the `list` style:

```
2775 \glossarystyle{list}{%
```

Each main (level 0) entry starts a new item:

```
2776 \renewcommand*{\glossaryentryfield}[5]{%
2777   \item[]\makebox[\glslistdottedwidth][1]{\glstarget{##1}{##2}}%
2778   \unskip\leaders\hbox to 2.9mm{\hss.}\hfill\strut}##3}%
```

Sub entries have the same format as main entries:

```
2779 \renewcommand*{\glossarysubentryfield}[6]{%
2780   \item[]\makebox[\glslistdottedwidth][1]{\glstarget{##2}{##3}}%
2781   \unskip\leaders\hbox to 2.9mm{\hss.}\hfill\strut}##4}%
2782 }
```

```
\glslistdottedwidth
```

```
2783 \newlength\glslistdottedwidth
2784 \setlength{\glslistdottedwidth}{.5\linewidth}
```

- sublistdotted** This style is similar to the `glostylelistdotted` style, except that the main entries just have the name displayed.

```
2785 \newglossarystyle{sublistdotted}{%
```

Base it on the `listdotted` style:

```
2786 \glossarystyle{listdotted}{%
```

Main (level 0) entries just display the name:

```
2787 \renewcommand*{\glossaryentryfield}[5]{%
2788   \item[\glstarget{##1}{##2}]}%
2789 }
```

7.3 Glossary Styles using `longtable` (the `glossary-long` package)

The glossary styles defined in the `glossary-long` package used the `longtable` environment in the glossary.

```
2790 \ProvidesPackage{glossary-long}[2009/01/14 v1.03 (NLCT)]
```

Requires the `longtable` package:

```
2791 \RequirePackage{longtable}
```

`\glsdescwidth` This is a length that governs the width of the description column. (There's a chance that the user may specify `nolong` and then load `glossary-long` later, in which case `\glsdescwidth` may have already been defined by `glossary-super`. The same goes for `\glspagelistwidth`.)

```
2792 \@ifundefined{\glsdescwidth}{%
2793   \newlength\glsdescwidth
2794   \setlength{\glsdescwidth}{0.6\linewidth}
2795 }{}
```

`\glspagelistwidth` This is a length that governs the width of the page list column.

```
2796 \@ifundefined{\glspagelistwidth}{%
2797   \newlength\glspagelistwidth
2798   \setlength{\glspagelistwidth}{0.1\linewidth}
2799 }{}
```

`long` The `long` glossary style command which uses the `longtable` environment:

```
2800 \newglossarystyle{long}{%
```

 Use `longtable` with two columns:

```
2801 \renewenvironment{theglossary}{%
2802   \begin{longtable}{lp{\glsdescwidth}}}{%
2803   \end{longtable}}
```

 Do nothing at the start of the environment:

```
2804 \renewcommand*\glossaryheader{}{%
```

 No heading between groups:

```
2805 \renewcommand*\glsgroupheading[1]{}{%
```

 Main (level 0) entries displayed in a row:

```
2806 \renewcommand*\glossaryentryfield[5]{%
2807   \glstarget{\#1}{\#2} & \#3\glspostdescription\space \#5\\}{%
```

 Sub entries displayed on the following row without the name:

```
2808 \renewcommand*\glossarysubentryfield[6]{%
2809   & \glstarget{\#2}{\strut}\#4\glspostdescription\space \#6\\}{%
```

 Blank row between groups:

```
2810 \renewcommand*\glsgroupskip{}{ & \\}{%
2811 }
```

`longborder` The `longborder` style is like the above, but with horizontal and vertical lines:

```
2812 \newglossarystyle{longborder}{%
```

 Base it on the `glostylelong` style:

```
2813 \glossarystyle{long}{%
```

 Use `longtable` with two columns with vertical lines between each column:

```
2814 \renewenvironment{theglossary}{%
2815   \begin{longtable}{|l|p{\glsdescwidth}|}{\end{longtable}}{}}
```

 Place horizontal lines at the head and foot of the table:

```
2816 \renewcommand*\glossaryheader{}{\hline\endhead\hline\endfoot}{%
2817 }
```

`longheader` The `longheader` style is like the `long` style but with a header:

```
2818 \newglossarystyle{longheader}{%
```

Base it on the `glostylelong` style:

```
2819 \glossarystyle{long}%
```

Set the table's header:

```
2820 \renewcommand*{\glossaryheader}{%
2821   \bfseries \entryname & \bfseries \descriptionname\\endhead}%
2822 }
```

longheaderborder The `longheaderborder` style is like the `long` style but with a header and border:

```
2823 \newglossarystyle{longheaderborder}{%
```

Base it on the `glostylelongborder` style:

```
2824 \glossarystyle{longborder}%
```

Set the table's header and add horizontal line to table's foot:

```
2825 \renewcommand*{\glossaryheader}{%
2826   \hline\bfseries \entryname & \bfseries \descriptionname\\hline
2827   \endhead
2828   \hline\endfoot}%
2829 }
```

long3col The `long3col` style is like `long` but with 3 columns

```
2830 \newglossarystyle{long3col}{%
```

Use a `longtable` with 3 columns:

```
2831 \renewenvironment{theglossary}{%
2832   \begin{longtable}{lp{\glscdescwidth}p{\glspagelistwidth}}{%
2833     \end{longtable}}
```

No table header:

```
2834 \renewcommand*{\glossaryheader}{}%
```

No headings between groups:

```
2835 \renewcommand*{\glsgroupheading}[1]{}%
```

Main (level 0) entries on a row (name in first column, description in second column, page list in last column):

```
2836 \renewcommand*{\glossaryentryfield}[5]{%
2837   \glstarget{##1}{##2} & ##3 & ##5\\}%
```

Sub-entries on a separate row (no name, description in second column, page list in third column):

```
2838 \renewcommand*{\glossarysubentryfield}[6]{%
2839   & \glstarget{##2}{\strut}##4 & ##6\\}%
```

Blank row between groups:

```
2840 \renewcommand*{\glsgroupskip}{\&\}\\%
2841 }
```

long3colborder The `long3colborder` style is like the `long3col` style but with a border:

```
2842 \newglossarystyle{long3colborder}{%
```

Base it on the `glostylelong3col` style:

```
2843 \glossarystyle{long3col}%
```

Use a `longtable` with 3 columns with vertical lines around them:

```
2844 \renewenvironment{theglossary}{%
2845   \begin{longtable}{|l|p{\glscdescwidth}|p{\glspagelistwidth}|}%
2846     \end{longtable}}
```

Place horizontal lines at the head and foot of the table:

```
2847 \renewcommand*{\glossaryheader}{\hline\endhead\hline\endfoot}%
2848 }
```

long3colheader The **long3colheader** style is like **long3col** but with a header row:

```
2849 \newglossarystyle{long3colheader}{%
```

Base it on the **glostylelong3col** style:

```
2850 \glossarystyle{long3col}{%
```

Set the table's header:

```
2851 \renewcommand*{\glossaryheader}{%
2852   \bfseries\entryname&\bfseries\descriptionname&
2853   \bfseries\pagelistname\\endhead}%
2854 }
```

long3colheaderborder The **long3colheaderborder** style is like the above but with a border

```
2855 \newglossarystyle{long3colheaderborder}{%
```

Base it on the **glostylelong3colborder** style:

```
2856 \glossarystyle{long3colborder}{%
```

Set the table's header and add horizontal line at table's foot:

```
2857 \renewcommand*{\glossaryheader}{%
2858   \hline
2859   \bfseries\entryname&\bfseries\descriptionname&
2860   \bfseries\pagelistname\\hline\endhead
2861   \hline\endfoot}%
2862 }
```

long4col The **long4col** style has four columns where the third column contains the value of the associated **symbol** key.

```
2863 \newglossarystyle{long4col}{%
```

Use a **longtable** with 4 columns:

```
2864 \renewenvironment{theglossary}{%
2865   \begin{longtable}{llll}%
2866   \end{longtable}}%
```

No table header:

```
2867 \renewcommand*{\glossaryheader}{}
```

No group headings:

```
2868 \renewcommand*{\glsgroupheading}[1]{}
```

Main (level 0) entries on a single row (name in first column, description in second column, symbol in third column, page list in last column):

```
2869 \renewcommand*{\glossaryentryfield}[5]{%
2870   \glstarget{##1}{##2} & ##3 & ##4 & ##5\\}%
```

Sub entries on a single row with no name (description in second column, symbol in third column, page list in last column):

```
2871 \renewcommand*{\glossarysubentryfield}[6]{%
2872   & \glstarget{##2}{\strut}##4 & ##5 & ##6\\}%
```

Blank row between groups:

```
2873 \renewcommand*{\glsgroupskip}{ & & &\\}%
2874 }
```

long4colheader The `long4colheader` style is like `long4col` but with a header row.

2875 `\newglossarystyle{long4colheader}{%`

Base it on the `glostylelong4col` style:

2876 `\glossarystyle{long4col}{%`

Table has a header:

2877 `\renewcommand*\glossaryheader{%`

2878 `\bfseries\entryname&\bfseries\descriptionname&`

2879 `\bfseries \symbolname&`

2880 `\bfseries\pagelistname\\endhead}{%`

2881 `}`

long4colborder The `long4colborder` style is like `long4col` but with a border.

2882 `\newglossarystyle{long4colborder}{%`

Base it on the `glostylelong4col` style:

2883 `\glossarystyle{long4col}{%`

Use a `longtable` with 4 columns surrounded by vertical lines:

2884 `\renewenvironment{theglossary}{%`

2885 `{\begin{longtable}{|l|l|l|l|}}{%`

2886 `{\end{longtable}}{}}`

Add horizontal lines to the head and foot of the table:

2887 `\renewcommand*\glossaryheader{\hline\endhead\hline\endfoot}{%`

2888 `}`

long4colheaderborder The `long4colheaderborder` style is like the above but with a border.

2889 `\newglossarystyle{long4colheaderborder}{%`

Base it on the `glostylelong4col` style:

2890 `\glossarystyle{long4col}{%`

Use a `longtable` with 4 columns surrounded by vertical lines:

2891 `\renewenvironment{theglossary}{%`

2892 `{\begin{longtable}{|l|l|l|l|}}{%`

2893 `{\end{longtable}}{}}`

Add table header and horizontal line at the table's foot:

2894 `\renewcommand*\glossaryheader{%`

2895 `\hline\bfseries\entryname&\bfseries\descriptionname&`

2896 `\bfseries \symbolname&`

2897 `\bfseries\pagelistname\\hline\endhead\hline\endfoot}{%`

2898 `}`

altnlong4col The `altnlong4col` style is like the `long4col` style but can have multiline descriptions and page lists.

2899 `\newglossarystyle{altnlong4col}{%`

Base it on the `glostylelong4col` style:

2900 `\glossarystyle{long4col}{%`

Use a `longtable` with 4 columns where the second and last columns may have multiple lines in each row:

2901 `\renewenvironment{theglossary}{%`

2902 `{\begin{longtable}{lp{\glsdescwidth}lp{\glspagelistwidth}}{}}`

2903 `{\end{longtable}}{}}`

2904 `}`

altnlong4colheader The altnlong4colheader style is like altnlong4col but with a header row.

2905 \newglossarystyle{altnlong4colheader}{%

Base it on the glostylelong4colheader style:

2906 \glossarystyle{long4colheader}{%

Use a longtable with 4 columns where the second and last columns may have multiple lines in each row:

2907 \renewenvironment{theglossary}{%

2908 {\begin{longtable}{lp{\glsdescwidth}lp{\glspagelistwidth}}}{%

2909 {\end{longtable}}{}}

2910 }

altnlong4colborder The altnlong4colborder style is like altnlong4col but with a border.

2911 \newglossarystyle{altnlong4colborder}{%

Base it on the glostylelong4colborder style:

2912 \glossarystyle{long4colborder}{%

Use a longtable with 4 columns where the second and last columns may have multiple lines in each row:

2913 \renewenvironment{theglossary}{%

2914 {\begin{longtable}{|l|p{\glsdescwidth}|l|p{\glspagelistwidth}|}}{}}

2915 {\end{longtable}}{}}

2916 }

altnlong4colheaderborder The altnlong4colheaderborder style is like the above but with a header as well as a border.

2917 \newglossarystyle{altnlong4colheaderborder}{%

Base it on the glostylelong4colheaderborder style:

2918 \glossarystyle{long4colheaderborder}{%

Use a longtable with 4 columns where the second and last columns may have multiple lines in each row:

2919 \renewenvironment{theglossary}{%

2920 {\begin{longtable}{|l|p{\glsdescwidth}|l|p{\glspagelistwidth}|}}{}}

2921 {\end{longtable}}{}}

2922 }

7.4 Glossary Styles using supertabular environment (glossary-super package)

The glossary styles defined in the glossary-super package use the supertabular environment.

2923 \ProvidesPackage{glossary-super}[2009/01/14 v1.03 (NLCT)]

Requires the supertabular package:

2924 \RequirePackage{supertabular}

\glsdescwidth This is a length that governs the width of the description column. This may already have been defined if glossary-long has been loaded.

2925 \@ifundefined{\glsdescwidth}{%

2926 \newlength\glsdescwidth

2927 \setlength{\glsdescwidth}{0.6\linewidth}

2928 }{}}

\glspagelistwidth This is a length that governs the width of the page list column. This may already have been defined if `glossary-long` has been loaded.

```
2929 \ifundefined{\glspagelistwidth}{%
2930   \newlength{\glspagelistwidth}%
2931   \setlength{\glspagelistwidth}{0.1\linewidth}%
2932 }
```

super The `super` glossary style uses the `supertabular` environment (it uses lengths defined in the `glossary-long` package.)

```
2933 \newglossarystyle{super}{%
```

Put the glossary in a `supertabular` environment with two columns and no head or tail:

```
2934 \renewenvironment{theglossary}{%
2935   {\tablehead{}\tabletail{}%
2936   \begin{supertabular}{lp{\glsdescwidth}}}}%
2937 \end{supertabular}}
```

Do nothing at the start of the table:

```
2938 \renewcommand*{\glossaryheader}{}
```

No group headings:

```
2939 \renewcommand*{\glsgroupheading}[1]{}
```

Main (level 0) entries put in a row (name in first column, description and page list in second column):

```
2940 \renewcommand*{\glossaryentryfield}[5]{%
2941   \glstarget{\#1}{\#2} & \#3\glspostdescription\space \#5\\}%
```

Sub entries put in a row (no name, description and page list in second column):

```
2942 \renewcommand*{\glossarysubentryfield}[6]{%
2943   & \glstarget{\#2}{\strut}\#4\glspostdescription\space \#6\\}%
```

Blank row between groups:

```
2944 \renewcommand*{\glsgroupskip}{\& \\}%
2945 }
```

superborder The `superborder` style is like the above, but with horizontal and vertical lines:

```
2946 \newglossarystyle{superborder}{%
```

Base it on the `glostypesuper` style:

```
2947 \glossarystyle{super}{%
```

Put the glossary in a `supertabular` environment with two columns and a horizontal line in the head and tail:

```
2948 \renewenvironment{theglossary}{%
2949   {\tablehead{\hline}\tabletail{\hline}%
2950   \begin{supertabular}{|l|p{\glsdescwidth}|}}%
2951 \end{supertabular}}%
2952 }
```

superheader The `superheader` style is like the `super` style, but with a header:

```
2953 \newglossarystyle{superheader}{%
```

Base it on the `glostypesuper` style:

```
2954 \glossarystyle{super}{%
```

Put the glossary in a `supertabular` environment with two columns, a header and no tail:

```
2955 \renewenvironment{theglossary}%
2956   {\tablehead{\bfseries \entryname & \bfseries \descriptionname\}}%
2957   \tabletail{}%
2958   \begin{supertabular}{lp{\glsdescwidth}}}%
2959   {\end{supertabular}}%
2960 }
```

superheaderborder The `superheaderborder` style is like the `super` style but with a header and border:

```
2961 \newglossarystyle{superheaderborder}{%
```

Base it on the `glostylesuper` style:

```
2962 \glossarystyle{super}%
```

Put the glossary in a `supertabular` environment with two columns, a header and horizontal lines above and below the table:

```
2963 \renewenvironment{theglossary}%
2964   {\tablehead{\hline\bfseries \entryname &
2965   \bfseries \descriptionname\hline}%
2966   \tabletail{\hline}%
2967   \begin{supertabular}{|l|p{\glsdescwidth}|}}%
2968   {\end{supertabular}}%
2969 }
```

super3col The `super3col` style is like the `super` style, but with 3 columns:

```
2970 \newglossarystyle{super3col}{%
```

Put the glossary in a `supertabular` environment with three columns and no head or tail:

```
2971 \renewenvironment{theglossary}%
2972   {\tablehead{}\tabletail{}%
2973   \begin{supertabular}{lp{\glsdescwidth}p{\glspagelistwidth}}}}%
2974 {\end{supertabular}}%
```

Do nothing at the start of the table:

```
2975 \renewcommand*{\glossaryheader}{}%
```

No group headings:

```
2976 \renewcommand*{\glsgroupheading}[1]{}%
```

Main (level 0) entries on a row (name in first column, description in second column, page list in last column):

```
2977 \renewcommand*{\glossaryentryfield}[5]{%
2978   \glstarget{##1}{##2} & ##3 & ##5\\}%
```

Sub entries on a row (no name, description in second column, page list in last column):

```
2979 \renewcommand*{\glossarysubentryfield}[6]{%
2980   & \glstarget{##2}{\strut}##4 & ##6\\}%
```

Blank row between groups:

```
2981 \renewcommand*{\glsgroupskip}{ & &\\}%
2982 }
```

super3colborder The `super3colborder` style is like the `super3col` style, but with a border:

```
2983 \newglossarystyle{super3colborder}{%
```

Base it on the `glostylesuper3col` style:

```
2984 \glossarystyle{super3col}%
```

Put the glossary in a `supertabular` environment with three columns and a horizontal line in the head and tail:

```
2985 \renewenvironment{theglossary}%
2986   {\tablehead{\hline}\tabletail{\hline}%
2987   \begin{supertabular}{|l|p{\glsdescwidth}|p{\glspagelistwidth}|}{}%
2988   \end{supertabular}}%
2989 }
```

super3colheader The `super3colheader` style is like the `super3col` style but with a header row:

```
2990 \newglossarystyle{super3colheader}{%
```

Base it on the `glostylesuper3col` style:

```
2991 \glossarystyle{super3col}%
```

Put the glossary in a `supertabular` environment with three columns, a header and no tail:

```
2992 \renewenvironment{theglossary}%
2993   {\tablehead{\bfseries\entryname\&\bfseries\descriptionname\&
2994   \bfseries\pagelistname\\}\tabletail{}%
2995   \begin{supertabular}{lp{\glsdescwidth}p{\glspagelistwidth}}{}%
2996   \end{supertabular}}%
2997 }
```

super3colheaderborder The `super3colheaderborder` style is like the `super3col` style but with a header and border:

```
2998 \newglossarystyle{super3colheaderborder}{%
```

Base it on the `glostylesuper3colborder` style:

```
2999 \glossarystyle{super3colborder}%
```

Put the glossary in a `supertabular` environment with three columns, a header with horizontal lines and a horizontal line in the tail:

```
3000 \renewenvironment{theglossary}%
3001   {\tablehead{\hline
3002   \bfseries\entryname\&\bfseries\descriptionname\&
3003   \bfseries\pagelistname\\}\hline\tabletail{\hline}%
3004   \begin{supertabular}{|l|p{\glsdescwidth}|p{\glspagelistwidth}|}{}%
3005   \end{supertabular}}%
3006 }
```

super4col The `super4col` glossary style has four columns, where the third column contains the value of the corresponding `symbol` key used when that entry was defined.

```
3008 \newglossarystyle{super4col}{%
```

Put the glossary in a `supertabular` environment with four columns and no head or tail:

```
3009 \renewenvironment{theglossary}%
3010   {\tablehead{}\tabletail{}%
3011   \begin{supertabular}{llll}{}%
3012   \end{supertabular}}%
```

Do nothing at the start of the table:

```
3013 \renewcommand*{\glossaryheader}{}%
```

No group headings:

```
3014 \renewcommand*{\glsgroupheading}[1]{}%
```

Main (level 0) entries on a row with the name in the first column, description in second column, symbol in third column and page list in last column:

```
3015 \renewcommand*{\glossaryentryfield}[5]{%
```

```
3016 \glstarget{##1}{##2} & ##3 & ##4 & ##5\\}%
```

Sub entries on a row with no name, the description in the second column, symbol in third column and page list in last column:

```
3017 \renewcommand*{\glossarysubentryfield}[6]{%
```

```
3018 & \glstarget{##2}{\strut}##4 & ##5 & ##6\\}%
```

Blank row between groups:

```
3019 \renewcommand*{\glsgroupskip}{ & & &\\}%
```

```
3020 }%
```

super4colheader The **super4colheader** style is like the **super4col** but with a header row.

```
3021 \newglossarystyle{super4colheader}{%
```

Base it on the **glostylesuper4col** style:

```
3022 \glossarystyle{super4col}{%
```

Put the glossary in a **supertabular** environment with four columns, a header and no tail:

```
3023 \renewenvironment{theglossary}{%
```

```
3024 \tablehead{\bfseries\entryname\&\bfseries\descriptionname&
```

```
3025 \bfseries\symbolname &
```

```
3026 \bfseries\pagelistname\\}%
```

```
3027 \tabletail{}%
```

```
3028 \begin{supertabular}{llll}
```

```
3029 \end{supertabular}}
```

```
3030 }%
```

super4colborder The **super4colborder** style is like the **super4col** but with a border.

```
3031 \newglossarystyle{super4colborder}{%
```

Base it on the **glostylesuper4col** style:

```
3032 \glossarystyle{super4col}{%
```

Put the glossary in a **supertabular** environment with four columns and a horizontal line in the head and tail:

```
3033 \renewenvironment{theglossary}{%
```

```
3034 \tablehead{\hline\tabletail{\hline}}
```

```
3035 \begin{supertabular}{|l|l|l|l|}
```

```
3036 \end{supertabular}}
```

```
3037 }%
```

super4colheaderborder The **super4colheaderborder** style is like the **super4col** but with a header and border.

```
3038 \newglossarystyle{super4colheaderborder}{%
```

Base it on the **glostylesuper4col** style:

```
3039 \glossarystyle{super4col}{%
```

Put the glossary in a `supertabular` environment with four columns and a header bordered by horizontal lines and a horizontal line in the tail:

```
3040 \renewenvironment{theglossary}%
3041   {\tablehead{\hline\bfseries\entryname\&\bfseries\descriptionname\&
3042     \bfseries\symbolname \&
3043     \bfseries\pagelistname\\hline}\tabletail{\hline}%
3044   \begin{supertabular}{|l|l|l|l|}%
3045   \end{supertabular}}%
3046 }
```

altsuper4col The `altsuper4col` glossary style is like `super4col` but has provision for multiline descriptions.

```
3047 \newglossarystyle{altsuper4col}{%
```

Base it on the `glostylesuper4col` style:

```
3048 \glossarystyle{super4col}{%
```

Put the glossary in a `supertabular` environment with four columns and no head or tail:

```
3049 \renewenvironment{theglossary}%
3050   {\tablehead{}\tabletail{}%
3051   \begin{supertabular}{lp{\glscdescwidth}lp{\glspagelistwidth}}}%%
3052   \end{supertabular}}%
3053 }
```

altsuper4colheader The `altsuper4colheader` style is like the `altsuper4col` but with a header row.

```
3054 \newglossarystyle{altsuper4colheader}{%
```

Base it on the `glostylesuper4colheader` style:

```
3055 \glossarystyle{super4colheader}{%
```

Put the glossary in a `supertabular` environment with four columns, a header and no tail:

```
3056 \renewenvironment{theglossary}%
3057   {\tablehead{\bfseries\entryname\&\bfseries\descriptionname\&
3058     \bfseries\symbolname \&
3059     \bfseries\pagelistname\\}\tabletail{}%
3060   \begin{supertabular}{lp{\glscdescwidth}lp{\glspagelistwidth}}}%%
3061   \end{supertabular}}%
3062 }
```

altsuper4colborder The `altsuper4colborder` style is like the `altsuper4col` but with a border.

```
3063 \newglossarystyle{altsuper4colborder}{%
```

Base it on the `glostylesuper4colborder` style:

```
3064 \glossarystyle{super4colborder}{%
```

Put the glossary in a `supertabular` environment with four columns and a horizontal line in the head and tail:

```
3065 \renewenvironment{theglossary}%
3066   {\tablehead{\hline}\tabletail{\hline}%
3067   \begin{supertabular}%
3068     {|l|p{\glscdescwidth}|l|p{\glspagelistwidth}|}%
3069   \end{supertabular}}%
3070 }
```

altsuper4colheaderborder The `altsuper4colheaderborder` style is like the `altsuper4col` but with a header and border.

```
3071 \newglossarystyle{altsuper4colheaderborder}{%
```

Base it on the `glostylesuper4colheaderborder` style:

```
3072 \glossarystyle{super4colheaderborder}{%
```

Put the glossary in a `supertabular` environment with four columns and a header bordered by horizontal lines and a horizontal line in the tail:

```
3073 \renewenvironment{theglossary}{%
3074   \tablehead{\hline
3075     \bfseries\entryname &
3076     \bfseries\descriptionname &
3077     \bfseries\symbolname &
3078     \bfseries\pagelistname\\\hline}%
3079   \tabletail{\hline}%
3080   \begin{supertabular}{|l|p{\glscdescwidth}|l|p{\glspagelistwidth}|}%
3081     \hline
3082   \end{supertabular}}%
3083 }
```

7.5 Tree Styles (`glossary-tree.sty`)

The `glossary-tree` style file defines glossary styles that have a tree-like structure. These are designed for hierarchical glossaries.

```
3084 \ProvidesPackage{glossary-tree}[2009/01/14 v1.01 (NLCT)]
```

index The `index` glossary style is similar in style to the way indices are usually typeset using `\item`, `\subitem` and `\subsubitem`. The entry name is set in bold. If an entry has a symbol, it is placed in brackets after the name. Then the description is displayed, followed by the number list. This style allows up to three levels.

```
3085 \newglossarystyle{index}{%
```

Set the paragraph indentation and skip and define `\item` to be the same as that used by `theindex`:

```
3086 \renewenvironment{theglossary}{%
3087   \setlength{\parindent}{0pt}%
3088   \setlength{\parskip}{0pt plus 0.3pt}%
3089   \let\item\@idxitem}%
3090 {}%
```

Do nothing at the start of the environment:

```
3091 \renewcommand*{\glossaryheader}{}%
```

No group headers:

```
3092 \renewcommand*{\glsgroupheading}[1]{}%
```

Main (level 0) entry starts a new item with the name in bold followed by the symbol in brackets (if it exists), the description and the page list.

```
3093 \renewcommand*{\glossaryentryfield}[5]{%
3094   \item\textbf{\glstarget{##1}{##2}}%
3095   \ifx\relax##4\relax
3096   \else
3097     \space{##4}%
3098   \fi
3099   \space{##3}\glspostdescription \space{##5}%
}
```

Sub entries: level 1 entries use `\subitem`, levels greater than 1 use `\subsubitem`. The level (`##1`) shouldn't be 0, as that's catered by `\glossaryentryfield`, but for completeness, if the level is 0, `\item` is used. The name is put in bold, followed by the symbol in brackets (if it exists), the description and the page list.

```

3100  \renewcommand*{\glossarysubentryfield}[6]{%
3101    \ifcase##1\relax
3102      % level 0
3103      \item
3104    \or
3105      % level 1
3106      \subitem
3107    \else
3108      % all other levels
3109      \subsubitem
3110    \fi
3111    \textbf{\glstarget{##2}{##3}}%
3112    \ifx\relax##5\relax
3113    \else
3114      \space(##5)%
3115    \fi
3116    \space##4\glspostdescription\space ##6}%

```

Vertical gap between groups is the same as that used by indices:

```
3117  \renewcommand*{\glsgroupskip}{\indexspace}
```

`indexgroup` The `indexgroup` style is like the `index` style but has headings.

```
3118  \newglossarystyle{indexgroup}{%
```

Base it on the `glostyleindex` style:

```
3119  \glossarystyle{index}{%
```

Add a heading for each group. This puts the group's title in bold followed by a vertical gap.

```

3120  \renewcommand*{\glsgroupheading}[1]{%
3121    \item\textbf{\glsgrouptitle{##1}}\indexspace}%
3122 }
```

`indexhypergroup` The `indexhypergroup` style is like the `indexgroup` style but has hyper navigation.

```
3123  \newglossarystyle{indexhypergroup}{%
```

Base it on the `glostyleindex` style:

```
3124  \glossarystyle{index}{%
```

Put navigation links to the groups at the start of the glossary:

```

3125  \renewcommand*{\glossaryheader}{%
3126    \item\textbf{\glsnavigation}\indexspace}%
3127 }
```

Add a heading for each group (with a target). The group's title is in bold followed by a vertical gap.

```

3128  \renewcommand*{\glsgroupheading}[1]{%
3129    \item\textbf{\glshypertarget{##1}{\glsgrouptitle{##1}}}%
3130 }
```

tree The tree glossary style is similar in style to the index style, but can have arbitrary levels.

```
3131 \newglossarystyle{tree}{%
```

Set the paragraph indentation and skip:

```
3132 \renewenvironment{theglossary}{%
3133   \setlength{\parindent}{0pt}%
3134   \setlength{\parskip}{0pt plus 0.3pt}%
3135 }%
```

Do nothing at the start of the `theglossary` environment:

```
3136 \renewcommand*{\glossaryheader}{}%
```

No group headings:

```
3137 \renewcommand*{\glsgroupheading}[1]{%
```

Main (level 0) entries: name in bold, followed by symbol in brackets (if it exists), the description and the page list:

```
3138 \renewcommand{\glossaryentryfield}[5]{%
3139   \hangindent0pt\relax
3140   \parindent0pt\relax
3141   \textbf{\glstarget{##1}{##2}}%
3142   \ifx\relax##4\relax
3143   \else
3144     \space{##4}%
3145   \fi
3146   \space{##3}\glspostdescription \space{##5}\par}%

```

Sub entries: level $\langle n \rangle$ is indented by $\langle n \rangle$ times `\glstreeindent`. The name is in bold, followed by the symbol in brackets (if it exists), the description and the page list.

```
3147 \renewcommand{\glossarysubentryfield}[6]{%
3148   \hangindent##1\glstreeindent\relax
3149   \parindent##1\glstreeindent\relax
3150   \textbf{\glstarget{##2}{##3}}%
3151   \ifx\relax##5\relax
3152   \else
3153     \space{##5}%
3154   \fi
3155   \space{##4}\glspostdescription\space{##6}\par}%

```

Vertical gap between groups is the same as that used by indices:

```
3156 \renewcommand*{\glsgroupskip}{\indexspace}
```

treegroup Like the tree style but the glossary groups have headings.

```
3157 \newglossarystyle{treegroup}{%
```

Base it on the `glostyletree` style:

```
3158 \glossarystyle{tree}{%
```

Each group has a heading (in bold) followed by a vertical gap):

```
3159 \renewcommand{\glsgroupheading}[1]{\par
3160   \noindent\textbf{\glsgrouptitle{##1}}\par\indexspace}%
3161 }
```

treehypergroup The treehypergroup style is like the treegroup style, but has a set of links to the groups at the start of the glossary.

```
3162 \newglossarystyle{treehypergroup}{%
```

Base it on the glostyletree style:

```
3163   \glossarystyle{tree}{%
```

Put navigation links to the groups at the start of the theglossary environment:

```
3164   \renewcommand*\glossaryheader{}{%
```

```
3165     \par\noindent\textbf{\glsnavigation}\par\indexspace{}}
```

Each group has a heading (in bold with a target) followed by a vertical gap):

```
3166   \renewcommand*\glsgroupheading[1]{%
```

```
3167     \par\noindent
```

```
3168     \textbf{\glsnavhypertarget{\#\#1}{\glsgetgrouptitle{\#\#1}}}\par
```

```
3169     \indexspace{}
```

```
3170 }
```

\glstreeindent Length governing left indent for each level of the tree style.

```
3171 \newlength\glstreeindent
```

```
3172 \setlength{\glstreeindent}{10pt}
```

treenoname The treenoname glossary style is like the tree style, but doesn't print the name or symbol for sub-levels.

```
3173 \newglossarystyle{treenoname}{%
```

Set the paragraph indentation and skip:

```
3174 \renewenvironment{theglossary}{%
```

```
3175   \setlength{\parindent}{0pt}{}
```

```
3176   \setlength{\parskip}{0pt plus 0.3pt}{}
```

```
3177 }
```

No header:

```
3178 \renewcommand*\glossaryheader{}{}
```

No group headings:

```
3179 \renewcommand*\glsgroupheading[1]{%}
```

Main (level 0) entries: the name is in bold, followed by the symbol in brackets (if it exists), the description and the page list.

```
3180 \renewcommand{\glossaryentryfield}[5]{%
```

```
3181   \hangindent0pt\relax
```

```
3182   \parindent0pt\relax
```

```
3183   \textbf{\glstarget{\#\#1}{\#\#2}}{}
```

```
3184   \ifx\relax##4\relax
```

```
3185   \else
```

```
3186     \space{\#\#4}{}
```

```
3187   \fi
```

```
3188   \space{\#\#3}{\glspostdescription}\space{\#\#5}{\par}{}
```

Sub entries: level $\langle n \rangle$ is indented by $\langle n \rangle$ times \glstreeindent. The name and symbol are omitted. The description followed by the page list are displayed.

```
3189 \renewcommand{\glossarysubentryfield}[6]{%
```

```
3190   \hangindent##1\glstreeindent\relax
```

```
3191   \parindent##1\glstreeindent\relax
```

```
3192   \glstarget{\#\#2}{\strut}{}
```

```
3193   ##4\glspostdescription\space{\#\#6}{\par}{}
```

Vertical gap between groups is the same as that used by indices:

```
3194 \renewcommand*\glsgroupskip{\indexspace}%
3195 }
```

treenonamegroup Like the **treenoname** style but the glossary groups have headings.

```
3196 \newglossarystyle{treenonamegroup}{%
```

Base it on the **glostyletreenoname** style:

```
3197 \glossarystyle{treenoname}{%
```

Give each group a heading:

```
3198 \renewcommand{\glsgroupheading}[1]{\par
3199   \noindent\textbf{\glsgetgrouptitle{\#1}}\par\indexspace}%
3200 }
```

treenonamehypergroup The **treenonamehypergroup** style is like the **treenonamegroup** style, but has a set of links to the groups at the start of the glossary.

```
3201 \newglossarystyle{treenonamehypergroup}{%
```

Base it on the **glostyletreenoname** style:

```
3202 \glossarystyle{treenoname}{%
```

Put navigation links to the groups at the start of the **theglossary** environment:

```
3203 \renewcommand*\glossaryheader{}%
3204   \par\noindent\textbf{\glsnavigation}\par\indexspace}%
```

Each group has a heading (in bold with a target) followed by a vertical gap):

```
3205 \renewcommand*\glsgroupheading[1]{%
3206   \par\noindent
3207   \textbf{\glsnavhypertarget{\#1}{\glsgetgrouptitle{\#1}}}\par
3208   \indexspace}%
3209 }
```

\glssetwidest **\glssetwidest[<level>][<text>]** sets the widest text for the given level. It is used by the **alttree** glossary styles to determine the indentation of each level.

```
3210 \newcommand*\glssetwidest[2][0]{%
3211   \expandafter\def\csname @glswidestname\romannumeral#1\endcsname{%
3212     #2}%
3213 }
```

\@glswidestname Initialise **\@glswidestname**.

```
3214 \newcommand*\@glswidestname{}%
```

alttree The **alttree** glossary style is similar in style to the **tree** style, but the indentation is obtained from the width of **\@glswidestname** which is set using **\glssetwidest**.

```
3215 \newglossarystyle{alttree}{%
```

Redefine **theglossary** environment.

```
3216 \renewenvironment{theglossary}%
3217   {\def\@gls@prevlevel{-1}%
3218    \mbox{}\par}%
3219   {\par}%
```

Set the header and group headers to nothing.

```
3220 \renewcommand*\glossaryheader{}%
3221 \renewcommand*\glsgroupheading[1]{}%
```

Redefine the way that the level 0 entries are displayed.

```
3222 \renewcommand{\glossaryentryfield}[5]{%
  If the level hasn't changed, keep the same settings, otherwise change \glstreeindent
  accordingly.
```

```
3223 \ifnum\@gls@prevlevel=0\relax
3224 \else
```

Find out how big the indentation should be by measuring the widest entry.

```
3225 \settowidth{\glstreeindent}{\textbf{@glswidestname\space}}%
  Set the hangindent and paragraph indent.
```

```
3226 \hangindent\glstreeindent
3227 \parindent\glstreeindent
3228 \fi
```

Put the name to the left of the paragraph block.

```
3229 \makebox[0pt][r]{\makebox[\glstreeindent][1]{%
  \textbf{\glstarget{##1}{##2}}}}%
```

If the symbol is missing, ignore it, otherwise put it in brackets.

```
3231 \ifx\relax##4\relax
3232 \else
3233 (##4)\space
3234 \fi
```

Do the description followed by the description terminator and location list.

```
3235 ##3\glspostdescription \space ##5\par
```

Set the previous level to 0.

```
3236 \def\@gls@prevlevel{0}%
3237 }%
```

Redefine the way sub-entries are displayed.

```
3238 \renewcommand{\glossarysubentryfield}[6]{%
```

If the level hasn't changed, keep the same settings, otherwise adjust \glstreeindent accordingly.

```
3239 \ifnum\@gls@prevlevel=##1\relax
3240 \else
```

Compute the widest entry for this level, or for level 0 if not defined for this level.

Store in \gls@tmp

```
3241 @ifundefined{@glswidestname\romannumeral##1}{%
3242 \settowidth{\gls@tmp}{\textbf{@glswidestname\space}}}{%
3243 \settowidth{\gls@tmp}{\textbf{\csname @glswidestname\romannumeral##1\endcsname\space}}}%
```

Determine if going up or down a level

```
3245 \ifnum\@gls@prevlevel<##1\relax
```

Depth has increased, so add the width of the widest entry to \glstreeindent.

```
3246 \setlength\glstreeindent\gls@tmp
3247 \addtolength\glstreeindent\parindent
3248 \parindent\glstreeindent
3249 \else
```

Depth has decreased, so subtract width of the widest entry from the previous level to `\glstreeindent`. First determine the width of the widest entry for the previous level and store in `\glstreeindent`.

```
3250      \gdef\glswidestname{\romannumeral\@gls@prevlevel}{%
3251          \settowidth{\glstreeindent}{\textbf{%
3252              \glswidestname\space}}}{%
3253          \settowidth{\glstreeindent}{\textbf{%
3254              \csname\glswidestname\romannumeral\@gls@prevlevel%
3255                  \endcsname\space}}}{%
```

Subtract this length from the previous level's paragraph indent and set to `\glstreeindent`.

```
3256      \addtolength{\parindent}{-\glstreeindent}%
3257      \setlength{\glstreeindent}{\parindent
3258          \fi
3259          \fi}
```

Set the hanging indentation.

```
3260      \hangindent\glstreeindent
```

Put the name to the left of the paragraph block

```
3261      \makebox[0pt][r]{\makebox[\gls@tmpplen][1]{%
3262          \textbf{\glstarget{\#2}{\#3}}}}{}
```

If the symbol is missing, ignore it, otherwise put it in brackets.

```
3263      \ifx##5\relax\relax
3264      \else
3265          (##5)\space
3266      \fi
```

Do the description followed by the description terminator and location list.

```
3267      ##4\glspostdescription\space ##6\par
```

Set the previous level macro to the current level.

```
3268      \def\@gls@prevlevel{\#1}%
3269  }%
```

Vertical gap between groups is the same as that used by indices:

```
3270      \renewcommand*{\glsgroupskip}{\indexspace}%
3271 }
```

`alttreegroup` Like the `alttree` style but the glossary groups have headings.

```
3272 \newglossarystyle{alttreegroup}{%
```

Base it on the `glostylealttree` style:

```
3273 \glossarystyle{alttree}{}
```

Give each group a heading.

```
3274 \renewcommand{\glsgroupheading}[1]{\par
3275     \def\@gls@prevlevel{-1}%
3276     \hangindent0pt\relax
3277     \parindent0pt\relax
3278     \textbf{\glsgetgrouptitle{\#1}}\par\indexspace}%
3279 }
```

`alttreehypergroup` The `alttreehypergroup` style is like the `alttreegroup` style, but has a set of links to the groups at the start of the glossary.

```
3280 \newglossarystyle{alttreehypergroup}{%
```

Base it on the `glostylealttree` style:

```
3281 \glossarystyle{alttree}%
  Put the navigation links in the header
3282 \renewcommand*\glossaryheader{%
3283   \par
3284   \def\@gls@prevlevel{-1}%
3285   \hangindent0pt\relax
3286   \parindent0pt\relax
3287   \textbf{\glsnavigation}\par\indexspace}%
  Put a hypertarget at the start of each group
3288 \renewcommand*\glsgroupheading[1]{%
3289   \par
3290   \def\@gls@prevlevel{-1}%
3291   \hangindent0pt\relax
3292   \parindent0pt\relax
3293   \textbf{\glsnavhypertarget{\#\#1}{\glsgetgrouptitle{\#\#1}}}\par
3294   \indexspace}}
```

8 Accessibilty Support (glossaries-accsupp Code)

The `glossaries-accsupp` package is experimental. It is intended to provide a means of using the PDF accessibility support in glossary entries. See the `accsupp` documentation for further details about accessibility support.

```
3295 \NeedsTeXFormat{LaTeX2e}
3296 \ProvidesPackage{glossaries-accsupp}[2009/03/02 v0.1 (NLCT)]
```

Required packages:

```
3297 \RequirePackage{glossaries}
3298 \RequirePackage{accsupp}
```

Store the replacement text in the `symbol` key when defining new glossary entries. For example:

```
\newglossaryentry{dr}{name=Dr,description={},symbol={Doctor}}
```

The accessibility support is only provided via the commands `\gls`, `\glspl` and their uppercase variants, e.g. `\Gls{dr}`.

```
\glsaccsupp \glsaccsupp{\langle replacement text\rangle}{\langle text\rangle}
```

This can be redefined to use `E` or `Alt` instead of `ActualText`. (I don't have the software to test the `E` or `Alt` options.)

```
3299 \newcommand*\glsaccsupp[2]{%
3300   \BeginAccSupp{ActualText=#1}#2\EndAccSupp{}%
3301 }
```

```
\glsdisplay Redefine \glsdisplay to use symbol as replacement text
```

```
3302 \renewcommand{\glsdisplay}[4]{%
3303   \protected@edef\@glo@symbol{\#3}%
3304   \ifx\@glo@symbol\relax
3305     \#1%
3306   \else
```

```

3307     \expandafter\glsaccsupp\expandafter{\@glo@symbol}{#1}%
3308   \fi
3309   #4%
3310 }

\glsdisplayfirst Redefine \glsdisplayfirst to use symbol as replacement text on first use.
3311 \renewcommand{\glsdisplayfirst}[4]{%
3312   \protected@edef{\@glo@symbol}{#3}%
3313   \ifx{\@glo@symbol}\relax
3314     #1%
3315   \else
3316     \expandafter\glsaccsupp\expandafter{\@glo@symbol}{#1}%
3317   \fi
3318   #4%
3319 }

\@gls@ Redefine \@gls@ to change the way the link text is defined
3320 \def{\@gls@#1#2[#3]}{%
3321   \glsdoifexists{#2}%
3322   {%
3323     \edef{\@glo@type{\glsentrytype{#2}}}%
Save options in \@gls@link@opts and label in \@gls@link@label
3324   \def{\@gls@link@opts}{#1}%
3325   \def{\@gls@link@label}{#2}%

Determine what the link text should be (this is stored in \@glo@text). This is no
longer expanded.
3326   \ifglsused{#2}%
3327   {%
3328     \def{\@glo@text{\csname gls@\@glo@type @display\endcsname}}%
3329       {\glsentrytext{#2}}{\glsentrydesc{#2}}{\glsentrysymbol{#2}}{%
3330       {#3}}%
3331   }%
3332   {%
3333     \def{\@glo@text{\csname gls@\@glo@type @displayfirst\endcsname}}%
3334       {\glsentryfirst{#2}}{\glsentrydesc{#2}}{\glsentrysymbol{#2}}{%
3335       {#3}}%
3336   }%
Call \@gls@link. If footnote package option has been used, suppress hyperlink
for first use.
3337   \ifglsused{#2}%
3338   {%
3339     \@gls@link[#1]{#2}{\@glo@text}%
3340   }%
3341   {%
3342     \ifthenelse{\equal{\@glo@type}{\acronymtype}}{\and}%
3343       {\boolean{glsacrfootnote}}{%
3344       {%
3345         \@gls@link[#1,hyper=false]{#2}{\@glo@text}%
3346       }%
3347       {%
3348         \@gls@link[#1]{#2}{\@glo@text}%
3349       }%
3350   }%

```

Indicate that this entry has now been used

```
3351     \glsunset{#2}%
3352 }%
3353 }
```

\@Gls@

```
3354 \def\@Gls@#1#2[#3]{%
3355   \glsdoifexists{#2}%
3356   {%
3357     \edef\@glo@type{\glsentrytype{#2}}%
Save options in \@gls@link@opts and label in \@gls@link@label
3358     \def\@gls@link@opts{#1}%
3359     \def\@gls@link@label{#2}%

```

Determine what the link text should be (this is stored in \@glo@text). The first character of the entry text is converted to uppercase before passing to \gls@<type>@display or \gls@<type>@displayfirst

```
3360   \ifglsused{#2}%
3361   {%
3362     \def\@glo@text{\csname gls@\@glo@type @display\endcsname
3363       {\Glsentrytext{#2}}{\glsentrydesc{#2}}{\glsentrysymbol{#2}}%
3364       {#3}}%
3365   }%
3366   {%
3367     \def\@glo@text{\csname gls@\@glo@type @displayfirst\endcsname
3368       {\Glsentryfirst{#2}}{\glsentrydesc{#2}}{\glsentrysymbol{#2}}%
3369       {#3}}%
3370   }%
```

Call \@gls@link. If footnote package option has been used, suppress hyperlink for first use.

```
3371 \ifglsused{#2}%
3372 {%
3373   \@gls@link[#1]{#2}{\@glo@text}%
3374 }%
3375 {%
3376   \ifthenelse{\equal{\@glo@type}{\acronymtype}\and
3377     \boolean{glsacrfootnote}}%
3378   {%
3379     \@gls@link[#1,hyper=false]{#2}{\@glo@text}%
3380   }%
3381   {%
3382     \@gls@link[#1]{#2}{\@glo@text}%
3383   }%
3384 }%
```

Indicate that this entry has now been used

```
3385   \glsunset{#2}%
3386 }%
3387 }
```

\@GLS@

```
3388 \def\@GLS@#1#2[#3]{%
3389   \glsdoifexists{#2}%
3390     \edef\@glo@type{\glsentrytype{#2}}%
```

Save options in `\@gls@link@opts` and label in `\@gls@link@label`

```
3391 \def\@gls@link@opts{#1}%
3392 \def\@gls@link@label{#2}%
```

Determine what the link text should be (this is stored in `\@glo@text`).

```
3393 \ifglsused{#2}%
3394 {%
3395   \def\@glo@text{\csname gls@\@glo@type @display\endcsname
3396     {\glsentrytext{#2}}{\glsentrydesc{#2}}{\glsentrysymbol{#2}}%
3397     {#3}}%
3398 }%
3399 {%
3400   \edef\@glo@text{\csname gls@\@glo@type @displayfirst\endcsname
3401     {\glsentryfirst{#2}}{\glsentrydesc{#2}}{\glsentrysymbol{#2}}%
3402     {#3}}%
3403 }%
```

Call `\@gls@link` If footnote package option has been used, suppress hyperlink for first use.

```
3404 \ifglsused{#2}%
3405 {%
3406   \@gls@link[#1]{#2}{\MakeUppercase{\@glo@text}}%
3407 }%
3408 {%
3409   \ifthenelse{\equal{\@glo@type}{\acronymtype}\and
3410     \boolean{glsacrfootnote}}{%
3411     \@gls@link[#1,hyper=false]{#2}{\MakeUppercase{\@glo@text}}%
3412   }%
3413   {%
3414     \@gls@link[#1]{#2}{\MakeUppercase{\@glo@text}}%
3415   }%
3416 }%
```

Indicate that this entry has now been used

```
3417 \glsunset{#2}%
3418 }%
3419 }
```

`\@gls@pl0`

```
3420 \def\@glspl0#1#2[#3]{%
3421   \glsdoifexists{#2}%
3422   {%
3423     \edef\@glo@type{\glsentrytype{#2}}%
```

Save options in `\@gls@link@opts` and label in `\@gls@link@label`

```
3424 \def\@gls@link@opts{#1}%
3425 \def\@gls@link@label{#2}%
```

Determine what the link text should be (this is stored in `\@glo@text`)

```
3426 \ifglsused{#2}%
3427 {%
3428   \def\@glo@text{\csname gls@\@glo@type @display\endcsname
3429     {\glsentryplural{#2}}{\glsentrydescplural{#2}}%
3430     {\glsentrysymbolplural{#2}}{#3}}%
3431 }%
3432 {%
```

```

3433     \def\@glo@text{\csname gls@\@glo@type @displayfirst\endcsname
3434         {\glsentryfirstplural{#2}\{\glsentrydescplural{#2}\}%
3435          {\glsentrysymbolplural{#2}\{#3\}}\%
3436      }%
3437     \ifglsused{#2}%
3438     {%
3439         \@gls@link[#1]{#2}{\@glo@text}%
3440     }%
3441     {%
3442         \ifthenelse{\equal{\@glo@type}{\acronymtype}\and
3443             \boolean{glsacrfootnote}}{%
3444             {%
3445                 \@gls@link[#1,hyper=false]{#2}{\@glo@text}%
3446             }%
3447             {%
3448                 \@gls@link[#1]{#2}{\@glo@text}%
3449             }%
3450         }%
3451     }%
3452     {%
3453 }

```

Indicate that this entry has now been used

```

3451     \glsunset{#2}%
3452 }%
3453 }

```

\@Glspl@

```

3454 \def\@Glspl@#1#2[#3]{%
3455     \glsdoifexists{#2}%
3456     {%
3457         \edef\@glo@type{\glsentrytype{#2}}%
3458     }%
3459     \def\@gls@link@opts{#1}%
3460     \def\@gls@link@label{#2}%

```

Determine what the link text should be (this is stored in \@glo@text).

```

3461     \ifglsused{#2}%
3462     {%
3463         \def\@glo@text{\csname gls@\@glo@type @display\endcsname
3464             {\Glsentryplural{#2}\{\glsentrydescplural{#2}\}%
3465              {\glsentrysymbolplural{#2}\{#3\}}\%
3466            }%
3467         \def\@glo@text{\csname gls@\@glo@type @displayfirst\endcsname
3468             {\Glsentryfirstplural{#2}\{\glsentrydescplural{#2}\}%
3469              {\glsentrysymbolplural{#2}\{#3\}}\%
3470            }%

```

Call \@gls@link If footnote package option has been used, suppress hyperlink for first use.

```

3471     \ifglsused{#2}%
3472     {%
3473         \@gls@link[#1]{#2}{\@glo@text}%
3474     }%

```

```

3475      {%
3476          \ifthenelse{\equal{\@glo@type}{\acronymtype}\and
3477              \boolean{glsacrfootnote}}{%
3478              {%
3479                  \gls@link[#1,hyper=false]{\@glo@text}%
3480              }%
3481              {%
3482                  \gls@link[#1]{\@glo@text}%
3483              }%
3484          }%
3485      }%
3486  }%
3487 }

\@GLSp1@

3488 \def\@GLSp1@#1#2[#3]{%
3489   \glsdoifexists{#2}{%
3490     {%
3491       \edef\@glo@type{\glsentrytype{#2}}%
3492       Save options in \gls@link@opts and label in \gls@link@label
3493       \def\@gls@link@opts{#1}%
3494       \def\@gls@link@label{#2}%
3495       Determine what the link text should be (this is stored in \glo@text)
3496       \def\@glo@text{\csname gls@\@glo@type @display\endcsname
3497         {\glsentryplural{#2}}{\glsentrydescplural{#2}}%
3498         {\glsentrysymbolplural{#2}}{#3}}%
3499     }%
3500     {%
3501       \def\@glo@text{\csname gls@\@glo@type @displayfirst\endcsname
3502         {\glsentryfirstplural{#2}}{\glsentrydescplural{#2}}%
3503         {\glsentrysymbolplural{#2}}{#3}}%
3504     }%
3505   }%
3506   \ifglsused{#2}{%
3507     \gls@link[#1]{\MakeUppercase{\@glo@text}}%
3508   }%
3509   {%
3510     \ifthenelse{\equal{\@glo@type}{\acronymtype}\and
3511         \boolean{glsacrfootnote}}{%
3512         {%
3513             \gls@link[#1,hyper=false]{\MakeUppercase{\@glo@text}}%
3514         }%
3515         {%
3516             \gls@link[#1]{\MakeUppercase{\@glo@text}}%
3517         }%
3518     }%
3519   }%
3520 }

```

Indicate that this entry has now been used

```
3519     \glsunset{#2}%
3520 }%
3521 }
```

9 Multi-Lingual Support

Many thanks to everyone who contributed to the translations both via email and on comp.text.tex.

9.1 Babel Captions

Define babel captions if multi-lingual support is required, but the translator package is not loaded.

```
3522 \NeedsTeXFormat{LaTeX2e}
3523 \ProvidesPackage{glossaries-babel}[2009/04/16 v1.2 (NLCT)]
    English:
3524 \@ifundefined{captionsenglish}{}{%
3525   \addto\captionsenglish{%
3526     \renewcommand*\glossaryname{Glossary}%
3527     \renewcommand*\acronymname{Acronyms}%
3528     \renewcommand*\entryname{Notation}%
3529     \renewcommand*\descriptionname{Description}%
3530     \renewcommand*\symbolname{Symbol}%
3531     \renewcommand*\pagelistname{Page List}%
3532     \renewcommand*\glssymbolsgroupname{Symbols}%
3533     \renewcommand*\glsnumbersgroupname{Numbers}%
3534 }%
3535 }
3536 \@ifundefined{captionsamerican}{}{%
3537   \addto\captionsamerican{%
3538     \renewcommand*\glossaryname{Glossary}%
3539     \renewcommand*\acronymname{Acronyms}%
3540     \renewcommand*\entryname{Notation}%
3541     \renewcommand*\descriptionname{Description}%
3542     \renewcommand*\symbolname{Symbol}%
3543     \renewcommand*\pagelistname{Page List}%
3544     \renewcommand*\glssymbolsgroupname{Symbols}%
3545     \renewcommand*\glsnumbersgroupname{Numbers}%
3546 }%
3547 }
3548 \@ifundefined{captionsaustralian}{}{%
3549   \addto\captionsaustralian{%
3550     \renewcommand*\glossaryname{Glossary}%
3551     \renewcommand*\acronymname{Acronyms}%
3552     \renewcommand*\entryname{Notation}%
3553     \renewcommand*\descriptionname{Description}%
3554     \renewcommand*\symbolname{Symbol}%
3555     \renewcommand*\pagelistname{Page List}%
3556     \renewcommand*\glssymbolsgroupname{Symbols}%
3557     \renewcommand*\glsnumbersgroupname{Numbers}%
3558 }}
```

```

3559 }
3560 \@ifundefined{captionsbritish}{}{%
3561   \addto\captionsbritish{%
3562     \renewcommand*\{\glossaryname}{Glossary}%
3563     \renewcommand*\{\acronymname}{Acronyms}%
3564     \renewcommand*\{\entryname}{Notation}%
3565     \renewcommand*\{\descriptionname}{Description}%
3566     \renewcommand*\{\symbolname}{Symbol}%
3567     \renewcommand*\{\pagelistname}{Page List}%
3568     \renewcommand*\{\glssymbolsgroupname}{Symbols}%
3569     \renewcommand*\{\glsnumbersgroupname}{Numbers}%
3570 } }%
3571 \@ifundefined{captionscanadian}{}{%
3572   \addto\captionscanadian{%
3573     \renewcommand*\{\glossaryname}{Glossary}%
3574     \renewcommand*\{\acronymname}{Acronyms}%
3575     \renewcommand*\{\entryname}{Notation}%
3576     \renewcommand*\{\descriptionname}{Description}%
3577     \renewcommand*\{\symbolname}{Symbol}%
3578     \renewcommand*\{\pagelistname}{Page List}%
3579     \renewcommand*\{\glssymbolsgroupname}{Symbols}%
3580     \renewcommand*\{\glsnumbersgroupname}{Numbers}%
3581 } }%
3582 }%
3583 \@ifundefined{captionsnewzealand}{}{%
3584   \addto\captionsnewzealand{%
3585     \renewcommand*\{\glossaryname}{Glossary}%
3586     \renewcommand*\{\acronymname}{Acronyms}%
3587     \renewcommand*\{\entryname}{Notation}%
3588     \renewcommand*\{\descriptionname}{Description}%
3589     \renewcommand*\{\symbolname}{Symbol}%
3590     \renewcommand*\{\pagelistname}{Page List}%
3591     \renewcommand*\{\glssymbolsgroupname}{Symbols}%
3592     \renewcommand*\{\glsnumbersgroupname}{Numbers}%
3593 } }%
3594 }%
3595 \@ifundefined{captionsUKenglish}{}{%
3596   \addto\captionsUKenglish{%
3597     \renewcommand*\{\glossaryname}{Glossary}%
3598     \renewcommand*\{\acronymname}{Acronyms}%
3599     \renewcommand*\{\entryname}{Notation}%
3600     \renewcommand*\{\descriptionname}{Description}%
3601     \renewcommand*\{\symbolname}{Symbol}%
3602     \renewcommand*\{\pagelistname}{Page List}%
3603     \renewcommand*\{\glssymbolsgroupname}{Symbols}%
3604     \renewcommand*\{\glsnumbersgroupname}{Numbers}%
3605 } }%
3606 }%
3607 \@ifundefined{captionsUSenglish}{}{%
3608   \addto\captionsUSenglish{%
3609     \renewcommand*\{\glossaryname}{Glossary}%
3610     \renewcommand*\{\acronymname}{Acronyms}%
3611     \renewcommand*\{\entryname}{Notation}%
3612     \renewcommand*\{\descriptionname}{Description}%

```

```

3613 \renewcommand*\{\symbolname\}{Symbol}%
3614 \renewcommand*\{\pagelistname\}{Page List}%
3615 \renewcommand*\{\glssymbolsgroupname\}{Symbols}%
3616 \renewcommand*\{\glsnumbersgroupname\}{Numbers}%
3617 }%
3618 }

```

German (quite a few variations were suggested for German; I settled on the following):

```

3619 \@ifundefined{captionsgerman}{}{%
3620   \addto\captionsgerman{%
3621     \renewcommand*\{\glossaryname\}{Glossar}%
3622     \renewcommand*\{\acronymname\}{Akronyme}%
3623     \renewcommand*\{\entryname\}{Bezeichnung}%
3624     \renewcommand*\{\descriptionname\}{Beschreibung}%
3625     \renewcommand*\{\symbolname\}{Symbol}%
3626     \renewcommand*\{\pagelistname\}{Seiten}%
3627     \renewcommand*\{\glssymbolsgroupname\}{Symbole}%
3628     \renewcommand*\{\glsnumbersgroupname\}{Zahlen}%
3629 }

```

`ngerman` is identical to German:

```

3630 \@ifundefined{captionsngerman}{}{%
3631   \addto\captionsngerman{%
3632     \renewcommand*\{\glossaryname\}{Glossar}%
3633     \renewcommand*\{\acronymname\}{Akronyme}%
3634     \renewcommand*\{\entryname\}{Bezeichnung}%
3635     \renewcommand*\{\descriptionname\}{Beschreibung}%
3636     \renewcommand*\{\symbolname\}{Symbol}%
3637     \renewcommand*\{\pagelistname\}{Seiten}%
3638     \renewcommand*\{\glssymbolsgroupname\}{Symbole}%
3639     \renewcommand*\{\glsnumbersgroupname\}{Zahlen}%
3640 }

```

Italian:

```

3641 \@ifundefined{captionsitalian}{}{%
3642   \addto\captionsitalian{%
3643     \renewcommand*\{\glossaryname\}{Glossario}%
3644     \renewcommand*\{\acronymname\}{Acronimi}%
3645     \renewcommand*\{\entryname\}{Nomenclatura}%
3646     \renewcommand*\{\descriptionname\}{Descrizione}%
3647     \renewcommand*\{\symbolname\}{Simbolo}%
3648     \renewcommand*\{\pagelistname\}{Elenco delle pagine}%
3649     \renewcommand*\{\glssymbolsgroupname\}{Simboli}%
3650     \renewcommand*\{\glsnumbersgroupname\}{Numeri}%
3651 }

```

Dutch:

```

3652 \@ifundefined{captionsdutch}{}{%
3653   \addto\captionsdutch{%
3654     \renewcommand*\{\glossaryname\}{Woordenlijst}%
3655     \renewcommand*\{\acronymname\}{Acroniemen}%
3656     \renewcommand*\{\entryname\}{Benaming}%
3657     \renewcommand*\{\descriptionname\}{Beschrijving}%
3658     \renewcommand*\{\symbolname\}{Symbool}%
3659     \renewcommand*\{\pagelistname\}{Pagina's}%

```

```
3660     \renewcommand*{\glssymbolsgroupname}{Symbolen}%
3661     \renewcommand*{\glsnumbersgroupname}{Cijfers}%
3662 }
```

Spanish:

```
3663 \@ifundefined{captionsspanish}{}{%
3664   \addto\captionsspanish{%
3665     \renewcommand*{\glossaryname}{Glosario}%
3666     \renewcommand*{\acronymname}{Siglas}%
3667     \renewcommand*{\entryname}{Entrada}%
3668     \renewcommand*{\descriptionname}{Descripción}%
3669     \renewcommand*{\symbolname}{Símbolo}%
3670     \renewcommand*{\pagelistname}{Lista de páginas}%
3671     \renewcommand*{\glssymbolsgroupname}{Símbolos}%
3672     \renewcommand*{\glsnumbersgroupname}{Números}%
3673 }}
```

French:

```
3674 \@ifundefined{captionsfrench}{}{%
3675   \addto\captionsfrench{%
3676     \renewcommand*{\glossaryname}{Glossaire}%
3677     \renewcommand*{\acronymname}{Acronymes}%
3678     \renewcommand*{\entryname}{Terme}%
3679     \renewcommand*{\descriptionname}{Description}%
3680     \renewcommand*{\symbolname}{Symbole}%
3681     \renewcommand*{\pagelistname}{Pages}%
3682     \renewcommand*{\glssymbolsgroupname}{Symboles}%
3683     \renewcommand*{\glsnumbersgroupname}{Nombres}%
3684 }
3685 \@ifundefined{captionsfrenchb}{}{%
3686   \addto\captionsfrenchb{%
3687     \renewcommand*{\glossaryname}{Glossaire}%
3688     \renewcommand*{\acronymname}{Acronymes}%
3689     \renewcommand*{\entryname}{Terme}%
3690     \renewcommand*{\descriptionname}{Description}%
3691     \renewcommand*{\symbolname}{Symbole}%
3692     \renewcommand*{\pagelistname}{Pages}%
3693     \renewcommand*{\glssymbolsgroupname}{Symboles}%
3694     \renewcommand*{\glsnumbersgroupname}{Nombres}%
3695 }
3696 \@ifundefined{captionsfrancais}{}{%
3697   \addto\captionsfrancais{%
3698     \renewcommand*{\glossaryname}{Glossaire}%
3699     \renewcommand*{\acronymname}{Acronymes}%
3700     \renewcommand*{\entryname}{Terme}%
3701     \renewcommand*{\descriptionname}{Description}%
3702     \renewcommand*{\symbolname}{Symbole}%
3703     \renewcommand*{\pagelistname}{Pages}%
3704     \renewcommand*{\glssymbolsgroupname}{Symboles}%
3705     \renewcommand*{\glsnumbersgroupname}{Nombres}%
3706 }}
```

Danish:

```
3707 \@ifundefined{captionsdanish}{}{%
3708   \addto\captionsdanish{%
```

```

3709 \renewcommand*\glossaryname{Ordliste}%
3710 \renewcommand*\acronymname{Akronymer}%
3711 \renewcommand*\entryname{Symbolforklaring}%
3712 \renewcommand*\descriptionname{Beskrivelse}%
3713 \renewcommand*\symbolname{Symbol}%
3714 \renewcommand*\pagelistname{Side}%
3715 \renewcommand*\glssymbolsgroupname{Symboler}%
3716 \renewcommand*\glsnumbersgroupname{Tal}%
3717 }

```

Irish:

```

3718 \@ifundefined{captionsirish}{}{%
3719   \addto\captionsirish{%
3720     \renewcommand*\glossaryname{Gluais}%
3721     \renewcommand*\acronymname{Acrainmneacha}%
}

```

wasn't sure whether to go for Nóta (Note), Ciall ('Meaning', 'sense') or Brí ('Meaning'). In the end I chose Ciall.

```

3722 \renewcommand*\entryname{Ciall}%
3723 \renewcommand*\descriptionname{Tuairisc}%

```

Again, not sure whether to use Comhartha/Comharthaí or Siombail/Siombaile, so have chosen the former.

```

3724 \renewcommand*\symbolname{Comhartha}%
3725 \renewcommand*\glssymbolsgroupname{Comhartha'\i}%
3726 \renewcommand*\pagelistname{Leathanaigh}%
3727 \renewcommand*\glsnumbersgroupname{Uimhreacha}%
3728 }

```

Hungarian:

```

3729 \@ifundefined{captionsmagyar}{}{%
3730   \addto\captionsmagyar{%
3731     \renewcommand*\glossaryname{Sz\'ojegyz\'ek}%
3732     \renewcommand*\acronymname{Bet\'H uszavak}%
3733     \renewcommand*\entryname{Kifejez\'es}%
3734     \renewcommand*\descriptionname{Magyar\'azat}%
3735     \renewcommand*\symbolname{Jel\"ol\'es}%
3736     \renewcommand*\pagelistname{Oldalsz\'am}%
3737     \renewcommand*\glssymbolsgroupname{Jelek}%
3738     \renewcommand*\glsnumbersgroupname{Sz\'amjegyek}%
3739   }
3740 }
3741 \@ifundefined{captionshungarian}{}{%
3742   \addto\captionshungarian{%
3743     \renewcommand*\glossaryname{Sz\'ojegyz\'ek}%
3744     \renewcommand*\acronymname{Bet\'H uszavak}%
3745     \renewcommand*\entryname{Kifejez\'es}%
3746     \renewcommand*\descriptionname{Magyar\'azat}%
3747     \renewcommand*\symbolname{Jel\"ol\'es}%
3748     \renewcommand*\pagelistname{Oldalsz\'am}%
3749     \renewcommand*\glssymbolsgroupname{Jelek}%
3750     \renewcommand*\glsnumbersgroupname{Sz\'amjegyek}%
3751   }
3752 }

```

Polish

```

3753 \@ifundefined{captionspolish}{}{%
3754   \addto\captionspolish{%
3755     \renewcommand*{\glossaryname}{S{\l}ownik termin\'ow}%
3756     \renewcommand*{\acronymname}{Skr\'ot}%
3757     \renewcommand*{\entryname}{Termin}%
3758     \renewcommand*{\descriptionname}{Opis}%
3759     \renewcommand*{\symbolname}{Symbol}%
3760     \renewcommand*{\pagelistname}{Strony}%
3761     \renewcommand*{\glssymbolsgroupname}{Symbole}%
3762     \renewcommand*{\glsnumbersgroupname}{Liczby}%
3763 }

```

Brazilian

```

3764 \@ifundefined{captionsbrazil}{}{%
3765   \addto\captionsbrazil{%
3766     \renewcommand*{\glossaryname}{Gloss\'ario}%
3767     \renewcommand*{\acronymname}{Siglas}%
3768     \renewcommand*{\entryname}{Nota\c c\^ao}%
3769     \renewcommand*{\descriptionname}{Descri\c c\^ao}%
3770     \renewcommand*{\symbolname}{S\'imbolo}%
3771     \renewcommand*{\pagelistname}{Lista de P\'aginas}%
3772     \renewcommand*{\glssymbolsgroupname}{S\'imbolos}%
3773     \renewcommand*{\glsnumbersgroupname}{N\'umeros}%
3774   }%
3775 }

```

9.2 Brazilian Dictionary

This is a dictionary file provided by Thiago de Melo for use with the `translator` package.

```
3776 \ProvidesDictionary{glossaries-dictionary}{Brazil}
```

Provide Brazilian translations:

```

3777 \providetranslation{Glossary}{Gloss\'ario}
3778 \providetranslation{Acronyms}{Siglas}
3779 \providetranslation{Notation (glossaries)}{Nota\c c\^ao}
3780 \providetranslation{Description (glossaries)}{Descri\c c\^ao}
3781 \providetranslation{Symbol (glossaries)}{S\'imbolo}
3782 \providetranslation{Page List (glossaries)}{Lista de P\'aginas}
3783 \providetranslation{Symbols (glossaries)}{S\'imbolos}
3784 \providetranslation{Numbers (glossaries)}{N\'umeros}

```

9.3 Danish Dictionary

This is a dictionary file provided for use with the `translator` package.

```
3785 \ProvidesDictionary{glossaries-dictionary}{Danish}
```

Provide Danish translations:

```

3786 \providetranslation{Glossary}{Ordliste}
3787 \providetranslation{Acronyms}{Akronymer}
3788 \providetranslation{Notation (glossaries)}{Symbolforklaring}
3789 \providetranslation{Description (glossaries)}{Beskrivelse}
3790 \providetranslation{Symbol (glossaries)}{Symbol}
3791 \providetranslation{Page List (glossaries)}{Side}

```

```
3792 \providetranslation{Symbols (glossaries)}{Symboler}
3793 \providetranslation{Numbers (glossaries)}{Tal}
```

9.4 Dutch Dictionary

This is a dictionary file provided for use with the translator package.

```
3794 \ProvidesDictionary{glossaries-dictionary}{Dutch}
```

Provide Dutch translations:

```
3795 \providetranslation{Glossary}{Woordenlijst}
3796 \providetranslation{Acronyms}{Acroniemen}
3797 \providetranslation{Notation (glossaries)}{Benaming}
3798 \providetranslation{Description (glossaries)}{Beschrijving}
3799 \providetranslation{Symbol (glossaries)}{Symbool}
3800 \providetranslation{Page List (glossaries)}{Pagina's}
3801 \providetranslation{Symbols (glossaries)}{Symbolen}
3802 \providetranslation{Numbers (glossaries)}{Cijfers}
```

9.5 English Dictionary

This is a dictionary file provided for use with the translator package.

```
3803 \ProvidesDictionary{glossaries-dictionary}{English}
```

Provide English translations:

```
3804 \providetranslation{Glossary}{Glossary}
3805 \providetranslation{Acronyms}{Acronyms}
3806 \providetranslation{Notation (glossaries)}{Notation}
3807 \providetranslation{Description (glossaries)}{Description}
3808 \providetranslation{Symbol (glossaries)}{Symbol}
3809 \providetranslation{Page List (glossaries)}{Page List}
3810 \providetranslation{Symbols (glossaries)}{Symbols}
3811 \providetranslation{Numbers (glossaries)}{Numbers}
```

9.6 French Dictionary

This is a dictionary file provided for use with the translator package.

```
3812 \ProvidesDictionary{glossaries-dictionary}{French}
```

Provide French translations:

```
3813 \providetranslation{Glossary}{Glossaire}
3814 \providetranslation{Acronyms}{Acronymes}
3815 \providetranslation{Notation (glossaries)}{Terme}
3816 \providetranslation{Description (glossaries)}{Description}
3817 \providetranslation{Symbol (glossaries)}{Symbole}
3818 \providetranslation{Page List (glossaries)}{Pages}
3819 \providetranslation{Symbols (glossaries)}{Symboles}
3820 \providetranslation{Numbers (glossaries)}{Nombres}
```

9.7 German Dictionary

This is a dictionary file provided for use with the translator package.

```
3821 \ProvidesDictionary{glossaries-dictionary}{German}
```

Provide German translations (quite a few variations were suggested for German; I settled on the following):

```
3822 \providetranslation{Glossary}{Glossar}
3823 \providetranslation{Acronyms}{Akronyme}
3824 \providetranslation{Notation (glossaries)}{Bezeichnung}
3825 \providetranslation{Description (glossaries)}{Beschreibung}
3826 \providetranslation{Symbol (glossaries)}{Symbol}
3827 \providetranslation{Page List (glossaries)}{Seiten}
3828 \providetranslation{Symbols (glossaries)}{Symbole}
3829 \providetranslation{Numbers (glossaries)}{Zahlen}
```

9.8 Irish Dictionary

This is a dictionary file provided for use with the `translator` package.

```
3830 \ProvidesDictionary{glossaries-dictionary}{Irish}
```

Provide Irish translations:

```
3831 \providetranslation{Glossary}{Gluais}
3832 \providetranslation{Acronyms}{Acrainmneacha}
3833 \providetranslation{Notation (glossaries)}{Ciall}
3834 \providetranslation{Description (glossaries)}{Tuairisc}
3835 \providetranslation{Symbol (glossaries)}{Comhartha}
3836 \providetranslation{Page List (glossaries)}{Leathanaigh}
3837 \providetranslation{Symbols (glossaries)}{Comhartha'\{\i\}}
3838 \providetranslation{Numbers (glossaries)}{Uimhreacha}
```

9.9 Italian Dictionary

This is a dictionary file provided for use with the `translator` package.

```
3839 \ProvidesDictionary{glossaries-dictionary}{Italian}
```

Provide Italian translations:

```
3840 \providetranslation{Glossary}{Glossario}
3841 \providetranslation{Acronyms}{Acronimi}
3842 \providetranslation{Notation (glossaries)}{Nomenclatura}
3843 \providetranslation{Description (glossaries)}{Descrizione}
3844 \providetranslation{Symbol (glossaries)}{Simbolo}
3845 \providetranslation{Page List (glossaries)}{Elenco delle pagine}
3846 \providetranslation{Symbols (glossaries)}{Simboli}
3847 \providetranslation{Numbers (glossaries)}{Numeri}
```

9.10 Magyar Dictionary

This is a dictionary file provided for use with the `translator` package.

```
3848 \ProvidesDictionary{glossaries-dictionary}{Magyar}
```

Provide translations:

```
3849 \providetranslation{Glossary}{Sz\'ojegyz\'ek}
3850 \providetranslation{Acronyms}{Bet\H uszavak}
3851 \providetranslation{Notation (glossaries)}{Kifejez\'es}
3852 \providetranslation{Description (glossaries)}{Magyar\'azat}
3853 \providetranslation{Symbol (glossaries)}{Jel\"ol\'es}
3854 \providetranslation{Page List (glossaries)}{Oldalsz\'am}
```

```
3855 \providetranslation{Symbols (glossaries)}{Jelek}
3856 \providetranslation{Numbers (glossaries)}{Számjegyek}
```

9.11 Polish Dictionary

This is a dictionary file provided for use with the translator package.

```
3857 \ProvidesDictionary{glossaries-dictionary}{Polish}
```

Provide Polish translations:

```
3858 \providetranslation{Glossary}{Słownik terminów}
3859 \providetranslation{Acronyms}{Skrót}
3860 \providetranslation{Notation (glossaries)}{Termin}
3861 \providetranslation{Description (glossaries)}{Opis}
3862 \providetranslation{Symbol (glossaries)}{Symbol}
3863 \providetranslation{Page List (glossaries)}{Strony}
3864 \providetranslation{Symbols (glossaries)}{Symbole}
3865 \providetranslation{Numbers (glossaries)}{Liczby}
```

9.12 Spanish Dictionary

This is a dictionary file provided for use with the translator package.

```
3866 \ProvidesDictionary{glossaries-dictionary}{Spanish}
```

Provide Spanish translations:

```
3867 \providetranslation{Glossary}{Glosario}
3868 \providetranslation{Acronyms}{Siglas}
3869 \providetranslation{Notation (glossaries)}{Entrada}
3870 \providetranslation{Description (glossaries)}{Descripción}
3871 \providetranslation{Symbol (glossaries)}{Símbolo}
3872 \providetranslation{Page List (glossaries)}{Lista de páginas}
3873 \providetranslation{Symbols (glossaries)}{Símbolos}
3874 \providetranslation{Numbers (glossaries)}{Números}
```

Index

Symbols			
\@glossarysec	73	\@gls@tmpb	107
\@glossaryseclabel	73	\@gls@toc	85
\@glossarysecstar	73	\@gls@updatechecked	107
\@GLS@	115, 192	\@gls@xdycheckbackslash	111
\@GLSpl	117	\@gls@xdycheckquote	111
\@GLSpl@	195	\@glsAlphacompositor	
\@Gls@	114, 192	\@glsdefaultplural	96
\@Glspl@	117, 194	\@glsdefaultsort	96
\@delimN	151	\@glsdisp	118
\@delimR	151	\@glsfirstletter	135
\@disable@onlypremakeg	79	\@glshypernumber	151
\@disable@premakecs	79	\@glslink	112
\@do@seeglossary	144	\@glsminrange	135
\@do@wrgglossary	143	\@glsnoname	96
\@glo@storeentry	100	\@glsnonextpages	148
\@glo@types	93	\@glsorder	77
\@glossary	142	\@glspl@	116
\@glossary@default@style	73	\@glstarget	112
\@glossarysection	84	\@glswidestname	187
\@gls	113	\@istfilename	82
\@gls@	113, 191	\@makeglossary	141
\@gls@checkactual	110	\@newglossary	94
\@gls@checkboxbar	109	\@nopostdesc	81
\@gls@checkescactual	108	\@onlypremakeg	79
\@gls@checkescbar	108	\@p@glossarysection	84
\@gls@checkesclevel	109	\@set@glo@numformat	105
\@gls@checkescquote	107	\@sgls	113, 118
\@gls@checklevel	110	\@sgls@link	105
\@gls@checkmkidxchars	106	\@wrgglossary	143
\@gls@checkquote	107	\@xdy@main@language	78
\@gls@codepage	90	\@xdyattributes	85
\@gls@escbsdq	106	\@xdylanguage	90
\@gls@fixbraces	144	\@xdylettergroups	90
\@gls@getcounter	94	\@xdylocationclassorder	
\@gls@hypergroup	169	\@xdylocref	85
\@gls@link	105	\@xdyrequiredstyles	88
\@gls@loadlist	74	\@xdysortrules	88
\@gls@loadlong	74	\@xdyuseralphabets	86
\@gls@loadsper	74	\@xdyuserlocationdefs	
\@gls@loadtree	74	\@xdyuserlocationnames	87
\@gls@onlypremakeg	79	\@xdyuserlocations	
\@gls@pl@	193	A	
\@gls@renewglossary	142	\Ac	58, 166
\@gls@sanitizedesc	76	\ac	58, 166
\@gls@sanitizename	76	accsupp package	70, 71, 190
\@gls@sanitizesymbol	76	\Acf	58, 166
\@gls@setcounter	94	\acf	58, 165
		\Acfp	58, 166
		\acfpl	58, 165
		\Acp	58, 166
		\acp	58, 166
		\ACRfull	58, 156
		\Acrlfull	58, 58, 156
		\acrfull	58, 58, 155
		\ACRfullpl	156
		\Acrlfullpl	58, 156
		\acrfullpl	58, 156
		\ACRlong	57, 155
		\Acrlong	57, 58, 155
		\acrlong	16, 57, 58, 155
		\ACRlongpl	155
		\Acrlongpl	58, 155
		\acrlongpl	58, 155
		\acrnameformat	
			55, 55, 156, 159
		\acronym	75
		\acronymfont	
			53, 55, 57, 156,
			158, 160, 162, 163
		\acronymname	11, 79
		\acronymtype	25, 26,
			31, 51, 52, 75, 153
		\acrpluralsuffix	154
		\ACRshort	57, 154
		\Acrshort	57, 58, 154
		\acrshort	57, 58, 154
		\ACRshortpl	155
		\Acrshortpl	58, 155
		\acrshortpl	58, 155
		\Acs	58, 165
		\acs	58, 165
		\Acsp	58, 165
		\acsp	58, 165
		\altlist	171
		\altlistgroup	171
		\altlisthypergroup	171
		\altlong4col	176
		\altlong4colborder	177
		\altlong4colheader	177
		\altlong4colheaderborder	
			177
		\altsuper4col	182
		\altsuper4colborder	182
		\altsuper4colheader	182

\altsuper4colheaderborder	flag	36, 38, 39, 44	
.....	183	text	30, 31, 45
\alttree	187	\firstacronymfont	53, 156
\alttreegroup	189	\firstplural	95
\alttreehypergroup	189	flowfram package	65
amsgen package . . .	72, 104	fmtcount package	49
\andname	80	fontenc package	22
		\footnote	77
B		\forallglossaries	91
babel package		\forallglentries	91
...	10, 16, 18,	\forglentries	91
	72, 79, 80, 89, 196		
C			
\clearpage	18, 26	G	
\counter	75, 96	german package	10
		glossaries package	8, 10, 59
D		glossaries-accsupp package	9, 70, 190
\defglsdisplay	42, 54, 58, 93–95, 103, 104	\glossary 93, 141, 142, 150
\defglsdisplayfirst 42, 54, 58, 93–95, 103, 104	glossary package 3, 16, 59, 153
\delimN	83, 150	glossary styles	
\delimR	83, 150	altlist	63, 171
\description	77, 94	altlistgroup	63, 171
\descriptionname	11, 80	altlisthypergroup	63, 171
\descriptionplural	95	altlong4col	62, 64, 176, 177
\dua	77	altlong4colborder	64, 177
		altnlong4colheader	64, 177
E		altnlong4colheaderborder	64, 177
\emph	37	altsuper4col	62, 65, 66, 182, 183
\entryname	11, 80	altsuper4colborder	66, 182
environments:		altsuper4colheader	66, 182
theglossary . . .	67, 148	altsuper4colheaderborder	66, 183
		alttree	66, 67, 187, 189
F		alttreegroup	67, 189
file types		alttreehypergroup	67, 189
.alg	13	index	54, 55, 66, 183–185
.aux	13, 48, 146	indexgroup	66, 184
.glg	13–15, 17, 20	indexhypergroup	66, 184
.glo	14, 15, 29, 100	list	27, 62, 63, 67–70, 73, 170–172
.gls	14, 15, 29		
.ist	13, 14, 28, 29, 135, 140, 141		
.log	17		
.nlg	20		
.tex	14		
.toc	85		
.xdy	13, 14, 28, 29, 48, 82		
\findrootlanguage	88		
\first	95		
first use	16, 24, 41, 42, 52–57, 59		

glossary-long package
 27, 47, 63, 74,
 172, 173, 177, 178
 glossary-super package
 27,
 47, 65, 74, 173, 177
 glossary-tree package
 27, 47, 66, 74, 183
 \glossaryentryfield
 68, 69, 95, 148, 150
 \glossaryentrynumber
 148
 \glossaryentrynumbers
 69, 74, 83, 146
 \glossaryheader
 63, 68, 69, 148, 150
 \glossaryname 11, 79
 \glossarypostamble
 47, 84, 150
 \glossarypreamble
 47, 83, 150
 \glossarysection
 73, 84, 93
 \glossarystyle 19, 27,
 46, 60, 62, 150, 166
 \glossarysubentryfield
 69
 \GLS 23, 38, 115
 \Gls 9, 22, 23, 38,
 58, 59, 114, 116, 167
 \gls 21, 23, 30, 36, 38,
 39, 41, 43, 58,
 59, 70, 72, 95,
 102, 103, 113,
 115, 119, 120,
 122–124, 126,
 127, 129, 130, 190
 \gls@codepage 78
 \gls@docclearpage 85
 \gls@hypergrouprerun
 169
 \gls@level 96
 \gls@suffixF 82
 \gls@suffixFF 83
 \glsaccsupp 190
 \glsadd 21,
 24, 43, 102, 134, 150
 \glsadd options
 counter 134
 format 134, 150
 \glsaddall 6,
 21, 24, 43, 102, 134
 \glsaddall options
 types 43, 134

\GlsAddSortRule 88
 \GlsAddXdyAlphabet 86
 \GlsAddXdyAttribute 86
 37, 49, 86
 \GlsAddXdyLocation 50, 87
 \GlsAddXdyStyle 88
 \glsautoprefix 26, 73
 \glsclearpage 18, 26, 85
 \glsclosebrace 48, 135
 \glscompositor 82, 137
 \glscounter 75, 93
 \glsdefaulttype 25, 75
 \GLSdesc 41, 127
 \Glsdesc 41, 126
 \glsdesc 41,
 58, 126, 127, 155
 \GLSdescplural 128
 \Glsdescplural 128
 \glsdescplural 127, 128
 \glsdescwidth 62, 64–66, 173, 177
 \glsdisablehyper 43, 112
 \glsdisp 32, 39, 41, 118
 \glsdisplay 30, 31, 39,
 41, 75, 94, 95,
 103, 113, 153, 190
 \glsdisplayfirst
 30, 31, 39,
 41, 94, 95, 103,
 104, 113, 153, 191
 \glsdoifexists 92
 \glsdoifnoexists 92
 \glsenablehyper 43, 112
 \Glsentrydesc 45, 132
 \glsentrydesc 45, 75, 132
 \Glsentrydescplural 45, 132
 \glsentrydescplural 45, 132
 \glsentryfirst 45, 133
 \glsentryfirst 45, 133
 \Glsentryfirstplural 45, 133
 \glsentryfirstplural 45, 133
 \Glsentryname 45, 131
 \glsentryname 45, 46, 131
 \Glsentryplural 45, 132
 \glsentryplural 45, 132
 \glsentriesort 133
 \Glsentrysymbol 45, 133
 \glsentrysymbol 45, 132
 \Glsentrysymbolplural 46, 133
 \glsentrysymbolplural 45, 133
 \glsentrytext 45, 132
 \glsentrytext 45, 132
 \glsentrytype 133
 \GLSfirst 39, 121
 \Glsfirst 39, 121
 \glsfirst 39,
 58, 120, 121, 155
 \GLSfirstplural 40, 124
 \Glsfirstplural 40, 124
 \glsfirstplural 40, 123, 124
 \glsgetgrouplabel 150
 \glsgetgrouptitle 68, 135, 149
 \glsgroupheading 68, 69, 149, 150
 \glsgroupskip 5, 62,
 68, 69, 149, 150, 170
 \glshyperlink 44, 46, 134
 \glshypernavsep 63, 170
 \glshypernumber 83, 151
 \glslabel 41, 41
 \glslink 21,
 24, 32, 36, 38,
 41, 43, 102, 103,
 105, 113, 134, 150
 \glslink options
 counter 38, 104, 113
 format 37, 49, 104, 113, 150
 hyper 38, 43, 104, 113
 \glslink* 38
 \glslistdottedwidth 63, 172
 \glslocalreset 60, 101
 \glslocalresetall 60, 102
 \glslocalunset 60, 102
 \glslocalunsetall 60, 102
 \glslongkey 54, 154
 \glslongpluralkey 54, 154
 \GLSname 40, 125
 \Glsname 40, 125
 \glsname 40, 124, 125
 \glsnamefont 19, 47, 150
 \glsnavhyperlink 168
 \glsnavhypertarget 68, 168

\glsnavigation 169 \GlsSetXdyStyles .. 88
\glsnonextpages 148 \glsshortkey 54, 154
\glsnoxindywarning . 85 \glsshortpluralkey .
\glsnumberformat .. 83 54, 154
\glsnumbersgroupname .. 11, 80, 135, 149 \GLSsymbol 41, 129
\glsopenbrace .. 48, 135 \Glssymbol 40, 129
\glsorder 77 \glssymbol .. 40, 58, 129
\glspagelistwidth .. 62, 64–66, 173, 178 \glssymbolnav 170
\glspar 30, 81 \GLSsymbolplural .. 131
\GLSp1 24, 30, 31, 39, 117 \Glssymbolplural .. 130
\GLSp1 ... 22, 24, 30,
 31, 39, 58, 116, 167 \glssymbolplural ..
\glspl ... 23, 30,
 31, 36, 39, 41,
 58, 59, 70, 102,
 103, 115–117, 190 130, 131
\GLSplural 40, 123 \glssymbolsgroupname
\GLSplural 40, 122 11, 80, 135, 149
\glspplural 39, 122, 123 \glstarget 69, 148
\glsppluralsuffix ..
 31, 32, 80, 95 \GLStext 39, 120
\glspostdescription ..
 62, 81 \Glstext 39, 120
\glsquote 48, 135 \glstext 39, 39,
 40, 41, 57, 119, 154
\glsreset .. 25, 60, 101 \glstextformat
\glsresetall 25, 60, 102 36, 42, 103
\glsresetentrylist . 148 \glstreeindent
\glssee 3,
 21, 23, 37, 44, 144 66, 185, 186
\glsseeformat 137 \glsunset 60, 102
\glsseeitem 145 \glsunsetall ... 60, 102
\glsseelastsep 145 **H**
\glsseelist 144 html package 18, 43
\glsseesep 145 \hyperbf 37, 152
\glsSetAlphaCompositor ..
 30, 82 \hyperemph 37, 152
\glsSetCompositor ..
 19, 29, 82 \hyperit 37, 152
\glsSetSuffixF .. 35, 82 \hyperlink .. 38, 43, 112
\glsSetSuffixFF .. 35, 83 \hypermd 37, 152
\glssettotitle ... 80 \hyperpage 37, 151
\glssetwidest ... 67, 187 hyperref package 18, 26,
 36, 37, 43, 69, 151
\GlsSetXdyCodePage ..
 13, 48, 90 \hyperrm ... 37, 49, 152
\GlsSetXdyFirstLetterAfterDigit ..
 135 \hypersc 37, 152
\GlsSetXdyLanguage ..
 13, 48, 90 \hypersf 37, 152
\GlsSetXdyLocationClassOrder ..
 50, 88 \hypersl 37, 152
\GlsSetXdyMinRangeLength ..
 35, 50, 135 \hypertarget 43, 112
 \hypertt 37, 152
 \hyperup 37, 152
I
\ifglossaryexists .. 92
\ifglsentryexists .. 92
\ifglsused .. 60, 92, 101
\ifglsxindy 78
\index .. 183
\indexgroup 184
\indexhypergroup .. 184
\indexspace 66
J
\inputenc package
 8, 9, 22, 31, 48, 71
\inputencodingname ..
 48, 78
\istfilename 81
\item 19,
 150, 170, 183, 184
L
\language 88
link text 36, 38, 41, 42, 103
\list 170
\listdotted 172
\listgroup 170
\listhypergroup ... 171
\loadglsentries ...
 34, 75, 103
location list *see* number list
\long 173
\long3col 174
\long3colborder ... 174
\long3colheader ... 175
\long3colheaderborder
 175
\long4col 175
\long4colborder ... 176
\long4colheader ... 176
\long4colheaderborder
 176
\longborder 173
\longheader 173
\longheaderborder ... 174
longtable package ...
 27, 63, 172
M
\makefirststuc 57, 71, 167
makeglossaries 3, 5–
 9, 12–17, 19, 20,
 28, 29, 44, 46,
 48, 49, 51, 77,
 82, 88, 90, 93, 146
\makeglossaries ...
 . 12, 16, 18–20,
 29, 35, 36, 46,
 49–51, 79, 81,
 82, 92, 93, 141, 142
\makeglossary 142
makeindex 3,
 5–9, 12–17, 20,
 22, 24, 28, 29,

31, 35–37, 46,
 51, 61, 66, 68,
 76, 78, 80–83,
 93–95, 101, 105,
 108, 135, 138,
 139, 141, 143, 149
`delim_n` 83
`delim_r` 83
`page_compositor` 82
 special characters 106, 107, 135
`\MakeUppercase` 71
 memoir class 142
`mfirstruc` package 71

N

`\name` 94
`\newacronym`
 6, 24, 25, 28, 52,
 52, 53, 55, 58,
 59, 77, 102, 103, 153
`\newglossary`
 14, 15, 20, 51,
 75, 93, 94, 141, 147
`\newglossaryentry`
 6, 20, 23, 25,
 30, 36, 38, 53,
 75, 96, 102, 103, 153
`\newglossaryentry` options
 counter 96
 description
 20, 27, 28, 30,
 41, 53, 55, 75–
 77, 94, 96, 103,
 126, 132, 154, 161
`descriptionplural` 30, 41, 127
`first` 30,
 31, 36, 38, 39,
 41, 45, 53, 59,
 95, 98, 103, 113,
 120, 133, 159, 162
`firstplural` 31,
 32, 39–41, 45,
 95, 98, 103, 123, 133
`format` 38, 136
`name` 20, 22, 27, 28,
 30, 31, 33, 40,
 45, 55, 68, 75,
 76, 94–96, 124, 131
`nonumberlist` 31, 96
`parent` 21, 30, 32, 96

`plural` 23, 30–
 33, 39–41, 45,
 95, 98, 103, 122
 see 3, 23, 31, 37, 44, 96
`sort` 17, 22, 28,
 31, 33, 55, 68,
 75, 76, 95, 133, 149
`symbol` 27, 28,
 31, 40–42, 53–
 55, 70, 75, 76,
 94, 95, 103, 129,
 132, 156–159,
 162, 175, 180, 190
`symbolplural` 31, 41, 130
`text` 28,
 30, 31, 36, 38,
 39, 41, 45, 53,
 59, 95, 103, 113,
 119, 132, 156, 159
`type` 21, 31,
 34, 75, 96, 102, 133
`\newglossarystyle`
 62, 67, 150
`\newline` 30, 62
`ngerman` package 10, 48, 89
`\nohyperpage` 36
`\noist` 8, 29,
 35, 36, 48–51, 141
`\nolist` 74
`\nolong` 74
`\nonumberlist` 74, 96
`\nopostdesc`
 22, 30, 33, 62, 81
`\nostyles` 75
`\nosuper` 74
`\notree` 74
 number list 6,
 7, 13, 20, 27, 29–
 33, 35, 36, 44,
 50, 51, 62–65, 69
`\numberedsection` 73
`\numberline` 72

O

`\oldacronym` 59, 59, 153
`\order` 78

P

package options
`acronym` 11,
 14, 15, 20, 25,
 26, 31, 35, 51,
 52, 75, 79, 147, 153
`counter` 27, 29, 35, 75

description
 28, 52–57, 159
`dua` 28, 52–55, 57, 159
`footnote` 28, 52–57,
 113–119, 157,
 159, 161, 191–195
`makeindex` 28
`nolist` 27, 62, 166
`nolong`
 27, 62, 63, 166, 173
`nonumberlist`
 19, 27, 35, 69, 74
`nostyles`
 27, 62, 63, 65, 66
`nosuper` 27, 62, 65, 166
`notree` 27, 66, 166
`numberedsection` 26, 46
`autolabel` 26
`false` 26
`nolabel` 26
`numberline` 25, 72
`order` 29
`letter` 7, 13, 29
`word` 7, 13, 29
`sanitize`
 27, 54, 57, 58,
 75, 76, 94, 131, 132
`description` 54, 56
`symbol` 54–57
`section` 19, 25, 73, 84
`shortcuts` 28, 52, 58
`smallcaps` 15,
 28, 52–54, 56, 57
`smaller` 15, 16,
 28, 52–54, 56, 57
`style` 19,
 27, 46, 60, 73, 166
`toc` 18, 20, 25, 46, 72
`true` 72
`translate` 77
`xindy` 9, 12–14,
 28, 30, 47, 51, 78

`\pagelistname` 11, 80
`\parent` 96
`\phantomsection` 84
`\plural` 95
`\printglossaries`
 17, 18, 29,
 46, 83, 92, 94,
 142, 145, 147, 168

`\printglossary`
 17, 27, 29, 46,
 60, 62, 83, 93,
 142, 145, 147, 168

\printglossary	options	\sublistdotted	172	translator package
		\subsubitem	184	10, 16, 18,
	nonumberlist .	\super	178	72, 80, 196, 201–204
	numberedsection	\super3col	179	\tree
	46, 147	\super3colborder	179	185
	style 27, 46, 60, 62, 147	\super3colheader	180	\treegroup
	title	\super3colheaderborder	180	\treehypergroup
	toctitle	\super4col	180	\treenoname
	type	\super4colborder	181	\treenonamegroup
\protect	75	\super4colheader	181	\treenonamehypergroup
	R	\super4colheaderborder	187	
\relsize package	53, 57			\type
\roman	136	\superborder	178	96
\rootlanguagename	89	\superheader	178	
	S	\superheaderborder	179	W
\sanitize	76	\supertabular package	27, 65, 74, 166, 177	\warn@nomakeglossaries
\section	73	\symbol	95	141
\see	96	\symbolname	11, 80	\warn@noprintglossary
\seename	23, 44, 80	\symbolplural	95	145
\setAlphaCompositor	50			\writeist
\setCompositor	50	T		81, 86, 87, 136
\setentrycounter	150	\text	95	
\setglossarysection	26, 84	\textbf	37	X
\setStyleFile	14, 29, 81	\textrm	49	
\shotcuts	77	\textsc	56	xindy
\smallcaps	77	\textsmaller	57	12–14, 16, 17, 20, 22,
\smaller	57, 77	the glossary (environment)	67, 148	24, 28–31, 35–38, 46–51, 66,
\sort	95	\thepage	49	68, 76, 78, 81, 82, 85–88, 90,
\style	73	\toc	72	100, 111, 135–137, 143, 146, 149
\subitem	184	\translate	77	xkeyval package
				5, 15
				\xmakefirststuc
				71, 168
				\xspace
				59
				xspace package
				59, 153