

Grzegorz Murzynowski

The gutils Package^{*}

Written by Grzegorz Murzynowski,
natror at o2 dot pl

© 2005, 2006, 2007, 2008 by Grzegorz Murzynowski.

This program is subject to the L^AT_EX Project Public License.

See <http://www.ctan.org/tex-archive/help/Catalogue/licenses.lppl.html>
for the details of that license.

LPPL status: "author-maintained".

Many thanks to my T_EX Guru Marcin Woliński for his T_EXnical support.

```
84 \NeedsTeXFormat{LaTeX2e}
85 \ProvidesPackage{gutils}
86 [2008/10/04] v0.95 some rather TeXnical macros, some of them
               tricky (GM)
```

Contents

Intro	2	Macros for printing macros and filenames	19
Installation	2	Storing and restoring the meanings of cses	21
Contents of the gutils.zip archive	2	Not only preamble!	24
Compiling of the documentation	2	Third person pronouns	25
A couple of abbreviations	3	Improvements to mwcls sectioning commands	26
\firstofoone and the queer \catcodes	4	An improvement of MW's \SetSectionFormatting	28
Global Boolean switches	4	Negative \addvspace	29
\gm@ifundefined—a test that doesn't create any hash entry unlike \c@ifundefined	6	My heading setup for mwcls	30
Storing and restoring the catcodes of specials	7	Compatibilising standard and mwcls sectionings	31
From the ancient xparse of TeXLive 2007	7	enumerate* and itemize*	33
Ampulex Compressa-like modifications of macros	11	The logos	34
\c@ifnextcat, \c@ifnextac	13	Expandable turning stuff all into 'other'	36
\afterfi and pals	15	Brave New World of X_ET_EX	36
Environments redefined	15	Fractions	37
Almost an environment or redefinition of \begin	15	\resizegraphics	38
\c@ifenvir and improvement of \end	16	Settings for mathematics in main font	38
From relsize	16	Minion and Garamond Premier kerning and ligature fixes	42
Some 'other' stuff	18	Varia	42
Metasymbols	19	\c@ifempty	46

^{*} This file has version number v0.95 dated 2008/10/04.

\include not only .tex's	46	Typesetting dates in my memoirs	51
Faked small caps	47	A left-slanted font	56
See above/see below	48	Thousand separator	57
luzniej and napa- pierki—environments used in page breaking for money . .	49	hyperref's \nolinkurl into \url*	58
		Change History	58
		Index	60

Intro

The gutils.sty package provides some macros that are analogous to the standard L^AT_EX ones but extend their functionality, such as \@ifnextcat, \addtomacro or \begin(*). The others are just conveniences I like to use in all my TeX works, such as \afterfi, \pk or \cs.

I wouldn't say they are only for the package writers but I assume some nonzero (L)A^TE_X-awareness of the user.

For details just read the code part.

Installation

Unpack the gutils-tds.zip archive (this is an archive that conforms the TDS standard, see CTAN/tds/tds.pdf) in some texmf directory or just put the gutils.sty somewhere in the texmf/tex/latex branch. Creating a texmf/tex/latex/gm directory may be advisable if you consider using other packages written by me.

Then you should refresh your TeX distribution's files' database most probably.

Contents of the gutils.zip archive

The distribution of the gutils package consists of the following three files and a TDS-compliant archive.

```
gutils.sty
README
gutils.pdf
gutils.tds.zip
```

Compiling of the documentation

The last of the above files (the .pdf, i.e., *this file*) is a documentation compiled from the .sty file by running L^AT_EX on the gutils.sty file twice (xelatex gutils.sty in the directory you wish the documentation to be in, you don't have copy the .sty file there, TeX will find it), then MakeIndex on the gutils.idx file, and then L^AT_EX on gutils.sty once more.

MakeIndex shell command:

```
makeindex -r gutilsDoc
```

The -r switch is to forbid MakeIndex to make implicit ranges since the (code line) numbers will be hyperlinks.

Compiling the documentation requires the packages: gmdoc (gmdoc.sty and gmdoc.cls), gmverb.sty, gutils.sty, gmiflink.sty and also some standard packages: hyperref.sty, color.sty, geometry.sty, multicol.sty, lmodern.sty, fontenc.sty that should be installed on your computer by default.

If you had not installed the mwcls classes (available on CTAN and present in TeX Live e.g.), the result of your compilation might differ a bit from the .pdf provided in this .zip

archive in formatting: If you had not installed mwcls, the standard article.cls class would be used.

```

158 \ifx\XeTeXversion\relax
159   \let\XeTeXversion\@undefined% If someone earlier used \@ifundefined{%
   % \XeTeXversion} to test whether the engine is XETEX, then \XeTeXversion
   is defined in the sense of ε-TEX tests. In that case we \let it to something
   really undefined. Well, we might keep sticking to \@ifundefined, but it's
   a macro and it eats its arguments, freezing their catcodes, which is not what
   we want in line 3438.
166 \fi
168 \ifdefinable\XeTeXversion
169 \XeTeXinputencoding(utf-8)% we use Unicode dashes later in this file.
170 \fi% and if we are not in XETEX, we skip them thanks to XETEX-test.

```

A couple of abbreviations

```

\@xa 176 \let\@xa\expandafter
\@nx 177 \let\@nx\noexpand
\@xau 179 \def\@xau{\@xa\unexpanded\@xa}
\pdef 183 \def\pdef{\protected\def}

```

And this one is defined, I know, but it's not \long with the standard definition and I want to be able to \gobble a \par sometimes.

```

\gobble 190 \long\def\gobble#1{%
\@gobble 192 \let\@gobble\gobble
\gobbletwo 193 \let\gobbletwo\gobbletwo
\provide 197 \long\pdef\provide#1{%
198   \ifdefined#1%
199     \ifx\relax#1\afterfifi{\def#1}%
200     \else\afterfifi{\gmu@gobdef}%
201     \fi
202   \else\afterfi{\def#1}%
203   \fi}
\gmu@gobdef 206 \long\def\gmu@gobdef#1#2{%
207   \def\gmu@tempa{}% it's a junk macro assignment to absorb possible prefixes.
209   \gobble}
\pprovide 212 \def\pprovide{\protected\provide}

```

Note that both \provide and \pprovide may be prefixed with \global, \outer, \long and \protected because the prefixes stick to \def because all before it is expandable. If the condition(s) is false (#1 is defined) then the prefixes are absorbed by a junk assignment.

Note moreover that unlike L_AT_EX's \providecommand, our \pprovide allow any parameters string just like \def (because they just *expand* to \def).

```

\@nameedef 225 \long\def\@nameedef#1#2{%
226   \@xa\edef\csname#1\endcsname{#2}}

```

\firstofone and the queer \catcodes

Remember that once a macro's argument has been read, its \catcodes are assigned forever and ever. That's what is \firstofone for. It allows you to change the \catcodes locally for a definition *outside* the changed \catcodes' group. Just see the below usage of this macro 'with T_EX's eyes', as my T_EX Guru taught me.

```
237 \long\def\firstofone#1{#1}
```

The next command, \foone, is intended as two-argument for shortening of the \begingroup... \firstofone{\endgroup...} hack.

```
\foone 242 \long\def\foone#1{\begingroup#1\egfirstofone}  
244 \long\def\egfirstofone#1{\endgroup#1}  
\fooatletter 246 \long\def\fooatletter{\foone\makeatletter}
```

Global Boolean switches

The \newgif declaration's effect is used even in the L^AT_EX 2_E source by redefining some particular user defined ifs (UD-ifs henceforth) step by step. The goal is to make the UD-if's assignment global. I needed it at least twice during gmdoc writing so I make it a macro. It's an almost verbatim copy of L^AT_EX's \newif modulo the letter *g* and the \global prefix. (File d: ltdefns.dtx Date: 2004/02/20 Version v1.3g, lines 139–150)

```
\newgif 260 \pdef\newgif#1{  
  261   {\escapechar\m@ne  
  262     \global\let#1\iffalse  
  263     \g@if#1\iftrue  
  264     \g@if#1\iffalse  
  265 }
```

'Almost' is also in the detail that in this case, which deals with \global assignments, we don't have to bother with storing and restoring the value of \escapechar: we can do all the work inside a group.

```
\g@if 271 \def\g@if#1#2{  
  272   \protected\@xa\gdef\csname\@xa\@gobbletwo\string#1%  
  273   g% the letter g for '\global'.  
  274   \@xa\@gobbletwo\string#2\endcsname  
  275   {\global\let#1#2}}  
  
277 \pdef\newif#1{  
  278   % We not only make \newif \protected but also make it to define  
  279   \protected assignments so that premature expansion doesn't affect \if...  
  280   % \fi nesting.  
  281   \count@\escapechar\escapechar\m@ne  
  282   \let#1\iffalse  
  283   \g@if#1\iftrue  
  284   \g@if#1\iffalse  
  285   \escapechar\count@}  
  
\@if 290 \def\g@if#1#2{  
  291   \protected\@xa\def\csname\@xa\@gobbletwo\string#1%  
  292   \@xa\@gobbletwo\string#2\endcsname  
  293   {\let#1#2}}  
  
\hidden@iffalse 296 \pdef\hidden@iffalse{\iffalse}  
\hidden@iftrue 297 \pdef\hidden@iftrue{\iftrue}
```

After `\newgif\iffoo` you may type `{\foogtrue}` and the `\iffoo` switch becomes globally equal `\iftrue`. Simili modo `\foogfalse`. Note the letter `g` added to underline globalness of the assignment.

If for any reason, no matter how queer ;-) may it be, you need *both* global and local switchers of your `\if...`, declare it both with `\newif` and `\newgif`.

Note that it's just a shorthand. `\global\if<switch>true/false` does work as expected.

There's a trouble with `\refstepcounter`: defining `\@currentlabel` is local. So let's `\def` a `\global` version of `\refstepcounter`.

Warning. I use it because of very special reasons in gmdoc and in general it is probably not a good idea to make `\refstepcounter` global since it is contrary to the original L^AT_EX approach.

```
\grefstepcounter 318 \pdef\grefstepcounter#1{%
 319   {\let\protected@edef=\protected@xdef\refstepcounter{#1}}}
```

Naïve first try `\globaldefs=\tw@` raised an error unknown command `\reserved@e`. The matter was to globalize `\protected@edef` of `\@currentlabel`.

Thanks to using the true `\refstepcounter` inside, it observes the change made to `\refstepcounter` by `hyperref`.

2008/08/10 I spent all the night debugging `\penalty 1000` that was added after a hypertarget in vertical mode. I didn't dare to touch `hyperref`'s guts, so I worked it around with ensuring every `\grefstepcounter` to be in hmode:

```
\hhrefstepcounter 333 \pdef\hhrefstepcounter#1{%
 334   \ifhmode\leavevmode\fi\grefstepcounter{#1}}
```

By the way I read some lines from *The T_EXbook* and was reminded that `\unskip` strips any last skip, whether horizontal or vertical. And I use `\unskip` mostly to replace a blank space with some fixed skip. Therefore define

```
\hunskip 341 \pdef\hunskip{\ifhmode\unskip\fi}
```

Note the two macros defined above are `\protected`. I think it's a good idea to make `\protected` all the macros that contain assignments. There is one more thing with `\ifhmode`: it can be different at the point of `\edef` and at the point of execution.

Another shorthand. It may decrease a number of `\expandafters` e.g.

```
\glet 351 \def\glet{\global\let}
```

L^AT_EX provides a very useful `\g@addto@macro` macro that adds its second argument to the current definition of its first argument (works iff the first argument is a no argument macro). But I needed it some times in a document, where @ is not a letter. So:

```
\gaddtomacro 359 \let\gaddtomacro=\g@addto@macro
```

The redefining of the first argument of the above macro(s) is `\global`. What if we want it local? Here we are:

```
\addto@macro 364 \long\def\addto@macro#1#2{%
 365   \toks@\@xa{#1#2}%
 366   \edef#1{\the\toks@}%
 367 }% (\toks@ is a scratch register, namely \tokso.)
```

And for use in the very document,

```
\addtomacro 371 \let\addtomacro=\addto@macro
```

2008/08/09 I need to prepend something not add at the end—so

```
\prependtomacro 374 \long\def\prependtomacro#1#2{%
```

```

376  \edef#1{\unexpanded{#2}\@xa\unexpanded\@xa{#1}}}
      Note that \prependtomacro can be prefixed.

\addtotoks 380 \long\def\addtotoks#1#2{%
  #1=\@xa{\the#1#2}%

\@emptyify 384 \newcommand*\@emptyify[1]{\let#1=\@empty}
\emptyify   385 \@ifdefinable\emptyify{\let\emptyify\@emptyify}

      Note the two following commands are in fact one-argument.

\g@emptyify 389 \newcommand*\g@emptyify{\global\@emptyify}
\gemptyify   390 \@ifdefinable\gemptyify{\let\gemptyify\g@emptyify}

\@relaxen 393 \newcommand\@relaxen[1]{\let#1=\relax}
\relaxen    394 \@ifdefinable\relaxen{\let\relaxen\@relaxen}

      Note the two following commands are in fact one-argument.

\g@relaxen 398 \newcommand*\g@relaxen{\global\@relaxen}
\grelaxen   399 \@ifdefinable\grelaxen{\let\grelaxen\g@relaxen}

```

\gm@ifundefined—a test that doesn't create any hash entry unlike \ifundefined

I define it under another name not redefine \ifundefined because I can imagine an odd case when something works thanks to \ifundefined's 'relaxation effect'.

```

\gm@ifundefined 408 \long\def\gm@ifundefined#1{%
  not \protected because expandable.
  \ifcsname#1\endcsname%
  \else%
    \@xa\ifx\csname\#1\endcsname\relax%
    but as \relax
    \afterfifi\@firstoftwo%
  \else%
    \relax
    \afterfifi\@secondoftwo%
  \fi
  \else%
    not defined
    \afterfi\@firstoftwo%
  \fi}

\gm@testdefined 425 \long\def\gm@testdefined#1\iftrue{%
  This is a macro that expands to \iftrue
  or \iffalse depending on whether its argument is defined in the LATEX
  sense. Its syntax requires an \iftrue to balance \ifs with \fis.
  \csname
  \ifdefined#1%
  \ifx#1\relax
    \iffalse%
  \else\iftrue%
  \fi
  \else\iffalse%
  \fi\endcsname
}

\gm@testundefined 440 \long\def\gm@testundefined#1\iftrue{%
  we expand the last macro two levels.
  We repeat the parameter string to force the proper syntax.
  \@xa\@xa\@xa\unless\gm@testdefined#1\iftrue}

```

Storing and restoring the catcodes of specials

```
\gmu@storespecials 448 \newcommand*\gmu@storespecials[1] [] {%
  we provide a possibility of adding
  stuff. For usage see line 2673.
  450 \def\do##1{\catcode`@nx##1=\the\catcode`##1\relax}%
  451 \edef\gmu@restorespecials{\dospecials\do\^\^M#1}}
\gmu@septify 453 \newcommand*\gmu@septify[1] [] {%
  restoring the standard catcodes of specials.
  The name is the opposite of 'sanitize' :-). It restores also the original catcode
  of `^\^M
  456 \def\do{\relax\catcode`}%
  457 \do\_\_1o\do\o\do\{1\do\}\_2\do\$3\do\&4%
  458 \do\#6\do\^\_7\do\_\_8\do\%\_14\do\~\_13\do\^\^M5#1\relax}
```

From the ancient xparse of T_EXLive 2007

The code of this section is rewritten contents of the xparse package version 0.17 dated 1999/09/10, the version available in T_EX Live 2007-13, in Ubuntu packages at least. It's a stub 'im Erwartung' (Schönberg) for the L^AT_EX3 bundle and it does what I want, namely defines \DeclareDocumentCommand. I rewrote the code to use the usual catcodes (only with @ a letter) and not to use the ldcsetup package (which caused an error of undefined cs\KV@def).

Well, I add the \protected prefix to the first macro.

After exchange of some mails with Morten Høgholm and trying xparse of 2008/08/03 svn 748 (which beautifully spoils the catcodes) I wrap the ancient code in a conditional to avoid name collision if someone loads xparse before gutils

```
478 \gm@testundefined\DeclareDocumentCommand\iftrue
480 \unless\ifdef\@temptokenb
\@temptokenb 481 \newtoks\@temptokenb
482 \fi
\xparsed@args 484 \newtoks\xpased@args
\DeclareDocumentCommand 486 \long\def\DeclareDocumentCommand#1#2#3{%
  % #1 command to be defined,
  % #2 arguments specification,
  % #3 definition body.
  492 \@tempcnta\z@
  493 \toks@{}%
  494 \@temptokena\toks@
  495 \@temptokenb\toks@
  496 \@ddc#2X% X is the guardian of parsing.
  \protected\edef#1{\% The \protected prefix is my (GM) addition.
  498 \nx@\ddc@
  499 {\the\toks@}%
  500 \xa\nx\csname\string#1\endcsname
  501 \nx#1%
  502 }%
  503 \long\xa\def\csname\string#1\xa\endcsname
  504 \the\@temptokena{#3}}
\DeclareDocumentEnvironment 506 \long\def\DeclareDocumentEnvironment#1#2#3#4{%
  507 \xa\DeclareDocumentCommand\csname#1\endcsname{#2}{%
    \xpased@args\toks@}
```

```

509      #3}%
510      \@xa\let\csname_end#1\endcsname\@parsed@endenv
511      \long\@xa\def\csname_end\string\\#1\@xa\endcsname
512      \the\@temptokena{#4}}
513
514 \def\@parsed@endenv{%
515     \@xa\@parsed@endenv@\the\xparsed@args}
516
517 \def\@parsed@endenv@#1{%
518     \csname_end\string#1\endcsname}
519
520 \def\@ddc@#1#2#3{%
521     \ifx\protect\@typeset@protect
522     \@xa\@firstofone
523     \else
524     \protect#3\@xa\@gobble
525     \fi
526     {\toks@{#2}#1\the\toks@}}
527
528 \def\@ddc#1{%
529     \ifx#1X%
530     \else
531     \ifx#1m%
532     \addto@hook\@temptokenb_m%
533     \else
534     \toks@{\@xa{%
535         \the\@xa\toks@
536         \csname_\@ddc@\the\@temptokenb\@xa\endcsname
537         \csname_\@ddc@#1\endcsname}%
538     \@temptokenb{}}%
539     \fi
540     \advance\@tempcnta\@ne
541     \@temptokena\@xa{%
542         \the\@xa\@temptokena\@xa##\the\@tempcnta}%
543     \@xa
544     \@ddc
545     \fi}
546
547 \def\@ddc@s{%
548     \ifstar
549     {\addto@hook\toks@\BooleanTrue#1\toks@}%
550     {\addto@hook\toks@\BooleanFalse#1\toks@}}
551
552 \def\@ddc@m{%
553     \addto@hook\toks@{\{\#2\}}#1\toks@}%
554
555 \def\@ddc@o{%
556     \ifnextchar[%]
557     {\@ddc@o@{#1}}
558     {\addto@hook\toks@\NoValue#1\toks@}}
559
560 \def\@ddc@o@[#2]{%
561     \addto@hook\toks@{\{\#2\}}#1\toks@}
562
563 \def\@ddc#1{%
564     \ifx#1X%
565     \perhaps@grab@ms
566     \else

```

```

567  \ifx#1m%
568  \addto@hook\@temptokenb\m%
569  \else
570  \toks@\@xa{%
571  \the\@xa\toks@
572  \csname\@ddc@x\the\@temptokenb\@xa\endcsname
573  \csname\@ddc@#1\endcsname}%
574  \@temptokenb{}%
575  \ifx#10%
576  \let\next@ddc\grab@default
577  \else
578  \ifx#1C%
579  \let\next@ddc\grab@default
580  \fi
581  \fi
582  \fi
583  \advance\@tempcnta\@ne
584  \@temptokena\@xa{%
585  \the\@xa\@temptokena\@xa##\the\@tempcnta}%
586  \@xa
587  \next@ddc
588  \fi
589 }%
590 \let\next@ddc\@ddc
591 \def\grab@default#1{%
592  \toks@\@xa{%
593  \the\toks@
594  {#1}}%
595  \let\next@ddc\@ddc
596  \next@ddc
597  \fi
598 }
599 \long\def\@ddc@0#1#2\toks@{%
600  \@ifnextchar[%
601  {\@ddc@o@{#2}}%
602  {\@addto@hook\toks@{{#1}}#2\toks@}}
603 \long\def\@ddc@c#1\toks@{%
604  \@ifnextchar(%
605  {\@ddc@c@#1}%
606  {\PackageError{xparse}{Missing~coordinate~argument}%
607  {A~value~of~(o,o)~is~assumed}%
608  \addto@hook\toks@{{oo}}#1\toks@}}
609  \fi
610 }
611 \long\def\@ddc@c@#1(#2,#3){%
612  \addto@hook\toks@{{{{#2}}{#3}}}}#1\toks@}
613 \long\def\@ddc@c@#1#2\toks@{%
614  \@ifnextchar(%
615  {\@ddc@c@#2}%
616  {\@addto@hook\toks@{{#1}}#2\toks@}}
617 \long\def\perhaps@grab@ms\relax
618 \def\grab@ms{%
619  \toks@\@xa{%
620  \relax
621  \let\perhaps@grab@ms\relax
622  \def\grab@ms{%
623  \toks@\@xa{%

```

```

624     \the\@xa\toks@
625     \csname_@ddc@x\the\@temptokenb\endcsname
626   }
628 \let\@ddc@m\undefined
630 \long\def\@ddc@xm#1\toks@#2{%
631   \addto@hook\toks@{\{#2\}}#1\toks@}
633 \long\def\@ddc@xmm#1\toks@#2#3{%
634   \addto@hook\toks@{\{#2\}{#3}}#1\toks@}
636 \long\def\@ddc@xmmm#1\toks@#2#3#4{%
637   \addto@hook\toks@{\{#2\}{#3}{#4}}#1\toks@}
639 \long\def\@ddc@xmwww#1\toks@#2#3#4#5{%
640   \addto@hook\toks@{\{#2\}{#3}{#4}{#5}}#1\toks@}
642 \long\def\@ddc@xmwwwm#1\toks@#2#3#4#5#6{%
643   \addto@hook\toks@{\{#2\}{#3}{#4}{#5}{#6}}#1\toks@}
645 \long\def\@ddc@xmwwwmm#1\toks@#2#3#4#5#6#7{%
646   \addto@hook\toks@{\{#2\}{#3}{#4}{#5}{#6}{#7}}#1\toks@}
648 \long\def\@ddc@xmwwwmm#1\toks@#2#3#4#5#6#7#8{%
649   \addto@hook\toks@{\{#2\}{#3}{#4}{#5}{#6}{#7}{#8}}#1\toks@}
651 \long\def\@ddc@xmwwwmm#1\toks@#2#3#4#5#6#7#8#9{%
652   \addto@hook\toks@{\{#2\}{#3}{#4}{#5}{#6}{#7}{#8}{#9}}#1\toks@}
654 \long\def\@ddc@xmwwwmm#1\the\toks@#1#2#3#4#5#6#7#8#9{%
655   \addto@hook\toks@{\{#1\}{#2}{#3}{#4}{#5}{#6}{#7}{#8}{#9}}\the%
   \toks@}
657 \let\@ddc@x\relax
659 \long\def\DeclareDocumentEnvironment#1#2#3#4{%
660   @_a\DeclareDocumentCommand\csname#1\endcsname{#2}{%
661     #3}%
662   \namedef{end#1}{#4}%
663 }
664 \let\@parsed@endenv\undefined
665 \let\@parsed@endenv@\undefined
666 \def\IfSomethingTF#1{\def\something@in{#1}\If@SomethingTF}
667 \def\IfSomethingT#1#2#3{\def\something@in{#1}%
668   \If@SomethingTF{#2}{#3}\empty}
670 \def\IfSomethingF#1#2#3{\def\something@in{#1}%
671   \If@SomethingTF{#2}\empty{#3}}
673 \def\If@SomethingTF#1{%
674   \def\something@tmp{#1}%
675   \ifx\something@tmp\something@in
676     @_a\@secondofthree
677   \else
678     @_a\def @_a\something@tmpb @_a{#1}%
679     \ifx\something@tmp\something@tmpb
680       @_a @_a @_a\@thirdofthree
681     \else
682       @_a @_a @_a\@firstofone
683     \fi
684   \fi

```

```

685   { \@xa\If@SomethingTF\@xa{#1} }%
686 }

\@secondofthree 688 \long\def\@secondofthree#1#2#3{#2}
\@thirdofthree 689 \long\def\@thirdofthree#1#2#3{#3}
\noValue 690 \def\noValue{-\noValue-}
\noValueInIt 691 \def\noValueInIt{\noValue}
\IfNoValueTF 692 \def\IfNoValueTF{\IfSomethingTF\noValue}
\IfNoValueT 693 \def\IfNoValueT{\IfSomethingT\noValue}
\IfNoValueF 694 \def\IfNoValueF{\IfSomethingF\noValue}
\IfValueTF 695 \def\IfValueTF#1#2#3{\IfNoValueTF{#1}{#3}{#2}}
\IfValueT 696 \let\IfValueT\IfNoValueF
\IfValueF 697 \let\IfValueF\IfNoValueT
\BooleanFalse 698 \def\BooleanFalse{TF}
\BooleanTrue 699 \def\BooleanTrue{TT}
\IfBooleanTF 700 \def\IfBooleanTF#1{%
  \if#1%
  \@xa\@firstoftwo
  \else
  \@xa\@secondoftwo
  \fi
}

\IfBooleanT 708 \def\IfBooleanT#1#2{%
  \IfBooleanTF{#1}{#2}\@empty
}

\IfBooleanF 712 \def\IfBooleanF#1{%
  \IfBooleanTF{#1}\@empty
}

\fi% of \unless\ifdefined\DeclareDocumentCommand.

```

Ampulex Compressa-like modifications of macros

Ampulex Compressa is a wasp that performs brain surgery on its victim cockroach to lead it to its lair and keep alive for its larva. Well, all we do here with the internal L^AT_EX macros resembles Ampulex's actions but here is a tool for a replacement of part of macro's definition.

The \ampulexdef command takes its #2 which has to be a macro and replaces part of its definition delimited with #5 and #6 with the replacement #7. The redefinition may be prefixed with #1. #2 may have parameters and for such a macro you have to set the parameters string and arguments string (the stuff to be taken by the one-step expansion of the macro) as the optional [#3] and [#4].. If \ampulexdef doesn't find the start and end tokens in the meaning of the macro, it does nothing to it. You have to write ##### instead of # or you can use \ampulexhash as well. For an example use see line 1707.

```

\ampulexdef 751 \DeclareDocumentCommand\ampulexdef{O{}mO{}O{}mmmm}{%
  % [#1] definition prefix, empty by default,
  % #2 macro to be redefined,
  % [#3] \def parameters string, empty by default,
  % [#4] definition body parameters to be taken in a one-step expansion of the
        redefined macro, empty by default,
  % #5 start token(s),
  % #6 end token(s)
}

```

% #7 replacement.

For the example of usage see [1707](#).

```
\gmu@tempa 766 \def\gmu@tempa{\#5}%
\gmu@tempb 767 \def\gmu@tempb{\#6}%
\gmu@tempc 768 \def\gmu@tempc{\#7}% we wrap the start, end and replacement tokens in macros
          to avoid unbalanced \ifs.
770 \edef\gmu@tempd{%
771   \long\def\@nx\gmu@tempd
772   #####1\all@other\gmu@tempa
773   #####2\all@other\gmu@tempb
774   #####3\@nx\gmu@tempd{%
775     \@ifempty{#####3}{\hidden@iffalse}{\hidden@iftrue}}}}%
777 \gmu@tempd% it defines \gmu@tempc to produce an open \if depending on whether
          the start and end token(s) are found in the meaning of #2.
781 \edef\gmu@tempe{%
782   \@nx\gmu@tempd\all@other#2%
783   \all@other\gmu@tempa
784   \all@other\gmu@tempb\@nx\gmu@tempd
785 }%
787 \gmu@tempe% we apply the checker and it produces an open \if.
789 \edef\gmu@tempd{%
790   \long\def\@nx\gmu@tempd
791   #####1\@xa\unexpanded\@xa{\gmu@tempa}%
792   #####2\@xa\unexpanded\@xa{\gmu@tempb}%
793   #####3\@nx\ampulexdef{}% we define a temporary macro with the parameters
          delimited with the 'start' and 'end' parameters of \ampulexdef.
794   \@nx\unexpanded{#####1}%
795   \@nx\@xa\@nx\unexpanded
796   \@nx\@xa{\@nx\gmu@tempc}% we replace the part of the redefined macro's
          meaning with the replacement text.
797   \@nx\unexpanded{#####3}}}}%
800 \gmu@tempd
802 \edef\gmu@tempf{\#4}%
805 \edef\gmu@tempe{%
806   \#1\def\@nx#2#3{%
807     \@xa\@xa\@xa\gmu@tempd\@xa#2\gmu@tempf\ampulexdef}}%
808   \gmu@tempe
809   \fi}
810 }
\ampulexhash 812 \def\ampulexhash{####}% for your convenience (not to count the hashes).
```

For the heavy debugs I was doing while preparing gmdoc, as a last resort I used \showlists. But this command alone was usually too little: usually it needed setting \showboxdepth and \showboxbreadth to some positive values. So,

```
\gmshowlists 820 \def\gmshowlists{\showboxdepth=1000\showboxbreadth=1000%
          \showlists}
\nameshow 824 \newcommand\nameshow[1]{\@xa\show\csname#1\endcsname}
\nameshowthe 825 \newcommand\nameshowthe[1]{\@xa\showthe\csname#1\endcsname}
```

Note that to get proper \showthe\my@dimen14 in the 'other' @'s scope you write \nameshowthe{\my@dimen}14.

Standard \string command returns a string of 'other' chars except for the space, for which it returns \space. In gmdoc I needed the spaces in macros' and environments' names to be always \space, so I define

```

\xiistring 836 \def\xiistring#1{%
837   \if@nx#1\xiispace
838     \xiispace
839   \else
840     \string#1%
841   \fi}

```

\@ifnextcat, \@ifnextac

As you guess, we \def \@ifnextcat à la \ifnextchar, see L^AT_EX 2_ε source dated 2003/12/01, file d, lines 253–271. The difference is in the kind of test used: while \ifnextchar does \ifx, \@ifnextcat does \ifcat which means it looks not at the meaning of a token(s) but at their \catcode(s). As you (should) remember from *The T_EXbook*, the former test doesn't expand macros while the latter does. But in \@ifnextcat the peeked token is protected against expanding by \noexpand. Note that the first parameter is not protected and therefore it shall be expanded if it's a macro. Because an assignment is involved, you can't test whether the next token is an active char.

```

@ifnextcat 858 \long\def\@ifnextcat#1#2#3{%
862   \def\reserved@d{#1}%
863   \def\reserved@a{#2}%
864   \def\reserved@b{#3}%
865   \futurelet\@let@token\@ifncat}

@ifncat 868 \def\@ifncat{%
869   \ifx\@let@token\@sptoken
870     \let\reserved@c\@xifncat
871   \else
872     \ifcat\reserved@d\@nx\@let@token
873       \let\reserved@c\reserved@a
874     \else
875       \let\reserved@c\reserved@b
876     \fi
877   \fi
878   \reserved@c}

880 {\def\:{\let\@sptoken=\global\:}% this makes \@sptoken a space token.
883 \def\:{\@xifncat}\@xa\gdef\:{\futurelet\@let@token\@ifncat}}

```

Note the trick to get a macro with no parameter and requiring a space after it. We do it inside a group not to spoil the general meaning of \: (which we extend later).

The next command provides the real \if test for the next token. It should be called \@ifnextchar but that name is assigned for the future \ifx text, as we know. Therefore we call it \@ifnextif.

```

@ifnextif 894 \long\pdef\@ifnextif#1#2#3{%
898   \def\reserved@d{#1}%
899   \def\reserved@a{#2}%
900   \def\reserved@b{#3}%
901   \futurelet\@let@token\@ifnif}

@ifnif 904 \def\@ifnif{%
905   \ifx\@let@token\@sptoken
906     \let\reserved@c\@xifnif

```

```

907   \else
908     \if\reserved@d\@nx\@let@token
909       \let\reserved@c\reserved@a
910     \else
911       \let\reserved@c\reserved@b
912     \fi
913   \fi
914 \reserved@c}

917 {\def\:{\let\@sptoken= }% this makes \@sptoken a space token.
919 \def\:{\@xifnif}\@xa\gdef\:{\futurelet\@let@token\@ifnif}}

```

But how to peek at the next token to check whether it's an active char? First, we look with \@ifnextcat whether there stands a group opener. We do that to avoid taking a whole {\dots} as the argument of the next macro, that doesn't use \futurelet but takes the next token as an argument, tests it and puts back intact.

```

\@ifnextac 930 \long\pdef\@ifnextac#1#2{%
931   \@ifnextcat\bgroup{\#2}{\gm@ifnac{\#1}{\#2}}}

\gm@ifnac 933 \long\def\gm@ifnac#1#2#3{%
934   \ifcat\@nx~\@nx#3\afterfi{\#1#3}\else\afterfi{\#2#3}\fi}

```

Yes, it won't work for an active char \let to {₁, but it *will* work for an active char \let to a char of catcode ≠ 1. (Is there anybody on Earth who'd make an active char working as \bgroup?)

Now, define a test that checks whether the next token is a genuine space, ₁₀ that is. First define a cs let such a space. The assignment needs a little trick (*The TeXbook* appendix D) since \let's syntax includes one optional space after =.

```

947 \let\gmu@reserved@da\*%
\* 948 \def\*{%
949   \let\*\gmu@reserved@da
950   \let\gm@let@space= }%
951 \* }%

\@ifnextspace 954 \def\@ifnextspace#1#2{%
955   \let\gmu@reserved@da\*%
\* 956 \def\*{%
957   \let\*\gmu@reserved@da
958   \ifx\@let@token\gm@let@space\afterfi{\#1}%
959   \else\afterfi{\#2}%
960   \fi}%
961 \futurelet\@let@token\*}

```

First use of this macro is for an active – that expands to --- if followed by a space. Another to make dot checking whether is followed by ~ without gobbling the space if it occurs instead.

Now a test if the next token is an active line end. I use it in gmdoc and later in this package for active long dashes.

```

\foone\obeylines{%
\@ifnextMac 970 \long\pdef\@ifnextMac#1#2{%
971   \@ifnextchar^{\M{\#1}{\#2}}}
972 }

```

\afterfi and pals

It happens from time to time that you have some sequence of macros in an `\if...` and you would like to expand `\fi` before expanding them (e.g., when the macros should take some tokens next to `\fi...` as their arguments). If you know how many macros are there, you may type a couple of `\expandafters` and not to care how terrible it looks. But if you don't know how many tokens will there be, you seem to be in a real trouble. There's the Knuthian trick with `\next`. And here another, revealed to me by my TEX Guru.

I think the situations when the Knuthian (the former) trick is not available are rather seldom, but they are imaginable at least: the `\next` trick involves an assignment so it won't work e.g. in `\edef`.

```
\afterfi 997 \long\def\afterfi#1#2\fi{\fi#1}
```

And two more of that family:

```
\afterfifi 999 \long\def\afterfifi#1#2\fi#3\fi{\fi\fi#1}  
\afteriffifi 1001 \long\def\afteriffifi#1#2\fi#3\fi{\fi#1}
```

Notice the refined elegance of those macros, that cover both 'then' and 'else' cases thanks to `#2` that is discarded.

```
\afterififfififi 1005 \long\def\afterififfififi#1#2\fi#3\fi#4\fi{\fi#1}  
\afteriffififi 1006 \long\def\afteriffififi#1#2\fi#3\fi#4\fi{\fi\fi#1}  
\afterfififi 1007 \long\def\afterfififi#1#2\fi#3\fi#4\fi{\fi\fi\fi#1}
```

Environments redefined

Almost an environment or redefinition of `\begin`

We'll extend the functionality of `\begin`: the non-starred instances shall act as usual and we'll add the starred version. The difference of the latter will be that it won't check whether the 'environment' has been defined so any name will be allowed.

This is intended to structure the source with named groups that don't have to be especially defined and probably don't take any particular action except the scoping.

(If the `\begin*`'s argument is a (defined) environment's name, `\begin*` will act just like `\begin`.)

Original LATEX's `\begin`:

```
\def\begin#1%  
  \@ifundefined{#1}%  
    {\def\reserved@a{\@latex@error{Environment #1  
      undefined}\@eha}}%  
    {\def\reserved@a{\def\@currenvir{#1}%  
      \edef\@currenvline{\on@line}%  
      \csname #1\endcsname}}%  
  \@ignorefalse  
  \begingroup\@endpefalse\reserved@a}  
  
\@begnamedgroup 1039 \long\def\@begnamedgroup#1%  
  1040  \@ignorefalse% not to ignore blanks after group  
  1041  \begingroup\@endpefalse  
  1042  \edef\@currenvir{#1}% We could do recatcoding through \string but all the  
        name 'other' could affect a thousand packages so we don't do that and we'll  
        recatcode in a testing macro, see line 1087.  
  1046  \edef\@currenvline{\on@line}%
```

1047 \csname\#1\endcsname}% if the argument is a command's name (an environment's e.g.), this command will now be executed. (If the corresponding control sequence hasn't been known to TeX, this line will act as \relax.)

Let us make it the starred version of \begin.

```

\begin* 1056 \def\begin{\@ifstar{\@begnamedgroup}{%
\begin 1057         \@begnamedgroup@ifcs}}
\@begnamedgroup@ifcs 1060 \def\@begnamedgroup@ifcs#1{%
1061     \ifcsname#1\endcsname\afterfi{\@begnamedgroup{#1}}%
1062     \else\afterfi{\@latex@error{Environment #1 undefined}\@eha}%
1063     \fi}%

```

\@ifenvir **and improvement of \end**

It's very clever and useful that `\end` checks whether its argument is `\ifx`-equivalent `\@currenvir`. However, in standard L^AT_EX it works not quite as I would expect: Since the idea of environment is to open a group and launch the cs named in the `\begin`'s argument. That last thing is done with `\csname ... \endcsname` so the catcodes of chars are irrelevant (until they are `\active`, 1, 2 etc.). Thus should be also in the `\end`'s test and therefore we ensure the compared texts are both expanded and made all 'other'.

First a (not expandable) macro that checks whether current environment is as given in #1. Why is this macro `\long`?—you may ask. It's `\long` to allow environments such as `\string\par`.

```
\@ifenvir 1087 \long\def\@ifenvir#1#2#3{%
 1089   \edef\gmu@reserveda{\@xa\string\csname\@currenvir\endcsname}%
 1090   \edef\gmu@reservedb{\@xa\string\csname#1\endcsname}%
 1091   \ifx\gmu@reserveda\gmu@reservedb\afterfi{#2}%
 1092   \else\afterfi{#3}%
 1093   \fi}
\@checkend 1095 \def\@checkend#1{\@ifenvir{#1}{}{\@badend{#1}}}
```

Thanks to it you may write `\begin{macrocode*}` with *₁₂ and end it with `\end{macrocode*}` with *₁₁ (that was the problem that led me to this solution). The error messages looked really funny:

! LaTeX Error: \begin{macrocode*} on input line 1844 ended by
 \end{macrocode*}

You might also write also `\end{macrocode}\star` where `\star` is defined as 'other' star or letter star.

From `relsize`

As file `relsize.sty`, v3.1 dated July 4, 2003 states, L^AT_EX 2 _{ϵ} version of these macros was written by Donald Arseneau asnd@triumf.ca and Matt Swift swift@bu.edu after the L^AT_EX 2.09 `smaller.sty` style file written by Bernie Cosell cose11@WTTI.MA.BBN.COM.

I take only the basic, non-math mode commands with the assumption that there are the predefined font sizes.

\relsize You declare the font size with `\relsize{<n>}` where $<n>$ gives the number of steps ("mag-step" = factor of 1.2) to change the size by. E.g., $n = 3$ changes from `\normalsize` to `\LARGE` size. Negative n selects smaller fonts. `\smaller == \relsize{-1}; \larger == \relsize{1}.` `\smallerr(my addition) == \relsize{-2}; \largerr` guess yourself.

(Since `\DeclareRobustCommand` doesn't issue an error if its argument has been defined and it only informs about redefining, loading `relsize` remains allowed.)

```

\relsize 1135 \pdef\relsize#1{%
  1136   \ifmmode\c@nomath\relsize\else
  1137     \begingroup
  1138       \c@tempcnta% assign number representing current font size
  1139       \ifx\currsize\normalsize\else\c@tempcnta% funny order is to have most
  1140         ...
  1141         \ifx\currsize\small\else\c@tempcnta% ...likely sizes checked first
  1142           \ifx\currsize\footnotesize\else
  1143             \ifx\currsize\large\else
  1144               \ifx\currsize\Large\else
  1145                 \ifx\currsize\LARGE\else
  1146                   \ifx\currsize\scriptsize\else
  1147                     \ifx\currsize\tiny\else
  1148                       \ifx\currsize\huge\else
  1149                         \ifx\currsize\Huge\else
  1150                           4\rs@unknown@warning% unknown state: \normalsize as
                                starting point
  1151                           \fi\fi\fi\fi\fi\fi\fi\fi\fi
  1152   Change the number by the given increment:
  1153   \advance\c@tempcnta#1\relax
  1154   watch out for size underflow:
  1155   \ifnum\c@tempcnta<\z@\rs@size@warning{small}{\string\tiny}%
    1156     \c@tempcnta\z@\fi
  1157   \c@xa\endgroup
  1158   \ifcase\c@tempcnta% set new size based on altered number
    1159     \tiny\or\scriptsize\or\footnotesize\or\small\or
      \normalsize\or
      \large\or\Large\or\Large\or\LARGE\or\huge\or\huge\or\Huge\else
        \rs@size@warning{large}{\string\Huge}\Huge
  1160   \fi\fi}% end of \relsize.

\rs@size@warning 1162 \providecommand*\rs@size@warning[2]{\PackageWarning{gmutils}%
  (relsize)}{%
  1163   \csize requested is too #1.\MessageBreak Using #2 instead}
\rs@unknown@warning 1165 \providecommand*\rs@unknown@warning{\PackageWarning{gmutils}%
  (relsize)}{Current font size
  1166  is unknown! (Why?!?)\MessageBreak Assuming \string\normalsize}

```

And a handful of shorthands:

```

\larger 1170 \ DeclareRobustCommand*\larger[1][\cne]{\relsize{+\#1}}
\smaller 1171 \ DeclareRobustCommand*\smaller[1][\cne]{\relsize{-\#1}}
\textlarger 1172 \ DeclareRobustCommand*\textlarger[2][\cne]{{\relsize{+\#1}\#2}}
\textsmaller 1173 \ DeclareRobustCommand*\textsmaller[2][\cne]{{\relsize{-\#1}\#2}}
\largerr 1174 \pdef\largerr{\relsize{+2}}
\smallerr 1175 \pdef\smallerr{\relsize{-2}}

```

Some ‘other’ stuff

Here I define a couple of macros expanding to special chars made ‘other’. It’s important the cs are expandable and therefore they can occur e.g. inside `\csname ... \endcsname` unlike e.g. cs’es `\chardef`.

```

1185 \foone{\catcode`\_=_8}%
\subs {\let\subs=_}
1188 \foone{@makeother\_}%
\xiunder {\def\xiunder{_}}
1191 \ifdefined\XeTeXversion
\xiunder \def\xiunder{\char"005F}%
1193 \let\_ \xiunder
1194 \fi
1196 \foone{\catcode`[\_=1@\makeother\{%
1197 \catcode`\]=2@\makeother\}}%
1198 [%]
\xiilbrace \def\xiilbrace[{}]
\xiirbrace \def\xiirbrace[{}]]%
1201 ]% of \firstofone

```

Note that L^AT_EX’s `\@charlb` and `\@charrb` are of catcode 11 (‘letter’), cf. The L^AT_EX 2_ε Source file k, lines 129–130.

Now, let’s define such a smart `_` (underscore) which will be usual `_8` in the math mode and `_12` (‘other’) outside math.

```

1212 \foone{\catcode`\_=\active}
1213 {%
\smartunder \newcommand*\smartunder{%
1215 \catcode`\_=\active
1216 \def_{\ifmmode\subs\else\_\\fi}}% We define it as \_ not just as \xiunder
                                because some font encodings don’t have _ at the \char`\_ position.
1222 \foone{\catcode`\!=o
1223 \@makeother\\}
1224 {!newcommand!*\xiibackslash{}}

\bslash \let\bslash=\xiibackslash
1228 \foone{@makeother\%}
\xipercent \def\xipercent{%%}
1233 \foone{@makeother\&}%
\xiand \def\xiand{&}
1236 \foone{@makeother\_\_}%
\xispace \def\xispace{\_}
1239 \foone{@makeother\_\_}%
1240 \def\xispace{\_}

```

We introduce `\visibleinspace` from Will Robertson’s `xltextra` if available. It’s not sufficient `\@ifpackageloaded{xltextra}` since `\xxt@visibleinspace` is defined only unless `no-verb` option is set. 2008/08/06 I recognized the difference between `\xiispace` which has to be plain ‘other’ char (used in `\xiistring`) and something visible to be printed in any font.

```

1249 \AtBeginDocument{%
1250 \ifdefined\xxt@visibleinspace
1251 \let\visibleinspace\xxt@visibleinspace
1252 \else

```

```

1253     \let\visiblespace\xiispace
1254     \fi}

```

Metasymbols

I fancy also another Knuthian trick for typesetting *metasymbols* in *The T_EXbook*. So I repeat it here. The inner `\meta` macro is copied verbatim from doc's v2.1b documentation dated 2004/02/09 because it's so beautifully crafted I couldn't resist. I only don't make it `\long`.

"The new implementation fixes this problem by defining `\meta` in a radically different way: we prevent hyphenation by defining a `\language` which has no patterns associated with it and use this to typeset the words within the angle brackets."

```

\meta 1275 \pdef\meta#1{%

```

"Since the old implementation of `\meta` could be used in math we better ensure that this is possible with the new one as well. So we use `\ensuremath` around `\langle` and `\rangle`. However this is not enough: if `\meta@font@select` below expands to `\itshape` it will fail if used in math mode. For this reason we hide the whole thing inside an `\nfss@text` box in that case."

```

1283   \ensuremath\langle
1284   \ifmmode\@xa\@nfss@text\fi
1285   {%
1286     \meta@font@select

```

Need to keep track of what we changed just in case the user changes font inside the argument so we store the font explicitly.

```

1294   #1\%
1295   }\ensuremath\rangle
1296   }

```

But I define `\meta@font@select` as the brutal and explicit `\it` instead of the original `\itshape` to make it usable e.g. in the gmdoc's `\cs` macro's argument.

```

\meta@font@select 1305 \def\meta@font@select{\it}

```

The below `\meta`'s drag¹ is a version of *The T_EXbook*'s one.

```

\langle...> 1311 \def\langle#1\rangle{\meta{#1}}

```

Macros for printing macros and filenames

First let's define three auxiliary macros analogous to `\dywiz` from `polski.sty`: a short-hands for `\discretionary` that'll stick to the word not spoiling its hyphenability and that'll won't allow a linebreak just before nor just after themselves. The `\discretionary` T_EX primitive has three arguments: #1 'before break', #2 'after break', #3 'without break', remember?

```

\discr 1322 \def\discr#1#2#3{\leavevmode\kernosp%
1323   \discretionary{#1}{#2}{#3}\penalty10000\hskip0pt\relax}
\discret 1324 \def\discret#1{\leavevmode\kernosp%
1325   \discretionary{#1}{#1}{#1}\penalty10000\hskip0pt\relax}

```

¹ Think of the drags that transform a very nice but rather standard 'auntie' ('Tante' in Deutsch) into a most adorable Queen ;-).

A tiny little macro that acts like `\-` outside the math mode and has its original meaning inside math.

```
1329 \def\:{\ifmmode\afterfi{\mskip\medmuskip}\else\afterfi{\discret{%
}}\fi}
\vs 1331 \newcommand*\vs{\discre{\visiblespace}{\visiblespace}}
```

Then we define a macro that makes the spaces visible even if used in an argument (i.e., in a situation where `\catcode`ing has no effect).

```
\printspaces 1337 \def\printspaces#1{{\let~=\vs\let_==\vs\gm@pswords#1\@nil}}
\gm@pswords 1339 \def\gm@pswords#1_#2\@nil{%
1340   \ifx\relax#1\relax\else#1\fi
1341   \ifx\relax#2\relax\else\vs\penalty\hyphenpenalty\gm@pswords#2%
      \at\@nil\fi}% note that in the recursive call of \gm@pswords the argument
      string is not extended with a guardian space: it has been already
      by \printspaces.
```

`\sfname` 1346 \pdef\sfname#1{\textsf{\printspaces{#1}}}

`\gmu@discretionaryslash` 1348 \def\gmu@discretionaryslash{\discre{}{\hbox{}{}}}% the
second pseudo-argument nonempty to get \hyphenpenalty
not \exhyphenpenalty.

`\file` 1353 \pdef\file#1{\gmu@printslashes#1/\gmu@printslashes}

`\gmu@printslashes` 1355 \def\gmu@printslashes#1/#2\gmu@printslashes{%
1356 \sfname{#1}%
1357 \ifx\gmu@printslashes#2\gmu@printslashes
1358 \else
1359 \textsf{\gmu@discretionaryslash}%
1360 \afterfi{\gmu@printslashes#2\gmu@printslashes}\fi}

it allows the spaces in the filenames (and prints them as `_`).

The below macro I use to format the packages' names.

`\pk` 1368 \pdef\pk#1{\textsf{\textup{#1}}}

Some (if not all) of the below macros are copied from doc and/or ltxdoc.

A macro for printing control sequences in arguments of a macro. Robust to avoid writing an explicit `\` into a file. It calls `\ttfamily` not `\tt` to be usable in headings which are boldface sometimes.

```
\cs 1379 \DeclareRobustCommand*\cs[2][\bslash]{%
1380   \def\-\{\discretionary{\rmfamily-}{}{}\}%
1381   \def\{\{\char`\\}\def\}\{\char`\\}\ttfamily\#1\#2\}}
```

`\env` 1385 \pdef\env#1{\cs[]{#1}}

And for the special sequences like `^A`:

1388 \foone{\makeother\^}

`\hathat` 1389 {\pdef\hathat#1{\cs[^]{#1}}}

And one for encouraging linebreaks e.g., before long verbatim words.

`\possfil` 1394 \newcommand*\possfil{\hfil\penalty1000\hfilneg}

The five macros below are taken from the ltxdoc.dtx.

`\cmd{\foo}` Prints `\foo` verbatim. It may be used inside moving arguments.
`\cs{foo}` also prints `\foo`, for those who prefer that syntax. (This second form may even be used when `\foo` is `\outer`.)

`\cmd` 1404 \def\cmd#1{\cs{\@xa\cmd@to@cs\string#1}}

```

\cmd@to@cs 1406 \def\cmd@to@cs#1#2{\char\number`#2\relax}
            \marg{text} prints {text}, ‘mandatory argument’.
\marg 1410 \def\marg#1{{\ttfamily\char`\\{}\meta{#1}{\ttfamily\char`\\{}}}}
            \oarg{text} prints [text], ‘optional argument’. Also \oarg[text] does that.
\oarg 1415 \def\oarg{\@ifnextchar[\@oargsq\@arg}
\@oarg 1417 \def\@oarg#1{{\ttfamily[]}\meta{#1}{\ttfamily[]}}
\@oargsq 1418 \def\@oargsq[#1]{\@oarg{#1}}
            \parg{te,xt} prints ((te,xt)), ‘picture mode argument’.
\parg 1422 \def\parg{\@ifnextchar(\@pargp\@parg}
\@parg 1424 \def\@parg#1{{\ttfamily()}\meta{#1}{\ttfamily()}\meta{#1}}
\@pargp 1425 \def\@pargp(#1){\@parg{#1}}
            But we can have all three in one command.

1429 \AtBeginDocument{%
\arg 1430   \let\math@arg\arg
\arg 1431   \def\arg{\ifmmode\math@arg\else\afterfi{%
1432     \@ifnextchar[%]
1433     \@oargsq{\@ifnextchar(%}
1434     \@pargp\marg}}\fi}%
1435 }

```

Now you can write

```

\arg{mand.\arg} to get {mand. arg},
\arg[opt.\arg] for [opt. arg] and
\arg(pict.\arg) for (pict. arg).
And $\arg(1+i)=\pi/4$ for  $\arg(1 + i) = \pi/4$ .

```

Storing and restoring the meanings of cses

First a Boolean switch of globalness of assignments and its verifier.

```

\ifgmu@SMglobal 1450 \newif\ifgmu@SMglobal
\SMglobal 1452 \pdef\SMglobal{\gmu@SMglobaltrue}

```

The subsequent commands are defined in such a way that you can ‘prefix’ them with \SMglobal to get global (re)storing.

A command to store the current meaning of a cs in another macro to temporarily redefine the cs and be able to set its original meanig back (when grouping is not recommended):

```

\StoreMacro 1463 \pdef\StoreMacro{%
1464   \begingroup\makeatletter\@ifstar\egStore@MacroSt\egStore@Macro}

```

The unstarred version takes a cs and the starred version a text, which is intended for special control sequences. For storing environments there is a special command in line 1587.

```

\egStore@Macro 1469 \long\def\egStore@Macro#1{\endgroup\Store@Macro{#1}}
\egStore@MacroSt 1470 \long\def\egStore@MacroSt#1{\endgroup\Store@MacroSt{#1}}
\Store@Macro 1472 \long\def\Store@Macro#1{%
1473   \escapechar92
1474   \ifgmu@SMglobal\afterfi\global\fi

```

```

1475  \@xa\let\csname\gmu/store\string#1\endcsname#1%
1476  \global\gmu@SMglobalfalse}

\Store@MacroSt
1479 \long\def\Store@MacroSt#1{%
1480   \edef\gmu@smtempa{%
1481     \ifgmu@SMglobal\global\fi
1482     \c@nx\let\c@xa\c@nx\csname/gmu/store\bslash#1\endcsname% we add
1483       backslash because to ensure compatibility between \ReStoreMacro
1484       and \ReStoreMacro*, that is. to allow writing
1485       e.g. \StoreMacro{kitten} and then \RestoreMacro*kitten} to
1486       restore the meaning of \kitten.
1487     \c@xa\c@nx\csname#1\endcsname}
1488   \gmu@smtempa
1489 \global\gmu@SMglobalfalse}% we wish the globality to be just once.

```

We make the `\StoreMacro` command a three-step to allow usage of the most inner macro also in the next command.

The starred version, `\StoreMacro*` works with csnames (without the backslash). It's first used to store the meanings of robust commands, when you may need to store not only `\foo`, but also `\csname\foo\endcsname`.

The next command iterates over a list of cses and stores each of them. The cs may be separated with commas but they don't have to.

```

\StoreMacros
1506 \long\pdef\StoreMacros{\begingroup\makeatletter\Store@Macros}
\Store@Macros
1507 \long\def\Store@Macros#1{\endgroup
1508   \gmu@setsetSMglobal
1509   \let\gml@StoreCS\Store@Macro
1510   \gml@storemacros#1.}

\gmu@setsetSMglobal
1513 \def\gmu@setsetSMglobal{%
1514   \ifgmu@SMglobal
1515     \let\gmu@setSMglobal\gmu@SMglobaltrue
1516   \else
1517     \let\gmu@setSMglobal\gmu@SMglobalfalse
1518   \fi}

```

And the inner iterating macro:

```

\gml@storemacros
1521 \long\def\gml@storemacros#1{%
1522   \def\gmu@reserveda{\c@nx#1}% My TeX Guru's trick to deal with \fi and such,
1523   i.e., to hide #1 from TeX when it is processing a test's branch without expanding.
1524   \if\gmu@reserveda.% a dot finishes storing.
1525     \global\gmu@SMglobalfalse
1526   \else
1527     \if\gmu@reserveda,% The list this macro is put before may contain commas
1528       and that's O.K., we just continue the work.
1529       \afterfifi\gml@storemacros
1530   \else% what is else this shall be stored.
1531     \gml@StoreCS{#1}% we use a particular cs to may \let it both to the storing
1532       macro as above and to the restoring one as below.
1533       \afterfifi{\gmu@setSMglobal\gml@storemacros}%
1534   \fi
1535 \fi}

```

And for the restoring

```
\RestoreMacro 1543 \pdef\RestoreMacro{%
```

```

1544 \begingroup\makeatletter@ifstar\egRestore@MacroSt%
      \egRestore@Macro}
1545 \long\def\egRestore@Macro#1{\endgroup\Restore@Macro{#1}}
1546 \long\def\egRestore@MacroSt#1{\endgroup\Restore@MacroSt{#1}}
1547 \long\def\Restore@Macro#1{%
1548   \escapechar92
1549   \ifgmu@SMglobal\afterfi\global\fi
1550   \@xa\let\@xa#1\csname\gmu/store/string#1\endcsname
1551   \global\gmu@SMglobalfalse}
1552 \long\def\Restore@MacroSt#1{%
1553   \edef\gmu@smtempa{%
1554     \ifgmu@SMglobal\global\fi
1555     \c@nx\let\c@xa\c@nx\csname#1\endcsname
1556     \c@xa\c@nx\csname/gmu/store\bslash#1\endcsname}% cf. the commentary
1557     in line 1482.
1558   \gmu@smtempa
1559   \global\gmu@SMglobalfalse}
1560 \long\def\RestoreMacros{\begingroup\makeatletter\Restore@Macros}
1561 \long\def\Restore@Macros#1{\endgroup
1562   \gmu@setsetSMglobal
1563   \let\gml@StoreCS\Restore@Macro% we direct the core cs towards restoring
1564   and call the same iterating macro as in line 1510.
1565   \gml@storemacros#1.}

```

As you see, the `\RestoreMacros` command uses the same iterating macro inside, it only changes the meaning of the core macro.

And to restore *and* use immediately:

```

\StoredMacro 1578 \def\StoredMacro{\begingroup\makeatletter\Stored@Macro}
\Stored@Macro 1579 \long\def\Stored@Macro#1{\endgroup\Restore@Macro#1#1}

```

To be able to call a stored cs without restoring it.

```

\storedcsname 1582 \def\storedcsname#1{%
1583   \csname\gmu/store\bslash#1\endcsname}

```

2008/08/03 we need to store also an environment.

```

\StoreEnvironment 1587 \pdef\StoreEnvironment#1{%
1588   \StoreMacro*{#1}\StoreMacro*{end#1}}

```

```

\RestoreEnvironment 1591 \pdef\RestoreEnvironment#1{%
1593   \RestoreMacro*{#1}\RestoreMacro*{end#1}}

```

It happened (see the definition of `\@docininclude` in `gmdoc.sty`) that I needed to `\relax` a bunch of macros and restore them after some time. Because the macros were rather numerous and I wanted the code more readable, I wanted to `\do` them. After a proper defining of `\do` of course. So here is this proper definition of `\do`, provided as a macro (a declaration).

```

\StoringAndRelaxingDo 1608 \long\def\StoringAndRelaxingDo{%
1609   \gmu@SMdo@setscope
1610   \long\def\do##1{%
1611     \gmu@SMdo@scope
1612     \@xa\let\csname\gmu/store/string##1\endcsname##1%
1613     \gmu@SMdo@scope\let##1\relax}}

```

```
\gmu@SMdo@setscope 1615 \def\gmu@SMdo@setscope{%
 1616   \ifgmu@SMglobal\let\gmu@SMdo@scope\global
 1617   \else\let\gmu@SMdo@scope\relax
 1618   \fi
 1619   \global\gmu@SMglobalfalse}
```

And here is the counter-definition for restore.

```
\RestoringDo 1628 \long\def\RestoringDo{%
 1629   \gmu@SMdo@setscope
 1630   \long\def\do##1{%
 1631     \gmu@SMdo@scope
 1632     \cxa\let\cxa##1\csname\gmu@store\string##1\endcsname}}
```

Note that both `\StoringAndRelaxingDo` and `\RestoringDo` are sensitive to the `\SMglobal` ‘prefix’.

And to store a cs as explicitly named cs, i.e. to `\let` one csname another (`\n@melet` not `\cnamelet` because the latter is defined in Till Tantau’s beamer class another way) (both arguments should be text):

```
\n@melet 1640 \def\n@melet#1#2{%
 1641   \edef\gmu@nl@reserveda{%
 1642     \let\cxa\cna\cxa\csname#1\endcsname
 1643     \cxa\cna\cxa\csname#2\endcsname}%
 1644   \gmu@nl@reserveda}
```

The `\global` prefix doesn’t work with `\n@melet` so we define the alternative.

```
\gn@melet 1648 \def\gn@melet#1#2{%
 1649   \edef\gmu@nl@reserveda{%
 1650     \global\let\cxa\cna\cxa\csname#1\endcsname
 1651     \cxa\cna\cxa\csname#2\endcsname}%
 1652   \gmu@nl@reserveda}
```

Not only preamble!

Let’s remove some commands from the list to erase at begin document! Primarily that list was intended to save memory not to forbid anything. Nowadays, when memory is cheap, the list of only-preamble commands should be rethought IMO.

```
\not@onlypreamble 1669 \newcommand\not@onlypreamble[1]{{%
 1670   \def\do##1{\ifx##1##1\else\cna\do\cna##1\fi}%
 1671   \xdef\@preamblecmds{\@preamblecmds}}}
 1673 \not@onlypreamble\@preamblecmds
 1674 \not@onlypreamble\@ifpackageloaded
 1675 \not@onlypreamble\@ifclassloaded
 1676 \not@onlypreamble\@ifl@aded
 1677 \not@onlypreamble\@pkgextension
```

And let’s make the message of only preamble command’s forbidden use informative a bit:

```
\gm@notprerr 1682 \def\gm@notprerr{\canbeusedonlyinpreamble(\online)}
 1684 \AtBeginDocument{%
 1685   \def\do##1{\cna\do\cna##1}%
 1686   \edef\@preamblecmds{%
 1687     \def\cna\do##1{%
```

```

1688     \def##1{\@nx\PackageError{gmutils/LaTeX}%
1689       {\@nx\string##1\@nx\gm@notprerr}\@nx\@eha}}%
1690   \@preamblecmds}

```

A subtle error raises: the L^AT_EX standard \onlypreamble and what \document does with \preamblecmds makes any two of ‘only preamble’ cs’s \ifx-identical inside document. And my change makes any two cs’s \ifx-different. The first it causes a problem with is standard L^AT_EX’s \nocite that checks \ifx\onlypreamble\document. So hoping this is a rare problem, we circumvent in with. 2008/08/29 a bug is reported by Edd Barrett that with natbib an ‘extra }’ error occurs so we wrap the fix in a conditional.

```

\gmu@nocite@ampulex 1707 \def\gmu@nocite@ampulex{\% we wrap the stuff in a macro to hide an open \if.
                           And not to make the begin-input hook not too large. the first is the parameters
                           string and the second the argument for one-level expansion of \nocite so it
                           has to consist of two times less hashes than the first. Both hash strings are
                           doubled to pass the first \def.
1714 \ampulexdef []\nocite[####1] [{####1}]% note the double brace around
                           % #3.
1716 \ifx
1717 {\onlypreamble\document}%
1718 \iftrue
1720 \AtBeginDocument\gmu@nocite@ampulex

```

Third person pronouns

Is a reader of my documentations ‘she’ or ‘he’ and does it make a difference?

Not to favour any gender in the personal pronouns, define commands that’ll print alternately masculine and feminine pronoun of third person. By ‘any’ I mean not only typically masculine and typically feminine but the entire amazingly rich variety of people’s genders, *including* those who do not describe themselves as ‘man’ or ‘woman’.

One may say two pronouns is far too little to cover this variety but I could point Ursula’s K. LeGuin’s *The Left Hand Of Darkness* as another acceptable answer. In that moody and moderate SF novel the androgynous persons are usually referred to as ‘mister’, ‘sir’ or ‘he’: the meaning of reference is extended. Such an extension also my automatic pronouns do suggest. It’s *not* political correctness, it’s just respect to people’s diversity.

```

\gm@PronounGender 1747 \newcounter{gm@PronounGender}
\gm@atppron 1749 \newcommand*\gm@atppron[2]{%
1750   \stepcounter{gm@PronounGender}% remember \stepcounter is global.
1751   \ifodd\value{gm@PronounGender}\#1\else\#2\fi}
\heshe 1753 \newcommand*\heshe{\gm@atppron{he}{she}}
\hisher 1754 \newcommand*\hisher{\gm@atppron{his}{her}}
\himher 1755 \newcommand*\himher{\gm@atppron{him}{her}}
\hishers 1756 \newcommand*\hishers{\gm@atppron{his}{hers}}
\HeShe 1758 \newcommand*\HeShe{\gm@atppron{He}{She}}
\HisHer 1759 \newcommand*\HisHer{\gm@atppron{His}{Her}}
\HimHer 1760 \newcommand*\HimHer{\gm@atppron{Him}{Her}}
\HisHers 1761 \newcommand*\HisHers{\gm@atppron{His}{Hers}}

```

Improvements to mwcls sectioning commands

That is, ‘Experi-mente’² mit MW sectioning & \refstepcounter to improve mwcls’s cooperation with hyperref. They shouldn’t make any harm if another class (non-mwcls) is loaded.

We \refstep sectioning counters even if the sectionings are not numbered, because otherwise

1. pdfTeX cried of multiply defined \labels,
2. e.g. in a table of contents the hyperlink <rozdzia\l\Kwiaty_polskie> linked not to the chapter’s heading but to the last-before-it change of \ref.

¹⁷⁸⁰ \AtBeginDocument{ % because we don’t know when exactly hyperref is loaded and maybe after this package.

```
NoNumSecs 1782  \@ifpackageloaded{hyperref}{\newcounter{NoNumSecs}%
1783    \setcounter{NoNumSecs}{617}%
1784    }% to make \refing to an unnumbered section
1785    visible (and funny?).
1786    \def\gm@hyperrefstepcounter{\refstepcounter{NoNumSecs}%
1787    \pdef\gm@targetheading#1{%
1788      \hypertarget{#1}{#1}}% end of then
1789    {\def\gm@hyperrefstepcounter{}%
1790      \def\gm@targetheading#1{#1}}% end of else
1791  }% of \AtBeginDocument
```

Auxiliary macros for the kernel sectioning macro:

```
1793 \def\gm@dontnumbersectionsoutofmainmatter{%
1794   \if@mainmatter\else\HeadingNumberedfalse\fi}
1795 \def\gm@clearpagesduetoopenright{%
1796   \if@openright\cleardoublepage\else\clearpage\fi}
```

To avoid \defing of \mw@sectionxx if it’s undefined, we redefine \def to gobble the definition and restore the original meaning of itself.

Why shouldn’t we change the ontological status of \mw@sectionxx (not define if undefined)? Because some macros (in gmdoc e.g.) check it to learn whether they are in an mwcls or not.

But let’s make a shorthand for this test since we’ll use it three times in this package and maybe also somewhere else.

```
@ifnotmw 1809 \long\def@ifnotmw#1#2{\gm@ifundefined{mw@sectionxx}{#1}{#2}}
```

The kernel of MW’s sectioning commands:

```
1834 \@ifnotmw{}{%
1835 \def\mw@sectionxx#1#2[#3]{%
1836   \edef\mw@HeadingLevel{\csname #1@level\endcsname
1837     \space}% space delimits level number!
1838   \ifHeadingNumbered
1839     \ifnum\mw@HeadingLevel>\c@secnumdepth%
1840       \HeadingNumberedfalse\fi
line below is in \gm@ifundefined to make it work in classes other than mwbk
1842   \gm@ifundefined{if@mainmatter}{}{%
1843     \gm@dontnumbersectionsoutofmainmatter}
1843   \fi
%   \ifHeadingNumbered
%   \refstepcounter{#1}%
```

² A. Berg, Wozzeck.

```

%      \protected@edef\HeadingNumber{\csname
%        the#1\endcsname\relax}%
% \else
%   \let\HeadingNumber\empty
% \fi

\HeadingRHeadText 1852 \def\HeadingRHeadText{\#2}%
\HeadingTOCText 1853 \def\HeadingTOCText{\#3}%
\HeadingText 1854 \def\HeadingText{\#4}%
\mw@HeadingType 1855 \def\mw@HeadingType{\#1}%
1856 \if\mw@HeadingBreakBefore
1857   \if@specialpage\else\thispagestyle{closing}\fi
1858   \gm@ifundefined{if@openright}{}{%
1859     \gm@clearpagesduetoopenright}%
1860   \if\mw@HeadingBreakAfter
1861     \thispagestyle{blank}\else
1862     \thispagestyle{opening}\fi
1863   \global\@topnum\z@
1864 \fi% of \if\mw@HeadingBreakBefore

placement of \refstep suggested by me (GM):
1866 \ifHeadingNumbered
1867   \refstepcounter{\#1}%
1868   \protected@edef\HeadingNumber{\csname the#1\endcsname\relax}%
1869 \else
1870   \let\HeadingNumber\empty
1871   \gm@hyperrefstepcounter
1872 \fi% of \ifHeadingNumbered
1873 \if\mw@HeadingRunIn
1874   \mw@runinheading
1875 \else
1876   \if\mw@HeadingWholeWidth
1877     \if@twocolumn
1878       \if\mw@HeadingBreakAfter
1879         \onecolumn
1880         \mw@normalheading
1881         \pagebreak\relax
1882           \if@twoside
1883             \null
1884             \thispagestyle{blank}%
1885             \newpage
1886           \fi% of \if@twoside
1887         \twocolumn
1888       \else
1889         \atopnewpage[\mw@normalheading]%
1890       \fi% of \if\mw@HeadingBreakAfter
1891     \else
1892       \mw@normalheading
1893       \if\mw@HeadingBreakAfter\pagebreak\relax\fi
1894     \fi% of \if@twocolumn
1895   \else
1896     \mw@normalheading
1897     \if\mw@HeadingBreakAfter\pagebreak\relax\fi
1898   \fi% of \if\mw@HeadingWholeWidth
1899 
```

```

1900   \fi% of \if\mw@HeadingRunIn
1901 }

```

An improvement of MW's \SetSectionFormatting

A version of MW's \SetSectionFormatting that lets to leave some settings unchanged by leaving the respective argument empty ({} or []).

Notice: If we adjust this command for new version of mwcls, we should name it \SetSectionFormatting and add issuing errors if the inner macros are undefined.

- [#1] the flags, e.g. breakbefore, breakafter;
- #2 the sectioning name, e.g. chapter, part;
- #3 preskip;
- #4 heading type;
- #5 postskeep

```

1925 \relax\n SetSectionFormatting
1926 \newcommand*\SetSectionFormatting[5][\empty]%
1927   \ifx\empty#1\relax\else% empty (not \empty!) #1 also launches \else.
1928     \def\mw@HeadingRunIn{\o}\def\mw@HeadingBreakBefore{\o}%
1929     \def\mw@HeadingBreakAfter{\o}\def\mw@HeadingWholeWidth{\o}%
1930     \@ifempty{#1}{}{\mw@processflags#1,\relax}% If #1 is omitted, the flags
1931       are left unchanged. If #1 is given, even as [], the flags are first cleared and
1932       then processed again.
1933   \fi
1934   \gm@ifundefined{#2}{\@namedef{#2}{\mw@section{#2}}}{}
1935   \mw@secdef{#2}{@preskip}{#3}{2\oblig.}%
1936   \mw@secdef{#2}{@head}{#4}{3\oblig.}%
1937   \mw@secdef{#2}{@postskip}{#5}{4\oblig.}%
1938   \ifx\empty#1\relax
1939     \mw@secundef{#2@flags}{1(optional)}%
1940   \else\mw@setflags{#2}%
1941   \fi
1942 
1943 \def\mw@secdef#1#2#3#4{%
1944   % #1 the heading name,
1945   % #2 the command distinctor,
1946   % #3 the meaning,
1947   % #4 the number of argument to error message.
1948   \@ifempty{#3}
1949     {\mw@secundef{#1#2}{#4}}
1950     {\@namedef{#1#2}{#3}}}
1951 
1952 \def\mw@secundef#1#2{%
1953   \gm@ifundefined{#1}{%
1954     \ClassError{mwcls/gm}{%
1955       command\bslash#1\undefined\MessageBreak
1956       after\bslash\SetSectionFormatting!!!\MessageBreak}{%
1957         Provide the #2 argument of \bslash
1958         SetSectionFormatting.}}{}}
1959

```

First argument is a sectioning command (wo. the backslash) and second the stuff to be added at the beginning of the heading declarations.

```

1964 \def\addtoheading#1#2{%
1965   \n@melet{\gmu@reserveda}{#1@head}%

```

```

1966 \edef\gmu@reserveda{\unexpanded{\#2}\@xa\unexpanded{%
1967   \gmu@reserveda}}%
1968 \n@melet{\#1@head}{\gmu@reserveda}%
1969 }
1970 }% of \@ifnotmw's else.

```

Negative \addvspace

When two sectioning commands appear one after another (we may assume that this occurs only when a lower section appears immediately after higher), we prefer to put the *smaller* vertical space not the larger, that is, the preskip of the lower sectioning not the postskip of the higher.

For that purpose we modify the very inner macros of `MWCLS` to introduce a check whether the previous vertical space equals the postskip of the section one level higher.
`1983 \@ifnotmw{}{}% We proceed only in MWCLS.`

The information that we are just after a heading will be stored in the `\gmu@prevsec` macro: any heading will define it as the section name and `\everypar` (any normal text) will clear it.

```

\@afterheading 1988 \def\@afterheading{%
1989   \@nobreaktrue
1990   \xdef\gmu@prevsec{\mw@HeadingType}% added now
1991   \everypar{%
1992     \grelax\gmu@prevsec% added now. All the rest is original LATEX.
1993     \if@nobreak
1994     \else
1995       \clubpenalty\@M
1996       \if@afterindent\else
1997         {\setbox\z@\lastbox}%
1998       \fi
1999       \else
2000         \clubpenalty\@clubpenalty
2001         \everypar{}%
2002       \fi}%
}

```

If we are (with the current heading) just after another heading (one level lower I suppose), then we add the less of the higher header's post-skip and the lower header preskip or, if defined, the two-header-skip. (We put the macro defined below just before `\addvspace` in `MWCLS` inner macros.)

```

\gmu@checkaftersec 2009 \def\gmu@checkaftersec{%
2010   \gm@ifundefined{\gmu@prevsec}{}{%
2011     \ifgmu@postsec% an additional switch that is true by default but may be
2012       turned into an \ifdim in special cases, see line 2047.
2013       {\@xa\mw@getflags\@xa{\gmu@prevsec}%
2014         \glet\gmu@reserveda\mw@HeadingBreakAfter}%
2015       \if\mw@HeadingBreakBefore\def\gmu@reserveda{\fi}% if the current
2016         heading inserts page break before itself, all the play with vskips is irrele-
2017         vant.
2018       \if\gmu@reserveda\else
2019         \penalty1000\relax
2020         \skip\z@=\csname\gmu@prevsec\@postskip\endcsname\relax
2021         \skip\tw@=\csname\mw@HeadingType\@preskip\endcsname\relax
2022         \gm@ifundefined{\mw@HeadingType\@twoheadskip}{%
}
}

```

```

2024 \ifdim\skip\z@>\skip\tw@
2025   \vskip-\skip\z@% we strip off the post-skip of previous header if it's bigger
      than current pre-skip
2027 \else
2028   \vskip-\skip\tw@% we strip off the current pre-skip otherwise
2029   \fi}{% But if the two-header-skip is defined, we put it
2031   \penalty10000
2032   \vskip-\skip\z@
2033   \penalty10000
2034   \vskip-\skip\tw@
2035   \penalty10000
2036   \vskip\csname\mw@HeadingType\endcsname\twoheadskip\endcsname
2037   \relax}%
2038 \penalty10000
2039 \hrule\height\z@\relax% to hide the last (un)skip before
      subsequent \addvspaces.
2041 \penalty10000
2042 \fi
2043 \fi
2044 }% of \gm@ifundefined{\gmu@prevsec} 'else'.
2045 }% of \def\gmu@checkaftersec.

\ParanoidPostsec 2047 \def\ParanoidPostsec{%
  this version of \ifgmu@postsec is intended for the spe-
  cial case of sections may contain no normal text, as while gmdocing.
\ifgmu@postsec 2050 \def\ifgmu@postsec{%
  note this macro expands to an open \if.
  \skip\z@=\csname\gmu@prevsec\endcsname\relax
  \ifdim\lastskip=\skip\z@\relax% we play with the vskips only if the last
  skip is the previous heading's postskip (a counter-example I met while
  gmdocing).
2056   }%
2058 \let\ifgmu@postsec\iftrue
\gmu@getaddvs 2060 \def\gmu@getaddvs#1\addvspace#2\gmu@getaddvs{%
2061   \toks\z@={#1}%
2062   \toks\tw@={#2}}

```

And the modification of the inner macros at last:

```

\gmu@setheading 2065 \def\gmu@setheading#1{%
2066   \xa\gmu@getaddvs#1\gmu@getaddvs
2067   \edef#1{%
2068     \the\toks\z@\@nx\gmu@checkaftersec
2069     \@nx\addvspace\the\toks\tw@}}
2071 \gmu@setheading\mw@normalheading
2072 \gmu@setheading\mw@runinheading
\SetTwoheadSkip 2074 \def\SetTwoheadSkip#1#2{\@namedef{#1@twoheadskip}{#2}}
2076 }% of \@ifnotmw's else.

```

My heading setup for mwcls

The setup of heading skips was tested in ‘real’ typesetting, for money that is. The skips are designed for 11/13 pt leading and together with my version of mw11.clo option file for mwcls make the headings (except paragraph and subparagraph) consist of an integer number of lines. The name of the declaration comes from my employer, “Wiedza Powszechna” Editions.

```

2088 \@ifnotmw{}{%
2089   \def\WPheadings{%
2090     \SetSectionFormatting[breakbefore,wholewidth]
2091     {part}{\z@\@plus1fill}{}{\z@\@plus3fill}%
2092     \gm@ifundefined{chapter}{}{%
2093       \SetSectionFormatting[breakbefore,wholewidth]
2094       {chapter}
2095       {66\p@}{67\p@} for Adventor/Schola o,95.
2096       {\FormatHangHeading{\LARGE}}
2097       {27\p@\@plus0,2\p@\@minus1\p@}%
2098     }%
2099   }%
2100   \SetTwoheadSkip{section}{27\p@\@plus0,5\p@}%
2101   \SetSectionFormatting{section}
2102     {24\p@\@plus0,5\p@\@minus5\p@}%
2103     {\FormatHangHeading{\Large}}
2104     {10\p@\@plus0,5\p@}% ed. Krajewska of "Wiedza Powszechna", as we un-
2105       derstand her, wants the skip between a heading and text to be rigid.
2106   \SetTwoheadSkip{subsection}{11\p@\@plus0,5\p@\@minus1\p@}%
2107   \SetSectionFormatting{subsection}
2108     {19\p@\@plus0,4\p@\@minus6\p@}
2109     {\FormatHangHeading{\large}}% 12/14 pt
2110     {6\p@\@plus0,3\p@}% after-skip 6 pt due to p.12, not to squeeze the before-
2111       skip too much.
2112   \SetTwoheadSkip{subsubsection}{10\p@\@plus1,75\p@\@minus1\p@}%
2113   \SetSectionFormatting{subsubsection}
2114     {10\p@\@plus0,2\p@\@minus1\p@}
2115     {\FormatHangHeading{\normalsize}}
2116     {3\p@\@plus0,1\p@}% those little skips should be smaller than you calcu-
2117       late out of a geometric progression, because the interline skip enlarges
2118       them.
2119   \SetSectionFormatting[runin]{paragraph}
2120     {7\p@\@plus0,15\p@\@minus1\p@}
2121     {\FormatRunInHeading{\normalsize}}
2122     {2\p@}%
2123   \SetSectionFormatting[runin]{ subparagraph}
2124     {4\p@\@plus1\p@\@minus0,5\p@}
2125     {\FormatRunInHeading{\normalsize}}
2126     {\z@}%
2127 }% of \WPheadings
2128 }% of \ifnotmw

```

Compatibilising standard and mwcls sectionings

If you use Marcin Woliński's document classes (mwcls), you might have met their little queerness: the sectioning commands take two optional arguments instead of standard one. It's reasonable since one may wish one text to be put into the running head, another to the toc and yet else to the page. But the order of optionalities causes an incompatibility with the standard classes: MW section's first optional argument goes to the running head not to toc and if you've got a source file written with the standard classes in mind and use the first (and only) optional argument, the effect with mwcls would be different if not error.

Therefore I counter-assign the commands and arguments to reverse the order of optional arguments for sectioning commands when mwcls are in use and reverse, to make mwcls-like sectioning optionals usable in the standard classes.

With the following in force, you may both in the standard classes and in mwcls give a sectioning command one or two optional arguments (and mandatory the last, of course). If you give just one optional, it goes to the running head and to toc as in scls (which is unlike in mwcls). If you give two optionals, the first goes to the running head and the other to toc (like in mwcls and unlike in scls).

(In both cases the mandatory last argument goes only to the page.)

What more is unlike in scls, it's that even with them the starred versions of sectioning commands allow optionals (but they still send them to the Gobbled Tokens' Paradise).

(In mwcls, the only difference between starred and non-starred sec commands is (not) numbering the titles, both versions make a contents line and a mark and that's not changed with my redefinitions.)

2175 \@ifnotmw{ we are not in mwcls and want to handle mwcls-like sectionings i.e.,
those written with two optionals.

```
\gm@secini 2178 \def\gm@secini{\gm@la}%
\gm@secxx 2180 \def\gm@secxx[#1#2[#3]#4{%
2181   \ifx\gm@secstar\empty
2182     \n@melet{\gm@true@#1mark}{#1mark}%
2183       a little trick to allow a special ver-
2184       sion of the heading just to the running head.
2185     \cnamedef{#1mark}##1{%
2186       we redefine \secmark to gobble its argument
2187       and to launch the stored true marking command on the appropriate
2188       argument.
2189     \csname\gm@true@#1mark\endcsname{#2}%
2190     \n@melet{#1mark}{\gm@true@#1mark}%
2191       after we've done what we
2192       wanted we restore original \#1mark.
2193   }%
```

\gm@secstar 2194 \def\gm@secstar{[#3]}% if \gm@secstar is empty, which means the sectioning command was written starless, we pass the 'true' sectioning command #3 as the optional argument. Otherwise the sectioning command was written with star so the 'true' s.c. takes no optional.

```
2195   \fi
2196   \o@xa\@xa\csname\gm@secini#1\endcsname
2197   \gm@secstar{#4}%
2198 }
```

2200 }{ we are in mwcls and want to reverse MW's optionals order i.e., if there's just one optional, it should go both to toc and to running head.

```
\gm@secini 2203 \def\gm@secini{\gm@mw}%
2205 \let\gm@secmarkh\@gobble% in mwcls there's no need to make tricks for special
2206   version to running headings.
```

```
\gm@secxx 2208 \def\gm@secxx[#1#2[#3]#4{%
2209   \o@xa\@xa\csname\gm@secini#1\endcsname
2210   \gm@secstar[#2][#3]{#4}%
2211 }
```

\gm@sec 2213 \def\gm@sec#1{\@dblarg{\gm@secx{#1}}}
\gm@secx 2214 \def\gm@secx#1[#2]{%
2215 \o@ifnextchar[\{\gm@secxx{#1}{#2}\}{\gm@secxx{#1}{#2}[#2]}%
2216 if there's
2217 only one optional, we double it not the mandatory argument.

```
\gm@straightensec 2219 \def\gm@straightensec#1{%
2220   the parameter is for the command's name.
2221   \gm@ifundefined{#1}{}%
2222     we don't change the ontological status of the com-
2223     mand because someone may test it.
```

```

2222 \n@melet{\gm@secini#1}{#1}%
2223 \cnamedef{#1}{%
2224   \@ifstar{\def\gm@secstar{*}\gm@sec{#1}}{%
2225     \def\gm@secstar{}\gm@sec{#1}}}}%
2226 }%
2228 \let\do\gm@straightensec
2229 \do{part}\do{chapter}\do{section}\do{subsection}\do{%
2230   subsubsection}%
2230 \cifnotmw{}{\do{paragraph}}% this ‘straightening’ of \paragraph with the stan-
dard article caused the ‘ $\text{T}_{\text{E}}\text{X}$  capacity exceeded’ error. Anyway, who on Earth
wants paragraph titles in toc or running head?

```

enumerate* and itemize*

We wish the starred version of `enumerate` to be just numbered paragraphs. But `hyperref` redefines `\item` so we should do it a smart way, to set the $\text{L}\text{A}\text{T}_{\text{E}}\text{X}$'s list parameters that is.

(Marcin Woliński in `mwcls` defines those environments slightly different: his item labels are indented, mine are not; his subsequent paragraphs of an item are not indented, mine are.)

```

enumerate* 2246 \cnamedef{enumerate*}{%
2247   \ifnum\@enumdepth>\thr@@
2248     \atodeep
2249   \else
2250     \advance\@enumdepth\@ne
2251     \edef\@enumctr{enum\romannumeral\the\@enumdepth}%
2252     \xa\list\csname_label\@enumctr\endcsname{%
2253       \partopsep\topsep\topsep\z@\leftmargin\z@
2254       \itemindent\parindent\% \advance\itemindent\labelsep
2255       \labelwidth\parindent
2256       \advance\labelwidth-\labelsep
2257       \listparindent\parindent
2258       \usecounter\@enumctr
2259       \def\makelabel##1{\hfil}%
2260     \fi}
2261   \cnamedef{endenumerate*}{\endlist}

itemize* 2264 \cnamedef{itemize*}{%
2265   \ifnum\@itemdepth>\thr@@
2266     \atodeep
2267   \else
2268     \advance\@itemdepth\@ne
2269     \edef\@itemitem{labelitem\romannumeral\the\@itemdepth}%
2270     \xa\list\csname\@itemitem\endcsname{%
2271       \partopsep\topsep\topsep\z@\leftmargin\z@
2272       \itemindent\parindent
2273       \labelwidth\parindent
2274       \advance\labelwidth-\labelsep
2275       \listparindent\parindent
2276       \def\makelabel##1{\hfil}%
2277     \fi}
2278   \cnamedef{enditemize*}{\endlist}

```

The logos

We'll modify The L^AT_EX logo now to make it fit better to various fonts.

```

2287 \let\oldLaTeX\LaTeX
2288 \let\oldTeXe\TeXe
2290 \def\TeX{T\kern-.1667em\lower.5ex\hbox{E}\kern-.125emX\@}
\DeclareLogo 2292 \newcommand*\DeclareLogo[3]{%
    % [#1] is for non-LATEX spelling and will be used in the PD1 encoding (to make
    % pdf bookmarks);
    % #2 is the command, its name will be the PD1 spelling by default,
    % #3 is the definition for all the font encodings except PD1.
\gmu@reserveda 2300 \ifx\relax#1\def\gmu@reserveda{\@xa\@gobble\string#2}%
2301 \else
\gmu@reserveda 2302 \def\gmu@reserveda{#1}%
2303 \fi
2304 \edef\gmu@reserveda{%
2305     \@nx\DeclareTextCommand{\nx#2{PD1}}{\gmu@reserveda}%
2306 \gmu@reserveda
2307 \DeclareTextCommandDefault{#2}{#3}%
\pdef 2308 \pdef#2{#3}%
    \pdef#2{#3}%
    added for XHTEX
\DeclareLogo 2311 \DeclareLogo\LaTeX{%
    {%
        L%
        \setbox\z@\hbox{\check@mathfonts
            \fontsize@size\z@
            \math@fontsfalse\selectfont
        A}%
        \kern-.57\wd\z@
        \sbox\tw@\T%
        \vbox\to\ht\tw@{\copy\z@\vss}%
        \kern-.2\wd\z@%
        originally -,15 em for T.
    {%
        \ifdim\fontdimen1\font=\z@
        \else
            \count\z@=\fontdimen5\font
            \multiply\count\z@ by 64\relax
            \divide\count\z@ by \p@
            \count\tw@=\fontdimen1\font
            \multiply\count\tw@ by \count\z@
            \divide\count\tw@ by 64\relax
            \divide\count\tw@ by \tw@
            \kern-\the\count\tw@ sp\relax
        \fi}%
    \TeX}
\TeXe 2337 \DeclareLogo\TeXe{\mbox{\m@th\if
2338 b\expandafter\@car\f@series\@nil\boldmath\fi
2339 \LaTeX\kern.15em2$_{\{\textstyle\varepsilon\}}$}}
2341 \StoreMacro\TeX
2342 \StoreMacro*\{\TeX\}

```

'(L^A)T_EX' in my opinion better describes what I work with/in than just 'L^AT_EX'.

```

\LaTeXpar 2348 \DeclareLogo[(La)TeX]{\LaTeXpar}{%
2349   {%
2350     \setbox\z@\hbox{()%
2351     \copy\z@%
2352     \kern-.2\wd\z@\L%
2353     \setbox\z@\hbox{\check@mathfonts%
2354       \fontsize\sf@size\z@%
2355       \math@fontsfalse\selectfont%
2356       A}%
2357     \kern-.57\wd\z@%
2358     \sbox\tw@\T%
2359     \vbox\to\ht\tw@{\box\z@%
2360     \vss}%
2361   }%
2362   \kern-.07em% originally -, 15 em for T.
2363   {%
2364     \sbox\z@%
2365     \kern-.2\wd\z@\copy\z@%
2366     \kern-.2\wd\z@\TeX%
2367 }

```

“Here are a few definitions which can usefully be employed when documenting package files: now we can readily refer to *$\mathcal{A}\mathcal{M}\mathcal{S}$ - TeX* , *$\text{B}\mathcal{I}\mathcal{B}$ - TeX* and *$\text{S}\mathcal{L}\mathcal{T}$ - TeX* , as well as the usual TeX and $\text{L}\mathcal{A}\text{T}$ - TeX . There’s even a *PLAIN* TeX and a *WEB*.”

```

\AmSTeX 2374 \gm@ifundefined{AmSTeX}
2375   {\def\AmSTeX{\leavevmode\hbox{$\mathcal{A}\kern-.2em$%
2376     \lower.376ex%
2377     \hbox{$\mathcal{M}$}\kern-.2em$\mathcal{S}$-\TeX}}{}}
\BibTeX 2378 \DeclareLogo\BibTeX{{\rmfamily\B\kern-.05em%
2379   \textsc{i}\{\kern-.025em\B\kern-.08em\% the kern is wrapped in braces%
2380   for my \fakesc's sake.%
2381   \TeX}}
\SlTeX 2384 \DeclareLogo\SlTeX{{\rmfamily\kern-.06em\kern-.18em\%
2385   \raise.32ex\hbox%
2386   {\scshape i}\kern-.03em\TeX}}
\PlainTeX 2387 \DeclareLogo\PlainTeX{\textsc{Plain}\kern2pt\TeX}
\Web 2389 \DeclareLogo\Web{\textsc{Web}}

```

There’s also the (L)TeX logo got with the \LaTeXpar macro provided by gutils. And here *The TeXbook ’s logo*:

```

\TeXbook 2392 \DeclareLogo[\TeXbook]\TeXbook{\textsl{\TeXbook}}
2393 \let\TB\TeXbook% TUG Boat uses this.
\eTeX 2395 \DeclareLogo[e-TeX]\eTeX{%
2396   \ensuremath{\varepsilon}-\kern-.125em\TeX}% definition sent by Karl Berry
   from TUG Boat itself.
\pdfTeX 2399 \DeclareLogo[pdf-TeX]\pdfTeX{pdf\TeX}
\pdfTeX 2401 \DeclareLogo\pdfTeX{pdf\TeX}
\pdfTeX 2403 \gm@ifundefined{XeTeX}{%
2404   \DeclareLogo\XeTeX{X\kern-.125em\relax%
2405   \gm@ifundefined{reflectbox}{%
```

```

2406      \lower.5ex\hbox{E}\kern-.1667em\relax}%
2407      \lower.5ex\hbox{\reflectbox{E}}\kern-.1667em\relax}%
2408  \TeX\}}{}}
2410 \gm@ifundefined{XeLaTeX}{%
\XeLaTeX  \DeclareLogo{XeLaTeX}{X}\kern-.125em\relax
2412   \gm@ifundefined{reflectbox}{%
2413     \lower.5ex\hbox{E}\kern-.1667em\relax}%
2414     \lower.5ex\hbox{\reflectbox{E}}\kern-.1667em\relax}%
2415   \LaTeX\}}

```

As you see, if \TeX doesn't recognize `\reflectbox` (graphics isn't loaded), the first E will not be reversed. This version of the command is intended for non- \TeX usage. With \TeX , you can load the `xltextra` package (e.g. with the `gmutils \XeTeXthree` declaration) and then the reversed E you get as the Unicode Latin Letter Reversed E.

Expandable turning stuff all into ‘other’

While typesetting a unicode file contents with `inputenc` package I got a trouble with some Unicode sequences that expanded to unexpandable cses: they could'nt be used within `\csname ... \endcsname`. My \TeX Guru advised to use `\meanig` to make all the name ‘other’. So—here we are.

Don't use them in `\edefs`, they would expand not quite.

The next macro is intended to be put in `\edefs` with a macro argument. The meaning of the macro will be made all ‘other’ and the words ‘(long) macro:->’ gobbled.

```
\all@other 2440 \long\def\all@other#1{\@xa\gm@gobmacro\meaning#1}
```

The `\gm@gobmacro` macro above is applied to gobble the `\meaning`'s beginnig, `long macro:->` all ‘other’ that is. Use of it:

```
\gm@gobmacro 2445 \edef\gmu@tempa{%
2446   \def\@nx\gm@gobmacro##1\@xa\@gobble\string\macro##2->{}}
2447 \gmu@tempa
```

Brave New World of \TeX

```
\@ifXeTeX 2464 \newcommand{\@ifXeTeX}[2]{%
2465   \ifdefinable{XeTeXversion}{%
2466     \unless\ifx\XeTeXversion\relax\afterfifi{#1}\else\afterfifi{%
2467       #2}\fi
2468     \else\afterfi{#2}\fi}
\XeTeXthree 2470 \def\XeTeXthree{%
2471   \@ifXeTeX{%
2472     \ifpackageloaded{gmverb}{\StoreMacro{\verb}{}}{%
2473       \RequirePackage{xltextra}}% since v 0.4 (2008/07/29) this package redefines \verb and verbatim*, and quite elegantly provides an option to suppress the redefinitions, but unfortunately that option excludes also a nice definition of \xxt@visiblespace which I fancy.
2474     \ifpackageloaded{gmverb}{\RestoreMacro{\verb}}{%
2475       \AtBeginDocument{%
2476         \RestoreMacro{\LaTeX}\RestoreMacro*{\LaTeX}}% my version of the
2477         \LaTeX logo has been stored just after defining, in line 2342.
2478       }{}}{}}{}}{}}
```

The `\udigits` declaration causes the digits to be typeset uppercase. I provide it since by default I prefer the lowercase (nautical) digits.

```

2491 \AtBeginDocument{%
2492   \@ifpackageloaded{fontspec}{%
2493     \pdef\udigits{%
2494       \addfontfeature{Numbers=Uppercase}}%
2495   }{%
2496     \empty\udigits}%

```

Fractions

```
\Xedeckfracc \def\Xedeckfracc{\@ifstar\gmu@xedekfraccstar\gmu@xedekfraccplain}
```

(plain) The starless version turns the font feature `frac` on.

(*) But nor my modification of Minion Pro neither TeX Gyre Pagella doesn't feature the `frac` font feature properly so, with the starred version of the declaration we use the characters from the font where available (see the `\@namedefs` below) and the `numr` and `dnom` features with the fractional slash otherwise (via `\gmu@dekfracc`).

(**) But Latin Modern Sans Serif Quotation doesn't support the numerator and denominator positions so we provide the double star version for it, which takes the char from font if it exist and typesets with lowers and kerns otherwise.

```

\gmu@xedekfraccstar \def\gmu@xedekfraccstar{%
\gmu@xefraccdef \def\gmu@xefraccdef##1##2{%
  \iffontchar\font\#2{%
    \gmu@xefraccdef\#1{\char\#2}%
  }{%
    \else
      \n@melet\gmu@xefracc\#1{relax}%
    \fi}%
  \def\gmu@dekfracc##1##2{%
    \addfontfeature{VerticalPosition=Numerator}\#1\%
    \gmu@numeratorkern
    \char"2044\gmu@denominatorkern
    \addfontfeature{VerticalPosition=Denominator}\#2}%
}

```

We define the fractional macros. Since Adobe Minion Pro doesn't contain $\frac{n}{5}$ nor $\frac{n}{6}$, we don't provide them here.

```

\gmu@xefraccdef{1/4}{\"BC}%
\gmu@xefraccdef{1/2}{\"BD}%
\gmu@xefraccdef{3/4}{\"BE}%
\gmu@xefraccdef{1/3}{\"2153}%
\gmu@xefraccdef{2/3}{\"2154}%
\gmu@xefraccdef{1/8}{\"215B}%
\gmu@xefraccdef{3/8}{\"215C}%
\gmu@xefraccdef{5/8}{\"215D}%
\gmu@xefraccdef{7/8}{\"215E}%
\pdef\dekfracc@args##1##2{%
  \def\gm@duppa##1##2{%
    \gm@ifundefined{\gmu@xefracc\all@other\gm@duppa}{%
      \gmu@dekfracc\#1/\#2}%
    \csname\gmu@xefracc\all@other\gm@duppa\endcsname%
    \if@gmu@mmbbox\egroup\fi
  }% of \dekfracc@args.
  \@ifstar{\let\gmu@dekfracc\gmu@dekfraccsimple}{}%
}

```

```

2548      }
2550 \def\gmu@xedekfraccplain{\% 'else' of the main \@ifstar
2551   \pdef\dekfracc@args##1##2{%
2552     \ifmmode\hbox\fi{%
2553       \addfontfeature{Fractions=On}%
2554       ##1##2}%
2555     \if@gmu@mmhbox\egroup\fi
2556   }% of \dekfracc@args
2557 }

\if@gmu@mmhbox 2559 \newif\if@gmu@mmhbox% we'll use this switch for \dekfracc and also for \thous
               (hacky thousand separator).

\dekfracc 2562 \pdef\dekfracc{%
2564   \ifmmode\hbox\bgroup@gmu@mmhboxtrue\fi
2565   \dekfracc@args}
\gmu@numeratorkern 2568 \def\gmu@numeratorkern{\kern-.05em\relax}
2569 \let\gmu@denominatorkern\gmu@numeratorkern

```

What have we just done? We defined two versions of the `\Xefractions` declaration. The starred version is intended to make use only of the built-in fractions such as $\frac{1}{2}$ or $\frac{7}{8}$. To achieve that, a handful of macros is defined that expand to the Unicodes of built-in fractions and `\dekfracc` command is defined to use them.

The unstarred version makes use of the Fraction font feature and therefore is much simpler.

Note that in the first argument of `\@ifstar` we wrote 8 (eight) `#`s to get the correct definition and in the second argument 'only' 4. (The L^AT_EX 2_E Source claims that that is changed in the 'new implementation' of `\@ifstar` so maybe it's subject to change.)

A simpler version of `\dekfracc` is provided in line [3128](#).

```

\resizegraphics
\resizegraphics 2591 \def\resizegraphics#1#2#3{%
2594   \resizebox{#1}{#2}{%
2595     \includegraphics{#3}}}

\GMtextsuperscript 2597 \def\GMtextsuperscript{%
2598   \@ifXeTeX{%
\textsuperscript 2599     \def\textsuperscript##1{%
2600       \addfontfeature{VerticalPosition=Numerator}##1}%
2601     }{\truetextsuperscript}}
\truetextsuperscript 2603 \def\truetextsuperscript{%
\textsuperscript 2604   \pdef\textsuperscript##1{%
2605     \@textsuperscript{\selectfont##1}}%
\@textsuperscript 2606   \def\@textsuperscript##1{%
2607     {\m@th\ensuremath{\hat{\mbox{\scriptsize\sf\size{z@##1}}}}}}}

```

Settings for mathematics in main font

`\gmath` I used these terrible macros while typesetting E. Szarzyński's *Letters* in 2008. The `\gmath` declaration introduces math-active digits and binary operators and redefines greek letters and parentheses, the `\garamath` declaration redefines the quantifiers and is more Garamond Premier Pro-specific.

```

\gmath 2620 \pdef\gmath{%

```

```

2621 \everymath{%
2622   \relaxen\do
2623   \newcommand*\do[4][\mathit]{\def##2##3##1{\char"##4}}}}%
2624   \do\alpha{}{o3B1}%
2625   \do[\mathrm]{\Delta}{o394}%
2626   \do\varepsilon{}{o3B5}%
2627   \do\vartheta{}{o3D1}%
2628   \do\nu{}{o3BD}%
2629   \do\pi{}{o3Co}%
2630   \do\phi{}{o3D5}%
2631   \do[\mathrm]\Phi{}{o424}%
2632   \do\sigma{}{o3C3}%
2633   \do\varsigma{}{o3DA}%
2634   \do\psi{}{o3C8}%
2635   \do\omega{}{o3C9}%
2636   \do\infty{}{221E}%
2637   \do[\mathrm]\neg{\mathbin}{ooAC}%
2638   \do[\mathrm]\neq{\mathrel}{2260}%
2639   \do\partial{}{2202}%
2640   \do[\mathrm]\pm{\mathbin}{ooB1}%
2641   \do[\mathrm]\pm{\mathbin}{ooB1}%
2642   \do[\mathrm]\sim{\mathrel}{oo7E}%
2643   \def\do##1##2##3{\def##1{%
2644     \mathop{\mathchoice{\hbox{%
2645       \rm
2646       \edef\gma@tempa{\the\fontdimen8\font}%
2647       \larger[3]%
2648       \lower\dimexpr(\fontdimen8\font-\gma@tempa)/2\hbox{##2}}}\hbox{%
2649       \rm
2650       \edef\gma@tempa{\the\fontdimen8\font}%
2651       \larger[2]%
2652       \lower\dimexpr(\fontdimen8\font-\gma@tempa)/2\hbox{##2}}}}%
2653       {\mathrm{##2}}{\mathrm{##2}}}\hbox{##3}}%
2654   \do\sum{\char"2211}{}%
2655   \do\forall{\gma@quantifierhook\rotatebox[origin=c]{180}{A}}%
2656     \setboxo=\hbox{A}\setboxz=\hbox{\scriptsize x}%
2657     \kern\dimexpr\htz/3*2-\wdz/2\relax\{\nolimits}%
2658   \do\exists{\rotatebox[origin=c]{180}{\gma@quantifierhook E}}%
2659     \nolimits%
2660   \def\do##1##2##3{\def##1{##3}%
2661     \mathchoice{\hbox{\rm##2}}{\hbox{\rm##2}}{\hbox{\rm\tiny##2}}}}%
2662     {\mathrm{##2}}{\mathrm{##2}}}\hbox{##3}}%
2663   \do\vee{\rotatebox[origin=c]{90}{<}}\mathbin
2664   \do\wedge{\rotatebox[origin=c]{-90}{<}}\mathbin
2665   \do\leftarrow{\char"2190}\mathrel
2666   \do\rightarrow{\char"2192}\mathrel
2667   \do\leftrightarrow{\char"2190\kern-0.1em\char"2192}\mathrel
2668   \gmu@storespecials[\do`^{\do`\do`=}]%
2669   \gmu@septify[\do`_12\do`_12\do`=_12]%
2670   \def\do##1##2##3{%
2671     \catcode`##1=12\relax}% to ensure ##2 be 'other' in the definition body.

```

```

2678 \scantokens{\mathcode`##1="8000\relax
2679   \foone{\catcode`##1=\active}{\def##1}{##3{%
2680     \mathchoice{\hbox{\rm##2}}{\hbox{\rm##2}}{%
2681       {\hbox{\rm\scriptsize##2}}{\hbox{\rm\tiny##2}}}}}}%
2682   \ignorespaces}}% to eat the lineend (scantokens acts as \read including
2683   line end).
2684 \do..\mathpunct\do,,\mathpunct\do....\mathpunct
2685 \do((\mathopen%
2686 \gm@ifundefined{resetMathstrut@}{}{%
2687   an error occured 'bad mathchar
2688   etc.' because amsmath.sty doesn't take account of a possibility of '(' being
2689   math-active.
2690 \def\resetMathstrut@{%
2691   \setbox\z@\hbox{%
2692     \mathchardef\@tempa\mathcode`\\(\relax
2693     \def\@tempb##1"##2##3{\the\textfont"##3\char"}%
2694     \expandafter\@tempb\meaning\@tempa\relax
2695     (%
2696     }%
2697     \ht\Mathstrutbox@\ht\z@\dp\Mathstrutbox@\dp\z@
2698   }%
2699   \do))\mathclose
2700   \do[\mathopen\do]\mathclose
2701   \do-\{\char"2212}\mathbin\do+\mathbin\do==\mathrel\%
2702   \do\times\mathbin
2703   \do:\mathbin\do\cdot\mathbin\do/\mathbin\do<<\mathrel
2704   \do>>\mathrel
2705   \dooo\mathord\do11\mathord\do22\mathord\do33\mathord
2706   \do44\mathord\do55\mathord\do66\mathord\do77\mathord
2707   \do88\mathord\do99\mathord
2708   \gmu@restorespecials
2709   \def\do##1##2##3{\def##1####1{##2{\hbox{%
2710     \rm
2711     \setboxo=\hbox{####1}%
2712     \edef\gma@tempa{\the\hto}%
2713     \edef\gma@tempb{\the\dpo}%
2714     ##3%
2715     \setboxo=\hbox{####1}%
2716     \lower\dimexpr(\hto+\dpo)/2-\dpo-((\gma@tempa+%
2717     \gma@tempb)/2-\gma@tempb)\hbox{%
2718     \do\bigl\mathopen\larger
2719     \do\bigr\mathclose\larger
2720     \do\Bigl\mathopen\largerr
2721     \do\Bigr\mathclose\largerr
2722     \do\biggl\mathopen\larger[3]%
2723     \do\biggr\mathclose\larger[3]%
2724     \do\Biggl\mathopen\larger[4]%
2725     \do\Biggr\mathclose\larger[4]%
2726     \def\do##1##2{\def##1{\ifmmode##2{\mathchoice{%
2727       {\hbox{\rm\char`##1}}{\hbox{\rm\char`##1}}{%
2728         {\hbox{\rm\scriptsize\char`##1}}{\hbox{\rm\tiny%
2729           \char`##1}}}}}}%
2730     \else\char`##1\fi}}%

```

```

2732 \do{\{\mathopen
2733 \do\}\mathclose
2735 \def\={\mathbin{=}}%
2736 \def\neqb{\mathbin{\neq}}%
2737 \def\do##1{\edef\gma@tempa{%
2738     \def\x@nx\csname\x@xa\gobble\string##1r\endcsname{%
2739         \x@nx\mathrel{\x@nx##1}}}}%
2740     \gma@tempa}%
2741 \do\vee\do\wedge\do\neg
2742 \def\fakern{\mkern-3mu}%
2743 \thickmuskip=8mu plus 4mu\relax
2745 \gma@gmathhook
2746 }% of \everymath.
2747 \everydisplay\everymath
2748 \ifdefined\Url
2749     \ampulexdef\Url{\let\do}{\makeother
2750     \everymath{}\let\do}{\makeother}% I don't know why but the url package's
2751     % \url typesets the argument inside a math which caused digits not to
2752     be typewriter but Roman and lowercase.
2753     \fi
2754 }% of \def\gmath.
2755 \emptyify\gma@quantifierhook
2756 \def\quantifierhook#1{%
2757     \def\gma@quantifierhook{#1}}
2758 \emptyify\gma@gmathhook
2759 \def\gmathhook#1{%
2760     \emptyify\gma@gmathhook
2761     \def\gmathhook#1{\addtomacro\gma@gmathhook{#1}}
2762 \gma@dollar
2763 \def\gma@dollar##1{{\gmath##1}}%
2764 \gma@bare
2765 \def\gma@bare#1{\gma@dollar##1}%
2766 \gma@checkbracket
2767 \def\gma@checkbracket{\ifnextchar[%
2768     \gma@bracket\gma@bare}
2769 \def\gma@bracket[#1]{{\gmath[#1]}}\ifnextchar\par{}{%
2770     \noindent}}
2771 \gma\def\gma{\ifnextchar$%
2772     \gma@dollar\gma@checkbracket}
2773 \garamath\def\garamath{%
2774     \addtotoks\everymath{%
2775         \quantifierhook{\addfontfeature{OpticalSize=800}}%
2776     \def\gma@arrowdash{%
2777         \setboxo=\hbox{\char"2192}\copyo\kern-0.6\wdo
2778         \bgcolor\rule[-\dpo]{0,6\wdo}{\dimexpr\hto+\dpo}%
2779         \kern-0.6\wdo}}%
2780     \def\gma@gmathhook{%
2781         \def\do####1####2####3{\def####1{####3}{%
2782             \mathchoice{\hbox{\rm####2}}{\hbox{\rm####2}}{\hbox{\rm####2}}{%
2783                 \hbox{\rm\scriptsize####2}}}}%
2784         \do\mapsto{\rule[0,4ex]{0,1ex}{0,4ex}\kern-0.05em}%
2785         \gma@arrowdash\kern-0.05em\char"2192\mathrel
2786         \do\cup{\scshape u}\mathbin
2787         \do\varnothing{\setboxo=\hbox{\gma@quantifierhook{%
2788             \addfontfeature{Scale=1.272727}0}}}}%
2789         \do\varnothing{\setboxo=\hbox{\gma@quantifierhook{%
2790             \addfontfeature{Scale=1.272727}0}}}}%
2791         \do\varnothing{\setboxo=\hbox{\gma@quantifierhook{%
2792             \addfontfeature{Scale=1.272727}0}}}}%

```

```

2793   \setbox2=\hbox{\char"2044}%
2794   \copyo\kern-0.5\wd0\kern-0.5\wd2\lower0.125\wd0\copy2
2795   \kerno.5\wd0\kern-0.5\wd2}{}}%
2796   \do\leftarrow{\char"2190\kern-0.05em\gma@arrowdash}\mathrel
2797   \do\rightarrow{\gma@arrowdash\kern-0.05em\char"2192}}%
2798   \mathrel
2799   \do\in{\gma@quantifierhook\char"0454}\mathbin
2800   }}}}%
2800 \everydisplay\everymath}

```

Minion and Garamond Premier kerning and ligature fixes

»Ws« shall not make long »s« because long »s« looks ugly next to »W«.

```

\gmu@tempa 2808 \def\gmu@tempa{\kern-0.08em\penalty10000\hskip0.5pt\relax
2809   s\penalty10000\hskip0.5pt\relax}
2811 \protected\edef\V{\gmu@tempa}
2813 \protected\edef\W{\gmu@tempa}
\Wz 2815 \pdef\Wz{W\kern-0.05em\penalty10000\hskip0.5pt\relax_z}

```

Varia

A very neat macro provided by doc. I copy it *verbatim*.

```

\gmu@tilde 2824 \def\gmu@tilde{%
2825   \leavevmode\lower.8ex\hbox{$\backslash$\widetilde{\mbox{}},$}}

```

Originally there was just `\`` instead of `\widetilde{\mbox{}}` but some commands of ours do redefine `\``.

```

/* 2829 \pdef\*{\gmu@tilde}
2835 \AtBeginDocument{%
  \def\widetilde{\let\widetilde\mbox\widetilde}
\texttilde 2837 \pdef\texttilde{%
2840   \@ifnextchar/{\gmu@tilde\kern-0.1667em\relax}{\gmu@tilde}}}

```

We prepare the proper kerning for “~/”.

The standard `\obeyspaces` declaration just changes the space's `\catcode` to 13 ('active'). Usually it is fairly enough because no one 'normal' redefines the active space. But we are *not* normal and we do *not* do usual things and therefore we want a declaration that not only will `\activeate` the space but also will (re)define it as the `\`` primitive. So define `\gmobeyspaces` that obeys this requirement.

(This definition is repeated in `gmverb`.)

```

\gmobeyspaces 2852 \foone{\catcode`\`=\active}%
2853 {\def\gmobeyspaces{\let\`=\catcode`\``\active}}

```

While typesetting poetry, I was surprised that sth. didn't work. The reason was that original `\obeylines` does `\let` not `\def`, so I give the latter possibility.

```

\defobeylines 2860 \foone{\catcode`\^^M=\active}%
2861 {\def\defobeylines{\catcode`\^^M=13\def^^M{\par}}}

```

Another thing I dislike in L^AT_EX yet is doing special things for `\dotskip`'s, 'cause I like the Knuthian simplicity. So I sort of restore Knuthian meanings:

```

\deksmallskip 2870 \def\deksmallskip{\vskip\smallskipamount}

```

```

\undecksmallskip 2871 \def\undecksmallskip{\vskip-\smallskipamount}
\dekmedskip     2872 \def\dekmedskip{\vskip\medskipamount}
\dekbigskip     2873 \def\dekbigskip{\vskip\bigskipamount}
\hfillneg      2876 \def\hfillneg{\hskip\opt\plus-\ifill\relax}

```

In some `\if(cat?)` test I needed to look only at the first token of a tokens' string (first letter of a word usually) and to drop the rest of it. So I define a macro that expands to the first token (or `{<text>}`) of its argument.

```

@firstofmany 2884 \long\def@firstofmany#1#2@@nil{#1}

```

A mark for the **TODO!**s:

```

\TODO 2888 \newcommand*\TODO[1][]{{%
 2889   \sffamily\bfseries\huge\textcolor{red}{TODO!}\if\relax#1\relax\else\space%
 2890   \fi#1}}

```

I like twocolumn tables of contents. First I tried to provide them by writing `\begin{multicols}{2}` and `\end{multicols}` outto the .toc file but it worked wrong in some cases. So I redefine the internal L^AT_EX macro instead.

```

\twocoltoc 2924 \newcommand*\twocoltoc{%
 2925   \RequirePackage{multicol}%
@starttoc 2926 \def@starttoc##1{%
 2927   \begin{multicols}{2}\makeatletter\@input{\jobname.\#\#1}%
 2928   \if@filesw\@xa\newwrite\csname\@name\@ext\endcsname
 2929   \immediate\openout\csname\@name\@ext\endcsname\jobname
 2930   .\#\#1\relax
 2931   \fi
 2932   \nobreakfalse\end{multicols}}}
 2933 \onlypreamble\twocoltoc

```

The macro given below is taken from the multicol package (where its name is `\enough@room`). I put it in this package since I needed it in two totally different works.

```

\enoughpage 2938 \newcommand*\enoughpage[1]{%
 2939   \par
 2940   \dimeno=\pagegoal
 2941   \advance\dimeno by-\pagetotal
 2942   \ifdim\dimeno<\#1\relax\newpage\fi}

```

An equality sign properly spaced:

```

>equals 2951 \pdef\equals{\hunskip${}={}$\ignorespaces}

```

And for the L^AT_EX's pseudo-code statements:

```

\eequals 2953 \pdef\eequals{\hunskip${}==${}\ignorespaces}
\cdot 2955 \pdef\cdot{\hunskip${}$\ignorespaces}

```

While typesetting a UTF-8 ls-R result I found a difficulty that follows: UTF-8 encoding is handled by the inputenc package. It's O.K. so far. The UTF-8 sequences are managed using active chars. That's O.K. so far. While writing such sequences to a file, the active chars expand. You feel the blues? When the result of expansion is read again, it sometimes is again an active char, but now it doesn't star a correct UTF-8 sequence.

Because of that I wanted to 'freeze' the active chars so that they would be `\written` to a file unexpanded. A very brutal operation is done: we look at all 256 chars' catcodes and if we find an active one, we `\let` it `\relax`. As the macro does lots and lots of assignments, it shouldn't be used in `\edefs`.

```

\freeze@actives 2975 \def\freeze@actives{%
2976   \count\z@\z@
2978   \@whilenum\count\z@<\@cclvi\do{%
2979     \ifnum\catcode\count\z@=\active
2980       \uccode`~\~= \count\z@
2981       \uppercase{\let~\relax}%
2982     \fi
2983   \advance\count\z@\@ne}

```

A macro that typesets all 256 chars of given font. It makes use of `\@whilenum`.

```

>ShowFont 2989 \newcommand*\ShowFont[1][6]{%
2990   \begin{multicols}{#1}[The current font (the \f@encoding \u
2991   encoding):]
2991   \parindent\z@
2992   \count\z@\m@ne
2993   \@whilenum\count\z@<\@cclv\do{%
2994     \advance\count\z@\@ne
2995     \u\the\count\z@:\~\char\count\z@\par}
2996 \end{multicols}}

```

A couple of macros for typesetting liturgical texts such as psalmody of Liturgia Horarum. I wrap them into a declaration since they'll be needed not every time.

```

\liturgiques 3004 \newcommand*\liturgiques[1][red]{% Requires the color package.
3005   \gmu@RPfor{color}\color%
\czerwo 3006 \newcommand*\czerwo{\small\color{#1}}% environment
\czer 3007 \newcommand{\czer}[1]{\leavevmode{\czerwo##1}}% we leave vmode because if we don't, then verse's \everypar would be executed in a group and thus its effect lost.
\* 3010 \def\*{\czer{$*\$}}
\+ 3011 \def\+{\czer{$\dag\$}}
\nieczer 3012 \newcommand*\nieczer[1]{\textcolor{black}{##1}}}

```

After the next definition you can write `\gmu@RP[⟨options⟩]{⟨package⟩}{⟨cs⟩}` to get the package #2 loaded with options #1 if the cs#3 is undefined.

```

\gmu@RPfor 3017 \newcommand*\gmu@RPfor[3][]{%
3018   \ifx\relax#1\relax
\gmu@resa 3019   \else\def\gmu@resa{[#1]}%
3020   \fi
3021   \o@xa\RequirePackage\gmu@resa{#2}}

```

Since inside document we cannot load a package, we'll redefine `\gmu@RPfor` to issue a request before the error issued by undefined cs.

```

\gmu@RPfor 3028 \AtBeginDocument{%
3029   \renewcommand*\gmu@RPfor[3][]{%
3030     \unless\ifdefined#3%
3031       \o@ifpackageloaded{#2}{}{%
3032         \typeout{^^J! \Package #2 not loaded!!! (\online) ^^J}%
3033       \fi}{}}

```

It's very strange to me but it seems that `c` is not defined in the basic math packages. It is missing at least in the *Symbols* book.

```

\continuum 3039 \pprovide\continuum{%
3040   \gmu@RPfor{eufrak}\mathfrak\ensuremath{\mathfrak{c}}}

```

And this macro I saw in the *ltugproc* document class nad I liked it.

```

\iteracro 3044 \def\iteracro{%
  \acro 3045   \pdef\acro##1{\gmu@acrospace##1\gmu@acrospace}%
  3046 }
  3048 \iteracro
\gmu@acrospace 3050 \def\gmu@acrospace#1#2\gmu@acrospace{%
  3051   \gmu@acroinner#1\gmu@acroinner
  3052   \ifx\relax#2\relax\else
  3053     \space
  3054     \afterfi{\gmu@acrospace#2\gmu@acrospace}% when #2 is nonempty, it
      is ended with a space. Adding one more space in this line resulted in an
      infinite loop, of course.
  3058   \fi}
\gmu@acroinner 3061 \def\gmu@acroinner#1{%
  3062   \ifx\gmu@acroinner#1\relax\else
  3063     \ifcat_a\@nx#1\relax%
  3064       \ifnum`#1=\uccode`#1%
  3065         {\acrocore{#1}}%
  3066         \else{#1}% tu bylo \smallerr
  3067           \fi
  3068         \else{#1}%
  3069           \fi
  3070           \afterfi\gmu@acroinner
  3071   \fi}

```

We extract the very thing done to the letters to a macro because we need to redefine it in fonts that don't have small caps.

```
\acrocore 3075 \def\acrocore{\scshape\lowercase}
```

Since the fonts I am currently using do not support required font feature, I skip the following definition.

```
\IMO 3080 \newcommand*\IMO{\acro{IMO}}
\AKA 3081 \newcommand*\AKA{\acro{AKA}}
\usc 3083 \pdef\usc#1{{\addfontfeature{Letters=UppercaseSmallCaps}#1}}
\uscacro 3085 \def\uscacro{\let\acro\usc}
```

Probably the only use of it is loading gmdocc.cls 'as second class'. This command takes first argument optional, options of the class, and second mandatory, the class name. I use it in an article about gmdoc.

```
\secondclass 3103 \def\secondclass{%
\ifSecondClass 3104   \newif\ifSecondClass
  3105   \SecondClasstrue
  3106   \c@fileswithoptions\c@clsextension% [outeroff,gmeometric]{gmdocc}
      it's loading gmdocc.cls with all the bells and whistles except the error message.
```

Cf. *The TeXbook* exc. 11.6.

A line from L^AT_EX:

```
%\check@mathfonts\fontsize\sf@size\z@\math@fontsfalse\selectfont
didn't work as I would wish: in a \footnotesize's scope it still was \scriptsize, so
too large.
```

```
\gmu@dekfracsimple 3118 \def\gmu@dekfracsimple#1/#2{\leavevmode\kern.1em}
```

```

3119  \raise.5ex\hbox{%
3120    \smaller[3]#1}\gmu@numeratorkern
3121  \dekfraccslash\gmu@denominatorkern
3123  {%
3124    \smaller[3]#2}%
3125  \if@gmu@mmhbox\egroup\fi}

\dekfracsimple
3128 \def\dekfracsimple{%
3129   \let\dekfracc@args\gmu@dekfracsimple
3130 }
\dekfraccslash
3131 \@ifXeTeX{\def\dekfraccslash{\char"2044}}{%
3132   \def\dekfraccslash{/}}% You can define it as the fraction
3133   slash, \char"2044
3134 \dekfracsimple

```

A macro that acts like `\,` (thin and unbreakable space) except it allows hyphenation afterwards:

```
\ikern 3142 \newcommand*\ikern{\,,\penalty1000\hskip0pt\relax}
```

And a macro to forbid hyphenation of the next word:

```
\nohy 3146 \newcommand*\nohy{\leavevmode\kern0pt\relax}
```

```
\yeshy 3147 \newcommand*\yeshy{\leavevmode\penalty1000\hskip0pt\relax}
```

In both of the above definitions ‘osp’ not `\z@` to allow their writing to and reading from files where @ is ‘other’.

`\@isempty`

```
\@isempty 3153 \long\pdef\@isempty#1#2#3{%
3154   \def\gmu@reserveda{#1}%
3155   \ifx\gmu@reserveda\@empty\afterfi{#2}%
3156   \else\afterfi{#3}\fi
3157 }
```

`\include not only .tex's`

`\include` modified by me below lets you to include files of any extension provided that extension in the argument.

If you want to `\include` a non-.tex file and deal with it with `\includeonly`, give the latter command full file name, with the extension that is.

```
\gmu@gettext
3169 \def\gmu@gettext#1.#2\@nil{%
3170   \def\gmu@filename{#1}%
3171   \def\gmu@fileext{#2}%
3173 \def\include#1{\relax
3174   \ifnum\@auxout=\@partaux
3175     \@latex@error{\string\include\space cannot be nested}\@eha
3176   \else\@include#1\fi}
\@include
3178 \def\@include#1{%
3179   \gmu@gettext#1.\@nil
3181   \ifx\gmu@fileext\empty\def\gmu@fileext{tex}\fi
3182   \clearpage
3183   \if@files
3184     \immediate\write\@mainaux{\string\@input{\gmu@filename.aux}}%
3185   \fi

```

```

3186  \@tempsw@true
3187  \if@partsw
3188    \@tempsw@false
3189    \edef\reserved@b{\#1}%
3190    \@for\reserved@a:=\@partlist\do{%
3191      \ifx\reserved@a\reserved@b\@tempsw@true\fi}%
3192    \fi
3193  \if@tempswa
3194    \let\@auxout\@partaux
3195    \if@filesw
3196      \immediate\openout\@partaux\gmu@filename.aux
3197      \immediate\write\@partaux{\relax}%
3198    \fi
3199    \@input{\gmu@filename.\gmu@fileext}%
3200    \inlasthook
3201    \clearpage
3202    \@writeckpt{\gmu@filename}%
3203    \if@filesw
3204      \immediate\closeout\@partaux
3205    \fi
3206  \else

```

If the file is not included, reset \@include \deadcycles, so that a long list of non-included files does not generate an 'Output loop' error.

```

3210  \deadcycles\z@
3211  \nameuse{cp@\gmu@filename}%
3212  \fi
3213  \let\@auxout\@mainaux}

\whenonly \newcommand\whenonly[3]{%
\gmu@whonly \def\gmu@whonly{\#1,}%
3218  \ifx\gmu@whonly\@partlist\afterfi{\#2}\else\afterfi{\#3}\fi}

```

I assume one usually includes chapters or so so the last page style should be closing.

```
\inlasthook \def\inlasthook{\thispagestyle{closing}}
```

Faked small caps

```

\gmu@scapLetters \def\gmu@scapLetters#1{%
3229  \ifx#1\relax\relax\else% two \relaxes to cover the case of empty #1.
3230    \ifcat_a\#1\relax
3231      \ifnum\the\lccode`#1=\#1\relax
3232        {\fakescapscore\MakeUppercase{\#1}}% not Plain \uppercase because
3233          that works bad with inputenc.
3234        \else#1%
3235        \fi
3236      \else#1%
3237      \fi%
3238      \@xa\gmu@scapLetters
3239    \fi}%
\gmu@scapSpaces \def\gmu@scapSpaces#1\#2\@nil{%
3241  \ifx#1\relax\relax
3242  \else\gmu@scapLetters#1\relax
3243  \fi

```

```

3245  \ifx#2\relax\relax
3246  \else\afterfi{\gmu@scapSpaces#2\@nil}%
3247  \fi}
\gmu@scapss#1\@nil{{\def~{{\nobreakspace}}}}%
3249 \def\gmu@scapss#1\@nil{{\def~{{\nobreakspace}}}}%
3250      \gmu@scapSpaces#1\@nil}%% \def\\{{\newline}}\relax adding re-
                           definition of \\ caused stack overflow. Note it disallows hyphenation
                           except at \-
\nobreakspace
\fakescaps 3254 \pdef\fakescaps#1{{\gmu@scapss#1\@nil}}
3255 \let\fakescapscore\gmu@scalematchX
Experimente z akcentami patrz no3.tex.
\tinycae 3259 \def\tinycae{{\tiny AE}}% to use in \fakescaps[\tiny]{...}
3261 \RequirePackage{calc}
      wg \zf@calc@scale pakietu fontspec.
\gmu@scalar 3265 \ifpackageloaded{fontspec}{%
3266   \def\gmu@scalar{1.0}%
3267   \def\zf@scale{}%
\gmu@scalematchX 3268 \def\gmu@scalematchX{%
3269   \begingroup
3270     \ifx\zf@scale\empty\def\gmu@scalar{1.0}%
3271     \else\let\gmu@scalar\zf@scale\fi
3272     \setlength{\tempdima}{\fontdimen5\font}5—ex height
3273     \setlength{\tempdimb}{\fontdimen8\font}8—XTEX synthesized up-
                           percase height.
3274     \divide{\tempdimb}{1000}\relax
3275     \divide{\tempdima}{\tempdimb}
3276     \setlength{\tempdima}{\tempdima*\real{\gmu@scalar}}%
3277     \gm@ifundefined{fakesc@extrascale}{}{%
3278       \setlength{\tempdima}{\tempdima*\real{%
3279         \fakesc@extrascale}}%
3280       \tempcpta=\tempdima
3281       \divide{\tempcpta}{1000}\relax
3282       \tempcntb=-1000\relax
3283       \multiply{\tempcntb}{\tempcpta}
3284       \advance{\tempcntb}{\tempdima}
3285       \xdef\gmu@scscale{\the\tempcpta.%
3286         \ifnum\tempcntb<100\o\fi
3287         \ifnum\tempcntb<10\o\fi
3288         \the\tempcntb}%
3289       \endgroup
3290       \addfontfeature{Scale=\gmu@scscale}%
3291     }{\let\gmu@scalematchX\smallerr}
3292   }{\def\fakescextrascale#1{\def\fakesc@extrascale{#1}}}
\fakescextrascale
\fakesc@extrascale

```

See above/see below

To generate a phrase as in the header depending of whether the respective label is before or after.

```

\wyzejnizej 3300 \newcommand*\wyzejnizej[1]{%
3301   \edef\gmu@tempa{\gm@ifundefined{r@#1}{\arabic{page}}{%
3302     \xa\xa\xa\@secondoftwo\csname r@#1\endcsname}}%

```

```

3303  \ifnum\gmu@tempa<\arabic{page}\relax_wy\.zej\fi
3304  \ifnum\gmu@tempa>\arabic{page}\relax_ni\.zej\fi
3305  \ifnum\gmu@tempa=\arabic{page}\relax_\@xa\ignorespaces\fi
3306 }

```

luzniej and napapierki—environments used in page breaking for money

The name of first of them comes from Polish typesetters' phrase “rozbijać [skład] na papierki”—‘to broaden [leading] with paper scratches’.

```

\napapierkistretch 3316 \def\napapierkistretch{o,3pt}%
3317 It's quite much for 11/13pt leading.

\napapierkicore 3318 \def\napapierkicore{\advance\baselineskip%
3319 by_\optplus\napapierkistretch\relax}

napapierki 3320 \newenvironment*{napapierki}{%
3321 \par\global\napapierkicore}{%
3322 \par\dimen\z@=\baselineskip
3323 \global\baselineskip=\dimen\z@}%
3324 so that you can use \endnapapierki in
interlacing environments.

```

```

\gmu@luzniej 3328 \newcount\gmu@luzniej
\luzniejcore 3330 \newcommand*\luzniejcore[1][1]{%
3331 \advance\gmu@luzniej\@ne% We use this count to check whether we open the
3332 environment or just set \looseness inside it again.
3333 \ifnum\gmu@luzniej=\@ne\multiply\tolerance_by_2\fi
3334 \looseness=#1\relax}

```

After \begin{luzniej} we may put the optional argument of \luzniejcore

```

luzniej 3338 \newenvironment*{luzniej}{\par\luzniejcore}{\par}

```

The starred version does that \everypar, which has its advantages and disadvantages.

```

luzniej* 3343 \newenvironment*{luzniej*}[1][1]{%
3344 \multiply\tolerance_by_2\relax
3345 \everypar{\looseness=#1\relax}}{\par}

\nawj 3347 \newcommand*\nawj{\kern0.1em\relax}%
3348 a kern to be put between parentheses
3349 and letters with descendants such as j or y in certain fonts.

```

The original \pauza of polski has the skips rigid (one is even a kern). It begins with \ifhmode to be usable also at the beginning of a line as the mark of a dialogue.

```

3355 \ifdefined\XeTeXversion
3356 \def\pauza@skipcore{\hskip.2em\plus.1em\relax
3357 \pauzacore\hskip.2em\plus.1em\relax\ignorespaces}%
3359 \def\ppauza@skipcore{\unskip\penalty10000\hskip.2em\plus.1em\%
3360 \relax
3361 -\hskip.2em\plus.1em\ignorespaces}
3362 \AtBeginDocument{%
3363 \pdef\-\{%
3364 \ifhmode
3365 \unskip\penalty10000
3366 \afterfi{%
3367 \@ifnextspace{\pauza@skipcore}%
3368 {\@ifnextMac{\pauza@skipcore{%
3369 \pauzacore\penalty\hyphenpenalty\hskip\z@}}}}%
3370 \else

```

According to *Instrukcja technologiczna. Skład ręczny i maszynowy* the dialogue dash should be followed by a rigid hskip of $\frac{1}{2}$ em.

```
3374     \leavevmode\pauzacore\penalty10000\hskip0,5em\ignorespaces
3375     \fi}%

```

The next command's name consists of letters and therefore it eats any spaces following it, so \@ifnextspace would always be false.

```
\pauza 3378   \pdef\pauza{%
3379     \ifhmode
3380       \unskip\penalty10000
3381         \hskip0.2em\plus0.1em\relax
3382         \pauzacore\hskip.2em\plus0.1em\relax\ignorespaces%
3383     \else
3384       \pauzadial
3385     \fi}%

```

According to *Instrukcja technologiczna. Skład ręczny i maszynowy* the dialogue dash should be followed by a rigid hskip of $\frac{1}{2}$ em.

```
\pauzadial 3390   \pdef\pauzadial{%
3391     \leavevmode\pauzacore\penalty10000\hskip0,5em\ignorespaces}

```

And a version with no space at the left, to begin a \noindent paragraph or a dialogue in quotation marks:

```
\lpauza 3395   \pdef\lpauza{%
3396     \pauzacore\hskip.2em\plus0.1em\ignorespaces}%

```

We define \ppauza as an en dash surrounded with thin stretchable spaces and sticking to the upper line or bare but discretionary depending on the next token being space₁₀. Of course you'll never get such a space after a literal cs so an explicit \ppauza will always result with a bare discretionary en dash, but if we \let-\ppauza...

```
\- 3404   \pdef\-\{%
3405     \ifvmode\bgroup\PackageError{gmutils}{%
3406       command\bslash\ppauza(en\_dash)not\_intended\_for\_vmode.}%
3407       Use\bslash\ppauza(en\_dash)only\_in\_number\_and\_numeral\_%
3408       ranges.}%
3409   \else
3410     \afterfi{%
3411       \if@nextspace{\ppauza@skipcore}{%
3412         \if@nextMac\ppauza@skipcore{\unskip\discretionary{-}{-}{-}}%
3413       }%
3414     }%
3415   \fi
3416 \ppauza 3416   \pdef\ppauza{%
3417     \ifvmode\bgroup\PackageError{gmutils}{%
3418       command\bslash\ppauza(en\_dash)not\_intended\_for\_vmode.}%
3419       Use\bslash\ppauza(en\_dash)only\_in\_number\_and\_numeral\_%
3420       ranges.}%
3421   \else
3422     \unskip\discretionary{-}{-}{-}%
3423   \fi}%
3424 \emdash 3424   \def\emdash{\char`\-}%
3425 }% of at begin document

```

```

\longpauza 3427 \def\longpauza{\def\pauzacore{-}}
\pauzacore 3428 \longpauza
\shortpauza 3429 \def\shortpauza{%
\pauzacore 3430   \def\pauzacore{-\kern,23em\relax\llap{-}}}
3431 \fi% of if XETEX.

```

If you have all the three dashes on your keyboard (as I do), you may want to use them for short instead of `\pauza`, `\ppauza` and `\dywiz`. The shortest dash is defined to be smart in math mode and result with `-`.

```

3437 \ifdefined\XeTeXversion
3438 \foone{\catcode`-\active}\catcode`-\active\catcode`-\active}{%
\adashes 3439 \def\adashes{\AtBeginDocument\adashes}%
            because \pauza is defined at
            begin document.
\adashes 3441 \AtBeginDocument{\def\adashes{%
3442   \catcode`-\active\let-\-%
3443   \catcode`-\active\let-\-%
3445 }}}
3446 \else
3447 \relaxen\adashes
3448 \fi

```

The hyphen shouldn't be active IMO because it's used in T_EX control such as `\hskip-2pt`. Therefore we provide the `\ahyphen` declaration reluctantly, because sometimes we need it and always use it with caution. Note that my active hyphen in vertical and math modes expands to `-12`.

```

\gmu@dywiz 3457 \def\gmu@dywiz{\ifmmode-\else
3458   \ifvmode-\else\afterfifi\dywiz\fi\fi}%
3460 \foone{\catcode`-\active}{%
\ahyphen 3461 \def\ahyphen{\let-\gmu@dywiz\catcode`-\active}}

```

To get current time. Works in ε-T_EXs, including X_ET_EX. `\czas` typesets 16.30 and `\czas[:]` typesets 16:30.

```

\czas 3466 \newcommand*\czas[1][.]{%
3467   \the\numexpr(\time-30)/60\relax#1%
3468   \tempcnta=\numexpr\time-(\time-30)/60*60\relax
3469   \ifnum\tempcnta<10\o\fi\the\tempcnta}

3472 \@ifXeTeX{%
\textbullet 3473 \pdef\textbullet{%
3476   \iffontchar\font"2022\char"2022\else\ensuremath{\bullet}%
   \fi}}
\textbullet 3477 {\def\textbullet{\ensuremath{\bullet}}}

\tytulowa 3479 \newenvironment*{\tytulowa}{\newpage}{\par\thispagestyle{empty}%
\newpage}

```

To typeset peoples' names on page 4 (the editorial page):

```

\nazwired 3482 \def\nazwired{\quad\textsc}

```

Typesetting dates in my memoirs

A date in the YYYY-MM-DD format we'll transform into 'DD mmmm yyyy' format or we'll just typeset next two tokens/{...} if the arguments' string begins with --. The latter option is provided to preserve compatibility with already used macros and to avoid

a starred version of \thedata and the same time to be able to turn \datef off in some cases (for SevSevo4.tex).

```

\polskadata 3496 \newcommand*\polskadata{%
\gmu@datef 3497   \def\gmu@datef##1-##2-##3##4,##5\gmu@datef{%
3498     \ifx\relax##2\relax##3##4%
3499     \else
3500       \ifnum##3@firstofmany##4o\@nil=o\relax
3501       \else
3502         \ifnumo##3=o\relax
3503         \else##3%
3504           \fi##4%
3505           \fi
3506           \ifcase##2\relax\or\_\_stycznia\or\_\_lutego%
3507             \or\_\_marca\or\_\_kwietnia\or\_\_maja\or\_\_czerwca\or\_\_lipca\or\_\_
3508               sierpnia%
3509             \or\_\_wrze\u\144nia\or\_\_pa\u\144dziernika\or\_\_listopada\or\_\_grudnia\else
3510               {}%
3511             \fi
3512             \if\relax##1\relax\else\_\_fi\_\#1%
3513             \fi
3514             \gmu@datecomma{##5}{}% of \gmu@datef.

\gmu@datefs1 3515 \def\gmu@datefs1##1##2##3##4,##5\gmu@datefs1{%
3516   \if\relax##2\relax##3##4%
3517   \else
3518     \ifnum##3@firstofmany##4o\@nil=o\relax
3519     \else
3520       \ifnumo##3=o\relax
3521       \else##3%
3522         \fi##4%
3523         \fi
3524         \ifcase##2\relax\or\_\_stycznia\or\_\_lutego%
3525           \or\_\_marca\or\_\_kwietnia\or\_\_maja\or\_\_czerwca\or\_\_lipca\or\_\_
3526             sierpnia%
3527             \or\_\_wrze\u\144nia\or\_\_pa\u\144dziernika\or\_\_listopada\or\_\_grudnia\else
3528               {}%
3529             \fi
3530             \if\relax##1\relax\else\_\_fi\_\#1%
3531             \fi
3532             \gmu@datecomma{##5}{}%
3533 }% of \polskadata
3537 \polskadata

```

For documentation in English:

```

\englishdate 3540 \newcommand*\englishdate{%
\gmu@datef 3541   \def\gmu@datef##1-##2-##3##4,##5\gmu@datef{%
3542     \if\relax##2\relax##3##4%
3543     \else
3544       \ifcase##2\relax\or\_\_January\or\_\_February%
3545         \or\_\_March\or\_\_April\or\_\_May\or\_\_June\or\_\_July\or\_\_August%
3546         \or\_\_September\or\_\_October\or\_\_November\or\_\_December\else
3547           {}%
3548         \fi

```

```

3549 \ifnum##3@firstofmany##4o@@nil=o\relax
3550   \else
3551     \%
3552     \ifnumo##3=o\relax
3553       \else##3%
3554         \fi##4%
3555         \ifcase##3@firstofmany##4\relax@@nil\relax\or_st\or_nd%
3556           \or_rd\else_th\fi
3557         \fi
3558         \ifx\relax##1\relax\else,\_\fi##1%
3559       \fi
3560     \gmu@datecomma{##5}%
3561     \def\gmu@datefs1##1##2##3##4##5\gmu@datefs1{%
3562       \if\relax##2\relax##3##4%
3563       \else
3564         \ifcase##2\relax\or_January\or_February%
3565           \or_March\or_April\or_May\or_June\or_July\or_August%
3566           \or_September\or_October\or_November\or_December\else
3567             {}%
3568         \fi
3569         \ifnum##3@firstofmany##4o@@nil=o\relax
3570           \else
3571             \%
3572             \ifnumo##3=o\relax
3573               \else##3%
3574                 \fi##4%
3575                 \ifcase##3@firstofmany##4\relax@@nil\relax\or_st\or_nd%
3576                   \or_rd\else_th\fi
3577                   \fi
3578                   \if\relax##1\relax\else,\_\fi##1%
3579                 \fi
3580               \gmu@datecomma{##5}%
3581             }
3582 \gmu@datecomma 3583 \def\gmu@datecomma#1{ sometimes we want to typeset something like '11 wrześ-
3584           nia, czwartek' so we add handling for comma in the \ldate's argument.
3585           \ifx\gmu@datecomma#1\gmu@datecomma\else
3586             ,\gmu@stripcomma#1%
3587           \fi
3588 }% of \gmu@datecomma
\gmu@stripcomma 3591 \def\gmu@stripcomma#1,{#1}
3592 \ifgmu@dash 3594 \newif\ifgmu@dash
\gmu@ifnodash 3596 \def\gmu@ifnodash#1-#2@@nil{%
3597   \def\gmu@tempa{#2}%
3598   \ifx\gmu@tempa\@empty}
\gmu@testdash 3600 \pdef\gmu@testdash#1\ifgmu@dash{%
3601   \gmu@ifnodash#1-\@nil
3602   \gmu@dashfalse
3603   \else
3604     \gmu@dashtrue
3605   \fi
3606 \ifgmu@dash}

```

A word of explanation to the pair of macros above. `\gmu@testdash` sets `\iftrue` the `\ifgmu@dash` switch if the argument contains an explicit `-`. To learn it, an auxiliary `\gmu@ifdash` macro is used that expands to an open (un`\fied`) `\ifx` that tests whether the dash put by us is the only one in the argument string. This is done by matching the parameter string that contains a dash: if the investigated sequence contains (another) dash, #2 of `\gmu@ifdash` becomes the rest of it and the ‘guardian’ dash put by us so then it’s nonempty. Then #2 is took as the definiens of `\@tempa` so if it was empty, `\@tempa` becomesx equal `\@empty`, otherwise it isx not.

Why don’t we use just `\gmu@ifdash`? Because we want to put this test into another `\if...`. A macro that doesn’t *mean* `\if...` wouldn’t match its `\else` nor its `\fi` while TeX would skip the falsified branch of the external `\if...` and that would result in the ‘extra `\else`’ or ‘extra `\fi`’ error.

Therefore we wrap the very test in a macro that according to its result sets an explicit Boolean switch and write this switch right after the testing macro. (Delimiting `\gmu@testdash`’es parameter with this switch is intended to bind the two which are not one because of TeXnical reasons only.)

Warning: this pair of macros may result in ‘extra `\else`/extra `\fi`’ errors however, if `\gmu@testdash` was `\expandafter`d.

Dates for memoirs to be able to typeset them also as diaries.

```

\ifdate 3637 \newif\ifdate
\bidate 3639 \pdef\bidate#1{%
 3640   \ifdate\gmu@testdash#1%
 3641     \ifgmu@dash
 3642       \gmu@datef#1,\gmu@datef
 3643     \else
 3644       \gmu@datefsl#1,\gmu@datefsl
 3645     \fi\fi}

\linedate 3647 \pdef\linedate{\@ifstar\linedate@\@linedate@}
\linedate@ 3648 \pdef\linedate@#1{\linedate@{--{}{}#1}}
\linedate@ 3649 \pdef\linedate@#1{\par\ifdate\addvspace{\dateskip}%
 3650   \date@line{\footnotesize\itshape\bidate{#1}}%
 3651   \nopagebreak\else%\ifnum\arabic{dateinsection}>0\dekbigskip\fi
 3652   \addvspace{\bigskipamount}%
 3653 \fi}% end of \linedate.

 3655 \let\dateskip\medskipamount

\rdate 3663 \pdef\rdate{\let\date@line\rightline\linedate}
\ldate 3664 \pdef\ldate{%
 3666   \def\date@line##1{\par\raggedright##1\par}%
 3667   \linedate}
\runindate 3668 \newcommand*\runindate[1]{%
 3669   \paragraph{\footnotesize\itshape\gmu@datef#1\gmu@datef}%
 3670   \stepcounter{dateinsection}}

```

I’m not quite positive which side I want the date to be put to so let’s `let` for now and we’ll be able to change it in the very documents.

```

 3673 \let\thedata\ldate
\zwrobcy 3676 \pdef\zwrobcy#1{\emph{#1}}% ostinato, allegro con moto, garden party etc.,
          także kompliment
\tytul 3679 \pdef\tytul#1{\emph{#1}}

```

Maszynopis w świecie justowanym zrobi delikatną chorągiewkę. (The `maszynopis` environment will make a delicate ragged right if called in a justified world.)

```

maszynopis 3685 \newenvironment{maszynopis}[1][]{\#1\ttfamily
3686   \hyphenchar\font=45\relax% this assignment is global for the font.
3687   \tempskipa=\glueexpr\rightskip+\leftskip\relax
3688   \ifdim\gluestretch\tempskipa=\z@%
3689   \tolerance900
      it worked well with tolerance = 900.
3690   \advance\rightskip by \z@ plus .5em\relax\fi
3691   \fontdimen3\font=\z@% we forbid stretching spaces...
3692   \fontdimen4\font=\z@ but allow shrinking them.
3693   \hyphenpenalty0% not to make TeX nervous: in a typewriting this marvellous
      algorithm of hyphenation should be turned off and every line broken at the
      last allowable point.
3694   \StoreMacro\pauzacore
\pauzacore 3695 \def\pauzacore{-\rlap{\kern-0.3em-}}%
3696 }{\par}
\justified 3703 \newcommand*\justified{%
3704   \leftskip=1\leftskip% to preserve the natural length and discard stretch and
      shrink.
3705   \rightskip=1\rightskip
3706   \parfillskip=1\parfillskip
3707   \advance\parfillskip by \oslash plus \fil\relax
3708   \let\\=\@normalcr}
3709 }

To conform Polish recommendation for typesetting saying that a paragraph's last line
leaving less than \parindent should be stretched to fill the text width:
\fullpar 3714 \newcommand*\fullpar{%
3715   \hunskip
3716   \bgroup\parfillskip\z@skip\par\egroup}

To conform Polish recommendation for typesetting saying that the last line of a para-
graph has to be 2\parindent long at least. The idea is to set \parfillskip naturally
rigid and long as \textwidth-2\parindent, but that causes non-negligible shrinking
of the interword spaces so we provide a declaration to catch the proper glue where the
parindent is set (e.g. in footnotes parindent is 0pt)
\twoparinit 3725 \newcommand*\twoparinit{%
      the name stands for 'last' paragraph line's length
      minimum two \parindent.
3726   \edef\twopar{%
3727     \hunskip% it's \protected, remember?
3728     \bgroup
3729     \parfillskip=\the\glueexpr
3730     \dimexpr\textwidth-2\parindent\relax
3731     minus\dimexpr\textwidth-2\parindent\relax
3732     \relax% to delimit \glueexpr.
3733     \relax% to delimit the assignment.
3734     \par\egroup
3735   }% of \gmu@twoparfill
3736 }% of \twoparinit.
3741 }

For dati under poems.
\wherncore 3748 \newcommand\wherncore[1]{%
3749   \rightline{%
3750   \parbox{o.7666\textwidth}{%
3751     \leftskip\oslash plus \textwidth
3752     \parfillskip\relax

```

```

3753      \let\\linebreak
3754      \footnotesize_{#1}}}
\whern 3756 \def\whern{%
3757   \@ifstar\wherncore{\vskip\whernskip\wherncore}{}
\whernskip 3760 \newskip\whernskip
3761 \whernskip2\baselineskip_minus_2\baselineskip\relax
\whernup 3763 \newcommand\whernup[1]{\par\wherncore{#1}}

```

A left-slanted font

Or rather a left Italic *and* left slanted font. In both cases we sample the skewness of the *itshape* font of the current family, we reverse it and apply to *\itshape* in *\litshape* and *\textlit* and to *\sl* in *\lsl*. Note a slight asymmetry: *\litshape* and *\textlit* take the current family while *\lsl* and *\textlsl* the basic Roman family and basic (serif) Italic font. Therefore we introduce the *\lit* declaration for symmetry, that declaration left-slants *\it*.

I introduced them first while typesetting E. Szarzyński's *Letters* to follow his (elaborate) hand-writing and now I copy them here when need left Italic for his *Albert Camus' The Plague* to avoid using bold font.

Of course it's rather esoteric so I wrap all that in a declaration.

```

\leftslanting 3787 \def\leftslanting{%
\litshape 3788 \pdef\litshape{%
3790   \itshape
3791   \tempdima=-2\fontdimen1\font
3792   \advance\leftskip_by\strip@pt\fontdimen1\font_ex% to assure al least
           the lowercase letters not to overshoot to the (left) margin. Note this has
           any effect only if there is a \par in the scope.
3796 \edef\gmu@tempa{%
3797   @nx\addfontfeature{RawFeature={slant=\strip@pt%
           \tempdima}}}% when not \edefed, it caused an error, which is
           perfectly understandable.
3800 \gmu@tempa}%
\textlit 3803 \pdef\textlit##1{%
3804   {\litshape##1}}%
\lit 3806 \pdef\lit{\rm\litshape}%
\lsl 3809 \pdef\lsl{{\it
3812   \tempdima=-\fontdimen1\font
3813   \xdef\gmu@tempa{%
3814     @nx\addfontfeature{RawFeature={slant=\strip@pt%
           \tempdima}}}}%
3815   \rm}% Note in this declaration we left-slant the basic Roman font not the it-
           shape of the current family.
3817 \gmu@tempa}%

```

Now we can redefine *\em* and *\emph* to use left Italic for nested emphasis. In Polish typesetting there is bold in nested emphasis as I have heard but we don't like bold since it perturbs homogeneous greyness of a page. So we introduce a three-cycle instead of two: Italic, left Italic, upright.

```

\em 3825 \pdef\em{%
3826   \ifdim\fontdimen1\font=\z@\itshape
3827   \else
3828     \ifdim\fontdimen1\font>\z@\rm\itshape

```

```

3829      \else\upshape
3830      \fi
3831      \fi}%
3834  \pdef\emph##1{%
3835  {\em##1}}%
3836 }% of \leftslanting.

```

Thousand separator

\thousep 3840 \pdef\thousep#1{%
 a macro that'll put the thousand separator between every two
 three-digit groups.

First we check whether we have at least five digits.

```

3844  \gmu@thou@fiver#1\relax\relax\relax\relax% we put
      five \relaxes after the parameter to ensure the string will
      meet \gmu@thou@fiver's definition.
3847  \gmu@thou@fiver{#1}{%
  if more than five digits:
  \emptyify\gmu@thou@put
  \relaxen\gmu@thou@o\relaxen\gmu@thou@i\relaxen\gmu@thou@ii
  \tempcnta\z@
  \gmu@thou@putter#1\gmu@thou@putter
  \gmu@thou@put
}
3853  }}

\gmu@thou@fiver
3855 \def\gmu@thou@fiver#1#2#3#4#5\gmu@thou@fiver#6#7{%
3856   \ifx\relax#5\relax\afterfi{#6}\else\afterfi{#7}\fi}

```

\gmu@thou@putter 3858 \def\gmu@thou@putter#1#2{%
 we are sure to have at least five tokens before the
 guardian \gmu@thou@putter.

```

3860  \advance\tempcnta\@ne
3861  \tempcntb\tempcnta
3862  \divide\tempcntb\@relax
3863  \tempcnta=\numexpr\tempcnta-\tempcntb*3
3864  \edef\gmu@thou@put{\gmu@thou@put#1%
  \ifx\gmu@thou@putter#2\else
  \ifcase\tempcnta
    \gmu@thou@o\or\gmu@thou@i\or\gmu@thou@ii%
    all three cases are
    yet \relax so we may put them in an \edef safely.
  \fi
  \fi}%
3871  \fi}%
3872  \ifx\gmu@thou@putter#2%
  if we are at end of the digits...
3873  \edef\tempa{%
  \ifcase\tempcnta
    \gmu@thou@o\or\gmu@thou@i\or\gmu@thou@ii
  \fi}%
3877  \xa\let\tempa\gmu@thousep% ... we set the proper cs...
3878  \else%
  or ...
  \afterfi{%
    \gmu@thou@putter#2}%
  \ifendofdigits
  \fi}%
3882 }%

```

\gmu@thousep 3884 \def\gmu@thousep{\,}%
 in Polish the recommended thousand separator is a thin
 space.

So you can type `\thousep{7123123123123}` to get `7 123 123 123 123`. But what if you want to apply `\thousep` to a count register or a `\numexpr`? You should write one or two `\expandafters` and `\the`. Let's do it only once for all:

```
\xathousep 3892 \pdef\xathousep#1{\@xa\thousep\@xa{\the#1}}
            Now write \xathousep{\numexpr\!10*9*8*7*6*\!120} to get 3 628 800.

\shortthousep 3896 \def\shortthousep{%
\thous 3897 \pdef\thous{%
 3898   \ifmmode\hbox\bgroup\@gmu@mmhboxtrue\fi
 3899   \afterassignment\thous@inner
 3900   \tempcnta=\}%
}
\thous@inner 3902 \def\thous@inner{%
 3903   \ifnum\tempcnta<0\$-\$%
 3904     \tempcnta=-\tempcnta
 3905   \fi
 3906   \xathousep\tempcnta
 3907   \if@gmu@mmhbox\egroup
 3908   \else\afterfi{\ifnextcat\!a\space{}{}\}%
 3909   \fi\}%
}
3910 }% of \shortthousep.
```

And now write `\thous\!3628800` to get `3 628 800` even with a blank space (beware of the range of T_EX's counts).

hyperref's \nolinkurl into \url*

```
\urladdstar 3918 \def\urladdstar{%
 3919   \AtBeginDocument{%
 3920     \@ifpackageloaded{hyperref}{%
 3921       \StoreMacro\url
 3922       \def\url{\@ifstar{\nolinkurl}{\storedcsname{url}}}\%
 3923     }{}}
 3925 \onlypreamble\urladdstar
 3928 \endinput
```

Change History

vo.74

```
\begnamedgroup@ifcs:
The catcodes of \begin and \end
argument(s) don't have to agree
strictly anymore: an environment is
properly closed if the \begin's and
\end's arguments result in the same
\csname, 1063
```

General:

```
Added macros to make sectioning
commands of mwcls and standard
classes compatible. Now my
sectionings allow two optionals in
```

both worlds and with mwcls if there's
only one optional, it's the title to toc
and running head not just to the
latter, 3928

vo.75

```
\ifnextcat:
\let for #1 changed to \def to allow
things like \noexpand~, 858
\ifnextif:
\let for #1 changed to \def to allow
things like \noexpand~, 894
\ifnif:
added, 919
```

vo.76	\texttilde: renamed from \~ since the latter is one of L ^A T _E X accents, 2837
General:	
	A ‘fixing’ of \dots was rolled back since it came out they were o.k. and that was the qx encoding that prints them very tight, 3928
\freeze@actives:	added, 2955
vo.77	
General:	
	\afterfi & pals made two-argument as the Marcin Woliński’s analogoi are. At this occasion some redundant macros of that family are deleted, 3928
vo.78	
General:	
	\@namelet renamed to \n@melet to solve a conflict with the beamer class. The package contents regrouped, 3928
vo.79	
\not@onlypreamble:	All the actions are done in a group and therefore \xdef used instead of \edef because this command has to use \do (which is contained in the \@preamblecmds list) and \not@onlypreamble itself should be able to be let to \do, 1652
vo.80	
General:	
	CheckSum 1689, o
\hfillneg:	added, 2876
vo.81	
\dekfracslash:	moved here from pmlectionis.cls, 3134
\ifSecondClass:	moved here from pmlectionis.cls, 3106
vo.82	
\ikern:	added, 3142
vo.83	
\~:	postponed to \begin{document} to avoid overwriting by a text command and made sensible to a subsequent /, 2829
vo.84	
General:	
	CheckSum 2684, o
vo.85	
General:	
	CheckSum 2795, o
	fixed behaviour of too clever headings with gmdoc by adding an \ifdim test, 3928
vo.86	
	\texttilde: renamed from \~ since the latter is one of L ^A T _E X accents, 2837
vo.87	
General:	
	CheckSum 4027, o the package goes ε-T _E X even more, making use of \ifdefined and the code using UTF-8 chars is wrapped in a X _E T _E X-condition, 3928
vo.88	
General:	
	CheckSum 4040, o
\RestoreEnvironment:	added, 1591
\storedcsname:	added, 1582
\StoreEnvironment:	added, 1587
vo.89	
General:	
	removed obsolete adjustment of pgf for X _E T _E X, 3928
vo.90	
General:	
	CheckSum 4035, o
\XeTeXthree:	adjusted to the redefinition of \verb in xltxtra 2008/07/29, 2470
vo.91	
General:	
	CheckSum 4055, o removed \jobnamewoe since \jobname is always without extension. \xiispace forked to \visiblespace \let to \xxt@visiblespace of xltxtra if available. The documentation driver integrated with the .sty file, 3928
vo.92	
\@checkend:	shortened thanks to \@ifenvir, 1095
\@gif:	added redefinition so that now switches defined with it are \protected so they won’t expand to a further expanding or unbalanced \iftrue/false in an \edef, 277
\@ifenvir:	added, 1087
General:	
	CheckSum 4133, o
vo.93	
\@nameedef:	added, 225
General:	

A couple of
`\DeclareRobustCommand*` changed
 to `\pdef`, 3928
`CheckSum` 4140, o
`CheckSum` 4501, o
 The numerical macros commented out
 as obsolete and never really used, 3928
`\ampulexdef:`
 added, 751
`\em:`
 added, 3825, 3834
`\gmu@RPfor:`
 renamed from `\gmu@RPif` and #3
 changed from a csname to `cs`, 3017
`\litshape:`
 copied here from E. Szarzyński's *The Letters*, 3788
`\lsl:`
 copied here from E. Szarzyński's *The Letters*, 3809
`\nocite:`
 a bug fixed: with `natbib` an 'extra '' error. Now it fixes only the standard version of `\nocite`, 1690
`\pdef:`
 added, 183
`\pprovide:`
 added, 212
`\provide:`
 added, 197
`\textlit:`
 added, 3803
`\thoussep:`
 added, 3840

vo.94
`\@xau:`
 added, 179
 General:
`\bgroup` and `\egroup` in the macro
 storing commands and in `\foone`
 changed to `\begingroup` and
`\endgroup` since the former produce
 an empty `\mathord` in math mode
 while the latter don't, 3928
`CheckSum` 4880, o

removed `\unex@namedef` and
`\unex@nameuse`, probably never
 really used since they were
 incomplete: `\edef@other`
 undefined, 3928
 The code from ancient `xparse` (1999) of
`\TeXLive` 2007 rewritten here, 3928
`\afterfifi:`
`\if` removed from parameters' string, 999
`\ampulexdef:`
 made `xparse`-ish and `\ampulexset`
 removed, 751
`\dekfracc:`
 made to work also in math mode, even
 with math-active digits, 2562
`\gm@ifundefined:`
 added. All `\@ifundefined`s used by
 me changed to this, 408
 made robust to unbalanced `\ifs` and
`\fis` the same way as `\TeX`'s
`\@ifundefined` (after a heavy debug
`::`), 408
`\gmath:`
 removed definition of `\langle letter \rangle`s and
`\langle digit \rangle`s, 2621
`\ldate:`
`\leftline` replaced with `\par... \par`
 to work well with `floatfl`, 3664
`\prependmacro:`
 order of arguments reversed, 374
`\resizographics:`
`\includegraphics` works well in
`\TeX` so I remove the complicated
 version with `\XeTeXpicfile`, 2591
`\textbullet:`
 the `\TeX` version enriched with
`\iffontchar` due to lack of bullets
 with the default settings reported by
 Morten Høgholm and Edd Barrett, 3473

vo.95
 General:
`CheckSum` 4908, o
`\gm@testdefined:`
 added, 425
`\gm@testundefined:`
 added, 440

Index

Numbers written in italic refer to the code lines where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used. The numbers preceded with 'p.' are page numbers. All the numbers are hyperlinks.

`*`, 947, 948, 949, 951, 955,

956, 957, 961, 2829, 3010 `\+`, 3011

\-, 1380, 3461
\<...>, 1311
\@nil, 1337, 1339, 1341,
2884, 3169, 3179,
3241, 3246, 3249,
3250, 3254, 3500,
3518, 3549, 3555,
3569, 3575, 3596, 3601
\@M, 1995
\@afterheading, 1988
\@badend, 1095
\@begnamedgroup, 1039,
1056, 1061
\@begnamedgroup@ifcs,
1057, 1060
\@car, 2338
\@cclv, 2993
\@cclvi, 2978
\@checkend, 1095
\@clsextension, 3106
\@clubpenalty, 2000
\@currenvir, 1042, 1089
\@currenvline, 1046
\@currsize, 1139, 1140,
1141, 1142, 1143,
1144, 1145, 1146,
1147, 1148
\@ddc, 496, 528, 544, 563,
591, 596, 597
\@ddc@, 498, 520
\@ddc@C, 616
\@ddc@O, 600
\@ddc@c, 605
\@ddc@c@, 607, 613, 618
\@ddc@m, 552, 628
\@ddc@o, 555
\@ddc@o@, 557, 560, 602
\@ddc@s, 547
\@ddc@x, 657
\@ddc@xm, 630
\@ddc@xmm, 633
\@ddc@xmm, 636
\@ddc@xmomm, 639
\@ddc@xmomm, 642
\@ddc@xmomm, 645
\@ddc@xmomm, 648
\@ddc@xmomm, 651
\@ddc@xmomm, 654
\@emptify, 384, 385, 389
\@enumctr, 2251, 2252, 2258
\@enumdepth, 2247, 2250,
2251
\@fileswithoptions, 3106
\@firstofmany, 2884,
3500, 3518, 3549,
3555, 3569, 3575
\@firstofone, 522, 682
\@gif, 263, 264, 271
\@gmu@mmhboxtrue, 2564,
3898
\@if, 286, 287, 290
\@ifXeTeX, 2464, 2472,
2598, 3131, 3472
\@isempty, 775, 1930,
1950, 3153
\@ifenvir, 1087, 1095
\@ifl@aded, 1676
\@ifncat, 865, 868, 883
\@ifnextMac, 971, 3368, 3411
\@ifnextac, 930
\@ifnextcat, 858, 931, 3908
\@ifnextif, 894
\@ifnextspace, 954, 3367,
3410
\@ifnif, 901, 904, 919
\@ifnotmw, 1809, 1834,
1983, 2088, 2175, 2230
\@include, 3176, 3178
\@itemdepth, 2265, 2268,
2269
\@itemitem, 2269, 2270
\@minus, 2098, 2103, 2109,
2111, 2116, 2118,
2125, 2130
\@nameedef, 225
\@nobreakfalse, 1994, 2931
\@nobreaktrue, 1989
\@normalcr, 3709
\@nx, 177
\@oarg, 1415, 1417, 1418
\@oargsq, 1415, 1418, 1433
\@onlypreamble, 1717,
2933, 3925
\@parg, 1422, 1424, 1425
\@pargp, 1422, 1425, 1434
\@parindent, 2254, 2255,
2257, 2272, 2273, 2275
\@parsed@endenv, 510,
514, 664
\@parsed@endenv@, 515,
517, 665
\@pkgextension, 1677
\@preamblecmds, 1671,
1673, 1686, 1690
\@relaxen, 393, 394, 398
\@secondofthree, 676, 688
\@starttoc, 2926
\@tempcntb*, 3863
\@tempdima, 3272, 3276,
3277, 3279, 3280,
3284, 3791, 3797,
3812, 3814
\@tempdima*, 3277, 3279
\@tempdimb, 3273, 3275, 3276
\@temptokena, 494, 504,
512, 541, 542, 584, 585
\@temptokenb, 480, 481,
495, 532, 536, 538,
568, 572, 574, 625
\@textsuperscript,
2605, 2606
\@thirdofthree, 680, 689
\@toodeep, 2248, 2266
\@topnewpage, 1890
\@typeset@protect, 521
\@undefined, 159
\@whilenum, 2978, 2993
\@xa, 176, 179
\@xau, 179
\@xifncat, 870, 883
\@xifnif, 906, 919
\@acro, 3045, 3080, 3081, 3085
\@acrocore, 3065, 3075
\@adashes, 3439, 3439,
3441, 3447
\@addfontfeature, 2494,
2525, 2527, 2553,
2600, 2779, 2792,
3083, 3291, 3797, 3814
\@addto@macro, 364, 371
\@addtoheading, 1964
\@addtomacro, 371, 2762
\@addtotoks, 380, 2778
\@AE, 3259
\@afterassignment, 3899
\@afterfi, 202, 421, 934,
958, 959, 997, 1061,
1062, 1091, 1092,
1329, 1360, 1431,
1474, 1551, 2467,
3054, 3070, 3155,
3156, 3218, 3246,
3366, 3409, 3856,
3879, 3908
\@afterfifi, 199, 200, 416,
418, 999, 1530, 1535,
2466, 3458
\@afterfififi, 1007
\@afteriffifi, 1001
\@afteriffififi, 1006
\@afterififfififi, 1005

\ahyphen, [3461](#)
 \AKA, [3081](#)
 \all@other, [772](#), [773](#), [782](#),
 [783](#), [784](#), [2440](#), [2542](#),
 [2544](#)
 \alpha, [2625](#)
 \ampulexdef, [751](#), [793](#),
 [808](#), [1714](#), [2749](#)
 \ampulexhash, [812](#)
 \AmSTeX, [2375](#)
 \arg, [1430](#), [1431](#)
 \AtBeginDocument, [1249](#),
 [1429](#), [1684](#), [1720](#),
 [1780](#), [2482](#), [2491](#),
 [2835](#), [3028](#), [3362](#),
 [3439](#), [3441](#), [3919](#)

 \begin, [1056](#)
 \begin*, [1056](#)
 \bgcolor, [2783](#)
 \BibTeX, [2378](#)
 \bidate, [3639](#), [3650](#)
 \Biggl, [2724](#)
 \biggl, [2722](#)
 \Biggr, [2725](#)
 \biggr, [2723](#)
 \Bigl, [2720](#)
 \bigl, [2718](#)
 \Bigr, [2721](#)
 \bigr, [2719](#)
 \bigskipamount, [2873](#), [3652](#)
 \boldmath, [2338](#)
 \BooleanFalse, [550](#), [698](#)
 \BooleanTrue, [549](#), [699](#)
 \box, [2359](#), [2717](#)
 \bslash, [1228](#), [1379](#), [1482](#),
 [1559](#), [1583](#), [1957](#),
 [1958](#), [1959](#), [3406](#),
 [3407](#), [3418](#), [3419](#)
 \bullet, [3476](#), [3477](#)

 \c@gm@PronounGender, [1747](#)
 \c@NoNumSecs, [1782](#)
 \c@secnumdepth, [1839](#)
 \ClassError, [1956](#)
 \cleardoublepage, [1796](#)
 \clubpenalty, [1995](#), [2000](#)
 \cmd, [1404](#)
 \cmd@to@cs, [1404](#), [1406](#)
 \color, [3005](#), [3006](#)
 \continuum, [3039](#)
 \copy, [2321](#), [2351](#), [2365](#),
 [2782](#), [2794](#)
 \count, [2326](#), [2327](#), [2328](#),
 [2329](#), [2330](#), [2331](#),

 2332, [2333](#), [2976](#),
 [2978](#), [2979](#), [2980](#),
 [2983](#), [2992](#), [2993](#),
 [2994](#), [2995](#)
 \cs, [1379](#), [1385](#), [1389](#), [1404](#)
 \cup, [2791](#)
 \czas, [3466](#)
 \czer, [3007](#), [3010](#), [3011](#)
 \czerwo, [3006](#), [3007](#)

 \dag, [3011](#)
 \date@line, [3650](#), [3663](#), [3666](#)
 \dateskip, [3649](#), [3655](#)
 \deadcycles, [3210](#)
 \DeclareDocumentCommand, [478](#), [486](#), [507](#), [660](#), [751](#)
 \DeclareDocumentEnvironment, [506](#), [659](#)
 \DeclareLogo, [2292](#), [2311](#),
 [2337](#), [2348](#), [2378](#),
 [2384](#), [2387](#), [2389](#),
 [2392](#), [2395](#), [2399](#),
 [2401](#), [2404](#), [2411](#)
 \DeclareRobustCommand*, [1170](#), [1171](#), [1172](#),
 [1173](#), [1379](#)
 \DeclareTextCommand, [2305](#)
 \DeclareTextCommandDefault, [2307](#)
 \defobeylines, [2861](#)
 \dekbigskip, [2873](#)
 \dekfracc, [2562](#)
 \dekfracc@args, [2540](#),
 [2551](#), [2565](#), [3129](#)
 \dekfraccsimple, [3128](#), [3134](#)
 \dekfraccslash, [3121](#),
 [3131](#), [3132](#)
 \dekmedskip, [2872](#)
 \deksmallskip, [2870](#)
 \Delta, [2626](#)
 \dimen, [2940](#), [2941](#), [2942](#),
 [3323](#), [3324](#)
 \dimexpr, [2650](#), [2655](#),
 [2661](#), [2716](#), [2783](#),
 [3731](#), [3732](#)
 \discre, [1322](#), [1331](#), [1348](#)
 \discret, [1324](#), [1329](#)
 \divide, [2328](#), [2331](#), [2332](#),
 [3275](#), [3276](#), [3281](#), [3862](#)
 \document, [1717](#)
 \dp, [2697](#), [2713](#), [2716](#), [2783](#)
 \dywiz, [3458](#)
 \eequals, [2953](#)

 \egfirstofone, [242](#), [244](#)
 \egRestore@Macro, [1544](#),
 [1546](#)
 \egRestore@MacroSt, [1544](#), [1547](#)
 \egStore@Macro, [1464](#), [1469](#)
 \egStore@MacroSt, [1464](#),
 [1470](#)
 \em, [3825](#), [3835](#)
 \emdash, [3424](#)
 \emptify, [385](#), [385](#), [2496](#),
 [2757](#), [2761](#), [3848](#)
 \endlist, [2261](#), [2278](#)
 \englishdate, [3540](#)
 \enoughpage, [2938](#)
 \ensuremath, [1283](#), [1296](#),
 [2396](#), [2607](#), [3040](#),
 [3476](#), [3477](#)
 \enumerate*, [2246](#)
 \env, [1385](#)
 \equals, [2951](#)
 \eTeX, [2395](#), [2399](#)
 \everydisplay, [2747](#), [2800](#)
 \everymath, [2621](#), [2747](#),
 [2750](#), [2778](#), [2800](#)
 \everypar, [1991](#), [2001](#), [3345](#)
 \exists, [2662](#)

 \f@encoding, [2990](#)
 \f@series, [2338](#)
 \fakern, [2742](#)
 \fakesc@extrascale, [3279](#), [3294](#)
 \fakescaps, [3254](#)
 \fakesc@score, [3232](#), [3256](#)
 \fakesc@extrascale, [3294](#)
 \file, [1353](#)
 \fooatletter, [246](#)
 \foone, [242](#), [246](#), [970](#), [1185](#),
 [1188](#), [1196](#), [1212](#),
 [1232](#), [1236](#), [1239](#),
 [1388](#), [2679](#), [2852](#),
 [2860](#), [3438](#), [3460](#)
 \forall, [2659](#)
 \FormatHangHeading, [2097](#), [2104](#), [2112](#), [2119](#)
 \FormatRunInHeading, [2126](#), [2131](#)
 \freeze@actives, [2975](#)
 \fullpar, [3714](#)

 \g@emptify, [389](#), [390](#)
 \g@relaxen, [398](#), [399](#)
 \gaddtomacro, [359](#)

\garamath, *p. 38*, [2777](#)
\emptify, [390](#), [390](#)
\let, [351](#), [2015](#)
\glueexpr, [3687](#), [3730](#)
\gluestretch, [3688](#)
\gm@atppron, [1749](#), [1753](#),
 [1754](#), [1755](#), [1756](#),
 [1758](#), [1759](#), [1760](#), [1761](#)
\gm@clearpagesduetoopenright,
 [1795](#), [1858](#)
\gm@dontnumbersectionsoutofmainmatter,
 [1793](#), [1842](#)
\gm@duppa, [2541](#), [2542](#), [2544](#)
\gm@gobmacro, [2440](#), [2446](#)
\gm@hyperrefstepcounter,
 [1785](#), [1788](#), [1871](#)
\gm@ifnac, [931](#), [933](#)
\gm@ifundefined, [408](#),
 [1809](#), [1842](#), [1858](#),
 [1934](#), [1955](#), [2010](#),
 [2023](#), [2093](#), [2220](#),
 [2374](#), [2403](#), [2405](#),
 [2410](#), [2412](#), [2542](#),
 [2686](#), [3278](#), [3301](#)
\gm@letspace, [950](#), [958](#)
\gm@notprerr, [1682](#), [1689](#)
\gm@PronounGender, [1747](#)
\gm@pswords, [1337](#), [1339](#), [1341](#)
\gm@sec, [2213](#), [2224](#), [2225](#)
\gm@secini, [2178](#), [2197](#),
 [2203](#), [2209](#), [2222](#)
\gm@secmarkh, [2205](#)
\gm@secstar, [2181](#), [2191](#),
 [2198](#), [2210](#), [2224](#), [2225](#)
\gm@secx, [2213](#), [2214](#)
\gm@secxx, [2180](#), [2208](#), [2215](#)
\gm@straightensec,
 [2219](#), [2228](#)
\gm@targetheading,
 [1786](#), [1789](#)
\gm@testdefined, [425](#), [443](#)
\gm@testundefined, [440](#),
 [478](#)
\gma, [2770](#)
\gma@arrowdash, [2781](#),
 [2790](#), [2796](#), [2797](#)
\gma@bare, [2766](#), [2768](#)
\gma@bracket, [2768](#), [2769](#)
\gma@checkbracket,
 [2767](#), [2771](#)
\gma@dollar, [2765](#), [2766](#),
 [2771](#)
\gma@gmathhook, [2745](#),
 [2761](#), [2762](#), [2785](#)
\gma@quantifierhook,
 [2659](#), [2662](#), [2757](#),
 [2759](#), [2792](#), [2798](#)
\gma@tempa, [2648](#), [2650](#),
 [2653](#), [2655](#), [2712](#),
 [2716](#), [2737](#), [2740](#)
\gma@tempb, [2713](#), [2716](#)
\gmath, *p. 38*, [2620](#), [2765](#), [2769](#)
\gmathhook, [2762](#)
\gml@storeCS, [1509](#), [1532](#),
 [1569](#)
\gml@storemacros, [1510](#),
 [1521](#), [1530](#), [1535](#), [1572](#)
\gmobyspaces, [2853](#)
\gmshowlists, [820](#)
\GMtextsuperscript, [2597](#)
\gmu@acroinner, [3051](#),
 [3061](#), [3062](#), [3070](#)
\gmu@acrospace, [3045](#),
 [3050](#), [3050](#), [3054](#)
\gmu@checkaftersec,
 [2009](#), [2068](#)
\gmu@dashfalse, [3602](#)
\gmu@dashtrue, [3604](#)
\gmu@datecomma, [3513](#),
 [3531](#), [3559](#), [3579](#),
 [3583](#), [3586](#)
\gmu@datef, [3497](#), [3497](#),
 [3541](#), [3541](#), [3642](#), [3669](#)
\gmu@datesl, [3515](#), [3515](#),
 [3561](#), [3561](#), [3644](#)
\gmu@dekfrac, [2524](#),
 [2543](#), [2547](#)
\gmu@dekfraccsimple,
 [2547](#), [3118](#), [3129](#)
\gmu@denominatorkern,
 [2526](#), [2569](#), [3121](#)
\gmu@discretionaryslash,
 [1348](#), [1359](#)
\gmu@dywiz, [3457](#), [3461](#)
\gmu@fileext, [3171](#), [3181](#),
 [3199](#)
\gmu@filename, [3170](#),
 [3184](#), [3196](#), [3199](#),
 [3202](#), [3211](#)
\gmu@getaddvs, [2060](#),
 [2060](#), [2066](#)
\gmu@gettext, [3169](#), [3179](#)
\gmu@gobdef, [200](#), [206](#)
\gmu@ifnodash, [3596](#), [3601](#)
\gmu@luzniej, [3328](#), [3331](#),
 [3333](#)
\gmu@nl@reserved, [1641](#), [1644](#), [1649](#), [1652](#)
\gmu@nocite@ampulex,
 [1707](#), [1720](#)
\gmu@numeratorkern,
 [2525](#), [2568](#), [2569](#), [3120](#)
\gmu@prevsec, [1990](#), [1992](#),
 [2014](#), [2021](#), [2051](#)
\gmu@printslashes,
 [1353](#), [1355](#), [1355](#),
 [1357](#), [1360](#)
\gmu@resa, [3020](#), [3022](#)
\gmu@reserved, [947](#),
 [949](#), [955](#), [957](#), [1089](#),
 [1091](#), [1522](#), [1525](#),
 [1528](#), [1966](#), [2015](#),
 [2016](#), [2019](#), [2300](#),
 [2302](#), [2304](#), [2305](#),
 [2306](#), [3154](#), [3155](#)
\gmu@reservedb, [1090](#), [1091](#)
\gmu@restorespecials,
 [451](#), [2707](#)
\gmu@RPfor, [3005](#), [3017](#),
 [3029](#), [3040](#)
\gmu@scalar, [3266](#), [3270](#),
 [3271](#), [3277](#)
\gmu@scalematchX, [3256](#),
 [3268](#), [3292](#)
\gmu@scapLetters, [3228](#),
 [3238](#), [3243](#)
\gmu@scapSpaces, [3241](#),
 [3246](#), [3250](#)
\gmu@scapss, [3249](#), [3254](#)
\gmu@scscale, [3285](#), [3291](#)
\gmu@septify, [453](#), [2674](#)
\gmu@setheading, [2065](#),
 [2071](#), [2072](#)
\gmu@setsetSMglobal,
 [1508](#), [1513](#), [1568](#)
\gmu@setSMglobal, [1515](#),
 [1517](#), [1535](#)
\gmu@SMdo@scope, [1611](#),
 [1613](#), [1616](#), [1617](#), [1631](#)
\gmu@SMdo@setscope,
 [1609](#), [1615](#), [1629](#)
\gmu@SMglobalfalse,
 [1476](#), [1490](#), [1517](#),
 [1526](#), [1553](#), [1562](#), [1619](#)
\gmu@SMglobaltrue,
 [1452](#), [1515](#)
\gmu@smtempa, [1480](#), [1489](#),
 [1556](#), [1561](#)
\gmu@storespecials,
 [448](#), [2673](#)
\gmu@stripcomma, [3587](#), [3591](#)

\gmu@tempa, 207, 766, 772,
783, 791, 2445, 2447,
2808, 2811, 2813,
3301, 3303, 3304,
3305, 3597, 3598,
3796, 3800, 3813,
3817, 3873, 3877
\gmu@tempb, 767, 773, 784,
792
\gmu@tempc, 768, 798
\gmu@tempd, 770, 771, 774,
777, 782, 784, 789,
790, 802, 808
\gmu@tempe, 781, 787, 806, 809
\gmu@tempf, 805, 808
\gmu@testdash, 3600, 3640
\gmu@thou@fiver, 3844,
3847, 3855, 3855
\gmu@thou@i, 3849, 3867,
3875
\gmu@thou@ii, 3849, 3867,
3875
\gmu@thou@o, 3849, 3867,
3875
\gmu@thou@put, 3848,
3852, 3864
\gmu@thou@putter, 3851,
3858, 3865, 3872, 3880
\gmu@thousep, 3877, 3884
\gmu@tilde, 2824, 2829, 2840
\gmu@whonly, 3217, 3218
\gmu@xedekfraccplain,
2501, 2550
\gmu@xedekfraccstar,
2501, 2516
\gmu@xefraccdef, 2517,
2531, 2532, 2533,
2534, 2535, 2536,
2537, 2538, 2539
\gn@melet, 1648
\gobble, 190, 192, 2738
\gobbletwo, 193
\grab@default, 576, 579, 592
\grab@ms, 622
\grefstepcounter, 318, 334
\relaxen, 399, 399, 1992
1389
\HeadingNumber, 1868, 1870
\HeadingNumberedfalse,
1794, 1839
\HeadingRHeadText, 1852
\HeadingText, 1854
\HeadingTOCText, 1853

\HeShe, 1758
\heshe, 1753
\hfillneg, 2876
\hrefstepcounter, 333
\hidden@iffalse, 296, 775
\hidden@iftrue, 297, 775
\HimHer, 1760
\himher, 1755
\HisHer, 1759
\hisher, 1754
\HisHers, 1761
\hishers, 1756
\hrule, 2039
\hunskip, 341, 2951, 2953,
2955, 3715, 3728
\hyphenpenalty, 1341,
3369, 3694
\if@afterindent, 1996
\if@files, 2928, 3183,
3195, 3203
\if@gmu@mmhbox, 2545,
2555, 2559, 3125, 3907
\if@mainmatter, 1794
\if@nobreak, 1993
\if@openright, 1796
\If@SomethingTF, 666,
668, 671, 673, 685
\if@specialpage, 1857
\if@twoside, 1883
\IfBooleanF, 712
\IfBooleanT, 708
\IfBooleanTF, 700, 709, 713
\ifcsname, 414, 1061
\ifdate, 3637, 3640, 3649
\ifdefined, 168, 198, 431,
480, 1191, 1250, 2465,
2748, 3030, 3355, 3437
\iffontchar, 2518, 3476
\ifgmu@dash, 3594, 3600,
3606, 3641
\ifgmu@postsec, 2011,
2050, 2058
\ifgmu@SMglobal, 1450,
1474, 1481, 1514,
1551, 1557, 1616
\ifHeadingNumbered,
1838, 1866
\IfNoValueF, 694, 696
\IfNoValueT, 693, 697
\IfNoValueTF, 692, 695
\ifodd, 1751
\ifSecondClass, 3104
\IfSomethingF, 670, 694
\IfSomethingT, 667, 693
\IfSomethingTF, 666, 692
\IfValueF, 697
\IfValueT, 696
\IfValueTF, 695
\ikern, 3142
\IMO, 3080
\in, 2798
\inlasthook, 3200, 3222
\includegraphics, 2595
\infty, 2637
\itemindent, 2254, 2272
itemize*, 2264
\iteracro, 3044, 3048
\justified, 3703
\labelsep, 2256, 2274
\labelwidth, 2255, 2256,
2273, 2274
\larger, *p.* 16, 1170, 2649,
2654, 2718, 2719,
2722, 2723, 2724, 2725
\largerr, *p.* 16, 1174, 2720,
2721
\LaTeXe, 2288, 2337
\LaTeXpar, 2348
\ldate, 3664, 3673
\leftarrow, 2669, 2796
\leftmargin, 2253, 2271
\leftrightarrow, 2671
\leftslanting, 3787
\linebreak, 3753
\linedate, 3647, 3663, 3667
\linedate@, 3647, 3648, 3649
\linedate@@, 3647, 3648
\list, 2252, 2270
\listparindent, 2257, 2275
\lit, 3806
\litshape, 3788, 3804,
3806, 3828
\liturgiques, 3004
\longpauza, 3427, 3428
\looseness, 3334, 3345
\pauza, 3395
\lsl, 3809
luzniej, 3338
luzniej*, 3343
\luzniejcore, 3330, 3338
\macro, 2446
\MakeUppercase, 3232
\mapsto, 2789

\marg, [1410](#), [1434](#)
maszynopis, [3685](#)
\math@arg, [1430](#), [1431](#)
\mathbin, [2638](#), [2642](#),
 [2667](#), [2668](#), [2701](#),
 [2702](#), [2735](#), [2736](#),
 [2791](#), [2798](#)
\mathchoice, [2646](#), [2665](#),
 [2680](#), [2727](#), [2787](#)
\mathclose, [2699](#), [2700](#),
 [2719](#), [2721](#), [2723](#),
 [2725](#), [2733](#)
\mathfrak, [3040](#)
\mathit, [2624](#)
\mathop, [2646](#)
\mathopen, [2685](#), [2700](#),
 [2718](#), [2720](#), [2722](#),
 [2724](#), [2732](#)
\mathord, [2704](#), [2705](#), [2706](#)
\mathpunct, [2684](#)
\mathrel, [2639](#), [2643](#),
 [2669](#), [2670](#), [2671](#),
 [2701](#), [2702](#), [2703](#),
 [2739](#), [2790](#), [2796](#), [2797](#)
\mathrm, [2626](#), [2632](#), [2638](#),
 [2639](#), [2641](#), [2642](#),
 [2643](#), [2657](#)
\Mathstrutbox@, [2697](#)
\medmuskip, [1329](#)
\meta, [1275](#), [1311](#), [1410](#),
 [1417](#), [1424](#)
\meta@font@select,
 [1286](#), [1305](#)
\mkern, [2742](#)
\mskip, [1329](#)
\multiply, [2327](#), [2330](#),
 [3283](#), [3333](#), [3344](#)
\mw@getflags, [2014](#)
\mw@HeadingBreakAfter,
 [1859](#), [1879](#), [1894](#),
 [1898](#), [1929](#), [2015](#)
\mw@HeadingBreakBefore,
 [1856](#), [1928](#), [2016](#)
\mw@HeadingLevel, [1836](#),
 [1839](#)
\mw@HeadingRunIn, [1874](#),
 [1928](#)
\mw@HeadingType, [1855](#),
 [1990](#), [2022](#), [2023](#), [2036](#)
\mw@HeadingWholeWidth,
 [1877](#), [1929](#)
\mw@normalheading,
 [1881](#), [1890](#), [1893](#),
 [1897](#), [2071](#)
\mw@processflags, [1930](#)

\mw@runinheading, [1875](#),
 [2072](#)
\mw@secdef, [1935](#), [1936](#),
 [1937](#), [1943](#)
\mw@section, [1934](#)
\mw@sectionxx, [1835](#)
\mw@secundef, [1939](#), [1951](#),
 [1954](#)
\mw@setflags, [1940](#)
\n@melet, [1640](#), [1965](#), [1967](#),
 [2182](#), [2188](#), [2222](#), [2521](#)
\nameshow, [824](#)
\nameshowthe, [825](#)
napapierki, [3321](#)
\napapierkicore, [3318](#), [3322](#)
\napapierkistretch,
 [3316](#), [3319](#)
\nawj, [3347](#)
\nazwired, [3482](#)
\neg, [2638](#), [2741](#)
\neq, [2639](#), [2736](#)
\neqb, [2736](#)
\newcount, [3328](#)
\newcounter, [1747](#), [1782](#)
\newgif, [260](#)
\newskip, [3760](#)
\newtoks, [481](#), [484](#)
\newwrite, [2928](#)
\next@ddc, [576](#), [579](#), [587](#),
 [591](#), [596](#)
\nfss@text, [1284](#)
\nieczer, [3012](#)
\nobreakspace, [3249](#)
\nocite, [1714](#)
\nohy, [3146](#)
\nolimits, [2661](#), [2662](#)
\nolinkurl, [3922](#)
NoNumSecs, [1782](#)
\not@onlypreamble,
 [1669](#), [1673](#), [1674](#),
 [1675](#), [1676](#), [1677](#)
\NoValue, [558](#), [690](#), [691](#),
 [692](#), [693](#), [694](#)
\NoValueInIt, [691](#)
\nu, [2629](#)
\numexpr, [3467](#), [3468](#), [3863](#)
\oarg, [1415](#)
\oldLaTeX, [2287](#)
\oldLaTeXe, [2288](#)
\omega, [2636](#)
\PackageError, [608](#), [1688](#),
 [3405](#), [3417](#)
\PackageWarning, [1162](#), [1165](#)
\pagebreak, [1882](#), [1894](#), [1898](#)
\pagegoal, [2940](#)
\pagetotal, [2941](#)
\paragraph, [3669](#)
\ParanoidPostsec, [2047](#)
\parg, [1422](#)
\partial, [2640](#)
\partopsep, [2253](#), [2271](#)
\pauza, [3378](#)
\pauza@skipcore, [3356](#),
 [3367](#), [3368](#)
\pauzacore, [3357](#), [3369](#),
 [3374](#), [3382](#), [3391](#),
 [3396](#), [3427](#), [3430](#),
 [3697](#), [3698](#)
\pauzadial, [3384](#), [3390](#)
\pdef, [183](#), [197](#), [260](#), [277](#),
 [296](#), [297](#), [318](#), [333](#),
 [341](#), [894](#), [930](#), [971](#),
 [1135](#), [1174](#), [1175](#),
 [1275](#), [1346](#), [1353](#),
 [1368](#), [1385](#), [1389](#),
 [1452](#), [1463](#), [1506](#),
 [1543](#), [1565](#), [1587](#),
 [1591](#), [1786](#), [2308](#),
 [2493](#), [2540](#), [2551](#),
 [2562](#), [2604](#), [2620](#),
 [2815](#), [2829](#), [2837](#),
 [2951](#), [2953](#), [2955](#),
 [3045](#), [3083](#), [3153](#),
 [3254](#), [3363](#), [3378](#),
 [3390](#), [3395](#), [3404](#),
 [3416](#), [3473](#), [3600](#),
 [3639](#), [3647](#), [3648](#),
 [3649](#), [3663](#), [3664](#),
 [3676](#), [3679](#), [3788](#),
 [3803](#), [3806](#), [3809](#),
 [3825](#), [3834](#), [3840](#),
 [3892](#), [3897](#)
\pdfTeX, [2399](#)
\pdfTeX, [2401](#)
\perhaps@grab@ms, [565](#), [621](#)
\Phi, [2632](#)
\phi, [2631](#)
\pi, [2630](#)
\pk, [1368](#)
\PlainTeX, [2387](#)
\pm, [2641](#), [2642](#)
\polskadata, [3496](#), [3537](#)
\possfil, [1394](#)
\ppauza, [3416](#)
\ppauza@skipcore, [3359](#),
 [3410](#), [3411](#)
\pprovide, [212](#), [3039](#)

\prependtomacro, [374](#)
 \printspaces, [1337](#), [1346](#)
 \protected, [183](#), [212](#), [272](#),
 [291](#), [497](#), [2811](#), [2813](#)
 \provide, [197](#), [212](#)
 \psi, [2635](#)
 \quad, [3482](#)
 \quantifierhook, [2758](#), [2779](#)
 \rdate, [3663](#)
 \real, [3277](#), [3279](#)
 \reflectbox, [2407](#), [2414](#)
 \relaxen, [394](#), [394](#), [1925](#),
 [2623](#), [3447](#), [3849](#)
 \relsize, *p.* [16](#), [1135](#), [1136](#),
 [1170](#), [1171](#), [1172](#),
 [1173](#), [1174](#), [1175](#)
 \renewcommand*, [3029](#)
 \RequirePackage, [2474](#),
 [2925](#), [3022](#), [3261](#)
 \resetMathstrut@, [2690](#)
 \resizebox, [2594](#)
 \resizographics, [2591](#)
 \Restore@Macro, [1546](#),
 [1549](#), [1569](#), [1579](#)
 \Restore@Macros, [1565](#), [1567](#)
 \Restore@MacroSt, [1547](#),
 [1555](#)
 \RestoreEnvironment, [1591](#)
 \RestoreMacro, [1543](#),
 [2481](#), [2483](#)
 \RestoreMacro*, [1593](#), [2483](#)
 \RestoreMacros, [1565](#)
 \RestoringDo, [1628](#)
 \rightarrow, [2670](#), [2797](#)
 \rightline, [3663](#), [3749](#)
 \romannumeral, [2251](#), [2269](#)
 \rotatebox, [2659](#), [2662](#),
 [2667](#), [2668](#)
 \rs@size@warning, [1154](#),
 [1159](#), [1162](#)
 \rs@unknown@warning,
 [1149](#), [1165](#)
 \runindate, [3668](#)
 \scantokens, [2678](#)
 \scshape, [2385](#), [2791](#), [3075](#)
 \secondclass, [3103](#)
 \SecondClasstrue, [3105](#)
 \SetSectionFormatting,
 [1925](#), [1926](#), [2090](#),
 [2094](#), [2102](#), [2110](#),
 [2117](#), [2124](#), [2129](#)
 \SetTwoheadSkip, [2074](#),
 [2101](#), [2109](#), [2116](#)
 \sfname, [1346](#), [1356](#)
 \shortpauza, [3429](#)
 \shortthousep, [3896](#)
 \showboxbreadth, [820](#)
 \showboxdepth, [820](#)
 \ShowFont, [2989](#)
 \showlists, [820](#)
 \showthe, [825](#)
 \sigma, [2633](#)
 \sim, [2643](#)
 \SliTeX, [2384](#)
 \smaller, *p.* [16](#), [1171](#), [3120](#),
 [3124](#)
 \smallerr, *p.* [16](#), [1175](#), [3292](#)
 \smallskipamount, [2870](#),
 [2871](#)
 \smartunder, [1214](#)
 \SMglobal, [1452](#)
 \something@in, [666](#), [667](#),
 [670](#), [675](#)
 \something@tmp, [674](#),
 [675](#), [679](#)
 \something@tmpb, [678](#), [679](#)
 \Store@Macro, [1469](#), [1472](#),
 [1509](#)
 \Store@Macros, [1506](#), [1507](#)
 \Store@MacroSt, [1470](#), [1479](#)
 \Stored@Macro, [1578](#), [1579](#)
 \storedcsname, [1582](#), [3922](#)
 \StoredMacro, [1578](#)
 \StoreEnvironment, [1587](#)
 \StoreMacro, [1463](#), [2341](#),
 [2473](#), [3697](#), [3921](#)
 \StoreMacro*, [1589](#), [2342](#)
 \StoreMacros, [1506](#)
 \StoringAndRelaxingDo,
 [1608](#)
 \strip@pt, [3792](#), [3797](#), [3814](#)
 \subs, [1186](#), [1216](#)
 \sum, [2658](#)
 \TB, [2393](#)
 \TeXbook, [2392](#), [2393](#)
 \textbullet, [3473](#), [3477](#)
 \textcolor, [3012](#)
 \textlarger, [1172](#)
 \textlit, [3803](#)
 \textsl, [2392](#)
 \textsmaller, [1173](#)
 \textstyle, [2339](#)
 \textsuperscript, [2599](#),
 [2604](#)
 \texttilde, [2837](#)
 \textwidth, [3731](#), [3732](#),
 [3750](#), [3751](#)
 \thedate, [3673](#)
 \thickmuskip, [2743](#)
 \thous, [3897](#)
 \thous@inner, [3899](#), [3902](#)
 \thousep, [3840](#), [3892](#)
 \thr@@, [2247](#), [2265](#)
 \time, [3467](#), [3468](#)
 \tinycae, [3259](#)
 \TODO, [2888](#)
 \toks, [2061](#), [2062](#), [2068](#), [2069](#)
 \tolerance, [3333](#), [3344](#), [3689](#)
 \truetextsuperscript,
 [2601](#), [2603](#)
 \twocoltoc, [2924](#), [2933](#)
 \twopar, [3727](#)
 \twoparinit, [3725](#)
 \tytul, [3679](#)
 \tytulowa, [3479](#)
 \udigits, [2493](#), [2496](#)
 \undeksmallskip, [2871](#)
 \unexpanded, [179](#), [376](#),
 [791](#), [792](#), [796](#), [797](#),
 [800](#), [1966](#)
 \unless, [443](#), [480](#), [2466](#), [3030](#)
 \upshape, [3829](#)
 \Url, [2748](#), [2749](#)
 \url, [3921](#), [3922](#)
 \urladdstar, [3918](#), [3925](#)
 \usc, [3083](#), [3085](#)
 \uscacro, [3085](#)
 \usecounter, [2258](#)
 \value, [1751](#)
 \varepsilon, [2339](#), [2396](#),
 [2627](#)
 \varnothing, [2792](#)
 \varsigma, [2634](#)
 \vartheta, [2628](#)
 \vee, [2667](#), [2741](#)
 \verb, [2473](#), [2481](#)
 \visiblespace, [1251](#),
 [1253](#), [1331](#)
 \Vs, [2811](#)
 \vs, [1331](#), [1337](#), [1341](#)
 \wd, [2319](#), [2322](#), [2352](#), [2357](#),
 [2365](#), [2366](#), [2661](#),
 [2782](#), [2783](#), [2794](#), [2795](#)
 \Web, [2389](#)

\wedge, 2668, 2741
\whenonly, 3216
\whern, 3756
\wherncore, 3748, 3757, 3763
\whernskip, 3757, 3760, 3761
\whernup, 3763
\WPheadings, 2089
\Ws, 2813
\wyzejnizej, 3300
\Wz, 2815

\xathousep, 3892, 3906
\Xedekfracc, 2501
\XeLaTeX, 2411

\XeTeX, 2404
\XeTeXinputencoding, 169
\XeTeXthree, 2470
\XeTeXversion, 158, 159,
168, 1191, 2465, 2466,
3355, 3437
\xiinand, 1237
\xiibackslash, 1224, 1228
\xiilbrace, 1199
\xiipercent, 1233
\xiirbrace, 1200
\xiispace, 837, 838, 1240,
1253
\xiistring, 836

\xiiunder, 1189, 1192, 1193
\xparsed@args, 484, 508, 515
\xxt@visiblespace,
1250, 1251
\yeshy, 3147

\z@skip, 3716
\zf@scale, 3267, 3270, 3271
\zwrobcy, 3676

\cdot, 2955
\-, 3404, 3443
\-, 3363, 3424, 3442