

The HEP-PAPER package*
 Publications in high energy physics
 Jan Hajer†

Centre for Cosmology, Particle Physics and Phenomenology,
 Université catholique de Louvain, Louvain-la-Neuve B-1348, Belgium

2020/10/01

Abstract

The HEP-PAPER package aims to provide a single style file containing most configurations and macros necessary to write appealing publications in High Energy Physics. Instead of reinventing the wheel by introducing newly created macros HEP-PAPER preferably loads third party packages as long as they are lightweight enough.

Contents

1	Introduction	3
1.1	Options	3
1.1.1	Deactivation	3
1.1.2	Compatibility	4
1.1.3	Reactivation	4
2	Macros and environments	4
2.1	Title page	4
2.2	Text	5
2.2.1	References and footnotes	6
2.2.2	Acronyms	6
2.3	Math	6
2.3.1	Physics	8
2.4	FLOATS	8
2.5	Bibliography	9
3	Conclusion	10

*This document corresponds to HEP-PAPER v1.5.

†jan.hajer@uclouvain.be

A Allocation of math alphabets	11
B Options	12
B.1 Deactivation	13
B.2 Compatibility	13
B.3 Reactivation	14
B.4 Process options	14
B.5 Set compatibility	14
C Text	15
C.1 Font size	17
C.2 Text macros	18
C.3 Lists	18
D Geometry	19
E Math	20
E.1 Math fonts	21
E.2 Physics notation	23
F Floats	24
F.1 Sub-floats	25
F.2 Tables	26
F.3 Figures	27
G Title page	27
G.1 Titles	27
G.2 Authors	28
G.3 Preprint	29
G.4 Abstract	29
H Bibliography	30
H.1 Sourcemap	30
H.2 Eprints	33
I Hyperlinks, Footnotes and References	34
I.1 Footnotes	35
I.2 References	35
I.3 Citations	36
J Acronyms	37
K Biblatex datamodel file	42

1 Introduction

For usual publications it is enough to load additionally to the `article` class without optional arguments only the `HEP-PAPER` package [1].

```
\documentclass{article}  
\usepackage{hep-paper}
```

The most notable changes after loading the `HEP-PAPER` package is the change of some `LATEX` defaults. The paper and font sizes are set to A4 and 11 pt, respectively. Additionally, the paper geometry is adjusted using the `GEOMETRY` package [2]. Furthermore, the font is changed to latin modern (LM) using the `LMODERN` package [3] with `MICRO-TYPE` [4] optimizations. Finally, portable document format (PDF) hyperlinks are implemented with the `HYPERREF` package [5].

1.1 Options

- `paper` The `paper=⟨format⟩` option loads the specified paper format. The possible `⟨formats⟩` are: `a0`, `a1`, `a2`, `a3`, `a4`, `a5`, `a6`, `b0`, `b1`, `b2`, `b3`, `b4`, `b5`, `b6`, `c0`, `c1`, `c2`, `c3`, `c4`, `c5`, `c6`, `ansia`, `ansib`, `ansic`, `ansid`, `ansie`, `letter`, `executive`, `legal`. The default is `a4`.
- `font` The `font=⟨size⟩` option loads the specified font size. The possible `⟨sizes⟩` are: `8pt`, `9pt`, `10pt`, `11pt`, `12pt`, `14pt`, `17pt`, `20pt`. The default is 11 pt.
- `lang` The `lang=⟨name⟩` option switches the document language to one of the values values provided by the `BABEL` package [6]. The default is `british`.
- `sansserif` The `sansserif` option switches the document including math to sans serif font shape.
- `parskip` The `parskip` option changes how paragraphs are separated from each other using the `PARSKIP` package [7]. The `LATEX` default is separation via indentation the `parskip` option switches to separation via vertical space.¹
- `symbols` The `symbols=⟨family⟩` set the family of the symbol fonts. `symbols=ams` loads two `AMS` fonts [8] and the `BM` bold fonts. The default setting replaces additionally the blackboard font with the `DSFONT` [9]. `symbols=minion` switches the symbol fonts to the Adobe MinionPro companion font from the `MNSYMBOL` package [10]. `symbols=false` deactivates additional symbol fonts.

1.1.1 Deactivation

The `HEP-PAPER` package loads few bigger packages which have a large impact on the document. The deactivation options prevent such adjustments.

- `defaults` The `defaults` option prevents the adjustment of the page geometry and the font size set by the document class.
- `title` The `title=false` option deactivates the title page adjustments.

¹ Although the `parskip` option is used for this document, it is recommended only for very few document types such as technical manuals or answers to referees.

- bibliography** The `bibliography=<key>` option prevents the automatic loading of the `BIBLATEX` package [11] if `<key>=false`. Otherwise the `<key>` is passed as `style` string to the `BIBLATEX` package.
- glossaries** The `glossaries=false` option deactivates acronyms and the use of the `GLOSSARIES` package [12].
- references** The `references=false` option prevents the `CLEVEREF` package [13] from being loaded and deactivates further redefinitions of reference macros.

1.1.2 Compatibility

The compatibility options activate the compatibility mode for certain classes and packages used for publications in high energy physics. They are mostly suitable combinations of options described in the previous section. If `HEP-PAPER` is able to detect the presence of such a class or package, *i.e.* if it is loaded before the `HEP-PAPER` package, the compatibility mode is activated automatically.

- beamer** The `beamer` option activates the `BEAMER` [14] compatibility mode.
- jhep** The `jhep` option activates the `JHEP` [15] compatibility mode.
- jcap** The `jcap` option activates the `JCAP` [16] compatibility mode.
- revtex** The `revtex` option activates the `REVTEX` [17] compatibility mode.
- pos** The `pos` option activates the PoS compatibility mode.

1.1.3 Reactivation

The `HEP-PAPER` package deactivates unrecommended macros, which can be reactivated manually.

- manualplacement** The `manualplacement` option reactivates manual float placement.
- eqnarray** The `eqnarray` option reactivates the depreciated `eqnarray` environment.

2 Macros and environments

2.1 Title page

- \title** The PDF meta information is set according to the `\title{<text>}` and `\author{<text>}` information.
- \subtitle** The `\subtitle{<subtitle>}` macro is defined using the `TITLING` package [18].
- \author** In order to facilitate multiple authors with different affiliations the `AUTHBLK` package [19] is loaded. The following lines add *e.g.* two authors with different affiliations
- \affiliation**
- \email** `\author[1]{Author one \email{email one}}`
`\affiliation[1]{Affiliation one}`
`\author[2]{Author two \email{email two}}`

	\affiliation[1,2]{Affiliation two}	
\preprint	The \preprint{<numer>} macro places a pre-print number in the upper right corner of the title page.	
\abstract	The abstract environment is adjusted to not start with an indentation.	
\titlefont \subtitlefont	Various title font macros are defined, allowing to change the appearance of the \maketitle output.	
\authorfont	2.2 Text	
\affiliationfont	Hyphenation is provided by the BABEL package [6] and quotation commands are provided by the csquotes package [20] recommended by the BABEL package. The latter package provides the convenient macros \enquote{<text>} and \MakeOuterQuote{"} allowing to leave the choice of quotation marks to LATEX and use " instead of the pair “ and ”, respectively.	
\eg	The FOREIGN package [21] defines macros such as \eg, \ie, \cf, and \vs which are typeset as <i>e.g.</i> , <i>i.e.</i> , <i>cf.</i> , and <i>vs</i> .	
\vs		
\no	The \no{<number>} macro is typeset as № 123.	
\software	The \software[<version>]{<name>} macro is typeset as HEP-PAPER v1.5.	
\online	The \online{<url>}{<text>} macro combines the features of the \href{<url>}{<text>} [5] and the \url{<text>} [22] macros, resulting in <i>e.g.</i> ctan.org/pkg/hep-paper.	
inlinelist enumdescript	The inlinelist and enumdescript environments are defined using the ENUMITEM package [23]. The three main points are \begin{inlinelist} \item one \item two \item three \end{inlinelist} \begin{enumdescript}[label=\Roman*] \item{First} one \item{Second} two \item{Third} three \end{enumdescript}	The three main points are i) one, ii) two, and iii) three. I) First one II) Second two III) Third three
\textsc	A bold versions SMALL CAPS and a sans serif version of SMALL CAPS based on the computer modern (CM) font is provided, the latter using the SANSMATHFONTS package [24].	
\underline \overline	The \underline macro is redefined to allow line-breaks using the ULEM package [25]. The \overline macro is extended to also overline text outside of math environments.	
\useparskip \useparindent	If the parskip option is activated the \useparindent macro switches back the usual parindent mode, while the \useparskip macro switches to the parskip mode.	

2.2.1 References and footnotes

- \cref References are extended with the CLEVEREF package [13], which allows to *e.g.* just type \cref{\{key\}} in order to write ‘figure 1’. Furthermore, the CLEVEREF package allows to reference multiple objects within one \cref{\{key1,key2\}}.
- \cite Citations are adjusted to not start on a new line in order to avoid the repeated use of ~\cite{\{key\}}.
- \ref References are also adjusted to not start on a new line.

\eqref Footnotes are adjusted to swallow white space before the footnote mark and at the beginning of the footnote text.

\footnote

2.2.2 Acronyms

\acronym The \acronym{\{*\}}[\{typeset abbreviation\}]{\{abbreviation\}}{\{definition\}}{\{plural definition\}} macro generates the singular \{abbreviation\} and plural \{abbreviation\}S macros. The first star prevents the addition of an ‘s’ to the abbreviation plural. The second star restores the T_EX default of swallowing subsequent white space. The long form is only shown at the first appearance of these macros, later appearances generate the abbreviation with a hyperlink to the long form. Capitalization at the beginning of paragraphs and sentences is ensured. The \shortacronym and \longacronym macros are drop-in replacements of the \acronym macro showing only the short or

\resetacronym long form of their acronym. The first use form of the acronym can be enforced by resetting the acronym counter with \resetacronym{\{key\}}. If the acronym counter equals one at the end of the document the short form of the acronym is not introduced. Placing a \dummyacronym{\{key\}} at the end of the document ensures that the short form is introduced.

2.3 Math

The MATHTOOLS [26] and AMSSYMB [8] packages are loaded. They in turn load the *A^MS-L^AT_EX* AMSMATH [27] and AMSFONTS [8] packages. Bold math, via \mathbf is improved by the BM package [28], *i.e.* ($A\Gamma\delta A\boldsymbol{b}\Gamma\delta$). Macros switching to bfseries such as \section{\{text\}} are ensured to also typeset math in bold. This may cause trouble if bold symbols carry an additional non-implicit meaning. The \text{\{text\}} macro makes it possible to write text within math mode, *i.e.* ($A\Gamma\delta\mathbf{A}b\Gamma\delta$). This behaviour conflicts *e.g.* with the SANSERIF package option. The math sans serif alphabet is redefined to be italic sans serif if the main text is serif and italic serif if the main text is sans serif, *i.e.* ($A\Gamma\delta\mathbf{A}b\Gamma\delta$). The \mathcal font *i.e.* (\mathcal{ABC}) is accompanied by the \mathscr font *i.e.* (\mathscr{ABC}). The \mathbb font is improved by the DOUBLESTROKE package [9] and adjusted depending on the sansserif option *i.e.* ($\mathbb{A}\mathbb{b}\mathbb{1}$). Finally, the \mathfrak font is also available *i.e.* ($\mathfrak{A}\mathfrak{a}\mathfrak{B}\mathfrak{b}\mathfrak{1}$). Details about the font handling in T_EX can be found in reference [29].

\nicefrac The \frac{\{number\}}{\{number\}} macro is accompanied by \nicefrac{\{number\}}{\{number\}} and \flatfrac{\{number\}}{\{number\}} leading to $\frac{1}{2}$, $\frac{1}{2}$, and $\frac{1}{2}$. Diagonal

\diag

\sgn

matrix \diag and signum \sgn operators are defined.

\mathdef The `\mathdef{<name>}[<arguments>]{<code>}` macro (re-)defines macros only within math mode without changing the text mode definition.

- \i The imaginary unit i and the differential d are defined using this functionality.
 - \d For longer paper it can be useful to re-number the equation in accordance with the section numbering `\numberwithin{equation}{section}`. In order to further reduce the size of the equation counter it can be useful to wrap `align` environments with multiple rows in a `subequations` environment. Both macros are provided by the `amsmath` package.

eqnarray The depreciated `eqnarray` environment is undefined as long this behaviour is not prevented by the `eqnarray` package option. The `split`, `multiline`, `align`, `multlined`, `aligned`, `alignedat`, and `cases` environments of the `AMSMATH` and `MATHTOOLS` packages should be used instead.

equation Use the `equation` environment for short equations.

```
\begin{equation}
  \text{left} = \boxed{\text{right}} \; .
\end{equation}
```

multiline Use the `multiline` environment for longer equations.

```
\begin{multiline}
  left = right 1 \\
  + right 2 \ .
\end{multiline}
```

$\boxed{\text{left}} =$	$\boxed{\text{right 1}}$	
		$\boxed{\text{+ right 2}} \quad . \quad (2)$

split Use the **split** sub environment for equations in which multiple equal signs should be aligned.

$$\begin{aligned} \left. \begin{array}{l} \text{\backslash begin\{equation\}} \\ \text{\backslash begin\{split\}} \\ \quad \text{left} \&= \text{right 1} \\ \quad \&= \text{right 2} \\ \text{\end\{split\}} \end{array} \right. &= \boxed{\text{right 1}} \\ &= \boxed{\text{right 2}} \end{aligned} \quad (3)$$

align Use the `align` environment for the vertical alignment and horizontal distribution of multiple equations.

```
\begin{subequations} \begin{align}
\text{left} &= \text{right} \ , \ & \boxed{\text{left}} &= \boxed{\text{right}} \ , \ \boxed{\text{left}} &= \boxed{\text{right}} \ , \ (4a) \\
\text{left} &= \text{right} \ , \ \\
\text{left} &= \text{right} \ , \ & \boxed{\text{left}} &= \boxed{\text{right}} \ , \ \boxed{\text{left}} &= \boxed{\text{right}} \ . \ (4b) \\
\text{left} &= \text{right} \ .
\end{align} \end{subequations}
```

aligned Use the `aligned` environment within a `equation` environment if the aligned equations should be labeled with a single equation number.

multlined Use the `multlined` environment if either `split` or `align` contain very long lines.

```
\begin{equation} \begin{split} left &= right 1 \\ &\quad \begin{aligned} &\begin{multlined}[t] right 2 \\ + right 3 \end{multlined} \\ &\end{aligned} \end{split} \end{equation}
```

$$\boxed{\text{left}} = \boxed{\text{right 1}} \\ = \boxed{\text{right 2}} \quad (5) \\ \boxed{\text{+ right 3}} .$$

alignat Use the `alignat` environment together with the `\mathllap` macro for the alignment of multiple equations with vastly different lengths.

```
\begin{subequations} \begin{alignat}{2} left &= long right && \\ le. 2 &= ri. 2 & , & \\ \mathllap{le. 3 = ri. 3} & & . \end{alignat} \end{subequations}
```

$$\boxed{\text{left}} = \boxed{\text{long right}} , \quad (6a)$$

$$\boxed{\text{le. 2}} = \boxed{\text{ri. 2}} , \quad \boxed{\text{le. 3}} = \boxed{\text{ri. 3}} . \quad (6b)$$

`\end{alignat}`
`\end{subequations}`

As a rule of thumb if you have to use `\notag`, `\nonumber`, or perform manual spacing via `\quad` you are probably using the wrong environment.

2.3.1 Physics

Greek letters are adjusted to always be italic and upright in math and text mode, respectively, using the `FIXMATH` [30] and `ALPHABETA` [31] packages. This allows differentiations like

$$\sigma = 5 \text{ fb} , \quad \text{at } 5\sigma \text{ C.L.} , \quad \mu = 5 \text{ cm} , \quad l = 5 \mu\text{m} , \quad (7)$$

and *e.g.* to distinguish gauge ν and mass ν eigenstates in models with massive neutrinos. Additionally, Greek letters can also be directly typed using Unicode.

\ev The `PHYSICS` package [32] provides additional macros such as

$$\begin{array}{lll} \backslash \text{pdv} & \langle \phi \rangle , & \frac{\partial^n f}{\partial x^n} , \\ \backslash \text{comm} & [A, B] , & \mathcal{O}(x^2) , \quad x \Big|_0^\infty , \quad \det(M) . \end{array} \quad (8)$$

\order
\cancel
\slashed The `\cancel{<characters>}` macro from the `CANCEL` package [33] and the `\slashed{<character>}` macro from the `SLASHED` package [34] allow to `\cancel` math and use the Dirac slash notation *i.e.* $\not{}$, respectively.

\overleftright A better looking over left right arrow is defined *i.e.* $\overleftrightarrow{\partial}$.

\unit The correct spacing for units, *cf.* equation (7), is provided by the macro `\unit[<value>]{<unit>}` from the `UNITS` package [35] which can also be used in text mode. The macro `\inv[<power>]{<text>}` allows to avoid math mode also for inverse units such as 5 fb^{-1} typeset via `\unit[5]{\inv{fb}}`.

2.4 Floats

figure Automatic float placement is adjusted to place a single float at the top of pages and
table

```
\begin{panels}{.6}
  code
\panel{.4}
  \begin{tabular}... \end{tabular}
\end{panels}
```

(a) Code for this panel environment.

one	two
a	b
b	c

(b) The `booktabs` and `multirow` features.

Table 1: Example use of the `panels` environment in Panel (a) and the features from the `BOOKTABS` and `MULTIROW` packages in Panel (b).

to reduce the number of float pages, using the L^AT_EX macros.

\setcounter{bottomnumber}{0}	no floats at the bottom of a page (default 1)
\setcounter{topnumber}{1}	a single float at the top of a page (default 2)
\setcounter{dbltopnumber}{1}	same for full widths floats in two-column mode
\renewcommand{\textfraction}{.1}	large floats are allowed (default 0.2)
\renewcommand{\topfraction}{.9}	(default 0.7)
\renewcommand{\dbltopfraction}{.9}	(default 0.7)
\renewcommand{\floatpagefraction}{.8}	float pages must be full (default 0.5)

Additionally, manual float placement is deactivated but can be reactivated using the `manualplacement` package option. It is however recommended to archive the desired design by adjusting above macros. The most useful float placement is usually

`\raggedright` archived by placing the float *in front* of the paragraph it is referenced in first. The float environments have been adjusted to center their content. The usual behaviour can be reactivated using `\raggedright`.

`panels` The `panels` environment makes use of the `SUBCAPTION` package [36]. It provides sub-floats and takes as mandatory argument either the number of sub-floats (default 2) or the width of the first sub-float as fraction of the `\ linewidth`. Within the `\begin{panels}{<vertical alignment>}{}{width}` environment the `\panel` macro initiates a new sub-float. In the case that the width of the first sub-float has been given as an optional argument to the `panels` environment the `\panel{width}` macro takes the width of the next sub-float as mandatory argument. The example code is presented in table 1a.

`tabular` The `BOOKTABS` [37] and `MULTIROW` [38] packages are loaded enabling publication quality tabulars such as in table 1b.

`\graphic` The `GRAPHICX` package [39] is loaded and the `\graphic[width]{figure}` macro is defined, which is a wrapper for the `\includegraphics{figure}` macro and takes the figure width as fraction of the `\ linewidth` as optional argument (default 1). If the graphics are located in a sub-folder its path can be indicated by `\graphics{subfolder}`.

2.5 Bibliography

`\bibliography` The `BIBLATEX` package [11] is loaded for bibliography management. The user has `\printbibliography`

to add the line `\bibliography{\langle my.bib \rangle}` to the preamble of the document and `\printbibliography` at the end of the document. The bibliography is generated by BIBER [40]. `biblatex` is extended to be able to cope with the `collaboration` and `reportNumber` fields provided by `inspirehep.net` and a bug in the volume number is fixed. Additionally, the PubMed IDs are recognized and `ctan.org`, `github.com`, `gitlab.com`, `bitbucket.org`, `launchpad.net`, `sourceforge.net`, and `hepforge.org` are valid eprinttypes. Errata can be included using the `related` feature.

```
\article{key1,
  ...,
  relatedtype="erratum",
  related="key2",
}
\article{key2,
  ...,
}
```

3 Conclusion

The `HEP-PAPER` package provides a matching selection of preloaded packages and additional macros enabling the user to focus on the content instead of the layout by reducing the amount of manual tasks. The majority of the loaded packages are fairly lightweight, the others can be deactivated with package options.

`arxiv-collector` `arxiv.org` [41] requires the setup dependent `bbl` files instead of the original `bib` files, which causes trouble if the local L^AT_EX version differs from the one used by arXiv. The `ARXIV-COLLECTOR` python script [42] alleviates this problem by collecting all files necessary for publication on arXiv (including figures).

A Allocation of math alphabets

Of the 16 available math alphabets, T_EX loads four alphabets by default

0. **OT1** Text (latin, greek, numerals, text symbols)
1. **OML** Math Italic (latin, greek, numerals, text symbols)
2. **OMS** Symbol (`\mathcal`, operators)
3. **OMX** Math Extension (big operators, delimiters)

The text font 0. of CM is **cmr10** \OT1/cmr/m/n/10 , which is replaced by LM to be **rm-lmr10** \OT1/lmr/m/n/10 , the **sansserif** option uses **rm-lmss10** \OT1/lmss/m/n/10 . The italic math font 1. of CM is **cmmi10** \OML/cmm/m/it/10 , and is replaced by LM to be **lmmi10** \OML/lmm/m/it/10 , the **sansserif** options uses **cmbright10** $\text{\OML/cmbrm/m/it/10}$ from the **CMBRIGHT** package [43]. The symbol font 2. of CM is **cmsy10** \OMS/cmsy/m/n/10 , and is replaced by LM to be **lmsy10** \OMS/lmsy/m/n/10 , the **sansserif** options uses **cmsssy10** $\text{\OMS/cmsssy/m/n/10}$ from the **SANSMATHFONTS** package [24]. The extension font 3. of CM is **cmex10** \OMX/cmex/m/n/5 , and is replaced by the **EXSCALE** package [44] to be **cmex10** \OMX/cmex/m/n/10 , the **sansserif** option loads **cmssex10** $\text{\OMX/cmssex/m/n/10}$. The **AMSSYMB** (**AMSFONTS**) packages [45] load two more symbol fonts

4. **msam10** \U/msa/m/n/10 AMS symbol font A (special math operators)
5. **msbm10** \U/msb/m/n/10 AMS symbol font B (`\mathbb`, negated operators)

The **sansserif** option replaces them with **ssmsam10** \U/ssmsa/m/n/10 and **ssmsbm10** \U/ssmsb/m/n/10 from the **SANSMATHFONTS** package [24], respectively. The **BM** package [28] loads the bold version for the fonts 0. to 2..

Other math alphabets are only loaded on demand, *e.g.* `\mathsf` uses a sans serif font and `\mathbf` without **BM** uses a bold font. The `\mathscr` macro uses the script font from the **MATHRSFS** package [46]

9. **rsfs10** \U/rsfs/m/n/10 Math script font (capital letters)

The `\mathbb` macro loads the double stroke font from the **DSFONT** package [9], this can be prevented with the **symbols=ams** option.

10. **dsrom10** \U/dsrom/m/n/10 Double stroke font

The `\mathfrak` macro loads the fractur font from the **AMSSYMB** package [45]

11. **eufm10** \U/euf/m/n/10 Math fraktur (Basic Latin)

The **HEP-PAPER** package uses nine of the available 16 math alphabets. This number can be reduced by three using `\newcommand{\bmmax}{0}` from the **BM** package [28].

The **symbols=minion** options replaces the fonts 2. to 5. with corresponding fonts from the **MNSYMBOL** package [10]. Additionally, two more symbol alphabets are

allocated, the `bm` package [28] loads one more font and now `\mathcal` triggers the use of one additional alphabet. Hence, the `minion` option uses three to four more math alphabets than a usual setup.

B Options

Load the `pdftexcmds` [47] and `kvoptions` [48] packages and define a `hep` namespace.

```
1 \RequirePackage{pdftexcmds}
2 \RequirePackage{kvoptions}
3 \SetupKeyvalOptions{
4   family=hep,
5   prefix=hep@
6 }
```

`paper` Define a `paper=<size>` option. Make A4 paper the default.

```
7 \DeclareStringOption[a4]{paper}
```

`font` Define a `font=<size>` option. Make 11pt the default font size.

```
8 \DeclareStringOption[11pt]{font}
```

`lang` Define the `lang` option, which takes the values provided by the `babel` package [6]. Make `british` the default language.

```
9 \DeclareStringOption[british]{lang}
```

`sansserif` Define the option pair `serif` and `sansserif` controlling the font shape of the whole document.

```
10 \DeclareBoolOption[true]{serif}
11 \DeclareComplementaryOption{sansserif}{serif}
```

`parskip` Define the option pair `parindent` and `parskip` controlling the separation of paragraphs.

```
12 \DeclareBoolOption[true]{parindent}
13 \DeclareComplementaryOption{parskip}{parindent}
```

`symbols` Provide the option `symbols` allowing to switch the symbol font.

```
14 \DeclareStringOption[true]{symbols}
```

B.1 Deactivation

defaults Define the `defaults` option which deactivates the `paper` and `font` options and prevents the change of the class defaults by this package.

```
15 \DeclareBoolOption[false]{defaults}
```

title Provide the option `title` for deactivating redefinition of title macros.

```
16 \DeclareBoolOption[true]{title}
```

bibliography Provide the option `bibliography` for passing a `style` string to the `BIBLATEX` package [11] or disabling the automatic loading of `biblatex`.

```
17 \DeclareStringOption[numeric-comp]{bibliography}
```

glossaries Provide the option `glossaries` able to turn off the use of the `GLOSSARIES` package [12].

```
18 \DeclareBoolOption[true]{glossaries}
```

references Provide the option `references` for preventing the `CLEVEREF` package from being loaded redefinitions of reference macros.

```
19 \DeclareBoolOption[true]{references}
```

B.2 Compatibility

beamer Provide the option `beamer` for `BEAMER` [14] compatibility mode.

```
20 \DeclareBoolOption[false]{beamer}
```

revtex Provide the option `revtex` for `REVTEX` [17] compatibility mode.

```
21 \DeclareBoolOption[false]{revtex}
```

jhep Provide the option `jhep` for `JHEP` [15] compatibility mode.

```
22 \DeclareBoolOption[false]{jhep}
```

jcap Provide the option `jcap` for `JCAP` [16] compatibility mode.

```
23 \DeclareBoolOption[false]{jcap}
```

pos Provide the option `pos` for PoS compatibility mode.

```
24 \DeclareBoolOption[false]{pos}
```

B.3 Reactivation

`eqnarray` Provide the option `eqnarray` for reactivating the `eqnarray` environment.

```
25 \DeclareBoolOption[false]{eqnarray}
```

`manualplacement` Provide the `manualplacement` option for reactivating the manual placement of floats.

```
26 \DeclareBoolOption[false]{manualplacement}
```

B.4 Process options

```
27 \ProcessKeyvalOptions*
```

Read the class options regarding font and paper size.

```
28 \def\hep@get@class{\relax{\def\hep@class{\#1}}}
29 \def\hep@getclass{\expandafter\hep@get@class\@filelist\relax}
30 \hep@getclass
31 @ifclasswith{\hep@class}{10pt}{\setkeys{hep}{font=10pt}}{}
32 @ifclasswith{\hep@class}{12pt}{\setkeys{hep}{font=12pt}}{}
33 @ifclasswith{\hep@class}{a5paper}{\setkeys{hep}{paper=a5}}{}
34 @ifclasswith{\hep@class}{b5paper}{\setkeys{hep}{paper=b5}}{}
35 @ifclasswith{\hep@class}{letterpaper}{\setkeys{hep}{paper=letter}}{}
36 @ifclasswith{\hep@class}{legalpaper}{\setkeys{hep}{paper=legal}}{}
37 @ifclasswith{\hep@class}{executivepaper}{%
38   \setkeys{hep}{paper=executive}%
39 }{}}
```

B.5 Set compatibility

Set the `pos` compatibility options.

```
40 @ifclassloaded{PoS}{\setkeys{hep}{pos}}{}
41 \ifhep@pos
42   \setkeys{hep}{defaults, title=false}
43   \ DeclareRobustCommand\boldmath{\@nomath\boldmath\mathversion{bold}}
44 \fi
```

Set the `beamer` compatibility options.

```
45 @ifclassloaded{beamer}{\setkeys{hep}{beamer}}{}
46 \ifhep@beamer
47   \setkeys{hep}{defaults, title=false, references=false, sansserif}
48   \ Ifpackageloaded{beamerbasefont}{\usefonttheme{professionalfonts}}{}
49 \fi
```

Set the `revtex` compatibility options.

```
50 @ifclassloaded{revtex4}{\setkeys{hep}{revtex}}{}
51 @ifclassloaded{revtex4-1}{\setkeys{hep}{revtex}}{}
52 @ifclassloaded{revtex4-2}{\setkeys{hep}{revtex}}{}}
```

```

53 \ifhep@revtex
54   \setkeys{hep}{defaults, title=false, bibliography=false, lang=american}
55 \fi

```

Define the SISSA conditional.

```

56 \@ifpackageloaded{jheppub}{\setkeys{hep}{jhep}{}{}}
57 \@ifpackageloaded{jcappub}{\setkeys{hep}{jcap}{}{}}
58 \newif\ifhep@sissa
59 \ifhep@jhep\hep@sissatru
60 \else
61   \ifhep@jcap\hep@sissatru
62   \else\hep@sissafalse
63 \fi
64 \fi

```

Set the SISSA compatibility options.

```

65 \ifhep@sissa
66   \setkeys{hep}{title=false, bibliography=false}
67   \PassOptionsToPackage{
68     colorlinks=true, linktocpage=true, pdfproducer=medialab, pdfa=true,
69     urlcolor=blue, anchorcolor=blue, citecolor=blue, filecolor=blue,
70     linkcolor=blue, menucolor=blue, pagecolor=blue
71   }{hyperref}
72   \PassOptionsToPackage{reset}{geometry}
73 \fi

```

Set the JHEP compatibility options.

```

74 \ifhep@jhep
75   \voffset 0in
76   \hoffset 0in
77 \fi

```

C Text

Set the whole text to sans serif if requested.

```

78 \ifhep@serif\else
79   \renewcommand{\familydefault}{\sfdefault}
80 \fi

```

`\ifxetexorluatex` Load the IFLUATEX [49] and IFXETEX [50] packages. Define the `\ifxetexorluatex` conditional checking if the package is executed by Lua^ATEX or X_ETEX.

```

81 \RequirePackage{ifluatex}
82 \RequirePackage{ifxetex}
83 \newif\ifxetexorluatex
84 \ifxetex\xetexorluatexttrue

```

```

85 \else
86   \ifluatex\xetexorluatexttrue
87   \else\xetexorluatextfalse
88   \fi
89 \fi

```

Pick the correct font encoding depending on the engine used and load the `FONTENC` package [51] with this encoding. For details of the font encoding see [52].

```

90 \ifxetexorluatex
91   \def\hep@encoding{TU}
92 \else
93   \def\hep@encoding{T1}
94 \fi
95 \RequirePackage[\hep@encoding]{fontenc}

```

Fix the remaining CM fonts [53], load the `LMODERN` font [3], the `textcomp` extension [54], and the `MICROTYPE` font optimization [4].

```

96 \RequirePackage{fix-cm}
97 \RequirePackage{lmodern}
98 \renewcommand{\ttdefault}{lmvtt}
99 \RequirePackage{textcomp}
100 \RequirePackage{microtype}

```

Define bold and sans serif small caps font shapes using the `FONTSPEC` package [55]. The font abbreviations are

lmr LM regular font
lmss LM sans serif font
cmss CM sans serif font
xcmss Extended CM sans serif font (from the `SANSMATHFONTS` package [24])
bx Bold extended series
b Bold series
m Medium weight and width series
c Medium weight, condensed width series
sc Caps and small caps font shape

```

101 \ifxetexorluatex
102   \RequirePackage{fontspec}
103   \setmainfont{Latin Modern Roman}[
104     UprightFeatures={SmallCapsFont={[lmromancaps10-regular.otf]}},
105     BoldFeatures={
106       SmallCapsFeatures={Letters=SmallCaps},
107       SmallCapsFont={[cmunbx.otf]}
108     }
109   ]
110   \DeclareFontShape{\hep@encoding}{lmss}{bx}{sc}{<->cmssbxsc10}{}
111   \DeclareFontShape{\hep@encoding}{lmss}{b}{sc}{<->cmssbxsc10}{}
112   \DeclareFontShape{\hep@encoding}{lmss}{m}{sc}{%

```

```

113      <-9>cmsscsc8<9-10>cmsscsc9<10->cmsscsc10%
114  }{}
115 \else
116   \rmfamily
117   \DeclareFontShape{\hep@encoding}{lmr}{b}{sc}{<->ssub*cmr/bx/sc}{}
118   \DeclareFontShape{\hep@encoding}{lmr}{bx}{sc}{<->ssub*cmr/bx/sc}{}
119   \sffamily
120   \DeclareFontShape{\hep@encoding}{lmss}{bx}{sc}{<->ssub*xcmss/bx/sc}{}
121   \DeclareFontShape{\hep@encoding}{lmss}{b}{sc}{<->ssub*xcmss/bx/sc}{}
122   \DeclareFontShape{\hep@encoding}{lmss}{m}{sc}{<->ssub*xcmss/m/sc}{}
123 \fi

```

Load the `INPUTENC` package [56].

```

124 \ifxetexorluatex\else
125   \RequirePackage[utf8]{inputenc}
126 \fi

```

Load the `BABEL` package [6] for hyphenation and the recommended `csquotes` package [20].

```

127 \RequirePackage[\hep@lang]{babel}
128 \RequirePackage{csquotes}

```

`\underline` Load the `ULEM` package [25] for hyphenable underlined text.

```

129 \RequirePackage[normalem]{ulem}
130 \let\underline\uline

```

C.1 Font size

Undefine previously defined font sizes and load the `LATEX` font size file corresponding to the font size option.

```

131 \ifhep@defaults\else
132   \def\hep@remove@pt#1pt{#1}
133   \edef\hep@pt@size{\expandafter\hep@remove@pt\hep@font}
134   \let\small\relax
135   \let\footnotesize\relax
136   \let\scriptsize\relax
137   \let\tiny\relax
138   \let\large\relax
139   \let\Large\relax
140   \let\LARGE\relax
141   \let\huge\relax
142   \let\Huge\relax
143   \input{size\hep@pt@size.clo}
144 \fi

```

C.2 Text macros

- \vs Load the FOREIGN package [21] in order to highlight abbreviations and vocabularies from foreign languages. Add the missing \vs command.

```
145 \ifnum\pdfstrcmp{\hep@lang}{american}=0
146   \newcommand{\hep@lang@foreign}{USenglish}
147 \else
148   \ifnum\pdfstrcmp{\hep@lang}{USenglish}=0
149     \newcommand{\hep@lang@foreign}{USenglish}
150   \else
151     \newcommand{\hep@lang@foreign}{british}
152   \fi
153 \fi
154 \RequirePackage[all, \hep@lang@foreign]{foreign}
155 \DeclareRobustCommand\vs{\xperiodafter{{\foreignabbrfont{vs}}}}
```

The FOREIGN package relies on the XSPACE package [57]. Ensure that \xspace is compatible with the \enquote macro from the CSQUOTE package.

```
156 \xspaceaddexceptions{\csq@qclose@i}
```

- \no Define the macro \no{\langle number\rangle} for the use of № with appropriate spacing.

```
157 \newcommand{\no}[1]{\textnumero~#1}
```

- \software Define a macro for software with optional version information \software[\langle version\rangle]{\langle name\rangle}, using the RELSIZE package [58].

```
158 \RequirePackage{relsize}
159 \newcommand{\software}[2][\hspace{-\fontdimen2\font}]{%
160   \smaller\textsc{#2}~#1}%
161 }
```

- \online Define the \online{\langle text\rangle}{\langle url\rangle} macro combining the features of the \href and the \email macros. Define a macro for typesetting emails.

```
162 \newcommand{\online}[2]{\href{#1}{\nolinkurl{#2}}}
163 \newcommand{\email}[1]{\online{mailto:#1}{#1}}
```

- \prefix Define the \prefix{\langle prefix\rangle}{\langle word\rangle} macro ensuring the correct linebreak in (prefix-) word.

```
164 \newcommand{\prefix}[2]{(#1\mbox{-})\allowbreak #2}
```

C.3 Lists

Load the ENUMITEM package [23].

```
165 \RequirePackage[inline]{enumitem}
```

`inlinelist` Define an inline list environment.

```
166 \newlist{inlinelist}{enumerate*}{1}
167 \setlist*[inlinelist,1]{%
168   label=\roman*), itemjoin={,\ }, itemjoin*= {, and\ }, after=.%}
169 }
```

`enumdescript` Define an enumdescript list environment.

```
170 \newlist{enum@descript}{enumerate}{2}
171 \setlist[enum@descript]{label=\arabic*.}
172 \newenvironment{enumdescript}[1][]{%
173   \begin{enum@descript}[\#1]
174     \let\hep@item\item
175     \renewcommand{\item}[2][]{%
176       \ifx&#1&\hep@item\else\hep@item[\#1]\fi
177       \textbf{\#2}\ifx##2\empty\else~\fi\ifnextchar\par@gobble\relax
178     }
179 }{\end{enum@descript}}
```

D Geometry

Load the `GEOMETRY` package [2] and adjust the text width and height. This step must happen after readjusting the font size in appendix C.1.

```
180 \ifhep@defaults\else
181   \RequirePackage{geometry}
182   \geometry{%
183     \hep@paper paper,
184     hscale=.75,
185     vscale=.8,
186     vmarginratio=3:4,
187     includeheadfoot
188   }
189 \fi
```

`\useparskip` Load the `PARSKIP` package [7] if requested and provide two commands switching
`\useparindent` between the two paragraph modes.

```
190 \ifhep@parindent\else
191 \RequirePackage{parskip}
192 \newcommand{\useparskip}{%
193   \setlength{\parskip}{.5\baselineskip plus 2pt}%
194   \setlength{\parindent}{0pt}%
195 }
196 \newcommand{\useparindent}{%
197   \setlength{\parskip}{0pt}%
198   \setlength{\parindent}{15pt}%
199   \if@twocolumn\setlength{\parindent}{1em}%
200   \else\setlength{\parindent}{1.5em}%
201 }
```

```

201   \fi
202 }
203 \fi

```

E Math

Load the `MATHTOOLS` package [26] which loads the `AMSMATH` package [27]. Allow page breaks within equations if necessary.

```

204 \RequirePackage{mathtools}
205 \allowdisplaybreaks[1]

```

`\diag` Provide the `\diag` and `\sgn` operators
`\sgn`

```

206 \DeclareMathOperator{\diag}{diag}
207 \DeclareMathOperator{\sgn}{sgn}

```

`\mathdef` Define the `\mathdef{<name>}[<arguments>]{<macro>}` macro which (re-)defines macros in math mode only. This macro is implemented using the `XPARSE` package [59].

```

208 \RequirePackage{xparse}
209 \DeclareDocumentCommand{\mathdef}{m0{0}m}{%
210   \expandafter\let\csname text\string#1\endcsname=#1
211   \expandafter\newcommand\csname math\string#1\endcsname[#2]{#3}
212   \ DeclareRobustCommand#1{%
213     \ifmmode
214       \expandafter\let\expandafter\next\csname math\string#1\endcsname
215     \else
216       \expandafter\let\expandafter\next\csname text\string#1\endcsname
217     \fi
218     \next
219   }%
220 }

```

`\i` Provide an upright imaginary unit in math mode.

```

221 \AtBeginDocument{\mathdef{\i}{\operatorname{i}}}

```

`\overline` Redefine `\overline` to be a text macro using the `ULEM` package [25]. Extend it as a math macro with the original definition from the `AMSMATH` package [27].

```

222 \def\overline#1{{\renewcommand{\ULdepth}{-1.9ex}{}\uline{#1}}}
223 \DeclareRobustCommand{\over@line}[1]{\overline{#1}}
224 \mathdef{\overline}{\over@line}

```

`\left` Load the `MLEFTRIGHT` package [60] and adjust the spacing around `\left` and `\right`.

`\right`

```

225 \RequirePackage{mleftright}
226 \mleftright

```

`\eqnarray` Undefine the `\eqnarray` environment if not prevented by package option.

```
227 \ifhep@eqnarray\else  
228   \let\eqnarray\@undefined  
229   \let\endeqnarray\@undefined  
230 \fi
```

E.1 Math fonts

Define conditionals based on the `symbols` package option.

```
231 \newif\ifhep@symbols  
232 \ifnum\pdf@strcmp{\hep@symbols}{false}=0\else\hep@symbolstrue\fi  
233 \newif\ifhep@ams  
234 \ifnum\pdf@strcmp{\hep@symbols}{ams}=0 \hep@amstrue\fi  
235 \newif\ifhep@minion  
236 \ifnum\pdf@strcmp{\hep@symbols}{minion}=0 \hep@miniontrue\fi
```

Load the `FIXMATH` [30] and `ALPHABETA` [31] packages ensuring that upper Greek letters in math mode are italic and providing upright Greek letters in text mode, respectively.

```
237 \ifhep@symbols  
238   \RequirePackage{alphabeta}  
239   \RequirePackage{fixmath}
```

Either load the `MNSYMBOL` package [10] or the the `EXSCALE` package in order to fix Latin Modern `lmex` fonts. Additionally, load the `AMSSYMB` package [8] which provides further math symbols and also loads the `AMSFONTS` package [8].

```
240 \ifhep@minion  
241   \RequirePackage{MnSymbol}  
242 \else  
243   \RequirePackage{exscale}  
244   \RequirePackage{amssymb}  
245 \fi  
246 \fi
```

`\mathsf` If the `sansserif` package option is active use the `CMBRIGHT` font [43] and code adjusted from the `SANSMATHFONTS` package [24]. Ensure that `\mathsf` is italic as well as sans serif and sans for sans and sans serif documents, respectively.

```
247 \ifhep@serif  
248   \newcommand\hep@font@sf{cmbrm}  
249   \DeclareMathAlphabet{\mathsf}{OML}{\hep@font@sf}{m}{it}  
250   \SetMathAlphabet{\mathsf}{bold}{OML}{\hep@font@sf}{b}{it}  
251 \else  
252   \newcommand\hep@font@sf{lmr}  
253   \newcommand\hep@font@text{lmss}  
254   \newcommand\hep@font@math{cmbrm}  
255   \newcommand\hep@font@symbol{cmsssy}
```

```

256 \newcommand\hep@font@extra{cmssex}
257 \newcommand\hep@font@amsa{ssmsa}
258 \newcommand\hep@font@amsb{ssmsb}
```

Declare font substitutions.

```

259 \DeclareFontSubstitution{OML}{\hep@font@math}{m}{it}
260 \ifhep@symbols\ifhep@minion\else
261   \DeclareFontSubstitution{OMS}{\hep@font@symbol}{m}{n}
262   \DeclareFontSubstitution{OMX}{\hep@font@extra}{m}{n}
263 \fi\fi
```

Declare the symbol fonts.

```

264 \DeclareSymbolFont{operators}{OT1}{\hep@font@text}{m}{n}
265 \DeclareSymbolFont{letters}{OML}{\hep@font@math}{m}{it}
266 \ifhep@symbols\ifhep@minion\else
267   \DeclareSymbolFont{symbols}{OMS}{\hep@font@symbol}{m}{n}
268   \DeclareSymbolFont{largesymbols}{OMX}{\hep@font@extra}{m}{n}
269 \fi\fi
```

Set bold symbol fonts.

```

270 \SetSymbolFont{operators}{bold}{OT1}{\hep@font@text}{b}{n}
271 \SetSymbolFont{letters}{bold}{OML}{\hep@font@math}{b}{it}
272 \ifhep@symbols\ifhep@minion\else
273   \SetSymbolFont{symbols}{bold}{OMS}{\hep@font@symbol}{b}{n}
274 \fi\fi
```

Adjust the fonts loaded by the `AMSFONTS` [8] and `ESINT` [61] packages.

```

275 \ifhep@symbols\ifhep@minion\else
276   \DeclareSymbolFont{AMSA}{U}{\hep@font@amsa}{m}{n}
277   \DeclareSymbolFont{AMSb}{U}{\hep@font@amsb}{m}{n}
278 \fi\fi
279 \AtBeginDocument{%
280   \@ifpackageloaded{esint}{%
281     \DeclareSymbolFont{largetsymbolsa}{U}{ssesint}{m}{n}
282   }{}}
283 }
```

Declare the symbol font alphabets.

```

284 \DeclareSymbolFontAlphabet{\mathrm}{operators}
285 \DeclareSymbolFontAlphabet{\mathnormal}{letters}
286 \ifhep@minion\else
287   \DeclareSymbolFontAlphabet{\mathcal}{symbols}
288 \fi
```

Declare `\mathit`.

```

289 \DeclareMathAlphabet{\mathit}{OML}{\hep@font@text}{m}{it}
290 \SetMathAlphabet{\mathit}{bold}{OML}{\hep@font@text}{bx}{it}
```

Declare `\mathtt`.

```
291 \DeclareMathAlphabet{\mathtt}{OT1}{cmtl}{m}{n}
```

Declare `\mathsf`.

```
292 \DeclareMathAlphabet{\mathsf}{OML}{\hep@font@sf}{m}{it}
293 \SetMathAlphabet{\mathsf}{bold}{OML}{\hep@font@sf}{bx}{it}
```

End of `sansserif`.

```
294 \fi
```

`\mathbf` Load the `bm` package [28] for superior boldmath. Make math symbols bold whenever they appear in bold macros such as `\section{<text>}`.

```
295 \ifhep@symbols
296   \RequirePackage{bm}
297   \AtBeginDocument{\let\mathbf\bm}
298   \g@addto@macro\bfseries{\boldmath}
```

`\mathscr` Provid the `\mathscr` math script font from the `MATHRSFS` package [46].

```
299 \DeclareMathAlphabet{\mathscr}{U}{rsfs}{m}{n}
```

`\mathbb` Redefine the the `\mathbb` math blackboard style font according to the (sans-)serif option with the font from the `DSFONT` package [9].

```
300 \ifhep@minion
301   \DeclareMathAlphabet{\mathbb}{U}{%
302     \ifhep@serif dsrom\else dsss\fi%
303   }{m}{n}
304 \else
305   \ifhep@ams\else
306     \SetMathAlphabet{\mathbb}{normal}{U}{%
307       \ifhep@serif dsrom\else dsss\fi%
308     }{m}{n}
309   \fi
310 \fi
311 \fi
```

E.2 Physics notation

`\cancel` Load the `PHYSICS` package [32] which provides macros useful for publications in physics. Additionally, load the `CANCEL` [33] and `SLASHED` [34] packages which provide the `\unit` `\cancel` and `\slashed` macros. Finally, load the `UNITS` package [35] which provides the `\units` and `\nicefrac` macros.

```
312 \RequirePackage{physics}
```

```

313 \RequirePackage{cancel}
314 \RequirePackage{slashed}
315 \RequirePackage{units}
```

\inv Provide a macro for the inverse, useful in combination with the unit macro in text mode.

```
316 \newcommand{\inv}[2][1]{#2\ensuremath{^{\sim}{-}{#1}}}
```

\d Provide a differential \d.

```
317 \AtBeginDocument{\mathdef{\d}{\mathrm{d}}}
```

\oset Define a new overset macro \oset[*offset*]{*over*}{*base*}.

```

318 \newcommand{\oset}[3][-1pt]{%
319   \raisebox{1pt}{\ensuremath{\mathop{\#3}\limits^{\sim}}\vbox to#1{\kern-2\ex@\hbox{$\scriptscriptstyle\#2$}\vss}}%
320   }%
321 }%
322 }
```

\overleftright Define a over left right arrow \overleftright{*base*}.

```
323 \newcommand{\overleftright}[1]{\oset{\leftrightarrow}{#1}}
```

F Floats

Adjust the L^AT_EX float placement defaults

```

324 \setcounter{bottomnumber}{0} % 1
325 \setcounter{topnumber}{1} % 2
326 \setcounter{dbltopnumber}{1} % 2
327 \renewcommand{\topfraction}{.9} % .7
328 \renewcommand{\dbltopfraction}{.9} % .7
329 \renewcommand{\textfraction}{.1} % .2
330 \renewcommand{\floatpagefraction}{.8} % .5
```

figure Center the content of figure and table environments. Ignore the manual placement
table if the `manualplacement` option is set to false.

```

331 \let\@figure@\figure%
332 \let\end@\figure@\endfigure%
333 \let\@table@\table%
334 \let\end@\table@\endtable%
335 \ifhep@manualplacement%
336   \renewenvironment{figure}[1][tbp]{%
337     \@figure@[#1]\centering%
338   }{\end@\figure@}%
339 \renewenvironment{table}[1][tbp]{%
```

```

340     \@table@[#1]\centering%
341   }{\@end@table@}%
342 \else%
343   \renewenvironment{figure}[1][]{%
344     \@figure@\centering%
345   }{\@end@figure@}%
346   \renewenvironment{table}[1][]{%
347     \@table@\centering%
348   }{\@end@table@}
349 \fi%

```

F.1 Sub-floats

\ifhep@journal Define a new journal conditional.

```

350 \newif\ifhep@journal
351 \ifhep@sissa\hep@journaltrue
352 \else
353   \ifhep@revtex\hep@journaltrue
354   \else
355     \ifhep@pos\hep@journaltrue
356     \else\hep@journalfalse
357   \fi
358 \fi
359 \fi

```

Prevent the CAPTION package [62] from complaining about the journal classes and packages.

```

360 \ifhep@journal
361   \setlength\abovecaptionskip{\f@size\p@}
362   \setlength\belowcaptionskip{0\p@}
363   \long\def\@makecaption#1#2{%
364     \vskip\abovecaptionskip
365     \sbox\@tempboxa{#1: #2}%
366     \ifdim \wd\@tempboxa >\hsize
367       #1: #2\par
368     \else
369       \global \minipagetrue
370       \hb@xt@{\hsize}{\hfil\box\@tempboxa\hfil}%
371     \fi
372     \vskip\belowcaptionskip%
373   }
374 \fi

```

Load the SUBCAPTION package [36]. Provide the old \subcaption@minipage macro.

```

375 \RequirePackage[subrefformat=parens]{subcaption}
376 \captionsetup{font=small}
377 \captionsetup[sub]{font=small}
378 \providecommand*\subcaption@minipage[2]{%

```

```

379  \minipage{#1}{#2}\setcaptionsubtype\relax%
380 }

panels Define the panels environment and the \panel macro.
\panel
381 \newenvironment{panels}[2][b]{%
    Define an internal macro for global behaviour.

    382 \newcommand{\begin@subcaption@minipage}[2][b]{%
        383   \caption@withoptargs{\subcaption@minipage[##1]{##2}}%
        384   \centering\vskip 0pt%
        385 }
    Define the \panel macro for the case that the number of panels is given.

    386 \ifdim#2pt>1pt%
    387   \newcommand{\panel}[1][b]{%
        388     \endminipage\hfill\begin@subcaption@minipage[#1]{\linewidth/#2}%
        389   }%
    390   \begin@subcaption@minipage[#1]{\linewidth/#2}%
    Define the \panel macro for the case that the width of the panel is given.

    391 \else%
    392   \newcommand{\panel}[2][b]{%
        393     \endminipage\hfill\begin@subcaption@minipage[#1]{##2\linewidth}%
        394   }%
    395   \begin@subcaption@minipage[#1]{##2\linewidth}%
    396 \fi%
397 }{\endminipage}

Reajust the captions to the revtex class using the RAGGED2E package [63].
```

```

398 \ifhep@revtex
399   \RequirePackage{ragged2e}
400   \DeclareCaptionFormat{revtex}{#1#2\justifying{#3}}
401   \captionsetup{font=small, format=revtex}
402   \captionsetup[sub]{font=footnotesize, format=plain}
403   \renewcommand{\figurename}{Figure}
404   \renewcommand{\tablename}{Table}
405 \fi
```

F.2 Tables

tabular Enhance tabulars with the BOOKTABS and MULTIROW packages [37, 38].

```

406 \RequirePackage{booktabs}
407 \RequirePackage{multirow}
```

F.3 Figures

\graphic Provide the \graphic macro for the inclusion of figures using the GRAPHICX package [39].

```
408 \RequirePackage{graphicx}
409 \providecommand{\tikzsetnextfilename}[1]{}
410 \newcommand{\graphic}[2][1]{\tikzsetnextfilename{\#2}{%
411   \centering\includegraphics[width=\#1\linewidth]{\#2}\par%
412 }}
```

\graphics Provide the \graphics macro for the inclusion of figures located in a subfolder.

```
413 \newcommand{\graphics}[1]{\graphicspath{./#1}}
```

G Title page

Begin of title conditional.

```
414 \ifhep@title
```

\date Allow absent date field.

```
415 \date{}
```

G.1 Titles

Extend the title using the TITLING package [18].

```
416 \RequirePackage{titling}
```

\preprintfont Allow to change the fontface of the individual parts of the title.

```
\titlefont
417 \let\hep@preprint@font\relax
\subtitlefont
418 \newcommand{\preprintfont}[1]{\def\hep@preprint@font{\#1}}
\authorfont
419 \let\hep@title@font\relax
\affiliationfont
420 \newcommand{\titlefont}[1]{\def\hep@title@font{\#1}}
\datefont
421 \let\hep@subtitle@font\relax
422 \newcommand{\subtitlefont}[1]{\def\hep@subtitle@font{\#1}}
423 \let\hep@author@font\relax
424 \newcommand{\authorfont}[1]{\def\hep@author@font{\#1}}
425 \let\hep@affiliation@font\relax
426 \newcommand{\affiliationfont}[1]{\def\hep@affiliation@font{\#1}}
427 \let\hep@date@font\relax
428 \newcommand{\datefont}[1]{\def\hep@date@font{\#1}}
```

\subtitle Define a subtitle.

```
429 \newcommand{\presubtitle}[1]{\def\hep@pre@sub@title{\#1}}
430 \newcommand{\subtitle}[1]{\def\sub@title{\#1}}
```

```

431 \newcommand{\postsubtitle}[1]{\def\hep@post@sub@title{#1}}
432 \renewcommand{\maketitlehookb}{%
433   \@ifundefined{sub@title}{}{%
434     \hep@pre@sub@title\sub@title\hep@post@sub@title%
435   }%
436 }

```

Set standard values mostly taken from the TITLING package, add the font hook, and reduce the date font size.

```

437 \pretitle{\begin{center}\LARGE\hep@title@font}
438 \posttitle{\par\end{center}}
439 \presubtitle{\begin{center}\large\hep@subtitle@font}
440 \postsubtitle{\par\end{center}}
441 \preauthor{%
442   \begin{center}\large\hep@author@font\lineskip.5em\begin{tabular}[t]{c}%
443   \end{tabular}%
444 \postauthor{\end{tabular}\par\end{center}}
445 \predate{\begin{center}\hep@date@font}
446 \postdate{\par\end{center}}

```

G.2 Authors

\author Allow absent author field. Enable the handling of multiple authors with different affiliations using the AUTHBLK package [19].

```

447 \author{}
448 \RequirePackage{authblk}
449 \renewcommand{\Affilfont}{\small\hep@affiliation@font}
450 \renewcommand\Authfont{\hep@author@font}

```

\email Redefine the email macro to place the email address in a footnote if called from within the \author macro \author{*name*} \email{*email*}.

```

451 \let\hep@author\author
452 \def\author{%
453   \renewcommand{\email}[1]{\unskip\thanks{\online{mailto:##1##1}}\%%
454   \hep@author
455 }

```

\affiliation Define the \affiliation macro, ensure that linebreaks happen after a comma.

```

456 \newcommand\hep@active@comma{,\penalty-5\relax}
457 \newcommand\hep@cat@comma@active{\catcode`\,\active}
458 {\hep@cat@comma@active\gdef,{\hep@active@comma}}
459 \newcommand\hep@affil[1]{%
460   \endgroup\@flushglue=0pt plus .5\linewidth\affil{#1}%
461 }
462 \def\hep@affil@opt[#1]#2{%
463   \endgroup\@flushglue=0pt plus .5\linewidth\affil[#1]{#2}%

```

```

464 }
465 \DeclareRobustCommand{\hep@affiliation}{%
466   \@ifnextchar[{\hep@affil@opt}{\hep@affil}}%
467 }
468 \newcommand{\affiliation}{%
469   \begingroup\hep@cat@comma@active\hep@affiliation%
470 }

```

G.3 Preprint

\preprint Define the \preprint macro using the `varwidth` package [64].

```

471 \let\hep@preprint\relax
472 \newcommand{\preprint}[1]{\def\hep@preprint{#1}}
473 \RequirePackage{varwidth}
474 \newcommand{\hep@preprint@box}{%
475   \begin{varwidth}{\textwidth}%
476     \small\hep@preprint@font\hep@preprint%
477   \end{varwidth}%
478 }
479 \preprintfont{\sc}

```

\placepreprint Places a preprint number in the top right corner of the title page using the `atbegshi` [65] and `picture` [66] packages.

```

480 \RequirePackage{atbegshi}
481 \RequirePackage{picture}
482 \newcommand{\placepreprint}{%
483   \AtBeginShipoutFirst{%
484     \put(
485       \textwidth+\oddsidemargin-\widthof{\hep@preprint@box},
486       -2pt-\topmargin-\heightof{\hep@preprint@box}
487     ){\normalfont\hep@preprint@box}
488   }
489 }
490 \renewcommand{\maketitlehooka}{\placepreprint\vspace{-\bigskipamount}}

```

G.4 Abstract

\abstract Adjust the abstract environment to not start with indentation.

```

491 \@ifundefined{abstract}{}{%
492   \let\hep@abstract\abstract%
493   \renewcommand{\abstract}{\hep@abstract\noindent\ignorespaces}%
494 }

```

End of title conditional.

```
495 \fi
```

H Bibliography

Check if bibliography management is requested.

```
496 \ifnum\pdf@strcmp{\hep@bibliography}{false}=0\else
```

\bibliography Load the BIBLATEX package [11] with the datamodel defined in appendix K.

```
497 \RequirePackage[style=\hep@bibliography, datamodel=hep-paper]{biblatex}
```

hep-paper Provide the \DeclareSortingTemplate macro for older biblatex installations. Define a new sorting template that sorts only multi key \cite entries according to their date and leaves the rest of the bibliography entries in the order they appear in the text.

```
498 \providetcommand{\DeclareSortingTemplate}{\DeclareSortingScheme}
499 \DeclareSortingTemplate{hep-paper}{
500   \sort{\citeorder}
501   \sort[final]{\field{sortkey}}
502   \sort{\field{sortyear} \field{year} \literal{9999}}
503   \sort{\field{month}}
504   \sort{\field{eprint} \field{doi}}
505   \sort{\field{sorttitle} \field{title}}
506   \sort{\field{subtitle} \field{volume}}
507 }
```

Use the new sorting scheme and abbreviat all first names.

```
508 \ExecuteBibliographyOptions{
509   sorting=hep-paper,
510   giveninits=true
511 }
```

erratum Add new bibliography string ‘Erratum’ for the use in the relatedtype field.

```
512 \NewBibliographyString{erratum,erratums}
513 \DefineBibliographyStrings{english}{erratum={Erratum},erratums={Errata}}
514 \providetcommand{\relateddelimerratum}{\addsemicolon\space}
```

\printbibliography Allow the bibliography to be printed sloppy

```
515 \let\hep@printbibliography\printbibliography
516 \renewcommand{\printbibliography}{\sloppy\hep@printbibliography}
```

H.1 Sourcemap

\reg@exp@one Define regular expressions in order to deal with inconsistent journal title and volume naming as well as uniform resource locator (URL) protocols and the PMCID.
\reg@exp@two
\reg@exp@url
\reg@exp@pmc

```
517 \newcommand{\reg@exp@one}{\regexp{\A(\p{L}+)?\d+(\p{L}+)?\Z}}
518 \newcommand{\reg@exp@two}{\regexp{\A(\p{L}+)?(\d+(\p{L}+)?\Z)}
```

```
519 \newcommand{\reg@exp@url}{\regexp{\A(ht|f)tp(s)?:\//}}
520 \newcommand{\reg@exp@pmc}{\regexp{\A(PMC)?}}
```

\DeclareSourcemap Use the \DeclareSourcemap feature.

```
521 \DeclareSourcemap{%
522   \maps[datatype=bibtex, overwrite=true]{%
```

collaboration Read the collaboration information if present.

```
523   \map{%
524     \step[fieldsource=Collaboration, final=true]{}
525     \step[fieldset=collaboration, origfieldval, final=true]
526   }%
```

reportnumber Read the pre-print information if present.

```
527   \map{%
528     \step[fieldsource=reportNumber, final=true]{}
529     \step[fieldset=reportnumber, origfieldval, final=true]
530   }%
```

journal Move letters from the volume field to the journal field.

```
531   \map[overwrite]{
532     \step[fieldsource=volume, match=\reg@exp@one, final]
533     \step[fieldsource=volume, match=\reg@exp@two, replace={$2}]
534     \step[fieldsource=journal, fieldtarget=journalttitle]
535     \step[fieldset=journalttitle, fieldvalue={\space$1$2}, append=true]
536   }
```

url Remove the protocol from URL.

```
537   \map{
538     \step[fieldsource=url, final=true]
539     \step[fieldset=protocollessurl, origfieldval, final=true]
540     \step[fieldsource=protocollessurl, match=\reg@exp@url, replace={}]
541   }
```

pmc Remove the PMC from the PMCID.

```
542   \map{
543     \step[fieldsource=pmcid, final=true]
544     \step[fieldset=pmc, origfieldval, final=true]
545     \step[fieldsource=pmc, match=\reg@exp@pmc, replace={}]
546   }
547 }%
548 }
```

```

\letbibmacro Provide the \letbibmacro macro for old biblatex installations.

549 \providecommand{\letbibmacro}[2]{\csletcs{abx@macro@#1}{abx@macro@#2}}


collaboration Execute the author macro even if only the collaboration information is present and
override the author information with collaboration information if present.

550 \renewbibmacro*{author/translator+others}{%
551   \ifboolexpr{%
552     test \ifuseauthor and (%
553       not test {\ifnameundef{author}} or%
554       not test {\iffieldundef{collaboration}}%
555     )%
556   }{%
557     {\usebibmacro{author}}%
558     {\usebibmacro{translator+others}}%
559   }%
560 \letbibmacro{hep@bib@author}{author}%
561 \renewbibmacro*{author}{%
562   \iffieldundef{collaboration}{%
563     {\usebibmacro{hep@bib@author}}{\textit{\printfield{collaboration}}}%
564   }%
565 }

```

In: Remove spurious ‘In:’ if no journal is present.

```

566 \renewbibmacro*{in:}{%
567   \iffieldundef{journaltitle}{}{\printtext{\bibstring{in}}\intitlepunct}}%
568 }

```

url Show URLs without the protocol.

```

569 \DeclareFieldFormat{url}{%
570   \mkbibacro{URL}\addcolon\space\online{\#1}\thefield{protocollessurl}}%
571 }

```

\bib@online Private \bib@online macro

```

572 \newcommand{\bib@online}[2]{%
573   \ifhyperref{\online{\#1}{\#2}}{\nolinkurl{\#2}}%
574 }

```

pmid Present PubMed IDs.

pmcid

```

575 \DeclareFieldFormat{pmid}{%
576   \mkbibacro{PM}\addcolon\space%
577   \bib@online{\url{https://www.ncbi.nlm.nih.gov/pubmed/#1}{\#1}}%
578 }%
579 \DeclareFieldFormat{pmc}{%
580   \mkbibacro{PMC}\addcolon\space%

```

```

581 \bib@online{https://www.ncbi.nlm.nih.gov/pmc/articles/PMC#1}{#1}%
582 }

pmcid Add the pre-print and PubMed information if present.

pmid
reportnumber 583 \letbibmacro{hep-doi+eprint+url}{doi+eprint+url}
584 \renewbibmacro*{doi+eprint+url}{%
585   \usebibmacro{hep-doi+eprint+url}%
586   \iffieldundef{pmc}{%
587     \iffieldundef{pmid}{\printfield{pmid}\newunit}{%
588       \printfield{pmc}\newunit}%
589     \iffieldundef{reportnumber}{\newunit}{%
590       \newunitpunct\textnumero\intitlepunct}%
591       \textsc{\small\printfield{reportnumber}}\newunit}%
592     \newunit}%
593 }%
594 }

```

H.2 Eprints

\new@eprint Private \new@eprint macro

```

595 \NewDocumentCommand{\new@eprint}{smm}{%
596   \DeclareFieldFormat{eprint}{#2}{%
597     \newcommand{\@path}{\IfBooleanT{#1}{\thefield{eprintclass}/}##1}%
598     #2\addcolon\space\bib@online{#3/\@path}{\@path}%
599   }%
600 }

```

CTAN Add CTAN as a eprint option

```

601 \new@eprint{CTAN}{https://ctan.org/pkg}%
602 \DeclareFieldAlias{eprint:ctan}{eprint:CTAN}

```

GitHub Add GitHub as a eprint option

```

603 \new@eprint*{GitHub}{https://github.com}%
604 \DeclareFieldAlias{eprint:github}{eprint:GitHub}

```

GitLab Add GitLab as a eprint option

```

605 \new@eprint*{GitLab}{https://gitlab.com}%
606 \DeclareFieldAlias{eprint:gitlab}{eprint:GitLab}

```

Bitbucket Add Bitbucket as a eprint option

```

607 \new@eprint*{Bitbucket}{https://bitbucket.org}%
608 \DeclareFieldAlias{eprint:bitbucket}{eprint:Bitbucket}

```

Launchpad Add Launchpad as a eprint option

```
609 \new@eprint{Launchpad}{https://launchpad.net}
610 \DeclareFieldAlias{eprint:launchpad}{eprint:Launchpad}
```

SourceForge Add SourceForge as a eprint option

```
611 \new@eprint{SourceForge}{https://sourceforge.net/projects}
612 \DeclareFieldAlias{eprint:launchpad}{eprint:SourceForge}
```

HEPForge Add HEPForge as a eprint option

```
613 \DeclareFieldFormat{eprint:hepforge}%
614   HEPForge\addcolon\space\bib@online{https://#1/hepforge.org}{#1}%
615 }
616 \DeclareFieldAlias{eprint:HEPForge}{eprint:hepforge}
```

End check for bibliography option.

```
617 \fi
```

I Hyperlinks, Footnotes and References

Load the HYPERREF package [5] enable Unicode encoding and hide links.

```
618 \RequirePackage{hyperref}
619 \hypersetup{
620   pdfencoding=auto, psdextra,
621   hidelinks, linktoc=all, breaklinks=true,
622   pdfcreator={}, pdfproducer={}
623 }
```

Set the PDF meta data according to the paper information and ensure that unnecessary information is suppressed.

```
624 \pdfstringdefDisableCommands{\def\varepsilon{\text{\varepsilon}}}
625 \AtBeginDocument{
626   \pdfstringdefDisableCommands{\let\ensuremath\@gobble}
627   \pdfstringdefDisableCommands{\let\mathsurround\@gobble}
628   \pdfstringdefDisableCommands{\let\unskip\@gobble}
629   \pdfstringdefDisableCommands{\let\thanks\@gobble}
630   \pdfstringdefDisableCommands{\let\footnote\@gobble}
631   \pdfstringdefDisableCommands{\let\\@\gobble}
632 }
633 \ifhep@revtex
634   \AtBeginShipout{\hypersetup{pdftitle={\@title}}}
635 \else
636   \ifhep@beamer\else
637     \AtBeginDocument{\hypersetup{pdftitle={\@title}}}
638   \fi
```

```

639 \fi
640 \ifhep@title
641   \AtBeginDocument{\hypersetup{pdfauthor=\AB@authlist}}
642 \else
643   \ifhep@beamer\else
644     \AtBeginDocument{\hypersetup{pdfauthor={\@author}}}
645   \fi
646 \fi

```

I.1 Footnotes

Place a hyperlink from the footnote back to its referencing label using the FOOTNOTEBACKREF package [67].

```

647 \def\BackrefFootnoteTag{}
648 \RequirePackage{footnotebackref}

```

\footnote Ensure that no spaces appear before the footmark or at the beginning of the footnote.

```

649 \let\@foot@note\footnote
650 \renewcommand{\footnote}[1]{\unskip\@foot@note{\ignorespaces#1}}

```

I.2 References

Begin of references conditional

```
651 \ifhep@references
```

\cref Improve reference using the CLEVEREF package [13].

```

652 \RequirePackage[noabbrev, nameinlink]{cleveref}
653 \newcommand{\creflastconjunction}{, and\nobreakspace}
654 \crefname{enumi}{point}{points}
655 \crefname{inlinelisti}{point}{points}

```

\no@break@before Define a macro able to prevent line breaks.

```

656 \newcommand\no@break@before{%
657   \relax\ifvmode\else%
658   \ifhmode%
659     \ifdim\lastskip > 0pt%
660       \relax\unskip\nobreakspace%
661     \fi%
662   \fi%
663 \fi%
664 }

```

\ref Adjust \ref{\langle key\rangle} in order to prevent preceding line breaks.

```

665 \let\hep@ref\ref
666 \AtBeginDocument{\renewcommand\ref{\no@break@before\hep@ref}}

```

`\eqref` Adjust `\eqref{<key>}` in order to prevent preceding line breaks.

```
667 \renewcommand\eqref{\no@break@before\labelcref}
```

`\subref` Adjust `\subref{<key>}` in order to prevent preceding line breaks.

```
668 \let\hep@subref\subref
669 \renewcommand\subref{\no@break@before\hep@subref}
670 \renewcommand*\subcaption@ref[2]{\begingroup%
671   \caption@setoptions{sub}%
672   \subcaption@reffmt\p@subref{\hep@ref#1{sub@#2}}%
673 \endgroup}
```

`\subcref` Provide the `\subcref` macro.

```
674 \newcommand{\subcref}[1]{\cref{sub@#1}}
```

`\eqcrefname` Define the `\eqcrefname` macro for named equation types.

```
675 \NewDocumentCommand{\eqcrefname}{mmo}{%
676   \crefname{#1}{#2}{\IfValueTF{#3}{#3}{#2s}}%
677   \creflabelformat{#1}{(\##2##1##3)}%
678 }
```

`\labelcrefrange` Define the missing `\labelcrefrange{<key1>}{<key2>}` macro.

```
679 \DeclareRobustCommand{\labelcrefrange}[2]{%
680   \crefrange@star{\labelcref}{#1}{#2}%
681 }
```

End of references conditional

```
682 \fi
```

I.3 Citations

`\cite` Adjust `\cite{<key>}` in order to prevent preceding line breaks.

```
683 \let\hep@cite\cite
684 \renewcommand\cite{\no@break@before\hep@cite}
```

Begin of bibliography if.

```
685 \ifnum\pdf@strcmp{\hep@bibliography}{false}=0\else
```

Define bibstrings for reference names.

```
686 \NewBibliographyString{refname}
687 \NewBibliographyString{refsname}
688 \DefineBibliographyStrings{english}{%
```

```

689   refname = {reference},
690   refsname = {references}
691 }

\ccite Define clever citation macros.
\CCite
692 \DeclareCiteCommand{\ccite}{%
693   \ifnum\thecitetotal=1
694     \bibstring{refname}%
695   \else%
696     \bibstring{refsname}%
697   \fi%
698   \addnbspace\bibopenbracket%
699   \usebibmacro{cite:init}\usebibmacro{prenote}%
700 }{\usebibmacro{citeindex}\usebibmacro{cite:comp}}{}{%
701   \usebibmacro{cite:dump}\usebibmacro{postnote}%
702   \bibclosebracket%
703 }
704
705 \newrobustcmd*\CCite{\bibsentence\ccite}

```

End of biblatex if.

```
706 \fi
```

J Acronyms

Acronyms are implemented with the GLOSSARIES-EXTRA package [68] which is an extension of the GLOSSARIES package [12] and must be loaded after the HYPERREF pacakge in appendix I.

```

707 \ifhep@glossaries
708 \RequirePackage[nostyles]{glossaries-extra}

```

The entry count feature is used.

```

709 \glsenableentrycount
710 \glssetcategoryattribute{abbreviation}{entrycount}{1}

```

Provide macros for older glossaries-extra installations.

```

711 \providecommand{\glsxtrusefield}[2]{\@gls@entry@field{\#1}{\#2}}
712 \providecommand{\glsxtrsetfieldifexists}[3]{\glsdoifexists{\#1}{\#3}}
713 \providecommand{\gGlsXtrSetField}[3]{%
714   \glsxtrsetfieldifexists{\#1}{\#2}{%
715     \csgdef{glo@\glsdetoklabel{\#1}@{\#2}}{\#3}%
716   }%
717 }

```

Hyperlinks from the abbreviation to their definition in the text are set.

```
718 \glssetcategoryattribute{abbreviation}{nohyperfirst}{true}
719 \renewcommand*{\glsdonohyperlink}[2]{%
720   \glsxtrprotectlinks\edef\fieldvalue{%
721     \glsxtrusefield{\glslabel}{hastarget}%
722   }%
723   \ifdefstring\fieldvalue{true}{#2}{%
724     \gGlsXtrSetField{\glslabel}{hastarget}{true}%
725     \glsdohypertarget{#1}{#2}%
726   }%
727 }}
```

\begin@sentence Mark the beginning of a paragraph as if it would follow a full stop using the `EVERYHOOK` package [69].

```
728 \RequirePackage[excludeor]{everyhook}
729 \newcommand{\begin@sentence}{1001}
730 \PushPostHook{par}{\spacefactor=\begin@sentence}}
```

\frenchspacing Adjust the `\frenchspacing` macro to be compatibel with this idea.

```
731 \def\frenchspacing{%
732   \sfcode`\. \begin@sentence \sfcode`\?\begin@sentence
733   \sfcode`\! \begin@sentence \sfcode`\:\begin@sentence
734   \sfcode`\; \@m \sfcode`\,\@m
735 }
```

\if@begin@of@sentence Provide a macro checking for the beginning of a sentence by examining the length of the preceeding space.

```
736 \newcommand{\if@begin@of@sentence}[2]{\leavevmode\protecting{%
737   \ifboolexpr{ test {\ifnumcomp{\spacefactor}{=}{3000}} or%
738         test {\ifnumcomp{\spacefactor}{=}{2000}} or%
739         test {\ifnumcomp{\spacefactor}{=}{\begin@sentence}}%
740   }{#1}{#2}%
741 }}
```

\acronym The `\acronym{*}[<typeset abbreviation>]{<abbreviation>}(*){<definition>}[<plural definition>]` macro is defined.

#1 star for omitting the ‘s’ in the short plural
#2 optional typeset abbreviation
#3 mandatory abbreviation
#4 star for restoring the TeX default for space after text macros
#5 mandatory long form
#6 optional plural long form

```
742 \NewDocumentCommand{\acronym}{somsmo}{%
743   \newabbreviation[
```

```

744     type=\acronymtype,
745     sort=#3,
746     \glsshortpluralkey=\IfBooleanTF{#1}{#3}{\IfNoValueTF{#2}{#3s}{#2s}},
747     longplural=\IfNoValueTF{#6}{#5s}{#6}
748 ]{#3}{\IfNoValueTF{#2}{#3}{#2}}{#5}

```

Provide the singular acronym macro.

```

749 \expandafter\newcommand\csname#3\endcsname{%
750   \if@begin@of@sentence{%
751     \ifglsused{#3}{\cglshash{#3}{\cGls{#3}}}{%
752       \cglshash{#3}{%
753         \ifnum\glsentrycurrcount{#3}>1\relax
754           \IfBooleanTF{#4}{\@xspace}{%
755             \else\@xspace\fi
756           }

```

Expand the singular acronym macro in PDF labels.

```

757 \pdfstringdefDisableCommands{\expandafter\def\csname#3\endcsname{%
758   \IfNoValueTF{#2}{#3}{#2} }%
759 }

```

Provide the singular acronym macro in math mode.

```

760 \expandafter\mathdef\csname#3\endcsname{%
761   \text{\glsxtrshort{#3}}\gls@increment@currcount{#3}%
762 }

```

Provide the plural acronym macro.

```

763 \expandafter\newcommand\csname#3s\endcsname{%
764   \if@begin@of@sentence{\cGlspl{#3}}{\cglshash{#3}{%
765     \IfBooleanTF{#4}{\@xspace}{%
766       }

```

Expand the plural acronym macro in PDF labels.

```

767 \pdfstringdefDisableCommands{\expandafter\def\csname#3s\endcsname{%
768   \IfBooleanTF{#1}{#3}{\IfNoValueTF{#2}{#3s}{#2s}} }%
769 }

```

Provide the plural acronym macro in math mode.

```

770 \expandafter\mathdef\csname#3s\endcsname{%
771   \text{\glsxtrshortpl{#3}}\gls@increment@currcount{#3}%
772 }
773 }

```

\shortacronym The \shortacronym never expands into the long form.

```

774 \NewDocumentCommand{\shortacronym}{somsmo}{%

```

Provide the singular acronym macro.

```
775 \expandafter\newcommand\csname#3\endcsname{%
776   \IfNoValueTF{#2}{#3}{#2}\IfBooleanTF{#4}{}{\@xspace}%
777 }
```

Expand the singular acronym macro in PDF labels.

```
788 \pdfstringdefDisableCommands{\expandafter\def\csname#3\endcsname{%
789   \IfNoValueTF{#2}{#3}{#2} }%
790 }
```

Provide the singular acronym macro in math mode.

```
781 \expandafter\mathdef\csname#3\endcsname{%
782   \text{\IfNoValueTF{#2}{#3}{#2}}%
783 }
```

Provide the plural acronym macro.

```
784 \expandafter\newcommand\csname#3s\endcsname{%
785   \IfBooleanTF{#1}{#3}{\IfNoValueTF{#2}{#3s}{#2s}}%
786   \IfBooleanTF{#4}{}{\@xspace}%
787 }
```

Expand the plural acronym macro in PDF labels.

```
788 \pdfstringdefDisableCommands{\expandafter\def\csname#3s\endcsname{%
789   \IfBooleanTF{#1}{#3}{\IfNoValueTF{#2}{#3s}{#2s}} }%
790 }
```

Provide the plural acronym macro in math mode.

```
791 \expandafter\mathdef\csname#3s\endcsname{%
792   \text{\IfBooleanTF{#1}{#3}{\IfNoValueTF{#2}{#3s}{#2s}}}}%
793 }%
794 }
```

\longacronym The \longacronym never shows the abbreviated form.

```
795 \NewDocumentCommand{\longacronym}{somsmo}{
```

Provide the singular acronym macro.

```
796 \expandafter\newcommand\csname#3\endcsname{%
797   \if@begin@of@sentence{\MakeUppercase#5}{#5}%
798   \IfBooleanTF{#4}{}{\@xspace}%
799 }
```

Expand the singular acronym macro in PDF labels.

```
800 \pdfstringdefDisableCommands{\expandafter\def\csname#3\endcsname{#5 }}
```

Provide the plural acronym macro.

```
801 \expandafter\newcommand\csname#3s\endcsname{%
802   \if@begin@of@sentence{%
803     \IfNoValueTF{#6}{\MakeUppercase#5s}{\MakeUppercase#6}%
804   }{%
805     \IfNoValueTF{#6}{#5s}{#6}\IfBooleanTF{#4}{\@xspace}{%
806   }}
```

Expand the plural acronym macro in PDF labels.

```
807 \pdfstringdefDisableCommands{\expandafter\def\csname#3s\endcsname{%
808   \IfNoValueTF{#6}{#5s}{#6} }%
809 }
810 }
```

Silence warning if no acronyms are defined.

```
811 \renewcommand*{\@gls@write@entrycounts}{%
812   \immediate\write\auxout{%
813     \string\providecommand*\string\@gls@entry@count}[2]{}
814   }%
815 \count@=0\relax
816 \forallglsentries{\@glsentry}{%
817   \glshasattribute{\@glsentry}{entrycount}{%
818     \ifglsused{\@glsentry}{%
819       \immediate\write\auxout{%
820         \string\@gls@entry@count{\@glsentry}{%
821           \glsentrycurrcount{\@glsentry}}%
822       }
823     }%
824   }{}\advance\count@ by \one
825 }{}%
826 }%
827 }
```

\resetacronym Add two macros for acronym management.

\dummyacronym

```
828 \newcommand{\resetacronym}[1]{\protect\glsreset{#1}}
829 \newcommand{\dummyacronym}[1]{\protect\glsunset{#1}}
```

abstract Adjust the abstract environment to reset all acronym counters.

```
830 \@ifundefined{endabstract}{%
831   \let\end@hep@abstract\endabstract%
832   \renewcommand\endabstract{\glsresetall\end@hep@abstract}%
833 }
```

\tableofcontents Adjust the \tableofcontents macro to never show the long form of acronyms.

\listoffigures
\listoftables

```
834 \let\hep@table@of@contents\tableofcontents
```

```

835 \renewcommand\tableofcontents{%
836   \glsunsetall\hep@table@of@contents\glsresetall%
837 }
838 \let\hep@list@of@figures\listoffigures
839 \renewcommand\listoffigures{%
840   \glsunsetall\hep@list@of@figures\glsresetall%
841 }
842 \let\hep@list@of@tables\listoftables
843 \renewcommand\listoftables{%
844   \glsunsetall\hep@list@of@tables\glsresetall%
845 }

```

\acronyms Add a possibility to have different groups of acronyms.

```

846 \NewDocumentCommand{\acronyms}{om}{%
847   \IfNoValueTF{#1}{%
848     \newglossary{#2}{#2.in}{#2.out}{#2}%
849     \renewcommand{\acronymtype}{#2}%
850   }{%
851     \newglossary{#1}{#1.in}{#1.out}{#2}%
852     \renewcommand{\acronymtype}{#1}%
853   }%
854 }

```

End of glossaries if.

```
855 \fi
```

K Biblatex datamodel file

collaboration Define the dbx file containing the hep-paper datamodel.

```

reportnumber
  pmid
  pmcid
  pmc
protocollessurl
  856 \DeclareDatamodelFields[type=field, datatype=literal]{%
  857   collaboration, reportnumber, pmid, pmcid, pmc,
  858 }
  859 \DeclareDatamodelFields[type=field, datatype=uri]{protocollessurl}
  860 \DeclareDatamodelEntryfields{%
  861   collaboration, reportnumber, pmid, pmcid, pmc, protocollessurl,
  862 }

```

References

- [1] J. Hajer. ‘The hep-paper package. Publications in high energy physics’ (2019). CTAN: [hep-paper](#). DOI: 10.5281/zenodo.3606436. GitHub: [janhajer/hep-paper](#).
- [2] D. Carlisle and H. Umeiki. ‘The geometry package. Flexible and complete interface to document dimensions’ (1996). CTAN: [geometry](#). GitHub: [davidcarlisle/geometry](#).

- [3] B. Jackowski and J. Nowacki. ‘Latin Modern Family of Fonts. Latin modern fonts in outline formats’ (2003). CTAN: lm. URL: gust.org.pl/projects/e-foundry/latin-modern.
- [4] R. Schlicht. ‘The `microtype` package. Subliminal refinements towards typographical perfection’ (2004). CTAN: `microtype`.
- [5] *L^AT_EX3 Project*. ‘Hypertext marks in L^AT_EX: a manual for `hyperref`. Extensive support for hypertext in L^AT_EX’ (1995). CTAN: `hyperref`. GitHub: [latex3/hyperref](https://github.com/latex3/hyperref).
- [6] J. Braams, J. Bezos and at al. ‘`Babel` Localization and internationalization. Multilingual support for Plain T_EX or L^AT_EX’ (1989). CTAN: `babel`. GitHub: [latex3/babel](https://github.com/latex3/babel).
- [7] R. Fairbairns, F. Mittelbach and H. Partl. ‘The `parskip` package. Layout with zero `\parindent`, non-zero `\parskip`’ (1989). CTAN: `parskip`. GitHub: [FrankMittelbach/fmitex](https://github.com/FrankMittelbach/fmitex).
- [8] *American Mathematical Society*. ‘The `amsfonts` package. T_EX fonts from the American Mathematical Society’ (1995). CTAN: `amsfonts`. URL: ams.org/tex/amsfonts.
- [9] O. Kummer. ‘The `doublestroke` font. Typeset mathematical double stroke symbols’ (1995). CTAN: `doublestroke`.
- [10] A. Blumensath. ‘The `MnSymbol` package. Mathematical symbol font for Adobe MinionPro’ (2005). CTAN: `MnSymbol`.
- [11] P. Lehman et al. ‘The `biblatex` Package. Sophisticated Bibliographies in L^AT_EX’ (2006). CTAN: `biblatex`. GitHub: [plk/biblatex](https://github.com/plk/biblatex).
- [12] N. Talbot. ‘The `glossaries` package. Create glossaries and lists of acronyms’ (2007). CTAN: `glossaries`.
- [13] T. Cubitt. ‘The `cleveref` package. Intelligent cross-referencing’ (2006). CTAN: `cleveref`. URL: dr-qubit.org/cleveref.
- [14] T. Tantau, J. Wright and V. Miletic. ‘The `beamer` class. A L^AT_EX class for producing presentations and slides’ (2003). CTAN: `beamer`. GitHub: [josephwright/beamer](https://github.com/josephwright/beamer).
- [15] *SISSA Medialab*. ‘The `JHEP` package’ (1997). URL: jhep.sissa.it/jhep/help/JHEP_TeXclass.jsp.
- [16] *SISSA Medialab*. ‘The `JCAP` package’ (2002). URL: jcap.sissa.it/jcap/help/JCAP_TeXclass.jsp.
- [17] *American Physical Society*. ‘The `REVTeX` class. Styles for various Physics Journals’ (1999). CTAN: `revtex`. URL: journals.aps.org/revtex.
- [18] P. R. Wilson. ‘The `titling` package. Control over the typesetting of the `\maketitle` command’ (2000). CTAN: `titling`.
- [19] P. W. Daly. ‘A L^AT_EX Package to Prepare Author and Affiliation Blocks. Support for footnote style author/affiliation’ (2001). CTAN: `authblk`.
- [20] P. Lehman and J. Wright. ‘The `csquotes` Package. Context sensitive quotation facilities’ (2003). CTAN: `csquotes`.
- [21] P. G. Ratcliffe. ‘The `foreign` package for L^AT_EX 2 _{ε} . Systematic treatment of “foreign” words in documents’ (2012). CTAN: `foreign`.

- [22] D. Arseneau. ‘The `url` package. Verbatim with URL-sensitive line breaks’ (1996). CTAN: `url`.
- [23] J. Bezos. ‘Customizing lists with the `enumitem` package. Control layout of itemize, enumerate, description’ (2003). CTAN: `enumitem`. URL: texnia.com/enumitem.html. GitHub: [jbezos / enumitem](https://github.com/jbezos/enumitem).
- [24] A. Barton. ‘The `sansmathfonts` package. Correct placement of accents in sans-serif maths’ (2013). CTAN: `sansmathfonts`.
- [25] D. Arseneau. ‘The `ulem` package. Package for underlining’ (1989). CTAN: `ulem`.
- [26] L. Madsen et al. ‘The `mathtools` package. Mathematical tools to use with `amsmath`’ (2004). CTAN: `mathtools`.
- [27] *L^AT_EX Team*. ‘The `amsmath` package. AMS mathematical facilities for L^AT_EX’ (1994). CTAN: `amsmath`. URL: ams.org/tex/amslatex.
- [28] *L^AT_EX Team*. ‘The `bm` package. Access bold symbols in maths mode’ (1993). CTAN: `bm`.
- [29] *L^AT_EX Team*. ‘L^AT_EX 2 _{ε} font selection. Documentation of L^AT_EX font commands’ (1995). CTAN: `fntguide`.
- [30] W. Schmidt. ‘The `fixmath` package for L^AT_EX 2 _{ε} . Make maths comply with ISO 31-0:1992 to ISO 31-13:1992’ (2000). CTAN: `fixmath`.
- [31] G. Milde. ‘The `alphabeta` package. L^IC^R macros and encoding definition files for Greek’ (2013). CTAN: `greek - fontenc`.
- [32] S. C. de la Barrera. ‘The `physics` package. Macros supporting the Mathematics of Physics’ (2012). CTAN: `physics`.
- [33] D. Arseneau. ‘The `cancel` package. Place lines through maths formulae’ (2013). CTAN: `cancel`.
- [34] D. Carlisle. ‘The `slashed` package. Put a slash through characters’ (1987). CTAN: `slashed`.
- [35] A. Reichert. ‘The `units` and `nicefrac` packages. Typeset units’ (1998). CTAN: `units`.
- [36] A. Sommerfeldt. ‘The `subcaption` package. Support for sub-captions’ (2007). CTAN: `subcaption`. GitLab: [axelsommerfeldt / caption](https://gitlab.com/axelsommerfeldt/caption).
- [37] D. Els and S. Fear. ‘The `booktabs` package. Publication quality tables in L^AT_EX’ (1995). CTAN: `booktabs`.
- [38] P. van Oostrum and J. Leichter. ‘The `multirow`, `bigstrut` and `bigdelim` packages. Create tabular cells spanning multiple rows’ (1994). CTAN: `multirow`.
- [39] D. Carlisle and S. Rahtz. ‘Packages in the “graphics” bundle. Enhanced support for graphics’ (1994). CTAN: `graphicx`.
- [40] F. Charette and P. Kime. ‘`biber`. Backend processor for BibL^AT_EX’ (2009). GitHub: [plk / biber](https://github.com/plk/biber). sourceforge: `biblatex - biber`.
- [41] *arXiv Team*. ‘arXiv. free distribution service and an open archive for scholarly articles’ (1991). URL: [arxiv . org](http://arxiv.org).
- [42] D. Sutherland. ‘`arxiv-collector`. A little Python script to collect L^AT_EX sources for upload to the arXiv’ (2018). GitHub: [douglas-sutherland / arxiv-collector](https://github.com/douglas-sutherland/arxiv-collector).

- [43] W. A. Schmidt. ‘The `cmbright` package. Using the CM Bright typeface with L^AT_EX’ (1996). CTAN: `cmbright`.
- [44] F. Mittelbach and R. Schöpf. ‘The `exscale` package. Implements scaling of the “cmex” fonts’ (1993). CTAN: `exscale`.
- [45] *American Mathematical Society*. ‘The `amssymb` package’ (1995). CTAN: `amsfonts`.
- [46] J. Knappen. ‘The `mathrsfs` package. Support for using RSFS fonts in maths’ (1995). CTAN: `mathrsfs`.
- [47] H. Oberdiek. ‘The `pdftexcmds` package. LuaT_EX support for pdfT_EX utility functions’ (2007). CTAN: `pdftexcmds`.
- [48] H. Oberdiek. ‘The `kvoptions` package. Key value format for package options’ (2004). CTAN: `kvoptions`. GitHub: `ho-tex/kvoptions`.
- [49] *L^AT_EX Team*. ‘The `ifluatex` package. Provides the `\ifluatex` switch’ (2007). CTAN: `ifluatex`.
- [50] *L^AT_EX Team*. ‘The `ifxetex` package. Am I running under X_ET_EX?’ (2006). CTAN: `ifxetex`. GitHub: `latex3 / ifxetex`.
- [51] *L^AT_EX Team*. ‘The `fontenc` package. Standard package for selecting font encodings’ (1995). CTAN: `fontenc`.
- [52] *L^AT_EX3 Project Team*. ‘L^AT_EX font encodings. Documentation of L^AT_EX font encodings’ (1995). CTAN: `encguide`.
- [53] F. Mittelbach et al. ‘The `fix-cm` package. Permit Computer Modern fonts at arbitrary sizes’ (1993). CTAN: `fix-cm`.
- [54] *L^AT_EX Team*. ‘The `textcomp` package. L^AT_EX support for the Text Companion fonts’ (1995). CTAN: `textcomp`.
- [55] W. Robertson and K. Hosny. ‘The `fontspec` package. Advanced font selection in X_ET_EX and LuaL^AT_EX’ (2004). CTAN: `fontspec`.
- [56] *L^AT_EX Team*. ‘The `inputenc` package. Accept different input encodings’ (1989). CTAN: `inputenc`.
- [57] *L^AT_EX Team*. ‘The `xspace` package. Define commands that appear not to eat spaces’ (1993). CTAN: `xspace`.
- [58] D. Arseneau and M. Swift. ‘The `relsize` package. Set the font size relative to the current font size’ (2011). CTAN: `relsize`.
- [59] *L^AT_EX3 Project*. ‘The `xparse` package. A generic document command parser’ (1999). CTAN: `xparse`.
- [60] H. Oberdiek. ‘The `mleftright` package. Variants of delimiters that act as maths open/close’ (2010). CTAN: `mleftright`.
- [61] E. Saudrais. ‘The `esint` package. Extended set of integrals for Computer Modern’ (2005). CTAN: `esint`.
- [62] A. Sommerfeldt. ‘The `caption` package. Customising captions in floating environments’ (1994). CTAN: `caption`. GitLab: `axelsommerfeldt/caption`.
- [63] M. Schröder. ‘The `ragged2e`-package. Alternative versions of “ragged”-type commands’ (1996). CTAN: `ragged2e`. GitLab: `hagenbuch/ragged2e`.
- [64] D. Arseneau. ‘The `varwidth` package. A variable-width minipage’ (2003). CTAN: `varwidth`.

- [65] H. Oberdiek. ‘The `atbegshi` package. Execute stuff at `shipout` time’ (2007). CTAN: `atbegshi`. GitHub: `ho-tex/atbegshi`.
- [66] H. Oberdiek. ‘The `picture` package. Dimens for picture macros’ (2006). CTAN: `picture`. GitHub: `ho-tex/picture`.
- [67] H. Lange. ‘The `footnotebackref` package. Back-references from footnotes’ (2012). CTAN: `footnotebackref`.
- [68] N. T. Dickimaw Books. ‘The `glossaries-extra` package. An extension to the `glossaries` package’ (2015). CTAN: `glossaries-extra`.
- [69] S. Checkoway. ‘The `everyhook` package. Hooks for standard `TEX` token lists’ (2010). CTAN: `everyhook`.

Change History

v1.0		of biblatex datamodel into its own file 1
General: Initial version of the style file.	1	
v1.1		v1.4
General: Transition to documented L ^A T _E X source file.	1	General: If possible the compatibility options are selected automatically.
v1.2		Inclusion of PubMed IDs in bibliography 1
General: Introduction of package options.	1	v1.5
v1.3		General: Reduce the number of math alphabets used in sans serif mode. Add more title options such as a subtitle. Use standard class options 1
General: Inclusion of JHEP and JCAP package options. Fix of incompatibility with recent subcaption package version. Move		