

README for hyperref bundle

Heiko Oberdiek, Sebastian Rahtz

2008/07/05

Contents

1	Introduction	2
2	Download	3
3	Installation	3
	Installation with ZIP file in TDS format	3
	Manual installation	4
4	Additional Packages	4
5	New Features	5
	Expert feature <code>\HyperDestNameFilter</code>	5
	Experimental option <code>'ocgcolorlinks'</code>	5
	Option <code>'pdfa'</code>	6
	Option <code>'linktoc'</code> added	6
	Option <code>'pdfnewwindow'</code> changed	6
	Flag options for PDF forms	7
	Option <code>'pdfversion'</code>	8
	Field option <code>'name'</code>	8
	Option <code>'pdfencoding'</code>	9
	Color options/package <code>hycolor</code>	9
	Option <code>pdfusetitle</code>	9
	Starred form of <code>\autoref</code>	9
	Link border style	9
	Option <code>"bookmarksdepth"</code>	10
	Option <code>"pdfescapeform"</code>	10
	Default driver setting	10
	Backref entries	11
	<code>\phantomsection</code>	12
	<code>\hypercalcbp</code>	13
6	Package Compatibility	13
	<code>algorithm</code>	13
	<code>amsmath</code>	13
	<code>amsrefs</code>	13
	<code>arydshln</code> , <code>longtable</code>	13
	<code>babel/magyar.ldf</code>	13
	<code>bibentry</code>	14
	<code>chappg</code>	14
	<code>cite</code>	14
	<code>dblacnt</code>	14
	<code>easyeqn</code>	14
	<code>ellipsis</code>	15

float	15
foiltex	15
footnote	15
geometry	15
IEEEtran.cls	16
index	16
lastpage	16
linguex	16
ltabptch	16
minitoc-hyper	16
multind	16
natbib	16
nomencl	16
prettyref	17
ntheorem	17
setspace	17
sidecap	17
subfigure	17
titleref	18
titlesec	18
varioref	18
verse	18
vietnam	19
7 Limitations	19
Wrapped/broken link support	19
8 Hints	20
Spaces in option values	20
Index with makeindex	20
Warning "bookmark level for unknown <foobar> defaults to 0"	21
Link anchors in figures	21
Additional unicode characters in bookmarks and pdf information entries:	21
Footnotes	22
9 Authors/Maintainers	23
10 Bug Reports	23
Vietnamese part	23
Arabic part	23
11 Known Problems	23
12 ToDo	24
13 Versions in TeX distributions	24
TeX Live	24

1 Introduction

This package is used to emend cross-referencing commands in LaTeX to produce some sort of `\special` commands; there are backends for the `\special` set defined for HyperTeX dvi processors, for embedded pdfmark commands for processing by Acrobat Distiller (dvips and dvipsone), for dviwindo, for pdfTeX, for dviPDFm, for TeX4ht, and for VTeX's pdf and HTML backends.

Included are:

- a) 'backref' a package by David Carlisle to provide links back from bibliography to the main text; these are hypertext links after using hyperref.
- b) nameref' a package to allow reference to the *names* of sections rather than their numbers.

2 Download

'hyperref' is available on CTAN:

CTAN:macros/latex/contrib/hyperref/

Also a ZIP file is provided that contains the files, already sorted in a TDS tree:

CTAN:install/macros/latex/contrib/hyperref.tds.zip

'CTAN:' means one of the 'Comprehensive TeX Archive Network' nodes or one of its mirrors. This is explained in

<http://www.tex.ac.uk/cgi-bin/texfaq2html?label=archives>

The files are organized in three, sometimes four directories:

```
./
  Root directory that contains 'README', '.dtx',
  and '.ins' files.
doc/
  Directory for documentation files.
test/
  Directory for some test files.
```

The main repository of hyperref is located at the server of the international 'TeX User Group' (TUG). The hyperref directory at the TUG server

<http://www.tug.org/applications/hyperref/>

contains the following files:

```
hyperref.zip
hyperref-doc.zip
hyperref-test.zip
```

```
manual.html
manual2.html
manual.css
```

HTML version of the quite old hyperref manual in 'doc/manual.pdf'.

The CTAN stuff will be mirrored automatically from the ftp server, so

<ftp://ftp.tug.org/pub/tex/hyperref/>

corresponds to

CTAN:macros/latex/contrib/hyperref/

3 Installation

Installation with ZIP file in TDS format

The ZIP file 'hyperref.tds.zip' contains the files sorted in a TDS tree. Thus you can directly unpack the ZIP file inside a TDS tree. (See CTAN:tds.zip for an explanation of TDS.)

Example:

```
cd /...somewhere.../texmf
unzip /...downloadpath.../hyperref.tds.zip
```

Do not forget to refresh the file name database of this TDS tree,

Example:

```
texhash /...somewhere.../texmf
```

Manual installation

- a) Download the hyperref files from CTAN or the TUG server.
If necessary, unpack them.
- b) If directory 'beta' exists, replace the files by the counterparts in this directory, if you want to use the latest versions.
- c) Generate the package and driver files:
tex hyperref.ins
- d) Install the files '*.sty', '*.def', and '*.cfg' in your TDS tree:
cp *.sty *.def *.cfg TDS:tex/latex/hyperref/
Replace 'TDS:' by the prefix of your TDS tree (texmf directory).
The exception is bmhydoc.sty, it belongs to the source files (TDS:source/latex/hyperref/).
- e) Copy the documentation files to "TDS:doc/latex/hyperref/":
manual.pdf, README, README.pdf, ChangeLog, ChangeLog.pdf, slides.pdf, paper.pdf, options.pdf, hyperref.pdf, backref.pdf, nameref.pdf (Also the HTML version of the manual can be put there.)
- f) Update the databases if necessary, eg. for teTeX:
mktexlsr .../texmf

4 Additional Packages

Depending on the driver and option settings, hyperref loads other packages:

- * atbegshi.sty:
CTAN:macros/latex/contrib/oberdiek/atbegshi.pdf
- * backref.sty (loaded by option 'backref' or 'pagebackref'):
CTAN:macros/latex/contrib/hyperref/backref.dtx
- * bigintcalc.sty (loaded by package 'bitset'):
CTAN:macros/latex/contrib/oberdiek/bigintcalc.pdf
- * bitset.sty:
CTAN:macros/latex/contrib/oberdiek/bitset.pdf
- * color.sty (loaded by option 'colorlinks'):
CTAN:macros/latex/required/graphics/
- * etexcmds.sty:
CTAN:macros/latex/contrib/oberdiek/etexcmds.pdf
- * hycolor.sty:
CTAN:macros/latex/contrib/oberdiek/hycolor.pdf
- * infwarerr.sty (loaded by packages 'etexcmds', 'stringenc', 'atbegshi', 'bitset'):
CTAN:macros/latex/contrib/oberdiek/infwarerr.pdf
- * ifpdf.sty (loaded by package 'atbegshi'):
CTAN:macros/latex/contrib/oberdiek/atbegshi.pdf
- * ifvtex.sty:
CTAN:macros/latex/contrib/oberdiek/ifvtex.pdf
- * ifxetex.sty:
CTAN:macros/generic/ifxetex/ifxetex.sty
- * intcalc.sty (loaded by package 'bitset'):

```

    CTAN:macros/latex/contrib/oberdiek/intcalc.pdf
* keyval.sty
    CTAN:macros/latex/required/graphics/
* kvoptions.sty:
    CTAN:macros/latex/contrib/oberdiek/kvoptions.pdf
* kvsetkeys.sty:
    CTAN:macros/latex/contrib/oberdiek/kvsetkeys.pdf
* memhfixc.sty (loaded if class 'memoir' is loaded):
    CTAN:macros/latex/contrib/memoir/memhfixc.sty
* nameref.sty:
    CTAN:macros/latex/contrib/hyperref/nameref.dtx
* pdfescape.sty (loaded by package 'stringenc'):
    CTAN:macros/latex/contrib/oberdiek/pdfescape.pdf
* pdftexcmds.sty
    CTAN:macros/latex/contrib/oberdiek/pdftexcmds.pdf
* refcount.sty (loaded by package 'nameref')
    CTAN:macros/latex/contrib/oberdiek/refcount.pdf
* stringenc.sty:
    CTAN:macros/latex/contrib/oberdiek/stringenc.pdf
* tex4ht.sty (loaded by option 'tex4ht'):
    CTAN:support/Tex4ht/
* url.sty
    CTAN:macros/latex/contrib/other/misc/url.sty
* vtexhtml.sty (loaded if VTeX is used in HTML mode)

```

5 New Features

Expert feature `\HyperDestNameFilter`

Since version 2008/07/16 v6.78c.

Each anchor name and inner link name is put through filter `\HyperDestNameFilter`. The default behaviour is to let the name unchanged:

```
\def\HyperDestNameFilter#1{#1}
```

It can be redefined to prepend or append something, to avoid name collisions if several files are merged together.

For example, two documents with `hyperref` can be generated using different prefixes for destination names. Then it is easier to merge them with `'dviconcat'` or other merge utilities.

Experimental option `'ocgcolorlinks'`

The idea are colored links, when viewed, but printed without colors. This new experimental option `'ocgcolorlinks'` uses `Optional Content Groups`, a feature introduced in PDF 1.5.

* The option must be given for package loading:

```
\usepackage[ocgcolorlinks]{hyperref}
```

* Main disadvantage: Links cannot be broken across lines.

PDF reference 1.7: 4.10.2 "Making Graphical Content Optional":

Graphics state operations, such as setting the color, ..., are still applied.

Therefore the link text is put in a box and set twice, with and without color.

- * The feature can be switched off by `\hypersetup{ocgcolorlinks=false}` inside the document.
- * Supported drivers: `pdftex`, `dvipdfm`
- * The PDF version should be at least 1.5. It is automatically set for `pdfTeX`. Users of `dvipdfmx` set the version on the command line: `dvipdfmx -V 5`

Option ‘pdfa’

The new option ‘pdfa’ tries to avoid violations of PDF/A in code generated by `hyperref`. However, the result is usually not in PDF/A, because many features aren’t controlled by `hyperref` (XMP metadata, fonts, colors, driver dependend low level stuff, ...).

Currently, option ‘pdfa’ sets and disables the following items:

- * Enabled annotation flags: `Print`, `NoZoom`, `NoRotate` [PDF/A 6.5.3].
- * Disabled annotation flags: `Hidden`, `Invisible`, `NoView` [PDF/A 6.5.3].
- * Disabled: Launch action (`\href{run:...}`) [PDF/A 6.6.1].
- * Restricted: Named actions (`\Acrobatmenu: NextPage`, `PrevPage`, `FirstPage`, `LastPage`) [PDF/A 6.6.1].
- * Many things are disabled in PDF formulators:
 - * JavaScript actions [PDF/A 6.6.1]
 - * Trigger events (additional actions) [PDF/A 6.6.2]
 - * Push button (because of JavaScript)
 - * Interactive Forms: Flag `NeedAppearances` is the default ‘false’ (Because of this, `hyperref`’s implementation of Forms looks ugly). [PDF/A 6.9]

The default value of the new option ‘pdfa’ is ‘false’. It influences the loading of the package and cannot be changed after `hyperref` is loaded (`\usepackage{hyperref}`).

ToDo:

- * XMP support
- * ...

But perhaps Adobe Acrobat is now happy and can now convert the PDF file to PDF/A.

Option ‘linktoc’ added

The new option ‘linktoc’ allows more control which part of an entry in the table of contents is made into a link:

- * ‘linktoc=none’ (no links)
- * ‘linktoc=section’ (default behaviour, same as ‘linktocpage=false’)
- * ‘linktoc=page’ (same as ‘linktocpage=true’)
- * ‘linktoc=all’ (both the section and page part are links)

Option ‘pdfnewwindow’ changed

Before 6.77b:

- * `pdfnewwindow=true` --> `/NewWindow true`
- * `pdfnewwindow=false` --> `(absent)`
- * unused `pdfnewwindow` --> `(absent)`

Since 6.77b:

- * `pdfnewwindow=true` --> `/NewWindow true`
- * `pdfnewwindow=false` --> `/NewWindow false`

```
* pdfnewwindow={} --> (absent)
* unused pdfnewwindow --> (absent)
```

Rationale: There is a difference between setting to 'false' and an absent entry. In the former case the new document replaces the old one, in the latter case the PDF viewer application should respect the user preference.

Flag options for PDF forms

PDF form field macros (\TextField, \CheckBox, ...) support boolean flag options. The option name is the lowercase version of the names in the PDF specification (1.7):

http://www.adobe.com/devnet/pdf/pdf_reference.html

http://www.adobe.com/devnet/acrobat/pdfs/pdf_reference.pdf

Options (convert to lowercase) except flags in square brackets:

* Table 8.16 Annotation flags (page 608):

- 1 Invisible
- 2 Hidden (PDF 1.2)
- 3 Print (PDF 1.2)
- 4 NoZoom (PDF 1.3)
- 5 NoRotate (PDF 1.3)
- 6 NoView (PDF 1.3)
- [7 ReadOnly (PDF 1.3)] ignored for widget annotations, see table 8.70
- 8 Locked (PDF 1.4)
- 9 ToggleNoView (PDF 1.5)
- 10 LockedContents (PDF 1.7)

* Table 8.70 Field flags common to all field types (page 676):

- 1 ReadOnly
- 2 Required
- 3 NoExport

* Table 8.75 Field flags specific to button fields (page 686):

- 15 NoToggleToOff (Radio buttons only)
- 16 Radio (set: radio buttons, clear: check box, pushbutton: clear)
- 17 Pushbutton
- 26 RadiosInUniso (PDF 1.5)

* Table 8.77 Field flags specific to text fields (page 691):

- 13 Multiline
- 14 Password
- 21 FileSelect (PDF 1.4)
- 23 DoNotSpellCheck (PDF 1.4)
- 24 DoNotScroll (PDF 1.4)
- 25 Comb (PDF 1.5)
- 26 RichText (PDF 1.5)

* Table 8.79 Field flags specific to choice fields (page 693):

- 18 Combo (set: combo box, clear: list box)
- 19 Edit (only useful if Combo is set)
- 20 (Sort) for authoring tools, not PDF viewers
- 22 MultiSelect (PDF 1.4)
- 23 DoNotSpellCheck (PDF 1.4) (only useful if Combo and Edit are set)
- 27 CommitOnSelChange (PDF 1.5)

* Table 8.86 Flags for submit-form actions (page 704):

- [1 Include/Exclude] unsupported, use 'noexport' (table 8.70) instead
- 2 IncludeNoValueFields
- [3 ExportFormat] handled by option 'export'
- 4 GetMethod

```

5 SubmitCoordinates
[6 XFDF (PDF 1.4)] handled by option 'export'
7 IncludeAppendSaves (PDF 1.4)
8 IncludeAnnotations (PDF 1.4)
[9 SubmitPDF (PDF 1.4)] handled by option 'export'
10 CanonicalFormat (PDF 1.4)
11 ExclNonUserAnnots (PDF 1.4)
12 ExclFKey (PDF 1.4)
14 EmbedForm (PDF 1.5)

```

New option 'export' sets the export format of a submit action.
Valid values are (upper- or lowercase):

- * FDF
- * HTML
- * XFDF
- * PDF (not supported by Acrobat Reader)

Option 'pdfversion'

This is an experimental option. It notifies 'hyperref' about the intended PDF version. Currently this is used in code for PDF forms (implementation notes 116 and 122 of PDF spec 1.7).

Values: 1.2, 1.3, 1.4, 1.5, 1.6, 1.7. Values below 1.2 are not supported, because most drivers expect higher PDF versions.

The option must be used early, not after `\usepackage{hyperref}`.

In theory this option should also set the PDF version, but this is not generally supported.

- * pdfTeX below 1.10a: unsupported.
- pdfTeX >= 1.10a and < 1.30: `\pdfoptionpdfminorversion`
- pdfTeX >= 1.30: `\pdfminorversion`
- * dvipdfm: configuration file, example:
TeX Live 2007, `texmf/dvipdfm/config/config`, entry 'V 2'.
- * dvipdfmx: configuration file, example:
TeX Live 2007, `texmf/dvipdfm/dvipdfmx.cfg`, entry 'V 4'.
- * Ghostscript: option `-dCompatibilityLevel` (this is set in 'ps2pdf12', 'ps2pdf13', 'ps2pdf14').

The current PDF version is used as default if this version can be detected (only pdfTeX >= 1.10a). Otherwise the lowest version 1.2 is assumed. Thus 'hyperref' tries to avoid PDF code that breaks this version, but is free to use ignorable higher PDF features.

Field option 'name'

Many form objects uses the label argument for several purposes:

- * Laid out label.
- * As name in HTML structures.

Code that is suitable for layouting with TeX can break in the structures of the output format.

If option 'name' is given, then its value is used as name in the different output structures. Thus the value should consist of letters only.

Option ‘pdfencoding’

The PDF format allows two encodings for bookmarks and entries in the information dictionary: PDFDocEncoding and Unicode

as UTF-16BE. Option "pdfencoding" selects between these encodings:

- * "pdfdoc" uses PDFDocEncoding. It uses just one byte per character, but the supported characters are limited (244 in PDF-1.7).
- * "unicode" sets Unicode. It is encoded as UTF-16BE. Two bytes are used for most characters, surrogates need four bytes.
- * "auto" PDFDocEncoding if the string does not contain characters outside the encoding and Unicode otherwise.

Color options/package hycolor

See documentation of package ‘hycolor’.

Option pdfusetitle

If option pdfusetitle is set then hyperref tries to derive the values for pdftitle and pdfauthor from \title and \author. An optional argument for \title and \author is supported (class amsart).

Starred form of \autoref

\autoref* generates a reference without link as \ref* or \pageref*.

Link border style

Links can be underlined instead of the default rectangle or options "colorlinks", "frenchlinks". This is done by option pdfborderstyle={/S/U/W 1}

Some remarks:

- * AR7/Linux seems to have a bug, that don't use the default value "1" for the width, but zero, thus that the underline is not visible without "/W 1". The same applies for dashed boxes, eg.:
pdfborderstyle={/S/D/D[3 2]/W 1}
- * The syntax is described in the PDF specification, look for "border style", eg.
Table 8.13 "Entries in a border style dictionary"
(specification for version 1.6)
- * The border style is removed by
pdfborderstyle={}
This is automatically done if option colorlinks is enabled.
- * Be aware that not all PDF viewers support this feature, not even Acrobat Reader itself:

Some support:

- * AR7/Linux: "underline" and "dashed", but the border width must be given.

* xpdf 3.00: "underline" and "dashed"

Unsupported:

* AR5/Linux

* ghostscript 8.50

Option "bookmarksdepth"

The depth of the bookmarks can be controlled by the new option "bookmarksdepth". The option acts globally and distinguishes three cases:

* "bookmarksdepth" without value

Then hyperref uses the current value of counter "tocdepth".

This is the compatible behaviour and the default.

* "bookmarksdepth=<number>", the value is number (also negative):

The depth for the bookmarks are set to this number.

* "bookmarksdepth=<name>"

The <name> is a document division name (part, chapter, ...).

It must not start with a digit or minus to avoid mixing up with the number case. Internally hyperref uses the value of macro "\toclevel@<name>".

Examples:

```
\hypersetup{bookmarksdepth=paragraph}
```

```
\hypersetup{bookmarksdepth=4} % same as before
```

```
\hypersetup{bookmarksdepth} % counter "tocdepth" is used
```

Option "pdfescapeform"

There are many places where arbitrary strings end up as PS or PDF strings. The PS/PDF strings in parentheses form require the protection of some characters, e.g. unmatched left or right parentheses need escaping or the escape character itself (backslash).

Since 2006/02/12 v6.75a the PS/PDF driver should do this automatically. However I assume a problem with compatibility, especially regarding the form part where larger amounts of JavaScript code can be present. It would be a pain to remove all the escaping, because an additional escaping layer can falsify the code.

Therefore a new option pdfescapeform was introduced:

* pdfescapeform=false

Escaping for the formatters are disabled, this is the compatibility behaviour, therefore this is the default.

* pdfescapeform=true

Then the PS/PDF drivers do all the necessary escaping.

This is the logical choice and the recommended setting.

For example, the user writes JavaScript as JavaScript and do not care about escaping characters for PS/PDF output.

Default driver setting

(hyperref >= 6.72s)

If no driver is given, hyperref tries its best to guess the most suitable driver. Thus it loads "hpdftex", if pdfTeX is

detected running in PDF mode. Or it loads the corresponding VTeX driver for VTeX's working modes.

Unhappily many driver programs run after the TeX compiler, so hyperref does not have a chance (dvips, dvipdfm, ...). In this case driver "hypertex" is loaded that supports the HyperTeX features that are recognized by xdvi for example. This behaviour, however, can easily be changed in the configuration file "hyperref.cfg":

```
\providecommand*{\Hy@defaultdriver}{hdvips}
for dvips, or
\providecommand*{\Hy@defaultdriver}{hypertex}
for the default behaviour of hyperref.
```

Backref entries

Alternative interface for formatting of backref entries, example:

```
\documentclass[12pt,UKenglish]{article}

\usepackage{babel}
\usepackage[pagebackref]{hyperref}

% Some language options are detected by package backref.
% This affects the following macros:
% \backrefpagesname
% \backrefsectionsname
% \backrefsep
% \backreftwosep
% \backreflastsep

\renewcommand*{\backref}[1]{
  % default interface
  % #1: backref list
  %
  % We want to use the alternative interface,
  % therefore the definition is empty here.
}

\renewcommand*{\backrefalt}[4]{%
  % alternative interface
  % #1: number of distinct back references
  % #2: backref list with distinct entries
  % #3: number of back references including duplicates
  % #4: backref list including duplicates
  \par
  #3 citation(s) on #1 page(s): #2,\par
  \ifnum#1=1 %
    \ifnum#3=1 %
      1 citation on page %
    \else
      #3 citations on page %
    \fi
  \else
    #3 citations on #1 pages %
  \fi
  #2,\par
```

```

\ifnum#3=1 %
  1 citation located at page %
\else
  #3 citations located at pages %
\fi
#4.\par
}

\begin{document}

\section{Hello}
\cite{ref1, ref2, ref3, ref4}
\section{World}
\cite{ref1, ref3}
\newpage

\section{Next section}
\cite{ref1}
\newpage

\section{Last section}
\cite{ref1, ref2}
\newpage

\pdfbookmark[1]{Bibliography}{bib}
\begin{thebibliography}{99}
\bibitem{ref1} Dummy entry one.

\bibitem{ref2} Dummy entry two.

\bibitem{ref3} Dummy entry three.

\bibitem{ref4} Dummy entry four.

\end{thebibliography}

\end{document}

```

\phantomsection

Set an anchor at this location. It is often used in conjunction with `\addcontentsline` for sectionlike things (index, bibliography, preface). `\addcontentsline` refers to the latest previous location where an anchor is set.

```

\cleardoublepage
\phantomsection
\addcontentsline{toc}{chapter}{\indexname}
\printindex

```

Now the entry in the table of contents (and bookmarks) for the index points to the start of the index page, not to a location before this page.

\hypercalcbp

See manual.

6 Package Compatibility

Currently only package loading orders are available:

Note: hyperref loads package "nameref" at \begin{document}. Sometimes this is too late, thus this package must be loaded earlier.

algorithm

```
\usepackage{float}
\usepackage{hyperref}
\usepackage[chapter]{algorithm}% eg.
```

amsmath

The environments equation and eqnarray are not supported too well. For example, there can be spacing problems. Consider using the environments that package amsmath provide, e.g. gather for equation. The environment equation can even be redefined to use gather:

```
\usepackage{amsmath}
\let\equation\gather
\let\endequation\endgather
```

amsrefs

Package loading order:

```
\usepackage{hyperref}
\usepackage{amsrefs}
```

arydshln, longtable

Package longtable must be put before hyperref and arydshln, hyperref after arydshln generates an error, thus the resulting package order is then:

```
\usepackage{longtable}
\usepackage{hyperref}
\usepackage{arydshln}
```

babel/magyar.ldf

The old version 2005/03/30 v1.4j will not work. You need at least version 1.5, maintained by P'eter Szab'o, see CTAN:language/hungarian/babel/.

bibentry

Workaround:

```
\makeatletter
\let\saved@bibitem\@bibitem
\makeatother

\usepackage{bibentry}
\usepackage{hyperref}

\begin{document}

\begin{group}
  \makeatletter
  \let\@bibitem\saved@bibitem
  \nobibliography{database}
\end{group}
```

chappg

Package chappg uses \@addtoreset that is redefined by hyperref.
The package order is therefore:

```
\usepackage{hyperref}
\usepackage{chappg}
```

cite

This is from Mike Shell:

```
> cite.sty cannot currently be used with hyperref.
> However, I can do a workaround via:
>
> \makeatletter
> \def\NAT@parse{\typeout{This is a fake Natbib command to fool Hyperref.}}
> \makeatother
>
> \usepackage[hypertex]{hyperref}
>
> so that hyperref will not redefine any of the biblabel stuff - so cite.sty
> will work as normal - although the citations will not be hyperlinked, of
> course (But this may not be an issue for many people).
```

dblacnt

pd1enc.def or puenc.def should be loaded before:

```
\usepackage{hyperref}
\usepackage{dblacnt}
```

 or see entry for "vietnam".

easyeqn

Not compatible, breaks.

ellipsis

This package redefines `\textellipsis`, thus it has to be loaded after package `hyperref` (`pd1enc.def/puenc.def` should be loaded before):

```
\usepackage{hyperref}
\usepackage{ellipsis}
```

float

```
\usepackage{float}
\usepackage{hyperref}
```

- * Several `\caption` commands are not supported inside one float object.
- * Anchor are set at top of the float object, if its style is controlled by `float.sty`.

foiltex

Update to version 2008/01/28 v2.1.4b:
 Since version 6.77a `hyperref` does not hack into `\@begindvi`, it uses package `'atbegshi'` instead, that hooks into `\shipout`. Thus the patch of `'foils.cls'` regarding `hyperref` is now obsolete and causes an undefined error message about `\@hyperfixhead`. This is fixed in `FoilTeX 2.1.4b`.

footnote

This package is not supported, you have to disable `hyperref`'s footnote support by using option `"hyperfootnotes=false"`.

geometry

Driver `'dvipdfm'` and program `'dvipdfm'` might generate a warning:
 Sorry. Too late to change page size
 Then prefer the program `'dvipdfmx'` or use one of the following workarounds to move the `\special` of `geometry` to an earlier location:

```
\documentclass[dvipdfm]{article}% or other classes
\usepackage{atbegshi}
\AtBeginDocument{%
  \let\OrgAtBeginDvi\AtBeginDvi
  \let\AtBeginDvi\AtBeginShipoutFirst
}
\usepackage[
  paperwidth=170mm,
  paperheight=240mm
]{geometry}
\AtBeginDocument{%
  \let\AtBeginDvi\OrgAtBeginDvi
}
\usepackage{hyperref}
```

or

```
\documentclass[dvipdfm]{article}% or other classes
```

```

\usepackage{atbegshi}
\let\AtBeginDvi\AtBeginShipoutFirst
\usepackage[
  paperwidth=170mm,
  paperheight=240mm
]{geometry}
\usepackage{hyperref}

```

IEEEtran.cls

version >= V1.6b (because of \@makecaption, see ChangeLog)

index

version >= 1995/09/28 v4.1 (because of \addcontentsline redefinition)

lastpage

Compatible.

linguex

```

\usepackage{hyperref}
\usepackage{linguex}

```

ltabptch

```

\usepackage{longtable}
\usepackage{ltabptch}
\usepackage{hyperref}

```

minitoc-hyper

This package is obsolete, use the uptodate original package minitoc instead.

multind

```

\usepackage{multind}
\usepackage{hyperref}

```

natbib

```

\usepackage{natbib}
\usepackage{hyperref}

```

nomenc1

* Example for introducing links for the page numbers:
`\renewcommand*{\pagedeclaration}[1]{\unskip, \hyperpage{#1}}`

* For equations the following might work:
`\renewcommand*{\eqdeclaration}[1]{%
 \hyperlink{equation.#1}{(Equation~#1)}%
}`

But the mapping from the equation number to the anchor name is not available in general.

prettyref

```

%%% example for prettyref %%%
\documentclass{article}
\usepackage{prettyref}
\usepackage[pdftex]{hyperref}

%\newreformat{FIG}{Figure~\ref{#1}}% without hyperref
\newreformat{FIG}{\hyperref[{\#1}]{Figure~\ref*{#1}}}

\begin{document}
  This is a reference to \prettyref{FIG:ONE}.
  \newpage
  \begin{figure}
    \caption{This is my figure}
    \label{FIG:ONE}
  \end{figure}
\end{document}
%%% example for prettyref %%%

```

ntheorem

ntheorem-hyper.sty is an old patched version of ntheorem.sty.
 Newer versions of ntheorem know the option hyperref:

```

\usepackage{hyperref}
\usepackage[hyperref]{ntheorem}

```

But there are still unsolved problems (options thref, ...).

setspace

```

\usepackage{setspace}
\usepackage{hyperref}

```

sidecap

Before 2002/05/24 v1.5h:

```

\usepackage{nameref}
\usepackage{hyperref}
\usepackage{sidecap}

```

subfigure

1995/03/06 v2.0:

```

\usepackage{subfigure}
\usepackage{hyperref}
% hypertextnames is set to false.

```

v2.1:

```

\usepackage{nameref}
\usepackage{subfigure}
\usepackage{hyperref}
or
\usepackage{hyperref}
\usepackage{subfigure}

```

v2.1.2:
 please update

v2.1.3:

```
\usepackage{hyperref}
\usepackage{subfigure}
or vice versa?
```

titleref

```
\usepackage{nameref}
\usepackage{titleref}% without usetoc
\usepackage{hyperref}
```

titlesec

"nameref" supports titlesec, but hyperref does not (unsolved is the anchor setting, missing with unnumbered section, perhaps problems with page breaks with numbered ones).

varioref

There are too many problems with varioref. Nobody has time to sort them out. Therefore this package is now unsupported.

Perhaps you are lucky and some of the features of varioref works with the following loading order:

```
\usepackage{nameref}
\usepackage{varioref}
\usepackage{hyperref}
```

Also some babel versions can be problematic. For example, 2005/05/21 v3.8g contains a patch for varioref that breaks the hyperref support for varioref.

Also unsupported:

```
* \Ref, \Vref do not uppercase the first letter.
* \vpageref[]{...}
  On the same page a previous space is not suppressed.
```

verse

Version 2005/08/22 v2.22 contains support for hyperref.

For older versions see example from de.comp.text.tex (2005/08/11, slightly modified):

```
\documentclass{article}

% package order does not matter
\usepackage{verse}
\usepackage{hyperref}

\makeatletter
% make unique poemline anchors
\newcounter{verse@env}
\setcounter{verse@env}{0}
\let\org@verse\verse
\def\verse{%
  \stepcounter{verse@env}%
```

```

\org@verse
}
\def\theHpoemline{\arabic{verse@env}.\thepoemline}

% add anchor for before \addcontentsline in \@vsptitle
\let\org@vsptitle\@vsptitle
\def\@vsptitle{%
  \phantomsection
  \org@vsptitle
}
\makeatother

\begin{document}

\poemtitle{Poem 1}
\begin{verse}
An one-liner.
\end{verse}

\newpage

\poemtitle{Poem 2}
\begin{verse}
Another one-liner.
\end{verse}

\end{document}

```

vietnam

```

% pdlenc.def should be loaded before package dblacnt:
\usepackage[PD1,OT1]{fontenc}
\usepackage{vietnam}
\usepackage{hyperref}

```

7 Limitations

Wrapped/broken link support

Only few drivers support automatically wrapped/broken links, e.g. pdftex, dvipdfm, hypertext. Other drivers lack this feature, e.g. dvips, dvipsone.

Workarounds:

- * For long section or caption titles in the table of contents or list of figures/tables option "linktocpage" can be used. Then the page number will be a link, and the overlong section title is not forced into an one line link with overvull \hbox warning.
- * "\url"s are caught by package "breakurl".
- * The option "breaklinks" is intended for internal use. But it can be used to force link wrapping, e.g. when printing a document. However, when such a document is converted to PDF and viewed with a PDF viewer, the active link area will be misplaced.

Another limitation: some penalties are "optimized" by TeX, thus there are missing break points, especially within `\url`. (See thread "hyperref.sty, breaklinks and url.sty 3.2" in comp.text.tex 2005-09).

8 Hints

Spaces in option values

Unhappily LaTeX strips spaces from options if they are given in `\documentclass` or `\usepackage` (or `\RequirePackage`), e.g.:

```
\usepackage[pdfborder=0 0 1]{hyperref}
```

Package hyperref now gets

```
pdfborder=001
```

and the result is an invalid PDF file.

As workaround braces can be used:

```
\usepackage[pdfborder={0 0 1}]{hyperref}
```

Some options can also be given in `\hypersetup`:

```
\hypersetup[pdfborder=0 0 1]
```

In `\hypersetup` the options are directly processed as key value options (see package keyval) without space stripping in the value part.

Alternatively, LaTeX's option handling system can be adapted to key value options by one of the packages "kvoptions-patch" (from project "kvoptions") or "xkvltxp" (from project "xsetkeys").

Index with makeindex

- * Package hyperref adds `\hyperpage` commands by the encap mechanism (see documentation of Makeindex), if option hyperindex is set (default). `\hyperpage` uses the page anchors that are set by hyperref at each page (default). However in the default case page numbers are used in anchor names in arabic form. If the page numbers in other formats are used (book class with `\frontmatter`, `\romannumbering`, ...), then the page anchors are not unique. Therefore option "plainpages=false" is recommended.
- * The encap mechanism of Makeindex allows to use one command only (see documentation of Makeindex). If the user sets such a command, hyperref suppresses its `\hyperpage` command. With logical markup this situation can easily be solved:


```
\usepackage{makeidx}
\makeindex
\usepackage[hyperindex]{hyperref}
\newcommand*{\main}[1]{\textbf{\hyperpage{#1}}}
...
\index{Some example|main}
```
- * Scientific Word/Scientific Workplace users can use package robustindex with hyperindex=false.
- * Other encap characters can be set by option "encap". Example for use of "?":


```
\usepackage[encap=?]{hyperref}
```
- * An other possibility is the insertion of `\hyperpage` by

a style file for makeindex. For this case, hyperref's insertion will be disabled by "hyperindex=false".
`\hyperpage` will be defined regardless of setting of hyperindex.

```
%%% cut %%% hyperindex.ist %%% cut %%%
delim_0 ", \\\hyperpage{"
delim_1 ", \\\hyperpage{"
delim_2 ", \\\hyperpage{"
delim_n "}, \\\hyperpage{"
delim_t "}"
encap_prefix "}\\\"
encap_infix "{\\hyperpage{"
encap_suffix "}"
%%% cut %%% hyperindex.ist %%% cut %%%
```

Warning "bookmark level for unknown <foobar> defaults to 0"

Getting rid of it:

```
\makeatletter
\providecommand*{\toclevel@<foobar>}{0}
\makeatother
```

Link anchors in figures

The caption command increments the counter and here is the place where hyperref set the corresponding anchor. Unhappily the caption is set below the figure, so the figure is not visible if a link jumps to a figure.

In this cases, try package "hycap.sty" that implements a method to circumvent the problem.

Additional unicode characters in bookmarks and pdf information entries:

```
\documentclass[pdftex]{article}
\usepackage[unicode]{hyperref}

% Support for additional unicode characters:
%
% Example: \.{a} and \d{a}
%
% 1. Get a list with unicode data, eg:
%   http://www.unicode.org/Public/UNIDATA/UnicodeData.txt
%
% 2. Identify the characters (\.{a}, \d{a}):
%
%   0227;LATIN SMALL LETTER A WITH DOT ABOVE;...
%   1EA1;LATIN SMALL LETTER A WITH DOT BELOW;...
%
% 3. Calculate the octal code:
%   The first characters of the line in the file are
%   hex values, convert each byte and prepend them
%   with a backslash. (This will go into the PDF file.)
%
%   0227 -> \002\047
%   1EA1 -> \036\241
```

```
%
% 4. Transform into a form understood by hyperref:
%
%   Hyperref must know where the first byte starts,
%   this is marked by "9" (8 and 9 cannot occur in
%   octal numbers):
%
%   \002\047 -> \9002\047
%   \036\241 -> \9036\241
%
%   Optional: "8" is used for abbreviations:
%   \900 = \80, \901 = \81, \902 = \82, ...
%
%   \9002\047 -> \82\047
%
% 5. Declare the character with LaTeX:
%
\DeclareTextCompositeCommand{\.}{PU}{a}{\82\047}
\DeclareTextCompositeCommand{\d}{PU}{a}{\9036\241}

\begin{document}
\section{\={a}, \d{a}, \'{a}, \.a}
\end{document}
```

Footnotes

The footnote support is rather limited. It is beyond the scope to use `\footnotemark` and `\footnotetext` out of order or reusing `\footnotemark`. Here you can either disable hyperref's footnote support by "hyperfootnotes=false" or fiddle with internal macros, nasty example:

```
\documentclass{article}

\usepackage{hyperref}

\begin{document}

\makeatletter

A%
\footnotemark
\let\saved@Href@A\Hy@footnote@currentHref
% remember link name
B%
\footnotemark
\let\saved@Href@B\Hy@footnote@currentHref
b%
\addtocounter{footnote}{-1}%
\addtocounter{Hfootnote}{-1}% generate the same anchor
\footnotemark
C%
\footnotemark
\let\saved@Href@C\Hy@footnote@currentHref
```

```

\addtocounter{footnote}{-2}%
\let\Hy@footnote@currentHref\saved@Href@A
\footnotetext{AAAA}%
\addtocounter{footnote}{1}%
\let\Hy@footnote@currentHref\saved@Href@B
\footnotetext{BBBBB}%
\addtocounter{footnote}{1}%
\let\Hy@footnote@currentHref\saved@Href@C
\footnotetext{CCCC}%

\end{document}

```

9 Authors/Maintainers

- * Sebastian Rahtz
- * Heiko Oberdiek

10 Bug Reports

A bug report should contain:

- * Comprehensive problem description. This includes error or warning messages.
 - * `\errorcontextlines=\maxdimen` can be added in the TeX code to get more informations in TeX error messages.
 - * Minimal test file that shows the problem, but does not contain any unnecessary packages and code.
 - * Used drivers/programs.
 - * Version information about used packages and programs.
 - * If you are using LaTeX, then add `"\listfiles"`. Then a list of version informations is printed at the end of the LaTeX run.
 - * Please no other files than the minimal test file.

The other files `.log`, `.dvi`, `.ps`, `.pdf` are seldom necessary, so send them only on request.
- Bug address: Heiko Oberdiek <oberdiek@uni-freiburg.de>

Vietnamese part

Responsible for the Vietnamese translations of the

`\autoref` names and `puvnenc.def` are:

Han The Thanh <hanthethanh at gmail.com>

Reinhard Kotucha <reinhard.kotucha at web.de>

Arabic part

Responsible for the additions to PU encoding for Arabi is

Youssef Jabri <yjabri@ensa.univ-oujda.ac.ma>

11 Known Problems

- * (half-done) hyper images (link from thumbnail in text)
- * Relative links are not sorted out or documented well.

For PDF generation:

 - * With `baseurl`: all links are considered relative to this URL.

```

* Without baseurl: a relative link without "file:" can be
  achieved by:
    \begingroup
      \hypersetup{linkfileprefix={}}%
      \href{../foo/bar.html}{bar.html}
    \endgroup
* ...

```

12 **ToDo**

```

* modules
* bookmark organisation
* documentation
* PDF threads
* more for PDF forms
  * per object setting
  * vary gap between text and box
* PostScript driver: the current implementation doesn't rely support
  nested links. The start positions should be remembered in a stack,
  but there are complications with page breaks.
* ...

```

13 **Versions in TeX distributions**

TeX Live

```

* TL 2007:      2007/02/07 v6.75r
* TL 2005:      2003/11/30 v6.74m
* TL 2004:      2003/11/30 v6.75m
* TL 2003:      2003/09/15 v6.74i
* TL 7 (2002):  2002/05/27 v6.72r
* TL 6b (2001): 2001/05/26 v6.71g
* TL 5d (2000): 2000/07/02 v6.70m
* TL 5c (2000): 2000/05/08 v6.70f
* TL 4 (1999):  1999/04/13 v6.56
* TL 3 (1998):  1998/03/25 v6.19

```