

Hypertext marks in L^AT_EX: a manual for `hyperref`

Sebastian Rahtz

Heiko Oberdiek

October 2008

Contents

1	Introduction	1
2	Implicit behavior	3
3	Package options	3
3.1	General options	4
3.2	Configuration options	4
3.3	Backend drivers	5
3.4	Extension options	6
3.5	PDF-specific display options	7
3.6	PDF display and information options	8
3.7	Big alphabetical list	10
4	Additional user macros	12
4.1	Replacement macros	15
4.2	Utility macros	16
5	Acrobat-specific behavior	16
6	PDF and HTML forms	17
6.1	Forms environment parameters	19
6.2	Forms optional parameters	19
7	Defining a new driver	20
8	Special support for other packages	20
9	History and acknowledgments	21
10	GNU Free Documentation License	22

1 Introduction

The package derives from, and builds on, the work of the HyperT_EX project, described at <http://xxx.lanl.gov/hypertext/>. It extends the functionality of all the L^AT_EX cross-referencing commands (including the table of contents, bibliographies etc) to produce `\special` commands which a driver can turn into hypertext links; it also provides new commands to allow the user to write *ad hoc* hypertext links, including those to external documents and URLs.

This manual provides a brief overview of the `hyperref` package. For more details, you should read the additional documentation distributed with the package, as well as the complete documentation by processing `hyperref.dtx`. You should also read the chapter on `hyperref` in *The L^AT_EX Web Companion*, where you will find additional examples.

The HyperT_EX specification¹ says that conformant viewers/translators must recognize the following set of `\special` constructs:

```
href: html:<a href = "href_string">
name: html:<a name = "name_string">
end: html:</a>
image: html:<img src = "href_string">
base_name: html:<base href = "href_string">
```

The *href*, *name* and *end* commands are used to do the basic hypertext operations of establishing links between sections of documents. The *image* command is intended (as with current HTML viewers) to place an image of arbitrary graphical format on the page in the current location. The *base_name* command is be used to communicate to the DVI viewer the full (URL) location of the current document so that files specified by relative URL's may be retrieved correctly.

The *href* and *name* commands must be paired with an *end* command later in the T_EX file—the T_EX commands between the two ends of a pair form an *anchor* in the document. In the case of an *href* command, the *anchor* is to be highlighted in the *DVI viewer*, and when clicked on will cause the scene to shift to the destination specified by *href_string*. The *anchor* associated with a name command represents a possible location to which other hypertext links may refer, either as local references (of the form `href="#name_string"` with the *name_string* identical to the one in the name command) or as part of a URL (of the form `URL#name_string`). Here *href_string* is a valid URL or local identifier, while *name_string* could be any string at all: the only caveat is that ‘”’ characters should be escaped with a backslash (\), and if it looks like a URL name it may cause problems.

However, the drivers intended to produce *only* PDF use literal PostScript or PDF `\special` commands. The commands are defined in configuration files for different drivers, selected by package options; at present, the following drivers are supported:

hypertex DVI processors conforming to the HyperT_EX guidelines (i.e. `xdvi`, `dvips` (with the `-z` option), `OzTeX`, and `Textures`)

dvips produces `\special` commands tailored for `dvips`

dvipsone produces `\special` commands tailored for `dvipsone`

ps2pdf a special case of output suitable for processing by earlier versions of Ghostscript's PDF writer; this is basically the same as that for `dvips`, but a few variations remained before version 5.21

tex4ht produces `\special` commands for use with T_EX4ht

pdftex pdfT_EX, Hàn Thế Thành's T_EX variant that writes PDF directly

dvipdfm produces `\special` commands for Mark Wicks' DVI to PDF driver `dvipdfm`

dvipdfmx produces `\special` commands for driver `dvipdfmx`, a successor of `dvipdfm`

¹This is borrowed from an article by Arthur Smith.

dviwindo produces `\special` commands that Y&Y's Windows previewer interprets as hypertext jumps within the previewer

vtex produces `\special` commands that MicroPress' HTML and PDF-producing T_EX variants interpret as hypertext jumps within the previewer

textures produces `\special` commands that Textures interprets as hypertext jumps within the previewer

xetex produces `\special` commands for XeT_EX

Output from dvips or dvipsone must be processed using Acrobat Distiller to obtain a PDF file.² The result is generally preferable to that produced by using the `hypertex` driver, and then processing with `dvips -z`, but the DVI file is not portable. The main advantage of using the HyperT_EX `\special` commands is that you can also use the document in hypertext DVI viewers, such as `xdvi`.

2 Implicit behavior

This package can be used with more or less any normal L^AT_EX document by specifying in the document preamble

```
\usepackage{hyperref}
```

Make sure it comes *last* of your loaded packages, to give it a fighting chance of not being over-written, since its job is to redefine many L^AT_EX commands. Hopefully you will find that all cross-references work correctly as hypertext. For example, `\section` commands will produce a bookmark and a link, whereas `\section*` commands will only show links when paired with a corresponding `\addcontentsline` command.

In addition, the `hyperindex` option (see below) attempts to make items in the index by hyperlinked back to the text, and the option `backref` inserts extra 'back' links into the bibliography for each entry. Other options control the appearance of links, and give extra control over PDF output. For example, `colorlinks`, as its name well implies, colors the links instead of using boxes; this is the option used in this document.

3 Package options

All user-configurable aspects of `hyperref` are set using a single 'key=value' scheme (using the `keyval` package) with the key `Hyp`. The options can be set either in the optional argument to the `\usepackage` command, or using the `\hypersetup` macro. When the package is loaded, a file `hyperref.cfg` is read if it can be found, and this is a convenient place to set options on a site-wide basis.

As an example, the behavior of a particular file could be controlled by:

- a site-wide `hyperref.cfg` setting up the look of links, adding backreferencing, and setting a PDF display default:

```
\hypersetup{backref,
pdfpagemode=FullScreen,
colorlinks=true}
```

²Make sure you turn off the partial font downloading supported by `dvips` and `dvipsone` in favor of Distiller's own system.

- A global option in the file, which is passed down to `hyperref`:

```
\documentclass[dvips]{article}
```

- File-specific options in the `\usepackage` commands, which override the ones set in `hyperref.cfg`:

```
\usepackage[colorlinks=false]{hyperref}
\hypersetup{pdftitle={A Perfect Day}}
```

As seen in the previous example, information entries (`pdftitle`, `pdfauthor`, ...) should be set after the package is loaded. Otherwise \LaTeX expands the values of these options prematurely. Also \LaTeX strips spaces in options. Especially option ‘`pdfborder`’ requires some care. Curly braces protect the value, if given as package option. They are not necessary in `\hypersetup`.

```
\usepackage[pdfborder={0 0 0}]{hyperref}
\hypersetup{pdfborder=0 0 0}
```

Package ‘`kvoptions-patch`’ patches \LaTeX to make it aware of key value options and to prevent premature value expansions.

Some options can be given at any time, but many are restricted: before `\begin{document}`, only in `\usepackage[...]{hyperref}`, before first use, etc.

In the key descriptions that follow, many options do not need a value, as they default to the value `true` if used. These are the ones classed as ‘boolean’. The values `true` and `false` can always be specified, however.

3.1 General options

Firstly, the options to specify general behavior and page size.

<code>draft</code>	boolean	<i>false</i>	all hypertext options are turned off
<code>final</code>	boolean	<i>true</i>	all hypertext options are turned on
<code>debug</code>	boolean	<i>false</i>	extra diagnostic messages are printed in the log file
<code>verbose</code>	boolean	<i>false</i>	same as <code>debug</code>
<code>implicit</code>	boolean	<i>true</i>	redefines \LaTeX internals
<code>hypertextnames</code>	boolean	<i>true</i>	use guessable names for links
<code>naturalnames</code>	boolean	<i>false</i>	use \LaTeX -computed names for links
<code>a4paper</code>	boolean	<i>true</i>	sets paper size to 210mm \times 297mm
<code>a5paper</code>	boolean	<i>false</i>	sets paper size to 148mm \times 210mm
<code>b5paper</code>	boolean	<i>false</i>	sets paper size to 176mm \times 250mm
<code>letterpaper</code>	boolean	<i>false</i>	sets paper size to 8.5in \times 11in
<code>legalpaper</code>	boolean	<i>false</i>	sets paper size to 8.5in \times 14in
<code>executivepaper</code>	boolean	<i>false</i>	sets paper size to 7.25in \times 10.5in
<code>setpagesize</code>	boolean	<i>true</i>	sets page size by special driver commands

3.2 Configuration options

<code>raiselinks</code>	boolean	<i>true</i>	In the hypertext driver, the height of links is normally calculated by the driver as simply the base line of contained text; this options forces <code>\special</code> commands to reflect the real height of the link (which could contain a graphic)
<code>breaklinks</code>	boolean	<i>false</i>	Allows link text to break across lines; since this cannot be accommodated in PDF, it is only set true by default if the pdftex driver is used. This makes links on multiple lines into different PDF links to the same target.
<code>pageanchor</code>	boolean	<i>true</i>	Determines whether every page is given an implicit anchor at the top left corner. If this is turned off, <code>\printindex</code> will not contain valid hyperlinks.
<code>plainpages</code>	boolean	<i>false</i>	Forces page anchors to be named by the arabic form of the page number, rather than the formatted form.
<code>nesting</code>	boolean	<i>false</i>	Allows links to be nested; no drivers currently support this.

Note for option `breaklinks`: The correct value is automatically set according to the driver features. It can be overwritten for drivers that do not support broken links. However, at any case, the link area will be wrong and displaced.

3.3 Backend drivers

If no driver is specified, the package defaults to loading the `hypertext` driver.

<code>dvipdfm</code>	Sets up <code>hyperref</code> for use with the <code>dvipdfm</code> driver.
<code>dvipdfmx</code>	Sets up <code>hyperref</code> for use with the <code>dvipdfmx</code> driver.
<code>dvips</code>	Sets up <code>hyperref</code> for use with the <code>dvips</code> driver.
<code>dvipsone</code>	Sets up <code>hyperref</code> for use with the <code>dvipsone</code> driver.
<code>dviwindo</code>	Sets up <code>hyperref</code> for use with the <code>dviwindo</code> Windows previewer.
<code>hypertext</code>	Sets up <code>hyperref</code> for use with the HyperTeX-compliant drivers.
<code>latex2html</code>	Redefines a few macros for compatibility with <code>latex2html</code> .
<code>nativepdf</code>	An alias for <code>dvips</code>
<code>pdfmark</code>	An alias for <code>dvips</code>
<code>pdftex</code>	Sets up <code>hyperref</code> for use with the <code>pdftex</code> program.
<code>ps2pdf</code>	Redefines a few macros for compatibility with Ghostscript's PDF writer, otherwise identical to <code>dvips</code> .
<code>tex4ht</code>	For use with <code>TeX4ht</code>
<code>textures</code>	For use with <code>Textures</code>
<code>vtex</code>	For use with MicroPress' <code>VTex</code> ; the PDF and HTML backends are detected automatically.
<code>vtexpdfmark</code>	For use with <code>VTex</code> 's PostScript backend.
<code>xetex</code>	For use with <code>XeTeX</code> (using backend for <code>dvipdfm</code>).

If you use `dviwindo`, you may need to redefine the macro `\wwwbrowser` (the default is `C:\netscape\netscape`) to tell `dviwindo` what program to launch. Thus, users of Internet Explorer might add something like this to `hyperref.cfg`:

```
\renewcommand{wwwbrowser}{C:\string\Program\space
Files\string\Plus!\string\Microsoft\space
Internet\string\iexplore.exe}
```

3.4 Extension options

extension	text		Set the file extension (e.g. dvi) which will be appended to file links created if you use the xr package.
hyperfigures	boolean		Adds ‘backlink’ text to the end of each item in the bibliography, as a list of section numbers. This can only work properly <i>if</i> there is a blank line after each \bibitem. Supported values are section , slide , page , none , or false . If no value is given, section is taken as default.
backref	text	<i>false</i>	
pagebackref	boolean	<i>false</i>	Adds ‘backlink’ text to the end of each item in the bibliography, as a list of page numbers.
hyperindex	boolean	<i>true</i>	Makes the page numbers of index entries into hyperlinks. Relays on unique page anchors (pageanchor , ...)
pageanchors and plainpages=false. hyperfootnotes	boolean	<i>true</i>	Makes the footnote marks into hyperlinks to the footnote text. Easily broken ...
encap			Sets encap character for hyperindex
linktocpage	boolean	<i>false</i>	make page number, not text, be link on TOC, LOF and LOT
breaklinks	boolean	<i>false</i>	allow links to break over lines by making links over multiple lines into PDF links to the same target
colorlinks	boolean	<i>false</i>	Colors the text of links and anchors. The colors chosen depend on the the type of link. At present the only types of link distinguished are citations, page references, URLs, local file references, and other links.
linkcolor	color	<i>red</i>	Color for normal internal links.
anchorcolor	color	<i>black</i>	Color for anchor text.
citecolor	color	<i>green</i>	Color for bibliographical citations in text.
filecolor	color	<i>cyan</i>	Color for URLs which open local files.
menucolor	color	<i>red</i>	Color for Acrobat menu items.
runcolor	color	<i>filecolor</i>	Color for run links (launch annotations).
urlcolor	color	<i>magenta</i>	Color for linked URLs.
frenchlinks	boolean	<i>false</i>	use small caps instead of color for links

Note that all color names must be defined before use, following the normal system of the standard L^AT_EX color package.

3.5 PDF-specific display options

<code>bookmarks</code>	boolean	<i>true</i>	A set of Acrobat bookmarks are written, in a manner similar to the table of contents, requiring two passes of L ^A T _E X. Some postprocessing of the bookmark file (file extension <code>.out</code>) may be needed to translate L ^A T _E X codes, since bookmarks must be written in PDFEncoding. To aid this process, the <code>.out</code> file is not rewritten by L ^A T _E X if it is edited to contain a line <code>\let\WriteBookmarks\relax</code>
<code>bookmarksopen</code>	boolean	<i>false</i>	If Acrobat bookmarks are requested, show them with all the subtrees expanded.
<code>bookmarksopenlevel</code>	parameter		level (<code>\maxdimen</code>) to which bookmarks are open
<code>bookmarksnumbered</code>	boolean	<i>false</i>	If Acrobat bookmarks are requested, include section numbers.
<code>bookmarkstype</code>	text	<i>toc</i>	to specify which ‘toc’ file to mimic
<code>CJKbookmarks</code>	boolean	<i>false</i>	This option should be used to produce CJK bookmarks. Package <code>hyperref</code> supports both normal and preprocessed mode of the CJK package; during the creation of bookmarks, it simply replaces CJK’s macros with special versions which expand to the corresponding character codes. Note that without the ‘unicode’ option of <code>hyperref</code> you get PDF files which actually violate the PDF specification because non-Unicode character codes are used – some PDF readers localized for CJK languages (most notably Acroread itself) support this. Also note that option ‘CJKbookmarks’ cannot be used together with option ‘unicode’. No mechanism is provided to translate non-Unicode bookmarks to Unicode; for portable PDF documents only Unicode encoding should be used.
<code>pdfhighlight</code>	name	<i>/I</i>	How link buttons behave when selected; <i>/I</i> is for inverse (the default); the other possibilities are <i>/N</i> (no effect), <i>/O</i> (outline), and <i>/P</i> (inset highlighting).
<code>citebordercolor</code>	RGB color	<i>0 1 0</i>	The color of the box around citations
<code>filebordercolor</code>	RGB color	<i>0 .5 .5</i>	The color of the box around links to files
<code>linkbordercolor</code>	RGB color	<i>1 0 0</i>	The color of the box around normal links
<code>menubordercolor</code>	RGB color	<i>1 0 0</i>	The color of the box around Acrobat menu links
<code>urlbordercolor</code>	RGB color	<i>0 1 1</i>	The color of the box around links to URLs
<code>runbordercolor</code>	RGB color	<i>0 .7 .7</i>	color of border around ‘run’ links
<code>pdfborder</code>		<i>0 0 1</i>	The style of box around links; defaults to a box with lines of 1pt thickness, but the <code>colorlinks</code> option resets it to produce no border.

Note that the color of link borders can be specified *only* as 3 numbers in the range 0..1, giving an RGB color. You cannot use colors defined in T_EX.

The bookmark commands are stored in a file called *jobname.out*. The file is not processed by L^AT_EX so any markup is passed through. You can postprocess this file as needed; as an aid for this, the *.out* file is not overwritten on the next T_EX run if it is edited to contain the line

```
\let\WriteBookmarks\relax
```

3.6 PDF display and information options

<code>baseurl</code>	URL		Sets the base URL of the PDF document
<code>pdfpagemode</code>	text	<i>empty</i>	Determines how the file is opening in Acrobat; the possibilities are <code>UseNone</code> , <code>UseThumbs</code> (show thumbnails), <code>UseOutlines</code> (show bookmarks), <code>FullScreen</code> , <code>UseOC</code> (PDF 1.5), and <code>UseAttachments</code> (PDF 1.6). If no mode is explicitly chosen, but the bookmarks option is set, <code>UseOutlines</code> is used.
<code>pdftitle</code>	text		Sets the document information Title field
<code>pdfauthor</code>	text		Sets the document information Author field
<code>pdfsubject</code>	text		Sets the document information Subject field
<code>pdfcreator</code>	text		Sets the document information Creator field
<code>pdfproducer</code>	text		Sets the document information Producer field
<code>pdfkeywords</code>	text		Sets the document information Keywords field
<code>pdfview</code>	text	<i>XYZ</i>	Sets the default PDF ‘view’ for each link
<code>pdfstartpage</code>	text	<i>1</i>	Determines on which page the PDF file is opened.
<code>pdfstartview</code>	text	<i>Fit</i>	Set the startup page view
<code>pdfpagescrop</code>	n n n n		Sets the default PDF crop box for pages. This should be a set of four numbers
<code>pdfcenterwindow</code>	boolean	<i>false</i>	position the document window in the center of the screen
<code>pdfdirection</code>	text	<i>empty</i>	direction setting
<code>pdfdisplaydoctitle</code>	boolean	<i>false</i>	display document title instead of file name in title bar
<code>pdfduplex</code>	text	<i>empty</i>	paper handling option for print dialog
<code>pdfffitwindow</code>	boolean	<i>false</i>	resize document window to fit document size
<code>pdflang</code>	text	<i>empty</i>	PDF language identifier (RFC 3066)

<code>pdfmenubar</code>	boolean	<i>true</i>	make PDF viewer's menu bar visible
<code>pdfnewwindow</code>	boolean	<i>false</i>	make links that open another PDF file start a new window
<code>pdfnonfullscreenpagemode</code>	boolean	<i>empty</i>	page mode setting on exiting full-screen mode
<code>pdfnumcopies</code>	integer	<i>empty</i>	number of printed copies
<code>pdfpagelayout</code>	text	<i>empty</i>	set layout of PDF pages
<code>pdfpagelabels</code>	boolean	<i>true</i>	set PDF page labels
<code>pdfpagetransition</code>	text	<i>empty</i>	set PDF page transition style
<code>pdfpicktrackbypdfsize</code>	text	<i>empty</i>	set option for print dialog
<code>pdfprintarea</code>	text	<i>empty</i>	set /PrintArea of viewer preferences
<code>pdfprintclip</code>	text	<i>empty</i>	set /PrintClip of viewer preferences
<code>pdfprintpagerange</code>	n n (n n)*	<i>empty</i>	set /PrintPageRange of viewer preferences
<code>pdfprintscaling</code>	text	<i>empty</i>	page scaling option for print dialog; valid values are None and AppDefault
<code>pdftoolbar</code>	boolean	<i>true</i>	make PDF toolbar visible
<code>pdfviewarea</code>	text	<i>empty</i>	set /ViewArea of viewer preferences
<code>pdfviewclip</code>	text	<i>empty</i>	set /ViewClip of viewer preferences
<code>pdfwindowui</code>	boolean	<i>true</i>	make PDF user interface elements visible
<code>unicode</code>	boolean	<i>false</i>	Unicode encoded PDF strings

Each link in Acrobat carries its own magnification level, which is set using PDF coordinate space, which is not the same as TeX's. The unit is bp and the origin is in the lower left corner. See also `\hypercalcbp` that is explained on page 16. pdfTeX works by supplying default values for XYZ (horizontal \times vertical \times zoom) and FitBH. However, drivers using pdfmark do not supply defaults, so hyperref passes in a value of -32768, which causes Acrobat to set (usually) sensible defaults. The following are possible values for the pdfview and pdfstartview parameters.

XYZ	<i>left top zoom</i>	Sets a coordinate and a zoom factor. If any one is null, the source link value is used. <i>null null null</i> will give the same values as the current page.
Fit		Fits the page to the window.
FitH	<i>top</i>	Fits the width of the page to the window.
FitV	<i>left</i>	Fits the height of the page to the window.
FitR	<i>left bottom right top</i>	Fits the rectangle specified by the four coordinates to the window.
FitB		Fits the page bounding box to the window.
FitBH	<i>top</i>	Fits the width of the page bounding box to the window.
FitBV	<i>left</i>	Fits the height of the page bounding box to the window.

The pdfpagelayout can be one of the following values.

SinglePage	Displays a single page; advancing flips the page
OneColumn	Displays the document in one column; continuous scrolling.
TwoColumnLeft	Displays the document in two columns, odd-numbered pages to the left.

TwoColumnRight	Displays the document in two columns, odd-numbered pages to the right.
TwoPageLeft	Displays two pages, odd-numbered pages to the left (since PDF 1.5).
TwoPageRight	Displays two pages, odd-numbered pages to the right (since PDF 1.5).

Finally, the `pdfpagetransition` can be one of the following values, where `/Di` stands for direction of motion in degrees, generally in 90° steps, `/Dm` is a horizontal (`/H`) or vertical (`/V`) dimension (e.g. `Blinds /Dm /V`), and `/M` is for motion, either in (`/I`) or out (`/O`).

Blinds	<code>/Dm</code>	Multiple lines distributed evenly across the screen sweep in the same direction to reveal the new page.
Box	<code>/M</code>	A box sweeps in or out.
Dissolve		The page image dissolves in a piecemeal fashion to reveal the new page.
Glitter	<code>/Di</code>	Similar to Dissolve, except the effect sweeps across the screen.
Split	<code>/Dm /M</code>	Two lines sweep across the screen to reveal the new page.
Wipe	<code>/Di</code>	A single line sweeps across the screen to reveal the new page.

3.7 Big alphabetical list

The following is a complete listing of available options for `hyperref`, arranged alphabetically.

<code>a4paper</code>		use A4 paper
<code>a5paper</code>		use A5 paper
<code>anchorcolor</code>	<i>black</i>	set color of anchors
<code>b5paper</code>		use B5 paper
<code>backref</code>	<i>false</i>	do bibliographical back references
<code>baseurl</code>	<i>empty</i>	set base URL for document
<code>bookmarks</code>	<i>true</i>	make bookmarks
<code>bookmarksnumbered</code>	<i>false</i>	put section numbers in bookmarks
<code>bookmarksopen</code>	<i>false</i>	open up bookmark tree
<code>bookmarksopenlevel</code>	<code>\maxdimen</code>	level to which bookmarks are open
<code>bookmarkstype</code>	<i>toc</i>	to specify which ‘toc’ file to mimic
<code>breaklinks</code>	<i>false</i>	allow links to break over lines
<code>CJKbookmarks</code>	<i>false</i>	to produce CJK bookmarks
<code>citebordercolor</code>	<i>0 1 0</i>	color of border around cites
<code>citecolor</code>	<i>green</i>	color of citation links
<code>colorlinks</code>	<i>false</i>	color links
	<i>true</i>	(<code>tex4ht</code> , <code>dviwindo</code>)
<code>debug</code>	<i>false</i>	provide details of anchors defined; same as <code>verbose</code>
<code>draft</code>	<i>false</i>	do not do any hyperlinking
<code>dvipdfm</code>		use <code>dvipdfm</code> backend
<code>dvipdfmx</code>		use <code>dvipdfmx</code> backend
<code>dvips</code>		use <code>dvips</code> backend
<code>dvipsone</code>		use <code>dvipsone</code> backend
<code>dviwindo</code>		use <code>dviwindo</code> backend
<code>encap</code>		to set <code>encap</code> character for <code>hyperindex</code>

executivepaper		use executivepaper
extension	<i>dvi</i>	suffix of linked files
filebordercolor	<i>0 .5 .5</i>	color of border around file links
filecolor	<i>cyan</i>	color of file links
final	<i>true</i>	opposite of option draft
frenchlinks	<i>false</i>	use small caps instead of color for links
hyperfigures	<i>false</i>	make figures hyper links
hyperfootnotes	<i>true</i>	set up hyperlinked footnotes
hyperindex	<i>true</i>	set up hyperlinked indices
hypertex		use HyperTeX backend
hypertextnames	<i>true</i>	use guessable names for links
implicit	<i>true</i>	redefine L ^A T _E X internals
latex2html		use L ^A T _E X2HTML backend
legalpaper		use legalpaper
letterpaper		use letterpaper
linkbordercolor	<i>1 0 0</i>	color of border around links
linkcolor	<i>red</i>	color of links
linktocpage	<i>false</i>	make page number, not text, be link on TOC, LOF and LOT
menubordercolor	<i>1 0 0</i>	color of border around menu links
menucolor	<i>red</i>	color for menu links
nativepdf	<i>false</i>	an alias for dvips
naturalnames	<i>false</i>	use L ^A T _E X-computed names for links
nesting	<i>false</i>	allow nesting of links
pageanchor	<i>true</i>	put an anchor on every page
pagebackref	<i>false</i>	backreference by page number
pdfauthor	<i>empty</i>	text for PDF Author field
pdfborder	<i>0 0 1</i>	width of PDF link border
	<i>0 0 0</i>	(colorlinks)
pdfcenterwindow	<i>false</i>	position the document window in the center of the screen
pdfcreator	<i>LaTeX with hyperref package</i>	text for PDF Creator field
pdfdirection	<i>empty</i>	direction setting
pdfdisplaydoctitle	<i>false</i>	display document title instead of file name in title bar
pdfduplex	<i>empty</i>	paper handling option for print dialog
pdf-fitwindow	<i>false</i>	resize document window to fit document size
pdfhighlight	<i>/I</i>	set highlighting of PDF links
pdfkeywords	<i>empty</i>	text for PDF Keywords field
pdflang	<i>empty</i>	PDF language identifier (RFC 3066)
pdfmark	<i>false</i>	an alias for dvips
pdfmenubar	<i>true</i>	make PDF viewer's menu bar visible
pdfnewwindow	<i>false</i>	make links that open another PDF file start a new window
pdfnonfullscreenpagemode	<i>empty</i>	page mode setting on exiting full-screen mode
pdfnumcopies	<i>empty</i>	number of printed copies
pdfpagelayout	<i>empty</i>	set layout of PDF pages
pdfpagemode	<i>empty</i>	set default mode of PDF display

pdfpagelabels	<i>true</i>	set PDF page labels
pdfpagescrop	<i>empty</i>	set crop size of PDF document
pdfpagetransition	<i>empty</i>	set PDF page transition style
pdfpicktrackbypdfsize	<i>empty</i>	set option for print dialog
pdfprintarea	<i>empty</i>	set /PrintArea of viewer preferences
pdfprintclip	<i>empty</i>	set /PrintClip of viewer preferences
pdfprintpagerange	<i>empty</i>	set /PrintPageRange of viewer preferences
pdfprintscaling	<i>empty</i>	page scaling option for print dialog
pdfproducer	<i>empty</i>	text for PDF Producer field
pdfstartpage	<i>1</i>	page at which PDF document opens
pdfstartview	<i>Fit</i>	starting view of PDF document
pdfsubject	<i>empty</i>	text for PDF Subject field
pdfTEX		use pdfTEX backend
pdftitle	<i>empty</i>	text for PDF Title field
pdftoolbar	<i>true</i>	make PDF toolbar visible
pdfview	<i>XYZ</i>	PDF ‘view’ when on link traversal
pdfviewarea	<i>empty</i>	set /ViewArea of viewer preferences
pdfviewclip	<i>empty</i>	set /ViewClip of viewer preferences
pdfwindowui	<i>true</i>	make PDF user interface elements visible
plainpages	<i>false</i>	do page number anchors as plain arabic
ps2pdf		use ps2pdf backend
raiselinks	<i>false</i>	raise up links (for HyperTEX backend)
runbordercolor	<i>0 .7 .7</i>	color of border around ‘run’ links
runcolor	<i>filecolor</i>	color of ‘run’ links
setpagesize	<i>true</i>	set page size by special driver commands
tex4ht		use TEX4ht backend
textures		use Textures backend
unicode	<i>false</i>	Unicode encoded pdf strings
urlbordercolor	<i>0 1 1</i>	color of border around URL links
urlcolor	<i>magenta</i>	color of URL links
verbose	<i>false</i>	be chatty
vtex		use VTeX backend
xetex		use XeTEX backend

4 Additional user macros

If you need to make references to URLs, or write explicit links, the following low-level user macros are provided:

`\href{URL}{text}`

The *text* is made a hyperlink to the *URL*; this must be a full URL (relative to the base URL, if that is defined). The special characters # and ~ do *not* need to be escaped in any way.

`\url{URL}`

Similar to `\href{URL}{\nolinkurl{URL}}`. Depending on the driver `\href` also tries to detect the link type. Thus the result can be a url link, file link, ...

`\nolinkurl{URL}`

Write *URL* in the same way as `\url`, without creating a hyperlink.

`\hyperbaseurl{URL}`

A base *URL* is established, which is prepended to other specified URLs, to make it easier to write portable documents.

`\hyperimage{imageURL}{text}`

The link to the image referenced by the URL is inserted, using *text* as the anchor.

For drivers that produce HTML, the image itself is inserted by the browser, with the *text* being ignored completely.

`\hyperdef{category}{name}{text}`

A target area of the document (the *text*) is marked, and given the name *category.name*

`\hyperref{URL}{category}{name}{text}`

text is made into a link to *URL#category.name*

`\hyperref[label]{text}`

text is made into a link to the same place as `\ref{label}` would be linked.

`\hyperlink{name}{text}`

`\hypertarget{name}{text}`

A simple internal link is created with `\hypertarget`, with two parameters of an anchor *name*, and anchor *text*. `\hyperlink` has two arguments, the name of a hypertext object defined somewhere by `\hypertarget`, and the *text* which be used as the link on the page.

Note that in HTML parlance, the `\hyperlink` command inserts a notional `#` in front of each link, making it relative to the current testdocument; `\href` expects a full URL.

`\phantomsection`

This sets an anchor at this location. It works similar to `\hypertarget{}{}` with an automatically choosen anchor name. Often it is used in conjunction with `\addcontentsline` for sectionlike things (index, bibliography, preface). `\addcontentsline` refers to the latest previous location where an anchor is set. Example:

```
\cleardoublepage
\phantomsection
\addcontentsline{toc}{chapter}{\indexname}
\printindex
```

Now the entry in the table of contents (and bookmarks) for the index points to the start of the index page, not to a location before this page.

`\autoref{label}`

This is a replacement for the usual `\ref` command that places a contextual label in front of the reference. This gives your users a bigger target to click for hyperlinks (e.g. ‘section 2’ instead of merely the number ‘2’).

The label is worked out from the context of the original `\label` command by `hyperref` by using the macros listed below (shown with their default values). The macros can be (re)defined in documents using `\(re)newcommand`; note that some of these macros are already defined in the standard document classes. The mixture of lowercase and uppercase initial letters is deliberate and corresponds to the author’s practice.

For each macro below, `hyperref` checks `*autorefname` before `*name`. For instance, it looks for `\figureautorefname` before `\figurename`.

<i>Macro</i>	<i>Default</i>
<code>\figurename</code>	Figure
<code>\tablename</code>	Table
<code>\partname</code>	Part
<code>\appendixname</code>	Appendix
<code>\equationname</code>	Equation
<code>\itemname</code>	item
<code>\chaptername</code>	chapter
<code>\sectionname</code>	section
<code>\subsectionname</code>	subsection
<code>\subsubsectionname</code>	subsubsection
<code>\paragraphname</code>	paragraph
<code>\Hfootnotename</code>	footnote
<code>\AMSname</code>	Equation
<code>\theoremname</code>	Theorem
<code>\page</code>	page

Example for a redefinition if `babel` is used:

```
\usepackage[ngerman]{babel}
\addto\extrasngerman{%
  \def\subsectionautorefname{Unterkapitel}%
}
```

`\autopageref{label}`

It replaces `\pageref` and adds the name for page in front of the page reference. First `\pageautorefname` is checked before `\pagename`.

For instances where you want a reference to use the correct counter, but not to create a link, there are starred forms:

`\ref*{label}`

`\pageref*{label}`

`\autoref*{label}`

`\autopageref*{label}`

A typical use would be to write

```
\hyperref[other]{that nice section (\ref*{other}) we read before}
```

We want `\ref*{other}` to generate the correct number, but not to form a link, since we do this ourselves with `\hyperref`.

`\pdfstringdef{macroname}{TeXstring}`

`\pdfstringdef` returns a macro containing the PDF string. (Currently this is done globally, but do not rely on it.) All the following tasks, definitions and redefinitions are made in a group to keep them local:

- Switching to PD1 or PU encoding
- Defining the “octal sequence commands” (\345): `\edef\3{\string\3}`
- Special glyphs of T_EX: `\{`, `\%`, `\&`, `\space`, `\dots`, etc.
- National glyphs (`german.sty`, `french.sty`, etc.)
- Logos: `\TeX`, `\eTeX`, `\MF`, etc.
- Disabling commands that do not provide useful functionality in bookmarks: `\label`, `\index`, `\glossary`, `\discretionary`, `\def`, `\let`, etc.
- L^AT_EX’s font commands like `\textbf`, etc.
- Support for `\xspace` provided by the `xspace` package

In addition, parentheses are protected to avoid the danger of unsafe unbalanced parentheses in the PDF string. For further details, see Heiko Oberdiek’s EuroT_EX paper distributed with `hyperref`.

4.1 Replacement macros

`hyperref` takes the text for bookmarks from the arguments of commands like `\section`, which can contain things like math, colors, or font changes, none of which will display in bookmarks as is.

`\texorpdfstring{TeXstring}{PDFstring}`

For example,

```

\section{Pythagoras:
  \texorpdfstring{$ a^2 + b^2 = c^2 $}{%
    a\texttt{two}superior\ + b\texttt{two}superior\ =
    c\texttt{two}superior
  }%
}
\section{\texorpdfstring{\textcolor{red}}{}{Red} Mars}

```

`\pdfstringdef` executes the hook before it expands the string. Therefore, you can use this hook to perform additional tasks or to disable additional commands.

```

\expandafter\def\expandafter\pdfstringdefPreHook
\expandafter{%
  \pdfstringdefPreHook
  \renewcommand{\mycommand}[1]{}%
}

```

However, for disabling commands, an easier way is via `\pdfstringdefDisableCommands`, which adds its argument to the definition of `\pdfstringdefPreHook` (`@` can here be used as letter in command names):

```

\pdfstringdefDisableCommands{%
  \let~\textasciitilde
  \def\url{\pdfstringdefwarn\url}%
  \let\textcolor@gobble
}

```

4.2 Utility macros

`\hypercalsbp{dimen specification}`

`\hypercalsbp` takes a \TeX `dimen` specification and converts it to `bp` and returns the number without the unit. This is useful for options `pdfstartview` and `pdfview`. Example:

```

\hypersetup{
  pdfstartview={FitBH \hypercalsbp{\paperheight-\topmargin-1in
    -\headheight-\headsep}
}

```

The origin of the PDF coordinate system is the lower left corner.

Note, for calculations you need either package `|calc|` or ε - \TeX . Nowadays the latter should automatically be enabled for \LaTeX formats. Users without ε - \TeX , please, look in the source documentation `hyperref.dtx` for further limitations.

Also `\hypercalsbp` cannot be used in option specifications of `\documentclass` and `\usepackage`, because \LaTeX expands the option lists of these commands. However package `hyperref` is not yet loaded and an undefined control sequence error would arise.

5 Acrobat-specific behavior

If you want to access the menu options of Acrobat Reader or Exchange, the following macro is provided in the appropriate drivers:

<code>\Acrobatmenu{menuoption}{text}</code>

The *text* is used to create a button which activates the appropriate *menuoption*. The following table lists the option names you can use—comparison of this with the menus in Acrobat Reader or Exchange will show what they do. Obviously some are only appropriate to Exchange.

File	Open, Close, Scan, Save, SaveAs, Optimizer:SaveAsOpt, Print, PageSetup, Quit
File→Import	ImportImage, ImportNotes, AcroForm:ImportFDF
File→Export	ExportNotes, AcroForm:ExportFDF
File→DocumentInfo	GeneralInfo, OpenInfo, FontsInfo, SecurityInfo, Weblink:Base, AutoIndex:DocInfo
File→Preferences	GeneralPrefs, NotePrefs, FullScreenPrefs, Weblink:Prefs, AcroSearch:Preferences(Windows) or, AcroSearch:Prefs(Mac), Cpt:Capture
Edit	Undo, Cut, Copy, Paste, Clear, SelectAll, Ole:CopyFile, TouchUp:TextAttributes, TouchUp:FitTextToSelection, TouchUp:ShowLineMarkers, TouchUp:ShowCaptureSuspects, TouchUp:FindSuspect, Properties
Edit→Fields	AcroForm:Duplicate, AcroForm:TabOrder
Document	Cpt:CapturePages, AcroForm:Actions, CropPages, RotatePages, InsertPages, ExtractPages, ReplacePages, DeletePages, NewBookmark, SetBookmarkDest, CreateAllThumbs, DeleteAllThumbs
View	ActualSize, FitVisible, FitWidth, FitPage, ZoomTo, FullScreen, FirstPage, PrevPage, NextPage, LastPage, GoToPage, GoBack, GoForward, SinglePage, OneColumn, TwoColumns, ArticleThreads, PageOnly, ShowBookmarks, ShowThumbs
Tools	Hand, ZoomIn, ZoomOut, SelectText, SelectGraphics, Note, Link, Thread, AcroForm:Tool, Acro_Movie:MoviePlayer, TouchUp:TextTool, Find, FindAgain, FindNextNote, CreateNotesFile
Tools→Search	AcroSrch:Query, AcroSrch:Indexes, AcroSrch:Results, AcroSrch:Assist, AcroSrch:PrevDoc, AcroSrch:PrevHit, AcroSrch:NextHit, AcroSrch:NextDoc
Window	ShowHideToolBar, ShowHideMenuBar, ShowHideClipboard, Cascade, TileHorizontal, TileVertical, CloseAll
Help	HelpUserGuide, HelpTutorial, HelpExchange, HelpScan, HelpCapture, HelpPDFWriter, HelpDistiller, HelpSearch, HelpCatalog, HelpReader, Weblink:Home
Help(Windows)	About

6 PDF and HTML forms

You must put your fields inside a **Form** environment (only one per file).

There are six macros to prepare fields:

```
\TextField[parameters]{label}
```

```
\CheckBox[parameters]{label}
```

```
\ChoiceMenu[parameters]{label}{choices}
```

```
\PushButton[parameters]{label}
```

```
\Submit[parameters]{label}
```

```
\Reset[parameters]{label}
```

The way forms and their labels are laid out is determined by:

```
\LayoutTextField{label}{field}
```

```
\LayoutChoiceField{label}{field}
```

```
\LayoutCheckField{label}{field}
```

These macros default to #1 #2

What is actually shown in as the field is determined by:

```
\MakeRadioField{width}{height}
```

```
\MakeCheckField{width}{height}
```

```
\MakeTextField{width}{height}
```

```
\MakeChoiceField{width}{height}
```

```
\MakeButtonField{text}
```

These macros default to \vbox to #2{\hbox to #1{\hfill}\vfill}, except the last, which defaults to #1; it is used for buttons, and the special \Submit and \Reset macros.

You may also want to redefine the following macros:

```

\def\DefaultHeightofSubmit{12pt}
\def\DefaultWidthofSubmit{2cm}
\def\DefaultHeightofReset{12pt}
\def\DefaultWidthofReset{2cm}
\def\DefaultHeightofCheckBox{0.8\baselineskip}
\def\DefaultWidthofCheckBox{0.8\baselineskip}
\def\DefaultHeightofChoiceMenu{0.8\baselineskip}
\def\DefaultWidthofChoiceMenu{0.8\baselineskip}
\def\DefaultHeightofText{\baselineskip}
\def\DefaultHeightofTextMultiline{4\baselineskip}
\def\DefaultWidthofText{3cm}

```

6.1 Forms environment parameters

<code>action</code>	<i>URL</i>	The URL that will receive the form data if a <code>Submit</code> button is included in the form
<code>encoding</code>	<i>name</i>	The encoding for the string set to the URL; FDF-encoding is usual, and <code>html</code> is the only valid value
<code>method</code>	<i>name</i>	Used only when generating HTML; values can be <code>post</code> or <code>get</code>

6.2 Forms optional parameters

Note that all colors must be expressed as RGB triples, in the range 0..1 (i.e. `color=0 0 0.5`)

<code>accesskey</code>	<i>key</i>	(as per HTML)
<code>align</code>	<i>number</i> <i>0</i>	alignment within text field; 0 is left-aligned, 1 is centered, 2 is right-aligned.
<code>backgroundcolor</code>		color of box
<code>bordercolor</code>		color of border
<code>bordersep</code>		box border gap
<code>borderwidth</code>		width of box border
<code>calculate</code>		JavaScript code to calculate the value of the field
<code>charsize</code>	<i>dimen</i>	font size of field text
<code>checked</code>	<i>boolean</i> <i>false</i>	whether option selected by default
<code>color</code>		color of text in box
<code>combo</code>	<i>boolean</i> <i>false</i>	choice list is 'combo' style
<code>default</code>		default value
<code>disabled</code>	<i>boolean</i> <i>false</i>	field disabled
<code>format</code>		JavaScript code to format the field
<code>height</code>	<i>dimen</i>	height of field box
<code>hidden</code>	<i>boolean</i> <i>false</i>	field hidden
<code>ketstroke</code>		JavaScript code to control the keystrokes on entry
<code>maxlen</code>	<i>number</i> <i>0</i>	number of characters allowed in text field
<code>menulength</code>	<i>number</i> <i>4</i>	number of elements shown in list
<code>multiline</code>	<i>boolean</i> <i>false</i>	whether text box is multiline
<code>name</code>	<i>name</i>	name of field (defaults to label)
<code>onblur</code>		JavaScript code
<code>onchange</code>		JavaScript code
<code>onclick</code>		JavaScript code
<code>ondblclick</code>		JavaScript code

onfocus			JavaScript code
onkeydown			JavaScript code
onkeypress			JavaScript code
onkeyup			JavaScript code
onmousedown			JavaScript code
onmousemove			JavaScript code
onmouseout			JavaScript code
onmouseover			JavaScript code
onmouseup			JavaScript code
onselect			JavaScript code
password	boolean	<i>false</i>	text field is ‘password’ style
popdown	boolean	<i>false</i>	choice list is ‘popdown’ style
radio	boolean	<i>false</i>	choice list is ‘radio’ style
readonly	boolean	<i>false</i>	field is readonly
rotation	number	<i>0</i>	rotation of the widget annotation (degree, counterclockwise, multiple of 90)
tabkey			(as per HTML)
validate			JavaScript code to validate the entry
value			initial value
width	dimen		width of field box

7 Defining a new driver

A hyperref driver has to provide definitions for eight macros:

1. `\hyper@anchor`
2. `\hyper@link`
3. `\hyper@linkfile`
4. `\hyper@linkurl`
5. `\hyper@anchorstart`
6. `\hyper@anchorend`
7. `\hyper@linkstart`
8. `\hyper@linkend`

The draft option defines the macros as follows

```
\let\hyper@@anchor\@gobble
\gdef\hyper@link##1##2##3{##3}%
\def\hyper@linkurl##1##2{##1}%
\def\hyper@linkfile##1##2##3{##1}%
\let\hyper@anchorstart\@gobble
\let\hyper@anchorend\@empty
\let\hyper@linkstart\@gobbletwo
\let\hyper@linkend\@empty
```

8 Special support for other packages

hyperref aims to cooperate with other packages, but there are several possible sources for conflict, such as

- Packages that manipulate the bibliographic mechanism. Peter William’s `harvard` package is supported. However, the recommended package is Patrick Daly’s `natbib` package that has specific hyperref hooks to allow reliable interaction. This package covers a very wide variety of layouts and citation styles, all of which work with hyperref.

- Packages that typeset the contents of the `\label` and `\ref` macros, such as `showkeys`. Since the `hyperref` package redefines these commands, you must set `implicit=false` for these packages to work.
- Packages that do anything serious with the index.

The `hyperref` package is distributed with variants on two useful packages designed to work especially well with it. These are `xr` and `minitoc`, which support crossdocument links using L^AT_EX's normal `\label/\ref` mechanisms and per-chapter tables of contents, respectively.

9 History and acknowledgments

The original authors of `hyperbasics.tex` and `hypertex.sty`, from which this package descends, are Tanmoy Bhattacharya (tanmoy@qcd.lanl.gov) and Thorsten Ohl (thorsten.ohl@physik.th-darmstadt.de). `hyperref` started as a simple port of their work to L^AT_EX 2_ε standards, but eventually I rewrote nearly everything, because I didn't understand a lot of the original, and was only interested in getting it to work with L^AT_EX. I would like to thank Arthur Smith, Tanmoy Bhattacharya, Mark Doyle, Paul Ginsparg, David Carlisle, T. V. Raman and Leslie Lamport for comments, requests, thoughts and code to get the package into its first useable state. Various other people are mentioned at the point in the source where I had to change the code in later versions because of problems they found.

Tanmoy found a great many of the bugs, and (even better) often provided fixes, which has made the package more robust. The days spent on Rev_TE_X are entirely due to him! The investigations of Bill Moss (bmoss@math.clemson.edu) into the later versions including native PDF support uncovered a good many bugs, and his testing is appreciated. Hans Hagen (pragma@pi.net) provided a lot of insight into PDF.

Berthold Horn provided help, encouragement and sponsorship for the `dvipsone` and `dviwindo` drivers. Sergey Lesenko provided the changes needed for `dvipdf`, and Hàn Thế Thành supplied all the information needed for `pdftex`. Patrick Daly kindly updated his `natbib` package to allow easy integration with `hyperref`. Michael Mehlich's `hyper` package (developed in parallel with `hyperref`) showed me solutions for some problems. Hopefully the two packages will combine one day.

The forms creation section owes a great deal to: T. V. Raman, for encouragement, support and ideas; Thomas Merz, whose book *Web Publishing with Acrobat/PDF* provided crucial insights; D. P. Story, whose detailed article about pdfmarks and forms solved many practical problems; and Hans Hagen, who explained how to do it in `pdftex`.

Steve Dandy recreated the manual source in July 2003 after it had been lost.

Especial extra thanks to David Carlisle for the `backref` module, the `ps2pdf` and `dviwindo` support, frequent general rewrites of my bad code, and for working on changes to the `xr` package to suit `hyperref`.

10 GNU Free Documentation License

Version 1.2, November 2002

Copyright © 2000,2001,2002 Free Software Foundation, Inc.

59 Temple Place, Suite 330, Boston, MA 02111-1307 USA

Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

Preamble

The purpose of this License is to make a manual, textbook, or other functional and useful document “free” in the sense of freedom: to assure everyone the effective freedom to copy and redistribute it, with or without modifying it, either commercially or noncommercially. Secondly, this License preserves for the author and publisher a way to get credit for their work, while not being considered responsible for modifications made by others.

This License is a kind of “copyleft”, which means that derivative works of the document must themselves be free in the same sense. It complements the GNU General Public License, which is a copyleft license designed for free software.

We have designed this License in order to use it for manuals for free software, because free software needs free documentation: a free program should come with manuals providing the same freedoms that the software does. But this License is not limited to software manuals; it can be used for any textual work, regardless of subject matter or whether it is published as a printed book. We recommend this License principally for works whose purpose is instruction or reference.

10.1 Applicability and definitions

This License applies to any manual or other work, in any medium, that contains a notice placed by the copyright holder saying it can be distributed under the terms of this License. Such a notice grants a world-wide, royalty-free license, unlimited in duration, to use that work under the conditions stated herein. The “Document”, below, refers to any such manual or work. Any member of the public is a licensee, and is addressed as “you”. You accept the license if you copy, modify or distribute the work in a way requiring permission under copyright law.

A “Modified Version” of the Document means any work containing the Document or a portion of it, either copied verbatim, or with modifications and/or translated into another language.

A “Secondary Section” is a named appendix or a front-matter section of the Document that deals exclusively with the relationship of the publishers or authors of the Document to the Document’s overall subject (or to related matters) and contains nothing that could fall directly within that overall subject. (Thus, if the Document is in part a textbook of mathematics, a Secondary Section may not explain any mathematics.) The relationship could be a matter of historical connection with the subject or with related matters, or of legal, commercial, philosophical, ethical or political position regarding them.

The “Invariant Sections” are certain Secondary Sections whose titles are designated, as being those of Invariant Sections, in the notice that says that the Document is released under this License. If a section does not fit the above definition of Secondary then it is not allowed to be designated as Invariant. The Document may contain zero Invariant Sections. If the Document does not identify any Invariant Sections then there are none.

The “Cover Texts” are certain short passages of text that are listed, as Front-Cover Texts or Back-Cover Texts, in the notice that says that the Document is released under this License. A Front-Cover Text may be at most 5 words, and a Back-Cover Text may be at most 25 words.

A “Transparent” copy of the Document means a machine-readable copy, represented in a format whose specification is available to the general public, that is suitable for revising the

document straightforwardly with generic text editors or (for images composed of pixels) generic paint programs or (for drawings) some widely available drawing editor, and that is suitable for input to text formatters or for automatic translation to a variety of formats suitable for input to text formatters. A copy made in an otherwise Transparent file format whose markup, or absence of markup, has been arranged to thwart or discourage subsequent modification by readers is not Transparent. An image format is not Transparent if used for any substantial amount of text. A copy that is not “Transparent” is called “Opaque”.

Examples of suitable formats for Transparent copies include plain ASCII without markup, Texinfo input format, L^AT_EX input format, SGML or XML using a publicly available DTD, and standard-conforming simple HTML, PostScript or PDF designed for human modification. Examples of transparent image formats include PNG, XCF and JPG. Opaque formats include proprietary formats that can be read and edited only by proprietary word processors, SGML or XML for which the DTD and/or processing tools are not generally available, and the machine-generated HTML, PostScript or PDF produced by some word processors for output purposes only.

The “Title Page” means, for a printed book, the title page itself, plus such following pages as are needed to hold, legibly, the material this License requires to appear in the title page. For works in formats which do not have any title page as such, “Title Page” means the text near the most prominent appearance of the work’s title, preceding the beginning of the body of the text.

A section “Entitled XYZ” means a named subunit of the Document whose title either is precisely XYZ or contains XYZ in parentheses following text that translates XYZ in another language. (Here XYZ stands for a specific section name mentioned below, such as “Acknowledgements”, “Dedications”, “Endorsements”, or “History”.) To “Preserve the Title” of such a section when you modify the Document means that it remains a section “Entitled XYZ” according to this definition.

The Document may include Warranty Disclaimers next to the notice which states that this License applies to the Document. These Warranty Disclaimers are considered to be included by reference in this License, but only as regards disclaiming warranties: any other implication that these Warranty Disclaimers may have is void and has no effect on the meaning of this License.

10.2 Verbatim copying

You may copy and distribute the Document in any medium, either commercially or noncommercially, provided that this License, the copyright notices, and the license notice saying this License applies to the Document are reproduced in all copies, and that you add no other conditions whatsoever to those of this License. You may not use technical measures to obstruct or control the reading or further copying of the copies you make or distribute. However, you may accept compensation in exchange for copies. If you distribute a large enough number of copies you must also follow the conditions in section 10.3.

You may also lend copies, under the same conditions stated above, and you may publicly display copies.

10.3 Copying in quantity

If you publish printed copies (or copies in media that commonly have printed covers) of the Document, numbering more than 100, and the Document’s license notice requires Cover Texts, you must enclose the copies in covers that carry, clearly and legibly, all these Cover Texts: Front-Cover Texts on the front cover, and Back-Cover Texts on the back cover. Both covers must also clearly and legibly identify you as the publisher of these copies. The front cover must present the full title with all words of the title equally prominent and visible. You may add other material on the covers in addition. Copying with changes limited to the covers, as long as they preserve the title of the Document and satisfy these conditions, can be treated as verbatim copying in other respects.

If the required texts for either cover are too voluminous to fit legibly, you should put the first ones listed (as many as fit reasonably) on the actual cover, and continue the rest onto adjacent pages.

If you publish or distribute Opaque copies of the Document numbering more than 100, you must either include a machine-readable Transparent copy along with each Opaque copy, or state in or with each Opaque copy a computer-network location from which the general network-using public has access to download using public-standard network protocols a complete Transparent copy of the Document, free of added material. If you use the latter option, you must take reasonably prudent steps, when you begin distribution of Opaque copies in quantity, to ensure that this Transparent copy will remain thus accessible at the stated location until at least one year after the last time you distribute an Opaque copy (directly or through your agents or retailers) of that edition to the public.

It is requested, but not required, that you contact the authors of the Document well before redistributing any large number of copies, to give them a chance to provide you with an updated version of the Document.

10.4 Modifications

You may copy and distribute a Modified Version of the Document under the conditions of sections 10.2 and 10.3 above, provided that you release the Modified Version under precisely this License, with the Modified Version filling the role of the Document, thus licensing distribution and modification of the Modified Version to whoever possesses a copy of it. In addition, you must do these things in the Modified Version:

- A. Use in the Title Page (and on the covers, if any) a title distinct from that of the Document, and from those of previous versions (which should, if there were any, be listed in the History section of the Document). You may use the same title as a previous version if the original publisher of that version gives permission.
- B. List on the Title Page, as authors, one or more persons or entities responsible for authorship of the modifications in the Modified Version, together with at least five of the principal authors of the Document (all of its principal authors, if it has fewer than five), unless they release you from this requirement.
- C. State on the Title page the name of the publisher of the Modified Version, as the publisher.
- D. Preserve all the copyright notices of the Document.
- E. Add an appropriate copyright notice for your modifications adjacent to the other copyright notices.
- F. Include, immediately after the copyright notices, a license notice giving the public permission to use the Modified Version under the terms of this License, in the form shown in the Addendum below.
- G. Preserve in that license notice the full lists of Invariant Sections and required Cover Texts given in the Document's license notice.
- H. Include an unaltered copy of this License.
- I. Preserve the section Entitled "History", Preserve its Title, and add to it an item stating at least the title, year, new authors, and publisher of the Modified Version as given on the Title Page. If there is no section Entitled "History" in the Document, create one stating the title, year, authors, and publisher of the Document as given on its Title Page, then add an item describing the Modified Version as stated in the previous sentence.

- J. Preserve the network location, if any, given in the Document for public access to a Transparent copy of the Document, and likewise the network locations given in the Document for previous versions it was based on. These may be placed in the “History” section. You may omit a network location for a work that was published at least four years before the Document itself, or if the original publisher of the version it refers to gives permission.
- K. For any section Entitled “Acknowledgements” or “Dedications”, Preserve the Title of the section, and preserve in the section all the substance and tone of each of the contributor acknowledgements and/or dedications given therein.
- L. Preserve all the Invariant Sections of the Document, unaltered in their text and in their titles. Section numbers or the equivalent are not considered part of the section titles.
- M. Delete any section Entitled “Endorsements”. Such a section may not be included in the Modified Version.
- N. Do not retitle any existing section to be Entitled “Endorsements” or to conflict in title with any Invariant Section.
- O. Preserve any Warranty Disclaimers.

If the Modified Version includes new front-matter sections or appendices that qualify as Secondary Sections and contain no material copied from the Document, you may at your option designate some or all of these sections as invariant. To do this, add their titles to the list of Invariant Sections in the Modified Version’s license notice. These titles must be distinct from any other section titles.

You may add a section Entitled “Endorsements”, provided it contains nothing but endorsements of your Modified Version by various parties—for example, statements of peer review or that the text has been approved by an organization as the authoritative definition of a standard.

You may add a passage of up to five words as a Front-Cover Text, and a passage of up to 25 words as a Back-Cover Text, to the end of the list of Cover Texts in the Modified Version. Only one passage of Front-Cover Text and one of Back-Cover Text may be added by (or through arrangements made by) any one entity. If the Document already includes a cover text for the same cover, previously added by you or by arrangement made by the same entity you are acting on behalf of, you may not add another; but you may replace the old one, on explicit permission from the previous publisher that added the old one.

The author(s) and publisher(s) of the Document do not by this License give permission to use their names for publicity for or to assert or imply endorsement of any Modified Version.

10.5 Combining documents

You may combine the Document with other documents released under this License, under the terms defined in section 10.4 above for modified versions, provided that you include in the combination all of the Invariant Sections of all of the original documents, unmodified, and list them all as Invariant Sections of your combined work in its license notice, and that you preserve all their Warranty Disclaimers.

The combined work need only contain one copy of this License, and multiple identical Invariant Sections may be replaced with a single copy. If there are multiple Invariant Sections with the same name but different contents, make the title of each such section unique by adding at the end of it, in parentheses, the name of the original author or publisher of that section if known, or else a unique number. Make the same adjustment to the section titles in the list of Invariant Sections in the license notice of the combined work.

In the combination, you must combine any sections Entitled “History” in the various original documents, forming one section Entitled “History”; likewise combine any sections Entitled “Acknowledgements”, and any sections Entitled “Dedications”. You must delete all sections Entitled “Endorsements”.

10.6 Collections of documents

You may make a collection consisting of the Document and other documents released under this License, and replace the individual copies of this License in the various documents with a single copy that is included in the collection, provided that you follow the rules of this License for verbatim copying of each of the documents in all other respects.

You may extract a single document from such a collection, and distribute it individually under this License, provided you insert a copy of this License into the extracted document, and follow this License in all other respects regarding verbatim copying of that document.

10.7 Aggregation with independent works

A compilation of the Document or its derivatives with other separate and independent documents or works, in or on a volume of a storage or distribution medium, is called an “aggregate” if the copyright resulting from the compilation is not used to limit the legal rights of the compilation’s users beyond what the individual works permit. When the Document is included in an aggregate, this License does not apply to the other works in the aggregate which are not themselves derivative works of the Document.

If the Cover Text requirement of section 10.3 is applicable to these copies of the Document, then if the Document is less than one half of the entire aggregate, the Document’s Cover Texts may be placed on covers that bracket the Document within the aggregate, or the electronic equivalent of covers if the Document is in electronic form. Otherwise they must appear on printed covers that bracket the whole aggregate.

10.8 Translation

Translation is considered a kind of modification, so you may distribute translations of the Document under the terms of section 10.4. Replacing Invariant Sections with translations requires special permission from their copyright holders, but you may include translations of some or all Invariant Sections in addition to the original versions of these Invariant Sections. You may include a translation of this License, and all the license notices in the Document, and any Warranty Disclaimers, provided that you also include the original English version of this License and the original versions of those notices and disclaimers. In case of a disagreement between the translation and the original version of this License or a notice or disclaimer, the original version will prevail.

If a section in the Document is Entitled “Acknowledgements”, “Dedications”, or “History”, the requirement (section 10.4) to Preserve its Title (section 10.1) will typically require changing the actual title.

10.9 Termination

You may not copy, modify, sublicense, or distribute the Document except as expressly provided for under this License. Any other attempt to copy, modify, sublicense or distribute the Document is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

10.10 Future revisions of this license

The Free Software Foundation may publish new, revised versions of the GNU Free Documentation License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns. See <http://www.gnu.org/copyleft/>.

Each version of the License is given a distinguishing version number. If the Document specifies that a particular numbered version of this License “or any later version” applies to it, you have the option of following the terms and conditions either of that specified version or of any later version that has been published (not as a draft) by the Free Software Foundation. If the Document does not specify a version number of this License, you may choose any version ever published (not as a draft) by the Free Software Foundation.

Addendum: how to use this license for your documents

To use this License in a document you have written, include a copy of the License in the document and put the following copyright and license notices just after the title page:

Copyright © YEAR YOUR NAME. Permission is granted to copy, distribute and/or modify this document under the terms of the GNU Free Documentation License, Version 1.2 or any later version published by the Free Software Foundation; with no Invariant Sections, no Front-Cover Texts, and no Back-Cover Texts. A copy of the license is included in the section entitled “GNU Free Documentation License”.

If you have Invariant Sections, Front-Cover Texts and Back-Cover Texts, replace the “with...Texts.” line with this:

with the Invariant Sections being LIST THEIR TITLES, with the Front-Cover Texts being LIST, and with the Back-Cover Texts being LIST.

If you have Invariant Sections without Cover Texts, or some other combination of the three, merge those two alternatives to suit the situation.

If your document contains nontrivial examples of program code, we recommend releasing these examples in parallel under your choice of free software license, such as the GNU General Public License, to permit their use in free software.