

# Section name references in L<sup>A</sup>T<sub>E</sub>X<sup>\*</sup>

Sebastian Rahtz

2007/05/29

## Documentation overview for hyperref

The documentation for package `hyperref` consists of several files:

**Manual** The **USER MANUAL** (also available as HTML).

**README** The **README** file (also available as text file). Here information is collected that is not yet in the manual: new features, package compatibility, limitations, known problems, ...

**ChangeLog** This file records the version history (also available as text file).

**Options** This file provides a short option summary.

**Bookmark talk, slides** Slides for the talk “PDF information and navigation elements with hyperref, pdfTeX and thumbpdf” at EuroT<sub>E</sub>X 1999.

**Bookmark talk, paper** The paper version of the talk.

Source code documentation:

**hyperref.dtx** This is the source code documentation for hyperref (this file).

**backref.dtx** “Back referencing from bibliographical citations”

**nameref.dtx** “Section name references in L<sup>A</sup>T<sub>E</sub>X”

## Contents

|          |  |          |
|----------|--|----------|
| <b>1</b> | <b>Introduction</b>                                | <b>2</b> |
| <b>2</b> | <b>History</b>                                     | <b>2</b> |
| <b>3</b> | <b>Implementation</b>                              | <b>2</b> |
| 3.1      | <code>\label</code> stuff . . . . .                | 2        |
| 3.2      | Changes of section macros . . . . .                | 4        |
| 3.2.1    | Class beamer . . . . .                             | 5        |
| 3.3      | Referencing stuff . . . . .                        | 6        |
| 3.4      | Usage and frontend . . . . .                       | 7        |
| 3.5      | Package ifthen support . . . . .                   | 7        |
| 3.6      | Compatibility with <code>varioref</code> . . . . . | 8        |
| 3.7      | Support for listings . . . . .                     | 10       |

---

<sup>\*</sup>This file has version number v2.31, last revised 2007/05/29.

## 1 Introduction

Cross-referencing to include the *name* of the section, rather than just the number or page. This works by redefining some of the inside L<sup>A</sup>T<sub>E</sub>X macros, so it is vulnerable to future changes.

## 2 History

Sebastian Rahtz, for Lou Burnard, March 15th 1994;  
 SPQR CERN July 1994;  
 Last mod. Sept. 3th MG;  
 Sept. 19th SPQR;  
 April 11th 1995 SPQR (added section formatting hook);  
 April 14th 1995 SPQR (compatibility with hyperref);  
 June 22 1995 SPQR (removed typeout from Sectionformat);  
 September 22 1997 added varioref hacks by Corey Minyard;  
 September 28th changes by David Carlisle.  
 More recent changes are recorded in ChangeLog.

## 3 Implementation

```
1 <*package>
2 \RequirePackage{refcount}[2006/02/12]
```

We redefine `\label` so that it also writes the name of the current section to the .aux file; if the name ends in a dot, we zap it. To allow for the hyperref package, also write fourth and fifth fields (empty by default; used for cross-ref name, and file).

```
3 \def\strip@period#1.\relax#2\@@@{#1}
```

### 3.1 `\label` stuff

Here is tested, whether package showkeys is loaded. But if option final is used, the macros of showkeys are not defined, so we have to check an additional test.

```
4 \newif\ifNR@showkeys
5 \NR@showkeysfalse
6 \@ifpackageloaded{showkeys}{%
7   \begingroup
8     \@ifundefined{SK@@label}{%
9       }{%
10        \global\NR@showkeystrue
11      }%
12   \endgroup
13 }{}

14 \def\label#1{%
15   \@bsphack
16   \begingroup
17     \@onelevel@sanitize\@currentlabelname
18     \edef\@currentlabelname{%
19       \expandafter\strip@period\@currentlabelname\relax.\relax\@@@%
20     }%
```

```

21 \protected@write\@auxout{}\{-%
22 \string\newlabel{#1}\{-%
23 {\@currentlabel}%
24 {\thepage}%
25 {\@currentlabelname}%
26 {\@currentHref}\{-%
27 }%
28 }%
29 \endgroup
30 \@esphack
31 }%
32 \ifNR@showkeys
33 \def\label#1{%
34 \@bsphack
35 \SK@SK@@label{#1}%
36 \begingroup
37 \@onelevel@sanitize\@currentlabelname
38 \edef\@currentlabelname{%
39 \expandafter\strip@period\@currentlabelname\relax.\relax\@@@%
40 }%
41 \protected@write\@auxout{}\{-%
42 \string\newlabel{#1}\{-%
43 {\@currentlabel}%
44 {\thepage}%
45 {\@currentlabelname}%
46 {\@currentHref}\{-%
47 }%
48 }%
49 \endgroup
50 \@esphack
51 }%
52 \fi
53 \let\ltx@label\label

```

Needed for the *subeqnarray* package.

```

54 \@ifundefined{slabel}\{-%
55 \def\slabel#1{%
56 \@bsphack
57 \if@filesw
58 {%
59 \@onelevel@sanitize\@currentlabelname
60 \edef\@currentlabelname{%
61 \expandafter\strip@period\@currentlabelname\relax.\relax\@@@%
62 }%
63 \let\thepage\relax
64 \def\protect{\noexpand\noexpand\noexpand}%
65 \edef\@tempa{%
66 \write\@auxout{%
67 \string\newlabel{#1}\{-%
68 {\thesubequation}%
69 {\thepage}%
70 {\@currentlabelname}%
71 {\@currentHref}\{-%
72 }%
73 }%
74 }%
75 \expandafter

```

```

76     }%
77     \@tempa
78     \if@nobreak\ifvmode\nobreak\fi\fi
79     \fi
80     \@esphack
81 }%
82 }

```

Overload an AMS L<sup>A</sup>T<sub>E</sub>X command, which uses `\newlabel`. Sigh!

```

83 \def\@writetocindent@{%
84   \begingroup
85   \@for\@tempa:=-1,0,1,2,3\do{%
86     \immediate\write\@auxout{%
87       \string\newlabel{tocindent\@tempa}{%
88         \csname r@tocindent\@tempa\endcsname}{-}{-}{-}%
89     }%
90   }%
91 }%
92 \endgroup
93 }

```

## 3.2 Changes of section macros

Add to the underlying section heading macros so that they note the section name for use by label.

If a section heading or the like has a `\label` in it, we need to extract it, or subsequent processing breaks. This is done by the label-writing routine.

First the numbered sections. While we are about it, put in a useful section formatting macro.

```

94 \let\NR@ssect\@ssect
95 \newcounter{section@level}
96 \def\@sect#1#2#3#4#5#6[#7]#8{%
97   \setcounter{section@level}{#2}%
98   \def\@currentlabelname{#7}%
99   \NR@ssect{#1}{#2}{#3}{#4}{#5}{#6}[#7]{\Sectionformat{#8}{#2}}%
100 }

```

and now the unnumbered ones

```

101 \let\NR@ssect\@ssect
102 \def\@ssect#1#2#3#4#5{%
103   \def\@currentlabelname{#5}%
104   \NR@ssect{#1}{#2}{#3}{#4}{\Sectionformat{#5}{#1}}%
105 }

```

Parts and chapters are treated differently. sigh.

```

106 \let\NR@part\@part
107 \def\@part[#1]#2{%
108   \def\@currentlabelname{#1}%
109   \NR@part[#1]{#2}%
110 }
111 \let\NR@chapter\@chapter
112 \def\@chapter[#1]#2{%
113   \def\@currentlabelname{#1}%
114   \NR@chapter[#1]{#2}%
115 }
116 \let\NR@schapter\@schapter
117 \def\@schapter#1{%
118   \def\@currentlabelname{#1}%

```

```

119 \NR@schapter{#1}%
120 }

Captions

121 \let\NR@@caption\@caption
122 \long\def\@caption#1[#2]{%
123   \def\@currentlabelname{#2}%
124   \NR@@caption{#1}[{#2}]%
125 }

126 \AtBeginDocument{%
127   \@ifpackageloaded{longtable}{%
128     \let\NRorg@LT@c@ption\LT@c@ption
129     \def\LT@c@ption#1[#2]#3{%
130       \NRorg@LT@c@ption{#1}[{#2}]{#3}%
131       \def\@tempa{#2}%
132       \ifx\@tempa\@empty
133         \else
134           \def\@currentlabelname{#2}%
135         \fi
136       }%
137     }{}%
138 }

Compatibility for package titlesec.

139 \AtBeginDocument{%
140   \@ifpackageloaded{titlesec}{%
141     \let\NRorg@ttl@sect@i\ttl@sect@i
142     \def\ttl@sect@i#1#2[#3]#4{%
143       \def\@currentlabelname{#4}%
144       \NRorg@ttl@sect@i{#1}{#2}[{#3}]{#4}%
145     }%
146   }{}%
147 }

```

### 3.2.1 Class beamer

```

148 \@ifclassloaded{beamer}{%
149   \def\NR@PatchBeamer#1{%
150     \expandafter\let\csname NRorg@beamer@#1\expandafter\endcsname
151       \csname beamer@#1\endcsname
152     \begingroup
153       \edef\x{\endgroup
154         \long\def\expandafter\noexpand\csname beamer@#1\endcsname
155           [####1]{% hash-ok
156             \def\@currentlabelname{####1}%
157             \expandafter\@currentlabelname\csname NRorg@beamer@#1\endcsname
158             [{####1}]%
159           }%
160         }%
161       \x
162     }%
163   \NR@PatchBeamer{section}%
164   \NR@PatchBeamer{subsection}%
165   \NR@PatchBeamer{subsubsection}%
166 }{}

```

### 3.3 Referencing stuff

We default the label and hypertext reference to be empty.

```
167 \def\@currentlabelname{}
168 \def\@currentHref{}
```

Since the second part of the preserved reference now has five parts (number, page, name, hypertext reference and file), we need extra utility macros:

```
169 \long\def\@firstoffive#1#2#3#4#5{#1}
170 \long\def\@secondoffive#1#2#3#4#5{#2}
171 \long\def\@thirdoffive#1#2#3#4#5{#3}
172 \long\def\@fourthoffive#1#2#3#4#5{#4}
173 \long\def\@fifthoffive#1#2#3#4#5{#5}
```

We have to redefine `\ref` and `\pageref` to know about extra reference elements. Make them robust, and compatible with Babel. The Babel switch is mimicked if not already defined. Some support for package `showkeys` is implemented. If option `notref` of that package is set, `\SK@ref` has the meaning of `\@empty`.

```
174 \providecommand*\@safe@activetrue{}%
175 \providecommand*\@safe@activesfalse{}%
176 \def\NR@setref#1{%
177   \begingroup
178     \@safe@activetrue
179     \expandafter
180   \endgroup
181   \expandafter\NR@@setref\csname r@#1\endcsname
182 }
183 \def\NR@@setref#1{%
184   \ifx\@undefined#1%
185     \let#1\relax
186   \fi
187   \@setref#1%
188 }
189 \def\T@ref#1{%
190   \NR@setref{#1}\@firstoffive{#1}%
191 }%
192 \def\T@pageref#1{%
193   \NR@setref{#1}\@secondoffive{#1}%
194 }%
195 \ifNR@showkeys
196   \ifx\SK@ref\@empty
197     \else
198       \def\T@ref#1{%
199         \@safe@activetrue
200         \SK@\SK@@ref{#1}%
201         \@safe@activesfalse
202         \NR@setref{#1}\@firstoffive{#1}%
203       }%
204       \def\T@pageref#1{%
205         \@safe@activetrue
206         \SK@\SK@@ref{#1}%
207         \@safe@activesfalse
208         \NR@setref{#1}\@secondoffive{#1}%
209       }%
210     \fi
211   \fi
```

Package `hyperref` uses its own definitions of `\ref` and `\pageref` because it extends the syntax by the star form. `\DeclareRobustCommand` is used by `hyperref`.

Package `nameref` can be loaded before, after `hyperref` or after `hyperref`'s definitions in `\AtBeginDocument`.

```

212 \@ifpackageloaded{hyperref}{%
213 }{%
214   \DeclareRobustCommand{\ref}{\T@ref}%
215   \DeclareRobustCommand{\pageref}{\T@pageref}%
216 }

```

### 3.4 Usage and frontend

Access the (third) name part with `\nameref`;

```

217 \def\T@nameref#1{%
218   \begingroup
219     \let\label\@gobble
220     \NR@setref{#1}\@thirdoffive{#1}%
221   \endgroup
222 }%
223 \ifNR@showkeys
224   \ifx\SK@ref\@empty
225   \else
226     \def\T@nameref#1{%
227       \@safe@activestrue
228       \SK@\SK@@ref{#1}%
229       \@safe@activesfalse
230       \begingroup
231         \let\label\@gobble
232         \NR@setref{#1}\@thirdoffive{#1}%
233       \endgroup
234     }%
235   \fi
236 \fi
237 \def\nameref{\protect\T@nameref}

```

An extended form which gives title and page number.

```

238 \def\Nameref#1{'\nameref{#1}' on page~\pageref{#1}}

```

The default for `\Sectionformat`

```

239 \providecommand\Sectionformat[2]{#1}

```

### 3.5 Package `ifthen` support

Package `ifthen`'s `\isodd` does not work with `\pageref` because of the extra link and the star form. Therefore we need an expandable variant.

Unfortunately there is no hook in `\ifthenelse` in order to provide expandable versions without link of `\ref` and `\pageref`. As possible target I could only find `\begingroup`:

```

240 \@ifpackageloaded{ifthen}{%
241   \let\NR@Org@ifthenelse@ifthenelse
242   \def\ifthenelse{%
243     \let\begingroup\NR@TE@begingroup
244     \NR@Org@ifthenelse
245   }%
246   \let\NR@Org@begingroup\begingroup
247   \def\NR@TE@begingroup{%
248     \let\begingroup\NR@Org@begingroup
249     \begingroup
250     \def\ref##1{\getrefbykeydefault{##1}{}{??}}%

```

```

251 \def\pageref##1{\getrefbykeydefault{##1}{page}{0}}%
252 }%
253 {}

```

### 3.6 Compatibility with varioref

[This section was derived by Corey Minyard minyard@acm.org from the varioref package]

```

254 \AtBeginDocument{%
255   \ifx\csname @vpageref\endcsname\relax
256   \else
257     \def\@vpageref#1[#2]#3{%
258       \begingroup
259         \csname @safe@activetrue\endcsname
260         \edef\x{#3}%
261         \@onelevel@sanitize\x
262         \toks@{%
263           \NR@vpageref{#1}[{#2}]%
264         }%
265         \edef\x{\endgroup
266           \the\toks@{\x}%
267         }%
268       \x
269     }%
270     \def\NR@vpageref#1[#2]#3{%
271       \leavevmode\unskip
272       \global\advance\c@vrcnt\@ne
273       \@ifundefined{r@the\c@vrcnt @vr}%
274       {\@namedef{r@the\c@vrcnt @vr}{{??}{??}{-}{-}{-}}}%
275       \edef\@tempa{%
276         \expandafter\expandafter\expandafter
277         \@secondoffive\csname r@the\c@vrcnt @vr\endcsname
278       }%
279       \@ifundefined{r@the\c@vrcnt @xvr}%
280       {\@namedef{r@the\c@vrcnt @xvr}{{??}{??}{-}{-}{-}}}%
281       \edef\@tempb{%
282         \expandafter\expandafter\expandafter
283         \@secondoffive\csname r@the\c@vrcnt @xvr\endcsname
284       }%
285       {%
286         \let\@currentlabel\@empty
287         \expandafter\label\expandafter{\the\c@vrcnt @xvr}%
288       }%
289       \ifx\@tempa\@tempb
290       \else
291         \vref@err{%
292           \noexpand\vref at page boundary %
293           \@tempb-\@tempa\space (may loop)%
294         }%
295       \fi
296       \@ifundefined{r@#3}{\@namedef{r@#3}{{??}{??}{-}{-}{-}}}%
297       \edef\thevpagerefnum{%
298         \expandafter\expandafter\expandafter
299         \@secondoffive\csname r@#3\endcsname
300       }%
301       \ifx\vref@space\@undefined
302         \space

```



```

303 \else
304 \vref@space
305 \fi
306 \ifx\@tempa\thepagerefnum
307 #1%
308 \else
309 #2%
310 \is@pos@number\thepagerefnum{%
311 \is@pos@number\@tempa{%
312 \@tempcnta\@tempa
313 \advance\@tempcnta\@ne
314 }{%
315 \@tempcnta\maxdimen
316 }%
317 \ifnum \thepagerefnum =\@tempcnta
318 \ifodd\@tempcnta
319 \if@twoside
320 \reftextfaceafter
321 \else
322 \reftextafter
323 \fi
324 \else
325 \reftextafter
326 \fi
327 \else
328 \advance\@tempcnta-2 %
329 \ifnum \thepagerefnum =\@tempcnta
330 \ifodd\@tempcnta
331 \reftextbefore
332 \else
333 \if@twoside
334 \reftextfacebefore
335 \else
336 \reftextbefore
337 \fi
338 \fi
339 \else
340 \reftextfaraway{#3}%
341 \fi
342 \fi
343 }{%
344 \reftextfaraway{#3}%
345 }%
346 \fi
347 {%
348 \let\@currentlabel\@empty
349 \expandafter\label\expandafter{\the\c@vrcnt @vr}%
350 }%
351 }%
352 \DeclareRobustCommand\vnameref[1]{%
353 \unskip~\nameref{#1}%
354 \@vpageref[\unskip]{#1}%
355 }%
356 \fi
357 }

358 \ifundefined{@Refstar}{%
359 \def\T@Ref#1{%

```

```

360 \NR@setref{#1}\NR@MakeUppercaseFirstOfFive{#1}%
361 }%
362 \def\NR@MakeUppercaseFirstOfFive#1#2#3#4#5{%
363 \MakeUppercase#1%
364 }%
365 }{}%
366 \AtBeginDocument{%
367 \ifpackageloaded{varioref}{%
368 \ifundefined{@Refstar}{%
369 \DeclareRobustCommand*\Ref}[1]{%
370 \T@Ref{#1}%
371 }%
372 }{}%
373 }{}%
374 }%

```

### 3.7 Support for listings

```

375 \AtBeginDocument{%
376 \ifpackageloaded{listings}{%
377 \let\NR@Org@lst@MakeCaption\lst@MakeCaption
378 \def\lst@MakeCaption{%
379 \ifx\lst@label\@empty
380 \else
381 \let\@currentlabelname\lst@@caption
382 \fi
383 \NR@Org@lst@MakeCaption
384 }%
385 }{}%
386 }
387 </package>

```

## 4 Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

| Symbols                      | 118, 123, 134,   | 279, 296, 358, 368            |
|------------------------------|------------------|-------------------------------|
| \@@@ . . . . .               | 3, 19, 39, 61    | 143, 156, 167, 381            |
| \@@vpageref . . . . .        | 257              | \@namedef . 274, 280, 296     |
| \@auxout . . . . .           | 21, 41, 66, 86   | \@empty . . . 132, 196,       |
| \@bsphack . . . . .          | 15, 34, 56       | 224, 286, 348, 379            |
| \@caption . . . . .          | 121, 122         | \@esphack . . . 30, 50, 80    |
| \@chapter . . . . .          | 111, 112         | \@fifthoffive . . . . . 173   |
| \@currentHref . . . . .      | 26, 46, 71, 168  | \@firstoffive . . . . .       |
| \@currentlabel . . . . .     | 23, 43, 286, 348 | 169, 190, 202                 |
| \@currentlabelname . . . . . | 17,              | \@for . . . . . 85            |
| 18, 19, 25, 37,              |                  | \@fourthoffive . . . . . 172  |
| 38, 39, 45, 59,              |                  | \@gobble . . . . . 219, 231   |
| 60, 61, 70, 98,              |                  | \@ifclassloaded . . . 148     |
| 103, 108, 113,               |                  | \@ifpackageloaded . . . . .   |
|                              |                  | 6, 127, 140,                  |
|                              |                  | 212, 240, 367, 376            |
|                              |                  | \@ifundefined . . . . .       |
|                              |                  | 8, 54, 273,                   |
|                              |                  | \@one . . . . . 272, 313      |
|                              |                  | \@onelevel@sanitize . . . . . |
|                              |                  | 17, 37, 59, 261               |
|                              |                  | \@part . . . . . 106, 107     |
|                              |                  | \@safe@activesfalse . . . . . |
|                              |                  | 175, 201, 207, 229            |
|                              |                  | \@safe@activetrue . . . . .   |
|                              |                  | 174,                          |
|                              |                  | 178, 199, 205, 227            |
|                              |                  | \@schapter . . . . . 116, 117 |
|                              |                  | \@secondoffive . . . . .      |
|                              |                  | 170, 193,                     |
|                              |                  | 208, 277, 283, 299            |
|                              |                  | \@sect . . . . . 94, 96       |
|                              |                  | \@setref . . . . . 187        |

|   |                    |                                     |  |
|---|--------------------|-------------------------------------|--|
| <code>\@ssect</code> . . . . .          | 101, 102           | 60, 65, 153, 260,                   | 243, 246, 248,                             |
| <code>\@tempa</code> . . . . .          | 65, 77,            | 265, 275, 281, 297                  | 286, 348, 377, 381                         |
|   | 85, 87, 88, 131,   | <code>\else</code> . . . . .        | <code>\long</code> . . . . .               |
|   | 132, 275, 289,     | 133,                                | 122, 154, 169,                             |
|   | 293, 306, 311, 312 | 197, 225, 256,                      | 170, 171, 172, 173                         |
| <code>\@tempb</code> . . . . .          | 281, 289, 293      | 290, 303, 308,                      | <code>\lst@caption</code> . . . . .        |
| <code>\@tempcnta</code> . . . . .       | 312,               | 321, 324, 327,                      | <code>\lst@label</code> . . . . .          |
|   | 313, 315, 317,     | 332, 335, 339, 380                  | <code>\lst@MakeCaption</code> . .          |
|   | 318, 328, 329, 330 | <code>\endcsname</code> . . . . .   | 377, 378                                   |
| <code>\@thirdoffive</code> . . . . .    |                    | 88,                                 | <code>\LT@caption</code> . . . . .         |
|   | 171, 220, 232      | 150, 151, 154,                      | 128, 129                                   |
| <code>\@undefined</code> . . . . .      | 184, 301           | 157, 181, 255,                      | <code>\ltx@label</code> . . . . .          |
| <code>\@vpageref</code> . . . . .       | 354                | 259, 277, 283, 299                  | 53   |
| <code>\@writetocindent</code> . . . . . | 83                 | <code>\endgroup</code> . . . . .    |  |
|   |                    | 12,                                 | <b>M</b>                                   |
|   |                    | 29, 49, 92, 153,                    | <code>\MakeUppercase</code> . . . . .      |
|   |                    | 180, 221, 233, 265                  | 363  |
|   |                    | <code>\expandafter</code> . . . . . | <code>\maxdimen</code> . . . . .           |
|   |                    | . 19, 39, 61, 75,                   | 315  |
| <b>A</b>                                |                    | 150, 154, 157,                      | <b>N</b>                                   |
| <code>\advance</code> . . . . .         | 272, 313, 328      | 179, 181, 276,                      | <code>\Nameref</code> . . . . .            |
| <code>\AtBeginDocument</code> . . . . . | 126,               | 282, 287, 298, 349                  | 238  |
|   | 139, 254, 366, 375 |                                     | <code>\nameref</code> . . . . .            |
|   |                    |                                     | 237, 238, 353                              |
| <b>B</b>                                |                    |                                     | <code>\newcounter</code> . . . . .         |
| <code>\begingroup</code> . . . . .      | 7, 16,             |                                     | 95   |
|   | 36, 84, 152, 177,  |                                     | <code>\newif</code> . . . . .              |
|   | 218, 230, 243,     |                                     | 4  |
|   | 246, 248, 249, 258 |                                     | <code>\newlabel</code> . . . . .           |
|   |                    |                                     | 22, 42, 67, 87                             |
|   |                    |                                     | <code>\nobreak</code> . . . . .            |
|   |                    |                                     | 78   |
|   |                    |                                     | <code>\noexpand</code> . . . . .           |
|   |                    |                                     | 64,  |
|   |                    |                                     | 154, 156, 157, 292                         |
|   |                    |                                     | <code>\NR@caption</code> . . . . .         |
|   |                    |                                     | 121, 124                                   |
|   |                    |                                     | <code>\NR@setref</code> . . . . .          |
|   |                    |                                     | 181, 183                                   |
|   |                    |                                     | <code>\NR@vpageref</code> . . . . .        |
|   |                    |                                     | 263, 270                                   |
|   |                    |                                     | <code>\NR@chapter</code> . . . . .         |
|   |                    |                                     | 111, 114                                   |
| <code>\c@vrcent</code> . . . . .        | 272, 273,          |                                     | <code>\NR@MakeUppercaseFirstOfFive</code>  |
|   | 274, 277, 279,     |                                     | 360, 362                                   |
|   | 280, 283, 287, 349 |                                     | <code>\NR@part</code> . . . . .            |
| <code>\csname</code> . . . . .          | 88,                |                                     | 106, 109                                   |
|   | 150, 151, 154,     |                                     | <code>\NR@PatchBeamer</code> . . .         |
|   | 157, 181, 255,     |                                     | 149, 163, 164, 165                         |
|   | 259, 277, 283, 299 |                                     | <code>\NR@chapter</code> . . . . .         |
|   |                    |                                     | 116, 119                                   |
|   |                    |                                     | <code>\NR@ssect</code> . . . . .           |
|   |                    |                                     | 94, 99                                     |
|   |                    |                                     | <code>\NR@setref</code> . . . . .          |
|   |                    |                                     | 176,                                       |
|   |                    |                                     | 190, 193, 202,                             |
|   |                    |                                     | 208, 220, 232, 360                         |
|   |                    |                                     | <code>\NR@showkeysfalse</code> . . . . .   |
|   |                    |                                     | 5  |
|   |                    |                                     | <code>\NR@showkeystrue</code> . . . . .    |
|   |                    |                                     | 10   |
|   |                    |                                     | <code>\NR@ssect</code> . . . . .           |
|   |                    |                                     | 101, 104                                   |
|   |                    |                                     | <code>\NR@TE@begingroup</code> . . . . .   |
|   |                    |                                     | 243, 247                                   |
|   |                    |                                     | <code>\NR@Org@begingroup</code> . . . . .  |
|   |                    |                                     | 246, 248                                   |
|   |                    |                                     | <code>\NR@Org@ifthenelse</code> . . . . .  |
|   |                    |                                     | 241, 244                                   |
|   |                    |                                     | <code>\NR@Org@lst@MakeCaption</code>       |
|   |                    |                                     | 377, 383                                   |
|   |                    |                                     | <code>\NR@Org@LT@caption</code> . . . . .  |
|   |                    |                                     | 128, 130                                   |
|   |                    |                                     | <code>\NR@Org@ttl@ssect@i</code> . . . . . |
|   |                    |                                     | 141, 144                                   |
|   |                    |                                     | <b>P</b>                                   |
|   |                    |                                     | <code>\pageref</code> . . . . .            |
|   |                    |                                     | 215, 238, 251                              |
|   |                    |                                     | <code>\protect</code> . . . . .            |
|   |                    |                                     | 64, 237                                    |
|   |                    |                                     | <code>\protected@write</code> . . . . .    |
|   |                    |                                     | 21, 41                                     |

|   |   |  |
|---|---|--|
| <code>\providecommand</code> . . .        | <code>\SK@@label</code> . . . . . 35      | <code>\thevpagerefnum</code> 297,        |
| . . . . 174, 175, 239                     | <code>\SK@@ref</code> . . 200, 206, 228   | 306, 310, 317, 329                       |
| <b>R</b>                                  | <code>\SK@ref</code> . . . . . 196, 224   | <code>\toks@</code> . . . . . 262, 266   |
| <code>\Ref</code> . . . . . 369           | <code>\slabel</code> . . . . . 55         | <code>\ttl@sect@i</code> . . . 141, 142  |
| <code>\ref</code> . . . . . 214, 250      | <code>\space</code> . . . . . 293, 302    | <b>U</b>                                 |
| <code>\reftextafter</code> . 322, 325     | <code>\string</code> . . 22, 42, 67, 87   | <code>\unskip</code> . . . 271, 353, 354 |
| <code>\reftextbefore</code> 331, 336      | <code>\strip@period</code> . . . . .      |  |
| <code>\reftextfaceafter</code> . 320      | . . . . . 3, 19, 39, 61                   | <b>V</b>                                 |
| <code>\reftextfacebefore</code> . 334     |   | <code>\vnameref</code> . . . . . 352     |
| <code>\reftextfaraway</code> 340, 344     | <b>T</b>                                  | <code>\vref</code> . . . . . 292         |
| <code>\relax</code> . . . . . 3, 19,      | <code>\T@nameref</code> 217, 226, 237     | <code>\vref@err</code> . . . . . 291     |
| 39, 61, 63, 185, 255                      | <code>\T@pageref</code> 192, 204, 215     | <code>\vref@space</code> . . . 301, 304  |
| <code>\RequirePackage</code> . . . . 2    | <code>\T@Ref</code> . . . . . 359, 370    |  |
| <b>S</b>                                  | <code>\T@ref</code> . . . . 189, 198, 214 | <b>W</b>                                 |
| <code>\Sectionformat</code> . . . .       | <code>\the</code> . . . . . 266, 273,     | <code>\write</code> . . . . . 66, 86     |
| . . . . . 99, 104, 239                    | 274, 277, 279,                            |  |
| <code>\setcounter</code> . . . . . 97     | 280, 283, 287, 349                        | <b>X</b>                                 |
| <code>\SK@</code> . . . 35, 200, 206, 228 | <code>\thepage</code> . 24, 44, 63, 69    | <code>\x</code> . . . 153, 161, 260,     |
|   | <code>\thesubequation</code> . . . 68     | 261, 265, 266, 268                       |