

# The L<sup>A</sup>T<sub>E</sub>X keyfloat Package

v0.11 — 2016/12/02

© 2016 Brian Dunn  
bd@BDTechConcepts.com

Provides a key/value interface for generating floats.

## Abstract

The `keyfloat` package provides a key/value user interface for quickly creating figures with a single image each, figures with arbitrary contents, tables, subfloats, rows of floats, and floats [H].

Key/value combinations may specify a caption and label, a width proportional to `\linewidth`, a fixed width and/or height, rotation, scaling, a tight or loose frame, an `\arraystretch`, a continued float, additional supplemental text, and an artist/author's name with automatic index entry. When used with the `tocdata` package, the name also appears in the List of Figures.

Floats may be placed into a row environment, and are typeset to fit within the given number of columns, continuing to the next row if necessary. Nested sub-rows may be used to generate layouts such as two small figures placed vertically next to one larger figure.

Subfloats are supported by two environments.

As an example, a typical command to include a figure with a framed image of half `\linewidth` could be:

```
\keyfig*[hbp]{f,lw=.5,c={A caption},l={fig:label}}{image}
```

# Contents

<b>1</b>	<b>Introduction</b>	<b>5</b>
1.1	A Problem with Floats . . . . .	5
1.2	The <code>keyfloat</code> Package . . . . .	5
1.3	Features . . . . .	6
<b>2</b>	<b>Using the <code>keyfloat</code> Package</b>	<b>8</b>
2.1	Macros and Environments . . . . .	8
2.2	Keys and Values . . . . .	9
2.3	Examples . . . . .	12
2.3.1	Single Floats . . . . .	12
2.3.2	Groups of Floats . . . . .	21
2.3.3	Subfloats . . . . .	23
2.3.4	Continued Floats . . . . .	25
2.3.5	Continued Subfloats . . . . .	26
2.3.6	Custom Frames . . . . .	27
2.3.7	Artist's Name . . . . .	29
2.4	Customization . . . . .	31
2.4.1	Custom Frames . . . . .	31
2.4.2	Distance between Floats and Rows . . . . .	31
2.4.3	Formatting the Captions . . . . .	32
<b>3</b>	<b>Code</b>	<b>33</b>
3.1	Required Packages . . . . .	33
3.2	In-line Figures and Tables . . . . .	33
3.3	Row Counting and Control . . . . .	34
3.4	Float Key Handling . . . . .	34
3.5	Nesting Control . . . . .	39
3.6	Subfloat Key Handling . . . . .	39
3.7	Computing Image Width . . . . .	43
3.8	Framing and Rotation . . . . .	44
3.9	A Graphics Image from a File . . . . .	45
3.10	Printing the Caption . . . . .	47
3.11	Defaults for a New Float . . . . .	50
3.12	Row Start/End Processing . . . . .	51
3.13	Key Environment Helper Macros . . . . .	52
3.14	The <code>keyfigure</code> Environment . . . . .	58

3.15	The <code>\keyfig</code> Macro . . . . .	59
3.16	The <code>\keyfigbox</code> Macro . . . . .	59
3.17	The <code>\keyparbox</code> Macro . . . . .	60
3.18	The <code>\keytab</code> Macro . . . . .	60
3.19	The <code>keytable</code> Environment . . . . .	61
3.20	A Row of Floats . . . . .	61
3.21	Subfigures . . . . .	65

## Change History and Index 69

### List of Examples

1	Figure with an image from a file . . . . .	12
2	Figure with arbitrary contents . . . . .	12
3	Figure environment with arbitrary contents . . . . .	13
4	Table macro . . . . .	13
5	Table environment with arbitrary contents . . . . .	14
6	Figure with many options selected . . . . .	15
7	Using <code>\linewidth</code> . . . . .	16
8	Using frames . . . . .	17
9	Using rotation with boxes . . . . .	18
10	Located [H]ere . . . . .	18
11	Unnumbered float . . . . .	19
12	Unnumbered float with a LOF entry . . . . .	19
13	An unnumbered in-text image . . . . .	20
14	A box without a caption. . . . .	20
15	Groups of figures — <code>keyfloats</code> environment . . . . .	21
16	Subfigures — <code>keysubfigs</code> environment . . . . .	23
17	Continued figure . . . . .	25
18	Continued subfloats . . . . .	26
19	Custom frames with <code>mdframed</code> . . . . .	27
20	Custom shadows with <code>fancybox</code> . . . . .	28
21	Artist's name — image . . . . .	29
22	Artist's name — arbitrary contents . . . . .	29
23	Subfloats with an artist . . . . .	30

### List of Figures

1	A <code>\keyfig</code> with an image . . . . .	12
2	A <code>\keyfigbox</code> . . . . .	12
3	A <code>keyfigure</code> environment . . . . .	13
4	A figure with options . . . . .	15

5	Half of <code>\linewidth</code> . . . . .	16
6	Loosely-framed figure . . . . .	17
7	Tightly-framed figure . . . . .	17
	Starred short caption . . . . .	19
8	Next to a <code>\keyparbox</code> . . . . .	20
9	First in a group . . . . .	22
10	Third in a group . . . . .	22
11	Fourth in a group . . . . .	22
12	Fifth in a group . . . . .	22
13	Sixth in a group . . . . .	22
14	Subfigures . . . . .	23
15	Figure to be continued . . . . .	25
15	...continued . . . . .	25
16	A set of figures . . . . .	26
16	...continued . . . . .	26
17	Custom-framed image . . . . .	27
18	Custom loosely-framed box . . . . .	27
19	Custom shadow . . . . .	28
20	Custom loosely-framed shadow . . . . .	28
21	Artist's name — image . . . . . <i>First Last</i>	29
22	Artist's name — arbitrary contents . . . . . <i>Last</i>	29
23	Artist's collection . . . . . <i>First Last</i>	30

## List of Tables

1	Keys and Values — Part I . . . . .	10
1	Keys and Values — Part II . . . . .	11
2	Caption-Related Key Combinations . . . . .	11
3	A <code>\keytab</code> table . . . . .	13
4	A <code>keytable</code> environment . . . . .	14
5	Loosely-framed table . . . . .	17
6	Tightly-framed table . . . . .	17
7	Table, rotated . . . . .	18
8	A table [H] . . . . .	18
9	Seventh in a group . . . . .	22

# 1 Introduction

The `keyfloat` package simplifies the creation of L<sup>A</sup>T<sub>E</sub>X floats, while still allowing a number of useful features.

## 1.1 A Problem with Floats

When including a figure with a graphics image into a document, the user typically enters something such as:

```
\begin{figure}  
  \centering  
  \includegraphics[width=3in]{filename}  
  \caption{A Figure}  
  \label{fig:somelabel}  
\end{figure}
```

When doing that often enough, it makes sense to factor the common code:

```
\onefigure[3in]{filename}{A Figure}{fig:somelabel}
```

Expanding the capability of `\onefigure` via `xparse` can lead to the general case of:

```
\onefigure*[loc](width){filename}(add'l text)[shortcap]{caption}*[label]
```

Attempting to add additional features such as frames and continued floats hits the limit of nine parameters for a T<sub>E</sub>X macro, requiring that new features use some kind of change-state macros instead. Attempting to support rows of floats or subfloats only made things more complicated still.

A key/value system solves the problem of adding more features, does not require much additional typing, is a more self-documenting syntax, and allows the sharing of keys with subfloats as well. Thus, the `keyfloat` package.

## 1.2 The `keyfloat` Package

Using `keyfloat`, the first example above becomes:

```
\keyfig{w=3in,c=A Figure,l=fig:somelabel}{filename}
```

The `\onefigure` example above becomes:

```
\keyfig*[loc]{w=width,t={add'l text},sc=shortcap,cstar=caption,
l=label}{filename}
```

### 1.3 Features

The macros and environments provided by `keyfloat` include:

**`\keyfig`:** A figure with an image.

**`\keyfigbox`:** A figure with arbitrary contents.

**`\keyparbox`:** A “figure” without a caption, useful to place uncaptioned text inside a group,

**`\keytab`:** A table.

**`keyfigure`:** A figure environment.

**`keytable`:** A table environment.

**`keyfloats`:** A group of rows and columns of floats.

**`keysubfigs`:** A figure containing a group of rows and columns of subfigures.

**`keysubtabs`:** A table containing a group of rows and columns of subtables.

Additional features include:


- Rows and columns of floats may be generated by placing them inside a `keyfloats` environment.
- Subfloats may be generated by placing them inside a `keysubfigs` or `keysubtabs` environment.
- The number of columns is specified, and extra floats are placed onto additional rows.
- Floats may be placed [H]ere
- Floats may be starred to span two columns.
- Continued floats may be used to repeat the previous float number.
- A figure may contain an image, with additional sizing, rotation, and a frame.

- Tables may be stretched.
- Boxes of arbitrary contents may be assigned a width and framed.
- Floats may be moved into and out of the grouping environments as needed.
- An artist/author's name may be added to a figure and the index.
- If the `tocdata` package is loaded (use v0.12+), the name is also added to the LOF.
- Additional descriptive text may be added as well.
- Frames may be customized.

**examples** A large number of examples are provided, each showing  $\text{\LaTeX}$  source and the resulting float.

**index** A customized index is included at the back of the documentation.

**margin tags** Blue margin tags are used to help quickly find information, and often indicate the destination of index entries.

 **warnings** Several warnings are noted in the text. Watch out for these special cases.

**problems** See the “troubleshooting” section of the index for help with specific problems which may occur.

## 2 Using the keyfloat Package

### 2.1 Macros and Environments

<code>\keyfig</code>	* [ <i>loc</i> ] { <i>keys/values</i> } { <i>image filename</i> }	A macro to generate a figure with an image from a file.
<code>\keyfigbox</code>	* [ <i>loc</i> ] { <i>keys/values</i> } { <i>box contents</i> }	A macro to generate a figure with arbitrary paragraph contents. See example 2.
<code>\keyparbox</code>	* [ <i>loc</i> ] { <i>keys/values</i> } { <i>box contents</i> }	A macro to generate a figure with arbitrary paragraph contents, but no number or caption. This is equal to a <code>\keyfigbox</code> with <code>cstar={}</code> . Mostly useful to add supplemental information inside a row of floats or subfloats. See example 14.
<code>\keytab</code>	* [ <i>loc</i> ] { <i>keys/values</i> } { <i>tabular contents</i> }	A macro to generate a table with tabular contents. Usually use the <code>keytable</code> environment instead.
Env <code>keyfigure</code>	* [ <i>loc</i> ] { <i>keys/values</i> }	An environment to generate a figure with arbitrary contents. Useful for multi-paragraph contents. See example 3.
Env <code>keytable</code>	* [ <i>loc</i> ] { <i>keys/values</i> }	An environment to generate a table with arbitrary contents. Useful for larger tables. See example 5.
<hr/>		
The above macros and environments may be used by themselves, or inside the following <code>keyfloats</code> , <code>keysubfigs</code> , or <code>keysubtabs</code> environments.		
<hr/>		
Env <code>keyfloats</code>	* [ <i>loc</i> ] { <i>num columns</i> }	A group of figures or tables typeset in rows. May be nested. See example 15.
Env <code>keysubfigs</code>	* [ <i>loc</i> ] { <i>numcols</i> } { <i>keys</i> }	A group of subfigures or subtables typeset in rows. May not be nested. See example 16.
Env <code>keysubtabs</code>	* [ <i>loc</i> ] { <i>numcols</i> } { <i>keys</i> }	
<hr/>		
Arg *	The star option create floats which span both columns in a two-column document.	
Arg [H]	The [H] location may be used to force a figure to be “Here”, in the form of a minipage instead of a float. A caption and label may still be assigned.	
Arg [loc]	The star and [loc] options are ignored for floats inside a <code>keyfloats</code> , <code>keysubfigs</code> , or <code>keysubtabs</code> environment. Note that these container environments may have their own star and [loc] options.	



## 2.2 Keys and Values

Table 1 shows the key/value combinations which are allowed. In most cases these may be used in any order and any combination, except for the following:

**subfloat keys** The keys labeled "Sub" may be used for the `keysubfigs` and `keysubtabs` environments, which group a number of subfloats together under one master float. The master float has its own caption, label, and text, and each subfloat inside the group likewise has its own set of keys.

**keyfloats keys** `keyfloats` does not accept any keys at all.

The “artist” keys `ap`, `af`, `al`, and `as` are only used by figures.

The `stretch` key increases space between tabular elements.

The rest of the macros and environments accept all of the keys, as they each create an individual float or subfloat, and each may have its own assigned dimensions and frame.

**short/long caption combinations** Table 2 shows the combinations of the caption-related keys `c`, `cstar`, and `sc`, and how they control the caption numbering and entries in the LOF/LOT.

Table 1: Keys and Values — Part I

Key	Sub <sup>a</sup>	Description	Example
<code>c</code>	•	An unstarred caption. If empty, creates a figure with a number but no caption.	<code>c=A Caption</code>
<code>cstar</code>	•	A starred caption. Creates a float without a number. If empty, creates a figure with no number or caption.	<code>cstar=No Num</code>
<code>sc</code>	•	The short caption for the LOF/LOT, even if <code>cstar</code> .	<code>sc=Short Cap</code>
<code>cont</code>	•	Continued float?	<code>cont</code>
<code>l</code>	•	The label. Enclose in braces if a comma is included. Ignored in unnumbered floats.	<code>l=fig:A name</code>
<code>ap</code>	•	Artist's prefix, such as "Mr." <sup>b</sup>	<code>ap=Mr.</code>
<code>af</code>	•	Artist's first name. <sup>b</sup>	<code>af=First</code>
<code>al</code>	•	Artist's last name. <sup>b</sup>	<code>al=Last</code>
<code>as</code>	•	Artist's suffix, such as ~III. <sup>b</sup>	<code>al=~III</code>
<code>t</code>	•	Additional text. May include paragraphs. Enclose in braces if a comma is included. May need <code>\protect</code> before macro calls. Fully-justified alignment.	<code>t=Paragraphs</code>
<code>tc</code>	•	Additional text, aligned to the center.	<code>tc=Paragraphs</code>
<code>tl</code>	•	Additional text, aligned to the left.	<code>tl=Paragraphs</code>
<code>tr</code>	•	Additional text, aligned to the right.	<code>tr=Paragraphs</code>

<sup>a</sup>: All the keys in Part I may be used with the `keysubfigs` and `keysubtabs` environments.

<sup>b</sup>: Artist keys: Only used in Figure floats. A fixed-width non-breakable space is placed between names, except that the optional suffix is connected directly to the last name, allowing "`as={, Title}`", for example.

... continued

**Table 1: Keys and Values — Part II**

Key <sup>a</sup>	Description	Example
<b>lw</b>	Set the width to a fraction of <code>\linewidth</code> . Cancels <b>w</b> . If a non-image float, sets the width of the text box.	<code>lw=.5</code>
<b>w</b>	Set the actual width. Cancels <b>lw</b> . If a non-image float, sets the width of the text box.	<code>w=2in</code>
<b>h</b>	Set the actual height, images only.	<code>w=2in</code>
<b>s</b>	Set the image scale, images only.	<code>s=3</code>
<b>a</b>	Set the rotation angle; counter-clockwise degrees.	<code>r=90</code>
<b>f</b>	Selects a loose frame with the current <code>\fboxsep</code> . Only rotated with <code>\keyfig</code> .	<code>f</code>
<b>ft</b>	Selects a tight frame with no <code>\fboxsep</code> . Useful for photographs, or diagrams which already have some margin built in.	<code>ft</code>
<b>stretch</b>	Sets <code>\arraystretch</code> inside the float.	<code>stretch=1.5</code>

<sup>a</sup>: None of the keys in Part II are used in the `keysubfigs` and `keysubtabs` environments.

**Table 2: Caption-Related Key Combinations**

Keys in Use			Type of	
<b>c</b>	<b>cstar</b>	<b>sc</b>	<b>Caption<sup>a</sup></b>	<b>LOF/LOT<sup>b</sup></b>
•	—	—	Numbered	Caption
•	—	•	Numbered	Short Caption
—	•	—	Unnumbered	None
—	•	•	Unnumbered	Short Caption
—	<code>cstar={}</code>	Ignored	None	None

<sup>a</sup>: Caption: Shows whether the float will be numbered, un-numbered, or have no caption.

<sup>b</sup>: LOF/LOT: Shows whether the regular or short caption will appear in the List of Figures or List of Tables, or if there will be no listing.

*An image.*

Figure 1: A `\keyfig` with an image

<p>Some text. More text.</p> <p>Another paragraph.</p>
--

Figure 2: A `\keyfigbox`

## 2.3 Examples

### 2.3.1 Single Floats

---

#### Example 1: Figure with an image from a file

---

```
\keyfig{c=A \cs{keyfig} with an image,l=fig:simple}{image}
```

---

*Figure 1*

---

**natural size** This float (fig. 1) is shown at its natural size because no width or height modifiers were specified. When used alone like this, a regular float is created.

---

#### Example 2: Figure with arbitrary contents

---

```
\keyfigbox{f,c={A \cs{keyfigbox}},l=fig:figbox}
  {Some text. More text. \par Another paragraph.}
```

---

*Figure 2*

---

**default width** The `\keyfigbox` creates a figure with a box of arbitrary contents, instead of an image from a file. Its default width is the full `\linewidth`, unless `w` or `lw` keys are used.

Arbitrary contents may go here.

Including multiple paragraphs.

**Figure 3: A keyfigure environment**

**Table 3: A `\keytab` table**

A	B
C	D

---

**Example 3: Figure environment with arbitrary contents**

---

```
\begin{keyfigure}{f,c={A \env{keyfigure} environment},
  l=fig:environment}
Arbitrary contents may go here.

Including multiple paragraphs.
\end{keyfigure}
```

---

*Figure 3*

---

The `keyfigure` environment is preferred over the `\keyfigbox` macro when multiple lines of contents are to be included.

---

**Example 4: Table macro**

---

```
\keytab{c=A \cs{keytab} table,l=tab:simpletable}{\testtable}
```

---

*Table 3*

---

Do not try to use tables which overflow the page.

For anything other than a simple table, use the `keytable` environment. See example 5.

[large tables](#) For large tables, use the `longtable` or `supertabular` packages.

Table 4: A keytable environment

Arbitrary contents may go here.	
A	B
C	D

Example 5: Table environment with arbitrary contents

```
\begin{keytable}[f,c={A \env{keytable} environment},
  l=tab:environment}
Arbitrary contents may go here.

\testtable
\end{keytable}
```

Table 4

The `keytable` environment is preferred over the `\keytab` macro since most tables are multi-line creations.



Additional text. Multiple paragraphs may be used. The entire text is enclosed in braces because a comma is included. Alignment may be set by using tags `tc`, `tl`, or `tr` instead of `t`

**Figure 4: A figure with many options**

---

#### Example 6: Figure with many options selected

---

```
\keyfig{
  w=2in,ft,r=15,
  c=A figure with many options,
  sc=A figure with options,
  t={Additional text. Multiple paragraphs may be used.
    The entire text is enclosed in braces because a comma
    is included. Alignment may be set by using
    tags \texttt{tc}, \texttt{tl}, or \texttt{tr}
    instead of \texttt{t}},
  l=fig:options
}{image}
```

---

*Figure 4*

---

Width is fixed at 2 in, a tight frame is specified (`\fboxsep` of 0 pt), a short caption appears in the List of Figures, and the additional text is using the default fully-justified alignment.

Since fig. 4 is a float, it may appear on the following page.

Figure 5: Half of `\linewidth`


---

**Example 7: Using `\linewidth`**


---

```
\keyfig{lw=.5,c=Half of \cs{linewidth},l=fig:linewidth}{image}
```

---

*Figure 5*

---

`\linewidth` Figure 5 is half of `\linewidth` in size. When the `lw` key is used inside a `keyfloats` or `keysubfigs` environment, the `\linewidth` will be proportional to the sub-box for each element. When used alone, such as here, the `\linewidth` is the full width of the text on this page.

`lw` and `w` are not used at the same time. If both `lw` and `w` are specified, the last one cancels any previous ones.





Table 7: Table, rotated

A	B	C
D	E	F

(Framed to show box width.)

Example 9: Using rotation with boxes

```
\keytab{f,w=.8in,c={Table, rotated},
  r=70,l=tab:rotated,
  tc=(Framed to show box width.))
{\testwidetable}
```

Table 7

- rotated whitespace
- ⚠ box width

Unless a width is given, a box is the full `\linewidth`. When rotated, this extra horizontal space is rotated into extra vertical space. To avoid this extra space, set a `w` or `lw` to be wide enough for the table or other contents, but not much wider. When this box is rotated, it will not take much more vertical space than necessary.
- frame rotation
- Unlike an image, the frame of a box does not rotate with its contents.

Example 10: Located [H]ere

```
\keytab[H]{c={A table [H]},l=fig:here}{\testtable}
```


Table 8

Table 8: A table [H]

A	B
C	D

- ⚠ Out of sequence

Table 8 is to be placed “[H]ere”, and therefore may appear out-of-sequence with surrounding figures. Place a `\clearpage` before or after to re-sync, if necessary.



Starred caption with a short caption.


---

### Example 11: Unnumbered float

```
\keyfig[H]{f,cstar={A starred caption}}{image}
```

*See fig: “A starred caption”.*

---



A starred caption

A starred caption creates a float without a number, and without an entry in the List of Figures unless there is a non-empty short caption. (See the next example.)

 **No label** Labels cannot be used when there is no number for a float.

---

### Example 12: Unnumbered float with a lof entry

```
\keyfig{
  f,cstar={Starred caption with a short caption.},
  sc={Starred short caption}
}{image}
```

*See fig: “Starred caption with a short caption”.*

---

A starred caption with a non-empty short caption creates an unnumbered entry in the List of Figures.

Some contents.

*An image.*A `\keyparbox` with no number or label.**Figure 8:** Next to a `\keyparbox`**Example 13: An unnumbered in-text image**

```
\keyfig[H]{f,cstar={},
  tc={Optional text which is not a caption.}
}{image2}
```

*See fig: “Optional text which is not a caption.”*

Optional text which is not a caption.

By using `[H]` and `cstar={}`, the image is placed inline without a number or LOF entry.

Also see example 14.

**Example 14: A box without a caption.**

```
\begin{keyfloats}{2}
\keyparbox{
  f,lw=.5,
  tc={A \cs{keyparbox} with no number or label.}
}{Some contents.}
\keyfig{c=Next to a \cs{keyparbox},l=fig:nexttoparbox}{image}
\end{keyfloats}
\keyparbox[H]{f,lw=.5}{A \cs{keyparbox} [H], outside the floatrow.}
```

*Figure 8, and the box to its left.*

A `\keyparbox` [H], outside the floatrow.

A `\keyparbox` is a `\keyfigbox` with `cstar={}`, and is mostly useful as an information box inside a row or a set of subfloats.

### 2.3.2 Groups of Floats

---

#### Example 15: Groups of figures — `keyfloats` environment

---

```
\begin{keyfloats}{2}
\keyfig{lw=1,f,c={First in a group},
  l=fig:firstinrow,tl={\cs{raggedright} text}
}{image}
\keyparbox{}{\centering A \cs{keyparbox} describing something.
  \par With several paragraphs.}
\begin{keyfloats}{2}
\keyfig{lw=1,c={Third in a group},
  l=fig:thirdinarow}{image}
\keyfig{lw=1,c={Fourth in a group}}{image2}
\keyfig{lw=1,c={Fifth in a group}}{image}
\keyfig{lw=1,c={Sixth in a group},
  l=fig:sixthinrow}{image2}
\end{keyfloats}
\keytab{c={Seventh in a group},l=tab:seventhinrow}{\testwidetable}
\end{keyfloats}
```


---


*Figure 9 to Table 9*

---

Figure 9 to table 9 are in a `keyfloats` environment. Furthermore, Figures 10 to 13 are in an additional nested `keyfloats` environment, forming a small box of floats inside the larger group.

The `keyfloats` environment takes an argument for the number of columns. Additional floats are automatically placed on following rows. Changing the number of columns will cause the floats to automatically readjust as necessary. Leftovers will be centered on the last row.

 **`\linewidth`** Note that `\linewidth` is adjusted for each row and nested row, so the `lw` key will need to be changed if a float is moved to a different nesting level.

 **image too large** Fixed-width or fixed-height floats may be too large to fit if they are moved into a group. It is the user's responsibility to adjust `w`, `h`, or `lw` as necessary.

Keyfloats may be positioned [H]:  
`\begin{keyfloats}[H]{2} ...`

Keyfloats may be starred to span both columns in a two-column format:  
`\begin{keyfloats}*{2} ...`



\raggedright text

Figure 9: First in a group

A \keyparbox describing something.  
With several paragraphs.



Figure 10:  
Third in a  
group



Figure 11:  
Fourth in a  
group

Table 9: Seventh in a group

A	B	C
D	E	F



Figure 12:  
Fifth in a  
group



Figure 13:  
Sixth in a  
group




Figure 14: Subfigures

### 2.3.3 Subfloats

---

#### Example 16: Subfigures — keysubfigs environment

---



```
\begin{keysubfigs}{3}{c=Subfigures,l=fig:subfigs}
\keyfig{lw=1,f,c={First Subfigure},
  l=fig:firstsubfig,t=Some Text}{image}
\keyfig{lw=1,f,r=90,c={Second subfigure},
  l=fig:secondsubfig,
  t=Lots of lots of lots of lots of text.}
  {image2}
\begin{keyfloats}{1}
\keyfig{lw=1,f,c={Third subfigure},l=fig:thirdsubfig}{image}
\keytab{c={Fourth subfigure},l=fig:fourthsubfig}{\testtable}
\keyfig{lw=.5,f,c={Fifth subfigure},l=fig:fifthsubfig}{image}
\end{keyfloats}
\end{keysubfigs}
```

Figure 14

Figures 14a to 14e are in the fig. 14 `keysubfigs` environment. The `\keysubtabs` environment is similar. Mixed types have the type of their container, as shown with fig. 14d.

Subfloats are associated floats (a, b, ...) collected together into one common float

(the enclosing `\keysubfigs` or `\keysubtabs` environment). The enclosing float can have its own caption (call “Sub-Figures” in the example), which appears in the LOF/LOT, and also a label. Each subfloat can have its own caption and label as well, but the subcaption does not appear in the LOF/LOT.

-  **mixed subfloats** All subfloats are forced to have the same type as its containing float. A table inside a figure will be labeled as a figure, for example. This avoids miss-labeling as each subfloat must clearly be identified as a child of its containing float.
-  **nested subfloats** `\keysubfigs` and `\keysubtabs` may not be used inside the `keyfloats` environment, and cannot be nested inside each other. (No subfloat 12aa, 12ab, 12ba, etc.)
- nested keyfloats** The `keyfloats` environment may be used inside `\keysubfigs` or `\keysubtabs` to gather subfloats together, such as the three right-most figures in fig. 14.

Subfloats may be located H:

```
\begin{keysubfigs}[H]{3}{key/vals ...}
```

Subfloats may be starred to span both columns in a two-column format:

```
\begin{keysubfigs}*{2}{key/vals ...}
```



An image.

Figure 15: Figure to be continued



Figure 15: ...continued

### 2.3.4 Continued Floats

The `cont` key may be used to generate a “continued” float. The continued float receives the same number as the previous float, and it is assumed that they are the same float, except that they are separated for some reason such as size on the page.

The label may be placed in a continued float, and will still receive the same float number as the prior non-continued float.

---

#### Example 17: Continued figure

---

```
\begin{keyfloats}{2}
\keyfig{,c=Figure to be continued}{image}
\keyfig{c={\dots continued},cont,l=fig:firstcontinued}{image2}
\end{keyfloats}
```

---

Figure 15

---

*An image.*

a: First of a set

*An image.*

b: Second of a set

**Figure 16: A set of figures**Another  
image

c: Third of a set

Another  
image

d: Fourth of a set

**Figure 16: ...continued**

### 2.3.5 Continued Subfloats

The `keysubfigs` and `keysubtabs` environments may also be given the `cont` key. The containing environment's float receives the same number as the previous float (presumably another subfloat container).

---

**Example 18: Continued subfloats**

---

```
\begin{keysubfigs}{2}{c={A set of figures},l=fig:continuedfigures}
\keyfig{c={First of a set},l=fig:contfirst}{image}
\keyfig{c={Second of a set},l=fig:contsecond}{image}
\end{keysubfigs}
\begin{keysubfigs}{2}{c={\dots continued},cont}
\keyfig{c={Third of a set},l=fig:contthird}{image2}
\keyfig{c={Fourth of a set},l=fig:contfourth}{image2}
\end{keysubfigs}
```

---

*Figure 16*

---




Figure 17: Custom-framed image




Figure 18: Custom loosely-framed box

### 2.3.6 Custom Frames

---

#### Example 19: Custom frames with `mdframed`

---

```
\renewcommand{\KFLTtightframe}[1]{%
\begin{mdtightframe}%
#1
\end{mdtightframe}%
}
\setlength{\KFLTtightframewidth}{1pt}

\renewcommand{\KFLTlooseframe}[1]{%
\begin{mdlooseframe}[leftmargin=1.5in,rightmargin=1.5in]%
#1
\end{mdlooseframe}%
}
\setlength{\KFLTlooseframewidth}{4pt}

\keyfig{ft,c=Custom-framed image,l=fig:customframe}{image}
\keyfigbox{f,c=Custom loosely-framed box,
l=fig:customlooseframe}{A loosely-framed box.}
```

---

*Figures 17 and 18*

---

 Pkg `mdframed`  
`mdframed width`

Example 19 shows custom frames created with the `mdframed` package along with `tikz`. Note that `mdframed` uses the full `\linewidth` even if the left/right margins are explicitly set, which causes extra vertical space when rotated.

See section 2.4.1 for more details.

Figure 19: Custom shadow

Figure 20: Custom loosely-framed shadow

---

**Example 20: Custom shadows with fancybox**


---

```

\renewcommand{\KFLTtightframe}[1]{%
\setlength{\fboxrule}{.4pt}
\setlength{\fboxsep}{0pt}
\setlength{\shadowsize}{2pt}
\shadowbox{#1}%
}
\setlength{\KFLTtightframewidth}{0.4pt}

\renewcommand{\KFLTlooseframe}[1]{%
\setlength{\fboxrule}{.4pt}
\setlength{\fboxsep}{3pt}
\setlength{\shadowsize}{2pt}
\shadowbox{#1}%
}
\setlength{\KFLTlooseframewidth}{3.4pt}

\keyfig{ft,c=Custom shadow,l=fig:customshadow}{image}
\keyfigbox{f,c=Custom loosely-framed shadow,lw=.5,
l=fig:customlooseshadow}{A loosely-framed shadow box.}

```

---

*Figures 19 and 20*


---

Pkg **fancybox** Example 20 shows custom shadow frames created with the **fancybox** package. This combination respects **lw** and **w**.

See section 2.4.1 for more details.

An image.

MR. FIRST LAST III

*About the illustration.*

**Figure 21: Artist's name — image**

Some text, a quotation, a TikZ diagram — anything not an image file.

MR. LAST

**Figure 22: Artist's name — arbitrary contents**

### 2.3.7 Artist's Name

---

#### Example 21: Artist's name — image

---

```
\keyfig{ft,ap=Mr.,af=First,al=Last,as={~III},
tc={\textit{About the illustration.}},
c=Artist's name --- image,l=fig:artist}{image}
```

*Figure 21*

---



---

#### Example 22: Artist's name — arbitrary contents


---

```
\tdnameright
\begin{keyfigure}{f,ap=Mr.,al=Last,
c=Artist's name --- arbitrary contents,l=fig:artistpar}
\centering Some text, a quotation, a TikZ\ diagram ---
anything not an image file.
\end{keyfigure}
\tdnamecenter
```

*Figure 22*

---

The artist's name and optional prefix/suffix are printed below the figure, and an index entry is made for the name in (Last, First) format, or (Last) if there is no first name. If the `tocdata` package is loaded, the artist's name is also added to the List of Figures, and the `tocdata \tdname...` macros may be used to align the name.




---

### Example 23: Subfloats with an artist

---

```
\begin{keysubfigs}{2}{
  c=Artist's collection, l=fig:artistcollection,
  t={Some fully-justified text just for illustrative purposes,
    in case you have use for large explanations.
    This text may be the full \cs{linewidth} in size. \par
    Multiple paragraphs of text are allowed.},
  ap=Prefix,af=First,al=Last,as={, Suffix}
}
  \keyfig{c=Artist's First Work}{image}
  \keyfig{c=Artist's Second Work,
    tc={Commentary about the work.}}{image2}
\end{keysubfigs}
```

---

*Figure 23*

---

A group of figures may be placed into a subfloat container, which may have its own artist keys and additional text. Furthermore, each subfloat inside the collection may also have its own artist tags and additional text.

## 2.4 Customization

### 2.4.1 Custom Frames

There are two user-redefinable framing macros:

`\KFLTtightframe` and `\KFLTlooseframe`

A float's contents are placed into a box, which is passed to either of these two macros depending on the key `f` or `tf`.

Each macro takes one argument and frames it.

Each macro has an associated  $\text{\LaTeX}$  length:

`\KFLTtightframewidth` and `\KFLTlooseframewidth`

These lengths must be redefined to the expected total frame width, equal to the frame thickness plus separation.

The defaults definitions are:

```
\newcommand{\KFLTtightframe}[1]{%
\setlength{\fboxsep}{0pt}%
\setlength{\fboxrule}{.4pt}%
\fbox{#1}%
}
\setlength{\KFLTtightframewidth}{.4pt}

\newcommand{\KFLTlooseframe}[1]{%
\setlength{\fboxsep}{3pt}%
\setlength{\fboxrule}{.4pt}%
\fbox{#1}%
}
\setlength{\KFLTlooseframewidth}{3.4pt}
```

See example 19 for an example created with the `mdframed` package, and example 20 for an example created with the `fancybox` package.

### 2.4.2 Distance between Floats and Rows

rows too close/far

To spread out the distance between floats and/or rows of floats on a busy page, the following adjustments may be made. The values used in this documentation are:

```
\setlength{\floatsep}{5ex plus 1ex minus 1ex}
\setlength{\dblfloatsep}{5ex plus 1ex minus 1ex}
```

### 2.4.3 Formatting the Captions

To modify the typesetting of the captions, see the `caption` package. The settings used in this documentation are:

```
\captionsetup[figure]{
  style=default, justification=centering,
  margin=0pt, parskip=0pt, skip=1ex,
  labelfont={small,bf},textfont={small,bf}
}

\captionsetup[table]{
  style=default, justification=centering,
  margin=0pt, parskip=0pt, skip=1ex,
  labelfont={small,bf},textfont={small,bf}
}

\captionsetup[subfigure]{
  style=default, justification=centering,
  margin=0pt, parskip=0pt, skip=1ex,
  labelfont={small},textfont={small}
}

\captionsetup[subtable]{
  style=default, justification=centering,
  margin=0pt, parskip=0pt, skip=1ex,
  labelfont={small},textfont={small}
}
```



### 3 Code

#### 3.1 Required Packages

Pkg	<b>etoolbox</b>	v2.6 or later for <code>\BeforeBeginEnvironment</code> , <code>\AfterEndEnvironment</code>
		<pre> 1 \RequirePackage{etoolbox}[2011/01/03]% 2 3 \RequirePackage{xparse} 4 5 \RequirePackage{xifthen} </pre>
Pkg	<b>keyval</b>	Key processing:
		<pre> 6 \RequirePackage{xkeyval} </pre>
Pkg	<b>graphicx</b>	For <code>\includegraphics</code> and rotating:
		<pre> 7 \RequirePackage{graphicx} </pre>
Pkg	<b>caption</b>	Handles all caption-related functions:
		<pre> 8 \RequirePackage{caption}[2010/10/31]% v3.2 to support \phantomcaption </pre>
Pkg	<b>subcaption</b>	Derived from <code>caption</code> , used to handle subfloats:
		<pre> 9 \RequirePackage{subcaption} </pre>
Pkg	<b>calc</b>	Used to compute box width minus frame sep and width.
		<pre> 10 \RequirePackage{calc} </pre>
Pkg	<b>rotating</b>	Provides rotation via then <code>turn</code> environment:
		<pre> 11 \RequirePackage{rotating} </pre> <p>Rows of floats are created by a simple <code>minipage</code> environment, instead of relying on a preexisting package. This proved to be advantageous when support was added for multiple rows in one environment.</p>

#### 3.2 In-line Figures and Tables

These macros are commonly used by others.

Env **tablehere** Place a table exactly [H].

```
12 \ProvideDocumentEnvironment{tablehere}{}
13   {\bigbreak\noindent\minipage{\linewidth}\def\@capttype{table}}
14   {\endminipage\bigbreak}
```

Env **figurehere** Place a figure exactly [H].

```
15 \ProvideDocumentEnvironment{figurehere}{}
16   {\bigbreak\noindent\minipage{\linewidth}\def\@capttype{figure}}
17   {\endminipage\bigbreak}
```

### 3.3 Row Counting and Control

Used to count position and wrap at end of each row.

Ctr **KFLT@numcols** Columns per row.

```
18 \newcounter{KFLT@numcols}
```

Ctr **KFLT@thiscol** Column currently processing. 0 if not yet in a keyfloats or subfloat.

```
19 \newcounter{KFLT@thiscol}
```

Len **\KFLT@rowboxwidth** How wide is each box in the row.

```
20 \newlength{\KFLT@rowboxwidth}
```

### 3.4 Float Key Handling

Bool **KFLT@cont** Continued float?

```
21 \newboolean{KFLT@cont}{}

```

Key **cont** Continued float?

```
22 \define@key{KFLT@keys}{cont}[true]{\setboolean{KFLT@cont}{#1}}

```

**\KFLT@c** Caption storage

```
23 \newcommand{\KFLT@c}{}

```

---

Bool KFLT@cstar Starred caption?

```

24 \newboolean{KFLT@cstar}

```

Key c Caption

```

25 \define@key{KFLT@keys}{c}{%
26 {\renewcommand{\KFLT@c}{#1}\setboolean{KFLT@cstar}{false}}

```

Key cstar Caption starred?

```

27 \define@key{KFLT@keys}{cstar}{%
28 {\renewcommand{\KFLT@c}{#1}\setboolean{KFLT@cstar}{true}}

```

Key sc Short caption

```

29 \define@key{KFLT@keys}{sc}{%
30 \renewcommand{\KFLT@sc}{#1}%
31 \setboolean{KFLT@scgiven}{true}%
32 }

```

\KFLT@sc Short caption storage

```

33 \newcommand{\KFLT@sc}{}

```

Bool KFLT@scgiven Was a short caption given?

```

34 \newboolean{KFLT@scgiven}

```

\KFLT@type Float type: “figure”, “table”

```

35 \newcommand*{\KFLT@type}{}

```

\KFLT@listtype List type: “lof”, “lot”

```

36 \newcommand*{\KFLT@listtype}{}

```

Key l Label

```

37 \define@key{KFLT@keys}{l}{\renewcommand{\KFLT@l}{#1}}

```

\KFLT@l Label storage

```

38 \newcommand*{\KFLT@l}{}

```

For the tocdata package:

Key	ap	Artist prefix
	39	<code>\define@key{KFLT@keys}{ap}{\renewcommand{\KFLT@ap}{#1}}</code>
<code>\KFLT@ap</code>		Storage for artist prefix
	40	<code>\newcommand*{\KFLT@ap}{}{}</code>
Key	af	Artist first name
	41	<code>\define@key{KFLT@keys}{af}{\renewcommand{\KFLT@af}{#1}}</code>
<code>\KFLT@af</code>		Storage for artist first name
	42	<code>\newcommand*{\KFLT@af}{}{}</code>
Key	al	Artist last name
	43	<code>\define@key{KFLT@keys}{al}{\renewcommand{\KFLT@al}{#1}}</code>
<code>\KFLT@al</code>		Storage for artist last name
	44	<code>\newcommand*{\KFLT@al}{}{}</code>
Key	as	Artist suffix
	45	<code>\define@key{KFLT@keys}{as}{\renewcommand{\KFLT@as}{#1}}</code>
<code>\KFLT@as</code>		Storage for artist suffix
	46	<code>\newcommand*{\KFLT@as}{}{}</code>
<code>\KFLT@textalign</code>		Storage for text alignment.
		Used for the additional text in the float.
	47	<code>\newcommand*{\KFLT@textalign}{}{}</code>
<code>\KFLT@t</code>		Additional text storage
		Used for the additional text in the float.
	48	<code>\newcommand{\KFLT@t}{}{}</code>

Create replacement macros if tocdata is not loaded:

```

49 \@ifpackageloaded{tocdata}
50 {}
51 {
52 \newcommand{\tdtextjustify}{}
53 \newcommand{\tdtextcenter}{}
54 \newcommand{\tdtextleft}{}
55 \newcommand{\tdtextright}{}
56 \newcommand{\tdnamejustify}{}
57 \newcommand{\tdnamecenter}{}
58 \newcommand{\tdnameleft}{}
59 \newcommand{\tdnameright}{}
60 }

```

Key **t** Additional text, justified alignment.

```

61 \define@key{KFLT@keys}{t}{
62 \renewcommand{\KFLT@t}{#1}
63 \renewcommand{\KFLT@textalign}{}
64 \tdtextjustify
65 }

```

Key **tc** Additional text, centered alignment.

```

66 \define@key{KFLT@keys}{tc}{
67 \renewcommand{\KFLT@t}{#1}
68 \renewcommand{\KFLT@textalign}{\centering}
69 \tdtextcenter
70 }

```

Key **tr** Additional text, aligned to the right.

```

71 \define@key{KFLT@keys}{tr}{
72 \renewcommand{\KFLT@t}{#1}
73 \renewcommand{\KFLT@textalign}{\raggedleft}
74 \tdtextright
75 }

```

Key **tl** Additional text, aligned to the left.

```

76 \define@key{KFLT@keys}{tl}{
77 \renewcommand{\KFLT@t}{#1}
78 \renewcommand{\KFLT@textalign}{\raggedright}
79 \tdtextleft
80 }

```

**\KFLT@i** Image filename storage

```
81 \newcommand*{\KFLT@i}{}
```

Key **lw** Fraction of `\linewidth`

```
82 \define@key{KFLT@keys}{lw}{%
83 \renewcommand{\KFLT@lw}{#1}%
84 \setlength{\KFLT@w}{0pt}%
85 }
```

`\KFLT@lw` Fraction of linewidth storage: “.5”

```
86 \newcommand*{\KFLT@lw}{}
```

Key **w** Fixed width

```
87 \define@key{KFLT@keys}{w}{%
88 \setlength{\KFLT@w}{#1}%
89 \renewcommand{\KFLT@lw}{}%
90 }
```

`\KFLT@w` Width storage: “3cm”

```
91 \newlength{\KFLT@w}
```

Key **h** Fixed height

```
92 \define@key{KFLT@keys}{h}{\setlength{\KFLT@h}{#1}}
```

`\KFLT@h` Height storage: “2in”

```
93 \newlength{\KFLT@h}
```

Key **s** Scale

```
94 \define@key{KFLT@keys}{s}{\renewcommand{\KFLT@s}{#1}}
```

`\KFLT@s` Scale storage: “3”

```
95 \newcommand*{\KFLT@s}{1}
```

Key **r** Angle. 90 is counter-clockwise 90 degrees.

```
96 \define@key{KFLT@keys}{r}{\renewcommand{\KFLT@r}{#1}}
```

---

**\KFLT@r** Angle storage: “90”

```
97 \newcommand*{\KFLT@r}{0}
```

**Key f** Frame the image with `\KFLTlooseframe`.

```
98 \define@key{KFLT@keys}{f}[true]{\setboolean{KFLT@f}{#1}}
```

**Bool KFLT@f** Frame the image?

```
99 \newboolean{KFLT@f}
```

**Key ft** Tightly frame the image using `\KFLTtightframe`. This is useful for photographs, or diagrams which already have built-in margins.

```
100 \define@key{KFLT@keys}{ft}[true]{\setboolean{KFLT@ft}{#1}}
```

**Bool KFLT@ft** Tightly frame the image?

```
101 \newboolean{KFLT@ft}
```

**Key stretch** Set `\arraystretch` inside the table environment.

```
102 \define@key{KFLT@keys}{stretch}{\renewcommand{\KFLT@stretch}{#1}}
```

**\KFLT@stretch** Storage for `\arraystretch`.

```
103 \newcommand*{\KFLT@stretch}{1}
```

### 3.5 Nesting Control

**Ctr KFLT@keyfloatdepth** Depth inside a keyfigs environment

```
104 \newcounter{KFLT@keyfloatdepth}
105 \setcounter{KFLT@keyfloatdepth}{0}
```

**Bool KFLT@inkeysubfloats** Inside a keysubfigs environment?

```
106 \newboolean{KFLT@inkeysubfloats}
107 \setboolean{KFLT@inkeysubfloats}{false}
```

### 3.6 Subfloat Key Handling

These keys are for the container holding a collection of subfigures.

---

```

Bool  KFLT@subgrpcont  Continued float?

108 \newboolean{KFLT@subgrpcont}{%

Key   cont  Continued float

109 \define@key{KFLT@subgrpkeys}{cont}[true]{%
110 \setboolean{KFLT@subgrpcont}{#1}%
111 }

\KFLT@subgrpc  Sub-caption storage

112 \newcommand{\KFLT@subgrpc}{%

Bool  KFLT@subgrpcstart  Sub-caption starred?

113 \newboolean{KFLT@subgrpcstar}%

Key   c  Caption

114 \define@key{KFLT@subgrpkeys}{c}%
115 {\renewcommand{\KFLT@subgrpc}{#1}\setboolean{KFLT@subgrpcstar}{false}}

Key   cstar  Starred caption?

116 \define@key{KFLT@subgrpkeys}{cstar}%
117 {\renewcommand{\KFLT@subgrpc}{#1}\setboolean{KFLT@subgrpcstar}{true}}

Key   sc  Short caption

118 \define@key{KFLT@subgrpkeys}{sc}{%
119 \renewcommand{\KFLT@subgrpsc}{#1}%
120 \setboolean{KFLT@subgrpscgiven}{true}%
121 }

\KFLT@subgrpsc  Sub-shortcaption storage

122 \newcommand{\KFLT@subgrpsc}{%

Bool  KFLT@subgrpscgiven  Sub-shortcaption was given?

123 \newboolean{KFLT@subgrpscgiven}%

\KFLT@subgrptype  Subfloats collection type storage: “figure”, “table”

124 \newcommand*{\KFLT@subgrptype}{%

```



`\KFLT@subgrptype` Subfloats collection list type storage: “lof”, “lot”

```
125 \newcommand*{\KFLT@subgrplisttype}{}
```

`\KFLT@setsubgrpfigure` Set to figure type

```
126 \newcommand*{\KFLT@setsubgrpfigure}{%
127 \renewcommand{\KFLT@subgrptype}{figure}%
128 \renewcommand{\KFLT@subgrplisttype}{lof}%
129 }
```

`\KFLT@setsubgrptable` Set to table type

```
130 \newcommand*{\KFLT@setsubgrptable}{%
131 \renewcommand{\KFLT@subgrptype}{table}%
132 \renewcommand{\KFLT@subgrplisttype}{lot}%
133 }
```

Key 1 Label

```
134 \define@key{KFLT@subgrpkeys}{1}{\renewcommand{\KFLT@subgrpl}{#1}}
135 \newcommand*{\KFLT@subgrpl}{}%
```

`\KFLT@subgrptextalign` Storage for text alignment.

Used for the additional text in the float.

```
136 \newcommand*{\KFLT@subgrptextalign}{}%
```

`\KFLT@subgrpt` Additional text storage

Used for the additional text in the float.

```
137 \newcommand{\KFLT@subgrpt}{}%
```

Key t Additional text — full justification

```
138 \define@key{KFLT@subgrpkeys}{t}{%
139 \renewcommand{\KFLT@subgrpt}{#1}
140 \renewcommand{\KFLT@subgrptextalign}{t}%
141 \tdtextjustify
142 }
```

Key tc Additional text — center justification

```
143 \define@key{KFLT@subgrpkeys}{tc}{%
```

```

144 \renewcommand{\KFLT@subgrpt}{#1}
145 \renewcommand{\KFLT@subgrptextalign}{\centering}
146 \tdtextcenter
147 }

```

Key **t** Additional text — aligned left

```

148 \define@key{KFLT@subgrpkeys}{tl}{
149 \renewcommand{\KFLT@subgrpt}{#1}
150 \renewcommand{\KFLT@subgrptextalign}{\raggedright}
151 \tdtextleft
152 }

```

Key **t** Additional text — aligned right

```

153 \define@key{KFLT@subgrpkeys}{tr}{
154 \renewcommand{\KFLT@subgrpt}{#1}
155 \renewcommand{\KFLT@subgrptextalign}{\raggedleft}
156 \tdtextright
157 }

```

For the tocdata package:

Key **ap** Artist prefix

```

158 \define@key{KFLT@subgrpkeys}{ap}{\renewcommand{\KFLT@subgrpap}{#1}}

```

**\KFLT@subgrpap** Storage for artist prefix

```

159 \newcommand*{\KFLT@subgrpap}{}

```

Key **af** Artist first name

```

160 \define@key{KFLT@subgrpkeys}{af}{\renewcommand{\KFLT@subgrpaf}{#1}}

```

**\KFLT@subgrpaf** Storage for artist first name

```

161 \newcommand*{\KFLT@subgrpaf}{}

```

Key **al** Artist last name

```

162 \define@key{KFLT@subgrpkeys}{al}{\renewcommand{\KFLT@subgrpap}{#1}}

```

**\KFLT@subgrpap** Storage for artist last name

```

163 \newcommand*{\KFLT@subgrpap}{}

```

Key as Artist suffix

```
164 \define@key{KFLT@subgrpkeys}{as}{\renewcommand{\KFLT@subgrpas}{#1}}
```

\KFLT@subgrpas Storage for artist suffix

```
165 \newcommand*{\KFLT@subgrpas}{}%
```

### 3.7 Computing Image Width

Len \KFLT@imagewidth Computed width of the image

```
166 \newlength{\KFLT@imagewidth}
```

Len \KFLT@boxwidth Computed width of the container box

```
167 \newlength{\KFLT@boxwidth}
```

\KFLT@findwidths Figure out how wide to make an image and its container

```
168 \newcommand*{\KFLT@findwidths}{%
```

Default to a box of full \linewidth minus the potential frame:

```
169 \ifthenelse{\boolean{KFLT@ft}}{% tight frame?
170 {\setlength{\KFLT@boxwidth}{\linewidth - 2\KFLT@tightframewidth}}}%
171 {% not tight frame
172 \ifthenelse{\boolean{KFLT@f}}{% loose frame?
173 {\setlength{\KFLT@boxwidth}{\linewidth - 2\KFLT@looseframewidth}}}%
174 {\setlength{\KFLT@boxwidth}{\linewidth}}}% no frame
175 }% not tight frame
```

Several width options exist. First see if width was given:

```
176 \ifthenelse{\dimtest{\KFLT@w}{>}{0pt}}{%
```

Width was given:

```
177 {\setlength{\KFLT@imagewidth}{\KFLT@w}}%
178 {% width not given
```

Use full \linewidth or only a fraction:

```
179 \ifcempty{\KFLT@lw}%
180 {\setlength{\KFLT@imagewidth}{\KFLT@boxwidth}}%
```

```

181 {\setlength{\KFLT@imagewidth}{\KFLT@lw\KFLT@boxwidth}}%
182 }% width not given
183 }

```

### 3.8 Framing and Rotation

A user-redefinable macro and length to tightly frame the contents.

`\KFLTtightframe` may be redefined to a macro which frames its contents.  
`\KFLTtightframewidth` should be redefine to the total width of the new frame and its separation.

`\KFLT@tightframe`  $\{ \langle contents \rangle \}$

```

184 \newcommand{\KFLTtightframe}[1]{%
185 \setlength{\fboxsep}{0pt}%
186 \setlength{\fboxrule}{.4pt}%
187 \fbox{#1}%
188 }
189

```

Len Combined width of the frame and separation.

`\KFLTtightframewidth`

```

190 \newlength{\KFLTtightframewidth}
191 \setlength{\KFLTtightframewidth}{.4pt}

```

`\KFLTlooseframe`  $\{ \langle contents \rangle \}$

A user-redefinable macro and length to loosely frame the contents.

`\KFLTlooseframe` may be redefined to a macro which frames its contents.  
`\KFLTlooseframewidth` should be redefine to the total width of the new frame and its separation.

```

192 \newcommand{\KFLTlooseframe}[1]{%
193 \setlength{\fboxsep}{3pt}%
194 \setlength{\fboxrule}{.4pt}%
195 \fbox{#1}%
196 }

```

Len Combined width of the frame and separation.

`\KFLTlooseframewidth`

```

197 \newlength{\KFLTlooseframewidth}
198 \setlength{\KFLTlooseframewidth}{3.4pt}

```

`\KFLT@frame`  $\{\langle contents \rangle\}$

Frames the contents according to the `f` key. To be nested for further processing.

```
199 \newcommand{\KFLT@frame}[1]
200 {%
201 \ifthenelse{\boolean{KFLT@ft}}{%
202 {\KFLTtightframe{#1}}%
203 {% not tightframe
204 \ifthenelse{\boolean{KFLT@f}}{%
205 {\KFLTlooseframe{#1}}%
206 {#1}% no frame
207 }% not looseframe
208 }
```

`KFLT@findenvboxwidth` Figures the width of the contents of `\KFLT@envbox` plus the frame:

```
209 \newcommand{\KFLT@findenvboxwidth}{%
210 \settowidth{\KFLT@envboxwidth}{\usebox{\KFLT@envbox}}%
211 \ifthenelse{\boolean{KFLT@ft}}{%
212 {\addtolength{\KFLT@envboxwidth}{2\KFLTtightframewidth}}%
213 {% not tightframe
214 \ifthenelse{\boolean{KFLT@f}}{%
215 {\addtolength{\KFLT@envboxwidth}{2\KFLTlooseframewidth}}%
216 {}% no frame
217 }% not looseframe
218 }
```

### 3.9 A Graphics Image from a File

`\KFLT@onefigureimage` Create a stand-alone figure with an image.

```
219 \NewDocumentCommand{\KFLT@onefigureimage}{-}
220 {%
```

Several possible combinations of linewidth, width, and height are available, and each is treated separately. Scaling and width/height are done first, then framing, then rotation.

```
221 \begin{lrbox}{\KFLT@envbox}%
```

Handle the `lw` key. If `lw` is used, width and height are ignored.

```
222 \ifthenelse{\NOT\equal{\KFLT@lw}{}}{%
223 {\includegraphics%
224 [scale=\KFLT@s,width=\KFLT@imagewidth]{\KFLT@i}}%
225 {% not linewidth
```

Handle the `w` key, which may be used along with the `h` key:

```
226 \ifthenelse{\dimtest{\KFLT@w}{>}{0pt}}%
227 {% width is given
228 \ifthenelse{\dimtest{\KFLT@h}{>}{0pt}}%
```

Width and height are both given:

```
229 {% w and h
230 \includegraphics%
231 [scale=\KFLT@s,%
232 width=\KFLT@imagewidth,height=\KFLT@h]{\KFLT@i}%
233 }% w and h
```

Only width:

```
234 {% only w
235 \includegraphics%
236 [scale=\KFLT@s,width=\KFLT@imagewidth]{\KFLT@i}%
237 }% only w
238 }% width is given
```

Width was not given, so maybe handle `h` alone:

```
239 {% width is not given
240 \ifthenelse{\dimtest{\KFLT@h}{>}{0pt}}%
```

`h` was given:

```
241 {\includegraphics%
242 [scale=\KFLT@s,height=\KFLT@h]{\KFLT@i}}%
```

If none were given, use the image's natural size:

```
243 {\includegraphics%
244 [scale=\KFLT@s]{\KFLT@i}}%
245 }% width is not given
246 }% not linewidth
247 \end{lrbox}%
248 \unskip%
249 \KFLT@findenvboxwidth%
250 \begin{turn}{\KFLT@r}%
```

Encapsulate the frame in case the custom frame commands used pars:

```
251 \begin{minipage}{\KFLT@envboxwidth}%
252 \KFLT@frame{\usebox{\KFLT@envbox}}%
253 \end{minipage}%
254 \unskip%
```

```

255 \end{turn}%
256 \par%
257 \addvspace{2ex}%
258 }

```

### 3.10 Printing the Caption

`\KFLT@captioniftype`  $\{\langle figure\ or\ table\rangle\}\{\langle{} \rangle\ or\ subgrp\rangle\}$

Create a caption only if is of this float type.

The second argument is  $\{\}$  if a regular float, or `subgrp` if `\keysubfigs` or `\keysubtabs`.

```

259 \newcommand*{\KFLT@captioniftype}[2]{%
260 \ifthenelse{\equal{\csname KFLT@#2type\endcsname}{#1}}{%
261 {\KFLT@caption{#2}}%
262 {}%
263 }

```

`\KFLT@dosimplecaption`  $\{\langle star?\rangle\}\{\langle short\ cap\ or\ -NO\ VALUE-\rangle\}\{\langle caption\rangle\}$

Calls `\caption` depending on several combinations of star and short captions being given.

```

264 \NewDocumentCommand{\KFLT@dosimplecaption}{m m m}
265 {%
266 \unskip%
267 \IfBooleanTF{#1}% star?
268 {% star
269 \IfValueTF{#2}{\caption*{#2}{#3}}{\caption*{#3}}%
270 }% star
271 {% no star
272 \IfValueTF{#2}{\caption[#2]{#3}}{\caption{#3}}%
273 }% no star
274 }

```

`\KFLT@docaption`  $*[\langle short\ caption\rangle]\{\langle caption\rangle\}\{\langle{} \rangle\ or\ subgrp\rangle\}$

Depending on whether the `tocdata` package is present, and an artist is specified, use either `\caption` or `\captionartist`.

The fourth argument is  $\{\}$  if a regular float, or `subgrp` if `\keysubfigs` or `\keysubtabs`.

See Table 2 for the possible combinations of the caption-related keys: `c`, `cstar`,

and `sc`.

There are two versions, depending on whether `tocdata` is loaded.

```
275 \@ifpackageloaded{tocdata}
276 {% tocdata loaded
```

`tocdata` is loaded:

```
277 \NewDocumentCommand{\KFLT@docaption}{s o m m}
278 {%
```

Is this a figure?

```
279 \ifthenelse{\equal{\csname KFLT@#4type\endcsname}{figure}}{%
280 {% figure
```

Is the last name empty? Assume no artist if so.

```
281 \ifcseempty{KFLT@#4a1}%
282 {% figure w/o artist
```

A figure without an artist uses the simple caption.

```
283 \KFLT@dosimplecaption{#1}{#2}{#3}%
284 }% figure w/o artist
285 {% figure with an artist
```

A figure with an artist uses the `tocdata \captionartist` macro, which also creates an index entry.

```
286 \IfBooleanTF{#1}{% star
287 \captionartist*{#2}{#3}%
288 [\csname KFLT@#4t\endcsname]%
289 [\csname KFLT@#4ap\endcsname]%
290 {\csname KFLT@#4af\endcsname}%
291 {\csname KFLT@#4a1\endcsname}%
292 [\csname KFLT@#4as\endcsname]%
293 }% star
294 {% no star
295 \captionartist{#2}{#3}%
296 [\csname KFLT@#4t\endcsname]%
297 [\csname KFLT@#4ap\endcsname]%
298 {\csname KFLT@#4af\endcsname}%
299 {\csname KFLT@#4a1\endcsname}%
300 [\csname KFLT@#4as\endcsname}%
301 }% no star
302 }% figure with an artist
```



```

303 }% figure
304 {% not a figure, ignore artist information:

```

If it isn't a figure, ignore artist information and create a simple caption:

```

305 \KFLT@dosimplecaption{#1}{#2}{#3}%
306 }% not a figure
307 }% KFLT@tocdata
308 }% tocdata loaded
309 {% no tocdata
310 \NewDocumentCommand{\KFLT@docaption}{s o m}
311 {%

```

If tocdata is not loaded, use a simple caption.

```

312 \KFLT@dosimplecaption{#1}{#2}{#3}%

```

Create an index entry depending on whether there is a first name:

```

313 \ifcseempty{KFLT@#4af}%
314 {\index{\csname KFLT@#4al\endcsname}}%
315 {\index{\csname KFLT@#4al\endcsname, \csname KFLT@#4af\endcsname}}%
316 }% KFLT@docaption
317 }% no tocdata

```

`\KFLT@caption`  $\{\langle \{\} \text{ or } subgrp \rangle\}$

Caption-creation logic.

The argument is `{}` if a regular float, or `subgrp` if `\keysubfigs` or `\keysubtabs`.

See Table 2 for the possible combinations of the caption-related keys: `c`, `cstar`, and `sc`.

```

318 \newcommand{\KFLT@caption}[1]{%

```

A starred caption is printed but not numbered.

```

319 \ifthenelse{\boolean{KFLT@#1cstar}}{% starred caption?

```

This is a starred caption:

```

320 {%starred caption

```

A key given as `cstar={}` yields a float with no caption at all.

```

321 \ifcseempty{KFLT@#1c}% cstar={}?
322 {}%

```

Non-empty starred caption might have a LOF entry if it has a short caption `sc` key:

```
323 {% non-empty starred caption
324 \ifcsempy{KFLT@#1sc}%
```

No `sc` short caption, but there is a `cstar`, so no LOF entry:

```
325 {}%
```

Both `cstar` and `sc` were given, so add a LOF entry:

```
326 {% non-empty cstar and sc:
327 \addcontentsline{\KFLT@listtype}%
328 {\csname KFLT@#1type\endcsname}{\KFLT@sc}%
329 }% non-empty cstar and sc
```

`cstar` was given, so create an unnumbered caption:

```
330 \KFLT@docaption*{\csname KFLT@#1c\endcsname}{#1}%
331 }%
332 }% starred caption
```

Unstarred caption `c` was given, so number this float:

```
333 {% unstarred caption
334 \ifcsempy{KFLT@#1sc}%
335 {% no short cap
336 \KFLT@docaption{\csname KFLT@#1c\endcsname}{#1}%
337 }% no short cap
338 {% short cap
339 \KFLT@docaption[\csname KFLT@#1sc\endcsname]%
340 {\csname KFLT@#1c\endcsname}{#1}%
341 }% short cap
```

Optional label:

```
342 \ifcsempy{KFLT@#1l}%
343 {}%
344 {\label{\csname KFLT@#1l\endcsname}}%
345 }% unstarred caption
346 }
```

### 3.11 Defaults for a New Float

`\KFLT@defaults` Defaults all settings before reading the keys.

```

347 \newcommand*{\KFLT@defaults}{%
348 \setboolean{KFLT@cont}{false}%
349 \renewcommand{\KFLT@c}{}%
350 \setboolean{KFLT@cstar}{false}%
351 \renewcommand{\KFLT@sc}{}%
352 \setboolean{KFLT@scgiven}{false}%
353 \renewcommand{\KFLT@type}{figure}%
354 \renewcommand{\KFLT@listtype}{lof}%
355 \renewcommand{\KFLT@l}{}%
356 \renewcommand{\KFLT@ap}{}%
357 \renewcommand{\KFLT@af}{}%
358 \renewcommand{\KFLT@al}{}%
359 \renewcommand{\KFLT@as}{}%
360 \renewcommand{\KFLT@t}{}%
361 \renewcommand{\KFLT@textalign}{}%
362 \tdtextjustify%
363 \renewcommand{\KFLT@i}{}%
364 \renewcommand{\KFLT@lw}{}%
365 \setlength{\KFLT@w}{0pt}%
366 \setlength{\KFLT@h}{0pt}%
367 \renewcommand{\KFLT@s}{1}%
368 \renewcommand{\KFLT@r}{0}%
369 \setboolean{KFLT@f}{false}%
370 \setboolean{KFLT@ft}{false}%
371 \renewcommand{\KFLT@stretch}{1}%
372 }

```

### 3.12 Row Start/End Processing

`\KFLT@maybestartfloatrow` Counts rows

After ending a preexisting row, move to the next row. The use of `\defcounter` makes this counter change local.

```

373 \newcommand*{\KFLT@maybestartfloatrow}{%
374 \KFLT@maybeendfloatrow%
375 \defcounter{KFLT@thiscol}{\value{KFLT@thiscol}+1}%
376 }

```

`\KFLT@maybeendfloatrow` Counts rows

Adds vertical space then resets to allow the start of a new row. The use of `\defcounter` makes this counter change local.

```

377 \newcommand*{\KFLT@maybeendfloatrow}{%
378 \ifthenelse{\cnttest{\value{KFLT@thiscol}}{>=}{\value{KFLT@numcols}}}{%
379 {%

```

```

380
381 \addvspace{.75\floatsep}%
382
383 \defcounter{KFLT@thiscol}{0}%
384 }{}%
385 }%

```

### 3.13 Key Environment Helper Macros

`\KFLT@trackrows` Tracks and spaces rows and columns.

```

386 \newcommand{\KFLT@trackrows}
387 {%

```

If are nested inside a keyfloats or a subfloat:

```

388 \ifthenelse{%
389 \cnttest{\value{KFLT@keyfloatdepth}}>{0}%
390 \OR\boolean{KFLT@inkeysubfloats}%
391 }%
392 {% nested

```

Tracks row start and end:

```

393 \KFLT@maybestartfloatrow%

```

Possibly fill space between columns:

```

394 \ifthenelse{\cnttest{\value{KFLT@thiscol}}>{1}}%
395 {\hfill}{}%
396 }% nested
397 {}% not nested
398 }

```

`\KFLT@addtext` `{\{ or subgrp\}}`

Adds optional additional text.

The argument is `{}` if a regular float, or `subgrp` if `\keysubfigs` or `\keysubtabs`.

```

399 \newcommand{\KFLT@addtext}[1]
400 {%

```

Is there text to add?

```

401 \ifcempty{KFLT@#1t}%

```

```

402 {}% no text
403 {}% text to add
404 {}% local

```

Add some space, then create a full-width minipage to contain the text:

```

405 \addvspace{2ex}%
406 \begin{minipage}{\linewidth}%

```

Set the alignment and some text parameters:

```

407 \csname KFLT@#1textalign\endcsname%
408 \footnotesize%
409 \setlength{\parskip}{1.5ex}%
410 \setlength{\parindent}{0em}%

```

Typeset the actual text:

```

411 \csname KFLT@#1t\endcsname%

```

Close it all out with a little more space:

```

412 \end{minipage}%
413 \par\addvspace{2ex}%
414 }% local
415 }% text to add
416 }

```

`\KFLT@optionalname`  $\{\langle name \rangle\}$

Adds optional artist's name and the following space.

```

417 \newcommand{\KFLT@optionalname}[1]
418 {%
419 \ifthenelse{\equal{#1}{}}{}%
420 {}%
421 {#1~}%
422 }

```

`\KFLT@addartisttext`  $\{\{\} \text{ or } subgrp\}$

Adds optional artist's name and add'l text.

The argument is `{}` if a regular float, or `subgrp` if `\keysubfigs` or `\keysubtabs`.

One of two versions is used, depending on whether the `tocdata` package is available.

If `tocdata` is loaded, this float is a figure, and artist information is given, then

the float's artist's information and optional text will be printed elsewhere by `\KFLT@caption`. Otherwise, it is printed here along with the text.

Two versions, depending on whether `tocdata` is loaded:

```
423 \@ifpackageloaded{tocdata}
424 {% tocdata loaded
```

If `tocdata` is loaded:

```
425 \newcommand{\KFLT@addartisttext}[1]
426 {%
```

Only use the artist name if this is a figure:

```
427 \ifthenelse{\equal{\csname KFLT@#1type\endcsname}{figure}}{%
428 {% figure
```

Only use the artist name if a last name is given:

```
429 \ifcsemtyp{KFLT@#1al}%
```

A figure but no artist:

```
430 {\KFLT@addtext{#1}}%
```

A figure with an artist: will be handled by `tocdata` when the caption is created.

```
431 {%} fig w/ artist: text will be added by \captionartist in \KFLT@caption
432 {%} figure
```

If not a figure, ignore artist information:

```
433 {\KFLT@addtext{#1}}%
434 }% KFLT@addartisttext
435 }% tocdata loaded
```

If `tocdata` is not loaded:

```
436 {% tocdata not loaded
437 \newcommand{\KFLT@addartisttext}[1]
438 {%
```

Only use the artist information if a last name is given:

```
439 \ifcsemtyp{KFLT@#1al}%
440 {}% last name not given
441 {% last name given
```

Add space and create the name inside a full-width minipage:

```
442 \addvspace{2ex}%
443 \begin{minipage}{\linewidth}%
```

If `tocdata` is not used, the artist's name is always centered:

```
444 \centering\footnotesize\textsc{%
445 \KFLT@optionalname{\csname KFLT@#1ap\endcsname}%
446 \KFLT@optionalname{\csname KFLT@#1af\endcsname}%
447 \csname KFLT@#1al\endcsname\csname KFLT@#1as\endcsname%
448 }%
449 \end{minipage}%
450 \par\addvspace{2ex}%
451 }% last name given
```

Any additional text follows the artist's name:

```
452 \KFLT@addtext{#1}%
453 }% KFLT@addartisttext
454 }% tocdata not loaded
```

**Env** `KFLT@boxinner` Typeset the contents in a width which depends on the keys.

```
455 \newsavebox{\KFLT@envbox}
456 \newlength{\KFLT@envboxwidth}
457
458 \NewDocumentEnvironment{KFLT@boxinner}{}
459 {% keyboxinner
```

(Possibly) frame the contents of an `lrbox`:

```
460 \begin{lrbox}{\KFLT@envbox}%
```

Rotate the contents:

```
461 \turn{\KFLT@r}%
```

Box the contents in the width computed by `\KFLT@findwidths`:

```
462 \minipage{\KFLT@imagewidth}%
```

Spacing inside the box. Also default to regular justified text alignment.

```
463 \setlength{\parskip}{2ex}%
464 \renewcommand{\arraystretch}{\KFLT@stretch}%
465 }% keyboxinner
```

End of the environment:

```
466 {% endkeyboxinner
467 \endminipage%
```

End the rotated box:

```
468 \endturn%
```

Possibly frame:

```
469 \end{lrbox}%
470 \KFLT@frame{\usebox{\KFLT@envbox}}%
471 \par\addvspace{\medskipamount}%
472 }% endkeyboxinner
```

`\KFLT@boxkeys`  $\{\langle keys \rangle\}$   $\{\langle figure/table \rangle\}$   $\{\langle lof/lot \rangle\}$

Default the options, adjust for a table, then parse the keys:

```
473 \NewDocumentCommand{\KFLT@boxkeys}{+m m m}
474 {%
475 \KFLT@defaults%
476 \renewcommand{\KFLT@type}{#2}%
477 \renewcommand{\KFLT@listtype}{#3}%
478 \setkeys{KFLT@keys}{#1}%
479 }
```

Env `KFLT@boxouter`  $\{\langle star? \rangle\}$   $\{\langle loc \rangle\}$

Boxes the contents of figures and floats.

Not used by subfigures.

```
480 \NewDocumentEnvironment{KFLT@boxouter}{m m}
481 {% keyboxouter
```

The `keytable` environment boxes the contents inside an optional frame of hrules, then handles them in either of three possible ways, depending on whether it is called alone, inside a `keyfloats` environment, or inside a `keysubtabs` environment.

Start the new subfigure or subtable, of the given width:

```
482 \ifthenelse{\boolean{KFLT@inkeysubfloats}}%
483 {\csname sub\KFLT@type\endcsname{\KFLT@rowboxwidth}}% subfloat
```

If `keyfloats`, place the contents inside a `minipage`:



```

484 {% not subfloat:
485 \ifthenelse{\cnttest{\value{KFLT@keyfloatdepth}}>{0}}%
486 {% keyfloats
487 \minipage{\KFLT@rowboxwidth}%
488 \captionsetup{type=\KFLT@type}%
489 }% keyfloats
490 {% not keyfloats

```

Not a subfloat or `keyfloats`, so create a single float.

See if the float should be positioned [H]ere:

```

491 \ifthenelse{\equal{#2}{H}}%

```

Place [H], so create an inline minipage:

```

492 {% [H]
493 \noindent\minipage{\linewidth}%
494 \captionsetup{type=\KFLT@type}%
495 }% [H]

```

Not [H], so create a float: For a starred float, make a two-column table in a two-col format.

```

496 {% not [H]
497 \IfBooleanTF{#1}%
498 {\csname \KFLT@type*\endcsname[#2]}{\csname \KFLT@type\endcsname[#2]}%
499 }% not [H]
500 }% not keyfloats
501 }% not subfloat

```

Handle a continued float. Ignored if in a subfloat.

```

502 \ifthenelse{\boolean{KFLT@cont}}{\ContinuedFloat}{}%

```

Figure out image and parbox widths for the contents:

```

503 \KFLT@findwidths%

```

If a table, place the caption above the contents:

```

504 \KFLT@captioniftype{table}{}%

```

Typeset the contents:

```

505 \begin{center}%
506 \unskip%
507 \minipage{\linewidth}%
508 \centering%

```

509 }% keyboxouter

End of the keyboxouter environment:

```
510 {% endboxouter
511 \endminipage%
512 \end{center}%
513 \unskip\addvspace{\medskipamount}%
```

Optionally print artist's name and additional text:

514 \KFLT@addartisttext{}

If a figure, typeset the caption below the contents:

515 \KFLT@captioniftype{figure}{}

If are inside keysubtabs, end the subtable:

```
516 \ifthenelse{\boolean{KFLT@inkeysubfloats}}%
517 {\csname endsub\KFLT@type\endcsname}% subfloat
518 {% not subfloat
519 \ifthenelse{\cnttest{\value{KFLT@keyfloatdepth}}>{0}}% keyfloat?
520 {\endminipage}% keyfloats
521 {% not keyfloats
```

Not subfloat or keyfloats, so is an individual float.

Close the minipage or float:

```
522 \ifthenelse{\equal{#2}{H}}%
523 {%
524 \endminipage% [H]
525 }%
526 {% not [H]
527 \IfBooleanTF{#1}% starred table?
528 {\csname end\KFLT@type*\endcsname}{\csname end\KFLT@type\endcsname}%
529 }% not [H]
530 }% not keyfloats
531 }% not subfloat
532 }% endkeyboxouter
```

### 3.14 The keyfigure Environment

Env `keyfigure` \* [*loc*] {*keys/values*}

```

533 \NewDocumentEnvironment{keyfigure}{s O{tbp} +m}
534 {%
535 \KFLT@boxkeys{#3}{figure}{lof}%
536 \KFLT@boxouter{#1}{#2}%
537 \KFLT@boxinner%
538 }%
539 {%
540 \endKFLT@boxinner%
541 \endKFLT@boxouter%
542 }

```

**Before keyfigure** Extra code to track rows outside of the `keyfigure` environment, before it starts. This is done to allow nesting without losing track of the prior level.

```

543 \BeforeBeginEnvironment{keyfigure}{%
544 \KFLT@trackrows%
545 }

```

### 3.15 The `\keyfig` Macro

`\keyfig` \* [*loc*] {*keys/values*} {*image filename*}

A user-level macro to generate a figure with an image. This may be used by itself, or inside a `keyfloats` or `keysubfigs` environment.

```

546 \NewDocumentCommand{\keyfig}{s O{tbp} +m m}
547 {%
548 \KFLT@trackrows%
549 \KFLT@boxkeys{#3}{figure}{lof}%

```

After setting default values, override with the filename:

```

550 \renewcommand{\KFLT@i}{#4}%
551 \KFLT@boxouter{#1}{#2}%
552 \KFLT@onefigureimage%
553 \endKFLT@boxouter%
554 }

```

### 3.16 The `\keyfigbox` Macro

`\keyfigbox` \* [*loc*] {*keys/values*} {*box contents*}

A user-level macro to generate a figure with arbitrary paragraph contents. This may be used by itself, or inside a `keyfloats` or `keysubtabs` environment.

```

555 \NewDocumentCommand{\keyfigbox}{s O{tbp} +m +m}
556 {%
557 \KFLT@trackrows%
558 \KFLT@boxkeys{#3}{figure}{lof}%
559 \KFLT@boxouter{#1}{#2}%
560 \KFLT@boxinner%
561 #4%
562 \endKFLT@boxinner%
563 \endKFLT@boxouter%
564 }

```

### 3.17 The \keyparbox Macro

`\keyparbox` \* [*loc*] {*keys/values*} {*box contents*}

A user-level macro to generate a figure with arbitrary paragraph contents, but no number or caption. This is equal to a `\keyfigbox` with `cstar={}`. This may be used by itself, or inside a `keyfloats` or `keysubtabs` environment.

```

565 \NewDocumentCommand{\keyparbox}{s O{tbp} +m +m}
566 {%
567 \KFLT@trackrows%
568 \KFLT@boxkeys{#3}{figure}{lof}%

```

Force `cstar={}`:

```

569 \renewcommand{\KFLT@c}{}%
570 \setboolean{KFLT@cstar}{true}%

```

Continue like `\figbox`:

```

571 \KFLT@boxouter{#1}{#2}%
572 \KFLT@boxinner%
573 #4%
574 \endKFLT@boxinner%
575 \endKFLT@boxouter%
576 }

```

### 3.18 The \keytab Macro

`\keytab` \* [*loc*] {*keys/values*} {*tabular contents*}

A user-level macro to generate a table with tabular contents. This may be used by

itself, or inside a `keyfloats` or `keysubtabs` environment.

```

577 +
578 \NewDocumentCommand{\keytab}{s O{tbp} +m +m}
579 {%
580 \KFLT@trackrows%
581 \KFLT@boxkeys{#3}{table}{lot}%
582 \KFLT@boxouter{#1}{#2}%
583 \KFLT@boxinner%
584 \centering%
585 #4%
586 \endKFLT@boxinner%
587 \endKFLT@boxouter%
588 }

```

### 3.19 The keytable Environment

`Env keytable` \* [*loc*] {*keys/values*}

```

589 \NewDocumentEnvironment{keytable}{s O{tbp} +m}
590 {%
591 \KFLT@boxkeys{#3}{table}{lot}%
592 \KFLT@boxouter{#1}{#2}%
593 \KFLT@boxinner%
594 \centering%
595 }%
596 {%
597 \endKFLT@boxinner%
598 \endKFLT@boxouter%
599 }

```

`Before keytable` Extra code to track rows outside of the `keytable` environment, before it starts. This is done to allow nesting without losing track of the prior level.

```

600 \BeforeBeginEnvironment{keytable}{%
601 \KFLT@trackrows%
602 }

```

### 3.20 A Row of Floats

`\KFLT@nonest` Error message if tried to nest subfloats.

```

603 \newcommand*{\KFLT@nonest}{%
604 \ifthenelse{%

```

```

605 \cnttest{\value{KFLT@keyfloatdepth}}>{0}%
606 \OR\boolean{KFLT@inkeysubfloats}%
607 }%
608 {%
609 \PackageError{keyfloat}{Cannot nest keysubfigs or keysubtabs.%
610 (Not in outer par mode.)}%
611 {The subcaption package do not support nested environments, so%
612 the keyfloat package cannot place a keysubfigs or keysubtabs%
613 environment inside another, or inside a keyfloats.}%
614 }%
615 {}%
616 }

```

Env **keyfloats** \* [*loc*] {*num columns*}

User-level macro to create rows of figures/tables. Wrapping occurs after the number of specified columns. **keyfloats** environments may be nested to create a vertical set of figures next to a single larger figure, for example.

Place **\keyfig**, **\keyfigbox**, and **\keytab** commands inside the **keyfloats** environment.

Note that **lw** linewidth keys may need to be adjusted inside a **keyfloats**, **\keysubfigs**, or **\keysubtabs**, since **\linewidth** changes depending on the number of columns. Likewise, manually-selected **w** width and **h** tags may need to be adjusted to prevent overflow.

```

617 \NewDocumentEnvironment{keyfloats}{s O{tbp} m}
618 {%

```

Nest the environment:

```

619 \addtocounter{KFLT@keyfloatdepth}{1}%

```

If [H] or nested, use a minipage instead of a float:

```

620 \ifthenelse{%
621 \equal{#2}{H}%
622 \OR\cnttest{\value{KFLT@keyfloatdepth}}>{1}%
623 \OR\boolean{KFLT@inkeysubfloats}%
624 }%

```

Create an inline minipage:

```

625 {% [H] or nested

```

If nested, use different spacing as was computed in the outer nesting level:

```

626 \ifthenelse{%
627 \cnttest{\value{KFLT@keyfloatdepth}}>{1}}%
628 \OR\boolean{KFLT@inkeysubfloats}%
629 }%
630 {\noindent%
631 \begin{minipage}{\KFLT@rowboxwidth}}%
632 {\bigbreak%
633 \noindent\begin{minipage}{\linewidth}}%

```

If inside subfloats, generate subfigures by default:

```

634 \ifthenelse{\boolean{KFLT@inkeysubfloats}}%
635 {}{\captionsetup{type=figure}}%
636 }% [H] or nested

```

Isn't [H] or nested, so create a figure:

```

637 {% figure
638 \IfBooleanTF{#1}% starred figure, two-col figure in a two-col format
639 {\begin{figure*}[#2]}\begin{figure}[#2]}%
640 }% figure

```

Compute the width of each entry:

```

641 \ifthenelse{%
642 \cnttest{\value{KFLT@keyfloatdepth}}>{1}}%
643 \OR\boolean{KFLT@inkeysubfloats}%
644 }%

```

Nested or subfloats:

```

645 {\setlength{\KFLT@rowboxwidth}{.9\KFLT@rowboxwidth/\real{#3}}}%

```

Keyfloats:

```

646 {\setlength{\KFLT@rowboxwidth}{.9\linewidth/\real{#3}}}%

```

Center the contents:

```

647 \centering%

```

Count columns using \defcounter for a local effect:

```

648 \defcounter{KFLT@numcols}{#3}%
649 \defcounter{KFLT@thiscol}{0}%
650 }% starting keyfloats environment

```

When ending a keyfloats environment:

651 {% ending keyfloats environment

[H] or rows/subfigs? Close a minipage:

```
652 \ifthenelse{%
653 \equal{#2}{H}%
654 \OR\cnttest{\value{KFLT@keyfloatdepth}}>{1}%
655 \OR\boolean{KFLT@inkeysubfloats}%
656 }%
657 {\end{minipage}}%
```

Spacing if nested:

```
658 \ifthenelse{\cnttest{\value{KFLT@keyfloatdepth}}>{0}}%
659 {}{\bigbreak}%
660 }% was [H]
```

Was not [H], so close a figure:

```
661 {% not [H]
662 \IfBooleanTF{#1}% starred figure?
663 {\end{figure*}}{\end{figure}}%
664 }% not [H]
```

Unnest the environment:

```
665 \addtocounter{KFLT@keyfloatdepth}{-1}%
666 }
```

**Before keyfloats** Extra code to track rows outside of the `keyfloats` environment, before it starts. This is done to allow nesting without losing track of the prior level.

```
667 \BeforeBeginEnvironment{keyfloats}{%
```

Track rows:

```
668 \ifthenelse{%
669 \cnttest{\value{KFLT@keyfloatdepth}}>{0}%
670 \OR\boolean{KFLT@inkeysubfloats}%
671 }%
672 {\KFLT@maybestartfloatrow}{}%
```

Possibly fill space between columns:

```
673 \ifthenelse{\cnttest{\value{KFLT@thiscol}}>{1}}%
674 {\hfill}{}%
675 }
```



### 3.21 Subfigures

`\KFLT@subgrpdefaults` Sets defaults before reading the keys.

```

676 \newcommand*{\KFLT@subgrpdefaults}{%
677 \setboolean{KFLT@subgrpcont}{false}%
678 \renewcommand{KFLT@subgrpc}{}%
679 \setboolean{KFLT@subgrpcstar}{false}%
680 \renewcommand{KFLT@subgrpsc}{}%
681 \setboolean{KFLT@subgrpscgiven}{false}%
682 \renewcommand{KFLT@subgrptype}{figure}%
683 \renewcommand{KFLT@subgrplisttype}{lof}%
684 \renewcommand{KFLT@subgrpl}{}%
685 \renewcommand{KFLT@subgrpap}{}%
686 \renewcommand{KFLT@subgrpapf}{}%
687 \renewcommand{KFLT@subgrpapf}{}%
688 \renewcommand{KFLT@subgrpas}{}%
689 \renewcommand{KFLT@subgrpt}{}%
690 \renewcommand{KFLT@subgrptextalign}{l}
691 \tdtextjustify
692 }
```

`\KFLT@subfloats`  $\{\langle starred? \rangle\} \{\langle loc \rangle\} \{\langle cols \rangle\} \{\langle keys/values \rangle\}$

Start a subfloat environment

```

693 \NewDocumentCommand{\KFLT@subfloats}{m m m +m}
694 {%
```

Parse the key-value combinations:

```

695 \setkeys{KFLT@subgrpkeys}{#4}%
```

Nest the environment:

```

696 \setboolean{KFLT@inkeysubfloats}{true}%
```

Figure out the width of each subfloat. If starred, use the full-page `\textwidth`, else use `\linewidth`. `.9` is used to leave a little room between columns.

```

697 \IfBooleanTF{#1}%
698 {\setlength{KFLT@rowboxwidth}{.9\textwidth/\real{#3}}}%
699 {\setlength{KFLT@rowboxwidth}{.9\linewidth/\real{#3}}}%
```

If [H], create an inline minipage:

```

700 \ifthenelse{\equal{#2}{H}}{%
701 {%
```

```

702 \bigbreak\noindent\begin{minipage}{\linewidth}%
703 }%

```

Isn't [H], so create a float, possibly starred:

```

704 {%
705 \IfBooleanTF{#1}%
706 {\begin{KFLT@type*}[#2]}\begin{KFLT@type}[#2]}%
707 }%

```

Set the caption type:

```

708 \captionsetup{type=KFLT@subgrptype}%

```

Process continued floats:

```

709 \ifthenelse{\boolean{KFLT@subgrpcont}}{\ContinuedFloat}{}%

```

Center the contents:

```

710 \centering%

```

If this is a table, place the caption above the contents:

```

711 \KFLT@captioniftype{table}{subgrp}%

```

Not yet started a row of subfloats. The use of `\defcounter` makes these changes local.

```

712 \defcounter{KFLT@numcols}{#3}%
713 \defcounter{KFLT@thiscol}{0}%

```

Creat a group for the subfloats. Necessary in case they change `\tdtextcenter`, etc.

```

714 \begingroup%
715 }

```

```
\KFLT@endsubfloats {\starred?} {\loc}
```

Ends a subfloat environment.

```

716 \newcommand*{\KFLT@endsubfloats}[2]{%

```

End the group containing the subfloats:

```

717 \endgroup%

```

A little extra space at the bottom:

```
718 \par\addvspace{\bigskipamount}%
```

Optionally print artist's name and additional text:

```
719 \KFLT@addartisttext{subgrp}%
```

If this was a figure, place the caption below the contents:

```
720 \KFLT@captioniftype{figure}{subgrp}%
```

End the float or minipage:

```
721 \ifthenelse{\equal{#2}{H}}%
722 {\end{minipage}\bigbreak}% was [H]
723 {% not [H]:
724 \IfBooleanTF{#1}% starred?
725 {\end{\KFLT@type*}}{\end{\KFLT@type}}%
726 }% not [H]
```

Unnest the environment:

```
727 \setboolean{KFLT@inkeysubfloats}{false}%
728 }
```

**Env** **keysubfigs** \* [*loc*] {*numcols*} {*keys/values*}

A group of subfigures typeset in rows.

```
729 \NewDocumentEnvironment{keysubfigs}{s O{tbp} m +m}
730 {%
```

Error if trying to nest environments:

```
731 \KFLT@nonest%
```

Default the options:

```
732 \KFLT@subgrpdefaults%
```

Start of the environment:

```
733 \KFLT@subfloats{#1}{#2}{#3}{#4}%
734 }% the start of the environment
```

end of the environment:

```

735 {%
736 \KFLT@endsubfloats{#1}{#2}%
737 }

```

Env **keysubtabs** \* [*loc*] {*numcols*} {*keys/values*}

A group of subtables typeset in rows.

```

738 \NewDocumentEnvironment{keysubtabs}{s O{tbp} m +m}
739 {%

```

Error if trying to nest environments:

```

740 \KFLT@nonest%

```

Default the options:

```

741 \KFLT@subgrpdefaults%

```

Default to table float type:

```

742 \KFLT@setsubgrptable%

```

Start of the environment:

```

743 \KFLT@subfloats{#1}{#2}{#3}{#4}%
744 }% the start of the environment

```

End of the environment:

```

745 {%
746 \KFLT@endsubfloats{#1}{#2}%
747 }

```

# Change History and Index

## Change History

v0.10	paragraph handling. . . . .	52	
General: 2016/12/01 Initial ver. . . . .	1	General: 2016/12/02 . . . . .	1
v0.11	\KFLT@addtext: Improved		

## Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

Symbols		
* (argument) . . . . .	8	KFLT@ft . . . . . 39
\linewidth . . . . .	16	KFLT@inkeysubfloats . . . . . 39
subfloats . . . . .	21	KFLT@scgiven . . . . . 35
with rotation . . . . .	18	KFLT@subgrpcont . . . . . 40
[H] (argument) . . . . .	8	KFLT@subgrpctestart . . . . . 40
[loc] (argument) . . . . .	8	KFLT@subgrpctestgiven . . . . . 40
A		C
af (key) . . . . .	36, 42	c (key) . . . . . 35, 40
al (key) . . . . .	36, 42	calc (package) . . . . . 33
ap (key) . . . . .	36, 42	caption
arguments:		formatting . . . . . 32
* . . . . .	8	options . . . . . 11
[H] . . . . .	8	caption (package) . . . . . 33
[loc] . . . . .	8	cont (key) . . . . . 34, 40
as (key) . . . . .	36, 43	counters:
B		KFLT@keyfloatdepth . . . . . 39
Before keyfigure . . . . .	59	KFLT@numcols . . . . . 34
Before keyfloats . . . . .	64	KFLT@thiscol . . . . . 34
Before keytable . . . . .	61	cstar (key) . . . . . 35, 40
booleans:		D
KFLT@cont . . . . .	34	distance between floats . . . . . 31
KFLT@cstar . . . . .	35	E
KFLT@f . . . . .	39	environments:
		figurehere . . . . . <u>15</u>

keyfigure	8, <a href="#">533</a>	ap	36, <a href="#">42</a>
keyfloats	8, <a href="#">617</a>	as	36, <a href="#">43</a>
keysubfigs	8, <a href="#">729</a>	c	35, <a href="#">40</a>
keysubtabs	8, <a href="#">738</a>	cont	34, <a href="#">40</a>
keytable	8, <a href="#">589</a>	cstar	35, <a href="#">40</a>
KFLT@boxinner	<a href="#">455</a>	f	39
KFLT@boxouter	<a href="#">480</a>	ft	39
tablehere	<a href="#">12</a>	h	38
etoolbox (package)	33	l	35, <a href="#">41</a>
<b>F</b>		lw	38
f (key)	39	r	38
fancybox (package)	28	s	38
figurehere (environment)	<a href="#">15</a>	sc	35, <a href="#">40</a>
float		stretch	39
default width	12	t	37, <a href="#">41</a> , <a href="#">42</a>
distance between	31	tc	37
frame		tl	37
custom	31	tr	37
rotation	18	w	38
ft (key)	39	keysubfigs (environment)	8, <a href="#">729</a>
<b>G</b>		keysubtabs (environment)	8, <a href="#">738</a>
graphicx (package)	33	\keytab	8, <a href="#">577</a>
<b>H</b>		keytable (environment)	8, <a href="#">589</a>
h (key)	38	keyval (package)	33
<b>I</b>		\KFLT@addartisttext	<a href="#">423</a>
image		\KFLT@addtext	<a href="#">399</a>
\linewidth	16	\KFLT@aaf	<a href="#">42</a>
natural size	12	\KFLT@aaf	<a href="#">44</a>
<b>K</b>		\KFLT@ap	<a href="#">40</a>
\keyfig	8, <a href="#">546</a>	\KFLT@as	<a href="#">46</a>
\keyfigbox	8, <a href="#">555</a>	KFLT@boxinner (environment)	<a href="#">455</a>
keyfigure (environment)	8, <a href="#">533</a>	\KFLT@boxkeys	<a href="#">473</a>
keyfloats		KFLT@boxouter (environment)	<a href="#">480</a>
\linewidth	16	\KFLT@boxwidth (length)	<a href="#">166</a>
keys	9	\KFLT@c	<a href="#">23</a>
nested	24	\KFLT@caption	<a href="#">318</a>
keyfloats (environment)	8, <a href="#">617</a>	\KFLT@captionifttype	<a href="#">259</a>
\keyparbox	8, <a href="#">565</a>	KFLT@cont (boolean)	34
keys		KFLT@cstar (boolean)	35
and values	10, 11	\KFLT@defaults	<a href="#">347</a>
keyfloats	9	\KFLT@docaption	<a href="#">275</a>
subfloats	9	\KFLT@dosimplecaption	<a href="#">264</a>
keys:		\KFLT@endsubfloats	<a href="#">716</a>
af	36, <a href="#">42</a>	KFLT@f (boolean)	39
al	36, <a href="#">42</a>	\KFLT@findenvboxwidth	<a href="#">209</a>
		\KFLT@findwidths	<a href="#">168</a>
		\KFLT@frame	<a href="#">199</a>
		KFLT@ft (boolean)	39
		\KFLT@h	<a href="#">93</a>
		\KFLT@i	<a href="#">81</a>

\KFLT@imagewidth (length) . . . . .	165	lengths:	
KFLT@inkeysubfloats (boolean) . . .	39	\KFLT@boxwidth . . . . .	43
KFLT@keyfloatdepth (counter) . . . .	39	\KFLT@imagewidth . . . . .	43
\KFLT@l . . . . .	38	\KFLT@rowboxwidth . . . . .	34
\KFLT@listtype . . . . .	36	\KFLT@looseframewidth . . . . .	44
\KFLT@lw . . . . .	86	\KFLT@tightframewidth . . . . .	44
\KFLT@maybeendfloatrow . . . . .	377	lw (key) . . . . .	38
\KFLT@maybestartfloatrow . . . . .	373		
\KFLT@nonest . . . . .	603	<b>M</b>	
KFLT@numcols (counter) . . . . .	34	mdframed (package) . . . . .	27
\KFLT@onefigureimage . . . . .	219		
\KFLT@optionalname . . . . .	417	<b>P</b>	
\KFLT@r . . . . .	97	packages:	
\KFLT@rowboxwidth (length) . . . . .	19	calc . . . . .	33
\KFLT@s . . . . .	95	caption . . . . .	33
\KFLT@sc . . . . .	33	etoolbox . . . . .	33
KFLT@scgiven (boolean) . . . . .	35	fancybox . . . . .	28
\KFLT@setsubgrpfigure . . . . .	126	graphicx . . . . .	33
\KFLT@setsubgrptable . . . . .	130	keyval . . . . .	33
\KFLT@stretch . . . . .	103	mdframed . . . . .	27
\KFLT@subfloats . . . . .	693	rotating . . . . .	33
\KFLT@subgrpaf . . . . .	161	subcaption . . . . .	33
\KFLT@subgrpap . . . . .	163		
\KFLT@subgrpap . . . . .	159	<b>R</b>	
\KFLT@subgrpas . . . . .	165	r (key) . . . . .	38
\KFLT@subgrpc . . . . .	112	rotate	
KFLT@subgrpcont (boolean) . . . . .	40	box width and vertical space . . .	18
KFLT@subgrpstart (boolean) . . . . .	40	rotating (package) . . . . .	33
\KFLT@subgrpdefaults . . . . .	676		
\KFLT@subgrpssc . . . . .	122	<b>S</b>	
KFLT@subgrpsscgiven (boolean) . . . .	40	s (key) . . . . .	38
\KFLT@subgrpt . . . . .	137	sc (key) . . . . .	35, 40
\KFLT@subgrptextalign . . . . .	136	stretch (key) . . . . .	39
\KFLT@subgrptype . . . . .	124, 125	subcaption (package) . . . . .	33
\KFLT@t . . . . .	48	subfloat	
\KFLT@textalign . . . . .	47	\linewidth . . . . .	16, 21
KFLT@thiscol (counter) . . . . .	34	distance between . . . . .	31
\KFLT@tightframe . . . . .	184	keys . . . . .	9
\KFLT@trackrows . . . . .	386	nested . . . . .	24
\KFLT@type . . . . .	35		
\KFLT@w . . . . .	91	<b>T</b>	
\KFLT@looseframe . . . . .	192	t (key) . . . . .	37, 41, 42
\KFLT@looseframewidth (length) . . .	196	tablehere (environment) . . . . .	12
\KFLT@tightframewidth (length) . . .	189	tables	
		large . . . . .	13
<b>L</b>		tc (key) . . . . .	37
l (key) . . . . .	35, 41	tl (key) . . . . .	37
Last . . . . .	29	tr (key) . . . . .	37
Last, First . . . . .	29, 30	troubleshooting	
		\linewidth . . . . .	21

caption format	32	nested subfloats	24
float out of sequence	18	rotating	
image too large	21	extra space	18, 27
large tables	13	frame	18
mdframed	27	rows too close or far	31
missing label	19		
mixed subfloats	24	<b>W</b>	
		<b>w</b> (key)	38