

The **l3cctab** package

Experimental category code tables

The L^AT_EX3 Project*

Released 2019-05-28

1 **l3cctab** documentation

A category code table enables rapid switching of all category codes in one operation. For LuaT_EX, this is possible over the entire Unicode range. For other engines, only the 8-bit range (0-255) is covered by such tables.

<hr/> <hr/> <code>\cctab_new:N</code>	<code>\cctab_new:N</code> \langle <i>category code table</i> \rangle Creates a new category code table, initially with the codes as used by iniT _E X.
<hr/> <hr/> <code>\cctab_const:Nn</code>	<code>\cctab_const:Nn</code> \langle <i>category code table</i> \rangle $\{$ \langle <i>category code set up</i> \rangle $\}$ Creates a new category code table and applies the \langle <i>category code set up</i> \rangle on top of prevailing settings, then saves as a constant table.
<hr/> <hr/> <code>\cctab_gset:Nn</code>	<code>\cctab_gset:Nn</code> \langle <i>category code table</i> \rangle $\{$ \langle <i>category code set up</i> \rangle $\}$ Sets the \langle <i>category code table</i> \rangle to apply the category codes which apply when the prevailing régime is modified by the \langle <i>category code set up</i> \rangle . Thus within a standard code block the starting point will be the code applied by <code>\c_code_cctab</code> . The assignment of the table is global: the underlying primitive does not respect grouping.
<hr/> <hr/> <code>\cctab_begin:N</code>	<code>\cctab_begin:N</code> \langle <i>category code table</i> \rangle Switches the category codes in force to those stored in the \langle <i>category code table</i> \rangle . The prevailing codes before the function is called are added to a stack, for use with <code>\cctab_end:</code> .
<hr/> <hr/> <code>\cctab_end:</code>	<code>\cctab_end:</code> Ends the scope of a \langle <i>category code table</i> \rangle started using <code>\cctab_begin:N</code> , retuning the codes to those in force before the matching <code>\cctab_begin:N</code> was used.
<hr/> <hr/> <code>\c_code_cctab</code>	Category code table for the code environment. This does not include setting the behaviour of the line-end character, which is only altered by <code>\ExplSyntaxOn</code> .

*E-mail: latex-team@latex-project.org

<u><u>\c_document_cctab</u></u>	Category code table for a standard L ^A T _E X document. This does not include setting the behaviour of the line-end character, which is only altered by <code>\ExplSyntaxOff</code> .
<u><u>\c_initex_cctab</u></u>	Category code table as set up by <code>iniT_EX</code> .
<u><u>\c_other_cctab</u></u>	Category code table where all characters have category code 12 (other).
<u><u>\c_str_cctab</u></u>	Category code table where all characters have category code 12 (other) with the exception of spaces, which have category code 10 (space).

Index

The italic numbers denote the pages where the corresponding entry is described, numbers underlined point to the definition, all others indicate the places where it is used.

C			
cctab commands:		<code>\c_document_cctab</code>	2
<code>\cctab_begin:N</code>	1, 1	<code>\c_initex_cctab</code>	2
<code>\cctab_const:Nn</code>	1	<code>\c_other_cctab</code>	2
<code>\cctab_end:</code>	1, 1	<code>\c_str_cctab</code>	2
<code>\cctab_gset:Nn</code>	1	E	
<code>\cctab_new:N</code>	1	<code>\ExplSyntaxOff</code>	2
<code>\c_code_cctab</code>	1, 1	<code>\ExplSyntaxOn</code>	1