## The **I3docstrip** package Code extraction and manipulation\*

The I₄T<sub>E</sub>X3 Project<sup>†</sup>

Released 2017/03/18

## 1 Extending DocStrip

The l3docstrip module adds  $LAT_E X3$  extensions to the DocStrip program for extracting code from .dtx. As such, this documentation should be read along with that for DocStrip.

## 2 Internal functions and variables

An important consideration for LATEX3 development is separating out public and internal functions. Functions and variables which are private to one module should not be used or modified by any other module. As TEX does not have any formal namespacing system, this requires a convention for indicating which functions in a code-level module are public and which are private.

Using 13docstrip allows internal functions to be indicated using a "two part" system. Within the .dtx file, internal functions may be indicated using @@ in place of the module name, for example

```
\cs_new_protected:Npn \@0_some_function:nn #1#2
  {
    % Some code here
  }
  \tl_new:N \l_@0_internal_tl
```

To extract the code using |3docstrip, the "guard" concept used by DocStrip is extended by introduction of the syntax %<@@=(module)>. The (module) name will be used when the code is extracted to replace the @@, so that

```
%<*package>
%<@@=foo>
\cs_new_protected:Npn \@@_some_function:nn #1#2
    {
        % Some code here
    }
\tl_new:N \l_@@_internal_tl
%</package>
```

<sup>\*</sup>This file describes v7019, last revised 2017/03/18.

<sup>&</sup>lt;sup>†</sup>E-mail: latex-team@latex-project.org

will be extracted as

```
\cs_new_protected:Npn \__foo_some_function:nn #1#2
    {
        % Some code here
    }
    \tl_new:N \l__foo_internal_tl
```

where the  $\_\_$  indicates that the functions and variables are internal to the foo module.

Use @@@@ to obtain @@ in the output (@@@@@ to get @@@). For longer pieces of code the replacement can be completely suppressed by giving an empty module name, namely using the syntax %<@@=>.