

The L^AT_EX3 Sources

The L^AT_EX3 Project*

Released 2017/12/05

Abstract

This is the reference documentation for the `expl3` programming environment. The `expl3` modules set up an experimental naming scheme for L^AT_EX commands, which allow the L^AT_EX programmer to systematically name functions and variables, and specify the argument types of functions.

The T_EX and ϵ -T_EX primitives are all given a new name according to these conventions. However, in the main direct use of the primitives is not required or encouraged: the `expl3` modules define an independent low-level L^AT_EX3 programming language.

At present, the `expl3` modules are designed to be loaded on top of L^AT_EX 2 ϵ . In time, a L^AT_EX3 format will be produced based on this code. This allows the code to be used in L^AT_EX 2 ϵ packages *now* while a stand-alone L^AT_EX3 is developed.

While `expl3` is still experimental, the bundle is now regarded as broadly stable. The syntax conventions and functions provided are now ready for wider use. There may still be changes to some functions, but these will be minor when compared to the scope of `expl3`.

New modules will be added to the distributed version of `expl3` as they reach maturity.

*E-mail: latex-team@latex-project.org

Contents

I	Introduction to <code>expl3</code> and this document	1
1	Naming functions and variables	1
1.1	Terminological inexactitude	3
2	Documentation conventions	3
3	Formal language conventions which apply generally	5
4	<code>TeX</code> concepts not supported by <code>LaTeX3</code>	5
II	The <code>l3bootstrap</code> package: Bootstrap code	6
1	Using the <code>LaTeX3</code> modules	6
1.1	Internal functions and variables	7
III	The <code>l3names</code> package: Namespace for primitives	8
1	Setting up the <code>LaTeX3</code> programming language	8
IV	The <code>l3basics</code> package: Basic definitions	9
1	No operation functions	9
2	Grouping material	9
3	Control sequences and functions	10
3.1	Defining functions	10
3.2	Defining new functions using parameter text	11
3.3	Defining new functions using the signature	12
3.4	Copying control sequences	15
3.5	Deleting control sequences	15
3.6	Showing control sequences	15
3.7	Converting to and from control sequences	16
4	Using or removing tokens and arguments	17
4.1	Selecting tokens from delimited arguments	19
5	Predicates and conditionals	19
5.1	Tests on control sequences	20
5.2	Primitive conditionals	21
6	Internal kernel functions	22
V	The <code>l3expan</code> package: Argument expansion	25

1	Defining new variants	25
2	Methods for defining variants	26
3	Introducing the variants	27
4	Manipulating the first argument	29
5	Manipulating two arguments	30
6	Manipulating three arguments	30
7	Unbraced expansion	31
8	Preventing expansion	32
9	Controlled expansion	33
10	Internal functions and variables	35
VI	The <code>l3tl</code> package: Token lists	37
1	Creating and initialising token list variables	37
2	Adding data to token list variables	38
3	Modifying token list variables	39
4	Reassigning token list category codes	39
5	Token list conditionals	40
6	Mapping to token lists	42
7	Using token lists	44
8	Working with the content of token lists	45
9	The first token from a token list	46
10	Using a single item	49
11	Viewing token lists	49
12	Constant token lists	49
13	Scratch token lists	50
14	Internal functions	50
VII	The <code>l3str</code> package: Strings	51

1	Building strings	51
2	Adding data to string variables	52
2.1	Modifying string variables	53
2.2	String conditionals	53
3	Mapping to strings	55
4	Working with the content of strings	57
5	String manipulation	60
6	Viewing strings	61
7	Constant token lists	62
8	Scratch strings	62
8.1	Internal string functions	62
VIII	The l3seq package: Sequences and stacks	64
1	Creating and initialising sequences	64
2	Appending data to sequences	65
3	Recovering items from sequences	65
4	Recovering values from sequences with branching	66
5	Modifying sequences	68
6	Sequence conditionals	68
7	Mapping to sequences	69
8	Using the content of sequences directly	70
9	Sequences as stacks	71
10	Sequences as sets	72
11	Constant and scratch sequences	73
12	Viewing sequences	74
13	Internal sequence functions	74
IX	The l3int package: Integers	75
1	Integer expressions	75

2	Creating and initialising integers	76
3	Setting and incrementing integers	77
4	Using integers	77
5	Integer expression conditionals	78
6	Integer expression loops	79
7	Integer step functions	81
8	Formatting integers	81
9	Converting from other formats to integers	83
10	Viewing integers	84
11	Constant integers	85
12	Scratch integers	85
13	Primitive conditionals	86
14	Internal functions	87
X	The <code>l3intarray</code> package: low-level arrays of small integers	88
1	<code>l3intarray</code> documentation	88
1.1	Internal functions	88
XI	The <code>l3flag</code> package: expandable flags	89
1	Setting up flags	89
2	Expandable flag commands	90
XII	The <code>l3quark</code> package: Quarks	91
1	Introduction to quarks and scan marks	91
1.1	Quarks	91
2	Defining quarks	91
3	Quark tests	92
4	Recursion	92
5	An example of recursion with quarks	93

6	Internal quark functions	94
7	Scan marks	94
XIII	The <code>l3prg</code> package: Control structures	96
1	Defining a set of conditional functions	96
2	The boolean data type	98
3	Boolean expressions	100
4	Logical loops	102
5	Producing multiple copies	103
6	Detecting \TeX 's mode	103
7	Primitive conditionals	103
8	Internal programming functions	104
XIV	The <code>l3clist</code> package: Comma separated lists	105
1	Creating and initialising comma lists	105
2	Adding data to comma lists	106
3	Modifying comma lists	107
4	Comma list conditionals	108
5	Mapping to comma lists	108
6	Using the content of comma lists directly	110
7	Comma lists as stacks	111
8	Using a single item	112
9	Viewing comma lists	112
10	Constant and scratch comma lists	113
XV	The <code>l3token</code> package: Token manipulation	114
1	Creating character tokens	114
2	Manipulating and interrogating character tokens	116
3	Generic tokens	119

4	Converting tokens	119
5	Token conditionals	119
6	Peeking ahead at the next token	123
7	Decomposing a macro definition	125
8	Description of all possible tokens	126
9	Internal functions	128
 XVI The <code>l3prop</code> package: Property lists		129
1	Creating and initialising property lists	129
2	Adding entries to property lists	130
3	Recovering values from property lists	130
4	Modifying property lists	131
5	Property list conditionals	131
6	Recovering values from property lists with branching	132
7	Mapping to property lists	132
8	Viewing property lists	133
9	Scratch property lists	134
10	Constants	134
11	Internal property list functions	134
 XVII The <code>l3msg</code> package: Messages		136
1	Creating new messages	136
2	Contextual information for messages	137
3	Issuing messages	138
4	Redirecting messages	140
5	Low-level message functions	141
6	Kernel-specific functions	142
7	Expandable errors	144

8	Internal l3msg functions	144
XVIII	The l3file package: File and I/O operations	145
1	File operation functions	145
1.1	Input-output stream management	146
1.2	Reading from files	148
2	Writing to files	150
2.1	Wrapping lines in output	152
2.2	Constant input-output streams	153
2.3	Primitive conditionals	153
2.4	Internal file functions and variables	153
2.5	Internal input-output functions	154
XIX	The l3skip package: Dimensions and skips	155
1	Creating and initialising dim variables	155
2	Setting dim variables	156
3	Utilities for dimension calculations	156
4	Dimension expression conditionals	157
5	Dimension expression loops	159
6	Using dim expressions and variables	160
7	Viewing dim variables	162
8	Constant dimensions	162
9	Scratch dimensions	162
10	Creating and initialising skip variables	163
11	Setting skip variables	163
12	Skip expression conditionals	164
13	Using skip expressions and variables	164
14	Viewing skip variables	164
15	Constant skips	165
16	Scratch skips	165
17	Inserting skips into the output	165

18	Creating and initialising muskip variables	166
19	Setting muskip variables	166
20	Using muskip expressions and variables	167
21	Viewing muskip variables	167
22	Constant muskips	168
23	Scratch muskips	168
24	Primitive conditional	168
25	Internal functions	169
XX	The <code>l3keys</code> package: Key–value interfaces	170
1	Creating keys	171
2	Sub-dividing keys	175
3	Choice and multiple choice keys	175
4	Setting keys	178
5	Handling of unknown keys	178
6	Selective key setting	179
7	Utility functions for keys	180
8	Low-level interface for parsing key–val lists	181
XXI	The <code>l3fp</code> package: floating points	183
1	Creating and initialising floating point variables	184
2	Setting floating point variables	184
3	Using floating point numbers	185
4	Floating point conditionals	186
5	Floating point expression loops	188
6	Some useful constants, and scratch variables	189
7	Floating point exceptions	190
8	Viewing floating points	191

9	Floating point expressions	191
9.1	Input of floating point numbers	191
9.2	Precedence of operators	192
9.3	Operations	193
10	Disclaimer and roadmap	199
XXII	The <code>l3sort</code> package: Sorting functions	202
1	Controlling sorting	202
XXIII	The <code>l3tl-build</code> package: building token lists	203
1	<code>l3tl-build</code> documentation	203
1.1	Internal functions	203
XXIV	The <code>l3tl-analysis</code> package: analysing token lists	204
1	<code>l3tl-analysis</code> documentation	204
XXV	The <code>l3regex</code> package: regular expressions in \TeX	205
1	Regular expressions	205
1.1	Syntax of regular expressions	205
1.2	Syntax of the replacement text	210
1.3	Pre-compiling regular expressions	212
1.4	Matching	212
1.5	Submatch extraction	213
1.6	Replacement	214
1.7	Bugs, misfeatures, future work, and other possibilities	214
XXVI	The <code>l3box</code> package: Boxes	218
1	Creating and initialising boxes	218
2	Using boxes	219
3	Measuring and setting box dimensions	220
4	Box conditionals	220
5	The last box inserted	221
6	Constant boxes	221
7	Scratch boxes	221

8	Viewing box contents	221
9	Boxes and color	222
10	Horizontal mode boxes	222
11	Vertical mode boxes	223
12	Affine transformations	225
13	Primitive box conditionals	227
XXVII	The <code>l3coffins</code> package: Coffin code layer	229
1	Creating and initialising coffins	229
2	Setting coffin content and poles	229
3	Joining and using coffins	230
4	Measuring coffins	231
5	Coffin diagnostics	231
5.1	Constants and variables	232
XXVIII	The <code>l3color</code> package: Color support	233
1	Color in boxes	233
1.1	Internal functions	234
XXIX	The <code>l3sys</code> package: System/runtime functions	235
1	The name of the job	235
2	Date and time	235
3	Engine	235
4	Output format	236
XXX	The <code>l3deprecation</code> package: Deprecation errors	237
1	<code>l3deprecation</code> documentation	237
XXXI	The <code>l3candidates</code> package: Experimental additions to <code>l3kernel</code>	238
1	Important notice	238

2	Additions to l3basics	239
3	Additions to l3box	240
3.1	Viewing part of a box	240
4	Additions to l3clist	240
5	Additions to l3coffins	241
6	Additions to l3file	241
7	Additions to l3int	242
8	Additions to l3msg	242
9	Additions to l3prg	243
10	Additions to l3prop	244
11	Additions to l3seq	245
12	Additions to l3skip	246
13	Additions to l3sys	246
14	Additions to l3tl	247
15	Additions to l3token	252
XXXII	The l3luatex package: LuaTeX-specific functions	253
1	Breaking out to Lua	253
1.1	TeX code interfaces	253
1.2	Lua interfaces	254
XXXIII	The l3drivers package: Drivers	255
1	Box clipping	255
2	Box rotation and scaling	255
3	Color support	256
4	Drawing	256
4.1	Path construction	257
4.2	Stroking and filling	257
4.3	Stroke options	258
4.4	Color	259
4.5	Inserting TeX material	260
4.6	Coordinate system transformations	260

XXXIV	Implementation	260
1	l3bootstrap implementation	260
1.1	Format-specific code	260
1.2	The <code>\pdfstrcmp</code> primitive in \LaTeX	261
1.3	Loading support Lua code	261
1.4	Engine requirements	262
1.5	Extending allocators	263
1.6	Character data	264
1.7	The \LaTeX 3 code environment	266
2	l3names implementation	267
3	l3basics implementation	289
3.1	Renaming some \TeX primitives (again)	289
3.2	Defining some constants	291
3.3	Defining functions	292
3.4	Selecting tokens	293
3.5	Gobbling tokens from input	294
3.6	Debugging and patching later definitions	294
3.7	Conditional processing and definitions	301
3.8	Dissecting a control sequence	307
3.9	Exist or free	309
3.10	Preliminaries for new functions	310
3.11	Defining new functions	312
3.12	Copying definitions	313
3.13	Undefining functions	314
3.14	Generating parameter text from argument count	314
3.15	Defining functions from a given number of arguments	315
3.16	Using the signature to define functions	316
3.17	Checking control sequence equality	318
3.18	Diagnostic functions	318
3.19	Doing nothing functions	320
3.20	Breaking out of mapping functions	320
4	l3expan implementation	320
4.1	General expansion	321
4.2	Hand-tuned definitions	324
4.3	Definitions with the automated technique	326
4.4	Last-unbraced versions	327
4.5	Preventing expansion	329
4.6	Controlled expansion	329
4.7	Defining function variants	330

5	l3tl implementation	337
5.1	Functions	337
5.2	Constant token lists	339
5.3	Adding to token list variables	340
5.4	Reassigning token list category codes	342
5.5	Modifying token list variables	345
5.6	Token list conditionals	348
5.7	Mapping to token lists	353
5.8	Using token lists	354
5.9	Working with the contents of token lists	355
5.10	Token by token changes	357
5.11	The first token from a token list	359
5.12	Using a single item	364
5.13	Viewing token lists	364
5.14	Scratch token lists	365
5.15	Deprecated functions	366
6	l3str implementation	366
6.1	Creating and setting string variables	366
6.2	Modifying string variables	367
6.3	String comparisons	368
6.4	Mapping to strings	372
6.5	Accessing specific characters in a string	373
6.6	Counting characters	378
6.7	The first character in a string	380
6.8	String manipulation	381
6.9	Viewing strings	383
6.10	Unicode data for case changing	383
7	l3seq implementation	386
7.1	Allocation and initialisation	387
7.2	Appending data to either end	390
7.3	Modifying sequences	391
7.4	Sequence conditionals	393
7.5	Recovering data from sequences	394
7.6	Mapping to sequences	397
7.7	Using sequences	400
7.8	Sequence stacks	400
7.9	Viewing sequences	401
7.10	Scratch sequences	402

8	l3int implementation	402
8.1	Integer expressions	403
8.2	Creating and initialising integers	405
8.3	Setting and incrementing integers	407
8.4	Using integers	408
8.5	Integer expression conditionals	408
8.6	Integer expression loops	412
8.7	Integer step functions	414
8.8	Formatting integers	415
8.9	Converting from other formats to integers	421
8.10	Viewing integer	423
8.11	Constant integers	424
8.12	Scratch integers	425
8.13	Deprecated	425
9	l3intarray implementation	426
9.1	Allocating arrays	426
9.2	Array items	427
10	l3flag implementation	428
10.1	Non-expandable flag commands	428
10.2	Expandable flag commands	429
11	l3quark implementation	430
11.1	Quarks	430
11.2	Scan marks	433
12	l3prg implementation	434
12.1	Primitive conditionals	434
12.2	Defining a set of conditional functions	434
12.3	The boolean data type	435
12.4	Boolean expressions	437
12.5	Logical loops	441
12.6	Producing multiple copies	442
12.7	Detecting T _E X's mode	443
12.8	Internal programming functions	444
13	l3clist implementation	444
13.1	Allocation and initialisation	445
13.2	Removing spaces around items	447
13.3	Adding data to comma lists	448
13.4	Comma lists as stacks	449
13.5	Modifying comma lists	451
13.6	Comma list conditionals	453
13.7	Mapping to comma lists	454
13.8	Using comma lists	457
13.9	Using a single item	458
13.10	Viewing comma lists	459
13.11	Scratch comma lists	460

14	l3token implementation	460
14.1	Manipulating and interrogating character tokens	460
14.2	Creating character tokens	463
14.3	Generic tokens	467
14.4	Token conditionals	468
14.5	Peeking ahead at the next token	475
14.6	Decomposing a macro definition	480
14.7	Deprecated functions	481
15	l3prop implementation	481
15.1	Allocation and initialisation	482
15.2	Accessing data in property lists	484
15.3	Property list conditionals	488
15.4	Recovering values from property lists with branching	489
15.5	Mapping to property lists	490
15.6	Viewing property lists	491
16	l3msg implementation	491
16.1	Creating messages	491
16.2	Messages: support functions and text	493
16.3	Showing messages: low level mechanism	493
16.4	Displaying messages	496
16.5	Kernel-specific functions	504
16.6	Expandable errors	510
17	l3file implementation	512
17.1	File operations	512
17.2	Input operations	518
17.2.1	Variables and constants	518
17.2.2	Stream management	519
17.2.3	Reading input	521
17.3	Output operations	523
17.3.1	Variables and constants	523
17.4	Stream management	525
17.4.1	Deferred writing	526
17.4.2	Immediate writing	526
17.4.3	Special characters for writing	527
17.4.4	Hard-wrapping lines to a character count	528
17.5	Messages	536
17.6	Deprecated functions	537

18	l3skip implementation	538
18.1	Length primitives renamed	538
18.2	Creating and initialising <code>dim</code> variables	539
18.3	Setting <code>dim</code> variables	540
18.4	Utilities for dimension calculations	541
18.5	Dimension expression conditionals	542
18.6	Dimension expression loops	544
18.7	Using <code>dim</code> expressions and variables	545
18.8	Viewing <code>dim</code> variables	547
18.9	Constant dimensions	547
18.10	Scratch dimensions	547
18.11	Creating and initialising <code>skip</code> variables	547
18.12	Setting <code>skip</code> variables	548
18.13	<code>Skip</code> expression conditionals	549
18.14	Using <code>skip</code> expressions and variables	550
18.15	Inserting skips into the output	551
18.16	Viewing <code>skip</code> variables	551
18.17	Constant skips	551
18.18	Scratch skips	552
18.19	Creating and initialising <code>muskip</code> variables	552
18.20	Setting <code>muskip</code> variables	553
18.21	Using <code>muskip</code> expressions and variables	554
18.22	Viewing <code>muskip</code> variables	554
18.23	Constant muskips	555
18.24	Scratch muskips	555
19	l3keys Implementation	555
19.1	Low-level interface	555
19.2	Constants and variables	559
19.3	The key defining mechanism	561
19.4	Turning properties into actions	563
19.5	Creating key properties	568
19.6	Setting keys	572
19.7	Utilities	577
19.8	Messages	579
20	l3fp implementation	580
21	l3fp-aux implementation	580
21.1	Internal representation	580
21.2	Using arguments and semicolons	582
21.3	Constants, and structure of floating points	582
21.4	Overflow, underflow, and exact zero	584
21.5	Expanding after a floating point number	585
21.6	Packing digits	586
21.7	Decimate (dividing by a power of 10)	589
21.8	Functions for use within primitive conditional branches	591
21.9	Integer floating points	592
21.10	Small integer floating points	593
21.11	Length of a floating point array	593

	21.12x-like expansion expandably	594
	21.13Messages	594
22	l3fp-traps Implementation	595
	22.1 Flags	595
	22.2 Traps	595
	22.3 Errors	599
	22.4 Messages	599
23	l3fp-round implementation	600
	23.1 Rounding tools	601
	23.2 The round function	605
24	l3fp-parse implementation	608
	24.1 Work plan	608
	24.1.1 Storing results	609
	24.1.2 Precedence and infix operators	610
	24.1.3 Prefix operators, parentheses, and functions	613
	24.1.4 Numbers and reading tokens one by one	614
	24.2 Main auxiliary functions	616
	24.3 Helpers	616
	24.4 Parsing one number	618
	24.4.1 Numbers: trimming leading zeros	623
	24.4.2 Number: small significand	625
	24.4.3 Number: large significand	626
	24.4.4 Number: beyond 16 digits, rounding	628
	24.4.5 Number: finding the exponent	631
	24.5 Constants, functions and prefix operators	634
	24.5.1 Prefix operators	634
	24.5.2 Constants	636
	24.5.3 Functions	638
	24.6 Main functions	638
	24.7 Infix operators	639
	24.7.1 Closing parentheses and commas	640
	24.7.2 Usual infix operators	642
	24.7.3 Juxtaposition	643
	24.7.4 Multi-character cases	643
	24.7.5 Ternary operator	644
	24.7.6 Comparisons	645
	24.8 Candidate: defining new l3fp functions	647
	24.9 Messages	648
25	l3fp-logic Implementation	649
	25.1 Syntax of internal functions	649
	25.2 Existence test	650
	25.3 Comparison	650
	25.4 Floating point expression loops	652
	25.5 Extrema	655
	25.6 Boolean operations	656
	25.7 Ternary operator	657

26	l3fp-basics Implementation	658
26.1	Addition and subtraction	659
26.1.1	Sign, exponent, and special numbers	659
26.1.2	Absolute addition	661
26.1.3	Absolute subtraction	663
26.2	Multiplication	668
26.2.1	Signs, and special numbers	668
26.2.2	Absolute multiplication	669
26.3	Division	671
26.3.1	Signs, and special numbers	671
26.3.2	Work plan	672
26.3.3	Implementing the significand division	675
26.4	Square root	680
26.5	About the sign	687
27	l3fp-extended implementation	688
27.1	Description of fixed point numbers	688
27.2	Helpers for numbers with extended precision	688
27.3	Multiplying a fixed point number by a short one	689
27.4	Dividing a fixed point number by a small integer	690
27.5	Adding and subtracting fixed points	691
27.6	Multiplying fixed points	692
27.7	Combining product and sum of fixed points	693
27.8	Extended-precision floating point numbers	695
27.9	Dividing extended-precision numbers	698
27.10	Inverse square root of extended precision numbers	701
27.11	Converting from fixed point to floating point	703
28	l3fp-expo implementation	705
28.1	Logarithm	705
28.1.1	Work plan	705
28.1.2	Some constants	706
28.1.3	Sign, exponent, and special numbers	706
28.1.4	Absolute ln	706
28.2	Exponential	714
28.2.1	Sign, exponent, and special numbers	714
28.3	Power	718
29	l3fp-trig Implementation	724
29.1	Direct trigonometric functions	725
29.1.1	Filtering special cases	725
29.1.2	Distinguishing small and large arguments	728
29.1.3	Small arguments	729
29.1.4	Argument reduction in degrees	729
29.1.5	Argument reduction in radians	730
29.1.6	Computing the power series	736
29.2	Inverse trigonometric functions	739
29.2.1	Arctangent and arccotangent	740
29.2.2	Arcsine and arccosine	745
29.2.3	Arccosecant and arcsecant	747

30	l3fp-convert implementation	748
30.1	Trimming trailing zeros	748
30.2	Scientific notation	749
30.3	Decimal representation	750
30.4	Token list representation	751
30.5	Formatting	752
30.6	Convert to dimension or integer	752
30.7	Convert from a dimension	753
30.8	Use and eval	754
30.9	Convert an array of floating points to a comma list	754
31	l3fp-random Implementation	755
31.1	Engine support	755
31.2	Random floating point	757
31.3	Random integer	757
32	l3fp-assign implementation	759
32.1	Assigning values	760
32.2	Updating values	761
32.3	Showing values	761
32.4	Some useful constants and scratch variables	761
33	l3sort implementation	762
33.1	Variables	762
33.2	Finding available \toks registers	763
33.3	Protected user commands	765
33.4	Merge sort	767
33.5	Expandable sorting	770
33.6	Messages	775
33.7	Deprecated functions	777
34	l3tl-build implementation	777
34.1	Variables and helper functions	777
34.2	Building the token list	778
35	l3tl-analysis implementation	779
35.1	Internal functions	779
35.2	Internal format	779
35.3	Variables and helper functions	780
35.4	Plan of attack	782
35.5	Disabling active characters	783
35.6	First pass	784
35.7	Second pass	789
35.8	Mapping through the analysis	791
35.9	Showing the results	792
35.10	Messages	794

36	l3regex implementation	795
36.1	Plan of attack	795
36.2	Helpers	796
36.2.1	Constants and variables	797
36.2.2	Testing characters	799
36.2.3	Character property tests	802
36.2.4	Simple character escape	804
36.3	Compiling	809
36.3.1	Variables used when compiling	810
36.3.2	Generic helpers used when compiling	811
36.3.3	Mode	812
36.3.4	Framework	815
36.3.5	Quantifiers	817
36.3.6	Raw characters	820
36.3.7	Character properties	821
36.3.8	Anchoring and simple assertions	822
36.3.9	Character classes	823
36.3.10	Groups and alternations	826
36.3.11	Catcodes and csnames	829
36.3.12	Raw token lists with \u	832
36.3.13	Other	834
36.3.14	Showing regexes	835
36.4	Building	838
36.4.1	Variables used while building	838
36.4.2	Framework	839
36.4.3	Helpers for building an NFA	841
36.4.4	Building classes	842
36.4.5	Building groups	844
36.4.6	Others	848
36.5	Matching	850
36.5.1	Variables used when matching	850
36.5.2	Matching: framework	852
36.5.3	Using states of the NFA	856
36.5.4	Actions when matching	856
36.6	Replacement	859
36.6.1	Variables and helpers used in replacement	859
36.6.2	Query and brace balance	860
36.6.3	Framework	861
36.6.4	Submatches	863
36.6.5	Csnames in replacement	864
36.6.6	Characters in replacement	865
36.6.7	An error	869
36.7	User functions	869
36.7.1	Variables and helpers for user functions	871
36.7.2	Matching	872
36.7.3	Extracting submatches	872
36.7.4	Replacement	876
36.7.5	Storing and showing compiled patterns	878
36.8	Messages	878
36.9	Code for tracing	884

37	l3box implementation	885
37.1	Creating and initialising boxes	885
37.2	Measuring and setting box dimensions	886
37.3	Using boxes	886
37.4	Box conditionals	887
37.5	The last box inserted	887
37.6	Constant boxes	887
37.7	Scratch boxes	888
37.8	Viewing box contents	888
37.9	Horizontal mode boxes	889
37.10	Vertical mode boxes	891
37.11	Affine transformations	894
37.12	Deprecated functions	902
38	l3coffins Implementation	902
38.1	Coffins: data structures and general variables	902
38.2	Basic coffin functions	904
38.3	Measuring coffins	908
38.4	Coffins: handle and pole management	908
38.5	Coffins: calculation of pole intersections	911
38.6	Aligning and typesetting of coffins	914
38.7	Coffin diagnostics	918
38.8	Messages	923
39	l3color Implementation	924
40	l3sys implementation	925
40.1	The name of the job	925
40.2	Time and date	925
40.3	Detecting the engine	925
40.4	Detecting the output	926
41	l3deprecation implementation	927
42	l3candidates Implementation	928
42.1	Additions to l3basics	928
42.2	Additions to l3box	929
42.3	Viewing part of a box	929
42.4	Additions to l3clist	931
42.5	Additions to l3coffins	932
42.6	Rotating coffins	932
42.7	Resizing coffins	936
42.8	Additions to l3file	938
42.9	Additions to l3int	941
42.10	Additions to l3msg	942
42.11	Additions to l3prg	943
42.12	Additions to l3prop	944
42.13	Additions to l3seq	945
42.14	Additions to l3skip	947
42.15	Additions to l3sys	947

42.16	Additions to l3tl	950
42.16.1	Unicode case changing	952
42.16.2	Other additions to l3tl	973
42.17	Additions to l3token	976
43	l3luatex implementation	978
43.1	Breaking out to Lua	978
43.2	Messages	979
43.3	Lua functions for internal use	979
43.4	Generic Lua and font support	982
44	l3drivers Implementation	982
44.1	Color support	983
44.1.1	dvips-style	983
44.1.2	pdfmode	984
44.2	dvips driver	986
44.2.1	Basics	986
44.3	Driver-specific auxiliaries	987
44.3.1	Box operations	987
44.4	Images	988
44.5	Drawing	988
44.6	pdfmode driver	995
44.6.1	Basics	995
44.6.2	Box operations	996
44.7	Images	997
44.8	dvipdfmx driver	999
44.8.1	Basics	999
44.8.2	Box operations	1000
44.9	Images	1001
44.10	xdvipdfmx driver	1003
44.11	Images	1003
44.12	Drawing commands: pdfmode and (x)dvipdfmx	1004
44.13	Drawing	1005
44.14	dvisvgm driver	1009
44.14.1	Basics	1009
44.15	Driver-specific auxiliaries	1010
44.15.1	Box operations	1010
44.16	Images	1012
44.17	Drawing	1012
	Index	1020

Part I

Introduction to expl3 and this document

This document is intended to act as a comprehensive reference manual for the expl3 language. A general guide to the L^AT_EX3 programming language is found in [expl3.pdf](#).

1 Naming functions and variables

L^AT_EX3 does not use `@` as a “letter” for defining internal macros. Instead, the symbols `_` and `:` are used in internal macro names to provide structure. The name of each *function* is divided into logical units using `_`, while `:` separates the *name* of the function from the *argument specifier* (“arg-spec”). This describes the arguments expected by the function. In most cases, each argument is represented by a single letter. The complete list of arg-spec letters for a function is referred to as the *signature* of the function.

Each function name starts with the *module* to which it belongs. Thus apart from a small number of very basic functions, all expl3 function names contain at least one underscore to divide the module name from the descriptive name of the function. For example, all functions concerned with comma lists are in module `clist` and begin `\clist_`.

Every function must include an argument specifier. For functions which take no arguments, this will be blank and the function name will end `:`. Most functions take one or more arguments, and use the following argument specifiers:

- D** The **D** specifier means *do not use*. All of the T_EX primitives are initially `\let` to a **D** name, and some are then given a second name. Only the kernel team should use anything with a **D** specifier!
- N and n** These mean *no manipulation*, of a single token for **N** and of a set of tokens given in braces for **n**. Both pass the argument through exactly as given. Usually, if you use a single token for an **n** argument, all will be well.
- c** This means *cname*, and indicates that the argument will be turned into a *cname* before being used. So `\foo:c {ArgumentOne}` will act in the same way as `\foo:N \ArgumentOne`.
- V and v** These mean *value of variable*. The **V** and **v** specifiers are used to get the content of a variable without needing to worry about the underlying T_EX structure containing the data. A **V** argument will be a single token (similar to **N**), for example `\foo:V \MyVariable`; on the other hand, using **v** a *cname* is constructed first, and then the value is recovered, for example `\foo:v {MyVariable}`.
- o** This means *expansion once*. In general, the **V** and **v** specifiers are favoured over **o** for recovering stored information. However, **o** is useful for correctly processing information with delimited arguments.
- x** The **x** specifier stands for *exhaustive expansion*: every token in the argument is fully expanded until only unexpandable ones remain. The T_EX `\edef` primitive carries out this type of expansion. Functions which feature an **x**-type argument are in general *not* expandable, unless specifically noted.

- f** The **f** specifier stands for *full expansion*, and in contrast to **x** stops at the first non-expandable item (reading the argument from left to right) without trying to expand it. For example, when setting a token list variable (a macro used for storage), the sequence

```
\tl_set:Nn \l_my_a_tl { A }
\tl_set:Nn \l_my_b_tl { B }
\tl_set:Nf \l_my_a_tl { \l_my_a_tl \l_my_b_tl }
```

will leave `\l_my_a_tl` with the content `A\l_my_b_tl`, as `A` cannot be expanded and so terminates expansion before `\l_my_b_tl` is considered.

- T and F** For logic tests, there are the branch specifiers **T** (*true*) and **F** (*false*). Both specifiers treat the input in the same way as **n** (no change), but make the logic much easier to see.
- p** The letter **p** indicates `TeX parameters`. Normally this will be used for delimited functions as `expl3` provides better methods for creating simple sequential arguments.
- w** Finally, there is the **w** specifier for *weird* arguments. This covers everything else, but mainly applies to delimited values (where the argument must be terminated by some arbitrary string).

Notice that the argument specifier describes how the argument is processed prior to being passed to the underlying function. For example, `\foo:c` will take its argument, convert it to a control sequence and pass it to `\foo:N`.

Variables are named in a similar manner to functions, but begin with a single letter to define the type of variable:

- c** Constant: global parameters whose value should not be changed.
- g** Parameters whose value should only be set globally.
- l** Parameters whose value should only be set locally.

Each variable name is then build up in a similar way to that of a function, typically starting with the module¹ name and then a descriptive part. Variables end with a short identifier to show the variable type:

bool Either true or false.

box Box register.

clist Comma separated list.

coffin a “box with handles” — a higher-level data type for carrying out **box** alignment operations.

dim “Rigid” lengths.

fp floating-point values;

¹The module names are not used in case of generic scratch registers defined in the data type modules, e.g., the `int` module contains some scratch variables called `\l_tmpa_int`, `\l_tmpb_int`, and so on. In such a case adding the module name up front to denote the module and in the back to indicate the type, as in `\l_int_tmpa_int` would be very unreadable.

int Integer-valued count register.

prop Property list.

seq “Sequence”: a data-type used to implement lists (with access at both ends) and stacks.

skip “Rubber” lengths.

stream An input or output stream (for reading from or writing to, respectively).

tl Token list variables: placeholder for a token list.

1.1 Terminological inexactitude

A word of warning. In this document, and others referring to the `expl3` programming modules, we often refer to “variables” and “functions” as if they were actual constructs from a real programming language. In truth, `TeX` is a macro processor, and functions are simply macros that may or may not take arguments and expand to their replacement text. Many of the common variables are *also* macros, and if placed into the input stream will simply expand to their definition as well — a “function” with no arguments and a “token list variable” are in truth one and the same. On the other hand, some “variables” are actually registers that must be initialised and their values set and retrieved with specific functions.

The conventions of the `expl3` code are designed to clearly separate the ideas of “macros that contain data” and “macros that contain code”, and a consistent wrapper is applied to all forms of “data” whether they be macros or actually registers. This means that sometimes we will use phrases like “the function returns a value”, when actually we just mean “the macro expands to something”. Similarly, the term “execute” might be used in place of “expand” or it might refer to the more specific case of “processing in `TeX`’s stomach” (if you are familiar with the `TeXbook` parlance).

If in doubt, please ask; chances are we’ve been hasty in writing certain definitions and need to be told to tighten up our terminology.

2 Documentation conventions

This document is typeset with the experimental `l3doc` class; several conventions are used to help describe the features of the code. A number of conventions are used here to make the documentation clearer.

Each group of related functions is given in a box. For a function with a “user” name, this might read:

```
\ExplSyntaxOn
\ExplSyntaxOff
```

```
\ExplSyntaxOn ... \ExplSyntaxOff
```

The textual description of how the function works would appear here. The syntax of the function is shown in mono-spaced text to the right of the box. In this example, the function takes no arguments and so the name of the function is simply reprinted.

For programming functions, which use `_` and `:` in their name there are a few additional conventions: If two related functions are given with identical names but different argument specifiers, these are termed *variants* of each other, and the latter functions are printed in grey to show this more clearly. They will carry out the same function but will take different types of argument:

<code>\seq_new:N</code>	<code>\seq_new:N</code> $\langle sequence \rangle$
<code>\seq_new:c</code>	

When a number of variants are described, the arguments are usually illustrated only for the base function. Here, $\langle sequence \rangle$ indicates that `\seq_new:N` expects the name of a sequence. From the argument specifier, `\seq_new:c` also expects a sequence name, but as a name rather than as a control sequence. Each argument given in the illustration should be described in the following text.

Fully expandable functions Some functions are fully expandable, which allows them to be used within an **x**-type argument (in plain \TeX terms, inside an `\edef`), as well as within an **f**-type argument. These fully expandable functions are indicated in the documentation by a star:

<code>\cs_to_str:N</code> ★	<code>\cs_to_str:N</code> $\langle cs \rangle$
-----------------------------	--

As with other functions, some text should follow which explains how the function works. Usually, only the star will indicate that the function is expandable. In this case, the function expects a $\langle cs \rangle$, shorthand for a $\langle control\ sequence \rangle$.

Restricted expandable functions A few functions are fully expandable but cannot be fully expanded within an **f**-type argument. In this case a hollow star is used to indicate this:

<code>\seq_map_function:NN</code> ☆	<code>\seq_map_function:NN</code> $\langle seq \rangle$ $\langle function \rangle$
-------------------------------------	--

Conditional functions Conditional (**if**) functions are normally defined in three variants, with **T**, **F** and **TF** argument specifiers. This allows them to be used for different “true”/“false” branches, depending on which outcome the conditional is being used to test. To indicate this without repetition, this information is given in a shortened form:

<code>\sys_if_engine_xetex:TF</code> ★	<code>\sys_if_engine_xetex:TF</code> $\{\langle true\ code \rangle\}$ $\{\langle false\ code \rangle\}$
--	---

The underlining and italic of **TF** indicates that `\sys_if_engine_xetex:T`, `\sys_if_engine_xetex:F` and `\sys_if_engine_xetex:TF` are all available. Usually, the illustration will use the **TF** variant, and so both $\langle true\ code \rangle$ and $\langle false\ code \rangle$ will be shown. The two variant forms **T** and **F** take only $\langle true\ code \rangle$ and $\langle false\ code \rangle$, respectively. Here, the star also shows that this function is expandable. With some minor exceptions, *all* conditional functions in the `expl3` modules should be defined in this way.

Variables, constants and so on are described in a similar manner:

<code>\l_tmpa_tl</code>	
-------------------------	--

A short piece of text will describe the variable: there is no syntax illustration in this case.

In some cases, the function is similar to one in $\text{\LaTeX 2}_{\epsilon}$ or plain \TeX . In these cases, the text will include an extra “ **\TeX hackers note**” section:

<code>\token_to_str:N</code> ★	<code>\token_to_str:N</code> $\langle token \rangle$
--------------------------------	--

The normal description text.

\TeX hackers note: Detail for the experienced \TeX or $\text{\LaTeX 2}_{\epsilon}$ programmer. In this case, it would point out that this function is the \TeX primitive `\string`.

Changes to behaviour When new functions are added to `expl3`, the date of first inclusion is given in the documentation. Where the documented behaviour of a function changes after it is first introduced, the date of the update will also be given. This means that the programmer can be sure that any release of `expl3` after the date given will contain the function of interest with expected behaviour as described. Note that changes to code internals, including bug fixes, are not recorded in this way *unless* they impact on the expected behaviour.

3 Formal language conventions which apply generally

As this is a formal reference guide for $\text{\LaTeX}3$ programming, the descriptions of functions are intended to be reasonably “complete”. However, there is also a need to avoid repetition. Formal ideas which apply to general classes of function are therefore summarised here.

For tests which have a `TF` argument specification, the test is evaluated to give a logically `TRUE` or `FALSE` result. Depending on this result, either the $\langle true\ code \rangle$ or the $\langle false\ code \rangle$ will be left in the input stream. In the case where the test is expandable, and a predicate (`_p`) variant is available, the logical value determined by the test is left in the input stream: this will typically be part of a larger logical construct.

4 \TeX concepts not supported by $\text{\LaTeX}3$

The \TeX concept of an “`\outer`” macro is *not supported* at all by $\text{\LaTeX}3$. As such, the functions provided here may break when used on top of $\text{\LaTeX}2_\epsilon$ if `\outer` tokens are used in the arguments.

Part II

The l3bootstrap package

Bootstrap code

1 Using the L^AT_EX3 modules

The modules documented in `source3` are designed to be used on top of L^AT_EX 2_ε and are loaded all as one with the usual `\usepackage{expl3}` or `\RequirePackage{expl3}` instructions. These modules will also form the basis of the L^AT_EX3 format, but work in this area is incomplete and not included in this documentation at present.

As the modules use a coding syntax different from standard L^AT_EX 2_ε it provides a few functions for setting it up.

`\ExplSyntaxOn`
`\ExplSyntaxOff`
 Updated: 2011-08-13

`\ExplSyntaxOn` *<code>* `\ExplSyntaxOff`

The `\ExplSyntaxOn` function switches to a category code régime in which spaces are ignored and in which the colon (:) and underscore (_) are treated as “letters”, thus allowing access to the names of code functions and variables. Within this environment, ~ is used to input a space. The `\ExplSyntaxOff` reverts to the document category code régime.

`\ProvidesExplPackage`
`\ProvidesExplClass`
`\ProvidesExplFile`
 Updated: 2017-03-19

`\RequirePackage{expl3}`
`\ProvidesExplPackage` *<package>* *<date>* *<version>* *<description>*

These functions act broadly in the same way as the corresponding L^AT_EX 2_ε kernel functions `\ProvidesPackage`, `\ProvidesClass` and `\ProvidesFile`. However, they also implicitly switch `\ExplSyntaxOn` for the remainder of the code with the file. At the end of the file, `\ExplSyntaxOff` will be called to reverse this. (This is the same concept as L^AT_EX 2_ε provides in turning on `\makeatletter` within package and class code.) The *<date>* should be given in the format *<year>/<month>/<day>*. If the *<version>* is given then it will be prefixed with v in the package identifier line.

`\GetIdInfo`
 Updated: 2012-06-04

`\RequirePackage{l3bootstrap}`
`\GetIdInfo` *\$Id: <SVN info field> \$* *<description>*

Extracts all information from a SVN field. Spaces are not ignored in these fields. The information pieces are stored in separate control sequences with `\ExplFileName` for the part of the file name leading up to the period, `\ExplFileDate` for date, `\ExplFileVersion` for version and `\ExplFileDescription` for the description.

To summarize: Every single package using this syntax should identify itself using one of the above methods. Special care is taken so that every package or class file loaded with `\RequirePackage` or similar are loaded with usual L^AT_EX 2_ε category codes and the L^AT_EX3 category code scheme is reloaded when needed afterwards. See implementation for details. If you use the `\GetIdInfo` command you can use the information when loading a package with

```
\ProvidesExplPackage{\ExplFileName}
  {\ExplFileDate}{\ExplFileVersion}{\ExplFileDescription}
```

1.1 Internal functions and variables

`\l_kernel_expl_bool`

A boolean which records the current code syntax status: `true` if currently inside a code environment. This variable should only be set by `\ExplSyntaxOn/\ExplSyntaxOff`.

Part III

The l3names package

Namespace for primitives

1 Setting up the L^AT_EX3 programming language

This module is at the core of the L^AT_EX3 programming language. It performs the following tasks:

- defines new names for all T_EX primitives;
- switches to the category code régime for programming;
- provides support settings for building the code as a T_EX format.

This module is entirely dedicated to primitives, which should not be used directly within L^AT_EX3 code (outside of “kernel-level” code). As such, the primitives are not documented here: *The T_EXbook*, *T_EX by Topic* and the manuals for pdfT_EX, X_YT_EX and LuaT_EX should be consulted for details of the primitives. These are named based on the engine which first introduced them:

`\tex_...` Introduced by T_EX itself;
`\etex_...` Introduced by the ϵ -T_EX extensions;
`\pdftex_...` Introduced by pdfT_EX;
`\xetex_...` Introduced by X_YT_EX;
`\luatex_...` Introduced by LuaT_EX;
`\utex_...` Introduced by X_YT_EX and LuaT_EX;
`\ptex_...` Introduced by pT_EX;
`\uptex_...` Introduced by upT_EX.

Part IV

The l3basics package

Basic definitions

As the name suggest this package holds some basic definitions which are needed by most or all other packages in this set.

Here we describe those functions that are used all over the place. With that we mean functions dealing with the construction and testing of control sequences. Furthermore the basic parts of conditional processing are covered; conditional processing dealing with specific data types is described in the modules specific for the respective data types.

1 No operation functions

`\prg_do_nothing:` ★**`\prg_do_nothing:`**

An expandable function which does nothing at all: leaves nothing in the input stream after a single expansion.

`\scan_stop:`**`\scan_stop:`**

A non-expandable function which does nothing. Does not vanish on expansion but produces no typeset output.

2 Grouping material

`\group_begin:`
`\group_end:`**`\group_begin:`**
`\group_end:`

These functions begin and end a group for definition purposes. Assignments are local to groups unless carried out in a global manner. (A small number of exceptions to this rule will be noted as necessary elsewhere in this document.) Each **`\group_begin:`** must be matched by a **`\group_end:`**, although this does not have to occur within the same function. Indeed, it is often necessary to start a group within one function and finish it within another, for example when seeking to use non-standard category codes.

`\group_insert_after:N`**`\group_insert_after:N`** *<token>*

Adds *<token>* to the list of *<tokens>* to be inserted when the current group level ends. The list of *<tokens>* to be inserted is empty at the beginning of a group: multiple applications of **`\group_insert_after:N`** may be used to build the inserted list one *<token>* at a time. The current group level may be closed by a **`\group_end:`** function or by a token with category code 2 (close-group), namely a `}` if standard category codes apply.

3 Control sequences and functions

As \TeX is a macro language, creating new functions means creating macros. At point of use, a function is replaced by the replacement text (“code”) in which each parameter in the code ($\#1$, $\#2$, *etc.*) is replaced the appropriate arguments absorbed by the function. In the following, *code* is therefore used as a shorthand for “replacement text”.

Functions which are not “protected” are fully expanded inside an \mathbf{x} expansion. In contrast, “protected” functions are not expanded within \mathbf{x} expansions.

3.1 Defining functions

Functions can be created with no requirement that they are declared first (in contrast to variables, which must always be declared). Declaring a function before setting up the code means that the name chosen is checked and an error raised if it is already in use. The name of a function can be checked at the point of definition using the `\cs_new...` functions: this is recommended for all functions which are defined for the first time.

There are three ways to define new functions. All classes define a function to expand to the substitution text. Within the substitution text the actual parameters are substituted for the formal parameters ($\#1$, $\#2$, ...).

new Create a new function with the **new** scope, such as `\cs_new:Npn`. The definition is global and results in an error if it is already defined.

set Create a new function with the **set** scope, such as `\cs_set:Npn`. The definition is restricted to the current \TeX group and does not result in an error if the function is already defined.

gset Create a new function with the **gset** scope, such as `\cs_gset:Npn`. The definition is global and does not result in an error if the function is already defined.

Within each set of scope there are different ways to define a function. The differences depend on restrictions on the actual parameters and the expandability of the resulting function.

nopar Create a new function with the **nopar** restriction, such as `\cs_set_nopar:Npn`. The parameter may not contain `\par` tokens.

protected Create a new function with the **protected** restriction, such as `\cs_set_protected:Npn`. The parameter may contain `\par` tokens but the function will not expand within an \mathbf{x} -type expansion.

Finally, the functions in Subsections 3.2 and 3.3 are primarily meant to define *base functions* only. Base functions can only have the following argument specifiers:

N and n No manipulation.

T and F Functionally equivalent to **n** (you are actually encouraged to use the family of `\prg_new_conditional:` functions described in Section 1).

p and w These are special cases.

The `\cs_new:` functions below (and friends) do not stop you from using other argument specifiers in your function names, but they do not handle expansion for you. You should define the base function and then use `\cs_generate_variant:Nn` to generate custom variants as described in Section 2.

3.2 Defining new functions using parameter text

<code>\cs_new:Npn</code>	<code>\cs_new:Npn <function> <parameters> {<code>}</code>
<code>\cs_new:cpn</code>	Creates <code><function></code> to expand to <code><code></code> as replacement text. Within the <code><code></code> , the
<code>\cs_new:Npx</code>	<code><parameters></code> (<code>#1</code> , <code>#2</code> , <i>etc.</i>) will be replaced by those absorbed by the function. The
<code>\cs_new:cpx</code>	definition is global and an error results if the <code><function></code> is already defined.

<code>\cs_new_nopar:Npn</code>	<code>\cs_new_nopar:Npn <function> <parameters> {<code>}</code>
<code>\cs_new_nopar:cpn</code>	Creates <code><function></code> to expand to <code><code></code> as replacement text. Within the <code><code></code> , the
<code>\cs_new_nopar:Npx</code>	<code><parameters></code> (<code>#1</code> , <code>#2</code> , <i>etc.</i>) will be replaced by those absorbed by the function. When the
<code>\cs_new_nopar:cpx</code>	<code><function></code> is used the <code><parameters></code> absorbed cannot contain <code>\par</code> tokens. The definition

is global and an error results if the `<function>` is already defined.

<code>\cs_new_protected:Npn</code>	<code>\cs_new_protected:Npn <function> <parameters> {<code>}</code>
<code>\cs_new_protected:cpn</code>	Creates <code><function></code> to expand to <code><code></code> as replacement text. Within the <code><code></code> , the
<code>\cs_new_protected:Npx</code>	<code><parameters></code> (<code>#1</code> , <code>#2</code> , <i>etc.</i>) will be replaced by those absorbed by the function. The
<code>\cs_new_protected:cpx</code>	<code><function></code> will not expand within an x-type argument. The definition is global and an

error results if the `<function>` is already defined.

<code>\cs_new_protected_nopar:Npn</code>	<code>\cs_new_protected_nopar:Npn <function> <parameters> {<code>}</code>
<code>\cs_new_protected_nopar:cpn</code>	
<code>\cs_new_protected_nopar:Npx</code>	
<code>\cs_new_protected_nopar:cpx</code>	

Creates `<function>` to expand to `<code>` as replacement text. Within the `<code>`, the `<parameters>` (`#1`, `#2`, *etc.*) will be replaced by those absorbed by the function. When the `<function>` is used the `<parameters>` absorbed cannot contain `\par` tokens. The `<function>` will not expand within an x-type argument. The definition is global and an error results if the `<function>` is already defined.

<code>\cs_set:Npn</code>	<code>\cs_set:Npn <function> <parameters> {<code>}</code>
<code>\cs_set:cpn</code>	Sets <code><function></code> to expand to <code><code></code> as replacement text. Within the <code><code></code> , the
<code>\cs_set:Npx</code>	<code><parameters></code> (<code>#1</code> , <code>#2</code> , <i>etc.</i>) will be replaced by those absorbed by the function. The
<code>\cs_set:cpx</code>	assignment of a meaning to the <code><function></code> is restricted to the current \TeX group level.

<code>\cs_set_nopar:Npn</code>	<code>\cs_set_nopar:Npn <function> <parameters> {<code>}</code>
<code>\cs_set_nopar:cpn</code>	Sets <code><function></code> to expand to <code><code></code> as replacement text. Within the <code><code></code> , the
<code>\cs_set_nopar:Npx</code>	<code><parameters></code> (<code>#1</code> , <code>#2</code> , <i>etc.</i>) will be replaced by those absorbed by the function. When the
<code>\cs_set_nopar:cpx</code>	<code><function></code> is used the <code><parameters></code> absorbed cannot contain <code>\par</code> tokens. The assignment

of a meaning to the `<function>` is restricted to the current \TeX group level.

<code>\cs_set_protected:Npn</code>	<code>\cs_set_protected:Npn <function> <parameters> {<code>}</code>
<code>\cs_set_protected:cpn</code>	Sets <code><function></code> to expand to <code><code></code> as replacement text. Within the <code><code></code> , the
<code>\cs_set_protected:Npx</code>	<code><parameters></code> (<code>#1</code> , <code>#2</code> , <i>etc.</i>) will be replaced by those absorbed by the function. The
<code>\cs_set_protected:cpx</code>	assignment of a meaning to the <code><function></code> is restricted to the current \TeX group level.

The `<function>` will not expand within an x-type argument.

<code>\cs_set_protected_nopar:Npn</code>	<code>\cs_set_protected_nopar:Npn <function> <parameters> {<code>}</code>
<code>\cs_set_protected_nopar:cpn</code>	
<code>\cs_set_protected_nopar:Npx</code>	
<code>\cs_set_protected_nopar:cpx</code>	

Sets $\langle function \rangle$ to expand to $\langle code \rangle$ as replacement text. Within the $\langle code \rangle$, the $\langle parameters \rangle$ ($\#1$, $\#2$, *etc.*) will be replaced by those absorbed by the function. When the $\langle function \rangle$ is used the $\langle parameters \rangle$ absorbed cannot contain `\par` tokens. The assignment of a meaning to the $\langle function \rangle$ is restricted to the current T_EX group level. The $\langle function \rangle$ will not expand within an x-type argument.

<code>\cs_gset:Npn</code>	<code>\cs_gset:Npn <function> <parameters> {<code>}</code>
<code>\cs_gset:cpn</code>	
<code>\cs_gset:Npx</code>	
<code>\cs_gset:cpx</code>	

Globally sets $\langle function \rangle$ to expand to $\langle code \rangle$ as replacement text. Within the $\langle code \rangle$, the $\langle parameters \rangle$ ($\#1$, $\#2$, *etc.*) will be replaced by those absorbed by the function. The assignment of a meaning to the $\langle function \rangle$ is *not* restricted to the current T_EX group level: the assignment is global.

<code>\cs_gset_nopar:Npn</code>	<code>\cs_gset_nopar:Npn <function> <parameters> {<code>}</code>
<code>\cs_gset_nopar:cpn</code>	
<code>\cs_gset_nopar:Npx</code>	
<code>\cs_gset_nopar:cpx</code>	

Globally sets $\langle function \rangle$ to expand to $\langle code \rangle$ as replacement text. Within the $\langle code \rangle$, the $\langle parameters \rangle$ ($\#1$, $\#2$, *etc.*) will be replaced by those absorbed by the function. When the $\langle function \rangle$ is used the $\langle parameters \rangle$ absorbed cannot contain `\par` tokens. The assignment of a meaning to the $\langle function \rangle$ is *not* restricted to the current T_EX group level: the assignment is global.

<code>\cs_gset_protected:Npn</code>	<code>\cs_gset_protected:Npn <function> <parameters> {<code>}</code>
<code>\cs_gset_protected:cpn</code>	
<code>\cs_gset_protected:Npx</code>	
<code>\cs_gset_protected:cpx</code>	

Globally sets $\langle function \rangle$ to expand to $\langle code \rangle$ as replacement text. Within the $\langle code \rangle$, the $\langle parameters \rangle$ ($\#1$, $\#2$, *etc.*) will be replaced by those absorbed by the function. The assignment of a meaning to the $\langle function \rangle$ is *not* restricted to the current T_EX group level: the assignment is global. The $\langle function \rangle$ will not expand within an x-type argument.

<code>\cs_gset_protected_nopar:Npn</code>	<code>\cs_gset_protected_nopar:Npn <function> <parameters> {<code>}</code>
<code>\cs_gset_protected_nopar:cpn</code>	
<code>\cs_gset_protected_nopar:Npx</code>	
<code>\cs_gset_protected_nopar:cpx</code>	

Globally sets $\langle function \rangle$ to expand to $\langle code \rangle$ as replacement text. Within the $\langle code \rangle$, the $\langle parameters \rangle$ ($\#1$, $\#2$, *etc.*) will be replaced by those absorbed by the function. When the $\langle function \rangle$ is used the $\langle parameters \rangle$ absorbed cannot contain `\par` tokens. The assignment of a meaning to the $\langle function \rangle$ is *not* restricted to the current T_EX group level: the assignment is global. The $\langle function \rangle$ will not expand within an x-type argument.

3.3 Defining new functions using the signature

<code>\cs_new:Nn</code>	<code>\cs_new:Nn <function> {<code>}</code>
<code>\cs_new:(cn Nx cx)</code>	

Creates $\langle function \rangle$ to expand to $\langle code \rangle$ as replacement text. Within the $\langle code \rangle$, the number of $\langle parameters \rangle$ is detected automatically from the function signature. These $\langle parameters \rangle$ ($\#1$, $\#2$, *etc.*) will be replaced by those absorbed by the function. The definition is global and an error results if the $\langle function \rangle$ is already defined.

<hr/> <code>\cs_new_nopar:Nn</code> <code>\cs_new_nopar:(cn Nx cx)</code> <hr/>	<code>\cs_new_nopar:Nn <function> {<code>}</code> <p>Creates $\langle function \rangle$ to expand to $\langle code \rangle$ as replacement text. Within the $\langle code \rangle$, the number of $\langle parameters \rangle$ is detected automatically from the function signature. These $\langle parameters \rangle$ ($\#1$, $\#2$, <i>etc.</i>) will be replaced by those absorbed by the function. When the $\langle function \rangle$ is used the $\langle parameters \rangle$ absorbed cannot contain <code>\par</code> tokens. The definition is global and an error results if the $\langle function \rangle$ is already defined.</p>
<hr/> <code>\cs_new_protected:Nn</code> <code>\cs_new_protected:(cn Nx cx)</code> <hr/>	<code>\cs_new_protected:Nn <function> {<code>}</code> <p>Creates $\langle function \rangle$ to expand to $\langle code \rangle$ as replacement text. Within the $\langle code \rangle$, the number of $\langle parameters \rangle$ is detected automatically from the function signature. These $\langle parameters \rangle$ ($\#1$, $\#2$, <i>etc.</i>) will be replaced by those absorbed by the function. The $\langle function \rangle$ will not expand within an x-type argument. The definition is global and an error results if the $\langle function \rangle$ is already defined.</p>
<hr/> <code>\cs_new_protected_nopar:Nn</code> <code>\cs_new_protected_nopar:(cn Nx cx)</code> <hr/>	<code>\cs_new_protected_nopar:Nn <function> {<code>}</code> <p>Creates $\langle function \rangle$ to expand to $\langle code \rangle$ as replacement text. Within the $\langle code \rangle$, the number of $\langle parameters \rangle$ is detected automatically from the function signature. These $\langle parameters \rangle$ ($\#1$, $\#2$, <i>etc.</i>) will be replaced by those absorbed by the function. When the $\langle function \rangle$ is used the $\langle parameters \rangle$ absorbed cannot contain <code>\par</code> tokens. The $\langle function \rangle$ will not expand within an x-type argument. The definition is global and an error results if the $\langle function \rangle$ is already defined.</p>
<hr/> <code>\cs_set:Nn</code> <code>\cs_set:(cn Nx cx)</code> <hr/>	<code>\cs_set:Nn <function> {<code>}</code> <p>Sets $\langle function \rangle$ to expand to $\langle code \rangle$ as replacement text. Within the $\langle code \rangle$, the number of $\langle parameters \rangle$ is detected automatically from the function signature. These $\langle parameters \rangle$ ($\#1$, $\#2$, <i>etc.</i>) will be replaced by those absorbed by the function. The assignment of a meaning to the $\langle function \rangle$ is restricted to the current \TeX group level.</p>
<hr/> <code>\cs_set_nopar:Nn</code> <code>\cs_set_nopar:(cn Nx cx)</code> <hr/>	<code>\cs_set_nopar:Nn <function> {<code>}</code> <p>Sets $\langle function \rangle$ to expand to $\langle code \rangle$ as replacement text. Within the $\langle code \rangle$, the number of $\langle parameters \rangle$ is detected automatically from the function signature. These $\langle parameters \rangle$ ($\#1$, $\#2$, <i>etc.</i>) will be replaced by those absorbed by the function. When the $\langle function \rangle$ is used the $\langle parameters \rangle$ absorbed cannot contain <code>\par</code> tokens. The assignment of a meaning to the $\langle function \rangle$ is restricted to the current \TeX group level.</p>
<hr/> <code>\cs_set_protected:Nn</code> <code>\cs_set_protected:(cn Nx cx)</code> <hr/>	<code>\cs_set_protected:Nn <function> {<code>}</code> <p>Sets $\langle function \rangle$ to expand to $\langle code \rangle$ as replacement text. Within the $\langle code \rangle$, the number of $\langle parameters \rangle$ is detected automatically from the function signature. These $\langle parameters \rangle$ ($\#1$, $\#2$, <i>etc.</i>) will be replaced by those absorbed by the function. The $\langle function \rangle$ will not expand within an x-type argument. The assignment of a meaning to the $\langle function \rangle$ is restricted to the current \TeX group level.</p>

<code>\cs_set_protected_nopar:Nn</code>	<code>\cs_set_protected_nopar:Nn <function> {<code>}</code>
<code>\cs_set_protected_nopar:(cn Nx cx)</code>	

Sets $\langle function \rangle$ to expand to $\langle code \rangle$ as replacement text. Within the $\langle code \rangle$, the number of $\langle parameters \rangle$ is detected automatically from the function signature. These $\langle parameters \rangle$ ($\#1$, $\#2$, *etc.*) will be replaced by those absorbed by the function. When the $\langle function \rangle$ is used the $\langle parameters \rangle$ absorbed cannot contain `\par` tokens. The $\langle function \rangle$ will not expand within an x-type argument. The assignment of a meaning to the $\langle function \rangle$ is restricted to the current TeX group level.

<code>\cs_gset:Nn</code>	<code>\cs_gset:Nn <function> {<code>}</code>
<code>\cs_gset:(cn Nx cx)</code>	

Sets $\langle function \rangle$ to expand to $\langle code \rangle$ as replacement text. Within the $\langle code \rangle$, the number of $\langle parameters \rangle$ is detected automatically from the function signature. These $\langle parameters \rangle$ ($\#1$, $\#2$, *etc.*) will be replaced by those absorbed by the function. The assignment of a meaning to the $\langle function \rangle$ is global.

<code>\cs_gset_nopar:Nn</code>	<code>\cs_gset_nopar:Nn <function> {<code>}</code>
<code>\cs_gset_nopar:(cn Nx cx)</code>	

Sets $\langle function \rangle$ to expand to $\langle code \rangle$ as replacement text. Within the $\langle code \rangle$, the number of $\langle parameters \rangle$ is detected automatically from the function signature. These $\langle parameters \rangle$ ($\#1$, $\#2$, *etc.*) will be replaced by those absorbed by the function. When the $\langle function \rangle$ is used the $\langle parameters \rangle$ absorbed cannot contain `\par` tokens. The assignment of a meaning to the $\langle function \rangle$ is global.

<code>\cs_gset_protected:Nn</code>	<code>\cs_gset_protected:Nn <function> {<code>}</code>
<code>\cs_gset_protected:(cn Nx cx)</code>	

Sets $\langle function \rangle$ to expand to $\langle code \rangle$ as replacement text. Within the $\langle code \rangle$, the number of $\langle parameters \rangle$ is detected automatically from the function signature. These $\langle parameters \rangle$ ($\#1$, $\#2$, *etc.*) will be replaced by those absorbed by the function. The $\langle function \rangle$ will not expand within an x-type argument. The assignment of a meaning to the $\langle function \rangle$ is global.

<code>\cs_gset_protected_nopar:Nn</code>	<code>\cs_gset_protected_nopar:Nn <function> {<code>}</code>
<code>\cs_gset_protected_nopar:(cn Nx cx)</code>	

Sets $\langle function \rangle$ to expand to $\langle code \rangle$ as replacement text. Within the $\langle code \rangle$, the number of $\langle parameters \rangle$ is detected automatically from the function signature. These $\langle parameters \rangle$ ($\#1$, $\#2$, *etc.*) will be replaced by those absorbed by the function. When the $\langle function \rangle$ is used the $\langle parameters \rangle$ absorbed cannot contain `\par` tokens. The $\langle function \rangle$ will not expand within an x-type argument. The assignment of a meaning to the $\langle function \rangle$ is global.

<code>\cs_generate_from_arg_count:NNnn</code>	<code>\cs_generate_from_arg_count:NNnn <function> <creator> {<number>}</code>
<code>\cs_generate_from_arg_count:(cNnn Ncnn)</code>	<code>{<code>}</code>

Updated: 2012-01-14

Uses the $\langle creator \rangle$ function (which should have signature Npn , for example `\cs_new:Npn`) to define a $\langle function \rangle$ which takes $\langle number \rangle$ arguments and has $\langle code \rangle$ as replacement text. The $\langle number \rangle$ of arguments is an integer expression, evaluated as detailed for `\int_eval:n`.

3.4 Copying control sequences

Control sequences (not just functions as defined above) can be set to have the same meaning using the functions described here. Making two control sequences equivalent means that the second control sequence is a *copy* of the first (rather than a pointer to it). Thus the old and new control sequence are not tied together: changes to one are not reflected in the other.

In the following text “cs” is used as an abbreviation for “control sequence”.

```
\cs_new_eq:NN
\cs_new_eq:(Nc|cN|cc)
```

```
\cs_new_eq:NN <cs1> <cs2>
\cs_new_eq:NN <cs1> <token>
```

Globally creates $\langle control\ sequence_1 \rangle$ and sets it to have the same meaning as $\langle control\ sequence_2 \rangle$ or $\langle token \rangle$. The second control sequence may subsequently be altered without affecting the copy.

```
\cs_set_eq:NN
\cs_set_eq:(Nc|cN|cc)
```

```
\cs_set_eq:NN <cs1> <cs2>
\cs_set_eq:NN <cs1> <token>
```

Sets $\langle control\ sequence_1 \rangle$ to have the same meaning as $\langle control\ sequence_2 \rangle$ (or $\langle token \rangle$). The second control sequence may subsequently be altered without affecting the copy. The assignment of a meaning to the $\langle control\ sequence_1 \rangle$ is restricted to the current \TeX group level.

```
\cs_gset_eq:NN
\cs_gset_eq:(Nc|cN|cc)
```

```
\cs_gset_eq:NN <cs1> <cs2>
\cs_gset_eq:NN <cs1> <token>
```

Globally sets $\langle control\ sequence_1 \rangle$ to have the same meaning as $\langle control\ sequence_2 \rangle$ (or $\langle token \rangle$). The second control sequence may subsequently be altered without affecting the copy. The assignment of a meaning to the $\langle control\ sequence_1 \rangle$ is *not* restricted to the current \TeX group level: the assignment is global.

3.5 Deleting control sequences

There are occasions where control sequences need to be deleted. This is handled in a very simple manner.

```
\cs_undefine:N
\cs_undefine:c
```

Updated: 2011-09-15

```
\cs_undefine:N <control\ sequence>
```

Sets $\langle control\ sequence \rangle$ to be globally undefined.

3.6 Showing control sequences

```
\cs_meaning:N ★
\cs_meaning:c ★
```

Updated: 2011-12-22

```
\cs_meaning:N <control\ sequence>
```

This function expands to the *meaning* of the $\langle control\ sequence \rangle$ control sequence. For a macro, this includes the $\langle replacement\ text \rangle$.

\TeX hackers note: This is \TeX ’s $\backslash meaning$ primitive. The `c` variant correctly reports undefined arguments.

`\cs_show:N`
`\cs_show:c`

Updated: 2017-02-14

`\cs_show:N` $\langle control\ sequence \rangle$
Displays the definition of the $\langle control\ sequence \rangle$ on the terminal.

T_EXhackers note: This is similar to the T_EX primitive `\show`, wrapped to a fixed number of characters per line.

`\cs_log:N`
`\cs_log:c`

New: 2014-08-22
Updated: 2017-02-14

`\cs_log:N` $\langle control\ sequence \rangle$
Writes the definition of the $\langle control\ sequence \rangle$ in the log file. See also `\cs_show:N` which displays the result in the terminal.

3.7 Converting to and from control sequences

`\use:c` ★

`\use:c` $\{\langle control\ sequence\ name \rangle\}$

Converts the given $\langle control\ sequence\ name \rangle$ into a single control sequence token. This process requires two expansions. The content for $\langle control\ sequence\ name \rangle$ may be literal material or from other expandable functions. The $\langle control\ sequence\ name \rangle$ must, when fully expanded, consist of character tokens which are not active: typically of category code 10 (space), 11 (letter) or 12 (other), or a mixture of these.

As an example of the `\use:c` function, both

`\use:c { a b c }`

and

`\tl_new:N \l_my_tl`
`\tl_set:Nn \l_my_tl { a b c }`
`\use:c { \tl_use:N \l_my_tl }`

would be equivalent to

`\abc`

after two expansions of `\use:c`.

`\cs_if_exist_use:N` ★
`\cs_if_exist_use:c` ★
`\cs_if_exist_use:NTF` ★
`\cs_if_exist_use:cTF` ★

New: 2012-11-10

`\cs_if_exist_use:N` $\langle control\ sequence \rangle$
`\cs_if_exist_use:NNTF` $\langle control\ sequence \rangle$ $\{\langle true\ code \rangle\}$ $\{\langle false\ code \rangle\}$

Tests whether the $\langle control\ sequence \rangle$ is currently defined (whether as a function or another control sequence type), and if it is inserts the $\langle control\ sequence \rangle$ into the input stream followed by the $\langle true\ code \rangle$. Otherwise the $\langle false\ code \rangle$ is used.

`\cs:w` ★
`\cs_end:` ★

`\cs:w` $\langle control\ sequence\ name \rangle$ `\cs_end:`

Converts the given $\langle control\ sequence\ name \rangle$ into a single control sequence token. This process requires one expansion. The content for $\langle control\ sequence\ name \rangle$ may be literal material or from other expandable functions. The $\langle control\ sequence\ name \rangle$ must, when fully expanded, consist of character tokens which are not active: typically of category code 10 (space), 11 (letter) or 12 (other), or a mixture of these.

T_EXhackers note: These are the T_EX primitives `\csname` and `\endcsname`.

As an example of the `\cs:w` and `\cs_end:` functions, both

```
\cs:w a b c \cs_end:
```

and

```
\tl_new:N \l_my_tl
\tl_set:Nn \l_my_tl { a b c }
\cs:w \tl_use:N \l_my_tl \cs_end:
```

would be equivalent to

```
\abc
```

after one expansion of `\cs:w`.

```
\cs_to_str:N ★ \cs_to_str:N <control sequence>
```

Converts the given *<control sequence>* into a series of characters with category code 12 (other), except spaces, of category code 10. The result does *not* include the current escape token, contrarily to `\token_to_str:N`. Full expansion of this function requires exactly 2 expansion steps, and so an x-type expansion, or two o-type expansions are required to convert the *<control sequence>* to a sequence of characters in the input stream. In most cases, an f-expansion is correct as well, but this loses a space at the start of the result.

4 Using or removing tokens and arguments

Tokens in the input can be read and used or read and discarded. If one or more tokens are wrapped in braces then when absorbing them the outer set is removed. At the same time, the category code of each token is set when the token is read by a function (if it is read more than once, the category code is determined by the situation in force when first function absorbs the token).

```
\use:n ★ \use:n {<group1>}
\use:nn ★ \use:nn {<group1>} {<group2>}
\use:nnn ★ \use:nnn {<group1>} {<group2>} {<group3>}
\use:nnnn ★ \use:nnnn {<group1>} {<group2>} {<group3>} {<group4>}
```

As illustrated, these functions absorb between one and four arguments, as indicated by the argument specifier. The braces surrounding each argument are removed and the remaining tokens are left in the input stream. The category code of these tokens is also fixed by this process (if it has not already been by some other absorption). All of these functions require only a single expansion to operate, so that one expansion of

```
\use:nn { abc } { { def } }
```

results in the input stream containing

```
abc { def }
```

i.e. only the outer braces are removed.

<code>\use_i:nn</code>	★	<code>\use_i:nn {\langle arg_1 \rangle} {\langle arg_2 \rangle}</code>
------------------------	---	--

<code>\use_ii:nn</code>	★	These functions absorb two arguments from the input stream. The function <code>\use_i:nn</code> discards the second argument, and leaves the content of the first argument in the input stream. <code>\use_ii:nn</code> discards the first argument and leaves the content of the second argument in the input stream. The category code of these tokens is also fixed (if it has not already been by some other absorption). A single expansion is needed for the functions to take effect.
-------------------------	---	--

<code>\use_i:nnn</code>	★	<code>\use_i:nnn {\langle arg_1 \rangle} {\langle arg_2 \rangle} {\langle arg_3 \rangle}</code>
-------------------------	---	---

<code>\use_ii:nnn</code>	★	These functions absorb three arguments from the input stream. The function <code>\use_i:nnn</code> discards the second and third arguments, and leaves the content of the first argument in the input stream. <code>\use_ii:nnn</code> and <code>\use_iii:nnn</code> work similarly, leaving the content of second or third arguments in the input stream, respectively. The category code of these tokens is also fixed (if it has not already been by some other absorption). A single expansion is needed for the functions to take effect.
<code>\use_iii:nnn</code>	★	

<code>\use_i:nnnn</code>	★	<code>\use_i:nnnn {\langle arg_1 \rangle} {\langle arg_2 \rangle} {\langle arg_3 \rangle} {\langle arg_4 \rangle}</code>
--------------------------	---	--

<code>\use_ii:nnnn</code>	★	These functions absorb four arguments from the input stream. The function <code>\use_i:nnnn</code> discards the second, third and fourth arguments, and leaves the content of the first argument in the input stream. <code>\use_ii:nnnn</code> , <code>\use_iii:nnnn</code> and <code>\use_iv:nnnn</code> work similarly, leaving the content of second, third or fourth arguments in the input stream, respectively. The category code of these tokens is also fixed (if it has not already been by some other absorption). A single expansion is needed for the functions to take effect.
<code>\use_iii:nnnn</code>	★	
<code>\use_iv:nnnn</code>	★	

<code>\use_i_ii:nnn</code>	★	<code>\use_i_ii:nnn {\langle arg_1 \rangle} {\langle arg_2 \rangle} {\langle arg_3 \rangle}</code>
----------------------------	---	--

This function absorbs three arguments and leaves the content of the first and second in the input stream. The category code of these tokens is also fixed (if it has not already been by some other absorption). A single expansion is needed for the function to take effect. An example:

`\use_i_ii:nnn { abc } { { def } } { ghi }`

results in the input stream containing

`abc { def }`

i.e. the outer braces are removed and the third group is removed.

<code>\use_none:n</code>	★	<code>\use_none:n {\langle group_1 \rangle}</code>
--------------------------	---	--

<code>\use_none:nn</code>	★	These functions absorb between one and nine groups from the input stream, leaving nothing on the resulting input stream. These functions work after a single expansion. One or more of the <code>n</code> arguments may be an unbraced single token (<i>i.e.</i> an <code>N</code> argument).
<code>\use_none:nnn</code>	★	
<code>\use_none:nnnn</code>	★	
<code>\use_none:nnnnn</code>	★	
<code>\use_none:nnnnnn</code>	★	

<code>\use_none:nnnnnn</code>	★
-------------------------------	---

<code>\use_none:nnnnnnn</code>	★
--------------------------------	---

<code>\use_none:nnnnnnnn</code>	★
---------------------------------	---

<code>\use_none:nnnnnnnnn</code>	★
----------------------------------	---

<code>\use:x</code>	<code>\use:x {⟨expandable tokens⟩}</code>
---------------------	---

Updated: 2011-12-31	Fully expands the <i>⟨expandable tokens⟩</i> and inserts the result into the input stream at the current location. Any hash characters (#) in the argument must be doubled.
---------------------	---

4.1 Selecting tokens from delimited arguments

A different kind of function for selecting tokens from the token stream are those that use delimited arguments.

<code>\use_none_delimit_by_q_nil:w</code>	★	<code>\use_none_delimit_by_q_nil:w ⟨balanced text⟩ \q_nil</code>
<code>\use_none_delimit_by_q_stop:w</code>	★	<code>\use_none_delimit_by_q_stop:w ⟨balanced text⟩ \q_stop</code>
<code>\use_none_delimit_by_q_recursion_stop:w</code>	★	<code>\use_none_delimit_by_q_recursion_stop:w ⟨balanced text⟩</code> <code>\q_recursion_stop</code>

Absorb the *⟨balanced text⟩* from the input stream delimited by the marker given in the function name, leaving nothing in the input stream.

<code>\use_i_delimit_by_q_nil:nw</code>	★	<code>\use_i_delimit_by_q_nil:nw {⟨inserted tokens⟩} ⟨balanced text⟩</code>
<code>\use_i_delimit_by_q_stop:nw</code>	★	<code>\q_nil</code>
<code>\use_i_delimit_by_q_recursion_stop:nw</code>	★	<code>\use_i_delimit_by_q_stop:nw {⟨inserted tokens⟩} ⟨balanced</code> <code>text⟩ \q_stop</code> <code>\use_i_delimit_by_q_recursion_stop:nw {⟨inserted tokens⟩}</code> <code>⟨balanced text⟩ \q_recursion_stop</code>

Absorb the *⟨balanced text⟩* from the input stream delimited by the marker given in the function name, leaving *⟨inserted tokens⟩* in the input stream for further processing.

5 Predicates and conditionals

L^AT_EX3 has three concepts for conditional flow processing:

Branching conditionals Functions that carry out a test and then execute, depending on its result, either the code supplied as the *⟨true code⟩* or the *⟨false code⟩*. These arguments are denoted with T and F, respectively. An example would be

`\cs_if_free:cTF {abc} {⟨true code⟩} {⟨false code⟩}`

a function that turns the first argument into a control sequence (since it's marked as c) then checks whether this control sequence is still free and then depending on the result carries out the code in the second argument (true case) or in the third argument (false case).

These type of functions are known as “conditionals”; whenever a TF function is defined it is usually accompanied by T and F functions as well. These are provided for convenience when the branch only needs to go a single way. Package writers are free to choose which types to define but the kernel definitions always provide all three versions.

Important to note is that these branching conditionals with *⟨true code⟩* and/or *⟨false code⟩* are always defined in a way that the code of the chosen alternative can operate on following tokens in the input stream.

These conditional functions may or may not be fully expandable, but if they are expandable they are accompanied by a “predicate” for the same test as described below.

Predicates “Predicates” are functions that return a special type of boolean value which can be tested by the boolean expression parser. All functions of this type are expandable and have names that end with `_p` in the description part. For example,

`\cs_if_free_p:N`

would be a predicate function for the same type of test as the conditional described above. It would return “true” if its argument (a single token denoted by `N`) is still free for definition. It would be used in constructions like

```
\bool_if:nTF {
  \cs_if_free_p:N \l_tmpz_tl || \cs_if_free_p:N \g_tmpz_tl
} {\true code} {\false code}
```

For each predicate defined, a “branching conditional” also exists that behaves like a conditional described above.

Primitive conditionals There is a third variety of conditional, which is the original concept used in plain \TeX and $\text{\LaTeX 2}_{\epsilon}$. Their use is discouraged in `expl3` (although still used in low-level definitions) because they are more fragile and in many cases require more expansion control (hence more code) than the two types of conditionals described above.

`\c_true_bool`
`\c_false_bool`

Constants that represent `true` and `false`, respectively. Used to implement predicates.

5.1 Tests on control sequences

`\cs_if_eq_p:NN` ★
`\cs_if_eq:NNTF` ★

`\cs_if_eq_p:NN` $\langle cs_1 \rangle$ $\langle cs_2 \rangle$
`\cs_if_eq:NNTF` $\langle cs_1 \rangle$ $\langle cs_2 \rangle$ $\{\langle true\ code \rangle\}$ $\{\langle false\ code \rangle\}$

Compares the definition of two $\langle control\ sequence \rangle$ and is logically `true` if they are the same, *i.e.* if they have exactly the same definition when examined with `\cs_show:N`.

`\cs_if_exist_p:N` ★
`\cs_if_exist_p:c` ★
`\cs_if_exist:NTF` ★
`\cs_if_exist:cTF` ★

`\cs_if_exist_p:N` $\langle control\ sequence \rangle$
`\cs_if_exist:NTF` $\langle control\ sequence \rangle$ $\{\langle true\ code \rangle\}$ $\{\langle false\ code \rangle\}$
`\cs_if_exist:NTF` ★ Tests whether the $\langle control\ sequence \rangle$ is currently defined (whether as a function or another control sequence type). Any valid definition of $\langle control\ sequence \rangle$ evaluates as `true`.
`\cs_if_exist:cTF` ★

`\cs_if_free_p:N` ★
`\cs_if_free_p:c` ★
`\cs_if_free:NTF` ★
`\cs_if_free:cTF` ★

`\cs_if_free_p:N` $\langle control\ sequence \rangle$
`\cs_if_free:NTF` $\langle control\ sequence \rangle$ $\{\langle true\ code \rangle\}$ $\{\langle false\ code \rangle\}$
`\cs_if_free:NTF` ★ Tests whether the $\langle control\ sequence \rangle$ is currently free to be defined. This test is `false` if the $\langle control\ sequence \rangle$ currently exists (as defined by `\cs_if_exist:N`).
`\cs_if_free:cTF` ★

5.2 Primitive conditionals

The ε -TeX engine itself provides many different conditionals. Some expand whatever comes after them and others don't. Hence the names for these underlying functions often contains a :w part but higher level functions are often available. See for instance `\int_compare_p:nNn` which is a wrapper for `\if_int_compare:w`.

Certain conditionals deal with specific data types like boxes and fonts and are described there. The ones described below are either the universal conditionals or deal with control sequences. We prefix primitive conditionals with `\if_`.

<code>\if_true:</code>	★	<code>\if_true: <true code> \else: <false code> \fi:</code>
<code>\if_false:</code>	★	<code>\if_false: <true code> \else: <false code> \fi:</code>
<code>\else:</code>	★	<code>\reverse_if:N <primitive conditional></code>
<code>\fi:</code>	★	<code>\if_true:</code> always executes <code><true code></code> , while <code>\if_false:</code> always executes <code><false code></code> .
<code>\reverse_if:N</code>	★	<code>\reverse_if:N</code> reverses any two-way primitive conditional. <code>\else:</code> and <code>\fi:</code> delimit the branches of the conditional. The function <code>\or:</code> is documented in <code>l3int</code> and used in case switches.

TeXhackers note: These are equivalent to their corresponding TeX primitive conditionals; `\reverse_if:N` is ε -TeX's `\unless`.

<code>\if_meaning:w</code>	★	<code>\if_meaning:w <arg₁> <arg₂> <true code> \else: <false code> \fi:</code>
----------------------------	---	---

`\if_meaning:w` executes `<true code>` when `<arg1>` and `<arg2>` are the same, otherwise it executes `<false code>`. `<arg1>` and `<arg2>` could be functions, variables, tokens; in all cases the *unexpanded* definitions are compared.

TeXhackers note: This is TeX's `\ifx`.

<code>\if:w</code>	★	<code>\if:w <token₁> <token₂> <true code> \else: <false code> \fi:</code>
<code>\if_charcode:w</code>	★	<code>\if_catcode:w <token₁> <token₂> <true code> \else: <false code> \fi:</code>
<code>\if_catcode:w</code>	★	These conditionals expand any following tokens until two unexpandable tokens are left. If you wish to prevent this expansion, prefix the token in question with <code>\exp_not:N</code> . <code>\if_catcode:w</code> tests if the category codes of the two tokens are the same whereas <code>\if:w</code> tests if the character codes are identical. <code>\if_charcode:w</code> is an alternative name for <code>\if:w</code> .

<code>\if_cs_exist:N</code>	★	<code>\if_cs_exist:N <cs> <true code> \else: <false code> \fi:</code>
<code>\if_cs_exist:w</code>	★	<code>\if_cs_exist:w <tokens> \cs_end: <true code> \else: <false code> \fi:</code>

Check if `<cs>` appears in the hash table or if the control sequence that can be formed from `<tokens>` appears in the hash table. The latter function does not turn the control sequence in question into `\scan_stop:!` This can be useful when dealing with control sequences which cannot be entered as a single token.

<code>\if_mode_horizontal:</code>	★	<code>\if_mode_horizontal: <true code> \else: <false code> \fi:</code>
<code>\if_mode_vertical:</code>	★	
<code>\if_mode_math:</code>	★	Execute <code><true code></code> if currently in horizontal mode, otherwise execute <code><false code></code> . Similar for the other functions.
<code>\if_mode_inner:</code>	★	

6 Internal kernel functions

<hr/> <code>_chk_if_free_cs:N</code> <hr/>	<code>_chk_if_free_cs:N</code> $\langle cs \rangle$
<code>_chk_if_free_cs:c</code>	This function checks that $\langle cs \rangle$ is free according to the criteria for <code>\cs_if_free_p:N</code> , and if not raises a kernel-level error.
<hr/> <code>_cs_count_signature:N</code> \star <hr/>	<code>_cs_count_signature:N</code> $\langle function \rangle$
<code>_cs_count_signature:c</code> \star	Splits the $\langle function \rangle$ into the $\langle name \rangle$ (<i>i.e.</i> the part before the colon) and the $\langle signature \rangle$ (<i>i.e.</i> after the colon). The $\langle number \rangle$ of tokens in the $\langle signature \rangle$ is then left in the input stream. If there was no $\langle signature \rangle$ then the result is the marker value -1 .
<hr/> <code>_cs_split_function:NN</code> \star <hr/>	<code>_cs_split_function:NN</code> $\langle function \rangle$ $\langle processor \rangle$
	Splits the $\langle function \rangle$ into the $\langle name \rangle$ (<i>i.e.</i> the part before the colon) and the $\langle signature \rangle$ (<i>i.e.</i> after the colon). This information is then placed in the input stream after the $\langle processor \rangle$ function in three parts: the $\langle name \rangle$, the $\langle signature \rangle$ and a logic token indicating if a colon was found (to differentiate variables from function names). The $\langle name \rangle$ does not include the escape character, and both the $\langle name \rangle$ and $\langle signature \rangle$ are made up of tokens with category code 12 (other). The $\langle processor \rangle$ should be a function with argument specification <code>:nnN</code> (plus any trailing arguments needed).
<hr/> <code>_cs_get_function_name:N</code> \star <hr/>	<code>_cs_get_function_name:N</code> $\langle function \rangle$
	Splits the $\langle function \rangle$ into the $\langle name \rangle$ (<i>i.e.</i> the part before the colon) and the $\langle signature \rangle$ (<i>i.e.</i> after the colon). The $\langle name \rangle$ is then left in the input stream without the escape character present made up of tokens with category code 12 (other).
<hr/> <code>_cs_get_function_signature:N</code> \star <hr/>	<code>_cs_get_function_signature:N</code> $\langle function \rangle$
	Splits the $\langle function \rangle$ into the $\langle name \rangle$ (<i>i.e.</i> the part before the colon) and the $\langle signature \rangle$ (<i>i.e.</i> after the colon). The $\langle signature \rangle$ is then left in the input stream made up of tokens with category code 12 (other).
<hr/> <code>_cs_tmp:w</code> <hr/>	Function used for various short-term usages, for instance defining functions whose definition involves tokens which are hard to insert normally (spaces, characters with category other).
<hr/> <code>_debug:TF</code> <hr/>	<code>_debug:TF</code> $\{\langle true code \rangle\}$ $\{\langle false code \rangle\}$
	Runs the $\langle true code \rangle$ if debugging is enabled, namely only in L ^A T _E X 2 _ε package mode with one of the options <code>check-declarations</code> , <code>enable-debug</code> , or <code>log-functions</code> . Otherwise runs the $\langle false code \rangle$. The T and F variants are not provided for this low-level conditional.
<hr/> <code>_debug_chk_cs_exist:N</code> <hr/>	<code>_debug_chk_cs_exist:N</code> $\langle cs \rangle$
<code>_debug_chk_cs_exist:c</code>	This function is only created if debugging is enabled. It checks that $\langle cs \rangle$ exists according to the criteria for <code>\cs_if_exist_p:N</code> , and if not raises a kernel-level error.

<u><code>__debug_chk_expr:nNn</code></u>	<code>__debug_chk_expr:nNn {<expr>} {<eval>} {<convert>} {<caller>}</code> This function is only created if debugging is enabled. By default it is equivalent to <code>\use_i:nnnn</code> . When expression checking is enabled, it leaves in the input stream the result of <code>\tex_the:D {<eval>} {<expr>} \tex_relax:D</code> after checking that no token was left over. If any token was not taken as part of the expression, there is an error message displaying the result of the evaluation as well as the <code><caller></code> . For instance <code><eval></code> can be <code>__int_eval:w</code> and <code><caller></code> can be <code>\int_eval:n</code> or <code>\int_set:Nn</code> . The argument <code><convert></code> is empty except for mu expressions where it is <code>\etex_mutoglu:D</code> , used for internal purposes.
<u><code>__debug_chk_var_exist:N</code></u>	<code>__debug_chk_var_exist:N {<var>}</code> This function is only created if debugging is enabled. It checks that <code><var></code> is defined according to the criteria for <code>\cs_if_exist_p:N</code> , and if not raises a kernel-level error.
<u><code>__debug_chk_var_scope:NN</code></u>	<code>__debug_chk_var_scope:NN {<scope>} {<var>}</code> Checks the <code><var></code> has the correct <code><scope></code> , and if not raises a kernel-level error. This function is only created if debugging is enabled. The <code><scope></code> is a single letter <code>l</code> , <code>g</code> , <code>c</code> denoting local variables, global variables, or constants. More precisely, if the variable name starts with a letter and an underscore (normal <code>expl3</code> convention) the function checks that this single letter matches the <code><scope></code> . Otherwise the function cannot know the scope <code><var></code> the first time: instead, it defines <code>__debug_chk_/{<var name>}</code> to store that information for the next call. Thus, if a given <code><var></code> is subject to assignments of different scopes a kernel error will result.
<u><code>__debug_chk_var_local:N</code></u> <u><code>__debug_chk_var_global:N</code></u>	<code>__debug_chk_var_local:N {<var>}</code> <code>__debug_chk_var_global:N {<var>}</code> Applies <code>__debug_chk_var_exist:N {<var>}</code> , then <code>__debug_chk_var_scope:NN {<scope>} {<var>}</code> , where <code><scope></code> is <code>l</code> or <code>g</code> .
<u><code>__debug_log:x</code></u>	<code>__debug_log:x {<message text>}</code> If the <code>log-functions</code> option is active, this function writes the <code><message text></code> to the log file using <code>\iow_log:x</code> . Otherwise, the <code><message text></code> is ignored using <code>\use_none:n</code> . This function is only created if debugging is enabled.
<u><code>__debug_patch:nnNpnn</code></u>	<code>__debug_patch:nnNpnn {<before>} {<after>} {<definition>} {<function>} {<parameters>} {<code>}</code> If debugging is not enabled, this function ignores the <code><before></code> and <code><after></code> code and performs the <code><definition></code> with no patching. Otherwise it replaces <code><code></code> by <code><before> {<code>} {<after>}</code> (which can involve <code>#1</code> and so on) in the <code><definition></code> that follows. The <code><definition></code> must start with <code>\cs_new:Npn</code> or <code>\cs_set:Npn</code> or <code>\cs_gset:Npn</code> or their <code>_protected</code> counterparts. Other cases can be added as needed.
<u><code>__debug_patch_conditional:nnNpnn</code></u>	<code>__debug_patch_conditional:nnNpnn {<before>} {<definition>} {<conditional>} {<parameters>} {<type>} {<code>}</code> Similar to <code>__debug_patch:nnNpnn</code> for conditionals, namely <code><definition></code> must be <code>\prg_new_conditional:Npnn</code> or its <code>_protected</code> counterpart. There is no <code><after></code> code because that would interfere with the action of the conditional.

<hr/>	
<code>__debug_patch_args:nNNpn</code>	<code>__debug_patch_args:nNNpn {<arguments>}</code>
<code>__debug_patch_conditional_args:nNNpnn</code>	<code><definition> <function> <parameters> {<code>}</code>
<hr/>	

Like `__debug_patch:nNNpn`, this tweaks the following definition, but from the “inside out” (and if debugging is not enabled, the `<arguments>` are ignored). It replaces `#1`, `#2` and so on in the `<code>` of the definition as indicated by the `<arguments>`. More precisely, a temporary function is defined using the `<definition>` with the `<parameters>` and `<code>`, then the result of expanding that function once in front of the `<arguments>` is used instead of the `<code>` when defining the actual function. For instance,

```
\__debug_patch_args:nNNpn { { (#1) } }
\cs_new:Npn \int_eval:n #1
{ \__int_value:w \__int_eval:w #1 \__int_eval_end: }
```

would replace `#1` by `(#1)` in the definition of `\int_eval:n` when debugging is enabled. This fails if the `<code>` contains `##`. The `__debug_patch_conditional_args:nNNpnn` function is for use before `\prg_new_conditional:Npnn` or its `_protected` counterpart.

<hr/>	
<code>__debug_patch_args:nnnNNpn</code>	<code>__debug_patch_args:nnnNNpn {<before>} {<after>} {<arguments>}</code>
<code>__debug_patch_conditional_args:nnnNNpnn</code>	<code><definition> <function> <parameters> {<code>}</code>
<hr/>	

A combination of `__debug_patch:nNNpn` and `__debug_patch_args:nNNpn`.

<hr/>	
<code>_kernel_check_defined:NT</code>	<code>_kernel_check_defined:NT <variable> {<true code>}</code>
<hr/>	

If `<variable>` is not defined (according to `\cs_if_exist:NTF`), this triggers an error, otherwise the `<true code>` is run.

<hr/>	
<code>_kernel_register_show:N</code>	<code>_kernel_register_show:N <register></code>
<code>_kernel_register_show:c</code>	
<hr/>	

Used to show the contents of a T_EX register at the terminal, formatted such that internal parts of the mechanism are not visible.

<hr/>	
<code>_kernel_register_log:N</code>	<code>_kernel_register_log:N <register></code>
<code>_kernel_register_log:c</code>	
<hr/>	

Used to write the contents of a T_EX register to the log file in a form similar to `__kernel_register_show:N`.

Updated: 2015-08-03

<hr/>	
<code>_prg_case_end:nw ★</code>	<code>_prg_case_end:nw {<code>} <tokens> \q_mark {<true code>} \q_mark {<false code>} \q_stop</code>
<hr/>	

Used to terminate case statements (`\int_case:nnTF`, *etc.*) by removing trailing `<tokens>` and the end marker `\q_stop`, inserting the `<code>` for the successful case (if one is found) and either the `true code` or `false code` for the over all outcome, as appropriate.

Part V

The l3expan package

Argument expansion

This module provides generic methods for expanding T_EX arguments in a systematic manner. The functions in this module all have prefix `exp`.

Not all possible variations are implemented for every base function. Instead only those that are used within the L^AT_EX3 kernel or otherwise seem to be of general interest are implemented. Consult the module description to find out which functions are actually defined. The next section explains how to define missing variants.

1 Defining new variants

The definition of variant forms for base functions may be necessary when writing new functions or when applying a kernel function in a situation that we haven't thought of before.

Internally preprocessing of arguments is done with functions from the `\exp_` module. They all look alike, an example would be `\exp_args:NNo`. This function has three arguments, the first and the second are a single tokens, while the third argument should be given in braces. Applying `\exp_args:NNo` expands the content of third argument once before any expansion of the first and second arguments. If `\seq_gpush:No` was not defined it could be coded in the following way:

```
\exp_args:NNo \seq_gpush:Nn
  \g_file_name_stack
  { \l_tmpa_tl }
```

In other words, the first argument to `\exp_args:NNo` is the base function and the other arguments are preprocessed and then passed to this base function. In the example the first argument to the base function should be a single token which is left unchanged while the second argument is expanded once. From this example we can also see how the variants are defined. They just expand into the appropriate `\exp_` function followed by the desired base function, *e.g.*

```
\cs_generate_variant:Nn \seq_gpush:Nn { No }
```

results in the definition of `\seq_gpush:No`

```
\cs_new:Npn \seq_gpush:No { \exp_args:NNo \seq_gpush:Nn }
```

Providing variants in this way in style files is safe as the `\cs_generate_variant:Nn` function will only create new definitions if there is not already one available. Therefore adding such definition to later releases of the kernel will not make such style files obsolete.

The steps above may be automated by using the function `\cs_generate_variant:Nn`, described next.

2 Methods for defining variants

We recall the set of available argument specifiers.

- `N` is used for single-token arguments while `c` constructs a control sequence from its name and passes it to a parent function as an `N`-type argument.
- Many argument types extract or expand some tokens and provide it as an `n`-type argument, namely a braced multiple-token argument: `V` extracts the value of a variable, `v` extracts the value from the name of a variable, `n` uses the argument as it is, `o` expands once, `f` expands fully the first token, `x` expands fully all tokens at the price of being non-expandable.
- A few odd argument types remain: `T` and `F` for conditional processing, otherwise identical to `n`-type arguments, `p` for the parameter text in definitions, `w` for arguments with a specific syntax, and `D` to denote primitives that should not be used directly.

`\cs_generate_variant:Nn`

Updated: 2017-11-28

`\cs_generate_variant:Nn` \langle parent control sequence \rangle $\{$ \langle variant argument specifiers \rangle $\}$

This function is used to define argument-specifier variants of the \langle parent control sequence \rangle for L^AT_EX3 code-level macros. The \langle parent control sequence \rangle is first separated into the \langle base name \rangle and \langle original argument specifier \rangle . The comma-separated list of \langle variant argument specifiers \rangle is then used to define variants of the \langle original argument specifier \rangle if these are not already defined. For each \langle variant \rangle given, a function is created that expands its arguments as detailed and passes them to the \langle parent control sequence \rangle . So for example

```
\cs_set:Npn \foo:Nn #1#2 { code here }
\cs_generate_variant:Nn \foo:Nn { c }
```

creates a new function `\foo:cn` which expands its first argument into a control sequence name and passes the result to `\foo:Nn`. Similarly

```
\cs_generate_variant:Nn \foo:Nn { NV , cV }
```

generates the functions `\foo:NV` and `\foo:cV` in the same way. The `\cs_generate_variant:Nn` function can only be applied if the \langle parent control sequence \rangle is already defined. If the \langle parent control sequence \rangle is protected or if the \langle variant \rangle involves x arguments, then the \langle variant control sequence \rangle is also protected. The \langle variant \rangle is created globally, as is any `\exp_args:N \langle variant \rangle` function needed to carry out the expansion.

Only n and N arguments can be changed to other types. The only allowed changes are

- c variant of an N parent;
- o , V , v , f , or x variant of an n parent;
- N , n , T , F , or p argument unchanged.

This means the \langle parent \rangle of a \langle variant \rangle form is always unambiguous, even in cases where both an n -type parent and an N -type parent exist, such as for `\tl_count:n` and `\tl_count:N`.

For backward compatibility it is currently possible to make n , o , V , v , f , or x -type variants of an N -type argument or N or c -type variants of an n -type argument. Both are deprecated. The first because passing more than one token to an N -type argument will typically break the parent function's code. The second because programmers who use that most often want to access the value of a variable given its name, hence should use a V -type or v -type variant instead of c -type. In those cases, using the lower-level `\exp_args:No` or `\exp_args:Nc` functions explicitly is preferred to defining confusing variants.

3 Introducing the variants

It is usually best to follow the following guidelines when defining new functions that are supposed to come with variant forms.

- Arguments that need full expansion (*i.e.*, are denoted with x) should be avoided if possible as they can not be processed expandably, *i.e.*, functions of this type cannot work correctly in arguments that are themselves subject to x expansion.

When speed is essential (for functions that do very little work and are used numerous times in a document) the following applies because internal functions for argument expansion come in two flavours, some faster than others.

- Arguments that might need expansion should come first in the list of arguments.
- Arguments that should consist of single tokens `N`, `c`, `V`, or `v` should come first among these.
- Arguments that appear after the first multi-token argument `n`, `f` or `o` require slightly slower special processing to be expanded. Therefore it is best to use the optimized functions, namely those that contain only `N`, `c`, `V`, and `v`, and, in the last position, `o`, `f`, with possible trailing `N` or `n` or `T` or `F`, which are not expanded.

The `V` type returns the value of a register, which can be one of `tl`, `clist`, `int`, `skip`, `dim`, `muskip`, or built-in `TEX` registers. The `v` type is the same except it first creates a control sequence out of its argument before returning the value.

In general, the programmer should not need to be concerned with expansion control. When simply using the content of a variable, functions with a `V` specifier should be used. For those referred to by `(cs)name`, the `v` specifier is available for the same purpose. Only when specific expansion steps are needed, such as when using delimited arguments, should the lower-level functions with `o` specifiers be employed.

The `f` type is so special that it deserves an example. It is typically used in contexts where only expandable commands are allowed. Then `x`-expansion cannot be used, and `f`-expansion provides an alternative that expands as much as can be done in such contexts. For instance, say that we want to evaluate the integer expression `3+4` and pass the result `7` as an argument to an expandable function `\example:n`. For this, one should define a variant using `\cs_generate_variant:Nn \example:n { f }`, then do

```
\example:f { \int_eval:n { 3 + 4 } }
```

Note that `x`-expansion would also expand `\int_eval:n` fully to its result `7`, but the variant `\example:x` cannot be expandable. Note also that `o`-expansion would not expand `\int_eval:n` fully to its result since that function requires several expansions. Besides the fact that `x`-expansion is protected rather than expandable, another difference between `f`-expansion and `x`-expansion is that `f`-expansion expands tokens from the beginning and stops as soon as a non-expandable token is encountered, while `x`-expansion continues expanding further tokens. Thus, for instance

```
\example:f { \int_eval:n { 1 + 2 } , \int_eval:n { 3 + 4 } }
```

results in the call `\example:n { 3 , \int_eval:n { 3 + 4 } }` while using `\example:x` instead results in `\example:n { 3 , 7 }` at the cost of being protected. If you use this type of expansion in conditional processing then you should stick to using `TF` type functions only as the expansion does not finish any `\if... \fi`: itself!

It is important to note that both `f`- and `o`-type expansion are concerned with the expansion of tokens from left to right in their arguments. In particular, `o`-type expansion applies to the first *token* in the argument it receives: it is conceptually similar to

```
\exp_after:wN <base function> \exp_after:wN { <argument> }
```

At the same time, `f`-type expansion stops at the *first* non-expandable token. This means for example that both

`\tl_set:No \l_tmpa_tl { { \g_tmpb_tl } }`

and

`\tl_set:Nf \l_tmpa_tl { { \g_tmpb_tl } }`

leave `\g_tmpb_tl` unchanged: `{` is the first token in the argument and is non-expandable.

4 Manipulating the first argument

These functions are described in detail: expansion of multiple tokens follows the same rules but is described in a shorter fashion.

`\exp_args:Nc` ★
`\exp_args:cc` ★

`\exp_args:Nc` $\langle function \rangle$ $\{\langle tokens \rangle\}$

This function absorbs two arguments (the $\langle function \rangle$ name and the $\langle tokens \rangle$). The $\langle tokens \rangle$ are expanded until only characters remain, and are then turned into a control sequence. (An internal error occurs if non-characters remain, as the conversion is not possible.) The result is inserted into the input stream *after* reinsertion of the $\langle function \rangle$. Thus the $\langle function \rangle$ may take more than one argument: all others are left unchanged.

The `:cc` variant constructs the $\langle function \rangle$ name in the same manner as described for the $\langle tokens \rangle$.

`\exp_args:No` ★

`\exp_args:No` $\langle function \rangle$ $\{\langle tokens \rangle\}$...

This function absorbs two arguments (the $\langle function \rangle$ name and the $\langle tokens \rangle$). The $\langle tokens \rangle$ are expanded once, and the result is inserted in braces into the input stream *after* reinsertion of the $\langle function \rangle$. Thus the $\langle function \rangle$ may take more than one argument: all others are left unchanged.

`\exp_args:Nv` ★

`\exp_args:Nv` $\langle function \rangle$ $\langle variable \rangle$

This function absorbs two arguments (the names of the $\langle function \rangle$ and the $\langle variable \rangle$). The content of the $\langle variable \rangle$ are recovered and placed inside braces into the input stream *after* reinsertion of the $\langle function \rangle$. Thus the $\langle function \rangle$ may take more than one argument: all others are left unchanged.

`\exp_args:Nv` ★

`\exp_args:Nv` $\langle function \rangle$ $\{\langle tokens \rangle\}$

This function absorbs two arguments (the $\langle function \rangle$ name and the $\langle tokens \rangle$). The $\langle tokens \rangle$ are expanded until only characters remain, and are then turned into a control sequence. (An internal error occurs if non-characters remain, as the conversion is not possible.) This control sequence should be the name of a $\langle variable \rangle$. The content of the $\langle variable \rangle$ are recovered and placed inside braces into the input stream *after* reinsertion of the $\langle function \rangle$. Thus the $\langle function \rangle$ may take more than one argument: all others are left unchanged.

`\exp_args:Nf` ★

`\exp_args:Nf` $\langle function \rangle$ $\{\langle tokens \rangle\}$

This function absorbs two arguments (the $\langle function \rangle$ name and the $\langle tokens \rangle$). The $\langle tokens \rangle$ are fully expanded until the first non-expandable token is found (if that is a space it is removed), and the result is inserted in braces into the input stream *after* reinsertion of the $\langle function \rangle$. Thus the $\langle function \rangle$ may take more than one argument: all others are left unchanged.

<code>\exp_args:Nx</code>	<code>\exp_args:Nx <function> {\tokens}</code>
---------------------------	--

This function absorbs two arguments (the *<function>* name and the *<tokens>*) and exhaustively expands the *<tokens>*. The result is inserted in braces into the input stream *after* reinsertion of the *<function>*. Thus the *<function>* may take more than one argument: all others are left unchanged.

5 Manipulating two arguments

<code>\exp_args:NNc</code> *	<code>\exp_args:NNc <token₁₂</code>
------------------------------	---

These optimized functions absorb three arguments and expand the second and third as detailed by their argument specifier. The first argument of the function is then the next item on the input stream, followed by the expansion of the second and third arguments.

<code>\exp_args:Ncc</code> *
<code>\exp_args:Nco</code> *
<code>\exp_args:NcV</code> *
<code>\exp_args:Ncv</code> *
<code>\exp_args:Ncf</code> *
<code>\exp_args:NVV</code> *

<code>\exp_args:Nnc</code> *	<code>\exp_args:Nno <token> {\tokens₁} {\tokens₂}</code>
------------------------------	--

These functions absorb three arguments and expand the second and third as detailed by their argument specifier. The first argument of the function is then the next item on the input stream, followed by the expansion of the second and third arguments. These functions need slower processing.

<code>\exp_args:Noo</code> *
<code>\exp_args:Nof</code> *
<code>\exp_args:NVo</code> *
<code>\exp_args:Nfo</code> *
<code>\exp_args:Nff</code> *

Updated: 2012-01-14

<code>\exp_args:NNx</code>	<code>\exp_args:NNx <token₁₂</code>
----------------------------	---

These functions absorb three arguments and expand the second and third as detailed by their argument specifier. The first argument of the function is then the next item on the input stream, followed by the expansion of the second and third arguments. These functions are not expandable due to their x-type argument.

<code>\exp_args:Ncx</code>
<code>\exp_args:Nnx</code>
<code>\exp_args:Nox</code>
<code>\exp_args:Nxo</code>
<code>\exp_args:Nxx</code>

6 Manipulating three arguments

<code>\exp_args:NNNo</code> *	<code>\exp_args:NNNo <token₁₂₃</code>
-------------------------------	---

These optimized functions absorb four arguments and expand the second, third and fourth as detailed by their argument specifier. The first argument of the function is then the next item on the input stream, followed by the expansion of the second argument, *etc.*

<code>\exp_args:NNNV</code> *
<code>\exp_args:Nccc</code> *
<code>\exp_args:NcNc</code> *
<code>\exp_args:NcNo</code> *
<code>\exp_args:Ncco</code> *

<code>\exp_args:NNcf</code>	★	<code>\exp_args:NNoo</code> $\langle token_1 \rangle$ $\langle token_2 \rangle$ $\{\langle token_3 \rangle\}$ $\{\langle tokens \rangle\}$
<code>\exp_args:NNno</code>	★	These functions absorb four arguments and expand the second, third and fourth as detailed by their argument specifier. The first argument of the function is then the next item on the input stream, followed by the expansion of the second argument, <i>etc.</i> These functions need slower processing.
<code>\exp_args:NNnV</code>	★	
<code>\exp_args:NNoo</code>	★	
<code>\exp_args:NNVV</code>	★	
<code>\exp_args:Ncno</code>	★	
<code>\exp_args:NcnV</code>	★	
<code>\exp_args:Ncoo</code>	★	
<code>\exp_args:NcVV</code>	★	
<code>\exp_args:Nnnc</code>	★	
<code>\exp_args:Nnno</code>	★	
<code>\exp_args:Nnnf</code>	★	
<code>\exp_args:Nnff</code>	★	
<code>\exp_args:Nooo</code>	★	
<code>\exp_args:Noof</code>	★	
<code>\exp_args:Nffo</code>	★	

<code>\exp_args:NNNx</code>		<code>\exp_args:NNnx</code> $\langle token_1 \rangle$ $\langle token_2 \rangle$ $\{\langle tokens_1 \rangle\}$ $\{\langle tokens_2 \rangle\}$
<code>\exp_args:NNnx</code>		These functions absorb four arguments and expand the second, third and fourth as detailed by their argument specifier. The first argument of the function is then the next item on the input stream, followed by the expansion of the second argument, <i>etc.</i>
<code>\exp_args:NNox</code>		
<code>\exp_args:Nccx</code>		
<code>\exp_args:Ncnx</code>		
<code>\exp_args:NNnx</code>		
<code>\exp_args:Nnox</code>		
<code>\exp_args:Noox</code>		

New: 2015-08-12

7 Unbraced expansion

<code>\exp_last_unbraced:No</code>	★	<code>\exp_last_unbraced:Nno</code> $\langle token \rangle$ $\{\langle tokens_1 \rangle\}$ $\{\langle tokens_2 \rangle\}$
<code>\exp_last_unbraced:(NV Nv Nf)</code>	★	
<code>\exp_last_unbraced:NNo</code>	★	
<code>\exp_last_unbraced:(NNV Nco NcV)</code>	★	
<code>\exp_last_unbraced:Nno</code>	★	
<code>\exp_last_unbraced:(Noo Nfo)</code>	★	
<code>\exp_last_unbraced:NNNo</code>	★	
<code>\exp_last_unbraced:NNNV</code>	★	
<code>\exp_last_unbraced:NnNo</code>	★	
<code>\exp_last_unbraced:NNNNo</code>	★	

Updated: 2012-02-12

These functions absorb the number of arguments given by their specification, carry out the expansion indicated and leave the results in the input stream, with the last argument not surrounded by the usual braces. Of these, the `:Nno`, `:Noo`, `:Nfo` and `:NnNo` variants need slower processing.

T_EXhackers note: As an optimization, the last argument is unbraced by some of those functions before expansion. This can cause problems if the argument is empty: for instance, `\exp_last_unbraced:Nf \foo_bar:w { } \q_stop` leads to an infinite loop, as the quark is `f`-expanded.

`\exp_last_unbraced:Nx` `\exp_last_unbraced:Nx <function> {\tokens}`

This function fully expands the `<tokens>` and leaves the result in the input stream after reinsertion of the `<function>`. This function is not expandable.

`\exp_last_two_unbraced:Noo` ★ `\exp_last_two_unbraced:Noo <token> {\tokens1} {\tokens2}`

This function absorbs three arguments and expands the second and third once. The first argument of the function is then the next item on the input stream, followed by the expansion of the second and third arguments, which are not wrapped in braces. This function needs special (slower) processing.

`\exp_after:wN` ★ `\exp_after:wN <token12`

Carries out a single expansion of `<token2 (which may consume arguments) prior to the expansion of <token1. If <token2 has no expansion (for example, if it is a character) then it is left unchanged. It is important to notice that <token1 may be any single token, including group-opening and -closing tokens ({ or } assuming normal \TeX category codes). Unless specifically required this should be avoided: expansion should be carried out using an appropriate argument specifier variant or the appropriate \exp_arg:N function.`

\TeX hackers note: This is the \TeX primitive `\expandafter` renamed.

8 Preventing expansion

Despite the fact that the following functions are all about preventing expansion, they're designed to be used in an expandable context and hence are all marked as being 'expandable' since they themselves disappear after the expansion has completed.

`\exp_not:N` ★ `\exp_not:N <token>`

Prevents expansion of the `<token>` in a context where it would otherwise be expanded, for example an `x`-type argument or the first token in an `o` or `f` argument.

\TeX hackers note: This is the \TeX `\noexpand` primitive. It only prevents expansion. At the beginning of an `f`-type argument, a space `<token>` is removed despite `\exp_not:N`. In an `x`-expanding definition (`\cs_new:Npx`) a macro parameter `<token>` (normally `#`) denotes an argument despite `\exp_not:N` (see `\exp_not:n`).

`\exp_not:c` ★ `\exp_not:c {\tokens}`

Expands the `<tokens>` until only characters remain, and then converts this into a control sequence. (An internal error occurs if non-characters remain, as the conversion is not possible.) Further expansion of this control sequence is then inhibited using `\exp_not:N`.

<code>\exp_not:n</code>	★	<code>\exp_not:n {⟨tokens⟩}</code>
-------------------------	---	------------------------------------

Prevents expansion of the $\langle tokens \rangle$ in an x -type argument. In other cases (input stream or o or f arguments) the $\langle tokens \rangle$ continue being expanded.

T_EXhackers note: This is the ε -T_EX `\unexpanded` primitive. Hence its argument *must* be surrounded by braces. In an x -expanding definition (`\cs_new:Npx`), `\exp_not:n {#}` inserts a macro parameter character in the replacement text.

<code>\exp_not:o</code>	★	<code>\exp_not:o {⟨tokens⟩}</code>
-------------------------	---	------------------------------------

Expands the $\langle tokens \rangle$ once, then prevents any further expansion in x -type arguments using `\exp_not:n`.

<code>\exp_not:V</code>	★	<code>\exp_not:V ⟨variable⟩</code>
-------------------------	---	------------------------------------

Recovers the content of the $\langle variable \rangle$, then prevents expansion of this material in x -type arguments using `\exp_not:n`.

<code>\exp_not:v</code>	★	<code>\exp_not:v {⟨tokens⟩}</code>
-------------------------	---	------------------------------------

Expands the $\langle tokens \rangle$ until only characters remains, and then converts this into a control sequence which should be a $\langle variable \rangle$ name. (An internal error occurs if non-characters remain, as the conversion is not possible.) The content of the $\langle variable \rangle$ is recovered, and further expansion in x -type arguments is prevented using `\exp_not:n`.

<code>\exp_not:f</code>	★	<code>\exp_not:f {⟨tokens⟩}</code>
-------------------------	---	------------------------------------

Expands $\langle tokens \rangle$ fully until the first unexpandable token is found (if it is a space it is removed). Expansion then stops, and the result of the expansion (including any tokens which were not expanded) is protected from further expansion in x -type arguments using `\exp_not:n`.

<code>\exp_stop_f:</code>	★	<code>\foo_bar:f { ⟨tokens⟩ \exp_stop_f: ⟨more tokens⟩ }</code>
---------------------------	---	---

Updated: 2011-06-03

This function terminates an f -type expansion. Thus if a function `\foo_bar:f` starts an f -type expansion and all of $\langle tokens \rangle$ are expandable `\exp_stop_f:` terminates the expansion of tokens even if $\langle more tokens \rangle$ are also expandable. The function itself is an implicit space token. Inside an x -type expansion, it retains its form, but when typeset it produces the underlying space (\sqcup).

9 Controlled expansion

The `expl3` language makes all efforts to hide the complexity of T_EX expansion from the programmer by providing concepts that evaluate/expand arguments of functions prior to calling the “base” functions. Thus, instead of using many `\expandafter` calls and other trickery it is usually a matter of choosing the right variant of a function to achieve a desired result.

Of course, deep down T_EX is using expansion as always and there are cases where a programmer needs to control that expansion directly; typical situations are basic data manipulation tools. This section documents the functions for that level. These commands are used throughout the kernel code, but we hope that outside the kernel there will be

little need to resort to them. Instead the argument manipulation methods document above should usually be sufficient.

While `\exp_after:wN` expands one token (out of order) it is sometimes necessary to expand several tokens in one go. The next set of commands provide this functionality. Be aware that it is absolutely required that the programmer has full control over the tokens to be expanded, i.e., it is not possible to use these functions to expand unknown input as part of *expandable-tokens* as that will break badly if unexpandable tokens are encountered in that place!

<code>\exp:w</code>	★	<code>\exp:w <expandable-tokens> \exp_end:</code>
<code>\exp_end:</code>	★	Expands <i><expandable-tokens></i> until reaching <code>\exp_end:</code> at which point expansion stops.
New: 2015-08-23		The full expansion of <i><expandable-tokens></i> has to be empty. If any token in <i><expandable-tokens></i> or any token generated by expanding the tokens therein is not expandable the expansion will end prematurely and as a result <code>\exp_end:</code> will be misinterpreted later on. ²
		In typical use cases the <code>\exp_end:</code> is hidden somewhere in the replacement text of <i><expandable-tokens></i> rather than being on the same expansion level than <code>\exp:w</code> , e.g., you may see code such as

```
\exp:w \@@_case:NnTF #1 {#2} { } { }
```

where somewhere during the expansion of `\@@_case:NnTF` the `\exp_end:` gets generated.

²Due to the implementation you might get the character in position 0 in the current font (typically “”) in the output without any error message!

<code>\exp:w</code>	★
<code>\exp_end_continue_f:w</code>	★
New: 2015-08-23	

`\exp:w` $\langle expandable-tokens \rangle$ `\exp_end_continue_f:w` $\langle further-tokens \rangle$

Expands $\langle expandable-tokens \rangle$ until reaching `\exp_end_continue_f:w` at which point expansion continues as an f-type expansion expanding $\langle further-tokens \rangle$ until an unexpandable token is encountered (or the f-type expansion is explicitly terminated by `\exp_stop_f:`). As with all f-type expansions a space ending the expansion gets removed.

The full expansion of $\langle expandable-tokens \rangle$ has to be empty. If any token in $\langle expandable-tokens \rangle$ or any token generated by expanding the tokens therein is not expandable the expansion will end prematurely and as a result `\exp_end_continue_f:w` will be misinterpreted later on.³

In typical use cases $\langle expandable-tokens \rangle$ contains no tokens at all, e.g., you will see code such as

```
\exp_after:wN { \exp:w \exp_end_continue_f:w #2 }
```

where the `\exp_after:wN` triggers an f-expansion of the tokens in #2. For technical reasons this has to happen using two tokens (if they would be hidden inside another command `\exp_after:wN` would only expand the command but not trigger any additional f-expansion).

You might wonder why there are two different approaches available, after all the effect of

```
\exp:w \langle expandable-tokens \rangle \exp_end:
```

can be alternatively achieved through an f-type expansion by using `\exp_stop_f:`, i.e.

```
\exp:w \exp_end_continue_f:w \langle expandable-tokens \rangle \exp_stop_f:
```

The reason is simply that the first approach is slightly faster (one less token to parse and less expansion internally) so in places where such performance really matters and where we want to explicitly stop the expansion at a defined point the first form is preferable.

<code>\exp:w</code>	★
<code>\exp_end_continue_f:nw</code>	★
New: 2015-08-23	

`\exp:w` $\langle expandable-tokens \rangle$ `\exp_end_continue_f:nw` $\langle further-tokens \rangle$

The difference to `\exp_end_continue_f:w` is that we first we pick up an argument which is then returned to the input stream. If $\langle further-tokens \rangle$ starts with space tokens then these space tokens are removed while searching for the argument. If it starts with a brace group then the braces are removed. Thus such spaces or braces will not terminate the f-type expansion.

10 Internal functions and variables

`\l__exp_internal_tl`

The `\exp_` module has its private variable to temporarily store the result of x-type argument expansion. This is done to avoid interference with other functions using temporary variables.

³In this particular case you may get a character into the output as well as an error message.

```

\::n \cs_set:Npn \exp_args:Ncof { \::c \::o \::f \::: }
\::N
\::p Internal forms for the base expansion types. These names do not conform to the general
\::c LATEX3 approach as this makes them more readily visible in the log and so forth.
\::o
\::f
\::x
\::v
\::V
\:::

```

Part VI

The l3tl package

Token lists

T_EX works with tokens, and L^AT_EX3 therefore provides a number of functions to deal with lists of tokens. Token lists may be present directly in the argument to a function:

```
\foo:n { a collection of \tokens }
```

or may be stored in a so-called “token list variable”, which have the suffix `tl`: a token list variable can also be used as the argument to a function, for example

```
\foo:N \l_some_tl
```

In both cases, functions are available to test and manipulate the lists of tokens, and these have the module prefix `tl`. In many cases, functions which can be applied to token list variables are paired with similar functions for application to explicit lists of tokens: the two “views” of a token list are therefore collected together here.

A token list (explicit, or stored in a variable) can be seen either as a list of “items”, or a list of “tokens”. An item is whatever `\use:n` would grab as its argument: a single non-space token or a brace group, with optional leading explicit space characters (each item is thus itself a token list). A token is either a normal `N` argument, or `␣`, `{`, or `}` (assuming normal T_EX category codes). Thus for example

```
{ Hello } ~ world
```

contains six items (Hello, w, o, r, l and d), but thirteen tokens (`{`, H, e, l, l, o, `}`, `␣`, w, o, r, l and d). Functions which act on items are often faster than their analogue acting directly on tokens.

1 Creating and initialising token list variables

<code>\tl_new:N</code>	<code>\tl_new:N <tl var></code>
<code>\tl_new:c</code>	

Creates a new `<tl var>` or raises an error if the name is already taken. The declaration is global. The `<tl var>` is initially empty.

<code>\tl_const:Nn</code>	<code>\tl_const:Nn <tl var> {<token list>}</code>
<code>\tl_const:(Nx cn cx)</code>	

Creates a new constant `<tl var>` or raises an error if the name is already taken. The value of the `<tl var>` is set globally to the `<token list>`.

<code>\tl_clear:N</code>	<code>\tl_clear:N <tl var></code>
<code>\tl_clear:c</code>	
<code>\tl_gclear:N</code>	
<code>\tl_gclear:c</code>	

Clears all entries from the `<tl var>`.

<hr/>	
<code>\tl_clear_new:N</code>	<code>\tl_clear_new:N <tl var></code>
<code>\tl_clear_new:c</code>	
<code>\tl_gclear_new:N</code>	Ensures that the $\langle tl\ var\rangle$ exists globally by applying <code>\tl_new:N</code> if necessary, then applies
<code>\tl_gclear_new:c</code>	<code>\tl_(g)clear:N</code> to leave the $\langle tl\ var\rangle$ empty.
<hr/>	
<code>\tl_set_eq:NN</code>	<code>\tl_set_eq:NN <tl var_1> <tl var_2></code>
<code>\tl_set_eq:(cN Nc cc)</code>	Sets the content of $\langle tl\ var_1\rangle$ equal to that of $\langle tl\ var_2\rangle$.
<code>\tl_gset_eq:NN</code>	
<code>\tl_gset_eq:(cN Nc cc)</code>	
<hr/>	
<code>\tl_concat:NNN</code>	<code>\tl_concat:NNN <tl var_1> <tl var_2> <tl var_3></code>
<code>\tl_concat:ccc</code>	
<code>\tl_gconcat:NNN</code>	Concatenates the content of $\langle tl\ var_2\rangle$ and $\langle tl\ var_3\rangle$ together and saves the result in
<code>\tl_gconcat:ccc</code>	$\langle tl\ var_1\rangle$. The $\langle tl\ var_2\rangle$ is placed at the left side of the new token list.
<hr/>	
New: 2012-05-18	
<hr/>	
<code>\tl_if_exist_p:N *</code>	<code>\tl_if_exist_p:N <tl var></code>
<code>\tl_if_exist_p:c *</code>	<code>\tl_if_exist:NTF <tl var> {\true code} {\false code}</code>
<code>\tl_if_exist:NTF *</code>	
<code>\tl_if_exist:cTF *</code>	Tests whether the $\langle tl\ var\rangle$ is currently defined. This does not check that the $\langle tl\ var\rangle$
	really is a token list variable.
<hr/>	
New: 2012-03-03	

2 Adding data to token list variables

<hr/>	
<code>\tl_set:Nn</code>	<code>\tl_set:Nn <tl var> {\tokens}</code>
<code>\tl_set:(NV Nv No Nf Nx cn cV cv co cf cx)</code>	
<code>\tl_gset:Nn</code>	
<code>\tl_gset:(NV Nv No Nf Nx cn cV cv co cf cx)</code>	
<hr/>	
	Sets $\langle tl\ var\rangle$ to contain $\langle tokens\rangle$, removing any previous content from the variable.
<hr/>	
<code>\tl_put_left:Nn</code>	<code>\tl_put_left:Nn <tl var> {\tokens}</code>
<code>\tl_put_left:(NV No Nx cn cV co cx)</code>	
<code>\tl_gput_left:Nn</code>	
<code>\tl_gput_left:(NV No Nx cn cV co cx)</code>	
<hr/>	
	Appends $\langle tokens\rangle$ to the left side of the current content of $\langle tl\ var\rangle$.
<hr/>	
<code>\tl_put_right:Nn</code>	<code>\tl_put_right:Nn <tl var> {\tokens}</code>
<code>\tl_put_right:(NV No Nx cn cV co cx)</code>	
<code>\tl_gput_right:Nn</code>	
<code>\tl_gput_right:(NV No Nx cn cV co cx)</code>	
<hr/>	
	Appends $\langle tokens\rangle$ to the right side of the current content of $\langle tl\ var\rangle$.

3 Modifying token list variables

```
\tl_replace_once:Nnn
\tl_replace_once:cnn
\tl_greplace_once:Nnn
\tl_greplace_once:cnn
```

Updated: 2011-08-11

```
\tl_replace_once:Nnn <tl var> {{<old tokens>}} {{<new tokens>}}
```

Replaces the first (leftmost) occurrence of *<old tokens>* in the *<tl var>* with *<new tokens>*. *<Old tokens>* cannot contain `{`, `}` or `#` (more precisely, explicit character tokens with category code 1 (begin-group) or 2 (end-group), and tokens with category code 6).

```
\tl_replace_all:Nnn
\tl_replace_all:cnn
\tl_greplace_all:Nnn
\tl_greplace_all:cnn
```

Updated: 2011-08-11

```
\tl_replace_all:Nnn <tl var> {{<old tokens>}} {{<new tokens>}}
```

Replaces all occurrences of *<old tokens>* in the *<tl var>* with *<new tokens>*. *<Old tokens>* cannot contain `{`, `}` or `#` (more precisely, explicit character tokens with category code 1 (begin-group) or 2 (end-group), and tokens with category code 6). As this function operates from left to right, the pattern *<old tokens>* may remain after the replacement (see `\tl_remove_all:Nn` for an example).

```
\tl_remove_once:Nn
\tl_remove_once:cn
\tl_gremove_once:Nn
\tl_gremove_once:cn
```

Updated: 2011-08-11

```
\tl_remove_once:Nn <tl var> {{<tokens>}}
```

Removes the first (leftmost) occurrence of *<tokens>* from the *<tl var>*. *<Tokens>* cannot contain `{`, `}` or `#` (more precisely, explicit character tokens with category code 1 (begin-group) or 2 (end-group), and tokens with category code 6).

```
\tl_remove_all:Nn
\tl_remove_all:cn
\tl_gremove_all:Nn
\tl_gremove_all:cn
```

Updated: 2011-08-11

```
\tl_remove_all:Nn <tl var> {{<tokens>}}
```

Removes all occurrences of *<tokens>* from the *<tl var>*. *<Tokens>* cannot contain `{`, `}` or `#` (more precisely, explicit character tokens with category code 1 (begin-group) or 2 (end-group), and tokens with category code 6). As this function operates from left to right, the pattern *<tokens>* may remain after the removal, for instance,

```
\tl_set:Nn \l_tmpa_tl {abbccd} \tl_remove_all:Nn \l_tmpa_tl {bc}
```

results in `\l_tmpa_tl` containing `abcd`.

4 Reassigning token list category codes

These functions allow the rescanning of tokens: re-apply T_EX's tokenization process to apply category codes different from those in force when the tokens were absorbed. Whilst this functionality is supported, it is often preferable to find alternative approaches to achieving outcomes rather than rescanning tokens (for example construction of token lists token-by-token with intervening category code changes).

<code>\tl_set_rescan:Nnn</code>	<code>\tl_set_rescan:Nnn <tl var> {<setup>} {<tokens>}</code>
<code>\tl_set_rescan:(Nno Nnx cnn cno cnx)</code>	
<code>\tl_gset_rescan:Nnn</code>	
<code>\tl_gset_rescan:(Nno Nnx cnn cno cnx)</code>	

Updated: 2015-08-11

Sets `<tl var>` to contain `<tokens>`, applying the category code régime specified in the `<setup>` before carrying out the assignment. (Category codes applied to tokens not explicitly covered by the `<setup>` are those in force at the point of use of `\tl_set_rescan:Nnn`.) This allows the `<tl var>` to contain material with category codes other than those that apply when `<tokens>` are absorbed. The `<setup>` is run within a group and may contain any valid input, although only changes in category codes are relevant. See also `\tl_rescan:nn`.

TeXhackers note: The `<tokens>` are first turned into a string (using `\tl_to_str:n`). If the string contains one or more characters with character code `\newlinechar` (set equal to `\endlinechar` unless that is equal to 32, before the user `<setup>`), then it is split into lines at these characters, then read as if reading multiple lines from a file, ignoring spaces (catcode 10) at the beginning and spaces and tabs (character code 32 or 9) at the end of every line. Otherwise, spaces (and tabs) are retained at both ends of the single-line string, as if it appeared in the middle of a line read from a file. Only the case of a single line is supported in LuaTeX because of a bug in this engine.

<code>\tl_rescan:nn</code>	<code>\tl_rescan:nn {<setup>} {<tokens>}</code>
----------------------------	---

Updated: 2015-08-11

Rescans `<tokens>` applying the category code régime specified in the `<setup>`, and leaves the resulting tokens in the input stream. (Category codes applied to tokens not explicitly covered by the `<setup>` are those in force at the point of use of `\tl_rescan:nn`.) The `<setup>` is run within a group and may contain any valid input, although only changes in category codes are relevant. See also `\tl_set_rescan:Nnn`, which is more robust than using `\tl_set:Nn` in the `<tokens>` argument of `\tl_rescan:nn`.

TeXhackers note: The `<tokens>` are first turned into a string (using `\tl_to_str:n`). If the string contains one or more characters with character code `\newlinechar` (set equal to `\endlinechar` unless that is equal to 32, before the user `<setup>`), then it is split into lines at these characters, then read as if reading multiple lines from a file, ignoring spaces (catcode 10) at the beginning and spaces and tabs (character code 32 or 9) at the end of every line. Otherwise, spaces (and tabs) are retained at both ends of the single-line string, as if it appeared in the middle of a line read from a file. Only the case of a single line is supported in LuaTeX because of a bug in this engine.

5 Token list conditionals

<code>\tl_if_blank_p:n</code>	★	<code>\tl_if_blank_p:n {<token list>}</code>
<code>\tl_if_blank_p:(V o)</code>	★	<code>\tl_if_blank:nTF {<token list>} {<true code>} {<false code>}</code>
<code>\tl_if_blank:nTF</code>	★	
<code>\tl_if_blank:(V o)TF</code>	★	

Tests if the `<token list>` consists only of blank spaces (*i.e.* contains no item). The test is **true** if `<token list>` is zero or more explicit space characters (explicit tokens with character code 32 and category code 10), and is **false** otherwise.

<code>\tl_if_empty_p:N</code>	★	<code>\tl_if_empty_p:N <tl var></code>
<code>\tl_if_empty_p:c</code>	★	<code>\tl_if_empty:NNTF <tl var> {<true code>} {<false code>}</code>
<code>\tl_if_empty:nTF</code>	★	Tests if the <i><token list variable></i> is entirely empty (<i>i.e.</i> contains no tokens at all).
<code>\tl_if_empty:cTF</code>	★	

<code>\tl_if_empty_p:n</code>	★	<code>\tl_if_empty_p:n {<token list>}</code>
<code>\tl_if_empty_p:(V o)</code>	★	<code>\tl_if_empty:nNTF {<token list>} {<true code>} {<false code>}</code>
<code>\tl_if_empty:nTF</code>	★	Tests if the <i><token list></i> is entirely empty (<i>i.e.</i> contains no tokens at all).
<code>\tl_if_empty:(V o)TF</code>	★	

New: 2012-05-24
Updated: 2012-06-05

<code>\tl_if_eq_p:NN</code>	★	<code>\tl_if_eq_p:NN <tl var₁> <tl var₂></code>
<code>\tl_if_eq_p:(Nc cN cc)</code>	★	<code>\tl_if_eq:NNTF <tl var₁> <tl var₂> {<true code>} {<false code>}</code>
<code>\tl_if_eq:NNTF</code>	★	Compares the content of two <i><token list variables></i> and is logically true if the two contain the same list of tokens (<i>i.e.</i> identical in both the list of characters they contain and the category codes of those characters). Thus for example
<code>\tl_if_eq:(Nc cN cc)TF</code>	★	

```

\tl_set:Nn \l_tmpa_tl { abc }
\tl_set:Nx \l_tmpb_tl { \tl_to_str:n { abc } }
\tl_if_eq:NNTF \l_tmpa_tl \l_tmpb_tl { true } { false }

```

yields **false**.

<code>\tl_if_eq:nnTF</code>	★	<code>\tl_if_eq:nnTF {<token list₁>} {<token list₂>} {<true code>} {<false code>}</code>
-----------------------------	---	--

Tests if *<token list₁>* and *<token list₂>* contain the same list of tokens, both in respect of character codes and category codes.

<code>\tl_if_in:NnTF</code>	★	<code>\tl_if_in:NnTF <tl var> {<token list>} {<true code>} {<false code>}</code>
<code>\tl_if_in:cnTF</code>	★	Tests if the <i><token list></i> is found in the content of the <i><tl var></i> . The <i><token list></i> cannot contain the tokens <code>{</code> , <code>}</code> or <code>#</code> (more precisely, explicit character tokens with category code 1 (begin-group) or 2 (end-group), and tokens with category code 6).

<code>\tl_if_in:nnTF</code>	★	<code>\tl_if_in:nnTF {<token list₁>} {<token list₂>} {<true code>} {<false code>}</code>
<code>\tl_if_in:(Vn on no)TF</code>	★	Tests if <i><token list₂></i> is found inside <i><token list₁></i> . The <i><token list₂></i> cannot contain the tokens <code>{</code> , <code>}</code> or <code>#</code> (more precisely, explicit character tokens with category code 1 (begin-group) or 2 (end-group), and tokens with category code 6).

<code>\tl_if_noval_p:n</code>	★	<code>\tl_if_noval_p:n {<token list>}</code>
<code>\tl_if_noval_p:nTF</code>	★	<code>\tl_if_noval_p:nTF {<token list>} {<true code>} {<false code>}</code>

New: 2017-11-14

Tests if the *<token list>* is exactly equal to the special `\c_noval_p_tl` marker. This function is intended to allow construction of flexible document interface structures in which missing optional arguments are detected.

<code>\tl_if_single_p:N</code> ★	<code>\tl_if_single_p:N <tl var></code>
<code>\tl_if_single_p:c</code> ★	<code>\tl_if_single:NNTF <tl var> {\true code} {\false code}</code>
<code>\tl_if_single:NTF</code> ★	Tests if the content of the <i><tl var></i> consists of a single item, <i>i.e.</i> is a single normal token (neither an explicit space character nor a begin-group character) or a single brace group, surrounded by optional spaces on both sides. In other words, such a token list has token count 1 according to <code>\tl_count:N</code> .
<code>\tl_if_single:cTF</code> ★	
Updated: 2011-08-13	

<code>\tl_if_single_p:n</code> ★	<code>\tl_if_single_p:n {\token list}</code>
<code>\tl_if_single:nTF</code> ★	<code>\tl_if_single:nNTF {\token list} {\true code} {\false code}</code>
Updated: 2011-08-13	
Tests if the <i><token list></i> has exactly one item, <i>i.e.</i> is a single normal token (neither an explicit space character nor a begin-group character) or a single brace group, surrounded by optional spaces on both sides. In other words, such a token list has token count 1 according to <code>\tl_count:n</code> .	

<code>\tl_case:Nn</code> ★	<code>\tl_case:NnNTF <test token list variable></code>
<code>\tl_case:cn</code> ★	{
<code>\tl_case:NnTF</code> ★	<i><token list variable case₁></i> {\code case ₁ }
<code>\tl_case:cnTF</code> ★	<i><token list variable case₂></i> {\code case ₂ }
...	
	<i><token list variable case_n></i> {\code case _n }
	}
	{\true code}
	{\false code}
New: 2013-07-24	

This function compares the *<test token list variable>* in turn with each of the *<token list variable cases>*. If the two are equal (as described for `\tl_if_eq:NNTF`) then the associated *<code>* is left in the input stream and other cases are discarded. If any of the cases are matched, the *<true code>* is also inserted into the input stream (after the code for the appropriate case), while if none match then the *<false code>* is inserted. The function `\tl_case:Nn`, which does nothing if there is no match, is also available.

6 Mapping to token lists

<code>\tl_map_function:NN</code> ☆	<code>\tl_map_function:NN <tl var> <function></code>
<code>\tl_map_function:cN</code> ☆	Applies <i><function></i> to every <i><item></i> in the <i><tl var></i> . The <i><function></i> receives one argument for each iteration. This may be a number of tokens if the <i><item></i> was stored within braces. Hence the <i><function></i> should anticipate receiving n-type arguments. See also <code>\tl_map_function:nN</code> .
Updated: 2012-06-29	

<code>\tl_map_function:nN</code> ☆	<code>\tl_map_function:nN {\token list} <function></code>
Updated: 2012-06-29	
Applies <i><function></i> to every <i><item></i> in the <i><token list></i> , The <i><function></i> receives one argument for each iteration. This may be a number of tokens if the <i><item></i> was stored within braces. Hence the <i><function></i> should anticipate receiving n-type arguments. See also <code>\tl_map_function:NN</code> .	

<code>\tl_map_inline:Nn</code>	<code>\tl_map_inline:Nn <tl var> {\inline function}</code>
<code>\tl_map_inline:cn</code>	Applies the <i><inline function></i> to every <i><item></i> stored within the <i><tl var></i> . The <i><inline function></i> should consist of code which receives the <i><item></i> as #1. See also <code>\tl_map_function:NN</code> .
Updated: 2012-06-29	

<hr/> <code>\tl_map_inline:nn</code> <hr/> Updated: 2012-06-29 <hr/>	<code>\tl_map_inline:nn {<token list>} {<inline function>}</code> Applies the <i><inline function></i> to every <i><item></i> stored within the <i><token list></i> . The <i><inline function></i> should consist of code which receives the <i><item></i> as #1. See also <code>\tl_map_function:nn</code> .
<hr/> <code>\tl_map_variable:NNn</code> <code>\tl_map_variable:cNn</code> <hr/> Updated: 2012-06-29 <hr/>	<code>\tl_map_variable:NNn <tl var> <variable> {<code>}</code> Stores each <i><item></i> of the <i><tl var></i> in turn in the (token list) <i><variable></i> and applies the <i><code></i> . The <i><code></i> will usually make use of the <i><variable></i> , but this is not enforced. The assignments to the <i><variable></i> are local. See also <code>\tl_map_inline:Nn</code> .
<hr/> <code>\tl_map_variable:nNn</code> <hr/> Updated: 2012-06-29 <hr/>	<code>\tl_map_variable:nNn {<token list>} <variable> {<code>}</code> Stores each <i><item></i> of the <i><token list></i> in turn in the (token list) <i><variable></i> and applies the <i><code></i> . The <i><code></i> will usually make use of the <i><variable></i> , but this is not enforced. The assignments to the <i><variable></i> are local. See also <code>\tl_map_inline:nn</code> .
<hr/> <code>\tl_map_break: ☆</code> <hr/> Updated: 2012-06-29 <hr/>	<code>\tl_map_break:</code> Used to terminate a <code>\tl_map...</code> function before all entries in the <i><token list variable></i> have been processed. This normally takes place within a conditional statement, for example <pre> \tl_map_inline:Nn \l_my_tl { \str_if_eq:nnT { #1 } { bingo } { \tl_map_break: } % Do something useful } </pre> <p>See also <code>\tl_map_break:n</code>. Use outside of a <code>\tl_map...</code> scenario leads to low level TeX errors.</p> <p>TeXhackers note: When the mapping is broken, additional tokens may be inserted before the <i><tokens></i> are inserted into the input stream. This depends on the design of the mapping function.</p>

`\tl_map_break:n` ★

Updated: 2012-06-29

`\tl_map_break:n` { $\langle code \rangle$ }

Used to terminate a `\tl_map...` function before all entries in the $\langle token list variable \rangle$ have been processed, inserting the $\langle code \rangle$ after the mapping has ended. This normally takes place within a conditional statement, for example

```
\tl_map_inline:Nn \l_my_tl
{
  \str_if_eq:nnT { #1 } { bingo }
  { \tl_map_break:n { <code> } }
  % Do something useful
}
```

Use outside of a `\tl_map...` scenario leads to low level TeX errors.

TeXhackers note: When the mapping is broken, additional tokens may be inserted before the $\langle code \rangle$ is inserted into the input stream. This depends on the design of the mapping function.

7 Using token lists

`\tl_to_str:n` ★

`\tl_to_str:V` ★

`\tl_to_str:n` { $\langle token list \rangle$ }

Converts the $\langle token list \rangle$ to a $\langle string \rangle$, leaving the resulting character tokens in the input stream. A $\langle string \rangle$ is a series of tokens with category code 12 (other) with the exception of spaces, which retain category code 10 (space).

TeXhackers note: Converting a $\langle token list \rangle$ to a $\langle string \rangle$ yields a concatenation of the string representations of every token in the $\langle token list \rangle$. The string representation of a control sequence is

- an escape character, whose character code is given by the internal parameter `\escapechar`, absent if the `\escapechar` is negative or greater than the largest character code;
- the control sequence name, as defined by `\cs_to_str:N`;
- a space, unless the control sequence name is a single character whose category at the time of expansion of `\tl_to_str:n` is not “letter”.

The string representation of an explicit character token is that character, doubled in the case of (explicit) macro parameter characters (normally `#`). In particular, the string representation of a token list may depend on the category codes in effect when it is evaluated, and the value of the `\escapechar`: for instance `\tl_to_str:n {\a}` normally produces the three character “backslash”, “lower-case a”, “space”, but it may also produce a single “lower-case a” if the escape character is negative and `a` is currently not a letter.

`\tl_to_str:N` ★

`\tl_to_str:c` ★

`\tl_to_str:N` $\langle tl var \rangle$

Converts the content of the $\langle tl var \rangle$ into a series of characters with category code 12 (other) with the exception of spaces, which retain category code 10 (space). This $\langle string \rangle$ is then left in the input stream. For low-level details, see the notes given for `\tl_to_str:n`.

<code>\tl_use:N</code>	★	<code>\tl_use:N <tl var></code>
------------------------	---	---------------------------------------

<code>\tl_use:c</code>	★	
------------------------	---	--

Recovers the content of a $\langle tl\ var \rangle$ and places it directly in the input stream. An error is raised if the variable does not exist or if it is invalid. Note that it is possible to use a $\langle tl\ var \rangle$ directly without an accessor function.

8 Working with the content of token lists

<code>\tl_count:n</code>	★	<code>\tl_count:n {(tokens)}</code>
--------------------------	---	-------------------------------------

<code>\tl_count:(V o)</code>	★	
------------------------------	---	--

New: 2012-05-13

Counts the number of $\langle items \rangle$ in $\langle tokens \rangle$ and leaves this information in the input stream. Unbraced tokens count as one element as do each token group $\{...\}$. This process ignores any unprotected spaces within $\langle tokens \rangle$. See also `\tl_count:N`. This function requires three expansions, giving an $\langle integer\ denotation \rangle$.

<code>\tl_count:N</code>	★	<code>\tl_count:N <tl var></code>
--------------------------	---	---

<code>\tl_count:c</code>	★	
--------------------------	---	--

New: 2012-05-13

Counts the number of token groups in the $\langle tl\ var \rangle$ and leaves this information in the input stream. Unbraced tokens count as one element as do each token group $\{...\}$. This process ignores any unprotected spaces within the $\langle tl\ var \rangle$. See also `\tl_count:n`. This function requires three expansions, giving an $\langle integer\ denotation \rangle$.

<code>\tl_reverse:n</code>	★	<code>\tl_reverse:n {(token list)}</code>
----------------------------	---	---

<code>\tl_reverse:(V o)</code>	★	
--------------------------------	---	--

Updated: 2012-01-08

Reverses the order of the $\langle items \rangle$ in the $\langle token\ list \rangle$, so that $\langle item_1 \rangle \langle item_2 \rangle \langle item_3 \rangle \dots \langle item_n \rangle$ becomes $\langle item_n \rangle \dots \langle item_3 \rangle \langle item_2 \rangle \langle item_1 \rangle$. This process preserves unprotected space within the $\langle token\ list \rangle$. Tokens are not reversed within braced token groups, which keep their outer set of braces. In situations where performance is important, consider `\tl_reverse_items:n`. See also `\tl_reverse:N`.

TeXhackers note: The result is returned within `\unexpanded`, which means that the token list does not expand further when appearing in an `x`-type argument expansion.

<code>\tl_reverse:N</code>		<code>\tl_reverse:N <tl var></code>
----------------------------	--	---

<code>\tl_reverse:c</code>		
----------------------------	--	--

<code>\tl_greverse:N</code>		
-----------------------------	--	--

<code>\tl_greverse:c</code>		
-----------------------------	--	--

Updated: 2012-01-08

Reverses the order of the $\langle items \rangle$ stored in $\langle tl\ var \rangle$, so that $\langle item_1 \rangle \langle item_2 \rangle \langle item_3 \rangle \dots \langle item_n \rangle$ becomes $\langle item_n \rangle \dots \langle item_3 \rangle \langle item_2 \rangle \langle item_1 \rangle$. This process preserves unprotected spaces within the $\langle token\ list\ variable \rangle$. Braced token groups are copied without reversing the order of tokens, but keep the outer set of braces. See also `\tl_reverse:n`, and, for improved performance, `\tl_reverse_items:n`.

<code>\tl_reverse_items:n</code>	★	<code>\tl_reverse_items:n {(token list)}</code>
----------------------------------	---	---

New: 2012-01-08

Reverses the order of the $\langle items \rangle$ stored in $\langle tl\ var \rangle$, so that $\{\langle item_1 \rangle\} \{\langle item_2 \rangle\} \{\langle item_3 \rangle\} \dots \{\langle item_n \rangle\}$ becomes $\{\langle item_n \rangle\} \dots \{\langle item_3 \rangle\} \{\langle item_2 \rangle\} \{\langle item_1 \rangle\}$. This process removes any unprotected space within the $\langle token\ list \rangle$. Braced token groups are copied without reversing the order of tokens, and keep the outer set of braces. Items which are initially not braced are copied with braces in the result. In cases where preserving spaces is important, consider the slower function `\tl_reverse:n`.

TeXhackers note: The result is returned within `\unexpanded`, which means that the token list does not expand further when appearing in an `x`-type argument expansion.

<code>\tl_trim_spaces:n</code> ★	<code>\tl_trim_spaces:n {⟨token list⟩}</code>
New: 2011-07-09 Updated: 2012-06-25	Removes any leading and trailing explicit space characters (explicit tokens with character code 32 and category code 10) from the <i>⟨token list⟩</i> and leaves the result in the input stream.

TeXhackers note: The result is returned within `\unexpanded`, which means that the token list does not expand further when appearing in an *x*-type argument expansion.

<code>\tl_trim_spaces:N</code> <code>\tl_trim_spaces:c</code> <code>\tl_gtrim_spaces:N</code> <code>\tl_gtrim_spaces:c</code>	<code>\tl_trim_spaces:N ⟨tl var⟩</code>
New: 2011-07-09	Removes any leading and trailing explicit space characters (explicit tokens with character code 32 and category code 10) from the content of the <i>⟨tl var⟩</i> . Note that this therefore <i>resets</i> the content of the variable.

<code>\tl_sort:Nn</code> <code>\tl_sort:cn</code> <code>\tl_gsort:Nn</code> <code>\tl_gsort:cn</code>	<code>\tl_sort:Nn ⟨tl var⟩ {⟨comparison code⟩}</code>
New: 2017-02-06	Sorts the items in the <i>⟨tl var⟩</i> according to the <i>⟨comparison code⟩</i> , and assigns the result to <i>⟨tl var⟩</i> . The details of sorting comparison are described in Section 1.

<code>\tl_sort:nN</code> ★	<code>\tl_sort:nN {⟨token list⟩} ⟨conditional⟩</code>
New: 2017-02-06	Sorts the items in the <i>⟨token list⟩</i> , using the <i>⟨conditional⟩</i> to compare items, and leaves the result in the input stream. The <i>⟨conditional⟩</i> should have signature <code>:nnTF</code> , and return true if the two items being compared should be left in the same order, and false if the items should be swapped. The details of sorting comparison are described in Section 1.

TeXhackers note: The result is returned within `\exp_not:n`, which means that the token list does not expand further when appearing in an *x*-type argument expansion.

9 The first token from a token list

Functions which deal with either only the very first item (balanced text or single normal token) in a token list, or the remaining tokens.

<code>\tl_head:N</code>	★	<code>\tl_head:n {⟨token list⟩}</code>
<code>\tl_head:n</code>	★	
<code>\tl_head:(V v f)</code>	★	Leaves in the input stream the first <i>⟨item⟩</i> in the <i>⟨token list⟩</i> , discarding the rest of the <i>⟨token list⟩</i> . All leading explicit space characters (explicit tokens with character code 32 and category code 10) are discarded; for example
Updated: 2012-09-09		

`\tl_head:n { abc }`

and

`\tl_head:n { ~ abc }`

both leave `a` in the input stream. If the “head” is a brace group, rather than a single token, the braces are removed, and so

`\tl_head:n { ~ { ~ ab } c }`

yields `▯ab`. A blank *⟨token list⟩* (see `\tl_if_blank:nTF`) results in `\tl_head:n` leaving nothing in the input stream.

TeXhackers note: The result is returned within `\exp_not:n`, which means that the token list does not expand further when appearing in an *x*-type argument expansion.

<code>\tl_head:w</code>	★	<code>\tl_head:w ⟨token list⟩ { } \q_stop</code>
-------------------------	---	--

Leaves in the input stream the first *⟨item⟩* in the *⟨token list⟩*, discarding the rest of the *⟨token list⟩*. All leading explicit space characters (explicit tokens with character code 32 and category code 10) are discarded. A blank *⟨token list⟩* (which consists only of space characters) results in a low-level TeX error, which may be avoided by the inclusion of an empty group in the input (as shown), without the need for an explicit test. Alternatively, `\tl_if_blank:nF` may be used to avoid using the function with a “blank” argument. This function requires only a single expansion, and thus is suitable for use within an *o*-type expansion. In general, `\tl_head:n` should be preferred if the number of expansions is not critical.

<code>\tl_tail:N</code>	★	<code>\tl_tail:n {⟨token list⟩}</code>
<code>\tl_tail:n</code>	★	
<code>\tl_tail:(V v f)</code>	★	Discards all leading explicit space characters (explicit tokens with character code 32 and category code 10) and the first <i>⟨item⟩</i> in the <i>⟨token list⟩</i> , and leaves the remaining tokens in the input stream. Thus for example
Updated: 2012-09-01		

`\tl_tail:n { a ~ {bc} d }`

and

`\tl_tail:n { ~ a ~ {bc} d }`

both leave `▯{bc}d` in the input stream. A blank *⟨token list⟩* (see `\tl_if_blank:nTF`) results in `\tl_tail:n` leaving nothing in the input stream.

TeXhackers note: The result is returned within `\exp_not:n`, which means that the token list does not expand further when appearing in an *x*-type argument expansion.

<code>\tl_if_head_eq_catcode_p:nN</code>	★	<code>\tl_if_head_eq_catcode_p:nN {<token list>} <test token></code>
<code>\tl_if_head_eq_catcode:nNTF</code>	★	<code>\tl_if_head_eq_catcode:nNTF {<token list>} <test token></code>
		<code>{<true code>} {<false code>}</code>

Updated: 2012-07-09

Tests if the first *<token>* in the *<token list>* has the same category code as the *<test token>*.
In the case where the *<token list>* is empty, the test is always **false**.

<code>\tl_if_head_eq_charcode_p:nN</code>	★	<code>\tl_if_head_eq_charcode_p:nN {<token list>} <test token></code>
<code>\tl_if_head_eq_charcode_p:fN</code>	★	<code>\tl_if_head_eq_charcode:nNTF {<token list>} <test token></code>
<code>\tl_if_head_eq_charcode:nNTF</code>	★	<code>{<true code>} {<false code>}</code>
<code>\tl_if_head_eq_charcode:fNTF</code>	★	

Updated: 2012-07-09

Tests if the first *<token>* in the *<token list>* has the same character code as the *<test token>*.
In the case where the *<token list>* is empty, the test is always **false**.

<code>\tl_if_head_eq_meaning_p:nN</code>	★	<code>\tl_if_head_eq_meaning_p:nN {<token list>} <test token></code>
<code>\tl_if_head_eq_meaning:nNTF</code>	★	<code>\tl_if_head_eq_meaning:nNTF {<token list>} <test token></code>
		<code>{<true code>} {<false code>}</code>

Updated: 2012-07-09

Tests if the first *<token>* in the *<token list>* has the same meaning as the *<test token>*. In the case where *<token list>* is empty, the test is always **false**.

<code>\tl_if_head_is_group_p:n</code>	★	<code>\tl_if_head_is_group_p:n {<token list>}</code>
<code>\tl_if_head_is_group:nTF</code>	★	<code>\tl_if_head_is_group:nTF {<token list>} {<true code>} {<false code>}</code>

New: 2012-07-08

Tests if the first *<token>* in the *<token list>* is an explicit begin-group character (with category code 1 and any character code), in other words, if the *<token list>* starts with a brace group. In particular, the test is **false** if the *<token list>* starts with an implicit token such as `\c_group_begin_token`, or if it is empty. This function is useful to implement actions on token lists on a token by token basis.

<code>\tl_if_head_is_N_type_p:n</code>	★	<code>\tl_if_head_is_N_type_p:n {<token list>}</code>
<code>\tl_if_head_is_N_type:nTF</code>	★	<code>\tl_if_head_is_N_type:nTF {<token list>} {<true code>} {<false code>}</code>

New: 2012-07-08

Tests if the first *<token>* in the *<token list>* is a normal N-type argument. In other words, it is neither an explicit space character (explicit token with character code 32 and category code 10) nor an explicit begin-group character (with category code 1 and any character code). An empty argument yields **false**, as it does not have a “normal” first token. This function is useful to implement actions on token lists on a token by token basis.

<code>\tl_if_head_is_space_p:n</code>	★	<code>\tl_if_head_is_space_p:n {<token list>}</code>
<code>\tl_if_head_is_space:nTF</code>	★	<code>\tl_if_head_is_space:nTF {<token list>} {<true code>} {<false code>}</code>

Updated: 2012-07-08

Tests if the first *<token>* in the *<token list>* is an explicit space character (explicit token with character code 12 and category code 10). In particular, the test is **false** if the *<token list>* starts with an implicit token such as `\c_space_token`, or if it is empty. This function is useful to implement actions on token lists on a token by token basis.

10 Using a single item

<hr/> <code>\tl_item:nn</code> ★	<code>\tl_item:nn {⟨token list⟩} {⟨integer expression⟩}</code>
<code>\tl_item:Nn</code> ★	Indexing items in the $\langle token list \rangle$ from 1 on the left, this function evaluates the $\langle integer expression \rangle$ and leaves the appropriate item from the $\langle token list \rangle$ in the input stream. If the $\langle integer expression \rangle$ is negative, indexing occurs from the right of the token list, starting at -1 for the right-most item. If the index is out of bounds, then the function expands to nothing.
<code>\tl_item:cn</code> ★	
<hr/> New: 2014-07-17 <hr/>	

TeXhackers note: The result is returned within the `\unexpanded` primitive (`\exp_not:n`), which means that the $\langle item \rangle$ does not expand further when appearing in an x-type argument expansion.

11 Viewing token lists

<hr/> <code>\tl_show:N</code>	<code>\tl_show:N {tl var}</code>
<code>\tl_show:c</code>	Displays the content of the $\langle tl var \rangle$ on the terminal.
<hr/> Updated: 2015-08-01 <hr/>	

TeXhackers note: This is similar to the TeX primitive `\show`, wrapped to a fixed number of characters per line.

<hr/> <code>\tl_show:n</code>	<code>\tl_show:n {(token list)}</code>
<hr/> Updated: 2015-08-07 <hr/>	Displays the $\langle token list \rangle$ on the terminal.

TeXhackers note: This is similar to the ϵ -TeX primitive `\showtokens`, wrapped to a fixed number of characters per line.

<hr/> <code>\tl_log:N</code>	<code>\tl_log:N {tl var}</code>
<code>\tl_log:c</code>	Writes the content of the $\langle tl var \rangle$ in the log file. See also <code>\tl_show:N</code> which displays the result in the terminal.
<hr/> New: 2014-08-22 <hr/> Updated: 2015-08-01 <hr/>	

<hr/> <code>\tl_log:n</code>	<code>\tl_log:n {(token list)}</code>
<hr/> New: 2014-08-22 <hr/> Updated: 2015-08-07 <hr/>	Writes the $\langle token list \rangle$ in the log file. See also <code>\tl_show:n</code> which displays the result in the terminal.

12 Constant token lists

<hr/> <code>\c_empty_tl</code> <hr/>	Constant that is always empty.
--------------------------------------	--------------------------------

`\c_novalue_tl`
 New: 2017-11-14

A marker for the absence of an argument. This constant `tl` can safely be typeset (cf. `\q_nil`), with the result being `-NoValue-`. It is important to note that `\c_novalue_tl` is constructed such that it will *not* match the simple text input `-NoValue-`, *i.e.* that

```
\tl_if_eq:VnTF \c_novalue_tl { -NoValue- }
```

is logically **false**. The `\c_novalue_tl` marker is intended for use in creating document-level interfaces, where it serves as an indicator that an (optional) argument was omitted. In particular, it is distinct from a simple empty `tl`.

`\c_space_tl`

An explicit space character contained in a token list (compare this with `\c_space_token`). For use where an explicit space is required.

13 Scratch token lists

`\l_tmpa_tl`
`\l_tmpb_tl`

Scratch token lists for local assignment. These are never used by the kernel code, and so are safe for use with any L^AT_EX3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.

`\g_tmpa_tl`
`\g_tmpb_tl`

Scratch token lists for global assignment. These are never used by the kernel code, and so are safe for use with any L^AT_EX3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.

14 Internal functions

`_tl_trim_spaces:nn`

```
\_tl_trim_spaces:nn { \q_mark <token list> } {<continuation>}
```

This function removes all leading and trailing explicit space characters from the *<token list>*, and expands to the *<continuation>*, followed by a brace group containing `\use_none:n \q_mark <trimmed token list>`. For instance, `\tl_trim_spaces:n` is implemented by taking the *<continuation>* to be `\exp_not:o`, and the *o*-type expansion removes the `\q_mark`. This function is also used in `l3clist` and `l3candidates`.

Part VII

The l3str package

Strings

TeX associates each character with a category code: as such, there is no concept of a “string” as commonly understood in many other programming languages. However, there are places where we wish to manipulate token lists while in some sense “ignoring” category codes: this is done by treating token lists as strings in a TeX sense.

A TeX string (and thus an expl3 string) is a series of characters which have category code 12 (“other”) with the exception of space characters which have category code 10 (“space”). Thus at a technical level, a TeX string is a token list with the appropriate category codes. In this documentation, these are simply referred to as strings.

String variables are simply specialised token lists, but by convention should be named with the suffix `...str`. Such variables should contain characters with category code 12 (other), except spaces, which have category code 10 (blank space). All the functions in this module which accept a token list argument first convert it to a string using `\tl_to_str:n` for internal processing, and do not treat a token list or the corresponding string representation differently.

As a string is a subset of the more general token list, it is sometimes unclear when one should be used over the other. Use a string variable for data that isn’t primarily intended for typesetting and for which a level of protection from unwanted expansion is suitable. This data type simplifies comparison of variables since there are no concerns about expansion of their contents.

The functions `\cs_to_str:N`, `\tl_to_str:n`, `\tl_to_str:N` and `\token_to_str:N` (and variants) generate strings from the appropriate input: these are documented in l3basics, l3tl and l3token, respectively.

Most expandable functions in this module come in three flavours:

- `\str_...:N`, which expect a token list or string variable as their argument;
- `\str_...:n`, taking any token list (or string) as an argument;
- `\str_..._ignore_spaces:n`, which ignores any space encountered during the operation: these functions are typically faster than those which take care of escaping spaces appropriately.

1 Building strings

`\str_new:N`
`\str_new:c`
 New: 2015-09-18

`\str_new:N` $\langle str\ var \rangle$
 Creates a new $\langle str\ var \rangle$ or raises an error if the name is already taken. The declaration is global. The $\langle str\ var \rangle$ is initially empty.

`\str_const:Nn`
`\str_const:(Nx|cn|cx)`
 New: 2015-09-18

`\str_const:Nn` $\langle str\ var \rangle$ $\{ \langle token\ list \rangle \}$
 Creates a new constant $\langle str\ var \rangle$ or raises an error if the name is already taken. The value of the $\langle str\ var \rangle$ is set globally to the $\langle token\ list \rangle$, converted to a string.

```
\str_clear:N
\str_clear:c
\str_gclear:N
\str_gclear:c
```

New: 2015-09-18

`\str_clear:N` $\langle str\ var \rangle$
Clears the content of the $\langle str\ var \rangle$.

```
\str_clear_new:N
\str_clear_new:c
```

New: 2015-09-18

`\str_clear_new:N` $\langle str\ var \rangle$
Ensures that the $\langle str\ var \rangle$ exists globally by applying `\str_new:N` if necessary, then applies `\str_(g)clear:N` to leave the $\langle str\ var \rangle$ empty.

```
\str_set_eq:NN
\str_set_eq:(cN|Nc|cc)
\str_gset_eq:NN
\str_gset_eq:(cN|Nc|cc)
```

New: 2015-09-18

`\str_set_eq:NN` $\langle str\ var_1 \rangle$ $\langle str\ var_2 \rangle$
Sets the content of $\langle str\ var_1 \rangle$ equal to that of $\langle str\ var_2 \rangle$.

```
\str_concat:NNN
\str_concat:ccc
\str_gconcat:NNN
\str_gconcat:ccc
```

New: 2017-10-08

`\str_concat:NNN` $\langle str\ var_1 \rangle$ $\langle str\ var_2 \rangle$ $\langle str\ var_3 \rangle$
Concatenates the content of $\langle str\ var_2 \rangle$ and $\langle str\ var_3 \rangle$ together and saves the result in $\langle str\ var_1 \rangle$. The $\langle str\ var_2 \rangle$ is placed at the left side of the new string variable. The $\langle str\ var_2 \rangle$ and $\langle str\ var_3 \rangle$ must indeed be strings, as this function does not convert their contents to a string.

2 Adding data to string variables

```
\str_set:Nn
\str_set:(Nx|cn|cx)
\str_gset:Nn
\str_gset:(Nx|cn|cx)
```

New: 2015-09-18

`\str_set:Nn` $\langle str\ var \rangle$ $\{ \langle token\ list \rangle \}$
Converts the $\langle token\ list \rangle$ to a $\langle string \rangle$, and stores the result in $\langle str\ var \rangle$.

```
\str_put_left:Nn
\str_put_left:(Nx|cn|cx)
\str_gput_left:Nn
\str_gput_left:(Nx|cn|cx)
```

New: 2015-09-18

`\str_put_left:Nn` $\langle str\ var \rangle$ $\{ \langle token\ list \rangle \}$
Converts the $\langle token\ list \rangle$ to a $\langle string \rangle$, and prepends the result to $\langle str\ var \rangle$. The current contents of the $\langle str\ var \rangle$ are not automatically converted to a string.

```
\str_put_right:Nn
\str_put_right:(Nx|cn|cx)
\str_gput_right:Nn
\str_gput_right:(Nx|cn|cx)
```

New: 2015-09-18

`\str_put_right:Nn` $\langle str\ var \rangle$ $\{ \langle token\ list \rangle \}$
Converts the $\langle token\ list \rangle$ to a $\langle string \rangle$, and appends the result to $\langle str\ var \rangle$. The current contents of the $\langle str\ var \rangle$ are not automatically converted to a string.

2.1 Modifying string variables

```
\str_replace_once:Nnn
\str_replace_once:cnn
\str_greplace_once:Nnn
\str_greplace_once:cnn
```

New: 2017-10-08

```
\str_replace_all:Nnn
\str_replace_all:cnn
\str_greplace_all:Nnn
\str_greplace_all:cnn
```

New: 2017-10-08

```
\str_remove_once:Nn
\str_remove_once:cn
\str_gremove_once:Nn
\str_gremove_once:cn
```

New: 2017-10-08

```
\str_remove_all:Nn
\str_remove_all:cn
\str_gremove_all:Nn
\str_gremove_all:cn
```

New: 2017-10-08

`\str_replace_once:Nnn` $\langle str\ var \rangle$ $\{\langle old \rangle\}$ $\{\langle new \rangle\}$

Converts the $\langle old \rangle$ and $\langle new \rangle$ token lists to strings, then replaces the first (leftmost) occurrence of $\langle old\ string \rangle$ in the $\langle str\ var \rangle$ with $\langle new\ string \rangle$.

`\str_replace_all:Nnn` $\langle str\ var \rangle$ $\{\langle old \rangle\}$ $\{\langle new \rangle\}$

Converts the $\langle old \rangle$ and $\langle new \rangle$ token lists to strings, then replaces all occurrences of $\langle old\ string \rangle$ in the $\langle str\ var \rangle$ with $\langle new\ string \rangle$. As this function operates from left to right, the pattern $\langle old\ string \rangle$ may remain after the replacement (see `\str_remove_all:Nn` for an example).

`\str_remove_once:Nn` $\langle str\ var \rangle$ $\{\langle token\ list \rangle\}$

Converts the $\langle token\ list \rangle$ to a $\langle string \rangle$ then removes the first (leftmost) occurrence of $\langle string \rangle$ from the $\langle str\ var \rangle$.

`\str_remove_all:Nn` $\langle str\ var \rangle$ $\{\langle token\ list \rangle\}$

Converts the $\langle token\ list \rangle$ to a $\langle string \rangle$ then removes all occurrences of $\langle string \rangle$ from the $\langle str\ var \rangle$. As this function operates from left to right, the pattern $\langle string \rangle$ may remain after the removal, for instance,

```
\str_set:Nn \l_tmpa_str {abbccd} \str_remove_all:Nn \l_tmpa_str
{bc}
```

results in `\l_tmpa_str` containing `abcd`.

2.2 String conditionals

```
\str_if_exist_p:N ★
\str_if_exist_p:c ★
\str_if_exist:NTF ★
\str_if_exist:cTF ★
```

New: 2015-09-18

`\str_if_exist_p:N` $\langle str\ var \rangle$

`\str_if_exist:NTF` $\langle str\ var \rangle$ $\{\langle true\ code \rangle\}$ $\{\langle false\ code \rangle\}$

Tests whether the $\langle str\ var \rangle$ is currently defined. This does not check that the $\langle str\ var \rangle$ really is a string.

```
\str_if_empty_p:N ★
\str_if_empty_p:c ★
\str_if_empty:NTF ★
\str_if_empty:cTF ★
```

New: 2015-09-18

`\str_if_empty_p:N` $\langle str\ var \rangle$

`\str_if_empty:NTF` $\langle str\ var \rangle$ $\{\langle true\ code \rangle\}$ $\{\langle false\ code \rangle\}$

Tests if the $\langle string\ variable \rangle$ is entirely empty (*i.e.* contains no characters at all).

<code>\str_if_eq_p:NN</code>	★	<code>\str_if_eq_p:NN <str var₁> <str var₂></code>
<code>\str_if_eq_p:(Nc cN cc)</code>	★	<code>\str_if_eq:NNTF <str var₁> <str var₂> {\true code} {\false code}</code>
<code>\str_if_eq:NNTF</code>	★	
<code>\str_if_eq:(Nc cN cc)TF</code>	★	Compares the content of two <i><str variables></i> and is logically true if the two contain the same characters in the same order.

New: 2015-09-18

<code>\str_if_eq_p:nn</code>	★	<code>\str_if_eq_p:nn {\tl₁} {\tl₂}</code>
<code>\str_if_eq_p:(Vn on no nV VV)</code>	★	<code>\str_if_eq:nnTF {\tl₁} {\tl₂} {\true code} {\false code}</code>
<code>\str_if_eq:nnTF</code>	★	
<code>\str_if_eq:(Vn on no nV VV)TF</code>	★	

Compares the two *<token lists>* on a character by character basis (namely after converting them to strings), and is **true** if the two *<strings>* contain the same characters in the same order. Thus for example

`\str_if_eq_p:no { abc } { \tl_to_str:n { abc } }`

is logically **true**.

<code>\str_if_eq_x_p:nn</code>	★	<code>\str_if_eq_x_p:nn {\tl₁} {\tl₂}</code>
<code>\str_if_eq_x_p:nnTF</code>	★	<code>\str_if_eq_x:nnTF {\tl₁} {\tl₂} {\true code} {\false code}</code>

New: 2012-06-05

Fully expands the two *<token lists>* and converts them to *<strings>*, then compares these on a character by character basis: it is **true** if the two *<strings>* contain the same characters in the same order. Thus for example

`\str_if_eq_x_p:nn { abc } { \tl_to_str:n { abc } }`

is logically **true**.

<code>\str_if_in:NnTF</code>	<code>\str_if_in:NnTF <str var> {\token list} {\true code} {\false code}</code>
<code>\str_if_in:cnTF</code>	

New: 2017-10-08

Converts the *<token list>* to a *<string>* and tests if that *<string>* is found in the content of the *<str var>*.

<code>\str_if_in:nnTF</code>	<code>\str_if_in:nnTF {\tl₁} {\tl₂} {\true code} {\false code}</code>
------------------------------	---

New: 2017-10-08

Converts both *<token lists>* to *<strings>* and tests whether *<string_{2 is found inside *<string_{1.}*}*

<code>\str_case:nn</code> ★	<code>\str_case:nnTF {⟨test string⟩}</code>
<code>\str_case:(on nV nv)</code> ★	{
<code>\str_case:nnTF</code> ★	{⟨string case ₁ ⟩} {⟨code case ₁ ⟩}
<code>\str_case:(on nV nv)TF</code> ★	{⟨string case ₂ ⟩} {⟨code case ₂ ⟩}
	...
	{⟨string case _n ⟩} {⟨code case _n ⟩}
	}
	{⟨true code⟩}
	{⟨false code⟩}

New: 2013-07-24
Updated: 2015-02-28

Compares the *⟨test string⟩* in turn with each of the *⟨string cases⟩* (all token lists are converted to strings). If the two are equal (as described for `\str_if_eq:nnTF`) then the associated *⟨code⟩* is left in the input stream and other cases are discarded. If any of the cases are matched, the *⟨true code⟩* is also inserted into the input stream (after the code for the appropriate case), while if none match then the *⟨false code⟩* is inserted. The function `\str_case:nn`, which does nothing if there is no match, is also available.

<code>\str_case_x:nn</code> ★	<code>\str_case_x:nnTF {⟨test string⟩}</code>
<code>\str_case_x:nnTF</code> ★	{
	{⟨string case ₁ ⟩} {⟨code case ₁ ⟩}
	{⟨string case ₂ ⟩} {⟨code case ₂ ⟩}
	...
	{⟨string case _n ⟩} {⟨code case _n ⟩}
	}
	{⟨true code⟩}
	{⟨false code⟩}

New: 2013-07-24

Compares the full expansion of the *⟨test string⟩* in turn with the full expansion of the *⟨string cases⟩* (all token lists are converted to strings). If the two full expansions are equal (as described for `\str_if_eq:nnTF`) then the associated *⟨code⟩* is left in the input stream and other cases are discarded. If any of the cases are matched, the *⟨true code⟩* is also inserted into the input stream (after the code for the appropriate case), while if none match then the *⟨false code⟩* is inserted. The function `\str_case_x:nn`, which does nothing if there is no match, is also available. The *⟨test string⟩* is expanded in each comparison, and must always yield the same result: for example, random numbers must not be used within this string.

3 Mapping to strings

<code>\str_map_function:NN</code> ☆	<code>\str_map_function:NN ⟨str var⟩ ⟨function⟩</code>
<code>\str_map_function:cN</code> ☆	Applies <i>⟨function⟩</i> to every <i>⟨character⟩</i> in the <i>⟨str var⟩</i> including spaces. See also <code>\str_map_function:nN</code> .
<code>\str_map_function:nN</code> ☆	<code>\str_map_function:nN {⟨token list⟩} ⟨function⟩</code>
	Converts the <i>⟨token list⟩</i> to a <i>⟨string⟩</i> then applies <i>⟨function⟩</i> to every <i>⟨character⟩</i> in the <i>⟨string⟩</i> including spaces. See also <code>\str_map_function:NN</code> .

New: 2017-11-14

New: 2017-11-14

<hr/> <code>\str_map_inline:Nn</code> <code>\str_map_inline:cn</code> <hr/> New: 2017-11-14	<code>\str_map_inline:Nn <str var> {<inline function>}</code> Applies the <i><inline function></i> to every <i><character></i> in the <i><str var></i> including spaces. The <i><inline function></i> should consist of code which receives the <i><character></i> as #1. See also <code>\str_map_function:NN</code> .
<hr/> <code>\str_map_inline:nn</code> <hr/> New: 2017-11-14	<code>\str_map_inline:nn {<token list>} {<inline function>}</code> Converts the <i><token list></i> to a <i><string></i> then applies the <i><inline function></i> to every <i><character></i> in the <i><string></i> including spaces. The <i><inline function></i> should consist of code which receives the <i><character></i> as #1. See also <code>\str_map_function:NN</code> .
<hr/> <code>\str_map_variable:NNn</code> <code>\str_map_variable:cNn</code> <hr/> New: 2017-11-14	<code>\str_map_variable:NNn <str var> <variable> {<code>}</code> Stores each <i><character></i> of the <i><string></i> (including spaces) in turn in the (string or token list) <i><variable></i> and applies the <i><code></i> . The <i><code></i> will usually make use of the <i><variable></i> , but this is not enforced. The assignments to the <i><variable></i> are local. See also <code>\str_map_inline:Nn</code> .
<hr/> <code>\str_map_variable:nNn</code> <hr/> New: 2017-11-14	<code>\str_map_variable:nNn {<token list>} <variable> {<code>}</code> Converts the <i><token list></i> to a <i><string></i> then stores each <i><character></i> in the <i><string></i> (including spaces) in turn in the (string or token list) <i><variable></i> and applies the <i><code></i> . The <i><code></i> will usually make use of the <i><variable></i> , but this is not enforced. The assignments to the <i><variable></i> are local. See also <code>\str_map_inline:Nn</code> .
<hr/> <code>\str_map_break: ☆</code> <hr/> New: 2017-10-08	<code>\str_map_break:</code> Used to terminate a <code>\str_map...</code> function before all characters in the <i><string></i> have been processed. This normally takes place within a conditional statement, for example <pre> \str_map_inline:Nn \l_my_str { \str_if_eq:nnT { #1 } { bingo } { \str_map_break: } % Do something useful } </pre> <p>See also <code>\str_map_break:n</code>. Use outside of a <code>\str_map...</code> scenario leads to low level \TeX errors.</p> <p>\TeXhackers note: When the mapping is broken, additional tokens may be inserted before continuing with the code that follows the loop. This depends on the design of the mapping function.</p>

`\str_map_break:n` ☆

New: 2017-10-08

`\str_map_break:n {⟨code⟩}`

Used to terminate a `\str_map...` function before all characters in the *⟨string⟩* have been processed, inserting the *⟨code⟩* after the mapping has ended. This normally takes place within a conditional statement, for example

```
\str_map_inline:Nn \l_my_str
{
  \str_if_eq:nnT { #1 } { bingo }
  { \str_map_break:n { <code> } }
  % Do something useful
}
```

Use outside of a `\str_map...` scenario leads to low level TeX errors.

TeXhackers note: When the mapping is broken, additional tokens may be inserted before the *⟨code⟩* is inserted into the input stream. This depends on the design of the mapping function.

4 Working with the content of strings

`\str_use:N` ☆

`\str_use:c` ☆

New: 2015-09-18

`\str_use:N ⟨str var⟩`

Recovers the content of a *⟨str var⟩* and places it directly in the input stream. An error is raised if the variable does not exist or if it is invalid. Note that it is possible to use a *⟨str⟩* directly without an accessor function.

`\str_count:N`

`\str_count:c`

`\str_count:n`

`\str_count_ignore_spaces:n` ☆

New: 2015-09-18

☆ `\str_count:n {⟨token list⟩}`

Leaves in the input stream the number of characters in the string representation of *⟨token list⟩*, as an integer denotation. The functions differ in their treatment of spaces. In the case of `\str_count:N` and `\str_count:n`, all characters including spaces are counted. The `\str_count_ignore_spaces:n` function leaves the number of non-space characters in the input stream.

`\str_count_spaces:N` ☆

`\str_count_spaces:c` ☆

`\str_count_spaces:n` ☆

New: 2015-09-18

☆ `\str_count_spaces:n {⟨token list⟩}`

Leaves in the input stream the number of space characters in the string representation of *⟨token list⟩*, as an integer denotation. Of course, this function has no `_ignore_spaces` variant.

<code>\str_head:N</code>	★	<code>\str_head:n {⟨token list⟩}</code>
<code>\str_head:c</code>	★	
<code>\str_head:n</code>	★	
<code>\str_head_ignore_spaces:n</code>	★	

New: 2015-09-18

Converts the $\langle token\ list \rangle$ into a $\langle string \rangle$. The first character in the $\langle string \rangle$ is then left in the input stream, with category code “other”. The functions differ if the first character is a space: `\str_head:N` and `\str_head:n` return a space token with category code 10 (blank space), while the `\str_head_ignore_spaces:n` function ignores this space character and leaves the first non-space character in the input stream. If the $\langle string \rangle$ is empty (or only contains spaces in the case of the `_ignore_spaces` function), then nothing is left on the input stream.

<code>\str_tail:N</code>	★	<code>\str_tail:n {⟨token list⟩}</code>
<code>\str_tail:c</code>	★	
<code>\str_tail:n</code>	★	
<code>\str_tail_ignore_spaces:n</code>	★	

New: 2015-09-18

Converts the $\langle token\ list \rangle$ to a $\langle string \rangle$, removes the first character, and leaves the remaining characters (if any) in the input stream, with category codes 12 and 10 (for spaces). The functions differ in the case where the first character is a space: `\str_tail:N` and `\str_tail:n` only trim that space, while `\str_tail_ignore_spaces:n` removes the first non-space character and any space before it. If the $\langle token\ list \rangle$ is empty (or blank in the case of the `_ignore_spaces` variant), then nothing is left on the input stream.

<code>\str_item:Nn</code>	★	<code>\str_item:nn {⟨token list⟩} {⟨integer expression⟩}</code>
<code>\str_item:nn</code>	★	
<code>\str_item_ignore_spaces:nn</code>	★	

New: 2015-09-18

Converts the $\langle token\ list \rangle$ to a $\langle string \rangle$, and leaves in the input stream the character in position $\langle integer\ expression \rangle$ of the $\langle string \rangle$, starting at 1 for the first (left-most) character. In the case of `\str_item:Nn` and `\str_item:nn`, all characters including spaces are taken into account. The `\str_item_ignore_spaces:nn` function skips spaces when counting characters. If the $\langle integer\ expression \rangle$ is negative, characters are counted from the end of the $\langle string \rangle$. Hence, -1 is the right-most character, *etc.*

```

\str_range:Nnn      ★ \str_range:nnn {⟨token list⟩} {⟨start index⟩} {⟨end index⟩}
\str_range:cnn      ★
\str_range:nnn      ★
\str_range_ignore_spaces:nnn ★

```

New: 2015-09-18

Converts the $\langle token\ list \rangle$ to a $\langle string \rangle$, and leaves in the input stream the characters from the $\langle start\ index \rangle$ to the $\langle end\ index \rangle$ inclusive. Positive $\langle indices \rangle$ are counted from the start of the string, 1 being the first character, and negative $\langle indices \rangle$ are counted from the end of the string, -1 being the last character. If either of $\langle start\ index \rangle$ or $\langle end\ index \rangle$ is 0, the result is empty. For instance,

```

\iow_term:x { \str_range:nnn { abcdef } { 2 } { 5 } }
\iow_term:x { \str_range:nnn { abcdef } { -4 } { -1 } }
\iow_term:x { \str_range:nnn { abcdef } { -2 } { -1 } }
\iow_term:x { \str_range:nnn { abcdef } { 0 } { -1 } }

```

prints bcde, cdef, ef, and an empty line to the terminal. The $\langle start\ index \rangle$ must always be smaller than or equal to the $\langle end\ index \rangle$: if this is not the case then no output is generated. Thus

```

\iow_term:x { \str_range:nnn { abcdef } { 5 } { 2 } }
\iow_term:x { \str_range:nnn { abcdef } { -1 } { -4 } }

```

both yield empty strings.

5 String manipulation

<code>\str_lower_case:n</code>	★	<code>\str_lower_case:n {⟨tokens⟩}</code>
<code>\str_lower_case:f</code>	★	<code>\str_upper_case:n {⟨tokens⟩}</code>
<code>\str_upper_case:n</code>	★	
<code>\str_upper_case:f</code>	★	

New: 2015-03-01

Converts the input `⟨tokens⟩` to their string representation, as described for `\tl_to_str:n`, and then to the lower or upper case representation using a one-to-one mapping as described by the Unicode Consortium file `UnicodeData.txt`.

These functions are intended for case changing programmatic data in places where upper/lower case distinctions are meaningful. One example would be automatically generating a function name from user input where some case changing is needed. In this situation the input is programmatic, not textual, case does have meaning and a language-independent one-to-one mapping is appropriate. For example

```
\cs_new_protected:Npn \myfunc:nn #1#2
{
  \cs_set_protected:cpn
  {
    user
    \str_upper_case:f { \tl_head:n {#1} }
    \str_lower_case:f { \tl_tail:n {#1} }
  }
  { #2 }
}
```

would be used to generate a function with an auto-generated name consisting of the upper case equivalent of the supplied name followed by the lower case equivalent of the rest of the input.

These functions should *not* be used for

- Caseless comparisons: use `\str_fold_case:n` for this situation (case folding is distinct from lower casing).
- Case changing text for typesetting: see the `\tl_lower_case:n(n)`, `\tl_upper_case:n(n)` and `\tl_mixed_case:n(n)` functions which correctly deal with context-dependence and other factors appropriate to text case changing.

T_EXhackers note: As with all `expl3` functions, the input supported by `\str_fold_case:n` is *engine-native* characters which are or interoperate with UTF-8. As such, when used with pdfT_EX *only* the Latin alphabet characters A–Z are case-folded (*i.e.* the ASCII range which coincides with UTF-8). Full UTF-8 support is available with both X_ƎT_EX and LuaT_EX, subject only to the fact that X_ƎT_EX in particular has issues with characters of code above hexadecimal 0xFFFF when interacting with `\tl_to_str:n`.

`\str_fold_case:n` ★ `\str_fold_case:n {(tokens)}`

`\str_fold_case:V` ★

New: 2014-06-19

Updated: 2016-03-07

Converts the input $\langle tokens \rangle$ to their string representation, as described for `\tl_to_str:n`, and then folds the case of the resulting $\langle string \rangle$ to remove case information. The result of this process is left in the input stream.

String folding is a process used for material such as identifiers rather than for “text”. The folding provided by `\str_fold_case:n` follows the mappings provided by the [Unicode Consortium](#), who [state](#):

Case folding is primarily used for caseless comparison of text, such as identifiers in a computer program, rather than actual text transformation. Case folding in Unicode is based on the lowercase mapping, but includes additional changes to the source text to help make it language-insensitive and consistent. As a result, case-folded text should be used solely for internal processing and generally should not be stored or displayed to the end user.

The folding approach implemented by `\str_fold_case:n` follows the “full” scheme defined by the Unicode Consortium (*e.g.* `SS` folds to `ss`). As case-folding is a language-insensitive process, there is no special treatment of Turkic input (*i.e.* `I` always folds to `i` and not to `ı`).

TeXhackers note: As with all `expl3` functions, the input supported by `\str_fold_case:n` is *engine-native* characters which are or interoperate with UTF-8. As such, when used with pdfTeX *only* the Latin alphabet characters A–Z are case-folded (*i.e.* the ASCII range which coincides with UTF-8). Full UTF-8 support is available with both XeTeX and LuaTeX, subject only to the fact that XeTeX in particular has issues with characters of code above hexadecimal 0xFFFF when interacting with `\tl_to_str:n`.

6 Viewing strings

`\str_show:N` `\str_show:N {str var}`

`\str_show:c`

`\str_show:n`

New: 2015-09-18

Displays the content of the $\langle str var \rangle$ on the terminal.

7 Constant token lists

```

\c_ampersand_str
\c_atsign_str
\c_backslash_str
\c_left_brace_str
\c_right_brace_str
\c_circumflex_str
\c_colon_str
\c_dollar_str
\c_hash_str
\c_percent_str
\c_tilde_str
\c_underscore_str

```

New: 2015-09-19

Constant strings, containing a single character token, with category code 12.

8 Scratch strings

```

\l_tmpa_str
\l_tmpb_str

```

Scratch strings for local assignment. These are never used by the kernel code, and so are safe for use with any L^AT_EX3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.

```

\g_tmpa_str
\g_tmpb_str

```

Scratch strings for global assignment. These are never used by the kernel code, and so are safe for use with any L^AT_EX3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.

8.1 Internal string functions

```

\__str_if_eq_x:nn ★ \__str_if_eq_x:nn {\t1} {\t2}

```

Compares the full expansion of two *<token lists>* on a character by character basis, and is `true` if the two lists contain the same characters in the same order. Leaves 0 in the input stream if the condition is true, and +1 or -1 otherwise.

```

\__str_if_eq_x_return:nn \__str_if_eq_x_return:nn {\t1} {\t2}

```

Compares the full expansion of two *<token lists>* on a character by character basis, and is `true` if the two lists contain the same characters in the same order. Either `\prg_return_true:` or `\prg_return_false:` is then left in the input stream. This is a version of `\str_if_eq_x:nnTF` coded for speed.

```

\__str_to_other:n ★ \__str_to_other:n {\token list}

```

Converts the *<token list>* to a *<other string>*, where spaces have category code “other”. This function can be f-expanded without fear of losing a leading space, since spaces do not have category code 10 in its result. It takes a time quadratic in the character count of the string.

<hr/> <hr/>	<hr/> <hr/>
<code>__str_to_other_fast:n</code> ☆	<code>__str_to_other_fast:n {⟨token list⟩}</code>
	Same behaviour <code>__str_to_other:n</code> but only restricted-expandable. It takes a time linear in the character count of the string. It is used for <code>\iow_wrap:nnnN</code> .
<hr/> <hr/>	<hr/> <hr/>
<code>__str_count:n</code> ★	<code>__str_count:n {⟨other string⟩}</code>
	This function expects an argument that is entirely made of characters with category “other”, as produced by <code>__str_to_other:n</code> . It leaves in the input stream the number of character tokens in the <i>⟨other string⟩</i> , faster than the analogous <code>\str_count:n</code> function.
<hr/> <hr/>	<hr/> <hr/>
<code>__str_range:nnn</code> ★	<code>__str_range:nnn {⟨other string⟩} {⟨start index⟩} {⟨end index⟩}</code>
	Identical to <code>\str_range:nnn</code> except that the first argument is expected to be entirely made of characters with category “other”, as produced by <code>__str_to_other:n</code> , and the result is also an <i>⟨other string⟩</i> .

Part VIII

The l3seq package

Sequences and stacks

L^AT_EX3 implements a “sequence” data type, which contain an ordered list of entries which may contain any *balanced text*. It is possible to map functions to sequences such that the function is applied to every item in the sequence.

Sequences are also used to implement stack functions in L^AT_EX3. This is achieved using a number of dedicated stack functions.

1 Creating and initialising sequences

<code>\seq_new:N</code>	<code>\seq_new:N <sequence></code>
<code>\seq_new:c</code>	

Creates a new *<sequence>* or raises an error if the name is already taken. The declaration is global. The *<sequence>* initially contains no items.

<code>\seq_clear:N</code>	<code>\seq_clear:N <sequence></code>
<code>\seq_clear:c</code>	
<code>\seq_gclear:N</code>	Clears all items from the <i><sequence></i> .
<code>\seq_gclear:c</code>	

<code>\seq_clear_new:N</code>	<code>\seq_clear_new:N <sequence></code>
<code>\seq_clear_new:c</code>	
<code>\seq_gclear_new:N</code>	Ensures that the <i><sequence></i> exists globally by applying <code>\seq_new:N</code> if necessary, then applies <code>\seq_(g)clear:N</code> to leave the <i><sequence></i> empty.
<code>\seq_gclear_new:c</code>	

<code>\seq_set_eq:NN</code>	<code>\seq_set_eq:NN <sequence₁> <sequence₂></code>
<code>\seq_set_eq:(cN Nc cc)</code>	
<code>\seq_gset_eq:NN</code>	Sets the content of <i><sequence₁></i> equal to that of <i><sequence₂></i> .
<code>\seq_gset_eq:(cN Nc cc)</code>	

<code>\seq_set_from_clist:NN</code>	<code>\seq_set_from_clist:NN <sequence> <comma-list></code>
<code>\seq_set_from_clist:(cN Nc cc)</code>	
<code>\seq_set_from_clist:Nn</code>	
<code>\seq_set_from_clist:cn</code>	
<code>\seq_gset_from_clist:NN</code>	
<code>\seq_gset_from_clist:(cN Nc cc)</code>	
<code>\seq_gset_from_clist:Nn</code>	
<code>\seq_gset_from_clist:cn</code>	

New: 2014-07-17

Converts the data in the *<comma list>* into a *<sequence>*: the original *<comma list>* is unchanged.

```

\seq_set_split:Nnn
\seq_set_split:NnV
\seq_gset_split:Nnn
\seq_gset_split:NnV

```

New: 2011-08-15
Updated: 2012-07-02

```
\seq_set_split:Nnn <sequence> {<delimiter>} {<token list>}
```

Splits the $\langle token list \rangle$ into $\langle items \rangle$ separated by $\langle delimiter \rangle$, and assigns the result to the $\langle sequence \rangle$. Spaces on both sides of each $\langle item \rangle$ are ignored, then one set of outer braces is removed (if any); this space trimming behaviour is identical to that of `l3clist` functions. Empty $\langle items \rangle$ are preserved by `\seq_set_split:Nnn`, and can be removed afterwards using `\seq_remove_all:Nn <sequence> {<>}`. The $\langle delimiter \rangle$ may not contain `{`, `}` or `#` (assuming \TeX 's normal category code régime). If the $\langle delimiter \rangle$ is empty, the $\langle token list \rangle$ is split into $\langle items \rangle$ as a $\langle token list \rangle$.

```

\seq_concat:NNN
\seq_concat:ccc
\seq_gconcat:NNN
\seq_gconcat:ccc

```

```
\seq_concat:NNN <sequence1> <sequence2> <sequence3>
```

Concatenates the content of $\langle sequence_2 \rangle$ and $\langle sequence_3 \rangle$ together and saves the result in $\langle sequence_1 \rangle$. The items in $\langle sequence_2 \rangle$ are placed at the left side of the new sequence.

```

\seq_if_exist_p:N *
\seq_if_exist_p:c *
\seq_if_exist:NTF *
\seq_if_exist:cTF *

```

New: 2012-03-03

```
\seq_if_exist_p:N <sequence>
```

```
\seq_if_exist:NNTF <sequence> {<true code>} {<false code>}
```

Tests whether the $\langle sequence \rangle$ is currently defined. This does not check that the $\langle sequence \rangle$ really is a sequence variable.

2 Appending data to sequences

```

\seq_put_left:Nn
\seq_put_left:(NV|Nv|No|Nx|cn|cV|cv|co|cx)
\seq_gput_left:Nn
\seq_gput_left:(NV|Nv|No|Nx|cn|cV|cv|co|cx)

```

```
\seq_put_left:Nn <sequence> {<item>}
```

Appends the $\langle item \rangle$ to the left of the $\langle sequence \rangle$.

```

\seq_put_right:Nn
\seq_put_right:(NV|Nv|No|Nx|cn|cV|cv|co|cx)
\seq_gput_right:Nn
\seq_gput_right:(NV|Nv|No|Nx|cn|cV|cv|co|cx)

```

```
\seq_put_right:Nn <sequence> {<item>}
```

Appends the $\langle item \rangle$ to the right of the $\langle sequence \rangle$.

3 Recovering items from sequences

Items can be recovered from either the left or the right of sequences. For implementation reasons, the actions at the left of the sequence are faster than those acting on the right. These functions all assign the recovered material locally, *i.e.* setting the $\langle token list variable \rangle$ used with `\tl_set:Nn` and *never* `\tl_gset:Nn`.

```

\seq_get_left:NN
\seq_get_left:cN

```

Updated: 2012-05-14

```
\seq_get_left:NN <sequence> <token list variable>
```

Stores the left-most item from a $\langle sequence \rangle$ in the $\langle token list variable \rangle$ without removing it from the $\langle sequence \rangle$. The $\langle token list variable \rangle$ is assigned locally. If $\langle sequence \rangle$ is empty the $\langle token list variable \rangle$ is set to the special marker `\q_no_value`.

<hr/> <code>\seq_get_right:NN</code> <code>\seq_get_right:cN</code> <hr/> Updated: 2012-05-19 <hr/>	<code>\seq_get_right:NN</code> $\langle sequence \rangle$ $\langle token list variable \rangle$ Stores the right-most item from a $\langle sequence \rangle$ in the $\langle token list variable \rangle$ without removing it from the $\langle sequence \rangle$. The $\langle token list variable \rangle$ is assigned locally. If $\langle sequence \rangle$ is empty the $\langle token list variable \rangle$ is set to the special marker <code>\q_no_value</code> .
<hr/> <code>\seq_pop_left:NN</code> <code>\seq_pop_left:cN</code> <hr/> Updated: 2012-05-14 <hr/>	<code>\seq_pop_left:NN</code> $\langle sequence \rangle$ $\langle token list variable \rangle$ Pops the left-most item from a $\langle sequence \rangle$ into the $\langle token list variable \rangle$, <i>i.e.</i> removes the item from the sequence and stores it in the $\langle token list variable \rangle$. Both of the variables are assigned locally. If $\langle sequence \rangle$ is empty the $\langle token list variable \rangle$ is set to the special marker <code>\q_no_value</code> .
<hr/> <code>\seq_gpop_left:NN</code> <code>\seq_gpop_left:cN</code> <hr/> Updated: 2012-05-14 <hr/>	<code>\seq_gpop_left:NN</code> $\langle sequence \rangle$ $\langle token list variable \rangle$ Pops the left-most item from a $\langle sequence \rangle$ into the $\langle token list variable \rangle$, <i>i.e.</i> removes the item from the sequence and stores it in the $\langle token list variable \rangle$. The $\langle sequence \rangle$ is modified globally, while the assignment of the $\langle token list variable \rangle$ is local. If $\langle sequence \rangle$ is empty the $\langle token list variable \rangle$ is set to the special marker <code>\q_no_value</code> .
<hr/> <code>\seq_pop_right:NN</code> <code>\seq_pop_right:cN</code> <hr/> Updated: 2012-05-19 <hr/>	<code>\seq_pop_right:NN</code> $\langle sequence \rangle$ $\langle token list variable \rangle$ Pops the right-most item from a $\langle sequence \rangle$ into the $\langle token list variable \rangle$, <i>i.e.</i> removes the item from the sequence and stores it in the $\langle token list variable \rangle$. Both of the variables are assigned locally. If $\langle sequence \rangle$ is empty the $\langle token list variable \rangle$ is set to the special marker <code>\q_no_value</code> .
<hr/> <code>\seq_gpop_right:NN</code> <code>\seq_gpop_right:cN</code> <hr/> Updated: 2012-05-19 <hr/>	<code>\seq_gpop_right:NN</code> $\langle sequence \rangle$ $\langle token list variable \rangle$ Pops the right-most item from a $\langle sequence \rangle$ into the $\langle token list variable \rangle$, <i>i.e.</i> removes the item from the sequence and stores it in the $\langle token list variable \rangle$. The $\langle sequence \rangle$ is modified globally, while the assignment of the $\langle token list variable \rangle$ is local. If $\langle sequence \rangle$ is empty the $\langle token list variable \rangle$ is set to the special marker <code>\q_no_value</code> .
<hr/> <code>\seq_item:Nn</code> ★ <code>\seq_item:cn</code> ★ <hr/> New: 2014-07-17 <hr/>	<code>\seq_item:Nn</code> $\langle sequence \rangle$ $\{ \langle integer expression \rangle \}$ Indexing items in the $\langle sequence \rangle$ from 1 at the top (left), this function evaluates the $\langle integer expression \rangle$ and leaves the appropriate item from the sequence in the input stream. If the $\langle integer expression \rangle$ is negative, indexing occurs from the bottom (right) of the sequence. If the $\langle integer expression \rangle$ is larger than the number of items in the $\langle sequence \rangle$ (as calculated by <code>\seq_count:N</code>) then the function expands to nothing.

T_EXhackers note: The result is returned within the `\unexpanded` primitive (`\exp_not:n`), which means that the $\langle item \rangle$ does not expand further when appearing in an x-type argument expansion.

4 Recovering values from sequences with branching

The functions in this section combine tests for non-empty sequences with recovery of an item from the sequence. They offer increased readability and performance over separate testing and recovery phases.

<hr/> <code>\seq_get_left:NNTF</code> <code>\seq_get_left:cNTF</code> <hr/> New: 2012-05-14 Updated: 2012-05-19 <hr/>	<code>\seq_get_left:NNTF <sequence> <token list variable> {<true code>} {<false code>}</code> <p>If the <i><sequence></i> is empty, leaves the <i><false code></i> in the input stream. The value of the <i><token list variable></i> is not defined in this case and should not be relied upon. If the <i><sequence></i> is non-empty, stores the left-most item from the <i><sequence></i> in the <i><token list variable></i> without removing it from the <i><sequence></i>, then leaves the <i><true code></i> in the input stream. The <i><token list variable></i> is assigned locally.</p>
<hr/> <code>\seq_get_right:NNTF</code> <code>\seq_get_right:cNTF</code> <hr/> New: 2012-05-19 <hr/>	<code>\seq_get_right:NNTF <sequence> <token list variable> {<true code>} {<false code>}</code> <p>If the <i><sequence></i> is empty, leaves the <i><false code></i> in the input stream. The value of the <i><token list variable></i> is not defined in this case and should not be relied upon. If the <i><sequence></i> is non-empty, stores the right-most item from the <i><sequence></i> in the <i><token list variable></i> without removing it from the <i><sequence></i>, then leaves the <i><true code></i> in the input stream. The <i><token list variable></i> is assigned locally.</p>
<hr/> <code>\seq_pop_left:NNTF</code> <code>\seq_pop_left:cNTF</code> <hr/> New: 2012-05-14 Updated: 2012-05-19 <hr/>	<code>\seq_pop_left:NNTF <sequence> <token list variable> {<true code>} {<false code>}</code> <p>If the <i><sequence></i> is empty, leaves the <i><false code></i> in the input stream. The value of the <i><token list variable></i> is not defined in this case and should not be relied upon. If the <i><sequence></i> is non-empty, pops the left-most item from the <i><sequence></i> in the <i><token list variable></i>, <i>i.e.</i> removes the item from the <i><sequence></i>, then leaves the <i><true code></i> in the input stream. Both the <i><sequence></i> and the <i><token list variable></i> are assigned locally.</p>
<hr/> <code>\seq_gpop_left:NNTF</code> <code>\seq_gpop_left:cNTF</code> <hr/> New: 2012-05-14 Updated: 2012-05-19 <hr/>	<code>\seq_gpop_left:NNTF <sequence> <token list variable> {<true code>} {<false code>}</code> <p>If the <i><sequence></i> is empty, leaves the <i><false code></i> in the input stream. The value of the <i><token list variable></i> is not defined in this case and should not be relied upon. If the <i><sequence></i> is non-empty, pops the left-most item from the <i><sequence></i> in the <i><token list variable></i>, <i>i.e.</i> removes the item from the <i><sequence></i>, then leaves the <i><true code></i> in the input stream. The <i><sequence></i> is modified globally, while the <i><token list variable></i> is assigned locally.</p>
<hr/> <code>\seq_pop_right:NNTF</code> <code>\seq_pop_right:cNTF</code> <hr/> New: 2012-05-19 <hr/>	<code>\seq_pop_right:NNTF <sequence> <token list variable> {<true code>} {<false code>}</code> <p>If the <i><sequence></i> is empty, leaves the <i><false code></i> in the input stream. The value of the <i><token list variable></i> is not defined in this case and should not be relied upon. If the <i><sequence></i> is non-empty, pops the right-most item from the <i><sequence></i> in the <i><token list variable></i>, <i>i.e.</i> removes the item from the <i><sequence></i>, then leaves the <i><true code></i> in the input stream. Both the <i><sequence></i> and the <i><token list variable></i> are assigned locally.</p>
<hr/> <code>\seq_gpop_right:NNTF</code> <code>\seq_gpop_right:cNTF</code> <hr/> New: 2012-05-19 <hr/>	<code>\seq_gpop_right:NNTF <sequence> <token list variable> {<true code>} {<false code>}</code> <p>If the <i><sequence></i> is empty, leaves the <i><false code></i> in the input stream. The value of the <i><token list variable></i> is not defined in this case and should not be relied upon. If the <i><sequence></i> is non-empty, pops the right-most item from the <i><sequence></i> in the <i><token list variable></i>, <i>i.e.</i> removes the item from the <i><sequence></i>, then leaves the <i><true code></i> in the input stream. The <i><sequence></i> is modified globally, while the <i><token list variable></i> is assigned locally.</p>

5 Modifying sequences

While sequences are normally used as ordered lists, it may be necessary to modify the content. The functions here may be used to update sequences, while retaining the order of the unaffected entries.

```
\seq_remove_duplicates:N
\seq_remove_duplicates:c
\seq_gremove_duplicates:N
\seq_gremove_duplicates:c
```

`\seq_remove_duplicates:N` $\langle sequence \rangle$

Removes duplicate items from the $\langle sequence \rangle$, leaving the left most copy of each item in the $\langle sequence \rangle$. The $\langle item \rangle$ comparison takes place on a token basis, as for `\tl_if_eq:nnTF`.

TeXhackers note: This function iterates through every item in the $\langle sequence \rangle$ and does a comparison with the $\langle items \rangle$ already checked. It is therefore relatively slow with large sequences.

```
\seq_remove_all:Nn
\seq_remove_all:cn
\seq_gremove_all:Nn
\seq_gremove_all:cn
```

`\seq_remove_all:Nn` $\langle sequence \rangle$ $\{\langle item \rangle\}$

Removes every occurrence of $\langle item \rangle$ from the $\langle sequence \rangle$. The $\langle item \rangle$ comparison takes place on a token basis, as for `\tl_if_eq:nnTF`.

```
\seq_reverse:N
\seq_reverse:c
\seq_greverse:N
\seq_greverse:c
```

`\seq_reverse:N` $\langle sequence \rangle$

Reverses the order of the items stored in the $\langle sequence \rangle$.

New: 2014-07-18

```
\seq_sort:Nn
\seq_sort:cn
\seq_gsort:Nn
\seq_gsort:cn
```

`\seq_sort:Nn` $\langle sequence \rangle$ $\{\langle comparison code \rangle\}$

Sorts the items in the $\langle sequence \rangle$ according to the $\langle comparison code \rangle$, and assigns the result to $\langle sequence \rangle$. The details of sorting comparison are described in Section 1.

New: 2017-02-06

6 Sequence conditionals

```
\seq_if_empty_p:N ★
\seq_if_empty_p:c ★
\seq_if_empty:NTF ★
\seq_if_empty:cTF ★
```

`\seq_if_empty_p:N` $\langle sequence \rangle$

`\seq_if_empty:NNTF` $\langle sequence \rangle$ $\{\langle true code \rangle\}$ $\{\langle false code \rangle\}$

Tests if the $\langle sequence \rangle$ is empty (containing no items).

```
\seq_if_in:NnTF
\seq_if_in:(NV|Nv|No|Nx|cn|cV|cv|co|cx)TF
```

`\seq_if_in:NnTF` $\langle sequence \rangle$ $\{\langle item \rangle\}$ $\{\langle true code \rangle\}$ $\{\langle false code \rangle\}$

Tests if the $\langle item \rangle$ is present in the $\langle sequence \rangle$.

7 Mapping to sequences

`\seq_map_function:NN` ☆
`\seq_map_function:cN` ☆

Updated: 2012-06-29

`\seq_map_function:NN` $\langle sequence \rangle$ $\langle function \rangle$

Applies $\langle function \rangle$ to every $\langle item \rangle$ stored in the $\langle sequence \rangle$. The $\langle function \rangle$ will receive one argument for each iteration. The $\langle items \rangle$ are returned from left to right. The function `\seq_map_inline:Nn` is faster than `\seq_map_function:NN` for sequences with more than about 10 items.

`\seq_map_inline:Nn`
`\seq_map_inline:cn`

Updated: 2012-06-29

`\seq_map_inline:Nn` $\langle sequence \rangle$ $\{\langle inline function \rangle\}$

Applies $\langle inline function \rangle$ to every $\langle item \rangle$ stored within the $\langle sequence \rangle$. The $\langle inline function \rangle$ should consist of code which will receive the $\langle item \rangle$ as #1. The $\langle items \rangle$ are returned from left to right.

`\seq_map_variable:NNn`
`\seq_map_variable:(Ncn|cNn|ccn)`

Updated: 2012-06-29

`\seq_map_variable:NNn` $\langle sequence \rangle$ $\langle variable \rangle$ $\{\langle code \rangle\}$

Stores each $\langle item \rangle$ of the $\langle sequence \rangle$ in turn in the (token list) $\langle variable \rangle$ and applies the $\langle code \rangle$. The $\langle code \rangle$ will usually make use of the $\langle variable \rangle$, but this is not enforced. The assignments to the $\langle variable \rangle$ are local. The $\langle items \rangle$ are returned from left to right.

`\seq_map_break:` ☆

Updated: 2012-06-29

`\seq_map_break:`

Used to terminate a `\seq_map...` function before all entries in the $\langle sequence \rangle$ have been processed. This normally takes place within a conditional statement, for example

```
\seq_map_inline:Nn \l_my_seq
{
  \str_if_eq:nnTF { #1 } { bingo }
  { \seq_map_break: }
  {
    % Do something useful
  }
}
```

Use outside of a `\seq_map...` scenario leads to low level TeX errors.

TeXhackers note: When the mapping is broken, additional tokens may be inserted before further items are taken from the input stream. This depends on the design of the mapping function.

`\seq_map_break:n` ☆

Updated: 2012-06-29

`\seq_map_break:n {<code>}`

Used to terminate a `\seq_map...` function before all entries in the *<sequence>* have been processed, inserting the *<code>* after the mapping has ended. This normally takes place within a conditional statement, for example

```
\seq_map_inline:Nn \l_my_seq
{
  \str_if_eq:nnTF { #1 } { bingo }
  { \seq_map_break:n { <code> } }
  {
    % Do something useful
  }
}
```

Use outside of a `\seq_map...` scenario leads to low level TeX errors.

TeXhackers note: When the mapping is broken, additional tokens may be inserted before the *<code>* is inserted into the input stream. This depends on the design of the mapping function.

`\seq_count:N` ☆

`\seq_count:c` ☆

New: 2012-07-13

`\seq_count:N <sequence>`

Leaves the number of items in the *<sequence>* in the input stream as an *<integer denotation>*. The total number of items in a *<sequence>* includes those which are empty and duplicates, *i.e.* every item in a *<sequence>* is unique.

8 Using the content of sequences directly

`\seq_use:Nnnn` ☆

`\seq_use:cnnn` ☆

New: 2013-05-26

`\seq_use:Nnnn <seq var> {<separator between two>}`

`{<separator between more than two>} {<separator between final two>}`

Places the contents of the *<seq var>* in the input stream, with the appropriate *<separator>* between the items. Namely, if the sequence has more than two items, the *<separator between more than two>* is placed between each pair of items except the last, for which the *<separator between final two>* is used. If the sequence has exactly two items, then they are placed in the input stream separated by the *<separator between two>*. If the sequence has a single item, it is placed in the input stream, and an empty sequence produces no output. An error is raised if the variable does not exist or if it is invalid.

For example,

```
\seq_set_split:Nnn \l_tmpa_seq { | } { a | b | c | {de} | f }
\seq_use:Nnnn \l_tmpa_seq { ~and~ } { ,~ } { ,~and~ }
```

inserts “a, b, c, de, and f” in the input stream. The first separator argument is not used in this case because the sequence has more than 2 items.

TeXhackers note: The result is returned within the `\unexpanded` primitive (`\exp_not:n`), which means that the *<items>* do not expand further when appearing in an x-type argument expansion.

<code>\seq_use:Nn</code> ★	<code>\seq_use:Nn <seq var> {<separator>}</code>
<code>\seq_use:cn</code> ★	Places the contents of the <code><seq var></code> in the input stream, with the <code><separator></code> between the items. If the sequence has a single item, it is placed in the input stream with no <code><separator></code> , and an empty sequence produces no output. An error is raised if the variable does not exist or if it is invalid.
New: 2013-05-26	

For example,

```
\seq_set_split:Nnn \l_tmpa_seq { | } { a | b | c | {de} | f }
\seq_use:Nn \l_tmpa_seq { ~and~ }
```

inserts “a and b and c and de and f” in the input stream.

TeXhackers note: The result is returned within the `\unexpanded` primitive (`\exp_not:n`), which means that the `<items>` do not expand further when appearing in an `x`-type argument expansion.

9 Sequences as stacks

Sequences can be used as stacks, where data is pushed to and popped from the top of the sequence. (The left of a sequence is the top, for performance reasons.) The stack functions for sequences are not intended to be mixed with the general ordered data functions detailed in the previous section: a sequence should either be used as an ordered data type or as a stack, but not in both ways.

<code>\seq_get:NN</code> <code>\seq_get:cn</code>	<code>\seq_get:NN <sequence> <token list variable></code>
Updated: 2012-05-14	Reads the top item from a <code><sequence></code> into the <code><token list variable></code> without removing it from the <code><sequence></code> . The <code><token list variable></code> is assigned locally. If <code><sequence></code> is empty the <code><token list variable></code> is set to the special marker <code>\q_no_value</code> .
<code>\seq_pop:NN</code> <code>\seq_pop:cn</code>	<code>\seq_pop:NN <sequence> <token list variable></code>
Updated: 2012-05-14	Pops the top item from a <code><sequence></code> into the <code><token list variable></code> . Both of the variables are assigned locally. If <code><sequence></code> is empty the <code><token list variable></code> is set to the special marker <code>\q_no_value</code> .
<code>\seq_gpop:NN</code> <code>\seq_gpop:cn</code>	<code>\seq_gpop:NN <sequence> <token list variable></code>
Updated: 2012-05-14	Pops the top item from a <code><sequence></code> into the <code><token list variable></code> . The <code><sequence></code> is modified globally, while the <code><token list variable></code> is assigned locally. If <code><sequence></code> is empty the <code><token list variable></code> is set to the special marker <code>\q_no_value</code> .
<code>\seq_get:NNTF</code> <code>\seq_get:cNTF</code>	<code>\seq_get:NNTF <sequence> <token list variable> {<true code>} {<false code>}</code>
New: 2012-05-14 Updated: 2012-05-19	If the <code><sequence></code> is empty, leaves the <code><false code></code> in the input stream. The value of the <code><token list variable></code> is not defined in this case and should not be relied upon. If the <code><sequence></code> is non-empty, stores the top item from a <code><sequence></code> in the <code><token list variable></code> without removing it from the <code><sequence></code> . The <code><token list variable></code> is assigned locally.

`\seq_pop:NNTF`
`\seq_pop:cNTF`

New: 2012-05-14
Updated: 2012-05-19

`\seq_pop:NNTF <sequence> <token list variable> {\true code} {\false code}`

If the `<sequence>` is empty, leaves the `<false code>` in the input stream. The value of the `<token list variable>` is not defined in this case and should not be relied upon. If the `<sequence>` is non-empty, pops the top item from the `<sequence>` in the `<token list variable>`, *i.e.* removes the item from the `<sequence>`. Both the `<sequence>` and the `<token list variable>` are assigned locally.

`\seq_gpop:NNTF`
`\seq_gpop:cNTF`

New: 2012-05-14
Updated: 2012-05-19

`\seq_gpop:NNTF <sequence> <token list variable> {\true code} {\false code}`

If the `<sequence>` is empty, leaves the `<false code>` in the input stream. The value of the `<token list variable>` is not defined in this case and should not be relied upon. If the `<sequence>` is non-empty, pops the top item from the `<sequence>` in the `<token list variable>`, *i.e.* removes the item from the `<sequence>`. The `<sequence>` is modified globally, while the `<token list variable>` is assigned locally.

`\seq_push:Nn`
`\seq_push:(NV|Nv|No|Nx|cn|cV|cv|co|cx)`
`\seq_gpush:Nn`
`\seq_gpush:(NV|Nv|No|Nx|cn|cV|cv|co|cx)`

`\seq_push:Nn <sequence> {\item}`

Adds the `{\item}` to the top of the `<sequence>`.

10 Sequences as sets

Sequences can also be used as sets, such that all of their items are distinct. Usage of sequences as sets is not currently widespread, hence no specific set function is provided. Instead, it is explained here how common set operations can be performed by combining several functions described in earlier sections. When using sequences to implement sets, one should be careful not to rely on the order of items in the sequence representing the set.

Sets should not contain several occurrences of a given item. To make sure that a `<sequence variable>` only has distinct items, use `\seq_remove_duplicates:N <sequence variable>`. This function is relatively slow, and to avoid performance issues one should only use it when necessary.

Some operations on a set `<seq var>` are straightforward. For instance, `\seq_count:N <seq var>` expands to the number of items, while `\seq_if_in:NnTF <seq var> {\item}` tests if the `<item>` is in the set.

Adding an `<item>` to a set `<seq var>` can be done by appending it to the `<seq var>` if it is not already in the `<seq var>`:

```
\seq_if_in:NnF <seq var> {\item}
{ \seq_put_right:Nn <seq var> {\item} }
```

Removing an `<item>` from a set `<seq var>` can be done using `\seq_remove_all:Nn`,

```
\seq_remove_all:Nn <seq var> {\item}
```

The intersection of two sets `<seq var1 and <seq var2 can be stored into <seq var3 by collecting items of <seq var1 which are in <seq var2.`

```

\seq_clear:N <seq var3>
\seq_map_inline:Nn <seq var1>
{
\seq_if_in:NnT <seq var2> {#1}
{ \seq_put_right:Nn <seq var3> {#1} }
}

```

The code as written here only works if $\langle seq\ var_3 \rangle$ is different from the other two sequence variables. To cover all cases, items should first be collected in a sequence $\backslash l_ \langle pkg \rangle_internal_seq$, then $\langle seq\ var_3 \rangle$ should be set equal to this internal sequence. The same remark applies to other set functions.

The union of two sets $\langle seq\ var_1 \rangle$ and $\langle seq\ var_2 \rangle$ can be stored into $\langle seq\ var_3 \rangle$ through

```

\seq_concat:NNN <seq var3> <seq var1> <seq var2>
\seq_remove_duplicates:N <seq var3>

```

or by adding items to (a copy of) $\langle seq\ var_1 \rangle$ one by one

```

\seq_set_eq:NN <seq var3> <seq var1>
\seq_map_inline:Nn <seq var2>
{
\seq_if_in:NnF <seq var3> {#1}
{ \seq_put_right:Nn <seq var3> {#1} }
}

```

The second approach is faster than the first when the $\langle seq\ var_2 \rangle$ is short compared to $\langle seq\ var_1 \rangle$.

The difference of two sets $\langle seq\ var_1 \rangle$ and $\langle seq\ var_2 \rangle$ can be stored into $\langle seq\ var_3 \rangle$ by removing items of the $\langle seq\ var_2 \rangle$ from (a copy of) the $\langle seq\ var_1 \rangle$ one by one.

```

\seq_set_eq:NN <seq var3> <seq var1>
\seq_map_inline:Nn <seq var2>
{ \seq_remove_all:Nn <seq var3> {#1} }

```

The symmetric difference of two sets $\langle seq\ var_1 \rangle$ and $\langle seq\ var_2 \rangle$ can be stored into $\langle seq\ var_3 \rangle$ by computing the difference between $\langle seq\ var_1 \rangle$ and $\langle seq\ var_2 \rangle$ and storing the result as $\backslash l_ \langle pkg \rangle_internal_seq$, then the difference between $\langle seq\ var_2 \rangle$ and $\langle seq\ var_1 \rangle$, and finally concatenating the two differences to get the symmetric differences.

```

\seq_set_eq:NN \l\_ \langle pkg \rangle\_internal\_seq <seq var1>
\seq_map_inline:Nn <seq var2>
{ \seq_remove_all:Nn \l\_ \langle pkg \rangle\_internal\_seq {#1} }
\seq_set_eq:NN <seq var3> <seq var2>
\seq_map_inline:Nn <seq var1>
{ \seq_remove_all:Nn <seq var3> {#1} }
\seq_concat:NNN <seq var3> <seq var3> \l\_ \langle pkg \rangle\_internal\_seq

```

11 Constant and scratch sequences

$\backslash c_empty_seq$

Constant that is always empty.

New: 2012-07-02

`\l_tmpa_seq`
`\l_tmpb_seq`

New: 2012-04-26

Scratch sequences for local assignment. These are never used by the kernel code, and so are safe for use with any L^AT_EX3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.

`\g_tmpa_seq`
`\g_tmpb_seq`

New: 2012-04-26

Scratch sequences for global assignment. These are never used by the kernel code, and so are safe for use with any L^AT_EX3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.

12 Viewing sequences

`\seq_show:N`
`\seq_show:c`

Updated: 2015-08-01

`\seq_show:N` $\langle sequence \rangle$
Displays the entries in the $\langle sequence \rangle$ in the terminal.

`\seq_log:N`
`\seq_log:c`

New: 2014-08-12
Updated: 2015-08-01

`\seq_log:N` $\langle sequence \rangle$
Writes the entries in the $\langle sequence \rangle$ in the log file.

13 Internal sequence functions

`\s__seq`

This scan mark (equal to `\scan_stop:`) marks the beginning of a sequence variable.

`__seq_item:n` ★

`__seq_item:n` $\{\langle item \rangle\}$

The internal token used to begin each sequence entry. If expanded outside of a mapping or manipulation function, an error is raised. The definition should always be set globally.

`__seq_push_item_def:n`
`__seq_push_item_def:x`

`__seq_push_item_def:n` $\{\langle code \rangle\}$

Saves the definition of `__seq_item:n` and redefines it to accept one parameter and expand to $\langle code \rangle$. This function should always be balanced by use of `__seq_pop_item_def:`.

`__seq_pop_item_def:`

`__seq_pop_item_def:`

Restores the definition of `__seq_item:n` most recently saved by `__seq_push_item_def:n`. This function should always be used in a balanced pair with `__seq_push_item_def:n`.

Part IX

The l3int package

Integers

Calculation and comparison of integer values can be carried out using literal numbers, `int` registers, constants and integers stored in token list variables. The standard operators `+`, `-`, `/` and `*` and parentheses can be used within such expressions to carry arithmetic operations. This module carries out these functions on *integer expressions* (“`intexpr`”).

1 Integer expressions

<code>\int_eval:n</code>	★	<code>\int_eval:n {⟨integer expression⟩}</code>
--------------------------	---	---

Evaluates the *⟨integer expression⟩*, expanding any integer and token list variables within the *⟨expression⟩* to their content (without requiring `\int_use:N/\tl_use:N`) and applying the standard mathematical rules. For example both

```
\int_eval:n { 5 + 4 * 3 - ( 3 + 4 * 5 ) }
```

and

```
\tl_new:N \l_my_tl
\tl_set:Nn \l_my_tl { 5 }
\int_new:N \l_my_int
\int_set:Nn \l_my_int { 4 }
\int_eval:n { \l_my_tl + \l_my_int * 3 - ( 3 + 4 * 5 ) }
```

both evaluate to -6 . The *⟨integer expression⟩* may contain the operators `+`, `-`, `*` and `/`, along with parenthesis `(` and `)`. Any functions within the expressions should expand to an *⟨integer denotation⟩*: a sequence of a sign and digits matching the regex `\-?[0-9]+`. After expansion `\int_eval:n` yields an *⟨integer denotation⟩* which is left in the input stream.

T_EXhackers note: Exactly two expansions are needed to evaluate `\int_eval:n`. The result is *not* an *⟨internal integer⟩*, and therefore requires suitable termination if used in a T_EX-style integer assignment.

<code>\int_abs:n</code>	★	<code>\int_abs:n {⟨integer expression⟩}</code>
-------------------------	---	--

Updated: 2012-09-26

Evaluates the *⟨integer expression⟩* as described for `\int_eval:n` and leaves the absolute value of the result in the input stream as an *⟨integer denotation⟩* after two expansions.

<code>\int_div_round:nn</code>	★	<code>\int_div_round:nn {⟨intexpr₁⟩} {⟨intexpr₂⟩}</code>
--------------------------------	---	--

Updated: 2012-09-26

Evaluates the two *⟨integer expressions⟩* as described earlier, then divides the first value by the second, and rounds the result to the closest integer. Ties are rounded away from zero. Note that this is identical to using `/` directly in an *⟨integer expression⟩*. The result is left in the input stream as an *⟨integer denotation⟩* after two expansions.

<hr/> <code>\int_div_truncate:nn</code> ★ <hr/>	<code>\int_div_truncate:nn {\langle integer_1 \rangle} {\langle integer_2 \rangle}</code>
Updated: 2012-02-09	Evaluates the two $\langle integer expressions \rangle$ as described earlier, then divides the first value by the second, and rounds the result towards zero. Note that division using <code>/</code> rounds to the closest integer instead. The result is left in the input stream as an $\langle integer denotation \rangle$ after two expansions.

<hr/> <code>\int_max:nn</code> ★	<code>\int_max:nn {\langle integer_1 \rangle} {\langle integer_2 \rangle}</code>
<hr/> <code>\int_min:nn</code> ★	<code>\int_min:nn {\langle integer_1 \rangle} {\langle integer_2 \rangle}</code>
Updated: 2012-09-26	Evaluates the $\langle integer expressions \rangle$ as described for <code>\int_eval:n</code> and leaves either the larger or smaller value in the input stream as an $\langle integer denotation \rangle$ after two expansions.

<hr/> <code>\int_mod:nn</code> ★	<code>\int_mod:nn {\langle integer_1 \rangle} {\langle integer_2 \rangle}</code>
Updated: 2012-09-26	Evaluates the two $\langle integer expressions \rangle$ as described earlier, then calculates the integer remainder of dividing the first expression by the second. This is obtained by subtracting <code>\int_div_truncate:nn {\langle integer_1 \rangle} {\langle integer_2 \rangle}</code> times $\langle integer_2 \rangle$ from $\langle integer_1 \rangle$. Thus, the result has the same sign as $\langle integer_1 \rangle$ and its absolute value is strictly less than that of $\langle integer_2 \rangle$. The result is left in the input stream as an $\langle integer denotation \rangle$ after two expansions.

2 Creating and initialising integers

<hr/> <code>\int_new:N</code>	<code>\int_new:N \langle integer \rangle</code>
<hr/> <code>\int_new:c</code>	Creates a new $\langle integer \rangle$ or raises an error if the name is already taken. The declaration is global. The $\langle integer \rangle$ is initially equal to 0.

<hr/> <code>\int_const:Nn</code>	<code>\int_const:Nn \langle integer \rangle {\langle integer expression \rangle}</code>
<hr/> <code>\int_const:cn</code>	Creates a new constant $\langle integer \rangle$ or raises an error if the name is already taken. The value of the $\langle integer \rangle$ is set globally to the $\langle integer expression \rangle$.
Updated: 2011-10-22	

<hr/> <code>\int_zero:N</code>	<code>\int_zero:N \langle integer \rangle</code>
<hr/> <code>\int_zero:c</code>	Sets $\langle integer \rangle$ to 0.
<hr/> <code>\int_gzero:N</code>	
<hr/> <code>\int_gzero:c</code>	

<hr/> <code>\int_zero_new:N</code>	<code>\int_zero_new:N \langle integer \rangle</code>
<hr/> <code>\int_zero_new:c</code>	Ensures that the $\langle integer \rangle$ exists globally by applying <code>\int_new:N</code> if necessary, then applies <code>\int_(g)zero:N</code> to leave the $\langle integer \rangle$ set to zero.
<hr/> <code>\int_gzero_new:N</code>	
<hr/> <code>\int_gzero_new:c</code>	
New: 2011-12-13	

<hr/> <code>\int_set_eq:NN</code>	<code>\int_set_eq:NN \langle integer_1 \rangle \langle integer_2 \rangle</code>
<hr/> <code>\int_set_eq:(cN Nc cc)</code>	Sets the content of $\langle integer_1 \rangle$ equal to that of $\langle integer_2 \rangle$.
<hr/> <code>\int_gset_eq:NN</code>	
<hr/> <code>\int_gset_eq:(cN Nc cc)</code>	

<code>\int_if_exist_p:N</code>	★	<code>\int_if_exist_p:N</code>	$\langle integer \rangle$
<code>\int_if_exist_p:c</code>	★	<code>\int_if_exist:NTF</code>	$\langle integer \rangle$ <code>{\true code}</code> <code>{\false code}</code>
<code>\int_if_exist:NTF</code>	★	Tests whether the $\langle integer \rangle$ is currently defined. This does not check that the $\langle integer \rangle$ really is an integer variable.	
<code>\int_if_exist:cTF</code>	★		

New: 2012-03-03

3 Setting and incrementing integers

<code>\int_add:Nn</code>	<code>\int_add:Nn</code>	$\langle integer \rangle$ <code>{\integer expression}</code>
<code>\int_add:cn</code>	Adds the result of the $\langle integer expression \rangle$ to the current content of the $\langle integer \rangle$.	
<code>\int_gadd:Nn</code>		
<code>\int_gadd:cn</code>		

Updated: 2011-10-22

<code>\int_decr:N</code>	<code>\int_decr:N</code>	$\langle integer \rangle$
<code>\int_decr:c</code>	Decreases the value stored in $\langle integer \rangle$ by 1.	
<code>\int_gdecr:N</code>		
<code>\int_gdecr:c</code>		

<code>\int_incr:N</code>	<code>\int_incr:N</code>	$\langle integer \rangle$
<code>\int_incr:c</code>	Increases the value stored in $\langle integer \rangle$ by 1.	
<code>\int_gincr:N</code>		
<code>\int_gincr:c</code>		

<code>\int_set:Nn</code>	<code>\int_set:Nn</code>	$\langle integer \rangle$ <code>{\integer expression}</code>
<code>\int_set:cn</code>	Sets $\langle integer \rangle$ to the value of $\langle integer expression \rangle$, which must evaluate to an integer (as described for <code>\int_eval:n</code>).	
<code>\int_gset:Nn</code>		
<code>\int_gset:cn</code>		

Updated: 2011-10-22

<code>\int_sub:Nn</code>	<code>\int_sub:Nn</code>	$\langle integer \rangle$ <code>{\integer expression}</code>
<code>\int_sub:cn</code>	Subtracts the result of the $\langle integer expression \rangle$ from the current content of the $\langle integer \rangle$.	
<code>\int_gsub:Nn</code>		
<code>\int_gsub:cn</code>		

Updated: 2011-10-22

4 Using integers

<code>\int_use:N</code>	★	<code>\int_use:N</code> $\langle integer \rangle$
<code>\int_use:c</code>	★	Recovers the content of an $\langle integer \rangle$ and places it directly in the input stream. An error is raised if the variable does not exist or if it is invalid. Can be omitted in places where an $\langle integer \rangle$ is required (such as in the first and third arguments of <code>\int_compare:nNTF</code>).
Updated: 2011-10-22		

TeXhackers note: `\int_use:N` is the TeX primitive `\the`: this is one of several L^AT_EX3 names for this primitive.

5 Integer expression conditionals

```
\int_compare_p:nNn ★ \int_compare_p:nNn {\langle intexpr_1 \rangle} \langle relation \rangle {\langle intexpr_2 \rangle}
\int_compare:nNnTF ★ \int_compare:nNnTF
                        {\langle intexpr_1 \rangle} \langle relation \rangle {\langle intexpr_2 \rangle}
                        {\langle true code \rangle} {\langle false code \rangle}
```

This function first evaluates each of the $\langle integer expressions \rangle$ as described for `\int_eval:n`. The two results are then compared using the $\langle relation \rangle$:

Equal	=
Greater than	>
Less than	<

```
\int_compare_p:n ★ \int_compare_p:n
\int_compare:nTF ★ {
                    \langle intexpr_1 \rangle \langle relation_1 \rangle
                    ...
                    \langle intexpr_N \rangle \langle relation_N \rangle
                    \langle intexpr_{N+1} \rangle
                }
\int_compare:nTF
{
    \langle intexpr_1 \rangle \langle relation_1 \rangle
    ...
    \langle intexpr_N \rangle \langle relation_N \rangle
    \langle intexpr_{N+1} \rangle
}
{\langle true code \rangle} {\langle false code \rangle}
```

Updated: 2013-01-13

This function evaluates the $\langle integer expressions \rangle$ as described for `\int_eval:n` and compares consecutive result using the corresponding $\langle relation \rangle$, namely it compares $\langle intexpr_1 \rangle$ and $\langle intexpr_2 \rangle$ using the $\langle relation_1 \rangle$, then $\langle intexpr_2 \rangle$ and $\langle intexpr_3 \rangle$ using the $\langle relation_2 \rangle$, until finally comparing $\langle intexpr_N \rangle$ and $\langle intexpr_{N+1} \rangle$ using the $\langle relation_N \rangle$. The test yields **true** if all comparisons are **true**. Each $\langle integer expression \rangle$ is evaluated only once, and the evaluation is lazy, in the sense that if one comparison is **false**, then no other $\langle integer expression \rangle$ is evaluated and no other comparison is performed. The $\langle relations \rangle$ can be any of the following:

Equal	= or ==
Greater than or equal to	>=
Greater than	>
Less than or equal to	<=
Less than	<
Not equal	!=

<code>\int_case:nn</code> ★	<code>\int_case:nnTF {⟨test integer expression⟩}</code>
<code>\int_case:nnTF</code> ★	<code>{</code>
	<code>{⟨intexpr case₁⟩} {⟨code case₁⟩}</code>
	<code>{⟨intexpr case₂⟩} {⟨code case₂⟩}</code>
	<code>...</code>
	<code>{⟨intexpr case_n⟩} {⟨code case_n⟩}</code>
	<code>}</code>
	<code>{⟨true code⟩}</code>
	<code>{⟨false code⟩}</code>

New: 2013-07-24

This function evaluates the *⟨test integer expression⟩* and compares this in turn to each of the *⟨integer expression cases⟩*. If the two are equal then the associated *⟨code⟩* is left in the input stream and other cases are discarded. If any of the cases are matched, the *⟨true code⟩* is also inserted into the input stream (after the code for the appropriate case), while if none match then the *⟨false code⟩* is inserted. The function `\int_case:nn`, which does nothing if there is no match, is also available. For example

```
\int_case:nnF
{ 2 * 5 }
{
  { 5 }      { Small }
  { 4 + 6 }   { Medium }
  { -2 * 10 } { Negative }
}
{ No idea! }
```

leaves “Medium” in the input stream.

<code>\int_if_even_p:n</code> ★	<code>\int_if_odd_p:n {⟨integer expression⟩}</code>
<code>\int_if_even:nTF</code> ★	<code>\int_if_odd:nTF {⟨integer expression⟩}</code>
<code>\int_if_odd_p:n</code> ★	<code>{⟨true code⟩} {⟨false code⟩}</code>
<code>\int_if_odd:nTF</code> ★	

This function first evaluates the *⟨integer expression⟩* as described for `\int_eval:n`. It then evaluates if this is odd or even, as appropriate.

6 Integer expression loops

<code>\int_do_until:nNnn</code> ☆	<code>\int_do_until:nNnn {⟨intexpr₁⟩} ⟨relation⟩ {⟨intexpr₂⟩} {⟨code⟩}</code>
-----------------------------------	---

Places the *⟨code⟩* in the input stream for T_EX to process, and then evaluates the relationship between the two *⟨integer expressions⟩* as described for `\int_compare:nNnTF`. If the test is **false** then the *⟨code⟩* is inserted into the input stream again and a loop occurs until the *⟨relation⟩* is **true**.

<code>\int_do_while:nNnn</code> ☆	<code>\int_do_while:nNnn {⟨intexpr₁⟩} ⟨relation⟩ {⟨intexpr₂⟩} {⟨code⟩}</code>
-----------------------------------	---

Places the *⟨code⟩* in the input stream for T_EX to process, and then evaluates the relationship between the two *⟨integer expressions⟩* as described for `\int_compare:nNnTF`. If the test is **true** then the *⟨code⟩* is inserted into the input stream again and a loop occurs until the *⟨relation⟩* is **false**.

<hr/> <code>\int_until_do:nNnn</code> ☆ <hr/>	<code>\int_until_do:nNnn {⟨intexpr₁⟩} ⟨relation⟩ {⟨intexpr₂⟩} {⟨code⟩}</code>
	Evaluates the relationship between the two <i>⟨integer expressions⟩</i> as described for <code>\int_compare:nNnTF</code> , and then places the <i>⟨code⟩</i> in the input stream if the <i>⟨relation⟩</i> is false . After the <i>⟨code⟩</i> has been processed by T _E X the test is repeated, and a loop occurs until the test is true .
<hr/> <code>\int_while_do:nNnn</code> ☆ <hr/>	<code>\int_while_do:nNnn {⟨intexpr₁⟩} ⟨relation⟩ {⟨intexpr₂⟩} {⟨code⟩}</code>
	Evaluates the relationship between the two <i>⟨integer expressions⟩</i> as described for <code>\int_compare:nNnTF</code> , and then places the <i>⟨code⟩</i> in the input stream if the <i>⟨relation⟩</i> is true . After the <i>⟨code⟩</i> has been processed by T _E X the test is repeated, and a loop occurs until the test is false .
<hr/> <code>\int_do_until:nn</code> ☆ <hr/>	<code>\int_do_until:nn {⟨integer relation⟩} {⟨code⟩}</code>
Updated: 2013-01-13	Places the <i>⟨code⟩</i> in the input stream for T _E X to process, and then evaluates the <i>⟨integer relation⟩</i> as described for <code>\int_compare:nTF</code> . If the test is false then the <i>⟨code⟩</i> is inserted into the input stream again and a loop occurs until the <i>⟨relation⟩</i> is true .
<hr/> <code>\int_do_while:nn</code> ☆ <hr/>	<code>\int_do_while:nn {⟨integer relation⟩} {⟨code⟩}</code>
Updated: 2013-01-13	Places the <i>⟨code⟩</i> in the input stream for T _E X to process, and then evaluates the <i>⟨integer relation⟩</i> as described for <code>\int_compare:nTF</code> . If the test is true then the <i>⟨code⟩</i> is inserted into the input stream again and a loop occurs until the <i>⟨relation⟩</i> is false .
<hr/> <code>\int_until_do:nn</code> ☆ <hr/>	<code>\int_until_do:nn {⟨integer relation⟩} {⟨code⟩}</code>
Updated: 2013-01-13	Evaluates the <i>⟨integer relation⟩</i> as described for <code>\int_compare:nTF</code> , and then places the <i>⟨code⟩</i> in the input stream if the <i>⟨relation⟩</i> is false . After the <i>⟨code⟩</i> has been processed by T _E X the test is repeated, and a loop occurs until the test is true .
<hr/> <code>\int_while_do:nn</code> ☆ <hr/>	<code>\int_while_do:nn {⟨integer relation⟩} {⟨code⟩}</code>
Updated: 2013-01-13	Evaluates the <i>⟨integer relation⟩</i> as described for <code>\int_compare:nTF</code> , and then places the <i>⟨code⟩</i> in the input stream if the <i>⟨relation⟩</i> is true . After the <i>⟨code⟩</i> has been processed by T _E X the test is repeated, and a loop occurs until the test is false .

7 Integer step functions

`\int_step_function:nnnN` ★

New: 2012-06-04

Updated: 2014-05-30

`\int_step_function:nnnN` $\langle initial\ value \rangle$ $\langle step \rangle$ $\langle final\ value \rangle$ $\langle function \rangle$

This function first evaluates the $\langle initial\ value \rangle$, $\langle step \rangle$ and $\langle final\ value \rangle$, all of which should be integer expressions. The $\langle function \rangle$ is then placed in front of each $\langle value \rangle$ from the $\langle initial\ value \rangle$ to the $\langle final\ value \rangle$ in turn (using $\langle step \rangle$ between each $\langle value \rangle$). The $\langle step \rangle$ must be non-zero. If the $\langle step \rangle$ is positive, the loop stops when the $\langle value \rangle$ becomes larger than the $\langle final\ value \rangle$. If the $\langle step \rangle$ is negative, the loop stops when the $\langle value \rangle$ becomes smaller than the $\langle final\ value \rangle$. The $\langle function \rangle$ should absorb one numerical argument. For example

```
\cs_set:Npn \my_func:n #1 { [I~saw~#1] \quad }
\int_step_function:nnnN { 1 } { 1 } { 5 } \my_func:n
```

would print

```
[I saw 1] [I saw 2] [I saw 3] [I saw 4] [I saw 5]
```

`\int_step_inline:nnnn`

New: 2012-06-04

Updated: 2014-05-30

`\int_step_inline:nnnn` $\langle initial\ value \rangle$ $\langle step \rangle$ $\langle final\ value \rangle$ $\langle code \rangle$

This function first evaluates the $\langle initial\ value \rangle$, $\langle step \rangle$ and $\langle final\ value \rangle$, all of which should be integer expressions. Then for each $\langle value \rangle$ from the $\langle initial\ value \rangle$ to the $\langle final\ value \rangle$ in turn (using $\langle step \rangle$ between each $\langle value \rangle$), the $\langle code \rangle$ is inserted into the input stream with `#1` replaced by the current $\langle value \rangle$. Thus the $\langle code \rangle$ should define a function of one argument (`#1`).

`\int_step_variable:nnnNn`

New: 2012-06-04

Updated: 2014-05-30

`\int_step_variable:nnnNn`
 $\langle initial\ value \rangle$ $\langle step \rangle$ $\langle final\ value \rangle$ $\langle tl\ var \rangle$ $\langle code \rangle$

This function first evaluates the $\langle initial\ value \rangle$, $\langle step \rangle$ and $\langle final\ value \rangle$, all of which should be integer expressions. Then for each $\langle value \rangle$ from the $\langle initial\ value \rangle$ to the $\langle final\ value \rangle$ in turn (using $\langle step \rangle$ between each $\langle value \rangle$), the $\langle code \rangle$ is inserted into the input stream, with the $\langle tl\ var \rangle$ defined as the current $\langle value \rangle$. Thus the $\langle code \rangle$ should make use of the $\langle tl\ var \rangle$.

8 Formatting integers

Integers can be placed into the output stream with formatting. These conversions apply to any integer expressions.

`\int_to_arabic:n` ★

Updated: 2011-10-22

`\int_to_arabic:n` $\langle integer\ expression \rangle$

Places the value of the $\langle integer\ expression \rangle$ in the input stream as digits, with category code 12 (other).

<code>\int_to_alph:n</code> ★	<code>\int_to_alph:n {⟨integer expression⟩}</code>
-------------------------------	--

<code>\int_to_Alph:n</code> ★

Updated: 2011-09-17

Evaluates the *⟨integer expression⟩* and converts the result into a series of letters, which are then left in the input stream. The conversion rule uses the 26 letters of the English alphabet, in order, adding letters when necessary to increase the total possible range of representable numbers. Thus

```
\int_to_alph:n { 1 }
```

places **a** in the input stream,

```
\int_to_alph:n { 26 }
```

is represented as **z** and

```
\int_to_alph:n { 27 }
```

is converted to **aa**. For conversions using other alphabets, use `\int_to_symbols:nnn` to define an alphabet-specific function. The basic `\int_to_alph:n` and `\int_to_Alph:n` functions should not be modified. The resulting tokens are digits with category code 12 (other) and letters with category code 11 (letter).

<code>\int_to_symbols:nnn</code> ★

Updated: 2011-09-17

```
\int_to_symbols:nnn
  {⟨integer expression⟩} {⟨total symbols⟩}
  {⟨value to symbol mapping⟩}
```

This is the low-level function for conversion of an *⟨integer expression⟩* into a symbolic form (often letters). The *⟨total symbols⟩* available should be given as an integer expression. Values are actually converted to symbols according to the *⟨value to symbol mapping⟩*. This should be given as *⟨total symbols⟩* pairs of entries, a number and the appropriate symbol. Thus the `\int_to_alph:n` function is defined as

```
\cs_new:Npn \int_to_alph:n #1
{
  \int_to_symbols:nnn {#1} { 26 }
  {
    { 1 } { a }
    { 2 } { b }
    ...
    { 26 } { z }
  }
}
```

<code>\int_to_bin:n</code> ★

New: 2014-02-11

```
\int_to_bin:n {⟨integer expression⟩}
```

Calculates the value of the *⟨integer expression⟩* and places the binary representation of the result in the input stream.

<code>\int_to_hex:n</code> ★	<code>\int_to_hex:n {⟨integer expression⟩}</code>
<code>\int_to_Hex:n</code> ★	Calculates the value of the <i>⟨integer expression⟩</i> and places the hexadecimal (base 16) representation of the result in the input stream. Letters are used for digits beyond 9: lower case letters for <code>\int_to_hex:n</code> and upper case ones for <code>\int_to_Hex:n</code> . The resulting tokens are digits with category code 12 (other) and letters with category code 11 (letter).
New: 2014-02-11	

<code>\int_to_oct:n</code> ★	<code>\int_to_oct:n {⟨integer expression⟩}</code>
New: 2014-02-11	
	Calculates the value of the <i>⟨integer expression⟩</i> and places the octal (base 8) representation of the result in the input stream. The resulting tokens are digits with category code 12 (other) and letters with category code 11 (letter).

<code>\int_to_base:nn</code> ★	<code>\int_to_base:nn {⟨integer expression⟩} {⟨base⟩}</code>
<code>\int_to_Base:nn</code> ★	Calculates the value of the <i>⟨integer expression⟩</i> and converts it into the appropriate representation in the <i>⟨base⟩</i> ; the later may be given as an integer expression. For bases greater than 10 the higher “digits” are represented by letters from the English alphabet: lower case letters for <code>\int_to_base:n</code> and upper case ones for <code>\int_to_Base:n</code> . The maximum <i>⟨base⟩</i> value is 36. The resulting tokens are digits with category code 12 (other) and letters with category code 11 (letter).
Updated: 2014-02-11	

TeXhackers note: This is a generic version of `\int_to_bin:n`, etc.

<code>\int_to_roman:n</code> ☆	<code>\int_to_roman:n {⟨integer expression⟩}</code>
<code>\int_to_Roman:n</code> ☆	Places the value of the <i>⟨integer expression⟩</i> in the input stream as Roman numerals, either lower case (<code>\int_to_roman:n</code>) or upper case (<code>\int_to_Roman:n</code>). The Roman numerals are letters with category code 11 (letter).
Updated: 2011-10-22	

9 Converting from other formats to integers

<code>\int_from_alph:n</code> ★	<code>\int_from_alph:n {⟨letters⟩}</code>
Updated: 2014-08-25	
	Converts the <i>⟨letters⟩</i> into the integer (base 10) representation and leaves this in the input stream. The <i>⟨letters⟩</i> are first converted to a string, with no expansion. Lower and upper case letters from the English alphabet may be used, with “a” equal to 1 through to “z” equal to 26. The function also accepts a leading sign, made of + and -. This is the inverse function of <code>\int_to_alph:n</code> and <code>\int_to_Alph:n</code> .

<code>\int_from_bin:n</code> ★	<code>\int_from_bin:n {⟨binary number⟩}</code>
New: 2014-02-11	
Updated: 2014-08-25	
	Converts the <i>⟨binary number⟩</i> into the integer (base 10) representation and leaves this in the input stream. The <i>⟨binary number⟩</i> is first converted to a string, with no expansion. The function accepts a leading sign, made of + and -, followed by binary digits. This is the inverse function of <code>\int_to_bin:n</code> .

<hr/> <code>\int_from_hex:n</code> ★ <hr/>	<code>\int_from_hex:n {⟨hexadecimal number⟩}</code>
New: 2014-02-11 Updated: 2014-08-25 <hr/>	Converts the <i>⟨hexadecimal number⟩</i> into the integer (base 10) representation and leaves this in the input stream. Digits greater than 9 may be represented in the <i>⟨hexadecimal number⟩</i> by upper or lower case letters. The <i>⟨hexadecimal number⟩</i> is first converted to a string, with no expansion. The function also accepts a leading sign, made of + and -. This is the inverse function of <code>\int_to_hex:n</code> and <code>\int_to_Hex:n</code> .
<hr/> <code>\int_from_oct:n</code> ★ <hr/>	<code>\int_from_oct:n {⟨octal number⟩}</code>
New: 2014-02-11 Updated: 2014-08-25 <hr/>	Converts the <i>⟨octal number⟩</i> into the integer (base 10) representation and leaves this in the input stream. The <i>⟨octal number⟩</i> is first converted to a string, with no expansion. The function accepts a leading sign, made of + and -, followed by octal digits. This is the inverse function of <code>\int_to_oct:n</code> .
<hr/> <code>\int_from_roman:n</code> ★ <hr/>	<code>\int_from_roman:n {⟨roman numeral⟩}</code>
Updated: 2014-08-25 <hr/>	Converts the <i>⟨roman numeral⟩</i> into the integer (base 10) representation and leaves this in the input stream. The <i>⟨roman numeral⟩</i> is first converted to a string, with no expansion. The <i>⟨roman numeral⟩</i> may be in upper or lower case; if the numeral contains characters besides <i>mdclxvi</i> or <i>MDCLXVI</i> then the resulting value is -1. This is the inverse function of <code>\int_to_roman:n</code> and <code>\int_to_Roman:n</code> .
<hr/> <code>\int_from_base:nn</code> ★ <hr/>	<code>\int_from_base:nn {⟨number⟩} {⟨base⟩}</code>
Updated: 2014-08-25 <hr/>	Converts the <i>⟨number⟩</i> expressed in <i>⟨base⟩</i> into the appropriate value in base 10. The <i>⟨number⟩</i> is first converted to a string, with no expansion. The <i>⟨number⟩</i> should consist of digits and letters (either lower or upper case), plus optionally a leading sign. The maximum <i>⟨base⟩</i> value is 36. This is the inverse function of <code>\int_to_base:nn</code> and <code>\int_to_Base:nn</code> .

10 Viewing integers

<hr/> <code>\int_show:N</code> <code>\int_show:c</code> <hr/>	<code>\int_show:N ⟨integer⟩</code>
	Displays the value of the <i>⟨integer⟩</i> on the terminal.
<hr/> <code>\int_show:n</code> <hr/>	<code>\int_show:n {⟨integer expression⟩}</code>
New: 2011-11-22 Updated: 2015-08-07 <hr/>	Displays the result of evaluating the <i>⟨integer expression⟩</i> on the terminal.
<hr/> <code>\int_log:N</code> <code>\int_log:c</code> <hr/>	<code>\int_log:N ⟨integer⟩</code>
New: 2014-08-22 Updated: 2015-08-03 <hr/>	Writes the value of the <i>⟨integer⟩</i> in the log file.
<hr/> <code>\int_log:n</code> <hr/>	<code>\int_log:n {⟨integer expression⟩}</code>
New: 2014-08-22 Updated: 2015-08-07 <hr/>	Writes the result of evaluating the <i>⟨integer expression⟩</i> in the log file.

11 Constant integers

`\c_zero`
`\c_one`
`\c_two`
`\c_three`
`\c_four`
`\c_five`
`\c_six`
`\c_seven`
`\c_eight`
`\c_nine`
`\c_ten`
`\c_eleven`
`\c_twelve`
`\c_thirteen`
`\c_fourteen`
`\c_fifteen`
`\c_sixteen`
`\c_thirty_two`
`\c_one_hundred`
`\c_two_hundred_fifty_five`
`\c_two_hundred_fifty_six`
`\c_one_thousand`
`\c_ten_thousand`

Integer values used with primitive tests and assignments: self-terminating nature makes these more convenient and faster than literal numbers.

`\c_max_int`

The maximum value that can be stored as an integer.

`\c_max_register_int`

Maximum number of registers.

`\c_max_char_int`

Maximum character code completely supported by the engine.

12 Scratch integers

`\l_tmpa_int`
`\l_tmpb_int`

Scratch integer for local assignment. These are never used by the kernel code, and so are safe for use with any L^AT_EX3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.

`\g_tmpa_int`
`\g_tmpb_int`

Scratch integer for global assignment. These are never used by the kernel code, and so are safe for use with any L^AT_EX3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.

13 Primitive conditionals

<code>\if_int_compare:w</code>	★	<code>\if_int_compare:w</code>	<code><integer₁></code>	<code><relation></code>	<code><integer₂></code>
			<code><true code></code>		
		<code>\else:</code>			
			<code><false code></code>		
		<code>\fi:</code>			

Compare two integers using `<relation>`, which must be one of =, < or > with category code 12. The `\else:` branch is optional.

T_EXhackers note: These are both names for the T_EX primitive `\ifnum`.

<code>\if_case:w</code>	★	<code>\if_case:w</code>	<code><integer></code>	<code><case₀></code>
<code>\or:</code>	★	<code>\or:</code>	<code><case₁></code>	
		<code>\or:</code>	<code>...</code>	
		<code>\else:</code>	<code><default></code>	
		<code>\fi:</code>		

Selects a case to execute based on the value of the `<integer>`. The first case (`<case0>`) is executed if `<integer>` is 0, the second (`<case1>`) if the `<integer>` is 1, *etc.* The `<integer>` may be a literal, a constant or an integer expression (*e.g.* using `\int_eval:n`).

T_EXhackers note: These are the T_EX primitives `\ifcase` and `\or`.

<code>\if_int_odd:w</code>	★	<code>\if_int_odd:w</code>	<code><tokens></code>	<code><optional space></code>
			<code><true code></code>	
		<code>\else:</code>		
			<code><true code></code>	
		<code>\fi:</code>		

Expands `<tokens>` until a non-numeric token or a space is found, and tests whether the resulting `<integer>` is odd. If so, `<true code>` is executed. The `\else:` branch is optional.

T_EXhackers note: This is the T_EX primitive `\ifodd`.

14 Internal functions

<code>__int_value:w</code> ★	<code>__int_value:w</code> $\langle integer \rangle$
	<code>__int_value:w</code> $\langle integer\ denotation \rangle$ $\langle optional\ space \rangle$

Expands the following tokens until an $\langle integer \rangle$ is formed, and leaves a normalized form (no leading sign except for negative numbers, no leading digit 0 except for zero) in the input stream as category code 12 (other) characters. The $\langle integer \rangle$ can consist of any number of signs (with intervening spaces) followed by

- an integer variable (in fact, any \TeX register except `\toks`) or
- `__int_eval:w` $\langle intexpr \rangle$ `__int_eval_end:` (or another $\varepsilon\text{-TeX}$ expression) or
- explicit digits (or by `'` $\langle octal\ digits \rangle$ or `"` $\langle hexadecimal\ digits \rangle$ or `'` $\langle character \rangle$)

In this last case expansion stops once a non-digit is found; if that is a space it is removed as in `f`-expansion. Note that protected functions *are* expanded by this process

\TeX hackers note: This is the \TeX primitive `\number`.

<code>__int_to_roman:w</code> ★	<code>__int_to_roman:w</code> $\langle integer \rangle$
	<code>__int_to_roman:w</code> $\langle integer\ denotation \rangle$ $\langle optional\ space \rangle$

Converts an $\langle integer \rangle$ to lower case Roman representation. The $\langle integer \rangle$ is found as in `__int_value:w` by expanding what follows exhaustively. One (optional) space is lost if the $\langle integer \rangle$ is given by explicit digits. Note that this function produces a string of letters with category code 12. Negative $\langle integer \rangle$ values result in no output, although the function does not terminate expansion until a suitable endpoint is found in the same way as for positive numbers.

\TeX hackers note: This is the \TeX primitive `\romannumeral` renamed.

<code>__int_eval:w</code> ★	<code>__int_eval:w</code> $\langle intexpr \rangle$ <code>__int_eval_end:</code>
<code>__int_eval_end:</code> ★	

Evaluates $\langle integer\ expression \rangle$ as described for `\int_eval:n`. The evaluation stops when an unexpandable token which is not a valid part of an integer is read or when `__int_eval_end:` is reached. The latter is gobbled by the scanner mechanism: `__int_eval_end:` itself is unexpandable but used correctly the entire construct is expandable.

\TeX hackers note: This is the $\varepsilon\text{-TeX}$ primitive `\numexpr`.

<code>__int_eval:n</code> ★	<code>__int_eval:n</code> $\{ \langle intexpr \rangle \}$
------------------------------	--

By default this expands to `__int_eval:w` $\langle intexpr \rangle$ `__int_eval_end:` but when debugging is enabled this expands to a more complicated construction that evaluates $\langle intexpr \rangle$ with parentheses and within a brace group to detect early termination.

<code>__prg_compare_error:</code>	<code>__prg_compare_error:</code>
<code>__prg_compare_error:Nw</code>	<code>__prg_compare_error:Nw</code> $\langle token \rangle$

These are used within `\int_compare:nTF`, `\dim_compare:nTF` and so on to recover correctly if the `n`-type argument does not contain a properly-formed relation.

Part X

The `l3intarray` package: low-level arrays of small integers

1 `l3intarray` documentation

This module provides no user function: at present it is meant for kernel use only.

It is a wrapper around the `\fontdimen` primitive, used to store arrays of integers (with a restricted range: absolute value at most $2^{30} - 1$). In contrast to `l3seq` sequences the access to individual entries is done in constant time rather than linear time, but only integers can be stored. More precisely, the primitive `\fontdimen` stores dimensions but the `l3intarray` package transparently converts these from/to integers. Assignments are always global.

While LuaTeX’s memory is extensible, other engines can “only” deal with a bit less than 4×10^6 entries in all `\fontdimen` arrays combined (with default TeXLive settings).

1.1 Internal functions

<code>__intarray_new:Nn</code>	<code>__intarray_new:Nn <intarray var> {<size>}</code>
---------------------------------	---

Evaluates the integer expression `<size>` and allocates an `<integer array variable>` with that number of (zero) entries.

<code>__intarray_count:N</code> ★	<code>__intarray_count:N <intarray var></code>
------------------------------------	---

Expands to the number of entries in the `<integer array variable>`. Contrarily to `\seq_count:N` this is performed in constant time.

<code>__intarray_gset:Nnn</code>	<code>__intarray_gset:Nnn <intarray var> {<position>} {<value>}</code>
<code>__intarray_gset_fast:Nnn</code>	<code>__intarray_gset_fast:Nnn <intarray var> {<position>} {<value>}</code>

Stores the result of evaluating the integer expression `<value>` into the `<integer array variable>` at the (integer expression) `<position>`. While `__intarray_gset:Nnn` checks that the `<position>` is between 1 and the `__intarray_count:N` and that the `<value>`’s absolute value is at most $2^{30} - 1$, the “fast” function performs no such bound check. Assignments are always global.

<code>__intarray_item:Nn</code> ★	<code>__intarray_item:Nn <intarray var> {<position>}</code>
<code>__intarray_item_fast:Nn</code> ★	<code>__intarray_item_fast:Nn <intarray var> {<position>}</code>

Expands to the integer entry stored at the (integer expression) `<position>` in the `<integer array variable>`. While `__intarray_item:Nn` checks that the `<position>` is between 1 and the `__intarray_count:N`, the “fast” function performs no such bound check.

Part XI

The l3flag package: expandable flags

Flags are the only data-type that can be modified in expansion-only contexts. This module is meant mostly for kernel use: in almost all cases, booleans or integers should be preferred to flags because they are very significantly faster.

A flag can hold any non-negative value, which we call its *height*. In expansion-only contexts, a flag can only be “raised”: this increases the *height* by 1. The *height* can also be queried expandably. However, decreasing it, or setting it to zero requires non-expandable assignments.

Flag variables are always local. They are referenced by a *flag name* such as `str_missing`. The *flag name* is used as part of `\use:c` constructions hence is expanded at point of use. It must expand to character tokens only, with no spaces.

A typical use case of flags would be to keep track of whether an exceptional condition has occurred during expandable processing, and produce a meaningful (non-expandable) message after the end of the expandable processing. This is exemplified by `l3str-convert`, which for performance reasons performs conversions of individual characters expandably and for readability reasons produces a single error message describing incorrect inputs that were encountered.

Flags should not be used without carefully considering the fact that raising a flag takes a time and memory proportional to its height. Flags should not be used unless unavoidable.

1 Setting up flags

<code>\flag_new:n</code>	<code>\flag_new:n {<flag name>}</code>
--------------------------	--

Creates a new flag with a name given by *flag name*, or raises an error if the name is already taken. The *flag name* may not contain spaces. The declaration is global, but flags are always local variables. The *flag* initially has zero height.

<code>\flag_clear:n</code>	<code>\flag_clear:n {<flag name>}</code>
----------------------------	--

The *flag*’s height is set to zero. The assignment is local.

<code>\flag_clear_new:n</code>	<code>\flag_clear_new:n {<flag name>}</code>
--------------------------------	--

Ensures that the *flag* exists globally by applying `\flag_new:n` if necessary, then applies `\flag_clear:n`, setting the height to zero locally.

<code>\flag_show:n</code>	<code>\flag_show:n {<flag name>}</code>
---------------------------	---

Displays the *flag*’s height in the terminal.

<code>\flag_log:n</code>	<code>\flag_log:n {<flag name>}</code>
--------------------------	--

Writes the *flag*’s height to the log file.

2 Expandable flag commands

<hr/> <code>\flag_if_exist:n</code> \star	<code>\flag_if_exist:n {\langle flag name \rangle}</code>
<hr/> <code>\flag_if_exist:n</code> <u>$\textcolor{red}{TF}$</u> \star	This function returns <code>true</code> if the $\langle flag name \rangle$ references a flag that has been defined previously, and <code>false</code> otherwise.
<hr/> <code>\flag_if_raised_p:n</code> \star	<code>\flag_if_raised:n {\langle flag name \rangle}</code>
<hr/> <code>\flag_if_raised:n</code> <u>$\textcolor{red}{TF}$</u> \star	This function returns <code>true</code> if the $\langle flag \rangle$ has non-zero height, and <code>false</code> if the $\langle flag \rangle$ has zero height.
<hr/> <code>\flag_height:n</code> \star	<code>\flag_height:n {\langle flag name \rangle}</code>
	Expands to the height of the $\langle flag \rangle$ as an integer denotation.
<hr/> <code>\flag_raise:n</code> \star	<code>\flag_raise:n {\langle flag name \rangle}</code>
	The $\langle flag \rangle$'s height is increased by 1 locally.

Part XII

The l3quark package

Quarks

1 Introduction to quarks and scan marks

Two special types of constants in L^AT_EX3 are “quarks” and “scan marks”. By convention all constants of type quark start out with `\q_`, and scan marks start with `\s_`. Scan marks are for internal use by the kernel: they are not intended for more general use.

1.1 Quarks

Quarks are control sequences that expand to themselves and should therefore *never* be executed directly in the code. This would result in an endless loop!

They are meant to be used as delimiter in weird functions, the most common use case being the ‘stop token’ (*i.e.* `\q_stop`). For example, when writing a macro to parse a user-defined date

```
\date_parse:n {19/June/1981}
```

one might write a command such as

```
\cs_new:Npn \date_parse:n #1 { \date_parse_aux:w #1 \q_stop }
\cs_new:Npn \date_parse_aux:w #1 / #2 / #3 \q_stop
{ <do something with the date> }
```

Quarks are sometimes also used as error return values for functions that receive erroneous input. For example, in the function `\prop_get:NnN` to retrieve a value stored in some key of a property list, if the key does not exist then the return value is the quark `\q_no_value`. As mentioned above, such quarks are extremely fragile and it is imperative when using such functions that code is carefully written to check for pathological cases to avoid leakage of a quark into an uncontrolled environment.

Quarks also permit the following ingenious trick when parsing tokens: when you pick up a token in a temporary variable and you want to know whether you have picked up a particular quark, all you have to do is compare the temporary variable to the quark using `\tl_if_eq:NNTF`. A set of special quark testing functions is set up below. All the quark testing functions are expandable although the ones testing only single tokens are much faster. An example of the quark testing functions and their use in recursion can be seen in the implementation of `\clist_map_function:NN`.

2 Defining quarks

<code>\quark_new:N</code>	<code>\quark_new:N <quark></code>
---------------------------	---

Creates a new `<quark>` which expands only to `<quark>`. The `<quark>` is defined globally, and an error message is raised if the name was already taken.

<u><code>\q_stop</code></u>	Used as a marker for delimited arguments, such as <code>\cs_set:Npn \tmp:w #1#2 \q_stop {#1}</code>
<u><code>\q_mark</code></u>	Used as a marker for delimited arguments when <code>\q_stop</code> is already in use.
<u><code>\q_nil</code></u>	Quark to mark a null value in structured variables or functions. Used as an end delimiter when this may itself need to be tested (in contrast to <code>\q_stop</code> , which is only ever used as a delimiter).
<u><code>\q_no_value</code></u>	A canonical value for a missing value, when one is requested from a data structure. This is therefore used as a “return” value by functions such as <code>\prop_get:NnN</code> if there is no data to return.

3 Quark tests

The method used to define quarks means that the single token (`N`) tests are faster than the multi-token (`n`) tests. The latter should therefore only be used when the argument can definitely take more than a single token.

<u><code>\quark_if_nil_p:N</code> ★</u>	<code>\quark_if_nil_p:N</code> <i><token></i>
<u><code>\quark_if_nil:NTF</code> ★</u>	<code>\quark_if_nil:NTF</code> <i><token></i> <i>{<true code>}</i> <i>{<false code>}</i>
	Tests if the <i><token></i> is equal to <code>\q_nil</code> .
<u><code>\quark_if_nil_p:n</code> ★</u>	<code>\quark_if_nil_p:n</code> <i>{<token list>}</i>
<u><code>\quark_if_nil_p:(o V)</code> ★</u>	<code>\quark_if_nil:nTF</code> <i>{<token list>}</i> <i>{<true code>}</i> <i>{<false code>}</i>
<u><code>\quark_if_nil:nTF</code> ★</u>	Tests if the <i><token list></i> contains only <code>\q_nil</code> (distinct from <i><token list></i> being empty or containing <code>\q_nil</code> plus one or more other tokens).
<u><code>\quark_if_nil:(o V)TF</code> ★</u>	
<u><code>\quark_if_no_value_p:N</code> ★</u>	<code>\quark_if_no_value_p:N</code> <i><token></i>
<u><code>\quark_if_no_value_p:c</code> ★</u>	<code>\quark_if_no_value:NTF</code> <i><token></i> <i>{<true code>}</i> <i>{<false code>}</i>
<u><code>\quark_if_no_value:NTF</code> ★</u>	Tests if the <i><token></i> is equal to <code>\q_no_value</code> .
<u><code>\quark_if_no_value:cTF</code> ★</u>	
<u><code>\quark_if_no_value_p:n</code> ★</u>	<code>\quark_if_no_value_p:n</code> <i>{<token list>}</i>
<u><code>\quark_if_no_value:nTF</code> ★</u>	<code>\quark_if_no_value:nTF</code> <i>{<token list>}</i> <i>{<true code>}</i> <i>{<false code>}</i>
	Tests if the <i><token list></i> contains only <code>\q_no_value</code> (distinct from <i><token list></i> being empty or containing <code>\q_no_value</code> plus one or more other tokens).

4 Recursion

This module provides a uniform interface to intercepting and terminating loops as when one is doing tail recursion. The building blocks follow below and an example is shown in Section 5.

<code>\q_recursion_tail</code>	This quark is appended to the data structure in question and appears as a real element there. This means it gets any list separators around it.
--------------------------------	---

<code>\q_recursion_stop</code>	This quark is added <i>after</i> the data structure. Its purpose is to make it possible to terminate the recursion at any point easily.
--------------------------------	---

<code>\quark_if_recursion_tail_stop:N</code>	<code>\quark_if_recursion_tail_stop:N <token></code>
--	--

Tests if `<token>` contains only the marker `\q_recursion_tail`, and if so uses `\use_none_delimit_by_q_recursion_stop:w` to terminate the recursion that this belongs to. The recursion input must include the marker tokens `\q_recursion_tail` and `\q_recursion_stop` as the last two items.

<code>\quark_if_recursion_tail_stop:n</code>	<code>\quark_if_recursion_tail_stop:n {<token list>}</code>
--	---

<code>\quark_if_recursion_tail_stop:o</code>	
--	--

Updated: 2011-09-06

Tests if the `<token list>` contains only `\q_recursion_tail`, and if so uses `\use_none_delimit_by_q_recursion_stop:w` to terminate the recursion that this belongs to. The recursion input must include the marker tokens `\q_recursion_tail` and `\q_recursion_stop` as the last two items.

<code>\quark_if_recursion_tail_stop_do:Nn</code>	<code>\quark_if_recursion_tail_stop_do:Nn <token> {<insertion>}</code>
--	--

Tests if `<token>` contains only the marker `\q_recursion_tail`, and if so uses `\use_none_delimit_by_q_recursion_stop:w` to terminate the recursion that this belongs to. The recursion input must include the marker tokens `\q_recursion_tail` and `\q_recursion_stop` as the last two items. The `<insertion>` code is then added to the input stream after the recursion has ended.

<code>\quark_if_recursion_tail_stop_do:nn</code>	<code>\quark_if_recursion_tail_stop_do:nn {<token list>} {<insertion>}</code>
--	---

<code>\quark_if_recursion_tail_stop_do:on</code>	
--	--

Updated: 2011-09-06

Tests if the `<token list>` contains only `\q_recursion_tail`, and if so uses `\use_none_delimit_by_q_recursion_stop:w` to terminate the recursion that this belongs to. The recursion input must include the marker tokens `\q_recursion_tail` and `\q_recursion_stop` as the last two items. The `<insertion>` code is then added to the input stream after the recursion has ended.

5 An example of recursion with quarks

Quarks are mainly used internally in the `expl3` code to define recursion functions such as `\tl_map_inline:nn` and so on. Here is a small example to demonstrate how to use quarks in this fashion. We shall define a command called `\my_map_dbl:nn` which takes a token list and applies an operation to every *pair* of tokens. For example, `\my_map_dbl:nn {abcd} {[--#1--#2--]~}` would produce “`[-a-b-] [-c-d-]` ”. Using quarks to define such functions simplifies their logic and ensures robustness in many cases.

Here's the definition of `\my_map_dbl:nn`. First of all, define the function that does the processing based on the inline function argument `#2`. Then initiate the recursion using an internal function. The token list `#1` is terminated using `\q_recursion_tail`, with delimiters according to the type of recursion (here a pair of `\q_recursion_tail`), concluding with `\q_recursion_stop`. These quarks are used to mark the end of the token list being operated upon.

```
\cs_new:Npn \my_map_dbl:nn #1#2
{
  \cs_set:Npn \__my_map_dbl_fn:nn ##1 ##2 {#2}
  \__my_map_dbl:nn #1 \q_recursion_tail \q_recursion_tail
  \q_recursion_stop
}
```

The definition of the internal recursion function follows. First check if either of the input tokens are the termination quarks. Then, if not, apply the inline function to the two arguments.

```
\cs_new:Nn \__my_map_dbl:nn
{
  \quark_if_recursion_tail_stop:n {#1}
  \quark_if_recursion_tail_stop:n {#2}
  \__my_map_dbl_fn:nn {#1} {#2}
}
```

Finally, recurse:

```
\__my_map_dbl:nn
}
```

Note that contrarily to L^AT_EX3 built-in mapping functions, this mapping function cannot be nested, since the second map would overwrite the definition of `__my_map_dbl_fn:nn`.

6 Internal quark functions

```
\__quark_if_recursion_tail_break:NN \__quark_if_recursion_tail_break:nN {<token list>}
\__quark_if_recursion_tail_break:nN \<type>_map_break:
```

Tests if `<token list>` contains only `\q_recursion_tail`, and if so terminates the recursion using `\<type>_map_break:.` The recursion end should be marked by `\prg_break_point:Nn \<type>_map_break:.`

7 Scan marks

Scan marks are control sequences set equal to `\scan_stop:`, hence never expand in an expansion context and are (largely) invisible if they are encountered in a typesetting context.

Like quarks, they can be used as delimiters in weird functions and are often safer to use for this purpose. Since they are harmless when executed by T_EX in non-expandable contexts, they can be used to mark the end of a set of instructions. This allows to skip to that point if the end of the instructions should not be performed (see l3regex).

The scan marks system is only for internal use by the kernel team in a small number of very specific places. These functions should not be used more generally.

<code>_scan_new:N</code>	<code>_scan_new:N</code> $\langle scan\ mark \rangle$
----------------------------	---

Creates a new $\langle scan\ mark \rangle$ which is set equal to `\scan_stop:`. The $\langle scan\ mark \rangle$ is defined globally, and an error message is raised if the name was already taken by another scan mark.

<code>\s_stop</code>	Used at the end of a set of instructions, as a marker that can be jumped to using <code>_use_none_delimit_by_s_stop:w</code> .
-----------------------	--

<code>_use_none_delimit_by_s_stop:w</code>	<code>_use_none_delimit_by_s_stop:w</code> $\langle tokens \rangle$ <code>\s_stop</code>
--	---

Removes the $\langle tokens \rangle$ and `\s_stop` from the input stream. This leads to a low-level TeX error if `\s_stop` is absent.

Part XIII

The l3prg package

Control structures

Conditional processing in L^AT_EX3 is defined as something that performs a series of tests, possibly involving assignments and calling other functions that do not read further ahead in the input stream. After processing the input, a *state* is returned. The states returned are *⟨true⟩* and *⟨false⟩*.

L^AT_EX3 has two forms of conditional flow processing based on these states. The first form is predicate functions that turn the returned state into a boolean *⟨true⟩* or *⟨false⟩*. For example, the function `\cs_if_free_p:N` checks whether the control sequence given as its argument is free and then returns the boolean *⟨true⟩* or *⟨false⟩* values to be used in testing with `\if_predicate:w` or in functions to be described below. The second form is the kind of functions choosing a particular argument from the input stream based on the result of the testing as in `\cs_if_free:NTF` which also takes one argument (the *N*) and then executes either **true** or **false** depending on the result.

T_EXhackers note: The arguments are executed after exiting the underlying `\if... \fi` structure.

1 Defining a set of conditional functions

```
\prg_new_conditional:Npnn
\prg_set_conditional:Npnn
\prg_new_conditional:Nnn
\prg_set_conditional:Nnn
```

Updated: 2012-02-06

```
\prg_new_conditional:Npnn \<name>:<arg spec> <parameters> {\<conditions>} {\<code>}
\prg_new_conditional:Nnn \<name>:<arg spec> {\<conditions>} {\<code>}
```

These functions create a family of conditionals using the same *{⟨code⟩}* to perform the test created. Those conditionals are expandable if *⟨code⟩* is. The **new** versions check for existing definitions and perform assignments globally (cf. `\cs_new:Npn`) whereas the **set** versions do no check and perform assignments locally (cf. `\cs_set:Npn`). The conditionals created are dependent on the comma-separated list of *⟨conditions⟩*, which should be one or more of **p**, **T**, **F** and **TF**.

```
\prg_new_protected_conditional:Npnn \prg_new_protected_conditional:Npnn \<name>:<arg spec> <parameters>
\prg_set_protected_conditional:Npnn {\<conditions>} {\<code>}
\prg_new_protected_conditional:Nnn \prg_new_protected_conditional:Nnn \<name>:<arg spec>
\prg_set_protected_conditional:Nnn {\<conditions>} {\<code>}
```

Updated: 2012-02-06

These functions create a family of protected conditionals using the same *{⟨code⟩}* to perform the test created. The *⟨code⟩* does not need to be expandable. The **new** version check for existing definitions and perform assignments globally (cf. `\cs_new:Npn`) whereas the **set** version do not (cf. `\cs_set:Npn`). The conditionals created are depended on the comma-separated list of *⟨conditions⟩*, which should be one or more of **T**, **F** and **TF** (not **p**).

The conditionals are defined by `\prg_new_conditional:Npnn` and friends as:

- `\<name>_p:<arg spec>` — a predicate function which will supply either a logical `true` or logical `false`. This function is intended for use in cases where one or more logical tests are combined to lead to a final outcome. This function cannot be defined for `protected` conditionals.
- `\<name>:<arg spec>T` — a function with one more argument than the original `<arg spec>` demands. The `<true branch>` code in this additional argument will be left on the input stream only if the test is `true`.
- `\<name>:<arg spec>F` — a function with one more argument than the original `<arg spec>` demands. The `<false branch>` code in this additional argument will be left on the input stream only if the test is `false`.
- `\<name>:<arg spec>TF` — a function with two more argument than the original `<arg spec>` demands. The `<true branch>` code in the first additional argument will be left on the input stream if the test is `true`, while the `<false branch>` code in the second argument will be left on the input stream if the test is `false`.

The `<code>` of the test may use `<parameters>` as specified by the second argument to `\prg_set_conditional:Npnn`: this should match the `<argument specification>` but this is not enforced. The `Nnn` versions infer the number of arguments from the argument specification given (cf. `\cs_new:Nn`, etc.). Within the `<code>`, the functions `\prg_return_true:` and `\prg_return_false:` are used to indicate the logical outcomes of the test.

An example can easily clarify matters here:

```
\prg_set_conditional:Npnn \foo_if_bar:NN #1#2 { p , T , TF }
{
  \if_meaning:w \l_tmpa_tl #1
  \prg_return_true:
\else:
  \if_meaning:w \l_tmpa_tl #2
  \prg_return_true:
\else:
  \prg_return_false:
\fi:
\fi:
}
```

This defines the function `\foo_if_bar_p:NN`, `\foo_if_bar:NNTF` and `\foo_if_bar:NNT` but not `\foo_if_bar:NNF` (because `F` is missing from the `<conditions>` list). The return statements take care of resolving the remaining `\else:` and `\fi:` before returning the state. There must be a return statement for each branch; failing to do so will result in erroneous output if that branch is executed.

<code>\prg_new_eq_conditional:Nnn</code>	<code>\prg_new_eq_conditional:Nnn \<name1>:<arg spec1> \<name2>:<arg spec2></code>
<code>\prg_set_eq_conditional:Nnn</code>	<code>{<conditions>}</code>

These functions copy a family of conditionals. The `new` version checks for existing definitions (cf. `\cs_new_eq:NN`) whereas the `set` version does not (cf. `\cs_set_eq:NN`). The conditionals copied are depended on the comma-separated list of `<conditions>`, which should be one or more of `p`, `T`, `F` and `TF`.

<code>\prg_return_true:</code>	★	<code>\prg_return_true:</code>
<code>\prg_return_false:</code>	★	<code>\prg_return_false:</code>

These “return” functions define the logical state of a conditional statement. They appear within the code for a conditional function generated by `\prg_set_conditional:Npnn`, *etc.*, to indicate when a true or false branch should be taken. While they may appear multiple times each within the code of such conditionals, the execution of the conditional must result in the expansion of one of these two functions *exactly once*.

The return functions trigger what is internally an **f**-expansion process to complete the evaluation of the conditional. Therefore, after `\prg_return_true:` or `\prg_return_false:` there must be no non-expandable material in the input stream for the remainder of the expansion of the conditional code. This includes other instances of either of these functions.

2 The boolean data type

This section describes a boolean data type which is closely connected to conditional processing as sometimes you want to execute some code depending on the value of a switch (*e.g.*, draft/final) and other times you perhaps want to use it as a predicate function in an `\if_predicate:w` test. The problem of the primitive `\if_false:` and `\if_true:` tokens is that it is not always safe to pass them around as they may interfere with scanning for termination of primitive conditional processing. Therefore, we employ two canonical booleans: `\c_true_bool` or `\c_false_bool`. Besides preventing problems as described above, it also allows us to implement a simple boolean parser supporting the logical operations And, Or, Not, *etc.* which can then be used on both the boolean type and predicate functions.

All conditional `\bool_` functions except assignments are expandable and expect the input to also be fully expandable (which generally means being constructed from predicate functions and booleans, possibly nested).

T_EXhackers note: The `bool` data type is not implemented using the `\iffalse`/`\iftrue` primitives, in contrast to `\newif`, *etc.*, in plain T_EX, L^AT_EX 2_ε and so on. Programmers should not base use of `bool` switches on any particular expectation of the implementation.

<code>\bool_new:N</code>	<code>\bool_new:N</code>	<code><boolean></code>
<code>\bool_new:c</code>		

Creates a new `<boolean>` or raises an error if the name is already taken. The declaration is global. The `<boolean>` is initially **false**.

<code>\bool_set_false:N</code>	<code>\bool_set_false:N</code>	<code><boolean></code>
<code>\bool_set_false:c</code>		
<code>\bool_gset_false:N</code>		
<code>\bool_gset_false:c</code>		

Sets `<boolean>` logically **false**.

<code>\bool_set_true:N</code>	<code>\bool_set_true:N</code>	<code><boolean></code>
<code>\bool_set_true:c</code>		
<code>\bool_gset_true:N</code>		
<code>\bool_gset_true:c</code>		

Sets `<boolean>` logically **true**.

`\bool_set_eq:NN`
`\bool_set_eq:(cN|Nc|cc)`
`\bool_gset_eq:NN`
`\bool_gset_eq:(cN|Nc|cc)`

`\bool_set_eq:NN` $\langle boolean_1 \rangle$ $\langle boolean_2 \rangle$
 Sets $\langle boolean_1 \rangle$ to the current value of $\langle boolean_2 \rangle$.

`\bool_set:Nn`
`\bool_set:cn`
`\bool_gset:Nn`
`\bool_gset:cn`

`\bool_set:Nn` $\langle boolean \rangle$ $\{\langle boolexpr \rangle\}$
 Evaluates the $\langle boolean \text{ expression} \rangle$ as described for `\bool_if:nTF`, and sets the $\langle boolean \rangle$ variable to the logical truth of this evaluation.

Updated: 2017-07-15

`\bool_if_p:N` ★
`\bool_if_p:c` ★
`\bool_if:NTF` ★
`\bool_if:cTF` ★

`\bool_if_p:N` $\langle boolean \rangle$
`\bool_if:NTF` $\langle boolean \rangle$ $\{\langle true \text{ code} \rangle\}$ $\{\langle false \text{ code} \rangle\}$
 Tests the current truth of $\langle boolean \rangle$, and continues expansion based on this result.

Updated: 2017-07-15

`\bool_show:N`
`\bool_show:c`

`\bool_show:N` $\langle boolean \rangle$
 Displays the logical truth of the $\langle boolean \rangle$ on the terminal.

New: 2012-02-09

Updated: 2015-08-01

`\bool_show:n`

`\bool_show:n` $\{\langle boolean \text{ expression} \rangle\}$

New: 2012-02-09

Updated: 2017-07-15

`\bool_log:N`
`\bool_log:c`

`\bool_log:N` $\langle boolean \rangle$
 Writes the logical truth of the $\langle boolean \rangle$ in the log file.

New: 2014-08-22

Updated: 2015-08-03

`\bool_log:n`

`\bool_log:n` $\{\langle boolean \text{ expression} \rangle\}$

New: 2014-08-22

Updated: 2017-07-15

`\bool_if_exist_p:N` ★
`\bool_if_exist_p:c` ★
`\bool_if_exist:NTF` ★
`\bool_if_exist:cTF` ★

`\bool_if_exist_p:N` $\langle boolean \rangle$
`\bool_if_exist:NTF` $\langle boolean \rangle$ $\{\langle true \text{ code} \rangle\}$ $\{\langle false \text{ code} \rangle\}$
 Tests whether the $\langle boolean \rangle$ is currently defined. This does not check that the $\langle boolean \rangle$ really is a boolean variable.

New: 2012-03-03

`\l_tmpa_bool`
`\l_tmpb_bool`

A scratch boolean for local assignment. It is never used by the kernel code, and so is safe for use with any L^AT_EX3-defined function. However, it may be overwritten by other non-kernel code and so should only be used for short-term storage.

`\g_tmpa_bool`
`\g_tmpb_bool`

A scratch boolean for global assignment. It is never used by the kernel code, and so is safe for use with any L^AT_EX3-defined function. However, it may be overwritten by other non-kernel code and so should only be used for short-term storage.

3 Boolean expressions

As we have a boolean datatype and predicate functions returning boolean $\langle true \rangle$ or $\langle false \rangle$ values, it seems only fitting that we also provide a parser for $\langle boolean\ expressions \rangle$.

A boolean expression is an expression which given input in the form of predicate functions and boolean variables, return boolean $\langle true \rangle$ or $\langle false \rangle$. It supports the logical operations And, Or and Not as the well-known infix operators `&&` and `||` and prefix `!` with their usual precedences (namely, `&&` binds more tightly than `||`). In addition to this, parentheses can be used to isolate sub-expressions. For example,

```
\int_compare_p:n { 1 = 1 } &&
(
  \int_compare_p:n { 2 = 3 } ||
  \int_compare_p:n { 4 <= 4 } ||
  \str_if_eq_p:nn { abc } { def }
) &&
! \int_compare_p:n { 2 = 4 }
```

is a valid boolean expression.

Contrarily to some other programming languages, the operators `&&` and `||` evaluate both operands in all cases, even when the first operand is enough to determine the result. This “eager” evaluation should be contrasted with the “lazy” evaluation of `\bool_lazy_...` functions.

T_EXhackers note: The eager evaluation of boolean expressions is unfortunately necessary in T_EX. Indeed, a lazy parser can get confused if `&&` or `||` or parentheses appear as (unbraced) arguments of some predicates. For instance, the innocuous-looking expression below would break (in a lazy parser) if `#1` were a closing parenthesis and `\l_tmpa_bool` were `true`.

```
( \l_tmpa_bool || \token_if_eq_meaning_p:NN X #1 )
```

Minimal (lazy) evaluation can be obtained using the conditionals `\bool_lazy_all:nTF`, `\bool_lazy_and:nnTF`, `\bool_lazy_any:nTF`, or `\bool_lazy_or:nnTF`, which only evaluate their boolean expression arguments when they are needed to determine the resulting truth value. For example, when evaluating the boolean expression

```
\bool_lazy_and_p:nn
{
  \bool_lazy_any_p:n
  {
    { \int_compare_p:n { 2 = 3 } }
    { \int_compare_p:n { 4 <= 4 } }
    { \int_compare_p:n { 1 = \error } } % skipped
  }
}
{ ! \int_compare_p:n { 2 = 4 } }
```

the line marked with `skipped` is not expanded because the result of `\bool_lazy_any_p:n` is known once the second boolean expression is found to be logically `true`. On the other hand, the last line is expanded because its logical value is needed to determine the result of `\bool_lazy_and_p:nn`.

<code>\bool_if_p:n</code> ★ <code>\bool_if:nTF</code> ★ <hr/> Updated: 2017-07-15	<code>\bool_if_p:n {⟨boolean expression⟩}</code> <code>\bool_if:nTF {⟨boolean expression⟩} {⟨true code⟩} {⟨false code⟩}</code>
---	---

Tests the current truth of *⟨boolean expression⟩*, and continues expansion based on this result. The *⟨boolean expression⟩* should consist of a series of predicates or boolean variables with the logical relationship between these defined using `&&` (“And”), `||` (“Or”), `!` (“Not”) and parentheses. The logical Not applies to the next predicate or group.

<code>\bool_lazy_all_p:n</code> ★ <code>\bool_lazy_all:nTF</code> ★ <hr/> New: 2015-11-15 Updated: 2017-07-15	<code>\bool_lazy_all_p:n { {⟨boolexpr₁⟩} {⟨boolexpr₂⟩} ... {⟨boolexpr_N⟩} }</code> <code>\bool_lazy_all:nTF { {⟨boolexpr₁⟩} {⟨boolexpr₂⟩} ... {⟨boolexpr_N⟩} } {⟨true code⟩} {⟨false code⟩}</code>
--	---

Implements the “And” operation on the *⟨boolean expressions⟩*, hence is `true` if all of them are `true` and `false` if any of them is `false`. Contrarily to the infix operator `&&`, only the *⟨boolean expressions⟩* which are needed to determine the result of `\bool_lazy_all:nTF` are evaluated. See also `\bool_lazy_and:nnTF` when there are only two *⟨boolean expressions⟩*.

<code>\bool_lazy_and_p:nn</code> ★ <code>\bool_lazy_and:nnTF</code> ★ <hr/> New: 2015-11-15 Updated: 2017-07-15	<code>\bool_lazy_and_p:nn {⟨boolexpr₁⟩} {⟨boolexpr₂⟩}</code> <code>\bool_lazy_and:nnTF {⟨boolexpr₁⟩} {⟨boolexpr₂⟩} {⟨true code⟩} {⟨false code⟩}</code>
--	---

Implements the “And” operation between two boolean expressions, hence is `true` if both are `true`. Contrarily to the infix operator `&&`, the *⟨boolexpr₂⟩* is only evaluated if it is needed to determine the result of `\bool_lazy_and:nnTF`. See also `\bool_lazy_all:nTF` when there are more than two *⟨boolean expressions⟩*.

<code>\bool_lazy_any_p:n</code> ★ <code>\bool_lazy_any:nTF</code> ★ <hr/> New: 2015-11-15 Updated: 2017-07-15	<code>\bool_lazy_any_p:n { {⟨boolexpr₁⟩} {⟨boolexpr₂⟩} ... {⟨boolexpr_N⟩} }</code> <code>\bool_lazy_any:nTF { {⟨boolexpr₁⟩} {⟨boolexpr₂⟩} ... {⟨boolexpr_N⟩} } {⟨true code⟩} {⟨false code⟩}</code>
--	---

Implements the “Or” operation on the *⟨boolean expressions⟩*, hence is `true` if any of them is `true` and `false` if all of them are `false`. Contrarily to the infix operator `||`, only the *⟨boolean expressions⟩* which are needed to determine the result of `\bool_lazy_any:nTF` are evaluated. See also `\bool_lazy_or:nnTF` when there are only two *⟨boolean expressions⟩*.

<code>\bool_lazy_or_p:nn</code> ★ <code>\bool_lazy_or:nnTF</code> ★ <hr/> New: 2015-11-15 Updated: 2017-07-15	<code>\bool_lazy_or_p:nn {⟨boolexpr₁⟩} {⟨boolexpr₂⟩}</code> <code>\bool_lazy_or:nnTF {⟨boolexpr₁⟩} {⟨boolexpr₂⟩} {⟨true code⟩} {⟨false code⟩}</code>
--	---

Implements the “Or” operation between two boolean expressions, hence is `true` if either one is `true`. Contrarily to the infix operator `||`, the *⟨boolexpr₂⟩* is only evaluated if it is needed to determine the result of `\bool_lazy_or:nnTF`. See also `\bool_lazy_any:nTF` when there are more than two *⟨boolean expressions⟩*.

<code>\bool_not_p:n</code> ★ <hr/> Updated: 2017-07-15	<code>\bool_not_p:n {⟨boolean expression⟩}</code> Function version of <code>!(⟨boolean expression⟩)</code> within a boolean expression.
---	--

<code>\bool_xor_p:nn</code> ☆
Updated: 2017-07-15

`\bool_xor_p:nn` $\{ \langle \text{boolean expr}_1 \rangle \} \{ \langle \text{boolean expr}_2 \rangle \}$

Implements an “exclusive or” operation between two boolean expressions. There is no infix operation for this logical operator.

4 Logical loops

Loops using either boolean expressions or stored boolean values.

<code>\bool_do_until:Nn</code> ☆
<code>\bool_do_until:cn</code> ☆
Updated: 2017-07-15

`\bool_do_until:Nn` $\langle \text{boolean} \rangle \{ \langle \text{code} \rangle \}$

Places the $\langle \text{code} \rangle$ in the input stream for T_EX to process, and then checks the logical value of the $\langle \text{boolean} \rangle$. If it is **false** then the $\langle \text{code} \rangle$ is inserted into the input stream again and the process loops until the $\langle \text{boolean} \rangle$ is **true**.

<code>\bool_do_while:Nn</code> ☆
<code>\bool_do_while:cn</code> ☆
Updated: 2017-07-15

`\bool_do_while:Nn` $\langle \text{boolean} \rangle \{ \langle \text{code} \rangle \}$

Places the $\langle \text{code} \rangle$ in the input stream for T_EX to process, and then checks the logical value of the $\langle \text{boolean} \rangle$. If it is **true** then the $\langle \text{code} \rangle$ is inserted into the input stream again and the process loops until the $\langle \text{boolean} \rangle$ is **false**.

<code>\bool_until_do:Nn</code> ☆
<code>\bool_until_do:cn</code> ☆
Updated: 2017-07-15

`\bool_until_do:Nn` $\langle \text{boolean} \rangle \{ \langle \text{code} \rangle \}$

This function firsts checks the logical value of the $\langle \text{boolean} \rangle$. If it is **false** the $\langle \text{code} \rangle$ is placed in the input stream and expanded. After the completion of the $\langle \text{code} \rangle$ the truth of the $\langle \text{boolean} \rangle$ is re-evaluated. The process then loops until the $\langle \text{boolean} \rangle$ is **true**.

<code>\bool_while_do:Nn</code> ☆
<code>\bool_while_do:cn</code> ☆
Updated: 2017-07-15

`\bool_while_do:Nn` $\langle \text{boolean} \rangle \{ \langle \text{code} \rangle \}$

This function firsts checks the logical value of the $\langle \text{boolean} \rangle$. If it is **true** the $\langle \text{code} \rangle$ is placed in the input stream and expanded. After the completion of the $\langle \text{code} \rangle$ the truth of the $\langle \text{boolean} \rangle$ is re-evaluated. The process then loops until the $\langle \text{boolean} \rangle$ is **false**.

<code>\bool_do_until:nn</code> ☆
Updated: 2017-07-15

`\bool_do_until:nn` $\{ \langle \text{boolean expression} \rangle \} \{ \langle \text{code} \rangle \}$

Places the $\langle \text{code} \rangle$ in the input stream for T_EX to process, and then checks the logical value of the $\langle \text{boolean expression} \rangle$ as described for `\bool_if:nTF`. If it is **false** then the $\langle \text{code} \rangle$ is inserted into the input stream again and the process loops until the $\langle \text{boolean expression} \rangle$ evaluates to **true**.

<code>\bool_do_while:nn</code> ☆
Updated: 2017-07-15

`\bool_do_while:nn` $\{ \langle \text{boolean expression} \rangle \} \{ \langle \text{code} \rangle \}$

Places the $\langle \text{code} \rangle$ in the input stream for T_EX to process, and then checks the logical value of the $\langle \text{boolean expression} \rangle$ as described for `\bool_if:nTF`. If it is **true** then the $\langle \text{code} \rangle$ is inserted into the input stream again and the process loops until the $\langle \text{boolean expression} \rangle$ evaluates to **false**.

<code>\bool_until_do:nn</code> ☆
Updated: 2017-07-15

`\bool_until_do:nn` $\{ \langle \text{boolean expression} \rangle \} \{ \langle \text{code} \rangle \}$

This function firsts checks the logical value of the $\langle \text{boolean expression} \rangle$ (as described for `\bool_if:nTF`). If it is **false** the $\langle \text{code} \rangle$ is placed in the input stream and expanded. After the completion of the $\langle \text{code} \rangle$ the truth of the $\langle \text{boolean expression} \rangle$ is re-evaluated. The process then loops until the $\langle \text{boolean expression} \rangle$ is **true**.

`\bool_while_do:nn` ★

Updated: 2017-07-15

`\bool_while_do:nn` $\{\langle\textit{boolean expression}\rangle\}$ $\{\langle\textit{code}\rangle\}$

This function firsts checks the logical value of the $\langle\textit{boolean expression}\rangle$ (as described for `\bool_if:nTF`). If it is `true` the $\langle\textit{code}\rangle$ is placed in the input stream and expanded. After the completion of the $\langle\textit{code}\rangle$ the truth of the $\langle\textit{boolean expression}\rangle$ is re-evaluated. The process then loops until the $\langle\textit{boolean expression}\rangle$ is `false`.

5 Producing multiple copies

`\prg_replicate:nn` ★

Updated: 2011-07-04

`\prg_replicate:nn` $\{\langle\textit{integer expression}\rangle\}$ $\{\langle\textit{tokens}\rangle\}$

Evaluates the $\langle\textit{integer expression}\rangle$ (which should be zero or positive) and creates the resulting number of copies of the $\langle\textit{tokens}\rangle$. The function is both expandable and safe for nesting. It yields its result after two expansion steps.

6 Detecting T_EX's mode

`\mode_if_horizontal_p:` ★

`\mode_if_horizontal:TF` ★

`\mode_if_horizontal_p:`

`\mode_if_horizontal:TF` $\{\langle\textit{true code}\rangle\}$ $\{\langle\textit{false code}\rangle\}$

Detects if T_EX is currently in horizontal mode.

`\mode_if_inner_p:` ★

`\mode_if_inner:TF` ★

`\mode_if_inner_p:`

`\mode_if_inner:TF` $\{\langle\textit{true code}\rangle\}$ $\{\langle\textit{false code}\rangle\}$

Detects if T_EX is currently in inner mode.

`\mode_if_math_p:` ★

`\mode_if_math:TF` ★

`\mode_if_math:TF` $\{\langle\textit{true code}\rangle\}$ $\{\langle\textit{false code}\rangle\}$

Detects if T_EX is currently in maths mode.

Updated: 2011-09-05

`\mode_if_vertical_p:` ★

`\mode_if_vertical:TF` ★

`\mode_if_vertical_p:`

`\mode_if_vertical:TF` $\{\langle\textit{true code}\rangle\}$ $\{\langle\textit{false code}\rangle\}$

Detects if T_EX is currently in vertical mode.

7 Primitive conditionals

`\if_predicate:w` ★

`\if_predicate:w` $\langle\textit{predicate}\rangle$ $\langle\textit{true code}\rangle$ `\else:` $\langle\textit{false code}\rangle$ `\fi:`

This function takes a predicate function and branches according to the result. (In practice this function would also accept a single boolean variable in place of the $\langle\textit{predicate}\rangle$ but to make the coding clearer this should be done through `\if_bool:N`.)

`\if_bool:N` ★

`\if_bool:N` $\langle\textit{boolean}\rangle$ $\langle\textit{true code}\rangle$ `\else:` $\langle\textit{false code}\rangle$ `\fi:`

This function takes a boolean variable and branches according to the result.

8 Internal programming functions

<code>\group_align_safe_begin:</code>	★
<code>\group_align_safe_end:</code>	★

Updated: 2011-08-11

`\group_align_safe_begin:`
`...`
`\group_align_safe_end:`

These functions are used to enclose material in a T_EX alignment environment within a specially-constructed group. This group is designed in such a way that it does not add brace groups to the output but does act as a group for the `&` token inside `\halign`. This is necessary to allow grabbing of tokens for testing purposes, as T_EX uses group level to determine the effect of alignment tokens. Without the special grouping, the use of a function such as `\peek_after:Nw` would result in a forbidden comparison of the internal `\endtemplate` token, yielding a fatal error. Each `\group_align_safe_begin:` must be matched by a `\group_align_safe_end:`, although this does not have to occur within the same function.

<code>__prg_break_point:Nn</code>	★
------------------------------------	---

`__prg_break_point:Nn \<type>_map_break: {<code>}`

Used to mark the end of a recursion or mapping: the functions `\<type>_map_break:` and `\<type>_map_break:n` use this to break out of the loop. After the loop ends, the `<code>` is inserted into the input stream. This occurs even if the break functions are *not* applied: `__prg_break_point:Nn` is functionally-equivalent in these cases to `\use_ii:nn`.

<code>__prg_map_break:Nn</code>	★
----------------------------------	---

`__prg_map_break:Nn \<type>_map_break: {<user code>}`

`...`
`__prg_break_point:Nn \<type>_map_break: {<ending code>}`

Breaks a recursion in mapping contexts, inserting in the input stream the `<user code>` after the `<ending code>` for the loop. The function breaks loops, inserting their `<ending code>`, until reaching a loop with the same `<type>` as its first argument. This `\<type>_map_break:` argument is simply used as a recognizable marker for the `<type>`.

<code>\g__prg_map_int</code>	
------------------------------	--

This integer is used by non-expandable mapping functions to track the level of nesting in force. The functions `__prg_map_1:w`, `__prg_map_2:w`, *etc.*, labelled by `\g__prg_map_int` hold functions to be mapped over various list datatypes in inline and variable mappings.

<code>__prg_break_point:</code>	★
----------------------------------	---

This copy of `\prg_do_nothing:` is used to mark the end of a fast short-term recursion: the function `__prg_break:n` uses this to break out of the loop.

<code>__prg_break:</code>	★
<code>__prg_break:n</code>	★

`__prg_break:n {<code>} ... __prg_break_point:`

Breaks a recursion which has no `<ending code>` and which is not a user-breakable mapping (see for instance `\prop_get:Nn`), and inserts the `<code>` in the input stream.

Part XIV

The l3clist package

Comma separated lists

Comma lists contain ordered data where items can be added to the left or right end of the list. The resulting ordered list can then be mapped over using `\clist_map_function:NN`. Several items can be added at once, and spaces are removed from both sides of each item on input. Hence,

```
\clist_new:N \l_my_clist
\clist_put_left:Nn \l_my_clist { ~ a ~ , ~ {b} ~ }
\clist_put_right:Nn \l_my_clist { ~ { c ~ } , d }
```

results in `\l_my_clist` containing `a,{b},{c~},d`. Comma lists cannot contain empty items, thus

```
\clist_clear_new:N \l_my_clist
\clist_put_right:Nn \l_my_clist { , ~ , , }
\clist_if_empty:NTF \l_my_clist { true } { false }
```

leaves `true` in the input stream. To include an item which contains a comma, or starts or ends with a space, surround it with braces. The sequence data type should be preferred to comma lists if items are to contain `{`, `}`, or `#` (assuming the usual \TeX category codes apply).

1 Creating and initialising comma lists

```
\clist_new:N
\clist_new:c
```

`\clist_new:N` \langle comma list \rangle

Creates a new \langle comma list \rangle or raises an error if the name is already taken. The declaration is global. The \langle comma list \rangle initially contains no items.

```
\clist_const:Nn
\clist_const:(Nx|cn|cx)
```

`\clist_const:Nn` \langle clist var \rangle $\{ \langle$ comma list $\rangle \}$

Creates a new constant \langle clist var \rangle or raises an error if the name is already taken. The value of the \langle clist var \rangle is set globally to the \langle comma list \rangle .

New: 2014-07-05

```
\clist_clear:N
\clist_clear:c
\clist_gclear:N
\clist_gclear:c
```

`\clist_clear:N` \langle comma list \rangle

Clears all items from the \langle comma list \rangle .

```
\clist_clear_new:N
\clist_clear_new:c
\clist_gclear_new:N
\clist_gclear_new:c
```

`\clist_clear_new:N` \langle comma list \rangle

Ensures that the \langle comma list \rangle exists globally by applying `\clist_new:N` if necessary, then applies `\clist_(g)clear:N` to leave the list empty.

<code>\clist_set_eq:NN</code>	<code>\clist_set_eq:NN <comma list₁> <comma list₂></code>
<code>\clist_set_eq:(cN Nc cc)</code>	Sets the content of <code><comma list₁></code> equal to that of <code><comma list₂></code> .
<code>\clist_gset_eq:NN</code>	
<code>\clist_gset_eq:(cN Nc cc)</code>	

<code>\clist_set_from_seq:NN</code>	<code>\clist_set_from_seq:NN <comma list> <sequence></code>
<code>\clist_set_from_seq:(cN Nc cc)</code>	
<code>\clist_gset_from_seq:NN</code>	
<code>\clist_gset_from_seq:(cN Nc cc)</code>	

New: 2014-07-17

Converts the data in the `<sequence>` into a `<comma list>`: the original `<sequence>` is unchanged. Items which contain either spaces or commas are surrounded by braces.

<code>\clist_concat:NNN</code>	<code>\clist_concat:NNN <comma list₁> <comma list₂> <comma list₃></code>
<code>\clist_concat:ccc</code>	Concatenates the content of <code><comma list₂></code> and <code><comma list₃></code> together and saves the result in <code><comma list₁></code> . The items in <code><comma list₂></code> are placed at the left side of the new comma list.
<code>\clist_gconcat:NNN</code>	
<code>\clist_gconcat:ccc</code>	

<code>\clist_if_exist_p:N *</code>	<code>\clist_if_exist_p:N <comma list></code>
<code>\clist_if_exist_p:c *</code>	<code>\clist_if_exist:NTF <comma list> {\true code} {\false code}</code>
<code>\clist_if_exist:NTF *</code>	Tests whether the <code><comma list></code> is currently defined. This does not check that the <code><comma list></code> really is a comma list.
<code>\clist_if_exist:cTF *</code>	

New: 2012-03-03

2 Adding data to comma lists

<code>\clist_set:Nn</code>	<code>\clist_set:Nn <comma list> {\<item₁>, ..., <item_n>}</code>
<code>\clist_set:(NV No Nx cn cV co cx)</code>	
<code>\clist_gset:Nn</code>	
<code>\clist_gset:(NV No Nx cn cV co cx)</code>	

New: 2011-09-06

Sets `<comma list>` to contain the `<items>`, removing any previous content from the variable. Spaces are removed from both sides of each item.

<code>\clist_put_left:Nn</code>	<code>\clist_put_left:Nn <comma list> {\<item₁>, ..., <item_n>}</code>
<code>\clist_put_left:(NV No Nx cn cV co cx)</code>	
<code>\clist_gput_left:Nn</code>	
<code>\clist_gput_left:(NV No Nx cn cV co cx)</code>	

Updated: 2011-09-05

Appends the `<items>` to the left of the `<comma list>`. Spaces are removed from both sides of each item.

<code>\clist_put_right:Nn</code>	<code>\clist_put_right:Nn <comma list> {\<item_1>, ..., \<item_n>}</code>
<code>\clist_put_right:(NV No Nx cn cV co cx)</code>	
<code>\clist_gput_right:Nn</code>	
<code>\clist_gput_right:(NV No Nx cn cV co cx)</code>	

Updated: 2011-09-05

Appends the $\langle items \rangle$ to the right of the $\langle comma list \rangle$. Spaces are removed from both sides of each item.

3 Modifying comma lists

While comma lists are normally used as ordered lists, it may be necessary to modify the content. The functions here may be used to update comma lists, while retaining the order of the unaffected entries.

<code>\clist_remove_duplicates:N</code>	<code>\clist_remove_duplicates:N <comma list></code>
<code>\clist_remove_duplicates:c</code>	
<code>\clist_gremove_duplicates:N</code>	
<code>\clist_gremove_duplicates:c</code>	

Removes duplicate items from the $\langle comma list \rangle$, leaving the left most copy of each item in the $\langle comma list \rangle$. The $\langle item \rangle$ comparison takes place on a token basis, as for `\tl_if_eq:nn(TF)`.

TeXhackers note: This function iterates through every item in the $\langle comma list \rangle$ and does a comparison with the $\langle items \rangle$ already checked. It is therefore relatively slow with large comma lists. Furthermore, it does not work if any of the items in the $\langle comma list \rangle$ contains `{`, `}`, or `#` (assuming the usual TeX category codes apply).

<code>\clist_remove_all:Nn</code>	<code>\clist_remove_all:Nn <comma list> {\<item>}</code>
<code>\clist_remove_all:cn</code>	
<code>\clist_gremove_all:Nn</code>	
<code>\clist_gremove_all:cn</code>	

Updated: 2011-09-06

Removes every occurrence of $\langle item \rangle$ from the $\langle comma list \rangle$. The $\langle item \rangle$ comparison takes place on a token basis, as for `\tl_if_eq:nn(TF)`.

TeXhackers note: The $\langle item \rangle$ may not contain `{`, `}`, or `#` (assuming the usual TeX category codes apply).

<code>\clist_reverse:N</code>	<code>\clist_reverse:N <comma list></code>
<code>\clist_reverse:c</code>	
<code>\clist_greverse:N</code>	
<code>\clist_greverse:c</code>	

New: 2014-07-18

Reverses the order of items stored in the $\langle comma list \rangle$.

<code>\clist_reverse:n</code>	<code>\clist_reverse:n {\<comma list>}</code>
-------------------------------	---

New: 2014-07-18

Leaves the items in the $\langle comma list \rangle$ in the input stream in reverse order. Braces and spaces are preserved by this process.

TeXhackers note: The result is returned within `\unexpanded`, which means that the comma list does not expand further when appearing in an x-type argument expansion.

<code>\clist_sort:Nn</code>	<code>\clist_sort:Nn <clist var> {<comparison code>}</code>
<code>\clist_sort:cn</code>	
<code>\clist_gsort:Nn</code>	Sorts the items in the <i><clist var></i> according to the <i><comparison code></i> , and assigns the result to <i><clist var></i> . The details of sorting comparison are described in Section 1.
<code>\clist_gsort:cn</code>	

New: 2017-02-06

4 Comma list conditionals

<code>\clist_if_empty_p:N</code> *	<code>\clist_if_empty_p:N <comma list></code>
<code>\clist_if_empty_p:c</code> *	<code>\clist_if_empty:NtF <comma list> {<true code>} {<false code>}</code>
<code>\clist_if_empty:NtF</code> *	
<code>\clist_if_empty:cTf</code> *	Tests if the <i><comma list></i> is empty (containing no items).

<code>\clist_if_empty_p:n</code> *	<code>\clist_if_empty_p:n {<comma list>}</code>
<code>\clist_if_empty:nTf</code> *	<code>\clist_if_empty:nTf {<comma list>} {<true code>} {<false code>}</code>

New: 2014-07-05

Tests if the *<comma list>* is empty (containing no items). The rules for space trimming are as for other n-type comma-list functions, hence the comma list *{~,~,~}* (without outer braces) is empty, while *{~,{}},}* (without outer braces) contains one element, which happens to be empty: the comma-list is not empty.

<code>\clist_if_in:NnTf</code>	<code>\clist_if_in:NnTf <comma list> {<item>} {<true code>} {<false code>}</code>
<code>\clist_if_in:(NV No cn cV co)Tf</code>	
<code>\clist_if_in:nnTf</code>	
<code>\clist_if_in:(nV no)Tf</code>	

Updated: 2011-09-06

Tests if the *<item>* is present in the *<comma list>*. In the case of an n-type *<comma list>*, spaces are stripped from each item, but braces are not removed. Hence,

`\clist_if_in:nnTf { a , {b}~ , {b} , c } { b } {true} {false}`

yields false.

TeXhackers note: The *<item>* may not contain `{}`, `}`, or `#` (assuming the usual TeX category codes apply), and should not contain `,` nor start or end with a space.

5 Mapping to comma lists

The functions described in this section apply a specified function to each item of a comma list.

When the comma list is given explicitly, as an n-type argument, spaces are trimmed around each item. If the result of trimming spaces is empty, the item is ignored. Otherwise, if the item is surrounded by braces, one set is removed, and the result is passed to the mapped function. Thus, if your comma list that is being mapped is *{a,~,{b}~,~,{}~{c},}* then the arguments passed to the mapped function are ‘a’, ‘{b}~’, an empty argument, and ‘c’.

When the comma list is given as an N-type argument, spaces have already been trimmed on input, and items are simply stripped of one set of braces if any. This case is more efficient than using n-type comma lists.

`\clist_map_function:NN` ☆
`\clist_map_function:cN` ☆
`\clist_map_function:nN` ☆

Updated: 2012-06-29

`\clist_map_function:NN` $\langle comma\ list \rangle$ $\langle function \rangle$
Applies $\langle function \rangle$ to every $\langle item \rangle$ stored in the $\langle comma\ list \rangle$. The $\langle function \rangle$ receives one argument for each iteration. The $\langle items \rangle$ are returned from left to right. The function `\clist_map_inline:nN` is in general more efficient than `\clist_map_function:NN`.

`\clist_map_inline:Nn`
`\clist_map_inline:cn`
`\clist_map_inline:nn`

Updated: 2012-06-29

`\clist_map_inline:Nn` $\langle comma\ list \rangle$ $\{ \langle inline\ function \rangle \}$
Applies $\langle inline\ function \rangle$ to every $\langle item \rangle$ stored within the $\langle comma\ list \rangle$. The $\langle inline\ function \rangle$ should consist of code which receives the $\langle item \rangle$ as #1. The $\langle items \rangle$ are returned from left to right.

`\clist_map_variable:NNn`
`\clist_map_variable:cNn`
`\clist_map_variable:nNn`

Updated: 2012-06-29

`\clist_map_variable:NNn` $\langle comma\ list \rangle$ $\langle variable \rangle$ $\{ \langle code \rangle \}$
Stores each $\langle item \rangle$ of the $\langle comma\ list \rangle$ in turn in the (token list) $\langle variable \rangle$ and applies the $\langle code \rangle$. The $\langle code \rangle$ will usually make use of the $\langle variable \rangle$, but this is not enforced. The assignments to the $\langle variable \rangle$ are local. The $\langle items \rangle$ are returned from left to right.

`\clist_map_break:` ☆

Updated: 2012-06-29

`\clist_map_break:`
Used to terminate a `\clist_map_...` function before all entries in the $\langle comma\ list \rangle$ have been processed. This normally takes place within a conditional statement, for example

```
\clist_map_inline:Nn \l_my_clist
{
  \str_if_eq:nnTF { #1 } { bingo }
  { \clist_map_break: }
  {
    % Do something useful
  }
}
```

Use outside of a `\clist_map_...` scenario leads to low level T_EX errors.

T_EXhackers note: When the mapping is broken, additional tokens may be inserted before further items are taken from the input stream. This depends on the design of the mapping function.

`\clist_map_break:n` ☆

Updated: 2012-06-29

`\clist_map_break:n` {<code>}

Used to terminate a `\clist_map_...` function before all entries in the <comma list> have been processed, inserting the <code> after the mapping has ended. This normally takes place within a conditional statement, for example

```
\clist_map_inline:Nn \l_my_clist
{
  \str_if_eq:nnTF { #1 } { bingo }
  { \clist_map_break:n { <code> } }
  {
    % Do something useful
  }
}
```

Use outside of a `\clist_map_...` scenario leads to low level T_EX errors.

T_EXhackers note: When the mapping is broken, additional tokens may be inserted before the <code> is inserted into the input stream. This depends on the design of the mapping function.

`\clist_count:N` ☆

`\clist_count:c` ☆

`\clist_count:n` ☆

New: 2012-07-13

`\clist_count:N` <comma list>

Leaves the number of items in the <comma list> in the input stream as an <integer denotation>. The total number of items in a <comma list> includes those which are duplicates, *i.e.* every item in a <comma list> is unique.

6 Using the content of comma lists directly

`\clist_use:Nnnn` ☆

`\clist_use:cnnn` ☆

New: 2013-05-26

`\clist_use:Nnnn` <clist var> {<separator between two>}

{<separator between more than two>} {<separator between final two>}

Places the contents of the <clist var> in the input stream, with the appropriate <separator> between the items. Namely, if the comma list has more than two items, the <separator between more than two> is placed between each pair of items except the last, for which the <separator between final two> is used. If the comma list has exactly two items, then they are placed in the input stream separated by the <separator between two>. If the comma list has a single item, it is placed in the input stream, and a comma list with no items produces no output. An error is raised if the variable does not exist or if it is invalid.

For example,

```
\clist_set:Nn \l_tmpa_clist { a , b , , c , {de} , f }
\clist_use:Nnnn \l_tmpa_clist { ~and~ } { ,~ } { ,~and~ }
```

inserts “a, b, c, de, and f” in the input stream. The first separator argument is not used in this case because the comma list has more than 2 items.

T_EXhackers note: The result is returned within the `\unexpanded` primitive (`\exp_not:n`), which means that the <items> do not expand further when appearing in an x-type argument expansion.

<code>\clist_use:Nn</code> ★	<code>\clist_use:Nn <clist var> {<separator>}</code>
<code>\clist_use:cn</code> ★	Places the contents of the <i><clist var></i> in the input stream, with the <i><separator></i> between the items. If the comma list has a single item, it is placed in the input stream, and a comma list with no items produces no output. An error is raised if the variable does not exist or if it is invalid.
New: 2013-05-26	

For example,

```
\clist_set:Nn \l_tmpa_clist { a , b , , c , {de} , f }
\clist_use:Nn \l_tmpa_clist { ~and~ }
```

inserts “a and b and c and de and f” in the input stream.

TeXhackers note: The result is returned within the `\unexpanded` primitive (`\exp_not:n`), which means that the *<items>* do not expand further when appearing in an *x*-type argument expansion.

7 Comma lists as stacks

Comma lists can be used as stacks, where data is pushed to and popped from the top of the comma list. (The left of a comma list is the top, for performance reasons.) The stack functions for comma lists are not intended to be mixed with the general ordered data functions detailed in the previous section: a comma list should either be used as an ordered data type or as a stack, but not in both ways.

<code>\clist_get:NN</code>	<code>\clist_get:NN <comma list> <token list variable></code>
<code>\clist_get:cN</code>	Stores the left-most item from a <i><comma list></i> in the <i><token list variable></i> without removing it from the <i><comma list></i> . The <i><token list variable></i> is assigned locally. If the <i><comma list></i> is empty the <i><token list variable></i> is set to the marker value <code>\q_no_value</code> .
Updated: 2012-05-14	

<code>\clist_get:NNTF</code>	<code>\clist_get:NNTF <comma list> <token list variable> {<true code>} {<false code>}</code>
<code>\clist_get:cNTF</code>	If the <i><comma list></i> is empty, leaves the <i><false code></i> in the input stream. The value of the <i><token list variable></i> is not defined in this case and should not be relied upon. If the <i><comma list></i> is non-empty, stores the top item from the <i><comma list></i> in the <i><token list variable></i> without removing it from the <i><comma list></i> . The <i><token list variable></i> is assigned locally.
New: 2012-05-14	

<code>\clist_pop:NN</code>	<code>\clist_pop:NN <comma list> <token list variable></code>
<code>\clist_pop:cN</code>	Pops the left-most item from a <i><comma list></i> into the <i><token list variable></i> , <i>i.e.</i> removes the item from the comma list and stores it in the <i><token list variable></i> . Both of the variables are assigned locally.
Updated: 2011-09-06	

<code>\clist_gpop:NN</code>	<code>\clist_gpop:NN <comma list> <token list variable></code>
<code>\clist_gpop:cN</code>	Pops the left-most item from a <i><comma list></i> into the <i><token list variable></i> , <i>i.e.</i> removes the item from the comma list and stores it in the <i><token list variable></i> . The <i><comma list></i> is modified globally, while the assignment of the <i><token list variable></i> is local.

<code>\clist_pop:NNTF</code>	<code>\clist_pop:NNTF <comma list> <token list variable> {(true code)} {(false code)}</code>
<code>\clist_pop:cNTF</code>	If the <i><comma list></i> is empty, leaves the <i><false code></i> in the input stream. The value of the <i><token list variable></i> is not defined in this case and should not be relied upon. If the <i><comma list></i> is non-empty, pops the top item from the <i><comma list></i> in the <i><token list variable></i> , <i>i.e.</i> removes the item from the <i><comma list></i> . Both the <i><comma list></i> and the <i><token list variable></i> are assigned locally.
New: 2012-05-14	

<code>\clist_gpop:NNTF</code>	<code>\clist_gpop:NNTF <comma list> <token list variable> {(true code)} {(false code)}</code>
<code>\clist_gpop:cNTF</code>	If the <i><comma list></i> is empty, leaves the <i><false code></i> in the input stream. The value of the <i><token list variable></i> is not defined in this case and should not be relied upon. If the <i><comma list></i> is non-empty, pops the top item from the <i><comma list></i> in the <i><token list variable></i> , <i>i.e.</i> removes the item from the <i><comma list></i> . The <i><comma list></i> is modified globally, while the <i><token list variable></i> is assigned locally.
New: 2012-05-14	

<code>\clist_push:Nn</code>	<code>\clist_push:Nn <comma list> {(items)}</code>
<code>\clist_push:(NV No Nx cn cV co cx)</code>	
<code>\clist_gpush:Nn</code>	
<code>\clist_gpush:(NV No Nx cn cV co cx)</code>	
Adds the <i>{(items)}</i> to the top of the <i><comma list></i> . Spaces are removed from both sides of each item.	

8 Using a single item

<code>\clist_item:Nn</code> ★	<code>\clist_item:Nn <comma list> {(integer expression)}</code>
<code>\clist_item:cn</code> ★	
<code>\clist_item:nn</code> ★	Indexing items in the <i><comma list></i> from 1 at the top (left), this function evaluates the <i><integer expression></i> and leaves the appropriate item from the comma list in the input stream. If the <i><integer expression></i> is negative, indexing occurs from the bottom (right) of the comma list. When the <i><integer expression></i> is larger than the number of items in the <i><comma list></i> (as calculated by <code>\clist_count:N</code>) then the function expands to nothing.
New: 2014-07-17	

TeXhackers note: The result is returned within the `\unexpanded` primitive (`\exp_not:n`), which means that the *<item>* does not expand further when appearing in an *x*-type argument expansion.

9 Viewing comma lists

<code>\clist_show:N</code>	<code>\clist_show:N <comma list></code>
<code>\clist_show:c</code>	Displays the entries in the <i><comma list></i> in the terminal.
Updated: 2015-08-03	
<code>\clist_show:n</code>	<code>\clist_show:n {(tokens)}</code>
<code>\clist_show:n</code>	Displays the entries in the comma list in the terminal.
Updated: 2013-08-03	

<hr/> <code>\clist_log:N</code> <hr/>	<code>\clist_log:N</code> $\langle comma list \rangle$
<code>\clist_log:c</code> <hr/>	Writes the entries in the $\langle comma list \rangle$ in the log file. See also <code>\clist_show:N</code> which displays the result in the terminal.
New: 2014-08-22 Updated: 2015-08-03 <hr/>	

<hr/> <code>\clist_log:n</code> <hr/>	<code>\clist_log:n</code> $\{\langle tokens \rangle\}$
<code>\clist_log:n</code> <hr/>	Writes the entries in the comma list in the log file. See also <code>\clist_show:n</code> which displays the result in the terminal.
New: 2014-08-22 <hr/>	

10 Constant and scratch comma lists

<hr/> <code>\c_empty_clist</code> <hr/>	Constant that is always empty.
New: 2012-07-02 <hr/>	

<hr/> <code>\l_tmpa_clist</code> <hr/>	Scratch comma lists for local assignment. These are never used by the kernel code, and so are safe for use with any L ^A T _E X3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.
<code>\l_tmpb_clist</code> <hr/>	
New: 2011-09-06 <hr/>	

<code>\g_tmpa_clist</code>	Scratch comma lists for global assignment. These are never used by the kernel code, and so are safe for use with any L ^A T _E X3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.
<code>\g_tmpb_clist</code>	
New: 2011-09-06	

Part XV

The l3token package

Token manipulation

This module deals with tokens. Now this is perhaps not the most precise description so let's try with a better description: When programming in T_EX, it is often desirable to know just what a certain token is: is it a control sequence or something else. Similarly one often needs to know if a control sequence is expandable or not, a macro or a primitive, how many arguments it takes etc. Another thing of great importance (especially when it comes to document commands) is looking ahead in the token stream to see if a certain character is present and maybe even remove it or disregard other tokens while scanning. This module provides functions for both and as such has two primary function categories: `\token_` for anything that deals with tokens and `\peek_` for looking ahead in the token stream.

Most functions we describe here can be used on control sequences, as those are tokens as well.

It is important to distinguish two aspects of a token: its “shape” (for lack of a better word), which affects the matching of delimited arguments and the comparison of token lists containing this token, and its “meaning”, which affects whether the token expands or what operation it performs. One can have tokens of different shapes with the same meaning, but not the converse.

For instance, `\if:w`, `\if_charcode:w`, and `\tex_if:D` are three names for the same internal operation of T_EX, namely the primitive testing the next two characters for equality of their character code. They have the same meaning hence behave identically in many situations. However, T_EX distinguishes them when searching for a delimited argument. Namely, the example function `\show_until_if:w` defined below takes everything until `\if:w` as an argument, despite the presence of other copies of `\if:w` under different names.

```
\cs_new:Npn \show_until_if:w #1 \if:w { \tl_show:n {#1} }
\show_until_if:w \tex_if:D \if_charcode:w \if:w
```

A list of all possible shapes and a list of all possible meanings are given in section 8.

1 Creating character tokens

```
\char_set_active_eq:NN
\char_set_active_eq:Nc
\char_gset_active_eq:NN
\char_gset_active_eq:Nc
```

Updated: 2015-11-12

```
\char_set_active_eq:NN <char> <function>
```

Sets the behaviour of the `<char>` in situations where it is active (category code 13) to be equivalent to that of the `<function>`. The category code of the `<char>` is *unchanged* by this process. The `<function>` may itself be an active character.

```
\char_set_active_eq:nN
\char_set_active_eq:nc
\char_gset_active_eq:nN
\char_gset_active_eq:nc
```

New: 2015-11-12

```
\char_set_active_eq:nN {<integer expression>} <function>
```

Sets the behaviour of the `<char>` which has character code as given by the `<integer expression>` in situations where it is active (category code 13) to be equivalent to that of the `<function>`. The category code of the `<char>` is *unchanged* by this process. The `<function>` may itself be an active character.

<hr/> <code>\char_generate:nn</code> ★ <hr/>	<code>\char_generate:nn</code> $\{\langle charcode \rangle\} \{\langle catcode \rangle\}$
<hr/> New: 2015-09-09 <hr/>	<p>Generates a character token of the given $\langle charcode \rangle$ and $\langle catcode \rangle$ (both of which may be integer expressions). The $\langle catcode \rangle$ may be one of</p> <ul style="list-style-type: none"> • 1 (begin group) • 2 (end group) • 3 (math toggle) • 4 (alignment) • 6 (parameter) • 7 (math superscript) • 8 (math subscript) • 11 (letter) • 12 (other) <p>and other values raise an error.</p> <p>The $\langle charcode \rangle$ may be any one valid for the engine in use. Note however that for X_YTeX releases prior to 0.99992 only the 8-bit range (0 to 255) is accepted due to engine limitations.</p>

<hr/> <code>\c_catcode_other_space_tl</code> <hr/>	<code>\c_catcode_other_space_tl</code>
<hr/> New: 2011-09-05 <hr/>	Token list containing one character with category code 12, (“other”), and character code 32 (space).

2 Manipulating and interrogating character tokens

<code>\char_set_catcode_escape:N</code>	<code>\char_set_catcode_letter:N</code> $\langle character \rangle$
<code>\char_set_catcode_group_begin:N</code>	
<code>\char_set_catcode_group_end:N</code>	
<code>\char_set_catcode_math_toggle:N</code>	
<code>\char_set_catcode_alignment:N</code>	
<code>\char_set_catcode_end_line:N</code>	
<code>\char_set_catcode_parameter:N</code>	
<code>\char_set_catcode_math_superscript:N</code>	
<code>\char_set_catcode_math_subscript:N</code>	
<code>\char_set_catcode_ignore:N</code>	
<code>\char_set_catcode_space:N</code>	
<code>\char_set_catcode_letter:N</code>	
<code>\char_set_catcode_other:N</code>	
<code>\char_set_catcode_active:N</code>	
<code>\char_set_catcode_comment:N</code>	
<code>\char_set_catcode_invalid:N</code>	

Updated: 2015-11-11

Sets the category code of the $\langle character \rangle$ to that indicated in the function name. Depending on the current category code of the $\langle token \rangle$ the escape token may also be needed:

`\char_set_catcode_other:N \%`

The assignment is local.

<code>\char_set_catcode_escape:n</code>	<code>\char_set_catcode_letter:n</code> $\{ \langle integer\ expression \rangle \}$
<code>\char_set_catcode_group_begin:n</code>	
<code>\char_set_catcode_group_end:n</code>	
<code>\char_set_catcode_math_toggle:n</code>	
<code>\char_set_catcode_alignment:n</code>	
<code>\char_set_catcode_end_line:n</code>	
<code>\char_set_catcode_parameter:n</code>	
<code>\char_set_catcode_math_superscript:n</code>	
<code>\char_set_catcode_math_subscript:n</code>	
<code>\char_set_catcode_ignore:n</code>	
<code>\char_set_catcode_space:n</code>	
<code>\char_set_catcode_letter:n</code>	
<code>\char_set_catcode_other:n</code>	
<code>\char_set_catcode_active:n</code>	
<code>\char_set_catcode_comment:n</code>	
<code>\char_set_catcode_invalid:n</code>	

Updated: 2015-11-11

Sets the category code of the $\langle character \rangle$ which has character code as given by the $\langle integer\ expression \rangle$. This version can be used to set up characters which cannot otherwise be given (*cf.* the N-type variants). The assignment is local.

<hr/> <code>\char_set_catcode:nn</code> <hr/>	<code>\char_set_catcode:nn {⟨intexpr₁⟩} {⟨intexpr₂⟩}</code>
Updated: 2015-11-11	These functions set the category code of the <i>⟨character⟩</i> which has character code as given by the <i>⟨integer expression⟩</i> . The first <i>⟨integer expression⟩</i> is the character code and the second is the category code to apply. The setting applies within the current T _E X group. In general, the symbolic functions <code>\char_set_catcode_⟨type⟩</code> should be preferred, but there are cases where these lower-level functions may be useful.
<hr/> <code>\char_value_catcode:n</code> ★ <hr/>	<code>\char_value_catcode:n {⟨integer expression⟩}</code>
	Expands to the current category code of the <i>⟨character⟩</i> with character code given by the <i>⟨integer expression⟩</i> .
<hr/> <code>\char_show_value_catcode:n</code> <hr/>	<code>\char_show_value_catcode:n {⟨integer expression⟩}</code>
	Displays the current category code of the <i>⟨character⟩</i> with character code given by the <i>⟨integer expression⟩</i> on the terminal.
<hr/> <code>\char_set_lccode:nn</code> <hr/>	<code>\char_set_lccode:nn {⟨intexpr₁⟩} {⟨intexpr₂⟩}</code>
Updated: 2015-08-06	Sets up the behaviour of the <i>⟨character⟩</i> when found inside <code>\tl_lower_case:n</code> , such that <i>⟨character₁⟩</i> will be converted into <i>⟨character₂⟩</i> . The two <i>⟨characters⟩</i> may be specified using an <i>⟨integer expression⟩</i> for the character code concerned. This may include the T _E X ‘ <i>⟨character⟩</i> ’ method for converting a single character into its character code:
	<pre> \char_set_lccode:nn { ‘\A } { ‘\a } % Standard behaviour \char_set_lccode:nn { ‘\A } { ‘\A + 32 } \char_set_lccode:nn { 50 } { 60 } </pre>
	The setting applies within the current T _E X group.
<hr/> <code>\char_value_lccode:n</code> ★ <hr/>	<code>\char_value_lccode:n {⟨integer expression⟩}</code>
	Expands to the current lower case code of the <i>⟨character⟩</i> with character code given by the <i>⟨integer expression⟩</i> .
<hr/> <code>\char_show_value_lccode:n</code> <hr/>	<code>\char_show_value_lccode:n {⟨integer expression⟩}</code>
	Displays the current lower case code of the <i>⟨character⟩</i> with character code given by the <i>⟨integer expression⟩</i> on the terminal.
<hr/> <code>\char_set_uccode:nn</code> <hr/>	<code>\char_set_uccode:nn {⟨intexpr₁⟩} {⟨intexpr₂⟩}</code>
Updated: 2015-08-06	Sets up the behaviour of the <i>⟨character⟩</i> when found inside <code>\tl_upper_case:n</code> , such that <i>⟨character₁⟩</i> will be converted into <i>⟨character₂⟩</i> . The two <i>⟨characters⟩</i> may be specified using an <i>⟨integer expression⟩</i> for the character code concerned. This may include the T _E X ‘ <i>⟨character⟩</i> ’ method for converting a single character into its character code:
	<pre> \char_set_uccode:nn { ‘\a } { ‘\A } % Standard behaviour \char_set_uccode:nn { ‘\A } { ‘\A - 32 } \char_set_uccode:nn { 60 } { 50 } </pre>
	The setting applies within the current T _E X group.

<hr/> <code>\char_value_uccode:n</code> ★ <hr/>	<code>\char_value_uccode:n {⟨integer expression⟩}</code> Expands to the current upper case code of the <i>⟨character⟩</i> with character code given by the <i>⟨integer expression⟩</i> .
<hr/> <code>\char_show_value_uccode:n</code> <hr/>	<code>\char_show_value_uccode:n {⟨integer expression⟩}</code> Displays the current upper case code of the <i>⟨character⟩</i> with character code given by the <i>⟨integer expression⟩</i> on the terminal.
<hr/> <code>\char_set_mathcode:nn</code> <div>Updated: 2015-08-06</div> <hr/>	<code>\char_set_mathcode:nn {⟨intexpr₁⟩} {⟨intexpr₂⟩}</code> This function sets up the math code of <i>⟨character⟩</i> . The <i>⟨character⟩</i> is specified as an <i>⟨integer expression⟩</i> which will be used as the character code of the relevant character. The setting applies within the current T _E X group.
<hr/> <code>\char_value_mathcode:n</code> ★ <hr/>	<code>\char_value_mathcode:n {⟨integer expression⟩}</code> Expands to the current math code of the <i>⟨character⟩</i> with character code given by the <i>⟨integer expression⟩</i> .
<hr/> <code>\char_show_value_mathcode:n</code> <hr/>	<code>\char_show_value_mathcode:n {⟨integer expression⟩}</code> Displays the current math code of the <i>⟨character⟩</i> with character code given by the <i>⟨integer expression⟩</i> on the terminal.
<hr/> <code>\char_set_sfcode:nn</code> <div>Updated: 2015-08-06</div> <hr/>	<code>\char_set_sfcode:nn {⟨intexpr₁⟩} {⟨intexpr₂⟩}</code> This function sets up the space factor for the <i>⟨character⟩</i> . The <i>⟨character⟩</i> is specified as an <i>⟨integer expression⟩</i> which will be used as the character code of the relevant character. The setting applies within the current T _E X group.
<hr/> <code>\char_value_sfcode:n</code> ★ <hr/>	<code>\char_value_sfcode:n {⟨integer expression⟩}</code> Expands to the current space factor for the <i>⟨character⟩</i> with character code given by the <i>⟨integer expression⟩</i> .
<hr/> <code>\char_show_value_sfcode:n</code> <hr/>	<code>\char_show_value_sfcode:n {⟨integer expression⟩}</code> Displays the current space factor for the <i>⟨character⟩</i> with character code given by the <i>⟨integer expression⟩</i> on the terminal.
<hr/> <code>\l_char_active_seq</code> <div>New: 2012-01-23 Updated: 2015-11-11</div> <hr/>	Used to track which tokens may require special handling at the document level as they are (or have been at some point) of category <i>⟨active⟩</i> (catcode 13). Each entry in the sequence consists of a single escaped token, for example <code>\~</code> . Active tokens should be added to the sequence when they are defined for general document use.
<hr/> <code>\l_char_special_seq</code> <div>New: 2012-01-23 Updated: 2015-11-11</div> <hr/>	Used to track which tokens will require special handling when working with verbatim-like material at the document level as they are not of categories <i>⟨letter⟩</i> (catcode 11) or <i>⟨other⟩</i> (catcode 12). Each entry in the sequence consists of a single escaped token, for example <code>\</code> for the backslash or <code>{</code> for an opening brace. Escaped tokens should be added to the sequence when they are defined for general document use.

3 Generic tokens

```
\c_group_begin_token
\c_group_end_token
\c_math_toggle_token
\c_alignment_token
\c_parameter_token
\c_math_superscript_token
\c_math_subscript_token
\c_space_token
```

These are implicit tokens which have the category code described by their name. They are used internally for test purposes but are also available to the programmer for other uses.

```
\c_catcode_letter_token
\c_catcode_other_token
```

These are implicit tokens which have the category code described by their name. They are used internally for test purposes and should not be used other than for category code tests.

```
\c_catcode_active_tl
```

A token list containing an active token. This is used internally for test purposes and should not be used other than in appropriately-constructed category code tests.

4 Converting tokens

```
\token_to_meaning:N ★
\token_to_meaning:c ★
```

`\token_to_meaning:N <token>`

Inserts the current meaning of the *<token>* into the input stream as a series of characters of category code 12 (other). This is the primitive \TeX description of the *<token>*, thus for example both functions defined by `\cs_set_nopar:Npn` and token list variables defined using `\tl_new:N` are described as macros.

\TeX hackers note: This is the \TeX primitive `\meaning`.

```
\token_to_str:N ★
\token_to_str:c ★
```

`\token_to_str:N <token>`

Converts the given *<token>* into a series of characters with category code 12 (other). If the *<token>* is a control sequence, this will start with the current escape character with category code 12 (the escape character is part of the *<token>*). This function requires only a single expansion.

\TeX hackers note: `\token_to_str:N` is the \TeX primitive `\string` renamed.

5 Token conditionals

```
\token_if_group_begin_p:N ★ \token_if_group_begin_p:N <token>
\token_if_group_begin:NTF ★ \token_if_group_begin:NTF <token> {(true code)} {(false code)}
```

Tests if *<token>* has the category code of a begin group token (`{` when normal \TeX category codes are in force). Note that an explicit begin group token cannot be tested in this way, as it is not a valid N-type argument.

<code>\token_if_group_end_p:N</code>	★	<code>\token_if_group_end_p:N</code>	$\langle token \rangle$
<code>\token_if_group_end:NTF</code>	★	<code>\token_if_group_end:NTF</code>	$\langle token \rangle$ $\{\langle true code \rangle\}$ $\{\langle false code \rangle\}$

Tests if $\langle token \rangle$ has the category code of an end group token (`}` when normal \TeX category codes are in force). Note that an explicit end group token cannot be tested in this way, as it is not a valid N-type argument.

<code>\token_if_math_toggle_p:N</code>	★	<code>\token_if_math_toggle_p:N</code>	$\langle token \rangle$
<code>\token_if_math_toggle:NTF</code>	★	<code>\token_if_math_toggle:NTF</code>	$\langle token \rangle$ $\{\langle true code \rangle\}$ $\{\langle false code \rangle\}$

Tests if $\langle token \rangle$ has the category code of a math shift token (`$` when normal \TeX category codes are in force).

<code>\token_if_alignment_p:N</code>	★	<code>\token_if_alignment_p:N</code>	$\langle token \rangle$
<code>\token_if_alignment:NTF</code>	★	<code>\token_if_alignment:NTF</code>	$\langle token \rangle$ $\{\langle true code \rangle\}$ $\{\langle false code \rangle\}$

Tests if $\langle token \rangle$ has the category code of an alignment token (`&` when normal \TeX category codes are in force).

<code>\token_if_parameter_p:N</code>	★	<code>\token_if_parameter_p:N</code>	$\langle token \rangle$
<code>\token_if_parameter:NTF</code>	★	<code>\token_if_parameter:NTF</code>	$\langle token \rangle$ $\{\langle true code \rangle\}$ $\{\langle false code \rangle\}$

Tests if $\langle token \rangle$ has the category code of a macro parameter token (`#` when normal \TeX category codes are in force).

<code>\token_if_math_superscript_p:N</code>	★	<code>\token_if_math_superscript_p:N</code>	$\langle token \rangle$
<code>\token_if_math_superscript:NTF</code>	★	<code>\token_if_math_superscript:NTF</code>	$\langle token \rangle$ $\{\langle true code \rangle\}$ $\{\langle false code \rangle\}$

Tests if $\langle token \rangle$ has the category code of a superscript token (`^` when normal \TeX category codes are in force).

<code>\token_if_math_subscript_p:N</code>	★	<code>\token_if_math_subscript_p:N</code>	$\langle token \rangle$
<code>\token_if_math_subscript:NTF</code>	★	<code>\token_if_math_subscript:NTF</code>	$\langle token \rangle$ $\{\langle true code \rangle\}$ $\{\langle false code \rangle\}$

Tests if $\langle token \rangle$ has the category code of a subscript token (`_` when normal \TeX category codes are in force).

<code>\token_if_space_p:N</code>	★	<code>\token_if_space_p:N</code>	$\langle token \rangle$
<code>\token_if_space:NTF</code>	★	<code>\token_if_space:NTF</code>	$\langle token \rangle$ $\{\langle true code \rangle\}$ $\{\langle false code \rangle\}$

Tests if $\langle token \rangle$ has the category code of a space token. Note that an explicit space token with character code 32 cannot be tested in this way, as it is not a valid N-type argument.

<code>\token_if_letter_p:N</code>	★	<code>\token_if_letter_p:N</code>	$\langle token \rangle$
<code>\token_if_letter:NTF</code>	★	<code>\token_if_letter:NTF</code>	$\langle token \rangle$ $\{\langle true code \rangle\}$ $\{\langle false code \rangle\}$

Tests if $\langle token \rangle$ has the category code of a letter token.

<code>\token_if_other_p:N</code>	★	<code>\token_if_other_p:N</code>	$\langle token \rangle$
<code>\token_if_other:NTF</code>	★	<code>\token_if_other:NTF</code>	$\langle token \rangle$ $\{\langle true code \rangle\}$ $\{\langle false code \rangle\}$

Tests if $\langle token \rangle$ has the category code of an “other” token.

<code>\token_if_active_p:N</code>	★	<code>\token_if_active_p:N</code>	$\langle token \rangle$
<code>\token_if_active:NTF</code>	★	<code>\token_if_active:NTF</code>	$\langle token \rangle$ $\{\langle true\ code \rangle\}$ $\{\langle false\ code \rangle\}$

Tests if $\langle token \rangle$ has the category code of an active character.

<code>\token_if_eq_catcode_p:NN</code>	★	<code>\token_if_eq_catcode_p:NN</code>	$\langle token_1 \rangle$ $\langle token_2 \rangle$
<code>\token_if_eq_catcode:NNTF</code>	★	<code>\token_if_eq_catcode:NNTF</code>	$\langle token_1 \rangle$ $\langle token_2 \rangle$ $\{\langle true\ code \rangle\}$ $\{\langle false\ code \rangle\}$

Tests if the two $\langle tokens \rangle$ have the same category code.

<code>\token_if_eq_charcode_p:NN</code>	★	<code>\token_if_eq_charcode_p:NN</code>	$\langle token_1 \rangle$ $\langle token_2 \rangle$
<code>\token_if_eq_charcode:NNTF</code>	★	<code>\token_if_eq_charcode:NNTF</code>	$\langle token_1 \rangle$ $\langle token_2 \rangle$ $\{\langle true\ code \rangle\}$ $\{\langle false\ code \rangle\}$

Tests if the two $\langle tokens \rangle$ have the same character code.

<code>\token_if_eq_meaning_p:NN</code>	★	<code>\token_if_eq_meaning_p:NN</code>	$\langle token_1 \rangle$ $\langle token_2 \rangle$
<code>\token_if_eq_meaning:NNTF</code>	★	<code>\token_if_eq_meaning:NNTF</code>	$\langle token_1 \rangle$ $\langle token_2 \rangle$ $\{\langle true\ code \rangle\}$ $\{\langle false\ code \rangle\}$

Tests if the two $\langle tokens \rangle$ have the same meaning when expanded.

<code>\token_if_macro_p:N</code>	★	<code>\token_if_macro_p:N</code>	$\langle token \rangle$
<code>\token_if_macro:NTF</code>	★	<code>\token_if_macro:NTF</code>	$\langle token \rangle$ $\{\langle true\ code \rangle\}$ $\{\langle false\ code \rangle\}$

Updated: 2011-05-23

Tests if the $\langle token \rangle$ is a \TeX macro.

<code>\token_if_cs_p:N</code>	★	<code>\token_if_cs_p:N</code>	$\langle token \rangle$
<code>\token_if_cs:NTF</code>	★	<code>\token_if_cs:NTF</code>	$\langle token \rangle$ $\{\langle true\ code \rangle\}$ $\{\langle false\ code \rangle\}$

Tests if the $\langle token \rangle$ is a control sequence.

<code>\token_if_expandable_p:N</code>	★	<code>\token_if_expandable_p:N</code>	$\langle token \rangle$
<code>\token_if_expandable:NTF</code>	★	<code>\token_if_expandable:NTF</code>	$\langle token \rangle$ $\{\langle true\ code \rangle\}$ $\{\langle false\ code \rangle\}$

Tests if the $\langle token \rangle$ is expandable. This test returns $\langle false \rangle$ for an undefined token.

<code>\token_if_long_macro_p:N</code>	★	<code>\token_if_long_macro_p:N</code>	$\langle token \rangle$
<code>\token_if_long_macro:NTF</code>	★	<code>\token_if_long_macro:NTF</code>	$\langle token \rangle$ $\{\langle true\ code \rangle\}$ $\{\langle false\ code \rangle\}$

Updated: 2012-01-20

Tests if the $\langle token \rangle$ is a long macro.

<code>\token_if_protected_macro_p:N</code>	★	<code>\token_if_protected_macro_p:N</code>	$\langle token \rangle$
<code>\token_if_protected_macro:NNTF</code>	★	<code>\token_if_protected_macro:NNTF</code>	$\langle token \rangle$ $\{\langle true\ code \rangle\}$ $\{\langle false\ code \rangle\}$

Updated: 2012-01-20

Tests if the $\langle token \rangle$ is a protected macro: for a macro which is both protected and long this returns **false**.

<code>\token_if_protected_long_macro_p:N</code>	★	<code>\token_if_protected_long_macro_p:N</code>	$\langle token \rangle$
<code>\token_if_protected_long_macro:NNTF</code>	★	<code>\token_if_protected_long_macro:NNTF</code>	$\langle token \rangle$ $\{\langle true\ code \rangle\}$ $\{\langle false\ code \rangle\}$

Updated: 2012-01-20

Tests if the $\langle token \rangle$ is a protected long macro.

<code>\token_if_chardef_p:N</code>	★	<code>\token_if_chardef_p:N</code>	$\langle token \rangle$
<code>\token_if_chardef:NTF</code>	★	<code>\token_if_chardef:NTF</code>	$\langle token \rangle$ $\{\langle true code \rangle\}$ $\{\langle false code \rangle\}$

Updated: 2012-01-20 Tests if the $\langle token \rangle$ is defined to be a chardef.

TeXhackers note: Booleans, boxes and small integer constants are implemented as `\chardefs`.

<code>\token_if_mathchardef_p:N</code>	★	<code>\token_if_mathchardef_p:N</code>	$\langle token \rangle$
<code>\token_if_mathchardef:NTF</code>	★	<code>\token_if_mathchardef:NTF</code>	$\langle token \rangle$ $\{\langle true code \rangle\}$ $\{\langle false code \rangle\}$

Updated: 2012-01-20

Tests if the $\langle token \rangle$ is defined to be a mathchardef.

<code>\token_if_dim_register_p:N</code>	★	<code>\token_if_dim_register_p:N</code>	$\langle token \rangle$
<code>\token_if_dim_register:NTF</code>	★	<code>\token_if_dim_register:NTF</code>	$\langle token \rangle$ $\{\langle true code \rangle\}$ $\{\langle false code \rangle\}$

Updated: 2012-01-20

Tests if the $\langle token \rangle$ is defined to be a dimension register.

<code>\token_if_int_register_p:N</code>	★	<code>\token_if_int_register_p:N</code>	$\langle token \rangle$
<code>\token_if_int_register:NTF</code>	★	<code>\token_if_int_register:NTF</code>	$\langle token \rangle$ $\{\langle true code \rangle\}$ $\{\langle false code \rangle\}$

Updated: 2012-01-20

Tests if the $\langle token \rangle$ is defined to be a integer register.

TeXhackers note: Constant integers may be implemented as integer registers, `\chardefs`, or `\mathchardefs` depending on their value.

<code>\token_if_muskip_register_p:N</code>	★	<code>\token_if_muskip_register_p:N</code>	$\langle token \rangle$
<code>\token_if_muskip_register:NTF</code>	★	<code>\token_if_muskip_register:NTF</code>	$\langle token \rangle$ $\{\langle true code \rangle\}$ $\{\langle false code \rangle\}$

New: 2012-02-15

Tests if the $\langle token \rangle$ is defined to be a muskip register.

<code>\token_if_skip_register_p:N</code>	★	<code>\token_if_skip_register_p:N</code>	$\langle token \rangle$
<code>\token_if_skip_register:NTF</code>	★	<code>\token_if_skip_register:NTF</code>	$\langle token \rangle$ $\{\langle true code \rangle\}$ $\{\langle false code \rangle\}$

Updated: 2012-01-20

Tests if the $\langle token \rangle$ is defined to be a skip register.

<code>\token_if_toks_register_p:N</code>	★	<code>\token_if_toks_register_p:N</code>	$\langle token \rangle$
<code>\token_if_toks_register:NTF</code>	★	<code>\token_if_toks_register:NTF</code>	$\langle token \rangle$ $\{\langle true code \rangle\}$ $\{\langle false code \rangle\}$

Updated: 2012-01-20

Tests if the $\langle token \rangle$ is defined to be a toks register (not used by L^AT_EX3).

<code>\token_if_primitive_p:N</code>	★	<code>\token_if_primitive_p:N</code>	$\langle token \rangle$
<code>\token_if_primitive:NTF</code>	★	<code>\token_if_primitive:NTF</code>	$\langle token \rangle$ $\{\langle true code \rangle\}$ $\{\langle false code \rangle\}$

Updated: 2011-05-23 Tests if the $\langle token \rangle$ is an engine primitive.

6 Peeking ahead at the next token

There is often a need to look ahead at the next token in the input stream while leaving it in place. This is handled using the “peek” functions. The generic `\peek_after:Nw` is provided along with a family of predefined tests for common cases. As peeking ahead does *not* skip spaces the predefined tests include both a space-respecting and space-skipping version.

`\peek_after:Nw`

`\peek_after:Nw <function> <token>`

Locally sets the test variable `\l_peek_token` equal to `<token>` (as an implicit token, *not* as a token list), and then expands the `<function>`. The `<token>` remains in the input stream as the next item after the `<function>`. The `<token>` here may be `_`, `{` or `}` (assuming normal T_EX category codes), *i.e.* it is not necessarily the next argument which would be grabbed by a normal function.

`\peek_gafter:Nw`

`\peek_gafter:Nw <function> <token>`

Globally sets the test variable `\g_peek_token` equal to `<token>` (as an implicit token, *not* as a token list), and then expands the `<function>`. The `<token>` remains in the input stream as the next item after the `<function>`. The `<token>` here may be `_`, `{` or `}` (assuming normal T_EX category codes), *i.e.* it is not necessarily the next argument which would be grabbed by a normal function.

`\l_peek_token`

Token set by `\peek_after:Nw` and available for testing as described above.

`\g_peek_token`

Token set by `\peek_gafter:Nw` and available for testing as described above.

`\peek_catcode:NTF`

`\peek_catcode:NTF <test token> {\<true code>} {\<false code>}`

Updated: 2012-12-20

Tests if the next `<token>` in the input stream has the same category code as the `<test token>` (as defined by the test `\token_if_eq_catcode:NNTF`). Spaces are respected by the test and the `<token>` is left in the input stream after the `<true code>` or `<false code>` (as appropriate to the result of the test).

`\peek_catcode_ignore_spaces:NTF`

`\peek_catcode_ignore_spaces:NTF <test token> {\<true code>} {\<false code>}`

Updated: 2012-12-20

Tests if the next non-space `<token>` in the input stream has the same category code as the `<test token>` (as defined by the test `\token_if_eq_catcode:NNTF`). Explicit and implicit space tokens (with character code 32 and category code 10) are ignored and removed by the test and the `<token>` is left in the input stream after the `<true code>` or `<false code>` (as appropriate to the result of the test).

`\peek_catcode_remove:NTF`

`\peek_catcode_remove:NTF <test token> {\<true code>} {\<false code>}`

Updated: 2012-12-20

Tests if the next `<token>` in the input stream has the same category code as the `<test token>` (as defined by the test `\token_if_eq_catcode:NNTF`). Spaces are respected by the test and the `<token>` is removed from the input stream if the test is true. The function then places either the `<true code>` or `<false code>` in the input stream (as appropriate to the result of the test).

<code>\peek_catcode_remove_ignore_spaces:NTF</code>	<code>\peek_catcode_remove_ignore_spaces:NTF <test token> {{<true code>}} {{<false code>}}</code>
Updated: 2012-12-20	

Tests if the next non-space *<token>* in the input stream has the same category code as the *<test token>* (as defined by the test `\token_if_eq_catcode:NNTF`). Explicit and implicit space tokens (with character code 32 and category code 10) are ignored and removed by the test and the *<token>* is removed from the input stream if the test is true. The function then places either the *<true code>* or *<false code>* in the input stream (as appropriate to the result of the test).

<code>\peek_charcode:NTF</code>	<code>\peek_charcode:NTF <test token> {{<true code>}} {{<false code>}}</code>
Updated: 2012-12-20	

Tests if the next *<token>* in the input stream has the same character code as the *<test token>* (as defined by the test `\token_if_eq_charcode:NNTF`). Spaces are respected by the test and the *<token>* is left in the input stream after the *<true code>* or *<false code>* (as appropriate to the result of the test).

<code>\peek_charcode_ignore_spaces:NTF</code>	<code>\peek_charcode_ignore_spaces:NTF <test token> {{<true code>}} {{<false code>}}</code>
Updated: 2012-12-20	

Tests if the next non-space *<token>* in the input stream has the same character code as the *<test token>* (as defined by the test `\token_if_eq_charcode:NNTF`). Explicit and implicit space tokens (with character code 32 and category code 10) are ignored and removed by the test and the *<token>* is left in the input stream after the *<true code>* or *<false code>* (as appropriate to the result of the test).

<code>\peek_charcode_remove:NTF</code>	<code>\peek_charcode_remove:NTF <test token> {{<true code>}} {{<false code>}}</code>
Updated: 2012-12-20	

Tests if the next *<token>* in the input stream has the same character code as the *<test token>* (as defined by the test `\token_if_eq_charcode:NNTF`). Spaces are respected by the test and the *<token>* is removed from the input stream if the test is true. The function then places either the *<true code>* or *<false code>* in the input stream (as appropriate to the result of the test).

<code>\peek_charcode_remove_ignore_spaces:NTF</code>	<code>\peek_charcode_remove_ignore_spaces:NTF <test token> {{<true code>}} {{<false code>}}</code>
Updated: 2012-12-20	

Tests if the next non-space *<token>* in the input stream has the same character code as the *<test token>* (as defined by the test `\token_if_eq_charcode:NNTF`). Explicit and implicit space tokens (with character code 32 and category code 10) are ignored and removed by the test and the *<token>* is removed from the input stream if the test is true. The function then places either the *<true code>* or *<false code>* in the input stream (as appropriate to the result of the test).

<code>\peek_meaning:NTF</code>	<code>\peek_meaning:NTF <test token> {{<true code>}} {{<false code>}}</code>
Updated: 2011-07-02	

Tests if the next *<token>* in the input stream has the same meaning as the *<test token>* (as defined by the test `\token_if_eq_meaning:NNTF`). Spaces are respected by the test and the *<token>* is left in the input stream after the *<true code>* or *<false code>* (as appropriate to the result of the test).

<code>\peek_meaning_ignore_spaces:N</code> <u>TF</u>	<code>\peek_meaning_ignore_spaces:N</code> <u>TF</u> $\langle test\ token \rangle$ $\{ \langle true\ code \rangle \}$ $\{ \langle false\ code \rangle \}$
--	---

Updated: 2012-12-05

Tests if the next non-space $\langle token \rangle$ in the input stream has the same meaning as the $\langle test\ token \rangle$ (as defined by the test `\token_if_eq_meaning:NNTF`). Explicit and implicit space tokens (with character code 32 and category code 10) are ignored and removed by the test and the $\langle token \rangle$ is left in the input stream after the $\langle true\ code \rangle$ or $\langle false\ code \rangle$ (as appropriate to the result of the test).

<code>\peek_meaning_remove:N</code> <u>TF</u>	<code>\peek_meaning_remove:N</code> <u>TF</u> $\langle test\ token \rangle$ $\{ \langle true\ code \rangle \}$ $\{ \langle false\ code \rangle \}$
---	--

Updated: 2011-07-02

Tests if the next $\langle token \rangle$ in the input stream has the same meaning as the $\langle test\ token \rangle$ (as defined by the test `\token_if_eq_meaning:NNTF`). Spaces are respected by the test and the $\langle token \rangle$ is removed from the input stream if the test is true. The function then places either the $\langle true\ code \rangle$ or $\langle false\ code \rangle$ in the input stream (as appropriate to the result of the test).

<code>\peek_meaning_remove_ignore_spaces:N</code> <u>TF</u>	<code>\peek_meaning_remove_ignore_spaces:N</code> <u>TF</u> $\langle test\ token \rangle$ $\{ \langle true\ code \rangle \}$ $\{ \langle false\ code \rangle \}$
---	--

Updated: 2012-12-05

Tests if the next non-space $\langle token \rangle$ in the input stream has the same meaning as the $\langle test\ token \rangle$ (as defined by the test `\token_if_eq_meaning:NNTF`). Explicit and implicit space tokens (with character code 32 and category code 10) are ignored and removed by the test and the $\langle token \rangle$ is removed from the input stream if the test is true. The function then places either the $\langle true\ code \rangle$ or $\langle false\ code \rangle$ in the input stream (as appropriate to the result of the test).

7 Decomposing a macro definition

These functions decompose \TeX macros into their constituent parts: if the $\langle token \rangle$ passed is not a macro then no decomposition can occur. In the latter case, all three functions leave `\scan_stop:` in the input stream.

<code>\token_get_arg_spec:N</code> ★	<code>\token_get_arg_spec:N</code> $\langle token \rangle$
--------------------------------------	--

If the $\langle token \rangle$ is a macro, this function leaves the primitive \TeX argument specification in input stream as a string of tokens of category code 12 (with spaces having category code 10). Thus for example for a token `\next` defined by

`\cs_set:Npn \next #1#2 { x #1 y #2 }`

leaves `#1#2` in the input stream. If the $\langle token \rangle$ is not a macro then `\scan_stop:` is left in the input stream.

\TeX hackers note: If the arg spec. contains the string `->`, then the `spec` function produces incorrect results.

`\token_get_replacement_spec:N` ★ `\token_get_replacement_spec:N` $\langle token \rangle$

If the $\langle token \rangle$ is a macro, this function leaves the replacement text in input stream as a string of tokens of category code 12 (with spaces having category code 10). Thus for example for a token `\next` defined by

`\cs_set:Npn \next #1#2 { x #1~y #2 }`

leaves `x#1 y#2` in the input stream. If the $\langle token \rangle$ is not a macro then `\scan_stop:` is left in the input stream.

TeXhackers note: If the arg spec. contains the string `->`, then the `spec` function produces incorrect results.

`\token_get_prefix_spec:N` ★ `\token_get_prefix_spec:N` $\langle token \rangle$

If the $\langle token \rangle$ is a macro, this function leaves the TeX prefixes applicable in input stream as a string of tokens of category code 12 (with spaces having category code 10). Thus for example for a token `\next` defined by

`\cs_set:Npn \next #1#2 { x #1~y #2 }`

leaves `\long` in the input stream. If the $\langle token \rangle$ is not a macro then `\scan_stop:` is left in the input stream

8 Description of all possible tokens

Let us end by reviewing every case that a given token can fall into. This section is quite technical and some details are only meant for completeness. We distinguish the meaning of the token, which controls the expansion of the token and its effect on TeX's state, and its shape, which is used when comparing token lists such as for delimited arguments. Two tokens of the same shape must have the same meaning, but the converse does not hold.

A token has one of the following shapes.

- A control sequence, characterized by the sequence of characters that constitute its name: for instance, `\use:n` is a five-letter control sequence.
- An active character token, characterized by its character code (between 0 and 1114111 for LuaTeX and XeTeX and less for other engines) and category code 13.
- A character token, characterized by its character code and category code (one of 1, 2, 3, 4, 6, 7, 8, 10, 11 or 12 whose meaning is described below).⁴

There are also a few internal tokens. The following list may be incomplete in some engines.

- Expanding `\the\font` results in a token that looks identical to the command that was used to select the current font (such as `\tenrm`) but it differs from it in shape.

⁴In LuaTeX, there is also the case of “bytes”, which behave as character tokens of category code 12 (other) and character code between 1114112 and 1114366. They are used to output individual bytes to files, rather than UTF-8.

- A “frozen” `\relax`, which differs from the primitive in shape (but has the same meaning), is inserted when the closing `\fi` of a conditional is encountered before the conditional is evaluated.
- Expanding `\noexpand <token>` (when the `<token>` is expandable) results in an internal token, displayed (temporarily) as `\notexpanded: <token>`, whose shape coincides with the `<token>` and whose meaning differs from `\relax`.
- An `\outer endtemplate:` (expanding to another internal token, `end of alignment template`) can be encountered when peeking ahead at the next token.
- Tricky programming might access a frozen `\endwrite`.
- Some frozen tokens can only be accessed in interactive sessions: `\cr`, `\right`, `\endgroup`, `\fi`, `\inaccessible`.

The meaning of a (non-active) character token is fixed by its category code (and character code) and cannot be changed. We call these tokens *explicit* character tokens. Category codes that a character token can have are listed below by giving a sample output of the \TeX primitive `\meaning`, together with their \LaTeX 3 names and most common example:

- 1 begin-group character (`group_begin`, often `{`),
- 2 end-group character (`group_end`, often `}`),
- 3 math shift character (`math_toggle`, often `$`),
- 4 alignment tab character (`alignment`, often `&`),
- 6 macro parameter character (`parameter`, often `#`),
- 7 superscript character (`math_superscript`, often `^`),
- 8 subscript character (`math_subscript`, often `_`),
- 10 blank space (`space`, often character code 32),
- 11 the letter (`letter`, such as `A`),
- 12 the character (`other`, such as `0`).

Category code 13 (`active`) is discussed below. Input characters can also have several other category codes which do not lead to character tokens for later processing: 0 (`escape`), 5 (`end_line`), 9 (`ignore`), 14 (`comment`), and 15 (`invalid`).

The meaning of a control sequence or active character can be identical to that of any character token listed above (with any character code), and we call such tokens *implicit* character tokens. The meaning is otherwise in the following list:

- a macro, used in \LaTeX 3 for most functions and some variables (`tl`, `fp`, `seq`, ...),
- a primitive such as `\def` or `\topmark`, used in \LaTeX 3 for some functions,
- a register such as `\count123`, used in \LaTeX 3 for the implementation of some variables (`int`, `dim`, ...),
- a constant integer such as `\char"56` or `\mathchar"121`,

- a font selection command,
- undefined.

Macros be `\protected` or not, `\long` or not (the opposite of what L^AT_EX3 calls `nopar`), and `\outer` or not (unused in L^AT_EX3). Their `\meaning` takes the form

$\langle properties \rangle \text{ macro: } \langle parameters \rangle \rightarrow \langle replacement \rangle$

where $\langle properties \rangle$ is among `\protected\long\outer`, $\langle parameters \rangle$ describes parameters that the macro expects, such as `#1#2#3`, and $\langle replacement \rangle$ describes how the parameters are manipulated, such as `#2/#1/#3`.

Now is perhaps a good time to mention some subtleties relating to tokens with category code 10 (space). Any input character with this category code (normally, space and tab characters) becomes a normal space, with character code 32 and category code 10.

When a macro takes an undelimited argument, explicit space characters (with character code 32 and category code 10) are ignored. If the following token is an explicit character token with category code 1 (begin-group) and an arbitrary character code, then T_EX scans ahead to obtain an equal number of explicit character tokens with category code 1 (begin-group) and 2 (end-group), and the resulting list of tokens (with outer braces removed) becomes the argument. Otherwise, a single token is taken as the argument for the macro: we call such single tokens “N-type”, as they are suitable to be used as an argument for a function with the signature `:N`.

9 Internal functions

`_char_generate:nn` ★

New: 2016-03-25

`_char_generate:nn` $\{ \langle charcode \rangle \} \{ \langle catcode \rangle \}$

This function is identical in operation to the public `\char_generate:nn` but omits various sanity tests. In particular, this means it is used in certain places where engine variations need to be accounted for by the kernel. The $\langle catcode \rangle$ must give an explicit integer when expanded (and must not absorb a space for instance).

Part XVI

The l3prop package

Property lists

L^AT_EX3 implements a “property list” data type, which contain an unordered list of entries each of which consists of a $\langle key \rangle$ and an associated $\langle value \rangle$. The $\langle key \rangle$ and $\langle value \rangle$ may both be any $\langle balanced\ text \rangle$. It is possible to map functions to property lists such that the function is applied to every key–value pair within the list.

Each entry in a property list must have a unique $\langle key \rangle$: if an entry is added to a property list which already contains the $\langle key \rangle$ then the new entry overwrites the existing one. The $\langle keys \rangle$ are compared on a string basis, using the same method as `\str_if_eq:nn`.

Property lists are intended for storing key-based information for use within code. This is in contrast to key–value lists, which are a form of *input* parsed by the `keys` module.

1 Creating and initialising property lists

 $\backslash\text{prop_new:N}$
 $\backslash\text{prop_new:c}$

 $\backslash\text{prop_new:N}$ $\langle property\ list \rangle$

Creates a new $\langle property\ list \rangle$ or raises an error if the name is already taken. The declaration is global. The $\langle property\ list \rangle$ initially contains no entries.

 $\backslash\text{prop_clear:N}$
 $\backslash\text{prop_clear:c}$
 $\backslash\text{prop_gclear:N}$
 $\backslash\text{prop_gclear:c}$

 $\backslash\text{prop_clear:N}$ $\langle property\ list \rangle$

Clears all entries from the $\langle property\ list \rangle$.

 $\backslash\text{prop_clear_new:N}$
 $\backslash\text{prop_clear_new:c}$
 $\backslash\text{prop_gclear_new:N}$
 $\backslash\text{prop_gclear_new:c}$

 $\backslash\text{prop_clear_new:N}$ $\langle property\ list \rangle$

Ensures that the $\langle property\ list \rangle$ exists globally by applying $\backslash\text{prop_new:N}$ if necessary, then applies $\backslash\text{prop_gclear:N}$ to leave the list empty.

 $\backslash\text{prop_set_eq:NN}$
 $\backslash\text{prop_set_eq:(cN|Nc|cc)}$
 $\backslash\text{prop_gset_eq:NN}$
 $\backslash\text{prop_gset_eq:(cN|Nc|cc)}$

 $\backslash\text{prop_set_eq:NN}$ $\langle property\ list_1 \rangle$ $\langle property\ list_2 \rangle$

Sets the content of $\langle property\ list_1 \rangle$ equal to that of $\langle property\ list_2 \rangle$.

2 Adding entries to property lists

<code>\prop_put:Nnn</code> <code>\prop_put: (NnV Nno Nnx NVn NVV Non Noo cnn cnV cno cnx cVn cVV con coo)</code> <code>\prop_gput:Nnn</code> <code>\prop_gput: (NnV Nno Nnx NVn NVV Non Noo cnn cnV cno cnx cVn cVV con coo)</code>	<code>\prop_put:Nnn <property list></code> <code>{<key>} {<value>}</code>
--	--

Updated: 2012-07-09

Adds an entry to the *<property list>* which may be accessed using the *<key>* and which has *<value>*. Both the *<key>* and *<value>* may contain any *<balanced text>*. The *<key>* is stored after processing with `\tl_to_str:n`, meaning that category codes are ignored. If the *<key>* is already present in the *<property list>*, the existing entry is overwritten by the new *<value>*.

<code>\prop_put_if_new:Nnn</code> <code>\prop_put_if_new:cnn</code> <code>\prop_gput_if_new:Nnn</code> <code>\prop_gput_if_new:cnn</code>	<code>\prop_put_if_new:Nnn <property list> {<key>} {<value>}</code>
--	---

If the *<key>* is present in the *<property list>* then no action is taken. If the *<key>* is not present in the *<property list>* then a new entry is added. Both the *<key>* and *<value>* may contain any *<balanced text>*. The *<key>* is stored after processing with `\tl_to_str:n`, meaning that category codes are ignored.

3 Recovering values from property lists

<code>\prop_get:NnN</code> <code>\prop_get: (NVN NoN cnN cVN coN)</code>	<code>\prop_get:NnN <property list> {<key>} <tl var></code>
---	---

Updated: 2011-08-28

Recovers the *<value>* stored with *<key>* from the *<property list>*, and places this in the *<token list variable>*. If the *<key>* is not found in the *<property list>* then the *<token list variable>* is set to the special marker `\q_no_value`. The *<token list variable>* is set within the current TeX group. See also `\prop_get:NnNTF`.

<code>\prop_pop:NnN</code> <code>\prop_pop: (NoN cnN coN)</code>	<code>\prop_pop:NnN <property list> {<key>} <tl var></code>
---	---

Updated: 2011-08-18

Recovers the *<value>* stored with *<key>* from the *<property list>*, and places this in the *<token list variable>*. If the *<key>* is not found in the *<property list>* then the *<token list variable>* is set to the special marker `\q_no_value`. The *<key>* and *<value>* are then deleted from the property list. Both assignments are local. See also `\prop_pop:NnNTF`.

<code>\prop_gpop:NnN</code> <code>\prop_gpop: (NoN cnN coN)</code>	<code>\prop_gpop:NnN <property list> {<key>} <tl var></code>
---	--

Updated: 2011-08-18

Recovers the *<value>* stored with *<key>* from the *<property list>*, and places this in the *<token list variable>*. If the *<key>* is not found in the *<property list>* then the *<token list variable>* is set to the special marker `\q_no_value`. The *<key>* and *<value>* are then deleted from the property list. The *<property list>* is modified globally, while the assignment of the *<token list variable>* is local. See also `\prop_gpop:NnNTF`.

<code>\prop_item:Nn</code> ★	<code>\prop_item:Nn</code> $\langle property list \rangle$ $\{\langle key \rangle\}$
------------------------------	--

<code>\prop_item:cn</code> ★

New: 2014-07-17

Expands to the $\langle value \rangle$ corresponding to the $\langle key \rangle$ in the $\langle property list \rangle$. If the $\langle key \rangle$ is missing, this has an empty expansion.

TeXhackers note: This function is slower than the non-expandable analogue `\prop_get:NnN`. The result is returned within the `\unexpanded` primitive (`\exp_not:n`), which means that the $\langle value \rangle$ does not expand further when appearing in an `x`-type argument expansion.

4 Modifying property lists

<code>\prop_remove:Nn</code>

<code>\prop_remove:(NV cn cV)</code>

<code>\prop_gremove:Nn</code>

<code>\prop_gremove:(NV cn cV)</code>

New: 2012-05-12

<code>\prop_remove:Nn</code> $\langle property list \rangle$ $\{\langle key \rangle\}$
--

Removes the entry listed under $\langle key \rangle$ from the $\langle property list \rangle$. If the $\langle key \rangle$ is not found in the $\langle property list \rangle$ no change occurs, *i.e* there is no need to test for the existence of a key before deleting it.

5 Property list conditionals

<code>\prop_if_exist_p:N</code> ★

<code>\prop_if_exist_p:c</code> ★

<code>\prop_if_exist:NTF</code> ★

<code>\prop_if_exist:cTF</code> ★

New: 2012-03-03

<code>\prop_if_exist_p:N</code> $\langle property list \rangle$

<code>\prop_if_exist:NTF</code> $\langle property list \rangle$ $\{\langle true code \rangle\}$ $\{\langle false code \rangle\}$
--

Tests whether the $\langle property list \rangle$ is currently defined. This does not check that the $\langle property list \rangle$ really is a property list variable.

<code>\prop_if_empty_p:N</code> ★

<code>\prop_if_empty_p:c</code> ★

<code>\prop_if_empty:NTF</code> ★

<code>\prop_if_empty:cTF</code> ★

<code>\prop_if_empty_p:N</code> $\langle property list \rangle$

<code>\prop_if_empty:NTF</code> $\langle property list \rangle$ $\{\langle true code \rangle\}$ $\{\langle false code \rangle\}$
--

Tests if the $\langle property list \rangle$ is empty (containing no entries).

<code>\prop_if_in_p:Nn</code>	★	<code>\prop_if_in:NnTF</code> $\langle property list \rangle$ $\{\langle key \rangle\}$ $\{\langle true code \rangle\}$ $\{\langle false code \rangle\}$
-------------------------------	---	--

<code>\prop_if_in_p:(NV No cn cV co)</code>	★
---	---

<code>\prop_if_in:NnTF</code>	★
-------------------------------	---

<code>\prop_if_in:(NV No cn cV co)TF</code>	★
---	---

Updated: 2011-09-15

Tests if the $\langle key \rangle$ is present in the $\langle property list \rangle$, making the comparison using the method described by `\str_if_eq:nnTF`.

TeXhackers note: This function iterates through every key–value pair in the $\langle property list \rangle$ and is therefore slower than using the non-expandable `\prop_get:NnNTF`.

6 Recovering values from property lists with branching

The functions in this section combine tests for the presence of a key in a property list with recovery of the associated valued. This makes them useful for cases where different cases follow dependent on the presence or absence of a key in a property list. They offer increased readability and performance over separate testing and recovery phases.

<u>\prop_get:NnNTF</u>	<u>\prop_get:NnNTF</u> $\langle \text{property list} \rangle$ $\{\langle \text{key} \rangle\}$ $\langle \text{token list variable} \rangle$
<u>\prop_get:(NVN NoN cnN cVN coN)TF</u>	<u>\prop_get:(NVN NoN cnN cVN coN)TF</u> $\{\langle \text{true code} \rangle\}$ $\{\langle \text{false code} \rangle\}$
Updated: 2012-05-19	

If the $\langle \text{key} \rangle$ is not present in the $\langle \text{property list} \rangle$, leaves the $\langle \text{false code} \rangle$ in the input stream. The value of the $\langle \text{token list variable} \rangle$ is not defined in this case and should not be relied upon. If the $\langle \text{key} \rangle$ is present in the $\langle \text{property list} \rangle$, stores the corresponding $\langle \text{value} \rangle$ in the $\langle \text{token list variable} \rangle$ without removing it from the $\langle \text{property list} \rangle$, then leaves the $\langle \text{true code} \rangle$ in the input stream. The $\langle \text{token list variable} \rangle$ is assigned locally.

<u>\prop_pop:NnNTF</u>	<u>\prop_pop:NnNTF</u> $\langle \text{property list} \rangle$ $\{\langle \text{key} \rangle\}$ $\langle \text{token list variable} \rangle$ $\{\langle \text{true code} \rangle\}$
<u>\prop_pop:cnNTF</u>	<u>\prop_pop:cnNTF</u> $\{\langle \text{false code} \rangle\}$
New: 2011-08-18	If the $\langle \text{key} \rangle$ is not present in the $\langle \text{property list} \rangle$, leaves the $\langle \text{false code} \rangle$ in the input stream. The value of the $\langle \text{token list variable} \rangle$ is not defined in this case and should not be relied upon. If the $\langle \text{key} \rangle$ is present in the $\langle \text{property list} \rangle$, pops the corresponding $\langle \text{value} \rangle$ in the $\langle \text{token list variable} \rangle$, <i>i.e.</i> removes the item from the $\langle \text{property list} \rangle$. Both the $\langle \text{property list} \rangle$ and the $\langle \text{token list variable} \rangle$ are assigned locally.
Updated: 2012-05-19	

<u>\prop_gpop:NnNTF</u>	<u>\prop_gpop:NnNTF</u> $\langle \text{property list} \rangle$ $\{\langle \text{key} \rangle\}$ $\langle \text{token list variable} \rangle$ $\{\langle \text{true code} \rangle\}$
<u>\prop_gpop:cnNTF</u>	<u>\prop_gpop:cnNTF</u> $\{\langle \text{false code} \rangle\}$
New: 2011-08-18	If the $\langle \text{key} \rangle$ is not present in the $\langle \text{property list} \rangle$, leaves the $\langle \text{false code} \rangle$ in the input stream. The value of the $\langle \text{token list variable} \rangle$ is not defined in this case and should not be relied upon. If the $\langle \text{key} \rangle$ is present in the $\langle \text{property list} \rangle$, pops the corresponding $\langle \text{value} \rangle$ in the $\langle \text{token list variable} \rangle$, <i>i.e.</i> removes the item from the $\langle \text{property list} \rangle$. The $\langle \text{property list} \rangle$ is modified globally, while the $\langle \text{token list variable} \rangle$ is assigned locally.
Updated: 2012-05-19	

7 Mapping to property lists

<u>\prop_map_function:NN</u> ☆	<u>\prop_map_function:NN</u> $\langle \text{property list} \rangle$ $\langle \text{function} \rangle$
<u>\prop_map_function:cN</u> ☆	Applies $\langle \text{function} \rangle$ to every $\langle \text{entry} \rangle$ stored in the $\langle \text{property list} \rangle$. The $\langle \text{function} \rangle$ receives two argument for each iteration: the $\langle \text{key} \rangle$ and associated $\langle \text{value} \rangle$. The order in which $\langle \text{entries} \rangle$ are returned is not defined and should not be relied upon.
Updated: 2013-01-28	

<u>\prop_map_inline:Nn</u>	<u>\prop_map_inline:Nn</u> $\langle \text{property list} \rangle$ $\{\langle \text{inline function} \rangle\}$
<u>\prop_map_inline:cn</u>	Applies $\langle \text{inline function} \rangle$ to every $\langle \text{entry} \rangle$ stored within the $\langle \text{property list} \rangle$. The $\langle \text{inline function} \rangle$ should consist of code which receives the $\langle \text{key} \rangle$ as #1 and the $\langle \text{value} \rangle$ as #2. The order in which $\langle \text{entries} \rangle$ are returned is not defined and should not be relied upon.
Updated: 2013-01-08	

\prop_map_break: ☆

Updated: 2012-06-29

\prop_map_break:

Used to terminate a `\prop_map...` function before all entries in the *property list* have been processed. This normally takes place within a conditional statement, for example

```
\prop_map_inline:Nn \l_my_prop
{
  \str_if_eq:nnTF { #1 } { bingo }
  { \prop_map_break: }
  {
    % Do something useful
  }
}
```

Use outside of a `\prop_map...` scenario leads to low level TeX errors.

TeXhackers note: When the mapping is broken, additional tokens may be inserted before further items are taken from the input stream. This depends on the design of the mapping function.

\prop_map_break:n ☆

Updated: 2012-06-29

\prop_map_break:n {<code>}

Used to terminate a `\prop_map...` function before all entries in the *property list* have been processed, inserting the *code* after the mapping has ended. This normally takes place within a conditional statement, for example

```
\prop_map_inline:Nn \l_my_prop
{
  \str_if_eq:nnTF { #1 } { bingo }
  { \prop_map_break:n { <code> } }
  {
    % Do something useful
  }
}
```

Use outside of a `\prop_map...` scenario leads to low level TeX errors.

TeXhackers note: When the mapping is broken, additional tokens may be inserted before the *code* is inserted into the input stream. This depends on the design of the mapping function.

8 Viewing property lists

\prop_show:N

\prop_show:c

Updated: 2015-08-01

\prop_show:N *property list*

Displays the entries in the *property list* in the terminal.

`\prop_log:N`
`\prop_log:c`

New: 2014-08-12
Updated: 2015-08-01

`\prop_log:N` $\langle property\ list \rangle$
Writes the entries in the $\langle property\ list \rangle$ in the log file.

9 Scratch property lists

`\l_tmpa_prop`
`\l_tmpb_prop`

New: 2012-06-23

Scratch property lists for local assignment. These are never used by the kernel code, and so are safe for use with any L^AT_EX3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.

`\g_tmpa_prop`
`\g_tmpb_prop`

New: 2012-06-23

Scratch property lists for global assignment. These are never used by the kernel code, and so are safe for use with any L^AT_EX3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.

10 Constants

`\c_empty_prop`

A permanently-empty property list used for internal comparisons.

11 Internal property list functions

`\s__prop`

The internal token used at the beginning of property lists. This is also used after each $\langle key \rangle$ (see `__prop_pair:wn`).

`__prop_pair:wn`

`__prop_pair:wn` $\langle key \rangle$ `\s__prop` $\{ \langle item \rangle \}$

The internal token used to begin each key–value pair in the property list. If expanded outside of a mapping or manipulation function, an error is raised. The definition should always be set globally.

`\l__prop_internal_tl`

Token list used to store new key–value pairs to be inserted by functions of the `\prop_put:Nnn` family.

`__prop_split:NnTF`

Updated: 2013-01-08

`__prop_split:NnTF` $\langle\textit{property list}\rangle$ $\{\langle\textit{key}\rangle\}$ $\{\langle\textit{true code}\rangle\}$ $\{\langle\textit{false code}\rangle\}$

Splits the $\langle\textit{property list}\rangle$ at the $\langle\textit{key}\rangle$, giving three token lists: the $\langle\textit{extract}\rangle$ of $\langle\textit{property list}\rangle$ before the $\langle\textit{key}\rangle$, the $\langle\textit{value}\rangle$ associated with the $\langle\textit{key}\rangle$ and the $\langle\textit{extract}\rangle$ of the $\langle\textit{property list}\rangle$ after the $\langle\textit{value}\rangle$. Both $\langle\textit{extracts}\rangle$ retain the internal structure of a property list, and the concatenation of the two $\langle\textit{extracts}\rangle$ is a property list. If the $\langle\textit{key}\rangle$ is present in the $\langle\textit{property list}\rangle$ then the $\langle\textit{true code}\rangle$ is left in the input stream, with #1, #2, and #3 replaced by the first $\langle\textit{extract}\rangle$, the $\langle\textit{value}\rangle$, and the second $\langle\textit{extract}\rangle$. If the $\langle\textit{key}\rangle$ is not present in the $\langle\textit{property list}\rangle$ then the $\langle\textit{false code}\rangle$ is left in the input stream, with no trailing material. Both $\langle\textit{true code}\rangle$ and $\langle\textit{false code}\rangle$ are used in the replacement text of a macro defined internally, hence macro parameter characters should be doubled, except #1, #2, and #3 which stand in the $\langle\textit{true code}\rangle$ for the three $\langle\textit{extracts}\rangle$ from the property list. The $\langle\textit{key}\rangle$ comparison takes place as described for `\str_if_eq:nn`.

Part XVII

The l3msg package

Messages

Messages need to be passed to the user by modules, either when errors occur or to indicate how the code is proceeding. The `l3msg` module provides a consistent method for doing this (as opposed to writing directly to the terminal or log).

The system used by `l3msg` to create messages divides the process into two distinct parts. Named messages are created in the first part of the process; at this stage, no decision is made about the type of output that the message will produce. The second part of the process is actually producing a message. At this stage a choice of message *class* has to be made, for example `error`, `warning` or `info`.

By separating out the creation and use of messages, several benefits are available. First, the messages can be altered later without needing details of where they are used in the code. This makes it possible to alter the language used, the detail level and so on. Secondly, the output which results from a given message can be altered. This can be done on a message class, module or message name basis. In this way, message behaviour can be altered and messages can be entirely suppressed.

1 Creating new messages

All messages have to be created before they can be used. The text of messages is automatically wrapped to the length available in the console. As a result, formatting is only needed where it helps to show meaning. In particular, `\\` may be used to force a new line and `_` forces an explicit space. Additionally, `\{`, `\#`, `\}`, `\%` and `\~` can be used to produce the corresponding character.

Messages may be subdivided *by one level* using the `/` character. This is used within the message filtering system to allow for example the L^AT_EX kernel messages to belong to the module `LaTeX` while still being filterable at a more granular level. Thus for example

```
\msg_new:nnnn { mymodule } { submodule / message } ...
```

will allow to filter out specifically messages from the `submodule`.

```
\msg_new:nnnn
\msg_new:nnn
Updated: 2011-08-16
```

```
\msg_new:nnnn {<module>} {<message>} {<text>} {<more text>}
```

Creates a `<message>` for a given `<module>`. The message is defined to first give `<text>` and then `<more text>` if the user requests it. If no `<more text>` is available then a standard text is given instead. Within `<text>` and `<more text>` four parameters (`#1` to `#4`) can be used: these will be supplied at the time the message is used. An error is raised if the `<message>` already exists.

```
\msg_set:nnnn
\msg_set:nnn
\msg_gset:nnnn
\msg_gset:nnn
```

```
\msg_set:nnnn {<module>} {<message>} {<text>} {<more text>}
```

Sets up the text for a `<message>` for a given `<module>`. The message is defined to first give `<text>` and then `<more text>` if the user requests it. If no `<more text>` is available then a standard text is given instead. Within `<text>` and `<more text>` four parameters (`#1` to `#4`) can be used: these will be supplied at the time the message is used.

<code>\msg_if_exist_p:nn</code> ★	<code>\msg_if_exist_p:nn {<module>} {<message>}</code>
<code>\msg_if_exist:nnTF</code> ★	<code>\msg_if_exist:nnTF {<module>} {<message>} {<true code>} {<false code>}</code>
New: 2012-03-03	Tests whether the <i><message></i> for the <i><module></i> is currently defined.

2 Contextual information for messages

<code>\msg_line_context:</code> ☆	<code>\msg_line_context:</code>
	Prints the current line number when a message is given, and thus suitable for giving context to messages. The number itself is preceded by the text <code>on line</code> .

<code>\msg_line_number:</code> ★	<code>\msg_line_number:</code>
	Prints the current line number when a message is given.

<code>\msg_fatal_text:n</code> ★	<code>\msg_fatal_text:n {<module>}</code>
	Produces the standard text
	<code>Fatal <module> error</code>
	This function can be redefined to alter the language in which the message is given, using #1 as the name of the <i><module></i> to be included.

<code>\msg_critical_text:n</code> ★	<code>\msg_critical_text:n {<module>}</code>
	Produces the standard text
	<code>Critical <module> error</code>
	This function can be redefined to alter the language in which the message is given, using #1 as the name of the <i><module></i> to be included.

<code>\msg_error_text:n</code> ★	<code>\msg_error_text:n {<module>}</code>
	Produces the standard text
	<code><module> error</code>
	This function can be redefined to alter the language in which the message is given, using #1 as the name of the <i><module></i> to be included.

<code>\msg_warning_text:n</code> ★	<code>\msg_warning_text:n {<module>}</code>
	Produces the standard text
	<code><module> warning</code>
	This function can be redefined to alter the language in which the message is given, using #1 as the name of the <i><module></i> to be included.

`\msg_info_text:n` ★ `\msg_info_text:n {<module>}`

Produces the standard text:

`<module> info`

This function can be redefined to alter the language in which the message is given, using #1 as the name of the `<module>` to be included.

`\msg_see_documentation_text:n` ★ `\msg_see_documentation_text:n {<module>}`

Produces the standard text

`See the <module> documentation for further information.`

This function can be redefined to alter the language in which the message is given, using #1 as the name of the `<module>` to be included.

3 Issuing messages

Messages behave differently depending on the message class. In all cases, the message may be issued supplying 0 to 4 arguments. If the number of arguments supplied here does not match the number in the definition of the message, extra arguments are ignored, or empty arguments added (of course the sense of the message may be impaired). The four arguments are converted to strings before being added to the message text: the x-type variants should be used to expand material.

`\msg_fatal:nnnnnn` `\msg_fatal:nnnnnn {<module>} {<message>} {<arg one>} {<arg two>} {<arg three>} {<arg four>}`
`\msg_fatal:nnxxxx`
`\msg_fatal:nnnnn` Issues `<module>` error `<message>`, passing `<arg one>` to `<arg four>` to the text-creating
`\msg_fatal:nnxxx` functions. After issuing a fatal error the `TEX` run halts.
`\msg_fatal:nnnn`
`\msg_fatal:nnxx`
`\msg_fatal:nnn`
`\msg_fatal:nnx`
`\msg_fatal:nn`

Updated: 2012-08-11

`\msg_critical:nnnnnn` `\msg_critical:nnnnnn {<module>} {<message>} {<arg one>} {<arg two>} {<arg three>} {<arg four>}`
`\msg_critical:nnxxxx`

`\msg_critical:nnnnn` Issues `<module>` error `<message>`, passing `<arg one>` to `<arg four>` to the text-creating
`\msg_critical:nnxxx` functions. After issuing a critical error, `TEX` stops reading the current input file. This
`\msg_critical:nnnn` may halt the `TEX` run (if the current file is the main file) or may abort reading a sub-file.
`\msg_critical:nnxx`

`\msg_critical:nnn` **T_EXhackers note:** The `TEX \endinput` primitive is used to exit the file. In particular,
`\msg_critical:nnx` the rest of the current line remains in the input stream.
`\msg_critical:nn`

Updated: 2012-08-11

<code>\msg_error:nnnnnn</code>	<code>\msg_error:nnnnnn {<module>} {<message>} {<arg one>} {<arg two>} {<arg three>} {<arg four>}</code>
<code>\msg_error:nnxxxx</code>	
<code>\msg_error:nnnnn</code>	Issues <i><module></i> error <i><message></i> , passing <i><arg one></i> to <i><arg four></i> to the text-creating functions. The error interrupts processing and issues the text at the terminal. After user input, the run continues.
<code>\msg_error:nnxxx</code>	
<code>\msg_error:nnnn</code>	
<code>\msg_error:nnxx</code>	
<code>\msg_error:nnn</code>	
<code>\msg_error:nnx</code>	
<code>\msg_error:nn</code>	

Updated: 2012-08-11

<code>\msg_warning:nnnnnn</code>	<code>\msg_warning:nnxxxx {<module>} {<message>} {<arg one>} {<arg two>} {<arg three>} {<arg four>}</code>
<code>\msg_warning:nnxxxx</code>	
<code>\msg_warning:nnnnn</code>	Issues <i><module></i> warning <i><message></i> , passing <i><arg one></i> to <i><arg four></i> to the text-creating functions. The warning text is added to the log file and the terminal, but the \TeX run is not interrupted.
<code>\msg_warning:nnxxx</code>	
<code>\msg_warning:nnnn</code>	
<code>\msg_warning:nnxx</code>	
<code>\msg_warning:nnn</code>	
<code>\msg_warning:nnx</code>	
<code>\msg_warning:nn</code>	

Updated: 2012-08-11

<code>\msg_info:nnnnnn</code>	<code>\msg_info:nnnnnn {<module>} {<message>} {<arg one>} {<arg two>} {<arg three>} {<arg four>}</code>
<code>\msg_info:nnxxxx</code>	
<code>\msg_info:nnnnn</code>	Issues <i><module></i> information <i><message></i> , passing <i><arg one></i> to <i><arg four></i> to the text-creating functions. The information text is added to the log file.
<code>\msg_info:nnxxx</code>	
<code>\msg_info:nnnn</code>	
<code>\msg_info:nnxx</code>	
<code>\msg_info:nnn</code>	
<code>\msg_info:nnx</code>	
<code>\msg_info:nn</code>	

Updated: 2012-08-11

<code>\msg_log:nnnnnn</code>	<code>\msg_log:nnnnnn {<module>} {<message>} {<arg one>} {<arg two>} {<arg three>} {<arg four>}</code>
<code>\msg_log:nnxxxx</code>	
<code>\msg_log:nnnnn</code>	Issues <i><module></i> information <i><message></i> , passing <i><arg one></i> to <i><arg four></i> to the text-creating functions. The information text is added to the log file: the output is briefer than <code>\msg_info:nnnnnn</code> .
<code>\msg_log:nnxxx</code>	
<code>\msg_log:nnnn</code>	
<code>\msg_log:nnxx</code>	
<code>\msg_log:nnn</code>	
<code>\msg_log:nnx</code>	
<code>\msg_log:nn</code>	

Updated: 2012-08-11

<pre> \msg_none:nnnnnn \msg_none:nnxxxx \msg_none:nnnnn \msg_none:nnxxx \msg_none:nnnn \msg_none:nnxx \msg_none:nnn \msg_none:nnx \msg_none:nn </pre>	<pre> \msg_none:nnnnnn {<module>} {<message>} {<arg one>} {<arg two>} {<arg three>} {<arg four>}} </pre> <p>Does nothing: used as a message class to prevent any output at all (see the discussion of message redirection).</p>
---	---

Updated: 2012-08-11

4 Redirecting messages

Each message has a “name”, which can be used to alter the behaviour of the message when it is given. Thus we might have

```
\msg_new:nnnn { module } { my-message } { Some-text } { Some-more-text }
```

to define a message, with

```
\msg_error:nn { module } { my-message }
```

when it is used. With no filtering, this raises an error. However, we could alter the behaviour with

```
\msg_redirect_class:nn { error } { warning }
```

to turn all errors into warnings, or with

```
\msg_redirect_module:nnn { module } { error } { warning }
```

to alter only messages from that module, or even

```
\msg_redirect_name:nnn { module } { my-message } { warning }
```

to target just one message. Redirection applies first to individual messages, then to messages from one module and finally to messages of one class. Thus it is possible to select out an individual message for special treatment even if the entire class is already redirected.

Multiple redirections are possible. Redirections can be cancelled by providing an empty argument for the target class. Redirection to a missing class raises an error immediately. Infinite loops are prevented by eliminating the redirection starting from the target of the redirection that caused the loop to appear. Namely, if redirections are requested as $A \rightarrow B$, $B \rightarrow C$ and $C \rightarrow A$ in this order, then the $A \rightarrow B$ redirection is cancelled.

<pre> \msg_redirect_class:nn </pre>	<pre> \msg_redirect_class:nn {<class one>} {<class two>} </pre>
-------------------------------------	---

Updated: 2012-04-27

Changes the behaviour of messages of $\langle class one \rangle$ so that they are processed using the code for those of $\langle class two \rangle$.

<code>\msg_log:n</code>	<code>\msg_log:n {<text>}</code>
-------------------------	--

New: 2012-06-28	Writes to the log file with the <i><text></i> laid out in the format
-----------------	--

```

.....
. <text>
.....

```

where the *<text>* is wrapped to fit within the current line length. Wrapping takes place using `\iow_wrap:nnnN`; the documentation for the latter should be consulted for full details.

<code>\msg_term:n</code>	<code>\msg_term:n {<text>}</code>
--------------------------	---

New: 2012-06-28	Writes to the terminal and log file with the <i><text></i> laid out in the format
-----------------	---

```

*****
* <text>
*****

```

where the *<text>* is wrapped to fit within the current line length. Wrapping takes place using `\iow_wrap:nnnN`; the documentation for the latter should be consulted for full details.

6 Kernel-specific functions

Messages from L^AT_EX3 itself are handled by the general message system, but have their own functions. This allows some text to be pre-defined, and also ensures that serious errors can be handled properly.

<code>_msg_kernel_new:nnnn</code>	<code>_msg_kernel_new:nnnn {<module>} {<message>} {<text>} {<more text>}</code>
------------------------------------	--

<code>_msg_kernel_new:nnn</code>	
-----------------------------------	--

Updated: 2011-08-16	
---------------------	--

Creates a kernel *<message>* for a given *<module>*. The message is defined to first give *<text>* and then *<more text>* if the user requests it. If no *<more text>* is available then a standard text is given instead. Within *<text>* and *<more text>* four parameters (**#1** to **#4**) can be used: these will be supplied and expanded at the time the message is used. An error is raised if the *<message>* already exists.

<code>_msg_kernel_set:nnnn</code>	<code>_msg_kernel_set:nnnn {<module>} {<message>} {<text>} {<more text>}</code>
------------------------------------	--

<code>_msg_kernel_set:nnn</code>	
-----------------------------------	--

Sets up the text for a kernel *<message>* for a given *<module>*. The message is defined to first give *<text>* and then *<more text>* if the user requests it. If no *<more text>* is available then a standard text is given instead. Within *<text>* and *<more text>* four parameters (**#1** to **#4**) can be used: these will be supplied and expanded at the time the message is used.

```

\_msg_kernel_fatal:nnnnnn
\_msg_kernel_fatal:nnxxxx
\_msg_kernel_fatal:nnnnn
\_msg_kernel_fatal:nnxxx
\_msg_kernel_fatal:nnnn
\_msg_kernel_fatal:nnxx
\_msg_kernel_fatal:nnn
\_msg_kernel_fatal:nnx
\_msg_kernel_fatal:nn

```

Updated: 2012-08-11

```

\_msg_kernel_fatal:nnnnnn {\module} {\message} {\arg one} {\arg two} {\arg
three}} {\arg four}}

```

Issues kernel *<module>* error *<message>*, passing *<arg one>* to *<arg four>* to the text-creating functions. After issuing a fatal error the T_EX run halts. Cannot be redirected.

```

\_msg_kernel_error:nnnnnn
\_msg_kernel_error:nnxxxx
\_msg_kernel_error:nnnnn
\_msg_kernel_error:nnxxx
\_msg_kernel_error:nnnn
\_msg_kernel_error:nnxx
\_msg_kernel_error:nnn
\_msg_kernel_error:nnx
\_msg_kernel_error:nn

```

Updated: 2012-08-11

```

\_msg_kernel_error:nnnnnn {\module} {\message} {\arg one} {\arg two} {\arg
three}} {\arg four}}

```

Issues kernel *<module>* error *<message>*, passing *<arg one>* to *<arg four>* to the text-creating functions. The error stops processing and issues the text at the terminal. After user input, the run continues. Cannot be redirected.

```

\_msg_kernel_warning:nnnnnn
\_msg_kernel_warning:nnxxxx
\_msg_kernel_warning:nnnnn
\_msg_kernel_warning:nnxxx
\_msg_kernel_warning:nnnn
\_msg_kernel_warning:nnxx
\_msg_kernel_warning:nnn
\_msg_kernel_warning:nnx
\_msg_kernel_warning:nn

```

Updated: 2012-08-11

```

\_msg_kernel_warning:nnnnnn {\module} {\message} {\arg one} {\arg
two}} {\arg three}} {\arg four}}

```

Issues kernel *<module>* warning *<message>*, passing *<arg one>* to *<arg four>* to the text-creating functions. The warning text is added to the log file, but the T_EX run is not interrupted.

```

\_msg_kernel_info:nnnnnn
\_msg_kernel_info:nnxxxx
\_msg_kernel_info:nnnnn
\_msg_kernel_info:nnxxx
\_msg_kernel_info:nnnn
\_msg_kernel_info:nnxx
\_msg_kernel_info:nnn
\_msg_kernel_info:nnx
\_msg_kernel_info:nn

```

Updated: 2012-08-11

```

\_msg_kernel_info:nnnnnn {\module} {\message} {\arg one} {\arg two} {\arg
three}} {\arg four}}

```

Issues kernel *<module>* information *<message>*, passing *<arg one>* to *<arg four>* to the text-creating functions. The information text is added to the log file.

7 Expandable errors

In a few places, the L^AT_EX3 kernel needs to produce errors in an expansion only context. This must be handled internally very differently from normal error messages, as none of the tools to print to the terminal or the log file are expandable. However, the interface is similar, with the important caveat that the message text and arguments are not expanded, and messages should be very short.

```

\_msg_kernel_expandable_error:nnnnnn ★ \_msg_kernel_expandable_error:nnnnnn {\module} {\message}
\_msg_kernel_expandable_error:nnnnnn ★ {\arg one} {\arg two} {\arg three} {\arg four}
\_msg_kernel_expandable_error:nnnn ★
\_msg_kernel_expandable_error:nnnn ★
\_msg_kernel_expandable_error:nnnn ★
\_msg_kernel_expandable_error:nnnn ★

```

New: 2011-11-23

Issues an error, passing $\langle arg\ one\rangle$ to $\langle arg\ four\rangle$ to the text-creating functions. The resulting string must be much shorter than a line, otherwise it is cropped.

```

\_msg_expandable_error:n ★ \_msg_expandable_error:n {\error message}

```

New: 2011-08-11

Updated: 2011-08-13

Issues an “Undefined error” message from T_EX itself, and prints the $\langle error\ message\rangle$. The $\langle error\ message\rangle$ must be short: it is cropped at the end of one line.

T_EXhackers note: This function expands to an empty token list after two steps. Tokens inserted in response to T_EX’s prompt are read with the current category code setting, and inserted just after the place where the error message was issued.

8 Internal l3msg functions

```

\c_msg_coding_error_text_tl

```

The text

This is a coding error.

used by kernel functions when erroneous programming input is encountered.

Part XVIII

The l3file package

File and I/O operations

This module provides functions for working with external files. Some of these functions apply to an entire file, and have prefix `\file_...`, while others are used to work with files on a line by line basis and have prefix `\ior_...` (reading) or `\iow_...` (writing).

It is important to remember that when reading external files \TeX attempts to locate them using both the operating system path and entries in the \TeX file database (most \TeX systems use such a database). Thus the “current path” for \TeX is somewhat broader than that for other programs.

For functions which expect a $\langle file\ name \rangle$ argument, this argument may contain both literal items and expandable content, which should on full expansion be the desired file name. Active characters (as declared in `\l_char_active_seq`) are *not* expanded, allowing the direct use of these in file names. File names are quoted using `"` tokens if they contain spaces: as a result, `"` tokens are *not* permitted in file names.

1 File operation functions

```
\g_file_curr_dir_str
\g_file_curr_name_str
\g_file_curr_ext_str
```

New: 2017-06-21

Contain the directory, name and extension of the current file. The directory is empty if the file was loaded without an explicit path (*i.e.* if it is in the \TeX search path), and does *not* end in `/` other than the case that it is exactly equal to the root directory. The $\langle name \rangle$ and $\langle ext \rangle$ parts together make up the file name, thus the $\langle name \rangle$ part may be thought of as the “job name” for the current file. Note that \TeX does not provide information on the $\langle ext \rangle$ part for the main (top level) file and that this file always has an empty $\langle dir \rangle$ component. Also, the $\langle name \rangle$ here will be equal to `\c_sys_jobname_str`, which may be different from the real file name (if set using `--jobname`, for example).

```
\l_file_search_path_seq
```

New: 2017-06-18

Each entry is the path to a directory which should be searched when seeking a file. Each path can be relative or absolute, and should not include the trailing slash. The entries are not expanded when used so may contain active characters but should not feature any variable content. Spaces need not be quoted.

\TeX hackers note: When working as a package in $\text{\LaTeX}2_{\epsilon}$, `expl3` will automatically append the current `\input@path` to the set of values from `\l_file_search_path_seq`.

```
\file_if_exist:nTF \file_if_exist:nTF {\file name} {\true code} {\false code}
```

Updated: 2012-02-10

Searches for $\langle file\ name \rangle$ using the current \TeX search path and the additional paths controlled by `\l_file_search_path_seq`.

`\file_get_full_name:nN`
`\file_get_full_name:VN`

Updated: 2017-06-26

`\file_get_full_name:nN` $\{\langle file\ name\rangle\}$ $\langle str\ var\rangle$

Searches for $\langle file\ name\rangle$ in the path as detailed for `\file_if_exist:nTF`, and if found sets the $\langle str\ var\rangle$ the fully-qualified name of the file, *i.e.* the path and file name. This includes an extension `.tex` when the given $\langle file\ name\rangle$ has no extension but the file found has that extension. If the file is not found then the $\langle str\ var\rangle$ is empty.

`\file_parse_full_name:nNNN`
New: 2017-06-23
Updated: 2017-06-26

`\file_parse_full_name:nNNN` $\{\langle full\ name\rangle\}$ $\langle dir\rangle$ $\langle name\rangle$ $\langle ext\rangle$

Parses the $\langle full\ name\rangle$ and splits it into three parts, each of which is returned by setting the appropriate local string variable:

- The $\langle dir\rangle$: everything up to the last `/` (path separator) in the $\langle file\ path\rangle$. As with system `PATH` variables and related functions, the $\langle dir\rangle$ does *not* include the trailing `/` unless it points to the root directory. If there is no path (only a file name), $\langle dir\rangle$ is empty.
- The $\langle name\rangle$: everything after the last `/` up to the last `.`, where both of those characters are optional. The $\langle name\rangle$ may contain multiple `.` characters. It is empty if $\langle full\ name\rangle$ consists only of a directory name.
- The $\langle ext\rangle$: everything after the last `.` (including the dot). The $\langle ext\rangle$ is empty if there is no `.` after the last `/`.

This function does not expand the $\langle full\ name\rangle$ before turning it to a string. It assume that the $\langle full\ name\rangle$ either contains no quote (`"`) characters or is surrounded by a pair of quotes.

`\file_input:n`
Updated: 2017-06-26

`\file_input:n` $\{\langle file\ name\rangle\}$

Searches for $\langle file\ name\rangle$ in the path as detailed for `\file_if_exist:nTF`, and if found reads in the file as additional L^AT_EX source. All files read are recorded for information and the file name stack is updated by this function. An error is raised if the file is not found.

`\file_show_list:`
`\file_log_list:`

`\file_show_list:`

`\file_log_list:`

These functions list all files loaded by L^AT_EX 2_ε commands that populate `\@filelist` or by `\file_input:n`. While `\file_show_list:` displays the list in the terminal, `\file_log_list:` outputs it to the log file only.

1.1 Input–output stream management

As T_EX engines have a limited number of input and output streams, direct use of the streams by the programmer is not supported in L^AT_EX 3. Instead, an internal pool of streams is maintained, and these are allocated and deallocated as needed by other modules. As a result, the programmer should close streams when they are no longer needed, to release them for other processes.

Note that I/O operations are global: streams should all be declared with global names and treated accordingly.

<hr/> <code>\ior_new:N</code> <code>\ior_new:c</code> <code>\iow_new:N</code> <code>\iow_new:c</code> <hr/> New: 2011-09-26 Updated: 2011-12-27 <hr/>	<code>\ior_new:N</code> $\langle stream \rangle$ <code>\iow_new:N</code> $\langle stream \rangle$ <p>Globally reserves the name of the $\langle stream \rangle$, either for reading or for writing as appropriate. The $\langle stream \rangle$ is not opened until the appropriate <code>\..._open:Nn</code> function is used. Attempting to use a $\langle stream \rangle$ which has not been opened is an error, and the $\langle stream \rangle$ will behave as the corresponding <code>\c_term_....</code></p>
<hr/> <code>\ior_open:Nn</code> <code>\ior_open:cn</code> <hr/> Updated: 2012-02-10 <hr/>	<code>\ior_open:Nn</code> $\langle stream \rangle$ $\{\langle file\ name \rangle\}$ <p>Opens $\langle file\ name \rangle$ for reading using $\langle stream \rangle$ as the control sequence for file access. If the $\langle stream \rangle$ was already open it is closed before the new operation begins. The $\langle stream \rangle$ is available for access immediately and will remain allocated to $\langle file\ name \rangle$ until a <code>\ior_close:N</code> instruction is given or the T_EX run ends. If the file is not found, an error is raised.</p>
<hr/> <code>\ior_open:NnTF</code> <code>\ior_open:cnTF</code> <hr/> New: 2013-01-12 <hr/>	<code>\ior_open:NnTF</code> $\langle stream \rangle$ $\{\langle file\ name \rangle\}$ $\{\langle true\ code \rangle\}$ $\{\langle false\ code \rangle\}$ <p>Opens $\langle file\ name \rangle$ for reading using $\langle stream \rangle$ as the control sequence for file access. If the $\langle stream \rangle$ was already open it is closed before the new operation begins. The $\langle stream \rangle$ is available for access immediately and will remain allocated to $\langle file\ name \rangle$ until a <code>\ior_close:N</code> instruction is given or the T_EX run ends. The $\langle true\ code \rangle$ is then inserted into the input stream. If the file is not found, no error is raised and the $\langle false\ code \rangle$ is inserted into the input stream.</p>
<hr/> <code>\iow_open:Nn</code> <code>\iow_open:cn</code> <hr/> Updated: 2012-02-09 <hr/>	<code>\iow_open:Nn</code> $\langle stream \rangle$ $\{\langle file\ name \rangle\}$ <p>Opens $\langle file\ name \rangle$ for writing using $\langle stream \rangle$ as the control sequence for file access. If the $\langle stream \rangle$ was already open it is closed before the new operation begins. The $\langle stream \rangle$ is available for access immediately and will remain allocated to $\langle file\ name \rangle$ until a <code>\iow_close:N</code> instruction is given or the T_EX run ends. Opening a file for writing clears any existing content in the file (<i>i.e.</i> writing is <i>not</i> additive).</p>
<hr/> <code>\ior_close:N</code> <code>\ior_close:c</code> <code>\iow_close:N</code> <code>\iow_close:c</code> <hr/> Updated: 2012-07-31 <hr/>	<code>\ior_close:N</code> $\langle stream \rangle$ <code>\iow_close:N</code> $\langle stream \rangle$ <p>Closes the $\langle stream \rangle$. Streams should always be closed when they are finished with as this ensures that they remain available to other programmers.</p>
<hr/> <code>\ior_show_list:</code> <code>\ior_log_list:</code> <code>\iow_show_list:</code> <code>\iow_log_list:</code> <hr/> New: 2017-06-27 <hr/>	<code>\ior_show_list:</code> <code>\ior_log_list:</code> <code>\iow_show_list:</code> <code>\iow_log_list:</code> <p>Display (to the terminal or log file) a list of the file names associated with each open (read or write) stream. This is intended for tracking down problems.</p>

1.2 Reading from files

<code>\ior_get:NN</code>	<code>\ior_get:NN <stream> <token list variable></code>
--------------------------	---

New: 2012-06-24

Function that reads one or more lines (until an equal number of left and right braces are found) from the input *<stream>* and stores the result locally in the *<token list>* variable. If the *<stream>* is not open, input is requested from the terminal. The material read from the *<stream>* is tokenized by \TeX according to the category codes and `\endlinechar` in force when the function is used. Assuming normal settings, any lines which do not end in a comment character `%` have the line ending converted to a space, so for example input

```
a b c
```

results in a token list `a_b_c_`. Any blank line is converted to the token `\par`. Therefore, blank lines can be skipped by using a test such as

```
\ior_get:NN \l_my_stream \l_tmpa_tl
\tl_set:Nn \l_tmpb_tl { \par }
\tl_if_eq:NNF \l_tmpa_tl \l_tmpb_tl
...
```

Also notice that if multiple lines are read to match braces then the resulting token list can contain `\par` tokens.

\TeX hackers note: This protected macro is a wrapper around the \TeX primitive `\read`. Regardless of settings, \TeX replaces trailing space and tab characters (character codes 32 and 9) in each line by an end-of-line character (character code `\endlinechar`, omitted if `\endlinechar` is negative or too large) before turning characters into tokens according to current category codes. With default settings, spaces appearing at the beginning of lines are also ignored.

<code>\ior_str_get:NN</code>	<code>\ior_str_get:NN <stream> <token list variable></code>
------------------------------	---

New: 2016-12-04

Function that reads one line from the input *<stream>* and stores the result locally in the *<token list>* variable. If the *<stream>* is not open, input is requested from the terminal. The material is read from the *<stream>* as a series of tokens with category code 12 (other), with the exception of space characters which are given category code 10 (space). Multiple whitespace characters are retained by this process. It always only reads one line and any blank lines in the input result in the *<token list variable>* being empty. Unlike `\ior_get:NN`, line ends do not receive any special treatment. Thus input

```
a b c
```

results in a token list `a b c` with the letters `a`, `b`, and `c` having category code 12.

\TeX hackers note: This protected macro is a wrapper around the $\varepsilon\text{\TeX}$ primitive `\readline`. Regardless of settings, \TeX removes trailing space and tab characters (character codes 32 and 9). However, the end-line character normally added by this primitive is not included in the result of `\ior_str_get:NN`.

<hr/> <code>\ior_map_inline:Nn</code> <hr/>	<code>\ior_map_inline:Nn <stream> {<inline function>}</code>
<hr/> New: 2012-02-11 <hr/>	Applies the <i><inline function></i> to each set of <i><lines></i> obtained by calling <code>\ior_get:NN</code> until reaching the end of the file. T _E X ignores any trailing new-line marker from the file it reads. The <i><inline function></i> should consist of code which receives the <i><line></i> as #1.
<hr/> <code>\ior_str_map_inline:Nn</code> <hr/>	<code>\ior_str_map_inline:Nn <stream> {<inline function>}</code>
<hr/> New: 2012-02-11 <hr/>	Applies the <i><inline function></i> to every <i><line></i> in the <i><stream></i> . The material is read from the <i><stream></i> as a series of tokens with category code 12 (other), with the exception of space characters which are given category code 10 (space). The <i><inline function></i> should consist of code which receives the <i><line></i> as #1. Note that T _E X removes trailing space and tab characters (character codes 32 and 9) from every line upon input. T _E X also ignores any trailing new-line marker from the file it reads.
<hr/> <code>\ior_map_break:</code> <hr/>	<code>\ior_map_break:</code>
<hr/> New: 2012-06-29 <hr/>	Used to terminate a <code>\ior_map...</code> function before all lines from the <i><stream></i> have been processed. This normally takes place within a conditional statement, for example <pre> \ior_map_inline:Nn \l_my_ior { \str_if_eq:nnTF { #1 } { bingo } { \ior_map_break: } { % Do something useful } } </pre> <p>Use outside of a <code>\ior_map...</code> scenario leads to low level T_EX errors.</p> <p>T_EXhackers note: When the mapping is broken, additional tokens may be inserted before further items are taken from the input stream. This depends on the design of the mapping function.</p>

<hr/> <code>\ior_map_break:n</code> <hr/>	<code>\ior_map_break:n {<code>}</code>
<hr/> New: 2012-06-29 <hr/>	Used to terminate a <code>\ior_map_...</code> function before all lines in the $\langle stream \rangle$ have been processed, inserting the $\langle code \rangle$ after the mapping has ended. This normally takes place within a conditional statement, for example

```

\ior_map_inline:Nn \l_my_ior
{
  \str_if_eq:nnTF { #1 } { bingo }
  { \ior_map_break:n { <code> } }
  {
    % Do something useful
  }
}

```

Use outside of a `\ior_map_...` scenario leads to low level \TeX errors.

\TeX hackers note: When the mapping is broken, additional tokens may be inserted before the $\langle code \rangle$ is inserted into the input stream. This depends on the design of the mapping function.

<hr/> <code>\ior_if_eof_p:N</code> ★	<code>\ior_if_eof_p:N <stream></code>
<code>\ior_if_eof:NTF</code> ★	<code>\ior_if_eof:NTF <stream> {<true code>} {<false code>}</code>
<hr/> Updated: 2012-02-10 <hr/>	Tests if the end of a $\langle stream \rangle$ has been reached during a reading operation. The test also returns a <code>true</code> value if the $\langle stream \rangle$ is not open.

2 Writing to files

<hr/> <code>\iow_now:Nn</code>	<code>\iow_now:Nn <stream> {<tokens>}</code>
<code>\iow_now:(Nx cn cx)</code>	This functions writes $\langle tokens \rangle$ to the specified $\langle stream \rangle$ immediately (<i>i.e.</i> the write operation is called on expansion of <code>\iow_now:Nn</code>).
<hr/> Updated: 2012-06-05 <hr/>	

<hr/> <code>\iow_log:n</code>	<code>\iow_log:n {<tokens>}</code>
<code>\iow_log:x</code>	This function writes the given $\langle tokens \rangle$ to the log (transcript) file immediately: it is a dedicated version of <code>\iow_now:Nn</code> .

<hr/> <code>\iow_term:n</code>	<code>\iow_term:n {<tokens>}</code>
<code>\iow_term:x</code>	This function writes the given $\langle tokens \rangle$ to the terminal file immediately: it is a dedicated version of <code>\iow_now:Nn</code> .

<hr/> <code>\iow_shipout:Nn</code> <code>\iow_shipout:(Nx cn cx)</code> <hr/>	<code>\iow_shipout:Nn <stream> {<tokens>}</code> This functions writes $\langle tokens \rangle$ to the specified $\langle stream \rangle$ when the current page is finalised (<i>i.e.</i> at shipout). The x -type variants expand the $\langle tokens \rangle$ at the point where the function is used but <i>not</i> when the resulting tokens are written to the $\langle stream \rangle$ (<i>cf.</i> <code>\iow_shipout_x:Nn</code>). <p>T_EXhackers note: When using <code>expl3</code> with a format other than L^AT_EX, new line characters inserted using <code>\iow_newline:</code> or using the line-wrapping code <code>\iow_wrap:nnnN</code> are not recognized in the argument of <code>\iow_shipout:Nn</code>. This may lead to the insertion of additional unwanted line-breaks.</p>
<hr/> <code>\iow_shipout_x:Nn</code> <code>\iow_shipout_x:(Nx cn cx)</code> <hr/> <div>Updated: 2012-09-08</div> <hr/>	<code>\iow_shipout_x:Nn <stream> {<tokens>}</code> This functions writes $\langle tokens \rangle$ to the specified $\langle stream \rangle$ when the current page is finalised (<i>i.e.</i> at shipout). The $\langle tokens \rangle$ are expanded at the time of writing in addition to any expansion when the function is used. This makes these functions suitable for including material finalised during the page building process (such as the page number integer). <p>T_EXhackers note: This is a wrapper around the T_EX primitive <code>\write</code>. When using <code>expl3</code> with a format other than L^AT_EX, new line characters inserted using <code>\iow_newline:</code> or using the line-wrapping code <code>\iow_wrap:nnnN</code> are not recognized in the argument of <code>\iow_shipout:Nn</code>. This may lead to the insertion of additional unwanted line-breaks.</p>
<hr/> <code>\iow_char:N</code> ★ <hr/>	<code>\iow_char:N \<char></code> Inserts $\langle char \rangle$ into the output stream. Useful when trying to write difficult characters such as %, {, }, <i>etc.</i> in messages, for example: <code>\iow_now:Nx \g_my_iow { \iow_char:N \{ text \iow_char:N \} }</code> The function has no effect if writing is taking place without expansion (<i>e.g.</i> in the second argument of <code>\iow_now:Nn</code>).
<hr/> <code>\iow_newline:</code> ★ <hr/>	<code>\iow_newline:</code> Function to add a new line within the $\langle tokens \rangle$ written to a file. The function has no effect if writing is taking place without expansion (<i>e.g.</i> in the second argument of <code>\iow_now:Nn</code>). <p>T_EXhackers note: When using <code>expl3</code> with a format other than L^AT_EX, the character inserted by <code>\iow_newline:</code> is not recognized by T_EX, which may lead to the insertion of additional unwanted line-breaks. This issue only affects <code>\iow_shipout:Nn</code>, <code>\iow_shipout_x:Nn</code> and direct uses of primitive operations.</p>

2.1 Wrapping lines in output

`\iow_wrap:nnnN`

New: 2012-06-28

Updated: 2017-12-04

`\iow_wrap:nnnN` $\langle text \rangle$ $\langle run-on\ text \rangle$ $\langle set\ up \rangle$ $\langle function \rangle$

This function wraps the $\langle text \rangle$ to a fixed number of characters per line. At the start of each line which is wrapped, the $\langle run-on\ text \rangle$ is inserted. The line character count targeted is the value of `\l_iow_line_count_int` minus the number of characters in the $\langle run-on\ text \rangle$ for all lines except the first, for which the target number of characters is simply `\l_iow_line_count_int` since there is no run-on text. The $\langle text \rangle$ and $\langle run-on\ text \rangle$ are exhaustively expanded by the function, with the following substitutions:

- `\` or `\iow_newline`: may be used to force a new line,
- `_` may be used to represent a forced space (for example after a control sequence),
- `\#`, `\%`, `\{`, `\}`, `\~` may be used to represent the corresponding character,
- `\iow_indent:n` may be used to indent a part of the $\langle text \rangle$ (not the $\langle run-on\ text \rangle$).

Additional functions may be added to the wrapping by using the $\langle set\ up \rangle$, which is executed before the wrapping takes place: this may include overriding the substitutions listed.

Any expandable material in the $\langle text \rangle$ which is not to be expanded on wrapping should be converted to a string using `\token_to_str:N`, `\tl_to_str:n`, `\tl_to_str:N`, *etc.*

The result of the wrapping operation is passed as a braced argument to the $\langle function \rangle$, which is typically a wrapper around a write operation. The output of `\iow_wrap:nnnN` (*i.e.* the argument passed to the $\langle function \rangle$) consists of characters of category “other” (category code 12), with the exception of spaces which have category “space” (category code 10). This means that the output does *not* expand further when written to a file.

T_EXhackers note: Internally, `\iow_wrap:nnnN` carries out an `x`-type expansion on the $\langle text \rangle$ to expand it. This is done in such a way that `\exp_not:N` or `\exp_not:n` *could* be used to prevent expansion of material. However, this is less conceptually clear than conversion to a string, which is therefore the supported method for handling expandable material in the $\langle text \rangle$.

`\iow_indent:n`

New: 2011-09-21

`\iow_indent:n` $\langle text \rangle$

In the first argument of `\iow_wrap:nnnN` (for instance in messages), indents $\langle text \rangle$ by four spaces. This function does not cause a line break, and only affects lines which start within the scope of the $\langle text \rangle$. In case the indented $\langle text \rangle$ should appear on separate lines from the surrounding text, use `\` to force line breaks.

`\l_iow_line_count_int`

New: 2012-06-24

The maximum number of characters in a line to be written by the `\iow_wrap:nnnN` function. This value depends on the T_EX system in use: the standard value is 78, which is typically correct for unmodified T_EXlive and MiK_TE_X systems.

2.2 Constant input–output streams

<code>\c_term_ior</code>	Constant input stream for reading from the terminal. Reading from this stream using <code>\ior_get:NN</code> or similar results in a prompt from T _E X of the form
--------------------------	---

`<tl>=`

<code>\c_log_iow</code> <code>\c_term_iow</code>	Constant output streams for writing to the log and to the terminal (plus the log), respectively.
---	--

2.3 Primitive conditionals

<code>\if_eof:w</code> ★	<pre> \if_eof:w <stream> <true code> \else: <false code> \fi: </pre> <p>Tests if the <code><stream></code> returns “end of file”, which is true for non-existent files. The <code>\else:</code> branch is optional.</p>
--------------------------	---

T_EXhackers note: This is the T_EX primitive `\ifeof`.

2.4 Internal file functions and variables

<code>\g__file_internal_ior</code>	Used to test for the existence of files when opening.
------------------------------------	---

<code>\l__file_base_name_str</code> <code>\l__file_full_name_str</code>	Used to store and transfer the file name (including extension) and (partial) file path whilst reading files. (The file base is the base name plus any preceding directory name.)
--	--

<code>__file_missing:n</code>	<code>__file_missing:n {<name>}</code>
New: 2017-06-25	Expands the <code><name></code> as per <code>__file_name_sanitize:nN</code> then produces an error message indicating that that file was not found.

<code>__file_name_sanitize:nN</code>	<code>__file_name_sanitize:nN {<name>} <str var></code>
New: 2017-06-19	Exhaustively-expands the <code><name></code> with the exception of any category <code><active></code> (catcode 13) tokens, which are not expanded. The list of <code><active></code> tokens is taken from <code>\l_char_active_seq</code> . The <code><str var></code> is then set to the <code><sanitized name></code> .

<code>__file_name_quote:nN</code>	<code>__file_name_quote:nN {<name>} <str var></code>
New: 2017-06-19 Updated: 2017-06-25	Expands the <code><name></code> (without special-casing active tokens), then sets the <code><str var></code> to the <code><name></code> quoted using " at each end if required by the presence of spaces in the <code><name></code> . Any existing " tokens is removed and if their number is odd an error is raised.

2.5 Internal input–output functions

<hr/>	<code>_ior_open:Nn</code>	<code>_ior_open:Nn</code>	<code><stream> {<file name>}</code>
<hr/>	<code>_ior_open:No</code>		
<hr/>	New: 2012-01-23		
			This function has identical syntax to the public version. However, it does not take precautions against active characters in the <code><file name></code> , and it does not attempt to add a <code><path></code> to the <code><file name></code> : it is therefore intended to be used by higher-level functions which have already fully expanded the <code><file name></code> and which need to perform multiple open or close operations. See for example the implementation of <code>\file_get_full_name:nN</code> ,
<hr/>		<code>_iow_with:Nnn</code>	<code>_iow_with:Nnn</code>
<hr/>			<code><integer> {<value>} {<code>}</code>
<hr/>	New: 2014-08-23		
			If the <code><integer></code> is equal to the <code><value></code> then this function simply runs the <code><code></code> . Otherwise it saves the current value of the <code><integer></code> , sets it to the <code><value></code> , runs the <code><code></code> , and restores the <code><integer></code> to its former value. This is used to ensure that the <code>\newlinechar</code> is 10 when writing to a stream, which lets <code>\iow_newline:</code> work, and that <code>\errorcontextlines</code> is <code>-1</code> when displaying a message.

Part XIX

The l3skip package

Dimensions and skips

L^AT_EX3 provides two general length variables: `dim` and `skip`. Lengths stored as `dim` variables have a fixed length, whereas `skip` lengths have a rubber (stretch/shrink) component. In addition, the `muskip` type is available for use in math mode: this is a special form of `skip` where the lengths involved are determined by the current math font (in μ). There are common features in the creation and setting of length variables, but for clarity the functions are grouped by variable type.

1 Creating and initialising `dim` variables

<code>\dim_new:N</code>
<code>\dim_new:c</code>

`\dim_new:N` $\langle dimension \rangle$

Creates a new $\langle dimension \rangle$ or raises an error if the name is already taken. The declaration is global. The $\langle dimension \rangle$ is initially equal to 0pt.

<code>\dim_const:Nn</code>
<code>\dim_const:cn</code>

`\dim_const:Nn` $\langle dimension \rangle$ $\{ \langle dimension expression \rangle \}$

Creates a new constant $\langle dimension \rangle$ or raises an error if the name is already taken. The value of the $\langle dimension \rangle$ is set globally to the $\langle dimension expression \rangle$.

New: 2012-03-05

<code>\dim_zero:N</code>
<code>\dim_zero:c</code>
<code>\dim_gzero:N</code>
<code>\dim_gzero:c</code>

`\dim_zero:N` $\langle dimension \rangle$

Sets $\langle dimension \rangle$ to 0pt.

<code>\dim_zero_new:N</code>
<code>\dim_zero_new:c</code>
<code>\dim_gzero_new:N</code>
<code>\dim_gzero_new:c</code>

`\dim_zero_new:N` $\langle dimension \rangle$

Ensures that the $\langle dimension \rangle$ exists globally by applying `\dim_new:N` if necessary, then applies `\dim_(g)zero:N` to leave the $\langle dimension \rangle$ set to zero.

New: 2012-01-07

<code>\dim_if_exist_p:N</code> ★
<code>\dim_if_exist_p:c</code> ★
<code>\dim_if_exist:NTF</code> ★
<code>\dim_if_exist:cTF</code> ★

`\dim_if_exist_p:N` $\langle dimension \rangle$

`\dim_if_exist:NTF` $\langle dimension \rangle$ $\{ \langle true code \rangle \} \{ \langle false code \rangle \}$

Tests whether the $\langle dimension \rangle$ is currently defined. This does not check that the $\langle dimension \rangle$ really is a dimension variable.

New: 2012-03-03

2 Setting dim variables

<code>\dim_add:Nn</code>	<code>\dim_add:Nn <dimension> {<dimension expression>}</code>
<code>\dim_add:cn</code>	
<code>\dim_gadd:Nn</code>	Adds the result of the $\langle dimension expression \rangle$ to the current content of the $\langle dimension \rangle$.
<code>\dim_gadd:cn</code>	

Updated: 2011-10-22

<code>\dim_set:Nn</code>	<code>\dim_set:Nn <dimension> {<dimension expression>}</code>
<code>\dim_set:cn</code>	
<code>\dim_gset:Nn</code>	Sets $\langle dimension \rangle$ to the value of $\langle dimension expression \rangle$, which must evaluate to a length with units.
<code>\dim_gset:cn</code>	

Updated: 2011-10-22

<code>\dim_set_eq:NN</code>	<code>\dim_set_eq:NN <dimension₁> <dimension₂></code>
<code>\dim_set_eq:(cN Nc cc)</code>	
<code>\dim_gset_eq:NN</code>	Sets the content of $\langle dimension_1 \rangle$ equal to that of $\langle dimension_2 \rangle$.
<code>\dim_gset_eq:(cN Nc cc)</code>	

<code>\dim_sub:Nn</code>	<code>\dim_sub:Nn <dimension> {<dimension expression>}</code>
<code>\dim_sub:cn</code>	
<code>\dim_gsub:Nn</code>	Subtracts the result of the $\langle dimension expression \rangle$ from the current content of the $\langle dimension \rangle$.
<code>\dim_gsub:cn</code>	

Updated: 2011-10-22

3 Utilities for dimension calculations

<code>\dim_abs:n</code>	★ <code>\dim_abs:n {<dimexpr>}</code>
Updated: 2012-09-26	Converts the $\langle dimexpr \rangle$ to its absolute value, leaving the result in the input stream as a $\langle dimension denotation \rangle$.

<code>\dim_max:nn</code>	★ <code>\dim_max:nn {<dimexpr₁>} {<dimexpr₂>}</code>
<code>\dim_min:nn</code>	★ <code>\dim_min:nn {<dimexpr₁>} {<dimexpr₂>}</code>
New: 2012-09-09	
Updated: 2012-09-26	Evaluates the two $\langle dimension expressions \rangle$ and leaves either the maximum or minimum value in the input stream as appropriate, as a $\langle dimension denotation \rangle$.

`\dim_ratio:nn` ☆

Updated: 2011-10-22

`\dim_ratio:nn {⟨dimexpr1⟩} {⟨dimexpr2⟩}`

Parses the two *⟨dimension expressions⟩* and converts the ratio of the two to a form suitable for use inside a *⟨dimension expression⟩*. This ratio is then left in the input stream, allowing syntax such as

```
\dim_set:Nn \l_my_dim
{ 10 pt * \dim_ratio:nn { 5 pt } { 10 pt } }
```

The output of `\dim_ratio:nn` on full expansion is a ration expression between two integers, with all distances converted to scaled points. Thus

```
\tl_set:Nx \l_my_tl { \dim_ratio:nn { 5 pt } { 10 pt } }
\tl_show:N \l_my_tl
```

displays 327680/655360 on the terminal.

4 Dimension expression conditionals

`\dim_compare_p:nNn` ☆

`\dim_compare:nNnTF` ☆

`\dim_compare_p:nNn {⟨dimexpr1⟩} ⟨relation⟩ {⟨dimexpr2⟩}`

`\dim_compare:nNnTF {⟨dimexpr1⟩} ⟨relation⟩ {⟨dimexpr2⟩}
{⟨true code⟩} {⟨false code⟩}`

This function first evaluates each of the *⟨dimension expressions⟩* as described for `\dim_eval:n`. The two results are then compared using the *⟨relation⟩*:

Equal	=
Greater than	>
Less than	<

<code>\dim_compare_p:n</code> ★ <code>\dim_compare:nTF</code> ★	<pre> \dim_compare_p:n { <dimexpr₁> <relation₁> ... <dimexpr_N> <relation_N> <dimexpr_{N+1}> } \dim_compare:nTF { <dimexpr₁> <relation₁> ... <dimexpr_N> <relation_N> <dimexpr_{N+1}> } {<true code>} {<false code>}</pre>
--	--

Updated: 2013-01-13

This function evaluates the *<dimension expressions>* as described for `\dim_eval:n` and compares consecutive result using the corresponding *<relation>*, namely it compares *<dimexpr₁>* and *<dimexpr₂>* using the *<relation₁>*, then *<dimexpr₂>* and *<dimexpr₃>* using the *<relation₂>*, until finally comparing *<dimexpr_N>* and *<dimexpr_{N+1}>* using the *<relation_N>*. The test yields **true** if all comparisons are **true**. Each *<dimension expression>* is evaluated only once, and the evaluation is lazy, in the sense that if one comparison is **false**, then no other *<dimension expression>* is evaluated and no other comparison is performed. The *<relations>* can be any of the following:

Equal	= or ==
Greater than or equal to	>=
Greater than	>
Less than or equal to	<=
Less than	<
Not equal	!=

<code>\dim_case:nn</code> ★	<code>\dim_case:nnTF {⟨test dimension expression⟩}</code>
<code>\dim_case:nnTF</code> ★	<code>{</code>
New: 2013-07-24	<code>{⟨dimexpr case₁⟩} {⟨code case₁⟩}</code>
	<code>{⟨dimexpr case₂⟩} {⟨code case₂⟩}</code>
	<code>...</code>
	<code>{⟨dimexpr case_n⟩} {⟨code case_n⟩}</code>
	<code>}</code>
	<code>{⟨true code⟩}</code>
	<code>{⟨false code⟩}</code>

This function evaluates the *⟨test dimension expression⟩* and compares this in turn to each of the *⟨dimension expression cases⟩*. If the two are equal then the associated *⟨code⟩* is left in the input stream and other cases are discarded. If any of the cases are matched, the *⟨true code⟩* is also inserted into the input stream (after the code for the appropriate case), while if none match then the *⟨false code⟩* is inserted. The function `\dim_case:nn`, which does nothing if there is no match, is also available. For example

```

\dim_set:Nn \l_tmpa_dim { 5 pt }
\dim_case:nnF
{ 2 \l_tmpa_dim }
{
  { 5 pt }      { Small }
  { 4 pt + 6 pt } { Medium }
  { - 10 pt }   { Negative }
}
{ No idea! }

```

leaves “Medium” in the input stream.

5 Dimension expression loops

<code>\dim_do_until:nNnn</code> ☆	<code>\dim_do_until:nNnn {⟨dimexpr₁⟩} ⟨relation⟩ {⟨dimexpr₂⟩} {⟨code⟩}</code>
-----------------------------------	---

Places the *⟨code⟩* in the input stream for T_EX to process, and then evaluates the relationship between the two *⟨dimension expressions⟩* as described for `\dim_compare:nNnTF`. If the test is **false** then the *⟨code⟩* is inserted into the input stream again and a loop occurs until the *⟨relation⟩* is **true**.

<code>\dim_do_while:nNnn</code> ☆	<code>\dim_do_while:nNnn {⟨dimexpr₁⟩} ⟨relation⟩ {⟨dimexpr₂⟩} {⟨code⟩}</code>
-----------------------------------	---

Places the *⟨code⟩* in the input stream for T_EX to process, and then evaluates the relationship between the two *⟨dimension expressions⟩* as described for `\dim_compare:nNnTF`. If the test is **true** then the *⟨code⟩* is inserted into the input stream again and a loop occurs until the *⟨relation⟩* is **false**.

<code>\dim_until_do:nNnn</code> ☆	<code>\dim_until_do:nNnn {⟨dimexpr₁⟩} ⟨relation⟩ {⟨dimexpr₂⟩} {⟨code⟩}</code>
-----------------------------------	---

Evaluates the relationship between the two *⟨dimension expressions⟩* as described for `\dim_compare:nNnTF`, and then places the *⟨code⟩* in the input stream if the *⟨relation⟩* is **false**. After the *⟨code⟩* has been processed by T_EX the test is repeated, and a loop occurs until the test is **true**.

<hr/> <code>\dim_while_do:nNnn</code> ☆ <hr/>	<code>\dim_while_do:nNnn {<dimexpr₁>} <relation> {<dimexpr₂>} {<code>}</code>
	Evaluates the relationship between the two <i><dimension expressions></i> as described for <code>\dim_compare:nNnTF</code> , and then places the <i><code></i> in the input stream if the <i><relation></i> is true . After the <i><code></i> has been processed by T _E X the test is repeated, and a loop occurs until the test is false .
<hr/> <code>\dim_do_until:nn</code> ☆ <hr/> <div>Updated: 2013-01-13</div>	<code>\dim_do_until:nn {<dimension relation>} {<code>}</code>
	Places the <i><code></i> in the input stream for T _E X to process, and then evaluates the <i><dimension relation></i> as described for <code>\dim_compare:nTF</code> . If the test is false then the <i><code></i> is inserted into the input stream again and a loop occurs until the <i><relation></i> is true .
<hr/> <code>\dim_do_while:nn</code> ☆ <hr/> <div>Updated: 2013-01-13</div>	<code>\dim_do_while:nn {<dimension relation>} {<code>}</code>
	Places the <i><code></i> in the input stream for T _E X to process, and then evaluates the <i><dimension relation></i> as described for <code>\dim_compare:nTF</code> . If the test is true then the <i><code></i> is inserted into the input stream again and a loop occurs until the <i><relation></i> is false .
<hr/> <code>\dim_until_do:nn</code> ☆ <hr/> <div>Updated: 2013-01-13</div>	<code>\dim_until_do:nn {<dimension relation>} {<code>}</code>
	Evaluates the <i><dimension relation></i> as described for <code>\dim_compare:nTF</code> , and then places the <i><code></i> in the input stream if the <i><relation></i> is false . After the <i><code></i> has been processed by T _E X the test is repeated, and a loop occurs until the test is true .
<hr/> <code>\dim_while_do:nn</code> ☆ <hr/> <div>Updated: 2013-01-13</div>	<code>\dim_while_do:nn {<dimension relation>} {<code>}</code>
	Evaluates the <i><dimension relation></i> as described for <code>\dim_compare:nTF</code> , and then places the <i><code></i> in the input stream if the <i><relation></i> is true . After the <i><code></i> has been processed by T _E X the test is repeated, and a loop occurs until the test is false .

6 Using dim expressions and variables

<hr/> <code>\dim_eval:n</code> ☆ <hr/> <div>Updated: 2011-10-22</div>	<code>\dim_eval:n {<dimension expression>}</code>
	Evaluates the <i><dimension expression></i> , expanding any dimensions and token list variables within the <i><expression></i> to their content (without requiring <code>\dim_use:N/\tl_use:N</code>) and applying the standard mathematical rules. The result of the calculation is left in the input stream as a <i><dimension denotation></i> after two expansions. This is expressed in points (pt), and requires suitable termination if used in a T _E X-style assignment as it is <i>not</i> an <i><internal dimension></i> .
<hr/> <code>\dim_use:N</code> ☆ <hr/> <code>\dim_use:c</code> ☆ <hr/>	<code>\dim_use:N <dimension></code>
	Recovers the content of a <i><dimension></i> and places it directly in the input stream. An error is raised if the variable does not exist or if it is invalid. Can be omitted in places where a <i><dimension></i> is required (such as in the argument of <code>\dim_eval:n</code>).

T_EXhackers note: `\dim_use:N` is the T_EX primitive `\the`: this is one of several L^AT_EX3 names for this primitive.

<code>\dim_to_decimal:n</code> ★	<code>\dim_to_decimal:n {<dimexpr>}</code>
----------------------------------	--

New: 2014-07-15

Evaluates the $\langle dimension expression \rangle$, and leaves the result, expressed in points (`pt`) in the input stream, with *no units*. The result is rounded by \TeX to four or five decimal places. If the decimal part of the result is zero, it is omitted, together with the decimal marker.

For example

`\dim_to_decimal:n { 1bp }`

leaves 1.00374 in the input stream, *i.e.* the magnitude of one “big point” when converted to (\TeX) points.

<code>\dim_to_decimal_in_bp:n</code> ★	<code>\dim_to_decimal_in_bp:n {<dimexpr>}</code>
--	--

New: 2014-07-15

Evaluates the $\langle dimension expression \rangle$, and leaves the result, expressed in big points (`bp`) in the input stream, with *no units*. The result is rounded by \TeX to four or five decimal places. If the decimal part of the result is zero, it is omitted, together with the decimal marker.

For example

`\dim_to_decimal_in_bp:n { 1pt }`

leaves 0.99628 in the input stream, *i.e.* the magnitude of one (\TeX) point when converted to big points.

<code>\dim_to_decimal_in_sp:n</code> ★	<code>\dim_to_decimal_in_sp:n {<dimexpr>}</code>
--	--

New: 2015-05-18

Evaluates the $\langle dimension expression \rangle$, and leaves the result, expressed in scaled points (`sp`) in the input stream, with *no units*. The result is necessarily an integer.

<code>\dim_to_decimal_in_unit:nn</code> ★	<code>\dim_to_decimal_in_unit:nn {<dimexpr₁>} {<dimexpr₂>}</code>
---	---

New: 2014-07-15

Evaluates the $\langle dimension expressions \rangle$, and leaves the value of $\langle dimexpr_1 \rangle$, expressed in a unit given by $\langle dimexpr_2 \rangle$, in the input stream. The result is a decimal number, rounded by \TeX to four or five decimal places. If the decimal part of the result is zero, it is omitted, together with the decimal marker.

For example

`\dim_to_decimal_in_unit:nn { 1bp } { 1mm }`

leaves 0.35277 in the input stream, *i.e.* the magnitude of one big point when converted to millimetres.

Note that this function is not optimised for any particular output and as such may give different results to `\dim_to_decimal_in_bp:n` or `\dim_to_decimal_in_sp:n`. In particular, the latter is able to take a wider range of input values as it is not limited by the ability to calculate a ratio using ε - \TeX primitives, which is required internally by `\dim_to_decimal_in_unit:nn`.

<hr/> <code>\dim_to_fp:n</code> ★ <hr/>	<code>\dim_to_fp:n {⟨<i>dimexpr</i>⟩}</code>
New: 2012-05-08 <hr/>	Expands to an internal floating point number equal to the value of the $\langle \textit{dimexpr} \rangle$ in pt. Since dimension expressions are evaluated much faster than their floating point equivalent, <code>\dim_to_fp:n</code> can be used to speed up parts of a computation where a low precision and a smaller range are acceptable.

7 Viewing dim variables

<hr/> <code>\dim_show:N</code> <code>\dim_show:c</code> <hr/>	<code>\dim_show:N ⟨<i>dimension</i>⟩</code> Displays the value of the $\langle \textit{dimension} \rangle$ on the terminal.
<hr/> <code>\dim_show:n</code> <hr/>	<code>\dim_show:n {⟨<i>dimension expression</i>⟩}</code>
New: 2011-11-22 Updated: 2015-08-07 <hr/>	Displays the result of evaluating the $\langle \textit{dimension expression} \rangle$ on the terminal.
<hr/> <code>\dim_log:N</code> <code>\dim_log:c</code> <hr/>	<code>\dim_log:N ⟨<i>dimension</i>⟩</code> Writes the value of the $\langle \textit{dimension} \rangle$ in the log file.
New: 2014-08-22 Updated: 2015-08-03 <hr/>	
<hr/> <code>\dim_log:n</code> <hr/>	<code>\dim_log:n {⟨<i>dimension expression</i>⟩}</code>
New: 2014-08-22 Updated: 2015-08-07 <hr/>	Writes the result of evaluating the $\langle \textit{dimension expression} \rangle$ in the log file.

8 Constant dimensions

<hr/> <code>\c_max_dim</code> <hr/>	The maximum value that can be stored as a dimension. This can also be used as a component of a skip.
<hr/> <code>\c_zero_dim</code> <hr/>	A zero length as a dimension. This can also be used as a component of a skip.

9 Scratch dimensions

<hr/> <code>\l_tmpa_dim</code> <code>\l_tmpb_dim</code> <hr/>	Scratch dimension for local assignment. These are never used by the kernel code, and so are safe for use with any L ^A T _E X3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.
<hr/> <code>\g_tmpa_dim</code> <code>\g_tmpb_dim</code> <hr/>	Scratch dimension for global assignment. These are never used by the kernel code, and so are safe for use with any L ^A T _E X3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.

10 Creating and initialising skip variables

`\skip_new:N`
`\skip_new:c`

`\skip_new:N` $\langle skip \rangle$

Creates a new $\langle skip \rangle$ or raises an error if the name is already taken. The declaration is global. The $\langle skip \rangle$ is initially equal to 0pt.

`\skip_const:Nn`
`\skip_const:cn`

`\skip_const:Nn` $\langle skip \rangle$ $\{ \langle skip \text{ expression} \rangle \}$

Creates a new constant $\langle skip \rangle$ or raises an error if the name is already taken. The value of the $\langle skip \rangle$ is set globally to the $\langle skip \text{ expression} \rangle$.

New: 2012-03-05

`\skip_zero:N`
`\skip_zero:c`
`\skip_gzero:N`
`\skip_gzero:c`

`\skip_zero:N` $\langle skip \rangle$

Sets $\langle skip \rangle$ to 0pt.

`\skip_zero_new:N`
`\skip_zero_new:c`
`\skip_gzero_new:N`
`\skip_gzero_new:c`

`\skip_zero_new:N` $\langle skip \rangle$

Ensures that the $\langle skip \rangle$ exists globally by applying `\skip_new:N` if necessary, then applies `\skip_(g)zero:N` to leave the $\langle skip \rangle$ set to zero.

New: 2012-01-07

`\skip_if_exist_p:N` ★
`\skip_if_exist_p:c` ★
`\skip_if_exist:NTF` ★
`\skip_if_exist:cTF` ★

`\skip_if_exist_p:N` $\langle skip \rangle$

`\skip_if_exist:NTF` $\langle skip \rangle$ $\{ \langle true \text{ code} \rangle \} \{ \langle false \text{ code} \rangle \}$

Tests whether the $\langle skip \rangle$ is currently defined. This does not check that the $\langle skip \rangle$ really is a skip variable.

New: 2012-03-03

11 Setting skip variables

`\skip_add:Nn`
`\skip_add:cn`
`\skip_gadd:Nn`
`\skip_gadd:cn`

`\skip_add:Nn` $\langle skip \rangle$ $\{ \langle skip \text{ expression} \rangle \}$

Adds the result of the $\langle skip \text{ expression} \rangle$ to the current content of the $\langle skip \rangle$.

Updated: 2011-10-22

`\skip_set:Nn`
`\skip_set:cn`
`\skip_gset:Nn`
`\skip_gset:cn`

`\skip_set:Nn` $\langle skip \rangle$ $\{ \langle skip \text{ expression} \rangle \}$

Sets $\langle skip \rangle$ to the value of $\langle skip \text{ expression} \rangle$, which must evaluate to a length with units and may include a rubber component (for example 1 cm plus 0.5 cm).

Updated: 2011-10-22

`\skip_set_eq:NN`
`\skip_set_eq:(cN|Nc|cc)`
`\skip_gset_eq:NN`
`\skip_gset_eq:(cN|Nc|cc)`

`\skip_set_eq:NN` $\langle skip_1 \rangle$ $\langle skip_2 \rangle$

Sets the content of $\langle skip_1 \rangle$ equal to that of $\langle skip_2 \rangle$.

<hr/> <code>\skip_sub:Nn</code>	<code>\skip_sub:Nn <skip> {<skip expression>}</code>
<code>\skip_sub:cn</code>	
<code>\skip_gsub:Nn</code>	Subtracts the result of the <i><skip expression></i> from the current content of the <i><skip></i> .
<code>\skip_gsub:cn</code>	
<hr/> Updated: 2011-10-22 <hr/>	

12 Skip expression conditionals

<hr/> <code>\skip_if_eq_p:nn</code> ★	<code>\skip_if_eq_p:nn {<skipexpr₁>} {<skipexpr₂>}</code>
<code>\skip_if_eq:nnTF</code> ★	<code>\skip_if_eq:nnTF</code>
	<code>{<skipexpr₁>} {<skipexpr₂>}</code>
	<code>{<true code>} {<false code>}</code>

This function first evaluates each of the *<skip expressions>* as described for `\skip_eval:n`. The two results are then compared for exact equality, *i.e.* both the fixed and rubber components must be the same for the test to be true.

<hr/> <code>\skip_if_finite_p:n</code> ★	<code>\skip_if_finite_p:n {<skipexpr>}</code>
<code>\skip_if_finite:nTF</code> ★	<code>\skip_if_finite:nTF {<skipexpr>} {<true code>} {<false code>}</code>
<hr/> New: 2012-03-05 <hr/>	

Evaluates the *<skip expression>* as described for `\skip_eval:n`, and then tests if all of its components are finite.

13 Using skip expressions and variables

<hr/> <code>\skip_eval:n</code> ★	<code>\skip_eval:n {<skip expression>}</code>
<hr/> Updated: 2011-10-22 <hr/>	

Evaluates the *<skip expression>*, expanding any skips and token list variables within the *<expression>* to their content (without requiring `\skip_use:N/\tl_use:N`) and applying the standard mathematical rules. The result of the calculation is left in the input stream as a *<glue denotation>* after two expansions. This is expressed in points (**pt**), and requires suitable termination if used in a **T**_EX-style assignment as it is *not* an *<internal glue>*.

<hr/> <code>\skip_use:N</code> ★	<code>\skip_use:N <skip></code>
<code>\skip_use:c</code> ★	

Recovers the content of a *<skip>* and places it directly in the input stream. An error is raised if the variable does not exist or if it is invalid. Can be omitted in places where a *<dimension>* is required (such as in the argument of `\skip_eval:n`).

T_EXhackers note: `\skip_use:N` is the **T**_EX primitive `\the`: this is one of several L^AT_EX3 names for this primitive.

14 Viewing skip variables

<hr/> <code>\skip_show:N</code>	<code>\skip_show:N <skip></code>
<code>\skip_show:c</code>	
<hr/> Updated: 2015-08-03 <hr/>	

Displays the value of the *<skip>* on the terminal.

<hr/> <code>\skip_show:n</code> <hr/>	<code>\skip_show:n {\langle skip expression \rangle}</code>
New: 2011-11-22 Updated: 2015-08-07	Displays the result of evaluating the $\langle skip expression \rangle$ on the terminal.

<hr/> <code>\skip_log:N</code> <code>\skip_log:c</code> <hr/>	<code>\skip_log:N \langle skip \rangle</code>
New: 2014-08-22 Updated: 2015-08-03	Writes the value of the $\langle skip \rangle$ in the log file.

<hr/> <code>\skip_log:n</code> <hr/>	<code>\skip_log:n {\langle skip expression \rangle}</code>
New: 2014-08-22 Updated: 2015-08-07	Writes the result of evaluating the $\langle skip expression \rangle$ in the log file.

15 Constant skips

<hr/> <code>\c_max_skip</code> <hr/>	The maximum value that can be stored as a skip (equal to <code>\c_max_dim</code> in length), with no stretch nor shrink component.
Updated: 2012-11-02	

<hr/> <code>\c_zero_skip</code> <hr/>	A zero length as a skip, with no stretch nor shrink component.
Updated: 2012-11-01	

16 Scratch skips

<hr/> <code>\l_tmpa_skip</code> <code>\l_tmpb_skip</code> <hr/>	Scratch skip for local assignment. These are never used by the kernel code, and so are safe for use with any L ^A T _E X3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.
--	--

<hr/> <code>\g_tmpa_skip</code> <code>\g_tmpb_skip</code> <hr/>	Scratch skip for global assignment. These are never used by the kernel code, and so are safe for use with any L ^A T _E X3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.
--	---

17 Inserting skips into the output

<hr/> <code>\skip_horizontal:N</code> <code>\skip_horizontal:c</code> <code>\skip_horizontal:n</code> <hr/>	<code>\skip_horizontal:N \langle skip \rangle</code> <code>\skip_horizontal:n {\langle skipexpr \rangle}</code>
Updated: 2011-10-22	Inserts a horizontal $\langle skip \rangle$ into the current list.

T_EXhackers note: `\skip_horizontal:N` is the T_EX primitive `\hskip` renamed.

```
\skip_vertical:N
\skip_vertical:c
\skip_vertical:n
```

Updated: 2011-10-22

```
\skip_vertical:N <skip>
\skip_vertical:n {<skipexpr>}
```

Inserts a vertical $\langle skip \rangle$ into the current list.

T_EXhackers note: `\skip_vertical:N` is the T_EX primitive `\vskip` renamed.

18 Creating and initialising muskip variables

```
\muskip_new:N
\muskip_new:c
```

```
\muskip_new:N <muskip>
```

Creates a new $\langle muskip \rangle$ or raises an error if the name is already taken. The declaration is global. The $\langle muskip \rangle$ is initially equal to 0 mu.

```
\muskip_const:Nn
\muskip_const:cn
```

New: 2012-03-05

```
\muskip_const:Nn <muskip> {<muskip expression>}
```

Creates a new constant $\langle muskip \rangle$ or raises an error if the name is already taken. The value of the $\langle muskip \rangle$ is set globally to the $\langle muskip expression \rangle$.

```
\muskip_zero:N
\muskip_zero:c
\muskip_gzero:N
\muskip_gzero:c
```

```
\skip_zero:N <muskip>
```

Sets $\langle muskip \rangle$ to 0 mu.

```
\muskip_zero_new:N
\muskip_zero_new:c
\muskip_gzero_new:N
\muskip_gzero_new:c
```

New: 2012-01-07

```
\muskip_zero_new:N <muskip>
```

Ensures that the $\langle muskip \rangle$ exists globally by applying `\muskip_new:N` if necessary, then applies `\muskip_(g)zero:N` to leave the $\langle muskip \rangle$ set to zero.

```
\muskip_if_exist_p:N ★
\muskip_if_exist_p:c ★
\muskip_if_exist:NTF ★
\muskip_if_exist:cTF ★
```

New: 2012-03-03

```
\muskip_if_exist_p:N <muskip>
```

```
\muskip_if_exist:NTF <muskip> {<true code>} {<false code>}
```

Tests whether the $\langle muskip \rangle$ is currently defined. This does not check that the $\langle muskip \rangle$ really is a muskip variable.

19 Setting muskip variables

```
\muskip_add:Nn
\muskip_add:cn
\muskip_gadd:Nn
\muskip_gadd:cn
```

Updated: 2011-10-22

```
\muskip_add:Nn <muskip> {<muskip expression>}
```

Adds the result of the $\langle muskip expression \rangle$ to the current content of the $\langle muskip \rangle$.

<hr/> <code>\muskip_set:Nn</code> <hr/>	<code>\muskip_set:Nn <muskip> {<muskip expression>}</code>
<code>\muskip_set:cn</code>	
<code>\muskip_gset:Nn</code>	Sets $\langle muskip \rangle$ to the value of $\langle muskip expression \rangle$, which must evaluate to a math length with units and may include a rubber component (for example 1 mu plus 0.5 mu).
<code>\muskip_gset:cn</code> <hr/>	
Updated: 2011-10-22 <hr/>	

<hr/> <code>\muskip_set_eq:NN</code> <hr/>	<code>\muskip_set_eq:NN <muskip₁> <muskip₂></code>
<code>\muskip_set_eq:(cN Nc cc)</code>	
<code>\muskip_gset_eq:NN</code>	Sets the content of $\langle muskip_1 \rangle$ equal to that of $\langle muskip_2 \rangle$.
<code>\muskip_gset_eq:(cN Nc cc)</code> <hr/>	

<hr/> <code>\muskip_sub:Nn</code> <hr/>	<code>\muskip_sub:Nn <muskip> {<muskip expression>}</code>
<code>\muskip_sub:cn</code>	
<code>\muskip_gsub:Nn</code>	Subtracts the result of the $\langle muskip expression \rangle$ from the current content of the $\langle skip \rangle$.
<code>\muskip_gsub:cn</code> <hr/>	
Updated: 2011-10-22 <hr/>	

20 Using muskip expressions and variables

<hr/> <code>\muskip_eval:n</code> ★ <hr/>	<code>\muskip_eval:n {<muskip expression>}</code>
Updated: 2011-10-22 <hr/>	
	Evaluates the $\langle muskip expression \rangle$, expanding any skips and token list variables within the $\langle expression \rangle$ to their content (without requiring <code>\muskip_use:N/\tl_use:N</code>) and applying the standard mathematical rules. The result of the calculation is left in the input stream as a $\langle muglue denotation \rangle$ after two expansions. This is expressed in mu , and requires suitable termination if used in a T _E X-style assignment as it is <i>not</i> an $\langle internal muglue \rangle$.

<hr/> <code>\muskip_use:N</code> ★ <hr/>	<code>\muskip_use:N <muskip></code>
<code>\muskip_use:c</code> ★ <hr/>	
	Recovers the content of a $\langle skip \rangle$ and places it directly in the input stream. An error is raised if the variable does not exist or if it is invalid. Can be omitted in places where a $\langle dimension \rangle$ is required (such as in the argument of <code>\muskip_eval:n</code>).

T_EXhackers note: `\muskip_use:N` is the T_EX primitive `\the`: this is one of several L^AT_EX3 names for this primitive.

21 Viewing muskip variables

<hr/> <code>\muskip_show:N</code> <hr/>	<code>\muskip_show:N <muskip></code>
<code>\muskip_show:c</code> <hr/>	
Updated: 2015-08-03 <hr/>	Displays the value of the $\langle muskip \rangle$ on the terminal.

<hr/> <code>\muskip_show:n</code> <hr/>	<code>\muskip_show:n {<muskip expression>}</code>
New: 2011-11-22 <hr/>	
Updated: 2015-08-07 <hr/>	Displays the result of evaluating the $\langle muskip expression \rangle$ on the terminal.

<code>\muskip_log:N</code>	<code>\muskip_log:N <muskip></code>
<code>\muskip_log:c</code>	Writes the value of the <code><muskip></code> in the log file.

New: 2014-08-22
Updated: 2015-08-03

<code>\muskip_log:n</code>	<code>\muskip_log:n {<muskip expression>}</code>
	Writes the result of evaluating the <code><muskip expression></code> in the log file.

New: 2014-08-22
Updated: 2015-08-07

22 Constant muskips

<code>\c_max_muskip</code>	The maximum value that can be stored as a muskip, with no stretch nor shrink component.
----------------------------	---

<code>\c_zero_muskip</code>	A zero length as a muskip, with no stretch nor shrink component.
-----------------------------	--

23 Scratch muskips

<code>\l_tmpa_muskip</code> <code>\l_tmpb_muskip</code>	Scratch muskip for local assignment. These are never used by the kernel code, and so are safe for use with any L ^A T _E X3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.
--	--

<code>\g_tmpa_muskip</code> <code>\g_tmpb_muskip</code>	Scratch muskip for global assignment. These are never used by the kernel code, and so are safe for use with any L ^A T _E X3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.
--	---

24 Primitive conditional

<code>\if_dim:w</code>	<code>\if_dim:w <dimen_{12 <code> <true code></code> <code>\else:</code> <code> <false></code> <code>\fi:</code>}</code>
------------------------	---

Compare two dimensions. The `<relation>` is one of `<`, `=` or `>` with category code 12.

T_EXhackers note: This is the T_EX primitive `\ifdim`.

25 Internal functions

<hr/>	
<code>_dim_eval:w</code> ★	<code>_dim_eval:w <dimexpr> _dim_eval_end:</code>
<code>_dim_eval_end:</code> ★	
<hr/>	
	Evaluates <i><dimension expression></i> as described for <code>\dim_eval:n</code> . The evaluation stops when an unexpandable token which is not a valid part of a dimension is read or when <code>_dim_eval_end:</code> is reached. The latter is gobbled by the scanner mechanism: <code>_dim_eval_end:</code> itself is unexpandable but used correctly the entire construct is expandable.

TeXhackers note: This is the ε -TeX primitive `\dimexpr`.

<hr/>	
<code>_dim_eval:n</code> ★	<code>_dim_eval:n {<dimexpr>}</code>
<hr/>	
	By default this expands to <code>_dim_eval:w <dimexpr> _dim_eval_end:</code> but when debugging is enabled this expands to a more complicated construction that evaluates <i><dimexpr></i> with parentheses and within a brace group to detect early termination.

Part XX

The l3keys package

Key–value interfaces

The key–value method is a popular system for creating large numbers of settings for controlling function or package behaviour. The system normally results in input of the form

```
\MyModuleSetup{
  key-one = value one,
  key-two = value two
}
```

or

```
\MyModuleMacro[
  key-one = value one,
  key-two = value two
]{argument}
```

for the user.

The high level functions here are intended as a method to create key–value controls. Keys are themselves created using a key–value interface, minimising the number of functions and arguments required. Each key is created by setting one or more *properties* of the key:

```
\keys_define:nn { mymodule }
{
  key-one .code:n = code including parameter #1,
  key-two .tl_set:N = \l_mymodule_store_tl
}
```

These values can then be set as with other key–value approaches:

```
\keys_set:nn { mymodule }
{
  key-one = value one,
  key-two = value two
}
```

At a document level, `\keys_set:nn` is used within a document function, for example

```
\DeclareDocumentCommand \MyModuleSetup { m }
{ \keys_set:nn { mymodule } { #1 } }
\DeclareDocumentCommand \MyModuleMacro { o m }
{
  \group_begin:
    \keys_set:nn { mymodule } { #1 }
    % Main code for \MyModuleMacro
  \group_end:
}
```

Key names may contain any tokens, as they are handled internally using `\tl_to_str:n`. As discussed in section 2, it is suggested that the character `/` is reserved for sub-division of keys into logical groups. Functions and variables are *not* expanded when creating key names, and so

```
\tl_set:Nn \l_mymodule_tmp_tl { key }
\keys_define:nn { mymodule }
{
  \l_mymodule_tmp_tl .code:n = code
}
```

creates a key called `\l_mymodule_tmp_tl`, and not one called `key`.

1 Creating keys

`\keys_define:nn`

Updated: 2015-11-07

`\keys_define:nn {<module>} {<keyval list>}`

Parses the *<keyval list>* and defines the keys listed there for *<module>*. The *<module>* name should be a text value, but there are no restrictions on the nature of the text. In practice the *<module>* should be chosen to be unique to the module in question (unless deliberately adding keys to an existing module).

The *<keyval list>* should consist of one or more key names along with an associated key *property*. The properties of a key determine how it acts. The individual properties are described in the following text; a typical use of `\keys_define:nn` might read

```
\keys_define:nn { mymodule }
{
  keyname .code:n = Some-code~using~#1,
  keyname .value_required:n = true
}
```

where the properties of the key begin from the `.` after the key name.

The various properties available take either no arguments at all, or require one or more arguments. This is indicated in the name of the property using an argument specification. In the following discussion, each property is illustrated attached to an arbitrary *<key>*, which when used may be supplied with a *<value>*. All key *definitions* are local.

Key properties are applied in the reading order and so the ordering is significant. Key properties which define “actions”, such as `.code:n`, `.tl_set:N`, *etc.*, override one another. Some other properties are mutually exclusive, notably `.value_required:n` and `.value_forbidden:n`, and so they replace one another. However, properties covering non-exclusive behaviours may be given in any order. Thus for example the following definitions are equivalent.

```
\keys_define:nn { mymodule }
{
  keyname .code:n          = Some-code~using~#1,
  keyname .value_required:n = true
}
\keys_define:nn { mymodule }
```

```

{
  keyname .value_required:n = true,
  keyname .code:n           = Some~code~using~#1
}

```

Note that with the exception of the special `.undefine:` property, all key properties define the key within the current \TeX scope.

```

.bool_set:N
.bool_set:c
.bool_gset:N
.bool_gset:c

```

Updated: 2013-07-08

$\langle key \rangle$.bool_set:N = $\langle boolean \rangle$

Defines $\langle key \rangle$ to set $\langle boolean \rangle$ to $\langle value \rangle$ (which must be either `true` or `false`). If the variable does not exist, it will be created globally at the point that the key is set up.

```

.bool_set_inverse:N
.bool_set_inverse:c
.bool_gset_inverse:N
.bool_gset_inverse:c

```

New: 2011-08-28

Updated: 2013-07-08

$\langle key \rangle$.bool_set_inverse:N = $\langle boolean \rangle$

Defines $\langle key \rangle$ to set $\langle boolean \rangle$ to the logical inverse of $\langle value \rangle$ (which must be either `true` or `false`). If the $\langle boolean \rangle$ does not exist, it will be created globally at the point that the key is set up.

```

.choice:

```

$\langle key \rangle$.choice:

Sets $\langle key \rangle$ to act as a choice key. Each valid choice for $\langle key \rangle$ must then be created, as discussed in section 3.

```

.choices:nn
.choices:(Vn|on|xn)

```

New: 2011-08-21

Updated: 2013-07-10

$\langle key \rangle$.choices:nn = $\{\langle choices \rangle\}$ $\{\langle code \rangle\}$

Sets $\langle key \rangle$ to act as a choice key, and defines a series $\langle choices \rangle$ which are implemented using the $\langle code \rangle$. Inside $\langle code \rangle$, `\l_keys_choice_tl` will be the name of the choice made, and `\l_keys_choice_int` will be the position of the choice in the list of $\langle choices \rangle$ (indexed from 1). Choices are discussed in detail in section 3.

```

.clist_set:N
.clist_set:c
.clist_gset:N
.clist_gset:c

```

New: 2011-09-11

$\langle key \rangle$.clist_set:N = $\langle comma list variable \rangle$

Defines $\langle key \rangle$ to set $\langle comma list variable \rangle$ to $\langle value \rangle$. Spaces around commas and empty items will be stripped. If the variable does not exist, it is created globally at the point that the key is set up.

```

.code:n

```

Updated: 2013-07-10

$\langle key \rangle$.code:n = $\{\langle code \rangle\}$

Stores the $\langle code \rangle$ for execution when $\langle key \rangle$ is used. The $\langle code \rangle$ can include one parameter (#1), which will be the $\langle value \rangle$ given for the $\langle key \rangle$. The x-type variant expands $\langle code \rangle$ at the point where the $\langle key \rangle$ is created.

`.default:n`
`.default:(V|o|x)`
Updated: 2013-07-09

`<key> .default:n = {<default>}`

Creates a *<default>* value for *<key>*, which is used if no value is given. This will be used if only the key name is given, but not if a blank *<value>* is given:

```
\keys_define:nn { mymodule }
{
    key .code:n      = Hello~#1,
    key .default:n = World
}
\keys_set:nn { mymodule }
{
    key = Fred, % Prints 'Hello Fred'
    key,      % Prints 'Hello World'
    key = ,    % Prints 'Hello '
}
```

The default does not affect keys where values are required or forbidden. Thus a required value cannot be supplied by a default value, and giving a default value for a key which cannot take a value does not trigger an error.

`.dim_set:N`
`.dim_set:c`
`.dim_gset:N`
`.dim_gset:c`

`<key> .dim_set:N = <dimension>`

Defines *<key>* to set *<dimension>* to *<value>* (which must a dimension expression). If the variable does not exist, it is created globally at the point that the key is set up.

`.fp_set:N`
`.fp_set:c`
`.fp_gset:N`
`.fp_gset:c`

`<key> .fp_set:N = <floating point>`

Defines *<key>* to set *<floating point>* to *<value>* (which must a floating point expression). If the variable does not exist, it is created globally at the point that the key is set up.

`.groups:n`
New: 2013-07-14

`<key> .groups:n = {<groups>}`

Defines *<key>* as belonging to the *<groups>* declared. Groups provide a “secondary axis” for selectively setting keys, and are described in Section 6.

`.inherit:n`
New: 2016-11-22

`<key> .inherit:n = {<parents>}`

Specifies that the *<key>* path should inherit the keys listed as *<parents>*. For example, after setting

```
\keys_define:n { foo } { test .code:n = \tl_show:n {#1} }
\keys_define:n { } { bar .inherit:n = foo }
```

setting

```
\keys_set:n { bar } { test = a }
```

will be equivalent to

```
\keys_set:n { foo } { test = a }
```

<hr/> <code>.initial:n</code> <hr/>	<code><key> .initial:n = {<value>}</code>
<code>.initial:(V o x)</code>	Initialises the <code><key></code> with the <code><value></code> , equivalent to
<hr/> Updated: 2013-07-09 <hr/>	<code>\keys_set:nn {<module>} { <key> = <value> }</code>
<hr/> <code>.int_set:N</code> <hr/>	<code><key> .int_set:N = <integer></code>
<code>.int_set:c</code>	Defines <code><key></code> to set <code><integer></code> to <code><value></code> (which must be an integer expression). If the variable does not exist, it is created globally at the point that the key is set up.
<code>.int_gset:N</code>	
<code>.int_gset:c</code> <hr/>	
<hr/> <code>.meta:n</code> <hr/>	<code><key> .meta:n = {<keyval list>}</code>
<hr/> Updated: 2013-07-10 <hr/>	Makes <code><key></code> a meta-key, which will set <code><keyval list></code> in one go. If <code><key></code> is given with a value at the time the key is used, then the value will be passed through to the subsidiary <code><keys></code> for processing (as #1).
<hr/> <code>.meta:nn</code> <hr/>	<code><key> .meta:nn = {<path>} {<keyval list>}</code>
<hr/> New: 2013-07-10 <hr/>	Makes <code><key></code> a meta-key, which will set <code><keyval list></code> in one go using the <code><path></code> in place of the current one. If <code><key></code> is given with a value at the time the key is used, then the value will be passed through to the subsidiary <code><keys></code> for processing (as #1).
<hr/> <code>.multichoice:</code> <hr/>	<code><key> .multichoice:</code>
<hr/> New: 2011-08-21 <hr/>	Sets <code><key></code> to act as a multiple choice key. Each valid choice for <code><key></code> must then be created, as discussed in section 3.
<hr/> <code>.multichoices:nn</code> <hr/>	<code><key> .multichoices:nn {<choices>} {<code>}</code>
<code>.multichoices:(Vn on xn)</code>	Sets <code><key></code> to act as a multiple choice key, and defines a series <code><choices></code> which are implemented using the <code><code></code> . Inside <code><code></code> , <code>\l_keys_choice_tl</code> will be the name of the choice made, and <code>\l_keys_choice_int</code> will be the position of the choice in the list of <code><choices></code> (indexed from 1). Choices are discussed in detail in section 3.
<hr/> New: 2011-08-21 <hr/>	
<hr/> Updated: 2013-07-10 <hr/>	
<hr/> <code>.skip_set:N</code> <hr/>	<code><key> .skip_set:N = <skip></code>
<code>.skip_set:c</code>	Defines <code><key></code> to set <code><skip></code> to <code><value></code> (which must be a skip expression). If the variable does not exist, it is created globally at the point that the key is set up.
<code>.skip_gset:N</code>	
<code>.skip_gset:c</code> <hr/>	
<hr/> <code>.tl_set:N</code> <hr/>	<code><key> .tl_set:N = <token list variable></code>
<code>.tl_set:c</code>	Defines <code><key></code> to set <code><token list variable></code> to <code><value></code> . If the variable does not exist, it is created globally at the point that the key is set up.
<code>.tl_gset:N</code>	
<code>.tl_gset:c</code> <hr/>	
<hr/> <code>.tl_set_x:N</code> <hr/>	<code><key> .tl_set_x:N = <token list variable></code>
<code>.tl_set_x:c</code>	Defines <code><key></code> to set <code><token list variable></code> to <code><value></code> , which will be subjected to an x-type expansion (<i>i.e.</i> using <code>\tl_set:Nx</code>). If the variable does not exist, it is created globally at the point that the key is set up.
<code>.tl_gset_x:N</code>	
<code>.tl_gset_x:c</code> <hr/>	

<code>.undefine:</code>	<code><key> .undefine:</code>
-------------------------	-------------------------------------

New: 2015-07-14	Removes the definition of the <code><key></code> within the current scope.
-----------------	--

<code>.value_forbidden:n</code>	<code><key> .value_forbidden:n = true false</code>
---------------------------------	--

New: 2015-07-14	Specifies that <code><key></code> cannot receive a <code><value></code> when used. If a <code><value></code> is given then an error will be issued. Setting the property <code>false</code> cancels the restriction.
-----------------	--

<code>.value_required:n</code>	<code><key> .value_required:n = true false</code>
--------------------------------	---

New: 2015-07-14	Specifies that <code><key></code> must receive a <code><value></code> when used. If a <code><value></code> is not given then an error will be issued. Setting the property <code>false</code> cancels the restriction.
-----------------	--

2 Sub-dividing keys

When creating large numbers of keys, it may be desirable to divide them into several sub-groups for a given module. This can be achieved either by adding a sub-division to the module name:

```
\keys_define:nn { module / subgroup }
{ key .code:n = code }
```

or to the key name:

```
\keys_define:nn { mymodule }
{ subgroup / key .code:n = code }
```

As illustrated, the best choice of token for sub-dividing keys in this way is `/`. This is because of the method that is used to represent keys internally. Both of the above code fragments set the same key, which has full name `module/subgroup/key`.

As illustrated in the next section, this subdivision is particularly relevant to making multiple choices.

3 Choice and multiple choice keys

The `l3keys` system supports two types of choice key, in which a series of pre-defined input values are linked to varying implementations. Choice keys are usually created so that the various values are mutually-exclusive: only one can apply at any one time. “Multiple” choice keys are also supported: these allow a selection of values to be chosen at the same time.

Mutually-exclusive choices are created by setting the `.choice:` property:

```
\keys_define:nn { mymodule }
{ key .choice: }
```

For keys which are set up as choices, the valid choices are generated by creating sub-keys of the choice key. This can be carried out in two ways.

In many cases, choices execute similar code which is dependant only on the name of the choice or the position of the choice in the list of all possibilities. Here, the keys can share the same code, and can be rapidly created using the `.choices:nn` property.

```

\keys_define:nn { mymodule }
{
  key .choices:nn =
    { choice-a, choice-b, choice-c }
    {
      You~gave~choice~'\tl_use:N \l_keys_choice_tl',~
      which~is~in~position~\int_use:N \l_keys_choice_int \c_space_tl
      in~the~list.
    }
}

```

The index `\l_keys_choice_int` in the list of choices starts at 1.

`\l_keys_choice_int`
`\l_keys_choice_tl`

Inside the code block for a choice generated using `.choices:nn`, the variables `\l_keys_choice_tl` and `\l_keys_choice_int` are available to indicate the name of the current choice, and its position in the comma list. The position is indexed from 1. Note that, as with standard key code generated using `.code:n`, the value passed to the key (i.e. the choice name) is also available as `#1`.

On the other hand, it is sometimes useful to create choices which use entirely different code from one another. This can be achieved by setting the `.choice:` property of a key, then manually defining sub-keys.

```

\keys_define:nn { mymodule }
{
  key .choice:,
  key / choice-a .code:n = code-a,
  key / choice-b .code:n = code-b,
  key / choice-c .code:n = code-c,
}

```

It is possible to mix the two methods, but manually-created choices should *not* use `\l_keys_choice_tl` or `\l_keys_choice_int`. These variables do not have defined behaviour when used outside of code created using `.choices:nn` (i.e. anything might happen).

It is possible to allow choice keys to take values which have not previously been defined by adding code for the special `unknown` choice. The general behavior of the `unknown` key is described in Section 5. A typical example in the case of a choice would be to issue a custom error message:

```

\keys_define:nn { mymodule }
{
  key .choice:,
  key / choice-a .code:n = code-a,
  key / choice-b .code:n = code-b,
  key / choice-c .code:n = code-c,
  key / unknown .code:n =
    \msg_error:nnxxx { mymodule } { unknown-choice }
    { key } % Name of choice key
    { choice-a , choice-b , choice-c } % Valid choices
    { \exp_not:n {#1} } % Invalid choice given
}

```

```
%
%
}
```

Multiple choices are created in a very similar manner to mutually-exclusive choices, using the properties `.multichoice:` and `.multichoices:nn`. As with mutually exclusive choices, multiple choices are define as sub-keys. Thus both

```
\keys_define:nn { mymodule }
{
  key .multichoices:nn =
    { choice-a, choice-b, choice-c }
    {
      You~gave~choice~'\tl_use:N \l_keys_choice_tl',~
      which~is~in~position~
      \int_use:N \l_keys_choice_int \c_space_tl
      in~the~list.
    }
}
```

and

```
\keys_define:nn { mymodule }
{
  key .multichoice:,
  key / choice-a .code:n = code-a,
  key / choice-b .code:n = code-b,
  key / choice-c .code:n = code-c,
}
```

are valid.

When a multiple choice key is set

```
\keys_set:nn { mymodule }
{
  key = { a , b , c } % 'key' defined as a multiple choice
}
```

each choice is applied in turn, equivalent to a `clist` mapping or to applying each value individually:

```
\keys_set:nn { mymodule }
{
  key = a ,
  key = b ,
  key = c ,
}
```

Thus each separate choice will have passed to it the `\l_keys_choice_tl` and `\l_keys_choice_int` in exactly the same way as described for `.choices:nn`.

4 Setting keys

```
\keys_set:nn  
\keys_set:(nV|nv|no)
```

Updated: 2015-11-07

```
\keys_set:nn {<module>} {<keyval list>}
```

Parses the *<keyval list>*, and sets those keys which are defined for *<module>*. The behaviour on finding an unknown key can be set by defining a special **unknown** key: this is illustrated later.

```
\l_keys_key_tl  
\l_keys_path_tl  
\l_keys_value_tl
```

Updated: 2015-07-14

For each key processed, information of the full *path* of the key, the *name* of the key and the *value* of the key is available within three token list variables. These may be used within the code of the key.

The *value* is everything after the =, which may be empty if no value was given. This is stored in `\l_keys_value_tl`, and is not processed in any way by `\keys_set:nn`.

The *path* of the key is a “full” description of the key, and is unique for each key. It consists of the module and full key name, thus for example

```
\keys_set:nn { mymodule } { key-a = some-value }
```

has path `mymodule/key-a` while

```
\keys_set:nn { mymodule } { subset / key-a = some-value }
```

has path `mymodule/subset/key-a`. This information is stored in `\l_keys_path_tl`, and will have been processed by `\tl_to_str:n`.

The *name* of the key is the part of the path after the last /, and thus is not unique. In the preceding examples, both keys have name `key-a` despite having different paths. This information is stored in `\l_keys_key_tl`, and will have been processed by `\tl_to_str:n`.

5 Handling of unknown keys

If a key has not previously been defined (is unknown), `\keys_set:nn` looks for a special **unknown** key for the same module, and if this is not defined raises an error indicating that the key name was unknown. This mechanism can be used for example to issue custom error texts.

```
\keys_define:nn { mymodule }  
{  
  unknown .code:n =  
    You~tried~to~set~key~'\l_keys_key_tl'~to~'#1'.  
}
```

```

\keys_set_known:nnN      \keys_set_known:nnN {<module>} {<keyval list>} {<tl>}
\keys_set_known:(nVN|nvN|noN)
\keys_set_known:nn
\keys_set_known:(nV|nv|no)

```

New: 2011-08-23
Updated: 2017-05-27

In some cases, the desired behavior is to simply ignore unknown keys, collecting up information on these for later processing. The `\keys_set_known:nnN` function parses the `<keyval list>`, and sets those keys which are defined for `<module>`. Any keys which are unknown are not processed further by the parser. The key-value pairs for each *unknown* key name are stored in the `<tl>` in a comma-separated form (*i.e.* an edited version of the `<keyval list>`). The `\keys_set_known:nn` version skips this stage.

Use of `\keys_set_known:nnN` can be nested, with the correct residual `<keyval list>` returned at each stage.

6 Selective key setting

In some cases it may be useful to be able to select only some keys for setting, even though these keys have the same path. For example, with a set of keys defined using

```

\keys define:nn { mymodule }
{
  key-one   .code:n   = { \my_func:n {#1} } ,
  key-two   .tl_set:N = \l_my_a_tl           ,
  key-three .tl_set:N = \l_my_b_tl           ,
  key-four  .fp_set:N = \l_my_a_fp           ,
}

```

the use of `\keys_set:nn` attempts to set all four keys. However, in some contexts it may only be sensible to set some keys, or to control the order of setting. To do this, keys may be assigned to *groups*: arbitrary sets which are independent of the key tree. Thus modifying the example to read

```

\keys define:nn { mymodule }
{
  key-one   .code:n   = { \my_func:n {#1} } ,
  key-one   .groups:n = { first }           ,
  key-two   .tl_set:N = \l_my_a_tl           ,
  key-two   .groups:n = { first }           ,
  key-three .tl_set:N = \l_my_b_tl           ,
  key-three .groups:n = { second }          ,
  key-four  .fp_set:N = \l_my_a_fp           ,
}

```

assigns `key-one` and `key-two` to group `first`, `key-three` to group `second`, while `key-four` is not assigned to a group.

Selective key setting may be achieved either by selecting one or more groups to be made “active”, or by marking one or more groups to be ignored in key setting.

<code>\keys_set_filter:nnnN</code>	<code>\keys_set_filter:nnnN {<module>} {<groups>} {<keyval list>} {<tl>}</code>
<code>\keys_set_filter:(nnVN nnvN nnoN)</code>	
<code>\keys_set_filter:nnn</code>	
<code>\keys_set_filter:(nnV nnv nno)</code>	

New: 2013-07-14

Updated: 2017-05-27

Activates key filtering in an “opt-out” sense: keys assigned to any of the $\langle groups \rangle$ specified are ignored. The $\langle groups \rangle$ are given as a comma-separated list. Unknown keys are not assigned to any group and are thus always set. The key-value pairs for each key which is filtered out are stored in the $\langle tl \rangle$ in a comma-separated form (*i.e.* an edited version of the $\langle keyval list \rangle$). The `\keys_set_filter:nnn` version skips this stage.

Use of `\keys_set_filter:nnnN` can be nested, with the correct residual $\langle keyval list \rangle$ returned at each stage.

<code>\keys_set_groups:nnn</code>	<code>\keys_set_groups:nnn {<module>} {<groups>} {<keyval list>}</code>
<code>\keys_set_groups:(nnV nnv nno)</code>	

New: 2013-07-14

Updated: 2017-05-27

Activates key filtering in an “opt-in” sense: only keys assigned to one or more of the $\langle groups \rangle$ specified are set. The $\langle groups \rangle$ are given as a comma-separated list. Unknown keys are not assigned to any group and are thus never set.

7 Utility functions for keys

<code>\keys_if_exist_p:nn</code> ★	<code>\keys_if_exist_p:nn {<module>} {<key>}</code>
<code>\keys_if_exist:nnTF</code> ★	<code>\keys_if_exist:nnTF {<module>} {<key>} {<true code>} {<false code>}</code>

Updated: 2015-11-07 Tests if the $\langle key \rangle$ exists for $\langle module \rangle$, *i.e.* if any code has been defined for $\langle key \rangle$.

<code>\keys_if_choice_exist_p:nnn</code> ★	<code>\keys_if_choice_exist_p:nnn {<module>} {<key>} {<choice>}</code>
<code>\keys_if_choice_exist:nnnTF</code> ★	<code>\keys_if_choice_exist:nnnTF {<module>} {<key>} {<choice>} {<true code>} {<false code>}</code>

New: 2011-08-21

Updated: 2015-11-07

Tests if the $\langle choice \rangle$ is defined for the $\langle key \rangle$ within the $\langle module \rangle$, *i.e.* if any code has been defined for $\langle key \rangle / \langle choice \rangle$. The test is **false** if the $\langle key \rangle$ itself is not defined.

<code>\keys_show:nn</code>	<code>\keys_show:nn {<module>} {<key>}</code>
----------------------------	---

Updated: 2015-08-09

Displays in the terminal the information associated to the $\langle key \rangle$ for a $\langle module \rangle$, including the function which is used to actually implement it.

<code>\keys_log:nn</code>	<code>\keys_log:nn {<module>} {<key>}</code>
---------------------------	--

New: 2014-08-22

Updated: 2015-08-09

Writes in the log file the information associated to the $\langle key \rangle$ for a $\langle module \rangle$. See also `\keys_show:nn` which displays the result in the terminal.

8 Low-level interface for parsing key–val lists

To re-cap from earlier, a key–value list is input of the form

```
KeyOne = ValueOne ,  
KeyTwo = ValueTwo ,  
KeyThree
```

where each key–value pair is separated by a comma from the rest of the list, and each key–value pair does not necessarily contain an equals sign or a value! Processing this type of input correctly requires a number of careful steps, to correctly account for braces, spaces and the category codes of separators.

While the functions described earlier are used as a high-level interface for processing such input, in special circumstances you may wish to use a lower-level approach. The low-level parsing system converts a *key–value list* into *keys* and associated *values*. After the parsing phase is completed, the resulting keys and values (or keys alone) are available for further processing. This processing is not carried out by the low-level parser itself, and so the parser requires the names of two functions along with the key–value list. One function is needed to process key–value pairs (it receives two arguments), and a second function is required for keys given without any value (it is called with a single argument).

The parser does not double # tokens or expand any input. Active tokens = and , appearing at the outer level of braces are converted to category “other” (12) so that the parser does not “miss” any due to category code changes. Spaces are removed from the ends of the keys and values. Keys and values which are given in braces have exactly one set removed (after space trimming), thus

```
key = {value here},
```

and

```
key = value here,
```

are treated identically.

\keyval_parse:NNn

Updated: 2011-09-08

\keyval_parse:NNn $\langle function_1 \rangle$ $\langle function_2 \rangle$ { $\langle key-value list \rangle$ }

Parses the $\langle key-value list \rangle$ into a series of $\langle keys \rangle$ and associated $\langle values \rangle$, or keys alone (if no $\langle value \rangle$ was given). $\langle function_1 \rangle$ should take one argument, while $\langle function_2 \rangle$ should absorb two arguments. After **\keyval_parse:NNn** has parsed the $\langle key-value list \rangle$, $\langle function_1 \rangle$ is used to process keys given with no value and $\langle function_2 \rangle$ is used to process keys given with a value. The order of the $\langle keys \rangle$ in the $\langle key-value list \rangle$ is preserved. Thus

```
\keyval_parse:NNn \function:n \function:nn
{ key1 = value1 , key2 = value2, key3 = , key4 }
```

is converted into an input stream

```
\function:nn { key1 } { value1 }
\function:nn { key2 } { value2 }
\function:nn { key3 } { }
\function:n { key4 }
```

Note that there is a difference between an empty value (an equals sign followed by nothing) and a missing value (no equals sign at all). Spaces are trimmed from the ends of the $\langle key \rangle$ and $\langle value \rangle$, then one *outer* set of braces is removed from the $\langle key \rangle$ and $\langle value \rangle$ as part of the processing.

Part XXI

The l3fp package: floating points

A decimal floating point number is one which is stored as a significand and a separate exponent. The module implements expandably a wide set of arithmetic, trigonometric, and other operations on decimal floating point numbers, to be used within floating point expressions. Floating point expressions support the following operations with their usual precedence.

- Basic arithmetic: addition $x + y$, subtraction $x - y$, multiplication $x * y$, division x / y , square root \sqrt{x} , and parentheses.
- Comparison operators: $x < y$, $x <= y$, $x >? y$, $x != y$ etc.
- Boolean logic: sign $\text{sign } x$, negation $!x$, conjunction $x \&\& y$, disjunction $x || y$, ternary operator $x ? y : z$.
- Exponentials: $\exp x$, $\ln x$, x^y .
- Trigonometry: $\sin x$, $\cos x$, $\tan x$, $\cot x$, $\sec x$, $\csc x$ expecting their arguments in radians, and $\text{sind } x$, $\text{cosd } x$, $\text{tand } x$, $\text{cotd } x$, $\text{secd } x$, $\text{cscd } x$ expecting their arguments in degrees.
- Inverse trigonometric functions: $\text{asin } x$, $\text{acos } x$, $\text{atan } x$, $\text{acot } x$, $\text{asec } x$, $\text{acsc } x$ giving a result in radians, and $\text{asind } x$, $\text{acosd } x$, $\text{atand } x$, $\text{acotd } x$, $\text{asecd } x$, $\text{acscd } x$ giving a result in degrees.

(not yet) Hyperbolic functions and their inverse functions: $\sinh x$, $\cosh x$, $\tanh x$, $\coth x$, $\text{sech } x$, $\text{csch } x$, and $\text{asinh } x$, $\text{acosh } x$, $\text{atanh } x$, $\text{acoth } x$, $\text{asech } x$, $\text{acsch } x$.

- Extrema: $\max(x, y, \dots)$, $\min(x, y, \dots)$, $\text{abs}(x)$.
- Rounding functions ($n = 0$ by default, $t = \text{NaN}$ by default): $\text{trunc}(x, n)$ rounds towards zero, $\text{floor}(x, n)$ rounds towards $-\infty$, $\text{ceil}(x, n)$ rounds towards $+\infty$, $\text{round}(x, n, t)$ rounds to the closest value, with ties rounded to an even value by default, towards zero if $t = 0$, towards $+\infty$ if $t > 0$ and towards $-\infty$ if $t < 0$. And (not yet) modulo, and “quantize”.
- Random numbers: $\text{rand}()$, $\text{randint}(m, n)$ in pdfTeX and LuaTeX engines.
- Constants: `pi`, `deg` (one degree in radians).
- Dimensions, automatically expressed in points, e.g., `pc` is 12.
- Automatic conversion (no need for `\langle type \rangle_use:N`) of integer, dimension, and skip variables to floating points, expressing dimensions in points and ignoring the stretch and shrink components of skips.

Floating point numbers can be given either explicitly (in a form such as `1.234e-34`, or `-.0001`), or as a stored floating point variable, which is automatically replaced by its current value. See section 9.1 for a description of what a floating point is, section 9.2 for details about how an expression is parsed, and section 9.3 to know what the various operations do. Some operations may raise exceptions (error messages), described in section 7.

An example of use could be the following.

`\LaTeX{}` can now compute: $\frac{\sin(3.5)}{2} + 2 \cdot 10^{-3}$
`= \ExplSyntaxOn \fp_to_decimal:n {sin 3.5 /2 + 2e-3} $.`

But in all fairness, this module is mostly meant as an underlying tool for higher-level commands. For example, one could provide a function to typeset nicely the result of floating point computations.

```
\documentclass{article}
\usepackage{xparse, siunitx}
\ExplSyntaxOn
\NewDocumentCommand { \calcnun } { m }
{ \num { \fp_to_scientific:n {#1} } }
\ExplSyntaxOff
\begin{document}
\calcnun { 2 pi * sin ( 2.3 ^ 5 ) }
\end{document}
```

1 Creating and initialising floating point variables

<code>\fp_new:N</code>	<code>\fp_new:N <fp var></code>
<code>\fp_new:c</code>	Creates a new <i><fp var></i> or raises an error if the name is already taken. The declaration is global. The <i><fp var></i> is initially +0.
Updated: 2012-05-08	
<code>\fp_const:Nn</code>	<code>\fp_const:Nn <fp var> {<floating point expression>}</code>
<code>\fp_const:cn</code>	Creates a new constant <i><fp var></i> or raises an error if the name is already taken. The <i><fp var></i> is set globally equal to the result of evaluating the <i><floating point expression></i> .
Updated: 2012-05-08	
<code>\fp_zero:N</code>	<code>\fp_zero:N <fp var></code>
<code>\fp_zero:c</code>	Sets the <i><fp var></i> to +0.
<code>\fp_gzero:N</code>	
<code>\fp_gzero:c</code>	
Updated: 2012-05-08	
<code>\fp_zero_new:N</code>	<code>\fp_zero_new:N <fp var></code>
<code>\fp_zero_new:c</code>	Ensures that the <i><fp var></i> exists globally by applying <code>\fp_new:N</code> if necessary, then applies <code>\fp_(g)zero:N</code> to leave the <i><fp var></i> set to +0.
<code>\fp_gzero_new:N</code>	
<code>\fp_gzero_new:c</code>	
Updated: 2012-05-08	

2 Setting floating point variables

<code>\fp_set:Nn</code>	<code>\fp_set:Nn <fp var> {<floating point expression>}</code>
<code>\fp_set:cn</code>	Sets <i><fp var></i> equal to the result of computing the <i><floating point expression></i> .
<code>\fp_gset:Nn</code>	
<code>\fp_gset:cn</code>	
Updated: 2012-05-08	

```
\fp_set_eq:NN
\fp_set_eq:(cN|Nc|cc)
\fp_gset_eq:NN
\fp_gset_eq:(cN|Nc|cc)
```

Updated: 2012-05-08

```
\fp_add:Nn
\fp_add:cn
\fp_gadd:Nn
\fp_gadd:cn
```

Updated: 2012-05-08

```
\fp_sub:Nn
\fp_sub:cn
\fp_gsub:Nn
\fp_gsub:cn
```

Updated: 2012-05-08

```
\fp_set_eq:NN <fp var1> <fp var2>
```

Sets the floating point variable $\langle fp\ var_1 \rangle$ equal to the current value of $\langle fp\ var_2 \rangle$.

```
\fp_add:Nn <fp var> {<floating point expression>}
```

Adds the result of computing the $\langle floating\ point\ expression \rangle$ to the $\langle fp\ var \rangle$.

```
\fp_sub:Nn <fp var> {<floating point expression>}
```

Subtracts the result of computing the $\langle floating\ point\ expression \rangle$ from the $\langle fp\ var \rangle$.

3 Using floating point numbers

```
\fp_eval:n ★
```

New: 2012-05-08

Updated: 2012-07-08

```
\fp_eval:n {<floating point expression>}
```

Evaluates the $\langle floating\ point\ expression \rangle$ and expresses the result as a decimal number with no exponent. Leading or trailing zeros may be inserted to compensate for the exponent. Non-significant trailing zeros are trimmed, and integers are expressed without a decimal separator. The values $\pm\infty$ and NaN trigger an “invalid operation” exception. This function is identical to `\fp_to_decimal:n`.

```
\fp_to_decimal:N ★
\fp_to_decimal:c ★
\fp_to_decimal:n ★
```

New: 2012-05-08

Updated: 2012-07-08

```
\fp_to_decimal:N <fp var>
```

```
\fp_to_decimal:n {<floating point expression>}
```

Evaluates the $\langle floating\ point\ expression \rangle$ and expresses the result as a decimal number with no exponent. Leading or trailing zeros may be inserted to compensate for the exponent. Non-significant trailing zeros are trimmed, and integers are expressed without a decimal separator. The values $\pm\infty$ and NaN trigger an “invalid operation” exception.

```
\fp_to_dim:N ★
\fp_to_dim:c ★
\fp_to_dim:n ★
```

Updated: 2016-03-22

```
\fp_to_dim:N <fp var>
```

```
\fp_to_dim:n {<floating point expression>}
```

Evaluates the $\langle floating\ point\ expression \rangle$ and expresses the result as a dimension (in pt) suitable for use in dimension expressions. The output is identical to `\fp_to_decimal:n`, with an additional trailing `pt` (both letter tokens). In particular, the result may be outside the range $[-2^{14} + 2^{-17}, 2^{14} - 2^{-17}]$ of valid TeX dimensions, leading to overflow errors if used as a dimension. The values $\pm\infty$ and NaN trigger an “invalid operation” exception.

<code>\fp_to_int:N</code>	★	<code>\fp_to_int:N</code>	$\langle fp\ var \rangle$
<code>\fp_to_int:c</code>	★	<code>\fp_to_int:n</code>	$\{ \langle floating\ point\ expression \rangle \}$
<code>\fp_to_int:n</code>	★		Evaluates the $\langle floating\ point\ expression \rangle$, and rounds the result to the closest integer, rounding exact ties to an even integer. The result may be outside the range $[-2^{31} + 1, 2^{31} - 1]$ of valid TeX integers, leading to overflow errors if used in an integer expression. The values $\pm\infty$ and NaN trigger an “invalid operation” exception.

Updated: 2012-07-08

<code>\fp_to_scientific:N</code>	★	<code>\fp_to_scientific:N</code>	$\langle fp\ var \rangle$
<code>\fp_to_scientific:c</code>	★	<code>\fp_to_scientific:n</code>	$\{ \langle floating\ point\ expression \rangle \}$
<code>\fp_to_scientific:n</code>	★		Evaluates the $\langle floating\ point\ expression \rangle$ and expresses the result in scientific notation:

New: 2012-05-08
Updated: 2016-03-22

$\langle optional\ - \rangle \langle digit \rangle . \langle 15\ digits \rangle e \langle optional\ sign \rangle \langle exponent \rangle$

The leading $\langle digit \rangle$ is non-zero except in the case of ± 0 . The values $\pm\infty$ and NaN trigger an “invalid operation” exception. Normal category codes apply: thus the `e` is category code 11 (a letter).

<code>\fp_to_tl:N</code>	★	<code>\fp_to_tl:N</code>	$\langle fp\ var \rangle$
<code>\fp_to_tl:c</code>	★	<code>\fp_to_tl:n</code>	$\{ \langle floating\ point\ expression \rangle \}$
<code>\fp_to_tl:n</code>	★		Evaluates the $\langle floating\ point\ expression \rangle$ and expresses the result in (almost) the shortest possible form. Numbers in the ranges $(0, 10^{-3})$ and $[10^{16}, \infty)$ are expressed in scientific notation with trailing zeros trimmed and no decimal separator when there is a single significant digit (this differs from <code>\fp_to_scientific:n</code>). Numbers in the range $[10^{-3}, 10^{16})$ are expressed in a decimal notation without exponent, with trailing zeros trimmed, and no decimal separator for integer values (see <code>\fp_to_decimal:n</code>). Negative numbers start with <code>-</code> . The special values ± 0 , $\pm\infty$ and NaN are rendered as <code>0</code> , <code>-0</code> , <code>inf</code> , <code>-inf</code> , and <code>nan</code> respectively. Normal category codes apply and thus <code>inf</code> or <code>nan</code> , if produced, are made up of letters.

Updated: 2016-03-22

<code>\fp_use:N</code>	★	<code>\fp_use:N</code>	$\langle fp\ var \rangle$
<code>\fp_use:c</code>	★		Inserts the value of the $\langle fp\ var \rangle$ into the input stream as a decimal number with no exponent. Leading or trailing zeros may be inserted to compensate for the exponent. Non-significant trailing zeros are trimmed. Integers are expressed without a decimal separator. The values $\pm\infty$ and NaN trigger an “invalid operation” exception. This function is identical to <code>\fp_to_decimal:N</code> .

Updated: 2012-07-08

4 Floating point conditionals

<code>\fp_if_exist_p:N</code>	★	<code>\fp_if_exist_p:N</code>	$\langle fp\ var \rangle$
<code>\fp_if_exist_p:c</code>	★	<code>\fp_if_exist:NTF</code>	$\langle fp\ var \rangle \{ \langle true\ code \rangle \} \{ \langle false\ code \rangle \}$
<code>\fp_if_exist:NTF</code>	★		Tests whether the $\langle fp\ var \rangle$ is currently defined. This does not check that the $\langle fp\ var \rangle$ really is a floating point variable.
<code>\fp_if_exist:cTF</code>	★		

Updated: 2012-05-08

<code>\fp_compare_p:nNn</code> ★ <code>\fp_compare:nNnTF</code> ★	<code>\fp_compare_p:nNn {<fpexpr₁>} <relation> {<fpexpr₂>}</code> <code>\fp_compare:nNnTF {<fpexpr₁>} <relation> {<fpexpr₂>} {(true code)} {(false code)}</code>
--	---

Updated: 2012-05-08

Compares the $\langle fpexpr_1 \rangle$ and the $\langle fpexpr_2 \rangle$, and returns **true** if the $\langle relation \rangle$ is obeyed. Two floating point numbers x and y may obey four mutually exclusive relations: $x < y$, $x = y$, $x > y$, or x and y are not ordered. The latter case occurs exactly when one or both operands is NaN, and this relation is denoted by the symbol ?. Note that a NaN is distinct from any value, even another NaN, hence $x = x$ is not true for a NaN. To test if a value is NaN, compare it to an arbitrary number with the “not ordered” relation.

```

\fp_compare:nNnTF { <value> } ? { 0 }
{ } % <value> is nan
{ } % <value> is not nan

```

<code>\fp_compare_p:n</code> ★ <code>\fp_compare:nTF</code> ★	<code>\fp_compare_p:n</code> <code>{</code> <code> <fpexpr₁> <relation₁></code> <code> ...</code> <code> <fpexpr_N> <relation_N></code> <code> <fpexpr_{N+1}></code> <code>}</code> <code>\fp_compare:nTF</code> <code>{</code> <code> <fpexpr₁> <relation₁></code> <code> ...</code> <code> <fpexpr_N> <relation_N></code> <code> <fpexpr_{N+1}></code> <code>}</code> <code>{(true code)} {(false code)}</code>
--	---

Updated: 2012-12-14

Evaluates the $\langle floating\ point\ expressions \rangle$ as described for `\fp_eval:n` and compares consecutive result using the corresponding $\langle relation \rangle$, namely it compares $\langle intexpr_1 \rangle$ and $\langle intexpr_2 \rangle$ using the $\langle relation_1 \rangle$, then $\langle intexpr_2 \rangle$ and $\langle intexpr_3 \rangle$ using the $\langle relation_2 \rangle$, until finally comparing $\langle intexpr_N \rangle$ and $\langle intexpr_{N+1} \rangle$ using the $\langle relation_N \rangle$. The test yields **true** if all comparisons are **true**. Each $\langle floating\ point\ expression \rangle$ is evaluated only once. Contrarily to `\int_compare:nTF`, all $\langle floating\ point\ expressions \rangle$ are computed, even if one comparison is **false**. Two floating point numbers x and y may obey four mutually exclusive relations: $x < y$, $x = y$, $x > y$, or x and y are not ordered. The latter case occurs exactly when one or both operands is NaN, and this relation is denoted by the symbol ?. Each $\langle relation \rangle$ can be any (non-empty) combination of $<$, $=$, $>$, and $?$, plus an optional leading ! (which negates the $\langle relation \rangle$), with the restriction that the $\langle relation \rangle$ may not start with $?$, as this symbol has a different meaning (in combination with $:$) within floatin point expressions. The comparison $x \langle relation \rangle y$ is then **true** if the $\langle relation \rangle$ does not start with ! and the actual relation ($<$, $=$, $>$, or $?$) between x and y appears within the $\langle relation \rangle$, or on the contrary if the $\langle relation \rangle$ starts with ! and the relation between x and y does not appear within the $\langle relation \rangle$. Common choices of $\langle relation \rangle$ include $>=$ (greater or equal), $!=$ (not equal), $!?$ or $<=>$ (comparable).

5 Floating point expression loops

<code>\fp_do_until:nNnn</code> ☆	<code>\fp_do_until:nNnn {<fpexpr₁>} <relation> {<fpexpr₂>} {<code>}</code>
New: 2012-08-16	Places the <i><code></i> in the input stream for T _E X to process, and then evaluates the relationship between the two <i><floating point expressions></i> as described for <code>\fp_compare:nNnTF</code> . If the test is false then the <i><code></i> is inserted into the input stream again and a loop occurs until the <i><relation></i> is true .
<code>\fp_do_while:nNnn</code> ☆	<code>\fp_do_while:nNnn {<fpexpr₁>} <relation> {<fpexpr₂>} {<code>}</code>
New: 2012-08-16	Places the <i><code></i> in the input stream for T _E X to process, and then evaluates the relationship between the two <i><floating point expressions></i> as described for <code>\fp_compare:nNnTF</code> . If the test is true then the <i><code></i> is inserted into the input stream again and a loop occurs until the <i><relation></i> is false .
<code>\fp_until_do:nNnn</code> ☆	<code>\fp_until_do:nNnn {<fpexpr₁>} <relation> {<fpexpr₂>} {<code>}</code>
New: 2012-08-16	Evaluates the relationship between the two <i><floating point expressions></i> as described for <code>\fp_compare:nNnTF</code> , and then places the <i><code></i> in the input stream if the <i><relation></i> is false . After the <i><code></i> has been processed by T _E X the test is repeated, and a loop occurs until the test is true .
<code>\fp_while_do:nNnn</code> ☆	<code>\fp_while_do:nNnn {<fpexpr₁>} <relation> {<fpexpr₂>} {<code>}</code>
New: 2012-08-16	Evaluates the relationship between the two <i><floating point expressions></i> as described for <code>\fp_compare:nNnTF</code> , and then places the <i><code></i> in the input stream if the <i><relation></i> is true . After the <i><code></i> has been processed by T _E X the test is repeated, and a loop occurs until the test is false .
<code>\fp_do_until:nn</code> ☆	<code>\fp_do_until:nn { <fpexpr₁> <relation> <fpexpr₂> } {<code>}</code>
New: 2012-08-16	Places the <i><code></i> in the input stream for T _E X to process, and then evaluates the relationship between the two <i><floating point expressions></i> as described for <code>\fp_compare:nTF</code> . If the test is false then the <i><code></i> is inserted into the input stream again and a loop occurs until the <i><relation></i> is true .
<code>\fp_do_while:nn</code> ☆	<code>\fp_do_while:nn { <fpexpr₁> <relation> <fpexpr₂> } {<code>}</code>
New: 2012-08-16	Places the <i><code></i> in the input stream for T _E X to process, and then evaluates the relationship between the two <i><floating point expressions></i> as described for <code>\fp_compare:nTF</code> . If the test is true then the <i><code></i> is inserted into the input stream again and a loop occurs until the <i><relation></i> is false .
<code>\fp_until_do:nn</code> ☆	<code>\fp_until_do:nn { <fpexpr₁> <relation> <fpexpr₂> } {<code>}</code>
New: 2012-08-16	Evaluates the relationship between the two <i><floating point expressions></i> as described for <code>\fp_compare:nTF</code> , and then places the <i><code></i> in the input stream if the <i><relation></i> is false . After the <i><code></i> has been processed by T _E X the test is repeated, and a loop occurs until the test is true .

<hr/> <code>\fp_while_do:nn</code> ☆ <hr/>	<code>\fp_while_do:nn { <fpexpr₁> <relation> <fpexpr₂> } {<code>}</code>
New: 2012-08-16	Evaluates the relationship between the two <i><floating point expressions></i> as described for <code>\fp_compare:nTF</code> , and then places the <i><code></i> in the input stream if the <i><relation></i> is true. After the <i><code></i> has been processed by T _E X the test is repeated, and a loop occurs until the test is false.

<hr/> <code>\fp_step_function:nnnN</code> ☆ <code>\fp_step_function:nnnc</code> ☆ <hr/>	<code>\fp_step_function:nnnN {<initial value>} {<step>} {<final value>} <function></code>
New: 2016-11-21 Updated: 2016-12-06	This function first evaluates the <i><initial value></i> , <i><step></i> and <i><final value></i> , all of which should be floating point expressions. The <i><function></i> is then placed in front of each <i><value></i> from the <i><initial value></i> to the <i><final value></i> in turn (using <i><step></i> between each <i><value></i>). The <i><step></i> must be non-zero. If the <i><step></i> is positive, the loop stops when the <i><value></i> becomes larger than the <i><final value></i> . If the <i><step></i> is negative, the loop stops when the <i><value></i> becomes smaller than the <i><final value></i> . The <i><function></i> should absorb one numerical argument. For example

```
\cs_set:Npn \my_func:n #1 { [I~saw~#1] \quad }
\fp_step_function:nnnN { 1.0 } { 0.1 } { 1.5 } \my_func:n
```

would print

```
[I saw 1.0]   [I saw 1.1]   [I saw 1.2]   [I saw 1.3]   [I saw 1.4]   [I saw 1.5]
```

T_EXhackers note: Due to rounding, it may happen that adding the *<step>* to the *<value>* does not change the *<value>*; such cases give an error, as they would otherwise lead to an infinite loop.

<hr/> <code>\fp_step_inline:nnnn</code> <hr/>	<code>\fp_step_inline:nnnn {<initial value>} {<step>} {<final value>} {<code>}</code>
New: 2016-11-21 Updated: 2016-12-06	This function first evaluates the <i><initial value></i> , <i><step></i> and <i><final value></i> , all of which should be floating point expressions. Then for each <i><value></i> from the <i><initial value></i> to the <i><final value></i> in turn (using <i><step></i> between each <i><value></i>), the <i><code></i> is inserted into the input stream with <code>#1</code> replaced by the current <i><value></i> . Thus the <i><code></i> should define a function of one argument (<code>#1</code>).

<hr/> <code>\fp_step_variable:nnnNn</code> <hr/>	<code>\fp_step_variable:nnnNn {<initial value>} {<step>} {<final value>} <tl var> {<code>}</code>
New: 2017-04-12	This function first evaluates the <i><initial value></i> , <i><step></i> and <i><final value></i> , all of which should be floating point expressions. Then for each <i><value></i> from the <i><initial value></i> to the <i><final value></i> in turn (using <i><step></i> between each <i><value></i>), the <i><code></i> is inserted into the input stream, with the <i><tl var></i> defined as the current <i><value></i> . Thus the <i><code></i> should make use of the <i><tl var></i> .

6 Some useful constants, and scratch variables

<hr/> <code>\c_zero_fp</code> <code>\c_minus_zero_fp</code> <hr/>	Zero, with either sign.
New: 2012-05-08	

<hr/> <code>\c_one_fp</code> <hr/>	One as an <code>fp</code> : useful for comparisons in some places.
<hr/> New: 2012-05-08 <hr/>	
<hr/> <code>\c_inf_fp</code> <code>\c_minus_inf_fp</code> <hr/>	Infinity, with either sign. These can be input directly in a floating point expression as <code>inf</code> and <code>-inf</code> .
<hr/> New: 2012-05-08 <hr/>	
<hr/> <code>\c_e_fp</code> <hr/>	The value of the base of the natural logarithm, $e = \exp(1)$.
<hr/> Updated: 2012-05-08 <hr/>	
<hr/> <code>\c_pi_fp</code> <hr/>	The value of π . This can be input directly in a floating point expression as <code>pi</code> .
<hr/> Updated: 2013-11-17 <hr/>	
<hr/> <code>\c_one_degree_fp</code> <hr/>	The value of 1° in radians. Multiply an angle given in degrees by this value to obtain a result in radians. Note that trigonometric functions expecting an argument in radians or in degrees are both available. Within floating point expressions, this can be accessed as <code>deg</code> .
<hr/> New: 2012-05-08 Updated: 2013-11-17 <hr/>	
<hr/> <code>\l_tmpa_fp</code> <code>\l_tmpb_fp</code> <hr/>	Scratch floating points for local assignment. These are never used by the kernel code, and so are safe for use with any $\text{\LaTeX}3$ -defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.
<hr/> <code>\g_tmpa_fp</code> <code>\g_tmpb_fp</code> <hr/>	Scratch floating points for global assignment. These are never used by the kernel code, and so are safe for use with any $\text{\LaTeX}3$ -defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.

7 Floating point exceptions

The functions defined in this section are experimental, and their functionality may be altered or removed altogether.

“Exceptions” may occur when performing some floating point operations, such as `0 / 0`, or `10 ** 1e9999`. The relevant IEEE standard defines 5 types of exceptions, of which we implement 4.

- *Overflow* occurs whenever the result of an operation is too large to be represented as a normal floating point number. This results in $\pm\infty$.
- *Underflow* occurs whenever the result of an operation is too close to 0 to be represented as a normal floating point number. This results in ± 0 .
- *Invalid operation* occurs for operations with no defined outcome, for instance `0/0` or `sin(∞)`, and results in a NaN. It also occurs for conversion functions whose target type does not have the appropriate infinite or NaN value (*e.g.*, `\fp_to_dim:n`).
- *Division by zero* occurs when dividing a non-zero number by 0, or when evaluating functions at poles, *e.g.*, `ln(0)` or `cot(0)`. This results in $\pm\infty$.

(*not yet*) *Inexact* occurs whenever the result of a computation is not exact, in other words, almost always. At the moment, this exception is entirely ignored in L^AT_EX3.

To each exception we associate a “flag”: `fp_overflow`, `fp_underflow`, `fp_invalid_operation` and `fp_division_by_zero`. The state of these flags can be tested and modified with commands from `l3flag`

By default, the “invalid operation” exception triggers an (expandable) error, and raises the corresponding flag. Other exceptions raise the corresponding flag but do not trigger an error. The behaviour when an exception occurs can be modified (using `\fp_trap:nn`) to either produce an error and raise the flag, or only raise the flag, or do nothing at all.

<code>\fp_trap:nn</code>	<code>\fp_trap:nn {(exception)} {(trap type)}</code>
New: 2012-07-19 Updated: 2017-02-13	All occurrences of the <code><exception></code> (<code>overflow</code> , <code>underflow</code> , <code>invalid_operation</code> or <code>division_by_zero</code>) within the current group are treated as <code><trap type></code> , which can be <ul style="list-style-type: none"> • none: the <code><exception></code> will be entirely ignored, and leave no trace; • flag: the <code><exception></code> will turn the corresponding flag on when it occurs; • error: additionally, the <code><exception></code> will halt the T_EX run and display some information about the current operation in the terminal.

This function is experimental, and may be altered or removed.

`flag_fp_overflow`
`flag_fp_underflow`
`flag_fp_invalid_operation`
`flag_fp_division_by_zero`

Flags denoting the occurrence of various floating-point exceptions.

8 Viewing floating points

<code>\fp_show:N</code>	<code>\fp_show:N {fp var}</code>
<code>\fp_show:c</code>	<code>\fp_show:n {(floating point expression)}</code>
<code>\fp_show:n</code>	Evaluates the <code><floating point expression></code> and displays the result in the terminal.

New: 2012-05-08
Updated: 2015-08-07

<code>\fp_log:N</code>	<code>\fp_log:N {fp var}</code>
<code>\fp_log:c</code>	<code>\fp_log:n {(floating point expression)}</code>
<code>\fp_log:n</code>	Evaluates the <code><floating point expression></code> and writes the result in the log file.

New: 2014-08-22
Updated: 2015-08-07

9 Floating point expressions

9.1 Input of floating point numbers

We support four types of floating point numbers:

- $\pm m \cdot 10^n$, a floating point number, with integer $1 \leq m \leq 10^{16}$, and $-10000 \leq n \leq 10000$;
- ± 0 , zero, with a given sign;
- $\pm \infty$, infinity, with a given sign;
- NaN, is “not a number”, and can be either quiet or signalling (*not yet*: this distinction is currently unsupported);

Normal floating point numbers are stored in base 10, with up to 16 significant figures.

On input, a normal floating point number consists of:

- $\langle sign \rangle$: a possibly empty string of + and - characters;
- $\langle significand \rangle$: a non-empty string of digits together with zero or one dot;
- $\langle exponent \rangle$ optionally: the character e, followed by a possibly empty string of + and - tokens, and a non-empty string of digits.

The sign of the resulting number is + if $\langle sign \rangle$ contains an even number of -, and - otherwise, hence, an empty $\langle sign \rangle$ denotes a non-negative input. The stored significand is obtained from $\langle significand \rangle$ by omitting the decimal separator and leading zeros, and rounding to 16 significant digits, filling with trailing zeros if necessary. In particular, the value stored is exact if the input $\langle significand \rangle$ has at most 16 digits. The stored $\langle exponent \rangle$ is obtained by combining the input $\langle exponent \rangle$ (0 if absent) with a shift depending on the position of the significand and the number of leading zeros.

A special case arises if the resulting $\langle exponent \rangle$ is either too large or too small for the floating point number to be represented. This results either in an overflow (the number is then replaced by $\pm \infty$), or an underflow (resulting in ± 0).

The result is thus ± 0 if and only if $\langle significand \rangle$ contains no non-zero digit (*i.e.*, consists only in characters 0, and an optional period), or if there is an underflow. Note that a single dot is currently a valid floating point number, equal to +0, but that is not guaranteed to remain true.

The $\langle significand \rangle$ must be non-empty, so e1 and e-1 are not valid floating point numbers. Note that the latter could be mistaken with the difference of “e” and 1. To avoid confusions, the base of natural logarithms cannot be input as e and should be input as exp(1) or \c_e_fp.

Special numbers are input as follows:

- inf represents $+\infty$, and can be preceded by any $\langle sign \rangle$, yielding $\pm \infty$ as appropriate.
- nan represents a (quiet) non-number. It can be preceded by any sign, but that sign is ignored.
- Any unrecognizable string triggers an error, and produces a NaN.

9.2 Precedence of operators

We list here all the operations supported in floating point expressions, in order of decreasing precedence: operations listed earlier bind more tightly than operations listed below them.

- Function calls (sin, ln, etc).

- Binary `**` and `^` (right associative).
- Unary `+`, `-`, `!`.
- Binary `*`, `/`, and implicit multiplication by juxtaposition (`2pi`, `3(4+5)`, *etc.*).
- Binary `+` and `-`.
- Comparisons `>=`, `!=`, `<?`, *etc.*
- Logical `and`, denoted by `&&`.
- Logical `or`, denoted by `||`.
- Ternary operator `?:` (right associative).

The precedence of operations can be overridden using parentheses. In particular, those precedences imply that

$$\begin{aligned}\sin 2\pi &= \sin(2\pi) = 0, \\ 2^{2\max(3,4)} &= 2^{2\max(3,4)} = 256.\end{aligned}$$

Functions are called on the value of their argument, contrarily to \TeX macros.

9.3 Operations

We now present the various operations allowed in floating point expressions, from the lowest precedence to the highest. When used as a truth value, a floating point expression is `false` if it is ± 0 , and `true` otherwise, including when it is `NaN`.

```
?:\fp_eval:n { <operand1> ? <operand2> : <operand3> }
```

The ternary operator `?:` results in `<operand2>` if `<operand1>` is true, and `<operand3>` if it is false (equal to ± 0). All three `<operands>` are evaluated in all cases. The operator is right associative, hence

```
\fp_eval:n
{
  1 + 3 > 4 ? 1 :
  2 + 4 > 5 ? 2 :
  3 + 5 > 6 ? 3 : 4
}
```

first tests whether $1 + 3 > 4$; since this isn't true, the branch following `:` is taken, and $2 + 4 > 5$ is compared; since this is true, the branch before `:` is taken, and everything else is (evaluated then) ignored. That allows testing for various cases in a concise manner, with the drawback that all computations are made in all cases.

```
||\fp_eval:n { <operand1> || <operand2> }
```

If `<operand1>` is true (non-zero), use that value, otherwise the value of `<operand2>`. Both `<operands>` are evaluated in all cases.

<hr/>	<code>\fp_eval:n { <operand1> && <operand2> }</code>	
		If $\langle operand_1 \rangle$ is false (equal to ± 0), use that value, otherwise the value of $\langle operand_2 \rangle$. Both $\langle operands \rangle$ are evaluated in all cases.
<hr/>		
<code><</code>	<code>\fp_eval:n</code>	
<code>=</code>	<code>{</code>	
<code>></code>	<code> <operand1> <relation1></code>	
<code>?</code>	<code> ...</code>	
	<code> <operandN> <relationN></code>	
Updated: 2013-12-14	<code> <operandN+1></code>	
<hr/>	<code>}</code>	
		Each $\langle relation \rangle$ consists of a non-empty string of <code><</code> , <code>=</code> , <code>></code> , and <code>?</code> , optionally preceded by <code>!</code> , and may not start with <code>?</code> . This evaluates to <code>+1</code> if all comparisons $\langle operand_i \rangle \langle relation_j \rangle$ are true, and <code>+0</code> otherwise. All $\langle operands \rangle$ are evaluated in all cases. See <code>\fp_compare:nTF</code> for details.
<hr/>		
<code>+</code>	<code>\fp_eval:n { <operand1> + <operand2> }</code>	
<code>-</code>	<code>\fp_eval:n { <operand1> - <operand2> }</code>	
<hr/>		Computes the sum or the difference of its two $\langle operands \rangle$. The “invalid operation” exception occurs for $\infty - \infty$. “Underflow” and “overflow” occur when appropriate.
<hr/>		
<code>*</code>	<code>\fp_eval:n { <operand1> * <operand2> }</code>	
<code>/</code>	<code>\fp_eval:n { <operand1> / <operand2> }</code>	
<hr/>		Computes the product or the ratio of its two $\langle operands \rangle$. The “invalid operation” exception occurs for ∞/∞ , $0/0$, or $0 * \infty$. “Division by zero” occurs when dividing a finite non-zero number by ± 0 . “Underflow” and “overflow” occur when appropriate.
<hr/>		
<code>+</code>	<code>\fp_eval:n { + <operand> }</code>	
<code>-</code>	<code>\fp_eval:n { - <operand> }</code>	
<code>!</code>	<code>\fp_eval:n { ! <operand> }</code>	
<hr/>		The unary <code>+</code> does nothing, the unary <code>-</code> changes the sign of the $\langle operand \rangle$, and <code>!</code> $\langle operand \rangle$ evaluates to <code>1</code> if $\langle operand \rangle$ is false and <code>0</code> otherwise (this is the <code>not</code> boolean function). Those operations never raise exceptions.
<hr/>		
<code>**</code>	<code>\fp_eval:n { <operand1> ** <operand2> }</code>	
<code>^</code>	<code>\fp_eval:n { <operand1> ^ <operand2> }</code>	
<hr/>		Raises $\langle operand_1 \rangle$ to the power $\langle operand_2 \rangle$. This operation is right associative, hence <code>2 ** 2 ** 3</code> equals $2^{2^3} = 256$. If $\langle operand_1 \rangle$ is negative or -0 then: the result’s sign is <code>+</code> if the $\langle operand_2 \rangle$ is infinite and $(-1)^p$ if the $\langle operand_2 \rangle$ is $p/5^q$ with p, q integers; the result is <code>+0</code> if <code>abs(<operand1>)^<operand2></code> evaluates to zero; in other cases the “invalid operation” exception occurs because the sign cannot be determined. “Division by zero” occurs when raising ± 0 to a finite strictly negative power. “Underflow” and “overflow” occur when appropriate.
<hr/>		
<code>abs</code>	<code>\fp_eval:n { abs(<fpexpr>) }</code>	
<hr/>		Computes the absolute value of the $\langle fpexpr \rangle$. This function does not raise any exception beyond those raised when computing its operand $\langle fpexpr \rangle$. See also <code>\fp_abs:n</code> .

<hr/> exp <hr/>	<code>\fp_eval:n { exp(<fpexpr>) }</code>	Computes the exponential of the $\langle fpexpr \rangle$. “Underflow” and “overflow” occur when appropriate.
<hr/> ln <hr/>	<code>\fp_eval:n { ln(<fpexpr>) }</code>	Computes the natural logarithm of the $\langle fpexpr \rangle$. Negative numbers have no (real) logarithm, hence the “invalid operation” is raised in that case, including for $\ln(-0)$. “Division by zero” occurs when evaluating $\ln(+0) = -\infty$. “Underflow” and “overflow” occur when appropriate.
<hr/> max min <hr/>	<code>\fp_eval:n { max(<fpexpr₁> , <fpexpr₂> , ...) }</code> <code>\fp_eval:n { min(<fpexpr₁> , <fpexpr₂> , ...) }</code>	Evaluates each $\langle fpexpr \rangle$ and computes the largest (smallest) of those. If any of the $\langle fpexpr \rangle$ is a NaN, the result is NaN. Those operations do not raise exceptions.
<hr/> round trunc ceil floor <hr/>	<code>\fp_eval:n { round (<fpexpr>) }</code> <code>\fp_eval:n { round (<fpexpr₁> , <fpexpr₂>) }</code> <code>\fp_eval:n { round (<fpexpr₁> , <fpexpr₂> , <fpexpr₃>) }</code>	Only round accepts a third argument. Evaluates $\langle fpexpr_1 \rangle = x$ and $\langle fpexpr_2 \rangle = n$ and $\langle fpexpr_3 \rangle = t$ then rounds x to n places. If n is an integer, this rounds x to a multiple of 10^{-n} ; if $n = +\infty$, this always yields x ; if $n = -\infty$, this yields one of ± 0 , $\pm\infty$, or NaN; if n is neither $\pm\infty$ nor an integer, then an “invalid operation” exception is raised. When $\langle fpexpr_2 \rangle$ is omitted, $n = 0$, <i>i.e.</i> , $\langle fpexpr_1 \rangle$ is rounded to an integer. The rounding direction depends on the function. <ul style="list-style-type: none"> • round yields the multiple of 10^{-n} closest to x, with ties (x half-way between two such multiples) rounded as follows. If t is nan or not given the even multiple is chosen (“ties to even”), if $t = \pm 0$ the multiple closest to 0 is chosen (“ties to zero”), if t is positive/negative the multiple closest to $\infty/-\infty$ is chosen (“ties towards positive/negative infinity”). • floor yields the largest multiple of 10^{-n} smaller or equal to x (“round towards negative infinity”); • ceil yields the smallest multiple of 10^{-n} greater or equal to x (“round towards positive infinity”); • trunc yields a multiple of 10^{-n} with the same sign as x and with the largest absolute value less than that of x (“round towards zero”). <p>“Overflow” occurs if x is finite and the result is infinite (this can only happen if $\langle fpexpr_2 \rangle < -9984$).</p>
<hr/> sign <hr/>	<code>\fp_eval:n { sign(<fpexpr>) }</code>	Evaluates the $\langle fpexpr \rangle$ and determines its sign: +1 for positive numbers and for $+\infty$, -1 for negative numbers and for $-\infty$, ± 0 for ± 0 , and NaN for NaN. This operation does not raise exceptions.

<code>sin</code>	<code>\fp_eval:n { sin(<fpexpr>) }</code>
<code>cos</code>	<code>\fp_eval:n { cos(<fpexpr>) }</code>
<code>tan</code>	<code>\fp_eval:n { tan(<fpexpr>) }</code>
<code>cot</code>	<code>\fp_eval:n { cot(<fpexpr>) }</code>
<code>csc</code>	<code>\fp_eval:n { csc(<fpexpr>) }</code>
<code>sec</code>	<code>\fp_eval:n { sec(<fpexpr>) }</code>

Updated: 2013-11-17

Computes the sine, cosine, tangent, cotangent, cosecant, or secant of the $\langle fpexpr \rangle$ given in radians. For arguments given in degrees, see `sind`, `cosd`, *etc.* Note that since π is irrational, `sin(8pi)` is not quite zero, while its analogue `sind(8 × 180)` is exactly zero. The trigonometric functions are undefined for an argument of $\pm\infty$, leading to the “invalid operation” exception. Additionally, evaluating tangent, cotangent, cosecant, or secant at one of their poles leads to a “division by zero” exception. “Underflow” and “overflow” occur when appropriate.

<code>sind</code>	<code>\fp_eval:n { sind(<fpexpr>) }</code>
<code>cosd</code>	<code>\fp_eval:n { cosd(<fpexpr>) }</code>
<code>tand</code>	<code>\fp_eval:n { tand(<fpexpr>) }</code>
<code>cotd</code>	<code>\fp_eval:n { cotd(<fpexpr>) }</code>
<code>cscd</code>	<code>\fp_eval:n { cscd(<fpexpr>) }</code>
<code>secd</code>	<code>\fp_eval:n { secd(<fpexpr>) }</code>

New: 2013-11-02

Computes the sine, cosine, tangent, cotangent, cosecant, or secant of the $\langle fpexpr \rangle$ given in degrees. For arguments given in radians, see `sin`, `cos`, *etc.* Note that since π is irrational, `sin(8pi)` is not quite zero, while its analogue `sind(8 × 180)` is exactly zero. The trigonometric functions are undefined for an argument of $\pm\infty$, leading to the “invalid operation” exception. Additionally, evaluating tangent, cotangent, cosecant, or secant at one of their poles leads to a “division by zero” exception. “Underflow” and “overflow” occur when appropriate.

<code>asin</code>	<code>\fp_eval:n { asin(<fpexpr>) }</code>
<code>acos</code>	<code>\fp_eval:n { acos(<fpexpr>) }</code>
<code>acsc</code>	<code>\fp_eval:n { acsc(<fpexpr>) }</code>
<code>asec</code>	<code>\fp_eval:n { asec(<fpexpr>) }</code>

New: 2013-11-02

Computes the arcsine, arccosine, arccosecant, or arcsecant of the $\langle fpexpr \rangle$ and returns the result in radians, in the range $[-\pi/2, \pi/2]$ for `asin` and `acsc` and $[0, \pi]$ for `acos` and `asec`. For a result in degrees, use `asind`, *etc.* If the argument of `asin` or `acos` lies outside the range $[-1, 1]$, or the argument of `acsc` or `asec` inside the range $(-1, 1)$, an “invalid operation” exception is raised. “Underflow” and “overflow” occur when appropriate.

<code>asind</code>	<code>\fp_eval:n { asind(<fpexpr>) }</code>
<code>acosd</code>	<code>\fp_eval:n { acosd(<fpexpr>) }</code>
<code>acscd</code>	<code>\fp_eval:n { acscd(<fpexpr>) }</code>
<code>asecd</code>	<code>\fp_eval:n { asecd(<fpexpr>) }</code>

New: 2013-11-02

Computes the arcsine, arccosine, arccosecant, or arcsecant of the $\langle fpexpr \rangle$ and returns the result in degrees, in the range $[-90, 90]$ for `asin` and `acsc` and $[0, 180]$ for `acos` and `asec`. For a result in radians, use `asin`, *etc.* If the argument of `asin` or `acos` lies outside the range $[-1, 1]$, or the argument of `acsc` or `asec` inside the range $(-1, 1)$, an “invalid operation” exception is raised. “Underflow” and “overflow” occur when appropriate.

atan	<code>\fp_eval:n { atan(<fpexpr>) }</code>
acot	<code>\fp_eval:n { atan(<fpexpr₁> , <fpexpr₂>) }</code>
<hr/>	
New: 2013-11-02	<code>\fp_eval:n { acot(<fpexpr>) }</code>
	<code>\fp_eval:n { acot(<fpexpr₁> , <fpexpr₂>) }</code>

Those functions yield an angle in radians: **atand** and **acotd** are their analogs in degrees. The one-argument versions compute the arctangent or arccotangent of the $\langle fpexpr \rangle$: arctangent takes values in the range $[-\pi/2, \pi/2]$, and arccotangent in the range $[0, \pi]$. The two-argument arctangent computes the angle in polar coordinates of the point with Cartesian coordinates $(\langle fpexpr_2 \rangle, \langle fpexpr_1 \rangle)$: this is the arctangent of $\langle fpexpr_1 \rangle / \langle fpexpr_2 \rangle$, possibly shifted by π depending on the signs of $\langle fpexpr_1 \rangle$ and $\langle fpexpr_2 \rangle$. The two-argument arccotangent computes the angle in polar coordinates of the point $(\langle fpexpr_1 \rangle, \langle fpexpr_2 \rangle)$, equal to the arccotangent of $\langle fpexpr_1 \rangle / \langle fpexpr_2 \rangle$, possibly shifted by π . Both two-argument functions take values in the wider range $[-\pi, \pi]$. The ratio $\langle fpexpr_1 \rangle / \langle fpexpr_2 \rangle$ need not be defined for the two-argument arctangent: when both expressions yield ± 0 , or when both yield $\pm \infty$, the resulting angle is one of $\{\pm\pi/4, \pm 3\pi/4\}$ depending on signs. Only the “underflow” exception can occur.

atand	<code>\fp_eval:n { atand(<fpexpr>) }</code>
acotd	<code>\fp_eval:n { atand(<fpexpr₁> , <fpexpr₂>) }</code>
<hr/>	
New: 2013-11-02	<code>\fp_eval:n { acotd(<fpexpr>) }</code>
	<code>\fp_eval:n { acotd(<fpexpr₁> , <fpexpr₂>) }</code>

Those functions yield an angle in degrees: **atand** and **acotd** are their analogs in radians. The one-argument versions compute the arctangent or arccotangent of the $\langle fpexpr \rangle$: arctangent takes values in the range $[-90, 90]$, and arccotangent in the range $[0, 180]$. The two-argument arctangent computes the angle in polar coordinates of the point with Cartesian coordinates $(\langle fpexpr_2 \rangle, \langle fpexpr_1 \rangle)$: this is the arctangent of $\langle fpexpr_1 \rangle / \langle fpexpr_2 \rangle$, possibly shifted by 180 depending on the signs of $\langle fpexpr_1 \rangle$ and $\langle fpexpr_2 \rangle$. The two-argument arccotangent computes the angle in polar coordinates of the point $(\langle fpexpr_1 \rangle, \langle fpexpr_2 \rangle)$, equal to the arccotangent of $\langle fpexpr_1 \rangle / \langle fpexpr_2 \rangle$, possibly shifted by 180. Both two-argument functions take values in the wider range $[-180, 180]$. The ratio $\langle fpexpr_1 \rangle / \langle fpexpr_2 \rangle$ need not be defined for the two-argument arctangent: when both expressions yield ± 0 , or when both yield $\pm \infty$, the resulting angle is one of $\{\pm 45, \pm 135\}$ depending on signs. Only the “underflow” exception can occur.

sqrt	<code>\fp_eval:n { sqrt(<fpexpr>) }</code>
-------------	--

New: 2013-12-14 Computes the square root of the $\langle fpexpr \rangle$. The “invalid operation” is raised when the $\langle fpexpr \rangle$ is negative; no other exception can occur. Special values yield $\sqrt{-0} = -0$, $\sqrt{+0} = +0$, $\sqrt{+\infty} = +\infty$ and $\sqrt{\text{NaN}} = \text{NaN}$.

<hr/> rand <hr/>	<code>\fp_eval:n { rand() }</code>
<hr/> <small>New: 2016-12-05</small> <hr/>	Produces a pseudo-random floating-point number (multiple of 10^{-16}) between 0 included and 1 excluded. Available in pdfTeX and LuaTeX engines only.
<p>TeXhackers note: This is based on pseudo-random numbers provided by the engine's primitive <code>\pdfuniformdeviate</code> in pdfTeX and <code>\uniformdeviate</code> in LuaTeX. The underlying code in pdfTeX and LuaTeX is based on Metapost, which follows an additive scheme recommended in Section 3.6 of “The Art of Computer Programming, Volume 2”.</p> <p>While we are more careful than <code>\uniformdeviate</code> to preserve uniformity of the underlying stream of 28-bit pseudo-random integers, these pseudo-random numbers should of course not be relied upon for serious numerical computations nor cryptography.</p> <p>The random seed can be queried using <code>\pdfrandomseed</code> and set using <code>\pdfsetrandomseed</code> (in LuaTeX <code>\randomseed</code> and <code>\setrandomseed</code>). While a 32-bit (signed) integer can be given as a seed, only the absolute value is used and any number beyond 2^{28} is divided by an appropriate power of 2. We recommend using an integer in $[0, 2^{28} - 1]$.</p>	
<hr/> randint <hr/>	<code>\fp_eval:n { randint(<fpexpr>) }</code>
<hr/> <small>New: 2016-12-05</small> <hr/>	<code>\fp_eval:n { randint(<fpexpr₁₂</code>
	Produces a pseudo-random integer between 1 and <code><fpexpr></code> or between <code><fpexpr_{1 and <code><fpexpr_{2 inclusive. The bounds must be integers in the range $(-10^{16}, 10^{16})$ and the first must be smaller or equal to the second. See rand for important comments on how these pseudo-random numbers are generated.}</code>}</code>
<hr/> inf <hr/>	The special values $+\infty$, $-\infty$, and NaN are represented as <code>inf</code> , <code>-inf</code> and <code>nan</code> (see <code>\c_inf_fp</code> , <code>\c_minus_inf_fp</code> and <code>\c_nan_fp</code>).
<hr/> nan <hr/>	
<hr/> pi <hr/>	The value of π (see <code>\c_pi_fp</code>).
<hr/> deg <hr/>	The value of 1° in radians (see <code>\c_one_degree_fp</code>).

<hr/>	Those units of measurement are equal to their values in pt, namely
<code>em</code>	
<code>ex</code>	
<code>in</code>	$1\text{in} = 72.27\text{pt}$
<code>pt</code>	$1\text{pt} = 1\text{pt}$
<code>pc</code>	
<code>cm</code>	$1\text{pc} = 12\text{pt}$
<code>mm</code>	
<code>dd</code>	$1\text{cm} = \frac{1}{2.54}\text{in} = 28.45275590551181\text{pt}$
<code>cc</code>	
<code>nd</code>	$1\text{mm} = \frac{1}{25.4}\text{in} = 2.845275590551181\text{pt}$
<code>nc</code>	
<code>bp</code>	$1\text{dd} = 0.376065\text{mm} = 1.07000856496063\text{pt}$
<code>sp</code>	
	$1\text{cc} = 12\text{dd} = 12.84010277952756\text{pt}$
	$1\text{nd} = 0.375\text{mm} = 1.066978346456693\text{pt}$
	$1\text{nc} = 12\text{nd} = 12.80374015748031\text{pt}$
	$1\text{bp} = \frac{1}{72}\text{in} = 1.00375\text{pt}$
	$1\text{sp} = 2^{-16}\text{pt} = 1.52587890625e - 5\text{pt}.$

The values of the (font-dependent) units `em` and `ex` are gathered from T_EX when the surrounding floating point expression is evaluated.

<hr/>	
<code>true</code>	Other names for 1 and +0.
<code>false</code>	
<hr/>	

<hr/>	
<code>\fp_abs:n</code> ★	<code>\fp_abs:n {⟨floating point expression⟩}</code>
New: 2012-05-14	Evaluates the <i>⟨floating point expression⟩</i> as described for <code>\fp_eval:n</code> and leaves the absolute value of the result in the input stream. This function does not raise any exception beyond those raised when evaluating its argument. Within floating point expressions, <code>abs()</code> can be used.
Updated: 2012-07-08	
<hr/>	
<code>\fp_max:nn</code> ★	<code>\fp_max:nn {⟨fp expression 1⟩} {⟨fp expression 2⟩}</code>
<code>\fp_min:nn</code> ★	Evaluates the <i>⟨floating point expressions⟩</i> as described for <code>\fp_eval:n</code> and leaves the resulting larger (<code>max</code>) or smaller (<code>min</code>) value in the input stream. This function does not raise any exception beyond those raised when evaluating its argument. Within floating point expressions, <code>max()</code> and <code>min()</code> can be used.
New: 2012-09-26	
<hr/>	

10 Disclaimer and roadmap

The package may break down if the escape character is among 0123456789_+, or if it receives a T_EX primitive conditional affected by `\exp_not:N`.

The following need to be done. I'll try to time-order the items.

- Decide what exponent range to consider.
- Support signalling `nan`.

- Modulo and remainder, and rounding functions `quantize`, `quantize0`, `quantize+`, `quantize-`, `quantize=`, `round=`. Should the modulo also be provided as (catcode 12) `%`?
- `\fp_format:nn` $\{\langle fpexpr \rangle\}$ $\{\langle format \rangle\}$, but what should $\langle format \rangle$ be? More general pretty printing?
- Add `and`, `or`, `xor`? Perhaps under the names `all`, `any`, and `xor`?
- Add `log(x,b)` for logarithm of x in base b .
- `hypot` (Euclidean length). Cartesian-to-polar transform.
- Hyperbolic functions `cosh`, `sinh`, `tanh`.
- Inverse hyperbolics.
- Base conversion, input such as `0xAB.CDEF`.
- Factorial (not with `!`), gamma function.
- Improve coefficients of the `sin` and `tan` series.
- Treat upper and lower case letters identically in identifiers, and ignore underscores.
- Add an `array(1,2,3)` and `i=complex(0,1)`.
- Provide an experimental `map` function? Perhaps easier to implement if it is a single character, `@sin(1,2)`?
- Provide `\fp_if_nan:nTF`, and an `isnan` function?
- Support keyword arguments?

`Pgfmath` also provides box-measurements (depth, height, width), but boxes are not possible expandably.

Bugs.

- Check that functions are monotonic when they should.
- Add exceptions to `?:`, `!<=>?`, `&&`, `||`, and `!`.
- Logarithms of numbers very close to 1 are inaccurate.
- When rounding towards $-\infty$, `\dim_to_fp:n` $\{0pt\}$ should return -0 , not $+0$.
- The result of $(\pm 0) + (\pm 0)$, of $x + (-x)$, and of $(-x) + x$ should depend on the rounding mode.
- `0e9999999999` gives a T_EX “number too large” error.
- Subnormals are not implemented.

Possible optimizations/improvements.

- Document that `l3trial/l3fp-types` introduces tools for adding new types.
- In subsection 9.1, write a grammar.

- It would be nice if the `parse` auxiliaries for each operation were set up in the corresponding module, rather than centralizing in `l3fp-parse`.
- Some functions should get an `_o` ending to indicate that they expand after their result.
- More care should be given to distinguish expandable/restricted expandable (auxiliary and internal) functions.
- The code for the `ternary` set of functions is ugly.
- There are many `~` missing in the doc to avoid bad line-breaks.
- The algorithm for computing the logarithm of the significand could be made to use a 5 terms Taylor series instead of 10 terms by taking $c = 2000/([200x]+1) \in [10, 95]$ instead of $c \in [1, 10]$. Also, it would then be possible to simplify the computation of t . However, we would then have to hard-code the logarithms of 44 small integers instead of 9.
- Improve notations in the explanations of the division algorithm (`l3fp-basics`).
- Understand and document `_fp_basics_pack_weird_low:NNNNw` and `_fp_basics_pack_weird_high:NNNNNNNNw` better. Move the other `basics_pack` auxiliaries to `l3fp-aux` under a better name.
- Find out if underflow can really occur for trigonometric functions, and redoc as appropriate.
- Add bibliography. Some of Kahan’s articles, some previous T_EX fp packages, the international standards,...
- Also take into account the “inexact” exception?
- Support multi-character prefix operators (*e.g.*, `@/` or whatever)?

Part XXII

The l3sort package

Sorting functions

1 Controlling sorting

L^AT_EX3 comes with a facility to sort list variables (sequences, token lists, or comma-lists) according to some user-defined comparison. For instance,

```
\clist_set:Nn \l_foo_clist { 3 , 01 , -2 , 5 , +1 }
\clist_sort:Nn \l_foo_clist
{
  \int_compare:nNnTF { #1 } > { #2 }
  { \sort_return_swapped: }
  { \sort_return_same: }
}
```

results in `\l_foo_clist` holding the values `{ -2 , 01 , +1 , 3 , 5 }` sorted in non-decreasing order.

The code defining the comparison should call `\sort_return_swapped:` if the two items given as `#1` and `#2` are not in the correct order, and otherwise it should call `\sort_return_same:` to indicate that the order of this pair of items should not be changed.

For instance, a *comparison code* consisting only of `\sort_return_same:` with no test yields a trivial sort: the final order is identical to the original order. Conversely, using a *comparison code* consisting only of `\sort_return_swapped:` reverses the list (in a fairly inefficient way).

T_EXhackers note: The current implementation is limited to sorting approximately 20000 items (40000 in LuaT_EX), depending on what other packages are loaded.

Internally, the code from `l3sort` stores items in `\toks` registers allocated locally. Thus, the *comparison code* should not call `\newtoks` or other commands that allocate new `\toks` registers. On the other hand, altering the value of a previously allocated `\toks` register is not a problem.

Part XXIII

The `l3tl-build` package: building token lists

1 `l3tl-build` documentation

This module provides no user function: it is meant for kernel use only.

There are two main ways of building token lists from individual tokens. Either in one go within an `x`-expanding assignment, or by repeatedly using `\tl_put_right:Nn`. The first method takes a linear time, but only allows expandable operations. The second method takes a time quadratic in the length of the token list, but allows expandable and non-expandable operations.

The goal of this module is to provide functions to build a token list piece by piece in linear time, while allowing non-expandable operations. This is achieved by abusing `\toks`: adding some tokens to the token list is done by storing them in a free token register (time $O(1)$ for each such operation). Those token registers are only put together at the end, within an `x`-expanding assignment, which takes a linear time.⁵ Of course, all this must be done in a group: we can't go and clobber the values of legitimate `\toks` used by L^AT_EX 2_ε.

Since none of the current applications need the ability to insert material on the left of the token list, I have not implemented that. This could be done for instance by using odd-numbered `\toks` for the left part, and even-numbered `\toks` for the right part.

1.1 Internal functions

<code>__tl_build:Nw</code>
<code>__tl_gbuild:Nw</code>
<code>__tl_build_x:Nw</code>
<code>__tl_gbuild_x:Nw</code>

<code>__tl_build:Nw</code>	<code>__tl_build:Nw <tl var> ...</code>
<code>__tl_gbuild:Nw</code>	<code>__tl_build_one:n {\tokens₁} ...</code>
<code>__tl_build_x:Nw</code>	<code>__tl_build_one:n {\tokens₂} ...</code>
<code>__tl_gbuild_x:Nw</code>	<code>...</code>
	<code>__tl_build_end:</code>

Defines the `<tl var>` to contain the contents of `<tokens1>` followed by `<tokens2>`, *etc.* This is built in such a way to be more efficient than repeatedly using `\tl_put_right:Nn`. The code in “...” does not need to be expandable. The commands `__tl_build:Nw` and `__tl_build_end:` start and end a group. The assignment to the `<tl var>` occurs just after the end of that group, using `\tl_set:Nn`, `\tl_gset:Nn`, `\tl_set:Nx`, or `\tl_gset:Nx`.

<code>__tl_build_one:n</code>
<code>__tl_build_one:(o x)</code>

<code>__tl_build_one:n</code>	<code>__tl_build_one:n {\tokens}</code>
--------------------------------	--

This function may only be used within the scope of a `__tl_build:Nw` function. It adds the `<tokens>` on the right of the current token list.

<code>__tl_build_end:</code>

Ends the scope started by `__tl_build:Nw`, and performs the relevant assignment.

⁵If we run out of token registers, then the currently filled-up `\toks` are put together in a temporary token list, and cleared, and we ultimately use `\tl_put_right:Nx` to put those chunks together. Hence the true asymptotic is quadratic, with a very small constant.

Part XXIV

The l3tl-analysis package: analysing token lists

1 l3tl-analysis documentation

This module mostly provides internal functions for use in the l3regex module. However, it provides as a side-effect a user debugging function, very similar to the \ShowTokens macro from the ted package.

\tl_show_analysis:N
\tl_show_analysis:n

New: 2017-05-26

\tl_show_analysis:n {<token list>}

Displays to the terminal the detailed decomposition of the <token list> into tokens, showing the category code of each character token, the meaning of control sequences and active characters, and the value of registers.

Part XXV

The `l3regex` package: regular expressions in `TEX`

1 Regular expressions

The `l3regex` package provides regular expression testing, extraction of submatches, splitting, and replacement, all acting on token lists. The syntax of regular expressions is mostly a subset of the PCRE syntax (and very close to POSIX), with some additions due to the fact that `TEX` manipulates tokens rather than characters. For performance reasons, only a limited set of features are implemented. Notably, back-references are not supported.

Let us give a few examples. After

```
\tl_set:Nn \l_my_tl { That~cat. }
\regex_replace_once:nnN { at } { is } \l_my_tl
```

the token list variable `\l_my_tl` holds the text “`This cat.`”, where the first occurrence of “`at`” was replaced by “`is`”. A more complicated example is a pattern to emphasize each word and add a comma after it:

```
\regex_replace_all:nnN { \w+ } { \c{emph}\cB\{ \0 \cE\} , } \l_my_tl
```

The `\w` sequence represents any “word” character, and `+` indicates that the `\w` sequence should be repeated as many times as possible (at least once), hence matching a word in the input token list. In the replacement text, `\0` denotes the full match (here, a word). The command `\emph` is inserted using `\c{emph}`, and its argument `\0` is put between braces `\cB\{` and `\cE\}`.

If a regular expression is to be used several times, it can be compiled once, and stored in a regex variable using `\regex_const:Nn`. For example,

```
\regex_const:Nn \c_foo_regex { \c{begin} \cB. (\c[~BE].*) \cE. }
```

stores in `\c_foo_regex` a regular expression which matches the starting marker for an environment: `\begin`, followed by a begin-group token (`\cB.`), then any number of tokens which are neither begin-group nor end-group character tokens (`\c[~BE].*`), ending with an end-group token (`\cE.`). As explained in the next section, the parentheses “capture” the result of `\c[~BE].*`, giving us access to the name of the environment when doing replacements.

1.1 Syntax of regular expressions

We start with a few examples, and encourage the reader to apply `\regex_show:n` to these regular expressions.

- `Cat` matches the word “Cat” capitalized in this way, but also matches the beginning of the word “Cattle”: use `\bCat\b` to match a complete word only.
- `[abc]` matches one letter among “a”, “b”, “c”; the pattern `(a|b|c)` matches the same three possible letters (but see the discussion of submatches below).

- `[A-Za-z]*` matches any number (due to the quantifier `*`) of Latin letters (not accented).
- `\c{[A-Za-z]*}` matches a control sequence made of Latin letters.
- `_[^_]*_` matches an underscore, any number of characters other than underscore, and another underscore; it is equivalent to `_.*?_` where `.` matches arbitrary characters and the lazy quantifier `*?` means to match as few characters as possible, thus avoiding matching underscores.
- `[+-]?\d+` matches an explicit integer with at most one sign.
- `[+-_]*\d+_*` matches an explicit integer with any number of `+` and `-` signs, with spaces allowed except within the mantissa, and surrounded by spaces.
- `[+-_]*(\d+|\\d*\\.\\d+)_*` matches an explicit integer or decimal number; using `[.,]` instead of `\\.` would allow the comma as a decimal marker.
- `[+-_]*(\d+|\\d*\\.\\d+)_*((?i)pt|in|[cem]m|ex|[bs]p|[dn]d|[pcn]c)_*` matches an explicit dimension with any unit that `TEX` knows, where `(?i)` means to treat lowercase and uppercase letters identically.
- `[+-_]*((?i)nan|inf|(\d+|\\d*\\.\\d+)(_e[+-_]*\\d+)?)_*` matches an explicit floating point number or the special values `nan` and `inf` (with signs).
- `[+-_]*(\d+|\\cC.)_*` matches an explicit integer or control sequence (without checking whether it is an integer variable).
- `\G.*?\K` at the beginning of a regular expression matches and discards (due to `\K`) everything between the end of the previous match (`\G`) and what is matched by the rest of the regular expression; this is useful in `\regex_replace_all:nnN` when the goal is to extract matches or submatches in a finer way than with `\regex_extract_all:nnN`.

While it is impossible for a regular expression to match only integer expressions, `[+-\\(\)*\d+\\]*([+ -*/] [+ -\\(\)*\d+\\])*` matches among other things all valid integer expressions (made only with explicit integers). One should follow it with further testing.

Most characters match exactly themselves, with an arbitrary category code. Some characters are special and must be escaped with a backslash (*e.g.*, `*` matches a star character). Some escape sequences of the form backslash-letter also have a special meaning (for instance `\d` matches any digit). As a rule,

- every alphanumeric character (`A-Z`, `a-z`, `0-9`) matches exactly itself, and should not be escaped, because `\A`, `\B`, ... have special meanings;
- non-alphanumeric printable ascii characters can (and should) always be escaped: many of them have special meanings (*e.g.*, use `\(`, `\)`, `\?`, `\.`);
- spaces should always be escaped (even in character classes);
- any other character may be escaped or not, without any effect: both versions match exactly that character.

Note that these rules play nicely with the fact that many non-alphanumeric characters are difficult to input into T_EX under normal category codes. For instance, `\abc%` matches the characters `\abc%` (with arbitrary category codes), but does not match the control sequence `\abc` followed by a percent character. Matching control sequences can be done using the `\c{<regex>}` syntax (see below).

Any special character which appears at a place where its special behaviour cannot apply matches itself instead (for instance, a quantifier appearing at the beginning of a string), after raising a warning.

Characters.

`\x{hh...}` Character with hex code `hh...`

`\xhh` Character with hex code `hh`.

`\a` Alarm (hex 07).

`\e` Escape (hex 1B).

`\f` Form-feed (hex 0C).

`\n` New line (hex 0A).

`\r` Carriage return (hex 0D).

`\t` Horizontal tab (hex 09).

Character types.

`.` A single period matches any token.

`\d` Any decimal digit.

`\h` Any horizontal space character, equivalent to `[\ \^^I]`: space and tab.

`\s` Any space character, equivalent to `[\ \^^I\^^J\^^L\^^M]`.

`\v` Any vertical space character, equivalent to `[\^^J\^^K\^^L\^^M]`. Note that `\^^K` is a vertical space, but not a space, for compatibility with Perl.

`\w` Any word character, *i.e.*, alpha- numerics and underscore, equivalent to `[A-Za-z0-9_]`.

`\D` Any token not matched by `\d`.

`\H` Any token not matched by `\h`.

`\N` Any token other than the `\n` character (hex 0A).

`\S` Any token not matched by `\s`.

`\V` Any token not matched by `\v`.

`\W` Any token not matched by `\w`.

Of those, `.`, `\D`, `\H`, `\N`, `\S`, `\V`, and `\W` match arbitrary control sequences.

Character classes match exactly one token in the subject.

`[...]` Positive character class. Matches any of the specified tokens.

[**^...**] Negative character class. Matches any token other than the specified characters.

x-y Within a character class, this denotes a range (can be used with escaped characters).

[:**<name>**:] Within a character class (one more set of brackets), this denotes the POSIX character class **<name>**, which can be **alnum**, **alpha**, **ascii**, **blank**, **cntrl**, **digit**, **graph**, **lower**, **print**, **punct**, **space**, **upper**, **word**, or **xdigit**.

[:**~<name>**:] Negative POSIX character class.

For instance, [**a-oq-z\cC.**] matches any lowercase latin letter except **p**, as well as control sequences (see below for a description of **\c**).

Quantifiers (repetition).

? 0 or 1, greedy.

?? 0 or 1, lazy.

***** 0 or more, greedy.

***?** 0 or more, lazy.

+ 1 or more, greedy.

+? 1 or more, lazy.

{n} Exactly *n*.

{n,} *n* or more, greedy.

{n,}? *n* or more, lazy.

{n,m} At least *n*, no more than *m*, greedy.

{n,m}? At least *n*, no more than *m*, lazy.

Anchors and simple assertions.

\b Word boundary: either the previous token is matched by **\w** and the next by **\W**, or the opposite. For this purpose, the ends of the token list are considered as **\W**.

\B Not a word boundary: between two **\w** tokens or two **\W** tokens (including the boundary).

^ or **\A** Start of the subject token list.

\$, **\Z** or **\z** End of the subject token list.

\G Start of the current match. This is only different from **^** in the case of multiple matches: for instance **\regex_count:nnN { \G a } { aaba } \l_tmpa_int** yields 2, but replacing **\G** by **^** would result in **\l_tmpa_int** holding the value 1.

Alternation and capturing groups.

A|B|C Either one of **A**, **B**, or **C**.

(...) Capturing group.

(?:...) Non-capturing group.

(?<|...)) Non-capturing group which resets the group number for capturing groups in each alternative. The following group is numbered with the first unused group number.

The `\c` escape sequence allows to test the category code of tokens, and match control sequences. Each character category is represented by a single uppercase letter:

- C for control sequences;
- B for begin-group tokens;
- E for end-group tokens;
- M for math shift;
- T for alignment tab tokens;
- P for macro parameter tokens;
- U for superscript tokens (up);
- D for subscript tokens (down);
- S for spaces;
- L for letters;
- O for others; and
- A for active characters.

The `\c` escape sequence is used as follows.

`\c{<regex>}` A control sequence whose *cname* matches the *<regex>*, anchored at the beginning and end, so that `\c{begin}` matches exactly `\begin`, and nothing else.

`\cX` Applies to the next object, which can be a character, character property, class, or group, and forces this object to only match tokens with category **X** (any of CBEMTPUDSLOA). For instance, `\cL[A-Z\d]` matches uppercase letters and digits of category code letter, `\cC.` matches any control sequence, and `\cO(abc)` matches `abc` where each character has category other.

`\c[XYZ]` Applies to the next object, and forces it to only match tokens with category **X**, **Y**, or **Z** (each being any of CBEMTPUDSLOA). For instance, `\c[LSO](..)` matches two tokens of category letter, space, or other.

`\c[^XYZ]` Applies to the next object and prevents it from matching any token with category **X**, **Y**, or **Z** (each being any of CBEMTPUDSLOA). For instance, `\c[^O]\d` matches digits which have any category different from other.

The category code tests can be used inside classes; for instance, `[\cO\d \c[LO][A-F]]` matches what \TeX considers as hexadecimal digits, namely digits with category other, or uppercase letters from **A** to **F** with category either letter or other. Within a group affected by a category code test, the outer test can be overridden by a nested test: for instance, `\cL(ab\cO*cd)` matches `ab*cd` where all characters are of category letter, except `*` which has category other.

The `\u` escape sequence allows to insert the contents of a token list directly into a regular expression or a replacement, avoiding the need to escape special characters.

Namely, `\u{<tl var name>}` matches the exact contents of the token list `<tl var>`. Within a `\c{...}` control sequence matching, the `\u` escape sequence only expands its argument once, in effect performing `\tl_to_str:v`. Quantifiers are not supported directly: use a group.

The option `(?i)` makes the match case insensitive (identifying A–Z with a–z; no Unicode support yet). This applies until the end of the group in which it appears, and can be reverted using `(?-i)`. For instance, in `(?i)(a(?-i)b|c)d`, the letters `a` and `d` are affected by the `i` option. Characters within ranges and classes are affected individually: `(?i)[Y-\]` is equivalent to `[YZ\[\]yz]`, and `(?i)[^aeiou]` matches any character which is not a vowel. Neither character properties, nor `\c{...}` nor `\u{...}` are affected by the `i` option.

In character classes, only `[`, `^`, `-`, `]`, `\` and spaces are special, and should be escaped. Other non-alphanumeric characters can still be escaped without harm. Any escape sequence which matches a single character (`\d`, `\D`, *etc.*) is supported in character classes. If the first character is `^`, then the meaning of the character class is inverted; `^` appearing anywhere else in the range is not special. If the first character (possibly following a leading `^`) is `]` then it does not need to be escaped since ending the range there would make it empty. Ranges of characters can be expressed using `-`, for instance, `[\D 0–5]` and `[^6–9]` are equivalent.

Capturing groups are a means of extracting information about the match. Parenthesized groups are labelled in the order of their opening parenthesis, starting at 1. The contents of those groups corresponding to the “best” match (leftmost longest) can be extracted and stored in a sequence of token lists using for instance `\regex_extract_once:nnTF`.

The `\K` escape sequence resets the beginning of the match to the current position in the token list. This only affects what is reported as the full match. For instance,

```
\regex_extract_all:nnN { a \K . } { a123aaxyz } \l_foo_seq
```

results in `\l_foo_seq` containing the items `{1}` and `{a}`: the true matches are `{a1}` and `{aa}`, but they are trimmed by the use of `\K`. The `\K` command does not affect capturing groups: for instance,

```
\regex_extract_once:nnN { (. \K c)+ \d } { acbc3 } \l_foo_seq
```

results in `\l_foo_seq` containing the items `{c3}` and `{bc}`: the true match is `{acbc3}`, with first submatch `{bc}`, but `\K` resets the beginning of the match to the last position where it appears.

1.2 Syntax of the replacement text

Most of the features described in regular expressions do not make sense within the replacement text. Backslash introduces various special constructions, described further below:

- `\0` is the whole match;
- `\1` is the submatch that was matched by the first (capturing) group `(...)`; similarly for `\2`, ..., `\9` and `\g{<number>}`;
- `_` inserts a space (spaces are ignored when not escaped);

- `\a, \e, \f, \n, \r, \t, \xhh, \x{hhh}` correspond to single characters as in regular expressions;
- `\c{<cs name>}` inserts a control sequence;
- `\c{<category>}<character>` (see below);
- `\u{<tl var name>}` inserts the contents of the `<tl var>` (see below).

Characters other than backslash and space are simply inserted in the result (but since the replacement text is first converted to a string, one should also escape characters that are special for T_EX, for instance use `\#`). Non-alphanumeric characters can always be safely escaped with a backslash.

For instance,

```
\tl_set:Nn \l_my_tl { Hello,~world! }
\regex_replace_all:nnN { ([er]?l|o) . } { (\0--\1) } \l_my_tl
```

results in `\l_my_tl` holding `H(e1l--e1)(o,--o) w(or--o)(ld--l)!`

The submatches are numbered according to the order in which the opening parenthesis of capturing groups appear in the regular expression to match. The n -th submatch is empty if there are fewer than n capturing groups or for capturing groups that appear in alternatives that were not used for the match. In case a capturing group matches several times during a match (due to quantifiers) only the last match is used in the replacement text. Submatches always keep the same category codes as in the original token list.

The characters inserted by the replacement have category code 12 (other) by default, with the exception of space characters. Spaces inserted through `_` have category code 10, while spaces inserted through `\x20` or `\x{20}` have category code 12. The escape sequence `\c` allows to insert characters with arbitrary category codes, as well as control sequences.

`\cX(...)` Produces the characters “...” with category `X`, which must be one of `CBEMTPUDSLOA` as in regular expressions. Parentheses are optional for a single character (which can be an escape sequence). When nested, the innermost category code applies, for instance `\cL(Hello\cS\ world)!` gives this text with standard category codes.

`\c{<text>}` Produces the control sequence with csname `<text>`. The `<text>` may contain references to the submatches `\0`, `\1`, and so on, as in the example for `\u` below.

The escape sequence `\u{<tl var name>}` allows to insert the contents of the token list with name `<tl var name>` directly into the replacement, giving an easier control of category codes. When nested in `\c{...}` and `\u{...}` constructions, the `\u` and `\c` escape sequences perform `\tl_to_str:v`, namely extract the value of the control sequence and turn it into a string. Matches can also be used within the arguments of `\c` and `\u`. For instance,

```
\tl_set:Nn \l_my_one_tl { first }
\tl_set:Nn \l_my_two_tl { \emph{second} }
\tl_set:Nn \l_my_tl { one , two , one , one }
\regex_replace_all:nnN { [^,]+ } { \u{1_my_\0_tl} } \l_my_tl
```

results in `\l_my_tl` holding `first,\emph{second},first,first`.

1.3 Pre-compiling regular expressions

If a regular expression is to be used several times, it is better to compile it once rather than doing it each time the regular expression is used. The compiled regular expression is stored in a variable. All of the `l3regex` module's functions can be given their regular expression argument either as an explicit string or as a compiled regular expression.

<code>\regex_new:N</code>	<code>\regex_new:N <regex var></code>
---------------------------	---

New: 2017-05-26

Creates a new *<regex var>* or raises an error if the name is already taken. The declaration is global. The *<regex var>* is initially such that it never matches.

<code>\regex_set:Nn</code>	<code>\regex_set:Nn <regex var> {<regex>}</code>
----------------------------	--

`\regex_gset:Nn`

`\regex_const:Nn`

New: 2017-05-26

Stores a compiled version of the *<regular expression>* in the *<regex var>*. For instance, this function can be used as

```
\regex_new:N \l_my_regex
\regex_set:Nn \l_my_regex { my\ (simple\ )? reg(ex|ular\ expression) }
```

The assignment is local for `\regex_set:Nn` and global for `\regex_gset:Nn`. Use `\regex_const:Nn` for compiled expressions which never change.

<code>\regex_show:n</code>	<code>\regex_show:n {<regex>}</code>
----------------------------	--

`\regex_show:N`

New: 2017-05-26

Shows how `l3regex` interprets the *<regex>*. For instance, `\regex_show:n {\A X|Y}` shows

```
+--branch
  anchor at start (\A)
  char code 88
+--branch
  char code 89
```

indicating that the anchor `\A` only applies to the first branch: the second branch is not anchored to the beginning of the match.

1.4 Matching

All regular expression functions are available in both `:n` and `:N` variants. The former require a “standard” regular expression, while the later require a compiled expression as generated by `\regex_(g)set:Nn`.

<code>\regex_match:nnTF</code>	<code>\regex_match:nnTF {<regex>} {<token list>} {<true code>} {<false code>}</code>
--------------------------------	--

`\regex_match:NnTF`

New: 2017-05-26

Tests whether the *<regular expression>* matches any part of the *<token list>*. For instance,

```
\regex_match:nnTF { b [cde]* } { abecdcdx } { TRUE } { FALSE }
\regex_match:nnTF { [b-dq-w] } { example } { TRUE } { FALSE }
```

leaves `TRUE` then `FALSE` in the input stream.

```
\regex_count:nnN
\regex_count:NnN
```

New: 2017-05-26

```
\regex_count:nnN {<regex>} {<token list>} <int var>
```

Sets *<int var>* within the current T_EX group level equal to the number of times *<regular expression>* appears in *<token list>*. The search starts by finding the left-most longest match, respecting greedy and ungreedy operators. Then the search starts again from the character following the last character of the previous match, until reaching the end of the token list. Infinite loops are prevented in the case where the regular expression can match an empty token list: then we count one match between each pair of characters. For instance,

```
\int_new:N \l_foo_int
\regex_count:nnN { (b+|c) } { abbababcb } \l_foo_int
```

results in `\l_foo_int` taking the value 5.

1.5 Submatch extraction

```
\regex_extract_once:nnNTF
\regex_extract_once:NnNTF
```

New: 2017-05-26

```
\regex_extract_once:nnN {<regex>} {<token list>} <seq var>
\regex_extract_once:nnNTF {<regex>} {<token list>} <seq var> {<true code>} {<false code>}
```

Finds the first match of the *<regular expression>* in the *<token list>*. If it exists, the match is stored as the first item of the *<seq var>*, and further items are the contents of capturing groups, in the order of their opening parenthesis. The *<seq var>* is assigned locally. If there is no match, the *<seq var>* is cleared. The testing versions insert the *<true code>* into the input stream if a match was found, and the *<false code>* otherwise.

For instance, assume that you type

```
\regex_extract_once:nnNTF { \A(La)?TeX(!*)\Z } { LaTeX!!! } \l_foo_seq
{ true } { false }
```

Then the regular expression (anchored at the start with `\A` and at the end with `\Z`) must match the whole token list. The first capturing group, `(La)?`, matches `La`, and the second capturing group, `(!*)`, matches `!!!`. Thus, `\l_foo_seq` contains as a result the items `{LaTeX!!!}`, `{La}`, and `{!!!}`, and the `true` branch is left in the input stream. Note that the n -th item of `\l_foo_seq`, as obtained using `\seq_item:Nn`, correspond to the submatch numbered $(n - 1)$ in functions such as `\regex_replace_once:nnN`.

```
\regex_extract_all:nnNTF
\regex_extract_all:NnNTF
```

New: 2017-05-26

```
\regex_extract_all:nnN {<regex>} {<token list>} <seq var>
\regex_extract_all:nnNTF {<regex>} {<token list>} <seq var> {<true code>} {<false code>}
```

Finds all matches of the *<regular expression>* in the *<token list>*, and stores all the submatch information in a single sequence (concatenating the results of multiple `\regex_extract_once:nnN` calls). The *<seq var>* is assigned locally. If there is no match, the *<seq var>* is cleared. The testing versions insert the *<true code>* into the input stream if a match was found, and the *<false code>* otherwise. For instance, assume that you type

```
\regex_extract_all:nnNTF { \w+ } { Hello,~world! } \l_foo_seq
{ true } { false }
```

Then the regular expression matches twice, the resulting sequence contains the two items `{Hello}` and `{world}`, and the `true` branch is left in the input stream.

```
\regex_split:nnNTF
\regex_split:NnNTF
```

New: 2017-05-26

```
\regex_split:nnN {<regular expression>} {<token list>} <seq var>
\regex_split:nnNTF {<regular expression>} {<token list>} <seq var> {<true code>}
{<false code>}
```

Splits the *<token list>* into a sequence of parts, delimited by matches of the *<regular expression>*. If the *<regular expression>* has capturing groups, then the token lists that they match are stored as items of the sequence as well. The assignment to *<seq var>* is local. If no match is found the resulting *<seq var>* has the *<token list>* as its sole item. If the *<regular expression>* matches the empty token list, then the *<token list>* is split into single tokens. The testing versions insert the *<true code>* into the input stream if a match was found, and the *<false code>* otherwise. For example, after

```
\seq_new:N \l_path_seq
\regex_split:nnNTF { / } { the/path/for/this/file.tex } \l_path_seq
{ true } { false }
```

the sequence `\l_path_seq` contains the items `{the}`, `{path}`, `{for}`, `{this}`, and `{file.tex}`, and the `true` branch is left in the input stream.

1.6 Replacement

```
\regex_replace_once:nnNTF
\regex_replace_once:NnNTF
```

New: 2017-05-26

```
\regex_replace_once:nnN {<regular expression>} {<replacement>} <tl var>
\regex_replace_once:nnNTF {<regular expression>} {<replacement>} <tl var> {<true
code>} {<false code>}
```

Searches for the *<regular expression>* in the *<token list>* and replaces the first match with the *<replacement>*. The result is assigned locally to *<tl var>*. In the *<replacement>*, `\0` represents the full match, `\1` represent the contents of the first capturing group, `\2` of the second, *etc.*

```
\regex_replace_all:nnNTF
\regex_replace_all:NnNTF
```

New: 2017-05-26

```
\regex_replace_all:nnN {<regular expression>} {<replacement>} <tl var>
\regex_replace_all:nnNTF {<regular expression>} {<replacement>} <tl var> {<true
code>} {<false code>}
```

Replaces all occurrences of the *\regular expression* in the *<token list>* by the *<replacement>*, where `\0` represents the full match, `\1` represent the contents of the first capturing group, `\2` of the second, *etc.* Every match is treated independently, and matches cannot overlap. The result is assigned locally to *<tl var>*.

1.7 Bugs, misfeatures, future work, and other possibilities

The following need to be done now.

- Rewrite the documentation in a more ordered way, perhaps add a BNF?
- Additional error-checking to come.
- Clean up the use of messages.
- Cleaner error reporting in the replacement phase.
- Add tracing information.
- Detect attempts to use back-references and other non-implemented syntax.

- Test for the maximum register `\c_max_register_int`.
- Find out whether the fact that `\W` and friends match the end-marker leads to bugs. Possibly update `_regex_item_reverse:n`.
- The empty `cs` should be matched by `\c{}`, not by `\c{csname.?endcsname\s?}`.

Code improvements to come.

- Shift arrays so that the useful information starts at position 1.
- Only build `.,` once.
- Use arrays for the left and right state stacks when compiling a regex.
- Should `_regex_action_free_group:n` only be used for greedy `{n,}` quantifier? (I think not.)
- Quantifiers for `\u` and assertions.
- When matching, keep track of an explicit stack of `current_state` and `current_submatches`.
- If possible, when a state is reused by the same thread, kill other subthreads.
- Use an array rather than `\l_regex_balance_tl` to build `_regex_replacement_balance_one_match:n`.
- Reduce the number of epsilon-transitions in alternatives.
- Optimize simple strings: use less states (`abcade` should give two states, for `abc` and `ade`). [Does that really make sense?]
- Optimize groups with no alternative.
- Optimize states with a single `_regex_action_free:n`.
- Optimize the use of `_regex_action_success:` by inserting it in state 2 directly instead of having an extra transition.
- Optimize the use of `\int_step...` functions.
- Groups don't capture within regexes for `csnames`; optimize and document.
- Better “show” for anchors, properties, and catcode tests.
- Does `\K` really need a new state for itself?
- When compiling, use a boolean `in_cs` and less magic numbers.
- Instead of checking whether the character is special or alphanumeric using its character code, check if it is special in regexes with `\cs_if_exist` tests.

The following features are likely to be implemented at some point in the future.

- General look-ahead/behind assertions.
- Regex matching on external files.

- Conditional subpatterns with look ahead/behind: “if what follows is [...], then [...]”.
- `(*..)` and `(?..)` sequences to set some options.
- UTF-8 mode for pdfTeX.
- Newline conventions are not done. In particular, we should have an option for `.` not to match newlines. Also, `\A` should differ from `^`, and `\Z`, `\z` and `$` should differ.
- Unicode properties: `\p{..}` and `\P{..}`; `\X` which should match any “extended” Unicode sequence. This requires to manipulate a lot of data, probably using tree-boxes.
- Provide a syntax such as `\ur{1_my_regex}` to use an already-compiled regex in a more complicated regex. This makes regexes more easily composable.
- Allowing `\u{1_my_tl}` in more places, for instance as the number of repetitions in a quantifier.

The following features of PCRE or Perl may or may not be implemented.

- Callout with `(?C...)` or other syntax: some internal code changes make that possible, and it can be useful for instance in the replacement code to stop a regex replacement when some marker has been found; this raises the question of a potential `\regex_break`: and then of playing well with `\tl_map_break`: called from within the code in a regex. It also raises the question of nested calls to the regex machinery, which is a problem since `\fontdimen` are global.
- Conditional subpatterns (other than with a look-ahead or look-behind condition): this is non-regular, isn’t it?
- Named subpatterns: TeX programmers have lived so far without any need for named macro parameters.

The following features of PCRE or Perl will definitely not be implemented.

- Back-references: non-regular feature, this requires backtracking, which is prohibitively slow.
- Recursion: this is a non-regular feature.
- Atomic grouping, possessive quantifiers: those tools, mostly meant to fix catastrophic backtracking, are unnecessary in a non-backtracking algorithm, and difficult to implement.
- Subroutine calls: this syntactic sugar is difficult to include in a non-backtracking algorithm, in particular because the corresponding group should be treated as atomic.
- Backtracking control verbs: intrinsically tied to backtracking.
- `\ddd`, matching the character with octal code `ddd`: we already have `\x{...}` and the syntax is confusingly close to what we could have used for backreferences (`\1`, `\2`, ...), making it harder to produce useful error message.
- `\cx`, similar to TeX’s own `\^^x`.

- Comments: \TeX already has its own system for comments.
- $\backslash\text{Q}\dots\backslash\text{E}$ escaping: this would require to read the argument verbatim, which is not in the scope of this module.
- $\backslash\text{C}$ single byte in UTF-8 mode: XeTeX and LuaTeX serve us characters directly, and splitting those into bytes is tricky, encoding dependent, and most likely not useful anyways.

Part XXVI

The l3box package

Boxes

There are three kinds of box operations: horizontal mode denoted with prefix `\hbox_`, vertical mode with prefix `\vbox_`, and the generic operations working in both modes with prefix `\box_`.

1 Creating and initialising boxes

<code>\box_new:N</code>	<code>\box_new:N</code> $\langle box \rangle$
<code>\box_new:c</code>	Creates a new $\langle box \rangle$ or raises an error if the name is already taken. The declaration is global. The $\langle box \rangle$ is initially void.

<code>\box_clear:N</code>	<code>\box_clear:N</code> $\langle box \rangle$
<code>\box_clear:c</code>	Clears the content of the $\langle box \rangle$ by setting the box equal to <code>\c_empty_box</code> .
<code>\box_gclear:N</code>	
<code>\box_gclear:c</code>	

<code>\box_clear_new:N</code>	<code>\box_clear_new:N</code> $\langle box \rangle$
<code>\box_clear_new:c</code>	Ensures that the $\langle box \rangle$ exists globally by applying <code>\box_new:N</code> if necessary, then applies <code>\box_(g)clear:N</code> to leave the $\langle box \rangle$ empty.
<code>\box_gclear_new:N</code>	
<code>\box_gclear_new:c</code>	

<code>\box_set_eq:NN</code>	<code>\box_set_eq:NN</code> $\langle box_1 \rangle$ $\langle box_2 \rangle$
<code>\box_set_eq:(cN Nc cc)</code>	Sets the content of $\langle box_1 \rangle$ equal to that of $\langle box_2 \rangle$.
<code>\box_gset_eq:NN</code>	
<code>\box_gset_eq:(cN Nc cc)</code>	

<code>\box_set_eq_clear:NN</code>	<code>\box_set_eq_clear:NN</code> $\langle box_1 \rangle$ $\langle box_2 \rangle$
<code>\box_set_eq_clear:(cN Nc cc)</code>	Sets the content of $\langle box_1 \rangle$ within the current \TeX group equal to that of $\langle box_2 \rangle$, then clears $\langle box_2 \rangle$ globally.

<code>\box_gset_eq_clear:NN</code>	<code>\box_gset_eq_clear:NN</code> $\langle box_1 \rangle$ $\langle box_2 \rangle$
<code>\box_gset_eq_clear:(cN Nc cc)</code>	Sets the content of $\langle box_1 \rangle$ equal to that of $\langle box_2 \rangle$, then clears $\langle box_2 \rangle$. These assignments are global.

<code>\box_if_exist_p:N</code> ★	<code>\box_if_exist_p:N</code> $\langle box \rangle$
<code>\box_if_exist_p:c</code> ★	<code>\box_if_exist:NTF</code> $\langle box \rangle$ $\{\langle true\ code \rangle\}$ $\{\langle false\ code \rangle\}$
<code>\box_if_exist:NTF</code> ★	Tests whether the $\langle box \rangle$ is currently defined. This does not check that the $\langle box \rangle$ really is a box.
<code>\box_if_exist:cTF</code> ★	

New: 2012-03-03

2 Using boxes

`\box_use:N`
`\box_use:c`

`\box_use:N` $\langle box \rangle$

Inserts the current content of the $\langle box \rangle$ onto the current list for typesetting.

T_EXhackers note: This is the T_EX primitive `\copy`.

`\box_use_drop:N`
`\box_use_drop:c`

`\box_use_drop:N` $\langle box \rangle$

Inserts the current content of the $\langle box \rangle$ onto the current list for typesetting. The $\langle box \rangle$ is then cleared at the group level the box was set at, *i.e.* the current content is “dropped” entirely. For example, with

```
\hbox_set:Nn \l_tmpa_box { A }
\group_begin:
  \hbox_set:Nn \l_tmpa_box { B }
  \group_begin:
    \box_use_drop:N \l_tmpa_box
  \group_end:
  \box_show:N \l_tmpa_box
\group_end:
\box_show:N \l_tmpa_box
```

the first use of `\box_show:N` will show an entirely cleared (void) box, and the second will show the letter A in the box.

This function is useful as boxes can contain an open-ended amount of material. As such, they can have a significant memory impact on T_EX. At the same time, it is often the case that once a box has been inserted, it is no longer needed at all. Using `\box_use_drop:N` in these circumstances therefore offers improved memory use and performance. It should therefore be preferred over `\box_use:N` where it is clear that the content is no longer needed in the variable.

T_EXhackers note: This is the T_EX primitive `\box`.

`\box_move_right:nn`
`\box_move_left:nn`

`\box_move_right:nn` $\{\langle dimexpr \rangle\} \{\langle box function \rangle\}$

This function operates in vertical mode, and inserts the material specified by the $\langle box function \rangle$ such that its reference point is displaced horizontally by the given $\langle dimexpr \rangle$ from the reference point for typesetting, to the right or left as appropriate. The $\langle box function \rangle$ should be a box operation such as `\box_use:N` $\langle box \rangle$ or a “raw” box specification such as `\vbox:n` $\{ xyz \}$.

`\box_move_up:nn`
`\box_move_down:nn`

`\box_move_up:nn` $\{\langle dimexpr \rangle\} \{\langle box function \rangle\}$

This function operates in horizontal mode, and inserts the material specified by the $\langle box function \rangle$ such that its reference point is displaced vertically by the given $\langle dimexpr \rangle$ from the reference point for typesetting, up or down as appropriate. The $\langle box function \rangle$ should be a box operation such as `\box_use:N` $\langle box \rangle$ or a “raw” box specification such as `\vbox:n` $\{ xyz \}$.

3 Measuring and setting box dimensions

<code>\box_dp:N</code>	<code>\box_dp:N</code> $\langle box \rangle$
<code>\box_dp:c</code>	Calculates the depth (below the baseline) of the $\langle box \rangle$ in a form suitable for use in a $\langle dimension expression \rangle$.

T_EXhackers note: This is the T_EX primitive `\dp`.

<code>\box_ht:N</code>	<code>\box_ht:N</code> $\langle box \rangle$
<code>\box_ht:c</code>	Calculates the height (above the baseline) of the $\langle box \rangle$ in a form suitable for use in a $\langle dimension expression \rangle$.

T_EXhackers note: This is the T_EX primitive `\ht`.

<code>\box_wd:N</code>	<code>\box_wd:N</code> $\langle box \rangle$
<code>\box_wd:c</code>	Calculates the width of the $\langle box \rangle$ in a form suitable for use in a $\langle dimension expression \rangle$.

T_EXhackers note: This is the T_EX primitive `\wd`.

<code>\box_set_dp:Nn</code>	<code>\box_set_dp:Nn</code> $\langle box \rangle$ $\{\langle dimension expression \rangle\}$
<code>\box_set_dp:cn</code>	Set the depth (below the baseline) of the $\langle box \rangle$ to the value of the $\{\langle dimension expression \rangle\}$. This is a global assignment.
Updated: 2011-10-22	

<code>\box_set_ht:Nn</code>	<code>\box_set_ht:Nn</code> $\langle box \rangle$ $\{\langle dimension expression \rangle\}$
<code>\box_set_ht:cn</code>	Set the height (above the baseline) of the $\langle box \rangle$ to the value of the $\{\langle dimension expression \rangle\}$. This is a global assignment.
Updated: 2011-10-22	

<code>\box_set_wd:Nn</code>	<code>\box_set_wd:Nn</code> $\langle box \rangle$ $\{\langle dimension expression \rangle\}$
<code>\box_set_wd:cn</code>	Set the width of the $\langle box \rangle$ to the value of the $\{\langle dimension expression \rangle\}$. This is a global assignment.
Updated: 2011-10-22	

4 Box conditionals

<code>\box_if_empty_p:N</code> *	<code>\box_if_empty_p:N</code> $\langle box \rangle$
<code>\box_if_empty_p:c</code> *	<code>\box_if_empty:N</code> $\langle box \rangle$ $\{\langle true code \rangle\}$ $\{\langle false code \rangle\}$
<code>\box_if_empty:NTF</code> *	Tests if $\langle box \rangle$ is a empty (equal to <code>\c_empty_box</code>).
<code>\box_if_empty:cTF</code> *	

<code>\box_if_horizontal_p:N</code> *	<code>\box_if_horizontal_p:N</code> $\langle box \rangle$
<code>\box_if_horizontal_p:c</code> *	<code>\box_if_horizontal:N</code> $\langle box \rangle$ $\{\langle true code \rangle\}$ $\{\langle false code \rangle\}$
<code>\box_if_horizontal:NTF</code> *	Tests if $\langle box \rangle$ is a horizontal box.
<code>\box_if_horizontal:cTF</code> *	

<code>\box_if_vertical_p:N</code>	★	<code>\box_if_vertical_p:N</code>	$\langle box \rangle$
<code>\box_if_vertical_p:c</code>	★	<code>\box_if_vertical:NTF</code>	$\langle box \rangle$ $\{\langle true\ code \rangle\}$ $\{\langle false\ code \rangle\}$
<code>\box_if_vertical:NTF</code>	★		Tests if $\langle box \rangle$ is a vertical box.
<code>\box_if_vertical:cTF</code>	★		

5 The last box inserted

<code>\box_set_to_last:N</code>	<code>\box_set_to_last:N</code>	$\langle box \rangle$
<code>\box_set_to_last:c</code>		Sets the $\langle box \rangle$ equal to the last item (box) added to the current partial list, removing the item from the list at the same time. When applied to the main vertical list, the $\langle box \rangle$ is always void as it is not possible to recover the last added item.
<code>\box_gset_to_last:N</code>		
<code>\box_gset_to_last:c</code>		

6 Constant boxes

<code>\c_empty_box</code>	This is a permanently empty box, which is neither set as horizontal nor vertical.
Updated: 2012-11-04	TeXhackers note: At the TeX level this is a void box.

7 Scratch boxes

<code>\l_tmpa_box</code>	Scratch boxes for local assignment. These are never used by the kernel code, and so are safe for use with any L ^A T _E X3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.
<code>\l_tmpb_box</code>	
Updated: 2012-11-04	

<code>\g_tmpa_box</code>	Scratch boxes for global assignment. These are never used by the kernel code, and so are safe for use with any L ^A T _E X3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.
<code>\g_tmpb_box</code>	

8 Viewing box contents

<code>\box_show:N</code>	<code>\box_show:N</code>	$\langle box \rangle$
<code>\box_show:c</code>		Shows full details of the content of the $\langle box \rangle$ in the terminal.
Updated: 2012-05-11		
<code>\box_show:Nnn</code>	<code>\box_show:Nnn</code>	$\langle box \rangle$ $\{\langle intexpr_1 \rangle\}$ $\{\langle intexpr_2 \rangle\}$
<code>\box_show:cnn</code>		Display the contents of $\langle box \rangle$ in the terminal, showing the first $\langle intexpr_1 \rangle$ items of the box, and descending into $\langle intexpr_2 \rangle$ group levels.
New: 2012-05-11		

<code>\box_log:N</code>	<code>\box_log:N</code> $\langle box \rangle$
<code>\box_log:c</code>	Writes full details of the content of the $\langle box \rangle$ to the log.
New: 2012-05-11	

<code>\box_log:Nnn</code>	<code>\box_log:Nnn</code> $\langle box \rangle$ $\{\langle intexpr_1 \rangle\}$ $\{\langle intexpr_2 \rangle\}$
<code>\box_log:cnn</code>	Writes the contents of $\langle box \rangle$ to the log, showing the first $\langle intexpr_1 \rangle$ items of the box, and descending into $\langle intexpr_2 \rangle$ group levels.
New: 2012-05-11	

9 Boxes and color

All L^AT_EX3 boxes are “color safe”: a color set inside the box stops applying after the end of the box has occurred.

10 Horizontal mode boxes

<code>\hbox:n</code>	<code>\hbox:n</code> $\{\langle contents \rangle\}$
Updated: 2017-04-05	Typesets the $\langle contents \rangle$ into a horizontal box of natural width and then includes this box in the current list for typesetting.

<code>\hbox_to_wd:nn</code>	<code>\hbox_to_wd:nn</code> $\{\langle dimexpr \rangle\}$ $\{\langle contents \rangle\}$
Updated: 2017-04-05	Typesets the $\langle contents \rangle$ into a horizontal box of width $\langle dimexpr \rangle$ and then includes this box in the current list for typesetting.

<code>\hbox_to_zero:n</code>	<code>\hbox_to_zero:n</code> $\{\langle contents \rangle\}$
Updated: 2017-04-05	Typesets the $\langle contents \rangle$ into a horizontal box of zero width and then includes this box in the current list for typesetting.

<code>\hbox_set:Nn</code>	<code>\hbox_set:Nn</code> $\langle box \rangle$ $\{\langle contents \rangle\}$
<code>\hbox_set:cn</code>	Typesets the $\langle contents \rangle$ at natural width and then stores the result inside the $\langle box \rangle$.
<code>\hbox_gset:Nn</code>	
<code>\hbox_gset:cn</code>	
Updated: 2017-04-05	

<code>\hbox_set_to_wd:Nnn</code>	<code>\hbox_set_to_wd:Nnn</code> $\langle box \rangle$ $\{\langle dimexpr \rangle\}$ $\{\langle contents \rangle\}$
<code>\hbox_set_to_wd:cnn</code>	Typesets the $\langle contents \rangle$ to the width given by the $\langle dimexpr \rangle$ and then stores the result inside the $\langle box \rangle$.
<code>\hbox_gset_to_wd:Nnn</code>	
<code>\hbox_gset_to_wd:cnn</code>	
Updated: 2017-04-05	

<code>\hbox_overlap_right:n</code>	<code>\hbox_overlap_right:n</code> $\{\langle contents \rangle\}$
Updated: 2017-04-05	Typesets the $\langle contents \rangle$ into a horizontal box of zero width such that material protrudes to the right of the insertion point.

<hr/> <code>\hbox_overlap_left:n</code> <hr/>	<code>\hbox_overlap_left:n {\langle contents \rangle}</code>
Updated: 2017-04-05	Typesets the $\langle contents \rangle$ into a horizontal box of zero width such that material protrudes to the left of the insertion point.
<hr/> <code>\hbox_set:Nw</code> <code>\hbox_set:cw</code> <code>\hbox_set_end:</code> <code>\hbox_gset:Nw</code> <code>\hbox_gset:cw</code> <code>\hbox_gset_end:</code> <hr/>	<code>\hbox_set:Nw \langle box \rangle \langle contents \rangle \hbox_set_end:</code> Typesets the $\langle contents \rangle$ at natural width and then stores the result inside the $\langle box \rangle$. In contrast to <code>\hbox_set:Nn</code> this function does not absorb the argument when finding the $\langle content \rangle$, and so can be used in circumstances where the $\langle content \rangle$ may not be a simple argument.
Updated: 2017-04-05	
<hr/> <code>\hbox_set_to_wd:Nnw</code> <code>\hbox_set_to_wd:cnw</code> <code>\hbox_gset_to_wd:Nnw</code> <code>\hbox_gset_to_wd:cnw</code> <hr/>	<code>\hbox_set_to_wd:Nnw \langle box \rangle {\langle dimexpr \rangle} \langle contents \rangle \hbox_set_end:</code> Typesets the $\langle contents \rangle$ to the width given by the $\langle dimexpr \rangle$ and then stores the result inside the $\langle box \rangle$. In contrast to <code>\hbox_set_to_wd:Nnn</code> this function does not absorb the argument when finding the $\langle content \rangle$, and so can be used in circumstances where the $\langle content \rangle$ may not be a simple argument
New: 2017-06-08	
<hr/> <code>\hbox_unpack:N</code> <code>\hbox_unpack:c</code> <hr/>	<code>\hbox_unpack:N \langle box \rangle</code> Unpacks the content of the horizontal $\langle box \rangle$, retaining any stretching or shrinking applied when the $\langle box \rangle$ was set.
	TeXhackers note: This is the TeX primitive <code>\unhcopy</code> .
<hr/> <code>\hbox_unpack_clear:N</code> <code>\hbox_unpack_clear:c</code> <hr/>	<code>\hbox_unpack_clear:N \langle box \rangle</code> Unpacks the content of the horizontal $\langle box \rangle$, retaining any stretching or shrinking applied when the $\langle box \rangle$ was set. The $\langle box \rangle$ is then cleared globally.
	TeXhackers note: This is the TeX primitive <code>\unhbox</code> .

11 Vertical mode boxes

Vertical boxes inherit their baseline from their contents. The standard case is that the baseline of the box is at the same position as that of the last item added to the box. This means that the box has no depth unless the last item added to it had depth. As a result most vertical boxes have a large height value and small or zero depth. The exception are `_top` boxes, where the reference point is that of the first item added. These tend to have a large depth and small height, although the latter is typically non-zero.

<hr/> <code>\vbox:n</code> <hr/>	<code>\vbox:n {\langle contents \rangle}</code>
Updated: 2017-04-05	Typesets the $\langle contents \rangle$ into a vertical box of natural height and includes this box in the current list for typesetting.
<hr/> <code>\vbox_top:n</code> <hr/>	<code>\vbox_top:n {\langle contents \rangle}</code>
Updated: 2017-04-05	Typesets the $\langle contents \rangle$ into a vertical box of natural height and includes this box in the current list for typesetting. The baseline of the box is equal to that of the <i>first</i> item added to the box.

<code>\vbox_to_ht:nn</code>	<code>\vbox_to_ht:nn {<dimexpr>} {<contents>}</code>
-----------------------------	--

Updated: 2017-04-05	Typesets the $\langle contents \rangle$ into a vertical box of height $\langle dimexpr \rangle$ and then includes this box in the current list for typesetting.
---------------------	---

<code>\vbox_to_zero:n</code>	<code>\vbox_to_zero:n {<contents>}</code>
------------------------------	---

Updated: 2017-04-05	Typesets the $\langle contents \rangle$ into a vertical box of zero height and then includes this box in the current list for typesetting.
---------------------	--

<code>\vbox_set:Nn</code>	<code>\vbox_set:Nn <box> {<contents>}</code>
---------------------------	--

<code>\vbox_set:cn</code> <code>\vbox_gset:Nn</code> <code>\vbox_gset:cn</code>	Typesets the $\langle contents \rangle$ at natural height and then stores the result inside the $\langle box \rangle$.
---	---

Updated: 2017-04-05	
---------------------	--

<code>\vbox_set_top:Nn</code>	<code>\vbox_set_top:Nn <box> {<contents>}</code>
-------------------------------	--

<code>\vbox_set_top:cn</code> <code>\vbox_gset_top:Nn</code> <code>\vbox_gset_top:cn</code>	Typesets the $\langle contents \rangle$ at natural height and then stores the result inside the $\langle box \rangle$. The baseline of the box is equal to that of the <i>first</i> item added to the box.
---	---

Updated: 2017-04-05	
---------------------	--

<code>\vbox_set_to_ht:Nnn</code>	<code>\vbox_set_to_ht:Nnn <box> {<dimexpr>} {<contents>}</code>
----------------------------------	---

<code>\vbox_set_to_ht:cn</code> <code>\vbox_gset_to_ht:Nnn</code> <code>\vbox_gset_to_ht:cn</code>	Typesets the $\langle contents \rangle$ to the height given by the $\langle dimexpr \rangle$ and then stores the result inside the $\langle box \rangle$.
--	--

Updated: 2017-04-05	
---------------------	--

<code>\vbox_set:Nw</code>	<code>\vbox_set:Nw <box> <contents> \vbox_set_end:</code>
---------------------------	---

<code>\vbox_set:cw</code> <code>\vbox_set_end:</code> <code>\vbox_gset:Nw</code> <code>\vbox_gset:cw</code> <code>\vbox_gset_end:</code>	Typesets the $\langle contents \rangle$ at natural height and then stores the result inside the $\langle box \rangle$. In contrast to <code>\vbox_set:Nn</code> this function does not absorb the argument when finding the $\langle content \rangle$, and so can be used in circumstances where the $\langle content \rangle$ may not be a simple argument.
--	--

Updated: 2017-04-05	
---------------------	--

<code>\vbox_set_to_ht:Nnw</code>	<code>\vbox_set_to_wd:Nnw <box> {<dimexpr>} <contents> \vbox_set_end:</code>
----------------------------------	--

<code>\vbox_set_to_ht:cnw</code> <code>\vbox_gset_to_ht:Nnw</code> <code>\vbox_gset_to_ht:cnw</code>	Typesets the $\langle contents \rangle$ to the height given by the $\langle dimexpr \rangle$ and then stores the result inside the $\langle box \rangle$. In contrast to <code>\vbox_set_to_ht:Nnn</code> this function does not absorb the argument when finding the $\langle content \rangle$, and so can be used in circumstances where the $\langle content \rangle$ may not be a simple argument
--	---

New: 2017-06-08	
-----------------	--

<code>\vbox_set_split_to_ht:NNn</code>	<code>\vbox_set_split_to_ht:NNn <box₁₂</code>
--	---

Updated: 2011-10-22	Sets $\langle box_1 \rangle$ to contain material to the height given by the $\langle dimexpr \rangle$ by removing content from the top of $\langle box_2 \rangle$ (which must be a vertical box).
---------------------	---

T_EXhackers note: This is the T_EX primitive `\vsplit`.

<hr/> <code>\vbox_unpack:N</code>	<code>\vbox_unpack:N <box></code>
<hr/> <code>\vbox_unpack:c</code>	Unpacks the content of the vertical <code><box></code> , retaining any stretching or shrinking applied when the <code><box></code> was set.

T_EXhackers note: This is the T_EX primitive `\unvcopy`.

<hr/> <code>\vbox_unpack_clear:N</code>	<code>\vbox_unpack:N <box></code>
<hr/> <code>\vbox_unpack_clear:c</code>	Unpacks the content of the vertical <code><box></code> , retaining any stretching or shrinking applied when the <code><box></code> was set. The <code><box></code> is then cleared globally.

T_EXhackers note: This is the T_EX primitive `\unvbox`.

12 Affine transformations

Affine transformations are changes which (informally) preserve straight lines. Simple translations are affine transformations, but are better handled in T_EX by doing the translation first, then inserting an unmodified box. On the other hand, rotation and resizing of boxed material can best be handled by modifying boxes. These transformations are described here.

<hr/> <code>\box_autosize_to_wd_and_ht:Nnn</code>	<code>\box_autosize_to_wd_and_ht:Nnn <box> {<x-size>} {<y-size>}</code>
<hr/> <code>\box_autosize_to_wd_and_ht:Nnn</code>	

New: 2017-04-04

Resizes the `<box>` to fit within the given `<x-size>` (horizontally) and `<y-size>` (vertically); both of the sizes are dimension expressions. The `<y-size>` is the height only: it does not include any depth. The updated `<box>` is an `hbox`, irrespective of the nature of the `<box>` before the resizing is applied. The final size of the `<box>` is the smaller of `{<x-size>}` and `{<y-size>}`, *i.e.* the result fits within the dimensions specified. Negative sizes cause the material in the `<box>` to be reversed in direction, but the reference point of the `<box>` is unchanged. Thus a negative `<y-size>` results in the `<box>` having a depth dependent on the height of the original and *vice versa*. The resizing applies within the current T_EX group level.

<hr/> <code>\box_autosize_to_wd_and_ht_plus_dp:Nnn</code>	<code>\box_autosize_to_wd_and_ht_plus_dp:Nnn <box> {<x-size>}</code>
<hr/> <code>\box_autosize_to_wd_and_ht_plus_dp:Nnn</code>	<code>{<y-size>}</code>

New: 2017-04-04

Resizes the `<box>` to fit within the given `<x-size>` (horizontally) and `<y-size>` (vertically); both of the sizes are dimension expressions. The `<y-size>` is the total vertical size (height plus depth). The updated `<box>` is an `hbox`, irrespective of the nature of the `<box>` before the resizing is applied. The final size of the `<box>` is the smaller of `{<x-size>}` and `{<y-size>}`, *i.e.* the result fits within the dimensions specified. Negative sizes cause the material in the `<box>` to be reversed in direction, but the reference point of the `<box>` is unchanged. Thus a negative `<y-size>` results in the `<box>` having a depth dependent on the height of the original and *vice versa*. The resizing applies within the current T_EX group level.

`\box_resize_to_ht:Nn` `\box_resize_to_ht:Nn <box> {<y-size>}`

`\box_resize_to_ht:cn`

Resizes the $\langle box \rangle$ to $\langle y-size \rangle$ (vertically), scaling the horizontal size by the same amount; $\langle y-size \rangle$ is a dimension expression. The $\langle y-size \rangle$ is the height only: it does not include any depth. The updated $\langle box \rangle$ is an `hbox`, irrespective of the nature of the $\langle box \rangle$ before the resizing is applied. A negative $\langle y-size \rangle$ causes the material in the $\langle box \rangle$ to be reversed in direction, but the reference point of the $\langle box \rangle$ is unchanged. Thus a negative $\langle y-size \rangle$ results in the $\langle box \rangle$ having a depth dependent on the height of the original and *vice versa*. The resizing applies within the current \TeX group level.

`\box_resize_to_ht_plus_dp:Nn` `\box_resize_to_ht_plus_dp:Nn <box> {<y-size>}`

`\box_resize_to_ht_plus_dp:cn`

Resizes the $\langle box \rangle$ to $\langle y-size \rangle$ (vertically), scaling the horizontal size by the same amount; $\langle y-size \rangle$ is a dimension expression. The $\langle y-size \rangle$ is the total vertical size (height plus depth). The updated $\langle box \rangle$ is an `hbox`, irrespective of the nature of the $\langle box \rangle$ before the resizing is applied. A negative $\langle y-size \rangle$ causes the material in the $\langle box \rangle$ to be reversed in direction, but the reference point of the $\langle box \rangle$ is unchanged. Thus a negative $\langle y-size \rangle$ results in the $\langle box \rangle$ having a depth dependent on the height of the original and *vice versa*. The resizing applies within the current \TeX group level.

`\box_resize_to_wd:Nn` `\box_resize_to_wd:Nn <box> {<x-size>}`

`\box_resize_to_wd:cn`

Resizes the $\langle box \rangle$ to $\langle x-size \rangle$ (horizontally), scaling the vertical size by the same amount; $\langle x-size \rangle$ is a dimension expression. The updated $\langle box \rangle$ is an `hbox`, irrespective of the nature of the $\langle box \rangle$ before the resizing is applied. A negative $\langle x-size \rangle$ causes the material in the $\langle box \rangle$ to be reversed in direction, but the reference point of the $\langle box \rangle$ is unchanged. Thus a negative $\langle x-size \rangle$ results in the $\langle box \rangle$ having a depth dependent on the height of the original and *vice versa*. The resizing applies within the current \TeX group level.

`\box_resize_to_wd_and_ht:Nnn` `\box_resize_to_wd_and_ht:Nnn <box> {<x-size>} {<y-size>}`

`\box_resize_to_wd_and_ht:cnn`

New: 2014-07-03

Resizes the $\langle box \rangle$ to $\langle x-size \rangle$ (horizontally) and $\langle y-size \rangle$ (vertically): both of the sizes are dimension expressions. The $\langle y-size \rangle$ is the height only and does not include any depth. The updated $\langle box \rangle$ is an `hbox`, irrespective of the nature of the $\langle box \rangle$ before the resizing is applied. Negative sizes cause the material in the $\langle box \rangle$ to be reversed in direction, but the reference point of the $\langle box \rangle$ is unchanged. Thus a negative $\langle y-size \rangle$ results in the $\langle box \rangle$ having a depth dependent on the height of the original and *vice versa*. The resizing applies within the current \TeX group level.

<code>\box_resize_to_wd_and_ht_plus_dp:Nnn</code>	<code>\box_resize_to_wd_and_ht_plus_dp:Nnn <box> {(x-size)} {(y-size)}</code>
<code>\box_resize_to_wd_and_ht_plus_dp:cnn</code>	

New: 2017-04-06

Resizes the $\langle box \rangle$ to $\langle x-size \rangle$ (horizontally) and $\langle y-size \rangle$ (vertically): both of the sizes are dimension expressions. The $\langle y-size \rangle$ is the total vertical size (height plus depth). The updated $\langle box \rangle$ is an **hbox**, irrespective of the nature of the $\langle box \rangle$ before the resizing is applied. Negative sizes cause the material in the $\langle box \rangle$ to be reversed in direction, but the reference point of the $\langle box \rangle$ is unchanged. Thus a negative $\langle y-size \rangle$ results in the $\langle box \rangle$ having a depth dependent on the height of the original and *vice versa*. The resizing applies within the current \TeX group level.

<code>\box_rotate:Nn</code>	<code>\box_rotate:Nn <box> {(angle)}</code>
<code>\box_rotate:cn</code>	

Rotates the $\langle box \rangle$ by $\langle angle \rangle$ (in degrees) anti-clockwise about its reference point. The reference point of the updated box is moved horizontally such that it is at the left side of the smallest rectangle enclosing the rotated material. The updated $\langle box \rangle$ is an **hbox**, irrespective of the nature of the $\langle box \rangle$ before the rotation is applied. The rotation applies within the current \TeX group level.

<code>\box_scale:Nnn</code>	<code>\box_scale:Nnn <box> {(x-scale)} {(y-scale)}</code>
<code>\box_scale:cnn</code>	

Scales the $\langle box \rangle$ by factors $\langle x-scale \rangle$ and $\langle y-scale \rangle$ in the horizontal and vertical directions, respectively (both scales are integer expressions). The updated $\langle box \rangle$ is an **hbox**, irrespective of the nature of the $\langle box \rangle$ before the scaling is applied. Negative scalings cause the material in the $\langle box \rangle$ to be reversed in direction, but the reference point of the $\langle box \rangle$ is unchanged. Thus a negative $\langle y-scale \rangle$ results in the $\langle box \rangle$ having a depth dependent on the height of the original and *vice versa*. The resizing applies within the current \TeX group level.

13 Primitive box conditionals

<code>\if_hbox:N</code> ★	<code>\if_hbox:N <box></code> <code> <true code></code> <code>\else:</code> <code> <false code></code> <code>\fi:</code>
---------------------------	--

Tests if $\langle box \rangle$ is a horizontal box.

\TeX hackers note: This is the \TeX primitive `\ifhbox`.

<code>\if_vbox:N</code> ★	<code>\if_vbox:N <box></code> <code> <true code></code> <code>\else:</code> <code> <false code></code> <code>\fi:</code>
---------------------------	--

Tests if $\langle box \rangle$ is a vertical box.

\TeX hackers note: This is the \TeX primitive `\ifvbox`.

`\if_box_empty:N` ★

```
\if_box_empty:N <box>
  <true code>
\else:
  <false code>
\fi:
```

Tests if `<box>` is an empty (void) box.

TeXhackers note: This is the TeX primitive `\ifvoid`.

Part XXVII

The l3coffins package

Coffin code layer

The material in this module provides the low-level support system for coffins. For details about the design concept of a coffin, see the xcoffins module (in the l3experimental bundle).

1 Creating and initialising coffins

<code>\coffin_new:N</code>
<code>\coffin_new:c</code>
New: 2011-08-17

`\coffin_new:N` $\langle coffin \rangle$

Creates a new $\langle coffin \rangle$ or raises an error if the name is already taken. The declaration is global. The $\langle coffin \rangle$ is initially empty.

<code>\coffin_clear:N</code>
<code>\coffin_clear:c</code>
New: 2011-08-17

`\coffin_clear:N` $\langle coffin \rangle$

Clears the content of the $\langle coffin \rangle$ within the current T_EX group level.

<code>\coffin_set_eq:NN</code>
<code>\coffin_set_eq:(Nc cN cc)</code>
New: 2011-08-17

`\coffin_set_eq:NN` $\langle coffin_1 \rangle$ $\langle coffin_2 \rangle$

Sets both the content and poles of $\langle coffin_1 \rangle$ equal to those of $\langle coffin_2 \rangle$ within the current T_EX group level.

<code>\coffin_if_exist_p:N</code> ★
<code>\coffin_if_exist_p:c</code> ★
<code>\coffin_if_exist:NTF</code> ★
<code>\coffin_if_exist:cTF</code> ★
New: 2012-06-20

`\coffin_if_exist_p:N` $\langle box \rangle$

`\coffin_if_exist:NTF` $\langle box \rangle$ $\{\langle true\ code \rangle\}$ $\{\langle false\ code \rangle\}$

Tests whether the $\langle coffin \rangle$ is currently defined.

2 Setting coffin content and poles

All coffin functions create and manipulate coffins locally within the current T_EX group level.

<code>\hcoffin_set:Nn</code>
<code>\hcoffin_set:cn</code>
New: 2011-08-17
Updated: 2011-09-03

`\hcoffin_set:Nn` $\langle coffin \rangle$ $\{\langle material \rangle\}$

Typesets the $\langle material \rangle$ in horizontal mode, storing the result in the $\langle coffin \rangle$. The standard poles for the $\langle coffin \rangle$ are then set up based on the size of the typeset material.

<code>\hcoffin_set:Nw</code>
<code>\hcoffin_set:cw</code>
<code>\hcoffin_set_end:</code>
New: 2011-09-10

`\hcoffin_set:Nw` $\langle coffin \rangle$ $\langle material \rangle$ `\hcoffin_set_end:`

Typesets the $\langle material \rangle$ in horizontal mode, storing the result in the $\langle coffin \rangle$. The standard poles for the $\langle coffin \rangle$ are then set up based on the size of the typeset material. These functions are useful for setting the entire contents of an environment in a coffin.

`\vcoffin_set:Nnn`
`\vcoffin_set:cnn`
 New: 2011-08-17
 Updated: 2012-05-22

`\vcoffin_set:Nnn` $\langle coffin \rangle$ $\{\langle width \rangle\}$ $\{\langle material \rangle\}$
 Typesets the $\langle material \rangle$ in vertical mode constrained to the given $\langle width \rangle$ and stores the result in the $\langle coffin \rangle$. The standard poles for the $\langle coffin \rangle$ are then set up based on the size of the typeset material.

`\vcoffin_set:Nnw`
`\vcoffin_set:cnw`
`\vcoffin_set_end:`
 New: 2011-09-10
 Updated: 2012-05-22

`\vcoffin_set:Nnw` $\langle coffin \rangle$ $\{\langle width \rangle\}$ $\langle material \rangle$ `\vcoffin_set_end:`
 Typesets the $\langle material \rangle$ in vertical mode constrained to the given $\langle width \rangle$ and stores the result in the $\langle coffin \rangle$. The standard poles for the $\langle coffin \rangle$ are then set up based on the size of the typeset material. These functions are useful for setting the entire contents of an environment in a coffin.

`\coffin_set_horizontal_pole:Nnn`
`\coffin_set_horizontal_pole:cnn`
 New: 2012-07-20

`\coffin_set_horizontal_pole:Nnn` $\langle coffin \rangle$
 $\{\langle pole \rangle\}$ $\{\langle offset \rangle\}$

Sets the $\langle pole \rangle$ to run horizontally through the $\langle coffin \rangle$. The $\langle pole \rangle$ is placed at the $\langle offset \rangle$ from the bottom edge of the bounding box of the $\langle coffin \rangle$. The $\langle offset \rangle$ should be given as a dimension expression.

`\coffin_set_vertical_pole:Nnn`
`\coffin_set_vertical_pole:cnn`
 New: 2012-07-20

`\coffin_set_vertical_pole:Nnn` $\langle coffin \rangle$ $\{\langle pole \rangle\}$ $\{\langle offset \rangle\}$

Sets the $\langle pole \rangle$ to run vertically through the $\langle coffin \rangle$. The $\langle pole \rangle$ is placed at the $\langle offset \rangle$ from the left-hand edge of the bounding box of the $\langle coffin \rangle$. The $\langle offset \rangle$ should be given as a dimension expression.

3 Joining and using coffins

`\coffin_attach:NnnNnnnn`
`\coffin_attach:(cnnNnnnn|Nnnncnnnn|cnnncnnnn)`

`\coffin_attach:NnnNnnnn`
 $\langle coffin_1 \rangle$ $\{\langle coffin_1-pole_1 \rangle\}$ $\{\langle coffin_1-pole_2 \rangle\}$
 $\langle coffin_2 \rangle$ $\{\langle coffin_2-pole_1 \rangle\}$ $\{\langle coffin_2-pole_2 \rangle\}$
 $\{\langle x-offset \rangle\}$ $\{\langle y-offset \rangle\}$

This function attaches $\langle coffin_2 \rangle$ to $\langle coffin_1 \rangle$ such that the bounding box of $\langle coffin_1 \rangle$ is not altered, *i.e.* $\langle coffin_2 \rangle$ can protrude outside of the bounding box of the coffin. The alignment is carried out by first calculating $\langle handle_1 \rangle$, the point of intersection of $\langle coffin_1-pole_1 \rangle$ and $\langle coffin_1-pole_2 \rangle$, and $\langle handle_2 \rangle$, the point of intersection of $\langle coffin_2-pole_1 \rangle$ and $\langle coffin_2-pole_2 \rangle$. $\langle coffin_2 \rangle$ is then attached to $\langle coffin_1 \rangle$ such that the relationship between $\langle handle_1 \rangle$ and $\langle handle_2 \rangle$ is described by the $\langle x-offset \rangle$ and $\langle y-offset \rangle$. The two offsets should be given as dimension expressions.

```
\coffin_join:NnnNnnnn
\coffin_join:(cnnNnnnn|Nnnncnnnn|cnnncnnnn)
```

```
\coffin_join:NnnNnnnn
  <coffin_1> {<coffin_1-pole_1>} {<coffin_1-pole_2>}
  <coffin_2> {<coffin_2-pole_1>} {<coffin_2-pole_2>}
  {<x-offset>} {<y-offset>}
```

This function joins $\langle coffin_2 \rangle$ to $\langle coffin_1 \rangle$ such that the bounding box of $\langle coffin_1 \rangle$ may expand. The new bounding box covers the area containing the bounding boxes of the two original coffins. The alignment is carried out by first calculating $\langle handle_1 \rangle$, the point of intersection of $\langle coffin_1-pole_1 \rangle$ and $\langle coffin_1-pole_2 \rangle$, and $\langle handle_2 \rangle$, the point of intersection of $\langle coffin_2-pole_1 \rangle$ and $\langle coffin_2-pole_2 \rangle$. $\langle coffin_2 \rangle$ is then attached to $\langle coffin_1 \rangle$ such that the relationship between $\langle handle_1 \rangle$ and $\langle handle_2 \rangle$ is described by the $\langle x-offset \rangle$ and $\langle y-offset \rangle$. The two offsets should be given as dimension expressions.

```
\coffin_typeset:Nnnnn
\coffin_typeset:cnnnn
```

Updated: 2012-07-20

```
\coffin_typeset:Nnnnn <coffin> {<pole_1>} {<pole_2>}
  {<x-offset>} {<y-offset>}
```

Typesetting is carried out by first calculating $\langle handle \rangle$, the point of intersection of $\langle pole_1 \rangle$ and $\langle pole_2 \rangle$. The coffin is then typeset in horizontal mode such that the relationship between the current reference point in the document and the $\langle handle \rangle$ is described by the $\langle x-offset \rangle$ and $\langle y-offset \rangle$. The two offsets should be given as dimension expressions. Typesetting a coffin is therefore analogous to carrying out an alignment where the “parent” coffin is the current insertion point.

4 Measuring coffins

```
\coffin_dp:N
\coffin_dp:c
```

```
\coffin_dp:N <coffin>
```

Calculates the depth (below the baseline) of the $\langle coffin \rangle$ in a form suitable for use in a $\langle dimension expression \rangle$.

```
\coffin_ht:N
\coffin_ht:c
```

```
\coffin_ht:N <coffin>
```

Calculates the height (above the baseline) of the $\langle coffin \rangle$ in a form suitable for use in a $\langle dimension expression \rangle$.

```
\coffin_wd:N
\coffin_wd:c
```

```
\coffin_wd:N <coffin>
```

Calculates the width of the $\langle coffin \rangle$ in a form suitable for use in a $\langle dimension expression \rangle$.

5 Coffin diagnostics

```
\coffin_display_handles:Nn
\coffin_display_handles:cn
```

Updated: 2011-09-02

```
\coffin_display_handles:Nn <coffin> {<color>}
```

This function first calculates the intersections between all of the $\langle poles \rangle$ of the $\langle coffin \rangle$ to give a set of $\langle handles \rangle$. It then prints the $\langle coffin \rangle$ at the current location in the source, with the position of the $\langle handles \rangle$ marked on the coffin. The $\langle handles \rangle$ are labelled as part of this process: the locations of the $\langle handles \rangle$ and the labels are both printed in the $\langle color \rangle$ specified.

`\coffin_mark_handle:Nnnn`
`\coffin_mark_handle:cnnn`

Updated: 2011-09-02

`\coffin_mark_handle:Nnnn` $\langle coffin \rangle$ $\{\langle pole_1 \rangle\}$ $\{\langle pole_2 \rangle\}$ $\{\langle color \rangle\}$

This function first calculates the $\langle handle \rangle$ for the $\langle coffin \rangle$ as defined by the intersection of $\langle pole_1 \rangle$ and $\langle pole_2 \rangle$. It then marks the position of the $\langle handle \rangle$ on the $\langle coffin \rangle$. The $\langle handle \rangle$ are labelled as part of this process: the location of the $\langle handle \rangle$ and the label are both printed in the $\langle color \rangle$ specified.

`\coffin_show_structure:N`
`\coffin_show_structure:c`

Updated: 2015-08-01

`\coffin_show_structure:N` $\langle coffin \rangle$

This function shows the structural information about the $\langle coffin \rangle$ in the terminal. The width, height and depth of the typeset material are given, along with the location of all of the poles of the coffin.

Notice that the poles of a coffin are defined by four values: the x and y co-ordinates of a point that the pole passes through and the x - and y -components of a vector denoting the direction of the pole. It is the ratio between the later, rather than the absolute values, which determines the direction of the pole.

`\coffin_log_structure:N`
`\coffin_log_structure:c`

New: 2014-08-22
Updated: 2015-08-01

`\coffin_log_structure:N` $\langle coffin \rangle$

This function writes the structural information about the $\langle coffin \rangle$ in the log file. See also `\coffin_show_structure:N` which displays the result in the terminal.

5.1 Constants and variables

`\c_empty_coffin`

A permanently empty coffin.

`\l_tmpa_coffin`
`\l_tmpb_coffin`

New: 2012-06-19

Scratch coffins for local assignment. These are never used by the kernel code, and so are safe for use with any L^AT_EX3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.

Part XXVIII

The **l3color** package

Color support

This module provides support for color in L^AT_EX3. At present, the material here is mainly intended to support a small number of low-level requirements in other **l3kernel** modules.

1 Color in boxes

Controlling the color of text in boxes requires a small number of control functions, so that the boxed material uses the color at the point where it is set, rather than where it is used.

`\color_group_begin:`
`\color_group_end:`

New: 2011-09-03

`\color_group_begin:`
...
`\color_group_end:`

Creates a color group: one used to “trap” color settings.

`\color_ensure_current:`

New: 2011-09-03

`\color_ensure_current:`

Ensures that material inside a box uses the foreground color at the point where the box is set, rather than that in force when the box is used. This function should usually be used within a `\color_group_begin: ... \color_group_end:` group.

1.1 Internal functions

`\l__color_current_tl`

New: 2017-06-15
Updated: 2017-10-02

The color currently active for foreground (text, *etc.*) material. This is stored in the form of a color model followed by one or more values. There are four pre-defined models, three of which take numerical values in the range $[0, 1]$:

- `gray` $\langle gray \rangle$ Grayscale color with the $\langle gray \rangle$ value running from 0 (fully black) to 1 (fully white)
- `cmk` $\langle cyan \rangle$ $\langle magenta \rangle$ $\langle yellow \rangle$ $\langle black \rangle$
- `rgb` $\langle red \rangle$ $\langle green \rangle$ $\langle blue \rangle$

Notice that the value are separated by spaces. There is a fourth pre-defined model using a string value and a numerical one:

- `spot` $\langle name \rangle$ $\langle tint \rangle$ A pre-defined spot color, where the $\langle name \rangle$ should be a pre-defined string color name and the $\langle tint \rangle$ should be in the range $[0, 1]$.

Additional models may be created to allow mixing of spot colors. The number of data entries these require will depend on the number of colors to be mixed.

T_EXhackers note: The content of `\l__color_current_tl` is space-separated as this allows it to be used directly in specials in many common cases. This internal representation is close to that used by the `dvips` program.

Part XXIX

The l3sys package

System/runtime functions

1 The name of the job

`\c_sys_jobname_str`

New: 2015-09-19

Constant that gets the “job name” assigned when T_EX starts.

T_EXhackers note: This copies the contents of the primitive `\jobname`. It is a constant that is set by T_EX and should not be overwritten by the package.

2 Date and time

`\c_sys_minute_int`
`\c_sys_hour_int`
`\c_sys_day_int`
`\c_sys_month_int`
`\c_sys_year_int`

New: 2015-09-22

The date and time at which the current job was started: these are all reported as integers.

T_EXhackers note: Whilst the underlying primitives can be altered by the user, this interface to the time and date is intended to be the “real” values.

3 Engine

`\sys_if_engine luatex_p:` ★
`\sys_if_engine luatex:` *TF* ★
`\sys_if_engine pdftex_p:` ★
`\sys_if_engine pdftex:` *TF* ★
`\sys_if_engine ptex_p:` ★
`\sys_if_engine ptex:` *TF* ★
`\sys_if_engine uptex_p:` ★
`\sys_if_engine uptex:` *TF* ★
`\sys_if_engine xetex_p:` ★
`\sys_if_engine xetex:` *TF* ★

New: 2015-09-07

`\sys_if_engine pdftex:TF` *{(true code)}* *{(false code)}*

Conditionals which allow engine-specific code to be used. The names follow naturally from those of the engine binaries: note that the (u)ptex tests are for ε -pT_EX and ε -upT_EX as expl3 requires the ε -T_EX extensions. Each conditional is true for *exactly one* supported engine. In particular, `\sys_if_engine ptex_p:` is true for ε -pT_EX but false for ε -upT_EX.

`\c_sys_engine_str`

New: 2015-09-19

The current engine given as a lower case string: one of `luatex`, `pdftex`, `ptex`, `uptex` or `xetex`.

4 Output format

<code>\sys_if_output_dvi_p: *</code>	<code>\sys_if_output_dvi:TF {\true code} {\false code}</code>
<code>\sys_if_output_dvi:TF *</code>	
<code>\sys_if_output_pdf_p: *</code>	
<code>\sys_if_output_pdf:TF *</code>	Conditionals which give the current output mode the \TeX run is operating in. This is always one of two outcomes, DVI mode or PDF mode. The two sets of conditionals are thus complementary and are both provided to allow the programmer to emphasise the most appropriate case.

New: 2015-09-19

<code>\c_sys_output_str</code>	The current output mode given as a lower case string: one of dvi or pdf.
--------------------------------	--

New: 2015-09-19

Part XXX

The l3deprecation package

Deprecation errors

1 l3deprecation documentation

A few commands have had to be deprecated over the years. This module defines deprecated and deleted commands to produce an error.

Part XXXI

The l3candidates package

Experimental additions to l3kernel

1 Important notice

This module provides a space in which functions can be added to l3kernel (expl3) while still being experimental.

As such, the functions here may not remain in their current form, or indeed at all, in l3kernel in the future.

In contrast to the material in l3experimental, the functions here are all *small* additions to the kernel. We encourage programmers to test them out and report back on the **LaTeX-L** mailing list.

Thus, if you intend to use any of these functions from the candidate module in a public package offered to others for productive use (e.g., being placed on CTAN) please consider the following points carefully:

- Be prepared that your public packages might require updating when such functions are being finalized.
- Consider informing us that you use a particular function in your public package, e.g., by discussing this on the **LaTeX-L** mailing list. This way it becomes easier to coordinate any updates necessary without issues for the users of your package.
- Discussing and understanding use cases for a particular addition or concept also helps to ensure that we provide the right interfaces in the final version so please give us feedback if you consider a certain candidate function useful (or not).

We only add functions in this space if we consider them being serious candidates for a final inclusion into the kernel. However, real use sometimes leads to better ideas, so functions from this module are **not necessarily stable** and we may have to adjust them!

2 Additions to l3basics

`\debug_on:n`
`\debug_off:n`

New: 2017-07-16
Updated: 2017-08-02

`\debug_on:n { <comma-separated list> }`
`\debug_off:n { <comma-separated list> }`

Turn on and off within a group various debugging code, some of which is also available as expl3 load-time options. The items that can be used in the *<list>* are

- **check-declarations** that checks all expl3 variables used were previously declared and that local/global variables (based on their name or on their first assignment) are only locally/globally assigned;
- **check-expressions** that checks integer, dimension, skip, and muskip expressions are not terminated prematurely;
- **deprecation** that makes soon-to-be-deprecated commands produce errors;
- **log-functions** that logs function definitions;

Providing these as switches rather than options allows testing code even if it relies on other packages: load all other packages, call `\debug_on:n`, and load the code that one is interested in testing. These functions can only be used in L^AT_EX 2_ε package mode loaded with **enable-debug** or another option implying it.

`\debug_suspend:`
`\debug_resume:`

New: 2017-11-28

`\debug_suspend: ... \debug_resume:`

Suppress (locally) errors and logging from **debug** commands, except for the **deprecation** errors or warnings. These pairs of commands can be nested. This can be used around pieces of code that are known to fail checks, if such failures should be ignored. See for instance l3coffins.

`\mode_leave_vertical:`

New: 2017-07-04

`\mode_leave_vertical:`

Ensures that T_EX is not in vertical (inter-paragraph) mode. In horizontal or math mode this command has no effect, in vertical mode it switches to horizontal mode, and inserts a box of width `\parindent`, followed by the `\everypar` token list.

T_EXhackers note: This results in the contents of the `\everypar` token register being inserted, after `\mode_leave_vertical:` is complete. Notice that in contrast to the L^AT_EX 2_ε `\leavevmode` approach, no box is used by the method implemented here.

3 Additions to l3box

3.1 Viewing part of a box

<code>\box_clip:N</code>	<code>\box_clip:N <box></code>
<code>\box_clip:c</code>	

Clips the $\langle box \rangle$ in the output so that only material inside the bounding box is displayed in the output. The updated $\langle box \rangle$ is an hbox, irrespective of the nature of the $\langle box \rangle$ before the clipping is applied. The clipping applies within the current T_EX group level.

These functions require the L^AT_EX 3 native drivers: they do not work with the L^AT_EX 2_ε graphics drivers!

T_EXhackers note: Clipping is implemented by the driver, and as such the full content of the box is placed in the output file. Thus clipping does not remove any information from the raw output, and hidden material can therefore be viewed by direct examination of the file.

<code>\box_trim:Nnnnn</code>	<code>\box_trim:Nnnnn <box> {<left>} {<bottom>} {<right>} {<top>}</code>
<code>\box_trim:cnnnn</code>	

Adjusts the bounding box of the $\langle box \rangle$ $\langle left \rangle$ is removed from the left-hand edge of the bounding box, $\langle right \rangle$ from the right-hand edge and so fourth. All adjustments are $\langle dimension expressions \rangle$. Material outside of the bounding box is still displayed in the output unless `\box_clip:N` is subsequently applied. The updated $\langle box \rangle$ is an hbox, irrespective of the nature of the $\langle box \rangle$ before the trim operation is applied. The adjustment applies within the current T_EX group level. The behavior of the operation where the trims requested is greater than the size of the box is undefined.

<code>\box_viewport:Nnnnn</code>	<code>\box_viewport:Nnnnn <box> {<llx>} {<lly>} {<urx>} {<ury>}</code>
<code>\box_viewport:cnnnn</code>	

Adjusts the bounding box of the $\langle box \rangle$ such that it has lower-left co-ordinates ($\langle llx \rangle$, $\langle lly \rangle$) and upper-right co-ordinates ($\langle urx \rangle$, $\langle ury \rangle$). All four co-ordinate positions are $\langle dimension expressions \rangle$. Material outside of the bounding box is still displayed in the output unless `\box_clip:N` is subsequently applied. The updated $\langle box \rangle$ is an hbox, irrespective of the nature of the $\langle box \rangle$ before the viewport operation is applied. The adjustment applies within the current T_EX group level.

4 Additions to l3clist

<code>\clist_rand_item:N</code> ★	<code>\clist_rand_item:N <clist var></code>
<code>\clist_rand_item:c</code> ★	<code>\clist_rand_item:n {<comma list>}</code>
<code>\clist_rand_item:n</code> ★	

New: 2016-12-06

Selects a pseudo-random item of the $\langle comma list \rangle$. If the $\langle comma list \rangle$ has no item, the result is empty. This is only available in pdfT_EX and LuaT_EX.

T_EXhackers note: The result is returned within the `\unexpanded` primitive (`\exp_not:n`), which means that the $\langle item \rangle$ does not expand further when appearing in an x-type argument expansion.

5 Additions to l3coffins

`\coffin_resize:Nnn`
`\coffin_resize:cnn`

`\coffin_resize:Nnn` $\langle coffin \rangle$ $\{\langle width \rangle\}$ $\{\langle total-height \rangle\}$

Resized the $\langle coffin \rangle$ to $\langle width \rangle$ and $\langle total-height \rangle$, both of which should be given as dimension expressions.

`\coffin_rotate:Nn`
`\coffin_rotate:cn`

`\coffin_rotate:Nn` $\langle coffin \rangle$ $\{\langle angle \rangle\}$

Rotates the $\langle coffin \rangle$ by the given $\langle angle \rangle$ (given in degrees counter-clockwise). This process rotates both the coffin content and poles. Multiple rotations do not result in the bounding box of the coffin growing unnecessarily.

`\coffin_scale:Nnn`
`\coffin_scale:cnn`

`\coffin_scale:Nnn` $\langle coffin \rangle$ $\{\langle x-scale \rangle\}$ $\{\langle y-scale \rangle\}$

Scales the $\langle coffin \rangle$ by a factors $\langle x-scale \rangle$ and $\langle y-scale \rangle$ in the horizontal and vertical directions, respectively. The two scale factors should be given as real numbers.

6 Additions to l3file

`\file_get_md5five_hash:nN`

New: 2017-07-11

`\file_get_md5five_hash:nN` $\{\langle file name \rangle\}$ $\langle str var \rangle$

Searches for $\langle file name \rangle$ using the current T_EX search path and the additional paths controlled by `\file_path_include:n`. If found, sets the $\langle str var \rangle$ to the MD5 sum generated from the content of the file. The file is read as bytes, which means that in contrast to most T_EX behaviour there will be a difference in result depending on the line endings used in text files. The same file will produce the same result between different engines: the algorithm used is the same in all cases. Where the file is not found, the $\langle str var \rangle$ will be empty.

`\file_get_size:nN`

New: 2017-07-09

`\file_get_size:nN` $\{\langle file name \rangle\}$ $\langle str var \rangle$

Searches for $\langle file name \rangle$ using the current T_EX search path and the additional paths controlled by `\file_path_include:n`. If found, sets the $\langle str var \rangle$ to the size of the file in bytes. Where the file is not found, the $\langle str var \rangle$ will be empty.

T_EXhackers note: The X_ƎT_EX engine provides no way to implement this function.

`\file_get_timestamp:nN`

New: 2017-07-09

`\file_get_timestamp:nN` $\{\langle file name \rangle\}$ $\langle str var \rangle$

Searches for $\langle file name \rangle$ using the current T_EX search path and the additional paths controlled by `\file_path_include:n`. If found, sets the $\langle str var \rangle$ to the modification timestamp of the file in the form D: $\langle year \rangle$ $\langle month \rangle$ $\langle day \rangle$ $\langle hour \rangle$ $\langle minute \rangle$ $\langle second \rangle$ $\langle offset \rangle$, where the latter may be Z (UTC) or $\langle plus-minus \rangle$ $\langle hours \rangle$ ' $\langle minutes \rangle$ '. Where the file is not found, the $\langle str var \rangle$ will be empty.

T_EXhackers note: The X_ƎT_EX engine provides no way to implement this function.

```
\file_if_exist_input:n
\file_if_exist_input:nF
```

New: 2014-07-02

```
\file_if_exist_input:n {\file name}
\file_if_exist_input:nF {\file name} {\false code}
```

Searches for $\langle file\ name \rangle$ using the current \TeX search path and the additional paths controlled by $\text{\file_path_include:n}$. If found then reads in the file as additional \LaTeX source as described for \file_input:n , otherwise inserts the $\langle false\ code \rangle$. Note that these functions do not raise an error if the file is not found, in contrast to \file_input:n .

```
\file_input_stop:
```

New: 2017-07-07

```
\file_input_stop:
```

Ends the reading of a file started by \file_input:n or similar before the end of the file is reached. Where the file reading is being terminated due to an error, $\text{\msg_critical:nn(nn)}$ should be preferred.

\TeX hackers note: This function must be used on a line on its own: \TeX reads files line-by-line and so any additional tokens in the “current” line will still be read.

This is also true if the function is hidden inside another function (which will be the normal case), i.e., all tokens on the same line in the source file are still processed. Putting it on a line by itself in the definition doesn’t help as it is the line where it is used that counts!

7 Additions to \l3int

```
\int_rand:nn ★
```

New: 2016-12-06

```
\int_rand:nn {\intexpr1} {\intexpr2}
```

Evaluates the two $\langle integer\ expressions \rangle$ and produces a pseudo-random number between the two (with bounds included). This is only available in \pdfTeX and \LuaTeX .

8 Additions to \l3msg

In very rare cases it may be necessary to produce errors in an expansion-only context. The functions in this section should only be used if there is no alternative approach using \msg_error:nnnnnn or other non-expandable commands from the previous section. Despite having a similar interface as non-expandable messages, expandable errors must be handled internally very differently from normal error messages, as none of the tools to print to the terminal or the log file are expandable. As a result, the message text and arguments are not expanded, and messages must be very short (with default settings, they are truncated after approximately 50 characters). It is advisable to ensure that the message is understandable even when truncated. Another particularity of expandable messages is that they cannot be redirected or turned off by the user.

<code>\msg_expandable_error:nnnnnn</code>	★	<code>\msg_expandable_error:nnnnnn {<module>} {<message>} {<arg one>} {<arg</code>
<code>\msg_expandable_error:nnffff</code>	★	<code>two}> {<arg three>} {<arg four>}</code>
<code>\msg_expandable_error:nnnnn</code>	★	
<code>\msg_expandable_error:nnfff</code>	★	
<code>\msg_expandable_error:nnnn</code>	★	
<code>\msg_expandable_error:nnff</code>	★	
<code>\msg_expandable_error:nnn</code>	★	
<code>\msg_expandable_error:nnf</code>	★	
<code>\msg_expandable_error:nn</code>	★	

New: 2015-08-06

Issues an “Undefined error” message from T_EX itself using the undefined control sequence `\::error` then prints “! <module>: ”<error message>, which should be short. With default settings, anything beyond approximately 60 characters long (or bytes in some engines) is cropped. A leading space might be removed as well.

<code>\msg_show_eval:Nn</code>	<code>\msg_show_eval:Nn <function> {<expression>}</code>
<code>\msg_log_eval:Nn</code>	

New: 2017-12-04

Shows or logs the <expression> (turned into a string), an equal sign, and the result of applying the <function> to the {<expression>} (with f-expansion). For instance, if the <function> is `\int_eval:n` and the <expression> is `1+2` then this logs `> 1+2=3`.

<code>\msg_show:nnnnnn</code>	<code>\msg_show:nnnnnn {<module>} {<message>} {<arg one>} {<arg two>} {<arg three>} {<arg</code>
<code>\msg_show:nnxxxx</code>	<code>four}></code>
<code>\msg_show:nnnnn</code>	
<code>\msg_show:nnxxx</code>	
<code>\msg_show:nnnn</code>	
<code>\msg_show:nnxx</code>	
<code>\msg_show:nnn</code>	
<code>\msg_show:nnx</code>	
<code>\msg_show:nn</code>	

New: 2017-12-04

Issues <module> information <message>, passing <arg one> to <arg four> to the text-creating functions. The information text is shown on the terminal and the T_EX run is interrupted in a manner similar to `\tl_show:n`. This is used in conjunction with `\msg_show_item:n` and similar functions to print complex variable contents completely. If the formatted text does not contain `>~` at the start of a line, an additional line `>~`. will be put at the end. In addition, a final period is added if not present.

<code>\msg_show_item:n</code>	★	<code>\seq_map_function:NN <seq> \msg_show_item:n</code>
<code>\msg_show_item_unbraced:n</code>	★	<code>\prop_map_function:NN <prop> \msg_show_item:nn</code>
<code>\msg_show_item:nn</code>	★	
<code>\msg_show_item_unbraced:nn</code>	★	

New: 2017-12-04

Used in the text of messages for `\msg_show:nnxxxx` to show or log a list of items or key-value pairs. The one-argument functions are used for sequences, clist or token lists and the others for property lists. These functions turn their arguments to strings.

9 Additions to l3prg

<code>\bool_const:Nn</code>	<code>\bool_const:Nn <boolean> {<boolexpr>}</code>
<code>\bool_const:cn</code>	

New: 2017-11-28

Creates a new constant <boolean> or raises an error if the name is already taken. The value of the <boolean> is set globally to the result of evaluating the <boolexpr>.

10 Additions to l3prop

`\prop_count:N` ★
`\prop_count:c` ★

`\prop_count:N` $\langle property list \rangle$

Leaves the number of key–value pairs in the $\langle property list \rangle$ in the input stream as an $\langle integer denotation \rangle$.

`\prop_map_tokens:Nn` ★
`\prop_map_tokens:cn` ★

`\prop_map_tokens:Nn` $\langle property list \rangle$ $\{ \langle code \rangle \}$

Analogue of `\prop_map_function:NN` which maps several tokens instead of a single function. The $\langle code \rangle$ receives each key–value pair in the $\langle property list \rangle$ as two trailing brace groups. For instance,

`\prop_map_tokens:Nn \l_my_prop { \str_if_eq:nnT { mykey } }`

expands to the value corresponding to `mykey`: for each pair in `\l_my_prop` the function `\str_if_eq:nnT` receives `mykey`, the $\langle key \rangle$ and the $\langle value \rangle$ as its three arguments. For that specific task, `\prop_item:Nn` is faster.

`\prop_rand_key_value:N` ★
`\prop_rand_key_value:c` ★

`\prop_rand_key_value:N` $\langle prop var \rangle$

Selects a pseudo-random key–value pair in the $\langle property list \rangle$ and returns $\{ \langle key \rangle \} \{ \langle value \rangle \}$. If the $\langle property list \rangle$ is empty the result is empty. This is only available in pdfTeX and LuaTeX.

New: 2016-12-06

TeXhackers note: The result is returned within the `\unexpanded` primitive (`\exp_not:n`), which means that the $\langle value \rangle$ does not expand further when appearing in an x-type argument expansion.

`\prop_set_from_keyval:Nn`
`\prop_set_from_keyval:cn`
`\prop_gset_from_keyval:Nn`
`\prop_gset_from_keyval:cn`

`\prop_set_from_keyval:Nn` $\langle prop var \rangle$

```
{
  \key1 = \value1 ,
  \key2 = \value2 , ...
}
```

New: 2017-11-28

Sets $\langle prop var \rangle$ to contain key–value pairs given in the second argument.

`\prop_const_from_keyval:Nn`
`\prop_const_from_keyval:cn`

`\prop_const_from_keyval:Nn` $\langle prop var \rangle$

```
{
  \key1 = \value1 ,
  \key2 = \value2 , ...
}
```

New: 2017-11-28

Creates a new constant $\langle prop var \rangle$ or raises an error if the name is already taken. The $\langle prop var \rangle$ is set globally to contain key–value pairs given in the second argument.

11 Additions to l3seq

<code>\seq_mapthread_function:NNN</code>	☆	<code>\seq_mapthread_function:NNN <seq1> <seq2> <function></code>
<code>\seq_mapthread_function:(NcN cNN ccN)</code>	☆	

Applies $\langle function \rangle$ to every pair of items $\langle seq_1-item \rangle$ – $\langle seq_2-item \rangle$ from the two sequences, returning items from both sequences from left to right. The $\langle function \rangle$ receives two `n`-type arguments for each iteration. The mapping terminates when the end of either sequence is reached (*i.e.* whichever sequence has fewer items determines how many iterations occur).

<code>\seq_set_filter:NNn</code>	<code>\seq_set_filter:NNn <sequence1> <sequence2> {\inline boolexpr}</code>
<code>\seq_gset_filter:NNn</code>	

Evaluates the $\langle inline boolexpr \rangle$ for every $\langle item \rangle$ stored within the $\langle sequence_2 \rangle$. The $\langle inline boolexpr \rangle$ receives the $\langle item \rangle$ as `#1`. The sequence of all $\langle items \rangle$ for which the $\langle inline boolexpr \rangle$ evaluated to `true` is assigned to $\langle sequence_1 \rangle$.

TeXhackers note: Contrarily to other mapping functions, `\seq_map_break:` cannot be used in this function, and would lead to low-level TeX errors.

<code>\seq_set_map:NNn</code>	<code>\seq_set_map:NNn <sequence1> <sequence2> {\inline function}</code>
<code>\seq_gset_map:NNn</code>	

New: 2011-12-22

Applies $\langle inline function \rangle$ to every $\langle item \rangle$ stored within the $\langle sequence_2 \rangle$. The $\langle inline function \rangle$ should consist of code which will receive the $\langle item \rangle$ as `#1`. The sequence resulting from `x`-expanding $\langle inline function \rangle$ applied to each $\langle item \rangle$ is assigned to $\langle sequence_1 \rangle$. As such, the code in $\langle inline function \rangle$ should be expandable.

TeXhackers note: Contrarily to other mapping functions, `\seq_map_break:` cannot be used in this function, and would lead to low-level TeX errors.

<code>\seq_rand_item:N</code>	★	<code>\seq_rand_item:N <seq var></code>
<code>\seq_rand_item:c</code>	★	

New: 2016-12-06

Selects a pseudo-random item of the $\langle sequence \rangle$. If the $\langle sequence \rangle$ is empty the result is empty. This is only available in pdfTeX and LuaTeX.

TeXhackers note: The result is returned within the `\unexpanded` primitive (`\exp_not:n`), which means that the $\langle item \rangle$ does not expand further when appearing in an `x`-type argument expansion.

<code>\seq_const_from_clist:Nn</code>	<code>\seq_const_from_clist:Nn <seq var> {\comma-list}</code>
<code>\seq_const_from_clist:cn</code>	

New: 2017-11-28

Creates a new constant $\langle seq var \rangle$ or raises an error if the name is already taken. The $\langle seq var \rangle$ is set globally to contain the items in the $\langle comma list \rangle$.

12 Additions to l3skip

<code>\skip_split_finite_else_action:nnNN</code>	<code>\skip_split_finite_else_action:nnNN {<skipexpr>} {<action>} <dimen₁> <dimen₂></code>
--	--

Checks if the *<skipexpr>* contains finite glue. If it does then it assigns *<dimen₁>* the stretch component and *<dimen₂>* the shrink component. If it contains infinite glue set *<dimen₁>* and *<dimen₂>* to 0pt and place #2 into the input stream: this is usually an error or warning message of some sort.

13 Additions to l3sys

<code>\sys_if_rand_exist_p: *</code>	<code>\sys_if_rand_exist_p:</code>
<code>\sys_if_rand_exist:TF *</code>	<code>\sys_if_rand_exist:TF {<true code>} {<false code>}</code>

New: 2017-05-27

Tests if the engine has a pseudo-random number generator. Currently this is the case in pdfTeX and LuaTeX.

<code>\sys_rand_seed: *</code>	<code>\sys_rand_seed:</code>
--------------------------------	------------------------------

New: 2017-05-27

Expands to the current value of the engine's random seed, a non-negative integer. In engines without random number support this expands to 0.

<code>\sys_gset_rand_seed:n</code>	<code>\sys_gset_rand_seed:n {<intexpr>}</code>
------------------------------------	--

New: 2017-05-27

Sets the seed for the engine's pseudo-random number generator to the *<integer expression>*. The assignment is global. This random seed affects all `\..._rand` functions (such as `\int_rand:nn` or `\clist_rand_item:n`) as well as other packages relying on the engine's random number generator. Currently only the absolute value of the seed is used. In engines without random number support this produces an error.

<code>\c_sys_shell_escape_int</code>

New: 2017-05-27

This variable exposes the internal triple of the shell escape status. The possible values are

- 0 Shell escape is disabled
- 1 Unrestricted shell escape is enabled
- 2 Restricted shell escape is enabled

<code>\sys_if_shell_p: *</code>	<code>\sys_if_shell_p:</code>
<code>\sys_if_shell:TF *</code>	<code>\sys_if_shell:TF {<true code>} {<false code>}</code>

New: 2017-05-27

Performs a check for whether shell escape is enabled. This returns true if either of restricted or unrestricted shell escape is enabled.

<code>\sys_if_shell_unrestricted_p: *</code>	<code>\sys_if_shell_unrestricted_p:</code>
<code>\sys_if_shell_unrestricted:TF *</code>	<code>\sys_if_shell_unrestricted:TF {<true code>} {<false code>}</code>

New: 2017-05-27

Performs a check for whether *unrestricted* shell escape is enabled.

<code>\sys_if_shell_restricted_p:n</code>	★	<code>\sys_if_shell_restricted_p:</code>
<code>\sys_if_shell_restricted:TF</code>	★	<code>\sys_if_shell_restricted:TF</code> $\{\langle true\ code\rangle\}$ $\{\langle false\ code\rangle\}$

New: 2017-05-27

Performs a check for whether *restricted* shell escape is enabled. This returns false if unrestricted shell escape is enabled. Unrestricted shell escape is not considered a superset of restricted shell escape in this case. To find whether any shell escape is enabled use `\sys_if_shell:.`

<code>\sys_shell_now:n</code>	<code>\sys_shell_now:n</code> $\{\langle tokens\rangle\}$
<code>\sys_shell_now:x</code>	

New: 2017-05-27

Execute $\langle tokens\rangle$ through shell escape immediately.

<code>\sys_shell_shipout:n</code>	<code>\sys_shell_shipout:n</code> $\{\langle tokens\rangle\}$
<code>\sys_shell_shipout:x</code>	

New: 2017-05-27

Execute $\langle tokens\rangle$ through shell escape at shipout.

14 Additions to l3tl

<code>\tl_if_single_token_p:n</code>	★	<code>\tl_if_single_token_p:n</code> $\{\langle token\ list\rangle\}$
<code>\tl_if_single_token:nTF</code>	★	<code>\tl_if_single_token:nTF</code> $\{\langle token\ list\rangle\}$ $\{\langle true\ code\rangle\}$ $\{\langle false\ code\rangle\}$

Tests if the token list consists of exactly one token, *i.e.* is either a single space character or a single “normal” token. Token groups $\{\dots\}$ are not single tokens.

<code>\tl_reverse_tokens:n</code>	★	<code>\tl_reverse_tokens:n</code> $\{\langle tokens\rangle\}$
-----------------------------------	---	---

This function, which works directly on T_EX tokens, reverses the order of the $\langle tokens\rangle$: the first becomes the last and the last becomes first. Spaces are preserved. The reversal also operates within brace groups, but the braces themselves are not exchanged, as this would lead to an unbalanced token list. For instance, `\tl_reverse_tokens:n {a~{b()}}` leaves `{() (b)~a` in the input stream. This function requires two steps of expansion.

T_EXhackers note: The result is returned within the `\unexpanded` primitive (`\exp_not:n`), which means that the token list does not expand further when appearing in an x-type argument expansion.

<code>\tl_count_tokens:n</code>	★	<code>\tl_count_tokens:n</code> $\{\langle tokens\rangle\}$
---------------------------------	---	---

Counts the number of T_EX tokens in the $\langle tokens\rangle$ and leaves this information in the input stream. Every token, including spaces and braces, contributes one to the total; thus for instance, the token count of `a~{bc}` is 6. This function requires three expansions, giving an *integer denotation*.

<code>\tl_lower_case:n</code>	★	<code>\tl_upper_case:n</code>	<code>{\tokens}</code>
<code>\tl_upper_case:n</code>	★	<code>\tl_upper_case:nn</code>	<code>{\language}</code> <code>{\tokens}</code>
<code>\tl_mixed_case:n</code>	★		
<code>\tl_lower_case:nn</code>	★		
<code>\tl_upper_case:nn</code>	★		
<code>\tl_mixed_case:nn</code>	★		

New: 2014-06-30
Updated: 2016-01-12

These functions are intended to be applied to input which may be regarded broadly as “text”. They traverse the `\tokens` and change the case of characters as discussed below. The character code of the characters replaced may be arbitrary: the replacement characters have standard document-level category codes (11 for letters, 12 for letter-like characters which can also be case-changed). Begin-group and end-group characters in the `\tokens` are normalized and become `{` and `}`, respectively.

Importantly, notice that these functions are intended for working with user text for typesetting. For case changing programmatic data see the `l3str` module and discussion there of `\str_lower_case:n`, `\str_upper_case:n` and `\str_fold_case:n`.

The functions perform expansion on the input in most cases. In particular, input in the form of token lists or expandable functions is expanded *unless* it falls within one of the special handling classes described below. This expansion approach means that in general the result of case changing matches the “natural” outcome expected from a “functional” approach to case modification. For example

```
\tl_set:Nn \l_tmpa_tl { hello }
\tl_upper_case:n { \l_tmpa_tl \c_space_tl world }
```

produces

HELLO WORLD

The expansion approach taken means that in package mode any L^AT_EX 2_ε “robust” commands which may appear in the input should be converted to engine-protected versions using for example the `\robustify` command from the `etoolbox` package.

`\l_tl_case_change_math_tl`

Case changing does not take place within math mode material so for example

```
\tl_upper_case:n { Some~text~$y = mx + c$~with~{Braces} }
```

becomes

SOME TEXT \$y = mx + c\$ WITH {BRACES}

Material inside math mode is left entirely unchanged: in particular, no expansion is undertaken.

Detection of math mode is controlled by the list of tokens in `\l_tl_case_change_math_tl`, which should be in open-close pairs. In package mode the standard settings is

```
$ $ \ ( \)
```

Note that while expansion occurs when searching the text it does not apply to math mode material (which should be unaffected by case changing). As such, whilst the opening token for math mode may be “hidden” inside a command/macro, the closing one cannot be as this is being searched for in math mode. Typically, in the types of “text” the case changing functions are intended to apply to this should not be an issue.

`\l_tl_case_change_exclude_tl`

Case changing can be prevented by using any command on the list `\l_tl_case_change_exclude_tl`. Each entry should be a function to be followed by one argument: the latter will be preserved as-is with no expansion. Thus for example following

```
\tl_put_right:Nn \l_tl_case_change_exclude_tl { \NoChangeCase }
```

the input

```
\tl_upper_case:n  
  { Some~text~$y = mx + c$~with~\NoChangeCase {Protection} }
```

will result in

```
SOME TEXT $y = mx + c$ WITH \NoChangeCase {Protection}
```

Notice that the case changing mapping preserves the inclusion of the escape functions: it is left to other code to provide suitable definitions (typically equivalent to `\use:n`). In particular, the result of case changing is returned protected by `\exp_not:n`.

When used with L^AT_EX 2_ε the commands `\cite`, `\ensuremath`, `\label` and `\ref` are automatically included in the list for exclusion from case changing.

`\l_tl_case_change_accents_tl`

This list specifies accent commands which should be left unexpanded in the output. This allows for example

```
\tl_upper_case:n { \" { a } }
```

to yield

```
\" { A }
```

irrespective of the expandability of `\`.

The standard contents of this variable is `\`, `\'`, `\.`, `\^`, `\'`, `\~`, `\c`, `\H`, `\k`, `\r`, `\t`, `\u` and `\v`.

“Mixed” case conversion may be regarded informally as converting the first character of the *<tokens>* to upper case and the rest to lower case. However, the process is more complex than this as there are some situations where a single lower case character maps to a special form, for example *ij* in Dutch which becomes *IJ*. As such, `\tl_mixed_case:n(n)` implement a more sophisticated mapping which accounts for this and for modifying accents on the first letter. Spaces at the start of the *<tokens>* are ignored when finding the first “letter” for conversion.

```
\tl_mixed_case:n { hello~WORLD } % => "Hello world"  
\tl_mixed_case:n { ~hello~WORLD } % => " Hello world"  
\tl_mixed_case:n { {hello}~WORLD } % => "{Hello} world"
```

When finding the first “letter” for this process, any content in math mode or covered by `\l_tl_case_change_exclude_tl` is ignored.

(Note that the Unicode Consortium describe this as “title case”, but that in English title case applies on a word-by-word basis. The “mixed” case implemented here is a lower level concept needed for both “title” and “sentence” casing of text.)

`\tl_mixed_case_ignore_tl`

The list of characters to ignore when searching for the first “letter” in mixed-casing is determined by `\tl_mixed_change_ignore_tl`. This has the standard setting

`([{ ‘ -`

where comparisons are made on a character basis.

As is generally true for `expl3`, these functions are designed to work with Unicode input only. As such, UTF-8 input is assumed for *all* engines. When used with \TeX or Lua \TeX a full range of Unicode transformations are enabled. Specifically, the standard mappings here follow those defined by the [Unicode Consortium](#) in `UnicodeData.txt` and `SpecialCasing.txt`. In the case of 8-bit engines, mappings are provided for characters which can be represented in output typeset using the T1 font encoding. Thus for example `Ãd` can be case-changed using pdf \TeX . For p \TeX only the ASCII range is covered as the engine treats input outside of this range as east Asian.

Context-sensitive mappings are enabled: language-dependent cases are discussed below. Context detection expands input but treats any unexpandable control sequences as “failures” to match a context.

Language-sensitive conversions are enabled using the `<language>` argument, and follow Unicode Consortium guidelines. Currently, the languages recognised for special handling are as follows.

- Azeri and Turkish (`az` and `tr`). The case pairs I/i-dotless and I-dot/i are activated for these languages. The combining dot mark is removed when lower casing I-dot and introduced when upper casing i-dotless.
- German (`de-alt`). An alternative mapping for German in which the lower case *Eszett* maps to a *großes Eszett*.
- Lithuanian (`lt`). The lower case letters i and j should retain a dot above when the accents grave, acute or tilde are present. This is implemented for lower casing of the relevant upper case letters both when input as single Unicode codepoints and when using combining accents. The combining dot is removed when upper casing in these cases. Note that *only* the accents used in Lithuanian are covered: the behaviour of other accents are not modified.
- Dutch (`nl`). Capitalisation of `ij` at the beginning of mixed cased input produces `IJ` rather than `Ij`. The output retains two separate letters, thus this transformation *is* available using pdf \TeX .

Creating additional context-sensitive mappings requires knowledge of the underlying mapping implementation used here. The team are happy to add these to the kernel where they are well-documented (*e.g.* in Unicode Consortium or relevant government publications).

`\tl_set_from_file:Nnn`
`\tl_set_from_file:cnn`
`\tl_gset_from_file:Nnn`
`\tl_gset_from_file:cnn`

New: 2014-06-25

`\tl_set_from_file:Nnn <tl> {<setup>} {<filename>}`

Defines `<tl>` to the contents of `<filename>`. Category codes may need to be set appropriately via the `<setup>` argument.

<code>\tl_set_from_file_x:Nnn</code>	<code>\tl_set_from_file_x:Nnn <tl> {<setup>} {<filename>}</code>
<code>\tl_set_from_file_x:cnn</code>	Defines <code><tl></code> to the contents of <code><filename></code> , expanding the contents of the file as it is read.
<code>\tl_gset_from_file_x:Nnn</code>	Category codes and other definitions may need to be set appropriately via the <code><setup></code>
<code>\tl_gset_from_file_x:cnn</code>	argument.

New: 2014-06-25

<code>\tl_rand_item:N *</code>	<code>\tl_rand_item:N <tl var></code>
<code>\tl_rand_item:c *</code>	<code>\tl_rand_item:n {<token list>}</code>
<code>\tl_rand_item:n *</code>	Selects a pseudo-random item of the <code><token list></code> . If the <code><token list></code> is blank, the result is empty. This is only available in pdfTeX and LuaTeX.

New: 2016-12-06

TeXhackers note: The result is returned within the `\unexpanded` primitive (`\exp_not:n`), which means that the `<item>` does not expand further when appearing in an `x`-type argument expansion.

<code>\tl_range:nnn *</code>	<code>\tl_range:nnn <tl var> {<start index>} {<end index>}</code>
	<code>\tl_range:nnn {<token list>} {<start index>} {<end index>}</code>

New: 2017-02-17

Updated: 2017-07-15

Leaves in the input stream the items from the `<start index>` to the `<end index>` inclusive. Spaces and braces are preserved between the items returned (but never at either end of the list). Positive `<indices>` are counted from the start of the `<token list>`, 1 being the first item, and negative `<indices>` are counted from the end of the token list, `-1` being the last item. If either of `<start index>` or `<end index>` is 0, the result is empty. For instance,

```
\iow_term:x { \tl_range:nnn { abcd~{e}}f } { 2 } { 5 } }
\iow_term:x { \tl_range:nnn { abcd~{e}}f } { -4 } { -1 } }
\iow_term:x { \tl_range:nnn { abcd~{e}}f } { -2 } { -1 } }
\iow_term:x { \tl_range:nnn { abcd~{e}}f } { 0 } { -1 } }
```

prints `bcd_{e}}`, `cd_{e}}f`, `{e}}f` and an empty line to the terminal. The `<start index>` must always be smaller than or equal to the `<end index>`: if this is not the case then no output is generated. Thus

```
\iow_term:x { \tl_range:nnn { abcd~{e}}f } { 5 } { 2 } }
\iow_term:x { \tl_range:nnn { abcd~{e}}f } { -1 } { -4 } }
```

both yield empty token lists. For improved performance, see `\tl_range_braced:nnn` and `\tl_range_unbraced:nnn`.

TeXhackers note: The result is returned within the `\unexpanded` primitive (`\exp_not:n`), which means that the `<item>` does not expand further when appearing in an `x`-type argument expansion.

<code>\tl_range_braced:Nnn</code>	★
<code>\tl_range_braced:cnn</code>	★
<code>\tl_range_braced:nnn</code>	★
<code>\tl_range_unbraced:Nnn</code>	★
<code>\tl_range_unbraced:cnn</code>	★
<code>\tl_range_unbraced:nnn</code>	★

New: 2017-07-15

```

\tl_range_braced:Nnn <tl var> {\<start index>} {\<end index>}
\tl_range_braced:cnn <token list> {\<start index>} {\<end index>}
\tl_range_braced:nnn <tl var> {\<start index>} {\<end index>}
\tl_range_unbraced:Nnn <token list> {\<start index>} {\<end index>}

```

Leaves in the input stream the items from the $\langle start\ index \rangle$ to the $\langle end\ index \rangle$ inclusive, using the same indexing as `\tl_range:nnn`. Spaces are ignored. Regardless of whether items appear with or without braces in the $\langle token\ list \rangle$, the `\tl_range_braced:nnn` function wraps each item in braces, while `\tl_range_unbraced:nnn` does not (overall it removes an outer set of braces). For instance,

```

\iow_term:x { \tl_range_braced:nnn { abcd~{e}}f } { 2 } { 5 } }
\iow_term:x { \tl_range_braced:nnn { abcd~{e}}f } { -4 } { -1 } }
\iow_term:x { \tl_range_braced:nnn { abcd~{e}}f } { -2 } { -1 } }
\iow_term:x { \tl_range_braced:nnn { abcd~{e}}f } { 0 } { -1 } }

```

prints `{b}{c}{d}{e}`, `{c}{d}{e}{f}`, `{e}{f}`, and an empty line to the terminal, while

```

\iow_term:x { \tl_range_unbraced:nnn { abcd~{e}}f } { 2 } { 5 } }
\iow_term:x { \tl_range_unbraced:nnn { abcd~{e}}f } { -4 } { -1 } }
\iow_term:x { \tl_range_unbraced:nnn { abcd~{e}}f } { -2 } { -1 } }
\iow_term:x { \tl_range_unbraced:nnn { abcd~{e}}f } { 0 } { -1 } }

```

prints `bcde{}`, `cde{f}`, `e{f}`, and an empty line to the terminal. Because braces are removed, the result of `\tl_range_unbraced:nnn` may have a different number of items as for `\tl_range:nnn` or `\tl_range_braced:nnn`. In cases where preserving spaces is important, consider the slower function `\tl_range:nnn`.

TeXhackers note: The result is returned within the `\unexpanded` primitive (`\exp_not:n`), which means that the $\langle item \rangle$ does not expand further when appearing in an x-type argument expansion.

15 Additions to l3token

<code>\c_catcode_active_space_tl</code>

New: 2017-08-07

<code>\peek_N_type:TF</code>

Updated: 2012-12-20

Token list containing one character with category code 13, (“active”), and character code 32 (space).

```

\peek_N_type:TF {\<true code>} {\<false code>}

```

Tests if the next $\langle token \rangle$ in the input stream can be safely grabbed as an N-type argument. The test is $\langle false \rangle$ if the next $\langle token \rangle$ is either an explicit or implicit begin-group or end-group token (with any character code), or an explicit or implicit space character (with character code 32 and category code 10), or an outer token (never used in L^AT_EX3) and $\langle true \rangle$ in all other cases. Note that a $\langle true \rangle$ result ensures that the next $\langle token \rangle$ is a valid N-type argument. However, if the next $\langle token \rangle$ is for instance `\c_space_token`, the test takes the $\langle false \rangle$ branch, even though the next $\langle token \rangle$ is in fact a valid N-type argument. The $\langle token \rangle$ is left in the input stream after the $\langle true\ code \rangle$ or $\langle false\ code \rangle$ (as appropriate to the result of the test).

Part XXXII

The l3_{uatex} package

LuaTeX-specific functions

1 Breaking out to Lua

The LuaTeX engine provides access to the Lua programming language, and with it access to the “internals” of TeX. In order to use this within the framework provided here, a family of functions is available. When used with pdfTeX or XeTeX these raise an error: use `\sys_if_engine luatex:T` to avoid this. Details on using Lua with the LuaTeX engine are given in the LuaTeX manual.

1.1 TeX code interfaces

<code>\lua_now_x:n</code>	★	<code>\lua_now:n {⟨token list⟩}</code>
---------------------------	---	--

<code>\lua_now:n</code>	★
-------------------------	---

New: 2015-06-29

The *⟨token list⟩* is first tokenized by TeX, which includes converting line ends to spaces in the usual TeX manner and which respects currently-applicable TeX category codes. The resulting *⟨Lua input⟩* is passed to the Lua interpreter for processing. Each `\lua_now:n` block is treated by Lua as a separate chunk. The Lua interpreter executes the *⟨Lua input⟩* immediately, and in an expandable manner.

In the case of the `\lua_now_x:n` version the input is fully expanded by TeX in an x-type manner *but* the function remains fully expandable.

TeXhackers note: `\lua_now_x:n` is a macro wrapper around `\directlua:` when LuaTeX is in use two expansions are required to yield the result of the Lua code.

<code>\lua_shipout_x:n</code>		<code>\lua_shipout:n {⟨token list⟩}</code>
-------------------------------	--	--

<code>\lua_shipout:n</code>

New: 2015-06-30

The *⟨token list⟩* is first tokenized by TeX, which includes converting line ends to spaces in the usual TeX manner and which respects currently-applicable TeX category codes. The resulting *⟨Lua input⟩* is passed to the Lua interpreter when the current page is finalised (*i.e.* at shipout). Each `\lua_shipout:n` block is treated by Lua as a separate chunk. The Lua interpreter will execute the *⟨Lua input⟩* during the page-building routine: no TeX expansion of the *⟨Lua input⟩* will occur at this stage.

In the case of the `\lua_shipout_x:n` version the input is fully expanded by TeX in an x-type manner during the shipout operation.

TeXhackers note: At a TeX level, the *⟨Lua input⟩* is stored as a “whatsit”.

<code>\lua_escape_x:n</code>	★	<code>\lua_escape:n {⟨token list⟩}</code>
------------------------------	---	---

<code>\lua_escape:n</code>	★
----------------------------	---

New: 2015-06-29

Converts the *⟨token list⟩* such that it can safely be passed to Lua: embedded backslashes, double and single quotes, and newlines and carriage returns are escaped. This is done by prepending an extra token consisting of a backslash with category code 12, and for the line endings, converting them to `\n` and `\r`, respectively.

In the case of the `\lua_escape_x:n` version the input is fully expanded by $\mathrm{T}_{\mathrm{E}}\mathrm{X}$ in an *x*-type manner *but* the function remains fully expandable.

$\mathrm{T}_{\mathrm{E}}\mathrm{X}$ hackers note: `\lua_escape_x:n` is a macro wrapper around `\luaescapestring`: when $\mathrm{LuaT}_{\mathrm{E}}\mathrm{X}$ is in use two expansions are required to yield the result of the Lua code.

1.2 Lua interfaces

As well as interfaces for $\mathrm{T}_{\mathrm{E}}\mathrm{X}$, there are a small number of Lua functions provided here. Currently these are intended for internal use only.

<code>l3kernel.charcat</code>	<code>l3kernel.charcat(⟨charcode⟩, ⟨catcode⟩)</code>
-------------------------------	--

Constructs a character of *⟨charcode⟩* and *⟨catcode⟩* and returns the result to $\mathrm{T}_{\mathrm{E}}\mathrm{X}$.

<code>l3kernel.filemdfivesum</code>	<code>l3kernel.filemdfivesum(⟨file⟩)</code>
-------------------------------------	---

Returns the of the MD5 sum of the file contents read as bytes; note that the result will depend on the nature of the line endings used in the file, in contrast to normal $\mathrm{T}_{\mathrm{E}}\mathrm{X}$ behaviour. If the *⟨file⟩* is not found, nothing is returned with *no error raised*.

<code>l3kernel.filemoddate</code>	<code>l3kernel.filemoddate(⟨file⟩)</code>
-----------------------------------	---

Returns the of the date/time of last modification of the *⟨file⟩* in the format `D:⟨year⟩⟨month⟩⟨day⟩⟨hour⟩⟨m` where the latter may be `Z` (UTC) or `⟨plus-minus⟩⟨hours⟩'⟨minutes⟩'`. If the *⟨file⟩* is not found, nothing is returned with *no error raised*.

<code>l3kernel.filesize</code>	<code>l3kernel.filesize(⟨file⟩)</code>
--------------------------------	--

Returns the size of the *⟨file⟩* in bytes. If the *⟨file⟩* is not found, nothing is returned with *no error raised*.

<code>l3kernel.strcmp</code>	<code>l3kernel.strcmp(⟨str one⟩, ⟨str two⟩)</code>
------------------------------	--

Compares the two strings and returns 0 to $\mathrm{T}_{\mathrm{E}}\mathrm{X}$ if the two are identical.

Part XXXIII

The l3drivers package

Drivers

T_EX relies on drivers in order to carry out a number of tasks, such as using color, including graphics and setting up hyper-links. The nature of the code required depends on the exact driver in use. Currently, L^AT_EX3 is aware of the following drivers:

- **pdfmode**: The “driver” for direct PDF output by *both* pdfT_EX and LuaT_EX (no separate driver is used in this case: the engine deals with PDF creation itself).
- **dvips**: The dvips program, which works in conjugation with pdfT_EX or LuaT_EX in DVI mode.
- **dvipdfmx**: The dvipdfmx program, which works in conjugation with pdfT_EX or LuaT_EX in DVI mode.
- **dvisvgm**: The dvisvgm program, which works in conjugation with pdfT_EX or LuaT_EX when run in DVI mode as well as with (u)pT_EX and X_YT_EX.
- **xdvipdfmx**: The driver used by X_YT_EX.

The code here is all very low-level, and should not in general be used outside of the kernel. It is also important to note that many of the functions here are closely tied to the immediate level “up”, and they must be used in the correct contexts.

1 Box clipping

`_driver_box_use_clip:N`

New: 2011-11-11

`_driver_box_use_clip:N <box>`

Inserts the content of the *<box>* at the current insertion point such that any material outside of the bounding box is not displayed by the driver. The material in the *<box>* is still placed in the output stream: the clipping takes place at a driver level.

This function should only be used within a surrounding horizontal box construct.

2 Box rotation and scaling

`_driver_box_use_rotate:Nn`

New: 2016-05-12

`_driver_box_use_rotate:Nn <box> {<angle>}`

Inserts the content of the *<box>* at the current insertion point rotated by the *<angle>* (expressed in degrees). The material is inserted with no apparent height or width, and is rotated such the the T_EX reference point of the box is the center of rotation and remains the reference point after rotation. It is the responsibility of the code using this function to adjust the apparent size of the box to be correct at the T_EX side.

This function should only be used within a surrounding horizontal box construct.

<code>_driver_box_use_scale:Nnn</code>	<code>_driver_box_use_scale:Nnn <box> <x-scale> <y-scale></code>
--	--

New: 2016-05-12

Inserts the content of the $\langle box \rangle$ at the current insertion point scale by the $\langle x-scale \rangle$ and $\langle y-scale \rangle$. The material is inserted with no apparent height or width. It is the responsibility of the code using this function to adjust the apparent size of the box to be correct at the \TeX side.

This function should only be used within a surrounding horizontal box construct.

3 Color support

<code>_driver_color_select:n</code>	<code>_driver_color_select:n <color></code>
--	--

`_driver_color_select:V`

New: 2017-10-25

Selects the $\langle color \rangle$ (which is given in low-level format: a $\langle model \rangle$ followed by a space and one or more space-separated axes).

<code>_driver_color_pickup:N</code>	<code>_driver_color_pickup:N <tl></code>
--	---

New: 2017-10-25

In $\text{\LaTeX 2}_{\epsilon}$ package mode, collects data on the current color from `\current@color` and stores it in the low-level format used by `expl3` in the $\langle tl \rangle$.

4 Drawing

The drawing functions provided here are *highly* experimental. They are inspired heavily by the system layer of `pgf` (most have the same interface as the same functions in the latter's `\pgfsys@... namespace`). They are intended to form the basis for higher level drawing interfaces, which themselves are likely to be further abstracted for user access. Again, this model is heavily inspired by `pgf` and `Tikz`.

These low level drawing interfaces abstract from the driver raw requirements but still require an appreciation of the concepts of PostScript/PDF/SVG graphic creation.

<code>_driver_draw_begin:</code>	<code>_driver_draw_begin:</code>
<code>_driver_draw_end:</code>	$\langle content \rangle$

`_driver_draw_end:`

Defines a drawing environment. This is a scope for the purposes of the graphics state. Depending on the driver, other set up may or may not take place here. The natural size of the $\langle content \rangle$ should be zero from the \TeX perspective: allowance for the size of the content must be made at a higher level (or indeed this can be skipped if the content is to overlap other material).

<code>_driver_draw_scope_begin:</code>	<code>_driver_draw_scope_begin:</code>
<code>_driver_draw_scope_end:</code>	$\langle content \rangle$

`_driver_draw_scope_end:`

Defines a scope for drawing settings and so on. Changes to the graphic state and concepts such as color or linewidth are localised to a scope. This function pair must never be used if an partial path is under construction: such paths must be entirely contained at one unbroken scope level. Note that scopes do not form \TeX groups and may not be aligned with them.

4.1 Path construction

<hr/> <hr/>	<code>__driver_draw_moveto:nn</code>	<code>__driver_draw_move:nn {<x>} {<y>}</code>	Moves the current drawing reference point to $(\langle x \rangle, \langle y \rangle)$; any active transformation matrix applies.
<hr/> <hr/>	<code>__driver_draw_lineto:nn</code>	<code>__driver_draw_lineto:nn {<x>} {<y>}</code>	Adds a path from the current drawing reference point to $(\langle x \rangle, \langle y \rangle)$; any active transformation matrix applies. Note that nothing is drawn until a fill or stroke operation is applied, and that the path may be discarded or used as a clip without appearing itself.
<hr/> <hr/>	<code>__driver_draw_curveto:nnnnnn</code>	<code>__driver_draw_curveto:nnnnnn {<x₁>} {<y₁>} {<x₂>} {<y₂>} {<x₃>} {<y₃>}</code>	Adds a Bezier curve path from the current drawing reference point to $(\langle x_3 \rangle, \langle y_3 \rangle)$, using $(\langle x_1 \rangle, \langle y_1 \rangle)$ and $(\langle x_2 \rangle, \langle y_2 \rangle)$ as control points; any active transformation matrix applies. Note that nothing is drawn until a fill or stroke operation is applied, and that the path may be discarded or used as a clip without appearing itself.
<hr/> <hr/>	<code>__driver_draw_rectangle:nnnn</code>	<code>__driver_draw_rectangle:nnnn {<x>} {<y>} {<width>} {<height>}</code>	Adds rectangular path from $(\langle x_1 \rangle, \langle y_1 \rangle)$ of $\langle height \rangle$ and $\langle width \rangle$; any active transformation matrix applies. Note that nothing is drawn until a fill or stroke operation is applied, and that the path may be discarded or used as a clip without appearing itself.
<hr/> <hr/>	<code>__driver_draw_closepath:</code>		Closes an existing path, adding a line from the current point to the start of path. Note that nothing is drawn until a fill or stroke operation is applied, and that the path may be discarded or used as a clip without appearing itself.

4.2 Stroking and filling

<hr/> <hr/>	<code>__driver_draw_stroke:</code>	<code><path construction></code>	
<hr/> <hr/>	<code>__driver_draw_closestroke:</code>	<code>__driver_draw_stroke:</code>	
			Draws a line along the current path, which is also closed by <code>__driver_draw_closestroke:.</code> The nature of the line drawn is influenced by settings for
			<ul style="list-style-type: none"> • Line thickness • Stroke color (or the current color if no specific stroke color is set) • Line capping (how non-closed line ends should look) • Join style (how a bend in the path should be rendered) • Dash pattern

The path may also be used for clipping.

<code>__driver_draw_fill:</code>	<code><path construction></code>
<code>__driver_draw_fillstroke:</code>	<code>__driver_draw_fill:</code>

Fills the area surrounded by the current path: this will be closed prior to filling if it is not already. The `fillstroke` version also strokes the path as described for `__driver_draw_stroke:`. The fill is influenced by the setting for fill color (or the current color if no specific stroke color is set). The path may also be used for clipping. For paths which are self-intersecting or comprising multiple parts, the determination of which areas are inside the path is made using the non-zero winding number rule unless the even-odd rule is active.

<code>__driver_draw_nonzero_rule:</code>	<code>__driver_draw_nonzero_rule:</code>
<code>__driver_draw_evenodd_rule:</code>	

Active either the non-zero winding number or the even-odd rule, respectively, for determining what is inside a fill or clip area. For technical reasons, these command are not influenced by scoping and apply on an ongoing basis.

<code>__driver_draw_clip:</code>	<code><path construction></code>
<code>__driver_draw_clip:</code>	<code>__driver_draw_clip:</code>

Indicates that the current path should be used for clipping, such that any subsequent material outside of the path (but within the current scope) will not be shown. This command should be given once a path is complete but before it is stroked or filled (if appropriate). This command is *not* affected by scoping: it applies to exactly one path as shown.

<code>__driver_draw_discardpath:</code>	<code><path construction></code>
<code>__driver_draw_discardpath:</code>	<code>__driver_draw_discardpath:</code>

Discards the current path without stroking or filling. This is primarily useful for paths constructed purely for clipping, as this alone does not end the paths existence.

4.3 Stroke options

<code>__driver_draw_linewidth:n</code>	<code>__driver_draw_linewidth:n {<dimexpr>}</code>
---	---

Sets the width to be used for stroking to `<dimexpr>`.

<code>__driver_draw_dash:nn</code>	<code>__driver_draw_dash:nn {<dash pattern>} {<phase>}</code>
-------------------------------------	--

Sets the pattern of dashing to be used when stroking a line. The `<dash pattern>` should be a comma-separated list of dimension expressions. This is then interpreted as a series of pairs of line-on and line-off lengths. For example `3pt, 4pt` means that 3pt on, 4pt off, 3pt on, and so on. A more complex pattern will also repeat: `3pt, 4pt, 1pt, 2pt` results in 3pt on, 4pt off, 1pt on, 2pt off, 3pt on, and so on. An odd number of entries means that the last is repeated, for example `3pt` is equal to `3pt, 3pt`. An empty pattern yields a solid line.

The `<phase>` specifies an offset at the start of the cycle. For example, with a pattern `3pt` a phase of `1pt` means that the output is 2pt on, 3pt off, 3pt on, 3pt on, *etc.*

<code>_driver_draw_cap_butt:</code>	<code>_driver_draw_cap_butt:</code>
<code>_driver_draw_cap_rectangle:</code>	
<code>_driver_draw_cap_round:</code>	

Sets the style of terminal stroke position to one of butt, rectangle or round.

<code>_driver_draw_join_bevel:</code>	<code>_driver_draw_cap_butt:</code>
<code>_driver_draw_join_miter:</code>	Sets the style of stroke joins to one of bevel, miter or round.
<code>_driver_draw_join_round:</code>	

<code>_driver_draw_miterlimit:n</code>	<code>_driver_draw_miterlimit:n {<dimexpr>}</code>
---	---

Sets the miter limit of lines joined as a miter, as described in the PDF and PostScript manuals.

4.4 Color

<code>_driver_draw_color_cmyk:nnnn</code>	<code>_driver_draw_color_cmyk:nnnn {<cyan>} {<magenta>} {<yellow>}</code>
<code>_driver_draw_color_cmyk_fill:nnnn</code>	<code>{<black>}</code>
<code>_driver_draw_color_cmyk_stroke:nnnn</code>	

Sets the color for drawing to the CMYK values specified, all of which are fp expressions which should evaluate to between 0 and 1. The **fill** and **stroke** versions set only the color for those operations. Note that the general setting is more efficient with some drivers so should in most cases be preferred.

<code>_driver_draw_color_gray:n</code>	<code>_driver_draw_color_gray:n {<gray>}</code>
<code>_driver_draw_color_gray_fill:n</code>	
<code>_driver_draw_color_gray_stroke:n</code>	

Sets the color for drawing to the grayscale value specified, which is fp expressions which should evaluate to between 0 and 1. The **fill** and **stroke** versions set only the color for those operations. Note that the general setting is more efficient with some drivers so should in most cases be preferred.

<code>_driver_draw_color_rgb:nnn</code>	<code>_driver_draw_color_rgb:nnn {<red>} {<green>} {<blue>}</code>
<code>_driver_draw_color_rgb_fill:nnn</code>	
<code>_driver_draw_color_rgb_stroke:nnn</code>	

Sets the color for drawing to the RGB values specified, all of which are fp expressions which should evaluate to between 0 and 1. The **fill** and **stroke** versions set only the color for those operations. Note that the general setting is more efficient with some drivers so should in most cases be preferred.

4.5 Inserting T_EX material

```

\__driver_draw_hbox:Nnnnnnn \__driver_draw_hbox:Nnnnnnn <box>
                             {\a}\b}\c}\d}\x}\y}

```

Inserts the $\langle box \rangle$ as an hbox with the box reference point placed at (x, y) . The transformation matrix $[abcd]$ is applied to the box, allowing it to be in synchronisation with any scaling, rotation or skewing applying more generally. Note that T_EX material should not be inserted directly into a drawing as it would not be in the correct location. Also note that as for other drawing elements the box here has no size from a T_EX perspective.

4.6 Coordinate system transformations

```

\__driver_draw_transformcm:nnnnnn \__driver_draw_transformcm:nnnnnn {\a}\b}\c}\d}\
                             {\x}\y}

```

Applies the transformation matrix $[abcd]$ and offset vector (x, y) to the current graphic state. This affects any subsequent items in the same scope but not those already given.

Part XXXIV

Implementation

1 l3bootstrap implementation

```

1 <*initex | package>
2 <@@=kernel>

```

1.1 Format-specific code

The very first thing to do is to bootstrap the iniT_EX system so that everything else will actually work. T_EX does not start with some pretty basic character codes set up.

```

3 <*initex>
4 \catcode '\{ = 1 %
5 \catcode '\} = 2 %
6 \catcode '\# = 6 %
7 \catcode '\^ = 7 %
8 </initex>

```

Tab characters should not show up in the code, but to be on the safe side.

```

9 <*initex>
10 \catcode '\^^I = 10 %
11 </initex>

```

For LuaT_EX, the extra primitives need to be enabled. This is not needed in package mode: common formats have the primitives enabled.

```

12 <*initex>
13 \begingroup\expandafter\expandafter\expandafter\endgroup
14 \expandafter\ifx\curname directlua\endcurname\relax
15 \else
16 \directlua{tex.enableprimitives("", tex.extraprimitives())}%
17 \fi
18 </initex>

```

Depending on the versions available, the L^AT_EX format may not have the raw `\Umath` primitive names available. We fix that globally: it should cause no issues. Older LuaT_EX versions do not have a pre-built table of the primitive names here so sort one out ourselves. These end up globally-defined but at that is true with a newer format anyway and as they all start `\U` this should be reasonably safe.

```

19 \begin{package}
20 \begin{group}
21   \expandafter\ifx\csname directlua\endcsname\relax
22   \else
23     \directlua{%
24       local i
25       local t = { }
26       for _,i in pairs(tex.extraprimitives("luatex")) do
27         if string.match(i,"^U") then
28           if not string.match(i,"^Uchar$") then %$
29             table.insert(t,i)
30           end
31         end
32       end
33       tex.enableprimitives("", t)
34     }%
35   \fi
36 \end{group}
37 \end{package}

```

1.2 The `\pdfstrcmp` primitive in X_YT_EX

Only pdfT_EX has a primitive called `\pdfstrcmp`. The X_YT_EX version is just `\strcmp`, so there is some shuffling to do. As this is still a real primitive, using the pdfT_EX name is “safe”.

```

38 \begin{group}\expandafter\expandafter\expandafter\end{group}
39 \expandafter\ifx\csname pdfstrcmp\endcsname\relax
40   \let\pdfstrcmp\strcmp
41 \fi

```

1.3 Loading support Lua code

When LuaT_EX is used there are various pieces of Lua code which need to be loaded. The code itself is defined in `l3luatex` and is extracted into a separate file. Thus here the task is to load the Lua code both now and (if required) at the start of each job.

```

42 \begin{group}\expandafter\expandafter\expandafter\end{group}
43 \expandafter\ifx\csname directlua\endcsname\relax
44 \else
45   \ifnum\luatexversion<70 %
46   \else

```

In package mode a category code table is needed: either use a pre-loaded allocator or provide one using the L^AT_EX 2_ε-based generic code. In format mode the table used here can be hard-coded into the Lua.

```

47 \begin{package}
48   \begin{group}\expandafter\expandafter\expandafter\end{group}
49   \expandafter\ifx\csname newcatcodetable\endcsname\relax

```

```

50     \input{ltluatex}%
51 \fi
52 \newcatcodetable\ucharcat@table
53 \directlua{
54     l3kernel = l3kernel or { }
55     local charcat_table = \number\ucharcat@table\space
56     l3kernel.charcat_table = charcat_table
57 }%
58 \end{package}
59 \directlua{require("expl3")}%

```

As the user might be making a custom format, no assumption is made about matching package mode with only loading the Lua code once. Instead, a query to Lua reveals what mode is in operation.

```

60 \ifnum 0%
61 \directlua{
62     if status.ini_version then
63         tex.write("1")
64     end
65 }>0 %
66 \everyjob\expandafter{%
67     \the\expandafter\everyjob
68     \csname\detokenize{lua_now_x:n}\endcsname{require("expl3")}%
69 }%
70 \fi
71 \fi
72 \fi

```

1.4 Engine requirements

The code currently requires ϵ -TeX and functionality equivalent to `\pdfstrcmp`, and also driver and Unicode character support. This is available in a reasonably-wide range of engines.

```

73 \begingroup
74 \def\next{\endgroup}%
75 \def\ShortText{Required primitives not found}%
76 \def\LongText%
77 {%
78     LaTeX3 requires the e-TeX primitives and additional functionality as
79     described in the README file.
80     \LineBreak
81     These are available in the engines\LineBreak
82     - pdfTeX v1.40\LineBreak
83     - XeTeX v0.9994\LineBreak
84     - LuaTeX v0.70\LineBreak
85     - e-(u)pTeX mid-2012\LineBreak
86     or later.\LineBreak
87     \LineBreak
88 }%
89 \ifnum0%
90 \expandafter\ifx\csname pdfstrcmp\endcsname\relax
91 \else
92 \expandafter\ifx\csname pdftexversion\endcsname\relax
93     1%

```

```

94     \else
95       \ifnum\pdfTeXversion<140 \else 1\fi
96     \fi
97   \fi
98   \expandafter\ifx\csname directlua\endcsname\relax
99   \else
100     \ifnum\luaTeXversion<70 \else 1\fi
101   \fi
102   =0 %
103   \newlinechar'\^^J %
104 <*\initex>
105   \def\LineBreak{^^J}%
106   \edef\next
107     {%
108     \errhelp
109     {%
110       \LongText
111       For pdfTeX and XeTeX the '-etex' command-line switch is also
112       needed.\LineBreak
113       \LineBreak
114       Format building will abort!\LineBreak
115     }%
116     \errmessage{\ShortText}%
117   \endgroup
118   \noexpand\end
119   }%
120 </\initex>
121 <*\package>
122   \def\LineBreak{\noexpand\MessageBreak}%
123   \expandafter\ifx\csname PackageError\endcsname\relax
124     \def\LineBreak{^^J}%
125     \def\PackageError#1#2#3%
126       {%
127         \errhelp{#3}%
128         \errmessage{#1 Error: #2}%
129       }%
130   \fi
131   \edef\next
132     {%
133     \noexpand\PackageError{expl3}{\ShortText}
134     {\LongText Loading of expl3 will abort!}%
135   \endgroup
136   \noexpand\endinput
137   }%
138 </\package>
139   \fi
140 \next

```

1.5 Extending allocators

In format mode, allocating registers is handled by `l3alloc`. However, in package mode it's much safer to rely on more general code. For example, the ability to extend \TeX 's allocation routine to allow for $\varepsilon\text{-}\TeX$ has been around since 1997 in the `etex` package.

Loading this support is delayed until here as we are now sure that the ε -TeX extensions and `\pdfstrcmp` or equivalent are available. Thus there is no danger of an “uncontrolled” error if the engine requirements are not met.

For $\text{\LaTeX}2_{\varepsilon}$ we need to make sure that the extended pool is being used: `expl3` uses a lot of registers. For formats from 2015 onward there is nothing to do as this is automatic. For older formats, the `etex` package needs to be loaded to do the job. In that case, some inserts are reserved also as these have to be from the standard pool. Note that `\reserveinserts` is `\outer` and so is accessed here by `csname`. In earlier versions, loading `etex` was done directly and so `\reserveinserts` appeared in the code: this then required a `\relax` after `\RequirePackage` to prevent an error with “unsafe” definitions as seen for example with `capoptions`. The optional loading here is done using a group and `\ifx` test as we are not quite in the position to have a single name for `\pdfstrcmp` just yet.

```

141 <*package>
142 \begingroup
143   \def\@tempa{LaTeX2e}%
144   \def\next{}%
145   \ifx\fmtname\@tempa
146     \expandafter\ifx\csname extrafloats\endcsname\relax
147       \def\next
148         {%
149           \RequirePackage{etex}%
150           \csname reserveinserts\endcsname{32}%
151         }%
152     \fi
153   \fi
154 \expandafter\endgroup
155 \next
156 </package>

```

1.6 Character data

TeX needs various pieces of data to be set about characters, in particular which ones to treat as letters and which `\lccode` values apply as these affect hyphenation. It makes most sense to set this and related information up in one place. Whilst for \LaTeX hyphenation patterns can be read anywhere, other engines have to build them into the format and so we *must* do this set up before reading the patterns. For the Unicode engines, there are shared loaders available to obtain the relevant information directly from the Unicode Consortium data files. These need standard (Ini)TeX category codes and primitive availability and must therefore be loaded *very* early. This has a knock-on effect on the 8-bit set up: it makes sense to do the definitions for those here as well so it is all in one place.

For \XeTeX and \LuaTeX , which are natively Unicode engines, simply load the Unicode data.

```

157 <*initex>
158 \ifdefined\Umathcode
159   \input load-unicode-data %
160   \input load-unicode-math-classes %
161 \else

```

For the 8-bit engines a font encoding scheme must be chosen. At present, this is the EC (T1) scheme, with the assumption that languages for which this is not appropriate will be used with one of the Unicode engines.

```
162 \begingroup
```

Lower case chars: map to themselves when lower casing and down by "20 when upper casing. (The characters a–z are set up correctly by IniT_EX.)

```
163 \def\temp{%
164   \ifnum\count0>\count2 %
165   \else
166     \global\lccode\count0 = \count0 %
167     \global\uccode\count0 = \numexpr\count0 - "20\relax
168     \advance\count0 by 1 %
169     \expandafter\temp
170   \fi
171 }
172 \count0 = "A0 %
173 \count2 = "BC %
174 \temp
175 \count0 = "E0 %
176 \count2 = "FF %
177 \temp
```

Upper case chars: map up by "20 when lower casing, to themselves when upper casing and require an \sfcode of 999. (The characters A–Z are set up correctly by IniT_EX.)

```
178 \def\temp{%
179   \ifnum\count0>\count2 %
180   \else
181     \global\lccode\count0 = \numexpr\count0 + "20\relax
182     \global\uccode\count0 = \count0 %
183     \global\sfcode\count0 = 999 %
184     \advance\count0 by 1 %
185     \expandafter\temp
186   \fi
187 }
188 \count0 = "80 %
189 \count2 = "9C %
190 \temp
191 \count0 = "C0 %
192 \count2 = "DF %
193 \temp
```

A few special cases where things are not as one might expect using the above pattern: dotless-I, dotless-J, dotted-I and d-bar.

```
194 \global\lccode'\^Y = '\^Y %
195 \global\uccode'\^Y = '\I %
196 \global\lccode'\^Z = '\^Z %
197 \global\uccode'\^Y = '\J %
198 \global\lccode"9D = '\i %
199 \global\uccode"9D = "9D %
200 \global\lccode"9E = "9E %
201 \global\uccode"9E = "D0 %
```

Allow hyphenation at a zero-width glyph (used to break up ligatures or to place accents between characters).


```

202 \global\lccode23 = 23 %
203 \endgroup
204 \fi

```

In all cases it makes sense to set up - to map to itself: this allows hyphenation of the rest of a word following it (suggested by Lars Helström).

```

205 \global\lccode'\- = '\- %
206 \</initex>

```

1.7 The L^AT_EX3 code environment

The code environment is now set up.

\ExplSyntaxOff Before changing any category codes, in package mode we need to save the situation before loading. Note the set up here means that once applied \ExplSyntaxOff becomes a “do nothing” command until \ExplSyntaxOn is used. For format mode, there is no need to save category codes so that step is skipped.

```

207 \protected\def\ExplSyntaxOff{}%
208 (*package)
209 \protected\edef\ExplSyntaxOff
210 {%
211   \protected\def\ExplSyntaxOff{}%
212   \catcode 9 = \the\catcode 9\relax
213   \catcode 32 = \the\catcode 32\relax
214   \catcode 34 = \the\catcode 34\relax
215   \catcode 38 = \the\catcode 38\relax
216   \catcode 58 = \the\catcode 58\relax
217   \catcode 94 = \the\catcode 94\relax
218   \catcode 95 = \the\catcode 95\relax
219   \catcode 124 = \the\catcode 124\relax
220   \catcode 126 = \the\catcode 126\relax
221   \endlinechar = \the\endlinechar\relax
222   \chardef\csname\detokenize{l__kernel_expl_bool}\endcsname = 0\relax
223 }%
224 \</package>

```

(End definition for \ExplSyntaxOff. This function is documented on page 6.)

The code environment is now set up.

```

225 \catcode 9 = 9\relax
226 \catcode 32 = 9\relax
227 \catcode 34 = 12\relax
228 \catcode 38 = 4\relax
229 \catcode 58 = 11\relax
230 \catcode 94 = 7\relax
231 \catcode 95 = 11\relax
232 \catcode 124 = 12\relax
233 \catcode 126 = 10\relax
234 \endlinechar = 32\relax

```

\l__kernel_expl_bool The status for experimental code syntax: this is on at present.

```

235 \chardef\l__kernel_expl_bool = 1\relax

```

(End definition for \l__kernel_expl_bool.)

\ExplSyntaxOn The idea here is that multiple `\ExplSyntaxOn` calls are not going to mess up category codes, and that multiple calls to `\ExplSyntaxOff` are also not wasting time. Applying `\ExplSyntaxOn` alters the definition of `\ExplSyntaxOff` and so in package mode this function should not be used until after the end of the loading process!

```

236 \protected \def \ExplSyntaxOn
237 {
238   \bool_if:NF \l__kernel_expl_bool
239   {
240     \cs_set_protected:Npx \ExplSyntaxOff
241     {
242       \char_set_catcode:nn { 9 } { \char_value_catcode:n { 9 } }
243       \char_set_catcode:nn { 32 } { \char_value_catcode:n { 32 } }
244       \char_set_catcode:nn { 34 } { \char_value_catcode:n { 34 } }
245       \char_set_catcode:nn { 38 } { \char_value_catcode:n { 38 } }
246       \char_set_catcode:nn { 58 } { \char_value_catcode:n { 58 } }
247       \char_set_catcode:nn { 94 } { \char_value_catcode:n { 94 } }
248       \char_set_catcode:nn { 95 } { \char_value_catcode:n { 95 } }
249       \char_set_catcode:nn { 124 } { \char_value_catcode:n { 124 } }
250       \char_set_catcode:nn { 126 } { \char_value_catcode:n { 126 } }
251       \tex_endlinechar:D =
252         \tex_the:D \tex_endlinechar:D \scan_stop:
253       \bool_set_false:N \l__kernel_expl_bool
254       \cs_set_protected:Npn \ExplSyntaxOff { }
255     }
256   }
257   \char_set_catcode_ignore:n { 9 } % tab
258   \char_set_catcode_ignore:n { 32 } % space
259   \char_set_catcode_other:n { 34 } % double quote
260   \char_set_catcode_alignment:n { 38 } % ampersand
261   \char_set_catcode_letter:n { 58 } % colon
262   \char_set_catcode_math_superscript:n { 94 } % circumflex
263   \char_set_catcode_letter:n { 95 } % underscore
264   \char_set_catcode_other:n { 124 } % pipe
265   \char_set_catcode_space:n { 126 } % tilde
266   \tex_endlinechar:D = 32 \scan_stop:
267   \bool_set_true:N \l__kernel_expl_bool
268 }

```

(End definition for `\ExplSyntaxOn`. This function is documented on page 6.)

```

269 \</initex | package>

```

2 l3names implementation

```

270 \<*initex | package>

```

The prefix here is `kernel`. A few places need `@@` to be left as is; this is obtained as `@@@`.

```

271 \<@@=kernel>

```

The code here simply renames all of the primitives to new, internal, names. In format mode, it also deletes all of the existing names (although some do come back later).

`\tex_undefined:D` This function does not exist at all, but is the name used by the plain T_EX format for an undefined function. So it should be marked here as “taken”.

(End definition for `\tex_undefined:D`. This function is documented on page ??.)

The `\let` primitive is renamed by hand first as it is essential for the entire process to follow. This also uses `\global`, as that way we avoid leaving an unneeded csname in the hash table.

```
272 \let \tex_global:D \global
273 \let \tex_let:D \let
```

Everything is inside a (rather long) group, which keeps `__kernel_primitive:NN` trapped.

```
274 \begingroup
```

`__kernel_primitive:NN` A temporary function to actually do the renaming. This also allows the original names to be removed in format mode.

```
275 \long \def \__kernel_primitive:NN #1#2
276 {
277   \tex_global:D \tex_let:D #2 #1
278   \*initex
279   \tex_global:D \tex_let:D #1 \tex_undefined:D
280   \*initex
281 }
```

(End definition for `__kernel_primitive:NN`.)

To allow extracting “just the names”, a bit of DocStrip fiddling.

```
282 \*initex | package)
283 \*initex | names | package)
```

In the current incarnation of this package, all \TeX primitives are given a new name of the form `\tex_oldname:D`. But first three special cases which have symbolic original names. These are given modified new names, so that they may be entered without catcode tricks.

```
284 \__kernel_primitive:NN \tex_space:D
285 \__kernel_primitive:NN \tex_italiccorrection:D
286 \__kernel_primitive:NN \tex_hyphen:D
```

Now all the other primitives.

```
287 \__kernel_primitive:NN \tex_above:D
288 \__kernel_primitive:NN \tex_abovedisplayshortskip:D
289 \__kernel_primitive:NN \tex_abovedisplayskip:D
290 \__kernel_primitive:NN \tex_abovewithdelims:D
291 \__kernel_primitive:NN \tex_accent:D
292 \__kernel_primitive:NN \tex_adjdemerits:D
293 \__kernel_primitive:NN \tex_advance:D
294 \__kernel_primitive:NN \tex_afterassignment:D
295 \__kernel_primitive:NN \tex_aftergroup:D
296 \__kernel_primitive:NN \tex_atop:D
297 \__kernel_primitive:NN \tex_atopwithdelims:D
298 \__kernel_primitive:NN \tex_badness:D
299 \__kernel_primitive:NN \tex_baselineskip:D
300 \__kernel_primitive:NN \tex_batchmode:D
301 \__kernel_primitive:NN \tex_begingroup:D
302 \__kernel_primitive:NN \tex_belowdisplayshortskip:D
303 \__kernel_primitive:NN \tex_belowdisplayskip:D
304 \__kernel_primitive:NN \tex_binoppenalty:D
305 \__kernel_primitive:NN \tex_botmark:D
```

306	_kernel_primitive:NN \box	\tex_box:D
307	_kernel_primitive:NN \boxmaxdepth	\tex_boxmaxdepth:D
308	_kernel_primitive:NN \brokenpenalty	\tex_brokenpenalty:D
309	_kernel_primitive:NN \catcode	\tex_catcode:D
310	_kernel_primitive:NN \char	\tex_char:D
311	_kernel_primitive:NN \chardef	\tex_chardef:D
312	_kernel_primitive:NN \cleaders	\tex_cleaders:D
313	_kernel_primitive:NN \closein	\tex_closein:D
314	_kernel_primitive:NN \closeout	\tex_closeout:D
315	_kernel_primitive:NN \clubpenalty	\tex_clubpenalty:D
316	_kernel_primitive:NN \copy	\tex_copy:D
317	_kernel_primitive:NN \count	\tex_count:D
318	_kernel_primitive:NN \countdef	\tex_countdef:D
319	_kernel_primitive:NN \cr	\tex_cr:D
320	_kernel_primitive:NN \crrcr	\tex_crrcr:D
321	_kernel_primitive:NN \csname	\tex_csname:D
322	_kernel_primitive:NN \day	\tex_day:D
323	_kernel_primitive:NN \deadcycles	\tex_deadcycles:D
324	_kernel_primitive:NN \def	\tex_def:D
325	_kernel_primitive:NN \defaultthyphenchar	\tex_defaultthyphenchar:D
326	_kernel_primitive:NN \defaultskewchar	\tex_defaultskewchar:D
327	_kernel_primitive:NN \delcode	\tex_delcode:D
328	_kernel_primitive:NN \delimiter	\tex_delimiter:D
329	_kernel_primitive:NN \delimiterfactor	\tex_delimiterfactor:D
330	_kernel_primitive:NN \delimitershortfall	\tex_delimitershortfall:D
331	_kernel_primitive:NN \dimen	\tex_dimen:D
332	_kernel_primitive:NN \dimendef	\tex_dimendef:D
333	_kernel_primitive:NN \discretionary	\tex_discretionary:D
334	_kernel_primitive:NN \displayindent	\tex_displayindent:D
335	_kernel_primitive:NN \displaylimits	\tex_displaylimits:D
336	_kernel_primitive:NN \displaystyle	\tex_displaystyle:D
337	_kernel_primitive:NN \displaywidowpenalty	\tex_displaywidowpenalty:D
338	_kernel_primitive:NN \displaywidth	\tex_displaywidth:D
339	_kernel_primitive:NN \divide	\tex_divide:D
340	_kernel_primitive:NN \doublehyphendemerits	\tex_doublehyphendemerits:D
341	_kernel_primitive:NN \dp	\tex_dp:D
342	_kernel_primitive:NN \dump	\tex_dump:D
343	_kernel_primitive:NN \edef	\tex_edef:D
344	_kernel_primitive:NN \else	\tex_else:D
345	_kernel_primitive:NN \emergencystretch	\tex_emergencystretch:D
346	_kernel_primitive:NN \end	\tex_end:D
347	_kernel_primitive:NN \endcsname	\tex_endcsname:D
348	_kernel_primitive:NN \endgroup	\tex_endgroup:D
349	_kernel_primitive:NN \endinput	\tex_endinput:D
350	_kernel_primitive:NN \endlinechar	\tex_endlinechar:D
351	_kernel_primitive:NN \eqno	\tex_eqno:D
352	_kernel_primitive:NN \errhelp	\tex_errhelp:D
353	_kernel_primitive:NN \errmessage	\tex_errmessage:D
354	_kernel_primitive:NN \errorcontextlines	\tex_errorcontextlines:D
355	_kernel_primitive:NN \errorstopmode	\tex_errorstopmode:D
356	_kernel_primitive:NN \escapechar	\tex_escapechar:D
357	_kernel_primitive:NN \everycr	\tex_everycr:D
358	_kernel_primitive:NN \everydisplay	\tex_everydisplay:D
359	_kernel_primitive:NN \everyhbox	\tex_everyhbox:D

360	_kernel_primitive:NN	\everyjob	\tex_everyjob:D
361	_kernel_primitive:NN	\everymath	\tex_everymath:D
362	_kernel_primitive:NN	\everypar	\tex_everypar:D
363	_kernel_primitive:NN	\everyvbox	\tex_everyvbox:D
364	_kernel_primitive:NN	\exhyphenpenalty	\tex_exhyphenpenalty:D
365	_kernel_primitive:NN	\expandafter	\tex_expandafter:D
366	_kernel_primitive:NN	\fam	\tex_fam:D
367	_kernel_primitive:NN	\fi	\tex_fi:D
368	_kernel_primitive:NN	\finalhyphendemerits	\tex_finalhyphendemerits:D
369	_kernel_primitive:NN	\firstmark	\tex_firstmark:D
370	_kernel_primitive:NN	\floatingpenalty	\tex_floatingpenalty:D
371	_kernel_primitive:NN	\font	\tex_font:D
372	_kernel_primitive:NN	\fontdimen	\tex_fontdimen:D
373	_kernel_primitive:NN	\fontname	\tex_fontname:D
374	_kernel_primitive:NN	\futurelet	\tex_futurelet:D
375	_kernel_primitive:NN	\gdef	\tex_gdef:D
376	_kernel_primitive:NN	\global	\tex_global:D
377	_kernel_primitive:NN	\globaldefs	\tex_globaldefs:D
378	_kernel_primitive:NN	\halign	\tex_halign:D
379	_kernel_primitive:NN	\hangafter	\tex_hangafter:D
380	_kernel_primitive:NN	\hangindent	\tex_hangindent:D
381	_kernel_primitive:NN	\hbadness	\tex_hbadness:D
382	_kernel_primitive:NN	\hbox	\tex_hbox:D
383	_kernel_primitive:NN	\hfil	\tex_hfil:D
384	_kernel_primitive:NN	\hfill	\tex_hfill:D
385	_kernel_primitive:NN	\hfilneg	\tex_hfilneg:D
386	_kernel_primitive:NN	\hfuzz	\tex_hfuzz:D
387	_kernel_primitive:NN	\hoffset	\tex_hoffset:D
388	_kernel_primitive:NN	\holdinginserts	\tex_holdinginserts:D
389	_kernel_primitive:NN	\hrule	\tex_hrule:D
390	_kernel_primitive:NN	\hsize	\tex_hsize:D
391	_kernel_primitive:NN	\hskip	\tex_hskip:D
392	_kernel_primitive:NN	\hss	\tex_hss:D
393	_kernel_primitive:NN	\ht	\tex_ht:D
394	_kernel_primitive:NN	\hyphenation	\tex_hyphenation:D
395	_kernel_primitive:NN	\hyphenchar	\tex_hyphenchar:D
396	_kernel_primitive:NN	\hyphenpenalty	\tex_hyphenpenalty:D
397	_kernel_primitive:NN	\if	\tex_if:D
398	_kernel_primitive:NN	\ifcase	\tex_ifcase:D
399	_kernel_primitive:NN	\ifcat	\tex_ifcat:D
400	_kernel_primitive:NN	\ifdim	\tex_ifdim:D
401	_kernel_primitive:NN	\ifeof	\tex_ifeof:D
402	_kernel_primitive:NN	\iffalse	\tex_iffalse:D
403	_kernel_primitive:NN	\ifhbox	\tex_ifhbox:D
404	_kernel_primitive:NN	\ifhmode	\tex_ifhmode:D
405	_kernel_primitive:NN	\ifinner	\tex_ifinner:D
406	_kernel_primitive:NN	\ifmmode	\tex_ifmmode:D
407	_kernel_primitive:NN	\ifnum	\tex_ifnum:D
408	_kernel_primitive:NN	\ifodd	\tex_ifodd:D
409	_kernel_primitive:NN	\iftrue	\tex_iftrue:D
410	_kernel_primitive:NN	\ifvbox	\tex_ifvbox:D
411	_kernel_primitive:NN	\ifvmode	\tex_ifvmode:D
412	_kernel_primitive:NN	\ifvoid	\tex_ifvoid:D
413	_kernel_primitive:NN	\ifx	\tex_ifx:D

414	<code>_kernel_primitive:NN \ignorespaces</code>	<code>\tex_ignorespaces:D</code>
415	<code>_kernel_primitive:NN \immediate</code>	<code>\tex_immediate:D</code>
416	<code>_kernel_primitive:NN \indent</code>	<code>\tex_indent:D</code>
417	<code>_kernel_primitive:NN \input</code>	<code>\tex_input:D</code>
418	<code>_kernel_primitive:NN \inputlineno</code>	<code>\tex_inputlineno:D</code>
419	<code>_kernel_primitive:NN \insert</code>	<code>\tex_insert:D</code>
420	<code>_kernel_primitive:NN \insertpenalties</code>	<code>\tex_insertpenalties:D</code>
421	<code>_kernel_primitive:NN \interlinepenalty</code>	<code>\tex_interlinepenalty:D</code>
422	<code>_kernel_primitive:NN \jobname</code>	<code>\tex_jobname:D</code>
423	<code>_kernel_primitive:NN \kern</code>	<code>\tex_kern:D</code>
424	<code>_kernel_primitive:NN \language</code>	<code>\tex_language:D</code>
425	<code>_kernel_primitive:NN \lastbox</code>	<code>\tex_lastbox:D</code>
426	<code>_kernel_primitive:NN \lastkern</code>	<code>\tex_lastkern:D</code>
427	<code>_kernel_primitive:NN \lastpenalty</code>	<code>\tex_lastpenalty:D</code>
428	<code>_kernel_primitive:NN \lastskip</code>	<code>\tex_lastskip:D</code>
429	<code>_kernel_primitive:NN \lccode</code>	<code>\tex_lccode:D</code>
430	<code>_kernel_primitive:NN \leaders</code>	<code>\tex_leaders:D</code>
431	<code>_kernel_primitive:NN \left</code>	<code>\tex_left:D</code>
432	<code>_kernel_primitive:NN \lefthyphenmin</code>	<code>\tex_lefthyphenmin:D</code>
433	<code>_kernel_primitive:NN \leftskip</code>	<code>\tex_leftskip:D</code>
434	<code>_kernel_primitive:NN \leqno</code>	<code>\tex_leqno:D</code>
435	<code>_kernel_primitive:NN \let</code>	<code>\tex_let:D</code>
436	<code>_kernel_primitive:NN \limits</code>	<code>\tex_limits:D</code>
437	<code>_kernel_primitive:NN \linepenalty</code>	<code>\tex_linepenalty:D</code>
438	<code>_kernel_primitive:NN \lineskip</code>	<code>\tex_lineskip:D</code>
439	<code>_kernel_primitive:NN \lineskiplimit</code>	<code>\tex_lineskiplimit:D</code>
440	<code>_kernel_primitive:NN \long</code>	<code>\tex_long:D</code>
441	<code>_kernel_primitive:NN \looseness</code>	<code>\tex_looseness:D</code>
442	<code>_kernel_primitive:NN \lower</code>	<code>\tex_lower:D</code>
443	<code>_kernel_primitive:NN \lowercase</code>	<code>\tex_lowercase:D</code>
444	<code>_kernel_primitive:NN \mag</code>	<code>\tex_mag:D</code>
445	<code>_kernel_primitive:NN \mark</code>	<code>\tex_mark:D</code>
446	<code>_kernel_primitive:NN \mathaccent</code>	<code>\tex_mathaccent:D</code>
447	<code>_kernel_primitive:NN \mathbin</code>	<code>\tex_mathbin:D</code>
448	<code>_kernel_primitive:NN \mathchar</code>	<code>\tex_mathchar:D</code>
449	<code>_kernel_primitive:NN \mathchardef</code>	<code>\tex_mathchardef:D</code>
450	<code>_kernel_primitive:NN \mathchoice</code>	<code>\tex_mathchoice:D</code>
451	<code>_kernel_primitive:NN \mathclose</code>	<code>\tex_mathclose:D</code>
452	<code>_kernel_primitive:NN \mathcode</code>	<code>\tex_mathcode:D</code>
453	<code>_kernel_primitive:NN \mathinner</code>	<code>\tex_mathinner:D</code>
454	<code>_kernel_primitive:NN \mathop</code>	<code>\tex_mathop:D</code>
455	<code>_kernel_primitive:NN \mathopen</code>	<code>\tex_mathopen:D</code>
456	<code>_kernel_primitive:NN \mathord</code>	<code>\tex_mathord:D</code>
457	<code>_kernel_primitive:NN \mathpunct</code>	<code>\tex_mathpunct:D</code>
458	<code>_kernel_primitive:NN \mathrel</code>	<code>\tex_mathrel:D</code>
459	<code>_kernel_primitive:NN \mathsurround</code>	<code>\tex_mathsurround:D</code>
460	<code>_kernel_primitive:NN \maxdeadcycles</code>	<code>\tex_maxdeadcycles:D</code>
461	<code>_kernel_primitive:NN \maxdepth</code>	<code>\tex_maxdepth:D</code>
462	<code>_kernel_primitive:NN \meaning</code>	<code>\tex_meaning:D</code>
463	<code>_kernel_primitive:NN \medmuskip</code>	<code>\tex_medmuskip:D</code>
464	<code>_kernel_primitive:NN \message</code>	<code>\tex_message:D</code>
465	<code>_kernel_primitive:NN \mkern</code>	<code>\tex_mkern:D</code>
466	<code>_kernel_primitive:NN \month</code>	<code>\tex_month:D</code>
467	<code>_kernel_primitive:NN \moveleft</code>	<code>\tex_moveleft:D</code>

468	_kernel_primitive:NN	\moveright	\tex_moveright:D
469	_kernel_primitive:NN	\mskip	\tex_mskip:D
470	_kernel_primitive:NN	\multiply	\tex_multiply:D
471	_kernel_primitive:NN	\muskip	\tex_muskip:D
472	_kernel_primitive:NN	\muskipdef	\tex_muskipdef:D
473	_kernel_primitive:NN	\newlinechar	\tex_newlinechar:D
474	_kernel_primitive:NN	\noalign	\tex_noalign:D
475	_kernel_primitive:NN	\noboundary	\tex_noboundary:D
476	_kernel_primitive:NN	\noexpand	\tex_noexpand:D
477	_kernel_primitive:NN	\noindent	\tex_noindent:D
478	_kernel_primitive:NN	\nolimits	\tex_nolimits:D
479	_kernel_primitive:NN	\nonscript	\tex_nonscript:D
480	_kernel_primitive:NN	\nonstopmode	\tex_nonstopmode:D
481	_kernel_primitive:NN	\nulldelimiterspace	\tex_nulldelimiterspace:D
482	_kernel_primitive:NN	\nullfont	\tex_nullfont:D
483	_kernel_primitive:NN	\number	\tex_number:D
484	_kernel_primitive:NN	\omit	\tex_omit:D
485	_kernel_primitive:NN	\openin	\tex_openin:D
486	_kernel_primitive:NN	\openout	\tex_openout:D
487	_kernel_primitive:NN	\or	\tex_or:D
488	_kernel_primitive:NN	\outer	\tex_outer:D
489	_kernel_primitive:NN	\output	\tex_output:D
490	_kernel_primitive:NN	\outputpenalty	\tex_outputpenalty:D
491	_kernel_primitive:NN	\over	\tex_over:D
492	_kernel_primitive:NN	\overfullrule	\tex_overfullrule:D
493	_kernel_primitive:NN	\overline	\tex_overline:D
494	_kernel_primitive:NN	\overwithdelims	\tex_overwithdelims:D
495	_kernel_primitive:NN	\pagedepth	\tex_pagedepth:D
496	_kernel_primitive:NN	\pagefilllstretch	\tex_pagefilllstretch:D
497	_kernel_primitive:NN	\pagefillstretch	\tex_pagefillstretch:D
498	_kernel_primitive:NN	\pagefilstretch	\tex_pagefilstretch:D
499	_kernel_primitive:NN	\pagegoal	\tex_pagegoal:D
500	_kernel_primitive:NN	\pageshrink	\tex_pageshrink:D
501	_kernel_primitive:NN	\pagestretch	\tex_pagestretch:D
502	_kernel_primitive:NN	\pagetotal	\tex_pagetotal:D
503	_kernel_primitive:NN	\par	\tex_par:D
504	_kernel_primitive:NN	\parfillskip	\tex_parfillskip:D
505	_kernel_primitive:NN	\parindent	\tex_parindent:D
506	_kernel_primitive:NN	\parshape	\tex_parshape:D
507	_kernel_primitive:NN	\parskip	\tex_parskip:D
508	_kernel_primitive:NN	\patterns	\tex_patterns:D
509	_kernel_primitive:NN	\pausing	\tex_pausing:D
510	_kernel_primitive:NN	\penalty	\tex_penalty:D
511	_kernel_primitive:NN	\postdisplaypenalty	\tex_postdisplaypenalty:D
512	_kernel_primitive:NN	\predisdisplaypenalty	\tex_predisdisplaypenalty:D
513	_kernel_primitive:NN	\predisplaysize	\tex_predisplaysize:D
514	_kernel_primitive:NN	\pretolerance	\tex_pretolerance:D
515	_kernel_primitive:NN	\prevdepth	\tex_prevdepth:D
516	_kernel_primitive:NN	\prevgraf	\tex_prevgraf:D
517	_kernel_primitive:NN	\radical	\tex_radical:D
518	_kernel_primitive:NN	\raise	\tex_raise:D
519	_kernel_primitive:NN	\read	\tex_read:D
520	_kernel_primitive:NN	\relax	\tex_relax:D
521	_kernel_primitive:NN	\relpenalty	\tex_relpenalty:D

522	_kernel_primitive:NN	\right	\tex_right:D
523	_kernel_primitive:NN	\righthypenmin	\tex_righthypenmin:D
524	_kernel_primitive:NN	\rightskip	\tex_rightskip:D
525	_kernel_primitive:NN	\romannumeral	\tex_romannumeral:D
526	_kernel_primitive:NN	\scriptfont	\tex_scriptfont:D
527	_kernel_primitive:NN	\scriptscriptfont	\tex_scriptscriptfont:D
528	_kernel_primitive:NN	\scriptscriptstyle	\tex_scriptscriptstyle:D
529	_kernel_primitive:NN	\scriptspace	\tex_scriptspace:D
530	_kernel_primitive:NN	\scriptstyle	\tex_scriptstyle:D
531	_kernel_primitive:NN	\scrollmode	\tex_scrollmode:D
532	_kernel_primitive:NN	\setbox	\tex_setbox:D
533	_kernel_primitive:NN	\setlanguage	\tex_setlanguage:D
534	_kernel_primitive:NN	\sfcode	\tex_sfcode:D
535	_kernel_primitive:NN	\shipout	\tex_shipout:D
536	_kernel_primitive:NN	\show	\tex_show:D
537	_kernel_primitive:NN	\showbox	\tex_showbox:D
538	_kernel_primitive:NN	\showboxbreadth	\tex_showboxbreadth:D
539	_kernel_primitive:NN	\showboxdepth	\tex_showboxdepth:D
540	_kernel_primitive:NN	\showlists	\tex_showlists:D
541	_kernel_primitive:NN	\showthe	\tex_showthe:D
542	_kernel_primitive:NN	\skewchar	\tex_skewchar:D
543	_kernel_primitive:NN	\skip	\tex_skip:D
544	_kernel_primitive:NN	\skipdef	\tex_skipdef:D
545	_kernel_primitive:NN	\spacefactor	\tex_spacefactor:D
546	_kernel_primitive:NN	\spaceskip	\tex_spaceskip:D
547	_kernel_primitive:NN	\span	\tex_span:D
548	_kernel_primitive:NN	\special	\tex_special:D
549	_kernel_primitive:NN	\splitbotmark	\tex_splitbotmark:D
550	_kernel_primitive:NN	\splitfirstmark	\tex_splitfirstmark:D
551	_kernel_primitive:NN	\splitmaxdepth	\tex_splitmaxdepth:D
552	_kernel_primitive:NN	\splittopskip	\tex_splittopskip:D
553	_kernel_primitive:NN	\string	\tex_string:D
554	_kernel_primitive:NN	\tabskip	\tex_tabskip:D
555	_kernel_primitive:NN	\textfont	\tex_textfont:D
556	_kernel_primitive:NN	\textstyle	\tex_textstyle:D
557	_kernel_primitive:NN	\the	\tex_the:D
558	_kernel_primitive:NN	\thickmuskip	\tex_thickmuskip:D
559	_kernel_primitive:NN	\thinmuskip	\tex_thinmuskip:D
560	_kernel_primitive:NN	\time	\tex_time:D
561	_kernel_primitive:NN	\toks	\tex_toks:D
562	_kernel_primitive:NN	\toksdef	\tex_toksdef:D
563	_kernel_primitive:NN	\tolerance	\tex_tolerance:D
564	_kernel_primitive:NN	\topmark	\tex_topmark:D
565	_kernel_primitive:NN	\topskip	\tex_topskip:D
566	_kernel_primitive:NN	\tracingcommands	\tex_tracingcommands:D
567	_kernel_primitive:NN	\tracinglostchars	\tex_tracinglostchars:D
568	_kernel_primitive:NN	\tracingmacros	\tex_tracingmacros:D
569	_kernel_primitive:NN	\tracingonline	\tex_tracingonline:D
570	_kernel_primitive:NN	\tracingoutput	\tex_tracingoutput:D
571	_kernel_primitive:NN	\tracingpages	\tex_tracingpages:D
572	_kernel_primitive:NN	\tracingparagraphs	\tex_tracingparagraphs:D
573	_kernel_primitive:NN	\tracingrestores	\tex_tracingrestores:D
574	_kernel_primitive:NN	\tracingstats	\tex_tracingstats:D
575	_kernel_primitive:NN	\uccode	\tex_uccode:D

576	__kernel_primitive:NN	\uchyph	\tex_uchyph:D
577	__kernel_primitive:NN	\underline	\tex_underline:D
578	__kernel_primitive:NN	\unhbox	\tex_unhbox:D
579	__kernel_primitive:NN	\unhcopy	\tex_unhcopy:D
580	__kernel_primitive:NN	\unkern	\tex_unkern:D
581	__kernel_primitive:NN	\unpenalty	\tex_unpenalty:D
582	__kernel_primitive:NN	\unskip	\tex_unskip:D
583	__kernel_primitive:NN	\unvbox	\tex_unvbox:D
584	__kernel_primitive:NN	\unvcopy	\tex_unvcopy:D
585	__kernel_primitive:NN	\uppercase	\tex_uppercase:D
586	__kernel_primitive:NN	\vadjust	\tex_vadjust:D
587	__kernel_primitive:NN	\valign	\tex_valign:D
588	__kernel_primitive:NN	\vbadness	\tex_vbadness:D
589	__kernel_primitive:NN	\vbox	\tex_vbox:D
590	__kernel_primitive:NN	\vcenter	\tex_vcenter:D
591	__kernel_primitive:NN	\vfil	\tex_vfil:D
592	__kernel_primitive:NN	\vfill	\tex_vfill:D
593	__kernel_primitive:NN	\vfилneg	\tex_vfilneg:D
594	__kernel_primitive:NN	\vfuzz	\tex_vfuzz:D
595	__kernel_primitive:NN	\voffset	\tex_voffset:D
596	__kernel_primitive:NN	\vrule	\tex_vrule:D
597	__kernel_primitive:NN	\vsize	\tex_vsize:D
598	__kernel_primitive:NN	\vskip	\tex_vskip:D
599	__kernel_primitive:NN	\vsplit	\tex_vsplit:D
600	__kernel_primitive:NN	\vss	\tex_vss:D
601	__kernel_primitive:NN	\vtop	\tex_vtop:D
602	__kernel_primitive:NN	\wd	\tex_wd:D
603	__kernel_primitive:NN	\widowpenalty	\tex_widowpenalty:D
604	__kernel_primitive:NN	\write	\tex_write:D
605	__kernel_primitive:NN	\xdef	\tex_xdef:D
606	__kernel_primitive:NN	\xleaders	\tex_xleaders:D
607	__kernel_primitive:NN	\xspaceskip	\tex_xspaceskip:D
608	__kernel_primitive:NN	\year	\tex_year:D

Since L^AT_EX3 requires at least the ε -T_EX extensions, we also rename the additional primitives. These are all given the prefix `\etex_`.

609	__kernel_primitive:NN	\beginL	\etex_beginL:D
610	__kernel_primitive:NN	\beginR	\etex_beginR:D
611	__kernel_primitive:NN	\botmarks	\etex_botmarks:D
612	__kernel_primitive:NN	\clubpenalties	\etex_clubpenalties:D
613	__kernel_primitive:NN	\currentgrouplevel	\etex_currentgrouplevel:D
614	__kernel_primitive:NN	\currentgrouptype	\etex_currentgrouptype:D
615	__kernel_primitive:NN	\currentifbranch	\etex_currentifbranch:D
616	__kernel_primitive:NN	\currentiflevel	\etex_currentiflevel:D
617	__kernel_primitive:NN	\currentifttype	\etex_currentifttype:D
618	__kernel_primitive:NN	\detokenize	\etex_detokenize:D
619	__kernel_primitive:NN	\dimexpr	\etex_dimexpr:D
620	__kernel_primitive:NN	\displaywidowpenalties	\etex_displaywidowpenalties:D
621	__kernel_primitive:NN	\endL	\etex_endL:D
622	__kernel_primitive:NN	\endR	\etex_endR:D
623	__kernel_primitive:NN	\eTeXrevision	\etex_eTeXrevision:D
624	__kernel_primitive:NN	\eTeXversion	\etex_eTeXversion:D
625	__kernel_primitive:NN	\everyeof	\etex_everyeof:D
626	__kernel_primitive:NN	\firstmarks	\etex_firstmarks:D

627	<code>__kernel_primitive:NN \fontchardp</code>	<code>\etex_fontchardp:D</code>
628	<code>__kernel_primitive:NN \fontcharht</code>	<code>\etex_fontcharht:D</code>
629	<code>__kernel_primitive:NN \fontcharic</code>	<code>\etex_fontcharic:D</code>
630	<code>__kernel_primitive:NN \fontcharwd</code>	<code>\etex_fontcharwd:D</code>
631	<code>__kernel_primitive:NN \glueexpr</code>	<code>\etex_glueexpr:D</code>
632	<code>__kernel_primitive:NN \glueshrink</code>	<code>\etex_glueshrink:D</code>
633	<code>__kernel_primitive:NN \glueshrinkorder</code>	<code>\etex_glueshrinkorder:D</code>
634	<code>__kernel_primitive:NN \gluestretch</code>	<code>\etex_gluestretch:D</code>
635	<code>__kernel_primitive:NN \gluestretchorder</code>	<code>\etex_gluestretchorder:D</code>
636	<code>__kernel_primitive:NN \gluetomu</code>	<code>\etex_gluetomu:D</code>
637	<code>__kernel_primitive:NN \ifcsname</code>	<code>\etex_ifcsname:D</code>
638	<code>__kernel_primitive:NN \ifdefined</code>	<code>\etex_ifdefined:D</code>
639	<code>__kernel_primitive:NN \iffontchar</code>	<code>\etex_iffontchar:D</code>
640	<code>__kernel_primitive:NN \interactionmode</code>	<code>\etex_interactionmode:D</code>
641	<code>__kernel_primitive:NN \interlinepenalties</code>	<code>\etex_interlinepenalties:D</code>
642	<code>__kernel_primitive:NN \lastlinefit</code>	<code>\etex_lastlinefit:D</code>
643	<code>__kernel_primitive:NN \lastnodetype</code>	<code>\etex_lastnodetype:D</code>
644	<code>__kernel_primitive:NN \marks</code>	<code>\etex_marks:D</code>
645	<code>__kernel_primitive:NN \middle</code>	<code>\etex_middle:D</code>
646	<code>__kernel_primitive:NN \muexpr</code>	<code>\etex_muexpr:D</code>
647	<code>__kernel_primitive:NN \mutoglua</code>	<code>\etex_mutoglua:D</code>
648	<code>__kernel_primitive:NN \numexpr</code>	<code>\etex_numexpr:D</code>
649	<code>__kernel_primitive:NN \pagediscards</code>	<code>\etex_pagediscards:D</code>
650	<code>__kernel_primitive:NN \parshapedimen</code>	<code>\etex_parshapedimen:D</code>
651	<code>__kernel_primitive:NN \parshapeindent</code>	<code>\etex_parshapeindent:D</code>
652	<code>__kernel_primitive:NN \parshapelength</code>	<code>\etex_parshapelength:D</code>
653	<code>__kernel_primitive:NN \predisplaydirection</code>	<code>\etex_predisplaydirection:D</code>
654	<code>__kernel_primitive:NN \protected</code>	<code>\etex_protected:D</code>
655	<code>__kernel_primitive:NN \readline</code>	<code>\etex_readline:D</code>
656	<code>__kernel_primitive:NN \savingshyphcodes</code>	<code>\etex_savingshyphcodes:D</code>
657	<code>__kernel_primitive:NN \savingsvdiscards</code>	<code>\etex_savingsvdiscards:D</code>
658	<code>__kernel_primitive:NN \scantokens</code>	<code>\etex_scantokens:D</code>
659	<code>__kernel_primitive:NN \showgroups</code>	<code>\etex_showgroups:D</code>
660	<code>__kernel_primitive:NN \showifs</code>	<code>\etex_showifs:D</code>
661	<code>__kernel_primitive:NN \showtokens</code>	<code>\etex_showtokens:D</code>
662	<code>__kernel_primitive:NN \splitbotmarks</code>	<code>\etex_splitbotmarks:D</code>
663	<code>__kernel_primitive:NN \splitdiscards</code>	<code>\etex_splitdiscards:D</code>
664	<code>__kernel_primitive:NN \splitfirstmarks</code>	<code>\etex_splitfirstmarks:D</code>
665	<code>__kernel_primitive:NN \TeXXeTstate</code>	<code>\etex_TeXeTstate:D</code>
666	<code>__kernel_primitive:NN \topmarks</code>	<code>\etex_topmarks:D</code>
667	<code>__kernel_primitive:NN \tracingassigns</code>	<code>\etex_tracingassigns:D</code>
668	<code>__kernel_primitive:NN \tracinggroups</code>	<code>\etex_tracinggroups:D</code>
669	<code>__kernel_primitive:NN \tracingifs</code>	<code>\etex_tracingifs:D</code>
670	<code>__kernel_primitive:NN \tracingnesting</code>	<code>\etex_tracingnesting:D</code>
671	<code>__kernel_primitive:NN \tracingscantokens</code>	<code>\etex_tracingscantokens:D</code>
672	<code>__kernel_primitive:NN \unexpanded</code>	<code>\etex_unexpanded:D</code>
673	<code>__kernel_primitive:NN \unless</code>	<code>\etex_unless:D</code>
674	<code>__kernel_primitive:NN \widowpenalties</code>	<code>\etex_widowpenalties:D</code>

The newer primitives are more complex: there are an awful lot of them, and we don't use them all at the moment. So the following is selective, based on those also available in LuaTeX or used in expl3. In the case of the pdfTeX primitives, we retain `pdf` at the start of the names *only* for directly PDF-related primitives, as there are a lot of pdfTeX primitives that start `\pdf...` but are not related to PDF output. These ones related to

PDF output or only work in PDF mode.

675	_kernel_primitive:NN	\pdfannot	\pdfTEX_pdfannot:D
676	_kernel_primitive:NN	\pdfcatalog	\pdfTEX_pdfcatalog:D
677	_kernel_primitive:NN	\pdfcompresslevel	\pdfTEX_pdfcompresslevel:D
678	_kernel_primitive:NN	\pdfcolorstack	\pdfTEX_pdfcolorstack:D
679	_kernel_primitive:NN	\pdfcolorstackinit	\pdfTEX_pdfcolorstackinit:D
680	_kernel_primitive:NN	\pdfcreationdate	\pdfTEX_pdfcreationdate:D
681	_kernel_primitive:NN	\pdfdecimaldigits	\pdfTEX_pdfdecimaldigits:D
682	_kernel_primitive:NN	\pdfdest	\pdfTEX_pdfdest:D
683	_kernel_primitive:NN	\pdfdestmargin	\pdfTEX_pdfdestmargin:D
684	_kernel_primitive:NN	\pdfendlink	\pdfTEX_pdfendlink:D
685	_kernel_primitive:NN	\pdfendthread	\pdfTEX_pdfendthread:D
686	_kernel_primitive:NN	\pdffontattr	\pdfTEX_pdffontattr:D
687	_kernel_primitive:NN	\pdffontname	\pdfTEX_pdffontname:D
688	_kernel_primitive:NN	\pdffontobjnum	\pdfTEX_pdffontobjnum:D
689	_kernel_primitive:NN	\pdfgamma	\pdfTEX_pdfgamma:D
690	_kernel_primitive:NN	\pdfimageapplygamma	\pdfTEX_pdfimageapplygamma:D
691	_kernel_primitive:NN	\pdfimagegamma	\pdfTEX_pdfimagegamma:D
692	_kernel_primitive:NN	\pdfgentounicode	\pdfTEX_pdfgentounicode:D
693	_kernel_primitive:NN	\pdfglyptounicode	\pdfTEX_pdfglyptounicode:D
694	_kernel_primitive:NN	\pdfhorigin	\pdfTEX_pdfhorigin:D
695	_kernel_primitive:NN	\pdfimagehicolor	\pdfTEX_pdfimagehicolor:D
696	_kernel_primitive:NN	\pdfimageresolution	\pdfTEX_pdfimageresolution:D
697	_kernel_primitive:NN	\pdfincludechars	\pdfTEX_pdfincludechars:D
698	_kernel_primitive:NN	\pdfinclusioncopyfonts	\pdfTEX_pdfinclusioncopyfonts:D
699	_kernel_primitive:NN	\pdfinclusionerrorlevel	\pdfTEX_pdfinclusionerrorlevel:D
700	_kernel_primitive:NN	\pdfinfo	\pdfTEX_pdfinfo:D
701	_kernel_primitive:NN	\pdflastannot	\pdfTEX_pdflastannot:D
702	_kernel_primitive:NN	\pdflastlink	\pdfTEX_pdflastlink:D
703	_kernel_primitive:NN	\pdflastobj	\pdfTEX_pdflastobj:D
704	_kernel_primitive:NN	\pdflastxform	\pdfTEX_pdflastxform:D
705	_kernel_primitive:NN	\pdflastximage	\pdfTEX_pdflastximage:D
706	_kernel_primitive:NN	\pdflastximagecolordepth	\pdfTEX_pdflastximagecolordepth:D
707	_kernel_primitive:NN	\pdflastximagepages	\pdfTEX_pdflastximagepages:D
708	_kernel_primitive:NN	\pdflinkmargin	\pdfTEX_pdflinkmargin:D
709	_kernel_primitive:NN	\pdfliteral	\pdfTEX_pdfliteral:D
710	_kernel_primitive:NN	\pdfminorversion	\pdfTEX_pdfminorversion:D
711	_kernel_primitive:NN	\pdfnames	\pdfTEX_pdfnames:D
712	_kernel_primitive:NN	\pdfobj	\pdfTEX_pdfobj:D
713	_kernel_primitive:NN	\pdfobjcompresslevel	\pdfTEX_pdfobjcompresslevel:D
714	_kernel_primitive:NN	\pdfoutline	\pdfTEX_pdfoutline:D
715	_kernel_primitive:NN	\pdfoutput	\pdfTEX_pdfoutput:D
716	_kernel_primitive:NN	\pdfpageattr	\pdfTEX_pdfpageattr:D
717	_kernel_primitive:NN	\pdfpagebox	\pdfTEX_pdfpagebox:D
718	_kernel_primitive:NN	\pdfpageref	\pdfTEX_pdfpageref:D
719	_kernel_primitive:NN	\pdfpageresources	\pdfTEX_pdfpageresources:D
720	_kernel_primitive:NN	\pdfpagesattr	\pdfTEX_pdfpagesattr:D
721	_kernel_primitive:NN	\pdfrefobj	\pdfTEX_pdfrefobj:D
722	_kernel_primitive:NN	\pdfrefxform	\pdfTEX_pdfrefxform:D
723	_kernel_primitive:NN	\pdfrefximage	\pdfTEX_pdfrefximage:D
724	_kernel_primitive:NN	\pdfrestore	\pdfTEX_pdfrestore:D
725	_kernel_primitive:NN	\pdfretval	\pdfTEX_pdfretval:D
726	_kernel_primitive:NN	\pdfsave	\pdfTEX_pdfsave:D
727	_kernel_primitive:NN	\pdfsetmatrix	\pdfTEX_pdfsetmatrix:D

728	_kernel_primitive:NN	\pdfstartlink	\pdfTeX_pdfstartlink:D
729	_kernel_primitive:NN	\pdfstartthread	\pdfTeX_pdfstartthread:D
730	_kernel_primitive:NN	\pdfsuppressptexinfo	\pdfTeX_pdfsuppressptexinfo:D
731	_kernel_primitive:NN	\pdfthread	\pdfTeX_pdfthread:D
732	_kernel_primitive:NN	\pdfthreadmargin	\pdfTeX_pdfthreadmargin:D
733	_kernel_primitive:NN	\pdftrailer	\pdfTeX_pdftrailer:D
734	_kernel_primitive:NN	\pdfuniqueresname	\pdfTeX_pdfuniqueresname:D
735	_kernel_primitive:NN	\pdfvorigin	\pdfTeX_pdfvorigin:D
736	_kernel_primitive:NN	\pdfxform	\pdfTeX_pdfxform:D
737	_kernel_primitive:NN	\pdfxformattr	\pdfTeX_pdfxformattr:D
738	_kernel_primitive:NN	\pdfxformname	\pdfTeX_pdfxformname:D
739	_kernel_primitive:NN	\pdfxformresources	\pdfTeX_pdfxformresources:D
740	_kernel_primitive:NN	\pdfximage	\pdfTeX_pdfximage:D
741	_kernel_primitive:NN	\pdfximagebbox	\pdfTeX_pdfximagebbox:D

While these are not.

742	_kernel_primitive:NN	\ifpdfabsdim	\pdfTeX_ifabsdim:D
743	_kernel_primitive:NN	\ifpdfabsnum	\pdfTeX_ifabsnum:D
744	_kernel_primitive:NN	\ifpdfprimitive	\pdfTeX_ifprimitive:D
745	_kernel_primitive:NN	\pdfadjustspacing	\pdfTeX_adjustspacing:D
746	_kernel_primitive:NN	\pdfcopyfont	\pdfTeX_copyfont:D
747	_kernel_primitive:NN	\pdfdraftmode	\pdfTeX_draftmode:D
748	_kernel_primitive:NN	\pdfeachlinedepth	\pdfTeX_eachlinedepth:D
749	_kernel_primitive:NN	\pdfeachlineheight	\pdfTeX_eachlineheight:D
750	_kernel_primitive:NN	\pdffilemoddate	\pdfTeX_filemoddate:D
751	_kernel_primitive:NN	\pdffilesize	\pdfTeX_filesize:D
752	_kernel_primitive:NN	\pdffirstlineheight	\pdfTeX_firstlineheight:D
753	_kernel_primitive:NN	\pdffontexpand	\pdfTeX_fontexpand:D
754	_kernel_primitive:NN	\pdffontsize	\pdfTeX_fontsize:D
755	_kernel_primitive:NN	\pdfignoreddimen	\pdfTeX_ignoreddimen:D
756	_kernel_primitive:NN	\pdfinsertht	\pdfTeX_insertht:D
757	_kernel_primitive:NN	\pdflastlinedepth	\pdfTeX_lastlinedepth:D
758	_kernel_primitive:NN	\pdflastxpos	\pdfTeX_lastxpos:D
759	_kernel_primitive:NN	\pdflastypos	\pdfTeX_lastypos:D
760	_kernel_primitive:NN	\pdfmapfile	\pdfTeX_mapfile:D
761	_kernel_primitive:NN	\pdfmapline	\pdfTeX_mapline:D
762	_kernel_primitive:NN	\pdfmdfivesum	\pdfTeX_mdfivesum:D
763	_kernel_primitive:NN	\pdfnoligatures	\pdfTeX_noligatures:D
764	_kernel_primitive:NN	\pdfnormaldeviate	\pdfTeX_normaldeviate:D
765	_kernel_primitive:NN	\pdfpageheight	\pdfTeX_pageheight:D
766	_kernel_primitive:NN	\pdfpagewidth	\pdfTeX_pagewidth:D
767	_kernel_primitive:NN	\pdfpkmode	\pdfTeX_pkmode:D
768	_kernel_primitive:NN	\pdfpkresolution	\pdfTeX_pkresolution:D
769	_kernel_primitive:NN	\pdfprimitive	\pdfTeX_primitive:D
770	_kernel_primitive:NN	\pdfprotrudechars	\pdfTeX_protrudechars:D
771	_kernel_primitive:NN	\pdfpxdimen	\pdfTeX_pxdimen:D
772	_kernel_primitive:NN	\pdfrandomseed	\pdfTeX_randomseed:D
773	_kernel_primitive:NN	\pdfsavepos	\pdfTeX_savepos:D
774	_kernel_primitive:NN	\pdfstrcmp	\pdfTeX_strcmp:D
775	_kernel_primitive:NN	\pdfsetrandomseed	\pdfTeX_setrandomseed:D
776	_kernel_primitive:NN	\pdfshellescape	\pdfTeX_shellescape:D
777	_kernel_primitive:NN	\pdftracingfonts	\pdfTeX_tracingfonts:D
778	_kernel_primitive:NN	\pdfuniformdeviate	\pdfTeX_uniformdeviate:D

The version primitives are not related to PDF mode but are related to pdfTeX so retain

the full prefix.

```

779 \__kernel_primitive:NN \pdfetxbanner \pdfetx_pdfetxbanner:D
780 \__kernel_primitive:NN \pdfetxrevision \pdfetx_pdfetxrevision:D
781 \__kernel_primitive:NN \pdfetxversion \pdfetx_pdfetxversion:D

```

These ones appear in pdfTeX but don't have pdf in the name at all. (\synctex is odd as it's really not from pdfTeX but from SyncTeX!)

```

782 \__kernel_primitive:NN \efcode \pdfetx_efcode:D
783 \__kernel_primitive:NN \ifincsname \pdfetx_ifincsname:D
784 \__kernel_primitive:NN \leftmarginkern \pdfetx_leftmarginkern:D
785 \__kernel_primitive:NN \letterspacefont \pdfetx_letterspacefont:D
786 \__kernel_primitive:NN \lpcode \pdfetx_lpcode:D
787 \__kernel_primitive:NN \quitvmode \pdfetx_quitvmode:D
788 \__kernel_primitive:NN \rightmarginkern \pdfetx_rightmarginkern:D
789 \__kernel_primitive:NN \rpcode \pdfetx_rpcode:D
790 \__kernel_primitive:NN \synctex \pdfetx_synctex:D
791 \__kernel_primitive:NN \tagcode \pdfetx_tagcode:D

```

Post pdfTeX primitive availability gets more complex. Both XeTeX and LuaTeX have varying names for some primitives from pdfTeX. Particularly for LuaTeX tracking all of that would be hard. Instead, we now check that we only save primitives if they actually exist.

```

792 </initex | names | package>
793 < *initex | package>
794 \tex_long:D \tex_def:D \use_ii:nn #1#2 {#2}
795 \tex_long:D \tex_def:D \use_none:n #1 { }
796 \tex_long:D \tex_def:D \__kernel_primitive:NN #1#2
797 {
798 \etex_ifdefined:D #1
799 \tex_expandafter:D \use_ii:nn
800 \tex_fi:D
801 \use_none:n { \tex_global:D \tex_let:D #2 #1 }
802 < *initex>
803 \tex_global:D \tex_let:D #1 \tex_undefined:D
804 </initex>
805 }
806 </initex | package>
807 < *initex | names | package>

```

XeTeX-specific primitives. Note that XeTeX's \strcmp is handled earlier and is “rolled up” into \pdfstrcmp. With the exception of the version primitives these don't carry XeTeX through into the “base” name. A few cross-compatibility names which lack the pdf of the original are handled later.

```

808 \__kernel_primitive:NN \suppressfontnotfounderror \xetex_suppressfontnotfounderror:D
809 \__kernel_primitive:NN \XeTeXcharclass \xetex_charclass:D
810 \__kernel_primitive:NN \XeTeXcharglyph \xetex_charglyph:D
811 \__kernel_primitive:NN \XeTeXcountfeatures \xetex_countfeatures:D
812 \__kernel_primitive:NN \XeTeXcountglyphs \xetex_countglyphs:D
813 \__kernel_primitive:NN \XeTeXcountselectors \xetex_countselectors:D
814 \__kernel_primitive:NN \XeTeXcountvariations \xetex_countvariations:D
815 \__kernel_primitive:NN \XeTeXdefaultencoding \xetex_defaultencoding:D
816 \__kernel_primitive:NN \XeTeXdashbreakstate \xetex_dashbreakstate:D
817 \__kernel_primitive:NN \XeTeXfeaturecode \xetex_featurecode:D
818 \__kernel_primitive:NN \XeTeXfeaturename \xetex_featurename:D

```

819	<code>__kernel_primitive:NN \XeTeXfindfeaturebyname</code>	<code>\xetex_findfeaturebyname:D</code>
820	<code>__kernel_primitive:NN \XeTeXfindselectorbyname</code>	<code>\xetex_findselectorbyname:D</code>
821	<code>__kernel_primitive:NN \XeTeXfindvariationbyname</code>	<code>\xetex_findvariationbyname:D</code>
822	<code>__kernel_primitive:NN \XeTeXfirstfontchar</code>	<code>\xetex_firstfontchar:D</code>
823	<code>__kernel_primitive:NN \XeTeXfonttype</code>	<code>\xetex_fonttype:D</code>
824	<code>__kernel_primitive:NN \XeTeXgenerateactualtext</code>	<code>\xetex_generateactualtext:D</code>
825	<code>__kernel_primitive:NN \XeTeXglyph</code>	<code>\xetex_glyph:D</code>
826	<code>__kernel_primitive:NN \XeTeXglyphbounds</code>	<code>\xetex_glyphbounds:D</code>
827	<code>__kernel_primitive:NN \XeTeXglyphindex</code>	<code>\xetex_glyphindex:D</code>
828	<code>__kernel_primitive:NN \XeTeXglyphname</code>	<code>\xetex_glyphname:D</code>
829	<code>__kernel_primitive:NN \XeTeXinputencoding</code>	<code>\xetex_inputencoding:D</code>
830	<code>__kernel_primitive:NN \XeTeXinputnormalization</code>	<code>\xetex_inputnormalization:D</code>
831	<code>__kernel_primitive:NN \XeTeXinterchartokenstate</code>	<code>\xetex_interchartokenstate:D</code>
832	<code>__kernel_primitive:NN \XeTeXinterchartoks</code>	<code>\xetex_interchartoks:D</code>
833	<code>__kernel_primitive:NN \XeTeXisdefaultselector</code>	<code>\xetex_isdefaultselector:D</code>
834	<code>__kernel_primitive:NN \XeTeXisexclusivefeature</code>	<code>\xetex_isexclusivefeature:D</code>
835	<code>__kernel_primitive:NN \XeTeXlastfontchar</code>	<code>\xetex_lastfontchar:D</code>
836	<code>__kernel_primitive:NN \XeTeXlinebreakskip</code>	<code>\xetex_linebreakskip:D</code>
837	<code>__kernel_primitive:NN \XeTeXlinebreaklocale</code>	<code>\xetex_linebreaklocale:D</code>
838	<code>__kernel_primitive:NN \XeTeXlinebreakpenalty</code>	<code>\xetex_linebreakpenalty:D</code>
839	<code>__kernel_primitive:NN \XeTeXOTcountfeatures</code>	<code>\xetex_OTcountfeatures:D</code>
840	<code>__kernel_primitive:NN \XeTeXOTcountlanguages</code>	<code>\xetex_OTcountlanguages:D</code>
841	<code>__kernel_primitive:NN \XeTeXOTcountscripts</code>	<code>\xetex_OTcountscripts:D</code>
842	<code>__kernel_primitive:NN \XeTeXOTfeaturetag</code>	<code>\xetex_OTfeaturetag:D</code>
843	<code>__kernel_primitive:NN \XeTeXOTlanguagetag</code>	<code>\xetex_OTlanguagetag:D</code>
844	<code>__kernel_primitive:NN \XeTeXOTscripttag</code>	<code>\xetex_OTscripttag:D</code>
845	<code>__kernel_primitive:NN \XeTeXpdffile</code>	<code>\xetex_pdffile:D</code>
846	<code>__kernel_primitive:NN \XeTeXpdfpagecount</code>	<code>\xetex_pdfpagecount:D</code>
847	<code>__kernel_primitive:NN \XeTeXpicfile</code>	<code>\xetex_picfile:D</code>
848	<code>__kernel_primitive:NN \XeTeXselectorname</code>	<code>\xetex_selectorname:D</code>
849	<code>__kernel_primitive:NN \XeTeXtracingfonts</code>	<code>\xetex_tracingfonts:D</code>
850	<code>__kernel_primitive:NN \XeTeXupwardsmode</code>	<code>\xetex_upwardsmode:D</code>
851	<code>__kernel_primitive:NN \XeTeXuseglyphmetrics</code>	<code>\xetex_useglyphmetrics:D</code>
852	<code>__kernel_primitive:NN \XeTeXvariation</code>	<code>\xetex_variation:D</code>
853	<code>__kernel_primitive:NN \XeTeXvariationdefault</code>	<code>\xetex_variationdefault:D</code>
854	<code>__kernel_primitive:NN \XeTeXvariationmax</code>	<code>\xetex_variationmax:D</code>
855	<code>__kernel_primitive:NN \XeTeXvariationmin</code>	<code>\xetex_variationmin:D</code>
856	<code>__kernel_primitive:NN \XeTeXvariationname</code>	<code>\xetex_variationname:D</code>

The version primitives retain XeTeX.

857	<code>__kernel_primitive:NN \XeTeXrevision</code>	<code>\xetex_XeTeXrevision:D</code>
858	<code>__kernel_primitive:NN \XeTeXversion</code>	<code>\xetex_XeTeXversion:D</code>

Primitives from pdfTeX that XeTeX renames: also helps with LuaTeX.

859	<code>__kernel_primitive:NN \mdfivesum</code>	<code>\pdfTEX_mdfivesum:D</code>
860	<code>__kernel_primitive:NN \ifprimitive</code>	<code>\pdfTEX_ifprimitive:D</code>
861	<code>__kernel_primitive:NN \primitive</code>	<code>\pdfTEX_primitive:D</code>
862	<code>__kernel_primitive:NN \shellescape</code>	<code>\pdfTEX_shellescape:D</code>

Primitives from LuaTeX, some of which have been ported back to XeTeX. Notice that `\expanded` was intended for pdfTeX 1.50 but as that was not released we call this a LuaTeX primitive.

863	<code>__kernel_primitive:NN \alignmark</code>	<code>\luaTEX_alignmark:D</code>
864	<code>__kernel_primitive:NN \aligntab</code>	<code>\luaTEX_aligntab:D</code>
865	<code>__kernel_primitive:NN \attribute</code>	<code>\luaTEX_attribute:D</code>

866	_kernel_primitive:NN	\attributedef	\luatex_attributedef:D
867	_kernel_primitive:NN	\automatichyphenpenalty	\luatex_automatichyphenpenalty:D
868	_kernel_primitive:NN	\beginscname	\luatex_beginscname:D
869	_kernel_primitive:NN	\catcodetable	\luatex_catcodetable:D
870	_kernel_primitive:NN	\clearmarks	\luatex_clearmarks:D
871	_kernel_primitive:NN	\crampeddisplaystyle	\luatex_crampeddisplaystyle:D
872	_kernel_primitive:NN	\crampedscriptscriptstyle	\luatex_crampedscriptscriptstyle:D
873	_kernel_primitive:NN	\crampedscriptstyle	\luatex_crampedscriptstyle:D
874	_kernel_primitive:NN	\crampedtextstyle	\luatex_crampedtextstyle:D
875	_kernel_primitive:NN	\directlua	\luatex_directlua:D
876	_kernel_primitive:NN	\dviextension	\luatex_dviextension:D
877	_kernel_primitive:NN	\dvifedback	\luatex_dvifedback:D
878	_kernel_primitive:NN	\dvivariable	\luatex_dvivariable:D
879	_kernel_primitive:NN	\etoksapp	\luatex_etoksapp:D
880	_kernel_primitive:NN	\etokspre	\luatex_etokspre:D
881	_kernel_primitive:NN	\explicitthyphenpenalty	\luatex_explicitthyphenpenalty:D
882	_kernel_primitive:NN	\expanded	\luatex_expanded:D
883	_kernel_primitive:NN	\firstvalidlanguage	\luatex_firstvalidlanguage:D
884	_kernel_primitive:NN	\fontid	\luatex_fontid:D
885	_kernel_primitive:NN	\formatname	\luatex_formatname:D
886	_kernel_primitive:NN	\hjcode	\luatex_hjcode:D
887	_kernel_primitive:NN	\hpack	\luatex_hpack:D
888	_kernel_primitive:NN	\hyphenationbounds	\luatex_hyphenationbounds:D
889	_kernel_primitive:NN	\hyphenationmin	\luatex_hyphenationmin:D
890	_kernel_primitive:NN	\hyphenpenaltymode	\luatex_hyphenpenaltymode:D
891	_kernel_primitive:NN	\gleaders	\luatex_gleaders:D
892	_kernel_primitive:NN	\initcatcodetable	\luatex_initcatcodetable:D
893	_kernel_primitive:NN	\lastnamedcs	\luatex_lastnamedcs:D
894	_kernel_primitive:NN	\latelua	\luatex_latelua:D
895	_kernel_primitive:NN	\letcharcode	\luatex_letcharcode:D
896	_kernel_primitive:NN	\luaescapestring	\luatex_luaescapestring:D
897	_kernel_primitive:NN	\luafunction	\luatex_luafunction:D
898	_kernel_primitive:NN	\luatexbanner	\luatex_luatexbanner:D
899	_kernel_primitive:NN	\luatexdatestamp	\luatex_luatexdatestamp:D
900	_kernel_primitive:NN	\luatexrevision	\luatex_luatexrevision:D
901	_kernel_primitive:NN	\luatexversion	\luatex_luatexversion:D
902	_kernel_primitive:NN	\mathdisplayskipmode	\luatex_mathdisplayskipmode:D
903	_kernel_primitive:NN	\matheqnogapstep	\luatex_matheqnogapstep:D
904	_kernel_primitive:NN	\mathnolimitsmode	\luatex_mathnolimitsmode:D
905	_kernel_primitive:NN	\mathoption	\luatex_mathoption:D
906	_kernel_primitive:NN	\mathrulesfam	\luatex_mathrulesfam:D
907	_kernel_primitive:NN	\mathscriptsmode	\luatex_mathscriptsmode:D
908	_kernel_primitive:NN	\mathstyle	\luatex_mathstyle:D
909	_kernel_primitive:NN	\mathsurroundmode	\luatex_mathsurroundmode:D
910	_kernel_primitive:NN	\mathsurroundskip	\luatex_mathsurroundskip:D
911	_kernel_primitive:NN	\nohrule	\luatex_nohrule:D
912	_kernel_primitive:NN	\nokerns	\luatex_nokerns:D
913	_kernel_primitive:NN	\noligs	\luatex_noligs:D
914	_kernel_primitive:NN	\nospaces	\luatex_nospaces:D
915	_kernel_primitive:NN	\novrule	\luatex_novrule:D
916	_kernel_primitive:NN	\outputbox	\luatex_outputbox:D
917	_kernel_primitive:NN	\pagebottomoffset	\luatex_pagebottomoffset:D
918	_kernel_primitive:NN	\pageleftoffset	\luatex_pageleftoffset:D
919	_kernel_primitive:NN	\pagerightoffset	\luatex_pagerightoffset:D

920	<code>__kernel_primitive:NN \pagetopoffset</code>	<code>\luatex_pagetopoffset:D</code>
921	<code>__kernel_primitive:NN \pdfextension</code>	<code>\luatex_pdfextension:D</code>
922	<code>__kernel_primitive:NN \pdffeedback</code>	<code>\luatex_pdffeedback:D</code>
923	<code>__kernel_primitive:NN \pdfvariable</code>	<code>\luatex_pdfvariable:D</code>
924	<code>__kernel_primitive:NN \postexhyphenchar</code>	<code>\luatex_postexhyphenchar:D</code>
925	<code>__kernel_primitive:NN \posthyphenchar</code>	<code>\luatex_posthyphenchar:D</code>
926	<code>__kernel_primitive:NN \predisplaygapfactor</code>	<code>\luatex_predisplaygapfactor:D</code>
927	<code>__kernel_primitive:NN \preexhyphenchar</code>	<code>\luatex_preexhyphenchar:D</code>
928	<code>__kernel_primitive:NN \prehyphenchar</code>	<code>\luatex_prehyphenchar:D</code>
929	<code>__kernel_primitive:NN \savecatcodetable</code>	<code>\luatex_savecatcodetable:D</code>
930	<code>__kernel_primitive:NN \scantexttokens</code>	<code>\luatex_scantexttokens:D</code>
931	<code>__kernel_primitive:NN \setfontid</code>	<code>\luatex_setfontid:D</code>
932	<code>__kernel_primitive:NN \shapemode</code>	<code>\luatex_shapemode:D</code>
933	<code>__kernel_primitive:NN \suppressifcsnameerror</code>	<code>\luatex_suppressifcsnameerror:D</code>
934	<code>__kernel_primitive:NN \suppresslongerror</code>	<code>\luatex_suppresslongerror:D</code>
935	<code>__kernel_primitive:NN \suppressmathparerror</code>	<code>\luatex_suppressmathparerror:D</code>
936	<code>__kernel_primitive:NN \suppressoutererror</code>	<code>\luatex_suppressoutererror:D</code>
937	<code>__kernel_primitive:NN \toksapp</code>	<code>\luatex_toksapp:D</code>
938	<code>__kernel_primitive:NN \tokspre</code>	<code>\luatex_tokspre:D</code>
939	<code>__kernel_primitive:NN \tpack</code>	<code>\luatex_tpack:D</code>
940	<code>__kernel_primitive:NN \vpack</code>	<code>\luatex_vpack:D</code>

Slightly more awkward are the directional primitives in LuaTeX. These come from Omega/Aleph, but we do not support those engines and so it seems most sensible to treat them as LuaTeX primitives for prefix purposes. One here is “new” but fits into the general set.

941	<code>__kernel_primitive:NN \bodydir</code>	<code>\luatex_bodydir:D</code>
942	<code>__kernel_primitive:NN \boxdir</code>	<code>\luatex_boxdir:D</code>
943	<code>__kernel_primitive:NN \leftghost</code>	<code>\luatex_leftghost:D</code>
944	<code>__kernel_primitive:NN \linedir</code>	<code>\luatex_linedir:D</code>
945	<code>__kernel_primitive:NN \localbrokenpenalty</code>	<code>\luatex_localbrokenpenalty:D</code>
946	<code>__kernel_primitive:NN \localinterlinepenalty</code>	<code>\luatex_localinterlinepenalty:D</code>
947	<code>__kernel_primitive:NN \localleftbox</code>	<code>\luatex_localleftbox:D</code>
948	<code>__kernel_primitive:NN \localrightbox</code>	<code>\luatex_localrightbox:D</code>
949	<code>__kernel_primitive:NN \mathdir</code>	<code>\luatex_mathdir:D</code>
950	<code>__kernel_primitive:NN \pagedir</code>	<code>\luatex_pagedir:D</code>
951	<code>__kernel_primitive:NN \pardir</code>	<code>\luatex_pardir:D</code>
952	<code>__kernel_primitive:NN \rightghost</code>	<code>\luatex_rightghost:D</code>
953	<code>__kernel_primitive:NN \textdir</code>	<code>\luatex_textdir:D</code>

Primitives from pdfTeX that LuaTeX renames.

954	<code>__kernel_primitive:NN \adjustspacing</code>	<code>\pdfTeX_adjustspacing:D</code>
955	<code>__kernel_primitive:NN \copyfont</code>	<code>\pdfTeX_copyfont:D</code>
956	<code>__kernel_primitive:NN \draftmode</code>	<code>\pdfTeX_draftmode:D</code>
957	<code>__kernel_primitive:NN \expandglyphsinfont</code>	<code>\pdfTeX_fontexpand:D</code>
958	<code>__kernel_primitive:NN \ifabsdim</code>	<code>\pdfTeX_ifabsdim:D</code>
959	<code>__kernel_primitive:NN \ifabsnum</code>	<code>\pdfTeX_ifabsnum:D</code>
960	<code>__kernel_primitive:NN \ignoreligaturesinfont</code>	<code>\pdfTeX_ignoreligaturesinfont:D</code>
961	<code>__kernel_primitive:NN \insertht</code>	<code>\pdfTeX_insertht:D</code>
962	<code>__kernel_primitive:NN \lastsavedboxresourceindex</code>	<code>\pdfTeX_pdflastxform:D</code>
963	<code>__kernel_primitive:NN \lastsavedimageresourceindex</code>	<code>\pdfTeX_pdflastximage:D</code>
964	<code>__kernel_primitive:NN \lastsavedimageresourcepages</code>	<code>\pdfTeX_pdflastximagepages:D</code>
965	<code>__kernel_primitive:NN \lastxpos</code>	<code>\pdfTeX_lastxpos:D</code>
966	<code>__kernel_primitive:NN \lastypos</code>	<code>\pdfTeX_lastypos:D</code>
967	<code>__kernel_primitive:NN \normaldeviate</code>	<code>\pdfTeX_normaldeviate:D</code>

968	<code>__kernel_primitive:NN</code>	<code>\outputmode</code>	<code>\pdftex_pdfoutput:D</code>
969	<code>__kernel_primitive:NN</code>	<code>\pageheight</code>	<code>\pdftex_pageheight:D</code>
970	<code>__kernel_primitive:NN</code>	<code>\pagewidth</code>	<code>\pdftex_pagewidth:D</code>
971	<code>__kernel_primitive:NN</code>	<code>\protrudechars</code>	<code>\pdftex_protrudechars:D</code>
972	<code>__kernel_primitive:NN</code>	<code>\pxdimen</code>	<code>\pdftex_pxdimen:D</code>
973	<code>__kernel_primitive:NN</code>	<code>\randomseed</code>	<code>\pdftex_randomseed:D</code>
974	<code>__kernel_primitive:NN</code>	<code>\useboxresource</code>	<code>\pdftex_pdfrefxform:D</code>
975	<code>__kernel_primitive:NN</code>	<code>\useimageresource</code>	<code>\pdftex_pdfrefximage:D</code>
976	<code>__kernel_primitive:NN</code>	<code>\savepos</code>	<code>\pdftex_savepos:D</code>
977	<code>__kernel_primitive:NN</code>	<code>\saveboxresource</code>	<code>\pdftex_pdfxform:D</code>
978	<code>__kernel_primitive:NN</code>	<code>\saveimageresource</code>	<code>\pdftex_pdfximage:D</code>
979	<code>__kernel_primitive:NN</code>	<code>\setrandomseed</code>	<code>\pdftex_setrandomseed:D</code>
980	<code>__kernel_primitive:NN</code>	<code>\tracingfonts</code>	<code>\pdftex_tracingfonts:D</code>
981	<code>__kernel_primitive:NN</code>	<code>\uniformdeviate</code>	<code>\pdftex_uniformdeviate:D</code>

The set of Unicode math primitives were introduced by \XeTeX and \LuaTeX in a somewhat complex fashion: a few first as $\text{\XeTeX}\dots$ which were then renamed with \LuaTeX having a lot more. These names now all start $\text{\U}\dots$ and mainly $\text{\Umath}\dots$. To keep things somewhat clear we therefore prefix all of these as $\text{\utex}\dots$ (introduced by a Unicode \TeX engine) and drop \U(math) from the names. Where there is a related \TeX90 primitive or where it really seems required we keep the math part of the name.

982	<code>__kernel_primitive:NN</code>	<code>\Uchar</code>	<code>\utex_char:D</code>
983	<code>__kernel_primitive:NN</code>	<code>\Ucharcat</code>	<code>\utex_charcat:D</code>
984	<code>__kernel_primitive:NN</code>	<code>\Udelcode</code>	<code>\utex_delcode:D</code>
985	<code>__kernel_primitive:NN</code>	<code>\Udelcodenum</code>	<code>\utex_delcodenum:D</code>
986	<code>__kernel_primitive:NN</code>	<code>\Udelimiter</code>	<code>\utex_delimiter:D</code>
987	<code>__kernel_primitive:NN</code>	<code>\Udelimiterover</code>	<code>\utex_delimiterover:D</code>
988	<code>__kernel_primitive:NN</code>	<code>\Udelimiterunder</code>	<code>\utex_delimiterunder:D</code>
989	<code>__kernel_primitive:NN</code>	<code>\Uhextensible</code>	<code>\utex_hextensible:D</code>
990	<code>__kernel_primitive:NN</code>	<code>\Umathaccent</code>	<code>\utex_mathaccent:D</code>
991	<code>__kernel_primitive:NN</code>	<code>\Umathaxis</code>	<code>\utex_mathaxis:D</code>
992	<code>__kernel_primitive:NN</code>	<code>\Umathbinbinspacing</code>	<code>\utex_binbinspacing:D</code>
993	<code>__kernel_primitive:NN</code>	<code>\Umathbinclosespacing</code>	<code>\utex_binclosespacing:D</code>
994	<code>__kernel_primitive:NN</code>	<code>\Umathbininnerspacing</code>	<code>\utex_bininnerspacing:D</code>
995	<code>__kernel_primitive:NN</code>	<code>\Umathbinopenspacing</code>	<code>\utex_binopenspacing:D</code>
996	<code>__kernel_primitive:NN</code>	<code>\Umathbinopspacing</code>	<code>\utex_binopspacing:D</code>
997	<code>__kernel_primitive:NN</code>	<code>\Umathbinordspacing</code>	<code>\utex_binordspacing:D</code>
998	<code>__kernel_primitive:NN</code>	<code>\Umathbinpunctspacing</code>	<code>\utex_binpunctspacing:D</code>
999	<code>__kernel_primitive:NN</code>	<code>\Umathbinrelspacing</code>	<code>\utex_binrelspacing:D</code>
1000	<code>__kernel_primitive:NN</code>	<code>\Umathchar</code>	<code>\utex_mathchar:D</code>
1001	<code>__kernel_primitive:NN</code>	<code>\Umathcharclass</code>	<code>\utex_mathcharclass:D</code>
1002	<code>__kernel_primitive:NN</code>	<code>\Umathchardef</code>	<code>\utex_mathchardef:D</code>
1003	<code>__kernel_primitive:NN</code>	<code>\Umathcharfam</code>	<code>\utex_mathcharfam:D</code>
1004	<code>__kernel_primitive:NN</code>	<code>\Umathcharnum</code>	<code>\utex_mathcharnum:D</code>
1005	<code>__kernel_primitive:NN</code>	<code>\Umathcharnumdef</code>	<code>\utex_mathcharnumdef:D</code>
1006	<code>__kernel_primitive:NN</code>	<code>\Umathcharslot</code>	<code>\utex_mathcharslot:D</code>
1007	<code>__kernel_primitive:NN</code>	<code>\Umathclosebinspacing</code>	<code>\utex_closebinspacing:D</code>
1008	<code>__kernel_primitive:NN</code>	<code>\Umathcloseclosespacing</code>	<code>\utex_closeclosespacing:D</code>
1009	<code>__kernel_primitive:NN</code>	<code>\Umathcloseinnerspacing</code>	<code>\utex_closeinnerspacing:D</code>
1010	<code>__kernel_primitive:NN</code>	<code>\Umathcloseopenspacing</code>	<code>\utex_closeopenspacing:D</code>
1011	<code>__kernel_primitive:NN</code>	<code>\Umathcloseopspacing</code>	<code>\utex_closeopspacing:D</code>
1012	<code>__kernel_primitive:NN</code>	<code>\Umathcloseordspacing</code>	<code>\utex_closeordspacing:D</code>
1013	<code>__kernel_primitive:NN</code>	<code>\Umathclosepunctspacing</code>	<code>\utex_closepunctspacing:D</code>
1014	<code>__kernel_primitive:NN</code>	<code>\Umathcloserelspacing</code>	<code>\utex_closerelspacing:D</code>

1015	_kernel_primitive:NN	\Umathcode	\utex_mathcode:D
1016	_kernel_primitive:NN	\Umathcodenum	\utex_mathcodenum:D
1017	_kernel_primitive:NN	\Umathconnectoroverlapmin	\utex_connectoroverlapmin:D
1018	_kernel_primitive:NN	\Umathfractiondelsize	\utex_fractiondelsize:D
1019	_kernel_primitive:NN	\Umathfractiondenomdown	\utex_fractiondenomdown:D
1020	_kernel_primitive:NN	\Umathfractiondenomvgap	\utex_fractiondenomvgap:D
1021	_kernel_primitive:NN	\Umathfractionnumup	\utex_fractionnumup:D
1022	_kernel_primitive:NN	\Umathfractionnumvgap	\utex_fractionnumvgap:D
1023	_kernel_primitive:NN	\Umathfractionrule	\utex_fractionrule:D
1024	_kernel_primitive:NN	\Umathinnerbinspacing	\utex_innerbinspacing:D
1025	_kernel_primitive:NN	\Umathinnerclosespacing	\utex_innerclosespacing:D
1026	_kernel_primitive:NN	\Umathinnerinnerspacing	\utex_innerinnerspacing:D
1027	_kernel_primitive:NN	\Umathinneropenspacing	\utex_inneropenspacing:D
1028	_kernel_primitive:NN	\Umathinneropspacing	\utex_inneropspacing:D
1029	_kernel_primitive:NN	\Umathinnerordspacing	\utex_innerordspacing:D
1030	_kernel_primitive:NN	\Umathinnerpunctspacing	\utex_innerpunctspacing:D
1031	_kernel_primitive:NN	\Umathinnerrelspacing	\utex_innerrelspacing:D
1032	_kernel_primitive:NN	\Umathlimitabovebgap	\utex_limitabovebgap:D
1033	_kernel_primitive:NN	\Umathlimitabovekern	\utex_limitabovekern:D
1034	_kernel_primitive:NN	\Umathlimitabovevgap	\utex_limitabovevgap:D
1035	_kernel_primitive:NN	\Umathlimitbelowbgap	\utex_limitbelowbgap:D
1036	_kernel_primitive:NN	\Umathlimitbelowkern	\utex_limitbelowkern:D
1037	_kernel_primitive:NN	\Umathlimitbelowvgap	\utex_limitbelowvgap:D
1038	_kernel_primitive:NN	\Umathnolimitsubfactor	\utex_nolimitsubfactor:D
1039	_kernel_primitive:NN	\Umathnolimitsupfactor	\utex_nolimitsupfactor:D
1040	_kernel_primitive:NN	\Umathopbinspacing	\utex_opbinspacing:D
1041	_kernel_primitive:NN	\Umathopclosespacing	\utex_opclosespacing:D
1042	_kernel_primitive:NN	\Umathopenbinspacing	\utex_openbinspacing:D
1043	_kernel_primitive:NN	\Umathopenclosespacing	\utex_openclosespacing:D
1044	_kernel_primitive:NN	\Umathopeninnerspacing	\utex_openinnerspacing:D
1045	_kernel_primitive:NN	\Umathopenopenspacing	\utex_openopenspacing:D
1046	_kernel_primitive:NN	\Umathopenopspacing	\utex_openopspacing:D
1047	_kernel_primitive:NN	\Umathopenordspacing	\utex_openordspacing:D
1048	_kernel_primitive:NN	\Umathopenpunctspacing	\utex_openpunctspacing:D
1049	_kernel_primitive:NN	\Umathopenrelspacing	\utex_openrelspacing:D
1050	_kernel_primitive:NN	\Umathoperatorsize	\utex_operatorsize:D
1051	_kernel_primitive:NN	\Umathopinnerspacing	\utex_opinnerspacing:D
1052	_kernel_primitive:NN	\Umathopopenspacing	\utex_opopenspacing:D
1053	_kernel_primitive:NN	\Umathopopspacing	\utex_opopspacing:D
1054	_kernel_primitive:NN	\Umathopordspacing	\utex_opordspacing:D
1055	_kernel_primitive:NN	\Umathoppunctspacing	\utex_oppunctspacing:D
1056	_kernel_primitive:NN	\Umathoprelspacing	\utex_oprelspacing:D
1057	_kernel_primitive:NN	\Umathordbinspacing	\utex_ordbinspacing:D
1058	_kernel_primitive:NN	\Umathordclosespacing	\utex_ordclosespacing:D
1059	_kernel_primitive:NN	\Umathordinnerspacing	\utex_ordinnerspacing:D
1060	_kernel_primitive:NN	\Umathordopenspacing	\utex_ordopenspacing:D
1061	_kernel_primitive:NN	\Umathordopspacing	\utex_ordopspacing:D
1062	_kernel_primitive:NN	\Umathordordspacing	\utex_ordordspacing:D
1063	_kernel_primitive:NN	\Umathordpunctspacing	\utex_ordpunctspacing:D
1064	_kernel_primitive:NN	\Umathordrelspacing	\utex_ordrelspacing:D
1065	_kernel_primitive:NN	\Umathoverbarkern	\utex_overbarkern:D
1066	_kernel_primitive:NN	\Umathoverbarrule	\utex_overbarrule:D
1067	_kernel_primitive:NN	\Umathoverbarvgap	\utex_overbarvgap:D
1068	_kernel_primitive:NN	\Umathoverdelimiterbgap	\utex_overdelimiterbgap:D

1069	__kernel_primitive:NN	\Umathoverdelimitervgap	\utex_overdelimitervgap:D
1070	__kernel_primitive:NN	\Umathpunctbinspacing	\utex_punctbinspacing:D
1071	__kernel_primitive:NN	\Umathpunctclosespacing	\utex_punctclosespacing:D
1072	__kernel_primitive:NN	\Umathpunctinnerspacing	\utex_punctinnerspacing:D
1073	__kernel_primitive:NN	\Umathpunctopenspacing	\utex_punctopenspacing:D
1074	__kernel_primitive:NN	\Umathpuncttopspacing	\utex_puncttopspacing:D
1075	__kernel_primitive:NN	\Umathpunctordspacing	\utex_punctordspacing:D
1076	__kernel_primitive:NN	\Umathpunctpunctspacing	\utex_punctpunctspacing:D
1077	__kernel_primitive:NN	\Umathpunctrelspacing	\utex_punctrelspacing:D
1078	__kernel_primitive:NN	\Umathquad	\utex_quad:D
1079	__kernel_primitive:NN	\Umathradicaldegreeafter	\utex_radicaldegreeafter:D
1080	__kernel_primitive:NN	\Umathradicaldegreebefore	\utex_radicaldegreebefore:D
1081	__kernel_primitive:NN	\Umathradicaldegreeraise	\utex_radicaldegreeraise:D
1082	__kernel_primitive:NN	\Umathradicalkern	\utex_radicalkern:D
1083	__kernel_primitive:NN	\Umathradicalrule	\utex_radicalrule:D
1084	__kernel_primitive:NN	\Umathradicalvgap	\utex_radicalvgap:D
1085	__kernel_primitive:NN	\Umathrelbinspacing	\utex_relbinspacing:D
1086	__kernel_primitive:NN	\Umathrelclosespacing	\utex_relclosespacing:D
1087	__kernel_primitive:NN	\Umathrelinnerspacing	\utex_relinnerspacing:D
1088	__kernel_primitive:NN	\Umathrelopenspacing	\utex_reloopenspacing:D
1089	__kernel_primitive:NN	\Umathreltopspacing	\utex_reloptspacing:D
1090	__kernel_primitive:NN	\Umathrelordspacing	\utex_relordspacing:D
1091	__kernel_primitive:NN	\Umathrelpunctspacing	\utex_relpunctspacing:D
1092	__kernel_primitive:NN	\Umathrelrelspacing	\utex_relrelspacing:D
1093	__kernel_primitive:NN	\Umathskewedfractionhgap	\utex_skewedfractionhgap:D
1094	__kernel_primitive:NN	\Umathskewedfractionvgap	\utex_skewedfractionvgap:D
1095	__kernel_primitive:NN	\Umathspaceafterscript	\utex_spaceafterscript:D
1096	__kernel_primitive:NN	\Umathstackdenomdown	\utex_stackdenomdown:D
1097	__kernel_primitive:NN	\Umathstacknumup	\utex_stacknumup:D
1098	__kernel_primitive:NN	\Umathstackvgap	\utex_stackvgap:D
1099	__kernel_primitive:NN	\Umathsubshiftdown	\utex_subshiftdown:D
1100	__kernel_primitive:NN	\Umathsubshiftdrop	\utex_subshiftdrop:D
1101	__kernel_primitive:NN	\Umathsubsupshiftdown	\utex_subsupshiftdown:D
1102	__kernel_primitive:NN	\Umathsubsupvgap	\utex_subsupvgap:D
1103	__kernel_primitive:NN	\Umathsubtopmax	\utex_subtopmax:D
1104	__kernel_primitive:NN	\Umathsupbottommin	\utex_supbottommin:D
1105	__kernel_primitive:NN	\Umathsupshiftdrop	\utex_supshiftdrop:D
1106	__kernel_primitive:NN	\Umathsupshiftup	\utex_supshiftup:D
1107	__kernel_primitive:NN	\Umathsupsubbottommax	\utex_supsubbottommax:D
1108	__kernel_primitive:NN	\Umathunderbarkern	\utex_underbarkern:D
1109	__kernel_primitive:NN	\Umathunderbarrule	\utex_underbarrule:D
1110	__kernel_primitive:NN	\Umathunderbarvgap	\utex_underbarvgap:D
1111	__kernel_primitive:NN	\Umathunderdelimiterbgap	\utex_underdelimiterbgap:D
1112	__kernel_primitive:NN	\Umathunderdelimitervgap	\utex_underdelimitervgap:D
1113	__kernel_primitive:NN	\Uoverdelimiter	\utex_overdelimiter:D
1114	__kernel_primitive:NN	\Uradical	\utex_radical:D
1115	__kernel_primitive:NN	\Uroot	\utex_root:D
1116	__kernel_primitive:NN	\Uskewed	\utex_skewed:D
1117	__kernel_primitive:NN	\Uskewedwithdelims	\utex_skewedwithdelims:D
1118	__kernel_primitive:NN	\Ustack	\utex_stack:D
1119	__kernel_primitive:NN	\Ustartdisplaymath	\utex_startdisplaymath:D
1120	__kernel_primitive:NN	\Ustartmath	\utex_startmath:D
1121	__kernel_primitive:NN	\Ustopdisplaymath	\utex_stopdisplaymath:D
1122	__kernel_primitive:NN	\Ustopmath	\utex_stopmath:D

1123	<code>__kernel_primitive:NN \Usubscript</code>	<code>\utex_subscript:D</code>
1124	<code>__kernel_primitive:NN \Usuperscript</code>	<code>\utex_superscript:D</code>
1125	<code>__kernel_primitive:NN \Uunderdelimit</code>	<code>\utex_underdelimit:D</code>
1126	<code>__kernel_primitive:NN \Uvextensible</code>	<code>\utex_vextensible:D</code>

Primitives from pT_EX.

1127	<code>__kernel_primitive:NN \autospace</code>	<code>\ptex_autospace:D</code>
1128	<code>__kernel_primitive:NN \autoxspace</code>	<code>\ptex_autoxspace:D</code>
1129	<code>__kernel_primitive:NN \dtou</code>	<code>\ptex_dtou:D</code>
1130	<code>__kernel_primitive:NN \euc</code>	<code>\ptex_euc:D</code>
1131	<code>__kernel_primitive:NN \ifdbx</code>	<code>\ptex_ifdbx:D</code>
1132	<code>__kernel_primitive:NN \ifddir</code>	<code>\ptex_ifddir:D</code>
1133	<code>__kernel_primitive:NN \ifmdir</code>	<code>\ptex_ifmdir:D</code>
1134	<code>__kernel_primitive:NN \iftbx</code>	<code>\ptex_iftbx:D</code>
1135	<code>__kernel_primitive:NN \iftdir</code>	<code>\ptex_iftdir:D</code>
1136	<code>__kernel_primitive:NN \ifybx</code>	<code>\ptex_ifybx:D</code>
1137	<code>__kernel_primitive:NN \ifydir</code>	<code>\ptex_ifydir:D</code>
1138	<code>__kernel_primitive:NN \inhibitglue</code>	<code>\ptex_inhibitglue:D</code>
1139	<code>__kernel_primitive:NN \inhibitxspcode</code>	<code>\ptex_inhibitxspcode:D</code>
1140	<code>__kernel_primitive:NN \jcharwidowpenalty</code>	<code>\ptex_jcharwidowpenalty:D</code>
1141	<code>__kernel_primitive:NN \jfam</code>	<code>\ptex_jfam:D</code>
1142	<code>__kernel_primitive:NN \jfont</code>	<code>\ptex_jfont:D</code>
1143	<code>__kernel_primitive:NN \jis</code>	<code>\ptex_jis:D</code>
1144	<code>__kernel_primitive:NN \kanjiskip</code>	<code>\ptex_kanjiskip:D</code>
1145	<code>__kernel_primitive:NN \kansuji</code>	<code>\ptex_kansuji:D</code>
1146	<code>__kernel_primitive:NN \kansujichar</code>	<code>\ptex_kansujichar:D</code>
1147	<code>__kernel_primitive:NN \kcatcode</code>	<code>\ptex_kcatcode:D</code>
1148	<code>__kernel_primitive:NN \kuten</code>	<code>\ptex_kuten:D</code>
1149	<code>__kernel_primitive:NN \noautospace</code>	<code>\ptex_noautospace:D</code>
1150	<code>__kernel_primitive:NN \noautoxspace</code>	<code>\ptex_noautoxspace:D</code>
1151	<code>__kernel_primitive:NN \postbreakpenalty</code>	<code>\ptex_postbreakpenalty:D</code>
1152	<code>__kernel_primitive:NN \prebreakpenalty</code>	<code>\ptex_prebreakpenalty:D</code>
1153	<code>__kernel_primitive:NN \showmode</code>	<code>\ptex_showmode:D</code>
1154	<code>__kernel_primitive:NN \sjis</code>	<code>\ptex_sjis:D</code>
1155	<code>__kernel_primitive:NN \tate</code>	<code>\ptex_tate:D</code>
1156	<code>__kernel_primitive:NN \tbaselineshift</code>	<code>\ptex_tbaselineshift:D</code>
1157	<code>__kernel_primitive:NN \tfont</code>	<code>\ptex_tfont:D</code>
1158	<code>__kernel_primitive:NN \xkanjiskip</code>	<code>\ptex_xkanjiskip:D</code>
1159	<code>__kernel_primitive:NN \xspcode</code>	<code>\ptex_xspcode:D</code>
1160	<code>__kernel_primitive:NN \ybaselineshift</code>	<code>\ptex_ybaselineshift:D</code>
1161	<code>__kernel_primitive:NN \yoko</code>	<code>\ptex_yoko:D</code>

Primitives from upT_EX.

1162	<code>__kernel_primitive:NN \disablecjktoken</code>	<code>\uptex_disablecjktoken:D</code>
1163	<code>__kernel_primitive:NN \enablecjktoken</code>	<code>\uptex_enablecjktoken:D</code>
1164	<code>__kernel_primitive:NN \forcecjktoken</code>	<code>\uptex_forcecjktoken:D</code>
1165	<code>__kernel_primitive:NN \kchar</code>	<code>\uptex_kchar:D</code>
1166	<code>__kernel_primitive:NN \kchardef</code>	<code>\uptex_kchardef:D</code>
1167	<code>__kernel_primitive:NN \kuten</code>	<code>\uptex_kuten:D</code>
1168	<code>__kernel_primitive:NN \ucs</code>	<code>\uptex_ucs:D</code>

End of the “just the names” part of the source.

1169	<code></initex names package></code>
1170	<code><*initex package></code>

The job is done: close the group (using the primitive renamed!).

```
1171 \tex_endgroup:D
```

L^AT_εX moves a few primitives, so these are sorted out. A convenient test for L^AT_εX is the `\@@end` saved primitive.

```
1172 \*package>
1173 \etex_ifdefined:D \@@end
1174 \tex_let:D \tex_end:D \@@end
1175 \tex_let:D \tex_everydisplay:D \frozen@everydisplay
1176 \tex_let:D \tex_everymath:D \frozen@everymath
1177 \tex_let:D \tex_hyphen:D \@@hyph
1178 \tex_let:D \tex_input:D \@@input
1179 \tex_let:D \tex_italiccorrection:D \@@italiccorr
1180 \tex_let:D \tex_underline:D \@@underline
```

The `\shipout` primitive is particularly tricky as a number of packages want to hook in here. First, we see if a sufficiently-new kernel has saved a copy: if it has, just use that. Otherwise, we need to check each of the possible packages/classes that might move it: here, we are looking for those which do *not* delay action to the `\AtBeginDocument` hook. (We cannot use `\primitive` a (u)p_εT_εX doesn't offer it and as that doesn't allow us to make a direct copy of the primitive *itself*.) As we know that L^AT_εX is in use, we use it's `\@tfor` loop here.

```
1181 \etex_ifdefined:D \@@shipout
1182 \tex_let:D \tex_shipout:D \@@shipout
1183 \tex_fi:D
1184 \tex_begingroup:D
1185 \tex_edef:D \l_tmpa_tl { \tex_string:D \shipout }
1186 \tex_edef:D \l_tmpb_tl { \tex_meaning:D \shipout }
1187 \tex_ifx:D \l_tmpa_tl \l_tmpb_tl
1188 \tex_else:D
1189 \tex_expandafter:D \@tfor \tex_expandafter:D \@tempa \tex_string:D :=
1190 \CROP@shipout
1191 \dup@shipout
1192 \GPTorg@shipout
1193 \LL@shipout
1194 \mem@oldshipout
1195 \opem@shipout
1196 \pgfpages@originalshipout
1197 \pr@shipout
1198 \Shipout
1199 \verso@orig@shipout
1200 \do
1201 {
1202 \tex_edef:D \l_tmpb_tl
1203 { \tex_expandafter:D \tex_meaning:D \@tempa }
1204 \tex_ifx:D \l_tmpa_tl \l_tmpb_tl
1205 \tex_global:D \tex_expandafter:D \tex_let:D
1206 \tex_expandafter:D \tex_shipout:D \@tempa
1207 \tex_fi:D
1208 }
1209 \tex_fi:D
1210 \tex_endgroup:D
```

Some tidying up is needed for `\(pdf)tracingfonts`. Newer L^AT_εX has this simply as `\tracingfonts`, but that is overwritten by the L^AT_εX kernel. So any spurious

definition has to be removed, then the real version saved either from the pdfTeX name or from LuaTeX. In the latter case, we leave \@@@tracingfonts available: this might be useful and almost all L^AT_EX 2_ε users will have expl3 loaded by fontspec. (We follow the usual kernel convention that @@ is used for saved primitives.)

```

1211 \tex_let:D \pdfTeX_tracingfonts:D \tex_undefined:D
1212 \etex_ifdefined:D \pdftracingfonts
1213 \tex_let:D \pdfTeX_tracingfonts:D \pdftracingfonts
1214 \tex_else:D
1215 \etex_ifdefined:D \luaTeX_directlua:D
1216 \luaTeX_directlua:D { tex.enableprimitives("@@", {"tracingfonts"}) }
1217 \tex_let:D \pdfTeX_tracingfonts:D \luaTeXtracingfonts
1218 \tex_fi:D
1219 \tex_fi:D
1220 \tex_fi:D

```

That is also true for the LuaTeX primitives under L^AT_EX 2_ε (depending on the format-building date). There are a few primitives that get the right names anyway so are missing here!

```

1221 \etex_ifdefined:D \luaTeXsuppressfontnotfounderror
1222 \tex_let:D \luaTeX_alignmark:D \luaTeXalignmark
1223 \tex_let:D \luaTeX_aligntab:D \luaTeXaligntab
1224 \tex_let:D \luaTeX_attribute:D \luaTeXattribute
1225 \tex_let:D \luaTeX_attributedef:D \luaTeXattributedef
1226 \tex_let:D \luaTeX_catcodetable:D \luaTeXcatcodetable
1227 \tex_let:D \luaTeX_clearmarks:D \luaTeXclearmarks
1228 \tex_let:D \luaTeX_crampeddisplaystyle:D \luaTeXcrampeddisplaystyle
1229 \tex_let:D \luaTeX_crampedscriptscriptstyle:D \luaTeXcrampedscriptscriptstyle
1230 \tex_let:D \luaTeX_crampedscriptstyle:D \luaTeXcrampedscriptstyle
1231 \tex_let:D \luaTeX_crampedtextstyle:D \luaTeXcrampedtextstyle
1232 \tex_let:D \luaTeX_fontid:D \luaTeXfontid
1233 \tex_let:D \luaTeX_formatname:D \luaTeXformatname
1234 \tex_let:D \luaTeX_gleaders:D \luaTeXgleaders
1235 \tex_let:D \luaTeX_initcatcodetable:D \luaTeXinitcatcodetable
1236 \tex_let:D \luaTeX_latelua:D \luaTeXlatelua
1237 \tex_let:D \luaTeX_luaescapestring:D \luaTeXluaescapestring
1238 \tex_let:D \luaTeX_luafunction:D \luaTeXluafunction
1239 \tex_let:D \luaTeX_mathstyle:D \luaTeXmathstyle
1240 \tex_let:D \luaTeX_nokerns:D \luaTeXnokerns
1241 \tex_let:D \luaTeX_noligs:D \luaTeXnoligs
1242 \tex_let:D \luaTeX_outputbox:D \luaTeXoutputbox
1243 \tex_let:D \luaTeX_pageleftoffset:D \luaTeXpageleftoffset
1244 \tex_let:D \luaTeX_pagetopoffset:D \luaTeXpagetopoffset
1245 \tex_let:D \luaTeX_postexhyphenchar:D \luaTeXpostexhyphenchar
1246 \tex_let:D \luaTeX_posthyphenchar:D \luaTeXposthyphenchar
1247 \tex_let:D \luaTeX_preexhyphenchar:D \luaTeXpreexhyphenchar
1248 \tex_let:D \luaTeX_prehyphenchar:D \luaTeXprehyphenchar
1249 \tex_let:D \luaTeX_savecatcodetable:D \luaTeXsavecatcodetable
1250 \tex_let:D \luaTeX_scantextokens:D \luaTeXscantextokens
1251 \tex_let:D \luaTeX_suppressifcsnameerror:D \luaTeXsuppressifcsnameerror
1252 \tex_let:D \luaTeX_suppresslongerror:D \luaTeXsuppresslongerror
1253 \tex_let:D \luaTeX_suppressmathparerror:D \luaTeXsuppressmathparerror
1254 \tex_let:D \luaTeX_suppressoutererror:D \luaTeXsuppressoutererror
1255 \tex_let:D \utex_char:D \luaTeXUchar
1256 \tex_let:D \xetex_suppressfontnotfounderror:D \luaTeXsuppressfontnotfounderror

```

Which also covers those slightly odd ones.

```

1257 \tex_let:D \luatex_bodydir:D \luatexbodydir
1258 \tex_let:D \luatex_boxdir:D \luatexboxdir
1259 \tex_let:D \luatex_leftghost:D \luatexleftghost
1260 \tex_let:D \luatex_localbrokenpenalty:D \luatexlocalbrokenpenalty
1261 \tex_let:D \luatex_localinterlinepenalty:D \luatexlocalinterlinepenalty
1262 \tex_let:D \luatex_localleftbox:D \luatexlocalleftbox
1263 \tex_let:D \luatex_localrightbox:D \luatexlocalrightbox
1264 \tex_let:D \luatex_mathdir:D \luatexmathdir
1265 \tex_let:D \luatex_pagebottomoffset:D \luatexpagebottomoffset
1266 \tex_let:D \luatex_pagedir:D \luatexpagedir
1267 \tex_let:D \pdfTeX_pageheight:D \luatexpageheight
1268 \tex_let:D \luatex_pagerightoffset:D \luatexpagerightoffset
1269 \tex_let:D \pdfTeX_pagewidth:D \luatexpagewidth
1270 \tex_let:D \luatex_pardir:D \luatexpardir
1271 \tex_let:D \luatex_rightghost:D \luatexrightghost
1272 \tex_let:D \luatex_textdir:D \luatextextdir
1273 \tex_fi:D

```

Only pdfTeX and LuaTeX define \pdfmapfile and \pdfmapline: Tidy up the fact that some format-building processes leave a couple of questionable decisions about that!

```

1274 \tex_ifnum:D 0
1275 \etex_ifdefined:D \pdfTeX_pdfTeXversion:D 1 \tex_fi:D
1276 \etex_ifdefined:D \luatex luatexversion:D 1 \tex_fi:D
1277 = 0 %
1278 \tex_let:D \pdfTeX_mapfile:D \tex_undefined:D
1279 \tex_let:D \pdfTeX_mapline:D \tex_undefined:D
1280 \tex_fi:D
1281 \</package>

```

Older XeTeX versions use \XeTeX as the prefix for the Unicode math primitives it knows. That is tidied up here (we support XeTeX versions from 0.9994 but this change was in 0.9999).

```

1282 \*initex | package)
1283 \etex_ifdefined:D \XeTeXdelcode
1284 \tex_let:D \utex_delcode:D \XeTeXdelcode
1285 \tex_let:D \utex_delcodenum:D \XeTeXdelcodenum
1286 \tex_let:D \utex_delimiter:D \XeTeXdelimiter
1287 \tex_let:D \utex_mathaccent:D \XeTeXmathaccent
1288 \tex_let:D \utex_mathchar:D \XeTeXmathchar
1289 \tex_let:D \utex_mathchardef:D \XeTeXmathchardef
1290 \tex_let:D \utex_mathcharnum:D \XeTeXmathcharnum
1291 \tex_let:D \utex_mathcharnumdef:D \XeTeXmathcharnumdef
1292 \tex_let:D \utex_mathcode:D \XeTeXmathcode
1293 \tex_let:D \utex_mathcodenum:D \XeTeXmathcodenum
1294 \tex_fi:D

```

Up to v0.80, LuaTeX defines the pdfTeX version data: rather confusing. Removing them means that \pdfTeX_pdfTeXversion:D is a marker for pdfTeX alone: useful in engine-dependent code later.

```

1295 \etex_ifdefined:D \luatex luatexversion:D
1296 \tex_let:D \pdfTeX_pdfTeXbanner:D \tex_undefined:D
1297 \tex_let:D \pdfTeX_pdfTeXrevision:D \tex_undefined:D
1298 \tex_let:D \pdfTeX_pdfTeXversion:D \tex_undefined:D
1299 \tex_fi:D

```

```
1300 </initex | package>
```

For ConT_EXt, two tests are needed. Both Mark II and Mark IV move several primitives: these are all covered by the first test, again using `\end` as a marker. For Mark IV, a few more primitives are moved: they are implemented using some Lua code in the current ConT_EXt.

```
1301 <*package>
1302 \etex_ifdefined:D \normalend
1303 \tex_let:D \tex_end:D \normalend
1304 \tex_let:D \tex_everyjob:D \normaleveryjob
1305 \tex_let:D \tex_input:D \normalinput
1306 \tex_let:D \tex_language:D \normallanguage
1307 \tex_let:D \tex_mathop:D \normalmathop
1308 \tex_let:D \tex_month:D \normalmonth
1309 \tex_let:D \tex_outer:D \normalouter
1310 \tex_let:D \tex_over:D \normalover
1311 \tex_let:D \tex_vcenter:D \normalvcenter
1312 \tex_let:D \etex_unexpanded:D \normalunexpanded
1313 \tex_let:D \luatex_expanded:D \normalexpanded
1314 \tex_fi:D
1315 \etex_ifdefined:D \normalitaliccorrection
1316 \tex_let:D \tex_hoffset:D \normalhoffset
1317 \tex_let:D \tex_italiccorrection:D \normalitaliccorrection
1318 \tex_let:D \tex_voffset:D \normalvoffset
1319 \tex_let:D \etex_showtokens:D \normalshowtokens
1320 \tex_let:D \luatex_bodydir:D \spac_directions_normal_body_dir
1321 \tex_let:D \luatex_pagedir:D \spac_directions_normal_page_dir
1322 \tex_fi:D
1323 \etex_ifdefined:D \normalleft
1324 \tex_let:D \tex_left:D \normalleft
1325 \tex_let:D \tex_middle:D \normalmiddle
1326 \tex_let:D \tex_right:D \normalright
1327 \tex_fi:D
1328 </package>
1329 </initex | package>
```

3 l3basics implementation

```
1330 <*initex | package>
```

3.1 Renaming some T_EX primitives (again)

Having given all the T_EX primitives a consistent name, we need to give sensible names to the ones we actually want to use. These will be defined as needed in the appropriate modules, but we do a few now, just to get started.⁶

```
\if_true: Then some conditionals.
\if_false: 1331 \tex_let:D \if_true: \tex_iftrue:D
\or: 1332 \tex_let:D \if_false: \tex_iffalse:D
\else: 1333 \tex_let:D \or: \tex_or:D
\fi: 1334 \tex_let:D \else: \tex_else:D
\reverse_if:N
\if:w
\if_charcode:w
\if_catcode:w
\if_meaning:w
```

⁶This renaming gets expensive in terms of csname usage, an alternative scheme would be to just use the `\tex...:D` name in the cases where no good alternative exists.


```

1335 \tex_let:D \fi:                \tex_fi:D
1336 \tex_let:D \reverse_if:N       \etex_unless:D
1337 \tex_let:D \if:w               \tex_if:D
1338 \tex_let:D \if_charcode:w      \tex_if:D
1339 \tex_let:D \if_catcode:w       \tex_ifcat:D
1340 \tex_let:D \if_meaning:w       \tex_ifx:D

```

(End definition for `\if_true:` and others. These functions are documented on page 21.)

```

\tif_mode_math:  TeX lets us detect some if its modes.
\if_mode_horizontal: 1341 \tex_let:D \if_mode_math:      \tex_ifmmode:D
\if_mode_vertical:  1342 \tex_let:D \if_mode_horizontal: \tex_ifhmode:D
\if_mode_inner:     1343 \tex_let:D \if_mode_vertical:   \tex_ifvmode:D
                    1344 \tex_let:D \if_mode_inner:     \tex_ifinner:D

```

(End definition for `\if_mode_math:` and others. These functions are documented on page 21.)

```

\if_cs_exist:N Building csnames and testing if control sequences exist.
\if_cs_exist:w 1345 \tex_let:D \if_cs_exist:N      \etex_ifdefined:D
               \cs:w 1346 \tex_let:D \if_cs_exist:w      \etex_ifcsname:D
               \cs_end: 1347 \tex_let:D \cs:w          \tex_csname:D
                    1348 \tex_let:D \cs_end:        \tex_endcsname:D

```

(End definition for `\if_cs_exist:N` and others. These functions are documented on page 21.)

```

\exp_after:wN The five \exp_ functions are used in the l3expan module where they are described.
\exp_not:N    1349 \tex_let:D \exp_after:wN      \tex_expandafter:D
\exp_not:n    1350 \tex_let:D \exp_not:N        \tex_noexpand:D
              1351 \tex_let:D \exp_not:n          \etex_unexpanded:D
              1352 \tex_let:D \exp:w            \tex_romannumeral:D
              1353 \tex_chardef:D \exp_end: = 0 ~

```

(End definition for `\exp_after:wN`, `\exp_not:N`, and `\exp_not:n`. These functions are documented on page 32.)

```

\token_to_meaning:N Examining a control sequence or token.
\cs_meaning:N       1354 \tex_let:D \token_to_meaning:N \tex_meaning:D
                    1355 \tex_let:D \cs_meaning:N      \tex_meaning:D

```

(End definition for `\token_to_meaning:N` and `\cs_meaning:N`. These functions are documented on page 119.)

```

\tl_to_str:n Making strings.
\token_to_str:N 1356 \tex_let:D \tl_to_str:n      \etex_detokenize:D
                1357 \tex_let:D \token_to_str:N    \tex_string:D

```

(End definition for `\tl_to_str:n` and `\token_to_str:N`. These functions are documented on page 44.)

```

\scan_stop: The next three are basic functions for which there also exist versions that are safe inside
\group_begin: alignments. These safe versions are defined in the l3prg module.
\group_end:  1358 \tex_let:D \scan_stop:        \tex_relax:D
              1359 \tex_let:D \group_begin:      \tex_begingroup:D
              1360 \tex_let:D \group_end:        \tex_endgroup:D

```

(End definition for `\scan_stop:`, `\group_begin:`, and `\group_end:`. These functions are documented on page 9.)

```
1361 <@@=int>
```

`\if_int_compare:w` For integers.

```
\__int_to_roman:w      1362 \tex_let:D \if_int_compare:w    \tex_ifnum:D
                      1363 \tex_let:D \__int_to_roman:w    \tex_romannumeral:D
```

(End definition for `\if_int_compare:w` and `__int_to_roman:w`. This function is documented on page 86.)

`\group_insert_after:N` Adding material after the end of a group.

```
1364 \tex_let:D \group_insert_after:N \tex_aftergroup:D
```

(End definition for `\group_insert_after:N`. This function is documented on page 9.)

`\exp_args:Nc` Discussed in l3expan, but needed much earlier.

```
\exp_args:cc      1365 \tex_long:D \tex_def:D \exp_args:Nc #1#2
                  1366 { \exp_after:wN #1 \cs:w #2 \cs_end: }
                  1367 \tex_long:D \tex_def:D \exp_args:cc #1#2
                  1368 { \cs:w #1 \exp_after:wN \cs_end: \cs:w #2 \cs_end: }
```

(End definition for `\exp_args:Nc` and `\exp_args:cc`. These functions are documented on page 29.)

`\token_to_meaning:c` A small number of variants defined by hand. Some of the necessary functions (`\use_i:nn`, `\use_ii:nn`, and `\exp_args:NNc`) are not defined at that point yet, but will be defined before those variants are used. The `\cs_meaning:c` command must check for an undefined control sequence to avoid defining it mistakenly.

```
\token_to_str:c      1369 \tex_def:D \token_to_str:c { \exp_args:Nc \token_to_str:N }
\cs_meaning:c        1370 \tex_long:D \tex_def:D \cs_meaning:c #1
                    1371 {
                    1372   \if_cs_exist:w #1 \cs_end:
                    1373   \exp_after:wN \use_i:nn
                    1374   \else:
                    1375   \exp_after:wN \use_ii:nn
                    1376   \fi:
                    1377   { \exp_args:Nc \cs_meaning:N {#1} }
                    1378   { \tl_to_str:n {undefined} }
                    1379   }
                    1380 \tex_let:D \token_to_meaning:c = \cs_meaning:c
```

(End definition for `\token_to_meaning:N`. This function is documented on page 119.)

3.2 Defining some constants

`\c_zero` We need the constant `\c_zero` which is used by some functions in the `l3alloc` module. The rest are defined in the `l3int` module – at least for the ones that can be defined with `\tex_chardef:D` or `\tex_mathchardef:D`. For other constants the `l3int` module is required but it can't be used until the allocation has been set up properly!

```
1381 \tex_chardef:D \c_zero = 0 ~
```

(End definition for `\c_zero`. This variable is documented on page 85.)

`\c_max_register_int` This is here as this particular integer is needed both in package mode and to bootstrap l3alloc, and is documented in l3int.

```

1382 \etex_ifdefined:D \luatex luatexversion:D
1383   \tex_chardef:D \c_max_register_int = 65 535 ~
1384 \tex_else:D
1385   \tex_mathchardef:D \c_max_register_int = 32 767 ~
1386 \tex_fi:D

```

(End definition for `\c_max_register_int`. This variable is documented on page 85.)

3.3 Defining functions

We start by providing functions for the typical definition functions. First the local ones.

`\cs_set_nopar:Npn` All assignment functions in L^AT_EX3 should be naturally protected; after all, the T_EX primitives for assignments are and it can be a cause of problems if others aren't.

```

\cs_set_nopar:Npn
\cs_set_nopar:Npx
  \cs_set:Npn
  \cs_set:Npx
\cs_set_protected_nopar:Npn
\cs_set_protected_nopar:Npx
  \cs_set_protected:Npn
  \cs_set_protected:Npx
1387 \tex_let:D \cs_set_nopar:Npn          \tex_def:D
1388 \tex_let:D \cs_set_nopar:Npx          \tex_edef:D
1389 \etex_protected:D \tex_long:D \tex_def:D \cs_set:Npn
1390   { \tex_long:D \tex_def:D }
1391 \etex_protected:D \tex_long:D \tex_def:D \cs_set:Npx
1392   { \tex_long:D \tex_edef:D }
1393 \etex_protected:D \tex_long:D \tex_def:D \cs_set_protected_nopar:Npn
1394   { \etex_protected:D \tex_def:D }
1395 \etex_protected:D \tex_long:D \tex_def:D \cs_set_protected_nopar:Npx
1396   { \etex_protected:D \tex_edef:D }
1397 \etex_protected:D \tex_long:D \tex_def:D \cs_set_protected:Npn
1398   { \etex_protected:D \tex_long:D \tex_def:D }
1399 \etex_protected:D \tex_long:D \tex_def:D \cs_set_protected:Npx
1400   { \etex_protected:D \tex_long:D \tex_edef:D }

```

(End definition for `\cs_set_nopar:Npn` and others. These functions are documented on page 11.)

`\cs_gset_nopar:Npn` Global versions of the above functions.

```

\cs_gset_nopar:Npn
\cs_gset_nopar:Npx
  \cs_gset:Npn
  \cs_gset:Npx
\cs_gset_protected_nopar:Npn
\cs_gset_protected_nopar:Npx
  \cs_gset_protected:Npn
  \cs_gset_protected:Npx
1401 \tex_let:D \cs_gset_nopar:Npn          \tex_gdef:D
1402 \tex_let:D \cs_gset_nopar:Npx          \tex_xdef:D
1403 \cs_set_protected:Npn \cs_gset:Npn
1404   { \tex_long:D \tex_gdef:D }
1405 \cs_set_protected:Npn \cs_gset:Npx
1406   { \tex_long:D \tex_xdef:D }
1407 \cs_set_protected:Npn \cs_gset_protected_nopar:Npn
1408   { \etex_protected:D \tex_gdef:D }
1409 \cs_set_protected:Npn \cs_gset_protected_nopar:Npx
1410   { \etex_protected:D \tex_xdef:D }
1411 \cs_set_protected:Npn \cs_gset_protected:Npn
1412   { \etex_protected:D \tex_long:D \tex_gdef:D }
1413 \cs_set_protected:Npn \cs_gset_protected:Npx
1414   { \etex_protected:D \tex_long:D \tex_xdef:D }

```

(End definition for `\cs_gset_nopar:Npn` and others. These functions are documented on page 12.)

3.4 Selecting tokens

1415 <@@=exp>

`\l__exp_internal_tl` Scratch token list variable for `l3expan`, used by `\use:x`, used in defining conditionals. We don't use `tl` methods because `l3basics` is loaded earlier.

1416 `\cs_set_nopar:Npn \l__exp_internal_tl { }`

(End definition for `\l__exp_internal_tl`.)

`\use:c` This macro grabs its argument and returns a csname from it.

1417 `\cs_set:Npn \use:c #1 { \cs:w #1 \cs_end: }`

(End definition for `\use:c`. This function is documented on page 16.)

`\use:x` Fully expands its argument and passes it to the input stream. Uses the reserved `\l__exp_internal_tl` which will be set up in `l3expan`.

1418 `\cs_set_protected:Npn \use:x #1`
 1419 `{`
 1420 `\cs_set_nopar:Npx \l__exp_internal_tl {#1}`
 1421 `\l__exp_internal_tl`
 1422 `}`

(End definition for `\use:x`. This function is documented on page 19.)

`\use:n` These macros grab their arguments and returns them back to the input (with outer braces removed).

`\use:nnn` 1423 `\cs_set:Npn \use:n #1 {#1}`
`\use:nnnn` 1424 `\cs_set:Npn \use:nn #1#2 {#1#2}`
 1425 `\cs_set:Npn \use:nnn #1#2#3 {#1#2#3}`
 1426 `\cs_set:Npn \use:nnnn #1#2#3#4 {#1#2#3#4}`

(End definition for `\use:n` and others. These functions are documented on page 17.)

`\use_i:nn` The equivalent to L^AT_EX 2_ε's `\@firstoftwo` and `\@secondoftwo`.

`\use_ii:nn` 1427 `\cs_set:Npn \use_i:nn #1#2 {#1}`
 1428 `\cs_set:Npn \use_ii:nn #1#2 {#2}`

(End definition for `\use_i:nn` and `\use_ii:nn`. These functions are documented on page 18.)

`\use_i:nnn` We also need something for picking up arguments from a longer list.

`\use_ii:nnn` 1429 `\cs_set:Npn \use_i:nnn #1#2#3 {#1}`
`\use_iii:nnn` 1430 `\cs_set:Npn \use_ii:nnn #1#2#3 {#2}`
`\use_i_ii:nnn` 1431 `\cs_set:Npn \use_iii:nnn #1#2#3 {#3}`
`\use_i:nnnn` 1432 `\cs_set:Npn \use_i_ii:nnn #1#2#3 {#1#2}`
`\use_ii:nnnn` 1433 `\cs_set:Npn \use_i:nnnn #1#2#3#4 {#1}`
`\use_iii:nnnn` 1434 `\cs_set:Npn \use_ii:nnnn #1#2#3#4 {#2}`
`\use_iv:nnnn` 1435 `\cs_set:Npn \use_iii:nnnn #1#2#3#4 {#3}`
 1436 `\cs_set:Npn \use_iv:nnnn #1#2#3#4 {#4}`

(End definition for `\use_i:nnn` and others. These functions are documented on page 18.)

`\use_none_delimit_by_q_nil:w` Functions that gobble everything until they see either `\q_nil`, `\q_stop`, or `\q_recursion_stop`, respectively.

`\use_none_delimit_by_q_stop:w`
`\use_none_delimit_by_q_recursion_stop:w` 1437 `\cs_set:Npn \use_none_delimit_by_q_nil:w #1 \q_nil { }`
 1438 `\cs_set:Npn \use_none_delimit_by_q_stop:w #1 \q_stop { }`
 1439 `\cs_set:Npn \use_none_delimit_by_q_recursion_stop:w #1 \q_recursion_stop { }`

(End definition for `\use_none_delimit_by_q_nil:w`, `\use_none_delimit_by_q_stop:w`, and `\use_none_delimit_by_q_recursion_stop:w`. These functions are documented on page 19.)

`\use_i_delimit_by_q_nil:nw` Same as above but execute first argument after gobbling. Very useful when you need to skip the rest of a mapping sequence but want an easy way to control what should be expanded next.

```
1440 \cs_set:Npn \use_i_delimit_by_q_nil:nw #1#2 \q_nil {#1}
1441 \cs_set:Npn \use_i_delimit_by_q_stop:nw #1#2 \q_stop {#1}
1442 \cs_set:Npn \use_i_delimit_by_q_recursion_stop:nw #1#2 \q_recursion_stop {#1}
```

(End definition for `\use_i_delimit_by_q_nil:nw`, `\use_i_delimit_by_q_stop:nw`, and `\use_i_delimit_by_q_recursion_stop:nw`. These functions are documented on page 19.)

3.5 Gobbling tokens from input

`\use_none:n` To gobble tokens from the input we use a standard naming convention: the number of tokens gobbled is given by the number of n's following the : in the name. Although we could define functions to remove ten arguments or more using separate calls of `\use_none:nnnnn`, this is very non-intuitive to the programmer who will assume that expanding such a function once takes care of gobbling all the tokens in one go.

```
1443 \cs_set:Npn \use_none:n #1 { }
1444 \cs_set:Npn \use_none:nn #1#2 { }
1445 \cs_set:Npn \use_none:nnn #1#2#3 { }
1446 \cs_set:Npn \use_none:nnnn #1#2#3#4 { }
1447 \cs_set:Npn \use_none:nnnnn #1#2#3#4#5 { }
1448 \cs_set:Npn \use_none:nnnnnn #1#2#3#4#5#6 { }
1449 \cs_set:Npn \use_none:nnnnnnn #1#2#3#4#5#6#7 { }
1450 \cs_set:Npn \use_none:nnnnnnnn #1#2#3#4#5#6#7#8 { }
1451 \cs_set:Npn \use_none:nnnnnnnnn #1#2#3#4#5#6#7#8#9 { }
```

(End definition for `\use_none:n` and others. These functions are documented on page 18.)

3.6 Debugging and patching later definitions

```
1452 <@@=debug>
```

`__debug:TF` A more meaningful test of whether debugging is enabled than messing up with guards. We can also more easily change the logic in one place then. At present, debugging is disabled in the format and in generic mode, while in L^AT_EX 2_ε mode it is enabled if one of the options `enable-debug`, `log-functions` or `check-declarations` was given.

```
1453 \cs_set_protected:Npn \__debug:TF #1#2 {#2}
1454 <*package>
1455 \tex_ifodd:D \l@expl@enable@debug@bool
1456 \cs_set_protected:Npn \__debug:TF #1#2 {#1}
1457 \fi:
1458 </package>
```

(End definition for `__debug:TF`.)

```
\debug_on:n
\debug_off:n
1459 \__debug:TF
1460 {
1461   \cs_set_protected:Npn \debug_on:n #1
1462   {
```

```

1463     \exp_args:No \clist_map_inline:nn { \tl_to_str:n {#1} }
1464     {
1465         \cs_if_exist_use:cF { __debug_##1_on: }
1466         { \__msg_kernel_error:nnn { kernel } { debug } {##1} }
1467     }
1468 }
1469 \cs_set_protected:Npn \debug_off:n #1
1470 {
1471     \exp_args:No \clist_map_inline:nn { \tl_to_str:n {#1} }
1472     {
1473         \cs_if_exist_use:cF { __debug_##1_off: }
1474         { \__msg_kernel_error:nnn { kernel } { debug } {##1} }
1475     }
1476 }
1477 }
1478 {
1479     \cs_set_protected:Npn \debug_on:n #1
1480     {
1481         \__msg_kernel_error:nnx { kernel } { enable-debug }
1482         { \tl_to_str:n { \debug_on:n {#1} } }
1483     }
1484     \cs_set_protected:Npn \debug_off:n #1
1485     {
1486         \__msg_kernel_error:nnx { kernel } { enable-debug }
1487         { \tl_to_str:n { \debug_off:n {#1} } }
1488     }
1489 }

```

(End definition for `\debug_on:n` and `\debug_off:n`. These functions are documented on page 239.)

\debug_suspend: Suspend and resume locally all debug-related errors and logging except deprecation errors.

\debug_resume: The `\debug_suspend:` and `\debug_resume:` pairs can be nested. We keep track of

`__debug_suspended:T` nesting in a token list containing a number of periods. At first begin with the “non-suspended” version of `__debug_suspended:T`.

```

1490 \__debug:TF
1491 {
1492     \cs_set_nopar:Npn \l__debug_suspended_tl { }
1493     \cs_set_protected:Npn \debug_suspend:
1494     {
1495         \tl_put_right:Nn \l__debug_suspended_tl { . }
1496         \cs_set_eq:NN \__debug_suspended:T \use:n
1497     }
1498     \cs_set_protected:Npn \debug_resume:
1499     {
1500         \tl_set:Nx \l__debug_suspended_tl
1501         { \tl_tail:N \l__debug_suspended_tl }
1502         \tl_if_empty:NT \l__debug_suspended_tl
1503         {
1504             \cs_set_eq:NN \__debug_suspended:T \use_none:n
1505         }
1506     }
1507     \cs_set:Npn \__debug_suspended:T #1 { }
1508 }
1509 {

```

```

1510     \cs_set_protected:Npn \debug_suspend: { }
1511     \cs_set_protected:Npn \debug_resume: { }
1512 }

```

(End definition for `\debug_suspend:` and others. These functions are documented on page 239.)

```

\__debug_check-declarations_on:
\__debug_check-declarations_off:
\__debug_chk_var_exist:N
\__debug_chk_cs_exist:N
\__debug_chk_cs_exist:c
\__debug_chk_var_local:N
\__debug_chk_var_global:N
\__debug_chk_var_scope:NN

```

When debugging is enabled these two functions set up functions that test their argument (when `check-declarations` is active)

- `__debug_chk_var_exist:N` and `__debug_chk_cs_exist:N`, two functions that test that their argument is defined;
- `__debug_chk_var_scope:NN` that checks that its argument #2 has scope #1.
- `__debug_chk_var_local:N` and `__debug_chk_var_global:N` that perform both checks.

```

1513 \__debug:TF
1514 {
1515     \exp_args:Nc \cs_set_protected:Npn { __debug_check-declarations_on: }
1516     {
1517         \cs_set_protected:Npn \__debug_chk_var_exist:NN ##1
1518         {
1519             \__debug_suspended:T \use_none:nnn
1520             \cs_if_exist:NF ##1
1521             {
1522                 \__msg_kernel_error:nxx { kernel } { non-declared-variable }
1523                 { \token_to_str:N ##1 }
1524             }
1525         }
1526         \cs_set_protected:Npn \__debug_chk_cs_exist:N ##1
1527         {
1528             \__debug_suspended:T \use_none:nnn
1529             \cs_if_exist:NF ##1
1530             {
1531                 \__msg_kernel_error:nxx { kernel } { command-not-defined }
1532                 { \token_to_str:N ##1 }
1533             }
1534         }
1535         \cs_set_protected:Npn \__debug_chk_var_scope:NN
1536         {
1537             \__debug_suspended:T \use_none:nnn
1538             \__debug_chk_var_scope_aux:NN
1539         }
1540         \cs_set_protected:Npn \__debug_chk_var_local:N ##1
1541         {
1542             \__debug_suspended:T \use_none:nnnnn
1543             \__debug_chk_var_exist:N ##1
1544             \__debug_chk_var_scope_aux:NN l ##1
1545         }
1546         \cs_set_protected:Npn \__debug_chk_var_global:N ##1
1547         {
1548             \__debug_suspended:T \use_none:nnnnn
1549             \__debug_chk_var_exist:N ##1
1550             \__debug_chk_var_scope_aux:NN g ##1

```

```

1551     }
1552   }
1553   \exp_args:Nc \cs_set_protected:Npn { __debug_check-declarations_off: }
1554   {
1555     \cs_set_protected:Npn \__debug_chk_var_exist:N ##1 { }
1556     \cs_set_protected:Npn \__debug_chk_cs_exist:N ##1 { }
1557     \cs_set_protected:Npn \__debug_chk_var_local:N ##1 { }
1558     \cs_set_protected:Npn \__debug_chk_var_global:N ##1 { }
1559     \cs_set_protected:Npn \__debug_chk_var_scope:NN ##1##2 { }
1560   }
1561   \cs_set_protected:Npn \__debug_chk_cs_exist:c
1562   { \exp_args:Nc \__debug_chk_cs_exist:N }
1563   \tex_ifodd:D \l@expl@check@declarations@bool
1564   \use:c { __debug_check-declarations_on: }
1565   \else:
1566     \use:c { __debug_check-declarations_off: }
1567   \fi:
1568 }
1569 { }

```

(End definition for `__debug_check-declarations_on:` and others.)

`__debug_chk_var_scope_aux:NN` First check whether the name of the variable #2 starts with $\langle letter \rangle$ _. If it does then pass that letter, the $\langle scope \rangle$, and the variable name to `__debug_chk_var_scope_aux:NNn`.
`__debug_chk_var_scope_aux:NNn` That function compares the two letters and triggers an error if they differ (the `\scan_stop:` case is not reachable here). If the second character was not _ then pass the same data to the same auxiliary, except for its first argument which is now a control sequence.
`__debug_chk_var_scope_aux:NNn` That control sequence is actually a token list (but to avoid triggering the checking code we manipulate it using `\cs_set_nopar:Npn`) containing a single letter $\langle scope \rangle$ according to what the first assignment to the given variable was.

```

1570 \__debug:TF
1571 {
1572   \cs_set_protected:Npn \__debug_chk_var_scope_aux:NN #1#2
1573   { \exp_args:NNf \__debug_chk_var_scope_aux:Nn #1 { \cs_to_str:N #2 } }
1574   \cs_set_protected:Npn \__debug_chk_var_scope_aux:Nn #1#2
1575   {
1576     \if:w _ \use_i:nn \use_i_delimit_by_q_stop:nw #2 ? ? \q_stop
1577     \exp_after:wN \__debug_chk_var_scope_aux:NNn
1578     \use_i_delimit_by_q_stop:nw #2 ? \q_stop
1579     #1 {#2}
1580   \else:
1581     \exp_args:Nc \__debug_chk_var_scope_aux:NNn
1582     { __debug_chk_/ #2 }
1583     #1 {#2}
1584   \fi:
1585 }
1586 \cs_set_protected:Npn \__debug_chk_var_scope_aux:NNn #1#2#3
1587 {
1588   \if:w #1 #2
1589   \else:
1590     \if:w #1 \scan_stop:
1591     \cs_gset_nopar:Npn #1 {#2}
1592   \else:
1593     \__msg_kernel_error:nxxx { kernel } { local-global }

```



```

1594         {#1} {#2} { \iow_char:N \ \ #3 }
1595         \fi:
1596     \fi:
1597 }
1598 }
1599 { }

```

(End definition for `__debug_chk_var_scope_aux:NN`, `__debug_chk_var_scope_aux:Nn`, and `__debug_chk_var_scope_aux:NNn`.)

```

\__debug_check-expressions_on:
\__debug_check-expressions_off:
\__debug_chk_expr:nNnN
\__debug_chk_expr_aux:nNnN

```

When debugging is enabled these two functions set `__debug_chk_expr:nNnN` to test or not whether the given expression is valid. The idea is to evaluate the expression within a brace group (to catch trailing `\use_none:n` or similar), then test that the result is what we expect. This is done by turning it to an integer and hitting that with `\tex_romannumeral:D` after replacing the first character by `-0`. If all goes well, that primitive finds a non-positive integer and gives an empty output. If the original expression evaluation stopped early it leaves a trailing `\tex_relax:D`, which stops the second evaluation (used to convert to integer) before it encounters the final `\tex_relax:D`. Since `\tex_romannumeral:D` does not absorb `\tex_relax:D` the output will be nonempty. Note that `#3` is empty except for mu expressions for which it is `\etex_mutogluue:D` to avoid an “incompatible glue units” error. Note also that if we had omitted the first `\tex_relax:D` then for instance `1+2\relax+3` would incorrectly be accepted as a valid integer expression.

```

1600 \__debug:TF
1601 {
1602     \exp_args:Nc \cs_set_protected:Npn { __debug_check-expressions_on: }
1603     {
1604         \cs_set:Npn \__debug_chk_expr:nNnN ##1##2
1605         {
1606             \__debug_suspended:T { ##1 \use_none:nnnnnnn }
1607             \exp_after:wN \__debug_chk_expr_aux:nNnN
1608             \exp_after:wN { \tex_the:D ##2 ##1 \tex_relax:D }
1609             ##2
1610         }
1611     }
1612     \exp_args:Nc \cs_set_protected:Npn { __debug_check-expressions_off: }
1613     { \cs_set:Npn \__debug_chk_expr:nNnN ##1##2##3##4 {##1} }
1614     \use:c { __debug_check-expressions_off: }
1615     \cs_set:Npn \__debug_chk_expr_aux:nNnN #1#2#3#4
1616     {
1617         \tl_if_empty:oF
1618         {
1619             \tex_romannumeral:D - 0
1620             \exp_after:wN \use_none:n
1621             \__int_value:w #3 #2 #1 \tex_relax:D
1622         }
1623         {
1624             \__msg_kernel_expandable_error:nnnn
1625             { kernel } { expr } {#4} {#1}
1626         }
1627         #1
1628     }
1629 }
1630 { }

```

(End definition for `__debug_check-expressions_on:` and others.)

`__debug_log-functions_on:` These two functions (corresponding to the `expl3` option `log-functions`) control whether
`__debug_log-functions_off:` `__debug_log:x` writes to the log file or not. Since `\iow_log:x` does not yet have its
`__debug_log:x` final definition we do not use `\cs_set_eq:NN` (not defined yet anyway). Once everything
is defined, turn logging on or off depending on what option was given. When debugging
is not enabled, simply produce an error.

```

1631 \__debug:TF
1632 {
1633   \exp_args:Nc \cs_set_protected:Npn { __debug_log-functions_on: }
1634   {
1635     \cs_set_protected:Npn \__debug_log:x
1636     { \__debug_suspended:T \use_none:nn \iow_log:x }
1637   }
1638   \exp_args:Nc \cs_set_protected:Npn { __debug_log-functions_off: }
1639   { \cs_set_protected:Npn \__debug_log:x { \use_none:n } }
1640   \tex_ifodd:D \l@expl@log@functions@bool
1641   \use:c { __debug_log-functions_on: }
1642   \else:
1643   \use:c { __debug_log-functions_off: }
1644   \fi:
1645 }
1646 { }

```

(End definition for `__debug_log-functions_on:`, `__debug_log-functions_off:`, and `__debug_log:x`.)

`__debug_deprecation_on:` Some commands were more recently deprecated and not yet removed; only make these
`__debug_deprecation_off:` into errors if the user requests it. This relies on two token lists, mostly filled up by calls
`\g__debug_deprecation_on_tl` to `__debug_deprecation:nnNNpn` in each module.
`\g__debug_deprecation_off_tl`

```

1647 \__debug:TF
1648 {
1649   \cs_set_protected:Npn \__debug_deprecation_on:
1650   { \g__debug_deprecation_on_tl }
1651   \cs_set_protected:Npn \__debug_deprecation_off:
1652   { \g__debug_deprecation_off_tl }
1653   \cs_set_nopar:Npn \g__debug_deprecation_on_tl { }
1654   \cs_set_nopar:Npn \g__debug_deprecation_off_tl { }
1655 }
1656 { }

```

(End definition for `__debug_deprecation_on:` and others.)

`__debug_deprecation:nnNNpn` Grab a definition (at present, must be `\cs_new_protected:Npn`). Add to `\g__debug_deprecation_on_tl` some code that makes the defined macro #3 outer (and defines it as
`__debug_deprecation_aux:nnNnn` an error). Add to `\g__debug_deprecation_off_tl` the definition itself. In both cases
we undefine the token with `\tex_let:D` to avoid taking a potentially outer macro as the
argument of some `expl3` function. Finally define the macro itself to produce a warning
then redefine and call itself. The macro initially takes no parameters: together with
the `x`-expanding assignment and `\exp_not:n` this gives a convenient way of storing the
macro's definition in itself in order to only produce the warning once for each macro. If
debugging is disabled, `__debug_deprecation:nnNNpn` lets the definition happen.

```

1657 \__debug:TF

```

```

1658 {
1659   \cs_set_protected:Npn \__debug_deprecation:nnNNpn #1#2#3#4#5#
1660   {
1661     \if_meaning:w \cs_new_protected:Npn #3
1662     \else:
1663       \__msg_kernel_error:nxx { kernel } { debug-unpatchable }
1664       { \token_to_str:N #3 ~(for~deprecation) }
1665     \fi:
1666     \__debug_deprecation_aux:nnNnn {#1} {#2} #4 {#5}
1667   }
1668   \cs_set_protected:Npn \__debug_deprecation_aux:nnNnn #1#2#3#4#5
1669   {
1670     \tl_gput_right:Nn \g__debug_deprecation_on_tl
1671     {
1672       \tex_let:D #3 \scan_stop:
1673       \__deprecation_error:Nnn #3 {#2} {#1}
1674     }
1675     \tl_gput_right:Nn \g__debug_deprecation_off_tl
1676     {
1677       \tex_let:D #3 \scan_stop:
1678       \cs_set_protected:Npn #3 #4 {#5}
1679     }
1680     \cs_new_protected:Npx #3
1681     {
1682       \exp_not:N \__msg_kernel_warning:nnxxx
1683       { kernel } { deprecated-command }
1684       {#1} { \token_to_str:N #3 } { \tl_to_str:n {#2} }
1685       \exp_not:n { \cs_gset_protected:Npn #3 #4 {#5} }
1686       \exp_not:N #3
1687     }
1688   }
1689 }
1690 { \cs_set_protected:Npn \__debug_deprecation:nnNNpn #1#2 { } }

```

(End definition for __debug_deprecation:nnNNpn and __debug_deprecation_aux:nnNnn.)

__debug_patch:nnNNpn
 __debug_patch_conditional:nnNpnn
 __debug_patch_aux:nnnn
 __debug_patch_auxii:nnnn

When debugging is not enabled, __debug_patch:nnNNpn and __debug_patch_conditional:nnNpnn throw the patch away. Otherwise they can be followed by \cs_new:Npn (or similar), and \prg_new_conditional:Npnn (or similar), respectively. In each case, grab the name of the function to be defined and its parameters then insert tokens before and/or after the definition.

```

1691 \__debug:TF
1692 {
1693   \cs_set_protected:Npn \__debug_patch:nnNNpn #1#2#3#4#5#
1694   { \__debug_patch_aux:nnnn {#1} {#2} { #3 #4 #5 } }
1695   \cs_set_protected:Npn \__debug_patch_conditional:nnNpnn #1#2#3#4#
1696   { \__debug_patch_auxii:nnnn {#1} { #2 #3 #4 } }
1697   \cs_set_protected:Npn \__debug_patch_aux:nnnn #1#2#3#4
1698   { #3 { #1 #4 #2 } }
1699   \cs_set_protected:Npn \__debug_patch_auxii:nnnn #1#2#3#4
1700   { #2 {#3} { #1 #4 } }
1701 }
1702 {
1703   \cs_set_protected:Npn \__debug_patch:nnNNpn #1#2 { }

```

```

1704     \cs_set_protected:Npn \__debug_patch_conditional:nNNpnn #1 { }
1705 }

```

(End definition for __debug_patch:nnNNpn and others.)

```

\__debug_patch_args:nNNpn See \__debug_patch:nnNNpn. The first argument is something like {#1}{( #2)}. Define
\__debug_patch_conditional_args:nNNpnn a temporary macro using the parameters and code of the definition that follows, then
\__debug_patch_args:nnnNNpn expand that temporary macro in front of the first argument to obtain new code. Then
\__debug_patch_conditional_args:nnnNNpnn perform the definition as if that new code was directly typed in the file.
\__debug_tmp:w
\__debug_patch_args_aux:nnnNNnn
\__debug_patch_args_aux:nnnNNnnn
\__debug_patch_args_aux:nnnn
1706 \cs_set_protected:Npn \__debug_patch_args:nNNpn
1707 { \__debug_patch_args:nnnNNpn { } { } }
1708 \cs_set_protected:Npn \__debug_patch_conditional_args:nNNpnn
1709 { \__debug_patch_conditional_args:nnnNNpnn { } { } }
1710 \__debug:TF
1711 {
1712   \cs_set_protected:Npn \__debug_patch_args:nnnNNpn #1#2#3#4#5#6#
1713   { \__debug_patch_args_aux:nnnNNnn {#1} {#2} {#3} #4 #5 {#6} }
1714   \cs_set_protected:Npn \__debug_patch_conditional_args:nnnNNpnn #1#2#3#4#5#6#
1715   { \__debug_patch_args_aux:nnnNNnnn {#1} {#2} {#3} #4 #5 {#6} }
1716   \cs_set_protected:Npn \__debug_patch_args_aux:nnnNNnn #1#2#3#4#5#6#7
1717   {
1718     \cs_set:Npn \__debug_tmp:w #6 {#7}
1719     \exp_after:wN \__debug_patch_args_aux:nnnn \exp_after:wN
1720     { \__debug_tmp:w #3 } { #4 #5 #6 } {#1} {#2}
1721   }
1722   \cs_set_protected:Npn \__debug_patch_args_aux:nnnNNnnn #1#2#3#4#5#6#7#8
1723   {
1724     \cs_set:Npn \__debug_tmp:w #6 {#8}
1725     \exp_after:wN \__debug_patch_args_aux:nnnn \exp_after:wN
1726     { \__debug_tmp:w #3 } { #4 #5 #6 {#7} } {#1} {#2}
1727   }
1728   \cs_set_protected:Npn \__debug_patch_args_aux:nnnn #1#2#3#4
1729   { #2 { #3 #1 #4 } }
1730 }
1731 {
1732   \cs_set_protected:Npn \__debug_patch_args:nnnNNpn #1#2#3 { }
1733   \cs_set_protected:Npn \__debug_patch_conditional_args:nnnNNpnn #1#2#3 { }
1734 }

```

(End definition for __debug_patch_args:nNNpn and others.)

3.7 Conditional processing and definitions

```

1735 <@@=prg>

```

Underneath any predicate function (`_p`) or other conditional forms (TF, etc.) is a built-in logic saying that it after all of the testing and processing must return the *state* this leaves $\text{T}_{\text{E}}\text{X}$ in. Therefore, a simple user interface could be something like

```

\if_meaning:w #1#2
\prg_return_true:
\else:
\if_meaning:w #1#3
\prg_return_true:
\else:

```

```

\prg_return_false:
\fi:
\fi:

```

Usually, a T_EX programmer would have to insert a number of `\exp_after:wN`s to ensure the state value is returned at exactly the point where the last conditional is finished. However, that obscures the code and forces the T_EX programmer to prove that he/she knows the $2^n - 1$ table. We therefore provide the simpler interface.

`\prg_return_true:` The idea here is that `\exp:w` expands fully any `\else:` and `\fi:` that are waiting to be discarded, before reaching the `\exp_end:` which leaves an empty expansion. The code can then leave either the first or second argument in the input stream. This means that all of the branching code has to contain at least two tokens: see how the logical tests are actually implemented to see this.

```

1736 \cs_set:Npn \prg_return_true:
1737   { \exp_after:wN \use_i:nn \exp:w }
1738 \cs_set:Npn \prg_return_false:
1739   { \exp_after:wN \use_ii:nn \exp:w }

```

An extended state space could be implemented by including a more elaborate function in place of `\use_i:nn/\use_ii:nn`. Provided two arguments are absorbed then the code would work.

(End definition for \prg_return_true: and \prg_return_false:. These functions are documented on page 98.)

`\prg_set_conditional:Npnn` The user functions for the types using parameter text from the programmer. The various functions only differ by which function is used for the assignment. For those `Npnn` type functions, we must grab the parameter text, reading everything up to a left brace before continuing. Then split the base function into name and signature, and feed `{\langle name \rangle}` `{\langle signature \rangle}` `\langle boolean \rangle` `{\langle set or new \rangle}` `{\langle maybe protected \rangle}` `{\langle parameters \rangle}` `{TF,...}` `{\langle code \rangle}` to the auxiliary function responsible for defining all conditionals.

```

1740 \cs_set_protected:Npn \prg_set_conditional:Npnn
1741   { \prg_generate_conditional_parm:nnNpnn { set } { } }
1742 \cs_set_protected:Npn \prg_new_conditional:Npnn
1743   { \prg_generate_conditional_parm:nnNpnn { new } { } }
1744 \cs_set_protected:Npn \prg_set_protected_conditional:Npnn
1745   { \prg_generate_conditional_parm:nnNpnn { set } { _protected } }
1746 \cs_set_protected:Npn \prg_new_protected_conditional:Npnn
1747   { \prg_generate_conditional_parm:nnNpnn { new } { _protected } }
1748 \cs_set_protected:Npn \prg_generate_conditional_parm:nnNpnn #1#2#3#4#
1749   {
1750     \cs_split_function:NN #3 \prg_generate_conditional:nnNnnnnn
1751     {#1} {#2} {#4}
1752   }

```

(End definition for \prg_set_conditional:Npnn and others. These functions are documented on page 96.)

`\prg_set_conditional:Nnn` The user functions for the types automatically inserting the correct parameter text based on the signature. The various functions only differ by which function is used for the assignment. Split the base function into name and signature. The second auxiliary generates the parameter text from the number of letters in the signature. Then feed `{\langle name \rangle}` `{\langle signature \rangle}` `\langle boolean \rangle` `{\langle set or new \rangle}` `{\langle maybe protected \rangle}` `{\langle parameters \rangle}`

{TF,...} {\code} to the auxiliary function responsible for defining all conditionals. If the *signature* has more than 9 letters, the definition is aborted since T_EX macros have at most 9 arguments. The erroneous case where the function name contains no colon is captured later.

```

1753 \cs_set_protected:Npn \prg_set_conditional:Nnn
1754   { \prg_generate_conditional_count:nnNnn { set } { } }
1755 \cs_set_protected:Npn \prg_new_conditional:Nnn
1756   { \prg_generate_conditional_count:nnNnn { new } { } }
1757 \cs_set_protected:Npn \prg_set_protected_conditional:Nnn
1758   { \prg_generate_conditional_count:nnNnn { set } { _protected } }
1759 \cs_set_protected:Npn \prg_new_protected_conditional:Nnn
1760   { \prg_generate_conditional_count:nnNnn { new } { _protected } }
1761 \cs_set_protected:Npn \prg_generate_conditional_count:nnNnn #1#2#3
1762   {
1763     \cs_split_function:NN #3 \prg_generate_conditional_count:nnNnnnn
1764     {#1} {#2}
1765   }
1766 \cs_set_protected:Npn \prg_generate_conditional_count:nnNnnnn #1#2#3#4#5
1767   {
1768     \cs_parm_from_arg_count:nnF
1769     { \prg_generate_conditional:nnNnnnn {#1} {#2} #3 {#4} {#5} }
1770     { \tl_count:n {#2} }
1771     {
1772       \msg_kernel_error:nxx { kernel } { bad-number-of-arguments }
1773       { \token_to_str:c { #1 : #2 } }
1774       { \tl_count:n {#2} }
1775       \use_none:nn
1776     }
1777   }

```

(End definition for \prg_set_conditional:Nnn and others. These functions are documented on page 96.)

\prg_generate_conditional:nnNnnnn
\prg_generate_conditional:nnNnnnnw

The workhorse here is going through a list of desired forms, *i.e.*, p, TF, T and F. The first three arguments come from splitting up the base form of the conditional, which gives the name, signature and a boolean to signal whether or not there was a colon in the name. In the absence of a colon, we throw an error and don't define any conditional. The fourth and fifth arguments build up the defining function. The sixth is the parameters to use (possibly empty), the seventh is the list of forms to define, the eighth is the replacement text which we will augment when defining the forms. The use of \tl_to_str:n makes the later loop more robust.

```

1778 \cs_set_protected:Npn \prg_generate_conditional:nnNnnnn #1#2#3#4#5#6#7#8
1779   {
1780     \if_meaning:w \c_false_bool #3
1781     \msg_kernel_error:nxx { kernel } { missing-colon }
1782     { \token_to_str:c {#1} }
1783     \exp_after:wN \use_none:nn
1784     \fi:
1785     \use:x
1786     {
1787       \exp_not:N \prg_generate_conditional:nnNnnnnw
1788       \exp_not:n { {#4} {#5} {#1} {#2} {#6} {#8} }
1789       \tl_to_str:n {#7}

```

```

1790     \exp_not:n { , \q_recursion_tail , \q_recursion_stop }
1791   }
1792 }

```

Looping through the list of desired forms. First are six arguments and seventh is the form. Use the form to call the correct type. If the form does not exist, the `\use:c` construction results in `\relax`, and the error message is displayed (unless the form is empty, to allow for `{T, , F}`), then `\use_none:nnnnnnn` cleans up. Otherwise, the error message is removed by the variant form.

```

1793 \cs_set_protected:Npn \__prg_generate_conditional:nnnnnnw #1#2#3#4#5#6#7 ,
1794 {
1795   \if_meaning:w \q_recursion_tail #7
1796   \exp_after:wN \use_none_delimit_by_q_recursion_stop:w
1797   \fi:
1798   \use:c { __prg_generate_ #7 _form:wnnnnnn }
1799   \tl_if_empty:nF {#7}
1800   {
1801     \__msg_kernel_error:nnxx
1802     { kernel } { conditional-form-unknown }
1803     {#7} { \token_to_str:c { #3 : #4 } }
1804   }
1805   \use_none:nnnnnnn
1806   \q_stop
1807   {#1} {#2} {#3} {#4} {#5} {#6}
1808   \__prg_generate_conditional:nnnnnnw {#1} {#2} {#3} {#4} {#5} {#6}
1809 }

```

(End definition for `__prg_generate_conditional:nnNnnnnn` and `__prg_generate_conditional:nnnnnnw`.)

```

\_prg_generate_p_form:wnnnnnn
\_prg_generate_TF_form:wnnnnnn
\_prg_generate_T_form:wnnnnnn
\_prg_generate_F_form:wnnnnnn

```

How to generate the various forms. Those functions take the following arguments: 1: **set** or **new**, 2: **empty** or **_protected**, 3: function name 4: signature, 5: parameter text (or empty), 6: replacement. Remember that the logic-returning functions expect two arguments to be present after `\exp_end::` notice the construction of the different variants relies on this, and that the TF and F variants will be slightly faster than the T version. The p form is only valid for expandable tests, we check for that by making sure that the second argument is empty.

```

1810 \cs_set_protected:Npn \__prg_generate_p_form:wnnnnnn
1811   #1 \q_stop #2#3#4#5#6#7
1812 {
1813   \if_meaning:w \scan_stop: #3 \scan_stop:
1814   \exp_after:wN \use_i:nn
1815   \else:
1816   \exp_after:wN \use_ii:nn
1817   \fi:
1818   {
1819     \exp_args:cc { cs_ #2 #3 :Npn } { #4 _p: #5 } #6
1820     { #7 \exp_end: \c_true_bool \c_false_bool }
1821   }
1822   {
1823     \__msg_kernel_error:nnx { kernel } { protected-predicate }
1824     { \token_to_str:c { #4 _p: #5 } }
1825   }
1826 }
1827 \cs_set_protected:Npn \__prg_generate_T_form:wnnnnnn

```

```

1828     #1 \q_stop #2#3#4#5#6#7
1829   {
1830     \exp_args:cc { cs_ #2 #3 :Npn } { #4 : #5 T } #6
1831     { #7 \exp_end: \use:n \use_none:n }
1832   }
1833 \cs_set_protected:Npn \__prg_generate_F_form:wnnnnnn
1834   #1 \q_stop #2#3#4#5#6#7
1835   {
1836     \exp_args:cc { cs_ #2 #3 :Npn } { #4 : #5 F } #6
1837     { #7 \exp_end: { } }
1838   }
1839 \cs_set_protected:Npn \__prg_generate_TF_form:wnnnnnn
1840   #1 \q_stop #2#3#4#5#6#7
1841   {
1842     \exp_args:cc { cs_ #2 #3 :Npn } { #4 : #5 TF } #6
1843     { #7 \exp_end: }
1844   }

```

(End definition for __prg_generate_p_form:wnnnnnn and others.)

\prg_set_eq_conditional:NNn The setting-equal functions. Split both functions and feed $\{\langle name_1 \rangle\}$ $\{\langle signature_1 \rangle\}$
\prg_new_eq_conditional:NNn $\langle boolean_1 \rangle$ $\{\langle name_2 \rangle\}$ $\{\langle signature_2 \rangle\}$ $\langle boolean_2 \rangle$ $\langle copying\ function \rangle$ $\langle conditions \rangle$, \q-
 __prg_set_eq_conditional:NNNn recursion_tail , \q-recursion_stop to a first auxiliary.

```

1845 \cs_set_protected:Npn \prg_set_eq_conditional:NNn
1846   { \__prg_set_eq_conditional:NNNn \cs_set_eq:cc }
1847 \cs_set_protected:Npn \prg_new_eq_conditional:NNn
1848   { \__prg_set_eq_conditional:NNNn \cs_new_eq:cc }
1849 \cs_set_protected:Npn \__prg_set_eq_conditional:NNNn #1#2#3#4
1850   {
1851     \use:x
1852     {
1853       \exp_not:N \__prg_set_eq_conditional:nnNnnNNw
1854       \__cs_split_function:NN #2 \prg_do_nothing:
1855       \__cs_split_function:NN #3 \prg_do_nothing:
1856       \exp_not:N #1
1857       \tl_to_str:n {#4}
1858       \exp_not:n { , \q-recursion_tail , \q-recursion_stop }
1859     }
1860   }

```

(End definition for \prg_set_eq_conditional:NNn, \prg_new_eq_conditional:NNn, and __prg_set_eq_conditional:NNNn. These functions are documented on page 97.)

__prg_set_eq_conditional:nnNnnNNw Split the function to be defined, and setup a manual clist loop over argument #6 of the
 __prg_set_eq_conditional_loop:nnnnNw first auxiliary. The second auxiliary receives twice three arguments coming from splitting
 __prg_set_eq_conditional_p_form:nnn the function to be defined and the function to copy. Make sure that both functions
 __prg_set_eq_conditional_TF_form:nnn contained a colon, otherwise we don't know how to build conditionals, hence abort. Call
 __prg_set_eq_conditional_T_form:nnn the looping macro, with arguments $\{\langle name_1 \rangle\}$ $\{\langle signature_1 \rangle\}$ $\{\langle name_2 \rangle\}$ $\{\langle signature_2 \rangle\}$
 __prg_set_eq_conditional_F_form:nnn $\langle copying\ function \rangle$ and followed by the comma list. At each step in the loop, make sure
 that the conditional form we copy is defined, and copy it, otherwise abort.

```

1861 \cs_set_protected:Npn \__prg_set_eq_conditional:nnNnnNNw #1#2#3#4#5#6
1862   {
1863     \if_meaning:w \c_false_bool #3
1864     \__msg_kernel_error:nx { kernel } { missing-colon }

```



```

1865     { \token_to_str:c {#1} }
1866     \exp_after:wN \use_none_delimit_by_q_recursion_stop:w
1867   \fi:
1868   \if_meaning:w \c_false_bool #6
1869     \__msg_kernel_error:nxx { kernel } { missing-colon }
1870     { \token_to_str:c {#4} }
1871     \exp_after:wN \use_none_delimit_by_q_recursion_stop:w
1872   \fi:
1873   \__prg_set_eq_conditional_loop:nnnnNw {#1} {#2} {#4} {#5}
1874 }
1875 \cs_set_protected:Npn \__prg_set_eq_conditional_loop:nnnnNw #1#2#3#4#5#6 ,
1876 {
1877   \if_meaning:w \q_recursion_tail #6
1878   \exp_after:wN \use_none_delimit_by_q_recursion_stop:w
1879   \fi:
1880   \use:c { __prg_set_eq_conditional_ #6 _form:wNnnnn }
1881   \tl_if_empty:nF {#6}
1882   {
1883     \__msg_kernel_error:nxxx
1884     { kernel } { conditional-form-unknown }
1885     {#6} { \token_to_str:c { #1 : #2 } }
1886   }
1887   \use_none:nnnnnn
1888   \q_stop
1889   #5 {#1} {#2} {#3} {#4}
1890   \__prg_set_eq_conditional_loop:nnnnNw {#1} {#2} {#3} {#4} #5
1891 }
1892 \__debug_patch:nnNNpn
1893 { \__debug_chk_cs_exist:c { #5_p : #6 } } { }
1894 \cs_set:Npn \__prg_set_eq_conditional_p_form:wNnnnn #1 \q_stop #2#3#4#5#6
1895 { #2 { #3_p : #4 } { #5_p : #6 } }
1896 \__debug_patch:nnNNpn
1897 { \__debug_chk_cs_exist:c { #5 : #6 TF } } { }
1898 \cs_set:Npn \__prg_set_eq_conditional_TF_form:wNnnnn #1 \q_stop #2#3#4#5#6
1899 { #2 { #3 : #4 TF } { #5 : #6 TF } }
1900 \__debug_patch:nnNNpn
1901 { \__debug_chk_cs_exist:c { #5 : #6 T } } { }
1902 \cs_set:Npn \__prg_set_eq_conditional_T_form:wNnnnn #1 \q_stop #2#3#4#5#6
1903 { #2 { #3 : #4 T } { #5 : #6 T } }
1904 \__debug_patch:nnNNpn
1905 { \__debug_chk_cs_exist:c { #5 : #6 F } } { }
1906 \cs_set:Npn \__prg_set_eq_conditional_F_form:wNnnnn #1 \q_stop #2#3#4#5#6
1907 { #2 { #3 : #4 F } { #5 : #6 F } }

```

(End definition for `__prg_set_eq_conditional:nnNnnNnw` and others.)

All that is left is to define the canonical boolean true and false. I think Michael originated the idea of expandable boolean tests. At first these were supposed to expand into either TT or TF to be tested using `\if:w` but this was later changed to 00 and 01, so they could be used in logical operations. Later again they were changed to being numerical constants with values of 1 for true and 0 for false. We need this from the get-go.

`\c_true_bool` Here are the canonical boolean values.
`\c_false_bool`

```

1908 \tex_chardef:D \c_true_bool = 1 ~

```

```
1909 \tex_chardef:D \c_false_bool = 0 ~
```

(End definition for `\c_true_bool` and `\c_false_bool`. These variables are documented on page 20.)

3.8 Dissecting a control sequence

```
1910 <@@=cs>
```

`\cs_to_str:N` This converts a control sequence into the character string of its name, removing the leading escape character. This turns out to be a non-trivial matter as there are different cases:

- The usual case of a printable escape character;
- the case of a non-printable escape character, e.g., when the value of the `\escapechar` is negative;
- when the escape character is a space.

One approach to solve this is to test how many tokens result from `\token_to_str:N \a`. If there are two tokens, then the escape character is printable, while if it is non-printable then only one is present.

However, there is an additional complication: the control sequence itself may start with a space. Clearly that should *not* be lost in the process of converting to a string. So the approach adopted is a little more intricate still. When the escape character is printable, `\token_to_str:N _` yields the escape character itself and a space. The character codes are different, thus the `\if:w` test is false, and TeX reads `_cs_to_str:N` after turning the following control sequence into a string; this auxiliary removes the escape character, and stops the expansion of the initial `\tex_romannumeral:D`. The second case is that the escape character is not printable. Then the `\if:w` test is unfinished after reading the space from `\token_to_str:N _`, and the auxiliary `_cs_to_str:w` is expanded, feeding – as a second character for the test; the test is false, and TeX skips to `\fi:`, then performs `\token_to_str:N`, and stops the `\tex_romannumeral:D` with `\c_zero`. The last case is that the escape character is itself a space. In this case, the `\if:w` test is true, and the auxiliary `_cs_to_str:w` comes into play, inserting `-_int_value:w`, which expands `\c_zero` to the character 0. The initial `\tex_romannumeral:D` then sees 0, which is not a terminated number, followed by the escape character, a space, which is removed, terminating the expansion of `\tex_romannumeral:D`. In all three cases, `\cs_to_str:N` takes two expansion steps to be fully expanded.

```
1911 \cs_set:Npn \cs_to_str:N
1912 {
```

We implement the expansion scheme using `\tex_romannumeral:D` terminating it with `\c_zero` rather than using `\exp:w` and `\exp_end:` as we normally do. The reason is that the code heavily depends on terminating the expansion with `\c_zero` so we make this dependency explicit.

```
1913 \tex_romannumeral:D
1914 \if:w \token_to_str:N \\_cs_to_str:w \fi:
1915 \exp_after:wN \\_cs_to_str:N \token_to_str:N
1916 }
1917 \cs_set:Npn \_cs_to_str:N #1 { \c_zero }
1918 \cs_set:Npn \_cs_to_str:w #1 \_cs_to_str:N
1919 { - \_int_value:w \fi: \exp_after:wN \c_zero }
```

If speed is a concern we could use `\csstring` in Lua_{TeX}. For the empty csname that primitive gives an empty result while the current `\cs_to_str:N` gives incorrect results in all engines (this is impossible to fix without huge performance hit).

(End definition for `\cs_to_str:N`, `__cs_to_str:N`, and `__cs_to_str:w`. This function is documented on page 17.)

```
\__cs_split_function:NN
\__cs_split_function_auxi:w
\__cs_split_function_auxii:w
```

This function takes a function name and splits it into name with the escape char removed and argument specification. In addition to this, a third argument, a boolean $\langle true \rangle$ or $\langle false \rangle$ is returned with $\langle true \rangle$ for when there is a colon in the function and $\langle false \rangle$ if there is not. Lastly, the second argument of `__cs_split_function:NN` is supposed to be a function taking three variables, one for name, one for signature, and one for the boolean. For example, `\@@_split_function:NN \foo_bar:cnx \use_i:nnn` as input becomes `\use_i:nnn {foo_bar} {cnx} \c_true_bool`.

We cannot use `:` directly as it has the wrong category code so an x-type expansion is used to force the conversion.

First ensure that we actually get a properly evaluated string by expanding `\cs_to_str:N` twice. If the function contained a colon, the auxiliary takes as `#1` the function name, delimited by the first colon, then the signature `#2`, delimited by `\q_mark`, then `\c_true_bool` as `#3`, and `#4` cleans up until `\q_stop`. Otherwise, the `#1` contains the function name and `\q_mark \c_true_bool`, `#2` is empty, `#3` is `\c_false_bool`, and `#4` cleans up. In both cases, `#5` is the $\langle processor \rangle$. The second auxiliary trims the trailing `\q_mark` from the function name if present (that is, if the original function had no colon).

```
1920 \cs_set:Npx \__cs_split_function:NN #1
1921 {
1922   \exp_not:N \exp_after:wN \exp_not:N \exp_after:wN
1923   \exp_not:N \exp_after:wN \exp_not:N \__cs_split_function_auxi:w
1924   \exp_not:N \cs_to_str:N #1 \exp_not:N \q_mark \c_true_bool
1925   \token_to_str:N : \exp_not:N \q_mark \c_false_bool
1926   \exp_not:N \q_stop
1927 }
1928 \use:x
1929 {
1930   \cs_set:Npn \exp_not:N \__cs_split_function_auxi:w
1931     ##1 \token_to_str:N : ##2 \exp_not:N \q_mark ##3##4 \exp_not:N \q_stop ##5
1932 }
1933 { \__cs_split_function_auxii:w #5 #1 \q_mark \q_stop {#2} #3 }
1934 \cs_set:Npn \__cs_split_function_auxii:w #1#2 \q_mark #3 \q_stop
1935   { #1 {#2} }
```

(End definition for `__cs_split_function:NN`, `__cs_split_function_auxi:w`, and `__cs_split_function_auxii:w`.)

```
\__cs_get_function_name:N
\__cs_get_function_signature:N
```

Simple wrappers.

```
1936 \cs_set:Npn \__cs_get_function_name:N #1
1937   { \__cs_split_function:NN #1 \use_i:nnn }
1938 \cs_set:Npn \__cs_get_function_signature:N #1
1939   { \__cs_split_function:NN #1 \use_ii:nnn }
```

(End definition for `__cs_get_function_name:N` and `__cs_get_function_signature:N`.)

3.9 Exist or free

A control sequence is said to *exist* (to be used) if has an entry in the hash table and its meaning is different from the primitive `\relax` token. A control sequence is said to be *free* (to be defined) if it does not already exist.

`\cs_if_exist_p:N` Two versions for checking existence. For the `N` form we firstly check for `\scan_stop:` and
`\cs_if_exist_p:c` then if it is in the hash table. There is no problem when inputting something like `\else:`
`\cs_if_exist:NTF` or `\fi:` as `TEX` will only ever skip input in case the token tested against is `\scan_stop:`.
`\cs_if_exist:cTF`

```

1940 \prg_set_conditional:Npnn \cs_if_exist:N #1 { p , T , F , TF }
1941 {
1942   \if_meaning:w #1 \scan_stop:
1943   \prg_return_false:
1944   \else:
1945     \if_cs_exist:N #1
1946     \prg_return_true:
1947     \else:
1948       \prg_return_false:
1949     \fi:
1950   \fi:
1951 }

```

For the `c` form we firstly check if it is in the hash table and then for `\scan_stop:` so that we do not add it to the hash table unless it was already there. Here we have to be careful as the text to be skipped if the first test is false may contain tokens that disturb the scanner. Therefore, we ensure that the second test is performed after the first one has concluded completely.

```

1952 \prg_set_conditional:Npnn \cs_if_exist:c #1 { p , T , F , TF }
1953 {
1954   \if_cs_exist:w #1 \cs_end:
1955   \exp_after:wN \use_i:nn
1956   \else:
1957     \exp_after:wN \use_ii:nn
1958   \fi:
1959   {
1960     \exp_after:wN \if_meaning:w \cs:w #1 \cs_end: \scan_stop:
1961     \prg_return_false:
1962     \else:
1963       \prg_return_true:
1964     \fi:
1965   }
1966   \prg_return_false:
1967 }

```

(End definition for `\cs_if_exist:NTF`. This function is documented on page 20.)

`\cs_if_free_p:N` The logical reversal of the above.
`\cs_if_free_p:c`
`\cs_if_free:NTF`
`\cs_if_free:cTF`

```

1968 \prg_set_conditional:Npnn \cs_if_free:N #1 { p , T , F , TF }
1969 {
1970   \if_meaning:w #1 \scan_stop:
1971   \prg_return_true:
1972   \else:
1973     \if_cs_exist:N #1
1974     \prg_return_false:

```

```

1975     \else:
1976     \prg_return_true:
1977     \fi:
1978 \fi:
1979 }
1980 \prg_set_conditional:Npnn \cs_if_free:c #1 { p , T , F , TF }
1981 {
1982     \if_cs_exist:w #1 \cs_end:
1983     \exp_after:wN \use_i:nn
1984     \else:
1985     \exp_after:wN \use_ii:nn
1986     \fi:
1987     {
1988         \exp_after:wN \if_meaning:w \cs:w #1 \cs_end: \scan_stop:
1989         \prg_return_true:
1990     \else:
1991         \prg_return_false:
1992     \fi:
1993 }
1994 { \prg_return_true: }
1995 }

```

(End definition for `\cs_if_free:NTF`. This function is documented on page 20.)

`\cs_if_exist_use:N` The `\cs_if_exist_use:...` functions cannot be implemented as conditionals because the true branch must leave both the control sequence itself and the true code in the input stream. For the `c` variants, we are careful not to put the control sequence in the hash table if it does not exist. In LuaTeX we could use the `\lastnamedcs` primitive.

```

1996 \cs_set:Npn \cs_if_exist_use:NTF #1#2
1997 { \cs_if_exist:NTF #1 { #1 #2 } }
1998 \cs_set:Npn \cs_if_exist_use:NF #1
1999 { \cs_if_exist:NTF #1 { #1 } }
2000 \cs_set:Npn \cs_if_exist_use:NT #1 #2
2001 { \cs_if_exist:NTF #1 { #1 #2 } { } }
2002 \cs_set:Npn \cs_if_exist_use:N #1
2003 { \cs_if_exist:NTF #1 { #1 } { } }
2004 \cs_set:Npn \cs_if_exist_use:cTF #1#2
2005 { \cs_if_exist:cTF {#1} { \use:c {#1} #2 } }
2006 \cs_set:Npn \cs_if_exist_use:cF #1
2007 { \cs_if_exist:cTF {#1} { \use:c {#1} } }
2008 \cs_set:Npn \cs_if_exist_use:cT #1#2
2009 { \cs_if_exist:cTF {#1} { \use:c {#1} #2 } { } }
2010 \cs_set:Npn \cs_if_exist_use:c #1
2011 { \cs_if_exist:cTF {#1} { \use:c {#1} } { } }

```

(End definition for `\cs_if_exist_use:NTF`. This function is documented on page 16.)

3.10 Preliminaries for new functions

We provide two kinds of functions that can be used to define control sequences. On the one hand we have functions that check if their argument doesn't already exist, they are called `\..._new`. The second type of defining functions doesn't check if the argument is already defined.

Before we can define them, we need some auxiliary macros that allow us to generate error messages. The next few definitions here are only temporary, they will be redefined later on.

<pre> _msg_kernel_error:nxxx _msg_kernel_error:nxx _msg_kernel_error:nn </pre>	<p>If an internal error occurs before L^AT_EX3 has loaded l3msg then the code should issue a usable if terse error message and halt. This can only happen if a coding error is made by the team, so this is a reasonable response. Setting the <code>\newlinechar</code> is needed, to turn <code>^^J</code> into a proper line break in plain T_EX.</p>
---	--

```

2012 \cs_set_protected:Npn \__msg_kernel_error:nxxx #1#2#3#4
2013 {
2014   \tex_newlinechar:D = '\^^J \tex_relax:D
2015   \tex_errmessage:D
2016   {
2017     !!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!~! ^^J
2018     Argh,~internal~LaTeX3~error! ^^J ^^J
2019     Module ~ #1 , ~ message~name~"#2": ^^J
2020     Arguments~'#3'~and~'#4' ^^J ^^J
2021     This~is~one~for~The~LaTeX3~Project::~bailing-out
2022   }
2023   \tex_end:D
2024 }
2025 \cs_set_protected:Npn \__msg_kernel_error:nxx #1#2#3
2026 { \__msg_kernel_error:nxxx {#1} {#2} {#3} { } }
2027 \cs_set_protected:Npn \__msg_kernel_error:nn #1#2
2028 { \__msg_kernel_error:nxxx {#1} {#2} { } { } }

```

(End definition for \ msg kernel error:nnxx, \ msg kernel error:nnx, and \ msg kernel error:nn.)

`\msg_line_context:` Another one from `l3msg` which will be altered later.

```
2029 \cs_set:Npn \msg_line_context:
2030   { on~line~ \tex the:D \tex inputlineno:D }
```

(End definition for `\msg_line_context`:. This function is documented on page 137.)

```
\iow_log:x We define a routine to write only to the log file. And a similar one for writing to both
\iow_term:x the log file and the terminal. These will be redefined later by l3io.
```

```

2031 \cs_set_protected:Npn \iow_log:x
2032   { \tex_immediate:D \tex_write:D -1 }
2033 \cs_set_protected:Npn \iow_term:x
2034   { \tex_immediate:D \tex_write:D 16 }

```

(End definition for \iow log:n. This function is documented on page 150.)

```

\__chk_if_free_cs:N This command is called by \cs_new_nopar:Npn and \cs_new_eq:NN etc. to make sure
\__chk_if_free_cs:c that the argument sequence is not already in use. If it is, an error is signalled. It checks
if <csname> is undefined or \scan_stop:. Otherwise an error message is issued. We have
to make sure we don't put the argument into the conditional processing since it may be
an \if... type function!

```

```

2035  __debug_patch:nnNnpn { }
2036  { __debug_log:x { Defining~\token_to_str:N #1~ \msg_line_context: } }
2037  \cs_set_protected:Npn __chk_if_free_cs:N #1
2038  {
2039    \cs_if_free:NF #1
2040    {

```

```

2041         \_msg_kernel_error:nxx { kernel } { command-already-defined }
2042         { \token_to_str:N #1 } { \token_to_meaning:N #1 }
2043     }
2044 }
2045 \cs_set_protected:Npn \__chk_if_free_cs:c
2046 { \exp_args:Nc \__chk_if_free_cs:N }

```

(End definition for __chk_if_free_cs:N.)

3.11 Defining new functions

```

2047 <@@=cs>

```

Function which check that the control sequence is free before defining it.

```

\cs_new_nopar:Npn \cs_new_nopar:Npx \cs_new:Npn \cs_new:Npx
\cs_new_protected_nopar:Npn \cs_new_protected_nopar:Npx
\cs_new_protected:Npn \cs_new_protected:Npx
\__cs_tmp:w
2048 \cs_set:Npn \__cs_tmp:w #1#2
2049 {
2050     \cs_set_protected:Npn #1 ##1
2051     {
2052         \__chk_if_free_cs:N ##1
2053         #2 ##1
2054     }
2055 }
2056 \__cs_tmp:w \cs_new_nopar:Npn \cs_gset_nopar:Npn
2057 \__cs_tmp:w \cs_new_nopar:Npx \cs_gset_nopar:Npx
2058 \__cs_tmp:w \cs_new:Npn \cs_gset:Npn
2059 \__cs_tmp:w \cs_new:Npx \cs_gset:Npx
2060 \__cs_tmp:w \cs_new_protected_nopar:Npn \cs_gset_protected_nopar:Npn
2061 \__cs_tmp:w \cs_new_protected_nopar:Npx \cs_gset_protected_nopar:Npx
2062 \__cs_tmp:w \cs_new_protected:Npn \cs_gset_protected:Npn
2063 \__cs_tmp:w \cs_new_protected:Npx \cs_gset_protected:Npx

```

(End definition for \cs_new_nopar:Npn and others. These functions are documented on page 11.)

\cs_set_nopar:cpn \cs_set_nopar:cpx \cs_gset_nopar:cpn \cs_gset_nopar:cpx \cs_new_nopar:cpn \cs_new_nopar:cpx

Like \cs_set_nopar:Npn and \cs_new_nopar:Npn, except that the first argument consists of the sequence of characters that should be used to form the name of the desired control sequence (the c stands for csname argument, see the expansion module). Global versions are also provided.

\cs_set_nopar:cpn<string><rep-text> turns <string> into a csname and then assigns <rep-text> to it by using \cs_set_nopar:Npn. This means that there might be a parameter string between the two arguments.

```

2064 \cs_set:Npn \__cs_tmp:w #1#2
2065 { \cs_new_protected_nopar:Npn #1 { \exp_args:Nc #2 } }
2066 \__cs_tmp:w \cs_set_nopar:cpn \cs_set_nopar:Npn
2067 \__cs_tmp:w \cs_set_nopar:cpx \cs_set_nopar:Npx
2068 \__cs_tmp:w \cs_gset_nopar:cpn \cs_gset_nopar:Npn
2069 \__cs_tmp:w \cs_gset_nopar:cpx \cs_gset_nopar:Npx
2070 \__cs_tmp:w \cs_new_nopar:cpn \cs_new_nopar:Npn
2071 \__cs_tmp:w \cs_new_nopar:cpx \cs_new_nopar:Npx

```

(End definition for \cs_set_nopar:Npn. This function is documented on page 11.)

\cs_set:cpn \cs_set:cpx \cs_gset:cpn \cs_gset:cpx \cs_new:cpn \cs_new:cpx

Variants of the \cs_set:Npn versions which make a csname out of the first arguments. We may also do this globally.

```

2072 \__cs_tmp:w \cs_set:cpn \cs_set:Npn

```

```

2073 \__cs_tmp:w \cs_set:cpx \cs_set:Npx
2074 \__cs_tmp:w \cs_gset:cpn \cs_gset:Npn
2075 \__cs_tmp:w \cs_gset:cpx \cs_gset:Npx
2076 \__cs_tmp:w \cs_new:cpn \cs_new:Npn
2077 \__cs_tmp:w \cs_new:cpx \cs_new:Npx

```

(End definition for `\cs_set:Npn`. This function is documented on page 11.)

`\cs_set_protected_nopar:cpn` Variants of the `\cs_set_protected_nopar:Npn` versions which make a csname out of the first arguments. We may also do this globally.

```

\cs_set_protected_nopar:cpx
\cs_gset_protected_nopar:cpn
\cs_gset_protected_nopar:cpx
\cs_new_protected_nopar:cpn
\cs_new_protected_nopar:cpx
2078 \__cs_tmp:w \cs_set_protected_nopar:cpn \cs_set_protected_nopar:Npn
2079 \__cs_tmp:w \cs_set_protected_nopar:cpx \cs_set_protected_nopar:Npx
2080 \__cs_tmp:w \cs_gset_protected_nopar:cpn \cs_gset_protected_nopar:Npn
2081 \__cs_tmp:w \cs_gset_protected_nopar:cpx \cs_gset_protected_nopar:Npx
2082 \__cs_tmp:w \cs_new_protected_nopar:cpn \cs_new_protected_nopar:Npn
2083 \__cs_tmp:w \cs_new_protected_nopar:cpx \cs_new_protected_nopar:Npx

```

(End definition for `\cs_set_protected_nopar:Npn`. This function is documented on page 12.)

`\cs_set_protected:cpn` Variants of the `\cs_set_protected:Npn` versions which make a csname out of the first arguments. We may also do this globally.

```

\cs_set_protected:cpx
\cs_gset_protected:cpn
\cs_gset_protected:cpx
\cs_new_protected:cpn
\cs_new_protected:cpx
2084 \__cs_tmp:w \cs_set_protected:cpn \cs_set_protected:Npn
2085 \__cs_tmp:w \cs_set_protected:cpx \cs_set_protected:Npx
2086 \__cs_tmp:w \cs_gset_protected:cpn \cs_gset_protected:Npn
2087 \__cs_tmp:w \cs_gset_protected:cpx \cs_gset_protected:Npx
2088 \__cs_tmp:w \cs_new_protected:cpn \cs_new_protected:Npn
2089 \__cs_tmp:w \cs_new_protected:cpx \cs_new_protected:Npx

```

(End definition for `\cs_set_protected:Npn`. This function is documented on page 11.)

3.12 Copying definitions

`\cs_set_eq:NN` These macros allow us to copy the definition of a control sequence to another control sequence.

`\cs_set_eq:cN` The = sign allows us to define funny char tokens like = itself or `_` with this function.

`\cs_set_eq:Nc` For the definition of `\c_space_char{~}` to work we need the ~ after the =.

`\cs_set_eq:cc` `\cs_set_eq:NN` is long to avoid problems with a literal argument of `\par`. While

`\cs_gset_eq:NN` `\cs_new_eq:NN` will probably never be correct with a first argument of `\par`, define it

`\cs_gset_eq:cN` long in order to throw an “already defined” error rather than “runaway argument”.

```

\cs_gset_eq:Nc
\cs_gset_eq:cc
2090 \cs_new_protected:Npn \cs_set_eq:NN #1 { \tex_let:D #1 =~ }
\cs_new_eq:NN
2091 \cs_new_protected:Npn \cs_set_eq:cN { \exp_args:Nc \cs_set_eq:NN }
\cs_new_eq:cN
2092 \cs_new_protected:Npn \cs_set_eq:Nc { \exp_args:NNc \cs_set_eq:NN }
\cs_new_eq:Nc
2093 \cs_new_protected:Npn \cs_set_eq:cc { \exp_args:Ncc \cs_set_eq:NN }
\cs_new_eq:cc
2094 \cs_new_protected:Npn \cs_gset_eq:NN { \tex_global:D \cs_set_eq:NN }

```

```

2095 \cs_new_protected:Npn \cs_gset_eq:Nc { \exp_args:NNc \cs_gset_eq:NN }
2096 \cs_new_protected:Npn \cs_gset_eq:cN { \exp_args:Nc \cs_gset_eq:NN }
2097 \cs_new_protected:Npn \cs_gset_eq:cc { \exp_args:Ncc \cs_gset_eq:NN }
2098 \cs_new_protected:Npn \cs_new_eq:NN #1
2099 {
2100   \__chk_if_free_cs:N #1
2101   \tex_global:D \cs_set_eq:NN #1
2102 }
2103 \cs_new_protected:Npn \cs_new_eq:cN { \exp_args:Nc \cs_new_eq:NN }
2104 \cs_new_protected:Npn \cs_new_eq:Nc { \exp_args:NNc \cs_new_eq:NN }
2105 \cs_new_protected:Npn \cs_new_eq:cc { \exp_args:Ncc \cs_new_eq:NN }

```


(End definition for `\cs_set_eq:NN`, `\cs_gset_eq:NN`, and `\cs_new_eq:NN`. These functions are documented on page 15.)

3.13 Undefining functions

`\cs_undefine:N` The following function is used to free the main memory from the definition of some function that isn't in use any longer. The `c` variant is careful not to add the control sequence to the hash table if it isn't there yet, and it also avoids nesting `TeX` conditionals in case `#1` is unbalanced in this matter.

```

2106 \cs_new_protected:Npn \cs_undefine:N #1
2107 { \cs_gset_eq:NN #1 \tex_undefined:D }
2108 \cs_new_protected:Npn \cs_undefine:c #1
2109 {
2110   \if_cs_exist:w #1 \cs_end:
2111     \exp_after:wN \use:n
2112   \else:
2113     \exp_after:wN \use_none:n
2114   \fi:
2115   { \cs_gset_eq:cN {#1} \tex_undefined:D }
2116 }
```

(End definition for `\cs_undefine:N`. This function is documented on page 15.)

3.14 Generating parameter text from argument count

```

2117 <@@=cs>
```

`__cs_parm_from_arg_count:nnF` `__cs_parm_from_arg_count_test:nnF` `LaTeX3` provides shorthands to define control sequences and conditionals with a simple parameter text, derived directly from the signature, or more generally from knowing the number of arguments, between 0 and 9. This function expands to its first argument, untouched, followed by a brace group containing the parameter text `{#1...#n}`, where `n` is the result of evaluating the second argument (as described in `\int_eval:n`). If the second argument gives a result outside the range `[0, 9]`, the third argument is returned instead, normally an error message. Some of the functions use here are not defined yet, but will be defined before this function is called.

```

2118 \cs_set_protected:Npn \__cs_parm_from_arg_count:nnF #1#2
2119 {
2120   \exp_args:Nx \__cs_parm_from_arg_count_test:nnF
2121   {
2122     \exp_after:wN \exp_not:n
2123     \if_case:w \__int_eval:n {#2}
2124       { }
2125     \or: { ##1 }
2126     \or: { ##1##2 }
2127     \or: { ##1##2##3 }
2128     \or: { ##1##2##3##4 }
2129     \or: { ##1##2##3##4##5 }
2130     \or: { ##1##2##3##4##5##6 }
2131     \or: { ##1##2##3##4##5##6##7 }
2132     \or: { ##1##2##3##4##5##6##7##8 }
2133     \or: { ##1##2##3##4##5##6##7##8##9 }
2134     \else: { \c_false_bool }
2135   \fi:
```

```

2136     }
2137     {#1}
2138   }
2139   \cs_set_protected:Npn \__cs_parm_from_arg_count_test:nnF #1#2
2140   {
2141     \if_meaning:w \c_false_bool #1
2142       \exp_after:wN \use_ii:nn
2143     \else:
2144       \exp_after:wN \use_i:nn
2145     \fi:
2146     { #2 {#1} }
2147   }

```

(End definition for `__cs_parm_from_arg_count:nnF` and `__cs_parm_from_arg_count_test:nnF`.)

3.15 Defining functions from a given number of arguments

```

2148   <@@=cs>

```

`__cs_count_signature:N` Counting the number of tokens in the signature, *i.e.*, the number of arguments the function should take. Since this is not used in any time-critical function, we simply use `\tl_count:n` if there is a signature, otherwise `-1` arguments to signal an error. We need a variant form right away.

```

2149   \cs_new:Npn \__cs_count_signature:N #1
2150   { \int_eval:n { \__cs_split_function:NN #1 \__cs_count_signature:nnN } }
2151   \cs_new:Npn \__cs_count_signature:nnN #1#2#3
2152   {
2153     \if_meaning:w \c_true_bool #3
2154       \tl_count:n {#2}
2155     \else:
2156       -1
2157     \fi:
2158   }
2159   \cs_new:Npn \__cs_count_signature:c
2160   { \exp_args:Nc \__cs_count_signature:N }

```

(End definition for `__cs_count_signature:N` and `__cs_count_signature:nnN`.)

```

\cs_generate_from_arg_count:NNnn
\cs_generate_from_arg_count:cNnn
\cs_generate_from_arg_count:Ncnn

```

We provide a constructor function for defining functions with a given number of arguments. For this we need to choose the correct parameter text and then use that when defining. Since \TeX supports from zero to nine arguments, we use a simple switch to choose the correct parameter text, ensuring the result is returned after finishing the conditional. If it is not between zero and nine, we throw an error.

1: function to define, 2: with what to define it, 3: the number of args it requires and 4: the replacement text

```

2161   \cs_new_protected:Npn \cs_generate_from_arg_count:NNnn #1#2#3#4
2162   {
2163     \__cs_parm_from_arg_count:nnF { \use:nnn #2 #1 } {#3}
2164     {
2165       \__msg_kernel_error:nxxx { kernel } { bad-number-of-arguments }
2166       { \token_to_str:N #1 } { \int_eval:n {#3} }
2167       \use_none:n
2168     }
2169     {#4}
2170   }

```

A variant form we need right away, plus one which is used elsewhere but which is most logically created here.

```

2171 \cs_new_protected:Npn \cs_generate_from_arg_count:cNnn
2172 { \exp_args:Nc \cs_generate_from_arg_count:NNnn }
2173 \cs_new_protected:Npn \cs_generate_from_arg_count:Ncnn
2174 { \exp_args:NNc \cs_generate_from_arg_count:NNnn }

```

(End definition for `\cs_generate_from_arg_count:NNnn`. This function is documented on page 14.)

3.16 Using the signature to define functions

```

2175 <@@=cs>

```

We can now combine some of the tools we have to provide a simple interface for defining functions, where the number of arguments is read from the signature. For instance, `\cs_set:Nn \foo_bar:nn {#1,#2}`.

We want to define `\cs_set:Nn` as

```

\cs_set:Nn
\cs_set:Nx
\cs_set_nopar:Nn
\cs_set_nopar:Nx
\cs_set_protected:Nn
\cs_set_protected:Nx
\cs_set_protected_nopar:Nn
\cs_set_protected_nopar:Nx
\cs_gset:Nn
\cs_gset:Nx
\cs_gset_nopar:Nn
\cs_gset_nopar:Nx
\cs_gset_protected:Nn
\cs_gset_protected:Nx
\cs_new:Nn
\cs_new:Nx
\cs_new_nopar:Nn
\cs_new_nopar:Nx
\cs_new_protected:Nn
\cs_new_protected:Nx
\cs_new_protected_nopar:Nn
\cs_new_protected_nopar:Nx

```

In short, to define `\cs_set:Nn` we need just use `\cs_set:Npn`, everything else is the same for each variant. Therefore, we can make it simpler by temporarily defining a function to do this for us.

```

2176 \cs_set:Npn \__cs_tmp:w #1#2#3
2177 {
2178   \cs_new_protected:cpx { cs_ #1 : #2 }
2179   {
2180     \exp_not:N \__cs_generate_from_signature:NNn
2181     \exp_after:wN \exp_not:N \cs:w cs_ #1 : #3 \cs_end:
2182   }
2183 }
2184 \cs_new_protected:Npn \__cs_generate_from_signature:NNn #1#2
2185 {
2186   \__cs_split_function:NN #2 \__cs_generate_from_signature:nnNNNn
2187   #1 #2
2188 }
2189 \cs_new_protected:Npn \__cs_generate_from_signature:nnNNNn #1#2#3#4#5#6
2190 {
2191   \bool_if:NTF #3
2192   {
2193     \str_if_eq_x:nnF { }
2194     { \tl_map_function:nN {#2} \__cs_generate_from_signature:n }
2195     {
2196       \__msg_kernel_error:nnx { kernel } { non-base-function }
2197       { \token_to_str:N #5 }
2198     }
2199     \cs_generate_from_arg_count:NNnn
2200     #5 #4 { \tl_count:n {#2} } {#6}
2201   }
2202   {

```

```

2203         \_msg_kernel_error:nnx { kernel } { missing-colon }
2204         { \token_to_str:N #5 }
2205     }
2206 }
2207 \cs_new:Npn \__cs_generate_from_signature:n #1
2208 {
2209     \if:w n #1 \else: \if:w N #1 \else:
2210     \if:w T #1 \else: \if:w F #1 \else: #1 \fi: \fi: \fi: \fi:
2211 }

```

Then we define the 24 variants beginning with N.

```

2212 \__cs_tmp:w { set } { Nn } { Npn }
2213 \__cs_tmp:w { set } { Nx } { Npx }
2214 \__cs_tmp:w { set_nopar } { Nn } { Npn }
2215 \__cs_tmp:w { set_nopar } { Nx } { Npx }
2216 \__cs_tmp:w { set_protected } { Nn } { Npn }
2217 \__cs_tmp:w { set_protected } { Nx } { Npx }
2218 \__cs_tmp:w { set_protected_nopar } { Nn } { Npn }
2219 \__cs_tmp:w { set_protected_nopar } { Nx } { Npx }
2220 \__cs_tmp:w { gset } { Nn } { Npn }
2221 \__cs_tmp:w { gset } { Nx } { Npx }
2222 \__cs_tmp:w { gset_nopar } { Nn } { Npn }
2223 \__cs_tmp:w { gset_nopar } { Nx } { Npx }
2224 \__cs_tmp:w { gset_protected } { Nn } { Npn }
2225 \__cs_tmp:w { gset_protected } { Nx } { Npx }
2226 \__cs_tmp:w { gset_protected_nopar } { Nn } { Npn }
2227 \__cs_tmp:w { gset_protected_nopar } { Nx } { Npx }
2228 \__cs_tmp:w { new } { Nn } { Npn }
2229 \__cs_tmp:w { new } { Nx } { Npx }
2230 \__cs_tmp:w { new_nopar } { Nn } { Npn }
2231 \__cs_tmp:w { new_nopar } { Nx } { Npx }
2232 \__cs_tmp:w { new_protected } { Nn } { Npn }
2233 \__cs_tmp:w { new_protected } { Nx } { Npx }
2234 \__cs_tmp:w { new_protected_nopar } { Nn } { Npn }
2235 \__cs_tmp:w { new_protected_nopar } { Nx } { Npx }

```

(End definition for \cs_set:Nn and others. These functions are documented on page 13.)

\cs_set:cn The 24 c variants simply use \exp_args:Nc.

\cs_set:cx

\cs_set_nopar:cn

\cs_set_nopar:cx

\cs_set_protected:cn

\cs_set_protected:cx

\cs_set_protected_nopar:cn

\cs_set_protected_nopar:cx

\cs_gset:cn

\cs_gset:cx

\cs_gset_nopar:cn

\cs_gset_nopar:cx

\cs_gset_protected:cn

\cs_gset_protected:cx

\cs_gset_protected_nopar:cn

\cs_gset_protected_nopar:cx

\cs_new:cn

\cs_new:cx

\cs_new_nopar:cn

\cs_new_nopar:cx

\cs_new_protected:cn

\cs_new_protected:cx

\cs_new_protected_nopar:cn

\cs_new_protected_nopar:cx

```

2236 \cs_set:Npn \__cs_tmp:w #1#2
2237 {
2238     \cs_new_protected:cpx { cs_ #1 : c #2 }
2239     {
2240         \exp_not:N \exp_args:Nc
2241         \exp_after:wN \exp_not:N \cs:w cs_ #1 : N #2 \cs_end:
2242     }
2243 }
2244 \__cs_tmp:w { set } { n }
2245 \__cs_tmp:w { set } { x }
2246 \__cs_tmp:w { set_nopar } { n }
2247 \__cs_tmp:w { set_nopar } { x }
2248 \__cs_tmp:w { set_protected } { n }
2249 \__cs_tmp:w { set_protected } { x }
2250 \__cs_tmp:w { set_protected_nopar } { n }
2251 \__cs_tmp:w { set_protected_nopar } { x }

```

```

2252 \__cs_tmp:w { gset } { n }
2253 \__cs_tmp:w { gset } { x }
2254 \__cs_tmp:w { gset_nopar } { n }
2255 \__cs_tmp:w { gset_nopar } { x }
2256 \__cs_tmp:w { gset_protected } { n }
2257 \__cs_tmp:w { gset_protected } { x }
2258 \__cs_tmp:w { gset_protected_nopar } { n }
2259 \__cs_tmp:w { gset_protected_nopar } { x }
2260 \__cs_tmp:w { new } { n }
2261 \__cs_tmp:w { new } { x }
2262 \__cs_tmp:w { new_nopar } { n }
2263 \__cs_tmp:w { new_nopar } { x }
2264 \__cs_tmp:w { new_protected } { n }
2265 \__cs_tmp:w { new_protected } { x }
2266 \__cs_tmp:w { new_protected_nopar } { n }
2267 \__cs_tmp:w { new_protected_nopar } { x }

```

(End definition for \cs_set:Nn. This function is documented on page 13.)

3.17 Checking control sequence equality

\cs_if_eq_p:NN Check if two control sequences are identical.

```

\cs_if_eq_p:cN 2268 \prg_new_conditional:Npnn \cs_if_eq:NN #1#2 { p , T , F , TF }
\cs_if_eq_p:Nc 2269 {
\cs_if_eq_p:cc 2270 \if_meaning:w #1#2
\cs_if_eq:NNTF 2271 \prg_return_true: \else: \prg_return_false: \fi:
\cs_if_eq:cNTF 2272 }
\cs_if_eq:NcTF 2273 \cs_new:Npn \cs_if_eq_p:cN { \exp_args:Nc \cs_if_eq_p:NN }
\cs_if_eq:ccTF 2274 \cs_new:Npn \cs_if_eq:cNTF { \exp_args:Nc \cs_if_eq:NNTF }
\cs_if_eq:ccTF 2275 \cs_new:Npn \cs_if_eq:cNT { \exp_args:Nc \cs_if_eq:NNT }
\cs_if_eq:ccTF 2276 \cs_new:Npn \cs_if_eq:cNF { \exp_args:Nc \cs_if_eq:NNF }
\cs_if_eq:ccTF 2277 \cs_new:Npn \cs_if_eq_p:Nc { \exp_args:NNc \cs_if_eq_p:NN }
\cs_if_eq:ccTF 2278 \cs_new:Npn \cs_if_eq:NcTF { \exp_args:NNc \cs_if_eq:NNTF }
\cs_if_eq:ccTF 2279 \cs_new:Npn \cs_if_eq:NcT { \exp_args:NNc \cs_if_eq:NNT }
\cs_if_eq:ccTF 2280 \cs_new:Npn \cs_if_eq:NcF { \exp_args:NNc \cs_if_eq:NNF }
\cs_if_eq:ccTF 2281 \cs_new:Npn \cs_if_eq_p:cc { \exp_args:Ncc \cs_if_eq_p:NN }
\cs_if_eq:ccTF 2282 \cs_new:Npn \cs_if_eq:ccTF { \exp_args:Ncc \cs_if_eq:NNTF }
\cs_if_eq:ccTF 2283 \cs_new:Npn \cs_if_eq:ccT { \exp_args:Ncc \cs_if_eq:NNT }
\cs_if_eq:ccTF 2284 \cs_new:Npn \cs_if_eq:ccF { \exp_args:Ncc \cs_if_eq:NNF }

```

(End definition for \cs_if_eq:NNTF. This function is documented on page 20.)

3.18 Diagnostic functions

```

2285 <@@=kernel>

```

__kernel_check_defined:NT Error if the variable #1 is not defined.

```

2286 \cs_new_protected:Npn \__kernel_check_defined:NT #1#2
2287 {
2288 \cs_if_exist:NTF #1
2289 {#2}
2290 {
2291 \_msg_kernel_error:nxx { kernel } { variable-not-defined }
2292 { \token_to_str:N #1 }

```

```

2293     }
2294 }

```

(End definition for `_kernel_check_defined:NT`.)

`_kernel_register_show:N` Simply using the `\show` primitive does not allow for line-wrapping, so instead use `\tl_show:n` and `\tl_log:n` (defined in `l3tl` and that performs line-wrapping). This displays `>~⟨variable⟩=⟨value⟩`. We expand the value before-hand as otherwise some integers (such as `\currentgrouplevel` or `\currentgrouptype`) altered by the line-wrapping code would show wrong values.

```

2295 \cs_new_protected:Npn \_kernel\_register\_show:N
2296 { \_kernel\_register\_show\_aux:NN \tl\_show:n }
2297 \cs_new_protected:Npn \_kernel\_register\_show:c
2298 { \exp\_args:Nc \_kernel\_register\_show:N }
2299 \cs_new_protected:Npn \_kernel\_register\_log:N
2300 { \_kernel\_register\_show\_aux:NN \tl\_log:n }
2301 \cs_new_protected:Npn \_kernel\_register\_log:c
2302 { \exp\_args:Nc \_kernel\_register\_log:N }
2303 \cs_new_protected:Npn \_kernel\_register\_show\_aux:NN #1#2
2304 {
2305   \_kernel\_check\_defined:NT #2
2306   {
2307     \exp\_args:No \_kernel\_register\_show\_aux:nNN
2308     { \tex\_the:D #2 } #2 #1
2309   }
2310 }
2311 \cs_new_protected:Npn \_kernel\_register\_show\_aux:nNN #1#2#3
2312 { \exp\_args:No #3 { \token\_to\_str:N #2 = #1 } }

```

(End definition for `_kernel_register_show:N` and others.)

`\cs_show:N` Some control sequences have a very long name or meaning. Thus, simply using TeX's primitive `\show` could lead to overlong lines. The output of this primitive is mimicked to some extent, then the re-built string is given to `\tl_show:n` or `\tl_log:n` for line-wrapping. We must expand the meaning before passing it to the wrapping code as otherwise we would wrongly see the definitions that are in place there. To get correct escape characters, set the `\escapechar` in a group; this also localizes the assignment performed by x-expansion. The `\cs_show:c` and `\cs_log:c` commands convert their argument to a control sequence within a group to avoid showing `\relax` for undefined control sequences.

```

2313 \cs_new_protected:Npn \cs\_show:N { \_kernel\_show:NN \tl\_show:n }
2314 \cs_new_protected:Npn \cs\_show:c
2315 { \group\_begin: \exp\_args:NNc \group\_end: \cs\_show:N }
2316 \cs_new_protected:Npn \cs\_log:N { \_kernel\_show:NN \tl\_log:n }
2317 \cs_new_protected:Npn \cs\_log:c
2318 { \group\_begin: \exp\_args:NNc \group\_end: \cs\_log:N }
2319 \cs_new_protected:Npn \_kernel\_show:NN #1#2
2320 {
2321   \group\_begin:
2322     \int\_set:Nn \tex\_escapechar:D { ‘\ ’ }
2323     \exp\_args:NNx
2324     \group\_end:
2325     #1 { \token\_to\_str:N #2 = \cs\_meaning:N #2 }
2326 }

```

(End definition for `\cs_show:N`, `\cs_log:N`, and `__kernel_show:NN`. These functions are documented on page 16.)

3.19 Doing nothing functions

`\prg_do_nothing:` This does not fit anywhere else!

```
2327 \cs_new_nopar:Npn \prg_do_nothing: { }
```

(End definition for `\prg_do_nothing:..` This function is documented on page 9.)

3.20 Breaking out of mapping functions

```
2328 <@@=prg>
```

`__prg_break_point:Nn` In inline mappings, the nesting level must be reset at the end of the mapping, even when the user decides to break out. This is done by putting the code that must be performed as an argument of `__prg_break_point:Nn`. The breaking functions are then defined to jump to that point and perform the argument of `__prg_break_point:Nn`, before the user’s code (if any). There is a check that we close the correct loop, otherwise we continue breaking.

```
2329 \cs_new_eq:NN \__prg_break_point:Nn \use_ii:nn
2330 \cs_new:Npn \__prg_map_break:Nn #1#2#3 \__prg_break_point:Nn #4#5
2331 {
2332     #5
2333     \if_meaning:w #1 #4
2334     \exp_after:wN \use_iii:nnn
2335     \fi:
2336     \__prg_map_break:Nn #1 {#2}
2337 }
```

(End definition for `__prg_break_point:Nn` and `__prg_map_break:Nn`.)

`__prg_break_point:` Very simple analogues of `__prg_break_point:Nn` and `__prg_map_break:Nn`, for use
`__prg_break:` in fast short-term recursions which are not mappings, do not need to support nesting,
`__prg_break:n` and in which nothing has to be done at the end of the loop.

```
2338 \cs_new_eq:NN \__prg_break_point: \prg_do_nothing:
2339 \cs_new:Npn \__prg_break: #1 \__prg_break_point: { }
2340 \cs_new:Npn \__prg_break:n #1#2 \__prg_break_point: {#1}
```

(End definition for `__prg_break_point:`, `__prg_break:`, and `__prg_break:n`.)

```
2341 </initex | package>
```

4 l3expan implementation

```
2342 <*initex | package>
```

```
2343 <@@=exp>
```

`\exp_after:wN` These are defined in `l3basics`, as they are needed “early”. This is just a reminder of that
`\exp_not:N` fact!

`\exp_not:n`

(End definition for `\exp_after:wN`, `\exp_not:N`, and `\exp_not:n`. These functions are documented on page 32.)

4.1 General expansion

In this section a general mechanism for defining functions that handle arguments is defined. These general expansion functions are expandable unless `x` is used. (Any version of `x` is going to have to use one of the L^AT_EX3 names for `\cs_set:Npx` at some point, and so is never going to be expandable.)

The definition of expansion functions with this technique happens in section 4.3. In section 4.2 some common cases are coded by a more direct method for efficiency, typically using calls to `\exp_after:wN`.

`\l__exp_internal_tl` This scratch token list variable is defined in `l3basics`.

(End definition for `\l__exp_internal_tl`.)

This code uses internal functions with names that start with `\:` to perform the expansions. All macros are `long` since the tokens undergoing expansion may be arbitrary user input.

An argument manipulator `\:<Z>` always has signature `#1\:::#2#3` where `#1` holds the remaining argument manipulations to be performed, `\:::` serves as an end marker for the list of manipulations, `#2` is the carried over result of the previous expansion steps and `#3` is the argument about to be processed. One exception to this rule is `\:p`, which has to grab an argument delimited by a left brace.

`__exp_arg_next:nnn` `#1` is the result of an expansion step, `#2` is the remaining argument manipulations and `#3` is the current result of the expansion chain. This auxiliary function moves `#1` back after `#3` in the input stream and checks if any expansion is left to be done by calling `#2`. In by far the most cases we need to add a set of braces to the result of an argument manipulation so it is more effective to do it directly here. Actually, so far only the `c` of the final argument manipulation variants does not require a set of braces.

```
2344 \cs_new:Npn \__exp_arg_next:nnn #1#2#3 { #2 \::: { #3 {#1} } }
2345 \cs_new:Npn \__exp_arg_next:Nnn #1#2#3 { #2 \::: { #3 #1 } }
```

(End definition for `__exp_arg_next:nnn` and `__exp_arg_next:Nnn`.)

`\:::` The end marker is just another name for the identity function.

```
2346 \cs_new:Npn \::: #1 {#1}
```

(End definition for `\:::`. This function is documented on page 36.)

`\:n` This function is used to skip an argument that doesn't need to be expanded.

```
2347 \cs_new:Npn \:n #1 \::: #2#3 { #1 \::: { #2 {#3} } }
```

(End definition for `\:n`. This function is documented on page 36.)

`\:N` This function is used to skip an argument that consists of a single token and doesn't need to be expanded.

```
2348 \cs_new:Npn \:N #1 \::: #2#3 { #1 \::: {#2#3} }
```

(End definition for `\:N`. This function is documented on page 36.)

`\:p` This function is used to skip an argument that is delimited by a left brace and doesn't need to be expanded. It is not wrapped in braces in the result.

```
2349 \cs_new:Npn \:p #1 \::: #2#3# { #1 \::: {#2#3} }
```

(End definition for `\:p`. This function is documented on page 36.)

\::c This function is used to skip an argument that is turned into a control sequence without expansion.

```
2350 \cs_new:Npn \::c #1 \::: #2#3
2351 { \exp_after:wN \__exp_arg_next:Nnn \cs:w #3 \cs_end: {#1} {#2} }
```

(End definition for \::c. This function is documented on page 36.)

\::o This function is used to expand an argument once.

```
2352 \cs_new:Npn \::o #1 \::: #2#3
2353 { \exp_after:wN \__exp_arg_next:nnn \exp_after:wN {#3} {#1} {#2} }
```

(End definition for \::o. This function is documented on page 36.)

\::f This function is used to expand a token list until the first unexpandable token is found. This is achieved through `\exp:w \exp_end_continue_f:w` that expands everything in its way following it. This scanning procedure is terminated once the expansion hits something non-expandable (if that is a space it is removed). We introduce `\exp_stop_f:` to mark such an end-of-expansion marker. For example, `f`-expanding `\cs_set_eq:Nc \aaa { b \l_tmpa_tl b }` where `\l_tmpa_tl` contains the characters `lur` gives `\tex_let:D \aaa = \blurb` which then turns out to start with the non-expandable token `\tex_let:D`. Since the expansion of `\exp:w \exp_end_continue_f:w` is empty, we wind up with a fully expanded list, only `TEX` has not tried to execute any of the non-expandable tokens. This is what differentiates this function from the `x` argument type.

```
2354 \cs_new:Npn \::f #1 \::: #2#3
2355 {
2356   \exp_after:wN \__exp_arg_next:nnn
2357   \exp_after:wN { \exp:w \exp_end_continue_f:w #3 }
2358   {#1} {#2}
2359 }
2360 \use:nn { \cs_new_eq:NN \exp_stop_f: } { ~ }
```

(End definition for \::f and `\exp_stop_f:`. These functions are documented on page 36.)

\::x This function is used to expand an argument fully.

```
2361 \cs_new_protected:Npn \::x #1 \::: #2#3
2362 {
2363   \cs_set_nopar:Npx \l__exp_internal_tl { {#3} }
2364   \exp_after:wN \__exp_arg_next:nnn \l__exp_internal_tl {#1} {#2}
2365 }
```

(End definition for \::x. This function is documented on page 36.)

\::v These functions return the value of a register, i.e., one of `tl`, `clist`, `int`, `skip`, `dim`, `muskip`, or built-in `TEX` register. The `V` version expects a single token whereas `v` like `c` creates a `csname` from its argument given in braces and then evaluates it as if it was a `V`. The `\exp:w` sets off an expansion similar to an `f`-type expansion, which we terminate using `\exp_end:`. The argument is returned in braces.

```
2366 \cs_new:Npn \::V #1 \::: #2#3
2367 {
2368   \exp_after:wN \__exp_arg_next:nnn
2369   \exp_after:wN { \exp:w \__exp_eval_register:N #3 }
2370   {#1} {#2}
```

```

2371 }
2372 \cs_new:Npn \::v # 1\::: #2#3
2373 {
2374   \exp_after:wN \__exp_arg_next:nnn
2375   \exp_after:wN { \exp:w \__exp_eval_register:c {#3} }
2376   {#1} {#2}
2377 }

```

(End definition for `\::v` and `\::V`. These functions are documented on page 36.)

```

\__exp_eval_register:N
\__exp_eval_register:c
\__exp_eval_error_msg:w

```

This function evaluates a register. Now a register might exist as one of two things: A parameter-less macro or a built-in T_EX register such as `\count`. For the T_EX registers we have to utilize a `\the` whereas for the macros we merely have to expand them once. The trick is to find out when to use `\the` and when not to. What we want here is to find out whether the token expands to something else when hit with `\exp_after:wN`. The technique is to compare the meaning of the token in question when it has been prefixed with `\exp_not:N` and the token itself. If it is a macro, the prefixed `\exp_not:N` temporarily turns it into the primitive `\scan_stop:`.

```

2378 \cs_new:Npn \__exp_eval_register:N #1
2379 {
2380   \exp_after:wN \if_meaning:w \exp_not:N #1 #1

```

If the token was not a macro it may be a malformed variable from a `c` expansion in which case it is equal to the primitive `\scan_stop:`. In that case we throw an error. We could let T_EX do it for us but that would result in the rather obscure

! You can't use '`\relax`' after `\the`.

which while quite true doesn't give many hints as to what actually went wrong. We provide something more sensible.

```

2381   \if_meaning:w \scan_stop: #1
2382   \__exp_eval_error_msg:w
2383   \fi:

```

The next bit requires some explanation. The function must be initiated by `\exp:w` and we want to terminate this expansion chain by inserting the `\exp_end:` token. However, we have to expand the register `#1` before we do that. If it is a T_EX register, we need to execute the sequence `\exp_after:wN \exp_end: \tex_the:D #1` and if it is a macro we need to execute `\exp_after:wN \exp_end: #1`. We therefore issue the longer of the two sequences and if the register is a macro, we remove the `\tex_the:D`.

```

2384   \else:
2385     \exp_after:wN \use_i_ii:nnn
2386   \fi:
2387   \exp_after:wN \exp_end: \tex_the:D #1
2388 }
2389 \cs_new:Npn \__exp_eval_register:c #1
2390 { \exp_after:wN \__exp_eval_register:N \cs:w #1 \cs_end: }

```

Clean up nicely, then call the undefined control sequence. The result is an error message looking like this:

```

! Undefined control sequence.
<argument> \LaTeX3 error:
                               Erroneous variable used!
1.55 \tl_set:Nv \l_tmpa_tl {undefined_tl}

```

```

2391 \cs_new:Npn \__exp_eval_error_msg:w #1 \tex_the:D #2
2392 {
2393     \fi:
2394     \fi:
2395     \__msg_kernel_expandable_error:nnn { kernel } { bad-variable } {#2}
2396     \exp_end:
2397 }

```

(End definition for `__exp_eval_register:N` and `__exp_eval_error_msg:w`.)

4.2 Hand-tuned definitions

One of the most important features of these functions is that they are fully expandable.

`\exp_args:Nc` In l3basics.

`\exp_args:cc` (End definition for `\exp_args:Nc` and `\exp_args:cc`. These functions are documented on page 29.)

`\exp_args:NNc` Here are the functions that turn their argument into csnames but are expandable.

```

\exp_args:Ncc 2398 \cs_new:Npn \exp_args:NNc #1#2#3
\exp_args:Nccc 2399 { \exp_after:wN #1 \exp_after:wN #2 \cs:w # 3\cs_end: }
2400 \cs_new:Npn \exp_args:Ncc #1#2#3
2401 { \exp_after:wN #1 \cs:w #2 \exp_after:wN \cs_end: \cs:w #3 \cs_end: }
2402 \cs_new:Npn \exp_args:Nccc #1#2#3#4
2403 {
2404     \exp_after:wN #1
2405     \cs:w #2 \exp_after:wN \cs_end:
2406     \cs:w #3 \exp_after:wN \cs_end:
2407     \cs:w #4 \cs_end:
2408 }

```

(End definition for `\exp_args:NNc`, `\exp_args:Ncc`, and `\exp_args:Nccc`. These functions are documented on page 30.)

`\exp_args:No` Those lovely runs of expansion!

```

\exp_args:NNo 2409 \cs_new:Npn \exp_args:No #1#2 { \exp_after:wN #1 \exp_after:wN {#2} }
\exp_args:NNNo 2410 \cs_new:Npn \exp_args:NNo #1#2#3
2411 { \exp_after:wN #1 \exp_after:wN #2 \exp_after:wN {#3} }
2412 \cs_new:Npn \exp_args:NNNo #1#2#3#4
2413 { \exp_after:wN #1 \exp_after:wN#2 \exp_after:wN #3 \exp_after:wN {#4} }

```

(End definition for `\exp_args:No`, `\exp_args:NNo`, and `\exp_args:NNNo`. These functions are documented on page 29.)

`\exp_args:Nf`

`\exp_args:Nv`

`\exp_args:Nv`

```

2414 \cs_new:Npn \exp_args:Nf #1#2
2415 { \exp_after:wN #1 \exp_after:wN { \exp:w \exp_end_continue_f:w #2 } }
2416 \cs_new:Npn \exp_args:Nv #1#2
2417 {
2418     \exp_after:wN #1 \exp_after:wN
2419     { \exp:w \__exp_eval_register:c {#2} }
2420 }
2421 \cs_new:Npn \exp_args:Nv #1#2
2422 {
2423     \exp_after:wN #1 \exp_after:wN
2424     { \exp:w \__exp_eval_register:N #2 }
2425 }

```

(End definition for `\exp_args:Nf`, `\exp_args:Nv`, and `\exp_args:Nv`. These functions are documented on page 29.)

`\exp_args:NNV` Some more hand-tuned function with three arguments. If we forced that an `o` argument always has braces, we could implement `\exp_args:Nco` with less tokens and only two arguments.

```

2426 \cs_new:Npn \exp_args:NNV #1#2#3
2427 {
2428   \exp_after:wN #1
2429   \exp_after:wN #2
2430   \exp_after:wN { \exp:w \__exp_eval_register:N #3 }
2431 }
2432 \cs_new:Npn \exp_args:NNv #1#2#3
2433 {
2434   \exp_after:wN #1
2435   \exp_after:wN #2
2436   \exp_after:wN { \exp:w \__exp_eval_register:c {#3} }
2437 }
2438 \cs_new:Npn \exp_args:NNf #1#2#3
2439 {
2440   \exp_after:wN #1
2441   \exp_after:wN #2
2442   \exp_after:wN { \exp:w \exp_end_continue_f:w #3 }
2443 }
2444 \cs_new:Npn \exp_args:Nco #1#2#3
2445 {
2446   \exp_after:wN #1
2447   \cs:w #2 \exp_after:wN \cs_end:
2448   \exp_after:wN {#3}
2449 }
2450 \cs_new:Npn \exp_args:NcV #1#2#3
2451 {
2452   \exp_after:wN #1
2453   \cs:w #2 \exp_after:wN \cs_end:
2454   \exp_after:wN { \exp:w \__exp_eval_register:N #3 }
2455 }
2456 \cs_new:Npn \exp_args:Ncv #1#2#3
2457 {
2458   \exp_after:wN #1
2459   \cs:w #2 \exp_after:wN \cs_end:
2460   \exp_after:wN { \exp:w \__exp_eval_register:c {#3} }
2461 }
2462 \cs_new:Npn \exp_args:Ncf #1#2#3
2463 {
2464   \exp_after:wN #1
2465   \cs:w #2 \exp_after:wN \cs_end:
2466   \exp_after:wN { \exp:w \exp_end_continue_f:w #3 }
2467 }
2468 \cs_new:Npn \exp_args:NVV #1#2#3
2469 {
2470   \exp_after:wN #1
2471   \exp_after:wN { \exp:w \exp_after:wN
2472     \__exp_eval_register:N \exp_after:wN #2 \exp_after:wN }
2473   \exp_after:wN { \exp:w \__exp_eval_register:N #3 }

```

```
2474 }
```

(End definition for `\exp_args:NNV` and others. These functions are documented on page 30.)

`\exp_args:NNNV` A few more that we can hand-tune.

```
\exp_args:NcNc 2475 \cs_new:Npn \exp_args:NNNV #1#2#3#4
\exp_args:NcNo 2476 {
\exp_args:Ncco 2477   \exp_after:wN #1
2478   \exp_after:wN #2
2479   \exp_after:wN #3
2480   \exp_after:wN { \exp:w \_exp_eval_register:N #4 }
2481 }
2482 \cs_new:Npn \exp_args:NcNc #1#2#3#4
2483 {
2484   \exp_after:wN #1
2485   \cs:w #2 \exp_after:wN \cs_end:
2486   \exp_after:wN #3
2487   \cs:w #4 \cs_end:
2488 }
2489 \cs_new:Npn \exp_args:NcNo #1#2#3#4
2490 {
2491   \exp_after:wN #1
2492   \cs:w #2 \exp_after:wN \cs_end:
2493   \exp_after:wN #3
2494   \exp_after:wN {#4}
2495 }
2496 \cs_new:Npn \exp_args:Ncco #1#2#3#4
2497 {
2498   \exp_after:wN #1
2499   \cs:w #2 \exp_after:wN \cs_end:
2500   \cs:w #3 \exp_after:wN \cs_end:
2501   \exp_after:wN {#4}
2502 }
```

(End definition for `\exp_args:NNNV` and others. These functions are documented on page 30.)

4.3 Definitions with the automated technique

Some of these could be done more efficiently, but the complexity of coding then becomes an issue. Notice that the auto-generated functions actually take no arguments themselves.

`\exp_args:Nx`

```
2503 \cs_new_protected:Npn \exp_args:Nx { \::x \::: }
```

(End definition for `\exp_args:Nx`. This function is documented on page 30.)

`\exp_args:Nnc` Here are the actual function definitions, using the helper functions above.

```
\exp_args:Nno 2504 \cs_new:Npn \exp_args:Nnc { \::n \::c \::: }
\exp_args:NnV 2505 \cs_new:Npn \exp_args:Nno { \::n \::o \::: }
\exp_args:Nnv 2506 \cs_new:Npn \exp_args:NnV { \::n \::V \::: }
\exp_args:Nnf 2507 \cs_new:Npn \exp_args:Nnv { \::n \::v \::: }
\exp_args:Noc 2508 \cs_new:Npn \exp_args:Nnf { \::n \::f \::: }
\exp_args:Noo 2509 \cs_new:Npn \exp_args:Noc { \::o \::c \::: }
\exp_args:Nof 2510 \cs_new:Npn \exp_args:Noo { \::o \::o \::: }
```

`\exp_args:NVo`

`\exp_args:Nfo`

`\exp_args:Nff`

`\exp_args:NNx`

`\exp_args:Ncx`

`\exp_args:Nnx`

`\exp_args:Nox`

`\exp_args:Nxo`

`\exp_args:Nxx`

```

2511 \cs_new:Npn \exp_args:Nof { \::o \::f \::: }
2512 \cs_new:Npn \exp_args:NVo { \::V \::o \::: }
2513 \cs_new:Npn \exp_args:Nfo { \::f \::o \::: }
2514 \cs_new:Npn \exp_args:Nff { \::f \::f \::: }
2515 \cs_new_protected:Npn \exp_args:NNx { \::N \::x \::: }
2516 \cs_new_protected:Npn \exp_args:Ncx { \::c \::x \::: }
2517 \cs_new_protected:Npn \exp_args:Nnx { \::n \::x \::: }
2518 \cs_new_protected:Npn \exp_args:Nox { \::o \::x \::: }
2519 \cs_new_protected:Npn \exp_args:Nxo { \::x \::o \::: }
2520 \cs_new_protected:Npn \exp_args:Nxx { \::x \::x \::: }

```

(End definition for `\exp_args:Nnc` and others. These functions are documented on page 30.)

```

\exp_args:NNcf
\exp_args:NNno
\exp_args:NNnV
\exp_args:NNoo
\exp_args:NNVV
\exp_args:Ncno
\exp_args:NcnV
\exp_args:Ncoo
\exp_args:NcVV
\exp_args:Nnnc
\exp_args:Nnno
\exp_args:Nnnf
\exp_args:Nnff
\exp_args:Nooo
\exp_args:Noof
\exp_args:Nffo
\exp_args:NNNx
\exp_args:NNnx
\exp_args:NNox
\exp_args:Nccx
\exp_args:Ncnx
\exp_args:Nnnx
\exp_args:Nnox
\exp_args:Noox
2521 \cs_new:Npn \exp_args:NNcf { \::N \::c \::f \::: }
2522 \cs_new:Npn \exp_args:NNno { \::N \::n \::o \::: }
2523 \cs_new:Npn \exp_args:NNnV { \::N \::n \::V \::: }
2524 \cs_new:Npn \exp_args:NNoo { \::N \::o \::o \::: }
2525 \cs_new:Npn \exp_args:NNVV { \::N \::V \::V \::: }
2526 \cs_new:Npn \exp_args:Ncno { \::c \::n \::o \::: }
2527 \cs_new:Npn \exp_args:NcnV { \::c \::n \::V \::: }
2528 \cs_new:Npn \exp_args:Ncoo { \::c \::o \::o \::: }
2529 \cs_new:Npn \exp_args:NcVV { \::c \::V \::V \::: }
2530 \cs_new:Npn \exp_args:Nnnc { \::n \::n \::c \::: }
2531 \cs_new:Npn \exp_args:Nnno { \::n \::n \::o \::: }
2532 \cs_new:Npn \exp_args:Nnnf { \::n \::n \::f \::: }
2533 \cs_new:Npn \exp_args:Nnff { \::n \::f \::f \::: }
2534 \cs_new:Npn \exp_args:Nooo { \::o \::o \::o \::: }
2535 \cs_new:Npn \exp_args:Noof { \::o \::o \::f \::: }
2536 \cs_new:Npn \exp_args:Nffo { \::f \::f \::o \::: }
2537 \cs_new_protected:Npn \exp_args:NNNx { \::N \::N \::x \::: }
2538 \cs_new_protected:Npn \exp_args:NNnx { \::N \::n \::x \::: }
2539 \cs_new_protected:Npn \exp_args:NNox { \::N \::o \::x \::: }
2540 \cs_new_protected:Npn \exp_args:Nnnx { \::n \::n \::x \::: }
2541 \cs_new_protected:Npn \exp_args:Nnox { \::n \::o \::x \::: }
2542 \cs_new_protected:Npn \exp_args:Nccx { \::c \::c \::x \::: }
2543 \cs_new_protected:Npn \exp_args:Ncnx { \::c \::n \::x \::: }
2544 \cs_new_protected:Npn \exp_args:Noox { \::o \::o \::x \::: }

```

(End definition for `\exp_args:NNcf` and others. These functions are documented on page 31.)

4.4 Last-unbraced versions

`__exp_arg_last_unbraced:nn` There are a few places where the last argument needs to be available unbraced. First some helper macros.

```

\::o_unbraced
\::V_unbraced
\::v_unbraced
\::f_unbraced
\::x_unbraced
2545 \cs_new:Npn \__exp_arg_last_unbraced:nn #1#2 { #2#1 }
2546 \cs_new:Npn \::o_unbraced \::: { #1#2 }
2547 { \exp_after:wN \__exp_arg_last_unbraced:nn \exp_after:wN {#2} {#1} }
2548 \cs_new:Npn \::V_unbraced \::: { #1#2 }
2549 {
2550   \exp_after:wN \__exp_arg_last_unbraced:nn
2551   \exp_after:wN { \exp:w \__exp_eval_register:N #2 } {#1}
2552 }
2553 \cs_new:Npn \::v_unbraced \::: { #1#2 }

```

```

2554 {
2555     \exp_after:wN \__exp_arg_last_unbraced:nn
2556     \exp_after:wN { \exp:w \__exp_eval_register:c {#2} } {#1}
2557 }
2558 \cs_new:Npn \::f_unbraced \::: #1#2
2559 {
2560     \exp_after:wN \__exp_arg_last_unbraced:nn
2561     \exp_after:wN { \exp:w \exp_end_continue_f:w #2 } {#1}
2562 }
2563 \cs_new_protected:Npn \::x_unbraced \::: #1#2
2564 {
2565     \cs_set_nopar:Npx \l__exp_internal_tl { \exp_not:n {#1} #2 }
2566     \l__exp_internal_tl
2567 }

```

(End definition for __exp_arg_last_unbraced:nn and others. These functions are documented on page ??.)

\exp_last_unbraced:No Now the business end: most of these are hand-tuned for speed, but the general system is in place.

```

\exp_last_unbraced:NV
\exp_last_unbraced:Nv
\exp_last_unbraced:Nf
\exp_last_unbraced:NNo
\exp_last_unbraced:NNV
\exp_last_unbraced:Nco
\exp_last_unbraced:NcV
\exp_last_unbraced:NNNo
\exp_last_unbraced:NNNV
\exp_last_unbraced:Nno
\exp_last_unbraced:Noo
\exp_last_unbraced:Nfo
\exp_last_unbraced:NnNo
\exp_last_unbraced:NNNNo
\exp_last_unbraced:Nx

```

```

2568 \cs_new:Npn \exp_last_unbraced:No #1#2 { \exp_after:wN #1 #2 }
2569 \cs_new:Npn \exp_last_unbraced:NV #1#2
2570 { \exp_after:wN #1 \exp:w \__exp_eval_register:N #2 }
2571 \cs_new:Npn \exp_last_unbraced:Nv #1#2
2572 { \exp_after:wN #1 \exp:w \__exp_eval_register:c {#2} }
2573 \cs_new:Npn \exp_last_unbraced:Nf #1#2
2574 { \exp_after:wN #1 \exp:w \exp_end_continue_f:w #2 }
2575 \cs_new:Npn \exp_last_unbraced:NNo #1#2#3
2576 { \exp_after:wN #1 \exp_after:wN #2 #3 }
2577 \cs_new:Npn \exp_last_unbraced:NNV #1#2#3
2578 {
2579     \exp_after:wN #1
2580     \exp_after:wN #2
2581     \exp:w \__exp_eval_register:N #3
2582 }
2583 \cs_new:Npn \exp_last_unbraced:Nco #1#2#3
2584 { \exp_after:wN #1 \cs:w #2 \exp_after:wN \cs_end: #3 }
2585 \cs_new:Npn \exp_last_unbraced:NcV #1#2#3
2586 {
2587     \exp_after:wN #1
2588     \cs:w #2 \exp_after:wN \cs_end:
2589     \exp:w \__exp_eval_register:N #3
2590 }
2591 \cs_new:Npn \exp_last_unbraced:NNNo #1#2#3#4
2592 { \exp_after:wN #1 \exp_after:wN #2 \exp_after:wN #3 #4 }
2593 \cs_new:Npn \exp_last_unbraced:NNNV #1#2#3#4
2594 {
2595     \exp_after:wN #1
2596     \exp_after:wN #2
2597     \exp_after:wN #3
2598     \exp:w \__exp_eval_register:N #4
2599 }
2600 \cs_new:Npn \exp_last_unbraced:Nno { \::n \::o_unbraced \::: }
2601 \cs_new:Npn \exp_last_unbraced:Noo { \::o \::o_unbraced \::: }

```

```

2602 \cs_new:Npn \exp_last_unbraced:Nfo { \::f \::o_unbraced \::: }
2603 \cs_new:Npn \exp_last_unbraced:NnNo { \::n \::N \::o_unbraced \::: }
2604 \cs_new:Npn \exp_last_unbraced:NNNNo #1#2#3#4#5
2605   { \exp_after:wN #1 \exp_after:wN #2 \exp_after:wN #3 \exp_after:wN #4 #5 }
2606 \cs_new_protected:Npn \exp_last_unbraced:Nx { \::x_unbraced \::: }

```

(End definition for `\exp_last_unbraced:No` and others. These functions are documented on page 31.)

```

\exp_last_two_unbraced:Noo
\__exp_last_two_unbraced:noN

```

If #2 is a single token then this can be implemented as

```

\cs_new:Npn \exp_last_two_unbraced:Noo #1 #2 #3
  { \exp_after:wN \exp_after:wN \exp_after:wN #1 \exp_after:wN #2 #3 }

```

However, for robustness this is not suitable. Instead, a bit of a shuffle is used to ensure that #2 can be multiple tokens.

```

2607 \cs_new:Npn \exp_last_two_unbraced:Noo #1#2#3
2608   { \exp_after:wN \__exp_last_two_unbraced:noN \exp_after:wN {#3} {#2} #1 }
2609 \cs_new:Npn \__exp_last_two_unbraced:noN #1#2#3
2610   { \exp_after:wN #3 #2 #1 }

```

(End definition for `\exp_last_two_unbraced:Noo` and `__exp_last_two_unbraced:noN`. This function is documented on page 32.)

4.5 Preventing expansion

All these except `\exp_not:c` call the primitive `\etex_unexpanded:D` namely `\exp_not:n`.

```

\exp_not:c 2611 \cs_new:Npn \exp_not:c #1 { \exp_after:wN \exp_not:N \cs:w #1 \cs_end: }
\exp_not:o 2612 \cs_new:Npn \exp_not:o #1 { \etex_unexpanded:D \exp_after:wN {#1} }
\exp_not:f 2613 \cs_new:Npn \exp_not:f #1
\exp_not:V 2614   { \etex_unexpanded:D \exp_after:wN { \exp:w \exp_end_continue_f:w #1 } }
\exp_not:v 2615 \cs_new:Npn \exp_not:V #1
2616   {
2617     \etex_unexpanded:D \exp_after:wN
2618     { \exp:w \__exp_eval_register:N #1 }
2619   }
2620 \cs_new:Npn \exp_not:v #1
2621   {
2622     \etex_unexpanded:D \exp_after:wN
2623     { \exp:w \__exp_eval_register:c {#1} }
2624   }

```

(End definition for `\exp_not:c` and others. These functions are documented on page 32.)

4.6 Controlled expansion

`\exp:w` To trigger a sequence of “arbitrarily” many expansions we need a method to invoke T_EX’s
`\exp_end:` expansion mechanism in such a way that (a) we are able to stop it in a controlled manner
`\exp_end_continue_f:w` and (b) the result of what triggered the expansion in the first place is null, i.e., that we
`\exp_end_continue_f:nw` do not get any unwanted side effects. There aren’t that many possibilities in T_EX; in fact
the one explained below might well be the only one (as normally the result of expansion is not null).

The trick here is to make use of the fact that `\tex_romannumeral:D` expands the tokens following it when looking for a number and that its expansion is null if that number

turns out to be zero or negative. So we use that to start the expansion sequence: `\exp:w` is set equal to `\tex_romannumeral:D` in `l3basics`. To stop the expansion sequence in a controlled way all we need to provide is a constant integer zero as part of expanded tokens. As this is an integer constant it immediately stops `\tex_romannumeral:D`'s search for a number. Again, the definition of `\exp_end:` as the integer constant zero is in `l3basics`. (Note that according to our specification all tokens we expand initiated by `\exp:w` are supposed to be expandable (as well as their replacement text in the expansion) so we will not encounter a “number” that actually result in a roman numeral being generated. Or if we do then the programmer made a mistake.)

If on the other hand we want to stop the initial expansion sequence but continue with an `f`-type expansion we provide the alphabetic constant `^^@` that also represents 0 but this time `TEX`'s syntax for a *⟨number⟩* continues searching for an optional space (and it continues expansion doing that) — see `TEXbook` page 269 for details.

```
2625 \group_begin:
2626   \tex_catcode:D '^^@ = 13
2627   \cs_new_protected:Npn \exp_end_continue_f:w { '^^@ }
```

If the above definition ever appears outside its proper context the active character `^^@` will be executed so we turn this into an error.

```
2628   \cs_new:Npn ^^@
2629     { \__msg_kernel_expandable_error:nn { kernel } { bad-exp-end-f } }
```

The same but grabbing an argument to remove spaces and braces.

```
2630   \cs_new:Npn \exp_end_continue_f:nw #1 { '^^@ #1 }
2631 \group_end:
```

(End definition for `\exp:w` and others. These functions are documented on page 34.)

4.7 Defining function variants

```
2632 <@@=cs>
```

`\cs_generate_variant:Nn` #1 : Base form of a function; e.g., `\tl_set:Nn`
 #2 : One or more variant argument specifiers; e.g., `{Nx,c,cx}`

After making sure that the base form exists, test whether it is protected or not and define `__cs_tmp:w` as either `\cs_new:Npx` or `\cs_new_protected:Npx`, which is then used to define all the variants (except those involving `x`-expansion, always protected). Split up the original base function only once, to grab its name and signature. Then we wish to iterate through the comma list of variant argument specifiers, which we first convert to a string: the reason is explained later.

```
2633 \__debug_patch:nnNpn { \__debug_chk_cs_exist:N #1 } { }
2634 \cs_new_protected:Npn \cs_generate_variant:Nn #1#2
2635 {
2636   \__cs_generate_variant:N #1
2637   \exp_after:wN \__cs_split_function:NN
2638   \exp_after:wN #1
2639   \exp_after:wN \__cs_generate_variant:nnNN
2640   \exp_after:wN #1
2641   \tl_to_str:n {#2} , \scan_stop: , \q_recursion_stop
2642 }
```

(End definition for `\cs_generate_variant:Nn`. This function is documented on page 27.)

```

\__cs_generate_variant:N
\__cs_generate_variant:ww
\__cs_generate_variant:wwNw

```

The goal here is to pick up protected parent functions. There are four cases: the parent function can be a primitive or a macro, and can be expandable or not. For non-expandable primitives, all variants should be protected; skipping the `\else:` branch is safe because non-expandable primitives cannot be \TeX conditionals.

The other case where variants should be protected is when the parent function is a protected macro: then `protected` appears in the meaning before the first occurrence of `macro`. The `ww` auxiliary removes everything in the meaning string after the first `ma`. We use `ma` rather than the full `macro` because the meaning of the `\firstmark` primitive (and four others) can contain an arbitrary string after a leading `firstmark:`. Then, look for `pr` in the part we extracted: no need to look for anything longer: the only strings we can have are an empty string, `\long`, `\protected`, `\protected\long`, `\first`, `\top`, `\bot`, `\splittop`, or `\splitbot`, with `\` replaced by the appropriate escape character. If `pr` appears in the part before `ma`, the first `\q_mark` is taken as an argument of the `wwNw` auxiliary, and `#3` is `\cs_new_protected:Npx`, otherwise it is `\cs_new:Npx`.

```

2643 \cs_new_protected:Npx \__cs_generate_variant:N #1
2644 {
2645   \exp_not:N \exp_after:wN \exp_not:N \if_meaning:w
2646     \exp_not:N \exp_not:N #1 #1
2647     \cs_set_eq:NN \exp_not:N \__cs_tmp:w \cs_new_protected:Npx
2648     \exp_not:N \else:
2649     \exp_not:N \exp_after:wN \exp_not:N \__cs_generate_variant:ww
2650     \exp_not:N \token_to_meaning:N #1 \tl_to_str:n { ma }
2651     \exp_not:N \q_mark
2652     \exp_not:N \q_mark \cs_new_protected:Npx
2653     \tl_to_str:n { pr }
2654     \exp_not:N \q_mark \cs_new:Npx
2655     \exp_not:N \q_stop
2656   \exp_not:N \fi:
2657 }
2658 \exp_last_unbraced:NNNNo
2659 \cs_new_protected:Npn \__cs_generate_variant:ww
2660   #1 { \tl_to_str:n { ma } } #2 \q_mark
2661   { \__cs_generate_variant:wwNw #1 }
2662 \exp_last_unbraced:NNNNo
2663 \cs_new_protected:Npn \__cs_generate_variant:wwNw
2664   #1 { \tl_to_str:n { pr } } #2 \q_mark #3 #4 \q_stop
2665   { \cs_set_eq:NN \__cs_tmp:w #3 }

```

(End definition for `__cs_generate_variant:N`, `__cs_generate_variant:ww`, and `__cs_generate_variant:wwNw`.)

```

\__cs_generate_variant:nnNN

```

- `#1` : Base name.
- `#2` : Base signature.
- `#3` : Boolean.
- `#4` : Base function.

If the boolean is `\c_false_bool`, the base function has no colon and we abort with an error; otherwise, set off a loop through the desired variant forms. The original function is retained as `#4` for efficiency.

```

2666 \cs_new_protected:Npn \__cs_generate_variant:nnNN #1#2#3#4
2667 {
2668   \if_meaning:w \c_false_bool #3
2669     \__msg_kernel_error:nnx { kernel } { missing-colon }

```

```

2670         { \token_to_str:c {#1} }
2671         \exp_after:wN \use_none_delimit_by_q_recursion_stop:w
2672     \fi:
2673     \__cs_generate_variant:Nnnw #4 {#1}{#2}
2674 }

```

(End definition for __cs_generate_variant:nnNN.)

__cs_generate_variant:Nnnw #1 : Base function.
 #2 : Base name.
 #3 : Base signature.
 #4 : Beginning of variant signature.

First check whether to terminate the loop over variant forms. Then, for each variant form, construct a new function name using the original base name, the variant signature consisting of l letters and the last $k - l$ letters of the base signature (of length k). For example, for a base function \prop_put:Nnn which needs a cV variant form, we want the new signature to be cVn.

There are further subtleties:

- In \cs_generate_variant:Nn \foo:nnTF {xxTF}, we must define \foo:xxTF using \exp_args:Nxx, rather than a hypothetical \exp_args:NxxTF. Thus, we wish to trim a common trailing part from the base signature and the variant signature.
- In \cs_generate_variant:Nn \foo:on {ox}, the function \foo:ox must be defined using \exp_args:Nnx, not \exp_args:Nox, to avoid double o expansion.
- Lastly, \cs_generate_variant:Nn \foo:on {xn} must trigger an error, because we do not have a means to replace o-expansion by x-expansion. More generally, we can only convert N to c, or convert n to V, v, o, f, x.

All this boils down to a few rules. Only n and N-type arguments can be replaced by \cs_generate_variant:Nn. Other argument types are allowed to be passed unchanged from the base form to the variant: in the process they are changed to n except for N and p-type arguments. A common trailing part is ignored.

We compare the base and variant signatures one character at a time within x-expansion. The result is given to __cs_generate_variant:wwNN (defined later) in the form $\langle processed\ variant\ signature \rangle \backslash q_mark \langle errors \rangle \backslash q_stop \langle base\ function \rangle \langle new\ function \rangle$. If all went well, $\langle errors \rangle$ is empty; otherwise, it is a kernel error message and some clean-up code.

Note the space after #3 and after the following brace group. Those are ignored by T_EX when fetching the last argument for __cs_generate_variant_loop:nNwN, but can be used as a delimiter for __cs_generate_variant_loop_end:nwwwNNnn.

```

2675 \cs_new_protected:Npn \__cs_generate_variant:Nnnw #1#2#3#4 ,
2676 {
2677     \if_meaning:w \scan_stop: #4
2678     \exp_after:wN \use_none_delimit_by_q_recursion_stop:w
2679     \fi:
2680     \use:x
2681     {
2682         \exp_not:N \__cs_generate_variant:wwNN
2683         \__cs_generate_variant_loop:nNwN { }
2684         #4
2685         \__cs_generate_variant_loop_end:nwwwNNnn

```

```

2686         \q_mark
2687         #3 ~
2688         { ~ { } \fi: \_cs_generate_variant_loop_long:wNNnn } ~
2689         { }
2690         \q_stop
2691         \exp_not:N #1 {#2} {#4}
2692     }
2693     \_cs_generate_variant:Nnnw #1 {#2} {#3}
2694 }

```

(End definition for `_cs_generate_variant:Nnnw`.)

<code>_cs_generate_variant_loop:nNwN</code>	#1 : Last few consecutive letters common between the base and variant (more precisely,
<code>_cs_generate_variant_loop_base:N</code>	<code>_cs_generate_variant_same:N</code> <i><letter></i> for each letter).
<code>_cs_generate_variant_loop_same:w</code>	#2 : Next variant letter.
<code>_cs_generate_variant_loop_end:nwwwNNnn</code>	#3 : Remainder of variant form.
<code>_cs_generate_variant_loop_long:wNNnn</code>	#4 : Next base letter.
<code>_cs_generate_variant_loop_invalid:NNwNNnn</code>	The first argument is populated by <code>_cs_generate_variant_loop_same:w</code> when
<code>_cs_generate_variant_loop_special:NNwNNnn</code>	a variant letter and a base letter match. It is flushed into the input stream whenever the
<code>_cs_generate_variant_loop_warning:nxxxxx</code>	two letters are different: if the loop ends before, the argument is dropped, which means

that trailing common letters are ignored.

The case where the two letters are different is only allowed if the base is N and the variant is o, V, v, f or x. Otherwise, call `_cs_generate_variant_loop_invalid:NNwNNnn` to remove the end of the loop, get arguments at the end of the loop, and place an appropriate error message as a second argument of `_cs_generate_variant:wwNN`. If the letters are distinct and the base letter is indeed n or N, leave in the input stream whatever argument #1 was collected, and the next variant letter #2, then loop by calling `_cs_generate_variant_loop:nNwN`.

The loop can stop in three ways.

- If the end of the variant form is encountered first, #2 is `_cs_generate_variant_loop_end:nwwwNNnn` (expanded by the conditional `\if:w`), which inserts some tokens to end the conditional; grabs the *<base name>* as #7, the *<variant signature>* #8, the *<next base letter>* #1 and the part #3 of the base signature that wasn't read yet; and combines those into the *<new function>* to be defined.
- If the end of the base form is encountered first, #4 is `~{ }\fi:` which ends the conditional (with an empty expansion), followed by `_cs_generate_variant_loop_long:wNNnn`, which places an error as the second argument of `_cs_generate_variant:wwNN`.
- The loop can be interrupted early if the requested expansion is unavailable, namely when the variant and base letters differ and the base is not the right one (n or N to support the variant). In that case too an error is placed as the second argument of `_cs_generate_variant:wwNN`.

Note that if the variant form has the same length as the base form, #2 is as described in the first point, and #4 as described in the second point above. The `_cs_generate_variant_loop_end:nwwwNNnn` breaking function takes the empty brace group in #4 as its first argument: this empty brace group produces the correct signature for the full variant.

Since people seem to have tried generating N or c-type variants of n-type arguments, and n, o, V, v, f, x variants of N-type arguments, in those cases we only produce a warning.

```

2695 \cs_new:Npn \__cs_generate_variant_loop:nNwN #1#2#3 \q_mark #4
2696 {
2697   \if:w #2 #4
2698     \exp_after:wN \__cs_generate_variant_loop_same:w
2699   \else:
2700     \if:w #4 \__cs_generate_variant_loop_base:N #2 \else:
2701       \if:w 0
2702         \if:w N #4 \else: \if:w n #4 \else: 1 \fi: \fi:
2703         \if:w \scan_stop: \__cs_generate_variant_loop_base:N #2 1 \fi:
2704         0
2705         \__cs_generate_variant_loop_special:NNwNNnn #4#2
2706       \else:
2707         \__cs_generate_variant_loop_invalid:NNwNNnn #4#2
2708       \fi:
2709     \fi:
2710   \fi:
2711   #1
2712   \prg_do_nothing:
2713   #2
2714   \__cs_generate_variant_loop:nNwN { } #3 \q_mark
2715 }
2716 \cs_new:Npn \__cs_generate_variant_loop_base:N #1
2717 {
2718   \if:w c #1 N \else:
2719     \if:w o #1 n \else:
2720       \if:w V #1 n \else:
2721         \if:w v #1 n \else:
2722           \if:w f #1 n \else:
2723             \if:w x #1 n \else:
2724               \if:w n #1 n \else:
2725                 \if:w N #1 N \else:
2726                   \scan_stop:
2727                 \fi:
2728               \fi:
2729             \fi:
2730           \fi:
2731         \fi:
2732       \fi:
2733     \fi:
2734   \fi:
2735 }
2736 \cs_new:Npn \__cs_generate_variant_loop_same:w
2737 #1 \prg_do_nothing: #2#3#4
2738 { #3 { #1 \__cs_generate_variant_same:N #2 } }
2739 \cs_new:Npn \__cs_generate_variant_loop_end:nwwwNNnn
2740 #1#2 \q_mark #3 ~ #4 \q_stop #5#6#7#8
2741 {
2742   \scan_stop: \scan_stop: \fi:
2743   \exp_not:N \q_mark
2744   \exp_not:N \q_stop
2745   \exp_not:N #6
2746   \exp_not:c { #7 : #8 #1 #3 }
2747 }
2748 \cs_new:Npn \__cs_generate_variant_loop_long:wNNnn #1 \q_stop #2#3#4#5

```

```

2749 {
2750   \exp_not:n
2751   {
2752     \q_mark
2753     \_msg_kernel_error:nnxx { kernel } { variant-too-long }
2754     {#5} { \token_to_str:N #3 }
2755     \use_none:nnn
2756     \q_stop
2757     #3
2758     #3
2759   }
2760 }
2761 \cs_new:Npn \__cs_generate_variant_loop_invalid:NNwNNnn
2762   #1#2 \fi: \fi: \fi: #3 \q_stop #4#5#6#7
2763 {
2764   \fi: \fi: \fi:
2765   \exp_not:n
2766   {
2767     \q_mark
2768     \_msg_kernel_error:nnxxx { kernel } { invalid-variant }
2769     {#7} { \token_to_str:N #5 } {#1} {#2}
2770     \use_none:nnn
2771     \q_stop
2772     #5
2773     #5
2774   }
2775 }
2776 \cs_new:Npn \__cs_generate_variant_loop_special:NNwNNnn #1#2#3 \q_stop #4#5#6#7
2777 {
2778   #3 \q_stop #4 #5 {#6} {#7}
2779   \exp_not:n
2780   {
2781     \_cs_generate_variant_loop_warning:nnxxx { kernel } { invalid-variant }
2782     {#7} { \token_to_str:N #5 } {#1} {#2}
2783   }
2784 }
2785 \cs_new_protected:Npn \__cs_generate_variant_loop_warning:nnxxx
2786   { \_msg_kernel_warning:nnxxx }

```

(End definition for __cs_generate_variant_loop:nNwN and others.)

__cs_generate_variant_same:N When the base and variant letters are identical, don't do any expansion. For most argument types, we can use the n-type no-expansion, but the N and p types require a slightly different behaviour with respect to braces. For V-type this function could output N to avoid adding useless braces but that is not a problem.

```

2787 \cs_new:Npn \__cs_generate_variant_same:N #1
2788 {
2789   \if:w N #1 N \else:
2790     \if:w p #1 p \else:
2791       n
2792     \if:w n #1 \else:
2793       \_cs_generate_variant_loop_special:NNwNNnn #1#1
2794     \fi:
2795   \fi:

```

```

2796     \fi:
2797   }

```

(End definition for _cs_generate_variant_same:N.)

_cs_generate_variant:wwNN If the variant form has already been defined, log its existence (provided log-functions is active). Otherwise, make sure that the \exp_args:N #3 form is defined, and if it contains x, change _cs_tmp:w locally to \cs_new_protected:Npx. Then define the variant by combining the \exp_args:N #3 variant and the base function.

```

2798 \__debug_patch:nnNNpn
2799 {
2800   \cs_if_free:NF #4
2801   {
2802     \__debug_log:x
2803     {
2804       Variant~\token_to_str:N #4~%
2805       already~defined;~ not~ changing~ it~ \msg_line_context:
2806     }
2807   }
2808 }
2809 { }
2810 \cs_new_protected:Npn \_cs_generate_variant:wwNN
2811   #1 \q_mark #2 \q_stop #3#4
2812 {
2813   #2
2814   \cs_if_free:NT #4
2815   {
2816     \group_begin:
2817     \_cs_generate_internal_variant:n {#1}
2818     \_cs_tmp:w #4 { \exp_not:c { exp_args:N #1 } \exp_not:N #3 }
2819     \group_end:
2820   }
2821 }

```

(End definition for _cs_generate_variant:wwNN.)

_cs_generate_internal_variant:n Test if \exp_args:N #1 is already defined and if not define it via the \:: commands using the chars in #1. If #1 contains an x (this is the place where having converted the original comma-list argument to a string is very important), the result should be protected, and the next variant to be defined using that internal variant should be protected.

```

2822 \cs_new_protected:Npx \_cs_generate_internal_variant:n #1
2823 {
2824   \exp_not:N \_cs_generate_internal_variant:wwnNwnn
2825   #1 \exp_not:N \q_mark
2826   { \cs_set_eq:NN \exp_not:N \_cs_tmp:w \cs_new_protected:Npx }
2827   \cs_new_protected:cpx
2828   \token_to_str:N x \exp_not:N \q_mark
2829   { }
2830   \cs_new:cpx
2831   \exp_not:N \q_stop
2832   { exp_args:N #1 }
2833   {
2834     \exp_not:N \_cs_generate_internal_variant_loop:n #1
2835     { : \exp_not:N \use_i:nn }

```

```

2836     }
2837   }
2838   \use:x
2839   {
2840     \cs_new_protected:Npn \exp_not:N \__cs_generate_internal_variant:wwnNwnn
2841       ##1 \token_to_str:N x ##2 \exp_not:N \q_mark
2842       ##3 ##4 ##5 \exp_not:N \q_stop ##6 ##7
2843   }
2844   {
2845     #3
2846     \cs_if_free:cT {#6} { #4 {#6} {#7} }
2847   }

```

This command grabs char by char outputting `\:##1` (not expanded further). We avoid tests by putting a trailing `\use_i:nn`, which leaves `\cs_end:` and removes the looping macro. The colon is in fact also turned into `\:::` so that the required structure for `\exp_args:N...` commands is correctly terminated.

```

2848 \cs_new:Npn \__cs_generate_internal_variant_loop:n #1
2849 {
2850   \exp_after:wN \exp_not:N \cs:w :: #1 \cs_end:
2851   \__cs_generate_internal_variant_loop:n
2852 }

```

(End definition for `__cs_generate_internal_variant:n`, `__cs_generate_internal_variant:wwnw`, and `__cs_generate_internal_variant_loop:n`.)

```

2853 </initex | package>

```

5 l3tl implementation

```

2854 <*initex | package>

```

```

2855 <@@=tl>

```

A token list variable is a `TeX` macro that holds tokens. By using the ε -`TeX` primitive `\unexpanded` inside a `TeX` `\edef` it is possible to store any tokens, including `#`, in this way.

5.1 Functions

`\tl_new:N` Creating new token list variables is a case of checking for an existing definition and doing the definition.

`\tl_new:c`

```

2856 \cs_new_protected:Npn \tl_new:N #1
2857 {
2858   \__chk_if_free_cs:N #1
2859   \cs_gset_eq:NN #1 \c_empty_tl
2860 }
2861 \cs_generate_variant:Nn \tl_new:N { c }

```

(End definition for `\tl_new:N`. This function is documented on page 37.)

`\tl_const:Nn` Constants are also easy to generate.

`\tl_const:Nx`

`\tl_const:cn`

`\tl_const:cx`

```

2862 \__debug_patch:nnNpn { \__debug_chk_var_scope:NN c #1 } { }
2863 \cs_new_protected:Npn \tl_const:Nn #1#2
2864 {
2865   \__chk_if_free_cs:N #1

```



```

2866     \cs_gset_nopar:Npx #1 { \exp_not:n {#2} }
2867   }
2868   \__debug_patch:nnNNpn { \__debug_chk_var_scope:NN c #1 } { }
2869   \cs_new_protected:Npn \tl_const:Nx #1#2
2870   {
2871     \__chk_if_free_cs:N #1
2872     \cs_gset_nopar:Npx #1 {#2}
2873   }
2874   \cs_generate_variant:Nn \tl_const:Nn { c }
2875   \cs_generate_variant:Nn \tl_const:Nx { c }

```

(End definition for `\tl_const:Nn`. This function is documented on page 37.)

`\tl_clear:N` Clearing a token list variable means setting it to an empty value. Error checking is sorted out by the parent function.

```

\tl_clear:c      2876 \cs_new_protected:Npn \tl_clear:N #1
\tl_gclear:N     2877 { \tl_set_eq:NN #1 \c_empty_tl }
\tl_gclear:c     2878 \cs_new_protected:Npn \tl_gclear:N #1
\tl_gclear:c     2879 { \tl_gset_eq:NN #1 \c_empty_tl }
\tl_gclear:c     2880 \cs_generate_variant:Nn \tl_clear:N { c }
\tl_gclear:c     2881 \cs_generate_variant:Nn \tl_gclear:N { c }

```

(End definition for `\tl_clear:N` and `\tl_gclear:N`. These functions are documented on page 37.)

`\tl_clear_new:N` Clearing a token list variable means setting it to an empty value. Error checking is sorted out by the parent function.

```

\tl_clear_new:N  2882 \cs_new_protected:Npn \tl_clear_new:N #1
\tl_clear_new:c  2883 { \tl_if_exist:NTF #1 { \tl_clear:N #1 } { \tl_new:N #1 } }
\tl_gclear_new:N 2884 \cs_new_protected:Npn \tl_gclear_new:N #1
\tl_gclear_new:c 2885 { \tl_if_exist:NTF #1 { \tl_gclear:N #1 } { \tl_new:N #1 } }
\tl_gclear_new:c 2886 \cs_generate_variant:Nn \tl_clear_new:N { c }
\tl_gclear_new:c 2887 \cs_generate_variant:Nn \tl_gclear_new:N { c }

```

(End definition for `\tl_clear_new:N` and `\tl_gclear_new:N`. These functions are documented on page 38.)

`\tl_set_eq:NN` For setting token list variables equal to each other. When checking is turned on, make sure both variables exist.

```

\tl_set_eq:Nc    2888 \tex_ifodd:D \l@expl@enable@debug@bool
\tl_set_eq:cN    2889 \cs_new_protected:Npn \tl_set_eq:NN #1#2
\tl_set_eq:cc    2890 {
\tl_gset_eq:NN   2891   \__debug_chk_var_local:N #1
\tl_gset_eq:Nc   2892   \__debug_chk_var_exist:N #2
\tl_gset_eq:cN   2893   \cs_set_eq:NN #1 #2
\tl_gset_eq:cc   2894 }
\tl_gset_eq:cc   2895 \cs_new_protected:Npn \tl_gset_eq:NN #1#2
\tl_gset_eq:cc   2896 {
\tl_gset_eq:cc   2897   \__debug_chk_var_global:N #1
\tl_gset_eq:cc   2898   \__debug_chk_var_exist:N #2
\tl_gset_eq:cc   2899   \cs_gset_eq:NN #1 #2
\tl_gset_eq:cc   2900 }
\tl_gset_eq:cc   2901 \else:
\tl_gset_eq:cc   2902   \cs_new_eq:NN \tl_set_eq:NN \cs_set_eq:NN
\tl_gset_eq:cc   2903   \cs_new_eq:NN \tl_gset_eq:NN \cs_gset_eq:NN
\tl_gset_eq:cc   2904 \fi:

```

```

2905 \cs_generate_variant:Nn \tl_set_eq:NN { cN, Nc, cc }
2906 \cs_generate_variant:Nn \tl_gset_eq:NN { cN, Nc, cc }

```

(End definition for `\tl_set_eq:NN` and `\tl_gset_eq:NN`. These functions are documented on page 38.)

`\tl_concat:NNN` Concatenating token lists is easy. When checking is turned on, all three arguments must be checked: a token list #2 or #3 equal to `\scan_stop:` would lead to problems later on.

```

\tl_concat:ccc
\tl_gconcat:NNN
\tl_gconcat:ccc
2907 \__debug_patch:nnNNpn
2908 {
2909   \__debug_chk_var_exist:N #2
2910   \__debug_chk_var_exist:N #3
2911 }
2912 { }
2913 \cs_new_protected:Npn \tl_concat:NNN #1#2#3
2914 { \tl_set:Nx #1 { \exp_not:o {#2} \exp_not:o {#3} } }
2915 \__debug_patch:nnNNpn
2916 {
2917   \__debug_chk_var_exist:N #2
2918   \__debug_chk_var_exist:N #3
2919 }
2920 { }
2921 \cs_new_protected:Npn \tl_gconcat:NNN #1#2#3
2922 { \tl_gset:Nx #1 { \exp_not:o {#2} \exp_not:o {#3} } }
2923 \cs_generate_variant:Nn \tl_concat:NNN { ccc }
2924 \cs_generate_variant:Nn \tl_gconcat:NNN { ccc }

```

(End definition for `\tl_concat:NNN` and `\tl_gconcat:NNN`. These functions are documented on page 38.)

`\tl_if_exist_p:N` Copies of the `cs` functions defined in `l3basics`.

```

\tl_if_exist_p:c
\tl_if_exist:NTF
\tl_if_exist:cTF
2925 \prg_new_eq_conditional:NNn \tl_if_exist:N \cs_if_exist:N { TF , T , F , p }
2926 \prg_new_eq_conditional:NNn \tl_if_exist:c \cs_if_exist:c { TF , T , F , p }

```

(End definition for `\tl_if_exist:NTF`. This function is documented on page 38.)

5.2 Constant token lists

`\c_empty_tl` Never full. We need to define that constant before using `\tl_new:N`.

```

2927 \tl_const:Nn \c_empty_tl { }

```

(End definition for `\c_empty_tl`. This variable is documented on page 49.)

`\c_novalue_tl` A special marker: as we don't have `\char_generate:nn` yet, has to be created the old-fashioned way.

```

2928 \group_begin:
2929 \tex_lccode:D 'A = '-
2930 \tex_lccode:D 'N = 'N
2931 \tex_lccode:D 'V = 'V
2932 \tex_lowercase:D
2933 {
2934   \group_end:
2935   \tl_const:Nn \c_novalue_tl { ANoValue- }
2936 }

```

(End definition for `\c_novalue_tl`. This variable is documented on page 50.)

\c_space_tl A space as a token list (as opposed to as a character).

```
2937 \tl_const:Nn \c_space_tl { ~ }
```

(End definition for \c_space_tl. This variable is documented on page 50.)

5.3 Adding to token list variables

\tl_set:Nn By using \exp_not:n token list variables can contain # tokens, which makes the token list registers provided by T_EX more or less redundant. The \tl_set:No version is done “by hand” as it is used quite a lot. Each definition is prefixed by a call to __debug_patch:nnNNpn which adds an existence check to the definition.

```
2938 \__debug_patch:nnNNpn { \__debug_chk_var_local:N #1 } { }
2939 \cs_new_protected:Npn \tl_set:Nn #1#2
2940 { \cs_set_nopar:Npx #1 { \exp_not:n {#2} } }
2941 \__debug_patch:nnNNpn { \__debug_chk_var_local:N #1 } { }
2942 \cs_new_protected:Npn \tl_set:No #1#2
2943 { \cs_set_nopar:Npx #1 { \exp_not:o {#2} } }
2944 \__debug_patch:nnNNpn { \__debug_chk_var_local:N #1 } { }
2945 \cs_new_protected:Npn \tl_set:Nx #1#2
2946 { \cs_set_nopar:Npx #1 {#2} }
2947 \__debug_patch:nnNNpn { \__debug_chk_var_global:N #1 } { }
2948 \cs_new_protected:Npn \tl_gset:Nn #1#2
2949 { \cs_gset_nopar:Npx #1 { \exp_not:n {#2} } }
2950 \__debug_patch:nnNNpn { \__debug_chk_var_global:N #1 } { }
2951 \cs_new_protected:Npn \tl_gset:No #1#2
2952 { \cs_gset_nopar:Npx #1 { \exp_not:o {#2} } }
2953 \__debug_patch:nnNNpn { \__debug_chk_var_global:N #1 } { }
2954 \cs_new_protected:Npn \tl_gset:Nx #1#2
2955 { \cs_gset_nopar:Npx #1 {#2} }
2956 \cs_generate_variant:Nn \tl_set:Nn { NV , Nv , Nf }
2957 \cs_generate_variant:Nn \tl_set:Nx { c }
2958 \cs_generate_variant:Nn \tl_set:Nn { c , co , cV , cv , cf }
2959 \cs_generate_variant:Nn \tl_gset:Nn { NV , Nv , Nf }
2960 \cs_generate_variant:Nn \tl_gset:Nx { c }
2961 \cs_generate_variant:Nn \tl_gset:Nn { c , co , cV , cv , cf }
```

(End definition for \tl_set:Nn and \tl_gset:Nn. These functions are documented on page 38.)

\tl_put_left:Nn Adding to the left is done directly to gain a little performance.

```
2962 \__debug_patch:nnNNpn { \__debug_chk_var_local:N #1 } { }
2963 \cs_new_protected:Npn \tl_put_left:Nn #1#2
2964 { \cs_set_nopar:Npx #1 { \exp_not:n {#2} \exp_not:o #1 } }
2965 \__debug_patch:nnNNpn { \__debug_chk_var_local:N #1 } { }
2966 \cs_new_protected:Npn \tl_put_left:NV #1#2
2967 { \cs_set_nopar:Npx #1 { \exp_not:V #2 \exp_not:o #1 } }
2968 \__debug_patch:nnNNpn { \__debug_chk_var_local:N #1 } { }
2969 \cs_new_protected:Npn \tl_put_left:No #1#2
2970 { \cs_set_nopar:Npx #1 { \exp_not:o {#2} \exp_not:o #1 } }
2971 \__debug_patch:nnNNpn { \__debug_chk_var_local:N #1 } { }
2972 \cs_new_protected:Npn \tl_put_left:Nx #1#2
2973 { \cs_set_nopar:Npx #1 { #2 \exp_not:o #1 } }
2974 \__debug_patch:nnNNpn { \__debug_chk_var_global:N #1 } { }
2975 \cs_new_protected:Npn \tl_gput_left:Nn #1#2
2976 { \cs_gset_nopar:Npx #1 { \exp_not:n {#2} \exp_not:o #1 } }
```

```

2977 \__debug_patch:nnNNpn { \__debug_chk_var_global:N #1 } { }
2978 \cs_new_protected:Npn \tl_gput_left:NV #1#2
2979   { \cs_gset_nopar:Npx #1 { \exp_not:V #2 \exp_not:o #1 } }
2980 \__debug_patch:nnNNpn { \__debug_chk_var_global:N #1 } { }
2981 \cs_new_protected:Npn \tl_gput_left:No #1#2
2982   { \cs_gset_nopar:Npx #1 { \exp_not:o {#2} \exp_not:o #1 } }
2983 \__debug_patch:nnNNpn { \__debug_chk_var_global:N #1 } { }
2984 \cs_new_protected:Npn \tl_gput_left:Nx #1#2
2985   { \cs_gset_nopar:Npx #1 { #2 \exp_not:o {#1} } }
2986 \cs_generate_variant:Nn \tl_put_left:Nn { c }
2987 \cs_generate_variant:Nn \tl_put_left:NV { c }
2988 \cs_generate_variant:Nn \tl_put_left:No { c }
2989 \cs_generate_variant:Nn \tl_put_left:Nx { c }
2990 \cs_generate_variant:Nn \tl_gput_left:Nn { c }
2991 \cs_generate_variant:Nn \tl_gput_left:NV { c }
2992 \cs_generate_variant:Nn \tl_gput_left:No { c }
2993 \cs_generate_variant:Nn \tl_gput_left:Nx { c }

```

(End definition for `\tl_put_left:Nn` and `\tl_gput_left:Nn`. These functions are documented on page 38.)

`\tl_put_right:Nn`

The same on the right.

```

\tl_put_right:NV 2994 \__debug_patch:nnNNpn { \__debug_chk_var_local:N #1 } { }
\tl_put_right:No 2995 \cs_new_protected:Npn \tl_put_right:Nn #1#2
\tl_put_right:Nx 2996   { \cs_set_nopar:Npx #1 { \exp_not:o #1 \exp_not:n {#2} } }
\tl_put_right:cn 2997 \__debug_patch:nnNNpn { \__debug_chk_var_local:N #1 } { }
\tl_put_right:cV 2998 \cs_new_protected:Npn \tl_put_right:NV #1#2
\tl_put_right:co 2999   { \cs_set_nopar:Npx #1 { \exp_not:o #1 \exp_not:V #2 } }
\tl_put_right:cx 3000 \__debug_patch:nnNNpn { \__debug_chk_var_local:N #1 } { }
\tl_gput_right:Nn 3001 \cs_new_protected:Npn \tl_put_right:No #1#2
\tl_gput_right:NV 3002   { \cs_set_nopar:Npx #1 { \exp_not:o #1 \exp_not:o {#2} } }
\tl_gput_right:No 3003 \__debug_patch:nnNNpn { \__debug_chk_var_local:N #1 } { }
\tl_gput_right:Nx 3004 \cs_new_protected:Npn \tl_put_right:Nx #1#2
\tl_gput_right:cn 3005   { \cs_set_nopar:Npx #1 { \exp_not:o #1 #2 } }
\tl_gput_right:cV 3006 \__debug_patch:nnNNpn { \__debug_chk_var_global:N #1 } { }
\tl_gput_right:co 3007 \cs_new_protected:Npn \tl_gput_right:Nn #1#2
\tl_gput_right:cx 3008   { \cs_gset_nopar:Npx #1 { \exp_not:o #1 \exp_not:n {#2} } }
3009 \__debug_patch:nnNNpn { \__debug_chk_var_global:N #1 } { }
3010 \cs_new_protected:Npn \tl_gput_right:NV #1#2
3011   { \cs_gset_nopar:Npx #1 { \exp_not:o #1 \exp_not:V #2 } }
3012 \__debug_patch:nnNNpn { \__debug_chk_var_global:N #1 } { }
3013 \cs_new_protected:Npn \tl_gput_right:No #1#2
3014   { \cs_gset_nopar:Npx #1 { \exp_not:o #1 \exp_not:o {#2} } }
3015 \__debug_patch:nnNNpn { \__debug_chk_var_global:N #1 } { }
3016 \cs_new_protected:Npn \tl_gput_right:Nx #1#2
3017   { \cs_gset_nopar:Npx #1 { \exp_not:o {#1} #2 } }
3018 \cs_generate_variant:Nn \tl_put_right:Nn { c }
3019 \cs_generate_variant:Nn \tl_put_right:NV { c }
3020 \cs_generate_variant:Nn \tl_put_right:No { c }
3021 \cs_generate_variant:Nn \tl_put_right:Nx { c }
3022 \cs_generate_variant:Nn \tl_gput_right:Nn { c }
3023 \cs_generate_variant:Nn \tl_gput_right:NV { c }
3024 \cs_generate_variant:Nn \tl_gput_right:No { c }
3025 \cs_generate_variant:Nn \tl_gput_right:Nx { c }

```

(End definition for `\tl_put_right:Nn` and `\tl_gput_right:Nn`. These functions are documented on page 38.)

5.4 Reassigning token list category codes

`\c_tl_rescan_marker_tl`

The rescanning code needs a special token list containing the same character (chosen here to be a colon) with two different category codes: it cannot appear in the tokens being rescanned since all colons have the same category code.

```
3026 \tl_const:Nx \c_tl_rescan_marker_tl { : \token_to_str:N : }
```

(End definition for `\c_tl_rescan_marker_tl`.)

`\tl_set_rescan:Nnn`

`\tl_set_rescan:Nno`

`\tl_set_rescan:Nnx`

`\tl_set_rescan:cnn`

`\tl_set_rescan:cno`

`\tl_set_rescan:cnx`

`\tl_gset_rescan:Nnn`

`\tl_gset_rescan:Nno`

`\tl_gset_rescan:Nnx`

`\tl_gset_rescan:cnn`

`\tl_gset_rescan:cno`

`\tl_gset_rescan:cnx`

`\tl_rescan:nn`

`__tl_set_rescan:NNnn`

`__tl_set_rescan_multi:n`

`__tl_rescan:w`

These functions use a common auxiliary. After some initial setup explained below, and the user setup #3 (followed by `\scan_stop:` to be safe), the tokens are rescanned by `__tl_set_rescan:n` and stored into `\l__tl_internal_a_tl`, then passed to #1#2 outside the group after expansion. The auxiliary `__tl_set_rescan:n` is defined later: in the simplest case, this auxiliary calls `__tl_set_rescan_multi:n`, whose code is included here to help understand the approach.

One difficulty when rescanning is that `\scantokens` treats the argument as a file, and without the correct settings a T_EX error occurs:

```
! File ended while scanning definition of ...
```

The standard solution is to use an x-expanding assignment and set `\everyeof` to `\exp_not:N` to suppress the error at the end of the file. Since the rescanned tokens should not be expanded, they are taken as a delimited argument of an auxiliary which wraps them in `\exp_not:n` (in fact `\exp_not:o`, as there is a `\prg_do_nothing:` to avoid losing braces). The delimiter cannot appear within the rescanned token list because it contains twice the same character, with different catcodes.

The difference between single-line and multiple-line files complicates the story, as explained below.

```
3027 \cs_new_protected:Npn \tl_set_rescan:Nnn
3028 { \__tl_set_rescan:NNnn \tl_set:Nn }
3029 \cs_new_protected:Npn \tl_gset_rescan:Nnn
3030 { \__tl_set_rescan:NNnn \tl_gset:Nn }
3031 \cs_new_protected:Npn \tl_rescan:nn
3032 { \__tl_set_rescan:NNnn \prg_do_nothing: \use:n }
3033 \cs_new_protected:Npn \__tl_set_rescan:NNnn #1#2#3#4
3034 {
3035   \tl_if_empty:nTF {#4}
3036   {
3037     \group_begin:
3038     #3
3039     \group_end:
3040     #1 #2 { }
3041   }
3042   {
3043     \group_begin:
3044     \exp_args:No \etex_everyeof:D { \c_tl_rescan_marker_tl \exp_not:N }
3045     \int_compare:nNnT \tex_endlinechar:D = { 32 }
3046     { \int_set:Nn \tex_endlinechar:D { -1 } }
3047     \tex_newlinechar:D \tex_endlinechar:D
3048     #3 \scan_stop:
```

```

3049         \exp_args:No \__tl_set_rescan:n { \tl_to_str:n {#4} }
3050         \exp_args:NNNo
3051         \group_end:
3052         #1 #2 \l__tl_internal_a_tl
3053     }
3054 }
3055 \cs_new_protected:Npn \__tl_set_rescan_multi:n #1
3056 {
3057     \tl_set:Nx \l__tl_internal_a_tl
3058     {
3059         \exp_after:wN \__tl_rescan:w
3060         \exp_after:wN \prg_do_nothing:
3061         \etex_scantokens:D {#1}
3062     }
3063 }
3064 \exp_args:Nno \use:nn
3065 { \cs_new:Npn \__tl_rescan:w #1 } \c__tl_rescan_marker_tl
3066 { \exp_not:o {#1} }
3067 \cs_generate_variant:Nn \tl_set_rescan:Nnn { Nno , Nnx }
3068 \cs_generate_variant:Nn \tl_set_rescan:Nnn { c , cno , cnx }
3069 \cs_generate_variant:Nn \tl_gset_rescan:Nnn { Nno , Nnx }
3070 \cs_generate_variant:Nn \tl_gset_rescan:Nnn { c , cno }

```

(End definition for `\tl_set_rescan:Nnn` and others. These functions are documented on page 40.)

```

\__tl_set_rescan:n
\__tl_set_rescan:NnTF
\__tl_set_rescan_single:nn
\__tl_set_rescan_single_aux:nn

```

This function calls `__tl_set_rescan_multiple:n` or `__tl_set_rescan_single:nn` { ' } depending on whether its argument is a single-line fragment of code/data or is made of multiple lines by testing for the presence of a `\newlinechar` character. If `\newlinechar` is out of range, the argument is assumed to be a single line.

The case of multiple lines is a straightforward application of `\scantokens` as described above. The only subtlety is that `\newlinechar` should be equal to `\endlinechar` because `\newlinechar` characters become new lines and then become `\endlinechar` characters when writing to an abstract file and reading back. This equality is ensured by setting `\newlinechar` equal to `\endlinechar`. Prior to this, `\endlinechar` is set to -1 if it was 32 (in particular true after `\ExplSyntaxOn`) to avoid unreasonable line-breaks at every space for instance in error messages triggered by the user setup. Another side effect of reading back from the file is that spaces (catcode 10) are ignored at the beginning of lines, and spaces and tabs (character code 32 and 9) are ignored at the end of lines.

For a single line, no `\endlinechar` should be added, so it is set to -1, and spaces should not be removed.

Trailing spaces and tabs are a difficult matter, as TeX removes these at a very low level. The only way to preserve them is to rescan not the argument but the argument followed by a character with a reasonable category code. Here, 11 (letter), 12 (other) and 13 (active) are accepted, as these are suitable for delimiting an argument, and it is very unlikely that none of the ASCII characters are in one of these categories. To avoid selecting one particular character to put at the end, whose category code may have been modified, there is a loop through characters from ' (ASCII 39) to ~ (ASCII 127). The choice of starting point was made because this is the start of a very long range of characters whose standard category is letter or other, thus minimizing the number of steps needed by the loop (most often just a single one). Once a valid character is found, run some code very similar to `__tl_set_rescan_multi:n`, except that `__tl_rescan:w` must be redefined to also remove the additional character (with the appropriate

catcode). Getting the delimiter with the right catcode requires using `\scantokens` inside an `x`-expansion, hence using the previous definition of `__tl_rescan:w` as well. The odd `\exp_not:N \use:n` ensures that the trailing `\exp_not:N` in `\everyeof` does not prevent the expansion of `\c__tl_rescan_marker_tl`, but rather of a closing brace (this does nothing). If no valid character is found, similar code is ran, and the only difference is that trailing spaces are not preserved (bear in mind that this only happens if no character between 39 and 127 has catcode letter, other or active).

There is also some work to preserve leading spaces: test whether the first character (given by `\str_head:n`, with an extra space to circumvent a limitation of `f`-expansion) has catcode 10 and add what `TEX` would add in the middle of a line for any sequence of such characters: a single space with catcode 10 and character code 32.

```

3071 \group_begin:
3072   \tex_catcode:D '\^~@ = 12 \scan_stop:
3073   \cs_new_protected:Npn \__tl_set_rescan:n #1
3074   {
3075     \int_compare:nNnTF \tex_newlinechar:D < 0
3076     { \use_ii:nn }
3077     {
3078       \char_set_lccode:nn { 0 } { \tex_newlinechar:D }
3079       \tex_lowercase:D { \__tl_set_rescan:NnTF ^~@ } {#1}
3080     }
3081     { \__tl_set_rescan_multi:n }
3082     { \__tl_set_rescan_single:nn { ' } }
3083   {#1}
3084   }
3085   \cs_new_protected:Npn \__tl_set_rescan:NnTF #1#2
3086   { \tl_if_in:nnTF {#2} {#1} }
3087   \cs_new_protected:Npn \__tl_set_rescan_single:nn #1
3088   {
3089     \int_compare:nNnTF
3090     { \char_value_catcode:n { '#1 } / 3 } = 4
3091     { \__tl_set_rescan_single_aux:nn {#1} }
3092     {
3093       \int_compare:nNnTF { '#1 } < { '\~ }
3094       {
3095         \char_set_lccode:nn { 0 } { '#1 + 1 }
3096         \tex_lowercase:D { \__tl_set_rescan_single:nn { ^~@ } }
3097       }
3098       { \__tl_set_rescan_single_aux:nn { } }
3099     }
3100   }
3101   \cs_new_protected:Npn \__tl_set_rescan_single_aux:nn #1#2
3102   {
3103     \int_set:Nn \tex_endlinechar:D { -1 }
3104     \use:x
3105     {
3106       \exp_not:N \use:n
3107       {
3108         \exp_not:n { \cs_set:Npn \__tl_rescan:w ##1 }
3109         \exp_after:wN \__tl_rescan:w
3110         \exp_after:wN \prg_do_nothing:
3111         \etex_scantokens:D {#1}
3112       }

```

```

3113         \c__tl_rescan_marker_tl
3114     }
3115     { \exp_not:o {##1} }
3116 \tl_set:Nx \l__tl_internal_a_tl
3117 {
3118     \int_compare:nNnT
3119     {
3120         \char_value_catcode:n
3121         { \exp_last_unbraced:Nf ‘ \str_head:n {#2} ~ }
3122     }
3123     = { 10 } { ~ }
3124     \exp_after:wN \__tl_rescan:w
3125     \exp_after:wN \prg_do_nothing:
3126     \etex_scantokens:D { #2 #1 }
3127 }
3128 }
3129 \group_end:

```

(End definition for `__tl_set_rescan:n` and others.)

5.5 Modifying token list variables

`\tl_replace_all:Nnn` All of the `replace` functions call `__tl_replace:NnNNnn` with appropriate arguments. The first two arguments are explained later. The next controls whether the replacement function calls itself (`__tl_replace_next:w`) or stops (`__tl_replace_wrap:w`) after the first replacement. Next comes an x-type assignment function `\tl_set:Nx` or `\tl_gset:Nx` for local or global replacements. Finally, the three arguments $\langle tl\ var \rangle$ $\{ \langle pattern \rangle \}$ $\{ \langle replacement \rangle \}$ provided by the user. When describing the auxiliary functions below, we denote the contents of the $\langle tl\ var \rangle$ by $\langle token\ list \rangle$.

```

3130 \cs_new_protected:Npn \tl_replace_once:Nnn
3131 { \__tl_replace:NnNNnn \q_mark ? \__tl_replace_wrap:w \tl_set:Nx }
3132 \cs_new_protected:Npn \tl_greplace_once:Nnn
3133 { \__tl_replace:NnNNnn \q_mark ? \__tl_replace_wrap:w \tl_gset:Nx }
3134 \cs_new_protected:Npn \tl_replace_all:Nnn
3135 { \__tl_replace:NnNNnn \q_mark ? \__tl_replace_next:w \tl_set:Nx }
3136 \cs_new_protected:Npn \tl_greplace_all:Nnn
3137 { \__tl_replace:NnNNnn \q_mark ? \__tl_replace_next:w \tl_gset:Nx }
3138 \cs_generate_variant:Nn \tl_replace_once:Nnn { c }
3139 \cs_generate_variant:Nn \tl_greplace_once:Nnn { c }
3140 \cs_generate_variant:Nn \tl_replace_all:Nnn { c }
3141 \cs_generate_variant:Nn \tl_greplace_all:Nnn { c }

```

(End definition for `\tl_replace_all:Nnn` and others. These functions are documented on page 39.)

`__tl_replace:NnNNnn` To implement the actual replacement auxiliary `__tl_replace_auxii:nNNNnn` we need a $\langle delimiter \rangle$ with the following properties:

- all occurrences of the $\langle pattern \rangle$ #6 in “ $\langle token\ list \rangle$ $\langle delimiter \rangle$ ” belong to the $\langle token\ list \rangle$ and have no overlap with the $\langle delimiter \rangle$,
- the first occurrence of the $\langle delimiter \rangle$ in “ $\langle token\ list \rangle$ $\langle delimiter \rangle$ ” is the trailing $\langle delimiter \rangle$.

We first find the building blocks for the $\langle \text{delimiter} \rangle$, namely two tokens $\langle A \rangle$ and $\langle B \rangle$ such that $\langle A \rangle$ does not appear in $\#6$ and $\#6$ is not $\langle B \rangle$ (this condition is trivial if $\#6$ has more than one token). Then we consider the delimiters “ $\langle A \rangle$ ” and “ $\langle A \rangle \langle A \rangle^n \langle B \rangle \langle A \rangle^n \langle B \rangle$ ”, for $n \geq 1$, where $\langle A \rangle^n$ denotes n copies of $\langle A \rangle$, and we choose as our $\langle \text{delimiter} \rangle$ the first one which is not in the $\langle \text{token list} \rangle$.

Every delimiter in the set obeys the first condition: $\#6$ does not contain $\langle A \rangle$ hence cannot be overlapping with the $\langle \text{token list} \rangle$ and the $\langle \text{delimiter} \rangle$, and it cannot be within the $\langle \text{delimiter} \rangle$ since it would have to be in one of the two $\langle B \rangle$ hence be equal to this single token (or empty, but this is an error case filtered separately). Given the particular form of these delimiters, for which no prefix is also a suffix, the second condition is actually a consequence of the weaker condition that the $\langle \text{delimiter} \rangle$ we choose does not appear in the $\langle \text{token list} \rangle$. Additionally, the set of delimiters is such that a $\langle \text{token list} \rangle$ of n tokens can contain at most $O(n^{1/2})$ of them, hence we find a $\langle \text{delimiter} \rangle$ with at most $O(n^{1/2})$ tokens in a time at most $O(n^{3/2})$. Bear in mind that these upper bounds are reached only in very contrived scenarios: we include the case “ $\langle A \rangle$ ” in the list of delimiters to try, so that the $\langle \text{delimiter} \rangle$ is simply $\backslash \text{q_mark}$ in the most common situation where neither the $\langle \text{token list} \rangle$ nor the $\langle \text{pattern} \rangle$ contains $\backslash \text{q_mark}$.

Let us now ahead, optimizing for this most common case. First, two special cases: an empty $\langle \text{pattern} \rangle$ $\#6$ is an error, and if $\#1$ is absent from both the $\langle \text{token list} \rangle$ $\#5$ and the $\langle \text{pattern} \rangle$ $\#6$ then we can use it as the $\langle \text{delimiter} \rangle$ through $\backslash _ \text{tl_replace_auxii:nNNNnn} \{ \#1 \}$. Otherwise, we end up calling $\backslash _ \text{tl_replace:NnNNNnn}$ repeatedly with the first two arguments $\backslash \text{q_mark} \{ ? \}$, $\backslash ? \{ ?? \}$, $\backslash ?? \{ ??? \}$, and so on, until $\#6$ does not contain the control sequence $\#1$, which we take as our $\langle A \rangle$. The argument $\#2$ only serves to collect $?$ characters for $\#1$. Note that the order of the tests means that the first two are done every time, which is wasteful (for instance, we repeatedly test for the emptiness of $\#6$). However, this is rare enough not to matter. Finally, choose $\langle B \rangle$ to be $\backslash \text{q_nil}$ or $\backslash \text{q_stop}$ such that it is not equal to $\#6$.

The $\backslash _ \text{tl_replace_auxi:NnnNNNnn}$ auxiliary receives $\{ \langle A \rangle \}$ and $\{ \langle A \rangle^n \langle B \rangle \}$ as its arguments, initially with $n = 1$. If “ $\langle A \rangle \langle A \rangle^n \langle B \rangle \langle A \rangle^n \langle B \rangle$ ” is in the $\langle \text{token list} \rangle$ then increase n and try again. Once it is not anymore in the $\langle \text{token list} \rangle$ we take it as our $\langle \text{delimiter} \rangle$ and pass this to the auxii auxiliary.

```

3142 \cs_new_protected:Npn \_tl_replace:NnNNNnn #1#2#3#4#5#6#7
3143 {
3144   \tl_if_empty:nTF {#6}
3145   {
3146     \_msg_kernel_error:nxx { kernel } { empty-search-pattern }
3147     { \tl_to_str:n {#7} }
3148   }
3149   {
3150     \tl_if_in:onTF { #5 #6 } {#1}
3151     {
3152       \tl_if_in:nnTF {#6} {#1}
3153       { \exp_args:Nc \_tl_replace:NnNNNnn {#2} {#2?} }
3154       {
3155         \quark_if_nil:nTF {#6}
3156         { \_tl_replace_auxi:NnnNNNnn #5 {#1} { #1 \q_stop } }
3157         { \_tl_replace_auxi:NnnNNNnn #5 {#1} { #1 \q_nil } }
3158       }
3159     }
3160     { \_tl_replace_auxii:nNNNnn {#1} }
3161     #3#4#5 {#6} {#7}

```

```

3162     }
3163   }
3164   \cs_new_protected:Npn \__tl_replace_auxi:NnnNNNnn #1#2#3
3165   {
3166     \tl_if_in:NnTF #1 { #2 #3 #3 }
3167     { \__tl_replace_auxi:NnnNNNnn #1 { #2 #3 } {#2} }
3168     { \__tl_replace_auxii:nNNNnn { #2 #3 #3 } }
3169   }

```

The auxiliary `__tl_replace_auxii:nNNNnn` receives the following arguments: $\{\langle\textit{delimiter}\rangle\}$ $\langle\textit{function}\rangle$ $\langle\textit{assignment}\rangle$ $\langle\textit{tl var}\rangle$ $\{\langle\textit{pattern}\rangle\}$ $\{\langle\textit{replacement}\rangle\}$. All of its work is done between `\group_align_safe_begin:` and `\group_align_safe_end:` to avoid issues in alignments. It does the actual replacement within `#3 #4 {...}`, an x-expanding $\langle\textit{assignment}\rangle$ `#3` to the $\langle\textit{tl var}\rangle$ `#4`. The auxiliary `__tl_replace_next:w` is called, followed by the $\langle\textit{token list}\rangle$, some tokens including the $\langle\textit{delimiter}\rangle$ `#1`, followed by the $\langle\textit{pattern}\rangle$ `#5`. This auxiliary finds an argument delimited by `#5` (the presence of a trailing `#5` avoids runaway arguments) and calls `__tl_replace_wrap:w` to test whether this `#5` is found within the $\langle\textit{token list}\rangle$ or is the trailing one.

If on the one hand it is found within the $\langle\textit{token list}\rangle$, then `##1` cannot contain the $\langle\textit{delimiter}\rangle$ `#1` that we worked so hard to obtain, thus `__tl_replace_wrap:w` gets `##1` as its own argument `##1`, and protects it against the x-expanding assignment. It also finds `\exp_not:n` as `##2` and does nothing to it, thus letting through `\exp_not:n` $\{\langle\textit{replacement}\rangle\}$ into the assignment. Note that `__tl_replace_next:w` and `__tl_replace_wrap:w` are always called followed by two empty brace groups. These are safe because no delimiter can match them. They prevent losing braces when grabbing delimited arguments, but require the use of `\exp_not:o` and `\use_none:nn`, rather than simply `\exp_not:n`. Afterwards, `__tl_replace_next:w` is called to repeat the replacement, or `__tl_replace_wrap:w` if we only want a single replacement. In this second case, `##1` is the $\langle\textit{remaining tokens}\rangle$ in the $\langle\textit{token list}\rangle$ and `##2` is some $\langle\textit{ending code}\rangle$ which ends the assignment and removes the trailing tokens `#5` using some `\if_false: { \fi: }` trickery because `#5` may contain any delimiter.

If on the other hand the argument `##1` of `__tl_replace_next:w` is delimited by the trailing $\langle\textit{pattern}\rangle$ `#5`, then `##1` is “`{ } { } { } \langle\textit{token list}\rangle \langle\textit{delimiter}\rangle \{\langle\textit{ending code}\rangle\}`”, hence `__tl_replace_wrap:w` finds “`{ } { } { } \langle\textit{token list}\rangle`” as `##1` and the $\langle\textit{ending code}\rangle$ as `##2`. It leaves the $\langle\textit{token list}\rangle$ into the assignment and unbraces the $\langle\textit{ending code}\rangle$ which removes what remains (essentially the $\langle\textit{delimiter}\rangle$ and $\langle\textit{replacement}\rangle$).

```

3170 \cs_new_protected:Npn \__tl_replace_auxii:nNNNnn #1#2#3#4#5#6
3171 {
3172   \group_align_safe_begin:
3173   \cs_set:Npn \__tl_replace_wrap:w ##1 #1 ##2
3174   { \exp_not:o { \use_none:nn ##1 } ##2 }
3175   \cs_set:Npx \__tl_replace_next:w ##1 #5
3176   {
3177     \exp_not:N \__tl_replace_wrap:w ##1
3178     \exp_not:n { #1 }
3179     \exp_not:n { \exp_not:n {#6} }
3180     \exp_not:n { #2 { } { } }
3181   }
3182   #3 #4
3183   {
3184     \exp_after:wN \__tl_replace_next:w
3185     \exp_after:wN { \exp_after:wN }

```

```

3186     \exp_after:wN { \exp_after:wN }
3187     #4
3188     #1
3189     {
3190       \if_false: { \fi: }
3191       \exp_after:wN \use_none:n \exp_after:wN { \if_false: } \fi:
3192     }
3193     #5
3194   }
3195   \group_align_safe_end:
3196 }
3197 \cs_new_eq:NN \__tl_replace_wrap:w ?
3198 \cs_new_eq:NN \__tl_replace_next:w ?

```

(End definition for `__tl_replace:NnNNNnn` and others.)

```

\relax \tl_remove_once:Nn Removal is just a special case of replacement.
\relax \tl_remove_once:cn 3199 \cs_new_protected:Npn \tl_remove_once:Nn #1#2
\relax \tl_gremove_once:Nn 3200 { \tl_replace_once:Nnn #1 {#2} { } }
\relax \tl_gremove_once:cn 3201 \cs_new_protected:Npn \tl_gremove_once:Nn #1#2
3202 { \tl_greplace_once:Nnn #1 {#2} { } }
3203 \cs_generate_variant:Nn \tl_remove_once:Nn { c }
3204 \cs_generate_variant:Nn \tl_gremove_once:Nn { c }

```

(End definition for `\tl_remove_once:Nn` and `\tl_gremove_once:Nn`. These functions are documented on page 39.)

```

\relax \tl_remove_all:Nn Removal is just a special case of replacement.
\relax \tl_remove_all:cn 3205 \cs_new_protected:Npn \tl_remove_all:Nn #1#2
\relax \tl_gremove_all:Nn 3206 { \tl_replace_all:Nnn #1 {#2} { } }
\relax \tl_gremove_all:cn 3207 \cs_new_protected:Npn \tl_gremove_all:Nn #1#2
3208 { \tl_greplace_all:Nnn #1 {#2} { } }
3209 \cs_generate_variant:Nn \tl_remove_all:Nn { c }
3210 \cs_generate_variant:Nn \tl_gremove_all:Nn { c }

```

(End definition for `\tl_remove_all:Nn` and `\tl_gremove_all:Nn`. These functions are documented on page 39.)

5.6 Token list conditionals

```

\relax \tl_if_blank_p:n TeX skips spaces when reading a non-delimited arguments. Thus, a <token list> is blank
\relax \tl_if_blank_p:V if and only if \use_none:n <token list> ? is empty after one expansion. The auxiliary
\relax \tl_if_blank_p:o \__tl_if_empty_return:o is a fast emptiness test, converting its argument to a string
\relax \tl_if_blank:nTF (after one expansion) and using the test \if_meaning:w \q_nil ... \q_nil.
\relax \tl_if_blank:VTF
\relax \tl_if_blank:oTF
\__tl_if_blank_p:NNw
3211 \prg_new_conditional:Npnn \tl_if_blank:n #1 { p , T , F , TF }
3212 { \__tl_if_empty_return:o { \use_none:n #1 ? } }
3213 \cs_generate_variant:Nn \tl_if_blank_p:n { V }
3214 \cs_generate_variant:Nn \tl_if_blank:nT { V }
3215 \cs_generate_variant:Nn \tl_if_blank:nF { V }
3216 \cs_generate_variant:Nn \tl_if_blank:nTF { V }
3217 \cs_generate_variant:Nn \tl_if_blank_p:n { o }
3218 \cs_generate_variant:Nn \tl_if_blank:nT { o }
3219 \cs_generate_variant:Nn \tl_if_blank:nF { o }
3220 \cs_generate_variant:Nn \tl_if_blank:nTF { o }

```

(End definition for `\tl_if_blank:nTF` and `__tl_if_blank_p:NNw`. This function is documented on page 40.)

<code>\tl_if_empty_p:N</code>	These functions check whether the token list in the argument is empty and execute the proper code from their argument(s).
<code>\tl_if_empty_p:c</code>	

```

\tl_if_empty:N $\underline{TF}$ 
\tl_if_empty:c $\underline{TF}$ 
3221 \prg_new_conditional:Npnn \tl_if_empty:N #1 { p , T , F , TF }
3222 {
3223   \if_meaning:w #1 \c_empty_tl
3224     \prg_return_true:
3225   \else:
3226     \prg_return_false:
3227   \fi:
3228 }
3229 \cs_generate_variant:Nn \tl_if_empty_p:N { c }
3230 \cs_generate_variant:Nn \tl_if_empty_NT { c }
3231 \cs_generate_variant:Nn \tl_if_empty_NF { c }
3232 \cs_generate_variant:Nn \tl_if_empty_NTF { c }

```

(End definition for `\tl_if_empty:NTF`. This function is documented on page 41.)

<code>\tl_if_empty_p:n</code>	Convert the argument to a string: this is empty if and only if the argument is. Then
<code>\tl_if_empty_p:V</code>	<code>\if_meaning:w \q_nil ... \q_nil</code> is true if and only if the string ... is empty. It
<code>\tl_if_empty:nTF</code>	could be tempting to use <code>\if_meaning:w \q_nil #1 \q_nil</code> directly. This fails on a
<code>\tl_if_empty:VTF</code>	token list starting with <code>\q_nil</code> of course but more troubling is the case where argument
	is a complete conditional such as <code>\if_true: a \else: b \fi:</code> because then <code>\if_true:</code>
	is used by <code>\if_meaning:w</code> , the test turns out false, the <code>\else:</code> executes the false
	branch, the <code>\fi:</code> ends it and the <code>\q_nil</code> at the end starts executing...

```

3233 \prg_new_conditional:Npnn \tl_if_empty:n #1 { p , TF , T , F }
3234 {
3235     \exp_after:wN \if_meaning:w \exp_after:wN \q_nil
3236     \tl_to_str:n {#1} \q_nil
3237     \prg_return_true:
3238 }else:
3239     \prg_return_false:
3240 \fi:
3241 }
3242 \cs_generate_variant:Nn \tl_if_empty_p:n { V }
3243 \cs_generate_variant:Nn \tl_if_empty:nTF { V }
3244 \cs_generate_variant:Nn \tl_if_empty:nT { V }
3245 \cs_generate_variant:Nn \tl_if_empty:nF { V }

```

(End definition for `\tl_if_empty:nTF`. This function is documented on page 41.)

<code>\tl_if_empty_p:o</code> <code>\tl_if_empty:oTF</code> <code>_tl_if_empty_return:o</code>	<p>The auxiliary function <code>_tl_if_empty_return:o</code> is for use in various token list conditionals which reduce to testing if a given token list is empty after applying a simple function to it. The test for emptiness is based on <code>\tl_if_empty:nTF</code>, but the expansion is hard-coded for efficiency, as this auxiliary function is used in many places. Note that this works because <code>\etex_detokenize:D</code> expands tokens that follow until reading a catcode 1 (begin-group) token.</p>
---	--

```

3246 \cs_new:Npn \__tl_if_empty_return:o #1
3247 {
3248   \exp_after:wN \if_meaning:w \exp_after:wN \q_nil
3249   \etex_detokenize:D \exp_after:wN {#1} \q_nil

```

```

3250     \prg_return_true:
3251   \else:
3252     \prg_return_false:
3253   \fi:
3254 }
3255 \prg_new_conditional:Npnn \tl_if_empty:o #1 { p , TF , T , F }
3256 { \__tl_if_empty_return:o {#1} }

```

(End definition for `\tl_if_empty:nTF` and `__tl_if_empty_return:o`. This function is documented on page 41.)

`\tl_if_eq_p:NN` Returns `\c_true_bool` if and only if the two token list variables are equal.

```

\tl_if_eq_p:Nc 3257 \prg_new_conditional:Npnn \tl_if_eq:NN #1#2 { p , T , F , TF }
\tl_if_eq_p:cN 3258 {
\tl_if_eq_p:cc 3259   \if_meaning:w #1 #2
\tl_if_eq:NNTF 3260     \prg_return_true:
\tl_if_eq:NcTF 3261   \else:
\tl_if_eq:cNTF 3262     \prg_return_false:
\tl_if_eq:ccTF 3263   \fi:
3264 }
3265 \cs_generate_variant:Nn \tl_if_eq_p:NN { Nc , c , cc }
3266 \cs_generate_variant:Nn \tl_if_eq:NNTF { Nc , c , cc }
3267 \cs_generate_variant:Nn \tl_if_eq:NNT { Nc , c , cc }
3268 \cs_generate_variant:Nn \tl_if_eq:NNTF { Nc , c , cc }

```

(End definition for `\tl_if_eq:NNTF`. This function is documented on page 41.)

`\tl_if_eq:nnTF` A simple store and compare routine.

```

\l__tl_internal_a_tl 3269 \prg_new_protected_conditional:Npnn \tl_if_eq:nn #1#2 { T , F , TF }
\l__tl_internal_b_tl 3270 {
3271   \group_begin:
3272     \tl_set:Nn \l__tl_internal_a_tl {#1}
3273     \tl_set:Nn \l__tl_internal_b_tl {#2}
3274     \if_meaning:w \l__tl_internal_a_tl \l__tl_internal_b_tl
3275       \group_end:
3276       \prg_return_true:
3277     \else:
3278       \group_end:
3279       \prg_return_false:
3280     \fi:
3281 }
3282 \tl_new:N \l__tl_internal_a_tl
3283 \tl_new:N \l__tl_internal_b_tl

```

(End definition for `\tl_if_eq:nnTF`, `\l__tl_internal_a_tl`, and `\l__tl_internal_b_tl`. This function is documented on page 41.)

`\tl_if_in:NnTF` See `\tl_if_in:nnTF` for further comments. Here we simply expand the token list variable and pass it to `\tl_if_in:nnTF`.

```

\tl_if_in:cnTF 3284 \cs_new_protected:Npn \tl_if_in:NnT { \exp_args:No \tl_if_in:nnT }
3285 \cs_new_protected:Npn \tl_if_in:NnF { \exp_args:No \tl_if_in:nnF }
3286 \cs_new_protected:Npn \tl_if_in:NnTF { \exp_args:No \tl_if_in:nnTF }
3287 \cs_generate_variant:Nn \tl_if_in:NnT { c }
3288 \cs_generate_variant:Nn \tl_if_in:NnF { c }
3289 \cs_generate_variant:Nn \tl_if_in:NnTF { c }

```

(End definition for `\tl_if_in:nTF`. This function is documented on page 41.)

`\tl_if_in:nnTF` Once more, the test relies on the emptiness test for robustness. The function `__tl_tmp:w` removes tokens until the first occurrence of #2. If this does not appear in #1, then the final #2 is removed, leaving an empty token list. Otherwise some tokens remain, and the test is false. See `\tl_if_empty:nTF` for details on the emptiness test.

Treating correctly cases like `\tl_if_in:nnTF {a state}{states}`, where #1#2 contains #2 before the end, requires special care. To cater for this case, we insert `{ }{ }` between the two token lists. This marker may not appear in #2 because of T_EX limitations on what can delimit a parameter, hence we are safe. Using two brace groups makes the test work also for empty arguments. The `\if_false:` constructions are a faster way to do `\group_align_safe_begin:` and `\group_align_safe_end:`.

```

3290 \prg_new_protected_conditional:Npnn \tl_if_in:nn #1#2 { T , F , TF }
3291 {
3292   \if_false: { \fi:
3293     \cs_set:Npn \__tl_tmp:w ##1 #2 { }
3294     \tl_if_empty:oTF { \__tl_tmp:w #1 {} {} #2 }
3295     { \prg_return_false: } { \prg_return_true: }
3296   \if_false: } \fi:
3297 }
3298 \cs_generate_variant:Nn \tl_if_in:nnT { V , o , no }
3299 \cs_generate_variant:Nn \tl_if_in:nnF { V , o , no }
3300 \cs_generate_variant:Nn \tl_if_in:nnTF { V , o , no }

```

(End definition for `\tl_if_in:nTF`. This function is documented on page 41.)

`\tl_if_novalue:nTF` Tests for -NoValue-: this is similar to `\tl_if_in:nn` but set up to be expandable and `__tl_if_novalue:w` to check the value exactly. The question mark prevents the auxiliary from losing braces.

```

3301 \use:x
3302 {
3303   \prg_new_conditional:Npnn \exp_not:N \tl_if_novalue:n ##1
3304   { T , F , TF }
3305   {
3306     \exp_not:N \str_if_eq:onTF
3307     {
3308       \exp_not:N \__tl_if_novalue:w ? ##1 { }
3309       \c_novalue_tl
3310     }
3311     { ? { } \c_novalue_tl }
3312     { \exp_not:N \prg_return_true: }
3313     { \exp_not:N \prg_return_false: }
3314   }
3315   \cs_new:Npn \exp_not:N \__tl_if_novalue:w ##1 \c_novalue_tl
3316   {##1}
3317 }

```

(End definition for `\tl_if_novalue:nTF` and `__tl_if_novalue:w`. This function is documented on page 41.)

`\tl_if_single_p:N` Expand the token list and feed it to `\tl_if_single:n`.

`\tl_if_single:NTF`

```

3318 \cs_new:Npn \tl_if_single_p:N { \exp_args:No \tl_if_single_p:n }
3319 \cs_new:Npn \tl_if_single:NT { \exp_args:No \tl_if_single:nT }
3320 \cs_new:Npn \tl_if_single:NF { \exp_args:No \tl_if_single:nF }
3321 \cs_new:Npn \tl_if_single:NTF { \exp_args:No \tl_if_single:nTF }

```

(End definition for `\tl_if_single:NTF`. This function is documented on page 42.)

`\tl_if_single_p:n` This test is similar to `\tl_if_empty:nTF`. Expanding `\use_none:nn #1 ??` once yields an empty result if #1 is blank, a single ? if #1 has a single item, and otherwise yields some tokens ending with ??. Then, `\tl_to_str:n` makes sure there are no odd category codes. `__tl_if_single_p:n` An earlier version would compare the result to a single ? using string comparison, but `__tl_if_single:nTF` the Lua call is slow in LuaTeX. Instead, `__tl_if_single:nnw` picks the second token in front of it. If #1 is empty, this token is the trailing ? and the catcode test yields `false`. If #1 has a single item, the token is ^ and the catcode test yields `true`. Otherwise, it is one of the characters resulting from `\tl_to_str:n`, and the catcode test yields `false`. Note that `\if_catcode:w` takes care of the expansions, and that `\tl_to_str:n` (the `\detokenize` primitive) actually expands tokens until finding a begin-group token.

```

3322 \prg_new_conditional:Npnn \tl_if_single:n #1 { p , T , F , TF }
3323   {
3324     \if_catcode:w ^ \exp_after:wN \__tl_if_single:nnw
3325       \tl_to_str:n \exp_after:wN { \use_none:nn #1 ?? } ^ ? \q_stop
3326     \prg_return_true:
3327   \else:
3328     \prg_return_false:
3329   \fi:
3330 }
3331 \cs_new:Npn \__tl_if_single:nnw #1#2#3 \q_stop {#2}

```

(End definition for `\tl_if_single:nTF` and `__tl_if_single:nTF`. This function is documented on page 42.)

`\tl_case:Nn` The aim here is to allow the case statement to be evaluated using a known number of expansion steps (two), and without needing to use an explicit “end of recursion” marker. `\tl_case:cn` That is achieved by using the test input as the final case, as this is always true. The `\tl_case:NnTF` trick is then to tidy up the output such that the appropriate case code plus either the `\tl_case:cnTF` true or false branch code is inserted. `__tl_case:nnTF`

```

\__tl_case:Nw
\__prg_case_end:nw
\__tl_case_end:nw
3332 \cs_new:Npn \tl_case:Nn #1#2
3333   {
3334     \exp:w
3335     \__tl_case:NnTF #1 {#2} { } { }
3336   }
3337 \cs_new:Npn \tl_case:NnT #1#2#3
3338   {
3339     \exp:w
3340     \__tl_case:NnTF #1 {#2} {#3} { }
3341   }
3342 \cs_new:Npn \tl_case:NnF #1#2#3
3343   {
3344     \exp:w
3345     \__tl_case:NnTF #1 {#2} { } {#3}
3346   }
3347 \cs_new:Npn \tl_case:NnTF #1#2
3348   {
3349     \exp:w
3350     \__tl_case:NnTF #1 {#2}
3351   }
3352 \cs_new:Npn \__tl_case:NnTF #1#2#3#4
3353   { \__tl_case:Nw #1 #2 #1 { } \q_mark {#3} \q_mark {#4} \q_stop }

```

```

3354 \cs_new:Npn \__tl_case:Nw #1#2#3
3355 {
3356   \tl_if_eq:NNTF #1 #2
3357   { \__tl_case_end:nw {#3} }
3358   { \__tl_case:Nw #1 }
3359 }
3360 \cs_generate_variant:Nn \tl_case:Nn { c }
3361 \cs_generate_variant:Nn \tl_case:NnT { c }
3362 \cs_generate_variant:Nn \tl_case:NnF { c }
3363 \cs_generate_variant:Nn \tl_case:NnTF { c }

```

To tidy up the recursion, there are two outcomes. If there was a hit to one of the cases searched for, then #1 is the code to insert, #2 is the *next* case to check on and #3 is all of the rest of the cases code. That means that #4 is the **true** branch code, and #5 tidies up the spare \q_mark and the **false** branch. On the other hand, if none of the cases matched then we arrive here using the “termination” case of comparing the search with itself. That means that #1 is empty, #2 is the first \q_mark and so #4 is the **false** code (the **true** code is mopped up by #3).

```

3364 \cs_new:Npn \__prg_case_end:nw #1#2#3 \q_mark #4#5 \q_stop
3365 { \exp_end: #1 #4 }
3366 \cs_new_eq:NN \__tl_case_end:nw \__prg_case_end:nw

```

(End definition for \tl_case:NnTF and others. This function is documented on page 42.)

5.7 Mapping to token lists

\tl_map_function:nN Expandable loop macro for token lists. These have the advantage of not needing to test if the argument is empty, because if it is, the stop marker is read immediately and the loop terminated.

```

\__tl_map_function:Nn
3367 \cs_new:Npn \tl_map_function:nN #1#2
3368 {
3369   \__tl_map_function:Nn #2 #1
3370   \q_recursion_tail
3371   \__prg_break_point:Nn \tl_map_break: { }
3372 }
3373 \cs_new:Npn \tl_map_function:NN
3374 { \exp_args:No \tl_map_function:nN }
3375 \cs_new:Npn \__tl_map_function:Nn #1#2
3376 {
3377   \__quark_if_recursion_tail_break:nN {#2} \tl_map_break:
3378   #1 {#2} \__tl_map_function:Nn #1
3379 }
3380 \cs_generate_variant:Nn \tl_map_function:NN { c }

```

(End definition for \tl_map_function:nN, \tl_map_function:NN, and __tl_map_function:Nn. These functions are documented on page 42.)

\tl_map_inline:nn The inline functions are straight forward by now. We use a little trick with the counter **\g__prg_map_int** to make them nestable. We can also make use of **__tl_map_function:Nn** from before.

```

3381 \cs_new_protected:Npn \tl_map_inline:nn #1#2
3382 {
3383   \int_gincr:N \g__prg_map_int
3384   \cs_gset_protected:cpn

```



```

3385     { __prg_map_ \int_use:N \g__prg_map_int :w } ##1 {#2}
3386 \exp_args:Nc \__tl_map_function:Nn
3387     { __prg_map_ \int_use:N \g__prg_map_int :w }
3388     #1 \q_recursion_tail
3389     \__prg_break_point:Nn \tl_map_break: { \int_gdecr:N \g__prg_map_int }
3390   }
3391 \cs_new_protected:Npn \tl_map_inline:Nn
3392   { \exp_args:No \tl_map_inline:nn }
3393 \cs_generate_variant:Nn \tl_map_inline:Nn { c }

```

(End definition for `\tl_map_inline:nn` and `\tl_map_inline:Nn`. These functions are documented on page 43.)

`\tl_map_variable:nNn` `\tl_map_variable:nNn` *<token list>* *<temp>* *<action>* assigns *<temp>* to each element and executes *<action>*.

```

\__tl_map_variable:Nnn
3394 \cs_new_protected:Npn \tl_map_variable:nNn #1#2#3
3395   {
3396     \__tl_map_variable:Nnn #2 {#3} #1
3397     \q_recursion_tail
3398     \__prg_break_point:Nn \tl_map_break: { }
3399   }
3400 \cs_new_protected:Npn \tl_map_variable:NNn
3401   { \exp_args:No \tl_map_variable:nNn }
3402 \cs_new_protected:Npn \__tl_map_variable:Nnn #1#2#3
3403   {
3404     \tl_set:Nn #1 {#3}
3405     \__quark_if_recursion_tail_break:NN #1 \tl_map_break:
3406     \use:n {#2}
3407     \__tl_map_variable:Nnn #1 {#2}
3408   }
3409 \cs_generate_variant:Nn \tl_map_variable:NNn { c }

```

(End definition for `\tl_map_variable:nNn`, `\tl_map_variable:NNn`, and `__tl_map_variable:Nnn`. These functions are documented on page 43.)

`\tl_map_break:` The break statements use the general `__prg_map_break:Nn`.

```

\__tl_map_break:Nn
3410 \cs_new:Npn \tl_map_break:
3411   { \__prg_map_break:Nn \tl_map_break: { } }
3412 \cs_new:Npn \tl_map_break:n
3413   { \__prg_map_break:Nn \tl_map_break: }

```

(End definition for `\tl_map_break:` and `\tl_map_break:n`. These functions are documented on page 43.)

5.8 Using token lists

`\tl_to_str:n` Another name for a primitive: defined in `l3basics`.

```

\__tl_to_str:N
3414 \cs_generate_variant:Nn \tl_to_str:n { V }

```

(End definition for `\tl_to_str:n`. This function is documented on page 44.)

`\tl_to_str:N` These functions return the replacement text of a token list as a string.

```

\__tl_to_str:c
3415 \cs_new:Npn \tl_to_str:N #1 { \etex_detokenize:D \exp_after:wN {#1} }
3416 \cs_generate_variant:Nn \tl_to_str:N { c }

```

(End definition for `\tl_to_str:N`. This function is documented on page 44.)

`\tl_use:N` Token lists which are simply not defined give a clear T_EX error here. No such luck for ones equal to `\scan_stop`: so instead a test is made and if there is an issue an error is forced.

```

3417 \cs_new:Npn \tl_use:N #1
3418 {
3419   \tl_if_exist:NTF #1 {#1}
3420   {
3421     \_msg_kernel_expandable_error:nnn
3422     { kernel } { bad-variable } {#1}
3423   }
3424 }
3425 \cs_generate_variant:Nn \tl_use:N { c }

```

(End definition for `\tl_use:N`. This function is documented on page 45.)

5.9 Working with the contents of token lists

`\tl_count:n` Count number of elements within a token list or token list variable. Brace groups within the list are read as a single element. Spaces are ignored. `_tl_count:n` grabs the element and replaces it by +1. The 0 ensures that it works on an empty list.

```

3426 \cs_new:Npn \tl_count:n #1
3427 {
3428   \int_eval:n
3429   { 0 \tl_map_function:nN {#1} \_tl_count:n }
3430 }
3431 \cs_new:Npn \tl_count:N #1
3432 {
3433   \int_eval:n
3434   { 0 \tl_map_function:NN #1 \_tl_count:n }
3435 }
3436 \cs_new:Npn \_tl_count:n #1 { + 1 }
3437 \cs_generate_variant:Nn \tl_count:n { V , o }
3438 \cs_generate_variant:Nn \tl_count:N { c }

```

(End definition for `\tl_count:n`, `\tl_count:N`, and `_tl_count:n`. These functions are documented on page 45.)

`\tl_reverse_items:n` Reversal of a token list is done by taking one item at a time and putting it after `\q_stop`.

```

3439 \cs_new:Npn \tl_reverse_items:n #1
3440 {
3441   \_tl_reverse_items:nwNwn #1 ?
3442   \q_mark \_tl_reverse_items:nwNwn
3443   \q_mark \_tl_reverse_items:wn
3444   \q_stop { }
3445 }
3446 \cs_new:Npn \_tl_reverse_items:nwNwn #1 #2 \q_mark #3 #4 \q_stop #5
3447 {
3448   #3 #2
3449   \q_mark \_tl_reverse_items:nwNwn
3450   \q_mark \_tl_reverse_items:wn
3451   \q_stop { {#1} #5 }
3452 }

```

```

3453 \cs_new:Npn \__tl_reverse_items:wn #1 \q_stop #2
3454 { \exp_not:o { \use_none:nn #2 } }

```

(End definition for `\tl_reverse_items:n`, `__tl_reverse_items:nwNwn`, and `__tl_reverse_items:wn`. This function is documented on page 45.)

`\tl_trim_spaces:n` Trimming spaces from around the input is deferred to an internal function whose first argument is the token list to trim, augmented by an initial `\q_mark`, and whose second argument is a *continuation*, which receives as a braced argument `\use_none:n \q_mark` *trimmed token list*. In the case at hand, we take `\exp_not:o` as our continuation, so that space trimming behaves correctly within an x-type expansion.

```

\tl_trim_spaces:o
\tl_trim_spaces:N
\tl_trim_spaces:c
\tl_gtrim_spaces:N
\tl_gtrim_spaces:c
3455 \cs_new:Npn \tl_trim_spaces:n #1
3456 { \__tl_trim_spaces:nn { \q_mark #1 } \exp_not:o }
3457 \cs_generate_variant:Nn \tl_trim_spaces:n { o }
3458 \cs_new_protected:Npn \tl_trim_spaces:N #1
3459 { \tl_set:Nx #1 { \exp_args:No \tl_trim_spaces:n {#1} } }
3460 \cs_new_protected:Npn \tl_gtrim_spaces:N #1
3461 { \tl_gset:Nx #1 { \exp_args:No \tl_trim_spaces:n {#1} } }
3462 \cs_generate_variant:Nn \tl_trim_spaces:N { c }
3463 \cs_generate_variant:Nn \tl_gtrim_spaces:N { c }

```

(End definition for `\tl_trim_spaces:n`, `\tl_trim_spaces:N`, and `\tl_gtrim_spaces:N`. These functions are documented on page 46.)

`__tl_trim_spaces:nn` Trimming spaces from around the input is done using delimited arguments and quarks, and to get spaces at odd places in the definitions, we nest those in `__tl_tmp:w`, which then receives a single space as its argument: `#1` is `␣`. Removing leading spaces is done with `__tl_trim_spaces_auxi:w`, which loops until `\q_mark␣` matches the end of the token list: then `##1` is the token list and `##3` is `__tl_trim_spaces_auxii:w`. This hands the relevant tokens to the loop `__tl_trim_spaces_auxiii:w`, responsible for trimming trailing spaces. The end is reached when `␣ \q_nil` matches the one present in the definition of `\tl_trim_spaces:n`. Then `__tl_trim_spaces_auxiv:w` puts the token list into a group, with `\use_none:n` placed there to gobble a lingering `\q_mark`, and feeds this to the *continuation*.

```

3464 \cs_set:Npn \__tl_tmp:w #1
3465 {
3466   \cs_new:Npn \__tl_trim_spaces:nn ##1
3467   {
3468     \__tl_trim_spaces_auxi:w
3469     ##1
3470     \q_nil
3471     \q_mark #1 { }
3472     \q_mark \__tl_trim_spaces_auxii:w
3473     \__tl_trim_spaces_auxiii:w
3474     #1 \q_nil
3475     \__tl_trim_spaces_auxiv:w
3476     \q_stop
3477   }
3478   \cs_new:Npn \__tl_trim_spaces_auxi:w ##1 \q_mark #1 ##2 \q_mark ##3
3479   {
3480     ##3
3481     \__tl_trim_spaces_auxi:w
3482     \q_mark
3483     ##2

```

```

3484     \q_mark #1 {##1}
3485   }
3486   \cs_new:Npn \__tl_trim_spaces_auxii:w
3487     \__tl_trim_spaces_auxi:w \q_mark \q_mark ##1
3488   {
3489     \__tl_trim_spaces_auxiii:w
3490     ##1
3491   }
3492   \cs_new:Npn \__tl_trim_spaces_auxiii:w ##1 #1 \q_nil ##2
3493   {
3494     ##2
3495     ##1 \q_nil
3496     \__tl_trim_spaces_auxiii:w
3497   }
3498   \cs_new:Npn \__tl_trim_spaces_auxiv:w ##1 \q_nil ##2 \q_stop ##3
3499   { ##3 { \use_none:n ##1 } }
3500 }
3501 \__tl_tmp:w { ~ }

```

(End definition for `__tl_trim_spaces:nn` and others.)

`\tl_sort:Nn` Implemented in `l3sort`.

`\tl_sort:cn`

`\tl_gsort:Nn` (End definition for `\tl_sort:Nn`, `\tl_gsort:Nn`, and `\tl_sort:nN`. These functions are documented on page 46.)

`\tl_gsort:cn`

`\tl_sort:nN`

5.10 Token by token changes

`\q__tl_act_mark`

`\q__tl_act_stop`

The `\tl_act` functions may be applied to any token list. Hence, we use two private quarks, to allow any token, even quarks, in the token list. Only `\q__tl_act_mark` and `\q__tl_act_stop` may not appear in the token lists manipulated by `__tl_act:NNNnn` functions. The quarks are effectively defined in `l3quark`.

(End definition for `\q__tl_act_mark` and `\q__tl_act_stop`.)

`__tl_act:NNNnn`

`__tl_act_output:n`

`__tl_act_reverse_output:n`

`__tl_act_loop:w`

`__tl_act_normal:NwnNNN`

`__tl_act_group:nwnNNN`

`__tl_act_space:wwnNNN`

`__tl_act_end:w`

To help control the expansion, `__tl_act:NNNnn` should always be preceded by `\exp:w` and ends by producing `\exp_end:` once the result has been obtained. Then loop over tokens, groups, and spaces in #5. The marker `\q__tl_act_mark` is used both to avoid losing outer braces and to detect the end of the token list more easily. The result is stored as an argument for the dummy function `__tl_act_result:n`.

```

3502 \cs_new:Npn \__tl_act:NNNnn #1#2#3#4#5
3503 {
3504   \group_align_safe_begin:
3505   \__tl_act_loop:w #5 \q__tl_act_mark \q__tl_act_stop
3506   {#4} #1 #2 #3
3507   \__tl_act_result:n { }
3508 }

```

In the loop, we check how the token list begins and act accordingly. In the “normal” case, we may have reached `\q__tl_act_mark`, the end of the list. Then leave `\exp_end:` and the result in the input stream, to terminate the expansion of `\exp:w`. Otherwise, apply the relevant function to the “arguments”, #3 and to the head of the token list. Then repeat the loop. The scheme is the same if the token list starts with a group or with a space. Some extra work is needed to make `__tl_act_space:wwnNNN` gobble the space.

```

3509 \cs_new:Npn \__tl_act_loop:w #1 \q__tl_act_stop
3510 {
3511   \tl_if_head_is_N_type:nTF {#1}
3512   { \__tl_act_normal:NwnNNN }
3513   {
3514     \tl_if_head_is_group:nTF {#1}
3515     { \__tl_act_group:nwnNNN }
3516     { \__tl_act_space:wnnNNN }
3517   }
3518   #1 \q__tl_act_stop
3519 }
3520 \cs_new:Npn \__tl_act_normal:NwnNNN #1 #2 \q__tl_act_stop #3#4
3521 {
3522   \if_meaning:w \q__tl_act_mark #1
3523   \exp_after:wN \__tl_act_end:wn
3524   \fi:
3525   #4 {#3} #1
3526   \__tl_act_loop:w #2 \q__tl_act_stop
3527   {#3} #4
3528 }
3529 \cs_new:Npn \__tl_act_end:wn #1 \__tl_act_result:n #2
3530 { \group_align_safe_end: \exp_end: #2 }
3531 \cs_new:Npn \__tl_act_group:nwnNNN #1 #2 \q__tl_act_stop #3#4#5
3532 {
3533   #5 {#3} {#1}
3534   \__tl_act_loop:w #2 \q__tl_act_stop
3535   {#3} #4 #5
3536 }
3537 \exp_last_unbraced:NNo
3538 \cs_new:Npn \__tl_act_space:wnnNNN \c_space_tl #1 \q__tl_act_stop #2#3#4#5
3539 {
3540   #5 {#2}
3541   \__tl_act_loop:w #1 \q__tl_act_stop
3542   {#2} #3 #4 #5
3543 }

```

Typically, the output is done to the right of what was already output, using `__tl_act_output:n`, but for the `__tl_act_reverse` functions, it should be done to the left.

```

3544 \cs_new:Npn \__tl_act_output:n #1 #2 \__tl_act_result:n #3
3545 { #2 \__tl_act_result:n { #3 #1 } }
3546 \cs_new:Npn \__tl_act_reverse_output:n #1 #2 \__tl_act_result:n #3
3547 { #2 \__tl_act_result:n { #1 #3 } }

```

(End definition for `__tl_act:NNNnn` and others.)

`\tl_reverse:n` The goal here is to reverse without losing spaces nor braces. This is done using the
`\tl_reverse:o` general internal function `__tl_act:NNNnn`. Spaces and “normal” tokens are output on
`\tl_reverse:V` the left of the current output. Grouped tokens are output to the left but without any
`__tl_reverse_normal:nN` reversal within the group. All of the internal functions here drop one argument: this is
`__tl_reverse_group_preserve:nn` needed by `__tl_act:NNNnn` when changing case (to record which direction the change
`__tl_reverse_space:n` is in), but not when reversing the tokens.

```

3548 \cs_new:Npn \tl_reverse:n #1
3549 {
3550   \etex_unexpanded:D \exp_after:wN

```

```

3551     {
3552       \exp:w
3553       \__tl_act:NNNnn
3554       \__tl_reverse_normal:nN
3555       \__tl_reverse_group_preserve:nn
3556       \__tl_reverse_space:n
3557       { }
3558       {#1}
3559     }
3560   }
3561   \cs_generate_variant:Nn \tl_reverse:n { o , V }
3562   \cs_new:Npn \__tl_reverse_normal:nN #1#2
3563     { \__tl_act_reverse_output:n {#2} }
3564   \cs_new:Npn \__tl_reverse_group_preserve:nn #1#2
3565     { \__tl_act_reverse_output:n { {#2} } }
3566   \cs_new:Npn \__tl_reverse_space:n #1
3567     { \__tl_act_reverse_output:n { ~ } }

```

(End definition for `\tl_reverse:n` and others. This function is documented on page 45.)

`\tl_reverse:N` This reverses the list, leaving `\exp_stop_f:` in front, which stops the `f`-expansion.

```

\tl_reverse:c 3568 \cs_new_protected:Npn \tl_reverse:N #1
\tl_greverse:N 3569   { \tl_set:Nx #1 { \exp_args:No \tl_reverse:n { #1 } } }
\tl_greverse:c 3570 \cs_new_protected:Npn \tl_greverse:N #1
                 3571   { \tl_gset:Nx #1 { \exp_args:No \tl_reverse:n { #1 } } }
                 3572 \cs_generate_variant:Nn \tl_reverse:N { c }
                 3573 \cs_generate_variant:Nn \tl_greverse:N { c }

```

(End definition for `\tl_reverse:N` and `\tl_greverse:N`. These functions are documented on page 45.)

5.11 The first token from a token list

`\tl_head:N` Finding the head of a token list expandably always strips braces, which is fine as this is consistent with for example mapping to a list. The empty brace groups in `\tl_head:n` ensure that a blank argument gives an empty result. The result is returned within the `\unexpanded` primitive. The approach here is to use `\if_false:` to allow us to use `}` as the closing delimiter: this is the only safe choice, as any other token would not be able to parse it's own code. Using a marker, we can see if what we are grabbing is exactly the marker, or there is anything else to deal with. If there is, there is a loop. If not, tidy up and leave the item in the output stream. More detail in <http://tex.stackexchange.com/a/70168>.

```

\tl_head:w 3574 \cs_new:Npn \tl_head:n #1
\tl_head:N 3575   {
\tl_head:V 3576     \etex_unexpanded:D
\tl_head:v 3577     \if_false: { \fi: \__tl_head_auxi:nw #1 { } \q_stop }
\tl_head:f 3578   }
\__tl_head_auxi:nw 3579 \cs_new:Npn \__tl_head_auxi:nw #1#2 \q_stop
\__tl_head_auxii:n 3580   {
\tl_head:w 3581     \exp_after:wN \__tl_head_auxii:n \exp_after:wN {
\tl_head:N 3582     \if_false: } \fi: {#1}
\tl_head:V 3583   }
\tl_head:v 3584 \cs_new:Npn \__tl_head_auxii:n #1
\tl_head:f 3585   {

```

```

3586 \exp_after:wN \if_meaning:w \exp_after:wN \q_nil
3587 \tl_to_str:n \exp_after:wN { \use_none:n #1 } \q_nil
3588 \exp_after:wN \use_i:nn
3589 \else:
3590 \exp_after:wN \use_ii:nn
3591 \fi:
3592 {#1}
3593 { \if_false: { \fi: \__tl_head_auxi:nw #1 } }
3594 }
3595 \cs_generate_variant:Nn \tl_head:n { V , v , f }
3596 \cs_new:Npn \tl_head:w #1#2 \q_stop {#1}
3597 \cs_new:Npn \tl_head:N { \exp_args:No \tl_head:n }

```

To correctly leave the tail of a token list, it's important *not* to absorb any of the tail part as an argument. For example, the simple definition

```

\cs_new:Npn \tl_tail:n #1 { \tl_tail:w #1 \q_stop }
\cs_new:Npn \tl_tail:w #1#2 \q_stop

```

would give the wrong result for `\tl_tail:n { a { bc } }` (the braces would be stripped). Thus the only safe way to proceed is to first check that there is an item to grab (*i.e.* that the argument is not blank) and assuming there is to dispose of the first item. As with `\tl_head:n`, the result is protected from further expansion by `\unexpanded`. While we could optimise the test here, this would leave some tokens “banned” in the input, which we do not have with this definition.

```

3598 \cs_new:Npn \tl_tail:n #1
3599 {
3600 \etex_unexpanded:D
3601 \tl_if_blank:nTF {#1}
3602 { { } }
3603 { \exp_after:wN { \use_none:n #1 } }
3604 }
3605 \cs_generate_variant:Nn \tl_tail:n { V , v , f }
3606 \cs_new:Npn \tl_tail:N { \exp_args:No \tl_tail:n }

```

(End definition for `\tl_head:N` and others. These functions are documented on page 47.)

<pre> \tl_if_head_eq_meaning_p:nN \tl_if_head_eq_meaning:nNTF \tl_if_head_eq_charcode_p:nN \tl_if_head_eq_charcode:nNTF \tl_if_head_eq_charcode_p:fN \tl_if_head_eq_charcode:fNTF \tl_if_head_eq_catcode_p:nN \tl_if_head_eq_catcode:nNTF </pre>	<p>Accessing the first token of a token list is tricky in three cases: when it has category code 1 (begin-group token), when it is an explicit space, with category code 10 and character code 32, or when the token list is empty (obviously).</p> <p>Forgetting temporarily about this issue we would use the following test in <code>\tl_if_head_eq_charcode:nN</code>. Here, <code>\tl_head:w</code> yields the first token of the token list, then passed to <code>\exp_not:N</code>.</p> <pre> \if_charcode:w \exp_after:wN \exp_not:N \tl_head:w #1 \q_nil \q_stop \exp_not:N #2 </pre>
--	--

The two first special cases are detected by testing if the token list starts with an N-type token (the extra ? sends empty token lists to the `true` branch of this test). In those cases, the first token is a character, and since we only care about its character code, we can use `\str_head:n` to access it (this works even if it is a space character). An empty argument results in `\tl_head:w` leaving two tokens: ? which is taken in the `\if_charcode:w` test,

and `\use_none:nn`, which ensures that `\prg_return_false:` is returned regardless of whether the charcode test was true or false.

```

3607 \prg_new_conditional:Npnn \tl_if_head_eq_charcode:nN #1#2 { p , T , F , TF }
3608 {
3609   \if_charcode:w
3610     \exp_not:N #2
3611     \tl_if_head_is_N_type:nTF { #1 ? }
3612     {
3613       \exp_after:wN \exp_not:N
3614       \tl_head:w #1 { ? \use_none:nn } \q_stop
3615     }
3616     { \str_head:n {#1} }
3617     \prg_return_true:
3618   \else:
3619     \prg_return_false:
3620   \fi:
3621 }
3622 \cs_generate_variant:Nn \tl_if_head_eq_charcode_p:nN { f }
3623 \cs_generate_variant:Nn \tl_if_head_eq_charcode:nNTF { f }
3624 \cs_generate_variant:Nn \tl_if_head_eq_charcode:nNT { f }
3625 \cs_generate_variant:Nn \tl_if_head_eq_charcode:nNF { f }

```

For `\tl_if_head_eq_catcode:nN`, again we detect special cases with a `\tl_if_head_is_N_type:n`. Then we need to test if the first token is a begin-group token or an explicit space token, and produce the relevant token, either `\c_group_begin_token` or `\c_space_token`. Again, for an empty argument, a hack is used, removing `\prg_return_true:` and `\else:` with `\use_none:nn` in case the catcode test with the (arbitrarily chosen) `?` is true.

```

3626 \prg_new_conditional:Npnn \tl_if_head_eq_catcode:nN #1 #2 { p , T , F , TF }
3627 {
3628   \if_catcode:w
3629     \exp_not:N #2
3630     \tl_if_head_is_N_type:nTF { #1 ? }
3631     {
3632       \exp_after:wN \exp_not:N
3633       \tl_head:w #1 { ? \use_none:nn } \q_stop
3634     }
3635     {
3636       \tl_if_head_is_group:nTF {#1}
3637       { \c_group_begin_token }
3638       { \c_space_token }
3639     }
3640     \prg_return_true:
3641   \else:
3642     \prg_return_false:
3643   \fi:
3644 }

```

For `\tl_if_head_eq_meaning:nN`, again, detect special cases. In the normal case, use `\tl_head:w`, with no `\exp_not:N` this time, since `\if_meaning:w` causes no expansion. With an empty argument, the test is true, and `\use_none:nnn` removes `#2` and the usual `\prg_return_true:` and `\else:`. In the special cases, we know that the first token is a character, hence `\if_charcode:w` and `\if_catcode:w` together are enough. We combine

them in some order, hopefully faster than the reverse. Tests are not nested because the arguments may contain unmatched primitive conditionals.

```

3645 \prg_new_conditional:Npnn \tl_if_head_eq_meaning:nN #1#2 { p , T , F , TF }
3646 {
3647   \tl_if_head_is_N_type:nTF { #1 ? }
3648   { \__tl_if_head_eq_meaning_normal:nN }
3649   { \__tl_if_head_eq_meaning_special:nN }
3650   {#1} #2
3651 }
3652 \cs_new:Npn \__tl_if_head_eq_meaning_normal:nN #1 #2
3653 {
3654   \exp_after:wN \if_meaning:w
3655   \tl_head:w #1 { ?? \use_none:nnn } \q_stop #2
3656   \prg_return_true:
3657   \else:
3658   \prg_return_false:
3659   \fi:
3660 }
3661 \cs_new:Npn \__tl_if_head_eq_meaning_special:nN #1 #2
3662 {
3663   \if_charcode:w \str_head:n {#1} \exp_not:N #2
3664   \exp_after:wN \use:n
3665   \else:
3666   \prg_return_false:
3667   \exp_after:wN \use_none:n
3668   \fi:
3669   {
3670     \if_catcode:w \exp_not:N #2
3671     \tl_if_head_is_group:nTF {#1}
3672     { \c_group_begin_token }
3673     { \c_space_token }
3674     \prg_return_true:
3675     \else:
3676     \prg_return_false:
3677     \fi:
3678   }
3679 }

```

(End definition for `\tl_if_head_eq_meaning:nNTF` and others. These functions are documented on page 48.)

`\tl_if_head_is_N_type_p:n`
`\tl_if_head_is_N_type:nTF`
`__tl_if_head_is_N_type:w`

A token list can be empty, can start with an explicit space character (catcode 10 and charcode 32), can start with a begin-group token (catcode 1), or start with an N-type argument. In the first two cases, the line involving `__tl_if_head_is_N_type:w` produces `~` (and otherwise nothing). In the third case (begin-group token), the lines involving `\exp_after:wN` produce a single closing brace. The category code test is thus true exactly in the fourth case, which is what we want. One cannot optimize by moving one of the `*` to the beginning: if `#1` contains primitive conditionals, all of its occurrences must be dealt with before the `\if_catcode:w` tries to skip the `true` branch of the conditional.

```

3680 \prg_new_conditional:Npnn \tl_if_head_is_N_type:n #1 { p , T , F , TF }
3681 {
3682   \if_catcode:w
3683   \if_false: { \fi: \__tl_if_head_is_N_type:w ? #1 ~ }

```

```

3684         \exp_after:wN \use_none:n
3685         \exp_after:wN { \exp_after:wN { \token_to_str:N #1 ? } }
3686         * *
3687         \prg_return_true:
3688     \else:
3689         \prg_return_false:
3690 \fi:
3691 }
3692 \cs_new:Npn \__tl_if_head_is_N_type:w #1 ~
3693 {
3694     \tl_if_empty:oTF { \use_none:n #1 } { ^ } { }
3695     \exp_after:wN \use_none:n \exp_after:wN { \if_false: } \fi:
3696 }

```

(End definition for `\tl_if_head_is_N_type:nTF` and `__tl_if_head_is_N_type:w`. This function is documented on page 48.)

`\tl_if_head_is_group_p:n` Pass the first token of #1 through `\token_to_str:N`, then check for the brace balance.
`\tl_if_head_is_group:nTF` The extra ? caters for an empty argument.⁷

```

3697 \prg_new_conditional:Npnn \tl_if_head_is_group:n #1 { p , T , F , TF }
3698 {
3699     \if_catcode:w
3700         \exp_after:wN \use_none:n
3701         \exp_after:wN { \exp_after:wN { \token_to_str:N #1 ? } }
3702         * *
3703         \prg_return_false:
3704     \else:
3705         \prg_return_true:
3706 \fi:
3707 }

```

(End definition for `\tl_if_head_is_group:nTF`. This function is documented on page 48.)

`\tl_if_head_is_space_p:n` The auxiliary's argument is all that is before the first explicit space in `?#1?~`. If that
`\tl_if_head_is_space:nTF` is a single ? the test yields `true`. Otherwise, that is more than one token, and the
`__tl_if_head_is_space:w` test yields `false`. The work is done within braces (with an `\if_false: { \fi: ... }` construction) both to hide potential alignment tab characters from \TeX in a table, and to allow for removing what remains of the token list after its first space. The `\exp:w` and `\exp_end:` ensure that the result of a single step of expansion directly yields a balanced token list (no trailing closing brace).

```

3708 \prg_new_conditional:Npnn \tl_if_head_is_space:n #1 { p , T , F , TF }
3709 {
3710     \exp:w \if_false: { \fi:
3711         \__tl_if_head_is_space:w ? #1 ? ~ }
3712 }
3713 \cs_new:Npn \__tl_if_head_is_space:w #1 ~
3714 {
3715     \tl_if_empty:oTF { \use_none:n #1 }
3716     { \exp_after:wN \exp_end: \exp_after:wN \prg_return_true: }
3717     { \exp_after:wN \exp_end: \exp_after:wN \prg_return_false: }
3718     \exp_after:wN \use_none:n \exp_after:wN { \if_false: } \fi:

```

⁷Bruno: this could be made faster, but we don't: if we hope to ever have an e-type argument, we need all brace "tricks" to happen in one step of expansion, keeping the token list brace balanced at all times.

```
3719 }
```

(End definition for `\tl_if_head_is_space:nTF` and `__tl_if_head_is_space:w`. This function is documented on page 48.)

5.12 Using a single item

```
\tl_item:nn The idea here is to find the offset of the item from the left, then use a loop to grab
\tl_item:Nn the correct item. If the resulting offset is too large, then \quark_if_recursion_tail_
\tl_item:cn stop:n terminates the loop, and returns nothing at all.
\__tl_item_aux:nn 3720 \cs_new:Npn \tl_item:nn #1#2
\__tl_item:nn 3721 {
3722     \exp_args:Nf \__tl_item:nn
3723     { \exp_args:Nf \__tl_item_aux:nn { \int_eval:n {#2} } {#1} }
3724     #1
3725     \q_recursion_tail
3726     \__prg_break_point:
3727 }
3728 \cs_new:Npn \__tl_item_aux:nn #1#2
3729 {
3730     \int_compare:nNnTF {#1} < 0
3731     { \int_eval:n { \tl_count:n {#2} + 1 + #1 } }
3732     {#1}
3733 }
3734 \cs_new:Npn \__tl_item:nn #1#2
3735 {
3736     \__quark_if_recursion_tail_break:nN {#2} \__prg_break:
3737     \int_compare:nNnTF {#1} = 1
3738     { \__prg_break:n { \exp_not:n {#2} } }
3739     { \exp_args:Nf \__tl_item:nn { \int_eval:n { #1 - 1 } } }
3740 }
3741 \cs_new:Npn \tl_item:Nn { \exp_args:No \tl_item:nn }
3742 \cs_generate_variant:Nn \tl_item:Nn { c }
```

(End definition for `\tl_item:nn` and others. These functions are documented on page 49.)

5.13 Viewing token lists

```
\tl_show:N Showing token list variables is done after checking that the variable is defined (see \__-
\tl_show:c kernel_register_show:N).
\tl_log:N 3743 \cs_new_protected:Npn \tl_show:N { \__tl_show:NN \tl_show:n }
\tl_log:c 3744 \cs_generate_variant:Nn \tl_show:N { c }
\__tl_show:NN 3745 \cs_new_protected:Npn \tl_log:N { \__tl_show:NN \tl_log:n }
3746 \cs_generate_variant:Nn \tl_log:N { c }
3747 \cs_new_protected:Npn \__tl_show:NN #1#2
3748 {
3749     \__kernel_check_defined:NT #2
3750     { \exp_args:Nx #1 { \token_to_str:N #2 = \exp_not:o {#2} } }
3751 }
```

(End definition for `\tl_show:N`, `\tl_log:N`, and `__tl_show:NN`. These functions are documented on page 49.)

\tl_show:n Many `show` functions are based on `\tl_show:n`. The argument of `\tl_show:n` is line-wrapped using `\iow_wrap:nnnN` but with a leading `>~` and trailing period, both removed before passing the wrapped text to the `\showtokens` primitive. This primitive shows the result with a leading `>~` and trailing period.

The token list `\l__tl_internal_a_tl` containing the result of all these manipulations is displayed to the terminal using `\etex_showtokens:D` and an odd `\exp_after:wN` which expand the closing brace to improve the output slightly. The calls to `__iow_with:Nnn` ensure that the `\newlinechar` is set to 10 so that the `\iow_newline:` inserted by the line-wrapping code are correctly recognized by T_EX, and that `\errorcontextlines` is `-1` to avoid printing irrelevant context.

```

3752 \cs_new_protected:Npn \tl_show:n #1
3753 { \iow_wrap:nnnN { >~ \tl_to_str:n {#1} . } { } { } \__tl_show:n }
3754 \cs_new_protected:Npn \__tl_show:n #1
3755 {
3756   \tl_set:Nf \l__tl_internal_a_tl { \__tl_show:w #1 \q_stop }
3757   \__iow_with:Nnn \tex_newlinechar:D { 10 }
3758   {
3759     \__iow_with:Nnn \tex_errorcontextlines:D { -1 }
3760     {
3761       \etex_showtokens:D \exp_after:wN \exp_after:wN \exp_after:wN
3762       { \exp_after:wN \l__tl_internal_a_tl }
3763     }
3764   }
3765 }
3766 \cs_new:Npn \__tl_show:w #1 > #2 . \q_stop {#2}

```

(End definition for `\tl_show:n`, `__tl_show:n`, and `__tl_show:w`. This function is documented on page 49.)

\tl_log:n Logging is much easier, simply line-wrap. The `>~` and trailing period is there to match the output of `\tl_show:n`.

```

3767 \cs_new_protected:Npn \tl_log:n #1
3768 { \iow_wrap:nnnN { > ~ \tl_to_str:n {#1} . } { } { } \iow_log:n }

```

(End definition for `\tl_log:n`. This function is documented on page 49.)

5.14 Scratch token lists

\g_tmpa_tl Global temporary token list variables. They are supposed to be set and used immediately, with no delay between the definition and the use because you can't count on other macros not to redefine them from under you.

```

3769 \tl_new:N \g_tmpa_tl
3770 \tl_new:N \g_tmpb_tl

```

(End definition for `\g_tmpa_tl` and `\g_tmpb_tl`. These variables are documented on page 50.)

\l_tmpa_tl These are local temporary token list variables. Be sure not to assume that the value you put into them will survive for long—see discussion above.

```

3771 \tl_new:N \l_tmpa_tl
3772 \tl_new:N \l_tmpb_tl

```

(End definition for `\l_tmpa_tl` and `\l_tmpb_tl`. These variables are documented on page 50.)

5.15 Deprecatd functions

`\tl_to_lowercase:n` For removal after 2017-12-31.
`\tl_to_uppercase:n`

```

3773 \__debug_deprecation:nnNNpn { 2017-12-31 } { \tex_lowercase:D }
3774 \cs_new_protected:Npn \tl_to_lowercase:n #1 { \tex_lowercase:D {#1} }
3775 \__debug_deprecation:nnNNpn { 2017-12-31 } { \tex_uppercase:D }
3776 \cs_new_protected:Npn \tl_to_uppercase:n #1 { \tex_uppercase:D {#1} }

(End definition for \tl_to_lowercase:n and \tl_to_uppercase:n.)

3777 </initex | package>

```

6 l3str implementation

```

3778 <*initex | package>
3779 <@@=str>

```

6.1 Creating and setting string variables

`\str_new:N` A string is simply a token list. The full mapping system isn't set up yet so do things by hand.
`\str_new:c`
`\str_use:N`
`\str_use:c`
`\str_clear:N`
`\str_clear:c`
`\str_gclear:N`
`\str_gclear:c`
`\str_clear_new:N`
`\str_clear_new:c`
`\str_gclear_new:N`
`\str_gclear_new:c`
`\str_set_eq:NN`
`\str_set_eq:cN`
`\str_set_eq:Nc`
`\str_set_eq:cc`
`\str_gset_eq:NN`
`\str_gset_eq:cN`
`\str_gset_eq:Nc`
`\str_gset_eq:cc`
`\str_concat:NNN`
`\str_concat:ccc`
`\str_gconcat:NNN`
`\str_gconcat:ccc`

```

3780 \group_begin:
3781 \cs_set_protected:Npn \__str_tmp:n #1
3782 {
3783   \tl_if_blank:nF {#1}
3784   {
3785     \cs_new_eq:cc { str_ #1 :N } { tl_ #1 :N }
3786     \exp_args:Nc \cs_generate_variant:Nn { str_ #1 :N } { c }
3787     \__str_tmp:n
3788   }
3789 }
3790 \__str_tmp:n
3791 { new }
3792 { use }
3793 { clear }
3794 { gclear }
3795 { clear_new }
3796 { gclear_new }
3797 { }
3798 \group_end:
3799 \cs_new_eq:NN \str_set_eq:NN \tl_set_eq:NN
3800 \cs_new_eq:NN \str_gset_eq:NN \tl_gset_eq:NN
3801 \cs_generate_variant:Nn \str_set_eq:NN { c , Nc , cc }
3802 \cs_generate_variant:Nn \str_gset_eq:NN { c , Nc , cc }
3803 \cs_new_eq:NN \str_concat:NNN \tl_concat:NNN
3804 \cs_new_eq:NN \str_gconcat:NNN \tl_gconcat:NNN
3805 \cs_generate_variant:Nn \str_concat:NNN { ccc }
3806 \cs_generate_variant:Nn \str_gconcat:NNN { ccc }

```

(End definition for `\str_new:N` and others. These functions are documented on page 51.)

`\str_set:Nn` Simply convert the token list inputs to *<strings>*.
`\str_set:Nx`
`\str_set:cn`
`\str_set:cx`
`\str_gset:Nn`
`\str_gset:Nx`
`\str_gset:cn`
`\str_gset:cx`
`\str_const:Nn`
`\str_const:Nx`
`\str_const:cn`
`\str_const:cx`
`\str_put_left:Nn`

```

3809     {
3810       \tl_if_blank:nF {#1}
3811       {
3812         \cs_new_protected:cpx { str_ #1 :Nn } ##1##2
3813         { \exp_not:c { tl_ #1 :Nx } ##1 { \exp_not:N \tl_to_str:n {##2} } }
3814         \exp_args:Nc \cs_generate_variant:Nn { str_ #1 :Nn } { Nx , cn , cx }
3815         \__str_tmp:n
3816       }
3817     }
3818     \__str_tmp:n
3819     { set }
3820     { gset }
3821     { const }
3822     { put_left }
3823     { gput_left }
3824     { put_right }
3825     { gput_right }
3826     { }
3827 \group_end:

```

(End definition for `\str_set:Nn` and others. These functions are documented on page 52.)

6.2 Modifying string variables

`\str_replace_all:Nnn` Start by applying `\tl_to_str:n` to convert the old and new token lists to strings, and
`\str_replace_all:cnm` also apply `\tl_to_str:N` to avoid any issues if we are fed a token list variable. Then the
`\str_greplace_all:Nnn` code is a much simplified version of the token list code because neither the delimiter nor
`\str_greplace_all:cnm` the replacement can contain macro parameters or braces. The delimiter `\q_mark` cannot
`\str_replace_once:Nnn` appear in the string to edit so it is used in all cases. Some x-expansion is unnecessary.
`\str_replace_once:cnm` There is no need to avoid losing braces nor to protect against expansion. The ending
`\str_greplace_once:Nnn` code is much simplified and does not need to hide in braces.
`\str_replace_once:cnm`

```

3828 \cs_new_protected:Npn \str_replace_once:Nnn
3829   { \__str_replace:NNNnn \prg_do_nothing: \tl_set:Nx }
3830 \cs_new_protected:Npn \str_greplace_once:Nnn
3831   { \__str_replace:NNNnn \prg_do_nothing: \tl_gset:Nx }
3832 \cs_new_protected:Npn \str_replace_all:Nnn
3833   { \__str_replace:NNNnn \__str_replace_next:w \tl_set:Nx }
3834 \cs_new_protected:Npn \str_greplace_all:Nnn
3835   { \__str_replace:NNNnn \__str_replace_next:w \tl_gset:Nx }
3836 \cs_generate_variant:Nn \str_replace_once:Nnn { c }
3837 \cs_generate_variant:Nn \str_greplace_once:Nnn { c }
3838 \cs_generate_variant:Nn \str_replace_all:Nnn { c }
3839 \cs_generate_variant:Nn \str_greplace_all:Nnn { c }
3840 \cs_new_protected:Npn \__str_replace:NNNnn #1#2#3#4#5
3841   {
3842     \tl_if_empty:nTF {#4}
3843     {
3844       \__msg_kernel_error:nxx { kernel } { empty-search-pattern } {#5}
3845     }
3846     {
3847       \use:x
3848       {
3849         \exp_not:n { \__str_replace_aux:NNNnnn #1 #2 #3 }

```

```

3850         { \tl_to_str:N #3 }
3851         { \tl_to_str:n {#4} } { \tl_to_str:n {#5} }
3852     }
3853 }
3854 }
3855 \cs_new_protected:Npn \__str_replace_aux:NNNnnn #1#2#3#4#5#6
3856 {
3857     \cs_set:Npn \__str_replace_next:w ##1 #5 { ##1 #6 #1 }
3858     #2 #3
3859     {
3860         \__str_replace_next:w
3861         #4
3862         \use_none_delimit_by_q_stop:w
3863         #5
3864         \q_stop
3865     }
3866 }
3867 \cs_new_eq:NN \__str_replace_next:w ?

```

(End definition for `\str_replace_all:Nnn` and others. These functions are documented on page 53.)

```

\str_remove_once:Nn Removal is just a special case of replacement.
\str_remove_once:cn
\str_gremove_once:Nn
\str_gremove_once:cn
3868 \cs_new_protected:Npn \str_remove_once:Nn #1#2
3869 { \str_replace_once:Nnn #1 {#2} { } }
3870 \cs_new_protected:Npn \str_gremove_once:Nn #1#2
3871 { \str_greplace_once:Nnn #1 {#2} { } }
3872 \cs_generate_variant:Nn \str_remove_once:Nn { c }
3873 \cs_generate_variant:Nn \str_gremove_once:Nn { c }

```

(End definition for `\str_remove_once:Nn` and `\str_gremove_once:Nn`. These functions are documented on page 53.)

```

\str_remove_all:Nn Removal is just a special case of replacement.
\str_remove_all:cn
\str_gremove_all:Nn
\str_gremove_all:cn
3874 \cs_new_protected:Npn \str_remove_all:Nn #1#2
3875 { \str_replace_all:Nnn #1 {#2} { } }
3876 \cs_new_protected:Npn \str_gremove_all:Nn #1#2
3877 { \str_greplace_all:Nnn #1 {#2} { } }
3878 \cs_generate_variant:Nn \str_remove_all:Nn { c }
3879 \cs_generate_variant:Nn \str_gremove_all:Nn { c }

```

(End definition for `\str_remove_all:Nn` and `\str_gremove_all:Nn`. These functions are documented on page 53.)

6.3 String comparisons

```

\str_if_empty_p:N More copy-paste!
\str_if_empty_p:c
\str_if_empty:NTF
\str_if_empty:cTF
\str_if_exist_p:N
\str_if_exist_p:c
\str_if_exist:NTF
\str_if_exist:cTF
3880 \prg_new_eq_conditional:NNn \str_if_exist:N \tl_if_exist:N { p , T , F , TF }
3881 \prg_new_eq_conditional:NNn \str_if_exist:c \tl_if_exist:c { p , T , F , TF }
3882 \prg_new_eq_conditional:NNn \str_if_empty:N \tl_if_empty:N { p , T , F , TF }
3883 \prg_new_eq_conditional:NNn \str_if_empty:c \tl_if_empty:c { p , T , F , TF }

```

(End definition for `\str_if_empty:NTF` and `\str_if_exist:NTF`. These functions are documented on page 53.)

`__str_if_eq_x:nn` String comparisons rely on the primitive `\(pdf)strcmp` if available: LuaTeX does not have it, so emulation is required. As the net result is that we do not *always* use the primitive, the correct approach is to wrap up in a function with defined behaviour. That's done by providing a wrapper and then redefining in the LuaTeX case. Note that the necessary Lua code is covered in `l3bootstrap`: long-term this may need to go into a separate Lua file, but at present it's somewhere that spaces are not skipped for ease-of-input. The need to detokenize and force expansion of input arises from the case where a `#` token is used in the input, *e.g.* `__str_if_eq_x:nn {#} { \tl_to_str:n {#} }`, which otherwise would fail as `\luatex_luaescapestring:D` does not double such tokens.

```

3884 \cs_new:Npn \__str_if_eq_x:nn #1#2 { \pdfstrcmp:D {#1} {#2} }
3885 \cs_if_exist:NT \luatex_luaescapestring:D
3886 {
3887   \cs_set:Npn \__str_if_eq_x:nn #1#2
3888   {
3889     \luatex_directlua:D
3890     {
3891       l3kernel_strcmp
3892       (
3893         " \__str_escape_x:n {#1} " ,
3894         " \__str_escape_x:n {#2} "
3895       )
3896     }
3897   }
3898   \cs_new:Npn \__str_escape_x:n #1
3899   {
3900     \luatex_luaescapestring:D
3901     {
3902       \etex_detokenize:D \exp_after:wN { \luatex_expanded:D {#1} }
3903     }
3904   }
3905 }

```

(End definition for `__str_if_eq_x:nn` and `__str_escape_x:n`.)

`__str_if_eq_x_return:nn` It turns out that we often need to compare a token list with the result of applying some function to it, and return with `\prg_return_true/false:`. This test is similar to `\str_if_eq:nnTF` (see `l3str`), but is hard-coded for speed.

```

3906 \cs_new:Npn \__str_if_eq_x_return:nn #1 #2
3907 {
3908   \if_int_compare:w \__str_if_eq_x:nn {#1} {#2} = 0 \exp_stop_f:
3909   \prg_return_true:
3910   \else:
3911     \prg_return_false:
3912   \fi:
3913 }

```

(End definition for `__str_if_eq_x_return:nn`.)

`\str_if_eq_p:nn` Modern engines provide a direct way of comparing two token lists, but returning a number. This set of conditionals therefore make life a bit clearer. The `nn` and `xx` versions are created directly as this is most efficient.

```

3914 \prg_new_conditional:Npnn \str_if_eq:nn #1#2 { p , T , F , TF }
3915 {

```

`\str_if_eq_p:nn`
`\str_if_eq_p:Vn`
`\str_if_eq_p:on`
`\str_if_eq_p:nV`
`\str_if_eq_p:no`
`\str_if_eq_p:VV`
`\str_if_eq:nnTF`
`\str_if_eq:VnTF`
`\str_if_eq:onTF`
`\str_if_eq:nVTF`
`\str_if_eq:noTF`
`\str_if_eq:VVTf`
`\str_if_eq_x_p:nn`
`\str_if_eq_x:nnTF`


```

3916 \if_int_compare:w
3917 \__str_if_eq_x:nn { \exp_not:n {#1} } { \exp_not:n {#2} }
3918 = 0 \exp_stop_f:
3919 \prg_return_true: \else: \prg_return_false: \fi:
3920 }
3921 \cs_generate_variant:Nn \str_if_eq_p:nn { V , o }
3922 \cs_generate_variant:Nn \str_if_eq_p:nn { nV , no , VV }
3923 \cs_generate_variant:Nn \str_if_eq:nnT { V , o }
3924 \cs_generate_variant:Nn \str_if_eq:nnT { nV , no , VV }
3925 \cs_generate_variant:Nn \str_if_eq:nnF { V , o }
3926 \cs_generate_variant:Nn \str_if_eq:nnF { nV , no , VV }
3927 \cs_generate_variant:Nn \str_if_eq:nnTF { V , o }
3928 \cs_generate_variant:Nn \str_if_eq:nnTF { nV , no , VV }
3929 \prg_new_conditional:Npnn \str_if_eq_x:nn #1#2 { p , T , F , TF }
3930 {
3931 \if_int_compare:w \__str_if_eq_x:nn {#1} {#2} = 0 \exp_stop_f:
3932 \prg_return_true: \else: \prg_return_false: \fi:
3933 }

```

(End definition for `\str_if_eq:nnTF` and `\str_if_eq_x:nnTF`. These functions are documented on page 54.)

`\str_if_eq_p:NN` Note that `\str_if_eq:NN` is different from `\tl_if_eq:NN` because it needs to ignore category codes.

`\str_if_eq_p:Nc`

`\str_if_eq_p:cN`

`\str_if_eq_p:cc`

`\str_if_eq:NNTF`

`\str_if_eq:NcTF`

`\str_if_eq:cNTF`

`\str_if_eq:ccTF`

```

3934 \prg_new_conditional:Npnn \str_if_eq:NN #1#2 { p , TF , T , F }
3935 {
3936 \if_int_compare:w \__str_if_eq_x:nn { \tl_to_str:N #1 } { \tl_to_str:N #2 }
3937 = 0 \exp_stop_f: \prg_return_true: \else: \prg_return_false: \fi:
3938 }
3939 \cs_generate_variant:Nn \str_if_eq:NNT { c , Nc , cc }
3940 \cs_generate_variant:Nn \str_if_eq:NNF { c , Nc , cc }
3941 \cs_generate_variant:Nn \str_if_eq:NNTF { c , Nc , cc }
3942 \cs_generate_variant:Nn \str_if_eq_p:NN { c , Nc , cc }

```

(End definition for `\str_if_eq:NNTF`. This function is documented on page 54.)

`\str_if_in:NnTF` Everything here needs to be detokenized but beyond that it is a simple token list test.

`\str_if_in:cn\str_if_in:nnTF` It would be faster to fine-tune the T, F, TF variants by calling the appropriate variant of `\tl_if_in:nnTF` directly but that takes more code.

```

3943 \prg_new_protected_conditional:Npnn \str_if_in:Nn #1#2 { T , F , TF }
3944 {
3945 \use:x
3946 { \tl_if_in:nnTF { \tl_to_str:N #1 } { \tl_to_str:n {#2} } }
3947 { \prg_return_true: } { \prg_return_false: }
3948 }
3949 \cs_generate_variant:Nn \str_if_in:NnT { c }
3950 \cs_generate_variant:Nn \str_if_in:NnF { c }
3951 \cs_generate_variant:Nn \str_if_in:NnTF { c }
3952 \prg_new_protected_conditional:Npnn \str_if_in:nn #1#2 { T , F , TF }
3953 {
3954 \use:x
3955 { \tl_if_in:nnTF { \tl_to_str:n {#1} } { \tl_to_str:n {#2} } }
3956 { \prg_return_true: } { \prg_return_false: }
3957 }

```

(End definition for `\str_if_in:NnTF` and `\str_if_in:cn \str_if_in:nnTF`. These functions are documented on page 54.)

`\str_case:nn` Much the same as `\tl_case:nn(TF)` here: just a change in the internal comparison.

```

\str_case:on      3958 \cs_new:Npn \str_case:nn #1#2
\str_case:nV      3959 {
\str_case:nv      3960   \exp:w
\str_case:nnTF    3961   \__str_case:nnTF {#1} {#2} { } { }
\str_case:onTF    3962 }
\str_case:nVTF    3963 \cs_new:Npn \str_case:nnT #1#2#3
\str_case:nvTF    3964 {
\str_case_x:nn    3965   \exp:w
\str_case_x:nnTF  3966   \__str_case:nnTF {#1} {#2} {#3} { }
\__str_case:nnTF  3967 }
\__str_case_x:nnTF 3968 \cs_new:Npn \str_case:nnF #1#2
\__str_case:nw    3969 {
\__str_case:nw    3970   \exp:w
\__str_case_x:nw  3971   \__str_case:nnTF {#1} {#2} { }
\__str_case_end:nw 3972 }
3973 \cs_new:Npn \str_case:nnTF #1#2
3974 {
3975   \exp:w
3976   \__str_case:nnTF {#1} {#2}
3977 }
3978 \cs_new:Npn \__str_case:nnTF #1#2#3#4
3979 { \__str_case:nw {#1} #2 {#1} { } \q_mark {#3} \q_mark {#4} \q_stop }
3980 \cs_generate_variant:Nn \str_case:nn { o , nV , nv }
3981 \cs_generate_variant:Nn \str_case:nnT { o , nV , nv }
3982 \cs_generate_variant:Nn \str_case:nnF { o , nV , nv }
3983 \cs_generate_variant:Nn \str_case:nnTF { o , nV , nv }
3984 \cs_new:Npn \__str_case:nw #1#2#3
3985 {
3986   \str_if_eq:nnTF {#1} {#2}
3987   { \__str_case_end:nw {#3} }
3988   { \__str_case:nw {#1} }
3989 }
3990 \cs_new:Npn \str_case_x:nn #1#2
3991 {
3992   \exp:w
3993   \__str_case_x:nnTF {#1} {#2} { } { }
3994 }
3995 \cs_new:Npn \str_case_x:nnT #1#2#3
3996 {
3997   \exp:w
3998   \__str_case_x:nnTF {#1} {#2} {#3} { }
3999 }
4000 \cs_new:Npn \str_case_x:nnF #1#2
4001 {
4002   \exp:w
4003   \__str_case_x:nnTF {#1} {#2} { }
4004 }
4005 \cs_new:Npn \str_case_x:nnTF #1#2
4006 {
4007   \exp:w

```

```

4008     \_str_case_x:nnTF {#1} {#2}
4009   }
4010 \cs_new:Npn \_str_case_x:nnTF #1#2#3#4
4011   { \_str_case_x:nw {#1} #2 {#1} { } \q_mark {#3} \q_mark {#4} \q_stop }
4012 \cs_new:Npn \_str_case_x:nw #1#2#3
4013   {
4014     \str_if_eq_x:nnTF {#1} {#2}
4015     { \_str_case_end:nw {#3} }
4016     { \_str_case_x:nw {#1} }
4017   }
4018 \cs_new_eq:NN \_str_case_end:nw \_prg_case_end:nw

```

(End definition for `\str_case:nnTF` and others. These functions are documented on page 55.)

6.4 Mapping to strings

`\str_map_function:NN` The inline and variable mappings are similar to the usual token list mappings but start out by turning the argument to an “other string”. Doing the same for the expandable function mapping would require `_str_to_other:n`, quadratic in the string length. To deal with spaces in that case, `_str_map_function:w` replaces the following space by a braced space and a further call to itself. These are received by `_str_map_function:Nn`, which passes the space to `#1` and calls `_str_map_function:w` to deal with the next space. The space before the braced space allows to optimize the `\q_recursion_tail` test. Of course we need to include a trailing space (the question mark is needed to avoid losing the space when \TeX tokenizes the line). At the cost of about three more auxiliaries this code could get a 9 times speed up by testing only every 9-th character for whether it is `\q_recursion_tail` (also by converting 9 spaces at a time in the `\str_map_function:nN` case).

```

4019 \cs_new:Npn \str_map_function:nN #1#2
4020   {
4021     \exp_after:wN \_str_map_function:w
4022     \exp_after:wN \_str_map_function:Nn \exp_after:wN #2
4023     \etex_detokenize:D {#1}
4024     \q_recursion_tail ? ~
4025     \_prg_break_point:Nn \str_map_break: { }
4026   }
4027 \cs_new:Npn \str_map_function:NN
4028   { \exp_args:No \str_map_function:nN }
4029 \cs_new:Npn \_str_map_function:w #1 ~
4030   { #1 { ~ { ~ } \_str_map_function:w } }
4031 \cs_new:Npn \_str_map_function:Nn #1#2
4032   {
4033     \if_meaning:w \q_recursion_tail #2
4034     \exp_after:wN \str_map_break:
4035     \fi:
4036     #1 #2 \_str_map_function:Nn #1
4037   }
4038 \cs_generate_variant:Nn \str_map_function:NN { c }
4039 \cs_new_protected:Npn \str_map_inline:nn #1#2
4040   {
4041     \int_gincr:N \g__prg_map_int
4042     \cs_gset_protected:cpn
4043     { \_prg_map_ \int_use:N \g__prg_map_int :w } ##1 {#2}

```

```

4044 \use:x
4045 {
4046   \exp_not:N \__str_map_inline:NN
4047   \exp_not:c { __prg_map_ \int_use:N \g__prg_map_int :w }
4048   \__str_to_other_fast:n {#1}
4049 }
4050 \q_recursion_tail
4051 \__prg_break_point:Nn \str_map_break: { \int_gdecr:N \g__prg_map_int }
4052 }
4053 \cs_new_protected:Npn \str_map_inline:Nn
4054 { \exp_args:No \str_map_inline:nn }
4055 \cs_generate_variant:Nn \str_map_inline:Nn { c }
4056 \cs_new:Npn \__str_map_inline:NN #1#2
4057 {
4058   \__quark_if_recursion_tail_break:NN #2 \str_map_break:
4059   \exp_args:No #1 { \token_to_str:N #2 }
4060   \__str_map_inline:NN #1
4061 }
4062 \cs_new_protected:Npn \str_map_variable:nNn #1#2#3
4063 {
4064   \use:x
4065   {
4066     \exp_not:n { \__str_map_variable:NnN #2 {#3} }
4067     \__str_to_other_fast:n {#1}
4068   }
4069   \q_recursion_tail
4070   \__prg_break_point:Nn \str_map_break: { }
4071 }
4072 \cs_new_protected:Npn \str_map_variable:NNn
4073 { \exp_args:No \str_map_variable:nNn }
4074 \cs_new_protected:Npn \__str_map_variable:NnN #1#2#3
4075 {
4076   \__quark_if_recursion_tail_break:NN #3 \str_map_break:
4077   \str_set:Nn #1 {#3}
4078   \use:n {#2}
4079   \__str_map_variable:NnN #1 {#2}
4080 }
4081 \cs_generate_variant:Nn \str_map_variable:NNn { c }
4082 \cs_new:Npn \str_map_break:
4083 { \__prg_map_break:Nn \str_map_break: { } }
4084 \cs_new:Npn \str_map_break:n
4085 { \__prg_map_break:Nn \str_map_break: }

```

(End definition for `\str_map_function:NN` and others. These functions are documented on page 55.)

6.5 Accessing specific characters in a string

`__str_to_other:n` First apply `\tl_to_str:n`, then replace all spaces by “other” spaces, 8 at a time, storing the converted part of the string between the `\q_mark` and `\q_stop` markers. The end is detected when `__str_to_other_loop:w` finds one of the trailing A, distinguished from any contents of the initial token list by their category. Then `__str_to_other_end:w` is called, and finds the result between `\q_mark` and the first A (well, there is also the need to remove a space).

```

4086 \cs_new:Npn \__str_to_other:n #1
4087 {
4088   \exp_after:wN \__str_to_other_loop:w
4089   \tl_to_str:n {#1} ~ A ~ A ~ A ~ A ~ A ~ A ~ A ~ \q_mark \q_stop
4090 }
4091 \group_begin:
4092 \tex_lccode:D '\* = '\ %
4093 \tex_lccode:D '\A = '\A %
4094 \tex_lowercase:D
4095 {
4096   \group_end:
4097   \cs_new:Npn \__str_to_other_loop:w
4098     #1 ~ #2 ~ #3 ~ #4 ~ #5 ~ #6 ~ #7 ~ #8 ~ #9 \q_stop
4099   {
4100     \if_meaning:w A #8
4101       \__str_to_other_end:w
4102     \fi:
4103     \__str_to_other_loop:w
4104     #9 #1 * #2 * #3 * #4 * #5 * #6 * #7 * #8 * \q_stop
4105   }
4106   \cs_new:Npn \__str_to_other_end:w \fi: #1 \q_mark #2 * A #3 \q_stop
4107   { \fi: #2 }
4108 }

```

(End definition for __str_to_other:n, __str_to_other_loop:w, and __str_to_other_end:w.)

__str_to_other_fast:n The difference with __str_to_other:n is that the converted part is left in the input stream, making these commands only restricted-expandable.

```

\__str_to_other_fast_loop:w
\__str_to_other_fast_end:w
4109 \cs_new:Npn \__str_to_other_fast:n #1
4110 {
4111   \exp_after:wN \__str_to_other_fast_loop:w \tl_to_str:n {#1} ~
4112   A ~ A ~ A ~ A ~ A ~ A ~ A ~ A ~ A ~ A ~ \q_stop
4113 }
4114 \group_begin:
4115 \tex_lccode:D '\* = '\ %
4116 \tex_lccode:D '\A = '\A %
4117 \tex_lowercase:D
4118 {
4119   \group_end:
4120   \cs_new:Npn \__str_to_other_fast_loop:w
4121     #1 ~ #2 ~ #3 ~ #4 ~ #5 ~ #6 ~ #7 ~ #8 ~ #9 ~
4122   {
4123     \if_meaning:w A #9
4124       \__str_to_other_fast_end:w
4125     \fi:
4126     #1 * #2 * #3 * #4 * #5 * #6 * #7 * #8 * #9
4127     \__str_to_other_fast_loop:w *
4128   }
4129   \cs_new:Npn \__str_to_other_fast_end:w #1 * A #2 \q_stop {#1}
4130 }

```

(End definition for __str_to_other_fast:n, __str_to_other_fast_loop:w, and __str_to_other_fast_end:w.)

`\str_item:Nn` The `\str_item:nn` hands its argument with spaces escaped to `__str_item:nn`, and
`\str_item:cn` makes sure to turn the result back into a proper string (with category code 10 spaces)
`\str_item:nn` eventually. The `\str_item_ignore_spaces:nn` function does not escape spaces, which
`\str_item_ignore_spaces:nn` are thus ignored by `__str_item:nn` since everything else is done with undelimited arguments. Evaluate the $\langle index \rangle$ argument #2 and count characters in the string, passing
`__str_item:nn` those two numbers to `__str_item:w` for further analysis. If the $\langle index \rangle$ is negative, shift
`__str_item:w` it by the $\langle count \rangle$ to know the how many character to discard, and if that is still negative give an empty result. If the $\langle index \rangle$ is larger than the $\langle count \rangle$, give an empty result, and otherwise discard $\langle index \rangle - 1$ characters before returning the following one. The shift by -1 is obtained by inserting an empty brace group before the string in that case: that brace group also covers the case where the $\langle index \rangle$ is zero.

```

4131 \cs_new:Npn \str_item:Nn { \exp_args:No \str_item:nn }
4132 \cs_generate_variant:Nn \str_item:Nn { c }
4133 \cs_new:Npn \str_item:nn #1#2
4134 {
4135     \exp_args:Nf \tl_to_str:n
4136     {
4137         \exp_args:Nf \__str_item:nn
4138         { \__str_to_other:n {#1} } {#2}
4139     }
4140 }
4141 \cs_new:Npn \str_item_ignore_spaces:nn #1
4142 { \exp_args:No \__str_item:nn { \tl_to_str:n {#1} } }
4143 \__debug_patch_args:nNn { {#1} { \__int_eval:n {#2} } }
4144 \cs_new:Npn \__str_item:nn #1#2
4145 {
4146     \exp_after:wN \__str_item:w
4147     \__int_value:w \__int_eval:w #2 \exp_after:wN ;
4148     \__int_value:w \__str_count:n {#1} ;
4149     #1 \q_stop
4150 }
4151 \cs_new:Npn \__str_item:w #1; #2;
4152 {
4153     \int_compare:nNnTF {#1} < 0
4154     {
4155         \int_compare:nNnTF {#1} < {-#2}
4156         { \use_none_delimit_by_q_stop:w }
4157         {
4158             \exp_after:wN \use_i_delimit_by_q_stop:nw
4159             \exp:w \exp_after:wN \__str_skip_exp_end:w
4160             \__int_value:w \__int_eval:w #1 + #2 ;
4161         }
4162     }
4163     {
4164         \int_compare:nNnTF {#1} > {#2}
4165         { \use_none_delimit_by_q_stop:w }
4166         {
4167             \exp_after:wN \use_i_delimit_by_q_stop:nw
4168             \exp:w \__str_skip_exp_end:w #1 ; { }
4169         }
4170     }
4171 }

```

(End definition for `\str_item:Nn` and others. These functions are documented on page 58.)

```

    \__str_skip_exp_end:w Removes max(#1,0) characters from the input stream, and then leaves \exp_end:. This
\__str_skip_loop:wNNNNNNNN should be expanded using \exp:w. We remove characters 8 at a time until there are
    \__str_skip_end:w at most 8 to remove. Then we do a dirty trick: the \if_case:w construction leaves
    \__str_skip_end:NNNNNNNN between 0 and 8 times the \or: control sequence, and those \or: become arguments of
\__str_skip_end:NNNNNNNN. If the number of characters to remove is 6, say, then there
are two \or: left, and the 8 arguments of \__str_skip_end:NNNNNNNN are the two \or:,
and 6 characters from the input stream, exactly what we wanted to remove. Then close
the \if_case:w conditional with \fi:, and stop the initial expansion with \exp_end:
(see places where \__str_skip_exp_end:w is called).
4172 \cs_new:Npn \__str_skip_exp_end:w #1;
4173 {
4174     \if_int_compare:w #1 > 8 \exp_stop_f:
4175     \exp_after:wN \__str_skip_loop:wNNNNNNNN
4176     \else:
4177     \exp_after:wN \__str_skip_end:w
4178     \__int_value:w \__int_eval:w
4179     \fi:
4180     #1 ;
4181 }
4182 \cs_new:Npn \__str_skip_loop:wNNNNNNNN #1; #2#3#4#5#6#7#8#9
4183 { \exp_after:wN \__str_skip_exp_end:w \__int_value:w \__int_eval:w #1 - 8 ; }
4184 \cs_new:Npn \__str_skip_end:w #1 ;
4185 {
4186     \exp_after:wN \__str_skip_end:NNNNNNNN
4187     \if_case:w #1 \exp_stop_f: \or: \or: \or: \or: \or: \or: \or: \or:
4188 }
4189 \cs_new:Npn \__str_skip_end:NNNNNNNN #1#2#3#4#5#6#7#8 { \fi: \exp_end: }

```

(End definition for `__str_skip_exp_end:w` and others.)

```

\str_range:Nnn Sanitize the string. Then evaluate the arguments. At this stage we also decrement the
\str_range:nnn <start index>, since our goal is to know how many characters should be removed. Then
\str_range_ignore_spaces:nnn limit the range to be non-negative and at most the length of the string (this avoids
\__str_range:nnn needing to check for the end of the string when grabbing characters), shifting negative
\__str_range:w numbers by the appropriate amount. Afterwards, skip characters, then keep some more,
\__str_range:nnw and finally drop the end of the string.

```

```

4190 \cs_new:Npn \str_range:Nnn { \exp_args:No \str_range:nnn }
4191 \cs_generate_variant:Nn \str_range:Nnn { c }
4192 \cs_new:Npn \str_range:nnn #1#2#3
4193 {
4194     \exp_args:Nf \tl_to_str:n
4195     {
4196         \exp_args:Nf \__str_range:nnn
4197         { \__str_to_other:n {#1} } {#2} {#3}
4198     }
4199 }
4200 \cs_new:Npn \str_range_ignore_spaces:nnn #1
4201 { \exp_args:No \__str_range:nnn { \tl_to_str:n {#1} } }
4202 \__debug_patch_args:nNNpn
4203 { {#1} { \__int_eval:n {#2} } { \__int_eval:n {#3} } }
4204 \cs_new:Npn \__str_range:nnn #1#2#3

```

```

4205 {
4206   \exp_after:wN \__str_range:w
4207   \__int_value:w \__str_count:n {#1} \exp_after:wN ;
4208   \__int_value:w \__int_eval:w #2 - 1 \exp_after:wN ;
4209   \__int_value:w \__int_eval:w #3 ;
4210   #1 \q_stop
4211 }
4212 \cs_new:Npn \__str_range:w #1; #2; #3;
4213 {
4214   \exp_args:Nf \__str_range:nnw
4215   { \__str_range_normalize:nn {#2} {#1} }
4216   { \__str_range_normalize:nn {#3} {#1} }
4217 }
4218 \cs_new:Npn \__str_range:nnw #1#2
4219 {
4220   \exp_after:wN \__str_collect_delimit_by_q_stop:w
4221   \__int_value:w \__int_eval:w #2 - #1 \exp_after:wN ;
4222   \exp:w \__str_skip_exp_end:w #1 ;
4223 }

```

(End definition for `\str_range:Nnn` and others. These functions are documented on page 59.)

`__str_range_normalize:nn` This function converts an *<index>* argument into an explicit position in the string (a result of 0 denoting “out of bounds”). Expects two explicit integer arguments: the *<index>* #1 and the string count #2. If #1 is negative, replace it by #1 + #2 + 1, then limit to the range [0, #2].

```

4224 \cs_new:Npn \__str_range_normalize:nn #1#2
4225 {
4226   \int_eval:n
4227   {
4228     \if_int_compare:w #1 < 0 \exp_stop_f:
4229     \if_int_compare:w #1 < -#2 \exp_stop_f:
4230     0
4231     \else:
4232       #1 + #2 + 1
4233     \fi:
4234     \else:
4235       \if_int_compare:w #1 < #2 \exp_stop_f:
4236       #1
4237     \else:
4238       #2
4239     \fi:
4240   \fi:
4241 }
4242 }

```

(End definition for `__str_range_normalize:nn`.)

`_str_collect_delimit_by_q_stop:w` Collects `max(#1,0)` characters, and removes everything else until `\q_stop`. This is somewhat similar to `__str_skip_exp_end:w`, but accepts integer expression arguments. This time we can only grab 7 characters at a time. At the end, we use an `\if_case:w` trick again, so that the 8 first arguments of `__str_collect_end:nnnnnnnnw` are some `\or:`, followed by an `\fi:`, followed by #1 characters from the input stream. Simply leaving this in the input stream closes the conditional properly and the `\or:` disappear.


```

4243 \cs_new:Npn \__str_collect_delimit_by_q_stop:w #1;
4244 { \__str_collect_loop:wn #1 ; { } }
4245 \cs_new:Npn \__str_collect_loop:wn #1 ;
4246 {
4247   \if_int_compare:w #1 > 7 \exp_stop_f:
4248   \exp_after:wN \__str_collect_loop:wnNNNNNNN
4249   \else:
4250   \exp_after:wN \__str_collect_end:wn
4251   \fi:
4252   #1 ;
4253 }
4254 \cs_new:Npn \__str_collect_loop:wnNNNNNNN #1; #2 #3#4#5#6#7#8#9
4255 {
4256   \exp_after:wN \__str_collect_loop:wn
4257   \__int_value:w \__int_eval:w #1 - 7 ;
4258   { #2 #3#4#5#6#7#8#9 }
4259 }
4260 \cs_new:Npn \__str_collect_end:wn #1 ;
4261 {
4262   \exp_after:wN \__str_collect_end:nnnnnnnnw
4263   \if_case:w \if_int_compare:w #1 > 0 \exp_stop_f: #1 \else: 0 \fi: \exp_stop_f:
4264   \or: \or: \or: \or: \or: \or: \fi:
4265 }
4266 \cs_new:Npn \__str_collect_end:nnnnnnnnw #1#2#3#4#5#6#7#8 #9 \q_stop
4267 { #1#2#3#4#5#6#7#8 }

```

(End definition for `__str_collect_delimit_by_q_stop:w` and others.)

6.6 Counting characters

`\str_count_spaces:N` To speed up this function, we grab and discard 9 space-delimited arguments in each iteration of the loop. The loop stops when the last argument is one of the trailing `X⟨number⟩`, and that `⟨number⟩` is added to the sum of 9 that precedes, to adjust the result.

```

4268 \cs_new:Npn \str_count_spaces:N
4269 { \exp_args:No \str_count_spaces:n }
4270 \cs_generate_variant:Nn \str_count_spaces:N { c }
4271 \cs_new:Npn \str_count_spaces:n #1
4272 {
4273   \int_eval:n
4274   {
4275     \exp_after:wN \__str_count_spaces_loop:w
4276     \tl_to_str:n {#1} ~
4277     X 7 ~ X 6 ~ X 5 ~ X 4 ~ X 3 ~ X 2 ~ X 1 ~ X 0 ~ X -1 ~
4278     \q_stop
4279   }
4280 }
4281 \cs_new:Npn \__str_count_spaces_loop:w #1~#2~#3~#4~#5~#6~#7~#8~#9~
4282 {
4283   \if_meaning:w X #9
4284   \use_i_delimit_by_q_stop:nw
4285   \fi:
4286   9 + \__str_count_spaces_loop:w
4287 }

```

(End definition for `\str_count_spaces:N`, `\str_count_spaces:n`, and `__str_count_spaces_loop:w`. These functions are documented on page 57.)

`\str_count:N` To count characters in a string we could first escape all spaces using `__str_to_other:n`, then pass the result to `\tl_count:n`. However, the escaping step would be quadratic in the number of characters in the string, and we can do better. Namely, sum the number of spaces (`\str_count_spaces:n`) and the result of `\tl_count:n`, which ignores spaces. `\str_count:n` Since strings tend to be longer than token lists, we use specialized functions to count characters ignoring spaces. Namely, loop, grabbing 9 non-space characters at each step, and end as soon as we reach one of the 9 trailing items. The internal function `__str_count:n`, used in `\str_item:nn` and `\str_range:nnn`, is similar to `\str_count_ignore_spaces:n` but expects its argument to already be a string or a string with spaces escaped.

```

4288 \cs_new:Npn \str_count:N { \exp_args:No \str_count:n }
4289 \cs_generate_variant:Nn \str_count:N { c }
4290 \cs_new:Npn \str_count:n #1
4291 {
4292   \__str_count_aux:n
4293   {
4294     \str_count_spaces:n {#1}
4295     + \exp_after:wN \__str_count_loop:NNNNNNNNN \tl_to_str:n {#1}
4296   }
4297 }
4298 \cs_new:Npn \__str_count:n #1
4299 {
4300   \__str_count_aux:n
4301   { \__str_count_loop:NNNNNNNNN #1 }
4302 }
4303 \cs_new:Npn \str_count_ignore_spaces:n #1
4304 {
4305   \__str_count_aux:n
4306   { \exp_after:wN \__str_count_loop:NNNNNNNNN \tl_to_str:n {#1} }
4307 }
4308 \cs_new:Npn \__str_count_aux:n #1
4309 {
4310   \int_eval:n
4311   {
4312     #1
4313     { X 8 } { X 7 } { X 6 }
4314     { X 5 } { X 4 } { X 3 }
4315     { X 2 } { X 1 } { X 0 }
4316     \q_stop
4317   }
4318 }
4319 \cs_new:Npn \__str_count_loop:NNNNNNNNN #1#2#3#4#5#6#7#8#9
4320 {
4321   \if_meaning:w X #9
4322     \exp_after:wN \use_none_delimit_by_q_stop:w
4323   \fi:
4324   9 + \__str_count_loop:NNNNNNNNN
4325 }
```

(End definition for `\str_count:N` and others. These functions are documented on page 57.)

6.7 The first character in a string

`\str_head:N` The `_ignore_spaces` variant applies `\tl_to_str:n` then grabs the first item, thus skipping spaces. As usual, `\str_head:N` expands its argument and hands it to `\str_head:n`.
`\str_head:c` To circumvent the fact that TeX skips spaces when grabbing undelimited macro parameters, `__str_head:w` takes an argument delimited by a space. If #1 starts with a non-space character, `\use_i_delimit_by_q_stop:nw` leaves that in the input stream. On the other hand, if #1 starts with a space, the `__str_head:w` takes an empty argument, and the single (initially braced) space in the definition of `__str_head:w` makes its way to the output. Finally, for an empty argument, the (braced) empty brace group in the definition of `\str_head:n` gives an empty result after passing through `\use_i_delimit_by_q_stop:nw`.
`\str_head:n`
`\str_head_ignore_spaces:n`
`__str_head:w`

```

4326 \cs_new:Npn \str_head:N { \exp_args:No \str_head:n }
4327 \cs_generate_variant:Nn \str_head:N { c }
4328 \cs_new:Npn \str_head:n #1
4329 {
4330     \exp_after:wN \__str_head:w
4331     \tl_to_str:n {#1}
4332     { { } } ~ \q_stop
4333 }
4334 \cs_new:Npn \__str_head:w #1 ~ %
4335 { \use_i_delimit_by_q_stop:nw #1 { ~ } }
4336 \cs_new:Npn \str_head_ignore_spaces:n #1
4337 {
4338     \exp_after:wN \use_i_delimit_by_q_stop:nw
4339     \tl_to_str:n {#1} { } \q_stop
4340 }
```

(End definition for `\str_head:N` and others. These functions are documented on page 58.)

`\str_tail:N` Getting the tail is a little bit more convoluted than the head of a string. We hit the front of the string with `\reverse_if:N \if_charcode:w \scan_stop:.` This removes the first character, and necessarily makes the test true, since the character cannot match `\scan_stop:.` The auxiliary function then inserts the required `\fi:` to close the conditional, and leaves the tail of the string in the input stream. The details are such that an empty string has an empty tail (this requires in particular that the end-marker X be unexpandable and not a control sequence). The `_ignore_spaces` is rather simpler: after converting the input to a string, `__str_tail_auxii:w` removes one undelimited argument and leaves everything else until an end-marker `\q_mark`. One can check that an empty (or blank) string yields an empty tail.
`\str_tail:c`
`\str_tail:n`
`\str_tail_ignore_spaces:n`
`__str_tail_auxi:w`
`__str_tail_auxii:w`

```

4341 \cs_new:Npn \str_tail:N { \exp_args:No \str_tail:n }
4342 \cs_generate_variant:Nn \str_tail:N { c }
4343 \cs_new:Npn \str_tail:n #1
4344 {
4345     \exp_after:wN \__str_tail_auxi:w
4346     \reverse_if:N \if_charcode:w
4347         \scan_stop: \tl_to_str:n {#1} X X \q_stop
4348 }
4349 \cs_new:Npn \__str_tail_auxi:w #1 X #2 \q_stop { \fi: #1 }
4350 \cs_new:Npn \str_tail_ignore_spaces:n #1
4351 {
4352     \exp_after:wN \__str_tail_auxii:w
4353     \tl_to_str:n {#1} \q_mark \q_mark \q_stop
```

```

4354 }
4355 \cs_new:Npn \__str_tail_auxii:w #1 #2 \q_mark #3 \q_stop { #2 }

```

(End definition for `\str_tail:N` and others. These functions are documented on page 58.)

6.8 String manipulation

`\str_fold_case:n` Case changing for programmatic reasons is done by first detokenizing input then doing a simple loop that only has to worry about spaces and everything else. The output is detokenized to allow data sharing with text-based case changing.

`\str_fold_case:V`

`\str_lower_case:n`

`\str_lower_case:f`

`\str_upper_case:n`

`\str_upper_case:f`

```

4356 \cs_new:Npn \str_fold_case:n #1 { \__str_change_case:nn {#1} { fold } }
4357 \cs_new:Npn \str_lower_case:n #1 { \__str_change_case:nn {#1} { lower } }
4358 \cs_new:Npn \str_upper_case:n #1 { \__str_change_case:nn {#1} { upper } }
4359 \cs_generate_variant:Nn \str_fold_case:n { V }
4360 \cs_generate_variant:Nn \str_lower_case:n { f }
4361 \cs_generate_variant:Nn \str_upper_case:n { f }
4362 \cs_new:Npn \__str_change_case:nn #1
4363 {
4364   \exp_after:wN \__str_change_case_aux:nn \exp_after:wN
4365   { \tl_to_str:n {#1} }
4366 }
4367 \cs_new:Npn \__str_change_case_aux:nn #1#2
4368 {
4369   \__str_change_case_loop:nw {#2} #1 \q_recursion_tail \q_recursion_stop
4370   \__str_change_case_result:n { }
4371 }
4372 \cs_new:Npn \__str_change_case_output:nw #1#2 \__str_change_case_result:n #3
4373 { #2 \__str_change_case_result:n { #3 #1 } }
4374 \cs_generate_variant:Nn \__str_change_case_output:nw { f }
4375 \cs_new:Npn \__str_change_case_end:wn #1 \__str_change_case_result:n #2 { #2 }
4376 \cs_new:Npn \__str_change_case_loop:nw #1#2 \q_recursion_stop
4377 {
4378   \tl_if_head_is_space:nTF {#2}
4379   { \__str_change_case_space:n }
4380   { \__str_change_case_char:nN }
4381   {#1} #2 \q_recursion_stop
4382 }
4383 \use:x
4384 { \cs_new:Npn \exp_not:N \__str_change_case_space:n ##1 \c_space_tl }
4385 {
4386   \__str_change_case_output:nw { ~ }
4387   \__str_change_case_loop:nw {#1}
4388 }
4389 \cs_new:Npn \__str_change_case_char:nN #1#2
4390 {
4391   \quark_if_recursion_tail_stop_do:Nn #2
4392   { \__str_change_case_end:wn }
4393   \cs_if_exist:cTF { c__unicode_ #1 _ #2 _tl }
4394   {
4395     \__str_change_case_output:fw
4396     { \tl_to_str:c { c__unicode_ #1 _ #2 _tl } }
4397   }
4398   { \__str_change_case_char_aux:nN {#1} #2 }
4399   \__str_change_case_loop:nw {#1}

```

```
4400 }
```

For Unicode engines there's a look up to see if the current character has a valid one-to-one case change mapping. That's not needed for 8-bit engines: as they don't have `\utex_char:D` all of the changes they can make are hard-coded and so already picked up above.

```
4401 \cs_if_exist:NTF \utex_char:D
4402 {
4403   \cs_new:Npn \__str_change_case_char_aux:nN #1#2
4404   {
4405     \int_compare:nNnTF { \use:c { __str_lookup_ #1 :N } #2 } = { 0 }
4406     { \__str_change_case_output:nw {#2} }
4407     {
4408       \__str_change_case_output:fw
4409       { \utex_char:D \use:c { __str_lookup_ #1 :N } #2 ~ }
4410     }
4411   }
4412   \cs_new_protected:Npn \__str_lookup_lower:N #1 { \tex_lccode:D '#1 }
4413   \cs_new_protected:Npn \__str_lookup_upper:N #1 { \tex_uccode:D '#1 }
4414   \cs_new_eq:NN \__str_lookup_fold:N \__str_lookup_lower:N
4415 }
4416 {
4417   \cs_new:Npn \__str_change_case_char_aux:nN #1#2
4418   { \__str_change_case_output:nw {#2} }
4419 }
```

(End definition for `\str_fold_case:n` and others. These functions are documented on page 61.)

<code>\c_ampersand_str</code>	For all of those strings, use <code>\cs_to_str:N</code> to get characters with the correct category code without worries
<code>\c_atsign_str</code>	
<code>\c_backslash_str</code>	4420 <code>\str_const:Nx \c_ampersand_str { \cs_to_str:N \& }</code>
<code>\c_left_brace_str</code>	4421 <code>\str_const:Nx \c_atsign_str { \cs_to_str:N \@ }</code>
<code>\c_right_brace_str</code>	4422 <code>\str_const:Nx \c_backslash_str { \cs_to_str:N \ }</code>
<code>\c_circumflex_str</code>	4423 <code>\str_const:Nx \c_left_brace_str { \cs_to_str:N \{ }</code>
<code>\c_colon_str</code>	4424 <code>\str_const:Nx \c_right_brace_str { \cs_to_str:N \} }</code>
<code>\c_dollar_str</code>	4425 <code>\str_const:Nx \c_circumflex_str { \cs_to_str:N ^ }</code>
<code>\c_hash_str</code>	4426 <code>\str_const:Nx \c_colon_str { \cs_to_str:N : }</code>
<code>\c_percent_str</code>	4427 <code>\str_const:Nx \c_dollar_str { \cs_to_str:N \$ }</code>
<code>\c_tilde_str</code>	4428 <code>\str_const:Nx \c_hash_str { \cs_to_str:N # }</code>
<code>\c_underscore_str</code>	4429 <code>\str_const:Nx \c_percent_str { \cs_to_str:N % }</code>
	4430 <code>\str_const:Nx \c_tilde_str { \cs_to_str:N ~ }</code>
	4431 <code>\str_const:Nx \c_underscore_str { \cs_to_str:N _ }</code>

(End definition for `\c_ampersand_str` and others. These variables are documented on page 62.)

`\l_tmpa_str` Scratch strings.

```
4432 \str_new:N \l_tmpa_str
4433 \str_new:N \l_tmpb_str
4434 \str_new:N \g_tmpa_str
4435 \str_new:N \g_tmpb_str
```

(End definition for `\l_tmpa_str` and others. These variables are documented on page 62.)

6.9 Viewing strings

```

\str_show:n Displays a string on the terminal.
\str_show:N
\str_show:c
4436 \cs_new_eq:NN \str_show:n \tl_show:n
4437 \cs_new_eq:NN \str_show:N \tl_show:N
4438 \cs_generate_variant:Nn \str_show:N { c }

```

(End definition for `\str_show:n` and `\str_show:N`. These functions are documented on page 61.)

6.10 Unicode data for case changing

```

4439 <@@=unicode>

```

Case changing both for strings and “text” requires data from the Unicode Consortium. Some of this is build in to the format (as `\lccode` and `\uccode` values) but this covers only the simple one-to-one situations and does not fully handle for example case folding.

The data required for cross-module manipulations is loaded here: currently this means for `str` and `tl` functions. As such, the prefix used is not `str` but rather `unicode`. For performance (as the entire data set must be read during each run) and as this code comes somewhat early in the load process, there is quite a bit of low-level code here.

As only the data needs to remain at the end of this process, everything is set up inside a group.

```

4440 \group_begin:

```

A read stream is needed. The I/O module is not yet in place *and* we do not want to use up a stream. We therefore use a known free one in format mode or look for the next free one in package mode (covers plain, $\text{\LaTeX} 2_{\epsilon}$ and ConTeXt MkII and MkIV).

```

4441 <*initex>
4442 \tex_chardef:D \g__unicode_data_ior = 0 \scan_stop:
4443 </initex>
4444 <*package>
4445 \tex_chardef:D \g__unicode_data_ior
4446 \etex_numexpr:D
4447 \cs_if_exist:NTF \lastallocatedread
4448 { \lastallocatedread }
4449 {
4450 \cs_if_exist:NTF \c_syst_last_allocated_read
4451 { \c_syst_last_allocated_read }
4452 { \tex_count:D 16 ~ }
4453 }
4454 + 1
4455 \scan_stop:
4456 </package>

```

Set up to read each file. As they use C-style comments, there is a need to deal with `#`. At the same time, spaces are important so they need to be picked up as they are important. Beyond that, the current category code scheme works fine. With no I/O loop available, hard-code one that works quickly.

```

4457 \cs_set_protected:Npn \__unicode_map_inline:n #1
4458 {
4459 \group_begin:
4460 \tex_catcode:D '\# = 12 \scan_stop:
4461 \tex_catcode:D '\ = 10 \scan_stop:
4462 \tex_openin:D \g__unicode_data_ior = #1 \scan_stop:

```

```

4463     \cs_if_exist:NT \utex_char:D
4464     { \__unicode_map_loop: }
4465     \tex_closein:D \g__unicode_data_ior
4466   \group_end:
4467 }
4468 \cs_set_protected:Npn \__unicode_map_loop:
4469 {
4470   \tex_if_eof:D \g__unicode_data_ior
4471   \exp_after:wN \use_none:n
4472   \else:
4473     \exp_after:wN \use:n
4474   \fi:
4475   {
4476     \tex_read:D \g__unicode_data_ior to \l__unicode_tmp_tl
4477     \if_meaning:w \c_empty_tl \l__unicode_tmp_tl
4478     \else:
4479       \exp_after:wN \__unicode_parse:w \l__unicode_tmp_tl \q_stop
4480     \fi:
4481     \__unicode_map_loop:
4482   }
4483 }

```

The lead-off parser for each line is common for all of the files. If the line starts with a # it's a comment. There's one special comment line to look out for in `SpecialCasing.txt` as we want to ignore everything after it. As this line does not appear in any other sources and the test is quite quick (there are relatively few comment lines), it can be present in all of the passes.

```

4484 \cs_set_protected:Npn \__unicode_parse:w #1#2 \q_stop
4485 {
4486   \reverse_if:N \if:w \c_hash_str #1
4487   \__unicode_parse_auxi:w #1#2 \q_stop
4488   \else:
4489     \if_int_compare:w \__str_if_eq_x:nn
4490     { \exp_not:n {#2} } { ~Conditional~Mappings~ } = 0 \exp_stop_f:
4491     \cs_set_protected:Npn \__unicode_parse:w ##1 \q_stop { }
4492   \fi:
4493   \fi:
4494 }

```

Storing each exception is always done in the same way: create a constant token list which expands to exactly the mapping. These have the category codes “now” (so should be letters) but are later detokenized for string use.

```

4495 \cs_set_protected:Npn \__unicode_store:nnnnn #1#2#3#4#5
4496 {
4497   \tl_const:cx { c__unicode_ #2 _ \utex_char:D "#1 _tl }
4498   {
4499     \utex_char:D "#3 ~
4500     \utex_char:D "#4 ~
4501     \tl_if_blank:nF {#5}
4502     { \utex_char:D "#5 }
4503   }
4504 }

```

Parse the main Unicode data file for title case exceptions (the one-to-one lower and upper case mappings it contains are all be covered by the `TEX` data).

```

4505 \cs_set_protected:Npn \__unicode_parse_auxi:w
4506   #1 ; #2 ; #3 ; #4 ; #5 ; #6 ; #7 ; #8 ; #9 ;
4507   { \__unicode_parse_auxii:w #1 ; }
4508 \cs_set_protected:Npn \__unicode_parse_auxii:w
4509   #1 ; #2 ; #3 ; #4 ; #5 ; #6 ; #7 \q_stop
4510   {
4511     \tl_if_blank:nF {#7}
4512     {
4513       \if_int_compare:w \__str_if_eq_x:nn { #5 ~ } {#7} = 0 \exp_stop_f:
4514       \else:
4515         \tl_const:cx
4516         { c__unicode_mixed_ \utex_char:D "#1 _tl }
4517         { \utex_char:D "#7 }
4518       \fi:
4519     }
4520   }
4521 \__unicode_map_inline:n { UnicodeData.txt }

```

The set up for case folding is in two parts. For the basic (core) mappings, folding is the same as lower casing in most positions so only store the differences. For the more complex foldings, always store the result, splitting up the two or three code points in the input as required.

```

4522 \cs_set_protected:Npn \__unicode_parse_auxi:w #1 ;~ #2 ;~ #3 ; #4 \q_stop
4523   {
4524     \if_int_compare:w \__str_if_eq_x:nn {#2} { C } = 0 \exp_stop_f:
4525     \if_int_compare:w \tex_lccode:D "#1 = "#3 \scan_stop:
4526     \else:
4527       \tl_const:cx
4528       { c__unicode_fold_ \utex_char:D "#1 _tl }
4529       { \utex_char:D "#3 ~ }
4530     \fi:
4531   \else:
4532     \if_int_compare:w \__str_if_eq_x:nn {#2} { F } = 0 \exp_stop_f:
4533     \__unicode_parse_auxii:w #1 ~ #3 ~ \q_stop
4534   \fi:
4535 \fi:
4536 }
4537 \cs_set_protected:Npn \__unicode_parse_auxii:w #1 ~ #2 ~ #3 ~ #4 \q_stop
4538   { \__unicode_store:nnnn {#1} { fold } {#2} {#3} {#4} }
4539 \__unicode_map_inline:n { CaseFolding.txt }

```

For upper and lower casing special situations, there is a bit more to do as we also have title casing to consider.

```

4540 \cs_set_protected:Npn \__unicode_parse_auxi:w #1 ;~ #2 ;~ #3 ;~ #4 ; #5 \q_stop
4541   {
4542     \use:n { \__unicode_parse_auxii:w #1 ~ lower ~ #2 ~ } ~ \q_stop
4543     \use:n { \__unicode_parse_auxii:w #1 ~ upper ~ #4 ~ } ~ \q_stop
4544     \if_int_compare:w \__str_if_eq_x:nn {#3} {#4} = 0 \exp_stop_f:
4545     \else:
4546       \use:n { \__unicode_parse_auxii:w #1 ~ mixed ~ #3 ~ } ~ \q_stop
4547     \fi:
4548   }
4549 \cs_set_protected:Npn \__unicode_parse_auxii:w #1 ~ #2 ~ #3 ~ #4 ~ #5 \q_stop
4550   {
4551     \tl_if_empty:nF {#4}

```



```

4552     { \__unicode_store:nnnnn {#1} {#2} {#3} {#4} {#5} }
4553   }
4554   \__unicode_map_inline:n { SpecialCasing.txt }

```

For the 8-bit engines, the above does nothing but there is some set up needed. There is no expandable character generator primitive so some alternative is needed. As we've not used up hash space for the above, we can go for the fast approach here of one name per letter. Keeping folding and lower casing separate makes the use later a bit easier.

```

4555   \cs_if_exist:NF \utex_char:D
4556   {
4557     \cs_set_protected:Npn \__unicode_tmp:NN #1#2
4558     {
4559       \if_meaning:w \q_recursion_tail #2
4560       \exp_after:wN \use_none_delimit_by_q_recursion_stop:w
4561       \fi:
4562       \tl_const:cn { c__unicode_fold_ #1 _tl } {#2}
4563       \tl_const:cn { c__unicode_lower_ #1 _tl } {#2}
4564       \tl_const:cn { c__unicode_upper_ #2 _tl } {#1}
4565       \__unicode_tmp:NN
4566     }
4567     \__unicode_tmp:NN
4568     AaBbCcDdEeFfGgHhIiJjKkLlMmNnOoPpQqRrSsTtUuVvWwXxYyZz
4569     ? \q_recursion_tail \q_recursion_stop
4570   }

```

All done: tidy up.

```

4571 \group_end:
4572 </initex | package>

```

7 l3seq implementation

The following test files are used for this code: *m3seq002*, *m3seq003*.

```

4573 <*initex | package>
4574 <@@=seq>

```

A sequence is a control sequence whose top-level expansion is of the form “\s__seq __seq_item:n {<item₁>} ... __seq_item:n {<item_n>}”, with a leading scan mark followed by *n* items of the same form. An earlier implementation used the structure “\seq_elt:w <item₁> \seq_elt_end: ... \seq_elt:w <item_n> \seq_elt_end:”. This allowed rapid searching using a delimited function, but was not suitable for items containing {, } and # tokens, and also lead to the loss of surrounding braces around items.

\s__seq The variable is defined in the l3quark module, loaded later.

(End definition for \s__seq.)

__seq_item:n The delimiter is always defined, but when used incorrectly simply removes its argument and hits an undefined control sequence to raise an error.

```

4575 \cs_new:Npn \__seq_item:n
4576 {
4577   \__msg_kernel_expandable_error:nn { kernel } { misused-sequence }
4578   \use_none:n
4579 }

```

(End definition for __seq_item:n.)

`\l__seq_internal_a_tl` Scratch space for various internal uses.
`\l__seq_internal_b_tl` 4580 `\tl_new:N \l__seq_internal_a_tl`
4581 `\tl_new:N \l__seq_internal_b_tl`
(End definition for `\l__seq_internal_a_tl` and `\l__seq_internal_b_tl`.)

`__seq_tmp:w` Scratch function for internal use.
4582 `\cs_new_eq:NN __seq_tmp:w ?`
(End definition for `__seq_tmp:w`.)

`\c_empty_seq` A sequence with no item, following the structure mentioned above.
4583 `\tl_const:Nn \c_empty_seq { \s__seq }`
(End definition for `\c_empty_seq`. This variable is documented on page 73.)

7.1 Allocation and initialisation

`\seq_new:N` Sequences are initialized to `\c_empty_seq`.
`\seq_new:c` 4584 `\cs_new_protected:Npn \seq_new:N #1`
4585 `{`
4586 `__chk_if_free_cs:N #1`
4587 `\cs_gset_eq:NN #1 \c_empty_seq`
4588 `}`
4589 `\cs_generate_variant:Nn \seq_new:N { c }`
(End definition for `\seq_new:N`. This function is documented on page 64.)

`\seq_clear:N` Clearing a sequence is similar to setting it equal to the empty one.
`\seq_clear:c` 4590 `\cs_new_protected:Npn \seq_clear:N #1`
`\seq_gclear:N` 4591 `{ \seq_set_eq:NN #1 \c_empty_seq }`
`\seq_gclear:c` 4592 `\cs_generate_variant:Nn \seq_clear:N { c }`
4593 `\cs_new_protected:Npn \seq_gclear:N #1`
4594 `{ \seq_gset_eq:NN #1 \c_empty_seq }`
4595 `\cs_generate_variant:Nn \seq_gclear:N { c }`
(End definition for `\seq_clear:N` and `\seq_gclear:N`. These functions are documented on page 64.)

`\seq_clear_new:N` Once again we copy code from the token list functions.
`\seq_clear_new:c` 4596 `\cs_new_protected:Npn \seq_clear_new:N #1`
`\seq_gclear_new:N` 4597 `{ \seq_if_exist:NTF #1 { \seq_clear:N #1 } { \seq_new:N #1 } }`
`\seq_gclear_new:c` 4598 `\cs_generate_variant:Nn \seq_clear_new:N { c }`
4599 `\cs_new_protected:Npn \seq_gclear_new:N #1`
4600 `{ \seq_if_exist:NTF #1 { \seq_gclear:N #1 } { \seq_new:N #1 } }`
4601 `\cs_generate_variant:Nn \seq_gclear_new:N { c }`
(End definition for `\seq_clear_new:N` and `\seq_gclear_new:N`. These functions are documented on page 64.)

\seq_set_eq:NN Copying a sequence is the same as copying the underlying token list.

```

\seq_set_eq:cN 4602 \cs_new_eq:NN \seq_set_eq:NN \tl_set_eq:NN
\seq_set_eq:Nc 4603 \cs_new_eq:NN \seq_set_eq:Nc \tl_set_eq:Nc
\seq_set_eq:cc 4604 \cs_new_eq:NN \seq_set_eq:cN \tl_set_eq:cN
\seq_gset_eq:NN 4605 \cs_new_eq:NN \seq_gset_eq:NN \tl_gset_eq:NN
\seq_gset_eq:cN 4606 \cs_new_eq:NN \seq_gset_eq:Nc \tl_gset_eq:Nc
\seq_gset_eq:Nc 4607 \cs_new_eq:NN \seq_gset_eq:cN \tl_gset_eq:cN
\seq_gset_eq:cc 4608 \cs_new_eq:NN \seq_gset_eq:cc \tl_gset_eq:cc
4609 \cs_new_eq:NN \seq_gset_eq:cc \tl_gset_eq:cc

```

(End definition for `\seq_set_eq:NN` and `\seq_gset_eq:NN`. These functions are documented on page 64.)

\seq_set_from_clist:NN Setting a sequence from a comma-separated list is done using a simple mapping.

```

\seq_set_from_clist:cN 4610 \cs_new_protected:Npn \seq_set_from_clist:NN #1#2
\seq_set_from_clist:Nc 4611 {
\seq_set_from_clist:cc 4612   \tl_set:Nx #1
\seq_set_from_clist:Nn 4613   { \s__seq \clist_map_function:NN #2 \__seq_wrap_item:n }
\seq_set_from_clist:cn 4614 }
\seq_gset_from_clist:NN 4615 \cs_new_protected:Npn \seq_gset_from_clist:Nn #1#2
\seq_gset_from_clist:cN 4616 {
\seq_gset_from_clist:Nc 4617   \tl_set:Nx #1
\seq_gset_from_clist:cc 4618   { \s__seq \clist_map_function:nN {#2} \__seq_wrap_item:n }
4619 }
\seq_gset_from_clist:Nn 4620 \cs_new_protected:Npn \seq_gset_from_clist:NN #1#2
\seq_gset_from_clist:cn 4621 {
4622   \tl_gset:Nx #1
4623   { \s__seq \clist_map_function:NN #2 \__seq_wrap_item:n }
4624 }
4625 \cs_new_protected:Npn \seq_gset_from_clist:Nn #1#2
4626 {
4627   \tl_gset:Nx #1
4628   { \s__seq \clist_map_function:nN {#2} \__seq_wrap_item:n }
4629 }
4630 \cs_generate_variant:Nn \seq_set_from_clist:NN { Nc }
4631 \cs_generate_variant:Nn \seq_set_from_clist:NN { c , cc }
4632 \cs_generate_variant:Nn \seq_set_from_clist:Nn { c }
4633 \cs_generate_variant:Nn \seq_gset_from_clist:NN { Nc }
4634 \cs_generate_variant:Nn \seq_gset_from_clist:NN { c , cc }
4635 \cs_generate_variant:Nn \seq_gset_from_clist:Nn { c }

```

(End definition for `\seq_set_from_clist:NN` and others. These functions are documented on page 64.)

\seq_set_split:Nnn When the separator is empty, everything is very simple, just map `__seq_wrap_item:n` through the items of the last argument. For non-trivial separators, the goal is to split a given token list at the marker, strip spaces from each item, and remove one set of outer braces if after removing leading and trailing spaces the item is enclosed within braces. After `\tl_replace_all:Nnn`, the token list `\l__seq_internal_a_tl` is a repetition of the pattern `__seq_set_split_auxi:w \prg_do_nothing: <item with spaces> __seq_set_split_end:.` Then, x-expansion causes `__seq_set_split_auxi:w` to trim spaces, and leaves its result as `__seq_set_split_auxii:w <trimmed item> __seq_set_split_end:.` This is then converted to the `l3seq` internal structure by another x-expansion. In the first step, we insert `\prg_do_nothing:` to avoid losing braces too early:

that would cause space trimming to act within those lost braces. The second step is solely there to strip braces which are outermost after space trimming.

```

4636 \cs_new_protected:Npn \seq_set_split:Nnn
4637 { \__seq_set_split:NNnn \tl_set:Nx }
4638 \cs_new_protected:Npn \seq_gset_split:Nnn
4639 { \__seq_set_split:NNnn \tl_gset:Nx }
4640 \cs_new_protected:Npn \__seq_set_split:NNnn #1#2#3#4
4641 {
4642   \tl_if_empty:nTF {#3}
4643   {
4644     \tl_set:Nn \l__seq_internal_a_tl
4645     { \tl_map_function:nN {#4} \__seq_wrap_item:n }
4646   }
4647   {
4648     \tl_set:Nn \l__seq_internal_a_tl
4649     {
4650       \__seq_set_split_auxi:w \prg_do_nothing:
4651       #4
4652       \__seq_set_split_end:
4653     }
4654     \tl_replace_all:Nnn \l__seq_internal_a_tl { #3 }
4655     {
4656       \__seq_set_split_end:
4657       \__seq_set_split_auxi:w \prg_do_nothing:
4658     }
4659     \tl_set:Nx \l__seq_internal_a_tl { \l__seq_internal_a_tl }
4660   }
4661   #1 #2 { \s__seq \l__seq_internal_a_tl }
4662 }
4663 \cs_new:Npn \__seq_set_split_auxi:w #1 \__seq_set_split_end:
4664 {
4665   \exp_not:N \__seq_set_split_auxii:w
4666   \exp_args:No \tl_trim_spaces:n {#1}
4667   \exp_not:N \__seq_set_split_end:
4668 }
4669 \cs_new:Npn \__seq_set_split_auxii:w #1 \__seq_set_split_end:
4670 { \__seq_wrap_item:n {#1} }
4671 \cs_generate_variant:Nn \seq_set_split:Nnn { NnV }
4672 \cs_generate_variant:Nn \seq_gset_split:Nnn { NnV }

```

(End definition for `\seq_set_split:Nnn` and others. These functions are documented on page 65.)

`\seq_concat:NNN` When concatenating sequences, one must remove the leading `\s__seq` of the second sequence. The result starts with `\s__seq` (of the first sequence), which stops `f`-expansion.

`\seq_gconcat:NNN`

```

4673 \cs_new_protected:Npn \seq_concat:NNN #1#2#3
4674 { \tl_set:Nf #1 { \exp_after:wN \use_i:nn \exp_after:wN #2 #3 } }
4675 \cs_new_protected:Npn \seq_gconcat:NNN #1#2#3
4676 { \tl_gset:Nf #1 { \exp_after:wN \use_i:nn \exp_after:wN #2 #3 } }
4677 \cs_generate_variant:Nn \seq_concat:NNN { ccc }
4678 \cs_generate_variant:Nn \seq_gconcat:NNN { ccc }

```

(End definition for `\seq_concat:NNN` and `\seq_gconcat:NNN`. These functions are documented on page 65.)

```

\seq_if_exist_p:N Copies of the cs functions defined in l3basics.
\seq_if_exist_p:c 4679 \prg_new_eq_conditional:NNn \seq_if_exist:N \cs_if_exist:N
\seq_if_exist:NTF 4680 { TF , T , F , p }
\seq_if_exist:cTF 4681 \prg_new_eq_conditional:NNn \seq_if_exist:c \cs_if_exist:c
4682 { TF , T , F , p }

```

(End definition for `\seq_if_exist:N`. This function is documented on page 65.)

7.2 Appending data to either end

```

\seq_put_left:Nn When adding to the left of a sequence, remove \s__seq. This is done by \__seq_put_
\seq_put_left:NV left_aux:w, which also stops f-expansion.
\seq_put_left:Nv 4683 \cs_new_protected:Npn \seq_put_left:Nn #1#2
\seq_put_left:No 4684 {
\seq_put_left:Nx 4685   \tl_set:Nx #1
\seq_put_left:cn 4686   {
\seq_put_left:cV 4687     \exp_not:n { \s__seq \__seq_item:n {#2} }
\seq_put_left:cv 4688     \exp_not:f { \exp_after:wN \__seq_put_left_aux:w #1 }
\seq_put_left:co 4689   }
\seq_put_left:cx 4690 }
\seq_gput_left:Nn 4691 \cs_new_protected:Npn \seq_gput_left:Nn #1#2
\seq_gput_left:NV 4692 {
\seq_gput_left:Nv 4693   \tl_gset:Nx #1
\seq_gput_left:No 4694   {
\seq_gput_left:Nx 4695     \exp_not:n { \s__seq \__seq_item:n {#2} }
\seq_gput_left:cn 4696     \exp_not:f { \exp_after:wN \__seq_put_left_aux:w #1 }
\seq_gput_left:cV 4697   }
\seq_gput_left:cv 4698 }
\seq_gput_left:co 4699 \cs_new:Npn \__seq_put_left_aux:w \s__seq { \exp_stop_f: }
\seq_gput_left:cx 4700 \cs_generate_variant:Nn \seq_put_left:Nn { NV , Nv , No , Nx }
\__seq_put_left_aux:w 4701 \cs_generate_variant:Nn \seq_put_left:Nn { c , cV , cv , co , cx }
4702 \cs_generate_variant:Nn \seq_gput_left:Nn { NV , Nv , No , Nx }
4703 \cs_generate_variant:Nn \seq_gput_left:Nn { c , cV , cv , co , cx }

```

(End definition for `\seq_put_left:Nn`, `\seq_gput_left:Nn`, and `__seq_put_left_aux:w`. These functions are documented on page 65.)

```

\seq_put_right:Nn Since there is no trailing marker, adding an item to the right of a sequence simply means
\seq_put_right:NV wrapping it in \__seq_item:n.
\seq_put_right:Nv 4704 \cs_new_protected:Npn \seq_put_right:Nn #1#2
\seq_put_right:No 4705 { \tl_put_right:Nn #1 { \__seq_item:n {#2} } }
\seq_put_right:Nx 4706 \cs_new_protected:Npn \seq_gput_right:Nn #1#2
\seq_put_right:cn 4707 { \tl_gput_right:Nn #1 { \__seq_item:n {#2} } }
\seq_put_right:cV 4708 \cs_generate_variant:Nn \seq_gput_right:Nn { NV , Nv , No , Nx }
\seq_put_right:cv 4709 \cs_generate_variant:Nn \seq_gput_right:Nn { c , cV , cv , co , cx }
\seq_put_right:co 4710 \cs_generate_variant:Nn \seq_put_right:Nn { NV , Nv , No , Nx }
\seq_put_right:cx 4711 \cs_generate_variant:Nn \seq_put_right:Nn { c , cV , cv , co , cx }
\seq_gput_right:Nn (End definition for \seq_put_right:Nn and \seq_gput_right:Nn. These functions are documented on
\seq_gput_right:NV page 65.)
\seq_gput_right:Nv
\seq_gput_right:No
\seq_gput_right:Nx
\seq_gput_right:cn
\seq_gput_right:cV
\seq_gput_right:cv
\seq_gput_right:co
\seq_gput_right:cx

```

7.3 Modifying sequences

`__seq_wrap_item:n` This function converts its argument to a proper sequence item in an x-expansion context.

```
4712 \cs_new:Npn \__seq_wrap_item:n #1 { \exp_not:n { \__seq_item:n {#1} } }
```

(End definition for __seq_wrap_item:n.)

`\l__seq_remove_seq` An internal sequence for the removal routines.

```
4713 \seq_new:N \l__seq_remove_seq
```

(End definition for \l__seq_remove_seq.)

`\seq_remove_duplicates:N` Removing duplicates means making a new list then copying it.

`\seq_remove_duplicates:c`

```
4714 \cs_new_protected:Npn \seq_remove_duplicates:N
```

```
4715 { \__seq_remove_duplicates:NN \seq_set_eq:NN }
```

`\seq_gremove_duplicates:N`

```
4716 \cs_new_protected:Npn \seq_gremove_duplicates:N
```

`\seq_gremove_duplicates:c`

```
4717 { \__seq_remove_duplicates:NN \seq_gset_eq:NN }
```

`__seq_remove_duplicates:NN`

```
4718 \cs_new_protected:Npn \__seq_remove_duplicates:NN #1#2
```

```
4719 {
```

```
4720   \seq_clear:N \l__seq_remove_seq
```

```
4721   \seq_map_inline:Nn #2
```

```
4722   {
```

```
4723     \seq_if_in:NnF \l__seq_remove_seq {##1}
```

```
4724     { \seq_put_right:Nn \l__seq_remove_seq {##1} }
```

```
4725   }
```

```
4726   #1 #2 \l__seq_remove_seq
```

```
4727 }
```

```
4728 \cs_generate_variant:Nn \seq_remove_duplicates:N { c }
```

```
4729 \cs_generate_variant:Nn \seq_gremove_duplicates:N { c }
```

(End definition for \seq_remove_duplicates:N, \seq_gremove_duplicates:N, and __seq_remove_duplicates:NN. These functions are documented on page 68.)

`\seq_remove_all:Nn` The idea of the code here is to avoid a relatively expensive addition of items one at a time

`\seq_remove_all:cn` to an intermediate sequence. The approach taken is therefore similar to that in `__seq_`

`\seq_gremove_all:Nn` `pop_right:NNN`, using a “flexible” x-type expansion to do most of the work. As `\tl_`

`\seq_gremove_all:cn` `if_eq:nnT` is not expandable, a two-part strategy is needed. First, the x-type expansion

`__seq_remove_all_aux:NNn` uses `\str_if_eq:nnT` to find potential matches. If one is found, the expansion is halted

and the necessary set up takes place to use the `\tl_if_eq:NNT` test. The x-type is started

again, including all of the items copied already. This happens repeatedly until the entire

sequence has been scanned. The code is set up to avoid needing and intermediate scratch

list: the lead-off x-type expansion (`#1 #2 {#2}`) ensures that nothing is lost.

```
4730 \cs_new_protected:Npn \seq_remove_all:Nn
```

```
4731 { \__seq_remove_all_aux:NNn \tl_set:Nx }
```

```
4732 \cs_new_protected:Npn \seq_gremove_all:Nn
```

```
4733 { \__seq_remove_all_aux:NNn \tl_gset:Nx }
```

```
4734 \cs_new_protected:Npn \__seq_remove_all_aux:NNn #1#2#3
```

```
4735 {
```

```
4736   \__seq_push_item_def:n
```

```
4737   {
```

```
4738     \str_if_eq:nnT {##1} {#3}
```

```
4739     {
```

```
4740       \if_false: { \fi: }
```

```
4741       \tl_set:Nn \l__seq_internal_b_tl {##1}
```

```

4742         #1 #2
4743         { \if_false: } \fi:
4744         \exp_not:o {#2}
4745         \tl_if_eq:NNT \l__seq_internal_a_tl \l__seq_internal_b_tl
4746         { \use_none:nn }
4747     }
4748     \__seq_wrap_item:n {##1}
4749 }
4750 \tl_set:Nn \l__seq_internal_a_tl {#3}
4751 #1 #2 {#2}
4752 \__seq_pop_item_def:
4753 }
4754 \cs_generate_variant:Nn \seq_remove_all:Nn { c }
4755 \cs_generate_variant:Nn \seq_gremove_all:Nn { c }

```

(End definition for `\seq_remove_all:Nn`, `\seq_gremove_all:Nn`, and `__seq_remove_all_aux:NNn`. These functions are documented on page 68.)

```

\seq_reverse:N Previously, \seq_reverse:N was coded by collecting the items in reverse order after an
\seq_reverse:c \exp_stop_f: marker.
\seq_greverse:N
\seq_greverse:c
\__seq_reverse:NN
\__seq_reverse_item:nwn
\cs_new_protected:Npn \seq_reverse:N #1
{
  \cs_set_eq:NN \@@_item:n \@@_reverse_item:nw
  \tl_set:Nf #2 { #2 \exp_stop_f: }
}
\cs_new:Npn \@@_reverse_item:nw #1 #2 \exp_stop_f:
{
  #2 \exp_stop_f:
  \@@_item:n {#1}
}

```

At first, this seems optimal, since we can forget about each item as soon as it is placed after `\exp_stop_f:`. Unfortunately, \TeX 's usual tail recursion does not take place in this case: since the following `__seq_reverse_item:nw` only reads tokens until `\exp_stop_f:`, and never reads the `\@@_item:n {#1}` left by the previous call, \TeX cannot remove that previous call from the stack, and in particular must retain the various macro parameters in memory, until the end of the replacement text is reached. The stack is thus only flushed after all the `__seq_reverse_item:nw` are expanded. Keeping track of the arguments of all those calls uses up a memory quadratic in the length of the sequence. \TeX can then not cope with more than a few thousand items.

Instead, we collect the items in the argument of `\exp_not:n`. The previous calls are cleanly removed from the stack, and the memory consumption becomes linear.

```

4756 \cs_new_protected:Npn \seq_reverse:N
4757 { \__seq_reverse:NN \tl_set:Nx }
4758 \cs_new_protected:Npn \seq_greverse:N
4759 { \__seq_reverse:NN \tl_gset:Nx }
4760 \cs_new_protected:Npn \__seq_reverse:NN #1 #2
4761 {
4762   \cs_set_eq:NN \__seq_tmp:w \__seq_item:n
4763   \cs_set_eq:NN \__seq_item:n \__seq_reverse_item:nwn
4764   #1 #2 { #2 \exp_not:n { } }
4765   \cs_set_eq:NN \__seq_item:n \__seq_tmp:w

```

```

4766 }
4767 \cs_new:Npn \__seq_reverse_item:nwn #1 #2 \exp_not:n #3
4768 {
4769     #2
4770     \exp_not:n { \__seq_item:n {#1} #3 }
4771 }
4772 \cs_generate_variant:Nn \seq_reverse:N { c }
4773 \cs_generate_variant:Nn \seq_greverse:N { c }

```

(End definition for `\seq_reverse:N` and others. These functions are documented on page 68.)

`\seq_sort:Nn` Implemented in `l3sort`.

`\seq_sort:cn`

`\seq_gsort:Nn` (End definition for `\seq_sort:Nn` and `\seq_gsort:Nn`. These functions are documented on page 68.)

`\seq_gsort:cn`

7.4 Sequence conditionals

`\seq_if_empty_p:N` Similar to token lists, we compare with the empty sequence.

```

\seq_if_empty_p:c 4774 \prg_new_conditional:Npnn \seq_if_empty:N #1 { p , T , F , TF }
\seq_if_empty:NTF 4775 {
\seq_if_empty:cTF 4776     \if_meaning:w #1 \c_empty_seq
4777     \prg_return_true:
4778     \else:
4779     \prg_return_false:
4780     \fi:
4781 }
4782 \cs_generate_variant:Nn \seq_if_empty_p:N { c }
4783 \cs_generate_variant:Nn \seq_if_empty:NT { c }
4784 \cs_generate_variant:Nn \seq_if_empty:NF { c }
4785 \cs_generate_variant:Nn \seq_if_empty:NTF { c }

```

(End definition for `\seq_if_empty:NTF`. This function is documented on page 68.)

`\seq_if_in:NnTF` The approach here is to define `__seq_item:n` to compare its argument with the test sequence. If the two items are equal, the mapping is terminated and `\group_end: \prg_return_true:` is inserted after skipping over the rest of the recursion. On the other hand, if there is no match then the loop breaks, returning `\prg_return_false:`. Everything is inside a group so that `__seq_item:n` is preserved in nested situations.

```

\seq_if_in:NvTF 4786 \prg_new_protected_conditional:Npnn \seq_if_in:Nn #1#2
\seq_if_in:NvTF 4787 { T , F , TF }
\seq_if_in:NoTF 4788 {
\seq_if_in:NxTF 4789     \group_begin:
\seq_if_in:cnTF 4790     \tl_set:Nn \l__seq_internal_a_tl {#2}
\seq_if_in:cVTF 4791     \cs_set_protected:Npn \__seq_item:n ##1
\seq_if_in:cvTF 4792     {
\seq_if_in:coTF 4793         \tl_set:Nn \l__seq_internal_b_tl {##1}
\seq_if_in:cxTF 4794         \if_meaning:w \l__seq_internal_a_tl \l__seq_internal_b_tl
4795         \exp_after:wN \__seq_if_in:
4796         \fi:
4797     }
4798     #1
4799     \group_end:
4800     \prg_return_false:
4801     \__prg_break_point:

```



```

4802 }
4803 \cs_new:Npn \__seq_if_in:
4804 { \__prg_break:n { \group_end: \prg_return_true: } }
4805 \cs_generate_variant:Nn \seq_if_in:NnT { NV , Nv , No , Nx }
4806 \cs_generate_variant:Nn \seq_if_in:NnT { c , cV , cv , co , cx }
4807 \cs_generate_variant:Nn \seq_if_in:NnF { NV , Nv , No , Nx }
4808 \cs_generate_variant:Nn \seq_if_in:NnF { c , cV , cv , co , cx }
4809 \cs_generate_variant:Nn \seq_if_in:NnTF { NV , Nv , No , Nx }
4810 \cs_generate_variant:Nn \seq_if_in:NnTF { c , cV , cv , co , cx }

```

(End definition for `\seq_if_in:NnTF` and `__seq_if_in:`. This function is documented on page 68.)

7.5 Recovering data from sequences

`__seq_pop:NNNN` The two pop functions share their emptiness tests. We also use a common emptiness test
`__seq_pop_TF:NNNN` for all branching get and pop functions.

```

4811 \cs_new_protected:Npn \__seq_pop:NNNN #1#2#3#4
4812 {
4813   \if_meaning:w #3 \c_empty_seq
4814     \tl_set:Nn #4 { \q_no_value }
4815   \else:
4816     #1#2#3#4
4817   \fi:
4818 }
4819 \cs_new_protected:Npn \__seq_pop_TF:NNNN #1#2#3#4
4820 {
4821   \if_meaning:w #3 \c_empty_seq
4822     % \tl_set:Nn #4 { \q_no_value }
4823     \prg_return_false:
4824   \else:
4825     #1#2#3#4
4826     \prg_return_true:
4827   \fi:
4828 }

```

(End definition for `__seq_pop:NNNN` and `__seq_pop_TF:NNNN`.)

`\seq_get_left:NN` Getting an item from the left of a sequence is pretty easy: just trim off the first item
`\seq_get_left:cN` after `__seq_item:n` at the start. We append a `\q_no_value` item to cover the case of
`__seq_get_left:wnw` an empty sequence

```

4829 \cs_new_protected:Npn \seq_get_left:NN #1#2
4830 {
4831   \tl_set:Nx #2
4832   {
4833     \exp_after:wN \__seq_get_left:wnw
4834     #1 \__seq_item:n { \q_no_value } \q_stop
4835   }
4836 }
4837 \cs_new:Npn \__seq_get_left:wnw #1 \__seq_item:n #2#3 \q_stop
4838 { \exp_not:n {#2} }
4839 \cs_generate_variant:Nn \seq_get_left:NN { c }

```

(End definition for `\seq_get_left:NN` and `__seq_get_left:wnw`. This function is documented on page 65.)

`\seq_pop_left:NN`
`\seq_pop_left:cN`
`\seq_gpop_left:NN`
`\seq_gpop_left:cN`
`__seq_pop_left:NNN`
`__seq_pop_left:wnwNNN`

The approach to popping an item is pretty similar to that to get an item, with the only difference being that the sequence itself has to be redefined. This makes it more sensible to use an auxiliary function for the local and global cases.

```

4840 \cs_new_protected:Npn \seq_pop_left:NN
4841 { \__seq_pop:NNNN \__seq_pop_left:NNN \tl_set:Nn }
4842 \cs_new_protected:Npn \seq_gpop_left:NN
4843 { \__seq_pop:NNNN \__seq_pop_left:NNN \tl_gset:Nn }
4844 \cs_new_protected:Npn \__seq_pop_left:NNN #1#2#3
4845 { \exp_after:wN \__seq_pop_left:wnwNNN #2 \q_stop #1#2#3 }
4846 \cs_new_protected:Npn \__seq_pop_left:wnwNNN
4847 #1 \__seq_item:n #2#3 \q_stop #4#5#6
4848 {
4849 #4 #5 { #1 #3 }
4850 \tl_set:Nn #6 {#2}
4851 }
4852 \cs_generate_variant:Nn \seq_pop_left:NN { c }
4853 \cs_generate_variant:Nn \seq_gpop_left:NN { c }

```

(End definition for `\seq_pop_left:NN` and others. These functions are documented on page 66.)

`\seq_get_right:NN`
`\seq_get_right:cN`
`__seq_get_right_loop:nn`

First remove `\s__seq` and prepend `\q_no_value`, then take two arguments at a time. Before the right-hand end of the sequence, this is a brace group followed by `__seq_item:n`, both removed by `\use_none:nn`. At the end of the sequence, the two question marks are taken by `\use_none:nn`, and the assignment is placed before the right-most item. In the next iteration, `__seq_get_right_loop:nn` receives two empty arguments, and `\use_none:nn` stops the loop.

```

4854 \cs_new_protected:Npn \seq_get_right:NN #1#2
4855 {
4856 \exp_after:wN \use_i_ii:nnn
4857 \exp_after:wN \__seq_get_right_loop:nn
4858 \exp_after:wN \q_no_value
4859 #1
4860 { ?? \tl_set:Nn #2 }
4861 { } { }
4862 }
4863 \cs_new_protected:Npn \__seq_get_right_loop:nn #1#2
4864 {
4865 \use_none:nn #2 {#1}
4866 \__seq_get_right_loop:nn
4867 }
4868 \cs_generate_variant:Nn \seq_get_right:NN { c }

```

(End definition for `\seq_get_right:NN` and `__seq_get_right_loop:nn`. This function is documented on page 66.)

`\seq_pop_right:NN`
`\seq_pop_right:cN`
`\seq_gpop_right:NN`
`\seq_gpop_right:cN`
`__seq_pop_right:NNN`
`__seq_pop_right_loop:nn`

The approach to popping from the right is a bit more involved, but does use some of the same ideas as getting from the right. What is needed is a “flexible length” way to set a token list variable. This is supplied by the `{\if_false:}\fi:... construct. Using an x-type expansion and a “non-expanding” definition for __seq_item:n, the left-most $n - 1$ entries in a sequence of n items are stored back in the sequence. That needs a loop of unknown length, hence using the strange \if_false: way of including braces. When the last item of the sequence is reached, the closing brace for the assignment is inserted, and \tl_set:Nn #3 is inserted`

in front of the final entry. This therefore does the pop assignment. One more iteration is performed, with an empty argument and `\use_none:nn`, which finally stops the loop.

```

4869 \cs_new_protected:Npn \seq_pop_right:NN
4870 { \__seq_pop:NNNN \__seq_pop_right:NNN \tl_set:Nx }
4871 \cs_new_protected:Npn \seq_gpop_right:NN
4872 { \__seq_pop:NNNN \__seq_pop_right:NNN \tl_gset:Nx }
4873 \cs_new_protected:Npn \__seq_pop_right:NNN #1#2#3
4874 {
4875   \cs_set_eq:NN \__seq_tmp:w \__seq_item:n
4876   \cs_set_eq:NN \__seq_item:n \scan_stop:
4877   #1 #2
4878   { \if_false: } \fi: \s__seq
4879     \exp_after:wN \use_i:nnn
4880     \exp_after:wN \__seq_pop_right_loop:nn
4881     #2
4882     {
4883       \if_false: { \fi: }
4884       \tl_set:Nx #3
4885     }
4886     { } \use_none:nn
4887     \cs_set_eq:NN \__seq_item:n \__seq_tmp:w
4888   }
4889   \cs_new:Npn \__seq_pop_right_loop:nn #1#2
4890   {
4891     #2 { \exp_not:n {#1} }
4892     \__seq_pop_right_loop:nn
4893   }
4894   \cs_generate_variant:Nn \seq_pop_right:NN { c }
4895   \cs_generate_variant:Nn \seq_gpop_right:NN { c }

```

(End definition for `\seq_pop_right:NN` and others. These functions are documented on page 66.)

`\seq_get_left:NNTF` Getting from the left or right with a check on the results. The first argument to `__seq_pop_TF:NNNN` is left unused.

```

\seq_get_left:cNTF
\seq_get_right:NNTF
\seq_get_right:cNTF
4896 \prg_new_protected_conditional:Npnn \seq_get_left:NN #1#2 { T , F , TF }
4897 { \__seq_pop_TF:NNNN \prg_do_nothing: \seq_get_left:NN #1#2 }
4898 \prg_new_protected_conditional:Npnn \seq_get_right:NN #1#2 { T , F , TF }
4899 { \__seq_pop_TF:NNNN \prg_do_nothing: \seq_get_right:NN #1#2 }
4900 \cs_generate_variant:Nn \seq_get_left:NNT { c }
4901 \cs_generate_variant:Nn \seq_get_left:NNF { c }
4902 \cs_generate_variant:Nn \seq_get_left:NNTF { c }
4903 \cs_generate_variant:Nn \seq_get_right:NNT { c }
4904 \cs_generate_variant:Nn \seq_get_right:NNF { c }
4905 \cs_generate_variant:Nn \seq_get_right:NNTF { c }

```

(End definition for `\seq_get_left:NNTF` and `\seq_get_right:NNTF`. These functions are documented on page 67.)

`\seq_pop_left:NNTF` More or less the same for popping.

```

\seq_pop_left:cNTF
\seq_gpop_left:NNTF
\seq_gpop_left:cNTF
\seq_pop_right:NNTF
\seq_pop_right:cNTF
\seq_gpop_right:NNTF
\seq_gpop_right:cNTF
4906 \prg_new_protected_conditional:Npnn \seq_pop_left:NN #1#2 { T , F , TF }
4907 { \__seq_pop_TF:NNNN \__seq_pop_left:NNN \tl_set:Nn #1 #2 }
4908 \prg_new_protected_conditional:Npnn \seq_gpop_left:NN #1#2 { T , F , TF }
4909 { \__seq_pop_TF:NNNN \__seq_pop_left:NNN \tl_gset:Nn #1 #2 }
4910 \prg_new_protected_conditional:Npnn \seq_pop_right:NN #1#2 { T , F , TF }

```

```

4911 { \__seq_pop_TF:NNNN \__seq_pop_right:NNN \tl_set:Nx #1 #2 }
4912 \prg_new_protected_conditional:Npnn \seq_gpop_right:NN #1#2 { T , F , TF }
4913 { \__seq_pop_TF:NNNN \__seq_pop_right:NNN \tl_gset:Nx #1 #2 }
4914 \cs_generate_variant:Nn \seq_pop_left:NNT { c }
4915 \cs_generate_variant:Nn \seq_pop_left:NNF { c }
4916 \cs_generate_variant:Nn \seq_pop_left:NNTF { c }
4917 \cs_generate_variant:Nn \seq_gpop_left:NNT { c }
4918 \cs_generate_variant:Nn \seq_gpop_left:NNF { c }
4919 \cs_generate_variant:Nn \seq_gpop_left:NNTF { c }
4920 \cs_generate_variant:Nn \seq_pop_right:NNT { c }
4921 \cs_generate_variant:Nn \seq_pop_right:NNF { c }
4922 \cs_generate_variant:Nn \seq_pop_right:NNTF { c }
4923 \cs_generate_variant:Nn \seq_gpop_right:NNT { c }
4924 \cs_generate_variant:Nn \seq_gpop_right:NNF { c }
4925 \cs_generate_variant:Nn \seq_gpop_right:NNTF { c }

```

(End definition for `\seq_pop_left:NNTF` and others. These functions are documented on page 67.)

`\seq_item:Nn` The idea here is to find the offset of the item from the left, then use a loop to grab the correct item. If the resulting offset is too large, then the stop code `{ ? __prg_break: } { }` is used by the auxiliary, terminating the loop and returning nothing at all.

```

\seq_item:cn
\__seq_item:wNn
\__seq_item:nN
\__seq_item:nnn
4926 \cs_new:Npn \seq_item:Nn #1
4927 { \exp_after:wN \__seq_item:wNn #1 \q_stop #1 }
4928 \cs_new:Npn \__seq_item:wNn \s__seq #1 \q_stop #2#3
4929 {
4930   \exp_args:Nf \__seq_item:nnn
4931   { \exp_args:Nf \__seq_item:nN { \int_eval:n {#3} } #2 }
4932   #1
4933   { ? \__prg_break: } { }
4934   \__prg_break_point:
4935 }
4936 \cs_new:Npn \__seq_item:nN #1#2
4937 {
4938   \int_compare:nNnTF {#1} < 0
4939   { \int_eval:n { \seq_count:N #2 + 1 + #1 } }
4940   {#1}
4941 }
4942 \cs_new:Npn \__seq_item:nnn #1#2#3
4943 {
4944   \use_none:n #2
4945   \int_compare:nNnTF {#1} = 1
4946   { \__prg_break:n { \exp_not:n {#3} } }
4947   { \exp_args:Nf \__seq_item:nnn { \int_eval:n { #1 - 1 } } }
4948 }
4949 \cs_generate_variant:Nn \seq_item:Nn { c }

```

(End definition for `\seq_item:Nn` and others. This function is documented on page 66.)

7.6 Mapping to sequences

`\seq_map_break:` To break a function, the special token `__prg_break_point:Nn` is used to find the end of the code. Any ending code is then inserted before the return value of `\seq_map_break:n` is inserted.

```

4950 \cs_new:Npn \seq_map_break:
4951   { \__prg_map_break:Nn \seq_map_break: { } }
4952 \cs_new:Npn \seq_map_break:n
4953   { \__prg_map_break:Nn \seq_map_break: }

```

(End definition for `\seq_map_break:` and `\seq_map_break:n`. These functions are documented on page 69.)

`\seq_map_function:NN` The idea here is to apply the code of #2 to each item in the sequence without altering the definition of `__seq_item:n`. This is done as by noting that every odd token in the sequence must be `__seq_item:n`, which can be gobbled by `\use_none:n`. At the end of the loop, #2 is instead ? `\seq_map_break:`, which therefore breaks the loop without needing to do a (relatively-expensive) quark test.

```

4954 \cs_new:Npn \seq_map_function:NN #1#2
4955   {
4956     \exp_after:wN \use_i_ii:nnn
4957     \exp_after:wN \__seq_map_function:NNn
4958     \exp_after:wN #2
4959     #1
4960     { ? \seq_map_break: } { }
4961     \__prg_break_point:Nn \seq_map_break: { }
4962   }
4963 \cs_new:Npn \__seq_map_function:NNn #1#2#3
4964   {
4965     \use_none:n #2
4966     #1 {#3}
4967     \__seq_map_function:NNn #1
4968   }
4969 \cs_generate_variant:Nn \seq_map_function:NN { c }

```

(End definition for `\seq_map_function:NN` and `__seq_map_function:NNn`. This function is documented on page 69.)

`__seq_push_item_def:n` The definition of `__seq_item:n` needs to be saved and restored at various points within the mapping and manipulation code. That is handled here: as always, this approach uses global assignments.

```

\__seq_push_item_def:n
\__seq_push_item_def:x
\__seq_push_item_def:
\__seq_pop_item_def:
4970 \cs_new_protected:Npn \__seq_push_item_def:n
4971   {
4972     \__seq_push_item_def:
4973     \cs_gset:Npn \__seq_item:n ##1
4974   }
4975 \cs_new_protected:Npn \__seq_push_item_def:x
4976   {
4977     \__seq_push_item_def:
4978     \cs_gset:Npx \__seq_item:n ##1
4979   }
4980 \cs_new_protected:Npn \__seq_push_item_def:
4981   {
4982     \int_gincr:N \g__prg_map_int
4983     \cs_gset_eq:cN { __prg_map_ \int_use:N \g__prg_map_int :w }
4984     \__seq_item:n
4985   }
4986 \cs_new_protected:Npn \__seq_pop_item_def:
4987   {

```

```

4988 \cs_gset_eq:Nc \__seq_item:n
4989 { __prg_map_ \int_use:N \g__prg_map_int :w }
4990 \int_gdecr:N \g__prg_map_int
4991 }

```

(End definition for __seq_push_item_def:n, __seq_push_item_def:, and __seq_pop_item_def:.)

\seq_map_inline:Nn The idea here is that __seq_item:n is already “applied” to each item in a sequence, and so an in-line mapping is just a case of redefining __seq_item:n.

\seq_map_inline:cn

```

4992 \cs_new_protected:Npn \seq_map_inline:Nn #1#2
4993 {
4994   \__seq_push_item_def:n {#2}
4995   #1
4996   \__prg_break_point:Nn \seq_map_break: { \__seq_pop_item_def: }
4997 }
4998 \cs_generate_variant:Nn \seq_map_inline:Nn { c }

```

(End definition for \seq_map_inline:Nn. This function is documented on page 69.)

\seq_map_variable:NNn This is just a specialised version of the in-line mapping function, using an x-type expansion for the code set up so that the number of # tokens required is as expected.

\seq_map_variable:Ncn

\seq_map_variable:cNn

\seq_map_variable:ccn

```

4999 \cs_new_protected:Npn \seq_map_variable:NNn #1#2#3
5000 {
5001   \__seq_push_item_def:x
5002   {
5003     \tl_set:Nn \exp_not:N #2 {##1}
5004     \exp_not:n {#3}
5005   }
5006   #1
5007   \__prg_break_point:Nn \seq_map_break: { \__seq_pop_item_def: }
5008 }
5009 \cs_generate_variant:Nn \seq_map_variable:NNn { Nc }
5010 \cs_generate_variant:Nn \seq_map_variable:NNn { c , cc }

```

(End definition for \seq_map_variable:NNn. This function is documented on page 69.)

\seq_count:N Counting the items in a sequence is done using the same approach as for other count functions: turn each entry into a +1 then use integer evaluation to actually do the mathematics.

\seq_count:c

__seq_count:n

```

5011 \cs_new:Npn \seq_count:N #1
5012 {
5013   \int_eval:n
5014   {
5015     0
5016     \seq_map_function:NN #1 \__seq_count:n
5017   }
5018 }
5019 \cs_new:Npn \__seq_count:n #1 { + 1 }
5020 \cs_generate_variant:Nn \seq_count:N { c }

```

(End definition for \seq_count:N and __seq_count:n. This function is documented on page 70.)

7.7 Using sequences

`\seq_use:Nnnn` See `\clist_use:Nnnn` for a general explanation. The main difference is that we use `_seq_item:n` as a delimiter rather than commas. We also need to add `_seq_item:n` at various places, and `\s__seq`.

```

\seq_use:cn
\__seq_use:NNnNnn
\__seq_use_setup:w
\__seq_use:nwwwnwn
\__seq_use:nwwn
\seq_use:Nn
\seq_use:cn
5021 \cs_new:Npn \seq_use:Nnnn #1#2#3#4
5022 {
5023   \seq_if_exist:NTF #1
5024   {
5025     \int_case:nnF { \seq_count:N #1 }
5026     {
5027       { 0 } { }
5028       { 1 } { \exp_after:wN \__seq_use:NNnNnn #1 ? { } { } }
5029       { 2 } { \exp_after:wN \__seq_use:NNnNnn #1 {#2} }
5030     }
5031     {
5032       \exp_after:wN \__seq_use_setup:w #1 \_seq_item:n
5033       \q_mark { \__seq_use:nwwwnwn {#3} }
5034       \q_mark { \__seq_use:nwwn {#4} }
5035       \q_stop { }
5036     }
5037   }
5038   {
5039     \_msg_kernel_expandable_error:nnn
5040     { kernel } { bad-variable } {#1}
5041   }
5042 }
5043 \cs_generate_variant:Nn \seq_use:Nnnn { c }
5044 \cs_new:Npn \__seq_use:NNnNnn #1#2#3#4#5#6 { \exp_not:n { #3 #6 #5 } }
5045 \cs_new:Npn \__seq_use_setup:w \s__seq { \__seq_use:nwwwnwn { } }
5046 \cs_new:Npn \__seq_use:nwwwnwn
5047   #1 \_seq_item:n #2 \_seq_item:n #3 \_seq_item:n #4#5
5048   \q_mark #6#7 \q_stop #8
5049   {
5050     #6 \_seq_item:n {#3} \_seq_item:n {#4} #5
5051     \q_mark {#6} #7 \q_stop { #8 #1 #2 }
5052   }
5053 \cs_new:Npn \__seq_use:nwwn #1 \_seq_item:n #2 #3 \q_stop #4
5054   { \exp_not:n { #4 #1 #2 } }
5055 \cs_new:Npn \seq_use:Nn #1#2
5056   { \seq_use:Nnnn #1 {#2} {#2} {#2} }
5057 \cs_generate_variant:Nn \seq_use:Nn { c }

```

(End definition for `\seq_use:Nnnn` and others. These functions are documented on page 70.)

7.8 Sequence stacks

The same functions as for sequences, but with the correct naming.

`\seq_push:Nn` Pushing to a sequence is the same as adding on the left.

```

\seq_push:NV
\seq_push:Nv
\seq_push:No
\seq_push:Nx
\seq_push:cn
\seq_push:cV
\seq_push:cV
\seq_push:co
\seq_push:cx
\seq_gpush:Nn
\seq_gpush:NV
\seq_gpush:Nv
\seq_gpush:No
\seq_gpush:Nx

```

```

5062 \cs_new_eq:NN \seq_push:Nx \seq_put_left:Nx
5063 \cs_new_eq:NN \seq_push:cn \seq_put_left:cn
5064 \cs_new_eq:NN \seq_push:cV \seq_put_left:cV
5065 \cs_new_eq:NN \seq_push:cv \seq_put_left:cv
5066 \cs_new_eq:NN \seq_push:co \seq_put_left:co
5067 \cs_new_eq:NN \seq_push:cx \seq_put_left:cx
5068 \cs_new_eq:NN \seq_gpush:Nn \seq_gput_left:Nn
5069 \cs_new_eq:NN \seq_gpush:Nv \seq_gput_left:Nv
5070 \cs_new_eq:NN \seq_gpush:Nv \seq_gput_left:Nv
5071 \cs_new_eq:NN \seq_gpush:No \seq_gput_left:No
5072 \cs_new_eq:NN \seq_gpush:Nx \seq_gput_left:Nx
5073 \cs_new_eq:NN \seq_gpush:cn \seq_gput_left:cn
5074 \cs_new_eq:NN \seq_gpush:cV \seq_gput_left:cV
5075 \cs_new_eq:NN \seq_gpush:cv \seq_gput_left:cv
5076 \cs_new_eq:NN \seq_gpush:co \seq_gput_left:co
5077 \cs_new_eq:NN \seq_gpush:cx \seq_gput_left:cx

```

(End definition for `\seq_push:Nn` and `\seq_gpush:Nn`. These functions are documented on page 72.)

`\seq_get:NN` In most cases, getting items from the stack does not need to specify that this is from the left. So alias are provided.

```

\seq_get:cn
\seq_pop:NN
\seq_pop:cn
\seq_gpop:NN
\seq_gpop:cn
5078 \cs_new_eq:NN \seq_get:NN \seq_get_left:NN
5079 \cs_new_eq:NN \seq_get:cn \seq_get_left:cn
5080 \cs_new_eq:NN \seq_pop:NN \seq_pop_left:NN
5081 \cs_new_eq:NN \seq_pop:cn \seq_pop_left:cn
5082 \cs_new_eq:NN \seq_gpop:NN \seq_gpop_left:NN
5083 \cs_new_eq:NN \seq_gpop:cn \seq_gpop_left:cn

```

(End definition for `\seq_get:NN`, `\seq_pop:NN`, and `\seq_gpop:NN`. These functions are documented on page 71.)

`\seq_get:NNTF` More copies.

```

\seq_get:cnTF
\seq_pop:NNTF
\seq_pop:cnTF
\seq_gpop:NNTF
\seq_gpop:cnTF
5084 \prg_new_eq_conditional:NNn \seq_get:NN \seq_get_left:NN { T , F , TF }
5085 \prg_new_eq_conditional:NNn \seq_get:cn \seq_get_left:cn { T , F , TF }
5086 \prg_new_eq_conditional:NNn \seq_pop:NN \seq_pop_left:NN { T , F , TF }
5087 \prg_new_eq_conditional:NNn \seq_pop:cn \seq_pop_left:cn { T , F , TF }
5088 \prg_new_eq_conditional:NNn \seq_gpop:NN \seq_gpop_left:NN { T , F , TF }
5089 \prg_new_eq_conditional:NNn \seq_gpop:cn \seq_gpop_left:cn { T , F , TF }

```

(End definition for `\seq_get:NNTF`, `\seq_pop:NNTF`, and `\seq_gpop:NNTF`. These functions are documented on page 71.)

7.9 Viewing sequences

`\seq_show:N` Apply the general `\msg_show:nnnnnn`.

```

\seq_show:c
\seq_log:N
\seq_log:c
\__seq_show:NN
5090 \cs_new_protected:Npn \seq_show:N { \__seq_show:NN \msg_show:nnxxxx }
5091 \cs_generate_variant:Nn \seq_show:N { c }
5092 \cs_new_protected:Npn \seq_log:N { \__seq_show:NN \msg_log:nnxxxx }
5093 \cs_generate_variant:Nn \seq_log:N { c }
5094 \cs_new_protected:Npn \__seq_show:NN #1#2
5095 {
5096   \__kernel_check_defined:NT #2
5097   {
5098     #1 { LaTeX/kernel } { show-seq }
5099     { \token_to_str:N #2 }

```



```

5100         { \seq_map_function:NN #2 \msg_show_item:n }
5101         { } { }
5102     }
5103 }

```

(End definition for `\seq_show:N`, `\seq_log:N`, and `__seq_show:NN`. These functions are documented on page 74.)

7.10 Scratch sequences

`\l_tmpa_seq` Temporary comma list variables.

```

\l_tmpb_seq 5104 \seq_new:N \l_tmpa_seq
\g_tmpa_seq 5105 \seq_new:N \l_tmpb_seq
\g_tmpb_seq 5106 \seq_new:N \g_tmpa_seq
5107 \seq_new:N \g_tmpb_seq

```

(End definition for `\l_tmpa_seq` and others. These variables are documented on page 74.)

```
5108 </initex | package>
```

8 l3int implementation

```
5109 <*initex | package>
```

```
5110 <@@=int>
```

The following test files are used for this code: `m3int001`, `m3int002`, `m3int03`.

`\c_max_register_int` Done in l3basics.

(End definition for `\c_max_register_int`. This variable is documented on page 85.)

`__int_to_roman:w` Done in l3basics.

`\if_int_compare:w` (End definition for `__int_to_roman:w` and `\if_int_compare:w`. This function is documented on page 86.)

`\or:` Done in l3basics.

(End definition for `\or:`. This function is documented on page 86.)

`__int_value:w` Here are the remaining primitives for number comparisons and expressions.

```

\__int_eval:w 5111 \cs_new_eq:NN \__int_value:w \tex_number:D
\__int_eval_end: 5112 \cs_new_eq:NN \__int_eval:w \etex_numexpr:D
\if_int_odd:w 5113 \cs_new_eq:NN \__int_eval_end: \tex_relax:D
\if_case:w 5114 \cs_new_eq:NN \if_int_odd:w \tex_ifodd:D
5115 \cs_new_eq:NN \if_case:w \tex_ifcase:D

```

(End definition for `__int_value:w` and others. These functions are documented on page 86.)

8.1 Integer expressions

\int_eval:n Wrapper for `__int_eval:w`: can be used in an integer expression or directly in the input stream. When debugging, use parentheses to catch early termination.

```
5116 \__debug_patch_args:nNNpn
5117 { { \__debug_chk_expr:nNnN {#1} \__int_eval:w { } \int_eval:n } }
5118 \cs_new:Npn \int_eval:n #1
5119 { \__int_value:w \__int_eval:w #1 \__int_eval_end: }
```

(End definition for `\int_eval:n`. This function is documented on page 75.)

__int_eval:n Only differ from `\int_eval:n` by the absence of `__int_value:w`, so as to produce an internal integer rather than expanding into characters. This is for use in other modules.

```
5120 \__debug_patch_args:nNNpn
5121 { { \__debug_chk_expr:nNnN {#1} \__int_eval:w { } \__int_eval:n } }
5122 \cs_new:Npn \__int_eval:n #1 { \__int_eval:w #1 \__int_eval_end: }
```

(End definition for `__int_eval:n`.)

\int_abs:n Functions for min, max, and absolute value with only one evaluation. The absolute value is obtained by removing a leading sign if any. All three functions expand in two steps.

__int_abs:N

\int_max:nn

\int_min:nn

__int_maxmin:wwN

```
5123 \__debug_patch_args:nNNpn
5124 { { \__debug_chk_expr:nNnN {#1} \__int_eval:w { } \int_abs:n } }
5125 \cs_new:Npn \int_abs:n #1
5126 {
5127   \__int_value:w \exp_after:wN \__int_abs:N
5128   \__int_value:w \__int_eval:w #1 \__int_eval_end:
5129   \exp_stop_f:
5130 }
5131 \cs_new:Npn \__int_abs:N #1
5132 { \if_meaning:w - #1 \else: \exp_after:wN #1 \fi: }
5133 \__debug_patch_args:nNNpn
5134 {
5135   { \__debug_chk_expr:nNnN {#1} \__int_eval:w { } \int_max:nn }
5136   { \__debug_chk_expr:nNnN {#2} \__int_eval:w { } \int_max:nn }
5137 }
5138 \cs_set:Npn \int_max:nn #1#2
5139 {
5140   \__int_value:w \exp_after:wN \__int_maxmin:wwN
5141   \__int_value:w \__int_eval:w #1 \exp_after:wN ;
5142   \__int_value:w \__int_eval:w #2 ;
5143   >
5144   \exp_stop_f:
5145 }
5146 \__debug_patch_args:nNNpn
5147 {
5148   { \__debug_chk_expr:nNnN {#1} \__int_eval:w { } \int_min:nn }
5149   { \__debug_chk_expr:nNnN {#2} \__int_eval:w { } \int_min:nn }
5150 }
5151 \cs_set:Npn \int_min:nn #1#2
5152 {
5153   \__int_value:w \exp_after:wN \__int_maxmin:wwN
5154   \__int_value:w \__int_eval:w #1 \exp_after:wN ;
5155   \__int_value:w \__int_eval:w #2 ;
```

```

5156         <
5157         \exp_stop_f:
5158     }
5159 \cs_new:Npn \__int_maxmin:wwN #1 ; #2 ; #3
5160 {
5161     \if_int_compare:w #1 #3 #2 ~
5162         #1
5163     \else:
5164         #2
5165     \fi:
5166 }

```

(End definition for `\int_abs:n` and others. These functions are documented on page 75.)

`\int_div_truncate:nn` As `__int_eval:w` rounds the result of a division we also provide a version that truncates the result. We use an auxiliary to make sure numerator and denominator are only evaluated once: this comes in handy when those are more expressions are expensive to evaluate (e.g., `\tl_count:n`). If the numerator `#1#2` is 0, then we divide 0 by the denominator (this ensures that 0/0 is correctly reported as an error). Otherwise, shift the numerator `#1#2` towards 0 by $(| \#3\#4 | - 1)/2$, which we round away from zero. It turns out that this quantity exactly compensates the difference between ε -TeX's rounding and the truncating behaviour that we want. The details are thanks to Heiko Oberdiek: getting things right in all cases is not so easy.

```

5167 \__debug_patch_args:nNnNpn
5168 {
5169     { \__debug_chk_expr:nNnN {#1} \__int_eval:w { } \int_div_truncate:nn }
5170     { \__debug_chk_expr:nNnN {#2} \__int_eval:w { } \int_div_truncate:nn }
5171 }
5172 \cs_new:Npn \int_div_truncate:nn #1#2
5173 {
5174     \__int_value:w \__int_eval:w
5175     \exp_after:wN \__int_div_truncate:NwNw
5176     \__int_value:w \__int_eval:w #1 \exp_after:wN ;
5177     \__int_value:w \__int_eval:w #2 ;
5178     \__int_eval_end:
5179 }
5180 \cs_new:Npn \__int_div_truncate:NwNw #1#2; #3#4;
5181 {
5182     \if_meaning:w 0 #1
5183     0
5184     \else:
5185     (
5186         #1#2
5187         \if_meaning:w - #1 + \else: - \fi:
5188         ( \if_meaning:w - #3 - \fi: #3#4 - 1 ) / 2
5189     )
5190     \fi:
5191     / #3#4
5192 }

```

For the sake of completeness:

```

5193 \cs_new:Npn \int_div_round:nn #1#2
5194 { \__int_value:w \__int_eval:w ( #1 ) / ( #2 ) \__int_eval_end: }

```

Finally there's the modulus operation.

```

5195 \__debug_patch_args:nNNpn
5196 {
5197   { \__debug_chk_expr:nNnN {#1} \__int_eval:w { } \int_mod:nn }
5198   { \__debug_chk_expr:nNnN {#2} \__int_eval:w { } \int_mod:nn }
5199 }
5200 \cs_new:Npn \int_mod:nn #1#2
5201 {
5202   \__int_value:w \__int_eval:w \exp_after:wN \__int_mod:ww
5203   \__int_value:w \__int_eval:w #1 \exp_after:wN ;
5204   \__int_value:w \__int_eval:w #2 ;
5205   \__int_eval_end:
5206 }
5207 \cs_new:Npn \__int_mod:ww #1; #2;
5208 { #1 - ( \__int_div_truncate:NwNw #1 ; #2 ; ) * #2 }

```

(End definition for `\int_div_truncate:nn` and others. These functions are documented on page 76.)

8.2 Creating and initialising integers

`\int_new:N` Two ways to do this: one for the format and one for the L^AT_EX 2_ε package. In plain T_EX, `\int_new:c` `\newcount` (and other allocators) are `\outer:` to allow the code here to work in “generic” mode this is therefore accessed by name. (The same applies to `\newbox`, `\newdimen` and so on.)

```

5209 <*package>
5210 \cs_new_protected:Npn \int_new:N #1
5211 {
5212   \__chk_if_free_cs:N #1
5213   \cs:w newcount \cs_end: #1
5214 }
5215 </package>
5216 \cs_generate_variant:Nn \int_new:N { c }

```

(End definition for `\int_new:N`. This function is documented on page 76.)

`\int_const:Nn` As stated, most constants can be defined as `\chardef` or `\mathchardef` but that's engine dependent. As a result, there is some set up code to determine what can be done. No full engine testing just yet so everything is a little awkward. We cannot use `\int_gset:Nn` `\int_const:cn` because (when `check-declarations` is enabled) this runs some checks that constants would fail.

```

5217 \__debug_patch_args:nnnNNpn
5218 { \__debug_chk_var_scope:NN c #1 }
5219 { }
5220 { {#1} { \__debug_chk_expr:nNnN {#2} \__int_eval:w { } \int_const:Nn } }
5221 \cs_new_protected:Npn \int_const:Nn #1#2
5222 {
5223   \int_compare:nNnTF {#2} < \c_zero
5224   {
5225     \int_new:N #1
5226     \tex_global:D
5227   }
5228   {
5229     \int_compare:nNnTF {#2} > \c_max_constdef_int

```

```

5230         {
5231             \int_new:N #1
5232             \tex_global:D
5233         }
5234         {
5235             \__chk_if_free_cs:N #1
5236             \tex_global:D \__int_constdef:Nw
5237         }
5238     }
5239     #1 = \__int_eval:w #2 \__int_eval_end:
5240 }
5241 \cs_generate_variant:Nn \int_const:Nn { c }
5242 \if_int_odd:w 0
5243     \cs_if_exist:NT \luatex luatexversion:D { 1 }
5244     \cs_if_exist:NT \uptex_disablecjktoken:D
5245     { \if_int_compare:w \ptex_jis:D "2121 = "3000 ~ 1 \fi: }
5246     \cs_if_exist:NT \xetex_XeTeXversion:D { 1 } ~
5247     \cs_if_exist:NTF \uptex_disablecjktoken:D
5248     { \cs_new_eq:NN \__int_constdef:Nw \uptex_kchardef:D }
5249     { \cs_new_eq:NN \__int_constdef:Nw \tex_chardef:D }
5250     \__int_constdef:Nw \c__max_constdef_int 1114111 ~
5251 \else:
5252     \cs_new_eq:NN \__int_constdef:Nw \tex_mathchardef:D
5253     \tex_mathchardef:D \c__max_constdef_int 32767 ~
5254 \fi:

```

(End definition for `\int_const:Nn`, `__int_constdef:Nw`, and `\c__max_constdef_int`. This function is documented on page 76.)

`\int_zero:N` Functions that reset an *integer* register to zero.

```

\int_zero:c      5255 \__debug_patch:nnNpn { \__debug_chk_var_local:N #1 } { }
\int_gzero:N     5256 \cs_new_protected:Npn \int_zero:N #1 { #1 = \c_zero }
\int_gzero:c     5257 \__debug_patch:nnNpn { \__debug_chk_var_global:N #1 } { }
                 5258 \cs_new_protected:Npn \int_gzero:N #1 { \tex_global:D #1 = \c_zero }
                 5259 \cs_generate_variant:Nn \int_zero:N { c }
                 5260 \cs_generate_variant:Nn \int_gzero:N { c }

```

(End definition for `\int_zero:N` and `\int_gzero:N`. These functions are documented on page 76.)

`\int_zero_new:N` Create a register if needed, otherwise clear it.

```

\int_zero_new:c  5261 \cs_new_protected:Npn \int_zero_new:N #1
\int_gzero_new:N 5262 { \int_if_exist:NTF #1 { \int_zero:N #1 } { \int_new:N #1 } }
\int_gzero_new:c 5263 \cs_new_protected:Npn \int_gzero_new:N #1
                 5264 { \int_if_exist:NTF #1 { \int_gzero:N #1 } { \int_new:N #1 } }
                 5265 \cs_generate_variant:Nn \int_zero_new:N { c }
                 5266 \cs_generate_variant:Nn \int_gzero_new:N { c }

```

(End definition for `\int_zero_new:N` and `\int_gzero_new:N`. These functions are documented on page 76.)

`\int_set_eq:NN` Setting equal means using one integer inside the set function of another. Check that assigned integer is local/global. No need to check that the other one is defined as T_EX does it for us.

```

\int_set_eq:cN   5267 \__debug_patch:nnNpn { \__debug_chk_var_local:N #1 } { }
\int_set_eq:Nc   5268 \cs_new_protected:Npn \int_set_eq:NN #1#2 { #1 = #2 }
\int_set_eq:cc
\int_gset_eq:NN
\int_gset_eq:cN
\int_gset_eq:Nc
\int_gset_eq:cc

```

```

5269 \cs_generate_variant:Nn \int_set_eq:NN { c }
5270 \cs_generate_variant:Nn \int_set_eq:NN { Nc , cc }
5271 \__debug_patch:nnNNpn { \__debug_chk_var_global:N #1 } { }
5272 \cs_new_protected:Npn \int_gset_eq:NN #1#2 { \tex_global:D #1 = #2 }
5273 \cs_generate_variant:Nn \int_gset_eq:NN { c }
5274 \cs_generate_variant:Nn \int_gset_eq:NN { Nc , cc }

```

(End definition for `\int_set_eq:NN` and `\int_gset_eq:NN`. These functions are documented on page 76.)

```

\int_if_exist_p:N Copies of the cs functions defined in l3basics.
\int_if_exist_p:c 5275 \prg_new_eq_conditional:NNn \int_if_exist:N \cs_if_exist:N
\int_if_exist:NTF 5276 { TF , T , F , p }
\int_if_exist:cTF 5277 \prg_new_eq_conditional:NNn \int_if_exist:c \cs_if_exist:c
5278 { TF , T , F , p }

```

(End definition for `\int_if_exist:NTF`. This function is documented on page 77.)

8.3 Setting and incrementing integers

Several functions here have a signature `:Nn` and are such that when debugging, the first argument should be checked to be a local/global variable and the second should be wrapped in code for an expression. The temporary function `__int_tmp:w` finds the name `#3` of the function being redefined and writes the appropriate patch.

```

5279 \cs_set_protected:Npn \__int_tmp:w #1#2#3
5280 {
5281   \__debug_patch_args:nnnNNpn
5282   { #1 ##1 }
5283   { }
5284   { {##1} { \__debug_chk_expr:nNnN {##2} \__int_eval:w { } #3 } }
5285   #2 #3
5286 }

```

```

\int_add:Nn Adding and subtracting to and from a counter. For each function, the debugging code
\int_add:cn produced by \__int_tmp:w checks that the assigned variable is correctly local/global and
\int_gadd:Nn wraps the expression in some checking code.
\int_gadd:cn 5287 \__int_tmp:w \__debug_chk_var_local:N
\int_sub:Nn 5288 \cs_new_protected:Npn \int_add:Nn #1#2
\int_sub:cn 5289 { \tex_advance:D #1 by \__int_eval:w #2 \__int_eval_end: }
\int_gsub:Nn 5290 \__int_tmp:w \__debug_chk_var_local:N
\int_gsub:cn 5291 \cs_new_protected:Npn \int_sub:Nn #1#2
5292 { \tex_advance:D #1 by - \__int_eval:w #2 \__int_eval_end: }
5293 \__int_tmp:w \__debug_chk_var_global:N
5294 \cs_new_protected:Npn \int_gadd:Nn #1#2
5295 { \tex_global:D \tex_advance:D #1 by \__int_eval:w #2 \__int_eval_end: }
5296 \__int_tmp:w \__debug_chk_var_global:N
5297 \cs_new_protected:Npn \int_gsub:Nn #1#2
5298 { \tex_global:D \tex_advance:D #1 by - \__int_eval:w #2 \__int_eval_end: }
5299 \cs_generate_variant:Nn \int_add:Nn { c }
5300 \cs_generate_variant:Nn \int_gadd:Nn { c }
5301 \cs_generate_variant:Nn \int_sub:Nn { c }
5302 \cs_generate_variant:Nn \int_gsub:Nn { c }

```

(End definition for `\int_add:Nn` and others. These functions are documented on page 77.)

\int_incr:N Incrementing and decrementing of integer registers is done with the following functions.

\int_incr:c 5303 __debug_patch:nnNNpn { __debug_chk_var_local:N #1 } { }

\int_gincr:N 5304 \cs_new_protected:Npn \int_incr:N #1

\int_gincr:c 5305 { \tex_advance:D #1 \c_one }

\int_decr:N 5306 __debug_patch:nnNNpn { __debug_chk_var_local:N #1 } { }

\int_decr:c 5307 \cs_new_protected:Npn \int_decr:N #1

\int_gdecr:N 5308 { \tex_advance:D #1 - \c_one }

\int_gdecr:c 5309 __debug_patch:nnNNpn { __debug_chk_var_global:N #1 } { }

5310 \cs_new_protected:Npn \int_gincr:N #1

5311 { \tex_global:D \tex_advance:D #1 \c_one }

5312 __debug_patch:nnNNpn { __debug_chk_var_global:N #1 } { }

5313 \cs_new_protected:Npn \int_gdecr:N #1

5314 { \tex_global:D \tex_advance:D #1 - \c_one }

5315 \cs_generate_variant:Nn \int_incr:N { c }

5316 \cs_generate_variant:Nn \int_decr:N { c }

5317 \cs_generate_variant:Nn \int_gincr:N { c }

5318 \cs_generate_variant:Nn \int_gdecr:N { c }

(End definition for \int_incr:N and others. These functions are documented on page 77.)

\int_set:Nn As integers are register-based TeX issues an error if they are not defined. Thus there is

\int_set:cn no need to check their existence as for token list variables. However, the code that checks

\int_gset:Nn whether the assignment is local or global is still needed.

\int_gset:cn 5319 __int_tmp:w __debug_chk_var_local:N

5320 \cs_new_protected:Npn \int_set:Nn #1#2

5321 { #1 ~ __int_eval:w #2 __int_eval_end: }

5322 __int_tmp:w __debug_chk_var_global:N

5323 \cs_new_protected:Npn \int_gset:Nn #1#2

5324 { \tex_global:D #1 ~ __int_eval:w #2 __int_eval_end: }

5325 \cs_generate_variant:Nn \int_set:Nn { c }

5326 \cs_generate_variant:Nn \int_gset:Nn { c }

(End definition for \int_set:Nn and \int_gset:Nn. These functions are documented on page 77.)

8.4 Using integers

\int_use:N Here is how counters are accessed:

\int_use:c 5327 \cs_new_eq:NN \int_use:N \tex_the:D

We hand-code this for some speed gain:

5328 %\cs_generate_variant:Nn \int_use:N { c }

5329 \cs_new:Npn \int_use:c #1 { \tex_the:D \cs:w #1 \cs_end: }

(End definition for \int_use:N. This function is documented on page 77.)

8.5 Integer expression conditionals

__prg_compare_error: Those functions are used for comparison tests which use a simple syntax where only

__prg_compare_error:Nw one set of braces is required and additional operators such as != and >= are supported. The tests first evaluate their left-hand side, with a trailing **__prg_compare_error:.** This marker is normally not expanded, but if the relation symbol is missing from the test's argument, then the marker inserts = (and itself) after triggering the relevant TeX error. If the first token which appears after evaluating and removing the left-hand side is

not a known relation symbol, then a judiciously placed `__prg_compare_error:Nw` gets expanded, cleaning up the end of the test and telling the user what the problem was.

```

5330 \cs_new_protected:Npn \__prg_compare_error:
5331 {
5332   \if_int_compare:w \c_zero \c_zero \fi:
5333   =
5334   \__prg_compare_error:
5335 }
5336 \cs_new:Npn \__prg_compare_error:Nw
5337 #1#2 \q_stop
5338 {
5339   { }
5340   \c_zero \fi:
5341   \__msg_kernel_expandable_error:nnn
5342   { kernel } { unknown-comparison } {#1}
5343   \prg_return_false:
5344 }

```

(End definition for `__prg_compare_error:` and `__prg_compare_error:Nw`.)

Comparison tests using a simple syntax where only one set of braces is required, additional operators such as `!=` and `>=` are supported, and multiple comparisons can be performed at once, for instance `0 < 5 <= 1`. The idea is to loop through the argument, finding one operand at a time, and comparing it to the previous one. The looping auxiliary `__int_compare:Nw` reads one *operand* and one *comparison* symbol, and leaves roughly

```

\int_compare_p:n
\int_compare:nTF
\__int_compare:w
\__int_compare:Nw
\__int_compare:NNw
\__int_compare:nnN
\__int_compare_end=:NNw
\__int_compare=:NNw
\__int_compare:<:NNw
\__int_compare:>:NNw
\__int_compare==:NNw
\__int_compare!=:NNw
\__int_compare<=:NNw
\__int_compare>=:NNw

```

in the input stream. Each call to this auxiliary provides the second operand of the last call's `\if_int_compare:w`. If one of the *comparisons* is **false**, the **true** branch of the TeX conditional is taken (because of `\reverse_if:N`), immediately returning **false** as the result of the test. There is no TeX conditional waiting the first operand, so we add an `\if_false:` and expand by hand with `__int_value:w`, thus skipping `\prg_return_false:` on the first iteration.

Before starting the loop, the first step is to make sure that there is at least one relation symbol. We first let TeX evaluate this left hand side of the (in)equality using `__int_eval:w`. Since the relation symbols `<`, `>`, `=` and `!` are not allowed in integer expressions, they would terminate the expression. If the argument contains no relation symbol, `__prg_compare_error:` is expanded, inserting `=` and itself after an error. In all cases, `__int_compare:w` receives as its argument an integer, a relation symbol, and some more tokens. We then setup the loop, which is ended by the two odd-looking items `e` and `{=nd_}`, with a trailing `\q_stop` used to grab the entire argument when necessary.

```

5345 \prg_new_conditional:Npnn \int_compare:n #1 { p , T , F , TF }
5346 {
5347   \exp_after:wN \__int_compare:w
5348   \__int_value:w \__int_eval:w #1 \__prg_compare_error:
5349 }
5350 \cs_new:Npn \__int_compare:w #1 \__prg_compare_error:
5351 {
5352   \exp_after:wN \if_false: \__int_value:w
5353   \__int_compare:Nw #1 e { = nd_ } \q_stop
5354 }

```


The goal here is to find an $\langle operand \rangle$ and a $\langle comparison \rangle$. The $\langle operand \rangle$ is already evaluated, but we cannot yet grab it as an argument. To access the following relation symbol, we remove the number by applying `_int_to_roman:w`, after making sure that the argument becomes non-positive: its roman numeral representation is then empty. Then probe the first two tokens with `_int_compare:NNw` to determine the relation symbol, building a control sequence from it (`\token_to_str:N` gives better errors if #1 is not a character). All the extended forms have an extra = hence the test for that as a second token. If the relation symbol is unknown, then the control sequence is turned by TeX into `\scan_stop:`, ignored thanks to `\unexpanded`, and `_prg_compare_error:Nw` raises an error.

```

5355 \cs_new:Npn \_int\_compare:Nw #1#2 \q\_stop
5356 {
5357   \exp\_after:wN \_int\_compare:NNw
5358   \_int\_to\_roman:w - 0 #2 \q\_mark
5359   #1#2 \q\_stop
5360 }
5361 \cs_new:Npn \_int\_compare:NNw #1#2#3 \q\_mark
5362 {
5363   \etex\_unexpanded:D
5364   \use:c
5365   {
5366     \_int\_compare\_ \token\_to\_str:N #1
5367     \if\_meaning:w = #2 = \fi:
5368     :NNw
5369   }
5370   \_prg\_compare\_error:Nw #1
5371 }

```

When the last $\langle operand \rangle$ is seen, `_int_compare:NNw` receives `e` and `=nd_` as arguments, hence calling `_int_compare_end_=:NNw` to end the loop: return the result of the last comparison (involving the operand that we just found). When a normal relation is found, the appropriate auxiliary calls `_int_compare:nnN` where #1 is `\if_int_compare:w` or `\reverse_if:N \if_int_compare:w`, #2 is the $\langle operand \rangle$, and #3 is one of `<`, `=`, or `>`. As announced earlier, we leave the $\langle operand \rangle$ for the previous conditional. If this conditional is true the result of the test is known, so we remove all tokens and return `false`. Otherwise, we apply the conditional #1 to the $\langle operand \rangle$ #2 and the comparison #3, and call `_int_compare:Nw` to look for additional operands, after evaluating the following expression.

```

5372 \cs_new:cpn { \_int\_compare\_end\_=:NNw } #1#2#3 e #4 \q\_stop
5373 {
5374   {#3} \exp\_stop\_f:
5375   \prg\_return\_false: \else: \prg\_return\_true: \fi:
5376 }
5377 \cs_new:Npn \_int\_compare:nnN #1#2#3
5378 {
5379   {#2} \exp\_stop\_f:
5380   \prg\_return\_false: \exp\_after:wN \use\_none\_delimit\_by\_q\_stop:w
5381   \fi:
5382   #1 #2 #3 \exp\_after:wN \_int\_compare:Nw \_int\_value:w \_int\_eval:w
5383 }

```

The actual comparisons are then simple function calls, using the relation as delimiter for a delimited argument and discarding `_prg_compare_error:Nw` $\langle token \rangle$ responsible for

error detection.

```

5384 \cs_new:cpn { __int_compare=:NNw } #1#2#3 =
5385 { \__int_compare:nnN { \reverse_if:N \if_int_compare:w } {#3} = }
5386 \cs_new:cpn { __int_compare:<:NNw } #1#2#3 <
5387 { \__int_compare:nnN { \reverse_if:N \if_int_compare:w } {#3} < }
5388 \cs_new:cpn { __int_compare:>:NNw } #1#2#3 >
5389 { \__int_compare:nnN { \reverse_if:N \if_int_compare:w } {#3} > }
5390 \cs_new:cpn { __int_compare=:NNw } #1#2#3 ==
5391 { \__int_compare:nnN { \reverse_if:N \if_int_compare:w } {#3} = }
5392 \cs_new:cpn { __int_compare!=:NNw } #1#2#3 !=
5393 { \__int_compare:nnN { \if_int_compare:w } {#3} = }
5394 \cs_new:cpn { __int_compare<=:NNw } #1#2#3 <=
5395 { \__int_compare:nnN { \if_int_compare:w } {#3} > }
5396 \cs_new:cpn { __int_compare>=:NNw } #1#2#3 >=
5397 { \__int_compare:nnN { \if_int_compare:w } {#3} < }

```

(End definition for \int_compare:nTF and others. This function is documented on page 78.)

\int_compare_p:nNn More efficient but less natural in typing.

```

\int_compare:nNnTF
5398 \__debug_patch_conditional_args:nNnpnn
5399 {
5400   { \__debug_chk_expr:nNnN {#1} \__int_eval:w { } \int_compare:nNn }
5401   { \__int_eval_end: #2 }
5402   { \__debug_chk_expr:nNnN {#3} \__int_eval:w { } \int_compare:nNn }
5403 }
5404 \prg_new_conditional:Npnn \int_compare:nNn #1#2#3 { p , T , F , TF }
5405 {
5406   \if_int_compare:w \__int_eval:w #1 #2 \__int_eval:w #3 \__int_eval_end:
5407   \prg_return_true:
5408   \else:
5409   \prg_return_false:
5410   \fi:
5411 }

```

(End definition for \int_compare:nNnTF. This function is documented on page 78.)

\int_case:nn For integer cases, the first task to fully expand the check condition. The over all idea is then much the same as for \str_case:nn(TF) as described in l3basics.

```

\__int_case:nnTF
\__int_case:nw
\__int_case_end:nw
5412 \cs_new:Npn \int_case:nnTF #1
5413 {
5414   \exp:w
5415   \exp_args:Nf \__int_case:nnTF { \int_eval:n {#1} }
5416 }
5417 \cs_new:Npn \int_case:nnT #1#2#3
5418 {
5419   \exp:w
5420   \exp_args:Nf \__int_case:nnTF { \int_eval:n {#1} } {#2} {#3} { }
5421 }
5422 \cs_new:Npn \int_case:nnF #1#2
5423 {
5424   \exp:w
5425   \exp_args:Nf \__int_case:nnTF { \int_eval:n {#1} } {#2} { }
5426 }
5427 \cs_new:Npn \int_case:nn #1#2

```

```

5428 {
5429   \exp:w
5430   \exp_args:Nf \__int_case:nnTF { \int_eval:n {#1} } {#2} { } { }
5431 }
5432 \cs_new:Npn \__int_case:nnTF #1#2#3#4
5433 { \__int_case:nw {#1} #2 {#1} { } \q_mark {#3} \q_mark {#4} \q_stop }
5434 \cs_new:Npn \__int_case:nw #1#2#3
5435 {
5436   \int_compare:nNnTF {#1} = {#2}
5437   { \__int_case_end:nw {#3} }
5438   { \__int_case:nw {#1} }
5439 }
5440 \cs_new_eq:NN \__int_case_end:nw \__prg_case_end:nw

```

(End definition for `\int_case:nnTF` and others. This function is documented on page 79.)

```

\int_if_odd_p:n A predicate function.
\int_if_odd:nTF
\int_if_even_p:n
\int_if_even:nTF
5441 \__debug_patch_conditional_args:nNnpnn
5442 { { \__debug_chk_expr:nNnN {#1} \__int_eval:w { } \int_if_odd:n } }
5443 \prg_new_conditional:Npnn \int_if_odd:n #1 { p , T , F , TF }
5444 {
5445   \if_int_odd:w \__int_eval:w #1 \__int_eval_end:
5446   \prg_return_true:
5447   \else:
5448   \prg_return_false:
5449   \fi:
5450 }
5451 \__debug_patch_conditional_args:nNnpnn
5452 { { \__debug_chk_expr:nNnN {#1} \__int_eval:w { } \int_if_even:n } }
5453 \prg_new_conditional:Npnn \int_if_even:n #1 { p , T , F , TF }
5454 {
5455   \if_int_odd:w \__int_eval:w #1 \__int_eval_end:
5456   \prg_return_false:
5457   \else:
5458   \prg_return_true:
5459   \fi:
5460 }

```

(End definition for `\int_if_odd:nTF` and `\int_if_even:nTF`. These functions are documented on page 79.)

8.6 Integer expression loops

`\int_while_do:nn` These are quite easy given the above functions. The `while` versions test first and then execute the body. The `do_while` does it the other way round.

```

\int_until_do:nn
\int_do_while:nn
\int_do_until:nn
5461 \cs_new:Npn \int_while_do:nn #1#2
5462 {
5463   \int_compare:nT {#1}
5464   {
5465     #2
5466     \int_while_do:nn {#1} {#2}
5467   }
5468 }
5469 \cs_new:Npn \int_until_do:nn #1#2

```

```

5470 {
5471   \int_compare:nF {#1}
5472   {
5473     #2
5474     \int_until_do:nn {#1} {#2}
5475   }
5476 }
5477 \cs_new:Npn \int_do_while:nn #1#2
5478 {
5479   #2
5480   \int_compare:nT {#1}
5481   { \int_do_while:nn {#1} {#2} }
5482 }
5483 \cs_new:Npn \int_do_until:nn #1#2
5484 {
5485   #2
5486   \int_compare:nF {#1}
5487   { \int_do_until:nn {#1} {#2} }
5488 }

```

(End definition for `\int_while_do:nn` and others. These functions are documented on page 80.)

`\int_while_do:nNnn` As above but not using the more natural syntax.

`\int_until_do:nNnn`

`\int_do_while:nNnn`

`\int_do_until:nNnn`

```

5489 \cs_new:Npn \int_while_do:nNnn #1#2#3#4
5490 {
5491   \int_compare:nNnT {#1} #2 {#3}
5492   {
5493     #4
5494     \int_while_do:nNnn {#1} #2 {#3} {#4}
5495   }
5496 }
5497 \cs_new:Npn \int_until_do:nNnn #1#2#3#4
5498 {
5499   \int_compare:nNnF {#1} #2 {#3}
5500   {
5501     #4
5502     \int_until_do:nNnn {#1} #2 {#3} {#4}
5503   }
5504 }
5505 \cs_new:Npn \int_do_while:nNnn #1#2#3#4
5506 {
5507   #4
5508   \int_compare:nNnT {#1} #2 {#3}
5509   { \int_do_while:nNnn {#1} #2 {#3} {#4} }
5510 }
5511 \cs_new:Npn \int_do_until:nNnn #1#2#3#4
5512 {
5513   #4
5514   \int_compare:nNnF {#1} #2 {#3}
5515   { \int_do_until:nNnn {#1} #2 {#3} {#4} }
5516 }

```

(End definition for `\int_while_do:nNnn` and others. These functions are documented on page 80.)

8.7 Integer step functions

`\int_step_function:nnnN`
`__int_step:wwwN`
`__int_step:NnnnN`

Before all else, evaluate the initial value, step, and final value. Repeating a function by steps first needs a check on the direction of the steps. After that, do the function for the start value then step and loop around. It would be more symmetrical to test for a step size of zero before checking the sign, but we optimize for the most frequent case (positive step).

```

5517 \__debug_patch_args:nNnpn
5518 {
5519   { \__debug_chk_expr:nNnN {#1} \__int_eval:w { } \int_step_function:nnnN }
5520   { \__debug_chk_expr:nNnN {#2} \__int_eval:w { } \int_step_function:nnnN }
5521   { \__debug_chk_expr:nNnN {#3} \__int_eval:w { } \int_step_function:nnnN }
5522 }
5523 \cs_new:Npn \int_step_function:nnnN #1#2#3
5524 {
5525   \exp_after:wN \__int_step:wwwN
5526   \__int_value:w \__int_eval:w #1 \exp_after:wN ;
5527   \__int_value:w \__int_eval:w #2 \exp_after:wN ;
5528   \__int_value:w \__int_eval:w #3 ;
5529 }
5530 \cs_new:Npn \__int_step:wwwN #1; #2; #3; #4
5531 {
5532   \int_compare:nNnTF {#2} > \c_zero
5533   { \__int_step:NnnnN > }
5534   {
5535     \int_compare:nNnTF {#2} = \c_zero
5536     {
5537       \__msg_kernel_expandable_error:nnn { kernel } { zero-step } {#4}
5538       \use_none:nnnn
5539     }
5540     { \__int_step:NnnnN < }
5541   }
5542   {#1} {#2} {#3} #4
5543 }
5544 \cs_new:Npn \__int_step:NnnnN #1#2#3#4#5
5545 {
5546   \int_compare:nNnF {#2} #1 {#4}
5547   {
5548     #5 {#2}
5549     \exp_args:NNf \__int_step:NnnnN
5550     #1 { \int_eval:n { #2 + #3 } } {#3} {#4} #5
5551   }
5552 }
```

(End definition for `\int_step_function:nnnN`, `__int_step:wwwN`, and `__int_step:NnnnN`. This function is documented on page 81.)

`\int_step_inline:nnnn`
`\int_step_variable:nnnNn`
`__int_step:NNnnnn`

The approach here is to build a function, with a global integer required to make the nesting safe (as seen in other in line functions), and map that function using `\int_step_function:nnnN`. We put a `__prg_break_point:Nn` so that `map_break` functions from other modules correctly decrement `\g__prg_map_int` before looking for their own break point. The first argument is `\scan_stop:`, so that no breaking function recognizes this break point as its own.

```

5553 \cs_new_protected:Npn \int_step_inline:nnnn
```

```

5554 {
5555   \int_gincr:N \g__prg_map_int
5556   \exp_args:NNc \__int_step:NNnnnn
5557   \cs_gset_protected:Npn
5558     { __prg_map_ \int_use:N \g__prg_map_int :w }
5559 }
5560 \cs_new_protected:Npn \int_step_variable:nnnNn #1#2#3#4#5
5561 {
5562   \int_gincr:N \g__prg_map_int
5563   \exp_args:NNc \__int_step:NNnnnn
5564   \cs_gset_protected:Npx
5565     { __prg_map_ \int_use:N \g__prg_map_int :w }
5566     {#1}{#2}{#3}
5567     {
5568       \tl_set:Nn \exp_not:N #4 {##1}
5569       \exp_not:n {#5}
5570     }
5571 }
5572 \cs_new_protected:Npn \__int_step:NNnnnn #1#2#3#4#5#6
5573 {
5574   #1 #2 ##1 {#6}
5575   \int_step_function:nnnN {#3} {#4} {#5} #2
5576   \__prg_break_point:Nn \scan_stop: { \int_gdecr:N \g__prg_map_int }
5577 }

```

(End definition for `\int_step_inline:nnnn`, `\int_step_variable:nnnNn`, and `__int_step:NNnnnn`. These functions are documented on page 81.)

8.8 Formatting integers

`\int_to_arabic:n` Nothing exciting here.

```

5578 \cs_new_eq:NN \int_to_arabic:n \int_eval:n

```

(End definition for `\int_to_arabic:n`. This function is documented on page 81.)

`\int_to_symbols:nnn` For conversion of integers to arbitrary symbols the method is in general as follows. The input number (#1) is compared to the total number of symbols available at each place (#2). If the input is larger than the total number of symbols available then the modulus is needed, with one added so that the positions don't have to number from zero. Using an `f`-type expansion, this is done so that the system is recursive. The actual conversion function therefore gets a 'nice' number at each stage. Of course, if the initial input was small enough then there is no problem and everything is easy.

```

5579 \cs_new:Npn \int_to_symbols:nnn #1#2#3
5580 {
5581   \int_compare:nNnTF {#1} > {#2}
5582   {
5583     \exp_args:NNo \exp_args:No \__int_to_symbols:nnnn
5584     {
5585       \int_case:nn
5586         { 1 + \int_mod:nn { #1 - 1 } {#2} }
5587         {#3}
5588       }
5589     {#1} {#2} {#3}
5590   }

```

```

5591     { \int_case:nn {#1} {#3} }
5592   }
5593 \cs_new:Npn \__int_to_symbols:nnnn #1#2#3#4
5594 {
5595   \exp_args:Nf \int_to_symbols:nnn
5596     { \int_div_truncate:nn { #2 - 1 } {#3} } {#3} {#4}
5597   #1
5598 }

```

(End definition for `\int_to_symbols:nnn` and `__int_to_symbols:nnnn`. This function is documented on page 82.)

`\int_to_alph:n` These both use the above function with input functions that make sense for the alphabet in English.

`\int_to_Alph:n`

```

5599 \cs_new:Npn \int_to_alph:n #1
5600 {
5601   \int_to_symbols:nnn {#1} { 26 }
5602   {
5603     { 1 } { a }
5604     { 2 } { b }
5605     { 3 } { c }
5606     { 4 } { d }
5607     { 5 } { e }
5608     { 6 } { f }
5609     { 7 } { g }
5610     { 8 } { h }
5611     { 9 } { i }
5612     { 10 } { j }
5613     { 11 } { k }
5614     { 12 } { l }
5615     { 13 } { m }
5616     { 14 } { n }
5617     { 15 } { o }
5618     { 16 } { p }
5619     { 17 } { q }
5620     { 18 } { r }
5621     { 19 } { s }
5622     { 20 } { t }
5623     { 21 } { u }
5624     { 22 } { v }
5625     { 23 } { w }
5626     { 24 } { x }
5627     { 25 } { y }
5628     { 26 } { z }
5629   }
5630 }
5631 \cs_new:Npn \int_to_Alph:n #1
5632 {
5633   \int_to_symbols:nnn {#1} { 26 }
5634   {
5635     { 1 } { A }
5636     { 2 } { B }
5637     { 3 } { C }
5638     { 4 } { D }

```

```

5639      { 5 } { E }
5640      { 6 } { F }
5641      { 7 } { G }
5642      { 8 } { H }
5643      { 9 } { I }
5644      { 10 } { J }
5645      { 11 } { K }
5646      { 12 } { L }
5647      { 13 } { M }
5648      { 14 } { N }
5649      { 15 } { O }
5650      { 16 } { P }
5651      { 17 } { Q }
5652      { 18 } { R }
5653      { 19 } { S }
5654      { 20 } { T }
5655      { 21 } { U }
5656      { 22 } { V }
5657      { 23 } { W }
5658      { 24 } { X }
5659      { 25 } { Y }
5660      { 26 } { Z }
5661    }
5662  }

```

(End definition for `\int_to_alph:n` and `\int_to_Alph:n`. These functions are documented on page 82.)

```

\int_to_base:nn Converting from base ten (#1) to a second base (#2) starts with computing #1: if it is
\int_to_Base:nn a complicated calculation, we shouldn't perform it twice. Then check the sign, store it,
\__int_to_base:nn either - or \c_empty_tl, and feed the absolute value to the next auxiliary function.
\__int_to_Base:nn
\__int_to_base:nnN 5663 \cs_new:Npn \int_to_base:nn #1
\__int_to_Base:nnN 5664 { \exp_args:Nf \__int_to_base:nn { \int_eval:n {#1} } }
\__int_to_base:nnN 5665 \cs_new:Npn \int_to_Base:nn #1
\__int_to_Base:nnN 5666 { \exp_args:Nf \__int_to_Base:nn { \int_eval:n {#1} } }
\__int_to_Base:nnN 5667 \cs_new:Npn \__int_to_base:nn #1#2
\__int_to_letter:n 5668 {
\__int_to_Letter:n 5669   \int_compare:nNnTF {#1} < 0
5670     { \exp_args:No \__int_to_base:nnN { \use_none:n #1 } {#2} - }
5671     { \__int_to_base:nnN {#1} {#2} \c_empty_tl }
5672   }
5673 \cs_new:Npn \__int_to_Base:nn #1#2
5674 {
5675   \int_compare:nNnTF {#1} < 0
5676     { \exp_args:No \__int_to_Base:nnN { \use_none:n #1 } {#2} - }
5677     { \__int_to_Base:nnN {#1} {#2} \c_empty_tl }
5678   }

```

Here, the idea is to provide a recursive system to deal with the input. The output is built up after the end of the function. At each pass, the value in #1 is checked to see if it is less than the new base (#2). If it is, then it is converted directly, putting the sign back in front. On the other hand, if the value to convert is greater than or equal to the new base then the modulus and remainder values are found. The modulus is converted to a symbol and put on the right, and the remainder is carried forward to the next round.

```

5679 \cs_new:Npn \__int_to_base:nnN #1#2#3

```



```

5680 {
5681   \int_compare:nNnTF {#1} < {#2}
5682   { \exp_last_unbraced:Nf #3 { \__int_to_letter:n {#1} } }
5683   {
5684     \exp_args:Nf \__int_to_base:nnnN
5685     { \__int_to_letter:n { \int_mod:nn {#1} {#2} } }
5686     {#1}
5687     {#2}
5688     #3
5689   }
5690 }
5691 \cs_new:Npn \__int_to_base:nnnN #1#2#3#4
5692 {
5693   \exp_args:Nf \__int_to_base:nnN
5694   { \int_div_truncate:nn {#2} {#3} }
5695   {#3}
5696   #4
5697   #1
5698 }
5699 \cs_new:Npn \__int_to_Base:nnN #1#2#3
5700 {
5701   \int_compare:nNnTF {#1} < {#2}
5702   { \exp_last_unbraced:Nf #3 { \__int_to_Letter:n {#1} } }
5703   {
5704     \exp_args:Nf \__int_to_Base:nnnN
5705     { \__int_to_Letter:n { \int_mod:nn {#1} {#2} } }
5706     {#1}
5707     {#2}
5708     #3
5709   }
5710 }
5711 \cs_new:Npn \__int_to_Base:nnnN #1#2#3#4
5712 {
5713   \exp_args:Nf \__int_to_Base:nnN
5714   { \int_div_truncate:nn {#2} {#3} }
5715   {#3}
5716   #4
5717   #1
5718 }

```

Convert to a letter only if necessary, otherwise simply return the value unchanged. It would be cleaner to use `\int_case:nn`, but in our case, the cases are contiguous, so it is forty times faster to use the `\if_case:w` primitive. The first `\exp_after:wN` expands the conditional, jumping to the correct case, the second one expands after the resulting character to close the conditional. Since `#1` might be an expression, and not directly a single digit, we need to evaluate it properly, and expand the trailing `\fi:`.

```

5719 \cs_new:Npn \__int_to_letter:n #1
5720 {
5721   \exp_after:wN \exp_after:wN
5722   \if_case:w \__int_eval:w #1 - 10 \__int_eval_end:
5723   a
5724   \or: b
5725   \or: c
5726   \or: d

```

```

5727     \or: e
5728     \or: f
5729     \or: g
5730     \or: h
5731     \or: i
5732     \or: j
5733     \or: k
5734     \or: l
5735     \or: m
5736     \or: n
5737     \or: o
5738     \or: p
5739     \or: q
5740     \or: r
5741     \or: s
5742     \or: t
5743     \or: u
5744     \or: v
5745     \or: w
5746     \or: x
5747     \or: y
5748     \or: z
5749     \else: \__int_value:w \__int_eval:w #1 \exp_after:wN \__int_eval_end:
5750     \fi:
5751 }
5752 \cs_new:Npn \__int_to_Letter:n #1
5753 {
5754     \exp_after:wN \exp_after:wN
5755     \if_case:w \__int_eval:w #1 - 10 \__int_eval_end:
5756         A
5757     \or: B
5758     \or: C
5759     \or: D
5760     \or: E
5761     \or: F
5762     \or: G
5763     \or: H
5764     \or: I
5765     \or: J
5766     \or: K
5767     \or: L
5768     \or: M
5769     \or: N
5770     \or: O
5771     \or: P
5772     \or: Q
5773     \or: R
5774     \or: S
5775     \or: T
5776     \or: U
5777     \or: V
5778     \or: W
5779     \or: X
5780     \or: Y

```

```

5781     \or: Z
5782     \else: \__int_value:w \__int_eval:w #1 \exp_after:wN \__int_eval_end:
5783     \fi:
5784 }

```

(End definition for \int_to_base:nn and others. These functions are documented on page 83.)

\int_to_bin:n Wrappers around the generic function.

```

\int_to_hex:n
\int_to_Hex:n
\int_to_oct:n
5785 \cs_new:Npn \int_to_bin:n #1
5786 { \int_to_base:nn {#1} { 2 } }
5787 \cs_new:Npn \int_to_hex:n #1
5788 { \int_to_base:nn {#1} { 16 } }
5789 \cs_new:Npn \int_to_Hex:n #1
5790 { \int_to_Base:nn {#1} { 16 } }
5791 \cs_new:Npn \int_to_oct:n #1
5792 { \int_to_base:nn {#1} { 8 } }

```

(End definition for \int_to_bin:n and others. These functions are documented on page 82.)

\int_to_roman:n The __int_to_roman:w primitive creates tokens of category code 12 (other). Usually, what is actually wanted is letters. The approach here is to convert the output of the primitive into letters using appropriate control sequence names. That keeps everything expandable. The loop is terminated by the conversion of the Q.

\int_to_Roman:n

```

\__int_to_roman:N
\__int_to_roman:N
5793 \cs_new:Npn \int_to_roman:n #1
5794 {
5795     \exp_after:wN \__int_to_roman:N
5796     \__int_to_roman:w \int_eval:n {#1} Q
5797 }
5798 \cs_new:Npn \__int_to_roman:N #1
5799 {
5800     \use:c { __int_to_roman_ #1 :w }
5801     \__int_to_roman:N
5802 }
5803 \cs_new:Npn \int_to_Roman:n #1
5804 {
5805     \exp_after:wN \__int_to_Roman_aux:N
5806     \__int_to_roman:w \int_eval:n {#1} Q
5807 }
5808 \cs_new:Npn \__int_to_Roman_aux:N #1
5809 {
5810     \use:c { __int_to_Roman_ #1 :w }
5811     \__int_to_Roman_aux:N
5812 }
5813 \cs_new:Npn \__int_to_roman_i:w { i }
5814 \cs_new:Npn \__int_to_roman_v:w { v }
5815 \cs_new:Npn \__int_to_roman_x:w { x }
5816 \cs_new:Npn \__int_to_roman_l:w { l }
5817 \cs_new:Npn \__int_to_roman_c:w { c }
5818 \cs_new:Npn \__int_to_roman_d:w { d }
5819 \cs_new:Npn \__int_to_roman_m:w { m }
5820 \cs_new:Npn \__int_to_roman_Q:w #1 { }
5821 \cs_new:Npn \__int_to_Roman_i:w { I }
5822 \cs_new:Npn \__int_to_Roman_v:w { V }
5823 \cs_new:Npn \__int_to_Roman_x:w { X }

```

```

5824 \cs_new:Npn \__int_to_Roman_l:w { L }
5825 \cs_new:Npn \__int_to_Roman_c:w { C }
5826 \cs_new:Npn \__int_to_Roman_d:w { D }
5827 \cs_new:Npn \__int_to_Roman_m:w { M }
5828 \cs_new:Npn \__int_to_Roman_Q:w #1 { }

```

(End definition for `\int_to_roman:n` and others. These functions are documented on page 83.)

8.9 Converting from other formats to integers

```

\__int_pass_signs:wn
\__int_pass_signs_end:wn

```

Called as `__int_pass_signs:wn <signs and digits> \q_stop {<code>}`, this function leaves in the input stream any sign it finds, then inserts the `<code>` before the first non-sign token (and removes `\q_stop`). More precisely, it deletes any + and passes any - to the input stream, hence should be called in an integer expression.

```

5829 \cs_new:Npn \__int_pass_signs:wn #1
5830 {
5831   \if:w + \if:w - \exp_not:N #1 + \fi: \exp_not:N #1
5832   \exp_after:wN \__int_pass_signs:wn
5833   \else:
5834     \exp_after:wN \__int_pass_signs_end:wn
5835     \exp_after:wN #1
5836   \fi:
5837 }
5838 \cs_new:Npn \__int_pass_signs_end:wn #1 \q_stop #2 { #2 #1 }

```

(End definition for `__int_pass_signs:wn` and `__int_pass_signs_end:wn`.)

```

\int_from_alph:n
\__int_from_alph:nN
\__int_from_alph:N

```

First take care of signs then loop through the input using the recursion quarks. The `__int_from_alph:nN` auxiliary collects in its first argument the value obtained so far, and the auxiliary `__int_from_alph:N` converts one letter to an expression which evaluates to the correct number.

```

5839 \cs_new:Npn \int_from_alph:n #1
5840 {
5841   \int_eval:n
5842   {
5843     \exp_after:wN \__int_pass_signs:wn \tl_to_str:n {#1}
5844     \q_stop { \__int_from_alph:nN { 0 } }
5845     \q_recursion_tail \q_recursion_stop
5846   }
5847 }
5848 \cs_new:Npn \__int_from_alph:nN #1#2
5849 {
5850   \quark_if_recursion_tail_stop_do:Nn #2 {#1}
5851   \exp_args:Nf \__int_from_alph:nN
5852   { \int_eval:n { #1 * 26 + \__int_from_alph:N #2 } }
5853 }
5854 \cs_new:Npn \__int_from_alph:N #1
5855 { '#1 - \int_compare:nNnTF { '#1 } < { 91 } { 64 } { 96 } }

```

(End definition for `\int_from_alph:n`, `__int_from_alph:nN`, and `__int_from_alph:N`. This function is documented on page 83.)

`\int_from_base:nn` Leave the signs into the integer expression, then loop through characters, collecting the value found so far in the first argument of `__int_from_base:nnN`. To convert a single character, `__int_from_base:N` checks first for digits, then distinguishes lower from upper case letters, turning them into the appropriate number. Note that this auxiliary does not use `\int_eval:n`, hence is not safe for general use.

```

5856 \cs_new:Npn \int_from_base:nn #1#2
5857 {
5858   \int_eval:n
5859   {
5860     \exp_after:wN \__int_pass_signs:wn \tl_to_str:n {#1}
5861     \q_stop { \__int_from_base:nnN { 0 } {#2} }
5862     \q_recursion_tail \q_recursion_stop
5863   }
5864 }
5865 \cs_new:Npn \__int_from_base:nnN #1#2#3
5866 {
5867   \quark_if_recursion_tail_stop_do:Nn #3 {#1}
5868   \exp_args:Nf \__int_from_base:nnN
5869   { \int_eval:n { #1 * #2 + \__int_from_base:N #3 } }
5870   {#2}
5871 }
5872 \cs_new:Npn \__int_from_base:N #1
5873 {
5874   \int_compare:nNnTF { '#1 } < { 58 }
5875   {#1}
5876   { '#1 - \int_compare:nNnTF { '#1 } < { 91 } { 55 } { 87 } }
5877 }

```

(End definition for `\int_from_base:nn`, `__int_from_base:nnN`, and `__int_from_base:N`. This function is documented on page 84.)

`\int_from_bin:n` Wrappers around the generic function.

```

\int_from_hex:n
\int_from_oct:n
5878 \cs_new:Npn \int_from_bin:n #1
5879 { \int_from_base:nn {#1} { 2 } }
5880 \cs_new:Npn \int_from_hex:n #1
5881 { \int_from_base:nn {#1} { 16 } }
5882 \cs_new:Npn \int_from_oct:n #1
5883 { \int_from_base:nn {#1} { 8 } }

```

(End definition for `\int_from_bin:n`, `\int_from_hex:n`, and `\int_from_oct:n`. These functions are documented on page 83.)

`\c__int_from_roman_i_int` Constants used to convert from Roman numerals to integers.

```

\c__int_from_roman_v_int
\c__int_from_roman_x_int
\c__int_from_roman_l_int
\c__int_from_roman_c_int
\c__int_from_roman_d_int
\c__int_from_roman_m_int
\c__int_from_roman_I_int
\c__int_from_roman_V_int
\c__int_from_roman_X_int
\c__int_from_roman_L_int
\c__int_from_roman_C_int
\c__int_from_roman_D_int
\c__int_from_roman_M_int
5884 \int_const:cn { c__int_from_roman_i_int } { 1 }
5885 \int_const:cn { c__int_from_roman_v_int } { 5 }
5886 \int_const:cn { c__int_from_roman_x_int } { 10 }
5887 \int_const:cn { c__int_from_roman_l_int } { 50 }
5888 \int_const:cn { c__int_from_roman_c_int } { 100 }
5889 \int_const:cn { c__int_from_roman_d_int } { 500 }
5890 \int_const:cn { c__int_from_roman_m_int } { 1000 }
5891 \int_const:cn { c__int_from_roman_I_int } { 1 }
5892 \int_const:cn { c__int_from_roman_V_int } { 5 }
5893 \int_const:cn { c__int_from_roman_X_int } { 10 }
5894 \int_const:cn { c__int_from_roman_L_int } { 50 }

```

```

5895 \int_const:cn { c__int_from_roman_C_int } { 100 }
5896 \int_const:cn { c__int_from_roman_D_int } { 500 }
5897 \int_const:cn { c__int_from_roman_M_int } { 1000 }

```

(End definition for `\c__int_from_roman_i_int` and others.)

`\int_from_roman:n` The method here is to iterate through the input, finding the appropriate value for each letter and building up a sum. This is then evaluated by \TeX . If any unknown letter is found, skip to the closing parenthesis and insert `*0-1` afterwards, to replace the value by `-1`.

```

5898 \cs_new:Npn \int_from_roman:n #1
5899 {
5900   \int_eval:n
5901   {
5902     (
5903       0
5904       \exp_after:wN \__int_from_roman:NN \tl_to_str:n {#1}
5905       \q_recursion_tail \q_recursion_tail \q_recursion_stop
5906     )
5907   }
5908 }
5909 \cs_new:Npn \__int_from_roman:NN #1#2
5910 {
5911   \quark_if_recursion_tail_stop:N #1
5912   \int_if_exist:cF { c__int_from_roman_ #1 _int }
5913   { \__int_from_roman_error:w }
5914   \quark_if_recursion_tail_stop_do:Nn #2
5915   { + \use:c { c__int_from_roman_ #1 _int } }
5916   \int_if_exist:cF { c__int_from_roman_ #2 _int }
5917   { \__int_from_roman_error:w }
5918   \int_compare:nNnTF
5919   { \use:c { c__int_from_roman_ #1 _int } }
5920   <
5921   { \use:c { c__int_from_roman_ #2 _int } }
5922   {
5923     + \use:c { c__int_from_roman_ #2 _int }
5924     - \use:c { c__int_from_roman_ #1 _int }
5925     \__int_from_roman:NN
5926   }
5927   {
5928     + \use:c { c__int_from_roman_ #1 _int }
5929     \__int_from_roman:NN #2
5930   }
5931 }
5932 \cs_new:Npn \__int_from_roman_error:w #1 \q_recursion_stop #2
5933 { #2 * 0 - 1 }

```

(End definition for `\int_from_roman:n`, `__int_from_roman:NN`, and `__int_from_roman_error:w`. This function is documented on page 84.)

8.10 Viewing integer

`\int_show:N` Diagnostics.
`\int_show:c` 5934 \cs_new_eq:NN \int_show:N __kernel_register_show:N
`__int_show:nN` 5935 \cs_generate_variant:Nn \int_show:N { c }

(End definition for `\int_show:N` and `__int_show:nN`. This function is documented on page 84.)

`\int_show:n` We don't use the TeX primitive `\showthe` to show integer expressions: this gives a more unified output.

```
5936 \cs_new_protected:Npn \int_show:n
5937   { \msg_show_eval:Nn \int_eval:n }
```

(End definition for `\int_show:n`. This function is documented on page 84.)

`\int_log:N` Diagnostics.

```
\int_log:c 5938 \cs_new_eq:NN \int_log:N \__kernel_register_log:N
5939 \cs_generate_variant:Nn \int_log:N { c }
```

(End definition for `\int_log:N`. This function is documented on page 84.)

`\int_log:n` Similar to `\int_show:n`.

```
5940 \cs_new_protected:Npn \int_log:n
5941   { \msg_log_eval:Nn \int_eval:n }
```

(End definition for `\int_log:n`. This function is documented on page 84.)

8.11 Constant integers

`\c_zero` Again, in `l3basics`

(End definition for `\c_zero`. This variable is documented on page 85.)

`\c_one` Low-number values not previously defined.

```
\c_two 5942 \int_const:Nn \c_one { 1 }
\c_three 5943 \int_const:Nn \c_two { 2 }
\c_four 5944 \int_const:Nn \c_three { 3 }
\c_five 5945 \int_const:Nn \c_four { 4 }
\c_six 5946 \int_const:Nn \c_five { 5 }
\c_seven 5947 \int_const:Nn \c_six { 6 }
\c_eight 5948 \int_const:Nn \c_seven { 7 }
\c_nine 5949 \int_const:Nn \c_eight { 8 }
\c_ten 5950 \int_const:Nn \c_nine { 9 }
\c_eleven 5951 \int_const:Nn \c_ten { 10 }
\c_twelve 5952 \int_const:Nn \c_eleven { 11 }
\c_thirteen 5953 \int_const:Nn \c_twelve { 12 }
\c_fourteen 5954 \int_const:Nn \c_thirteen { 13 }
\c_fifteen 5955 \int_const:Nn \c_fourteen { 14 }
\c_sixteen 5956 \int_const:Nn \c_fifteen { 15 }
5957 \int_const:Nn \c_sixteen { 16 }
```

(End definition for `\c_one` and others. These variables are documented on page 85.)

`\c_thirty_two` One middling value.

```
5958 \int_const:Nn \c_thirty_two { 32 }
```

(End definition for `\c_thirty_two`. This variable is documented on page 85.)

`\c_two_hundred_fifty_five` Two classic mid-range integer constants.

```
\c_two_hundred_fifty_six 5959 \int_const:Nn \c_two_hundred_fifty_five { 255 }
5960 \int_const:Nn \c_two_hundred_fifty_six { 256 }
```

(End definition for `\c_two_hundred_fifty_five` and `\c_two_hundred_fifty_six`. These variables are documented on page 85.)

`\c_one_hundred` Simple runs of powers of ten.
`\c_one_thousand` 5961 `\int_const:Nn \c_one_hundred { 100 }`
`\c_ten_thousand` 5962 `\int_const:Nn \c_one_thousand { 1000 }`
5963 `\int_const:Nn \c_ten_thousand { 10000 }`

(End definition for `\c_one_hundred`, `\c_one_thousand`, and `\c_ten_thousand`. These variables are documented on page 85.)

`\c_max_int` The largest number allowed is $2^{31} - 1$
5964 `\int_const:Nn \c_max_int { 2 147 483 647 }`

(End definition for `\c_max_int`. This variable is documented on page 85.)

`\c_max_char_int` The largest character code is 1114111 (hexadecimal 10FFFF) in X_ƎT_ƎX and LuaT_ƎX and 255 in other engines. In many places pT_ƎX and upT_ƎX support larger character codes but for instance the values of `\lccode` are restricted to [0, 255].

```
5965 \int_const:Nn \c_max_char_int
5966 {
5967   \if_int_odd:w 0
5968     \cs_if_exist:NT \luatex luatexversion:D { 1 }
5969     \cs_if_exist:NT \xetex XeTeXversion:D { 1 } ~
5970     "10FFFF
5971   \else:
5972     "FF
5973   \fi:
5974 }
```

(End definition for `\c_max_char_int`. This variable is documented on page 85.)

8.12 Scratch integers

`\l_tmpa_int` We provide two local and two global scratch counters, maybe we need more or less.
`\l_tmpb_int` 5975 `\int_new:N \l_tmpa_int`
`\g_tmpa_int` 5976 `\int_new:N \l_tmpb_int`
`\g_tmpb_int` 5977 `\int_new:N \g_tmpa_int`
5978 `\int_new:N \g_tmpb_int`

(End definition for `\l_tmpa_int` and others. These variables are documented on page 85.)

8.13 Deprecated

`\c_minus_one` The actual allocation mechanism is in `l3alloc`; it requires `\c_one` to be defined. In package mode, reuse `\m@ne`. We also store in two global token lists some code for `\debug_deprecation_on:` and `\debug_deprecation_off:`. For the latter, we need to locally set `\c_minus_one` back to the constant hence use a private name. We use `\tex_let:D` directly because `\c_minus_one` (as all deprecated commands) is made outer by `\debug_deprecation_on:`.

```
5979 <package>\cs_gset_eq:NN \c__deprecation_minus_one \m@ne
5980 <initex>\int_const:Nn \c__deprecation_minus_one { -1 }
5981 \cs_new_eq:NN \c_minus_one \c__deprecation_minus_one
5982 \__debug:TF
```



```

5983 {
5984   \tl_gput_right:Nn \g__debug_deprecation_on_tl
5985   { \__deprecation_error:Nnn \c_minus_one { -1 } { 2018-12-31 } }
5986   \tl_gput_right:Nn \g__debug_deprecation_off_tl
5987   { \tex_let:D \c_minus_one \c__deprecation_minus_one }
5988 }
5989 { }

```

(End definition for \c_minus_one.)

```
5990 </initex | package>
```

9 l3intarray implementation

```
5991 <*initex | package>
```

```
5992 <@@=intarray>
```

9.1 Allocating arrays

\g__intarray_font_int Used to assign one font per array.

```
5993 \int_new:N \g__intarray_font_int
```

(End definition for \g__intarray_font_int.)

__intarray_new:Nn Declare #1 to be a font (arbitrarily cmr10 at a never-used size). Store the array's size as the \hyphenchar of that font and make sure enough \fontdimen are allocated, by setting the last one. Then clear any \fontdimen that cmr10 starts with. It seems LuaTeX's cmr10 has an extra \fontdimen parameter number 8 compared to other engines (for a math font we would replace 8 by 22 or some such).

```

5994 \cs_new_protected:Npn \__intarray_new:Nn #1#2
5995 {
5996   \__chk_if_free_cs:N #1
5997   \int_gincr:N \g__intarray_font_int
5998   \tex_global:D \tex_font:D #1 = cmr10-at~ \g__intarray_font_int sp \scan_stop:
5999   \tex_hyphenchar:D #1 = \int_eval:n {#2} \scan_stop:
6000   \int_compare:nNnT { \tex_hyphenchar:D #1 } > 0
6001     { \tex_fontdimen:D \tex_hyphenchar:D #1 #1 = 0 sp \scan_stop: }
6002   \int_step_inline:nnnn { 1 } { 1 } { 8 }
6003     { \tex_fontdimen:D ##1 #1 = 0 sp \scan_stop: }
6004 }

```

(End definition for __intarray_new:Nn.)

__intarray_count:N Size of an array.

```
6005 \cs_new:Npn \__intarray_count:N #1 { \tex_the:D \tex_hyphenchar:D #1 }
```

(End definition for __intarray_count:N.)

9.2 Array items

`__intarray_gset:Nnn` Set the appropriate `\fontdimen`. The slow version checks the position and value are within bounds.
`__intarray_gset_fast:Nnn`
`__intarray_gset_aux:Nnn`

```

6006 \cs_new_protected:Npn \__intarray_gset_fast:Nnn #1#2#3
6007 { \tex_fontdimen:D \int_eval:n {#2} #1 = \int_eval:n {#3} sp \scan_stop: }
6008 \cs_new_protected:Npn \__intarray_gset:Nnn #1#2#3
6009 {
6010   \exp_args:Nff \__intarray_gset_aux:Nnn #1
6011   { \int_eval:n {#2} } { \int_eval:n {#3} }
6012 }
6013 \cs_new_protected:Npn \__intarray_gset_aux:Nnn #1#2#3
6014 {
6015   \int_compare:nTF { 1 <= #2 <= \__intarray_count:N #1 }
6016   {
6017     \int_compare:nTF { - \c_max_dim <= \int_abs:n {#3} <= \c_max_dim }
6018     { \__intarray_gset_fast:Nnn #1 {#2} {#3} }
6019     {
6020       \__msg_kernel_error:nnxxxx { kernel } { overflow }
6021       { \token_to_str:N #1 } {#2} {#3}
6022       { \int_compare:nNnT {#3} < 0 { - } \__int_value:w \c_max_dim }
6023       \__intarray_gset_fast:Nnn #1 {#2}
6024       { \int_compare:nNnT {#3} < 0 { - } \c_max_dim }
6025     }
6026   }
6027   {
6028     \__msg_kernel_error:nnxxx { kernel } { out-of-bounds }
6029     { \token_to_str:N #1 } {#2} { \__intarray_count:N #1 }
6030   }
6031 }

```

(End definition for `__intarray_gset:Nnn`, `__intarray_gset_fast:Nnn`, and `__intarray_gset_aux:Nnn`.)

`__intarray_item:Nn` Get the appropriate `\fontdimen` and perform bound checks if requested.
`__intarray_item_fast:Nn`
`__intarray_item_aux:Nn`

```

6032 \cs_new:Npn \__intarray_item_fast:Nn #1#2
6033 { \__int_value:w \tex_fontdimen:D \int_eval:n {#2} #1 }
6034 \cs_new:Npn \__intarray_item:Nn #1#2
6035 { \exp_args:Nf \__intarray_item_aux:Nn #1 { \int_eval:n {#2} } }
6036 \cs_new:Npn \__intarray_item_aux:Nn #1#2
6037 {
6038   \int_compare:nTF { 1 <= #2 <= \__intarray_count:N #1 }
6039   { \__intarray_item_fast:Nn #1 {#2} }
6040   {
6041     \__msg_kernel_expandable_error:nnnnn { kernel } { out-of-bounds }
6042     { \token_to_str:N #1 } {#2} { \__intarray_count:N #1 }
6043     0
6044   }
6045 }

```

(End definition for `__intarray_item:Nn`, `__intarray_item_fast:Nn`, and `__intarray_item_aux:Nn`.)

```

6046 </initex | package>

```

10 l3flag implementation

6047 `*initex | package)`

6048 `\@@=flag)`

The following test files are used for this code: m3flag001.

10.1 Non-expandable flag commands

The height h of a flag (initially zero) is stored by setting control sequences of the form `\flag <name> <integer>` to `\relax` for $0 \leq \langle integer \rangle < h$. When a flag is raised, a “trap” function `\flag <name>` is called. The existence of this function is also used to test for the existence of a flag.

\flag_new:n For each flag, we define a “trap” function, which by default simply increases the flag by 1 by letting the appropriate control sequence to `\relax`. This can be done expandably!

```
6049 \cs_new_protected:Npn \flag_new:n #1
6050 {
6051   \cs_new:cpn { flag~#1 } ##1 ;
6052   { \exp_after:wN \use_none:n \cs:w flag~#1~##1 \cs_end: }
6053 }
```

(End definition for \flag_new:n. This function is documented on page 89.)

\flag_clear:n **__flag_clear:wn** Undefine control sequences, starting from the 0 flag, upwards, until reaching an undefined control sequence. We don’t use `\cs_undefine:c` because that would act globally. When the option `check-declarations` is used, check for the function defined by `\flag_new:n`.

```
6054 \__debug_patch:nnNpn
6055 { \exp_args:Nc \__debug_chk_var_exist:N { flag~#1 } } { }
6056 \cs_new_protected:Npn \flag_clear:n #1 { \__flag_clear:wn 0 ; {#1} }
6057 \cs_new_protected:Npn \__flag_clear:wn #1 ; #2
6058 {
6059   \if_cs_exist:w flag~#2~#1 \cs_end:
6060   \cs_set_eq:cN { flag~#2~#1 } \tex_undefined:D
6061   \exp_after:wN \__flag_clear:wn
6062   \__int_value:w \__int_eval:w 1 + #1
6063   \else:
6064     \use_i:nnn
6065   \fi:
6066   ; {#2}
6067 }
```

(End definition for \flag_clear:n and __flag_clear:wn. This function is documented on page 89.)

\flag_clear_new:n As for other datatypes, clear the `<flag>` or create a new one, as appropriate.

```
6068 \cs_new_protected:Npn \flag_clear_new:n #1
6069 { \flag_if_exist:nTF {#1} { \flag_clear:n } { \flag_new:n } {#1} }
```

(End definition for \flag_clear_new:n. This function is documented on page 89.)

\flag_show:n **\flag_log:n** **__flag_show:Nn** Show the height (terminal or log file) using appropriate `l3msg` auxiliaries.

```
6070 \cs_new_protected:Npn \flag_show:n { \__flag_show:Nn \tl_show:n }
6071 \cs_new_protected:Npn \flag_log:n { \__flag_show:Nn \tl_log:n }
6072 \cs_new_protected:Npn \__flag_show:Nn #1#2
6073 {
```

```

6074 \exp_args:Nc \__kernel_check_defined:NT { flag~#2 }
6075 {
6076   \exp_args:Nx #1
6077   { \tl_to_str:n { flag~#2~height } = \flag_height:n {#2} }
6078 }
6079 }

```

(End definition for `\flag_show:n`, `\flag_log:n`, and `__flag_show:Nn`. These functions are documented on page 89.)

10.2 Expandable flag commands

`__flag_chk_exist:n` Analogue of `__debug_chk_var_exist:N` for flags, and with an expandable error. We need to add checks by hand because flags are not implemented in terms of other variables. Not all functions need to be patched since some are defined in terms of others.

```

6080 \*package
6081 \tex_ifodd:D \l@expl@enable@debug@bool
6082 \cs_new:Npn \__flag_chk_exist:n #1
6083 {
6084   \flag_if_exist:nF {#1}
6085   {
6086     \__msg_kernel_expandable_error:nnn
6087     { kernel } { bad-variable } { flag~#1~ }
6088   }
6089 }
6090 \fi:
6091 \*package

```

(End definition for `__flag_chk_exist:n`.)

`\flag_if_exist_p:n` A flag exist if the corresponding trap `\flag <flag name>:n` is defined.

```

\flag_if_exist:nTF
6092 \prg_new_conditional:Npnn \flag_if_exist:n #1 { p , T , F , TF }
6093 {
6094   \cs_if_exist:cTF { flag~#1 }
6095   { \prg_return_true: } { \prg_return_false: }
6096 }

```

(End definition for `\flag_if_exist:nTF`. This function is documented on page 90.)

`\flag_if_raised_p:n` Test if the flag has a non-zero height, by checking the 0 control sequence.

```

\flag_if_raised:nTF
6097 \__debug_patch_conditional:nNNpnn { \__flag_chk_exist:n {#1} }
6098 \prg_new_conditional:Npnn \flag_if_raised:n #1 { p , T , F , TF }
6099 {
6100   \if_cs_exist:w flag~#1~0 \cs_end:
6101   \prg_return_true:
6102   \else:
6103   \prg_return_false:
6104   \fi:
6105 }

```

(End definition for `\flag_if_raised:nTF`. This function is documented on page 90.)

\flag_height:n Extract the value of the flag by going through all of the control sequences starting from 0.

```

6106 \__debug_patch:nnNNpn { \__flag_chk_exist:n {#1} } { }
6107 \cs_new:Npn \flag_height:n #1 { \__flag_height_loop:wn 0; {#1} }
6108 \cs_new:Npn \__flag_height_loop:wn #1 ; #2
6109 {
6110   \if_cs_exist:w flag~#2~#1 \cs_end:
6111     \exp_after:wN \__flag_height_loop:wn \__int_value:w \__int_eval:w 1 +
6112   \else:
6113     \exp_after:wN \__flag_height_end:wn
6114   \fi:
6115   #1 ; {#2}
6116 }
6117 \cs_new:Npn \__flag_height_end:wn #1 ; #2 {#1}

```

(End definition for \flag_height:n, __flag_height_loop:wn, and __flag_height_end:wn. This function is documented on page 90.)

\flag_raise:n Simply apply the trap to the height, after expanding the latter.

```

6118 \cs_new:Npn \flag_raise:n #1
6119 {
6120   \cs:w flag~#1 \exp_after:wN \cs_end:
6121   \__int_value:w \flag_height:n {#1} ;
6122 }

```

(End definition for \flag_raise:n. This function is documented on page 90.)

```
6123 </initex | package>
```

11 l3quark implementation

The following test files are used for this code: m3quark001.lvt.

```
6124 (*initex | package)
```

11.1 Quarks

```
6125 <@@=quark>
```

\quark_new:N Allocate a new quark.

```

6126 \__debug_patch:nnNNpn { \__debug_chk_var_scope:NN q #1 } { }
6127 \cs_new_protected:Npn \quark_new:N #1
6128 {
6129   \__chk_if_free_cs:N #1
6130   \cs_gset_nopar:Npn #1 {#1}
6131 }

```

(End definition for \quark_new:N. This function is documented on page 91.)

\q_nil Some “public” quarks. \q_stop is an “end of argument” marker, \q_nil is a empty value and \q_no_value marks an empty argument.

```

6132 \quark_new:N \q_nil
6133 \quark_new:N \q_mark
6134 \quark_new:N \q_no_value
6135 \quark_new:N \q_stop

```

(End definition for `\q_nil` and others. These variables are documented on page 92.)

`\q_recursion_tail` Quarks for ending recursions. Only ever used there! `\q_recursion_tail` is appended to whatever list structure we are doing recursion on, meaning it is added as a proper list item with whatever list separator is in use. `\q_recursion_stop` is placed directly after the list.

```
6136 \quark_new:N \q_recursion_tail
6137 \quark_new:N \q_recursion_stop
```

(End definition for `\q_recursion_tail` and `\q_recursion_stop`. These variables are documented on page 93.)

`\quark_if_recursion_tail_stop:N` When doing recursions, it is easy to spend a lot of time testing if the end marker has been found. To avoid this, a dedicated end marker is used each time a recursion is set up. Thus if the marker is found everything can be wrapper up and finished off. The simple case is when the test can guarantee that only a single token is being tested. In this case, there is just a dedicated copy of the standard quark test. Both a gobbling version and one inserting end code are provided.

```
6138 \cs_new:Npn \quark_if_recursion_tail_stop:N #1
6139 {
6140   \if_meaning:w \q_recursion_tail #1
6141   \exp_after:wN \use_none_delimit_by_q_recursion_stop:w
6142   \fi:
6143 }
6144 \cs_new:Npn \quark_if_recursion_tail_stop_do:Nn #1
6145 {
6146   \if_meaning:w \q_recursion_tail #1
6147   \exp_after:wN \use_i_delimit_by_q_recursion_stop:nw
6148   \else:
6149   \exp_after:wN \use_none:n
6150   \fi:
6151 }
```

(End definition for `\quark_if_recursion_tail_stop:N` and `\quark_if_recursion_tail_stop_do:Nn`. These functions are documented on page 93.)

`\quark_if_recursion_tail_stop:n` See `\quark_if_nil:nTF` for the details. Expanding `__quark_if_recursion_tail:w` once in front of the tokens chosen here gives an empty result if and only if #1 is exactly `\q_recursion_tail`.

```
6152 \cs_new:Npn \quark_if_recursion_tail_stop:n #1
6153 {
6154   \tl_if_empty:oTF
6155   { \__quark_if_recursion_tail:w {} #1 {} ?! \q_recursion_tail ??? }
6156   { \use_none_delimit_by_q_recursion_stop:w }
6157   { }
6158 }
6159 \cs_new:Npn \quark_if_recursion_tail_stop_do:nn #1
6160 {
6161   \tl_if_empty:oTF
6162   { \__quark_if_recursion_tail:w {} #1 {} ?! \q_recursion_tail ??? }
6163   { \use_i_delimit_by_q_recursion_stop:nw }
6164   { \use_none:n }
6165 }
6166 \cs_new:Npn \__quark_if_recursion_tail:w
```

```

6167     #1 \q_recursion_tail #2 ? #3 ?! { #1 #2 }
6168 \cs_generate_variant:Nn \quark_if_recursion_tail_stop:n { o }
6169 \cs_generate_variant:Nn \quark_if_recursion_tail_stop_do:nn { o }

(End definition for \quark_if_recursion_tail_stop:n, \quark_if_recursion_tail_stop_do:nn, and
\_quark_if_recursion_tail:w. These functions are documented on page 93.)

```

_quark_if_recursion_tail_break:NN
_quark_if_recursion_tail_break:nN

Analogs of the \quark_if_recursion_tail_stop... functions. Break the mapping using #2.

```

6170 \cs_new:Npn \_quark_if_recursion_tail_break:NN #1#2
6171 {
6172     \if_meaning:w \q_recursion_tail #1
6173     \exp_after:wN #2
6174     \fi:
6175 }
6176 \cs_new:Npn \_quark_if_recursion_tail_break:nN #1#2
6177 {
6178     \tl_if_empty:oTF
6179     { \_quark_if_recursion_tail:w {} #1 {} ?! \q_recursion_tail ??? }
6180     {#2}
6181     { }
6182 }

(End definition for \_quark_if_recursion_tail_break:NN and \_quark_if_recursion_tail_break:nN.)

```

\quark_if_nil_p:N Here we test if we found a special quark as the first argument. We better start with
\quark_if_nil:N \underline{TF} \q_no_value as the first argument since the whole thing may otherwise loop if #1 is
\quark_if_no_value_p:N wrongly given a string like aabc instead of a single token.⁸

```

\quark_if_no_value_p:c 6183 \prg_new_conditional:Npnn \quark_if_nil:N #1 { p, T , F , TF }
\quark_if_no_value:N $\underline{TF}$  6184 {
\quark_if_no_value:c $\underline{TF}$  6185     \if_meaning:w \q_nil #1
6186     \prg_return_true:
6187     \else:
6188     \prg_return_false:
6189     \fi:
6190 }
6191 \prg_new_conditional:Npnn \quark_if_no_value:N #1 { p, T , F , TF }
6192 {
6193     \if_meaning:w \q_no_value #1
6194     \prg_return_true:
6195     \else:
6196     \prg_return_false:
6197     \fi:
6198 }
6199 \cs_generate_variant:Nn \quark_if_no_value_p:N { c }
6200 \cs_generate_variant:Nn \quark_if_no_value:NT { c }
6201 \cs_generate_variant:Nn \quark_if_no_value:NF { c }
6202 \cs_generate_variant:Nn \quark_if_no_value:NTF { c }

```

(End definition for \quark_if_nil:NTF and \quark_if_no_value:NTF. These functions are documented on page 92.)

⁸It may still loop in special circumstances however!

`\quark_if_nil_p:n` Let us explain `\quark_if_nil:n(TF)`. Expanding `__quark_if_nil:w` once is safe thanks to the trailing `\q_nil ? ? !`. The result of expanding once is empty if and only if both delimited arguments #1 and #2 are empty and #3 is delimited by the last tokens `?!`. Thanks to the leading `{}`, the argument #1 is empty if and only if the argument of `\quark_if_nil:n` starts with `\q_nil`. The argument #2 is empty if and only if this `\q_nil` is followed immediately by `?` or by `{}`?, coming either from the trailing tokens in the definition of `\quark_if_nil:n`, or from its argument. In the first case, `__quark_if_nil:w` is followed by `{}\q_nil {}? !\q_nil ? ? !`, hence #3 is delimited by the final `?!`, and the test returns `true` as wanted. In the second case, the result is not empty since the first `?!` in the definition of `\quark_if_nil:n` stop #3.

```

6203 \prg_new_conditional:Npnn \quark_if_nil:n #1 { p , T , F , TF }
6204 {
6205     \__tl_if_empty_return:o
6206     { \__quark_if_nil:w {} #1 {} ? ! \q_nil ? ? ! }
6207 }
6208 \cs_new:Npn \__quark_if_nil:w #1 \q_nil #2 ? #3 ? ! { #1 #2 }
6209 \prg_new_conditional:Npnn \quark_if_no_value:n #1 { p , T , F , TF }
6210 {
6211     \__tl_if_empty_return:o
6212     { \__quark_if_no_value:w {} #1 {} ? ! \q_no_value ? ? ! }
6213 }
6214 \cs_new:Npn \__quark_if_no_value:w #1 \q_no_value #2 ? #3 ? ! { #1 #2 }
6215 \cs_generate_variant:Nn \quark_if_nil_p:n { V , o }
6216 \cs_generate_variant:Nn \quark_if_nil:nTF { V , o }
6217 \cs_generate_variant:Nn \quark_if_nil:nT { V , o }
6218 \cs_generate_variant:Nn \quark_if_nil:nF { V , o }

```

(End definition for `\quark_if_nil:nTF` and others. These functions are documented on page 92.)

`\q__tl_act_mark` These private quarks are needed by `l3tl`, but that is loaded before the quark module, hence their definition is deferred.

```

6219 \quark_new:N \q__tl_act_mark
6220 \quark_new:N \q__tl_act_stop

```

(End definition for `\q__tl_act_mark` and `\q__tl_act_stop`.)

11.2 Scan marks

```

6221 <@@=scan>

```

`\g__scan_marks_tl` The list of all scan marks currently declared.

```

6222 \tl_new:N \g__scan_marks_tl

```

(End definition for `\g__scan_marks_tl`.)

`__scan_new:N` Check whether the variable is already a scan mark, then declare it to be equal to `\scan_stop`: globally.

```

6223 \cs_new_protected:Npn \__scan_new:N #1
6224 {
6225     \tl_if_in:NnTF \g__scan_marks_tl { #1 }
6226     {
6227         \__msg_kernel_error:nnx { kernel } { scanmark-already-defined }
6228         { \token_to_str:N #1 }
6229     }

```



```

6230     {
6231         \tl_gput_right:Nn \g__scan_marks_tl {#1}
6232         \cs_new_eq:NN #1 \scan_stop:
6233     }
6234 }

```

(End definition for __scan_new:N.)

\s__stop We only declare one scan mark here, more can be defined by specific modules.

```

6235 \__scan_new:N \s__stop

```

(End definition for \s__stop.)

_use_none_delimit_by_s__stop:w Similar to \use_none_delimit_by_q_stop:w.

```

6236 \cs_new:Npn \__use_none_delimit_by_s__stop:w #1 \s__stop { }

```

(End definition for _use_none_delimit_by_s__stop:w.)

\s__seq This private scan mark is needed by l3seq, but that is loaded before the quark module, hence its definition is deferred.

```

6237 \__scan_new:N \s__seq

```

(End definition for \s__seq.)

```

6238 </initex | package>

```

12 l3prg implementation

The following test files are used for this code: m3prg001.lvt,m3prg002.lvt,m3prg003.lvt.

```

6239 <*initex | package>

```

12.1 Primitive conditionals

\if_bool:N Those two primitive TeX conditionals are synonyms.
\if_predicate:w

```

6240 \cs_new_eq:NN \if_bool:N \tex_ifodd:D

```

```

6241 \cs_new_eq:NN \if_predicate:w \tex_ifodd:D

```

(End definition for \if_bool:N and \if_predicate:w. These functions are documented on page 103.)

12.2 Defining a set of conditional functions

\prg_set_conditional:Npnn These are all defined in l3basics, as they are needed “early”. This is just a reminder!

\prg_new_conditional:Npnn

(End definition for \prg_set_conditional:Npnn and others. These functions are documented on page 96.)

\prg_set_protected_conditional:Npnn

\prg_new_protected_conditional:Npnn

\prg_set_conditional:Nnn

\prg_new_conditional:Nnn

\prg_set_protected_conditional:Nnn

\prg_new_protected_conditional:Nnn

\prg_set_eq_conditional:NNn

\prg_new_eq_conditional:NNn

\prg_return_true:

\prg_return_false:

12.3 The boolean data type

6242 `<@@=bool>`

`\bool_new:N` Boolean variables have to be initiated when they are created. Other than that there is
`\bool_new:c` not much to say here.

6243 `\cs_new_protected:Npn \bool_new:N #1 { \cs_new_eq:NN #1 \c_false_bool }`
 6244 `\cs_generate_variant:Nn \bool_new:N { c }`

(End definition for `\bool_new:N`. This function is documented on page 98.)

`\bool_set_true:N` Setting is already pretty easy. When `check-declarations` is active, the definitions are
`\bool_set_true:c` patched to make sure the boolean exists. This is needed because booleans are not based
`\bool_gset_true:N` on token lists nor on T_EX registers.

`\bool_gset_true:c` 6245 `__debug_patch:nnNNpn { __debug_chk_var_local:N #1 } { }`
`\bool_set_false:N` 6246 `\cs_new_protected:Npn \bool_set_true:N #1`
`\bool_set_false:c` 6247 `{ \cs_set_eq:NN #1 \c_true_bool }`
`\bool_gset_false:N` 6248 `__debug_patch:nnNNpn { __debug_chk_var_local:N #1 } { }`
`\bool_gset_false:c` 6249 `\cs_new_protected:Npn \bool_set_false:N #1`
 6250 `{ \cs_set_eq:NN #1 \c_false_bool }`
 6251 `__debug_patch:nnNNpn { __debug_chk_var_global:N #1 } { }`
 6252 `\cs_new_protected:Npn \bool_gset_true:N #1`
 6253 `{ \cs_gset_eq:NN #1 \c_true_bool }`
 6254 `__debug_patch:nnNNpn { __debug_chk_var_global:N #1 } { }`
 6255 `\cs_new_protected:Npn \bool_gset_false:N #1`
 6256 `{ \cs_gset_eq:NN #1 \c_false_bool }`
 6257 `\cs_generate_variant:Nn \bool_set_true:N { c }`
 6258 `\cs_generate_variant:Nn \bool_set_false:N { c }`
 6259 `\cs_generate_variant:Nn \bool_gset_true:N { c }`
 6260 `\cs_generate_variant:Nn \bool_gset_false:N { c }`

(End definition for `\bool_set_true:N` and others. These functions are documented on page 98.)

`\bool_set_eq:NN` The usual copy code. While it would be cleaner semantically to copy the `\cs_set_eq:NN`
`\bool_set_eq:cN` family of functions, we copy `\tl_set_eq:NN` because that has the correct checking code.

`\bool_set_eq:Nc` 6261 `\cs_new_eq:NN \bool_set_eq:NN \tl_set_eq:NN`
`\bool_set_eq:cc` 6262 `\cs_new_eq:NN \bool_gset_eq:NN \tl_gset_eq:NN`
`\bool_gset_eq:NN` 6263 `\cs_generate_variant:Nn \bool_set_eq:NN { Nc, cN, cc }`
`\bool_gset_eq:cN` 6264 `\cs_generate_variant:Nn \bool_gset_eq:NN { Nc, cN, cc }`

`\bool_gset_eq:Nc` (End definition for `\bool_set_eq:NN` and `\bool_gset_eq:NN`. These functions are documented on page
`\bool_gset_eq:cc` 99.)

`\bool_set:Nn` This function evaluates a boolean expression and assigns the first argument the meaning
`\bool_set:cn` `\c_true_bool` or `\c_false_bool`. Again, we include some checking code.

`\bool_gset:Nn` 6265 `__debug_patch:nnNNpn { __debug_chk_var_local:N #1 } { }`
`\bool_gset:cn` 6266 `\cs_new_protected:Npn \bool_set:Nn #1#2`
 6267 `{ \tex_chardef:D #1 = \bool_if_p:n {#2} }`
 6268 `__debug_patch:nnNNpn { __debug_chk_var_global:N #1 } { }`
 6269 `\cs_new_protected:Npn \bool_gset:Nn #1#2`
 6270 `{ \tex_global:D \tex_chardef:D #1 = \bool_if_p:n {#2} }`
 6271 `\cs_generate_variant:Nn \bool_set:Nn { c }`
 6272 `\cs_generate_variant:Nn \bool_gset:Nn { c }`

(End definition for `\bool_set:Nn` and `\bool_gset:Nn`. These functions are documented on page 99.)

`\bool_if_p:N` Straight forward here. We could optimize here if we wanted to as the boolean can just be input directly.

```

\bool_if:N $\overline{TF}$  6273 \prg_new_conditional:Npnn \bool_if:N #1 { p , T , F , TF }
\bool_if:c $\overline{TF}$  6274 {
6275     \if_bool:N #1
6276     \prg_return_true:
6277     \else:
6278     \prg_return_false:
6279     \fi:
6280 }
6281 \cs_generate_variant:Nn \bool_if_p:N { c }
6282 \cs_generate_variant:Nn \bool_if:NT { c }
6283 \cs_generate_variant:Nn \bool_if:NF { c }
6284 \cs_generate_variant:Nn \bool_if:NTF { c }

```

(End definition for `\bool_if:NTF`. This function is documented on page 99.)

`\bool_show:n` Show the truth value of the boolean, as true or false.

```

\bool_log:n 6285 \cs_new_protected:Npn \bool_show:n
\__bool_to_str:n 6286 { \msg_show_eval:Nn \__bool_to_str:n }
6287 \cs_new_protected:Npn \bool_log:n
6288 { \msg_log_eval:Nn \__bool_to_str:n }
6289 \cs_new:Npn \__bool_to_str:n #1
6290 { \bool_if:nTF {#1} { true } { false } }

```

(End definition for `\bool_show:n`, `\bool_log:n`, and `__bool_to_str:n`. These functions are documented on page 99.)

`\bool_show:N` Show the truth value of the boolean, as true or false.

```

\bool_show:c 6291 \cs_new_protected:Npn \bool_show:N { \__bool_show:NN \tl_show:n }
\bool_log:N 6292 \cs_generate_variant:Nn \bool_show:N { c }
\bool_log:c 6293 \cs_new_protected:Npn \bool_log:N { \__bool_show:NN \tl_log:n }
\__bool_show:NN 6294 \cs_generate_variant:Nn \bool_log:N { c }
6295 \cs_new_protected:Npn \__bool_show:NN #1#2
6296 {
6297     \__kernel_check_defined:NT #2
6298     { \exp_args:Nx #1 { \token_to_str:N #2 = \__bool_to_str:n {#2} } }
6299 }

```

(End definition for `\bool_show:N`, `\bool_log:N`, and `__bool_show:NN`. These functions are documented on page 99.)

`\l_tmpa_bool` A few booleans just if you need them.

```

\l_tmpb_bool 6300 \bool_new:N \l_tmpa_bool
\g_tmpa_bool 6301 \bool_new:N \l_tmpb_bool
\g_tmpb_bool 6302 \bool_new:N \g_tmpa_bool
6303 \bool_new:N \g_tmpb_bool

```

(End definition for `\l_tmpa_bool` and others. These variables are documented on page 99.)

`\bool_if_exist_p:N` Copies of the `cs` functions defined in `l3basics`.

```

\bool_if_exist_p:c 6304 \prg_new_eq_conditional:NNn \bool_if_exist:N \cs_if_exist:N
\bool_if_exist:N $\overline{TF}$  6305 { TF , T , F , p }
\bool_if_exist:c $\overline{TF}$  6306 \prg_new_eq_conditional:NNn \bool_if_exist:c \cs_if_exist:c
6307 { TF , T , F , p }

```

(End definition for `\bool_if_exist:NTF`. This function is documented on page 99.)

12.4 Boolean expressions

`\bool_if_p:n` Evaluating the truth value of a list of predicates is done using an input syntax somewhat similar to the one found in other programming languages with (and) for grouping, ! for logical “Not”, && for logical “And” and || for logical “Or”. However, they perform eager evaluation. We shall use the terms Not, And, Or, Open and Close for these operations.

`\bool_if:nTF` Any expression is terminated by a Close operation. Evaluation happens from left to right in the following manner using a GetNext function:

- If an Open is seen, start evaluating a new expression using the Eval function and call GetNext again.
- If a Not is seen, remove the ! and call a GetNext function with the logic reversed.
- If none of the above, reinsert the token found (this is supposed to be a predicate function) in front of an Eval function, which evaluates it to the boolean value $\langle true \rangle$ or $\langle false \rangle$.

The Eval function then contains a post-processing operation which grabs the instruction following the predicate. This is either And, Or or Close. In each case the truth value is used to determine where to go next. The following situations can arise:

$\langle true \rangle$ **And** Current truth value is true, logical And seen, continue with GetNext to examine truth value of next boolean (sub-)expression.

$\langle false \rangle$ **And** Current truth value is false, logical And seen, stop using the values of predicates within this sub-expression until the next Close. Then return $\langle false \rangle$.

$\langle true \rangle$ **Or** Current truth value is true, logical Or seen, stop using the values of predicates within this sub-expression until the nearest Close. Then return $\langle true \rangle$.

$\langle false \rangle$ **Or** Current truth value is false, logical Or seen, continue with GetNext to examine truth value of next boolean (sub-)expression.

$\langle true \rangle$ **Close** Current truth value is true, Close seen, return $\langle true \rangle$.

$\langle false \rangle$ **Close** Current truth value is false, Close seen, return $\langle false \rangle$.

```

6308 \prg_new_conditional:Npmn \bool_if:n #1 { T , F , TF }
6309 {
6310   \if_predicate:w \bool_if_p:n {#1}
6311   \prg_return_true:
6312   \else:
6313   \prg_return_false:
6314   \fi:
6315 }
```

(End definition for `\bool_if:nTF`. This function is documented on page 101.)

`\bool_if_p:n` First issue a `\group_align_safe_begin:` as we are using && as syntax shorthand for the And operation and we need to hide it for T_EX. This group is closed after `__bool_get_next:NN` returns `\c_true_bool` or `\c_false_bool`. That function requires the trailing parenthesis to know where the expression ends.

```

6316 \cs_new:Npmn \bool_if_p:n #1
6317 {
6318   \group_align_safe_begin:
```

```

6319     \exp_after:wN
6320     \group_align_safe_end:
6321     \exp:w \exp_end_continue_f:w % (
6322     \__bool_get_next:NN \use_i:nnnn #1 )
6323 }

```

(End definition for \bool_if_p:n. This function is documented on page 101.)

`__bool_get_next:NN` The GetNext operation. Its first argument is `\use_i:nnnn`, `\use_ii:nnnn`, `\use_iii:nnnn`, or `\use_iv:nnnn` (we call these “states”). In the first state, this function eventually expand to the truth value `\c_true_bool` or `\c_false_bool` of the expression which follows until the next unmatched closing parenthesis. For instance “`__bool_get_next:NN \use_i:nnnn \c_true_bool && \c_true_bool)`” (including the closing parenthesis) expands to `\c_true_bool`. In the second state (after a `!`) the logic is reversed. We call these two states “normal” and the next two “skipping”. In the third state (after `\c_true_bool||`) it always returns `\c_true_bool`. In the fourth state (after `\c_false_bool&&`) it always returns `\c_false_bool` and also stops when encountering `||`, not only parentheses. This code itself is a switch: if what follows is neither `!` nor `(`, we assume it is a predicate.

```

6324 \cs_new:Npn \__bool_get_next:NN #1#2
6325 {
6326     \use:c
6327     {
6328         __bool_
6329         \if_meaning:w !#2 ! \else: \if_meaning:w (#2 ( \else: p \fi: \fi:
6330         :Nw
6331     }
6332     #1 #2
6333 }

```

(End definition for __bool_get_next:NN.)

`__bool_!:Nw` The Not operation reverses the logic: it discards the `!` token and calls the GetNext operation with the appropriate first argument. Namely the first and second states are interchanged, but after `\c_true_bool||` or `\c_false_bool&&` the `!` is ignored.

```

6334 \cs_new:cpn { __bool_!:Nw } #1#2
6335 {
6336     \exp_after:wN \__bool_get_next:NN
6337     #1 \use_ii:nnnn \use_i:nnnn \use_iii:nnnn \use_iv:nnnn
6338 }

```

(End definition for __bool_!:Nw.)

`__bool_(:Nw` The Open operation starts a sub-expression after discarding the open parenthesis. This is done by calling GetNext (which eventually discards the corresponding closing parenthesis), with a post-processing step which looks for And, Or or Close after the group.

```

6339 \cs_new:cpn { __bool_(:Nw } #1#2
6340 {
6341     \exp_after:wN \__bool_choose:NNN \exp_after:wN #1
6342     \__int_value:w \__bool_get_next:NN \use_i:nnnn
6343 }

```

(End definition for __bool_(:Nw.)

_bool_p:Nw If what follows GetNext is neither ! nor (, evaluate the predicate using the primitive _int_value:w. The canonical true and false values have numerical values 1 and 0 respectively. Look for And, Or or Close afterwards.

```
6344 \cs_new:cpn { \_bool\_p:Nw } #1
6345 { \exp_after:wN \_bool\_choose:NNN \exp_after:wN #1 \_int\_value:w }
```

(End definition for _bool_p:Nw.)

_bool_choose:NNN The arguments are #1: a function such as \use_i:nnnn, #2: 0 or 1 encoding the current truth value, #3: the next operation, And, Or or Close. We distinguish three cases according to a combination of #1 and #2. Case 2 is when #1 is \use_iii:nnnn (state 3), namely after \c_true_bool ||. Case 1 is when #1 is \use_i:nnnn and #2 is true or when #1 is \use_ii:nnnn and #2 is false, for instance for !\c_false_bool. Case 0 includes the same with true/false interchanged and the case where #1 is \use_iv:nnnn namely after \c_false_bool &&.

bool|_0: When seeing) the current subexpression is done, leave the appropriate boolean.
bool|_1: When seeing & in case 0 go into state 4, equivalent to having seen \c_false_bool &&.
bool|_2: In case 1, namely when the argument is true and we are in a normal state continue in the normal state 1. In case 2, namely when skipping alternatives in an Or, continue in the same state. When seeing | in case 0, continue in a normal state; in particular stop skipping for \c_false_bool && because that binds more tightly than ||. In the other two cases start skipping for \c_true_bool ||.

```
6346 \cs_new:Npn \_bool\_choose:NNN #1#2#3
6347 {
6348   \use:c
6349   {
6350     \_bool\_ \token\_to\_str:N #3 _
6351     #1 #2 { \if\_meaning:w 0 #2 1 \else: 0 \fi: } 2 0 :
6352   }
6353 }
6354 \cs_new:cpn { \_bool\_|_0: } { \c\_false\_bool }
6355 \cs_new:cpn { \_bool\_|_1: } { \c\_true\_bool }
6356 \cs_new:cpn { \_bool\_|_2: } { \c\_true\_bool }
6357 \cs_new:cpn { \_bool\_&_0: } & { \_bool\_get\_next:NN \use\_iv:nnnn }
6358 \cs_new:cpn { \_bool\_&_1: } & { \_bool\_get\_next:NN \use\_i:nnnn }
6359 \cs_new:cpn { \_bool\_&_2: } & { \_bool\_get\_next:NN \use\_iii:nnnn }
6360 \cs_new:cpn { \_bool\_|_0: } | { \_bool\_get\_next:NN \use\_i:nnnn }
6361 \cs_new:cpn { \_bool\_|_1: } | { \_bool\_get\_next:NN \use\_iii:nnnn }
6362 \cs_new:cpn { \_bool\_|_2: } | { \_bool\_get\_next:NN \use\_iii:nnnn }
```

(End definition for _bool_choose:NNN and others.)

_bool_lazy_all_p:n Go through the list of expressions, stopping whenever an expression is false. If the end is reached without finding any false expression, then the result is true.

_bool_lazy_all:nTF

_bool_lazy_all:n

```
6363 \prg\_new\_conditional:Npnn \_bool\_lazy\_all:n #1 { p , T , F , TF }
6364 { \_bool\_lazy\_all:n #1 \q\_recursion\_tail \q\_recursion\_stop }
6365 \cs\_new:Npn \_bool\_lazy\_all:n #1
6366 {
6367   \quark\_if\_recursion\_tail\_stop\_do:nn {#1} { \prg\_return\_true: }
6368   \bool\_if:nF {#1}
6369   { \use\_i\_delimit\_by\_q\_recursion\_stop:nw { \prg\_return\_false: } }
6370   \_bool\_lazy\_all:n
6371 }
```

(End definition for \bool_lazy_all:nTF and __bool_lazy_all:n. This function is documented on page 101.)

\bool_lazy_and_p:n Only evaluate the second expression if the first is true.

\bool_lazy_and:nnTF

```

6372 \prg_new_conditional:Npnn \bool_lazy_and:nn #1#2 { p , T , F , TF }
6373 {
6374     \bool_if:nTF {#1}
6375     { \bool_if:nTF {#2} { \prg_return_true: } { \prg_return_false: } }
6376     { \prg_return_false: }
6377 }

```

(End definition for \bool_lazy_and:nnTF. This function is documented on page 101.)

\bool_lazy_any_p:n Go through the list of expressions, stopping whenever an expression is true. If the end is reached without finding any true expression, then the result is false.

\bool_lazy_any:nTF

```

6378 \prg_new_conditional:Npnn \bool_lazy_any:n #1 { p , T , F , TF }
6379 { \__bool_lazy_any:n #1 \q_recursion_tail \q_recursion_stop }
6380 \cs_new:Npn \__bool_lazy_any:n #1
6381 {
6382     \quark_if_recursion_tail_stop_do:nn {#1} { \prg_return_false: }
6383     \bool_if:nT {#1}
6384     { \use_i_delimit_by_q_recursion_stop:nw { \prg_return_true: } }
6385     \__bool_lazy_any:n
6386 }

```

(End definition for \bool_lazy_any:nTF and __bool_lazy_any:n. This function is documented on page 101.)

\bool_lazy_or_p:n Only evaluate the second expression if the first is false.

\bool_lazy_or:nnTF

```

6387 \prg_new_conditional:Npnn \bool_lazy_or:nn #1#2 { p , T , F , TF }
6388 {
6389     \bool_if:nTF {#1}
6390     { \prg_return_true: }
6391     { \bool_if:nTF {#2} { \prg_return_true: } { \prg_return_false: } }
6392 }

```

(End definition for \bool_lazy_or:nnTF. This function is documented on page 101.)

\bool_not_p:n The Not variant just reverses the outcome of \bool_if_p:n. Can be optimized but this is nice and simple and according to the implementation plan. Not even particularly useful to have it when the infix notation is easier to use.

```

6393 \cs_new:Npn \bool_not_p:n #1 { \bool_if_p:n { ! ( #1 ) } }

```

(End definition for \bool_not_p:n. This function is documented on page 101.)

\bool_xor_p:n Exclusive or. If the boolean expressions have same truth value, return false, otherwise return true.

```

6394 \cs_new:Npn \bool_xor_p:n #1#2
6395 {
6396     \int_compare:nNnTF { \bool_if_p:n {#1} } = { \bool_if_p:n {#2} }
6397     \c_false_bool
6398     \c_true_bool
6399 }

```

(End definition for \bool_xor_p:n. This function is documented on page 102.)

12.5 Logical loops

`\bool_while_do:Nn` A while loop where the boolean is tested before executing the statement. The “while” version executes the code as long as the boolean is true; the “until” version executes the code as long as the boolean is false.

```
\bool_while_do:cn
\bool_while_do:Nn
\bool_until_do:Nn
\bool_until_do:cn
6400 \cs_new:Npn \bool_while_do:Nn #1#2
6401   { \bool_if:NT #1 { #2 \bool_while_do:Nn #1 {#2} } }
6402 \cs_new:Npn \bool_until_do:Nn #1#2
6403   { \bool_if:NF #1 { #2 \bool_until_do:Nn #1 {#2} } }
6404 \cs_generate_variant:Nn \bool_while_do:Nn { c }
6405 \cs_generate_variant:Nn \bool_until_do:Nn { c }
```

(End definition for \bool_while_do:Nn and \bool_until_do:Nn. These functions are documented on page 102.)

`\bool_do_while:Nn` A do-while loop where the body is performed at least once and the boolean is tested after executing the body. Otherwise identical to the above functions.

```
\bool_do_while:cn
\bool_do_while:Nn
\bool_do_until:Nn
\bool_do_until:cn
6406 \cs_new:Npn \bool_do_while:Nn #1#2
6407   { #2 \bool_if:NT #1 { \bool_do_while:Nn #1 {#2} } }
6408 \cs_new:Npn \bool_do_until:Nn #1#2
6409   { #2 \bool_if:NF #1 { \bool_do_until:Nn #1 {#2} } }
6410 \cs_generate_variant:Nn \bool_do_while:Nn { c }
6411 \cs_generate_variant:Nn \bool_do_until:Nn { c }
```

(End definition for \bool_do_while:Nn and \bool_do_until:Nn. These functions are documented on page 102.)

`\bool_while_do:nn` Loop functions with the test either before or after the first body expansion.

```
\bool_do_while:nn
\bool_while_do:nn
\bool_until_do:nn
\bool_do_until:nn
6412 \cs_new:Npn \bool_while_do:nn #1#2
6413   {
6414     \bool_if:nT {#1}
6415     {
6416       #2
6417       \bool_while_do:nn {#1} {#2}
6418     }
6419   }
6420 \cs_new:Npn \bool_do_while:nn #1#2
6421   {
6422     #2
6423     \bool_if:nT {#1} { \bool_do_while:nn {#1} {#2} }
6424   }
6425 \cs_new:Npn \bool_until_do:nn #1#2
6426   {
6427     \bool_if:nF {#1}
6428     {
6429       #2
6430       \bool_until_do:nn {#1} {#2}
6431     }
6432   }
6433 \cs_new:Npn \bool_do_until:nn #1#2
6434   {
6435     #2
6436     \bool_if:nF {#1} { \bool_do_until:nn {#1} {#2} }
6437   }
```

(End definition for \bool_while_do:nn and others. These functions are documented on page 103.)

12.6 Producing multiple copies

6438 <@@=prg>

\prg_replicate:nn

This function uses a cascading csname technique by David Kastrup (who else :-)

The idea is to make the input 25 result in first adding five, and then 20 copies of the code to be replicated. The technique uses cascading csnames which means that we start building several csnames so we end up with a list of functions to be called in reverse order. This is important here (and other places) because it means that we can for instance make the function that inserts five copies of something to also hand down ten to the next function in line. This is exactly what happens here: in the example with 25 then the next function is the one that inserts two copies but it sees the ten copies handed down by the previous function. In order to avoid the last function to insert say, 100 copies of the original argument just to gobble them again we define separate functions to be inserted first. These functions also close the expansion of `\exp:w`, which ensures that `\prg_replicate:nn` only requires two steps of expansion.

This function has one flaw though: Since it constantly passes down ten copies of its previous argument it severely affects the main memory once you start demanding hundreds of thousands of copies. Now I don't think this is a real limitation for any ordinary use, and if necessary, it is possible to write `\prg_replicate:nn {1000} { \prg_replicate:nn {1000} {<code>} }`. An alternative approach is to create a string of m's with `\exp:w` which can be done with just four macros but that method has its own problems since it can exhaust the string pool. Also, it is considerably slower than what we use here so the few extra csnames are well spent I would say.

```
6439 \cs_new:Npn \prg_replicate:nn #1
6440 {
6441   \exp:w
6442     \exp_after:wN \__prg_replicate_first:N
6443     \__int_value:w \__int_eval:n {#1}
6444   \cs_end:
6445 }
6446 \cs_new:Npn \__prg_replicate:N #1
6447 { \cs:w \__prg_replicate_#1 :n \__prg_replicate:N }
6448 \cs_new:Npn \__prg_replicate_first:N #1
6449 { \cs:w \__prg_replicate_first_#1 :n \__prg_replicate:N }
```

Then comes all the functions that do the hard work of inserting all the copies. The first function takes `:n` as a parameter.

```
6450 \cs_new:Npn \__prg_replicate_ :n #1 { \cs_end: }
6451 \cs_new:cpn { \__prg_replicate_0:n } #1
6452 { \cs_end: {#1#1#1#1#1#1#1#1#1#1} }
6453 \cs_new:cpn { \__prg_replicate_1:n } #1
6454 { \cs_end: {#1#1#1#1#1#1#1#1#1#1} #1 }
6455 \cs_new:cpn { \__prg_replicate_2:n } #1
6456 { \cs_end: {#1#1#1#1#1#1#1#1#1#1} #1#1 }
6457 \cs_new:cpn { \__prg_replicate_3:n } #1
6458 { \cs_end: {#1#1#1#1#1#1#1#1#1#1} #1#1#1 }
6459 \cs_new:cpn { \__prg_replicate_4:n } #1
6460 { \cs_end: {#1#1#1#1#1#1#1#1#1#1} #1#1#1#1 }
6461 \cs_new:cpn { \__prg_replicate_5:n } #1
6462 { \cs_end: {#1#1#1#1#1#1#1#1#1#1} #1#1#1#1#1 }
6463 \cs_new:cpn { \__prg_replicate_6:n } #1
6464 { \cs_end: {#1#1#1#1#1#1#1#1#1#1} #1#1#1#1#1#1 }
```

Users shouldn't ask for something to be replicated once or even not at all but...

(End definition for \prg_replicate:nn and others. This function is documented on page 103.)

12.8 Internal programming functions

`\group_align_safe_begin:` \TeX 's alignment structures present many problems. As Knuth says himself in *\TeX : The Program*: “It’s sort of a miracle whenever `\halign` or `\valign` work, [...]” One problem relates to commands that internally issues a `\cr` but also peek ahead for the next character for use in, say, an optional argument. If the next token happens to be a `&` with category code 4 we get some sort of weird error message because the underlying `\futurelet` stores the token at the end of the alignment template. This could be a `&_4` giving a message like `! Misplaced \cr.` or even worse: it could be the `\endtemplate` token causing even more trouble! To solve this we have to open a special group so that \TeX still thinks it’s on safe ground but at the same time we don’t want to introduce any brace group that may find its way to the output. The following functions help with this by using code documented only in Appendix D of *The \TeX book*... We place the `\if_false: { \fi:` part at that place so that the successive expansions of `\group_align_safe_begin/end:` are always brace balanced.

```
6494 \cs_new:Npn \group_align_safe_begin:
6495   { \if_int_compare:w \if_false: { \fi: ‘} = \c_zero \fi: }
6496 \cs_new:Npn \group_align_safe_end:
6497   { \if_int_compare:w ‘{ = \c_zero } \fi: }
```

(End definition for `\group_align_safe_begin:` and `\group_align_safe_end:`. These functions are documented on page 104.)

```
6498 <@@=prg>
```

`\g__prg_map_int` A nesting counter for mapping.

```
6499 \int_new:N \g__prg_map_int
```

(End definition for `\g__prg_map_int`.)

`__prg_break_point:Nn` These are defined in `l3basics`, as they are needed “early”. This is just a reminder that is the case!

`__prg_map_break:Nn`

(End definition for `__prg_break_point:Nn` and `__prg_map_break:Nn`.)

`__prg_break_point:` Also done in `l3basics` as in format mode these are needed within `l3alloc`.

`__prg_break:`

`__prg_break:n`

(End definition for `__prg_break_point:`, `__prg_break:`, and `__prg_break:n`.)

```
6500 </initex | package>
```

13 l3clist implementation

The following test files are used for this code: `m3clist002`.

```
6501 <*initex | package>
```

```
6502 <@@=clist>
```

`\c_empty_clist` An empty comma list is simply an empty token list.

```
6503 \cs_new_eq:NN \c_empty_clist \c_empty_tl
```

(End definition for `\c_empty_clist`. This variable is documented on page 113.)

`\l__clist_internal_clist` Scratch space for various internal uses. This comma list variable cannot be declared as such because it comes before `\clist_new:N`

```
6504 \tl_new:N \l__clist_internal_clist
```

(End definition for `\l__clist_internal_clist`.)

`__clist_tmp:w` A temporary function for various purposes.

```
6505 \cs_new_protected:Npn \__clist_tmp:w { }
```

(End definition for `__clist_tmp:w`.)

13.1 Allocation and initialisation

`\clist_new:N` Internally, comma lists are just token lists.

```
\clist_new:c
6506 \cs_new_eq:NN \clist_new:N \tl_new:N
6507 \cs_new_eq:NN \clist_new:c \tl_new:c
```

(End definition for `\clist_new:N`. This function is documented on page 105.)

`\clist_const:Nn` Creating and initializing a constant comma list is done in a way similar to `\clist_set:Nn` and `\clist_gset:Nn`, being careful to strip spaces.

```
\clist_const:cn
\clist_const:Nx
\clist_const:cx
6508 \cs_new_protected:Npn \clist_const:Nn #1#2
6509 { \tl_const:Nx #1 { \__clist_trim_spaces:n {#2} } }
6510 \cs_generate_variant:Nn \clist_const:Nn { c , Nx , cx }
```

(End definition for `\clist_const:Nn`. This function is documented on page 105.)

`\clist_clear:N` Clearing comma lists is just the same as clearing token lists.

```
\clist_clear:c
6511 \cs_new_eq:NN \clist_clear:N \tl_clear:N
\clist_gclear:N
6512 \cs_new_eq:NN \clist_clear:c \tl_clear:c
\clist_gclear:c
6513 \cs_new_eq:NN \clist_gclear:N \tl_gclear:N
6514 \cs_new_eq:NN \clist_gclear:c \tl_gclear:c
```

(End definition for `\clist_clear:N` and `\clist_gclear:N`. These functions are documented on page 105.)

`\clist_clear_new:N` Once again a copy from the token list functions.

```
\clist_clear_new:c
6515 \cs_new_eq:NN \clist_clear_new:N \tl_clear_new:N
\clist_gclear_new:N
6516 \cs_new_eq:NN \clist_clear_new:c \tl_clear_new:c
\clist_gclear_new:c
6517 \cs_new_eq:NN \clist_gclear_new:N \tl_gclear_new:N
6518 \cs_new_eq:NN \clist_gclear_new:c \tl_gclear_new:c
```

(End definition for `\clist_clear_new:N` and `\clist_gclear_new:N`. These functions are documented on page 105.)

`\clist_set_eq:NN` Once again, these are simple copies from the token list functions.

```
\clist_set_eq:cN
6519 \cs_new_eq:NN \clist_set_eq:NN \tl_set_eq:NN
\clist_set_eq:Nc
6520 \cs_new_eq:NN \clist_set_eq:Nc \tl_set_eq:Nc
\clist_set_eq:cc
6521 \cs_new_eq:NN \clist_set_eq:cN \tl_set_eq:cN
\clist_gset_eq:NN
6522 \cs_new_eq:NN \clist_set_eq:cc \tl_set_eq:cc
\clist_gset_eq:cN
6523 \cs_new_eq:NN \clist_gset_eq:NN \tl_gset_eq:NN
\clist_gset_eq:Nc
6524 \cs_new_eq:NN \clist_gset_eq:Nc \tl_gset_eq:Nc
\clist_gset_eq:cN
6525 \cs_new_eq:NN \clist_gset_eq:cN \tl_gset_eq:cN
\clist_gset_eq:cc
6526 \cs_new_eq:NN \clist_gset_eq:cc \tl_gset_eq:cc
```

(End definition for `\clist_set_eq:NN` and `\clist_gset_eq:NN`. These functions are documented on page 106.)

`\clist_set_from_seq:NN` Setting a comma list from a comma-separated list is done using a simple mapping. We wrap most items with `\exp_not:n`, and a comma. Items which contain a comma or a space are surrounded by an extra set of braces. The first comma must be removed, except in the case of an empty comma-list.

`\clist_set_from_seq:cN`

`\clist_set_from_seq:Nc`

`\clist_set_from_seq:cc`

`\clist_gset_from_seq:NN`

`\clist_gset_from_seq:cN`

`\clist_gset_from_seq:Nc`

`\clist_gset_from_seq:cc`

`__clist_set_from_seq:NNNN`

`__clist_wrap_item:n`

`__clist_set_from_seq:w`

```

6527 \cs_new_protected:Npn \clist_set_from_seq:NN
6528 { \__clist_set_from_seq:NNNN \clist_clear:N \tl_set:Nx }
6529 \cs_new_protected:Npn \clist_gset_from_seq:NN
6530 { \__clist_set_from_seq:NNNN \clist_gclear:N \tl_gset:Nx }
6531 \cs_new_protected:Npn \__clist_set_from_seq:NNNN #1#2#3#4
6532 {
6533   \seq_if_empty:NTF #4
6534   { #1 #3 }
6535   {
6536     #2 #3
6537     {
6538       \exp_last_unbraced:Nf \use_none:n
6539       { \seq_map_function:NN #4 \__clist_wrap_item:n }
6540     }
6541   }
6542 }
6543 \cs_new:Npn \__clist_wrap_item:n #1
6544 {
6545   ,
6546   \tl_if_empty:oTF { \__clist_set_from_seq:w #1 ~ , #1 ~ }
6547   { \exp_not:n {#1} }
6548   { \exp_not:n { {#1} } }
6549 }
6550 \cs_new:Npn \__clist_set_from_seq:w #1 , #2 ~ { }
6551 \cs_generate_variant:Nn \clist_set_from_seq:NN { c Nc }
6552 \cs_generate_variant:Nn \clist_set_from_seq:NN { c , cc }
6553 \cs_generate_variant:Nn \clist_gset_from_seq:NN { c Nc }
6554 \cs_generate_variant:Nn \clist_gset_from_seq:NN { c , cc }

```

(End definition for `\clist_set_from_seq:NN` and others. These functions are documented on page 106.)

`\clist_concat:NNN` Concatenating comma lists is not quite as easy as it seems, as there needs to be the correct addition of a comma to the output. So a little work to do.

`\clist_concat:ccc`

`\clist_gconcat:NNN`

`\clist_gconcat:ccc`

`__clist_concat:NNNN`

```

6555 \cs_new_protected:Npn \clist_concat:NNN
6556 { \__clist_concat:NNNN \tl_set:Nx }
6557 \cs_new_protected:Npn \clist_gconcat:NNN
6558 { \__clist_concat:NNNN \tl_gset:Nx }
6559 \cs_new_protected:Npn \__clist_concat:NNNN #1#2#3#4
6560 {
6561   #1 #2
6562   {
6563     \exp_not:o #3
6564     \clist_if_empty:NF #3 { \clist_if_empty:NF #4 { , } }
6565     \exp_not:o #4
6566   }
6567 }
6568 \cs_generate_variant:Nn \clist_concat:NNN { ccc }

```

```
6569 \cs_generate_variant:Nn \clist_gconcat:NNN { ccc }
```

(End definition for `\clist_concat:NNN`, `\clist_gconcat:NNN`, and `__clist_concat:NNNN`. These functions are documented on page 106.)

`\clist_if_exist_p:N` Copies of the `cs` functions defined in `l3basics`.

```
\clist_if_exist_p:c      6570 \prg_new_eq_conditional:NNn \clist_if_exist:N \cs_if_exist:N
\clist_if_exist:NTF      6571 { TF , T , F , p }
\clist_if_exist:cTF      6572 \prg_new_eq_conditional:NNn \clist_if_exist:c \cs_if_exist:c
                        6573 { TF , T , F , p }
```

(End definition for `\clist_if_exist:NTF`. This function is documented on page 106.)

13.2 Removing spaces around items

```
\__clist_trim_spaces_generic:nw \__clist_trim_spaces_generic:nw {<code>} \q_mark <item> ,
```

`__clist_trim_spaces_generic:nw` This expands to the `<code>`, followed by a brace group containing the `<item>`, with leading and trailing spaces removed. The calling function is responsible for inserting `\q_mark` in front of the `<item>`, as well as testing for the end of the list. We reuse a `l3tl` internal function, whose first argument must start with `\q_mark`. That trims the item `#2`, then feeds the result (after having to do an `o`-type expansion) to `__clist_trim_spaces_generic:nn` which places the `<code>` in front of the `<trimmed item>`.

```
6574 \cs_new:Npn \__clist_trim_spaces_generic:nw #1#2 ,
6575 {
6576   \__tl_trim_spaces:nn {#2}
6577   { \exp_args:No \__clist_trim_spaces_generic:nn } {#1}
6578 }
6579 \cs_new:Npn \__clist_trim_spaces_generic:nn #1#2 { #2 {#1} }
```

(End definition for `__clist_trim_spaces_generic:nw` and `__clist_trim_spaces_generic:nn`.)

`__clist_trim_spaces:n` The first argument of `__clist_trim_spaces:nn` is initially empty, and later a comma, namely, as soon as we have added an item to the resulting list. The auxiliary tests for the end of the list, and also prevents empty arguments from finding their way into the output.

```
6580 \cs_new:Npn \__clist_trim_spaces:n #1
6581 {
6582   \__clist_trim_spaces_generic:nw
6583   { \__clist_trim_spaces:nn { } }
6584   \q_mark #1 ,
6585   \q_recursion_tail, \q_recursion_stop
6586 }
6587 \cs_new:Npn \__clist_trim_spaces:nn #1 #2
6588 {
6589   \quark_if_recursion_tail_stop:n {#2}
6590   \tl_if_empty:nTF {#2}
6591   {
6592     \__clist_trim_spaces_generic:nw
6593     { \__clist_trim_spaces:nn {#1} } \q_mark
6594   }
6595   {
6596     #1 \exp_not:n {#2}
6597     \__clist_trim_spaces_generic:nw
6598     { \__clist_trim_spaces:nn { , } } \q_mark
```

```

6599     }
6600 }

```

(End definition for `_clist_trim_spaces:n` and `_clist_trim_spaces:nn`.)

13.3 Adding data to comma lists

```

\clist_set:Nn
\clist_set:NV 6601 \cs_new_protected:Npn \clist_set:Nn #1#2
\clist_set:No 6602 { \tl_set:Nx #1 { \_clist_trim_spaces:n {#2} } }
\clist_set:Nx 6603 \cs_new_protected:Npn \clist_gset:Nn #1#2
\clist_set:cn 6604 { \tl_gset:Nx #1 { \_clist_trim_spaces:n {#2} } }
\clist_set:cV 6605 \cs_generate_variant:Nn \clist_set:Nn { NV , No , Nx , c , cV , co , cx }
\clist_set:co 6606 \cs_generate_variant:Nn \clist_gset:Nn { NV , No , Nx , c , cV , co , cx }
\clist_set:cx

```

(End definition for `\clist_set:Nn` and `\clist_gset:Nn`. These functions are documented on page 106.)

`\clist_gset:Nn`

`\clist_gset:NV`

`\clist_put_left:Nn`

`\clist_put_left:Nx`

`\clist_put_left:cn`

`\clist_put_left:cV`

`\clist_put_left:co`

`\clist_put_left:cx`

`\clist_gput_left:Nn`

`\clist_gput_left:Nx`

`\clist_gput_left:cn`

`\clist_gput_left:cV`

`\clist_gput_left:co`

`\clist_gput_left:cx`

`_clist_put_left:NNNn`

`\clist_put_right:Nn`

`\clist_put_right:Nx`

`\clist_put_right:cn`

`\clist_put_right:cV`

`\clist_put_right:co`

`\clist_put_right:cx`

`\clist_gput_right:Nn`

`\clist_gput_right:Nx`

`\clist_gput_right:cn`

`\clist_gput_right:cV`

`\clist_gput_right:co`

`\clist_gput_right:cx`

`_clist_put_right:NNNn`

`\clist_put_right:Nn`

`\clist_put_right:Nx`

`\clist_put_right:cn`

`\clist_put_right:cV`

`\clist_put_right:co`

`\clist_put_right:cx`

`\clist_gput_right:Nn`

`\clist_gput_right:Nx`

`\clist_gput_right:cn`

`\clist_gput_right:cV`

`\clist_gput_right:co`

`\clist_gput_right:cx`

`_clist_put_right:NNNn`

Comma lists cannot hold empty values: there are therefore a couple of sanity checks to avoid accumulating commas.

```

6607 \cs_new_protected:Npn \clist_put_left:Nn
6608 { \_clist_put_left:NNNn \clist_concat:NNN \clist_set:Nn }
6609 \cs_new_protected:Npn \clist_gput_left:Nn
6610 { \_clist_put_left:NNNn \clist_gconcat:NNN \clist_set:Nn }
6611 \cs_new_protected:Npn \_clist_put_left:NNNn #1#2#3#4
6612 {
6613   #2 \l__clist_internal_clist {#4}
6614   #1 #3 \l__clist_internal_clist #3
6615 }
6616 \cs_generate_variant:Nn \clist_put_left:Nn { NV , No , Nx }
6617 \cs_generate_variant:Nn \clist_put_left:Nn { c , cV , co , cx }
6618 \cs_generate_variant:Nn \clist_gput_left:Nn { NV , No , Nx }
6619 \cs_generate_variant:Nn \clist_gput_left:Nn { c , cV , co , cx }

```

(End definition for `\clist_put_left:Nn`, `\clist_gput_left:Nn`, and `_clist_put_left:NNNn`. These functions are documented on page 106.)

`_clist_put_left:NNNn`

`\clist_put_right:Nn`

`\clist_put_right:Nx`

`\clist_put_right:cn`

`\clist_put_right:cV`

`\clist_put_right:co`

`\clist_put_right:cx`

`\clist_gput_right:Nn`

`\clist_gput_right:Nx`

`\clist_gput_right:cn`

`\clist_gput_right:cV`

`\clist_gput_right:co`

`\clist_gput_right:cx`

`_clist_put_right:NNNn`

`\clist_put_right:Nn`

`\clist_put_right:Nx`

`\clist_put_right:cn`

`\clist_put_right:cV`

`\clist_put_right:co`

`\clist_put_right:cx`

`\clist_gput_right:Nn`

`\clist_gput_right:Nx`

`\clist_gput_right:cn`

`\clist_gput_right:cV`

`\clist_gput_right:co`

`\clist_gput_right:cx`

`_clist_put_right:NNNn`

(End definition for `\clist_put_right:Nn`, `\clist_gput_right:Nn`, and `_clist_put_right:NNNn`. These functions are documented on page 107.)

13.4 Comma lists as stacks

\clist_get:NN Getting an item from the left of a comma list is pretty easy: just trim off the first item using the comma.

```
\clist_get:cN
__clist_get:wN
6633 \cs_new_protected:Npn \clist_get:NN #1#2
6634 {
6635     \if_meaning:w #1 \c_empty_clist
6636     \tl_set:Nn #2 { \q_no_value }
6637     \else:
6638     \exp_after:wN __clist_get:wN #1 , \q_stop #2
6639     \fi:
6640 }
6641 \cs_new_protected:Npn __clist_get:wN #1 , #2 \q_stop #3
6642 { \tl_set:Nn #3 {#1} }
6643 \cs_generate_variant:Nn \clist_get:NN { c }
```

(End definition for \clist_get:NN and __clist_get:wN. This function is documented on page 111.)

\clist_pop:NN An empty clist leads to \q_no_value, otherwise grab until the first comma and assign to the variable. The second argument of __clist_pop:wwNNN is a comma list ending in a comma and \q_mark, unless the original clist contained exactly one item: then the argument is just \q_mark. The next auxiliary picks either \exp_not:n or \use_none:n as #2, ensuring that the result can safely be an empty comma list.

```
\clist_pop:cN
\clist_gpop:NN
\clist_gpop:cN
__clist_pop:NNN
__clist_pop:wwNNN
__clist_pop:wN
6644 \cs_new_protected:Npn \clist_pop:NN
6645 { __clist_pop:NNN \tl_set:Nx }
6646 \cs_new_protected:Npn \clist_gpop:NN
6647 { __clist_pop:NNN \tl_gset:Nx }
6648 \cs_new_protected:Npn __clist_pop:NNN #1#2#3
6649 {
6650     \if_meaning:w #2 \c_empty_clist
6651     \tl_set:Nn #3 { \q_no_value }
6652     \else:
6653     \exp_after:wN __clist_pop:wwNNN #2 , \q_mark \q_stop #1#2#3
6654     \fi:
6655 }
6656 \cs_new_protected:Npn __clist_pop:wwNNN #1 , #2 \q_stop #3#4#5
6657 {
6658     \tl_set:Nn #5 {#1}
6659     #3 #4
6660     {
6661         __clist_pop:wN \prg_do_nothing:
6662         #2 \exp_not:o
6663         , \q_mark \use_none:n
6664         \q_stop
6665     }
6666 }
6667 \cs_new:Npn __clist_pop:wN #1 , \q_mark #2 #3 \q_stop { #2 {#1} }
6668 \cs_generate_variant:Nn \clist_pop:NN { c }
6669 \cs_generate_variant:Nn \clist_gpop:NN { c }
```

(End definition for \clist_pop:NN and others. These functions are documented on page 111.)

\clist_get:NTF The same, as branching code: very similar to the above.

```
\clist_get:cNTF
6670 \prg_new_protected_conditional:Npnn \clist_get:NN #1#2 { T , F , TF }
```

\clist_pop:NTF

\clist_pop:cNTF

\clist_gpop:NTF

\clist_gpop:cNTF

__clist_pop_TF:NNN


```

6671 {
6672   \if_meaning:w #1 \c_empty_clist
6673   \prg_return_false:
6674   \else:
6675     \exp_after:wN \__clist_get:wN #1 , \q_stop #2
6676     \prg_return_true:
6677   \fi:
6678 }
6679 \cs_generate_variant:Nn \clist_get:NNT { c }
6680 \cs_generate_variant:Nn \clist_get:NNF { c }
6681 \cs_generate_variant:Nn \clist_get:NNTF { c }
6682 \prg_new_protected_conditional:Npnn \clist_pop:NN #1#2 { T , F , TF }
6683 { \__clist_pop_TF:NNN \tl_set:Nx #1 #2 }
6684 \prg_new_protected_conditional:Npnn \clist_gpop:NN #1#2 { T , F , TF }
6685 { \__clist_pop_TF:NNN \tl_gset:Nx #1 #2 }
6686 \cs_new_protected:Npn \__clist_pop_TF:NNN #1#2#3
6687 {
6688   \if_meaning:w #2 \c_empty_clist
6689   \prg_return_false:
6690   \else:
6691     \exp_after:wN \__clist_pop:wwNNN #2 , \q_mark \q_stop #1#2#3
6692     \prg_return_true:
6693   \fi:
6694 }
6695 \cs_generate_variant:Nn \clist_pop:NNT { c }
6696 \cs_generate_variant:Nn \clist_pop:NNF { c }
6697 \cs_generate_variant:Nn \clist_pop:NNTF { c }
6698 \cs_generate_variant:Nn \clist_gpop:NNT { c }
6699 \cs_generate_variant:Nn \clist_gpop:NNF { c }
6700 \cs_generate_variant:Nn \clist_gpop:NNTF { c }

```

(End definition for `\clist_get:NNTF` and others. These functions are documented on page 111.)

\clist_push:Nn Pushing to a comma list is the same as adding on the left.

\clist_push:NV	6701 \cs_new_eq:NN \clist_push:Nn \clist_put_left:Nn
\clist_push:No	6702 \cs_new_eq:NN \clist_push:NV \clist_put_left:NV
\clist_push:Nx	6703 \cs_new_eq:NN \clist_push:No \clist_put_left:No
\clist_push:cn	6704 \cs_new_eq:NN \clist_push:Nx \clist_put_left:Nx
\clist_push:cV	6705 \cs_new_eq:NN \clist_push:cn \clist_put_left:cn
\clist_push:cO	6706 \cs_new_eq:NN \clist_push:cV \clist_put_left:cV
\clist_push:cX	6707 \cs_new_eq:NN \clist_push:cO \clist_put_left:cO
\clist_gpush:Nn	6708 \cs_new_eq:NN \clist_push:cX \clist_put_left:cX
\clist_gpush:NV	6709 \cs_new_eq:NN \clist_gpush:Nn \clist_gput_left:Nn
\clist_gpush:No	6710 \cs_new_eq:NN \clist_gpush:NV \clist_gput_left:NV
\clist_gpush:Nx	6711 \cs_new_eq:NN \clist_gpush:No \clist_gput_left:No
\clist_gpush:cn	6712 \cs_new_eq:NN \clist_gpush:Nx \clist_gput_left:Nx
\clist_gpush:cV	6713 \cs_new_eq:NN \clist_gpush:cn \clist_gput_left:cn
\clist_gpush:cO	6714 \cs_new_eq:NN \clist_gpush:cV \clist_gput_left:cV
\clist_gpush:cX	6715 \cs_new_eq:NN \clist_gpush:cO \clist_gput_left:cO
	6716 \cs_new_eq:NN \clist_gpush:cX \clist_gput_left:cX

(End definition for `\clist_push:Nn` and `\clist_gpush:Nn`. These functions are documented on page 112.)

13.5 Modifying comma lists

`\l_clist_internal_remove_clist` An internal comma list for the removal routines.

```
6717 \clist_new:N \l__clist_internal_remove_clist
```

(End definition for `\l__clist_internal_remove_clist`.)

`\clist_remove_duplicates:N` Removing duplicates means making a new list then copying it.

```
\clist_remove_duplicates:c
\clist_gremove_duplicates:N
\clist_gremove_duplicates:c
  \__clist_remove_duplicates:NN
6718 \cs_new_protected:Npn \clist_remove_duplicates:N
6719 { \__clist_remove_duplicates:NN \clist_set_eq:NN }
6720 \cs_new_protected:Npn \clist_gremove_duplicates:N
6721 { \__clist_remove_duplicates:NN \clist_gset_eq:NN }
6722 \cs_new_protected:Npn \__clist_remove_duplicates:NN #1#2
6723 {
6724   \clist_clear:N \l__clist_internal_remove_clist
6725   \clist_map_inline:Nn #2
6726   {
6727     \clist_if_in:NnF \l__clist_internal_remove_clist {##1}
6728     { \clist_put_right:Nn \l__clist_internal_remove_clist {##1} }
6729   }
6730   #1 #2 \l__clist_internal_remove_clist
6731 }
6732 \cs_generate_variant:Nn \clist_remove_duplicates:N { c }
6733 \cs_generate_variant:Nn \clist_gremove_duplicates:N { c }
```

(End definition for `\clist_remove_duplicates:N`, `\clist_gremove_duplicates:N`, and `__clist_remove_duplicates:NN`. These functions are documented on page 107.)

`\clist_remove_all:Nn` The method used here is very similar to `\tl_replace_all:Nnn`. Build a function delimited by the `<item>` that should be removed, surrounded with commas, and call that function followed by the expanded comma list, and another copy of the `<item>`. The loop is controlled by the argument grabbed by `__clist_remove_all:w`: when the item was found, the `\q_mark` delimiter used is the one inserted by `__clist_tmp:w`, and `\use_none_delimit_by_q_stop:w` is deleted. At the end, the final `<item>` is grabbed, and the argument of `__clist_tmp:w` contains `\q_mark`: in that case, `__clist_remove_all:w` removes the second `\q_mark` (inserted by `__clist_tmp:w`), and lets `\use_none_delimit_by_q_stop:w` act.

No brace is lost because items are always grabbed with a leading comma. The result of the first assignment has an extra leading comma, which we remove in a second assignment. Two exceptions: if the clist lost all of its elements, the result is empty, and we shouldn't remove anything; if the clist started up empty, the first step happens to turn it into a single comma, and the second step removes it.

```
6734 \cs_new_protected:Npn \clist_remove_all:Nn
6735 { \__clist_remove_all:NNn \tl_set:Nx }
6736 \cs_new_protected:Npn \clist_gremove_all:Nn
6737 { \__clist_remove_all:NNn \tl_gset:Nx }
6738 \cs_new_protected:Npn \__clist_remove_all:NNn #1#2#3
6739 {
6740   \cs_set:Npn \__clist_tmp:w ##1 , #3 ,
6741   {
6742     ##1
6743     , \q_mark , \use_none_delimit_by_q_stop:w ,
6744     \__clist_remove_all:
```

```

6745     }
6746     #1 #2
6747     {
6748         \exp_after:wN \__clist_remove_all:
6749         #2 , \q_mark , #3 , \q_stop
6750     }
6751     \clist_if_empty:NF #2
6752     {
6753         #1 #2
6754         {
6755             \exp_args:No \exp_not:o
6756             { \exp_after:wN \use_none:n #2 }
6757         }
6758     }
6759 }
6760 \cs_new:Npn \__clist_remove_all:
6761 { \exp_after:wN \__clist_remove_all:w \__clist_tmp:w , }
6762 \cs_new:Npn \__clist_remove_all:w #1 , \q_mark , #2 , { \exp_not:n {#1} }
6763 \cs_generate_variant:Nn \clist_remove_all:Nn { c }
6764 \cs_generate_variant:Nn \clist_gremove_all:Nn { c }

```

(End definition for `\clist_remove_all:Nn` and others. These functions are documented on page 107.)

`\clist_reverse:N` Use `\clist_reverse:n` in an x-expanding assignment. The extra work that `\clist_reverse:n` does to preserve braces and spaces would not be needed for the well-controlled case of N-type comma lists, but the slow-down is not too bad.

`\clist_reverse:c`
`\clist_greverse:N`
`\clist_greverse:c`

```

6765 \cs_new_protected:Npn \clist_reverse:N #1
6766 { \tl_set:Nx #1 { \exp_args:No \clist_reverse:n {#1} } }
6767 \cs_new_protected:Npn \clist_greverse:N #1
6768 { \tl_gset:Nx #1 { \exp_args:No \clist_reverse:n {#1} } }
6769 \cs_generate_variant:Nn \clist_reverse:N { c }
6770 \cs_generate_variant:Nn \clist_greverse:N { c }

```

(End definition for `\clist_reverse:N` and `\clist_greverse:N`. These functions are documented on page 107.)

`\clist_reverse:n` The reversed token list is built one item at a time, and stored between `\q_stop` and `\q_mark`, in the form of ? followed by zero or more instances of “ $\langle item \rangle$,”. We start from a comma list “ $\langle item_1 \rangle, \dots, \langle item_n \rangle$ ”. During the loop, the auxiliary `__clist_reverse:wwNww` receives “ $\langle item_i \rangle$ ” as #1, “ $\langle item_{i+1} \rangle, \dots, \langle item_n \rangle$ ” as #2, `__clist_reverse:wwNww` as #3, what remains until `\q_stop` as #4, and “ $\langle item_{i-1} \rangle, \dots, \langle item_1 \rangle$,” as #5. The auxiliary moves #1 just before #5, with a comma, and calls itself (#3). After the last item is moved, `__clist_reverse:wwNww` receives “`\q_mark __clist_reverse:wwNww !`” as its argument #1, thus `__clist_reverse_end:ww` as its argument #3. This second auxiliary cleans up until the marker !, removes the trailing comma (introduced when the first item was moved after `\q_stop`), and leaves its argument #1 within `\exp_not:n`. There is also a need to remove a leading comma, hence `\exp_not:o` and `\use_none:n`.

`__clist_reverse:wwNww`
`__clist_reverse_end:ww`

```

6771 \cs_new:Npn \clist_reverse:n #1
6772 {
6773     \__clist_reverse:wwNww ? #1 ,
6774     \q_mark \__clist_reverse:wwNww ! ,
6775     \q_mark \__clist_reverse_end:ww

```

```

6776     \q_stop ? \q_mark
6777 }
6778 \cs_new:Npn \__clist_reverse:wwNww
6779     #1 , #2 \q_mark #3 #4 \q_stop ? #5 \q_mark
6780 { #3 ? #2 \q_mark #3 #4 \q_stop #1 , #5 \q_mark }
6781 \cs_new:Npn \__clist_reverse_end:ww #1 ! #2 , \q_mark
6782 { \exp_not:o { \use_none:n #2 } }

```

(End definition for `\clist_reverse:n`, `__clist_reverse:wwNww`, and `__clist_reverse_end:ww`. This function is documented on page 107.)

`\clist_sort:Nn` Implemented in `l3sort`.
`\clist_sort:cn`
`\clist_gsort:Nn` (End definition for `\clist_sort:Nn` and `\clist_gsort:Nn`. These functions are documented on page 108.)
`\clist_gsort:cn`

13.6 Comma list conditionals

`\clist_if_empty_p:N` Simple copies from the token list variable material.
`\clist_if_empty_p:c` 6783 \prg_new_eq_conditional:Nnn \clist_if_empty:N \tl_if_empty:N
`\clist_if_empty:NTF` 6784 { p , T , F , TF }
`\clist_if_empty:cTF` 6785 \prg_new_eq_conditional:Nnn \clist_if_empty:c \tl_if_empty:c
6786 { p , T , F , TF }

(End definition for `\clist_if_empty:NTF`. This function is documented on page 108.)

`\clist_if_empty_p:n` As usual, we insert a token (here ?) before grabbing any argument: this avoids losing
`\clist_if_empty:nTF` braces. The argument of `\tl_if_empty:oTF` is empty if #1 is ? followed by blank spaces
`__clist_if_empty_n:w` (besides, this particular variant of the emptiness test is optimized). If the item of the
`__clist_if_empty_n:wNw` comma list is blank, grab the next one. As soon as one item is non-blank, exit: the second
auxiliary grabs `\prg_return_false:` as #2, unless every item in the comma list was blank
and the loop actually got broken by the trailing `\q_mark \prg_return_false:` item.

```

6787 \prg_new_conditional:Npnn \clist_if_empty:n #1 { p , T , F , TF }
6788 {
6789     \__clist_if_empty_n:w ? #1
6790     , \q_mark \prg_return_false:
6791     , \q_mark \prg_return_true:
6792     \q_stop
6793 }
6794 \cs_new:Npn \__clist_if_empty_n:w #1 ,
6795 {
6796     \tl_if_empty:oTF { \use_none:nn #1 ? }
6797     { \__clist_if_empty_n:w ? }
6798     { \__clist_if_empty_n:wNw }
6799 }
6800 \cs_new:Npn \__clist_if_empty_n:wNw #1 \q_mark #2#3 \q_stop {#2}

```

(End definition for `\clist_if_empty:nTF`, `__clist_if_empty_n:w`, and `__clist_if_empty_n:wNw`. This function is documented on page 108.)

`\clist_if_in:NnTF` See description of the `\tl_if_in:Nn` function for details. We simply surround the comma
`\clist_if_in:NVTf` list, and the item, with commas.
`\clist_if_in:NoTF` 6801 \prg_new_protected_conditional:Npnn \clist_if_in:Nn #1#2 { T , F , TF }
`\clist_if_in:cnTF` 6802 {
`\clist_if_in:cVTF` 6803 \exp_args:No __clist_if_in_return:nn #1 {#2}
`\clist_if_in:coTF`
`\clist_if_in:nnTF`
`\clist_if_in:nVTf`
`\clist_if_in:noTF`
`__clist_if_in_return:nn`

```

6804 }
6805 \prg_new_protected_conditional:Npnn \clist_if_in:nn #1#2 { T , F , TF }
6806 {
6807   \clist_set:Nn \l__clist_internal_clist {#1}
6808   \exp_args:No \__clist_if_in_return:nn \l__clist_internal_clist {#2}
6809 }
6810 \cs_new_protected:Npn \__clist_if_in_return:nn #1#2
6811 {
6812   \cs_set:Npn \__clist_tmp:w ##1 ,#2, { }
6813   \tl_if_empty:oTF
6814     { \__clist_tmp:w ,#1, {} {} ,#2, }
6815     { \prg_return_false: } { \prg_return_true: }
6816 }
6817 \cs_generate_variant:Nn \clist_if_in:NnT { NV , No }
6818 \cs_generate_variant:Nn \clist_if_in:NnT { c , cV , co }
6819 \cs_generate_variant:Nn \clist_if_in:NnF { NV , No }
6820 \cs_generate_variant:Nn \clist_if_in:NnF { c , cV , co }
6821 \cs_generate_variant:Nn \clist_if_in:NnTF { NV , No }
6822 \cs_generate_variant:Nn \clist_if_in:NnTF { c , cV , co }
6823 \cs_generate_variant:Nn \clist_if_in:nnT { nV , no }
6824 \cs_generate_variant:Nn \clist_if_in:nnF { nV , no }
6825 \cs_generate_variant:Nn \clist_if_in:nnTF { nV , no }

```

(End definition for `\clist_if_in:NnTF`, `\clist_if_in:nnTF`, and `__clist_if_in_return:nn`. These functions are documented on page 108.)

13.7 Mapping to comma lists

```

\clist_map_function:NN
\clist_map_function:cN
\__clist_map_function:Nw

```

If the variable is empty, the mapping is skipped (otherwise, that comma-list would be seen as consisting of one empty item). Then loop over the comma-list, grabbing one comma-delimited item at a time. The end is marked by `\q_recursion_tail`. The auxiliary function `__clist_map_function:Nw` is used directly in `\clist_map_inline:Nn`. Change with care.

```

6826 \cs_new:Npn \clist_map_function:NN #1#2
6827 {
6828   \clist_if_empty:NF #1
6829   {
6830     \exp_last_unbraced:NNo \__clist_map_function:Nw #2 #1
6831     , \q_recursion_tail ,
6832     \__prg_break_point:Nn \clist_map_break: { }
6833   }
6834 }
6835 \cs_new:Npn \__clist_map_function:Nw #1#2 ,
6836 {
6837   \__quark_if_recursion_tail_break:nN {#2} \clist_map_break:
6838   #1 {#2}
6839   \__clist_map_function:Nw #1
6840 }
6841 \cs_generate_variant:Nn \clist_map_function:NN { c }

```

(End definition for `\clist_map_function:NN` and `__clist_map_function:Nw`. This function is documented on page 109.)

```

\clist_map_function:nN
\__clist_map_function_n:Nn
\__clist_map_unbrace:Nw

```

The `n`-type mapping function is a bit more awkward, since spaces must be trimmed from each item. Space trimming is again based on `__clist_trim_spaces_generic:nw`.

The auxiliary `__clist_map_function:n:Nn` receives as arguments the function, and the result of removing leading and trailing spaces from the item which lies until the next comma. Empty items are ignored, then one level of braces is removed by `__clist_map_unbrace:Nw`.

```

6842 \cs_new:Npn \clist_map_function:nN #1#2
6843 {
6844   \__clist_trim_spaces_generic:nw { \__clist_map_function:n:Nn #2 }
6845   \q_mark #1, \q_recursion_tail,
6846   \__prg_break_point:Nn \clist_map_break: { }
6847 }
6848 \cs_new:Npn \__clist_map_function_n:Nn #1 #2
6849 {
6850   \__quark_if_recursion_tail_break:nN {#2} \clist_map_break:
6851   \tl_if_empty:nF {#2} { \__clist_map_unbrace:Nw #1 #2, }
6852   \__clist_trim_spaces_generic:nw { \__clist_map_function_n:Nn #1 }
6853   \q_mark
6854 }
6855 \cs_new:Npn \__clist_map_unbrace:Nw #1 #2, { #1 {#2} }

```

(End definition for `\clist_map_function:nN`, `__clist_map_function_n:Nn`, and `__clist_map_unbrace:Nw`. This function is documented on page 109.)

`\clist_map_inline:Nn`
`\clist_map_inline:cn`
`\clist_map_inline:nn`

Inline mapping is done by creating a suitable function “on the fly”: this is done globally to avoid any issues with \TeX ’s groups. We use a different function for each level of nesting.

Since the mapping is non-expandable, we can perform the space-trimming needed by the `n` version simply by storing the comma-list in a variable. We don’t need a different comma-list for each nesting level: the comma-list is expanded before the mapping starts.

```

6856 \cs_new_protected:Npn \clist_map_inline:Nn #1#2
6857 {
6858   \clist_if_empty:NF #1
6859   {
6860     \int_gincr:N \g__prg_map_int
6861     \cs_gset_protected:cpn
6862     { \__prg_map_ \int_use:N \g__prg_map_int :w } ##1 {#2}
6863     \exp_last_unbraced:Nco \__clist_map_function:Nw
6864     { \__prg_map_ \int_use:N \g__prg_map_int :w }
6865     #1 , \q_recursion_tail ,
6866     \__prg_break_point:Nn \clist_map_break:
6867     { \int_gdecr:N \g__prg_map_int }
6868   }
6869 }
6870 \cs_new_protected:Npn \clist_map_inline:nn #1
6871 {
6872   \clist_set:Nn \l__clist_internal_clist {#1}
6873   \clist_map_inline:Nn \l__clist_internal_clist
6874 }
6875 \cs_generate_variant:Nn \clist_map_inline:Nn { c }

```

(End definition for `\clist_map_inline:Nn` and `\clist_map_inline:nn`. These functions are documented on page 109.)

`\clist_map_variable:NNn`
`\clist_map_variable:cNn`
`\clist_map_variable:nNn`
`__clist_map_variable:Nnw`

As for other comma-list mappings, filter out the case of an empty list. Same approach as `\clist_map_function:Nn`, additionally we store each item in the given variable. As

for inline mappings, space trimming for the `n` variant is done by storing the comma list in a variable.

```

6876 \cs_new_protected:Npn \clist_map_variable:NNn #1#2#3
6877 {
6878   \clist_if_empty:NF #1
6879   {
6880     \exp_args:Nno \use:nn
6881     { \__clist_map_variable:Nnw #2 {#3} }
6882     #1
6883     , \q_recursion_tail , \q_recursion_stop
6884     \__prg_break_point:Nn \clist_map_break: { }
6885   }
6886 }
6887 \cs_new_protected:Npn \clist_map_variable:nNn #1
6888 {
6889   \clist_set:Nn \l__clist_internal_clist {#1}
6890   \clist_map_variable:NNn \l__clist_internal_clist
6891 }
6892 \cs_new_protected:Npn \__clist_map_variable:Nnw #1#2#3,
6893 {
6894   \tl_set:Nn #1 {#3}
6895   \quark_if_recursion_tail_stop:N #1
6896   \use:n {#2}
6897   \__clist_map_variable:Nnw #1 {#2}
6898 }
6899 \cs_generate_variant:Nn \clist_map_variable:NNn { c }

```

(End definition for `\clist_map_variable:NNn`, `\clist_map_variable:nNn`, and `__clist_map_variable:Nnw`. These functions are documented on page 109.)

`\clist_map_break:` The break statements use the general `__prg_map_break:Nn` mechanism.
`\clist_map_break:n`

```

6900 \cs_new:Npn \clist_map_break:
6901 { \__prg_map_break:Nn \clist_map_break: { } }
6902 \cs_new:Npn \clist_map_break:n
6903 { \__prg_map_break:Nn \clist_map_break: }

```

(End definition for `\clist_map_break:` and `\clist_map_break:n`. These functions are documented on page 109.)

`\clist_count:N` Counting the items in a comma list is done using the same approach as for other token
`\clist_count:c` count functions: turn each entry into a +1 then use integer evaluation to actually do the
`\clist_count:n` mathematics. In the case of an `n`-type comma-list, we could of course use `\clist_map_-`
`__clist_count:n` **function:nN**, but that is very slow, because it carefully removes spaces. Instead, we loop
`__clist_count:w` manually, and skip blank items (but not `{}`, hence the extra spaces).

```

6904 \cs_new:Npn \clist_count:N #1
6905 {
6906   \int_eval:n
6907   {
6908     0
6909     \clist_map_function:NN #1 \__clist_count:n
6910   }
6911 }
6912 \cs_generate_variant:Nn \clist_count:N { c }
6913 \cs_new:Npx \clist_count:n #1

```

```

6914 {
6915   \exp_not:N \int_eval:n
6916   {
6917     0
6918     \exp_not:N \__clist_count:w \c_space_tl
6919     #1 \exp_not:n { , \q_recursion_tail , \q_recursion_stop }
6920   }
6921 }
6922 \cs_new:Npn \__clist_count:n #1 { + 1 }
6923 \cs_new:Npx \__clist_count:w #1 ,
6924 {
6925   \exp_not:n { \exp_args:Nf \quark_if_recursion_tail_stop:n } {#1}
6926   \exp_not:N \tl_if_blank:nF {#1} { + 1 }
6927   \exp_not:N \__clist_count:w \c_space_tl
6928 }

```

(End definition for `\clist_count:N` and others. These functions are documented on page 110.)

13.8 Using comma lists

`\clist_use:Nnnn` First check that the variable exists. Then count the items in the comma list. If it has none, output nothing. If it has one item, output that item, brace stripped (note that space-trimming has already been done when the comma list was assigned). If it has two, place the *<separator between two>* in the middle.

Otherwise, `__clist_use:nwwwnwn` takes the following arguments; 1: a *<separator>*, 2, 3, 4: three items from the comma list (or quarks), 5: the rest of the comma list, 6: a *<continuation>* function (`use_ii` or `use_iii` with its *<separator>* argument), 7: junk, and 8: the temporary result, which is built in a brace group following `\q_stop`. The *<separator>* and the first of the three items are placed in the result, then we use the *<continuation>*, placing the remaining two items after it. When we begin this loop, the three items really belong to the comma list, the first `\q_mark` is taken as a delimiter to the `use_ii` function, and the continuation is `use_ii` itself. When we reach the last two items of the original token list, `\q_mark` is taken as a third item, and now the second `\q_mark` serves as a delimiter to `use_ii`, switching to the other *<continuation>*, `use_iii`, which uses the *<separator between final two>*.

```

6929 \cs_new:Npn \clist_use:Nnnn #1#2#3#4
6930 {
6931   \clist_if_exist:NTF #1
6932   {
6933     \int_case:nnF { \clist_count:N #1 }
6934     {
6935       { 0 } { }
6936       { 1 } { \exp_after:wN \__clist_use:wnn #1 , , { } }
6937       { 2 } { \exp_after:wN \__clist_use:wnn #1 , {#2} }
6938     }
6939     {
6940       \exp_after:wN \__clist_use:nwwwnwn
6941       \exp_after:wN { \exp_after:wN } #1 ,
6942       \q_mark , { \__clist_use:nwwwnwn {#3} }
6943       \q_mark , { \__clist_use:nwnn {#4} }
6944       \q_stop { }
6945     }
6946   }

```



```

6947     {
6948         \_msg_kernel_expandable_error:nnn
6949         { kernel } { bad-variable } {#1}
6950     }
6951 }
6952 \cs_generate_variant:Nn \clist_use:Nnnn { c }
6953 \cs_new:Npn \__clist_use:wnn #1 , #2 , #3 { \exp_not:n { #1 #3 #2 } }
6954 \cs_new:Npn \__clist_use:nwwwnnw
6955     #1#2 , #3 , #4 , #5 \q_mark , #6#7 \q_stop #8
6956     { #6 {#3} , {#4} , #5 \q_mark , {#6} #7 \q_stop { #8 #1 #2 } }
6957 \cs_new:Npn \__clist_use:nwnn #1#2 , #3 \q_stop #4
6958     { \exp_not:n { #4 #1 #2 } }
6959 \cs_new:Npn \clist_use:Nn #1#2
6960     { \clist_use:Nnnn #1 {#2} {#2} {#2} }
6961 \cs_generate_variant:Nn \clist_use:Nn { c }

```

(End definition for `\clist_use:Nnnn` and others. These functions are documented on page 110.)

13.9 Using a single item

<pre> \clist_item:Nn \clist_item:cn __clist_item:nnnN __clist_item:ffoN __clist_item:ffnN __clist_item_N_loop:nw </pre>	<p>To avoid needing to test the end of the list at each step, we first compute the $\langle length \rangle$ of the list. If the item number is 0, less than $-\langle length \rangle$, or more than $\langle length \rangle$, the result is empty. If it is negative, but not less than $-\langle length \rangle$, add $\langle length \rangle + 1$ to the item number before performing the loop. The loop itself is very simple, return the item if the counter reached 1, otherwise, decrease the counter and repeat.</p> <pre> 6962 \cs_new:Npn \clist_item:Nn #1#2 6963 { 6964 __clist_item:ffoN 6965 { \clist_count:N #1 } 6966 { \int_eval:n {#2} } 6967 #1 6968 __clist_item_N_loop:nw 6969 } 6970 \cs_new:Npn __clist_item:nnnN #1#2#3#4 6971 { 6972 \int_compare:nNnTF {#2} < 0 6973 { 6974 \int_compare:nNnTF {#2} < { - #1 } 6975 { \use_none_delimit_by_q_stop:w } 6976 { \exp_args:Nf #4 { \int_eval:n { #2 + 1 + #1 } } } 6977 } 6978 { 6979 \int_compare:nNnTF {#2} > {#1} 6980 { \use_none_delimit_by_q_stop:w } 6981 { #4 {#2} } 6982 } 6983 { } , #3 , \q_stop 6984 } 6985 \cs_generate_variant:Nn __clist_item:nnnN { ffo, ff } 6986 \cs_new:Npn __clist_item_N_loop:nw #1 #2, 6987 { 6988 \int_compare:nNnTF {#1} = 0 6989 { \use_i_delimit_by_q_stop:nw { \exp_not:n {#2} } } 6990 { \exp_args:Nf __clist_item_N_loop:nw { \int_eval:n { #1 - 1 } } } </pre>
---	--

```

6991 }
6992 \cs_generate_variant:Nn \clist_item:Nn { c }

```

(End definition for `\clist_item:Nn`, `__clist_item:nnnN`, and `__clist_item_N_loop:nw`. This function is documented on page 112.)

```

\clist_item:nn This starts in the same way as \clist_item:Nn by counting the items of the comma list.
\__clist_item_n:nw The final item should be space-trimmed before being brace-stripped, hence we insert a
\__clist_item_n_loop:nw couple of odd-looking \prg_do_nothing: to avoid losing braces. Blank items are ignored.
\__clist_item_n_end:n
\__clist_item_n_strip:w
6993 \cs_new:Npn \clist_item:nn #1#2
6994 {
6995   \__clist_item:ffnN
6996   { \clist_count:n {#1} }
6997   { \int_eval:n {#2} }
6998   {#1}
6999   \__clist_item_n:nw
7000 }
7001 \cs_new:Npn \__clist_item_n:nw #1
7002 { \__clist_item_n_loop:nw {#1} \prg_do_nothing: }
7003 \cs_new:Npn \__clist_item_n_loop:nw #1 #2,
7004 {
7005   \exp_args:No \tl_if_blank:nTF {#2}
7006   { \__clist_item_n_loop:nw {#1} \prg_do_nothing: }
7007   {
7008     \int_compare:nNnTF {#1} = 0
7009     { \exp_args:No \__clist_item_n_end:n {#2} }
7010     {
7011       \exp_args:Nf \__clist_item_n_loop:nw
7012       { \int_eval:n { #1 - 1 } }
7013       \prg_do_nothing:
7014     }
7015   }
7016 }
7017 \cs_new:Npn \__clist_item_n_end:n #1 #2 \q_stop
7018 {
7019   \__tl_trim_spaces:nn { \q_mark #1 }
7020   { \exp_last_unbraced:No \__clist_item_n_strip:w } ,
7021 }
7022 \cs_new:Npn \__clist_item_n_strip:w #1 , { \exp_not:n {#1} }

```

(End definition for `\clist_item:nn` and others. This function is documented on page 112.)

13.10 Viewing comma lists

```

\clist_show:N Apply the general \__kernel_check_defined:NT and \msg_show:nnnnnn.
\clist_show:c
\clist_log:N
\clist_log:c
\__clist_show:NN
7023 \cs_new_protected:Npn \clist_show:N { \__clist_show:NN \msg_show:nnxxxx }
7024 \cs_generate_variant:Nn \clist_show:N { c }
7025 \cs_new_protected:Npn \clist_log:N { \__clist_show:NN \msg_log:nnxxxx }
7026 \cs_generate_variant:Nn \clist_log:N { c }
7027 \cs_new_protected:Npn \__clist_show:NN #1#2
7028 {
7029   \__kernel_check_defined:NT #2
7030   {
7031     #1 { LaTeX/kernel } { show-clist }

```

```

7032         { \token_to_str:N #2 }
7033         { \clist_map_function:NN #2 \msg_show_item:n }
7034         { } { }
7035     }
7036 }

```

(End definition for `\clist_show:N`, `\clist_log:N`, and `__clist_show:NN`. These functions are documented on page 112.)

```

\clist_show:n A variant of the above: no existence check, empty first argument for the message.
\clist_log:n
\__clist_show:Nn
7037 \cs_new_protected:Npn \clist_show:n { \__clist_show:Nn \msg_show:nnxxxx }
7038 \cs_new_protected:Npn \clist_log:n { \__clist_show:Nn \msg_log:nnxxxx }
7039 \cs_new_protected:Npn \__clist_show:Nn #1#2
7040 {
7041     #1 { LaTeX/kernel } { show-clist }
7042     { } { \clist_map_function:nN {#2} \msg_show_item:n } { } { }
7043 }

```

(End definition for `\clist_show:n`, `\clist_log:n`, and `__clist_show:Nn`. These functions are documented on page 112.)

13.11 Scratch comma lists

```

\l_tmpa_clist Temporary comma list variables.
\l_tmpb_clist
\g_tmpa_clist
\g_tmpb_clist
7044 \clist_new:N \l_tmpa_clist
7045 \clist_new:N \l_tmpb_clist
7046 \clist_new:N \g_tmpa_clist
7047 \clist_new:N \g_tmpb_clist

```

(End definition for `\l_tmpa_clist` and others. These variables are documented on page 113.)

```

7048 </initex | package>

```

14 l3token implementation

```

7049 <*initex | package>
7050 <@@=char>

```

14.1 Manipulating and interrogating character tokens

```

\char_set_catcode:nn Simple wrappers around the primitives.
\char_value_catcode:n
\char_show_value_catcode:n
7051 \cs_new_protected:Npn \char_set_catcode:nn #1#2
7052 { \tex_catcode:D \__int_eval:n {#1} = \__int_eval:n {#2} }
7053 \cs_new:Npn \char_value_catcode:n #1
7054 { \tex_the:D \tex_catcode:D \__int_eval:n {#1} }
7055 \cs_new_protected:Npn \char_show_value_catcode:n #1
7056 { \exp_args:Nf \tl_show:n { \char_value_catcode:n {#1} } }

```

(End definition for `\char_set_catcode:nn`, `\char_value_catcode:n`, and `\char_show_value_catcode:n`. These functions are documented on page 117.)

```

\char_set_catcode_escape:N
  \char_set_catcode_group_begin:N
  \char_set_catcode_group_end:N
  \char_set_catcode_math_toggle:N
  \char_set_catcode_alignment:N
\char_set_catcode_end_line:N
  \char_set_catcode_parameter:N
  \char_set_catcode_math_superscript:N
  \char_set_catcode_math_subscript:N
\char_set_catcode_ignore:N
\char_set_catcode_space:N
\char_set_catcode_letter:N
\char_set_catcode_other:N
\char_set_catcode_active:N
\char_set_catcode_comment:N
\char_set_catcode_invalid:N

7057 \cs_new_protected:Npn \char_set_catcode_escape:N #1
7058   { \char_set_catcode:nn { '#1 } { 0 } }
7059 \cs_new_protected:Npn \char_set_catcode_group_begin:N #1
7060   { \char_set_catcode:nn { '#1 } { 1 } }
7061 \cs_new_protected:Npn \char_set_catcode_group_end:N #1
7062   { \char_set_catcode:nn { '#1 } { 2 } }
7063 \cs_new_protected:Npn \char_set_catcode_math_toggle:N #1
7064   { \char_set_catcode:nn { '#1 } { 3 } }
7065 \cs_new_protected:Npn \char_set_catcode_alignment:N #1
7066   { \char_set_catcode:nn { '#1 } { 4 } }
7067 \cs_new_protected:Npn \char_set_catcode_end_line:N #1
7068   { \char_set_catcode:nn { '#1 } { 5 } }
7069 \cs_new_protected:Npn \char_set_catcode_parameter:N #1
7070   { \char_set_catcode:nn { '#1 } { 6 } }
7071 \cs_new_protected:Npn \char_set_catcode_math_superscript:N #1
7072   { \char_set_catcode:nn { '#1 } { 7 } }
7073 \cs_new_protected:Npn \char_set_catcode_math_subscript:N #1
7074   { \char_set_catcode:nn { '#1 } { 8 } }
7075 \cs_new_protected:Npn \char_set_catcode_ignore:N #1
7076   { \char_set_catcode:nn { '#1 } { 9 } }
7077 \cs_new_protected:Npn \char_set_catcode_space:N #1
7078   { \char_set_catcode:nn { '#1 } { 10 } }
7079 \cs_new_protected:Npn \char_set_catcode_letter:N #1
7080   { \char_set_catcode:nn { '#1 } { 11 } }
7081 \cs_new_protected:Npn \char_set_catcode_other:N #1
7082   { \char_set_catcode:nn { '#1 } { 12 } }
7083 \cs_new_protected:Npn \char_set_catcode_active:N #1
7084   { \char_set_catcode:nn { '#1 } { 13 } }
7085 \cs_new_protected:Npn \char_set_catcode_comment:N #1
7086   { \char_set_catcode:nn { '#1 } { 14 } }
7087 \cs_new_protected:Npn \char_set_catcode_invalid:N #1
7088   { \char_set_catcode:nn { '#1 } { 15 } }

```

(End definition for `\char_set_catcode_escape:N` and others. These functions are documented on page 116.)

```

\char_set_catcode_escape:n
  \char_set_catcode_group_begin:n
  \char_set_catcode_group_end:n
  \char_set_catcode_math_toggle:n
  \char_set_catcode_alignment:n
\char_set_catcode_end_line:n
  \char_set_catcode_parameter:n
  \char_set_catcode_math_superscript:n
  \char_set_catcode_math_subscript:n
\char_set_catcode_ignore:n
\char_set_catcode_space:n
\char_set_catcode_letter:n
\char_set_catcode_other:n
\char_set_catcode_active:n
\char_set_catcode_comment:n
\char_set_catcode_invalid:n

7089 \cs_new_protected:Npn \char_set_catcode_escape:n #1
7090   { \char_set_catcode:nn {#1} { 0 } }
7091 \cs_new_protected:Npn \char_set_catcode_group_begin:n #1
7092   { \char_set_catcode:nn {#1} { 1 } }
7093 \cs_new_protected:Npn \char_set_catcode_group_end:n #1
7094   { \char_set_catcode:nn {#1} { 2 } }
7095 \cs_new_protected:Npn \char_set_catcode_math_toggle:n #1
7096   { \char_set_catcode:nn {#1} { 3 } }
7097 \cs_new_protected:Npn \char_set_catcode_alignment:n #1
7098   { \char_set_catcode:nn {#1} { 4 } }
7099 \cs_new_protected:Npn \char_set_catcode_end_line:n #1
7100   { \char_set_catcode:nn {#1} { 5 } }
7101 \cs_new_protected:Npn \char_set_catcode_parameter:n #1
7102   { \char_set_catcode:nn {#1} { 6 } }
7103 \cs_new_protected:Npn \char_set_catcode_math_superscript:n #1
7104   { \char_set_catcode:nn {#1} { 7 } }

```

```

7105 \cs_new_protected:Npn \char_set_catcode_math_subscript:n #1
7106 { \char_set_catcode:nn {#1} { 8 } }
7107 \cs_new_protected:Npn \char_set_catcode_ignore:n #1
7108 { \char_set_catcode:nn {#1} { 9 } }
7109 \cs_new_protected:Npn \char_set_catcode_space:n #1
7110 { \char_set_catcode:nn {#1} { 10 } }
7111 \cs_new_protected:Npn \char_set_catcode_letter:n #1
7112 { \char_set_catcode:nn {#1} { 11 } }
7113 \cs_new_protected:Npn \char_set_catcode_other:n #1
7114 { \char_set_catcode:nn {#1} { 12 } }
7115 \cs_new_protected:Npn \char_set_catcode_active:n #1
7116 { \char_set_catcode:nn {#1} { 13 } }
7117 \cs_new_protected:Npn \char_set_catcode_comment:n #1
7118 { \char_set_catcode:nn {#1} { 14 } }
7119 \cs_new_protected:Npn \char_set_catcode_invalid:n #1
7120 { \char_set_catcode:nn {#1} { 15 } }

```

(End definition for `\char_set_catcode_escape:n` and others. These functions are documented on page 116.)

```

\char_set_mathcode:nn Pretty repetitive, but necessary!
\char_value_mathcode:n
\char_show_value_mathcode:n
\char_set_lccode:nn
\char_value_lccode:n
\char_show_value_lccode:n
\char_set_uccode:nn
\char_value_uccode:n
\char_show_value_uccode:n
\char_set_sfcode:nn
\char_value_sfcode:n
\char_show_value_sfcode:n
7121 \cs_new_protected:Npn \char_set_mathcode:nn #1#2
7122 { \tex_mathcode:D \__int_eval:n {#1} = \__int_eval:n {#2} }
7123 \cs_new:Npn \char_value_mathcode:n #1
7124 { \tex_the:D \tex_mathcode:D \__int_eval:n {#1} }
7125 \cs_new_protected:Npn \char_show_value_mathcode:n #1
7126 { \exp_args:Nf \tl_show:n { \char_value_mathcode:n {#1} } }
7127 \cs_new_protected:Npn \char_set_lccode:nn #1#2
7128 { \tex_lccode:D \__int_eval:n {#1} = \__int_eval:n {#2} }
7129 \cs_new:Npn \char_value_lccode:n #1
7130 { \tex_the:D \tex_lccode:D \__int_eval:n {#1} }
7131 \cs_new_protected:Npn \char_show_value_lccode:n #1
7132 { \exp_args:Nf \tl_show:n { \char_value_lccode:n {#1} } }
7133 \cs_new_protected:Npn \char_set_uccode:nn #1#2
7134 { \tex_uccode:D \__int_eval:n {#1} = \__int_eval:n {#2} }
7135 \cs_new:Npn \char_value_uccode:n #1
7136 { \tex_the:D \tex_uccode:D \__int_eval:n {#1} }
7137 \cs_new_protected:Npn \char_show_value_uccode:n #1
7138 { \exp_args:Nf \tl_show:n { \char_value_uccode:n {#1} } }
7139 \cs_new_protected:Npn \char_set_sfcode:nn #1#2
7140 { \tex_sfcode:D \__int_eval:n {#1} = \__int_eval:n {#2} }
7141 \cs_new:Npn \char_value_sfcode:n #1
7142 { \tex_the:D \tex_sfcode:D \__int_eval:n {#1} }
7143 \cs_new_protected:Npn \char_show_value_sfcode:n #1
7144 { \exp_args:Nf \tl_show:n { \char_value_sfcode:n {#1} } }

```

(End definition for `\char_set_mathcode:nn` and others. These functions are documented on page 118.)

`\l_char_active_seq` Two sequences for dealing with special characters. The first is characters which may be active, the second longer list is for “special” characters more generally. Both lists are escaped so that for example bulk code assignments can be carried out. In both cases, the order is by ASCII character code (as is done in for example `\ExplSyntaxOn`).

```

7145 \seq_new:N \l_char_special_seq
7146 \seq_set_split:Nnn \l_char_special_seq { }

```

```

7147 { \ \ " \# \$ \% \& \ \ ^ \_ \{ \} \~ }
7148 \seq_new:N \l_char_active_seq
7149 \seq_set_split:Nnn \l_char_active_seq { }
7150 { \ " \$ & ^ _ \~ }

```

(End definition for `\l_char_active_seq` and `\l_char_special_seq`. These variables are documented on page 118.)

14.2 Creating character tokens

```

\char_set_active_eq:NN
\char_set_active_eq:Nc
\char_gset_active_eq:NN
\char_gset_active_eq:Nc
\char_set_active_eq:nN
\char_gset_active_eq:nc
\char_set_active_eq:nc
\char_gset_active_eq:nc

```

Four simple functions with very similar definitions, so set up using an auxiliary. These are similar to LuaTeX's `\letcharcode` primitive.

```

7151 \group_begin:
7152   \char_set_catcode_active:N \^^@
7153   \cs_set_protected:Npn \__char_tmp:nN #1#2
7154   {
7155     \cs_new_protected:cpn { #1 :nN } ##1
7156     {
7157       \group_begin:
7158         \char_set_lccode:nn { \^^@ } { ##1 }
7159         \tex_lowercase:D { \group_end: #2 ^^@ }
7160       }
7161     \cs_new_protected:cpx { #1 :NN } ##1
7162     { \exp_not:c { #1 : nN } { '##1 } }
7163   }
7164   \__char_tmp:nN { char_set_active_eq } \cs_set_eq:NN
7165   \__char_tmp:nN { char_gset_active_eq } \cs_gset_eq:NN
7166 \group_end:
7167 \cs_generate_variant:Nn \char_set_active_eq:NN { Nc }
7168 \cs_generate_variant:Nn \char_gset_active_eq:NN { Nc }
7169 \cs_generate_variant:Nn \char_set_active_eq:nN { nc }
7170 \cs_generate_variant:Nn \char_gset_active_eq:nN { nc }

```

(End definition for `\char_set_active_eq:NN` and others. These functions are documented on page 114.)

```

\char_generate:nn
\__char_generate:nn
\__char_generate_aux:nn
\__char_generate_aux:nnw
  \l__char_tmp_tl
  \c__char_max_int
\__char_generate_invalid_catcode:

```

The aim here is to generate characters of (broadly) arbitrary category code. Where possible, that is done using engine support (XeTeX, LuaTeX). There are though various issues which are covered below. At the interface layer, turn the two arguments into integers up-front so this is only done once.

```

7171 \__debug_patch_args:nNn { { \__int_eval:n {#1} } { \__int_eval:n {#2} } }
7172 \cs_new:Npn \char_generate:nn #1#2
7173 {
7174   \exp:w \exp_after:wN \__char_generate_aux:w
7175     \__int_value:w \__int_eval:w #1 \exp_after:wN ;
7176     \__int_value:w \__int_eval:w #2 ;
7177 }
7178 \cs_new:Npn \__char_generate:nn #1#2
7179 {
7180   \exp:w \exp_after:wN
7181     \__char_generate_aux:nnw \exp_after:wN
7182     { \__int_value:w \__int_eval:w #1 } {#2} \exp_end:
7183 }

```

Before doing any actual conversion, first some special case filtering. The `\Ucharcat` primitive cannot make active chars, so that is turned off here: if the primitive gets altered then the code is already in place for 8-bit engines and will kick in for LuaTeX too. Spaces are also banned here as LuaTeX emulation only makes normal (charcode 32 spaces. However, `^^@` is filtered out separately as that can't be done with macro emulation either, so is flagged up separately. That done, hand off to the engine-dependent part.

```

7184 \cs_new:Npn \__char_generate_aux:w #1 ; #2 ;
7185 {
7186   \if_int_compare:w #2 = 13 \exp_stop_f:
7187     \__msg_kernel_expandable_error:nn { kernel } { char-active }
7188   \else:
7189     \if_int_compare:w #2 = 10 \exp_stop_f:
7190       \if_int_compare:w #1 = 0 \exp_stop_f:
7191         \__msg_kernel_expandable_error:nn { kernel } { char-null-space }
7192       \else:
7193         \__msg_kernel_expandable_error:nn { kernel } { char-space }
7194       \fi:
7195     \else:
7196       \if_int_odd:w 0
7197         \if_int_compare:w #2 < 1 \exp_stop_f: 1 \fi:
7198         \if_int_compare:w #2 = 5 \exp_stop_f: 1 \fi:
7199         \if_int_compare:w #2 = 9 \exp_stop_f: 1 \fi:
7200         \if_int_compare:w #2 > 13 \exp_stop_f: 1 \fi: \exp_stop_f:
7201         \__msg_kernel_expandable_error:nn { kernel }
7202         { char-invalid-catcode }
7203       \else:
7204         \if_int_odd:w 0
7205           \if_int_compare:w #1 < 0 \exp_stop_f: 1 \fi:
7206           \if_int_compare:w #1 > \c_char_max_int 1 \fi: \exp_stop_f:
7207           \__msg_kernel_expandable_error:nn { kernel }
7208           { char-out-of-range }
7209         \else:
7210           \__char_generate_aux:nnw {#1} {#2}
7211         \fi:
7212       \fi:
7213     \fi:
7214   \fi:
7215   \exp_end:
7216 }
7217 \tl_new:N \l__char_tmp_tl

```

Engine-dependent definitions are now needed for the implementation. For LuaTeX and recent XeTeX releases there is engine-level support. They can do cases that macro emulation can't. All of those are filtered out here using a primitive-based boolean expression for speed. The final level is the basic definition at the engine level: the arguments here are integers so there is no need to worry about them too much.

```

7218 \group_begin:
7219 <*package>
7220   \char_set_catcode_active:N \^^L
7221   \cs_set:Npn ^^L { }
7222 </package>
7223   \char_set_catcode_other:n { 0 }
7224   \if_int_odd:w 0

```

```

7225     \cs_if_exist:NT \luatex_directlua:D { 1 }
7226     \cs_if_exist:NT \utex_charcat:D      { 1 } \exp_stop_f:
7227     \int_const:Nn \c__char_max_int { 1114111 }
7228     \cs_if_exist:NTF \luatex_directlua:D
7229     {
7230         \cs_new:Npn \__char_generate_aux:nw #1#2#3 \exp_end:
7231         {
7232             #3
7233             \exp_after:wN \exp_end:
7234             \luatex_directlua:D { l3kernel.charcat(#1, #2) }
7235         }
7236     }
7237     {
7238         \cs_new:Npn \__char_generate_aux:nw #1#2#3 \exp_end:
7239         {
7240             #3
7241             \exp_after:wN \exp_end:
7242             \utex_charcat:D #1 ~ #2 ~
7243         }
7244     }
7245     \else:

```

For engines where `\Ucharcat` isn't available (or emulated) then we have to work in macros, and cover only the 8-bit range. The first stage is to build up a `tl` containing `^^@` with each category code that can be accessed in this way, with an error set up for the other cases. This is all done such that it can be quickly accessed using a `\if_case:w` low-level conditional. There are a few things to notice here. As `^^L` is `\outer` we need to locally set it to avoid a problem. To get open/close braces into the list, they are set up using `\if_false:` pairing and are then x-type expanded together into the desired form.

```

7246     \int_const:Nn \c__char_max_int { 255 }
7247     \tl_set:Nn \l__char_tmp_tl { \exp_not:N \or: }
7248     \char_set_catcode_group_begin:n { 0 } % {
7249     \tl_put_right:Nn \l__char_tmp_tl { ^^@ \if_false: } }
7250     \char_set_catcode_group_end:n { 0 }
7251     \tl_put_right:Nn \l__char_tmp_tl { { \fi: \exp_not:N \or: ^^@ } % }
7252     \tl_set:Nx \l__char_tmp_tl { \l__char_tmp_tl }
7253     \char_set_catcode_math_toggle:n { 0 }
7254     \tl_put_right:Nn \l__char_tmp_tl { \or: ^^@ }

```

As \TeX is very unhappy if it finds an alignment character inside a primitive `\halign` even when skipping false branches, some precautions are required. \TeX is happy if the token is hidden inside `\unexpanded` (which needs to be the primitive). The expansion chain here is required so that the conditional gets cleaned up correctly (other code assumes there is exactly one token to skip during the clean-up).

```

7255     \char_set_catcode_alignment:n { 0 }
7256     \tl_put_right:Nn \l__char_tmp_tl
7257     {
7258         \or:
7259         \etex_unexpanded:D \exp_after:wN
7260         { \exp_after:wN ^^@ \exp_after:wN }
7261     }
7262     \tl_put_right:Nn \l__char_tmp_tl { \or: }
7263     \char_set_catcode_parameter:n { 0 }
7264     \tl_put_right:Nn \l__char_tmp_tl { \or: ^^@ }

```



```

7265 \char_set_catcode_math_superscript:n { 0 }
7266 \tl_put_right:Nn \l__char_tmp_tl { \or: ^^@ }
7267 \char_set_catcode_math_subscript:n { 0 }
7268 \tl_put_right:Nn \l__char_tmp_tl { \or: ^^@ }
7269 \tl_put_right:Nn \l__char_tmp_tl { \or: }

```

For making spaces, there needs to be an o-type expansion of a `\use:n` (or some other tokenization) to avoid dropping the space. We also set up active tokens although they are (currently) filtered out by the interface layer (`\Ucharcat` cannot make active tokens).

```

7270 \char_set_catcode_space:n { 0 }
7271 \tl_put_right:No \l__char_tmp_tl { \use:n { \or: } ^^@ }
7272 \char_set_catcode_letter:n { 0 }
7273 \tl_put_right:Nn \l__char_tmp_tl { \or: ^^@ }
7274 \char_set_catcode_other:n { 0 }
7275 \tl_put_right:Nn \l__char_tmp_tl { \or: ^^@ }
7276 \char_set_catcode_active:n { 0 }
7277 \tl_put_right:Nn \l__char_tmp_tl { \or: ^^@ }

```

Convert the above temporary list into a series of constant token lists, one for each character code, using `\tex_lowercase:D` to convert `^^@` in each case. The x-type expansion ensures that `\tex_lowercase:D` receives the contents of the token list. In package mode, `^^L` is awkward hence this is done in three parts. Notice that at this stage `^^@` is active.

```

7278 \cs_set_protected:Npn \__char_tmp:n #1
7279 {
7280   \char_set_lccode:nn { 0 } {#1}
7281   \char_set_lccode:nn { 32 } {#1}
7282   \exp_args:Nx \tex_lowercase:D
7283   {
7284     \tl_const:Nn
7285       \exp_not:c { c__char_ \__int_to_roman:w #1 _tl }
7286       { \exp_not:o \l__char_tmp_tl }
7287   }
7288 }
7289 \*package>
7290 \int_step_function:nnnN { 0 } { 1 } { 11 } \__char_tmp:n
7291 \group_begin:
7292   \tl_replace_once:Nnn \l__char_tmp_tl { ^^@ } { \ERROR }
7293   \__char_tmp:n { 12 }
7294 \group_end:
7295 \int_step_function:nnnN { 13 } { 1 } { 255 } \__char_tmp:n
7296 </package>
7297 \*initex>
7298 \int_step_function:nnnN { 0 } { 1 } { 255 } \__char_tmp:n
7299 </initex>
7300 \cs_new:Npn \__char_generate_aux:nnw #1#2#3 \exp_end:
7301 {
7302   #3
7303   \exp_after:wN \exp_after:wN
7304   \exp_after:wN \exp_end:
7305   \exp_after:wN \exp_after:wN
7306   \if_case:w #2
7307     \exp_last_unbraced:Nv \exp_stop_f:
7308     { c__char_ \__int_to_roman:w #1 _tl }
7309   \fi:

```

```

7310     }
7311     \fi:
7312 \group_end:

```

(End definition for `\char_generate:nn` and others. This function is documented on page 115.)

`\c_catcode_other_space_tl` Create a space with category code 12: an “other” space.

```

7313 \tl_const:Nx \c_catcode_other_space_tl { \char_generate:nn { '\ } { 12 } }

```

(End definition for `\c_catcode_other_space_tl`. This function is documented on page 115.)

14.3 Generic tokens

```

7314 <@@=token>

```

`\token_to_meaning:N` These are all defined in `l3basics`, as they are needed “early”. This is just a reminder!

`\token_to_meaning:c`

`\token_to_str:N`

`\token_to_str:c`

(End definition for `\token_to_meaning:N` and `\token_to_str:N`. These functions are documented on page 119.)

`\c_group_begin_token`

`\c_group_end_token`

`\c_math_toggle_token`

`\c_alignment_token`

`\c_parameter_token`

We define these useful tokens. For the brace and space tokens things have to be done by hand: the formal argument spec. for `\cs_new_eq:NN` does not cover them so we do things by hand. (As currently coded it would *work* with `\cs_new_eq:NN` but that’s not really a great idea to show off: we want people to stick to the defined interfaces and that includes us.) So that these few odd names go into the log when appropriate there is a need to hand-apply the `__chk_if_free_cs:N` check.

`\c_math_superscript_token`

`\c_math_subscript_token`

`\c_space_token`

`\c_catcode_letter_token`

`\c_catcode_other_token`

```

7315 \group_begin:
7316   \__chk_if_free_cs:N \c_group_begin_token
7317   \tex_global:D \tex_let:D \c_group_begin_token {
7318     \__chk_if_free_cs:N \c_group_end_token
7319     \tex_global:D \tex_let:D \c_group_end_token }
7320   \char_set_catcode_math_toggle:N \*
7321   \cs_new_eq:NN \c_math_toggle_token *
7322   \char_set_catcode_alignment:N \*
7323   \cs_new_eq:NN \c_alignment_token *
7324   \cs_new_eq:NN \c_parameter_token #
7325   \cs_new_eq:NN \c_math_superscript_token ^
7326   \char_set_catcode_math_subscript:N \*
7327   \cs_new_eq:NN \c_math_subscript_token *
7328   \__chk_if_free_cs:N \c_space_token
7329   \use:n { \tex_global:D \tex_let:D \c_space_token = ~ } ~
7330   \cs_new_eq:NN \c_catcode_letter_token a
7331   \cs_new_eq:NN \c_catcode_other_token 1
7332 \group_end:

```

(End definition for `\c_group_begin_token` and others. These functions are documented on page 119.)

`\c_catcode_active_tl` Not an implicit token!

```

7333 \group_begin:
7334   \char_set_catcode_active:N \*
7335   \tl_const:Nn \c_catcode_active_tl { \exp_not:N * }
7336 \group_end:

```

(End definition for `\c_catcode_active_tl`. This variable is documented on page 119.)

14.4 Token conditionals

`\token_if_group_begin_p:N` Check if token is a begin group token. We use the constant `\c_group_begin_token` for this.
`\token_if_group_begin:N \underline{TF}`

```
7337 \prg_new_conditional:Npnn \token_if_group_begin:N #1 { p , T , F , TF }
7338 {
7339     \if_catcode:w \exp_not:N #1 \c_group_begin_token
7340     \prg_return_true: \else: \prg_return_false: \fi:
7341 }
```

(End definition for `\token_if_group_begin:N \underline{TF}` . This function is documented on page 119.)

`\token_if_group_end_p:N` Check if token is a end group token. We use the constant `\c_group_end_token` for this.
`\token_if_group_end:N \underline{TF}`

```
7342 \prg_new_conditional:Npnn \token_if_group_end:N #1 { p , T , F , TF }
7343 {
7344     \if_catcode:w \exp_not:N #1 \c_group_end_token
7345     \prg_return_true: \else: \prg_return_false: \fi:
7346 }
```

(End definition for `\token_if_group_end:N \underline{TF}` . This function is documented on page 120.)

`\token_if_math_toggle_p:N` Check if token is a math shift token. We use the constant `\c_math_toggle_token` for this.
`\token_if_math_toggle:N \underline{TF}`

```
7347 \prg_new_conditional:Npnn \token_if_math_toggle:N #1 { p , T , F , TF }
7348 {
7349     \if_catcode:w \exp_not:N #1 \c_math_toggle_token
7350     \prg_return_true: \else: \prg_return_false: \fi:
7351 }
```

(End definition for `\token_if_math_toggle:N \underline{TF}` . This function is documented on page 120.)

`\token_if_alignment_p:N` Check if token is an alignment tab token. We use the constant `\c_alignment_token` for this.
`\token_if_alignment:N \underline{TF}`

```
7352 \prg_new_conditional:Npnn \token_if_alignment:N #1 { p , T , F , TF }
7353 {
7354     \if_catcode:w \exp_not:N #1 \c_alignment_token
7355     \prg_return_true: \else: \prg_return_false: \fi:
7356 }
```

(End definition for `\token_if_alignment:N \underline{TF}` . This function is documented on page 120.)

`\token_if_parameter_p:N` Check if token is a parameter token. We use the constant `\c_parameter_token` for this.
`\token_if_parameter:N \underline{TF}` We have to trick T_EX a bit to avoid an error message: within a group we prevent `\c_parameter_token` from behaving like a macro parameter character. The definitions of `\prg_new_conditional:Npnn` are global, so they remain after the group.

```
7357 \group_begin:
7358 \cs_set_eq:NN \c_parameter_token \scan_stop:
7359 \prg_new_conditional:Npnn \token_if_parameter:N #1 { p , T , F , TF }
7360 {
7361     \if_catcode:w \exp_not:N #1 \c_parameter_token
7362     \prg_return_true: \else: \prg_return_false: \fi:
7363 }
7364 \group_end:
```

(End definition for `\token_if_parameter:N \underline{TF}` . This function is documented on page 120.)

`\token_if_math_superscript_p:N` Check if token is a math superscript token. We use the constant `\c_math_superscript_token` for this.
`\token_if_math_superscript:N \mathbf{TF}`

```

7365 \prg_new_conditional:Npnn \token_if_math_superscript:N #1
7366 { p , T , F , TF }
7367 {
7368   \if_catcode:w \exp_not:N #1 \c_math_superscript_token
7369   \prg_return_true: \else: \prg_return_false: \fi:
7370 }

```

(End definition for `\token_if_math_superscript:N \mathbf{TF}` . This function is documented on page 120.)

`\token_if_math_subscript_p:N` Check if token is a math subscript token. We use the constant `\c_math_subscript_token` for this.
`\token_if_math_subscript:N \mathbf{TF}`

```

7371 \prg_new_conditional:Npnn \token_if_math_subscript:N #1 { p , T , F , TF }
7372 {
7373   \if_catcode:w \exp_not:N #1 \c_math_subscript_token
7374   \prg_return_true: \else: \prg_return_false: \fi:
7375 }

```

(End definition for `\token_if_math_subscript:N \mathbf{TF}` . This function is documented on page 120.)

`\token_if_space_p:N` Check if token is a space token. We use the constant `\c_space_token` for this.

`\token_if_space:N \mathbf{TF}`

```

7376 \prg_new_conditional:Npnn \token_if_space:N #1 { p , T , F , TF }
7377 {
7378   \if_catcode:w \exp_not:N #1 \c_space_token
7379   \prg_return_true: \else: \prg_return_false: \fi:
7380 }

```

(End definition for `\token_if_space:N \mathbf{TF}` . This function is documented on page 120.)

`\token_if_letter_p:N` Check if token is a letter token. We use the constant `\c_catcode_letter_token` for this.

`\token_if_letter:N \mathbf{TF}`

```

7381 \prg_new_conditional:Npnn \token_if_letter:N #1 { p , T , F , TF }
7382 {
7383   \if_catcode:w \exp_not:N #1 \c_catcode_letter_token
7384   \prg_return_true: \else: \prg_return_false: \fi:
7385 }

```

(End definition for `\token_if_letter:N \mathbf{TF}` . This function is documented on page 120.)

`\token_if_other_p:N` Check if token is an other char token. We use the constant `\c_catcode_other_token` for this.
`\token_if_other:N \mathbf{TF}`

```

7386 \prg_new_conditional:Npnn \token_if_other:N #1 { p , T , F , TF }
7387 {
7388   \if_catcode:w \exp_not:N #1 \c_catcode_other_token
7389   \prg_return_true: \else: \prg_return_false: \fi:
7390 }

```

(End definition for `\token_if_other:N \mathbf{TF}` . This function is documented on page 120.)

`\token_if_active_p:N` Check if token is an active char token. We use the constant `\c_catcode_active_tl` for this. A technical point is that `\c_catcode_active_tl` is in fact a macro expanding to `\exp_not:N *`, where `*` is active.

`\token_if_active:N \mathbf{TF}`

```

7391 \prg_new_conditional:Npnn \token_if_active:N #1 { p , T , F , TF }
7392 {
7393   \if_catcode:w \exp_not:N #1 \c_catcode_active_tl
7394   \prg_return_true: \else: \prg_return_false: \fi:
7395 }

```

(End definition for `\token_if_active:NTF`. This function is documented on page 121.)

`\token_if_eq_meaning_p:NN` Check if the tokens #1 and #2 have same meaning.

```
\token_if_eq_meaning:NNTF
7396 \prg_new_conditional:Npnn \token_if_eq_meaning:NN #1#2 { p , T , F , TF }
7397 {
7398   \if_meaning:w #1 #2
7399   \prg_return_true: \else: \prg_return_false: \fi:
7400 }
```

(End definition for `\token_if_eq_meaning:NNTF`. This function is documented on page 121.)

`\token_if_eq_catcode_p:NN` Check if the tokens #1 and #2 have same category code.

```
\token_if_eq_catcode:NNTF
7401 \prg_new_conditional:Npnn \token_if_eq_catcode:NN #1#2 { p , T , F , TF }
7402 {
7403   \if_catcode:w \exp_not:N #1 \exp_not:N #2
7404   \prg_return_true: \else: \prg_return_false: \fi:
7405 }
```

(End definition for `\token_if_eq_catcode:NNTF`. This function is documented on page 121.)

`\token_if_eq_charcode_p:NN` Check if the tokens #1 and #2 have same character code.

```
\token_if_eq_charcode:NNTF
7406 \prg_new_conditional:Npnn \token_if_eq_charcode:NN #1#2 { p , T , F , TF }
7407 {
7408   \if_charcode:w \exp_not:N #1 \exp_not:N #2
7409   \prg_return_true: \else: \prg_return_false: \fi:
7410 }
```

(End definition for `\token_if_eq_charcode:NNTF`. This function is documented on page 121.)

`\token_if_macro_p:N` When a token is a macro, `\token_to_meaning:N` always outputs something like
`\token_if_macro:NTF` `\long macro:#1->#1` so we could naively check to see if the meaning contains `->`.
`__token_if_macro_p:w` However, this can fail the five `\...mark` primitives, whose meaning has the form `\...mark:<user material>`. The problem is that the `<user material>` can contain `->`.

However, only characters, macros, and marks can contain the colon character. The idea is thus to grab until the first `:`, and analyse what is left. However, macros can have any combination of `\long`, `\protected` or `\outer` (not used in L^AT_EX3) before the string `macro:.` We thus only select the part of the meaning between the first `ma` and the first following `:`. If this string is `cro`, then we have a macro. If the string is `rk`, then we have a mark. The string can also be `cro parameter character` for a colon with a weird category code (namely the usual category code of `#`). Otherwise, it is empty.

This relies on the fact that `\long`, `\protected`, `\outer` cannot contain `ma`, regardless of the escape character, even if the escape character is `m...`

Both `ma` and `:` must be of category code 12 (other), so are detokenized.

```
7411 \use:x
7412 {
7413   \prg_new_conditional:Npnn \exp_not:N \token_if_macro:N ##1
7414   { p , T , F , TF }
7415   {
7416     \exp_not:N \exp_after:wN \exp_not:N \__token_if_macro_p:w
7417     \exp_not:N \token_to_meaning:N ##1 \tl_to_str:n { ma : }
7418     \exp_not:N \q_stop
7419   }
7420   \cs_new:Npn \exp_not:N \__token_if_macro_p:w
```

```

7421     ##1 \tl_to_str:n { ma } ##2 \c_colon_str ##3 \exp_not:N \q_stop
7422   }
7423   {
7424     \if_int_compare:w \__str_if_eq_x:nn { #2 } { cro } = 0 \exp_stop_f:
7425     \prg_return_true:
7426     \else:
7427       \prg_return_false:
7428     \fi:
7429   }

```

(End definition for `\token_if_macro:NTF` and `__token_if_macro_p:w`. This function is documented on page 121.)

`\token_if_cs_p:N` Check if token has same catcode as a control sequence. This follows the same pattern as `\token_if_letter:N` etc. We use `\scan_stop:` for this.

`\token_if_cs:NTF`

```

7430 \prg_new_conditional:Npnn \token_if_cs:N #1 { p , T , F , TF }
7431 {
7432   \if_catcode:w \exp_not:N #1 \scan_stop:
7433   \prg_return_true: \else: \prg_return_false: \fi:
7434 }

```

(End definition for `\token_if_cs:NTF`. This function is documented on page 121.)

`\token_if_expandable_p:N` Check if token is expandable. We use the fact that T_EX temporarily converts `\exp_not:N` $\langle token \rangle$ into `\scan_stop:` if $\langle token \rangle$ is expandable. An undefined token is not considered as expandable. No problem nesting the conditionals, since the third #1 is only skipped if it is non-expandable (hence not part of T_EX's conditional apparatus).

`\token_if_expandable:NTF`

```

7435 \prg_new_conditional:Npnn \token_if_expandable:N #1 { p , T , F , TF }
7436 {
7437   \exp_after:wN \if_meaning:w \exp_not:N #1 #1
7438   \prg_return_false:
7439   \else:
7440     \if_cs_exist:N #1
7441     \prg_return_true:
7442     \else:
7443       \prg_return_false:
7444     \fi:
7445   \fi:
7446 }

```

(End definition for `\token_if_expandable:NTF`. This function is documented on page 121.)

`__token_delimit_by_char:w` These auxiliary functions are used below to define some conditionals which detect whether the `\meaning` of their argument begins with a particular string. Each auxiliary takes an argument delimited by a string, a second one delimited by `\q_stop`, and returns the first one and its delimiter. This result is eventually compared to another string.

`__token_delimit_by_count:w`
`__token_delimit_by_dimen:w`
`__token_delimit_by_macro:w`
`__token_delimit_by_muskip:w`
`__token_delimit_by_skip:w`
`__token_delimit_by_toks:w`

```

7447 \group_begin:
7448 \cs_set_protected:Npn \__token_tmp:w #1
7449 {
7450   \use:x
7451   {
7452     \cs_new:Npn \exp_not:c { __token_delimit_by_ #1 :w }
7453     #####1 \tl_to_str:n {#1} #####2 \exp_not:N \q_stop
7454     { #####1 \tl_to_str:n {#1} }

```

```

7455     }
7456   }
7457   \__token_tmp:w { char" }
7458   \__token_tmp:w { count }
7459   \__token_tmp:w { dimen }
7460   \__token_tmp:w { macro }
7461   \__token_tmp:w { muskip }
7462   \__token_tmp:w { skip }
7463   \__token_tmp:w { toks }
7464 \group_end:

```

(End definition for `__token_delimit_by_char:w` and others.)

<pre> \token_if_chardef_p:N \token_if_chardef:NTF \token_if_mathchardef_p:N \token_if_mathchardef:NTF \token_if_long_macro_p:N \token_if_long_macro:NTF \token_if_protected_macro_p:N \token_if_protected_macro:NTF \token_if_protected_long_macro_p:N \token_if_protected_long_macro:NTF \token_if_dim_register_p:N \token_if_dim_register:NTF \token_if_int_register_p:N \token_if_int_register:NTF \token_if_muskip_register_p:N \token_if_muskip_register:NTF \token_if_skip_register_p:N \token_if_skip_register:NTF \token_if_toks_register_p:N \token_if_toks_register:NTF </pre>	<p>Each of these conditionals tests whether its argument's <code>\meaning</code> starts with a given string. This is essentially done by having an auxiliary grab an argument delimited by the string and testing whether the argument was empty. Of course, a copy of this string must first be added to the end of the <code>\meaning</code> to avoid a runaway argument in case it does not contain the string. Two complications arise. First, the escape character is not fixed, and cannot be included in the delimiter of the auxiliary function (this function cannot be defined on the fly because tests must remain expandable): instead the first argument of the auxiliary (plus the delimiter to avoid complications with trailing spaces) is compared using <code>__str_if_eq_x_return:nn</code> to the result of applying <code>\token_to_str:N</code> to a control sequence. Second, the <code>\meaning</code> of primitives such as <code>\dimen</code> or <code>\dimendef</code> starts in the same way as registers such as <code>\dimen123</code>, so they must be tested for.</p> <p>Characters used as delimiters must have catcode 12 and are obtained through <code>\tl_to_str:n</code>. This requires doing all definitions within <code>x</code>-expansion. The temporary function <code>__token_tmp:w</code> used to define each conditional receives three arguments: the name of the conditional, the auxiliary's delimiter (also used to name the auxiliary), and the string to which one compares the auxiliary's result. Note that the <code>\meaning</code> of a protected long macro starts with <code>\protected\long macro</code>, with no space after <code>\protected</code> but a space after <code>\long</code>, hence the mixture of <code>\token_to_str:N</code> and <code>\tl_to_str:n</code>.</p>
--	---

For the first five conditionals, `\cs_if_exist:cT` turns out to be `false`, and the code boils down to a string comparison between the result of the auxiliary on the `\meaning` of the conditional's argument `####1`, and `#3`. Both are evaluated at run-time, as this is important to get the correct escape character.

The other five conditionals have additional code that compares the argument `####1` to two TeX primitives which would wrongly be recognized as registers otherwise. Despite using TeX's primitive conditional construction, this does not break when `####1` is itself a conditional, because branches of the conditionals are only skipped if `####1` is one of the two primitives that are tested for (which are not TeX conditionals).

```

7465 \group_begin:
7466 \cs_set_protected:Npn \__token_tmp:w #1#2#3
7467 {
7468   \use:x
7469   {
7470     \prg_new_conditional:Npnn \exp_not:c { token_if_ #1 :N } ####1
7471     { p , T , F , TF }
7472     {
7473       \cs_if_exist:cT { tex_ #2 :D }
7474       {
7475         \exp_not:N \if_meaning:w ####1 \exp_not:c { tex_ #2 :D }

```

```

7476         \exp_not:N \prg_return_false:
7477     \exp_not:N \else:
7478     \exp_not:N \if_meaning:w #####1 \exp_not:c { tex_ #2 def:D }
7479     \exp_not:N \prg_return_false:
7480     \exp_not:N \else:
7481     }
7482 \exp_not:N \__str_if_eq_x_return:nn
7483 {
7484     \exp_not:N \exp_after:wN
7485     \exp_not:c { __token_delimit_by_ #2 :w }
7486     \exp_not:N \token_to_meaning:N #####1
7487     ? \tl_to_str:n {#2} \exp_not:N \q_stop
7488 }
7489 { \exp_not:n {#3} }
7490 \cs_if_exist:cT { tex_ #2 :D }
7491 {
7492     \exp_not:N \fi:
7493     \exp_not:N \fi:
7494 }
7495 }
7496 }
7497 }
7498 \__token_tmp:w { chardef } { char" } { \token_to_str:N \char" }
7499 \__token_tmp:w { mathchardef } { char" } { \token_to_str:N \mathchar" }
7500 \__token_tmp:w { long_macro } { macro } { \tl_to_str:n { \long } macro }
7501 \__token_tmp:w { protected_macro } { macro }
7502     { \tl_to_str:n { \protected } macro }
7503 \__token_tmp:w { protected_long_macro } { macro }
7504     { \token_to_str:N \protected \tl_to_str:n { \long } macro }
7505 \__token_tmp:w { dim_register } { dimen } { \token_to_str:N \dimen }
7506 \__token_tmp:w { int_register } { count } { \token_to_str:N \count }
7507 \__token_tmp:w { muskip_register } { muskip } { \token_to_str:N \muskip }
7508 \__token_tmp:w { skip_register } { skip } { \token_to_str:N \skip }
7509 \__token_tmp:w { toks_register } { toks } { \token_to_str:N \toks }
7510 \group_end:

```

(End definition for `\token_if_chardef:NTF` and others. These functions are documented on page 122.)

`\token_if_primitive_p:N`

`\token_if_primitive:NTF`

We filter out macros first, because they cause endless trouble later otherwise.

Primitives are almost distinguished by the fact that the result of `\token_to_meaning:N` is formed from letters only. Every other token has either a space (e.g., the letter A), a digit (e.g., `\count123`) or a double quote (e.g., `\char"A`).

Ten exceptions: on the one hand, `\tex_undefined:D` is not a primitive, but its meaning is undefined, only letters; on the other hand, `\space`, `\italiccorr`, `\hyphen`, `\firstmark`, `\topmark`, `\botmark`, `\splitfirstmark`, `\splitbotmark`, and `\nullfont` are primitives, but have non-letters in their meaning.

We start by removing the two first (non-space) characters from the meaning. This removes the escape character (which may be nonexistent depending on `\endlinechar`), and takes care of three of the exceptions: `\space`, `\italiccorr` and `\hyphen`, whose meaning is at most two characters. This leaves a string terminated by some `:`, and `\q_stop`.

The meaning of each one of the five `\...mark` primitives has the form $\langle letters \rangle : \langle user material \rangle$. In other words, the first non-letter is a colon. We remove everything after the first colon.

We are now left with a string, which we must analyze. For primitives, it contains only letters. For non-primitives, it contains either " , or a space, or a digit. Two exceptions remain: `\tex_undefined:D`, which is not a primitive, and `\nullfont`, which is a primitive.

Spaces cannot be grabbed in an undelimited way, so we check them separately. If there is a space, we test for `\nullfont`. Otherwise, we go through characters one by one, and stop at the first character less than 'A (this is not quite a test for "only letters", but is close enough to work in this context). If this first character is : then we have a primitive, or `\tex_undefined:D`, and if it is " or a digit, then the token is not a primitive.

```

7511 \tex_chardef:D \c__token_A_int = 'A ~ %
7512 \use:x
7513 {
7514   \prg_new_conditional:Npnn \exp_not:N \token_if_primitive:N ##1
7515   { p , T , F , TF }
7516   {
7517     \exp_not:N \token_if_macro:NTF ##1
7518     \exp_not:N \prg_return_false:
7519     {
7520       \exp_not:N \exp_after:wN \exp_not:N \__token_if_primitive:NNw
7521       \exp_not:N \token_to_meaning:N ##1
7522       \tl_to_str:n { : : : } \exp_not:N \q_stop ##1
7523     }
7524   }
7525   \cs_new:Npn \exp_not:N \__token_if_primitive:NNw
7526   ##1##2 ##3 \c_colon_str ##4 \exp_not:N \q_stop
7527   {
7528     \exp_not:N \tl_if_empty:oTF
7529     { \exp_not:N \__token_if_primitive_space:w ##3 ~ }
7530     {
7531       \exp_not:N \__token_if_primitive_loop:N ##3
7532       \c_colon_str \exp_not:N \q_stop
7533     }
7534     { \exp_not:N \__token_if_primitive_nullfont:N }
7535   }
7536 }
7537 \cs_new:Npn \__token_if_primitive_space:w #1 ~ { }
7538 \cs_new:Npn \__token_if_primitive_nullfont:N #1
7539 {
7540   \if_meaning:w \tex_nullfont:D #1
7541   \prg_return_true:
7542   \else:
7543   \prg_return_false:
7544   \fi:
7545 }
7546 \cs_new:Npn \__token_if_primitive_loop:N #1
7547 {
7548   \if_int_compare:w '##1 < \c__token_A_int %
7549   \exp_after:wN \__token_if_primitive:Nw
7550   \exp_after:wN #1
7551   \else:
7552   \exp_after:wN \__token_if_primitive_loop:N
7553   \fi:
7554 }
```

```

7555 \cs_new:Npn \__token_if_primitive:Nw #1 #2 \q_stop
7556 {
7557   \if:w : #1
7558     \exp_after:wN \__token_if_primitive_undefined:N
7559   \else:
7560     \prg_return_false:
7561     \exp_after:wN \use_none:n
7562   \fi:
7563 }
7564 \cs_new:Npn \__token_if_primitive_undefined:N #1
7565 {
7566   \if_cs_exist:N #1
7567     \prg_return_true:
7568   \else:
7569     \prg_return_false:
7570   \fi:
7571 }

```

(End definition for `\token_if_primitive:NTF` and others. This function is documented on page 122.)

14.5 Peeking ahead at the next token

```

7572 <@@=peek>

```

Peeking ahead is implemented using a two part mechanism. The outer level provides a defined interface to the lower level material. This allows a large amount of code to be shared. There are four cases:

1. peek at the next token;
2. peek at the next non-space token;
3. peek at the next token and remove it;
4. peek at the next non-space token and remove it.

`\l_peek_token` Storage tokens which are publicly documented: the token peeked.

`\g_peek_token`

```

7573 \cs_new_eq:NN \l_peek_token ?
7574 \cs_new_eq:NN \g_peek_token ?

```

(End definition for `\l_peek_token` and `\g_peek_token`. These variables are documented on page 123.)

`\l__peek_search_token` The token to search for as an implicit token: cf. `\l__peek_search_tl`.

```

7575 \cs_new_eq:NN \l__peek_search_token ?

```

(End definition for `\l__peek_search_token`.)

`\l__peek_search_tl` The token to search for as an explicit token: cf. `\l__peek_search_token`.

```

7576 \tl_new:N \l__peek_search_tl

```

(End definition for `\l__peek_search_tl`.)

`__peek_true:w` Functions used by the branching and space-stripping code.

```

\__peek_true_aux:w 7577 \cs_new:Npn \__peek_true:w { }
\__peek_false:w    7578 \cs_new:Npn \__peek_true_aux:w { }
\__peek_tmp:w      7579 \cs_new:Npn \__peek_false:w { }
                   7580 \cs_new:Npn \__peek_tmp:w { }

```

(End definition for `_peek_true:w` and others.)

`\peek_after:Nw` Simple wrappers for `\futurelet`: no arguments absorbed here.
`\peek_gafter:Nw`

```
7581 \cs_new_protected:Npn \peek_after:Nw
7582   { \tex_futurelet:D \l_peek_token }
7583 \cs_new_protected:Npn \peek_gafter:Nw
7584   { \tex_global:D \tex_futurelet:D \g_peek_token }
```

(End definition for `\peek_after:Nw` and `\peek_gafter:Nw`. These functions are documented on page 123.)

`_peek_true_remove:w` A function to remove the next token and then regain control.

```
7585 \cs_new_protected:Npn \_peek_true_remove:w
7586   {
7587     \tex_afterassignment:D \_peek_true_aux:w
7588     \cs_set_eq:NN \_peek_tmp:w
7589   }
```

(End definition for `_peek_true_remove:w`.)

`_peek_token_generic_aux:NNNTF` The generic functions store the test token in both implicit and explicit modes, and the `true` and `false` code as token lists, more or less. The two branches have to be absorbed here as the input stream needs to be cleared for the peek function itself. Here, #1 is `_peek_true_remove:w` when removing the token and `_peek_true_aux:w` otherwise.

```
7590 \cs_new_protected:Npn \_peek_token_generic_aux:NNNTF #1#2#3#4#5
7591   {
7592     \group_align_safe_begin:
7593     \cs_set_eq:NN \l_peek_search_token #3
7594     \tl_set:Nn \l_peek_search_tl {#3}
7595     \cs_set:Npx \_peek_true_aux:w
7596       {
7597         \exp_not:N \group_align_safe_end:
7598         \exp_not:n {#4}
7599       }
7600     \cs_set_eq:NN \_peek_true:w #1
7601     \cs_set:Npx \_peek_false:w
7602       {
7603         \exp_not:N \group_align_safe_end:
7604         \exp_not:n {#5}
7605       }
7606     \peek_after:Nw #2
7607   }
```

(End definition for `_peek_token_generic_aux:NNNTF`.)

`_peek_token_generic:NNTF` For token removal there needs to be a call to the auxiliary function which does the work.

```
\_peek_token_remove_generic:NNTF
7608 \cs_new_protected:Npn \_peek_token_generic:NNTF
7609   { \_peek_token_generic_aux:NNNTF \_peek_true_aux:w }
7610 \cs_new_protected:Npn \_peek_token_generic:NNT #1#2#3
7611   { \_peek_token_generic:NNTF #1 #2 {#3} { } }
7612 \cs_new_protected:Npn \_peek_token_generic:NNTF #1#2#3
7613   { \_peek_token_generic:NNTF #1 #2 { } {#3} }
7614 \cs_new_protected:Npn \_peek_token_remove_generic:NNTF
7615   { \_peek_token_generic_aux:NNNTF \_peek_true_remove:w }
```

```

7616 \cs_new_protected:Npn \__peek_token_remove_generic:NNTF #1#2#3
7617 { \__peek_token_remove_generic:NNTF #1 #2 {#3} { } }
7618 \cs_new_protected:Npn \__peek_token_remove_generic:NNF #1#2#3
7619 { \__peek_token_remove_generic:NNTF #1 #2 { } {#3} }

```

(End definition for __peek_token_generic:NNTF and __peek_token_remove_generic:NNTF.)

__peek_execute_branches_meaning: The meaning test is straight forward.

```

7620 \cs_new:Npn \__peek_execute_branches_meaning:
7621 {
7622   \if_meaning:w \l_peek_token \l__peek_search_token
7623   \exp_after:wN \__peek_true:w
7624   \else:
7625     \exp_after:wN \__peek_false:w
7626   \fi:
7627 }

```

(End definition for __peek_execute_branches_meaning:.)

__peek_execute_branches_catcode: The catcode and charcode tests are very similar, and in order to use the same auxiliaries we do something a little bit odd, firing \if_catcode:w and \if_charcode:w before finding the operands for those tests, which are only given in the auxii:N and auxiii: auxiliaries. For our purposes, three kinds of tokens may follow the peeking function:

- control sequences which are not equal to a non-active character token (*e.g.*, macro, primitive);
- active characters which are not equal to a non-active character token (*e.g.*, macro, primitive);
- explicit non-active character tokens, or control sequences or active characters set equal to a non-active character token.

The first two cases are not distinguishable simply using TeX's \futurelet, because we can only access the \meaning of tokens in that way. In those cases, detected thanks to a comparison with \scan_stop:, we grab the following token, and compare it explicitly with the explicit search token stored in \l__peek_search_tl. The \exp_not:N prevents outer macros (coming from non-L^AT_EX3 code) from blowing up. In the third case, \l_peek_token is good enough for the test, and we compare it again with the explicit search token. Just like the peek token, the search token may be of any of the three types above, hence the need to use the explicit token that was given to the peek function.

```

7628 \cs_new:Npn \__peek_execute_branches_catcode:
7629 { \if_catcode:w \__peek_execute_branches_catcode_aux: }
7630 \cs_new:Npn \__peek_execute_branches_charcode:
7631 { \if_charcode:w \__peek_execute_branches_catcode_aux: }
7632 \cs_new:Npn \__peek_execute_branches_catcode_aux:
7633 {
7634   \if_catcode:w \exp_not:N \l_peek_token \scan_stop:
7635   \exp_after:wN \exp_after:wN
7636   \exp_after:wN \__peek_execute_branches_catcode_auxii:N
7637   \exp_after:wN \exp_not:N
7638   \else:
7639     \exp_after:wN \__peek_execute_branches_catcode_auxiii:
7640   \fi:

```

```

7641 }
7642 \cs_new:Npn \__peek_execute_branches_catcode_auxii:N #1
7643 {
7644     \exp_not:N #1
7645     \exp_after:wN \exp_not:N \l__peek_search_tl
7646     \exp_after:wN \__peek_true:w
7647 \else:
7648     \exp_after:wN \__peek_false:w
7649 \fi:
7650 #1
7651 }
7652 \cs_new:Npn \__peek_execute_branches_catcode_auxiii:
7653 {
7654     \exp_not:N \l__peek_token
7655     \exp_after:wN \exp_not:N \l__peek_search_tl
7656     \exp_after:wN \__peek_true:w
7657 \else:
7658     \exp_after:wN \__peek_false:w
7659 \fi:
7660 }

```

(End definition for __peek_execute_branches_catcode: and others.)

__peek_ignore_spaces_execute_branches: This function removes one space token at a time, and calls __peek_execute_branches: when encountering the first non-space token. We directly use the primitive meaning test rather than \token_if_eq_meaning:NNTF because \l__peek_token may be an outer macro (coming from non-L^AT_EX3 packages). Spaces are removed using a side-effect of f-expansion: \exp:w \exp_end_continue_f:w removes one space.

```

7661 \cs_new_protected:Npn \__peek_ignore_spaces_execute_branches:
7662 {
7663     \if_meaning:w \l__peek_token \c_space_token
7664     \exp_after:wN \peek_after:Nw
7665     \exp_after:wN \__peek_ignore_spaces_execute_branches:
7666     \exp:w \exp_end_continue_f:w
7667 \else:
7668     \exp_after:wN \__peek_execute_branches:
7669 \fi:
7670 }

```

(End definition for __peek_ignore_spaces_execute_branches:.)

__peek_def:nnnn The public functions themselves cannot be defined using \prg_new_conditional:Npnn and so a couple of auxiliary functions are used. As a result, everything is done inside a group. As a result things are a bit complicated.

```

7671 \group_begin:
7672 \cs_set:Npn \__peek_def:nnnn #1#2#3#4
7673 {
7674     \__peek_def:nnnnn {#1} {#2} {#3} {#4} { TF }
7675     \__peek_def:nnnnn {#1} {#2} {#3} {#4} { T }
7676     \__peek_def:nnnnn {#1} {#2} {#3} {#4} { F }
7677 }
7678 \cs_set:Npn \__peek_def:nnnnn #1#2#3#4#5
7679 {
7680     \cs_new_protected:cpx { #1 #5 }

```

```

7681     {
7682         \tl_if_empty:nF {#2}
7683         { \exp_not:n { \cs_set_eq:NN \__peek_execute_branches: #2 } }
7684         \exp_not:c { #3 #5 }
7685         \exp_not:n {#4}
7686     }
7687 }

```

(End definition for `__peek_def:nnnn` and `__peek_def:nnnnn`.)

With everything in place the definitions can take place. First for category codes.

```

\peek_catcode:N $\underline{TF}$ 
\peek_catcode_ignore_spaces:N $\underline{TF}$ 
\peek_catcode_remove:N $\underline{TF}$ 
\peek_catcode_remove_ignore_spaces:N $\underline{TF}$ 
7688 \__peek_def:nnnn { peek_catcode:N }
7689 { }
7690 { __peek_token_generic:NN }
7691 { \__peek_execute_branches_catcode: }
7692 \__peek_def:nnnn { peek_catcode_ignore_spaces:N }
7693 { \__peek_execute_branches_catcode: }
7694 { __peek_token_generic:NN }
7695 { \__peek_ignore_spaces_execute_branches: }
7696 \__peek_def:nnnn { peek_catcode_remove:N }
7697 { }
7698 { __peek_token_remove_generic:NN }
7699 { \__peek_execute_branches_catcode: }
7700 \__peek_def:nnnn { peek_catcode_remove_ignore_spaces:N }
7701 { \__peek_execute_branches_catcode: }
7702 { __peek_token_remove_generic:NN }
7703 { \__peek_ignore_spaces_execute_branches: }

```

(End definition for `\peek_catcode:N \underline{TF}` and others. These functions are documented on page 123.)

Then for character codes.

```

\peek_charcode:N $\underline{TF}$ 
\peek_charcode_ignore_spaces:N $\underline{TF}$ 
\peek_charcode_remove:N $\underline{TF}$ 
\peek_charcode_remove_ignore_spaces:N $\underline{TF}$ 
7704 \__peek_def:nnnn { peek_charcode:N }
7705 { }
7706 { __peek_token_generic:NN }
7707 { \__peek_execute_branches_charcode: }
7708 \__peek_def:nnnn { peek_charcode_ignore_spaces:N }
7709 { \__peek_execute_branches_charcode: }
7710 { __peek_token_generic:NN }
7711 { \__peek_ignore_spaces_execute_branches: }
7712 \__peek_def:nnnn { peek_charcode_remove:N }
7713 { }
7714 { __peek_token_remove_generic:NN }
7715 { \__peek_execute_branches_charcode: }
7716 \__peek_def:nnnn { peek_charcode_remove_ignore_spaces:N }
7717 { \__peek_execute_branches_charcode: }
7718 { __peek_token_remove_generic:NN }
7719 { \__peek_ignore_spaces_execute_branches: }

```

(End definition for `\peek_charcode:N \underline{TF}` and others. These functions are documented on page 124.)

Finally for meaning, with the group closed to remove the temporary definition functions.

```

\peek_meaning:N $\underline{TF}$ 
\peek_meaning_ignore_spaces:N $\underline{TF}$ 
\peek_meaning_remove:N $\underline{TF}$ 
\peek_meaning_remove_ignore_spaces:N $\underline{TF}$ 
7720 \__peek_def:nnnn { peek_meaning:N }
7721 { }
7722 { __peek_token_generic:NN }
7723 { \__peek_execute_branches_meaning: }

```

```

7724 \__peek_def:nnnn { peek_meaning_ignore_spaces:N }
7725   { \__peek_execute_branches_meaning: }
7726   { \__peek_token_generic:NN }
7727   { \__peek_ignore_spaces_execute_branches: }
7728 \__peek_def:nnnn { peek_meaning_remove:N }
7729   { }
7730   { \__peek_token_remove_generic:NN }
7731   { \__peek_execute_branches_meaning: }
7732 \__peek_def:nnnn { peek_meaning_remove_ignore_spaces:N }
7733   { \__peek_execute_branches_meaning: }
7734   { \__peek_token_remove_generic:NN }
7735   { \__peek_ignore_spaces_execute_branches: }
7736 \group_end:

```

(End definition for `\peek_meaning:N` and others. These functions are documented on page 124.)

14.6 Decomposing a macro definition

`\token_get_prefix_spec:N` We sometimes want to test if a control sequence can be expanded to reveal a hidden value. However, we cannot just expand the macro blindly as it may have arguments and none might be present. Therefore we define these functions to pick either the prefix(es), the argument specification, or the replacement text from a macro. All of this information is returned as characters with catcode 12. If the token in question isn't a macro, the token `\scan_stop:` is returned instead.

```

7737 \exp_args:Nno \use:nn
7738 { \cs_new:Npn \__peek_get_prefix_arg_replacement:wN #1 }
7739 { \tl_to_str:n { macro : } #2 -> #3 \q_stop #4 }
7740 { #4 {#1} {#2} {#3} }
7741 \cs_new:Npn \token_get_prefix_spec:N #1
7742 {
7743   \token_if_macro:NTF #1
7744   {
7745     \exp_after:wN \__peek_get_prefix_arg_replacement:wN
7746     \token_to_meaning:N #1 \q_stop \use_i:nnn
7747   }
7748   { \scan_stop: }
7749 }
7750 \cs_new:Npn \token_get_arg_spec:N #1
7751 {
7752   \token_if_macro:NTF #1
7753   {
7754     \exp_after:wN \__peek_get_prefix_arg_replacement:wN
7755     \token_to_meaning:N #1 \q_stop \use_ii:nnn
7756   }
7757   { \scan_stop: }
7758 }
7759 \cs_new:Npn \token_get_replacement_spec:N #1
7760 {
7761   \token_if_macro:NTF #1
7762   {
7763     \exp_after:wN \__peek_get_prefix_arg_replacement:wN
7764     \token_to_meaning:N #1 \q_stop \use_iii:nnn
7765   }
7766   { \scan_stop: }

```

7767 }

(End definition for `\token_get_prefix_spec:N` and others. These functions are documented on page 126.)

14.7 Deprecated functions

`\token_new:Nn` For removal after 2018-12-31.

7768 `__debug_deprecation:nnNNpn { 2018-12-31 } { \cs_new_eq:NN }`
 7769 `\cs_new_protected:Npn \token_new:Nn #1#2 { \cs_new_eq:NN #1 #2 }`

(End definition for `\token_new:Nn`.)

7770 `\</initex | package>`

15 l3prop implementation

The following test files are used for this code: `m3prop001`, `m3prop002`, `m3prop003`, `m3prop004`, `m3show001`.

7771 `\<*initex | package>`

7772 `\<@@=prop>`

A property list is a macro whose top-level expansion is of the form

`\s__prop __prop_pair:wn <key1> \s__prop {<value1>}`
`...`
`__prop_pair:wn <keyn> \s__prop {<valuen>}`

where `\s__prop` is a scan mark (equal to `\scan_stop:`), and `__prop_pair:wn` can be used to map through the property list.

`\s__prop` A private scan mark is used as a marker after each key, and at the very beginning of the property list.

7773 `__scan_new:N \s__prop`

(End definition for `\s__prop`.)

`__prop_pair:wn` The delimiter is always defined, but when misused simply triggers an error and removes its argument.

7774 `\cs_new:Npn __prop_pair:wn #1 \s__prop #2`
 7775 `{ __msg_kernel_expandable_error:nn { kernel } { misused-prop } }`

(End definition for `__prop_pair:wn`.)

`\l__prop_internal_tl` Token list used to store the new key–value pair inserted by `\prop_put:Nnn` and friends.

7776 `\tl_new:N \l__prop_internal_tl`

(End definition for `\l__prop_internal_tl`.)

`\c_empty_prop` An empty prop.

7777 `\tl_const:Nn \c_empty_prop { \s__prop }`

(End definition for `\c_empty_prop`. This variable is documented on page 134.)

15.1 Allocation and initialisation

\prop_new:N Property lists are initialized with the value `\c_empty_prop`.

```
\prop_new:c 7778 \cs_new_protected:Npn \prop_new:N #1
              7779 {
              7780   \__chk_if_free_cs:N #1
              7781   \cs_gset_eq:NN #1 \c_empty_prop
              7782 }
              7783 \cs_generate_variant:Nn \prop_new:N { c }
```

(End definition for `\prop_new:N`. This function is documented on page 129.)

\prop_clear:N The same idea for clearing.

```
\prop_clear:c 7784 \cs_new_protected:Npn \prop_clear:N #1
\prop_gclear:N 7785 { \prop_set_eq:NN #1 \c_empty_prop }
\prop_gclear:c 7786 \cs_generate_variant:Nn \prop_clear:N { c }
              7787 \cs_new_protected:Npn \prop_gclear:N #1
              7788 { \prop_gset_eq:NN #1 \c_empty_prop }
              7789 \cs_generate_variant:Nn \prop_gclear:N { c }
```

(End definition for `\prop_clear:N` and `\prop_gclear:N`. These functions are documented on page 129.)

\prop_clear_new:N Once again a simple variation of the token list functions.

```
\prop_clear_new:c 7790 \cs_new_protected:Npn \prop_clear_new:N #1
\prop_gclear_new:N 7791 { \prop_if_exist:NTF #1 { \prop_clear:N #1 } { \prop_new:N #1 } }
\prop_gclear_new:c 7792 \cs_generate_variant:Nn \prop_clear_new:N { c }
              7793 \cs_new_protected:Npn \prop_gclear_new:N #1
              7794 { \prop_if_exist:NTF #1 { \prop_gclear:N #1 } { \prop_new:N #1 } }
              7795 \cs_generate_variant:Nn \prop_gclear_new:N { c }
```

(End definition for `\prop_clear_new:N` and `\prop_gclear_new:N`. These functions are documented on page 129.)

\prop_set_eq:NN These are simply copies from the token list functions.

```
\prop_set_eq:cN 7796 \cs_new_eq:NN \prop_set_eq:NN \tl_set_eq:NN
\prop_set_eq:Nc 7797 \cs_new_eq:NN \prop_set_eq:Nc \tl_set_eq:Nc
\prop_set_eq:cc 7798 \cs_new_eq:NN \prop_set_eq:cN \tl_set_eq:cN
\prop_gset_eq:NN 7799 \cs_new_eq:NN \prop_set_eq:cc \tl_set_eq:cc
\prop_gset_eq:cN 7800 \cs_new_eq:NN \prop_gset_eq:NN \tl_gset_eq:NN
\prop_gset_eq:Nc 7801 \cs_new_eq:NN \prop_gset_eq:Nc \tl_gset_eq:Nc
\prop_gset_eq:cN 7802 \cs_new_eq:NN \prop_gset_eq:cN \tl_gset_eq:cN
\prop_gset_eq:cc 7803 \cs_new_eq:NN \prop_gset_eq:cc \tl_gset_eq:cc
```

(End definition for `\prop_set_eq:NN` and `\prop_gset_eq:NN`. These functions are documented on page 129.)

\l_tmpa_prop We can now initialize the scratch variables.

```
\l_tmpb_prop 7804 \prop_new:N \l_tmpa_prop
\g_tmpa_prop 7805 \prop_new:N \l_tmpb_prop
\g_tmpb_prop 7806 \prop_new:N \g_tmpa_prop
              7807 \prop_new:N \g_tmpb_prop
```

(End definition for `\l_tmpa_prop` and others. These variables are documented on page 134.)

<pre> \prop_set_from_keyval:Nn \prop_set_from_keyval:cn \prop_gset_from_keyval:Nn \prop_gset_from_keyval:cn \prop_const_from_keyval:Nn \prop_const_from_keyval:cn __prop_from_keyval:n __prop_from_keyval_loop:w __prop_from_keyval_split:Nw __prop_from_keyval_key:w __prop_from_keyval_value:w </pre>	<p>Loop through items separated by commas, with \q_mark to avoid losing braces. After checking for termination, split the item at the first then at the second = (which ought to be the first of the trailing =). At both splits, trim spaces (the internal __tl_trim_spaces:nn expects the \q_mark we give it) and call __prop_from_keyval_key:w, then __prop_from_keyval_value:w, followed by the trimmed material, \q_nil, the subsequent part of the item, and the trailing ='s and \q_stop. After finding the <key> just store it after \q_stop. After finding the <value> ignore completely empty items (both trailing = were used as delimiters and all parts are empty); if the remaining part #2 consists exactly of the second trailing = (namely there was exactly one = in the item) then output one key–value pair for the property list; otherwise complain about a missing or extra =.</p>
--	--

```

7808 \cs_new_protected:Npn \prop_set_from_keyval:Nn #1#2
7809   { \tl_set:Nx #1 { \__prop_from_keyval:n {#2} } }
7810 \cs_generate_variant:Nn \prop_set_from_keyval:Nn { c }
7811 \cs_new_protected:Npn \prop_gset_from_keyval:Nn #1#2
7812   { \tl_gset:Nx #1 { \__prop_from_keyval:n {#2} } }
7813 \cs_generate_variant:Nn \prop_gset_from_keyval:Nn { c }
7814 \cs_new_protected:Npn \prop_const_from_keyval:Nn #1#2
7815   { \tl_const:Nx #1 { \__prop_from_keyval:n {#2} } }
7816 \cs_generate_variant:Nn \prop_const_from_keyval:Nn { c }
7817 \cs_new:Npn \__prop_from_keyval:n #1
7818   {
7819     \s__prop
7820     \__prop_from_keyval_loop:w \q_mark #1 ,
7821     \q_recursion_tail , \q_recursion_stop
7822   }
7823 \cs_new:Npn \__prop_from_keyval_loop:w #1 ,
7824   {
7825     \quark_if_recursion_tail_stop:o { \use_none:n #1 }
7826     \__prop_from_keyval_split:Nw \__prop_from_keyval_key:w
7827     #1 = = \q_stop { \use_none:n #1 }
7828     \__prop_from_keyval_loop:w \q_mark
7829   }
7830 \cs_new:Npn \__prop_from_keyval_split:Nw #1#2 =
7831   {
7832     \__tl_trim_spaces:nn {#2}
7833     { \exp_last_unbraced:No #1 } \q_nil
7834   }
7835 \cs_new:Npn \__prop_from_keyval_key:w #1 \q_nil #2 \q_stop
7836   {
7837     \__prop_from_keyval_split:Nw \__prop_from_keyval_value:w
7838     \q_mark #2 \q_stop {#1}
7839   }
7840 \cs_new:Npn \__prop_from_keyval_value:w #1 \q_nil #2 \q_stop #3#4
7841   {
7842     \tl_if_empty:nF { #3 #1 #2 }
7843     {
7844       \str_if_eq:nnTF {#2} { = }
7845       {
7846         \exp_not:N \__prop_pair:wn \tl_to_str:n {#3}
7847         \s__prop { \exp_not:n {#1} }
7848       }
7849     }

```

```

7850         \exp_args:Nnno \_msg_kernel_expandable_error:nnn
7851         { kernel } { prop-keyval } {#4}
7852     }
7853 }
7854 }

```

(End definition for `\prop_set_from_keyval:Nn` and others. These functions are documented on page 244.)

15.2 Accessing data in property lists

`__prop_split:NnTF` This function is used by most of the module, and hence must be fast. It receives a *property list*, a *key*, a *true code* and a *false code*. The aim is to split the *property list* at the given *key* into the *extract₁* before the key–value pair, the *value* associated with the *key* and the *extract₂* after the key–value pair. This is done using a delimited function, whose definition is as follows, where the *key* is turned into a string.

```

\cs_set:Npn \__prop_split_aux:w #1
\__prop_pair:wn <key> \s__prop #2
#3 \q_mark #4 #5 \q_stop
{ #4 {<true code>} {<false code>} }

```

If the *key* is present in the property list, `__prop_split_aux:w`'s #1 is the part before the *key*, #2 is the *value*, #3 is the part after the *key*, #4 is `\use_i:nn`, and #5 is additional tokens that we do not care about. The *true code* is left in the input stream, and can use the parameters #1, #2, #3 for the three parts of the property list as desired. Namely, the original property list is in this case #1 `__prop_pair:wn <key> \s__prop {#2} #3`.

If the *key* is not there, then the *function* is `\use_ii:nn`, which keeps the *false code*.

```

7855 \cs_new_protected:Npn \__prop_split:NnTF #1#2
7856 { \exp_args:Nno \__prop_split_aux:NnTF #1 { \tl_to_str:n {#2} } }
7857 \cs_new_protected:Npn \__prop_split_aux:NnTF #1#2#3#4
7858 {
7859   \cs_set:Npn \__prop_split_aux:w ##1
7860     \__prop_pair:wn #2 \s__prop ##2 ##3 \q_mark ##4 ##5 \q_stop
7861     { ##4 {#3} {#4} }
7862   \exp_after:wN \__prop_split_aux:w #1 \q_mark \use_i:nn
7863   \__prop_pair:wn #2 \s__prop { } \q_mark \use_ii:nn \q_stop
7864 }
7865 \cs_new:Npn \__prop_split_aux:w { }

```

(End definition for `__prop_split:NnTF`, `__prop_split_aux:NnTF`, and `__prop_split_aux:w`.)

`\prop_remove:Nn` Deleting from a property starts by splitting the list. If the key is present in the property list, the returned value is ignored. If the key is missing, nothing happens.

```

\prop_remove:NV
\prop_remove:cn
\prop_remove:cV
\prop_gremove:Nn
\prop_gremove:NV
\prop_gremove:cn
\prop_gremove:cV
7866 \cs_new_protected:Npn \prop_remove:Nn #1#2
7867 {
7868   \__prop_split:NnTF #1 {#2}
7869   { \tl_set:Nn #1 { ##1 ##3 } }
7870   { }
7871 }
7872 \cs_new_protected:Npn \prop_gremove:Nn #1#2

```

```

7873 {
7874   \__prop_split:NnTF #1 {#2}
7875   { \tl_gset:Nn #1 { ##1 ##3 } }
7876   { }
7877 }
7878 \cs_generate_variant:Nn \prop_remove:Nn { NV }
7879 \cs_generate_variant:Nn \prop_remove:Nn { c , cV }
7880 \cs_generate_variant:Nn \prop_gremove:Nn { NV }
7881 \cs_generate_variant:Nn \prop_gremove:Nn { c , cV }

```

(End definition for `\prop_remove:Nn` and `\prop_gremove:Nn`. These functions are documented on page 131.)

`\prop_get:NnN` Getting an item from a list is very easy: after splitting, if the key is in the property list, just set the token list variable to the return value, otherwise to `\q_no_value`.

```

\prop_get:NVN 7882 \cs_new_protected:Npn \prop_get:NnN #1#2#3
\prop_get:NoN 7883 {
\prop_get:cnN 7884   \__prop_split:NnTF #1 {#2}
\prop_get:cVN 7885   { \tl_set:Nn #3 {##2} }
\prop_get:coN 7886   { \tl_set:Nn #3 { \q_no_value } }
7887 }
7888 \cs_generate_variant:Nn \prop_get:NnN { NV , No }
7889 \cs_generate_variant:Nn \prop_get:NnN { c , cV , co }

```

(End definition for `\prop_get:NnN`. This function is documented on page 130.)

`\prop_pop:NnN` Popping a value also starts by doing the split. If the key is present, save the value in the token list and update the property list as when deleting. If the key is missing, save `\q_no_value` in the token list.

```

\prop_pop:NoN 7890 \cs_new_protected:Npn \prop_pop:NnN #1#2#3
\prop_pop:cnN 7891 {
\prop_gpop:NnN 7892   \__prop_split:NnTF #1 {#2}
\prop_gpop:NoN 7893   {
\prop_gpop:cnN 7894     \tl_set:Nn #3 {##2}
7895     \tl_set:Nn #1 { ##1 ##3 }
7896   }
7897   { \tl_set:Nn #3 { \q_no_value } }
7898 }
7899 \cs_new_protected:Npn \prop_gpop:NnN #1#2#3
7900 {
7901   \__prop_split:NnTF #1 {#2}
7902   {
7903     \tl_set:Nn #3 {##2}
7904     \tl_gset:Nn #1 { ##1 ##3 }
7905   }
7906   { \tl_set:Nn #3 { \q_no_value } }
7907 }
7908 \cs_generate_variant:Nn \prop_pop:NnN { No }
7909 \cs_generate_variant:Nn \prop_pop:NnN { c , co }
7910 \cs_generate_variant:Nn \prop_gpop:NnN { No }
7911 \cs_generate_variant:Nn \prop_gpop:NnN { c , co }

```

(End definition for `\prop_pop:NnN` and `\prop_gpop:NnN`. These functions are documented on page 130.)

\prop_item:Nn Getting the value corresponding to a key in a property list in an expandable fashion is similar to mapping some tokens. Go through the property list one $\langle key \rangle$ – $\langle value \rangle$ pair at a time: the arguments of **__prop_item_Nn:nwn** are the $\langle key \rangle$ we are looking for, a $\langle key \rangle$ of the property list, and its associated value. The $\langle keys \rangle$ are compared (as strings). If they match, the $\langle value \rangle$ is returned, within **\exp_not:n**. The loop terminates even if the $\langle key \rangle$ is missing, and yields an empty value, because we have appended the appropriate $\langle key \rangle$ – $\langle empty\ value \rangle$ pair to the property list.

```

7912 \cs_new:Npn \prop_item:Nn #1#2
7913 {
7914   \exp_last_unbraced:Noo \__prop_item_Nn:nwn { \tl_to_str:n {#2} } #1
7915   \__prop_pair:wn \tl_to_str:n {#2} \s__prop { }
7916   \__prg_break_point:
7917 }
7918 \cs_new:Npn \__prop_item_Nn:nwn #1#2 \__prop_pair:wn #3 \s__prop #4
7919 {
7920   \str_if_eq_x:nnTF {#1} {#3}
7921   { \__prg_break:n { \exp_not:n {#4} } }
7922   { \__prop_item_Nn:nwn {#1} }
7923 }
7924 \cs_generate_variant:Nn \prop_item:Nn { c }

```

(End definition for **\prop_item:Nn** and **__prop_item_Nn:nwn**. This function is documented on page 131.)

\prop_pop:NnNTF Popping an item from a property list, keeping track of whether the key was present or not, is implemented as a conditional. If the key was missing, neither the property list, nor the token list are altered. Otherwise, **\prg_return_true:** is used after the assignments.

\prop_gpop:NnNTF

\prop_gpop:cnNTF

```

7925 \prg_new_protected_conditional:Npnn \prop_pop:NnN #1#2#3 { T , F , TF }
7926 {
7927   \__prop_split:NnTF #1 {#2}
7928   {
7929     \tl_set:Nn #3 {##2}
7930     \tl_set:Nn #1 { ##1 ##3 }
7931     \prg_return_true:
7932   }
7933   { \prg_return_false: }
7934 }
7935 \prg_new_protected_conditional:Npnn \prop_gpop:NnN #1#2#3 { T , F , TF }
7936 {
7937   \__prop_split:NnTF #1 {#2}
7938   {
7939     \tl_set:Nn #3 {##2}
7940     \tl_gset:Nn #1 { ##1 ##3 }
7941     \prg_return_true:
7942   }
7943   { \prg_return_false: }
7944 }
7945 \cs_generate_variant:Nn \prop_pop:NnNT { c }
7946 \cs_generate_variant:Nn \prop_pop:NnNF { c }
7947 \cs_generate_variant:Nn \prop_pop:NnNTF { c }
7948 \cs_generate_variant:Nn \prop_gpop:NnNT { c }
7949 \cs_generate_variant:Nn \prop_gpop:NnNF { c }
7950 \cs_generate_variant:Nn \prop_gpop:NnNTF { c }

```

(End definition for `\prop_pop:NnNTF` and `\prop_gpop:NnNTF`. These functions are documented on page 132.)

`\prop_put:Nnn` Since the branches of `__prop_split:NnTF` are used as the replacement text of an internal macro, and since the $\langle key \rangle$ and new $\langle value \rangle$ may contain arbitrary tokens, it is not safe to include them in the argument of `__prop_split:NnTF`. We thus start by storing in `\l__prop_internal_tl` tokens which (after x-expansion) encode the key–value pair. This variable can safely be used in `__prop_split:NnTF`. If the $\langle key \rangle$ was absent, append the new key–value to the list. Otherwise concatenate the extracts `##1` and `##3` with the new key–value pair `\l__prop_internal_tl`. The updated entry is placed at the same spot as the original $\langle key \rangle$ in the property list, preserving the order of entries.

```

7951 \cs_new_protected:Npn \prop_put:Nnn { \__prop_put:NNnn \tl_set:Nx }
7952 \cs_new_protected:Npn \prop_gput:Nnn { \__prop_put:NNnn \tl_gset:Nx }
7953 \cs_new_protected:Npn \__prop_put:NNnn #1#2#3#4
7954 {
7955   \tl_set:Nn \l__prop_internal_tl
7956   {
7957     \exp_not:N \__prop_pair:wn \tl_to_str:n {#3}
7958     \s__prop { \exp_not:n {#4} }
7959   }
7960   \__prop_split:NnTF #2 {#3}
7961   { #1 #2 { \exp_not:n {##1} \l__prop_internal_tl \exp_not:n {##3} } }
7962   { #1 #2 { \exp_not:o {#2} \l__prop_internal_tl } }
7963 }
7964 \cs_generate_variant:Nn \prop_put:Nnn
7965 { NnV , Nno , Nnx , NV , NVV , No , Noo }
7966 \cs_generate_variant:Nn \prop_put:Nnn
7967 { c , cnV , cno , cnx , cV , cVV , co , coo }
7968 \cs_generate_variant:Nn \prop_gput:Nnn
7969 { NnV , Nno , Nnx , NV , NVV , No , Noo }
7970 \cs_generate_variant:Nn \prop_gput:Nnn
7971 { c , cnV , cno , cnx , cV , cVV , co , coo }

```

(End definition for `\prop_put:Nnn`, `\prop_gput:Nnn`, and `__prop_put:NNnn`. These functions are documented on page 130.)

`\prop_put_if_new:Nnn` Adding conditionally also splits. If the key is already present, the three brace groups given by `__prop_split:NnTF` are removed. If the key is new, then the value is added, being careful to convert the key to a string using `\tl_to_str:n`.

```

7972 \cs_new_protected:Npn \prop_put_if_new:Nnn
7973 { \__prop_put_if_new:NNnn \tl_set:Nx }
7974 \cs_new_protected:Npn \prop_gput_if_new:Nnn
7975 { \__prop_put_if_new:NNnn \tl_gset:Nx }
7976 \cs_new_protected:Npn \__prop_put_if_new:NNnn #1#2#3#4
7977 {
7978   \tl_set:Nn \l__prop_internal_tl
7979   {
7980     \exp_not:N \__prop_pair:wn \tl_to_str:n {#3}
7981     \s__prop \exp_not:n {#4} }
7982 }
7983 \__prop_split:NnTF #2 {#3}
7984 { }
7985 { #1 #2 { \exp_not:o {#2} \l__prop_internal_tl } }
7986 }

```

```

7987 \cs_generate_variant:Nn \prop_put_if_new:Nnn { c }
7988 \cs_generate_variant:Nn \prop_gput_if_new:Nnn { c }

```

(End definition for `\prop_put_if_new:Nnn`, `\prop_gput_if_new:Nnn`, and `__prop_put_if_new:Nnn`. These functions are documented on page 130.)

15.3 Property list conditionals

```

\prop_if_exist_p:N
\prop_if_exist_p:c
\prop_if_exist:NTF
\prop_if_exist:cTF

```

Copies of the `cs` functions defined in `l3basics`.

```

7989 \prg_new_eq_conditional:Nnn \prop_if_exist:N \cs_if_exist:N
7990 { TF , T , F , p }
7991 \prg_new_eq_conditional:Nnn \prop_if_exist:c \cs_if_exist:c
7992 { TF , T , F , p }

```

(End definition for `\prop_if_exist:NTF`. This function is documented on page 131.)

```

\prop_if_empty_p:N
\prop_if_empty_p:c
\prop_if_empty:NTF
\prop_if_empty:cTF

```

Same test as for token lists.

```

7993 \prg_new_conditional:Npnn \prop_if_empty:N #1 { p , T , F , TF }
7994 {
7995   \tl_if_eq:NNTF #1 \c_empty_prop
7996   \prg_return_true: \prg_return_false:
7997 }
7998 \cs_generate_variant:Nn \prop_if_empty_p:N { c }
7999 \cs_generate_variant:Nn \prop_if_empty:NT { c }
8000 \cs_generate_variant:Nn \prop_if_empty:NF { c }
8001 \cs_generate_variant:Nn \prop_if_empty:NTF { c }

```

(End definition for `\prop_if_empty:NTF`. This function is documented on page 131.)

```

\prop_if_in_p:Nn
\prop_if_in_p:Nv
\prop_if_in_p:No
\prop_if_in_p:cn
\prop_if_in_p:cV
\prop_if_in_p:co
\prop_if_in:NnNTF
\prop_if_in:NvNTF
\prop_if_in:NoTF
\prop_if_in:cnTF
\prop_if_in:cVTF
\prop_if_in:coTF
\__prop_if_in:nwnn
\__prop_if_in:N

```

Testing expandably if a key is in a property list requires to go through the key–value pairs one by one. This is rather slow, and a faster test would be

```

\prg_new_protected_conditional:Npnn \prop_if_in:Nn #1 #2
{
  \@@_split:NnTF #1 {#2}
  { \prg_return_true: }
  { \prg_return_false: }
}

```

but `__prop_split:NnTF` is non-expandable.

Instead, the key is compared to each key in turn using `\str_if_eq_x:nn`, which is expandable. To terminate the mapping, we append to the property list the key that is searched for. This second `\tl_to_str:n` is not expanded at the start, but only when included in the `\str_if_eq_x:nn`. It cannot make the breaking mechanism choke, because the arbitrary token list material is enclosed in braces. The second argument of `__prop_if_in:nwnn` is most often empty. When the *key* is found in the list, `__prop_if_in:N` receives `__prop_pair:wn`, and if it is found as the extra item, the function receives `\q_recursion_tail`, easily recognizable.

Here, `\prop_map_function:NN` is not sufficient for the mapping, since it can only map a single token, and cannot carry the key that is searched for.

```

8002 \prg_new_conditional:Npnn \prop_if_in:Nn #1#2 { p , T , F , TF }
8003 {
8004   \exp_last_unbraced:Noo \__prop_if_in:nwnn { \tl_to_str:n {#2} } #1
8005   \__prop_pair:wn \tl_to_str:n {#2} \s_prop { }

```

```

8006     \q_recursion_tail
8007     \__prg_break_point:
8008   }
8009 \cs_new:Npn \__prop_if_in:nwwn #1#2 \__prop_pair:wn #3 \s__prop #4
8010 {
8011   \str_if_eq_x:nnTF {#1} {#3}
8012   { \__prop_if_in:N }
8013   { \__prop_if_in:nwwn {#1} }
8014 }
8015 \cs_new:Npn \__prop_if_in:N #1
8016 {
8017   \if_meaning:w \q_recursion_tail #1
8018   \prg_return_false:
8019   \else:
8020     \prg_return_true:
8021   \fi:
8022   \__prg_break:
8023 }
8024 \cs_generate_variant:Nn \prop_if_in_p:Nn { NV , No }
8025 \cs_generate_variant:Nn \prop_if_in_p:Nn { c , cV , co }
8026 \cs_generate_variant:Nn \prop_if_in:NnT { NV , No }
8027 \cs_generate_variant:Nn \prop_if_in:NnT { c , cV , co }
8028 \cs_generate_variant:Nn \prop_if_in:NnF { NV , No }
8029 \cs_generate_variant:Nn \prop_if_in:NnF { c , cV , co }
8030 \cs_generate_variant:Nn \prop_if_in:NnTF { NV , No }
8031 \cs_generate_variant:Nn \prop_if_in:NnTF { c , cV , co }

```

(End definition for `\prop_if_in:NnTF`, `__prop_if_in:nwwn`, and `__prop_if_in:N`. This function is documented on page [131](#).)

15.4 Recovering values from property lists with branching

`\prop_get:NnTF` Getting the value corresponding to a key, keeping track of whether the key was present or not, is implemented as a conditional (with side effects). If the key was absent, the token list is not altered.

```

\prop_get:NnTF
\prop_get:NvNTF
\prop_get:NnNTF
\prop_get:cnNTF
\prop_get:cVNTF
\prop_get:coNTF
8032 \prg_new_protected_conditional:Npnn \prop_get:NnN #1#2#3 { T , F , TF }
8033 {
8034   \__prop_split:NnTF #1 {#2}
8035   {
8036     \tl_set:Nn #3 {##2}
8037     \prg_return_true:
8038   }
8039   { \prg_return_false: }
8040 }
8041 \cs_generate_variant:Nn \prop_get:NnNT { NV , No }
8042 \cs_generate_variant:Nn \prop_get:NnNF { NV , No }
8043 \cs_generate_variant:Nn \prop_get:NnNTF { NV , No }
8044 \cs_generate_variant:Nn \prop_get:NnNT { c , cV , co }
8045 \cs_generate_variant:Nn \prop_get:NnNF { c , cV , co }
8046 \cs_generate_variant:Nn \prop_get:NnNTF { c , cV , co }

```

(End definition for `\prop_get:NnNTF`. This function is documented on page [132](#).)

15.5 Mapping to property lists

`\prop_map_function:NN` The fastest way to do a recursion here is to use an `\if_meaning:w` test: the keys are strings, and thus cannot match the marker `\q_recursion_tail`. A special case to note is when the key #3 is empty: then `\q_recursion_tail` is compared to `\exp_after:wN`, also different. Note that #2 is empty, except at the first iteration, where it is `\s__prop`.

`\prop_map_function:Nc`

`\prop_map_function:cN`

`\prop_map_function:cc`

`__prop_map_function:Nwwn`

```

8047 \cs_new:Npn \prop_map_function:NN #1#2
8048 {
8049   \exp_last_unbraced:NNo \__prop_map_function:Nwwn #2 #1
8050   \__prop_pair:wn \q_recursion_tail \s__prop { }
8051   \__prg_break_point:Nn \prop_map_break: { }
8052 }
8053 \cs_new:Npn \__prop_map_function:Nwwn #1#2 \__prop_pair:wn #3 \s__prop #4
8054 {
8055   \if_meaning:w \q_recursion_tail #3
8056   \exp_after:wN \prop_map_break:
8057   \fi:
8058   #1 {#3} {#4}
8059   \__prop_map_function:Nwwn #1
8060 }
8061 \cs_generate_variant:Nn \prop_map_function:NN { Nc }
8062 \cs_generate_variant:Nn \prop_map_function:NN { c , cc }

```

(End definition for `\prop_map_function:NN` and `__prop_map_function:Nwwn`. This function is documented on page 132.)

`\prop_map_inline:Nn` Mapping in line requires a nesting level counter. Store the current definition of `__prop_pair:wn`, and define it anew. At the end of the loop, revert to the earlier definition. Note that besides pairs of the form `__prop_pair:wn <key> \s__prop {<value>}`, there are a leading and a trailing tokens, but both are equal to `\scan_stop:`, hence have no effect in such inline mapping. Such `\scan_stop:` could have affected ligatures if they appeared during the mapping.

`\prop_map_inline:cn`

```

8063 \cs_new_protected:Npn \prop_map_inline:Nn #1#2
8064 {
8065   \cs_gset_eq:cN
8066   { \__prg_map_ \int_use:N \g__prg_map_int :wn } \__prop_pair:wn
8067   \int_gincr:N \g__prg_map_int
8068   \cs_gset_protected:Npn \__prop_pair:wn ##1 \s__prop ##2 {#2}
8069   #1
8070   \__prg_break_point:Nn \prop_map_break:
8071   {
8072     \int_gdecr:N \g__prg_map_int
8073     \cs_gset_eq:Nc \__prop_pair:wn
8074     { \__prg_map_ \int_use:N \g__prg_map_int :wn }
8075   }
8076 }
8077 \cs_generate_variant:Nn \prop_map_inline:Nn { c }

```

(End definition for `\prop_map_inline:Nn`. This function is documented on page 132.)

`\prop_map_break:` The break statements are based on the general `__prg_map_break:Nn`.

`\prop_map_break:n`

```

8078 \cs_new:Npn \prop_map_break:
8079 { \__prg_map_break:Nn \prop_map_break: { } }
8080 \cs_new:Npn \prop_map_break:n
8081 { \__prg_map_break:Nn \prop_map_break: }

```

(End definition for `\prop_map_break:` and `\prop_map_break:n`. These functions are documented on page 133.)

15.6 Viewing property lists

`\prop_show:N` Apply the general `__kernel_check_defined:NT` and `\msg_show:nnnnnn`. Contrarily to sequences and comma lists, we use `\msg_show_item:nn` to format both the key and the value for each pair.

```
\prop_show:c
\prop_log:N
\prop_log:c
8082 \cs_new_protected:Npn \prop_show:N { \__prop_show:NN \msg_show:nnxxxx }
8083 \cs_generate_variant:Nn \prop_show:N { c }
8084 \cs_new_protected:Npn \prop_log:N { \__prop_show:NN \msg_log:nnxxxx }
8085 \cs_generate_variant:Nn \prop_log:N { c }
8086 \cs_new_protected:Npn \__prop_show:NN #1#2
8087 {
8088   \__kernel_check_defined:NT #2
8089   {
8090     #1 { LaTeX/kernel } { show-prop }
8091     { \token_to_str:N #2 }
8092     { \prop_map_function:NN #2 \msg_show_item:nn }
8093     { } { }
8094   }
8095 }
```

(End definition for `\prop_show:N` and `\prop_log:N`. These functions are documented on page 133.)

```
8096 </initex | package>
```

16 l3msg implementation

```
8097 <*initex | package>
```

```
8098 <@@=msg>
```

`\l_msg_internal_tl` A general scratch for the module.

```
8099 \tl_new:N \l_msg_internal_tl
```

(End definition for `\l_msg_internal_tl`.)

`\l_msg_line_context_bool` Controls whether the line context is shown as part of the decoration of all (non-expandable) messages.

```
8100 \bool_new:N \l_msg_line_context_bool
```

(End definition for `\l_msg_line_context_bool`.)

16.1 Creating messages

Messages are created and used separately, so there two parts to the code here. First, a mechanism for creating message text. This is pretty simple, as there is not actually a lot to do.

`\c_msg_text_prefix_tl` Locations for the text of messages.

```
\c_msg_more_text_prefix_tl
8101 \tl_const:Nn \c_msg_text_prefix_tl { msg~text~>~ }
8102 \tl_const:Nn \c_msg_more_text_prefix_tl { msg~extra~text~>~ }
```

(End definition for `\c_msg_text_prefix_tl` and `\c_msg_more_text_prefix_tl`.)

\msg_if_exist_p:nn Test whether the control sequence containing the message text exists or not.
\msg_if_exist:nnTF

```

8103 \prg_new_conditional:Npnn \msg_if_exist:nn #1#2 { p , T , F , TF }
8104 {
8105     \cs_if_exist:cTF { \c__msg_text_prefix_tl #1 / #2 }
8106     { \prg_return_true: } { \prg_return_false: }
8107 }

```

(End definition for \msg_if_exist:nnTF. This function is documented on page 137.)

__chk_if_free_msg:nn This auxiliary is similar to __chk_if_free_cs:N, and is used when defining messages with \msg_new:nnnn.

```

8108 \__debug_patch:nnNNpn { }
8109 { \__debug_log:x { Defining~message~ #1 / #2 ~\msg_line_context: } }
8110 \cs_new_protected:Npn \__chk_if_free_msg:nn #1#2
8111 {
8112     \msg_if_exist:nnT {#1} {#2}
8113     {
8114         \__msg_kernel_error:nxxx { kernel } { message-already-defined }
8115         {#1} {#2}
8116     }
8117 }

```

(End definition for __chk_if_free_msg:nn.)

\msg_new:nnnn Setting a message simply means saving the appropriate text into two functions. A sanity check first.

```

8118 \cs_new_protected:Npn \msg_new:nnnn #1#2
8119 {
8120     \__chk_if_free_msg:nn {#1} {#2}
8121     \msg_gset:nnnn {#1} {#2}
8122 }
8123 \cs_new_protected:Npn \msg_new:nnn #1#2#3
8124 { \msg_new:nnnn {#1} {#2} {#3} { } }
8125 \cs_new_protected:Npn \msg_set:nnnn #1#2#3#4
8126 {
8127     \cs_set:cpn { \c__msg_text_prefix_tl #1 / #2 }
8128     ##1##2##3##4 {#3}
8129     \cs_set:cpn { \c__msg_more_text_prefix_tl #1 / #2 }
8130     ##1##2##3##4 {#4}
8131 }
8132 \cs_new_protected:Npn \msg_set:nnn #1#2#3
8133 { \msg_set:nnnn {#1} {#2} {#3} { } }
8134 \cs_new_protected:Npn \msg_gset:nnnn #1#2#3#4
8135 {
8136     \cs_gset:cpn { \c__msg_text_prefix_tl #1 / #2 }
8137     ##1##2##3##4 {#3}
8138     \cs_gset:cpn { \c__msg_more_text_prefix_tl #1 / #2 }
8139     ##1##2##3##4 {#4}
8140 }
8141 \cs_new_protected:Npn \msg_gset:nnn #1#2#3
8142 { \msg_gset:nnnn {#1} {#2} {#3} { } }

```

(End definition for \msg_new:nnnn and others. These functions are documented on page 136.)

16.2 Messages: support functions and text

Simple pieces of text for messages.

```

\c__msg_coding_error_text_tl
\c__msg_continue_text_tl
\c__msg_critical_text_tl
\c__msg_fatal_text_tl
\c__msg_help_text_tl
\c__msg_no_info_text_tl
\c__msg_on_line_text_tl
\c__msg_return_text_tl
\c__msg_trouble_text_tl

8143 \tl_const:Nn \c__msg_coding_error_text_tl
8144 {
8145   This~is~a~coding~error.
8146   \\ \\
8147 }
8148 \tl_const:Nn \c__msg_continue_text_tl
8149 { Type~<return>~to~continue }
8150 \tl_const:Nn \c__msg_critical_text_tl
8151 { Reading~the~current~file~'\g_file_curr_name_str'~will~stop. }
8152 \tl_const:Nn \c__msg_fatal_text_tl
8153 { This~is~a~fatal~error:~LaTeX~will~abort. }
8154 \tl_const:Nn \c__msg_help_text_tl
8155 { For~immediate~help~type~H~<return> }
8156 \tl_const:Nn \c__msg_no_info_text_tl
8157 {
8158   LaTeX~does~not~know~anything~more~about~this~error,~sorry.
8159   \c__msg_return_text_tl
8160 }
8161 \tl_const:Nn \c__msg_on_line_text_tl { on~line }
8162 \tl_const:Nn \c__msg_return_text_tl
8163 {
8164   \\ \\
8165   Try~typing~<return>~to~proceed.
8166   \\
8167   If~that~doesn't~work,~type~X~<return>~to~quit.
8168 }
8169 \tl_const:Nn \c__msg_trouble_text_tl
8170 {
8171   \\ \\
8172   More~errors~will~almost~certainly~follow: \\
8173   the~LaTeX~run~should~be~aborted.
8174 }

```

(End definition for `\c__msg_coding_error_text_tl` and others.)

`\msg_line_number:` For writing the line number nicely. `\msg_line_context:` was set up earlier, so this is not new.

```

8175 \cs_new:Npn \msg_line_number: { \int_use:N \tex_inputlineno:D }
8176 \cs_gset:Npn \msg_line_context:
8177 {
8178   \c__msg_on_line_text_tl
8179   \c_space_tl
8180   \msg_line_number:
8181 }

```

(End definition for `\msg_line_number:` and `\msg_line_context:`. These functions are documented on page 137.)

16.3 Showing messages: low level mechanism

`\msg_interrupt:nm` The low-level interruption macro is rather opaque, unfortunately. Depending on the availability of more information there is a choice of how to set up the further help. We

feed the extra help text and the message itself to a wrapping auxiliary, in this order because we must first setup T_EX's `\errhelp` register before issuing an `\errmessage`.

```

8182 \cs_new_protected:Npn \msg_interrupt:nnn #1#2#3
8183 {
8184   \tl_if_empty:nTF {#3}
8185   {
8186     \__msg_interrupt_wrap:nn { \ \ \c__msg_no_info_text_tl }
8187     {#1 \ \ \ \ #2 \ \ \ \ \c__msg_continue_text_tl }
8188   }
8189   {
8190     \__msg_interrupt_wrap:nn { \ \ \ #3 }
8191     {#1 \ \ \ \ #2 \ \ \ \ \c__msg_help_text_tl }
8192   }
8193 }

```

(End definition for `\msg_interrupt:nnn`. This function is documented on page 141.)

```

\__msg_interrupt_wrap:nn
\__msg_interrupt_more_text:n

```

First setup T_EX's `\errhelp` register with the extra help #1, then build a nice-looking error message with #2. Everything is done using x-type expansion as the new line markers are different for the two type of text and need to be correctly set up. The auxiliary `__msg_interrupt_more_text:n` receives its argument as a line-wrapped string, which is thus unaffected by expansion.

```

8194 \cs_new_protected:Npn \__msg_interrupt_wrap:nn #1#2
8195 {
8196   \iow_wrap:nnnN {#1} { | ~ } { } \__msg_interrupt_more_text:n
8197   \iow_wrap:nnnN {#2} { ! ~ } { } \__msg_interrupt_text:n
8198 }
8199 \cs_new_protected:Npn \__msg_interrupt_more_text:n #1
8200 {
8201   \exp_args:Nx \tex_errhelp:D
8202   {
8203     |,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,
8204     #1 \iow_newline:
8205     |.....
8206   }
8207 }

```

(End definition for `__msg_interrupt_wrap:nn` and `__msg_interrupt_more_text:n`.)

```

\__msg_interrupt_text:n

```

The business end of the process starts by producing some visual separation of the message from the main part of the log. The error message needs to be printed with everything made “invisible”: T_EX's own information involves the macro in which `\errmessage` is called, and the end of the argument of the `\errmessage`, including the closing brace. We use an active `!` to call the `\errmessage` primitive, and end its argument with `\use_none:n {<dots>}` which fills the output with dots. Two trailing closing braces are turned into spaces to hide them as well. The group in which we alter the definition of the active `!` is closed before producing the message: this ensures that tokens inserted by typing `I` in the command-line are inserted after the message is entirely cleaned up.

The `__iow_with:Nnn` auxiliary, defined in `l3file`, expects an *<integer variable>*, an integer *<value>*, and some *<code>*. It runs the *<code>* after ensuring that the *<integer variable>* takes the given *<value>*, then restores the former value of the *<integer variable>* if needed. We use it to ensure that the `\newlinechar` is 10, as needed for `\iow_newline:` to work, and that `\errorcontextlines` is `-1`, to avoid showing irrelevant

context. Note that restoring the former value of these integers requires inserting tokens after the `\errmessage`, which go in the way of tokens which could be inserted by the user. This is unavoidable.

```

8208 \group_begin:
8209   \char_set_lccode:nn {'\} {'\ }
8210   \char_set_lccode:nn {'\} {'\ }
8211   \char_set_lccode:nn {'&} {'!\}
8212   \char_set_catcode_active:N \&
8213 \tex_lowercase:D
8214 {
8215   \group_end:
8216   \cs_new_protected:Npn \_msg_interrupt_text:n #1
8217   {
8218     \iow_term:x
8219     {
8220       \iow_newline:
8221       !!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!
8222       \iow_newline:
8223       !
8224     }
8225     \_iow_with:Nnn \tex_newlinechar:D { '\^~J }
8226     {
8227       \_iow_with:Nnn \tex_errorcontextlines:D { -1 }
8228       {
8229         \group_begin:
8230         \cs_set_protected:Npn &
8231         {
8232           \tex_errmessage:D
8233           {
8234             #1
8235             \use_none:n
8236             { ..... }
8237           }
8238         }
8239         \exp_after:wN
8240         \group_end:
8241         &
8242       }
8243     }
8244   }
8245 }
```

(End definition for `_msg_interrupt_text:n`.)

`\msg_log:n` Printing to the log or terminal without a stop is rather easier. A bit of simple visual
`\msg_term:n` work sets things off nicely.

```

8246 \cs_new_protected:Npn \msg_log:n #1
8247 {
8248   \iow_log:n { ..... }
8249   \iow_wrap:nnnN { . ~ #1 } { . ~ } { } \iow_log:n
8250   \iow_log:n { ..... }
8251 }
8252 \cs_new_protected:Npn \msg_term:n #1
8253 {
```

```

8254 \iow_term:n { ***** }
8255 \iow_wrap:nnnN { * ~ #1 } { * ~ } { } \iow_term:n
8256 \iow_term:n { ***** }
8257 }

```

(End definition for `\msg_log:n` and `\msg_term:n`. These functions are documented on page 142.)

16.4 Displaying messages

L^AT_EX is handling error messages and so the T_EX ones are disabled. This is already done by the L^AT_EX_{2 ϵ} kernel, so to avoid messing up any deliberate change by a user this is only set in format mode.

```

8258 \*initex
8259 \int_gset:Nn \tex_errorcontextlines:D { -1 }
8260 \</initex

```

`\msg_fatal_text:n` A function for issuing messages: both the text and order could in principle vary.

```

\msg_fatal_text:n
\msg_critical_text:n
\msg_error_text:n
\msg_warning_text:n
\msg_info_text:n
8261 \cs_new:Npn \msg_fatal_text:n #1
8262 {
8263   Fatal~#1~error
8264   \bool_if:NT \l__msg_line_context_bool { ~ \msg_line_context: }
8265 }
8266 \cs_new:Npn \msg_critical_text:n #1
8267 {
8268   Critical~#1~error
8269   \bool_if:NT \l__msg_line_context_bool { ~ \msg_line_context: }
8270 }
8271 \cs_new:Npn \msg_error_text:n #1
8272 {
8273   #1~error
8274   \bool_if:NT \l__msg_line_context_bool { ~ \msg_line_context: }
8275 }
8276 \cs_new:Npn \msg_warning_text:n #1
8277 {
8278   #1~warning
8279   \bool_if:NT \l__msg_line_context_bool { ~ \msg_line_context: }
8280 }
8281 \cs_new:Npn \msg_info_text:n #1
8282 {
8283   #1~info
8284   \bool_if:NT \l__msg_line_context_bool { ~ \msg_line_context: }
8285 }

```

(End definition for `\msg_fatal_text:n` and others. These functions are documented on page 137.)

`\msg_see_documentation_text:n` Contextual footer information. The L^AT_EX module only comprises L^AT_EX₃ code, so we refer to the L^AT_EX₃ documentation rather than simply “L^AT_EX”.

```

8286 \cs_new:Npn \msg_see_documentation_text:n #1
8287 {
8288   \ \ See~the~
8289   \str_if_eq:nnTF {#1} { LaTeX } { LaTeX3 } {#1} ~
8290   documentation~for~further~information.
8291 }

```

(End definition for \msg_see_documentation_text:n. This function is documented on page 138.)

_msg_class_new:nn

```

8292 \group_begin:
8293   \cs_set_protected:Npn \_msg_class_new:nn #1#2
8294   {
8295     \prop_new:c { l\_msg_redirect_ #1 _prop }
8296     \cs_new_protected:cpn { \_msg_ #1 _code:nnnnnn }
8297       ##1##2##3##4##5##6 {#2}
8298     \cs_new_protected:cpn { msg_ #1 :nnnnnn } ##1##2##3##4##5##6
8299     {
8300       \use:x
8301       {
8302         \exp_not:n { \_msg_use:nnnnnn {#1} {##1} {##2} }
8303         { \tl_to_str:n {##3} } { \tl_to_str:n {##4} }
8304         { \tl_to_str:n {##5} } { \tl_to_str:n {##6} }
8305       }
8306     }
8307     \cs_new_protected:cpx { msg_ #1 :nnnnn } ##1##2##3##4##5
8308     { \exp_not:c { msg_ #1 :nnnnnn } {##1} {##2} {##3} {##4} {##5} { } }
8309     \cs_new_protected:cpx { msg_ #1 :nnnn } ##1##2##3##4
8310     { \exp_not:c { msg_ #1 :nnnnnn } {##1} {##2} {##3} {##4} { } { } }
8311     \cs_new_protected:cpx { msg_ #1 :nnn } ##1##2##3
8312     { \exp_not:c { msg_ #1 :nnnnnn } {##1} {##2} {##3} { } { } { } }
8313     \cs_new_protected:cpx { msg_ #1 :nn } ##1##2
8314     { \exp_not:c { msg_ #1 :nnnnnn } {##1} {##2} { } { } { } { } }
8315     \cs_new_protected:cpx { msg_ #1 :nnxxx } ##1##2##3##4##5##6
8316     {
8317       \use:x
8318       {
8319         \exp_not:N \exp_not:n
8320         { \exp_not:c { msg_ #1 :nnnnnn } {##1} {##2} }
8321         {##3} {##4} {##5} {##6}
8322       }
8323     }
8324     \cs_new_protected:cpx { msg_ #1 :nnxxx } ##1##2##3##4##5
8325     { \exp_not:c { msg_ #1 :nnxxx } {##1} {##2} {##3} {##4} {##5} { } }
8326     \cs_new_protected:cpx { msg_ #1 :nnxx } ##1##2##3##4
8327     { \exp_not:c { msg_ #1 :nnxxx } {##1} {##2} {##3} {##4} { } { } }
8328     \cs_new_protected:cpx { msg_ #1 :nnx } ##1##2##3
8329     { \exp_not:c { msg_ #1 :nnxxx } {##1} {##2} {##3} { } { } { } }
8330   }

```

(End definition for _msg_class_new:nn.)

\msg_fatal:nnnnnn For fatal errors, after the error message T_EX bails out.

```

\msg_fatal:nnxxxx 8331 \_msg_class_new:nn { fatal }
\msg_fatal:nnnnn 8332 {
\msg_fatal:nnxxx 8333   \msg_interrupt:nnn
\msg_fatal:nnnn 8334   { \msg_fatal_text:n {#1} : ~ "#2" }
\msg_fatal:nnxx 8335   {
\msg_fatal:nnnn 8336     \use:c { \c\_msg_text_prefix_tl #1 / #2 } {#3} {#4} {#5} {#6}
\msg_fatal:nnx 8337     \msg_see_documentation_text:n {#1}
\msg_fatal:nn 8338   }

```



```

8339         { \c__msg_fatal_text_tl }
8340     \tex_end:D
8341 }

```

(End definition for `\msg_fatal:nnnnnn` and others. These functions are documented on page 138.)

`\msg_critical:nnnnnn` Not quite so bad: just end the current file.

```

\msg_critical:nnxxxx 8342 \__msg_class_new:nn { critical }
\msg_critical:nnnnnn 8343 {
\msg_critical:nnxxx 8344     \msg_interrupt:nnn
\msg_critical:nnnn 8345     { \msg_critical_text:n {#1} : ~ "#2" }
\msg_critical:nnxx 8346     {
\msg_critical:nnnn 8347         \use:c { \c__msg_text_prefix_tl #1 / #2 } {#3} {#4} {#5} {#6}
\msg_critical:nnx 8348         \msg_see_documentation_text:n {#1}
\msg_critical:nn 8349     }
\msg_critical:nn 8350     { \c__msg_critical_text_tl }
8351 \tex_endinput:D
8352 }

```

(End definition for `\msg_critical:nnnnnn` and others. These functions are documented on page 138.)

`\msg_error:nnnnnn` For an error, the interrupt routine is called. We check if there is a “more text” by comparing that control sequence with a permanently empty text.

```

\msg_error:nnxxxx 8353 \__msg_class_new:nn { error }
\msg_error:nnxxx 8354 {
\msg_error:nnnn 8355     \__msg_error:cnnnnn
\msg_error:nnxx 8356     { \c__msg_more_text_prefix_tl #1 / #2 }
\msg_error:nnn 8357     {#3} {#4} {#5} {#6}
\msg_error:nnx 8358     {
\msg_error:nn 8359         \msg_interrupt:nnn
\__msg_error:cnnnnn 8360         { \msg_error_text:n {#1} : ~ "#2" }
\__msg_no_more_text:nnnn 8361         {
8362             \use:c { \c__msg_text_prefix_tl #1 / #2 } {#3} {#4} {#5} {#6}
8363             \msg_see_documentation_text:n {#1}
8364         }
8365     }
8366 }
8367 \cs_new_protected:Npn \__msg_error:cnnnnn #1#2#3#4#5#6
8368 {
8369     \cs_if_eq:cNTF {#1} \__msg_no_more_text:nnnn
8370     { #6 { } }
8371     { #6 { \use:c {#1} {#2} {#3} {#4} {#5} } }
8372 }
8373 \cs_new:Npn \__msg_no_more_text:nnnn #1#2#3#4 { }

```

(End definition for `\msg_error:nnnnnn` and others. These functions are documented on page 139.)

`\msg_warning:nnnnnn` Warnings are printed to the terminal.

```

\msg_warning:nnxxxx 8374 \__msg_class_new:nn { warning }
\msg_warning:nnnnnn 8375 {
\msg_warning:nnxxx 8376     \msg_term:n
\msg_warning:nnnn 8377     {
\msg_warning:nnxx 8378         \msg_warning_text:n {#1} : ~ "#2" \\ \\
\msg_warning:nnn 8379         \use:c { \c__msg_text_prefix_tl #1 / #2 } {#3} {#4} {#5} {#6}
\msg_warning:nnx 8380     }
\msg_warning:nn 8381 }

```

(End definition for `\msg_warning:nnnnnn` and others. These functions are documented on page 139.)

```

\msg_info:nnnnnn Information only goes into the log.
\msg_info:nnxxxx 8382 \_msg_class_new:nn { info }
\msg_info:nnnnnn 8383 {
\msg_info:nnxxxx 8384 \msg_log:n
\msg_info:nnnnnn 8385 {
\msg_info:nnxxx 8386 \msg_info_text:n {#1} : ~ "#2" \\ \\
\msg_info:nnnn 8387 \use:c { \c_msg_text_prefix_tl #1 / #2 } {#3} {#4} {#5} {#6}
\msg_info:nnxx 8388 }
\msg_info:nn 8389 }

```

(End definition for `\msg_info:nnnnnn` and others. These functions are documented on page 139.)

```

\msg_log:nnnnnn "Log" data is very similar to information, but with no extras added.
\msg_log:nnxxxx 8390 \_msg_class_new:nn { log }
\msg_log:nnnnnn 8391 {
\msg_log:nnxxxx 8392 \iow_wrap:nnnN
\msg_log:nnnnnn 8393 { \use:c { \c_msg_text_prefix_tl #1 / #2 } {#3} {#4} {#5} {#6} }
\msg_log:nnxxx 8394 { } { } \iow_log:n
\msg_log:nnnn 8395 }
\msg_log:nnxx
\msg_log:nn

```

(End definition for `\msg_log:nnnnnn` and others. These functions are documented on page 139.)

The `none` message type is needed so that input can be gobbled.

```

\msg_none:nnnnnn 8396 \_msg_class_new:nn { none } { }
\msg_none:nnxxxx

```

(End definition for `\msg_none:nnnnnn` and others. These functions are documented on page 140.)

The `show` message type is used for `\seq_show:N` and similar complicated data structures. Wrap the given text with a trailing dot (important later) then pass it to `_msg_show:n`. If there is `\\>~` (or if the whole thing starts with `>~`) we split there, print the first part and show the second part using `\showtokens` (the `\exp_after:wN` ensure a nice display). Note that that primitive adds a leading `>~` and trailing dot. That is why we included a trailing dot before wrapping and removed it afterwards. If there is no `\\>~` do the same but with an empty second part which adds a spurious but inevitable `>~`.

```

\msg_show:nnxx 8397 \_msg_class_new:nn { show }
\msg_show:nnnn 8398 {
\_msg_show:n 8399 \iow_wrap:nnnN
\_msg_show:w 8400 { \use:c { \c_msg_text_prefix_tl #1 / #2 } {#3} {#4} {#5} {#6} }
\_msg_show_dot:w 8401 { } { } \_msg_show:n
\_msg_show:nn 8402 }
8403 \cs_new_protected:Npn \_msg_show:n #1
8404 {
8405 \tl_if_in:nnTF { ^^J #1 } { ^^J > ~ }
8406 {
8407 \tl_if_in:nnTF { #1 \q_mark } { . \q_mark }
8408 { \_msg_show_dot:w } { \_msg_show:w }
8409 ^^J #1 \q_stop
8410 }
8411 { \_msg_show:nn { ? #1 } { } }
8412 }
8413 \cs_new:Npn \_msg_show_dot:w #1 ^^J > ~ #2 . \q_stop
8414 { \_msg_show:nn {#1} {#2} }

```

```

8415 \cs_new:Npn \__msg_show:w #1 ^^J > ~ #2 \q_stop
8416 { \__msg_show:nn {#1} {#2} }
8417 \cs_new_protected:Npn \__msg_show:nn #1#2
8418 {
8419   \tl_if_empty:nF {#1}
8420   { \exp_args:No \iow_term:n { \use_none:n #1 } }
8421   \tl_set:Nn \l__msg_internal_tl {#2}
8422   \__iow_with:Nnn \tex_newlinechar:D { 10 }
8423   {
8424     \__iow_with:Nnn \tex_errorcontextlines:D { -1 }
8425     {
8426       \etex_showtokens:D \exp_after:wN \exp_after:wN \exp_after:wN
8427       { \exp_after:wN \l__msg_internal_tl }
8428     }
8429   }
8430 }

```

(End definition for `\msg_show:nnnnnn` and others. These functions are documented on page 243.)

End the group to eliminate `__msg_class_new:nn`.

```

8431 \group_end:

```

`__msg_class_chk_exist:nT` Checking that a message class exists. We build this from `\cs_if_free:cTF` rather than `\cs_if_exist:cTF` because that avoids reading the second argument earlier than necessary.

```

8432 \cs_new:Npn \__msg_class_chk_exist:nT #1
8433 {
8434   \cs_if_free:cTF { __msg_ #1 _code:nnnnnn }
8435   { \__msg_kernel_error:nx { kernel } { message-class-unknown } {#1} }
8436 }

```

(End definition for `__msg_class_chk_exist:nT`.)

`\l__msg_class_tl` Support variables needed for the redirection system.
`\l__msg_current_class_tl`

```

8437 \tl_new:N \l__msg_class_tl
8438 \tl_new:N \l__msg_current_class_tl

```

(End definition for `\l__msg_class_tl` and `\l__msg_current_class_tl`.)

`\l__msg_redirect_prop` For redirection of individually-named messages

```

8439 \prop_new:N \l__msg_redirect_prop

```

(End definition for `\l__msg_redirect_prop`.)

`\l__msg_hierarchy_seq` During redirection, split the message name into a sequence with items `{/module/submodule}`, `{/module}`, and `{}`.

```

8440 \seq_new:N \l__msg_hierarchy_seq

```

(End definition for `\l__msg_hierarchy_seq`.)

`\l__msg_class_loop_seq` Classes encountered when following redirections to check for loops.

```

8441 \seq_new:N \l__msg_class_loop_seq

```

(End definition for `\l__msg_class_loop_seq`.)

`__msg_use:nnnnnnn` Actually using a message is a multi-step process. First, some safety checks on the message
`__msg_use_redirect_name:n` and class requested. The code and arguments are then stored to avoid passing them
`__msg_use_hierarchy:nwwN` around. The assignment to `__msg_use_code:` is similar to `\tl_set:Nn`. The message
`__msg_use_redirect_module:n` is eventually produced with whatever `\l__msg_class_tl` is when `__msg_use_code:` is
`__msg_use_code:` called.

```

8442 \cs_new_protected:Npn \__msg_use:nnnnnnn #1#2#3#4#5#6#7
8443 {
8444   \msg_if_exist:nnTF {#2} {#3}
8445   {
8446     \__msg_class_chk_exist:nT {#1}
8447     {
8448       \tl_set:Nn \l__msg_current_class_tl {#1}
8449       \cs_set_protected:Npx \__msg_use_code:
8450       {
8451         \exp_not:n
8452         {
8453           \use:c { __msg_ \l__msg_class_tl _code:nnnnnnn }
8454           {#2} {#3} {#4} {#5} {#6} {#7}
8455         }
8456       }
8457       \__msg_use_redirect_name:n { #2 / #3 }
8458     }
8459   }
8460   { \__msg_kernel_error:nxx { kernel } { message-unknown } {#2} {#3} }
8461 }
8462 \cs_new_protected:Npn \__msg_use_code: { }

```

The first check is for a individual message redirection. If this applies then no further redirection is attempted. Otherwise, split the message name into module/submodule/message (with an arbitrary number of slashes), and store `{/module/submodule}`, `{/module}` and `{}` into `\l__msg_hierarchy_seq`. We then map through this sequence, applying the most specific redirection.

```

8463 \cs_new_protected:Npn \__msg_use_redirect_name:n #1
8464 {
8465   \prop_get:NnNTF \l__msg_redirect_prop { / #1 } \l__msg_class_tl
8466   { \__msg_use_code: }
8467   {
8468     \seq_clear:N \l__msg_hierarchy_seq
8469     \__msg_use_hierarchy:nwwN { }
8470     #1 \q_mark \__msg_use_hierarchy:nwwN
8471     / \q_mark \use_none_delimit_by_q_stop:w
8472     \q_stop
8473     \__msg_use_redirect_module:n { }
8474   }
8475 }
8476 \cs_new_protected:Npn \__msg_use_hierarchy:nwwN #1#2 / #3 \q_mark #4
8477 {
8478   \seq_put_left:Nn \l__msg_hierarchy_seq {#1}
8479   #4 { #1 / #2 } #3 \q_mark #4
8480 }

```

At this point, the items of `\l__msg_hierarchy_seq` are the various levels at which we should look for a redirection. Redirections which are less specific than the argument of `__msg_use_redirect_module:n` are not attempted. This argument is empty for a class

redirection, /module for a module redirection, *etc.* Loop through the sequence to find the most specific redirection, with module ##1. The loop is interrupted after testing for a redirection for ##1 equal to the argument #1 (least specific redirection allowed). When a redirection is found, break the mapping, then if the redirection targets the same class, output the code with that class, and otherwise set the target as the new current class, and search for further redirections. Those redirections should be at least as specific as ##1.

```

8481 \cs_new_protected:Npn \__msg_use_redirect_module:n #1
8482 {
8483   \seq_map_inline:Nn \l__msg_hierarchy_seq
8484   {
8485     \prop_get:cnNTF { l__msg_redirect_ \l__msg_current_class_tl _prop }
8486     {##1} \l__msg_class_tl
8487     {
8488       \seq_map_break:n
8489       {
8490         \tl_if_eq:NNTF \l__msg_current_class_tl \l__msg_class_tl
8491         { \__msg_use_code: }
8492         {
8493           \tl_set_eq:NN \l__msg_current_class_tl \l__msg_class_tl
8494           \__msg_use_redirect_module:n {##1}
8495         }
8496       }
8497     }
8498   {
8499     \str_if_eq:nnT {##1} {#1}
8500     {
8501       \tl_set_eq:NN \l__msg_class_tl \l__msg_current_class_tl
8502       \seq_map_break:n { \__msg_use_code: }
8503     }
8504   }
8505 }
8506 }

```

(End definition for __msg_use:nnnnnnn and others.)

\msg_redirect_name:nnn Named message always use the given class even if that class is redirected further. An empty target class cancels any existing redirection for that message.

```

8507 \cs_new_protected:Npn \msg_redirect_name:nnn #1#2#3
8508 {
8509   \tl_if_empty:nTF {#3}
8510   { \prop_remove:Nn \l__msg_redirect_prop { / #1 / #2 } }
8511   {
8512     \__msg_class_chk_exist:nT {#3}
8513     { \prop_put:Nnn \l__msg_redirect_prop { / #1 / #2 } {#3} }
8514   }
8515 }

```

(End definition for \msg_redirect_name:nnn. This function is documented on page 141.)

\msg_redirect_class:nn If the target class is empty, eliminate the corresponding redirection. Otherwise, add the redirection. We must then check for a loop: as an initialization, we start by storing the initial class in \l__msg_current_class_tl.

\msg_redirect_module:nnn

__msg_redirect:nnn

__msg_redirect_loop_chk:nnn

__msg_redirect_loop_list:n

```

8516 \cs_new_protected:Npn \msg_redirect_class:nn
8517 { \__msg_redirect:nnn { } }
8518 \cs_new_protected:Npn \msg_redirect_module:nnn #1
8519 { \__msg_redirect:nnn { / #1 } }
8520 \cs_new_protected:Npn \__msg_redirect:nnn #1#2#3
8521 {
8522   \__msg_class_chk_exist:nT {#2}
8523   {
8524     \tl_if_empty:nTF {#3}
8525     { \prop_remove:cn { l__msg_redirect_ #2 _prop } {#1} }
8526     {
8527       \__msg_class_chk_exist:nT {#3}
8528       {
8529         \prop_put:cnn { l__msg_redirect_ #2 _prop } {#1} {#3}
8530         \tl_set:Nn \l__msg_current_class_tl {#2}
8531         \seq_clear:N \l__msg_class_loop_seq
8532         \__msg_redirect_loop_chk:nnn {#2} {#3} {#1}
8533       }
8534     }
8535   }
8536 }

```

Since multiple redirections can only happen with increasing specificity, a loop requires that all steps are of the same specificity. The new redirection can thus only create a loop with other redirections for the exact same module, #1, and not submodules. After some initialization above, follow redirections with `\l__msg_class_tl`, and keep track in `\l__msg_class_loop_seq` of the various classes encountered. A redirection from a class to itself, or the absence of redirection both mean that there is no loop. A redirection to the initial class marks a loop. To break it, we must decide which redirection to cancel. The user most likely wants the newly added redirection to hold with no further redirection. We thus remove the redirection starting from #2, target of the new redirection. Note that no message is emitted by any of the underlying functions: otherwise we may get an infinite loop because of a message from the message system itself.

```

8537 \cs_new_protected:Npn \__msg_redirect_loop_chk:nnn #1#2#3
8538 {
8539   \seq_put_right:Nn \l__msg_class_loop_seq {#1}
8540   \prop_get:cnNT { l__msg_redirect_ #1 _prop } {#3} \l__msg_class_tl
8541   {
8542     \str_if_eq_x:nnF { \l__msg_class_tl } {#1}
8543     {
8544       \tl_if_eq:NNTF \l__msg_class_tl \l__msg_current_class_tl
8545       {
8546         \prop_put:cnn { l__msg_redirect_ #2 _prop } {#3} {#2}
8547         \__msg_kernel_warning:nnxxxx
8548         { kernel } { message-redirect-loop }
8549         { \seq_item:Nn \l__msg_class_loop_seq { 1 } }
8550         { \seq_item:Nn \l__msg_class_loop_seq { 2 } }
8551         {#3}
8552         {
8553           \seq_map_function:NN \l__msg_class_loop_seq
8554           \__msg_redirect_loop_list:n
8555           { \seq_item:Nn \l__msg_class_loop_seq { 1 } }
8556         }
8557       }
8558     }
8559   }
8560 }

```

```

8558             { \_msg_redirect_loop_chk:onn \l\_msg_class_tl {#2} {#3} }
8559         }
8560     }
8561 }
8562 \cs_generate_variant:Nn \_msg_redirect_loop_chk:nnn { o }
8563 \cs_new:Npn \_msg_redirect_loop_list:n #1 { {#1} ~ => ~ }

```

(End definition for `\msg_redirect_class:nn` and others. These functions are documented on page 140.)

16.5 Kernel-specific functions

`_msg_kernel_new:nnnn` The kernel needs some messages of its own. These are created using pre-built functions. Two functions are provided: one more general and one which only has the short text part.

```

\_msg_kernel_new:nnnn
\_msg_kernel_new:nnn
\_msg_kernel_set:nnnn
\_msg_kernel_set:nnn
8564 \cs_new_protected:Npn \_msg_kernel_new:nnnn #1#2
8565 { \msg_new:nnnn { LaTeX } { #1 / #2 } }
8566 \cs_new_protected:Npn \_msg_kernel_new:nnn #1#2
8567 { \msg_new:nnn { LaTeX } { #1 / #2 } }
8568 \cs_new_protected:Npn \_msg_kernel_set:nnnn #1#2
8569 { \msg_set:nnnn { LaTeX } { #1 / #2 } }
8570 \cs_new_protected:Npn \_msg_kernel_set:nnn #1#2
8571 { \msg_set:nnn { LaTeX } { #1 / #2 } }

```

(End definition for `_msg_kernel_new:nnnn` and others.)

`_msg_kernel_class_new:nN` All the functions for kernel messages come in variants ranging from 0 to 4 arguments. Those with less than 4 arguments are defined in terms of the 4-argument variant, in a way very similar to `_msg_class_new:nn`. This auxiliary is destroyed at the end of the group.

`_msg_kernel_class_new_aux:nN`

```

8572 \group_begin:
8573 \cs_set_protected:Npn \_msg_kernel_class_new:nN #1
8574 { \_msg_kernel_class_new_aux:nN { kernel_ #1 } }
8575 \cs_set_protected:Npn \_msg_kernel_class_new_aux:nN #1#2
8576 {
8577     \cs_new_protected:cpn { \_msg_ #1 :nnnnnn } ##1##2##3##4##5##6
8578     {
8579         \use:x
8580         {
8581             \exp_not:n { #2 { LaTeX } { ##1 / ##2 } }
8582             { \tl_to_str:n {##3} } { \tl_to_str:n {##4} }
8583             { \tl_to_str:n {##5} } { \tl_to_str:n {##6} }
8584         }
8585     }
8586     \cs_new_protected:cpx { \_msg_ #1 :nnnnnn } ##1##2##3##4##5
8587     { \exp_not:c { \_msg_ #1 :nnnnnn } {##1} {##2} {##3} {##4} {##5} { } }
8588     \cs_new_protected:cpx { \_msg_ #1 :nnnn } ##1##2##3##4
8589     { \exp_not:c { \_msg_ #1 :nnnnnn } {##1} {##2} {##3} {##4} { } { } }
8590     \cs_new_protected:cpx { \_msg_ #1 :nnn } ##1##2##3
8591     { \exp_not:c { \_msg_ #1 :nnnnnn } {##1} {##2} {##3} { } { } { } }
8592     \cs_new_protected:cpx { \_msg_ #1 :nn } ##1##2
8593     { \exp_not:c { \_msg_ #1 :nnnnnn } {##1} {##2} { } { } { } { } }
8594     \cs_new_protected:cpx { \_msg_ #1 :nnxxxx } ##1##2##3##4##5##6
8595     {
8596         \use:x

```

```

8597     {
8598         \exp_not:N \exp_not:n
8599         { \exp_not:c { __msg_ #1 :nnnnnn } {##1} {##2} }
8600         {##3} {##4} {##5} {##6}
8601     }
8602 }
8603 \cs_new_protected:cpx { __msg_ #1 :nnxxx } ##1##2##3##4##5
8604 { \exp_not:c { __msg_ #1 :nnxxxx } {##1} {##2} {##3} {##4} {##5} { } }
8605 \cs_new_protected:cpx { __msg_ #1 :nnxx } ##1##2##3##4
8606 { \exp_not:c { __msg_ #1 :nnxxxx } {##1} {##2} {##3} {##4} { } { } }
8607 \cs_new_protected:cpx { __msg_ #1 :nnx } ##1##2##3
8608 { \exp_not:c { __msg_ #1 :nnxxxx } {##1} {##2} {##3} { } { } { } }
8609 }

```

(End definition for \ msg kernel class new:nN and \ msg kernel class new aux:nN.)

Neither fatal kernel errors nor kernel errors can be redirected. We directly use
(non-kernel) fatal errors and errors, adding the “L^AT_EX” module name. The macros
are already defined by l3basics; we need to undefine them to avoid errors.

```
\_msg_kernel_fatal:nnnnnn
\_msg_kernel_fatal:nxxxxx
\_msg_kernel_fatal:nnnnn
\_msg_kernel_fatal:nxxxx
8610 \_msg_kernel_class_new:nN { fatal } \_msg_fatal_code:nnnnnn
\_msg_kernel_fatal:nnnn      8611 \cs_undefine:N \_msg_kernel_error:nxxx
\_msg_kernel_fatal:nnxx     8612 \cs_undefine:N \_msg_kernel_error:nnx
\_msg_kernel_fatal:nnn      8613 \cs_undefine:N \_msg_kernel_error:nn
\_msg_kernel_fatal:nnx      8614 \_msg_kernel_class_new:nN { error } \_msg_error_code:nnnnnn
\_msg_kernel_fatal:nn
\_msg_kernel_error:nnnnnn
```

(End definition for _msg_kernel_fatal:nnnnnn and others.)

Kernel messages which can be redirected simply use the machinery for normal messages, with the module name “L^AT_EX”.

```

\__msg_kernel_warning:nnnnn      8615  \__msg_kernel_class_new:nN { warning } \msg_warning:nnxxx
\__msg_kernel_warning:nnnnn      8616  \__msg_kernel_class_new:nN { info } \msg_info:nnxxx
\__msg_kernel_warning:nnnnn
\__msg_kernel_warning:nnnnn      (End definition for \__msg_kernel_warning:nnnnnn and others.)
\__msg_kernel_warning:nnnnn      End the group to eliminate \__msg_kernel_class_new:nN.
\__msg_kernel_warning:nnnnn
\__msg_kernel_warning:nnnnn      8617  \group_end:

```

Error messages needed to actually implement the message system itself.

```

5618 \_msg_kernel_info:nnnnnn
5619 \_msg_kernel_info:nnxxxx
5620 \_msg_kernel_info:nnnnn
5621 \_msg_kernel_info:nnxxx
5622 \_msg_kernel_info:nnnn
5623 \_msg_kernel_info:nnxx
5624 \_msg_kernel_info:nnn
5625 \_msg_kernel_info:nnx
5626 \_msg_kernel_info:nn
5627
5628 \_msg_kernel_new:nnnn { kernel } { message-already-defined }
5629 { Message~'#2'~for~module~'#1'~already-defined. }
5630 {
5631   \c__msg_coding_error_text_tl
5632   LaTeX~was~asked~to~define~a~new~message~called~'#2'~\
5633   by~the~module~'#1'~:~this~message~already~exists.
5634   \c__msg_return_text_tl
5635 }
5636 \_msg_kernel_new:nnnn { kernel } { message-unknown }
5637 { Unknown~message~'#2'~for~module~'#1'. }
5638 {
5639   \c__msg_coding_error_text_tl
5640   LaTeX~was~asked~to~display~a~message~called~'#2'~\
5641   by~the~module~'#1'~:~this~message~does~not~exist.
5642   \c__msg_return_text_tl
5643 }
5644 \_msg_kernel_new:nnnn { kernel } { message-class-unknown }
5645 { Unknown~message~class~'#1'. }

```



```

8636 {
8637   LaTeX-has-been-asked-to-redirect-messages-to-a-class~'#1':\\
8638   this-was-never-defined.
8639   \c__msg_return_text_tl
8640 }
8641 \__msg_kernel_new:nnnn { kernel } { message-redirect-loop }
8642 {
8643   Message-redirect-loop-caused-by~ {#1} ~>~ {#2}
8644   \tl_if_empty:nF {#3} { ~for-module~' \use_none:n #3 ' } .
8645 }
8646 {
8647   Adding-the-message-redirection~ {#1} ~>~ {#2}
8648   \tl_if_empty:nF {#3} { ~for-the-module~' \use_none:n #3 ' } ~
8649   created-an-infinite-loop\\
8650   \iow_indent:n { #4 \\ }
8651 }

```

Messages for earlier kernel modules.

```

8652 \__msg_kernel_new:nnnn { kernel } { bad-number-of-arguments }
8653 { Function~'#1'~cannot-be-defined-with~#2~arguments. }
8654 {
8655   \c__msg_coding_error_text_tl
8656   LaTeX-has-been-asked-to-define-a-function~'#1'~with~
8657   #2~arguments.~
8658   TeX~allows-between-0~and~9~arguments~for~a~single~function.
8659 }
8660 \__msg_kernel_new:nnn { kernel } { char-active }
8661 { Cannot-generate-active-chars. }
8662 \__msg_kernel_new:nnn { kernel } { char-invalid-catcode }
8663 { Invalid-catcode-for-char-generation. }
8664 \__msg_kernel_new:nnn { kernel } { char-null-space }
8665 { Cannot-generate-null-char-as-a-space. }
8666 \__msg_kernel_new:nnn { kernel } { char-out-of-range }
8667 { Charcode-requested-out-of-engine-range. }
8668 \__msg_kernel_new:nnn { kernel } { char-space }
8669 { Cannot-generate-space-chars. }
8670 \__msg_kernel_new:nnnn { kernel } { command-already-defined }
8671 { Control-sequence~#1~already-defined. }
8672 {
8673   \c__msg_coding_error_text_tl
8674   LaTeX-has-been-asked-to-create-a-new-control-sequence~'#1'~
8675   but-this-name-has-already-been-used-elsewhere. \\ \\
8676   The-current-meaning-is:\\
8677   \ \ #2
8678 }
8679 \__msg_kernel_new:nnnn { kernel } { command-not-defined }
8680 { Control-sequence~#1~undefined. }
8681 {
8682   \c__msg_coding_error_text_tl
8683   LaTeX-has-been-asked-to-use-a-control-sequence~'#1':\\
8684   this-has-not-been-defined-yet.
8685 }
8686 \__msg_kernel_new:nnn { kernel } { deprecated-command }
8687 {
8688   The-deprecated-command~'#2'~has-been-or-will-be-removed-on~#1.

```

```

8689 \tl_if_empty:nF {#3} { ~Use~instead~'#3'. }
8690 }
8691 \__msg_kernel_new:nnnn { kernel } { empty-search-pattern }
8692 { Empty~search~pattern. }
8693 {
8694   \c__msg_coding_error_text_tl
8695   LaTeX~has~been~asked~to~replace~an~empty~pattern~by~'#1':~that~
8696   would~lead~to~an~infinite~loop!
8697 }
8698 \__msg_kernel_new:nnnn { kernel } { out-of-registers }
8699 { No~room~for~a~new~#1. }
8700 {
8701   TeX~only~supports~\int_use:N \c_max_register_int \ %
8702   of~each~type.~All~the~#1~registers~have~been~used.~
8703   This~run~will~be~aborted~now.
8704 }
8705 \__msg_kernel_new:nnnn { kernel } { non-base-function }
8706 { Function~'#1'~is~not~a~base~function }
8707 {
8708   \c__msg_coding_error_text_tl
8709   Functions~defined~through~\iow_char:N\cs_new:Nn~must~have~
8710   a~signature~consisting~of~only~normal~arguments~'N'~and~'n'.~
8711   To~define~variants~use~\iow_char:N\cs_generate_variant:Nn~
8712   and~to~define~other~functions~use~\iow_char:N\cs_new:Npn.
8713 }
8714 \__msg_kernel_new:nnnn { kernel } { missing-colon }
8715 { Function~'#1'~contains~no~':'. }
8716 {
8717   \c__msg_coding_error_text_tl
8718   Code~level~functions~must~contain~':'~to~separate~the~
8719   argument~specification~from~the~function~name.~This~is~
8720   needed~when~defining~conditionals~or~variants,~or~when~building~a~
8721   parameter~text~from~the~number~of~arguments~of~the~function.
8722 }
8723 \__msg_kernel_new:nnnn { kernel } { overflow }
8724 { Integers~larger~than~230-1~cannot~be~stored~in~arrays. }
8725 {
8726   An~attempt~was~made~to~store~#3~at~position~#2~in~the~array~'#1'.~
8727   The~largest~allowed~value~#4~will~be~used~instead.
8728 }
8729 \__msg_kernel_new:nnnn { kernel } { out-of-bounds }
8730 { Access~to~an~entry~beyond~an~array's~bounds. }
8731 {
8732   An~attempt~was~made~to~access~or~store~data~at~position~#2~of~the~
8733   array~'#1',~but~this~array~has~entries~at~positions~from~1~to~#3.
8734 }
8735 \__msg_kernel_new:nnnn { kernel } { protected-predicate }
8736 { Predicate~'#1'~must~be~expandable. }
8737 {
8738   \c__msg_coding_error_text_tl
8739   LaTeX~has~been~asked~to~define~'#1'~as~a~protected~predicate.~
8740   Only~expandable~tests~can~have~a~predicate~version.
8741 }
8742 \__msg_kernel_new:nnnn { kernel } { conditional-form-unknown }

```

```

8743 { Conditional-form~'~#1'~for~function~'~#2'~unknown. }
8744 {
8745   \c_msg_coding_error_text_tl
8746   LaTeX-has-been-asked-to-define-the-conditional-form~'~#1'~of~
8747   the-function~'~#2',~but-only~'TF',~'T',~'F',~and~'p'~forms~exist.
8748 }
8749 \__msg_kernel_new:nnnn { kernel } { scanmark-already-defined }
8750 { Scan-mark~#1~already-defined. }
8751 {
8752   \c_msg_coding_error_text_tl
8753   LaTeX-has-been-asked-to-create-a-new-scan-mark~'~#1'~
8754   but-this-name-has-already-been-used-for-a-scan-mark.
8755 }
8756 \__msg_kernel_new:nnnn { kernel } { variable-not-defined }
8757 { Variable~#1~undefined. }
8758 {
8759   \c_msg_coding_error_text_tl
8760   LaTeX-has-been-asked-to-show-a-variable~#1,~but~this~has~not~
8761   been-defined-yet.
8762 }
8763 \__msg_kernel_new:nnnn { kernel } { variant-too-long }
8764 { Variant-form~'~#1'~longer~than~base-signature-of~'~#2'. }
8765 {
8766   \c_msg_coding_error_text_tl
8767   LaTeX-has-been-asked-to-create-a-variant-of-the-function~'~#2'~
8768   with-a-signature-starting-with~'~#1',~but~that~is~longer~than~
8769   the-signature~(part~after~the~colon)~of~'~#2'.
8770 }
8771 \__msg_kernel_new:nnnn { kernel } { invalid-variant }
8772 { Variant-form~'~#1'~invalid~for~base-form~'~#2'. }
8773 {
8774   \c_msg_coding_error_text_tl
8775   LaTeX-has-been-asked-to-create-a-variant-of~the~function~'~#2'~
8776   with-a-signature-starting-with~'~#1',~but~cannot~change~an~argument~
8777   from~type~'~#3'~to~type~'~#4'.
8778 }

```

Some errors are only needed in package mode if debugging is enabled by one of the options `enable-debug`, `check-declarations`, `log-functions`, or on the contrary if debugging is turned off. In format mode the error is somewhat different.

```

8779 \*package>
8780 \bool_if:NTF \l@expl@enable@debug@bool
8781 {
8782   \__msg_kernel_new:nnnn { kernel } { debug }
8783   { The~debugging-option~'~#1'~does-not-exist~\msg_line_context:. }
8784   {
8785     The~functions~'\iow_char:N\debug_on:n'~and~
8786     '\iow_char:N\debug_off:n'~only~accept~the~arguments~
8787     'check-declarations',~'deprecation',~'log-functions',~not~'~#1'.
8788   }
8789   \__msg_kernel_new:nnn { kernel } { expr } { '#2'~in~#1 }
8790   \__msg_kernel_new:nnnn { kernel } { local-global }
8791   { Inconsistent~local/global~assignment }
8792   {

```

```

8793 \c__msg_coding_error_text_tl
8794 \if:w l #2 Local \else: Global \fi: \
8795 assignment~to~a~
8796 \if:w l #1 local \else: \if:w g #1 global \else: constant \fi: \fi: \
8797 variable~'#3'.
8798 }
8799 \__msg_kernel_new:nnnn { kernel } { non-declared-variable }
8800 { The~variable~#1~has~not~been~declared~\msg_line_context:. }
8801 {
8802   Checking~is~active,~and~you~have~tried~do~so~something~like: \\
8803   \ \ \tl_set:Nn ~ #1 ~ \{ ~ ... ~ \} \\
8804   without~first~having: \\
8805   \ \ \tl_new:N ~ #1 \\
8806   \\
8807   LaTeX~will~create~the~variable~and~continue.
8808 }
8809 }
8810 {
8811 \__msg_kernel_new:nnnn { kernel } { enable-debug }
8812 { To~use~'#1'~load~expl3~with~the~'enable-debug'~option. }
8813 {
8814   The~function~'#1'~will~be~ignored~because~it~can~only~work~if~
8815   some~internal~functions~in~expl3~have~been~appropriately~
8816   defined.~This~only~happens~if~one~of~the~options~
8817   'enable-debug',~'check-declarations'~or~'log-functions'~was~
8818   given~when~loading~expl3.
8819 }
8820 }
8821 \</package>
8822 \*initex>
8823 \__msg_kernel_new:nnnn { kernel } { enable-debug }
8824 { '#1'~cannot~be~used~in~format~mode. }
8825 {
8826   The~function~'#1'~will~be~ignored~because~it~can~only~work~if~
8827   some~internal~functions~in~expl3~have~been~appropriately~
8828   defined.~This~only~happens~in~package~mode~(and~only~if~one~of~
8829   the~options~'enable-debug',~'check-declarations'~or~'log-functions'~
8830   was~given~when~loading~expl3.
8831 }
8832 \</initex>

```

Some errors only appear in expandable settings, hence don't need a "more-text" argument.

```

8833 \__msg_kernel_new:nnn { kernel } { bad-exp-end-f }
8834 { Misused~\exp_end_continue_f:w or~:nw }
8835 \__msg_kernel_new:nnn { kernel } { bad-variable }
8836 { Erroneous~variable~#1 used! }
8837 \__msg_kernel_new:nnn { kernel } { misused-sequence }
8838 { A~sequence~was~misused. }
8839 \__msg_kernel_new:nnn { kernel } { misused-prop }
8840 { A~property~list~was~misused. }
8841 \__msg_kernel_new:nnn { kernel } { negative-replication }
8842 { Negative~argument~for~\prg_replicate:nn. }
8843 \__msg_kernel_new:nnn { kernel } { prop-keyval }

```

```

8844 { Missing/extra~'='~in~'#1'~(in~'..._keyval:Nn') }
8845 \_msg_kernel_new:nnn { kernel } { unknown-comparison }
8846 { Relation~'#1'~unknown:~use~=',~<,~>,~==,~!=,~<=,~>=. }
8847 \_msg_kernel_new:nnn { kernel } { zero-step }
8848 { Zero~step~size~for~step~function~#1. }

Messages used by the “show” functions.

8849 \_msg_kernel_new:nnn { kernel } { show-clist }
8850 {
8851   The~comma~list~ \tl_if_empty:nF {#1} { #1 ~ }
8852   \tl_if_empty:nTF {#2}
8853   { is~empty \>~ . }
8854   { contains~the~items~(without~outer~braces): #2 . }
8855 }
8856 \_msg_kernel_new:nnn { kernel } { show-prop }
8857 {
8858   The~property~list~#1~
8859   \tl_if_empty:nTF {#2}
8860   { is~empty \>~ . }
8861   { contains~the~pairs~(without~outer~braces): #2 . }
8862 }
8863 \_msg_kernel_new:nnn { kernel } { show-seq }
8864 {
8865   The~sequence~#1~
8866   \tl_if_empty:nTF {#2}
8867   { is~empty \>~ . }
8868   { contains~the~items~(without~outer~braces): #2 . }
8869 }
8870 \_msg_kernel_new:nnn { kernel } { show-streams }
8871 {
8872   \tl_if_empty:nTF {#2} { No~ } { The~following~ }
8873   \str_case:nn {#1}
8874   {
8875     { ior } { input ~ }
8876     { iow } { output ~ }
8877   }
8878   streams~are~
8879   \tl_if_empty:nTF {#2} { open } { in~use: #2 . }
8880 }

```

16.6 Expandable errors

`_msg_expandable_error:n` In expansion only context, we cannot use the normal means of reporting errors. Instead, we feed \TeX an undefined control sequence, `\LaTeX3 error:`. It is thus interrupted, and shows the context, which thanks to the odd-looking `\use:n` is

```

<argument> \LaTeX3 error:
The error message.

```

In other words, \TeX is processing the argument of `\use:n`, which is `\LaTeX3 error: <error message>`. Then `_msg_expandable_error:w` cleans up. In fact, there is an extra subtlety: if the user inserts tokens for error recovery, they should be kept. Thus we also use an odd space character (with category code 7) and keep tokens until that space character, dropping everything else until `\q_stop`. The `\exp_end:` prevents losing braces

around the user-inserted text if any, and stops the expansion of `\exp:w`. The group is used to prevent `\LaTeX3-error:` from being globally equal to `\scan_stop:`.

```

8881 \group_begin:
8882 \cs_set_protected:Npn \__msg_tmp:w #1#2
8883 {
8884   \cs_new:Npn \__msg_expandable_error:n ##1
8885   {
8886     \exp:w
8887     \exp_after:wN \exp_after:wN
8888     \exp_after:wN \__msg_expandable_error:w
8889     \exp_after:wN \exp_after:wN
8890     \exp_after:wN \exp_end:
8891     \use:n { #1 #2 ##1 } #2
8892   }
8893   \cs_new:Npn \__msg_expandable_error:w ##1 #2 ##2 #2 {##1}
8894 }
8895 \exp_args:Ncx \__msg_tmp:w { LaTeX3-error: }
8896 { \char_generate:nn { ' } { 7 } }
8897 \group_end:

```

(End definition for `__msg_expandable_error:n` and `__msg_expandable_error:w`.)

```

\__msg_kernel_expandable_error:nnnnnn
\__msg_kernel_expandable_error:nnnnn
\__msg_kernel_expandable_error:nnnn
\__msg_kernel_expandable_error:nnn
\__msg_kernel_expandable_error:nn

```

The command built from the csname `\c_@@_text_prefix_tl LaTeX / #1 / #2` takes four arguments and builds the error text, which is fed to `__msg_expandable_error:n`.

```

8898 \cs_new:Npn \__msg_kernel_expandable_error:nnnnnn #1#2#3#4#5#6
8899 {
8900   \exp_args:Nf \__msg_expandable_error:n
8901   {
8902     \exp_args:NNc \exp_after:wN \exp_stop_f:
8903     { \c_@@_text_prefix_tl LaTeX / #1 / #2 }
8904     {#3} {#4} {#5} {#6}
8905   }
8906 }
8907 \cs_new:Npn \__msg_kernel_expandable_error:nnnnn #1#2#3#4#5
8908 {
8909   \__msg_kernel_expandable_error:nnnnnn
8910   {#1} {#2} {#3} {#4} {#5} { }
8911 }
8912 \cs_new:Npn \__msg_kernel_expandable_error:nnnn #1#2#3#4
8913 {
8914   \__msg_kernel_expandable_error:nnnnnn
8915   {#1} {#2} {#3} {#4} { } { }
8916 }
8917 \cs_new:Npn \__msg_kernel_expandable_error:nnn #1#2#3
8918 {
8919   \__msg_kernel_expandable_error:nnnnnn
8920   {#1} {#2} {#3} { } { } { }
8921 }
8922 \cs_new:Npn \__msg_kernel_expandable_error:nn #1#2
8923 {
8924   \__msg_kernel_expandable_error:nnnnnn
8925   {#1} {#2} { } { } { } { }
8926 }

```

(End definition for `_msg_kernel_expandable_error:nnnnnn` and others.)

```
8927 </initex | package>
```

17 l3file implementation

The following test files are used for this code: `m3file001`.

```
8928 <*initex | package>
```

```
8929 <@@=file>
```

17.1 File operations

`\g_file_curr_dir_str`
`\g_file_curr_ext_str`
`\g_file_curr_name_str` The name of the current file should be available at all times. For the format the file name needs to be picked up at the start of the run. In L^AT_EX 2_ε package mode the current file name is collected from `\@currname`.

```
8930 \str_new:N \g_file_curr_dir_str
8931 \str_new:N \g_file_curr_ext_str
8932 \str_new:N \g_file_curr_name_str
8933 <*initex>
8934 \tex_everyjob:D \exp_after:wN
8935 {
8936   \tex_the:D \tex_everyjob:D
8937   \str_gset:Nx \g_file_curr_name_str { \tex_jobname:D }
8938 }
8939 </initex>
8940 <*package>
8941 \cs_if_exist:NT \@currname
8942 { \str_gset_eq:NN \g_file_curr_name_str \@currname }
8943 </package>
```

(End definition for `\g_file_curr_dir_str`, `\g_file_curr_ext_str`, and `\g_file_curr_name_str`. These variables are documented on page 145.)

`\g__file_stack_seq` The input list of files is stored as a sequence stack. In package mode we can recover the information from the details held by L^AT_EX 2_ε (we must be in the preamble and loaded using `\usepackage` or `\RequirePackage`). As L^AT_EX 2_ε doesn't store directory and name separately, we stick to the same convention here.

```
8944 \seq_new:N \g__file_stack_seq
8945 <*package>
8946 \group_begin:
8947   \cs_set_protected:Npn \__file_tmp:w #1#2#3
8948   {
8949     \tl_if_blank:nTF {#1}
8950     {
8951       \cs_set:Npn \__file_tmp:w ##1 " ##2 " ##3 \q_stop { { } {##2} { } }
8952       \seq_gput_right:Nx \g__file_stack_seq
8953       {
8954         \exp_after:wN \__file_tmp:w \tex_jobname:D
8955         " \tex_jobname:D " \q_stop
8956       }
8957     }
8958   }
```

```

8959         \seq_gput_right:Nn \g__file_stack_seq { { } {#1} {#2} }
8960         \__file_tmp:w
8961     }
8962 }
8963 \cs_if_exist:NT \@currnamestack
8964 { \exp_after:wN \__file_tmp:w \@currnamestack }
8965 \group_end:
8966 \</package>

```

(End definition for `\g__file_stack_seq`.)

`\g__file_record_seq` The total list of files used is recorded separately from the current file stack, as nothing is ever popped from this list. The current file name should be included in the file list! In format mode, this is done at the very start of the \TeX run. In package mode we will eventually copy the contents of `\@filelist`.

```

8967 \seq_new:N \g__file_record_seq
8968 \< *initex>
8969 \tex_everyjob:D \exp_after:wN
8970 {
8971     \tex_the:D \tex_everyjob:D
8972     \seq_gput_right:NV \g__file_record_seq \g_file_curr_name_str
8973 }
8974 \< /initex>

```

(End definition for `\g__file_record_seq`.)

`\l__file_tmp_tl` Used as a short-term scratch variable.

```

8975 \tl_new:N \l__file_tmp_tl

```

(End definition for `\l__file_tmp_tl`.)

`\l__file_base_name_str` For storing the basename and full path whilst passing data internally.

```

8976 \str_new:N \l__file_base_name_str
8977 \str_new:N \l__file_full_name_str

```

(End definition for `\l__file_base_name_str` and `\l__file_full_name_str`.)

`\l__file_dir_str` Used in parsing a path into parts: in contrast to the above, these are never used outside of the current module.

```

8978 \str_new:N \l__file_dir_str
8979 \str_new:N \l__file_ext_str
8980 \str_new:N \l__file_name_str

```

(End definition for `\l__file_dir_str`, `\l__file_ext_str`, and `\l__file_name_str`.)

`\l_file_search_path_seq` The current search path.

```

8981 \seq_new:N \l_file_search_path_seq

```

(End definition for `\l_file_search_path_seq`. This variable is documented on page 145.)

`\l__file_tmp_seq` Scratch space for comma list conversion in package mode.

```

8982 \< *package>
8983 \seq_new:N \l__file_tmp_seq
8984 \< /package>

```


(End definition for \l__file_tmp_seq.)

__file_name_sanitiz:nN For converting a token list to a string where active characters are treated as strings from the start. The logic to the quoting normalisation is the same as used by \lualatexquotejobname: check for balanced ", and assuming they balance strip all of them out before quoting the entire name if it contains spaces.

```

8985 \cs_new_protected:Npn \__file_name_sanitiz:nN #1#2
8986 {
8987   \group_begin:
8988     \seq_map_inline:Nn \l_char_active_seq
8989     {
8990       \tl_set:Nx \l__file_tmp_tl { \iow_char:N ##1 }
8991       \char_set_active_eq:NN ##1 \l__file_tmp_tl
8992     }
8993     \tl_set:Nx \l__file_tmp_tl {#1}
8994     \tl_set:Nx \l__file_tmp_tl
8995     { \tl_to_str:N \l__file_tmp_tl }
8996     \exp_args:NNNV \group_end:
8997     \str_set:Nn #2 \l__file_tmp_tl
8998   }
8999 \cs_new_protected:Npn \__file_name_quote:nN #1#2
9000 {
9001   \str_set:Nx #2 {#1}
9002   \int_if_even:nF
9003   { 0 \tl_map_function:NN #2 \__file_name_quote_aux:n }
9004   {
9005     \_msg_kernel_error:nnx
9006     { kernel } { unbalanced-quote-in-filename } {#2}
9007   }
9008   \tl_remove_all:Nn #2 { " }
9009   \tl_if_in:NnT #2 { ~ }
9010   { \str_set:Nx #2 { " \exp_not:V #2 " } }
9011 }
9012 \cs_new:Npn \__file_name_quote_aux:n #1
9013 { \token_if_eq_charcode:NNT #1 " { + 1 } }

```

(End definition for __file_name_sanitiz:nN, __file_name_quote:nN, and __file_name_sanitiz_aux:n.)

\file_get_full_name:nN The way to test if a file exists is to try to open it: if it does not exist then T_EX reports end-of-file. A search is made looking at each potential path in turn (starting from the current directory). The first location is of course treated as the correct one: this is done by jumping to __prg_break_point:. If nothing is found, #2 is returned empty. A special case when there is no extension is that once the first location is found we test the existence of the file with .tex extension in that directory, and if it exists we include the .tex extension in the result.

```

9014 \cs_new_protected:Npn \file_get_full_name:nN #1#2
9015 {
9016   \__file_name_sanitiz:nN {#1} \l__file_base_name_str
9017   \__file_get_full_name_search:nN { } \use:n
9018   \seq_map_inline:Nn \l_file_search_path_seq
9019   { \__file_get_full_name_search:nN { ##1 / } \seq_map_break:n }
9020 }

```

```

9021 \cs_if_exist:NT \input@path
9022 {
9023   \tl_map_inline:Nn \input@path
9024   { \__file_get_full_name_search:nN { ##1 } \tl_map_break:n }
9025 }
9026 \endpackage
9027 \str_clear:N \l__file_full_name_str
9028 \__prg_break_point:
9029 \str_if_empty:NF \l__file_full_name_str
9030 {
9031   \exp_args:NV \file_parse_full_name:nNNN \l__file_full_name_str
9032   \l__file_dir_str \l__file_name_str \l__file_ext_str
9033   \str_if_empty:NT \l__file_ext_str
9034   {
9035     \__ior_open:No \g__file_internal_ior
9036     { \l__file_full_name_str .tex }
9037     \ior_if_eof:NF \g__file_internal_ior
9038     { \str_put_right:Nn \l__file_full_name_str { .tex } }
9039   }
9040 }
9041 \str_set_eq:NN #2 \l__file_full_name_str
9042 \ior_close:N \g__file_internal_ior
9043 }
9044 \cs_generate_variant:Nn \file_get_full_name:nN { V }
9045 \cs_new_protected:Npn \__file_get_full_name_search:nN #1#2
9046 {
9047   \__file_name_quote:nN
9048   { \tl_to_str:n {#1} \l__file_base_name_str }
9049   \l__file_full_name_str
9050   \__ior_open:No \g__file_internal_ior \l__file_full_name_str
9051   \ior_if_eof:NF \g__file_internal_ior { #2 { \__prg_break: } }
9052 }

```

(End definition for `\file_get_full_name:nN` and `__file_get_full_name_search:nN`. This function is documented on page 146.)

`\file_if_exist:nTF` The test for the existence of a file is a wrapper around the function to add a path to a file. If the file was found, the path contains something, whereas if the file was not located then the return value is empty.

```

9053 \prg_new_protected_conditional:Npnn \file_if_exist:n #1 { T , F , TF }
9054 {
9055   \file_get_full_name:nN {#1} \l__file_full_name_str
9056   \str_if_empty:NTF \l__file_full_name_str
9057   { \prg_return_false: }
9058   { \prg_return_true: }
9059 }

```

(End definition for `\file_if_exist:nTF`. This function is documented on page 145.)

`__file_missing:n` An error message for a missing file, also used in `\ior_open:Nn`.

```

9060 \cs_new_protected:Npn \__file_missing:n #1
9061 {
9062   \__file_name_sanitise:nN {#1} \l__file_base_name_str
9063   \__msg_kernel_error:nnx { kernel } { file-not-found }

```

```

9064     { \l__file_base_name_str }
9065 }

```

(End definition for _file_missing:n.)

```

\file_input:n Loading a file is done in a safe way, checking first that the file exists and loading only
\__file_input:n if it does. Push the file name on the \g__file_stack_seq, and add it to the file list,
\__file_input:V either \g__file_record_seq, or \@filelist in package mode.
\__file_input_push:n
\__file_input_pop:
\__file_input_pop:nnn
9066 \cs_new_protected:Npn \file_input:n #1
9067 {
9068   \file_get_full_name:nN {#1} \l__file_full_name_str
9069   \str_if_empty:NTF \l__file_full_name_str
9070   { \_file_missing:n {#1} }
9071   { \__file_input:V \l__file_full_name_str }
9072 }
9073 \cs_new_protected:Npn \__file_input:n #1
9074 {
9075   < *initex >
9076   \seq_gput_right:Nn \g__file_record_seq {#1}
9077   < /initex >
9078   < *package >
9079   \clist_if_exist:NTF \@filelist
9080   { \@addtofilelist {#1} }
9081   { \seq_gput_right:Nn \g__file_record_seq {#1} }
9082   < /package >
9083   \__file_input_push:n {#1}
9084   \tex_input:D #1 \c_space_tl
9085   \__file_input_pop:
9086 }
9087 \cs_generate_variant:Nn \__file_input:n { V }

```

Keeping a track of the file data is easy enough: we store the separated parts so we do not need to parse them twice.

```

9088 \cs_new_protected:Npn \__file_input_push:n #1
9089 {
9090   \seq_gpush:Nx \g__file_stack_seq
9091   {
9092     { \g_file_curr_dir_str }
9093     { \g_file_curr_name_str }
9094     { \g_file_curr_ext_str }
9095   }
9096   \file_parse_full_name:nNNN {#1}
9097   \l__file_dir_str \l__file_name_str \l__file_ext_str
9098   \str_gset_eq:NN \g_file_curr_dir_str \l__file_dir_str
9099   \str_gset_eq:NN \g_file_curr_name_str \l__file_name_str
9100   \str_gset_eq:NN \g_file_curr_ext_str \l__file_ext_str
9101 }
9102 \cs_new_protected:Npn \__file_input_pop:
9103 {
9104   \seq_gpop:NN \g__file_stack_seq \l__file_tmp_tl
9105   \exp_after:wN \__file_input_pop:nnn \l__file_tmp_tl
9106 }
9107 \cs_new_protected:Npn \__file_input_pop:nnn #1#2#3
9108 {

```

```

9109     \str_gset:Nn \g_file_curr_dir_str  {#1}
9110     \str_gset:Nn \g_file_curr_name_str {#2}
9111     \str_gset:Nn \g_file_curr_ext_str  {#3}
9112 }

```

(End definition for `\file_input:n` and others. This function is documented on page 146.)

```

\file_parse_full_name:nNNN
  \_file_parse_full_name_auxi:w
  \_file_parse_full_name_split:nNNNTF

```

Parsing starts by stripping off any surrounding quotes. Then find the directory #4 by splitting at the last /. (The auxiliary returns true/false depending on whether it found the delimiter.) We correct for the case of a file in the root /, as in that case we wish to keep the trailing (and only) slash. Then split the base name #5 at the last dot. If there was indeed a dot, #5 contains the name and #6 the extension without the dot, which we add back for convenience. In the special case of no extension given, the auxiliary stored the name into #6, we just have to move it to #5.

```

9113 \cs_new_protected:Npn \file_parse_full_name:nNNN #1#2#3#4
9114 {
9115   \exp_after:wN \_file_parse_full_name_auxi:w
9116   \tl_to_str:n { #1 " #1 " } \q_stop #2#3#4
9117 }
9118 \cs_new_protected:Npn \_file_parse_full_name_auxi:w #1 " #2 " #3 \q_stop #4#5#6
9119 {
9120   \_file_parse_full_name_split:nNNNTF {#2} / #4 #5
9121   { \str_if_empty:NT #4 { \str_set:Nn #4 { / } } }
9122   { }
9123   \exp_args:No \_file_parse_full_name_split:nNNNTF {#5} . #5 #6
9124   { \str_put_left:Nn #6 { . } }
9125   {
9126     \str_set_eq:NN #5 #6
9127     \str_clear:N #6
9128   }
9129 }
9130 \cs_new_protected:Npn \_file_parse_full_name_split:nNNNTF #1#2#3#4
9131 {
9132   \cs_set_protected:Npn \_file_tmp:w ##1 ##2 #2 ##3 \q_stop
9133   {
9134     \tl_if_empty:nTF {##3}
9135     {
9136       \str_set:Nn #4 {##2}
9137       \tl_if_empty:nTF {##1}
9138       {
9139         \str_clear:N #3
9140         \use_ii:nn
9141       }
9142       {
9143         \str_set:Nx #3 { \str_tail:n {##1} }
9144         \use_i:nn
9145       }
9146     }
9147     { \_file_tmp:w { ##1 #2 ##2 } ##3 \q_stop }
9148   }
9149   \_file_tmp:w { } #1 #2 \q_stop
9150 }

```

(End definition for `\file_parse_full_name:nNNN`, `_file_parse_full_name_auxi:w`, and `_file_parse_full_name_split:nNNNTF`. This function is documented on page 146.)

```

\file_show_list: A function to list all files used to the log, without duplicates. In package mode, if
\file_log_list: \@filelist is still defined, we need to take this list of file names into account (we
  \_file_list:N capture it \AtBeginDocument into \g\_file_record_seq), turning it to a string (this
\_file_list_aux:n does not affect the commas of this comma list).

9151 \cs_new_protected:Npn \file_show_list: { \_file_list:N \msg_show:nnxxxx }
9152 \cs_new_protected:Npn \file_log_list: { \_file_list:N \msg_log:nnxxxx }
9153 \cs_new_protected:Npn \_file_list:N #1
9154 {
9155   \seq_clear:N \l__file_tmp_seq
9156   \*package
9157   \clist_if_exist:NT \@filelist
9158   {
9159     \exp_args:NNx \seq_set_from_clist:Nn \l__file_tmp_seq
9160     { \tl_to_str:N \@filelist }
9161   }
9162   \*package
9163   \seq_concat:NNN \l__file_tmp_seq \l__file_tmp_seq \g__file_record_seq
9164   \seq_remove_duplicates:N \l__file_tmp_seq
9165   #1 { LaTeX/kernel } { file-list }
9166   { \seq_map_function:NN \l__file_tmp_seq \_file_list_aux:n } { } { } { }
9167 }
9168 \cs_new:Npn \_file_list_aux:n #1 { \iow_newline: #1 }

```

(End definition for \file_show_list: and others. These functions are documented on page 146.)

When used as a package, there is a need to hold onto the standard file list as well as the new one here. File names recorded in \@filelist must be turned to strings before being added to \g__file_record_seq.

```

9169 \*package
9170 \AtBeginDocument
9171 {
9172   \exp_args:NNx \seq_set_from_clist:Nn \l__file_tmp_seq
9173   { \tl_to_str:N \@filelist }
9174   \seq_gconcat:NNN \g__file_record_seq \g__file_record_seq \l__file_tmp_seq
9175 }
9176 \*package

```

17.2 Input operations

```
9177 \@@=ior
```

17.2.1 Variables and constants

\c_term_ior Reading from the terminal (with a prompt) is done using a positive but non-existent stream number. Unlike writing, there is no concept of reading from the log.

```
9178 \int_const:Nn \c_term_ior { 16 }
```

(End definition for \c_term_ior. This variable is documented on page 153.)

\g_ior_streams_seq A list of the currently-available input streams to be used as a stack. In format mode, all streams (from 0 to 15) are available, while the package requests streams to L^AT_EX 2_ε as they are needed (initially none are needed), so the starting point varies!

```

9179 \seq_new:N \g_ior_streams_seq
9180 \*initex
9181 \seq_gset_split:Nnn \g_ior_streams_seq { , }

```

```

9182 { 0 , 1 , 2 , 3 , 4 , 5 , 6 , 7 , 8 , 9 , 10 , 11 , 12 , 13 , 14 , 15 }
9183 </initex>

```

(End definition for `\g__ior_streams_seq`.)

`\l__ior_stream_tl` Used to recover the raw stream number from the stack.

```

9184 \tl_new:N \l__ior_stream_tl

```

(End definition for `\l__ior_stream_tl`.)

`\g__ior_streams_prop` The name of the file attached to each stream is tracked in a property list. To get the correct number of reserved streams in package mode the underlying mechanism needs to be queried. For $\text{\LaTeX} 2_{\epsilon}$ and plain \TeX this data is stored in `\count16`: with the `etex` package loaded we need to subtract 1 as the register holds the number of the next stream to use. In `ConTeXt`, we need to look at `\count38` but there is no subtraction: like the original plain \TeX / $\text{\LaTeX} 2_{\epsilon}$ mechanism it holds the value of the *last* stream allocated.

```

9185 \prop_new:N \g__ior_streams_prop
9186 (*package)
9187 \int_step_inline:nnnn
9188 { 0 }
9189 { 1 }
9190 {
9191   \cs_if_exist:NTF \normalend
9192   { \tex_count:D 38 ~ }
9193   {
9194     \tex_count:D 16 ~ %
9195     \cs_if_exist:NT \loccount { - 1 }
9196   }
9197 }
9198 {
9199   \prop_gput:Nnn \g__ior_streams_prop {#1} { Reserved-by~format }
9200 }
9201 </package>

```

(End definition for `\g__ior_streams_prop`.)

17.2.2 Stream management

`\ior_new:N` Reserving a new stream is done by defining the name as equal to using the terminal.

```

\ior_new:c
9202 \cs_new_protected:Npn \ior_new:N #1 { \cs_new_eq:NN #1 \c_term_ior }
9203 \cs_generate_variant:Nn \ior_new:N { c }

```

(End definition for `\ior_new:N`. This function is documented on page 147.)

`\ior_open:Nn` Use the conditional version, with an error if the file is not found.

```

\ior_open:cn
9204 \cs_new_protected:Npn \ior_open:Nn #1#2
9205 { \ior_open:NnF #1 {#2} { \__file_missing:n {#2} } }
9206 \cs_generate_variant:Nn \ior_open:Nn { c }

```

(End definition for `\ior_open:Nn`. This function is documented on page 147.)

`\ior_open:NnTF` An auxiliary searches for the file in the \TeX , \LaTeX 2_ϵ and \LaTeX 3 paths. Then pass the file found to the lower-level function which deals with streams. The `full_name` is empty when the file is not found.

```

9207 \prg_new_protected_conditional:Npnn \ior_open:Nn #1#2 { T , F , TF }
9208 {
9209   \file_get_full_name:nN {#2} \l__file_full_name_str
9210   \str_if_empty:NTF \l__file_full_name_str
9211     { \prg_return_false: }
9212     {
9213       \__ior_open:No #1 \l__file_full_name_str
9214       \prg_return_true:
9215     }
9216 }
9217 \cs_generate_variant:Nn \ior_open:NnT { c }
9218 \cs_generate_variant:Nn \ior_open:NnF { c }
9219 \cs_generate_variant:Nn \ior_open:NnTF { c }

```

(End definition for `\ior_open:NnTF`. This function is documented on page 147.)

`__ior_new:N` In package mode, streams are reserved using `\newread` before they can be managed by `ior`. To prevent `ior` from being affected by redefinitions of `\newread` (such as done by the third-party package `morewrites`), this macro is saved here under a private name. The complicated code ensures that `__ior_new:N` is not `\outer` despite plain \TeX 's `\newread` being `\outer`.

```

9220 \*package
9221 \exp_args:NNf \cs_new_protected:Npn \__ior_new:N
9222   { \exp_args:NNc \exp_after:wN \exp_stop_f: { newread } }
9223 \*package

```

(End definition for `__ior_new:N`.)

`__ior_open:Nn` The stream allocation itself uses the fact that there is a list of all of those available, so allocation is simply a question of using the number at the top of the list. In package mode, life gets more complex as it's important to keep things in sync. That is done using a two-part approach: any streams that have already been taken up by `ior` but are now free are tracked, so we first try those. If that fails, ask plain \TeX or \LaTeX 2_ϵ for a new stream and use that number (after a bit of conversion).

```

9224 \cs_new_protected:Npn \__ior_open:Nn #1#2
9225 {
9226   \ior_close:N #1
9227   \seq_gpop:NNTF \g__ior_streams_seq \l__ior_stream_tl
9228     { \__ior_open_stream:Nn #1 {#2} }
9229   \*initex
9230   { \__msg_kernel_fatal:nn { kernel } { input-streams-exhausted } }
9231 \*initex
9232 \*package
9233 {
9234   \__ior_new:N #1
9235   \tl_set:Nx \l__ior_stream_tl { \int_eval:n {#1} }
9236   \__ior_open_stream:Nn #1 {#2}
9237 }
9238 \*package
9239 }

```

```

9240 \cs_generate_variant:Nn \__ior_open:Nn { No }
9241 \cs_new_protected:Npn \__ior_open_stream:Nn #1#2
9242 {
9243   \tex_global:D \tex_chardef:D #1 = \l__ior_stream_tl \scan_stop:
9244   \prop_gput:Nvn \g__ior_streams_prop #1 {#2}
9245   \tex_openin:D #1 #2 \scan_stop:
9246 }

```

(End definition for `__ior_open:Nn` and `__ior_open_stream:Nn`.)

`\ior_close:N` Closing a stream means getting rid of it at the T_EX level and removing from the various data structures. Unless the name passed is an invalid stream number (outside the range [0, 15]), it can be closed. On the other hand, it only gets added to the stack if it was not already there, to avoid duplicates building up.

`\ior_close:c`

```

9247 \cs_new_protected:Npn \ior_close:N #1
9248 {
9249   \int_compare:nT { -1 < #1 < \c_term_ior }
9250   {
9251     \tex_closein:D #1
9252     \prop_gremove:Nv \g__ior_streams_prop #1
9253     \seq_if_in:NvF \g__ior_streams_seq #1
9254     { \seq_gpush:Nv \g__ior_streams_seq #1 }
9255     \cs_gset_eq:NN #1 \c_term_ior
9256   }
9257 }
9258 \cs_generate_variant:Nn \ior_close:N { c }

```

(End definition for `\ior_close:N`. This function is documented on page 147.)

`\ior_show_list:` Show the property lists, but with some “pretty printing”. See the `l3msg` module. The first argument of the message is `ior` (as opposed to `iow`) and the second is empty if no read stream is open and non-empty (the list of streams formatted using `\msg_show_item_unbraced:nn`) otherwise. The code of the message `show-streams` takes care of translating `ior/iow` to English.

`\ior_log_list:`
`__ior_list:N`

```

9259 \cs_new_protected:Npn \ior_show_list: { \__ior_list:N \msg_show:nnxxxx }
9260 \cs_new_protected:Npn \ior_log_list: { \__ior_list:N \msg_log:nnxxxx }
9261 \cs_new_protected:Npn \__ior_list:N #1
9262 {
9263   #1 { LaTeX / kernel } { show-streams }
9264   { ior }
9265   {
9266     \prop_map_function:NN \g__ior_streams_prop
9267     \msg_show_item_unbraced:nn
9268   }
9269   { } { }
9270 }

```

(End definition for `\ior_show_list:`, `\ior_log_list:`, and `__ior_list:N`. These functions are documented on page 147.)

17.2.3 Reading input

`\if_eof:w` The primitive conditional

```

9271 \cs_new_eq:NN \if_eof:w \tex_ifeof:D

```


(End definition for `\if_eof:w`. This function is documented on page 153.)

`\ior_if_eof_p:N` To test if some particular input stream is exhausted the following conditional is provided.
`\ior_if_eof:NTF` The primitive test can only deal with numbers in the range [0,15] so we catch outliers (they are exhausted).

```

9272 \prg_new_conditional:Npnn \ior_if_eof:N #1 { p , T , F , TF }
9273 {
9274   \cs_if_exist:NTF #1
9275   {
9276     \int_compare:nTF { -1 < #1 < \c_term_ior }
9277     {
9278       \if_eof:w #1
9279       \prg_return_true:
9280     \else:
9281       \prg_return_false:
9282     \fi:
9283   }
9284   { \prg_return_true: }
9285 }
9286 { \prg_return_true: }
9287 }
```

(End definition for `\ior_if_eof:NTF`. This function is documented on page 150.)

`\ior_get:NN` And here we read from files.

```

9288 \cs_new_protected:Npn \ior_get:NN #1#2
9289 { \tex_read:D #1 to #2 }
```

(End definition for `\ior_get:NN`. This function is documented on page 148.)

`\ior_str_get:NN` Reading as strings is a more complicated wrapper, as we wish to remove the endline character.

```

9290 \cs_new_protected:Npn \ior_str_get:NN #1#2
9291 {
9292   \use:x
9293   {
9294     \int_set:Nn \tex_endlinechar:D { -1 }
9295     \exp_not:n { \etex_readline:D #1 to #2 }
9296     \int_set:Nn \tex_endlinechar:D { \int_use:N \tex_endlinechar:D }
9297   }
9298 }
```

(End definition for `\ior_str_get:NN`. This function is documented on page 148.)

`\ior_map_break:` Usual map breaking functions.

```

\ior_map_break:n
9299 \cs_new:Npn \ior_map_break:
9300 { \__prg_map_break:Nn \ior_map_break: { } }
9301 \cs_new:Npn \ior_map_break:n
9302 { \__prg_map_break:Nn \ior_map_break: }
```

(End definition for `\ior_map_break:` and `\ior_map_break:n`. These functions are documented on page 149.)

```

\ior_map_inline:Nn Mapping to an input stream can be done on either a token or a string basis, hence the
\ior_str_map_inline:Nn set up. Within that, there is a check to avoid reading past the end of a file, hence the
\__ior_map_inline:NNn two applications of \ior_if_eof:N. This mapping cannot be nested with twice the same
\__ior_map_inline:NNNn stream, as the stream has only one “current line”.
\__ior_map_inline_loop:NNN
  \l__ior_internal_tl
9303 \cs_new_protected:Npn \ior_map_inline:Nn
9304 { \__ior_map_inline:NNn \ior_get:NN }
9305 \cs_new_protected:Npn \ior_str_map_inline:Nn
9306 { \__ior_map_inline:NNn \ior_str_get:NN }
9307 \cs_new_protected:Npn \__ior_map_inline:NNn
9308 {
9309   \int_gincr:N \g__prg_map_int
9310   \exp_args:Nc \__ior_map_inline:NNNn
9311     { __prg_map_ \int_use:N \g__prg_map_int :n }
9312 }
9313 \cs_new_protected:Npn \__ior_map_inline:NNNn #1#2#3#4
9314 {
9315   \cs_gset_protected:Npn #1 ##1 {#4}
9316   \ior_if_eof:NF #3 { \__ior_map_inline_loop:NNN #1#2#3 }
9317   \__prg_break_point:Nn \ior_map_break:
9318     { \int_gdecr:N \g__prg_map_int }
9319 }
9320 \cs_new_protected:Npn \__ior_map_inline_loop:NNN #1#2#3
9321 {
9322   #2 #3 \l__ior_internal_tl
9323   \ior_if_eof:NF #3
9324   {
9325     \exp_args:No #1 \l__ior_internal_tl
9326     \__ior_map_inline_loop:NNN #1#2#3
9327   }
9328 }
9329 \tl_new:N \l__ior_internal_tl

```

(End definition for \ior_map_inline:Nn and others. These functions are documented on page 149.)

\g__file_internal_ior Needed by the higher-level code, but cannot be created until here.

```
9330 \ior_new:N \g__file_internal_ior
```

(End definition for \g__file_internal_ior.)

17.3 Output operations

```
9331 <@@=iow>
```

There is a lot of similarity here to the input operations, at least for many of the basics. Thus quite a bit is copied from the earlier material with minor alterations.

17.3.1 Variables and constants

\c_log_iow Here we allocate two output streams for writing to the transcript file only (\c_log_iow) and to both the terminal and transcript file (\c_term_iow). Recent LuaTeX provide 128 write streams; we also use \c_term_iow as the first non-allowed write stream so its value depends on the engine.

```

9332 \int_const:Nn \c_log_iow { -1 }
9333 \int_const:Nn \c_term_iow
9334 {

```

```

9335 \cs_if_exist:NTF \luatex_directlua:D
9336 {
9337     \int_compare:nNnTF \luatex luatexversion:D > { 80 }
9338         { 128 }
9339         { 16 }
9340     }
9341     { 16 }
9342 }

```

(End definition for `\c_log_iow` and `\c_term_iow`. These variables are documented on page 153.)

`\g__iow_streams_seq` A list of the currently-available output streams to be used as a stack.

```

9343 \seq_new:N \g__iow_streams_seq
9344 \*initex>
9345 \use:x
9346 {
9347     \exp_not:n { \seq_gset_split:Nnn \g__iow_streams_seq { } }
9348     {
9349         \int_step_function:nnnN { 0 } { 1 } { \c_term_iow }
9350         \prg_do_nothing:
9351     }
9352 }
9353 \</initex>

```

(End definition for `\g__iow_streams_seq`.)

`\l__iow_stream_tl` Used to recover the raw stream number from the stack.

```

9354 \tl_new:N \l__iow_stream_tl

```

(End definition for `\l__iow_stream_tl`.)

`\g__iow_streams_prop` As for reads with the appropriate adjustment of the register numbers to check on.

```

9355 \prop_new:N \g__iow_streams_prop
9356 \*package>
9357 \int_step_inline:nnnn
9358 { 0 }
9359 { 1 }
9360 {
9361     \cs_if_exist:NTF \normalend
9362     { \tex_count:D 39 ~ }
9363     {
9364         \tex_count:D 17 ~
9365         \cs_if_exist:NT \loccount { - 1 }
9366     }
9367 }
9368 {
9369     \prop_gput:Nnn \g__iow_streams_prop {#1} { Reserved-by~format }
9370 }
9371 \</package>

```

(End definition for `\g__iow_streams_prop`.)

17.4 Stream management

\iow_new:N Reserving a new stream is done by defining the name as equal to writing to the terminal:
\iow_new:c odd but at least consistent.

```
9372 \cs_new_protected:Npn \iow_new:N #1 { \cs_new_eq:NN #1 \c_term_iow }
9373 \cs_generate_variant:Nn \iow_new:N { c }
```

(End definition for \iow_new:N. This function is documented on page 147.)

__iow_new:N As for read streams, copy \newwrite in package mode, making sure that it is not \outer.

```
9374 \*package
9375 \exp_args:NNf \cs_new_protected:Npn \__iow_new:N
9376 { \exp_args:NNc \exp_after:wN \exp_stop_f: { newwrite } }
9377 \*package
```

(End definition for __iow_new:N.)

\iow_open:Nn The same idea as for reading, but without the path and without the need to allow for a
\iow_open:cn conditional version.

```
\__iow_open_stream:Nn 9378 \cs_new_protected:Npn \iow_open:Nn #1#2
\__iow_open_stream:NV 9379 {
9380   \__file_name_sanitise:nN {#2} \l__file_base_name_str
9381   \iow_close:N #1
9382   \seq_gpop:NNTF \g__iow_streams_seq \l__iow_stream_tl
9383   { \__iow_open_stream:NV #1 \l__file_base_name_str }
9384 \*initex
9385 { \__msg_kernel_fatal:nn { kernel } { output-streams-exhausted } }
9386 \*initex
9387 \*package
9388 {
9389   \__iow_new:N #1
9390   \tl_set:Nx \l__iow_stream_tl { \int_eval:n {#1} }
9391   \__iow_open_stream:NV #1 \l__file_base_name_str
9392 }
9393 \*package
9394 }
9395 \cs_generate_variant:Nn \iow_open:Nn { c }
9396 \cs_new_protected:Npn \__iow_open_stream:Nn #1#2
9397 {
9398   \tex_global:D \tex_chardef:D #1 = \l__iow_stream_tl \scan_stop:
9399   \prop_gput:NVn \g__iow_streams_prop #1 {#2}
9400   \tex_immediate:D \tex_openout:D #1 #2 \scan_stop:
9401 }
9402 \cs_generate_variant:Nn \__iow_open_stream:Nn { NV }
```

(End definition for \iow_open:Nn and __iow_open_stream:Nn. This function is documented on page 147.)

\iow_close:N Closing a stream is not quite the reverse of opening one. First, the close operation is
\iow_close:c easier than the open one, and second as the stream is actually a number we can use it directly to show that the slot has been freed up.

```
9403 \cs_new_protected:Npn \iow_close:N #1
9404 {
9405   \int_compare:nT { - \c_log_iow < #1 < \c_term_iow }
9406   {
```

```

9407     \tex_immediate:D \tex_closeout:D #1
9408     \prop_gremove:NV \g__iow_streams_prop #1
9409     \seq_if_in:NVF \g__iow_streams_seq #1
9410     { \seq_gpush:NV \g__iow_streams_seq #1 }
9411     \cs_gset_eq:NN #1 \c_term_iow
9412   }
9413 }
9414 \cs_generate_variant:Nn \iow_close:N { c }

```

(End definition for `\iow_close:N`. This function is documented on page 147.)

```

\iow_show_list: Done as for input, but with a copy of the auxiliary so the name is correct.
\iow_log_list:
\_iow_list:N
9415 \cs_new_protected:Npn \iow_show_list: { \_iow_list:N \msg_show:nnxxxx }
9416 \cs_new_protected:Npn \iow_log_list: { \_iow_list:N \msg_log:nnxxxx }
9417 \cs_new_protected:Npn \_iow_list:N #1
9418 {
9419   #1 { LaTeX / kernel } { show-streams }
9420   { iow }
9421   {
9422     \prop_map_function:NN \g__iow_streams_prop
9423     \msg_show_item_unbraced:nn
9424   }
9425   { } { }
9426 }

```

(End definition for `\iow_show_list:`, `\iow_log_list:`, and `_iow_list:N`. These functions are documented on page 147.)

17.4.1 Deferred writing

```

\iow_shipout_x:Nn First the easy part, this is the primitive, which expects its argument to be braced.
\iow_shipout_x:Nx
\iow_shipout_x:cn
\iow_shipout_x:cx
9427 \cs_new_protected:Npn \iow_shipout_x:Nn #1#2
9428 { \tex_write:D #1 {#2} }
9429 \cs_generate_variant:Nn \iow_shipout_x:Nn { c, Nx, cx }

```

(End definition for `\iow_shipout_x:Nn`. This function is documented on page 151.)

```

\iow_shipout:Nn With  $\varepsilon$ -TeX available deferred writing without expansion is easy.
\iow_shipout:Nx
\iow_shipout:cn
\iow_shipout:cx
9430 \cs_new_protected:Npn \iow_shipout:Nn #1#2
9431 { \tex_write:D #1 { \exp_not:n {#2} } }
9432 \cs_generate_variant:Nn \iow_shipout:Nn { c, Nx, cx }

```

(End definition for `\iow_shipout:Nn`. This function is documented on page 151.)

17.4.2 Immediate writing

`_iow_with:Nnn` If the integer `#1` is equal to `#2`, just leave `#3` in the input stream. Otherwise, pass the old value to an auxiliary, which sets the integer to the new value, runs the code, and restores the integer.

```

9433 \cs_new_protected:Npn \_iow_with:Nnn #1#2
9434 {
9435   \int_compare:nNnTF {#1} = {#2}
9436   { \use:n }
9437   { \exp_args:No \_iow_with_aux:nNnn { \int_use:N #1 } #1 {#2} }
9438 }

```

```

9439 \cs_new_protected:Npn \__iow_with_aux:nNnn #1#2#3#4
9440 {
9441   \int_set:Nn #2 {#3}
9442   #4
9443   \int_set:Nn #2 {#1}
9444 }

```

(End definition for `__iow_with:Nnn` and `__iow_with_aux:nNnn`.)

`\iow_now:Nn` This routine writes the second argument onto the output stream without expansion. If **`\iow_now:Nx`** this stream isn't open, the output goes to the terminal instead. If the first argument is **`\iow_now:cn`** no output stream at all, we get an internal error. We don't use the expansion done by **`\iow_now:cx`** `\write` to get the `Nx` variant, because it differs in subtle ways from `x`-expansion, namely, macro parameter characters would not need to be doubled. We set the `\newlinechar` to 10 using `__iow_with:Nnn` to support formats such as plain `TeX`: otherwise, `\iow_newline` would not work. We do not do this for `\iow_shipout:Nn` or `\iow_shipout_x:Nn`, as `TeX` looks at the value of the `\newlinechar` at shipout time in those cases.

```

9445 \cs_new_protected:Npn \iow_now:Nn #1#2
9446 {
9447   \__iow_with:Nnn \tex_newlinechar:D { '^J }
9448   { \tex_immediate:D \tex_write:D #1 { \exp_not:n {#2} } }
9449 }
9450 \cs_generate_variant:Nn \iow_now:Nn { c, Nx, cx }

```

(End definition for `\iow_now:Nn`. This function is documented on page 150.)

`\iow_log:n` Writing to the log and the terminal directly are relatively easy.
`\iow_log:x`
`\iow_term:n`
`\iow_term:x`

```

9451 \cs_set_protected:Npn \iow_log:x { \iow_now:Nx \c_log_iow }
9452 \cs_new_protected:Npn \iow_log:n { \iow_now:Nn \c_log_iow }
9453 \cs_set_protected:Npn \iow_term:x { \iow_now:Nx \c_term_iow }
9454 \cs_new_protected:Npn \iow_term:n { \iow_now:Nn \c_term_iow }

```

(End definition for `\iow_log:n` and `\iow_term:n`. These functions are documented on page 150.)

17.4.3 Special characters for writing

`\iow_newline:` Global variable holding the character that forces a new line when something is written to an output stream.

```

9455 \cs_new:Npn \iow_newline: { '^J }

```

(End definition for `\iow_newline:`. This function is documented on page 151.)

`\iow_char:N` Function to write any escaped char to an output stream.

```

9456 \cs_new_eq:NN \iow_char:N \cs_to_str:N

```

(End definition for `\iow_char:N`. This function is documented on page 151.)

17.4.4 Hard-wrapping lines to a character count

The code here implements a generic hard-wrapping function. This is used by the messaging system, but is designed such that it is available for other uses.

\l_iow_line_count_int This is the “raw” number of characters in a line which can be written to the terminal. The standard value is the line length typically used by T_EXLive and MikT_EX.

```
9457 \int_new:N \l_iow_line_count_int
9458 \int_set:Nn \l_iow_line_count_int { 78 }
```

(End definition for \l_iow_line_count_int. This variable is documented on page 152.)

\l__iow_newline_tl The token list inserted to produce a new line, with the *⟨run-on text⟩*.

```
9459 \tl_new:N \l__iow_newline_tl
```

(End definition for \l__iow_newline_tl.)

\l__iow_line_target_int This stores the target line count: the full number of characters in a line, minus any part for a leader at the start of each line.

```
9460 \int_new:N \l__iow_line_target_int
```

(End definition for \l__iow_line_target_int.)

__iow_set_indent:n The **one_indent** variables hold one indentation marker and its length. The **__iow_unindent:w** auxiliary removes one indentation. The function **__iow_set_indent:n** (that could possibly be public) sets the indentation in a consistent way. We set it to four spaces by default.

```
9461 \tl_new:N \l__iow_one_indent_tl
9462 \int_new:N \l__iow_one_indent_int
9463 \cs_new:Npn \__iow_unindent:w { }
9464 \cs_new_protected:Npn \__iow_set_indent:n #1
9465 {
9466   \tl_set:Nx \l__iow_one_indent_tl
9467   { \exp_args:No \__str_to_other_fast:n { \tl_to_str:n {#1} } }
9468   \int_set:Nn \l__iow_one_indent_int { \str_count:N \l__iow_one_indent_tl }
9469   \exp_last_unbraced:NNo
9470   \cs_set:Npn \__iow_unindent:w \l__iow_one_indent_tl { }
9471 }
9472 \exp_args:Nx \__iow_set_indent:n { \prg_replicate:nn { 4 } { ~ } }
```

(End definition for __iow_set_indent:n and others.)

\l__iow_indent_tl The current indentation (some copies of **\l__iow_one_indent_tl**) and its number of characters.

```
9473 \tl_new:N \l__iow_indent_tl
9474 \int_new:N \l__iow_indent_int
```

(End definition for \l__iow_indent_tl and \l__iow_indent_int.)

\l__iow_line_tl These hold the current line of text and a partial line to be added to it, respectively.

```
9475 \tl_new:N \l__iow_line_tl
9476 \tl_new:N \l__iow_line_part_tl
```

(End definition for \l__iow_line_tl and \l__iow_line_part_tl.)

`\l__iow_line_break_bool` Indicates whether the line was broken precisely at a chunk boundary.

```

9477 \bool_new:N \l__iow_line_break_bool

(End definition for \l__iow_line_break_bool.)

```

`\l__iow_wrap_tl` Used for the expansion step before detokenizing, and for the output from wrapping text: fully expanded and with lines which are not overly long.

```

9478 \tl_new:N \l__iow_wrap_tl

(End definition for \l__iow_wrap_tl.)

```

`\c__iow_wrap_marker_tl` Every special action of the wrapping code is starts with the same recognizable string, `\c__iow_wrap_marker_tl`. Upon seeing that “word”, the wrapping code reads one space-delimited argument to know what operation to perform. The setting of `\escapechar` here is not very important, but makes `\c__iow_wrap_marker_tl` look marginally nicer.

```

9479 \group_begin:
9480   \int_set:Nn \tex_escapechar:D { -1 }
9481   \tl_const:Nx \c__iow_wrap_marker_tl
9482     { \tl_to_str:n { \^^I \^^O \^^W \^^_ \^^W \^^R \^^A \^^P } }
9483 \group_end:
9484 \tl_map_inline:nn
9485   { { end } { newline } { indent } { unindent } }
9486   {
9487     \tl_const:cx { c__iow_wrap_ #1 _marker_tl }
9488     {
9489       \c__iow_wrap_marker_tl
9490       #1
9491       \c_catcode_other_space_tl
9492     }
9493   }

(End definition for \c__iow_wrap_marker_tl and others.)

```

`\iow_indent:n` We set `\iow_indent:n` to produce an error when outside messages. Within wrapped message, it is set to `__iow_indent:n` when valid and otherwise to `__iow_indent_error:n`.

`__iow_indent:n` The first places the instruction for increasing the indentation before its argument, and the instruction for unindenting afterwards. The second produces an error expandably.

`__iow_indent_error:n` Note that there are no forced line-break, so the indentation only changes when the next line is started.

```

9494 \cs_new_protected:Npn \iow_indent:n #1
9495   {
9496     \__msg_kernel_error:nnnnn { kernel } { iow-indent }
9497     { \iow_wrap:nnnN } { \iow_indent:n } { #1 }
9498     #1
9499   }
9500 \cs_new:Npx \__iow_indent:n #1
9501   {
9502     \c__iow_wrap_indent_marker_tl
9503     #1
9504     \c__iow_wrap_unindent_marker_tl
9505   }
9506 \cs_new:Npn \__iow_indent_error:n #1
9507   {
9508     \__msg_kernel_expandable_error:nnnnn { kernel } { iow-indent }

```



```

9509     { \iow_wrap:nnnN } { \iow_indent:n } {#1}
9510     #1
9511 }

```

(End definition for `\iow_indent:n`, `__iow_indent:n`, and `__iow_indent_error:n`. This function is documented on page 152.)

`\iow_wrap:nnnN` The main wrapping function works as follows. First give `\`, `_` and other formatting commands the correct definition for messages and perform the given setup #3. The definition of `_` uses an “other” space rather than a normal space, because the latter might be absorbed by T_EX to end a number or other f-type expansions.

```

9512 \cs_new_protected:Npn \iow_wrap:nnnN #1#2#3#4
9513 {
9514   \group_begin:
9515   \int_set:Nn \tex_escapechar:D { -1 }
9516   \cs_set:Npx \{ { \token_to_str:N \{ }
9517   \cs_set:Npx \# { \token_to_str:N \# }
9518   \cs_set:Npx \} { \token_to_str:N \} }
9519   \cs_set:Npx \% { \token_to_str:N \% }
9520   \cs_set:Npx \~ { \token_to_str:N \~ }
9521   \int_set:Nn \tex_escapechar:D { 92 }
9522   \cs_set_eq:NN \ \ \iow_newline:
9523   \cs_set_eq:NN \ \_ \c_catcode_other_space_tl
9524   \cs_set_eq:NN \iow_indent:n \__iow_indent:n
9525   #3

```

Then fully-expand the input: in package mode, the expansion uses L^AT_EX 2_ε’s `\protect` mechanism in the same way as `\typeout`. In generic mode this setting is useless but harmless. As soon as the expansion is done, reset `\iow_indent:n` to its error definition: it only works in the first argument of `\iow_wrap:nnnN`.

```

9526 <package> \cs_set_eq:NN \protect \token_to_str:N
9527 \tl_set:Nx \l__iow_wrap_tl {#1}
9528 \cs_set_eq:NN \iow_indent:n \__iow_indent_error:n

```

Afterwards, set the newline marker (two assignments to fully expand, then convert to a string) and initialize the target count for lines (the first line has target count `\l_iow_line_count_int` instead).

```

9529 \tl_set:Nx \l__iow_newline_tl { \iow_newline: #2 }
9530 \tl_set:Nx \l__iow_newline_tl { \tl_to_str:N \l__iow_newline_tl }
9531 \int_set:Nn \l__iow_line_target_int
9532 { \l_iow_line_count_int - \str_count:N \l__iow_newline_tl + 1 }

```

There is then a loop over the input, which stores the wrapped result in `\l__iow_wrap_tl`. After the loop, the resulting text is passed on to the function which has been given as a post-processor. The `\tl_to_str:N` step converts the “other” spaces back to normal spaces. The f-expansion removes a leading space from `\l__iow_wrap_tl`.

```

9533 \__iow_wrap_do:
9534 \exp_args:NNf \group_end:
9535 #4 { \tl_to_str:N \l__iow_wrap_tl }
9536 }

```

(End definition for `\iow_wrap:nnnN`. This function is documented on page 152.)

`__iow_wrap_do:` Escape spaces and change newlines to `\c__iow_wrap_newline_marker_tl`. Set up a few variables, in particular the initial value of `\l__iow_wrap_tl`: the space stops the `f`-expansion of the main wrapping function and `\use_none:n` removes a newline marker inserted by later code. The main loop consists of repeatedly calling the `chunk` auxiliary to wrap chunks delimited by (newline or indentation) markers.

```

9537 \cs_new_protected:Npn \__iow_wrap_do:
9538 {
9539   \tl_set:Nx \l__iow_wrap_tl
9540   {
9541     \exp_args:No \__str_to_other_fast:n \l__iow_wrap_tl
9542     \c__iow_wrap_end_marker_tl
9543   }
9544   \tl_set:Nx \l__iow_wrap_tl
9545   {
9546     \exp_after:wN \__iow_wrap_fix_newline:w \l__iow_wrap_tl
9547     ^^J \q_nil ^^J \q_stop
9548   }
9549   \exp_after:wN \__iow_wrap_start:w \l__iow_wrap_tl
9550 }
9551 \cs_new:Npn \__iow_wrap_fix_newline:w #1 ^^J #2 ^^J
9552 {
9553   #1
9554   \if_meaning:w \q_nil #2
9555   \use_i_delimit_by_q_stop:nw
9556   \fi:
9557   \c__iow_wrap_newline_marker_tl
9558   \__iow_wrap_fix_newline:w #2 ^^J
9559 }
9560 \cs_new_protected:Npn \__iow_wrap_start:w
9561 {
9562   \bool_set_false:N \l__iow_line_break_bool
9563   \tl_clear:N \l__iow_line_tl
9564   \tl_clear:N \l__iow_line_part_tl
9565   \tl_set:Nn \l__iow_wrap_tl { ~ \use_none:n }
9566   \int_zero:N \l__iow_indent_int
9567   \tl_clear:N \l__iow_indent_tl
9568   \__iow_wrap_chunk:nw { \l__iow_line_count_int }
9569 }

```

(End definition for `__iow_wrap_do:`, `__iow_wrap_fix_newline:w`, and `__iow_wrap_start:w`.)

`__iow_wrap_chunk:nw` The `chunk` and `next` auxiliaries are defined indirectly to obtain the expansions of `\c_catcode_other_space_tl` and `\c__iow_wrap_marker_tl` in their definition. The `next` auxiliary calls a function corresponding to the type of marker (its `##2`), which can be `newline` or `indent` or `unindent` or `end`. The first argument of the `chunk` auxiliary is a target number of characters and the second is some string to wrap. If the chunk is empty simply call `next`. Otherwise, set up a call to `__iow_wrap_line:nw`, including the indentation if the current line is empty, and including a trailing space (`#1`) before the `__iow_wrap_end_chunk:w` auxiliary.

```

9570 \cs_set_protected:Npn \__iow_tmp:w #1#2
9571 {
9572   \cs_new_protected:Npn \__iow_wrap_chunk:nw ##1##2 #2
9573   {

```

```

9574 \tl_if_empty:nTF {##2}
9575 {
9576   \tl_clear:N \l__iow_line_part_tl
9577   \__iow_wrap_next:nw {##1}
9578 }
9579 {
9580   \tl_if_empty:NTF \l__iow_line_tl
9581   {
9582     \__iow_wrap_line:nw
9583     { \l__iow_indent_tl }
9584     ##1 - \l__iow_indent_int ;
9585   }
9586   { \__iow_wrap_line:nw { } ##1 ; }
9587   ##2 #1
9588   \__iow_wrap_end_chunk:w 7 6 5 4 3 2 1 0 \q_stop
9589 }
9590 }
9591 \cs_new_protected:Npn \__iow_wrap_next:nw ##1##2 #1
9592 { \use:c { __iow_wrap_##2:n } {##1} }
9593 }
9594 \exp_args:NVV \__iow_tmp:w \c_catcode_other_space_tl \c__iow_wrap_marker_tl

```

(End definition for `__iow_wrap_chunk:nw` and `__iow_wrap_next:nw`.)

```

\__iow_wrap_line:nw
\__iow_wrap_line_loop:w
\__iow_wrap_line_aux:Nw
\__iow_wrap_line_end:NnnnnnnnN
\__iow_wrap_line_end:nw
\__iow_wrap_end_chunk:w

```

This is followed by `{\langle string \rangle} \langle intexpr \rangle ;`. It stores the `\langle string \rangle` and up to `\langle intexpr \rangle` characters from the current chunk into `\l__iow_line_part_tl`. Characters are grabbed 8 at a time and left in `\l__iow_line_part_tl` by the `line_loop` auxiliary. When $k < 8$ remain to be found, the `line_aux` auxiliary calls the `line_end` auxiliary followed by (the single digit) k , then $7 - k$ empty brace groups, then the chunk's remaining characters. The `line_end` auxiliary leaves k characters from the chunk in the line part, then ends the assignment. Ignore the `\use_none:nnnnn` line for now. If the next character is a space the line can be broken there: store what we found into the result and get the next line. Otherwise some work is needed to find a break-point. So far we have ignored what happens if the chunk is shorter than the requested number of characters: this is dealt with by the `end_chunk` auxiliary, which gets treated like a character by the rest of the code. It ends up being called either as one of the arguments #2-#9 of the `line_loop` auxiliary or as one of the arguments #2-#8 of the `line_end` auxiliary. In both cases stop the assignment and work out how many characters are still needed. The weird `\use_none:nnnnn` ensures that the required data is in the right place.

```

9595 \cs_new_protected:Npn \__iow_wrap_line:nw #1
9596 {
9597   \tex_edef:D \l__iow_line_part_tl { \if_false: } \fi:
9598   #1
9599   \exp_after:wN \__iow_wrap_line_loop:w
9600   \__int_value:w \__int_eval:w
9601 }
9602 \cs_new:Npn \__iow_wrap_line_loop:w #1 ; #2#3#4#5#6#7#8#9
9603 {
9604   \if_int_compare:w #1 < 8 \exp_stop_f:
9605   \__iow_wrap_line_aux:Nw #1
9606   \fi:
9607   #2 #3 #4 #5 #6 #7 #8 #9
9608   \exp_after:wN \__iow_wrap_line_loop:w

```

```

9609     \__int_value:w \__int_eval:w #1 - 8 ;
9610 }
9611 \cs_new:Npn \__iow_wrap_line_aux:Nw #1#2#3 \exp_after:wN #4 ;
9612 {
9613     #2
9614     \exp_after:wN \__iow_wrap_line_end:NnnnnnnnN
9615     \exp_after:wN #1
9616     \exp:w \exp_end_continue_f:w
9617     \exp_after:wN \exp_after:wN
9618     \if_case:w #1 \exp_stop_f:
9619         \prg_do_nothing:
9620     \or: \use_none:n
9621     \or: \use_none:nn
9622     \or: \use_none:nnn
9623     \or: \use_none:nnnn
9624     \or: \use_none:nnnnn
9625     \or: \use_none:nnnnnn
9626     \or: \use_none:nnnnnnn
9627     \fi:
9628     { } { } { } { } { } { } { } { } { } #3
9629 }
9630 \cs_new:Npn \__iow_wrap_line_end:NnnnnnnnN #1#2#3#4#5#6#7#8#9
9631 {
9632     #2 #3 #4 #5 #6 #7 #8
9633     \use_none:nnnnn \__int_eval:w 8 - ; #9
9634     \token_if_eq_charcode:NNTF \c_space_token #9
9635     { \__iow_wrap_line_end:nw { } }
9636     { \if_false: { \fi: } \__iow_wrap_break:w #9 }
9637 }
9638 \cs_new:Npn \__iow_wrap_line_end:nw #1
9639 {
9640     \if_false: { \fi: }
9641     \__iow_wrap_store_do:n {#1}
9642     \__iow_wrap_next_line:w
9643 }
9644 \cs_new:Npn \__iow_wrap_end_chunk:w
9645     #1 \__int_eval:w #2 - #3 ; #4#5 \q_stop
9646 {
9647     \if_false: { \fi: }
9648     \exp_args:Nf \__iow_wrap_next:nw { \int_eval:n { #2 - #4 } }
9649 }

```

(End definition for __iow_wrap_line:nw and others.)

<pre> __iow_wrap_break:w __iow_wrap_break_first:w __iow_wrap_break_none:w __iow_wrap_break_loop:w __iow_wrap_break_end:w </pre>	<p>Functions here are defined indirectly: __iow_tmp:w is eventually called with an “other” space as its argument. The goal is to remove from \l__iow_line_part_tl the part after the last space. In most cases this is done by repeatedly calling the <code>break_loop</code> auxiliary, which leaves “words” (delimited by spaces) until it hits the trailing space: then its argument <code>##3</code> is ? __iow_wrap_break_end:w instead of a single token, and that <code>break_end</code> auxiliary leaves in the assignment the line until the last space, then calls __iow_wrap_line_end:nw to finish up the line and move on to the next. If there is no space in \l__iow_line_part_tl then the <code>break_first</code> auxiliary calls the <code>break_none</code> auxiliary. In that case, if the current line is empty, the complete word (including <code>##4</code>, characters beyond what we had grabbed) is added to the line, making it over-long.</p>
--	--

Otherwise, the word is used for the following line (and the last space of the line so far is removed because it was inserted due to the presence of a marker).

```

9650 \cs_set_protected:Npn \__iow_tmp:w #1
9651 {
9652   \cs_new:Npn \__iow_wrap_break:w
9653   {
9654     \tex_edef:D \l__iow_line_part_tl
9655     { \if_false: } \fi:
9656     \exp_after:wN \__iow_wrap_break_first:w
9657     \l__iow_line_part_tl
9658     #1
9659     { ? \__iow_wrap_break_end:w }
9660     \q_mark
9661   }
9662   \cs_new:Npn \__iow_wrap_break_first:w ##1 #1 ##2
9663   {
9664     \use_none:nn ##2 \__iow_wrap_break_none:w
9665     \__iow_wrap_break_loop:w ##1 #1 ##2
9666   }
9667   \cs_new:Npn \__iow_wrap_break_none:w ##1##2 #1 ##3 \q_mark ##4 #1
9668   {
9669     \tl_if_empty:NTF \l__iow_line_tl
9670     { ##2 ##4 \__iow_wrap_line_end:nw { } }
9671     { \__iow_wrap_line_end:nw { \__iow_wrap_trim:N } ##2 ##4 #1 }
9672   }
9673   \cs_new:Npn \__iow_wrap_break_loop:w ##1 #1 ##2 #1 ##3
9674   {
9675     \use_none:n ##3
9676     ##1 #1
9677     \__iow_wrap_break_loop:w ##2 #1 ##3
9678   }
9679   \cs_new:Npn \__iow_wrap_break_end:w ##1 #1 ##2 ##3 #1 ##4 \q_mark
9680   { ##1 \__iow_wrap_line_end:nw { } ##3 }
9681 }
9682 \exp_args:NV \__iow_tmp:w \c_catcode_other_space_tl

```

(End definition for `__iow_wrap_break:w` and others.)

`__iow_wrap_next_line:w` The special case where the end of a line coincides with the end of a chunk is detected here, to avoid a spurious empty line. Otherwise, call `__iow_wrap_line:nw` to find characters for the next line (remembering to account for the indentation).

```

9683 \cs_new_protected:Npn \__iow_wrap_next_line:w #1#2 \q_stop
9684 {
9685   \tl_clear:N \l__iow_line_tl
9686   \token_if_eq_meaning:NNTF #1 \__iow_wrap_end_chunk:w
9687   {
9688     \tl_clear:N \l__iow_line_part_tl
9689     \bool_set_true:N \l__iow_line_break_bool
9690     \__iow_wrap_next:nw { \l__iow_line_target_int }
9691   }
9692   {
9693     \__iow_wrap_line:nw
9694     { \l__iow_indent_tl }
9695     \l__iow_line_target_int - \l__iow_indent_int ;

```

```

9696         #1 #2 \q_stop
9697     }
9698 }

```

(End definition for _iow_wrap_next_line:w.)

_iow_wrap_indent: These functions are called after a chunk has been wrapped, when encountering indent/unindent markers. Add the line part (last line part of the previous chunk) to the line so far and reset a boolean denoting the presence of a line-break. Most importantly, add or remove one indent from the current indent (both the integer and the token list). Finally, continue wrapping.

```

9699 \cs_new_protected:Npn \_iow_wrap_indent:n #1
9700 {
9701     \tl_put_right:Nx \l__iow_line_tl { \l__iow_line_part_tl }
9702     \bool_set_false:N \l__iow_line_break_bool
9703     \int_add:Nn \l__iow_indent_int { \l__iow_one_indent_int }
9704     \tl_put_right:No \l__iow_indent_tl { \l__iow_one_indent_tl }
9705     \_iow_wrap_chunk:nw {#1}
9706 }
9707 \cs_new_protected:Npn \_iow_wrap_unindent:n #1
9708 {
9709     \tl_put_right:Nx \l__iow_line_tl { \l__iow_line_part_tl }
9710     \bool_set_false:N \l__iow_line_break_bool
9711     \int_sub:Nn \l__iow_indent_int { \l__iow_one_indent_int }
9712     \tl_set:Nx \l__iow_indent_tl
9713     { \exp_after:wN \_iow_unindent:w \l__iow_indent_tl }
9714     \_iow_wrap_chunk:nw {#1}
9715 }

```

(End definition for _iow_wrap_indent: and _iow_wrap_unindent:.)

_iow_wrap_newline: These functions are called after a chunk has been line-wrapped, when encountering a newline/end marker. Unless we just took a line-break, store the line part and the line so far into the whole \l__iow_wrap_tl, trimming a trailing space. In the newline case look for a new line (of length \l__iow_line_target_int) in a new chunk.

```

9716 \cs_new_protected:Npn \_iow_wrap_newline:n #1
9717 {
9718     \bool_if:NF \l__iow_line_break_bool
9719     { \_iow_wrap_store_do:n { \_iow_wrap_trim:N } }
9720     \bool_set_false:N \l__iow_line_break_bool
9721     \_iow_wrap_chunk:nw { \l__iow_line_target_int }
9722 }
9723 \cs_new_protected:Npn \_iow_wrap_end:n #1
9724 {
9725     \bool_if:NF \l__iow_line_break_bool
9726     { \_iow_wrap_store_do:n { \_iow_wrap_trim:N } }
9727     \bool_set_false:N \l__iow_line_break_bool
9728 }

```

(End definition for _iow_wrap_newline: and _iow_wrap_end:.)

_iow_wrap_store_do:n First add the last line part to the line, then append it to \l__iow_wrap_tl with the appropriate new line (with “run-on” text), possibly with its last space removed (#1 is empty or _iow_wrap_trim:N).

```

9729 \cs_new_protected:Npn \__iow_wrap_store_do:n #1
9730 {
9731   \tl_set:Nx \l__iow_line_tl
9732     { \l__iow_line_tl \l__iow_line_part_tl }
9733   \tl_set:Nx \l__iow_wrap_tl
9734     {
9735       \l__iow_wrap_tl
9736       \l__iow_newline_tl
9737       #1 \l__iow_line_tl
9738     }
9739   \tl_clear:N \l__iow_line_tl
9740 }

```

(End definition for __iow_wrap_store_do:n.)

__iow_wrap_trim:N Remove one trailing “other” space from the argument.

```

\__iow_wrap_trim:w
9741 \cs_set_protected:Npn \__iow_tmp:w #1
9742 {
9743   \cs_new:Npn \__iow_wrap_trim:N ##1
9744     { \tl_if_empty:NF ##1 { \exp_after:wN \__iow_wrap_trim:w ##1 \q_stop } }
9745   \cs_new:Npn \__iow_wrap_trim:w ##1 #1 \q_stop {##1}
9746 }
9747 \exp_args:NV \__iow_tmp:w \c_catcode_other_space_tl

```

(End definition for __iow_wrap_trim:N and __iow_wrap_trim:w.)

17.5 Messages

```

9748 \__msg_kernel_new:nnnn { kernel } { file-not-found }
9749 { File~'#1'~not~found. }
9750 {
9751   The~requested~file~could~not~be~found~in~the~current~directory,~
9752   in~the~TeX~search~path~or~in~the~LaTeX~search~path.
9753 }
9754 \__msg_kernel_new:nnn { kernel } { file-list }
9755 {
9756   >~File~List~<
9757   #1 \\
9758   .....
9759 }
9760 \__msg_kernel_new:nnnn { kernel } { input-streams-exhausted }
9761 { Input~streams~exhausted }
9762 {
9763   TeX~can~only~open~up~to~16~input~streams~at~one~time.\\
9764   All~16~are~currently~in~use,~and~something~wanted~to~open~
9765   another~one.
9766 }
9767 \__msg_kernel_new:nnnn { kernel } { output-streams-exhausted }
9768 { Output~streams~exhausted }
9769 {
9770   TeX~can~only~open~up~to~16~output~streams~at~one~time.\\
9771   All~16~are~currently~in~use,~and~something~wanted~to~open~
9772   another~one.
9773 }
9774 \__msg_kernel_new:nnnn { kernel } { unbalanced-quote-in-filename }

```

```

9775 { Unbalanced~quotes~in~file~name~'~#1'. }
9776 {
9777   File~names~must~contain~balanced~numbers~of~quotes~(").
9778 }
9779 \_msg_kernel_new:nnnn { kernel } { iow-indent }
9780 { Only~#1 (arg-1)~allows~#2 }
9781 {
9782   The~command~#2 can~only~be~used~in~messages~
9783   which~will~be~wrapped~using~#1.~
9784   It~was~called~with~argument~'~#3'.
9785 }

```

17.6 Deprecated functions

`\g_file_current_name_tl` For removal after 2018-12-31. Contrarily to most other deprecated commands this is expandable so we need to put code by hand in two token lists. We use `\tex_def:D` directly because `\g_file_current_name_tl` is made out of by `\debug_deprecation_on:.`

```

9786 \tl_new:N \g_file_current_name_tl
9787 \tl_gset:Nn \g_file_current_name_tl { \g_file_curr_name_str }
9788 \__debug:TF
9789 {
9790   \tl_gput_right:Nn \g__debug_deprecation_on_tl
9791   {
9792     \__deprecation_error:Nnn \g_file_current_name_tl
9793     { \g_file_curr_name_str } { 2018-12-31 }
9794   }
9795   \tl_gput_right:Nn \g__debug_deprecation_off_tl
9796   { \tex_def:D \g_file_current_name_tl { \g_file_curr_name_str } }
9797 }
9798 { }

```

(End definition for `\g_file_current_name_tl`.)

`\file_path_include:n` Wrapper functions to manage the search path.

```

\file_path_remove:n
9799 \__debug_deprecation:nnNNpn { 2018-12-31 }
9800 { \seq_put_right:Nn \l_file_search_path_seq }
9801 \cs_new_protected:Npn \file_path_include:n #1
9802 {
9803   \__file_name_sanitiz:n {#1} \l__file_full_name_str
9804   \seq_if_in:NVF \l_file_search_path_seq \l__file_full_name_str
9805   { \seq_put_right:NV \l_file_search_path_seq \l__file_full_name_str }
9806 }
9807 \__debug_deprecation:nnNNpn { 2018-12-31 }
9808 { \seq_remove_all:Nn \l_file_search_path_seq }
9809 \cs_new_protected:Npn \file_path_remove:n #1
9810 {
9811   \__file_name_sanitiz:n {#1} \l__file_full_name_str
9812   \seq_remove_all:NV \l_file_search_path_seq \l__file_full_name_str
9813 }

```

(End definition for `\file_path_include:n` and `\file_path_remove:n`.)

`\file_add_path:nN` For removal after 2018-12-31.

```

9814 \__debug_deprecation:nnNNpn { 2018-12-31 } { \file_get_full_name:nN }

```



```

9815 \cs_new_protected:Npn \file_add_path:nN #1#2
9816 {
9817   \file_get_full_name:nN {#1} #2
9818   \str_if_empty:NT #2
9819     { \tl_set:Nn #2 { \q_no_value } }
9820 }

```

(End definition for \file_add_path:nN.)

\ior_get_str:NN For removal after 2017-12-31.

```

9821 \__debug_deprecation:nnNNpn { 2017-12-31 } { \ior_str_get:NN }
9822 \cs_new_protected:Npn \ior_get_str:NN { \ior_str_get:NN }

```

(End definition for \ior_get_str:NN.)

\file_list: Renamed to \file_log_list:. For removal after 2018-12-31.

```

9823 \__debug_deprecation:nnNNpn { 2018-12-31 } { \file_log_list: }
9824 \cs_new_protected:Npn \file_list: { \file_log_list: }

```

(End definition for \file_list:.)

\ior_list_streams: These got a more consistent naming.

```

\ior_log_streams: 9825 \__debug_deprecation:nnNNpn { 2018-12-31 } { \ior_show_list: }
\ior_list_streams: 9826 \cs_new_protected:Npn \ior_list_streams: { \ior_show_list: }
\iow_list_streams: 9827 \__debug_deprecation:nnNNpn { 2018-12-31 } { \ior_log_list: }
\iow_log_streams: 9828 \cs_new_protected:Npn \ior_log_streams: { \ior_log_list: }
9829 \__debug_deprecation:nnNNpn { 2018-12-31 } { \iow_show_list: }
9830 \cs_new_protected:Npn \iow_list_streams: { \iow_show_list: }
9831 \__debug_deprecation:nnNNpn { 2018-12-31 } { \iow_log_list: }
9832 \cs_new_protected:Npn \iow_log_streams: { \iow_log_list: }

```

(End definition for \ior_list_streams: and others.)

```
9833 </initex | package>
```

18 l3skip implementation

```
9834 <*initex | package>
```

```
9835 <@@=dim>
```

18.1 Length primitives renamed

\if_dim:w Primitives renamed.

```

\__dim_eval:w 9836 \cs_new_eq:NN \if_dim:w \tex_ifdim:D
\__dim_eval_end: 9837 \cs_new_eq:NN \__dim_eval:w \etex_dimexpr:D
9838 \cs_new_eq:NN \__dim_eval_end: \tex_relax:D

```

(End definition for \if_dim:w, __dim_eval:w, and __dim_eval_end:. This function is documented on page 168.)

18.2 Creating and initialising dim variables

\dim_new:N Allocating $\langle dim \rangle$ registers ...

```
\dim_new:c      9839 \*package>
                9840 \cs_new_protected:Npn \dim_new:N #1
                9841 {
                9842     \__chk_if_free_cs:N #1
                9843     \cs:w newdimen \cs_end: #1
                9844 }
                9845 \</package>
                9846 \cs_generate_variant:Nn \dim_new:N { c }
```

(End definition for `\dim_new:N`. This function is documented on page 155.)

\dim_const:Nn Contrarily to integer constants, we cannot avoid using a register, even for constants. We cannot use `\dim_gset:Nn` because debugging code would complain that the constant is not a global variable. Since `\dim_const:Nn` does not need to be fast, use `\dim_eval:n` to avoid needing a debugging patch that wraps the expression in checking code.

```
\dim_const:cn  9847 \__debug_patch:nnNNpn { \__debug_chk_var_scope:NN c #1 } { }
                9848 \cs_new_protected:Npn \dim_const:Nn #1#2
                9849 {
                9850     \dim_new:N #1
                9851     \tex_global:D #1 ~ \dim_eval:n {#2} \scan_stop:
                9852 }
                9853 \cs_generate_variant:Nn \dim_const:Nn { c }
```

(End definition for `\dim_const:Nn`. This function is documented on page 155.)

\dim_zero:N Reset the register to zero. Using `\c_zero_skip` deals with the case where the variable passed is incorrectly a skip (for example a L^AT_EX 2_ε length).

```
\dim_zero:c    9854 \__debug_patch:nnNNpn { \__debug_chk_var_local:N #1 } { }
                9855 \cs_new_protected:Npn \dim_zero:N #1 { #1 \c_zero_skip }
\dim_gzero:N    9856 \__debug_patch:nnNNpn { \__debug_chk_var_global:N #1 } { }
                9857 \cs_new_protected:Npn \dim_gzero:N #1
                9858 { \tex_global:D #1 \c_zero_skip }
                9859 \cs_generate_variant:Nn \dim_zero:N { c }
                9860 \cs_generate_variant:Nn \dim_gzero:N { c }
```

(End definition for `\dim_zero:N` and `\dim_gzero:N`. These functions are documented on page 155.)

\dim_zero_new:N Create a register if needed, otherwise clear it.

```
\dim_zero_new:c 9861 \cs_new_protected:Npn \dim_zero_new:N #1
\dim_gzero_new:N 9862 { \dim_if_exist:NTF #1 { \dim_zero:N #1 } { \dim_new:N #1 } }
\dim_gzero_new:c 9863 \cs_new_protected:Npn \dim_gzero_new:N #1
                9864 { \dim_if_exist:NTF #1 { \dim_gzero:N #1 } { \dim_new:N #1 } }
                9865 \cs_generate_variant:Nn \dim_zero_new:N { c }
                9866 \cs_generate_variant:Nn \dim_gzero_new:N { c }
```

(End definition for `\dim_zero_new:N` and `\dim_gzero_new:N`. These functions are documented on page 155.)

\dim_if_exist_p:N Copies of the cs functions defined in l3basics.

```
\dim_if_exist_p:c 9867 \prg_new_eq_conditional:NNn \dim_if_exist:N \cs_if_exist:N
\dim_if_exist:NTF 9868 { TF , T , F , p }
\dim_if_exist:cTF 9869 \prg_new_eq_conditional:NNn \dim_if_exist:c \cs_if_exist:c
                9870 { TF , T , F , p }
```

(End definition for `\dim_if_exist:NTF`. This function is documented on page 155.)

18.3 Setting dim variables

Several functions here have a signature `:Nn` and are such that when debugging, the first argument should be checked to be a local/global variable and the second should be wrapped in code for an expression. The temporary function `__dim_tmp:w` finds the name `#3` of the function being redefined and writes the appropriate patch.

```

9871 \cs_set_protected:Npn \__dim_tmp:w #1#2#3
9872 {
9873   \__debug_patch_args:nnnNnNpn
9874     { #1 ##1 }
9875     { }
9876     { {##1} { \__debug_chk_expr:nNn {##2} \__dim_eval:w { } #3 } }
9877     #2 #3
9878 }
```

\dim_set:Nn Setting dimensions is easy enough but when debugging we want both to check that the variable is correctly local/global and to wrap the expression in some code. The `\scan_stop:` deals with the case where the variable passed is a skip (for example a $\text{\LaTeX} 2_{\epsilon}$ length).

```

9879 \__dim_tmp:w \__debug_chk_var_local:N
9880 \cs_new_protected:Npn \dim_set:Nn #1#2
9881   { #1 ~ \__dim_eval:w #2 \__dim_eval_end: \scan_stop: }
9882 \__dim_tmp:w \__debug_chk_var_global:N
9883 \cs_new_protected:Npn \dim_gset:Nn #1#2
9884   { \tex_global:D #1 ~ \__dim_eval:w #2 \__dim_eval_end: \scan_stop: }
9885 \cs_generate_variant:Nn \dim_set:Nn { c }
9886 \cs_generate_variant:Nn \dim_gset:Nn { c }
```

(End definition for `\dim_set:Nn` and `\dim_gset:Nn`. These functions are documented on page 156.)

\dim_set_eq:NN All straightforward, with a `\scan_stop:` to deal with the case where `#1` is (incorrectly) a skip.

```

9887 \__debug_patch:nnNnNpn { \__debug_chk_var_local:N #1 } { }
9888 \cs_new_protected:Npn \dim_set_eq:NN #1#2
9889   { #1 = #2 \scan_stop: }
9890 \cs_generate_variant:Nn \dim_set_eq:NN { c }
9891 \cs_generate_variant:Nn \dim_set_eq:NN { Nc , cc }
9892 \__debug_patch:nnNnNpn { \__debug_chk_var_global:N #1 } { }
9893 \cs_new_protected:Npn \dim_gset_eq:NN #1#2
9894   { \tex_global:D #1 = #2 \scan_stop: }
9895 \cs_generate_variant:Nn \dim_gset_eq:NN { c }
9896 \cs_generate_variant:Nn \dim_gset_eq:NN { Nc , cc }
```

(End definition for `\dim_set_eq:NN` and `\dim_gset_eq:NN`. These functions are documented on page 156.)

\dim_add:Nn Using `by` here deals with the (incorrect) case `\dimen123`. Using `\scan_stop:` deals with skip variables. Since debugging checks that the variable is correctly local/global, the global versions cannot be defined as `\tex_global:D` followed by the local versions. The debugging code is inserted by `__dim_tmp:w`.

```

9897 \__dim_tmp:w \__debug_chk_var_local:N
9898 \cs_new_protected:Npn \dim_add:Nn #1#2
9899   { \tex_advance:D #1 by \__dim_eval:w #2 \__dim_eval_end: \scan_stop: }
9900 \__dim_tmp:w \__debug_chk_var_global:N
```

```

9901 \cs_new_protected:Npn \dim_gadd:Nn #1#2
9902 { \tex_global:D \tex_advance:D #1 by \__dim_eval:w #2 \__dim_eval_end: \scan_stop: }
9903 \cs_generate_variant:Nn \dim_add:Nn { c }
9904 \cs_generate_variant:Nn \dim_gadd:Nn { c }
9905 \__dim_tmp:w \__debug_chk_var_local:N
9906 \cs_new_protected:Npn \dim_sub:Nn #1#2
9907 { \tex_advance:D #1 by - \__dim_eval:w #2 \__dim_eval_end: \scan_stop: }
9908 \__dim_tmp:w \__debug_chk_var_global:N
9909 \cs_new_protected:Npn \dim_gsub:Nn #1#2
9910 { \tex_global:D \tex_advance:D #1 by - \__dim_eval:w #2 \__dim_eval_end: \scan_stop: }
9911 \cs_generate_variant:Nn \dim_sub:Nn { c }
9912 \cs_generate_variant:Nn \dim_gsub:Nn { c }

```

(End definition for `\dim_add:Nn` and others. These functions are documented on page 156.)

18.4 Utilities for dimension calculations

`\dim_abs:n` Functions for min, max, and absolute value with only one evaluation. The absolute value is evaluated by removing a leading `-` if present.

`__dim_abs:N`

`\dim_max:nn`

`\dim_min:nn`

`__dim_maxmin:wwN`

```

9913 \__debug_patch_args:nNNpn
9914 { { \__debug_chk_expr:nNnN {#1} \__dim_eval:w { } \dim_abs:n } }
9915 \cs_new:Npn \dim_abs:n #1
9916 {
9917   \exp_after:wN \__dim_abs:N
9918   \dim_use:N \__dim_eval:w #1 \__dim_eval_end:
9919 }
9920 \cs_new:Npn \__dim_abs:N #1
9921 { \if_meaning:w - #1 \else: \exp_after:wN #1 \fi: }
9922 \__debug_patch_args:nNNpn
9923 {
9924   { \__debug_chk_expr:nNnN {#1} \__dim_eval:w { } \dim_max:nn }
9925   { \__debug_chk_expr:nNnN {#2} \__dim_eval:w { } \dim_max:nn }
9926 }
9927 \cs_new:Npn \dim_max:nn #1#2
9928 {
9929   \dim_use:N \__dim_eval:w \exp_after:wN \__dim_maxmin:wwN
9930   \dim_use:N \__dim_eval:w #1 \exp_after:wN ;
9931   \dim_use:N \__dim_eval:w #2 ;
9932   >
9933   \__dim_eval_end:
9934 }
9935 \__debug_patch_args:nNNpn
9936 {
9937   { \__debug_chk_expr:nNnN {#1} \__dim_eval:w { } \dim_min:nn }
9938   { \__debug_chk_expr:nNnN {#2} \__dim_eval:w { } \dim_min:nn }
9939 }
9940 \cs_new:Npn \dim_min:nn #1#2
9941 {
9942   \dim_use:N \__dim_eval:w \exp_after:wN \__dim_maxmin:wwN
9943   \dim_use:N \__dim_eval:w #1 \exp_after:wN ;
9944   \dim_use:N \__dim_eval:w #2 ;
9945   <
9946   \__dim_eval_end:
9947 }

```

```

9948 \cs_new:Npn \__dim_maxmin:wwN #1 ; #2 ; #3
9949 {
9950   \if_dim:w #1 #3 #2 ~
9951     #1
9952   \else:
9953     #2
9954   \fi:
9955 }

```

(End definition for `\dim_abs:n` and others. These functions are documented on page 156.)

`\dim_ratio:nn` With dimension expressions, something like `10 pt * (5 pt / 10 pt)` does not work. Instead, the ratio part needs to be converted to an integer expression. Using `__int_value:w` forces everything into `sp`, avoiding any decimal parts.

```

9956 \cs_new:Npn \dim_ratio:nn #1#2
9957 { \__dim_ratio:n {#1} / \__dim_ratio:n {#2} }
9958 \cs_new:Npn \__dim_ratio:n #1
9959 { \__int_value:w \__dim_eval:w (#1) \__dim_eval_end: }

```

(End definition for `\dim_ratio:nn` and `__dim_ratio:n`. This function is documented on page 157.)

18.5 Dimension expression conditionals

`\dim_compare_p:nNn` Simple comparison.

`\dim_compare:nNnTF`

```

9960 \__debug_patch_conditional_args:nNnpnn
9961 {
9962   { \__debug_chk_expr:nNnN {#1} \__dim_eval:w { } \dim_compare:nNn }
9963   { \__dim_eval_end: #2 }
9964   { \__debug_chk_expr:nNnN {#3} \__dim_eval:w { } \dim_compare:nNn }
9965 }
9966 \prg_new_conditional:Npnn \dim_compare:nNn #1#2#3 { p , T , F , TF }
9967 {
9968   \if_dim:w \__dim_eval:w #1 #2 \__dim_eval:w #3 \__dim_eval_end:
9969   \prg_return_true: \else: \prg_return_false: \fi:
9970 }

```

(End definition for `\dim_compare:nNnTF`. This function is documented on page 157.)

`\dim_compare_p:n` This code is adapted from the `\int_compare:nTF` function. First make sure that there is at least one relation operator, by evaluating a dimension expression with a trailing `__prg_compare_error:`. Just like for integers, the looping auxiliary `__dim_compare:wNN` closes a primitive conditional and opens a new one. It is actually easier to grab a dimension operand than an integer one, because once evaluated, dimensions all end with `pt` (with category other). Thus we do not need specific auxiliaries for the three “simple” relations `<`, `=`, and `>`.

`\dim_compare:nTF`

```

9971 \prg_new_conditional:Npnn \dim_compare:n #1 { p , T , F , TF }
9972 {
9973   \exp_after:wN \__dim_compare:w
9974   \dim_use:N \__dim_eval:w #1 \__prg_compare_error:
9975 }
9976 \cs_new:Npn \__dim_compare:w #1 \__prg_compare_error:
9977 {
9978   \exp_after:wN \if_false: \exp:w \exp_end_continue_f:w
9979   \__dim_compare:wNN #1 ? { = \__dim_compare_end:w \else: } \q_stop

```

```

9980 }
9981 \exp_args:Nno \use:nn
9982 { \cs_new:Npn \__dim_compare:wNN #1 } { \tl_to_str:n {pt} #2#3 }
9983 {
9984   \if_meaning:w = #3
9985     \use:c { __dim_compare_#2:w }
9986   \fi:
9987   #1 pt \exp_stop_f:
9988   \prg_return_false:
9989   \exp_after:wN \use_none_delimit_by_q_stop:w
9990   \fi:
9991   \reverse_if:N \if_dim:w #1 pt #2
9992   \exp_after:wN \__dim_compare:wNN
9993   \dim_use:N \__dim_eval:w #3
9994 }
9995 \cs_new:cpn { __dim_compare_ ! :w }
9996   #1 \reverse_if:N #2 ! #3 = { #1 #2 = #3 }
9997 \cs_new:cpn { __dim_compare_ = :w }
9998   #1 \__dim_eval:w = { #1 \__dim_eval:w }
9999 \cs_new:cpn { __dim_compare_ < :w }
10000   #1 \reverse_if:N #2 < #3 = { #1 #2 > #3 }
10001 \cs_new:cpn { __dim_compare_ > :w }
10002   #1 \reverse_if:N #2 > #3 = { #1 #2 < #3 }
10003 \cs_new:Npn \__dim_compare_end:w #1 \prg_return_false: #2 \q_stop
10004   { #1 \prg_return_false: \else: \prg_return_true: \fi: }

```

(End definition for \dim_compare:nTF and others. This function is documented on page 158.)

<pre> \dim_case:nn \dim_case:nnTF __dim_case:nnTF __dim_case:nw __dim_case_end:nw </pre>	<p>For dimension cases, the first task to fully expand the check condition. The over all idea is then much the same as for \str_case:nn(TF) as described in l3basics.</p> <pre> 10005 \cs_new:Npn \dim_case:nnTF #1 10006 { 10007 \exp:w 10008 \exp_args:Nf __dim_case:nnTF { \dim_eval:n {#1} } 10009 } 10010 \cs_new:Npn \dim_case:nnT #1#2#3 10011 { 10012 \exp:w 10013 \exp_args:Nf __dim_case:nnTF { \dim_eval:n {#1} } {#2} {#3} { } 10014 } 10015 \cs_new:Npn \dim_case:nnF #1#2 10016 { 10017 \exp:w 10018 \exp_args:Nf __dim_case:nnTF { \dim_eval:n {#1} } {#2} { } 10019 } 10020 \cs_new:Npn \dim_case:nn #1#2 10021 { 10022 \exp:w 10023 \exp_args:Nf __dim_case:nnTF { \dim_eval:n {#1} } {#2} { } { } 10024 } 10025 \cs_new:Npn __dim_case:nnTF #1#2#3#4 10026 { __dim_case:nw {#1} #2 {#1} { } \q_mark {#3} \q_mark {#4} \q_stop } 10027 \cs_new:Npn __dim_case:nw #1#2#3 10028 { </pre>
--	--

```

10029     \dim_compare:nNnTF {#1} = {#2}
10030     { \__dim_case_end:nw {#3} }
10031     { \__dim_case:nw {#1} }
10032   }
10033 \cs_new_eq:NN \__dim_case_end:nw \__prg_case_end:nw

```

(End definition for `\dim_case:nnTF` and others. This function is documented on page 159.)

18.6 Dimension expression loops

`\dim_while_do:nn` `while_do` and `do_while` functions for dimensions. Same as for the `int` type only the names have changed.

```

\dim_until_do:nn
\dim_do_while:nn
\dim_do_until:nn
10034 \cs_new:Npn \dim_while_do:nn #1#2
10035 {
10036   \dim_compare:nT {#1}
10037   {
10038     #2
10039     \dim_while_do:nn {#1} {#2}
10040   }
10041 }
10042 \cs_new:Npn \dim_until_do:nn #1#2
10043 {
10044   \dim_compare:nF {#1}
10045   {
10046     #2
10047     \dim_until_do:nn {#1} {#2}
10048   }
10049 }
10050 \cs_new:Npn \dim_do_while:nn #1#2
10051 {
10052   #2
10053   \dim_compare:nT {#1}
10054   { \dim_do_while:nn {#1} {#2} }
10055 }
10056 \cs_new:Npn \dim_do_until:nn #1#2
10057 {
10058   #2
10059   \dim_compare:nF {#1}
10060   { \dim_do_until:nn {#1} {#2} }
10061 }

```

(End definition for `\dim_while_do:nn` and others. These functions are documented on page 160.)

`\dim_while_do:nNnn` `while_do` and `do_while` functions for dimensions. Same as for the `int` type only the names have changed.

```

\dim_until_do:nNnn
\dim_do_while:nNnn
\dim_do_until:nNnn
10062 \cs_new:Npn \dim_while_do:nNnn #1#2#3#4
10063 {
10064   \dim_compare:nNnT {#1} #2 {#3}
10065   {
10066     #4
10067     \dim_while_do:nNnn {#1} #2 {#3} {#4}
10068   }
10069 }
10070 \cs_new:Npn \dim_until_do:nNnn #1#2#3#4

```

```

10071 {
10072   \dim_compare:nNnF {#1} #2 {#3}
10073   {
10074     #4
10075     \dim_until_do:nNnn {#1} #2 {#3} {#4}
10076   }
10077 }
10078 \cs_new:Npn \dim_do_while:nNnn #1#2#3#4
10079 {
10080   #4
10081   \dim_compare:nNnT {#1} #2 {#3}
10082   { \dim_do_while:nNnn {#1} #2 {#3} {#4} }
10083 }
10084 \cs_new:Npn \dim_do_until:nNnn #1#2#3#4
10085 {
10086   #4
10087   \dim_compare:nNnF {#1} #2 {#3}
10088   { \dim_do_until:nNnn {#1} #2 {#3} {#4} }
10089 }

```

(End definition for `\dim_while_do:nNnn` and others. These functions are documented on page 160.)

18.7 Using dim expressions and variables

`\dim_eval:n` Evaluating a dimension expression expandably.

```

10090 \__debug_patch_args:nNnNpn
10091 { { \__debug_chk_expr:nNnN {#1} \__dim_eval:w { } \dim_eval:n } }
10092 \cs_new:Npn \dim_eval:n #1
10093 { \dim_use:N \__dim_eval:w #1 \__dim_eval_end: }

```

(End definition for `\dim_eval:n`. This function is documented on page 160.)

`__dim_eval:n` Evaluating a dimension expression expandably. This is for use in other modules, to avoid having to patch many commands. The only difference with `\dim_eval:n` is the lack of `\dim_use:N`, to produce an internal dimension rather than expand it into characters.

```

10094 \__debug_patch_args:nNnNpn
10095 { { \__debug_chk_expr:nNnN {#1} \__dim_eval:w { } \__dim_eval:n } }
10096 \cs_new:Npn \__dim_eval:n #1 { \__dim_eval:w #1 \__dim_eval_end: }

```

(End definition for `__dim_eval:n`.)

`\dim_use:N` Accessing a $\langle dim \rangle$.

`\dim_use:c`

```

10097 \cs_new_eq:NN \dim_use:N \tex_the:D

```

We hand-code this for some speed gain:

```

10098 %\cs_generate_variant:Nn \dim_use:N { c }
10099 \cs_new:Npn \dim_use:c #1 { \tex_the:D \cs:w #1 \cs_end: }

```

(End definition for `\dim_use:N`. This function is documented on page 160.)

`\dim_to_decimal:n` A function which comes up often enough to deserve a place in the kernel. Evaluate the dimension expression `#1` then remove the trailing `pt`. When debugging is enabled, the argument is put in parentheses as this prevents the dimension expression from terminating early and leaving extra tokens lying around. This is used a lot by low-level manipulations.

```

10100 \__debug_patch_args:nNnNpn

```



```

10101 { { \__debug_chk_expr:nNnN {#1} \__dim_eval:w { } \dim_to_decimal:n } }
10102 \cs_new:Npn \dim_to_decimal:n #1
10103 {
10104   \exp_after:wN
10105   \__dim_to_decimal:w \dim_use:N \__dim_eval:w #1 \__dim_eval_end:
10106 }
10107 \use:x
10108 {
10109   \cs_new:Npn \exp_not:N \__dim_to_decimal:w
10110   ##1 . ##2 \tl_to_str:n { pt }
10111 }
10112 {
10113   \int_compare:nNnTF {#2} > { 0 }
10114   { #1 . #2 }
10115   { #1 }
10116 }

```

(End definition for `\dim_to_decimal:n` and `__dim_to_decimal:w`. This function is documented on page 161.)

`\dim_to_decimal_in_bp:n` Conversion to big points is done using a scaling inside `__dim_eval:w` as ε -TeX does that using 64-bit precision. Here, 800/803 is the integer fraction for 72/72.27. This is a common case so is hand-coded for accuracy (and speed).

```

10117 \cs_new:Npn \dim_to_decimal_in_bp:n #1
10118 { \dim_to_decimal:n { ( #1 ) * 800 / 803 } }

```

(End definition for `\dim_to_decimal_in_bp:n`. This function is documented on page 161.)

`\dim_to_decimal_in_sp:n` Another hard-coded conversion: this one is necessary to avoid things going off-scale.

```

10119 \__debug_patch_args:nNpn
10120 { { \__debug_chk_expr:nNnN {#1} \__dim_eval:w { } \dim_to_decimal_in_sp:n } }
10121 \cs_new:Npn \dim_to_decimal_in_sp:n #1
10122 { \int_eval:n { \__dim_eval:w #1 \__dim_eval_end: } }

```

(End definition for `\dim_to_decimal_in_sp:n`. This function is documented on page 161.)

`\dim_to_decimal_in_unit:nn` An analogue of `\dim_ratio:nn` that produces a decimal number as its result, rather than a rational fraction for use within dimension expressions.

```

10123 \cs_new:Npn \dim_to_decimal_in_unit:nn #1#2
10124 {
10125   \dim_to_decimal:n
10126   {
10127     1pt *
10128     \dim_ratio:nn {#1} {#2}
10129   }
10130 }

```

(End definition for `\dim_to_decimal_in_unit:nn`. This function is documented on page 161.)

`\dim_to_fp:n` Defined in `l3fp-convert`, documented here.

(End definition for `\dim_to_fp:n`. This function is documented on page 162.)

18.8 Viewing dim variables

\dim_show:N Diagnostics.

\dim_show:c 10131 \cs_new_eq:NN \dim_show:N __kernel_register_show:N
10132 \cs_generate_variant:Nn \dim_show:N { c }

(End definition for \dim_show:N. This function is documented on page 162.)

\dim_show:n Diagnostics. We don't use the TeX primitive \showthe to show dimension expressions: this gives a more unified output.

10133 \cs_new_protected:Npn \dim_show:n
10134 { \msg_show_eval:Nn \dim_eval:n }

(End definition for \dim_show:n. This function is documented on page 162.)

\dim_log:N Diagnostics. Redirect output of \dim_show:n to the log.

\dim_log:c 10135 \cs_new_eq:NN \dim_log:N __kernel_register_log:N
\dim_log:n 10136 \cs_new_eq:NN \dim_log:c __kernel_register_log:c
10137 \cs_new_protected:Npn \dim_log:n
10138 { \msg_log_eval:Nn \dim_eval:n }

(End definition for \dim_log:N and \dim_log:n. These functions are documented on page 162.)

18.9 Constant dimensions

\c_zero_dim Constant dimensions.

\c_max_dim 10139 \dim_const:Nn \c_zero_dim { 0 pt }
10140 \dim_const:Nn \c_max_dim { 16383.99999 pt }

(End definition for \c_zero_dim and \c_max_dim. These variables are documented on page 162.)

18.10 Scratch dimensions

\l_tmpa_dim We provide two local and two global scratch registers, maybe we need more or less.

\l_tmpp_dim 10141 \dim_new:N \l_tmpa_dim
\g_tmpa_dim 10142 \dim_new:N \l_tmpp_dim
\g_tmpp_dim 10143 \dim_new:N \g_tmpa_dim
10144 \dim_new:N \g_tmpp_dim

(End definition for \l_tmpa_dim and others. These variables are documented on page 162.)

18.11 Creating and initialising skip variables

\skip_new:N Allocation of a new internal registers.

\skip_new:c 10145 \<package>
10146 \cs_new_protected:Npn \skip_new:N #1
10147 {
10148 __chk_if_free_cs:N #1
10149 \cs:w newskip \cs_end: #1
10150 }
10151 \</package>
10152 \cs_generate_variant:Nn \skip_new:N { c }

(End definition for \skip_new:N. This function is documented on page 163.)

\skip_const:Nn Contrarily to integer constants, we cannot avoid using a register, even for constants. See **\dim_const:Nn** for why we cannot use **\skip_gset:Nn**.

```

10153 \__debug_patch:nnNNpn { \__debug_chk_var_scope:NN c #1 } { }
10154 \cs_new_protected:Npn \skip_const:Nn #1#2
10155 {
10156   \skip_new:N #1
10157   \tex_global:D #1 ~ \skip_eval:n {#2} \scan_stop:
10158 }
10159 \cs_generate_variant:Nn \skip_const:Nn { c }

```

(End definition for **\skip_const:Nn**. This function is documented on page 163.)

\skip_zero:N Reset the register to zero.

```

10160 \__debug_patch:nnNNpn { \__debug_chk_var_local:N #1 } { }
10161 \cs_new_protected:Npn \skip_zero:N #1 { #1 \c_zero_skip }
10162 \__debug_patch:nnNNpn { \__debug_chk_var_global:N #1 } { }
10163 \cs_new_protected:Npn \skip_gzero:N #1 { \tex_global:D #1 \c_zero_skip }
10164 \cs_generate_variant:Nn \skip_zero:N { c }
10165 \cs_generate_variant:Nn \skip_gzero:N { c }

```

(End definition for **\skip_zero:N** and **\skip_gzero:N**. These functions are documented on page 163.)

\skip_zero_new:N Create a register if needed, otherwise clear it.

```

10166 \cs_new_protected:Npn \skip_zero_new:N #1
10167 { \skip_if_exist:NTF #1 { \skip_zero:N #1 } { \skip_new:N #1 } }
10168 \cs_new_protected:Npn \skip_gzero_new:N #1
10169 { \skip_if_exist:NTF #1 { \skip_gzero:N #1 } { \skip_new:N #1 } }
10170 \cs_generate_variant:Nn \skip_zero_new:N { c }
10171 \cs_generate_variant:Nn \skip_gzero_new:N { c }

```

(End definition for **\skip_zero_new:N** and **\skip_gzero_new:N**. These functions are documented on page 163.)

\skip_if_exist_p:N Copies of the cs functions defined in l3basics.

```

10172 \prg_new_eq_conditional:NNn \skip_if_exist:N \cs_if_exist:N
10173 { TF , T , F , p }
10174 \prg_new_eq_conditional:NNn \skip_if_exist:c \cs_if_exist:c
10175 { TF , T , F , p }

```

(End definition for **\skip_if_exist:NTF**. This function is documented on page 163.)

18.12 Setting skip variables

Much as for dim variables, **__dim_tmp:w** prepares a patch for :Nn function definitions in which the first argument should be checked to be a local/global variable and the second should be wrapped in code for an expression.

```

10176 \cs_set_protected:Npn \__dim_tmp:w #1#2#3
10177 {
10178   \__debug_patch_args:nnnNNpn
10179   { #1 ##1 }
10180   { }
10181   { {##1} { \__debug_chk_expr:nnNn {##2} \etex_glueexpr:D { } #3 } }
10182   #2 #3
10183 }

```

`\skip_set:Nn` Much the same as for dimensions.

`\skip_set:cn` 10184 `__dim_tmp:w __debug_chk_var_local:N`

`\skip_gset:Nn` 10185 `\cs_new_protected:Npn \skip_set:Nn #1#2`

`\skip_gset:cn` 10186 `{ #1 ~ \etex_glueexpr:D #2 \scan_stop: }`

10187 `__dim_tmp:w __debug_chk_var_global:N`

10188 `\cs_new_protected:Npn \skip_gset:Nn #1#2`

10189 `{ \tex_global:D #1 ~ \etex_glueexpr:D #2 \scan_stop: }`

10190 `\cs_generate_variant:Nn \skip_set:Nn { c }`

10191 `\cs_generate_variant:Nn \skip_gset:Nn { c }`

(End definition for `\skip_set:Nn` and `\skip_gset:Nn`. These functions are documented on page 163.)

`\skip_set_eq:NN` All straightforward.

`\skip_set_eq:cn` 10192 `\cs_new_protected:Npn \skip_set_eq:NN #1#2 { #1 = #2 }`

`\skip_set_eq:Nc` 10193 `\cs_generate_variant:Nn \skip_set_eq:NN { c }`

`\skip_set_eq:cc` 10194 `\cs_generate_variant:Nn \skip_set_eq:NN { Nc , cc }`

`\skip_gset_eq:NN` 10195 `\cs_new_protected:Npn \skip_gset_eq:NN #1#2 { \tex_global:D #1 = #2 }`

`\skip_gset_eq:cn` 10196 `\cs_generate_variant:Nn \skip_gset_eq:NN { c }`

`\skip_gset_eq:Nc` 10197 `\cs_generate_variant:Nn \skip_gset_eq:NN { Nc , cc }`

(End definition for `\skip_set_eq:NN` and `\skip_gset_eq:NN`. These functions are documented on page 163.)

`\skip_add:Nn` Using `by` here deals with the (incorrect) case `\skip123`.

`\skip_add:cn` 10198 `__dim_tmp:w __debug_chk_var_local:N`

`\skip_gadd:Nn` 10199 `\cs_new_protected:Npn \skip_add:Nn #1#2`

`\skip_gadd:cn` 10200 `{ \tex_advance:D #1 by \etex_glueexpr:D #2 \scan_stop: }`

`\skip_sub:Nn` 10201 `__dim_tmp:w __debug_chk_var_global:N`

`\skip_sub:cn` 10202 `\cs_new_protected:Npn \skip_gadd:Nn #1#2`

`\skip_gsub:Nn` 10203 `{ \tex_global:D \tex_advance:D #1 by \etex_glueexpr:D #2 \scan_stop: }`

`\skip_gsub:cn` 10204 `\cs_generate_variant:Nn \skip_add:Nn { c }`

10205 `\cs_generate_variant:Nn \skip_gadd:Nn { c }`

10206 `__dim_tmp:w __debug_chk_var_local:N`

10207 `\cs_new_protected:Npn \skip_sub:Nn #1#2`

10208 `{ \tex_advance:D #1 by - \etex_glueexpr:D #2 \scan_stop: }`

10209 `__dim_tmp:w __debug_chk_var_global:N`

10210 `\cs_new_protected:Npn \skip_gsub:Nn #1#2`

10211 `{ \tex_global:D \tex_advance:D #1 by - \etex_glueexpr:D #2 \scan_stop: }`

10212 `\cs_generate_variant:Nn \skip_sub:Nn { c }`

10213 `\cs_generate_variant:Nn \skip_gsub:Nn { c }`

(End definition for `\skip_add:Nn` and others. These functions are documented on page 163.)

18.13 Skip expression conditionals

`\skip_if_eq_p:nn` Comparing skips means doing two expansions to make strings, and then testing them.

`\skip_if_eq_nn:TF` As a result, only equality is tested.

10214 `\prg_new_conditional:Npnn \skip_if_eq:nn #1#2 { p , T , F , TF }`

10215 `{`

10216 `\if_int_compare:w`

10217 `__str_if_eq_x:nn { \skip_eval:n { #1 } } { \skip_eval:n { #2 } }`

10218 `= 0 \exp_stop_f:`

10219 `\prg_return_true:`

10220 `\else:`

```

10221     \prg_return_false:
10222     \fi:
10223 }

```

(End definition for `\skip_if_eq:nnTF`. This function is documented on page 164.)

`\skip_if_finite:p:n`
`\skip_if_finite:nTF`
`__skip_if_finite:wwNw`

With ε -TEX, we have an easy access to the order of infinities of the stretch and shrink components of a skip. However, to access both, we either need to evaluate the expression twice, or evaluate it, then call an auxiliary to extract both pieces of information from the result. Since we are going to need an auxiliary anyways, it is quicker to make it search for the string `fil` which characterizes infinite glue.

```

10224 \cs_set_protected:Npn \__dim_tmp:w #1
10225 {
10226   \__debug_patch_conditional_args:nNNpnn
10227   {
10228     {
10229       \__debug_chk_expr:nNnN
10230       {##1} \etex_glueexpr:D { } \skip_if_finite:n
10231     }
10232   }
10233   \prg_new_conditional:Npnn \skip_if_finite:n ##1 { p , T , F , TF }
10234   {
10235     \exp_after:wN \__skip_if_finite:wwNw
10236     \skip_use:N \etex_glueexpr:D ##1 ; \prg_return_false:
10237     #1 ; \prg_return_true: \q_stop
10238   }
10239   \cs_new:Npn \__skip_if_finite:wwNw ##1 #1 ##2 ; ##3 ##4 \q_stop {##3}
10240 }
10241 \exp_args:No \__dim_tmp:w { \tl_to_str:n { fil } }

```

(End definition for `\skip_if_finite:nTF` and `__skip_if_finite:wwNw`. This function is documented on page 164.)

18.14 Using skip expressions and variables

`\skip_eval:n` Evaluating a skip expression expandably.

```

10242 \__debug_patch_args:nNNpnn
10243 { { \__debug_chk_expr:nNnN {##1} \etex_glueexpr:D { } \skip_eval:n } }
10244 \cs_new:Npn \skip_eval:n #1
10245 { \skip_use:N \etex_glueexpr:D #1 \scan_stop: }

```

(End definition for `\skip_eval:n`. This function is documented on page 164.)

`\skip_use:N` Accessing a $\langle skip \rangle$.

```

\skip_use:c
10246 \cs_new_eq:NN \skip_use:N \tex_the:D
10247 %\cs_generate_variant:Nn \skip_use:N { c }
10248 \cs_new:Npn \skip_use:c #1 { \tex_the:D \cs:w #1 \cs_end: }

```

(End definition for `\skip_use:N`. This function is documented on page 164.)

18.15 Inserting skips into the output

```

\skip_horizontal:N Inserting skips.
\skip_horizontal:c 10249 \cs_new_eq:NN \skip_horizontal:N \tex_hskip:D
\skip_horizontal:n 10250 \__debug_patch_args:nNNpn
\skip_vertical:N 10251 { { \__debug_chk_expr:nNnN {#1} \etex_glueexpr:D { } \skip_horizontal:n } }
\skip_vertical:c 10252 \cs_new:Npn \skip_horizontal:n #1
\skip_vertical:n 10253 { \skip_horizontal:N \etex_glueexpr:D #1 \scan_stop: }
10254 \cs_new_eq:NN \skip_vertical:N \tex_vskip:D
10255 \__debug_patch_args:nNNpn
10256 { { \__debug_chk_expr:nNnN {#1} \etex_glueexpr:D { } \skip_vertical:n } }
10257 \cs_new:Npn \skip_vertical:n #1
10258 { \skip_vertical:N \etex_glueexpr:D #1 \scan_stop: }
10259 \cs_generate_variant:Nn \skip_horizontal:N { c }
10260 \cs_generate_variant:Nn \skip_vertical:N { c }

```

(End definition for `\skip_horizontal:N` and others. These functions are documented on page 165.)

18.16 Viewing skip variables

```

\skip_show:N Diagnostics.
\skip_show:c 10261 \cs_new_eq:NN \skip_show:N \__kernel_register_show:N
10262 \cs_generate_variant:Nn \skip_show:N { c }

```

(End definition for `\skip_show:N`. This function is documented on page 164.)

`\skip_show:n` Diagnostics. We don't use the \TeX primitive `\showthe` to show skip expressions: this gives a more unified output.

```

10263 \cs_new_protected:Npn \skip_show:n
10264 { \msg_show_eval:Nn \skip_eval:n }

```

(End definition for `\skip_show:n`. This function is documented on page 165.)

```

\skip_log:N Diagnostics. Redirect output of \skip_show:n to the log.
\skip_log:c 10265 \cs_new_eq:NN \skip_log:N \__kernel_register_log:N
\skip_log:n 10266 \cs_new_eq:NN \skip_log:c \__kernel_register_log:c
10267 \cs_new_protected:Npn \skip_log:n
10268 { \msg_log_eval:Nn \skip_eval:n }

```

(End definition for `\skip_log:N` and `\skip_log:n`. These functions are documented on page 165.)

18.17 Constant skips

`\c_zero_skip` Skips with no rubber component are just dimensions but need to terminate correctly.

```

\c_max_skip 10269 \skip_const:Nn \c_zero_skip { \c_zero_dim }
10270 \skip_const:Nn \c_max_skip { \c_max_dim }

```

(End definition for `\c_zero_skip` and `\c_max_skip`. These functions are documented on page 165.)

18.18 Scratch skips

`\l_tmpa_skip` We provide two local and two global scratch registers, maybe we need more or less.

```
\l_tmpb_skip 10271 \skip_new:N \l_tmpa_skip
\g_tmpa_skip 10272 \skip_new:N \l_tmpb_skip
\g_tmpb_skip 10273 \skip_new:N \g_tmpa_skip
10274 \skip_new:N \g_tmpb_skip
```

(End definition for `\l_tmpa_skip` and others. These variables are documented on page 165.)

18.19 Creating and initialising muskip variables

`\muskip_new:N` And then we add muskips.

```
\muskip_new:c 10275 (*package)
10276 \cs_new_protected:Npn \muskip_new:N #1
10277 {
10278     \__chk_if_free_cs:N #1
10279     \cs:w newmuskip \cs_end: #1
10280 }
10281 \package
10282 \cs_generate_variant:Nn \muskip_new:N { c }
```

(End definition for `\muskip_new:N`. This function is documented on page 166.)

`\muskip_const:Nn` See `\skip_const:Nn`.

```
\muskip_const:cn 10283 \__debug_patch:nnNNpn { \__debug_chk_var_scope:NN c #1 } { }
10284 \cs_new_protected:Npn \muskip_const:Nn #1#2
10285 {
10286     \muskip_new:N #1
10287     \tex_global:D #1 ~ \muskip_eval:n {#2} \scan_stop:
10288 }
10289 \cs_generate_variant:Nn \muskip_const:Nn { c }
```

(End definition for `\muskip_const:Nn`. This function is documented on page 166.)

`\muskip_zero:N` Reset the register to zero.

```
\muskip_zero:c 10290 \__debug_patch:nnNNpn { \__debug_chk_var_local:N #1 } { }
\muskip_gzero:N 10291 \cs_new_protected:Npn \muskip_zero:N #1
\muskip_gzero:c 10292 { #1 \c_zero_muskip }
10293 \__debug_patch:nnNNpn { \__debug_chk_var_global:N #1 } { }
10294 \cs_new_protected:Npn \muskip_gzero:N #1
10295 { \tex_global:D #1 \c_zero_muskip }
10296 \cs_generate_variant:Nn \muskip_zero:N { c }
10297 \cs_generate_variant:Nn \muskip_gzero:N { c }
```

(End definition for `\muskip_zero:N` and `\muskip_gzero:N`. These functions are documented on page 166.)

`\muskip_zero_new:N` Create a register if needed, otherwise clear it.

```
\muskip_zero_new:c 10298 \cs_new_protected:Npn \muskip_zero_new:N #1
\muskip_gzero_new:N 10299 { \muskip_if_exist:NTF #1 { \muskip_zero:N #1 } { \muskip_new:N #1 } }
\muskip_gzero_new:c 10300 \cs_new_protected:Npn \muskip_gzero_new:N #1
10301 { \muskip_if_exist:NTF #1 { \muskip_gzero:N #1 } { \muskip_new:N #1 } }
10302 \cs_generate_variant:Nn \muskip_zero_new:N { c }
10303 \cs_generate_variant:Nn \muskip_gzero_new:N { c }
```

(End definition for `\muskip_zero_new:N` and `\muskip_gzero_new:N`. These functions are documented on page 166.)

`\muskip_if_exist_p:N` Copies of the `cs` functions defined in `l3basics`.
`\muskip_if_exist_p:c` 10304 `\prg_new_eq_conditional:NNn \muskip_if_exist:N \cs_if_exist:N`
`\muskip_if_exist:N \textit{TF}` 10305 `{ TF , T , F , p }`
`\muskip_if_exist:c \textit{TF}` 10306 `\prg_new_eq_conditional:NNn \muskip_if_exist:c \cs_if_exist:c`
10307 `{ TF , T , F , p }`

(End definition for `\muskip_if_exist:N \textit{TF}` . This function is documented on page 166.)

18.20 Setting muskip variables

See `skip` case.

```
10308 \cs_set_protected:Npn \__dim_tmp:w #1#2#3
10309 {
10310   \__debug_patch_args:nnnNNpn
10311   { #1 ##1 }
10312   { }
10313   {
10314     {##1}
10315     {
10316       \__debug_chk_expr:nNnN {##2}
10317       \etex_muexpr:D { \etex_mutogluue:D } #3
10318     }
10319   }
10320   #2 #3
10321 }
```

`\muskip_set:Nn` This should be pretty familiar.
`\muskip_set:cn` 10322 `__dim_tmp:w __debug_chk_var_local:N`
`\muskip_gset:Nn` 10323 `\cs_new_protected:Npn \muskip_set:Nn #1#2`
`\muskip_gset:cn` 10324 `{ #1 ~ \etex_muexpr:D #2 \scan_stop: }`
10325 `__dim_tmp:w __debug_chk_var_global:N`
10326 `\cs_new_protected:Npn \muskip_gset:Nn #1#2`
10327 `{ \tex_global:D #1 ~ \etex_muexpr:D #2 \scan_stop: }`
10328 `\cs_generate_variant:Nn \muskip_set:Nn { c }`
10329 `\cs_generate_variant:Nn \muskip_gset:Nn { c }`

(End definition for `\muskip_set:Nn` and `\muskip_gset:Nn`. These functions are documented on page 167.)

`\muskip_set_eq:NN` All straightforward.
`\muskip_set_eq:cN` 10330 `__debug_patch:nnNNpn { __debug_chk_var_local:N #1 } { }`
`\muskip_set_eq:Nc` 10331 `\cs_new_protected:Npn \muskip_set_eq:NN #1#2 { #1 = #2 }`
`\muskip_set_eq:cc` 10332 `\cs_generate_variant:Nn \muskip_set_eq:NN { c }`
`\muskip_gset_eq:NN` 10333 `\cs_generate_variant:Nn \muskip_set_eq:NN { Nc , cc }`
`\muskip_gset_eq:cN` 10334 `__debug_patch:nnNNpn { __debug_chk_var_global:N #1 } { }`
`\muskip_gset_eq:Nc` 10335 `\cs_new_protected:Npn \muskip_gset_eq:NN #1#2 { \tex_global:D #1 = #2 }`
`\muskip_gset_eq:cc` 10336 `\cs_generate_variant:Nn \muskip_gset_eq:NN { c }`
10337 `\cs_generate_variant:Nn \muskip_gset_eq:NN { Nc , cc }`

(End definition for `\muskip_set_eq:NN` and `\muskip_gset_eq:NN`. These functions are documented on page 167.)

\muskip_add:Nn Using by here deals with the (incorrect) case \muskip123.

```

\muskip_add:cn 10338 \__dim_tmp:w \__debug_chk_var_local:N
\muskip_gadd:Nn 10339 \cs_new_protected:Npn \muskip_add:Nn #1#2
\muskip_gadd:cn 10340 { \tex_advance:D #1 by \etex_muexpr:D #2 \scan_stop: }
\muskip_sub:Nn 10341 \__dim_tmp:w \__debug_chk_var_global:N
\muskip_sub:cn 10342 \cs_new_protected:Npn \muskip_gadd:Nn #1#2
\muskip_gsub:Nn 10343 { \tex_global:D \tex_advance:D #1 by \etex_muexpr:D #2 \scan_stop: }
\muskip_gsub:cn 10344 \cs_generate_variant:Nn \muskip_add:Nn { c }
10345 \cs_generate_variant:Nn \muskip_gadd:Nn { c }
10346 \__dim_tmp:w \__debug_chk_var_local:N
10347 \cs_new_protected:Npn \muskip_sub:Nn #1#2
10348 { \tex_advance:D #1 by - \etex_muexpr:D #2 \scan_stop: }
10349 \__dim_tmp:w \__debug_chk_var_global:N
10350 \cs_new_protected:Npn \muskip_gsub:Nn #1#2
10351 { \tex_global:D \tex_advance:D #1 by - \etex_muexpr:D #2 \scan_stop: }
10352 \cs_generate_variant:Nn \muskip_sub:Nn { c }
10353 \cs_generate_variant:Nn \muskip_gsub:Nn { c }

```

(End definition for \muskip_add:Nn and others. These functions are documented on page 166.)

18.21 Using muskip expressions and variables

\muskip_eval:n Evaluating a muskip expression expandably.

```

10354 \__debug_patch_args:nNNpn
10355 {
10356   {
10357     \__debug_chk_expr:nNnN {#1} \etex_muexpr:D
10358     { \etex_mutogluue:D } \muskip_eval:n
10359   }
10360 }
10361 \cs_new:Npn \muskip_eval:n #1
10362 { \muskip_use:N \etex_muexpr:D #1 \scan_stop: }

```

(End definition for \muskip_eval:n. This function is documented on page 167.)

\muskip_use:N Accessing a $\langle muskip \rangle$.

```

\muskip_use:c 10363 \cs_new_eq:NN \muskip_use:N \tex_the:D
10364 \cs_generate_variant:Nn \muskip_use:N { c }

```

(End definition for \muskip_use:N. This function is documented on page 167.)

18.22 Viewing muskip variables

\muskip_show:N Diagnostics.

```

\muskip_show:c 10365 \cs_new_eq:NN \muskip_show:N \__kernel_register_show:N
10366 \cs_generate_variant:Nn \muskip_show:N { c }

```

(End definition for \muskip_show:N. This function is documented on page 167.)

\muskip_show:n Diagnostics. We don't use the T_EX primitive \showthe to show muskip expressions: this gives a more unified output.

```

10367 \cs_new_protected:Npn \muskip_show:n
10368 { \msg_show_eval:Nn \muskip_eval:n }

```

(End definition for `\muskip_show:n`. This function is documented on page 167.)

```
\muskip_log:N Diagnostics. Redirect output of \muskip_show:n to the log.
\muskip_log:c 10369 \cs_new_eq:NN \muskip_log:N \__kernel_register_log:N
\muskip_log:n 10370 \cs_new_eq:NN \muskip_log:c \__kernel_register_log:c
10371 \cs_new_protected:Npn \muskip_log:n
10372 { \msg_log_eval:Nn \muskip_eval:n }
```

(End definition for `\muskip_log:N` and `\muskip_log:n`. These functions are documented on page 168.)

18.23 Constant muskips

```
\c_zero_muskip Constant muskips given by their value.
\c_max_muskip 10373 \muskip_const:Nn \c_zero_muskip { 0 mu }
10374 \muskip_const:Nn \c_max_muskip { 16383.99999 mu }
```

(End definition for `\c_zero_muskip` and `\c_max_muskip`. These functions are documented on page 168.)

18.24 Scratch muskips

```
\l_tmpa_muskip We provide two local and two global scratch registers, maybe we need more or less.
\l_tmpb_muskip 10375 \muskip_new:N \l_tmpa_muskip
\g_tmpa_muskip 10376 \muskip_new:N \l_tmpb_muskip
\g_tmpb_muskip 10377 \muskip_new:N \g_tmpa_muskip
10378 \muskip_new:N \g_tmpb_muskip
```

(End definition for `\l_tmpa_muskip` and others. These variables are documented on page 168.)

```
10379 </initex | package>
```

19 l3keys Implementation

```
10380 <*initex | package>
```

19.1 Low-level interface

The low-level key parser is based heavily on `keyval`, but with a number of additional “safety” requirements and with the idea that the parsed list of key–value pairs can be processed in a variety of ways. The net result is that this code needs around twice the amount of time as `keyval` to parse the same list of keys. To optimise speed as far as reasonably practical, a number of lower-level approaches are taken rather than using the higher-level `expl3` interfaces.

```
10381 <@@=keyval>
```

```
\l__keyval_key_tl The current key name and value.
\l__keyval_value_tl 10382 \tl_new:N \l__keyval_key_tl
10383 \tl_new:N \l__keyval_value_tl
```

(End definition for `\l__keyval_key_tl` and `\l__keyval_value_tl`.)

```
\l__keyval_sanitise_tl A token list variable for dealing with awkward category codes in the input.
10384 \tl_new:N \l__keyval_sanitise_tl
```

(End definition for `\l__keyval_sanitise_tl`.)

`\keyval_parse:NNn` The main function starts off by normalising category codes in package mode. That’s relatively “expensive” so is skipped (hopefully) in format mode. We then hand off to the parser. The use of `\q_mark` here prevents loss of braces from the key argument. This particular quark is chosen as it fits in with `__tl_trim_spaces:nn` and allows a performance enhancement as the token can be carried through. Notice that by passing the two processor commands along the input stack we avoid the need to track these at all.

```

10385 \cs_new_protected:Npn \keyval_parse:NNn #1#2#3
10386 {
10387   \*initex
10388   \__keyval_loop:NNw #1#2 \q_mark #3 , \q_recursion_tail ,
10389   \*initex
10390   \*package
10391   \tl_set:Nn \l__keyval_sanitise_tl {#3}
10392   \__keyval_sanitise_equals:
10393   \__keyval_sanitise_comma:
10394   \exp_after:wN \__keyval_loop:NNw \exp_after:wN #1 \exp_after:wN #2
10395   \exp_after:wN \q_mark \l__keyval_sanitise_tl , \q_recursion_tail ,
10396   \*package
10397 }

```

(End definition for `\keyval_parse:NNn`. This function is documented on page 182.)

`__keyval_sanitise_equals:` A reasonably fast search and replace set up specifically for the active tokens. The nature of the input is known so everything is hard-coded. With only two tokens to cover, the speed gain from using dedicated functions is worth it.

```

\__keyval_sanitise_equals:
\__keyval_sanitise_comma:
  \__keyval_sanitise_equals_auxi:w
  \__keyval_sanitise_equals_auxii:w
  \__keyval_sanitise_comma_auxi:w
  \__keyval_sanitise_comma_auxii:w
\__keyval_sanitise_aux:w
10398 \*package
10399 \group_begin:
10400   \char_set_catcode_active:n { \ = }
10401   \char_set_catcode_active:n { \ , }
10402   \cs_new_protected:Npn \__keyval_sanitise_equals:
10403   {
10404     \exp_after:wN \__keyval_sanitise_equals_auxi:w \l__keyval_sanitise_tl
10405     \q_mark = \q_nil =
10406     \exp_after:wN \__keyval_sanitise_aux:w \l__keyval_sanitise_tl
10407   }
10408   \cs_new_protected:Npn \__keyval_sanitise_equals_auxi:w #1 =
10409   {
10410     \tl_set:Nn \l__keyval_sanitise_tl {#1}
10411     \__keyval_sanitise_equals_auxii:w
10412   }
10413   \cs_new_protected:Npn \__keyval_sanitise_equals_auxii:w #1 =
10414   {
10415     \if_meaning:w \q_nil #1 \scan_stop:
10416     \else:
10417       \tl_set:Nx \l__keyval_sanitise_tl
10418       {
10419         \exp_not:o \l__keyval_sanitise_tl
10420         \token_to_str:N =
10421         \exp_not:n {#1}
10422       }
10423       \exp_after:wN \__keyval_sanitise_equals_auxii:w
10424     \fi:

```

```

10425     }
10426 \cs_new_protected:Npn \__keyval_sanitise_comma:
10427 {
10428   \exp_after:wN \__keyval_sanitise_comma_auxi:w \l__keyval_sanitise_tl
10429   \q_mark , \q_nil ,
10430   \exp_after:wN \__keyval_sanitise_aux:w \l__keyval_sanitise_tl
10431 }
10432 \cs_new_protected:Npn \__keyval_sanitise_comma_auxi:w #1 ,
10433 {
10434   \tl_set:Nn \l__keyval_sanitise_tl {#1}
10435   \__keyval_sanitise_comma_auxii:w
10436 }
10437 \cs_new_protected:Npn \__keyval_sanitise_comma_auxii:w #1 ,
10438 {
10439   \if_meaning:w \q_nil #1 \scan_stop:
10440   \else:
10441     \tl_set:Nx \l__keyval_sanitise_tl
10442     {
10443       \exp_not:o \l__keyval_sanitise_tl
10444       \token_to_str:N ,
10445       \exp_not:n {#1}
10446     }
10447     \exp_after:wN \__keyval_sanitise_comma_auxii:w
10448   \fi:
10449 }
10450 \group_end:
10451 \cs_new_protected:Npn \__keyval_sanitise_aux:w #1 \q_mark
10452 { \tl_set:Nn \l__keyval_sanitise_tl {#1} }
10453 \</package>

```

(End definition for __keyval_sanitise_equals: and others.)

__keyval_loop:NNw A fast test for the end of the loop, remembering to remove the leading quark first. Assuming that is not the case, look for a key and value then loop around, re-inserting a leading quark in front of the next position.

```

10454 \cs_new_protected:Npn \__keyval_loop:NNw #1#2#3 ,
10455 {
10456   \exp_after:wN \if_meaning:w \exp_after:wN \q_recursion_tail
10457   \use_none:n #3 \prg_do_nothing:
10458   \else:
10459     \__keyval_split:NNw #1#2#3 == \q_stop
10460     \exp_after:wN \__keyval_loop:NNw \exp_after:wN #1 \exp_after:wN #2
10461     \exp_after:wN \q_mark
10462   \fi:
10463 }

```

(End definition for __keyval_loop:NNw.)

__keyval_split:NNw The value is picked up separately from the key so there can be another quark inserted
 __keyval_split_value:NNw at the front, keeping braces and allowing both parts to share the same code paths. The
 __keyval_split_tidy:w key is found first then there's a check that there is something there: this is biased to the
 __keyval_action: common case of there actually being a key. For the value, we first need to see if there is
 anything to do: if there is, extract it. The appropriate action is then inserted in front

of the key and value. Doing this using an assignment is marginally faster than an expansion chain.

```

10464 \cs_new_protected:Npn \__keyval_split:NNw #1#2#3 =
10465 {
10466   \__keyval_def:Nn \l__keyval_key_tl {#3}
10467   \if_meaning:w \l__keyval_key_tl \c_empty_tl
10468     \exp_after:wN \__keyval_split_tidy:w
10469   \else:
10470     \exp_after:wN \__keyval_split_value:NNw \exp_after:wN #1 \exp_after:wN #2
10471     \exp_after:wN \q_mark
10472   \fi:
10473 }
10474 \cs_new_protected:Npn \__keyval_split_value:NNw #1#2#3 = #4 \q_stop
10475 {
10476   \if:w \scan_stop: \tl_to_str:n {#4} \scan_stop:
10477     \cs_set:Npx \__keyval_action:
10478       { \exp_not:N #1 { \exp_not:o \l__keyval_key_tl } }
10479   \else:
10480     \if:w \scan_stop: \etex_detokenize:D \exp_after:wN { \use_none:n #4 }
10481     \scan_stop:
10482     \__keyval_def:Nn \l__keyval_value_tl {#3}
10483     \cs_set:Npx \__keyval_action:
10484       {
10485         \exp_not:N #2
10486         { \exp_not:o \l__keyval_key_tl }
10487         { \exp_not:o \l__keyval_value_tl }
10488       }
10489     \else:
10490     \cs_set:Npn \__keyval_action:
10491       { \__msg_kernel_error:nn { kernel } { misplaced-equals-sign } }
10492     \fi:
10493   \fi:
10494   \__keyval_action:
10495 }
10496 \cs_new_protected:Npn \__keyval_split_tidy:w #1 \q_stop
10497 {
10498   \if:w \scan_stop: \etex_detokenize:D \exp_after:wN { \use_none:n #1 }
10499   \scan_stop:
10500   \else:
10501     \exp_after:wN \__keyval_empty_key:
10502   \fi:
10503 }
10504 \cs_new:Npn \__keyval_action: { }
10505 \cs_new_protected:Npn \__keyval_empty_key:
10506   { \__msg_kernel_error:nn { kernel } { misplaced-equals-sign } }

```

(End definition for __keyval_split:NNw and others.)

__keyval_def:Nn First trim spaces off, then potentially remove a set of braces. By using the internal
 __keyval_def_aux:n interface __tl_trim_spaces:nn we can take advantage of the fact it needs a leading
 __keyval_def_aux:w \q_mark in this process. The \exp_after:wN removes the quark, the delimited argument
 deals with any braces.

```

10507 \cs_new_protected:Npn \__keyval_def:Nn #1#2
10508   { \tl_set:Nx #1 { \__tl_trim_spaces:nn {#2} \__keyval_def_aux:n } }

```

```

10509 \cs_new:Npn \__keyval_def_aux:n #1
10510 { \exp_after:wN \__keyval_def_aux:w #1 \q_stop }
10511 \cs_new:Npn \__keyval_def_aux:w #1 \q_stop { \exp_not:n {#1} }

(End definition for \__keyval_def:Nn, \__keyval_def_aux:n, and \__keyval_def_aux:w.)
One message for the low level parsing system.

10512 \__msg_kernel_new:nnnn { kernel } { misplaced-equals-sign }
10513 { Misplaced-equals-sign-in-key-value-input~\msg_line_number: }
10514 {
10515     LaTeX-is-attempting-to-parse-some-key-value-input-but-found~
10516     two-equals-signs-not-separated-by-a-comma.
10517 }

```

19.2 Constants and variables

```

10518 <@@=keys>

```

Various storage areas for the different data which make up keys.

```

\c__keys_code_root_tl
\c__keys_default_root_tl
\c__keys_groups_root_tl
\c__keys_inherit_root_tl
\c__keys_type_root_tl
\c__keys_validate_root_tl
10519 \tl_const:Nn \c__keys_code_root_tl { key~code~>~ }
10520 \tl_const:Nn \c__keys_default_root_tl { key~default~>~ }
10521 \tl_const:Nn \c__keys_groups_root_tl { key~groups~>~ }
10522 \tl_const:Nn \c__keys_inherit_root_tl { key~inherit~>~ }
10523 \tl_const:Nn \c__keys_type_root_tl { key~type~>~ }
10524 \tl_const:Nn \c__keys_validate_root_tl { key~validate~>~ }

```

(End definition for \c__keys_code_root_tl and others.)

\c__keys_props_root_tl The prefix for storing properties.

```

10525 \tl_const:Nn \c__keys_props_root_tl { key~prop~>~ }

```

(End definition for \c__keys_props_root_tl.)

\l_keys_choice_int Publicly accessible data on which choice is being used when several are generated as a set.

```

10526 \int_new:N \l_keys_choice_int
10527 \tl_new:N \l_keys_choice_tl

```

(End definition for \l_keys_choice_int and \l_keys_choice_tl. These variables are documented on page 176.)

\l__keys_groups_clist Used for storing and recovering the list of groups which apply to a key: set as a comma list but at one point we have to use this for a token list recovery.

```

10528 \clist_new:N \l__keys_groups_clist

```

(End definition for \l__keys_groups_clist.)

\l_keys_key_tl The name of a key itself: needed when setting keys.

```

10529 \tl_new:N \l_keys_key_tl

```

(End definition for \l_keys_key_tl. This variable is documented on page 178.)

\l__keys_module_tl The module for an entire set of keys.

```

10530 \tl_new:N \l__keys_module_tl

```

(End definition for \l__keys_module_tl.)

`\l__keys_no_value_bool` A marker is needed internally to show if only a key or a key plus a value was seen: this is recorded here.

```
10531 \bool_new:N \l__keys_no_value_bool
```

(End definition for \l__keys_no_value_bool.)

`\l__keys_only_known_bool` Used to track if only “known” keys are being set.

```
10532 \bool_new:N \l__keys_only_known_bool
```

(End definition for \l__keys_only_known_bool.)

`\l_keys_path_tl` The “path” of the current key is stored here: this is available to the programmer and so is public.

```
10533 \tl_new:N \l_keys_path_tl
```

(End definition for \l_keys_path_tl. This variable is documented on page 178.)

`\l__keys_property_tl` The “property” begin set for a key at definition time is stored here.

```
10534 \tl_new:N \l__keys_property_tl
```

(End definition for \l__keys_property_tl.)

`\l__keys_selective_bool` Two flags for using key groups: one to indicate that “selective” setting is active, a second to specify which type (“opt-in” or “opt-out”).

```
10535 \bool_new:N \l__keys_selective_bool
10536 \bool_new:N \l__keys_filtered_bool
```

(End definition for \l__keys_selective_bool and \l__keys_filtered_bool.)

`\l__keys_selective_seq` The list of key groups being filtered in or out during selective setting.

```
10537 \seq_new:N \l__keys_selective_seq
```

(End definition for \l__keys_selective_seq.)

`\l__keys_unused_clist` Used when setting only some keys to store those left over.

```
10538 \tl_new:N \l__keys_unused_clist
```

(End definition for \l__keys_unused_clist.)

`\l_keys_value_tl` The value given for a key: may be empty if no value was given.

```
10539 \tl_new:N \l_keys_value_tl
```

(End definition for \l_keys_value_tl. This variable is documented on page 178.)

`\l__keys_tmp_bool` Scratch space.

```
10540 \bool_new:N \l__keys_tmp_bool
```

(End definition for \l__keys_tmp_bool.)

19.3 The key defining mechanism

`\keys_define:nn` The public function for definitions is just a wrapper for the lower level mechanism, more or less. The outer function is designed to keep a track of the current module, to allow safe nesting. The module is set removing any leading / (which is not needed here).

```

10541 \cs_new_protected:Npn \keys_define:nn
10542   { \__keys_define:onn \l__keys_module_tl }
10543 \cs_new_protected:Npn \__keys_define:nnn #1#2#3
10544   {
10545     \tl_set:Nx \l__keys_module_tl { \__keys_remove_spaces:n {#2} }
10546     \keyval_parse:NNn \__keys_define:n \__keys_define:nn {#3}
10547     \tl_set:Nn \l__keys_module_tl {#1}
10548   }
10549 \cs_generate_variant:Nn \__keys_define:nnn { o }

```

(End definition for \keys_define:nn and __keys_define:nnn. This function is documented on page 171.)

`__keys_define:n` The outer functions here record whether a value was given and then converge on a common internal mechanism. There is first a search for a property in the current key name, then a check to make sure it is known before the code hands off to the next step.

```

10550 \cs_new_protected:Npn \__keys_define:n #1
10551   {
10552     \bool_set_true:N \l__keys_no_value_bool
10553     \__keys_define_aux:nn {#1} { }
10554   }
10555 \cs_new_protected:Npn \__keys_define:nn #1#2
10556   {
10557     \bool_set_false:N \l__keys_no_value_bool
10558     \__keys_define_aux:nn {#1} {#2}
10559   }
10560 \cs_new_protected:Npn \__keys_define_aux:nn #1#2
10561   {
10562     \__keys_property_find:n {#1}
10563     \cs_if_exist:cTF { \c__keys_props_root_tl \l__keys_property_tl }
10564       { \__keys_define_code:n {#2} }
10565       {
10566         \tl_if_empty:NF \l__keys_property_tl
10567         {
10568           \__msg_kernel_error:nnxx { kernel } { property-unknown }
10569           { \l__keys_property_tl } { \l_keys_path_tl }
10570         }
10571       }
10572   }

```

(End definition for __keys_define:n, __keys_define:nn, and __keys_define_aux:nn.)

`__keys_property_find:n` Searching for a property means finding the last . in the input, and storing the text before and after it. Everything is turned into strings, so there is no problem using an x-type expansion.

```

10573 \cs_new_protected:Npn \__keys_property_find:n #1
10574   {
10575     \tl_set:Nx \l__keys_property_tl { \__keys_remove_spaces:n {#1} }
10576     \exp_after:wN \__keys_property_find:w \l__keys_property_tl . . \q_stop {#1}

```



```

10577     }
10578 \cs_new_protected:Npn \__keys_property_find:w #1 . #2 . #3 \q_stop #4
10579 {
10580     \tl_if_blank:nTF {#3}
10581     {
10582         \tl_clear:N \l__keys_property_tl
10583         \__msg_kernel_error:nnn { kernel } { key-no-property } {#4}
10584     }
10585     {
10586         \str_if_eq:nnTF {#3} { . }
10587         {
10588             \tl_set:Nx \l_keys_path_tl
10589             {
10590                 \tl_if_empty:NF \l__keys_module_tl
10591                 { \l__keys_module_tl / }
10592                 #1
10593             }
10594             \tl_set:Nn \l__keys_property_tl { . #2 }
10595         }
10596         {
10597             \tl_set:Nx \l_keys_path_tl { \l__keys_module_tl / #1 . #2 }
10598             \__keys_property_search:w #3 \q_stop
10599         }
10600     }
10601 }
10602 \cs_new_protected:Npn \__keys_property_search:w #1 . #2 \q_stop
10603 {
10604     \str_if_eq:nnTF {#2} { . }
10605     {
10606         \tl_set:Nx \l_keys_path_tl { \l_keys_path_tl }
10607         \tl_set:Nn \l__keys_property_tl { . #1 }
10608     }
10609     {
10610         \tl_set:Nx \l_keys_path_tl { \l_keys_path_tl . #1 }
10611         \__keys_property_search:w #2 \q_stop
10612     }
10613 }

```

(End definition for __keys_property_find:n and __keys_property_find:w.)

__keys_define_code:n Two possible cases. If there is a value for the key, then just use the function. If not, then
 __keys_define_code:w a check to make sure there is no need for a value with the property. If there should be
 one then complain, otherwise execute it. There is no need to check for a : as if it was
 missing the earlier tests would have failed.

```

10614 \cs_new_protected:Npn \__keys_define_code:n #1
10615 {
10616     \bool_if:NTF \l__keys_no_value_bool
10617     {
10618         \exp_after:wN \__keys_define_code:w
10619         \l__keys_property_tl \q_stop
10620         { \use:c { \c__keys_props_root_tl \l__keys_property_tl } }
10621         {
10622             \__msg_kernel_error:nxxx { kernel }
10623             { property-requires-value } { \l__keys_property_tl }

```

```

10624         { \l_keys_path_tl }
10625     }
10626 }
10627 { \use:c { \c__keys_props_root_tl \l__keys_property_tl } {#1} }
10628 }
10629 \use:x
10630 {
10631     \cs_new:Npn \exp_not:N \__keys_define_code:w
10632         ##1 \c_colon_str ##2 \exp_not:N \q_stop
10633 }
10634 { \tl_if_empty:nTF {#2} }

```

(End definition for `__keys_define_code:n` and `__keys_define_code:w`.)

19.4 Turning properties into actions

`__keys_bool_set:Nn` Boolean keys are really just choices, but all done by hand. The second argument here is the scope: either empty or `g` for global.

```

10635 \cs_new_protected:Npn \__keys_bool_set:Nn #1#2
10636 {
10637     \bool_if_exist:NF #1 { \bool_new:N #1 }
10638     \__keys_choice_make:
10639     \__keys_cmd_set:nx { \l_keys_path_tl / true }
10640     { \exp_not:c { bool_ #2 set_true:N } \exp_not:N #1 }
10641     \__keys_cmd_set:nx { \l_keys_path_tl / false }
10642     { \exp_not:c { bool_ #2 set_false:N } \exp_not:N #1 }
10643     \__keys_cmd_set:nn { \l_keys_path_tl / unknown }
10644     {
10645         \_msg_kernel_error:nxx { kernel } { boolean-values-only }
10646         { \l_keys_key_tl }
10647     }
10648     \__keys_default_set:n { true }
10649 }
10650 \cs_generate_variant:Nn \__keys_bool_set:Nn { c }

```

(End definition for `__keys_bool_set:Nn`.)

`__keys_bool_set_inverse:Nn` Inverse boolean setting is much the same.

```

10651 \cs_new_protected:Npn \__keys_bool_set_inverse:Nn #1#2
10652 {
10653     \bool_if_exist:NF #1 { \bool_new:N #1 }
10654     \__keys_choice_make:
10655     \__keys_cmd_set:nx { \l_keys_path_tl / true }
10656     { \exp_not:c { bool_ #2 set_false:N } \exp_not:N #1 }
10657     \__keys_cmd_set:nx { \l_keys_path_tl / false }
10658     { \exp_not:c { bool_ #2 set_true:N } \exp_not:N #1 }
10659     \__keys_cmd_set:nn { \l_keys_path_tl / unknown }
10660     {
10661         \_msg_kernel_error:nxx { kernel } { boolean-values-only }
10662         { \l_keys_key_tl }
10663     }
10664     \__keys_default_set:n { true }
10665 }
10666 \cs_generate_variant:Nn \__keys_bool_set_inverse:Nn { c }

```

(End definition for `_keys_bool_set_inverse:Nn`.)

`_keys_choice_make:` To make a choice from a key, two steps: set the code, and set the unknown key. As
`_keys_multichoice_make:` multichoice and choices are essentially the same bar one function, the code is given
`_keys_choice_make:N` together.
`_keys_choice_make_aux:N`

```

10667 \cs_new_protected:Npn \_keys_choice_make:
10668   { \_keys_choice_make:N \_keys_choice_find:n }
10669 \cs_new_protected:Npn \_keys_multichoice_make:
10670   { \_keys_choice_make:N \_keys_multichoice_find:n }
10671 \cs_new_protected:Npn \_keys_choice_make:N #1
10672   {
10673     \cs_if_exist:cTF
10674       { \c__keys_type_root_tl \_keys_parent:o \l_keys_path_tl }
10675       {
10676         \str_if_eq_x:nnTF
10677           { \exp_not:v { \c__keys_type_root_tl \_keys_parent:o \l_keys_path_tl } }
10678           { choice }
10679           {
10680             \_msg_kernel_error:nxx { kernel } { nested-choice-key }
10681             { \l_keys_path_tl } { \_keys_parent:o \l_keys_path_tl }
10682           }
10683           { \_keys_choice_make_aux:N #1 }
10684         }
10685         { \_keys_choice_make_aux:N #1 }
10686       }
10687 \cs_new_protected:Npn \_keys_choice_make_aux:N #1
10688   {
10689     \cs_set_nopar:cpn { \c__keys_type_root_tl \l_keys_path_tl } { choice }
10690     \_keys_cmd_set:nn { \l_keys_path_tl } { #1 {##1} }
10691     \_keys_cmd_set:nn { \l_keys_path_tl / unknown }
10692     {
10693       \_msg_kernel_error:nxx { kernel } { key-choice-unknown }
10694       { \l_keys_path_tl } {##1}
10695     }
10696   }

```

(End definition for `_keys_choice_make:` and others.)

`_keys_choices_make:nn` Auto-generating choices means setting up the root key as a choice, then defining each
`_keys_multichoice_make:nn` choice in turn.
`_keys_choices_make:Nnn`

```

10697 \cs_new_protected:Npn \_keys_choices_make:nn
10698   { \_keys_choices_make:Nnn \_keys_choice_make: }
10699 \cs_new_protected:Npn \_keys_multichoice_make:nn
10700   { \_keys_choices_make:Nnn \_keys_multichoice_make: }
10701 \cs_new_protected:Npn \_keys_choices_make:Nnn #1#2#3
10702   {
10703     #1
10704     \int_zero:N \l_keys_choice_int
10705     \clist_map_inline:nn {#2}
10706     {
10707       \int_incr:N \l_keys_choice_int
10708       \_keys_cmd_set:nx { \l_keys_path_tl / \_keys_remove_spaces:n {##1} }
10709       {
10710         \tl_set:Nn \exp_not:N \l_keys_choice_tl {##1}

```

```

10711         \int_set:Nn \exp_not:N \l_keys_choice_int
10712         { \int_use:N \l_keys_choice_int }
10713         \exp_not:n {#3}
10714     }
10715 }
10716 }

```

(End definition for `__keys_choices_make:nn`, `__keys_multichoices_make:nn`, and `__keys_choices_make:Nnn`.)

`__keys_cmd_set:nn` Setting the code for a key first logs if appropriate that we are defining a new key, then saves the code.

```

\__keys_cmd_set:nx
\__keys_cmd_set:Vn
\__keys_cmd_set:Vo
10717 \__debug_patch:nnNNpn
10718 {
10719     \cs_if_exist:cF { \c__keys_code_root_tl #1 }
10720     { \__debug_log:x { Defining~key~#1~\msg_line_context: } }
10721 }
10722 { }
10723 \cs_new_protected:Npn \__keys_cmd_set:nn #1#2
10724 { \cs_set_protected:cpn { \c__keys_code_root_tl #1 } ##1 {#2} }
10725 \cs_generate_variant:Nn \__keys_cmd_set:nn { nx , Vn , Vo }

```

(End definition for `__keys_cmd_set:nn`.)

`__keys_default_set:n` Setting a default value is easy. These are stored using `\cs_set:cpx` as this avoids any worries about whether a token list exists.

```

10726 \cs_new_protected:Npn \__keys_default_set:n #1
10727 {
10728     \tl_if_empty:nTF {#1}
10729     {
10730         \cs_set_eq:cN
10731         { \c__keys_default_root_tl \l_keys_path_tl }
10732         \tex_undefined:D
10733     }
10734     {
10735         \cs_set:cpx
10736         { \c__keys_default_root_tl \l_keys_path_tl }
10737         { \exp_not:n {#1} }
10738     }
10739 }

```

(End definition for `__keys_default_set:n`.)

`__keys_groups_set:n` Assigning a key to one or more groups uses comma lists. As the list of groups only exists if there is anything to do, the setting is done using a scratch list. For the usual grouping reasons we use the low-level approach to undefining a list. We also use the low-level approach for the other case to avoid tripping up the `check-declarations` code.

```

10740 \cs_new_protected:Npn \__keys_groups_set:n #1
10741 {
10742     \clist_set:Nn \l__keys_groups_clist {#1}
10743     \clist_if_empty:NTF \l__keys_groups_clist
10744     {
10745         \cs_set_eq:cN { \c__keys_groups_root_tl \l_keys_path_tl }
10746         \tex_undefined:D

```

```

10747     }
10748     {
10749         \cs_set_eq:cN { \c__keys_groups_root_tl \l_keys_path_tl }
10750         \l__keys_groups_clist
10751     }
10752 }

```

(End definition for __keys_groups_set:n.)

__keys_inherit:n Inheritance means ignoring anything already said about the key: zap the lot and set up.

```

10753 \cs_new_protected:Npn \__keys_inherit:n #1
10754 {
10755     \__keys_undefine:
10756     \cs_set_nopar:cpn { \c__keys_inherit_root_tl \l_keys_path_tl } {#1}
10757 }

```

(End definition for __keys_inherit:n.)

__keys_initialise:n A set up for initialisation: just run the code if it exists.

```

10758 \cs_new_protected:Npn \__keys_initialise:n #1
10759 {
10760     \cs_if_exist_use:cT { \c__keys_code_root_tl \l_keys_path_tl } { {#1} }
10761 }

```

(End definition for __keys_initialise:n.)

__keys_meta_make:n To create a meta-key, simply set up to pass data through.

```

\__keys_meta_make:nn
10762 \cs_new_protected:Npn \__keys_meta_make:n #1
10763 {
10764     \__keys_cmd_set:Vo \l_keys_path_tl
10765     {
10766         \exp_after:wN \keys_set:nn
10767         \exp_after:wN { \l__keys_module_tl } {#1}
10768     }
10769 }
10770 \cs_new_protected:Npn \__keys_meta_make:nn #1#2
10771 { \__keys_cmd_set:Vn \l_keys_path_tl { \keys_set:nn {#1} {#2} } }

```

(End definition for __keys_meta_make:n and __keys_meta_make:nn.)

__keys_undefine: Undefined a key has to be done without \cs_undefine:c as that function acts globally.

```

10772 \cs_new_protected:Npn \__keys_undefine:
10773 {
10774     \clist_map_inline:nn
10775     { code , default , groups , inherit , type , validate }
10776     {
10777         \cs_set_eq:cN
10778         { \tl_use:c { c__keys_ ##1 _root_tl } \l_keys_path_tl }
10779         \tex_undefined:D
10780     }
10781 }

```

(End definition for __keys_undefine:.)

`__keys_value_requirement:nn` Validating key input is done using a second function which runs before the main key code. Setting that up means setting it equal to a generic stub which does the check. This approach makes the lookup very fast at the cost of one additional csname per key that needs it. The cleanup here has to know the structure of the following code.

```

10782 \cs_new_protected:Npn \__keys_value_requirement:nn #1#2
10783 {
10784   \str_case:nnF {#2}
10785   {
10786     { true }
10787     {
10788       \cs_set_eq:cc
10789       { \c__keys_validate_root_tl \l_keys_path_tl }
10790       { __keys_validate_ #1 : }
10791     }
10792   { false }
10793   {
10794     \cs_if_eq:ccT
10795     { \c__keys_validate_root_tl \l_keys_path_tl }
10796     { __keys_validate_ #1 : }
10797     {
10798       \cs_set_eq:cN
10799       { \c__keys_validate_root_tl \l_keys_path_tl }
10800       \tex_undefined:D
10801     }
10802   }
10803 }
10804 {
10805   \__msg_kernel_error:nnx { kernel } { property-boolean-values-only }
10806   { .value_ #1 :n }
10807 }
10808 }
10809 \cs_new_protected:Npn \__keys_validate_forbidden:
10810 {
10811   \bool_if:NF \l__keys_no_value_bool
10812   {
10813     \__msg_kernel_error:nnxx { kernel } { value-forbidden }
10814     { \l_keys_path_tl } { \l_keys_value_tl }
10815     \__keys_validate_cleanup:w
10816   }
10817 }
10818 \cs_new_protected:Npn \__keys_validate_required:
10819 {
10820   \bool_if:NT \l__keys_no_value_bool
10821   {
10822     \__msg_kernel_error:nnx { kernel } { value-required }
10823     { \l_keys_path_tl }
10824     \__keys_validate_cleanup:w
10825   }
10826 }
10827 \cs_new_protected:Npn \__keys_validate_cleanup:w #1 \cs_end: #2#3 { }
  
```

(End definition for __keys_value_requirement:nn and others.)

`__keys_variable_set:NnnN` Setting a variable takes the type and scope separately so that it is easy to make a new
`__keys_variable_set:cnnN`

variable if needed.

```

10828 \cs_new_protected:Npn \__keys_variable_set:NnnN #1#2#3#4
10829 {
10830   \use:c { #2_if_exist:NF } #1 { \use:c { #2_new:N } #1 }
10831   \__keys_cmd_set:nx { \l_keys_path_tl }
10832   {
10833     \exp_not:c { #2 _ #3 set:N #4 }
10834     \exp_not:N #1
10835     \exp_not:n { {##1} }
10836   }
10837 }
10838 \cs_generate_variant:Nn \__keys_variable_set:NnnN { c }

```

(End definition for `__keys_variable_set:NnnN`.)

19.5 Creating key properties

The key property functions are all wrappers for internal functions, meaning that things stay readable and can also be altered later on.

Importantly, while key properties have “normal” argument specs, the underlying code always supplies one braced argument to these. As such, argument expansion is handled by hand rather than using the standard tools. This shows up particularly for the two-argument properties, where things would otherwise go badly wrong.

```

.bool_set:N One function for this.
.bool_set:c 10839 \cs_new_protected:cpn { \c__keys_props_root_tl .bool_set:N } #1
.bool_gset:N 10840 { \__keys_bool_set:Nn #1 { } }
.bool_gset:c 10841 \cs_new_protected:cpn { \c__keys_props_root_tl .bool_set:c } #1
10842 { \__keys_bool_set:cn {#1} { } }
10843 \cs_new_protected:cpn { \c__keys_props_root_tl .bool_gset:N } #1
10844 { \__keys_bool_set:Nn #1 { g } }
10845 \cs_new_protected:cpn { \c__keys_props_root_tl .bool_gset:c } #1
10846 { \__keys_bool_set:cn {#1} { g } }

```

(End definition for `.bool_set:N` and `.bool_gset:N`. These functions are documented on page 172.)

```

.bool_set_inverse:N One function for this.
.bool_set_inverse:c 10847 \cs_new_protected:cpn { \c__keys_props_root_tl .bool_set_inverse:N } #1
.bool_gset_inverse:N 10848 { \__keys_bool_set_inverse:Nn #1 { } }
.bool_gset_inverse:c 10849 \cs_new_protected:cpn { \c__keys_props_root_tl .bool_set_inverse:c } #1
10850 { \__keys_bool_set_inverse:cn {#1} { } }
10851 \cs_new_protected:cpn { \c__keys_props_root_tl .bool_gset_inverse:N } #1
10852 { \__keys_bool_set_inverse:Nn #1 { g } }
10853 \cs_new_protected:cpn { \c__keys_props_root_tl .bool_gset_inverse:c } #1
10854 { \__keys_bool_set_inverse:cn {#1} { g } }

```

(End definition for `.bool_set_inverse:N` and `.bool_gset_inverse:N`. These functions are documented on page 172.)

`.choice:` Making a choice is handled internally, as it is also needed by `.generate_choices:n`.

```

10855 \cs_new_protected:cpn { \c__keys_props_root_tl .choice: }
10856 { \__keys_choice_make: }

```

(End definition for `.choice:`. This function is documented on page 172.)

.choices:nn For auto-generation of a series of mutually-exclusive choices. Here, #1 consists of two separate arguments, hence the slightly odd-looking implementation.

```
.choices:Vn
.choices:on
.choices:xn
10857 \cs_new_protected:cpn { \c__keys_props_root_tl .choices:nn } #1
10858 { \__keys_choices_make:nn #1 }
10859 \cs_new_protected:cpn { \c__keys_props_root_tl .choices:Vn } #1
10860 { \exp_args:NV \__keys_choices_make:nn #1 }
10861 \cs_new_protected:cpn { \c__keys_props_root_tl .choices:on } #1
10862 { \exp_args:No \__keys_choices_make:nn #1 }
10863 \cs_new_protected:cpn { \c__keys_props_root_tl .choices:xn } #1
10864 { \exp_args:Nx \__keys_choices_make:nn #1 }
```

(End definition for .choices:nn. This function is documented on page 172.)

.code:n Creating code is simply a case of passing through to the underlying set function.

```
10865 \cs_new_protected:cpn { \c__keys_props_root_tl .code:n } #1
10866 { \__keys_cmd_set:nn { \l_keys_path_tl } {#1} }
```

(End definition for .code:n. This function is documented on page 172.)

.clist_set:N

```
.clist_set:c
10867 \cs_new_protected:cpn { \c__keys_props_root_tl .clist_set:N } #1
10868 { \__keys_variable_set:NnnN #1 { clist } { } n }
.clist_gset:N
10869 \cs_new_protected:cpn { \c__keys_props_root_tl .clist_set:c } #1
10870 { \__keys_variable_set:cnnN {#1} { clist } { } n }
10871 \cs_new_protected:cpn { \c__keys_props_root_tl .clist_gset:N } #1
10872 { \__keys_variable_set:NnnN #1 { clist } { g } n }
10873 \cs_new_protected:cpn { \c__keys_props_root_tl .clist_gset:c } #1
10874 { \__keys_variable_set:cnnN {#1} { clist } { g } n }
```

(End definition for .clist_set:N and .clist_gset:N. These functions are documented on page 172.)

.default:n Expansion is left to the internal functions.

```
.default:V
10875 \cs_new_protected:cpn { \c__keys_props_root_tl .default:n } #1
10876 { \__keys_default_set:n {#1} }
.default:o
10877 \cs_new_protected:cpn { \c__keys_props_root_tl .default:V } #1
10878 { \exp_args:NV \__keys_default_set:n #1 }
.default:x
10879 \cs_new_protected:cpn { \c__keys_props_root_tl .default:o } #1
10880 { \exp_args:No \__keys_default_set:n {#1} }
10881 \cs_new_protected:cpn { \c__keys_props_root_tl .default:x } #1
10882 { \exp_args:Nx \__keys_default_set:n {#1} }
```

(End definition for .default:n. This function is documented on page 173.)

.dim_set:N Setting a variable is very easy: just pass the data along.

```
.dim_set:c
10883 \cs_new_protected:cpn { \c__keys_props_root_tl .dim_set:N } #1
10884 { \__keys_variable_set:NnnN #1 { dim } { } n }
.clist_gset:N
10885 \cs_new_protected:cpn { \c__keys_props_root_tl .dim_set:c } #1
10886 { \__keys_variable_set:cnnN {#1} { dim } { } n }
10887 \cs_new_protected:cpn { \c__keys_props_root_tl .dim_gset:N } #1
10888 { \__keys_variable_set:NnnN #1 { dim } { g } n }
10889 \cs_new_protected:cpn { \c__keys_props_root_tl .dim_gset:c } #1
10890 { \__keys_variable_set:cnnN {#1} { dim } { g } n }
```

(End definition for .dim_set:N and .dim_gset:N. These functions are documented on page 173.)

.fp_set:N Setting a variable is very easy: just pass the data along.

```

10891 \cs_new_protected:cpn { \c__keys_props_root_tl .fp_set:N } #1
10892 { \__keys_variable_set:NnnN #1 { fp } { } n }
.fp_gset:N
10893 \cs_new_protected:cpn { \c__keys_props_root_tl .fp_set:c } #1
10894 { \__keys_variable_set:cnnN {#1} { fp } { } n }
.fp_gset:c
10895 \cs_new_protected:cpn { \c__keys_props_root_tl .fp_gset:N } #1
10896 { \__keys_variable_set:NnnN #1 { fp } { g } n }
10897 \cs_new_protected:cpn { \c__keys_props_root_tl .fp_gset:c } #1
10898 { \__keys_variable_set:cnnN {#1} { fp } { g } n }

```

(End definition for .fp_set:N and .fp_gset:N. These functions are documented on page 173.)

.groups:n A single property to create groups of keys.

```

10899 \cs_new_protected:cpn { \c__keys_props_root_tl .groups:n } #1
10900 { \__keys_groups_set:n {#1} }

```

(End definition for .groups:n. This function is documented on page 173.)

.inherit:n Nothing complex: only one variant at the moment!

```

10901 \cs_new_protected:cpn { \c__keys_props_root_tl .inherit:n } #1
10902 { \__keys_inherit:n {#1} }

```

(End definition for .inherit:n. This function is documented on page 173.)

.initial:n The standard hand-off approach.

```

10903 \cs_new_protected:cpn { \c__keys_props_root_tl .initial:n } #1
10904 { \__keys_initialise:n {#1} }
.initial:V
10905 \cs_new_protected:cpn { \c__keys_props_root_tl .initial:V } #1
10906 { \exp_args:NV \__keys_initialise:n #1 }
.initial:o
10907 \cs_new_protected:cpn { \c__keys_props_root_tl .initial:o } #1
10908 { \exp_args:No \__keys_initialise:n {#1} }
.initial:x
10909 \cs_new_protected:cpn { \c__keys_props_root_tl .initial:x } #1
10910 { \exp_args:Nx \__keys_initialise:n {#1} }

```

(End definition for .initial:n. This function is documented on page 174.)

.int_set:N Setting a variable is very easy: just pass the data along.

```

10911 \cs_new_protected:cpn { \c__keys_props_root_tl .int_set:N } #1
10912 { \__keys_variable_set:NnnN #1 { int } { } n }
.int_gset:N
10913 \cs_new_protected:cpn { \c__keys_props_root_tl .int_set:c } #1
10914 { \__keys_variable_set:cnnN {#1} { int } { } n }
.int_gset:c
10915 \cs_new_protected:cpn { \c__keys_props_root_tl .int_gset:N } #1
10916 { \__keys_variable_set:NnnN #1 { int } { g } n }
10917 \cs_new_protected:cpn { \c__keys_props_root_tl .int_gset:c } #1
10918 { \__keys_variable_set:cnnN {#1} { int } { g } n }

```

(End definition for .int_set:N and .int_gset:N. These functions are documented on page 174.)

.meta:n Making a meta is handled internally.

```

10919 \cs_new_protected:cpn { \c__keys_props_root_tl .meta:n } #1
10920 { \__keys_meta_make:n {#1} }

```

(End definition for .meta:n. This function is documented on page 174.)

.meta:nn Meta with path: potentially lots of variants, but for the moment no so many defined.

```
10921 \cs_new_protected:cpn { \c__keys_props_root_tl .meta:nn } #1
10922 { \__keys_meta_make:nn #1 }
```

(End definition for .meta:nn. This function is documented on page 174.)

.multichoice: The same idea as .choice: and .choices:nn, but where more than one choice is allowed.

```
.multichoices:nn 10923 \cs_new_protected:cpn { \c__keys_props_root_tl .multichoice: }
10924 { \__keys_multichoice_make: }
.multichoices:Vn 10925 \cs_new_protected:cpn { \c__keys_props_root_tl .multichoices:nn } #1
10926 { \__keys_multichoices_make:nn #1 }
.multichoices:on 10927 \cs_new_protected:cpn { \c__keys_props_root_tl .multichoices:Vn } #1
10928 { \exp_args:NV \__keys_multichoices_make:nn #1 }
.multichoices:xn 10929 \cs_new_protected:cpn { \c__keys_props_root_tl .multichoices:on } #1
10930 { \exp_args:No \__keys_multichoices_make:nn #1 }
10931 \cs_new_protected:cpn { \c__keys_props_root_tl .multichoices:xn } #1
10932 { \exp_args:Nx \__keys_multichoices_make:nn #1 }
```

(End definition for .multichoice: and .multichoices:nn. These functions are documented on page 174.)

.skip_set:N Setting a variable is very easy: just pass the data along.

```
.skip_set:c 10933 \cs_new_protected:cpn { \c__keys_props_root_tl .skip_set:N } #1
10934 { \__keys_variable_set:NnnN #1 { skip } { } n }
.skip_gset:N 10935 \cs_new_protected:cpn { \c__keys_props_root_tl .skip_set:c } #1
10936 { \__keys_variable_set:cnnN {#1} { skip } { } n }
10937 \cs_new_protected:cpn { \c__keys_props_root_tl .skip_gset:N } #1
10938 { \__keys_variable_set:NnnN #1 { skip } { g } n }
10939 \cs_new_protected:cpn { \c__keys_props_root_tl .skip_gset:c } #1
10940 { \__keys_variable_set:cnnN {#1} { skip } { g } n }
```

(End definition for .skip_set:N and .skip_gset:N. These functions are documented on page 174.)

.tl_set:N Setting a variable is very easy: just pass the data along.

```
.tl_set:c 10941 \cs_new_protected:cpn { \c__keys_props_root_tl .tl_set:N } #1
10942 { \__keys_variable_set:NnnN #1 { tl } { } n }
.tl_gset:N 10943 \cs_new_protected:cpn { \c__keys_props_root_tl .tl_set:c } #1
10944 { \__keys_variable_set:cnnN {#1} { tl } { } n }
.tl_set_x:N 10945 \cs_new_protected:cpn { \c__keys_props_root_tl .tl_set_x:N } #1
10946 { \__keys_variable_set:NnnN #1 { tl } { } x }
.tl_gset_x:N 10947 \cs_new_protected:cpn { \c__keys_props_root_tl .tl_set_x:c } #1
10948 { \__keys_variable_set:cnnN {#1} { tl } { } x }
10949 \cs_new_protected:cpn { \c__keys_props_root_tl .tl_gset:N } #1
10950 { \__keys_variable_set:NnnN #1 { tl } { g } n }
10951 \cs_new_protected:cpn { \c__keys_props_root_tl .tl_gset:c } #1
10952 { \__keys_variable_set:cnnN {#1} { tl } { g } n }
10953 \cs_new_protected:cpn { \c__keys_props_root_tl .tl_gset_x:N } #1
10954 { \__keys_variable_set:NnnN #1 { tl } { g } x }
10955 \cs_new_protected:cpn { \c__keys_props_root_tl .tl_gset_x:c } #1
10956 { \__keys_variable_set:cnnN {#1} { tl } { g } x }
```

(End definition for .tl_set:N and others. These functions are documented on page 174.)

.undefine: Another simple wrapper.

```
10957 \cs_new_protected:cpn { \c__keys_props_root_tl .undefine: }
10958 { \__keys_undefine: }
```

(End definition for `.undefine:.`. This function is documented on page 175.)

`.value_forbidden:n` These are very similar, so both call the same function.

```
.value_required:n
10959 \cs_new_protected:cpn { \c__keys_props_root_tl .value_forbidden:n } #1
10960   { \__keys_value_requirement:nn { forbidden } {#1} }
10961 \cs_new_protected:cpn { \c__keys_props_root_tl .value_required:n } #1
10962   { \__keys_value_requirement:nn { required } {#1} }
```

(End definition for `.value_forbidden:n` and `.value_required:n`. These functions are documented on page 175.)

19.6 Setting keys

`\keys_set:nn` A simple wrapper again.

```
\keys_set:nV
\keys_set:nv
\keys_set:no
\__keys_set:nnn
\__keys_set:onn
10963 \cs_new_protected:Npn \keys_set:nn
10964   { \__keys_set:onn { \l__keys_module_tl } }
10965 \cs_new_protected:Npn \__keys_set:nnn #1#2#3
10966   {
10967     \tl_set:Nx \l__keys_module_tl { \__keys_remove_spaces:n {#2} }
10968     \keyval_parse:NNn \__keys_set:n \__keys_set:nn {#3}
10969     \tl_set:Nn \l__keys_module_tl {#1}
10970   }
10971 \cs_generate_variant:Nn \keys_set:nn { nV , nv , no }
10972 \cs_generate_variant:Nn \__keys_set:nnn { o }
```

(End definition for `\keys_set:nn` and `__keys_set:nnn`. This function is documented on page 178.)

`\keys_set_known:nnN` Setting known keys simply means setting the appropriate flag, then running the standard code. To allow for nested setting, any existing value of `\l__keys_unused_clist` is saved on the stack and reset afterwards. Note that for speed/simplicity reasons we use a `tl` operation to set the `clist` here!

```
\keys_set_known:nVN
\keys_set_known:nvN
\keys_set_known:noN
\__keys_set_known:nnnN
\__keys_set_known:onnN
10973 \cs_new_protected:Npn \keys_set_known:nnN
10974   { \__keys_set_known:onnN \l__keys_unused_clist }
10975 \cs_generate_variant:Nn \keys_set_known:nnN { nV , nv , no }
10976 \cs_new_protected:Npn \__keys_set_known:nnnN #1#2#3#4
10977   {
10978     \clist_clear:N \l__keys_unused_clist
10979     \keys_set_known:nn {#2} {#3}
10980     \tl_set:Nx #4 { \exp_not:o { \l__keys_unused_clist } }
10981     \tl_set:Nn \l__keys_unused_clist {#1}
10982   }
10983 \cs_generate_variant:Nn \__keys_set_known:nnnN { o }
10984 \cs_new_protected:Npn \keys_set_known:nn #1#2
10985   {
10986     \bool_if:NTF \l__keys_only_known_bool
10987       { \keys_set:nn }
10988       { \__keys_set_known:nn }
10989     {#1} {#2}
10990   }
10991 \cs_generate_variant:Nn \keys_set_known:nn { nV , nv , no }
10992 \cs_new_protected:Npn \__keys_set_known:nn #1#2
10993   {
10994     \bool_set_true:N \l__keys_only_known_bool
10995     \keys_set:nn {#1} {#2}
```

```

10996     \bool_set_false:N \l__keys_only_known_bool
10997 }

```

(End definition for \keys_set_known:nnN and others. These functions are documented on page 179.)

```

\keys_set_filter:nnnN The idea of setting keys in a selective manner again uses flags wrapped around the basic
\keys_set_filter:nnVN code. The comments on \keys_set_known:nnN also apply here. We have a bit more
\keys_set_filter:nnvN shuffling to do to keep everything nestable.
\keys_set_filter:nnoN
__keys_set_filter:nnnnN
__keys_set_filter:onnnN
\keys_set_filter:nnn 10998 \cs_new_protected:Npn \keys_set_filter:nnnN
\keys_set_filter:nnV 10999 { \__keys_set_filter:onnnN \l__keys_unused_clist }
\keys_set_filter:nnv 11000 \cs_generate_variant:Nn \keys_set_filter:nnnN { nnV , nnv , nno }
\keys_set_filter:nno 11001 \cs_new_protected:Npn \__keys_set_filter:nnnnN #1#2#3#4#5
__keys_set_filter:nnn 11002 {
\keys_set_filter:nnV 11003 \clist_clear:N \l__keys_unused_clist
\keys_set_filter:nnv 11004 \keys_set_filter:nnn {#2} {#3} {#4}
\keys_set_filter:nno 11005 \tl_set:Nx #5 { \exp_not:o { \l__keys_unused_clist } }
__keys_set_filter:nnn 11006 \tl_set:Nn \l__keys_unused_clist {#1}
\keys_set_groups:nnn 11007 }
\keys_set_groups:nnV 11008 \cs_generate_variant:Nn \__keys_set_filter:nnnnN { o }
\keys_set_groups:nnv 11009 \cs_new_protected:Npn \keys_set_filter:nnn #1#2#3
\keys_set_groups:nno 11010 {
__keys_set_groups:nnn 11011 \bool_if:NTF \l__keys_filtered_bool
__keys_set_selective:nnn 11012 { \__keys_set_selective:nnn }
__keys_set_selective:nnnn 11013 { \__keys_set_filter:nnn }
__keys_set_selective:onnn 11014 {#1} {#2} {#3}
__keys_set_selective:nn 11015 }
11016 \cs_generate_variant:Nn \keys_set_filter:nnn { nnV , nnv , nno }
11017 \cs_new_protected:Npn \__keys_set_filter:nnn #1#2#3
11018 {
11019 \bool_set_true:N \l__keys_filtered_bool
11020 \__keys_set_selective:nnn {#1} {#2} {#3}
11021 \bool_set_false:N \l__keys_filtered_bool
11022 }
11023 \cs_new_protected:Npn \keys_set_groups:nnn #1#2#3
11024 {
11025 \bool_if:NTF \l__keys_filtered_bool
11026 { \__keys_set_groups:nnn }
11027 { \__keys_set_selective:nnn }
11028 {#1} {#2} {#3}
11029 }
11030 \cs_generate_variant:Nn \keys_set_groups:nnn { nnV , nnv , nno }
11031 \cs_new_protected:Npn \__keys_set_groups:nnn #1#2#3
11032 {
11033 \bool_set_false:N \l__keys_filtered_bool
11034 \__keys_set_selective:nnn {#1} {#2} {#3}
11035 \bool_set_true:N \l__keys_filtered_bool
11036 }
11037 \cs_new_protected:Npn \__keys_set_selective:nnn
11038 { \__keys_set_selective:onnn \l__keys_selective_seq }
11039 \cs_new_protected:Npn \__keys_set_selective:nnnn #1#2#3#4
11040 {
11041 \seq_set_from_clist:Nn \l__keys_selective_seq {#3}
11042 \bool_if:NTF \l__keys_selective_bool
11043 { \keys_set:nn }

```

```

11044     { \_keys_set_selective:nn }
11045     {#2} {#4}
11046     \tl_set:Nn \l__keys_selective_seq {#1}
11047   }
11048 \cs_generate_variant:Nn \_keys_set_selective:nnnn { o }
11049 \cs_new_protected:Npn \_keys_set_selective:nn #1#2
11050 {
11051   \bool_set_true:N \l__keys_selective_bool
11052   \keys_set:nn {#1} {#2}
11053   \bool_set_false:N \l__keys_selective_bool
11054 }

```

(End definition for \keys_set_filter:nnnN and others. These functions are documented on page 180.)

```

\_keys_set:n      A shared system once again. First, set the current path and add a default if needed.
\_keys_set:nn     There are then checks to see if the a value is required or forbidden. If everything passes,
\_keys_set_aux:nnn move on to execute the code.
\_keys_set_aux:onn
\_keys_find_key_module:w
  \_keys_set_aux:
\_keys_set_selective:
11055 \cs_new_protected:Npn \_keys_set:n #1
11056 {
11057   \bool_set_true:N \l__keys_no_value_bool
11058   \_keys_set_aux:onn \l__keys_module_tl {#1} { }
11059 }
11060 \cs_new_protected:Npn \_keys_set:nn #1#2
11061 {
11062   \bool_set_false:N \l__keys_no_value_bool
11063   \_keys_set_aux:onn \l__keys_module_tl {#1} {#2}
11064 }

```

The key path here can be fully defined, after which there is a search for the key and module names: the user may have passed them with part of what is actually the module (for our purposes) in the key name. As that happens on a per-key basis, we use the stack approach to restore the module name without a group.

```

11065 \cs_new_protected:Npn \_keys_set_aux:nnn #1#2#3
11066 {
11067   \tl_set:Nx \l_keys_path_tl
11068   {
11069     \tl_if_blank:nF {#1}
11070     { #1 / }
11071     \_keys_remove_spaces:n {#2}
11072   }
11073   \tl_clear:N \l__keys_module_tl
11074   \exp_after:wN \_keys_find_key_module:w \l_keys_path_tl / \q_stop
11075   \_keys_value_or_default:n {#3}
11076   \bool_if:NTF \l__keys_selective_bool
11077   { \_keys_set_selective: }
11078   { \_keys_execute: }
11079   \tl_set:Nn \l__keys_module_tl {#1}
11080 }
11081 \cs_generate_variant:Nn \_keys_set_aux:nnn { o }
11082 \cs_new_protected:Npn \_keys_find_key_module:w #1 / #2 \q_stop
11083 {
11084   \tl_if_blank:nTF {#2}
11085   { \tl_set:Nn \l_keys_key_tl {#1} }
11086   {

```

```

11087         \tl_put_right:Nx \l__keys_module_tl
11088         {
11089             \tl_if_empty:NF \l__keys_module_tl { / }
11090             #1
11091         }
11092         \__keys_find_key_module:w #2 \q_stop
11093     }
11094 }

```

If selective setting is active, there are a number of possible sub-cases to consider. The key name may not be known at all or if it is, it may not have any groups assigned. There is then the question of whether the selection is opt-in or opt-out.

```

11095 \cs_new_protected:Npn \__keys_set_selective:
11096 {
11097     \cs_if_exist:cTF { \c__keys_groups_root_tl \l_keys_path_tl }
11098     {
11099         \clist_set_eq:Nc \l__keys_groups_clist
11100         { \c__keys_groups_root_tl \l_keys_path_tl }
11101         \__keys_check_groups:
11102     }
11103     {
11104         \bool_if:NTF \l__keys_filtered_bool
11105         { \__keys_execute: }
11106         { \__keys_store_unused: }
11107     }
11108 }

```

In the case where selective setting requires a comparison of the list of groups which apply to a key with the list of those which have been set active. That requires two mappings, and again a different outcome depending on whether opt-in or opt-out is set.

```

11109 \cs_new_protected:Npn \__keys_check_groups:
11110 {
11111     \bool_set_false:N \l__keys_tmp_bool
11112     \seq_map_inline:Nn \l__keys_selective_seq
11113     {
11114         \clist_map_inline:Nn \l__keys_groups_clist
11115         {
11116             \str_if_eq:nnT {##1} {####1}
11117             {
11118                 \bool_set_true:N \l__keys_tmp_bool
11119                 \clist_map_break:n { \seq_map_break: }
11120             }
11121         }
11122     }
11123     \bool_if:NTF \l__keys_tmp_bool
11124     {
11125         \bool_if:NTF \l__keys_filtered_bool
11126         { \__keys_store_unused: }
11127         { \__keys_execute: }
11128     }
11129     {
11130         \bool_if:NTF \l__keys_filtered_bool
11131         { \__keys_execute: }
11132         { \__keys_store_unused: }
11133     }

```

```
11134 }
```

(End definition for `_keys_set:n` and others.)

`_keys_value_or_default:n` If a value is given, return it as #1, otherwise send a default if available.

```
11135 \cs_new_protected:Npn \_keys_value_or_default:n #1
11136 {
11137   \bool_if:NTF \l_keys_no_value_bool
11138   {
11139     \cs_if_exist:cTF { \c__keys_default_root_tl \l_keys_path_tl }
11140     {
11141       \tl_set_eq:Nc
11142         \l_keys_value_tl
11143         { \c__keys_default_root_tl \l_keys_path_tl }
11144     }
11145     { \tl_clear:N \l_keys_value_tl }
11146   }
11147   { \tl_set:Nn \l_keys_value_tl {#1} }
11148 }
```

(End definition for `_keys_value_or_default:n`.)

`_keys_execute:` Actually executing a key is done in two parts. First, look for the key itself, then look
`_keys_execute_unknown:` for the **unknown** key with the same path. If both of these fail, complain. What exactly
`_keys_execute:nn` happens if a key is unknown depends on whether unknown keys are being skipped or if
`_keys_store_unused:` an error should be raised.

```
11149 \cs_new_protected:Npn \_keys_execute:
11150 {
11151   \cs_if_exist:cTF { \c__keys_code_root_tl \l_keys_path_tl }
11152   {
11153     \cs_if_exist_use:c { \c__keys_validate_root_tl \l_keys_path_tl }
11154     \cs:w \c__keys_code_root_tl \l_keys_path_tl \exp_after:wN \cs_end:
11155     \exp_after:wN { \l_keys_value_tl }
11156   }
11157   { \_keys_execute_unknown: }
11158 }
11159 \cs_new_protected:Npn \_keys_execute_unknown:
11160 {
11161   \bool_if:NTF \l_keys_only_known_bool
11162   { \_keys_store_unused: }
11163   {
11164     \cs_if_exist:cTF
11165     { \c__keys_inherit_root_tl \_keys_parent:o \l_keys_path_tl }
11166     {
11167       \clist_map_inline:cn
11168       { \c__keys_inherit_root_tl \_keys_parent:o \l_keys_path_tl }
11169       {
11170         \cs_if_exist:cT
11171         { \c__keys_code_root_tl ##1 / \l_keys_key_tl }
11172         {
11173           \cs:w \c__keys_code_root_tl ##1 / \l_keys_key_tl
11174           \exp_after:wN \cs_end: \exp_after:wN
11175           { \l_keys_value_tl }
11176         }
11177       }
11178     }
11179   }
11180 }
```

```

11177         }
11178     }
11179 }
11180 {
11181     \cs_if_exist:cTF { \c__keys_code_root_tl \l__keys_module_tl / unknown }
11182     {
11183         \cs:w \c__keys_code_root_tl \l__keys_module_tl / unknown
11184         \exp_after:wN \cs_end: \exp_after:wN { \l_keys_value_tl }
11185     }
11186     {
11187         \__msg_kernel_error:nxx { kernel } { key-unknown }
11188         { \l_keys_path_tl } { \l__keys_module_tl }
11189     }
11190 }
11191 }
11192 }
11193 \cs_new:Npn \__keys_execute:nn #1#2
11194 {
11195     \cs_if_exist:cTF { \c__keys_code_root_tl #1 }
11196     {
11197         \cs:w \c__keys_code_root_tl #1 \exp_after:wN \cs_end:
11198         \exp_after:wN { \l_keys_value_tl }
11199     }
11200     {#2}
11201 }
11202 \cs_new_protected:Npn \__keys_store_unused:
11203 {
11204     \clist_put_right:Nx \l__keys_unused_clist
11205     {
11206         \exp_not:o \l_keys_key_tl
11207         \bool_if:NF \l__keys_no_value_bool
11208         { = { \exp_not:o \l_keys_value_tl } }
11209     }
11210 }

```

(End definition for __keys_execute: and others.)

__keys_choice_find:n Executing a choice has two parts. First, try the choice given, then if that fails call the
 __keys_multichoice_find:n unknown key. That always exists, as it is created when a choice is first made. So there
 is no need for any escape code. For multiple choices, the same code ends up used in a
 mapping.

```

11211 \cs_new:Npn \__keys_choice_find:n #1
11212 {
11213     \__keys_execute:nn { \l_keys_path_tl / \__keys_remove_spaces:n {#1} }
11214     { \__keys_execute:nn { \l_keys_path_tl / unknown } { } }
11215 }
11216 \cs_new:Npn \__keys_multichoice_find:n #1
11217 { \clist_map_function:nN {#1} \__keys_choice_find:n }

```

(End definition for __keys_choice_find:n and __keys_multichoice_find:n.)

19.7 Utilities

__keys_parent:n Used to strip off the ending part of the key path after the last /.
 __keys_parent:o
 __keys_parent:w


```

11218 \cs_new:Npn \__keys_parent:n #1
11219 { \__keys_parent:w #1 / / \q_stop { } }
11220 \cs_generate_variant:Nn \__keys_parent:n { o }
11221 \cs_new:Npn \__keys_parent:w #1 / #2 / #3 \q_stop #4
11222 {
11223   \tl_if_blank:nTF {#2}
11224   { \use_none:n #4 }
11225   {
11226     \__keys_parent:w #2 / #3 \q_stop { #4 / #1 }
11227   }
11228 }

```

(End definition for __keys_parent:n and __keys_parent:w.)

__keys_remove_spaces:n Used in a few places so worth handling as a dedicated function.

```

11229 \cs_new:Npn \__keys_remove_spaces:n #1
11230 { \tl_trim_spaces:o { \tl_to_str:n {#1} } }

```

(End definition for __keys_remove_spaces:n.)

\keys_if_exist:p:nn A utility for others to see if a key exists.

```

\keys_if_exist:nnTF
11231 \prg_new_conditional:Npnn \keys_if_exist:nn #1#2 { p , T , F , TF }
11232 {
11233   \cs_if_exist:cTF
11234   { \c__keys_code_root_tl \__keys_remove_spaces:n { #1 / #2 } }
11235   { \prg_return_true: }
11236   { \prg_return_false: }
11237 }

```

(End definition for \keys_if_exist:nnTF. This function is documented on page 180.)

\keys_if_choice_exist:p:nnn Just an alternative view on \keys_if_exist:nnTF.

```

\keys_if_choice_exist:nnnTF
11238 \prg_new_conditional:Npnn \keys_if_choice_exist:nnn #1#2#3
11239 { p , T , F , TF }
11240 {
11241   \cs_if_exist:cTF
11242   { \c__keys_code_root_tl \__keys_remove_spaces:n { #1 / #2 / #3 } }
11243   { \prg_return_true: }
11244   { \prg_return_false: }
11245 }

```

(End definition for \keys_if_choice_exist:nnnTF. This function is documented on page 180.)

\keys_show:nn To show a key, show its code using a message.

```

\keys_log:nn
\__keys_show:Nnn
11246 \cs_new_protected:Npn \keys_show:nn
11247 { \__keys_show:Nnn \msg_show:nnxxxx }
11248 \cs_new_protected:Npn \keys_log:nn
11249 { \__keys_show:Nnn \msg_log:nnxxxx }
11250 \cs_new_protected:Npn \__keys_show:Nnn #1#2#3
11251 {
11252   #1 { LaTeX / kernel } { show-key }
11253   { \__keys_remove_spaces:n { #2 / #3 } }
11254   {
11255     \keys_if_exist:nnT {#2} {#3}
11256     {

```

```

11257         \exp_args:Nnf \msg_show_item_unbraced:nn { code }
11258         {
11259             \exp_args:Nc \token_get_replacement_spec:N
11260             { \c__keys_code_root_tl \__keys_remove_spaces:n { #2 / #3 } }
11261         }
11262     }
11263 }
11264 { } { }
11265 }

```

(End definition for `\keys_show:nn`, `\keys_log:nn`, and `__keys_show:Nnn`. These functions are documented on page 180.)

19.8 Messages

For when there is a need to complain.

```

11266 \__msg_kernel_new:nnnn { kernel } { boolean-values-only }
11267 { Key~'#1'~accepts~boolean~values~only. }
11268 { The~key~'#1'~only~accepts~the~values~'true'~and~'false'. }
11269 \__msg_kernel_new:nnnn { kernel } { key-choice-unknown }
11270 { Key~'#1'~accepts~only~a~fixed~set~of~choices. }
11271 {
11272     The~key~'#1'~only~accepts~predefined~values,~
11273     and~'#2'~is~not~one~of~these.
11274 }
11275 \__msg_kernel_new:nnnn { kernel } { key-no-property }
11276 { No~property~given~in~definition~of~key~'#1'. }
11277 {
11278     \c__msg_coding_error_text_tl
11279     Inside~\keys_define:nn  each~key~name~
11280     needs~a~property:  \ \ \
11281     \iow_indent:n { #1 .<property> } \ \ \
11282     LaTeX~did~not~find~a~'.'~to~indicate~the~start~of~a~property.
11283 }
11284 \__msg_kernel_new:nnnn { kernel } { key-unknown }
11285 { The~key~'#1'~is~unknown~and~is~being~ignored. }
11286 {
11287     The~module~'#2'~does~not~have~a~key~called~'#1'.\ \
11288     Check~that~you~have~spelled~the~key~name~correctly.
11289 }
11290 \__msg_kernel_new:nnnn { kernel } { nested-choice-key }
11291 { Attempt~to~define~'#1'~as~a~nested~choice~key. }
11292 {
11293     The~key~'#1'~cannot~be~defined~as~a~choice~as~the~parent~key~'#2'~is~
11294     itself~a~choice.
11295 }
11296 \__msg_kernel_new:nnnn { kernel } { property-boolean-values-only }
11297 { The~property~'#1'~accepts~boolean~values~only. }
11298 {
11299     \c__msg_coding_error_text_tl
11300     The~property~'#1'~only~accepts~the~values~'true'~and~'false'.
11301 }
11302 \__msg_kernel_new:nnnn { kernel } { property-requires-value }
11303 { The~property~'#1'~requires~a~value. }

```

```

11304 {
11305   \c__msg_coding_error_text_tl
11306   LaTeX~was~asked~to~set~property~'#1'~for~key~'#2'.\\
11307   No~value~was~given~for~the~property,~and~one~is~required.
11308 }
11309 \__msg_kernel_new:nnnn { kernel } { property-unknown }
11310 { The~key~property~'#1'~is~unknown. }
11311 {
11312   \c__msg_coding_error_text_tl
11313   LaTeX~has~been~asked~to~set~the~property~'#1'~for~key~'#2':~
11314   this~property~is~not~defined.
11315 }
11316 \__msg_kernel_new:nnnn { kernel } { value-forbidden }
11317 { The~key~'#1'~does~not~take~a~value. }
11318 {
11319   The~key~'#1'~should~be~given~without~a~value.\\
11320   The~value~'#2'~was~present:~the~key~will~be~ignored.
11321 }
11322 \__msg_kernel_new:nnnn { kernel } { value-required }
11323 { The~key~'#1'~requires~a~value. }
11324 {
11325   The~key~'#1'~must~have~a~value.\\
11326   No~value~was~present:~the~key~will~be~ignored.
11327 }
11328 \__msg_kernel_new:nnn { kernel } { show-key }
11329 {
11330   The~key~#1~
11331   \tl_if_empty:nTF {#2}
11332     { is~undefined. }
11333     { has~the~properties: #2 . }
11334 }
11335 </initex | package>

```

20 l3fp implementation

Nothing to see here: everything is in the subfiles!

21 l3fp-aux implementation

```

11336 <(*initex | package>
11337 <@@=fp>

```

21.1 Internal representation

Internally, a floating point number $\langle X \rangle$ is a token list containing

$$\backslash s_fp \backslash _fp_chk:w \langle case \rangle \langle sign \rangle \langle body \rangle ;$$

Let us explain each piece separately.

Internal floating point numbers are used in expressions, and in this context are subject to **f**-expansion. They must leave a recognizable mark after **f**-expansion, to prevent

Table 1: Internal representation of floating point numbers.

Representation	Meaning
0 0 \s_fp_... ;	Positive zero.
0 2 \s_fp_... ;	Negative zero.
1 0 {<exponent>} {<X ₁ >} {<X ₂ >} {<X ₃ >} {<X ₄ >} ;	Positive floating point.
1 2 {<exponent>} {<X ₁ >} {<X ₂ >} {<X ₃ >} {<X ₄ >} ;	Negative floating point.
2 0 \s_fp_... ;	Positive infinity.
2 2 \s_fp_... ;	Negative infinity.
3 1 \s_fp_... ;	Quiet nan.
3 1 \s_fp_... ;	Signalling nan.

the floating point number from being re-parsed. Thus, \s_fp is simply another name for \relax.

When used directly without an accessor function, floating points should produce an error: this is the role of _fp_chk:w. We could make floating point variables be protected to prevent them from expanding under x-expansion, but it seems more convenient to treat them as a subcase of token list variables.

The (decimal part of the) IEEE-754-2008 standard requires the format to be able to represent special floating point numbers besides the usual positive and negative cases. We distinguish the various possibilities by their <case>, which is a single digit:

- 0 zeros: +0 and -0,
- 1 “normal” numbers (positive and negative),
- 2 infinities: +inf and -inf,
- 3 quiet and signalling nan.

The <sign> is 0 (positive) or 2 (negative), except in the case of nan, which have <sign> = 1. This ensures that changing the <sign> digit to 2 - <sign> is exactly equivalent to changing the sign of the number.

Special floating point numbers have the form

\s_fp _fp_chk:w <case> <sign> \s_fp_... ;

where \s_fp_... is a scan mark carrying information about how the number was formed (useful for debugging).

Normal floating point numbers (<case> = 1) have the form

\s_fp _fp_chk:w 1 <sign> {<exponent>} {<X₁>} {<X₂>} {<X₃>} {<X₄>} ;

Here, the <exponent> is an integer, between -10000 and 10000. The body consists in four blocks of exactly 4 digits, 0000 ≤ <X_i> ≤ 9999, and the floating point is

$$(-1)^{\langle sign \rangle / 2} \langle X_1 \rangle \langle X_2 \rangle \langle X_3 \rangle \langle X_4 \rangle \cdot 10^{\langle exponent \rangle - 16}$$

where we have concatenated the 16 digits. Currently, floating point numbers are normalized such that the <exponent> is minimal, in other words, 1000 ≤ <X₁> ≤ 9999.

Calculations are done in base 10000, *i.e.* one myriad.

21.2 Using arguments and semicolons

<code>__fp_use_none_stop_f:n</code>	<p>This function removes an argument (typically a digit) and replaces it by <code>\exp_stop_f:</code>, a marker which stops f-type expansion.</p> <pre>11338 \cs_new:Npn __fp_use_none_stop_f:n #1 { \exp_stop_f: }</pre> <p>(End definition for <code>__fp_use_none_stop_f:n</code>.)</p>
<code>__fp_use_s:n</code> <code>__fp_use_s:nn</code>	<p>Those functions place a semicolon after one or two arguments (typically digits).</p> <pre>11339 \cs_new:Npn __fp_use_s:n #1 { #1; } 11340 \cs_new:Npn __fp_use_s:nn #1#2 { #1#2; }</pre> <p>(End definition for <code>__fp_use_s:n</code> and <code>__fp_use_s:nn</code>.)</p>
<code>__fp_use_none_until_s:w</code> <code>__fp_use_i_until_s:nw</code> <code>__fp_use_ii_until_s:nnw</code>	<p>Those functions select specific arguments among a set of arguments delimited by a semicolon.</p> <pre>11341 \cs_new:Npn __fp_use_none_until_s:w #1; { } 11342 \cs_new:Npn __fp_use_i_until_s:nw #1#2; {#1} 11343 \cs_new:Npn __fp_use_ii_until_s:nnw #1#2#3; {#2}</pre> <p>(End definition for <code>__fp_use_none_until_s:w</code>, <code>__fp_use_i_until_s:nw</code>, and <code>__fp_use_ii_until_s:nnw</code>.)</p>
<code>__fp_reverse_args:Nww</code>	<p>Many internal functions take arguments delimited by semicolons, and it is occasionally useful to swap two such arguments.</p> <pre>11344 \cs_new:Npn __fp_reverse_args:Nww #1 #2; #3; { #1 #3; #2; }</pre> <p>(End definition for <code>__fp_reverse_args:Nww</code>.)</p>
<code>__fp_rrot:www</code>	<p>Rotate three arguments delimited by semicolons. This is the inverse (or the square) of the Forth primitive ROT, hence the name.</p> <pre>11345 \cs_new:Npn __fp_rrot:www #1; #2; #3; { #2; #3; #1; }</pre> <p>(End definition for <code>__fp_rrot:www</code>.)</p>
<code>__fp_use_i:ww</code> <code>__fp_use_i:www</code>	<p>Many internal functions take arguments delimited by semicolons, and it is occasionally useful to remove one or two such arguments.</p> <pre>11346 \cs_new:Npn __fp_use_i:ww #1; #2; { #1; } 11347 \cs_new:Npn __fp_use_i:www #1; #2; #3; { #1; }</pre> <p>(End definition for <code>__fp_use_i:ww</code> and <code>__fp_use_i:www</code>.)</p>

21.3 Constants, and structure of floating points

<code>\s__fp</code> <code>__fp_chk:w</code>	<p>Floating points numbers all start with <code>\s__fp __fp_chk:w</code>, where <code>\s__fp</code> is equal to the TeX primitive <code>\relax</code>, and <code>__fp_chk:w</code> is protected. The rest of the floating point number is made of characters (or <code>\relax</code>). This ensures that nothing expands under f-expansion, nor under x-expansion. However, when typeset, <code>\s__fp</code> does nothing, and <code>__fp_chk:w</code> is expanded. We define <code>__fp_chk:w</code> to produce an error.</p> <pre>11348 __scan_new:N \s__fp 11349 \cs_new_protected:Npn __fp_chk:w #1 ; 11350 { 11351 __msg_kernel_error:nnx { kernel } { misused-fp } 11352 { \fp_to_tl:n { \s__fp __fp_chk:w #1 ; } } 11353 }</pre>
---	--

(End definition for `\s__fp` and `__fp_chk:w`.)

`\s__fp_mark` Aliases of `\tex_relax:D`, used to terminate expressions.

```
\s__fp_stop 11354 \__scan_new:N \s__fp_mark
            11355 \__scan_new:N \s__fp_stop
```

(End definition for `\s__fp_mark` and `\s__fp_stop`.)

`\s__fp_invalid` A couple of scan marks used to indicate where special floating point numbers come from.

```
\s__fp_underflow 11356 \__scan_new:N \s__fp_invalid
\s__fp_overflow 11357 \__scan_new:N \s__fp_underflow
\s__fp_division 11358 \__scan_new:N \s__fp_overflow
\s__fp_exact 11359 \__scan_new:N \s__fp_division
            11360 \__scan_new:N \s__fp_exact
```

(End definition for `\s__fp_invalid` and others.)

`\c_zero_fp` The special floating points. We define the floating points here as “exact”.

```
\c_minus_zero_fp 11361 \tl_const:Nn \c_zero_fp { \s__fp \__fp_chk:w 0 0 \s__fp_exact ; }
\c_inf_fp 11362 \tl_const:Nn \c_minus_zero_fp { \s__fp \__fp_chk:w 0 2 \s__fp_exact ; }
\c_minus_inf_fp 11363 \tl_const:Nn \c_inf_fp { \s__fp \__fp_chk:w 2 0 \s__fp_exact ; }
\c_nan_fp 11364 \tl_const:Nn \c_minus_inf_fp { \s__fp \__fp_chk:w 2 2 \s__fp_exact ; }
            11365 \tl_const:Nn \c_nan_fp { \s__fp \__fp_chk:w 3 1 \s__fp_exact ; }
```

(End definition for `\c_zero_fp` and others. These variables are documented on page 189.)

`\c__fp_prec_int` The number of digits of floating points.

```
\c__fp_half_prec_int 11366 \int_const:Nn \c__fp_prec_int { 16 }
\c__fp_block_int 11367 \int_const:Nn \c__fp_half_prec_int { 8 }
            11368 \int_const:Nn \c__fp_block_int { 4 }
```

(End definition for `\c__fp_prec_int`, `\c__fp_half_prec_int`, and `\c__fp_block_int`.)

`\c__fp_myriad_int` Blocks have 4 digits so this integer is useful.

```
11369 \int_const:Nn \c__fp_myriad_int { 10000 }
```

(End definition for `\c__fp_myriad_int`.)

`\c__fp_minus_min_exponent_int` Normal floating point numbers have an exponent between `– minus_min_exponent` and `max_exponent` inclusive. Larger numbers are rounded to $\pm\infty$. Smaller numbers are rounded to ± 0 . It would be more natural to define a `min_exponent` with the opposite sign but that would waste one TeX count.

```
11370 \int_const:Nn \c__fp_minus_min_exponent_int { 10000 }
11371 \int_const:Nn \c__fp_max_exponent_int { 10000 }
```

(End definition for `\c__fp_minus_min_exponent_int` and `\c__fp_max_exponent_int`.)

`\c__fp_max_exp_exponent_int` If a number’s exponent is larger than that, its exponential overflows/underflows.

```
11372 \int_const:Nn \c__fp_max_exp_exponent_int { 5 }
```

(End definition for `\c__fp_max_exp_exponent_int`.)

`\c__fp_overflowing_fp` A floating point number that is bigger than all normal floating point numbers. This replaces infinities when converting to formats that do not support infinities.

```

11373 \tl_const:Nx \c__fp_overflowing_fp
11374 {
11375   \s__fp \__fp_chk:w 1 0
11376   { \int_eval:n { \c__fp_max_exponent_int + 1 } }
11377   {1000} {0000} {0000} {0000} ;
11378 }

```

(End definition for `\c__fp_overflowing_fp`.)

`__fp_zero_fp:N` In case of overflow or underflow, we have to output a zero or infinity with a given sign.

```

\__fp_inf_fp:N
11379 \cs_new:Npn \__fp_zero_fp:N #1
11380 { \s__fp \__fp_chk:w 0 #1 \s__fp_underflow ; }
11381 \cs_new:Npn \__fp_inf_fp:N #1
11382 { \s__fp \__fp_chk:w 2 #1 \s__fp_overflow ; }

```

(End definition for `__fp_zero_fp:N` and `__fp_inf_fp:N`.)

`__fp_exponent:w` For normal numbers, the function expands to the exponent, otherwise to 0. This is used in l3str-format.

```

11383 \cs_new:Npn \__fp_exponent:w \s__fp \__fp_chk:w #1
11384 {
11385   \if_meaning:w 1 #1
11386     \exp_after:wN \__fp_use_ii_until_s:nnw
11387   \else:
11388     \exp_after:wN \__fp_use_i_until_s:nw
11389     \exp_after:wN 0
11390   \fi:
11391 }

```

(End definition for `__fp_exponent:w`.)

`__fp_neg_sign:N` When appearing in an integer expression or after `__int_value:w`, this expands to the sign opposite to #1, namely 0 (positive) is turned to 2 (negative), 1 (nan) to 1, and 2 to 0.

```

11392 \cs_new:Npn \__fp_neg_sign:N #1
11393 { \__int_eval:w 2 - #1 \__int_eval_end: }

```

(End definition for `__fp_neg_sign:N`.)

21.4 Overflow, underflow, and exact zero

`__fp_sanitize:Nw` `__fp_sanitize:wN` `__fp_sanitize_zero:w` Expects the sign and the exponent in some order, then the significand (which we don't touch). Outputs the corresponding floating point number, possibly underflowed to ± 0 or overflowed to $\pm\infty$. The functions `__fp_underflow:w` and `__fp_overflow:w` are defined in l3fp-traps.

```

11394 \cs_new:Npn \__fp_sanitize:Nw #1 #2;
11395 {
11396   \if_case:w
11397     \if_int_compare:w #2 > \c__fp_max_exponent_int 1 ~ \else:
11398     \if_int_compare:w #2 < - \c__fp_minus_min_exponent_int 2 ~ \else:
11399     \if_meaning:w 1 #1 3 ~ \fi: \fi: \fi: 0 ~
11400   \or: \exp_after:wN \__fp_overflow:w

```

```

11401 \or: \exp_after:wN \__fp_underflow:w
11402 \or: \exp_after:wN \__fp_sanitize_zero:w
11403 \fi:
11404 \s__fp \__fp_chk:w 1 #1 {#2}
11405 }
11406 \cs_new:Npn \__fp_sanitize:wN #1; #2 { \__fp_sanitize:Nw #2 #1; }
11407 \cs_new:Npn \__fp_sanitize_zero:w \s__fp \__fp_chk:w #1 #2 #3;
11408 { \c_zero_fp }

```

(End definition for `__fp_sanitize:Nw`, `__fp_sanitize:wN`, and `__fp_sanitize_zero:w`.)

21.5 Expanding after a floating point number

```

\__fp_exp_after_o:w
\__fp_exp_after_f:nw

```

```

\__fp_exp_after_o:w <floating point>
\__fp_exp_after_f:nw {<tokens>} <floating point>

```

Places *<tokens>* (empty in the case of `__fp_exp_after_o:w`) between the *<floating point>* and the *<more tokens>*, then hits those tokens with either o-expansion (one `\exp_after:wN`) or f-expansion, and leaves the floating point number unchanged.

We first distinguish normal floating points, which have a significand, from the much simpler special floating points.

```

11409 \cs_new:Npn \__fp_exp_after_o:w \s__fp \__fp_chk:w #1
11410 {
11411   \if_meaning:w 1 #1
11412   \exp_after:wN \__fp_exp_after_normal:nNNw
11413   \else:
11414   \exp_after:wN \__fp_exp_after_special:nNNw
11415   \fi:
11416   { }
11417   #1
11418 }
11419 \cs_new:Npn \__fp_exp_after_f:nw #1 \s__fp \__fp_chk:w #2
11420 {
11421   \if_meaning:w 1 #2
11422   \exp_after:wN \__fp_exp_after_normal:nNNw
11423   \else:
11424   \exp_after:wN \__fp_exp_after_special:nNNw
11425   \fi:
11426   { \exp:w \exp_end_continue_f:w #1 }
11427   #2
11428 }

```

(End definition for `__fp_exp_after_o:w` and `__fp_exp_after_f:nw`.)

```

\__fp_exp_after_special:nNNw

```

```

\__fp_exp_after_special:nNNw {<after>} <case> <sign> <scan mark> ;
Special floating point numbers are easy to jump over since they contain few tokens.

```

```

11429 \cs_new:Npn \__fp_exp_after_special:nNNw #1#2#3#4;
11430 {
11431   \exp_after:wN \s__fp
11432   \exp_after:wN \__fp_chk:w
11433   \exp_after:wN #2
11434   \exp_after:wN #3
11435   \exp_after:wN #4
11436   \exp_after:wN ;

```



```

11437     #1
11438   }

```

(End definition for `_fp_exp_after_special:nNw`.)

`_fp_exp_after_normal:nNw` For normal floating point numbers, life is slightly harder, since we have many tokens to jump over. Here it would be slightly better if the digits were not braced but instead were delimited arguments (for instance delimited by `,`). That may be changed some day.

```

11439 \cs_new:Npn \_fp_exp_after_normal:nNw #1 1 #2 #3 #4#5#6#7;
11440 {
11441   \exp_after:wN \_fp_exp_after_normal:Nwwwww
11442   \exp_after:wN #2
11443   \__int_value:w #3 \exp_after:wN ;
11444   \__int_value:w 1 #4 \exp_after:wN ;
11445   \__int_value:w 1 #5 \exp_after:wN ;
11446   \__int_value:w 1 #6 \exp_after:wN ;
11447   \__int_value:w 1 #7 \exp_after:wN ; #1
11448 }
11449 \cs_new:Npn \_fp_exp_after_normal:Nwwwww
11450   #1 #2; 1 #3 ; 1 #4 ; 1 #5 ; 1 #6 ;
11451   { \s_fp \_fp_chk:w 1 #1 {#2} {#3} {#4} {#5} {#6} ; }

```

(End definition for `_fp_exp_after_normal:nNw`.)

```

\__fp_exp_after_array_f:w
\__fp_exp_after_stop_f:nw
\__fp_exp_after_array_f:w
  <fp1> ;
  ...
  <fpn> ;
  \s_fp_stop
11452 \cs_new:Npn \_fp_exp_after_array_f:w #1
11453 {
11454   \cs:w \_fp_exp_after \_fp_type_from_scan:N #1 _f:nw \cs_end:
11455   { \_fp_exp_after_array_f:w }
11456   #1
11457 }
11458 \cs_new_eq:NN \_fp_exp_after_stop_f:nw \use_none:nn

```

(End definition for `_fp_exp_after_array_f:w` and `_fp_exp_after_stop_f:nw`.)

21.6 Packing digits

When a positive integer `#1` is known to be less than 10^8 , the following trick splits it into two blocks of 4 digits, padding with zeros on the left.

```

\cs_new:Npn \pack:NNNNw #1 #2#3#4#5 #6; { {#2#3#4#5} {#6} }
\exp_after:wN \pack:NNNNw
  \__int_value:w \__int_eval:w 1 0000 0000 + #1 ;

```

The idea is that adding 10^8 to the number ensures that it has exactly 9 digits, and can then easily find which digits correspond to what position in the number. Of course, this can be modified for any number of digits less or equal to 9 (we are limited by $\text{T}_{\text{E}}\text{X}$'s integers). This method is very heavily relied upon in `l3fp-basics`.

More specifically, the auxiliary inserts `+ #1#2#3#4#5 ; {#6}`, which allows us to compute several blocks of 4 digits in a nested manner, performing carries on the fly. Say we want to compute 12345×66778899 . With simplified names, we would do

```

\exp_after:wN \post_processing:w
\__int_value:w \__int_eval:w - 5 0000
\exp_after:wN \pack:NNNNNw
\__int_value:w \__int_eval:w 4 9995 0000
+ 12345 * 6677
\exp_after:wN \pack:NNNNNw
\__int_value:w \__int_eval:w 5 0000 0000
+ 12345 * 8899 ;

```

The `\exp_after:wN` triggers `__int_value:w __int_eval:w`, which starts a first computation, whose initial value is $-5\,0000$ (the “leading shift”). In that computation appears an `\exp_after:wN`, which triggers the nested computation `__int_value:w __int_eval:w` with starting value $4\,9995\,0000$ (the “middle shift”). That, in turn, expands `\exp_after:wN` which triggers the third computation. The third computation’s value is $5\,0000\,0000 + 12345 \times 8899$, which has 9 digits. Adding $5 \cdot 10^8$ to the product allowed us to know how many digits to expect as long as the numbers to multiply are not too big; it also works to some extent with negative results. The `pack` function puts the last 4 of those 9 digits into a brace group, moves the semi-colon delimiter, and inserts a `+`, which combines the carry with the previous computation. The shifts nicely combine into $5\,0000\,0000/10^4 + 4\,9995\,0000 = 5\,0000\,0000$. As long as the operands are in some range, the result of this second computation has 9 digits. The corresponding `pack` function, expanded after the result is computed, braces the last 4 digits, and leaves `+ {5 digits}` for the initial computation. The “leading shift” cancels the combination of the other shifts, and the `\post_processing:w` takes care of packing the last few digits.

Admittedly, this is quite intricate. It is probably the key in making `l3fp` as fast as other pure \TeX floating point units despite its increased precision. In fact, this is used so much that we provide different sets of packing functions and shifts, depending on ranges of input.

```

\__fp_pack:NNNNNw
\c_fp_trailing_shift_int
\c_fp_middle_shift_int
\c_fp_leading_shift_int
11459 \int_const:Nn \c_fp_leading_shift_int { - 5 0000 }
11460 \int_const:Nn \c_fp_middle_shift_int { 5 0000 * 9999 }
11461 \int_const:Nn \c_fp_trailing_shift_int { 5 0000 * 10000 }
11462 \cs_new:Npn \__fp_pack:NNNNNw #1 #2#3#4#5 #6; { + #1#2#3#4#5 ; {#6} }

```

This set of shifts allows for computations involving results in the range $[-4 \cdot 10^8, 5 \cdot 10^8 - 1]$. Shifted values all have exactly 9 digits.

(End definition for `__fp_pack:NNNNNw` and others.)

```

\__fp_pack_big:NNNNNNw
\c_fp_big_trailing_shift_int
\c_fp_big_middle_shift_int
\c_fp_big_leading_shift_int

```

This set of shifts allows for computations involving results in the range $[-5 \cdot 10^8, 6 \cdot 10^8 - 1]$ (actually a bit more). Shifted values all have exactly 10 digits. Note that the upper bound is due to \TeX ’s limit of $2^{31} - 1$ on integers. The shifts are chosen to be roughly the mid-point of 10^9 and 2^{31} , the two bounds on 10-digit integers in \TeX .

```

11463 \int_const:Nn \c_fp_big_leading_shift_int { - 15 2374 }
11464 \int_const:Nn \c_fp_big_middle_shift_int { 15 2374 * 9999 }
11465 \int_const:Nn \c_fp_big_trailing_shift_int { 15 2374 * 10000 }
11466 \cs_new:Npn \__fp_pack_big:NNNNNNw #1#2 #3#4#5#6 #7;
11467 { + #1#2#3#4#5#6 ; {#7} }

```

(End definition for `__fp_pack_big:NNNNNNw` and others.)

```

\__fp_pack_Bigg:NNNNNNw
\__fp_Bigg_trailing_shift_int
\__fp_Bigg_middle_shift_int
\__fp_Bigg_leading_shift_int
11468 \int_const:Nn \__fp_Bigg_leading_shift_int { - 20 0000 }
11469 \int_const:Nn \__fp_Bigg_middle_shift_int { 20 0000 * 9999 }
11470 \int_const:Nn \__fp_Bigg_trailing_shift_int { 20 0000 * 10000 }
11471 \cs_new:Npn \__fp_pack_Bigg:NNNNNNw #1#2 #3#4#5#6 #7;
11472 { + #1#2#3#4#5#6 ; {#7} }

```

This set of shifts allows for computations with results in the range $[-1 \cdot 10^9, 147483647]$; the end-point is $2^{31} - 1 - 2 \cdot 10^9 \simeq 1.47 \cdot 10^8$. Shifted values all have exactly 10 digits.

(End definition for `__fp_pack_Bigg:NNNNNNw` and others.)

```

\__fp_pack_twice_four:wNNNNNNNN
\__fp_pack_twice_four:wNNNNNNNN <tokens> ; <≥ 8 digits>
Grabs two sets of 4 digits and places them before the semi-colon delimiter. Putting
several copies of this function before a semicolon packs more digits since each takes the
digits packed by the others in its first argument.
11473 \cs_new:Npn \__fp_pack_twice_four:wNNNNNNNN #1; #2#3#4#5 #6#7#8#9
11474 { #1 {#2#3#4#5} {#6#7#8#9} ; }

```

(End definition for `__fp_pack_twice_four:wNNNNNNNN`.)

```

\__fp_pack_eight:wNNNNNNNN
\__fp_pack_eight:wNNNNNNNN <tokens> ; <≥ 8 digits>
Grabs one set of 8 digits and places them before the semi-colon delimiter as a single
group. Putting several copies of this function before a semicolon packs more digits since
each takes the digits packed by the others in its first argument.
11475 \cs_new:Npn \__fp_pack_eight:wNNNNNNNN #1; #2#3#4#5 #6#7#8#9
11476 { #1 {#2#3#4#5#6#7#8#9} ; }

```

(End definition for `__fp_pack_eight:wNNNNNNNN`.)

```

\__fp_basics_pack_low:NNNNNw
\__fp_basics_pack_high:NNNNNw
\__fp_basics_pack_high_carry:w
Addition and multiplication of significands are done in two steps: first compute a (more or
less) exact result, then round and pack digits in the final (braced) form. These functions
take care of the packing, with special attention given to the case where rounding has
caused a carry. Since rounding can only shift the final digit by 1, a carry always produces
an exact power of 10. Thus, \__fp_basics_pack_high_carry:w is always followed by
four times {0000}.

```

This is used in `l3fp-basics` and `l3fp-extended`.

```

11477 \cs_new:Npn \__fp_basics_pack_low:NNNNNw #1 #2#3#4#5 #6;
11478 { + #1 - 1 ; {#2#3#4#5} {#6} ; }
11479 \cs_new:Npn \__fp_basics_pack_high:NNNNNw #1 #2#3#4#5 #6;
11480 {
11481   \if_meaning:w 2 #1
11482     \__fp_basics_pack_high_carry:w
11483   \fi:
11484   ; {#2#3#4#5} {#6}
11485 }
11486 \cs_new:Npn \__fp_basics_pack_high_carry:w \fi: ; #1
11487 { \fi: + 1 ; {1000} }

```

(End definition for `__fp_basics_pack_low:NNNNNw`, `__fp_basics_pack_high:NNNNNw`, and `__fp_basics_pack_high_carry:w`.)

`_fp_basics_pack_weird_low:NNNNw`
`_fp_basics_pack_weird_high:NNNNNNNNw`

This is used in l3fp-basics for additions and divisions. Their syntax is confusing, hence the name.

```

11488 \cs_new:Npn \_fp\_basics\_pack\_weird\_low:NNNNw #1 #2#3#4 #5;
11489 {
11490   \if_meaning:w 2 #1
11491     + 1
11492   \fi:
11493   \__int_eval_end:
11494   #2#3#4; {#5} ;
11495 }
11496 \cs_new:Npn \_fp\_basics\_pack\_weird\_high:NNNNNNNNw
11497   1 #1#2#3#4 #5#6#7#8 #9; { ; {#1#2#3#4} {#5#6#7#8} {#9} }

```

(End definition for `_fp_basics_pack_weird_low:NNNNw` and `_fp_basics_pack_weird_high:NNNNNNNNw`.)

21.7 Decimate (dividing by a power of 10)

`_fp_decimate:nNnnnn`

`_fp_decimate:nNnnnn {<shift>} {<f1>}`
`{<X1>} {<X2>} {<X3>} {<X4>}`

Each $\langle X_i \rangle$ consists in 4 digits exactly, and $1000 \leq \langle X_1 \rangle < 9999$. The first argument determines by how much we shift the digits. $\langle f_1 \rangle$ is called as follows:

$\langle f_1 \rangle$ $\langle \text{rounding} \rangle$ $\{ \langle X'_1 \rangle \}$ $\{ \langle X'_2 \rangle \}$ $\langle \text{extra-digits} \rangle$;

where $0 \leq \langle X'_i \rangle < 10^8 - 1$ are 8 digit integers, forming the truncation of our number. In other words,

$$\left(\sum_{i=1}^4 \langle X_i \rangle \cdot 10^{-4i} \cdot 10^{-\langle \text{shift} \rangle} \right) - (\langle X'_1 \rangle \cdot 10^{-8} + \langle X'_2 \rangle \cdot 10^{-16}) = 0. \langle \text{extra-digits} \rangle \cdot 10^{-16} \in [0, 10^{-16}).$$

To round properly later, we need to remember some information about the difference. The $\langle \text{rounding} \rangle$ digit is 0 if and only if the difference is exactly 0, and 5 if and only if the difference is exactly $0.5 \cdot 10^{-16}$. Otherwise, it is the (non-0, non-5) digit closest to 10^{17} times the difference. In particular, if the shift is 17 or more, all the digits are dropped, $\langle \text{rounding} \rangle$ is 1 (not 0), and $\langle X'_1 \rangle$ and $\langle X'_2 \rangle$ are both zero.

If the shift is 1, the $\langle \text{rounding} \rangle$ digit is simply the only digit that was pushed out of the brace groups (this is important for subtraction). It would be more natural for the $\langle \text{rounding} \rangle$ digit to be placed after the $\langle X'_i \rangle$, but the choice we make involves less reshuffling.

Note that this function treats negative $\langle \text{shift} \rangle$ as 0.

```

11498 \cs_new:Npn \_fp\_decimate:nNnnnn #1
11499 {
11500   \cs:w
11501   \_fp\_decimate\_
11502   \if_int_compare:w \__int_eval:w #1 > \c\_fp\_prec\_int
11503     tiny
11504   \else:
11505     \__int_to_roman:w \__int_eval:w #1
11506   \fi:
11507   :Nnnnn
11508 \cs_end:
11509 }

```

Each of the auxiliaries see the function $\langle f_1 \rangle$, followed by 4 blocks of 4 digits.

(End definition for `_fp_decimate:nNnnnn`.)

If the $\langle shift \rangle$ is zero, or too big, life is very easy.

```
\_fp\_decimate_:Nnnnn
\_fp\_decimate\_tiny:Nnnnn
11510 \cs_new:Npn \_fp\_decimate_:Nnnnn #1 #2#3#4#5
11511 { #1 0 {#2#3} {#4#5} ; }
11512 \cs_new:Npn \_fp\_decimate\_tiny:Nnnnn #1 #2#3#4#5
11513 { #1 1 { 0000 0000 } { 0000 0000 } 0 #2#3#4#5 ; }
```

(End definition for `_fp_decimate_:Nnnnn` and `_fp_decimate_tiny:Nnnnn`.)

```
\_fp\_decimate\_auxi:Nnnnn      \_fp\_decimate\_auxi:Nnnnn  $\langle f_1 \rangle$  { $\langle X_1 \rangle$ } { $\langle X_2 \rangle$ } { $\langle X_3 \rangle$ } { $\langle X_4 \rangle$ }
\_fp\_decimate\_auxii:Nnnnn      Shifting happens in two steps: compute the  $\langle rounding \rangle$  digit, and repack digits into
\_fp\_decimate\_auxiii:Nnnnn      two blocks of 8. The sixteen functions are very similar, and defined through \_fp\_
\_fp\_decimate\_auxiv:Nnnnn      tmp:w. The arguments are as follows: #1 indicates which function is being defined; after
\_fp\_decimate\_auxv:Nnnnn      one step of expansion, #2 yields the “extra digits” which are then converted by \_fp\_
\_fp\_decimate\_auxvi:Nnnnn      round\_digit:Nw to the  $\langle rounding \rangle$  digit (note the + separating blocks of digits to
\_fp\_decimate\_auxvii:Nnnnn      avoid overflowing TeX’s integers). This triggers the f-expansion of \_fp\_decimate\_
\_fp\_decimate\_auxviii:Nnnnn     pack:nnnnnnnnnw,9 responsible for building two blocks of 8 digits, and removing the
\_fp\_decimate\_auxix:Nnnnn      rest. For this to work, #3 alternates between braced and unbraced blocks of 4 digits, in
\_fp\_decimate\_auxx:Nnnnn      such a way that the 5 first and 5 next token groups yield the correct blocks of 8 digits.
\_fp\_decimate\_auxxi:Nnnnn
\_fp\_decimate\_auxxii:Nnnnn
\_fp\_decimate\_auxxiii:Nnnnn
\_fp\_decimate\_auxxiv:Nnnnn
\_fp\_decimate\_auxxv:Nnnnn
\_fp\_decimate\_auxxvi:Nnnnn
11514 \cs_new:Npn \_fp\_tmp:w #1 #2 #3
11515 {
11516   \cs_new:cpn { \_fp\_decimate\_ #1 :Nnnnn } ##1 ##2##3##4##5
11517   {
11518     \exp_after:wN ##1
11519     \_int_value:w
11520     \exp_after:wN \_fp\_round\_digit:Nw #2 ;
11521     \_fp\_decimate\_pack:nnnnnnnnnw #3 ;
11522   }
11523 }
11524 \_fp\_tmp:w {i}   {\use\_none:nnn   #50}{ 0{#2}#3{#4}#5           }
11525 \_fp\_tmp:w {ii}  {\use\_none:nn    #5 }{ 00{#2}#3{#4}#5           }
11526 \_fp\_tmp:w {iii} {\use\_none:n     #5 }{ 000{#2}#3{#4}#5         }
11527 \_fp\_tmp:w {iv}  {                #5 }{ {0000}#2{#3}#4 #5       }
11528 \_fp\_tmp:w {v}   {\use\_none:nnn   #4#5 }{ 0{0000}#2{#3}#4 #5     }
11529 \_fp\_tmp:w {vi}  {\use\_none:nn    #4#5 }{ 00{0000}#2{#3}#4 #5     }
11530 \_fp\_tmp:w {vii} {\use\_none:n     #4#5 }{ 000{0000}#2{#3}#4 #5     }
11531 \_fp\_tmp:w {viii}{                #4#5 }{ {0000}0000{#2}#3 #4 #5   }
11532 \_fp\_tmp:w {ix}  {\use\_none:nnn   #3#4+#5}{ 0{0000}0000{#2}#3 #4 #5   }
11533 \_fp\_tmp:w {x}   {\use\_none:nn    #3#4+#5}{ 00{0000}0000{#2}#3 #4 #5   }
11534 \_fp\_tmp:w {xi}  {\use\_none:n     #3#4+#5}{ 000{0000}0000{#2}#3 #4 #5   }
11535 \_fp\_tmp:w {xii} {                #3#4+#5}{ {0000}0000{0000}#2 #3 #4 #5   }
11536 \_fp\_tmp:w {xiii}{\use\_none:nnn#2#3+#4#5}{ 0{0000}0000{0000}#2 #3 #4 #5   }
11537 \_fp\_tmp:w {xiv} {\use\_none:nn    #2#3+#4#5}{ 00{0000}0000{0000}#2 #3 #4 #5   }
11538 \_fp\_tmp:w {xv}  {\use\_none:n     #2#3+#4#5}{ 000{0000}0000{0000}#2 #3 #4 #5   }
11539 \_fp\_tmp:w {xvi} {                #2#3+#4#5}{ {0000}0000{0000}0000 #2 #3 #4 #5 }
```

(End definition for `_fp_decimate_auxi:Nnnnn` and others.)

⁹No, the argument spec is not a mistake: the function calls an auxiliary to do half of the job.

`_fp_decimate_pack:nnnnnnnnnnnw` The computation of the *rounding* digit leaves an unfinished `_int_value:w`, which expands the following functions. This allows us to repack nicely the digits we keep. Those digits come as an alternation of unbraced and braced blocks of 4 digits, such that the first 5 groups of token consist in 4 single digits, and one brace group (in some order), and the next 5 have the same structure. This is followed by some digits and a semicolon.

```

11540 \cs_new:Npn \_fp_decimate_pack:nnnnnnnnnnnw #1#2#3#4#5
11541   { \_fp_decimate_pack:nnnnnnnw { #1#2#3#4#5 } }
11542 \cs_new:Npn \_fp_decimate_pack:nnnnnnnw #1 #2#3#4#5#6
11543   { {#1} {#2#3#4#5#6} }

```

(End definition for `_fp_decimate_pack:nnnnnnnnnnnw`.)

21.8 Functions for use within primitive conditional branches

The functions described in this section are not pretty and can easily be misused. When correctly used, each of them removes one `\fi:` as part of its parameter text, and puts one back as part of its replacement text.

Many computation functions in `l3fp` must perform tests on the type of floating points that they receive. This is often done in an `\if_case:w` statement or another conditional statement, and only a few cases lead to actual computations: most of the special cases are treated using a few standard functions which we define now. A typical use context for those functions would be

```

\if_case:w <integer> \exp_stop_f:
  \@@_case_return_o:Nw <fp var>
\or: \@@_case_use:nw {<some computation>}
\or: \@@_case_return_same_o:w
\or: \@@_case_return:nw {<something>}
\fi:
<junk>
<floating point>

```

In this example, the case 0 returns the floating point `<fp var>`, expanding once after that floating point. Case 1 does `<some computation>` using the `<floating point>` (presumably compute the operation requested by the user in that non-trivial case). Case 2 returns the `<floating point>` without modifying it, removing the `<junk>` and expanding once after. Case 3 closes the conditional, removes the `<junk>` and the `<floating point>`, and expands `<something>` next. In other cases, the “`<junk>`” is expanded, performing some other operation on the `<floating point>`. We provide similar functions with two trailing `<floating points>`.

`_fp_case_use:nw` This function ends a TeX conditional, removes junk until the next floating point, and places its first argument before that floating point, to perform some operation on the floating point.

```

11544 \cs_new:Npn \_fp_case_use:nw #1#2 \fi: #3 \s__fp { \fi: #1 \s__fp }

```

(End definition for `_fp_case_use:nw`.)

`_fp_case_return:nw` This function ends a TeX conditional, removes junk and a floating point, and places its first argument in the input stream. A quirk is that we don’t define this function requiring a floating point to follow, simply anything ending in a semicolon. This, in turn, means that the `<junk>` may not contain semicolons.

```

11545 \cs_new:Npn \_fp_case_return:nw #1#2 \fi: #3 ; { \fi: #1 }

```

(End definition for _fp_case_return:nw.)

_fp_case_return_o:Nw This function ends a T_EX conditional, removes junk and a floating point, and returns its first argument (an *<fp var>*) then expands once after it.

```
11546 \cs_new:Npn \_fp_case_return_o:Nw #1#2 \fi: #3 \s__fp #4 ;
11547 { \fi: \exp_after:wN #1 }
```

(End definition for _fp_case_return_o:Nw.)

_fp_case_return_same_o:w This function ends a T_EX conditional, removes junk, and returns the following floating point, expanding once after it.

```
11548 \cs_new:Npn \_fp_case_return_same_o:w #1 \fi: #2 \s__fp
11549 { \fi: \_fp_exp_after_o:w \s__fp }
```

(End definition for _fp_case_return_same_o:w.)

_fp_case_return_o:Nww Same as _fp_case_return_o:Nw but with two trailing floating points.

```
11550 \cs_new:Npn \_fp_case_return_o:Nww #1#2 \fi: #3 \s__fp #4 ; #5 ;
11551 { \fi: \exp_after:wN #1 }
```

(End definition for _fp_case_return_o:Nww.)

_fp_case_return_i_o:ww Similar to _fp_case_return_same_o:w, but this returns the first or second of two trailing floating point numbers, expanding once after the result.

```
11552 \cs_new:Npn \_fp_case_return_i_o:ww #1 \fi: #2 \s__fp #3 ; \s__fp #4 ;
11553 { \fi: \_fp_exp_after_o:w \s__fp #3 ; }
11554 \cs_new:Npn \_fp_case_return_ii_o:ww #1 \fi: #2 \s__fp #3 ;
11555 { \fi: \_fp_exp_after_o:w }
```

(End definition for _fp_case_return_i_o:ww and _fp_case_return_ii_o:ww.)

21.9 Integer floating points

_fp_int_p:w Tests if the floating point argument is an integer. For normal floating point numbers, _fp_int:wTF this holds if the rounding digit resulting from _fp_decimate:nNnnnn is 0.

```
11556 \prg_new_conditional:Npnm \_fp_int:w \s__fp \_fp_chk:w #1 #2 #3 #4;
11557 { TF , T , F , p }
11558 {
11559   \if_case:w #1 \exp_stop_f:
11560     \prg_return_true:
11561   \or:
11562     \if_charcode:w 0
11563       \_fp_decimate:nNnnnn { \c__fp_prec_int - #3 }
11564       \_fp_use_i_until_s:nw #4
11565       \prg_return_true:
11566     \else:
11567       \prg_return_false:
11568     \fi:
11569   \else: \prg_return_false:
11570   \fi:
11571 }
```

(End definition for _fp_int:wTF.)

21.10 Small integer floating points

```

\__fp_small_int:wTF
\__fp_small_int_true:wTF
\__fp_small_int_normal:NnwTF
\__fp_small_int_test:NnnwNTF

```

Tests if the floating point argument is an integer or $\pm\infty$. If so, it is converted to an integer in the range $[-10^8, 10^8]$ and fed as a braced argument to the *⟨true code⟩*. Otherwise, the *⟨false code⟩* is performed.

First filter special cases: zeros and infinities are integers, `nan` is not. For normal numbers, decimate. If the rounding digit is not 0 run the *⟨false code⟩*. If it is, then the integer is #2 #3; use #3 if #2 vanishes and otherwise 10^8 .

```

11572 \cs_new:Npn \__fp_small_int:wTF \s__fp \__fp_chk:w #1#2
11573 {
11574   \if_case:w #1 \exp_stop_f:
11575     \__fp_case_return:nw { \__fp_small_int_true:wTF 0 ; }
11576   \or: \exp_after:wN \__fp_small_int_normal:NnwTF
11577   \or:
11578     \__fp_case_return:nw
11579     {
11580       \exp_after:wN \__fp_small_int_true:wTF \__int_value:w
11581       \if_meaning:w 2 #2 - \fi: 1 0000 0000 ;
11582     }
11583   \else: \__fp_case_return:nw \use_ii:nn
11584   \fi:
11585   #2
11586 }
11587 \cs_new:Npn \__fp_small_int_true:wTF #1; #2#3 { #2 {#1} }
11588 \cs_new:Npn \__fp_small_int_normal:NnwTF #1#2#3;
11589 {
11590   \__fp_decimate:nNnnnn { \c__fp_prec_int - #2 }
11591   \__fp_small_int_test:NnnwNw
11592   #3 #1
11593 }
11594 \cs_new:Npn \__fp_small_int_test:NnnwNw #1#2#3#4; #5
11595 {
11596   \if_meaning:w 0 #1
11597     \exp_after:wN \__fp_small_int_true:wTF
11598     \__int_value:w \if_meaning:w 2 #5 - \fi:
11599     \if_int_compare:w #2 > 0 \exp_stop_f:
11600     1 0000 0000
11601   \else:
11602     #3
11603   \fi:
11604   \exp_after:wN ;
11605   \else:
11606     \exp_after:wN \use_ii:nn
11607   \fi:
11608 }

```

(End definition for `__fp_small_int:wTF` and others.)

21.11 Length of a floating point array

```

\__fp_array_count:n
\__fp_array_count_loop:Nw

```

Count the number of items in an array of floating points. The technique is very similar to `\tl_count:n`, but with the loop built-in. Checking for the end of the loop is done with the `\use_none:n #1` construction.


```

11609 \cs_new:Npn \__fp_array_count:n #1
11610 {
11611   \__int_value:w \__int_eval:w 0
11612   \__fp_array_count_loop:Nw #1 { ? \__prg_break: } ;
11613   \__prg_break_point:
11614   \__int_eval_end:
11615 }
11616 \cs_new:Npn \__fp_array_count_loop:Nw #1#2;
11617 { \use_none:n #1 + 1 \__fp_array_count_loop:Nw }

```

(End definition for __fp_array_count:n and __fp_array_count_loop:Nw.)

21.12 x-like expansion expandably

__fp_expand:n
 __fp_expand_loop:nwnN

This expandable function behaves in a way somewhat similar to \use:x, but much less robust. The argument is f-expanded, then the leading item (often a single character token) is moved to a storage area after \s__fp_mark, and f-expansion is applied again, repeating until the argument is empty. The result built one piece at a time is then inserted in the input stream. Note that spaces are ignored by this procedure, unless surrounded with braces. Multiple tokens which do not need expansion can be inserted within braces.

```

11618 \cs_new:Npn \__fp_expand:n #1
11619 {
11620   \__fp_expand_loop:nwnN { }
11621   #1 \prg_do_nothing:
11622   \s__fp_mark { } \__fp_expand_loop:nwnN
11623   \s__fp_mark { } \__fp_use_i_until_s:nw ;
11624 }
11625 \cs_new:Npn \__fp_expand_loop:nwnN #1#2 \s__fp_mark #3 #4
11626 {
11627   \exp_after:wN #4 \exp:w \exp_end_continue_f:w
11628   #2
11629   \s__fp_mark { #3 #1 } #4
11630 }

```

(End definition for __fp_expand:n and __fp_expand_loop:nwnN.)

21.13 Messages

Using a floating point directly is an error.

```

11631 \__msg_kernel_new:nnnn { kernel } { misused-fp }
11632 { A~floating~point~with~value~'#1'~was~misused. }
11633 {
11634   To~obtain~the~value~of~a~floating~point~variable,~use~
11635   '\token_to_str:N \fp_to_decimal:N',~
11636   '\token_to_str:N \fp_to_scientific:N',~or~other~
11637   conversion~functions.
11638 }
11639 </initex | package>

```

22 13fp-traps Implementation

11640 $\langle *initex \mid package \rangle$

11641 $\langle @@=fp \rangle$

Exceptions should be accessed by an `n`-type argument, among

- `invalid_operation`
- `division_by_zero`
- `overflow`
- `underflow`
- `inexact` (actually never used).

22.1 Flags

Flags to denote exceptions.

```
flag_fp_invalid_operation 11642 \flag_new:n { fp_invalid_operation }
flag_fp_division_by_zero 11643 \flag_new:n { fp_division_by_zero }
flag_fp_overflow          11644 \flag_new:n { fp_overflow }
flag_fp_underflow         11645 \flag_new:n { fp_underflow }
```

(End definition for flag `fp_invalid_operation` and others. These variables are documented on page 191.)

22.2 Traps

Exceptions can be trapped to obtain custom behaviour. When an invalid operation or a division by zero is trapped, the trap receives as arguments the result as an `N`-type floating point number, the function name (multiple letters for prefix operations, or a single symbol for infix operations), and the operand(s). When an overflow or underflow is trapped, the trap receives the resulting overly large or small floating point number if it is not too big, otherwise it receives $+\infty$. Currently, the `inexact` exception is entirely ignored.

The behaviour when an exception occurs is controlled by the definitions of the functions

- `__fp_invalid_operation:nnw,`
- `__fp_invalid_operation_o:Nww,`
- `__fp_invalid_operation_tl_o:ff,`
- `__fp_division_by_zero_o:Nnw,`
- `__fp_division_by_zero_o:NNww,`
- `__fp_overflow:w,`
- `__fp_underflow:w.`

Rather than changing them directly, we provide a user interface as `\fp_trap:nn { $\langle exception \rangle$ } { $\langle way of trapping \rangle$ }`, where the $\langle way of trapping \rangle$ is one of `error`, `flag`, or `none`.

We also provide `__fp_invalid_operation_o:nw`, defined in terms of `__fp_invalid_operation:nnw`.

`\fp_trap:nn`

```
11646 \cs_new_protected:Npn \fp_trap:nn #1#2
11647 {
11648   \cs_if_exist_use:cF { __fp_trap_#1_set_#2: }
11649   {
11650     \clist_if_in:nnTF
11651     { invalid_operation , division_by_zero , overflow , underflow }
11652     {#1}
11653     {
11654       \__msg_kernel_error:nnxx { kernel }
11655       { unknown-fpu-trap-type } {#1} {#2}
11656     }
11657     {
11658       \__msg_kernel_error:nnx
11659       { kernel } { unknown-fpu-exception } {#1}
11660     }
11661   }
11662 }
```

(End definition for `\fp_trap:nn`. This function is documented on page 191.)

`__fp_trap_invalid_operation_set_error:` We provide three types of trapping for invalid operations: either produce an error and
`__fp_trap_invalid_operation_set_flag:` raise the relevant flag; or only raise the flag; or don't even raise the flag. In most cases,
`__fp_trap_invalid_operation_set_none:` the function produces as a result its first argument, possibly with post-expansion.
`__fp_trap_invalid_operation_set:N`

```
11663 \cs_new_protected:Npn \__fp_trap_invalid_operation_set_error:
11664 { \__fp_trap_invalid_operation_set:N \prg_do_nothing: }
11665 \cs_new_protected:Npn \__fp_trap_invalid_operation_set_flag:
11666 { \__fp_trap_invalid_operation_set:N \use_none:nnnnn }
11667 \cs_new_protected:Npn \__fp_trap_invalid_operation_set_none:
11668 { \__fp_trap_invalid_operation_set:N \use_none:nnnnnnn }
11669 \cs_new_protected:Npn \__fp_trap_invalid_operation_set:N #1
11670 {
11671   \exp_args:Nno \use:n
11672   { \cs_set:Npn \__fp_invalid_operation:nnw ##1##2##3; }
11673   {
11674     #1
11675     \__fp_error:nnfn { fp-invalid } {##2} { \fp_to_tl:n { ##3; } } { }
11676     \flag_raise:n { fp_invalid_operation }
11677     ##1
11678   }
11679   \exp_args:Nno \use:n
11680   { \cs_set:Npn \__fp_invalid_operation_o:Nww ##1##2; ##3; }
11681   {
11682     #1
11683     \__fp_error:nffn { fp-invalid-ii }
11684     { \fp_to_tl:n { ##2; } } { \fp_to_tl:n { ##3; } } {##1}
11685     \flag_raise:n { fp_invalid_operation }
11686     \exp_after:wN \c_nan_fp
11687   }
11688   \exp_args:Nno \use:n
11689   { \cs_set:Npn \__fp_invalid_operation_tl_o:ff ##1##2 }
11690   {
11691     #1
11692     \__fp_error:nffn { fp-invalid } {##1} {##2} { }
```

```

11693         \flag_raise:n { fp_invalid_operation }
11694         \exp_after:wN \c_nan_fp
11695     }
11696 }

```

(End definition for `__fp_trap_invalid_operation_set_error:` and others.)

`__fp_trap_division_by_zero_set_error:` We provide three types of trapping for invalid operations and division by zero: either produce an error and raise the relevant flag; or only raise the flag; or don't even raise the flag. In all cases, the function must produce a result, namely its first argument, $\pm\infty$ or NaN.

```

11697 \cs_new_protected:Npn \__fp_trap_division_by_zero_set_error:
11698 { \__fp_trap_division_by_zero_set:N \prg_do_nothing: }
11699 \cs_new_protected:Npn \__fp_trap_division_by_zero_set_flag:
11700 { \__fp_trap_division_by_zero_set:N \use_none:nnnnn }
11701 \cs_new_protected:Npn \__fp_trap_division_by_zero_set_none:
11702 { \__fp_trap_division_by_zero_set:N \use_none:nnnnnnn }
11703 \cs_new_protected:Npn \__fp_trap_division_by_zero_set:N #1
11704 {
11705     \exp_args:Nno \use:n
11706     { \cs_set:Npn \__fp_division_by_zero_o:NNw ##1##2##3; }
11707     {
11708         #1
11709         \__fp_error:nfn { fp-zero-div } {##2} { \fp_to_tl:n { ##3; } } { }
11710         \flag_raise:n { fp_division_by_zero }
11711         \exp_after:wN ##1
11712     }
11713     \exp_args:Nno \use:n
11714     { \cs_set:Npn \__fp_division_by_zero_o:NNww ##1##2##3; ##4; }
11715     {
11716         #1
11717         \__fp_error:nfn { fp-zero-div-ii }
11718         { \fp_to_tl:n { ##3; } } { \fp_to_tl:n { ##4; } } {##2}
11719         \flag_raise:n { fp_division_by_zero }
11720         \exp_after:wN ##1
11721     }
11722 }

```

(End definition for `__fp_trap_division_by_zero_set_error:` and others.)

`__fp_trap_overflow_set_error:` Just as for invalid operations and division by zero, the three different behaviours are obtained by feeding `\prg_do_nothing:`, `\use_none:nnnnn` or `\use_none:nnnnnnn` to an auxiliary, with a further auxiliary common to overflow and underflow functions. In most cases, the argument of the `__fp_overflow:w` and `__fp_underflow:w` functions will be an (almost) normal number (with an exponent outside the allowed range), and the error message thus displays that number together with the result to which it overflowed or underflowed. For extreme cases such as `10 ** 1e9999`, the exponent would be too large for TeX, and `__fp_overflow:w` receives $\pm\infty$ (`__fp_underflow:w` would receive ± 0); then we cannot do better than simply say an overflow or underflow occurred.

```

11723 \cs_new_protected:Npn \__fp_trap_overflow_set_error:
11724 { \__fp_trap_overflow_set:N \prg_do_nothing: }
11725 \cs_new_protected:Npn \__fp_trap_overflow_set_flag:
11726 { \__fp_trap_overflow_set:N \use_none:nnnnn }
11727 \cs_new_protected:Npn \__fp_trap_overflow_set_none:

```

```

11728 { \__fp_trap_overflow_set:N \use_none:nnnnnnn }
11729 \cs_new_protected:Npn \__fp_trap_overflow_set:N #1
11730 { \__fp_trap_overflow_set:NnNn #1 { overflow } \__fp_inf_fp:N { inf } }
11731 \cs_new_protected:Npn \__fp_trap_underflow_set_error:
11732 { \__fp_trap_underflow_set:N \prg_do_nothing: }
11733 \cs_new_protected:Npn \__fp_trap_underflow_set_flag:
11734 { \__fp_trap_underflow_set:N \use_none:nnnnn }
11735 \cs_new_protected:Npn \__fp_trap_underflow_set_none:
11736 { \__fp_trap_underflow_set:N \use_none:nnnnnnn }
11737 \cs_new_protected:Npn \__fp_trap_underflow_set:N #1
11738 { \__fp_trap_overflow_set:NnNn #1 { underflow } \__fp_zero_fp:N { 0 } }
11739 \cs_new_protected:Npn \__fp_trap_overflow_set:NnNn #1#2#3#4
11740 {
11741   \exp_args:Nno \use:n
11742   { \cs_set:cpn { \__fp_ #2 :w } \s__fp \__fp_chk:w ##1##2##3; }
11743   {
11744     #1
11745     \__fp_error:nffn
11746     { fp-flow \if_meaning:w 1 ##1 -to \fi: }
11747     { \fp_to_tl:n { \s__fp \__fp_chk:w ##1##2##3; } }
11748     { \token_if_eq_meaning:NNF 0 ##2 { - } #4 }
11749     {#2}
11750     \flag_raise:n { fp_#2 }
11751     #3 ##2
11752   }
11753 }

```

(End definition for __fp_trap_overflow_set_error: and others.)

```

\__fp_invalid_operation:nnw Initialize the control sequences (to log properly their existence). Then set invalid operations
  \__fp_invalid_operation_o:Nnw to trigger an error, and division by zero, overflow, and underflow to act silently on
  \__fp_invalid_operation_tl_o:ff their flag.
\__fp_division_by_zero_o:Nnw
  \__fp_division_by_zero_o:NNww
  \__fp_overflow:w
  \__fp_underflow:w
11754 \cs_new:Npn \__fp_invalid_operation:nnw #1#2#3; { }
11755 \cs_new:Npn \__fp_invalid_operation_o:Nnw #1#2; #3; { }
11756 \cs_new:Npn \__fp_invalid_operation_tl_o:ff #1 #2 { }
11757 \cs_new:Npn \__fp_division_by_zero_o:Nnw #1#2#3; { }
11758 \cs_new:Npn \__fp_division_by_zero_o:NNww #1#2#3; #4; { }
11759 \cs_new:Npn \__fp_overflow:w { }
11760 \cs_new:Npn \__fp_underflow:w { }
11761 \fp_trap:nn { invalid_operation } { error }
11762 \fp_trap:nn { division_by_zero } { flag }
11763 \fp_trap:nn { overflow } { flag }
11764 \fp_trap:nn { underflow } { flag }

```

(End definition for __fp_invalid_operation:nnw and others.)

```

\__fp_invalid_operation_o:nw Convenient short-hands for returning \c_nan_fp for a unary or binary operation, and
\__fp_invalid_operation_o:fw expanding after.
11765 \cs_new:Npn \__fp_invalid_operation_o:nw
11766 { \__fp_invalid_operation:nnw { \exp_after:wN \c_nan_fp } }
11767 \cs_generate_variant:Nn \__fp_invalid_operation_o:nw { f }

```

(End definition for __fp_invalid_operation_o:nw.)

22.3 Errors

```

\__fp_error:nnnn
\__fp_error:nnfn 11768 \cs_new:Npn \__fp_error:nnnn
\__fp_error:nffn 11769 { \__msg_kernel_expandable_error:nnnnn { kernel } }
11770 \cs_generate_variant:Nn \__fp_error:nnnn { nnf, nff }

```

(End definition for __fp_error:nnnn.)

22.4 Messages

Some messages.

```

11771 \__msg_kernel_new:nnnn { kernel } { unknown-fpu-exception }
11772 {
11773   The~FPU~exception~'#1'~is~not~known:~
11774   that~trap~will~never~be~triggered.
11775 }
11776 {
11777   The~only~exceptions~to~which~traps~can~be~attached~are \
11778   \iow_indent:n
11779   {
11780     * ~ invalid_operation \
11781     * ~ division_by_zero \
11782     * ~ overflow \
11783     * ~ underflow
11784   }
11785 }
11786 \__msg_kernel_new:nnnn { kernel } { unknown-fpu-trap-type }
11787 { The~FPU~trap~type~'#2'~is~not~known. }
11788 {
11789   The~trap~type~must~be~one~of \
11790   \iow_indent:n
11791   {
11792     * ~ error \
11793     * ~ flag \
11794     * ~ none
11795   }
11796 }
11797 \__msg_kernel_new:nnn { kernel } { fp-flow }
11798 { An ~ #3 ~ occurred. }
11799 \__msg_kernel_new:nnn { kernel } { fp-flow-to }
11800 { #1 ~ #3 ed ~ to ~ #2 . }
11801 \__msg_kernel_new:nnn { kernel } { fp-zero-div }
11802 { Division~by~zero~in~ #1 (#2) }
11803 \__msg_kernel_new:nnn { kernel } { fp-zero-div-ii }
11804 { Division~by~zero~in~ (#1) #3 (#2) }
11805 \__msg_kernel_new:nnn { kernel } { fp-invalid }
11806 { Invalid~operation~ #1 (#2) }
11807 \__msg_kernel_new:nnn { kernel } { fp-invalid-ii }
11808 { Invalid~operation~ (#1) #3 (#2) }
11809 </initex | package>

```

23 l3fp-round implementation

11810 <*initex | package>

11811 <@@=fp>

__fp_parse_word_trunc:N

__fp_parse_word_floor:N

__fp_parse_word_ceil:N

11812 \cs_new:Npn __fp_parse_word_trunc:N

11813 { __fp_parse_function:NNN __fp_round_o:Nw __fp_round_to_zero:NNN }

11814 \cs_new:Npn __fp_parse_word_floor:N

11815 { __fp_parse_function:NNN __fp_round_o:Nw __fp_round_to_ninf:NNN }

11816 \cs_new:Npn __fp_parse_word_ceil:N

11817 { __fp_parse_function:NNN __fp_round_o:Nw __fp_round_to_pinf:NNN }

(End definition for __fp_parse_word_trunc:N, __fp_parse_word_floor:N, and __fp_parse_word_ceil:N.)

__fp_parse_word_round:N

__fp_parse_round:Nw

__fp_parse_round_no_error:Nw

__fp_parse_round_deprecation_error:Nw

round+

round0

round-

This looks for +, -, 0 after round. That syntax was deprecated in 2013 but the system to tell users about deprecated syntax was not really available then, so we did not have anything set up. When l3doc complains, remove the syntax by removing everything until the last \fi: in __fp_parse_word_round:N (and getting rid of the unused definitions of __fp_parse_round:Nw and so on, as well as the fp-deprecated error in l3fp-parse).

11818 \cs_new:Npn __fp_parse_word_round:N #1#2

11819 {

11820 \if_meaning:w + #2

11821 __fp_parse_round:Nw __fp_round_to_pinf:NNN

11822 \else:

11823 \if_meaning:w 0 #2

11824 __fp_parse_round:Nw __fp_round_to_zero:NNN

11825 \else:

11826 \if_meaning:w - #2

11827 __fp_parse_round:Nw __fp_round_to_ninf:NNN

11828 \fi:

11829 \fi:

11830 \fi:

11831 __fp_parse_function:NNN

11832 __fp_round_o:Nw __fp_round_to_nearest:NNN #1

11833 #2

11834 }

11835 __debug:TF

11836 {

11837 \tl_gput_right:Nn \g__debug_deprecation_on_tl

11838 {

11839 \cs_set_eq:NN __fp_parse_round:Nw

11840 __fp_parse_round_deprecation_error:Nw

11841 }

11842 \tl_gput_right:Nn \g__debug_deprecation_off_tl

11843 {

11844 \cs_set_eq:NN __fp_parse_round:Nw

11845 __fp_parse_round_no_error:Nw

11846 }

11847 \cs_new:Npn __fp_parse_round_deprecation_error:Nw

11848 #1 #2 __fp_round_to_nearest:NNN #3#4

11849 {

11850 __fp_error:nmfn { fp-deprecated } { round#4() }

```

11851         {
11852             \str_case:nn {#2}
11853             { { + } { ceil } { 0 } { trunc } { - } { floor } }
11854             } { }
11855         #2 #1 #3
11856     }
11857     \cs_new:Npn \__fp_parse_round_no_error:Nw
11858         #1 #2 \__fp_round_to_nearest:NNN #3#4 { #2 #1 #3 }
11859     \cs_new_eq:NN \__fp_parse_round:Nw \__fp_parse_round_no_error:Nw
11860 }
11861 {
11862     \cs_new:Npn \__fp_parse_round:Nw
11863         #1 #2 \__fp_round_to_nearest:NNN #3#4 { #2 #1 #3 }
11864 }

```

(End definition for `__fp_parse_word_round:N` and others. These functions are documented on page ??.)

23.1 Rounding tools

`\c__fp_five_int` This is used as the half-point for which numbers are rounded up/down.

```

11865 \int_const:Nn \c__fp_five_int { 5 }

```

(End definition for `\c__fp_five_int`.)

Floating point operations often yield a result that cannot be exactly represented in a significand with 16 digits. In that case, we need to round the exact result to a representable number. The IEEE standard defines four rounding modes:

- Round to nearest: round to the representable floating point number whose absolute difference with the exact result is the smallest. If the exact result lies exactly at the mid-point between two consecutive representable floating point numbers, round to the floating point number whose last digit is even.
- Round towards negative infinity: round to the greatest floating point number not larger than the exact result.
- Round towards zero: round to a floating point number with the same sign as the exact result, with the largest absolute value not larger than the absolute value of the exact result.
- Round towards positive infinity: round to the least floating point number not smaller than the exact result.

This is not fully implemented in `l3fp` yet, and transcendental functions fall back on the “round to nearest” mode. All rounding for basic algebra is done through the functions defined in this module, which can be redefined to change their rounding behaviour (but there is not interface for that yet).

The rounding tools available in this module are many variations on a base function `__fp_round:NNN`, which expands to `0\exp_stop_f:` or `1\exp_stop_f:` depending on whether the final result should be rounded up or down.

- `__fp_round:NNN <sign> <digit1> <digit2>` can expand to `0\exp_stop_f:` or `1\exp_stop_f:`.
- `__fp_round_s:NNNw <sign> <digit1> <digit2> <more digits>`; can expand to `0\exp_stop_f;;` or `1\exp_stop_f;;`.

- `__fp_round_neg:NNN` $\langle sign \rangle$ $\langle digit_1 \rangle$ $\langle digit_2 \rangle$ can expand to `0\exp_stop_f:` or `1\exp_stop_f:`.

See implementation comments for details on the syntax.

```
\__fp_round:NNN
\__fp_round_to_nearest:NNN
  \__fp_round_to_nearest_ninf:NNN
  \__fp_round_to_nearest_zero:NNN
  \__fp_round_to_nearest_pinf:NNN
\__fp_round_to_ninf:NNN
\__fp_round_to_zero:NNN
\__fp_round_to_pinf:NNN
```

`__fp_round:NNN` $\langle final\ sign \rangle$ $\langle digit_1 \rangle$ $\langle digit_2 \rangle$
If rounding the number $\langle final\ sign \rangle \langle digit_1 \rangle . \langle digit_2 \rangle$ to an integer rounds it towards zero (truncates it), this function expands to `0\exp_stop_f:`, and otherwise to `1\exp_stop_f:`. Typically used within the scope of an `__int_eval:w`, to add 1 if needed, and thereby round correctly. The result depends on the rounding mode.

It is very important that $\langle final\ sign \rangle$ be the final sign of the result. Otherwise, the result would be incorrect in the case of rounding towards $-\infty$ or towards $+\infty$. Also recall that $\langle final\ sign \rangle$ is 0 for positive, and 2 for negative.

By default, the functions below return `0\exp_stop_f:`, but this is superseded by `__fp_round_return_one:`, which instead returns `1\exp_stop_f:`, expanding everything and removing `0\exp_stop_f:` in the process. In the case of rounding towards $\pm\infty$ or towards 0, this is not really useful, but it prepares us for the “round to nearest, ties to even” mode.

The “round to nearest” mode is the default. If the $\langle digit_2 \rangle$ is larger than 5, then round up. If it is less than 5, round down. If it is exactly 5, then round such that $\langle digit_1 \rangle$ plus the result is even. In other words, round up if $\langle digit_1 \rangle$ is odd.

The “round to nearest” mode has three variants, which differ in how ties are rounded: down towards $-\infty$, truncated towards 0, or up towards $+\infty$.

```
11866 \cs_new:Npn \__fp_round_return_one:
11867   { \exp_after:wN 1 \exp_after:wN \exp_stop_f: \exp:w }
11868 \cs_new:Npn \__fp_round_to_ninf:NNN #1 #2 #3
11869   {
11870     \if_meaning:w 2 #1
11871     \if_int_compare:w #3 > 0 \exp_stop_f:
11872       \__fp_round_return_one:
11873     \fi:
11874     \fi:
11875     0 \exp_stop_f:
11876   }
11877 \cs_new:Npn \__fp_round_to_zero:NNN #1 #2 #3 { 0 \exp_stop_f: }
11878 \cs_new:Npn \__fp_round_to_pinf:NNN #1 #2 #3
11879   {
11880     \if_meaning:w 0 #1
11881     \if_int_compare:w #3 > 0 \exp_stop_f:
11882       \__fp_round_return_one:
11883     \fi:
11884     \fi:
11885     0 \exp_stop_f:
11886   }
11887 \cs_new:Npn \__fp_round_to_nearest:NNN #1 #2 #3
11888   {
11889     \if_int_compare:w #3 > \c__fp_five_int
11890       \__fp_round_return_one:
11891     \else:
11892       \if_meaning:w 5 #3
11893         \if_int_odd:w #2 \exp_stop_f:
11894         \__fp_round_return_one:
```

```

11895         \fi:
11896     \fi:
11897 \fi:
11898     0 \exp_stop_f:
11899 }
11900 \cs_new:Npn \__fp_round_to_nearest_ninf:NNN #1 #2 #3
11901 {
11902     \if_int_compare:w #3 > \c__fp_five_int
11903         \__fp_round_return_one:
11904     \else:
11905         \if_meaning:w 5 #3
11906         \if_meaning:w 2 #1
11907             \__fp_round_return_one:
11908         \fi:
11909     \fi:
11910 \fi:
11911     0 \exp_stop_f:
11912 }
11913 \cs_new:Npn \__fp_round_to_nearest_zero:NNN #1 #2 #3
11914 {
11915     \if_int_compare:w #3 > \c__fp_five_int
11916         \__fp_round_return_one:
11917     \fi:
11918     0 \exp_stop_f:
11919 }
11920 \cs_new:Npn \__fp_round_to_nearest_pinf:NNN #1 #2 #3
11921 {
11922     \if_int_compare:w #3 > \c__fp_five_int
11923         \__fp_round_return_one:
11924     \else:
11925         \if_meaning:w 5 #3
11926         \if_meaning:w 0 #1
11927             \__fp_round_return_one:
11928         \fi:
11929     \fi:
11930 \fi:
11931     0 \exp_stop_f:
11932 }
11933 \cs_new_eq:NN \__fp_round:NNN \__fp_round_to_nearest:NNN

```

(End definition for __fp_round:NNN and others.)

__fp_round_s:NNNw

__fp_round_s:NNNw *<final sign>* *<digit>* *<more digits>* ;

Similar to __fp_round:NNN, but with an extra semicolon, this function expands to 0\exp_stop_f:; if rounding *<final sign>**<digit>**<more digits>* to an integer truncates, and to 1\exp_stop_f:; otherwise. The *<more digits>* part must be a digit, followed by something that does not overflow a \int_use:N __int_eval:w construction. The only relevant information about this piece is whether it is zero or not.

```

11934 \cs_new:Npn \__fp_round_s:NNNw #1 #2 #3 #4;
11935 {
11936     \exp_after:wN \__fp_round:NNN
11937     \exp_after:wN #1
11938     \exp_after:wN #2
11939     \__int_value:w \__int_eval:w

```

```

11940     \if_int_odd:w 0 \if_meaning:w 0 #3 1 \fi:
11941         \if_meaning:w 5 #3 1 \fi:
11942         \exp_stop_f:
11943     \if_int_compare:w \__int_eval:w #4 > 0 \exp_stop_f:
11944     1 +
11945     \fi:
11946 \fi:
11947 #3
11948 ;
11949 }

```

(End definition for __fp_round_s:NNNw.)

__fp_round_digit:Nw __int_value:w __fp_round_digit:Nw <digit> <intexpr> ;

This function should always be called within an __int_value:w or __int_eval:w expansion; it may add an extra __int_eval:w, which means that the integer or integer expression should not be ended with a synonym of \relax, but with a semi-colon for instance.

```

11950 \cs_new:Npn \__fp_round_digit:Nw #1 #2;
11951 {
11952     \if_int_odd:w \if_meaning:w 0 #1 1 \else:
11953         \if_meaning:w 5 #1 1 \else:
11954         0 \fi: \fi: \exp_stop_f:
11955     \if_int_compare:w \__int_eval:w #2 > 0 \exp_stop_f:
11956     \__int_eval:w 1 +
11957     \fi:
11958 \fi:
11959 #1
11960 }

```

(End definition for __fp_round_digit:Nw.)

__fp_round_neg:NNN __fp_round_neg:NNN <final sign> <digit₁> <digit₂>

This expands to 0\exp_stop_f: or 1\exp_stop_f: after doing the following test. Starting from a number of the form <final sign>0.<15 digits><digit₁> with exactly 15 (non-all-zero) digits before <digit₁>, subtract from it <final sign>0.0...0<digit₂>, where there are 16 zeros. If in the current rounding mode the result should be rounded down, then this function returns 1\exp_stop_f:. Otherwise, *i.e.*, if the result is rounded back to the first operand, then this function returns 0\exp_stop_f:.

It turns out that this negative “round to nearest” is identical to the positive one. And this is the default mode.

```

11961 \cs_new_eq:NN \__fp_round_to_ninf_neg:NNN \__fp_round_to_pinf:NNN
11962 \cs_new:Npn \__fp_round_to_zero_neg:NNN #1 #2 #3
11963 {
11964     \if_int_compare:w #3 > 0 \exp_stop_f:
11965     \__fp_round_return_one:
11966     \fi:
11967     0 \exp_stop_f:
11968 }
11969 \cs_new_eq:NN \__fp_round_to_pinf_neg:NNN \__fp_round_to_ninf:NNN
11970 \cs_new_eq:NN \__fp_round_to_nearest_neg:NNN \__fp_round_to_nearest:NNN
11971 \cs_new_eq:NN \__fp_round_to_nearest_ninf_neg:NNN \__fp_round_to_nearest_pinf:NNN
11972 \cs_new:Npn \__fp_round_to_nearest_zero_neg:NNN #1 #2 #3

```

```

11973 {
11974     \if_int_compare:w #3 < \c__fp_five_int \else:
11975         \__fp_round_return_one:
11976     \fi:
11977     0 \exp_stop_f:
11978 }
11979 \cs_new_eq:NN \__fp_round_to_nearest_pinf_neg:NNN \__fp_round_to_nearest_ninf:NNN
11980 \cs_new_eq:NN \__fp_round_neg:NNN \__fp_round_to_nearest_neg:NNN

```

(End definition for __fp_round_neg:NNN and others.)

23.2 The round function

__fp_round_o:Nw The **trunc**, **ceil** and **floor** functions expect one or two arguments (the second is 0 by default), and the **round** function also accepts a third argument (**nan** by default), which changes #1 from __fp_round_to_nearest:NNN to one of its analogues.

```

11981 \cs_new:Npn \__fp_round_o:Nw #1#2 @
11982 {
11983     \if_case:w
11984         \__int_eval:w \__fp_array_count:n {#2} \__int_eval_end:
11985         \__fp_round_no_arg_o:Nw #1 \exp:w
11986     \or: \__fp_round:Nwn #1 #2 {0} \exp:w
11987     \or: \__fp_round:Nww #1 #2 \exp:w
11988     \else: \__fp_round:Nwww #1 #2 @ \exp:w
11989     \fi:
11990     \exp_after:wN \exp_end:
11991 }

```

(End definition for __fp_round_o:Nw.)

__fp_round_no_arg_o:Nw

```

11992 \cs_new:Npn \__fp_round_no_arg_o:Nw #1
11993 {
11994     \cs_if_eq:NNTF #1 \__fp_round_to_nearest:NNN
11995     { \__fp_error:nnnn { fp-num-args } { round () } { 1 } { 3 } }
11996     {
11997         \__fp_error:nffn { fp-num-args }
11998         { \__fp_round_name_from_cs:N #1 () } { 1 } { 2 }
11999     }
12000     \exp_after:wN \c_nan_fp
12001 }

```

(End definition for __fp_round_no_arg_o:Nw.)

__fp_round:Nwww Having three arguments is only allowed for **round**, not **trunc**, **ceil**, **floor**, so check for that case. If all is well, construct one of __fp_round_to_nearest:NNN, __fp_round_to_nearest_zero:NNN, __fp_round_to_nearest_ninf:NNN, __fp_round_to_nearest_pinf:NNN and act accordingly.

```

12002 \cs_new:Npn \__fp_round:Nwww #1#2 ; #3 ; \s__fp \__fp_chk:w #4#5#6 ; #7 @
12003 {
12004     \cs_if_eq:NNTF #1 \__fp_round_to_nearest:NNN
12005     {
12006         \tl_if_empty:nTF {#7}
12007         {

```

```

12008         \exp_args:Nc \__fp_round:Nww
12009         {
12010             __fp_round_to_nearest
12011             \if_meaning:w 0 #4 _zero \else:
12012             \if_case:w #5 \exp_stop_f: _pinf \or: \else: _ninf \fi: \fi:
12013             :NNN
12014         }
12015         #2 ; #3 ;
12016     }
12017     {
12018         \__fp_error:nnnn { fp-num-args } { round () } { 1 } { 3 }
12019         \exp_after:wN \c_nan_fp
12020     }
12021 }
12022 {
12023     \__fp_error:nffn { fp-num-args }
12024     { \__fp_round_name_from_cs:N #1 () } { 1 } { 2 }
12025     \exp_after:wN \c_nan_fp
12026 }
12027 }

```

(End definition for __fp_round:Nwww.)

__fp_round_name_from_cs:N

```

12028 \cs_new:Npn \__fp_round_name_from_cs:N #1
12029 {
12030     \cs_if_eq:NNTF #1 \__fp_round_to_zero:NNN { trunc }
12031     {
12032         \cs_if_eq:NNTF #1 \__fp_round_to_ninf:NNN { floor }
12033         {
12034             \cs_if_eq:NNTF #1 \__fp_round_to_pinf:NNN { ceil }
12035             { round }
12036         }
12037     }
12038 }

```

(End definition for __fp_round_name_from_cs:N.)

__fp_round:Nww

__fp_round:Nwn

```

12039 \cs_new:Npn \__fp_round:Nww #1#2 ; #3 ;
12040 {
12041     \__fp_small_int:wTF #3; { \__fp_round:Nwn #1#2; }
12042     {
12043         \__fp_invalid_operation_tl_o:ff
12044         { \__fp_round_name_from_cs:N #1 }
12045         { \__fp_array_to_clist:n { #2; #3; } }
12046     }
12047 }
12048 \cs_new:Npn \__fp_round:Nwn #1 \s__fp \__fp_chk:w #2#3#4; #5
12049 {
12050     \if_meaning:w 1 #2
12051     \exp_after:wN \__fp_round_normal:NwNNnw
12052     \exp_after:wN #1
12053     \__int_value:w #5
12054     \else:

```

__fp_round_normal:NwNNnw

__fp_round_normal:NnnwNNnn

__fp_round_pack:Nw

__fp_round_normal:NNwNnn

__fp_round_normal_end:wwNnn

__fp_round_special:NwwNnn

__fp_round_special_aux:Nw

```

12055     \exp_after:wN \__fp_exp_after_o:w
12056     \fi:
12057     \s__fp \__fp_chk:w #2#3#4;
12058 }
12059 \cs_new:Npn \__fp_round_normal:NwNNnw #1#2 \s__fp \__fp_chk:w 1#3#4#5;
12060 {
12061     \__fp_decimate:nNnnnn { \c__fp_prec_int - #4 - #2 }
12062     \__fp_round_normal:NnnwNNnn #5 #1 #3 {#4} {#2}
12063 }
12064 \cs_new:Npn \__fp_round_normal:NnnwNNnn #1#2#3#4; #5#6
12065 {
12066     \exp_after:wN \__fp_round_normal:NNwNnn
12067     \__int_value:w \__int_eval:w
12068     \if_int_compare:w #2 > 0 \exp_stop_f:
12069         1 \__int_value:w #2
12070         \exp_after:wN \__fp_round_pack:Nw
12071         \__int_value:w \__int_eval:w 1#3 +
12072     \else:
12073         \if_int_compare:w #3 > 0 \exp_stop_f:
12074             1 \__int_value:w #3 +
12075     \fi:
12076     \fi:
12077     \exp_after:wN #5
12078     \exp_after:wN #6
12079     \use_none:nnnnnnn #3
12080     #1
12081     \__int_eval_end:
12082     0000 0000 0000 0000 ; #6
12083 }
12084 \cs_new:Npn \__fp_round_pack:Nw #1
12085 { \if_meaning:w 2 #1 + 1 \fi: \__int_eval_end: }
12086 \cs_new:Npn \__fp_round_normal:NNwNnn #1 #2
12087 {
12088     \if_meaning:w 0 #2
12089         \exp_after:wN \__fp_round_special:NwNnn
12090         \exp_after:wN #1
12091     \fi:
12092     \__fp_pack_twice_four:wNNNNNNNN
12093     \__fp_pack_twice_four:wNNNNNNNN
12094     \__fp_round_normal_end:wwNnn
12095     ; #2
12096 }
12097 \cs_new:Npn \__fp_round_normal_end:wwNnn #1;#2;#3#4#5
12098 {
12099     \exp_after:wN \__fp_exp_after_o:w \exp:w \exp_end_continue_f:w
12100     \__fp_sanitizew:Nw #3 #4 ; #1 ;
12101 }
12102 \cs_new:Npn \__fp_round_special:NwNnn #1#2;#3;#4#5#6
12103 {
12104     \if_meaning:w 0 #1
12105         \__fp_case_return:nw
12106         { \exp_after:wN \__fp_zero_fp:N \exp_after:wN #4 }
12107     \else:
12108         \exp_after:wN \__fp_round_special_aux:Nw

```

```

12109     \exp_after:wN #4
12110     \__int_value:w \__int_eval:w 1
12111     \if_meaning:w 1 #1 -#6 \else: +#5 \fi:
12112     \fi:
12113     ;
12114 }
12115 \cs_new:Npn \__fp_round_special_aux:Nw #1#2;
12116 {
12117     \exp_after:wN \__fp_exp_after_o:w \exp:w \exp_end_continue_f:w
12118     \__fp_sanitise:Nw #1#2; {1000}{0000}{0000}{0000};
12119 }

```

(End definition for `__fp_round:Nww` and others.)

```
12120 </initex | package>
```

24 l3fp-parse implementation

```
12121 <*initex | package>
```

```
12122 <@@=fp>
```

24.1 Work plan

The task at hand is non-trivial, and some previous failed attempts show that the code leads to unreadable logs, so we had better get it (almost) right the first time. Let us first describe our goal, then discuss the design precisely before writing any code.

```
\__fp_parse:n
```

```
\__fp_parse:n {<fpexpr>}
```

Evaluates the *<floating point expression>* and leaves the result in the input stream as an internal floating point number. This function forms the basis of almost all public `l3fp` functions. During evaluation, each token is fully `f`-expanded.

`__fp_parse_o:n` does the same but expands once after its result.

T_EXhackers note: Registers (integers, toks, etc.) are automatically unpacked, without requiring a function such as `\int_use:N`. Invalid tokens remaining after `f`-expansion lead to unrecoverable low-level T_EX errors.

(End definition for `__fp_parse:n`.)

Floating point expressions are composed of numbers, given in various forms, infix operators, such as `+`, `**`, or `,` (which joins two numbers into a list), and prefix operators, such as the unary `-`, functions, or opening parentheses. Here is a list of precedences which control the order of evaluation (some distinctions are irrelevant for the order of evaluation, but serve as signals), from the tightest binding to the loosest binding.

16 Function calls with multiple arguments.

15 Function calls expecting exactly one argument.

13/14 Binary `**` and `^` (right to left).

12 Unary `+`, `-`, `!` (right to left).

10 Binary `*`, `/`, and juxtaposition (implicit `*`).

- 9 Binary + and -.
- 7 Comparisons.
- 6 Logical and, denoted by &&.
- 5 Logical or, denoted by ||.
- 4 Ternary operator ?:, piece ?.
- 3 Ternary operator ?:, piece :.
- 2 Commas, and parentheses accepting commas.
- 1 Parentheses expecting exactly one argument.
- 0 Start and end of the expression.

```

\c__fp_prec_funcii_int
  \c__fp_prec_func_int      12123 \int_const:Nn \c__fp_prec_funcii_int { 16 }
\c__fp_prec_hatii_int      12124 \int_const:Nn \c__fp_prec_func_int   { 15 }
  \c__fp_prec_hat_int       12125 \int_const:Nn \c__fp_prec_hatii_int  { 14 }
  \c__fp_prec_not_int        12126 \int_const:Nn \c__fp_prec_hat_int   { 13 }
\c__fp_prec_times_int      12127 \int_const:Nn \c__fp_prec_not_int   { 12 }
  \c__fp_prec_plus_int       12128 \int_const:Nn \c__fp_prec_times_int  { 10 }
  \c__fp_prec_comp_int        12129 \int_const:Nn \c__fp_prec_plus_int   { 9 }
  \c__fp_prec_and_int         12130 \int_const:Nn \c__fp_prec_comp_int   { 7 }
  \c__fp_prec_or_int          12131 \int_const:Nn \c__fp_prec_and_int    { 6 }
\c__fp_prec_quest_int      12132 \int_const:Nn \c__fp_prec_or_int     { 5 }
\c__fp_prec_colon_int       12133 \int_const:Nn \c__fp_prec_quest_int  { 4 }
\c__fp_prec_comma_int       12134 \int_const:Nn \c__fp_prec_colon_int  { 3 }
\c__fp_prec_paren_int       12135 \int_const:Nn \c__fp_prec_comma_int  { 2 }
  \c__fp_prec_end_int         12136 \int_const:Nn \c__fp_prec_paren_int  { 1 }
                              12137 \int_const:Nn \c__fp_prec_end_int  { 0 }

```

(End definition for \c__fp_prec_funcii_int and others.)

24.1.1 Storing results

The main question in parsing expressions expandably is to decide where to put the intermediate results computed for various subexpressions.

One option is to store the values at the start of the expression, and carry them together as the first argument of each macro. However, we want to `f`-expand tokens one by one in the expression (as `\int_eval:n` does), and with this approach, expanding the next unread token forces us to jump with `\exp_after:wN` over every value computed earlier in the expression. With this approach, the run-time grows at least quadratically in the length of the expression, if not as its cube (inserting the `\exp_after:wN` is tricky and slow).

A second option is to place those values at the end of the expression. Then expanding the next unread token is straightforward, but this still hits a performance issue: for long expressions we would be reaching all the way to the end of the expression at every step of the calculation. The run-time is again quadratic.

A variation of the above attempts to place the intermediate results which appear when computing a parenthesized expression near the closing parenthesis. This still lets us expand tokens as we go, and avoids performance problems as long as there are enough

parentheses. However, it would be much better to avoid requiring the closing parenthesis to be present as soon as the corresponding opening parenthesis is read: the closing parenthesis may still be hidden in a macro yet to be expanded.

Hence, we need to go for some fine expansion control: the result is stored *before* the start!

Let us illustrate this idea in a simple model: adding positive integers which may be resulting from the expansion of macros, or may be values of registers. Assume that one number, say, 12345, has already been found, and that we want to parse the next number. The current status of the code may look as follows.

```
\exp_after:wN \add:ww \__int_value:w 12345 \exp_after:wN ;
\exp:w \operand:w (stuff)
```

One step of expansion expands `\exp_after:wN`, which triggers the primitive `__int_value:w`, which reads the five digits we have already found, 12345. This integer is unfinished, causing the second `\exp_after:wN` to expand, and to trigger the construction `\exp:w`, which expands `\operand:w`, defined to read what follows and make a number out of it, then leave `\exp_end:`, the number, and a semicolon in the input stream. Once `\operand:w` is done expanding, we obtain essentially

```
\exp_after:wN \add:ww \__int_value:w 12345 ;
\exp:w \exp_end: 333444 ;
```

where in fact `\exp_after:wN` has already been expanded, `__int_value:w` has already seen 12345, and `\exp:w` is still looking for a number. It finds `\exp_end:`, hence expands to nothing. Now, `__int_value:w` sees the `;`, which cannot be part of a number. The expansion stops, and we are left with

```
\add:ww 12345 ; 333444 ;
```

which can safely perform the addition by grabbing two arguments delimited by `;`.

If we were to continue parsing the expression, then the following number should also be cleaned up before the next use of a binary operation such as `\add:ww`. Just like `__int_value:w 12345 \exp_after:wN ;` expanded what follows once, we need `\add:ww` to do the calculation, and in the process to expand the following once. This is also true in our real application: all the functions of the form `__fp_..._o:ww` expand what follows once. This comes at the cost of leaving tokens in the input stack, and we need to be careful not to waste this memory. All of our discussion above is nice but simplistic, as operations should not simply be performed in the order they appear.

24.1.2 Precedence and infix operators

The various operators we will encounter have different precedences, which influence the order of calculations: $1 + 2 \times 3 = 1 + (2 \times 3)$ because \times has a higher precedence than $+$. The true analog of our macro `\operand:w` must thus take care of that. When looking for an operand, it needs to perform calculations until reaching an operator which has lower precedence than the one which called `\operand:w`. This means that `\operand:w` must know what the previous binary operator is, or rather, its precedence: we thus rename it `\operand:Nw`. Let us describe as an example how we plan to do the calculation $41 - 2^3 * 4 + 5$. Here, we abuse notations: the first argument of `\operand:Nw` should be an integer constant (`\c__fp_prec_plus_int, ...`) equal to the precedence of the given operator, not directly the operator itself.

- Clean up 41 and find $-$. We call `\operand:Nw -` to find the second operand.
- Clean up 2 and find \wedge .
- Compare the precedences of $-$ and \wedge . Since the latter is higher, we need to compute the exponentiation. For this, find the second operand with a nested call to `\operand:Nw ^`.
- Clean up 3 and find $*$.
- Compare the precedences of \wedge and $*$. Since the former is higher, `\operand:Nw ^` has found the second operand of the exponentiation, which is computed: $2^3 = 8$.
- We now have $41+8*4+5$, and `\operand:Nw -` is still looking for a second operand for the subtraction. Is it 8?
- Compare the precedences of $-$ and $*$. Since the latter is higher, we are not done with 8. Call `\operand:Nw *` to find the second operand of the multiplication.
- Clean up 4, and find $-$.
- Compare the precedences of $*$ and $-$. Since the former is higher, `\operand:Nw *` has found the second operand of the multiplication, which is computed: $8*4 = 32$.
- We now have $41+32+5$, and `\operand:Nw -` is still looking for a second operand for the subtraction. Is it 32?
- Compare the precedences of $-$ and $+$. Since they are equal, `\operand:Nw -` has found the second operand for the subtraction, which is computed: $41 - 32 = 9$.
- We now have $9+5$.

The procedure above stops short of performing all computations, but adding a surrounding call to `\operand:Nw` with a very low precedence ensures that all computations are performed before `\operand:Nw` is done. Adding a trailing marker with the same very low precedence prevents the surrounding `\operand:Nw` from going beyond the marker.

The pattern above to find an operand for a given operator, is to find one number and the next operator, then compare precedences to know if the next computation should be done. If it should, then perform it after finding its second operand, and look at the next operator, then compare precedences to know if the next computation should be done. This continues until we find that the next computation should not be done. Then, we stop.

We are now ready to get a bit more technical and describe which of the `l3fp-parse` functions correspond to each step above.

First, `__fp_parse_operand:Nw` is the `\operand:Nw` function above, with small modifications due to expansion issues discussed later. We denote by $\langle precedence \rangle$ the argument of `__fp_parse_operand:Nw`, that is, the precedence of the binary operator whose operand we are trying to find. The basic action is to read numbers from the input stream. This is done by `__fp_parse_one:Nw`. A first approximation of this function is that it reads one $\langle number \rangle$, performing no computation, and finds the following binary $\langle operator \rangle$. Then it expands to

$$\langle number \rangle \\ __fp_parse_infix_ \langle operator \rangle :N \langle precedence \rangle$$

expanding the `infix` auxiliary before leaving the above in the input stream.

We now explain the `infix` auxiliaries. We need some flexibility in how we treat the case of equal precedences: most often, the first operation encountered should be performed, such as `1-2-3` being computed as `(1-2)-3`, but `2^3^4` should be evaluated as `2^(3^4)` instead. For this reason, and to support the equivalence between `**` and `^` more easily, each binary operator is converted to a control sequence `__fp_parse_infix_⟨operator⟩:N` when it is encountered for the first time. Instead of passing both precedences to a test function to do the comparison steps above, we pass the `⟨precedence⟩` (of the earlier operator) to the `infix` auxiliary for the following `⟨operator⟩`, to know whether to perform the computation of the `⟨operator⟩`. If it should not be performed, the `infix` auxiliary expands to

```
@ \use_none:n \__fp_parse_infix_⟨operator⟩:N
```

and otherwise it calls `__fp_parse_operand:Nw` with the precedence of the `⟨operator⟩` to find its second operand `⟨number₂⟩` and the next `⟨operator₂⟩`, and expands to

```
@ \__fp_parse_apply_binary:NwNwN
  ⟨operator⟩ ⟨number₂⟩
@ \__fp_parse_infix_⟨operator₂⟩:N
```

The `infix` function is responsible for comparing precedences, but cannot directly call the computation functions, because the first operand `⟨number⟩` is before the `infix` function in the input stream. This is why we stop the expansion here and give control to another function to close the loop.

A definition of `__fp_parse_operand:Nw ⟨precedence⟩` with some of the expansion control removed is

```
\exp_after:wN \__fp_parse_continue:NwN
\exp_after:wN ⟨precedence⟩
\exp:w \exp_end_continue_f:w
  \__fp_parse_one:Nw ⟨precedence⟩
```

This expands `__fp_parse_one:Nw ⟨precedence⟩` completely, which finds a number, wraps the next `⟨operator⟩` into an `infix` function, feeds this function the `⟨precedence⟩`, and expands it, yielding either

```
\__fp_parse_continue:NwN ⟨precedence⟩
⟨number⟩ @
\use_none:n \__fp_parse_infix_⟨operator⟩:N
```

or

```
\__fp_parse_continue:NwN ⟨precedence⟩
⟨number⟩ @
\__fp_parse_apply_binary:NwNwN
  ⟨operator⟩ ⟨number₂⟩
@ \__fp_parse_infix_⟨operator₂⟩:N
```

The definition of `__fp_parse_continue:NwN` is then very simple:

```
\cs_new:Npn \__fp_parse_continue:NwN #1#2@#3 { #3 #1 #2 @ }
```

In the first case, `#3` is `\use_none:n`, yielding

then $\langle number \rangle @ _ _ \text{fp_parse_infix_} \langle operator \rangle : N$. In the second case, #3 is $_ _ \text{fp_parse_apply_binary} : NwNwN$, whose role is to compute $\langle number \rangle \langle operator \rangle \langle number_2 \rangle$ and to prepare for the next comparison of precedences: first we get

then

where `_fp_operator_o:ww` computes $\langle number \rangle \langle operator \rangle \langle number_2 \rangle$ and expands after the result, thus triggers the comparison of the precedence of the $\langle operator_2 \rangle$ and the $\langle precedence \rangle$, continuing the loop.

24.1.3 Prefix operators, parentheses, and functions

Prefix operators (unary `-`, `+`, `!`) and parentheses are taken care of by the same mechanism, and functions (`sin`, `exp`, etc.) as well. Finding the argument of the unary `-`, for instance, is very similar to grabbing the second operand of a binary infix operator, with a subtle precedence explained below. Once that operand is found, the operator can be applied to it (for the unary `-`, this simply flips the sign). A left parenthesis is just a prefix operator with a very low precedence equal to that of the closing parenthesis (which is treated as an infix operator, since it normally appears just after numbers), so that all computations are performed until the closing parenthesis. The prefix operator associated to the left parenthesis does not alter its argument, but it removes the closing parenthesis (with some checks).

Prefix operators are the reason why we only summarily described the function `_fp_parse_one:Nw` earlier. This function is responsible for reading in the input stream the first possible *number* and the next infix *operator*. If what follows `_fp_parse_one:Nw` *precedence* is a prefix operator, then we must find the operand of this prefix operator through a nested call to `_fp_parse_operand:Nw` with the appropriate precedence, then apply the operator to the operand found to yield the result of `_fp_parse_one:Nw`. So far, all is simple.

The unary operators `+`, `-`, `!` complicate things a little bit: `-3**2` should be $-(3^2) = -9$, and not $(-3)^2 = 9$. This would easily be done by giving `-` a lower precedence, equal to that of the infix `+` and `-`. Unfortunately, this fails in cases such as `3**-2*4`, yielding $3^{-2 \times 4}$ instead of the correct $3^{-2} \times 4$. A second attempt would be to call `_fp_parse_operand:Nw` with the *precedence* of the previous operator, but `0>-2+3` is then parsed as `0>-(2+3)`: the addition is performed because it binds more tightly than the comparison which precedes `-`. The correct approach is for a unary `-` to perform

operations whose precedence is greater than both that of the previous operation, and that of the unary `-` itself. The unary `-` is given a precedence higher than multiplication and division. This does not lead to any surprising result, since $-(x/y) = (-x)/y$ and similarly for multiplication, and it reduces the number of nested calls to `__fp_parse_operand:Nw`.

Functions are implemented as prefix operators with very high precedence, so that their argument is the first number that can possibly be built.

Note that contrarily to the `infix` functions discussed earlier, the `prefix` functions do perform tests on the previous *precedence* to decide whether to find an argument or not, since we know that we need a number, and must never stop there.

24.1.4 Numbers and reading tokens one by one

So far, we have glossed over one important point: what is a “number”? A number is typically given in the form $\langle\textit{significand}\rangle\mathbf{e}\langle\textit{exponent}\rangle$, where the $\langle\textit{significand}\rangle$ is any non-empty string composed of decimal digits and at most one decimal separator (a period), the exponent “ $\mathbf{e}\langle\textit{exponent}\rangle$ ” is optional and is composed of an exponent mark `e` followed by a possibly empty string of signs `+` or `-` and a non-empty string of decimal digits. The $\langle\textit{significand}\rangle$ can also be an integer, dimension, skip, or muskip variable, in which case dimensions are converted from points (or mu units) to floating points, and the $\langle\textit{exponent}\rangle$ can also be an integer variable. Numbers can also be given as floating point variables, or as named constants such as `nan`, `inf` or `pi`. We may add more types in the future.

When `__fp_parse_one:Nw` is looking for a “number”, here is what happens.

- If the next token is a control sequence with the meaning of `\scan_stop:`, it can be: `\s__fp`, in which case our job is done, as what follows is an internal floating point number, or `\s__fp_mark`, in which case the expression has come to an early end, as we are still looking for a number here, or something else, in which case we consider the control sequence to be a bad variable resulting from c-expansion.
- If the next token is a control sequence with a different meaning, we assume that it is a register, unpack it with `\tex_the:D`, and use its value (in `pt` for dimensions and skips, `mu` for muskips) as the $\langle\textit{significand}\rangle$ of a number: we look for an exponent.
- If the next token is a digit, we remove any leading zeros, then read a significand larger than 1 if the next character is a digit, read a significand smaller than 1 if the next character is a period, or we have found a significand equal to 0 otherwise, and look for an exponent.
- If the next token is a letter, we collect more letters until the first non-letter: the resulting word may denote a function such as `asin`, a constant such as `pi` or be unknown. In the first case, we call `__fp_parse_operand:Nw` to find the argument of the function, then apply the function, before declaring that we are done. Otherwise, we are done, either with the value of the constant, or with the value `nan` for unknown words.
- If the next token is anything else, we check whether it is a known prefix operator, in which case `__fp_parse_operand:Nw` finds its operand. If it is not known, then either a number is missing (if the token is a known infix operator) or the token is simply invalid in floating point expressions.

Once a number is found, `__fp_parse_one:Nw` also finds an infix operator. This goes as follows.

- If the next token is a control sequence, it could be the special marker `\s__fp_-mark`, and otherwise it is a case of juxtaposing numbers, such as `2\c_zero`, with an implied multiplication.
- If the next token is a letter, it is also a case of juxtaposition, as letters cannot be proper infix operators.
- Otherwise (including in the case of digits), if the token is a known infix operator, the appropriate `__fp_infix_⟨operator⟩:N` function is built, and if it does not exist, we complain. In particular, the juxtaposition `\c_zero 2` is disallowed.

In the above, we need to test whether a character token `#1` is a digit:

```
\if_int_compare:w 9 < 1 \token_to_str:N #1 \exp_stop_f:
  is a digit
\else:
  not a digit
\fi:
```

To exclude 0, replace 9 by 10. The use of `\token_to_str:N` ensures that a digit with any catcode is detected. To test if a character token is a letter, we need to work with its character code, testing if ‘`#1`’ lies in [65, 90] (uppercase letters) or [97, 112] (lowercase letters)

```
\if_int_compare:w \__int_eval:w
  ( ‘#1 \if_int_compare:w ‘#1 > ‘Z - 32 \fi: ) / 26 = 3 \exp_stop_f:
  is a letter
\else:
  not a letter
\fi:
```

At all steps, we try to accept all category codes: when `#1` is kept to be used later, it is almost always converted to category code other through `\token_to_str:N`. More precisely, catcodes {3, 6, 7, 8, 11, 12} should work without trouble, but not {1, 2, 4, 10, 13}, and of course {0, 5, 9} cannot become tokens.

Floating point expressions should behave as much as possible like ε -TeX-based integer expressions and dimension expressions. In particular, `f`-expansion should be performed as the expression is read, token by token, forcing the expansion of protected macros, and ignoring spaces. One advantage of expanding at every step is that restricted expandable functions can then be used in floating point expressions just as they can be in other kinds of expressions. Problematically, spaces stop `f`-expansion: for instance, the macro `\X` below would not be expanded if we simply performed `f`-expansion.

```
\DeclareDocumentCommand {\test} {m} { \fp_eval:n {#1} }
\ExplSyntaxOff
\test { 1 + \X }
```

Of course, spaces typically do not appear in a code setting, but may very easily come in document-level input, from which some expressions may come. To avoid this problem, at every step, we do essentially what `\use:f` would do: take an argument, put it back in the input stream, then `f`-expand it. This is not a complete solution, since a macro’s expansion could contain leading spaces which would stop the `f`-expansion before further macro calls are performed. However, in practice it should be enough: in particular, floating point numbers are correctly expanded to the underlying `\s__fp ...` structure. The `f`-expansion is performed by `__fp_parse_expand:w`.

24.2 Main auxiliary functions

`_fp_parse_operand:Nw` `\exp:w _fp_parse_operand:Nw <precedence> _fp_parse_expand:w`
 Reads the "...", performing every computation with a precedence higher than `<precedence>`, then expands to

`<result> @ _fp_parse_infix_<operation>:N ...`

where the `<operation>` is the first operation with a lower precedence, possibly `end`, and the "..." start just after the `<operation>`.

(End definition for `_fp_parse_operand:Nw`.)

`_fp_parse_infix_+:N` `_fp_parse_infix_+:N <precedence> ...`
 If `+` has a precedence higher than the `<precedence>`, cleans up a second `<operand>` and finds the `<operation2 which follows, and expands to`

`@ _fp_parse_apply_binary:NwNwN + <operand> @ _fp_parse_infix_<operation2
...`

Otherwise expands to

`@ \use_none:n _fp_parse_infix_+:N ...`

A similar function exists for each infix operator.

(End definition for `_fp_parse_infix_+:N`.)

`_fp_parse_one:Nw` `_fp_parse_one:Nw <precedence> ...`
 Cleans up one or two operands depending on how the precedence of the next operation compares to the `<precedence>`. If the following `<operation>` has a precedence higher than `<precedence>`, expands to

`<operand1> @ _fp_parse_apply_binary:NwNwN <operation> <operand2> @`
`_fp_parse_infix_<operation2`

and otherwise expands to

`<operand> @ \use_none:n _fp_parse_infix_<operation>:N ...`

(End definition for `_fp_parse_one:Nw`.)

24.3 Helpers

`_fp_parse_expand:w` `\exp:w _fp_parse_expand:w <tokens>`
 This function must always come within a `\exp:w` expansion. The `<tokens>` should be the part of the expression that we have not yet read. This requires in particular closing all conditionals properly before expanding.

12138 `\cs_new:Npn _fp_parse_expand:w #1 { \exp_end_continue_f:w #1 }`

(End definition for `_fp_parse_expand:w`.)

`_fp_parse_return_semicolon:w` This very odd function swaps its position with the following `\fi:` and removes `_fp_parse_expand:w` normally responsible for expansion. That turns out to be useful.

12139 `\cs_new:Npn _fp_parse_return_semicolon:w`
 12140 `#1 \fi: _fp_parse_expand:w { \fi: ; #1 }`

(End definition for _fp_parse_return_semicolon:w.)

```

\_fp_type_from_scan:N      \_fp_type_from_scan:N <token>
\_fp_type_from_scan:w      Grabs the pieces of the stringified <token> which lies after the first s\_fp. If the
                           <token> does not contain that string, the result is \_?.
12141 \cs_new:Npx \_fp_type_from_scan:N #1
12142   {
12143     \exp_not:N \exp_after:wN \exp_not:N \_fp_type_from_scan:w
12144     \exp_not:N \token_to_str:N #1 \exp_not:N \q_mark
12145     \tl_to_str:n { s\_fp _? } \exp_not:N \q_mark \exp_not:N \q_stop
12146   }
12147 \use:x
12148   {
12149     \cs_new:Npn \exp_not:N \_fp_type_from_scan:w
12150       ##1 \tl_to_str:n { s\_fp } ##2 \exp_not:N \q_mark ##3 \exp_not:N \q_stop
12151       {##2}
12152   }

```

(End definition for _fp_type_from_scan:N and _fp_type_from_scan:w.)

_fp_parse_digits_vii:N These functions must be called within an _int_value:w or _int_eval:w construction. The first token which follows must be f-expanded prior to calling those functions. The functions read tokens one by one, and output digits into the input stream, until meeting a non-digit, or up to a number of digits equal to their index. The full expansion is

_fp_parse_digits_vii:N <digits> ; <filling 0> ; <length>

_fp_parse_digits_vii:N where <filling 0> is a string of zeros such that <digits> <filling 0> has the length given by the index of the function, and <length> is the number of zeros in the <filling 0> string. Each function puts a digit into the input stream and calls the next function, until we find a non-digit. We are careful to pass the tested tokens through \token_to_str:N to normalize their category code.

```

12153 \cs_set_protected:Npn \_fp_tmp:w #1 #2 #3
12154   {
12155     \cs_new:cpn { \_fp_parse_digits_ #1 :N } ##1
12156     {
12157       \if_int_compare:w 9 < 1 \token_to_str:N ##1 \exp_stop_f:
12158       \token_to_str:N ##1 \exp_after:wN #2 \exp:w
12159       \else:
12160         \_fp_parse_return_semicolon:w #3 ##1
12161       \fi:
12162       \_fp_parse_expand:w
12163     }
12164   }
12165 \_fp_tmp:w {vii} \_fp_parse_digits_vi:N { 0000000 ; 7 }
12166 \_fp_tmp:w {vi} \_fp_parse_digits_v:N { 000000 ; 6 }
12167 \_fp_tmp:w {v} \_fp_parse_digits_iv:N { 00000 ; 5 }
12168 \_fp_tmp:w {iv} \_fp_parse_digits_iii:N { 0000 ; 4 }
12169 \_fp_tmp:w {iii} \_fp_parse_digits_ii:N { 000 ; 3 }
12170 \_fp_tmp:w {ii} \_fp_parse_digits_i:N { 00 ; 2 }
12171 \_fp_tmp:w {i} \_fp_parse_digits_:N { 0 ; 1 }
12172 \cs_new:Npn \_fp_parse_digits_:N { ; ; 0 }

```

(End definition for _fp_parse_digits_vii:N and others.)

24.4 Parsing one number

`__fp_parse_one:Nw` This function finds one number, and packs the symbol which follows in an `__fp_parse_infix_...` csname. #1 is the previous *precedence*, and #2 the first token of the operand. We distinguish four cases: #2 is equal to `\scan_stop:` in meaning, #2 is a different control sequence, #2 is a digit, and #2 is something else (this last case is split further later). Despite the earlier f-expansion, #2 may still be expandable if it was protected by `\exp_not:N`, as may happen with the L^AT_EX 2_ε command `\protect`. Using a well placed `\reverse_if:N`, this case is sent to `__fp_parse_one_fp:NN` which deals with it robustly.

```

12173 \cs_new:Npn \__fp_parse_one:Nw #1 #2
12174 {
12175   \if_catcode:w \scan_stop: \exp_not:N #2
12176   \exp_after:wN \if_meaning:w \exp_not:N #2 #2 \else:
12177     \exp_after:wN \reverse_if:N
12178   \fi:
12179   \if_meaning:w \scan_stop: #2
12180     \exp_after:wN \exp_after:wN
12181     \exp_after:wN \__fp_parse_one_fp:NN
12182   \else:
12183     \exp_after:wN \exp_after:wN
12184     \exp_after:wN \__fp_parse_one_register:NN
12185   \fi:
12186   \else:
12187     \if_int_compare:w 9 < 1 \token_to_str:N #2 \exp_stop_f:
12188       \exp_after:wN \exp_after:wN
12189       \exp_after:wN \__fp_parse_one_digit:NN
12190     \else:
12191       \exp_after:wN \exp_after:wN
12192       \exp_after:wN \__fp_parse_one_other:NN
12193     \fi:
12194   \fi:
12195   #1 #2
12196 }
```

(End definition for `__fp_parse_one:Nw`.)

`__fp_parse_one_fp:NN` This function receives a *precedence* and a control sequence equal to `\scan_stop:` in meaning. There are three cases, dispatched using `__fp_type_from_scan:N`.

- `\s__fp` starts a floating point number, and we call `__fp_exp_after_f:nw`, which f-expands after the floating point.
- `\s__fp_mark` is a premature end, we call `__fp_exp_after_mark_f:nw`, which triggers an fp-early-end error.
- For a control sequence not containing `\s__fp`, we call `__fp_exp_after_?_f:nw`, causing a bad-variable error.

This scheme is extensible: additional types can be added by starting the variables with a scan mark of the form `\s__fp_⟨type⟩` and defining `__fp_exp_after_⟨type⟩_f:nw`. In all cases, we make sure that the second argument of `__fp_parse_infix:NN` is correctly expanded. A special case only enabled in L^AT_EX 2_ε is that if `\protect` is encountered then

the error message mentions the control sequence which follows it rather than `\protect` itself. The test for L^AT_EX 2_ε uses `\@unexpandable@protect` rather than `\protect` because `\protect` is often `\scan_stop`: hence “does not exist”.

```

12197 \cs_new:Npn \__fp_parse_one_fp:NN #1#2
12198 {
12199   \cs:w __fp_exp_after \__fp_type_from_scan:N #2 _f:nw \cs_end:
12200   {
12201     \exp_after:wN \__fp_parse_infix:NN
12202     \exp_after:wN #1 \exp:w \__fp_parse_expand:w
12203   }
12204   #2
12205 }
12206 \cs_new:Npn \__fp_exp_after_mark_f:nw #1
12207 {
12208   \__msg_kernel_expandable_error:nn { kernel } { fp-early-end }
12209   \exp_after:wN \c_nan_fp \exp:w \exp_end_continue_f:w #1
12210 }
12211 \cs_new:cpn { __fp_exp_after_?_f:nw } #1#2
12212 {
12213   \__msg_kernel_expandable_error:nnn { kernel } { bad-variable } {#2}
12214   \exp_after:wN \c_nan_fp \exp:w \exp_end_continue_f:w #1
12215 }
12216 \*package
12217 \cs_set_protected:Npn \__fp_tmp:w #1
12218 {
12219   \cs_if_exist:NT #1
12220   {
12221     \cs_gset:cpn { __fp_exp_after_?_f:nw } ##1##2
12222     {
12223       \exp_after:wN \c_nan_fp \exp:w \exp_end_continue_f:w ##1
12224       \str_if_eq:nnTF {##2} { \protect }
12225       {
12226         \cs_if_eq:NNTF ##2 #1 { \use_i:nn } { \use:n }
12227         { \__msg_kernel_expandable_error:nnn { kernel } { fp-robust-cmd } }
12228       }
12229       { \__msg_kernel_expandable_error:nnn { kernel } { bad-variable } {##2} }
12230     }
12231   }
12232 }
12233 \exp_args:Nc \__fp_tmp:w { \@unexpandable@protect }
12234 \*package

```

(End definition for `__fp_parse_one_fp:NN`, `__fp_exp_after_mark_f:nw`, and `__fp_exp_after_?_f:nw`.)

`__fp_parse_one_register:NN` This is called whenever #2 is a control sequence other than `\scan_stop`: in meaning. We special-case `\wd`, `\ht`, `\dp` (see later) and otherwise assume that it is a register, but carefully unpack it with `\tex_the:D` within braces. First, we find the exponent following #2. Then we unpack #2 with `\tex_the:D`, and the `auxii` auxiliary distinguishes integer registers from dimensions/skips from muskips, according to the presence of a period and/or of `pt`. For integers, simply convert $\langle value \rangle e \langle exponent \rangle$ to a floating point number with `__fp_parse:n` (this is somewhat wasteful). For other registers, the decimal rounding provided by T_EX does not accurately represent the binary value that it manipulates, so

we extract this binary value as a number of scaled points with `__int_value:w __dim_eval:w <decimal value> pt`, and use an auxiliary of `\dim_to_fp:n`, which performs the multiplication by 2^{-16} , correctly rounded.

```

12235 \cs_new:Npn \__fp_parse_one_register:NN #1#2
12236 {
12237   \exp_after:wN \__fp_parse_infix_after_operand:NwN
12238   \exp_after:wN #1
12239   \exp:w \exp_end_continue_f:w
12240   \if_meaning:w \box_wd:N #2 \__fp_parse_one_register_wd:w \fi:
12241   \if_meaning:w \box_ht:N #2 \__fp_parse_one_register_wd:w \fi:
12242   \if_meaning:w \box_dp:N #2 \__fp_parse_one_register_wd:w \fi:
12243   \exp_after:wN \__fp_parse_one_register_aux:Nw
12244   \exp_after:wN #2
12245   \__int_value:w
12246   \exp_after:wN \__fp_parse_exponent:N
12247   \exp:w \__fp_parse_expand:w
12248 }
12249 \cs_new:Npx \__fp_parse_one_register_aux:Nw #1
12250 {
12251   \exp_not:n
12252   {
12253     \exp_after:wN \use:nn
12254     \exp_after:wN \__fp_parse_one_register_auxii:wwwNw
12255   }
12256   \exp_not:N \exp_after:wN { \exp_not:N \tex_the:D #1 }
12257   ; \exp_not:N \__fp_parse_one_register_dim:ww
12258   \tl_to_str:n { pt } ; \exp_not:N \__fp_parse_one_register_mu:www
12259   . \tl_to_str:n { pt } ; \exp_not:N \__fp_parse_one_register_int:www
12260   \exp_not:N \q_stop
12261 }
12262 \exp_args:Nno \use:nn
12263 { \cs_new:Npn \__fp_parse_one_register_auxii:wwwNw #1 . #2 }
12264 { \tl_to_str:n { pt } #3 ; #4#5 \q_stop }
12265 { #4 #1.#2; }
12266 \exp_args:Nno \use:nn
12267 { \cs_new:Npn \__fp_parse_one_register_mu:www #1 }
12268 { \tl_to_str:n { mu } ; #2 ; }
12269 { \__fp_parse_one_register_dim:ww #1 ; }
12270 \cs_new:Npn \__fp_parse_one_register_int:www #1; #2.; #3;
12271 { \__fp_parse:n { #1 e #3 } }
12272 \cs_new:Npn \__fp_parse_one_register_dim:ww #1; #2;
12273 {
12274   \exp_after:wN \__fp_from_dim_test:ww
12275   \__int_value:w #2 \exp_after:wN ,
12276   \__int_value:w \__dim_eval:w #1 pt ;
12277 }

```

The `\wd`, `\dp`, `\ht` primitives expect an integer argument. We abuse the exponent parser to find the integer argument: simply include the exponent marker `e`. Once that “exponent” is found, use `\tex_the:D` to find the box dimension and then copy what we did for dimensions.

```

12278 \cs_new:Npn \__fp_parse_one_register_wd:w
12279   #1#2 \exp_after:wN #3#4 \__fp_parse_expand:w
12280 {

```

```

12281     #1
12282     \exp_after:wN \__fp_parse_one_register_wd:Nw
12283     #4 \__fp_parse_expand:w e
12284   }
12285   \cs_new:Npn \__fp_parse_one_register_wd:Nw #1#2 ;
12286   {
12287     \exp_after:wN \__fp_from_dim_test:ww
12288     \exp_after:wN 0 \exp_after:wN ,
12289     \__int_value:w \__dim_eval:w
12290     \exp_after:wN \use:n \exp_after:wN { \tex_the:D #1 #2 } ;
12291   }

```

(End definition for __fp_parse_one_register:NN and others.)

__fp_parse_one_digit:NN A digit marks the beginning of an explicit floating point number. Once the number is found, we catch the case of overflow and underflow with __fp_sanitize:wN, then __fp_parse_infix_after_operand:NwN expands __fp_parse_infix:NN after the number we find, to wrap the following infix operator as required. Finding the number itself begins by removing leading zeros: further steps are described later.

```

12292   \cs_new:Npn \__fp_parse_one_digit:NN #1
12293   {
12294     \exp_after:wN \__fp_parse_infix_after_operand:NwN
12295     \exp_after:wN #1
12296     \exp:w \exp_end_continue_f:w
12297     \exp_after:wN \__fp_sanitize:wN
12298     \__int_value:w \__int_eval:w 0 \__fp_parse_trim_zeros:N
12299   }

```

(End definition for __fp_parse_one_digit:NN.)

__fp_parse_one_other:NN For this function, #2 is a character token which is not a digit. If it is an ASCII letter, __fp_parse_letters:N beyond this one and give the result to __fp_parse_word:Nw. Otherwise, the character is assumed to be a prefix operator, and we build __fp_parse_prefix_{operator}:Nw.

```

12300   \cs_new:Npn \__fp_parse_one_other:NN #1 #2
12301   {
12302     \if_int_compare:w
12303       \__int_eval:w
12304       ( '#2 \if_int_compare:w '#2 > 'Z - 32 \fi: ) / 26
12305       = 3 \exp_stop_f:
12306     \exp_after:wN \__fp_parse_word:Nw
12307     \exp_after:wN #1
12308     \exp_after:wN #2
12309     \exp:w \exp_after:wN \__fp_parse_letters:N
12310     \exp:w
12311   \else:
12312     \exp_after:wN \__fp_parse_prefix:NNN
12313     \exp_after:wN #1
12314     \exp_after:wN #2
12315     \cs:w
12316       __fp_parse_prefix_ \token_to_str:N #2 :Nw
12317     \exp_after:wN
12318     \cs_end:
12319     \exp:w

```

```

12320     \fi:
12321     \__fp_parse_expand:w
12322 }

```

(End definition for __fp_parse_one_other:NN.)

```

\__fp_parse_word:Nw
\__fp_parse_letters:N

```

Finding letters is a simple recursion. Once __fp_parse_letters:N has done its job, we try to build a control sequence from the word #2. If it is a known word, then the corresponding action is taken, and otherwise, we complain about an unknown word, yield \c_nan_fp, and look for the following infix operator. Note that the unknown word could be a mistyped function as well as a mistyped constant, so there is no way to tell whether to look for arguments; we do not. The standard requires “inf” and “infinity” and “nan” to be recognized regardless of case, but we probably don’t want to allow every l3fp word to have an arbitrary mixture of lower and upper case, so we test and use a differently-named control sequence.

```

12323 \cs_new:Npn \__fp_parse_word:Nw #1#2;
12324 {
12325     \cs_if_exist_use:cF { __fp_parse_word_#2:N }
12326     {
12327         \cs_if_exist_use:cF { __fp_parse_caseless_ \str_fold_case:n {#2} :N }
12328         {
12329             \_msg_kernel_expandable_error:nnn
12330             { kernel } { unknown-fp-word } {#2}
12331             \exp_after:wN \c_nan_fp \exp:w \exp_end_continue_f:w
12332             \__fp_parse_infix:NN
12333         }
12334     }
12335     #1
12336 }
12337 \cs_new:Npn \__fp_parse_letters:N #1
12338 {
12339     \exp_end_continue_f:w
12340     \if_int_compare:w
12341         \if_catcode:w \scan_stop: \exp_not:N #1
12342         0
12343     \else:
12344         \__int_eval:w
12345         ( ‘#1 \if_int_compare:w ‘#1 > ‘Z - 32 \fi: ) / 26
12346     \fi:
12347     = 3 \exp_stop_f:
12348     \exp_after:wN #1
12349     \exp:w \exp_after:wN \__fp_parse_letters:N
12350     \exp:w
12351 \else:
12352     \__fp_parse_return_semicolon:w #1
12353 \fi:
12354 \__fp_parse_expand:w
12355 }

```

(End definition for __fp_parse_word:Nw and __fp_parse_letters:N.)

```

\__fp_parse_prefix:NNN
\__fp_parse_prefix_unknown:NNN

```

For this function, #1 is the previous *precedence*, #2 is the operator just seen, and #3 is a control sequence which implements the operator if it is a known operator. If this control sequence is \scan_stop:, then the operator is in fact unknown. Either the expression is

missing a number there (if the operator is valid as an infix operator), and we put `nan`, wrapping the infix operator in a `cname` as appropriate, or the character is simply invalid in floating point expressions, and we continue looking for a number, starting again from `__fp_parse_one:Nw`.

```

12356 \cs_new:Npn \__fp_parse_prefix:NNN #1#2#3
12357 {
12358   \if_meaning:w \scan_stop: #3
12359   \exp_after:wN \__fp_parse_prefix_unknown:NNN
12360   \exp_after:wN #2
12361   \fi:
12362   #3 #1
12363 }
12364 \cs_new:Npn \__fp_parse_prefix_unknown:NNN #1#2#3
12365 {
12366   \cs_if_exist:cTF { __fp_parse_infix_ \token_to_str:N #1 :N }
12367   {
12368     \__msg_kernel_expandable_error:nnn
12369     { kernel } { fp-missing-number } {#1}
12370     \exp_after:wN \c_nan_fp \exp:w \exp_end_continue_f:w
12371     \__fp_parse_infix:NN #3 #1
12372   }
12373   {
12374     \__msg_kernel_expandable_error:nnn
12375     { kernel } { fp-unknown-symbol } {#1}
12376     \__fp_parse_one:Nw #3
12377   }
12378 }

```

(End definition for `__fp_parse_prefix:NNN` and `__fp_parse_prefix_unknown:NNN`.)

24.4.1 Numbers: trimming leading zeros

Numbers are parsed as follows: first we trim leading zeros, then if the next character is a digit, start reading a significand ≥ 1 with the set of functions `__fp_parse_large...`; if it is a period, the significand is < 1 ; and otherwise it is zero. In the second case, trim additional zeros after the period, counting them for an exponent shift $\langle exp_1 \rangle < 0$, then read the significand with the set of functions `__fp_parse_small...`. Once the significand is read, read the exponent if `e` is present.

```

\__fp_parse_trim_zeros:N
\__fp_parse_trim_end:w

```

This function expects an already expanded token. It removes any leading zero, then distinguishes three cases: if the first non-zero token is a digit, then call `__fp_parse_large:N` (the significand is ≥ 1); if it is `.`, then continue trimming zeros with `__fp_parse_strim_zeros:N`; otherwise, our number is exactly zero, and we call `__fp_parse_zero:` to take care of that case.

```

12379 \cs_new:Npn \__fp_parse_trim_zeros:N #1
12380 {
12381   \if:w 0 \exp_not:N #1
12382   \exp_after:wN \__fp_parse_trim_zeros:N
12383   \exp:w
12384   \else:
12385   \if:w . \exp_not:N #1
12386   \exp_after:wN \__fp_parse_strim_zeros:N
12387   \exp:w

```

```

12388         \else:
12389             \__fp_parse_trim_end:w #1
12390         \fi:
12391     \fi:
12392     \__fp_parse_expand:w
12393 }
12394 \cs_new:Npn \__fp_parse_trim_end:w #1 \fi: \fi: \__fp_parse_expand:w
12395 {
12396     \fi:
12397     \fi:
12398     \if_int_compare:w 9 < 1 \token_to_str:N #1 \exp_stop_f:
12399         \exp_after:wN \__fp_parse_large:N
12400     \else:
12401         \exp_after:wN \__fp_parse_zero:
12402     \fi:
12403     #1
12404 }

```

(End definition for __fp_parse_trim_zeros:N and __fp_parse_trim_end:w.)

__fp_parse_strim_zeros:N If we have removed all digits until a period (or if the body started with a period), then enter the “small_trim” loop which outputs −1 for each removed 0. Those −1 are added to an integer expression waiting for the exponent. If the first non-zero token is a digit, call __fp_parse_small:N (our significand is smaller than 1), and otherwise, the number is an exact zero. The name `strim` stands for “small trim”.

```

12405 \cs_new:Npn \__fp_parse_strim_zeros:N #1
12406 {
12407     \if:w 0 \exp_not:N #1
12408         - 1
12409         \exp_after:wN \__fp_parse_strim_zeros:N \exp:w
12410     \else:
12411         \__fp_parse_strim_end:w #1
12412     \fi:
12413     \__fp_parse_expand:w
12414 }
12415 \cs_new:Npn \__fp_parse_strim_end:w #1 \fi: \__fp_parse_expand:w
12416 {
12417     \fi:
12418     \if_int_compare:w 9 < 1 \token_to_str:N #1 \exp_stop_f:
12419         \exp_after:wN \__fp_parse_small:N
12420     \else:
12421         \exp_after:wN \__fp_parse_zero:
12422     \fi:
12423     #1
12424 }

```

(End definition for __fp_parse_strim_zeros:N and __fp_parse_strim_end:w.)

__fp_parse_zero: After reading a significand of 0, find any exponent, then put a sign of 1 for __fp-sanitize:wN, which removes everything and leaves an exact zero.

```

12425 \cs_new:Npn \__fp_parse_zero:
12426 {
12427     \exp_after:wN ; \exp_after:wN 1
12428     \__int_value:w \__fp_parse_exponent:N
12429 }

```

(End definition for `_fp_parse_zero:.`)

24.4.2 Number: small significand

`_fp_parse_small:N` This function is called after we have passed the decimal separator and removed all leading zeros from the significand. It is followed by a non-zero digit (with any catcode). The goal is to read up to 16 digits. But we can't do that all at once, because `_int_value:w` (which allows us to collect digits and continue expanding) can only go up to 9 digits. Hence we grab digits in two steps of 8 digits. Since `#1` is a digit, read seven more digits using `_fp_parse_digits_vii:N`. The `small_leading` auxiliary leaves those digits in the `_int_value:w`, and grabs some more, or stops if there are no more digits. Then the `pack_leading` auxiliary puts the various parts in the appropriate order for the processing further up.

```

12430 \cs_new:Npn \_fp_parse_small:N #1
12431 {
12432   \exp_after:wN \_fp_parse_pack_leading:NNNNNww
12433   \_int_value:w \_int_eval:w 1 \token_to_str:N #1
12434   \exp_after:wN \_fp_parse_small_leading:wwNN
12435   \_int_value:w 1
12436   \exp_after:wN \_fp_parse_digits_vii:N
12437   \exp:w \_fp_parse_expand:w
12438 }

```

(End definition for `_fp_parse_small:N`.)

`_fp_parse_small_leading:wwNN` `_fp_parse_small_leading:wwNN 1 <digits> ; <zeros> ; <number of zeros>`

We leave `<digits>` `<zeros>` in the input stream: the functions used to grab digits are such that this constitutes digits 1 through 8 of the significand. Then prepare to pack 8 more digits, with an exponent shift of zero (this shift is used in the case of a large significand). If `#4` is a digit, leave it behind for the packing function, and read 6 more digits to reach a total of 15 digits: further digits are involved in the rounding. Otherwise put 8 zeros in to complete the significand, then look for an exponent.

```

12439 \cs_new:Npn \_fp_parse_small_leading:wwNN 1 #1 ; #2; #3 #4
12440 {
12441   #1 #2
12442   \exp_after:wN \_fp_parse_pack_trailing:NNNNNNww
12443   \exp_after:wN 0
12444   \_int_value:w \_int_eval:w 1
12445   \if_int_compare:w 9 < 1 \token_to_str:N #4 \exp_stop_f:
12446     \token_to_str:N #4
12447     \exp_after:wN \_fp_parse_small_trailing:wwNN
12448     \_int_value:w 1
12449     \exp_after:wN \_fp_parse_digits_vi:N
12450     \exp:w
12451   \else:
12452     0000 0000 \_fp_parse_exponent:Nw #4
12453   \fi:
12454   \_fp_parse_expand:w
12455 }

```

(End definition for `_fp_parse_small_leading:wwNN`.)


```

\__fp_parse_small_trailing:wwNN      \__fp_parse_small_trailing:wwNN 1 <digits> ; <zeros> ; <number of zeros>
<next token>

```

Leave digits 10 to 15 (arguments #1 and #2) in the input stream. If the *<next token>* is a digit, it is the 16th digit, we keep it, then the `small_round` auxiliary considers this digit and all further digits to perform the rounding: the function expands to nothing, to +0 or to +1. Otherwise, there is no 16-th digit, so we put a 0, and look for an exponent.

```

12456 \cs_new:Npn \__fp_parse_small_trailing:wwNN 1 #1 ; #2; #3 #4
12457 {
12458   #1 #2
12459   \if_int_compare:w 9 < 1 \token_to_str:N #4 \exp_stop_f:
12460     \token_to_str:N #4
12461     \exp_after:wN \__fp_parse_small_round:NN
12462     \exp_after:wN #4
12463     \exp:w
12464   \else:
12465     0 \__fp_parse_exponent:Nw #4
12466   \fi:
12467   \__fp_parse_expand:w
12468 }

```

(End definition for `__fp_parse_small_trailing:wwNN`.)

```

\__fp_parse_pack_trailing:NNNNNNww
\__fp_parse_pack_leading:NNNNNNww
\__fp_parse_pack_carry:w

```

Those functions are expanded after all the digits are found, we took care of the rounding, as well as the exponent. The last argument is the exponent. The previous five arguments are 8 digits which we pack in groups of 4, and the argument before that is 1, except in the rare case where rounding lead to a carry, in which case the argument is 2. The `trailing` function has an exponent shift as its first argument, which we add to the exponent found in the `e...` syntax. If the trailing digits cause a carry, the integer expression for the leading digits is incremented (+1 in the code below). If the leading digits propagate this carry all the way up, the function `__fp_parse_pack_carry:w` increments the exponent, and changes the significand from 0000... to 1000...: this is simple because such a carry can only occur to give rise to a power of 10.

```

12469 \cs_new:Npn \__fp_parse_pack_trailing:NNNNNNww #1 #2 #3#4#5#6 #7; #8 ;
12470 {
12471   \if_meaning:w 2 #2 + 1 \fi:
12472   ; #8 + #1 ; {#3#4#5#6} {#7};
12473 }
12474 \cs_new:Npn \__fp_parse_pack_leading:NNNNNNww #1 #2#3#4#5 #6; #7;
12475 {
12476   + #7
12477   \if_meaning:w 2 #1 \__fp_parse_pack_carry:w \fi:
12478   ; 0 {#2#3#4#5} {#6}
12479 }
12480 \cs_new:Npn \__fp_parse_pack_carry:w \fi: ; 0 #1
12481 { \fi: + 1 ; 0 {1000} }

```

(End definition for `__fp_parse_pack_trailing:NNNNNNww`, `__fp_parse_pack_leading:NNNNNNww`, and `__fp_parse_pack_carry:w`.)

24.4.3 Number: large significand

Parsing a significand larger than 1 is a little bit more difficult than parsing small significands. We need to count the number of digits before the decimal separator, and add

that to the final exponent. We also need to test for the presence of a dot each time we run out of digits, and branch to the appropriate `parse_small` function in those cases.

`__fp_parse_large:N` This function is followed by the first non-zero digit of a “large” significand (≥ 1). It is called within an integer expression for the exponent. Grab up to 7 more digits, for a total of 8 digits.

```

12482 \cs_new:Npn \__fp_parse_large:N #1
12483 {
12484   \exp_after:wN \__fp_parse_large_leading:wwNN
12485   \__int_value:w 1 \token_to_str:N #1
12486   \exp_after:wN \__fp_parse_digits_vii:N
12487   \exp:w \__fp_parse_expand:w
12488 }

```

(End definition for `__fp_parse_large:N`.)

`__fp_parse_large_leading:wwNN` `__fp_parse_large_leading:wwNN 1 <digits> ; <zeros> ; <number of zeros>`
`<next token>`

We shift the exponent by the number of digits in #1, namely the target number, 8, minus the `<number of zeros>` (number of digits missing). Then prepare to pack the 8 first digits. If the `<next token>` is a digit, read up to 6 more digits (digits 10 to 15). If it is a period, try to grab the end of our 8 first digits, branching to the `small` functions since the number of digit does not affect the exponent anymore. Finally, if this is the end of the significand, insert the `<zeros>` to complete the 8 first digits, insert 8 more, and look for an exponent.

```

12489 \cs_new:Npn \__fp_parse_large_leading:wwNN 1 #1 ; #2; #3 #4
12490 {
12491   + \c__fp_half_prec_int - #3
12492   \exp_after:wN \__fp_parse_pack_leading:NNNNNww
12493   \__int_value:w \__int_eval:w 1 #1
12494   \if_int_compare:w 9 < 1 \token_to_str:N #4 \exp_stop_f:
12495     \exp_after:wN \__fp_parse_large_trailing:wwNN
12496     \__int_value:w 1 \token_to_str:N #4
12497     \exp_after:wN \__fp_parse_digits_vii:N
12498     \exp:w
12499   \else:
12500     \if:w . \exp_not:N #4
12501       \exp_after:wN \__fp_parse_small_leading:wwNN
12502       \__int_value:w 1
12503       \cs:w
12504         __fp_parse_digits_
12505         \__int_to_roman:w #3
12506         :N \exp_after:wN
12507         \cs_end:
12508         \exp:w
12509     \else:
12510       #2
12511       \exp_after:wN \__fp_parse_pack_trailing:NNNNNNww
12512       \exp_after:wN 0
12513       \__int_value:w 1 0000 0000
12514       \__fp_parse_exponent:Nw #4
12515     \fi:
12516   \fi:

```

```

12517     \__fp_parse_expand:w
12518 }

```

(End definition for __fp_parse_large_leading:wwNN.)

```

\__fp_parse_large_trailing:wwNN    \__fp_parse_large_trailing:wwNN 1 <digits> ; <zeros> ; <number of zeros>
                                   <next token>

```

We have just read 15 digits. If the *<next token>* is a digit, then the exponent shift caused by this block of 8 digits is 8, first argument to the `pack_trailing` function. We keep the *<digits>* and this 16-th digit, and find how this should be rounded using `__fp_parse_large_round:NN`. Otherwise, the exponent shift is the number of *<digits>*, 7 minus the *<number of zeros>*, and we test for a decimal point. This case happens in 123451234512345.67 with exactly 15 digits before the decimal separator. Then branch to the appropriate `small` auxiliary, grabbing a few more digits to complement the digits we already grabbed. Finally, if this is truly the end of the significand, look for an exponent after using the *<zeros>* and providing a 16-th digit of 0.

```

12519 \cs_new:Npn \__fp_parse_large_trailing:wwNN 1 #1 ; #2; #3 #4
12520 {
12521     \if_int_compare:w 9 < 1 \token_to_str:N #4 \exp_stop_f:
12522     \exp_after:wN \__fp_parse_pack_trailing:NNNNNNww
12523     \exp_after:wN \c__fp_half_prec_int
12524     \__int_value:w \__int_eval:w 1 #1 \token_to_str:N #4
12525     \exp_after:wN \__fp_parse_large_round:NN
12526     \exp_after:wN #4
12527     \exp:w
12528     \else:
12529     \exp_after:wN \__fp_parse_pack_trailing:NNNNNNww
12530     \__int_value:w \__int_eval:w 7 - #3 \exp_stop_f:
12531     \__int_value:w \__int_eval:w 1 #1
12532     \if:w . \exp_not:N #4
12533     \exp_after:wN \__fp_parse_small_trailing:wwNN
12534     \__int_value:w 1
12535     \cs:w
12536         __fp_parse_digits_
12537         \__int_to_roman:w #3
12538         :N \exp_after:wN
12539     \cs_end:
12540     \exp:w
12541     \else:
12542     #2 0 \__fp_parse_exponent:Nw #4
12543     \fi:
12544     \fi:
12545     \__fp_parse_expand:w
12546 }

```

(End definition for __fp_parse_large_trailing:wwNN.)

24.4.4 Number: beyond 16 digits, rounding

`__fp_parse_round_loop:N` This loop is called when rounding a number (whether the mantissa is small or large).
`__fp_parse_round_up:N` It should appear in an integer expression. This function reads digits one by one, until reaching a non-digit, and adds 1 to the integer expression for each digit. If all digits found are 0, the function ends the expression by ;0, otherwise by ;1. This is done by

switching the loop to `round_up` at the first non-zero digit, thus we avoid to test whether digits are 0 or not once we see a first non-zero digit.

```

12547 \cs_new:Npn \__fp_parse_round_loop:N #1
12548 {
12549   \if_int_compare:w 9 < 1 \token_to_str:N #1 \exp_stop_f:
12550     + 1
12551     \if:w 0 \token_to_str:N #1
12552       \exp_after:wN \__fp_parse_round_loop:N
12553       \exp:w
12554     \else:
12555       \exp_after:wN \__fp_parse_round_up:N
12556       \exp:w
12557     \fi:
12558   \else:
12559     \__fp_parse_return_semicolon:w 0 #1
12560   \fi:
12561   \__fp_parse_expand:w
12562 }
12563 \cs_new:Npn \__fp_parse_round_up:N #1
12564 {
12565   \if_int_compare:w 9 < 1 \token_to_str:N #1 \exp_stop_f:
12566     + 1
12567     \exp_after:wN \__fp_parse_round_up:N
12568     \exp:w
12569   \else:
12570     \__fp_parse_return_semicolon:w 1 #1
12571   \fi:
12572   \__fp_parse_expand:w
12573 }

```

(End definition for `__fp_parse_round_loop:N` and `__fp_parse_round_up:N`.)

`__fp_parse_round_after:wN` After the loop `__fp_parse_round_loop:N`, this function fetches an exponent with `__fp_parse_exponent:N`, and combines it with the number of digits counted by `__fp_parse_round_loop:N`. At the same time, the result 0 or 1 is added to the surrounding integer expression.

```

12574 \cs_new:Npn \__fp_parse_round_after:wN #1; #2
12575 {
12576   + #2 \exp_after:wN ;
12577   \__int_value:w \__int_eval:w #1 + \__fp_parse_exponent:N
12578 }

```

(End definition for `__fp_parse_round_after:wN`.)

`__fp_parse_small_round:NN` Here, `#1` is the digit that we are currently rounding (we only care whether it is even or odd). If `#2` is not a digit, then fetch an exponent and expand to `;\exponent` only. Otherwise, we expand to `+0` or `+1`, then `;\exponent`. To decide which, call `__fp_round_s:NNNw` to know whether to round up, giving it as arguments a sign 0 (all explicit numbers are positive), the digit `#1` to round, the first following digit `#2`, and either `+0` or `+1` depending on whether the following digits are all zero or not. This last argument is obtained by `__fp_parse_round_loop:N`, whose number of digits we discard by multiplying it by 0. The exponent which follows the number is also fetched by `__fp_parse_round_after:wN`.

```

12579 \cs_new:Npn \__fp_parse_small_round:NN #1#2
12580 {
12581   \if_int_compare:w 9 < 1 \token_to_str:N #2 \exp_stop_f:
12582     +
12583     \exp_after:wN \__fp_round_s:NNNw
12584     \exp_after:wN 0
12585     \exp_after:wN #1
12586     \exp_after:wN #2
12587     \__int_value:w \__int_eval:w
12588     \exp_after:wN \__fp_parse_round_after:wN
12589     \__int_value:w \__int_eval:w 0 * \__int_eval:w 0
12590     \exp_after:wN \__fp_parse_round_loop:N
12591     \exp:w
12592   \else:
12593     \__fp_parse_exponent:Nw #2
12594   \fi:
12595   \__fp_parse_expand:w
12596 }

```

(End definition for __fp_parse_small_round:NN and __fp_parse_round_after:wN.)

```

\__fp_parse_large_round:NN
  \__fp_parse_large_round_test:NN
  \__fp_parse_large_round_aux:wNN

```

Large numbers are harder to round, as there may be a period in the way. Again, #1 is the digit that we are currently rounding (we only care whether it is even or odd). If there are no more digits (#2 is not a digit), then we must test for a period: if there is one, then switch to the rounding function for small significands, otherwise fetch an exponent. If there are more digits (#2 is a digit), then round, checking with __fp_parse_round_loop:N if all further digits vanish, or some are non-zero. This loop is not enough, as it is stopped by a period. After the loop, the aux function tests for a period: if it is present, then we must continue looking for digits, this time discarding the number of digits we find.

```

12597 \cs_new:Npn \__fp_parse_large_round:NN #1#2
12598 {
12599   \if_int_compare:w 9 < 1 \token_to_str:N #2 \exp_stop_f:
12600     +
12601     \exp_after:wN \__fp_round_s:NNNw
12602     \exp_after:wN 0
12603     \exp_after:wN #1
12604     \exp_after:wN #2
12605     \__int_value:w \__int_eval:w
12606     \exp_after:wN \__fp_parse_large_round_aux:wNN
12607     \__int_value:w \__int_eval:w 1
12608     \exp_after:wN \__fp_parse_round_loop:N
12609   \else: %^A could be dot, or e, or other
12610     \exp_after:wN \__fp_parse_large_round_test:NN
12611     \exp_after:wN #1
12612     \exp_after:wN #2
12613   \fi:
12614 }
12615 \cs_new:Npn \__fp_parse_large_round_test:NN #1#2
12616 {
12617   \if:w . \exp_not:N #2
12618     \exp_after:wN \__fp_parse_small_round:NN
12619     \exp_after:wN #1
12620     \exp:w

```

```

12621 \else:
12622   \__fp_parse_exponent:Nw #2
12623 \fi:
12624 \__fp_parse_expand:w
12625 }
12626 \cs_new:Npn \__fp_parse_large_round_aux:wNN #1 ; #2 #3
12627 {
12628   + #2
12629   \exp_after:wN \__fp_parse_round_after:wN
12630   \__int_value:w \__int_eval:w #1
12631   \if:w . \exp_not:N #3
12632     + 0 * \__int_eval:w 0
12633     \exp_after:wN \__fp_parse_round_loop:N
12634     \exp:w \exp_after:wN \__fp_parse_expand:w
12635   \else:
12636     \exp_after:wN ;
12637     \exp_after:wN 0
12638     \exp_after:wN #3
12639   \fi:
12640 }

```

(End definition for `__fp_parse_large_round:NN`, `__fp_parse_large_round_test:NN`, and `__fp_parse_large_round_aux:wNN`.)

24.4.5 Number: finding the exponent

Expansion is a little bit tricky here, in part because we accept input where multiplication is implicit.

```

\__fp_parse:n { 3.2 erf(0.1) }
\__fp_parse:n { 3.2 e1_my_int }
\__fp_parse:n { 3.2 c_pi_fp }

```

The first case indicates that just looking one character ahead for an “e” is not enough, since we would mistake the function `erf` for an exponent of “`rf`”. An alternative would be to look two tokens ahead and check if what follows is a sign or a digit, considering in that case that we must be finding an exponent. But taking care of the second case requires that we unpack registers after `e`. However, blindly expanding the two tokens ahead completely would break the third example (unpacking is even worse). Indeed, in the course of reading `3.2`, `\c_pi_fp` is expanded to `\s__fp __fp_chk:w 1 0 {-1} {3141}` ... ; and `\s__fp` stops the expansion. Expanding two tokens ahead would then force the expansion of `__fp_chk:w` (despite it being protected), and that function tries to produce an error.

What can we do? Really, the reason why this last case breaks is that just as `TeX` does, we should read ahead as little as possible. Here, the only case where there may be an exponent is if the first token ahead is `e`. Then we expand (and possibly unpack) the second token.

`__fp_parse_exponent:Nw`

This auxiliary is convenient to smuggle some material through `\fi:` ending conditional processing. We place those `\fi:` (argument #2) at a very odd place because this allows us to insert `__int_eval:w` ... there if needed.

```

12641 \cs_new:Npn \__fp_parse_exponent:Nw #1 #2 \__fp_parse_expand:w
12642 {

```

```

12643 \exp_after:wN ;
12644 \__int_value:w #2 \__fp_parse_exponent:N #1
12645 }

```

(End definition for __fp_parse_exponent:Nw.)

__fp_parse_exponent:N
__fp_parse_exponent_aux:N

This function should be called within an __int_value:w expansion (or within an integer expression). It leaves digits of the exponent behind it in the input stream, and terminates the expansion with a semicolon. If there is no e, leave an exponent of 0. If there is an e, expand the next token to run some tests on it. The first rough test is that if the character code of #1 is greater than that of 9 (largest code valid for an exponent, less than any code valid for an identifier), there was in fact no exponent; otherwise, we search for the sign of the exponent.

```

12646 \cs_new:Npn \__fp_parse_exponent:N #1
12647 {
12648   \if:w e \exp_not:N #1
12649     \exp_after:wN \__fp_parse_exponent_aux:N
12650     \exp:w
12651   \else:
12652     0 \__fp_parse_return_semicolon:w #1
12653   \fi:
12654   \__fp_parse_expand:w
12655 }
12656 \cs_new:Npn \__fp_parse_exponent_aux:N #1
12657 {
12658   \if_int_compare:w \if_catcode:w \scan_stop: \exp_not:N #1
12659     0 \else: '#1 \fi: > '9 \exp_stop_f:
12660     0 \exp_after:wN ; \exp_after:wN e
12661   \else:
12662     \exp_after:wN \__fp_parse_exponent_sign:N
12663   \fi:
12664   #1
12665 }

```

(End definition for __fp_parse_exponent:N and __fp_parse_exponent_aux:N.)

__fp_parse_exponent_sign:N

Read signs one by one (if there is any).

```

12666 \cs_new:Npn \__fp_parse_exponent_sign:N #1
12667 {
12668   \if:w + \if:w - \exp_not:N #1 + \fi: \token_to_str:N #1
12669     \exp_after:wN \__fp_parse_exponent_sign:N
12670     \exp:w \exp_after:wN \__fp_parse_expand:w
12671   \else:
12672     \exp_after:wN \__fp_parse_exponent_body:N
12673     \exp_after:wN #1
12674   \fi:
12675 }

```

(End definition for __fp_parse_exponent_sign:N.)

__fp_parse_exponent_body:N

An exponent can be an explicit integer (most common case), or various other things (most of which are invalid).

```

12676 \cs_new:Npn \__fp_parse_exponent_body:N #1
12677 {

```

```

12678 \if_int_compare:w 9 < 1 \token_to_str:N #1 \exp_stop_f:
12679 \token_to_str:N #1
12680 \exp_after:wN \__fp_parse_exponent_digits:N
12681 \exp:w
12682 \else:
12683 \__fp_parse_exponent_keep:NTF #1
12684 { \__fp_parse_return_semicolon:w #1 }
12685 {
12686 \exp_after:wN ;
12687 \exp:w
12688 }
12689 \fi:
12690 \__fp_parse_expand:w
12691 }

```

(End definition for __fp_parse_exponent_body:N.)

__fp_parse_exponent_digits:N Read digits one by one, and leave them behind in the input stream. When finding a non-digit, stop, and insert a semicolon. Note that we do not check for overflow of the exponent, hence there can be a T_EX error. It is mostly harmless, except when parsing 0e9876543210, which should be a valid representation of 0, but is not.

```

12692 \cs_new:Npn \__fp_parse_exponent_digits:N #1
12693 {
12694 \if_int_compare:w 9 < 1 \token_to_str:N #1 \exp_stop_f:
12695 \token_to_str:N #1
12696 \exp_after:wN \__fp_parse_exponent_digits:N
12697 \exp:w
12698 \else:
12699 \__fp_parse_return_semicolon:w #1
12700 \fi:
12701 \__fp_parse_expand:w
12702 }

```

(End definition for __fp_parse_exponent_digits:N.)

__fp_parse_exponent_keep:NTF This is the last building block for parsing exponents. The argument #1 is already fully expanded, and neither + nor - nor a digit. It can be:

- \s__fp, marking the start of an internal floating point, invalid here;
- another control sequence equal to \relax, probably a bad variable;
- a register: in this case we make sure that it is an integer register, not a dimension;
- a character other than +, - or digits, again, an error.

```

12703 \prg_new_conditional:Npnn \__fp_parse_exponent_keep:N #1 { TF }
12704 {
12705 \if_catcode:w \scan_stop: \exp_not:N #1
12706 \if_meaning:w \scan_stop: #1
12707 \if_int_compare:w
12708 \__str_if_eq_x:nn { \s__fp } { \exp_not:N #1 }
12709 = 0 \exp_stop_f:
12710 0
12711 \__msg_kernel_expandable_error:nnn
12712 { kernel } { fp-after-e } { floating~point~ }

```



```

12713         \prg_return_true:
12714     \else:
12715         0
12716         \__msg_kernel_expandable_error:nnn
12717         { kernel } { bad-variable } {#1}
12718     \prg_return_false:
12719     \fi:
12720 \else:
12721     \if_int_compare:w
12722         \__str_if_eq_x:nn { \__int_value:w #1 } { \tex_the:D #1 }
12723         = 0 \exp_stop_f:
12724         \__int_value:w #1
12725     \else:
12726         0
12727         \__msg_kernel_expandable_error:nnn
12728         { kernel } { fp-after-e } { dimension~#1 }
12729     \fi:
12730     \prg_return_false:
12731     \fi:
12732 \else:
12733     0
12734     \__msg_kernel_expandable_error:nnn
12735     { kernel } { fp-missing } { exponent }
12736     \prg_return_true:
12737 \fi:
12738 }

```

(End definition for __fp_parse_exponent_keep:NTF.)

24.5 Constants, functions and prefix operators

24.5.1 Prefix operators

__fp_parse_prefix_+:Nw A unary + does nothing: we should continue looking for a number.

```

12739 \cs_new_eq:cN { \__fp_parse_prefix_+:Nw } \__fp_parse_one:Nw

```

(End definition for __fp_parse_prefix_+:Nw.)

__fp_parse_apply_unary:NNNwN Here, #1 is a precedence, #2 is some extra data used by some functions, #3 is *e.g.*, __fp_sin_o:w, and expands once after the calculation, #4 is the operand, and #5 is a __fp_parse_infix...:N function. We feed the data #2, and the argument #4, to the function #3, which expands \exp:w thus the infix function #5.

This is redefined in l3fp-extras.

```

12740 \cs_new:Npn \__fp_parse_apply_unary:NNNwN #1#2#3#4#5
12741 {
12742     #3 #2 #4 @
12743     \exp:w \exp_end_continue_f:w #5 #1
12744 }

```

(End definition for __fp_parse_apply_unary:NNNwN.)

__fp_parse_prefix_-:Nw The unary - and boolean not are harder: we parse the operand using a precedence equal to the maximum of the previous precedence ##1 and the precedence \c__fp_prec_not_int of the unary operator, then call the appropriate __fp_⟨operation⟩_o:w function, where the ⟨operation⟩ is set_sign or not.

```

12745 \cs_set_protected:Npn \__fp_tmp:w #1#2#3#4
12746 {
12747   \cs_new:cpn { \__fp_parse_prefix_ #1 :Nw } ##1
12748   {
12749     \exp_after:wN \__fp_parse_apply_unary:NNNwN
12750     \exp_after:wN ##1
12751     \exp_after:wN #4
12752     \exp_after:wN #3
12753     \exp:w
12754     \if_int_compare:w #2 < ##1
12755       \__fp_parse_operand:Nw ##1
12756     \else:
12757       \__fp_parse_operand:Nw #2
12758     \fi:
12759     \__fp_parse_expand:w
12760   }
12761 }
12762 \__fp_tmp:w - \c__fp_prec_not_int \__fp_set_sign_o:w 2
12763 \__fp_tmp:w ! \c__fp_prec_not_int \__fp_not_o:w ?

```

(End definition for __fp_parse_prefix_-:Nw and __fp_parse_prefix_!:Nw.)

__fp_parse_prefix_:Nw Numbers which start with a decimal separator (a period) end up here. Of course, we do not look for an operand, but for the rest of the number. This function is very similar to __fp_parse_one_digit:NN but calls __fp_parse_strim_zeros:N to trim zeros after the decimal point, rather than the trim_zeros function for zeros before the decimal point.

```

12764 \cs_new:cpn { \__fp_parse_prefix_:Nw } #1
12765 {
12766   \exp_after:wN \__fp_parse_infix_after_operand:NwN
12767   \exp_after:wN #1
12768   \exp:w \exp_end_continue_f:w
12769   \exp_after:wN \__fp_sanitize:wN
12770   \__int_value:w \__int_eval:w 0 \__fp_parse_strim_zeros:N
12771 }

```

(End definition for __fp_parse_prefix_:Nw.)

__fp_parse_prefix_(Nw __fp_parse_lparen_after:NwN The left parenthesis is treated as a unary prefix operator because it appears in exactly the same settings. Commas are allowed if the previous precedence is 16 (function with multiple arguments). In this case, find an operand using the precedence 1; otherwise the precedence 0. Once the operand is found, the lparen_after auxiliary makes sure that there was a closing parenthesis (otherwise it complains), and leaves in the input stream the array it found as an operand, fetching the following infix operator.

```

12772 \cs_new:cpn { \__fp_parse_prefix_(Nw } #1
12773 {
12774   \exp_after:wN \__fp_parse_lparen_after:NwN
12775   \exp_after:wN #1
12776   \exp:w
12777   \if_int_compare:w #1 = \c__fp_prec_funcii_int
12778     \__fp_parse_operand:Nw \c__fp_prec_comma_int
12779   \else:
12780     \__fp_parse_operand:Nw \c__fp_prec_paren_int
12781   \fi:

```

```

12782     \__fp_parse_expand:w
12783   }
12784 \cs_new:Npx \__fp_parse_lparen_after:NwN #1#2 @ #3
12785   {
12786     \exp_not:N \token_if_eq_meaning:NNTF #3
12787     \exp_not:c { \__fp_parse_infix_ } :N }
12788   {
12789     \exp_not:N \__fp_exp_after_array_f:w #2 \s__fp_stop
12790     \exp_not:N \exp_after:wN
12791     \exp_not:N \__fp_parse_infix:NN
12792     \exp_not:N \exp_after:wN #1
12793     \exp_not:N \exp:w
12794     \exp_not:N \__fp_parse_expand:w
12795   }
12796   {
12797     \exp_not:N \__msg_kernel_expandable_error:nnn
12798     { kernel } { fp-missing } { } }
12799   #2 @
12800   \exp_not:N \use_none:n #3
12801 }
12802 }

```

(End definition for __fp_parse_prefix_(:Nw and __fp_parse_lparen_after:NwN.)

__fp_parse_prefix_):Nw The right parenthesis can appear as unary prefixes when arguments of a multi-argument function end with a comma, or when there is no argument, as in `max(1,2,)` or in `rand()`. In single-argument functions (precedence 0 rather than 1) forbid this.

```

12803 \cs_new:cpn { \__fp_parse_prefix_):Nw } #1
12804   {
12805     \if_int_compare:w #1 = \c__fp_prec_comma_int
12806     \else:
12807       \__msg_kernel_expandable_error:nnn
12808       { kernel } { fp-missing-number } { } }
12809     \exp_after:wN \c_nan_fp \exp:w \exp_end_continue_f:w
12810   \fi:
12811   \__fp_parse_infix:NN #1 )
12812 }

```

(End definition for __fp_parse_prefix_):Nw.)

24.5.2 Constants

__fp_parse_word_inf:N Some words correspond to constant floating points. The floating point constant is left as a result of __fp_parse_one:Nw after expanding __fp_parse_infix:NN.

__fp_parse_word_nan:N

__fp_parse_word_pi:N

__fp_parse_word_deg:N

__fp_parse_word_true:N

__fp_parse_word_false:N

```

12813 \cs_set_protected:Npn \__fp_tmp:w #1 #2
12814   {
12815     \cs_new:cpn { \__fp_parse_word_#1:N }
12816     { \exp_after:wN #2 \exp:w \exp_end_continue_f:w \__fp_parse_infix:NN }
12817   }

```

```

12818 \__fp_tmp:w { inf } \c_inf_fp
12819 \__fp_tmp:w { nan } \c_nan_fp
12820 \__fp_tmp:w { pi } \c_pi_fp
12821 \__fp_tmp:w { deg } \c_one_degree_fp
12822 \__fp_tmp:w { true } \c_one_fp
12823 \__fp_tmp:w { false } \c_zero_fp

```

(End definition for `_fp_parse_word_inf:N` and others.)

`_fp_parse_caseless_inf:N` Copies of `_fp_parse_word_...:N` commands, to allow arbitrary case as mandated by the standard.

```

\fp_parse_caseless_infinity:N
\fp_parse_caseless_nan:N
12824 \cs_new_eq:NN \_fp_parse_caseless_inf:N \_fp_parse_word_inf:N
12825 \cs_new_eq:NN \_fp_parse_caseless_infinity:N \_fp_parse_word_inf:N
12826 \cs_new_eq:NN \_fp_parse_caseless_nan:N \_fp_parse_word_nan:N

```

(End definition for `_fp_parse_caseless_inf:N`, `_fp_parse_caseless_infinity:N`, and `_fp_parse_caseless_nan:N`.)

`_fp_parse_word_pt:N` Dimension units are also floating point constants but their value is not stored as a floating point constant. We give the values explicitly here.

```

\fp_parse_word_in:N
\fp_parse_word_pc:N
\fp_parse_word_cm:N
\fp_parse_word_mm:N
\fp_parse_word_dd:N
\fp_parse_word_cc:N
\fp_parse_word_nd:N
\fp_parse_word_nc:N
\fp_parse_word_bp:N
\fp_parse_word_sp:N
12827 \cs_set_protected:Npn \_fp_tmp:w #1 #2
12828 {
12829   \cs_new:cpn { \_fp_parse_word_#1:N }
12830   {
12831     \_fp_exp_after_f:nw { \_fp_parse_infix:NN }
12832     \s__fp \_fp_chk:w 10 #2 ;
12833   }
12834 }
12835 \_fp_tmp:w {pt} { {1} {1000} {0000} {0000} {0000} }
12836 \_fp_tmp:w {in} { {2} {7227} {0000} {0000} {0000} }
12837 \_fp_tmp:w {pc} { {2} {1200} {0000} {0000} {0000} }
12838 \_fp_tmp:w {cm} { {2} {2845} {2755} {9055} {1181} }
12839 \_fp_tmp:w {mm} { {1} {2845} {2755} {9055} {1181} }
12840 \_fp_tmp:w {dd} { {1} {1070} {0085} {6496} {0630} }
12841 \_fp_tmp:w {cc} { {2} {1284} {0102} {7795} {2756} }
12842 \_fp_tmp:w {nd} { {1} {1066} {9783} {4645} {6693} }
12843 \_fp_tmp:w {nc} { {2} {1280} {3740} {1574} {8031} }
12844 \_fp_tmp:w {bp} { {1} {1003} {7500} {0000} {0000} }
12845 \_fp_tmp:w {sp} { {-4} {1525} {8789} {0625} {0000} }

```

(End definition for `_fp_parse_word_pt:N` and others.)

`_fp_parse_word_em:N` The font-dependent units `em` and `ex` must be evaluated on the fly. We reuse an auxiliary of `\dim_to_fp:n`.

```

\fp_parse_word_ex:N
12846 \tl_map_inline:nn { {em} {ex} }
12847 {
12848   \cs_new:cpn { \_fp_parse_word_#1:N }
12849   {
12850     \exp_after:wN \_fp_from_dim_test:ww
12851     \exp_after:wN 0 \exp_after:wN ,
12852     \_int_value:w \_dim_eval:w 1 #1 \exp_after:wN ;
12853     \exp:w \exp_end_continue_f:w \_fp_parse_infix:NN
12854   }
12855 }

```

(End definition for `_fp_parse_word_em:N` and `_fp_parse_word_ex:N`.)

24.5.3 Functions

```

\__fp_parse_unary_function:NNN
\__fp_parse_function:NNN
12856 \cs_new:Npn \__fp_parse_unary_function:NNN #1#2#3
12857 {
12858   \exp_after:wN \__fp_parse_apply_unary:NNNwN
12859   \exp_after:wN #3
12860   \exp_after:wN #2
12861   \exp_after:wN #1
12862   \exp:w
12863   \__fp_parse_operand:Nw \c__fp_prec_func_int \__fp_parse_expand:w
12864 }
12865 \cs_new:Npn \__fp_parse_function:NNN #1#2#3
12866 {
12867   \exp_after:wN \__fp_parse_apply_unary:NNNwN
12868   \exp_after:wN #3
12869   \exp_after:wN #2
12870   \exp_after:wN #1
12871   \exp:w
12872   \__fp_parse_operand:Nw \c__fp_prec_funcii_int \__fp_parse_expand:w
12873 }

```

(End definition for `__fp_parse_unary_function:NNN` and `__fp_parse_function:NNN`.)

24.6 Main functions

`__fp_parse:n` Start an `\exp:w` expansion so that `__fp_parse:n` expands in two steps. The `__fp_parse_operand:Nw` function performs computations until reaching an operation with precedence `\c__fp_prec_end_int` or less, namely, the end of the expression. The marker `\s__fp_mark` indicates that the next token is an already parsed version of an infix operator, and `__fp_parse_infix_end:N` has infinitely negative precedence. Finally, clean up a (well-defined) set of extra tokens and stop the initial expansion with `\exp_end:`.

```

12874 \cs_new:Npn \__fp_parse:n #1
12875 {
12876   \exp:w
12877   \exp_after:wN \__fp_parse_after:ww
12878   \exp:w
12879   \__fp_parse_operand:Nw \c__fp_prec_end_int
12880   \__fp_parse_expand:w #1
12881   \s__fp_mark \__fp_parse_infix_end:N
12882   \s__fp_stop
12883 }
12884 \cs_new:Npn \__fp_parse_after:ww
12885   #1@ \__fp_parse_infix_end:N \s__fp_stop
12886   { \exp_end: #1 }

```

(End definition for `__fp_parse:n` and `__fp_parse_after:ww`.)

```

\__fp_parse_o:n
12887 \cs_new:Npn \__fp_parse_o:n #1
12888 {
12889   \exp_after:wN \exp_after:wN
12890   \exp_after:wN \__fp_exp_after_o:w
12891   \__fp_parse:n {#1}

```

12892 }

(End definition for _fp_parse_o:n.)

_fp_parse_operand:Nw This is just a shorthand which sets up both _fp_parse_continue:NwN and _fp_parse_one:Nw with the same precedence. Note the trailing \exp:w.
_fp_parse_continue:NwN

```
12893 \cs_new:Npn \_fp_parse_operand:Nw #1
12894 {
12895   \exp_end_continue_f:w
12896   \exp_after:wN \_fp_parse_continue:NwN
12897   \exp_after:wN #1
12898   \exp:w \exp_end_continue_f:w
12899   \exp_after:wN \_fp_parse_one:Nw
12900   \exp_after:wN #1
12901   \exp:w
12902 }
12903 \cs_new:Npn \_fp_parse_continue:NwN #1 #2 @ #3 { #3 #1 #2 @ }
```

(End definition for _fp_parse_operand:Nw and _fp_parse_continue:NwN.)

_fp_parse_apply_binary:NwNwN Receives $\langle precedence \rangle \langle operand_1 \rangle @ \langle operation \rangle \langle operand_2 \rangle @ \langle infix command \rangle$. Builds the appropriate call to the $\langle operation \rangle$ #3.

This is redefined in l3fp-extras.

```
12904 \cs_new:Npn \_fp_parse_apply_binary:NwNwN #1 #2@ #3 #4@ #5
12905 {
12906   \exp_after:wN \_fp_parse_continue:NwN
12907   \exp_after:wN #1
12908   \exp:w \exp_end_continue_f:w \cs:w \_fp_#3_o:ww \cs_end: #2 #4
12909   \exp:w \exp_end_continue_f:w #5 #1
12910 }
```

(End definition for _fp_parse_apply_binary:NwNwN.)

24.7 Infix operators

_fp_parse_infix_after_operand:NwN

```
12911 \cs_new:Npn \_fp_parse_infix_after_operand:NwN #1 #2;
12912 {
12913   \_fp_exp_after_f:nw { \_fp_parse_infix:NN #1 }
12914   #2;
12915 }
12916 \cs_new:Npn \_fp_parse_infix:NN #1 #2
12917 {
12918   \if_catcode:w \scan_stop: \exp_not:N #2
12919   \if_int_compare:w
12920     \_str_if_eq_x:nn { \s_fp_mark } { \exp_not:N #2 }
12921     = 0 \exp_stop_f:
12922     \exp_after:wN \exp_after:wN
12923     \exp_after:wN \_fp_parse_infix_mark:NNN
12924   \else:
12925     \exp_after:wN \exp_after:wN
12926     \exp_after:wN \_fp_parse_infix_juxtapose:N
12927   \fi:
12928   \else:
```

```

12929         \if_int_compare:w
12930             \__int_eval:w
12931             ( '#2 \if_int_compare:w '#2 > 'Z - 32 \fi: ) / 26
12932             = 3 \exp_stop_f:
12933             \exp_after:wN \exp_after:wN
12934             \exp_after:wN \__fp_parse_infix_juxtapose:N
12935         \else:
12936             \exp_after:wN \__fp_parse_infix_check:NNN
12937             \cs:w
12938             __fp_parse_infix_ \token_to_str:N #2 :N
12939             \exp_after:wN \exp_after:wN \exp_after:wN
12940             \cs_end:
12941         \fi:
12942     \fi:
12943     #1
12944     #2
12945 }
12946 \cs_new:Npx \__fp_parse_infix_check:NNN #1#2#3
12947 {
12948     \exp_not:N \if_meaning:w \scan_stop: #1
12949     \exp_not:N \__msg_kernel_expandable_error:nnn
12950     { kernel } { fp-missing } { * }
12951     \exp_not:N \exp_after:wN
12952     \exp_not:c { __fp_parse_infix_*:N }
12953     \exp_not:N \exp_after:wN #2
12954     \exp_not:N \exp_after:wN #3
12955     \exp_not:N \else:
12956         \exp_not:N \exp_after:wN #1
12957         \exp_not:N \exp_after:wN #2
12958         \exp_not:N \exp:w
12959         \exp_not:N \exp_after:wN
12960         \exp_not:N \__fp_parse_expand:w
12961     \exp_not:N \fi:
12962 }

```

(End definition for __fp_parse_infix_after_operand:NwN.)

24.7.1 Closing parentheses and commas

__fp_parse_infix_mark:NNN As an infix operator, \s__fp_mark means that the next token (#3) has already gone through __fp_parse_infix:NN and should be provided the precedence #1. The scan mark #2 is discarded.

```

12963 \cs_new:Npn \__fp_parse_infix_mark:NNN #1#2#3 { #3 #1 }

```

(End definition for __fp_parse_infix_mark:NNN.)

__fp_parse_infix_end:N This one is a little bit odd: force every previous operator to end, regardless of the precedence.

```

12964 \cs_new:Npn \__fp_parse_infix_end:N #1
12965 { @ \use_none:n \__fp_parse_infix_end:N }

```

(End definition for __fp_parse_infix_end:N.)

_fp_parse_infix_):N This is very similar to _fp_parse_infix_end:N, complaining about an extra closing parenthesis if the previous operator was the beginning of the expression.

```

12966 \cs_set_protected:Npn \_fp_tmp:w #1
12967 {
12968   \cs_new:Npn #1 ##1
12969   {
12970     \if_int_compare:w ##1 < \c_fp_prec_paren_int
12971     \_msg_kernel_expandable_error:nnn { kernel } { fp-extra } { ) }
12972     \exp_after:wN \_fp_parse_infix:NN
12973     \exp_after:wN ##1
12974     \exp:w \exp_after:wN \_fp_parse_expand:w
12975   \else:
12976     \exp_after:wN @
12977     \exp_after:wN \use_none:n
12978     \exp_after:wN #1
12979   \fi:
12980 }
12981 }
12982 \exp_args:Nc \_fp_tmp:w { \_fp_parse_infix_):N }

```

(End definition for _fp_parse_infix_):N.)

_fp_parse_infix_,:N _fp_,_o:ww is a complicated way of replacing any number of floating point arguments by nan.

```

\_fp_parse_infix_comma:w
\_fp_parse_infix_comma_error:w
\_fp_,_o:ww
12983 \cs_set_protected:Npn \_fp_tmp:w #1
12984 {
12985   \cs_new:Npn #1 ##1
12986   {
12987     \if_int_compare:w ##1 > \c_fp_prec_comma_int
12988     \exp_after:wN @
12989     \exp_after:wN \use_none:n
12990     \exp_after:wN #1
12991   \else:
12992     \if_int_compare:w ##1 < \c_fp_prec_comma_int
12993     \_fp_parse_infix_comma_error:w
12994   \fi:
12995     \exp_after:wN \_fp_parse_infix_comma:w
12996     \exp:w \_fp_parse_operand:Nw \c_fp_prec_comma_int
12997     \exp_after:wN \_fp_parse_expand:w
12998   \fi:
12999 }
13000 }
13001 \exp_args:Nc \_fp_tmp:w { \_fp_parse_infix_,:N }
13002 \cs_new:Npn \_fp_parse_infix_comma:w #1 @
13003 { #1 @ \use_none:n }
13004 \cs_new:Npn \_fp_parse_infix_comma_error:w #1 \exp:w
13005 {
13006   \fi:
13007   \_msg_kernel_expandable_error:nn { kernel } { fp-extra-comma }
13008   \exp_after:wN @
13009   \exp_after:wN \_fp_parse_apply_binary:NwNwN
13010   \exp_after:wN ,
13011   \exp:w
13012 }

```



```

13013 \cs_set_protected:Npn \__fp_tmp:w #1
13014 {
13015   \cs_new:Npn #1 ##1
13016   {
13017     \if_meaning:w \s__fp ##1
13018       \exp_after:wN \__fp_use_i_until_s:nw
13019       \exp_after:wN #1
13020     \fi:
13021     \exp_after:wN \c_nan_fp
13022     ##1
13023   }
13024 }
13025 \exp_args:Nc \__fp_tmp:w { __fp_,_o:ww }

```

(End definition for __fp_parse_infix_,:N and others.)

24.7.2 Usual infix operators

As described in the “work plan”, each infix operator has an associated \..._infix... function, a computing function, and precedence, given as arguments to __fp_tmp:w. Using the general mechanism for arithmetic operations. The power operation must be associative in the opposite order from all others. For this, we use two distinct precedences.

```

13026 \cs_set_protected:Npn \__fp_tmp:w #1#2#3#4
13027 {
13028   \cs_new:Npn #1 ##1
13029   {
13030     \if_int_compare:w ##1 < #3
13031       \exp_after:wN @
13032       \exp_after:wN \__fp_parse_apply_binary:NwNwN
13033       \exp_after:wN #2
13034       \exp:w
13035       \__fp_parse_operand:Nw #4
13036       \exp_after:wN \__fp_parse_expand:w
13037     \else:
13038       \exp_after:wN @
13039       \exp_after:wN \use_none:n
13040       \exp_after:wN #1
13041     \fi:
13042   }
13043 }
13044 \exp_args:Nc \__fp_tmp:w { __fp_parse_infix^:N } ^
13045   \c__fp_prec_hatii_int \c__fp_prec_hat_int
13046 \exp_args:Nc \__fp_tmp:w { __fp_parse_infix/:N } /
13047   \c__fp_prec_times_int \c__fp_prec_times_int
13048 \exp_args:Nc \__fp_tmp:w { __fp_parse_infix_mul:N } *
13049   \c__fp_prec_times_int \c__fp_prec_times_int
13050 \exp_args:Nc \__fp_tmp:w { __fp_parse_infix -:N } -
13051   \c__fp_prec_plus_int \c__fp_prec_plus_int
13052 \exp_args:Nc \__fp_tmp:w { __fp_parse_infix +:N } +
13053   \c__fp_prec_plus_int \c__fp_prec_plus_int
13054 \exp_args:Nc \__fp_tmp:w { __fp_parse_infix_and:N } &
13055   \c__fp_prec_and_int \c__fp_prec_and_int
13056 \exp_args:Nc \__fp_tmp:w { __fp_parse_infix_or:N } |
13057   \c__fp_prec_or_int \c__fp_prec_or_int

```

(End definition for `_fp_parse_infix_+ :N` and others.)

24.7.3 Juxtaposition

`_fp_parse_infix_(:N` When an opening parenthesis appears where we expect an infix operator, we compute the product of the previous operand and the contents of the parentheses using `_fp_parse_infix_juxtapose:N`.

```
13058 \cs_new:cpn { \_fp_parse_infix_(:N } #1
13059 { \_fp_parse_infix_juxtapose:N #1 ( }
```

(End definition for `_fp_parse_infix_(:N`.)

`_fp_parse_infix_juxtapose:N` Juxtaposition follows the same scheme as other binary operations, but calls `_fp_parse_apply_juxtapose:NwwN` rather than directly calling `_fp_parse_apply_binary:NwwN`. This lets us catch errors such as `... (1,2,3)pt` where one operand of the juxtaposition is not a single number: both #3 and #5 of the apply auxiliary must be empty.

```
13060 \cs_new:Npn \_fp_parse_infix_juxtapose:N #1
13061 {
13062   \if_int_compare:w #1 < \c__fp_prec_times_int
13063     \exp_after:wN @
13064     \exp_after:wN \_fp_parse_apply_juxtapose:NwwN
13065     \exp:w
13066     \_fp_parse_operand:Nw \c__fp_prec_times_int
13067     \exp_after:wN \_fp_parse_expand:w
13068   \else:
13069     \exp_after:wN @
13070     \exp_after:wN \use_none:n
13071     \exp_after:wN \_fp_parse_infix_juxtapose:N
13072   \fi:
13073 }
13074 \cs_new:Npn \_fp_parse_apply_juxtapose:NwwN #1 #2;#3@ #4;#5@
13075 {
13076   \if_catcode:w ^ \tl_to_str:n { #3 #5 } ^
13077   \else:
13078     \__fp_error:nffn { fp-invalid-ii }
13079     { \_fp_array_to_clist:n { #2; #3 } }
13080     { \_fp_array_to_clist:n { #4; #5 } }
13081     { }
13082   \fi:
13083   \_fp_parse_apply_binary:NwwN #1 #2;@ * #4;@
13084 }
```

(End definition for `_fp_parse_infix_juxtapose:N` and `_fp_parse_apply_juxtapose:NwwN`.)

24.7.4 Multi-character cases

`_fp_parse_infix_*:N`

```
13085 \cs_set_protected:Npn \_fp_tmp:w #1
13086 {
13087   \cs_new:cpn { \_fp_parse_infix_*:N } ##1##2
13088   {
13089     \if:w * \exp_not:N ##2
```

```

13090         \exp_after:wN #1
13091         \exp_after:wN ##1
13092     \else:
13093         \exp_after:wN \__fp_parse_infix_mul:N
13094         \exp_after:wN ##1
13095         \exp_after:wN ##2
13096     \fi:
13097 }
13098 }
13099 \exp_args:Nc \__fp_tmp:w { \__fp_parse_infix_~:N }

```

(End definition for __fp_parse_infix_*:N.)

__fp_parse_infix_|:Nw
__fp_parse_infix_&:Nw

```

13100 \cs_set_protected:Npn \__fp_tmp:w #1#2#3
13101 {
13102     \cs_new:Npn #1 ##1##2
13103     {
13104         \if:w #2 \exp_not:N ##2
13105             \exp_after:wN #1
13106             \exp_after:wN ##1
13107             \exp:w \exp_after:wN \__fp_parse_expand:w
13108         \else:
13109             \exp_after:wN #3
13110             \exp_after:wN ##1
13111             \exp_after:wN ##2
13112         \fi:
13113     }
13114 }
13115 \exp_args:Nc \__fp_tmp:w { \__fp_parse_infix_|:N } | \__fp_parse_infix_or:N
13116 \exp_args:Nc \__fp_tmp:w { \__fp_parse_infix_&:N } & \__fp_parse_infix_and:N

```

(End definition for __fp_parse_infix_|:Nw and __fp_parse_infix_&:Nw.)

24.7.5 Ternary operator

__fp_parse_infix_?:N
__fp_parse_infix_:N

```

13117 \cs_set_protected:Npn \__fp_tmp:w #1#2#3#4
13118 {
13119     \cs_new:Npn #1 ##1
13120     {
13121         \if_int_compare:w ##1 < \c__fp_prec_quest_int
13122             #4
13123             \exp_after:wN @
13124             \exp_after:wN #2
13125             \exp:w
13126             \__fp_parse_operand:Nw #3
13127             \exp_after:wN \__fp_parse_expand:w
13128         \else:
13129             \exp_after:wN @
13130             \exp_after:wN \use_none:n
13131             \exp_after:wN #1
13132         \fi:
13133     }

```

```

13134 }
13135 \exp_args:Nc \__fp_tmp:w { __fp_parse_infix_?:N }
13136 \__fp_ternary:NwwN \c__fp_prec_quest_int { }
13137 \exp_args:Nc \__fp_tmp:w { __fp_parse_infix_:N }
13138 \__fp_ternary_auxii:NwwN \c__fp_prec_colon_int
13139 {
13140   \__msg_kernel_expandable_error:nnnn
13141   { kernel } { fp-missing } { ? } { ~for~?: }
13142 }

```

(End definition for __fp_parse_infix_?:N and __fp_parse_infix_:N.)

24.7.6 Comparisons

```

\__fp_parse_infix_<:N
\__fp_parse_infix_=:N
\__fp_parse_infix_>:N
\__fp_parse_infix_!:N
\__fp_parse_excl_error:
\__fp_parse_compare:NNNNNNN
\__fp_parse_compare_auxi:NNNNNN
\__fp_parse_compare_auxii:NNNNN
\__fp_parse_compare_end:NNNNw
\__fp_compare:wNNNNw
13143 \cs_new:cpn { __fp_parse_infix_<:N } #1
13144 { \__fp_parse_compare:NNNNNNN #1 1 0 0 0 0 < }
13145 \cs_new:cpn { __fp_parse_infix_=:N } #1
13146 { \__fp_parse_compare:NNNNNNN #1 1 0 0 0 0 = }
13147 \cs_new:cpn { __fp_parse_infix_>:N } #1
13148 { \__fp_parse_compare:NNNNNNN #1 1 0 0 0 0 > }
13149 \cs_new:cpn { __fp_parse_infix_!:N } #1
13150 {
13151   \exp_after:wN \__fp_parse_compare:NNNNNNN
13152   \exp_after:wN #1
13153   \exp_after:wN 0
13154   \exp_after:wN 1
13155   \exp_after:wN 1
13156   \exp_after:wN 1
13157   \exp_after:wN 1
13158 }
13159 \cs_new:Npn \__fp_parse_excl_error:
13160 {
13161   \__msg_kernel_expandable_error:nnnn
13162   { kernel } { fp-missing } { = } { ~after~!. }
13163 }
13164 \cs_new:Npn \__fp_parse_compare:NNNNNNN #1
13165 {
13166   \if_int_compare:w #1 < \c__fp_prec_comp_int
13167     \exp_after:wN \__fp_parse_compare_auxi:NNNNNNN
13168     \exp_after:wN \__fp_parse_excl_error:
13169   \else:
13170     \exp_after:wN @
13171     \exp_after:wN \use_none:n
13172     \exp_after:wN \__fp_parse_compare:NNNNNNN
13173   \fi:
13174 }
13175 \cs_new:Npn \__fp_parse_compare_auxi:NNNNNNN #1#2#3#4#5#6#7
13176 {
13177   \if_case:w
13178     \__int_eval:w \exp_after:wN ‘ \token_to_str:N #7 - ‘< \__int_eval_end:
13179     \__fp_parse_compare_auxii:NNNNN #2#2#4#5#6
13180   \or: \__fp_parse_compare_auxii:NNNNN #2#3#2#5#6
13181   \or: \__fp_parse_compare_auxii:NNNNN #2#3#4#2#6

```

```

13182     \or: \_fp_parse_compare_auxii:NNNNN #2#3#4#5#2
13183     \else: #1 \_fp_parse_compare_end:NNNNw #3#4#5#6#7
13184     \fi:
13185 }
13186 \cs_new:Npn \_fp_parse_compare_auxii:NNNNN #1#2#3#4#5
13187 {
13188     \exp_after:wN \_fp_parse_compare_auxi:NNNNNNN
13189     \exp_after:wN \prg_do_nothing:
13190     \exp_after:wN #1
13191     \exp_after:wN #2
13192     \exp_after:wN #3
13193     \exp_after:wN #4
13194     \exp_after:wN #5
13195     \exp:w \exp_after:wN \_fp_parse_expand:w
13196 }
13197 \cs_new:Npn \_fp_parse_compare_end:NNNNw #1#2#3#4#5 \fi:
13198 {
13199     \fi:
13200     \exp_after:wN @
13201     \exp_after:wN \_fp_parse_apply_compare:NwNNNNNNwN
13202     \exp_after:wN \c_one_fp
13203     \exp_after:wN #1
13204     \exp_after:wN #2
13205     \exp_after:wN #3
13206     \exp_after:wN #4
13207     \exp:w
13208     \_fp_parse_operand:Nw \c__fp_prec_comp_int \_fp_parse_expand:w #5
13209 }
13210 \cs_new:Npn \_fp_parse_apply_compare:NwNNNNNNwN
13211 #1 #2@ #3 #4#5#6#7 #8@ #9
13212 {
13213     \if_int_odd:w
13214         \if_meaning:w \c_zero_fp #3
13215         0
13216     \else:
13217         \if_case:w \_fp_compare_back:ww #8 #2 \exp_stop_f:
13218             #5 \or: #6 \or: #7 \else: #4
13219         \fi:
13220     \fi:
13221     \exp_stop_f:
13222     \exp_after:wN \_fp_parse_apply_compare_aux:NNwN
13223     \exp_after:wN \c_one_fp
13224 \else:
13225     \exp_after:wN \_fp_parse_apply_compare_aux:NNwN
13226     \exp_after:wN \c_zero_fp
13227 \fi:
13228 #1 #8 #9
13229 }
13230 \cs_new:Npn \_fp_parse_apply_compare_aux:NNwN #1 #2 #3; #4
13231 {
13232     \if_meaning:w \_fp_parse_compare:NNNNNNN #4
13233     \exp_after:wN \_fp_parse_continue_compare:NNwNN
13234     \exp_after:wN #1
13235     \exp_after:wN #2

```

```

13236     \exp:w \exp_end_continue_f:w
13237     \__fp_exp_after_o:w #3;
13238     \exp:w \exp_end_continue_f:w
13239   \else:
13240     \exp_after:wN \__fp_parse_continue:NwN
13241     \exp_after:wN #2
13242     \exp:w \exp_end_continue_f:w
13243     \exp_after:wN #1
13244     \exp:w \exp_end_continue_f:w
13245   \fi:
13246   #4 #2
13247 }
13248 \cs_new:Npn \__fp_parse_continue_compare:NNwNN #1#2 #3@ #4#5
13249 { #4 #2 #3@ #1 }

```

(End definition for `__fp_parse_infix_<:N` and others.)

24.8 Candidate: defining new l3fp functions

`\fp_function:Nw` Parse the argument of the function #1 using `__fp_parse_operand:Nw` with a precedence of 16, and pass the function and argument to `__fp_function_apply:nw`.

```

13250 \cs_new:Npn \fp_function:Nw #1
13251 {
13252   \exp_after:wN \__fp_function_apply:nw
13253   \exp_after:wN #1
13254   \exp:w
13255     \__fp_parse_operand:Nw \c__fp_prec_funcii_int \__fp_parse_expand:w
13256 }

```

(End definition for `\fp_function:Nw`. This function is documented on page ??.)

`\fp_new_function:Npn` Save the code provided by the user in the control sequence `__fp_user_#1`. Define `__fp_new_function:NNnnn` #1 to call `__fp_function_apply:nw` after parsing one operand using `__fp_parse_operand:Nw` with precedence 16. The auxiliary `__fp_function_args:Nwn` receives the user function and the number of arguments (half of the number of tokens in the parameter text #2), followed by the operand (as a token list of floating points). It checks the number of arguments, and applies the user function to the arguments (without the outer brace group).

```

13257 \cs_new_protected:Npn \fp_new_function:Npn #1#2#
13258 {
13259   \__fp_new_function:Ncfnn #1
13260   { \__fp_user_ \cs_to_str:N #1 }
13261   { \int_eval:n { \tl_count:n {#2} / 2 } }
13262   {#2}
13263 }
13264 \cs_new_protected:Npn \__fp_new_function:NNnnn #1#2#3#4#5
13265 {
13266   \cs_new:Npn #1
13267   {
13268     \exp_after:wN \__fp_function_apply:nw \exp_after:wN
13269     {
13270       \exp_after:wN \__fp_function_args:Nwn
13271       \exp_after:wN #2
13272       \__int_value:w #3 \exp_after:wN ; \exp_after:wN

```

```

13273     }
13274     \exp:w
13275     \__fp_parse_operand:Nw \c__fp_prec_funcii_int \__fp_parse_expand:w
13276   }
13277   \cs_new:Npn #2 #4 {#5}
13278 }
13279 \cs_generate_variant:Nn \__fp_new_function:NNnnn { Ncf }
13280 \cs_new:Npn \__fp_function_args:Nwn #1#2; #3
13281 {
13282   \int_compare:nNnTF { \tl_count:n {#3} } = {#2}
13283   { #1 #3 }
13284   {
13285     \_msg_kernel_expandable_error:nnnnn
13286     { kernel } { fp-num-args } { #1() } {#2} {#2}
13287     \c_nan_fp
13288   }
13289 }

```

(End definition for `\fp_new_function:Npn`, `__fp_new_function:NNnnn`, and `__fp_function_args:Nwn`. This function is documented on page ??.)

```

\__fp_function_apply:nw
\__fp_function_store:wwNwnn
  \__fp_function_store_end:wnnn

```

The auxiliary `__fp_function_apply:nw` is called after parsing an operand, so it receives some code `#1`, then the operand ending with `@`, then a function such as `__fp_parse_infix_+:N` (but not always of this form, see comparisons for instance). Package the operand (an array) into a token list with floating point items: this is the role of `__fp_function_store:wwNwnn` and `__fp_function_store_end:wnnn`. Then apply `__fp_parse:n` to the code `#1` followed by a brace group with this token list. This results in a floating point result, which is then correctly parsed as the next operand of whatever was looking for one. The trailing `\s__fp_mark` is used as a special infix operator to indicate that the next token has already gone through `__fp_parse_infix:NN`.

```

13290 \cs_new:Npn \__fp_function_apply:nw #1#2 @
13291 {
13292   \__fp_parse:n
13293   {
13294     \__fp_function_store:wwNwnn #2
13295     \s__fp_mark \__fp_function_store:wwNwnn ;
13296     \s__fp_mark \__fp_function_store_end:wnnn
13297     \s__fp_stop { } { } {#1}
13298   }
13299   \s__fp_mark
13300 }
13301 \cs_new:Npn \__fp_function_store:wwNwnn
13302   #1; #2 \s__fp_mark #3#4 \s__fp_stop #5#6
13303   { #3 #2 \s__fp_mark #3#4 \s__fp_stop { #5 #6 } { { #1; } } }
13304 \cs_new:Npn \__fp_function_store_end:wnnn
13305   #1 \s__fp_stop #2#3#4
13306   { #4 {#2} }

```

(End definition for `__fp_function_apply:nw`, `__fp_function_store:wwNwnn`, and `__fp_function_store_end:wnnn`.)

24.9 Messages

```

13307 \_msg_kernel_new:nnn { kernel } { fp-deprecated }

```

```

13308 { '#1'~deprecated;~use~'#2' }
13309 \__msg_kernel_new:nnn { kernel } { unknown-fp-word }
13310 { Unknown~fp-word~#1. }
13311 \__msg_kernel_new:nnn { kernel } { fp-missing }
13312 { Missing~#1~inserted #2. }
13313 \__msg_kernel_new:nnn { kernel } { fp-extra }
13314 { Extra~#1~ignored. }
13315 \__msg_kernel_new:nnn { kernel } { fp-early-end }
13316 { Premature~end~in~fp-expression. }
13317 \__msg_kernel_new:nnn { kernel } { fp-after-e }
13318 { Cannot~use~#1 after~'e'. }
13319 \__msg_kernel_new:nnn { kernel } { fp-missing-number }
13320 { Missing~number~before~'#1'. }
13321 \__msg_kernel_new:nnn { kernel } { fp-unknown-symbol }
13322 { Unknown~symbol~#1~ignored. }
13323 \__msg_kernel_new:nnn { kernel } { fp-extra-comma }
13324 { Unexpected~comma:~extra~arguments~ignored. }
13325 \__msg_kernel_new:nnn { kernel } { fp-num-args }
13326 { #1~expects~between~#2~and~#3~arguments. }
13327 (*package)
13328 \cs_if_exist:cT { @unexpandable@protect }
13329 {
13330   \__msg_kernel_new:nnn { kernel } { fp-robust-cmd }
13331   { Robust~command~#1 invalid~in~fp-expression! }
13332 }
13333 </package>
13334 </initex | package>

```

25 l3fp-logic Implementation

```

13335 (*initex | package)
13336 <@@=fp>

```

```

\__fp_parse_word_max:N
\__fp_parse_word_min:N

```

Those functions may receive a variable number of arguments.

```

13337 \cs_new:Npn \__fp_parse_word_max:N
13338 { \__fp_parse_function:NNN \__fp_minmax_o:Nw 2 }
13339 \cs_new:Npn \__fp_parse_word_min:N
13340 { \__fp_parse_function:NNN \__fp_minmax_o:Nw 0 }

```

(End definition for `__fp_parse_word_max:N` and `__fp_parse_word_min:N`.)

25.1 Syntax of internal functions

- `__fp_compare_npos:nwnw {<expo1>} <body1> ; {<expo2>} <body2> ;`
- `__fp_minmax_o:Nw <sign> <floating point array>`
- `__fp_not_o:w ? <floating point array>` (with one floating point number only)
- `__fp_&_o:ww <floating point> <floating point>`
- `__fp_|_o:ww <floating point> <floating point>`
- `__fp_ternary:NwwN, __fp_ternary_auxi:NwwN, __fp_ternary_auxii:NwwN` have to be understood.

25.2 Existence test

`\fp_if_exist_p:N` Copies of the `cs` functions defined in `l3basics`.
`\fp_if_exist_p:c` 13341 `\prg_new_eq_conditional:Nn \fp_if_exist:N \cs_if_exist:N { TF , T , F , p }`
`\fp_if_exist:N \overline{TF}` 13342 `\prg_new_eq_conditional:Nn \fp_if_exist:c \cs_if_exist:c { TF , T , F , p }`
`\fp_if_exist:c \overline{TF}` (End definition for `\fp_if_exist:N \overline{TF}` . This function is documented on page 186.)

25.3 Comparison

`\fp_compare_p:n` Within floating point expressions, comparison operators are treated as operations, so we
`\fp_compare:n \overline{TF}` evaluate #1, then compare with 0.
`__fp_compare_return:w` 13343 `\prg_new_conditional:Npnn \fp_compare:n #1 { p , T , F , TF }`
13344 `{`
13345 `\exp_after:wN __fp_compare_return:w`
13346 `\exp:w \exp_end_continue_f:w __fp_parse:n {#1}`
13347 `}`
13348 `\cs_new:Npn __fp_compare_return:w \s_fp __fp_chk:w #1#2;`
13349 `{`
13350 `\if_meaning:w 0 #1`
13351 `\prg_return_false:`
13352 `\else:`
13353 `\prg_return_true:`
13354 `\fi:`
13355 `}`
(End definition for `\fp_compare:n \overline{TF}` and `__fp_compare_return:w`. This function is documented on page 187.)

`\fp_compare_p:nNn` Evaluate #1 and #3, using an auxiliary to expand both, and feed the two floating point
`\fp_compare:nNn \overline{TF}` numbers swapped to `__fp_compare_back:ww`, defined below. Compare the result with
`__fp_compare_aux:wn` ‘#2-‘=, which is -1 for <, 0 for =, 1 for > and 2 for ?.
13356 `\prg_new_conditional:Npnn \fp_compare:nNn #1#2#3 { p , T , F , TF }`
13357 `{`
13358 `\if_int_compare:w`
13359 `\exp_after:wN __fp_compare_aux:wn`
13360 `\exp:w \exp_end_continue_f:w __fp_parse:n {#1} {#3}`
13361 `= __int_eval:w ‘#2 - ‘= __int_eval_end:`
13362 `\prg_return_true:`
13363 `\else:`
13364 `\prg_return_false:`
13365 `\fi:`
13366 `}`
13367 `\cs_new:Npn __fp_compare_aux:wn #1; #2`
13368 `{`
13369 `\exp_after:wN __fp_compare_back:ww`
13370 `\exp:w \exp_end_continue_f:w __fp_parse:n {#2} #1;`
13371 `}`
(End definition for `\fp_compare:nNn \overline{TF}` and `__fp_compare_aux:wn`. This function is documented on page 187.)

`__fp_compare_back:ww`
`__fp_compare_nan:w`

`__fp_compare_back:ww` $\langle y \rangle$; $\langle x \rangle$;
 Expands (in the same way as `\int_eval:n`) to -1 if $x < y$, 0 if $x = y$, 1 if $x > y$, and 2 otherwise (denoted as $x?y$). If either operand is `nan`, stop the comparison with `__fp_compare_nan:w` returning 2 . If x is negative, swap the outputs 1 and -1 (i.e., $>$ and $<$); we can henceforth assume that $x \geq 0$. If $y \geq 0$, and they have the same type, either they are normal and we compare them with `__fp_compare_npos:nwnw`, or they are equal. If $y \geq 0$, but of a different type, the highest type is a larger number. Finally, if $y \leq 0$, then $x > y$, unless both are zero.

```

13372 \cs_new:Npn \__fp_compare_back:ww
13373   \s__fp \__fp_chk:w #1 #2 #3;
13374   \s__fp \__fp_chk:w #4 #5 #6;
13375   {
13376     \__int_value:w
13377     \if_meaning:w 3 #1 \exp_after:wN \__fp_compare_nan:w \fi:
13378     \if_meaning:w 3 #4 \exp_after:wN \__fp_compare_nan:w \fi:
13379     \if_meaning:w 2 #5 - \fi:
13380     \if_meaning:w #2 #5
13381     \if_meaning:w #1 #4
13382     \if_meaning:w 1 #1
13383     \__fp_compare_npos:nwnw #6; #3;
13384     \else:
13385       0
13386     \fi:
13387     \else:
13388       \if_int_compare:w #4 < #1 - \fi: 1
13389     \fi:
13390     \else:
13391       \if_int_compare:w #1#4 = 0 \exp_stop_f:
13392       0
13393     \else:
13394       1
13395     \fi:
13396     \fi:
13397     \exp_stop_f:
13398   }
13399 \cs_new:Npn \__fp_compare_nan:w #1 \fi: \exp_stop_f: { 2 \exp_stop_f: }

```

(End definition for `__fp_compare_back:ww` and `__fp_compare_nan:w`.)

`__fp_compare_npos:nwnw`
`__fp_compare_significand:nnnnnnnn`

`__fp_compare_npos:nwnw` $\{\langle expo_1 \rangle\} \langle body_1 \rangle$; $\{\langle expo_2 \rangle\} \langle body_2 \rangle$;
 Within an `__int_value:w ... \exp_stop_f:` construction, this expands to 0 if the two numbers are equal, -1 if the first is smaller, and 1 if the first is bigger. First compare the exponents: the larger one denotes the larger number. If they are equal, we must compare significands. If both the first 8 digits and the next 8 digits coincide, the numbers are equal. If only the first 8 digits coincide, the next 8 decide. Otherwise, the first 8 digits are compared.

```

13400 \cs_new:Npn \__fp_compare_npos:nwnw #1#2; #3#4;
13401   {
13402     \if_int_compare:w #1 = #3 \exp_stop_f:
13403     \__fp_compare_significand:nnnnnnnn #2 #4
13404     \else:
13405       \if_int_compare:w #1 < #3 - \fi: 1
13406     \fi:

```

```

13407 }
13408 \cs_new:Npn \__fp_compare_significand:nnnnnnnn #1#2#3#4#5#6#7#8
13409 {
13410   \if_int_compare:w #1#2 = #5#6 \exp_stop_f:
13411   \if_int_compare:w #3#4 = #7#8 \exp_stop_f:
13412   0
13413   \else:
13414     \if_int_compare:w #3#4 < #7#8 - \fi: 1
13415   \fi:
13416   \else:
13417     \if_int_compare:w #1#2 < #5#6 - \fi: 1
13418   \fi:
13419 }

```

(End definition for __fp_compare_npos:nwnw and __fp_compare_significand:nnnnnnnn.)

25.4 Floating point expression loops

\fp_do_until:nn These are quite easy given the above functions. The **do_until** and **do_while** versions execute the body, then test. The **until_do** and **while_do** do it the other way round.

```

\fp_do_while:nn
\fp_until_do:nn
\fp_while_do:nn
13420 \cs_new:Npn \fp_do_until:nn #1#2
13421 {
13422   #2
13423   \fp_compare:nF {#1}
13424   { \fp_do_until:nn {#1} {#2} }
13425 }
13426 \cs_new:Npn \fp_do_while:nn #1#2
13427 {
13428   #2
13429   \fp_compare:nT {#1}
13430   { \fp_do_while:nn {#1} {#2} }
13431 }
13432 \cs_new:Npn \fp_until_do:nn #1#2
13433 {
13434   \fp_compare:nF {#1}
13435   {
13436     #2
13437     \fp_until_do:nn {#1} {#2}
13438   }
13439 }
13440 \cs_new:Npn \fp_while_do:nn #1#2
13441 {
13442   \fp_compare:nT {#1}
13443   {
13444     #2
13445     \fp_while_do:nn {#1} {#2}
13446   }
13447 }

```

(End definition for \fp_do_until:nn and others. These functions are documented on page 188.)

\fp_do_until:nNnn As above but not using the nNn syntax.

```

\fp_do_while:nNnn
\fp_until_do:nNnn
\fp_while_do:nNnn
13448 \cs_new:Npn \fp_do_until:nNnn #1#2#3#4
13449 {

```

```

13450     #4
13451     \fp_compare:nNnF {#1} #2 {#3}
13452     { \fp_do_until:nNnn {#1} #2 {#3} {#4} }
13453   }
13454 \cs_new:Npn \fp_do_while:nNnn #1#2#3#4
13455 {
13456   #4
13457   \fp_compare:nNnT {#1} #2 {#3}
13458   { \fp_do_while:nNnn {#1} #2 {#3} {#4} }
13459 }
13460 \cs_new:Npn \fp_until_do:nNnn #1#2#3#4
13461 {
13462   \fp_compare:nNnF {#1} #2 {#3}
13463   {
13464     #4
13465     \fp_until_do:nNnn {#1} #2 {#3} {#4}
13466   }
13467 }
13468 \cs_new:Npn \fp_while_do:nNnn #1#2#3#4
13469 {
13470   \fp_compare:nNnT {#1} #2 {#3}
13471   {
13472     #4
13473     \fp_while_do:nNnn {#1} #2 {#3} {#4}
13474   }
13475 }

```

(End definition for `\fp_do_until:nNnn` and others. These functions are documented on page 188.)

`\fp_step_function:nnnN` The approach here is somewhat similar to `\int_step_function:nnnN`. There are two subtleties: we use the internal parser `__fp_parse:n` to avoid converting back and forth from the internal representation; and (due to rounding) even a non-zero step does not guarantee that the loop counter increases.

```

\fp_step_function:nnnc
  \__fp_step:wwwN
  \__fp_step:NnnnnN
  \__fp_step:NfnnnN
13476 \cs_new:Npn \fp_step_function:nnnN #1#2#3
13477 {
13478   \exp_after:wN \__fp_step:wwwN
13479   \exp:w \exp_end_continue_f:w \__fp_parse_o:n {#1}
13480   \exp:w \exp_end_continue_f:w \__fp_parse_o:n {#2}
13481   \exp:w \exp_end_continue_f:w \__fp_parse:n {#3}
13482 }
13483 \cs_generate_variant:Nn \fp_step_function:nnnN { nnnc }
13484 % \end{macrocode}
13485 % Only \enquote{normal} floating points (not $\pm 0$,
13486 % $\pm\texttt{inf}$, $\texttt{nan}$) can be used as step; if positive,
13487 % call \cs{__fp_step:NnnnnN} with argument |>| otherwise~|<|. This
13488 % function has one more argument than its integer counterpart, namely
13489 % the previous value, to catch the case where the loop has made no
13490 % progress. Conversion to decimal is done just before calling the
13491 % user's function.
13492 % \begin{macrocode}
13493 \cs_new:Npn \__fp_step:wwwN #1 ; \s__fp \__fp_chk:w #2#3#4 ; #5; #6
13494 {
13495   \token_if_eq_meaning:NNTF #2 1
13496   {

```

```

13497     \token_if_eq_meaning:NNTF #3 0
13498     { \__fp_step:NnnnnN > }
13499     { \__fp_step:NnnnnN < }
13500   }
13501   {
13502     \token_if_eq_meaning:NNTF #2 0
13503     { \__msg_kernel_expandable_error:nnn { kernel } { zero-step } {#6} }
13504     {
13505       \__fp_error:nfn { fp-bad-step } { }
13506       { \fp_to_tl:n { \s__fp \__fp_chk:w #2#3#4 ; } } {#6}
13507     }
13508     \use_none:nnnnn
13509   }
13510   { #1 ; } { \c_nan_fp } { \s__fp \__fp_chk:w #2#3#4 ; } { #5 ; } #6
13511 }
13512 \cs_new:Npn \__fp_step:NnnnnN #1#2#3#4#5#6
13513 {
13514   \fp_compare:nNnTF {#2} = {#3}
13515   {
13516     \__fp_error:nfn { fp-tiny-step }
13517     { \fp_to_tl:n {#3} } { \fp_to_tl:n {#4} } {#6}
13518   }
13519   {
13520     \fp_compare:nNnF {#2} #1 {#5}
13521     {
13522       \exp_args:Nf #6 { \__fp_to_decimal_dispatch:w #2 }
13523       \__fp_step:NfnnnN
13524       #1 { \__fp_parse:n { #2 + #4 } } {#2} {#4} {#5} #6
13525     }
13526   }
13527 }
13528 \cs_generate_variant:Nn \__fp_step:NnnnnN { Nf }

```

(End definition for `\fp_step_function:nnnN`, `__fp_step:wwwN`, and `__fp_step:NnnnnN`. This function is documented on page 189.)

`\fp_step_inline:nnnn` As for `\int_step_inline:nnnn`, create a global function and apply it, following up with a break point.

```

\fp_step_variable:nnnNn
\__fp_step:NNnnnnn
13529 \cs_new_protected:Npn \fp_step_inline:nnnn
13530 {
13531   \int_gincr:N \g__prg_map_int
13532   \exp_args:NNc \__fp_step:NNnnnn
13533   \cs_gset_protected:Npn
13534   { __prg_map_ \int_use:N \g__prg_map_int :w }
13535 }
13536 \cs_new_protected:Npn \fp_step_variable:nnnNn #1#2#3#4#5
13537 {
13538   \int_gincr:N \g__prg_map_int
13539   \exp_args:NNc \__fp_step:NNnnnn
13540   \cs_gset_protected:Npx
13541   { __prg_map_ \int_use:N \g__prg_map_int :w }
13542   {#1} {#2} {#3}
13543   {
13544     \tl_set:Nn \exp_not:N #4 {##1}

```

```

13545         \exp_not:n {#5}
13546     }
13547 }
13548 \cs_new_protected:Npn \__fp_step:NNnnnn #1#2#3#4#5#6
13549 {
13550     #1 #2 ##1 {#6}
13551     \fp_step_function:nnnN {#3} {#4} {#5} #2
13552     \__prg_break_point:Nn \scan_stop: { \int_gdecr:N \g__prg_map_int }
13553 }

```

(End definition for `\fp_step_inline:nnnn`, `\fp_step_variable:nnnNn`, and `__fp_step:NNnnnn`. These functions are documented on page 189.)

```

13554 \__msg_kernel_new:nnn { kernel } { fp-bad-step }
13555 { Invalid~step~size~#2~in~step~function~#3. }
13556 \__msg_kernel_new:nnn { kernel } { fp-tiny-step }
13557 { Tiny~step~size~(#1+#2=#1)~in~step~function~#3. }

```

25.5 Extrema

`__fp_minmax_o:Nw` The argument `#1` is `2` to find the maximum of an array `#2` of floating point numbers, and `0` to find the minimum. We read numbers sequentially, keeping track of the largest (smallest) number found so far. If numbers are equal (for instance ± 0), the first is kept. We append $-\infty$ (∞), for the case of an empty array. Since no number is smaller (larger) than that, this additional item only affects the maximum (minimum) in the case of `max()` and `min()` with no argument. The weird fp-like trailing marker breaks the loop correctly: see the precise definition of `__fp_minmax_loop:Nww`.

```

13558 \cs_new:Npn \__fp_minmax_o:Nw #1#2 @
13559 {
13560     \if_meaning:w 0 #1
13561         \exp_after:wN \__fp_minmax_loop:Nww \exp_after:wN +
13562     \else:
13563         \exp_after:wN \__fp_minmax_loop:Nww \exp_after:wN -
13564     \fi:
13565     #2
13566     \s__fp \__fp_chk:w 2 #1 \s__fp_exact ;
13567     \s__fp \__fp_chk:w { 3 \__fp_minmax_break_o:w } ;
13568 }

```

(End definition for `__fp_minmax_o:Nw`.)

`__fp_minmax_loop:Nww` The first argument is `-` or `+` to denote the case where the currently largest (smallest) number found (first floating point argument) should be replaced by the new number (second floating point argument). If the new number is `nan`, keep that as the extremum, unless that extremum is already a `nan`. Otherwise, compare the two numbers. If the new number is larger (in the case of `max`) or smaller (in the case of `min`), the test yields `true`, and we keep the second number as a new maximum; otherwise we keep the first number. Then loop.

```

13569 \cs_new:Npn \__fp_minmax_loop:Nww
13570     #1 \s__fp \__fp_chk:w #2#3; \s__fp \__fp_chk:w #4#5;
13571 {
13572     \if_meaning:w 3 #4
13573         \if_meaning:w 3 #2
13574             \__fp_minmax_auxi:ww

```

```

13575     \else:
13576         \__fp_minmax_auxii:ww
13577     \fi:
13578 \else:
13579     \if_int_compare:w
13580         \__fp_compare_back:ww
13581         \s__fp \__fp_chk:w #4#5;
13582         \s__fp \__fp_chk:w #2#3;
13583         = #1 1 \exp_stop_f:
13584         \__fp_minmax_auxii:ww
13585     \else:
13586         \__fp_minmax_auxi:ww
13587     \fi:
13588 \fi:
13589 \__fp_minmax_loop:Nww #1
13590     \s__fp \__fp_chk:w #2#3;
13591     \s__fp \__fp_chk:w #4#5;
13592 }

```

(End definition for __fp_minmax_loop:Nww.)

```

\__fp_minmax_auxi:ww Keep the first/second number, and remove the other.
\__fp_minmax_auxii:ww
13593 \cs_new:Npn \__fp_minmax_auxi:ww #1 \fi: \fi: #2 \s__fp #3 ; \s__fp #4;
13594 { \fi: \fi: #2 \s__fp #3 ; }
13595 \cs_new:Npn \__fp_minmax_auxii:ww #1 \fi: \fi: #2 \s__fp #3 ;
13596 { \fi: \fi: #2 }

```

(End definition for __fp_minmax_auxi:ww and __fp_minmax_auxii:ww.)

__fp_minmax_break_o:w This function is called from within an \if_meaning:w test. Skip to the end of the tests, close the current test with \fi:, clean up, and return the appropriate number with one post-expansion.

```

13597 \cs_new:Npn \__fp_minmax_break_o:w #1 \fi: \fi: #2 \s__fp #3; #4;
13598 { \fi: \__fp_exp_after_o:w \s__fp #3; }

```

(End definition for __fp_minmax_break_o:w.)

25.6 Boolean operations

__fp_not_o:w Return true or false, with two expansions, one to exit the conditional, and one to please l3fp-parse. The first argument is provided by l3fp-parse and is ignored.

```

13599 \cs_new:cpn { __fp_not_o:w } #1 \s__fp \__fp_chk:w #2#3; @
13600 {
13601     \if_meaning:w 0 #2
13602         \exp_after:wN \exp_after:wN \exp_after:wN \c_one_fp
13603     \else:
13604         \exp_after:wN \exp_after:wN \exp_after:wN \c_zero_fp
13605     \fi:
13606 }

```

(End definition for __fp_not_o:w.)

`__fp_&_o:ww` For **and**, if the first number is zero, return it (with the same sign). Otherwise, return
`__fp_|_o:ww` the second one. For **or**, the logic is reversed: if the first number is non-zero, return
`__fp_and_return:wNw` it, otherwise return the second number: we achieve that by hi-jacking `__fp_&_o:ww`,
inserting an extra argument, `\else:`, before `\s__fp`. In all cases, expand after the
floating point number.

```

13607 \group_begin:
13608   \char_set_catcode_letter:N &
13609   \char_set_catcode_letter:N |
13610   \cs_new:Npn \__fp_&_o:ww #1 \s__fp \__fp_chk:w #2#3;
13611   {
13612     \if_meaning:w 0 #2 #1
13613     \__fp_and_return:wNw \s__fp \__fp_chk:w #2#3;
13614     \fi:
13615     \__fp_exp_after_o:w
13616   }
13617   \cs_new:Npn \__fp_|_o:ww { \__fp_&_o:ww \else: }
13618 \group_end:
13619 \cs_new:Npn \__fp_and_return:wNw #1; \fi: #2#3; { \fi: #2 #1; }

```

(End definition for `__fp_&_o:ww`, `__fp_|_o:ww`, and `__fp_and_return:wNw`.)

25.7 Ternary operator

`__fp_ternary:NwN` The first function receives the test and the true branch of the `?:` ternary operator. It
`__fp_ternary_auxi:NwN` returns the true branch, unless the test branch is zero. In that case, the function returns
`__fp_ternary_auxii:NwN` a very specific **nan**. The second function receives the output of the first function, and the
`__fp_ternary_loop_break:w` false branch. It returns the previous input, unless that is the special **nan**, in which case
`__fp_ternary_loop:Nw` we return the false branch.
`__fp_ternary_map_break:`
`__fp_ternary_break_point:n`

```

13620 \cs_new:Npn \__fp_ternary:NwN #1 #2@ #3@ #4
13621 {
13622   \if_meaning:w \__fp_parse_infix_:N #4
13623   \__fp_ternary_loop:Nw
13624   #2
13625   \s__fp \__fp_chk:w { \__fp_ternary_loop_break:w } ;
13626   \__fp_ternary_break_point:n { \exp_after:wN \__fp_ternary_auxi:NwN }
13627   \exp_after:wN #1
13628   \exp:w \exp_end_continue_f:w
13629   \__fp_exp_after_array_f:w #3 \s__fp_stop
13630   \exp_after:wN @
13631   \exp:w
13632   \__fp_parse_operand:Nw \c__fp_prec_colon_int
13633   \__fp_parse_expand:w
13634   \else:
13635     \__msg_kernel_expandable_error:nnnn
13636     { kernel } { fp-missing } { : } { ~for~?: }
13637     \exp_after:wN \__fp_parse_continue:NwN
13638     \exp_after:wN #1
13639     \exp:w \exp_end_continue_f:w
13640     \__fp_exp_after_array_f:w #3 \s__fp_stop
13641     \exp_after:wN #4
13642     \exp_after:wN #1
13643   \fi:
13644 }

```



```

13645 \cs_new:Npn \__fp_ternary_loop_break:w
13646   #1 \fi: #2 \__fp_ternary_break_point:n #3
13647   {
13648     0 = 0 \exp_stop_f: \fi:
13649     \exp_after:wN \__fp_ternary_auxii:NwwN
13650   }
13651 \cs_new:Npn \__fp_ternary_loop:Nw \s__fp \__fp_chk:w #1#2;
13652   {
13653     \if_int_compare:w #1 > 0 \exp_stop_f:
13654     \exp_after:wN \__fp_ternary_map_break:
13655     \fi:
13656     \__fp_ternary_loop:Nw
13657   }
13658 \cs_new:Npn \__fp_ternary_map_break: #1 \__fp_ternary_break_point:n #2 {#2}
13659 \cs_new:Npn \__fp_ternary_auxi:NwwN #1#2@#3@#4
13660   {
13661     \exp_after:wN \__fp_parse_continue:NwN
13662     \exp_after:wN #1
13663     \exp:w \exp_end_continue_f:w
13664     \__fp_exp_after_array_f:w #2 \s__fp_stop
13665     #4 #1
13666   }
13667 \cs_new:Npn \__fp_ternary_auxii:NwwN #1#2@#3@#4
13668   {
13669     \exp_after:wN \__fp_parse_continue:NwN
13670     \exp_after:wN #1
13671     \exp:w \exp_end_continue_f:w
13672     \__fp_exp_after_array_f:w #3 \s__fp_stop
13673     #4 #1
13674   }

```

(End definition for __fp_ternary:NwwN and others.)

```
13675 </initex | package>
```

26 l3fp-basics Implementation

```
13676 <*initex | package>
```

```
13677 <@@=fp>
```

The l3fp-basics module implements addition, subtraction, multiplication, and division of two floating points, and the absolute value and sign-changing operations on one floating point. All operations implemented in this module yield the outcome of rounding the infinitely precise result of the operation to the nearest floating point.

Some algorithms used below end up being quite similar to some described in “What Every Computer Scientist Should Know About Floating Point Arithmetic”, by David Goldberg, which can be found at <http://cr.yp.to/2005-590/goldberg.pdf>.

Unary functions.

```

\__fp_parse_word_abs:N
\__fp_parse_word_sign:N
\__fp_parse_word_sqrt:N
13678 \cs_new:Npn \__fp_parse_word_abs:N
13679   { \__fp_parse_unary_function:NNN \__fp_set_sign_o:w 0 }
13680 \cs_new:Npn \__fp_parse_word_sign:N
13681   { \__fp_parse_unary_function:NNN \__fp_sign_o:w ? }
13682 \cs_new:Npn \__fp_parse_word_sqrt:N
13683   { \__fp_parse_unary_function:NNN \__fp_sqrt_o:w ? }

```

(End definition for `__fp_parse_word_abs:N`, `__fp_parse_word_sign:N`, and `__fp_parse_word_sqrt:N`.)

26.1 Addition and subtraction

We define here two functions, `__fp_-_o:ww` and `__fp+_o:ww`, which perform the subtraction and addition of their two floating point operands, and expand the tokens following the result once.

A more obscure function, `__fp_add_big_i_o:wNww`, is used in `l3fp-expo`.

The logic goes as follows:

- `__fp_-_o:ww` calls `__fp+_o:ww` to do the work, with the sign of the second operand flipped;
- `__fp+_o:ww` dispatches depending on the type of floating point, calling specialized auxiliaries;
- in all cases except summing two normal floating point numbers, we return one or the other operands depending on the signs, or detect an invalid operation in the case of $\infty - \infty$;
- for normal floating point numbers, compare the signs;
- to add two floating point numbers of the same sign or of opposite signs, shift the significand of the smaller one to match the bigger one, perform the addition or subtraction of significands, check for a carry, round, and pack using the `__fp-basics_pack_...` functions.

The trickiest part is to round correctly when adding or subtracting normal floating point numbers.

26.1.1 Sign, exponent, and special numbers

`__fp_-_o:ww` The `__fp+_o:ww` auxiliary has a hook: it takes one argument between the first `\s__fp` and `__fp_chk:w`, which is applied to the sign of the second operand. Positioning the hook there means that `__fp+_o:ww` can still perform the sanity check that it was followed by `\s__fp`.

```

13684 \cs_new:cpx { __fp_-_o:ww } \s__fp
13685 {
13686   \exp_not:c { __fp+_o:ww }
13687   \exp_not:n { \s__fp \__fp_neg_sign:N }
13688 }

```

(End definition for `__fp_-_o:ww`.)

`__fp+_o:ww` This function is either called directly with an empty `#1` to compute an addition, or it is called by `__fp_-_o:ww` with `__fp_neg_sign:N` as `#1` to compute a subtraction, in which case the second operand's sign should be changed. If the *<types>* `#2` and `#4` are the same, dispatch to case `#2` (0, 1, 2, or 3), where we call specialized functions: thanks to `__int_value:w`, those receive the tweaked *<sign₂>* (expansion of `#1#5`) as an argument. If the *<types>* are distinct, the result is simply the floating point number with the highest *<type>*. Since case 3 (used for two `nan`) also picks the first operand, we can also use it

when $\langle type_1 \rangle$ is greater than $\langle type_2 \rangle$. Also note that we don't need to worry about $\langle sign_2 \rangle$ in that case since the second operand is discarded.

```

13689 \cs_new:cpn { __fp+_o:ww }
13690 \s__fp #1 \__fp_chk:w #2 #3 ; \s__fp \__fp_chk:w #4 #5
13691 {
13692   \if_case:w
13693     \if_meaning:w #2 #4
13694     #2
13695   \else:
13696     \if_int_compare:w #2 > #4 \exp_stop_f:
13697     3
13698   \else:
13699     4
13700   \fi:
13701   \fi:
13702   \exp_stop_f:
13703     \exp_after:wN \__fp_add_zeros_o:Nww \__int_value:w
13704 \or: \exp_after:wN \__fp_add_normal_o:Nww \__int_value:w
13705 \or: \exp_after:wN \__fp_add_inf_o:Nww \__int_value:w
13706 \or: \__fp_case_return_i_o:ww
13707 \else: \exp_after:wN \__fp_add_return_ii_o:Nww \__int_value:w
13708 \fi:
13709 #1 #5
13710 \s__fp \__fp_chk:w #2 #3 ;
13711 \s__fp \__fp_chk:w #4 #5
13712 }

```

(End definition for $\backslash_fp_+_o:ww$.)

$\backslash_fp_add_return_ii_o:Nww$ Ignore the first operand, and return the second, but using the sign #1 rather than #4. As usual, expand after the floating point.

```

13713 \cs_new:Npn \__fp_add_return_ii_o:Nww #1 #2 ; \s__fp \__fp_chk:w #3 #4
13714 { \__fp_exp_after_o:w \s__fp \__fp_chk:w #3 #1 }

```

(End definition for $\backslash_fp_add_return_ii_o:Nww$.)

$\backslash_fp_add_zeros_o:Nww$ Adding two zeros yields $\backslash c_zero_fp$, except if both zeros were -0 .

```

13715 \cs_new:Npn \__fp_add_zeros_o:Nww #1 \s__fp \__fp_chk:w 0 #2
13716 {
13717   \if_int_compare:w #2 #1 = 20 \exp_stop_f:
13718     \exp_after:wN \__fp_add_return_ii_o:Nww
13719   \else:
13720     \__fp_case_return_i_o:ww
13721   \fi:
13722   #1
13723   \s__fp \__fp_chk:w 0 #2
13724 }

```

(End definition for $\backslash_fp_add_zeros_o:Nww$.)

$\backslash_fp_add_inf_o:Nww$ If both infinities have the same sign, just return that infinity, otherwise, it is an invalid operation. We find out if that invalid operation is an addition or a subtraction by testing whether the tweaked $\langle sign_2 \rangle$ (#1) and the $\langle sign_2 \rangle$ (#4) are identical.

```

13725 \cs_new:Npn \__fp_add_inf_o:Nww

```

```

13726     #1 \s__fp \__fp_chk:w 2 #2 #3; \s__fp \__fp_chk:w 2 #4
13727   {
13728     \if_meaning:w #1 #2
13729     \__fp_case_return_i_o:ww
13730   \else:
13731     \__fp_case_use:nw
13732     {
13733       \exp_last_unbraced:Nf \__fp_invalid_operation_o:Nww
13734       { \token_if_eq_meaning:NNTF #1 #4 + - }
13735     }
13736   \fi:
13737   \s__fp \__fp_chk:w 2 #2 #3;
13738   \s__fp \__fp_chk:w 2 #4
13739 }

```

(End definition for __fp_add_inf_o:Nww.)

```

\__fp_add_normal_o:Nww \__fp_add_normal_o:Nww <sign2> \s__fp \__fp_chk:w 1 <sign1> <exp1>
<body1> ; \s__fp \__fp_chk:w 1 <initial sign2> <exp2> <body2> ;

```

We now have two normal numbers to add, and we have to check signs and exponents more carefully before performing the addition.

```

13740 \cs_new:Npn \__fp_add_normal_o:Nww #1 \s__fp \__fp_chk:w 1 #2
13741 {
13742   \if_meaning:w #1#2
13743   \exp_after:wN \__fp_add_npos_o:NnwNnw
13744 \else:
13745   \exp_after:wN \__fp_sub_npos_o:NnwNnw
13746 \fi:
13747   #2
13748 }

```

(End definition for __fp_add_normal_o:Nww.)

26.1.2 Absolute addition

In this subsection, we perform the addition of two positive normal numbers.

```

\__fp_add_npos_o:NnwNnw \__fp_add_npos_o:NnwNnw <sign1> <exp1> <body1> ; \s__fp \__fp_chk:w 1
<initial sign2> <exp2> <body2> ;

```

Since we are doing an addition, the final sign is $\langle sign_1 \rangle$. Start an $\backslash_int_eval:w$, responsible for computing the exponent: the result, and the $\langle final\ sign \rangle$ are then given to $\backslash_fp_sanitize:Nw$ which checks for overflow. The exponent is computed as the largest exponent #2 or #5, incremented if there is a carry. To add the significands, we decimate the smaller number by the difference between the exponents. This is done by $\backslash_fp_add_big_i:wNww$ or $\backslash_fp_add_big_ii:wNww$. We need to bring the final sign with us in the midst of the calculation to round properly at the end.

```

13749 \cs_new:Npn \__fp_add_npos_o:NnwNnw #1#2#3 ; \s__fp \__fp_chk:w 1 #4 #5
13750 {
13751   \exp_after:wN \__fp_sanitize:Nw
13752   \exp_after:wN #1
13753   \__int_value:w \__int_eval:w
13754   \if_int_compare:w #2 > #5 \exp_stop_f:
13755     #2

```

```

13756     \exp_after:wN \_fp_add_big_i_o:wNww \_int_value:w -
13757     \else:
13758         #5
13759         \exp_after:wN \_fp_add_big_ii_o:wNww \_int_value:w
13760     \fi:
13761     \_int_eval:w #5 - #2 ; #1 #3;
13762 }

```

(End definition for _fp_add_npos_o:NnwNnw.)

_fp_add_big_i_o:wNww _fp_add_big_i_o:wNww $\langle shift \rangle$; $\langle final\ sign \rangle$ $\langle body_1 \rangle$; $\langle body_2 \rangle$;
_fp_add_big_ii_o:wNww Used in l3fp-expo. Shift the significand of the small number, then add with _fp-add_significand_o:NnnwnnnnN.

```

13763 \cs_new:Npn \_fp_add_big_i_o:wNww #1; #2 #3; #4;
13764 {
13765     \_fp_decimate:nNnnnn {#1}
13766     \_fp_add_significand_o:NnnwnnnnN
13767     #4
13768     #3
13769     #2
13770 }
13771 \cs_new:Npn \_fp_add_big_ii_o:wNww #1; #2 #3; #4;
13772 {
13773     \_fp_decimate:nNnnnn {#1}
13774     \_fp_add_significand_o:NnnwnnnnN
13775     #3
13776     #4
13777     #2
13778 }

```

(End definition for _fp_add_big_i_o:wNww and _fp_add_big_ii_o:wNww.)

_fp_add_significand_o:NnnwnnnnN _fp_add_significand_o:NnnwnnnnN $\langle rounding\ digit \rangle$ $\{ \langle Y'_1 \rangle \}$ $\{ \langle Y'_2 \rangle \}$
_fp_add_significand_pack:NNNNNNN $\langle extra-digits \rangle$; $\{ \langle X_1 \rangle \}$ $\{ \langle X_2 \rangle \}$ $\{ \langle X_3 \rangle \}$ $\{ \langle X_4 \rangle \}$ $\langle final\ sign \rangle$
_fp_add_significand_test_o:N

To round properly, we must know at which digit the rounding should occur. This requires to know whether the addition produces an overall carry or not. Thus, we do the computation now and check for a carry, then go back and do the rounding. The rounding may cause a carry in very rare cases such as $0.99 \dots 95 \rightarrow 1.00 \dots 0$, but this situation always give an exact power of 10, for which it is easy to correct the result at the end.

```

13779 \cs_new:Npn \_fp_add_significand_o:NnnwnnnnN #1 #2#3 #4; #5#6#7#8
13780 {
13781     \exp_after:wN \_fp_add_significand_test_o:N
13782     \_int_value:w \_int_eval:w 1#5#6 + #2
13783     \exp_after:wN \_fp_add_significand_pack:NNNNNNN
13784     \_int_value:w \_int_eval:w 1#7#8 + #3 ; #1
13785 }
13786 \cs_new:Npn \_fp_add_significand_pack:NNNNNNN #1 #2#3#4#5#6#7
13787 {
13788     \if_meaning:w 2 #1
13789     + 1
13790     \fi:
13791     ; #2 #3 #4 #5 #6 #7 ;
13792 }
13793 \cs_new:Npn \_fp_add_significand_test_o:N #1

```

```

13794 {
13795     \if_meaning:w 2 #1
13796     \exp_after:wN \__fp_add_significand_carry_o:wwwNN
13797     \else:
13798     \exp_after:wN \__fp_add_significand_no_carry_o:wwwNN
13799     \fi:
13800 }

```

(End definition for __fp_add_significand_o:NnnwnnnN, __fp_add_significand_pack:NNNNNN, and __fp_add_significand_test_o:N.)

__fp_add_significand_no_carry_o:wwwNN $\langle 8d \rangle$; $\langle 6d \rangle$; $\langle 2d \rangle$; $\langle \text{rounding digit} \rangle$ $\langle \text{sign} \rangle$

If there's no carry, grab all the digits again and round. The packing function __fp_basics_pack_high:NNNNNw takes care of the case where rounding brings a carry.

```

13801 \cs_new:Npn \__fp_add_significand_no_carry_o:wwwNN
13802     #1; #2; #3#4 ; #5#6
13803 {
13804     \exp_after:wN \__fp_basics_pack_high:NNNNNw
13805     \__int_value:w \__int_eval:w 1 #1
13806     \exp_after:wN \__fp_basics_pack_low:NNNNNw
13807     \__int_value:w \__int_eval:w 1 #2 #3#4
13808     + \__fp_round:NNN #6 #4 #5
13809     \exp_after:wN ;
13810 }

```

(End definition for __fp_add_significand_no_carry_o:wwwNN.)

__fp_add_significand_carry_o:wwwNN $\langle 8d \rangle$; $\langle 6d \rangle$; $\langle 2d \rangle$; $\langle \text{rounding digit} \rangle$ $\langle \text{sign} \rangle$

The case where there is a carry is very similar. Rounding can even raise the first digit from 1 to 2, but we don't care.

```

13811 \cs_new:Npn \__fp_add_significand_carry_o:wwwNN
13812     #1; #2; #3#4; #5#6
13813 {
13814     + 1
13815     \exp_after:wN \__fp_basics_pack_weird_high:NNNNNNNNw
13816     \__int_value:w \__int_eval:w 1 1 #1
13817     \exp_after:wN \__fp_basics_pack_weird_low:NNNNNw
13818     \__int_value:w \__int_eval:w 1 #2#3 +
13819     \exp_after:wN \__fp_round:NNN
13820     \exp_after:wN #6
13821     \exp_after:wN #3
13822     \__int_value:w \__fp_round_digit:Nw #4 #5 ;
13823     \exp_after:wN ;
13824 }

```

(End definition for __fp_add_significand_carry_o:wwwNN.)

26.1.3 Absolute subtraction

__fp_sub_npos_o:NnwNnw $\langle \text{sign}_1 \rangle$ $\langle \text{exp}_1 \rangle$ $\langle \text{body}_1 \rangle$; \s__fp __fp_chk:w 1
 __fp_sub_eq_o:Nnwnw $\langle \text{initial sign}_2 \rangle$ $\langle \text{exp}_2 \rangle$ $\langle \text{body}_2 \rangle$;
 __fp_sub_npos_ii_o:Nnwnw

Rounding properly in some modes requires to know what the sign of the result will be. Thus, we start by comparing the exponents and significands. If the numbers coincide, return zero. If the second number is larger, swap the numbers and call `__fp_sub_npos_i_o:Nnwnw` with the opposite of $\langle sign_1 \rangle$.

```

13825 \cs_new:Npn \__fp_sub_npos_o:NnwNnw #1#2#3; \s__fp \__fp_chk:w 1 #4#5#6;
13826 {
13827   \if_case:w \__fp_compare_npos:nwnw {#2} #3; {#5} #6; \exp_stop_f:
13828     \exp_after:wN \__fp_sub_eq_o:Nnwnw
13829   \or:
13830     \exp_after:wN \__fp_sub_npos_i_o:Nnwnw
13831   \else:
13832     \exp_after:wN \__fp_sub_npos_ii_o:Nnwnw
13833   \fi:
13834   #1 {#2} #3; {#5} #6;
13835 }
13836 \cs_new:Npn \__fp_sub_eq_o:Nnwnw #1#2; #3; { \exp_after:wN \c_zero_fp }
13837 \cs_new:Npn \__fp_sub_npos_ii_o:Nnwnw #1 #2; #3;
13838 {
13839   \exp_after:wN \__fp_sub_npos_i_o:Nnwnw
13840   \__int_value:w \__fp_neg_sign:N #1
13841   #3; #2;
13842 }

```

(End definition for `__fp_sub_npos_o:NnwNnw`, `__fp_sub_eq_o:Nnwnw`, and `__fp_sub_npos_ii_o:Nnwnw`.)

`__fp_sub_npos_i_o:Nnwnw`

After the computation is done, `__fp_sanitizew` checks for overflow/underflow. It expects the $\langle final\ sign \rangle$ and the $\langle exponent \rangle$ (delimited by ;). Start an integer expression for the exponent, which starts with the exponent of the largest number, and may be decreased if the two numbers are very close. If the two numbers have the same exponent, call the **near** auxiliary. Otherwise, decimate y , then call the **far** auxiliary to evaluate the difference between the two significands. Note that we decimate by 1 less than one could expect.

```

13843 \cs_new:Npn \__fp_sub_npos_i_o:Nnwnw #1 #2#3; #4#5;
13844 {
13845   \exp_after:wN \__fp_sanitizew
13846   \exp_after:wN #1
13847   \__int_value:w \__int_eval:w
13848   #2
13849   \if_int_compare:w #2 = #4 \exp_stop_f:
13850     \exp_after:wN \__fp_sub_back_near_o:nnnnnnnnN
13851   \else:
13852     \exp_after:wN \__fp_decimate:nNnnnn \exp_after:wN
13853     { \__int_value:w \__int_eval:w #2 - #4 - 1 \exp_after:wN }
13854     \exp_after:wN \__fp_sub_back_far_o:NnnwnnnnnN
13855   \fi:
13856   #5
13857   #3
13858   #1
13859 }

```

(End definition for `__fp_sub_npos_i_o:Nnwnw`.)

`__fp_sub_back_near_o:nnnnnnnnN`
`__fp_sub_back_near_pack:NNNNNNw`
`__fp_sub_back_near_after:wNNNNw`

`__fp_sub_back_near_o:nnnnnnnnN` $\{\langle Y_1 \rangle\} \{\langle Y_2 \rangle\} \{\langle Y_3 \rangle\} \{\langle Y_4 \rangle\} \{\langle X_1 \rangle\}$
 $\{\langle X_2 \rangle\} \{\langle X_3 \rangle\} \{\langle X_4 \rangle\} \langle final\ sign \rangle$

In this case, the subtraction is exact, so we discard the *final sign* #9. The very large shifts of 10^9 and $1.1 \cdot 10^9$ are unnecessary here, but allow the auxiliaries to be reused later. Each integer expression produces a 10 digit result. If the resulting 16 digits start with a 0, then we need to shift the group, padding with trailing zeros.

```

13860 \cs_new:Npn \__fp_sub_back_near_o:nnnnnnnnN #1#2#3#4 #5#6#7#8 #9
13861 {
13862   \exp_after:wN \__fp_sub_back_near_after:wNNNNw
13863   \__int_value:w \__int_eval:w 10#5#6 - #1#2 - 11
13864   \exp_after:wN \__fp_sub_back_near_pack:NNNNNNw
13865   \__int_value:w \__int_eval:w 11#7#8 - #3#4 \exp_after:wN ;
13866 }
13867 \cs_new:Npn \__fp_sub_back_near_pack:NNNNNNw #1#2#3#4#5#6#7 ;
13868 { + #1#2 ; {#3#4#5#6} {#7} ; }
13869 \cs_new:Npn \__fp_sub_back_near_after:wNNNNw 10 #1#2#3#4 #5 ;
13870 {
13871   \if_meaning:w 0 #1
13872   \exp_after:wN \__fp_sub_back_shift:wnnnn
13873   \fi:
13874   ; {#1#2#3#4} {#5}
13875 }

```

(End definition for `__fp_sub_back_near_o:nnnnnnnnN`, `__fp_sub_back_near_pack:NNNNNNw`, and `__fp_sub_back_near_after:wNNNNw`.)

```

\__fp_sub_back_shift:wnnnn
\__fp_sub_back_shift_ii:ww
  \fp_sub_back_shift_iii:NNNNNNNNw
    \fp_sub_back_shift_iv:nnnnw

```

`__fp_sub_back_shift:wnnnn` ; $\{ \langle Z_1 \rangle \} \{ \langle Z_2 \rangle \} \{ \langle Z_3 \rangle \} \{ \langle Z_4 \rangle \}$;
This function is called with $\langle Z_1 \rangle \leq 999$. Act with `\number` to trim leading zeros from $\langle Z_1 \rangle \langle Z_2 \rangle$ (we don't do all four blocks at once, since non-zero blocks would then overflow \TeX 's integers). If the first two blocks are zero, the auxiliary receives an empty #1 and trims #2#30 from leading zeros, yielding a total shift between 7 and 16 to the exponent. Otherwise we get the shift from #1 alone, yielding a result between 1 and 6. Once the exponent is taken care of, trim leading zeros from #1#2#3 (when #1 is empty, the space before #2#3 is ignored), get four blocks of 4 digits and finally clean up. Trailing zeros are added so that digits can be grabbed safely.

```

13876 \cs_new:Npn \__fp_sub_back_shift:wnnnn ; #1#2
13877 {
13878   \exp_after:wN \__fp_sub_back_shift_ii:ww
13879   \__int_value:w #1 #2 0 ;
13880 }
13881 \cs_new:Npn \__fp_sub_back_shift_ii:ww #1 0 ; #2#3 ;
13882 {
13883   \if_meaning:w @ #1 @
13884   - 7
13885   - \exp_after:wN \use_i:nnn
13886   \exp_after:wN \__fp_sub_back_shift_iii:NNNNNNNNw
13887   \__int_value:w #2#3 0 ~ 123456789;
13888   \else:
13889   - \__fp_sub_back_shift_iii:NNNNNNNNw #1 123456789;
13890   \fi:
13891   \exp_after:wN \__fp_pack_twice_four:wNNNNNNNN
13892   \exp_after:wN \__fp_pack_twice_four:wNNNNNNNN
13893   \exp_after:wN \__fp_sub_back_shift_iv:nnnnw
13894   \exp_after:wN ;
13895   \__int_value:w

```



```

13896      #1 ~ #2#3 0 ~ 0000 0000 0000 000 ;
13897    }
13898    \cs_new:Npn \__fp_sub_back_shift_iii:NNNNNNNNw #1#2#3#4#5#6#7#8#9; {#8}
13899    \cs_new:Npn \__fp_sub_back_shift_iv:nnnnw #1 ; #2 ; { ; #1 ; }

```

(End definition for __fp_sub_back_shift:wnnnn and others.)

```

\__fp_sub_back_far_o:NnnwnnnnN      \__fp_sub_back_far_o:NnnwnnnnN <rounding> {\langle Y'_1 \rangle} {\langle Y'_2 \rangle}
<extra-digits> ; {\langle X_1 \rangle} {\langle X_2 \rangle} {\langle X_3 \rangle} {\langle X_4 \rangle} <final sign>

```

If the difference is greater than $10^{\langle expo_x \rangle}$, call the `very_far` auxiliary. If the result is less than $10^{\langle expo_x \rangle}$, call the `not_far` auxiliary. If it is too close to know yet, namely if $1\langle Y'_1 \rangle\langle Y'_2 \rangle = \langle X_1 \rangle\langle X_2 \rangle\langle X_3 \rangle\langle X_4 \rangle 0$, then call the `quite_far` auxiliary. We use the odd combination of space and semi-colon delimiters to allow the `not_far` auxiliary to grab each piece individually, the `very_far` auxiliary to use `__fp_pack_eight:wNNNNNNNN`, and the `quite_far` to ignore the significands easily (using the `;` delimiter).

```

13900    \cs_new:Npn \__fp_sub_back_far_o:NnnwnnnnN #1 #2#3 #4; #5#6#7#8
13901    {
13902      \if_case:w
13903        \if_int_compare:w 1 #2 = #5#6 \use_i:nnnn #7 \exp_stop_f:
13904        \if_int_compare:w #3 = \use_none:n #7#8 0 \exp_stop_f:
13905        0
13906      \else:
13907        \if_int_compare:w #3 > \use_none:n #7#8 0 - \fi: 1
13908      \fi:
13909      \else:
13910        \if_int_compare:w 1 #2 > #5#6 \use_i:nnnn #7 - \fi: 1
13911      \fi:
13912      \exp_stop_f:
13913        \exp_after:wN \__fp_sub_back_quite_far_o:wwNN
13914      \or: \exp_after:wN \__fp_sub_back_very_far_o:wwwNN
13915      \else: \exp_after:wN \__fp_sub_back_not_far_o:wwwNN
13916      \fi:
13917      #2 ~ #3 ; #5 #6 ~ #7 #8 ; #1
13918    }

```

(End definition for __fp_sub_back_far_o:NnnwnnnnN.)

```

\__fp_sub_back_quite_far_o:wwNN
\__fp_sub_back_quite_far_ii:NN

```

The easiest case is when $x - y$ is extremely close to a power of 10, namely the first digit of x is 1, and all others vanish when subtracting y . Then the `<rounding> #3` and the `<final sign> #4` control whether we get 1 or 0.9999999999999999. In the usual round-to-nearest mode, we get 1 whenever the `<rounding>` digit is less than or equal to 5 (remember that the `<rounding>` digit is only equal to 5 if there was no further non-zero digit).

```

13919    \cs_new:Npn \__fp_sub_back_quite_far_o:wwNN #1; #2; #3#4
13920    {
13921      \exp_after:wN \__fp_sub_back_quite_far_ii:NN
13922      \exp_after:wN #3
13923      \exp_after:wN #4
13924    }
13925    \cs_new:Npn \__fp_sub_back_quite_far_ii:NN #1#2
13926    {
13927      \if_case:w \__fp_round_neg:NNN #2 0 #1
13928      \exp_after:wN \use_i:nn
13929      \else:
13930      \exp_after:wN \use_ii:nn

```

```

13931 \fi:
13932 { ; {1000} {0000} {0000} {0000} ; }
13933 { - 1 ; {9999} {9999} {9999} {9999} ; }
13934 }

```

(End definition for `__fp_sub_back_quite_far_o:wwwNN` and `__fp_sub_back_quite_far_ii:NN`.)

`__fp_sub_back_not_far_o:wwwNN`

In the present case, x and y have different exponents, but y is large enough that $x - y$ has a smaller exponent than x . Decrement the exponent (with `-1`). Then proceed in a way similar to the `near` auxiliaries seen earlier, but multiplying x by 10 (`#30` and `#40` below), and with the added quirk that the *rounding* digit has to be taken into account. Namely, we may have to decrease the result by one unit if `__fp_round_neg:NNN` returns 1. This function expects the *final sign* `#6`, the last digit of `1100000000+#40-#2`, and the *rounding* digit. Instead of redoing the computation for the second argument, we note that `__fp_round_neg:NNN` only cares about its parity, which is identical to that of the last digit of `#2`.

```

13935 \cs_new:Npn \__fp_sub_back_not_far_o:wwwNN #1 ~ #2; #3 ~ #4; #5#6
13936 {
13937   - 1
13938   \exp_after:wN \__fp_sub_back_near_after:wNNNNw
13939   \__int_value:w \__int_eval:w 1#30 - #1 - 11
13940   \exp_after:wN \__fp_sub_back_near_pack:NNNNNNw
13941   \__int_value:w \__int_eval:w 11 0000 0000 + #40 - #2
13942   - \exp_after:wN \__fp_round_neg:NNN
13943   \exp_after:wN #6
13944   \use_none:n nnnnnnn #2 #5
13945   \exp_after:wN ;
13946 }

```

(End definition for `__fp_sub_back_not_far_o:wwwNN`.)

`__fp_sub_back_very_far_o:wwwNN`
`__fp_sub_back_very_far_ii_o:nnNwwNN`

The case where $x - y$ and x have the same exponent is a bit more tricky, mostly because it cannot reuse the same auxiliaries. Shift the y significand by adding a leading 0. Then the logic is similar to the `not_far` functions above. Rounding is a bit more complicated: we have two *rounding* digits `#3` and `#6` (from the decimation, and from the new shift) to take into account, and getting the parity of the main result requires a computation. The first `__int_value:w` triggers the second one because the number is unfinished; we can thus not use 0 in place of 2 there.

```

13947 \cs_new:Npn \__fp_sub_back_very_far_o:wwwNN #1#2#3#4#5#6#7
13948 {
13949   \__fp_pack_eight:wNNNNNNNN
13950   \__fp_sub_back_very_far_ii_o:nnNwwNN
13951   { 0 #1#2#3 #4#5#6#7 }
13952   ;
13953 }
13954 \cs_new:Npn \__fp_sub_back_very_far_ii_o:nnNwwNN #1#2 ; #3 ; #4 ~ #5; #6#7
13955 {
13956   \exp_after:wN \__fp_basics_pack_high:NNNNNw
13957   \__int_value:w \__int_eval:w 1#4 - #1 - 1
13958   \exp_after:wN \__fp_basics_pack_low:NNNNNw
13959   \__int_value:w \__int_eval:w 2#5 - #2
13960   - \exp_after:wN \__fp_round_neg:NNN
13961   \exp_after:wN #7

```

```

13962         \__int_value:w
13963         \if_int_odd:w \__int_eval:w #5 - #2 \__int_eval_end:
13964             1 \else: 2 \fi:
13965         \__int_value:w \__fp_round_digit:Nw #3 #6 ;
13966     \exp_after:wN ;
13967 }

```

(End definition for __fp_sub_back_very_far_o:wwwNN and __fp_sub_back_very_far_ii_o:nnNwwNN.)

26.2 Multiplication

26.2.1 Signs, and special numbers

__fp*_o:ww We go through an auxiliary, which is common with __fp/_o:ww. The first argument is the operation, used for the invalid operation exception. The second is inserted in a formula to dispatch cases slightly differently between multiplication and division. The third is the operation for normal floating points. The fourth is there for extra cases needed in __fp/_o:ww.

```

13968 \cs_new:cpn { __fp*_o:ww }
13969 {
13970     \__fp_mul_cases_o:NnNww
13971     *
13972     { - 2 + }
13973     \__fp_mul_npos_o:Nww
13974     { }
13975 }

```

(End definition for __fp*_o:ww.)

__fp_mul_cases_o:nNnww Split into 10 cases (12 for division). If both numbers are normal, go to case 0 (same sign) or case 1 (opposite signs): in both cases, call __fp_mul_npos_o:Nww to do the work. If the first operand is `nan`, go to case 2, in which the second operand is discarded; if the second operand is `nan`, go to case 3, in which the first operand is discarded (note the weird interaction with the final test on signs). Then we separate the case where the first number is normal and the second is zero: this goes to cases 4 and 5 for multiplication, 10 and 11 for division. Otherwise, we do a computation which dispatches the products $0 \times 0 = 0 \times 1 = 1 \times 0 = 0$ to case 4 or 5 depending on the combined sign, the products $0 \times \infty$ and $\infty \times 0$ to case 6 or 7 (invalid operation), and the products $1 \times \infty = \infty \times 1 = \infty \times \infty = \infty$ to cases 8 and 9. Note that the code for these two cases (which return $\pm\infty$) is inserted as argument #4, because it differs in the case of divisions.

```

13976 \cs_new:Npn \__fp_mul_cases_o:NnNww
13977     #1#2#3#4 \s__fp \__fp_chk:w #5#6#7; \s__fp \__fp_chk:w #8#9
13978 {
13979     \if_case:w \__int_eval:w
13980         \if_int_compare:w #5 #8 = 11 ~
13981             1
13982         \else:
13983             \if_meaning:w 3 #8
13984                 3
13985             \else:
13986                 \if_meaning:w 3 #5
13987                     2
13988             \else:

```

```

13989         \if_int_compare:w #5 #8 = 10 ~
13990             9 #2 - 2
13991         \else:
13992             (#5 #2 #8) / 2 * 2 + 7
13993         \fi:
13994     \fi:
13995 \fi:
13996 \fi:
13997     \if_meaning:w #6 #9 - 1 \fi:
13998 \__int_eval_end:
13999     \__fp_case_use:nw { #3 0 }
14000 \or: \__fp_case_use:nw { #3 2 }
14001 \or: \__fp_case_return_i_o:ww
14002 \or: \__fp_case_return_ii_o:ww
14003 \or: \__fp_case_return_o:Nww \c_zero_fp
14004 \or: \__fp_case_return_o:Nww \c_minus_zero_fp
14005 \or: \__fp_case_use:nw { \__fp_invalid_operation_o:Nww #1 }
14006 \or: \__fp_case_use:nw { \__fp_invalid_operation_o:Nww #1 }
14007 \or: \__fp_case_return_o:Nww \c_inf_fp
14008 \or: \__fp_case_return_o:Nww \c_minus_inf_fp
14009 #4
14010 \fi:
14011 \s__fp \__fp_chk:w #5 #6 #7;
14012 \s__fp \__fp_chk:w #8 #9
14013 }

```

(End definition for __fp_mul_cases_o:nNnnww.)

26.2.2 Absolute multiplication

In this subsection, we perform the multiplication of two positive normal numbers.

```

\__fp_mul_npos_o:Nww     \__fp_mul_npos_o:Nww <final sign> \s__fp \__fp_chk:w 1 <sign1> {<exp1>}
                          <body1> ; \s__fp \__fp_chk:w 1 <sign2> {<exp2>} <body2> ;

```

After the computation, __fp_sanitizew checks for overflow or underflow. As we did for addition, __int_eval:w computes the exponent, catching any shift coming from the computation in the significand. The <final sign> is needed to do the rounding properly in the significand computation. We setup the post-expansion here, triggered by __fp_mul_significand_o:nnnnNnnnn.

This is also used in l3fp-convert.

```

14014 \cs_new:Npn \__fp_mul_npos_o:Nww
14015     #1 \s__fp \__fp_chk:w #2 #3 #4 #5 ; \s__fp \__fp_chk:w #6 #7 #8 #9 ;
14016 {
14017     \exp_after:wN \__fp_sanitizew
14018     \exp_after:wN #1
14019     \__int_value:w \__int_eval:w
14020     #4 + #8
14021     \__fp_mul_significand_o:nnnnNnnnn #5 #1 #9
14022 }

```

(End definition for __fp_mul_npos_o:Nww.)

```

\__fp_mul_significand_o:nnnnNnnnn     \__fp_mul_significand_o:nnnnNnnnn {<X1>} {<X2>} {<X3>} {<X4>} <sign>
\__fp_mul_significand_drop:NNNNNw     {<Y1>} {<Y2>} {<Y3>} {<Y4>}
\__fp_mul_significand_keep:NNNNNw

```

Note the three semicolons at the end of the definition. One is for the last `__fp_mul_significand_drop:NNNNNw`; one is for `__fp_round_digit:Nw` later on; and one, preceded by `\exp_after:wN`, which is correctly expanded (within an `__int_eval:w`), is used by `__fp_basics_pack_low:NNNNNw`.

The product of two 16 digit integers has 31 or 32 digits, but it is impossible to know which one before computing. The place where we round depends on that number of digits, and may depend on all digits until the last in some rare cases. The approach is thus to compute the 5 first blocks of 4 digits (the first one is between 100 and 9999 inclusive), and a compact version of the remaining 3 blocks. Afterwards, the number of digits is known, and we can do the rounding within yet another set of `__int_eval:w`.

```

14023 \cs_new:Npn \__fp_mul_significand_o:nnnnNnnnn #1#2#3#4 #5 #6#7#8#9
14024 {
14025   \exp_after:wN \__fp_mul_significand_test_f:NNN
14026   \exp_after:wN #5
14027   \__int_value:w \__int_eval:w 99990000 + #1*#6 +
14028   \exp_after:wN \__fp_mul_significand_keep:NNNNNw
14029   \__int_value:w \__int_eval:w 99990000 + #1*#7 + #2*#6 +
14030   \exp_after:wN \__fp_mul_significand_keep:NNNNNw
14031   \__int_value:w \__int_eval:w 99990000 + #1*#8 + #2*#7 + #3*#6 +
14032   \exp_after:wN \__fp_mul_significand_drop:NNNNNw
14033   \__int_value:w \__int_eval:w 99990000 + #1*#9 + #2*#8 + #3*#7 + #4*#6 +
14034   \exp_after:wN \__fp_mul_significand_drop:NNNNNw
14035   \__int_value:w \__int_eval:w 99990000 + #2*#9 + #3*#8 + #4*#7 +
14036   \exp_after:wN \__fp_mul_significand_drop:NNNNNw
14037   \__int_value:w \__int_eval:w 99990000 + #3*#9 + #4*#8 +
14038   \exp_after:wN \__fp_mul_significand_drop:NNNNNw
14039   \__int_value:w \__int_eval:w 100000000 + #4*#9 ;
14040   ; \exp_after:wN ;
14041 }
14042 \cs_new:Npn \__fp_mul_significand_drop:NNNNNw #1#2#3#4#5 #6;
14043 { #1#2#3#4#5 ; + #6 }
14044 \cs_new:Npn \__fp_mul_significand_keep:NNNNNw #1#2#3#4#5 #6;
14045 { #1#2#3#4#5 ; #6 ; }

```

(End definition for `__fp_mul_significand_o:nnnnNnnnn`, `__fp_mul_significand_drop:NNNNNw`, and `__fp_mul_significand_keep:NNNNNw`.)

```

\__fp_mul_significand_test_f:NNN \__fp_mul_significand_test_f:NNN <sign> 1 <digits 1-8> ; <digits 9-12> ;
<digits 13-16> ; + <digits 17-20> + <digits 21-24> + <digits 25-28> + <digits
29-32> ; \exp_after:wN ;

```

If the *<digit 1>* is non-zero, then for rounding we only care about the digits 16 and 17, and whether further digits are zero or not (check for exact ties). On the other hand, if *<digit 1>* is zero, we care about digits 17 and 18, and whether further digits are zero.

```

14046 \cs_new:Npn \__fp_mul_significand_test_f:NNN #1 #2 #3
14047 {
14048   \if_meaning:w 0 #3
14049   \exp_after:wN \__fp_mul_significand_small_f:NNwwwN
14050   \else:
14051   \exp_after:wN \__fp_mul_significand_large_f:NwwNNNN
14052   \fi:
14053   #1 #3
14054 }

```

(End definition for `_fp_mul_significand_test_f:NNN`.)

`_fp_mul_significand_large_f:NwwNNNN` In this branch, $\langle digit\ 1 \rangle$ is non-zero. The result is thus $\langle digits\ 1-16 \rangle$, plus some rounding which depends on the digits 16, 17, and whether all subsequent digits are zero or not. Here, `_fp_round_digit:Nw` takes digits 17 and further (as an integer expression), and replaces it by a $\langle rounding\ digit \rangle$, suitable for `_fp_round:NNN`.

```

14055 \cs_new:Npn \_fp_mul_significand_large_f:NwwNNNN #1 #2; #3; #4#5#6#7; +
14056   {
14057     \exp_after:wN \_fp_basics_pack_high:NNNNNw
14058     \_int_value:w \_int_eval:w 1#2
14059     \exp_after:wN \_fp_basics_pack_low:NNNNNw
14060     \_int_value:w \_int_eval:w 1#3#4#5#6#7
14061     + \exp_after:wN \_fp_round:NNN
14062     \exp_after:wN #1
14063     \exp_after:wN #7
14064     \_int_value:w \_fp_round_digit:Nw
14065   }

```

(End definition for `_fp_mul_significand_large_f:NwwNNNN`.)

`_fp_mul_significand_small_f:NNwwN` In this branch, $\langle digit\ 1 \rangle$ is zero. Our result is thus $\langle digits\ 2-17 \rangle$, plus some rounding which depends on the digits 17, 18, and whether all subsequent digits are zero or not. The 8 digits 1#3 are followed, after expansion of the `small_pack` auxiliary, by the next digit, to form a 9 digit number.

```

14066 \cs_new:Npn \_fp_mul_significand_small_f:NNwwN #1 #2#3; #4#5; #6; + #7
14067   {
14068     - 1
14069     \exp_after:wN \_fp_basics_pack_high:NNNNNw
14070     \_int_value:w \_int_eval:w 1#3#4
14071     \exp_after:wN \_fp_basics_pack_low:NNNNNw
14072     \_int_value:w \_int_eval:w 1#5#6#7
14073     + \exp_after:wN \_fp_round:NNN
14074     \exp_after:wN #1
14075     \exp_after:wN #7
14076     \_int_value:w \_fp_round_digit:Nw
14077   }

```

(End definition for `_fp_mul_significand_small_f:NNwwN`.)

26.3 Division

26.3.1 Signs, and special numbers

Time is now ripe to tackle the hardest of the four elementary operations: division.

`_fp/_o:ww` Filtering special floating point is very similar to what we did for multiplications, with a few variations. Invalid operation exceptions display `/` rather than `*`. In the formula for dispatch, we replace `- 2 +` by `-`. The case of normal numbers is treated using `_fp_div_npos_o:Nww` rather than `_fp_mul_npos_o:Nww`. There are two additional cases: if the first operand is normal and the second is a zero, then the division by zero exception is raised: cases 10 and 11 of the `\if_case:w` construction in `_fp_mul_cases_o:NnNww` are provided as the fourth argument here.

```

14078 \cs_new:cpn { \_fp/_o:ww }

```

```

14079 {
14080   \__fp_mul_cases_o:NnNnw
14081   /
14082   { - }
14083   \__fp_div_npos_o:Nww
14084   {
14085     \or:
14086     \__fp_case_use:nw
14087     { \__fp_division_by_zero_o:NNnw \c_inf_fp / }
14088     \or:
14089     \__fp_case_use:nw
14090     { \__fp_division_by_zero_o:NNnw \c_minus_inf_fp / }
14091   }
14092 }

```

(End definition for __fp_/_o:ww.)

```

\__fp_div_npos_o:Nww   \__fp_div_npos_o:Nww <final sign> \s__fp \__fp_chk:w 1 <sign_A> {<exp A>}
                        {<A_1>} {<A_2>} {<A_3>} {<A_4>} ; \s__fp \__fp_chk:w 1 <sign_Z> {<exp Z>}
                        {<Z_1>} {<Z_2>} {<Z_3>} {<Z_4>} ;

```

We want to compute A/Z . As for multiplication, `__fp_sanitizew` checks for overflow or underflow; we provide it with the $\langle final\ sign \rangle$, and an integer expression in which we compute the exponent. We set up the arguments of `__fp_div_significand_i_o:wnnw`, namely an integer $\langle y \rangle$ obtained by adding 1 to the first 5 digits of Z (explanation given soon below), then the four $\{A_i\}$, then the four $\{Z_i\}$, a semi-colon, and the $\langle final\ sign \rangle$, used for rounding at the end.

```

14093 \cs_new:Npn \__fp_div_npos_o:Nww
14094   #1 \s__fp \__fp_chk:w 1 #2 #3 #4 ; \s__fp \__fp_chk:w 1 #5 #6 #7#8#9;
14095 {
14096   \exp_after:wN \__fp_sanitizew
14097   \exp_after:wN #1
14098   \__int_value:w \__int_eval:w
14099   #3 - #6
14100   \exp_after:wN \__fp_div_significand_i_o:wnnw
14101   \__int_value:w \__int_eval:w #7 \use_i:nnnn #8 + 1 ;
14102   #4
14103   {#7}{#8}#9 ;
14104   #1
14105 }

```

(End definition for __fp_div_npos_o:Nww.)

26.3.2 Work plan

In this subsection, we explain how to avoid overflowing \TeX 's integers when performing the division of two positive normal numbers.

We are given two numbers, $A = 0.A_1A_2A_3A_4$ and $Z = 0.Z_1Z_2Z_3Z_4$, in blocks of 4 digits, and we know that the first digits of A_1 and of Z_1 are non-zero. To compute A/Z , we proceed as follows.

- Find an integer $Q_A \simeq 10^4 A/Z$.
- Replace A by $B = 10^4 A - Q_A Z$.

- Find an integer $Q_B \simeq 10^4 B/Z$.
- Replace B by $C = 10^4 B - Q_B Z$.
- Find an integer $Q_C \simeq 10^4 C/Z$.
- Replace C by $D = 10^4 C - Q_C Z$.
- Find an integer $Q_D \simeq 10^4 D/Z$.
- Consider $E = 10^4 D - Q_D Z$, and ensure correct rounding.

The result is then $Q = 10^{-4}Q_A + 10^{-8}Q_B + 10^{-12}Q_C + 10^{-16}Q_D + \text{rounding}$. Since the Q_i are integers, B , C , D , and E are all exact multiples of 10^{-16} , in other words, computing with 16 digits after the decimal separator yields exact results. The problem is the risk of overflow: in general B , C , D , and E may be greater than 1.

Unfortunately, things are not as easy as they seem. In particular, we want all intermediate steps to be positive, since negative results would require extra calculations at the end. This requires that $Q_A \leq 10^4 A/Z$ etc. A reasonable attempt would be to define Q_A as

$$\backslash\text{int_eval:n}\left\{\frac{A_1 A_2}{Z_1 + 1} - 1\right\} \leq 10^4 \frac{A}{Z}$$

Subtracting 1 at the end takes care of the fact that $\varepsilon\text{-TeX}$'s $\backslash_int_eval:w$ rounds divisions instead of truncating (really, $1/2$ would be sufficient, but we work with integers). We add 1 to Z_1 because $Z_1 \leq 10^4 Z < Z_1 + 1$ and we need Q_A to be an underestimate. However, we are now underestimating Q_A too much: it can be wrong by up to 100, for instance when $Z = 0.1$ and $A \simeq 1$. Then B could take values up to 10 (maybe more), and a few steps down the line, we would run into arithmetic overflow, since TeX can only handle integers less than roughly $2 \cdot 10^9$.

A better formula is to take

$$Q_A = \backslash\text{int_eval:n}\left\{\frac{10 \cdot A_1 A_2}{\lfloor 10^{-3} \cdot Z_1 Z_2 \rfloor + 1} - 1\right\}.$$

This is always less than $10^9 A/(10^5 Z)$, as we wanted. In words, we take the 5 first digits of Z into account, and the 8 first digits of A , using 0 as a 9-th digit rather than the true digit for efficiency reasons. We shall prove that using this formula to define all the Q_i avoids any overflow. For convenience, let us denote

$$y = \lfloor 10^{-3} \cdot Z_1 Z_2 \rfloor + 1,$$

so that, taking into account the fact that $\varepsilon\text{-TeX}$ rounds ties away from zero,

$$\begin{aligned} Q_A &= \left\lfloor \frac{A_1 A_2 0}{y} - \frac{1}{2} \right\rfloor \\ &> \frac{A_1 A_2 0}{y} - \frac{3}{2}. \end{aligned}$$

Note that $10^4 < y \leq 10^5$, and $999 \leq Q_A \leq 99989$. Also note that this formula does not cause an overflow as long as $A < (2^{31} - 1)/10^9 \simeq 2.147 \dots$, since the numerator involves an integer slightly smaller than $10^9 A$.

Let us bound B :

$$\begin{aligned}
10^5 B &= A_1 A_2 0 + 10 \cdot 0 \cdot A_3 A_4 - 10 \cdot Z_1 \cdot Z_2 Z_3 Z_4 \cdot Q_A \\
&< A_1 A_2 0 \cdot \left(1 - 10 \cdot \frac{Z_1 \cdot Z_2 Z_3 Z_4}{y}\right) + \frac{3}{2} \cdot 10 \cdot Z_1 \cdot Z_2 Z_3 Z_4 + 10 \\
&\leq \frac{A_1 A_2 0 \cdot (y - 10 \cdot Z_1 \cdot Z_2 Z_3 Z_4)}{y} + \frac{3}{2} y + 10 \\
&\leq \frac{A_1 A_2 0 \cdot 1}{y} + \frac{3}{2} y + 10 \leq \frac{10^9 A}{y} + 1.6 \cdot y.
\end{aligned}$$

At the last step, we hide 10 into the second term for later convenience. The same reasoning yields

$$\begin{aligned}
10^5 B &< 10^9 A/y + 1.6y, \\
10^5 C &< 10^9 B/y + 1.6y, \\
10^5 D &< 10^9 C/y + 1.6y, \\
10^5 E &< 10^9 D/y + 1.6y.
\end{aligned}$$

The goal is now to prove that none of B , C , D , and E can go beyond $(2^{31} - 1)/10^9 = 2.147 \dots$.

Combining the various inequalities together with $A < 1$, we get

$$\begin{aligned}
10^5 B &< 10^9/y + 1.6y, \\
10^5 C &< 10^{13}/y^2 + 1.6(y + 10^4), \\
10^5 D &< 10^{17}/y^3 + 1.6(y + 10^4 + 10^8/y), \\
10^5 E &< 10^{21}/y^4 + 1.6(y + 10^4 + 10^8/y + 10^{12}/y^2).
\end{aligned}$$

All of those bounds are convex functions of y (since every power of y involved is convex, and the coefficients are positive), and thus maximal at one of the end-points of the allowed range $10^4 < y \leq 10^5$. Thus,

$$\begin{aligned}
10^5 B &< \max(1.16 \cdot 10^5, 1.7 \cdot 10^5), \\
10^5 C &< \max(1.32 \cdot 10^5, 1.77 \cdot 10^5), \\
10^5 D &< \max(1.48 \cdot 10^5, 1.777 \cdot 10^5), \\
10^5 E &< \max(1.64 \cdot 10^5, 1.7777 \cdot 10^5).
\end{aligned}$$

All of those bounds are less than $2.147 \cdot 10^5$, and we are thus within $\text{T}_{\text{E}}\text{X}$'s bounds in all cases!

We later need to have a bound on the Q_i . Their definitions imply that $Q_A < 10^9 A/y - 1/2 < 10^5 A$ and similarly for the other Q_i . Thus, all of them are less than 177770.

The last step is to ensure correct rounding. We have

$$A/Z = \sum_{i=1}^4 (10^{-4i} Q_i) + 10^{-16} E/Z$$

exactly. Furthermore, we know that the result is in $[0.1, 10)$, hence will be rounded to a multiple of 10^{-16} or of 10^{-15} , so we only need to know the integer part of E/Z , and a “rounding” digit encoding the rest. Equivalently, we need to find the integer part of $2E/Z$, and determine whether it was an exact integer or not (this serves to detect ties). Since

$$\frac{2E}{Z} = 2 \frac{10^5 E}{10^5 Z} \leq 2 \frac{10^5 E}{10^4} < 36,$$

this integer part is between 0 and 35 inclusive. We let $\varepsilon\text{-TeX}$ round

$$P = \text{\texttt{\textbackslash int_eval:n}} \left\{ \frac{2 \cdot E_1 E_2}{Z_1 Z_2} \right\},$$

which differs from $2E/Z$ by at most

$$\frac{1}{2} + 2 \left| \frac{E}{Z} - \frac{E}{10^{-8} Z_1 Z_2} \right| + 2 \left| \frac{10^8 E - E_1 E_2}{Z_1 Z_2} \right| < 1,$$

($1/2$ comes from $\varepsilon\text{-TeX}$ ’s rounding) because each absolute value is less than 10^{-7} . Thus P is either the correct integer part, or is off by 1; furthermore, if $2E/Z$ is an integer, $P = 2E/Z$. We will check the sign of $2E - PZ$. If it is negative, then $E/Z \in ((P-1)/2, P/2)$. If it is zero, then $E/Z = P/2$. If it is positive, then $E/Z \in (P/2, (P+1)/2)$. In each case, we know how to round to an integer, depending on the parity of P , and the rounding mode.

26.3.3 Implementing the significand division

`_fp_div_significand_i_o:wnnw`

`_fp_div_significand_i_o:wnnw` $\langle y \rangle$; $\{\langle A_1 \rangle\} \{\langle A_2 \rangle\} \{\langle A_3 \rangle\} \{\langle A_4 \rangle\}$
 $\{\langle Z_1 \rangle\} \{\langle Z_2 \rangle\} \{\langle Z_3 \rangle\} \{\langle Z_4 \rangle\}$; $\langle sign \rangle$

Compute $10^6 + Q_A$ (a 7 digit number thanks to the shift), unbrace $\langle A_1 \rangle$ and $\langle A_2 \rangle$, and prepare the $\langle continuation \rangle$ arguments for 4 consecutive calls to `_fp_div_significand_calc:wnnnnnnnn`. Each of these calls needs $\langle y \rangle$ (#1), and it turns out that we need post-expansion there, hence the `_int_value:w`. Here, #4 is six brace groups, which give the six first n-type arguments of the `calc` function.

```

14106 \cs_new:Npn \_fp\_div\_significand\_i\_o:wnnw #1 ; #2 #3 #4 ;
14107 {
14108   \exp\_after:wN \_fp\_div\_significand\_test\_o:w
14109   \_int\_value:w \_int\_eval:w
14110   \exp\_after:wN \_fp\_div\_significand\_calc:wnnnnnnnn
14111   \_int\_value:w \_int\_eval:w 999999 + #2 #3 0 / #1 ;
14112   #2 #3 ;
14113   #4
14114   { \exp\_after:wN \_fp\_div\_significand\_ii:wN \_int\_value:w #1 }
14115   { \exp\_after:wN \_fp\_div\_significand\_ii:wN \_int\_value:w #1 }
14116   { \exp\_after:wN \_fp\_div\_significand\_ii:wN \_int\_value:w #1 }
14117   { \exp\_after:wN \_fp\_div\_significand\_iii:wnnnnnn \_int\_value:w #1 }
14118 }

```

(End definition for `_fp_div_significand_i_o:wnnw`.)

`_fp_div_significand_calc:wnnnnnnnn`
`_fp_div_significand_calc_i:wnnnnnnnn`
`_fp_div_significand_calc_ii:wnnnnnnnn`

`_fp_div_significand_calc:wnnnnnnnn` $\langle 10^6 + Q_A \rangle$; $\langle A_1 \rangle \langle A_2 \rangle$; $\{\langle A_3 \rangle\}$
 $\{\langle A_4 \rangle\} \{\langle Z_1 \rangle\} \{\langle Z_2 \rangle\} \{\langle Z_3 \rangle\} \{\langle Z_4 \rangle\} \{\langle continuation \rangle\}$

expands to

$$\langle 10^6 + Q_A \rangle \langle continuation \rangle ; \langle B_1 \rangle \langle B_2 \rangle ; \{\langle B_3 \rangle\} \{\langle B_4 \rangle\} \{\langle Z_1 \rangle\} \{\langle Z_2 \rangle\} \{\langle Z_3 \rangle\} \{\langle Z_4 \rangle\}$$

where $B = 10^4 A - Q_A \cdot Z$. This function is also used to compute C , D , E (with the input shifted accordingly), and is used in `l3fp-expo`.

We know that $0 < Q_A < 1.8 \cdot 10^5$, so the product of Q_A with each Z_i is within $\text{T}_{\text{E}}\text{X}$'s bounds. However, it is a little bit too large for our purposes: we would not be able to use the usual trick of adding a large power of 10 to ensure that the number of digits is fixed.

The bound on Q_A , implies that $10^6 + Q_A$ starts with the digit 1, followed by 0 or 1. We test, and call different auxiliaries for the two cases. An earlier implementation did the tests within the computation, but since we added a $\langle continuation \rangle$, this is not possible because the macro has 9 parameters.

The result we want is then (the overall power of 10 is arbitrary):

$$10^{-4}(\#2 - \#1 \cdot \#5 - 10 \cdot \langle i \rangle \cdot \#5\#6) + 10^{-8}(\#3 - \#1 \cdot \#6 - 10 \cdot \langle i \rangle \cdot \#7) \\ + 10^{-12}(\#4 - \#1 \cdot \#7 - 10 \cdot \langle i \rangle \cdot \#8) + 10^{-16}(-\#1 \cdot \#8),$$

where $\langle i \rangle$ stands for the 10^5 digit of Q_A , which is 0 or 1, and $\#1$, $\#2$, *etc.* are the parameters of either auxiliary. The factors of 10 come from the fact that $Q_A = 10 \cdot 10^4 \cdot \langle i \rangle + \#1$. As usual, to combine all the terms, we need to choose some shifts which must ensure that the number of digits of the second, third, and fourth terms are each fixed. Here, the positive contributions are at most 10^8 and the negative contributions can go up to 10^9 . Indeed, for the auxiliary with $\langle i \rangle = 1$, $\#1$ is at most 80000, leading to contributions of at worst $-8 \cdot 10^8$, while the other negative term is very small $< 10^6$ (except in the first expression, where we don't care about the number of digits); for the auxiliary with $\langle i \rangle = 0$, $\#1$ can go up to 99999, but there is no other negative term. Hence, a good choice is $2 \cdot 10^9$, which produces totals in the range $[10^9, 2.1 \cdot 10^9]$. We are flirting with $\text{T}_{\text{E}}\text{X}$'s limits once more.

```

14119 \cs_new:Npn \__fp_div_significand_calc:wwnnnnnnn #1#
14120 {
14121   \if_meaning:w 1 #1
14122     \exp_after:wN \__fp_div_significand_calc_i:wwnnnnnnn
14123   \else:
14124     \exp_after:wN \__fp_div_significand_calc_ii:wwnnnnnnn
14125   \fi:
14126 }
14127 \cs_new:Npn \__fp_div_significand_calc_i:wwnnnnnnn #1; #2;#3#4 #5#6#7#8 #9
14128 {
14129   1 1 #1
14130   #9 \exp_after:wN ;
14131   \__int_value:w \__int_eval:w \c__fp_Bigg_leading_shift_int
14132   + #2 - #1 * #5 - #5#60
14133   \exp_after:wN \__fp_pack_Bigg:NNNNNNw
14134   \__int_value:w \__int_eval:w \c__fp_Bigg_middle_shift_int
14135   + #3 - #1 * #6 - #70
14136   \exp_after:wN \__fp_pack_Bigg:NNNNNNw
14137   \__int_value:w \__int_eval:w \c__fp_Bigg_middle_shift_int
14138   + #4 - #1 * #7 - #80
14139   \exp_after:wN \__fp_pack_Bigg:NNNNNNw
14140   \__int_value:w \__int_eval:w \c__fp_Bigg_trailing_shift_int
14141   - #1 * #8 ;

```

```

14142     {#5}{#6}{#7}{#8}
14143   }
14144 \cs_new:Npn \__fp_div_significand_calc_ii:wwnnnnnnn #1; #2;#3#4 #5#6#7#8 #9
14145 {
14146   1 0 #1
14147   #9 \exp_after:wN ;
14148   \__int_value:w \__int_eval:w \c__fp_Bigg_leading_shift_int
14149   + #2 - #1 * #5
14150   \exp_after:wN \__fp_pack_Bigg:NNNNNNw
14151   \__int_value:w \__int_eval:w \c__fp_Bigg_middle_shift_int
14152   + #3 - #1 * #6
14153   \exp_after:wN \__fp_pack_Bigg:NNNNNNw
14154   \__int_value:w \__int_eval:w \c__fp_Bigg_middle_shift_int
14155   + #4 - #1 * #7
14156   \exp_after:wN \__fp_pack_Bigg:NNNNNNw
14157   \__int_value:w \__int_eval:w \c__fp_Bigg_trailing_shift_int
14158   - #1 * #8 ;
14159   {#5}{#6}{#7}{#8}
14160 }

```

(End definition for __fp_div_significand_calc:wwnnnnnnn, __fp_div_significand_calc_i:wwnnnnnnn, and __fp_div_significand_calc_ii:wwnnnnnnn.)

```

\__fp_div_significand_ii:wwn    \__fp_div_significand_ii:wwn <y> ; <B1> ; {<B2>} {<B3>} {<B4>} {<Z1>}
                                {<Z2>} {<Z3>} {<Z4>} <continuations> <sign>

```

Compute Q_B by evaluating $\langle B_1 \rangle \langle B_2 \rangle 0 / y - 1$. The result is output to the left, in an $\backslash_int_eval:w$ which we start now. Once that is evaluated (and the other Q_i also, since later expansions are triggered by this one), a packing auxiliary takes care of placing the digits of Q_B in an appropriate way for the final addition to obtain Q . This auxiliary is also used to compute Q_C and Q_D with the inputs C and D instead of B .

```

14161 \cs_new:Npn \__fp_div_significand_ii:wwn #1; #2;#3
14162 {
14163   \exp_after:wN \__fp_div_significand_pack:NNN
14164   \__int_value:w \__int_eval:w
14165   \exp_after:wN \__fp_div_significand_calc:wwnnnnnnn
14166   \__int_value:w \__int_eval:w 999999 + #2 #3 0 / #1 ; #2 #3 ;
14167 }

```

(End definition for __fp_div_significand_ii:wwn.)

```

\__fp_div_significand_iii:wwnnnnn    \__fp_div_significand_iii:wwnnnnn <y> ; <E1> ; {<E2>} {<E3>} {<E4>}
                                       {<Z1>} {<Z2>} {<Z3>} {<Z4>} <sign>

```

We compute $P \simeq 2E/Z$ by rounding $2E_1E_2/Z_1Z_2$. Note the first 0, which multiplies Q_D by 10: we later add (roughly) $5 \cdot P$, which amounts to adding $P/2 \simeq E/Z$ to Q_D , the appropriate correction from a hypothetical Q_E .

```

14168 \cs_new:Npn \__fp_div_significand_iii:wwnnnnn #1; #2;#3#4#5 #6#7
14169 {
14170   0
14171   \exp_after:wN \__fp_div_significand_iv:wwnnnnnnn
14172   \__int_value:w \__int_eval:w ( 2 * #2 #3 ) / #6 #7 ; % <- P
14173   #2 ; {#3} {#4} {#5}
14174   {#6} {#7}
14175 }

```

(End definition for _fp_div_significand_iii:wwnnnnn.)

_fp_div_significand_iv:wwnnnnnn
 _fp_div_significand_v:NNw
 _fp_div_significand_vi:Nw

_fp_div_significand_iv:wwnnnnnn $\langle P \rangle$; $\langle E_1 \rangle$; $\{\langle E_2 \rangle\}$ $\{\langle E_3 \rangle\}$ $\{\langle E_4 \rangle\}$
 $\{\langle Z_1 \rangle\}$ $\{\langle Z_2 \rangle\}$ $\{\langle Z_3 \rangle\}$ $\{\langle Z_4 \rangle\}$ $\langle sign \rangle$

This adds to the current expression $(10^7 + 10 \cdot Q_D)$ a contribution of $5 \cdot P + \text{sign}(T)$ with $T = 2E - PZ$. This amounts to adding $P/2$ to Q_D , with an extra $\langle \text{rounding} \rangle$ digit. This $\langle \text{rounding} \rangle$ digit is 0 or 5 if T does not contribute, *i.e.*, if $0 = T = 2E - PZ$, in other words if $10^{16}A/Z$ is an integer or half-integer. Otherwise it is in the appropriate range, $[1, 4]$ or $[6, 9]$. This is precise enough for rounding purposes (in any mode).

It seems an overkill to compute T exactly as I do here, but I see no faster way right now.

Once more, we need to be careful and show that the calculation $\#1 \cdot \#6\#7$ below does not cause an overflow: naively, P can be up to 35, and $\#6\#7$ up to 10^8 , but both cannot happen simultaneously. To show that things are fine, we split in two (non-disjoint) cases.

- For $P < 10$, the product obeys $P \cdot \#6\#7 < 10^8 \cdot P < 10^9$.
- For large $P \geq 3$, the rounding error on P , which is at most 1, is less than a factor of 2, hence $P \leq 4E/Z$. Also, $\#6\#7 \leq 10^8 \cdot Z$, hence $P \cdot \#6\#7 \leq 4E \cdot 10^8 < 10^9$.

Both inequalities could be made tighter if needed.

Note however that $P \cdot \#8\#9$ may overflow, since the two factors are now independent, and the result may reach $3.5 \cdot 10^9$. Thus we compute the two lower levels separately. The rest is standard, except that we use $+$ as a separator (ending integer expressions explicitly). T is negative if the first character is $-$, it is positive if the first character is neither 0 nor $-$. It is also positive if the first character is 0 and second argument of $_fp_div_significand_vi:Nw$, a sum of several terms, is also zero. Otherwise, there was an exact agreement: $T = 0$.

```

14176 \cs_new:Npn \_fp_div_significand_iv:wwnnnnnn #1; #2; #3#4#5 #6#7#8#9
14177 {
14178   + 5 * #1
14179   \exp_after:wN \_fp_div_significand_vi:Nw
14180   \_int_value:w \_int_eval:w -20 + 2*#2#3 - #1*#6#7 +
14181   \exp_after:wN \_fp_div_significand_v:NN
14182   \_int_value:w \_int_eval:w 199980 + 2*#4 - #1*#8 +
14183   \exp_after:wN \_fp_div_significand_v:NN
14184   \_int_value:w \_int_eval:w 200000 + 2*#5 - #1*#9 ;
14185 }
14186 \cs_new:Npn \_fp_div_significand_v:NN #1#2 { #1#2 \_int_eval_end: + }
14187 \cs_new:Npn \_fp_div_significand_vi:Nw #1#2;
14188 {
14189   \if_meaning:w 0 #1
14190     \if_int_compare:w \_int_eval:w #2 > 0 + 1 \fi:
14191   \else:
14192     \if_meaning:w - #1 - \else: + \fi: 1
14193   \fi:
14194   ;
14195 }
```

(End definition for _fp_div_significand_iv:wwnnnnnn, _fp_div_significand_v:NNw, and _fp_div_significand_vi:Nw.)

`_fp_div_significand_pack:NNN` At this stage, we are in the following situation: \TeX is in the process of expanding several integer expressions, thus functions at the bottom expand before those above.

```
\_fp_div_significand_test_o:w 10^6 + Q_A \_fp_div_significand_-
pack:NNN 10^6 + Q_B \_fp_div_significand_pack:NNN 10^6 + Q_C \_fp_-
div_significand_pack:NNN 10^7 + 10 \cdot Q_D + 5 \cdot P + \varepsilon ; \langle sign \rangle
```

Here, $\varepsilon = \text{sign}(T)$ is 0 in case $2E = PZ$, 1 in case $2E > PZ$, which means that P was the correct value, but not with an exact quotient, and -1 if $2E < PZ$, *i.e.*, P was an overestimate. The packing function we define now does nothing special: it removes the 10^6 and carries two digits (for the 10^5 's and the 10^4 's).

```
14196 \cs_new:Npn \_fp_div_significand_pack:NNN 1 #1 #2 { + #1 #2 ; }
```

(End definition for `_fp_div_significand_pack:NNN`.)

```
\_fp_div_significand_test_o:w \_fp_div_significand_test_o:w 1 0 \langle 5d \rangle ; \langle 4d \rangle ; \langle 4d \rangle ; \langle 5d \rangle ; \langle sign \rangle
```

The reason we know that the first two digits are 1 and 0 is that the final result is known to be between 0.1 (inclusive) and 10, hence \widetilde{Q}_A (the tilde denoting the contribution from the other Q_i) is at most 99999, and $10^6 + \widetilde{Q}_A = 10 \dots$.

It is now time to round. This depends on how many digits the final result will have.

```
14197 \cs_new:Npn \_fp_div_significand_test_o:w 10 #1
14198 {
14199   \if_meaning:w 0 #1
14200     \exp_after:wN \_fp_div_significand_small_o:wwwNNNNwN
14201   \else:
14202     \exp_after:wN \_fp_div_significand_large_o:wwwNNNNwN
14203   \fi:
14204   #1
14205 }
```

(End definition for `_fp_div_significand_test_o:w`.)

```
\_fp_div_significand_small_o:wwwNNNNwN \_fp_div_significand_small_o:wwwNNNNwN 0 \langle 4d \rangle ; \langle 4d \rangle ; \langle 4d \rangle ; \langle 5d \rangle
; \langle final sign \rangle
```

Standard use of the functions `_fp_basics_pack_low:NNNNw` and `_fp_basics_pack_high:NNNNw`. We finally get to use the $\langle final\ sign \rangle$ which has been sitting there for a while.

```
14206 \cs_new:Npn \_fp_div_significand_small_o:wwwNNNNwN
14207   0 #1; #2; #3; #4#5#6#7#8; #9
14208 {
14209   \exp_after:wN \_fp_basics_pack_high:NNNNw
14210   \_int_value:w \_int_eval:w 1 #1#2
14211   \exp_after:wN \_fp_basics_pack_low:NNNNw
14212   \_int_value:w \_int_eval:w 1 #3#4#5#6#7
14213   + \_fp_round:NNN #9 #7 #8
14214   \exp_after:wN ;
14215 }
```

(End definition for `_fp_div_significand_small_o:wwwNNNNwN`.)

```

\__fp_div_significand_large_o:wwwNNNNwN \__fp_div_significand_large_o:wwwNNNNwN <5d> ; <4d> ; <4d> ; <5d> ;
<sign>

```

We know that the final result cannot reach 10, hence 1#1#2, together with contributions from the level below, cannot reach $2 \cdot 10^9$. For rounding, we build the *<rounding digit>* from the last two of our 18 digits.

```

14216 \cs_new:Npn \__fp_div_significand_large_o:wwwNNNNwN
14217 #1; #2; #3; #4#5#6#7#8; #9
14218 {
14219   + 1
14220   \exp_after:wN \__fp_basics_pack_weird_high:NNNNNNNNw
14221   \__int_value:w \__int_eval:w 1 #1 #2
14222   \exp_after:wN \__fp_basics_pack_weird_low:NNNNw
14223   \__int_value:w \__int_eval:w 1 #3 #4 #5 #6 +
14224   \exp_after:wN \__fp_round:NNN
14225   \exp_after:wN #9
14226   \exp_after:wN #6
14227   \__int_value:w \__fp_round_digit:Nw #7 #8 ;
14228   \exp_after:wN ;
14229 }

```

(End definition for __fp_div_significand_large_o:wwwNNNNwN.)

26.4 Square root

__fp_sqrt_o:w Zeros are unchanged: $\sqrt{-0} = -0$ and $\sqrt{+0} = +0$. Negative numbers (other than -0) have no real square root. Positive infinity, and `nan`, are unchanged. Finally, for normal positive numbers, there is some work to do.

```

14230 \cs_new:Npn \__fp_sqrt_o:w #1 \s__fp \__fp_chk:w #2#3#4; @
14231 {
14232   \if_meaning:w 0 #2 \__fp_case_return_same_o:w \fi:
14233   \if_meaning:w 2 #3
14234     \__fp_case_use:nw { \__fp_invalid_operation_o:nw { sqrt } }
14235   \fi:
14236   \if_meaning:w 1 #2 \else: \__fp_case_return_same_o:w \fi:
14237   \__fp_sqrt_npos_o:w
14238   \s__fp \__fp_chk:w #2 #3 #4;
14239 }

```

(End definition for __fp_sqrt_o:w.)

__fp_sqrt_npos_o:w Prepare __fp_sanitize:Nw to receive the final sign 0 (the result is always positive) and the exponent, equal to half of the exponent #1 of the argument. If the exponent #1 is even, find a first approximation of the square root of the significand $10^8 a_1 + a_2 = 10^8 \#2\#3 + \#4\#5$ through Newton's method, starting at $x = 57234133 \simeq 10^{7.75}$. Otherwise, first shift the significand of of the argument by one digit, getting $a'_1 \in [10^6, 10^7)$ instead of $[10^7, 10^8)$, then use Newton's method starting at $17782794 \simeq 10^{7.25}$.

```

14240 \cs_new:Npn \__fp_sqrt_npos_o:w \s__fp \__fp_chk:w 1 0 #1#2#3#4#5;
14241 {
14242   \exp_after:wN \__fp_sanitize:Nw
14243   \exp_after:wN 0
14244   \__int_value:w \__int_eval:w
14245   \if_int_odd:w #1 \exp_stop_f:
14246     \exp_after:wN \__fp_sqrt_npos_auxi_o:wwwNNN

```

```

14247      \fi:
14248      #1 / 2
14249      \__fp_sqrt_Newton_o:wnn 56234133; 0; {#2#3} {#4#5} 0
14250    }
14251    \cs_new:Npn \__fp_sqrt_npos_auxii_o:wnnnN #1 / 2 #2; 0; #3#4#5
14252    {
14253      ( #1 + 1 ) / 2
14254      \__fp_pack_eight:wnnnnnnnN
14255      \__fp_sqrt_npos_auxii_o:wnnnnnnnN
14256      ;
14257      0 #3 #4
14258    }
14259    \cs_new:Npn \__fp_sqrt_npos_auxii_o:wnnnnnnnN #1; #2#3#4#5#6#7#8#9
14260    { \__fp_sqrt_Newton_o:wnn 17782794; 0; {#1} {#2#3#4#5#6#7#8#9} }

```

(End definition for `__fp_sqrt_npos_o:w`, `__fp_sqrt_npos_auxii_o:wnnnN`, and `__fp_sqrt_npos_auxii_o:wnnnnnnnN`.)

`__fp_sqrt_Newton_o:wnn` Newton's method maps $x \mapsto [(x + [10^8 a_1/x])/2]$ in each iteration, where $[b/c]$ denotes ε -TeX's division. This division rounds the real number b/c to the closest integer, rounding ties away from zero, hence when c is even, $b/c - 1/2 + 1/c \leq [b/c] \leq b/c + 1/2$ and when c is odd, $b/c - 1/2 + 1/(2c) \leq [b/c] \leq b/c + 1/2 - 1/(2c)$. For all c , $b/c - 1/2 + 1/(2c) \leq [b/c] \leq b/c + 1/2$.

Let us prove that the method converges when implemented with ε -TeX integer division, for any $10^6 \leq a_1 < 10^8$ and starting value $10^6 \leq x < 10^8$. Using the inequalities above and the arithmetic-geometric inequality $(x + t)/2 \geq \sqrt{xt}$ for $t = 10^8 a_1/x$, we find

$$x' = \left\lceil \frac{x + [10^8 a_1/x]}{2} \right\rceil \geq \frac{x + 10^8 a_1/x - 1/2 + 1/(2x)}{2} \geq \sqrt{10^8 a_1} - \frac{1}{4} + \frac{1}{4x}.$$

After any step of iteration, we thus have $\delta = x - \sqrt{10^8 a_1} \geq -0.25 + 0.25 \cdot 10^{-8}$. The new difference $\delta' = x' - \sqrt{10^8 a_1}$ after one step is bounded above as

$$x' - \sqrt{10^8 a_1} \leq \frac{x + 10^8 a_1/x + 1/2}{2} + \frac{1}{2} - \sqrt{10^8 a_1} \leq \frac{\delta}{2} \frac{\delta}{\sqrt{10^8 a_1} + \delta} + \frac{3}{4}.$$

For $\delta > 3/2$, this last expression is $\leq \delta/2 + 3/4 < \delta$, hence δ decreases at each step: since all x are integers, δ must reach a value $-1/4 < \delta \leq 3/2$. In this range of values, we get $\delta' \leq \frac{3}{2} \frac{3}{2\sqrt{10^8 a_1}} + \frac{3}{4} \leq 0.75 + 1.125 \cdot 10^{-7}$. We deduce that the difference $\delta = x - \sqrt{10^8 a_1}$ eventually reaches a value in the interval $[-0.25 + 0.25 \cdot 10^{-8}, 0.75 + 11.25 \cdot 10^{-8}]$, whose width is $1 + 11 \cdot 10^{-8}$. The corresponding interval for x may contain two integers, hence x might oscillate between those two values.

However, the fact that $x \mapsto x - 1$ and $x - 1 \mapsto x$ puts stronger constraints, which are not compatible: the first implies

$$x + [10^8 a_1/x] \leq 2x - 2$$

hence $10^8 a_1/x \leq x - 3/2$, while the second implies

$$x - 1 + [10^8 a_1/(x - 1)] \geq 2x - 1$$

hence $10^8 a_1/(x - 1) \geq x - 1/2$. Combining the two inequalities yields $x^2 - 3x/2 \geq 10^8 a_1 \geq x - 3x/2 + 1/2$, which cannot hold. Therefore, the iteration always converges to a single

integer x . To stop the iteration when two consecutive results are equal, the function `_fp_sqrt_Newton_o:wnn` receives the newly computed result as `#1`, the previous result as `#2`, and a_1 as `#3`. Note that ε -TeX combines the computation of a multiplication and a following division, thus avoiding overflow in `#3 * 100000000 / #1`. In any case, the result is within $[10^7, 10^8]$.

```

14261 \cs_new:Npn \_fp_sqrt_Newton_o:wnn #1; #2; #3
14262 {
14263   \if_int_compare:w #1 = #2 \exp_stop_f:
14264     \exp_after:wN \_fp_sqrt_auxi_o:NNNNwnnnN
14265     \_int_value:w \_int_eval:w 9999 9999 +
14266     \exp_after:wN \_fp_use_none_until_s:w
14267   \fi:
14268   \exp_after:wN \_fp_sqrt_Newton_o:wnn
14269   \_int_value:w \_int_eval:w (#1 + #3 * 1 0000 0000 / #1) / 2 ;
14270   #1; {#3}
14271 }

```

(End definition for `_fp_sqrt_Newton_o:wnn`.)

`_fp_sqrt_auxi_o:NNNNwnnnN`

This function is followed by $10^8 + x - 1$, which has 9 digits starting with 1, then ; $\{ \langle a_1 \rangle \} \{ \langle a_2 \rangle \} \langle a' \rangle$. Here, $x \simeq \sqrt{10^8 a_1}$ and we want to estimate the square root of $a = 10^{-8}a_1 + 10^{-16}a_2 + 10^{-17}a'$. We set up an initial underestimate

$$y = (x - 1)10^{-8} + 0.2499998875 \cdot 10^{-8} \lesssim \sqrt{a}.$$

From the inequalities shown earlier, we know that $y \leq \sqrt{10^{-8}a_1} \leq \sqrt{a}$ and that $\sqrt{10^{-8}a_1} \leq y + 10^{-8} + 11 \cdot 10^{-16}$ hence (using $0.1 \leq y \leq \sqrt{a} \leq 1$)

$$a - y^2 \leq 10^{-8}a_1 + 10^{-8} - y^2 \leq (y + 10^{-8} + 11 \cdot 10^{-16})^2 - y^2 + 10^{-8} < 3.2 \cdot 10^{-8},$$

and $\sqrt{a} - y = (a - y^2)/(\sqrt{a} + y) \leq 16 \cdot 10^{-8}$. Next, `_fp_sqrt_auxii_o:NnnnnnnnnN` is called several times to get closer and closer underestimates of \sqrt{a} . By construction, the underestimates y are always increasing, $a - y^2 < 3.2 \cdot 10^{-8}$ for all. Also, $y < 1$.

```

14272 \cs_new:Npn \_fp_sqrt_auxi_o:NNNNwnnnN 1 #1#2#3#4#5;
14273 {
14274   \_fp_sqrt_auxii_o:NnnnnnnnnN
14275   \_fp_sqrt_auxiii_o:wnnnnnnnnn
14276   {#1#2#3#4} {#5} {2499} {9988} {7500}
14277 }

```

(End definition for `_fp_sqrt_auxi_o:NNNNwnnnN`.)

`_fp_sqrt_auxii_o:NnnnnnnnnN`

This receives a continuation function `#1`, then five blocks of 4 digits for y , then two 8-digit blocks and a single digit for a . A common estimate of $\sqrt{a} - y = (a - y^2)/(\sqrt{a} + y)$ is $(a - y^2)/(2y)$, which leads to alternating overestimates and underestimates. We tweak this, to only work with underestimates (no need then to worry about signs in the computation). Each step finds the largest integer $j \leq 6$ such that $10^{4j}(a - y^2) < 2 \cdot 10^8$, then computes the integer (with ε -TeX's rounding division)

$$10^{4j}z = \left[([10^{4j}(a - y^2)] - 257) \cdot (0.5 \cdot 10^8) \middle/ [10^8 y + 1] \right].$$

The choice of j ensures that $10^{4j}z < 2 \cdot 10^8 \cdot 0.5 \cdot 10^8 / 10^7 = 10^9$, thus $10^9 + 10^{4j}z$ has exactly 10 digits, does not overflow TeX's integer range, and starts with 1. Incidentally, since all $a - y^2 \leq 3.2 \cdot 10^{-8}$, we know that $j \geq 3$.

Let us show that z is an underestimate of $\sqrt{a}-y$. On the one hand, $\sqrt{a}-y \leq 16 \cdot 10^{-8}$ because this holds for the initial y and values of y can only increase. On the other hand, the choice of j implies that $\sqrt{a}-y \leq 5(\sqrt{a}+y)(\sqrt{a}-y) = 5(a-y^2) < 10^{9-4j}$. For $j = 3$, the first bound is better, while for larger j , the second bound is better. For all $j \in [3, 6]$, we find $\sqrt{a}-y < 16 \cdot 10^{-2j}$. From this, we deduce that

$$10^{4j}(\sqrt{a}-y) = \frac{10^{4j}(a-y^2-(\sqrt{a}-y)^2)}{2y} \geq \frac{\lfloor 10^{4j}(a-y^2) \rfloor - 257}{2 \cdot 10^{-8} \lfloor 10^8 y + 1 \rfloor} + \frac{1}{2}$$

where we have replaced the bound $10^{4j}(16 \cdot 10^{-2j}) = 256$ by 257 and extracted the corresponding term $1/(2 \cdot 10^{-8} \lfloor 10^8 y + 1 \rfloor) \geq 1/2$. Given that ε -TeX's integer division obeys $\lfloor b/c \rfloor \leq b/c + 1/2$, we deduce that $10^{4j}z \leq 10^{4j}(\sqrt{a}-y)$, hence $y+z \leq \sqrt{a}$ is an underestimate of \sqrt{a} , as claimed. One implementation detail: because the computation involves $-4*4 - 2*3*5 - 2*2*6$ which may be as low as $-5 \cdot 10^8$, we need to use the `pack_big` functions, and the big shifts.

```

14278 \cs_new:Npn \__fp_sqrt_auxii_o:NnnnnnnN #1 #2#3#4#5#6 #7#8#9
14279 {
14280   \exp_after:wN #1
14281   \__int_value:w \__int_eval:w \c__fp_big_leading_shift_int
14282     + #7 - #2 * #2
14283   \exp_after:wN \__fp_pack_big:NNNNNNw
14284   \__int_value:w \__int_eval:w \c__fp_big_middle_shift_int
14285     - 2 * #2 * #3
14286   \exp_after:wN \__fp_pack_big:NNNNNNw
14287   \__int_value:w \__int_eval:w \c__fp_big_middle_shift_int
14288     + #8 - #3 * #3 - 2 * #2 * #4
14289   \exp_after:wN \__fp_pack_big:NNNNNNw
14290   \__int_value:w \__int_eval:w \c__fp_big_middle_shift_int
14291     - 2 * #3 * #4 - 2 * #2 * #5
14292   \exp_after:wN \__fp_pack_big:NNNNNNw
14293   \__int_value:w \__int_eval:w \c__fp_big_middle_shift_int
14294     + #9 000 0000 - #4 * #4 - 2 * #3 * #5 - 2 * #2 * #6
14295   \exp_after:wN \__fp_pack_big:NNNNNNw
14296   \__int_value:w \__int_eval:w \c__fp_big_middle_shift_int
14297     - 2 * #4 * #5 - 2 * #3 * #6
14298   \exp_after:wN \__fp_pack_big:NNNNNNw
14299   \__int_value:w \__int_eval:w \c__fp_big_middle_shift_int
14300     - #5 * #5 - 2 * #4 * #6
14301   \exp_after:wN \__fp_pack_big:NNNNNNw
14302   \__int_value:w \__int_eval:w
14303     \c__fp_big_middle_shift_int
14304     - 2 * #5 * #6
14305   \exp_after:wN \__fp_pack_big:NNNNNNw
14306   \__int_value:w \__int_eval:w
14307     \c__fp_big_trailing_shift_int
14308     - #6 * #6 ;
14309   % (
14310   - 257 ) * 5000 0000 / (#2#3 + 1) + 10 0000 0000 ;
14311   {#2}{#3}{#4}{#5}{#6} {#7}{#8}{#9}
14312 }

```

(End definition for `__fp_sqrt_auxii_o:NnnnnnnN`.)

```

    \_fp_sqrt_auxiii_o:wnnnnnnnn
\_fp_sqrt_auxiv_o:NNNNNw
\_fp_sqrt_auxv_o:NNNNNw
\_fp_sqrt_auxvi_o:NNNNNw
\_fp_sqrt_auxvii_o:NNNNNw

```

We receive here the difference $a - y^2 = d = \sum_i d_i \cdot 10^{-4i}$, as $\langle d_2 \rangle ; \{ \langle d_3 \rangle \} \dots \{ \langle d_{10} \rangle \}$, where each block has 4 digits, except $\langle d_2 \rangle$. This function finds the largest $j \leq 6$ such that $10^{4j}(a - y^2) < 2 \cdot 10^8$, then leaves an open parenthesis and the integer $\lfloor 10^{4j}(a - y^2) \rfloor$ in an integer expression. The closing parenthesis is provided by the caller `_fp_sqrt_auxii_o:NNnnnnnnN`, which completes the expression

$$10^{4j}z = \left[(\lfloor 10^{4j}(a - y^2) \rfloor - 257) \cdot (0.5 \cdot 10^8) / \lfloor 10^8 y + 1 \rfloor \right]$$

for an estimate of $10^{4j}(\sqrt{a} - y)$. If $d_2 \geq 2$, $j = 3$ and the `auxiv` auxiliary receives $10^{12}z$. If $d_2 \leq 1$ but $10^4 d_2 + d_3 \geq 2$, $j = 4$ and the `auxv` auxiliary is called, and receives $10^{16}z$, and so on. In all those cases, the `auxviii` auxiliary is set up to add z to y , then go back to the `auxii` step with continuation `auxiii` (the function we are currently describing). The maximum value of j is 6, regardless of whether $10^{12}d_2 + 10^8 d_3 + 10^4 d_4 + d_5 \geq 1$. In this last case, we detect when $10^{24}z < 10^7$, which essentially means $\sqrt{a} - y \lesssim 10^{-17}$: once this threshold is reached, there is enough information to find the correctly rounded \sqrt{a} with only one more call to `_fp_sqrt_auxii_o:NNnnnnnnN`. Note that the iteration cannot be stuck before reaching $j = 6$, because for $j < 6$, one has $2 \cdot 10^8 \leq 10^{4(j+1)}(a - y^2)$, hence

$$10^{4j}z \geq \frac{(20000 - 257)(0.5 \cdot 10^8)}{\lfloor 10^8 y + 1 \rfloor} \geq (20000 - 257) \cdot 0.5 > 0.$$

```

14313 \cs_new:Npn \_fp_sqrt_auxiii_o:wnnnnnnnn
14314   #1; #2#3#4#5#6#7#8#9
14315   {
14316     \if_int_compare:w #1 > 1 \exp_stop_f:
14317     \exp_after:wN \_fp_sqrt_auxiv_o:NNNNNw
14318     \__int_value:w \__int_eval:w (#1#2 %)
14319   \else:
14320     \if_int_compare:w #1#2 > 1 \exp_stop_f:
14321     \exp_after:wN \_fp_sqrt_auxv_o:NNNNNw
14322     \__int_value:w \__int_eval:w (#1#2#3 %)
14323   \else:
14324     \if_int_compare:w #1#2#3 > 1 \exp_stop_f:
14325     \exp_after:wN \_fp_sqrt_auxvi_o:NNNNNw
14326     \__int_value:w \__int_eval:w (#1#2#3#4 %)
14327   \else:
14328     \exp_after:wN \_fp_sqrt_auxvii_o:NNNNNw
14329     \__int_value:w \__int_eval:w (#1#2#3#4#5 %)
14330   \fi:
14331   \fi:
14332   \fi:
14333   }
14334 \cs_new:Npn \_fp_sqrt_auxiv_o:NNNNNw 1#1#2#3#4#5#6;
14335   { \_fp_sqrt_auxviii_o:nnnnnnn {#1#2#3#4#5#6} {00000000} }
14336 \cs_new:Npn \_fp_sqrt_auxv_o:NNNNNw 1#1#2#3#4#5#6;
14337   { \_fp_sqrt_auxviii_o:nnnnnnn {000#1#2#3#4#5} {#60000} }
14338 \cs_new:Npn \_fp_sqrt_auxvi_o:NNNNNw 1#1#2#3#4#5#6;
14339   { \_fp_sqrt_auxviii_o:nnnnnnn {0000000#1} {#2#3#4#5#6} }
14340 \cs_new:Npn \_fp_sqrt_auxvii_o:NNNNNw 1#1#2#3#4#5#6;
14341   {
14342     \if_int_compare:w #1#2 = 0 \exp_stop_f:
14343     \exp_after:wN \_fp_sqrt_auxx_o:Nnnnnnnn
14344   \fi:

```

```

14345     \_fp_sqrt_auxviii_o:nnnnnnnn {00000000} {000#1#2#3#4#5}
14346   }

```

(End definition for _fp_sqrt_auxiii_o:wnnnnnnn and others.)

_fp_sqrt_auxviii_o:nnnnnnnn Simply add the two 8-digit blocks of z , aligned to the last four of the five 4-digit blocks of y , then call the auxii auxiliary to evaluate $y'^2 = (y + z)^2$.

```

14347 \cs_new:Npn \_fp_sqrt_auxviii_o:nnnnnnnn #1#2 #3#4#5#6#7
14348 {
14349   \exp_after:wN \_fp_sqrt_auxix_o:wnwnw
14350   \_int_value:w \_int_eval:w #3
14351   \exp_after:wN \_fp_basics_pack_low:NNNNw
14352   \_int_value:w \_int_eval:w #1 + 1#4#5
14353   \exp_after:wN \_fp_basics_pack_low:NNNNw
14354   \_int_value:w \_int_eval:w #2 + 1#6#7 ;
14355 }
14356 \cs_new:Npn \_fp_sqrt_auxix_o:wnwnw #1; #2#3; #4#5;
14357 {
14358   \_fp_sqrt_auxii_o:NnnnnnnnN
14359   \_fp_sqrt_auxiii_o:wnnnnnnnnn {#1}{#2}{#3}{#4}{#5}
14360 }

```

(End definition for _fp_sqrt_auxviii_o:nnnnnnnn and _fp_sqrt_auxix_o:wnwnw.)

_fp_sqrt_auxx_o:Nnnnnnnnn
_fp_sqrt_auxxi_o:wnnnN

At this stage, $j = 6$ and $10^{24}z < 10^7$, hence

$$10^7 + 1/2 > 10^{24}z + 1/2 \geq (10^{24}(a - y^2) - 258) \cdot (0.5 \cdot 10^8) / (10^8y + 1),$$

then $10^{24}(a - y^2) - 258 < 2(10^7 + 1/2)(y + 10^{-8})$, and

$$10^{24}(a - y^2) < (10^7 + 1290.5)(1 + 10^{-8}/y)(2y) < (10^7 + 1290.5)(1 + 10^{-7})(y + \sqrt{a}),$$

which finally implies $0 \leq \sqrt{a} - y < 0.2 \cdot 10^{-16}$. In particular, y is an underestimate of \sqrt{a} and $y + 0.5 \cdot 10^{-16}$ is a (strict) overestimate. There is at exactly one multiple m of $0.5 \cdot 10^{-16}$ in the interval $[y, y + 0.5 \cdot 10^{-16})$. If $m^2 > a$, then the square root is inexact and is obtained by rounding $m - \epsilon$ to a multiple of 10^{-16} (the precise shift $0 < \epsilon < 0.5 \cdot 10^{-16}$ is irrelevant for rounding). If $m^2 = a$ then the square root is exactly m , and there is no rounding. If $m^2 < a$ then we round $m + \epsilon$. For now, discard a few irrelevant arguments #1, #2, #3, and find the multiple of $0.5 \cdot 10^{-16}$ within $[y, y + 0.5 \cdot 10^{-16})$; rather, only the last 4 digits #8 of y are considered, and we do not perform any carry yet. The auxxi auxiliary sets up auxii with a continuation function auxxii instead of auxiii as before. To prevent auxii from giving a negative results $a - m^2$, we compute $a + 10^{-16} - m^2$ instead, always positive since $m < \sqrt{a} + 0.5 \cdot 10^{-16}$ and $a \leq 1 - 10^{-16}$.

```

14361 \cs_new:Npn \_fp_sqrt_auxx_o:Nnnnnnnnn #1#2#3 #4#5#6#7#8
14362 {
14363   \exp_after:wN \_fp_sqrt_auxxi_o:wnnnN
14364   \_int_value:w \_int_eval:w
14365   (#8 + 2499) / 5000 * 5000 ;
14366   {#4} {#5} {#6} {#7} ;
14367 }
14368 \cs_new:Npn \_fp_sqrt_auxxi_o:wnnnN #1; #2; #3#4#5
14369 {
14370   \_fp_sqrt_auxii_o:NnnnnnnnN

```

```

14371      \__fp_sqrt_auxxii_o:nnnnnnnnnw
14372      #2 {#1}
14373      {#3} { #4 + 1 } #5
14374  }

```

(End definition for __fp_sqrt_auxx_o:nnnnnnnn and __fp_sqrt_auxxi_o:wnnnN.)

__fp_sqrt_auxxii_o:nnnnnnnnnw
 __fp_sqrt_auxxiii_o:w

The difference $0 \leq a + 10^{-16} - m^2 \leq 10^{-16} + (\sqrt{a} - m)(\sqrt{a} + m) \leq 2 \cdot 10^{-16}$ was just computed: its first 8 digits vanish, as do the next four, #1, and most of the following four, #2. The guess m is an overestimate if $a + 10^{-16} - m^2 < 10^{-16}$, that is, #1#2 vanishes. Otherwise it is an underestimate, unless $a + 10^{-16} - m^2 = 10^{-16}$ exactly. For an underestimate, call the auxxiv function with argument 9998. For an exact result call it with 9999, and for an overestimate call it with 10000.

```

14375 \cs_new:Npn \__fp_sqrt_auxxii_o:nnnnnnnnnw 0; #1#2#3#4#5#6#7#8 #9;
14376 {
14377   \if_int_compare:w #1#2 > 0 \exp_stop_f:
14378   \if_int_compare:w #1#2 = 1 \exp_stop_f:
14379   \if_int_compare:w #3#4 = 0 \exp_stop_f:
14380   \if_int_compare:w #5#6 = 0 \exp_stop_f:
14381   \if_int_compare:w #7#8 = 0 \exp_stop_f:
14382     \__fp_sqrt_auxxiii_o:w
14383     \fi:
14384     \fi:
14385     \fi:
14386     \fi:
14387     \exp_after:wN \__fp_sqrt_auxxiv_o:wnnnnnnnN
14388     \__int_value:w 9998
14389   \else:
14390     \exp_after:wN \__fp_sqrt_auxxiv_o:wnnnnnnnN
14391     \__int_value:w 10000
14392   \fi:
14393   ;
14394 }
14395 \cs_new:Npn \__fp_sqrt_auxxiii_o:w \fi: \fi: \fi: \fi: #1 \fi: ;
14396 {
14397   \fi: \fi: \fi: \fi: \fi:
14398   \__fp_sqrt_auxxiv_o:wnnnnnnnN 9999 ;
14399 }

```

(End definition for __fp_sqrt_auxxii_o:nnnnnnnnnw and __fp_sqrt_auxxiii_o:w.)

__fp_sqrt_auxxiv_o:wnnnnnnnN

This receives 9998, 9999 or 10000 as #1 when m is an underestimate, exact, or an overestimate, respectively. Then comes m as five blocks of 4 digits, but where the last block #6 may be 0, 5000, or 10000. In the latter case, we need to add a carry, unless m is an overestimate (#1 is then 10000). Then comes a as three arguments. Rounding is done by __fp_round:NNN, whose first argument is the final sign 0 (square roots are positive). We fake its second argument. It should be the last digit kept, but this is only used when ties are “rounded to even”, and only when the result is exactly half-way between two representable numbers rational square roots of numbers with 16 significant digits have: this situation never arises for the square root, as any exact square root of a 16 digit number has at most 8 significant digits. Finally, the last argument is the next digit, possibly shifted by 1 when there are further nonzero digits. This is achieved by __fp_round_digit:Nw, which receives (after removal of the 10000’s digit) one of 0000, 0001, 4999, 5000, 5001, or 9999, which it converts to 0, 1, 4, 5, 6, and 9, respectively.

```

14400 \cs_new:Npn \__fp_sqrt_auxxiv_o:wnnnnnnnN #1; #2#3#4#5#6 #7#8#9
14401 {
14402   \exp_after:wN \__fp_basics_pack_high:NNNNNw
14403   \__int_value:w \__int_eval:w 1 0000 0000 + #2#3
14404   \exp_after:wN \__fp_basics_pack_low:NNNNNw
14405   \__int_value:w \__int_eval:w 1 0000 0000
14406   + #4#5
14407   \if_int_compare:w #6 > #1 \exp_stop_f: + 1 \fi:
14408   + \exp_after:wN \__fp_round:NNN
14409   \exp_after:wN 0
14410   \exp_after:wN 0
14411   \__int_value:w
14412   \exp_after:wN \use_i:nn
14413   \exp_after:wN \__fp_round_digit:Nw
14414   \__int_value:w \__int_eval:w #6 + 19999 - #1 ;
14415   \exp_after:wN ;
14416 }

```

(End definition for __fp_sqrt_auxxiv_o:wnnnnnnnN.)

26.5 About the sign

__fp_sign_o:w Find the sign of the floating point: nan, +0, -0, +1 or -1.

```

\__fp_sign_aux_o:w 14417 \cs_new:Npn \__fp_sign_o:w ? \s__fp \__fp_chk:w #1#2; @
14418 {
14419   \if_case:w #1 \exp_stop_f:
14420     \__fp_case_return_same_o:w
14421   \or: \exp_after:wN \__fp_sign_aux_o:w
14422   \or: \exp_after:wN \__fp_sign_aux_o:w
14423   \else: \__fp_case_return_same_o:w
14424   \fi:
14425   \s__fp \__fp_chk:w #1 #2;
14426 }
14427 \cs_new:Npn \__fp_sign_aux_o:w \s__fp \__fp_chk:w #1 #2 #3 ;
14428 { \exp_after:wN \__fp_set_sign_o:w \exp_after:wN #2 \c_one_fp @ }

```

(End definition for __fp_sign_o:w and __fp_sign_aux_o:w.)

__fp_set_sign_o:w This function is used for the unary minus and for `abs`. It leaves the sign of `nan` invariant, turns negative numbers (sign 2) to positive numbers (sign 0) and positive numbers (sign 0) to positive or negative numbers depending on #1. It also expands after itself in the input stream, just like `__fp_+_o:ww`.

```

14429 \cs_new:Npn \__fp_set_sign_o:w #1 \s__fp \__fp_chk:w #2#3#4; @
14430 {
14431   \exp_after:wN \__fp_exp_after_o:w
14432   \exp_after:wN \s__fp
14433   \exp_after:wN \__fp_chk:w
14434   \exp_after:wN #2
14435   \__int_value:w
14436   \if_case:w #3 \exp_stop_f: #1 \or: 1 \or: 0 \fi: \exp_stop_f:
14437   #4;
14438 }

```

(End definition for __fp_set_sign_o:w.)

```

14439 </initex | package>

```

27 l3fp-extended implementation

14440 $\langle *initex \mid package \rangle$

14441 $\langle @@=fp \rangle$

27.1 Description of fixed point numbers

This module provides a few functions to manipulate positive floating point numbers with extended precision (24 digits), but mostly provides functions for fixed-point numbers with this precision (24 digits). Those are used in the computation of Taylor series for the logarithm, exponential, and trigonometric functions. Since we eventually only care about the 16 first digits of the final result, some of the calculations are not performed with the full 24-digit precision. In other words, the last two blocks of each fixed point number may be wrong as long as the error is small enough to be rounded away when converting back to a floating point number. The fixed point numbers are expressed as

$$\{ \langle a_1 \rangle \} \{ \langle a_2 \rangle \} \{ \langle a_3 \rangle \} \{ \langle a_4 \rangle \} \{ \langle a_5 \rangle \} \{ \langle a_6 \rangle \} ;$$

where each $\langle a_i \rangle$ is exactly 4 digits (ranging from 0000 to 9999), except $\langle a_1 \rangle$, which may be any “not-too-large” non-negative integer, with or without leading zeros. Here, “not-too-large” depends on the specific function (see the corresponding comments for details). Checking for overflow is the responsibility of the code calling those functions. The fixed point number a corresponding to the representation above is $a = \sum_{i=1}^6 \langle a_i \rangle \cdot 10^{-4i}$.

Most functions we define here have the form

$\backslash_fp_fixed_ \langle calculation \rangle : wwn \langle operand_1 \rangle ; \langle operand_2 \rangle ; \{ \langle continuation \rangle \}$

They perform the $\langle calculation \rangle$ on the two $\langle operands \rangle$, then feed the result (6 brace groups followed by a semicolon) to the $\langle continuation \rangle$, responsible for the next step of the calculation. Some functions only accept an N-type $\langle continuation \rangle$. This allows constructions such as

$\backslash_fp_fixed_add : wwn \langle X_1 \rangle ; \langle X_2 \rangle ;$
 $\backslash_fp_fixed_mul : wwn \langle X_3 \rangle ;$
 $\backslash_fp_fixed_add : wwn \langle X_4 \rangle ;$

to compute $(X_1 + X_2) \cdot X_3 + X_4$. This turns out to be very appropriate for computing continued fractions and Taylor series.

At the end of the calculation, the result is turned back to a floating point number using $\backslash_fp_fixed_to_float_o : wN$. This function has to change the exponent of the floating point number: it must be used after starting an integer expression for the overall exponent of the result.

27.2 Helpers for numbers with extended precision

$\backslash c_fp_one_fixed_tl$ The fixed-point number 1, used in l3fp-expo.

14442 $\backslash tl_const : Nn \backslash c_fp_one_fixed_tl$
 14443 $\{ \{ 10000 \} \{ 0000 \} \{ 0000 \} \{ 0000 \} \{ 0000 \} \{ 0000 \} ; \}$

(End definition for $\backslash c_fp_one_fixed_tl$.)

$\backslash_fp_fixed_continue : wn$ This function simply calls the next function.

14444 $\backslash cs_new : Npn \backslash_fp_fixed_continue : wn \#1 ; \#2 \{ \#2 \#1 ; \}$

(End definition for `_fp_fixed_continue:wn`.)

`_fp_fixed_add_one:wn` `_fp_fixed_add_one:wn` $\langle a \rangle$; $\langle continuation \rangle$
This function adds 1 to the fixed point $\langle a \rangle$, by changing a_1 to $10000 + a_1$, then calls the $\langle continuation \rangle$. This requires $a_1 + 10000 < 2^{31}$.

```

14445 \cs_new:Npn \_fp_fixed_add_one:wn #1#2; #3
14446 {
14447   \exp_after:wn #3 \exp_after:wn
14448   { \_int_value:w \_int_eval:w \c\_fp_myriad_int + #1 } #2 ;
14449 }

```

(End definition for `_fp_fixed_add_one:wn`.)

`_fp_fixed_div_myriad:wn` Divide a fixed point number by 10000. This is a little bit more subtle than just removing the last group and adding a leading group of zeros: the first group #1 may have any number of digits, and we must split #1 into the new first group and a second group of exactly 4 digits. The choice of shifts allows #1 to be in the range $[0, 5 \cdot 10^8 - 1]$.

```

14450 \cs_new:Npn \_fp_fixed_div_myriad:wn #1#2#3#4#5#6;
14451 {
14452   \exp_after:wn \_fp_fixed_mul_after:wn
14453   \_int_value:w \_int_eval:w \c\_fp_leading_shift_int
14454   \exp_after:wn \_fp_pack:NNNNNw
14455   \_int_value:w \_int_eval:w \c\_fp_trailing_shift_int
14456   + #1 ; {#2}{#3}{#4}{#5};
14457 }

```

(End definition for `_fp_fixed_div_myriad:wn`.)

`_fp_fixed_mul_after:wn` The fixed point operations which involve multiplication end by calling this auxiliary. It braces the last block of digits, and places the $\langle continuation \rangle$ #3 in front.

```

14458 \cs_new:Npn \_fp_fixed_mul_after:wn #1; #2; #3 { #3 {#1} #2; }

```

(End definition for `_fp_fixed_mul_after:wn`.)

27.3 Multiplying a fixed point number by a short one

`_fp_fixed_mul_short:wn`
 $\{ \langle a_1 \rangle \} \{ \langle a_2 \rangle \} \{ \langle a_3 \rangle \} \{ \langle a_4 \rangle \} \{ \langle a_5 \rangle \} \{ \langle a_6 \rangle \}$;
 $\{ \langle b_0 \rangle \} \{ \langle b_1 \rangle \} \{ \langle b_2 \rangle \}$; $\{ \langle continuation \rangle \}$

Computes the product $c = ab$ of $a = \sum_i \langle a_i \rangle 10^{-4i}$ and $b = \sum_i \langle b_i \rangle 10^{-4i}$, rounds it to the closest multiple of 10^{-24} , and leaves $\langle continuation \rangle \{ \langle c_1 \rangle \} \dots \{ \langle c_6 \rangle \}$; in the input stream, where each of the $\langle c_i \rangle$ are blocks of 4 digits, except $\langle c_1 \rangle$, which is any $\text{T}_{\text{E}}\text{X}$ integer. Note that indices for $\langle b \rangle$ start at 0: for instance a second operand of $\{0001\}\{0000\}\{0000\}$ leaves the first operand unchanged (rather than dividing it by 10^4 , as `_fp_fixed_mul:wn` would).

```

14459 \cs_new:Npn \_fp_fixed_mul_short:wn #1#2#3#4#5#6; #7#8#9;
14460 {
14461   \exp_after:wn \_fp_fixed_mul_after:wn
14462   \_int_value:w \_int_eval:w \c\_fp_leading_shift_int
14463   + #1*#7
14464   \exp_after:wn \_fp_pack:NNNNNw
14465   \_int_value:w \_int_eval:w \c\_fp_middle_shift_int
14466   + #1*#8 + #2*#7

```



```

14467      \exp_after:wN \_fp_pack:NNNNNw
14468      \_int_value:w \_int_eval:w \c\_fp\_middle\_shift\_int
14469      + #1*#9 + #2*#8 + #3*#7
14470      \exp_after:wN \_fp_pack:NNNNNw
14471      \_int_value:w \_int_eval:w \c\_fp\_middle\_shift\_int
14472      + #2*#9 + #3*#8 + #4*#7
14473      \exp_after:wN \_fp_pack:NNNNNw
14474      \_int_value:w \_int_eval:w \c\_fp\_middle\_shift\_int
14475      + #3*#9 + #4*#8 + #5*#7
14476      \exp_after:wN \_fp_pack:NNNNNw
14477      \_int_value:w \_int_eval:w \c\_fp\_trailing\_shift\_int
14478      + #4*#9 + #5*#8 + #6*#7
14479      + ( #5*#9 + #6*#8 + #6*#9 / \c\_fp\_myriad\_int )
14480      / \c\_fp\_myriad\_int ; ;
14481  }

```

(End definition for `_fp_fixed_mul_short:wnn`.)

27.4 Dividing a fixed point number by a small integer

```

\_fp\_fixed\_div\_int:wwN
\_fp\_fixed\_div\_int:wnN
\_fp\_fixed\_div\_int\_auxii:wnn
  \_fp\_fixed\_div\_int\_auxii:wnn
\_fp\_fixed\_div\_int\_pack:Nw
\_fp\_fixed\_div\_int\_after:Nw

```

`_fp_fixed_div_int:wwN` $\langle a \rangle$; $\langle n \rangle$; $\langle continuation \rangle$
 Divides the fixed point number $\langle a \rangle$ by the (small) integer $0 < \langle n \rangle < 10^4$ and feeds the result to the $\langle continuation \rangle$. There is no bound on a_1 .

The arguments of the `i` auxiliary are 1: one of the a_i , 2: n , 3: the `ii` or the `iii` auxiliary. It computes a (somewhat tight) lower bound Q_i for the ratio a_i/n .

The `ii` auxiliary receives Q_i , n , and a_i as arguments. It adds Q_i to a surrounding integer expression, and starts a new one with the initial value 9999, which ensures that the result of this expression has 5 digits. The auxiliary also computes $a_i - n \cdot Q_i$, placing the result in front of the 4 digits of a_{i+1} . The resulting $a'_{i+1} = 10^4(a_i - n \cdot Q_i) + a_{i+1}$ serves as the first argument for a new call to the `i` auxiliary.

When the `iii` auxiliary is called, the situation looks like this:

```

\_fp\_fixed\_div\_int\_after:Nw  $\langle continuation \rangle$ 
-1 +  $Q_1$ 
\_fp\_fixed\_div\_int\_pack:Nw 9999 +  $Q_2$ 
\_fp\_fixed\_div\_int\_pack:Nw 9999 +  $Q_3$ 
\_fp\_fixed\_div\_int\_pack:Nw 9999 +  $Q_4$ 
\_fp\_fixed\_div\_int\_pack:Nw 9999 +  $Q_5$ 
\_fp\_fixed\_div\_int\_pack:Nw 9999
\_fp\_fixed\_div\_int\_auxii:wnn  $Q_6$  ; { $\langle n \rangle$ } { $\langle a_6 \rangle$ }

```

where expansion is happening from the last line up. The `iii` auxiliary adds $Q_6 + 2 \simeq a_6/n + 1$ to the last 9999, giving the integer closest to $10000 + a_6/n$.

Each `pack` auxiliary receives 5 digits followed by a semicolon. The first digit is added as a carry to the integer expression above, and the 4 other digits are braced. Each call to the `pack` auxiliary thus produces one brace group. The last brace group is produced by the `after` auxiliary, which places the $\langle continuation \rangle$ as appropriate.

```

14482 \cs_new:Npn \_fp\_fixed\_div\_int:wwN #1#2#3#4#5#6 ; #7 ; #8
14483 {
14484   \exp_after:wN \_fp\_fixed\_div\_int\_after:Nw
14485   \exp_after:wN #8
14486   \_int_value:w \_int_eval:w - 1

```

```

14487     \__fp_fixed_div_int:wnN
14488     #1; {#7} \__fp_fixed_div_int_auxi:wnn
14489     #2; {#7} \__fp_fixed_div_int_auxi:wnn
14490     #3; {#7} \__fp_fixed_div_int_auxi:wnn
14491     #4; {#7} \__fp_fixed_div_int_auxi:wnn
14492     #5; {#7} \__fp_fixed_div_int_auxi:wnn
14493     #6; {#7} \__fp_fixed_div_int_auxii:wnn ;
14494 }
14495 \cs_new:Npn \__fp_fixed_div_int:wnN #1; #2 #3
14496 {
14497     \exp_after:wN #3
14498     \__int_value:w \__int_eval:w #1 / #2 - 1 ;
14499     {#2}
14500     {#1}
14501 }
14502 \cs_new:Npn \__fp_fixed_div_int_auxi:wnn #1; #2 #3
14503 {
14504     + #1
14505     \exp_after:wN \__fp_fixed_div_int_pack:Nw
14506     \__int_value:w \__int_eval:w 9999
14507     \exp_after:wN \__fp_fixed_div_int:wnN
14508     \__int_value:w \__int_eval:w #3 - #1*#2 \__int_eval_end:
14509 }
14510 \cs_new:Npn \__fp_fixed_div_int_auxii:wnn #1; #2 #3 { + #1 + 2 ; }
14511 \cs_new:Npn \__fp_fixed_div_int_pack:Nw #1 #2; { + #1; {#2} }
14512 \cs_new:Npn \__fp_fixed_div_int_after:Nw #1 #2; { #1 {#2} }

```

(End definition for `__fp_fixed_div_int:wnN` and others.)

27.5 Adding and subtracting fixed points

`__fp_fixed_add:wnn` `__fp_fixed_add:wnn <a> ; ; {<continuation>}`
`__fp_fixed_sub:wnn` Computes $a + b$ (resp. $a - b$) and feeds the result to the $\langle continuation \rangle$. This function
`__fp_fixed_add:Nnnnnwnn` requires $0 \leq a_1, b_1 \leq 114748$, its result must be positive (this happens automatically for
`__fp_fixed_add:nnNnnwnn` addition) and its first group must have at most 5 digits: $(a \pm b)_1 < 100000$. The two
`__fp_fixed_add_pack:NNNNNwnn` functions only differ by a sign, hence use a common auxiliary. It would be nice to grab
`__fp_fixed_add_after:NNNNNwnn` the 12 brace groups in one go; only 9 parameters are allowed. Start by grabbing the sign,
 a_1, \dots, a_4 , the rest of a , and b_1 and b_2 . The second auxiliary receives the rest of a , the
sign multiplying b , the rest of b , and the $\langle continuation \rangle$ as arguments. After going down
through the various level, we go back up, packing digits and bringing the $\langle continuation \rangle$
(#8, then #7) from the end of the argument list to its start.

```

14513 \cs_new:Npn \__fp_fixed_add:wnn { \__fp_fixed_add:Nnnnnwnn + }
14514 \cs_new:Npn \__fp_fixed_sub:wnn { \__fp_fixed_add:Nnnnnwnn - }
14515 \cs_new:Npn \__fp_fixed_add:Nnnnnwnn #1 #2#3#4#5 #6; #7#8
14516 {
14517     \exp_after:wN \__fp_fixed_add_after:NNNNNwnn
14518     \__int_value:w \__int_eval:w 9 9999 9998 + #2#3 #1 #7#8
14519     \exp_after:wN \__fp_fixed_add_pack:NNNNNwnn
14520     \__int_value:w \__int_eval:w 1 9999 9998 + #4#5
14521     \__fp_fixed_add:nnNnnwnn #6 #1
14522 }
14523 \cs_new:Npn \__fp_fixed_add:nnNnnwnn #1#2 #3 #4#5 #6#7 ; #8
14524 {

```

```

14525      #3 #4#5
14526      \exp_after:wN \_fp_fixed_add_pack:NNNNNwn
14527      \_int_value:w \_int_eval:w 2 0000 0000 #3 #6#7 + #1#2 ; {#8} ;
14528    }
14529 \cs_new:Npn \_fp_fixed_add_pack:NNNNNwn #1 #2#3#4#5 #6; #7
14530 { + #1 ; {#7} {#2#3#4#5} {#6} }
14531 \cs_new:Npn \_fp_fixed_add_after:NNNNNwn 1 #1 #2#3#4#5 #6; #7
14532 { #7 {#1#2#3#4#5} {#6} }

```

(End definition for `_fp_fixed_add:wnn` and others.)

27.6 Multiplying fixed points

```

\_fp_fixed_mul:wnn
\_fp_fixed_mul:nnnnnnnw

```

`_fp_fixed_mul:wnn` $\langle a \rangle$; $\langle b \rangle$; $\{\langle continuation \rangle\}$
 Computes $a \times b$ and feeds the result to $\langle continuation \rangle$. This function requires $0 \leq a_1, b_1 < 10000$. Once more, we need to play around the limit of 9 arguments for \TeX macros. Note that we don't need to obtain an exact rounding, contrarily to the `*` operator, so things could be harder. We wish to perform carries in

$$\begin{aligned}
 a \times b = & a_1 \cdot b_1 \cdot 10^{-8} \\
 & + (a_1 \cdot b_2 + a_2 \cdot b_1) \cdot 10^{-12} \\
 & + (a_1 \cdot b_3 + a_2 \cdot b_2 + a_3 \cdot b_1) \cdot 10^{-16} \\
 & + (a_1 \cdot b_4 + a_2 \cdot b_3 + a_3 \cdot b_2 + a_4 \cdot b_1) \cdot 10^{-20} \\
 & + \left(a_2 \cdot b_4 + a_3 \cdot b_3 + a_4 \cdot b_2 \right. \\
 & \quad \left. + \frac{a_3 \cdot b_4 + a_4 \cdot b_3 + a_1 \cdot b_6 + a_2 \cdot b_5 + a_5 \cdot b_2 + a_6 \cdot b_1}{10^4} \right. \\
 & \quad \left. + a_1 \cdot b_5 + a_5 \cdot b_1 \right) \cdot 10^{-24} + O(10^{-24}),
 \end{aligned}$$

where the $O(10^{-24})$ stands for terms which are at most $5 \cdot 10^{-24}$; ignoring those leads to an error of at most 5 ulp. Note how the first 15 terms only depend on a_1, \dots, a_4 and b_1, \dots, b_4 , while the last 6 terms only depend on a_1, a_2, a_5, a_6 , and the corresponding parts of b . Hence, the first function grabs a_1, \dots, a_4 , the rest of a , and b_1, \dots, b_4 , and writes the 15 first terms of the expression, including a left parenthesis for the fraction. The `i` auxiliary receives $a_5, a_6, b_1, b_2, a_1, a_2, b_5, b_6$ and finally the $\langle continuation \rangle$ as arguments. It writes the end of the expression, including the right parenthesis and the denominator of the fraction. The $\langle continuation \rangle$ is finally placed in front of the 6 brace groups by `_fp_fixed_mul_after:wnn`.

```

14533 \cs_new:Npn \_fp_fixed_mul:wnn #1#2#3#4 #5; #6#7#8#9
14534 {
14535   \exp_after:wN \_fp_fixed_mul_after:wnn
14536   \_int_value:w \_int_eval:w \c__fp_leading_shift_int
14537   \exp_after:wN \_fp_pack:NNNNNw
14538   \_int_value:w \_int_eval:w \c__fp_middle_shift_int
14539   + #1*#6
14540   \exp_after:wN \_fp_pack:NNNNNw
14541   \_int_value:w \_int_eval:w \c__fp_middle_shift_int
14542   + #1*#7 + #2*#6
14543   \exp_after:wN \_fp_pack:NNNNNw
14544   \_int_value:w \_int_eval:w \c__fp_middle_shift_int

```

```

14545         + #1*#8 + #2*#7 + #3*#6
14546         \exp_after:wN \__fp_pack:NNNNNw
14547         \__int_value:w \__int_eval:w \c__fp_middle_shift_int
14548         + #1*#9 + #2*#8 + #3*#7 + #4*#6
14549         \exp_after:wN \__fp_pack:NNNNNw
14550         \__int_value:w \__int_eval:w \c__fp_trailing_shift_int
14551         + #2*#9 + #3*#8 + #4*#7
14552         + ( #3*#9 + #4*#8
14553         + \__fp_fixed_mul:nnnnnnnw #5 {#6}{#7} {#1}{#2}
14554     }
14555 \cs_new:Npn \__fp_fixed_mul:nnnnnnnw #1#2 #3#4 #5#6 #7#8 ;
14556 {
14557     #1*#4 + #2*#3 + #5*#8 + #6*#7 ) / \c__fp_myriad_int
14558     + #1*#3 + #5*#7 ; ;
14559 }

```

(End definition for __fp_fixed_mul:wnn and __fp_fixed_mul:nnnnnnnw.)

27.7 Combining product and sum of fixed points

```

\__fp_fixed_mul_add:wwwn
\__fp_fixed_mul_sub_back:wwwn
\__fp_fixed_mul_one_minus_mul:wnn

```

```

\__fp_fixed_mul_add:wwwn <a> ; <b> ; <c> ; {<continuation>}
\__fp_fixed_mul_sub_back:wwwn <a> ; <b> ; <c> ; {<continuation>}
\__fp_fixed_one_minus_mul:wnn <a> ; <b> ; {<continuation>}

```

Compute $a \times b + c$, $c - a \times b$, and $1 - a \times b$ and feed the result to the $\langle continuation \rangle$. Those functions require $0 \leq a_1, b_1, c_1 \leq 10000$. Since those functions are at the heart of the computation of Taylor expansions, we over-optimize them a bit, and in particular we do not factor out the common parts of the three functions.

For definiteness, consider the task of computing $a \times b + c$. We perform carries in

$$\begin{aligned}
 a \times b + c = & (a_1 \cdot b_1 + c_1 c_2) \cdot 10^{-8} \\
 & + (a_1 \cdot b_2 + a_2 \cdot b_1) \cdot 10^{-12} \\
 & + (a_1 \cdot b_3 + a_2 \cdot b_2 + a_3 \cdot b_1 + c_3 c_4) \cdot 10^{-16} \\
 & + (a_1 \cdot b_4 + a_2 \cdot b_3 + a_3 \cdot b_2 + a_4 \cdot b_1) \cdot 10^{-20} \\
 & + \left(a_2 \cdot b_4 + a_3 \cdot b_3 + a_4 \cdot b_2 \right. \\
 & \quad \left. + \frac{a_3 \cdot b_4 + a_4 \cdot b_3 + a_1 \cdot b_6 + a_2 \cdot b_5 + a_5 \cdot b_2 + a_6 \cdot b_1}{10^4} \right. \\
 & \quad \left. + a_1 \cdot b_5 + a_5 \cdot b_1 + c_5 c_6 \right) \cdot 10^{-24} + O(10^{-24}),
 \end{aligned}$$

where $c_1 c_2$, $c_3 c_4$, $c_5 c_6$ denote the 8-digit number obtained by juxtaposing the two blocks of digits of c , and \cdot denotes multiplication. The task is obviously tough because we have 18 brace groups in front of us.

Each of the three function starts the first two levels (the first, corresponding to 10^{-4} , is empty), with $c_1 c_2$ in the first level, calls the i auxiliary with arguments described later, and adds a trailing $+ c_5 c_6$; $\{ \langle continuation \rangle \}$; . The $+ c_5 c_6$ piece, which is omitted for $\backslash_\text{fp_fixed_one_minus_mul:wnn}$, is taken in the integer expression for the 10^{-24} level.

```

14560 \cs_new:Npn \__fp_fixed_mul_add:wwwn #1; #2; #3#4#5#6#7#8;
14561 {
14562     \exp_after:wN \__fp_fixed_mul_after:wnn
14563     \__int_value:w \__int_eval:w \c__fp_big_leading_shift_int

```

```

14564     \exp_after:wN \_fp_pack_big:NNNNNNw
14565     \_int_value:w \_int_eval:w \c\_fp_big_middle_shift_int + #3 #4
14566     \_fp_fixed_mul_add:Nwnnnwnnn +
14567         + #5 #6 ; #2 ; #1 ; #2 ; +
14568         + #7 #8 ; ;
14569 }
14570 \cs_new:Npn \_fp_fixed_mul_sub_back:wwn #1; #2; #3#4#5#6#7#8;
14571 {
14572     \exp_after:wN \_fp_fixed_mul_after:wwn
14573     \_int_value:w \_int_eval:w \c\_fp_big_leading_shift_int
14574     \exp_after:wN \_fp_pack_big:NNNNNNw
14575     \_int_value:w \_int_eval:w \c\_fp_big_middle_shift_int + #3 #4
14576     \_fp_fixed_mul_add:Nwnnnwnnn -
14577         + #5 #6 ; #2 ; #1 ; #2 ; -
14578         + #7 #8 ; ;
14579 }
14580 \cs_new:Npn \_fp_fixed_one_minus_mul:wwn #1; #2;
14581 {
14582     \exp_after:wN \_fp_fixed_mul_after:wwn
14583     \_int_value:w \_int_eval:w \c\_fp_big_leading_shift_int
14584     \exp_after:wN \_fp_pack_big:NNNNNNw
14585     \_int_value:w \_int_eval:w \c\_fp_big_middle_shift_int + 1 0000 0000
14586     \_fp_fixed_mul_add:Nwnnnwnnn -
14587         ; #2 ; #1 ; #2 ; -
14588         ; ;
14589 }

```

(End definition for `_fp_fixed_mul_add:wwn`, `_fp_fixed_mul_sub_back:wwn`, and `_fp_fixed_mul_one_minus_mul:wwn`.)

`_fp_fixed_mul_add:Nwnnnwnnn`

$$_fp_fixed_mul_add:Nwnnnwnnn \langle op \rangle + \langle c_3 \rangle \langle c_4 \rangle ;$$

$$\langle b \rangle ; \langle a \rangle ; \langle b \rangle ; \langle op \rangle$$

$$+ \langle c_5 \rangle \langle c_6 \rangle ;$$

Here, $\langle op \rangle$ is either $+$ or $-$. Arguments $\#3$, $\#4$, $\#5$ are $\langle b_1 \rangle$, $\langle b_2 \rangle$, $\langle b_3 \rangle$; arguments $\#7$, $\#8$, $\#9$ are $\langle a_1 \rangle$, $\langle a_2 \rangle$, $\langle a_3 \rangle$. We can build three levels: $a_1 \cdot b_1$ for 10^{-8} , $(a_1 \cdot b_2 + a_2 \cdot b_1)$ for 10^{-12} , and $(a_1 \cdot b_3 + a_2 \cdot b_2 + a_3 \cdot b_1 + c_3 c_4)$ for 10^{-16} . The a - b products use the sign $\#1$. Note that $\#2$ is empty for `_fp_fixed_one_minus_mul:wwn`. We call the *ii* auxiliary for levels 10^{-20} and 10^{-24} , keeping the pieces of $\langle a \rangle$ we've read, but not $\langle b \rangle$, since there is another copy later in the input stream.

```

14590 \cs_new:Npn \_fp_fixed_mul_add:Nwnnnwnnn #1 #2; #3#4#5#6; #7#8#9
14591 {
14592     #1 #7*#3
14593     \exp_after:wN \_fp_pack_big:NNNNNNw
14594     \_int_value:w \_int_eval:w \c\_fp_big_middle_shift_int
14595     #1 #7*#4 #1 #8*#3
14596     \exp_after:wN \_fp_pack_big:NNNNNNw
14597     \_int_value:w \_int_eval:w \c\_fp_big_middle_shift_int
14598     #1 #7*#5 #1 #8*#4 #1 #9*#3 #2
14599     \exp_after:wN \_fp_pack_big:NNNNNNw
14600     \_int_value:w \_int_eval:w \c\_fp_big_middle_shift_int
14601     #1 \_fp_fixed_mul_add:nnnnwnnn {#7}{#8}{#9}
14602 }

```

(End definition for `_fp_fixed_mul_add:Nwnnnwnnn`.)

_fp_fixed_mul_add:nnnnwnnnn

_fp_fixed_mul_add:nnnnwnnnn $\langle a \rangle$; $\langle b \rangle$; $\langle op \rangle$
 $+ \langle c_5 \rangle \langle c_6 \rangle$;

Level 10^{-20} is $(a_1 \cdot b_4 + a_2 \cdot b_3 + a_3 \cdot b_2 + a_4 \cdot b_1)$, multiplied by the sign, which was inserted by the *i* auxiliary. Then we prepare level 10^{-24} . We don't have access to all parts of $\langle a \rangle$ and $\langle b \rangle$ needed to make all products. Instead, we prepare the partial expressions

$$b_1 + a_4 \cdot b_2 + a_3 \cdot b_3 + a_2 \cdot b_4 + a_1$$

$$b_2 + a_4 \cdot b_3 + a_3 \cdot b_4 + a_2.$$

Obviously, those expressions make no mathematical sense: we complete them with $a_5 \cdot$ and $\cdot b_5$, and with $a_6 \cdot b_1 + a_5 \cdot$ and $\cdot b_5 + a_1 \cdot b_6$, and of course with the trailing $+ c_5 c_6$. To do all this, we keep a_1, a_5, a_6 , and the corresponding pieces of $\langle b \rangle$.

```

14603 \cs_new:Npn \_fp_fixed_mul_add:nnnnwnnnn #1#2#3#4#5; #6#7#8#9
14604 {
14605   ( #1*#9 + #2*#8 + #3*#7 + #4*#6 )
14606   \exp_after:wN \_fp_pack_big:NNNNNNw
14607   \__int_value:w \__int_eval:w \c_fp_big_trailing_shift_int
14608   \_fp_fixed_mul_add:nnnnwnnwN
14609   { #6 + #4*#7 + #3*#8 + #2*#9 + #1 }
14610   { #7 + #4*#8 + #3*#9 + #2 }
14611   {#1} #5;
14612   {#6}
14613 }
```

(End definition for _fp_fixed_mul_add:nnnnwnnnn.)

_fp_fixed_mul_add:nnnnwnnwN

_fp_fixed_mul_add:nnnnwnnwN $\{\langle partial_1 \rangle\} \{\langle partial_2 \rangle\}$
 $\{\langle a_1 \rangle\} \{\langle a_5 \rangle\} \{\langle a_6 \rangle\}$; $\{\langle b_1 \rangle\} \{\langle b_5 \rangle\} \{\langle b_6 \rangle\}$;
 $\langle op \rangle + \langle c_5 \rangle \langle c_6 \rangle$;

Complete the $\langle partial_1 \rangle$ and $\langle partial_2 \rangle$ expressions as explained for the *ii* auxiliary. The second one is divided by 10000: this is the carry from level 10^{-28} . The trailing $+ c_5 c_6$ is taken into the expression for level 10^{-24} . Note that the total of level 10^{-24} is in the interval $[-5 \cdot 10^8, 6 \cdot 10^8]$ (give or take a couple of 10000), hence adding it to the shift gives a 10-digit number, as expected by the packing auxiliaries. See *l3fp-aux* for the definition of the shifts and packing auxiliaries.

```

14614 \cs_new:Npn \_fp_fixed_mul_add:nnnnwnnwN #1#2 #3#4#5; #6#7#8; #9
14615 {
14616   #9 (#4* #1 *#7)
14617   #9 (#5*#6+#4* #2 *#7+#3*#8) / \c_fp_myriad_int
14618 }
```

(End definition for _fp_fixed_mul_add:nnnnwnnwN.)

27.8 Extended-precision floating point numbers

In this section we manipulate floating point numbers with roughly 24 significant figures (“extended-precision” numbers, in short, “ep”), which take the form of an integer exponent, followed by a comma, then six groups of digits, ending with a semicolon. The first group of digit may be any non-negative integer, while other groups of digits have 4 digits. In other words, an extended-precision number is an exponent ending in a comma, then a fixed point number. The corresponding value is $0.\langle digits \rangle \cdot 10^{\langle exponent \rangle}$. This convention differs from floating points.

`__fp_ep_to_fixed:wwn` Converts an extended-precision number with an exponent at most 4 and a first block less than 10^8 to a fixed point number whose first block has 12 digits, hopefully starting with many zeros.
`__fp_ep_to_fixed_auxi:www`
`__fp_ep_to_fixed_auxii:nnnnnnnnwn`

```

14619 \cs_new:Npn __fp_ep_to_fixed:wwn #1,#2
14620 {
14621   \exp_after:wN __fp_ep_to_fixed_auxi:www
14622   \__int_value:w \__int_eval:w 1 0000 0000 + #2 \exp_after:wN ;
14623   \exp:w \exp_end_continue_f:w
14624   \prg_replicate:nn { 4 - \int_max:nn {#1} { -32 } } { 0 } ;
14625 }
14626 \cs_new:Npn __fp_ep_to_fixed_auxi:www 1#1; #2; #3#4#5#6#7;
14627 {
14628   __fp_pack_eight:wnnnnnnnnn
14629   __fp_pack_twice_four:wnnnnnnnnn
14630   __fp_pack_twice_four:wnnnnnnnnn
14631   __fp_pack_twice_four:wnnnnnnnnn
14632   __fp_ep_to_fixed_auxii:nnnnnnnnwn ;
14633   #2 #1#3#4#5#6#7 0000 !
14634 }
14635 \cs_new:Npn __fp_ep_to_fixed_auxii:nnnnnnnnwn #1#2#3#4#5#6#7; #8! #9
14636 { #9 {#1#2}{#3}{#4}{#5}{#6}{#7}; }

```

(End definition for `__fp_ep_to_fixed:wwn`, `__fp_ep_to_fixed_auxi:www`, and `__fp_ep_to_fixed_auxii:nnnnnnnnwn`.)

`__fp_ep_to_ep:wwN` Normalize an extended-precision number. More precisely, leading zeros are removed from the mantissa of the argument, decreasing its exponent as appropriate. Then the digits are packed into 6 groups of 4 (discarding any remaining digit, not rounding). Finally, the continuation #8 is placed before the resulting exponent-mantissa pair. The input exponent may in fact be given as an integer expression. The `loop` auxiliary grabs a digit: if it is 0, decrement the exponent and continue looping, and otherwise call the `end` auxiliary, which places all digits in the right order (the digit that was not 0, and any remaining digits), followed by some 0, then packs them up neatly in $3 \times 2 = 6$ blocks of four. At the end of the day, remove with `__fp_use_i:ww` any digit that did not make it in the final mantissa (typically only zeros, unless the original first block has more than 4 digits).
`__fp_ep_to_ep_loop:N`
`__fp_ep_to_ep_end:www`
`__fp_ep_to_ep_zero:ww`

```

14637 \cs_new:Npn __fp_ep_to_ep:wwN #1,#2#3#4#5#6#7; #8
14638 {
14639   \exp_after:wN #8
14640   \__int_value:w \__int_eval:w #1 + 4
14641   \exp_after:wN \use_i:nn
14642   \exp_after:wN __fp_ep_to_ep_loop:N
14643   \__int_value:w \__int_eval:w 1 0000 0000 + #2 \__int_eval_end:
14644   #3#4#5#6#7 ; ; !
14645 }
14646 \cs_new:Npn __fp_ep_to_ep_loop:N #1
14647 {
14648   \if_meaning:w 0 #1
14649   - 1
14650   \else:
14651     __fp_ep_to_ep_end:www #1
14652   \fi:
14653   __fp_ep_to_ep_loop:N

```

```

14654 }
14655 \cs_new:Npn \__fp_ep_to_ep_end:www
14656   #1 \fi: \__fp_ep_to_ep_loop:N #2; #3!
14657 {
14658   \fi:
14659   \if_meaning:w ; #1
14660     - 2 * \c_fp_max_exponent_int
14661     \__fp_ep_to_ep_zero:ww
14662   \fi:
14663   \__fp_pack_twice_four:wNNNNNNNN
14664   \__fp_pack_twice_four:wNNNNNNNN
14665   \__fp_pack_twice_four:wNNNNNNNN
14666   \__fp_use_i:ww , ;
14667   #1 #2 0000 0000 0000 0000 0000 0000 ;
14668 }
14669 \cs_new:Npn \__fp_ep_to_ep_zero:ww \fi: #1; #2; #3;
14670 { \fi: , {1000}{0000}{0000}{0000}{0000}{0000} ; }

```

(End definition for __fp_ep_to_ep:wwN and others.)

__fp_ep_compare:www
__fp_ep_compare_aux:www

In l3fp-trig we need to compare two extended-precision numbers. This is based on the same function for positive floating point numbers, with an extra test if comparing only 16 decimals is not enough to distinguish the numbers. Note that this function only works if the numbers are normalized so that their first block is in [1000,9999].

```

14671 \cs_new:Npn \__fp_ep_compare:www #1,#2#3#4#5#6#7;
14672 { \__fp_ep_compare_aux:www {#1}{#2}{#3}{#4}{#5}; #6#7; }
14673 \cs_new:Npn \__fp_ep_compare_aux:www #1;#2;#3;#4#5#6#7#8#9;
14674 {
14675   \if_case:w
14676     \__fp_compare_npos:nwnw #1; {#3}{#4}{#5}{#6}{#7}; \exp_stop_f:
14677     \if_int_compare:w #2 = #8#9 \exp_stop_f:
14678       0
14679     \else:
14680       \if_int_compare:w #2 < #8#9 - \fi: 1
14681     \fi:
14682   \or: 1
14683   \else: -1
14684   \fi:
14685 }

```

(End definition for __fp_ep_compare:www and __fp_ep_compare_aux:www.)

__fp_ep_mul:wwwN
__fp_ep_mul_raw:wwwN

Multiply two extended-precision numbers: first normalize them to avoid losing too much precision, then multiply the mantissas #2 and #4 as fixed point numbers, and sum the exponents #1 and #3. The result's first block is in [100,9999].

```

14686 \cs_new:Npn \__fp_ep_mul:wwwN #1,#2; #3,#4;
14687 {
14688   \__fp_ep_to_ep:wwN #3,#4;
14689   \__fp_fixed_continue:wn
14690   {
14691     \__fp_ep_to_ep:wwN #1,#2;
14692     \__fp_ep_mul_raw:wwwN
14693   }
14694   \__fp_fixed_continue:wn

```



```

14695     }
14696 \cs_new:Npn \__fp_ep_mul_raw:wwwN #1,#2; #3,#4; #5
14697 {
14698     \__fp_fixed_mul:wn #2; #4;
14699     { \exp_after:wN #5 \__int_value:w \__int_eval:w #1 + #3 , }
14700 }

```

(End definition for `__fp_ep_mul:wwwN` and `__fp_ep_mul_raw:wwwN`.)

27.9 Dividing extended-precision numbers

Divisions of extended-precision numbers are difficult to perform with exact rounding: the technique used in `l3fp-basics` for 16-digit floating point numbers does not generalize easily to 24-digit numbers. Thankfully, there is no need for exact rounding.

Let us call $\langle n \rangle$ the numerator and $\langle d \rangle$ the denominator. After a simple normalization step, we can assume that $\langle n \rangle \in [0.1, 1)$ and $\langle d \rangle \in [0.1, 1)$, and compute $\langle n \rangle / (10 \langle d \rangle) \in (0.01, 1)$. In terms of the 6 blocks of digits $\langle n_1 \rangle \cdots \langle n_6 \rangle$ and the 6 blocks $\langle d_1 \rangle \cdots \langle d_6 \rangle$, the condition translates to $\langle n_1 \rangle, \langle d_1 \rangle \in [1000, 9999]$.

We first find an integer estimate $a \simeq 10^8 / \langle d \rangle$ by computing

$$\alpha = \left\lceil \frac{10^9}{\langle d_1 \rangle + 1} \right\rceil$$

$$\beta = \left\lfloor \frac{10^9}{\langle d_1 \rangle} \right\rfloor$$

$$a = 10^3 \alpha + (\beta - \alpha) \cdot \left(10^3 - \left\lfloor \frac{\langle d_2 \rangle}{10} \right\rfloor \right) - 1250,$$

where $\left\lceil \cdot \right\rceil$ denotes ε -TEX's rounding division, which rounds ties away from zero. The idea is to interpolate between $10^3 \alpha$ and $10^3 \beta$ with a parameter $\langle d_2 \rangle / 10^4$, so that when $\langle d_2 \rangle = 0$ one gets $a = 10^3 \beta - 1250 \simeq 10^{12} / \langle d_1 \rangle \simeq 10^8 / \langle d \rangle$, while when $\langle d_2 \rangle = 9999$ one gets $a = 10^3 \alpha - 1250 \simeq 10^{12} / (\langle d_1 \rangle + 1) \simeq 10^8 / \langle d \rangle$. The shift by 1250 helps to ensure that a is an underestimate of the correct value. We shall prove that

$$1 - 1.755 \cdot 10^{-5} < \frac{\langle d \rangle a}{10^8} < 1.$$

We can then compute the inverse of $\langle d \rangle a / 10^8 = 1 - \epsilon$ using the relation $1 / (1 - \epsilon) \simeq (1 + \epsilon)(1 + \epsilon^2) + \epsilon^4$, which is correct up to a relative error of $\epsilon^5 < 1.6 \cdot 10^{-24}$. This allows us to find the desired ratio as

$$\frac{\langle n \rangle}{\langle d \rangle} = \frac{\langle n \rangle a}{10^8} ((1 + \epsilon)(1 + \epsilon^2) + \epsilon^4).$$

Let us prove the upper bound first (multiplied by 10^{15}). Note that $10^7 \langle d \rangle < 10^3 \langle d_1 \rangle + 10^{-1}(\langle d_2 \rangle + 1)$, and that ε -TEX's division $\left\lfloor \frac{\langle d_2 \rangle}{10} \right\rfloor$ underestimates $10^{-1}(\langle d_2 \rangle + 1)$ by 0.5 at

most, as can be checked for each possible last digit of $\langle d_2 \rangle$. Then,

$$10^7 \langle d \rangle a < \left(10^3 \langle d_1 \rangle + \left\lceil \frac{\langle d_2 \rangle}{10} \right\rceil + \frac{1}{2} \right) \left(\left(10^3 - \left\lceil \frac{\langle d_2 \rangle}{10} \right\rceil \right) \beta + \left\lceil \frac{\langle d_2 \rangle}{10} \right\rceil \alpha - 1250 \right) \quad (1)$$

$$< \left(10^3 \langle d_1 \rangle + \left\lceil \frac{\langle d_2 \rangle}{10} \right\rceil + \frac{1}{2} \right) \quad (2)$$

$$\left(\left(10^3 - \left\lceil \frac{\langle d_2 \rangle}{10} \right\rceil \right) \left(\frac{10^9}{\langle d_1 \rangle} + \frac{1}{2} \right) + \left\lceil \frac{\langle d_2 \rangle}{10} \right\rceil \left(\frac{10^9}{\langle d_1 \rangle + 1} + \frac{1}{2} \right) - 1250 \right) \quad (3)$$

$$< \left(10^3 \langle d_1 \rangle + \left\lceil \frac{\langle d_2 \rangle}{10} \right\rceil + \frac{1}{2} \right) \left(\frac{10^{12}}{\langle d_1 \rangle} - \left\lceil \frac{\langle d_2 \rangle}{10} \right\rceil \frac{10^9}{\langle d_1 \rangle (\langle d_1 \rangle + 1)} - 750 \right) \quad (4)$$

We recognize a quadratic polynomial in $[\langle d_2 \rangle / 10]$ with a negative leading coefficient: this polynomial is bounded above, according to $([\langle d_2 \rangle / 10] + a)(b - c[\langle d_2 \rangle / 10]) \leq (b + ca)^2 / (4c)$. Hence,

$$10^7 \langle d \rangle a < \frac{10^{15}}{\langle d_1 \rangle (\langle d_1 \rangle + 1)} \left(\langle d_1 \rangle + \frac{1}{2} + \frac{1}{4} 10^{-3} - \frac{3}{8} \cdot 10^{-9} \langle d_1 \rangle (\langle d_1 \rangle + 1) \right)^2$$

Since $\langle d_1 \rangle$ takes integer values within $[1000, 9999]$, it is a simple programming exercise to check that the squared expression is always less than $\langle d_1 \rangle (\langle d_1 \rangle + 1)$, hence $10^7 \langle d \rangle a < 10^{15}$. The upper bound is proven. We also find that $\frac{3}{8}$ can be replaced by slightly smaller numbers, but nothing less than $0.374563\dots$, and going back through the derivation of the upper bound, we find that 1250 is as small a shift as we can obtain without breaking the bound.

Now, the lower bound. The same computation as for the upper bound implies

$$10^7 \langle d \rangle a > \left(10^3 \langle d_1 \rangle + \left\lceil \frac{\langle d_2 \rangle}{10} \right\rceil - \frac{1}{2} \right) \left(\frac{10^{12}}{\langle d_1 \rangle} - \left\lceil \frac{\langle d_2 \rangle}{10} \right\rceil \frac{10^9}{\langle d_1 \rangle (\langle d_1 \rangle + 1)} - 1750 \right)$$

This time, we want to find the minimum of this quadratic polynomial. Since the leading coefficient is still negative, the minimum is reached for one of the extreme values $[y/10] = 0$ or $[y/10] = 100$, and we easily check the bound for those values.

We have proven that the algorithm gives us a precise enough answer. Incidentally, the upper bound that we derived tells us that $a < 10^8 / \langle d \rangle \leq 10^9$, hence we can compute a safely as a $\text{T}_{\text{E}}\text{X}$ integer, and even add 10^9 to it to ease grabbing of all the digits. The lower bound implies $10^8 - 1755 < a$, which we do not care about.

`_fp_ep_div:wwwn` Compute the ratio of two extended-precision numbers. The result is an extended-precision number whose first block lies in the range $[100, 9999]$, and is placed after the $\langle continuation \rangle$ once we are done. First normalize the inputs so that both first block lie in $[1000, 9999]$, then call `_fp_ep_div_esti:wwwn $\langle denominator \rangle$ $\langle numerator \rangle$` , responsible for estimating the inverse of the denominator.

```

14701 \cs_new:Npn \_fp\_ep\_div:wwwn #1,#2; #3,#4;
14702 {
14703   \_fp\_ep\_to\_ep:wwN #1,#2;
14704   \_fp\_fixed\_continue:wn
14705   {
14706     \_fp\_ep\_to\_ep:wwN #3,#4;
14707     \_fp\_ep\_div\_esti:wwwn
14708   }
14709 }
```

(End definition for `_fp_ep_div:wwwn`.)

`_fp_ep_div_esti:wwwn`
`_fp_ep_div_estii:wwnnwn`
`_fp_ep_div_estiii:NNNNNwwwn`

The **esti** function evaluates $\alpha = 10^9 / (\langle d_1 \rangle + 1)$, which is used twice in the expression for a , and combines the exponents **#1** and **#4** (with a shift by 1 because we later compute $\langle n \rangle / (10 \langle d \rangle)$). Then the **estii** function evaluates $10^9 + a$, and puts the exponent **#2** after the continuation **#7**: from there on we can forget exponents and focus on the mantissa. The **estiii** function multiplies the denominator **#7** by $10^{-8}a$ (obtained as a split into the single digit **#1** and two blocks of 4 digits, **#2#3#4#5** and **#6**). The result $10^{-8}a \langle d \rangle = (1 - \epsilon)$, and a partially packed $10^{-9}a$ (as a block of four digits, and five individual digits, not packed by lack of available macro parameters here) are passed to `_fp_ep_div_epsilon:wnNNNNn`, which computes $10^{-9}a / (1 - \epsilon)$, that is, $1 / (10 \langle d \rangle)$ and we finally multiply this by the numerator **#8**.

```

14710 \cs_new:Npn \_fp_ep_div_esti:wwwn #1,#2#3; #4,
14711 {
14712   \exp_after:wN \_fp_ep_div_estii:wwnnwn
14713   \__int_value:w \__int_eval:w 10 0000 0000 / ( #2 + 1 )
14714   \exp_after:wN ;
14715   \__int_value:w \__int_eval:w #4 - #1 + 1 ,
14716   {#2} #3;
14717 }
14718 \cs_new:Npn \_fp_ep_div_estii:wwnnwn #1; #2,#3#4#5; #6; #7
14719 {
14720   \exp_after:wN \_fp_ep_div_estiii:NNNNNwwwn
14721   \__int_value:w \__int_eval:w 10 0000 0000 - 1750
14722   + #1 000 + (10 0000 0000 / #3 - #1) * (1000 - #4 / 10) ;
14723   {#3}{#4}#5; #6; { #7 #2, }
14724 }
14725 \cs_new:Npn \_fp_ep_div_estiii:NNNNNwwwn 1#1#2#3#4#5#6; #7;
14726 {
14727   \_fp_fixed_mul_short:wnn #7; {#1}{#2#3#4#5}{#6};
14728   \_fp_ep_div_epsilon:wnNNNNn {#1#2#3#4}#5#6
14729   \_fp_fixed_mul:wnn
14730 }

```

(End definition for `_fp_ep_div_esti:wwwn`, `_fp_ep_div_estii:wwnnwn`, and `_fp_ep_div_estiii:NNNNNwwwn`.)

`_fp_ep_div_epsilon:wnNNNNn`
`_fp_ep_div_eps_pack:NNNNNw`
`_fp_ep_div_epsii:wnNNNNn`

The bounds shown above imply that the **epsi** function's first operand is $(1 - \epsilon)$ with $\epsilon \in [0, 1.755 \cdot 10^{-5}]$. The **epsi** function computes ϵ as $1 - (1 - \epsilon)$. Since $\epsilon < 10^{-4}$, its first block vanishes and there is no need to explicitly use **#1** (which is 9999). Then **epsii** evaluates $10^{-9}a / (1 - \epsilon)$ as $(1 + \epsilon^2)(1 + \epsilon)(10^{-9}a\epsilon) + 10^{-9}a$. Importantly, we compute $10^{-9}a\epsilon$ before multiplying it with the rest, rather than multiplying by ϵ and then $10^{-9}a$, as this second option loses more precision. Also, the combination of **short_mul** and **div_myriad** is both faster and more precise than a simple **mul**.

```

14731 \cs_new:Npn \_fp_ep_div_epsilon:wnNNNNn #1#2#3#4#5#6;
14732 {
14733   \exp_after:wN \_fp_ep_div_epsii:wnNNNNn
14734   \__int_value:w \__int_eval:w 1 9998 - #2
14735   \exp_after:wN \_fp_ep_div_eps_pack:NNNNNw
14736   \__int_value:w \__int_eval:w 1 9999 9998 - #3#4
14737   \exp_after:wN \_fp_ep_div_eps_pack:NNNNNw
14738   \__int_value:w \__int_eval:w 2 0000 0000 - #5#6 ; ;
14739 }

```

```

14740 \cs_new:Npn \__fp_ep_div_eps_pack:NNNNNw #1#2#3#4#5#6;
14741 { + #1 ; {#2#3#4#5} {#6} }
14742 \cs_new:Npn \__fp_ep_div_epsii:wnNNNNNn 1#1; #2; #3#4#5#6#7#8
14743 {
14744   \__fp_fixed_mul:wnn {0000}{#1}#2; {0000}{#1}#2;
14745   \__fp_fixed_add_one:wn
14746   \__fp_fixed_mul:wnn {10000} {#1} #2 ;
14747   {
14748     \__fp_fixed_mul_short:wnn {0000}{#1}#2; {#3}{#4#5#6#7}{#8000};
14749     \__fp_fixed_div_myriad:wn
14750     \__fp_fixed_mul:wnn
14751   }
14752   \__fp_fixed_add:wnn {#3}{#4#5#6#7}{#8000}{0000}{0000}{0000};
14753 }

```

(End definition for `__fp_ep_div_epsilon:wnNNNNNn`, `__fp_ep_div_eps_pack:NNNNNw`, and `__fp_ep_div_epsii:wnNNNNNn`.)

27.10 Inverse square root of extended precision numbers

The idea here is similar to division. Normalize the input, multiplying by powers of 100 until we have $x \in [0.01, 1)$. Then find an integer approximation $r \in [101, 1003]$ of $10^2/\sqrt{x}$, as the fixed point of iterations of the Newton method: essentially $r \mapsto (r + 10^8/(x_1 r))/2$, starting from a guess that optimizes the number of steps before convergence. In fact, just as there is a slight shift when computing divisions to ensure that some inequalities hold, we replace 10^8 by a slightly larger number which ensures that $r^2 x \geq 10^4$. This also causes $r \in [101, 1003]$. Another correction to the above is that the input is actually normalized to $[0.1, 1)$, and we use either 10^8 or 10^9 in the Newton method, depending on the parity of the exponent. Skipping those technical hurdles, once we have the approximation r , we set $y = 10^{-4}r^2x$ (or rather, the correct power of 10 to get $y \simeq 1$) and compute $y^{-1/2}$ through another application of Newton's method. This time, the starting value is $z = 1$, each step maps $z \mapsto z(1.5 - 0.5yz^2)$, and we perform a fixed number of steps. Our final result combines r with $y^{-1/2}$ as $x^{-1/2} = 10^{-2}ry^{-1/2}$.

```

\__fp_ep_isqrt:wnn
\__fp_ep_isqrt_aux:wnn
\__fp_ep_isqrt_auxii:wnnnwnn

```

First normalize the input, then check the parity of the exponent `#1`. If it is even, the result's exponent will be `-#1/2`, otherwise it will be `(#1 - 1)/2` (except in the case where the input was an exact power of 100). The `auxii` function receives as `#1` the result's exponent just computed, as `#2` the starting value for the iteration giving r (the values 168 and 535 lead to the least number of iterations before convergence, on average), as `#3` and `#4` one empty argument and one 0, depending on the parity of the original exponent, as `#5` and `#6` the normalized mantissa (`#5` $\in [1000, 9999]$), and as `#7` the continuation. It sets up the iteration giving r : the `esti` function thus receives the initial two guesses `#2` and 0, an approximation `#5` of 10^4x (its first block of digits), and the empty/zero arguments `#3` and `#4`, followed by the mantissa and an altered continuation where we have stored the result's exponent.

```

14754 \cs_new:Npn \__fp_ep_isqrt:wnn #1,#2;
14755 {
14756   \__fp_ep_to_ep:wnN #1,#2;
14757   \__fp_ep_isqrt_auxi:wnn
14758 }
14759 \cs_new:Npn \__fp_ep_isqrt_auxi:wnn #1,
14760 {

```

```

14761 \exp_after:wN \_fp_ep_isqrt_auxii:wwnnwn
14762 \_int_value:w \_int_eval:w
14763 \int_if_odd:nTF {#1}
14764 { (1 - #1) / 2 , 535 , { 0 } { } }
14765 { 1 - #1 / 2 , 168 , { } { 0 } }
14766 }
14767 \cs_new:Npn \_fp_ep_isqrt_auxii:wwnnwn #1, #2, #3#4 #5#6; #7
14768 {
14769 \_fp_ep_isqrt_esti:wwnnwn #2, 0, #5, {#3} {#4}
14770 {#5} #6 ; { #7 #1 , }
14771 }

```

(End definition for _fp_ep_isqrt:wn, _fp_ep_isqrt_aux:wn, and _fp_ep_isqrt_auxii:wwnnwn.)

```

\_fp_ep_isqrt_esti:wwnnwn
\_fp_ep_isqrt_estii:wwnnwn
\_fp_ep_isqrt_estiii:NNNNNwww

```

If the last two approximations gave the same result, we are done: call the `esti` function to clean up. Otherwise, evaluate $(\langle prev \rangle + 1.005 \cdot 10^8 \text{ or } 9 / (\langle prev \rangle \cdot x)) / 2$, as the next approximation: omitting the 1.005 factor, this would be Newton's method. We can check by brute force that if `#4` is empty (the original exponent was even), the process computes an integer slightly larger than $100/\sqrt{x}$, while if `#4` is 0 (the original exponent was odd), the result is an integer slightly larger than $100/\sqrt{x/10}$. Once we are done, we evaluate $100r^2/2$ or $10r^2/2$ (when the exponent is even or odd, respectively) and feed that to `estiii`. This third auxiliary finds $y_{\text{even}}/2 = 10^{-4}r^2x/2$ or $y_{\text{odd}}/2 = 10^{-5}r^2x/2$ (again, depending on earlier parity). A simple program shows that $y \in [1, 1.0201]$. The number $y/2$ is fed to `_fp_ep_isqrt_epsilon:wn`, which computes $1/\sqrt{y}$, and we finally multiply the result by r .

```

14772 \cs_new:Npn \_fp_ep_isqrt_esti:wwnnwn #1, #2, #3, #4
14773 {
14774 \if_int_compare:w #1 = #2 \exp_stop_f:
14775 \exp_after:wN \_fp_ep_isqrt_estii:wwnnwn
14776 \fi:
14777 \exp_after:wN \_fp_ep_isqrt_esti:wwnnwn
14778 \_int_value:w \_int_eval:w
14779 (#1 + 1 0050 0000 #4 / (#1 * #3)) / 2 ,
14780 #1, #3, {#4}
14781 }
14782 \cs_new:Npn \_fp_ep_isqrt_estii:wwnnwn #1, #2, #3, #4#5
14783 {
14784 \exp_after:wN \_fp_ep_isqrt_estiii:NNNNNwww
14785 \_int_value:w \_int_eval:w 1000 0000 + #2 * #2 #5 * 5
14786 \exp_after:wN , \_int_value:w \_int_eval:w 10000 + #2 ;
14787 }
14788 \cs_new:Npn \_fp_ep_isqrt_estiii:NNNNNwww 1#1#2#3#4#5#6, 1#7#8; #9;
14789 {
14790 \_fp_fixed_mul_short:wn #9; {#1} {#2#3#4#5} {#600} ;
14791 \_fp_ep_isqrt_epsilon:wn
14792 \_fp_fixed_mul_short:wn {#7} {#80} {0000} ;
14793 }

```

(End definition for _fp_ep_isqrt_esti:wwnnwn, _fp_ep_isqrt_estii:wwnnwn, and _fp_ep_isqrt_estiii:NNNNNwww.)

```

\_fp_ep_isqrt_epsilon:wn
\_fp_ep_isqrt_epsilonii:wn

```

Here, we receive a fixed point number $y/2$ with $y \in [1, 1.0201]$. Starting from $z = 1$ we iterate $z \mapsto z(3/2 - z^2y/2)$. In fact, we start from the first iteration $z = 3/2 - y/2$ to avoid useless multiplications. The `epsii` auxiliary receives z as `#1` and y as `#2`.

```

14794 \cs_new:Npn \__fp_ep_isqrt_epsilon:wwN #1;
14795 {
14796   \__fp_fixed_sub:wwn {15000}{0000}{0000}{0000}{0000}{0000}; #1;
14797   \__fp_ep_isqrt_epsilon:wwN #1;
14798   \__fp_ep_isqrt_epsilon:wwN #1;
14799   \__fp_ep_isqrt_epsilon:wwN #1;
14800 }
14801 \cs_new:Npn \__fp_ep_isqrt_epsilon:wwN #1; #2;
14802 {
14803   \__fp_fixed_mul:wwn #1; #1;
14804   \__fp_fixed_mul_sub_back:wwwn #2;
14805   {15000}{0000}{0000}{0000}{0000}{0000};
14806   \__fp_fixed_mul:wwn #1;
14807 }

```

(End definition for __fp_ep_isqrt_epsilon:wwN and __fp_ep_isqrt_epsilon:wwN.)

27.11 Converting from fixed point to floating point

After computing Taylor series, we wish to convert the result from extended precision (with or without an exponent) to the public floating point format. The functions here should be called within an integer expression for the overall exponent of the floating point.

__fp_ep_to_float_o:wwN
 __fp_ep_inv_to_float_o:wwN

An extended-precision number is simply a comma-delimited exponent followed by a fixed point number. Leave the exponent in the current integer expression then convert the fixed point number.

```

14808 \cs_new:Npn \__fp_ep_to_float_o:wwN #1,
14809 { + \__int_eval:w #1 \__fp_fixed_to_float_o:wwN }
14810 \cs_new:Npn \__fp_ep_inv_to_float_o:wwN #1,#2;
14811 {
14812   \__fp_ep_div:wwwn 1,{1000}{0000}{0000}{0000}{0000}{0000}; #1,#2;
14813   \__fp_ep_to_float_o:wwN
14814 }

```

(End definition for __fp_ep_to_float_o:wwN and __fp_ep_inv_to_float_o:wwN.)

__fp_fixed_inv_to_float_o:wwN

Another function which reduces to converting an extended precision number to a float.

```

14815 \cs_new:Npn \__fp_fixed_inv_to_float_o:wwN
14816 { \__fp_ep_inv_to_float_o:wwN 0, }

```

(End definition for __fp_fixed_inv_to_float_o:wwN.)

__fp_fixed_to_float_rad_o:wwN

Converts the fixed point number #1 from degrees to radians then to a floating point number. This could perhaps remain in l3fp-trig.

```

14817 \cs_new:Npn \__fp_fixed_to_float_rad_o:wwN #1;
14818 {
14819   \__fp_fixed_mul:wwn #1; {5729}{5779}{5130}{8232}{0876}{7981};
14820   { \__fp_ep_to_float_o:wwN 2, }
14821 }

```

(End definition for __fp_fixed_to_float_rad_o:wwN.)

```

\__fp_fixed_to_float_o:wN      ... \__int_eval:w <exponent> \__fp_fixed_to_float_o:wN {\langle a_1 \rangle} {\langle a_2 \rangle} {\langle a_3 \rangle} {\langle a_4 \rangle}
\__fp_fixed_to_float_o:Nw      {\langle a_5 \rangle} {\langle a_6 \rangle} ; <sign>
yields

```

```

<exponent'> ; {\langle a'_1 \rangle} {\langle a'_2 \rangle} {\langle a'_3 \rangle} {\langle a'_4 \rangle} ;

```

And the `to_fixed` version gives six brace groups instead of 4, ensuring that $1000 \leq \langle a'_1 \rangle \leq 9999$. At this stage, we know that $\langle a_1 \rangle$ is positive (otherwise, it is sign of an error before), and we assume that it is less than 10^8 .¹⁰

```

14822 \cs_new:Npn \__fp_fixed_to_float_o:Nw #1#2; { \__fp_fixed_to_float_o:wN #2; #1 }
14823 \cs_new:Npn \__fp_fixed_to_float_o:wN #1#2#3#4#5#6; #7
14824 {
14825   + \__int_eval:w \c__fp_block_int % for the 8-digit-at-the-start thing.
14826   \exp_after:wN \exp_after:wN
14827   \exp_after:wN \__fp_fixed_to_loop:N
14828   \exp_after:wN \use_none:n
14829   \__int_value:w \__int_eval:w
14830   1 0000 0000 + #1 \exp_after:wN \__fp_use_none_stop_f:n
14831   \__int_value:w 1#2 \exp_after:wN \__fp_use_none_stop_f:n
14832   \__int_value:w 1#3#4 \exp_after:wN \__fp_use_none_stop_f:n
14833   \__int_value:w 1#5#6
14834   \exp_after:wN ;
14835   \exp_after:wN ;
14836 }
14837 \cs_new:Npn \__fp_fixed_to_loop:N #1
14838 {
14839   \if_meaning:w 0 #1
14840   - 1
14841   \exp_after:wN \__fp_fixed_to_loop:N
14842   \else:
14843   \exp_after:wN \__fp_fixed_to_loop_end:w
14844   \exp_after:wN #1
14845   \fi:
14846 }
14847 \cs_new:Npn \__fp_fixed_to_loop_end:w #1 #2 ;
14848 {
14849   \if_meaning:w ; #1
14850   \exp_after:wN \__fp_fixed_to_float_zero:w
14851   \else:
14852   \exp_after:wN \__fp_pack_twice_four:wNNNNNNNN
14853   \exp_after:wN \__fp_pack_twice_four:wNNNNNNNN
14854   \exp_after:wN \__fp_fixed_to_float_pack:ww
14855   \exp_after:wN ;
14856   \fi:
14857   #1 #2 0000 0000 0000 0000 ;
14858 }
14859 \cs_new:Npn \__fp_fixed_to_float_zero:w ; 0000 0000 0000 0000 ;
14860 {
14861   - 2 * \c__fp_max_exponent_int ;
14862   {0000} {0000} {0000} {0000} ;
14863 }
14864 \cs_new:Npn \__fp_fixed_to_float_pack:ww #1 ; #2#3 ; ;

```

¹⁰Bruno: I must double check this assumption.

```

14865 {
14866   \if_int_compare:w #2 > 4 \exp_stop_f:
14867   \exp_after:wN \__fp_fixed_to_float_round_up:wnnnnw
14868   \fi:
14869   ; #1 ;
14870 }
14871 \cs_new:Npn \__fp_fixed_to_float_round_up:wnnnnw ; #1#2#3#4 ;
14872 {
14873   \exp_after:wN \__fp_basics_pack_high:NNNNw
14874   \__int_value:w \__int_eval:w 1 #1#2
14875   \exp_after:wN \__fp_basics_pack_low:NNNNw
14876   \__int_value:w \__int_eval:w 1 #3#4 + 1 ;
14877 }

```

(End definition for __fp_fixed_to_float_o:wN and __fp_fixed_to_float_o:Nw.)

```

14878 </initex | package>

```

28 l3fp-expo implementation

```

14879 <*initex | package>
14880 <@@=fp>

```

__fp_parse_word_exp:N Unary functions.

```

\__fp_parse_word_ln:N
14881 \cs_new:Npn \__fp_parse_word_exp:N
14882 { \__fp_parse_unary_function:NNN \__fp_exp_o:w ? }
14883 \cs_new:Npn \__fp_parse_word_ln:N
14884 { \__fp_parse_unary_function:NNN \__fp_ln_o:w ? }

```

(End definition for __fp_parse_word_exp:N and __fp_parse_word_ln:N.)

28.1 Logarithm

28.1.1 Work plan

As for many other functions, we filter out special cases in __fp_ln_o:w. Then __fp_ln_npos_o:w receives a positive normal number, which we write in the form $a \cdot 10^b$ with $a \in [0.1, 1)$.

The rest of this section is actually not in sync with the code. Or is the code not in sync with the section? In the current code, $c \in [1, 10]$ is such that $0.7 \leq ac < 1.4$.

We are given a positive normal number, of the form $a \cdot 10^b$ with $a \in [0.1, 1)$. To compute its logarithm, we find a small integer $5 \leq c < 50$ such that $0.91 \leq ac/5 < 1.1$, and use the relation

$$\ln(a \cdot 10^b) = b \cdot \ln(10) - \ln(c/5) + \ln(ac/5).$$

The logarithms $\ln(10)$ and $\ln(c/5)$ are looked up in a table. The last term is computed using the following Taylor series of \ln near 1:

$$\ln\left(\frac{ac}{5}\right) = \ln\left(\frac{1+t}{1-t}\right) = 2t \left(1 + t^2 \left(\frac{1}{3} + t^2 \left(\frac{1}{5} + t^2 \left(\frac{1}{7} + t^2 \left(\frac{1}{9} + \dots\right)\right)\right)\right)\right)$$

where $t = 1 - 10/(ac + 5)$. We can now see one reason for the choice of $ac \sim 5$: then $ac + 5 = 10(1 - \epsilon)$ with $-0.05 < \epsilon \leq 0.045$, hence

$$t = \frac{\epsilon}{1 - \epsilon} = \epsilon(1 + \epsilon)(1 + \epsilon^2)(1 + \epsilon^4) \dots,$$

is not too difficult to compute.

28.1.2 Some constants

A few values of the logarithm as extended fixed point numbers. Those are needed in the implementation. It turns out that we don't need the value of $\ln(5)$.

```
\c__fp_ln_i_fixed_t1
\c__fp_ln_ii_fixed_t1
\c__fp_ln_iii_fixed_t1
\c__fp_ln_iv_fixed_t1
\c__fp_ln_vii_fixed_t1
\c__fp_ln_viii_fixed_t1
\c__fp_ln_ix_fixed_t1
\c__fp_ln_x_fixed_t1
14885 \tl_const:Nn \c__fp_ln_i_fixed_t1 { {0000}{0000}{0000}{0000}{0000}{0000};}
14886 \tl_const:Nn \c__fp_ln_ii_fixed_t1 { {6931}{4718}{0559}{9453}{0941}{7232};}
14887 \tl_const:Nn \c__fp_ln_iii_fixed_t1 { {10986}{1228}{8668}{1096}{9139}{5245};}
14888 \tl_const:Nn \c__fp_ln_iv_fixed_t1 { {13862}{9436}{1119}{8906}{1883}{4464};}
14889 \tl_const:Nn \c__fp_ln_vii_fixed_t1 { {17917}{5946}{9228}{0550}{0081}{2477};}
14890 \tl_const:Nn \c__fp_ln_viii_fixed_t1 { {19459}{1014}{9055}{3133}{0510}{5353};}
14891 \tl_const:Nn \c__fp_ln_viii_fixed_t1 { {20794}{4154}{1679}{8359}{2825}{1696};}
14892 \tl_const:Nn \c__fp_ln_ix_fixed_t1 { {21972}{2457}{7336}{2193}{8279}{0490};}
14893 \tl_const:Nn \c__fp_ln_x_fixed_t1 { {23025}{8509}{2994}{0456}{8401}{7991};}
```

(End definition for `\c__fp_ln_i_fixed_t1` and others.)

28.1.3 Sign, exponent, and special numbers

`__fp_ln_o:w` The logarithm of negative numbers (including $-\infty$ and -0) raises the “invalid” exception. The logarithm of $+0$ is $-\infty$, raising a division by zero exception. The logarithm of $+\infty$ or a `nan` is itself. Positive normal numbers call `__fp_ln_npos_o:w`.

```
14894 \cs_new:Npn \__fp_ln_o:w #1 \s__fp \__fp_chk:w #2#3#4; @
14895 {
14896   \if_meaning:w 2 #3
14897     \__fp_case_use:nw { \__fp_invalid_operation_o:nw { ln } }
14898   \fi:
14899   \if_case:w #2 \exp_stop_f:
14900     \__fp_case_use:nw
14901     { \__fp_division_by_zero_o:Nnw \c_minus_inf_fp { ln } }
14902   \or:
14903   \else:
14904     \__fp_case_return_same_o:w
14905   \fi:
14906   \__fp_ln_npos_o:w \s__fp \__fp_chk:w #2#3#4;
14907 }
```

(End definition for `__fp_ln_o:w`.)

28.1.4 Absolute ln

`__fp_ln_npos_o:w` We catch the case of a significand very close to 0.1 or to 1. In all other cases, the final result is at least 10^{-4} , and then an error of $0.5 \cdot 10^{-20}$ is acceptable.

```
14908 \cs_new:Npn \__fp_ln_npos_o:w \s__fp \__fp_chk:w 10#1#2#3;
14909 { %^^A todo: ln(1) should be "exact zero", not "underflow"
14910   \exp_after:wN \__fp_sanitize:Nw
14911   \__int_value:w % for the overall sign
```

```

14912     \if_int_compare:w #1 < 1 \exp_stop_f:
14913         2
14914     \else:
14915         0
14916     \fi:
14917     \exp_after:wN \exp_stop_f:
14918     \__int_value:w \__int_eval:w % for the exponent
14919     \__fp_ln_significand:NNNNnnnnN #2#3
14920     \__fp_ln_exponent:wn {#1}
14921 }

```

(End definition for __fp_ln_npos_o:w.)

__fp_ln_significand:NNNNnnnnN __fp_ln_significand:NNNNnnnnN $\langle X_1 \rangle$ $\{\langle X_2 \rangle\}$ $\{\langle X_3 \rangle\}$ $\{\langle X_4 \rangle\}$ $\langle continuation \rangle$
This function expands to

$\langle continuation \rangle$ $\{\langle Y_1 \rangle\}$ $\{\langle Y_2 \rangle\}$ $\{\langle Y_3 \rangle\}$ $\{\langle Y_4 \rangle\}$ $\{\langle Y_5 \rangle\}$ $\{\langle Y_6 \rangle\}$;

where $Y = -\ln(X)$ as an extended fixed point.

```

14922 \cs_new:Npn \__fp_ln_significand:NNNNnnnnN #1#2#3#4
14923 {
14924     \exp_after:wN \__fp_ln_x_ii:wnnnnn
14925     \__int_value:w
14926     \if_case:w #1 \exp_stop_f:
14927     \or:
14928         \if_int_compare:w #2 < 4 \exp_stop_f:
14929         \__int_eval:w 10 - #2
14930     \else:
14931         6
14932     \fi:
14933     \or: 4
14934     \or: 3
14935     \or: 2
14936     \or: 2
14937     \or: 2
14938     \else: 1
14939     \fi:
14940     ; { #1 #2 #3 #4 }
14941 }

```

(End definition for __fp_ln_significand:NNNNnnnnN.)

__fp_ln_x_ii:wnnnnn We have thus found $c \in [1, 10]$ such that $0.7 \leq ac < 1.4$ in all cases. Compute $1 + x = 1 + ac \in [1.7, 2.4]$.

```

14942 \cs_new:Npn \__fp_ln_x_ii:wnnnnn #1; #2#3#4#5
14943 {
14944     \exp_after:wN \__fp_ln_div_after:Nw
14945     \cs:w c__fp_ln_ \__int_to_roman:w #1 _fixed_tl \exp_after:wN \cs_end:
14946     \__int_value:w
14947     \exp_after:wN \__fp_ln_x_iv:wnnnnnnnnn
14948     \__int_value:w \__int_eval:w
14949     \exp_after:wN \__fp_ln_x_iii_var:NNNNNw
14950     \__int_value:w \__int_eval:w 9999 9990 + #1*#2#3 +
14951     \exp_after:wN \__fp_ln_x_iii:NNNNNNw
14952     \__int_value:w \__int_eval:w 10 0000 0000 + #1*#4#5 ;

```

```

14953     {20000} {0000} {0000} {0000}
14954   } %^A todo: reoptimize (a generalization attempt failed).
14955 \cs_new:Npn \__fp_ln_x_iii:NNNNNw #1#2 #3#4#5#6 #7;
14956   { #1#2; {#3#4#5#6} {#7} }
14957 \cs_new:Npn \__fp_ln_x_iii_var:NNNNNw #1 #2#3#4#5 #6;
14958   {
14959     #1#2#3#4#5 + 1 ;
14960     {#1#2#3#4#5} {#6}
14961   }

```

The Taylor series to be used is expressed in terms of $t = (x - 1)/(x + 1) = 1 - 2/(x + 1)$. We now compute the quotient with extended precision, reusing some code from `__fp_/_o:ww`. Note that $1 + x$ is known exactly.

To reuse notations from `l3fp-basics`, we want to compute A/Z with $A = 2$ and $Z = x + 1$. In `l3fp-basics`, we considered the case where both A and Z are arbitrary, in the range $[0.1, 1)$, and we had to monitor the growth of the sequence of remainders A , B , C , etc. to ensure that no overflow occurred during the computation of the next quotient. The main source of risk was our choice to define the quotient as roughly $10^9 \cdot A/10^5 \cdot Z$: then A was bound to be below $2.147 \dots$, and this limit was never far.

In our case, we can simply work with $10^8 \cdot A$ and $10^4 \cdot Z$, because our reason to work with higher powers has gone: we needed the integer $y \simeq 10^5 \cdot Z$ to be at least 10^4 , and now, the definition $y \simeq 10^4 \cdot Z$ suffices.

Let us thus define $y = \lfloor 10^4 \cdot Z \rfloor + 1 \in (1.7 \cdot 10^4, 2.4 \cdot 10^4]$, and

$$Q_1 = \left\lfloor \frac{\lfloor 10^8 \cdot A \rfloor}{y} - \frac{1}{2} \right\rfloor.$$

(The $1/2$ comes from how `eTeX` rounds.) As for division, it is easy to see that $Q_1 \leq 10^4 A/Z$, *i.e.*, Q_1 is an underestimate.

Exactly as we did for division, we set $B = 10^4 A - Q_1 Z$. Then

$$\begin{aligned}
10^4 B &\leq A_1 A_2 \cdot A_3 A_4 - \left(\frac{A_1 A_2}{y} - \frac{3}{2} \right) 10^4 Z \\
&\leq A_1 A_2 \left(1 - \frac{10^4 Z}{y} \right) + 1 + \frac{3}{2} y \\
&\leq 10^8 \frac{A}{y} + 1 + \frac{3}{2} y
\end{aligned}$$

In the same way, and using $1.7 \cdot 10^4 \leq y \leq 2.4 \cdot 10^4$, and convexity, we get

$$\begin{aligned} 10^4 A &= 2 \cdot 10^4 \\ 10^4 B &\leq 10^8 \frac{A}{y} + 1.6y \leq 4.7 \cdot 10^4 \\ 10^4 C &\leq 10^8 \frac{B}{y} + 1.6y \leq 5.8 \cdot 10^4 \\ 10^4 D &\leq 10^8 \frac{C}{y} + 1.6y \leq 6.3 \cdot 10^4 \\ 10^4 E &\leq 10^8 \frac{D}{y} + 1.6y \leq 6.5 \cdot 10^4 \\ 10^4 F &\leq 10^8 \frac{E}{y} + 1.6y \leq 6.6 \cdot 10^4 \end{aligned}$$

Note that we compute more steps than for division: since t is not the end result, we need to know it with more accuracy (on the other hand, the ending is much simpler, as we don't need an exact rounding for transcendental functions, but just a faithful rounding).

`__fp_ln_x_iv:wnnnnnnnn <1 or 2> <8d> ; {<4d>} {<4d>} <fixed-t1>`

The number is x . Compute y by adding 1 to the five first digits.

```

14962 \cs_new:Npn __fp_ln_x_iv:wnnnnnnnn #1; #2#3#4#5 #6#7#8#9
14963 {
14964   \exp_after:wN __fp_div_significand_pack:NNN
14965   \__int_value:w \__int_eval:w
14966   \__fp_ln_div_i:w #1 ;
14967   #6 #7 ; {#8} {#9}
14968   {#2} {#3} {#4} {#5}
14969   { \exp_after:wN __fp_ln_div_ii:wnn \__int_value:w #1 }
14970   { \exp_after:wN __fp_ln_div_ii:wnn \__int_value:w #1 }
14971   { \exp_after:wN __fp_ln_div_ii:wnn \__int_value:w #1 }
14972   { \exp_after:wN __fp_ln_div_ii:wnn \__int_value:w #1 }
14973   { \exp_after:wN __fp_ln_div_vi:wnn \__int_value:w #1 }
14974 }
14975 \cs_new:Npn __fp_ln_div_i:w #1;
14976 {
14977   \exp_after:wN __fp_div_significand_calc:wnnnnnnnn
14978   \__int_value:w \__int_eval:w 999999 + 2 0000 0000 / #1 ; % Q1
14979 }
14980 \cs_new:Npn __fp_ln_div_ii:wnn #1; #2;#3 % y; B1;B2 <- for k=1
14981 {
14982   \exp_after:wN __fp_div_significand_pack:NNN
14983   \__int_value:w \__int_eval:w
14984   \exp_after:wN __fp_div_significand_calc:wnnnnnnnn
14985   \__int_value:w \__int_eval:w 999999 + #2 #3 / #1 ; % Q2
14986   #2 #3 ;
14987 }
14988 \cs_new:Npn __fp_ln_div_vi:wnn #1; #2;#3#4#5 #6#7#8#9 %y;F1;F2F3F4x1x2x3x4
14989 {
14990   \exp_after:wN __fp_div_significand_pack:NNN

```

```

14991     \__int_value:w \__int_eval:w 1000000 + #2 #3 / #1 ; % Q6
14992 }

```

We now have essentially

```

\__fp_ln_div_after:Nw <fixed t1>
\__fp_div_significand_pack:NNN 106 + Q1
\__fp_div_significand_pack:NNN 106 + Q2
\__fp_div_significand_pack:NNN 106 + Q3
\__fp_div_significand_pack:NNN 106 + Q4
\__fp_div_significand_pack:NNN 106 + Q5
\__fp_div_significand_pack:NNN 106 + Q6 ;
<exponent> ; <continuation>

```

where $\langle fixed\ t1 \rangle$ holds the logarithm of a number in $[1, 10]$, and $\langle exponent \rangle$ is the exponent. Also, the expansion is done backwards. Then `__fp_div_significand_pack:NNN` puts things in the correct order to add the Q_i together and put semicolons between each piece. Once those have been expanded, we get

```

\__fp_ln_div_after:Nw <fixed-t1> <1d> ; <4d> ; <4d> ;
<4d> ; <4d> ; <4d> ; <4d> ; <exponent> ;

```

Just as with division, we know that the first two digits are 1 and 0 because of bounds on the final result of the division $2/(x+1)$, which is between roughly 0.8 and 1.2. We then compute $1 - 2/(x+1)$, after testing whether $2/(x+1)$ is greater than or smaller than 1.

```

14993 \cs_new:Npn \__fp_ln_div_after:Nw #1#2;
14994 {
14995     \if_meaning:w 0 #2
14996     \exp_after:wN \__fp_ln_t_small:Nw
14997     \else:
14998     \exp_after:wN \__fp_ln_t_large:NNw
14999     \exp_after:wN -
15000     \fi:
15001     #1
15002 }
15003 \cs_new:Npn \__fp_ln_t_small:Nw #1 #2; #3; #4; #5; #6; #7;
15004 {
15005     \exp_after:wN \__fp_ln_t_large:NNw
15006     \exp_after:wN + % <sign>
15007     \exp_after:wN #1
15008     \__int_value:w \__int_eval:w 9999 - #2 \exp_after:wN ;
15009     \__int_value:w \__int_eval:w 9999 - #3 \exp_after:wN ;
15010     \__int_value:w \__int_eval:w 9999 - #4 \exp_after:wN ;
15011     \__int_value:w \__int_eval:w 9999 - #5 \exp_after:wN ;
15012     \__int_value:w \__int_eval:w 9999 - #6 \exp_after:wN ;
15013     \__int_value:w \__int_eval:w 1 0000 - #7 ;
15014 }

```

```

\__fp_ln_t_large:NNw <sign> <fixed t1>
<t123456

```

Compute the square t^2 , and keep t at the end with its sign. We know that $t < 0.1765$, so every piece has at most 4 digits. However, since we were not careful in `__fp_ln_t_small:w`, they can have less than 4 digits.

```

15015 \cs_new:Npn \__fp_ln_t_large:NNw #1 #2 #3; #4; #5; #6; #7; #8;
15016 {
15017   \exp_after:wN \__fp_ln_square_t_after:w
15018   \__int_value:w \__int_eval:w 9999 0000 + #3*#3
15019   \exp_after:wN \__fp_ln_square_t_pack:NNNNNw
15020   \__int_value:w \__int_eval:w 9999 0000 + 2*#3*#4
15021   \exp_after:wN \__fp_ln_square_t_pack:NNNNNw
15022   \__int_value:w \__int_eval:w 9999 0000 + 2*#3*#5 + #4*#4
15023   \exp_after:wN \__fp_ln_square_t_pack:NNNNNw
15024   \__int_value:w \__int_eval:w 9999 0000 + 2*#3*#6 + 2*#4*#5
15025   \exp_after:wN \__fp_ln_square_t_pack:NNNNNw
15026   \__int_value:w \__int_eval:w 1 0000 0000 + 2*#3*#7 + 2*#4*#6 + #5*#5
15027   + (2*#3*#8 + 2*#4*#7 + 2*#5*#6) / 1 0000
15028   % ; ; ;
15029   \exp_after:wN \__fp_ln_twice_t_after:w
15030   \__int_value:w \__int_eval:w -1 + 2*#3
15031   \exp_after:wN \__fp_ln_twice_t_pack:Nw
15032   \__int_value:w \__int_eval:w 9999 + 2*#4
15033   \exp_after:wN \__fp_ln_twice_t_pack:Nw
15034   \__int_value:w \__int_eval:w 9999 + 2*#5
15035   \exp_after:wN \__fp_ln_twice_t_pack:Nw
15036   \__int_value:w \__int_eval:w 9999 + 2*#6
15037   \exp_after:wN \__fp_ln_twice_t_pack:Nw
15038   \__int_value:w \__int_eval:w 9999 + 2*#7
15039   \exp_after:wN \__fp_ln_twice_t_pack:Nw
15040   \__int_value:w \__int_eval:w 10000 + 2*#8 ; ;
15041   { \__fp_ln_c:NwNw #1 }
15042   #2
15043 }
15044 \cs_new:Npn \__fp_ln_twice_t_pack:Nw #1 #2; { + #1 ; {#2} }
15045 \cs_new:Npn \__fp_ln_twice_t_after:w #1; { ; ; ; {#1} }
15046 \cs_new:Npn \__fp_ln_square_t_pack:NNNNNw #1 #2#3#4#5 #6;
15047 { + #1#2#3#4#5 ; {#6} }
15048 \cs_new:Npn \__fp_ln_square_t_after:w 1 0 #1#2#3 #4;
15049 { \__fp_ln_Taylor:wwNw {0#1#2#3} {#4} }

```

(End definition for __fp_ln_x_ii:wnnnn.)

__fp_ln_Taylor:wwNw Denoting $T = t^2$, we get

```

\__fp_ln_Taylor:wwNw
{ \langle T_1 \rangle } { \langle T_2 \rangle } { \langle T_3 \rangle } { \langle T_4 \rangle } { \langle T_5 \rangle } { \langle T_6 \rangle } ; ;
{ \langle (2t)_1 \rangle } { \langle (2t)_2 \rangle } { \langle (2t)_3 \rangle } { \langle (2t)_4 \rangle } { \langle (2t)_5 \rangle } { \langle (2t)_6 \rangle } ;
{ \__fp_ln_c:NwNw \langle sign \rangle }
\langle fixed t1 \rangle \langle exponent \rangle ; \langle continuation \rangle

```

And we want to compute

$$\ln\left(\frac{1+t}{1-t}\right) = 2t \left(1 + T \left(\frac{1}{3} + T \left(\frac{1}{5} + T \left(\frac{1}{7} + T \left(\frac{1}{9} + \cdots\right)\right)\right)\right)\right)$$

The process looks as follows

```

\loop 5; A;
\div_int 5; 1.0; \add A; \mul T; {\loop \eval 5-2;}

```

```

\add 0.2; A; \mul T; {\loop \eval 5-2;}
\mul B; T; {\loop 3;}
\loop 3; C;

```

This uses the routine for dividing a number by a small integer ($< 10^4$).

```

15050 \cs_new:Npn \__fp_ln_Taylor:wwNw
15051   { \__fp_ln_Taylor_loop:www 21 ; {0000}{0000}{0000}{0000}{0000}{0000} ; }
15052 \cs_new:Npn \__fp_ln_Taylor_loop:www #1; #2; #3;
15053   {
15054     \if_int_compare:w #1 = 1 \exp_stop_f:
15055     \__fp_ln_Taylor_break:w
15056     \fi:
15057     \exp_after:wN \__fp_fixed_div_int:wwN \c__fp_one_fixed_t1 #1;
15058     \__fp_fixed_add:wwn #2;
15059     \__fp_fixed_mul:wwn #3;
15060     {
15061       \exp_after:wN \__fp_ln_Taylor_loop:www
15062       \__int_value:w \__int_eval:w #1 - 2 ;
15063     }
15064     #3;
15065   }
15066 \cs_new:Npn \__fp_ln_Taylor_break:w \fi: #1 \__fp_fixed_add:wwn #2#3; #4 ;;
15067   {
15068     \fi:
15069     \exp_after:wN \__fp_fixed_mul:wwn
15070     \exp_after:wN { \__int_value:w \__int_eval:w 10000 + #2 } #3;
15071   }

```

(End definition for $\backslash_fp_ln_Taylor:wwNw$.)

```

\__fp_ln_c:NwNw <sign>
\__fp_ln_c:NwNw {<r1>} {<r2>} {<r3>} {<r4>} {<r5>} {<r6>} ;
<fixed t1> <exponent> ; <continuation>

```

We are now reduced to finding $\ln(c)$ and $\langle exponent \rangle \ln(10)$ in a table, and adding it to the mixture. The first step is to get $\ln(c) - \ln(x) = -\ln(a)$, then we get $\ln(10)$ and add or subtract.

For now, $\ln(x)$ is given as $\cdot 10^0$. Unless both the exponent is 1 and $c = 1$, we shift to working in units of $\cdot 10^4$, since the final result is at least $\ln(10/7) \simeq 0.35$.

```

15072 \cs_new:Npn \__fp_ln_c:NwNw #1 #2; #3
15073   {
15074     \if_meaning:w + #1
15075     \exp_after:wN \exp_after:wN \exp_after:wN \__fp_fixed_sub:wwn
15076     \else:
15077     \exp_after:wN \exp_after:wN \exp_after:wN \__fp_fixed_add:wwn
15078     \fi:
15079     #3 #2 ;
15080   }

```

(End definition for $\backslash_fp_ln_c:NwNw$.)

```

\__fp_ln_exponent:wn
\__fp_ln_exponent:wn {<s1>} {<s2>} {<s3>} {<s4>} {<s5>} {<s6>} ;
{<exponent>}

```

Compute $\langle exponent \rangle$ times $\ln(10)$. Apart from the cases where $\langle exponent \rangle$ is 0 or 1, the result is necessarily at least $\ln(10) \simeq 2.3$ in magnitude. We can thus drop the least significant 4 digits. In the case of a very large (positive or negative) exponent, we can (and we need to) drop 4 additional digits, since the result is of order 10^4 . Naively, one would think that in both cases we can drop 4 more digits than we do, but that would be slightly too tight for rounding to happen correctly. Besides, we already have addition and subtraction for 24 digits fixed point numbers.

```

15081 \cs_new:Npn \__fp_ln_exponent:wn #1; #2
15082 {
15083   \if_case:w #2 \exp_stop_f:
15084     0 \__fp_case_return:nw { \__fp_fixed_to_float_o:Nw 2 }
15085   \or:
15086     \exp_after:wN \__fp_ln_exponent_one:ww \__int_value:w
15087   \else:
15088     \if_int_compare:w #2 > 0 \exp_stop_f:
15089       \exp_after:wN \__fp_ln_exponent_small:NNww
15090       \exp_after:wN 0
15091       \exp_after:wN \__fp_fixed_sub:wwn \__int_value:w
15092     \else:
15093       \exp_after:wN \__fp_ln_exponent_small:NNww
15094       \exp_after:wN 2
15095       \exp_after:wN \__fp_fixed_add:wwn \__int_value:w -
15096     \fi:
15097   \fi:
15098   #2; #1;
15099 }

```

Now we painfully write all the cases.¹¹ No overflow nor underflow can happen, except when computing $\ln(1)$.

```

15100 \cs_new:Npn \__fp_ln_exponent_one:ww 1; #1;
15101 {
15102   0
15103   \exp_after:wN \__fp_fixed_sub:wwn \c__fp_ln_x_fixed_tl #1;
15104   \__fp_fixed_to_float_o:wN 0
15105 }

```

For small exponents, we just drop one block of digits, and set the exponent of the log to 4 (minus any shift coming from leading zeros in the conversion from fixed point to floating point). Note that here the exponent has been made positive.

```

15106 \cs_new:Npn \__fp_ln_exponent_small:NNww #1#2#3; #4#5#6#7#8#9;
15107 {
15108   4
15109   \exp_after:wN \__fp_fixed_mul:wwn
15110     \c__fp_ln_x_fixed_tl
15111     {#3}{0000}{0000}{0000}{0000}{0000} ;
15112   #2
15113     {0000}{#4}{#5}{#6}{#7}{#8};
15114   \__fp_fixed_to_float_o:wN #1
15115 }

```

(End definition for $\backslash_fp_ln_exponent:wn$.)

¹¹Bruno: do rounding.

28.2 Exponential

28.2.1 Sign, exponent, and special numbers

_fp_exp_o:w

```
15116 \cs_new:Npn \_fp_exp_o:w #1 \s__fp \_fp_chk:w #2#3#4; @
15117 {
15118   \if_case:w #2 \exp_stop_f:
15119     \_fp_case_return_o:Nw \c_one_fp
15120   \or:
15121     \exp_after:wN \_fp_exp_normal_o:w
15122   \or:
15123     \if_meaning:w 0 #3
15124       \exp_after:wN \_fp_case_return_o:Nw
15125       \exp_after:wN \c_inf_fp
15126     \else:
15127       \exp_after:wN \_fp_case_return_o:Nw
15128       \exp_after:wN \c_zero_fp
15129     \fi:
15130   \or:
15131     \_fp_case_return_same_o:w
15132   \fi:
15133   \s__fp \_fp_chk:w #2#3#4;
15134 }
```

(End definition for _fp_exp_o:w.)

_fp_exp_normal_o:w
_fp_exp_pos_o:NNwnw
_fp_exp_overflow:NN

```
15135 \cs_new:Npn \_fp_exp_normal_o:w \s__fp \_fp_chk:w 1#1
15136 {
15137   \if_meaning:w 0 #1
15138     \_fp_exp_pos_o:NNwnw + \_fp_fixed_to_float_o:wN
15139   \else:
15140     \_fp_exp_pos_o:NNwnw - \_fp_fixed_inv_to_float_o:wN
15141   \fi:
15142 }
15143 \cs_new:Npn \_fp_exp_pos_o:NNwnw #1#2#3 \fi: #4#5;
15144 {
15145   \fi:
15146   \if_int_compare:w #4 > \c__fp_max_exp_exponent_int
15147     \token_if_eq_charcode:NNTF + #1
15148     { \_fp_exp_overflow:NN \_fp_overflow:w \c_inf_fp }
15149     { \_fp_exp_overflow:NN \_fp_underflow:w \c_zero_fp }
15150   \exp:w
15151   \else:
15152     \exp_after:wN \_fp_sanitize:Nw
15153     \exp_after:wN 0
15154     \_int_value:w #1 \_int_eval:w
15155     \if_int_compare:w #4 < 0 \exp_stop_f:
15156       \exp_after:wN \use_i:nn
15157     \else:
15158       \exp_after:wN \use_ii:nn
15159     \fi:
15160     {
15161       0
```

```

15162         \__fp_decimate:nNnnnn { - #4 }
15163         \__fp_exp_Taylor:Nnnwn
15164     }
15165     {
15166         \__fp_decimate:nNnnnn { \c__fp_prec_int - #4 }
15167         \__fp_exp_pos_large:NnnNwn
15168     }
15169     #5
15170     {#4}
15171     #1 #2 0
15172     \exp:w
15173     \fi:
15174     \exp_after:wN \exp_end:
15175 }
15176 \cs_new:Npn \__fp_exp_overflow:NN #1#2
15177 {
15178     \exp_after:wN \exp_after:wN
15179     \exp_after:wN #1
15180     \exp_after:wN #2
15181 }

```

(End definition for __fp_exp_normal_o:w, __fp_exp_pos_o:Nnnwn, and __fp_exp_overflow:NN.)

```

\__fp_exp_Taylor:Nnnwn
\__fp_exp_Taylor_loop:www
\__fp_exp_Taylor_break:Nww

```

This function is called for numbers in the range $[10^{-9}, 10^{-1}]$. We compute 10 terms of the Taylor series. The first argument is irrelevant (rounding digit used by some other functions). The next three arguments, at least 16 digits, delimited by a semicolon, form a fixed point number, so we pack it in blocks of 4 digits.

```

15182 \cs_new:Npn \__fp_exp_Taylor:Nnnwn #1#2#3 #4; #5 #6
15183 {
15184     #6
15185     \__fp_pack_twice_four:wNNNNNNNN
15186     \__fp_pack_twice_four:wNNNNNNNN
15187     \__fp_pack_twice_four:wNNNNNNNN
15188     \__fp_exp_Taylor_ii:ww
15189     ; #2#3#4 0000 0000 ;
15190 }
15191 \cs_new:Npn \__fp_exp_Taylor_ii:ww #1; #2;
15192 { \__fp_exp_Taylor_loop:www 10 ; #1 ; #1 ; \s__stop }
15193 \cs_new:Npn \__fp_exp_Taylor_loop:www #1; #2; #3;
15194 {
15195     \if_int_compare:w #1 = 1 \exp_stop_f:
15196     \exp_after:wN \__fp_exp_Taylor_break:Nww
15197     \fi:
15198     \__fp_fixed_div_int:wwN #3 ; #1 ;
15199     \__fp_fixed_add_one:wN
15200     \__fp_fixed_mul:wwN #2 ;
15201     {
15202         \exp_after:wN \__fp_exp_Taylor_loop:www
15203         \__int_value:w \__int_eval:w #1 - 1 ;
15204         #2 ;
15205     }
15206 }
15207 \cs_new:Npn \__fp_exp_Taylor_break:Nww #1 #2; #3 \s__stop
15208 { \__fp_fixed_add_one:wN #2 ; }

```

(End definition for `__fp_exp_Taylor:Nnnwn`, `__fp_exp_Taylor_loop:www`, and `__fp_exp_Taylor-break:Nww`.)

`__fp_exp_pos_large:NnnNwn` The first two arguments are irrelevant (a rounding digit, and a brace group with 8 zeros).
`__fp_exp_large_after:wwn` The third argument is the integer part of our number, then we have the decimal part
`__fp_exp_large:w` delimited by a semicolon, and finally the exponent, in the range $[0, 5]$. Remove leading
`__fp_exp_large_v:wN` zeros from the integer part: putting #4 in there too ensures that an integer part of 0 is
`__fp_exp_large_iv:wN` also removed. Then read digits one by one, looking up $\exp(\langle digit \rangle \cdot 10^{\langle exponent \rangle})$ in a table,
`__fp_exp_large_iii:wN` and multiplying that to the current total. The loop is done by having the auxiliary for
`__fp_exp_large_ii:wN` one exponent call the auxiliary for the next exponent. The current total is expressed by
`__fp_exp_large_i:wN` leaving the exponent behind in the input stream (we are currently within an `__int-`
`__fp_exp_large:wN` `eval:w`), and keeping track of a fixed point number, #1 for the numbered auxiliaries. Our
usage of `\if_case:w` is somewhat dirty for optimization: `TeX` jumps to the appropriate
case, but we then close the `\if_case:w` “by hand”, using `\or:` and `\fi:` as delimiters.

```

15209 \cs_new:Npn \__fp_exp_pos_large:NnnNwn #1#2#3 #4#5; #6
15210 {
15211   \exp_after:wN \exp_after:wN
15212   \cs:w \__fp_exp_large_ \__int_to_roman:w #6 :wN \exp_after:wN \cs_end:
15213   \exp_after:wN \c__fp_one_fixed_tl
15214   \__int_value:w #3 #4 \exp_stop_f:
15215   #5 00000 ;
15216 }
15217 \cs_new:Npn \__fp_exp_large:w #1 \or: #2 \fi:
15218 { \fi: \__fp_fixed_mul:wwn #1; }
15219 \cs_new:Npn \__fp_exp_large_v:wN #1; #2
15220 {
15221   \if_case:w #2 ~ \exp_after:wN \__fp_fixed_continue:wn \or:
15222   + 4343 \__fp_exp_large:w {8806}{8182}{2566}{2921}{5872}{6150} \or:
15223   + 8686 \__fp_exp_large:w {7756}{0047}{2598}{6861}{0458}{3204} \or:
15224   + 13029 \__fp_exp_large:w {6830}{5723}{7791}{4884}{1932}{7351} \or:
15225   + 17372 \__fp_exp_large:w {6015}{5609}{3095}{3052}{3494}{7574} \or:
15226   + 21715 \__fp_exp_large:w {5297}{7951}{6443}{0315}{3251}{3576} \or:
15227   + 26058 \__fp_exp_large:w {4665}{6719}{0099}{3379}{5527}{2929} \or:
15228   + 30401 \__fp_exp_large:w {4108}{9724}{3326}{3186}{5271}{5665} \or:
15229   + 34744 \__fp_exp_large:w {3618}{6973}{3140}{0875}{3856}{4102} \or:
15230   + 39087 \__fp_exp_large:w {3186}{9209}{6113}{3900}{6705}{9685} \or:
15231   \fi:
15232   #1;
15233   \__fp_exp_large_iv:wN
15234 }
15235 \cs_new:Npn \__fp_exp_large_iv:wN #1; #2
15236 {
15237   \if_case:w #2 ~ \exp_after:wN \__fp_fixed_continue:wn \or:
15238   + 435 \__fp_exp_large:w {1970}{0711}{1401}{7046}{9938}{8888} \or:
15239   + 869 \__fp_exp_large:w {3881}{1801}{9428}{4368}{5764}{8232} \or:
15240   + 1303 \__fp_exp_large:w {7646}{2009}{8905}{4704}{8893}{1073} \or:
15241   + 1738 \__fp_exp_large:w {1506}{3559}{7005}{0524}{9009}{7592} \or:
15242   + 2172 \__fp_exp_large:w {2967}{6283}{8402}{3667}{0689}{6630} \or:
15243   + 2606 \__fp_exp_large:w {5846}{4389}{5650}{2114}{7278}{5046} \or:
15244   + 3041 \__fp_exp_large:w {1151}{7900}{5080}{6878}{2914}{4154} \or:
15245   + 3475 \__fp_exp_large:w {2269}{1083}{0850}{6857}{8724}{4002} \or:
15246   + 3909 \__fp_exp_large:w {4470}{3047}{3316}{5442}{6408}{6591} \or:
15247   \fi:

```

```

15248     #1;
15249     \__fp_exp_large_iii:wN
15250 }
15251 \cs_new:Npn \__fp_exp_large_iii:wN #1; #2
15252 {
15253     \if_case:w #2 ~          \exp_after:wN \__fp_fixed_continue:wn \or:
15254     + 44 \__fp_exp_large:w {2688}{1171}{4181}{6135}{4484}{1263} \or:
15255     + 87 \__fp_exp_large:w {7225}{9737}{6812}{5749}{2581}{7748} \or:
15256     + 131 \__fp_exp_large:w {1942}{4263}{9524}{1255}{9365}{8421} \or:
15257     + 174 \__fp_exp_large:w {5221}{4696}{8976}{4143}{9505}{8876} \or:
15258     + 218 \__fp_exp_large:w {1403}{5922}{1785}{2837}{4107}{3977} \or:
15259     + 261 \__fp_exp_large:w {3773}{0203}{0092}{9939}{8234}{0143} \or:
15260     + 305 \__fp_exp_large:w {1014}{2320}{5473}{5004}{5094}{5533} \or:
15261     + 348 \__fp_exp_large:w {2726}{3745}{7211}{2566}{5673}{6478} \or:
15262     + 391 \__fp_exp_large:w {7328}{8142}{2230}{7421}{7051}{8866} \or:
15263     \fi:
15264     #1;
15265     \__fp_exp_large_ii:wN
15266 }
15267 \cs_new:Npn \__fp_exp_large_ii:wN #1; #2
15268 {
15269     \if_case:w #2 ~          \exp_after:wN \__fp_fixed_continue:wn \or:
15270     + 5 \__fp_exp_large:w {2202}{6465}{7948}{0671}{6516}{9579} \or:
15271     + 9 \__fp_exp_large:w {4851}{6519}{5409}{7902}{7796}{9107} \or:
15272     + 14 \__fp_exp_large:w {1068}{6474}{5815}{2446}{2146}{9905} \or:
15273     + 18 \__fp_exp_large:w {2353}{8526}{6837}{0199}{8540}{7900} \or:
15274     + 22 \__fp_exp_large:w {5184}{7055}{2858}{7072}{4640}{8745} \or:
15275     + 27 \__fp_exp_large:w {1142}{0073}{8981}{5684}{2836}{6296} \or:
15276     + 31 \__fp_exp_large:w {2515}{4386}{7091}{9167}{0062}{6578} \or:
15277     + 35 \__fp_exp_large:w {5540}{6223}{8439}{3510}{0525}{7117} \or:
15278     + 40 \__fp_exp_large:w {1220}{4032}{9431}{7840}{8020}{0271} \or:
15279     \fi:
15280     #1;
15281     \__fp_exp_large_i:wN
15282 }
15283 \cs_new:Npn \__fp_exp_large_i:wN #1; #2
15284 {
15285     \if_case:w #2 ~          \exp_after:wN \__fp_fixed_continue:wn \or:
15286     + 1 \__fp_exp_large:w {2718}{2818}{2845}{9045}{2353}{6029} \or:
15287     + 1 \__fp_exp_large:w {7389}{0560}{9893}{0650}{2272}{3043} \or:
15288     + 2 \__fp_exp_large:w {2008}{5536}{9231}{8766}{7740}{9285} \or:
15289     + 2 \__fp_exp_large:w {5459}{8150}{0331}{4423}{9078}{1103} \or:
15290     + 3 \__fp_exp_large:w {1484}{1315}{9102}{5766}{0342}{1116} \or:
15291     + 3 \__fp_exp_large:w {4034}{2879}{3492}{7351}{2260}{8387} \or:
15292     + 4 \__fp_exp_large:w {1096}{6331}{5842}{8458}{5992}{6372} \or:
15293     + 4 \__fp_exp_large:w {2980}{9579}{8704}{1728}{2747}{4359} \or:
15294     + 4 \__fp_exp_large:w {8103}{0839}{2757}{5384}{0077}{1000} \or:
15295     \fi:
15296     #1;
15297     \__fp_exp_large_:wN
15298 }
15299 \cs_new:Npn \__fp_exp_large_:wN #1; #2
15300 {
15301     \if_case:w #2 ~          \exp_after:wN \__fp_fixed_continue:wn \or:

```

```

15302     + 1 \__fp_exp_large:w {1105}{1709}{1807}{5647}{6248}{1171} \or:
15303     + 1 \__fp_exp_large:w {1221}{4027}{5816}{0169}{8339}{2107} \or:
15304     + 1 \__fp_exp_large:w {1349}{8588}{0757}{6003}{1039}{8374} \or:
15305     + 1 \__fp_exp_large:w {1491}{8246}{9764}{1270}{3178}{2485} \or:
15306     + 1 \__fp_exp_large:w {1648}{7212}{7070}{0128}{1468}{4865} \or:
15307     + 1 \__fp_exp_large:w {1822}{1188}{0039}{0508}{9748}{7537} \or:
15308     + 1 \__fp_exp_large:w {2013}{7527}{0747}{0476}{5216}{2455} \or:
15309     + 1 \__fp_exp_large:w {2225}{5409}{2849}{2467}{6045}{7954} \or:
15310     + 1 \__fp_exp_large:w {2459}{6031}{1115}{6949}{6638}{0013} \or:
15311     \fi:
15312     #1;
15313     \__fp_exp_large_after:wwn
15314 }
15315 \cs_new:Npn \__fp_exp_large_after:wwn #1; #2; #3
15316 {
15317     \__fp_exp_Taylor:Nnnwn ? { } { } 0 #2; {} #3
15318     \__fp_fixed_mul:wwn #1;
15319 }

```

(End definition for `__fp_exp_pos_large:NnnNwn` and others.)

28.3 Power

Raising a number a to a power b leads to many distinct situations.

a^b	$-\infty$	$(-\infty, -0)$	$-\text{integer}$	± 0	$+\text{integer}$	$(0, \infty)$	$+\infty$	NaN
$+\infty$	$+0$		$+0$	$+1$	$+\infty$		$+\infty$	NaN
$(1, \infty)$	$+0$		$+ a ^b$	$+1$	$+ a ^b$		$+\infty$	NaN
$+1$	$+1$		$+1$	$+1$	$+1$		$+1$	$+1$
$(0, 1)$	$+\infty$		$+ a ^b$	$+1$	$+ a ^b$		$+0$	NaN
$+0$	$+\infty$		$+\infty$	$+1$	$+0$		$+0$	NaN
-0	$+\infty$	NaN	$(-1)^b \infty$	$+1$	$(-1)^b 0$	$+0$	$+0$	NaN
$(-1, 0)$	$+\infty$	NaN	$(-1)^b a ^b$	$+1$	$(-1)^b a ^b$	NaN	$+0$	NaN
-1	$+1$	NaN	$(-1)^b$	$+1$	$(-1)^b$	NaN	$+1$	NaN
$(-\infty, -1)$	$+0$	NaN	$(-1)^b a ^b$	$+1$	$(-1)^b a ^b$	NaN	$+\infty$	NaN
$-\infty$	$+0$	$+0$	$(-1)^b 0$	$+1$	$(-1)^b \infty$	NaN	$+\infty$	NaN
NaN	NaN	NaN	NaN	$+1$	NaN	NaN	NaN	NaN

We distinguished in this table the cases of finite (positive or negative) integer exponents, as $(-1)^b$ is defined in that case. One peculiarity of this operation is that $\text{NaN}^0 = 1^{\text{NaN}} = 1$, because this relation is obeyed for any number, even $\pm\infty$.

`__fp^_o:ww` We cram most of the tests into a single function to save csnames. First treat the case $b = 0$: $a^0 = 1$ for any a , even `nan`. Then test the sign of a .

- If it is positive, and a is a normal number, call `__fp_pow_normal_o:ww` followed by the two `fp` a and b . For $a = +0$ or $+\text{inf}$, call `__fp_pow_zero_or_inf:ww` instead, to return either $+0$ or $+\infty$ as appropriate.
- If a is a `nan`, then skip to the next semicolon (which happens to be conveniently the end of b) and return `nan`.

- Finally, if a is negative, compute a^b (`__fp_pow_normal_o:ww` which ignores the sign of its first operand), and keep an extra copy of a and b (the second brace group, containing $\{ b a \}$, is inserted between a and b). Then do some tests to find the final sign of the result if it exists.

```

15320 \cs_new:cpn { __fp_ \iow_char:N \^_o:ww }
15321   \s__fp \__fp_chk:w #1#2#3; \s__fp \__fp_chk:w #4#5#6;
15322   {
15323     \if_meaning:w 0 #4
15324       \__fp_case_return_o:Nw \c_one_fp
15325     \fi:
15326     \if_case:w #2 \exp_stop_f:
15327       \exp_after:wN \use_i:nn
15328     \or:
15329       \__fp_case_return_o:Nw \c_nan_fp
15330     \else:
15331       \exp_after:wN \__fp_pow_neg:www
15332       \exp:w \exp_end_continue_f:w \exp_after:wN \use:nn
15333     \fi:
15334     {
15335       \if_meaning:w 1 #1
15336         \exp_after:wN \__fp_pow_normal_o:ww
15337       \else:
15338         \exp_after:wN \__fp_pow_zero_or_inf:ww
15339       \fi:
15340       \s__fp \__fp_chk:w #1#2#3;
15341     }
15342     { \s__fp \__fp_chk:w #4#5#6; \s__fp \__fp_chk:w #1#2#3; }
15343     \s__fp \__fp_chk:w #4#5#6;
15344   }

```

(End definition for `__fp_ \^_o:ww`.)

`__fp_pow_zero_or_inf:ww` Raising -0 or $-\infty$ to `nan` yields `nan`. For other powers, the result is $+0$ if 0 is raised to a positive power or ∞ to a negative power, and $+\infty$ otherwise. Thus, if the type of a and the sign of b coincide, the result is 0 , since those conveniently take the same possible values, 0 and 2 . Otherwise, either $a = \pm\infty$ and $b > 0$ and the result is $+\infty$, or $a = \pm 0$ with $b < 0$ and we have a division by zero unless $b = -\infty$.

```

15345 \cs_new:Npn \__fp_pow_zero_or_inf:ww
15346   \s__fp \__fp_chk:w #1#2; \s__fp \__fp_chk:w #3#4
15347   {
15348     \if_meaning:w 1 #4
15349       \__fp_case_return_same_o:w
15350     \fi:
15351     \if_meaning:w #1 #4
15352       \__fp_case_return_o:Nw \c_zero_fp
15353     \fi:
15354     \if_meaning:w 2 #1
15355       \__fp_case_return_o:Nw \c_inf_fp
15356     \fi:
15357     \if_meaning:w 2 #3
15358       \__fp_case_return_o:Nw \c_inf_fp
15359     \else:
15360       \__fp_case_use:nw

```

```

15361     {
15362         \__fp_division_by_zero_o:NNww \c_inf_fp ^
15363         \s__fp \__fp_chk:w #1 #2 ;
15364     }
15365     \fi:
15366     \s__fp \__fp_chk:w #3#4
15367 }

```

(End definition for __fp_pow_zero_or_inf:ww.)

__fp_pow_normal_o:ww We have in front of us a , and $b \neq 0$, we know that a is a normal number, and we wish to compute $|a|^b$. If $|a| = 1$, we return 1, unless $a = -1$ and b is **nan**. Indeed, returning 1 at this point would wrongly raise “invalid” when the sign is considered. If $|a| \neq 1$, test the type of b :

0 Impossible, we already filtered $b = \pm 0$.

1 Call __fp_pow_npos_o:Nww.

2 Return $+\infty$ or $+0$ depending on the sign of b and whether the exponent of a is positive or not.

3 Return b .

```

15368 \cs_new:Npn \__fp_pow_normal_o:ww
15369     \s__fp \__fp_chk:w 1 #1#2#3; \s__fp \__fp_chk:w #4#5
15370 {
15371     \if_int_compare:w \__str_if_eq_x:nn { #2 #3 }
15372         { 1 {1000} {0000} {0000} {0000} } = 0 \exp_stop_f:
15373         \if_int_compare:w #4 #1 = 32 \exp_stop_f:
15374         \exp_after:wN \__fp_case_return_ii_o:ww
15375     \fi:
15376     \__fp_case_return_o:Nww \c_one_fp
15377 \fi:
15378 \if_case:w #4 \exp_stop_f:
15379 \or:
15380     \exp_after:wN \__fp_pow_npos_o:Nww
15381     \exp_after:wN #5
15382 \or:
15383     \if_meaning:w 2 #5 \exp_after:wN \reverse_if:N \fi:
15384     \if_int_compare:w #2 > 0 \exp_stop_f:
15385     \exp_after:wN \__fp_case_return_o:Nww
15386     \exp_after:wN \c_inf_fp
15387 \else:
15388     \exp_after:wN \__fp_case_return_o:Nww
15389     \exp_after:wN \c_zero_fp
15390 \fi:
15391 \or:
15392     \__fp_case_return_ii_o:ww
15393 \fi:
15394 \s__fp \__fp_chk:w 1 #1 {#2} #3 ;
15395 \s__fp \__fp_chk:w #4 #5
15396 }

```

(End definition for __fp_pow_normal_o:ww.)

_fp_pow_npos_o:Nww We now know that $a \neq \pm 1$ is a normal number, and b is a normal number too. We want to compute $|a|^b = (|x| \cdot 10^n)^{y \cdot 10^p} = \exp((\ln|x| + n \ln(10)) \cdot y \cdot 10^p) = \exp(z)$. To compute the exponential accurately, we need to know the digits of z up to the 16-th position. Since the exponential of 10^5 is infinite, we only need at most 21 digits, hence the fixed point result of _fp_ln_o:w is precise enough for our needs. Start an integer expression for the decimal exponent of $e^{|z|}$. If z is negative, negate that decimal exponent, and prepare to take the inverse when converting from the fixed point to the floating point result.

```

15397 \cs_new:Npn \_fp_pow_npos_o:Nww #1 \s__fp \_fp_chk:w 1#2#3
15398 {
15399   \exp_after:wN \_fp_sanitize:Nw
15400   \exp_after:wN 0
15401   \__int_value:w
15402   \if:w #1 \if_int_compare:w #3 > 0 \exp_stop_f: 0 \else: 2 \fi:
15403   \exp_after:wN \_fp_pow_npos_aux:NNnw
15404   \exp_after:wN +
15405   \exp_after:wN \_fp_fixed_to_float_o:wN
15406   \else:
15407   \exp_after:wN \_fp_pow_npos_aux:NNnw
15408   \exp_after:wN -
15409   \exp_after:wN \_fp_fixed_inv_to_float_o:wN
15410   \fi:
15411   {#3}
15412 }

```

(End definition for _fp_pow_npos_o:Nww.)

_fp_pow_npos_aux:NNnw The first argument is the conversion function from fixed point to float. Then comes an exponent and the 4 brace groups of x , followed by b . Compute $-\ln(x)$.

```

15413 \cs_new:Npn \_fp_pow_npos_aux:NNnw #1#2#3#4#5; \s__fp \_fp_chk:w 1#6#7#8;
15414 {
15415   #1
15416   \__int_eval:w
15417   \_fp_ln_significand:NNNNnnnN #4#5
15418   \_fp_pow_exponent:wnN {#3}
15419   \_fp_fixed_mul:wwN #8 {0000}{0000} ;
15420   \_fp_pow_B:wwN #7;
15421   #1 #2 0 % fixed_to_float_o:wN
15422 }
15423 \cs_new:Npn \_fp_pow_exponent:wnN #1; #2
15424 {
15425   \if_int_compare:w #2 > 0 \exp_stop_f:
15426   \exp_after:wN \_fp_pow_exponent:Nwnnnnw % n\ln(10) - (-\ln(x))
15427   \exp_after:wN +
15428   \else:
15429   \exp_after:wN \_fp_pow_exponent:Nwnnnnw % -(\ln|\ln(10) + (-\ln(x)))
15430   \exp_after:wN -
15431   \fi:
15432   #2; #1;
15433 }
15434 \cs_new:Npn \_fp_pow_exponent:Nwnnnnw #1#2; #3#4#5#6#7#8;
15435 { %^A todo: use that in ln.
15436   \exp_after:wN \_fp_fixed_mul_after:wwN
15437   \__int_value:w \__int_eval:w \c__fp_leading_shift_int

```



```

15438     \exp_after:wN \__fp_pack:NNNNNw
15439     \__int_value:w \__int_eval:w \c__fp_middle_shift_int
15440     #1#2*23025 - #1 #3
15441     \exp_after:wN \__fp_pack:NNNNNw
15442     \__int_value:w \__int_eval:w \c__fp_middle_shift_int
15443     #1 #2*8509 - #1 #4
15444     \exp_after:wN \__fp_pack:NNNNNw
15445     \__int_value:w \__int_eval:w \c__fp_middle_shift_int
15446     #1 #2*2994 - #1 #5
15447     \exp_after:wN \__fp_pack:NNNNNw
15448     \__int_value:w \__int_eval:w \c__fp_middle_shift_int
15449     #1 #2*0456 - #1 #6
15450     \exp_after:wN \__fp_pack:NNNNNw
15451     \__int_value:w \__int_eval:w \c__fp_trailing_shift_int
15452     #1 #2*8401 - #1 #7
15453     #1 ( #2*7991 - #8 ) / 1 0000 ; ;
15454 }
15455 \cs_new:Npn \__fp_pow_B:wwN #1#2#3#4#5#6; #7;
15456 {
15457     \if_int_compare:w #7 < 0 \exp_stop_f:
15458     \exp_after:wN \__fp_pow_C_neg:w \__int_value:w -
15459     \else:
15460     \if_int_compare:w #7 < 22 \exp_stop_f:
15461     \exp_after:wN \__fp_pow_C_pos:w \__int_value:w
15462     \else:
15463     \exp_after:wN \__fp_pow_C_overflow:w \__int_value:w
15464     \fi:
15465     \fi:
15466     #7 \exp_after:wN ;
15467     \__int_value:w \__int_eval:w 10 0000 + #1 \__int_eval_end:
15468     #2#3#4#5#6 0000 0000 0000 0000 0000 0000 ; %^A todo: how many 0?
15469 }
15470 \cs_new:Npn \__fp_pow_C_overflow:w #1; #2; #3
15471 {
15472     + 2 * \c__fp_max_exponent_int
15473     \exp_after:wN \__fp_fixed_continue:wn \c__fp_one_fixed_tl
15474 }
15475 \cs_new:Npn \__fp_pow_C_neg:w #1 ; 1
15476 {
15477     \exp_after:wN \exp_after:wN \exp_after:wN \__fp_pow_C_pack:w
15478     \prg_replicate:nn {#1} {0}
15479 }
15480 \cs_new:Npn \__fp_pow_C_pos:w #1; 1
15481 { \__fp_pow_C_pos_loop:wN #1; }
15482 \cs_new:Npn \__fp_pow_C_pos_loop:wN #1; #2
15483 {
15484     \if_meaning:w 0 #1
15485     \exp_after:wN \__fp_pow_C_pack:w
15486     \exp_after:wN #2
15487     \else:
15488     \if_meaning:w 0 #2
15489     \exp_after:wN \__fp_pow_C_pos_loop:wN \__int_value:w
15490     \else:
15491     \exp_after:wN \__fp_pow_C_overflow:w \__int_value:w

```

```

15492     \fi:
15493     \__int_eval:w #1 - 1 \exp_after:wN ;
15494     \fi:
15495   }
15496 \cs_new:Npn \__fp_pow_C_pack:w
15497 { \exp_after:wN \__fp_exp_large_v:wN \c__fp_one_fixed_tl }

```

(End definition for __fp_pow_npos_aux:NNnw.)

__fp_pow_neg:www
__fp_pow_neg_aux:wNN

This function is followed by three floating point numbers: a^b , $a \in [-\infty, -0]$, and b . If b is an even integer (case -1), $a^b = a^b$. If b is an odd integer (case 0), $a^b = -a^b$, obtained by a call to __fp_pow_neg_aux:wNN. Otherwise, the sign is undefined. This is invalid, unless a^b turns out to be $+0$ or nan , in which case we return that as a^b . In particular, since the underflow detection occurs before __fp_pow_neg:www is called, $(-0.1)**(12345.67)$ gives $+0$ rather than complaining that the sign is not defined.

```

15498 \cs_new:Npn \__fp_pow_neg:www \s__fp \__fp_chk:w #1#2; #3; #4;
15499 {
15500   \if_case:w \__fp_pow_neg_case:w #4 ;
15501     \exp_after:wN \__fp_pow_neg_aux:wNN
15502   \or:
15503     \if_int_compare:w \__int_eval:w #1 / 2 = 1 \exp_stop_f:
15504     \__fp_invalid_operation_o:Nww ^ #3; #4;
15505     \exp:w \exp_end_continue_f:w
15506     \exp_after:wN \exp_after:wN
15507     \exp_after:wN \__fp_use_none_until_s:w
15508   \fi:
15509   \fi:
15510   \__fp_exp_after_o:w
15511   \s__fp \__fp_chk:w #1#2;
15512 }
15513 \cs_new:Npn \__fp_pow_neg_aux:wNN #1 \s__fp \__fp_chk:w #2#3
15514 {
15515   \exp_after:wN \__fp_exp_after_o:w
15516   \exp_after:wN \s__fp
15517   \exp_after:wN \__fp_chk:w
15518   \exp_after:wN #2
15519   \__int_value:w \__int_eval:w 2 - #3 \__int_eval_end:
15520 }

```

(End definition for __fp_pow_neg:www and __fp_pow_neg_aux:wNN.)

__fp_pow_neg_case:w
__fp_pow_neg_case_aux:nnnnn
__fp_pow_neg_case_aux:Nnnw

This function expects a floating point number, and determines its “parity”. It should be used after \if_case:w or in an integer expression. It gives -1 if the number is an even integer, 0 if the number is an odd integer, and 1 otherwise. Zeros and $\pm\infty$ are even (because very large finite floating points are even), while nan is a non-integer. The sign of normal numbers is irrelevant to parity. After __fp_decimate:nNnnnn the argument $\#1$ of __fp_pow_neg_case_aux:Nnnw is a rounding digit, 0 if and only if the number was an integer, and $\#3$ is the 8 least significant digits of that integer.

```

15521 \cs_new:Npn \__fp_pow_neg_case:w \s__fp \__fp_chk:w #1#2#3;
15522 {
15523   \if_case:w #1 \exp_stop_f:
15524     -1
15525   \or: \__fp_pow_neg_case_aux:nnnnn #3

```

```

15526     \or:   -1
15527     \else: 1
15528     \fi:
15529     \exp_stop_f:
15530   }
15531 \cs_new:Npn \__fp_pow_neg_case_aux:nnnnn #1#2#3#4#5
15532 {
15533   \if_int_compare:w #1 > \c__fp_prec_int
15534     -1
15535   \else:
15536     \__fp_decimate:nNnnnn { \c__fp_prec_int - #1 }
15537     \__fp_pow_neg_case_aux:Nnnw
15538     {#2} {#3} {#4} {#5}
15539   \fi:
15540 }
15541 \cs_new:Npn \__fp_pow_neg_case_aux:Nnnw #1#2#3#4 ;
15542 {
15543   \if_meaning:w 0 #1
15544     \if_int_odd:w #3 \exp_stop_f:
15545     0
15546   \else:
15547     -1
15548   \fi:
15549   \else:
15550     1
15551   \fi:
15552 }

```

(End definition for `__fp_pow_neg_case:w`, `__fp_pow_neg_case_aux:nnnnn`, and `__fp_pow_neg_case_aux:Nnnw`.)

```

15553 </initex | package>

```

29 l3fp-trig Implementation

```

15554 <*initex | package>

```

```

15555 <@@=fp>

```

Unary functions.

```

\__fp_parse_word_acos:N
\__fp_parse_word_acosd:N
\__fp_parse_word_acsc:N
\__fp_parse_word_acscd:N
\__fp_parse_word_asec:N
\__fp_parse_word_asecd:N
\__fp_parse_word_asin:N
\__fp_parse_word_asind:N
\__fp_parse_word_cos:N
\__fp_parse_word_cosd:N
\__fp_parse_word_cot:N
\__fp_parse_word_cotd:N
\__fp_parse_word_csc:N
\__fp_parse_word_cscd:N
\__fp_parse_word_sec:N
\__fp_parse_word_secd:N
\__fp_parse_word_sin:N
\__fp_parse_word_sind:N
\__fp_parse_word_tan:N
\__fp_parse_word_tand:N

```

```

15556 \tl_map_inline:nn
15557 {
15558   {acos} {acsc} {asec} {asin}
15559   {cos} {cot} {csc} {sec} {sin} {tan}
15560 }
15561 {
15562   \cs_new:cpx { __fp_parse_word_#1:N }
15563   {
15564     \exp_not:N \__fp_parse_unary_function:NNN
15565     \exp_not:c { __fp_#1_o:w }
15566     \exp_not:N \use_i:nn
15567   }
15568   \cs_new:cpx { __fp_parse_word_#1d:N }
15569   {
15570     \exp_not:N \__fp_parse_unary_function:NNN

```

```

15571         \exp_not:c { __fp_#1_o:w }
15572         \exp_not:N \use_ii:nn
15573     }
15574 }

```

(End definition for `__fp_parse_word_acos:N` and others.)

```

\__fp_parse_word_acot:N
\__fp_parse_word_acotd:N
\__fp_parse_word_atan:N
\__fp_parse_word_atand:N
15575 \cs_new:Npn \__fp_parse_word_acot:N
15576 { \__fp_parse_function:NNN \__fp_acot_o:Nw \use_i:nn }
15577 \cs_new:Npn \__fp_parse_word_acotd:N
15578 { \__fp_parse_function:NNN \__fp_acot_o:Nw \use_ii:nn }
15579 \cs_new:Npn \__fp_parse_word_atan:N
15580 { \__fp_parse_function:NNN \__fp_atan_o:Nw \use_i:nn }
15581 \cs_new:Npn \__fp_parse_word_atand:N
15582 { \__fp_parse_function:NNN \__fp_atan_o:Nw \use_ii:nn }

```

(End definition for `__fp_parse_word_acot:N` and others.)

29.1 Direct trigonometric functions

The approach for all trigonometric functions (sine, cosine, tangent, cotangent, cosecant, and secant), with arguments given in radians or in degrees, is the same.

- Filter out special cases (± 0 , $\pm \infty$ and NaN).
- Keep the sign for later, and work with the absolute value $|x|$ of the argument.
- Small numbers ($|x| < 1$ in radians, $|x| < 10$ in degrees) are converted to fixed point numbers (and to radians if $|x|$ is in degrees).
- For larger numbers, we need argument reduction. Subtract a multiple of $\pi/2$ (in degrees, 90) to bring the number to the range to $[0, \pi/2)$ (in degrees, $[0, 90)$).
- Reduce further to $[0, \pi/4]$ (in degrees, $[0, 45]$) using $\sin x = \cos(\pi/2 - x)$, and when working in degrees, convert to radians.
- Use the appropriate power series depending on the octant $\lfloor \frac{x}{\pi/4} \rfloor \bmod 8$ (in degrees, the same formula with $\pi/4 \rightarrow 45$), the sign, and the function to compute.

29.1.1 Filtering special cases

`__fp_sin_o:w` This function, and its analogs for `cos`, `csc`, `sec`, `tan`, and `cot` instead of `sin`, are followed either by `\use_i:nn` and a float in radians or by `\use_ii:nn` and a float in degrees. The sine of ± 0 or NaN is the same float. The sine of $\pm \infty$ raises an invalid operation exception with the appropriate function name. Otherwise, call the `trig` function to perform argument reduction and if necessary convert the reduced argument to radians. Then, `__fp_sin_series_o:NNwww` is called to compute the Taylor series: this function receives a sign `#3`, an initial octant of 0, and the function `__fp_ep_to_float_o:wwN` which converts the result of the series to a floating point directly rather than taking its inverse, since $\sin(x) = \#3 \sin|x|$.

```

15583 \cs_new:Npn \__fp_sin_o:w #1 \s__fp \__fp_chk:w #2#3#4; @
15584 {
15585     \if_case:w #2 \exp_stop_f:

```

```

15586         \__fp_case_return_same_o:w
15587     \or:  \__fp_case_use:nw
15588         {
15589             \__fp_trig:NNNNNwn #1 \__fp_sin_series_o:NNwww
15590             \__fp_ep_to_float_o:wwN #3 0
15591         }
15592     \or:  \__fp_case_use:nw
15593         { \__fp_invalid_operation_o:fw { #1 { sin } { sind } } }
15594     \else: \__fp_case_return_same_o:w
15595     \fi:
15596     \s__fp \__fp_chk:w #2 #3 #4;
15597 }

```

(End definition for __fp_sin_o:w.)

__fp_cos_o:w The cosine of ± 0 is 1. The cosine of $\pm\infty$ raises an invalid operation exception. The cosine of NaN is itself. Otherwise, the `trig` function reduces the argument to at most half a right-angle and converts if necessary to radians. We then call the same series as for sine, but using a positive sign 0 regardless of the sign of x , and with an initial octant of 2, because $\cos(x) = +\sin(\pi/2 + |x|)$.

```

15598 \cs_new:Npn \__fp_cos_o:w #1 \s__fp \__fp_chk:w #2#3; @
15599 {
15600     \if_case:w #2 \exp_stop_f:
15601         \__fp_case_return_o:Nw \c_one_fp
15602     \or:  \__fp_case_use:nw
15603         {
15604             \__fp_trig:NNNNNwn #1 \__fp_sin_series_o:NNwww
15605             \__fp_ep_to_float_o:wwN 0 2
15606         }
15607     \or:  \__fp_case_use:nw
15608         { \__fp_invalid_operation_o:fw { #1 { cos } { cosd } } }
15609     \else: \__fp_case_return_same_o:w
15610     \fi:
15611     \s__fp \__fp_chk:w #2 #3;
15612 }

```

(End definition for __fp_cos_o:w.)

__fp_csc_o:w The cosecant of ± 0 is $\pm\infty$ with the same sign, with a division by zero exception (see __fp_cot_zero_o:Nfw defined below), which requires the function name. The cosecant of $\pm\infty$ raises an invalid operation exception. The cosecant of NaN is itself. Otherwise, the `trig` function performs the argument reduction, and converts if necessary to radians before calling the same series as for sine, using the sign #3, a starting octant of 0, and inverting during the conversion from the fixed point sine to the floating point result, because $\csc(x) = \#3(\sin|x|)^{-1}$.

```

15613 \cs_new:Npn \__fp_csc_o:w #1 \s__fp \__fp_chk:w #2#3#4; @
15614 {
15615     \if_case:w #2 \exp_stop_f:
15616         \__fp_cot_zero_o:Nfw #3 { #1 { csc } { csd } }
15617     \or:  \__fp_case_use:nw
15618         {
15619             \__fp_trig:NNNNNwn #1 \__fp_sin_series_o:NNwww
15620             \__fp_ep_inv_to_float_o:wwN #3 0
15621         }

```

```

15622     \or:   \__fp_case_use:nw
15623           { \__fp_invalid_operation_o:fw { #1 { csc } { cscd } } }
15624     \else: \__fp_case_return_same_o:w
15625     \fi:
15626     \s__fp \__fp_chk:w #2 #3 #4;
15627   }

```

(End definition for __fp_csc_o:w.)

__fp_sec_o:w The secant of ± 0 is 1. The secant of $\pm\infty$ raises an invalid operation exception. The secant of NaN is itself. Otherwise, the `trig` function reduces the argument and turns it to radians before calling the same series as for sine, using a positive sign 0, a starting octant of 2, and inverting upon conversion, because $\sec(x) = +1/\sin(\pi/2 + |x|)$.

```

15628 \cs_new:Npn \__fp_sec_o:w #1 \s__fp \__fp_chk:w #2#3; @
15629 {
15630   \if_case:w #2 \exp_stop_f:
15631     \__fp_case_return_o:Nw \c_one_fp
15632   \or:   \__fp_case_use:nw
15633         {
15634           \__fp_trig:NNNNNwn #1 \__fp_sin_series_o:NNwww
15635           \__fp_ep_inv_to_float_o:wwN 0 2
15636         }
15637   \or:   \__fp_case_use:nw
15638         { \__fp_invalid_operation_o:fw { #1 { sec } { secd } } }
15639   \else: \__fp_case_return_same_o:w
15640   \fi:
15641   \s__fp \__fp_chk:w #2 #3;
15642 }

```

(End definition for __fp_sec_o:w.)

__fp_tan_o:w The tangent of ± 0 or NaN is the same floating point number. The tangent of $\pm\infty$ raises an invalid operation exception. Once more, the `trig` function does the argument reduction step and conversion to radians before calling `__fp_tan_series_o:NNwww`, with a sign #3 and an initial octant of 1 (this shift is somewhat arbitrary). See `__fp_cot_o:w` for an explanation of the 0 argument.

```

15643 \cs_new:Npn \__fp_tan_o:w #1 \s__fp \__fp_chk:w #2#3#4; @
15644 {
15645   \if_case:w #2 \exp_stop_f:
15646     \__fp_case_return_same_o:w
15647   \or:   \__fp_case_use:nw
15648         {
15649           \__fp_trig:NNNNNwn #1
15650           \__fp_tan_series_o:NNwww 0 #3 1
15651         }
15652   \or:   \__fp_case_use:nw
15653         { \__fp_invalid_operation_o:fw { #1 { tan } { tand } } }
15654   \else: \__fp_case_return_same_o:w
15655   \fi:
15656   \s__fp \__fp_chk:w #2 #3 #4;
15657 }

```

(End definition for __fp_tan_o:w.)

_fp_cot_o:w
_fp_cot_zero_o:Nfw

The cotangent of ± 0 is $\pm\infty$ with the same sign, with a division by zero exception (see _fp_cot_zero_o:Nfw. The cotangent of $\pm\infty$ raises an invalid operation exception. The cotangent of NaN is itself. We use $\cot x = -\tan(\pi/2 + x)$, and the initial octant for the tangent was chosen to be 1, so the octant here starts at 3. The change in sign is obtained by feeding _fp_tan_series_o:NNwww two signs rather than just the sign of the argument: the first of those indicates whether we compute tangent or cotangent. Those signs are eventually combined.

```

15658 \cs_new:Npn \_fp_cot_o:w #1 \s__fp \_fp_chk:w #2#3#4; @
15659 {
15660   \if_case:w #2 \exp_stop_f:
15661     \_fp_cot_zero_o:Nfw #3 { #1 { cot } { cotd } }
15662   \or: \_fp_case_use:nw
15663     {
15664       \_fp_trig:NNNNwn #1
15665       \_fp_tan_series_o:NNwww 2 #3 3
15666     }
15667   \or: \_fp_case_use:nw
15668     { \_fp_invalid_operation_o:fw { #1 { cot } { cotd } } }
15669   \else: \_fp_case_return_same_o:w
15670   \fi:
15671   \s__fp \_fp_chk:w #2 #3 #4;
15672 }
15673 \cs_new:Npn \_fp_cot_zero_o:Nfw #1#2#3 \fi:
15674 {
15675   \fi:
15676   \token_if_eq_meaning:NNTF 0 #1
15677     { \exp_args:NNf \_fp_division_by_zero_o:Nnw \c_inf_fp }
15678     { \exp_args:NNf \_fp_division_by_zero_o:Nnw \c_minus_inf_fp }
15679   {#2}
15680 }

```

(End definition for _fp_cot_o:w and _fp_cot_zero_o:Nfw.)

29.1.2 Distinguishing small and large arguments

_fp_trig:NNNNwn

The first argument is \use_i:nn if the operand is in radians and \use_ii:nn if it is in degrees. Arguments #2 to #5 control what trigonometric function we compute, and #6 to #8 are pieces of a normal floating point number. Call the _series function #2, with arguments #3, either a conversion function (_fp_ep_to_float_o:wN or _fp_ep_inv_to_float_o:wN) or a sign 0 or 2 when computing tangent or cotangent; #4, a sign 0 or 2; the octant, computed in an integer expression starting with #5 and stopped by a period; and a fixed point number obtained from the floating point number by argument reduction (if necessary) and conversion to radians (if necessary). Any argument reduction adjusts the octant accordingly by leaving a (positive) shift into its integer expression. Let us explain the integer comparison. Two of the four \exp_after:wN are expanded, the expansion hits the test, which is true if the float is at least 1 when working in radians, and at least 10 when working in degrees. Then one of the remaining \exp_after:wN hits #1, which picks the trig or trigd function in whichever branch of the conditional was taken. The final \exp_after:wN closes the conditional. At the end of the day, a number is **large** if it is ≥ 1 in radians or ≥ 10 in degrees, and **small** otherwise. All four trig/trigd auxiliaries receive the operand as an extended-precision number.

```

15681 \cs_new:Npn \_fp_trig:NNNNwn #1#2#3#4#5 \s__fp \_fp_chk:w 1#6#7#8;

```

```

15682 {
15683   \exp_after:wN #2
15684   \exp_after:wN #3
15685   \exp_after:wN #4
15686   \__int_value:w \__int_eval:w #5
15687   \exp_after:wN \exp_after:wN \exp_after:wN \exp_after:wN
15688   \if_int_compare:w #7 > #1 0 1 \exp_stop_f:
15689     #1 \__fp_trig_large:ww \__fp_trigd_large:ww
15690   \else:
15691     #1 \__fp_trig_small:ww \__fp_trigd_small:ww
15692   \fi:
15693   #7,#8{0000}{0000};
15694 }

```

(End definition for __fp_trig:NNNNNwn.)

29.1.3 Small arguments

__fp_trig_small:ww This receives a small extended-precision number in radians and converts it to a fixed point number. Some trailing digits may be lost in the conversion, so we keep the original floating point number around: when computing sine or tangent (or their inverses), the last step is to multiply by the floating point number (as an extended-precision number) rather than the fixed point number. The period serves to end the integer expression for the octant.

```

15695 \cs_new:Npn \__fp_trig_small:ww #1,#2;
15696 { \__fp_ep_to_fixed:wwn #1,#2; . #1,#2; }

```

(End definition for __fp_trig_small:ww.)

__fp_trigd_small:ww Convert the extended-precision number to radians, then call __fp_trig_small:ww to massage it in the form appropriate for the `_series` auxiliary.

```

15697 \cs_new:Npn \__fp_trigd_small:ww #1,#2;
15698 {
15699   \__fp_ep_mul_raw:wwwN
15700   -1,{1745}{3292}{5199}{4329}{5769}{2369}; #1,#2;
15701   \__fp_trig_small:ww
15702 }

```

(End definition for __fp_trigd_small:ww.)

29.1.4 Argument reduction in degrees

__fp_trigd_large:ww Note that $25 \times 360 = 9000$, so $10^{k+1} \equiv 10^k \pmod{360}$ for $k \geq 3$. When the exponent #1 is very large, we can thus safely replace it by 22 (or even 19). We turn the floating point number into a fixed point number with two blocks of 8 digits followed by five blocks of 4 digits. The original float is $100 \times \langle block_1 \rangle \cdots \langle block_3 \rangle . \langle block_4 \rangle \cdots \langle block_7 \rangle$, or is equal to it modulo 360 if the exponent #1 is very large. The first auxiliary finds $\langle block_1 \rangle + \langle block_2 \rangle \pmod{9}$, a single digit, and prepends it to the 4 digits of $\langle block_3 \rangle$. It also unpacks $\langle block_4 \rangle$ and grabs the 4 digits of $\langle block_7 \rangle$. The second auxiliary grabs the $\langle block_3 \rangle$ plus any contribution from the first two blocks as #1, the first digit of $\langle block_4 \rangle$ (just after the decimal point in hundreds of degrees) as #2, and the three other digits as #3. It finds the quotient and remainder of #1#2 modulo 9, adds twice the quotient to the integer expression for the octant, and places the remainder (between 0 and 8) before #3 to form

a new $\langle block_4 \rangle$. The resulting fixed point number is $x \in [0, 0.9]$. If $x \geq 0.45$, we add 1 to the octant and feed $0.9 - x$ with an exponent of 2 (to compensate the fact that we are working in units of hundreds of degrees rather than degrees) to `_fp_trigd_small:ww`. Otherwise, we feed it x with an exponent of 2. The third auxiliary also discards digits which were not packed into the various $\langle blocks \rangle$. Since the original exponent #1 is at least 2, those are all 0 and no precision is lost (#6 and #7 are four 0 each).

```

15703 \cs_new:Npn \_fp_trigd_large:ww #1, #2#3#4#5#6#7;
15704 {
15705   \exp_after:wN \_fp_pack_eight:wNNNNNNNN
15706   \exp_after:wN \_fp_pack_eight:wNNNNNNNN
15707   \exp_after:wN \_fp_pack_twice_four:wNNNNNNNN
15708   \exp_after:wN \_fp_pack_twice_four:wNNNNNNNN
15709   \exp_after:wN \_fp_trigd_large_auxi:nnnnwNNNN
15710   \exp_after:wN ;
15711   \exp:w \exp_end_continue_f:w
15712   \prg_replicate:nn { \int_max:nn { 22 - #1 } { 0 } } { 0 }
15713   #2#3#4#5#6#7 0000 0000 0000 !
15714 }
15715 \cs_new:Npn \_fp_trigd_large_auxi:nnnnwNNNN #1#2#3#4#5; #6#7#8#9
15716 {
15717   \exp_after:wN \_fp_trigd_large_auxii:wNw
15718   \_int_value:w \_int_eval:w #1 + #2
15719   - (#1 + #2 - 4) / 9 * 9 \_int_eval_end:
15720   #3;
15721   #4; #5{#6#7#8#9};
15722 }
15723 \cs_new:Npn \_fp_trigd_large_auxii:wNw #1; #2#3;
15724 {
15725   + (#1#2 - 4) / 9 * 2
15726   \exp_after:wN \_fp_trigd_large_auxiii:www
15727   \_int_value:w \_int_eval:w #1#2
15728   - (#1#2 - 4) / 9 * 9 \_int_eval_end: #3 ;
15729 }
15730 \cs_new:Npn \_fp_trigd_large_auxiii:www #1; #2; #3!
15731 {
15732   \if_int_compare:w #1 < 4500 \exp_stop_f:
15733   \exp_after:wN \_fp_use_i_until_s:nw
15734   \exp_after:wN \_fp_fixed_continue:wn
15735   \else:
15736     + 1
15737   \fi:
15738   \_fp_fixed_sub:wnn {9000}{0000}{0000}{0000}{0000}{0000};
15739   {#1}#2{0000}{0000};
15740   { \_fp_trigd_small:ww 2, }
15741 }

```

(End definition for `_fp_trigd_large:ww` and others.)

29.1.5 Argument reduction in radians

Arguments greater or equal to 1 need to be reduced to a range where we only need a few terms of the Taylor series. We reduce to the range $[0, 2\pi]$ by subtracting multiples of 2π , then to the smaller range $[0, \pi/2]$ by subtracting multiples of $\pi/2$ (keeping track of how

many times $\pi/2$ is subtracted), then to $[0, \pi/4]$ by mapping $x \rightarrow \pi/2 - x$ if appropriate. When the argument is very large, say, 10^{100} , an equally large multiple of 2π must be subtracted, hence we must work with a very good approximation of 2π in order to get a sensible remainder modulo 2π .

Specifically, we multiply the argument by an approximation of $1/(2\pi)$ with 10048 digits, then discard the integer part of the result, keeping 52 digits of the fractional part. From the fractional part of $x/(2\pi)$ we deduce the octant (quotient of the first three digits by 125). We then multiply by 8 or -8 (the latter when the octant is odd), ignore any integer part (related to the octant), and convert the fractional part to an extended precision number, before multiplying by $\pi/4$ to convert back to a value in radians in $[0, \pi/4]$.

It is possible to prove that given the precision of floating points and their range of exponents, the 52 digits may start at most with 24 zeros. The 5 last digits are affected by carries from computations which are not done, hence we are left with at least $52 - 24 - 5 = 23$ significant digits, enough to round correctly up to $0.6 \cdot \text{ulp}$ in all cases.

`_fp_trig_inverse_two_pi:` This macro expands to `,,!` or `,!` followed by 10112 decimals of $10^{-16}/(2\pi)$. The number of decimals we really need is the maximum exponent plus the number of digits we later need, 52, plus 12 (4 – 1 groups of 4 digits). We store the decimals as a control sequence name, and convert it to a token list when required: strings take up less memory than their token list representation.

```

15742 \cs_new:Npx \_fp_trig_inverse_two_pi:
15743 {
15744   \exp_not:n { \exp_after:wN \use_none:n \token_to_str:N }
15745   \cs:w , , !
15746   0000000000000000159154943091895335768883763372514362034459645740 ~
15747   4564487476673440588967976342265350901138027662530859560728427267 ~
15748   5795803689291184611457865287796741073169983922923996693740907757 ~
15749   3077746396925307688717392896217397661693362390241723629011832380 ~
15750   1142226997557159404618900869026739561204894109369378440855287230 ~
15751   9994644340024867234773945961089832309678307490616698646280469944 ~
15752   8652187881574786566964241038995874139348609983868099199962442875 ~
15753   585171178858431117518767160546547536988009739460364759337680593 ~
15754   0249449663530532715677550322032477781639716602294674811959816584 ~
15755   0606016803035998133911987498832786654435279755070016240677564388 ~
15756   8495713108801221993761476813777647378906330680464579784817613124 ~
15757   2731406996077502450029775985708905690279678513152521001631774602 ~
15758   0924811606240561456203146484089248459191435211575407556200871526 ~
15759   6068022171591407574745827225977462853998751553293908139817724093 ~
15760   5825479707332871904069997590765770784934703935898280871734256403 ~
15761   6689511662545705943327631268650026122717971153211259950438667945 ~
15762   0376255608363171169525975812822494162333431451061235368785631136 ~
15763   3669216714206974696012925057833605311960859450983955671870995474 ~
15764   6510431623815517580839442979970999505254387566129445883306846050 ~
15765   7852915151410404892988506388160776196993073410389995786918905980 ~
15766   9373777206187543222718930136625526123878038753888110681406765434 ~
15767   0828278526933426799556070790386060352738996245125995749276297023 ~
15768   5940955843011648296411855777124057544494570217897697924094903272 ~
15769   9477021664960356531815354400384068987471769158876319096650696440 ~
15770   4776970687683656778104779795450353395758301881838687937766124814 ~
15771   9530599655802190835987510351271290432315804987196868777594656634 ~
15772   6221034204440855497850379273869429353661937782928735937843470323 ~

```

15773 0237145837923557118636341929460183182291964165008783079331353497 ~
15774 7909974586492902674506098936890945883050337030538054731232158094 ~
15775 3197676032283131418980974982243833517435698984750103950068388003 ~
15776 9786723599608024002739010874954854787923568261139948903268997427 ~
15777 0834961149208289037767847430355045684560836714793084567233270354 ~
15778 8539255620208683932409956221175331839402097079357077496549880868 ~
15779 6066360968661967037474542102831219251846224834991161149566556037 ~
15780 9696761399312829960776082779901007830360023382729879085402387615 ~
15781 5744543092601191005433799838904654921248295160707285300522721023 ~
15782 6017523313173179759311050328155109373913639645305792607180083617 ~
15783 9548767246459804739772924481092009371257869183328958862839904358 ~
15784 6866663975673445140950363732719174311388066383072592302759734506 ~
15785 0548212778037065337783032170987734966568490800326988506741791464 ~
15786 6835082816168533143361607309951498531198197337584442098416559541 ~
15787 5225064339431286444038388356150879771645017064706751877456059160 ~
15788 8716857857939226234756331711132998655941596890719850688744230057 ~
15789 5191977056900382183925622033874235362568083541565172971088117217 ~
15790 9593683256488518749974870855311659830610139214454460161488452770 ~
15791 2511411070248521739745103866736403872860099674893173561812071174 ~
15792 0478899368886556923078485023057057144063638632023685201074100574 ~
15793 8592281115721968003978247595300166958522123034641877365043546764 ~
15794 6456565971901123084767099309708591283646669191776938791433315566 ~
15795 5066981321641521008957117286238426070678451760111345080069947684 ~
15796 2235698962488051577598095339708085475059753626564903439445420581 ~
15797 7886435683042000315095594743439252544850674914290864751442303321 ~
15798 3324569511634945677539394240360905438335528292434220349484366151 ~
15799 4663228602477666660495314065734357553014090827988091478669343492 ~
15800 2737602634997829957018161964321233140475762897484082891174097478 ~
15801 2637899181699939487497715198981872666294601830539583275209236350 ~
15802 6853889228468247259972528300766856937583659722919824429747406163 ~
15803 8183113958306744348516928597383237392662402434501997809940402189 ~
15804 6134834273613676449913827154166063424829363741850612261086132119 ~
15805 9863346284709941839942742955915628333990480382117501161211667205 ~
15806 1912579303552929241134403116134112495318385926958490443846807849 ~
15807 0973982808855297045153053991400988698840883654836652224668624087 ~
15808 2540140400911787421220452307533473972538149403884190586842311594 ~
15809 6322744339066125162393106283195323883392131534556381511752035108 ~
15810 7459558201123754359768155340187407394340363397803881721004531691 ~
15811 8295194879591767395417787924352761740724605939160273228287946819 ~
15812 3649128949714953432552723591659298072479985806126900733218844526 ~
15813 7943350455801952492566306204876616134365339920287545208555344144 ~
15814 0990512982727454659118132223284051166615650709837557433729548631 ~
15815 2041121716380915606161165732000083306114606181280326258695951602 ~
15816 4632166138576614804719932707771316441201594960110632830520759583 ~
15817 4850305079095584982982186740289838551383239570208076397550429225 ~
15818 9847647071016426974384504309165864528360324933604354657237557916 ~
15819 1366324120457809969715663402215880545794313282780055246132088901 ~
15820 8742121092448910410052154968097113720754005710963406643135745439 ~
15821 9159769435788920793425617783022237011486424925239248728713132021 ~
15822 7667360756645598272609574156602343787436291321097485897150713073 ~
15823 9104072643541417970572226547980381512759579124002534468048220261 ~
15824 7342299001020483062463033796474678190501811830375153802879523433 ~
15825 4195502135689770912905614317878792086205744999257897569018492103 ~
15826 2420647138519113881475640209760554895793785141404145305151583964 ~

15827 2823265406020603311891586570272086250269916393751527887360608114 ~
15828 5569484210322407772727421651364234366992716340309405307480652685 ~
15829 0930165892136921414312937134106157153714062039784761842650297807 ~
15830 8606266969960809184223476335047746719017450451446166382846208240 ~
15831 8673595102371302904443779408535034454426334130626307459513830310 ~
15832 2293146934466832851766328241515210179422644395718121717021756492 ~
15833 1964449396532222187658488244511909401340504432139858628621083179 ~
15834 3939608443898019147873897723310286310131486955212620518278063494 ~
15835 5711866277825659883100535155231665984394090221806314454521212978 ~
15836 9734471488741258268223860236027109981191520568823472398358013366 ~
15837 0683786328867928619732367253606685216856320119489780733958419190 ~
15838 6659583867852941241871821727987506103946064819585745620060892122 ~
15839 8416394373846549589932028481236433466119707324309545859073361878 ~
15840 629063185016510626757685121635758869630745199922001077667830946 ~
15841 9814975622682434793671310841210219520899481912444048751171059184 ~
15842 4139907889455775184621619041530934543802808938628073237578615267 ~
15843 7971143323241969857805637630180884386640607175368321362629671224 ~
15844 2609428540110963218262765120117022552929289655594608204938409069 ~
15845 0760692003954646191640021567336017909631872891998634341086903200 ~
15846 5796637103128612356988817640364252540837098108148351903121318624 ~
15847 7228181050845123690190646632235938872454630737272808789830041018 ~
15848 9485913673742589418124056729191238003306344998219631580386381054 ~
15849 2457893450084553280313511884341007373060595654437362488771292628 ~
15850 9807423539074061786905784443105274262641767830058221486462289361 ~
15851 9296692992033046693328438158053564864073184440599549689353773183 ~
15852 6726613130108623588021288043289344562140479789454233736058506327 ~
15853 0439981932635916687341943656783901281912202816229500333012236091 ~
15854 8587559201959081224153679499095448881099758919890811581163538891 ~
15855 6339402923722049848375224236209100834097566791710084167957022331 ~
15856 7897107102928884897013099533995424415335060625843921452433864640 ~
15857 3432440657317477553405404481006177612569084746461432976543900008 ~
15858 3826521145210162366431119798731902751191441213616962045693602633 ~
15859 6102355962140467029012156796418735746835873172331004745963339773 ~
15860 2477044918885134415363760091537564267438450166221393719306748706 ~
15861 2881595464819775192207710236743289062690709117919412776212245117 ~
15862 2354677115640433357720616661564674474627305622913332030953340551 ~
15863 3841718194605321501426328000879551813296754972846701883657425342 ~
15864 5016994231069156343106626043412205213831587971115075454063290657 ~
15865 0248488648697402872037259869281149360627403842332874942332178578 ~
15866 7750735571857043787379693402336902911446961448649769719434527467 ~
15867 4429603089437192540526658890710662062575509930379976658367936112 ~
15868 8137451104971506153783743579555867972129358764463093757203221320 ~
15869 2460565661129971310275869112846043251843432691552928458573495971 ~
15870 5042565399302112184947232132380516549802909919676815118022483192 ~
15871 5127372199792134331067642187484426215985121676396779352982985195 ~
15872 8545392106957880586853123277545433229161989053189053725391582222 ~
15873 9232597278133427818256064882333760719681014481453198336237910767 ~
15874 1255017528826351836492103572587410356573894694875444694018175923 ~
15875 0609370828146501857425324969212764624247832210765473750568198834 ~
15876 5641035458027261252285503154325039591848918982630498759115406321 ~
15877 0354263890012837426155187877318375862355175378506956599570028011 ~
15878 5841258870150030170259167463020842412449128392380525772514737141 ~
15879 2310230172563968305553583262840383638157686828464330456805994018 ~
15880 7001071952092970177990583216417579868116586547147748964716547948 ~

```

15881      8312140431836079844314055731179349677763739898930227765607058530 ~
15882      4083747752640947435070395214524701683884070908706147194437225650 ~
15883      2823145872995869738316897126851939042297110721350756978037262545 ~
15884      8141095038270388987364516284820180468288205829135339013835649144 ~
15885      3004015706509887926715417450706686888783438055583501196745862340 ~
15886      8059532724727843829259395771584036885940989939255241688378793572 ~
15887      7967951654076673927031256418760962190243046993485989199060012977 ~
15888      7469214532970421677817261517850653008552559997940209969455431545 ~
15889      2745856704403686680428648404512881182309793496962721836492935516 ~
15890      2029872469583299481932978335803459023227052612542114437084359584 ~
15891      9443383638388317751841160881711251279233374577219339820819005406 ~
15892      3292937775306906607415304997682647124407768817248673421685881509 ~
15893      9133422075930947173855159340808957124410634720893194912880783576 ~
15894      3115829400549708918023366596077070927599010527028150868897828549 ~
15895      4340372642729262103487013992868853550062061514343078665396085995 ~
15896      0058714939141652065302070085265624074703660736605333805263766757 ~
15897      2018839497277047222153633851135483463624619855425993871933367482 ~
15898      0422097449956672702505446423243957506869591330193746919142980999 ~
15899      3424230550172665212092414559625960554427590951996824313084279693 ~
15900      7113207021049823238195747175985519501864630940297594363194450091 ~
15901      9150616049228764323192129703446093584259267276386814363309856853 ~
15902      2786024332141052330760658841495858718197071242995959226781172796 ~
15903      4438853796763139274314227953114500064922126500133268623021550837
15904      \cs_end:
15905      }

```

(End definition for _fp_trig_inverse_two_pi:.)

_fp_trig_large:ww The exponent #1 is between 1 and 10000. We discard the integer part of $10^{#1-16}/(2\pi)$, that is, the first #1 digits of $10^{-16}/(2\pi)$, because it yields an integer contribution to $x/(2\pi)$. The auxii auxiliary discards 64 digits at a time thanks to spaces inserted in the result of _fp_trig_inverse_two_pi:, while auxiii discards 8 digits at a time, and auxiv discards digits one at a time. Then 64 digits are packed into groups of 4 and the auxv auxiliary is called.

```

15906 \cs_new:Npn \_fp_trig_large:ww #1, #2#3#4#5#6;
15907 {
15908   \exp_after:wN \_fp_trig_large_auxi:wwwww
15909   \__int_value:w \__int_eval:w (#1 - 32) / 64 \exp_after:wN ,
15910   \__int_value:w \__int_eval:w (#1 - 4) / 8 \exp_after:wN ,
15911   \__int_value:w #1 \_fp_trig_inverse_two_pi: ;
15912   {#2}{#3}{#4}{#5} ;
15913 }
15914 \cs_new:Npn \_fp_trig_large_auxi:wwwww #1, #2, #3, #4!
15915 {
15916   \prg_replicate:nn {#1} { \_fp_trig_large_auxii:ww }
15917   \prg_replicate:nn { #2 - #1 * 8 }
15918   { \_fp_trig_large_auxiii:wNNNNNNNN }
15919   \prg_replicate:nn { #3 - #2 * 8 }
15920   { \_fp_trig_large_auxiv:wN }
15921   \prg_replicate:nn { 8 } { \_fp_pack_twice_four:wNNNNNNNN }
15922   \_fp_trig_large_auxv:www
15923   ;
15924 }
15925 \cs_new:Npn \_fp_trig_large_auxii:ww #1; #2 ~ { #1; }

```

```

15926 \cs_new:Npn \__fp_trig_large_auxiii:wNNNNNNNN
15927   #1; #2#3#4#5#6#7#8#9 { #1; }
15928 \cs_new:Npn \__fp_trig_large_auxiv:wN #1; #2 { #1; }

```

(End definition for __fp_trig_large:ww and others.)

```

\__fp_trig_large_auxv:www
\__fp_trig_large_auxvi:wNNNNNNNN
\__fp_trig_large_pack:NNNNNw

```

First come the first 64 digits of the fractional part of $10^{1-16}/(2\pi)$, arranged in 16 blocks of 4, and ending with a semicolon. Then some more digits of the same fractional part, ending with a semicolon, then 4 blocks of 4 digits holding the significand of the original argument. Multiply the 16-digit significand with the 64-digit fractional part: the `auxvi` auxiliary receives the significand as `#2#3#4#5` and 16 digits of the fractional part as `#6#7#8#9`, and computes one step of the usual ladder of `pack` functions we use for multiplication (see *e.g.*, `__fp_fixed_mul:wwn`), then discards one block of the fractional part to set things up for the next step of the ladder. We perform 13 such steps, replacing the last `middle` shift by the appropriate `trailing` shift, then discard the significand and remaining 3 blocks from the fractional part, as there are not enough digits to compute any more step in the ladder. The last semicolon closes the ladder, and we return control to the `auxvii` auxiliary.

```

15929 \cs_new:Npn \__fp_trig_large_auxv:www #1; #2; #3;
15930 {
15931   \exp_after:wN \__fp_use_i_until_s:nw
15932   \exp_after:wN \__fp_trig_large_auxvii:w
15933   \__int_value:w \__int_eval:w \c__fp_leading_shift_int
15934   \prg_replicate:nn { 13 }
15935   { \__fp_trig_large_auxvi:wNNNNNNNN }
15936   + \c__fp_trailing_shift_int - \c__fp_middle_shift_int
15937   \__fp_use_i_until_s:nw
15938   ; #3 #1 ; ;
15939 }
15940 \cs_new:Npn \__fp_trig_large_auxvi:wNNNNNNNN #1; #2#3#4#5#6#7#8#9
15941 {
15942   \exp_after:wN \__fp_trig_large_pack:NNNNNw
15943   \__int_value:w \__int_eval:w \c__fp_middle_shift_int
15944   + #2*#9 + #3*#8 + #4*#7 + #5*#6
15945   #1; {#2}{#3}{#4}{#5} {#7}{#8}{#9}
15946 }
15947 \cs_new:Npn \__fp_trig_large_pack:NNNNNw #1#2#3#4#5#6;
15948 { + #1#2#3#4#5 ; #6 }

```

(End definition for __fp_trig_large_auxv:www, __fp_trig_large_auxvi:wNNNNNNNN, and __fp_trig_large_pack:NNNNNw.)

```

\__fp_trig_large_auxvii:w
\__fp_trig_large_auxviii:w
\__fp_trig_large_auxix:Nw
\__fp_trig_large_auxx:wNNNNN
\__fp_trig_large_auxxi:w

```

The `auxvii` auxiliary is followed by 52 digits and a semicolon. We find the octant as the integer part of 8 times what follows, or equivalently as the integer part of `#1#2#3/125`, and add it to the surrounding integer expression for the octant. We then compute 8 times the 52-digit number, with a minus sign if the octant is odd. Again, the last `middle` shift is converted to a `trailing` shift. Any integer part (including negative values which come up when the octant is odd) is discarded by `__fp_use_i_until_s:nw`. The resulting fractional part should then be converted to radians by multiplying by $2\pi/8$, but first, build an extended precision number by abusing `__fp_ep_to_ep_loop:N` with the appropriate trailing markers. Finally, `__fp_trig_small:ww` sets up the argument for the functions which compute the Taylor series.

```

15949 \cs_new:Npn \__fp_trig_large_auxvii:w #1#2#3

```

```

15950 {
15951   \exp_after:wN \__fp_trig_large_auxviii:ww
15952   \__int_value:w \__int_eval:w (#1#2#3 - 62) / 125 ;
15953   #1#2#3
15954 }
15955 \cs_new:Npn \__fp_trig_large_auxviii:ww #1;
15956 {
15957   + #1
15958   \if_int_odd:w #1 \exp_stop_f:
15959     \exp_after:wN \__fp_trig_large_auxix:Nw
15960     \exp_after:wN -
15961   \else:
15962     \exp_after:wN \__fp_trig_large_auxix:Nw
15963     \exp_after:wN +
15964   \fi:
15965 }
15966 \cs_new:Npn \__fp_trig_large_auxix:Nw
15967 {
15968   \exp_after:wN \__fp_use_i_until_s:nw
15969   \exp_after:wN \__fp_trig_large_auxxi:w
15970   \__int_value:w \__int_eval:w \c__fp_leading_shift_int
15971   \prg_replicate:nn { 13 }
15972   { \__fp_trig_large_auxx:wNNNNN }
15973   + \c__fp_trailing_shift_int - \c__fp_middle_shift_int
15974   ;
15975 }
15976 \cs_new:Npn \__fp_trig_large_auxx:wNNNNN #1; #2 #3#4#5#6
15977 {
15978   \exp_after:wN \__fp_trig_large_pack:NNNNNw
15979   \__int_value:w \__int_eval:w \c__fp_middle_shift_int
15980   #2 8 * #3#4#5#6
15981   #1; #2
15982 }
15983 \cs_new:Npn \__fp_trig_large_auxxi:w #1;
15984 {
15985   \exp_after:wN \__fp_ep_mul_raw:wwwN
15986   \__int_value:w \__int_eval:w 0 \__fp_ep_to_ep_loop:N #1 ; ; !
15987   0,{7853}{9816}{3397}{4483}{0961}{5661};
15988   \__fp_trig_small:ww
15989 }

```

(End definition for __fp_trig_large_auxvii:w and others.)

29.1.6 Computing the power series

__fp_sin_series_o:NNwww Here we receive a conversion function __fp_ep_to_float_o:wwN or __fp_ep_inv_to_float_o:wwN, a *sign* (0 or 2), a (non-negative) *octant* delimited by a dot, a *fixed point* number delimited by a semicolon, and an extended-precision number. The auxiliary receives:

- the conversion function #1;
- the final sign, which depends on the octant #3 and the sign #2;
- the octant #3, which controls the series we use;

- the square `#4 * #4` of the argument as a fixed point number, computed with `__-fp_fixed_mul:wn`;
- the number itself as an extended-precision number.

If the octant is in $\{1, 2, 5, 6, \dots\}$, we are near an extremum of the function and we use the series

$$\cos(x) = 1 - x^2 \left(\frac{1}{2!} - x^2 \left(\frac{1}{4!} - x^2 \left(\dots \right) \right) \right).$$

Otherwise, the series

$$\sin(x) = x \left(1 - x^2 \left(\frac{1}{3!} - x^2 \left(\frac{1}{5!} - x^2 \left(\dots \right) \right) \right) \right)$$

is used. Finally, the extended-precision number is converted to a floating point number with the given sign, and `__fp_sanitizew` checks for overflow and underflow.

```

15990 \cs_new:Npn \__fp_sin_series_o:NNwww #1#2#3. #4;
15991 {
15992   \__fp_fixed_mul:wn #4; #4;
15993   {
15994     \exp_after:wN \__fp_sin_series_aux_o:NNwww
15995     \exp_after:wN #1
15996     \__int_value:w
15997     \if_int_odd:w \__int_eval:w (#3 + 2) / 4 \__int_eval_end:
15998       #2
15999     \else:
16000       \if_meaning:w #2 0 2 \else: 0 \fi:
16001       \fi:
16002     {#3}
16003   }
16004 }
16005 \cs_new:Npn \__fp_sin_series_aux_o:NNwww #1#2#3 #4; #5,#6;
16006 {
16007   \if_int_odd:w \__int_eval:w #3 / 2 \__int_eval_end:
16008     \exp_after:wN \use_i:nn
16009   \else:
16010     \exp_after:wN \use_ii:nn
16011   \fi:
16012   { % 1/18!
16013     \__fp_fixed_mul_sub_back:wwwn {0000}{0000}{0000}{0001}{5619}{2070};
16014     #4;{0000}{0000}{0000}{0477}{9477}{3324};
16015     \__fp_fixed_mul_sub_back:wwwn #4;{0000}{0000}{0011}{4707}{4559}{7730};
16016     \__fp_fixed_mul_sub_back:wwwn #4;{0000}{0000}{2087}{6756}{9878}{6810};
16017     \__fp_fixed_mul_sub_back:wwwn #4;{0000}{0027}{5573}{1922}{3985}{8907};
16018     \__fp_fixed_mul_sub_back:wwwn #4;{0000}{2480}{1587}{3015}{8730}{1587};
16019     \__fp_fixed_mul_sub_back:wwwn #4;{0013}{8888}{8888}{8888}{8888}{8889};
16020     \__fp_fixed_mul_sub_back:wwwn #4;{0416}{6666}{6666}{6666}{6666}{6667};
16021     \__fp_fixed_mul_sub_back:wwwn #4;{5000}{0000}{0000}{0000}{0000}{0000};
16022     \__fp_fixed_mul_sub_back:wwwn #4;{10000}{0000}{0000}{0000}{0000}{0000};
16023     { \__fp_fixed_continue:wn 0, }
16024   }
16025   { % 1/17!
16026     \__fp_fixed_mul_sub_back:wwwn {0000}{0000}{0000}{0028}{1145}{7254};
16027     #4;{0000}{0000}{0000}{7647}{1637}{3182};

```



```

16028     \__fp_fixed_mul_sub_back:wwwn #4;{0000}{0000}{0160}{5904}{3836}{8216};
16029     \__fp_fixed_mul_sub_back:wwwn #4;{0000}{0002}{5052}{1083}{8544}{1719};
16030     \__fp_fixed_mul_sub_back:wwwn #4;{0000}{0275}{5731}{9223}{9858}{9065};
16031     \__fp_fixed_mul_sub_back:wwwn #4;{0001}{9841}{2698}{4126}{9841}{2698};
16032     \__fp_fixed_mul_sub_back:wwwn #4;{0083}{3333}{3333}{3333}{3333}{3333};
16033     \__fp_fixed_mul_sub_back:wwwn #4;{1666}{6666}{6666}{6666}{6666}{6667};
16034     \__fp_fixed_mul_sub_back:wwwn#4;{10000}{0000}{0000}{0000}{0000}{0000};
16035     { \__fp_ep_mul:wwwn 0, } #5,#6;
16036 }
16037 {
16038     \exp_after:wN \__fp_sanitize:Nw
16039     \exp_after:wN #2
16040     \__int_value:w \__int_eval:w #1
16041 }
16042 #2
16043 }

```

(End definition for __fp_sin_series_o:NNwww and __fp_sin_series_aux_o:NNwww.)

__fp_tan_series_o:NNwww
__fp_tan_series_aux_o:Nnwww

Contrarily to __fp_sin_series_o:NNwww which received a conversion auxiliary as #1, here, #1 is 0 for tangent and 2 for cotangent. Consider first the case of the tangent. The octant #3 starts at 1, which means that it is 1 or 2 for $|x| \in [0, \pi/2]$, it is 3 or 4 for $|x| \in [\pi/2, \pi]$, and so on: the intervals on which $\tan|x| \geq 0$ coincide with those for which $\lfloor (\#3 + 1)/2 \rfloor$ is odd. We also have to take into account the original sign of x to get the sign of the final result; it is straightforward to check that the first __int_value:w expansion produces 0 for a positive final result, and 2 otherwise. A similar story holds for $\cot(x)$.

The auxiliary receives the sign, the octant, the square of the (reduced) input, and the (reduced) input (an extended-precision number) as arguments. It then computes the numerator and denominator of

$$\tan(x) \simeq \frac{x(1 - x^2(a_1 - x^2(a_2 - x^2(a_3 - x^2(a_4 - x^2 a_5))))))}{1 - x^2(b_1 - x^2(b_2 - x^2(b_3 - x^2(b_4 - x^2 b_5)))}.$$

The ratio is computed by __fp_ep_div:wwwn, then converted to a floating point number. For octants #3 (really, quadrants) next to a pole of the functions, the fixed point numerator and denominator are exchanged before computing the ratio. Note that this \if_int_odd:w test relies on the fact that the octant is at least 1.

```

16044 \cs_new:Npn \__fp_tan_series_o:NNwww #1#2#3. #4;
16045 {
16046     \__fp_fixed_mul:wwn #4; #4;
16047     {
16048         \exp_after:wN \__fp_tan_series_aux_o:Nnwww
16049         \__int_value:w
16050         \if_int_odd:w \__int_eval:w #3 / 2 \__int_eval_end:
16051         \exp_after:wN \reverse_if:N
16052         \fi:
16053         \if_meaning:w #1#2 2 \else: 0 \fi:
16054     }#3}
16055 }
16056 }
16057 \cs_new:Npn \__fp_tan_series_aux_o:Nnwww #1 #2 #3; #4,#5;
16058 {

```

```

16059  \__fp_fixed_mul_sub_back:wwwn    {0000}{0000}{1527}{3493}{0856}{7059};
16060                                     #3; {0000}{0159}{6080}{0274}{5257}{6472};
16061  \__fp_fixed_mul_sub_back:wwwn #3; {0002}{4571}{2320}{0157}{2558}{8481};
16062  \__fp_fixed_mul_sub_back:wwwn #3; {0115}{5830}{7533}{5397}{3168}{2147};
16063  \__fp_fixed_mul_sub_back:wwwn #3; {1929}{8245}{6140}{3508}{7719}{2982};
16064  \__fp_fixed_mul_sub_back:wwwn #3; {10000}{0000}{0000}{0000}{0000}{0000};
16065  { \__fp_ep_mul:wwwn 0, } #4,#5;
16066  {
16067      \__fp_fixed_mul_sub_back:wwwn    {0000}{0007}{0258}{0681}{9408}{4706};
16068                                          #3; {0000}{2343}{7175}{1399}{6151}{7670};
16069      \__fp_fixed_mul_sub_back:wwwn #3; {0019}{2638}{4588}{9232}{8861}{3691};
16070      \__fp_fixed_mul_sub_back:wwwn #3; {0536}{6357}{0691}{4344}{6852}{4252};
16071      \__fp_fixed_mul_sub_back:wwwn #3; {5263}{1578}{9473}{6842}{1052}{6315};
16072      \__fp_fixed_mul_sub_back:wwwn #3; {10000}{0000}{0000}{0000}{0000}{0000};
16073      {
16074          \reverse_if:N \if_int_odd:w
16075              \__int_eval:w (#2 - 1) / 2 \__int_eval_end:
16076              \exp_after:wN \__fp_reverse_args:Nww
16077              \fi:
16078              \__fp_ep_div:wwwn 0,
16079      }
16080      }
16081      {
16082          \exp_after:wN \__fp_sanitize:Nw
16083          \exp_after:wN #1
16084          \__int_value:w \__int_eval:w \__fp_ep_to_float_o:wwN
16085      }
16086      #1
16087  }

```

(End definition for `__fp_tan_series_o:NNwww` and `__fp_tan_series_aux_o:Nnwww`.)

29.2 Inverse trigonometric functions

All inverse trigonometric functions (arcsine, arccosine, arctangent, arccotangent, arcsecant, and arcsecant) are based on a function often denoted `atan2`. This function is accessed directly by feeding two arguments to arctangent, and is defined by $\text{atan}(y, x) = \text{atan}(y/x)$ for generic y and x . Its advantages over the conventional arctangent is that it takes values in $[-\pi, \pi]$ rather than $[-\pi/2, \pi/2]$, and that it is better behaved in boundary cases. Other inverse trigonometric functions are expressed in terms of `atan` as

$$\cos x = \text{atan}(\sqrt{1 - x^2}, x) \quad (5)$$

$$\sin x = \text{atan}(x, \sqrt{1 - x^2}) \quad (6)$$

$$\sec x = \text{atan}(\sqrt{x^2 - 1}, 1) \quad (7)$$

$$\csc x = \text{atan}(1, \sqrt{x^2 - 1}) \quad (8)$$

$$\tan x = \text{atan}(x, 1) \quad (9)$$

$$\cot x = \text{atan}(1, x). \quad (10)$$

Rather than introducing a new function, `atan2`, the arctangent function `atan` is overloaded: it can take one or two arguments. In the comments below, following many texts,

we call the first argument y and the second x , because $\text{atan}(y, x) = \text{atan}(y/x)$ is the angular coordinate of the point (x, y) .

As for direct trigonometric functions, the first step in computing $\text{atan}(y, x)$ is argument reduction. The sign of y gives that of the result. We distinguish eight regions where the point $(x, |y|)$ can lie, of angular size roughly $\pi/8$, characterized by their “octant”, between 0 and 7 included. In each region, we compute an arctangent as a Taylor series, then shift this arctangent by the appropriate multiple of $\pi/4$ and sign to get the result. Here is a list of octants, and how we compute the arctangent (we assume $y > 0$: otherwise replace y by $-y$ below):

0 $0 < |y| < 0.41421x$, then $\text{atan} \frac{|y|}{x}$ is given by a nicely convergent Taylor series;

1 $0 < 0.41421x < |y| < x$, then $\text{atan} \frac{|y|}{x} = \frac{\pi}{4} - \text{atan} \frac{x-|y|}{x+|y|}$;

2 $0 < 0.41421|y| < x < |y|$, then $\text{atan} \frac{|y|}{x} = \frac{\pi}{4} + \text{atan} \frac{-x+|y|}{x+|y|}$;

3 $0 < x < 0.41421|y|$, then $\text{atan} \frac{|y|}{x} = \frac{\pi}{2} - \text{atan} \frac{x}{|y|}$;

4 $0 < -x < 0.41421|y|$, then $\text{atan} \frac{|y|}{x} = \frac{\pi}{2} + \text{atan} \frac{-x}{|y|}$;

5 $0 < 0.41421|y| < -x < |y|$, then $\text{atan} \frac{|y|}{x} = \frac{3\pi}{4} - \text{atan} \frac{x+|y|}{-x+|y|}$;

6 $0 < -0.41421x < |y| < -x$, then $\text{atan} \frac{|y|}{x} = \frac{3\pi}{4} + \text{atan} \frac{-x-|y|}{-x+|y|}$;

7 $0 < |y| < -0.41421x$, then $\text{atan} \frac{|y|}{x} = \pi - \text{atan} \frac{|y|}{-x}$.

In the following, we denote by z the ratio among $|\frac{y}{x}|$, $|\frac{x}{y}|$, $|\frac{x+y}{x-y}|$, $|\frac{x-y}{x+y}|$ which appears in the right-hand side above.

29.2.1 Arctangent and arccotangent

`__fp_atan_o:Nw`

`__fp_acot_o:Nw`

`__fp_atan_dispatch_o:NNnNw`

The parsing step manipulates `atan` and `acot` like `min` and `max`, reading in an array of operands, but also leaves `\use_i:nn` or `\use_ii:nn` depending on whether the result should be given in radians or in degrees. Here, we dispatch according to the number of arguments. The one-argument versions of arctangent and arccotangent are special cases of the two-argument ones: $\text{atan}(y) = \text{atan}(y, 1) = \text{acot}(1, y)$ and $\text{acot}(x) = \text{atan}(1, x) = \text{acot}(x, 1)$.

```

16088 \cs_new:Npn \__fp_atan_o:Nw
16089 {
16090   \__fp_atan_dispatch_o:NNnNw
16091   \__fp_acotii_o:Nww \__fp_atanii_o:Nww { atan }
16092 }
16093 \cs_new:Npn \__fp_acot_o:Nw
16094 {
16095   \__fp_atan_dispatch_o:NNnNw
16096   \__fp_atanii_o:Nww \__fp_acotii_o:Nww { acot }
16097 }
16098 \cs_new:Npn \__fp_atan_dispatch_o:NNnNw #1#2#3#4#5@
16099 {
16100   \if_case:w
16101     \__int_eval:w \__fp_array_count:n {#5} - 1 \__int_eval_end:

```

```

16102         \exp_after:wN #1 \exp_after:wN #4 \c_one_fp #5
16103         \exp:w
16104     \or: #2 #4 #5 \exp:w
16105     \else:
16106         \__msg_kernel_expandable_error:nnnnn
16107         { kernel } { fp-num-args } { #3() } { 1 } { 2 }
16108         \exp_after:wN \c_nan_fp \exp:w
16109     \fi:
16110     \exp_after:wN \exp_end:
16111 }

```

(End definition for `__fp_atan_o:Nw`, `__fp_acot_o:Nw`, and `__fp_atan_dispatch_o:NNnNw`.)

`__fp_atanii_o:Nww` `__fp_acotii_o:Nww` If either operand is `nan`, we return it. If both are normal, we call `__fp_atan_normal_o:NNnNwNw`. If both are zero or both infinity, we call `__fp_atan_inf_o:NNNw` with argument 2, leading to a result among $\{\pm\pi/4, \pm3\pi/4\}$ (in degrees, $\{\pm45, \pm135\}$). Otherwise, one is much bigger than the other, and we call `__fp_atan_inf_o:NNNw` with either an argument of 4, leading to the values $\pm\pi/2$ (in degrees, ±90), or 0, leading to $\{\pm0, \pm\pi\}$ (in degrees, $\{\pm0, \pm180\}$). Since $\text{acot}(x, y) = \text{atan}(y, x)$, `__fp_acotii_o:ww` simply reverses its two arguments.

```

16112 \cs_new:Npn \__fp_atanii_o:Nww
16113     #1 \s_fp \__fp_chk:w #2#3#4; \s_fp \__fp_chk:w #5
16114 {
16115     \if_meaning:w 3 #2 \__fp_case_return_i_o:ww \fi:
16116     \if_meaning:w 3 #5 \__fp_case_return_ii_o:ww \fi:
16117     \if_case:w
16118         \if_meaning:w #2 #5
16119         \if_meaning:w 1 #2 10 \else: 0 \fi:
16120     \else:
16121         \if_int_compare:w #2 > #5 \exp_stop_f: 1 \else: 2 \fi:
16122     \fi:
16123     \exp_stop_f:
16124     \__fp_case_return:nw { \__fp_atan_inf_o:NNNw #1 #3 2 }
16125     \or: \__fp_case_return:nw { \__fp_atan_inf_o:NNNw #1 #3 4 }
16126     \or: \__fp_case_return:nw { \__fp_atan_inf_o:NNNw #1 #3 0 }
16127     \fi:
16128     \__fp_atan_normal_o:NNnNwNw #1
16129     \s_fp \__fp_chk:w #2#3#4;
16130     \s_fp \__fp_chk:w #5
16131 }
16132 \cs_new:Npn \__fp_acotii_o:Nww #1#2; #3;
16133 { \__fp_atanii_o:Nww #1#3; #2; }

```

(End definition for `__fp_atanii_o:Nww` and `__fp_acotii_o:Nww`.)

`__fp_atan_inf_o:NNNw` This auxiliary is called whenever one number is ±0 or $\pm\infty$ (and neither is `NaN`). Then the result only depends on the signs, and its value is a multiple of $\pi/4$. We use the same auxiliary as for normal numbers, `__fp_atan_combine_o:NwwwwwN`, with arguments the final sign `#2`; the octant `#3`; $\text{atan } z/z = 1$ as a fixed point number; $z = 0$ as a fixed point number; and $z = 0$ as an extended-precision number. Given the values we provide, $\text{atan } z$ is computed to be 0, and the result is $[#3/2] \cdot \pi/4$ if the sign `#5` of x is positive, and $[(7 - #3)/2] \cdot \pi/4$ for negative x , where the divisions are rounded up.

```

16134 \cs_new:Npn \__fp_atan_inf_o:NNNw #1#2#3 \s_fp \__fp_chk:w #4#5#6;

```

```

16135 {
16136   \exp_after:wN \__fp_atan_combine_o:NwwwwwN
16137   \exp_after:wN #2
16138   \__int_value:w \__int_eval:w
16139   \if_meaning:w 2 #5 7 - \fi: #3 \exp_after:wN ;
16140   \c__fp_one_fixed_t1
16141   {0000}{0000}{0000}{0000}{0000}{0000};
16142   0,{0000}{0000}{0000}{0000}{0000}{0000}; #1
16143 }

```

(End definition for __fp_atan_inf_o:NNw.)

__fp_atan_normal_o:NNwNnw

Here we simply reorder the floating point data into a pair of signed extended-precision numbers, that is, a sign, an exponent ending with a comma, and a six-block mantissa ending with a semi-colon. This extended precision is required by other inverse trigonometric functions, to compute things like $\text{atan}(x, \sqrt{1-x^2})$ without intermediate rounding errors.

```

16144 \cs_new_protected:Npn \__fp_atan_normal_o:NNwNnw
16145   #1 \s__fp \__fp_chk:w 1#2#3#4; \s__fp \__fp_chk:w 1#5#6#7;
16146   {
16147     \__fp_atan_test_o:NwwNwwN
16148     #2 #3, #4{0000}{0000};
16149     #5 #6, #7{0000}{0000}; #1
16150   }

```

(End definition for __fp_atan_normal_o:NNwNnw.)

__fp_atan_test_o:NwwNwwN

This receives: the sign #1 of y , its exponent #2, its 24 digits #3 in groups of 4, and similarly for x . We prepare to call __fp_atan_combine_o:NwwwwwN which expects the sign #1, the octant, the ratio $(\text{atan } z)/z = 1 - \dots$, and the value of z , both as a fixed point number and as an extended-precision floating point number with a mantissa in $[0.01, 1)$. For now, we place #1 as a first argument, and start an integer expression for the octant. The sign of x does not affect z , so we simply leave a contribution to the octant: $\langle \text{octant} \rangle \rightarrow 7 - \langle \text{octant} \rangle$ for negative x . Then we order $|y|$ and $|x|$ in a non-decreasing order: if $|y| > |x|$, insert 3- in the expression for the octant, and swap the two numbers. The finer test with 0.41421 is done by __fp_atan_div:wnwnw after the operands have been ordered.

```

16151 \cs_new:Npn \__fp_atan_test_o:NwwNwwN #1#2,#3; #4#5,#6;
16152 {
16153   \exp_after:wN \__fp_atan_combine_o:NwwwwwN
16154   \exp_after:wN #1
16155   \__int_value:w \__int_eval:w
16156   \if_meaning:w 2 #4
16157     7 - \__int_eval:w
16158   \fi:
16159   \if_int_compare:w
16160     \__fp_ep_compare:www #2,#3; #5,#6; > 0 \exp_stop_f:
16161     3 -
16162   \exp_after:wN \__fp_reverse_args:Nww
16163   \fi:
16164   \__fp_atan_div:wnwnw #2,#3; #5,#6;
16165 }

```

(End definition for __fp_atan_test_o:NwwNwwN.)

`__fp_atan_div:wnwnw`
`__fp_atan_near:wwn`
`__fp_atan_near_aux:wn`

This receives two positive numbers a and b (equal to $|x|$ and $|y|$ in some order), each as an exponent and 6 blocks of 4 digits, such that $0 < a < b$. If $0.41421b < a$, the two numbers are “near”, hence the point (y, x) that we started with is closer to the diagonals $\{|y| = |x|\}$ than to the axes $\{xy = 0\}$. In that case, the octant is 1 (possibly combined with the 7– and 3– inserted earlier) and we wish to compute $\text{atan} \frac{b-a}{a+b}$. Otherwise, the octant is 0 (again, combined with earlier terms) and we wish to compute $\text{atan} \frac{a}{b}$. In any case, call `__fp_atan_auxi:ww` followed by z , as a comma-delimited exponent and a fixed point number.

```

16166 \cs_new:Npn \__fp_atan_div:wnwnw #1,#2#3; #4,#5#6;
16167 {
16168   \if_int_compare:w
16169     \__int_eval:w 41421 * #5 < #2 000
16170     \if_case:w \__int_eval:w #4 - #1 \__int_eval_end: 00 \or: 0 \fi:
16171     \exp_stop_f:
16172     \exp_after:wN \__fp_atan_near:wwn
16173   \fi:
16174   0
16175   \__fp_ep_div:wwwn #1,{#2}#3; #4,{#5}#6;
16176   \__fp_atan_auxi:ww
16177 }
16178 \cs_new:Npn \__fp_atan_near:wwn
16179   0 \__fp_ep_div:wwwn #1,#2; #3,
16180 {
16181   1
16182   \__fp_ep_to_fixed:wn #1 - #3, #2;
16183   \__fp_atan_near_aux:wn
16184 }
16185 \cs_new:Npn \__fp_atan_near_aux:wn #1; #2;
16186 {
16187   \__fp_fixed_add:wn #1; #2;
16188   { \__fp_fixed_sub:wn #2; #1; { \__fp_ep_div:wwwn 0, } 0, }
16189 }

```

(End definition for `__fp_atan_div:wnwnw`, `__fp_atan_near:wwn`, and `__fp_atan_near_aux:wn`.)

`__fp_atan_auxi:ww`
`__fp_atan_auxii:w`

Convert z from a representation as an exponent and a fixed point number in $[0.01, 1)$ to a fixed point number only, then set up the call to `__fp_atan_Taylor_loop:www`, followed by the fixed point representation of z and the old representation.

```

16190 \cs_new:Npn \__fp_atan_auxi:ww #1,#2;
16191 { \__fp_ep_to_fixed:wn #1,#2; \__fp_atan_auxii:w #1,#2; }
16192 \cs_new:Npn \__fp_atan_auxii:w #1;
16193 {
16194   \__fp_fixed_mul:wn #1; #1;
16195   {
16196     \__fp_atan_Taylor_loop:www 39 ;
16197     {0000}{0000}{0000}{0000}{0000}{0000} ;
16198   }
16199   ! #1;
16200 }

```

(End definition for `__fp_atan_auxi:ww` and `__fp_atan_auxii:w`.)

`__fp_atan_Taylor_loop:www`
`__fp_atan_Taylor_break:w`

We compute the series of $(\text{atan } z)/z$. A typical intermediate stage has $\#1 = 2k - 1$, $\#2 = \frac{1}{2k+1} - z^2(\frac{1}{2k+3} - z^2(\dots - z^2\frac{1}{39}))$, and $\#3 = z^2$. To go to the next step $k \rightarrow k - 1$,

we compute $\frac{1}{2k-1}$, then subtract from it z^2 times #2. The loop stops when $k = 0$: then #2 is $(\operatorname{atan} z)/z$, and there is a need to clean up all the unnecessary data, end the integer expression computing the octant with a semicolon, and leave the result #2 afterwards.

```

16201 \cs_new:Npn \__fp_atan_Taylor_loop:www #1; #2; #3;
16202 {
16203   \if_int_compare:w #1 = -1 \exp_stop_f:
16204     \__fp_atan_Taylor_break:w
16205   \fi:
16206   \exp_after:wN \__fp_fixed_div_int:wwN \c__fp_one_fixed_tl #1;
16207   \__fp_rrot:www \__fp_fixed_mul_sub_back:wwwn #2; #3;
16208   {
16209     \exp_after:wN \__fp_atan_Taylor_loop:www
16210     \__int_value:w \__int_eval:w #1 - 2 ;
16211   }
16212   #3;
16213 }
16214 \cs_new:Npn \__fp_atan_Taylor_break:w
16215   \fi: #1 \__fp_fixed_mul_sub_back:wwwn #2; #3 !
16216   { \fi: ; #2 ; }

```

(End definition for `__fp_atan_Taylor_loop:www` and `__fp_atan_Taylor_break:w`.)

`__fp_atan_combine_o:NwwwwN` This receives a $\langle sign \rangle$, an $\langle octant \rangle$, a fixed point value of $(\operatorname{atan} z)/z$, a fixed point number z , and another representation of z , as an $\langle exponent \rangle$ and the fixed point number $10^{-\langle exponent \rangle} z$, followed by either `\use_i:nn` (when working in radians) or `\use_ii:nn` (when working in degrees). The function computes the floating point result

$$\langle sign \rangle \left(\left\lceil \frac{\langle octant \rangle}{2} \right\rceil \frac{\pi}{4} + (-1)^{\langle octant \rangle} \frac{\operatorname{atan} z}{z} \cdot z \right), \quad (11)$$

multiplied by $180/\pi$ if working in degrees, and using in any case the most appropriate representation of z . The floating point result is passed to `__fp_sanitize:Nw`, which checks for overflow or underflow. If the octant is 0, leave the exponent #5 for `__fp_sanitize:Nw`, and multiply #3 = $\frac{\operatorname{atan} z}{z}$ with #6, the adjusted z . Otherwise, multiply #3 = $\frac{\operatorname{atan} z}{z}$ with #4 = z , then compute the appropriate multiple of $\frac{\pi}{4}$ and add or subtract the product #3 · #4. In both cases, convert to a floating point with `__fp_fixed_to_float_o:wN`.

```

16217 \cs_new:Npn \__fp_atan_combine_o:NwwwwN #1 #2; #3; #4; #5,#6; #7
16218 {
16219   \exp_after:wN \__fp_sanitize:Nw
16220   \exp_after:wN #1
16221   \__int_value:w \__int_eval:w
16222   \if_meaning:w 0 #2
16223     \exp_after:wN \use_i:nn
16224   \else:
16225     \exp_after:wN \use_ii:nn
16226   \fi:
16227   { #5 \__fp_fixed_mul:wwn #3; #6; }
16228   {
16229     \__fp_fixed_mul:wwn #3; #4;
16230     {
16231       \exp_after:wN \__fp_atan_combine_aux:ww
16232       \__int_value:w \__int_eval:w #2 / 2 ; #2;

```

```

16233     }
16234   }
16235   { #7 \__fp_fixed_to_float_o:wN \__fp_fixed_to_float_rad_o:wN }
16236   #1
16237 }
16238 \cs_new:Npn \__fp_atan_combine_aux:ww #1; #2;
16239 {
16240   \__fp_fixed_mul_short:wwn
16241   {7853}{9816}{3397}{4483}{0961}{5661};
16242   {#1}{0000}{0000};
16243   {
16244     \if_int_odd:w #2 \exp_stop_f:
16245     \exp_after:wN \__fp_fixed_sub:wwn
16246     \else:
16247     \exp_after:wN \__fp_fixed_add:wwn
16248     \fi:
16249   }
16250 }

```

(End definition for __fp_atan_combine_o:NwwwwwN and __fp_atan_combine_aux:ww.)

29.2.2 Arcsine and arccosine

__fp_asin_o:w Again, the first argument provided by l3fp-parse is \use_i:nn if we are to work in radians and \use_ii:nn for degrees. Then comes a floating point number. The arcsine of ± 0 or NaN is the same floating point number. The arcsine of $\pm\infty$ raises an invalid operation exception. Otherwise, call an auxiliary common with __fp_acos_o:w, feeding it information about what function is being performed (for “invalid operation” exceptions).

```

16251 \cs_new:Npn \__fp_asin_o:w #1 \s__fp \__fp_chk:w #2#3; @
16252 {
16253   \if_case:w #2 \exp_stop_f:
16254   \__fp_case_return_same_o:w
16255   \or:
16256   \__fp_case_use:nw
16257   { \__fp_asin_normal_o:NfwNnnnnw #1 { #1 { asin } { asind } } }
16258   \or:
16259   \__fp_case_use:nw
16260   { \__fp_invalid_operation_o:fw { #1 { asin } { asind } } }
16261   \else:
16262   \__fp_case_return_same_o:w
16263   \fi:
16264   \s__fp \__fp_chk:w #2 #3;
16265 }

```

(End definition for __fp_asin_o:w.)

__fp_acos_o:w The arccosine of ± 0 is $\pi/2$ (in degrees, 90). The arccosine of $\pm\infty$ raises an invalid operation exception. The arccosine of NaN is itself. Otherwise, call an auxiliary common with __fp_sin_o:w, informing it that it was called by acos or acosd, and preparing to swap some arguments down the line.

```

16266 \cs_new:Npn \__fp_acos_o:w #1 \s__fp \__fp_chk:w #2#3; @
16267 {
16268   \if_case:w #2 \exp_stop_f:
16269   \__fp_case_use:nw { \__fp_atan_inf_o:NNNw #1 0 4 }

```



```

16270 \or:
16271 \__fp_case_use:nw
16272 {
16273 \__fp_asin_normal_o:NfwNnnnnw #1 { #1 { acos } { acosd } }
16274 \__fp_reverse_args:Nww
16275 }
16276 \or:
16277 \__fp_case_use:nw
16278 { \__fp_invalid_operation_o:fw { #1 { acos } { acosd } } }
16279 \else:
16280 \__fp_case_return_same_o:w
16281 \fi:
16282 \s__fp \__fp_chk:w #2 #3;
16283 }

```

(End definition for __fp_acos_o:w.)

__fp_asin_normal_o:NfwNnnnnw

If the exponent #5 is at most 0, the operand lies within $(-1, 1)$ and the operation is permitted: call __fp_asin_auxi_o:NnNww with the appropriate arguments. If the number is exactly ± 1 (the test works because we know that $\#5 \geq 1$, $\#6\#7 \geq 10000000$, $\#8\#9 \geq 0$, with equality only for ± 1), we also call __fp_asin_auxi_o:NnNww. Otherwise, __fp_use_i:ww gets rid of the asin auxiliary, and raises instead an invalid operation, because the operand is outside the domain of arcsine or arccosine.

```

16284 \cs_new:Npn \__fp_asin_normal_o:NfwNnnnnw
16285 #1#2#3 \s__fp \__fp_chk:w 1#4#5#6#7#8#9;
16286 {
16287 \if_int_compare:w #5 < 1 \exp_stop_f:
16288 \exp_after:wN \__fp_use_none_until_s:w
16289 \fi:
16290 \if_int_compare:w \__int_eval:w #5 + #6#7 + #8#9 = 1000 0001 ~
16291 \exp_after:wN \__fp_use_none_until_s:w
16292 \fi:
16293 \__fp_use_i:ww
16294 \__fp_invalid_operation_o:fw {#2}
16295 \s__fp \__fp_chk:w 1#4{#5}{#6}{#7}{#8}{#9};
16296 \__fp_asin_auxi_o:NnNww
16297 #1 {#3} #4 #5,{#6}{#7}{#8}{#9}{0000}{0000};
16298 }

```

(End definition for __fp_asin_normal_o:NfwNnnnnw.)

__fp_asin_auxi_o:NnNww
__fp_asin_isqrt:wn

We compute $x/\sqrt{1-x^2}$. This function is used by asin and acos, but also by acsc and asec after inverting the operand, thus it must manipulate extended-precision numbers. First evaluate $1-x^2$ as $(1+x)(1-x)$: this behaves better near $x = 1$. We do the addition/subtraction with fixed point numbers (they are not implemented for extended-precision floats), but go back to extended-precision floats to multiply and compute the inverse square root $1/\sqrt{1-x^2}$. Finally, multiply by the (positive) extended-precision float $|x|$, and feed the (signed) result, and the number +1, as arguments to the arctangent function. When computing the arccosine, the arguments $x/\sqrt{1-x^2}$ and +1 are swapped by #2 (__fp_reverse_args:Nww in that case) before __fp_atan_test_o:NwwNwwN is evaluated. Note that the arctangent function requires normalized arguments, hence the need for ep_to_ep and continue after ep_mul.

```

16299 \cs_new:Npn \__fp_asin_auxi_o:NnNww #1#2#3#4,#5;

```

```

16300 {
16301     \__fp_ep_to_fixed:wn #4,#5;
16302     \__fp_asin_isqrt:wn
16303     \__fp_ep_mul:www #4,#5;
16304     \__fp_ep_to_ep:wn
16305     \__fp_fixed_continue:wn
16306     { #2 \__fp_atan_test_o:NwNwN #3 }
16307     0 1,{1000}{0000}{0000}{0000}{0000}{0000}; #1
16308 }
16309 \cs_new:Npn \__fp_asin_isqrt:wn #1;
16310 {
16311     \exp_after:wN \__fp_fixed_sub:wn \c__fp_one_fixed_tl #1;
16312     {
16313         \__fp_fixed_add_one:wn #1;
16314         \__fp_fixed_continue:wn { \__fp_ep_mul:www 0, } 0,
16315     }
16316     \__fp_ep_isqrt:wn
16317 }

```

(End definition for __fp_asin_auxi_o:NnNw and __fp_asin_isqrt:wn.)

29.2.3 Arccosecant and arcsecant

__fp_acsc_o:w Cases are mostly labelled by #2, except when #2 is 2: then we use #3#2, which is 02 = 2 when the number is $+\infty$ and 22 when the number is $-\infty$. The arccosecant of ± 0 raises an invalid operation exception. The arccosecant of $\pm\infty$ is ± 0 with the same sign. The arcosecant of NaN is itself. Otherwise, __fp_acsc_normal_o:NfwNw does some more tests, keeping the function name (acsc or acscd) as an argument for invalid operation exceptions.

```

16318 \cs_new:Npn \__fp_acsc_o:w #1 \s__fp \__fp_chk:w #2#3#4; @
16319 {
16320     \if_case:w \if_meaning:w 2 #2 #3 \fi: #2 \exp_stop_f:
16321         \__fp_case_use:nw
16322         { \__fp_invalid_operation_o:fw { #1 { acsc } { acscd } } }
16323     \or: \__fp_case_use:nw
16324         { \__fp_acsc_normal_o:NfwNw #1 { #1 { acsc } { acscd } } }
16325     \or: \__fp_case_return_o:Nw \c_zero_fp
16326     \or: \__fp_case_return_same_o:w
16327     \else: \__fp_case_return_o:Nw \c_minus_zero_fp
16328     \fi:
16329     \s__fp \__fp_chk:w #2 #3 #4;
16330 }

```

(End definition for __fp_acsc_o:w.)

__fp_asec_o:w The arcsecant of ± 0 raises an invalid operation exception. The arcsecant of $\pm\infty$ is $\pi/2$ (in degrees, 90). The arccosecant of NaN is itself. Otherwise, do some more tests, keeping the function name asec (or asecd) as an argument for invalid operation exceptions, and a __fp_reverse_args:Nw following precisely that appearing in __fp_acos_o:w.

```

16331 \cs_new:Npn \__fp_asec_o:w #1 \s__fp \__fp_chk:w #2#3; @
16332 {
16333     \if_case:w #2 \exp_stop_f:
16334         \__fp_case_use:nw
16335         { \__fp_invalid_operation_o:fw { #1 { asec } { asecd } } }

```

```

16336 \or:
16337   \__fp_case_use:nw
16338   {
16339     \__fp_acsc_normal_o:NfwNnw #1 { #1 { asec } { asecd } }
16340     \__fp_reverse_args:Nww
16341   }
16342 \or: \__fp_case_use:nw { \__fp_atan_inf_o:NNNw #1 0 4 }
16343 \else: \__fp_case_return_same_o:w
16344 \fi:
16345 \s__fp \__fp_chk:w #2 #3;
16346 }

```

(End definition for __fp_asec_o:w.)

__fp_acsc_normal_o:NfwNnw If the exponent is non-positive, the operand is less than 1 in absolute value, which is always an invalid operation: complain. Otherwise, compute the inverse of the operand, and feed it to __fp_asin_auxi_o:NnNww (with all the appropriate arguments). This computes what we want thanks to $\operatorname{acsc}(x) = \operatorname{asin}(1/x)$ and $\operatorname{asec}(x) = \operatorname{acos}(1/x)$.

```

16347 \cs_new:Npn \__fp_acsc_normal_o:NfwNnw #1#2#3 \s__fp \__fp_chk:w 1#4#5#6;
16348 {
16349   \int_compare:nNnTF {#5} < 1
16350   {
16351     \__fp_invalid_operation_o:fw {#2}
16352     \s__fp \__fp_chk:w 1#4{#5}#6;
16353   }
16354   {
16355     \__fp_ep_div:wwwwn
16356     1,{1000}{0000}{0000}{0000}{0000};
16357     #5,#6{0000}{0000};
16358     { \__fp_asin_auxi_o:NnNww #1 {#3} #4 }
16359   }
16360 }

```

(End definition for __fp_acsc_normal_o:NfwNnw.)

16361 </initex | package>

30 13fp-convert implementation

16362 <*initex | package>

16363 <@@=fp>

30.1 Trimming trailing zeros

__fp_trim_zeros:w If #1 ends with a 0, the loop auxiliary takes that zero as an end-delimiter for its first argument, and the second argument is the same loop auxiliary. Once the last trailing zero is reached, the second argument is the dot auxiliary, which removes a trailing dot if any. We then clean-up with the end auxiliary, keeping only the number.

```

16364 \cs_new:Npn \__fp_trim_zeros:w #1 ;
16365 {
16366   \__fp_trim_zeros_loop:w #1
16367   ; \__fp_trim_zeros_loop:w 0; \__fp_trim_zeros_dot:w .; \s__stop
16368 }
16369 \cs_new:Npn \__fp_trim_zeros_loop:w #1 0; #2 { #2 #1 ; #2 }

```

```

16370 \cs_new:Npn \__fp_trim_zeros_dot:w #1 .; { \__fp_trim_zeros_end:w #1 ; }
16371 \cs_new:Npn \__fp_trim_zeros_end:w #1 ; #2 \s_stop { #1 }

```

(End definition for `__fp_trim_zeros:w` and others.)

30.2 Scientific notation

`\fp_to_scientific:N` The three public functions evaluate their argument, then pass it to `__fp_to_scientific_dispatch:w`.

```

\fp_to_scientific:c
\fp_to_scientific:n
16372 \cs_new:Npn \fp_to_scientific:N #1
16373 { \exp_after:wN \__fp_to_scientific_dispatch:w #1 }
16374 \cs_generate_variant:Nn \fp_to_scientific:N { c }
16375 \cs_new:Npn \fp_to_scientific:n
16376 {
16377   \exp_after:wN \__fp_to_scientific_dispatch:w
16378   \exp:w \exp_end_continue_f:w \__fp_parse:n
16379 }

```

(End definition for `\fp_to_scientific:N` and `\fp_to_scientific:n`. These functions are documented on page 186.)

```

\__fp_to_scientific_dispatch:w
\__fp_to_scientific_normal:wnnnnn
\__fp_to_scientific_normal:wNw

```

Expressing an internal floating point number in scientific notation is quite easy: no rounding, and the format is very well defined. First cater for the sign: negative numbers ($\#2 = 2$) start with `-`; we then only need to care about positive numbers and `nan`. Then filter the special cases: ± 0 are represented as `0`; infinities are converted to a number slightly larger than the largest after an “invalid_operation” exception; `nan` is represented as `0` after an “invalid_operation” exception. In the normal case, decrement the exponent and unbrace the 4 brace groups, then in a second step grab the first digit (previously hidden in braces) to order the various parts correctly.

```

16380 \cs_new:Npn \__fp_to_scientific_dispatch:w \s__fp \__fp_chk:w #1#2
16381 {
16382   \if_meaning:w 2 #2 \exp_after:wN - \exp:w \exp_end_continue_f:w \fi:
16383   \if_case:w #1 \exp_stop_f:
16384     \__fp_case_return:nw { 0.0000000000000000e0 }
16385   \or: \exp_after:wN \__fp_to_scientific_normal:wnnnnn
16386   \or:
16387     \__fp_case_use:nw
16388     {
16389       \__fp_invalid_operation:nnw
16390       { \fp_to_scientific:N \c__fp_overflowing_fp }
16391       { fp_to_scientific }
16392     }
16393   \or:
16394     \__fp_case_use:nw
16395     {
16396       \__fp_invalid_operation:nnw
16397       { \fp_to_scientific:N \c_zero_fp }
16398       { fp_to_scientific }
16399     }
16400   \fi:
16401   \s__fp \__fp_chk:w #1 #2
16402 }
16403 \cs_new:Npn \__fp_to_scientific_normal:wnnnnn
16404 \s__fp \__fp_chk:w 1 #1 #2 #3#4#5#6 ;

```

```

16405 {
16406     \exp_after:wN \_fp_to_scientific_normal:wNw
16407     \exp_after:wN e
16408     \_int_value:w \_int_eval:w #2 - 1
16409     ; #3 #4 #5 #6 ;
16410 }
16411 \cs_new:Npn \_fp_to_scientific_normal:wNw #1 ; #2#3;
16412 { #2.#3 #1 }

```

(End definition for `_fp_to_scientific_dispatch:w`, `_fp_to_scientific_normal:wnnnnn`, and `_fp_to_scientific_normal:wNw`.)

30.3 Decimal representation

`\fp_to_decimal:N` All three public variants are based on the same `_fp_to_decimal_dispatch:w` after evaluating their argument to an internal floating point.

```

\fp_to_decimal:c
\fp_to_decimal:n
16413 \cs_new:Npn \fp_to_decimal:N #1
16414 { \exp_after:wN \_fp_to_decimal_dispatch:w #1 }
16415 \cs_generate_variant:Nn \fp_to_decimal:N { c }
16416 \cs_new:Npn \fp_to_decimal:n
16417 {
16418     \exp_after:wN \_fp_to_decimal_dispatch:w
16419     \exp:w \exp_end_continue_f:w \_fp_parse:n
16420 }

```

(End definition for `\fp_to_decimal:N` and `\fp_to_decimal:n`. These functions are documented on page 185.)

```

\_fp_to_decimal_dispatch:w
    \_fp_to_decimal_normal:wnnnnn
\_fp_to_decimal_large:Nnw
\_fp_to_decimal_huge:wnnnn

```

The structure is similar to `_fp_to_scientific_dispatch:w`. Insert `-` for negative numbers. Zero gives 0, $\pm\infty$ and NaN yield an “invalid operation” exception; note that $\pm\infty$ produces a very large output, which we don’t expand now since it most likely won’t be needed. Normal numbers with an exponent in the range [1,15] have that number of digits before the decimal separator: “decimate” them, and remove leading zeros with `_int_value:w`, then trim trailing zeros and dot. Normal numbers with an exponent 16 or larger have no decimal separator, we only need to add trailing zeros. When the exponent is non-positive, the result should be 0.⟨zeros⟩⟨digits⟩, trimmed.

```

16421 \cs_new:Npn \_fp_to_decimal_dispatch:w \s_fp \_fp_chk:w #1#2
16422 {
16423     \if_meaning:w 2 #2 \exp_after:wN - \exp:w \exp_end_continue_f:w \fi:
16424     \if_case:w #1 \exp_stop_f:
16425         \_fp_case_return:nw { 0 }
16426     \or: \exp_after:wN \_fp_to_decimal_normal:wnnnnn
16427     \or:
16428         \_fp_case_use:nw
16429         {
16430             \_fp_invalid_operation:nnw
16431             { \fp_to_decimal:N \c_fp_overflowing_fp }
16432             { fp_to_decimal }
16433         }
16434     \or:
16435         \_fp_case_use:nw
16436         {
16437             \_fp_invalid_operation:nnw
16438             { 0 }

```

```

16439         { fp_to_decimal }
16440     }
16441     \fi:
16442     \s__fp \__fp_chk:w #1 #2
16443 }
16444 \cs_new:Npn \__fp_to_decimal_normal:wnnnnn
16445 \s__fp \__fp_chk:w 1 #1 #2 #3#4#5#6 ;
16446 {
16447     \int_compare:nNnTF {#2} > 0
16448     {
16449         \int_compare:nNnTF {#2} < \c__fp_prec_int
16450         {
16451             \__fp_decimate:nNnnnn { \c__fp_prec_int - #2 }
16452             \__fp_to_decimal_large:Nnw
16453         }
16454         {
16455             \exp_after:wN \exp_after:wN
16456             \exp_after:wN \__fp_to_decimal_huge:wnnnn
16457             \prg_replicate:nn { #2 - \c__fp_prec_int } { 0 } ;
16458         }
16459         {#3} {#4} {#5} {#6}
16460     }
16461     {
16462         \exp_after:wN \__fp_trim_zeros:w
16463         \exp_after:wN 0
16464         \exp_after:wN .
16465         \exp:w \exp_end_continue_f:w \prg_replicate:nn { - #2 } { 0 }
16466         #3#4#5#6 ;
16467     }
16468 }
16469 \cs_new:Npn \__fp_to_decimal_large:Nnw #1#2#3#4;
16470 {
16471     \exp_after:wN \__fp_trim_zeros:w \__int_value:w
16472     \if_int_compare:w #2 > 0 \exp_stop_f:
16473     #2
16474     \fi:
16475     \exp_stop_f:
16476     #3.#4 ;
16477 }
16478 \cs_new:Npn \__fp_to_decimal_huge:wnnnn #1; #2#3#4#5 { #2#3#4#5 #1 }

```

(End definition for `__fp_to_decimal_dispatch:w` and others.)

30.4 Token list representation

`\fp_to_tl:N` These three public functions evaluate their argument, then pass it to `__fp_to_tl_dispatch:w`.
`\fp_to_tl:c`
`\fp_to_tl:n`

```

16479 \cs_new:Npn \fp_to_tl:N #1 { \exp_after:wN \__fp_to_tl_dispatch:w #1 }
16480 \cs_generate_variant:Nn \fp_to_tl:N { c }
16481 \cs_new:Npn \fp_to_tl:n
16482 {
16483     \exp_after:wN \__fp_to_tl_dispatch:w
16484     \exp:w \exp_end_continue_f:w \__fp_parse:n
16485 }

```

(End definition for \fp_to_tl:N and \fp_to_tl:n. These functions are documented on page 186.)

__fp_to_tl_dispatch:w A structure similar to __fp_to_scientific_dispatch:w and __fp_to_decimal_dispatch:w, but without the “invalid operation” exception. First filter special cases.
__fp_to_tl_normal:nnnnn We express normal numbers in decimal notation if the exponent is in the range $[-2, 16]$,
__fp_to_tl_scientific:wnnnnn and otherwise use scientific notation.
__fp_to_tl_scientific:wNw

```

16486 \cs_new:Npn \__fp_to_tl_dispatch:w \s__fp \__fp_chk:w #1#2
16487 {
16488   \if_meaning:w 2 #2 \exp_after:wN - \exp:w \exp_end_continue_f:w \fi:
16489   \if_case:w #1 \exp_stop_f:
16490     \__fp_case_return:nw { 0 }
16491   \or: \exp_after:wN \__fp_to_tl_normal:nnnnn
16492   \or: \__fp_case_return:nw { inf }
16493   \else: \__fp_case_return:nw { nan }
16494   \fi:
16495 }
16496 \cs_new:Npn \__fp_to_tl_normal:nnnnn #1
16497 {
16498   \int_compare:nTF
16499     { -2 <= #1 <= \c__fp_prec_int }
16500     { \__fp_to_decimal_normal:wnnnnn }
16501     { \__fp_to_tl_scientific:wnnnnn }
16502   \s__fp \__fp_chk:w 1 0 {#1}
16503 }
16504 \cs_new:Npn \__fp_to_tl_scientific:wnnnnn
16505   \s__fp \__fp_chk:w 1 #1 #2 #3#4#5#6 ;
16506 {
16507   \exp_after:wN \__fp_to_tl_scientific:wNw
16508   \exp_after:wN e
16509   \__int_value:w \__int_eval:w #2 - 1
16510   ; #3 #4 #5 #6 ;
16511 }
16512 \cs_new:Npn \__fp_to_tl_scientific:wNw #1 ; #2#3;
16513 { \__fp_trim_zeros:w #2.#3 ; #1 }

```

(End definition for __fp_to_tl_dispatch:w and others.)

30.5 Formatting

This is not implemented yet, as it is not yet clear what a correct interface would be, for this kind of structured conversion from a floating point (or other types of variables) to a string. Ideas welcome.

30.6 Convert to dimension or integer

\fp_to_dim:N These three public functions rely on \fp_to_decimal:n internally.

```

\fp_to_dim:c 16514 \cs_new:Npn \fp_to_dim:N #1
\fp_to_dim:n 16515 { \fp_to_decimal:N #1 pt }
16516 \cs_generate_variant:Nn \fp_to_dim:N { c }
16517 \cs_new:Npn \fp_to_dim:n #1
16518 { \fp_to_decimal:n {#1} pt }

```

(End definition for \fp_to_dim:N and \fp_to_dim:n. These functions are documented on page 185.)

\fp_to_int:N These three public functions evaluate their argument, then pass it to **\fp_to_int_dispatch:w**.

\fp_to_int:c

```

16519 \cs_new:Npn \fp_to_int:N #1 { \exp_after:wN \__fp_to_int_dispatch:w #1 }
16520 \cs_generate_variant:Nn \fp_to_int:N { c }
16521 \cs_new:Npn \fp_to_int:n
16522 {
16523   \exp_after:wN \__fp_to_int_dispatch:w
16524   \exp:w \exp_end_continue_f:w \__fp_parse:n
16525 }
```

(End definition for **\fp_to_int:N** and **\fp_to_int:n**. These functions are documented on page 186.)

__fp_to_int_dispatch:w To convert to an integer, first round to 0 places (to the nearest integer), then express the result as a decimal number: the definition of **__fp_to_decimal_dispatch:w** is such that there are no trailing dot nor zero.

```

16526 \cs_new:Npn \__fp_to_int_dispatch:w #1;
16527 {
16528   \exp_after:wN \__fp_to_decimal_dispatch:w \exp:w \exp_end_continue_f:w
16529   \__fp_round:Nwn \__fp_round_to_nearest:NNN #1; { 0 }
16530 }
```

(End definition for **__fp_to_int_dispatch:w**.)

30.7 Convert from a dimension

\dim_to_fp:n The dimension expression (which can in fact be a glue expression) is evaluated, converted to a number (*i.e.*, expressed in scaled points), then multiplied by $2^{-16} = 0.0000152587890625$ to give a value expressed in points. The auxiliary **__fp_mul_npos_o:Nww** expects the desired *final sign* and two floating point operands (of the form **\s_fp ...**;) as arguments. This set of functions is also used to convert dimension registers to floating points while parsing expressions: in this context there is an additional exponent, which is the first argument of **__fp_from_dim_test:ww**, and is combined with the exponent -4 of 2^{-16} . There is also a need to expand afterwards: this is performed by **__fp_mul_npos_o:Nww**, and cancelled by **\prg_do_nothing:** here.

```

16531 \__debug_patch_args:nNNpn { { (#1) } }
16532 \cs_new:Npn \dim_to_fp:n #1
16533 {
16534   \exp_after:wN \__fp_from_dim_test:ww
16535   \exp_after:wN 0
16536   \exp_after:wN ,
16537   \__int_value:w \etex_glueexpr:D #1 ;
16538 }
16539 \cs_new:Npn \__fp_from_dim_test:ww #1, #2
16540 {
16541   \if_meaning:w 0 #2
16542     \__fp_case_return:nw { \exp_after:wN \c_zero_fp }
16543   \else:
16544     \exp_after:wN \__fp_from_dim:wNw
16545     \__int_value:w \__int_eval:w #1 - 4
16546     \if_meaning:w - #2
16547       \exp_after:wN , \exp_after:wN 2 \__int_value:w
16548     \else:
16549       \exp_after:wN , \exp_after:wN 0 \__int_value:w #2
```



```

16550         \fi:
16551     \fi:
16552 }
16553 \cs_new:Npn \__fp_from_dim:wNw #1,#2#3;
16554 {
16555     \__fp_pack_twice_four:wNNNNNNNN \__fp_from_dim:wNNnnnnnn ;
16556     #3 000 0000 00 {10}987654321; #2 {#1}
16557 }
16558 \cs_new:Npn \__fp_from_dim:wNNnnnnnn #1; #2#3#4#5#6#7#8#9
16559 { \__fp_from_dim:wnnnnwNn #1 {#2#300} {0000} ; }
16560 \cs_new:Npn \__fp_from_dim:wnnnnwNn #1; #2#3#4#5#6; #7#8
16561 {
16562     \__fp_mul_npos_o:Nww #7
16563     \s__fp \__fp_chk:w 1 #7 {#5} #1 ;
16564     \s__fp \__fp_chk:w 1 0 {#8} {1525} {8789} {0625} {0000} ;
16565     \prg_do_nothing:
16566 }

```

(End definition for `\dim_to_fp:n` and others. This function is documented on page 162.)

30.8 Use and eval

\fp_use:N Those public functions are simple copies of the decimal conversions.
\fp_use:c 16567 \cs_new_eq:NN \fp_use:N \fp_to_decimal:N
\fp_eval:n 16568 \cs_generate_variant:Nn \fp_use:N { c }
16569 \cs_new_eq:NN \fp_eval:n \fp_to_decimal:n

(End definition for `\fp_use:N` and `\fp_eval:n`. These functions are documented on page 186.)

\fp_abs:n Trivial but useful. See the implementation of `\fp_add:Nn` for an explanation of why to use `__fp_parse:n`, namely, for better error reporting.

```

16570 \cs_new:Npn \fp_abs:n #1
16571 { \fp_to_decimal:n { abs \__fp_parse:n {#1} } }

```

(End definition for `\fp_abs:n`. This function is documented on page 199.)

\fp_max:nn Similar to `\fp_abs:n`, for consistency with `\int_max:nn`, etc.
\fp_min:nn 16572 \cs_new:Npn \fp_max:nn #1#2
16573 { \fp_to_decimal:n { max (__fp_parse:n {#1} , __fp_parse:n {#2}) } }
16574 \cs_new:Npn \fp_min:nn #1#2
16575 { \fp_to_decimal:n { min (__fp_parse:n {#1} , __fp_parse:n {#2}) } }

(End definition for `\fp_max:nn` and `\fp_min:nn`. These functions are documented on page 199.)

30.9 Convert an array of floating points to a comma list

`__fp_array_to_clist:n` Converts an array of floating point numbers to a comma-list. If speed here ends up irrelevant, we can simplify the code for the auxiliary to become

```

\cs_new:Npn \__fp_array_to_clist_loop:Nw #1#2;
{
    \use_none:n #1
    { , ~ } \fp_to_tl:n { #1 #2 ; }
    \__fp_array_to_clist_loop:Nw
}

```

The `\use_ii:nn` function is expanded after `__fp_expand:n` is done, and it removes ,~ from the start of the representation.

```

16576 \cs_new:Npn \__fp_array_to_clist:n #1
16577 {
16578   \tl_if_empty:nF {#1}
16579   {
16580     \__fp_expand:n
16581     {
16582       { \use_ii:nn }
16583       \__fp_array_to_clist_loop:Nw #1 { ? \__prg_break: } ;
16584       \__prg_break_point:
16585     }
16586   }
16587 }
16588 \cs_new:Npx \__fp_array_to_clist_loop:Nw #1#2;
16589 {
16590   \exp_not:N \use_none:n #1
16591   \exp_not:N \exp_after:wN
16592   {
16593     \exp_not:N \exp_after:wN ,
16594     \exp_not:N \exp_after:wN \c_space_tl
16595     \exp_not:N \exp:w
16596     \exp_not:N \exp_end_continue_f:w
16597     \exp_not:N \__fp_to_tl_dispatch:w #1 #2 ;
16598   }
16599   \exp_not:N \__fp_array_to_clist_loop:Nw
16600 }

```

(End definition for `__fp_array_to_clist:n` and `__fp_array_to_clist_loop:Nw`.)

```

16601 </initex | package>

```

31 l3fp-random Implementation

```

16602 <*initex | package>

```

```

16603 <@@=fp>

```

`__fp_parse_word_rand:N` Those functions may receive a variable number of arguments. We won't use the argument ?.

```

16604 \cs_new:Npn \__fp_parse_word_rand:N
16605 { \__fp_parse_function:NNN \__fp_rand_o:Nw ? }
16606 \cs_new:Npn \__fp_parse_word_randint:N
16607 { \__fp_parse_function:NNN \__fp_randint_o:Nw ? }

```

(End definition for `__fp_parse_word_rand:N` and `__fp_parse_word_randint:N`.)

31.1 Engine support

At present, Xe_{La}TeX, p_{La}TeX and up_{La}TeX do not provide random numbers, while Lua_{La}TeX and pdf_{La}TeX provide the primitive `\pdfTeX_uniformdeviate:D` (`\pdfuniformdeviate` in pdf_{La}TeX and `\uniformdeviate` in Lua_{La}TeX). We write the test twice simply in order to write the `false` branch first.

```

16608 \cs_if_exist:NF \pdfTeX_uniformdeviate:D

```

```

16609 {
16610   \__msg_kernel_new:nnn { kernel } { fp-no-random }
16611   { Random-numbers-unavailable }
16612   \cs_new:Npn \__fp_rand_o:Nw ? #1 @
16613   {
16614     \__msg_kernel_expandable_error:nn { kernel } { fp-no-random }
16615     \exp_after:wN \c_nan_fp
16616   }
16617   \cs_new_eq:NN \__fp_randint_o:Nw \__fp_rand_o:Nw
16618 }
16619 \cs_if_exist:NT \pdfTEX_uniformdeviate:D
16620 {

```

`__fp_rand_uniform:` The `\pdfTEX_uniformdeviate:D` primitive gives a pseudo-random integer in a range $[0, n - 1]$ of the user's choice. This number is meant to be uniformly distributed, but is produced by rescaling a uniform pseudo-random integer in $[0, 2^{28} - 1]$. For instance, setting n to (any multiple of) 2^{29} gives only even values. Thus it is only safe to call `\pdfTEX_uniformdeviate:D` with argument 2^{28} . This integer is also used in the implementation of `\int_rand:nn`. We also use variants of this number rounded down to multiples of 10^4 and 10^8 .

```

16621 \cs_new:Npn \__fp_rand_uniform:
16622 { \pdfTEX_uniformdeviate:D \c__fp_rand_size_int }
16623 \int_const:Nn \c__fp_rand_size_int { 268 435 456 }
16624 \int_const:Nn \c__fp_rand_four_int { 268 430 000 }
16625 \int_const:Nn \c__fp_rand_eight_int { 200 000 000 }

```

(End definition for `__fp_rand_uniform:` and others.)

`__fp_rand_myriads:n` Used as `__fp_rand_myriads:n {XXX}` with one input character per block of four digit we want. Given a pseudo-random integer from the primitive, we extract 2 blocks of digits if possible, namely if the integer is less than 2×10^8 . If that's not possible, we try to extract 1 block, which succeeds in the range $[2 \times 10^8, 26843 \times 10^4)$. For the 5456 remaining possible values we just throw away the random integer and get a new one. Depending on whether we got 2, 1, or 0 blocks, remove the same number of characters from the input stream with `\use_i:nnn`, `\use_i:nn` or nothing.

```

16626 \cs_new:Npn \__fp_rand_myriads:n #1
16627 {
16628   \__fp_rand_myriads_loop:nn #1
16629   { ? \use_i_delimit_by_q_stop:nw \__fp_rand_myriads_last: }
16630   { ? \use_none_delimit_by_q_stop:w } \q_stop
16631 }
16632 \cs_new:Npn \__fp_rand_myriads_loop:nn #1#2
16633 {
16634   \use_none:n #2
16635   \exp_after:wN \__fp_rand_myriads_get:w
16636   \__int_value:w \__fp_rand_uniform: ; {#1}{#2}
16637 }
16638 \cs_new:Npn \__fp_rand_myriads_get:w #1 ;
16639 {
16640   \if_int_compare:w #1 < \c__fp_rand_eight_int
16641   \exp_after:wN \use_none:n
16642   \__int_value:w \__int_eval:w
16643   \c__fp_rand_eight_int + #1 \__int_eval_end:

```

```

16644     \exp_after:wN \use_i:nnn
16645 \else:
16646     \if_int_compare:w #1 < \c__fp_rand_four_int
16647     \exp_after:wN \use_none:nnnnn
16648     \__int_value:w \__int_eval:w
16649     \c__fp_rand_four_int + #1 \__int_eval_end:
16650     \exp_after:wN \exp_after:wN \exp_after:wN \use_i:nn
16651     \fi:
16652 \fi:
16653 \__fp_rand_myriads_loop:nn
16654 }
16655 \cs_new:Npn \__fp_rand_myriads_last:
16656 {
16657     \exp_after:wN \__fp_rand_myriads_last:w
16658     \__int_value:w \__fp_rand_uniform: ;
16659 }
16660 \cs_new:Npn \__fp_rand_myriads_last:w #1 ;
16661 {
16662     \if_int_compare:w #1 < \c__fp_rand_four_int
16663     \exp_after:wN \use_none:nnnnn
16664     \__int_value:w \__int_eval:w
16665     \c__fp_rand_four_int + #1 \__int_eval_end:
16666 \else:
16667     \exp_after:wN \__fp_rand_myriads_last:
16668 \fi:
16669 }

```

(End definition for `__fp_rand_myriads:n` and others.)

31.2 Random floating point

`__fp_rand_o:Nw` First we check that `random` was called without argument. Then get four blocks of four digits.

```

\__fp_rand_o:
\__fp_rand_o:w
16670 \cs_new:Npn \__fp_rand_o:Nw ? #1 @
16671 {
16672     \tl_if_empty:nTF {#1}
16673     { \__fp_rand_o: }
16674     {
16675         \_msg_kernel_expandable_error:nnnnn
16676         { kernel } { fp-num-args } { rand() } { 0 } { 0 }
16677         \exp_after:wN \c_nan_fp
16678     }
16679 }
16680 \cs_new:Npn \__fp_rand_o:
16681 { \__fp_parse_o:n { . \__fp_rand_myriads:n { xxxx } } }

```

(End definition for `__fp_rand_o:Nw`, `__fp_rand_o:`, and `__fp_rand_o:w`.)

31.3 Random integer

`__fp_randint_o:Nw` Enforce that there is one argument (then add first argument 1) or two arguments. Enforce that they are integers in $(-10^{16}, 10^{16})$ and ordered. We distinguish narrow ranges (less than 2^{28}) from wider ones.

```

\__fp_randint_badarg:w
\__fp_randint_e:w
\__fp_randint_e:wnn
\__fp_randint_e:wwNnn
\__fp_randint_e:wwwNnn
\__fp_randint_narrow_e:nnnn
\__fp_randint_wide_e:nnnn
\__fp_randint_wide_e:wnnn

```

For narrow ranges, compute the number n of possible outputs as an integer using `\fp_to_int:n`, and reduce a pseudo-random 28-bit integer r modulo n . On its own, this is not uniform when $[0, 2^{28} - 1]$ does not divide evenly into intervals of size n . The auxiliary `__fp_randint_e:wwwNnn` discards the pseudo-random integer if it lies in an incomplete interval, and repeats.

For wide ranges we use the same code except for the last eight digits which use `__fp_rand_myriads:n`. It is not safe to combine the first digits with the last eight as a single string of digits, as this may exceed 16 digits and be rounded. Instead, we first add the first few digits (times 10^8) to the lower bound. The result is compared to the upper bound and the process repeats if needed.

```

16682 \cs_new:Npn \__fp_randint_o:Nw ? #1 @
16683 {
16684   \if_case:w
16685     \__int_eval:w \__fp_array_count:n {#1} - 1 \__int_eval_end:
16686     \exp_after:wN \__fp_randint_e:w \c_one_fp #1
16687   \or: \__fp_randint_e:w #1
16688   \else:
16689     \__msg_kernel_expandable_error:nnnnn
16690     { kernel } { fp-num-args } { randint() } { 1 } { 2 }
16691     \exp_after:wN \c_nan_fp \exp:w
16692   \fi:
16693   \exp_after:wN \exp_end:
16694 }
16695 \cs_new:Npn \__fp_randint_badarg:w \s__fp \__fp_chk:w #1#2#3;
16696 {
16697   \__fp_int:wTF \s__fp \__fp_chk:w #1#2#3;
16698   {
16699     \if_meaning:w 1 #1
16700       \if_int_compare:w
16701         \use_i_delimit_by_q_stop:nw #3 \q_stop > \c__fp_prec_int
16702         1 \exp_stop_f:
16703       \fi:
16704     \fi:
16705   }
16706   { 1 \exp_stop_f: }
16707 }
16708 \cs_new:Npn \__fp_randint_e:w #1; #2;
16709 {
16710   \if_case:w
16711     \__fp_randint_badarg:w #1;
16712     \__fp_randint_badarg:w #2;
16713     \fp_compare:nNnTF { #1; } > { #2; } { 1 } { 0 } \exp_stop_f:
16714     \exp_after:wN \exp_after:wN \exp_after:wN \__fp_randint_e:wnn
16715     \__fp_parse:n { #2; - #1; } { #1; } { #2; }
16716   \or:
16717     \__fp_invalid_operation_tl_o:ff
16718     { randint } { \__fp_array_to_clist:n { #1; #2; } }
16719     \exp:w
16720   \fi:
16721 }
16722 \cs_new:Npn \__fp_randint_e:wnn #1;
16723 {
16724   \exp_after:wN \__fp_randint_e:wwwNnn

```

```

16725 \__int_value:w \__fp_rand_uniform: \exp_after:wN ;
16726 \exp:w \exp_end_continue_f:w
16727 \fp_compare:nNnTF { #1 ; } < \c__fp_rand_size_int
16728 { \fp_to_int:n { #1 ; + 1 } ; \__fp_randint_narrow_e:nnnn }
16729 { \fp_to_int:n { floor(#1 ; * 1e-8 + 1) } ; \__fp_randint_wide_e:nnnn }
16730 }
16731 \cs_new:Npn \__fp_randint_e:wwNnn #1 ; #2 ;
16732 {
16733 \exp_after:wN \__fp_randint_e:wwwNnn
16734 \__int_value:w \int_mod:nn {#1} {#2} ; #1 ; #2 ;
16735 }
16736 \cs_new:Npn \__fp_randint_e:wwwNnn #1 ; #2 ; #3 ; #4
16737 {
16738 \int_compare:nNnTF { #2 - #1 + #3 } > \c__fp_rand_size_int
16739 {
16740 \exp_after:wN \__fp_randint_e:wwNnn
16741 \__int_value:w \__fp_rand_uniform: ; #3 ; #4
16742 }
16743 { #4 {#1} {#3} }
16744 }
16745 \cs_new:Npn \__fp_randint_narrow_e:nnnn #1#2#3#4
16746 { \__fp_parse_o:n { #3 + #1 } \exp:w }
16747 \cs_new:Npn \__fp_randint_wide_e:nnnn #1#2#3#4
16748 {
16749 \exp_after:wN \exp_after:wN
16750 \exp_after:wN \__fp_randint_wide_e:wnnn
16751 \__fp_parse:n { #3 + #1e8 + \__fp_rand_myriads:n { xx } }
16752 {#2} {#3} {#4}
16753 }
16754 \cs_new:Npn \__fp_randint_wide_e:wnnn #1 ; #2#3#4
16755 {
16756 \fp_compare:nNnTF { #1 ; } > {#4}
16757 {
16758 \exp_after:wN \__fp_randint_e:wwNnn
16759 \__int_value:w \__fp_rand_uniform: ; #2 ;
16760 \__fp_randint_wide_e:nnnn {#3} {#4}
16761 }
16762 { \__fp_exp_after_o:w #1 ; \exp:w }
16763 }

```

(End definition for `__fp_randint_o:Nw` and others.)

End the initial conditional that ensures these commands are only defined in pdfTeX and LuaTeX.

```

16764 }
16765 </initex | package>

```

32 l3fp-assign implementation

```

16766 <*initex | package>
16767 <@@=fp>

```

32.1 Assigning values

\fp_new:N Floating point variables are initialized to be +0.

```
16768 \cs_new_protected:Npn \fp_new:N #1
16769 { \cs_new_eq:NN #1 \c_zero_fp }
16770 \cs_generate_variant:Nn \fp_new:N {c}
```

(End definition for \fp_new:N. This function is documented on page 184.)

\fp_set:Nn Simply use __fp_parse:n within various f-expanding assignments.

```
\fp_set:cn 16771 \cs_new_protected:Npn \fp_set:Nn #1#2
\fp_gset:Nn 16772 { \tl_set:Nx #1 { \exp_not:f { \__fp_parse:n {#2} } } }
\fp_gset:cn 16773 \cs_new_protected:Npn \fp_gset:Nn #1#2
\fp_const:Nn 16774 { \tl_gset:Nx #1 { \exp_not:f { \__fp_parse:n {#2} } } }
\fp_const:cn 16775 \cs_new_protected:Npn \fp_const:Nn #1#2
16776 { \tl_const:Nx #1 { \exp_not:f { \__fp_parse:n {#2} } } }
16777 \cs_generate_variant:Nn \fp_set:Nn {c}
16778 \cs_generate_variant:Nn \fp_gset:Nn {c}
16779 \cs_generate_variant:Nn \fp_const:Nn {c}
```

(End definition for \fp_set:Nn, \fp_gset:Nn, and \fp_const:Nn. These functions are documented on page 184.)

\fp_set_eq:NN Copying a floating point is the same as copying the underlying token list.

```
\fp_set_eq:cn 16780 \cs_new_eq:NN \fp_set_eq:NN \tl_set_eq:NN
\fp_set_eq:Nc 16781 \cs_new_eq:NN \fp_gset_eq:NN \tl_gset_eq:NN
\fp_set_eq:cc 16782 \cs_generate_variant:Nn \fp_set_eq:NN { c , Nc , cc }
\fp_gset_eq:NN 16783 \cs_generate_variant:Nn \fp_gset_eq:NN { c , Nc , cc }
```

(End definition for \fp_set_eq:NN and \fp_gset_eq:NN. These functions are documented on page 185.)

\fp_set_eq:cn Setting a floating point to zero: copy \c_zero_fp.

```
\fp_zero:c 16784 \cs_new_protected:Npn \fp_zero:N #1 { \fp_set_eq:NN #1 \c_zero_fp }
\fp_gzero:N 16785 \cs_new_protected:Npn \fp_gzero:N #1 { \fp_gset_eq:NN #1 \c_zero_fp }
\fp_gzero:c 16786 \cs_generate_variant:Nn \fp_zero:N { c }
16787 \cs_generate_variant:Nn \fp_gzero:N { c }
```

(End definition for \fp_zero:N and \fp_gzero:N. These functions are documented on page 184.)

\fp_zero_new:N Set the floating point to zero, or define it if needed.

```
\fp_zero_new:c 16788 \cs_new_protected:Npn \fp_zero_new:N #1
\fp_gzero_new:N 16789 { \fp_if_exist:NTF #1 { \fp_zero:N #1 } { \fp_new:N #1 } }
\fp_gzero_new:c 16790 \cs_new_protected:Npn \fp_gzero_new:N #1
16791 { \fp_if_exist:NTF #1 { \fp_gzero:N #1 } { \fp_new:N #1 } }
16792 \cs_generate_variant:Nn \fp_zero_new:N { c }
16793 \cs_generate_variant:Nn \fp_gzero_new:N { c }
```

(End definition for \fp_zero_new:N and \fp_gzero_new:N. These functions are documented on page 184.)

32.2 Updating values

These match the equivalent functions in `l3int` and `l3skip`.

`\fp_add:Nn` For the sake of error recovery we should not simply set `#1` to `#1 ± (#2)`: for instance, if `#2` is `0)+2`, the parsing error would be raised at the last closing parenthesis rather than at the closing parenthesis in the user argument. Thus we evaluate `#2` instead of just putting parentheses. As an optimization we use `__fp_parse:n` rather than `\fp_eval:n`, which would convert the result away from the internal representation and back.

`\fp_add:cn`

`\fp_gadd:Nn`

`\fp_gadd:cn`

`\fp_sub:Nn`

`\fp_sub:cn`

`\fp_gsub:Nn`

`\fp_gsub:cn`

`__fp_add:NNNn`

```

16794 \cs_new_protected:Npn \fp_add:Nn { \__fp_add:NNNn \fp_set:Nn + }
16795 \cs_new_protected:Npn \fp_gadd:Nn { \__fp_add:NNNn \fp_gset:Nn + }
16796 \cs_new_protected:Npn \fp_sub:Nn { \__fp_add:NNNn \fp_set:Nn - }
16797 \cs_new_protected:Npn \fp_gsub:Nn { \__fp_add:NNNn \fp_gset:Nn - }
16798 \cs_new_protected:Npn \__fp_add:NNNn #1#2#3#4
16799 { #1 #3 { #3 #2 \__fp_parse:n {#4} } }
16800 \cs_generate_variant:Nn \fp_add:Nn { c }
16801 \cs_generate_variant:Nn \fp_gadd:Nn { c }
16802 \cs_generate_variant:Nn \fp_sub:Nn { c }
16803 \cs_generate_variant:Nn \fp_gsub:Nn { c }

```

(End definition for `\fp_add:Nn` and others. These functions are documented on page 185.)

32.3 Showing values

`\fp_show:N` This shows the result of computing its argument by passing the right data to `\tl_show:n` or `\tl_log:n`.

`\fp_show:c`

`\fp_log:N`

`\fp_log:c`

`__fp_show:NN`

```

16804 \cs_new_protected:Npn \fp_show:N { \__fp_show:NN \tl_show:n }
16805 \cs_generate_variant:Nn \fp_show:N { c }
16806 \cs_new_protected:Npn \fp_log:N { \__fp_show:NN \tl_log:n }
16807 \cs_generate_variant:Nn \fp_log:N { c }
16808 \cs_new_protected:Npn \__fp_show:NN #1#2
16809 {
16810   \__kernel_check_defined:NT #2
16811   { \exp_args:Nx #1 { \token_to_str:N #2 = \fp_to_tl:N #2 } }
16812 }

```

(End definition for `\fp_show:N`, `\fp_log:N`, and `__fp_show:NN`. These functions are documented on page 191.)

`\fp_show:n` Use general tools.

`\fp_log:n`

```

16813 \cs_new_protected:Npn \fp_show:n
16814 { \msg_show_eval:Nn \fp_to_tl:n }
16815 \cs_new_protected:Npn \fp_log:n
16816 { \msg_log_eval:Nn \fp_to_tl:n }

```

(End definition for `\fp_show:n` and `\fp_log:n`. These functions are documented on page 191.)

32.4 Some useful constants and scratch variables

`\c_one_fp` Some constants.

`\c_e_fp`

```

16817 \fp_const:Nn \c_e_fp { 2.718 2818 2845 9045 }
16818 \fp_const:Nn \c_one_fp { 1 }

```

(End definition for `\c_one_fp` and `\c_e_fp`. These variables are documented on page 190.)

`\c_pi_fp` We simply round π to and $\pi/180$ to 16 significant digits.
`\c_one_degree_fp` 16819 `\fp_const:Nn \c_pi_fp { 3.141 5926 5358 9793 }`
16820 `\fp_const:Nn \c_one_degree_fp { 0.0 1745 3292 5199 4330 }`

(End definition for `\c_pi_fp` and `\c_one_degree_fp`. These variables are documented on page 190.)

`\l_tmpa_fp` Scratch variables are simply initialized there.
`\l_tmpb_fp` 16821 `\fp_new:N \l_tmpa_fp`
`\g_tmpa_fp` 16822 `\fp_new:N \l_tmpb_fp`
`\g_tmpb_fp` 16823 `\fp_new:N \g_tmpa_fp`
16824 `\fp_new:N \g_tmpb_fp`

(End definition for `\l_tmpa_fp` and others. These variables are documented on page 190.)

16825 `\</initex | package>`

33 l3sort implementation

16826 `*initex | package>`

16827 `\@@=sort>`

33.1 Variables

`\l__sort_length_int` The sequence has `\l__sort_length_int` items and is stored from `\l__sort_min_int`
`\l__sort_min_int` to `\l__sort_top_int - 1`. While reading the sequence in memory, we check that
`\l__sort_top_int` `\l__sort_top_int` remains at most `\l__sort_max_int`, precomputed by `__sort-`
`\l__sort_max_int` `compute_range:.` That bound is such that the merge sort only uses `\toks` registers
`\l__sort_true_max_int` less than `\l__sort_true_max_int`, namely those that have not been allocated for use in
other code: the user's comparison code could alter these.

16828 `\int_new:N \l__sort_length_int`
16829 `\int_new:N \l__sort_min_int`
16830 `\int_new:N \l__sort_top_int`
16831 `\int_new:N \l__sort_max_int`
16832 `\int_new:N \l__sort_true_max_int`

(End definition for `\l__sort_length_int` and others.)

`\l__sort_block_int` Merge sort is done in several passes. In each pass, blocks of size `\l__sort_block_int` are
merged in pairs. The block size starts at 1, and, for a length in the range $[2^k + 1, 2^{k+1}]$,
reaches 2^k in the last pass.

16833 `\int_new:N \l__sort_block_int`

(End definition for `\l__sort_block_int`.)

`\l__sort_begin_int` When merging two blocks, `\l__sort_begin_int` marks the lowest index in the two
`\l__sort_end_int` blocks, and `\l__sort_end_int` marks the highest index, plus 1.

16834 `\int_new:N \l__sort_begin_int`
16835 `\int_new:N \l__sort_end_int`

(End definition for `\l__sort_begin_int` and `\l__sort_end_int`.)

`\l__sort_A_int` When merging two blocks (whose end-points are `beg` and `end`), A starts from the high end of the low block, and decreases until reaching `beg`. The index B starts from the top of the range and marks the register in which a sorted item should be put. Finally, C points to the copy of the high block in the interval of registers starting at `\l__sort_length_int`, upwards. C starts from the upper limit of that range.

```
16836 \int_new:N \l__sort_A_int
16837 \int_new:N \l__sort_B_int
16838 \int_new:N \l__sort_C_int
```

(End definition for `\l__sort_A_int`, `\l__sort_B_int`, and `\l__sort_C_int`.)

33.2 Finding available `\toks` registers

`__sort_shrink_range:` After `__sort_compute_range:` (defined below) determines that `\toks` registers between `\l__sort_min_int` (included) and `\l__sort_true_max_int` (excluded) have not yet been assigned, `__sort_shrink_range:` computes `\l__sort_max_int` to reflect the need for a buffer when merging blocks in the merge sort. Given $2^n \leq A \leq 2^n + 2^{n-1}$ registers we can sort $\lfloor A/2 \rfloor + 2^{n-2}$ items while if we have $2^n + 2^{n-1} \leq A \leq 2^{n+1}$ registers we can sort $A - 2^{n-1}$ items. We first find out a power 2^n such that $2^n \leq A \leq 2^{n+1}$ by repeatedly halving `\l__sort_block_int`, starting at 2^{15} or 2^{14} namely half the total number of registers, then we use the formulas and set `\l__sort_max_int`.

```
16839 \cs_new_protected:Npn \__sort_shrink_range:
16840 {
16841   \int_set:Nn \l__sort_A_int
16842     { \l__sort_true_max_int - \l__sort_min_int + 1 }
16843   \int_set:Nn \l__sort_block_int { \c_max_register_int / 2 }
16844   \__sort_shrink_range_loop:
16845   \int_set:Nn \l__sort_max_int
16846     {
16847     \int_compare:nNnTF
16848       { \l__sort_block_int * 3 / 2 } > \l__sort_A_int
16849       {
16850         \l__sort_min_int
16851         + ( \l__sort_A_int - 1 ) / 2
16852         + \l__sort_block_int / 4
16853         - 1
16854       }
16855       { \l__sort_true_max_int - \l__sort_block_int / 2 }
16856     }
16857 }
16858 \cs_new_protected:Npn \__sort_shrink_range_loop:
16859 {
16860   \if_int_compare:w \l__sort_A_int < \l__sort_block_int
16861     \tex_divide:D \l__sort_block_int 2 \exp_stop_f:
16862     \exp_after:wN \__sort_shrink_range_loop:
16863   \fi:
16864 }
```

(End definition for `__sort_shrink_range:` and `__sort_shrink_range_loop:`.)

`__sort_compute_range:` First find out what `\toks` have not yet been assigned. There are many cases. In L^AT_EX 2_ε with no package, available `\toks` range from `\count15 + 1` to `\c_max_register_int` included (this was not altered despite the 2015 changes). When `\loctoks` is defined,

namely in plain (e)TeX, or when the package etex is loaded in L^AT_EX 2_ε, redefine _sort_compute_range: to use the range \count265 to \count275 - 1. The elocalloc package also defines \loctoks but uses yet another number for the upper bound, namely \e@alloc@top (minus one). We must check for \loctoks every time a sorting function is called, as etex or elocalloc could be loaded.

In ConT_EXt MkIV the range is from \c_syst_last_allocated_toks + 1 to \c_max_register_int, and in MkII it is from \lastallocatedtoks + 1 to \c_max_register_int. In all these cases, call _sort_shrink_range:. The L^AT_EX3 format mode is easiest: no \toks are ever allocated so available \toks range from 0 to \c_max_register_int and we precompute the result of _sort_shrink_range:.

```

16865 <*package>
16866 \cs_new_protected:Npn \_sort_compute_range:
16867 {
16868   \int_set:Nn \l__sort_min_int { \tex_count:D 15 + 1 }
16869   \int_set:Nn \l__sort_true_max_int { \c_max_register_int + 1 }
16870   \_sort_shrink_range:
16871   \if_meaning:w \loctoks \tex_undefined:D \else:
16872     \if_meaning:w \loctoks \scan_stop: \else:
16873       \_sort_redefine_compute_range:
16874       \_sort_compute_range:
16875     \fi:
16876   \fi:
16877 }
16878 \cs_new_protected:Npn \_sort_redefine_compute_range:
16879 {
16880   \cs_if_exist:cTF { ver@elocalloc.sty }
16881   {
16882     \cs_gset_protected:Npn \_sort_compute_range:
16883     {
16884       \int_set:Nn \l__sort_min_int { \tex_count:D 265 }
16885       \int_set_eq:NN \l__sort_true_max_int \e@alloc@top
16886       \_sort_shrink_range:
16887     }
16888   }
16889   {
16890     \cs_gset_protected:Npn \_sort_compute_range:
16891     {
16892       \int_set:Nn \l__sort_min_int { \tex_count:D 265 }
16893       \int_set:Nn \l__sort_true_max_int { \tex_count:D 275 }
16894       \_sort_shrink_range:
16895     }
16896   }
16897 }
16898 \cs_if_exist:NT \loctoks { \_sort_redefine_compute_range: }
16899 \tl_map_inline:nn { \lastallocatedtoks \c_syst_last_allocated_toks }
16900 {
16901   \cs_if_exist:NT #1
16902   {
16903     \cs_gset_protected:Npn \_sort_compute_range:
16904     {
16905       \int_set:Nn \l__sort_min_int { #1 + 1 }
16906       \int_set:Nn \l__sort_true_max_int { \c_max_register_int + 1 }
16907       \_sort_shrink_range:

```

```

16908     }
16909   }
16910 }
16911 </package>
16912 <*initex>
16913 \int_const:Nn \c__sort_max_length_int
16914 { ( \c_max_register_int + 1 ) * 3 / 4 }
16915 \cs_new_protected:Npn \__sort_compute_range:
16916 {
16917   \int_set:Nn \l__sort_min_int { 0 }
16918   \int_set:Nn \l__sort_true_max_int { \c_max_register_int + 1 }
16919   \int_set:Nn \l__sort_max_int { \c__sort_max_length_int }
16920 }
16921 </initex>

```

(End definition for `__sort_compute_range:`, `__sort_redefine_compute_range:`, and `\c__sort_max_length_int`.)

33.3 Protected user commands

`__sort_main:NNNnNn` Sorting happens in three steps. First store items in `\toks` registers ranging from `\l__sort_min_int` to `\l__sort_top_int - 1`, while checking that the list is not too long. If we reach the maximum length, all further items are entirely ignored after raising an error. Secondly, sort the array of `\toks` registers, using the user-defined sorting function, **#6**. Finally, unpack the `\toks` registers (now sorted) into a variable of the right type, by x-expanding the code in **#4**, specific to each type of list.

```

16922 \cs_new_protected:Npn \__sort_main:NNNnNn #1#2#3#4#5#6
16923 {
16924   \group_begin:
16925   <package> \__sort_disable_toksdef:
16926   \__sort_compute_range:
16927   \int_set_eq:NN \l__sort_top_int \l__sort_min_int
16928   #2 #5
16929   {
16930     \if_int_compare:w \l__sort_top_int = \l__sort_max_int
16931     \__sort_too_long_error:NNw #3 #5
16932     \fi:
16933     \tex_toks:D \l__sort_top_int {##1}
16934     \int_incr:N \l__sort_top_int
16935   }
16936   \int_set:Nn \l__sort_length_int
16937   { \l__sort_top_int - \l__sort_min_int }
16938   \cs_set:Npn \__sort_compare:nn ##1 ##2 { #6 }
16939   \int_set:Nn \l__sort_block_int { 1 }
16940   \__sort_level:
16941   \use:x
16942   {
16943     \group_end:
16944     #1 \exp_not:N #5 {#4}
16945   }
16946 }

```

(End definition for `__sort_main:NNNnNn`.)

\seq_sort:Nn The first argument to `__sort_main:NNNnNn` is the final assignment function used, either `\tl_set:Nn` or `\tl_gset:Nn` to control local versus global results. The second argument is what mapping function is used when storing items to `\toks` registers, and the third breaks away from the loop. The fourth is used to build back the correct kind of list from the contents of the `\toks` registers, including the leading `\s__seq`. Fifth and sixth arguments are the variable to sort, and the sorting method as inline code.

```

16947 \cs_new_protected:Npn \seq_sort:Nn
16948 {
16949   \__sort_main:NNNnNn \tl_set:Nn
16950   \seq_map_inline:Nn \seq_map_break:n
16951   { \s__seq \__sort_toks:NN \exp_not:N \__seq_item:n }
16952 }
16953 \cs_generate_variant:Nn \seq_sort:Nn { c }
16954 \cs_new_protected:Npn \seq_gsort:Nn
16955 {
16956   \__sort_main:NNNnNn \tl_gset:Nn
16957   \seq_map_inline:Nn \seq_map_break:n
16958   { \s__seq \__sort_toks:NN \exp_not:N \__seq_item:n }
16959 }
16960 \cs_generate_variant:Nn \seq_gsort:Nn { c }

```

(End definition for \seq_sort:Nn and \seq_gsort:Nn. These functions are documented on page 68.)

\tl_sort:Nn Again, use `\tl_set:Nn` or `\tl_gset:Nn` to control the scope of the assignment. Mapping through the token list is done with `\tl_map_inline:Nn`, and producing the token list is very similar to sequences, removing `__seq_item:n`.

\tl_gsort:Nn
\tl_sort:cn
\tl_gsort:cn

```

16961 \cs_new_protected:Npn \tl_sort:Nn
16962 {
16963   \__sort_main:NNNnNn \tl_set:Nn
16964   \tl_map_inline:Nn \tl_map_break:n
16965   { \__sort_toks:NN \prg_do_nothing: \prg_do_nothing: }
16966 }
16967 \cs_generate_variant:Nn \tl_sort:Nn { c }
16968 \cs_new_protected:Npn \tl_gsort:Nn
16969 {
16970   \__sort_main:NNNnNn \tl_gset:Nn
16971   \tl_map_inline:Nn \tl_map_break:n
16972   { \__sort_toks:NN \prg_do_nothing: \prg_do_nothing: }
16973 }
16974 \cs_generate_variant:Nn \tl_gsort:Nn { c }

```

(End definition for \tl_sort:Nn and \tl_gsort:Nn. These functions are documented on page 46.)

\clist_sort:Nn The case of empty comma-lists is a little bit special as usual, and filtered out: there is nothing to sort in that case. Otherwise, the input is done with `\clist_map_inline:Nn`, and the output requires some more elaborate processing than for sequences and token lists. The first comma must be removed. An item must be wrapped in an extra set of braces if it contains either the space or the comma characters. This is taken care of by `\clist_wrap_item:n`, but `__sort_toks:NN` would simply feed `\tex_the:D \tex_toks:D <number>` as an argument to that function; hence we need to expand this argument once to unpack the register.

```

16975 \cs_new_protected:Npn \clist_sort:Nn
16976 { \__sort_clist:NNn \tl_set:Nn }

```

```

16977 \cs_new_protected:Npn \clist_gsort:Nn
16978 { \__sort_clist:NNn \tl_gset:Nn }
16979 \cs_generate_variant:Nn \clist_sort:Nn { c }
16980 \cs_generate_variant:Nn \clist_gsort:Nn { c }
16981 \cs_new_protected:Npn \__sort_clist:NNn #1#2#3
16982 {
16983   \clist_if_empty:NF #2
16984   {
16985     \__sort_main:NNNnNn #1
16986     \clist_map_inline:Nn \clist_map_break:n
16987     {
16988       \exp_last_unbraced:Nf \use_none:n
16989       { \__sort_toks:NN \exp_args:No \__clist_wrap_item:n }
16990     }
16991     #2 {#3}
16992   }
16993 }

```

(End definition for `\clist_sort:Nn`, `\clist_gsort:Nn`, and `__sort_clist:NNn`. These functions are documented on page 108.)

`__sort_toks:NN` Unpack the various `\toks` registers, from `\l__sort_min_int` to `\l__sort_top_int - 1`.
`__sort_toks:NNw` The functions #1 and #2 allow us to treat the three data structures in a unified way:

- for sequences, they are `\exp_not:N __seq_item:n`, expanding to the `__seq_item:n` separator, as expected;
- for token lists, they expand to nothing;
- for comma lists, they expand to `\exp_args:No \clist_wrap_item:n`, taking care of unpacking the register before letting the undocumented internal `clist` function `\clist_wrap_item:n` do the work of putting a comma and possibly braces.

```

16994 \cs_new:Npn \__sort_toks:NN #1#2
16995 { \__sort_toks:NNw #1 #2 \l__sort_min_int ; }
16996 \cs_new:Npn \__sort_toks:NNw #1#2#3 ;
16997 {
16998   \if_int_compare:w #3 < \l__sort_top_int
16999   #1 #2 { \tex_the:D \tex_toks:D #3 }
17000   \exp_after:wN \__sort_toks:NNw \exp_after:wN #1 \exp_after:wN #2
17001   \__int_value:w \__int_eval:w #3 + 1 \exp_after:wN ;
17002   \fi:
17003 }

```

(End definition for `__sort_toks:NN` and `__sort_toks:NNw`.)

33.4 Merge sort

`__sort_level:` This function is called once blocks of size `\l__sort_block_int` (initially 1) are each sorted. If the whole list fits in one block, then we are done (this also takes care of the case of an empty list or a list with one item). Otherwise, go through pairs of blocks starting from 0, then double the block size, and repeat.

```

17004 \cs_new_protected:Npn \__sort_level:
17005 {
17006   \if_int_compare:w \l__sort_block_int < \l__sort_length_int

```

```

17007     \l__sort_end_int \l__sort_min_int
17008     \__sort_merge_blocks:
17009     \tex_advance:D \l__sort_block_int \l__sort_block_int
17010     \exp_after:wN \__sort_level:
17011     \fi:
17012 }

```

(End definition for __sort_level:.)

__sort_merge_blocks: This function is called to merge a pair of blocks, starting at the last value of \l__sort_end_int (end-point of the previous pair of blocks). If shifting by one block to the right we reach the end of the list, then this pass has ended: the end of the list is sorted already. Otherwise, store the result of that shift in *A*, which indexes the first block starting from the top end. Then locate the end-point (maximum) of the second block: shift *end* upwards by one more block, but keeping it \leq *top*. Copy this upper block of \toks registers in registers above *length*, indexed by *C*: this is covered by __sort_copy_block:. Once this is done we are ready to do the actual merger using __sort_merge_blocks_aux:, after shifting *A*, *B* and *C* so that they point to the largest index in their respective ranges rather than pointing just beyond those ranges. Of course, once that pair of blocks is merged, move on to the next pair.

```

17013 \cs_new_protected:Npn \__sort_merge_blocks:
17014 {
17015     \l__sort_begin_int \l__sort_end_int
17016     \tex_advance:D \l__sort_end_int \l__sort_block_int
17017     \if_int_compare:w \l__sort_end_int < \l__sort_top_int
17018         \l__sort_A_int \l__sort_end_int
17019         \tex_advance:D \l__sort_end_int \l__sort_block_int
17020         \if_int_compare:w \l__sort_end_int > \l__sort_top_int
17021             \l__sort_end_int \l__sort_top_int
17022         \fi:
17023         \l__sort_B_int \l__sort_A_int
17024         \l__sort_C_int \l__sort_top_int
17025         \__sort_copy_block:
17026         \int_decr:N \l__sort_A_int
17027         \int_decr:N \l__sort_B_int
17028         \int_decr:N \l__sort_C_int
17029         \exp_after:wN \__sort_merge_blocks_aux:
17030         \exp_after:wN \__sort_merge_blocks:
17031     \fi:
17032 }

```

(End definition for __sort_merge_blocks:.)

__sort_copy_block: We wish to store a copy of the “upper” block of \toks registers, ranging between the initial value of \l__sort_B_int (included) and \l__sort_end_int (excluded) into a new range starting at the initial value of \l__sort_C_int, namely \l__sort_top_int.

```

17033 \cs_new_protected:Npn \__sort_copy_block:
17034 {
17035     \tex_toks:D \l__sort_C_int \tex_toks:D \l__sort_B_int
17036     \int_incr:N \l__sort_C_int
17037     \int_incr:N \l__sort_B_int
17038     \if_int_compare:w \l__sort_B_int = \l__sort_end_int
17039         \use_i:nn

```

```

17040 \fi:
17041 \__sort_copy_block:
17042 }

```

(End definition for __sort_copy_block:.)

__sort_merge_blocks_aux: At this stage, the first block starts at \l__sort_begin_int, and ends at \l__sort_A_int, and the second block starts at \l__sort_top_int and ends at \l__sort_C_int. The result of the merger is stored at positions indexed by \l__sort_B_int, which starts at \l__sort_end_int - 1 and decreases down to \l__sort_begin_int, covering the full range of the two blocks. In other words, we are building the merger starting with the largest values. The comparison function is defined to return either **swapped** or **same**. Of course, this means the arguments need to be given in the order they appear originally in the list.

```

17043 \cs_new_protected:Npn \__sort_merge_blocks_aux:
17044 {
17045   \exp_after:wN \__sort_compare:nn \exp_after:wN
17046   { \tex_the:D \tex_toks:D \exp_after:wN \l__sort_A_int \exp_after:wN }
17047   \exp_after:wN { \tex_the:D \tex_toks:D \l__sort_C_int }
17048   \prg_do_nothing:
17049   \__sort_return_mark:N
17050   \__sort_return_mark:N
17051   \__sort_return_none_error:
17052 }

```

(End definition for __sort_merge_blocks_aux:.)

```

\sort_return_same: The marker removes one token. Each comparison should call \sort_return_same: or
\sort_return_swapped: \sort_return_swapped: exactly once. If neither is called, \__sort_return_none_
\__sort_return_mark:N error: is called.
\__sort_return_none_error:
\__sort_return_two_error:w
17053 \cs_new_protected:Npn \sort_return_same: #1 \__sort_return_mark:N
17054 { #1 \__sort_return_mark:N \__sort_return_two_error:w \__sort_return_same: }
17055 \cs_new_protected:Npn \sort_return_swapped: #1 \__sort_return_mark:N
17056 { #1 \__sort_return_mark:N \__sort_return_two_error:w \__sort_return_swapped: }
17057 \cs_new_protected:Npn \__sort_return_mark:N #1 { }
17058 \cs_new_protected:Npn \__sort_return_none_error:
17059 {
17060   \__msg_kernel_error:nnxx { kernel } { return-none }
17061   { \tex_the:D \tex_toks:D \l__sort_A_int }
17062   { \tex_the:D \tex_toks:D \l__sort_C_int }
17063   \__sort_return_same:
17064 }
17065 \cs_new_protected:Npn \__sort_return_two_error:w
17066 #1 \__sort_return_none_error:
17067 { \__msg_kernel_error:nn { kernel } { return-two } }

```

(End definition for \sort_return_same: and others. These functions are documented on page ??.)

__sort_return_same: If the comparison function returns **same**, then the second argument fed to __sort_compare:nn should remain to the right of the other one. Since we build the merger starting from the right, we copy that \toks register into the allotted range, then shift the pointers *B* and *C*, and go on to do one more step in the merger, unless the second block has been exhausted: then the remainder of the first block is already in the correct registers and we are done with merging those two blocks.


```

17068 \cs_new_protected:Npn \__sort_return_same:
17069 {
17070   \tex_toks:D \l__sort_B_int \tex_toks:D \l__sort_C_int
17071   \int_decr:N \l__sort_B_int
17072   \int_decr:N \l__sort_C_int
17073   \if_int_compare:w \l__sort_C_int < \l__sort_top_int
17074     \use_i:nn
17075   \fi:
17076   \__sort_merge_blocks_aux:
17077 }

```

(End definition for __sort_return_same:.)

__sort_return_swapped: If the comparison function returns **swapped**, then the next item to add to the merger is the first argument, contents of the `\toks` register *A*. Then shift the pointers *A* and *B* to the left, and go for one more step for the merger, unless the left block was exhausted (*A* goes below the threshold). In that case, all remaining `\toks` registers in the second block, indexed by *C*, are copied to the merger by `__sort_merge_blocks_end:`.

```

17078 \cs_new_protected:Npn \__sort_return_swapped:
17079 {
17080   \tex_toks:D \l__sort_B_int \tex_toks:D \l__sort_A_int
17081   \int_decr:N \l__sort_B_int
17082   \int_decr:N \l__sort_A_int
17083   \if_int_compare:w \l__sort_A_int < \l__sort_begin_int
17084     \__sort_merge_blocks_end: \use_i:nn
17085   \fi:
17086   \__sort_merge_blocks_aux:
17087 }

```

(End definition for __sort_return_swapped:.)

__sort_merge_blocks_end: This function's task is to copy the `\toks` registers in the block indexed by *C* to the merger indexed by *B*. The end can equally be detected by checking when *B* reaches the threshold **begin**, or when *C* reaches **top**.

```

17088 \cs_new_protected:Npn \__sort_merge_blocks_end:
17089 {
17090   \tex_toks:D \l__sort_B_int \tex_toks:D \l__sort_C_int
17091   \int_decr:N \l__sort_B_int
17092   \int_decr:N \l__sort_C_int
17093   \if_int_compare:w \l__sort_B_int < \l__sort_begin_int
17094     \use_i:nn
17095   \fi:
17096   \__sort_merge_blocks_end:
17097 }

```

(End definition for __sort_merge_blocks_end:.)

33.5 Expandable sorting

Sorting expandably is very different from sorting and assigning to a variable. Since tokens cannot be stored, they must remain in the input stream, and be read through at every step. It is thus necessarily much slower (at best $O(n^2 \ln n)$) than non-expandable sorting functions ($O(n \ln n)$).

A prototypical version of expandable quicksort is as follows. If the argument has no item, return nothing, otherwise partition, using the first item as a pivot (argument #4 of `__sort:nnNnn`). The arguments of `__sort:nnNnn` are 1. items less than #4, 2. items greater or equal to #4, 3. comparison, 4. pivot, 5. next item to test. If #5 is the tail of the list, call `\tl_sort:nN` on #1 and on #2, placing #4 in between; `\use:ff` expands the parts to make `\tl_sort:nN` f-expandable. Otherwise, compare #4 and #5 using #3. If they are ordered, place #5 amongst the “greater” items, otherwise amongst the “lesser” items, and continue partitioning.

```
\cs_new:Npn \tl_sort:nN #1#2
{
  \tl_if_blank:nF {#1}
  {
    \__sort:nnNnn { } { } #2
    #1 \q_recursion_tail \q_recursion_stop
  }
}
\cs_new:Npn \__sort:nnNnn #1#2#3#4#5
{
  \quark_if_recursion_tail_stop_do:nn {#5}
  { \use:ff { \tl_sort:nN {#1} #3 {#4} } { \tl_sort:nN {#2} #3 } }
  #3 {#4} {#5}
  { \__sort:nnNnn {#1} { #2 {#5} } #3 {#4} }
  { \__sort:nnNnn { #1 {#5} } {#2} #3 {#4} }
}
\cs_generate_variant:Nn \use:nn { ff }
```

There are quite a few optimizations available here: the code below is less legible, but more than twice as fast.

In the simple version of the code, `__sort:nnNnn` is called $O(n \ln n)$ times on average (the number of comparisons required by the quicksort algorithm). Hence most of our focus is on optimizing that function.

The first speed up is to avoid testing for the end of the list at every call to `__sort:nnNnn`. For this, the list is prepared by changing each $\langle item \rangle$ of the original token list into $\langle command \rangle \{ \langle item \rangle \}$, just like sequences are stored. We arrange things such that the $\langle command \rangle$ is the $\langle conditional \rangle$ provided by the user: the loop over the $\langle prepared tokens \rangle$ then looks like

```
\cs_new:Npn \__sort_loop:wNn ... #6#7
{
  #6 { \langle pivot \rangle } {#7} \langle loop big \rangle \langle loop small \rangle
  \langle extra arguments \rangle
}
\__sort_loop:wNn ... \langle prepared tokens \rangle
\langle end-loop \rangle {} \q_stop
```

In this example, which matches the structure of `__sort_quick_split_i:NnnnnNn` and a few other functions below, the `__sort_loop:wNn` auxiliary normally receives the user’s $\langle conditional \rangle$ as #6 and an $\langle item \rangle$ as #7. This is compared to the $\langle pivot \rangle$ (the argument #5, not shown here), and the $\langle conditional \rangle$ leaves the $\langle loop big \rangle$ or $\langle loop small \rangle$ auxiliary, which both have the same form as `__sort_loop:wNn`, receiving the next pair

$\langle conditional \rangle \{ \langle item \rangle \}$ as #6 and #7. At the end, #6 is the $\langle end-loop \rangle$ function, which terminates the loop.

The second speed up is to minimize the duplicated tokens between the `true` and `false` branches of the conditional. For this, we introduce two versions of `__sort:nnNnn`, which receive the new item as #1 and place it either into the list #2 of items less than the pivot #4 or into the list #3 of items greater or equal to the pivot.

```
\cs_new:Npn \__sort_i:nnnnNn #1#2#3#4#5#6
{
  #5 {#4} {#6} \__sort_ii:nnnnNn \__sort_i:nnnnNn
  {#6} { #2 {#1} } {#3} {#4}
}
\cs_new:Npn \__sort_ii:nnnnNn #1#2#3#4#5#6
{
  #5 {#4} {#6} \__sort_ii:nnnnNn \__sort_i:nnnnNn
  {#6} {#2} { #3 {#1} } {#4}
}
```

Note that the two functions have the form of `__sort_loop:wNn` above, receiving as #5 the conditional or a function to end the loop. In fact, the lists #2 and #3 must be made of pairs $\langle conditional \rangle \{ \langle item \rangle \}$, so we have to replace {#6} above by { #5 {#6} }, and {#1} by #1. The actual functions have one more argument, so all argument numbers are shifted compared to this code.

The third speed up is to avoid `\use:ff` using a continuation-passing style: `__sort_quick_split:NnNn` expects a list followed by `\q_mark { \code }`, and expands to $\langle code \rangle \langle sorted list \rangle$. Sorting the two parts of the list around the pivot is done with

```
\__sort_quick_split:NnNn #2 ... \q_mark
{
  \__sort_quick_split:NnNn #1 ... \q_mark { \code }
  { \pivot }
}
```

Items which are larger than the $\langle pivot \rangle$ are sorted, then placed after code that sorts the smaller items, and after the (braced) $\langle pivot \rangle$.

The fourth speed up is avoid the recursive call to `\tl_sort:nN` with an empty first argument. For this, we introduce functions similar to the `__sort_i:nnnnNn` of the last example, but aware of whether the list of $\langle conditional \rangle \{ \langle item \rangle \}$ read so far that are less than the pivot, and the list of those greater or equal, are empty or not: see `__sort_quick_split:NnNn` and functions defined below. Knowing whether the lists are empty or not is useless if we do not use distinct ending codes as appropriate. The splitting auxiliaries communicate to the $\langle end-loop \rangle$ function (that is initially placed after the “prepared” list) by placing a specific ending function, ignored when looping, but useful at the end. In fact, the $\langle end-loop \rangle$ function does nothing but place the appropriate ending function in front of all its arguments. The ending functions take care of sorting non-empty sublists, placing the pivot in between, and the continuation before.

The final change in fact slows down the code a little, but is required to avoid memory issues: schematically, when `TeX` encounters

```
\use:n { \use:n { \use:n { ... } ... } ... }
```

the argument of the first `\use:n` is not completely read by the second `\use:n`, hence must remain in memory; then the argument of the second `\use:n` is not completely read when grabbing the argument of the third `\use:n`, hence must remain in memory, and so on. The memory consumption grows quadratically with the number of nested `\use:n`. In practice, this means that we must read everything until a trailing `\q_stop` once in a while, otherwise sorting lists of more than a few thousand items would exhaust a typical TeX's memory.

`\tl_sort:nN`

`__sort_quick_prepare:Nnnn`
`__sort_quick_prepare_end:NNNnw`
`__sort_quick_cleanup:w`

The code within the `\exp_not:f` sorts the list, leaving in most cases a leading `\exp_not:f`, which stops the expansion, letting the result be return within `\exp_not:n`. We filter out the case of a list with no item, which would otherwise cause problems. Then prepare the token list #1 by inserting the conditional #2 before each item. The `prepare` auxiliary receives the conditional as #1, the prepared token list so far as #2, the next prepared item as #3, and the item after that as #4. The loop ends when #4 contains `__prg_break_point:`, then the `prepare_end` auxiliary finds the prepared token list as #4. The scene is then set up for `__sort_quick_split:NnNn`, which sorts the prepared list and perform the post action placed after `\q_mark`, namely removing the trailing `\s__stop` and `\q_stop` and leaving `\exp_stop_f:` to stop f-expansion.

```

17098 \cs_new:Npn \tl_sort:nN #1#2
17099 {
17100   \exp_not:f
17101   {
17102     \tl_if_blank:nF {#1}
17103     {
17104       \__sort_quick_prepare:Nnnn #2 { } { }
17105       #1
17106       { \__prg_break_point: \__sort_quick_prepare_end:NNNnw }
17107       \q_stop
17108     }
17109   }
17110 }
17111 \cs_new:Npn \__sort_quick_prepare:Nnnn #1#2#3#4
17112 {
17113   \__prg_break: #4 \__prg_break_point:
17114   \__sort_quick_prepare:Nnnn #1 { #2 #3 } { #1 {#4} }
17115 }
17116 \cs_new:Npn \__sort_quick_prepare_end:NNNnw #1#2#3#4#5 \q_stop
17117 {
17118   \__sort_quick_split:NnNn #4 \__sort_quick_end:nnTFNn { }
17119   \q_mark { \__sort_quick_cleanup:w \exp_stop_f: }
17120   \s__stop \q_stop
17121 }
17122 \cs_new:Npn \__sort_quick_cleanup:w #1 \s__stop \q_stop {#1}

```

(End definition for `\tl_sort:nN` and others. This function is documented on page 46.)

`__sort_quick_split:NnNn`

`__sort_quick_only_i:NnnnnNn`
`__sort_quick_only_ii:NnnnnNn`
`__sort_quick_split_i:NnnnnNn`
`__sort_quick_split_ii:NnnnnNn`

The `only_i`, `only_ii`, `split_i` and `split_ii` auxiliaries receive a useless first argument, the new item #2 (that they append to either one of the next two arguments), the list #3 of items less than the pivot, bigger items #4, the pivot #5, a *function* #6, and an item #7. The *function* is the user's *conditional* except at the end of the list where it is `__sort_quick_end:nnTFNn`. The comparison is applied to the *pivot* and the *item*, and calls the `only_i` or `split_i` auxiliaries if the *item* is smaller, and the `only_ii` or `split_ii` auxiliaries otherwise. In both cases, the next auxiliary goes to work right

away, with no intermediate expansion that would slow down operations. Note that the argument #2 left for the next call has the form $\langle conditional \rangle \{ \langle item \rangle \}$, so that the lists #3 and #4 keep the right form to be fed to the next sorting function. The `split` auxiliary differs from these in that it is missing three of the arguments, which would be empty, and its first argument is always the user's $\langle conditional \rangle$ rather than an ending function.

```

17123 \cs_new:Npn \__sort_quick_split:NnNn #1#2#3#4
17124 {
17125     #3 {#2} {#4} \__sort_quick_only_ii:NnnnnNn \__sort_quick_only_i:NnnnnNn
17126     \__sort_quick_single_end:nnnwnw
17127     { #3 {#4} } { } { } {#2}
17128 }
17129 \cs_new:Npn \__sort_quick_only_i:NnnnnNn #1#2#3#4#5#6#7
17130 {
17131     #6 {#5} {#7} \__sort_quick_split_ii:NnnnnNn \__sort_quick_only_i:NnnnnNn
17132     \__sort_quick_only_i_end:nnnwnw
17133     { #6 {#7} } { #3 #2 } { } {#5}
17134 }
17135 \cs_new:Npn \__sort_quick_only_ii:NnnnnNn #1#2#3#4#5#6#7
17136 {
17137     #6 {#5} {#7} \__sort_quick_only_ii:NnnnnNn \__sort_quick_split_i:NnnnnNn
17138     \__sort_quick_only_ii_end:nnnwnw
17139     { #6 {#7} } { } { #4 #2 } {#5}
17140 }
17141 \cs_new:Npn \__sort_quick_split_i:NnnnnNn #1#2#3#4#5#6#7
17142 {
17143     #6 {#5} {#7} \__sort_quick_split_ii:NnnnnNn \__sort_quick_split_i:NnnnnNn
17144     \__sort_quick_split_end:nnnwnw
17145     { #6 {#7} } { #3 #2 } {#4} {#5}
17146 }
17147 \cs_new:Npn \__sort_quick_split_ii:NnnnnNn #1#2#3#4#5#6#7
17148 {
17149     #6 {#5} {#7} \__sort_quick_split_ii:NnnnnNn \__sort_quick_split_i:NnnnnNn
17150     \__sort_quick_split_end:nnnwnw
17151     { #6 {#7} } {#3} { #4 #2 } {#5}
17152 }

```

(End definition for `__sort_quick_split:NnNn` and others.)

```

\__sort_quick_end:nnTFNn
\__sort_quick_single_end:nnnwnw
\__sort_quick_only_i_end:nnnwnw
\__sort_quick_only_ii_end:nnnwnw
\__sort_quick_split_end:nnnwnw

```

The `__sort_quick_end:nnTFNn` appears instead of the user's conditional, and receives as its arguments the pivot #1, a fake item #2, a `true` and a `false` branches #3 and #4, followed by an ending function #5 (one of the four auxiliaries here) and another copy #6 of the fake item. All those are discarded except the function #5. This function receives lists #1 and #2 of items less than or greater than the pivot #3, then a continuation code #5 just after `\q_mark`. To avoid a memory problem described earlier, all of the ending functions read #6 until `\q_stop` and place #6 back into the input stream. When the lists #1 and #2 are empty, the `single` auxiliary simply places the continuation #5 before the pivot {#3}. When #2 is empty, #1 is sorted and placed before the pivot {#3}, taking care to feed the continuation #5 as a continuation for the function sorting #1. When #1 is empty, #2 is sorted, and the continuation argument is used to place the continuation #5 and the pivot {#3} before the sorted result. Finally, when both lists are non-empty, items larger than the pivot are sorted, then items less than the pivot, and the continuations are done in such a way to place the pivot in between.

```

17153 \cs_new:Npn \__sort_quick_end:nnTFNn #1#2#3#4#5#6 {#5}
17154 \cs_new:Npn \__sort_quick_single_end:nnnwnw #1#2#3#4 \q_mark #5#6 \q_stop
17155 { #5 {#3} #6 \q_stop }
17156 \cs_new:Npn \__sort_quick_only_i_end:nnnwnw #1#2#3#4 \q_mark #5#6 \q_stop
17157 {
17158   \__sort_quick_split:NnNn #1
17159   \__sort_quick_end:nnTFNn { } \q_mark {#5}
17160   {#3}
17161   #6 \q_stop
17162 }
17163 \cs_new:Npn \__sort_quick_only_ii_end:nnnwnw #1#2#3#4 \q_mark #5#6 \q_stop
17164 {
17165   \__sort_quick_split:NnNn #2
17166   \__sort_quick_end:nnTFNn { } \q_mark { #5 {#3} }
17167   #6 \q_stop
17168 }
17169 \cs_new:Npn \__sort_quick_split_end:nnnwnw #1#2#3#4 \q_mark #5#6 \q_stop
17170 {
17171   \__sort_quick_split:NnNn #2 \__sort_quick_end:nnTFNn { } \q_mark
17172   {
17173     \__sort_quick_split:NnNn #1
17174     \__sort_quick_end:nnTFNn { } \q_mark {#5}
17175     {#3}
17176   }
17177   #6 \q_stop
17178 }

```

(End definition for __sort_quick_end:nnTFNn and others.)

33.6 Messages

__sort_error: Bailing out of the sorting code is a bit tricky. It may not be safe to use a delimited argument, so instead we redefine many l3sort commands to be trivial, with __sort_level: getting rid of the final assignment. This error recovery won't work in a group.

```

17179 \cs_new_protected:Npn \__sort_error:
17180 {
17181   \cs_set_eq:NN \__sort_merge_blocks_aux: \prg_do_nothing:
17182   \cs_set_eq:NN \__sort_merge_blocks: \prg_do_nothing:
17183   \cs_set_protected:Npn \__sort_level: \use:x ##1 { \group_end: }
17184 }

```

(End definition for __sort_error:.)

__sort_disable_toksdef: While sorting, \toksdef is locally disabled to prevent users from using \newtoks or similar commands in their comparison code: the \toks registers that would be assigned are in use by l3sort. In format mode, none of this is needed since there is no \toks allocator.

```

17185 (*package)
17186 \cs_new_protected:Npn \__sort_disable_toksdef:
17187 { \cs_set_eq:NN \toksdef \__sort_disabled_toksdef:n }
17188 \cs_new_protected:Npn \__sort_disabled_toksdef:n #1
17189 {
17190   \__msg_kernel_error:nnx { kernel } { toksdef }
17191   { \token_to_str:N #1 }

```

```

17192     \__sort_error:
17193     \tex_toksdef:D #1
17194   }
17195   \__msg_kernel_new:nnnn { kernel } { toksdef }
17196   { Allocation~of~\iow_char:N\ toks~registers~impossible~while~sorting. }
17197   {
17198     The~comparison~code~used~for~sorting~a~list~has~attempted~to~
17199     define~#1~as~a~new~\iow_char:N\ toks~register~using~\iow_char:N\ newtoks~
17200     or~a~similar~command.~The~list~will~not~be~sorted.
17201   }
17202 \end{package}

```

(End definition for __sort_disable_toksdef: and __sort_disabled_toksdef:n.)

__sort_too_long_error:NNw When there are too many items in a sequence, this is an error, and we clean up properly the mapping over items in the list: break using the type-specific breaking function #1.

```

17203 \cs_new_protected:Npn \__sort_too_long_error:NNw #1#2 \fi:
17204 {
17205   \fi:
17206   \__msg_kernel_error:nnxxx { kernel } { too-large }
17207   { \token_to_str:N #2 }
17208   { \int_eval:n { \l__sort_true_max_int - \l__sort_min_int } }
17209   { \int_eval:n { \l__sort_top_int - \l__sort_min_int } }
17210   #1 \__sort_error:
17211 }
17212 \__msg_kernel_new:nnnn { kernel } { too-large }
17213 { The~list~#1~is~too~long~to~be~sorted~by~TeX. }
17214 {
17215   TeX~has~#2~toks~registers~still~available:~
17216   this~only~allows~to~sort~with~up~to~#3~
17217   items.~All~extra~items~will~be~deleted.
17218 }

```

(End definition for __sort_too_long_error:NNw.)

```

17219 \__msg_kernel_new:nnnn { kernel } { return-none }
17220 { The~comparison~code~did~not~return. }
17221 {
17222   When~sorting~a~list,~the~code~to~compare~items~#1~and~#2~
17223   did~not~call~
17224   \iow_char:N\ sort_return_same: ~nor~
17225   \iow_char:N\ sort_return_swapped: .~
17226   Exactly~one~of~these~should~be~called.
17227 }
17228 \__msg_kernel_new:nnnn { kernel } { return-two }
17229 { The~comparison~code~returned~multiple~times. }
17230 {
17231   When~sorting~a~list,~the~code~to~compare~items~called~
17232   \iow_char:N\ sort_return_same: ~or~
17233   \iow_char:N\ sort_return_swapped: ~multiple~times.~
17234   Exactly~one~of~these~should~be~called.
17235 }

```

33.7 Deprecated functions

`\sort_ordered:` These functions were renamed for consistency.
`\sort_reversed:`

```

17236 \__debug_deprecation:nnNNpn { 2018-12-31 } { \sort_return_same: }
17237 \cs_new_protected:Npn \sort_ordered: { \sort_return_same: }
17238 \__debug_deprecation:nnNNpn { 2018-12-31 } { \sort_return_swapped: }
17239 \cs_new_protected:Npn \sort_reversed: { \sort_return_swapped: }

(End definition for \sort_ordered: and \sort_reversed:.)

17240 </initex | package>

```

34 l3tl-build implementation

```

17241 <*initex | package>
17242 <@@=tl_build>

```

34.1 Variables and helper functions

`\l__tl_build_start_index_int` Integers pointing to the starting index (currently always starts at zero), and the current
`\l__tl_build_index_int` index. The corresponding `\toks` are accessed directly by number.

```

17243 \int_new:N \l__tl_build_start_index_int
17244 \int_new:N \l__tl_build_index_int

```

(End definition for `\l__tl_build_start_index_int` and `\l__tl_build_index_int`.)

`\l__tl_build_result_tl` The resulting token list is normally built in one go by unpacking all `\toks` in some range. In the rare cases where there are too many `__tl_build_one:n` commands, leading to the depletion of registers, the contents of the current set of `\toks` is unpacked into `\l__tl_build_result_tl`. This prevents overflow from affecting the end-user (beyond an obvious performance hit).

```

17245 \tl_new:N \l__tl_build_result_tl

```

(End definition for `\l__tl_build_result_tl`.)

`__tl_build_unpack:` The various pieces of the token list are built in `\toks` from the `start_index` (inclusive)
`__tl_build_unpack_loop:w` to the (current) `index` (excluded). Those `\toks` are unpacked and stored in order in the `result` token list. Optimizations would be possible here, for instance, unpacking 10 `\toks` at a time with a macro expanding to `\the\toks#10...\the\toks#19`, but this should be kept for much later.

```

17246 \cs_new_protected:Npn \__tl_build_unpack:
17247 {
17248   \tl_put_right:Nx \l__tl_build_result_tl
17249   {
17250     \exp_after:wN \__tl_build_unpack_loop:w
17251     \int_use:N \l__tl_build_start_index_int ;
17252     \__prg_break_point:
17253   }
17254 }
17255 \cs_new:Npn \__tl_build_unpack_loop:w #1 ;
17256 {
17257   \if_int_compare:w #1 = \l__tl_build_index_int
17258     \exp_after:wN \__prg_break:
17259   \fi:

```



```

17260 \tex_the:D \tex_toks:D #1 \exp_stop_f:
17261 \exp_after:wN \__tl_build_unpack_loop:w
17262 \int_use:N \__int_eval:w #1 + 1 ;
17263 }

```

(End definition for `__tl_build_unpack:` and `__tl_build_unpack_loop:w`.)

34.2 Building the token list

```

\__tl_build:Nw Similar to what is done for coffins: redefine some command, here \__tl_build_end-
\__tl_build_x:Nw aux:n to hold the relevant assignment (see \__tl_build_end: for details). Then initialize
\__tl_gbuild:Nw the start index and the current index at zero, and empty the result token list.
\__tl_gbuild_x:Nw
\__tl_build_aux:NNw
17264 \cs_new_protected:Npn \__tl_build:Nw
17265 { \__tl_build_aux:NNw \tl_set:Nn }
17266 \cs_new_protected:Npn \__tl_build_x:Nw
17267 { \__tl_build_aux:NNw \tl_set:Nx }
17268 \cs_new_protected:Npn \__tl_gbuild:Nw
17269 { \__tl_build_aux:NNw \tl_gset:Nn }
17270 \cs_new_protected:Npn \__tl_gbuild_x:Nw
17271 { \__tl_build_aux:NNw \tl_gset:Nx }
17272 \cs_new_protected:Npn \__tl_build_aux:NNw #1#2
17273 {
17274   \group_begin:
17275   \cs_set:Npn \__tl_build_end_assignment:n
17276     { \group_end: #1 #2 }
17277   \int_zero:N \l__tl_build_start_index_int
17278   \int_zero:N \l__tl_build_index_int
17279   \tl_clear:N \l__tl_build_result_tl
17280 }

```

(End definition for `__tl_build:Nw` and others.)

```

\__tl_build_end: When we are done building a token list, unpack all \toks into the result token list, and
\__tl_build_end_assignment:n expand this list before closing the group. The \__tl_build_end_assignment:n function
is defined by \__tl_build_aux:NNw to end the group and hold the relevant assignment.
Its value outside is irrelevant, but just in case, we set it to a function which would clean
up the contents of \l__tl_build_result_tl.

```

```

17281 \cs_new_protected:Npn \__tl_build_end:
17282 {
17283   \__tl_build_unpack:
17284   \exp_args:No
17285   \__tl_build_end_assignment:n \l__tl_build_result_tl
17286 }
17287 \cs_new_eq:NN \__tl_build_end_assignment:n \use_none:n

```

(End definition for `__tl_build_end:` and `__tl_build_end_assignment:n`.)

```

\__tl_build_one:n Store the tokens in a free \toks, then move the pointer to the next one. If we overflow,
\__tl_build_one:o unpack the current \toks, and reset the current index, preparing to fill more \toks. This
\__tl_build_one:x could be optimized by avoiding to read #1, using \afterassignment.

```

```

17288 \cs_new_protected:Npn \__tl_build_one:n #1
17289 {
17290   \tex_toks:D \l__tl_build_index_int {#1}
17291   \int_incr:N \l__tl_build_index_int

```

```

17292     \if_int_compare:w \l__tl_build_index_int > \c_max_register_int
17293     \__tl_build_unpack:
17294     \l__tl_build_index_int \l__tl_build_start_index_int
17295     \fi:
17296   }
17297 \cs_new_protected:Npn \__tl_build_one:o #1
17298 {
17299   \tex_toks:D \l__tl_build_index_int \exp_after:wN {#1}
17300   \int_incr:N \l__tl_build_index_int
17301   \if_int_compare:w \l__tl_build_index_int > \c_max_register_int
17302   \__tl_build_unpack:
17303   \l__tl_build_index_int \l__tl_build_start_index_int
17304   \fi:
17305 }
17306 \cs_new_protected:Npn \__tl_build_one:x #1
17307 { \use:x { \__tl_build_one:n {#1} } }

(End definition for \__tl_build_one:n.)

17308 </initex | package>

```

35 l3tl-analysis implementation

35.1 Internal functions

`\s__tl` The format used to store token lists internally uses the scan mark `\s__tl` as a delimiter.

(End definition for `\s__tl`.)

```

\__tl_analysis_map_inline:nn \__tl_analysis_map_inline:nn {<token list>} {<inline function>}

```

Applies the *<inline function>* to each individual *<token>* in the *<token list>*. The *<inline function>* receives three arguments:

- *<tokens>*, which both o-expand and x-expand to the *<token>*. The detailed form of *<token>* may change in later releases.
- *<catcode>*, a capital hexadecimal digit which denotes the category code of the *<token>* (0: control sequence, 1: begin-group, 2: end-group, 3: math shift, 4: alignment tab, 6: parameter, 7: superscript, 8: subscript, A: space, B: letter, C: other, D: active).
- *<char code>*, a decimal representation of the character code of the token, −1 if it is a control sequence (with *<catcode>* 0).

For optimizations in `l3regex` (when matching control sequences), it may be useful to provide a `__tl_analysis_from_str_map_inline:nn` function, perhaps named `__-str_analysis_map_inline:nn`.

35.2 Internal format

The task of the `l3tl-analysis` module is to convert token lists to an internal format which allows us to extract all the relevant information about individual tokens (category code, character code), as well as reconstruct the token list quickly. This internal format is used in `l3regex` where we need to support arbitrary tokens, and it is used in conversion

functions in `l3str-convert`, where we wish to support clusters of characters instead of single tokens.

We thus need a way to encode any $\langle token \rangle$ (even begin-group and end-group character tokens) in a way amenable to manipulating tokens individually. The best we can do is to find $\langle tokens \rangle$ which both *o*-expand and *x*-expand to the given $\langle token \rangle$. Collecting more information about the category code and character code is also useful for regular expressions, since most regexes are catcode-agnostic. The internal format thus takes the form of a succession of items of the form

$\langle tokens \rangle \backslash s_tl \langle catcode \rangle \langle char\ code \rangle \backslash s_tl$

The $\langle tokens \rangle$ *o*- and *x*-expand to the original token in the token list or to the cluster of tokens corresponding to one Unicode character in the given encoding (for `l3str-convert`). The $\langle catcode \rangle$ is given as a single hexadecimal digit, 0 for control sequences. The $\langle char\ code \rangle$ is given as a decimal number, -1 for control sequences.

Using delimited arguments lets us build the $\langle tokens \rangle$ progressively when doing an encoding conversion in `l3str-convert`. On the other hand, the delimiter `\s_tl` may not appear unbraced in $\langle tokens \rangle$. This is not a problem because we are careful to wrap control sequences in braces (as an argument to `\exp_not:n`) when converting from a general token list to the internal format.

The current rule for converting a $\langle token \rangle$ to a balanced set of $\langle tokens \rangle$ which both *o*-expands and *x*-expands to it is the following.

- A control sequence `\cs` becomes `\exp_not:n { \cs } \s_tl 0 -1 \s_tl`.
- A begin-group character `{` becomes `\exp_after:wN { \if_false: } \fi: \s_tl 1 \langle char\ code \rangle \s_tl`.
- An end-group character `}` becomes `\if_false: { \fi: } \s_tl 2 \langle char\ code \rangle \s_tl`.
- A character with any other category code becomes `\exp_not:n {\langle character \rangle} \s_tl \langle hex\ catcode \rangle \langle char\ code \rangle \s_tl`.

17309 $\langle *initex | package \rangle$

17310 $\langle @@=tl_analysis \rangle$

35.3 Variables and helper functions

`\s_tl` The scan mark `\s_tl` is used as a delimiter in the internal format. This is more practical than using a quark, because we would then need to control expansion much more carefully: compare `__int_value:w '#1 \s_tl` with `__int_value:w '#1 \exp_stop_f: \exp_not:N \q_mark` to extract a character code followed by the delimiter in an *x*-expansion.

17311 `__scan_new:N \s_tl`

(End definition for `\s_tl`.)

`\l_tl_analysis_internal_tl` This token list variable is used to hand the argument of `\tl_show_analysis:n` to `\tl_show_analysis:N`.

17312 `\tl_new:N \l_tl_analysis_internal_tl`

(End definition for `\l_tl_analysis_internal_tl`.)

`\l__tl_analysis_token` The tokens in the token list are probed with the TeX primitive `\futurelet`. We use `\l__tl_analysis_char_token` in that construction. In some cases, we convert the following token to a string before probing it: then the token variable used is `\l__tl_analysis_char_token`.

```

17313 \cs_new_eq:NN \l__tl_analysis_token ?
17314 \cs_new_eq:NN \l__tl_analysis_char_token ?

```

(End definition for `\l__tl_analysis_token` and `\l__tl_analysis_char_token`.)

`\l__tl_analysis_normal_int` The number of normal (N-type argument) tokens since the last special token.

```

17315 \int_new:N \l__tl_analysis_normal_int

```

(End definition for `\l__tl_analysis_normal_int`.)

`\l__tl_analysis_index_int` During the first pass, this is the index in the array being built. During the second pass, it is equal to the maximum index in the array from the first pass.

```

17316 \int_new:N \l__tl_analysis_index_int

```

(End definition for `\l__tl_analysis_index_int`.)

`\l__tl_analysis_nesting_int` Nesting depth of explicit begin-group and end-group characters during the first pass. This lets us detect the end of the token list without a reserved end-marker.

```

17317 \int_new:N \l__tl_analysis_nesting_int

```

(End definition for `\l__tl_analysis_nesting_int`.)

`\l__tl_analysis_type_int` When encountering special characters, we record their “type” in this integer.

```

17318 \int_new:N \l__tl_analysis_type_int

```

(End definition for `\l__tl_analysis_type_int`.)

`\g__tl_analysis_result_tl` The result of the conversion is stored in this token list, with a succession of items of the form

```

\tokens \s__tl \catcode \char code \s__tl

```

```

17319 \tl_new:N \g__tl_analysis_result_tl

```

(End definition for `\g__tl_analysis_result_tl`.)

`__tl_analysis_extract_charcode:` Extracting the character code from the meaning of `\l__tl_analysis_token`. This has no error checking, and should only be assumed to work for begin-group and end-group character tokens. It produces a number in the form ‘`\char`’.

```

17320 \cs_new:Npn \__tl_analysis_extract_charcode:
17321 {
17322   \exp_after:wN \__tl_analysis_extract_charcode_aux:w
17323   \token_to_meaning:N \l__tl_analysis_token
17324 }
17325 \cs_new:Npn \__tl_analysis_extract_charcode_aux:w #1 ~ #2 ~ { ‘ ’ }

```

(End definition for `__tl_analysis_extract_charcode:` and `__tl_analysis_extract_charcode_aux:w`.)

```

\__tl_analysis_cs_space_count:NN Counts the number of spaces in the string representation of its second argument, as well
\__tl_analysis_cs_space_count:w as the number of characters following the last space in that representation, and feeds the
\__tl_analysis_cs_space_count_end:w two numbers as semicolon-delimited arguments to the first argument. When this function
is used, the escape character is printable and non-space.

17326 \cs_new:Npn \__tl_analysis_cs_space_count:NN #1 #2
17327 {
17328   \exp_after:wN #1
17329   \__int_value:w \__int_eval:w 0
17330   \exp_after:wN \__tl_analysis_cs_space_count:w
17331   \token_to_str:N #2
17332   \fi: \__tl_analysis_cs_space_count_end:w ; ~ !
17333 }
17334 \cs_new:Npn \__tl_analysis_cs_space_count:w #1 ~
17335 {
17336   \if_false: #1 #1 \fi:
17337   + 1
17338   \__tl_analysis_cs_space_count:w
17339 }
17340 \cs_new:Npn \__tl_analysis_cs_space_count_end:w ; #1 \fi: #2 !
17341 { \exp_after:wN ; \__int_value:w \str_count_ignore_spaces:n {#1} ; }

(End definition for \__tl_analysis_cs_space_count:NN, \__tl_analysis_cs_space_count:w, and \__-
tl_analysis_cs_space_count_end:w.)

```

35.4 Plan of attack

Our goal is to produce a token list of the form roughly

```

⟨token 1⟩ \s__tl ⟨catcode 1⟩ ⟨char code 1⟩ \s__tl
⟨token 2⟩ \s__tl ⟨catcode 2⟩ ⟨char code 2⟩ \s__tl
... ⟨token N⟩ \s__tl ⟨catcode N⟩ ⟨char code N⟩ \s__tl

```

Most but not all tokens can be grabbed as an undelimited (N-type) argument by \TeX . The plan is to have a two pass system. In the first pass, locate special tokens, and store them in various `\toks` registers. In the second pass, which is done within an `x-expanding` assignment, normal tokens are taken in as N-type arguments, and special tokens are retrieved from the `\toks` registers, and removed from the input stream by some means. The whole process takes linear time, because we avoid building the result one item at a time.

We make the escape character printable (backslash, but this later oscillates between slash and backslash): this allows us to distinguish characters from control sequences.

A token has two characteristics: its `\meaning`, and what it looks like for \TeX when it is in scanning mode (*e.g.*, when capturing parameters for a macro). For our purposes, we distinguish the following meanings:

- begin-group token (category code 1), either space (character code 32), or non-space;
- end-group token (category code 2), either space (character code 32), or non-space;
- space token (category code 10, character code 32);
- anything else (then the token is always an N-type argument).

The token itself can “look like” one of the following

- a non-active character, in which case its meaning is automatically that associated to its character code and category code, we call it “true” character;
- an active character;
- a control sequence.

The only tokens which are not valid N-type arguments are true begin-group characters, true end-group characters, and true spaces. We detect those characters by scanning ahead with `\futurelet`, then distinguishing true characters from control sequences set equal to them using the `\string` representation.

The second pass is a simple exercise in expandable loops.

`__tl_analysis:n` Everything is done within a group, and all definitions are local. We use `\group_align_safe_begin/end:` to avoid problems in case `__tl_analysis:n` is used within an alignment and its argument contains alignment tab tokens.

```

17342 \cs_new_protected:Npn \__tl_analysis:n #1
17343 {
17344   \group_begin:
17345     \group_align_safe_begin:
17346       \__tl_analysis_a:n {#1}
17347       \__tl_analysis_b:n {#1}
17348     \group_align_safe_end:
17349   \group_end:
17350 }
```

(End definition for `__tl_analysis:n`.)

35.5 Disabling active characters

`__tl_analysis_disable:n` Active characters can cause problems later on in the processing, so we provide a way to disable them, by setting them to `undefined`. Since Unicode contains too many characters to loop over all of them, we instead do this whenever we encounter a character. For `pTeX` and `upTeX` we skip characters beyond `[0, 255]` because `\lccode` only allows those values.

```

17351 \group_begin:
17352   \char_set_catcode_active:N \^^@
17353   \cs_new_protected:Npn \__tl_analysis_disable:n #1
17354   {
17355     \tex_lccode:D 0 = #1 \exp_stop_f:
17356     \tex_lowercase:D { \tex_let:D \^^@ } \tex_undefined:D
17357   }
17358   \cs_if_exist:NT \ptex_kanjiskip:D
17359   {
17360     \cs_gset_protected:Npn \__tl_analysis_disable:n #1
17361     {
17362       \if_int_compare:w 256 > #1 \exp_stop_f:
17363       \tex_lccode:D 0 = #1 \exp_stop_f:
17364       \tex_lowercase:D { \tex_let:D \^^@ } \tex_undefined:D
17365     }
17366   }
17367 }
17368 \group_end:
```

(End definition for `__tl_analysis_disable:n`.)

35.6 First pass

The goal of this pass is to detect special (non-N-type) tokens, and count how many N-type tokens lie between special tokens. Also, we wish to store some representation of each special token in a `\toks` register.

We have 11 types of tokens:

1. a true non-space begin-group character;
2. a true space begin-group character;
3. a true non-space end-group character;
4. a true space end-group character;
5. a true space blank space character;
6. an active character;
7. any other true character;
8. a control sequence equal to a begin-group token (category code 1);
9. a control sequence equal to an end-group token (category code 2);
10. a control sequence equal to a space token (character code 32, category code 10);
11. any other control sequence.

Our first tool is `\futurelet`. This cannot distinguish case 8 from 1 or 2, nor case 9 from 3 or 4, nor case 10 from case 5. Those cases are later distinguished by applying the `\string` primitive to the following token, after possibly changing the escape character to ensure that a control sequence's string representation cannot be mistaken for the true character.

In cases 6, 7, and 11, the following token is a valid N-type argument, so we grab it and distinguish the case of a character from a control sequence: in the latter case, `\str_tail:n {\token}` is non-empty, because the escape character is printable.

`__tl_analysis_a:n` We read tokens one by one using `\futurelet`. While performing the loop, we keep track of the number of true begin-group characters minus the number of true end-group characters in `\l__tl_analysis_nesting_int`. This reaches `-1` when we read the closing brace.

```
17369 \cs_new_protected:Npn \__tl_analysis_a:n #1
17370 {
17371   \__tl_analysis_disable:n { 32 }
17372   \int_set:Nn \tex_escapechar:D { 92 }
17373   \int_zero:N \l__tl_analysis_normal_int
17374   \int_zero:N \l__tl_analysis_index_int
17375   \int_zero:N \l__tl_analysis_nesting_int
17376   \if_false: { \fi: \__tl_analysis_a_loop:w #1 }
17377   \int_decr:N \l__tl_analysis_index_int
17378 }
```

(End definition for `__tl_analysis_a:n`.)

`__tl_analysis_a_loop:w` Read one character and check its type.

```

17379 \cs_new_protected:Npn \__tl_analysis_a_loop:w
17380 { \tex_futurelet:D \l__tl_analysis_token \__tl_analysis_a_type:w }

(End definition for \__tl_analysis_a_loop:w.)

```

`__tl_analysis_a_type:w` At this point, `\l__tl_analysis_token` holds the meaning of the following token. We store in `\l__tl_analysis_type_int` information about the meaning of the token ahead:

- 0 space token;
- 1 begin-group token;
- -1 end-group token;
- 2 other.

The values 0, 1, -1 correspond to how much a true such character changes the nesting level (2 is used only here, and is irrelevant later). Then call the auxiliary for each case. Note that nesting conditionals here is safe because we only skip over `\l__tl_analysis_token` if it matches with one of the character tokens (hence is not a primitive conditional).

```

17381 \cs_new_protected:Npn \__tl_analysis_a_type:w
17382 {
17383   \l__tl_analysis_type_int =
17384   \if_meaning:w \l__tl_analysis_token \c_space_token
17385     0
17386   \else:
17387     \if_catcode:w \exp_not:N \l__tl_analysis_token \c_group_begin_token
17388       1
17389     \else:
17390       \if_catcode:w \exp_not:N \l__tl_analysis_token \c_group_end_token
17391         - 1
17392       \else:
17393         2
17394       \fi:
17395     \fi:
17396   \fi:
17397   \exp_stop_f:
17398   \if_case:w \l__tl_analysis_type_int
17399     \exp_after:wN \__tl_analysis_a_space:w
17400   \or: \exp_after:wN \__tl_analysis_a_bgroup:w
17401   \or: \exp_after:wN \__tl_analysis_a_safe:N
17402   \else: \exp_after:wN \__tl_analysis_a_egroup:w
17403   \fi:
17404 }

```

(End definition for `__tl_analysis_a_type:w`.)

`__tl_analysis_a_space:w` In this branch, the following token's meaning is a blank space. Apply `\string` to that token: a true blank space gives a space, a control sequence gives a result starting with the escape character, an active character gives something else than a space since we disabled the space. We grab as `\l__tl_analysis_char_token` the first character of the string representation then test it in `__tl_analysis_a_space_test:w`. Also, since `__tl_analysis_a_store:` expects the special token to be stored in the relevant `\toks` register, we do that. The extra `\exp_not:n` is unnecessary of course, but it makes

the treatment of all tokens more homogeneous. If we discover that the next token was actually a control sequence or an active character instead of a true space, then we step the counter of normal tokens. We now have in front of us the whole string representation of the control sequence, including potential spaces; those will appear to be true spaces later in this pass. Hence, all other branches of the code in this first pass need to consider the string representation, so that the second pass does not need to test the meaning of tokens, only strings.

```

17405 \cs_new_protected:Npn \__tl_analysis_a_space:w
17406 {
17407   \tex_afterassignment:D \__tl_analysis_a_space_test:w
17408   \exp_after:wN \cs_set_eq:NN
17409   \exp_after:wN \l__tl_analysis_char_token
17410   \token_to_str:N
17411 }
17412 \cs_new_protected:Npn \__tl_analysis_a_space_test:w
17413 {
17414   \if_meaning:w \l__tl_analysis_char_token \c_space_token
17415     \tex_toks:D \l__tl_analysis_index_int { \exp_not:n { ~ } }
17416     \__tl_analysis_a_store:
17417   \else:
17418     \int_incr:N \l__tl_analysis_normal_int
17419   \fi:
17420   \__tl_analysis_a_loop:w
17421 }

```

(End definition for __tl_analysis_a_space:w and __tl_analysis_a_space_test:w.)

```

\__tl_analysis_a_bgroup:w
\__tl_analysis_a_egroup:w
\__tl_analysis_a_group:nw
\__tl_analysis_a_group_aux:w
  \__tl_analysis_a_group_auxii:w
  \__tl_analysis_a_group_test:w

```

The token is most likely a true character token with catcode 1 or 2, but it might be a control sequence, or an active character. Optimizing for the first case, we store in a toks register some code that expands to that token. Since we will turn what follows into a string, we make sure the escape character is different from the current character code (by switching between solidus and backslash). To detect the special case of an active character let to the catcode 1 or 2 character with the same character code, we disable the active character with that character code and re-test: if the following token has become undefined we can in fact safely grab it. We are finally ready to turn what follows to a string and test it. This is one place where we need \l__tl_analysis_char_token to be a separate control sequence from \l__tl_analysis_token, to compare them.

```

17422 \group_begin:
17423   \char_set_catcode_group_begin:N \^^@ % {
17424   \cs_new_protected:Npn \__tl_analysis_a_bgroup:w
17425     { \__tl_analysis_a_group:nw { \exp_after:wN \^^@ \if_false: } \fi: } }
17426   \char_set_catcode_group_end:N \^^@
17427   \cs_new_protected:Npn \__tl_analysis_a_egroup:w
17428     { \__tl_analysis_a_group:nw { \if_false: { \fi: \^^@ } } % }
17429 \group_end:
17430 \cs_new_protected:Npn \__tl_analysis_a_group:nw #1
17431 {
17432   \tex_lccode:D 0 = \__tl_analysis_extract_charcode: \scan_stop:
17433   \tex_lowercase:D { \tex_toks:D \l__tl_analysis_index_int {#1} }
17434   \if_int_compare:w \tex_lccode:D 0 = \tex_escapechar:D
17435     \int_set:Nn \tex_escapechar:D { 139 - \tex_escapechar:D }
17436   \fi:
17437   \__tl_analysis_disable:n { \tex_lccode:D 0 }

```

```

17438     \tex_futurelet:D \l__tl_analysis_token \__tl_analysis_a_group_aux:w
17439   }
17440 \cs_new_protected:Npn \__tl_analysis_a_group_aux:w
17441 {
17442   \if_meaning:w \l__tl_analysis_token \tex_undefined:D
17443     \exp_after:wN \__tl_analysis_a_safe:N
17444   \else:
17445     \exp_after:wN \__tl_analysis_a_group_auxii:w
17446   \fi:
17447 }
17448 \cs_new_protected:Npn \__tl_analysis_a_group_auxii:w
17449 {
17450   \tex_afterassignment:D \__tl_analysis_a_group_test:w
17451   \exp_after:wN \cs_set_eq:NN
17452   \exp_after:wN \l__tl_analysis_char_token
17453   \token_to_str:N
17454 }
17455 \cs_new_protected:Npn \__tl_analysis_a_group_test:w
17456 {
17457   \if_charcode:w \l__tl_analysis_token \l__tl_analysis_char_token
17458     \__tl_analysis_a_store:
17459   \else:
17460     \int_incr:N \l__tl_analysis_normal_int
17461   \fi:
17462   \__tl_analysis_a_loop:w
17463 }

```

(End definition for `__tl_analysis_a_bgroup:w` and others.)

`__tl_analysis_a_store:` This function is called each time we meet a special token; at this point, the `\toks` register `\l__tl_analysis_index_int` holds a token list which expands to the given special token. Also, the value of `\l__tl_analysis_type_int` indicates which case we are in:

- -1 end-group character;
- 0 space character;
- 1 begin-group character.

We need to distinguish further the case of a space character (code 32) from other character codes, because those behave differently in the second pass. Namely, after testing the `\lccode` of 0 (which holds the present character code) we change the cases above to

- -2 space end-group character;
- -1 non-space end-group character;
- 0 space blank space character;
- 1 non-space begin-group character;
- 2 space begin-group character.

This has the property that non-space characters correspond to odd values of `\l__tl_analysis_type_int`. The number of normal tokens until here and the type of special

token are packed into a `\skip` register. Finally, we check whether we reached the last closing brace, in which case we stop by disabling the looping function (locally).

```

17464 \cs_new_protected:Npn \__tl_analysis_a_store:
17465 {
17466   \tex_advance:D \l__tl_analysis_nesting_int \l__tl_analysis_type_int
17467   \if_int_compare:w \tex_lccode:D 0 = '\ \exp_stop_f:
17468     \tex_advance:D \l__tl_analysis_type_int \l__tl_analysis_type_int
17469   \fi:
17470   \tex_skip:D \l__tl_analysis_index_int
17471   = \l__tl_analysis_normal_int sp plus \l__tl_analysis_type_int sp \scan_stop:
17472   \int_incr:N \l__tl_analysis_index_int
17473   \int_zero:N \l__tl_analysis_normal_int
17474   \if_int_compare:w \l__tl_analysis_nesting_int = -1 \exp_stop_f:
17475     \cs_set_eq:NN \__tl_analysis_a_loop:w \scan_stop:
17476   \fi:
17477 }

```

(End definition for `__tl_analysis_a_store:`.)

```

\__tl_analysis_a_safe:N
\__tl_analysis_a_cs:ww

```

This should be the simplest case: since the upcoming token is safe, we can simply grab it in a second pass. If the token is a single character (including space), the `\if_charcode:w` test yields true; we disable a potentially active character (that could otherwise masquerade as the true character in the next pass) and we count one “normal” token. On the other hand, if the token is a control sequence, we should replace it by its string representation for compatibility with other code branches. Instead of slowly looping through the characters with the main code, we use the knowledge of how the second pass works: if the control sequence name contains no space, count that token as a number of normal tokens equal to its string length. If the control sequence contains spaces, they should be registered as special characters by increasing `\l__tl_analysis_index_int` (no need to carefully count character between each space), and all characters after the last space should be counted in the following sequence of “normal” tokens.

```

17478 \cs_new_protected:Npn \__tl_analysis_a_safe:N #1
17479 {
17480   \if_charcode:w
17481     \scan_stop:
17482     \exp_after:wN \use_none:n \token_to_str:N #1 \prg_do_nothing:
17483     \scan_stop:
17484     \exp_after:wN \use_i:nn
17485   \else:
17486     \exp_after:wN \use_ii:nn
17487   \fi:
17488   {
17489     \__tl_analysis_disable:n { '#1 }
17490     \int_incr:N \l__tl_analysis_normal_int
17491   }
17492   { \__tl_analysis_cs_space_count:NN \__tl_analysis_a_cs:ww #1 }
17493   \__tl_analysis_a_loop:w
17494 }
17495 \cs_new_protected:Npn \__tl_analysis_a_cs:ww #1; #2;
17496 {
17497   \if_int_compare:w #1 > 0 \exp_stop_f:
17498     \tex_skip:D \l__tl_analysis_index_int
17499     = \__int_eval:w \l__tl_analysis_normal_int + 1 sp \scan_stop:

```

```

17500     \tex_advance:D \l__tl_analysis_index_int #1 \exp_stop_f:
17501   \else:
17502     \tex_advance:D
17503   \fi:
17504   \l__tl_analysis_normal_int #2 \exp_stop_f:
17505 }

```

(End definition for `__tl_analysis_a_safe:N` and `__tl_analysis_a_cs:ww`.)

35.7 Second pass

The second pass is an exercise in expandable loops. All the necessary information is stored in `\skip` and `\toks` registers.

`__tl_analysis_b:n` Start the loop with the index 0. No need for an end-marker: the loop stops by itself when the last index is read. We repeatedly oscillate between reading long stretches of normal tokens, and reading special tokens.

```

17506 \cs_new_protected:Npn \__tl_analysis_b:n #1
17507 {
17508   \tl_gset:Nx \g__tl_analysis_result_tl
17509   {
17510     \__tl_analysis_b_loop:w 0; #1
17511     \__prg_break_point:
17512   }
17513 }
17514 \cs_new:Npn \__tl_analysis_b_loop:w #1;
17515 {
17516   \exp_after:wN \__tl_analysis_b_normals:ww
17517   \__int_value:w \tex_skip:D #1 ; #1 ;
17518 }

```

(End definition for `__tl_analysis_b:n` and `__tl_analysis_b_loop:w`.)

`__tl_analysis_b_normals:ww` The first argument is the number of normal tokens which remain to be read, and the second argument is the index in the array produced in the first step. A character's string representation is always one character long, while a control sequence is always longer (we have set the escape character to a printable value). In both cases, we leave `\exp_not:n` `{<token>}` `\s__tl` in the input stream (after x-expansion). Here, `\exp_not:n` is used rather than `\exp_not:N` because `#3` could be a macro parameter character or could be `\s__tl` (which must be hidden behind braces in the result).

```

17519 \cs_new:Npn \__tl_analysis_b_normals:ww #1;
17520 {
17521   \if_int_compare:w #1 = 0 \exp_stop_f:
17522   \__tl_analysis_b_special:w
17523   \fi:
17524   \__tl_analysis_b_normal:wwN #1;
17525 }
17526 \cs_new:Npn \__tl_analysis_b_normal:wwN #1; #2; #3
17527 {
17528   \exp_not:n { \exp_not:n { #3 } } \s__tl
17529   \if_charcode:w
17530     \scan_stop:
17531     \exp_after:wN \use_none:n \token_to_str:N #3 \prg_do_nothing:

```

```

17532         \scan_stop:
17533         \exp_after:wN \_tl_analysis_b_char:Nww
17534     \else:
17535         \exp_after:wN \_tl_analysis_b_cs:Nww
17536     \fi:
17537     #3 #1; #2;
17538 }

```

(End definition for _tl_analysis_b_normals:ww and _tl_analysis_b_normal:wwN.)

_tl_analysis_b_char:Nww If the normal token we grab is a character, leave $\langle catcode \rangle$ $\langle charcode \rangle$ followed by \s_tl in the input stream, and call _tl_analysis_b_normals:ww with its first argument decremented.

```

17539 \cs_new:Npx \_tl_analysis_b_char:Nww #1
17540 {
17541     \exp_not:N \if_meaning:w #1 \exp_not:N \tex_undefined:D
17542     \token_to_str:N D \exp_not:N \else:
17543     \exp_not:N \if_catcode:w #1 \c_catcode_other_token
17544     \token_to_str:N C \exp_not:N \else:
17545     \exp_not:N \if_catcode:w #1 \c_catcode_letter_token
17546     \token_to_str:N B \exp_not:N \else:
17547     \exp_not:N \if_catcode:w #1 \c_math_toggle_token      3 \exp_not:N \else:
17548     \exp_not:N \if_catcode:w #1 \c_alignment_token      4 \exp_not:N \else:
17549     \exp_not:N \if_catcode:w #1 \c_math_superscript_token 7 \exp_not:N \else:
17550     \exp_not:N \if_catcode:w #1 \c_math_subscript_token  8 \exp_not:N \else:
17551     \exp_not:N \if_catcode:w #1 \c_space_token
17552     \token_to_str:N A \exp_not:N \else:
17553     6
17554     \exp_not:n { \fi: \fi: \fi: \fi: \fi: \fi: \fi: \fi: }
17555     \exp_not:N \_int_value:w '#1 \s_tl
17556     \exp_not:N \exp_after:wN \exp_not:N \_tl_analysis_b_normals:ww
17557     \exp_not:N \_int_value:w \exp_not:N \_int_eval:w - 1 +
17558 }

```

(End definition for _tl_analysis_b_char:Nww.)

_tl_analysis_b_cs:Nww If the token we grab is a control sequence, leave 0 -1 (as category code and character code) in the input stream, followed by \s_tl, and call _tl_analysis_b_normals:ww with updated arguments.

```

17559 \cs_new:Npn \_tl_analysis_b_cs:Nww #1
17560 {
17561     0 -1 \s_tl
17562     \_tl_analysis_cs_space_count:NN \_tl_analysis_b_cs_test:ww #1
17563 }
17564 \cs_new:Npn \_tl_analysis_b_cs_test:ww #1 ; #2 ; #3 ; #4 ;
17565 {
17566     \exp_after:wN \_tl_analysis_b_normals:ww
17567     \_int_value:w \_int_eval:w
17568     \if_int_compare:w #1 = 0 \exp_stop_f:
17569     #3
17570 \else:
17571     \tex_skip:D \_int_eval:w #4 + #1 \_int_eval_end:
17572 \fi:
17573 - #2

```

```

17574 \exp_after:wN ;
17575 \__int_value:w \__int_eval:w #4 + #1 ;
17576 }

```

(End definition for `__tl_analysis_b_cs:Nww` and `__tl_analysis_b_cs_test:ww`.)

```

\__tl_analysis_b_special:w
\__tl_analysis_b_special_char:wN
\__tl_analysis_b_special_space:w

```

Here, `#1` is the current index in the array built in the first pass. Check now whether we reached the end (we shouldn't keep the trailing end-group character that marked the end of the token list in the first pass). Unpack the `\toks` register: when x-expanding again, we will get the special token. Then leave the category code in the input stream, followed by the character code, and call `__tl_analysis_b_loop:w` with the next index.

```

17577 \group_begin:
17578 \char_set_catcode_other:N A
17579 \cs_new:Npn \__tl_analysis_b_special:w
17580 \fi: \__tl_analysis_b_normal:wwN 0 ; #1 ;
17581 {
17582 \fi:
17583 \if_int_compare:w #1 = \l__tl_analysis_index_int
17584 \exp_after:wN \__prg_break:
17585 \fi:
17586 \tex_the:D \tex_toks:D #1 \s__tl
17587 \if_case:w \etex_gluestretch:D \tex_skip:D #1 \exp_stop_f:
17588 \token_to_str:N A
17589 \or: 1
17590 \or: 1
17591 \else: 2
17592 \fi:
17593 \if_int_odd:w \etex_gluestretch:D \tex_skip:D #1 \exp_stop_f:
17594 \exp_after:wN \__tl_analysis_b_special_char:wN \__int_value:w
17595 \else:
17596 \exp_after:wN \__tl_analysis_b_special_space:w \__int_value:w
17597 \fi:
17598 \__int_eval:w 1 + #1 \exp_after:wN ;
17599 \token_to_str:N
17600 }
17601 \group_end:
17602 \cs_new:Npn \__tl_analysis_b_special_char:wN #1 ; #2
17603 {
17604 \__int_value:w '#2 \s__tl
17605 \__tl_analysis_b_loop:w #1 ;
17606 }
17607 \cs_new:Npn \__tl_analysis_b_special_space:w #1 ; ~
17608 {
17609 32 \s__tl
17610 \__tl_analysis_b_loop:w #1 ;
17611 }

```

(End definition for `__tl_analysis_b_special:w`, `__tl_analysis_b_special_char:wN`, and `__tl_analysis_b_special_space:w`.)

35.8 Mapping through the analysis

```

\__tl_analysis_map_inline:nn
\__tl_analysis_map_inline_aux:Nn

```

First obtain the analysis of the token list into `\g__tl_analysis_result_tl`. To allow nested mappings, increase the nesting depth `\g__prg_map_int` (shared between all modules), then define the looping macro, which has a name specific to that nesting depth.

That looping grabs the $\langle tokens \rangle$, $\langle catcode \rangle$ and $\langle char code \rangle$; it checks for the end of the loop with $\backslash use_none:n \##2$, normally empty, but which becomes $\backslash tl_map_break:$ at the end; it then performs the user's code $\#2$, and loops by calling itself. When the loop ends, remember to decrease the nesting depth.

```

17612 \cs_new_protected:Npn \__tl_analysis_map_inline:nn #1
17613 {
17614   \__tl_analysis:n {#1}
17615   \int_gincr:N \g__prg_map_int
17616   \exp_args:Nc \__tl_analysis_map_inline_aux:Nn
17617   { \__tl_analysis_map_inline_ \int_use:N \g__prg_map_int :wNw }
17618 }
17619 \cs_new_protected:Npn \__tl_analysis_map_inline_aux:Nn #1#2
17620 {
17621   \cs_gset_protected:Npn #1 ##1 \s__tl ##2 ##3 \s__tl
17622   {
17623     \use_none:n ##2
17624     #2
17625     #1
17626   }
17627   \exp_after:wN #1
17628   \g__tl_analysis_result_tl
17629   \s__tl { ? \tl_map_break: } \s__tl
17630   \__prg_break_point:Nn \tl_map_break: { \int_gdecr:N \g__prg_map_int }
17631 }

```

(End definition for $\backslash_tl_analysis_map_inline:nn$ and $\backslash_tl_analysis_map_inline_aux:Nn$.)

35.9 Showing the results

$\backslash tl_show_analysis:N$ Add to $\backslash_tl_analysis:n$ a third pass to display tokens to the terminal. If the token list variable is not defined, throw the same error as $\backslash tl_show:N$ by simply calling that function.

```

17632 \cs_new_protected:Npn \tl_show_analysis:N #1
17633 {
17634   \tl_if_exist:NTF #1
17635   {
17636     \exp_args:No \__tl_analysis:n {#1}
17637     \msg_show:nnxxxx { LaTeX / kernel } { show-tl-analysis }
17638     { \token_to_str:N #1 } { \__tl_analysis_show: } { } { }
17639   }
17640   { \tl_show:N #1 }
17641 }
17642 \cs_new_protected:Npn \tl_show_analysis:n #1
17643 {
17644   \__tl_analysis:n {#1}
17645   \msg_show:nnxxxx { LaTeX / kernel } { show-tl-analysis }
17646   { } { \__tl_analysis_show: } { } { }
17647 }

```

(End definition for $\backslash tl_show_analysis:N$ and $\backslash tl_show_analysis:n$. These functions are documented on page 204.)

$\backslash_tl_analysis_show:$ Here, $\#1$ o- and x-expands to the token; $\#2$ is the category code (one uppercase hexadecimal digit), 0 for control sequences; $\#3$ is the character code, which we ignore. In the

cases of control sequences and active characters, the meaning may overflow one line, and we want to truncate it. Those cases are thus separated out.

```

17648 \cs_new:Npn \__tl_analysis_show:
17649 {
17650   \exp_after:wN \__tl_analysis_show_loop:wNw \g__tl_analysis_result_tl
17651   \s__tl { ? \__prg_break: } \s__tl
17652   \__prg_break_point:
17653 }
17654 \cs_new:Npn \__tl_analysis_show_loop:wNw #1 \s__tl #2 #3 \s__tl
17655 {
17656   \use_none:n #2
17657   \iow_newline: > \use:nn { ~ } { ~ }
17658   \if_int_compare:w "#2 = 0 \exp_stop_f:
17659     \exp_after:wN \__tl_analysis_show_cs:n
17660   \else:
17661     \if_int_compare:w "#2 = 13 \exp_stop_f:
17662       \exp_after:wN \exp_after:wN
17663       \exp_after:wN \__tl_analysis_show_active:n
17664     \else:
17665       \exp_after:wN \exp_after:wN
17666       \exp_after:wN \__tl_analysis_show_normal:n
17667     \fi:
17668   \fi:
17669   {#1}
17670   \__tl_analysis_show_loop:wNw
17671 }

```

(End definition for __tl_analysis_show: and __tl_analysis_show_loop:wNw.)

__tl_analysis_show_normal:n Non-active characters are a simple matter of printing the character, and its meaning. Our test suite checks that begin-group and end-group characters do not mess up TeX's alignment status.

```

17672 \cs_new:Npn \__tl_analysis_show_normal:n #1
17673 {
17674   \exp_after:wN \token_to_str:N #1 ~
17675   ( \exp_after:wN \token_to_meaning:N #1 )
17676 }

```

(End definition for __tl_analysis_show_normal:n.)

__tl_analysis_show_value:N This expands to the value of #1 if it has any.

```

17677 \cs_new:Npn \__tl_analysis_show_value:N #1
17678 {
17679   \token_if_expandable:NF #1
17680   {
17681     \token_if_chardef:NTF #1 \__prg_break: { }
17682     \token_if_mathchardef:NTF #1 \__prg_break: { }
17683     \token_if_dim_register:NTF #1 \__prg_break: { }
17684     \token_if_int_register:NTF #1 \__prg_break: { }
17685     \token_if_skip_register:NTF #1 \__prg_break: { }
17686     \token_if_toks_register:NTF #1 \__prg_break: { }
17687     \use_none:nnn
17688     \__prg_break_point:
17689     \use:n { \exp_after:wN = \tex_the:D #1 }

```



```

17690     }
17691 }

```

(End definition for _tl_analysis_show_value:N.)

_tl_analysis_show_cs:n Control sequences and active characters are printed in the same way, making sure not to go beyond the \l_iow_line_count_int. In case of an overflow, we replace the last characters by \c_tl_analysis_show_etc_str.

```

\_tl\_analysis\_show\_cs:n
\_tl\_analysis\_show\_active:n
\_tl\_analysis\_show\_long:nn
  \_tl\_analysis\_show\_long\_aux:nnnn
17692 \cs_new:Npn \_tl\_analysis\_show\_cs:n #1
17693   { \exp_args:No \_tl\_analysis\_show\_long:nn {#1} { control~sequence= } }
17694 \cs_new:Npn \_tl\_analysis\_show\_active:n #1
17695   { \exp_args:No \_tl\_analysis\_show\_long:nn {#1} { active~character= } }
17696 \cs_new:Npn \_tl\_analysis\_show\_long:nn #1
17697   {
17698     \_tl\_analysis\_show\_long\_aux:oofn
17699     { \token_to_str:N #1 }
17700     { \token_to_meaning:N #1 }
17701     { \_tl\_analysis\_show\_value:N #1 }
17702   }
17703 \cs_new:Npn \_tl\_analysis\_show\_long\_aux:nnnn #1#2#3#4
17704   {
17705     \int_compare:nNnTF
17706       { \str_count:n { #1 ~ ( #4 #2 #3 ) } }
17707       > { \l\_iow\_line\_count\_int - 3 }
17708       {
17709         \str_range:nnn { #1 ~ ( #4 #2 #3 ) } { 1 }
17710         {
17711           \l\_iow\_line\_count\_int - 3
17712           - \str_count:N \c\_tl\_analysis\_show\_etc\_str
17713         }
17714         \c\_tl\_analysis\_show\_etc\_str
17715       }
17716       { #1 ~ ( #4 #2 #3 ) }
17717   }
17718 \cs_generate_variant:Nn \_tl\_analysis\_show\_long\_aux:nnnn { oof }

```

(End definition for _tl_analysis_show_cs:n and others.)

35.10 Messages

\c_tl_analysis_show_etc_str When a control sequence (or active character) and its meaning are too long to fit in one line of the terminal, the end is replaced by this token list.

```

17719 \tl_const:Nx \c\_tl\_analysis\_show\_etc\_str % (
17720   { \token_to_str:N \ETC.) }

```

(End definition for \c_tl_analysis_show_etc_str.)

```

17721 \__msg_kernel_new:nnn { kernel } { show-tl-analysis }
17722   {
17723     The~token~list~ \tl_if_empty:nF {#1} { #1 ~ }
17724     \tl_if_empty:nTF {#2}
17725       { is~empty }
17726       { contains~the~tokens: #2 }
17727   }

```

17728 </initex | package>

36 l3regex implementation

17729 $\langle *initex \mid package \rangle$

17730 $\langle @@=regex \rangle$

36.1 Plan of attack

Most regex engines use backtracking. This allows to provide very powerful features (back-references come to mind first), but it is costly, and raises the problem of catastrophic backtracking. Since T_EX is not first and foremost a programming language, complicated code tends to run slowly, and we must use faster, albeit slightly more restrictive, techniques, coming from automata theory.

Given a regular expression of n characters, we do the following:

- (Compiling.) Analyse the regex, finding invalid input, and convert it to an internal representation.
- (Building.) Convert the compiled regex to a non-deterministic finite automaton (NFA) with $O(n)$ states which accepts precisely token lists matching that regex.
- (Matching.) Loop through the query token list one token (one “position”) at a time, exploring in parallel every possible path (“active thread”) through the NFA, considering active threads in an order determined by the quantifiers’ greediness.

We use the following vocabulary in the code comments (and in variable names).

- *Group*: index of the capturing group, -1 for non-capturing groups.
- *Position*: each token in the query is labelled by an integer $\langle position \rangle$, with $\text{min_pos} - 1 \leq \langle position \rangle \leq \text{max_pos}$. The lowest and highest positions correspond to imaginary begin and end markers (with inaccessible category code and character code).
- *Query*: the token list to which we apply the regular expression.
- *State*: each state of the NFA is labelled by an integer $\langle state \rangle$ with $\text{min_state} \leq \langle state \rangle < \text{max_state}$.
- *Active thread*: state of the NFA that is reached when reading the query token list for the matching. Those threads are ordered according to the greediness of quantifiers.
- *Step*: used when matching, starts at 0, incremented every time a character is read, and is not reset when searching for repeated matches. The integer `\l__regex_step_int` is a unique id for all the steps of the matching algorithm.

We use `l3intarray` to manipulate arrays of integers (stored into some dimension registers in scaled points). We also abuse T_EX’s `\toks` registers, by accessing them directly by number rather than tying them to control sequence using the `\newtoks` allocation functions. Specifically, these arrays and `\toks` are used as follows. When compiling, `\toks` registers are used under the hood by functions from the `l3tl-build` module. When building, `\toks\langle state \rangle` holds the tests and actions to perform in the $\langle state \rangle$ of the NFA. When matching,

- `\g__regex_state_active_intarray` holds the last $\langle step \rangle$ in which each $\langle state \rangle$ was active.

- `\g__regex_thread_state_intarray` maps each $\langle thread \rangle$ (with $\text{min_active} \leq \langle thread \rangle < \text{max_active}$) to the $\langle state \rangle$ in which the $\langle thread \rangle$ currently is. The $\langle threads \rangle$ or ordered starting from the best to the least preferred.
- `\toks\langle thread \rangle` holds the submatch information for the $\langle thread \rangle$, as the contents of a property list.
- `\g__regex_charcode_intarray` and `\g__regex_catcode_intarray` hold the character codes and category codes of tokens at each $\langle position \rangle$ in the query.
- `\g__regex_balance_intarray` holds the balance of begin-group and end-group character tokens which appear before that point in the token list.
- `\toks\langle position \rangle` holds $\langle tokens \rangle$ which o- and x-expand to the $\langle position \rangle$ -th token in the query.
- `\g__regex_submatch_prev_intarray`, `\g__regex_submatch_begin_intarray` and `\g__regex_submatch_end_intarray` hold, for each submatch (as would be extracted by `\regex_extract_all:nnN`), the place where the submatch started to be looked for and its two end-points. For historical reasons, the minimum index is twice `max_state`, and the used registers go up to `\l__regex_submatch_int`. They are organized in blocks of `\l__regex_capturing_group_int` entries, each block corresponding to one match with all its submatches stored in consecutive entries.

`\count` registers are not abused, which means that we can safely use named integers in this module. Note that `\box` registers are not abused either; maybe we could leverage those for some purpose.

The code is structured as follows. Variables are introduced in the relevant section. First we present some generic helper functions. Then comes the code for compiling a regular expression, and for showing the result of the compilation. The building phase converts a compiled regex to NFA states, and the automaton is run by the code in the following section. The only remaining brick is parsing the replacement text and performing the replacement. We are then ready for all the user functions. Finally, messages, and a little bit of tracing code.

36.2 Helpers

`__regex_standard_escapechar:` Make the `\escapechar` into the standard backslash.

```
17731 \cs_new_protected:Npn \__regex_standard_escapechar:
17732   { \int_set:Nn \tex_escapechar:D { '\ } }
```

(End definition for `__regex_standard_escapechar:.`)

`__regex_toks_use:w` Unpack a `\toks` given its number.

```
17733 \cs_new:Npn \__regex_toks_use:w { \tex_the:D \tex_toks:D }
```

(End definition for `__regex_toks_use:w.`)

`__regex_toks_clear:N` Empty a `\toks` or set it to a value, given its number.

```
\__regex_toks_set:Nn 17734 \cs_new_protected:Npn \__regex_toks_clear:N #1
\__regex_toks_set:No 17735   { \tex_toks:D #1 { } }
17736 \cs_new_eq:NN \__regex_toks_set:Nn \tex_toks:D
17737 \cs_new_protected:Npn \__regex_toks_set:No #1
17738   { \__regex_toks_set:Nn #1 \exp_after:wN }
```

(End definition for `_regex_toks_clear:N` and `_regex_toks_set:Nn`.)

`_regex_toks_memcpy:NNn` Copy #3 `\toks` registers from #2 onwards to #1 onwards, like C’s `memcpy`.

```

17739 \cs_new_protected:Npn \_regex_toks_memcpy:NNn #1#2#3
17740 {
17741   \prg_replicate:nn {#3}
17742   {
17743     \tex_toks:D #1 = \tex_toks:D #2
17744     \int_incr:N #1
17745     \int_incr:N #2
17746   }
17747 }
```

(End definition for `_regex_toks_memcpy:NNn`.)

`_regex_toks_put_left:Nx` During the building phase we wish to add x-expanded material to `\toks`, either to the left
`_regex_toks_put_right:Nx` or to the right. The expansion is done “by hand” for optimization (these operations are
`_regex_toks_put_right:Nn` used quite a lot). The `Nn` version of `_regex_toks_put_right:Nx` is provided because
it is more efficient than x-expanding with `\exp_not:n`.

```

17748 \cs_new_protected:Npn \_regex_toks_put_left:Nx #1#2
17749 {
17750   \cs_set:Npx \_regex_tmp:w { #2 }
17751   \tex_toks:D #1 \exp_after:wN \exp_after:wN \exp_after:wN
17752   { \exp_after:wN \_regex_tmp:w \tex_the:D \tex_toks:D #1 }
17753 }
17754 \cs_new_protected:Npn \_regex_toks_put_right:Nx #1#2
17755 {
17756   \cs_set:Npx \_regex_tmp:w {#2}
17757   \tex_toks:D #1 \exp_after:wN
17758   { \tex_the:D \tex_toks:D \exp_after:wN #1 \_regex_tmp:w }
17759 }
17760 \cs_new_protected:Npn \_regex_toks_put_right:Nn #1#2
17761 { \tex_toks:D #1 \exp_after:wN { \tex_the:D \tex_toks:D #1 #2 } }
```

(End definition for `_regex_toks_put_left:Nx` and `_regex_toks_put_right:Nx`.)

`_regex_curr_cs_to_str:` Expands to the string representation of the token (known to be a control sequence) at
the current position `\l__regex_curr_pos_int`. It should only be used in x-expansion to
avoid losing a leading space.

```

17762 \cs_new:Npn \_regex_curr_cs_to_str:
17763 {
17764   \exp_after:wN \exp_after:wN \exp_after:wN \cs_to_str:N
17765   \tex_the:D \tex_toks:D \l__regex_curr_pos_int
17766 }
```

(End definition for `_regex_curr_cs_to_str:.`)

36.2.1 Constants and variables

`_regex_tmp:w` Temporary function used for various short-term purposes.

```

17767 \cs_new:Npn \_regex_tmp:w { }
```

(End definition for `_regex_tmp:w`.)

`\l__regex_internal_a_tl` Temporary variables used for various purposes.

```

\l__regex_internal_b_tl 17768 \tl_new:N \l__regex_internal_a_tl
\l__regex_internal_a_int 17769 \tl_new:N \l__regex_internal_b_tl
\l__regex_internal_b_int 17770 \int_new:N \l__regex_internal_a_int
\l__regex_internal_c_int 17771 \int_new:N \l__regex_internal_b_int
\l__regex_internal_c_int 17772 \int_new:N \l__regex_internal_c_int
\l__regex_internal_bool 17773 \bool_new:N \l__regex_internal_bool
\l__regex_internal_seq 17774 \seq_new:N \l__regex_internal_seq
\g__regex_internal_tl 17775 \tl_new:N \g__regex_internal_tl

```

(End definition for \l__regex_internal_a_tl and others.)

`\c__regex_no_match_regex` This regular expression matches nothing, but is still a valid regular expression. We could use a failing assertion, but I went for an empty class. It is used as the initial value for regular expressions declared using `\regex_new:N`.

```

17776 \tl_const:Nn \c__regex_no_match_regex
17777 {
17778   \__regex_branch:n
17779   { \__regex_class:NnnnN \c_true_bool { } { 1 } { 0 } \c_true_bool }
17780 }

```

(End definition for \c__regex_no_match_regex.)

`\g__regex_charcode_intarray`
`\g__regex_catcode_intarray`
`\g__regex_balance_intarray` The first thing we do when matching is to go once through the query token list and store the information for each token into `\g__regex_charcode_intarray`, `\g__regex_catcode_intarray` and `\toks` registers. We also store the balance of begin-group/end-group characters into `\g__regex_balance_intarray`.

```

17781 \__intarray_new:Nn \g__regex_charcode_intarray { 65536 }
17782 \__intarray_new:Nn \g__regex_catcode_intarray { 65536 }
17783 \__intarray_new:Nn \g__regex_balance_intarray { 65536 }

```

(End definition for \g__regex_charcode_intarray, \g__regex_catcode_intarray, and \g__regex_balance_intarray.)

`\l__regex_balance_int` During this phase, `\l__regex_balance_int` counts the balance of begin-group and end-group character tokens which appear before a given point in the token list. This variable is also used to keep track of the balance in the replacement text.

```

17784 \int_new:N \l__regex_balance_int

```

(End definition for \l__regex_balance_int.)

`\l__regex_cs_name_tl` This variable is used in `__regex_item_cs:n` to store the csname of the currently-tested token when the regex contains a sub-regex for testing csnames.

```

17785 \tl_new:N \l__regex_cs_name_tl

```

(End definition for \l__regex_cs_name_tl.)

36.2.2 Testing characters

\c__regex_ascii_min_int
 \c__regex_ascii_max_control_int
 \c__regex_ascii_max_int

```
17786 \int_const:Nn \c__regex_ascii_min_int { 0 }
17787 \int_const:Nn \c__regex_ascii_max_control_int { 31 }
17788 \int_const:Nn \c__regex_ascii_max_int { 127 }
```

(End definition for \c__regex_ascii_min_int, \c__regex_ascii_max_control_int, and \c__regex_ascii_max_int.)

\c__regex_ascii_lower_int

```
17789 \int_const:Nn \c__regex_ascii_lower_int { 'a - 'A }
```

(End definition for \c__regex_ascii_lower_int.)

__regex_break_point:TF
 __regex_break_true:w

When testing whether a character of the query token list matches a given character class in the regular expression, we often have to test it against several ranges of characters, checking if any one of those matches. This is done with a structure like

```
<test1> ... <test_n>
\__regex_break_point:TF {<true code>} {<false code>}
```

If any of the tests succeeds, it calls __regex_break_true:w, which cleans up and leaves <true code> in the input stream. Otherwise, __regex_break_point:TF leaves the <false code> in the input stream.

```
17790 \cs_new_protected:Npn \__regex_break_true:w
17791   #1 \__regex_break_point:TF #2 #3 {#2}
17792 \cs_new_protected:Npn \__regex_break_point:TF #1 #2 { #2 }
```

(End definition for __regex_break_point:TF and __regex_break_true:w.)

__regex_item_reverse:n

This function makes showing regular expressions easier, and lets us define \D in terms of \d for instance. There is a subtlety: the end of the query is marked by -2, and thus matches \D and other negated properties; this case is caught by another part of the code.

```
17793 \cs_new_protected:Npn \__regex_item_reverse:n #1
17794   {
17795     #1
17796     \__regex_break_point:TF { } \__regex_break_true:w
17797   }
```

(End definition for __regex_item_reverse:n.)

__regex_item_caseful_equal:n
 __regex_item_caseful_range:nn

Simple comparisons triggering __regex_break_true:w when true.

```
17798 \cs_new_protected:Npn \__regex_item_caseful_equal:n #1
17799   {
17800     \if_int_compare:w #1 = \l__regex_curr_char_int
17801       \exp_after:wN \__regex_break_true:w
17802     \fi:
17803   }
17804 \cs_new_protected:Npn \__regex_item_caseful_range:nn #1 #2
17805   {
17806     \reverse_if:N \if_int_compare:w #1 > \l__regex_curr_char_int
17807     \reverse_if:N \if_int_compare:w #2 < \l__regex_curr_char_int
17808     \exp_after:wN \exp_after:wN \exp_after:wN \__regex_break_true:w
17809     \fi:
17810     \fi:
17811   }
```

(End definition for `_regex_item_caseful_equal:n` and `_regex_item_caseful_range:nn`.)

`_regex_item_caseless_equal:n` For caseless matching, we perform the test both on the `current_char` and on the `case_changed_char`. Before doing the second set of tests, we make sure that `case_changed_char` has been computed.

`_regex_item_caseless_range:nn`

```

17812 \cs_new_protected:Npn \_regex_item_caseless_equal:n #1
17813 {
17814   \if_int_compare:w #1 = \l__regex_curr_char_int
17815     \exp_after:wN \_regex_break_true:w
17816   \fi:
17817   \if_int_compare:w \l__regex_case_changed_char_int = \c_max_int
17818     \_regex_compute_case_changed_char:
17819   \fi:
17820   \if_int_compare:w #1 = \l__regex_case_changed_char_int
17821     \exp_after:wN \_regex_break_true:w
17822   \fi:
17823 }
17824 \cs_new_protected:Npn \_regex_item_caseless_range:nn #1 #2
17825 {
17826   \reverse_if:N \if_int_compare:w #1 > \l__regex_curr_char_int
17827   \reverse_if:N \if_int_compare:w #2 < \l__regex_curr_char_int
17828   \exp_after:wN \exp_after:wN \exp_after:wN \_regex_break_true:w
17829   \fi:
17830   \fi:
17831   \if_int_compare:w \l__regex_case_changed_char_int = \c_max_int
17832     \_regex_compute_case_changed_char:
17833   \fi:
17834   \reverse_if:N \if_int_compare:w #1 > \l__regex_case_changed_char_int
17835   \reverse_if:N \if_int_compare:w #2 < \l__regex_case_changed_char_int
17836   \exp_after:wN \exp_after:wN \exp_after:wN \_regex_break_true:w
17837   \fi:
17838   \fi:
17839 }

```

(End definition for `_regex_item_caseless_equal:n` and `_regex_item_caseless_range:nn`.)

`_regex_compute_case_changed_char:` This function is called when `\l__regex_case_changed_char_int` has not yet been computed (or rather, when it is set to the marker value `\c_max_int`). If the current character code is in the range [65,90] (upper-case), then add 32, making it lowercase. If it is in the lower-case letter range [97,122], subtract 32.

```

17840 \cs_new_protected:Npn \_regex_compute_case_changed_char:
17841 {
17842   \int_set_eq:NN \l__regex_case_changed_char_int \l__regex_curr_char_int
17843   \if_int_compare:w \l__regex_curr_char_int > 'Z \exp_stop_f:
17844     \if_int_compare:w \l__regex_curr_char_int > 'z \exp_stop_f: \else:
17845       \if_int_compare:w \l__regex_curr_char_int < 'a \exp_stop_f: \else:
17846         \int_sub:Nn \l__regex_case_changed_char_int { \c__regex_ascii_lower_int }
17847       \fi:
17848     \fi:
17849   \else:
17850     \if_int_compare:w \l__regex_curr_char_int < 'A \exp_stop_f: \else:
17851       \int_add:Nn \l__regex_case_changed_char_int { \c__regex_ascii_lower_int }
17852     \fi:
17853   \fi:

```

```
17854 }
```

(End definition for `_regex_compute_case_changed_char:.`)

`_regex_item_equal:n` Those must always be defined to expand to a **caseful** (default) or **caseless** version, and not be protected: they must expand when compiling, to hard-code which tests are caseless or caseful.

```
17855 \cs_new_eq:NN \_regex_item_equal:n ?
17856 \cs_new_eq:NN \_regex_item_range:nn ?
```

(End definition for `_regex_item_equal:n` and `_regex_item_range:nn`.)

`_regex_item_catcode:nT` The argument is a sum of powers of 4 with exponents given by the allowed category codes (between 0 and 13). Dividing by a given power of 4 gives an odd result if and only if that category code is allowed. If the catcode does not match, then skip the character code tests which follow.

```
17857 \cs_new_protected:Npn \_regex_item_catcode:
17858 {
17859   "
17860   \if_case:w \l__regex_curr_catcode_int
17861     1      \or: 4      \or: 10      \or: 40
17862   \or: 100  \or:      \or: 1000    \or: 4000
17863   \or: 10000 \or:      \or: 100000 \or: 400000
17864   \or: 1000000 \or: 4000000 \else: 1*0
17865   \fi:
17866 }
17867 \cs_new_protected:Npn \_regex_item_catcode:nT #1
17868 {
17869   \if_int_odd:w \_int_eval:n { #1 / \_regex_item_catcode: }
17870     \exp_after:wN \use:n
17871   \else:
17872     \exp_after:wN \use_none:n
17873   \fi:
17874 }
17875 \cs_new_protected:Npn \_regex_item_catcode_reverse:nT #1#2
17876 { \_regex_item_catcode:nT {#1} { \_regex_item_reverse:n {#2} } }
```

(End definition for `_regex_item_catcode:nT`, `_regex_item_catcode_reverse:nT`, and `_regex_item_catcode:.`)

`_regex_item_exact:nn` This matches an exact *<category>-<character code>* pair, or an exact control sequence, more precisely one of several possible control sequences.

```
17877 \cs_new_protected:Npn \_regex_item_exact:nn #1#2
17878 {
17879   \if_int_compare:w #1 = \l__regex_curr_catcode_int
17880     \if_int_compare:w #2 = \l__regex_curr_char_int
17881     \exp_after:wN \exp_after:wN \exp_after:wN \_regex_break_true:w
17882   \fi:
17883 }
17884 }
17885 \cs_new_protected:Npn \_regex_item_exact_cs:n #1
17886 {
17887   \int_compare:nNnTF \l__regex_curr_catcode_int = 0
17888   {
```



```

17889         \tl_set:Nx \l__regex_internal_a_tl
17890         { \scan_stop: \__regex_curr_cs_to_str: \scan_stop: }
17891         \tl_if_in:noTF { \scan_stop: #1 \scan_stop: } \l__regex_internal_a_tl
17892         { \__regex_break_true:w } { }
17893     }
17894     { }
17895 }

```

(End definition for `__regex_item_exact:nn` and `__regex_item_exact_cs:n`.)

`__regex_item_cs:n` Match a control sequence (the argument is a compiled regex). First test the catcode of the current token to be zero. Then perform the matching test, and break if the csname indeed matches. The three `\exp_after:wN` expand the contents of the `\toks⟨current position⟩` (of the form `\exp_not:n {⟨control sequence⟩}`) to `⟨control sequence⟩`. We store the cs name before building states for the cs, as those states may overlap with toks registers storing the user's input.

```

17896 \cs_new_protected:Npn \__regex_item_cs:n #1
17897 {
17898     \int_compare:nNnT \l__regex_curr_catcode_int = 0
17899     {
17900         \group_begin:
17901         \tl_set:Nx \l__regex_cs_name_tl { \__regex_curr_cs_to_str: }
17902         \__regex_single_match:
17903         \__regex_disable_submatches:
17904         \__regex_build_for_cs:n {#1}
17905         \bool_set_eq:NN \l__regex_saved_success_bool \g__regex_success_bool
17906         \exp_args:NV \__regex_match:n \l__regex_cs_name_tl
17907         \if_meaning:w \c_true_bool \g__regex_success_bool
17908             \group_insert_after:N \__regex_break_true:w
17909         \fi:
17910         \bool_gset_eq:NN \g__regex_success_bool \l__regex_saved_success_bool
17911         \group_end:
17912     }
17913 }

```

(End definition for `__regex_item_cs:n`.)

36.2.3 Character property tests

`__regex_prop_d:` Character property tests for `\d`, `\W`, *etc.* These character properties are not affected by the `(?i)` option. The characters recognized by each one are as follows: `\d=[0-9]`, `\w=[0-9A-Z_a-z]`, `\s=[_\^\^I\^\^J\^\^L\^\^M]`, `\h=[_\^\^I]`, `\v=[\^\^J\^\^M]`, and the upper case counterparts match anything that the lower case does not match. The order in which the various tests appear is optimized for usual mostly lower case letter text.

```

17914 \cs_new_protected:Npn \__regex_prop_d:
17915 { \__regex_item_caseful_range:nn { '0 } { '9 } }
17916 \cs_new_protected:Npn \__regex_prop_h:
17917 {
17918     \__regex_item_caseful_equal:n { '\ }
17919     \__regex_item_caseful_equal:n { '\^\^I }
17920 }
17921 \cs_new_protected:Npn \__regex_prop_s:
17922 {
17923     \__regex_item_caseful_equal:n { '\ }

```

```

17924     \_regex_item_caseful_equal:n { '\^I }
17925     \_regex_item_caseful_equal:n { '\^J }
17926     \_regex_item_caseful_equal:n { '\^L }
17927     \_regex_item_caseful_equal:n { '\^M }
17928   }
17929   \cs_new_protected:Npn \_regex_prop_v:
17930     { \_regex_item_caseful_range:nn { '\^J } { '\^M } } % lf, vtab, ff, cr
17931   \cs_new_protected:Npn \_regex_prop_w:
17932     {
17933       \_regex_item_caseful_range:nn { 'a } { 'z }
17934       \_regex_item_caseful_range:nn { 'A } { 'Z }
17935       \_regex_item_caseful_range:nn { '0 } { '9 }
17936       \_regex_item_caseful_equal:n { '_' }
17937     }
17938   \cs_new_protected:Npn \_regex_prop_N:
17939     {
17940       \_regex_item_reverse:n
17941       { \_regex_item_caseful_equal:n { '\^J } }
17942     }

```

(End definition for _regex_prop_d: and others.)

```

\_regex_posix_alnum: POSIX properties. No surprise.
\_regex_posix_alpha: 17943 \cs_new_protected:Npn \_regex_posix_alnum:
\_regex_posix_ascii: 17944   { \_regex_posix_alpha: \_regex_posix_digit: }
\_regex_posix_blank: 17945 \cs_new_protected:Npn \_regex_posix_alpha:
\_regex_posix_cntrl: 17946   { \_regex_posix_lower: \_regex_posix_upper: }
\_regex_posix_digit: 17947 \cs_new_protected:Npn \_regex_posix_ascii:
\_regex_posix_graph: 17948   {
\_regex_posix_lower: 17949     \_regex_item_caseful_range:nn
\_regex_posix_print: 17950       \c__regex_ascii_min_int
\_regex_posix_punct: 17951       \c__regex_ascii_max_int
17952   }
17953 \cs_new_eq:NN \_regex_posix_blank: \_regex_prop_h:
17954 \cs_new_protected:Npn \_regex_posix_cntrl:
17955   {
17956     \_regex_item_caseful_range:nn
17957       \c__regex_ascii_min_int
17958       \c__regex_ascii_max_control_int
17959     \_regex_item_caseful_equal:n \c__regex_ascii_max_int
17960   }
17961 \cs_new_eq:NN \_regex_posix_digit: \_regex_prop_d:
17962 \cs_new_protected:Npn \_regex_posix_graph:
17963   { \_regex_item_caseful_range:nn { '!' } { '~ } }
17964 \cs_new_protected:Npn \_regex_posix_lower:
17965   { \_regex_item_caseful_range:nn { 'a } { 'z } }
17966 \cs_new_protected:Npn \_regex_posix_print:
17967   { \_regex_item_caseful_range:nn { '\' } { '~ } }
17968 \cs_new_protected:Npn \_regex_posix_punct:
17969   {
17970     \_regex_item_caseful_range:nn { '!' } { '/' }
17971     \_regex_item_caseful_range:nn { ':' } { '@' }
17972     \_regex_item_caseful_range:nn { '[' } { '[' }
17973     \_regex_item_caseful_range:nn { '\' } { '~ }

```

```

17974 }
17975 \cs_new_protected:Npn \__regex_posix_space:
17976 {
17977   \__regex_item_caseful_equal:n { '\ }
17978   \__regex_item_caseful_range:nn { '\^^I } { '\^^M }
17979 }
17980 \cs_new_protected:Npn \__regex_posix_upper:
17981 { \__regex_item_caseful_range:nn { 'A } { 'Z } }
17982 \cs_new_eq:NN \__regex_posix_word: \__regex_prop_w:
17983 \cs_new_protected:Npn \__regex_posix_xdigit:
17984 {
17985   \__regex_posix_digit:
17986   \__regex_item_caseful_range:nn { 'A } { 'F }
17987   \__regex_item_caseful_range:nn { 'a } { 'f }
17988 }

```

(End definition for `__regex_posix_alnum:` and others.)

36.2.4 Simple character escape

Before actually parsing the regular expression or the replacement text, we go through them once, converting `\n` to the character 10, *etc.* In this pass, we also convert any special character (`*`, `?`, `{`, *etc.*) or escaped alphanumeric character into a marker indicating that this was a special sequence, and replace escaped special characters and non-escaped alphanumeric characters by markers indicating that those were “raw” characters. The rest of the code can then avoid caring about escaping issues (those can become quite complex to handle in combination with ranges in character classes).

Usage: `__regex_escape_use:nnnn` *<inline 1>* *<inline 2>* *<inline 3>* *{<token list>}*
The *<token list>* is converted to a string, then read from left to right, interpreting backslashes as escaping the next character. Unescaped characters are fed to the function *<inline 1>*, and escaped characters are fed to the function *<inline 2>* within an `x`-expansion context (typically those functions perform some tests on their argument to decide how to output them). The escape sequences `\a`, `\e`, `\f`, `\n`, `\r`, `\t` and `\x` are recognized, and those are replaced by the corresponding character, then fed to *<inline 3>*. The result is then left in the input stream. Spaces are ignored unless escaped.

The conversion is mostly done within an `x`-expanding assignment, except for the `\x` escape sequence, which is not amenable to that in general. For this, we use the general framework of `__tl_build:Nw`.

`__regex_escape_use:nnnn` The result is built in `\l__regex_internal_a_tl`, which is then left in the input stream. Go through #4 once, applying #1, #2, or #3 as relevant to each character (after de-escaping it). Note that we cannot replace `\tl_set:Nx` and `__tl_build_one:o` by a single call to `__tl_build_one:x`, because the `x`-expanding assignment may be interrupted by `\x`.

```

17989 \__debug_patch:nnNpn
17990 {
17991   \__debug_trace_push:nnN { regex } { 1 } \__regex_escape_use:nnnn
17992   \__tl_build:Nw \l__regex_internal_a_tl
17993   \__tl_build_one:n { \__debug_trace_pop:nnN { regex } { 1 } \__regex_escape_use:nnnn }
17994   \use_none:nn
17995 }
17996 { }
17997 \cs_new_protected:Npn \__regex_escape_use:nnnn #1#2#3#4

```

```

17998 {
17999     \__tl_build:Nw \l__regex_internal_a_tl
18000     \cs_set:Npn \__regex_escape_unescaped:N ##1 { #1 }
18001     \cs_set:Npn \__regex_escape_escaped:N ##1 { #2 }
18002     \cs_set:Npn \__regex_escape_raw:N ##1 { #3 }
18003     \__regex_standard_escapechar:
18004     \tl_gset:Nx \g__regex_internal_tl { \__str_to_other_fast:n {#4} }
18005     \tl_set:Nx \l__regex_internal_b_tl
18006     {
18007         \exp_after:wN \__regex_escape_loop:N \g__regex_internal_tl
18008         { break } \__prg_break_point:
18009     }
18010     \__tl_build_one:o \l__regex_internal_b_tl
18011     \__tl_build_end:
18012     \l__regex_internal_a_tl
18013 }

```

(End definition for __regex_escape_use:nnnn.)

__regex_escape_loop:N __regex_escape_loop:N reads one character: if it is special (space, backslash, or end-marker), perform the associated action, otherwise it is simply an unescaped character. After a backslash, the same is done, but unknown characters are “escaped”.

```

18014 \cs_new:Npn \__regex_escape_loop:N #1
18015 {
18016     \cs_if_exist_use:cF { __regex_escape\_token_to_str:N #1:w }
18017     { \__regex_escape_unescaped:N #1 }
18018     \__regex_escape_loop:N
18019 }
18020 \cs_new:cpn { __regex_escape\_c_backslash_str :w }
18021     \__regex_escape_loop:N #1
18022 {
18023     \cs_if_exist_use:cF { __regex_escape\_token_to_str:N #1:w }
18024     { \__regex_escape_escaped:N #1 }
18025     \__regex_escape_loop:N
18026 }

```

(End definition for __regex_escape_loop:N and __regex_escape_w.)

__regex_escape_unescaped:N Those functions are never called before being given a new meaning, so their definitions here don’t matter.

```

\__regex_escape_escaped:N
\__regex_escape_raw:N
18027 \cs_new_eq:NN \__regex_escape_unescaped:N ?
18028 \cs_new_eq:NN \__regex_escape_escaped:N ?
18029 \cs_new_eq:NN \__regex_escape_raw:N ?

```

(End definition for __regex_escape_unescaped:N, __regex_escape_escaped:N, and __regex_escape_raw:N.)

__regex_escape_break:w The loop is ended upon seeing the end-marker “break”, with an error if the string ended in a backslash. Spaces are ignored, and \a, \e, \f, \n, \r, \t take their meaning here.

```

\__regex_escape_/break:w
\__regex_escape_/a:w
\__regex_escape_/e:w
\__regex_escape_/f:w
\__regex_escape_/n:w
\__regex_escape_/r:w
\__regex_escape_/t:w
\__regex_escape_\_w
18030 \cs_new_eq:NN \__regex_escape_break:w \__prg_break:
18031 \cs_new:cpn { __regex_escape_/break:w }
18032 {
18033     \if_false: { \fi: }
18034     \__msg_kernel_error:nn { kernel } { trailing-backslash }

```

```

18035     \exp_after:wN \use_none:n \exp_after:wN { \if_false: } \fi:
18036   }
18037   \cs_new:cpn { __regex_escape_~:w } { }
18038   \cs_new:cpx { __regex_escape_/a:w }
18039     { \exp_not:N __regex_escape_raw:N \iow_char:N ^^G }
18040   \cs_new:cpx { __regex_escape_/t:w }
18041     { \exp_not:N __regex_escape_raw:N \iow_char:N ^^I }
18042   \cs_new:cpx { __regex_escape_/n:w }
18043     { \exp_not:N __regex_escape_raw:N \iow_char:N ^^J }
18044   \cs_new:cpx { __regex_escape_/f:w }
18045     { \exp_not:N __regex_escape_raw:N \iow_char:N ^^L }
18046   \cs_new:cpx { __regex_escape_/r:w }
18047     { \exp_not:N __regex_escape_raw:N \iow_char:N ^^M }
18048   \cs_new:cpx { __regex_escape_/e:w }
18049     { \exp_not:N __regex_escape_raw:N \iow_char:N ^^[ }

```

(End definition for `__regex_escape_break:w` and others.)

```

__regex_escape_/x:w
__regex_escape_x_end:w
__regex_escape_x_large:n

```

When `\x` is encountered, `__regex_escape_x_test:N` is responsible for grabbing some hexadecimal digits, and feeding the result to `__regex_escape_x_end:w`. If the number is too big interrupt the assignment and produce an error, otherwise call `__regex_escape_raw:N` on the corresponding character token.

```

18050 \cs_new:cpn { __regex_escape_/x:w } \__regex_escape_loop:N
18051 {
18052   \exp_after:wN __regex_escape_x_end:w
18053   __int_value:w "0 __regex_escape_x_test:N
18054 }
18055 \cs_new:Npn __regex_escape_x_end:w #1 ;
18056 {
18057   \int_compare:nNnTF {#1} > \c_max_char_int
18058   {
18059     \if_false: { \fi: }
18060     __tl_build_one:o \l__regex_internal_b_tl
18061     __msg_kernel_error:nx { kernel } { x-overflow } {#1}
18062     \tl_set:Nx \l__regex_internal_b_tl
18063       { \if_false: } \fi:
18064   }
18065   {
18066     \exp_last_unbraced:Nf __regex_escape_raw:N
18067     { \char_generate:nn {#1} { 12 } }
18068   }
18069 }

```

(End definition for `__regex_escape_/x:w`, `__regex_escape_x_end:w`, and `__regex_escape_x_large:n`.)

```

__regex_escape_x_test:N
__regex_escape_x_testii:N

```

Find out whether the first character is a left brace (allowing any number of hexadecimal digits), or not (allowing up to two hexadecimal digits). We need to check for the end-of-string marker. Eventually, call either `__regex_escape_x_loop:N` or `__regex_escape_x:N`.

```

18070 \cs_new:Npn __regex_escape_x_test:N #1
18071 {
18072   \str_if_eq_x:nnTF {#1} { break } { ; }
18073   {
18074     \if_charcode:w \c_space_token #1

```

```

18075         \exp_after:wN \_\_regex_escape_x_test:N
18076     \else:
18077         \exp_after:wN \_\_regex_escape_x_testii:N
18078         \exp_after:wN #1
18079     \fi:
18080 }
18081 }
18082 \cs_new:Npn \_\_regex_escape_x_testii:N #1
18083 {
18084     \if_charcode:w \c_left_brace_str #1
18085         \exp_after:wN \_\_regex_escape_x_loop:N
18086     \else:
18087         \_\_regex_hexadecimal_use:NTF #1
18088         { \exp_after:wN \_\_regex_escape_x:N }
18089         { ; \exp_after:wN \_\_regex_escape_loop:N \exp_after:wN #1 }
18090     \fi:
18091 }

```

(End definition for __regex_escape_x_test:N and __regex_escape_x_testii:N.)

__regex_escape_x:N This looks for the second digit in the unbraced case.

```

18092 \cs_new:Npn \_\_regex_escape_x:N #1
18093 {
18094     \str_if_eq_x:nnTF {#1} { break } { ; }
18095     {
18096         \_\_regex_hexadecimal_use:NTF #1
18097         { ; \_\_regex_escape_loop:N }
18098         { ; \_\_regex_escape_loop:N #1 }
18099     }
18100 }

```

(End definition for __regex_escape_x:N.)

__regex_escape_x_loop:N Grab hexadecimal digits, skip spaces, and at the end, check that there is a right brace,
 __regex_escape_x_loop_error: otherwise raise an error outside the assignment.

```

18101 \cs_new:Npn \_\_regex_escape_x_loop:N #1
18102 {
18103     \str_if_eq_x:nnTF {#1} { break }
18104     { ; \_\_regex_escape_x_loop_error:n { } {#1} }
18105     {
18106         \_\_regex_hexadecimal_use:NTF #1
18107         { \_\_regex_escape_x_loop:N }
18108         {
18109             \token_if_eq_charcode:NNTF \c_space_token #1
18110             { \_\_regex_escape_x_loop:N }
18111             {
18112                 ;
18113                 \exp_after:wN
18114                 \token_if_eq_charcode:NNTF \c_right_brace_str #1
18115                 { \_\_regex_escape_loop:N }
18116                 { \_\_regex_escape_x_loop_error:n {#1} }
18117             }
18118         }
18119     }

```

```

18120 }
18121 \cs_new:Npn \__regex_escape_x_loop_error:n #1
18122 {
18123   \if_false: { \fi: }
18124   \__tl_build_one:o \l__regex_internal_b_tl
18125   \__msg_kernel_error:nnx { kernel } { x-missing-rbrace } {#1}
18126   \tl_set:Nx \l__regex_internal_b_tl
18127     { \if_false: } \fi: \__regex_escape_loop:N #1
18128 }

```

(End definition for __regex_escape_x_loop:N and __regex_escape_x_loop_error:.)

__regex_hexadecimal_use:NTF **T**_E**X** detects uppercase hexadecimal digits for us but not the lowercase letters, which we need to detect and replace by their uppercase counterpart.

```

18129 \prg_new_conditional:Npnn \__regex_hexadecimal_use:N #1 { TF }
18130 {
18131   \if_int_compare:w 1 < "1 \token_to_str:N #1 \exp_stop_f:
18132     #1 \prg_return_true:
18133   \else:
18134     \if_case:w
18135       \__int_eval:n { \exp_after:wN ‘ \token_to_str:N #1 - ‘a }
18136       A
18137     \or: B
18138     \or: C
18139     \or: D
18140     \or: E
18141     \or: F
18142     \else:
18143       \prg_return_false:
18144       \exp_after:wN \use_none:n
18145     \fi:
18146     \prg_return_true:
18147   \fi:
18148 }

```

(End definition for __regex_hexadecimal_use:NTF.)

__regex_char_if_alphanumeric:NTF These two tests are used in the first pass when parsing a regular expression. That pass is responsible for finding escaped and non-escaped characters, and recognizing which ones have special meanings and which should be interpreted as “raw” characters. Namely,

- alphanumeric characters are “raw” if they are not escaped, and may have a special meaning when escaped;
- non-alphanumeric printable ascii characters are “raw” if they are escaped, and may have a special meaning when not escaped;
- characters other than printable ascii are always “raw”.

The code is ugly, and highly based on magic numbers and the ascii codes of characters. This is mostly unavoidable for performance reasons. Maybe the tests can be optimized a little bit more. Here, “alphanumeric” means 0–9, A–Z, a–z; “special” character means non-alphanumeric but printable ascii, from space (hex 20) to del (hex 7E).

```

18149 \prg_new_conditional:Npnn \__regex_char_if_special:N #1 { TF }
18150 {

```

```

18151 \if_int_compare:w '#1 > 'Z \exp_stop_f:
18152 \if_int_compare:w '#1 > 'z \exp_stop_f:
18153 \if_int_compare:w '#1 < \c__regex_ascii_max_int
18154 \prg_return_true: \else: \prg_return_false: \fi:
18155 \else:
18156 \if_int_compare:w '#1 < 'a \exp_stop_f:
18157 \prg_return_true: \else: \prg_return_false: \fi:
18158 \fi:
18159 \else:
18160 \if_int_compare:w '#1 > '9 \exp_stop_f:
18161 \if_int_compare:w '#1 < 'A \exp_stop_f:
18162 \prg_return_true: \else: \prg_return_false: \fi:
18163 \else:
18164 \if_int_compare:w '#1 < '0 \exp_stop_f:
18165 \if_int_compare:w '#1 < '\ \exp_stop_f:
18166 \prg_return_false: \else: \prg_return_true: \fi:
18167 \else: \prg_return_false: \fi:
18168 \fi:
18169 \fi:
18170 }
18171 \prg_new_conditional:Npnn \__regex_char_if_alphanumeric:N #1 { TF }
18172 {
18173 \if_int_compare:w '#1 > 'Z \exp_stop_f:
18174 \if_int_compare:w '#1 > 'z \exp_stop_f:
18175 \prg_return_false:
18176 \else:
18177 \if_int_compare:w '#1 < 'a \exp_stop_f:
18178 \prg_return_false: \else: \prg_return_true: \fi:
18179 \fi:
18180 \else:
18181 \if_int_compare:w '#1 > '9 \exp_stop_f:
18182 \if_int_compare:w '#1 < 'A \exp_stop_f:
18183 \prg_return_false: \else: \prg_return_true: \fi:
18184 \else:
18185 \if_int_compare:w '#1 < '0 \exp_stop_f:
18186 \prg_return_false: \else: \prg_return_true: \fi:
18187 \fi:
18188 \fi:
18189 }

```

(End definition for `__regex_char_if_alphanumeric:N` and `__regex_char_if_special:N`.)

36.3 Compiling

A regular expression starts its life as a string of characters. In this section, we convert it to internal instructions, resulting in a “compiled” regular expression. This compiled expression is then turned into states of an automaton in the building phase. Compiled regular expressions consist of the following:

- `__regex_class:NnnnN` $\langle \text{boolean} \rangle$ $\{ \langle \text{tests} \rangle \}$ $\{ \langle \text{min} \rangle \}$ $\{ \langle \text{more} \rangle \}$ $\langle \text{lazyness} \rangle$
- `__regex_group:nnnN` $\{ \langle \text{branches} \rangle \}$ $\{ \langle \text{min} \rangle \}$ $\{ \langle \text{more} \rangle \}$ $\langle \text{lazyness} \rangle$, also `__regex_group_no_capture:nnnN` and `__regex_group_resetting:nnnN` with the same syntax.

- `__regex_branch:n` $\{\langle contents \rangle\}$
- `__regex_command_K:`
- `__regex_assertion:Nn` $\langle boolean \rangle \{\langle assertion\ test \rangle\}$, where the $\langle assertion\ test \rangle$ is `__regex_b_test:` or $\{__regex_anchor:N \langle integer \rangle\}$

Tests can be the following:

- `__regex_item_caseful_equal:n` $\{\langle char\ code \rangle\}$
- `__regex_item_caseless_equal:n` $\{\langle char\ code \rangle\}$
- `__regex_item_caseful_range:nn` $\{\langle min \rangle\} \{\langle max \rangle\}$
- `__regex_item_caseless_range:nn` $\{\langle min \rangle\} \{\langle max \rangle\}$
- `__regex_item_catcode:nT` $\{\langle catcode\ bitmap \rangle\} \{\langle tests \rangle\}$
- `__regex_item_catcode_reverse:nT` $\{\langle catcode\ bitmap \rangle\} \{\langle tests \rangle\}$
- `__regex_item_reverse:n` $\{\langle tests \rangle\}$
- `__regex_item_exact:nn` $\{\langle catcode \rangle\} \{\langle char\ code \rangle\}$
- `__regex_item_exact_cs:n` $\{\langle csnames \rangle\}$, more precisely given as $\langle csname \rangle \backslash scan_stop: \langle csname \rangle \backslash scan_stop: \langle csname \rangle$ and so on in a brace group.
- `__regex_item_cs:n` $\{\langle compiled\ regex \rangle\}$

36.3.1 Variables used when compiling

`\l__regex_group_level_int` We make sure to open the same number of groups as we close.

```
18190 \int_new:N \l__regex_group_level_int
```

(End definition for `\l__regex_group_level_int`.)

`\l__regex_mode_int` While compiling, ten modes are recognized, labelled $-63, -23, -6, -2, 0, 2, 3, 6, 23, 63$.
`\c__regex_cs_in_class_mode_int` See section 36.3.3. We only define some of these as constants.

```
18191 \int_new:N \l__regex_mode_int
18192 \int_const:Nn \c__regex_cs_in_class_mode_int { -6 }
18193 \int_const:Nn \c__regex_cs_mode_int { -2 }
18194 \int_const:Nn \c__regex_outer_mode_int { 0 }
18195 \int_const:Nn \c__regex_catcode_mode_int { 2 }
18196 \int_const:Nn \c__regex_class_mode_int { 3 }
18197 \int_const:Nn \c__regex_catcode_in_class_mode_int { 6 }
```

(End definition for `\l__regex_mode_int` and others.)

`\l__regex_catcodes_int` We wish to allow constructions such as `\c[^BE](. . \cL[a-z] . .)`, where the outer catcode test applies to the whole group, but is superseded by the inner catcode test. For this to work, we need to keep track of lists of allowed category codes: `\l__regex_catcodes_int` and `\l__regex_default_catcodes_int` are bitmaps, sums of 4^c , for all allowed catcodes c . The latter is local to each capturing group, and we reset `\l__regex_catcodes_int` to that value after each character or class, changing it only when encountering a `\c` escape.

The boolean records whether the list of categories of a catcode test has to be inverted: compare `\c[^BE]` and `\c[BE]`.

```
18198 \int_new:N \l__regex_catcodes_int
18199 \int_new:N \l__regex_default_catcodes_int
18200 \bool_new:N \l__regex_catcodes_bool
```

(End definition for `\l__regex_catcodes_int`, `\l__regex_default_catcodes_int`, and `\l__regex_catcodes_bool`.)

<code>\c__regex_catcode_C_int</code>	Constants: 4^c for each category, and the sum of all powers of 4.
<code>\c__regex_catcode_B_int</code>	18201 <code>\int_const:Nn \c__regex_catcode_C_int { "1 }</code>
<code>\c__regex_catcode_E_int</code>	18202 <code>\int_const:Nn \c__regex_catcode_B_int { "4 }</code>
<code>\c__regex_catcode_M_int</code>	18203 <code>\int_const:Nn \c__regex_catcode_E_int { "10 }</code>
<code>\c__regex_catcode_T_int</code>	18204 <code>\int_const:Nn \c__regex_catcode_M_int { "40 }</code>
<code>\c__regex_catcode_P_int</code>	18205 <code>\int_const:Nn \c__regex_catcode_T_int { "100 }</code>
<code>\c__regex_catcode_U_int</code>	18206 <code>\int_const:Nn \c__regex_catcode_P_int { "1000 }</code>
<code>\c__regex_catcode_D_int</code>	18207 <code>\int_const:Nn \c__regex_catcode_U_int { "4000 }</code>
<code>\c__regex_catcode_S_int</code>	18208 <code>\int_const:Nn \c__regex_catcode_D_int { "10000 }</code>
<code>\c__regex_catcode_L_int</code>	18209 <code>\int_const:Nn \c__regex_catcode_S_int { "100000 }</code>
<code>\c__regex_catcode_O_int</code>	18210 <code>\int_const:Nn \c__regex_catcode_L_int { "400000 }</code>
<code>\c__regex_catcode_A_int</code>	18211 <code>\int_const:Nn \c__regex_catcode_O_int { "1000000 }</code>
<code>\c__regex_all_catcodes_int</code>	18212 <code>\int_const:Nn \c__regex_catcode_A_int { "4000000 }</code>
	18213 <code>\int_const:Nn \c__regex_all_catcodes_int { "5515155 }</code>

(End definition for `\c__regex_catcode_C_int` and others.)

<code>\l__regex_internal_regex</code>	The compilation step stores its result in this variable.
---------------------------------------	--

```
18214 \cs_new_eq:NN \l__regex_internal_regex \c__regex_no_match_regex
```

(End definition for `\l__regex_internal_regex`.)

<code>\l__regex_show_prefix_seq</code>	This sequence holds the prefix that makes up the line displayed to the user. The various items must be removed from the right, which is tricky with a token list, hence we use a sequence.
--	--

```
18215 \seq_new:N \l__regex_show_prefix_seq
```

(End definition for `\l__regex_show_prefix_seq`.)

<code>\l__regex_show_lines_int</code>	A hack. To know whether a given class has a single item in it or not, we count the number of lines when showing the class.
---------------------------------------	--

```
18216 \int_new:N \l__regex_show_lines_int
```

(End definition for `\l__regex_show_lines_int`.)

36.3.2 Generic helpers used when compiling

<code>__regex_get_digits:NTFw</code>	If followed by some raw digits, collect them one by one in the integer variable #1, and take the <code>true</code> branch. Otherwise, take the <code>false</code> branch.
<code>__regex_get_digits_loop:w</code>	

```
18217 \cs_new_protected:Npn \__regex_get_digits:NTFw #1#2#3#4#5
18218 {
18219   \__regex_if_raw_digit:NNTF #4 #5
18220   { #1 = #5 \__regex_get_digits_loop:nw {#2} }
18221   { #3 #4 #5 }
18222 }
```

```

18223 \cs_new:Npn \__regex_get_digits_loop:nw #1#2#3
18224 {
18225     \__regex_if_raw_digit:NNTF #2 #3
18226     { #3 \__regex_get_digits_loop:nw {#1} }
18227     { \scan_stop: #1 #2 #3 }
18228 }

```

(End definition for `__regex_get_digits:NNTFw` and `__regex_get_digits_loop:w`.)

`__regex_if_raw_digit:NNTF` Test used when grabbing digits for the `{m,n}` quantifier. It only accepts non-escaped digits.

```

18229 \prg_new_conditional:Npnn \__regex_if_raw_digit:NN #1#2 { TF }
18230 {
18231     \if_meaning:w \__regex_compile_raw:N #1
18232     \if_int_compare:w 1 < 1 #2 \exp_stop_f:
18233     \prg_return_true:
18234     \else:
18235     \prg_return_false:
18236     \fi:
18237     \else:
18238     \prg_return_false:
18239     \fi:
18240 }

```

(End definition for `__regex_if_raw_digit:NNTF`.)

36.3.3 Mode

When compiling the NFA corresponding to a given regex string, we can be in ten distinct modes, which we label by some magic numbers:

- 6 `[\c{...}]` control sequence in a class,
- 2 `\c{...}` control sequence,
- 0 ... outer,
- 2 `\c...` catcode test,
- 6 `[\c...]` catcode test in a class,
- 63 `[\c{[...]}]` class inside mode -6,
- 23 `\c{[...]}` class inside mode -2,
- 3 `[...]` class inside mode 0,
- 23 `\c[...]` class inside mode 2,
- 63 `[\c[...]]` class inside mode 6.

This list is exhaustive, because `\c` escape sequences cannot be nested, and character classes cannot be nested directly. The choice of numbers is such as to optimize the most useful tests, and make transitions from one mode to another as simple as possible.

- Even modes mean that we are not directly in a character class. In this case, a left bracket appends 3 to the mode. In a character class, a right bracket changes the mode as $m \rightarrow (m - 15)/13$, truncated.
- Grouping, assertion, and anchors are allowed in non-positive even modes (0, -2, -6), and do not change the mode. Otherwise, they trigger an error.
- A left bracket is special in even modes, appending 3 to the mode; in those modes, quantifiers and the dot are recognized, and the right bracket is normal. In odd modes (within classes), the left bracket is normal, but the right bracket ends the class, changing the mode from m to $(m - 15)/13$, truncated; also, ranges are recognized.
- In non-negative modes, left and right braces are normal. In negative modes, however, left braces trigger a warning; right braces end the control sequence, going from -2 to 0 or -6 to 3, with error recovery for odd modes.
- Properties (such as the `\d` character class) can appear in any mode.

`_regex_if_in_class:TF` Test whether we are directly in a character class (at the innermost level of nesting). There, many escape sequences are not recognized, and special characters are normal. Also, for every raw character, we must look ahead for a possible raw dash.

```

18241 \cs_new:Npn \_regex_if_in_class:TF
18242   {
18243     \if_int_odd:w \l__regex_mode_int
18244       \exp_after:wN \use_i:nn
18245     \else:
18246       \exp_after:wN \use_ii:nn
18247     \fi:
18248   }

```

(End definition for `_regex_if_in_class:TF`.)

`_regex_if_in_cs:TF` Right braces are special only directly inside control sequences (at the inner-most level of nesting, not counting groups).

```

18249 \cs_new:Npn \_regex_if_in_cs:TF
18250   {
18251     \if_int_odd:w \l__regex_mode_int
18252       \exp_after:wN \use_ii:nn
18253     \else:
18254       \if_int_compare:w \l__regex_mode_int < \c__regex_outer_mode_int
18255         \exp_after:wN \exp_after:wN \exp_after:wN \use_i:nn
18256       \else:
18257         \exp_after:wN \exp_after:wN \exp_after:wN \use_ii:nn
18258       \fi:
18259     \fi:
18260   }

```

(End definition for `_regex_if_in_cs:TF`.)

`_regex_if_in_class_or_catcode:TF` Assertions are only allowed in modes 0, -2, and -6, *i.e.*, even, non-positive modes.

```

18261 \cs_new:Npn \_regex_if_in_class_or_catcode:TF
18262   {
18263     \if_int_odd:w \l__regex_mode_int

```

```

18264     \exp_after:wN \use_i:nn
18265 \else:
18266     \if_int_compare:w \l__regex_mode_int > \c__regex_outer_mode_int
18267     \exp_after:wN \exp_after:wN \exp_after:wN \use_i:nn
18268 \else:
18269     \exp_after:wN \exp_after:wN \exp_after:wN \use_ii:nn
18270 \fi:
18271 \fi:
18272 }

```

(End definition for __regex_if_in_class_or_catcode:TF.)

__regex_if_within_catcode:TF This test takes the true branch if we are in a catcode test, either immediately following it (modes 2 and 6) or in a class on which it applies (modes 23 and 63). This is used to tweak how left brackets behave in modes 2 and 6.

```

18273 \cs_new:Npn \__regex_if_within_catcode:TF
18274 {
18275     \if_int_compare:w \l__regex_mode_int > \c__regex_outer_mode_int
18276     \exp_after:wN \use_i:nn
18277 \else:
18278     \exp_after:wN \use_ii:nn
18279 \fi:
18280 }

```

(End definition for __regex_if_within_catcode:TF.)

__regex_chk_c_allowed:T The \c escape sequence is only allowed in modes 0 and 3, *i.e.*, not within any other \c escape sequence.

```

18281 \cs_new_protected:Npn \__regex_chk_c_allowed:T
18282 {
18283     \if_int_compare:w \l__regex_mode_int = \c__regex_outer_mode_int
18284     \exp_after:wN \use:n
18285 \else:
18286     \if_int_compare:w \l__regex_mode_int = \c__regex_class_mode_int
18287     \exp_after:wN \exp_after:wN \exp_after:wN \use:n
18288 \else:
18289     \__msg_kernel_error:nn { kernel } { c-bad-mode }
18290     \exp_after:wN \exp_after:wN \exp_after:wN \use_none:n
18291 \fi:
18292 \fi:
18293 }

```

(End definition for __regex_chk_c_allowed:T.)

__regex_mode_quit_c: This function changes the mode as it is needed just after a catcode test.

```

18294 \cs_new_protected:Npn \__regex_mode_quit_c:
18295 {
18296     \if_int_compare:w \l__regex_mode_int = \c__regex_catcode_mode_int
18297     \int_set_eq:NN \l__regex_mode_int \c__regex_outer_mode_int
18298 \else:
18299     \if_int_compare:w \l__regex_mode_int = \c__regex_catcode_in_class_mode_int
18300     \int_set_eq:NN \l__regex_mode_int \c__regex_class_mode_int
18301 \fi:
18302 \fi:
18303 }

```

(End definition for __regex_mode_quit_c:.)

36.3.4 Framework

`__regex_compile:w` Used when compiling a user regex or a regex for the `\c{...}` escape sequence within another regex. Start building a token list within a group (with x-expansion at the outset), and set a few variables (group level, catcodes), then start the first branch. At the end, make sure there are no dangling classes nor groups, close the last branch: we are done building `l__regex_internal_regex`.

```

18304 \cs_new_protected:Npn \__regex_compile:w
18305 {
18306   \__tl_build_x:Nw \l__regex_internal_regex
18307   \int_zero:N \l__regex_group_level_int
18308   \int_set_eq:NN \l__regex_default_catcodes_int \c__regex_all_catcodes_int
18309   \int_set_eq:NN \l__regex_catcodes_int \l__regex_default_catcodes_int
18310   \cs_set:Npn \__regex_item_equal:n { \__regex_item_caseful_equal:n }
18311   \cs_set:Npn \__regex_item_range:nn { \__regex_item_caseful_range:nn }
18312   \__tl_build_one:n { \__regex_branch:n { \if_false: } \fi: }
18313 }
18314 \cs_new_protected:Npn \__regex_compile_end:
18315 {
18316   \__regex_if_in_class:TF
18317   {
18318     \__msg_kernel_error:nn { kernel } { missing-rbrack }
18319     \use:c { __regex_compile_]: }
18320     \prg_do_nothing: \prg_do_nothing:
18321   }
18322   { }
18323   \if_int_compare:w \l__regex_group_level_int > 0 \exp_stop_f:
18324     \__msg_kernel_error:nnx { kernel } { missing-rparen }
18325     { \int_use:N \l__regex_group_level_int }
18326     \prg_replicate:nn
18327     { \l__regex_group_level_int }
18328     {
18329       \__tl_build_one:n
18330       {
18331         \if_false: { \fi: }
18332         \if_false: { \fi: } { 1 } { 0 } \c_true_bool
18333       }
18334       \__tl_build_end:
18335       \__tl_build_one:o \l__regex_internal_regex
18336     }
18337     \fi:
18338     \__tl_build_one:n { \if_false: { \fi: } }
18339     \__tl_build_end:
18340   }

```

(End definition for `__regex_compile:w` and `__regex_compile_end:.`)

`__regex_compile:n` The compilation is done between `__regex_compile:w` and `__regex_compile_end:`, starting in mode 0. Then `__regex_escape_use:nnnn` distinguishes special characters, escaped alphanumerics, and raw characters, interpreting `\a`, `\x` and other sequences. The 4 trailing `\prg_do_nothing:` are needed because some functions defined later look up to 4 tokens ahead. Before ending, make sure that any `\c{...}` is properly closed. No need to check that brackets are closed properly since `__regex_compile_end:` does that. However, catch the case of a trailing `\cL` construction.

```

18341 \cs_new_protected:Npn \__regex_compile:n #1
18342 {
18343   \__regex_compile:w
18344   \__regex_standard_escapechar:
18345   \int_set_eq:NN \l__regex_mode_int \c__regex_outer_mode_int
18346   \__regex_escape_use:nnnn
18347   {
18348     \__regex_char_if_special:NTF ##1
18349     \__regex_compile_special:N \__regex_compile_raw:N ##1
18350   }
18351   {
18352     \__regex_char_if_alphanumeric:NTF ##1
18353     \__regex_compile_escaped:N \__regex_compile_raw:N ##1
18354   }
18355   { \__regex_compile_raw:N ##1 }
18356   { #1 }
18357   \prg_do_nothing: \prg_do_nothing:
18358   \prg_do_nothing: \prg_do_nothing:
18359   \int_compare:nNnT \l__regex_mode_int = \c__regex_catcode_mode_int
18360   { \__msg_kernel_error:nn { kernel } { c-trailing } }
18361   \int_compare:nNnT \l__regex_mode_int < \c__regex_outer_mode_int
18362   {
18363     \__msg_kernel_error:nn { kernel } { c-missing-rbrace }
18364     \__regex_compile_end_cs:
18365     \prg_do_nothing: \prg_do_nothing:
18366     \prg_do_nothing: \prg_do_nothing:
18367   }
18368   \__regex_compile_end:
18369 }

```

(End definition for __regex_compile:n.)

__regex_compile_escaped:N If the special character or escaped alphanumeric has a particular meaning in regexes, the corresponding function is used. Otherwise, it is interpreted as a raw character. We distinguish special characters from escaped alphanumeric characters because they behave differently when appearing as an end-point of a range.

```

18370 \cs_new_protected:Npn \__regex_compile_special:N #1
18371 {
18372   \cs_if_exist_use:cF { __regex_compile_#1: }
18373   { \__regex_compile_raw:N #1 }
18374 }
18375 \cs_new_protected:Npn \__regex_compile_escaped:N #1
18376 {
18377   \cs_if_exist_use:cF { __regex_compile_/#1: }
18378   { \__regex_compile_raw:N #1 }
18379 }

```

(End definition for __regex_compile_escaped:N and __regex_compile_special:N.)

__regex_compile_one:x This is used after finding one “test”, such as \d, or a raw character. If that followed a catcode test (e.g., \cL), then restore the mode. If we are not in a class, then the test is “standalone”, and we need to add __regex_class:NnnnN and search for quantifiers. In any case, insert the test, possibly together with a catcode test if appropriate.

```

18380 \cs_new_protected:Npn \__regex_compile_one:x #1

```

```

18381 {
18382   \__regex_mode_quit_c:
18383   \__regex_if_in_class:TF { }
18384   {
18385     \__tl_build_one:n
18386     { \__regex_class:NnnnN \c_true_bool { \if_false: } \fi: }
18387   }
18388   \__tl_build_one:x
18389   {
18390     \if_int_compare:w \l__regex_catcodes_int < \c__regex_all_catcodes_int
18391     \__regex_item_catcode:nT { \int_use:N \l__regex_catcodes_int }
18392     { \exp_not:N \exp_not:n {#1} }
18393     \else:
18394     \exp_not:N \exp_not:n {#1}
18395     \fi:
18396   }
18397   \int_set_eq:NN \l__regex_catcodes_int \l__regex_default_catcodes_int
18398   \__regex_if_in_class:TF { } { \__regex_compile_quantifier:w }
18399 }

```

(End definition for __regex_compile_one:x.)

__regex_compile_abort_tokens:n This function places the collected tokens back in the input stream, each as a raw character.
 __regex_compile_abort_tokens:x Spaces are not preserved.

```

18400 \cs_new_protected:Npn \__regex_compile_abort_tokens:n #1
18401 {
18402   \use:x
18403   {
18404     \exp_args:No \tl_map_function:nN { \tl_to_str:n {#1} }
18405     \__regex_compile_raw:N
18406   }
18407 }
18408 \cs_generate_variant:Nn \__regex_compile_abort_tokens:n { x }

```

(End definition for __regex_compile_abort_tokens:n.)

36.3.5 Quantifiers

__regex_compile_quantifier:w This looks ahead and finds any quantifier (special character equal to either of ?+*{).

```

18409 \cs_new_protected:Npn \__regex_compile_quantifier:w #1#2
18410 {
18411   \token_if_eq_meaning:NNTF #1 \__regex_compile_special:N
18412   {
18413     \cs_if_exist_use:cF { __regex_compile_quantifier_#2:w }
18414     { \__regex_compile_quantifier_none: #1 #2 }
18415   }
18416   { \__regex_compile_quantifier_none: #1 #2 }
18417 }

```

(End definition for __regex_compile_quantifier:w.)

__regex_compile_quantifier_none: Those functions are called whenever there is no quantifier, or a braced construction is
 __regex_compile_quantifier_abort:xNN invalid (equivalent to no quantifier, and whatever characters were grabbed are left raw).

```

18418 \cs_new_protected:Npn \__regex_compile_quantifier_none:

```



```

18419 { \_tl\_build\_one:n { \if\_false: { \fi: } { 1 } { 0 } \c\_false\_bool } }
18420 \cs\_new\_protected:Npn \_regex\_compile\_quantifier\_abort:xNN #1#2#3
18421 {
18422   \_regex\_compile\_quantifier\_none:
18423   \_msg\_kernel\_warning:nnxx { kernel } { invalid-quantifier } {#1} {#3}
18424   \_regex\_compile\_abort\_tokens:x {#1}
18425   #2 #3
18426 }

```

(End definition for _regex_compile_quantifier_none: and _regex_compile_quantifier_abort:xNN.)

_regex_compile_quantifier_lazyness:nnNN

Once the “main” quantifier (`?`, `*`, `+` or a braced construction) is found, we check whether it is lazy (followed by a question mark). We then add to the compiled regex a closing brace (ending _regex_class:NnnnN and friends), the start-point of the range, its end-point, and a boolean, true for lazy and false for greedy operators.

```

18427 \cs\_new\_protected:Npn \_regex\_compile\_quantifier\_lazyness:nnNN #1#2#3#4
18428 {
18429   \str\_if\_eq:nnTF { #3 #4 } { \_regex\_compile\_special:N ? }
18430   { \_tl\_build\_one:n { \if\_false: { \fi: } { #1 } { #2 } \c\_true\_bool } }
18431   {
18432     \_tl\_build\_one:n { \if\_false: { \fi: } { #1 } { #2 } \c\_false\_bool }
18433     #3 #4
18434   }
18435 }

```

(End definition for _regex_compile_quantifier_lazyness:nnNN.)

_regex_compile_quantifier_?:w
 _regex_compile_quantifier_*:w
 _regex_compile_quantifier_+:w

For each “basic” quantifier, `?`, `*`, `+`, feed the correct arguments to _regex_compile_quantifier_lazyness:nnNN, `-1` means that there is no upper bound on the number of repetitions.

```

18436 \cs\_new\_protected:cpn { \_regex\_compile\_quantifier\_?:w }
18437 { \_regex\_compile\_quantifier\_lazyness:nnNN { 0 } { 1 } }
18438 \cs\_new\_protected:cpn { \_regex\_compile\_quantifier\_*:w }
18439 { \_regex\_compile\_quantifier\_lazyness:nnNN { 0 } { -1 } }
18440 \cs\_new\_protected:cpn { \_regex\_compile\_quantifier\_+:w }
18441 { \_regex\_compile\_quantifier\_lazyness:nnNN { 1 } { -1 } }

```

(End definition for _regex_compile_quantifier_?:w, _regex_compile_quantifier_*:w, and _regex_compile_quantifier_+:w.)

_regex_compile_quantifier_{:w
 _regex_compile_quantifier_braced_auxi:w
 _regex_compile_quantifier_braced_auxii:w
 _regex_compile_quantifier_braced_auxiii:w

Three possible syntaxes: $\{\langle int \rangle\}$, $\{\langle int \rangle, \}$, or $\{\langle int \rangle, \langle int \rangle\}$. Any other syntax causes us to abort and put whatever we collected back in the input stream, as raw characters, including the opening brace. Grab a number into `\l_regex_internal_a_int`. If the number is followed by a right brace, the range is $[a, a]$. If followed by a comma, grab one more number, and call the `_ii` or `_iii` auxiliary. Those auxiliaries check for a closing brace, leading to the range $[a, \infty]$ or $[a, b]$, encoded as $\{a\}\{-1\}$ and $\{a\}\{b-a\}$.

```

18442 \cs\_new\_protected:cpn { \_regex\_compile\_quantifier\_ \c\_left\_brace\_str :w }
18443 {
18444   \_regex\_get\_digits:NTFw \l\_regex\_internal\_a\_int
18445   { \_regex\_compile\_quantifier\_braced\_auxi:w }
18446   { \_regex\_compile\_quantifier\_abort:xNN { \c\_left\_brace\_str } }
18447 }
18448 \cs\_new\_protected:Npn \_regex\_compile\_quantifier\_braced\_auxi:w #1#2
18449 {

```

```

18450 \str_case_x:nnF { #1 #2 }
18451 {
18452   { \__regex_compile_special:N \c_right_brace_str }
18453   {
18454     \exp_args:No \__regex_compile_quantifier_lazyness:nnNN
18455     { \int_use:N \l__regex_internal_a_int } { 0 }
18456   }
18457   { \__regex_compile_special:N , }
18458   {
18459     \__regex_get_digits:NTFw \l__regex_internal_b_int
18460     { \__regex_compile_quantifier_braced_auxiii:w }
18461     { \__regex_compile_quantifier_braced_auxii:w }
18462   }
18463 }
18464 {
18465   \__regex_compile_quantifier_abort:xNN
18466   { \c_left_brace_str \int_use:N \l__regex_internal_a_int }
18467   #1 #2
18468 }
18469 }
18470 \cs_new_protected:Npn \__regex_compile_quantifier_braced_auxii:w #1#2
18471 {
18472   \str_if_eq_x:nnTF
18473   { #1 #2 } { \__regex_compile_special:N \c_right_brace_str }
18474   {
18475     \exp_args:No \__regex_compile_quantifier_lazyness:nnNN
18476     { \int_use:N \l__regex_internal_a_int } { -1 }
18477   }
18478   {
18479     \__regex_compile_quantifier_abort:xNN
18480     { \c_left_brace_str \int_use:N \l__regex_internal_a_int , }
18481     #1 #2
18482   }
18483 }
18484 \cs_new_protected:Npn \__regex_compile_quantifier_braced_auxiii:w #1#2
18485 {
18486   \str_if_eq_x:nnTF
18487   { #1 #2 } { \__regex_compile_special:N \c_right_brace_str }
18488   {
18489     \if_int_compare:w \l__regex_internal_a_int > \l__regex_internal_b_int
18490     \__msg_kernel_error:nnxx { kernel } { backwards-quantifier }
18491     { \int_use:N \l__regex_internal_a_int }
18492     { \int_use:N \l__regex_internal_b_int }
18493     \int_zero:N \l__regex_internal_b_int
18494   }
18495   \else:
18496     \int_sub:Nn \l__regex_internal_b_int \l__regex_internal_a_int
18497   \fi:
18498   \exp_args:Noo \__regex_compile_quantifier_lazyness:nnNN
18499   { \int_use:N \l__regex_internal_a_int }
18500   { \int_use:N \l__regex_internal_b_int }
18501 }
18502 {
18503   \__regex_compile_quantifier_abort:xNN
18504   {

```

```

18504         \c_left_brace_str
18505         \int_use:N \l__regex_internal_a_int ,
18506         \int_use:N \l__regex_internal_b_int
18507     }
18508     #1 #2
18509 }
18510 }

```

(End definition for `__regex_compile_quantifier_{:w and others.}`)

36.3.6 Raw characters

`__regex_compile_raw_error:N` Within character classes, and following catcode tests, some escaped alphanumeric sequences such as `\b` do not have any meaning. They are replaced by a raw character, after spitting out an error.

```

18511 \cs_new_protected:Npn \__regex_compile_raw_error:N #1
18512 {
18513     \__msg_kernel_error:nnx { kernel } { bad-escape } {#1}
18514     \__regex_compile_raw:N #1
18515 }

```

(End definition for `__regex_compile_raw_error:N.`)

`__regex_compile_raw:N` If we are in a character class and the next character is an unescaped dash, this denotes a range. Otherwise, the current character `#1` matches itself.

```

18516 \cs_new_protected:Npn \__regex_compile_raw:N #1#2#3
18517 {
18518     \__regex_if_in_class:TF
18519     {
18520         \str_if_eq:nnTF {#2#3} { \__regex_compile_special:N - }
18521         { \__regex_compile_range:Nw #1 }
18522         {
18523             \__regex_compile_one:x
18524             { \__regex_item_equal:n { \__int_value:w '#1 ~ } }
18525             #2 #3
18526         }
18527     }
18528     {
18529         \__regex_compile_one:x
18530         { \__regex_item_equal:n { \__int_value:w '#1 ~ } }
18531         #2 #3
18532     }
18533 }

```

(End definition for `__regex_compile_raw:N.`)

`__regex_compile_range:Nw` We have just read a raw character followed by a dash; this should be followed by an end-point for the range. Valid end-points are: any raw character; any special character, except a right bracket. In particular, escaped characters are forbidden.

`__regex_if_end_range:NNTF`

```

18534 \prg_new_protected_conditional:Npnn \__regex_if_end_range:NN #1#2 { TF }
18535 {
18536     \if_meaning:w \__regex_compile_raw:N #1
18537     \prg_return_true:
18538 }

```

```

18539     \if_meaning:w \__regex_compile_special:N #1
18540     \if_charcode:w ] #2
18541     \prg_return_false:
18542     \else:
18543     \prg_return_true:
18544     \fi:
18545     \else:
18546     \prg_return_false:
18547     \fi:
18548     \fi:
18549   }
18550 \cs_new_protected:Npn \__regex_compile_range:Nw #1#2#3
18551 {
18552   \__regex_if_end_range:NNTF #2 #3
18553   {
18554     \if_int_compare:w '#1 > '#3 \exp_stop_f:
18555     \__msg_kernel_error:nxxx { kernel } { range-backwards } {#1} {#3}
18556     \else:
18557     \__tl_build_one:x
18558     {
18559       \if_int_compare:w '#1 = '#3 \exp_stop_f:
18560       \__regex_item_equal:n
18561       \else:
18562       \__regex_item_range:nn { \__int_value:w '#1 ~ }
18563       \fi:
18564       { \__int_value:w '#3 ~ }
18565     }
18566     \fi:
18567   }
18568   {
18569     \__msg_kernel_warning:nxxx { kernel } { range-missing-end }
18570     {#1} { \c_backslash_str #3 }
18571     \__tl_build_one:x
18572     {
18573       \__regex_item_equal:n { \__int_value:w '#1 ~ }
18574       \__regex_item_equal:n { \__int_value:w '- ~ }
18575     }
18576     #2#3
18577   }
18578 }

```

(End definition for `__regex_compile_range:Nw` and `__regex_if_end_range:NNTF`.)

36.3.7 Character properties

`__regex_compile_.`: In a class, the dot has no special meaning. Outside, insert `__regex_prop_.`, which matches any character or control sequence, and refuses `-2` (end-marker).

```

18579 \cs_new_protected:cpx { __regex_compile_.: }
18580 {
18581   \exp_not:N \__regex_if_in_class:TF
18582   { \__regex_compile_raw:N . }
18583   { \__regex_compile_one:x \exp_not:c { __regex_prop_.: } }
18584 }
18585 \cs_new_protected:cpn { __regex_prop_.: }

```

```

18586 {
18587     \if_int_compare:w \l__regex_curr_char_int > - 2 \exp_stop_f:
18588     \exp_after:wN \__regex_break_true:w
18589     \fi:
18590 }

```

(End definition for __regex_compile_.: and __regex_prop_..)

__regex_compile_/d: The constants __regex_prop_d:, etc. hold a list of tests which match the corresponding character class, and jump to the __regex_break_point:TF marker. As for a normal character, we check for quantifiers.

```

\__regex_compile_/H: 18591 \cs_set_protected:Npn \__regex_tmp:w #1#2
\__regex_compile_/s: 18592 {
\__regex_compile_/S: 18593     \cs_new_protected:cpx { __regex_compile_/#1: }
\__regex_compile_/v: 18594     { \__regex_compile_one:x \exp_not:c { __regex_prop_#1: } }
\__regex_compile_/V: 18595     \cs_new_protected:cpx { __regex_compile_/#2: }
\__regex_compile_/w: 18596     {
\__regex_compile_/W: 18597         \__regex_compile_one:x
\__regex_compile_/N: 18598         { \__regex_item_reverse:n \exp_not:c { __regex_prop_#1: } }
18599     }
18600 }
18601 \__regex_tmp:w d D
18602 \__regex_tmp:w h H
18603 \__regex_tmp:w s S
18604 \__regex_tmp:w v V
18605 \__regex_tmp:w w W
18606 \cs_new_protected:cpn { __regex_compile_/N: }
18607 { \__regex_compile_one:x \__regex_prop_N: }

```

(End definition for __regex_compile_/d: and others.)

36.3.8 Anchoring and simple assertions

__regex_compile_anchor:Nf In modes where assertions are allowed, anchor to the start of the query, the start of the match, or the end of the query, depending on the integer #1. In other modes, #2 treats the character as raw, with an error for escaped letters (\$ is valid in a class, but \A is definitely a mistake on the user's part).

```

\__regex_compile_anchor:Nf 18608 \cs_new_protected:Npn \__regex_compile_anchor:Nf #1#2
\__regex_compile_/A: 18609 {
\__regex_compile_/G: 18610     \__regex_if_in_class_or_catcode:TF {#2}
\__regex_compile_/Z: 18611     {
\__regex_compile_/z: 18612         \__tl_build_one:n
18613         { \__regex_assertion:Nn \c_true_bool { \__regex_anchor:N #1 } }
18614     }
18615 }
18616 \cs_set_protected:Npn \__regex_tmp:w #1#2
18617 {
18618     \cs_new_protected:cpn { __regex_compile_/#1: }
18619     { \__regex_compile_anchor:Nf #2 { \__regex_compile_raw_error:N #1 } }
18620 }
18621 \__regex_tmp:w A \l__regex_min_pos_int
18622 \__regex_tmp:w G \l__regex_start_pos_int
18623 \__regex_tmp:w Z \l__regex_max_pos_int
18624 \__regex_tmp:w z \l__regex_max_pos_int

```

```

18625 \cs_set_protected:Npn \__regex_tmp:w #1#2
18626 {
18627   \cs_new_protected:cpn { __regex_compile_#1: }
18628   { \__regex_compile_anchor:Nf #2 { \__regex_compile_raw:N #1 } }
18629 }
18630 \exp_args:Nx \__regex_tmp:w { \iow_char:N \^ } \l__regex_min_pos_int
18631 \exp_args:Nx \__regex_tmp:w { \iow_char:N \$ } \l__regex_max_pos_int

```

(End definition for `__regex_compile_anchor:Nf` and others.)

`__regex_compile_/b:` Contrarily to `^` and `$`, which could be implemented without really knowing what precedes in the token list, this requires more information, namely, the knowledge of the last character code.

```

18632 \cs_new_protected:cpn { __regex_compile_/b: }
18633 {
18634   \__regex_if_in_class_or_catcode:TF
18635   { \__regex_compile_raw_error:N b }
18636   {
18637     \__tl_build_one:n
18638     { \__regex_assertion:Nn \c_true_bool { \__regex_b_test: } }
18639   }
18640 }
18641 \cs_new_protected:cpn { __regex_compile_/B: }
18642 {
18643   \__regex_if_in_class_or_catcode:TF
18644   { \__regex_compile_raw_error:N B }
18645   {
18646     \__tl_build_one:n
18647     { \__regex_assertion:Nn \c_false_bool { \__regex_b_test: } }
18648   }
18649 }

```

(End definition for `__regex_compile_/b:` and `__regex_compile_/B:.`)

36.3.9 Character classes

`__regex_compile_]:` Outside a class, right brackets have no meaning. In a class, change the mode ($m \rightarrow (m - 15)/13$, truncated) to reflect the fact that we are leaving the class. Look for quantifiers, unless we are still in a class after leaving one (the case of `[... \cL[...]]`). quantifiers.

```

18650 \cs_new_protected:cpn { __regex_compile_]: }
18651 {
18652   \__regex_if_in_class:TF
18653   {
18654     \if_int_compare:w \l__regex_mode_int > \c__regex_catcode_in_class_mode_int
18655     \__tl_build_one:n { \if_false: { \fi: } }
18656     \fi:
18657     \tex_advance:D \l__regex_mode_int - 15 \exp_stop_f:
18658     \tex_divide:D \l__regex_mode_int 13 \exp_stop_f:
18659     \if_int_odd:w \l__regex_mode_int \else:
18660       \exp_after:wN \__regex_compile_quantifier:w
18661     \fi:
18662   }
18663   { \__regex_compile_raw:N ] }
18664 }

```

(End definition for _regex_compile[:])

_regex_compile[: In a class, left brackets might introduce a POSIX character class, or mean nothing. Immediately following \c<category>, we must insert the appropriate catcode test, then parse the class; we pre-expand the catcode as an optimization. Otherwise (modes 0, -2 and -6) just parse the class. The mode is updated later.

```

18665 \cs_new_protected:cpn { \_regex_compile[: }
18666 {
18667   \_regex_if_in_class:TF
18668   { \_regex_compile_class_posix_test:w }
18669   {
18670     \_regex_if_within_catcode:TF
18671     {
18672       \exp_after:wN \_regex_compile_class_catcode:w
18673       \int_use:N \l__regex_catcodes_int ;
18674     }
18675     { \_regex_compile_class_normal:w }
18676   }
18677 }

```

(End definition for _regex_compile[:])

_regex_compile_class_normal:w In the “normal” case, we insert _regex_class:NnnnN <boolean> in the compiled code. The <boolean> is true for positive classes, and false for negative classes, characterized by a leading \neg . The auxiliary _regex_compile_class:TFNN also checks for a leading] which has a special meaning.

```

18678 \cs_new_protected:Npn \_regex_compile_class_normal:w
18679 {
18680   \_regex_compile_class:TFNN
18681   { \_regex_class:NnnnN \c_true_bool }
18682   { \_regex_class:NnnnN \c_false_bool }
18683 }

```

(End definition for _regex_compile_class_normal:w.)

_regex_compile_class_catcode:w This function is called for a left bracket in modes 2 or 6 (catcode test, and catcode test within a class). In mode 2 the whole construction needs to be put in a class (like single character). Then determine if the class is positive or negative, inserting _regex_item_catcode:nT or the reverse variant as appropriate, each with the current catcodes bitmap #1 as an argument, and reset the catcodes.

```

18684 \cs_new_protected:Npn \_regex_compile_class_catcode:w #1;
18685 {
18686   \if_int_compare:w \l__regex_mode_int = \c__regex_catcode_mode_int
18687   \_tl_build_one:n
18688   { \_regex_class:NnnnN \c_true_bool { \if_false: } \fi: }
18689   \fi:
18690   \int_set_eq:NN \l__regex_catcodes_int \l__regex_default_catcodes_int
18691   \_regex_compile_class:TFNN
18692   { \_regex_item_catcode:nT {#1} }
18693   { \_regex_item_catcode_reverse:nT {#1} }
18694 }

```

(End definition for _regex_compile_class_catcode:w.)

`__regex_compile_class:TFNN` If the first character is ^, then the class is negative (use #2), otherwise it is positive (use #1). If the next character is a right bracket, then it should be changed to a raw one.
`__regex_compile_class:NN`

```

18695 \cs_new_protected:Npn __regex_compile_class:TFNN #1#2#3#4
18696 {
18697   \l__regex_mode_int = \__int_value:w \l__regex_mode_int 3 \exp_stop_f:
18698   \str_if_eq:nnTF { #3 #4 } { \__regex_compile_special:N ^ }
18699   {
18700     \__tl_build_one:n { #2 { \if_false: } \fi: }
18701     \__regex_compile_class:NN
18702   }
18703   {
18704     \__tl_build_one:n { #1 { \if_false: } \fi: }
18705     \__regex_compile_class:NN #3 #4
18706   }
18707 }
18708 \cs_new_protected:Npn __regex_compile_class:NN #1#2
18709 {
18710   \token_if_eq_charcode:NNTF #2 ]
18711   { \__regex_compile_raw:N #2 }
18712   { #1 #2 }
18713 }

```

(End definition for `__regex_compile_class:TFNN` and `__regex_compile_class:NN`.)

`__regex_compile_class_posix_test:w` Here we check for a syntax such as [:alpha:]. We also detect [= and [. which have a meaning in POSIX regular expressions, but are not implemented in l3regex. In case we see [:, grab raw characters until hopefully reaching :]. If that's missing, or the POSIX class is unknown, abort. If all is right, add the test to the current class, with an extra `__regex_item_reverse:n` for negative classes.
`__regex_compile_class_posix:NNNNw`
`__regex_compile_class_posix_loop:w`
`__regex_compile_class_posix_end:w`

```

18714 \cs_new_protected:Npn __regex_compile_class_posix_test:w #1#2
18715 {
18716   \token_if_eq_meaning:NNT \__regex_compile_special:N #1
18717   {
18718     \str_case:nn { #2 }
18719     {
18720       : { \__regex_compile_class_posix:NNNNw }
18721       = { \__msg_kernel_warning:nxx { kernel } { posix-unsupported } { = } }
18722       . { \__msg_kernel_warning:nxx { kernel } { posix-unsupported } { . } }
18723     }
18724   }
18725   \__regex_compile_raw:N [ #1 #2
18726 }
18727 \cs_new_protected:Npn __regex_compile_class_posix:NNNNw #1#2#3#4#5#6
18728 {
18729   \str_if_eq:nnTF { #5 #6 } { \__regex_compile_special:N ^ }
18730   {
18731     \bool_set_false:N \l__regex_internal_bool
18732     \tl_set:Nx \l__regex_internal_a_tl { \if_false: } \fi:
18733     \__regex_compile_class_posix_loop:w
18734   }
18735   {
18736     \bool_set_true:N \l__regex_internal_bool
18737     \tl_set:Nx \l__regex_internal_a_tl { \if_false: } \fi:
18738     \__regex_compile_class_posix_loop:w #5 #6

```



```

18739     }
18740   }
18741   \cs_new:Npn \__regex_compile_class_posix_loop:w #1#2
18742   {
18743     \token_if_eq_meaning:NNTF \__regex_compile_raw:N #1
18744     { #2 \__regex_compile_class_posix_loop:w }
18745     { \if_false: { \fi: } \__regex_compile_class_posix_end:w #1 #2 }
18746   }
18747   \cs_new_protected:Npn \__regex_compile_class_posix_end:w #1#2#3#4
18748   {
18749     \str_if_eq:nnTF { #1 #2 #3 #4 }
18750     { \__regex_compile_special:N : \__regex_compile_special:N ] }
18751     {
18752       \cs_if_exist:cTF { __regex_posix_ \l__regex_internal_a_tl : }
18753       {
18754         \__regex_compile_one:x
18755         {
18756           \bool_if:NF \l__regex_internal_bool \__regex_item_reverse:n
18757           \exp_not:c { __regex_posix_ \l__regex_internal_a_tl : }
18758         }
18759       }
18760       {
18761         \__msg_kernel_warning:nnx { kernel } { posix-unknown }
18762         { \l__regex_internal_a_tl }
18763         \__regex_compile_abort_tokens:x
18764         {
18765           [: \bool_if:NF \l__regex_internal_bool { ^ }
18766           \l__regex_internal_a_tl :]
18767         }
18768       }
18769     }
18770   }
18771   \__msg_kernel_error:nnxx { kernel } { posix-missing-close }
18772   { [: \l__regex_internal_a_tl ] { #2 #4 }
18773   \__regex_compile_abort_tokens:x { [: \l__regex_internal_a_tl ]
18774   #1 #2 #3 #4
18775   }
18776   }

```

(End definition for `__regex_compile_class_posix_test:w` and others.)

36.3.10 Groups and alternations

`__regex_compile_group_begin:N` The contents of a regex group are turned into compiled code in `\l__regex_internal_-`
`__regex_compile_group_end:` **regex**, which ends up with items of the form `__regex_branch:n {⟨concatenation⟩}`. This construction is done using `!3tl-build` within a `TeX` group, which automatically makes sure that options (case-sensitivity and default catcode) are reset at the end of the group. The argument `#1` is `__regex_group:nnnN` or a variant thereof. A small subtlety to support `\cL(abc)` as a shorthand for `(\cLa\cLb\cLc)`: exit any pending catcode test, save the category code at the start of the group as the default catcode for that group, and make sure that the catcode is restored to the default outside the group.

```

18777   \cs_new_protected:Npn \__regex_compile_group_begin:N #1
18778   {
18779     \__tl_build_one:n { #1 { \if_false: } \fi: }

```

```

18780     \__regex_mode_quit_c:
18781     \__tl_build:Nw \l__regex_internal_regex
18782     \int_set_eq:NN \l__regex_default_catcodes_int \l__regex_catcodes_int
18783     \int_incr:N \l__regex_group_level_int
18784     \__tl_build_one:n { \__regex_branch:n { \if_false: } \fi: }
18785   }
18786 \cs_new_protected:Npn \__regex_compile_group_end:
18787 {
18788   \if_int_compare:w \l__regex_group_level_int > 0 \exp_stop_f:
18789     \__tl_build_one:n { \if_false: { \fi: } }
18790     \__tl_build_end:
18791     \int_set_eq:NN \l__regex_catcodes_int \l__regex_default_catcodes_int
18792     \__tl_build_one:o \l__regex_internal_regex
18793     \exp_after:wN \__regex_compile_quantifier:w
18794   \else:
18795     \__msg_kernel_warning:nn { kernel } { extra-rparen }
18796     \exp_after:wN \__regex_compile_raw:N \exp_after:wN )
18797   \fi:
18798 }

```

(End definition for __regex_compile_group_begin:N and __regex_compile_group_end:.)

__regex_compile_(: In a class, parentheses are not special. Outside, check for a ?, denoting special groups, and run the code for the corresponding special group.

```

18799 \cs_new_protected:cpn { __regex_compile_(: }
18800 {
18801   \__regex_if_in_class:TF { \__regex_compile_raw:N ( }
18802   { \__regex_compile_lparen:w }
18803 }
18804 \cs_new_protected:Npn \__regex_compile_lparen:w #1#2#3#4
18805 {
18806   \str_if_eq:nnTF { #1 #2 } { \__regex_compile_special:N ? }
18807   {
18808     \cs_if_exist_use:cF
18809     { __regex_compile_special_group\_token_to_str:N #4 :w }
18810     {
18811       \__msg_kernel_warning:nnx { kernel } { special-group-unknown }
18812       { (? #4 }
18813       \__regex_compile_group_begin:N \__regex_group:nnnN
18814       \__regex_compile_raw:N ? #3 #4
18815     }
18816   }
18817   {
18818     \__regex_compile_group_begin:N \__regex_group:nnnN
18819     #1 #2 #3 #4
18820   }
18821 }

```

(End definition for __regex_compile_(:.)

__regex_compile_|: In a class, the pipe is not special. Otherwise, end the current branch and open another one.

```

18822 \cs_new_protected:cpn { __regex_compile_|: }
18823 {

```

```

18824     \__regex_if_in_class:TF { \__regex_compile_raw:N | }
18825     {
18826         \__tl_build_one:n
18827         { \if_false: { \fi: } \__regex_branch:n { \if_false: } \fi: }
18828     }
18829 }

```

(End definition for __regex_compile/:.)

__regex_compile_): Within a class, parentheses are not special. Outside, close a group.

```

18830 \cs_new_protected:cpn { __regex_compile_): }
18831 {
18832     \__regex_if_in_class:TF { \__regex_compile_raw:N ) }
18833     { \__regex_compile_group_end: }
18834 }

```

(End definition for __regex_compile_):.)

_regex_compile_special_group_::w Non-capturing, and resetting groups are easy to take care of during compilation; for those
_regex_compile_special_group_|:w groups, the harder parts come when building.

```

18835 \cs_new_protected:cpn { __regex_compile_special_group_::w }
18836 { \__regex_compile_group_begin:N \__regex_group_no_capture:nnnN }
18837 \cs_new_protected:cpn { __regex_compile_special_group_|:w }
18838 { \__regex_compile_group_begin:N \__regex_group_resetting:nnnN }

```

(End definition for __regex_compile_special_group_::w and __regex_compile_special_group_|:w.)

_regex_compile_special_group_i:w The match can be made case-insensitive by setting the option with (?i); the original
_regex_compile_special_group_-:w behaviour is restored by (?-i). This is the only supported option.

```

18839 \cs_new_protected:Npn \__regex_compile_special_group_i:w #1#2
18840 {
18841     \str_if_eq:nnTF { #1 #2 } { \__regex_compile_special:N ) }
18842     {
18843         \cs_set:Npn \__regex_item_equal:n { \__regex_item_caseless_equal:n }
18844         \cs_set:Npn \__regex_item_range:nn { \__regex_item_caseless_range:nn }
18845     }
18846     {
18847         \__msg_kernel_warning:nnx { kernel } { unknown-option } { (?i #2 }
18848         \__regex_compile_raw:N (
18849         \__regex_compile_raw:N ?
18850         \__regex_compile_raw:N i
18851         #1 #2
18852     }
18853 }
18854 \cs_new_protected:cpn { __regex_compile_special_group_-:w } #1#2#3#4
18855 {
18856     \str_if_eq:nnTF { #1 #2 #3 #4 }
18857     { \__regex_compile_raw:N i \__regex_compile_special:N ) }
18858     {
18859         \cs_set:Npn \__regex_item_equal:n { \__regex_item_caseful_equal:n }
18860         \cs_set:Npn \__regex_item_range:nn { \__regex_item_caseful_range:nn }
18861     }
18862     {
18863         \__msg_kernel_warning:nnx { kernel } { unknown-option } { (?-#2#4 }
18864         \__regex_compile_raw:N (

```

```

18865     \_regex_compile_raw:N ?
18866     \_regex_compile_raw:N -
18867     #1 #2 #3 #4
18868   }
18869 }

```

(End definition for _regex_compile_special_group_i:w and _regex_compile_special_group_~:w.)

36.3.11 Catcodes and csnames

_regex_compile_/c: The \c escape sequence can be followed by a capital letter representing a character category, by a left bracket which starts a list of categories, or by a brace group holding a regular expression for a control sequence name. Otherwise, raise an error.

```

18870 \cs_new_protected:cpn { \_regex_compile_/c: }
18871 { \_regex_chk_c_allowed:T { \_regex_compile_c_test:NN } }
18872 \cs_new_protected:Npn \_regex_compile_c_test:NN #1#2
18873 {
18874   \token_if_eq_meaning:NNTF #1 \_regex_compile_raw:N
18875   {
18876     \int_if_exist:cTF { c__regex_catcode_#2_int }
18877     {
18878       \int_set_eq:Nc \l__regex_catcodes_int { c__regex_catcode_#2_int }
18879       \l__regex_mode_int
18880       = \if_case:w \l__regex_mode_int
18881         \c__regex_catcode_mode_int
18882         \else:
18883         \c__regex_catcode_in_class_mode_int
18884         \fi:
18885       \token_if_eq_charcode:NNT C #2 { \_regex_compile_c_C:NN }
18886     }
18887   }
18888   { \cs_if_exist_use:cF { \_regex_compile_c_#2:w } }
18889   {
18890     \_msg_kernel_error:nxx { kernel } { c-missing-category } {#2}
18891     #1 #2
18892   }
18893 }

```

(End definition for _regex_compile_/c: and _regex_compile_c_test:NN.)

_regex_compile_c_C:NN If \cC is not followed by . or (...) then complain because that construction cannot match anything, except in cases like \cC[\c{...}], where it has no effect.

```

18894 \cs_new_protected:Npn \_regex_compile_c_C:NN #1#2
18895 {
18896   \token_if_eq_meaning:NNTF #1 \_regex_compile_special:N
18897   {
18898     \token_if_eq_charcode:NNTF #2 .
18899     { \use_none:n }
18900     { \token_if_eq_charcode:NNTF #2 ( ) % }
18901   }
18902   { \use:n }
18903   { \_msg_kernel_error:nnn { kernel } { c-C-invalid } {#2} }
18904   #1 #2
18905 }

```

(End definition for _regex_compile_c:C:NN.)

_regex_compile_c[:w When encountering \c[, the task is to collect uppercase letters representing character categories. First check for ^ which negates the list of category codes.

```

\_regex_compile_c_lbrack_loop:NN
\_regex_compile_c_lbrack_add:N
\_regex_compile_c_lbrack_end:
18906 \cs_new_protected:cpn { \_regex_compile_c[:w } #1#2
18907 {
18908   \l__regex_mode_int
18909   = \if_case:w \l__regex_mode_int
18910     \c__regex_catcode_mode_int
18911     \else:
18912       \c__regex_catcode_in_class_mode_int
18913     \fi:
18914   \int_zero:N \l__regex_catcodes_int
18915   \str_if_eq:nnTF { #1 #2 } { \_regex_compile_special:N ^ }
18916   {
18917     \bool_set_false:N \l__regex_catcodes_bool
18918     \_regex_compile_c_lbrack_loop:NN
18919   }
18920   {
18921     \bool_set_true:N \l__regex_catcodes_bool
18922     \_regex_compile_c_lbrack_loop:NN
18923     #1 #2
18924   }
18925 }
18926 \cs_new_protected:Npn \_regex_compile_c_lbrack_loop:NN #1#2
18927 {
18928   \token_if_eq_meaning:NNTF #1 \_regex_compile_raw:N
18929   {
18930     \int_if_exist:cTF { c__regex_catcode_#2_int }
18931     {
18932       \exp_args:Nc \_regex_compile_c_lbrack_add:N
18933       { c__regex_catcode_#2_int }
18934       \_regex_compile_c_lbrack_loop:NN
18935     }
18936   }
18937   {
18938     \token_if_eq_charcode:NNTF #2 ]
18939     { \_regex_compile_c_lbrack_end: }
18940   }
18941   {
18942     \__msg_kernel_error:nnx { kernel } { c-missing-rbrack } {#2}
18943     \_regex_compile_c_lbrack_end:
18944     #1 #2
18945   }
18946 }
18947 \cs_new_protected:Npn \_regex_compile_c_lbrack_add:N #1
18948 {
18949   \if_int_odd:w \_int_eval:n { \l__regex_catcodes_int / #1 }
18950   \else:
18951     \int_add:Nn \l__regex_catcodes_int {#1}
18952   \fi:
18953 }
18954 \cs_new_protected:Npn \_regex_compile_c_lbrack_end:
18955 {

```

```

18956     \if_meaning:w \c_false_bool \l__regex_catcodes_bool
18957     \int_set:Nn \l__regex_catcodes_int
18958     { \c__regex_all_catcodes_int - \l__regex_catcodes_int }
18959     \fi:
18960 }

```

(End definition for `__regex_compile_c[:w` and others.)

`__regex_compile_c_{:` The case of a left brace is easy, based on what we have done so far: in a group, compile the regular expression, after changing the mode to forbid nesting `\c`. Additionally, disable submatch tracking since groups don't escape the scope of `\c{...}`.

```

18961 \cs_new_protected:cpn { __regex_compile_c_ \c_left_brace_str :w }
18962 {
18963     \__regex_compile:w
18964     \__regex_disable_submatches:
18965     \l__regex_mode_int
18966     = \if_case:w \l__regex_mode_int
18967       \c__regex_cs_mode_int
18968     \else:
18969       \c__regex_cs_in_class_mode_int
18970     \fi:
18971 }

```

(End definition for `__regex_compile_c_{:}`.)

`__regex_compile_}`: Non-escaped right braces are only special if they appear when compiling the regular expression for a csname, but not within a class: `\c{[{}]}` matches the control sequences `\{` and `\}`. So, end compiling the inner regex (this closes any dangling class or group). `__regex_compile_cs_aux:Nn` Then insert the corresponding test in the outer regex. As an optimization, if the control sequence test simply consists of several explicit possibilities (branches) then use `__regex_item_exact_cs:n` with an argument consisting of all possibilities separated by `\scan_stop:.`

```

18972 \flag_new:n { __regex_cs }
18973 \cs_new_protected:cpn { __regex_compile_ \c_right_brace_str : }
18974 {
18975     \__regex_if_in_cs:TF
18976     { \__regex_compile_end_cs: }
18977     { \exp_after:wN \__regex_compile_raw:N \c_right_brace_str }
18978 }
18979 \cs_new_protected:Npn \__regex_compile_end_cs:
18980 {
18981     \__regex_compile_end:
18982     \flag_clear:n { __regex_cs }
18983     \tl_set:Nx \l__regex_internal_a_tl
18984     {
18985         \exp_after:wN \__regex_compile_cs_aux:Nn \l__regex_internal_regex
18986         \q_nil \q_nil \q_recursion_stop
18987     }
18988     \exp_args:Nx \__regex_compile_one:x
18989     {
18990         \flag_if_raised:nTF { __regex_cs }
18991         { \__regex_item_cs:n { \exp_not:o \l__regex_internal_regex } }
18992         { \__regex_item_exact_cs:n { \tl_tail:N \l__regex_internal_a_tl } }
18993     }

```

```

18994     }
18995     \cs_new:Npn \__regex_compile_cs_aux:Nn #1#2
18996     {
18997         \cs_if_eq:NNTF #1 \__regex_branch:n
18998         {
18999             \scan_stop:
19000             \__regex_compile_cs_aux:NNnnnN #2
19001             \q_nil \q_nil \q_nil \q_nil \q_nil \q_nil \q_recursion_stop
19002             \__regex_compile_cs_aux:Nn
19003         }
19004         {
19005             \quark_if_nil:NF #1 { \flag_raise:n { __regex_cs } }
19006             \use_none_delimit_by_q_recursion_stop:w
19007         }
19008     }
19009     \cs_new:Npn \__regex_compile_cs_aux:NNnnnN #1#2#3#4#5#6
19010     {
19011         \bool_lazy_all:nTF
19012         {
19013             { \cs_if_eq_p:NN #1 \__regex_class:NnnnN }
19014             {#2}
19015             { \tl_if_head_eq_meaning_p:nN {#3} \__regex_item_caseful_equal:n }
19016             { \int_compare_p:nNn { \tl_count:n {#3} } = { 2 } }
19017             { \int_compare_p:nNn {#5} = { 0 } }
19018         }
19019         {
19020             \prg_replicate:nn {#4}
19021             { \char_generate:nn { \use_ii:nn #3 } {12} }
19022             \__regex_compile_cs_aux:NNnnnN
19023         }
19024         {
19025             \quark_if_nil:NF #1
19026             {
19027                 \flag_raise:n { __regex_cs }
19028                 \use_i_delimit_by_q_recursion_stop:nw
19029             }
19030             \use_none_delimit_by_q_recursion_stop:w
19031         }
19032     }

```

(End definition for `__regex_compile_`: and others.)

36.3.12 Raw token lists with `\u`

`__regex_compile_/u:` The `\u` escape is invalid in classes and directly following a catcode test. Otherwise, it must be followed by a left brace. We then collect the characters for the argument of `\u` within an x-expanding assignment. In principle we could just wait to encounter a right brace, but this is unsafe: if the right brace was missing, then we would reach the end-markers of the regex, and continue, leading to obscure fatal errors. Instead, we only allow raw and special characters, and stop when encountering a special right brace, any escaped character, or the end-marker.

```

19033 \cs_new_protected:cpn { __regex_compile_/u: } #1#2
19034 {
19035     \__regex_if_in_class_or_catcode:TF

```

```

19036 { \_regex_compile_raw_error:N u #1 #2 }
19037 {
19038   \str_if_eq_x:nnTF {#1#2} { \_regex_compile_special:N \c_left_brace_str }
19039   {
19040     \tl_set:Nx \l__regex_internal_a_tl { \if_false: } \fi:
19041     \_regex_compile_u_loop:NN
19042   }
19043   {
19044     \_msg_kernel_error:nn { kernel } { u-missing-lbrace }
19045     \_regex_compile_raw:N u #1 #2
19046   }
19047 }
19048 }
19049 \cs_new:Npn \_regex_compile_u_loop:NN #1#2
19050 {
19051   \token_if_eq_meaning:NNTF #1 \_regex_compile_raw:N
19052   { #2 \_regex_compile_u_loop:NN }
19053   {
19054     \token_if_eq_meaning:NNTF #1 \_regex_compile_special:N
19055     {
19056       \exp_after:wN \token_if_eq_charcode:NNTF \c_right_brace_str #2
19057       { \if_false: { \fi: } \_regex_compile_u_end: }
19058       { #2 \_regex_compile_u_loop:NN }
19059     }
19060     {
19061       \if_false: { \fi: }
19062       \_msg_kernel_error:nmx { kernel } { u-missing-rbrace } {#2}
19063       \_regex_compile_u_end:
19064       #1 #2
19065     }
19066   }
19067 }

```

(End definition for _regex_compile_/u: and _regex_compile_u_loop:NN.)

_regex_compile_u_end: Once we have extracted the variable's name, we store the contents of that variable in \l__regex_internal_a_tl. The behaviour of \u then depends on whether we are within a \c{...} escape (in this case, the variable is turned to a string), or not.

```

19068 \cs_new_protected:Npn \_regex_compile_u_end:
19069 {
19070   \tl_set:Nv \l__regex_internal_a_tl { \l__regex_internal_a_tl }
19071   \if_int_compare:w \l__regex_mode_int = \c__regex_outer_mode_int
19072   \_regex_compile_u_not_cs:
19073   \else:
19074     \_regex_compile_u_in_cs:
19075   \fi:
19076 }

```

(End definition for _regex_compile_u_end:.)

_regex_compile_u_in_cs: When \u appears within a control sequence, we convert the variable to a string with escaped spaces. Then for each character insert a class matching exactly that character, once.

```

19077 \cs_new_protected:Npn \_regex_compile_u_in_cs:

```



```

19078 {
19079   \tl_gset:Nx \g__regex_internal_tl
19080   { \exp_args:No \__str_to_other_fast:n { \l__regex_internal_a_tl } }
19081   \__tl_build_one:x
19082   {
19083     \tl_map_function:NN \g__regex_internal_tl
19084     \__regex_compile_u_in_cs_aux:n
19085   }
19086 }
19087 \cs_new:Npn \__regex_compile_u_in_cs_aux:n #1
19088 {
19089   \__regex_class:NnnN \c_true_bool
19090   { \__regex_item_caseful_equal:n { \__int_value:w '#1 } }
19091   { 1 } { 0 } \c_false_bool
19092 }

```

(End definition for __regex_compile_u_in_cs:.)

__regex_compile_u_not_cs: In mode 0, the \u escape adds one state to the NFA for each token in \l__regex_internal_a_tl. If a given *<token>* is a control sequence, then insert a string comparison test, otherwise, __regex_item_exact:nn which compares catcode and character code.

```

19093 \cs_new_protected:Npn \__regex_compile_u_not_cs:
19094 {
19095   \exp_args:No \__tl_analysis_map_inline:nn { \l__regex_internal_a_tl }
19096   {
19097     \__tl_build_one:n
19098     {
19099       \__regex_class:NnnN \c_true_bool
19100       {
19101         \if_int_compare:w "##2 = 0 \exp_stop_f:
19102         \__regex_item_exact_cs:n { \exp_after:wN \cs_to_str:N ##1 }
19103         \else:
19104         \__regex_item_exact:nn { \__int_value:w "##2 } { ##3 }
19105         \fi:
19106       }
19107       { 1 } { 0 } \c_false_bool
19108     }
19109   }
19110 }

```

(End definition for __regex_compile_u_not_cs:.)

36.3.13 Other

__regex_compile_/K: The \K control sequence is currently the only “command”, which performs some action, rather than matching something. It is allowed in the same contexts as \b. At the compilation stage, we leave it as a single control sequence, defined later.

```

19111 \cs_new_protected:cpn { __regex_compile_/K: }
19112 {
19113   \int_compare:nNnTF \l__regex_mode_int = \c__regex_outer_mode_int
19114   { \__tl_build_one:n { \__regex_command_K: } }
19115   { \__regex_compile_raw_error:N K }
19116 }

```

(End definition for __regex_compile_/K:.)

36.3.14 Showing regexes

`__regex_show:N` Within a `__tl_build:Nw ... __tl_build_end:` group, we redefine all the function that can appear in a compiled regex, then run the regex. The result stored in `\l__regex_internal_a_tl` is then meant to be shown.

```
19117 \cs_new_protected:Npn \__regex_show:N #1
19118 {
19119   \__tl_build:Nw \l__regex_internal_a_tl
19120   \cs_set_protected:Npn \__regex_branch:n
19121   {
19122     \seq_pop_right:NN \l__regex_show_prefix_seq \l__regex_internal_a_tl
19123     \__regex_show_one:n { +-branch }
19124     \seq_put_right:No \l__regex_show_prefix_seq \l__regex_internal_a_tl
19125     \use:n
19126   }
19127   \cs_set_protected:Npn \__regex_group:nnnN
19128   { \__regex_show_group_aux:nnnnN { } }
19129   \cs_set_protected:Npn \__regex_group_no_capture:nnnN
19130   { \__regex_show_group_aux:nnnnN { ~(no~capture) } }
19131   \cs_set_protected:Npn \__regex_group_resetting:nnnN
19132   { \__regex_show_group_aux:nnnnN { ~(resetting) } }
19133   \cs_set_eq:NN \__regex_class:NnnnN \__regex_show_class:NnnnnN
19134   \cs_set_protected:Npn \__regex_command_K:
19135   { \__regex_show_one:n { reset~match~start~(\iow_char:N\K) } }
19136   \cs_set_protected:Npn \__regex_assertion:Nn ##1##2
19137   { \__regex_show_one:n { \bool_if:NF ##1 { negative~ } assertion:~##2 } }
19138   \cs_set:Npn \__regex_b_test: { word~boundary }
19139   \cs_set_eq:NN \__regex_anchor:N \__regex_show_anchor_to_str:N
19140   \cs_set_protected:Npn \__regex_item_caseful_equal:n ##1
19141   { \__regex_show_one:n { char~code~\int_eval:n{##1} } }
19142   \cs_set_protected:Npn \__regex_item_caseful_range:nn ##1##2
19143   { \__regex_show_one:n { range~[\int_eval:n{##1}, \int_eval:n{##2}] } }
19144   \cs_set_protected:Npn \__regex_item_caseless_equal:n ##1
19145   { \__regex_show_one:n { char~code~\int_eval:n{##1}~(caseless) } }
19146   \cs_set_protected:Npn \__regex_item_caseless_range:nn ##1##2
19147   {
19148     \__regex_show_one:n
19149     { Range~[\int_eval:n{##1}, \int_eval:n{##2}]~(caseless) }
19150   }
19151   \cs_set_protected:Npn \__regex_item_catcode:nT
19152   { \__regex_show_item_catcode:NnT \c_true_bool }
19153   \cs_set_protected:Npn \__regex_item_catcode_reverse:nT
19154   { \__regex_show_item_catcode:NnT \c_false_bool }
19155   \cs_set_protected:Npn \__regex_item_reverse:n
19156   { \__regex_show_scope:nn { Reversed~match } }
19157   \cs_set_protected:Npn \__regex_item_exact:nn ##1##2
19158   { \__regex_show_one:n { char~##2,~catcode~##1 } }
19159   \cs_set_eq:NN \__regex_item_exact_cs:n \__regex_show_item_exact_cs:n
19160   \cs_set_protected:Npn \__regex_item_cs:n
19161   { \__regex_show_scope:nn { control~sequence } }
19162   \cs_set:cpn { __regex_prop_.. } { \__regex_show_one:n { any~token } }
19163   \seq_clear:N \l__regex_show_prefix_seq
19164   \__regex_show_push:n { ~ }
19165   \cs_if_exist_use:N #1
```

```

19166     \__tl_build_end:
19167 }

```

(End definition for __regex_show:N.)

__regex_show_one:n Every part of the final message go through this function, which adds one line to the output, with the appropriate prefix.

```

19168 \cs_new_protected:Npn \__regex_show_one:n #1
19169 {
19170     \int_incr:N \l__regex_show_lines_int
19171     \__tl_build_one:x
19172     {
19173         \exp_not:N \iow_newline:
19174         \seq_map_function:NN \l__regex_show_prefix_seq \use:n
19175         #1
19176     }
19177 }

```

(End definition for __regex_show_one:n.)

__regex_show_push:n Enter and exit levels of nesting. The scope function prints its first argument as an “introduction”, then performs its second argument in a deeper level of nesting.
 __regex_show_pop:
 __regex_show_scope:nn

```

19178 \cs_new_protected:Npn \__regex_show_push:n #1
19179 { \seq_put_right:Nx \l__regex_show_prefix_seq { #1 ~ } }
19180 \cs_new_protected:Npn \__regex_show_pop:
19181 { \seq_pop_right:NN \l__regex_show_prefix_seq \l__regex_internal_a_tl }
19182 \cs_new_protected:Npn \__regex_show_scope:nn #1#2
19183 {
19184     \__regex_show_one:n {#1}
19185     \__regex_show_push:n { ~ }
19186     #2
19187     \__regex_show_pop:
19188 }

```

(End definition for __regex_show_push:n, __regex_show_pop:, and __regex_show_scope:nn.)

__regex_show_group_aux:nnnnN We display all groups in the same way, simply adding a message, (no capture) or (resetting), to special groups. The odd \use_ii:nn avoids printing a spurious +-branch for the first branch.

```

19189 \cs_new_protected:Npn \__regex_show_group_aux:nnnnN #1#2#3#4#5
19190 {
19191     \__regex_show_one:n { , -group~begin #1 }
19192     \__regex_show_push:n { | }
19193     \use_ii:nn #2
19194     \__regex_show_pop:
19195     \__regex_show_one:n
19196     { ‘-group~end \__regex_msg_repeated:nnN {#3} {#4} #5 }
19197 }

```

(End definition for __regex_show_group_aux:nnnnN.)

__regex_show_class:NnnnN I’m entirely unhappy about this function: I couldn’t find a way to test if a class is a single test. Instead, collect the representation of the tests in the class. If that had more than one line, write Match or Don’t match on its own line, with the repeating information if any. Then the various tests on lines of their own, and finally a line. Otherwise, we need

to evaluate the representation of the tests again (since the prefix is incorrect). That's clunky, but not too expensive, since it's only one test.

```

19198 \cs_set:Npn \__regex_show_class:NnnnN #1#2#3#4#5
19199 {
19200   \__tl_build:Nw \l__regex_internal_a_tl
19201   \int_zero:N \l__regex_show_lines_int
19202   \__regex_show_push:n {~}
19203   #2
19204   \exp_last_unbraced:Nf
19205   \int_case:nnF { \l__regex_show_lines_int }
19206   {
19207     {0}
19208     {
19209       \__tl_build_end:
19210       \__regex_show_one:n { \bool_if:NTF #1 { Fail } { Pass } }
19211     }
19212     {1}
19213     {
19214       \__tl_build_end:
19215       \bool_if:NTF #1
19216       {
19217         #2
19218         \__tl_build_one:n { \__regex_msg_repeated:nnN {#3} {#4} #5 }
19219       }
19220       {
19221         \__regex_show_one:n
19222         { Don't~match~\__regex_msg_repeated:nnN {#3} {#4} #5 }
19223         \__tl_build_one:o \l__regex_internal_a_tl
19224       }
19225     }
19226   }
19227   {
19228     \__tl_build_end:
19229     \__regex_show_one:n
19230     {
19231       \bool_if:NTF #1 { M } { Don't~m } atch
19232       \__regex_msg_repeated:nnN {#3} {#4} #5
19233     }
19234     \__tl_build_one:o \l__regex_internal_a_tl
19235   }
19236 }

```

(End definition for __regex_show_class:NnnnN.)

__regex_show_anchor_to_str:N The argument is an integer telling us where the anchor is. We convert that to the relevant info.

```

19237 \cs_new:Npn \__regex_show_anchor_to_str:N #1
19238 {
19239   anchor~at~
19240   \str_case:nnF { #1 }
19241   {
19242     { \l__regex_min_pos_int } { start~(\iow_char:N\A) }
19243     { \l__regex_start_pos_int } { start~of~match~(\iow_char:N\G) }
19244     { \l__regex_max_pos_int } { end~(\iow_char:N\Z) }

```

```

19245     }
19246     { <error:~'#1'~not~recognized> }
19247 }

```

(End definition for `__regex_show_anchor_to_str:N`.)

`__regex_show_item_catcode:NnT` Produce a sequence of categories which the catcode bitmap #2 contains, and show it, indenting the tests on which this catcode constraint applies.

```

19248 \cs_new_protected:Npn \__regex_show_item_catcode:NnT #1#2
19249 {
19250   \seq_set_split:Nnn \l__regex_internal_seq { } { CBEMTPUDSLOA }
19251   \seq_set_filter:NNn \l__regex_internal_seq \l__regex_internal_seq
19252     { \int_if_odd_p:n { #2 / \int_use:c { c__regex_catcode_##1_int } } }
19253   \__regex_show_scope:nn
19254     {
19255       categories~
19256       \seq_map_function:NN \l__regex_internal_seq \use:n
19257       , ~
19258       \bool_if:NF #1 { negative~ } class
19259     }
19260 }

```

(End definition for `__regex_show_item_catcode:NnT`.)

`__regex_show_item_exact_cs:n`

```

19261 \cs_new_protected:Npn \__regex_show_item_exact_cs:n #1
19262 {
19263   \seq_set_split:Nnn \l__regex_internal_seq { \scan_stop: } {#1}
19264   \seq_set_map:NNn \l__regex_internal_seq
19265     \l__regex_internal_seq { \iow_char:N\##1 }
19266   \__regex_show_one:n
19267     { control~sequence~ \seq_use:Nn \l__regex_internal_seq { ~or~ } }
19268 }

```

(End definition for `__regex_show_item_exact_cs:n`.)

36.4 Building

36.4.1 Variables used while building

`\l__regex_min_state_int` The last state that was allocated is `\l__regex_max_state_int - 1`, so that `\l__regex_max_state_int` always points to a free state. The `min_state` variable is 1, but is included to avoid hard-coding this value everywhere.

```

19269 \int_new:N \l__regex_min_state_int
19270 \int_set:Nn \l__regex_min_state_int { 1 }
19271 \int_new:N \l__regex_max_state_int

```

(End definition for `\l__regex_min_state_int` and `\l__regex_max_state_int`.)

`\l__regex_left_state_int` Alternatives are implemented by branching from a `left` state into the various choices, then merging those into a `right` state. We store information about those states in two sequences. Those states are also used to implement group quantifiers. Most often, the `left` and `right` pointers only differ by 1.

```

19272 \int_new:N \l__regex_left_state_int

```

```

19273 \int_new:N \l__regex_right_state_int
19274 \seq_new:N \l__regex_left_state_seq
19275 \seq_new:N \l__regex_right_state_seq

```

(End definition for `\l__regex_left_state_int` and others.)

`\l__regex_capturing_group_int` `\l__regex_capturing_group_int` is the next ID number to be assigned to a capturing group. This starts at 0 for the group enclosing the full regular expression, and groups are counted in the order of their left parenthesis, except when encountering **resetting** groups.

```

19276 \int_new:N \l__regex_capturing_group_int

```

(End definition for `\l__regex_capturing_group_int`.)

36.4.2 Framework

This phase is about going from a compiled regex to an NFA. Each state of the NFA is stored in a `\toks`. The operations which can appear in the `\toks` are

- `__regex_action_start_wildcard`: inserted at the start of the regular expression to make it unanchored.
- `__regex_action_success`: marks the exit state of the NFA.
- `__regex_action_cost:n {⟨shift⟩}` is a transition from the current `⟨state⟩` to `⟨state⟩ + ⟨shift⟩`, which consumes the current character: the target state is saved and will be considered again when matching at the next position.
- `__regex_action_free:n {⟨shift⟩}`, and `__regex_action_free_group:n {⟨shift⟩}` are free transitions, which immediately perform the actions for the state `⟨state⟩ + ⟨shift⟩` of the NFA. They differ in how they detect and avoid infinite loops. For now, we just need to know that the `group` variant must be used for transitions back to the start of a group.
- `__regex_action_submatch:n {⟨key⟩}` where the `⟨key⟩` is a group number followed by `<` or `>` for the beginning or end of group. This causes the current position in the query to be stored as the `⟨key⟩` submatch boundary.

We strive to preserve the following properties while building.

- The current capturing group is `capturing_group - 1`, and if a group opened now it would be labelled `capturing_group`.
- The last allocated state is `max_state - 1`, so `max_state` is a free state.
- The `left_state` points to a state to the left of the current group or of the last class.
- The `right_state` points to a newly created, empty state, with some transitions leading to it.
- The `left/right` sequences hold a list of the corresponding end-points of nested groups.

`__regex_build:n` The `n`-type function first compiles its argument. Reset some variables. Allocate two states, and put a wildcard in state 0 (transitions to state 1 and 0 state). Then build the regex within a (capturing) group numbered 0 (current value of `capturing_group`). Finally, if the match reaches the last state, it is successful.

```

19277 \cs_new_protected:Npn \__regex_build:n #1
19278 {
19279     \__regex_compile:n {#1}
19280     \__regex_build:N \l__regex_internal_regex
19281 }
19282 \__debug_patch:nnNnpn
19283 { \__debug_trace_push:nnN { regex } { 1 } \__regex_build:N }
19284 {
19285     \__regex_trace_states:n { 2 }
19286     \__debug_trace_pop:nnN { regex } { 1 } \__regex_build:N
19287 }
19288 \cs_new_protected:Npn \__regex_build:N #1
19289 {
19290     \__regex_standard_escapechar:
19291     \int_zero:N \l__regex_capturing_group_int
19292     \int_set_eq:NN \l__regex_max_state_int \l__regex_min_state_int
19293     \__regex_build_new_state:
19294     \__regex_build_new_state:
19295     \__regex_toks_put_right:Nn \l__regex_left_state_int
19296     { \__regex_action_start_wildcard: }
19297     \__regex_group:nnnN {#1} { 1 } { 0 } \c_false_bool
19298     \__regex_toks_put_right:Nn \l__regex_right_state_int
19299     { \__regex_action_success: }
19300 }

```

(End definition for `__regex_build:n` and `__regex_build:N`.)

`__regex_build_for_cs:n` When using a regex to match a `cs`, we don't insert a wildcard, we anchor at the end, and since we ignore submatches, there is no need to surround the expression with a group. However, for branches to work properly at the outer level, we need to put the appropriate `left` and `right` states in their sequence.

```

19301 \__debug_patch:nnNnpn
19302 { \__debug_trace_push:nnN { regex } { 1 } \__regex_build_for_cs:n }
19303 {
19304     \__regex_trace_states:n { 2 }
19305     \__debug_trace_pop:nnN { regex } { 1 } \__regex_build_for_cs:n
19306 }
19307 \cs_new_protected:Npn \__regex_build_for_cs:n #1
19308 {
19309     \int_set_eq:NN \l__regex_max_state_int \l__regex_min_state_int
19310     \__regex_build_new_state:
19311     \__regex_build_new_state:
19312     \__regex_push_lr_states:
19313     #1
19314     \__regex_pop_lr_states:
19315     \__regex_toks_put_right:Nn \l__regex_right_state_int
19316     {
19317         \if_int_compare:w \l__regex_curr_pos_int = \l__regex_max_pos_int
19318         \exp_after:wN \__regex_action_success:
19319         \fi:

```

```

19320     }
19321 }

```

(End definition for `_regex_build_for_cs:n`.)

36.4.3 Helpers for building an nfa

`_regex_push_lr_states:` When building the regular expression, we keep track of pointers to the left-end and right-end of each group without help from T_EX's grouping.

```

19322 \cs_new_protected:Npn \_regex_push_lr_states:
19323 {
19324   \seq_push:Nn \l__regex_left_state_seq
19325   { \int_use:N \l__regex_left_state_int }
19326   \seq_push:Nn \l__regex_right_state_seq
19327   { \int_use:N \l__regex_right_state_int }
19328 }
19329 \cs_new_protected:Npn \_regex_pop_lr_states:
19330 {
19331   \seq_pop:Nn \l__regex_left_state_seq \l__regex_internal_a_tl
19332   \int_set:Nn \l__regex_left_state_int \l__regex_internal_a_tl
19333   \seq_pop:Nn \l__regex_right_state_seq \l__regex_internal_a_tl
19334   \int_set:Nn \l__regex_right_state_int \l__regex_internal_a_tl
19335 }

```

(End definition for `_regex_push_lr_states:` and `_regex_pop_lr_states:`.)

`_regex_build_transition_left:NNN` Add a transition from #2 to #3 using the function #1. The `left` function is used for higher priority transitions, and the `right` function for lower priority transitions (which should be performed later). The signatures differ to reflect the differing usage later on. Both functions could be optimized.

```

19336 \cs_new_protected:Npn \_regex_build_transition_left:NNN #1#2#3
19337 { \_regex_toks_put_left:Nx #2 { #1 { \int_eval:n { #3 - #2 } } } }
19338 \cs_new_protected:Npn \_regex_build_transition_right:nNn #1#2#3
19339 { \_regex_toks_put_right:Nx #2 { #1 { \int_eval:n { #3 - #2 } } } }

```

(End definition for `_regex_build_transition_left:NNN` and `_regex_build_transition_right:nNn`.)

`_regex_build_new_state:` Add a new empty state to the NFA. Then update the `left`, `right`, and `max` states, so that the `right` state is the new empty state, and the `left` state points to the previously “current” state.

```

19340 \__debug_patch:nnNNpn
19341 {
19342   \__debug_trace:nxx { regex } { 2 }
19343   {
19344     regex~new-state~
19345     L=\int_use:N \l__regex_left_state_int ~ -> ~
19346     R=\int_use:N \l__regex_right_state_int ~ -> ~
19347     M=\int_use:N \l__regex_max_state_int ~ -> ~
19348     \int_eval:n { \l__regex_max_state_int + 1 }
19349   }
19350 }
19351 { }
19352 \cs_new_protected:Npn \_regex_build_new_state:
19353 {

```



```

19354     \_regex_toks_clear:N \l__regex_max_state_int
19355     \int_set_eq:NN \l__regex_left_state_int \l__regex_right_state_int
19356     \int_set_eq:NN \l__regex_right_state_int \l__regex_max_state_int
19357     \int_incr:N \l__regex_max_state_int
19358 }

```

(End definition for _regex_build_new_state:.)

_regex_build_transitions_lazy:NNNNN

This function creates a new state, and puts two transitions starting from the old current state. The order of the transitions is controlled by #1, true for lazy quantifiers, and false for greedy quantifiers.

```

19359 \cs_new_protected:Npn \_regex_build_transitions_lazy:NNNNN #1#2#3#4#5
19360 {
19361     \_regex_build_new_state:
19362     \_regex_toks_put_right:Nx \l__regex_left_state_int
19363     {
19364         \if_meaning:w \c_true_bool #1
19365             #2 { \int_eval:n { #3 - \l__regex_left_state_int } }
19366             #4 { \int_eval:n { #5 - \l__regex_left_state_int } }
19367         \else:
19368             #4 { \int_eval:n { #5 - \l__regex_left_state_int } }
19369             #2 { \int_eval:n { #3 - \l__regex_left_state_int } }
19370         \fi:
19371     }
19372 }

```

(End definition for _regex_build_transitions_lazy:NNNNN.)

36.4.4 Building classes

_regex_class:NnnnN
_regex_tests_action_cost:n

The arguments are: $\langle\text{boolean}\rangle$ $\{\langle\text{tests}\rangle\}$ $\{\langle\text{min}\rangle\}$ $\{\langle\text{more}\rangle\}$ $\langle\text{lazy:ness}\rangle$. First store the tests with a trailing _regex_action_cost:n, in the true branch of _regex_break_point:TF for positive classes, or the false branch for negative classes. The integer $\langle\text{more}\rangle$ is 0 for fixed repetitions, -1 for unbounded repetitions, and $\langle\text{max}\rangle - \langle\text{min}\rangle$ for a range of repetitions.

```

19373 \cs_new_protected:Npn \_regex_class:NnnnN #1#2#3#4#5
19374 {
19375     \cs_set:Npx \_regex_tests_action_cost:n ##1
19376     {
19377         \exp_not:n { \exp_not:n {#2} }
19378         \bool_if:NTF #1
19379             { \_regex_break_point:TF { \_regex_action_cost:n {##1} } { } }
19380             { \_regex_break_point:TF { } { \_regex_action_cost:n {##1} } }
19381     }
19382     \if_case:w - #4 \exp_stop_f:
19383         \_regex_class_repeat:n {#3}
19384     \or: \_regex_class_repeat:nN {#3} #5
19385     \else: \_regex_class_repeat:nnN {#3} {#4} #5
19386     \fi:
19387 }
19388 \cs_new:Npn \_regex_tests_action_cost:n { \_regex_action_cost:n }

```

(End definition for _regex_class:NnnnN and _regex_tests_action_cost:n.)

`_regex_class_repeat:n` This is used for a fixed number of repetitions. Build one state for each repetition, with a transition controlled by the tests that we have collected. That works just fine for `#1 = 0` repetitions: nothing is built.

```

19389 \cs_new_protected:Npn \_regex_class_repeat:n #1
19390 {
19391   \prg_replicate:nn {#1}
19392   {
19393     \_regex_build_new_state:
19394     \_regex_build_transition_right:nNn \_regex_tests_action_cost:n
19395     \l__regex_left_state_int \l__regex_right_state_int
19396   }
19397 }

```

(End definition for `_regex_class_repeat:n`.)

`_regex_class_repeat:nN` This implements unbounded repetitions of a single class (e.g. the `*` and `+` quantifiers). If the minimum number `#1` of repetitions is 0, then build a transition from the current state to itself governed by the tests, and a free transition to a new state (hence skipping the tests). Otherwise, call `_regex_class_repeat:n` for the code to match `#1` repetitions, and add free transitions from the last state to the previous one, and to a new one. In both cases, the order of transitions is controlled by the laziness boolean `#2`.

```

19398 \cs_new_protected:Npn \_regex_class_repeat:nN #1#2
19399 {
19400   \if_int_compare:w #1 = 0 \exp_stop_f:
19401     \_regex_build_transitions_lazyness:NNNNN #2
19402     \_regex_action_free:n \l__regex_right_state_int
19403     \_regex_tests_action_cost:n \l__regex_left_state_int
19404   \else:
19405     \_regex_class_repeat:n {#1}
19406     \int_set_eq:NN \l__regex_internal_a_int \l__regex_left_state_int
19407     \_regex_build_transitions_lazyness:NNNNN #2
19408     \_regex_action_free:n \l__regex_right_state_int
19409     \_regex_action_free:n \l__regex_internal_a_int
19410   \fi:
19411 }

```

(End definition for `_regex_class_repeat:nN`.)

`_regex_class_repeat:nnN` We want to build the code to match from `#1` to `#1 + #2` repetitions. Match `#1` repetitions (can be 0). Compute the final state of the next construction as `a`. Build `#2 > 0` states, each with a transition to the next state governed by the tests, and a transition to the final state `a`. The computation of `a` is safe because states are allocated in order, starting from `max_state`.

```

19412 \cs_new_protected:Npn \_regex_class_repeat:nnN #1#2#3
19413 {
19414   \_regex_class_repeat:n {#1}
19415   \int_set:Nn \l__regex_internal_a_int
19416     { \l__regex_max_state_int + #2 - 1 }
19417   \prg_replicate:nn { #2 }
19418   {
19419     \_regex_build_transitions_lazyness:NNNNN #3
19420     \_regex_action_free:n \l__regex_internal_a_int
19421     \_regex_tests_action_cost:n \l__regex_right_state_int

```

```

19422     }
19423 }

```

(End definition for `_regex_class_repeat:nnN`.)

36.4.5 Building groups

`_regex_group_aux:nnnnN` Arguments: $\{\langle label \rangle\} \{\langle contents \rangle\} \{\langle min \rangle\} \{\langle more \rangle\} \langle lazyness \rangle$. If $\langle min \rangle$ is 0, we need to add a state before building the group, so that the thread which skips the group does not also set the start-point of the submatch. After adding one more state, the `left_state` is the left end of the group, from which all branches stem, and the `right_state` is the right end of the group, and all branches end their course in that state. We store those two integers to be queried for each branch, we build the NFA states for the contents #2 of the group, and we forget about the two integers. Once this is done, perform the repetition: either exactly #3 times, or #3 or more times, or between #3 and #3 + #4 times, with lazyness #5. The $\langle label \rangle$ #1 is used for submatch tracking. Each of the three auxiliaries expects `left_state` and `right_state` to be set properly.

```

19424 \\_debug_patch:nnNpn
19425 { \\_debug_trace_push:nnN { regex } { 1 } \\_regex_group_aux:nnnnN }
19426 { \\_debug_trace_pop:nnN { regex } { 1 } \\_regex_group_aux:nnnnN }
19427 \\cs_new_protected:Npn \\_regex_group_aux:nnnnN #1#2#3#4#5
19428 {
19429     \\if_int_compare:w #3 = 0 \\exp_stop_f:
19430     \\_regex_build_new_state:
19431     (assert)\\assert_int:n { \\l__regex_max_state_int = \\l__regex_right_state_int + 1 }
19432     \\_regex_build_transition_right:nnN \\_regex_action_free_group:n
19433     \\l__regex_left_state_int \\l__regex_right_state_int
19434     \\fi:
19435     \\_regex_build_new_state:
19436     \\_regex_push_lr_states:
19437     #2
19438     \\_regex_pop_lr_states:
19439     \\if_case:w - #4 \\exp_stop_f:
19440         \\_regex_group_repeat:nn {#1} {#3}
19441     \\or: \\_regex_group_repeat:nnN {#1} {#3} #5
19442     \\else: \\_regex_group_repeat:nnnnN {#1} {#3} {#4} #5
19443     \\fi:
19444 }

```

(End definition for `_regex_group_aux:nnnnN`.)

`_regex_group:nnnN` Hand to `_regex_group_aux:nnnnN` the label of that group (expanded), and the group itself, with some extra commands to perform.

`_regex_group_no_capture:nnnN`

```

19445 \\cs_new_protected:Npn \\_regex_group:nnnN #1
19446 {
19447     \\exp_args:No \\_regex_group_aux:nnnnN
19448     { \\int_use:N \\l__regex_capturing_group_int }
19449     {
19450         \\int_incr:N \\l__regex_capturing_group_int
19451         #1
19452     }
19453 }
19454 \\cs_new_protected:Npn \\_regex_group_no_capture:nnnN
19455 { \\_regex_group_aux:nnnnN { -1 } }

```

(End definition for `_regex_group:nnnN` and `_regex_group_no_capture:nnnN`.)

`_regex_group_resetting:nnnN` Again, hand the label `-1` to `_regex_group_aux:nnnnN`, but this time we work a little
`_regex_group_resetting_loop:nnNn` bit harder to keep track of the maximum group label at the end of any branch, and to
reset the group number at each branch. This relies on the fact that a compiled regex
always is a sequence of items of the form `_regex_branch:n` `{<branch>}`.

```

19456 \cs_new_protected:Npn \_regex_group_resetting:nnnN #1
19457 {
19458   \_regex_group_aux:nnnnN { -1 }
19459   {
19460     \exp_args:Noo \_regex_group_resetting_loop:nnNn
19461       { \int_use:N \l__regex_capturing_group_int }
19462       { \int_use:N \l__regex_capturing_group_int }
19463       #1
19464       { ?? \prg_break:n } { }
19465     \prg_break_point:
19466   }
19467 }
19468 \cs_new_protected:Npn \_regex_group_resetting_loop:nnNn #1#2#3#4
19469 {
19470   \use_none:nn #3 { \int_set:Nn \l__regex_capturing_group_int {#1} }
19471   \int_set:Nn \l__regex_capturing_group_int {#2}
19472   #3 {#4}
19473   \exp_args:Nf \_regex_group_resetting_loop:nnNn
19474     { \int_max:nn {#1} { \l__regex_capturing_group_int } }
19475     {#2}
19476 }

```

(End definition for `_regex_group_resetting:nnnN` and `_regex_group_resetting_loop:nnNn`.)

`_regex_branch:n` Add a free transition from the left state of the current group to a brand new state,
starting point of this branch. Once the branch is built, add a transition from its last
state to the right state of the group. The left and right states of the group are extracted
from the relevant sequences.

```

19477 \__debug_patch:nnNnNpn
19478 { \__debug_trace_push:nnN { regex } { 1 } \_regex_branch:n }
19479 { \__debug_trace_pop:nnN { regex } { 1 } \_regex_branch:n }
19480 \cs_new_protected:Npn \_regex_branch:n #1
19481 {
19482   \_regex_build_new_state:
19483   \seq_get:NN \l__regex_left_state_seq \l__regex_internal_a_tl
19484   \int_set:Nn \l__regex_left_state_int \l__regex_internal_a_tl
19485   \_regex_build_transition_right:nNn \_regex_action_free:n
19486     \l__regex_left_state_int \l__regex_right_state_int
19487   #1
19488   \seq_get:NN \l__regex_right_state_seq \l__regex_internal_a_tl
19489   \_regex_build_transition_right:nNn \_regex_action_free:n
19490     \l__regex_right_state_int \l__regex_internal_a_tl
19491 }

```

(End definition for `_regex_branch:n`.)

`_regex_group_repeat:nn` This function is called to repeat a group a fixed number of times `#2`; if this is 0 we
remove the group altogether (but don't reset the `capturing_group` label). Otherwise,

the auxiliary `__regex_group_repeat_aux:n` copies `#2` times the `\toks` for the group, and leaves `internal_a` pointing to the left end of the last repetition. We only record the submatch information at the last repetition. Finally, add a state at the end (the transition to it has been taken care of by the replicating auxiliary).

```

19492 \cs_new_protected:Npn \__regex_group_repeat:nn #1#2
19493 {
19494   \if_int_compare:w #2 = 0 \exp_stop_f:
19495     \int_set:Nn \l__regex_max_state_int
19496       { \l__regex_left_state_int - 1 }
19497     \__regex_build_new_state:
19498   \else:
19499     \__regex_group_repeat_aux:n {#2}
19500     \__regex_group_submatches:nNN {#1}
19501     \l__regex_internal_a_int \l__regex_right_state_int
19502     \__regex_build_new_state:
19503   \fi:
19504 }

```

(End definition for `__regex_group_repeat:nn`.)

`__regex_group_submatches:nNN`

This inserts in states `#2` and `#3` the code for tracking submatches of the group `#1`, unless inhibited by a label of `-1`.

```

19505 \cs_new_protected:Npn \__regex_group_submatches:nNN #1#2#3
19506 {
19507   \if_int_compare:w #1 > - 1 \exp_stop_f:
19508     \__regex_toks_put_left:Nx #2 { \__regex_action_submatch:n { #1 < } }
19509     \__regex_toks_put_left:Nx #3 { \__regex_action_submatch:n { #1 > } }
19510   \fi:
19511 }

```

(End definition for `__regex_group_submatches:nNN`.)

`__regex_group_repeat_aux:n`

Here we repeat `\toks` ranging from `left_state` to `max_state`, `#1 > 0` times. First add a transition so that the copies “chain” properly. Compute the shift `c` between the original copy and the last copy we want. Shift the `right_state` and `max_state` to their final values. We then want to perform `c` copy operations. At the end, `b` is equal to the `max_state`, and `a` points to the left of the last copy of the group.

```

19512 \cs_new_protected:Npn \__regex_group_repeat_aux:n #1
19513 {
19514   \__regex_build_transition_right:nNn \__regex_action_free:n
19515     \l__regex_right_state_int \l__regex_max_state_int
19516   \int_set_eq:NN \l__regex_internal_a_int \l__regex_left_state_int
19517   \int_set_eq:NN \l__regex_internal_b_int \l__regex_max_state_int
19518   \if_int_compare:w \__int_eval:n {#1} > 1 \exp_stop_f:
19519     \int_set:Nn \l__regex_internal_c_int
19520       {
19521         ( #1 - 1 )
19522         * ( \l__regex_internal_b_int - \l__regex_internal_a_int )
19523       }
19524     \int_add:Nn \l__regex_right_state_int { \l__regex_internal_c_int }
19525     \int_add:Nn \l__regex_max_state_int { \l__regex_internal_c_int }
19526     \__regex_toks_memcpy:NNn
19527       \l__regex_internal_b_int
19528       \l__regex_internal_a_int

```

```

19529         \l__regex_internal_c_int
19530     \fi:
19531 }

```

(End definition for _regex_group_repeat_aux:n.)

_regex_group_repeat:nnN This function is called to repeat a group at least n times; the case $n = 0$ is very different from $n > 0$. Assume first that $n = 0$. Insert submatch tracking information at the start and end of the group, add a free transition from the right end to the “true” left state a (remember: in this case we had added an extra state before the left state). This forms the loop, which we break away from by adding a free transition from a to a new state.

Now consider the case $n > 0$. Repeat the group n times, chaining various copies with a free transition. Add submatch tracking only to the last copy, then add a free transition from the right end back to the left end of the last copy, either before or after the transition to move on towards the rest of the NFA. This transition can end up before submatch tracking, but that is irrelevant since it only does so when going again through the group, recording new matches. Finally, add a state; we already have a transition pointing to it from _regex_group_repeat_aux:n.

```

19532 \cs_new_protected:Npn \_regex_group_repeat:nnN #1#2#3
19533 {
19534     \if_int_compare:w #2 = 0 \exp_stop_f:
19535         \_regex_group_submatches:nnN {#1}
19536         \l__regex_left_state_int \l__regex_right_state_int
19537         \int_set:Nn \l__regex_internal_a_int
19538             { \l__regex_left_state_int - 1 }
19539         \_regex_build_transition_right:nNn \_regex_action_free:n
19540             \l__regex_right_state_int \l__regex_internal_a_int
19541         \_regex_build_new_state:
19542         \if_meaning:w \c_true_bool #3
19543             \_regex_build_transition_left:NNN \_regex_action_free:n
19544                 \l__regex_internal_a_int \l__regex_right_state_int
19545         \else:
19546             \_regex_build_transition_right:nNn \_regex_action_free:n
19547                 \l__regex_internal_a_int \l__regex_right_state_int
19548         \fi:
19549     \else:
19550         \_regex_group_repeat_aux:n {#2}
19551         \_regex_group_submatches:nnN {#1}
19552         \l__regex_internal_a_int \l__regex_right_state_int
19553         \if_meaning:w \c_true_bool #3
19554             \_regex_build_transition_right:nNn \_regex_action_free_group:n
19555                 \l__regex_right_state_int \l__regex_internal_a_int
19556         \else:
19557             \_regex_build_transition_left:NNN \_regex_action_free_group:n
19558                 \l__regex_right_state_int \l__regex_internal_a_int
19559         \fi:
19560         \_regex_build_new_state:
19561     \fi:
19562 }

```

(End definition for _regex_group_repeat:nnN.)

_regex_group_repeat:nnnN We wish to repeat the group between $\#2$ and $\#2 + \#3$ times, with a laziness controlled by $\#4$. We insert submatch tracking up front: in principle, we could avoid recording

submatches for the first #2 copies of the group, but that forces us to treat specially the case #2 = 0. Repeat that group with submatch tracking #2 + #3 times (the maximum number of repetitions). Then our goal is to add #3 transitions from the end of the #2-th group, and each subsequent groups, to the end. For a lazy quantifier, we add those transitions to the left states, before submatch tracking. For the greedy case, we add the transitions to the right states, after submatch tracking and the transitions which go on with more repetitions. In the greedy case with #2 = 0, the transition which skips over all copies of the group must be added separately, because its starting state does not follow the normal pattern: we had to add it “by hand” earlier.

```

19563 \cs_new_protected:Npn \__regex_group_repeat:nnnN #1#2#3#4
19564 {
19565   \__regex_group_submatches:nnN {#1}
19566   \l__regex_left_state_int \l__regex_right_state_int
19567   \__regex_group_repeat_aux:n { #2 + #3 }
19568   \if_meaning:w \c_true_bool #4
19569     \int_set_eq:NN \l__regex_left_state_int \l__regex_max_state_int
19570     \prg_replicate:nn { #3 }
19571     {
19572       \int_sub:Nn \l__regex_left_state_int
19573       { \l__regex_internal_b_int - \l__regex_internal_a_int }
19574       \__regex_build_transition_left:NNN \__regex_action_free:n
19575       \l__regex_left_state_int \l__regex_max_state_int
19576     }
19577   \else:
19578     \prg_replicate:nn { #3 - 1 }
19579     {
19580       \int_sub:Nn \l__regex_right_state_int
19581       { \l__regex_internal_b_int - \l__regex_internal_a_int }
19582       \__regex_build_transition_right:nNn \__regex_action_free:n
19583       \l__regex_right_state_int \l__regex_max_state_int
19584     }
19585     \if_int_compare:w #2 = 0 \exp_stop_f:
19586     \int_set:Nn \l__regex_right_state_int
19587     { \l__regex_left_state_int - 1 }
19588   \else:
19589     \int_sub:Nn \l__regex_right_state_int
19590     { \l__regex_internal_b_int - \l__regex_internal_a_int }
19591   \fi:
19592   \__regex_build_transition_right:nNn \__regex_action_free:n
19593   \l__regex_right_state_int \l__regex_max_state_int
19594 \fi:
19595 \__regex_build_new_state:
19596 }

```

(End definition for __regex_group_repeat:nnnN.)

36.4.6 Others

<pre> __regex_assertion:Nn __regex_b_test: __regex_anchor:N </pre>	<p>Usage: <code>__regex_assertion:Nn <boolean> {<test>}</code>, where the <i><test></i> is either of the two other functions. Add a free transition to a new state, conditionally to the assertion test. The <code>__regex_b_test:</code> test is used by the <code>\b</code> and <code>\B</code> escape: check if the last character was a word character or not, and do the same to the current character. The boundary-</p>
---	--

markers of the string are non-word characters for this purpose. Anchors at the start or end of match use `__regex_anchor:N`, with a position controlled by the integer #1.

```

19597 \cs_new_protected:Npn \__regex_assertion:Nn #1#2
19598 {
19599   \__regex_build_new_state:
19600   \__regex_toks_put_right:Nx \l__regex_left_state_int
19601   {
19602     \exp_not:n {#2}
19603     \__regex_break_point:TF
19604     \bool_if:NF #1 { { } }
19605     {
19606       \__regex_action_free:n
19607       {
19608         \int_eval:n
19609         { \l__regex_right_state_int - \l__regex_left_state_int }
19610       }
19611     }
19612     \bool_if:NT #1 { { } }
19613   }
19614 }
19615 \cs_new_protected:Npn \__regex_anchor:N #1
19616 {
19617   \if_int_compare:w #1 = \l__regex_curr_pos_int
19618   \exp_after:wN \__regex_break_true:w
19619   \fi:
19620 }
19621 \cs_new_protected:Npn \__regex_b_test:
19622 {
19623   \group_begin:
19624   \int_set_eq:NN \l__regex_curr_char_int \l__regex_last_char_int
19625   \__regex_prop_w:
19626   \__regex_break_point:TF
19627   { \group_end: \__regex_item_reverse:n \__regex_prop_w: }
19628   { \group_end: \__regex_prop_w: }
19629 }

```

(End definition for `__regex_assertion:Nn`, `__regex_b_test:`, and `__regex_anchor:N`.)

`__regex_command_K:` Change the starting point of the 0-th submatch (full match), and transition to a new state, pretending that this is a fresh thread.

```

19630 \cs_new_protected:Npn \__regex_command_K:
19631 {
19632   \__regex_build_new_state:
19633   \__regex_toks_put_right:Nx \l__regex_left_state_int
19634   {
19635     \__regex_action_submatch:n { 0< }
19636     \bool_set_true:N \l__regex_fresh_thread_bool
19637     \__regex_action_free:n
19638     { \int_eval:n { \l__regex_right_state_int - \l__regex_left_state_int } }
19639     \bool_set_false:N \l__regex_fresh_thread_bool
19640   }
19641 }

```

(End definition for `__regex_command_K:`.)

36.5 Matching

We search for matches by running all the execution threads through the NFA in parallel, reading one token of the query at each step. The NFA contains “free” transitions to other states, and transitions which “consume” the current token. For free transitions, the instruction at the new state of the NFA is performed immediately. When a transition consumes a character, the new state is appended to a list of “active states”, stored in `\g__regex_thread_state_intarray`: this thread is made active again when the next token is read from the query. At every step (for each token in the query), we unpack that list of active states and the corresponding submatch props, and empty those.

If two paths through the NFA “collide” in the sense that they reach the same state after reading a given token, then they only differ in how they previously matched, and any future execution would be identical for both. (Note that this would be wrong in the presence of back-references.) Hence, we only need to keep one of the two threads: the thread with the highest priority. Our NFA is built in such a way that higher priority actions always come before lower priority actions, which makes things work.

The explanation in the previous paragraph may make us think that we simply need to keep track of which states were visited at a given step: after all, the loop generated when matching `(a?)*` against `a` is broken, isn’t it? No. The group first matches `a`, as it should, then repeats; it attempts to match `a` again but fails; it skips `a`, and finds out that this state has already been seen at this position in the query: the match stops. The capturing group is (wrongly) `a`. What went wrong is that a thread collided with itself, and the later version, which has gone through the group one more times with an empty match, should have a higher priority than not going through the group.

We solve this by distinguishing “normal” free transitions `__regex_action_free:n` from transitions `__regex_action_free_group:n` which go back to the start of the group. The former keeps threads unless they have been visited by a “completed” thread, while the latter kind of transition also prevents going back to a state visited by the current thread.

36.5.1 Variables used when matching

```
\l__regex_min_pos_int
\l__regex_max_pos_int
\l__regex_curr_pos_int
\l__regex_start_pos_int
\l__regex_success_pos_int
```

The tokens in the query are indexed from `min_pos` for the first to `max_pos - 1` for the last, and their information is stored in several arrays and `\toks` registers with those numbers. We don’t start from 0 because the `\toks` registers with low numbers are used to hold the states of the NFA. We match without backtracking, keeping all threads in lockstep at the `current_pos` in the query. The starting point of the current match attempt is `start_pos`, and `success_pos`, updated whenever a thread succeeds, is used as the next starting position.

```
19642 \int_new:N \l__regex_min_pos_int
19643 \int_new:N \l__regex_max_pos_int
19644 \int_new:N \l__regex_curr_pos_int
19645 \int_new:N \l__regex_start_pos_int
19646 \int_new:N \l__regex_success_pos_int
```

(End definition for `\l__regex_min_pos_int` and others.)

```
\l__regex_curr_char_int
\l__regex_curr_catcode_int
\l__regex_last_char_int
\l__regex_case_changed_char_int
```

The character and category codes of the token at the current position; the character code of the token at the previous position; and the character code of the result of changing the case of the current token (`A-Z↔a-z`). This last integer is only computed when necessary,

and is otherwise `\c_max_int`. The `current_char` variable is also used in various other phases to hold a character code.

```
19647 \int_new:N \l__regex_curr_char_int
19648 \int_new:N \l__regex_curr_catcode_int
19649 \int_new:N \l__regex_last_char_int
19650 \int_new:N \l__regex_case_changed_char_int
```

(End definition for `\l__regex_curr_char_int` and others.)

`\l__regex_curr_state_int` For every character in the token list, each of the active states is considered in turn. The variable `\l__regex_curr_state_int` holds the state of the NFA which is currently considered: transitions are then given as shifts relative to the current state.

```
19651 \int_new:N \l__regex_curr_state_int
```

(End definition for `\l__regex_curr_state_int`.)

`\l__regex_curr_submatches_prop` The submatches for the thread which is currently active are stored in the `current_submatches` property list variable. This property list is stored by `__regex_action_cost:n` into the `\toks` register for the target state of the transition, to be retrieved when matching at the next position. When a thread succeeds, this property list is copied to `\l__regex_success_submatches_prop`: only the last successful thread remains there.

```
19652 \prop_new:N \l__regex_curr_submatches_prop
19653 \prop_new:N \l__regex_success_submatches_prop
```

(End definition for `\l__regex_curr_submatches_prop` and `\l__regex_success_submatches_prop`.)

`\l__regex_step_int` This integer, always even, is increased every time a character in the query is read, and not reset when doing multiple matches. We store in `\g__regex_state_active_intarray` the last step in which each `\state` in the NFA was encountered. This lets us break infinite loops by not visiting the same state twice in the same step. In fact, the step we store is equal to `step` when we have started performing the operations of `\toks\state`, but not finished yet. However, once we finish, we store `step + 1` in `\g__regex_state_active_intarray`. This is needed to track submatches properly (see building phase). The `step` is also used to attach each set of submatch information to a given iteration (and automatically discard it when it corresponds to a past step).

```
19654 \int_new:N \l__regex_step_int
```

(End definition for `\l__regex_step_int`.)

`\l__regex_min_active_int` All the currently active threads are kept in order of precedence in `\g__regex_thread_state_intarray`, and the corresponding submatches in the `\toks`. For our purposes, those serve as an array, indexed from `min_active` (inclusive) to `max_active` (excluded).
`\l__regex_max_active_int` At the start of every step, the whole array is unpacked, so that the space can immediately be reused, and `max_active` is reset to `min_active`, effectively clearing the array.

```
19655 \int_new:N \l__regex_min_active_int
19656 \int_new:N \l__regex_max_active_int
```

(End definition for `\l__regex_min_active_int` and `\l__regex_max_active_int`.)

`\g__regex_state_active_intarray` `\g__regex_state_active_intarray` stores the last `\step` in which each `\state` was active.
`\g__regex_thread_state_intarray` `\g__regex_thread_state_intarray` stores threads to be considered in the next step, more precisely the states in which these threads are.

```
19657 \__intarray_new:Nn \g__regex_state_active_intarray { 65536 }
19658 \__intarray_new:Nn \g__regex_thread_state_intarray { 65536 }
```

(End definition for `\g__regex_state_active_intarray` and `\g__regex_thread_state_intarray`.)

`\l__regex_every_match_tl` Every time a match is found, this token list is used. For single matching, the token list is empty. For multiple matching, the token list is set to repeat the matching, after performing some operation which depends on the user function. See `__regex_single_match:` and `__regex_multi_match:n`.

```
19659 \tl_new:N \l__regex_every_match_tl
```

(End definition for `\l__regex_every_match_tl`.)

`\l__regex_fresh_thread_bool`
`\l__regex_empty_success_bool`
`__regex_if_two_empty_matches:F` When doing multiple matches, we need to avoid infinite loops where each iteration matches the same empty token list. When an empty token list is matched, the next successful match of the same empty token list is suppressed. We detect empty matches by setting `\l__regex_fresh_thread_bool` to `true` for threads which directly come from the start of the regex or from the `\K` command, and testing that boolean whenever a thread succeeds. The function `__regex_if_two_empty_matches:F` is redefined at every match attempt, depending on whether the previous match was empty or not: if it was, then the function must cancel a purported success if it is empty and at the same spot as the previous match; otherwise, we definitely don't have two identical empty matches, so the function is `\use:n`.

```
19660 \bool_new:N \l__regex_fresh_thread_bool
19661 \bool_new:N \l__regex_empty_success_bool
19662 \cs_new_eq:NN \__regex_if_two_empty_matches:F \use:n
```

(End definition for `\l__regex_fresh_thread_bool`, `\l__regex_empty_success_bool`, and `__regex_if_two_empty_matches:F`.)

`\g__regex_success_bool`
`\l__regex_saved_success_bool`
`\l__regex_match_success_bool` The boolean `\l__regex_match_success_bool` is true if the current match attempt was successful, and `\g__regex_success_bool` is true if there was at least one successful match. This is the only global variable in this whole module, but we would need it to be local when matching a control sequence with `\c{...}`. This is done by saving the global variable into `\l__regex_saved_success_bool`, which is local, hence not affected by the changes due to inner regex functions.

```
19663 \bool_new:N \g__regex_success_bool
19664 \bool_new:N \l__regex_saved_success_bool
19665 \bool_new:N \l__regex_match_success_bool
```

(End definition for `\g__regex_success_bool`, `\l__regex_saved_success_bool`, and `\l__regex_match_success_bool`.)

36.5.2 Matching: framework

`__regex_match:n`
`__regex_match_init:` First store the query into `\toks` registers and arrays (see `__regex_query_set:nnn`). Then initialize the variables that should be set once for each user function (even for multiple matches). Namely, the overall matching is not yet successful; none of the states should be marked as visited (`\g__regex_state_active_intarray`), and we start at step 0; we pretend that there was a previous match ending at the start of the query, which was not empty (to avoid smothering an empty match at the start). Once all this is set up, we are ready for the ride. Find the first match.

```
19666 \__debug_patch:nnNNpn
19667 {
19668   \__debug_trace_push:nnN { regex } { 1 } \__regex_match:n
19669   \__debug_trace:nnx { regex } { 1 } { analyzing-query~token~list }
```

```

19670 }
19671 { \_debug_trace_pop:nnN { regex } { 1 } \_regex_match:n }
19672 \cs_new_protected:Npn \_regex_match:n #1
19673 {
19674   \int_zero:N \l__regex_balance_int
19675   \int_set:Nn \l__regex_curr_pos_int { 2 * \l__regex_max_state_int }
19676   \_regex_query_set:nnn { } { -1 } { -2 }
19677   \int_set_eq:NN \l__regex_min_pos_int \l__regex_curr_pos_int
19678   \_tl_analysis_map_inline:nn {#1}
19679     { \_regex_query_set:nnn {##1} {"##2"} {##3} }
19680   \int_set_eq:NN \l__regex_max_pos_int \l__regex_curr_pos_int
19681   \_regex_query_set:nnn { } { -1 } { -2 }
19682   \_regex_match_init:
19683   \_regex_match_once:
19684 }
19685 \_debug_patch:nnNNpn
19686 { \_debug_trace:nxx { regex } { 1 } { initializing } }
19687 { }
19688 \cs_new_protected:Npn \_regex_match_init:
19689 {
19690   \bool_gset_false:N \g__regex_success_bool
19691   \int_step_inline:nnnn
19692     \l__regex_min_state_int { 1 } { \l__regex_max_state_int - 1 }
19693     { \_intarray_gset_fast:Nnn \g__regex_state_active_intarray {##1} { 1 } }
19694   \int_set_eq:NN \l__regex_min_active_int \l__regex_max_state_int
19695   \int_zero:N \l__regex_step_int
19696   \int_set_eq:NN \l__regex_success_pos_int \l__regex_min_pos_int
19697   \int_set:Nn \l__regex_min_submatch_int
19698     { 2 * \l__regex_max_state_int }
19699   \int_set_eq:NN \l__regex_submatch_int \l__regex_min_submatch_int
19700   \bool_set_false:N \l__regex_empty_success_bool
19701 }

```

(End definition for _regex_match:n and _regex_match_init:.)

_regex_match_once: This function finds one match, then does some action defined by the `every_match` token list, which may recursively call _regex_match_once:. First initialize some variables: set the conditional which detects identical empty matches; this match attempt starts at the previous `success_pos`, is not yet successful, and has no submatches yet; clear the array of active threads, and put the starting state 0 in it. We are then almost ready to read our first token in the query, but we actually start one position earlier than the start, and `get` that token, to set `last_char` properly for word boundaries. Then call _regex_match_loop:, which runs through the query until the end or until a successful match breaks early.

```

19702 \cs_new_protected:Npn \_regex_match_once:
19703 {
19704   \if_meaning:w \c_true_bool \l__regex_empty_success_bool
19705     \cs_set:Npn \_regex_if_two_empty_matches:F
19706       { \int_compare:nNnF \l__regex_start_pos_int = \l__regex_curr_pos_int }
19707   \else:
19708     \cs_set_eq:NN \_regex_if_two_empty_matches:F \use:n
19709   \fi:
19710   \int_set_eq:NN \l__regex_start_pos_int \l__regex_success_pos_int
19711   \bool_set_false:N \l__regex_match_success_bool

```

```

19712     \prop_clear:N \l__regex_curr_submatches_prop
19713     \int_set_eq:NN \l__regex_max_active_int \l__regex_min_active_int
19714     \__regex_store_state:n { \l__regex_min_state_int }
19715     \int_set:Nn \l__regex_curr_pos_int
19716         { \l__regex_start_pos_int - 1 }
19717     \__regex_query_get:
19718     \__regex_match_loop:
19719     \l__regex_every_match_tl
19720 }

```

(End definition for __regex_match_once:.)

__regex_single_match: For a single match, the overall success is determined by whether the only match attempt is a success. When doing multiple matches, the overall matching is successful as soon as any match succeeds. Perform the action #1, then find the next match.

__regex_multi_match:n

```

19721 \cs_new_protected:Npn \__regex_single_match:
19722 {
19723     \tl_set:Nn \l__regex_every_match_tl
19724         { \bool_gset_eq:NN \g__regex_success_bool \l__regex_match_success_bool }
19725 }
19726 \cs_new_protected:Npn \__regex_multi_match:n #1
19727 {
19728     \tl_set:Nn \l__regex_every_match_tl
19729     {
19730         \if_meaning:w \c_true_bool \l__regex_match_success_bool
19731             \bool_gset_true:N \g__regex_success_bool
19732             #1
19733             \exp_after:wN \__regex_match_once:
19734         \fi:
19735     }
19736 }

```

(End definition for __regex_single_match: and __regex_multi_match:n.)

__regex_match_loop:
__regex_match_one_active:n

At each new position, set some variables and get the new character and category from the query. Then unpack the array of active threads, and clear it by resetting its length (max_active). This results in a sequence of __regex_use_state_and_submatches:nn {<state>} {<prop>}, and we consider those states one by one in order. As soon as a thread succeeds, exit the step, and, if there are threads to consider at the next position, and we have not reached the end of the string, repeat the loop. Otherwise, the last thread that succeeded is what __regex_match_once: matches. We explain the **fresh_thread** business when describing __regex_action_wildcard:.

```

19737 \cs_new_protected:Npn \__regex_match_loop:
19738 {
19739     \int_add:Nn \l__regex_step_int { 2 }
19740     \int_incr:N \l__regex_curr_pos_int
19741     \int_set_eq:NN \l__regex_last_char_int \l__regex_curr_char_int
19742     \int_set_eq:NN \l__regex_case_changed_char_int \c_max_int
19743     \__regex_query_get:
19744     \use:x
19745     {
19746         \int_set_eq:NN \l__regex_max_active_int \l__regex_min_active_int
19747         \int_step_function:nnnN
19748             { \l__regex_min_active_int }

```

```

19749         { 1 }
19750         { \l__regex_max_active_int - 1 }
19751         \__regex_match_one_active:n
19752     }
19753     \__prg_break_point:
19754     \bool_set_false:N \l__regex_fresh_thread_bool %^A was arg of break_point:n
19755     \if_int_compare:w \l__regex_max_active_int > \l__regex_min_active_int
19756         \if_int_compare:w \l__regex_curr_pos_int < \l__regex_max_pos_int
19757             \exp_after:wN \exp_after:wN \exp_after:wN \__regex_match_loop:
19758         \fi:
19759     \fi:
19760 }
19761 \cs_new:Npn \__regex_match_one_active:n #1
19762 {
19763     \__regex_use_state_and_submatches:nn
19764     { \__intarray_item_fast:Nn \g__regex_thread_state_intarray {#1} }
19765     { \__regex_toks_use:w #1 }
19766 }

```

(End definition for __regex_match_loop: and __regex_match_one_active:n.)

__regex_query_set:nnn The arguments are: tokens that o and x expand to one token of the query, the catcode, and the character code. Store those, and the current brace balance (used later to check for overall brace balance) in a \toks register and some arrays, then update the balance.

```

19767 \cs_new_protected:Npn \__regex_query_set:nnn #1#2#3
19768 {
19769     \__intarray_gset_fast:Nnn \g__regex_charcode_intarray
19770     { \l__regex_curr_pos_int } {#3}
19771     \__intarray_gset_fast:Nnn \g__regex_catcode_intarray
19772     { \l__regex_curr_pos_int } {#2}
19773     \__intarray_gset_fast:Nnn \g__regex_balance_intarray
19774     { \l__regex_curr_pos_int } { \l__regex_balance_int }
19775     \__regex_toks_set:Nn \l__regex_curr_pos_int {#1}
19776     \int_incr:N \l__regex_curr_pos_int
19777     \if_case:w #2 \exp_stop_f:
19778     \or: \int_incr:N \l__regex_balance_int
19779     \or: \int_decr:N \l__regex_balance_int
19780     \fi:
19781 }

```

(End definition for __regex_query_set:nnn.)

__regex_query_get: Extract the current character and category codes at the current position from the appropriate arrays.

```

19782 \cs_new_protected:Npn \__regex_query_get:
19783 {
19784     \l__regex_curr_char_int
19785     = \__intarray_item_fast:Nn \g__regex_charcode_intarray
19786     { \l__regex_curr_pos_int } \scan_stop:
19787     \l__regex_curr_catcode_int
19788     = \__intarray_item_fast:Nn \g__regex_catcode_intarray
19789     { \l__regex_curr_pos_int } \scan_stop:
19790 }

```

(End definition for __regex_query_get:.)

36.5.3 Using states of the nfa

`__regex_use_state:` Use the current NFA instruction. The state is initially marked as belonging to the current **step**: this allows normal free transition to repeat, but group-repeating transitions won't. Once we are done exploring all the branches it spawned, the state is marked as **step + 1**: any thread hitting it at that point will be terminated.

```

19791 \__debug_patch:nnNpn
19792 { \__debug_trace:nnx { regex } { 2 } { state~\int_use:N \l__regex_curr_state_int } }
19793 { }
19794 \cs_new_protected:Npn \__regex_use_state:
19795 {
19796   \__intarray_gset_fast:Nnn \g__regex_state_active_intarray
19797     { \l__regex_curr_state_int } { \l__regex_step_int }
19798   \__regex_toks_use:w \l__regex_curr_state_int
19799   \__intarray_gset_fast:Nnn \g__regex_state_active_intarray
19800     { \l__regex_curr_state_int } { \l__regex_step_int + 1 }
19801 }

```

(End definition for `__regex_use_state:.`)

`__regex_use_state_and_submatches:nn` This function is called as one item in the array of active threads after that array has been unpacked for a new step. Update the `current_state` and `current_submatches` and use the state if it has not yet been encountered at this step.

```

19802 \cs_new_protected:Npn \__regex_use_state_and_submatches:nn #1 #2
19803 {
19804   \int_set:Nn \l__regex_curr_state_int {#1}
19805   \if_int_compare:w
19806     \__intarray_item_fast:Nn \g__regex_state_active_intarray
19807       { \l__regex_curr_state_int }
19808       < \l__regex_step_int
19809     \tl_set:Nn \l__regex_curr_submatches_prop {#2}
19810     \exp_after:wN \__regex_use_state:
19811   \fi:
19812   \scan_stop:
19813 }

```

(End definition for `__regex_use_state_and_submatches:nn.`)

36.5.4 Actions when matching

`__regex_action_start_wildcard:` For an unanchored match, state 0 has a free transition to the next and a costly one to itself, to repeat at the next position. To catch repeated identical empty matches, we need to know if a successful thread corresponds to an empty match. The instruction resetting `\l__regex_fresh_thread_bool` may be skipped by a successful thread, hence we had to add it to `__regex_match_loop:` too.

```

19814 \cs_new_protected:Npn \__regex_action_start_wildcard:
19815 {
19816   \bool_set_true:N \l__regex_fresh_thread_bool
19817   \__regex_action_free:n {1}
19818   \bool_set_false:N \l__regex_fresh_thread_bool
19819   \__regex_action_cost:n {0}
19820 }

```

(End definition for `__regex_action_start_wildcard:.`)

`__regex_action_free:n` These functions copy a thread after checking that the NFA state has not already been used
`__regex_action_free_group:n` at this position. If not, store submatches in the new state, and insert the instructions for
`__regex_action_free_aux:nn` that state in the input stream. Then restore the old value of `\l__regex_curr_state_int`
and of the current submatches. The two types of free transitions differ by how they
test that the state has not been encountered yet: the `group` version is stricter, and will
not use a state if it was used earlier in the current thread, hence forcefully breaking the
loop, while the “normal” version will revisit a state even within the thread itself.

```

19821 \cs_new_protected:Npn __regex_action_free:n
19822   { __regex_action_free_aux:nn { > \l__regex_step_int \else: } }
19823 \cs_new_protected:Npn __regex_action_free_group:n
19824   { __regex_action_free_aux:nn { < \l__regex_step_int } }
19825 \cs_new_protected:Npn __regex_action_free_aux:nn #1#2
19826   {
19827     \use:x
19828     {
19829       \int_add:Nn \l__regex_curr_state_int {#2}
19830       \exp_not:n
19831       {
19832         \if_int_compare:w
19833           __intarray_item_fast:Nn \g__regex_state_active_intarray
19834             { \l__regex_curr_state_int }
19835           #1
19836           \exp_after:wN __regex_use_state:
19837         \fi:
19838       }
19839       \int_set:Nn \l__regex_curr_state_int
19840         { \int_use:N \l__regex_curr_state_int }
19841       \tl_set:Nn \exp_not:N \l__regex_curr_submatches_prop
19842         { \exp_not:o \l__regex_curr_submatches_prop }
19843     }
19844   }

```

(End definition for `__regex_action_free:n`, `__regex_action_free_group:n`, and `__regex_action_free_aux:nn`.)

`__regex_action_cost:n` A transition which consumes the current character and shifts the state by #1. The
resulting state is stored in the appropriate array for use at the next position, and we also
store the current submatches.

```

19845 \cs_new_protected:Npn __regex_action_cost:n #1
19846   {
19847     \exp_args:No __regex_store_state:n
19848       { __int_value:w __int_eval:n { \l__regex_curr_state_int + #1 } }
19849   }

```

(End definition for `__regex_action_cost:n`.)

`__regex_store_state:n` Put the given state in `\g__regex_thread_state_intarray`, and increment the length of
`__regex_store_submatches:` the array. Also store the current submatch in the appropriate `\toks`.

```

19850 \cs_new_protected:Npn __regex_store_state:n #1
19851   {
19852     __regex_store_submatches:
19853     __intarray_gset_fast:Nnn \g__regex_thread_state_intarray
19854       { \l__regex_max_active_int } {#1}
19855     \int_incr:N \l__regex_max_active_int

```



```

19856     }
19857 \cs_new_protected:Npn \__regex_store_submatches:
19858 {
19859     \__regex_toks_set:No \l__regex_max_active_int
19860     { \l__regex_curr_submatches_prop }
19861 }

```

(End definition for __regex_store_state:n and __regex_store_submatches:.)

__regex_disable_submatches: Some user functions don't require tracking submatches. We get a performance improvement by simply defining the relevant functions to remove their argument and do nothing with it.

```

19862 \cs_new_protected:Npn \__regex_disable_submatches:
19863 {
19864     \cs_set_protected:Npn \__regex_store_submatches: { }
19865     \cs_set_protected:Npn \__regex_action_submatch:n ##1 { }
19866 }

```

(End definition for __regex_disable_submatches:.)

__regex_action_submatch:n Update the current submatches with the information from the current position. Maybe a bottleneck.

```

19867 \cs_new_protected:Npn \__regex_action_submatch:n #1
19868 {
19869     \prop_put:Nno \l__regex_curr_submatches_prop {#1}
19870     { \int_use:N \l__regex_curr_pos_int }
19871 }

```

(End definition for __regex_action_submatch:n.)

__regex_action_success: There is a successful match when an execution path reaches the last state in the NFA, unless this marks a second identical empty match. Then mark that there was a successful match; it is empty if it is "fresh"; and we store the current position and submatches. The current step is then interrupted with __prg_break:, and only paths with higher precedence are pursued further. The values stored here may be overwritten by a later success of a path with higher precedence.

```

19872 \cs_new_protected:Npn \__regex_action_success:
19873 {
19874     \__regex_if_two_empty_matches:F
19875     {
19876         \bool_set_true:N \l__regex_match_success_bool
19877         \bool_set_eq:NN \l__regex_empty_success_bool
19878         \l__regex_fresh_thread_bool
19879         \int_set_eq:NN \l__regex_success_pos_int \l__regex_curr_pos_int
19880         \prop_set_eq:NN \l__regex_success_submatches_prop
19881         \l__regex_curr_submatches_prop
19882         \__prg_break:
19883     }
19884 }

```

(End definition for __regex_action_success:.)

36.6 Replacement

36.6.1 Variables and helpers used in replacement

`\l_regex_replacement_csnames_int` The behaviour of closing braces inside a replacement text depends on whether a sequences `\c{` or `\u{` has been encountered. The number of “open” such sequences that should be closed by `}` is stored in `\l__regex_replacement_csnames_int`, and decreased by 1 by each `}`.

```
19885 \int_new:N \l__regex_replacement_csnames_int
```

(End definition for \l__regex_replacement_csnames_int.)

`\l_regex_replacement_category_tl` This sequence of letters is used to correctly restore categories in nested constructions such as `\cL(abc\cD(_)d)`.

```
19886 \tl_new:N \l__regex_replacement_category_tl
```

```
19887 \seq_new:N \l__regex_replacement_category_seq
```

(End definition for \l__regex_replacement_category_tl and \l__regex_replacement_category_seq.)

`\l__regex_balance_tl` This token list holds the replacement text for `__regex_replacement_balance_one_match:n` while it is being built incrementally.

```
19888 \tl_new:N \l__regex_balance_tl
```

(End definition for \l__regex_balance_tl.)

`__regex_replacement_balance_one_match:n` This expects as an argument the first index of a set of entries in `\g__regex_submatch_begin_intarray` (and related arrays) which hold the submatch information for a given match. It can be used within an integer expression to obtain the brace balance incurred by performing the replacement on that match. This combines the braces lost by removing the match, braces added by all the submatches appearing in the replacement, and braces appearing explicitly in the replacement. Even though it is always redefined before use, we initialize it as for an empty replacement. An important property is that concatenating several calls to that function must result in a valid integer expression (hence a leading + in the actual definition).

```
19889 \cs_new:Npn \__regex_replacement_balance_one_match:n #1
```

```
19890 { - \__regex_submatch_balance:n {#1} }
```

(End definition for __regex_replacement_balance_one_match:n.)

`__regex_replacement_do_one_match:n` The input is the same as `__regex_replacement_balance_one_match:n`. This function is redefined to expand to the part of the token list from the end of the previous match to a given match, followed by the replacement text. Hence concatenating the result of this function with all possible arguments (one call for each match), as well as the range from the end of the last match to the end of the string, produces the fully replaced token list. The initialization does not matter, but (as an example) we set it as for an empty replacement.

```
19891 \cs_new:Npn \__regex_replacement_do_one_match:n #1
```

```
19892 {
```

```
19893   \__regex_query_range:nn
```

```
19894     { \__intarray_item_fast:Nn \g__regex_submatch_prev_intarray {#1} }
```

```
19895     { \__intarray_item_fast:Nn \g__regex_submatch_begin_intarray {#1} }
```

```
19896 }
```

(End definition for __regex_replacement_do_one_match:n.)

`_regex_replacement_exp_not:N` This function lets us navigate around the fact that the primitive `\exp_not:n` requires a braced argument. As far as I can tell, it is only needed if the user tries to include in the replacement text a control sequence set equal to a macro parameter character, such as `\c_parameter_token`. Indeed, within an x-expanding assignment, `\exp_not:N #` behaves as a single `#`, whereas `\exp_not:n {#}` behaves as a doubled `##`.

```
19897 \cs_new:Npn \_regex_replacement_exp_not:N #1 { \exp_not:n {#1} }
```

(End definition for `_regex_replacement_exp_not:N`.)

36.6.2 Query and brace balance

`_regex_query_range:nn` When it is time to extract submatches from the token list, the various tokens are stored in `\toks` registers numbered from `\l__regex_min_pos_int` inclusive to `\l__regex_max_pos_int` exclusive. The function `_regex_query_range:nn {<min>} {<max>}` unpacks registers from the position `<min>` to the position `<max> - 1` included. Once this is expanded, a second x-expansion results in the actual tokens from the query. That second expansion is only done by user functions at the very end of their operation, after checking (and correcting) the brace balance first.

`_regex_query_range_loop:ww`

```
19898 \cs_new:Npn \_regex_query_range:nn #1#2
19899 {
19900   \exp_after:wN \_regex_query_range_loop:ww
19901   \__int_value:w \__int_eval:w #1 \exp_after:wN ;
19902   \__int_value:w \__int_eval:w #2 ;
19903   \__prg_break_point:
19904 }
19905 \cs_new:Npn \_regex_query_range_loop:ww #1 ; #2 ;
19906 {
19907   \if_int_compare:w #1 < #2 \exp_stop_f:
19908   \else:
19909     \exp_after:wN \__prg_break:
19910   \fi:
19911   \_regex_toks_use:w #1 \exp_stop_f:
19912   \exp_after:wN \_regex_query_range_loop:ww
19913   \__int_value:w \__int_eval:w #1 + 1 ; #2 ;
19914 }
```

(End definition for `_regex_query_range:nn` and `_regex_query_range_loop:ww`.)

`_regex_query_submatch:n` Find the start and end positions for a given submatch (of a given match).

```
19915 \cs_new:Npn \_regex_query_submatch:n #1
19916 {
19917   \_regex_query_range:nn
19918   { \__intarray_item_fast:Nn \g__regex_submatch_begin_intarray {#1} }
19919   { \__intarray_item_fast:Nn \g__regex_submatch_end_intarray {#1} }
19920 }
```

(End definition for `_regex_query_submatch:n`.)

`_regex_submatch_balance:n` Every user function must result in a balanced token list (unbalanced token lists cannot be stored by TeX). When we unpacked the query, we kept track of the brace balance, hence the contribution from a given range is the difference between the brace balances at the `<max pos>` and `<min pos>`. These two positions are found in the corresponding “submatch” arrays.

```

19921 \cs_new_protected:Npn \__regex_submatch_balance:n #1
19922 {
19923   \__int_eval:n
19924   {
19925     \int_compare:nNnTF
19926     { \__intarray_item_fast:Nn \g__regex_submatch_end_intarray {#1} } = 0
19927     { 0 }
19928     {
19929       \__intarray_item_fast:Nn \g__regex_balance_intarray
19930       { \__intarray_item_fast:Nn \g__regex_submatch_end_intarray {#1} }
19931     }
19932     -
19933     \int_compare:nNnTF
19934     { \__intarray_item_fast:Nn \g__regex_submatch_begin_intarray {#1} } = 0
19935     { 0 }
19936     {
19937       \__intarray_item_fast:Nn \g__regex_balance_intarray
19938       { \__intarray_item_fast:Nn \g__regex_submatch_begin_intarray {#1} }
19939     }
19940   }
19941 }

```

(End definition for `__regex_submatch_balance:n`.)

36.6.3 Framework

`__regex_replacement:n` The replacement text is built incrementally by abusing `\toks` within a group (see `!3tl-build`). We keep track in `\l__regex_balance_int` of the balance of explicit begin- and end-group tokens and we store in `\l__regex_balance_tl` some code to compute the brace balance from submatches (see its description). Detect unescaped right braces, and escaped characters, with trailing `\prg_do_nothing:` because some of the later function look-ahead. Once the whole replacement text has been parsed, make sure that there is no open csname. Finally, define the `balance_one_match` and `do_one_match` functions.

```

19942 \__debug_patch:nnNpn
19943 { \__debug_trace_push:nnN { regex } { 1 } \__regex_replacement:n }
19944 { \__debug_trace_pop:nnN { regex } { 1 } \__regex_replacement:n }
19945 \cs_new_protected:Npn \__regex_replacement:n #1
19946 {
19947   \__tl_build:Nw \l__regex_internal_a_tl
19948   \int_zero:N \l__regex_balance_int
19949   \tl_clear:N \l__regex_balance_tl
19950   \__regex_escape_use:nnnn
19951   {
19952     \if_charcode:w \c_right_brace_str ##1
19953       \__regex_replacement_rbrace:N
19954     \else:
19955       \__regex_replacement_normal:n
19956     \fi:
19957     ##1
19958   }
19959   { \__regex_replacement_escaped:N ##1 }
19960   { \__regex_replacement_normal:n ##1 }
19961   {#1}
19962   \prg_do_nothing: \prg_do_nothing:

```

```

19963 \if_int_compare:w \l__regex_replacement_csnames_int > 0 \exp_stop_f:
19964 \__msg_kernel_error:nxx { kernel } { replacement-missing-rbrace }
19965 { \int_use:N \l__regex_replacement_csnames_int }
19966 \__tl_build_one:x
19967 { \prg_replicate:nn \l__regex_replacement_csnames_int \cs_end: }
19968 \fi:
19969 \seq_if_empty:NF \l__regex_replacement_category_seq
19970 {
19971 \__msg_kernel_error:nxx { kernel } { replacement-missing-rparen }
19972 { \seq_count:N \l__regex_replacement_category_seq }
19973 \seq_clear:N \l__regex_replacement_category_seq
19974 }
19975 \cs_gset:Npx \__regex_replacement_balance_one_match:n ##1
19976 {
19977 + \int_use:N \l__regex_balance_int
19978 \l__regex_balance_tl
19979 - \__regex_submatch_balance:n {##1}
19980 }
19981 \__tl_build_end:
19982 \exp_args:No \__regex_replacement_aux:n \l__regex_internal_a_tl
19983 }
19984 \cs_new_protected:Npn \__regex_replacement_aux:n #1
19985 {
19986 \cs_set:Npn \__regex_replacement_do_one_match:n ##1
19987 {
19988 \__regex_query_range:nn
19989 { \__intarray_item_fast:Nn \g__regex_submatch_prev_intarray {##1} }
19990 { \__intarray_item_fast:Nn \g__regex_submatch_begin_intarray {##1} }
19991 #1
19992 }
19993 }

```

(End definition for __regex_replacement:n and __regex_replacement_aux:n.)

__regex_replacement_normal:n Most characters are simply sent to the output by __tl_build_one:n, unless a particular category code has been requested: then __regex_replacement_c_A:w or a similar auxiliary is called. One exception is right parentheses, which restore the category code in place before the group started. Note that the sequence is non-empty there: it contains an empty entry corresponding to the initial value of \l__regex_replacement_category_tl.

```

19994 \cs_new_protected:Npn \__regex_replacement_normal:n #1
19995 {
19996 \tl_if_empty:NTF \l__regex_replacement_category_tl
19997 { \__tl_build_one:n {#1} }
19998 { % (
19999 \token_if_eq_charcode:NNTF #1 )
20000 {
20001 \seq_pop:NN \l__regex_replacement_category_seq
20002 \l__regex_replacement_category_tl
20003 }
20004 {
20005 \use:c { __regex_replacement_c_ \l__regex_replacement_category_tl :w }
20006 \__regex_replacement_normal:n {#1}
20007 }
20008 }

```

```
20009 }
```

(End definition for `_regex_replacement_normal:n`.)

`_regex_replacement_escaped:N` As in parsing a regular expression, we use an auxiliary built from #1 if defined. Otherwise, check for escaped digits (standing from submatches from 0 to 9): anything else is a raw character. We use `\token_to_str:N` to give spaces the right category code.

```
20010 \cs_new_protected:Npn \_regex_replacement_escaped:N #1
20011 {
20012   \cs_if_exist_use:cF { \_regex_replacement_#1:w }
20013   {
20014     \if_int_compare:w 1 < 1#1 \exp_stop_f:
20015     \_regex_replacement_put_submatch:n {#1}
20016     \else:
20017       \exp_args:No \_regex_replacement_normal:n
20018       { \token_to_str:N #1 }
20019     \fi:
20020   }
20021 }
```

(End definition for `_regex_replacement_escaped:N`.)

36.6.4 Submatches

`_regex_replacement_put_submatch:n` Insert a submatch in the replacement text. This is dropped if the submatch number is larger than the number of capturing groups. Unless the submatch appears inside a `\c{...}` or `\u{...}` construction, it must be taken into account in the brace balance. Later on, `##1` will be replaced by a pointer to the 0-th submatch for a given match. We cannot use `\int_eval:n` because it is expandable, and would be expanded too early (short of adding `\exp_not:N`, making the code messy again).

```
20022 \cs_new_protected:Npn \_regex_replacement_put_submatch:n #1
20023 {
20024   \if_int_compare:w #1 < \l__regex_capturing_group_int
20025   \_tl_build_one:n { \_regex_query_submatch:n { #1 + ##1 } }
20026   \if_int_compare:w \l__regex_replacement_csnames_int = 0 \exp_stop_f:
20027   \tl_put_right:Nn \l__regex_balance_tl
20028   { + \_regex_submatch_balance:n { \_int_eval:n { #1+##1 } } }
20029   \fi:
20030   \fi:
20031 }
```

(End definition for `_regex_replacement_put_submatch:n`.)

`_regex_replacement_g:w` Grab digits for the `\g` escape sequence in a primitive assignment to the integer `\l__regex_internal_a_int`. At the end of the run of digits, check that it ends with a right brace.

`_regex_replacement_g_digits:NN`

```
20032 \cs_new_protected:Npn \_regex_replacement_g:w #1#2
20033 {
20034   \str_if_eq_x:nnTF { #1#2 } { \_regex_replacement_normal:n \c_left_brace_str }
20035   { \l__regex_internal_a_int = \_regex_replacement_g_digits:NN }
20036   { \_regex_replacement_error:NNN g #1 #2 }
20037 }
20038 \cs_new:Npn \_regex_replacement_g_digits:NN #1#2
20039 {
```

```

20040 \token_if_eq_meaning:NNTF #1 \_regex_replacement_normal:n
20041 {
20042   \if_int_compare:w 1 < 1#2 \exp_stop_f:
20043     #2
20044     \exp_after:wN \use_i:nnn
20045     \exp_after:wN \_regex_replacement_g_digits:NN
20046   \else:
20047     \exp_stop_f:
20048     \exp_after:wN \_regex_replacement_error:NNN
20049     \exp_after:wN g
20050   \fi:
20051 }
20052 {
20053   \exp_stop_f:
20054   \if_meaning:w \_regex_replacement_rbrace:N #1
20055     \exp_args:No \_regex_replacement_put_submatch:n
20056       { \int_use:N \l\_regex_internal_a_int }
20057     \exp_after:wN \use_none:nn
20058   \else:
20059     \exp_after:wN \_regex_replacement_error:NNN
20060     \exp_after:wN g
20061   \fi:
20062 }
20063 #1 #2
20064 }

```

(End definition for _regex_replacement_g:w and _regex_replacement_g_digits:NN.)

36.6.5 Csnames in replacement

_regex_replacement_c:w \c may only be followed by an unescaped character. If followed by a left brace, start a control sequence by calling an auxiliary common with \u. Otherwise test whether the category is known; if it is not, complain.

```

20065 \cs_new_protected:Npn \_regex_replacement_c:w #1#2
20066 {
20067   \token_if_eq_meaning:NNTF #1 \_regex_replacement_normal:n
20068   {
20069     \exp_after:wN \token_if_eq_charcode:NNTF \c_left_brace_str #2
20070     { \_regex_replacement_cu_aux:Nw \_regex_replacement_exp_not:N }
20071     {
20072       \cs_if_exist:cTF { \_regex_replacement_c:#2:w }
20073       { \_regex_replacement_cat:NNN #2 }
20074       { \_regex_replacement_error:NNN c #1#2 }
20075     }
20076   }
20077   { \_regex_replacement_error:NNN c #1#2 }
20078 }

```

(End definition for _regex_replacement_c:w.)

_regex_replacement_cu_aux:Nw Start a control sequence with \cs:w, protected from expansion by #1 (either _regex_replacement_exp_not:N or \exp_not:V), or turned to a string by \tl_to_str:V if inside another csname construction \c or \u. We use \tl_to_str:V rather than \tl_to_str:N to deal with integers and other registers.

```

20079 \cs_new_protected:Npn \__regex_replacement_cu_aux:Nw #1
20080 {
20081   \if_case:w \l__regex_replacement_csnames_int
20082     \__tl_build_one:n { \exp_not:n { \exp_after:wN #1 \cs:w } }
20083   \else:
20084     \__tl_build_one:n { \exp_not:n { \exp_after:wN \tl_to_str:V \cs:w } }
20085   \fi:
20086   \int_incr:N \l__regex_replacement_csnames_int
20087 }

```

(End definition for __regex_replacement_cu_aux:Nw.)

__regex_replacement_u:w Check that \u is followed by a left brace. If so, start a control sequence with \cs:w, which is then unpacked either with \exp_not:V or \tl_to_str:V depending on the current context.

```

20088 \cs_new_protected:Npn \__regex_replacement_u:w #1#2
20089 {
20090   \str_if_eq_x:nnTF { #1#2 } { \__regex_replacement_normal:n \c_left_brace_str }
20091   { \__regex_replacement_cu_aux:Nw \exp_not:V }
20092   { \__regex_replacement_error:NNN u #1#2 }
20093 }

```

(End definition for __regex_replacement_u:w.)

__regex_replacement_rbrace:N Within a \c{...} or \u{...} construction, end the control sequence, and decrease the brace count. Otherwise, this is a raw right brace.

```

20094 \cs_new_protected:Npn \__regex_replacement_rbrace:N #1
20095 {
20096   \if_int_compare:w \l__regex_replacement_csnames_int > 0 \exp_stop_f:
20097     \__tl_build_one:n \cs_end:
20098     \int_decr:N \l__regex_replacement_csnames_int
20099   \else:
20100     \__regex_replacement_normal:n {#1}
20101   \fi:
20102 }

```

(End definition for __regex_replacement_rbrace:N.)

36.6.6 Characters in replacement

__regex_replacement_cat:NNN Here, #1 is a letter among BEMTPUDSLOA and #2#3 denote the next character. Complain if we reach the end of the replacement or if the construction appears inside \c{...} or \u{...}, and detect the case of a parenthesis. In that case, store the current category in a sequence and switch to a new one.

```

20103 \cs_new_protected:Npn \__regex_replacement_cat:NNN #1#2#3
20104 {
20105   \token_if_eq_meaning:NNTF \prg_do_nothing: #3
20106   { \__msg_kernel_error:nn { kernel } { replacement-catcode-end } }
20107   {
20108     \int_compare:nNnTF { \l__regex_replacement_csnames_int } > 0
20109     {
20110       \__msg_kernel_error:nnnn
20111       { kernel } { replacement-catcode-in-cs } {#1} {#3}
20112       #2 #3

```



```

20113     }
20114     {
20115         \str_if_eq:nnTF { #2 #3 } { \__regex_replacement_normal:n ( } % )
20116         {
20117             \seq_push:NV \l__regex_replacement_category_seq
20118             \l__regex_replacement_category_tl
20119             \tl_set:Nn \l__regex_replacement_category_tl {#1}
20120         }
20121         {
20122             \token_if_eq_meaning:NNT #2 \__regex_replacement_escaped:N
20123             {
20124                 \__regex_char_if_alphanumeric:NTF #3
20125                 {
20126                     \__msg_kernel_error:nnnn
20127                     { kernel } { replacement-catcode-escaped }
20128                     {#1} {#3}
20129                 }
20130                 { }
20131             }
20132             \use:c { \__regex_replacement_c_#1:w } #2 #3
20133         }
20134     }
20135 }
20136 }

```

(End definition for __regex_replacement_cat:NNN.)

We now need to change the category code of the null character many times, hence work in a group. The catcode-specific macros below are defined in alphabetical order; if you are trying to understand the code, start from the end of the alphabet as those categories are simpler than active or begin-group.

20137 \group_begin:

__regex_replacement_char:nnN The only way to produce an arbitrary character-catcode pair is to use the \lowercase or \uppercase primitives. This is a wrapper for our purposes. The first argument is the null character with various catcodes. The second and third arguments are grabbed from the input stream: #3 is the character whose character code to reproduce. We could use \char_generate:nn but only for some catcodes (active characters and spaces are not supported).

```

20138 \cs_new_protected:Npn \__regex_replacement_char:nnN #1#2#3
20139 {
20140     \tex_lccode:D 0 = '#3 \scan_stop:
20141     \tex_lowercase:D { \__tl_build_one:n {#1} }
20142 }

```

(End definition for __regex_replacement_char:nnN.)

__regex_replacement_c_A:w For an active character, expansion must be avoided, twice because we later do two x-expansions, to unpack \toks for the query, and to expand their contents to tokens of the query.

```

20143 \char_set_catcode_active:N ^^@
20144 \cs_new_protected:Npn \__regex_replacement_c_A:w
20145 { \__regex_replacement_char:nnN { \exp_not:n { \exp_not:N ^^@ } } }

```

(End definition for __regex_replacement_c_A:w.)

`_regex_replacement_c_B:w` An explicit begin-group token increases the balance, unless within a `\c{...}` or `\u{...}` construction. Add the desired begin-group character, using the standard `\if_false:` trick. We eventually x-expand twice. The first time must yield a balanced token list, and the second one gives the bare begin-group token. The `\exp_after:wN` is not strictly needed, but is more consistent with `l3tl-analysis`.

```

20146 \char_set_catcode_group_begin:N \^^@
20147 \cs_new_protected:Npn \_regex_replacement_c_B:w
20148 {
20149   \if_int_compare:w \l__regex_replacement_csnames_int = 0 \exp_stop_f:
20150   \int_incr:N \l__regex_balance_int
20151   \fi:
20152   \_regex_replacement_char:nNN
20153   { \exp_not:n { \exp_after:wN \^^@ \if_false: } \fi: } }
20154 }
```

(End definition for `_regex_replacement_c_B:w`.)

`_regex_replacement_c_C:w` This is not quite catcode-related: when the user requests a character with category “control sequence”, the one-character control symbol is returned. As for the active character, we prepare for two x-expansions.

```

20155 \cs_new_protected:Npn \_regex_replacement_c_C:w #1#2
20156 { \__tl_build_one:n { \exp_not:N \exp_not:N \exp_not:c {#2} } }
```

(End definition for `_regex_replacement_c_C:w`.)

`_regex_replacement_c_D:w` Subscripts fit the mould: `\lowercase` the null byte with the correct category.

```

20157 \char_set_catcode_math_subscript:N \^^@
20158 \cs_new_protected:Npn \_regex_replacement_c_D:w
20159 { \_regex_replacement_char:nNN { \^^@ } }
```

(End definition for `_regex_replacement_c_D:w`.)

`_regex_replacement_c_E:w` Similar to the begin-group case, the second x-expansion produces the bare end-group token.

```

20160 \char_set_catcode_group_end:N \^^@
20161 \cs_new_protected:Npn \_regex_replacement_c_E:w
20162 {
20163   \if_int_compare:w \l__regex_replacement_csnames_int = 0 \exp_stop_f:
20164   \int_decr:N \l__regex_balance_int
20165   \fi:
20166   \_regex_replacement_char:nNN
20167   { \exp_not:n { \if_false: { \fi: \^^@ } } }
20168 }
```

(End definition for `_regex_replacement_c_E:w`.)

`_regex_replacement_c_L:w` Simply `\lowercase` a letter null byte to produce an arbitrary letter.

```

20169 \char_set_catcode_letter:N \^^@
20170 \cs_new_protected:Npn \_regex_replacement_c_L:w
20171 { \_regex_replacement_char:nNN { \^^@ } }
```

(End definition for `_regex_replacement_c_L:w`.)

`_regex_replacement_c_M:w` No surprise here, we lowercase the null math toggle.

```

20172 \char_set_catcode_math_toggle:N \^^@
20173 \cs_new_protected:Npn \_regex_replacement_c_M:w
20174 { \_regex_replacement_char:nNN { ^^@ } }

```

(End definition for _regex_replacement_c_M:w.)

`_regex_replacement_c_O:w` Lowercase an other null byte.

```

20175 \char_set_catcode_other:N \^^@
20176 \cs_new_protected:Npn \_regex_replacement_c_O:w
20177 { \_regex_replacement_char:nNN { ^^@ } }

```

(End definition for _regex_replacement_c_O:w.)

`_regex_replacement_c_P:w` For macro parameters, expansion is a tricky issue. We need to prepare for two x-expansions and passing through various macro definitions. Note that we cannot replace one `\exp_not:n` by doubling the macro parameter characters because this would misbehave if a mischievous user asks for `\c{\cP\#}`, since that macro parameter character would be doubled.

```

20178 \char_set_catcode_parameter:N \^^@
20179 \cs_new_protected:Npn \_regex_replacement_c_P:w
20180 {
20181   \_regex_replacement_char:nNN
20182   { \exp_not:n { \exp_not:n { ^^@^^@^^@^^@ } } }
20183 }

```

(End definition for _regex_replacement_c_P:w.)

`_regex_replacement_c_S:w` Spaces are normalized on input by T_EX to have character code 32. It is in fact impossible to get a token with character code 0 and category code 10. Hence we use 32 instead of 0 as our base character.

```

20184 \cs_new_protected:Npn \_regex_replacement_c_S:w #1#2
20185 {
20186   \if_int_compare:w '#2 = 0 \exp_stop_f:
20187   \_msg_kernel_error:nn { kernel } { replacement-null-space }
20188   \fi:
20189   \tex_lccode:D '\ = '#2 \scan_stop:
20190   \tex_lowercase:D { \_tl_build_one:n {~} }
20191 }

```

(End definition for _regex_replacement_c_S:w.)

`_regex_replacement_c_T:w` No surprise for alignment tabs here. Those are surrounded by the appropriate braces whenever necessary, hence they don't cause trouble in alignment settings.

```

20192 \char_set_catcode_alignment:N \^^@
20193 \cs_new_protected:Npn \_regex_replacement_c_T:w
20194 { \_regex_replacement_char:nNN { ^^@ } }

```

(End definition for _regex_replacement_c_T:w.)

`_regex_replacement_c_U:w` Simple call to `_regex_replacement_char:nNN` which lowercases the math superscript `^^@`.

```

20195 \char_set_catcode_math_superscript:N \^^@
20196 \cs_new_protected:Npn \_regex_replacement_c_U:w
20197 { \_regex_replacement_char:nNN { ^^@ } }

```

(End definition for `_regex_replacement_c_U:w`.)

Restore the catcode of the null byte.

20198 `\group_end:`

36.6.7 An error

`_regex_replacement_error:NNN` Simple error reporting by calling one of the messages `replacement-c`, `replacement-g`, or `replacement-u`.

```
20199 \cs_new_protected:Npn \_regex_replacement_error:NNN #1#2#3
20200 {
20201   \__msg_kernel_error:nxx { kernel } { replacement-#1 } {#3}
20202   #2 #3
20203 }
```

(End definition for `_regex_replacement_error:NNN`.)

36.7 User functions

`\regex_new:N` Before being assigned a sensible value, a regex variable matches nothing.

```
20204 \cs_new_protected:Npn \regex_new:N #1
20205 { \cs_new_eq:NN #1 \c__regex_no_match_regex }
```

(End definition for `\regex_new:N`. This function is documented on page 212.)

`\regex_set:Nn` Compile, then store the result in the user variable with the appropriate assignment function.

`\regex_gset:Nn`
`\regex_const:Nn`

```
20206 \cs_new_protected:Npn \regex_set:Nn #1#2
20207 {
20208   \__regex_compile:n {#2}
20209   \tl_set_eq:NN #1 \l__regex_internal_regex
20210 }
20211 \cs_new_protected:Npn \regex_gset:Nn #1#2
20212 {
20213   \__regex_compile:n {#2}
20214   \tl_gset_eq:NN #1 \l__regex_internal_regex
20215 }
20216 \cs_new_protected:Npn \regex_const:Nn #1#2
20217 {
20218   \__regex_compile:n {#2}
20219   \tl_const:Nx #1 { \exp_not:o \l__regex_internal_regex }
20220 }
```

(End definition for `\regex_set:Nn`, `\regex_gset:Nn`, and `\regex_const:Nn`. These functions are documented on page 212.)

`\regex_show:N` User functions: the `n` variant requires compilation first. Then show the variable with some appropriate text. The auxiliary is defined in a different section.

`\regex_show:n`

```
20221 \cs_new_protected:Npn \regex_show:n #1
20222 {
20223   \__regex_compile:n {#1}
20224   \__regex_show:N \l__regex_internal_regex
20225   \msg_show:nnxxxx { LaTeX / kernel } { show-regex }
20226   { \tl_to_str:n {#1} } { }
20227   { \l__regex_internal_a_tl } { }
```

```

20228 }
20229 \cs_new_protected:Npn \regex_show:N #1
20230 {
20231   \__kernel_check_defined:NT #1
20232   {
20233     \__regex_show:N #1
20234     \msg_show:nnxxxx { LaTeX / kernel } { show-regex }
20235     { } { \token_to_str:N #1 }
20236     { \l__regex_internal_a_tl } { }
20237   }
20238 }

```

(End definition for `\regex_show:N` and `\regex_show:n`. These functions are documented on page 212.)

`\regex_match:nnTF`
`\regex_match:NnTF`

Those conditionals are based on a common auxiliary defined later. Its first argument builds the NFA corresponding to the regex, and the second argument is the query token list. Once we have performed the match, convert the resulting boolean to `\prg_return_true:` or false.

```

20239 \prg_new_protected_conditional:Npnn \regex_match:nn #1#2 { T , F , TF }
20240 {
20241   \__regex_if_match:nn { \__regex_build:n {#1} } {#2}
20242   \__regex_return:
20243 }
20244 \prg_new_protected_conditional:Npnn \regex_match:Nn #1#2 { T , F , TF }
20245 {
20246   \__regex_if_match:nn { \__regex_build:N #1 } {#2}
20247   \__regex_return:
20248 }

```

(End definition for `\regex_match:nnTF` and `\regex_match:NnTF`. These functions are documented on page 212.)

`\regex_count:nnN`
`\regex_count:NnN`

Again, use an auxiliary whose first argument builds the NFA.

```

20249 \cs_new_protected:Npn \regex_count:nnN #1
20250 { \__regex_count:nnN { \__regex_build:n {#1} } }
20251 \cs_new_protected:Npn \regex_count:NnN #1
20252 { \__regex_count:nnN { \__regex_build:N #1 } }

```

(End definition for `\regex_count:nnN` and `\regex_count:NnN`. These functions are documented on page 213.)

`\regex_extract_once:nnN`
`\regex_extract_once:NnN`
`\regex_extract_all:nnN`
`\regex_extract_all:NnN`
`\regex_replace_once:nnN`
`\regex_replace_once:NnN`
`\regex_replace_all:nnN`
`\regex_replace_all:NnN`
`\regex_split:nnN`
`\regex_split:NnN`
`\regex_extract_once:nnTF`
`\regex_extract_once:NnTF`
`\regex_extract_all:nnTF`
`\regex_extract_all:NnTF`
`\regex_replace_once:nnTF`
`\regex_replace_once:NnTF`
`\regex_replace_all:nnTF`
`\regex_replace_all:NnTF`
`\regex_split:nnTF`
`\regex_split:NnTF`

We define here 40 user functions, following a common pattern in terms of `:nnN` auxiliaries, defined in the coming subsections. The auxiliary is handed `__regex_build:n` or `__regex_build:N` with the appropriate regex argument, then all other necessary arguments (replacement text, token list, *etc.* The conditionals call `__regex_return:` to return either true or false once matching has been performed.

```

20253 \cs_set_protected:Npn \__regex_tmp:w #1#2#3
20254 {
20255   \cs_new_protected:Npn #2 ##1 { #1 { \__regex_build:n {##1} } }
20256   \cs_new_protected:Npn #3 ##1 { #1 { \__regex_build:N ##1 } }
20257   \prg_new_protected_conditional:Npnn #2 ##1##2##3 { T , F , TF }
20258   { #1 { \__regex_build:n {##1} } {##2} ##3 \__regex_return: }
20259   \prg_new_protected_conditional:Npnn #3 ##1##2##3 { T , F , TF }
20260   { #1 { \__regex_build:N ##1 } {##2} ##3 \__regex_return: }

```

```

20261     }
20262     \__regex_tmp:w \__regex_extract_once:nnN
20263     \regex_extract_once:nnN \regex_extract_once:NnN
20264     \__regex_tmp:w \__regex_extract_all:nnN
20265     \regex_extract_all:nnN \regex_extract_all:NnN
20266     \__regex_tmp:w \__regex_replace_once:nnN
20267     \regex_replace_once:nnN \regex_replace_once:NnN
20268     \__regex_tmp:w \__regex_replace_all:nnN
20269     \regex_replace_all:nnN \regex_replace_all:NnN
20270     \__regex_tmp:w \__regex_split:nnN \regex_split:nnN \regex_split:NnN

```

(End definition for \regex_extract_once:nnN and others. These functions are documented on page ??.)

36.7.1 Variables and helpers for user functions

\l__regex_match_count_int The number of matches found so far is stored in \l__regex_match_count_int. This is only used in the \regex_count:nnN functions.

```
20271 \int_new:N \l__regex_match_count_int
```

(End definition for \l__regex_match_count_int.)

__regex_begin __regex_end Those flags are raised to indicate extra begin-group or end-group tokens when extracting submatches.

```

20272 \flag_new:n { __regex_begin }
20273 \flag_new:n { __regex_end }

```

(End definition for __regex_begin and __regex_end.)

\l__regex_min_submatch_int \l__regex_submatch_int \l__regex_zeroth_submatch_int The end-points of each submatch are stored in two arrays whose index *<submatch>* ranges from \l__regex_min_submatch_int (inclusive) to \l__regex_submatch_int (exclusive). Each successful match comes with a 0-th submatch (the full match), and one match for each capturing group: submatches corresponding to the last successful match are labelled starting at zeroth_submatch. The entry \l__regex_zeroth_submatch_int in \g__regex_submatch_prev_intarray holds the position at which that match attempt started: this is used for splitting and replacements.

```

20274 \int_new:N \l__regex_min_submatch_int
20275 \int_new:N \l__regex_submatch_int
20276 \int_new:N \l__regex_zeroth_submatch_int

```

(End definition for \l__regex_min_submatch_int, \l__regex_submatch_int, and \l__regex_zeroth_submatch_int.)

\g__regex_submatch_prev_intarray Hold the place where the match attempt begun and the end-points of each submatch.

```

\g__regex_submatch_begin_intarray 20277 \__intarray_new:Nn \g__regex_submatch_prev_intarray { 65536 }
\g__regex_submatch_end_intarray    20278 \__intarray_new:Nn \g__regex_submatch_begin_intarray { 65536 }
20279 \__intarray_new:Nn \g__regex_submatch_end_intarray { 65536 }

```

(End definition for \g__regex_submatch_prev_intarray, \g__regex_submatch_begin_intarray, and \g__regex_submatch_end_intarray.)

`__regex_return:` This function triggers either `\prg_return_false:` or `\prg_return_true:` as appropriate to whether a match was found or not. It is used by all user conditionals.

```

20280 \cs_new_protected:Npn \__regex_return:
20281 {
20282   \if_meaning:w \c_true_bool \g__regex_success_bool
20283     \prg_return_true:
20284   \else:
20285     \prg_return_false:
20286   \fi:
20287 }

```

(End definition for __regex_return:.)

36.7.2 Matching

`__regex_if_match:nn` We don't track submatches, and stop after a single match. Build the NFA with #1, and perform the match on the query #2.

```

20288 \cs_new_protected:Npn \__regex_if_match:nn #1#2
20289 {
20290   \group_begin:
20291     \__regex_disable_submatches:
20292     \__regex_single_match:
20293     #1
20294     \__regex_match:n {#2}
20295   \group_end:
20296 }

```

(End definition for __regex_if_match:nn.)

`__regex_count:nnN` Again, we don't care about submatches. Instead of aborting after the first “longest match” is found, we search for multiple matches, incrementing `\l__regex_match_count_int` every time to record the number of matches. Build the NFA and match. At the end, store the result in the user's variable.

```

20297 \cs_new_protected:Npn \__regex_count:nnN #1#2#3
20298 {
20299   \group_begin:
20300     \__regex_disable_submatches:
20301     \int_zero:N \l__regex_match_count_int
20302     \__regex_multi_match:n { \int_incr:N \l__regex_match_count_int }
20303     #1
20304     \__regex_match:n {#2}
20305     \exp_args:NNNo
20306   \group_end:
20307   \int_set:Nn #3 { \int_use:N \l__regex_match_count_int }
20308 }

```

(End definition for __regex_count:nnN.)

36.7.3 Extracting submatches

`__regex_extract_once:nnN` Match once or multiple times. After each match (or after the only match), extract the submatches using `__regex_extract:.` At the end, store the sequence containing all the submatches into the user variable #3 after closing the group.

```

20309 \cs_new_protected:Npn \__regex_extract_once:nnN #1#2#3
20310 {
20311   \group_begin:
20312   \__regex_single_match:
20313   #1
20314   \__regex_match:n {#2}
20315   \__regex_extract:
20316   \__regex_group_end_extract_seq:N #3
20317 }
20318 \cs_new_protected:Npn \__regex_extract_all:nnN #1#2#3
20319 {
20320   \group_begin:
20321   \__regex_multi_match:n { \__regex_extract: }
20322   #1
20323   \__regex_match:n {#2}
20324   \__regex_group_end_extract_seq:N #3
20325 }

```

(End definition for __regex_extract_once:nnN and __regex_extract_all:nnN.)

__regex_split:nnN Splitting at submatches is a bit more tricky. For each match, extract all submatches, and replace the zeroth submatch by the part of the query between the start of the match attempt and the start of the zeroth submatch. This is inhibited if the delimiter matched an empty token list at the start of this match attempt. After the last match, store the last part of the token list, which ranges from the start of the match attempt to the end of the query. This step is inhibited if the last match was empty and at the very end: decrement \l__regex_submatch_int, which controls which matches will be used.

```

20326 \cs_new_protected:Npn \__regex_split:nnN #1#2#3
20327 {
20328   \group_begin:
20329   \__regex_multi_match:n
20330   {
20331     \if_int_compare:w \l__regex_start_pos_int < \l__regex_success_pos_int
20332     \__regex_extract:
20333     \__intarray_gset_fast:Nnn \g__regex_submatch_prev_intarray
20334     { \l__regex_zeroth_submatch_int } { 0 }
20335     \__intarray_gset_fast:Nnn \g__regex_submatch_end_intarray
20336     { \l__regex_zeroth_submatch_int }
20337     {
20338       \__intarray_item_fast:Nn \g__regex_submatch_begin_intarray
20339       { \l__regex_zeroth_submatch_int }
20340     }
20341     \__intarray_gset_fast:Nnn \g__regex_submatch_begin_intarray
20342     { \l__regex_zeroth_submatch_int }
20343     { \l__regex_start_pos_int }
20344   \fi:
20345   }
20346   #1
20347   \__regex_match:n {#2}
20348   (assert) \assert_int:n { \l__regex_curr_pos_int = \l__regex_max_pos_int }
20349   \__intarray_gset_fast:Nnn \g__regex_submatch_prev_intarray
20350   { \l__regex_submatch_int } { 0 }
20351   \__intarray_gset_fast:Nnn \g__regex_submatch_end_intarray
20352   { \l__regex_submatch_int }

```



```

20353     { \l__regex_max_pos_int }
20354     \__intarray_gset_fast:Nnn \g__regex_submatch_begin_intarray
20355     { \l__regex_submatch_int }
20356     { \l__regex_start_pos_int }
20357     \int_incr:N \l__regex_submatch_int
20358     \if_meaning:w \c_true_bool \l__regex_empty_success_bool
20359     \if_int_compare:w \l__regex_start_pos_int = \l__regex_max_pos_int
20360     \int_decr:N \l__regex_submatch_int
20361     \fi:
20362     \fi:
20363     \__regex_group_end_extract_seq:N #3
20364 }

```

(End definition for __regex_split:nnN.)

__regex_group_end_extract_seq:N The end-points of submatches are stored as entries of two arrays from \l__regex_min_submatch_int to \l__regex_submatch_int (exclusive). Extract the relevant ranges into \l__regex_internal_a_tl. We detect unbalanced results using the two flags @@_begin and @@_end, raised whenever we see too many begin-group or end-group tokens in a submatch. We disable __seq_item:n to prevent two x-expansions.

```

20365 \cs_new_protected:Npn \__regex_group_end_extract_seq:N #1
20366 {
20367     \cs_set_eq:NN \__seq_item:n \scan_stop:
20368     \flag_clear:n { __regex_begin }
20369     \flag_clear:n { __regex_end }
20370     \tl_set:Nx \l__regex_internal_a_tl
20371     {
20372         \s__seq
20373         \int_step_function:nnnN
20374         { \l__regex_min_submatch_int }
20375         { 1 }
20376         { \l__regex_submatch_int - 1 }
20377         \__regex_extract_seq_aux:n
20378     }
20379     \int_compare:nNnF
20380     { \flag_height:n { __regex_begin } + \flag_height:n { __regex_end } }
20381     = 0
20382     {
20383         \__msg_kernel_error:nnxxx { kernel } { result-unbalanced }
20384         { splitting~or~extracting~submatches }
20385         { \flag_height:n { __regex_end } }
20386         { \flag_height:n { __regex_begin } }
20387     }
20388     \use:x
20389     {
20390         \group_end:
20391         \tl_set:Nn \exp_not:N #1 { \l__regex_internal_a_tl }
20392     }
20393 }

```

(End definition for __regex_group_end_extract_seq:N.)

__regex_extract_seq_aux:n The :n auxiliary builds one item of the sequence of submatches. First compute the brace balance of the submatch, then extract the submatch from the query, adding the appropriate braces and raising a flag if the submatch is not balanced.

```

20394 \cs_new:Npn \__regex_extract_seq_aux:n #1
20395 {
20396   \__seq_item:n
20397   {
20398     \exp_after:wN \__regex_extract_seq_aux:ww
20399     \__int_value:w \__regex_submatch_balance:n {#1} ; #1;
20400   }
20401 }
20402 \cs_new:Npn \__regex_extract_seq_aux:ww #1; #2;
20403 {
20404   \if_int_compare:w #1 < 0 \exp_stop_f:
20405     \flag_raise:n { __regex_end }
20406     \prg_replicate:nn {-#1} { \exp_not:n { { \if_false: } \fi: } }
20407   \fi:
20408   \__regex_query_submatch:n {#2}
20409   \if_int_compare:w #1 > 0 \exp_stop_f:
20410     \flag_raise:n { __regex_begin }
20411     \prg_replicate:nn {#1} { \exp_not:n { \if_false: { \fi: } } }
20412   \fi:
20413 }

```

(End definition for __regex_extract_seq_aux:n and __regex_extract_seq_aux:ww.)

__regex_extract: Our task here is to extract from the property list \l__regex_success_submatches_prop the list of end-points of submatches, and store them in appropriate array entries, from \l__regex_extract_b:wn the list of end-points of submatches, and store them in appropriate array entries, from \l__regex_extract_e:wn \l__regex_zeroth_submatch_int upwards. We begin by emptying those entries. This is somewhat a hack: the *<key>* is a non-negative integer followed by < or >, which we use in a comparison to -1. At the end, store the information about the position at which the match attempt started, in \g__regex_submatch_prev_intarray.

```

20414 \cs_new_protected:Npn \__regex_extract:
20415 {
20416   \if_meaning:w \c_true_bool \g__regex_success_bool
20417     \int_set_eq:NN \l__regex_zeroth_submatch_int \l__regex_submatch_int
20418     \prg_replicate:nn \l__regex_capturing_group_int
20419     {
20420       \__intarray_gset_fast:Nnn \g__regex_submatch_begin_intarray
20421       { \l__regex_submatch_int } { 0 }
20422       \__intarray_gset_fast:Nnn \g__regex_submatch_end_intarray
20423       { \l__regex_submatch_int } { 0 }
20424       \__intarray_gset_fast:Nnn \g__regex_submatch_prev_intarray
20425       { \l__regex_submatch_int } { 0 }
20426       \int_incr:N \l__regex_submatch_int
20427     }
20428   \prop_map_inline:Nn \l__regex_success_submatches_prop
20429   {
20430     \if_int_compare:w ##1 - 1 \exp_stop_f:
20431       \exp_after:wN \__regex_extract_e:wn \__int_value:w
20432     \else:
20433       \exp_after:wN \__regex_extract_b:wn \__int_value:w
20434     \fi:
20435     \__int_eval:w \l__regex_zeroth_submatch_int + ##1 {##2}
20436   }
20437   \__intarray_gset_fast:Nnn \g__regex_submatch_prev_intarray

```

```

20438         { \l__regex_zeroth_submatch_int } { \l__regex_start_pos_int }
20439     \fi:
20440 }
20441 \cs_new_protected:Npn \__regex_extract_b:wn #1 < #2
20442 { \__intarray_gset_fast:Nnn \g__regex_submatch_begin_intarray {#1} {#2} }
20443 \cs_new_protected:Npn \__regex_extract_e:wn #1 > #2
20444 { \__intarray_gset_fast:Nnn \g__regex_submatch_end_intarray {#1} {#2} }

```

(End definition for `__regex_extract:`, `__regex_extract_b:wn`, and `__regex_extract_e:wn`.)

36.7.4 Replacement

`__regex_replace_once:nnN` Build the NFA and the replacement functions, then find a single match. If the match failed, simply exit the group. Otherwise, we do the replacement. Extract submatches. Compute the brace balance corresponding to replacing this match by the replacement (this depends on submatches). Prepare the replaced token list: the replacement function produces the tokens from the start of the query to the start of the match and the replacement text for this match; we need to add the tokens from the end of the match to the end of the query. Finally, store the result in the user's variable after closing the group: this step involves an additional x-expansion, and checks that braces are balanced in the final result.

```

20445 \cs_new_protected:Npn \__regex_replace_once:nnN #1#2#3
20446 {
20447     \group_begin:
20448     \__regex_single_match:
20449     #1
20450     \__regex_replacement:n {#2}
20451     \exp_args:No \__regex_match:n { #3 }
20452     \if_meaning:w \c_false_bool \g__regex_success_bool
20453     \group_end:
20454     \else:
20455     \__regex_extract:
20456     \int_set:Nn \l__regex_balance_int
20457     {
20458         \__regex_replacement_balance_one_match:n
20459         { \l__regex_zeroth_submatch_int }
20460     }
20461     \tl_set:Nx \l__regex_internal_a_tl
20462     {
20463         \__regex_replacement_do_one_match:n { \l__regex_zeroth_submatch_int }
20464         \__regex_query_range:nn
20465         {
20466             \__intarray_item_fast:Nn \g__regex_submatch_end_intarray
20467             { \l__regex_zeroth_submatch_int }
20468         }
20469         { \l__regex_max_pos_int }
20470     }
20471     \__regex_group_end_replace:N #3
20472     \fi:
20473 }

```

(End definition for `__regex_replace_once:nnN`.)

`__regex_replace_all:nnN` Match multiple times, and for every match, extract submatches and additionally store the position at which the match attempt started. The entries from `\l__regex_min_submatch_int` to `\l__regex_submatch_int` hold information about submatches of every

match in order; each match corresponds to `\l__regex_capturing_group_int` consecutive entries. Compute the brace balance corresponding to doing all the replacements: this is the sum of brace balances for replacing each match. Join together the replacement texts for each match (including the part of the query before the match), and the end of the query.

```

20474 \cs_new_protected:Npn \__regex_replace_all:nnN #1#2#3
20475 {
20476   \group_begin:
20477   \__regex_multi_match:n { \__regex_extract: }
20478   #1
20479   \__regex_replacement:n {#2}
20480   \exp_args:No \__regex_match:n {#3}
20481   \int_set:Nn \l__regex_balance_int
20482   {
20483     0
20484     \int_step_function:nnnN
20485     { \l__regex_min_submatch_int }
20486     \l__regex_capturing_group_int
20487     { \l__regex_submatch_int - 1 }
20488     \__regex_replacement_balance_one_match:n
20489   }
20490   \tl_set:Nx \l__regex_internal_a_tl
20491   {
20492     \int_step_function:nnnN
20493     { \l__regex_min_submatch_int }
20494     \l__regex_capturing_group_int
20495     { \l__regex_submatch_int - 1 }
20496     \__regex_replacement_do_one_match:n
20497     \__regex_query_range:nn
20498     \l__regex_start_pos_int \l__regex_max_pos_int
20499   }
20500   \__regex_group_end_replace:N #3
20501 }

```

(End definition for `__regex_replace_all:nnN`.)

`__regex_group_end_replace:N` If the brace balance is not 0, raise an error. Then set the user's variable #1 to the x-expansion of `\l__regex_internal_a_tl`, adding the appropriate braces to produce a balanced result. And end the group.

```

20502 \cs_new_protected:Npn \__regex_group_end_replace:N #1
20503 {
20504   \if_int_compare:w \l__regex_balance_int = 0 \exp_stop_f:
20505   \else:
20506     \__msg_kernel_error:nnxxx { kernel } { result-unbalanced }
20507     { replacing }
20508     { \int_max:nn { - \l__regex_balance_int } { 0 } }
20509     { \int_max:nn { \l__regex_balance_int } { 0 } }
20510   \fi:
20511   \use:x
20512   {
20513     \group_end:
20514     \tl_set:Nn \exp_not:N #1
20515     {
20516       \if_int_compare:w \l__regex_balance_int < 0 \exp_stop_f:

```

```

20517         \prg_replicate:nn { - \l__regex_balance_int }
20518         { { \if_false: } \fi: }
20519     \fi:
20520     \l__regex_internal_a_tl
20521     \if_int_compare:w \l__regex_balance_int > 0 \exp_stop_f:
20522         \prg_replicate:nn { \l__regex_balance_int }
20523         { \if_false: { \fi: } }
20524     \fi:
20525 }
20526 }
20527 }

```

(End definition for `__regex_group_end_replace:N`.)

36.7.5 Storing and showing compiled patterns

36.8 Messages

Messages for the parsing phase.

```

20528 \__msg_kernel_new:nnnn { kernel } { trailing-backslash }
20529 { Trailing-escape-character~'\iow_char:N\\'. }
20530 {
20531     A-regular-expression-or-its-replacement-text-ends-with~
20532     the-escape-character~'\iow_char:N\\'.~It-will-be-ignored.
20533 }
20534 \__msg_kernel_new:nnnn { kernel } { x-missing-rbrace }
20535 { Missing-closing-brace-in~'\iow_char:N\\x'-hexadecimal-sequence. }
20536 {
20537     You-wrote-something-like~
20538     '\iow_char:N\\x\{...#1'~
20539     The-closing-brace-is-missing.
20540 }
20541 \__msg_kernel_new:nnnn { kernel } { x-overflow }
20542 { Character-code~'#1'~too-large-in~'\iow_char:N\\x'-hexadecimal-sequence. }
20543 {
20544     You-wrote-something-like~
20545     '\iow_char:N\\x\{\int_to_Hex:n{#1}\}'~
20546     The-character-code~#1~is-larger-than~
20547     the-maximum-value~\int_use:N \c_max_char_int.
20548 }

```

Invalid quantifier.

```

20549 \__msg_kernel_new:nnnn { kernel } { invalid-quantifier }
20550 { Braced-quantifier~'#1'~may-not-be-followed-by~'#2'. }
20551 {
20552     The-character~'#2'~is-invalid-in-the-braced-quantifier~'#1'~
20553     The-only-valid-quantifiers-are~'*',~'?',~'+',~'{<int>}',~
20554     '{<min>}'~and~'{<min>,<max>}',~optionally-followed-by~'?'~
20555 }

```

Messages for missing or extra closing brackets and parentheses, with some fancy singular/plural handling for the case of parentheses.

```

20556 \__msg_kernel_new:nnnn { kernel } { missing-rbrack }
20557 { Missing-right-bracket-inserted-in-regular-expression. }
20558 {

```

```

20559 LaTeX~was~given~a~regular~expression~where~a~character~class~
20560 was~started~with~'['~,~but~the~matching~']'~is~missing.
20561 }
20562 \_msg_kernel_new:nnnn { kernel } { missing-rparen }
20563 {
20564 Missing-right~
20565 \int_compare:nTF { #1 = 1 } { parenthesis } { parentheses } ~
20566 inserted-in-regular-expression.
20567 }
20568 {
20569 LaTeX~was~given~a~regular~expression~with~\int_eval:n {#1} ~
20570 more~left~parentheses~than~right~parentheses.
20571 }
20572 \_msg_kernel_new:nnnn { kernel } { extra-rparen }
20573 { Extra~right~parenthesis~ignored~in~regular-expression. }
20574 {
20575 LaTeX~came~across~a~closing~parenthesis~when~no~submatch~group~
20576 was~open.~The~parenthesis~will~be~ignored.
20577 }

```

Some escaped alphanumerics are not allowed everywhere.

```

20578 \_msg_kernel_new:nnnn { kernel } { bad-escape }
20579 {
20580 Invalid-escape~'\iow_char:N\\#1'~
20581 \_regex_if_in_cs:TF { within-a-control-sequence. }
20582 {
20583 \_regex_if_in_class:TF
20584 { in-a-character-class. }
20585 { following-a-category-test. }
20586 }
20587 }
20588 {
20589 The-escape-sequence~'\iow_char:N\\#1'~may~not~appear~
20590 \_regex_if_in_cs:TF
20591 {
20592 within-a-control-sequence-test~introduced-by~
20593 '\iow_char:N\\c\iow_char:N\{'~.
20594 }
20595 {
20596 \_regex_if_in_class:TF
20597 { within-a-character-class~ }
20598 { following-a-category-test~such-as~'\iow_char:N\\cL'~ }
20599 because~it~does~not~match~exactly~one~character.
20600 }
20601 }

```

Range errors.

```

20602 \_msg_kernel_new:nnnn { kernel } { range-missing-end }
20603 { Invalid-end-point-for-range~'#1-#2'~in-character-class. }
20604 {
20605 The~end-point~'#2'~of~the~range~'#1-#2'~may~not~serve~as~an~
20606 end-point~for~a~range:~alphanumeric~characters~should~not~be~
20607 escaped,~and~non-alphanumeric~characters~should~be~escaped.
20608 }
20609 \_msg_kernel_new:nnnn { kernel } { range-backwards }

```

```

20610 { Range~'[#1-#2]''~out~of~order~in~character~class. }
20611 {
20612   In~ranges~of~characters~'[x-y]''~appearing~in~character~classes,~
20613   the~first~character~code~must~not~be~larger~than~the~second.~
20614   Here,~'#1''~has~character~code~\int_eval:n { '#1},~while~
20615   '#2''~has~character~code~\int_eval:n { '#2}.
20616 }

```

Errors related to \c and \u.

```

20617 \_msg_kernel_new:nnnn { kernel } { c-bad-mode }
20618 { Invalid-nested~'\iow_char:N\\c''~escape~in~regular~expression. }
20619 {
20620   The~'\iow_char:N\\c''~escape~cannot~be~used~within~
20621   a~control~sequence~test~'\iow_char:N\\c{...}''.~
20622   To~combine~several~category~tests,~use~'\iow_char:N\\c[...]'.
20623 }
20624 \_msg_kernel_new:nnnn { kernel } { c-C-invalid }
20625 { '\iow_char:N\\cC''~should~be~followed~by~'.'~or~'(',~not~'#1'. }
20626 {
20627   The~'\iow_char:N\\cC''~construction~restricts~the~next~item~to~be~a~
20628   control~sequence~or~the~next~group~to~be~made~of~control~sequences.~
20629   It~only~makes~sense~to~follow~it~by~'.'~or~by~a~group.
20630 }
20631 \_msg_kernel_new:nnnn { kernel } { c-missing-rbrace }
20632 { Missing-right-brace~inserted~for~'\iow_char:N\\c''~escape. }
20633 {
20634   LaTeX~was~given~a~regular~expression~where~a~
20635   '\iow_char:N\\c\iow_char:N{...''~construction~was~not~ended~
20636   with~a~closing~brace~'\iow_char:N\}''.
20637 }
20638 \_msg_kernel_new:nnnn { kernel } { c-missing-rbrack }
20639 { Missing-right-bracket~inserted~for~'\iow_char:N\\c''~escape. }
20640 {
20641   A~construction~'\iow_char:N\\c[...''~appears~in~a~
20642   regular~expression,~but~the~closing~'']'~is~not~present.
20643 }
20644 \_msg_kernel_new:nnnn { kernel } { c-missing-category }
20645 { Invalid-character~'#1''~following~'\iow_char:N\\c''~escape. }
20646 {
20647   In~regular~expressions,~the~'\iow_char:N\\c''~escape~sequence~
20648   may~only~be~followed~by~a~left~brace,~a~left~bracket,~or~a~
20649   capital~letter~representing~a~character~category,~namely~
20650   one~of~'ABCDELMOPTU'.
20651 }
20652 \_msg_kernel_new:nnnn { kernel } { c-trailing }
20653 { Trailing-category~code~escape~'\iow_char:N\\c'... }
20654 {
20655   A~regular~expression~ends~with~'\iow_char:N\\c''~followed~
20656   by~a~letter.~It~will~be~ignored.
20657 }
20658 \_msg_kernel_new:nnnn { kernel } { u-missing-lbrace }
20659 { Missing-left-brace~following~'\iow_char:N\\u''~escape. }
20660 {
20661   The~'\iow_char:N\\u''~escape~sequence~must~be~followed~by~
20662   a~brace~group~with~the~name~of~the~variable~to~use.

```

```

20663 }
20664 \_msg_kernel_new:nnnn { kernel } { u-missing-rbrace }
20665 { Missing~right~brace~inserted~for~'\iow_char:N\\u'~escape. }
20666 {
20667   LaTeX~
20668   \str_if_eq_x:nnTF { } {#2}
20669   { reached~the~end~of~the~string~ }
20670   { encountered~an~escaped~alphanumeric~character '\iow_char:N\\#2'~ }
20671   when~parsing~the~argument~of~an~'\iow_char:N\\u\iow_char:N\\{...}'~escape.
20672 }

```

Errors when encountering the POSIX syntax [:...:].

```

20673 \_msg_kernel_new:nnnn { kernel } { posix-unsupported }
20674 { POSIX~collating~element~'[#1 ~ #1]'~not~supported. }
20675 {
20676   The~'[.foo.]'~and~'[=bar=]'~syntaxes~have~a~special~meaning~
20677   in~POSIX~regular~expressions.~This~is~not~supported~by~LaTeX.~
20678   Maybe~you~forgot~to~escape~a~left~bracket~in~a~character~class?
20679 }
20680 \_msg_kernel_new:nnnn { kernel } { posix-unknown }
20681 { POSIX~class~'[:#1:]'~unknown. }
20682 {
20683   '[:#1:]'~is~not~among~the~known~POSIX~classes~
20684   '[:alnum:]',~'[:alpha:]',~'[:ascii:]',~'[:blank:]',~
20685   '[:cntrl:]',~'[:digit:]',~'[:graph:]',~'[:lower:]',~
20686   '[:print:]',~'[:punct:]',~'[:space:]',~'[:upper:]',~
20687   '[:word:]',~and~'[:xdigit:]'.
20688 }
20689 \_msg_kernel_new:nnnn { kernel } { posix-missing-close }
20690 { Missing~closing~':'~for~POSIX~class. }
20691 { The~POSIX~syntax~'#1'~must~be~followed~by~':'',~not~'#2'. }

```

In various cases, the result of a `l3regex` operation can leave us with an unbalanced token list, which we must re-balance by adding begin-group or end-group character tokens.

```

20692 \_msg_kernel_new:nnnn { kernel } { result-unbalanced }
20693 { Missing~brace~inserted~when~#1. }
20694 {
20695   LaTeX~was~asked~to~do~some~regular~expression~operation,~
20696   and~the~resulting~token~list~would~not~have~the~same~number~
20697   of~begin~group~and~end~group~tokens.~Braces~were~inserted:~
20698   #2~left,~#3~right.
20699 }

```

Error message for unknown options.

```

20700 \_msg_kernel_new:nnnn { kernel } { unknown-option }
20701 { Unknown~option~'#1'~for~regular~expressions. }
20702 {
20703   The~only~available~option~is~'case-insensitive',~toggled~by~
20704   '(?i)'~and~'(?-i)'.
20705 }
20706 \_msg_kernel_new:nnnn { kernel } { special-group-unknown }
20707 { Unknown~special~group~'#1~...'~in~a~regular~expression. }
20708 {
20709   The~only~valid~constructions~starting~with~'(?~are~

```



```

20710      ' (? : ~ . . . ~ ) ' , ~ ' ( ? | ~ . . . ~ ) ' , ~ ' ( ? i ) ' , ~ and ~ ' ( ? - i ) ' .
20711    }

```

Errors in the replacement text.

```

20712 \_msg_kernel_new:nnnn { kernel } { replacement-c }
20713 { Misused~'\iow_char:N\c'~command-in-a-replacement-text. }
20714 {
20715   In-a-replacement-text,~the~'\iow_char:N\c'~escape-sequence~
20716   can-be-followed-by-one-of-the-letters~'ABCDELMOPSTU'~
20717   or-a-brace-group,~not~by~'#1' .
20718 }
20719 \_msg_kernel_new:nnnn { kernel } { replacement-u }
20720 { Misused~'\iow_char:N\u'~command-in-a-replacement-text. }
20721 {
20722   In-a-replacement-text,~the~'\iow_char:N\u'~escape-sequence~
20723   must-be~followed-by-a-brace-group-holding-the-name-of-the~
20724   variable-to-use.
20725 }
20726 \_msg_kernel_new:nnnn { kernel } { replacement-g }
20727 {
20728   Missing-brace-for-the~'\iow_char:N\g'~construction~
20729   in-a-replacement-text.
20730 }
20731 {
20732   In-the-replacement-text-for-a-regular-expression-search,~
20733   submatches-are-represented-either-as~'\iow_char:N \g{dd..d}',~
20734   or~'\d',~where~'d'~are-single-digits.~Here,~a-brace-is-missing.
20735 }
20736 \_msg_kernel_new:nnnn { kernel } { replacement-catcode-end }
20737 {
20738   Missing-character-for-the~'\iow_char:N\c<category><character>'~
20739   construction-in-a-replacement-text.
20740 }
20741 {
20742   In-a-replacement-text,~the~'\iow_char:N\c'~escape-sequence~
20743   can-be-followed-by-one-of-the-letters~'ABCDELMOPSTU'~representing~
20744   the-character-category.~Then,~a-character-must-follow.~LaTeX~
20745   reached-the-end-of-the-replacement-when-looking-for-that.
20746 }
20747 \_msg_kernel_new:nnnn { kernel } { replacement-catcode-escaped }
20748 {
20749   Escaped-letter-or-digit-after-category-code-in-replacement-text.
20750 }
20751 {
20752   In-a-replacement-text,~the~'\iow_char:N\c'~escape-sequence~
20753   can-be-followed-by-one-of-the-letters~'ABCDELMOPSTU'~representing~
20754   the-character-category.~Then,~a-character-must-follow,~not~
20755   '\iow_char:N\#2' .
20756 }
20757 \_msg_kernel_new:nnnn { kernel } { replacement-catcode-in-cs }
20758 {
20759   Category-code~'\iow_char:N\c#1#3'~ignored-inside~
20760   '\iow_char:N\c\{...\}'~in-a-replacement-text.
20761 }
20762 {

```

```

20763 In~a~replacement~text,~the~category~codes~of~the~argument~of~
20764 '\iow_char:N\c\{\...\}'~are~ignored~when~building~the~control~
20765 sequence~name.
20766 }
20767 \__msg_kernel_new:nnnn { kernel } { replacement-null-space }
20768 { TeX~cannot~build~a~space~token~with~character~code~0. }
20769 {
20770   You~asked~for~a~character~token~with~category~space,~
20771   and~character~code~0,~for~instance~through~
20772   '\iow_char:N\cS\iow_char:N\x00'.~
20773   This~specific~case~is~impossible~and~will~be~replaced~
20774   by~a~normal~space.
20775 }
20776 \__msg_kernel_new:nnnn { kernel } { replacement-missing-rbrace }
20777 { Missing~right~brace~inserted~in~replacement~text. }
20778 {
20779   There~ \int_compare:nTF { #1 = 1 } { was } { were } ~ #1~
20780   missing~right~\int_compare:nTF { #1 = 1 } { brace } { braces } .
20781 }
20782 \__msg_kernel_new:nnnn { kernel } { replacement-missing-rparen }
20783 { Missing~right~parenthesis~inserted~in~replacement~text. }
20784 {
20785   There~ \int_compare:nTF { #1 = 1 } { was } { were } ~ #1~
20786   missing~right~\int_compare:nTF { #1 = 1 } { parenthesis } { parentheses } .
20787 }

```

Used when showing a regex.

```

20788 \__msg_kernel_new:nnn { kernel } { show-regex }
20789 {
20790   >~Compiled~regex~
20791   \tl_if_empty:nTF {#1} { variable~ #2 } { {#1} } :
20792   #3
20793 }

```

`__regex_msg_repeated:nnN` This is not technically a message, but seems related enough to go there. The arguments are: #1 is the minimum number of repetitions; #2 is the number of allowed extra repetitions (−1 for infinite number), and #3 tells us about laziness.

```

20794 \cs_new:Npn \__regex_msg_repeated:nnN #1#2#3
20795 {
20796   \str_if_eq_x:nnF { #1 #2 } { 1 0 }
20797   {
20798     , ~ repeated ~
20799     \int_case:nnF {#2}
20800     {
20801       { -1 } { #1~or~more~times,~\bool_if:NTF #3 { lazy } { greedy } }
20802       { 0 } { #1~times }
20803     }
20804     {
20805       between~#1~and~\int_eval:n {#1+#2}~times,~
20806       \bool_if:NTF #3 { lazy } { greedy }
20807     }
20808   }
20809 }

```

(End definition for `__regex_msg_repeated:nnN`.)

36.9 Code for tracing

There is a more extensive implementation of tracing in the l3trial package l3trace. Function names are a bit different but could be merged.

`__debug_trace_push:nnN` Here **#1** is the module name (regex) and **#2** is typically 1. If the module's current tracing level is less than **#2** show nothing, otherwise write **#3** to the terminal.
`__debug_trace_pop:nnN`
`__debug_trace:nnx`

```

20810 \__debug:TF
20811 {
20812   \cs_new_protected:Npn \__debug_trace_push:nnN #1#2#3
20813     { \__debug_trace:nnx {#1} {#2} { entering~ \token_to_str:N #3 } }
20814   \cs_new_protected:Npn \__debug_trace_pop:nnN #1#2#3
20815     { \__debug_trace:nnx {#1} {#2} { leaving~ \token_to_str:N #3 } }
20816   \cs_new_protected:Npn \__debug_trace:nnx #1#2#3
20817     {
20818       \int_compare:nNnF
20819         { \int_use:c { g__debug_trace_#1_int } } < {#2}
20820         { \iow_term:x { Trace:~#3 } }
20821     }
20822 }
20823 { }
```

(End definition for `__debug_trace_push:nnN`, `__debug_trace_pop:nnN`, and `__debug_trace:nnx`.)

`\g__debug_trace_regex_int` No tracing when that is zero.

```

20824 \int_new:N \g__debug_trace_regex_int
```

(End definition for `\g__debug_trace_regex_int`.)

`__regex_trace_states:n` This function lists the contents of all states of the NFA, stored in `\toks` from 0 to `\l__-regex_max_state_int` (excluded).

```

20825 \__debug:TF
20826 {
20827   \cs_new_protected:Npn \__regex_trace_states:n #1
20828     {
20829       \int_step_inline:nnnn
20830         \l__regex_min_state_int
20831         { 1 }
20832         { \l__regex_max_state_int - 1 }
20833         {
20834           \__debug_trace:nnx { regex } {#1}
20835           { \iow_char:N \toks ##1 = { \__regex_toks_use:w ##1 } }
20836         }
20837     }
20838 }
20839 { }
```

(End definition for `__regex_trace_states:n`.)

```

20840 </initex | package>
```

37 l3box implementation

20841 $\langle *initex | package \rangle$

20842 $\langle @@=box \rangle$

The code in this module is very straight forward so I'm not going to comment it very extensively.

37.1 Creating and initialising boxes

The following test files are used for this code: m3box001.lvt.

\box_new:N Defining a new $\langle box \rangle$ register: remember that box 255 is not generally available.

```
\box_new:c
20843 \package
20844 \cs_new_protected:Npn \box_new:N #1
20845 {
20846   \__chk_if_free_cs:N #1
20847   \cs:w newbox \cs_end: #1
20848 }
20849 \package
20850 \cs_generate_variant:Nn \box_new:N { c }
```

Clear a $\langle box \rangle$ register.

```
20851 \cs_new_protected:Npn \box_clear:N #1
\box_clear:N 20852 { \box_set_eq:NN #1 \c_empty_box }
\box_clear:c 20853 \cs_new_protected:Npn \box_gclear:N #1
\box_gclear:N 20854 { \box_gset_eq:NN #1 \c_empty_box }
\box_gclear:c 20855 \cs_generate_variant:Nn \box_clear:N { c }
20856 \cs_generate_variant:Nn \box_gclear:N { c }
```

Clear or new.

```
20857 \cs_new_protected:Npn \box_clear_new:N #1
\box_clear_new:N 20858 { \box_if_exist:NTF #1 { \box_clear:N #1 } { \box_new:N #1 } }
\box_clear_new:c 20859 \cs_new_protected:Npn \box_gclear_new:N #1
\box_gclear_new:N 20860 { \box_if_exist:NTF #1 { \box_gclear:N #1 } { \box_new:N #1 } }
\box_gclear_new:c 20861 \cs_generate_variant:Nn \box_clear_new:N { c }
20862 \cs_generate_variant:Nn \box_gclear_new:N { c }
```

Assigning the contents of a box to be another box.

```
20863 \__debug_patch:nnNNpn { \__debug_chk_var_local:N #1 } { }
\box_set_eq:NN 20864 \cs_new_protected:Npn \box_set_eq:NN #1#2
\box_set_eq:cN 20865 { \tex_setbox:D #1 \tex_copy:D #2 }
\box_set_eq:Nc 20866 \__debug_patch:nnNNpn { \__debug_chk_var_global:N #1 } { }
\box_set_eq:cc 20867 \cs_new_protected:Npn \box_gset_eq:NN #1#2
\box_gset_eq:NN 20868 { \tex_global:D \tex_setbox:D #1 \tex_copy:D #2 }
\box_gset_eq:cN 20869 \cs_generate_variant:Nn \box_set_eq:NN { c , Nc , cc }
\box_gset_eq:Nc 20870 \cs_generate_variant:Nn \box_gset_eq:NN { c , Nc , cc }
\box_gset_eq:cc
```

Assigning the contents of a box to be another box. This clears the second box globally (that's how \TeX does it).

```
20871 \__debug_patch:nnNNpn { \__debug_chk_var_local:N #1 } { }
\box_set_eq_clear:NN 20872 \cs_new_protected:Npn \box_set_eq_clear:NN #1#2
\box_set_eq_clear:cN 20873 { \tex_setbox:D #1 \tex_box:D #2 }
\box_set_eq_clear:Nc 20874 \__debug_patch:nnNNpn { \__debug_chk_var_global:N #1 } { }
\box_set_eq_clear:cc
\box_gset_eq_clear:NN
\box_gset_eq_clear:cN
\box_gset_eq_clear:Nc
\box_gset_eq_clear:cc
```

```

20875 \cs_new_protected:Npn \box_gset_eq_clear:NN #1#2
20876 { \tex_global:D \tex_setbox:D #1 \tex_box:D #2 }
20877 \cs_generate_variant:Nn \box_set_eq_clear:NN { c , Nc , cc }
20878 \cs_generate_variant:Nn \box_gset_eq_clear:NN { c , Nc , cc }

```

Copies of the cs functions defined in l3basics.

```

\box_if_exist_p:N
\box_if_exist_p:c
\box_if_exist:N $\underline{TF}$ 
\box_if_exist:c $\underline{TF}$ 
20879 \prg_new_eq_conditional:NNn \box_if_exist:N \cs_if_exist:N
20880 { TF , T , F , p }
20881 \prg_new_eq_conditional:NNn \box_if_exist:c \cs_if_exist:c
20882 { TF , T , F , p }

```

37.2 Measuring and setting box dimensions

Accessing the height, depth, and width of a $\langle box \rangle$ register.

```

\box_ht:N
\box_ht:c
\box_dp:N
\box_dp:c
\box_wd:N
\box_wd:c
20883 \cs_new_eq:NN \box_ht:N \tex_ht:D
20884 \cs_new_eq:NN \box_dp:N \tex_dp:D
20885 \cs_new_eq:NN \box_wd:N \tex_wd:D
20886 \cs_generate_variant:Nn \box_ht:N { c }
20887 \cs_generate_variant:Nn \box_dp:N { c }
20888 \cs_generate_variant:Nn \box_wd:N { c }

```

Setting the size is easy: all primitive work. These primitives are not expandable, so the derived functions are not either. When debugging, the dimension expression #2 is surrounded by parentheses to catch early termination.

```

\box_set_ht:Nn
\box_set_ht:cn
\box_set_dp:Nn
\box_set_dp:cn
\box_set_wd:Nn
\box_set_wd:cn
20889 \cs_new_protected:Npn \box_set_dp:Nn #1#2
20890 { \box_dp:N #1 \__dim_eval:n {#2} }
20891 \cs_new_protected:Npn \box_set_ht:Nn #1#2
20892 { \box_ht:N #1 \__dim_eval:n {#2} }
20893 \cs_new_protected:Npn \box_set_wd:Nn #1#2
20894 { \box_wd:N #1 \__dim_eval:n {#2} }
20895 \cs_generate_variant:Nn \box_set_ht:Nn { c }
20896 \cs_generate_variant:Nn \box_set_dp:Nn { c }
20897 \cs_generate_variant:Nn \box_set_wd:Nn { c }

```

37.3 Using boxes

Using a $\langle box \rangle$. These are just TeX primitives with meaningful names.

```

\box_use_drop:N
\box_use_drop:c
\box_use:N
\box_use:c
20898 \cs_new_eq:NN \box_use_drop:N \tex_box:D
20899 \cs_new_eq:NN \box_use:N \tex_copy:D
20900 \cs_generate_variant:Nn \box_use_drop:N { c }
20901 \cs_generate_variant:Nn \box_use:N { c }

```

Move box material in different directions. When debugging, the dimension expression #1 is surrounded by parentheses to catch early termination.

```

\box_move_left:nn
\box_move_right:nn
\box_move_up:nn
\box_move_down:nn
20902 \cs_new_protected:Npn \box_move_left:nn #1#2
20903 { \tex_moveleft:D \__dim_eval:n {#1} #2 }
20904 \cs_new_protected:Npn \box_move_right:nn #1#2
20905 { \tex_moveright:D \__dim_eval:n {#1} #2 }
20906 \cs_new_protected:Npn \box_move_up:nn #1#2
20907 { \tex_raise:D \__dim_eval:n {#1} #2 }
20908 \cs_new_protected:Npn \box_move_down:nn #1#2
20909 { \tex_lower:D \__dim_eval:n {#1} #2 }

```

37.4 Box conditionals

The primitives for testing if a $\langle box \rangle$ is empty/void or which type of box it is.

```

20910 \cs_new_eq:NN \if_hbox:N \tex_ifhbox:D
\if_hbox:N
20911 \cs_new_eq:NN \if_vbox:N \tex_ifvbox:D
\if_vbox:N
20912 \cs_new_eq:NN \if_box_empty:N \tex_ifvoid:D
\if_box_empty:N

20913 \prg_new_conditional:Npnn \box_if_horizontal:N #1 { p , T , F , TF }
\box_if_horizontal_p:N { \if_hbox:N #1 \prg_return_true: \else: \prg_return_false: \fi: }
\box_if_horizontal_p:c
20915 \prg_new_conditional:Npnn \box_if_vertical:N #1 { p , T , F , TF }
\box_if_vertical_p:N { \if_vbox:N #1 \prg_return_true: \else: \prg_return_false: \fi: }
\box_if_vertical_p:c
20917 \cs_generate_variant:Nn \box_if_horizontal_p:N { c }
\box_if_horizontal_p:c
20918 \cs_generate_variant:Nn \box_if_horizontal:N { NT }
\box_if_horizontal_NT:c
20919 \cs_generate_variant:Nn \box_if_horizontal:N { NF }
\box_if_horizontal_NF:c
20920 \cs_generate_variant:Nn \box_if_horizontal:N { NTF }
\box_if_horizontal_NTF:c
20921 \cs_generate_variant:Nn \box_if_vertical_p:N { c }
\box_if_vertical_p:c
20922 \cs_generate_variant:Nn \box_if_vertical:N { NT }
\box_if_vertical_NT:c
20923 \cs_generate_variant:Nn \box_if_vertical:N { NF }
\box_if_vertical_NF:c
20924 \cs_generate_variant:Nn \box_if_vertical:N { NTF }
\box_if_vertical_NTF:c

```

Testing if a $\langle box \rangle$ is empty/void.

```

20925 \prg_new_conditional:Npnn \box_if_empty:N #1 { p , T , F , TF }
\box_if_empty_p:N { \if_box_empty:N #1 \prg_return_true: \else: \prg_return_false: \fi: }
\box_if_empty_p:c
20927 \cs_generate_variant:Nn \box_if_empty_p:N { c }
\box_if_empty_p:c
20928 \cs_generate_variant:Nn \box_if_empty:N { NT }
\box_if_empty_NT:c
20929 \cs_generate_variant:Nn \box_if_empty:N { NF }
\box_if_empty_NF:c
20930 \cs_generate_variant:Nn \box_if_empty:N { NTF }
\box_if_empty_NTF:c

```

(End definition for $\backslash box_new:N$ and others. These functions are documented on page 218.)

37.5 The last box inserted

```

\box_set_to_last:N Set a box to the previous box.
\box_set_to_last:c
20931 \__debug_patch:nnNpn { \__debug_chk_var_local:N #1 } { }
\box_gset_to_last:N
20932 \cs_new_protected:Npn \box_set_to_last:N #1
\box_gset_to_last:c { \tex_setbox:D #1 \tex_lastbox:D }
20934 \__debug_patch:nnNpn { \__debug_chk_var_global:N #1 } { }
\box_gset_to_last:N
20935 \cs_new_protected:Npn \box_gset_to_last:N #1
\box_gset_to_last:c { \tex_global:D \tex_setbox:D #1 \tex_lastbox:D }
20936 \cs_generate_variant:Nn \box_set_to_last:N { c }
20937 \cs_generate_variant:Nn \box_gset_to_last:N { c }
20938 \cs_generate_variant:Nn \box_gset_to_last:N { c }

```

(End definition for $\backslash box_set_to_last:N$ and $\backslash box_gset_to_last:N$. These functions are documented on page 221.)

37.6 Constant boxes

$\backslash c_empty_box$ A box we never use.

```

20939 \box_new:N \c_empty_box

```

(End definition for $\backslash c_empty_box$. This variable is documented on page 221.)

37.7 Scratch boxes

```

\l_tmpa_box Scratch boxes.
\l_tmpb_box
\g_tmpa_box
\g_tmpb_box
20940 \box_new:N \l_tmpa_box
20941 \box_new:N \l_tmpb_box
20942 \box_new:N \g_tmpa_box
20943 \box_new:N \g_tmpb_box

```

(End definition for `\l_tmpa_box` and others. These variables are documented on page 221.)

37.8 Viewing box contents

TeX's `\showbox` is not really that helpful in many cases, and it is also inconsistent with other L^AT_EX3 show functions as it does not actually shows material in the terminal. So we provide a richer set of functionality.

```

\box_show:N Essentially a wrapper around the internal function, but evaluating the breadth and depth
\box_show:c arguments now outside the group.
\box_show:Nnn
\box_show:cnn
20944 \cs_new_protected:Npn \box_show:N #1
20945 { \box_show:Nnn #1 \c_max_int \c_max_int }
20946 \cs_generate_variant:Nn \box_show:N { c }
20947 \cs_new_protected:Npn \box_show:Nnn #1#2#3
20948 { \__box_show:NNff 1 #1 { \int_eval:n {#2} } { \int_eval:n {#3} } }
20949 \cs_generate_variant:Nn \box_show:Nnn { c }

```

(End definition for `\box_show:N` and `\box_show:Nnn`. These functions are documented on page 221.)

```

\box_log:N Getting TeX to write to the log without interruption the run is done by altering the
\box_log:c interaction mode. For that, the  $\varepsilon$ -TeX extensions are needed.
\box_log:Nnn
\box_log:cnn
\__box_log:nNnn
20950 \cs_new_protected:Npn \box_log:N #1
20951 { \box_log:Nnn #1 \c_max_int \c_max_int }
20952 \cs_generate_variant:Nn \box_log:N { c }
20953 \cs_new_protected:Npn \box_log:Nnn
20954 { \exp_args:No \__box_log:nNnn { \tex_the:D \etex_interactionmode:D } }
20955 \cs_new_protected:Npn \__box_log:nNnn #1#2#3#4
20956 {
20957   \int_set:Nn \etex_interactionmode:D { 0 }
20958   \__box_show:NNff 0 #2 { \int_eval:n {#3} } { \int_eval:n {#4} }
20959   \int_set:Nn \etex_interactionmode:D {#1}
20960 }
20961 \cs_generate_variant:Nn \box_log:Nnn { c }

```

(End definition for `\box_log:N`, `\box_log:Nnn`, and `__box_log:nNnn`. These functions are documented on page 222.)

```

\__box_show:NNnn The internal auxiliary to actually do the output uses a group to deal with breadth and
\__box_show:NNff depth values. The \use:n here gives better output appearance. Setting \tracingonline
and \errorcontextlines is used to control what appears in the terminal.
20962 \cs_new_protected:Npn \__box_show:NNnn #1#2#3#4
20963 {
20964   \box_if_exist:NTF #2
20965   {
20966     \group_begin:
20967     \int_set:Nn \tex_showboxbreadth:D {#3}

```

```

20968         \int_set:Nn \tex_showboxdepth:D    {#4}
20969         \int_set:Nn \tex_tracingonline:D    {#1}
20970         \int_set:Nn \tex_errorcontextlines:D { -1 }
20971         \tex_showbox:D \use:n {#2}
20972     \group_end:
20973 }
20974 {
20975     \__msg_kernel_error:nxx { kernel } { variable-not-defined }
20976     { \token_to_str:N #2 }
20977 }
20978 }
20979 \cs_generate_variant:Nn \__box_show:NNnn { NNff }

```

(End definition for `__box_show:NNnn`.)

37.9 Horizontal mode boxes

`\hbox:n` (The test suite for this command, and others in this file, is `m3box002.lvt`.)
Put a horizontal box directly into the input stream.

```

20980 \cs_new_protected:Npn \hbox:n #1
20981 { \tex_hbox:D \scan_stop: { \group_begin: #1 \group_end: } }

```

(End definition for `\hbox:n`. This function is documented on page 222.)

```

\hbox_set:Nn
\hbox_set:cn
\hbox_gset:Nn
\hbox_gset:cn
20982 \__debug_patch:nnNNpn { \__debug_chk_var_local:N #1 } { }
20983 \cs_new_protected:Npn \hbox_set:Nn #1#2
20984 { \tex_setbox:D #1 \tex_hbox:D { \group_begin: #2 \group_end: } }
20985 \__debug_patch:nnNNpn { \__debug_chk_var_global:N #1 } { }
20986 \cs_new_protected:Npn \hbox_gset:Nn #1#2
20987 { \tex_global:D \tex_setbox:D #1 \tex_hbox:D { \group_begin: #2 \group_end: } }
20988 \cs_generate_variant:Nn \hbox_set:Nn { c }
20989 \cs_generate_variant:Nn \hbox_gset:Nn { c }

```

(End definition for `\hbox_set:Nn` and `\hbox_gset:Nn`. These functions are documented on page 222.)

`\hbox_set_to_wd:Nnn` Storing material in a horizontal box with a specified width. Again, put the dimension expression in parentheses when debugging.

```

\hbox_set_to_wd:cnn
\hbox_gset_to_wd:Nnn
\hbox_gset_to_wd:cnn
20990 \__debug_patch:nnNNpn { \__debug_chk_var_local:N #1 } { }
20991 \cs_new_protected:Npn \hbox_set_to_wd:Nnn #1#2#3
20992 {
20993     \tex_setbox:D #1 \tex_hbox:D to \__dim_eval:n {#2}
20994     { \group_begin: #3 \group_end: }
20995 }
20996 \__debug_patch:nnNNpn { \__debug_chk_var_global:N #1 } { }
20997 \cs_new_protected:Npn \hbox_gset_to_wd:Nnn #1#2#3
20998 {
20999     \tex_global:D \tex_setbox:D #1 \tex_hbox:D to \__dim_eval:n {#2}
21000     { \group_begin: #3 \group_end: }
21001 }
21002 \cs_generate_variant:Nn \hbox_set_to_wd:Nnn { c }
21003 \cs_generate_variant:Nn \hbox_gset_to_wd:Nnn { c }

```

(End definition for `\hbox_set_to_wd:Nnn` and `\hbox_gset_to_wd:Nnn`. These functions are documented on page 222.)

\hbox_set:Nw Storing material in a horizontal box. This type is useful in environment definitions.

```

\hbox_set:cnw 21004 \__debug_patch:nnNNpn { \__debug_chk_var_local:N #1 } { }
\hbox_gset:Nw 21005 \cs_new_protected:Npn \hbox_set:Nw #1
\hbox_gset:cnw 21006 {
\hbox_set_end: 21007 \tex_setbox:D #1 \tex_hbox:D
\hbox_gset_end: 21008 \c_group_begin_token
21009 \group_begin:
21010 }
21011 \__debug_patch:nnNNpn { \__debug_chk_var_global:N #1 } { }
21012 \cs_new_protected:Npn \hbox_gset:Nw #1
21013 {
21014 \tex_global:D \tex_setbox:D #1 \tex_hbox:D
21015 \c_group_begin_token
21016 \group_begin:
21017 }
21018 \cs_generate_variant:Nn \hbox_set:Nw { c }
21019 \cs_generate_variant:Nn \hbox_gset:Nw { c }
21020 \cs_new_protected:Npn \hbox_set_end:
21021 {
21022 \group_end:
21023 \c_group_end_token
21024 }
21025 \cs_new_eq:NN \hbox_gset_end: \hbox_set_end:

```

(End definition for `\hbox_set:Nw` and others. These functions are documented on page 223.)

\hbox_set_to_wd:Nnw Combining the above ideas.

```

\hbox_set_to_wd:cnw 21026 \__debug_patch:nnNNpn { \__debug_chk_var_local:N #1 } { }
\hbox_gset_to_wd:Nnw 21027 \cs_new_protected:Npn \hbox_set_to_wd:Nnw #1#2
\hbox_gset_to_wd:cnw 21028 {
21029 \tex_setbox:D #1 \tex_hbox:D to \__dim_eval:n {#2}
21030 \c_group_begin_token
21031 \group_begin:
21032 }
21033 \__debug_patch:nnNNpn { \__debug_chk_var_global:N #1 } { }
21034 \cs_new_protected:Npn \hbox_gset_to_wd:Nnw #1#2
21035 {
21036 \tex_global:D \tex_setbox:D #1 \tex_hbox:D to \__dim_eval:n {#2}
21037 \c_group_begin_token
21038 \group_begin:
21039 }
21040 \cs_generate_variant:Nn \hbox_set_to_wd:Nnw { c }
21041 \cs_generate_variant:Nn \hbox_gset_to_wd:Nnw { c }

```

(End definition for `\hbox_set_to_wd:Nnw` and `\hbox_gset_to_wd:Nnw`. These functions are documented on page 223.)

\hbox_to_wd:nn Put a horizontal box directly into the input stream.

```

\hbox_to_zero:nn 21042 \cs_new_protected:Npn \hbox_to_wd:nn #1#2
21043 {
21044 \tex_hbox:D to \__dim_eval:n {#1}
21045 { \group_begin: #2 \group_end: }
21046 }
21047 \cs_new_protected:Npn \hbox_to_zero:n #1
21048 { \tex_hbox:D to \c_zero_dim { \group_begin: #1 \group_end: } }

```

(End definition for `\hbox_to_wd:n` and `\hbox_to_zero:n`. These functions are documented on page 222.)

`\hbox_overlap_left:n` Put a zero-sized box with the contents pushed against one side (which makes it stick out on the other) directly into the input stream.

```

21049 \cs_new_protected:Npn \hbox_overlap_left:n #1
21050 { \hbox_to_zero:n { \tex_hss:D #1 } }
21051 \cs_new_protected:Npn \hbox_overlap_right:n #1
21052 { \hbox_to_zero:n { #1 \tex_hss:D } }

```

(End definition for `\hbox_overlap_left:n` and `\hbox_overlap_right:n`. These functions are documented on page 223.)

`\hbox_unpack:N` Unpacking a box and if requested also clear it.

`\hbox_unpack:c`

`\hbox_unpack_clear:N`

`\hbox_unpack_clear:c`

```

21053 \cs_new_eq:NN \hbox_unpack:N \tex_unhcopy:D
21054 \cs_new_eq:NN \hbox_unpack_clear:N \tex_unhbox:D
21055 \cs_generate_variant:Nn \hbox_unpack:N { c }
21056 \cs_generate_variant:Nn \hbox_unpack_clear:N { c }

```

(End definition for `\hbox_unpack:N` and `\hbox_unpack_clear:N`. These functions are documented on page 223.)

37.10 Vertical mode boxes

TeX ends these boxes directly with the internal `end_graf` routine. This means that there is no `\par` at the end of vertical boxes unless we insert one.

`\vbox:n` The following test files are used for this code: `m3box003.lvt`.

The following test files are used for this code: `m3box003.lvt`.

`\vbox_top:n` Put a vertical box directly into the input stream.

```

21057 \cs_new_protected:Npn \vbox:n #1
21058 { \tex_vbox:D { \group_begin: #1 \par \group_end: } }
21059 \cs_new_protected:Npn \vbox_top:n #1
21060 { \tex_vtop:D { \group_begin: #1 \par \group_end: } }

```

(End definition for `\vbox:n` and `\vbox_top:n`. These functions are documented on page 223.)

`\vbox_to_ht:nn` Put a vertical box directly into the input stream.

```

21061 \cs_new_protected:Npn \vbox_to_ht:nn #1#2
21062 {
21063   \tex_vbox:D to \__dim_eval:n {#1}
21064   { \group_begin: #2 \par \group_end: }
21065 }
21066 \cs_new_protected:Npn \vbox_to_zero:n #1
21067 {
21068   \tex_vbox:D to \c_zero_dim
21069   { \group_begin: #1 \par \group_end: }
21070 }

```

(End definition for `\vbox_to_ht:nn` and others. These functions are documented on page 224.)

\vbox_set:Nn Storing material in a vertical box with a natural height.

\vbox_set:cn 21071 `__debug_patch:nnNNpn { __debug_chk_var_local:N #1 } { }`

\vbox_gset:Nn 21072 `\cs_new_protected:Npn \vbox_set:Nn #1#2`

\vbox_gset:cn 21073 `{`

21074 `\tex_setbox:D #1 \tex_vbox:D`

21075 `{ \group_begin: #2 \par \group_end: }`

21076 `}`

21077 `__debug_patch:nnNNpn { __debug_chk_var_global:N #1 } { }`

21078 `\cs_new_protected:Npn \vbox_gset:Nn #1#2`

21079 `{`

21080 `\tex_global:D \tex_setbox:D #1 \tex_vbox:D`

21081 `{ \group_begin: #2 \par \group_end: }`

21082 `}`

21083 `\cs_generate_variant:Nn \vbox_set:Nn { c }`

21084 `\cs_generate_variant:Nn \vbox_gset:Nn { c }`

(End definition for `\vbox_set:Nn` and `\vbox_gset:Nn`. These functions are documented on page 224.)

\vbox_set_top:Nn Storing material in a vertical box with a natural height and reference point at the baseline

\vbox_set_top:cn of the first object in the box.

\vbox_gset_top:Nn 21085 `__debug_patch:nnNNpn { __debug_chk_var_local:N #1 } { }`

\vbox_gset_top:cn 21086 `\cs_new_protected:Npn \vbox_set_top:Nn #1#2`

21087 `{`

21088 `\tex_setbox:D #1 \tex_vtop:D`

21089 `{ \group_begin: #2 \par \group_end: }`

21090 `}`

21091 `__debug_patch:nnNNpn { __debug_chk_var_global:N #1 } { }`

21092 `\cs_new_protected:Npn \vbox_gset_top:Nn #1#2`

21093 `{`

21094 `\tex_global:D \tex_setbox:D #1 \tex_vtop:D`

21095 `{ \group_begin: #2 \par \group_end: }`

21096 `}`

21097 `\cs_generate_variant:Nn \vbox_set_top:Nn { c }`

21098 `\cs_generate_variant:Nn \vbox_gset_top:Nn { c }`

(End definition for `\vbox_set_top:Nn` and `\vbox_gset_top:Nn`. These functions are documented on page 224.)

\vbox_set_to_ht:Nnn Storing material in a vertical box with a specified height.

\vbox_set_to_ht:cnn 21099 `__debug_patch:nnNNpn { __debug_chk_var_local:N #1 } { }`

\vbox_gset_to_ht:Nnn 21100 `\cs_new_protected:Npn \vbox_set_to_ht:Nnn #1#2#3`

\vbox_gset_to_ht:cnn 21101 `{`

21102 `\tex_setbox:D #1 \tex_vbox:D to __dim_eval:n {#2}`

21103 `{ \group_begin: #3 \par \group_end: }`

21104 `}`

21105 `__debug_patch:nnNNpn { __debug_chk_var_global:N #1 } { }`

21106 `\cs_new_protected:Npn \vbox_gset_to_ht:Nnn #1#2#3`

21107 `{`

21108 `\tex_global:D \tex_setbox:D #1 \tex_vbox:D to __dim_eval:n {#2}`

21109 `{ \group_begin: #3 \par \group_end: }`

21110 `}`

21111 `\cs_generate_variant:Nn \vbox_set_to_ht:Nnn { c }`

21112 `\cs_generate_variant:Nn \vbox_gset_to_ht:Nnn { c }`

(End definition for `\vbox_set_to_ht:Nnn` and `\vbox_gset_to_ht:Nnn`. These functions are documented on page 224.)

`\vbox_set:Nw` Storing material in a vertical box. This type is useful in environment definitions.

`\vbox_set:cw` 21113 `__debug_patch:nnNNpn { __debug_chk_var_local:N #1 } { }`

`\vbox_gset:Nw` 21114 `\cs_new_protected:Npn \vbox_set:Nw #1`

`\vbox_gset:cw` 21115 `{`

`\vbox_set_end:` 21116 `\tex_setbox:D #1 \tex_vbox:D`

`\vbox_gset_end:` 21117 `\c_group_begin_token`

21118 `\group_begin:`

21119 `}`

21120 `__debug_patch:nnNNpn { __debug_chk_var_global:N #1 } { }`

21121 `\cs_new_protected:Npn \vbox_gset:Nw #1`

21122 `{`

21123 `\tex_global:D \tex_setbox:D #1 \tex_vbox:D`

21124 `\c_group_begin_token`

21125 `\group_begin:`

21126 `}`

21127 `\cs_generate_variant:Nn \vbox_set:Nw { c }`

21128 `\cs_generate_variant:Nn \vbox_gset:Nw { c }`

21129 `\cs_new_protected:Npn \vbox_set_end:`

21130 `{`

21131 `\par`

21132 `\group_end:`

21133 `\c_group_end_token`

21134 `}`

21135 `\cs_new_eq:NN \vbox_gset_end: \vbox_set_end:`

(End definition for `\vbox_set:Nw` and others. These functions are documented on page 224.)

`\vbox_set_to_ht:Nnw` A combination of the above ideas.

`\vbox_set_to_ht:cnw` 21136 `__debug_patch:nnNNpn { __debug_chk_var_local:N #1 } { }`

`\vbox_gset_to_ht:Nnw` 21137 `\cs_new_protected:Npn \vbox_set_to_ht:Nnw #1#2`

`\vbox_gset_to_ht:cnw` 21138 `{`

21139 `\tex_setbox:D #1 \tex_vbox:D to __dim_eval:n {#2}`

21140 `\c_group_begin_token`

21141 `\group_begin:`

21142 `}`

21143 `__debug_patch:nnNNpn { __debug_chk_var_global:N #1 } { }`

21144 `\cs_new_protected:Npn \vbox_gset_to_ht:Nnw #1#2`

21145 `{`

21146 `\tex_global:D \tex_setbox:D #1 \tex_vbox:D to __dim_eval:n {#2}`

21147 `\c_group_begin_token`

21148 `\group_begin:`

21149 `}`

21150 `\cs_generate_variant:Nn \vbox_set_to_ht:Nnw { c }`

21151 `\cs_generate_variant:Nn \vbox_gset_to_ht:Nnw { c }`

(End definition for `\vbox_set_to_ht:Nnw` and `\vbox_gset_to_ht:Nnw`. These functions are documented on page 224.)

`\vbox_unpack:N` Unpacking a box and if requested also clear it.

`\vbox_unpack:c` 21152 `\cs_new_eq:NN \vbox_unpack:N \tex_unvcopy:D`

`\vbox_unpack_clear:N` 21153 `\cs_new_eq:NN \vbox_unpack_clear:N \tex_unvbox:D`

`\vbox_unpack_clear:c` 21154 `\cs_generate_variant:Nn \vbox_unpack:N { c }`

21155 `\cs_generate_variant:Nn \vbox_unpack_clear:N { c }`

(End definition for `\vbox_unpack:N` and `\vbox_unpack_clear:N`. These functions are documented on page 225.)

`\vbox_set_split_to_ht:NNn` Splitting a vertical box in two.

```
21156 \__debug_patch:nnNNpn { \__debug_chk_var_local:N #1 } { }
21157 \cs_new_protected:Npn \vbox_set_split_to_ht:NNn #1#2#3
21158 { \tex_setbox:D #1 \tex_vsplit:D #2 to \__dim_eval:n {#3} }
```

(End definition for `\vbox_set_split_to_ht:NNn`. This function is documented on page 224.)

37.11 Affine transformations

`\l__box_angle_fp` When rotating boxes, the angle itself may be needed by the engine-dependent code. This is done using the `fp` module so that the value is tidied up properly.

```
21159 \fp_new:N \l__box_angle_fp
```

(End definition for `\l__box_angle_fp`.)

`\l__box_cos_fp` `\l__box_sin_fp` These are used to hold the calculated sine and cosine values while carrying out a rotation.

```
21160 \fp_new:N \l__box_cos_fp
21161 \fp_new:N \l__box_sin_fp
```

(End definition for `\l__box_cos_fp` and `\l__box_sin_fp`.)

`\l__box_top_dim` `\l__box_bottom_dim` `\l__box_left_dim` `\l__box_right_dim` These are the positions of the four edges of a box before manipulation.

```
21162 \dim_new:N \l__box_top_dim
21163 \dim_new:N \l__box_bottom_dim
21164 \dim_new:N \l__box_left_dim
21165 \dim_new:N \l__box_right_dim
```

(End definition for `\l__box_top_dim` and others.)

`\l__box_top_new_dim` `\l__box_bottom_new_dim` `\l__box_left_new_dim` `\l__box_right_new_dim` These are the positions of the four edges of a box after manipulation.

```
21166 \dim_new:N \l__box_top_new_dim
21167 \dim_new:N \l__box_bottom_new_dim
21168 \dim_new:N \l__box_left_new_dim
21169 \dim_new:N \l__box_right_new_dim
```

(End definition for `\l__box_top_new_dim` and others.)

`\l__box_internal_box` Scratch space, but also needed by some parts of the driver.

```
21170 \box_new:N \l__box_internal_box
```

(End definition for `\l__box_internal_box`.)

`\box_rotate:Nn` Rotation of a box starts with working out the relevant sine and cosine. The actual rotation is in an auxiliary to keep the flow slightly clearer

`__box_rotate:N`

`__box_rotate_x:nnN`

`__box_rotate_y:nnN`

`__box_rotate_quadrant_one:`

`__box_rotate_quadrant_two:`

`__box_rotate_quadrant_three:`

`__box_rotate_quadrant_four:`

```
21171 \cs_new_protected:Npn \box_rotate:Nn #1#2
21172 {
21173   \hbox_set:Nn #1
21174   {
21175     \fp_set:Nn \l__box_angle_fp {#2}
21176     \fp_set:Nn \l__box_sin_fp { sind ( \l__box_angle_fp ) }
21177     \fp_set:Nn \l__box_cos_fp { cosd ( \l__box_angle_fp ) }
21178     \__box_rotate:N #1
21179   }
21180 }
```




Figure 1: Co-ordinates of a box prior to rotation.

The edges of the box are then recorded: the left edge is always at zero. Rotation of the four edges then takes place: this is most efficiently done on a quadrant by quadrant basis.

```

21181 \cs_new_protected:Npn \_box_rotate:N #1
21182 {
21183   \dim_set:Nn \l__box_top_dim { \box_ht:N #1 }
21184   \dim_set:Nn \l__box_bottom_dim { -\box_dp:N #1 }
21185   \dim_set:Nn \l__box_right_dim { \box_wd:N #1 }
21186   \dim_zero:N \l__box_left_dim

```

The next step is to work out the x and y coordinates of vertices of the rotated box in relation to its original coordinates. The box can be visualized with vertices B , C , D and E is illustrated (Figure 1). The vertex O is the reference point on the baseline, and in this implementation is also the centre of rotation. The formulae are, for a point P and angle α :

$$\begin{aligned}
 P'_x &= P_x - O_x \\
 P'_y &= P_y - O_y \\
 P''_x &= (P'_x \cos(\alpha)) - (P'_y \sin(\alpha)) \\
 P''_y &= (P'_x \sin(\alpha)) + (P'_y \cos(\alpha)) \\
 P'''_x &= P''_x + O_x + L_x \\
 P'''_y &= P''_y + O_y
 \end{aligned}$$

The “extra” horizontal translation L_x at the end is calculated so that the leftmost point of the resulting box has x -coordinate 0. This is desirable as T_EX boxes must have the reference point at the left edge of the box. (As O is always $(0,0)$, this part of the calculation is omitted here.)

```

21187   \fp_compare:nNnTF \l__box_sin_fp > \c_zero_fp
21188   {
21189     \fp_compare:nNnTF \l__box_cos_fp > \c_zero_fp
21190     { \_box_rotate_quadrant_one: }
21191     { \_box_rotate_quadrant_two: }
21192   }
21193   {
21194     \fp_compare:nNnTF \l__box_cos_fp < \c_zero_fp
21195     { \_box_rotate_quadrant_three: }
21196     { \_box_rotate_quadrant_four: }
21197   }

```

The position of the box edges are now known, but the box at this stage be misplaced relative to the current T_EX reference point. So the content of the box is moved such that the reference point of the rotated box is in the same place as the original.

```

21198 \hbox_set:Nn \l__box_internal_box { \box_use:N #1 }
21199 \hbox_set:Nn \l__box_internal_box
21200 {
21201   \tex_kern:D -\l__box_left_new_dim
21202   \hbox:n
21203   {
21204     \__driver_box_use_rotate:Nn
21205     \l__box_internal_box
21206     \l__box_angle_fp
21207   }
21208 }

```

Tidy up the size of the box so that the material is actually inside the bounding box. The result can then be used to reset the original box.

```

21209 \box_set_ht:Nn \l__box_internal_box { \l__box_top_new_dim }
21210 \box_set_dp:Nn \l__box_internal_box { -\l__box_bottom_new_dim }
21211 \box_set_wd:Nn \l__box_internal_box
21212 { \l__box_right_new_dim - \l__box_left_new_dim }
21213 \box_use_drop:N \l__box_internal_box
21214 }

```

These functions take a general point (#1,#2) and rotate its location about the origin, using the previously-set sine and cosine values. Each function gives only one component of the location of the updated point. This is because for rotation of a box each step needs only one value, and so performance is gained by avoiding working out both x' and y' at the same time. Contrast this with the equivalent function in the `l3coffins` module, where both parts are needed.

```

21215 \cs_new_protected:Npn \__box_rotate_x:nnN #1#2#3
21216 {
21217   \dim_set:Nn #3
21218   {
21219     \fp_to_dim:n
21220     {
21221       \l__box_cos_fp * \dim_to_fp:n {#1}
21222       - \l__box_sin_fp * \dim_to_fp:n {#2}
21223     }
21224   }
21225 }
21226 \cs_new_protected:Npn \__box_rotate_y:nnN #1#2#3
21227 {
21228   \dim_set:Nn #3
21229   {
21230     \fp_to_dim:n
21231     {
21232       \l__box_sin_fp * \dim_to_fp:n {#1}
21233       + \l__box_cos_fp * \dim_to_fp:n {#2}
21234     }
21235   }
21236 }

```

Rotation of the edges is done using a different formula for each quadrant. In every case, the top and bottom edges only need the resulting y -values, whereas the left and right edges need the x -values. Each case is a question of picking out which corner ends up at with the maximum top, bottom, left and right value. Doing this by hand means a lot less calculating and avoids lots of comparisons.

```

21237 \cs_new_protected:Npn \__box_rotate_quadrant_one:
21238 {
21239     \__box_rotate_y:nnN \l__box_right_dim \l__box_top_dim
21240     \l__box_top_new_dim
21241     \__box_rotate_y:nnN \l__box_left_dim \l__box_bottom_dim
21242     \l__box_bottom_new_dim
21243     \__box_rotate_x:nnN \l__box_left_dim \l__box_top_dim
21244     \l__box_left_new_dim
21245     \__box_rotate_x:nnN \l__box_right_dim \l__box_bottom_dim
21246     \l__box_right_new_dim
21247 }
21248 \cs_new_protected:Npn \__box_rotate_quadrant_two:
21249 {
21250     \__box_rotate_y:nnN \l__box_right_dim \l__box_bottom_dim
21251     \l__box_top_new_dim
21252     \__box_rotate_y:nnN \l__box_left_dim \l__box_top_dim
21253     \l__box_bottom_new_dim
21254     \__box_rotate_x:nnN \l__box_right_dim \l__box_top_dim
21255     \l__box_left_new_dim
21256     \__box_rotate_x:nnN \l__box_left_dim \l__box_bottom_dim
21257     \l__box_right_new_dim
21258 }
21259 \cs_new_protected:Npn \__box_rotate_quadrant_three:
21260 {
21261     \__box_rotate_y:nnN \l__box_left_dim \l__box_bottom_dim
21262     \l__box_top_new_dim
21263     \__box_rotate_y:nnN \l__box_right_dim \l__box_top_dim
21264     \l__box_bottom_new_dim
21265     \__box_rotate_x:nnN \l__box_right_dim \l__box_bottom_dim
21266     \l__box_left_new_dim
21267     \__box_rotate_x:nnN \l__box_left_dim \l__box_top_dim
21268     \l__box_right_new_dim
21269 }
21270 \cs_new_protected:Npn \__box_rotate_quadrant_four:
21271 {
21272     \__box_rotate_y:nnN \l__box_left_dim \l__box_top_dim
21273     \l__box_top_new_dim
21274     \__box_rotate_y:nnN \l__box_right_dim \l__box_bottom_dim
21275     \l__box_bottom_new_dim
21276     \__box_rotate_x:nnN \l__box_left_dim \l__box_bottom_dim
21277     \l__box_left_new_dim
21278     \__box_rotate_x:nnN \l__box_right_dim \l__box_top_dim
21279     \l__box_right_new_dim
21280 }

```

(End definition for `\box_rotate:Nn` and others. This function is documented on page 227.)

`\l__box_scale_x_fp` Scaling is potentially-different in the two axes.

```

\l__box_scale_y_fp
21281 \fp_new:N \l__box_scale_x_fp
21282 \fp_new:N \l__box_scale_y_fp

```

(End definition for `\l__box_scale_x_fp` and `\l__box_scale_y_fp`.)

`\box_resize_to_wd_and_ht_plus_dp:Nnn` Resizing a box starts by working out the various dimensions of the existing box.

```

\box_resize_to_wd_and_ht_plus_dp:cn
\__box_resize_set_corners:N
\__box_resize:N
\__box_resize:NNN

```



```

21283 \cs_new_protected:Npn \box_resize_to_wd_and_ht_plus_dp:Nnn #1#2#3
21284 {
21285   \hbox_set:Nn #1
21286   {
21287     \__box_resize_set_corners:N #1

```

The x -scaling and resulting box size is easy enough to work out: the dimension is that given as #2, and the scale is simply the new width divided by the old one.

```

21288     \fp_set:Nn \l__box_scale_x_fp
21289     { \dim_to_fp:n {#2} / \dim_to_fp:n { \l__box_right_dim } }

```

The y -scaling needs both the height and the depth of the current box.

```

21290     \fp_set:Nn \l__box_scale_y_fp
21291     {
21292       \dim_to_fp:n {#3}
21293       / \dim_to_fp:n { \l__box_top_dim - \l__box_bottom_dim }
21294     }

```

Hand off to the auxiliary which does the rest of the work.

```

21295     \__box_resize:N #1
21296   }
21297 }
21298 \cs_generate_variant:Nn \box_resize_to_wd_and_ht_plus_dp:Nnn { c }
21299 \cs_new_protected:Npn \__box_resize_set_corners:N #1
21300 {
21301   \dim_set:Nn \l__box_top_dim { \box_ht:N #1 }
21302   \dim_set:Nn \l__box_bottom_dim { -\box_dp:N #1 }
21303   \dim_set:Nn \l__box_right_dim { \box_wd:N #1 }
21304   \dim_zero:N \l__box_left_dim
21305 }

```

With at least one real scaling to do, the next phase is to find the new edge co-ordinates. In the x direction this is relatively easy: just scale the right edge. In the y direction, both dimensions have to be scaled, and this again needs the absolute scale value. Once that is all done, the common resize/rescale code can be employed.

```

21306 \cs_new_protected:Npn \__box_resize:N #1
21307 {
21308   \__box_resize:NNN \l__box_right_new_dim
21309   \l__box_scale_x_fp \l__box_right_dim
21310   \__box_resize:NNN \l__box_bottom_new_dim
21311   \l__box_scale_y_fp \l__box_bottom_dim
21312   \__box_resize:NNN \l__box_top_new_dim
21313   \l__box_scale_y_fp \l__box_top_dim
21314   \__box_resize_common:N #1
21315 }
21316 \cs_new_protected:Npn \__box_resize:NNN #1#2#3
21317 {
21318   \dim_set:Nn #1
21319   { \fp_to_dim:n { \fp_abs:n { #2 } * \dim_to_fp:n { #3 } } }
21320 }

```

(End definition for \box_resize_to_wd_and_ht_plus_dp:Nnn and others. This function is documented on page 227.)

\box_resize_to_ht:Nn Scaling to a (total) height or to a width is a simplified version of the main resizing operation, with the scale simply copied between the two parts. The internal auxiliary is

\box_resize_to_ht:cn

\box_resize_to_ht_plus_dp:Nn

\box_resize_to_ht_plus_dp:cn

\box_resize_to_wd:Nn

\box_resize_to_wd:cn

\box_resize_to_wd_and_ht:Nnn

\box_resize_to_wd_and_ht:cnn

called using the scaling value twice, as the sign for both parts is needed (as this allows the same internal code to be used as for the general case).

```

21321 \cs_new_protected:Npn \box_resize_to_ht:Nn #1#2
21322 {
21323   \hbox_set:Nn #1
21324   {
21325     \__box_resize_set_corners:N #1
21326     \fp_set:Nn \l__box_scale_y_fp
21327     {
21328       \dim_to_fp:n {#2}
21329       / \dim_to_fp:n { \l__box_top_dim }
21330     }
21331     \fp_set_eq:NN \l__box_scale_x_fp \l__box_scale_y_fp
21332     \__box_resize:N #1
21333   }
21334 }
21335 \cs_generate_variant:Nn \box_resize_to_ht:Nn { c }
21336 \cs_new_protected:Npn \box_resize_to_ht_plus_dp:Nn #1#2
21337 {
21338   \hbox_set:Nn #1
21339   {
21340     \__box_resize_set_corners:N #1
21341     \fp_set:Nn \l__box_scale_y_fp
21342     {
21343       \dim_to_fp:n {#2}
21344       / \dim_to_fp:n { \l__box_top_dim - \l__box_bottom_dim }
21345     }
21346     \fp_set_eq:NN \l__box_scale_x_fp \l__box_scale_y_fp
21347     \__box_resize:N #1
21348   }
21349 }
21350 \cs_generate_variant:Nn \box_resize_to_ht_plus_dp:Nn { c }
21351 \cs_new_protected:Npn \box_resize_to_wd:Nn #1#2
21352 {
21353   \hbox_set:Nn #1
21354   {
21355     \__box_resize_set_corners:N #1
21356     \fp_set:Nn \l__box_scale_x_fp
21357     { \dim_to_fp:n {#2} / \dim_to_fp:n { \l__box_right_dim } }
21358     \fp_set_eq:NN \l__box_scale_y_fp \l__box_scale_x_fp
21359     \__box_resize:N #1
21360   }
21361 }
21362 \cs_generate_variant:Nn \box_resize_to_wd:Nn { c }
21363 \cs_new_protected:Npn \box_resize_to_wd_and_ht:Nnn #1#2#3
21364 {
21365   \hbox_set:Nn #1
21366   {
21367     \__box_resize_set_corners:N #1
21368     \fp_set:Nn \l__box_scale_x_fp
21369     { \dim_to_fp:n {#2} / \dim_to_fp:n { \l__box_right_dim } }
21370     \fp_set:Nn \l__box_scale_y_fp
21371     {
21372       \dim_to_fp:n {#3}

```

```

21373         / \dim_to_fp:n { \l__box_top_dim }
21374     }
21375     \__box_resize:N #1
21376 }
21377 }
21378 \cs_generate_variant:Nn \box_resize_to_wd_and_ht:Nnn { c }

```

(End definition for \box_resize_to_ht:Nn and others. These functions are documented on page 226.)

\box_scale:Nnn When scaling a box, setting the scaling itself is easy enough. The new dimensions are also relatively easy to find, allowing only for the need to keep them positive in all cases.

\box_scale:cnn Once that is done then after a check for the trivial scaling a hand-off can be made to the common code. The code here is split into two as this allows sharing with the auto-resizing functions.

__box_scale_aux:N

```

21379 \cs_new_protected:Npn \box_scale:Nnn #1#2#3
21380 {
21381     \hbox_set:Nn #1
21382     {
21383         \fp_set:Nn \l__box_scale_x_fp {#2}
21384         \fp_set:Nn \l__box_scale_y_fp {#3}
21385         \__box_scale_aux:N #1
21386     }
21387 }
21388 \cs_generate_variant:Nn \box_scale:Nnn { c }
21389 \cs_new_protected:Npn \__box_scale_aux:N #1
21390 {
21391     \dim_set:Nn \l__box_top_dim { \box_ht:N #1 }
21392     \dim_set:Nn \l__box_bottom_dim { -\box_dp:N #1 }
21393     \dim_set:Nn \l__box_right_dim { \box_wd:N #1 }
21394     \dim_zero:N \l__box_left_dim
21395     \dim_set:Nn \l__box_top_new_dim
21396     { \fp_abs:n { \l__box_scale_y_fp } \l__box_top_dim }
21397     \dim_set:Nn \l__box_bottom_new_dim
21398     { \fp_abs:n { \l__box_scale_y_fp } \l__box_bottom_dim }
21399     \dim_set:Nn \l__box_right_new_dim
21400     { \fp_abs:n { \l__box_scale_x_fp } \l__box_right_dim }
21401     \__box_resize_common:N #1
21402 }

```

(End definition for \box_scale:Nnn and __box_scale_aux:N. This function is documented on page 227.)

\box_autosize_to_wd_and_ht:Nnn Although autosizing a box uses dimensions, it has more in common in implementation with scaling. As such, most of the real work here is done elsewhere.

\box_autosize_to_wd_and_ht:cnn

\box_autosize_to_wd_and_ht_plus_dp:cnn

\box_autosize_to_wd_and_ht_plus_dp:Nnn

__box_autosize:Nnnn

```

21403 \cs_new_protected:Npn \box_autosize_to_wd_and_ht:Nnn #1#2#3
21404 { \__box_autosize:Nnnn #1 {#2} {#3} { \box_ht:N #1 } }
21405 \cs_generate_variant:Nn \box_autosize_to_wd_and_ht:Nnn { c }
21406 \cs_new_protected:Npn \box_autosize_to_wd_and_ht_plus_dp:Nnn #1#2#3
21407 { \__box_autosize:Nnnn #1 {#2} {#3} { \box_ht:N #1 + \box_dp:N #1 } }
21408 \cs_generate_variant:Nn \box_autosize_to_wd_and_ht_plus_dp:Nnn { c }
21409 \cs_new_protected:Npn \__box_autosize:Nnnn #1#2#3#4
21410 {
21411     \hbox_set:Nn #1
21412     {

```

```

21413 \fp_set:Nn \l__box_scale_x_fp { ( #2 ) / \box_wd:N #1 }
21414 \fp_set:Nn \l__box_scale_y_fp { ( #3 ) / ( #4 ) }
21415 \fp_compare:nNnTF \l__box_scale_x_fp > \l__box_scale_y_fp
21416 { \fp_set_eq:NN \l__box_scale_x_fp \l__box_scale_y_fp }
21417 { \fp_set_eq:NN \l__box_scale_y_fp \l__box_scale_x_fp }
21418 \__box_scale_aux:N #1
21419 }
21420 }

```

(End definition for `\box_autosize_to_wd_and_ht:Nnn`, `\box_autosize_to_wd_and_ht_plus_dp:cnn`, and `__box_autosize:Nnnn`. These functions are documented on page 225.)

`__box_resize_common:N` The main resize function places its input into a box which start off with zero width, and includes the handles for engine rescaling.

```

21421 \cs_new_protected:Npn \__box_resize_common:N #1
21422 {
21423   \hbox_set:Nn \l__box_internal_box
21424   {
21425     \__driver_box_use_scale:Nnn
21426     #1
21427     \l__box_scale_x_fp
21428     \l__box_scale_y_fp
21429   }

```

The new height and depth can be applied directly.

```

21430 \fp_compare:nNnTF \l__box_scale_y_fp > \c_zero_fp
21431 {
21432   \box_set_ht:Nn \l__box_internal_box { \l__box_top_new_dim }
21433   \box_set_dp:Nn \l__box_internal_box { -\l__box_bottom_new_dim }
21434 }
21435 {
21436   \box_set_dp:Nn \l__box_internal_box { \l__box_top_new_dim }
21437   \box_set_ht:Nn \l__box_internal_box { -\l__box_bottom_new_dim }
21438 }

```

Things are not quite as obvious for the width, as the reference point needs to remain unchanged. For positive scaling factors resizing the box is all that is needed. However, for case of a negative scaling the material must be shifted such that the reference point ends up in the right place.

```

21439 \fp_compare:nNnTF \l__box_scale_x_fp < \c_zero_fp
21440 {
21441   \hbox_to_wd:nn { \l__box_right_new_dim }
21442   {
21443     \tex_kern:D \l__box_right_new_dim
21444     \box_use_drop:N \l__box_internal_box
21445     \tex_hss:D
21446   }
21447 }
21448 {
21449   \box_set_wd:Nn \l__box_internal_box { \l__box_right_new_dim }
21450   \hbox:n
21451   {
21452     \tex_kern:D \c_zero_dim
21453     \box_use_drop:N \l__box_internal_box
21454     \tex_hss:D

```

```

21455     }
21456   }
21457 }

```

(End definition for `_box_resize_common:N`.)

37.12 Deprecated functions

```

\box_resize:Nnn
\box_resize:cnn
\box_use_clear:N
\box_use_clear:c
21458 \__debug_deprecation:nnNNpn
21459 { 2018-12-31 } { \box_resize_to_wd_and_ht_plus_dp:Nnn }
21460 \cs_new_protected:Npn \box_resize:Nnn
21461 { \box_resize_to_wd_and_ht_plus_dp:Nnn }
21462 \__debug_deprecation:nnNNpn
21463 { 2018-12-31 } { \box_resize_to_wd_and_ht_plus_dp:cnn }
21464 \cs_new_protected:Npn \box_resize:cnn
21465 { \box_resize_to_wd_and_ht_plus_dp:cnn }
21466 \__debug_deprecation:nnNNpn
21467 { 2018-12-31 } { \box_use_clear:N }
21468 \cs_new_protected:Npn \box_use_clear:N { \box_use_drop:N }
21469 \__debug_deprecation:nnNNpn
21470 { 2018-12-31 } { \box_use_clear:c }
21471 \cs_new_protected:Npn \box_use_clear:c { \box_use_drop:c }

```

(End definition for `\box_resize:Nnn` and `\box_use_clear:N`.)

```

21472 </initex | package>

```

38 l3coffins Implementation

```

21473 <*initex | package>
21474 <@@=coffin>

```

38.1 Coffins: data structures and general variables

`\l__coffin_internal_box` Scratch variables.

```

\l__coffin_internal_dim
\l__coffin_internal_tl
21475 \box_new:N \l__coffin_internal_box
21476 \dim_new:N \l__coffin_internal_dim
21477 \tl_new:N \l__coffin_internal_tl

```

(End definition for `\l__coffin_internal_box`, `\l__coffin_internal_dim`, and `\l__coffin_internal_tl`.)

`\c__coffin_corners_prop` The “corners”; of a coffin define the real content, as opposed to the $\mathrm{T}_{\mathrm{E}}\mathrm{X}$ bounding box. They all start off in the same place, of course.

```

21478 \prop_const_from_keyval:Nn \c__coffin_corners_prop
21479 {
21480   tl = { Opt } { Opt } ,
21481   tr = { Opt } { Opt } ,
21482   bl = { Opt } { Opt } ,
21483   br = { Opt } { Opt } ,
21484 }

```

(End definition for `\c__coffin_corners_prop`.)

`\c__coffin_poles_prop` Pole positions are given for horizontal, vertical and reference-point based values.

```

21485 \prop_const_from_keyval:Nn \c__coffin_poles_prop
21486 {
21487   l = { Opt } { Opt } { Opt } { 1000pt } ,
21488   hc = { Opt } { Opt } { Opt } { 1000pt } ,
21489   r = { Opt } { Opt } { Opt } { 1000pt } ,
21490   b = { Opt } { Opt } { 1000pt } { Opt } ,
21491   vc = { Opt } { Opt } { 1000pt } { Opt } ,
21492   t = { Opt } { Opt } { 1000pt } { Opt } ,
21493   B = { Opt } { Opt } { 1000pt } { Opt } ,
21494   H = { Opt } { Opt } { 1000pt } { Opt } ,
21495   T = { Opt } { Opt } { 1000pt } { Opt } ,
21496 }

```

(End definition for \c__coffin_poles_prop.)

`\l__coffin_slope_x_fp` Used for calculations of intersections.
`\l__coffin_slope_y_fp`

```

21497 \fp_new:N \l__coffin_slope_x_fp
21498 \fp_new:N \l__coffin_slope_y_fp

```

(End definition for \l__coffin_slope_x_fp and \l__coffin_slope_y_fp.)

`\l__coffin_error_bool` For propagating errors so that parts of the code can work around them.

```

21499 \bool_new:N \l__coffin_error_bool

```

(End definition for \l__coffin_error_bool.)

`\l__coffin_offset_x_dim` The offset between two sets of coffin handles when typesetting. These values are corrected
`\l__coffin_offset_y_dim` from those requested in an alignment for the positions of the handles.

```

21500 \dim_new:N \l__coffin_offset_x_dim
21501 \dim_new:N \l__coffin_offset_y_dim

```

(End definition for \l__coffin_offset_x_dim and \l__coffin_offset_y_dim.)

`\l__coffin_pole_a_tl` Needed for finding the intersection of two poles.
`\l__coffin_pole_b_tl`

```

21502 \tl_new:N \l__coffin_pole_a_tl
21503 \tl_new:N \l__coffin_pole_b_tl

```

(End definition for \l__coffin_pole_a_tl and \l__coffin_pole_b_tl.)

`\l__coffin_x_dim` For calculating intersections and so forth.
`\l__coffin_y_dim`

```

21504 \dim_new:N \l__coffin_x_dim
21505 \dim_new:N \l__coffin_y_dim
21506 \dim_new:N \l__coffin_x_prime_dim
21507 \dim_new:N \l__coffin_y_prime_dim

```

(End definition for \l__coffin_x_dim and others.)

38.2 Basic coffin functions

There are a number of basic functions needed for creating coffins and placing material in them. This all relies on the following data structures.

\coffin_if_exist_p:N Several of the higher-level coffin functions would give multiple errors if the coffin does not exist. A cleaner way to handle this is provided here: both the box and the coffin structure are checked.

```
\coffin_if_exist_p:c
\coffin_if_exist:NTF
\coffin_if_exist:cTF
21508 \prg_new_conditional:Npnn \coffin_if_exist:N #1 { p , T , F , TF }
21509 {
21510     \cs_if_exist:NTF #1
21511     {
21512         \cs_if_exist:cTF { l__coffin_poles_ __int_value:w #1 _prop }
21513         { \prg_return_true: }
21514         { \prg_return_false: }
21515     }
21516     { \prg_return_false: }
21517 }
21518 \cs_generate_variant:Nn \coffin_if_exist_p:N { c }
21519 \cs_generate_variant:Nn \coffin_if_exist:NT { c }
21520 \cs_generate_variant:Nn \coffin_if_exist:NF { c }
21521 \cs_generate_variant:Nn \coffin_if_exist:NTF { c }
```

(End definition for \coffin_if_exist:NTF. This function is documented on page 229.)

__coffin_if_exist:NT Several of the higher-level coffin functions would give multiple errors if the coffin does not exist. So a wrapper is provided to deal with this correctly, issuing an error on erroneous use.

```
21522 \cs_new_protected:Npn \__coffin_if_exist:NT #1#2
21523 {
21524     \coffin_if_exist:NTF #1
21525     { #2 }
21526     {
21527         \__msg_kernel_error:nnx { kernel } { unknown-coffin }
21528         { \token_to_str:N #1 }
21529     }
21530 }
```

(End definition for __coffin_if_exist:NT.)

\coffin_clear:N Clearing coffins means emptying the box and resetting all of the structures.

```
\coffin_clear:c
21531 \cs_new_protected:Npn \coffin_clear:N #1
21532 {
21533     \__coffin_if_exist:NT #1
21534     {
21535         \box_clear:N #1
21536         \__coffin_reset_structure:N #1
21537     }
21538 }
21539 \cs_generate_variant:Nn \coffin_clear:N { c }
```

(End definition for \coffin_clear:N. This function is documented on page 229.)

\coffin_new:N Creating a new coffin means making the underlying box and adding the data structures.
\coffin_new:c These are created globally, as there is a need to avoid any strange effects if the coffin is created inside a group. This means that the usual rule about \l_... variables has to be broken. The \debug_suspend: and \debug_resume: functions prevent these checks. They also prevent \prop_clear_new:c from writing useless information to the log file.

```

21540 \cs_new_protected:Npn \coffin_new:N #1
21541 {
21542   \box_new:N #1
21543   \debug_suspend:
21544   \prop_clear_new:c { l__coffin_corners_ \__int_value:w #1 _prop }
21545   \prop_clear_new:c { l__coffin_poles_ \__int_value:w #1 _prop }
21546   \prop_gset_eq:cN { l__coffin_corners_ \__int_value:w #1 _prop }
21547     \c__coffin_corners_prop
21548   \prop_gset_eq:cN { l__coffin_poles_ \__int_value:w #1 _prop }
21549     \c__coffin_poles_prop
21550   \debug_resume:
21551 }
21552 \cs_generate_variant:Nn \coffin_new:N { c }

```

(End definition for \coffin_new:N. This function is documented on page 229.)

\hcoffin_set:Nn Horizontal coffins are relatively easy: set the appropriate box, reset the structures then
\hcoffin_set:cn update the handle positions.

```

21553 \cs_new_protected:Npn \hcoffin_set:Nn #1#2
21554 {
21555   \__coffin_if_exist:NT #1
21556   {
21557     \hbox_set:Nn #1
21558       {
21559         \color_ensure_current:
21560         #2
21561       }
21562     \__coffin_reset_structure:N #1
21563     \__coffin_update_poles:N #1
21564     \__coffin_update_corners:N #1
21565   }
21566 }
21567 \cs_generate_variant:Nn \hcoffin_set:Nn { c }

```

(End definition for \hcoffin_set:Nn. This function is documented on page 229.)

\vcoffin_set:Nnn Setting vertical coffins is more complex. First, the material is typeset with a given width.
\vcoffin_set:cnn The default handles and poles are set as for a horizontal coffin, before finding the top baseline using a temporary box. No \color_ensure_current: here as that would add a whatsit to the start of the vertical box and mess up the location of the T pole (see *TEX by Topic* for discussion of the \vtop primitive, used to do the measuring).

```

21568 \cs_new_protected:Npn \vcoffin_set:Nnn #1#2#3
21569 {
21570   \__coffin_if_exist:NT #1
21571   {
21572     \vbox_set:Nn #1
21573       {
21574         \dim_set:Nn \tex_hsize:D {#2}

```



```

21575 \begin{package}
21576         \dim_set_eq:NN \linewidth \tex_hsize:D
21577         \dim_set_eq:NN \columnwidth \tex_hsize:D
21578 \end{package}
21579         #3
21580     }
21581     \__coffin_reset_structure:N #1
21582     \__coffin_update_poles:N #1
21583     \__coffin_update_corners:N #1
21584     \vbox_set_top:Nn \l__coffin_internal_box { \vbox_unpack:N #1 }
21585     \__coffin_set_pole:Nnx #1 { T }
21586     {
21587         { Opt }
21588         {
21589             \dim_eval:n
21590             { \box_ht:N #1 - \box_ht:N \l__coffin_internal_box }
21591         }
21592         { 1000pt }
21593         { Opt }
21594     }
21595     \box_clear:N \l__coffin_internal_box
21596 }
21597 }
21598 \cs_generate_variant:Nn \vcoffin_set:Nnn { c }

```

(End definition for \vcoffin_set:Nnn. This function is documented on page 230.)

\hcoffin_set:Nw These are the “begin”/“end” versions of the above: watch the grouping!
\hcoffin_set:cw `\cs_new_protected:Npn \hcoffin_set:Nw #1`
\hcoffin_set_end: `{`

```

21599 \cs_new_protected:Npn \hcoffin_set:Nw #1
21600 {
21601     \__coffin_if_exist:NT #1
21602     {
21603         \hbox_set:Nw #1 \color_ensure_current:
21604         \cs_set_protected:Npn \hcoffin_set_end:
21605         {
21606             \hbox_set_end:
21607             \__coffin_reset_structure:N #1
21608             \__coffin_update_poles:N #1
21609             \__coffin_update_corners:N #1
21610         }
21611     }
21612 }
21613 \cs_new_protected:Npn \hcoffin_set_end: { }
21614 \cs_generate_variant:Nn \hcoffin_set:Nw { c }

```

(End definition for \hcoffin_set:Nw and \hcoffin_set_end:. These functions are documented on page 229.)

\vcoffin_set:Nnw The same for vertical coffins.

\vcoffin_set:cnw `\cs_new_protected:Npn \vcoffin_set:Nnw #1#2`
\vcoffin_set_end: `{`

```

21615 \cs_new_protected:Npn \vcoffin_set:Nnw #1#2
21616 {
21617     \__coffin_if_exist:NT #1
21618     {
21619         \vbox_set:Nw #1
21620         \dim_set:Nn \tex_hsize:D {#2}

```

```

21621 \*package\
21622     \dim_set_eq:NN \linewidth \tex_hsize:D
21623     \dim_set_eq:NN \columnwidth \tex_hsize:D
21624 \endpackage\
21625 \cs_set_protected:Npn \vcoffin_set_end:
21626 {
21627     \vbox_set_end:
21628     \__coffin_reset_structure:N #1
21629     \__coffin_update_poles:N #1
21630     \__coffin_update_corners:N #1
21631     \vbox_set_top:Nn \l__coffin_internal_box { \vbox_unpack:N #1 }
21632     \__coffin_set_pole:Nnx #1 { T }
21633     {
21634         { Opt }
21635         {
21636             \dim_eval:n
21637             { \box_ht:N #1 - \box_ht:N \l__coffin_internal_box }
21638         }
21639         { 1000pt }
21640         { Opt }
21641     }
21642     \box_clear:N \l__coffin_internal_box
21643 }
21644 }
21645 }
21646 \cs_new_protected:Npn \vcoffin_set_end: { }
21647 \cs_generate_variant:Nn \vcoffin_set:Nnw { c }

```

(End definition for `\vcoffin_set:Nnw` and `\vcoffin_set_end:`. These functions are documented on page 230.)

`\coffin_set_eq:NN` Setting two coffins equal is just a wrapper around other functions.

```

\coffin_set_eq:Nc
\coffin_set_eq:cN
\coffin_set_eq:cc
21648 \cs_new_protected:Npn \coffin_set_eq:NN #1#2
21649 {
21650     \__coffin_if_exist:NT #1
21651     {
21652         \box_set_eq:NN #1 #2
21653         \__coffin_set_eq_structure:NN #1 #2
21654     }
21655 }
21656 \cs_generate_variant:Nn \coffin_set_eq:NN { c , Nc , cc }

```

(End definition for `\coffin_set_eq:NN`. This function is documented on page 229.)

`\c_empty_coffin` Special coffins: these cannot be set up earlier as they need `\coffin_new:N`. The empty coffin is set as a box as the full coffin-setting system needs some material which is not yet available. Debugging must be suspended as we are assigning to a constant coffin.

```

\l__coffin_aligned_coffin
\l__coffin_aligned_internal_coffin
21657 \coffin_new:N \c_empty_coffin
21658 \debug_suspend:
21659 \hbox_set:Nn \c_empty_coffin { }
21660 \debug_resume:
21661 \coffin_new:N \l__coffin_aligned_coffin
21662 \coffin_new:N \l__coffin_aligned_internal_coffin

```

(End definition for `\c_empty_coffin`, `\l__coffin_aligned_coffin`, and `\l__coffin_aligned_internal_coffin`. This variable is documented on page 232.)

`\l_tmpa_coffin` The usual scratch space.
`\l_tmpb_coffin` 21663 `\coffin_new:N \l_tmpa_coffin`
21664 `\coffin_new:N \l_tmpb_coffin`

(End definition for `\l_tmpa_coffin` and `\l_tmpb_coffin`. These variables are documented on page 232.)

38.3 Measuring coffins

`\coffin_dp:N` Coffins are just boxes when it comes to measurement. However, semantically a separate set of functions are required.
`\coffin_dp:c`

`\coffin_ht:N` 21665 `\cs_new_eq:NN \coffin_dp:N \box_dp:N`
`\coffin_ht:c` 21666 `\cs_new_eq:NN \coffin_dp:c \box_dp:c`
`\coffin_wd:N` 21667 `\cs_new_eq:NN \coffin_ht:N \box_ht:N`
`\coffin_wd:c` 21668 `\cs_new_eq:NN \coffin_ht:c \box_ht:c`
21669 `\cs_new_eq:NN \coffin_wd:N \box_wd:N`
21670 `\cs_new_eq:NN \coffin_wd:c \box_wd:c`

(End definition for `\coffin_dp:N`, `\coffin_ht:N`, and `\coffin_wd:N`. These functions are documented on page 231.)

38.4 Coffins: handle and pole management

`__coffin_get_pole:NnN` A simple wrapper around the recovery of a coffin pole, with some error checking and recovery built-in.

21671 `\cs_new_protected:Npn __coffin_get_pole:NnN #1#2#3`
21672 `{`
21673 `\prop_get:cnNF`
21674 `{ l__coffin_poles_ __int_value:w #1 _prop } {#2} #3`
21675 `{`
21676 `_msg_kernel_error:nxx { kernel } { unknown-coffin-pole }`
21677 `{#2} { \token_to_str:N #1 }`
21678 `\tl_set:Nn #3 { { Opt } { Opt } { Opt } { Opt } }`
21679 `}`
21680 `}`

(End definition for `__coffin_get_pole:NnN`.)

`__coffin_reset_structure:N` Resetting the structure is a simple copy job.

21681 `\cs_new_protected:Npn __coffin_reset_structure:N #1`
21682 `{`
21683 `\prop_set_eq:cN { l__coffin_corners_ __int_value:w #1 _prop }`
21684 `\c__coffin_corners_prop`
21685 `\prop_set_eq:cN { l__coffin_poles_ __int_value:w #1 _prop }`
21686 `\c__coffin_poles_prop`
21687 `}`

(End definition for `__coffin_reset_structure:N`.)

`_coffin_set_eq_structure:NN` Setting coffin structures equal simply means copying the property list.

```

\coffin_gset_eq_structure:NN
21688 \cs_new_protected:Npn \__coffin_set_eq_structure:NN #1#2
21689 {
21690   \prop_set_eq:cc { l__coffin_corners_ \__int_value:w #1 _prop }
21691   { l__coffin_corners_ \__int_value:w #2 _prop }
21692   \prop_set_eq:cc { l__coffin_poles_ \__int_value:w #1 _prop }
21693   { l__coffin_poles_ \__int_value:w #2 _prop }
21694 }
21695 \cs_new_protected:Npn \__coffin_gset_eq_structure:NN #1#2
21696 {
21697   \prop_gset_eq:cc { l__coffin_corners_ \__int_value:w #1 _prop }
21698   { l__coffin_corners_ \__int_value:w #2 _prop }
21699   \prop_gset_eq:cc { l__coffin_poles_ \__int_value:w #1 _prop }
21700   { l__coffin_poles_ \__int_value:w #2 _prop }
21701 }

```

(End definition for `_coffin_set_eq_structure:NN` and `_coffin_gset_eq_structure:NN`.)

`\coffin_set_horizontal_pole:Nnn` Setting the pole of a coffin at the user/designer level requires a bit more care. The idea here is to provide a reasonable interface to the system, then to do the setting with full expansion. The three-argument version is used internally to do a direct setting.

`\coffin_set_vertical_pole:Nnn`

`\coffin_set_vertical_pole:cnn`

`__coffin_set_pole:Nnn`

`__coffin_set_pole:Nnx`

```

21702 \cs_new_protected:Npn \coffin_set_horizontal_pole:Nnn #1#2#3
21703 {
21704   \__coffin_if_exist:NT #1
21705   {
21706     \__coffin_set_pole:Nnx #1 {#2}
21707     {
21708       { Opt } { \dim_eval:n {#3} }
21709       { 1000pt } { Opt }
21710     }
21711   }
21712 }
21713 \cs_new_protected:Npn \coffin_set_vertical_pole:Nnn #1#2#3
21714 {
21715   \__coffin_if_exist:NT #1
21716   {
21717     \__coffin_set_pole:Nnx #1 {#2}
21718     {
21719       { \dim_eval:n {#3} } { Opt }
21720       { Opt } { 1000pt }
21721     }
21722   }
21723 }
21724 \cs_new_protected:Npn \__coffin_set_pole:Nnn #1#2#3
21725 { \prop_put:cnn { l__coffin_poles_ \__int_value:w #1 _prop } {#2} {#3} }
21726 \cs_generate_variant:Nn \coffin_set_horizontal_pole:Nnn { c }
21727 \cs_generate_variant:Nn \coffin_set_vertical_pole:Nnn { c }
21728 \cs_generate_variant:Nn \__coffin_set_pole:Nnn { Nnx }

```

(End definition for `\coffin_set_horizontal_pole:Nnn`, `\coffin_set_vertical_pole:Nnn`, and `__coffin_set_pole:Nnn`. These functions are documented on page 230.)

`__coffin_update_corners:N`

Updating the corners of a coffin is straight-forward as at this stage there can be no rotation. So the corners of the content are just those of the underlying TeX box.

```

21729 \cs_new_protected:Npn \__coffin_update_corners:N #1
21730 {
21731   \prop_put:cnx { l__coffin_corners_ \__int_value:w #1 _prop } { tl }
21732   { { Opt } { \dim_eval:n { \box_ht:N #1 } } } }
21733   \prop_put:cnx { l__coffin_corners_ \__int_value:w #1 _prop } { tr }
21734   { { \dim_eval:n { \box_wd:N #1 } } { \dim_eval:n { \box_ht:N #1 } } } }
21735   \prop_put:cnx { l__coffin_corners_ \__int_value:w #1 _prop } { bl }
21736   { { Opt } { \dim_eval:n { -\box_dp:N #1 } } } }
21737   \prop_put:cnx { l__coffin_corners_ \__int_value:w #1 _prop } { br }
21738   { { \dim_eval:n { \box_wd:N #1 } } { \dim_eval:n { -\box_dp:N #1 } } } }
21739 }

```

(End definition for __coffin_update_corners:N.)

__coffin_update_poles:N This function is called when a coffin is set, and updates the poles to reflect the nature of size of the box. Thus this function only alters poles where the default position is dependent on the size of the box. It also does not set poles which are relevant only to vertical coffins.

```

21740 \cs_new_protected:Npn \__coffin_update_poles:N #1
21741 {
21742   \prop_put:cnx { l__coffin_poles_ \__int_value:w #1 _prop } { hc }
21743   {
21744     { \dim_eval:n { 0.5 \box_wd:N #1 } }
21745     { Opt } { Opt } { 1000pt }
21746   }
21747   \prop_put:cnx { l__coffin_poles_ \__int_value:w #1 _prop } { r }
21748   {
21749     { \dim_eval:n { \box_wd:N #1 } }
21750     { Opt } { Opt } { 1000pt }
21751   }
21752   \prop_put:cnx { l__coffin_poles_ \__int_value:w #1 _prop } { vc }
21753   {
21754     { Opt }
21755     { \dim_eval:n { ( \box_ht:N #1 - \box_dp:N #1 ) / 2 } }
21756     { 1000pt }
21757     { Opt }
21758   }
21759   \prop_put:cnx { l__coffin_poles_ \__int_value:w #1 _prop } { t }
21760   {
21761     { Opt }
21762     { \dim_eval:n { \box_ht:N #1 } }
21763     { 1000pt }
21764     { Opt }
21765   }
21766   \prop_put:cnx { l__coffin_poles_ \__int_value:w #1 _prop } { b }
21767   {
21768     { Opt }
21769     { \dim_eval:n { -\box_dp:N #1 } }
21770     { 1000pt }
21771     { Opt }
21772   }
21773 }

```

(End definition for __coffin_update_poles:N.)

38.5 Coffins: calculation of pole intersections

```
\_coffin_calculate_intersection:Nnn
\_coffin_calculate_intersection:nnnnnnnn
\_coffin_calculate_intersection_aux:nnnnnN
```

The lead off in finding intersections is to recover the two poles and then hand off to the auxiliary for the actual calculation. There may of course not be an intersection, for which an error trap is needed.

```
21774 \cs_new_protected:Npn \_coffin_calculate_intersection:Nnn #1#2#3
21775 {
21776   \_coffin_get_pole:NnN #1 {#2} \l__coffin_pole_a_tl
21777   \_coffin_get_pole:NnN #1 {#3} \l__coffin_pole_b_tl
21778   \bool_set_false:N \l__coffin_error_bool
21779   \exp_last_two_unbraced:Noo
21780   \_coffin_calculate_intersection:nnnnnnnn
21781   \l__coffin_pole_a_tl \l__coffin_pole_b_tl
21782   \bool_if:NT \l__coffin_error_bool
21783   {
21784     \_msg_kernel_error:nn { kernel } { no-pole-intersection }
21785     \dim_zero:N \l__coffin_x_dim
21786     \dim_zero:N \l__coffin_y_dim
21787   }
21788 }
```

The two poles passed here each have four values (as dimensions), (a, b, c, d) and (a', b', c', d') . These are arguments 1–4 and 5–8, respectively. In both cases a and b are the co-ordinates of a point on the pole and c and d define the direction of the pole. Finding the intersection depends on the directions of the poles, which are given by d/c and d'/c' . However, if one of the poles is either horizontal or vertical then one or more of c, d, c' and d' are zero and a special case is needed.

```
21789 \cs_new_protected:Npn \_coffin_calculate_intersection:nnnnnnnn
21790 #1#2#3#4#5#6#7#8
21791 {
21792   \dim_compare:nNnTF {#3} = { \c_zero_dim }
```

The case where the first pole is vertical. So the x -component of the interaction is at a . There is then a test on the second pole: if it is also vertical then there is an error.

```
21793 {
21794   \dim_set:Nn \l__coffin_x_dim {#1}
21795   \dim_compare:nNnTF {#7} = { \c_zero_dim
21796     { \bool_set_true:N \l__coffin_error_bool }

```

The second pole may still be horizontal, in which case the y -component of the intersection is b' . If not,

$$y = \frac{d'}{c'} (x - a') + b'$$

with the x -component already known to be $\#1$. This calculation is done as a generalised auxiliary.

```
21797 {
21798   \dim_compare:nNnTF {#8} = { \c_zero_dim
21799     { \dim_set:Nn \l__coffin_y_dim {#6} }
21800     {
21801       \_coffin_calculate_intersection_aux:nnnnnN
21802       {#1} {#5} {#6} {#7} {#8} \l__coffin_y_dim
21803     }
21804   }
21805 }
```

If the first pole is not vertical then it may be horizontal. If so, then the procedure is essentially the same as that already done but with the x - and y -components interchanged.

```

21806     {
21807         \dim_compare:nNnTF {#4} = \c_zero_dim
21808     {
21809         \dim_set:Nn \l__coffin_y_dim {#2}
21810         \dim_compare:nNnTF {#8} = { \c_zero_dim }
21811         { \bool_set_true:N \l__coffin_error_bool }
21812     }
21813     \dim_compare:nNnTF {#7} = \c_zero_dim
21814     { \dim_set:Nn \l__coffin_x_dim {#5} }

```

The formula for the case where the second pole is neither horizontal nor vertical is

$$x = \frac{c'}{d'}(y - b') + a'$$

which is again handled by the same auxiliary.

```

21815     {
21816         \__coffin_calculate_intersection_aux:nnnnnN
21817         {#2} {#6} {#5} {#8} {#7} \l__coffin_x_dim
21818     }
21819 }
21820 }

```

The first pole is neither horizontal nor vertical. This still leaves the second pole, which may be a special case. For those possibilities, the calculations are the same as above with the first and second poles interchanged.

```

21821     {
21822         \dim_compare:nNnTF {#7} = \c_zero_dim
21823     {
21824         \dim_set:Nn \l__coffin_x_dim {#5}
21825         \__coffin_calculate_intersection_aux:nnnnnN
21826         {#5} {#1} {#2} {#3} {#4} \l__coffin_y_dim
21827     }
21828     {
21829         \dim_compare:nNnTF {#8} = \c_zero_dim
21830     {
21831         \dim_set:Nn \l__coffin_y_dim {#6}
21832         \__coffin_calculate_intersection_aux:nnnnnN
21833         {#6} {#2} {#1} {#4} {#3} \l__coffin_x_dim
21834     }

```

If none of the special cases apply then there is still a need to check that there is a unique intersection between the two pole. This is the case if they have different slopes.

```

21835     {
21836         \fp_set:Nn \l__coffin_slope_x_fp
21837         { \dim_to_fp:n {#4} / \dim_to_fp:n {#3} }
21838         \fp_set:Nn \l__coffin_slope_y_fp
21839         { \dim_to_fp:n {#8} / \dim_to_fp:n {#7} }
21840         \fp_compare:nNnTF
21841         \l__coffin_slope_x_fp = \l__coffin_slope_y_fp
21842         { \bool_set_true:N \l__coffin_error_bool }

```

All of the tests pass, so there is the full complexity of the calculation:

$$x = \frac{a(d/c) - a'(d'/c') - b + b'}{(d/c) - (d'/c')}$$

and noting that the two ratios are already worked out from the test just performed. There is quite a bit of shuffling from dimensions to floating points in order to do the work. The y -values is then worked out using the standard auxiliary starting from the x -position.

```

21843         {
21844             \dim_set:Nn \l__coffin_x_dim
21845             {
21846                 \fp_to_dim:n
21847                 {
21848                     (
21849                         \dim_to_fp:n {#1} * \l__coffin_slope_x_fp
21850                         - ( \dim_to_fp:n {#5} * \l__coffin_slope_y_fp )
21851                         - \dim_to_fp:n {#2}
21852                         + \dim_to_fp:n {#6}
21853                     )
21854                     /
21855                     ( \l__coffin_slope_x_fp - \l__coffin_slope_y_fp )
21856                 }
21857             }
21858             \__coffin_calculate_intersection_aux:nnnnnN
21859             { \l__coffin_x_dim }
21860             {#5} {#6} {#8} {#7} \l__coffin_y_dim
21861         }
21862     }
21863 }
21864 }
21865 }
21866 }

```

The formula for finding the intersection point is in most cases the same. The formula here is

$$\#6 = \#4 \cdot \left(\frac{\#1 - \#2}{\#5} \right) \#3$$

Thus #4 and #5 should be the directions of the pole while #2 and #3 are co-ordinates.

```

21867 \cs_new_protected:Npn \__coffin_calculate_intersection_aux:nnnnnN
21868     #1#2#3#4#5#6
21869     {
21870         \dim_set:Nn #6
21871         {
21872             \fp_to_dim:n
21873             {
21874                 \dim_to_fp:n {#4} *
21875                 ( \dim_to_fp:n {#1} - \dim_to_fp:n {#2} ) /
21876                 \dim_to_fp:n {#5}
21877                 + \dim_to_fp:n {#3}
21878             }
21879         }
21880     }

```


(End definition for `__coffin_calculate_intersection:Nnn`, `__coffin_calculate_intersection:nnnnnnnn`, and `__coffin_calculate_intersection_aux:nnnnnN`.)

38.6 Aligning and typesetting of coffins

`\coffin_join:NnnNnnnn` This command joins two coffins, using a horizontal and vertical pole from each coffin and making an offset between the two. The result is stored as the as a third coffin, which has all of its handles reset to standard values. First, the more basic alignment function `\coffin_join:nnncnnnn` is used to get things started.

```
21881 \cs_new_protected:Npn \coffin_join:NnnNnnnn #1#2#3#4#5#6#7#8
21882 {
21883   \__coffin_align:NnnNnnnnN
21884   #1 {#2} {#3} #4 {#5} {#6} {#7} {#8} \l__coffin_aligned_coffin
```

Correct the placement of the reference point. If the x -offset is negative then the reference point of the second box is to the left of that of the first, which is corrected using a kern. On the right side the first box might stick out, which would show up if it is wider than the sum of the x -offset and the width of the second box. So a second kern may be needed.

```
21885   \hbox_set:Nn \l__coffin_aligned_coffin
21886   {
21887     \dim_compare:nNnT { \l__coffin_offset_x_dim } < \c_zero_dim
21888     { \tex_kern:D -\l__coffin_offset_x_dim }
21889     \hbox_unpack:N \l__coffin_aligned_coffin
21890     \dim_set:Nn \l__coffin_internal_dim
21891     { \l__coffin_offset_x_dim - \box_wd:N #1 + \box_wd:N #4 }
21892     \dim_compare:nNnT \l__coffin_internal_dim < \c_zero_dim
21893     { \tex_kern:D -\l__coffin_internal_dim }
21894   }
```

The coffin structure is reset, and the corners are cleared: only those from the two parent coffins are needed.

```
21895   \__coffin_reset_structure:N \l__coffin_aligned_coffin
21896   \prop_clear:c
21897   { \l__coffin_corners_ \__int_value:w \l__coffin_aligned_coffin _ prop }
21898   \__coffin_update_poles:N \l__coffin_aligned_coffin
```

The structures of the parent coffins are now transferred to the new coffin, which requires that the appropriate offsets are applied. That then depends on whether any shift was needed.

```
21899   \dim_compare:nNnTF \l__coffin_offset_x_dim < \c_zero_dim
21900   {
21901     \__coffin_offset_poles:Nnn #1 { -\l__coffin_offset_x_dim } { Opt }
21902     \__coffin_offset_poles:Nnn #4 { Opt } { \l__coffin_offset_y_dim }
21903     \__coffin_offset_corners:Nnn #1 { -\l__coffin_offset_x_dim } { Opt }
21904     \__coffin_offset_corners:Nnn #4 { Opt } { \l__coffin_offset_y_dim }
21905   }
21906   {
21907     \__coffin_offset_poles:Nnn #1 { Opt } { Opt }
21908     \__coffin_offset_poles:Nnn #4
21909     { \l__coffin_offset_x_dim } { \l__coffin_offset_y_dim }
21910     \__coffin_offset_corners:Nnn #1 { Opt } { Opt }
21911     \__coffin_offset_corners:Nnn #4
21912     { \l__coffin_offset_x_dim } { \l__coffin_offset_y_dim }
21913   }
```

```

21914     \__coffin_update_vertical_poles:NNN #1 #4 \l__coffin_aligned_coffin
21915     \coffin_set_eq:NN #1 \l__coffin_aligned_coffin
21916 }
21917 \cs_generate_variant:Nn \coffin_join:NnnNnnnn { c , Nnnc , cncnc }

```

(End definition for \coffin_join:NnnNnnnn. This function is documented on page 231.)

\coffin_attach:NnnNnnnn

\coffin_attach:cnnNnnnn

\coffin_attach:Nnncnnnn

\coffin_attach:cncncnnnn

\coffin_attach_mark:NnnNnnnn

A more simple version of the above, as it simply uses the size of the first coffin for the new one. This means that the work here is rather simplified compared to the above code. The function used when marking a position is hear also as it is similar but without the structure updates.

```

21918 \cs_new_protected:Npn \coffin_attach:NnnNnnnn #1#2#3#4#5#6#7#8
21919 {
21920     \__coffin_align:NnnNnnnnN
21921     #1 {#2} {#3} #4 {#5} {#6} {#7} {#8} \l__coffin_aligned_coffin
21922     \box_set_ht:Nn \l__coffin_aligned_coffin { \box_ht:N #1 }
21923     \box_set_dp:Nn \l__coffin_aligned_coffin { \box_dp:N #1 }
21924     \box_set_wd:Nn \l__coffin_aligned_coffin { \box_wd:N #1 }
21925     \__coffin_reset_structure:N \l__coffin_aligned_coffin
21926     \prop_set_eq:cc
21927     { \l__coffin_corners_ \__int_value:w \l__coffin_aligned_coffin _prop }
21928     { \l__coffin_corners_ \__int_value:w #1 _prop }
21929     \__coffin_update_poles:N \l__coffin_aligned_coffin
21930     \__coffin_offset_poles:Nnn #1 { Opt } { Opt }
21931     \__coffin_offset_poles:Nnn #4
21932     { \l__coffin_offset_x_dim } { \l__coffin_offset_y_dim }
21933     \__coffin_update_vertical_poles:NNN #1 #4 \l__coffin_aligned_coffin
21934     \coffin_set_eq:NN #1 \l__coffin_aligned_coffin
21935 }
21936 \cs_new_protected:Npn \coffin_attach_mark:NnnNnnnn #1#2#3#4#5#6#7#8
21937 {
21938     \__coffin_align:NnnNnnnnN
21939     #1 {#2} {#3} #4 {#5} {#6} {#7} {#8} \l__coffin_aligned_coffin
21940     \box_set_ht:Nn \l__coffin_aligned_coffin { \box_ht:N #1 }
21941     \box_set_dp:Nn \l__coffin_aligned_coffin { \box_dp:N #1 }
21942     \box_set_wd:Nn \l__coffin_aligned_coffin { \box_wd:N #1 }
21943     \box_set_eq:NN #1 \l__coffin_aligned_coffin
21944 }
21945 \cs_generate_variant:Nn \coffin_attach:NnnNnnnn { c , Nnnc , cncnc }

```

(End definition for \coffin_attach:NnnNnnnn and \coffin_attach_mark:NnnNnnnn. These functions are documented on page 230.)

__coffin_align:NnnNnnnnN

The internal function aligns the two coffins into a third one, but performs no corrections on the resulting coffin poles. The process begins by finding the points of intersection for the poles for each of the input coffins. Those for the first coffin are worked out after those for the second coffin, as this allows the ‘primed’ storage area to be used for the second coffin. The ‘real’ box offsets are then calculated, before using these to re-box the input coffins. The default poles are then set up, but the final result depends on how the bounding box is being handled.

```

21946 \cs_new_protected:Npn \__coffin_align:NnnNnnnnN #1#2#3#4#5#6#7#8#9
21947 {
21948     \__coffin_calculate_intersection:Nnn #4 {#5} {#6}
21949     \dim_set:Nn \l__coffin_x_prime_dim { \l__coffin_x_dim }

```

```

21950 \dim_set:Nn \l__coffin_y_prime_dim { \l__coffin_y_dim }
21951 \__coffin_calculate_intersection:Nnn #1 {#2} {#3}
21952 \dim_set:Nn \l__coffin_offset_x_dim
21953 { \l__coffin_x_dim - \l__coffin_x_prime_dim + #7 }
21954 \dim_set:Nn \l__coffin_offset_y_dim
21955 { \l__coffin_y_dim - \l__coffin_y_prime_dim + #8 }
21956 \hbox_set:Nn \l__coffin_aligned_internal_coffin
21957 {
21958   \box_use:N #1
21959   \tex_kern:D -\box_wd:N #1
21960   \tex_kern:D \l__coffin_offset_x_dim
21961   \box_move_up:nn { \l__coffin_offset_y_dim } { \box_use:N #4 }
21962 }
21963 \coffin_set_eq:NN #9 \l__coffin_aligned_internal_coffin
21964 }

```

(End definition for __coffin_align:NnnNnnnnN.)

__coffin_offset_poles:Nnn
 __coffin_offset_pole:Nnnnnnn

Transferring structures from one coffin to another requires that the positions are updated by the offset between the two coffins. This is done by mapping to the property list of the source coffins, moving as appropriate and saving to the new coffin data structures. The test for a - means that the structures from the parent coffins are uniquely labelled and do not depend on the order of alignment. The pay off for this is that - should not be used in coffin pole or handle names, and that multiple alignments do not result in a whole set of values.

```

21965 \cs_new_protected:Npn \__coffin_offset_poles:Nnn #1#2#3
21966 {
21967   \prop_map_inline:cn { l__coffin_poles_ \__int_value:w #1 _prop }
21968   { \__coffin_offset_pole:Nnnnnnn #1 {##1} ##2 {#2} {#3} }
21969 }
21970 \cs_new_protected:Npn \__coffin_offset_pole:Nnnnnnn #1#2#3#4#5#6#7#8
21971 {
21972   \dim_set:Nn \l__coffin_x_dim { #3 + #7 }
21973   \dim_set:Nn \l__coffin_y_dim { #4 + #8 }
21974   \tl_if_in:nnTF {#2} { - }
21975   { \tl_set:Nn \l__coffin_internal_tl { {#2} } }
21976   { \tl_set:Nn \l__coffin_internal_tl { { #1 - #2 } } }
21977   \exp_last_unbraced:NNo \__coffin_set_pole:Nnx \l__coffin_aligned_coffin
21978   { \l__coffin_internal_tl }
21979   {
21980     { \dim_use:N \l__coffin_x_dim } { \dim_use:N \l__coffin_y_dim }
21981     {#5} {#6}
21982   }
21983 }

```

(End definition for __coffin_offset_poles:Nnn and __coffin_offset_pole:Nnnnnnn.)

__coffin_offset_corners:Nnn
 __coffin_offset_corner:Nnnnn

Saving the offset corners of a coffin is very similar, except that there is no need to worry about naming: every corner can be saved here as order is unimportant.

```

21984 \cs_new_protected:Npn \__coffin_offset_corners:Nnn #1#2#3
21985 {
21986   \prop_map_inline:cn { l__coffin_corners_ \__int_value:w #1 _prop }
21987   { \__coffin_offset_corner:Nnnnn #1 {##1} ##2 {#2} {#3} }
21988 }

```

```

21989 \cs_new_protected:Npn \__coffin_offset_corner:Nnnnn #1#2#3#4#5#6
21990 {
21991   \prop_put:cnx
21992   { l__coffin_corners_ \__int_value:w \l__coffin_aligned_coffin _prop }
21993   { #1 - #2 }
21994   {
21995     { \dim_eval:n { #3 + #5 } }
21996     { \dim_eval:n { #4 + #6 } }
21997   }
21998 }

```

(End definition for __coffin_offset_corners:Nnn and __coffin_offset_corner:Nnnnn.)

```

\__coffin_update_vertical_poles:NNN
\__coffin_update_T:nnnnnnnnN
\__coffin_update_B:nnnnnnnnN

```

The T and B poles need to be recalculated after alignment. These functions find the larger absolute value for the poles, but this is of course only logical when the poles are horizontal.

```

21999 \cs_new_protected:Npn \__coffin_update_vertical_poles:NNN #1#2#3
22000 {
22001   \__coffin_get_pole:NnN #3 { #1 -T } \l__coffin_pole_a_tl
22002   \__coffin_get_pole:NnN #3 { #2 -T } \l__coffin_pole_b_tl
22003   \exp_last_two_unbraced:Noo \__coffin_update_T:nnnnnnnnN
22004   \l__coffin_pole_a_tl \l__coffin_pole_b_tl #3
22005   \__coffin_get_pole:NnN #3 { #1 -B } \l__coffin_pole_a_tl
22006   \__coffin_get_pole:NnN #3 { #2 -B } \l__coffin_pole_b_tl
22007   \exp_last_two_unbraced:Noo \__coffin_update_B:nnnnnnnnN
22008   \l__coffin_pole_a_tl \l__coffin_pole_b_tl #3
22009 }
22010 \cs_new_protected:Npn \__coffin_update_T:nnnnnnnnN #1#2#3#4#5#6#7#8#9
22011 {
22012   \dim_compare:nNnTF {#2} < {#6}
22013   {
22014     \__coffin_set_pole:Nnx #9 { T }
22015     { { Opt } {#6} { 1000pt } { Opt } }
22016   }
22017   {
22018     \__coffin_set_pole:Nnx #9 { T }
22019     { { Opt } {#2} { 1000pt } { Opt } }
22020   }
22021 }
22022 \cs_new_protected:Npn \__coffin_update_B:nnnnnnnnN #1#2#3#4#5#6#7#8#9
22023 {
22024   \dim_compare:nNnTF {#2} < {#6}
22025   {
22026     \__coffin_set_pole:Nnx #9 { B }
22027     { { Opt } {#2} { 1000pt } { Opt } }
22028   }
22029   {
22030     \__coffin_set_pole:Nnx #9 { B }
22031     { { Opt } {#6} { 1000pt } { Opt } }
22032   }
22033 }

```

(End definition for __coffin_update_vertical_poles:NNN, __coffin_update_T:nnnnnnnnN, and __coffin_update_B:nnnnnnnnN.)

`\coffin_typeset:Nnnnn` Typesetting a coffin means aligning it with the current position, which is done using a coffin with no content at all. As well as aligning to the empty coffin, there is also a need to leave vertical mode, if necessary.

```

22034 \cs_new_protected:Npn \coffin_typeset:Nnnnn #1#2#3#4#5
22035 {
22036   \mode_leave_vertical:
22037   \__coffin_align:NnnNnnnnN \c_empty_coffin { H } { l }
22038   #1 {#2} {#3} {#4} {#5} \l__coffin_aligned_coffin
22039   \box_use_drop:N \l__coffin_aligned_coffin
22040 }
22041 \cs_generate_variant:Nn \coffin_typeset:Nnnnn { c }

```

(End definition for `\coffin_typeset:Nnnnn`. This function is documented on page 231.)

38.7 Coffin diagnostics

`\l__coffin_display_coffin` Used for printing coffins with data structures attached.

```

\l__coffin_display_coord_coffin 22042 \coffin_new:N \l__coffin_display_coffin
\l__coffin_display_pole_coffin 22043 \coffin_new:N \l__coffin_display_coord_coffin
22044 \coffin_new:N \l__coffin_display_pole_coffin

```

(End definition for `\l__coffin_display_coffin`, `\l__coffin_display_coord_coffin`, and `\l__coffin_display_pole_coffin`.)

`\l__coffin_display_handles_prop` This property list is used to print coffin handles at suitable positions. The offsets are expressed as multiples of the basic offset value, which therefore acts as a scale-factor.

```

22045 \prop_new:N \l__coffin_display_handles_prop
22046 \prop_put:Nnn \l__coffin_display_handles_prop { tl }
22047 { { b } { r } { -1 } { 1 } }
22048 \prop_put:Nnn \l__coffin_display_handles_prop { thc }
22049 { { b } { hc } { 0 } { 1 } }
22050 \prop_put:Nnn \l__coffin_display_handles_prop { tr }
22051 { { b } { l } { 1 } { 1 } }
22052 \prop_put:Nnn \l__coffin_display_handles_prop { vcl }
22053 { { vc } { r } { -1 } { 0 } }
22054 \prop_put:Nnn \l__coffin_display_handles_prop { vhc }
22055 { { vc } { hc } { 0 } { 0 } }
22056 \prop_put:Nnn \l__coffin_display_handles_prop { vcr }
22057 { { vc } { l } { 1 } { 0 } }
22058 \prop_put:Nnn \l__coffin_display_handles_prop { bl }
22059 { { t } { r } { -1 } { -1 } }
22060 \prop_put:Nnn \l__coffin_display_handles_prop { bhc }
22061 { { t } { hc } { 0 } { -1 } }
22062 \prop_put:Nnn \l__coffin_display_handles_prop { br }
22063 { { t } { l } { 1 } { -1 } }
22064 \prop_put:Nnn \l__coffin_display_handles_prop { Tl }
22065 { { t } { r } { -1 } { -1 } }
22066 \prop_put:Nnn \l__coffin_display_handles_prop { Thc }
22067 { { t } { hc } { 0 } { -1 } }
22068 \prop_put:Nnn \l__coffin_display_handles_prop { Tr }
22069 { { t } { l } { 1 } { -1 } }
22070 \prop_put:Nnn \l__coffin_display_handles_prop { Hl }
22071 { { vc } { r } { -1 } { 1 } }
22072 \prop_put:Nnn \l__coffin_display_handles_prop { Hhc }

```

```

22073 { { vc } { hc } { 0 } { 1 } }
22074 \prop_put:Nnn \l__coffin_display_handles_prop { Hr }
22075 { { vc } { 1 } { 1 } { 1 } }
22076 \prop_put:Nnn \l__coffin_display_handles_prop { Bl }
22077 { { b } { r } { -1 } { -1 } }
22078 \prop_put:Nnn \l__coffin_display_handles_prop { Bhc }
22079 { { b } { hc } { 0 } { -1 } }
22080 \prop_put:Nnn \l__coffin_display_handles_prop { Br }
22081 { { b } { 1 } { 1 } { -1 } }

```

(End definition for `\l__coffin_display_handles_prop`.)

`\l__coffin_display_offset_dim` The standard offset for the label from the handle position when displaying handles.

```

22082 \dim_new:N \l__coffin_display_offset_dim
22083 \dim_set:Nn \l__coffin_display_offset_dim { 2pt }

```

(End definition for `\l__coffin_display_offset_dim`.)

`\l__coffin_display_x_dim` As the intersections of poles have to be calculated to find which ones to print, there is
`\l__coffin_display_y_dim` a need to avoid repetition. This is done by saving the intersection into two dedicated
values.

```

22084 \dim_new:N \l__coffin_display_x_dim
22085 \dim_new:N \l__coffin_display_y_dim

```

(End definition for `\l__coffin_display_x_dim` and `\l__coffin_display_y_dim`.)

`\l__coffin_display_poles_prop` A property list for printing poles: various things need to be deleted from this to get a
“nice” output.

```

22086 \prop_new:N \l__coffin_display_poles_prop

```

(End definition for `\l__coffin_display_poles_prop`.)

`\l__coffin_display_font_tl` Stores the settings used to print coffin data: this keeps things flexible.

```

22087 \tl_new:N \l__coffin_display_font_tl
22088 {*\initex}
22089 \tl_set:Nn \l__coffin_display_font_tl { } % TODO
22090 \</initex>
22091 {*\package}
22092 \tl_set:Nn \l__coffin_display_font_tl { \sfamily \tiny }
22093 \</package>

```

(End definition for `\l__coffin_display_font_tl`.)

`\coffin_mark_handle:Nnnn` Marking a single handle is relatively easy. The standard attachment function is used,
`\coffin_mark_handle:cnmn` meaning that there are two calculations for the location. However, this is likely to be
`__coffin_mark_handle_aux:nnnnNnn` okay given the load expected. Contrast with the more optimised version for showing all
handles which comes next.

```

22094 \cs_new_protected:Npn \coffin_mark_handle:Nnnn #1#2#3#4
22095 {
22096   \hcoffin_set:Nn \l__coffin_display_pole_coffin
22097   {
22098     {*\initex}
22099     \hbox:n { \tex_vrule:D width 1pt height 1pt \scan_stop: } % TODO
22100     \</initex>
22101     {*\package}

```

```

22102         \color {#4}
22103         \rule { 1pt } { 1pt }
22104     \end{package}
22105 }
22106 \coffin_attach_mark:NnnNnnnn #1 {#2} {#3}
22107 \l__coffin_display_pole_coffin { hc } { vc } { Opt } { Opt }
22108 \hcoffin_set:Nn \l__coffin_display_coord_coffin
22109 {
22110 \*initex
22111 % TODO
22112 \end{initex}
22113 \end{package}
22114 \color {#4}
22115 \end{package}
22116 \l__coffin_display_font_tl
22117 ( \tl_to_str:n { #2 , #3 } )
22118 }
22119 \prop_get:NnN \l__coffin_display_handles_prop
22120 { #2 #3 } \l__coffin_internal_tl
22121 \quark_if_no_value:NTF \l__coffin_internal_tl
22122 {
22123     \prop_get:NnN \l__coffin_display_handles_prop
22124     { #3 #2 } \l__coffin_internal_tl
22125     \quark_if_no_value:NTF \l__coffin_internal_tl
22126     {
22127         \coffin_attach_mark:NnnNnnnn #1 {#2} {#3}
22128         \l__coffin_display_coord_coffin { l } { vc }
22129         { 1pt } { Opt }
22130     }
22131     {
22132         \exp_last_unbraced:No \__coffin_mark_handle_aux:nnnnNnn
22133         \l__coffin_internal_tl #1 {#2} {#3}
22134     }
22135 }
22136 {
22137     \exp_last_unbraced:No \__coffin_mark_handle_aux:nnnnNnn
22138     \l__coffin_internal_tl #1 {#2} {#3}
22139 }
22140 }
22141 \cs_new_protected:Npn \__coffin_mark_handle_aux:nnnnNnn #1#2#3#4#5#6#7
22142 {
22143     \coffin_attach_mark:NnnNnnnn #5 {#6} {#7}
22144     \l__coffin_display_coord_coffin {#1} {#2}
22145     { #3 \l__coffin_display_offset_dim }
22146     { #4 \l__coffin_display_offset_dim }
22147 }
22148 \cs_generate_variant:Nn \coffin_mark_handle:Nnnn { c }

```

(End definition for `\coffin_mark_handle:Nnnn` and `__coffin_mark_handle_aux:nnnnNnn`. This function is documented on page 232.)

`\coffin_display_handles:Nn`
`\coffin_display_handles:cn`
`__coffin_display_handles_aux:nnnnnn`
`__coffin_display_handles_aux:nnnn`
`__coffin_display_attach:Nnnnn`

Printing the poles starts by removing any duplicates, for which the H poles is used as the definitive version for the baseline and bottom. Two loops are then used to find the combinations of handles for all of these poles. This is done such that poles are removed

during the loops to avoid duplication.

```

22149 \cs_new_protected:Npn \coffin_display_handles:Nn #1#2
22150 {
22151   \hcoffin_set:Nn \l__coffin_display_pole_coffin
22152   {
22153     \*initex
22154     \hbox:n { \tex_vrule:D width 1pt height 1pt \scan_stop: } % TODO
22155   }
22156   \*package
22157   \color {#2}
22158   \rule { 1pt } { 1pt }
22159 \*package
22160 }
22161 \prop_set_eq:Nc \l__coffin_display_poles_prop
22162 { \l__coffin_poles_ \__int_value:w #1 _prop }
22163 \__coffin_get_pole:NnN #1 { H } \l__coffin_pole_a_tl
22164 \__coffin_get_pole:NnN #1 { T } \l__coffin_pole_b_tl
22165 \tl_if_eq:NNT \l__coffin_pole_a_tl \l__coffin_pole_b_tl
22166 { \prop_remove:Nn \l__coffin_display_poles_prop { T } }
22167 \__coffin_get_pole:NnN #1 { B } \l__coffin_pole_b_tl
22168 \tl_if_eq:NNT \l__coffin_pole_a_tl \l__coffin_pole_b_tl
22169 { \prop_remove:Nn \l__coffin_display_poles_prop { B } }
22170 \coffin_set_eq:NN \l__coffin_display_coffin #1
22171 \prop_map_inline:Nn \l__coffin_display_poles_prop
22172 {
22173   \prop_remove:Nn \l__coffin_display_poles_prop {##1}
22174   \__coffin_display_handles_aux:nnnnnn {##1} ##2 {#2}
22175 }
22176 \box_use_drop:N \l__coffin_display_coffin
22177 }

```

For each pole there is a check for an intersection, which here does not give an error if none is found. The successful values are stored and used to align the pole coffin with the main coffin for output. The positions are recovered from the preset list if available.

```

22178 \cs_new_protected:Npn \__coffin_display_handles_aux:nnnnnn #1#2#3#4#5#6
22179 {
22180   \prop_map_inline:Nn \l__coffin_display_poles_prop
22181   {
22182     \bool_set_false:N \l__coffin_error_bool
22183     \__coffin_calculate_intersection:nnnnnnnn {#2} {#3} {#4} {#5} ##2
22184     \bool_if:NF \l__coffin_error_bool
22185     {
22186       \dim_set:Nn \l__coffin_display_x_dim { \l__coffin_x_dim }
22187       \dim_set:Nn \l__coffin_display_y_dim { \l__coffin_y_dim }
22188       \__coffin_display_attach:Nnnnn
22189       \l__coffin_display_pole_coffin { hc } { vc }
22190       { Opt } { Opt }
22191       \hcoffin_set:Nn \l__coffin_display_coord_coffin
22192       {
22193         \*initex
22194         % TODO
22195       }
22196     }
22197     \*package
22198     \color {#6}

```



```

22198 \end{package}
22199 \l__coffin_display_font_tl
22200 ( \tl_to_str:n { #1 , ##1 } )
22201 }
22202 \prop_get:NnN \l__coffin_display_handles_prop
22203 { #1 ##1 } \l__coffin_internal_tl
22204 \quark_if_no_value:NTF \l__coffin_internal_tl
22205 {
22206   \prop_get:NnN \l__coffin_display_handles_prop
22207   { ##1 #1 } \l__coffin_internal_tl
22208   \quark_if_no_value:NTF \l__coffin_internal_tl
22209   {
22210     \__coffin_display_attach:Nnnnn
22211     \l__coffin_display_coord_coffin { 1 } { vc }
22212     { 1pt } { 0pt }
22213   }
22214   {
22215     \exp_last_unbraced:No
22216     \__coffin_display_handles_aux:nnnn
22217     \l__coffin_internal_tl
22218   }
22219 }
22220 {
22221   \exp_last_unbraced:No \__coffin_display_handles_aux:nnnn
22222   \l__coffin_internal_tl
22223 }
22224 }
22225 }
22226 }
22227 \cs_new_protected:Npn \__coffin_display_handles_aux:nnnn #1#2#3#4
22228 {
22229   \__coffin_display_attach:Nnnnn
22230   \l__coffin_display_coord_coffin {#1} {#2}
22231   { #3 \l__coffin_display_offset_dim }
22232   { #4 \l__coffin_display_offset_dim }
22233 }
22234 \cs_generate_variant:Nn \coffin_display_handles:Nn { c }

```

This is a dedicated version of `\coffin_attach:NnnNnnnn` with a hard-wired first coffin. As the intersection is already known and stored for the display coffin the code simply uses it directly, with no calculation.

```

22235 \cs_new_protected:Npn \__coffin_display_attach:Nnnnn #1#2#3#4#5
22236 {
22237   \__coffin_calculate_intersection:Nnn #1 {#2} {#3}
22238   \dim_set:Nn \l__coffin_x_prime_dim { \l__coffin_x_dim }
22239   \dim_set:Nn \l__coffin_y_prime_dim { \l__coffin_y_dim }
22240   \dim_set:Nn \l__coffin_offset_x_dim
22241   { \l__coffin_display_x_dim - \l__coffin_x_prime_dim + #4 }
22242   \dim_set:Nn \l__coffin_offset_y_dim
22243   { \l__coffin_display_y_dim - \l__coffin_y_prime_dim + #5 }
22244   \hbox_set:Nn \l__coffin_aligned_coffin
22245   {
22246     \box_use:N \l__coffin_display_coffin
22247     \tex_kern:D -\box_wd:N \l__coffin_display_coffin

```

```

22248     \tex_kern:D \l__coffin_offset_x_dim
22249     \box_move_up:nn { \l__coffin_offset_y_dim } { \box_use:N #1 }
22250   }
22251   \box_set_ht:Nn \l__coffin_aligned_coffin
22252     { \box_ht:N \l__coffin_display_coffin }
22253   \box_set_dp:Nn \l__coffin_aligned_coffin
22254     { \box_dp:N \l__coffin_display_coffin }
22255   \box_set_wd:Nn \l__coffin_aligned_coffin
22256     { \box_wd:N \l__coffin_display_coffin }
22257   \box_set_eq:NN \l__coffin_display_coffin \l__coffin_aligned_coffin
22258 }

```

(End definition for `\coffin_display_handles:Nn` and others. This function is documented on page 231.)

`\coffin_show_structure:N`

`\coffin_show_structure:c`

`\coffin_log_structure:N`

`\coffin_log_structure:c`

`__coffin_show_structure:NN`

For showing the various internal structures attached to a coffin in a way that keeps things relatively readable. If there is no apparent structure then the code complains.

```

22259 \cs_new_protected:Npn \coffin_show_structure:N
22260   { \__coffin_show_structure:NN \msg_show:nnxxxx }
22261 \cs_generate_variant:Nn \coffin_show_structure:N { c }
22262 \cs_new_protected:Npn \coffin_log_structure:N
22263   { \__coffin_show_structure:NN \msg_log:nnxxxx }
22264 \cs_generate_variant:Nn \coffin_log_structure:N { c }
22265 \cs_new_protected:Npn \__coffin_show_structure:NN #1#2
22266   {
22267     \__coffin_if_exist:NT #2
22268     {
22269       #1 { LaTeX / kernel } { show-coffin }
22270       { \token_to_str:N #2 }
22271       {
22272         \iow_newline: >~ ht ~~~ \dim_eval:n { \coffin_ht:N #2 }
22273         \iow_newline: >~ dp ~~~ \dim_eval:n { \coffin_dp:N #2 }
22274         \iow_newline: >~ wd ~~~ \dim_eval:n { \coffin_wd:N #2 }
22275       }
22276       {
22277         \prop_map_function:cN
22278           { l__coffin_poles_ \int_eval:n {#2} _prop }
22279         \msg_show_item_unbraced:nn
22280       }
22281     } }
22282   }
22283 }

```

(End definition for `\coffin_show_structure:N`, `\coffin_log_structure:N`, and `__coffin_show_structure:NN`. These functions are documented on page 232.)

38.8 Messages

```

22284 \__msg_kernel_new:nnnn { kernel } { no-pole-intersection }
22285   { No~intersection~between~coffin~poles. }
22286   {
22287     \c_msg_coding_error_text_tl
22288     LaTeX~was~asked~to~find~the~intersection~between~two~poles,~
22289     but~they~do~not~have~a~unique~meeting~point:~
22290     the~value~(0~pt,~0~pt)~will~be~used.

```

```

22291 }
22292 \__msg_kernel_new:nnnn { kernel } { unknown-coffin }
22293 { Unknown~coffin~'#1'. }
22294 { The~coffin~'#1'~was~never~defined. }
22295 \__msg_kernel_new:nnnn { kernel } { unknown-coffin-pole }
22296 { Pole~'#1'~unknown~for~coffin~'#2'. }
22297 {
22298   \c__msg_coding_error_text_tl
22299   LaTeX~was~asked~to~find~a~typesetting~pole~for~a~coffin,~
22300   but~either~the~coffin~does~not~exist~or~the~pole~name~is~wrong.
22301 }
22302 \__msg_kernel_new:nnn { kernel } { show-coffin }
22303 {
22304   Size~of~coffin~#1 : #2 \\
22305   Poles~of~coffin~#1 : #3 .
22306 }
22307 </initex | package>

```

39 l3color Implementation

```

22308 <*initex | package>

```

\color_group_begin: Grouping for color is almost the same as using the basic `\group_begin:` and `\group_end:` functions. However, in vertical mode the end-of-group needs a `\par`, which in horizontal mode does nothing.

```

22309 \cs_new_eq:NN \color_group_begin: \group_begin:
22310 \cs_new_protected:Npn \color_group_end:
22311 {
22312   \par
22313   \group_end:
22314 }

```

(End definition for `\color_group_begin:` and `\color_group_end:`. These functions are documented on page 233.)

\color_ensure_current: A driver-independent wrapper for setting the foreground color to the current color “now”.

```

22315 \cs_new_protected:Npn \color_ensure_current:
22316 {
22317   <*package>
22318   \__driver_color_pickup:N \l__color_current_tl
22319   </package>
22320   \__driver_color_select:V \l__color_current_tl
22321   \group_insert_after:N \__driver_color_reset:
22322 }

```

(End definition for `\color_ensure_current:`. This function is documented on page 233.)

\l__color_current_tl As the setting data is used only for specials, and those are always space-separated, it makes most sense to hold the internal information in that form. Any splitting is done by a delimited function but often the entire `tl` can be used as-is: see `l3drivers.dtx`.

```

22323 \tl_new:N \l__color_current_tl
22324 \tl_set:Nn \l__color_current_tl { gray~0 }

```

(End definition for `\l__color_current_tl`.)

```

22325 </initex | package>

```

40 l3sys implementation

22326 $\langle *initex | package \rangle$

40.1 The name of the job

$\backslash c_sys_jobname_str$ Inherited from the L^AT_EX3 name for the primitive: this needs to actually contain the text of the job name rather than the name of the primitive, of course.

```
22327  $\langle *initex \rangle$ 
22328  $\backslash tex\_everyjob:D \exp\_after:wN$ 
22329 {
22330    $\backslash tex\_the:D \backslash tex\_everyjob:D$ 
22331    $\backslash str\_const:Nx \backslash c\_sys\_jobname\_str \{ \backslash tex\_jobname:D \}$ 
22332 }
22333  $\langle /initex \rangle$ 
22334  $\langle *package \rangle$ 
22335  $\backslash str\_const:Nx \backslash c\_sys\_jobname\_str \{ \backslash tex\_jobname:D \}$ 
22336  $\langle /package \rangle$ 
```

(End definition for $\backslash c_sys_jobname_str$. This variable is documented on page 235.)

40.2 Time and date

$\backslash c_sys_minute_int$ Copies of the information provided by T_EX
 $\backslash c_sys_hour_int$ 22337 $\backslash int_const:Nn \backslash c_sys_minute_int$
 $\backslash c_sys_day_int$ 22338 { $\backslash int_mod:nn \{ \backslash tex_time:D \} \{ 60 \} \}$
 $\backslash c_sys_month_int$ 22339 $\backslash int_const:Nn \backslash c_sys_hour_int$
 $\backslash c_sys_year_int$ 22340 { $\backslash int_div_truncate:nn \{ \backslash tex_time:D \} \{ 60 \} \}$
22341 $\backslash int_const:Nn \backslash c_sys_day_int \{ \backslash tex_day:D \}$
22342 $\backslash int_const:Nn \backslash c_sys_month_int \{ \backslash tex_month:D \}$
22343 $\backslash int_const:Nn \backslash c_sys_year_int \{ \backslash tex_year:D \}$

(End definition for $\backslash c_sys_minute_int$ and others. These variables are documented on page 235.)

40.3 Detecting the engine

$\backslash sys_if_engine_luatex_p:$ Set up the engine tests on the basis exactly one test should be true. Mainly a case of
 $\backslash sys_if_engine_luatex:TF$ looking for the appropriate marker primitive. For upT_EX, there is a complexity in that
 $\backslash sys_if_engine_pdftex_p:$ setting $-kanji_internal=sjis$ or $-kanji_internal=euc$ effective makes it more like
 $\backslash sys_if_engine_pdftex:TF$ pT_EX. In those cases we therefore report pT_EX rather than upT_EX.

```
\sys_if_engine_ptex_p: 22344  $\backslash clist\_map\_inline:nn \{ lua , pdf , p , up , xe \}$ 
\sys_if_engine_ptex:TF 22345 {
\sys_if_engine_uptex_p: 22346    $\backslash cs\_new\_eq:cN \{ sys\_if\_engine\_ \#1 tex:T \} \backslash use\_none:n$ 
\sys_if_engine_uptex:TF 22347    $\backslash cs\_new\_eq:cN \{ sys\_if\_engine\_ \#1 tex:F \} \backslash use:n$ 
\sys_if_engine_xetex_p: 22348    $\backslash cs\_new\_eq:cN \{ sys\_if\_engine\_ \#1 tex:TF \} \backslash use\_ii:nn$ 
\sys_if_engine_xetex:TF 22349    $\backslash cs\_new\_eq:cN \{ sys\_if\_engine\_ \#1 tex:p: \} \backslash c\_false\_bool$ 
\c_sys_engine_str      22350 }
22351  $\backslash cs\_if\_exist:NT \backslash luatex\_luatexversion:D$ 
22352 {
22353    $\backslash cs\_gset\_eq:NN \backslash sys\_if\_engine\_luatex:T \backslash use:n$ 
22354    $\backslash cs\_gset\_eq:NN \backslash sys\_if\_engine\_luatex:F \backslash use\_none:n$ 
22355    $\backslash cs\_gset\_eq:NN \backslash sys\_if\_engine\_luatex:TF \backslash use\_i:nn$ 
22356    $\backslash cs\_gset\_eq:NN \backslash sys\_if\_engine\_luatex:p: \backslash c\_true\_bool$ 
22357    $\backslash str\_const:Nn \backslash c\_sys\_engine\_str \{ luatex \}$ 
```

```

22358 }
22359 \cs_if_exist:NT \pdfTeX_pdftexversion:D
22360 {
22361   \cs_gset_eq:NN \sys_if_engine_pdftex:T \use:n
22362   \cs_gset_eq:NN \sys_if_engine_pdftex:F \use_none:n
22363   \cs_gset_eq:NN \sys_if_engine_pdftex:TF \use_i:nn
22364   \cs_gset_eq:NN \sys_if_engine_pdftex_p: \c_true_bool
22365   \str_const:Nn \c_sys_engine_str { pdftex }
22366 }
22367 \cs_if_exist:NT \ptex_kanjiskip:D
22368 {
22369   \bool_lazy_and:nnTF
22370   { \cs_if_exist_p:N \uptex_disablecjktoken:D }
22371   { \int_compare_p:nNn { \ptex_jis:D "2121 } = { "3000 } }
22372   {
22373     \cs_gset_eq:NN \sys_if_engine_uptex:T \use:n
22374     \cs_gset_eq:NN \sys_if_engine_uptex:F \use_none:n
22375     \cs_gset_eq:NN \sys_if_engine_uptex:TF \use_i:nn
22376     \cs_gset_eq:NN \sys_if_engine_uptex_p: \c_true_bool
22377     \str_const:Nn \c_sys_engine_str { uptex }
22378   }
22379   {
22380     \cs_gset_eq:NN \sys_if_engine_ptex:T \use:n
22381     \cs_gset_eq:NN \sys_if_engine_ptex:F \use_none:n
22382     \cs_gset_eq:NN \sys_if_engine_ptex:TF \use_i:nn
22383     \cs_gset_eq:NN \sys_if_engine_ptex_p: \c_true_bool
22384     \str_const:Nn \c_sys_engine_str { ptex }
22385   }
22386 }
22387 \cs_if_exist:NT \xetex_XeTeXversion:D
22388 {
22389   \cs_gset_eq:NN \sys_if_engine_xetex:T \use:n
22390   \cs_gset_eq:NN \sys_if_engine_xetex:F \use_none:n
22391   \cs_gset_eq:NN \sys_if_engine_xetex:TF \use_i:nn
22392   \cs_gset_eq:NN \sys_if_engine_xetex_p: \c_true_bool
22393   \str_const:Nn \c_sys_engine_str { xetex }
22394 }

```

(End definition for `\sys_if_engine luatex:TF` and others. These functions are documented on page 235.)

40.4 Detecting the output

`\sys_if_output_dvi_p:` This is a simple enough concept: the two views here are complementary.

```

\sys_if_output_dvi:TF 22395 \int_compare:nNnTF
\sys_if_output_pdf_p: 22396 { \cs_if_exist_use:NF \pdfTeX_pdfoutput:D { 0 } } > { 0 }
\sys_if_output_pdf:TF 22397 {
  \c_sys_output_str 22398 \cs_new_eq:NN \sys_if_output_dvi:T \use_none:n
  22399 \cs_new_eq:NN \sys_if_output_dvi:F \use:n
  2400 \cs_new_eq:NN \sys_if_output_dvi:TF \use_ii:nn
  2401 \cs_new_eq:NN \sys_if_output_dvi_p: \c_false_bool
  2402 \cs_new_eq:NN \sys_if_output_pdf:T \use:n
  2403 \cs_new_eq:NN \sys_if_output_pdf:F \use_none:n
  2404 \cs_new_eq:NN \sys_if_output_pdf:TF \use_i:nn

```

```

22405 \cs_new_eq:NN \sys_if_output_pdf_p: \c_true_bool
22406 \str_const:Nn \c_sys_output_str { pdf }
22407 }
22408 {
22409 \cs_new_eq:NN \sys_if_output_dvi:T \use:n
22410 \cs_new_eq:NN \sys_if_output_dvi:F \use_none:n
22411 \cs_new_eq:NN \sys_if_output_dvi:TF \use_i:nn
22412 \cs_new_eq:NN \sys_if_output_dvi_p: \c_true_bool
22413 \cs_new_eq:NN \sys_if_output_pdf:T \use_none:n
22414 \cs_new_eq:NN \sys_if_output_pdf:F \use:n
22415 \cs_new_eq:NN \sys_if_output_pdf:TF \use_ii:nn
22416 \cs_new_eq:NN \sys_if_output_pdf_p: \c_false_bool
22417 \str_const:Nn \c_sys_output_str { dvi }
22418 }

```

(End definition for `\sys_if_output_dvi:TF`, `\sys_if_output_pdf:TF`, and `\c_sys_output_str`. These functions are documented on page [236](#).)

```

22419 </initex | package>

```

41 l3deprecation implementation

```

22420 <*initex | package>
22421 <@@=deprecation>

```

`__deprecation_error:Nnn` The `\outer` definition here ensures the command cannot appear in an argument. Use this auxiliary on all commands that have been removed since 2015.

```

22422 \cs_new_protected:Npn \__deprecation_error:Nnn #1#2#3
22423 {
22424 \etex_protected:D \tex_outer:D \tex_edef:D #1
22425 {
22426 \exp_not:N \__msg_kernel_expandable_error:nnnnn
22427 { kernel } { deprecated-command }
22428 { \tl_to_str:n {#3} } { \token_to_str:N #1 } { \tl_to_str:n {#2} }
22429 \exp_not:N \__msg_kernel_error:nnxxx
22430 { kernel } { deprecated-command }
22431 { \tl_to_str:n {#3} } { \token_to_str:N #1 } { \tl_to_str:n {#2} }
22432 }
22433 }
22434 \__deprecation_error:Nnn \c_job_name_tl { \c_sys_jobname_str } { 2017-01-01 }
22435 \__deprecation_error:Nnn \dim_case:nnn { \dim_case:nnF } { 2015-07-14 }
22436 \__deprecation_error:Nnn \int_case:nnn { \int_case:nnF } { 2015-07-14 }
22437 \__deprecation_error:Nnn \int_from_binary:n { \int_from_bin:n } { 2016-01-05 }
22438 \__deprecation_error:Nnn \int_from_hexadecimal:n { \int_from_hex:n } { 2016-01-05 }
22439 \__deprecation_error:Nnn \int_from_octal:n { \int_from_oct:n } { 2016-01-05 }
22440 \__deprecation_error:Nnn \int_to_binary:n { \int_to_bin:n } { 2016-01-05 }
22441 \__deprecation_error:Nnn \int_to_hexadecimal:n { \int_to_hex:n } { 2016-01-05 }
22442 \__deprecation_error:Nnn \int_to_octal:n { \int_to_oct:n } { 2016-01-05 }
22443 \__deprecation_error:Nnn \luatex_if_engine_p: { \sys_if_engine luatex_p: } { 2017-01-01 }
22444 \__deprecation_error:Nnn \luatex_if_engine:F { \sys_if_engine luatex:F } { 2017-01-01 }
22445 \__deprecation_error:Nnn \luatex_if_engine:T { \sys_if_engine luatex:T } { 2017-01-01 }
22446 \__deprecation_error:Nnn \luatex_if_engine:TF { \sys_if_engine luatex:TF } { 2017-01-01 }
22447 \__deprecation_error:Nnn \pdfTeX_if_engine_p: { \sys_if_engine pdfTeX_p: } { 2017-01-01 }
22448 \__deprecation_error:Nnn \pdfTeX_if_engine:F { \sys_if_engine pdfTeX:F } { 2017-01-01 }

```

```

22449 \__deprecation_error:Nnn \pdfTeX_if_engine:T { \sys_if_engine_pdfTeX:T } { 2017-01-01 }
22450 \__deprecation_error:Nnn \pdfTeX_if_engine:TF { \sys_if_engine_pdfTeX:TF } { 2017-01-01 }
22451 \__deprecation_error:Nnn \prop_get:cn { \prop_item:cn } { 2016-01-05 }
22452 \__deprecation_error:Nnn \prop_get:Nn { \prop_item:Nn } { 2016-01-05 }
22453 \__deprecation_error:Nnn \quark_if_recursion_tail_break:N { } { 2015-07-14 }
22454 \__deprecation_error:Nnn \quark_if_recursion_tail_break:n { } { 2015-07-14 }
22455 \__deprecation_error:Nnn \scan_align_safe_stop: { protected-commands } { 2017-01-01 }
22456 \__deprecation_error:Nnn \str_case:nnn { \str_case:nnF } { 2015-07-14 }
22457 \__deprecation_error:Nnn \str_case:onnn { \str_case:onF } { 2015-07-14 }
22458 \__deprecation_error:Nnn \str_case:x:nnn { \str_case:x:nnF } { 2015-07-14 }
22459 \__deprecation_error:Nnn \tl_case:cn { \tl_case:cnF } { 2015-07-14 }
22460 \__deprecation_error:Nnn \tl_case:Nnn { \tl_case:NnF } { 2015-07-14 }
22461 \__deprecation_error:Nnn \xetex_if_engine_p: { \sys_if_engine_xetex_p: } { 2017-01-01 }
22462 \__deprecation_error:Nnn \xetex_if_engine:F { \sys_if_engine_xetex:F } { 2017-01-01 }
22463 \__deprecation_error:Nnn \xetex_if_engine:T { \sys_if_engine_xetex:T } { 2017-01-01 }
22464 \__deprecation_error:Nnn \xetex_if_engine:TF { \sys_if_engine_xetex:TF } { 2017-01-01 }

```

(End definition for `__deprecation_error:Nnn`.)

This is left-over from `l3expan`. It cannot be done there because `l3tl` is not loaded at that time.

```

22465 \__debug:TF
22466 {
22467   \tl_gput_right:Nn \g__debug_deprecation_on_tl
22468   {
22469     \cs_set_protected:Npn \__cs_generate_variant_loop_warning:nnxxxx
22470     { \__msg_kernel_error:nnxxxx }
22471   }
22472   \tl_gput_right:Nn \g__debug_deprecation_off_tl
22473   {
22474     \cs_set_protected:Npn \__cs_generate_variant_loop_warning:nnxxxx
22475     { \__msg_kernel_warning:nnxxxx }
22476   }
22477 }
22478 { }
22479 </initex | package>

```

42 l3candidates Implementation

```
22480 <*initex | package>
```

42.1 Additions to `l3basics`

\mode_leave_vertical: The approach here is different to that used by $\text{\LaTeX} 2_{\epsilon}$ or plain \TeX , which unbox a void box to force horizontal mode. That inserts the `\everypar` tokens *before* the re-inserted unboxing tokens. The approach here uses either the `\quitvmode` primitive or the equivalent protected macro. In vertical mode, the `\indent` primitive is inserted: this will switch to horizontal mode and insert `\everypar` tokens and nothing else. Unlike the $\text{\LaTeX} 2_{\epsilon}$ version, the availability of $\epsilon\text{-TeX}$ means using a mode test can be done at for example the start of an `\halign`. The `\quitvmode` primitive essentially wraps the same code up at the engine level.

```

22481 \cs_new_protected:Npx \mode_leave_vertical:
22482 {

```

```

22483 \cs_if_exist:NTF \pdfTeX_quitvmode:D
22484 { \pdfTeX_quitvmode:D }
22485 {
22486   \exp_not:n
22487   {
22488     \if_mode_vertical:
22489       \exp_after:wN \tex_indent:D
22490     \fi:
22491   }
22492 }
22493 }

```

(End definition for `\mode_leave_vertical:`. This function is documented on page 239.)

42.2 Additions to `l3box`

```

22494 <@@=box>

```

42.3 Viewing part of a box

`\box_clip:N` A wrapper around the driver-dependent code.

```

\box_clip:c 22495 \cs_new_protected:Npn \box_clip:N #1
22496 { \hbox_set:Nn #1 { \_driver_box_use_clip:N #1 } }
22497 \cs_generate_variant:Nn \box_clip:N { c }

```

(End definition for `\box_clip:N`. This function is documented on page 240.)

`\box_trim:Nnnnn` Trimming from the left- and right-hand edges of the box is easy: kern the appropriate parts off each side.

```

\box_trim:cnnnn 22498 \cs_new_protected:Npn \box_trim:Nnnnn #1#2#3#4#5
22499 {
22500   \hbox_set:Nn \l__box_internal_box
22501   {
22502     \tex_kern:D - \_dim_eval:n {#2}
22503     \box_use:N #1
22504     \tex_kern:D - \_dim_eval:n {#4}
22505   }

```

For the height and depth, there is a need to watch the baseline is respected. Material always has to stay on the correct side, so trimming has to check that there is enough material to trim. First, the bottom edge. If there is enough depth, simply set the depth, or if not move down so the result is zero depth. `\box_move_down:nn` is used in both cases so the resulting box always contains a `\lower` primitive. The internal box is used here as it allows safe use of `\box_set_dp:Nn`.

```

22506   \dim_compare:nNnTF { \box_dp:N #1 } > {#3}
22507   {
22508     \hbox_set:Nn \l__box_internal_box
22509     {
22510       \box_move_down:nn \c_zero_dim
22511       { \box_use:N \l__box_internal_box }
22512     }
22513     \box_set_dp:Nn \l__box_internal_box { \box_dp:N #1 - (#3) }
22514   }
22515   {
22516     \hbox_set:Nn \l__box_internal_box

```



```

22517     {
22518         \box_move_down:nn { (#3) - \box_dp:N #1 }
22519         { \box_use:N \l__box_internal_box }
22520     }
22521     \box_set_dp:Nn \l__box_internal_box \c_zero_dim
22522 }

```

Same thing, this time from the top of the box.

```

22523     \dim_compare:nNnTF { \box_ht:N \l__box_internal_box } > {#5}
22524     {
22525         \hbox_set:Nn \l__box_internal_box
22526         {
22527             \box_move_up:nn \c_zero_dim
22528             { \box_use:N \l__box_internal_box }
22529         }
22530         \box_set_ht:Nn \l__box_internal_box
22531         { \box_ht:N \l__box_internal_box - (#5) }
22532     }
22533     {
22534         \hbox_set:Nn \l__box_internal_box
22535         {
22536             \box_move_up:nn { (#5) - \box_ht:N \l__box_internal_box }
22537             { \box_use:N \l__box_internal_box }
22538         }
22539         \box_set_ht:Nn \l__box_internal_box \c_zero_dim
22540     }
22541     \box_set_eq:NN #1 \l__box_internal_box
22542 }
22543 \cs_generate_variant:Nn \box_trim:Nnnnn { c }

```

(End definition for `\box_trim:Nnnnn`. This function is documented on page 240.)

`\box_viewport:Nnnnn`
`\box_viewport:cnnnn`

The same general logic as for the trim operation, but with absolute dimensions. As a result, there are some things to watch out for in the vertical direction.

```

22544 \cs_new_protected:Npn \box_viewport:Nnnnn #1#2#3#4#5
22545 {
22546     \hbox_set:Nn \l__box_internal_box
22547     {
22548         \tex_kern:D - \__dim_eval:n {#2}
22549         \box_use:N #1
22550         \tex_kern:D \__dim_eval:n { #4 - \box_wd:N #1 }
22551     }
22552     \dim_compare:nNnTF {#3} < \c_zero_dim
22553     {
22554         \hbox_set:Nn \l__box_internal_box
22555         {
22556             \box_move_down:nn \c_zero_dim
22557             { \box_use:N \l__box_internal_box }
22558         }
22559         \box_set_dp:Nn \l__box_internal_box { - \__dim_eval:n {#3} }
22560     }
22561     {
22562         \hbox_set:Nn \l__box_internal_box
22563         { \box_move_down:nn {#3} { \box_use:N \l__box_internal_box } }
22564         \box_set_dp:Nn \l__box_internal_box \c_zero_dim

```

```

22565     }
22566     \dim_compare:nNnTF {#5} > \c_zero_dim
22567     {
22568         \hbox_set:Nn \l__box_internal_box
22569         {
22570             \box_move_up:nn \c_zero_dim
22571             { \box_use:N \l__box_internal_box }
22572         }
22573         \box_set_ht:Nn \l__box_internal_box
22574         {
22575             (#5)
22576             \dim_compare:nNnT {#3} > \c_zero_dim
22577             { - (#3) }
22578         }
22579     }
22580     {
22581         \hbox_set:Nn \l__box_internal_box
22582         {
22583             \box_move_up:nn { - \__dim_eval:n {#5} }
22584             { \box_use:N \l__box_internal_box }
22585         }
22586         \box_set_ht:Nn \l__box_internal_box \c_zero_dim
22587     }
22588     \box_set_eq:NN #1 \l__box_internal_box
22589 }
22590 \cs_generate_variant:Nn \box_viewport:Nnnnn { c }

```

(End definition for `\box_viewport:Nnnnn`. This function is documented on page 240.)

42.4 Additions to `l3clist`

```

22591 (@@=clist)

```

`\clist_rand_item:n` The N-type function is not implemented through the n-type function for efficiency: for instance comma-list variables do not require space-trimming of their items. Even testing for emptiness of an n-type comma-list is slow, so we count items first and use that both for the emptiness test and the pseudo-random integer. Importantly, `\clist_item:Nn` and `\clist_item:nn` only evaluate their argument once.

```

22592 \cs_new:Npn \clist_rand_item:n #1
22593 { \exp_args:Nf \__clist_rand_item:nn { \clist_count:n {#1} } {#1} }
22594 \cs_new:Npn \__clist_rand_item:nn #1#2
22595 {
22596     \int_compare:nNnF {#1} = 0
22597     { \clist_item:nn {#2} { \int_rand:nn { 1 } {#1} } }
22598 }
22599 \cs_new:Npn \clist_rand_item:N #1
22600 {
22601     \clist_if_empty:NF #1
22602     { \clist_item:Nn #1 { \int_rand:nn { 1 } { \clist_count:N #1 } } }
22603 }
22604 \cs_generate_variant:Nn \clist_rand_item:N { c }

```

(End definition for `\clist_rand_item:n`, `\clist_rand_item:N`, and `__clist_rand_item:nn`. These functions are documented on page 240.)

42.5 Additions to l3coffins

22605 `<@@=coffin>`

42.6 Rotating coffins

`\l__coffin_sin_fp` Used for rotations to get the sine and cosine values.

`\l__coffin_cos_fp` 22606 `\fp_new:N \l__coffin_sin_fp`

22607 `\fp_new:N \l__coffin_cos_fp`

(End definition for \l__coffin_sin_fp and \l__coffin_cos_fp.)

`\l__coffin_bounding_prop` A property list for the bounding box of a coffin. This is only needed during the rotation, so there is just the one.

22608 `\prop_new:N \l__coffin_bounding_prop`

(End definition for \l__coffin_bounding_prop.)

`\l__coffin_bounding_shift_dim` The shift of the bounding box of a coffin from the real content.

22609 `\dim_new:N \l__coffin_bounding_shift_dim`

(End definition for \l__coffin_bounding_shift_dim.)

`\l__coffin_left_corner_dim` These are used to hold maxima for the various corner values: these thus define the minimum size of the bounding box after rotation.

`\l__coffin_right_corner_dim`

`\l__coffin_bottom_corner_dim`

22610 `\dim_new:N \l__coffin_left_corner_dim`

22611 `\dim_new:N \l__coffin_right_corner_dim`

22612 `\dim_new:N \l__coffin_bottom_corner_dim`

22613 `\dim_new:N \l__coffin_top_corner_dim`

(End definition for \l__coffin_left_corner_dim and others.)

`\coffin_rotate:Nn` Rotating a coffin requires several steps which can be conveniently run together. The sine and cosine of the angle in degrees are computed. This is then used to set `\l__coffin_sin_fp` and `\l__coffin_cos_fp`, which are carried through unchanged for the rest of the procedure.

`\coffin_rotate:cn`

22614 `\cs_new_protected:Npn \coffin_rotate:Nn #1#2`

22615 `{`

22616 `\fp_set:Nn \l__coffin_sin_fp { sind (#2) }`

22617 `\fp_set:Nn \l__coffin_cos_fp { cosd (#2) }`

The corners and poles of the coffin can now be rotated around the origin. This is best achieved using mapping functions.

22618 `\prop_map_inline:cn { l__coffin_corners_ __int_value:w #1 _prop }`

22619 `{ __coffin_rotate_corner:Nnnn #1 {##1} ##2 }`

22620 `\prop_map_inline:cn { l__coffin_poles_ __int_value:w #1 _prop }`

22621 `{ __coffin_rotate_pole:Nnnnnn #1 {##1} ##2 }`

The bounding box of the coffin needs to be rotated, and to do this the corners have to be found first. They are then rotated in the same way as the corners of the coffin material itself.

22622 `__coffin_set_bounding:N #1`

22623 `\prop_map_inline:Nn \l__coffin_bounding_prop`

22624 `{ __coffin_rotate_bounding:nnn {##1} ##2 }`

At this stage, there needs to be a calculation to find where the corners of the content and the box itself will end up.

```

22625    \__coffin_find_corner_maxima:N #1
22626    \__coffin_find_bounding_shift:
22627    \box_rotate:Nn #1 {#2}

```

The correction of the box position itself takes place here. The idea is that the bounding box for a coffin is tight up to the content, and has the reference point at the bottom-left. The x -direction is handled by moving the content by the difference in the positions of the bounding box and the content left edge. The y -direction is dealt with by moving the box down by any depth it has acquired. The internal box is used here to allow for the next step.

```

22628    \hbox_set:Nn \l__coffin_internal_box
22629    {
22630        \tex_kern:D
22631        \__dim_eval:n
22632        { \l__coffin_bounding_shift_dim - \l__coffin_left_corner_dim }
22633        \box_move_down:n { \l__coffin_bottom_corner_dim }
22634        { \box_use:N #1 }
22635    }

```

If there have been any previous rotations then the size of the bounding box will be bigger than the contents. This can be corrected easily by setting the size of the box to the height and width of the content. As this operation requires setting box dimensions and these transcend grouping, the safe way to do this is to use the internal box and to reset the result into the target box.

```

22636    \box_set_ht:Nn \l__coffin_internal_box
22637    { \l__coffin_top_corner_dim - \l__coffin_bottom_corner_dim }
22638    \box_set_dp:Nn \l__coffin_internal_box { 0 pt }
22639    \box_set_wd:Nn \l__coffin_internal_box
22640    { \l__coffin_right_corner_dim - \l__coffin_left_corner_dim }
22641    \hbox_set:Nn #1 { \box_use:N \l__coffin_internal_box }

```

The final task is to move the poles and corners such that they are back in alignment with the box reference point.

```

22642    \prop_map_inline:cn { l__coffin_corners_ \__int_value:w #1 _prop }
22643    { \__coffin_shift_corner:Nnnn #1 {##1} ##2 }
22644    \prop_map_inline:cn { l__coffin_poles_ \__int_value:w #1 _prop }
22645    { \__coffin_shift_pole:Nnnnnn #1 {##1} ##2 }
22646    }
22647    \cs_generate_variant:Nn \coffin_rotate:Nn { c }

```

(End definition for `\coffin_rotate:Nn`. This function is documented on page 241.)

`__coffin_set_bounding:N` The bounding box corners for a coffin are easy enough to find: this is the same code as for the corners of the material itself, but using a dedicated property list.

```

22648    \cs_new_protected:Npn \__coffin_set_bounding:N #1
22649    {
22650        \prop_put:Nnx \l__coffin_bounding_prop { tl }
22651        { { 0 pt } { \dim_eval:n { \box_ht:N #1 } } }
22652        \prop_put:Nnx \l__coffin_bounding_prop { tr }
22653        { { \dim_eval:n { \box_wd:N #1 } } { \dim_eval:n { \box_ht:N #1 } } }
22654        \dim_set:Nn \l__coffin_internal_dim { -\box_dp:N #1 }
22655        \prop_put:Nnx \l__coffin_bounding_prop { bl }

```

```

22656     { { 0 pt } { \dim_use:N \l__coffin_internal_dim } }
22657 \prop_put:Nnx \l__coffin_bounding_prop { br }
22658     { { \dim_eval:n { \box_wd:N #1 } } { \dim_use:N \l__coffin_internal_dim } }
22659 }

```

(End definition for __coffin_set_bounding:N.)

__coffin_rotate_bounding:nnn

Rotating the position of the corner of the coffin is just a case of treating this as a vector from the reference point. The same treatment is used for the corners of the material itself and the bounding box.

```

22660 \cs_new_protected:Npn \__coffin_rotate_bounding:nnn #1#2#3
22661 {
22662     \__coffin_rotate_vector:nnNN {#2} {#3} \l__coffin_x_dim \l__coffin_y_dim
22663     \prop_put:Nnx \l__coffin_bounding_prop {#1}
22664     { { \dim_use:N \l__coffin_x_dim } { \dim_use:N \l__coffin_y_dim } }
22665 }
22666 \cs_new_protected:Npn \__coffin_rotate_corner:Nnnn #1#2#3#4
22667 {
22668     \__coffin_rotate_vector:nnNN {#3} {#4} \l__coffin_x_dim \l__coffin_y_dim
22669     \prop_put:cnx { l__coffin_corners_ \__int_value:w #1 _prop } {#2}
22670     { { \dim_use:N \l__coffin_x_dim } { \dim_use:N \l__coffin_y_dim } }
22671 }

```

(End definition for __coffin_rotate_bounding:nnn and __coffin_rotate_corner:Nnnn.)

__coffin_rotate_pole:Nnnnnn

Rotating a single pole simply means shifting the co-ordinate of the pole and its direction. The rotation here is about the bottom-left corner of the coffin.

```

22672 \cs_new_protected:Npn \__coffin_rotate_pole:Nnnnnn #1#2#3#4#5#6
22673 {
22674     \__coffin_rotate_vector:nnNN {#3} {#4} \l__coffin_x_dim \l__coffin_y_dim
22675     \__coffin_rotate_vector:nnNN {#5} {#6}
22676     \l__coffin_x_prime_dim \l__coffin_y_prime_dim
22677     \__coffin_set_pole:Nnx #1 {#2}
22678     {
22679         { \dim_use:N \l__coffin_x_dim } { \dim_use:N \l__coffin_y_dim }
22680         { \dim_use:N \l__coffin_x_prime_dim }
22681         { \dim_use:N \l__coffin_y_prime_dim }
22682     }
22683 }

```

(End definition for __coffin_rotate_pole:Nnnnnn.)

__coffin_rotate_vector:nnNN

A rotation function, which needs only an input vector (as dimensions) and an output space. The values \l__coffin_cos_fp and \l__coffin_sin_fp should previously have been set up correctly. Working this way means that the floating point work is kept to a minimum: for any given rotation the sin and cosine values do no change, after all.

```

22684 \cs_new_protected:Npn \__coffin_rotate_vector:nnNN #1#2#3#4
22685 {
22686     \dim_set:Nn #3
22687     {
22688         \fp_to_dim:n
22689         {
22690             \dim_to_fp:n {#1} * \l__coffin_cos_fp
22691             - \dim_to_fp:n {#2} * \l__coffin_sin_fp

```

```

22692     }
22693   }
22694   \dim_set:Nn #4
22695   {
22696     \fp_to_dim:n
22697     {
22698       \dim_to_fp:n {#1} * \l__coffin_sin_fp
22699       + \dim_to_fp:n {#2} * \l__coffin_cos_fp
22700     }
22701   }
22702 }

```

(End definition for __coffin_rotate_vector:nnNN.)

_coffin_find_corner_maxima:N
_coffin_find_corner_maxima_aux:nn

The idea here is to find the extremities of the content of the coffin. This is done by looking for the smallest values for the bottom and left corners, and the largest values for the top and right corners. The values start at the maximum dimensions so that the case where all are positive or all are negative works out correctly.

```

22703 \cs_new_protected:Npn \__coffin_find_corner_maxima:N #1
22704 {
22705   \dim_set:Nn \l__coffin_top_corner_dim { -\c_max_dim }
22706   \dim_set:Nn \l__coffin_right_corner_dim { -\c_max_dim }
22707   \dim_set:Nn \l__coffin_bottom_corner_dim { \c_max_dim }
22708   \dim_set:Nn \l__coffin_left_corner_dim { \c_max_dim }
22709   \prop_map_inline:cn { l__coffin_corners_ \__int_value:w #1 _prop }
22710   { \__coffin_find_corner_maxima_aux:nn ##2 }
22711 }
22712 \cs_new_protected:Npn \__coffin_find_corner_maxima_aux:nn #1#2
22713 {
22714   \dim_set:Nn \l__coffin_left_corner_dim
22715   { \dim_min:nn { \l__coffin_left_corner_dim } {#1} }
22716   \dim_set:Nn \l__coffin_right_corner_dim
22717   { \dim_max:nn { \l__coffin_right_corner_dim } {#1} }
22718   \dim_set:Nn \l__coffin_bottom_corner_dim
22719   { \dim_min:nn { \l__coffin_bottom_corner_dim } {#2} }
22720   \dim_set:Nn \l__coffin_top_corner_dim
22721   { \dim_max:nn { \l__coffin_top_corner_dim } {#2} }
22722 }

```

(End definition for __coffin_find_corner_maxima:N and __coffin_find_corner_maxima_aux:nn.)

_coffin_find_bounding_shift:
_coffin_find_bounding_shift_aux:nn

The approach to finding the shift for the bounding box is similar to that for the corners. However, there is only one value needed here and a fixed input property list, so things are a bit clearer.

```

22723 \cs_new_protected:Npn \__coffin_find_bounding_shift:
22724 {
22725   \dim_set:Nn \l__coffin_bounding_shift_dim { \c_max_dim }
22726   \prop_map_inline:Nn \l__coffin_bounding_prop
22727   { \__coffin_find_bounding_shift_aux:nn ##2 }
22728 }
22729 \cs_new_protected:Npn \__coffin_find_bounding_shift_aux:nn #1#2
22730 {
22731   \dim_set:Nn \l__coffin_bounding_shift_dim
22732   { \dim_min:nn { \l__coffin_bounding_shift_dim } {#1} }
22733 }

```

(End definition for `_coffin_find_bounding_shift:` and `_coffin_find_bounding_shift_aux:nn`.)

`_coffin_shift_corner:Nnnn` `_coffin_shift_pole:Nnnnnn` Shifting the corners and poles of a coffin means subtracting the appropriate values from the x - and y -components. For the poles, this means that the direction vector is unchanged.

```

22734 \cs_new_protected:Npn \_coffin_shift_corner:Nnnn #1#2#3#4
22735 {
22736   \prop_put:cnx { l__coffin_corners_ \_int_value:w #1 _ prop } {#2}
22737   {
22738     { \dim_eval:n { #3 - \l__coffin_left_corner_dim } }
22739     { \dim_eval:n { #4 - \l__coffin_bottom_corner_dim } }
22740   }
22741 }
22742 \cs_new_protected:Npn \_coffin_shift_pole:Nnnnnn #1#2#3#4#5#6
22743 {
22744   \prop_put:cnx { l__coffin_poles_ \_int_value:w #1 _ prop } {#2}
22745   {
22746     { \dim_eval:n { #3 - \l__coffin_left_corner_dim } }
22747     { \dim_eval:n { #4 - \l__coffin_bottom_corner_dim } }
22748     {#5} {#6}
22749   }
22750 }

```

(End definition for `_coffin_shift_corner:Nnnn` and `_coffin_shift_pole:Nnnnnn`.)

42.7 Resizing coffins

`\l__coffin_scale_x_fp` `\l__coffin_scale_y_fp` Storage for the scaling factors in x and y , respectively.

```

22751 \fp_new:N \l__coffin_scale_x_fp
22752 \fp_new:N \l__coffin_scale_y_fp

```

(End definition for `\l__coffin_scale_x_fp` and `\l__coffin_scale_y_fp`.)

`\l__coffin_scaled_total_height_dim` `\l__coffin_scaled_width_dim` When scaling, the values given have to be turned into absolute values.

```

22753 \dim_new:N \l__coffin_scaled_total_height_dim
22754 \dim_new:N \l__coffin_scaled_width_dim

```

(End definition for `\l__coffin_scaled_total_height_dim` and `\l__coffin_scaled_width_dim`.)

`\coffin_resize:Nnn` `\coffin_resize:cnm` Resizing a coffin begins by setting up the user-friendly names for the dimensions of the coffin box. The new sizes are then turned into scale factor. This is the same operation as takes place for the underlying box, but that operation is grouped and so the same calculation is done here.

```

22755 \cs_new_protected:Npn \coffin_resize:Nnn #1#2#3
22756 {
22757   \fp_set:Nn \l__coffin_scale_x_fp
22758   { \dim_to_fp:n {#2} / \dim_to_fp:n { \coffin_wd:N #1 } }
22759   \fp_set:Nn \l__coffin_scale_y_fp
22760   {
22761     \dim_to_fp:n {#3}
22762     / \dim_to_fp:n { \coffin_ht:N #1 + \coffin_dp:N #1 }
22763   }
22764   \box_resize_to_wd_and_ht_plus_dp:Nnn #1 {#2} {#3}
22765   \_coffin_resize_common:Nnn #1 {#2} {#3}

```

```

22766 }
22767 \cs_generate_variant:Nn \coffin_resize:Nnn { c }

```

(End definition for `\coffin_resize:Nnn`. This function is documented on page 241.)

`__coffin_resize_common:Nnn` The poles and corners of the coffin are scaled to the appropriate places before actually resizing the underlying box.

```

22768 \cs_new_protected:Npn \__coffin_resize_common:Nnn #1#2#3
22769 {
22770   \prop_map_inline:cn { l__coffin_corners_ \__int_value:w #1 _prop }
22771   { \__coffin_scale_corner:Nnnn #1 {##1} ##2 }
22772   \prop_map_inline:cn { l__coffin_poles_ \__int_value:w #1 _prop }
22773   { \__coffin_scale_pole:Nnnnnn #1 {##1} ##2 }

```

Negative x -scaling values place the poles in the wrong location: this is corrected here.

```

22774   \fp_compare:nNnT \l__coffin_scale_x_fp < \c_zero_fp
22775   {
22776     \prop_map_inline:cn { l__coffin_corners_ \__int_value:w #1 _prop }
22777     { \__coffin_x_shift_corner:Nnnn #1 {##1} ##2 }
22778     \prop_map_inline:cn { l__coffin_poles_ \__int_value:w #1 _prop }
22779     { \__coffin_x_shift_pole:Nnnnnn #1 {##1} ##2 }
22780   }
22781 }

```

(End definition for `__coffin_resize_common:Nnn`.)

`\coffin_scale:Nnn` For scaling, the opposite calculation is done to find the new dimensions for the coffin.
`\coffin_scale:cnm` Only the total height is needed, as this is the shift required for corners and poles. The scaling is done the $\text{T}_{\text{E}}\text{X}$ way as this works properly with floating point values without needing to use the `fp` module.

```

22782 \cs_new_protected:Npn \coffin_scale:Nnn #1#2#3
22783 {
22784   \fp_set:Nn \l__coffin_scale_x_fp {#2}
22785   \fp_set:Nn \l__coffin_scale_y_fp {#3}
22786   \box_scale:Nnn #1 { \l__coffin_scale_x_fp } { \l__coffin_scale_y_fp }
22787   \dim_set:Nn \l__coffin_internal_dim
22788   { \coffin_ht:N #1 + \coffin_dp:N #1 }
22789   \dim_set:Nn \l__coffin_scaled_total_height_dim
22790   { \fp_abs:n { \l__coffin_scale_y_fp } \l__coffin_internal_dim }
22791   \dim_set:Nn \l__coffin_scaled_width_dim
22792   { -\fp_abs:n { \l__coffin_scale_x_fp } \coffin_wd:N #1 }
22793   \__coffin_resize_common:Nnn #1
22794   { \l__coffin_scaled_width_dim } { \l__coffin_scaled_total_height_dim }
22795 }
22796 \cs_generate_variant:Nn \coffin_scale:Nnn { c }

```

(End definition for `\coffin_scale:Nnn`. This function is documented on page 241.)

`__coffin_scale_vector:nnNN` This functions scales a vector from the origin using the pre-set scale factors in x and y . This is a much less complex operation than rotation, and as a result the code is a lot clearer.

```

22797 \cs_new_protected:Npn \__coffin_scale_vector:nnNN #1#2#3#4
22798 {
22799   \dim_set:Nn #3
22800   { \fp_to_dim:n { \dim_to_fp:n {#1} * \l__coffin_scale_x_fp } }

```



```

22801     \dim_set:Nn #4
22802     { \fp_to_dim:n { \dim_to_fp:n {#2} * \l__coffin_scale_y_fp } }
22803   }

```

(End definition for `__coffin_scale_vector:nnNN`.)

`__coffin_scale_corner:Nnnn` Scaling both corners and poles is a simple calculation using the preceding vector scaling.
`__coffin_scale_pole:Nnnnnn`

```

22804 \cs_new_protected:Npn \__coffin_scale_corner:Nnnn #1#2#3#4
22805 {
22806   \__coffin_scale_vector:nnNN {#3} {#4} \l__coffin_x_dim \l__coffin_y_dim
22807   \prop_put:cnx { l__coffin_corners_ \__int_value:w #1 _prop } {#2}
22808   { { \dim_use:N \l__coffin_x_dim } { \dim_use:N \l__coffin_y_dim } }
22809 }
22810 \cs_new_protected:Npn \__coffin_scale_pole:Nnnnnn #1#2#3#4#5#6
22811 {
22812   \__coffin_scale_vector:nnNN {#3} {#4} \l__coffin_x_dim \l__coffin_y_dim
22813   \__coffin_set_pole:Nnx #1 {#2}
22814   {
22815     { \dim_use:N \l__coffin_x_dim } { \dim_use:N \l__coffin_y_dim }
22816     {#5} {#6}
22817   }
22818 }

```

(End definition for `__coffin_scale_corner:Nnnn` and `__coffin_scale_pole:Nnnnnn`.)

`__coffin_x_shift_corner:Nnnn` These functions correct for the x displacement that takes place with a negative horizontal
`__coffin_x_shift_pole:Nnnnnn` scaling.

```

22819 \cs_new_protected:Npn \__coffin_x_shift_corner:Nnnn #1#2#3#4
22820 {
22821   \prop_put:cnx { l__coffin_corners_ \__int_value:w #1 _prop } {#2}
22822   {
22823     { \dim_eval:n { #3 + \box_wd:N #1 } } {#4}
22824   }
22825 }
22826 \cs_new_protected:Npn \__coffin_x_shift_pole:Nnnnnn #1#2#3#4#5#6
22827 {
22828   \prop_put:cnx { l__coffin_poles_ \__int_value:w #1 _prop } {#2}
22829   {
22830     { \dim_eval:n { #3 + \box_wd:N #1 } } {#4}
22831     {#5} {#6}
22832   }
22833 }

```

(End definition for `__coffin_x_shift_corner:Nnnn` and `__coffin_x_shift_pole:Nnnnnn`.)

42.8 Additions to l3file

```

22834 <@@=file>

```

`\file_get_md5hash:nN` These are all wrappers around the pdfTeX primitives doing the same jobs: as we want
`\file_get_size:nN` consistent file paths to be found, they are all set up using `\file_get_full_name:nN`
`\file_get_timestamp:nN` and so are non-expandable `get` functions. Much of the code is repetitive but we need
`__file_get_details:nnN` to branch for LuaTeX (emulation in Lua), for the slightly different syntax needed for
`\pdfTEX_md5sum:D` and for the fact that primitive coverage varies in other engines.

```

22835 \cs_new_protected:Npn \file_get_md5hash:nN #1#2
22836 { \__file_get_details:nnN {#1} { md5sum } {#2} }
22837 \cs_new_protected:Npn \file_get_size:nN #1#2
22838 { \__file_get_details:nnN {#1} { size } {#2} }
22839 \cs_new_protected:Npn \file_get_timestamp:nN #1#2
22840 { \__file_get_details:nnN {#1} { moddate } {#2} }
22841 \cs_new_protected:Npn \__file_get_details:nnN #1#2#3
22842 {
22843   \file_get_full_name:nN {#1} \l__file_full_name_str
22844   \str_set:Nx #3
22845   {
22846     \use:c { pdfTeX_file #2 :D } \exp_after:wN
22847     { \l__file_full_name_str }
22848   }
22849 }
22850 \cs_if_exist:NTF \luatex_directlua:D
22851 {
22852   \cs_set_protected:Npn \__file_get_details:nnN #1#2#3
22853   {
22854     \file_get_full_name:nN {#1} \l__file_full_name_str
22855     \str_set:Nx #3
22856     {
22857       \lua_now_x:n
22858       {
22859         l3kernel.file#2
22860         ( " \lua_escape_x:n { \l__file_full_name_str } " )
22861       }
22862     }
22863   }
22864 }
22865 {
22866   \cs_set_protected:Npn \file_get_md5hash:nN #1#2
22867   {
22868     \file_get_full_name:nN {#1} \l__file_full_name_str
22869     \tl_set:Nx #2
22870     {
22871       \pdfTeX_md5sum:D file \exp_after:wN
22872       { \l__file_full_name_str }
22873     }
22874   }
22875   \cs_if_exist:NTF \xetex_XeTeXversion:D
22876   {
22877     \cs_set_protected:Npn \__file_get_details:nnN #1#2#3
22878     {
22879       \tl_clear:N #3
22880       \__msg_kernel_error:nnx
22881       { kernel } { xetex-primitive-not-available }
22882       { \exp_not:c { pdfFile #2 } }
22883     }
22884   }
22885 }
22886 \__msg_kernel_new:nnnn { kernel } { xetex-primitive-not-available }
22887 { Primitive~\token_to_str:N #1 not~available }
22888 {

```

```

22889      XeTeX~does~not~currently~provide~functionality~equivalent~to~the~
22890      \token_to_str:N #1 primitive.
22891    }

```

(End definition for `\file_get_md5hash:nN` and others. These functions are documented on page 241.)

`\file_if_exist_input:n` Input of a file with a test for existence. We do not define the T or TF variants because the most useful place to place the *⟨true code⟩* would be inconsistent with other conditionals.

`\file_if_exist_input:nF`

```

22892 \cs_new_protected:Npn \file_if_exist_input:n #1
22893 {
22894   \file_get_full_name:nN {#1} \l__file_full_name_str
22895   \str_if_empty:NF \l__file_full_name_str
22896   { \__file_input:V \l__file_full_name_str }
22897 }
22898 \cs_new_protected:Npn \file_if_exist_input:nF #1#2
22899 {
22900   \file_get_full_name:nN {#1} \l__file_full_name_str
22901   \str_if_empty:NTF \l__file_full_name_str
22902   {#2}
22903   { \__file_input:V \l__file_full_name_str }
22904 }

```

(End definition for `\file_if_exist_input:n` and `\file_if_exist_input:nF`. These functions are documented on page 242.)

`\file_if_exist_input:nT`
`\file_if_exist_input:nTF`

For removal after 2017-12-31.

```

22905 \__debug_deprecation:nnNNpn { 2017-12-31 }
22906 { \file_if_exist:nTF and~ \file_input:n }
22907 \cs_new_protected:Npn \file_if_exist_input:nTF #1#2#3
22908 {
22909   \file_get_full_name:nN {#1} \l__file_full_name_str
22910   \str_if_empty:NTF \l__file_full_name_str
22911   {#3} { #2 \__file_input:V \l__file_full_name_str }
22912 }
22913 \__debug_deprecation:nnNNpn { 2017-12-31 }
22914 { \file_if_exist:nT and~ \file_input:n }
22915 \cs_new_protected:Npn \file_if_exist_input:nT #1#2
22916 {
22917   \file_get_full_name:nN {#1} \l__file_full_name_str
22918   \str_if_empty:NF \l__file_full_name_str
22919   { #2 \__file_input:V \l__file_full_name_str }
22920 }

```

(End definition for `\file_if_exist_input:nT` and `\file_if_exist_input:nTF`.)

`\file_input_stop:` A simple rename.

```

22921 \cs_new_protected:Npn \file_input_stop: { \tex_endinput:D }

```

(End definition for `\file_input_stop:`. This function is documented on page 242.)

42.9 Additions to l3int

22922 $\langle @@=int \rangle$

\int_rand:nn
__int_rand:ww
__int_rand_narrow:n
__int_rand_narrow:nnn
__int_rand_narrow:nnnn

Evaluate the argument and filter out the case where the lower bound #1 is more than the upper bound #2. Then determine whether the range is narrower than $\backslash c_fp_rand_size_int$; #2-#1 may overflow for very large positive #2 and negative #1. If the range is wide, use slower code from l3fp. If the range is narrow, call $\backslash_int_rand_narrow:nn$ $\langle \{choices\} \{#1\}$ where $\langle choices \rangle$ is the number of possible outcomes. Then $\backslash_int_rand_narrow:nnnn$ receives a random number reduced modulo $\langle choices \rangle$, the random number itself, $\langle choices \rangle$ and #1. To avoid bias, throw away the random number if it lies in the last, incomplete, interval of size $\langle choices \rangle$ in $[0, \backslash c_fp_rand_size_int - 1]$, and try again.

```
22923 \cs_if_exist:NTF \pdfTEX_uniformdeviate:D
22924 {
22925   \__debug_patch_args:nNnNpn
22926   {
22927     { \__debug_chk_expr:nNnN {#1} \__int_eval:w { } \int_rand:nn }
22928     { \__debug_chk_expr:nNnN {#2} \__int_eval:w { } \int_rand:nn }
22929   }
22930   \cs_new:Npn \int_rand:nn #1#2
22931   {
22932     \exp_after:wN \__int_rand:ww
22933     \__int_value:w \__int_eval:w #1 \exp_after:wN ;
22934     \__int_value:w \__int_eval:w #2 ;
22935   }
22936   \cs_new:Npn \__int_rand:ww #1; #2;
22937   {
22938     \int_compare:nNnTF {#1} > {#2}
22939     {
22940       \__msg_kernel_expandable_error:nnnn
22941       { kernel } { backward-range } {#1} {#2}
22942       \__int_rand:ww #2; #1;
22943     }
22944     {
22945       \int_compare:nNnTF {#1} > 0
22946       { \int_compare:nNnTF { #2 - #1 } < \c_fp_rand_size_int }
22947       { \int_compare:nNnTF {#2} < { #1 + \c_fp_rand_size_int } }
22948       {
22949         \exp_args:Nf \__int_rand_narrow:nn
22950         { \int_eval:n { #2 - #1 + 1 } } {#1}
22951       }
22952       { \fp_to_int:n { randint(#1,#2) } }
22953     }
22954   }
22955   \cs_new:Npn \__int_rand_narrow:nn
22956   {
22957     \exp_args:No \__int_rand_narrow:nnn
22958     { \pdfTEX_uniformdeviate:D \c_fp_rand_size_int }
22959   }
22960   \cs_new:Npn \__int_rand_narrow:nnn #1#2
22961   {
22962     \exp_args:Nf \__int_rand_narrow:nnnn
22963     { \int_mod:nn {#1} {#2} } {#1} {#2}
```

```

22964     }
22965     \cs_new:Npn \__int_rand_narrow:nnnn #1#2#3#4
22966     {
22967         \int_compare:nNnTF { #2 - #1 + #3 } > \c__fp_rand_size_int
22968         { \__int_rand_narrow:nn {#3} {#4} }
22969         { \int_eval:n { #4 + #1 } }
22970     }
22971 }
22972 {
22973     \cs_new:Npn \int_rand:nn #1#2
22974     {
22975         \__msg_kernel_expandable_error:nn { kernel } { fp-no-random }
22976         \int_eval:n {#1}
22977     }
22978 }

```

(End definition for `\int_rand:nn` and others. This function is documented on page 242.)

The following must be added to `l3msg`.

```

22979 \cs_if_exist:NT \pdfTeX_uniformdeviate:D
22980 {
22981     \__msg_kernel_new:nnn { kernel } { backward-range }
22982     { Bounds~ordered~backwards~in~\int_rand:nn {#1}~{#2}. }
22983 }

```

42.10 Additions to `l3msg`

```

22984 <@@=msg>

```

Pass to an auxiliary the message to display and the module name

```

\msg_expandable_error:nnnnnn \cs_new:Npn \msg_expandable_error:nnnnnn #1#2#3#4#5#6
\msg_expandable_error:nnffff {
\msg_expandable_error:nnnnn \exp_args:Nf \__msg_expandable_error_module:nn
\msg_expandable_error:nnfff {
\msg_expandable_error:nnnn \exp_args:Nf \tl_to_str:n
\msg_expandable_error:nnff { \use:c { \c__msg_text_prefix_tl #1 / #2 } {#3} {#4} {#5} {#6} }
\msg_expandable_error:nnn {
\msg_expandable_error:nnf {#1}
\msg_expandable_error:nn {
\__msg_expandable_error_module:nn
22985 \cs_new:Npn \msg_expandable_error:nnnnn #1#2#3#4#5
22986 { \msg_expandable_error:nnnnnn {#1} {#2} {#3} {#4} {#5} { } }
22987 \cs_new:Npn \msg_expandable_error:nnnn #1#2#3#4
22988 { \msg_expandable_error:nnnnnn {#1} {#2} {#3} {#4} { } { } }
22989 \cs_new:Npn \msg_expandable_error:nnn #1#2#3
22990 { \msg_expandable_error:nnnnnn {#1} {#2} {#3} { } { } { } }
22991 \cs_new:Npn \msg_expandable_error:nn #1#2
22992 { \msg_expandable_error:nnnnnn {#1} {#2} { } { } { } { } }
22993 { \msg_expandable_error:nnnnnn {#1} {#2} { } { } { } { } }
22994 \cs_generate_variant:Nn \msg_expandable_error:nnnnnn { nnffff }
22995 \cs_generate_variant:Nn \msg_expandable_error:nnnnn { nnfff }
22996 \cs_generate_variant:Nn \msg_expandable_error:nnnn { nnff }
22997 \cs_generate_variant:Nn \msg_expandable_error:nnn { nnf }
22998 \cs_new:Npn \__msg_expandable_error_module:nn #1#2
22999 {
23000     \exp_after:wN \exp_after:wN
23001     \exp_after:wN \use_none_delimit_by_q_stop:w

```

```

23010 \use:n { \::error ! ~ #2 : ~ #1 } \q_stop
23011 }

```

(End definition for `\msg_expandable_error:nnnnnn` and others. These functions are documented on page 243.)

`\msg_show_eval:Nn` A short-hand used for `\int_show:n` and similar functions that passes to `\tl_show:n` the result of applying `#1` (a function such as `\int_eval:n`) to the expression `#2`. The use of f-expansion ensures that `#1` is expanded in the scope in which the show command is called, rather than in the group created by `\iow_wrap:nnnN`. This is only important for expressions involving the `\currentgrouplevel` or `\currentgrouptype`. On the other hand we want the expression to be converted to a string with the usual escape character, hence within the wrapping code.

```

23012 \cs_new_protected:Npn \msg_show_eval:Nn #1#2
23013 { \exp_args:Nf \_msg_show_eval:nnN { #1 {#2} } {#2} \tl_show:n }
23014 \cs_new_protected:Npn \msg_log_eval:Nn #1#2
23015 { \exp_args:Nf \_msg_show_eval:nnN { #1 {#2} } {#2} \tl_log:n }
23016 \cs_new_protected:Npn \_msg_show_eval:nnN #1#2#3 { #3 { #2 = #1 } }

```

(End definition for `\msg_show_eval:Nn`, `\msg_log_eval:Nn`, and `_msg_show_eval:nnN`. These functions are documented on page 243.)

`\msg_show_item:n` Each item in the variable is formatted using one of the following functions. We cannot use `\` and so on because these short-hands cannot be used inside the arguments of messages, only when defining the messages.

```

\msg_show_item_unbraced:n
\msg_show_item:nn
\msg_show_item_unbraced:nn
23017 \cs_new:Npx \msg_show_item:n #1
23018 { \iow_newline: > ~ \c_space_tl \exp_not:N \tl_to_str:n { {#1} } }
23019 \cs_new:Npx \msg_show_item_unbraced:n #1
23020 { \iow_newline: > ~ \c_space_tl \exp_not:N \tl_to_str:n {#1} }
23021 \cs_new:Npx \msg_show_item:nn #1#2
23022 {
23023   \iow_newline: > \use:nn { ~ } { ~ }
23024   \exp_not:N \tl_to_str:n { {#1} }
23025   \use:nn { ~ } { ~ } => \use:nn { ~ } { ~ }
23026   \exp_not:N \tl_to_str:n { {#2} }
23027 }
23028 \cs_new:Npx \msg_show_item_unbraced:nn #1#2
23029 {
23030   \iow_newline: > \use:nn { ~ } { ~ }
23031   \exp_not:N \tl_to_str:n {#1}
23032   \use:nn { ~ } { ~ } => \use:nn { ~ } { ~ }
23033   \exp_not:N \tl_to_str:n {#2}
23034 }

```

(End definition for `\msg_show_item:n` and others. These functions are documented on page 243.)

42.11 Additions to l3prg

`\bool_const:Nn` A merger between `\tl_const:Nn` and `\bool_set:Nn`.

```

\bool_const:cn
23035 \_debug_patch:nnNpn { \_debug_chk_var_scope:NN c #1 } { }
23036 \cs_new_protected:Npn \bool_const:Nn #1#2
23037 {
23038   \_chk_if_free_cs:N #1
23039   \tex_global:D \tex_chardef:D #1 = \bool_if_p:n {#2}

```

```

23040     }
23041     \cs_generate_variant:Nn \bool_const:Nn { c }

```

(End definition for `\bool_const:Nn`. This function is documented on page 243.)

42.12 Additions to `l3prop`

```

23042 <@@=prop>

```

`\prop_count:N` Counting the key–value pairs in a property list is done using the same approach as for other count functions: turn each entry into a +1 then use integer evaluation to actually do the mathematics.

```

\prop_count:c
\__prop_count:nn
23043 \cs_new:Npn \prop_count:N #1
23044 {
23045     \int_eval:n
23046     {
23047         0
23048         \prop_map_function:NN #1 \__prop_count:nn
23049     }
23050 }
23051 \cs_new:Npn \__prop_count:nn #1#2 { + 1 }
23052 \cs_generate_variant:Nn \prop_count:N { c }

```

(End definition for `\prop_count:N` and `__prop_count:nn`. This function is documented on page 244.)

`\prop_map_tokens:Nn` The mapping is very similar to `\prop_map_function:NN`. It grabs one key–value pair at a time, and stops when reaching the marker key `\q_recursion_tail`, which cannot appear in normal keys since those are strings. The odd construction `\use:n {#1}` allows #1 to contain any token without interfering with `\prop_map_break:.` Argument #2 of `__prop_map_tokens:nwn` is `\s__prop` the first time, and is otherwise empty.

```

\prop_map_tokens:cn
\__prop_map_tokens:nwn
23053 \cs_new:Npn \prop_map_tokens:Nn #1#2
23054 {
23055     \exp_last_unbraced:Nno \__prop_map_tokens:nwn {#2} #1
23056     \__prop_pair:wn \q_recursion_tail \s__prop { }
23057     \__prg_break_point:Nn \prop_map_break: { }
23058 }
23059 \cs_new:Npn \__prop_map_tokens:nwn #1#2 \__prop_pair:wn #3 \s__prop #4
23060 {
23061     \if_meaning:w \q_recursion_tail #3
23062     \exp_after:wN \prop_map_break:
23063     \fi:
23064     \use:n {#1} {#3} {#4}
23065     \__prop_map_tokens:nwn {#1}
23066 }
23067 \cs_generate_variant:Nn \prop_map_tokens:Nn { c }

```

(End definition for `\prop_map_tokens:Nn` and `__prop_map_tokens:nwn`. This function is documented on page 244.)

`\prop_rand_key_value:N` Contrarily to `clist`, `seq` and `tl`, there is no function to get an item of a `prop` given an integer between 1 and the number of items, so we write the appropriate code. There is no bounds checking because `\int_rand:nn` is always within bounds. At the end, leave either the key #3 or the value #4 in the input stream.

```

23068 \cs_new:Npn \prop_rand_key_value:N { \__prop_rand:NN \__prop_rand:nNn }

```

```

23069 \cs_new:Npn \__prop_rand:nNn #1#2#3 { \exp_not:n { {#1} {#3} } }
23070 \cs_new:Npn \__prop_rand:NN #1#2
23071 {
23072   \prop_if_empty:NTF #2 { }
23073   {
23074     \exp_after:wN \__prop_rand_item:Nw \exp_after:wN #1
23075     \__int_value:w \int_rand:nn { 1 } { \prop_count:N #2 } #2
23076     \q_stop
23077   }
23078 }
23079 \cs_new:Npn \__prop_rand_item:Nw #1#2 \s__prop \__prop_pair:wn #3 \s__prop #4
23080 {
23081   \int_compare:nNnF {#2} > 1
23082   { \use_i_delimit_by_q_stop:nw { #1 {#3} \exp_not:n {#4} } }
23083   \exp_after:wN \__prop_rand_item:Nw \exp_after:wN #1
23084   \__int_value:w \int_eval:n { #2 - 1 } \s__prop
23085 }
23086 \cs_generate_variant:Nn \prop_rand_key_value:N { c }

```

(End definition for `\prop_rand_key_value:N`, `__prop_rand:NN`, and `__prop_rand_item:Nw`. This function is documented on page 244.)

42.13 Additions to l3seq

```

23087 <@@=seq>

```

```

\seq_mapthread_function:NNN
\seq_mapthread_function:NcN
\seq_mapthread_function:cNN
\seq_mapthread_function:ccN
  \__seq_mapthread_function:wNN
  \__seq_mapthread_function:wNw
  \__seq_mapthread_function:Nnnwnn

```

The idea is to first expand both sequences, adding the usual `{ ? __prg_break: } { }` to the end of each one. This is most conveniently done in two steps using an auxiliary function. The mapping then throws away the first tokens of #2 and #5, which for items in both sequences are `\s__seq __seq_item:n`. The function to be mapped are then be applied to the two entries. When the code hits the end of one of the sequences, the break material stops the entire loop and tidy up. This avoids needing to find the count of the two sequences, or worrying about which is longer.

```

23088 \cs_new:Npn \seq_mapthread_function:NNN #1#2#3
23089 { \exp_after:wN \__seq_mapthread_function:wNN #2 \q_stop #1 #3 }
23090 \cs_new:Npn \__seq_mapthread_function:wNN \s__seq #1 \q_stop #2#3
23091 {
23092   \exp_after:wN \__seq_mapthread_function:wNw #2 \q_stop #3
23093   #1 { ? \__prg_break: } { }
23094   \__prg_break_point:
23095 }
23096 \cs_new:Npn \__seq_mapthread_function:wNw \s__seq #1 \q_stop #2
23097 {
23098   \__seq_mapthread_function:Nnnwnn #2
23099   #1 { ? \__prg_break: } { }
23100   \q_stop
23101 }
23102 \cs_new:Npn \__seq_mapthread_function:Nnnwnn #1#2#3#4 \q_stop #5#6
23103 {
23104   \use_none:n #2
23105   \use_none:n #5
23106   #1 {#3} {#6}
23107   \__seq_mapthread_function:Nnnwnn #1 #4 \q_stop
23108 }

```



```

23109 \cs_generate_variant:Nn \seq_mapthread_function:NNN { Nc }
23110 \cs_generate_variant:Nn \seq_mapthread_function:NNN { c , cc }

```

(End definition for `\seq_mapthread_function:NNN` and others. This function is documented on page 245.)

`\seq_set_filter:NNn` Similar to `\seq_map_inline:Nn`, without a `__prg_break_point:` because the user's code is performed within the evaluation of a boolean expression, and skipping out of that would break horribly. The `__seq_wrap_item:n` function inserts the relevant `__seq_item:n` without expansion in the input stream, hence in the x-expanding assignment.

```

23111 \cs_new_protected:Npn \seq_set_filter:NNn
23112 { \__seq_set_filter:NNNn \tl_set:Nx }
23113 \cs_new_protected:Npn \seq_gset_filter:NNn
23114 { \__seq_set_filter:NNNn \tl_gset:Nx }
23115 \cs_new_protected:Npn \__seq_set_filter:NNNn #1#2#3#4
23116 {
23117   \__seq_push_item_def:n { \bool_if:nT {#4} { \__seq_wrap_item:n {##1} } }
23118   #1 #2 { #3 }
23119   \__seq_pop_item_def:
23120 }

```

(End definition for `\seq_set_filter:NNn`, `\seq_gset_filter:NNn`, and `__seq_set_filter:NNNn`. These functions are documented on page 245.)

`\seq_set_map:NNn` Very similar to `\seq_set_filter:NNn`. We could actually merge the two within a single function, but it would have weird semantics.

```

23121 \cs_new_protected:Npn \seq_set_map:NNn
23122 { \__seq_set_map:NNNn \tl_set:Nx }
23123 \cs_new_protected:Npn \seq_gset_map:NNn
23124 { \__seq_set_map:NNNn \tl_gset:Nx }
23125 \cs_new_protected:Npn \__seq_set_map:NNNn #1#2#3#4
23126 {
23127   \__seq_push_item_def:n { \exp_not:N \__seq_item:n {#4} }
23128   #1 #2 { #3 }
23129   \__seq_pop_item_def:
23130 }

```

(End definition for `\seq_set_map:NNn`, `\seq_gset_map:NNn`, and `__seq_set_map:NNNn`. These functions are documented on page 245.)

`\seq_rand_item:N` Importantly, `\seq_item:Nn` only evaluates its argument once.

```

23131 \cs_new:Npn \seq_rand_item:N #1
23132 {
23133   \seq_if_empty:NF #1
23134   { \seq_item:Nn #1 { \int_rand:nn { 1 } } { \seq_count:N #1 } } }
23135 }
23136 \cs_generate_variant:Nn \seq_rand_item:N { c }

```

(End definition for `\seq_rand_item:N`. This function is documented on page 245.)

`\seq_const_from_clist:Nn` Almost identical to `\seq_set_from_clist:Nn`.

```

23137 \cs_new_protected:Npn \seq_const_from_clist:Nn #1#2
23138 {
23139   \tl_const:Nx #1
23140   { \s__seq \clist_map_function:nN {#2} \__seq_wrap_item:n }
23141 }
23142 \cs_generate_variant:Nn \seq_const_from_clist:Nn { c }

```

(End definition for `\seq_const_from_clist:Nn`. This function is documented on page 245.)

42.14 Additions to `l3skip`

23143 `<@@=skip>`

`\skip_split_finite_else_action:nmNN`

This macro is useful when performing error checking in certain circumstances. If the `<skip>` register holds finite glue it sets #3 and #4 to the stretch and shrink component, resp. If it holds infinite glue set #3 and #4 to zero and issue the special action #2 which is probably an error message. Assignments are local.

```
23144 \cs_new:Npn \skip_split_finite_else_action:nmNN #1#2#3#4
23145 {
23146   \skip_if_finite:nTF {#1}
23147   {
23148     #3 = \etex_gluestretch:D #1 \scan_stop:
23149     #4 = \etex_glueshrink:D #1 \scan_stop:
23150   }
23151   {
23152     #3 = \c_zero_skip
23153     #4 = \c_zero_skip
23154     #2
23155   }
23156 }
```

(End definition for `\skip_split_finite_else_action:nmNN`. This function is documented on page 246.)

42.15 Additions to `l3sys`

23157 `<@@=sys>`

`\sys_if_rand_exist:p:`

Currently, randomness exists under pdfTeX and LuaTeX.

`\sys_if_rand_exist:TF`

```
23158 \cs_if_exist:NTF \pdftex_uniformdeviate:D
23159 {
23160   \prg_new_conditional:Npnn \sys_if_rand_exist: { p , T , F , TF }
23161   { \prg_return_true: }
23162 }
23163 {
23164   \prg_new_conditional:Npnn \sys_if_rand_exist: { p , T , F , TF }
23165   { \prg_return_false: }
23166 }
```

(End definition for `\sys_if_rand_exist:TF`. This function is documented on page 246.)

`\sys_rand_seed:`

Unpack the primitive.

```
23167 \cs_new:Npn \sys_rand_seed: { \tex_the:D \pdftex_randomseed:D }
23168 \cs_if_exist:NF \pdftex_randomseed:D
23169 { \cs_set:Npn \sys_rand_seed: { 0 } }
```

(End definition for `\sys_rand_seed:.` This function is documented on page 246.)

`\sys_gset_rand_seed:n`

The primitive always assigns the seed globally.

```
23170 \cs_new_protected:Npn \sys_gset_rand_seed:n #1
23171 { \pdftex_setrandomseed:D \__int_eval:n {#1} }
```

(End definition for `\sys_gset_rand_seed:n`. This function is documented on page 246.)

\c_sys_shell_escape_int Expose the engine's shell escape status to the user.

```
23172 \int_const:Nn \c_sys_shell_escape_int
23173 {
23174   \sys_if_engine luatex:TF
23175   {
23176     \luatex_directlua:D
23177     {
23178       tex.sprint((status.shell_escape~or~os.execute()) .. " ")
23179     }
23180   }
23181   {
23182     \pdfTeX_shellescape:D
23183   }
23184 }
```

(End definition for \c_sys_shell_escape_int. This variable is documented on page 246.)

\sys_if_shell_p: Performs a check for whether shell escape is enabled. This returns true if either of restricted or unrestricted shell escape is enabled.

\sys_if_shell:TF

```
23185 \prg_new_conditional:Nnn \sys_if_shell: { p , T , F , TF }
23186 {
23187   \if_int_compare:w \c_sys_shell_escape_int = 0 ~
23188     \prg_return_false:
23189   \else:
23190     \prg_return_true:
23191   \fi:
23192 }
```

(End definition for \sys_if_shell:TF. This function is documented on page 246.)

\sys_if_shell_unrestricted_p: Performs a check for whether *unrestricted* shell escape is enabled.

\sys_if_shell_unrestricted:TF

```
23193 \prg_new_conditional:Nnn \sys_if_shell_unrestricted: { p , T , F , TF }
23194 {
23195   \if_int_compare:w \c_sys_shell_escape_int = 1 ~
23196     \prg_return_true:
23197   \else:
23198     \prg_return_false:
23199   \fi:
23200 }
```

(End definition for \sys_if_shell_unrestricted:TF. This function is documented on page 246.)

\sys_if_shell_unrestricted_p: Performs a check for whether *restricted* shell escape is enabled. This returns false if unrestricted shell escape is enabled. Unrestricted shell escape is not considered a superset of restricted shell escape in this case. To find whether any shell escape is enabled use **\sys_if_shell:**.

\sys_if_shell_unrestricted:TF

```
23201 \prg_new_conditional:Nnn \sys_if_shell_restricted: { p , T , F , TF }
23202 {
23203   \if_int_compare:w \c_sys_shell_escape_int = 2 ~
23204     \prg_return_true:
23205   \else:
23206     \prg_return_false:
23207   \fi:
23208 }
```

(End definition for `\sys_if_shell_unrestricted:TF`. This function is documented on page 246.)

`\c__sys_shell_stream_int` This is not needed for LuaTeX: shell escape there isn't done using a T_EX interface

```
23209 \sys_if_engine luatex:F
23210 { \int_const:Nn \c__sys_shell_stream_int { 18 } }
```

(End definition for `\c__sys_shell_stream_int`.)

`\sys_shell_now:n` Execute commands through shell escape immediately.

```
23211 \sys_if_engine luatex:TF
23212 {
23213   \cs_new_protected:Npn \sys_shell_now:n #1
23214   {
23215     \luatex_directlua:D
23216     {
23217       os.execute("
23218         \luatex_luaescapestring:D { \etex_detokenize:D {#1} }
23219       ")
23220     }
23221   }
23222 }
23223 {
23224   \cs_new_protected:Npn \sys_shell_now:n #1
23225   {
23226     \iow_now:Nn \c__sys_shell_stream_int { #1 }
23227   }
23228 }
23229 \cs_generate_variant:Nn \sys_shell_now:n { x }
```

(End definition for `\sys_shell_now:n`. This function is documented on page 247.)

`\sys_shell_shipout:n` Execute commands through shell escape at shipout.

```
23230 \sys_if_engine luatex:TF
23231 {
23232   \cs_new_protected:Npn \sys_shell_shipout:n #1
23233   {
23234     \luatex_latelua:D
23235     {
23236       os.execute("
23237         \luatex_luaescapestring:D { \etex_detokenize:D {#1} }
23238       ")
23239     }
23240   }
23241 }
23242 {
23243   \cs_new_protected:Npn \sys_shell_shipout:n #1
23244   {
23245     \iow_shipout:Nn \c__sys_shell_stream_int { #1 }
23246   }
23247 }
23248 \cs_generate_variant:Nn \sys_shell_shipout:n { x }
```

(End definition for `\sys_shell_shipout:n`. This function is documented on page 247.)

42.16 Additions to l3tl

23249 <@@=tl>

`\tl_if_single_token_p:n`
`\tl_if_single_token:nTF`

There are four cases: empty token list, token list starting with a normal token, with a brace group, or with a space token. If the token list starts with a normal token, remove it and check for emptiness. For the next case, an empty token list is not a single token. Finally, we have a non-empty token list starting with a space or a brace group. Applying f-expansion yields an empty result if and only if the token list is a single space.

```
23250 \prg_new_conditional:Npnn \tl_if_single_token:n #1 { p , T , F , TF }
23251 {
23252   \tl_if_head_is_N_type:nTF {#1}
23253   { \__tl_if_empty_return:o { \use_none:n #1 } }
23254   {
23255     \tl_if_empty:nTF {#1}
23256     { \prg_return_false: }
23257     { \__tl_if_empty_return:o { \exp:w \exp_end_continue_f:w #1 } }
23258   }
23259 }
```

(End definition for `\tl_if_single_token:nTF`. This function is documented on page 247.)

`\tl_reverse_tokens:n`
`__tl_reverse_group:nn`

The same as `\tl_reverse:n` but with recursion within brace groups.

```
23260 \cs_new:Npn \tl_reverse_tokens:n #1
23261 {
23262   \etex_unexpanded:D \exp_after:wN
23263   {
23264     \exp:w
23265     \__tl_act:NNNnn
23266     \__tl_reverse_normal:nN
23267     \__tl_reverse_group:nn
23268     \__tl_reverse_space:n
23269     { }
23270     {#1}
23271   }
23272 }
23273 \cs_new:Npn \__tl_reverse_group:nn #1
23274 {
23275   \__tl_act_group_recurse:Nnn
23276   \__tl_act_reverse_output:n
23277   { \tl_reverse_tokens:n }
23278 }
```

`__tl_act_group_recurse:Nnn`

In many applications of `__tl_act:NNNnn`, we need to recursively apply some transformation within brace groups, then output. In this code, #1 is the output function, #2 is the transformation, which should expand in two steps, and #3 is the group.

```
23279 \cs_new:Npn \__tl_act_group_recurse:Nnn #1#2#3
23280 {
23281   \exp_args:Nf #1
23282   { \exp_after:wN \exp_after:wN \exp_after:wN { #2 {#3} } }
23283 }
```

(End definition for `\tl_reverse_tokens:n`, `__tl_reverse_group:nn`, and `__tl_act_group_recurse:Nnn`. This function is documented on page 247.)

`\tl_count_tokens:n` The token count is computed through an `\int_eval:n` construction. Each `1+` is output to the *left*, into the integer expression, and the sum is ended by the `\exp_end:` inserted by `__tl_act_end:wn` (which is technically implemented as `\c_zero`). Somewhat a hack!

```

23284 \cs_new:Npn \tl_count_tokens:n #1
23285 {
23286   \int_eval:n
23287   {
23288     \__tl_act:NNNnn
23289     \__tl_act_count_normal:nN
23290     \__tl_act_count_group:nn
23291     \__tl_act_count_space:n
23292     { }
23293     {#1}
23294   }
23295 }
23296 \cs_new:Npn \__tl_act_count_normal:nN #1 #2 { 1 + }
23297 \cs_new:Npn \__tl_act_count_space:n #1 { 1 + }
23298 \cs_new:Npn \__tl_act_count_group:nn #1 #2
23299 { 2 + \tl_count_tokens:n {#2} + }

```

(End definition for `\tl_count_tokens:n` and others. This function is documented on page 247.)

`\tl_set_from_file:Nnn` The approach here is similar to that for doing a rescan, and so the same internals can be reused. Thus the plan is to insert a pair of tokens of the same charcode but different catcodes after the file has been read. This plus `\exp_not:N` allows the primitive to be used to carry out a set operation.

`\tl_set_from_file:cnn`

`\tl_gset_from_file:Nnn`

`\tl_gset_from_file:cnn`

```

23300 \cs_new_protected:Npn \tl_set_from_file:Nnn
23301 { \__tl_set_from_file:NNnn \tl_set:Nn }
23302 \cs_new_protected:Npn \tl_gset_from_file:Nnn
23303 { \__tl_set_from_file:NNnn \tl_gset:Nn }
23304 \cs_generate_variant:Nn \tl_set_from_file:Nnn { c }
23305 \cs_generate_variant:Nn \tl_gset_from_file:Nnn { c }
23306 \cs_new_protected:Npn \__tl_set_from_file:NNnn #1#2#3#4
23307 {
23308   \file_get_full_name:nN {#4} \l__file_full_name_str
23309   \str_if_empty:NTF \l__file_full_name_str
23310   { \__file_missing:n {#4} }
23311   {
23312     \group_begin:
23313     \exp_args:No \etex_everyeof:D
23314     { \c__tl_rescan_marker_tl \exp_not:N }
23315     #3 \scan_stop:
23316     \exp_after:wN \__tl_from_file_do:w
23317     \exp_after:wN \prg_do_nothing:
23318     \tex_input:D \l__file_full_name_str \scan_stop:
23319     \exp_args:NNNo \group_end:
23320     #1 #2 \l__tl_internal_a_tl
23321   }
23322 }
23323 \exp_args:Nno \use:nn
23324 { \cs_new_protected:Npn \__tl_from_file_do:w #1 }
23325 { \c__tl_rescan_marker_tl }
23326 { \tl_set:No \l__tl_internal_a_tl {#1} }

```

(End definition for `\tl_set_from_file:Nnn` and others. These functions are documented on page 250.)

```

\tl_set_from_file_x:Nnn When reading a file and allowing expansion of the content, the set up only needs to
\tl_set_from_file_x:cnn prevent TeX complaining about the end of the file. That is done simply, with a group
\tl_gset_from_file_x:Nnn then used to trap the definition needed. Once the business is done using some scratch
\tl_gset_from_file_x:cnn space, the tokens can be transferred to the real target.
\_tl_set_from_file_x:NNnn
23327 \cs_new_protected:Npn \tl_set_from_file_x:Nnn
23328 { \_tl_set_from_file_x:NNnn \tl_set:Nn }
23329 \cs_new_protected:Npn \tl_gset_from_file_x:Nnn
23330 { \_tl_set_from_file_x:NNnn \tl_gset:Nn }
23331 \cs_generate_variant:Nn \tl_set_from_file_x:Nnn { c }
23332 \cs_generate_variant:Nn \tl_gset_from_file_x:Nnn { c }
23333 \cs_new_protected:Npn \_tl_set_from_file_x:NNnn #1#2#3#4
23334 {
23335   \file_get_full_name:nN {#4} \l__file_full_name_str
23336   \str_if_empty:NTF \l__file_full_name_str
23337   { \_file_missing:n {#4} }
23338   {
23339     \group_begin:
23340     \etex_veryeof:D { \exp_not:N }
23341     #3 \scan_stop:
23342     \tl_set:Nx \l__tl_internal_a_tl
23343     { \tex_input:D \l__file_full_name_str \c_space_token }
23344     \exp_args:NNNo \group_end:
23345     #1 #2 \l__tl_internal_a_tl
23346   }
23347 }

```

(End definition for `\tl_set_from_file_x:Nnn`, `\tl_gset_from_file_x:Nnn`, and `_tl_set_from_file_x:NNnn`. These functions are documented on page 251.)

42.16.1 Unicode case changing

The mechanisms needed for case changing are somewhat involved, particularly to allow for all of the special cases. These functions also require the appropriate data extracted from the Unicode documentation (either manually or automatically).

```

\tl_if_head_eq_catcode:oNTF Extra variants.
23348 \cs_generate_variant:Nn \tl_if_head_eq_catcode:nNTF { o }

```

(End definition for `\tl_if_head_eq_catcode:nNTF`. This function is documented on page 48.)

```

\tl_lower_case:n The user level functions here are all wrappers around the internal functions for case
\tl_upper_case:n changing.
\tl_mixed_case:n
23349 \cs_new:Npn \tl_lower_case:n { \_tl_change_case:nnn { lower } { } }
23350 \cs_new:Npn \tl_upper_case:n { \_tl_change_case:nnn { upper } { } }
23351 \cs_new:Npn \tl_mixed_case:n { \_tl_change_case:nnn { mixed } { } }
23352 \cs_new:Npn \tl_lower_case:nn { \_tl_change_case:nnn { lower } }
23353 \cs_new:Npn \tl_upper_case:nn { \_tl_change_case:nnn { upper } }
23354 \cs_new:Npn \tl_mixed_case:nn { \_tl_change_case:nnn { mixed } }

```

(End definition for `\tl_lower_case:n` and others. These functions are documented on page 248.)

```

\__tl_change_case:nnn
\__tl_change_case_aux:nnn
\__tl_change_case_loop:wnn
\__tl_change_case_output:nwn
\__tl_change_case_output:Vwn
\__tl_change_case_output:own
\__tl_change_case_output:vwn
\__tl_change_case_output:fwN
\__tl_change_case_end:wn
\__tl_change_case_group:nwnn
\__tl_change_case_group_lower:nnnn
\__tl_change_case_group_upper:nnnn
\__tl_change_case_group_mixed:nnnn
\__tl_change_case_space:wnn
\__tl_change_case_N_type:Nwnn
\__tl_change_case_N_type:NNNnnn
\__tl_change_case_math:NNNnnn
\__tl_change_case_math_loop:wNwnn
\__tl_change_case_math:NwNwnn
\__tl_change_case_math_group:nwNwnn
\__tl_change_case_math_space:wNwnn
\__tl_change_case_N_type:Nnnn
\__tl_change_case_char_lower:Nnn
\__tl_change_case_char_upper:Nnn
\__tl_change_case_char_mixed:Nnn
\__tl_change_case_char:nN
\__tl_change_case_char_auxi:nN
\__tl_change_case_char_auxii:nN
\__tl_change_case_char_mixed:N
\__tl_change_case_char_lower:N
\__tl_change_case_char_upper:N
\__tl_lookup_mixed:N
\__tl_lookup_lower:N
\__tl_lookup_upper:N
\__tl_change_case_char_UTFviii:nN
\__tl_change_case_char_UTFviii:nnN
\__tl_change_case_char_UTFviii:nnN
\__tl_change_case_char_UTFviii:nnN
\__tl_change_case_cs_letterlike:NnN
\__tl_change_case_cs_accents:NN
\__tl_change_case_cs:N
\__tl_change_case_cs:NN
\__tl_change_case_cs:NNn
\__tl_change_case_protect:wNn
\__tl_change_case_if_expandable:NTF
\__tl_change_case_cs_expand:NwN
\__tl_change_case_cs_expand:NN
\__tl_change_case_mixed_skip:N
\__tl_change_case_mixed_skip:NN
\__tl_change_case_mixed_skip_tidy:Nwn
\__tl_change_case_mixed_switch:w

```

The mechanism for the core conversion of case is based on the idea that we can use a loop to grab the entire token list plus a quark: the latter is used as an end marker and to avoid any brace stripping. Depending on the nature of the first item in the grabbed argument, it can either be processed as a single token, treated as a group or treated as a space. These different cases all work by re-reading #1 in the appropriate way, hence the repetition of #1 \q_recursion_stop.

```

23355 \cs_new:Npn \__tl_change_case:nnn #1#2#3
23356 {
23357   \etex_unexpanded:D \exp_after:wN
23358   {
23359     \exp:w
23360     \__tl_change_case_aux:nnn {#1} {#2} {#3}
23361   }
23362 }
23363 \cs_new:Npn \__tl_change_case_aux:nnn #1#2#3
23364 {
23365   \group_align_safe_begin:
23366   \__tl_change_case_loop:wnn
23367   #3 \q_recursion_tail \q_recursion_stop {#1} {#2}
23368   \__tl_change_case_result:n { }
23369 }
23370 \cs_new:Npn \__tl_change_case_loop:wnn #1 \q_recursion_stop
23371 {
23372   \tl_if_head_is_N_type:nTF {#1}
23373   { \__tl_change_case_N_type:Nwnn }
23374   {
23375     \tl_if_head_is_group:nTF {#1}
23376     { \__tl_change_case_group:nwnn }
23377     { \__tl_change_case_space:wnn }
23378   }
23379   #1 \q_recursion_stop
23380 }

```

Earlier versions of the code where only x-type expandable rather than f-type: this causes issues with nesting and so the slight performance hit is taken for a better outcome in usability terms. Setting up for f-type expandability has two requirements: a marker token after the main loop (see above) and a mechanism to “load” and finalise the result. That is handled in the code below, which includes the necessary material to end the \exp:w expansion.

```

23381 \cs_new:Npn \__tl_change_case_output:nwn #1#2 \__tl_change_case_result:n #3
23382 { #2 \__tl_change_case_result:n { #3 #1 } }
23383 \cs_generate_variant:Nn \__tl_change_case_output:nwn { V , o , v , f }
23384 \cs_new:Npn \__tl_change_case_end:wn #1 \__tl_change_case_result:n #2
23385 {
23386   \group_align_safe_end:
23387   \exp_end:
23388   #2
23389 }

```

Handling for the cases where the current argument is a brace group or a space is relatively easy. For the brace case, the routine works recursively, using the expandability of the mechanism to ensure that the result is finalised before storage. For the space case it is simply a question of removing the space in the input and storing it in the output. In

both cases, and indeed for the N-type grabber, after removing the current item from the input `__tl_change_case_loop:wnn` is inserted in front of the remaining tokens.

```

23390 \cs_new:Npn \__tl_change_case_group:nwnn #1#2 \q_recursion_stop #3#4
23391 {
23392   \use:c { __tl_change_case_group_ #3 : nnnn } {#1} {#2} {#3} {#4}
23393 }
23394 \cs_new:Npn \__tl_change_case_group_lower:nnnn #1#2#3#4
23395 {
23396   \__tl_change_case_output:own
23397   {
23398     \exp_after:wN
23399     {
23400       \exp:w
23401       \__tl_change_case_aux:nnn {#3} {#4} {#1}
23402     }
23403   }
23404   \__tl_change_case_loop:wnn #2 \q_recursion_stop {#3} {#4}
23405 }
23406 \cs_new_eq:NN \__tl_change_case_group_upper:nnnn
23407   \__tl_change_case_group_lower:nnnn

```

For the “mixed” case, a group is taken as forcing a switch to lower casing. That means we need a separate auxiliary. (Tracking whether we have found a first character inside a group and transferring the information out looks pretty horrible.)

```

23408 \cs_new:Npn \__tl_change_case_group_mixed:nnnn #1#2#3#4
23409 {
23410   \__tl_change_case_output:own
23411   {
23412     \exp_after:wN
23413     {
23414       \exp:w
23415       \__tl_change_case_aux:nnn {#3} {#4} {#1}
23416     }
23417   }
23418   \__tl_change_case_loop:wnn #2 \q_recursion_stop { lower } {#4}
23419 }
23420 \exp_last_unbraced:NNo \cs_new:Npn \__tl_change_case_space:wnn \c_space_tl
23421 {
23422   \__tl_change_case_output:nwn { ~ }
23423   \__tl_change_case_loop:wnn
23424 }

```

For N-type arguments there are several stages to the approach. First, a simply check for the end-of-input marker, which if found triggers the final clean up and output step. Assuming that is not the case, the first check is for math-mode escaping: this test can encompass control sequences or other N-type tokens so is handled up front.

```

23425 \cs_new:Npn \__tl_change_case_N_type:Nwnn #1#2 \q_recursion_stop
23426 {
23427   \quark_if_recursion_tail_stop_do:Nn #1
23428   { \__tl_change_case_end:wn }
23429   \exp_after:wN \__tl_change_case_N_type:NNNnnn
23430   \exp_after:wN #1 \l_tl_change_math_tl
23431   \q_recursion_tail ? \q_recursion_stop {#2}
23432 }

```

Looking for math mode escape first requires a loop over the possible token pairs to see if the current input (#1) matches an open-math case (#2). If it does then this test loop is ended and a new input-gathering one is begun. The latter simply transfers material from the input to the output without any expansion, testing each N-type token to see if it matches the close-math case required. If that is the situation then the “math loop” stops and resumes the main loop: as that might be either the standard case-changing one or the mixed-case alternative, it is not hard-coded into the math loop but is rather passed as argument #3 to `_tl_change_case_math:NNNnnn`. If no close-math token is found then the final clean-up is forced (*i.e.* there is no assumption of “well-behaved” input in terms of math mode).

```

23433 \cs_new:Npn \_tl\_change\_case\_N\_type:NNNnnn #1#2#3
23434 {
23435   \quark\_if\_recursion\_tail\_stop\_do:Nn #2
23436   { \_tl\_change\_case\_N\_type:Nnnn #1 }
23437   \token\_if\_eq\_meaning:NNTF #1 #2
23438   {
23439     \use\_i\_delimit\_by\_q\_recursion\_stop:nw
23440     {
23441       \_tl\_change\_case\_math:NNNnnn
23442       #1 #3 \_tl\_change\_case\_loop:wnn
23443     }
23444   }
23445   { \_tl\_change\_case\_N\_type:NNNnnn #1 }
23446 }
23447 \cs\_new:Npn \_tl\_change\_case\_math:NNNnnn #1#2#3#4
23448 {
23449   \_tl\_change\_case\_output:nwn {#1}
23450   \_tl\_change\_case\_math\_loop:wNNnn #4 \q\_recursion\_stop #2 #3
23451 }
23452 \cs\_new:Npn \_tl\_change\_case\_math\_loop:wNNnn #1 \q\_recursion\_stop
23453 {
23454   \tl\_if\_head\_is\_N\_type:nTF {#1}
23455   { \_tl\_change\_case\_math:NwNNnn }
23456   {
23457     \tl\_if\_head\_is\_group:nTF {#1}
23458     { \_tl\_change\_case\_math\_group:nwNNnn }
23459     { \_tl\_change\_case\_math\_space:wNNnn }
23460   }
23461   #1 \q\_recursion\_stop
23462 }
23463 \cs\_new:Npn \_tl\_change\_case\_math:NwNNnn #1#2 \q\_recursion\_stop #3#4
23464 {
23465   \token\_if\_eq\_meaning:NNTF \q\_recursion\_tail #1
23466   { \_tl\_change\_case\_end:wn }
23467   {
23468     \_tl\_change\_case\_output:nwn {#1}
23469     \token\_if\_eq\_meaning:NNTF #1 #3
23470     { #4 #2 \q\_recursion\_stop }
23471     { \_tl\_change\_case\_math\_loop:wNNnn #2 \q\_recursion\_stop #3#4 }
23472   }
23473 }
23474 \cs\_new:Npn \_tl\_change\_case\_math\_group:nwNNnn #1#2 \q\_recursion\_stop
23475 {

```

```

23476     \_tl_change_case_output:nwn { {#1} }
23477     \_tl_change_case_math_loop:wNNnn #2 \q_recursion_stop
23478   }
23479 \exp_last_unbraced:NNo
23480 \cs_new:Npn \_tl_change_case_math_space:wNNnn \c_space_tl
23481 {
23482     \_tl_change_case_output:nwn { ~ }
23483     \_tl_change_case_math_loop:wNNnn
23484 }

```

Once potential math-mode cases are filtered out the next stage is to test if the token grabbed is a control sequence: they cannot be used in the lookup table and also may require expansion. At this stage the loop code starting `_tl_change_case_loop:wnn` is inserted: all subsequent steps in the code which need a look-ahead are coded to rely on this and thus have w-type arguments if they may do a look-ahead.

```

23485 \cs_new:Npn \_tl_change_case_N_type:Nnnn #1#2#3#4
23486 {
23487     \token_if_cs:NTF #1
23488     { \_tl_change_case_cs_letterlike:Nn #1 {#3} }
23489     { \use:c { \_tl_change_case_char_ #3 :Nnn } #1 {#3} {#4} }
23490     \_tl_change_case_loop:wnn #2 \q_recursion_stop {#3} {#4}
23491 }

```

For character tokens there are some special cases to deal with then the majority of changes are covered by using the `TeX` data as a lookup along with expandable character generation. This avoids needing a very large number of macros or (as seen in earlier versions) a somewhat tricky split of the characters into various blocks. Notice that the special case code may do a look-ahead so requires a final w-type argument whereas the core lookup table does not and also guarantees an output so f-type expansion may be used to obtain the case-changed result.

```

23492 \cs_new:Npn \_tl_change_case_char_lower:Nnn #1#2#3
23493 {
23494     \cs_if_exist_use:cF { \_tl_change_case_ #2 _ #3 :Nnw }
23495     { \use_ii:nn }
23496     #1
23497     {
23498         \use:c { \_tl_change_case_ #2 _ sigma:Nnw } #1
23499         { \_tl_change_case_char:nN {#2} #1 }
23500     }
23501 }
23502 \cs_new_eq:NN \_tl_change_case_char_upper:Nnn
23503 \_tl_change_case_char_lower:Nnn

```

For mixed case, the code is somewhat different: there is a need to look up both mixed and upper case chars and we have to cover the situation where there is a character to skip over.

```

23504 \cs_new:Npn \_tl_change_case_char_mixed:Nnn #1#2#3
23505 {
23506     \_tl_change_case_mixed_switch:w
23507     \cs_if_exist_use:cF { \_tl_change_case_mixed_ #3 :Nnw }
23508     {
23509         \cs_if_exist_use:cF { \_tl_change_case_upper_ #3 :Nnw }
23510         { \use_ii:nn }
23511     }

```

```

23512         #1
23513         { \__tl_change_case_mixed_skip:N #1 }
23514     }

```

For Unicode engines we can handle all characters directly. However, for the 8-bit engines the aim is to deal with (a subset of) Unicode (UTF-8) input. They deal with that by making the upper half of the range active, so we look for that and if found work out how many UTF-8 octets there are to deal with. Those can then be grabbed to reconstruct the full Unicode character, which is then used in a lookup. (As will become obvious below, there is no intention here of covering all of Unicode.)

```

23515 \cs_if_exist:NTF \utex_char:D
23516 {
23517     \cs_new:Npn \__tl_change_case_char:nN #1#2
23518     { \__tl_change_case_char_auxi:nN {#1} #2 }
23519 }
23520 {
23521     \cs_new:Npn \__tl_change_case_char:nN #1#2
23522     {
23523         \int_compare:nNnTF { '#2 } > { "80 }
23524         {
23525             \int_compare:nNnTF { '#2 } < { "EO }
23526             { \__tl_change_case_char_UTFviii:nNNN {#1} #2 }
23527             {
23528                 \int_compare:nNnTF { '#2 } < { "FO }
23529                 { \__tl_change_case_char_UTFviii:nNNNN {#1} #2 }
23530                 { \__tl_change_case_char_UTFviii:nNNNNN {#1} #2 }
23531             }
23532         }
23533         { \__tl_change_case_char_auxi:nN {#1} #2 }
23534     }
23535 }

```

To allow for the special case of mixed case, we insert here a action-dependent auxiliary.

```

23536 \cs_new:Npn \__tl_change_case_char_auxi:nN #1#2
23537 { \use:c { __tl_change_case_char_ #1 :N } #2 }
23538 \cs_new:Npn \__tl_change_case_char_lower:N #1
23539 {
23540     \__tl_change_case_output:fwn
23541     {
23542         \cs_if_exist_use:cF { c__unicode_lower_ \token_to_str:N #1 _tl }
23543         { \__tl_change_case_char_auxii:nN { lower } #1 }
23544     }
23545 }
23546 \cs_new:Npn \__tl_change_case_char_upper:N #1
23547 {
23548     \__tl_change_case_output:fwn
23549     {
23550         \cs_if_exist_use:cF { c__unicode_upper_ \token_to_str:N #1 _tl }
23551         { \__tl_change_case_char_auxii:nN { upper } #1 }
23552     }
23553 }
23554 \cs_new:Npn \__tl_change_case_char_mixed:N #1
23555 {
23556     \cs_if_exist:cTF { c__unicode_mixed_ \token_to_str:N #1 _tl }

```

```

23557     {
23558         \__tl_change_case_output:fwn
23559         { \tl_use:c { c__unicode_mixed_ \token_to_str:N #1 _tl } }
23560     }
23561     { \__tl_change_case_char_upper:N #1 }
23562 }
23563 \cs_if_exist:NTF \utex_char:D
23564 {
23565     \cs_new:Npn \__tl_change_case_char_auxii:nN #1#2
23566     {
23567         \int_compare:nNnTF { \use:c { __tl_lookup_ #1 :N } #2 } = { 0 }
23568         { \exp_stop_f: #2 }
23569         {
23570             \char_generate:nn
23571             { \use:c { __tl_lookup_ #1 :N } #2 }
23572             { \char_value_catcode:n { \use:c { __tl_lookup_ #1 :N } #2 } }
23573         }
23574     }
23575     \cs_new_protected:Npn \__tl_lookup_lower:N #1 { \tex_lccode:D ‘#1 }
23576     \cs_new_protected:Npn \__tl_lookup_upper:N #1 { \tex_uccode:D ‘#1 }
23577     \cs_new_eq:NN \__tl_lookup_mixed:N \__tl_lookup_upper:N
23578 }
23579 {
23580     \cs_new:Npn \__tl_change_case_char_auxii:nN #1#2 { \exp_stop_f: #2 }
23581     \cs_new:Npn \__tl_change_case_char_UTFviii:nNNN #1#2#3#4
23582     { \__tl_change_case_char_UTFviii:nnN {#1} {#2#4} #3 }
23583     \cs_new:Npn \__tl_change_case_char_UTFviii:nNNNN #1#2#3#4#5
23584     { \__tl_change_case_char_UTFviii:nnN {#1} {#2#4#5} #3 }
23585     \cs_new:Npn \__tl_change_case_char_UTFviii:nNNNNN #1#2#3#4#5#6
23586     { \__tl_change_case_char_UTFviii:nnN {#1} {#2#4#5#6} #3 }
23587     \cs_new:Npn \__tl_change_case_char_UTFviii:nnN #1#2#3
23588     {
23589         \cs_if_exist:cTF { c__unicode_ #1 _ \tl_to_str:n {#2} _tl }
23590         {
23591             \__tl_change_case_output:vwn
23592             { c__unicode_ #1 _ \tl_to_str:n {#2} _tl }
23593         }
23594         { \__tl_change_case_output:nwn {#2} }
23595     } #3
23596 }
23597 }

```

Before dealing with general control sequences there are the special ones to deal with. Letter-like control sequences are a simple look-up, while for accents the loop is much as done elsewhere. Notice that we have a no-op test to make sure there is no unexpected expansion of letter-like input. The split into two parts here allows us to insert the “switch” code for mixed casing.

```

23598 \cs_new:Npn \__tl_change_case_cs_letterlike:Nn #1#2
23599 {
23600     \str_if_eq:nnTF {#2} { mixed }
23601     {
23602         \__tl_change_case_cs_letterlike:NnN #1 { upper }
23603         \__tl_change_case_mixed_switch:w
23604     }

```

```

23605     { \_tl_change_case_cs_letterlike:NnN #1 {#2} \prg_do_nothing: }
23606   }
23607 \cs_new:Npn \_tl_change_case_cs_letterlike:NnN #1#2#3
23608 {
23609   \cs_if_exist:cTF { c\_tl_change_case_ #2 _ \token_to_str:N #1 _tl }
23610   {
23611     \_tl_change_case_output:vwN
23612     { c\_tl_change_case_ #2 _ \token_to_str:N #1 _tl }
23613     #3
23614   }
23615   {
23616     \cs_if_exist:cTF
23617     {
23618       c\_tl_change_case_
23619       \str_if_eq:nnTF {#2} { lower } { upper } { lower }
23620       _ \token_to_str:N #1 _tl
23621     }
23622     {
23623       \_tl_change_case_output:nwN {#1}
23624       #3
23625     }
23626     {
23627       \exp_after:wN \_tl_change_case_cs_accents:NN
23628       \exp_after:wN #1 \l_tl_case_change_accents_tl
23629       \q_recursion_tail \q_recursion_stop
23630     }
23631   }
23632 }
23633 \cs_new:Npn \_tl_change_case_cs_accents:NN #1#2
23634 {
23635   \quark_if_recursion_tail_stop_do:Nn #2
23636   { \_tl_change_case_cs:N #1 }
23637   \str_if_eq:nnTF {#1} {#2}
23638   {
23639     \use_i_delimit_by_q_recursion_stop:nw
23640     { \_tl_change_case_output:nwN {#1} }
23641   }
23642   { \_tl_change_case_cs_accents:NN #1 }
23643 }

```

To deal with a control sequence there is first a need to test if it is on the list which indicate that case changing should be skipped. That's done using a loop as for the other special cases. If a hit is found then the argument is grabbed: that comes *after* the loop function which is therefore rearranged. In a L^AT_EX 2_ε context, `\protect` needs to be treated specially, to prevent expansion of the next token but output it without braces.

```

23644 \cs_new:Npn \_tl_change_case_cs:N #1
23645 {
23646   \*package>
23647   \str_if_eq:nnTF {#1} { \protect } { \_tl_change_case_protect:wNN }
23648   </package>
23649   \exp_after:wN \_tl_change_case_cs:NN
23650   \exp_after:wN #1 \l_tl_case_change_exclude_tl
23651   \q_recursion_tail \q_recursion_stop
23652 }

```

```

23653 \cs_new:Npn \__tl_change_case_cs:NN #1#2
23654 {
23655   \quark_if_recursion_tail_stop_do:Nn #2
23656   {
23657     \__tl_change_case_cs_expand:Nnw #1
23658     { \__tl_change_case_output:nwn {#1} }
23659   }
23660   \str_if_eq:nnTF {#1} {#2}
23661   {
23662     \use_i_delimit_by_q_recursion_stop:nw
23663     { \__tl_change_case_cs:NNn #1 }
23664   }
23665   { \__tl_change_case_cs:NN #1 }
23666 }
23667 \cs_new:Npn \__tl_change_case_cs:NNn #1#2#3
23668 {
23669   \__tl_change_case_output:nwn { #1 {#3} }
23670   #2
23671 }
23672 \*package>
23673 \cs_new:Npn \__tl_change_case_protect:wNN #1 \q_recursion_stop #2 #3
23674 { \__tl_change_case_output:nwn { \protect #3 } #2 }
23675 \</package>

```

When a control sequence is not on the exclude list the other test if to see if it is expandable. Once again, if there is a hit then the loop function is grabbed as part of the clean-up and reinserted before the now expanded material. The test for expandability has to check for end-of-recursion as it is needed by the look-ahead code which might hit the end of the input. The test is done in two parts as `\bool_if:nTF` would choke if #1 was (!

```

23676 \cs_new:Npn \__tl_change_case_if_expandable:NNTF #1
23677 {
23678   \token_if_expandable:NNTF #1
23679   {
23680     \bool_lazy_any:nTF
23681     {
23682       { \token_if_eq_meaning_p:NN \q_recursion_tail #1 }
23683       { \token_if_protected_macro_p:N #1 }
23684       { \token_if_protected_long_macro_p:N #1 }
23685     }
23686     { \use_ii:nn }
23687     { \use_i:nn }
23688   }
23689   { \use_ii:nn }
23690 }
23691 \cs_new:Npn \__tl_change_case_cs_expand:Nnw #1#2
23692 {
23693   \__tl_change_case_if_expandable:NNTF #1
23694   { \__tl_change_case_cs_expand:NN #1 }
23695   { #2 }
23696 }
23697 \cs_new:Npn \__tl_change_case_cs_expand:NN #1#2
23698 { \exp_after:wN #2 #1 }

```

For mixed case, there is an additional list of exceptions to deal with: once that is sorted,

we can move on back to the main loop.

```

23699 \cs_new:Npn \__tl_change_case_mixed_skip:N #1
23700 {
23701   \exp_after:wN \__tl_change_case_mixed_skip:NN
23702   \exp_after:wN #1 \l_tl_mixed_case_ignore_tl
23703   \q_recursion_tail \q_recursion_stop
23704 }
23705 \cs_new:Npn \__tl_change_case_mixed_skip:NN #1#2
23706 {
23707   \quark_if_recursion_tail_stop_do:nn {#2}
23708   { \__tl_change_case_char:nN { mixed } #1 }
23709   \int_compare:nNnT { '#1 } = { '#2 }
23710   {
23711     \use_i_delimit_by_q_recursion_stop:nw
23712     {
23713       \__tl_change_case_output:nwn {#1}
23714       \__tl_change_case_mixed_skip_tidy:Nwn
23715     }
23716   }
23717   \__tl_change_case_mixed_skip:NN #1
23718 }
23719 \cs_new:Npn \__tl_change_case_mixed_skip_tidy:Nwn #1#2 \q_recursion_stop #3
23720 {
23721   \__tl_change_case_loop:wnn #2 \q_recursion_stop { mixed }
23722 }

```

Needed to switch from mixed to lower casing when we have found a first character in the former mode.

```

23723 \cs_new:Npn \__tl_change_case_mixed_switch:w
23724   #1 \__tl_change_case_loop:wnn #2 \q_recursion_stop #3
23725 {
23726   #1
23727   \__tl_change_case_loop:wnn #2 \q_recursion_stop { lower }
23728 }

```

(End definition for __tl_change_case:nnn and others.)

__tl_change_case_lower_sigma:Nnw If the current char is an upper case sigma, the a check is made on the next item in the input. If it is N-type and not a control sequence then there is a look-ahead phase.

```

\__tl_change_case_lower_sigma:w
\__tl_change_case_lower_sigma:Nw
\__tl_change_case_upper_sigma:Nnw
23729 \cs_new:Npn \__tl_change_case_lower_sigma:Nnw #1#2#3#4 \q_recursion_stop
23730 {
23731   \int_compare:nNnTF { '#1 } = { "03A3 }
23732   {
23733     \__tl_change_case_output:fwn
23734     { \__tl_change_case_lower_sigma:w #4 \q_recursion_stop }
23735   }
23736   {#2}
23737   #3 #4 \q_recursion_stop
23738 }
23739 \cs_new:Npn \__tl_change_case_lower_sigma:w #1 \q_recursion_stop
23740 {
23741   \tl_if_head_is_N_type:nTF {#1}
23742   { \__tl_change_case_lower_sigma:Nw #1 \q_recursion_stop }
23743   { \c__unicode_final_sigma_tl }

```



```

23744 }
23745 \cs_new:Npn \__tl_change_case_lower_sigma:Nw #1#2 \q_recursion_stop
23746 {
23747   \__tl_change_case_if_expandable:NTF #1
23748   {
23749     \exp_after:wN \__tl_change_case_lower_sigma:w #1
23750     #2 \q_recursion_stop
23751   }
23752   {
23753     \token_if_letter:NTF #1
23754     { \c__unicode_std_sigma_tl }
23755     { \c__unicode_final_sigma_tl }
23756   }
23757 }

```

Simply skip to the final step for upper casing.

```

23758 \cs_new_eq:NN \__tl_change_case_upper_sigma:Nnw \use_ii:nn

```

(End definition for __tl_change_case_lower_sigma:Nnw and others.)

```

\__tl_change_case_lower_tr:Nnw
\__tl_change_case_lower_tr_auxi:Nw
\__tl_change_case_lower_tr_auxii:Nw
\__tl_change_case_upper_tr:Nnw
\__tl_change_case_lower_az:Nnw
\__tl_change_case_upper_az:Nnw

```

The Turkic languages need special treatment for dotted-i and dotless-i. The lower casing rule can be expressed in terms of searching first for either a dotless-I or a dotted-I. In the latter case the mapping is easy, but in the former there is a second stage search.

```

23759 \cs_if_exist:NTF \utex_char:D
23760 {
23761   \cs_new:Npn \__tl_change_case_lower_tr:Nnw #1#2
23762   {
23763     \int_compare:nNnTF { '#1 } = { "0049 }
23764     { \__tl_change_case_lower_tr_auxi:Nw }
23765     {
23766       \int_compare:nNnTF { '#1 } = { "0130 }
23767       { \__tl_change_case_output:nwn { i } }
23768       { #2 }
23769     }
23770   }

```

After a dotless-I there may be a dot-above character. If there is then a dotted-i should be produced, otherwise output a dotless-i. When the combination is found both the dotless-I and the dot-above char have to be removed from the input, which is done by the \use_i:nn (it grabs __tl_change_case_loop:wn and the dot-above char and discards the latter).

```

23771 \cs_new:Npn \__tl_change_case_lower_tr_auxi:Nw #1#2 \q_recursion_stop
23772 {
23773   \tl_if_head_is_N_type:nTF {#2}
23774   { \__tl_change_case_lower_tr_auxii:Nw #2 \q_recursion_stop }
23775   { \__tl_change_case_output:Vwn \c__unicode_dotless_i_tl }
23776   #1 #2 \q_recursion_stop
23777 }
23778 \cs_new:Npn \__tl_change_case_lower_tr_auxii:Nw #1#2 \q_recursion_stop
23779 {
23780   \__tl_change_case_if_expandable:NTF #1
23781   {
23782     \exp_after:wN \__tl_change_case_lower_tr_auxi:Nw #1
23783     #2 \q_recursion_stop
23784   }

```

```

23785     {
23786         \bool_lazy_or:nnTF
23787         { \token_if_cs_p:N #1 }
23788         { ! \int_compare_p:nNn { '#1 } = { "0307 } }
23789         { \__tl_change_case_output:Vwn \c__unicode_dotless_i_tl }
23790         {
23791             \__tl_change_case_output:nwn { i }
23792             \use_i:nn
23793         }
23794     }
23795 }
23796 }

```

For 8-bit engines, dot-above is not available so there is a simple test for an upper-case I. Then we can look for the UTF-8 representation of an upper case dotted-I without the combining char. If it's not there, preserve the UTF-8 sequence as-is.

```

23797 {
23798     \cs_new:Npn \__tl_change_case_lower_tr:Nnw #1#2
23799     {
23800         \int_compare:nNnTF { '#1 } = { "0049 }
23801         { \__tl_change_case_output:Vwn \c__unicode_dotless_i_tl }
23802         {
23803             \int_compare:nNnTF { '#1 } = { 196 }
23804             { \__tl_change_case_lower_tr_auxi:Nw #1 {#2} }
23805             {#2}
23806         }
23807     }
23808     \cs_new:Npn \__tl_change_case_lower_tr_auxi:Nw #1#2#3#4
23809     {
23810         \int_compare:nNnTF { '#4 } = { 176 }
23811         {
23812             \__tl_change_case_output:nwn { i }
23813             #3
23814         }
23815         {
23816             #2
23817             #3 #4
23818         }
23819     }
23820 }

```

Upper casing is easier: just one exception with no context.

```

23821 \cs_new:Npn \__tl_change_case_upper_tr:Nnw #1#2
23822 {
23823     \int_compare:nNnTF { '#1 } = { "0069 }
23824     { \__tl_change_case_output:Vwn \c__unicode_dotted_I_tl }
23825     {#2}
23826 }

```

Straight copies.

```

23827 \cs_new_eq:NN \__tl_change_case_lower_az:Nnw \__tl_change_case_lower_tr:Nnw
23828 \cs_new_eq:NN \__tl_change_case_upper_az:Nnw \__tl_change_case_upper_tr:Nnw

```

(End definition for __tl_change_case_lower_tr:Nnw and others.)

`_tl_change_case_lower_lt:Nnw` For Lithuanian, the issue to be dealt with is dots over lower case letters: these should
`_tl_change_case_lower_lt:nNnw` be present if there is another accent. That means that there is some work to do when
`_tl_change_case_lower_lt:nnw` lower casing I and J. The first step is a simple match attempt: `\c__tl_accents_lt_tl`
`_tl_change_case_lower_lt:Nw` contains accented upper case letters which should gain a dot-above char in their lower
`_tl_change_case_lower_lt:NNw` case form. This is done using f-type expansion so only one pass is needed to find if it
`_tl_change_case_upper_lt:Nnw` works or not. If there was no hit, the second stage is to check for I, J and I-ogonek, and
`_tl_change_case_upper_lt:nnw` if the current char is a match to look for a following accent.
`_tl_change_case_upper_lt:Nw`
`_tl_change_case_upper_lt:NNw`

```

23829 \cs_new:Npn \_tl_change_case_lower_lt:Nnw #1
23830 {
23831   \exp_args:Nf \_tl_change_case_lower_lt:nNnw
23832   { \str_case:nVF #1 \c__unicode_accents_lt_tl \exp_stop_f: }
23833   #1
23834 }
23835 \cs_new:Npn \_tl_change_case_lower_lt:nNnw #1#2
23836 {
23837   \tl_if_blank:nTF {#1}
23838   {
23839     \exp_args:Nf \_tl_change_case_lower_lt:nnw
23840     {
23841       \int_case:nnF {#2}
23842       {
23843         { "0049 } i
23844         { "004A } j
23845         { "012E } \c__unicode_i_ogonek_tl
23846       }
23847       \exp_stop_f:
23848     }
23849   }
23850   {
23851     \_tl_change_case_output:wnw {#1}
23852     \use_none:n
23853   }
23854 }
23855 \cs_new:Npn \_tl_change_case_lower_lt:nnw #1#2
23856 {
23857   \tl_if_blank:nTF {#1}
23858   {#2}
23859   {
23860     \_tl_change_case_output:wnw {#1}
23861     \_tl_change_case_lower_lt:Nw
23862   }
23863 }

```

Grab the next char and see if it is one of the accents used in Lithuanian: if it is, add the dot-above char into the output.

```

23864 \cs_new:Npn \_tl_change_case_lower_lt:Nw #1#2 \q_recursion_stop
23865 {
23866   \tl_if_head_is_N_type:nT {#2}
23867   { \_tl_change_case_lower_lt:NNw }
23868   #1 #2 \q_recursion_stop
23869 }
23870 \cs_new:Npn \_tl_change_case_lower_lt:NNw #1#2#3 \q_recursion_stop
23871 {
23872   \_tl_change_case_if_expandable:NTF #2

```

```

23873     {
23874         \exp_after:wN \_tl_change_case_lower_lt:Nw \exp_after:wN #1 #2
23875         #3 \q_recursion_stop
23876     }
23877     {
23878         \bool_lazy_and:nnT
23879         { ! \token_if_cs_p:N #2 }
23880         {
23881             \bool_lazy_any_p:n
23882             {
23883                 { \int_compare_p:nNn { '#2 } = { "0300 } }
23884                 { \int_compare_p:nNn { '#2 } = { "0301 } }
23885                 { \int_compare_p:nNn { '#2 } = { "0303 } }
23886             }
23887         }
23888         { \_tl_change_case_output:Vwn \c__unicode_dot_above_tl }
23889         #1 #2#3 \q_recursion_stop
23890     }
23891 }

```

For upper casing, the test required is for a dot-above char after an I, J or I-ogonek. First a test for the appropriate letter, and if found a look-ahead and potentially one token dropped.

```

23892 \cs_new:Npn \_tl_change_case_upper_lt:Nnw #1
23893 {
23894     \exp_args:Nf \_tl_change_case_upper_lt:nnw
23895     {
23896         \int_case:nnF { '#1 }
23897         {
23898             { "0069 } I
23899             { "006A } J
23900             { "012F } \c__unicode_I_ogonek_tl
23901         }
23902         \exp_stop_f:
23903     }
23904 }
23905 \cs_new:Npn \_tl_change_case_upper_lt:nnw #1#2
23906 {
23907     \tl_if_blank:nTF {#1}
23908     {#2}
23909     {
23910         \_tl_change_case_output:wnw {#1}
23911         \_tl_change_case_upper_lt:Nw
23912     }
23913 }
23914 \cs_new:Npn \_tl_change_case_upper_lt:Nw #1#2 \q_recursion_stop
23915 {
23916     \tl_if_head_is_N_type:nT {#2}
23917     { \_tl_change_case_upper_lt:NNw }
23918     #1 #2 \q_recursion_stop
23919 }
23920 \cs_new:Npn \_tl_change_case_upper_lt:NNw #1#2#3 \q_recursion_stop
23921 {
23922     \_tl_change_case_if_expandable:NTF #2

```

```

23923     {
23924         \exp_after:wN \_tl_change_case_upper_lt:Nw \exp_after:wN #1 #2
23925         #3 \q_recursion_stop
23926     }
23927     {
23928         \bool_lazy_and:nnTF
23929         { ! \token_if_cs_p:N #2 }
23930         { \int_compare_p:nNn { '#2 } = { "0307 } }
23931         { #1 }
23932         { #1 #2 }
23933         #3 \q_recursion_stop
23934     }
23935 }

```

(End definition for _tl_change_case_lower_lt:Nnw and others.)

_tl_change_case_upper_de-alt:Nnw A simple alternative version for German.

```

23936 \cs_new:cpn { \_tl_change_case_upper_de-alt:Nnw } #1#2
23937 {
23938     \int_compare:nNnTF { '#1 } = { 223 }
23939     { \_tl_change_case_output:Vwn \c__unicode_upper_Eszett_tl }
23940     {#2}
23941 }

```

(End definition for _tl_change_case_upper_de-alt:Nnw.)

_unicode_codepoint_to_UTFviii:n This code converts a codepoint into the correct UTF-8 representation. As there are a variable number of octets, the result starts with the numeral 1–4 to indicate the nature of the returned value. Note that this code covers the full range even though at this stage it is not required here. Also note that longer-term this is likely to need a public interface and/or moving to l3str (see experimental string conversions). In terms of the algorithm itself, see <https://en.wikipedia.org/wiki/UTF-8> for the octet pattern.

```

23942 \cs_new:Npn \_unicode_codepoint_to_UTFviii:n #1
23943 {
23944     \exp_args:Nf \_unicode_codepoint_to_UTFviii_auxi:n
23945     { \int_eval:n {#1} }
23946 }
23947 \cs_new:Npn \_unicode_codepoint_to_UTFviii_auxi:n #1
23948 {
23949     \if_int_compare:w #1 > "80 ~
23950     \if_int_compare:w #1 < "800 ~
23951     2
23952     \_unicode_codepoint_to_UTFviii_auxii:Nnn C {#1} { 64 }
23953     \_unicode_codepoint_to_UTFviii_auxiii:n {#1}
23954     \else:
23955     \if_int_compare:w #1 < "10000 ~
23956     3
23957     \_unicode_codepoint_to_UTFviii_auxii:Nnn E {#1} { 64 * 64 }
23958     \_unicode_codepoint_to_UTFviii_auxiii:n {#1}
23959     \_unicode_codepoint_to_UTFviii_auxiii:n
23960     { \int_div_truncate:nn {#1} { 64 } }
23961     \else:
23962     4
23963     \_unicode_codepoint_to_UTFviii_auxii:Nnn F

```

```

23964         {#1} { 64 * 64 * 64 }
23965     \__unicode_codepoint_to_UTFviii_auxiii:n
23966     { \int_div_truncate:nn {#1} { 64 * 64 } }
23967     \__unicode_codepoint_to_UTFviii_auxiii:n
23968     { \int_div_truncate:nn {#1} { 64 } }
23969     \__unicode_codepoint_to_UTFviii_auxiii:n {#1}
23970
23971     \fi:
23972     \fi:
23973     \else:
23974         1 {#1}
23975     \fi:
23976 }
23977 \cs_new:Npn \__unicode_codepoint_to_UTFviii_auxii:Nnn #1#2#3
23978 { { \int_eval:n { "#10 + \int_div_truncate:nn {#2} {#3} } } }
23979 \cs_new:Npn \__unicode_codepoint_to_UTFviii_auxiii:n #1
23980 { { \int_eval:n { \int_mod:nn {#1} { 64 } + 128 } } }

```

(End definition for __unicode_codepoint_to_UTFviii:n and others.)

\c__unicode_std_sigma_tl
\c__unicode_final_sigma_tl
\c__unicode_accents_lt_tl
\c__unicode_dot_above_tl
\c__unicode_upper_Eszett_tl

The above needs various special token lists containing pre-formed characters. This set are only available in Unicode engines, with no-op definitions for 8-bit use.

```

23981 \cs_if_exist:NTF \utex_char:D
23982 {
23983     \tl_const:Nx \c__unicode_std_sigma_tl    { \utex_char:D "03C3 ~ }
23984     \tl_const:Nx \c__unicode_final_sigma_tl  { \utex_char:D "03C2 ~ }
23985     \tl_const:Nx \c__unicode_accents_lt_tl
23986     {
23987         \utex_char:D "00CC ~
23988         { \utex_char:D "0069 ~ \utex_char:D "0307 ~ \utex_char:D "0300 ~ }
23989         \utex_char:D "00CD ~
23990         { \utex_char:D "0069 ~ \utex_char:D "0307 ~ \utex_char:D "0301 ~ }
23991         \utex_char:D "0128 ~
23992         { \utex_char:D "0069 ~ \utex_char:D "0307 ~ \utex_char:D "0303 ~ }
23993     }
23994     \tl_const:Nx \c__unicode_dot_above_tl    { \utex_char:D "0307 ~ }
23995     \tl_const:Nx \c__unicode_upper_Eszett_tl { \utex_char:D "1E9E ~ }
23996 }
23997 {
23998     \tl_const:Nn \c__unicode_std_sigma_tl    { }
23999     \tl_const:Nn \c__unicode_final_sigma_tl  { }
24000     \tl_const:Nn \c__unicode_accents_lt_tl    { }
24001     \tl_const:Nn \c__unicode_dot_above_tl    { }
24002     \tl_const:Nn \c__unicode_upper_Eszett_tl { }
24003 }

```

(End definition for \c__unicode_std_sigma_tl and others.)

\c__unicode_dotless_i_tl
\c__unicode_dotted_I_tl
\c__unicode_i_ogonek_tl
\c__unicode_I_ogonek_tl

For cases where there is an 8-bit option in the T1 font set up, a variant is provided in both cases.

```

24004 \group_begin:
24005     \cs_if_exist:NTF \utex_char:D
24006     {
24007         \cs_set_protected:Npn \__tl_tmp:w #1#2

```

```

24008     { \tl_const:Nx #1 { \utex_char:D "#2 ~ } }
24009   }
24010   {
24011     \cs_set_protected:Npn \__tl_tmp:w #1#2
24012     {
24013       \group_begin:
24014         \cs_set_protected:Npn \__tl_tmp:w ##1##2##3
24015         {
24016           \tl_const:Nx #1
24017           {
24018             \exp_after:wN \exp_after:wN \exp_after:wN
24019             \exp_not:N \__char_generate:nn {##2} { 13 }
24020             \exp_after:wN \exp_after:wN \exp_after:wN
24021             \exp_not:N \__char_generate:nn {##3} { 13 }
24022           }
24023         }
24024         \tl_set:Nx \l__tl_internal_a_tl
24025         { \__unicode_codepoint_to_UTFviii:n {"#2} }
24026         \exp_after:wN \__tl_tmp:w \l__tl_internal_a_tl
24027       \group_end:
24028     }
24029   }
24030   \__tl_tmp:w \c__unicode_dotless_i_tl { 0131 }
24031   \__tl_tmp:w \c__unicode_dotted_I_tl { 0130 }
24032   \__tl_tmp:w \c__unicode_i_ogonek_tl { 012F }
24033   \__tl_tmp:w \c__unicode_I_ogonek_tl { 012E }
24034 \group_end:

```

(End definition for \c__unicode_dotless_i_tl and others.)

For 8-bit engines we now need to define the case-change data for the multi-octet mappings. These need a list of what code points are doable in T1 so the list is hard coded (there's no saving in loading the mappings dynamically). All of the straight-forward ones have two octets, so that is taken as read.

```

24035 \group_begin:
24036   \bool_lazy_or:nnT
24037   { \sys_if_engine_pdftex_p: }
24038   { \sys_if_engine_uptex_p: }
24039   {
24040     \cs_set_protected:Npn \__tl_loop:nn #1#2
24041     {
24042       \quark_if_recursion_tail_stop:n {#1}
24043       \tl_set:Nx \l__tl_internal_a_tl
24044       {
24045         \__unicode_codepoint_to_UTFviii:n {"#1}
24046         \__unicode_codepoint_to_UTFviii:n {"#2}
24047       }
24048       \exp_after:wN \__tl_tmp:w \l__tl_internal_a_tl
24049       \__tl_loop:nn
24050     }
24051     \cs_set_protected:Npn \__tl_tmp:w #1#2#3#4#5#6
24052     {
24053       \tl_const:cx
24054       {
24055         c__unicode_lower_

```

```

24056         \char_generate:nn {#2} { 12 }
24057         \char_generate:nn {#3} { 12 }
24058         _tl
24059     }
24060     {
24061         \exp_after:wN \exp_after:wN \exp_after:wN
24062         \exp_not:N \__char_generate:nn {#5} { 13 }
24063         \exp_after:wN \exp_after:wN \exp_after:wN
24064         \exp_not:N \__char_generate:nn {#6} { 13 }
24065     }
24066     \tl_const:cx
24067     {
24068         c__unicode_upper_
24069         \char_generate:nn {#5} { 12 }
24070         \char_generate:nn {#6} { 12 }
24071         _tl
24072     }
24073     {
24074         \exp_after:wN \exp_after:wN \exp_after:wN
24075         \exp_not:N \__char_generate:nn {#2} { 13 }
24076         \exp_after:wN \exp_after:wN \exp_after:wN
24077         \exp_not:N \__char_generate:nn {#3} { 13 }
24078     }
24079 }
24080 \__tl_loop:nn
24081 { 00C0 } { 00E0 }
24082 { 00C2 } { 00E2 }
24083 { 00C3 } { 00E3 }
24084 { 00C4 } { 00E4 }
24085 { 00C5 } { 00E5 }
24086 { 00C6 } { 00E6 }
24087 { 00C7 } { 00E7 }
24088 { 00C8 } { 00E8 }
24089 { 00C9 } { 00E9 }
24090 { 00CA } { 00EA }
24091 { 00CB } { 00EB }
24092 { 00CC } { 00EC }
24093 { 00CD } { 00ED }
24094 { 00CE } { 00EE }
24095 { 00CF } { 00EF }
24096 { 00D0 } { 00F0 }
24097 { 00D1 } { 00F1 }
24098 { 00D2 } { 00F2 }
24099 { 00D3 } { 00F3 }
24100 { 00D4 } { 00F4 }
24101 { 00D5 } { 00F5 }
24102 { 00D6 } { 00F6 }
24103 { 00D8 } { 00F8 }
24104 { 00D9 } { 00F9 }
24105 { 00DA } { 00FA }
24106 { 00DB } { 00FB }
24107 { 00DC } { 00FC }
24108 { 00DD } { 00FD }
24109 { 00DE } { 00FE }

```


24110	{ 0100 }	{ 0101 }
24111	{ 0102 }	{ 0103 }
24112	{ 0104 }	{ 0105 }
24113	{ 0106 }	{ 0107 }
24114	{ 0108 }	{ 0109 }
24115	{ 010A }	{ 010B }
24116	{ 010C }	{ 010D }
24117	{ 010E }	{ 010F }
24118	{ 0110 }	{ 0111 }
24119	{ 0112 }	{ 0113 }
24120	{ 0114 }	{ 0115 }
24121	{ 0116 }	{ 0117 }
24122	{ 0118 }	{ 0119 }
24123	{ 011A }	{ 011B }
24124	{ 011C }	{ 011D }
24125	{ 011E }	{ 011F }
24126	{ 0120 }	{ 0121 }
24127	{ 0122 }	{ 0123 }
24128	{ 0124 }	{ 0125 }
24129	{ 0128 }	{ 0129 }
24130	{ 012A }	{ 012B }
24131	{ 012C }	{ 012D }
24132	{ 012E }	{ 012F }
24133	{ 0132 }	{ 0133 }
24134	{ 0134 }	{ 0135 }
24135	{ 0136 }	{ 0137 }
24136	{ 0139 }	{ 013A }
24137	{ 013B }	{ 013C }
24138	{ 013E }	{ 013F }
24139	{ 0141 }	{ 0142 }
24140	{ 0143 }	{ 0144 }
24141	{ 0145 }	{ 0146 }
24142	{ 0147 }	{ 0148 }
24143	{ 014A }	{ 014B }
24144	{ 014C }	{ 014D }
24145	{ 014E }	{ 014F }
24146	{ 0150 }	{ 0151 }
24147	{ 0152 }	{ 0153 }
24148	{ 0154 }	{ 0155 }
24149	{ 0156 }	{ 0157 }
24150	{ 0158 }	{ 0159 }
24151	{ 015A }	{ 015B }
24152	{ 015C }	{ 015D }
24153	{ 015E }	{ 015F }
24154	{ 0160 }	{ 0161 }
24155	{ 0162 }	{ 0163 }
24156	{ 0164 }	{ 0165 }
24157	{ 0168 }	{ 0169 }
24158	{ 016A }	{ 016B }
24159	{ 016C }	{ 016D }
24160	{ 016E }	{ 016F }
24161	{ 0170 }	{ 0171 }
24162	{ 0172 }	{ 0173 }
24163	{ 0174 }	{ 0175 }

```

24164     { 0176 } { 0177 }
24165     { 0178 } { 00FF }
24166     { 0179 } { 017A }
24167     { 017B } { 017C }
24168     { 017D } { 017E }
24169     { 01CD } { 01CE }
24170     { 01CF } { 01D0 }
24171     { 01D1 } { 01D2 }
24172     { 01D3 } { 01D4 }
24173     { 01E2 } { 01E3 }
24174     { 01E6 } { 01E7 }
24175     { 01E8 } { 01E9 }
24176     { 01EA } { 01EB }
24177     { 01F4 } { 01F5 }
24178     { 0218 } { 0219 }
24179     { 021A } { 021B }
24180     \q_recursion_tail ?
24181     \q_recursion_stop
24182     \cs_set_protected:Npn \__tl_tmp:w #1#2#3
24183     {
24184         \group_begin:
24185         \cs_set_protected:Npn \__tl_tmp:w ##1##2##3
24186         {
24187             \tl_const:cx
24188             {
24189                 c__unicode_ #3 _
24190                 \char_generate:nn {##2} { 12 }
24191                 \char_generate:nn {##3} { 12 }
24192                 _tl
24193             }
24194             {#2}
24195         }
24196         \tl_set:Nx \l__tl_internal_a_tl
24197         { \__unicode_codepoint_to_UTFviii:n { "#1 } }
24198         \exp_after:wN \__tl_tmp:w \l__tl_internal_a_tl
24199         \group_end:
24200     }
24201     \__tl_tmp:w { 00DF } { SS } { upper }
24202     \__tl_tmp:w { 00DF } { Ss } { mixed }
24203     \__tl_tmp:w { 0131 } { I } { upper }
24204 }
24205 \group_end:

```

The (fixed) look-up mappings for letter-like control sequences.

```

24206 \group_begin:
24207     \cs_set_protected:Npn \__tl_change_case_setup:NN #1#2
24208     {
24209         \quark_if_recursion_tail_stop:N #1
24210         \tl_const:cn { c__tl_change_case_lower_ \token_to_str:N #1 _tl } { #2 }
24211         \tl_const:cn { c__tl_change_case_upper_ \token_to_str:N #2 _tl } { #1 }
24212         \__tl_change_case_setup:NN
24213     }
24214     \__tl_change_case_setup:NN
24215     \AA \aa
24216     \AE \ae

```

```

24217 \DH \dh
24218 \DJ \dj
24219 \IJ \ij
24220 \L \l
24221 \NG \ng
24222 \O \o
24223 \OE \oe
24224 \SS \ss
24225 \TH \th
24226 \q_recursion_tail ?
24227 \q_recursion_stop
24228 \tl_const:cn { c__tl_change_case_upper_ \token_to_str:N \i _tl } { I }
24229 \tl_const:cn { c__tl_change_case_upper_ \token_to_str:N \j _tl } { J }
24230 \group_end:

```

\l_tl_case_change_accents_tl A list of accents to leave alone.

```

24231 \tl_new:N \l_tl_case_change_accents_tl
24232 \tl_set:Nn \l_tl_case_change_accents_tl
24233 { \" \' \. \^ \' \~ \c \H \k \r \t \u \v }

```

(End definition for \l_tl_case_change_accents_tl. This variable is documented on page 249.)

_tl_change_case_mixed_nl:Nnw For Dutch, there is a single look-ahead test for ij when title casing. If the appropriate letters are found, produce IJ and gobble the j/J.

```

\_tl_change_case_mixed_nl:Nw
\_tl_change_case_mixed_nl:NNw
24234 \cs_new:Npn \_tl_change_case_mixed_nl:Nnw #1
24235 {
24236   \bool_lazy_or:nnTF
24237     { \int_compare_p:nNn { '#1 } = { 'i } }
24238     { \int_compare_p:nNn { '#1 } = { 'I } }
24239     {
24240       \_tl_change_case_output:nwn { I }
24241       \_tl_change_case_mixed_nl:Nw
24242     }
24243 }
24244 \cs_new:Npn \_tl_change_case_mixed_nl:Nw #1#2 \q_recursion_stop
24245 {
24246   \tl_if_head_is_N_type:nT {#2}
24247   { \_tl_change_case_mixed_nl:NNw }
24248   #1 #2 \q_recursion_stop
24249 }
24250 \cs_new:Npn \_tl_change_case_mixed_nl:NNw #1#2#3 \q_recursion_stop
24251 {
24252   \_tl_change_case_if_expandable:NTF #2
24253   {
24254     \exp_after:wN \_tl_change_case_mixed_nl:Nw \exp_after:wN #1 #2
24255     #3 \q_recursion_stop
24256   }
24257   {
24258     \bool_lazy_and:nnTF
24259     { ! ( \token_if_cs_p:N #2 ) }
24260     {
24261       \bool_lazy_or_p:nn
24262       { \int_compare_p:nNn { '#2 } = { 'j } }
24263       { \int_compare_p:nNn { '#2 } = { 'J } }

```

```

24264     }
24265     {
24266         \_tl_change_case_output:nwn { J }
24267         #1
24268     }
24269     { #1 #2 }
24270     #3 \q_recursion_stop
24271 }
24272 }

```

(End definition for `_tl_change_case_mixed_n1:Nnw`, `_tl_change_case_mixed_n1:Nw`, and `_tl_change_case_mixed_n1:NNw`.)

`\l_tl_case_change_math_tl` The list of token pairs which are treated as math mode and so not case changed.

```

24273 \tl_new:N \l_tl_case_change_math_tl
24274 \*package
24275 \tl_set:Nn \l_tl_case_change_math_tl
24276 { $ $ \ ( \ ) }
24277 \*package

```

(End definition for `\l_tl_case_change_math_tl`. This variable is documented on page 248.)

`\l_tl_case_change_exclude_tl` The list of commands for which an argument is not case changed.

```

24278 \tl_new:N \l_tl_case_change_exclude_tl
24279 \*package
24280 \tl_set:Nn \l_tl_case_change_exclude_tl
24281 { \cite \ensuremath \label \ref }
24282 \*package

```

(End definition for `\l_tl_case_change_exclude_tl`. This variable is documented on page 249.)

`\l_tl_mixed_case_ignore_tl` Characters to skip over when finding the first letter in a word to be mixed cased.

```

24283 \tl_new:N \l_tl_mixed_case_ignore_tl
24284 \tl_set:Nx \l_tl_mixed_case_ignore_tl
24285 {
24286     ( % )
24287     [ % ]
24288     \cs_to_str:N \{ % \% }
24289     '
24290     -
24291 }

```

(End definition for `\l_tl_mixed_case_ignore_tl`. This variable is documented on page 250.)

42.16.2 Other additions to `l3tl`

`\tl_rand_item:n` Importantly `\tl_item:nn` only evaluates its argument once.

```

\tl_rand_item:N 24292 \cs_new:Npn \tl_rand_item:n #1
\tl_rand_item:c 24293 {
24294     \tl_if_blank:nF {#1}
24295     { \tl_item:nn {#1} { \int_rand:nn { 1 } { \tl_count:n {#1} } } }
24296 }
24297 \cs_new:Npn \tl_rand_item:N { \exp_args:No \tl_rand_item:n }
24298 \cs_generate_variant:Nn \tl_rand_item:N { c }

```

(End definition for `\tl_rand_item:n` and `\tl_rand_item:N`. These functions are documented on page 251.)

Some preliminary code is needed for the `\tl_range:nnn` family of functions.

```

\tl_range:Nnn To avoid checking for the end of the token list at every step, start by counting the
\tl_range:cnn number  $l$  of items and “normalizing” the bounds, namely clamping them to the inter-
\tl_range:nnn val  $[0, l]$  and dealing with negative indices. More precisely, \__tl_range_items:nnNn
\tl_range_braced:Nnn receives the number of items to skip at the beginning of the token list, the index of the
\tl_range_braced:cnn last item to keep, a function among \__tl_range:w, \__tl_range_braced:w, \__tl_
\tl_range_braced:nnn range_unbraced:w, and the token list itself. If nothing should be kept, leave {}: this
\tl_range_unbraced:Nnn stops the f-expansion of \tl_head:f and that function produces an empty result. Oth-
\tl_range_unbraced:cnn erwise, repeatedly call \__tl_range_skip:w to delete #1 items from the input stream
\tl_range_unbraced:nnn (the extra brace group avoids an off-by-one shift). For the braced version \__tl_range_
\tl_range:Nnnn braced:w sets up \__tl_range_collect_braced:w which stores items one by one in an
\tl_range:nnnNn argument after the semicolon. The unbraced version is almost identical. The version
\tl_range:nnNn preserving braces and spaces starts by deleting spaces before the argument to avoid col-
\tl_range_skip:w lecting them, and sets up \__tl_range_collect:nn with a first argument of the form {
\tl_range_braced:w {\langle collected \rangle} \langle tokens \rangle }, whose head is the collected tokens and whose tail is what remains
\tl_range_collect_braced:w of the original token list. This form makes it easier to move tokens to the \langle collected \rangle to-
\tl_range_unbraced:w kens. Depending on the first token of the tail, either just move it (if it is a space) or
\tl_range_collect_unbraced:w also decrement the number of items left to find. Eventually, the result is a brace group
\tl_range:w followed by the rest of the token list, and \tl_head:f cleans up and gives the result in
\tl_range_skip_spaces:n \exp_not:n.
\tl_range_collect:nn
\tl_range_collect:ff
\tl_range_collect_space:nw
\tl_range_collect_N:nN
\tl_range_collect_group:nN
24299 \cs_new:Npn \tl_range:Nnn { \exp_args:No \tl_range:nnn }
24300 \cs_generate_variant:Nn \tl_range:Nnn { c }
24301 \cs_new:Npn \tl_range:nnn { \__tl_range:Nnnn \__tl_range:w }
24302 \cs_new:Npn \tl_range_braced:Nnn { \exp_args:No \tl_range_braced:nnn }
24303 \cs_generate_variant:Nn \tl_range_braced:Nnn { c }
24304 \cs_new:Npn \tl_range_braced:nnn { \__tl_range:Nnnn \__tl_range_braced:w }
24305 \cs_new:Npn \tl_range_unbraced:Nnn { \exp_args:No \tl_range_unbraced:nnn }
24306 \cs_generate_variant:Nn \tl_range_unbraced:Nnn { c }
24307 \cs_new:Npn \tl_range_unbraced:nnn { \__tl_range:Nnnn \__tl_range_unbraced:w }
24308 \cs_new:Npn \__tl_range:Nnnn #1#2#3#4
24309 {
24310 \tl_head:f
24311 {
24312 \exp_args:Nf \__tl_range:nnnNn
24313 { \tl_count:n {#2} } {#3} {#4} #1 {#2}
24314 }
24315 }
24316 \cs_new:Npn \__tl_range:nnnNn #1#2#3
24317 {
24318 \exp_args:Nff \__tl_range:nnNn
24319 {
24320 \exp_args:Nf \__tl_range_normalize:nn
24321 { \int_eval:n { #2 - 1 } } {#1}
24322 }
24323 {
24324 \exp_args:Nf \__tl_range_normalize:nn
24325 { \int_eval:n {#3} } {#1}
24326 }
24327 }

```

```

24328 \cs_new:Npn \__tl_range:nnNn #1#2#3#4
24329 {
24330   \if_int_compare:w #2 > #1 \exp_stop_f: \else:
24331     \exp_after:wN { \exp_after:wN }
24332   \fi:
24333   \exp_after:wN #3
24334   \__int_value:w \__int_eval:w #2 - #1 \exp_after:wN ;
24335   \exp_after:wN { \exp:w \__tl_range_skip:w #1 ; { } #4 }
24336 }
24337 \cs_new:Npn \__tl_range_skip:w #1 ; #2
24338 {
24339   \if_int_compare:w #1 > 0 \exp_stop_f:
24340     \exp_after:wN \__tl_range_skip:w
24341     \__int_value:w \__int_eval:w #1 - 1 \exp_after:wN ;
24342   \else:
24343     \exp_after:wN \exp_end:
24344   \fi:
24345 }
24346 \cs_new:Npn \__tl_range_braced:w #1 ; #2
24347 { \__tl_range_collect_braced:w #1 ; { } #2 }
24348 \cs_new:Npn \__tl_range_unbraced:w #1 ; #2
24349 { \__tl_range_collect_unbraced:w #1 ; { } #2 }
24350 \cs_new:Npn \__tl_range_collect_braced:w #1 ; #2#3
24351 {
24352   \if_int_compare:w #1 > 1 \exp_stop_f:
24353     \exp_after:wN \__tl_range_collect_braced:w
24354     \__int_value:w \__int_eval:w #1 - 1 \exp_after:wN ;
24355   \fi:
24356   { #2 {#3} }
24357 }
24358 \cs_new:Npn \__tl_range_collect_unbraced:w #1 ; #2#3
24359 {
24360   \if_int_compare:w #1 > 1 \exp_stop_f:
24361     \exp_after:wN \__tl_range_collect_unbraced:w
24362     \__int_value:w \__int_eval:w #1 - 1 \exp_after:wN ;
24363   \fi:
24364   { #2 #3 }
24365 }
24366 \cs_new:Npn \__tl_range:w #1 ; #2
24367 {
24368   \exp_args:Nf \__tl_range_collect:nn
24369   { \__tl_range_skip_spaces:n {#2} } {#1}
24370 }
24371 \cs_new:Npn \__tl_range_skip_spaces:n #1
24372 {
24373   \tl_if_head_is_space:nTF {#1}
24374   { \exp_args:Nf \__tl_range_skip_spaces:n {#1} }
24375   { { } #1 }
24376 }
24377 \cs_new:Npn \__tl_range_collect:nn #1#2
24378 {
24379   \int_compare:nNnTF {#2} = 0
24380   {#1}
24381   {

```

```

24382 \exp_args:No \tl_if_head_is_space:nTF { \use_none:n #1 }
24383 {
24384   \exp_args:Nf \__tl_range_collect:nn
24385   { \__tl_range_collect_space:nw #1 }
24386   {#2}
24387 }
24388 {
24389   \__tl_range_collect:ff
24390   {
24391     \exp_args:No \tl_if_head_is_N_type:nTF { \use_none:n #1 }
24392     { \__tl_range_collect_N:nN }
24393     { \__tl_range_collect_group:nn }
24394     #1
24395   }
24396   { \int_eval:n { #2 - 1 } }
24397 }
24398 }
24399 }
24400 \cs_new:Npn \__tl_range_collect_space:nw #1 ~ { { #1 ~ } }
24401 \cs_new:Npn \__tl_range_collect_N:nN #1#2 { { #1 #2 } }
24402 \cs_new:Npn \__tl_range_collect_group:nn #1#2 { { #1 {#2} } }
24403 \cs_generate_variant:Nn \__tl_range_collect:nn { ff }

```

(End definition for \tl_range:Nnn and others. These functions are documented on page ??.)

`__tl_range_normalize:nn` This function converts an $\langle index \rangle$ argument into an explicit position in the token list (a result of 0 denoting “out of bounds”). Expects two explicit integer arguments: the $\langle index \rangle$ #1 and the string count #2. If #1 is negative, replace it by $\#1 + \#2 + 1$, then limit to the range $[0, \#2]$.

```

24404 \cs_new:Npn \__tl_range_normalize:nn #1#2
24405 {
24406   \int_eval:n
24407   {
24408     \if_int_compare:w #1 < 0 \exp_stop_f:
24409     \if_int_compare:w #1 < -#2 \exp_stop_f:
24410     0
24411     \else:
24412       #1 + #2 + 1
24413     \fi:
24414     \else:
24415       \if_int_compare:w #1 < #2 \exp_stop_f:
24416       #1
24417       \else:
24418       #2
24419     \fi:
24420     \fi:
24421   }
24422 }

```

(End definition for __tl_range_normalize:nn.)

42.17 Additions to l3token

`\c_catcode_active_space_tl` While `__char_generate:nn` can produce active characters in some engines it cannot in general. It would be possible to simply change the catcode of space but then the code

would need to avoid all spaces, making it quite unreadable. Instead we use the primitive `\tex_lowercase:D` trick.

```

24423 \group_begin:
24424   \char_set_catcode_active:N *
24425   \char_set_lccode:nn { '*' } { '\ }
24426   \tex_lowercase:D { \tl_const:Nn \c_catcode_active_space_tl { * } }
24427 \group_end:

```

(End definition for `\c_catcode_active_space_tl`. This variable is documented on page 252.)

```

24428 <@@=peek>

```

`\peek_N_type:TF` All tokens are N-type tokens, except in four cases: begin-group tokens, end-group tokens, space tokens with character code 32, and outer tokens. Since `\l_peek_token` might be outer, we cannot use the convenient `\bool_if:nTF` function, and must resort to the old trick of using `\ifodd` to expand a set of tests. The **false** branch of this test is taken if the token is one of the first three kinds of non-N-type tokens (explicit or implicit), thus we call `__peek_false:w`. In the **true** branch, we must detect outer tokens, without impacting performance too much for non-outer tokens. The first filter is to search for **outer** in the `\meaning` of `\l_peek_token`. If that is absent, `\use_none_delimit_by_q_stop:w` cleans up, and we call `__peek_true:w`. Otherwise, the token can be a non-outer macro or a primitive mark whose parameter or replacement text contains **outer**, it can be the primitive `\outer`, or it can be an outer token. Macros and marks would have **ma** in the part before the first occurrence of **outer**; the meaning of `\outer` has nothing after **outer**, contrarily to outer macros; and that covers all cases, calling `__peek_true:w` or `__peek_false:w` as appropriate. Here, there is no *<search token>*, so we feed a dummy `\scan_stop:` to the `__peek_token_generic:NNTF` function.

```

24429 \group_begin:
24430   \cs_set_protected:Npn \__peek_tmp:w #1 \q_stop
24431   {
24432     \cs_new_protected:Npn \__peek_execute_branches_N_type:
24433     {
24434       \if_int_odd:w
24435         \if_catcode:w \exp_not:N \l_peek_token { 0 \exp_stop_f: \fi:
24436         \if_catcode:w \exp_not:N \l_peek_token } 0 \exp_stop_f: \fi:
24437         \if_meaning:w \l_peek_token \c_space_token 0 \exp_stop_f: \fi:
24438         1 \exp_stop_f:
24439         \exp_after:wN \__peek_N_type:w
24440         \token_to_meaning:N \l_peek_token
24441         \q_mark \__peek_N_type_aux:nnw
24442         #1 \q_mark \use_none_delimit_by_q_stop:w
24443         \q_stop
24444         \exp_after:wN \__peek_true:w
24445       \else:
24446         \exp_after:wN \__peek_false:w
24447       \fi:
24448     }
24449     \cs_new_protected:Npn \__peek_N_type:w ##1 #1 ##2 \q_mark ##3
24450     { ##3 {##1} {##2} }
24451   }
24452   \exp_after:wN \__peek_tmp:w \tl_to_str:n { outer } \q_stop
24453 \group_end:
24454 \cs_new_protected:Npn \__peek_N_type_aux:nnw #1 #2 #3 \fi:

```



```

24455 {
24456   \fi:
24457   \tl_if_in:noTF {#1} { \tl_to_str:n {ma} }
24458     { \__peek_true:w }
24459     { \tl_if_empty:nTF {#2} { \__peek_true:w } { \__peek_false:w } }
24460 }
24461 \cs_new_protected:Npn \peek_N_type:TF
24462   { \__peek_token_generic:NNTF \__peek_execute_branches_N_type: \scan_stop: }
24463 \cs_new_protected:Npn \peek_N_type:T
24464   { \__peek_token_generic:NNT \__peek_execute_branches_N_type: \scan_stop: }
24465 \cs_new_protected:Npn \peek_N_type:F
24466   { \__peek_token_generic:NNTF \__peek_execute_branches_N_type: \scan_stop: }

```

(End definition for \peek_N_type:TF and others. This function is documented on page 252.)

```

24467 </initex | package>

```

43 l3luatex implementation

```

24468 <*initex | package>

```

43.1 Breaking out to Lua

```

24469 <*tex>

```

\lua_now_x:n Wrappers around the primitives. As with engines other than LuaTeX these have to be macros, we give them the same status in all cases. When LuaTeX is not in use, simply **\lua_now:n** give an error message/
\lua_shipout_x:n
\lua_shipout:n
\lua_escape_x:n
\lua_escape:n

```

24470 \cs_new:Npn \lua_now_x:n #1 { \luatex_directlua:D {#1} }
24471 \cs_new:Npn \lua_now:n #1 { \lua_now_x:n { \exp_not:n {#1} } }
24472 \cs_new_protected:Npn \lua_shipout_x:n #1 { \luatex_latelua:D {#1} }
24473 \cs_new_protected:Npn \lua_shipout:n #1
24474   { \lua_shipout_x:n { \exp_not:n {#1} } }
24475 \cs_new:Npn \lua_escape_x:n #1 { \luatex_luaescapestring:D {#1} }
24476 \cs_new:Npn \lua_escape:n #1 { \lua_escape_x:n { \exp_not:n {#1} } }
24477 \sys_if_engine luatex:F
24478 {
24479   \clist_map_inline:nn
24480     { \lua_now_x:n , \lua_now:n , \lua_escape_x:n , \lua_escape:n }
24481     {
24482       \cs_set:Npn #1 ##1
24483       {
24484         \__msg_kernel_expandable_error:nnn
24485           { kernel } { luatex-required } { #1 }
24486       }
24487     }
24488   \clist_map_inline:nn
24489     { \lua_shipout_x:n , \lua_shipout:n }
24490     {
24491       \cs_set_protected:Npn #1 ##1
24492       {
24493         \__msg_kernel_error:nnn
24494           { kernel } { luatex-required } { #1 }
24495       }
24496     }

```

```
24497 }

```

(End definition for `\lua_now_x:n` and others. These functions are documented on page 253.)

43.2 Messages

```
24498 \_msg_kernel_new:nnnn { kernel } { luatex-required }
24499 { LuaTeX~engine~not~in~use!~Ignoring~#1. }
24500 {
24501   The~feature~you~are~using~is~only~available~
24502   with~the~LuaTeX~engine.~LaTeX3~ignored~'~#1'.
24503 }
24504 \</tex>

```

43.3 Lua functions for internal use

```
24505 (*lua)

```

Most of the emulation of pdfTeX here is based heavily on Heiko Oberdiek's `pdfTeX-cmds` package.

l3kernel Create a table for the kernel's own use.

```
24506 l3kernel = l3kernel or { }

```

(End definition for `l3kernel`. This function is documented on page ??.)

Local copies of global tables.

```
24507 local io      = io
24508 local kpse    = kpse
24509 local lfs     = lfs
24510 local math    = math
24511 local md5     = md5
24512 local os      = os
24513 local string  = string
24514 local tex     = tex
24515 local unicode = unicode

```

Local copies of standard functions.

```
24516 local abs      = math.abs
24517 local byte     = string.byte
24518 local floor    = math.floor
24519 local format   = string.format
24520 local gsub     = string.gsub
24521 local kpse_find = kpse.find_file
24522 local lfs_attr = lfs.attributes
24523 local md5_sum  = md5.sum
24524 local open     = io.open
24525 local os_date  = os.date
24526 local setcatcode = tex.setcatcode
24527 local str_format = string.format
24528 local sprint   = tex.sprint
24529 local write    = tex.write
24530 local utf8_char = unicode.utf8.char

```

escapehex An internal auxiliary to convert a string to the matching hex escape. This works on a byte basis: extension to handled UTF-8 input is covered in `pdfTeX-cmds` but is not currently required here.

```

24531 local function escapehex(str)
24532   write((gsub(str, ".",
24533     function (ch) return format("%02X", byte(ch)) end)))
24534 end

```

(End definition for `escapehex`. This function is documented on page ??.)

l3kernel.charcat Creating arbitrary chars needs a category code table. As set up here, one may have been assigned earlier (see `l3bootstrap`) or a hard-coded one is used. The latter is intended for format mode and should be adjusted to match an eventual allocator.

```

24535 local charcat_table = l3kernel.charcat_table or 1
24536 local function charcat(charcode, catcode)
24537   setcatcode(charcat_table, charcode, catcode)
24538   sprint(charcat_table, utf8_char(charcode))
24539 end
24540 l3kernel.charcat = charcat

```

(End definition for `l3kernel.charcat`. This function is documented on page 254.)

l3kernel.filemdfivesum Read an entire file and hash it: the hash function itself is a built-in. As Lua is byte-based there is no work needed here in terms of UTF-8 (see `pdftexcmds` and how it handles strings that have passed through `LuaTeX`). The file is read in binary mode so that no line ending normalisation occurs.

```

24541 local function filemdfivesum(name)
24542   local file = kpse_find(name, "tex", true)
24543   if file then
24544     local f = open(file, "rb")
24545     if f then
24546       local data = f:read("*a")
24547       escapehex(md5_sum(data))
24548       f:close()
24549     end
24550   end
24551 end
24552 l3kernel.filemdfivesum = filemdfivesum

```

(End definition for `l3kernel.filemdfivesum`. This function is documented on page 254.)

l3kernel.filemoddate See procedure `makepdftime` in `utils.c` of `pdfTeX`.

```

24553 local function filemoddate(name)
24554   local file = kpse_find(name, "tex", true)
24555   if file then
24556     local date = lfs_attr(file, "modification")
24557     if date then
24558       local d = os_date("!*t", date)
24559       if d.sec >= 60 then
24560         d.sec = 59
24561       end
24562       local u = os_date("!*t", date)
24563       local off = 60 * (d.hour - u.hour) + d.min - u.min
24564       if d.year ~= u.year then
24565         if d.year > u.year then
24566           off = off + 1440
24567         else

```

```

24568         off = off - 1440
24569     end
24570 elseif d.yday ~= u.yday then
24571     if d.yday > u.yday then
24572         off = off + 1440
24573     else
24574         off = off - 1440
24575     end
24576 end
24577 local timezone
24578 if off == 0 then
24579     timezone = "Z"
24580 else
24581     local hours = floor(off / 60)
24582     local mins = abs(off - hours * 60)
24583     timezone = str_format("%+03d", hours)
24584     .. " " .. str_format("%02d", mins) .. " "
24585 end
24586 write("D:"
24587     .. str_format("%04d", d.year)
24588     .. str_format("%02d", d.month)
24589     .. str_format("%02d", d.day)
24590     .. str_format("%02d", d.hour)
24591     .. str_format("%02d", d.min)
24592     .. str_format("%02d", d.sec)
24593     .. timezone)
24594 end
24595 end
24596 end
24597 l3kernel.filemoddate = filemoddate

```

(End definition for `l3kernel.filemoddate`. This function is documented on page 254.)

l3kernel.filesize A simple disk lookup.

```

24598 local function filesize(name)
24599     local file = kpse_find(name, "tex", true)
24600     if file then
24601         local size = lfs_attr(file, "size")
24602         if size then
24603             write(size)
24604         end
24605     end
24606 end
24607 l3kernel.filesize = filesize

```

(End definition for `l3kernel.filesize`. This function is documented on page 254.)

l3kernel.strcmp String comparison which gives the same results as pdfTeX's `\pdfstrcmp`, although the ordering should likely not be relied upon!

```

24608 local function strcmp(A, B)
24609     if A == B then
24610         write("0")
24611     elseif A < B then
24612         write("-1")

```

```

24613     else
24614         write("1")
24615     end
24616 end
24617 l3kernel.strcmp = strcmp

```

(End definition for `l3kernel.strcmp`. This function is documented on page 254.)

43.4 Generic Lua and font support

```

24618 ⟨*initex⟩

```

A small amount of generic code is used by almost all LuaTeX material so needs to be loaded by the format.

```

24619 attribute_count_name = "g__alloc_attribute_int"
24620 bytecode_count_name  = "g__alloc_bytecode_int"
24621 chunkname_count_name  = "g__alloc_chunkname_int"
24622 whatsit_count_name    = "g__alloc_whatsit_int"
24623 require("l3luaotex")

```

With the above available the font loader code used by plain TeX and L^ATeX 2_ε when used with LuaTeX can be loaded here. This is thus being treated more-or-less as part of the engine itself.

```

24624 require("luaotfload-main")
24625 local _void = luaotfload.main()
24626 ⟨/initex⟩
24627 ⟨/lua⟩
24628 ⟨/initex | package⟩

```

44 l3drivers Implementation

```

24629 ⟨*initex | package⟩
24630 ⟨@@=driver⟩

```

Whilst there is a reasonable amount of code overlap between drivers, it is much clearer to have the blocks more-or-less separated than run in together and DocStripped out in parts. As such, most of the following is set up on a per-driver basis, though there is some common code (again given in blocks not interspersed with other material).

All the file identifiers are up-front so that they come out in the right place in the files.

```

24631 ⟨*package⟩
24632 \ProvidesExplFile
24633 ⟨*dvipdfmx⟩
24634 {l3dvidpfmt.def}{2017/03/18}{ }
24635 {L3 Experimental driver: dvipdfmx}
24636 ⟨/dvipdfmx⟩
24637 ⟨*dvips⟩
24638 {l3dvips.def}{2017/03/18}{ }
24639 {L3 Experimental driver: dvips}
24640 ⟨/dvips⟩
24641 ⟨*dvisvgm⟩
24642 {l3dvisvgm.def}{2017/03/18}{ }
24643 {L3 Experimental driver: dvisvgm}
24644 ⟨/dvisvgm⟩

```

```

24645 <*pdfmode>
24646   {l3pdfmode.def}{2017/03/18}{ }
24647   {L3 Experimental driver: PDF mode}
24648 </pdfmode>
24649 <*xdvipdfmx>
24650   {l3xdvipdfmx.def}{2017/03/18}{ }
24651   {L3 Experimental driver: xdvipdfmx}
24652 </xdvipdfmx>
24653 </package>

```

The order of the driver code here is such that we get somewhat logical outcomes in terms of code sharing whilst keeping things readable. (Trying to mix all of the code by concept is almost unmanageable.) The key parts which are shared are

- Color support is either dvips-like or pdfmode-like.
- pdfmode and (x)dvipdfmx share drawing routines.
- xdvipdfmx is largely the same as dvipdfmx so takes most of the same code.

44.1 Color support

Whilst (x)dvipdfmx does have its own approach to color specials, it is easier to use dvips-like ones for all cases except direct PDF output. As such the color code is collected here in two blocks.

44.1.1 dvips-style

```

24654 <*dvisvgm | dvipdfmx | dvips | xdvipdfmx>

```

`_driver_color_pickup:N` Allow for L^AT_EX 2_ε color. Here, the possible input values are limited: dvips-style colors can mainly be taken as-is with the exception spot ones (here we need a model and a tint).

```

24655 <*package>
24656 \cs_new_protected:Npn \_driver_color_pickup:N #1 { }
24657 \AtBeginDocument
24658 {
24659   \@ifpackageloaded { color }
24660   {
24661     \cs_set_protected:Npn \_driver_color_pickup:N #1
24662     {
24663       \exp_args:NV \tl_if_head_is_space:nTF \current@color
24664       {
24665         \tl_set:Nx #1
24666         {
24667           spot ~
24668           \exp_after:wN \use:n \current@color \c_space_tl 1
24669         }
24670       }
24671       { \exp_after:wN \_driver_color_pickup_aux:w \current@color \q_stop #1 }
24672     }
24673     \cs_new_protected:Npn \_driver_color_pickup_aux:w #1 ~ #2 \q_stop #3
24674     { \tl_set:Nn #3 { #1 ~ #2 } }
24675   }
24676   { }
24677 }
24678 </package>

```

(End definition for `_driver_color_pickup:N`.)

```

\_driver_color_select:n
\_driver_color_select:V
\_driver_convert_model:w
  \_driver_color_convert_spot:
  \_driver_color_convert_spot:w
\_driver_color_reset:
24679 \cs_new_protected:Npn \_driver_color_select:n #1
24680 {
24681   \tex_special:D
24682   {
24683     color~push~
24684     \cs_if_exist_use:cF
24685     { \_driver_color_convert\_ \_driver_convert_model:w #1 \q_stop :n }
24686     { \use:n }
24687     {#1}
24688   }
24689 }
24690 \cs_generate_variant:Nn \_driver_color_select:n { V }
24691 \cs_new:Npn \_driver_convert_model:w #1 ~ #2 \q_stop {#1}
24692 \cs_new:Npn \_driver_color_convert_spot:n #1
24693 { \_driver_color_convert_spot:w #1 \q_stop }
24694 \cs_new:Npn \_driver_color_convert_spot:w #1 ~ #2 ~ #3 \q_stop
24695 { \c_space_tl #2 }
24696 \cs_new_protected:Npn \_driver_color_reset:
24697 { \tex_special:D { color~pop } }

(End definition for \_driver_color_select:n and others.)

24698 </dvisvgm | dvipdfmx | dvips | xdvipdfmx>

```

44.1.2 pdfmode

24699 `<*pdfmode>`

`_driver_color_pickup:N` The current color in driver-dependent format: pick up the package-mode data if available.
`_driver_color_pickup_aux:w` We end up converting back and forward in this route as we store our color data in dvips format. The `\current@color` needs to be x-expanded before `_driver_color_pickup_aux:w` breaks it apart, because for instance xcolor sets it to be instructions to generate a colour

```

24700 <*package>
24701 \cs_new_protected:Npn \_driver_color_pickup:N #1 { }
24702 \AtBeginDocument
24703 {
24704   \@ifpackageloaded { color }
24705   {
24706     \cs_set_protected:Npn \_driver_color_pickup:N #1
24707     {
24708       \exp_last_unbraced:Nx \_driver_color_pickup_aux:w
24709       { \current@color } ~ 0 ~ 0 ~ 0 \q_stop #1
24710     }
24711     \cs_new_protected:Npn \_driver_color_pickup_aux:w
24712     #1 ~ #2 ~ #3 ~ #4 ~ #5 ~ #6 \q_stop #7
24713     {
24714       \str_if_eq:nnTF {#2} { g }
24715       { \tl_set:Nn #7 { gray ~ #1 } }

```

```

24716         {
24717         \str_if_eq:nnTF {#4} { rg }
24718         { \tl_set:Nn #7 { rgb ~ #1 ~ #2 ~ #3 } }
24719         {
24720         \str_if_eq:nnTF {#5} { k }
24721         { \tl_set:Nn #7 { cmyk ~ #1 ~ #2 ~ #3 ~ #4 } }
24722         {
24723         \str_if_eq:nnTF {#2} { cs }
24724         {
24725         \tl_set:Nx #7 { spot ~ \use_none:n #1 ~ #5 }
24726         }
24727         {
24728         \tl_set:Nn #7 { gray ~ 0 }
24729         }
24730         }
24731     }
24732 }
24733 }
24734 }
24735 { }
24736 }
24737 \</package>

```

(End definition for `__driver_color_pickup:N` and `__driver_color_pickup_aux:w`.)

`\l__driver_color_stack_int` pdfTeX and LuaTeX have multiple stacks available, and to track which one is in use a variable is required.

```

24738 \int_new:N \l__driver_color_stack_int

```

(End definition for `\l__driver_color_stack_int`.)

`__driver_color_select:n` There is a dedicated primitive/primitive interface for setting colors. As with scoping, this approach is not suitable for cached operations. Most of the conversions are trivial but the need to cover spot colors makes life slightly more interesting.

```

\__driver_color_convert:w
\__driver_color_convert_gray:w
\__driver_color_convert_cmyk:w
\__driver_color_convert_rgb:w
\__driver_color_convert_spot:w
\__driver_color_reset:
24739 \cs_new_protected:Npx \__driver_color_select:n #1
24740 {
24741 \cs_if_exist:NTF \luatex_pdfextension:D
24742 { \luatex_pdfextension:D colorstack }
24743 { \pdfTEX_pdfcolorstack:D }
24744 \exp_not:N \l__driver_color_stack_int push
24745 {
24746 \exp_not:N \__driver_color_convert:w
24747 #1
24748 \exp_not:N \q_stop
24749 }
24750 }
24751 \cs_generate_variant:Nn \__driver_color_select:n { V }
24752 \cs_new:Npn \__driver_color_convert:w #1 ~ #2 \q_stop
24753 { \use:c { \__driver_color_convert_ #1 :w } #2 \q_stop }
24754 \cs_new:Npn \__driver_color_convert_gray:w #1 \q_stop
24755 { #1 ~ g ~ #1 ~ G }
24756 \cs_new:Npn \__driver_color_convert_cmyk:w #1 \q_stop
24757 { #1 ~ k ~ #1 ~ K }
24758 \cs_new:Npn \__driver_color_convert_rgb:w #1 \q_stop

```



```

24759 { #1 ~ rg ~ #1 ~ RG }
24760 \cs_new:Npn \__driver_color_convert_spot:w #1 ~ #2 \q_stop
24761 {
24762   /#1 ~ cs ~ /#1 ~ CS ~ #2 ~ sc ~ #2 ~ SC
24763 }
24764 \cs_new_protected:Npx \__driver_color_reset:
24765 {
24766   \cs_if_exist:NTF \luatex_pdfextension:D
24767   { \luatex_pdfextension:D colorstack }
24768   { \pdfTEX_pdfcolorstack:D }
24769   \exp_not:N \l__driver_color_stack_int pop \scan_stop:
24770 }

```

(End definition for __driver_color_select:n and others.)

```

24771 \</pdfmode>

```

44.2 dvips driver

```

24772 \*dvips>

```

44.2.1 Basics

__driver_literal:n In the case of dvips there is no build-in saving of the current position, and so some additional PostScript is required to set up the transformation matrix and also to restore it afterwards. Notice the use of the stack to save the current position “up front” and to move back to it at the end of the process.

```

24773 \cs_new_protected:Npn \__driver_literal:n #1
24774 {
24775   \tex_special:D
24776   {
24777     ps:
24778     currentpoint~
24779     currentpoint~translate~
24780     #1 ~
24781     neg~exch~neg~exch~translate
24782   }
24783 }

```

(End definition for __driver_literal:n.)

__driver_scope_begin: Scope saving/restoring is done directly with no need to worry about the transformation matrix. General scoping is only for the graphics stack so the lower-cost gsave/grestore pair are used.

```

24784 \cs_new_protected:Npn \__driver_scope_begin:
24785 { \tex_special:D { ps:gsave } }
24786 \cs_new_protected:Npn \__driver_scope_end:
24787 { \tex_special:D { ps:grestore } }

```

(End definition for __driver_scope_begin: and __driver_scope_end:.)

44.3 Driver-specific auxiliaries

`_driver_absolute_lengths:n` The `dvips` driver scales all absolute dimensions based on the output resolution selected and any \TeX magnification. Thus for any operation involving absolute lengths there is a correction to make. This is based on `normalscale` from `special.pro` but using the stack rather than a definition to save the current matrix.

```

24788 \cs_new:Npn \_driver_absolute_lengths:n #1
24789 {
24790     matrix~currentmatrix~
24791     Resolution~72~div~VResolution~72~div~scale~
24792     DVImag~dup~scale~
24793     #1 ~
24794     setmatrix
24795 }
```

(End definition for `_driver_absolute_lengths:n`.)

44.3.1 Box operations

`_driver_box_use_clip:N` Much the same idea as for the PDF mode version but with a slightly different syntax for creating the clip path. To avoid any scaling issues we need the absolute length auxiliary here.

```

24796 \cs_new_protected:Npn \_driver_box_use_clip:N #1
24797 {
24798     \_driver_scope_begin:
24799     \_driver_literal:n
24800     {
24801         \_driver_absolute_lengths:n
24802         {
24803             0 ~
24804             \dim_to_decimal_in_bp:n { \box_dp:N #1 } ~
24805             \dim_to_decimal_in_bp:n { \box_wd:N #1 } ~
24806             \dim_to_decimal_in_bp:n { -\box_ht:N #1 - \box_dp:N #1 } ~
24807             rectclip
24808         }
24809     }
24810     \hbox_overlap_right:n { \box_use:N #1 }
24811     \_driver_scope_end:
24812     \skip_horizontal:n { \box_wd:N #1 }
24813 }
```

(End definition for `_driver_box_use_clip:N`.)

`_driver_box_use_rotate:Nn` Rotating using `dvips` does not require that the box dimensions are altered and has a very convenient built-in operation. Zero rotation must be written as 0 not -0 so there is a quick test.

```

24814 \cs_new_protected:Npn \_driver_box_use_rotate:Nn #1#2
24815 {
24816     \_driver_scope_begin:
24817     \_driver_literal:n
24818     {
24819         \fp_compare:nNnTF {#2} = \c_zero_fp
24820         { 0 }
24821         { \fp_eval:n { round ( -#2 , 5 ) } } ~

```

```

24822         rotate
24823     }
24824     \box_use:N #1
24825     \__driver_scope_end:
24826 }

```

(End definition for __driver_box_use_rotate:Nn.)

__driver_box_use_scale:Nnn The dvips driver once again has a dedicated operation we can use here.

```

24827 \cs_new_protected:Npn \__driver_box_use_scale:Nnn #1#2#3
24828 {
24829     \__driver_scope_begin:
24830     \__driver_literal:n
24831     {
24832         \fp_eval:n { round ( #2 , 5 ) } ~
24833         \fp_eval:n { round ( #3 , 5 ) } ~
24834         scale
24835     }
24836     \hbox_overlap_right:n { \box_use:N #1 }
24837     \__driver_scope_end:
24838 }

```

(End definition for __driver_box_use_scale:Nnn.)

44.4 Images

__driver_image_getbb_eps:n Simply use the generic function.

```

24839 \cs_new_eq:NN \__driver_image_getbb_eps:n \__image_read_bb:n

```

(End definition for __driver_image_getbb_eps:n.)

__driver_image_include_eps:n The special syntax is relatively clear here: remember we need PostScript sizes here.

```

24840 \cs_new_protected:Npn \__driver_image_include_eps:n #1
24841 {
24842     \tex_special:D { PSfile = #1 }
24843 }

```

(End definition for __driver_image_include_eps:n.)

44.5 Drawing

__driver_draw_literal:n Literals with no positioning (using ps: each one is positioned but cut off from everything else, so no good for the stepwise approach needed here).

__driver_draw_literal:x

```

24844 \cs_new_protected:Npn \__driver_draw_literal:n #1
24845 { \tex_special:D { ps:: ~ #1 } }
24846 \cs_generate_variant:Nn \__driver_draw_literal:n { x }

```

(End definition for __driver_draw_literal:n.)

__driver_draw_begin: The ps::[begin] special here deals with positioning but allows us to continue on to a matching ps::[end]: contrast with ps:, which positions but where we can't split material between separate calls. The @beginspecial/@endspecial pair are from special.pro and correct the scale and y-axis direction. The reference point at the start of the box is saved (as 13x/13y) as it is needed when inserting various items.

__driver_draw_end:

```

24847 \cs_new_protected:Npn \__driver_draw_begin:
24848 {
24849   \tex_special:D { ps::[begin] }
24850   \tex_special:D { ps::~save }
24851   \tex_special:D { ps::~/13x~currentpoint~/13y~exch~def~def }
24852   \tex_special:D { ps::~@beginspecial }
24853 }
24854 \cs_new_protected:Npn \__driver_draw_end:
24855 {
24856   \tex_special:D { ps::~@endspecial }
24857   \tex_special:D { ps::~restore }
24858   \tex_special:D { ps:::[end] }
24859 }

```

(End definition for __driver_draw_begin: and __driver_draw_end:.)

__driver_draw_scope_begin: Scope here may need to contain saved definitions, so the entire memory rather than just
 __driver_draw_scope_end: the graphic state has to be sent to the stack.

```

24860 \cs_new_protected:Npn \__driver_draw_scope_begin:
24861 { \__driver_draw_literal:n { save } }
24862 \cs_new_protected:Npn \__driver_draw_scope_end:
24863 { \__driver_draw_literal:n { restore } }

```

(End definition for __driver_draw_scope_begin: and __driver_draw_scope_end:.)

__driver_draw_moveto:nn Path creation operations mainly resolve directly to PostScript primitive steps, with only
 __driver_draw_lineto:nn the need to convert to bp. Notice that x-type expansion is included here to ensure that
 __driver_draw_rectangle:nnnn any variable values are forced to literals before any possible caching. There is no native
 __driver_draw_curveto:nnnnnn rectangular path command (without also clipping, filling or stroking), so that task is
 done using a small amount of PostScript.

```

24864 \cs_new_protected:Npn \__driver_draw_moveto:nn #1#2
24865 {
24866   \__driver_draw_literal:x
24867   { \dim_to_decimal_in_bp:n {#1} ~ \dim_to_decimal_in_bp:n {#2} ~ moveto }
24868 }
24869 \cs_new_protected:Npn \__driver_draw_lineto:nn #1#2
24870 {
24871   \__driver_draw_literal:x
24872   { \dim_to_decimal_in_bp:n {#1} ~ \dim_to_decimal_in_bp:n {#2} ~ lineto }
24873 }
24874 \cs_new_protected:Npn \__driver_draw_rectangle:nnnn #1#2#3#4
24875 {
24876   \__driver_draw_literal:x
24877   {
24878     \dim_to_decimal_in_bp:n {#4} ~ \dim_to_decimal_in_bp:n {#3} ~
24879     \dim_to_decimal_in_bp:n {#1} ~ \dim_to_decimal_in_bp:n {#2} ~
24880     moveto~dup~0~rlineto~exch~0~exch~rlineto~neg~0~rlineto~closepath
24881   }
24882 }
24883 \cs_new_protected:Npn \__driver_draw_curveto:nnnnnn #1#2#3#4#5#6
24884 {
24885   \__driver_draw_literal:x
24886   {
24887     \dim_to_decimal_in_bp:n {#1} ~ \dim_to_decimal_in_bp:n {#2} ~

```

```

24888         \dim_to_decimal_in_bp:n {#3} ~ \dim_to_decimal_in_bp:n {#4} ~
24889         \dim_to_decimal_in_bp:n {#5} ~ \dim_to_decimal_in_bp:n {#6} ~
24890         curveto
24891     }
24892 }

```

(End definition for `__driver_draw_moveto:nn` and others.)

`__driver_draw_evenodd_rule:` The even-odd rule here can be implemented as a simply switch.

```

\__driver_draw_nonzero_rule:
    \g__driver_draw_eor_bool
24893 \cs_new_protected:Npn \__driver_draw_evenodd_rule:
24894 { \bool_gset_true:N \g__driver_draw_eor_bool }
24895 \cs_new_protected:Npn \__driver_draw_nonzero_rule:
24896 { \bool_gset_false:N \g__driver_draw_eor_bool }
24897 \bool_new:N \g__driver_draw_eor_bool

```

(End definition for `__driver_draw_evenodd_rule:`, `__driver_draw_nonzero_rule:`, and `\g__driver_draw_eor_bool`.)

`__driver_draw_closepath:` Unlike PDF, PostScript doesn't track separate colors for strokes and other elements. It is also desirable to have the `clip` keyword after a stroke or fill. To achieve those outcomes, there is some work to do. For color, if a stroke or fill color is defined it is used for the relevant operation, with a graphic scope inserted as required. That does mean that once such a color is set all further uses inside the same scope have to use scoping: see also `__driver_draw_fillstroke:` the color set up functions. For clipping, the required ordering is achieved using a `TeX` switch. All of the operations end with a new path instruction as they do not terminate (again in contrast to PDF).

```

24898 \cs_new_protected:Npn \__driver_draw_closepath:
24899 { \__driver_draw_literal:n { closepath } }
24900 \cs_new_protected:Npn \__driver_draw_stroke:
24901 {
24902     \__driver_draw_literal:n { currentdict~/l3sc-known~{gsave~l3sc}-if }
24903     \__driver_draw_literal:n { stroke }
24904     \__driver_draw_literal:n { currentdict~/l3sc-known~{grestore}-if }
24905     \bool_if:NT \g__driver_draw_clip_bool
24906     {
24907         \__driver_draw_literal:x
24908         {
24909             \bool_if:NT \g__driver_draw_eor_bool { eo }
24910             clip
24911         }
24912     }
24913     \__driver_draw_literal:n { newpath }
24914     \bool_gset_false:N \g__driver_draw_clip_bool
24915 }
24916 \cs_new_protected:Npn \__driver_draw_closestroke:
24917 {
24918     \__driver_draw_closepath:
24919     \__driver_draw_stroke:
24920 }
24921 \cs_new_protected:Npn \__driver_draw_fill:
24922 {
24923     \__driver_draw_literal:n { currentdict~/l3fc-known~{gsave~l3fc}-if }
24924     \__driver_draw_literal:x
24925     {

```

```

24926         \bool_if:NT \g__driver_draw_eor_bool { eo }
24927         fill
24928     }
24929     \__driver_draw_literal:n { currentdict~/l3fc-known~{grestore}~if }
24930     \bool_if:NT \g__driver_draw_clip_bool
24931     {
24932         \__driver_draw_literal:x
24933         {
24934             \bool_if:NT \g__driver_draw_eor_bool { eo }
24935             clip
24936         }
24937     }
24938     \__driver_draw_literal:n { newpath }
24939     \bool_gset_false:N \g__driver_draw_clip_bool
24940 }
24941 \cs_new_protected:Npn \__driver_draw_fillstroke:
24942 {
24943     \__driver_draw_literal:n { currentdict~/l3fc-known~{gsave~l3fc}~if }
24944     \__driver_draw_literal:x
24945     {
24946         \bool_if:NT \g__driver_draw_eor_bool { eo }
24947         fill
24948     }
24949     \__driver_draw_literal:n { currentdict~/l3fc-known~{grestore}~if }
24950     \__driver_draw_literal:n { currentdict~/l3sc-known~{gsave~l3sc}~if }
24951     \__driver_draw_literal:n { stroke }
24952     \__driver_draw_literal:n { currentdict~/l3sc-known~{grestore}~if }
24953     \bool_if:NT \g__driver_draw_clip_bool
24954     {
24955         \__driver_draw_literal:x
24956         {
24957             \bool_if:NT \g__driver_draw_eor_bool { eo }
24958             clip
24959         }
24960     }
24961     \__driver_draw_literal:n { newpath }
24962     \bool_gset_false:N \g__driver_draw_clip_bool
24963 }
24964 \cs_new_protected:Npn \__driver_draw_clip:
24965 { \bool_gset_true:N \g__driver_draw_clip_bool }
24966 \bool_new:N \g__driver_draw_clip_bool
24967 \cs_new_protected:Npn \__driver_draw_discardpath:
24968 {
24969     \bool_if:NT \g__driver_draw_clip_bool
24970     {
24971         \__driver_draw_literal:x
24972         {
24973             \bool_if:NT \g__driver_draw_eor_bool { eo }
24974             clip
24975         }
24976     }
24977     \__driver_draw_literal:n { newpath }
24978     \bool_gset_false:N \g__driver_draw_clip_bool
24979 }

```

(End definition for `_driver_draw_closepath:` and others.)

Converting paths to output is again a case of mapping directly to PostScript operations.

```

\__driver\_draw\_dash:nn
\__driver\_draw\_dash:n
\__driver\_draw\_linewidth:n
\__driver\_draw\_miterlimit:n
\__driver\_draw\_cap\_butt:
\__driver\_draw\_cap\_round:
\__driver\_draw\_cap\_rectangle:
\__driver\_draw\_join\_miter:
\__driver\_draw\_join\_round:
\__driver\_draw\_join\_bevel:
24980 \cs\_new\_protected:Npn \__driver\_draw\_dash:nn #1#2
24981 {
24982   \__driver\_draw\_literal:x
24983   {
24984     [ ~
24985       \clist\_map\_function:nN {#1} \__driver\_draw\_dash:n
24986     ] ~
24987     \dim\_to\_decimal\_in\_bp:n {#2} ~ setdash
24988   }
24989 }
24990 \cs\_new:Npn \__driver\_draw\_dash:n #1
24991 { \dim\_to\_decimal\_in\_bp:n {#1} ~ }
24992 \cs\_new\_protected:Npn \__driver\_draw\_linewidth:n #1
24993 {
24994   \__driver\_draw\_literal:x
24995   { \dim\_to\_decimal\_in\_bp:n {#1} ~ setlinewidth }
24996 }
24997 \cs\_new\_protected:Npn \__driver\_draw\_miterlimit:n #1
24998 { \__driver\_draw\_literal:x { \fp\_eval:n {#1} ~ setmiterlimit } }
24999 \cs\_new\_protected:Npn \__driver\_draw\_cap\_butt:
25000 { \__driver\_draw\_literal:n { 0 ~ setlinecap } }
25001 \cs\_new\_protected:Npn \__driver\_draw\_cap\_round:
25002 { \__driver\_draw\_literal:n { 1 ~ setlinecap } }
25003 \cs\_new\_protected:Npn \__driver\_draw\_cap\_rectangle:
25004 { \__driver\_draw\_literal:n { 2 ~ setlinecap } }
25005 \cs\_new\_protected:Npn \__driver\_draw\_join\_miter:
25006 { \__driver\_draw\_literal:n { 0 ~ setlinejoin } }
25007 \cs\_new\_protected:Npn \__driver\_draw\_join\_round:
25008 { \__driver\_draw\_literal:n { 1 ~ setlinejoin } }
25009 \cs\_new\_protected:Npn \__driver\_draw\_join\_bevel:
25010 { \__driver\_draw\_literal:n { 2 ~ setlinejoin } }

```

(End definition for `_driver_draw_dash:nn` and others.)

To allow color to be defined for strokes and fills separately and to respect scoping, the data needs to be stored at the PostScript level. We cannot undefine (local) fill/stroke colors once set up but we can set them blank to improve performance slightly.

```

\__driver\_draw\_color\_reset:
\__driver\_draw\_color\_cmyk:nnnn
\__driver\_draw\_color\_cmyk\_fill:nnnn
\__driver\_draw\_color\_cmyk\_stroke:nnnn
\__driver\_draw\_color\_gray:n
\__driver\_draw\_color\_gray\_fill:n
\__driver\_draw\_color\_gray\_stroke:n
\__driver\_draw\_color\_rgb:nnn
\__driver\_draw\_color\_rgb\_fill:nnn
\__driver\_draw\_color\_rgb\_stroke:nnn
25011 \cs\_new\_protected:Npn \__driver\_draw\_color\_reset:
25012 {
25013   \__driver\_draw\_literal:n { currentdic~/l3fc~known~{ /l3fc~ { } ~def }~if }
25014   \__driver\_draw\_literal:n { currentdic~/l3sc~known~{ /l3sc~ { } ~def }~if }
25015 }
25016 \cs\_new\_protected:Npn \__driver\_draw\_color\_cmyk:nnnn #1#2#3#4
25017 {
25018   \__driver\_draw\_literal:x
25019   {
25020     \fp\_eval:n {#1} ~ \fp\_eval:n {#2} ~
25021     \fp\_eval:n {#3} ~ \fp\_eval:n {#4} ~
25022     setcmykcolor ~
25023   }
25024   \__driver\_draw\_color\_reset:

```

```

25025 }
25026 \cs_new_protected:Npn \__driver_draw_color_cmyk_fill:nnnn #1#2#3#4
25027 {
25028   \__driver_draw_literal:x
25029   {
25030     /l3fc ~
25031     {
25032       \fp_eval:n {#1} ~ \fp_eval:n {#2} ~
25033       \fp_eval:n {#3} ~ \fp_eval:n {#4} ~
25034       setcmykcolor
25035     } ~
25036     def
25037   }
25038 }
25039 \cs_new_protected:Npn \__driver_draw_color_cmyk_stroke:nnnn #1#2#3#4
25040 {
25041   \__driver_draw_literal:x
25042   {
25043     /l3sc ~
25044     {
25045       \fp_eval:n {#1} ~ \fp_eval:n {#2} ~
25046       \fp_eval:n {#3} ~ \fp_eval:n {#4} ~
25047       setcmykcolor
25048     } ~
25049     def
25050   }
25051 }
25052 \cs_new_protected:Npn \__driver_draw_color_gray:n #1
25053 {
25054   \__driver_draw_literal:x { \fp_eval:n {#1} ~ setgray }
25055   \__driver_draw_color_reset:
25056 }
25057 \cs_new_protected:Npn \__driver_draw_color_gray_fill:n #1
25058 { \__driver_draw_literal:x { /l3fc ~ { \fp_eval:n {#1} ~ setgray } ~ def } }
25059 \cs_new_protected:Npn \__driver_draw_color_gray_stroke:n #1
25060 { \__driver_draw_literal:x { /l3sc ~ { \fp_eval:n {#1} ~ setgray } ~ def } }
25061 \cs_new_protected:Npn \__driver_draw_color_rgb:nnn #1#2#3
25062 {
25063   \__driver_draw_literal:x
25064   {
25065     \fp_eval:n {#1} ~ \fp_eval:n {#2} ~ \fp_eval:n {#3} ~
25066     setrgbcolor
25067   }
25068   \__driver_draw_color_reset:
25069 }
25070 \cs_new_protected:Npn \__driver_draw_color_rgb_fill:nnn #1#2#3
25071 {
25072   \__driver_draw_literal:x
25073   {
25074     /l3fc ~
25075     {
25076       \fp_eval:n {#1} ~ \fp_eval:n {#2} ~ \fp_eval:n {#3} ~
25077       setrgbcolor
25078     } ~

```



```

25079         def
25080     }
25081 }
25082 \cs_new_protected:Npn \__driver_draw_color_rgb_stroke:nnn #1#2#3
25083 {
25084     \__driver_draw_literal:x
25085     {
25086         /l3sc ~
25087         {
25088             \fp_eval:n {#1} ~ \fp_eval:n {#2} ~ \fp_eval:n {#3} ~
25089             setrgbcolor
25090         } ~
25091     def
25092 }
25093 }

```

(End definition for `__driver_draw_color_reset:` and others.)

`__driver_draw_transformcm:nnnnnn` The first four arguments here are floats (the affine matrix), the last two are a displacement vector. Once again, force evaluation to allow for caching.

```

25094 \cs_new_protected:Npn \__driver_draw_transformcm:nnnnnn #1#2#3#4#5#6
25095 {
25096     \__driver_draw_literal:x
25097     {
25098         [
25099             \fp_eval:n {#1} ~ \fp_eval:n {#2} ~
25100             \fp_eval:n {#3} ~ \fp_eval:n {#4} ~
25101             \dim_to_decimal_in_bp:n {#5} ~ \dim_to_decimal_in_bp:n {#6} ~
25102         ] ~
25103         concat
25104     }
25105 }

```

(End definition for `__driver_draw_transformcm:nnnnnn`.)

`__driver_draw_hbox:Nnnnnnn` Inside a picture `@beginspecial/@endspecial` are active, which is normally a good thing but means that the position and scaling would be off if the box was inserted directly. Instead, we need to reverse the effect of the (normally desirable) shift/scaling within the box. That requires knowing where the reference point for the drawing is: saved as `l3x/l3y` at the start of the picture. Transformation here is relative to the drawing origin so has to be done purely in driver code not using \TeX offsets.

```

25106 \cs_new_protected:Npn \__driver_draw_hbox:Nnnnnnn #1#2#3#4#5#6#7
25107 {
25108     \__driver_scope_begin:
25109     \tex_special:D { ps::[end] }
25110     \__driver_draw_transformcm:nnnnnn {#2} {#3} {#4} {#5} {#6} {#7}
25111     \tex_special:D { ps::~~72~Resolution~div~72~VResolution~div~neg~scale }
25112     \tex_special:D { ps::~~magscale~{1~DVImag~div~dup~scale}~if }
25113     \tex_special:D { ps::~~l3x~neg~l3y~neg~translate }
25114     \box_set_wd:Nn #1 { Opt }
25115     \box_set_ht:Nn #1 { Opt }
25116     \box_set_dp:Nn #1 { Opt }
25117     \box_use:N #1
25118     \tex_special:D { ps::[begin] }

```

```

25119     \__driver_scope_end:
25120 }

(End definition for \__driver_draw_hbox:Nnnnnnn.)

25121 </dvips>

```

44.6 pdfmode driver

```

25122 <*pdfmode>

```

The direct PDF driver covers both pdfTeX and LuaTeX. The latter renames/restructures the driver primitives but this can be handled at one level of abstraction. As such, we avoid using two separate drivers for this material at the cost of some x-type definitions to get everything expanded up-front.

44.6.1 Basics

`__driver_literal:n` This is equivalent to `\special{pdf:}` but the engine can track it. Without the `direct` keyword everything is kept in sync: the transformation matrix is set to the current point automatically. Note that this is still inside the text (BT ...ET block).

```

25123 \cs_new_protected:Npx \__driver_literal:n #1
25124 {
25125     \cs_if_exist:NTF \luatex_pdfextension:D
25126     { \luatex_pdfextension:D literal }
25127     { \pdfTEX_pdfliteral:D }
25128     {#1}
25129 }

```

(End definition for `__driver_literal:n`.)

`__driver_scope_begin:` Higher-level interfaces for saving and restoring the graphic state.

```

\__driver_scope_end:
25130 \cs_new_protected:Npx \__driver_scope_begin:
25131 {
25132     \cs_if_exist:NTF \luatex_pdfextension:D
25133     { \luatex_pdfextension:D save \scan_stop: }
25134     { \pdfTEX_pdfsave:D }
25135 }
25136 \cs_new_protected:Npx \__driver_scope_end:
25137 {
25138     \cs_if_exist:NTF \luatex_pdfextension:D
25139     { \luatex_pdfextension:D restore \scan_stop: }
25140     { \pdfTEX_pdfrestore:D }
25141 }

```

(End definition for `__driver_scope_begin:` and `__driver_scope_end:.`)

`__driver_matrix:n` Here the appropriate function is set up to insert an affine matrix into the PDF. With pdfTeX and LuaTeX in direct PDF output mode there is a primitive for this, which only needs the rotation/scaling/skew part.

```

25142 \cs_new_protected:Npx \__driver_matrix:n #1
25143 {
25144     \cs_if_exist:NTF \luatex_pdfextension:D
25145     { \luatex_pdfextension:D setmatrix }
25146     { \pdfTEX_pdfsetmatrix:D }
25147     {#1}
25148 }

```

(End definition for _driver_matrix:n.)

44.6.2 Box operations

_driver_box_use_clip:N The general method is to save the current location, define a clipping path equivalent to the bounding box, then insert the content at the current position and in a zero width box. The “real” width is then made up using a horizontal skip before tidying up. There are other approaches that can be taken (for example using XForm objects), but the logic here shares as much code as possible and uses the same conversions (and so same rounding errors) in all cases.

```

25149 \cs_new_protected:Npn \_driver_box_use_clip:N #1
25150 {
25151   \_driver_scope_begin:
25152   \_driver_literal:n
25153   {
25154     0~
25155     \dim_to_decimal_in_bp:n { -\box_dp:N #1 } ~
25156     \dim_to_decimal_in_bp:n { \box_wd:N #1 } ~
25157     \dim_to_decimal_in_bp:n { \box_ht:N #1 + \box_dp:N #1 } ~
25158     re~W~n
25159   }
25160   \hbox_overlap_right:n { \box_use:N #1 }
25161   \_driver_scope_end:
25162   \skip_horizontal:n { \box_wd:N #1 }
25163 }

```

(End definition for _driver_box_use_clip:N.)

_driver_box_use_rotate:Nn Rotations are set using an affine transformation matrix which therefore requires sine/cosine values not the angle itself. We store the rounded values to avoid rounding twice. There are also a couple of comparisons to ensure that -0 is not written to the output, as this avoids any issues with problematic display programs. Note that numbers are compared to 0 after rounding.

```

25164 \cs_new_protected:Npn \_driver_box_use_rotate:Nn #1#2
25165 {
25166   \_driver_scope_begin:
25167   \box_set_wd:Nn #1 { Opt }
25168   \fp_set:Nn \l__driver_cos_fp { round ( cosd ( #2 ) , 5 ) }
25169   \fp_compare:nNnT \l__driver_cos_fp = \c_zero_fp
25170     { \fp_zero:N \l__driver_cos_fp }
25171   \fp_set:Nn \l__driver_sin_fp { round ( sind ( #2 ) , 5 ) }
25172   \_driver_matrix:n
25173   {
25174     \fp_use:N \l__driver_cos_fp \c_space_tl
25175     \fp_compare:nNnTF \l__driver_sin_fp = \c_zero_fp
25176       { 0~0 }
25177       {
25178         \fp_use:N \l__driver_sin_fp
25179         \c_space_tl
25180         \fp_eval:n { -\l__driver_sin_fp }
25181       }
25182     \c_space_tl
25183     \fp_use:N \l__driver_cos_fp

```

```

25184     }
25185     \box_use:N #1
25186     \__driver_scope_end:
25187   }
25188   \fp_new:N \l__driver_cos_fp
25189   \fp_new:N \l__driver_sin_fp

```

(End definition for __driver_box_use_rotate:Nn, \l__driver_cos_fp, and \l__driver_sin_fp.)

__driver_box_use_scale:Nnn The same idea as for rotation but without the complexity of signs and cosines.

```

25190   \cs_new_protected:Npn \__driver_box_use_scale:Nnn #1#2#3
25191   {
25192     \__driver_scope_begin:
25193     \__driver_matrix:n
25194     {
25195       \fp_eval:n { round ( #2 , 5 ) } ~
25196       0~0~
25197       \fp_eval:n { round ( #3 , 5 ) }
25198     }
25199     \hbox_overlap_right:n { \box_use:N #1 }
25200     \__driver_scope_end:
25201   }

```

(End definition for __driver_box_use_scale:Nnn.)

44.7 Images

\l__driver_image_attr_tl In PDF mode, additional attributes of an image (such as page number) are needed both to obtain the bounding box and when inserting the image: this occurs as the image dictionary approach means they are read as part of the bounding box operation. As such, it is easier to track additional attributes using a dedicated `tl` rather than build up the same data twice.

```

25202   \tl_new:N \l__driver_image_attr_tl

```

(End definition for \l__driver_image_attr_tl.)

__driver_image_getbb_jpg:n Getting the bounding box here requires us to box up the image and measure it. To deal with the difference in feature support in bitmap and vector images but keeping the common parts, there is a little work to do in terms of auxiliaries. The key here is to notice that we need two forms of the attributes: a “short” set to allow us to track for caching, and the full form to pass to the primitive.

```

25203   \cs_new_protected:Npn \__driver_image_getbb_jpg:n #1
25204   {
25205     \int_zero:N \l__image_page_int
25206     \tl_clear:N \l__image_pagebox_tl
25207     \tl_set:Nx \l__driver_image_attr_tl
25208     {
25209       \tl_if_empty:NF \l__image_decode_tl
25210       { :D \l__image_decode_tl }
25211       \bool_if:NT \l__image_interpolate_bool
25212       { :I }
25213     }
25214     \tl_clear:N \l__driver_image_attr_tl
25215     \__driver_image_getbb_auxi:n {#1}

```

```

25216 }
25217 \cs_new_eq:NN \__driver_image_getbb_png:n \__driver_image_getbb_jpg:n
25218 \cs_new_protected:Npn \__driver_image_getbb_pdf:n #1
25219 {
25220   \tl_clear:N \l__image_decode_tl
25221   \bool_set_false:N \l__image_interpolate_bool
25222   \tl_set:Nx \l__driver_image_attr_tl
25223   {
25224     : \l__image_pagebox_tl
25225     \int_compare:nNnT \l__image_page_int > 1
25226     { :P \int_use:N \l__image_page_int }
25227   }
25228   \__driver_image_getbb_auxi:n {#1}
25229 }
25230 \cs_new_protected:Npn \__driver_image_getbb_auxi:n #1
25231 {
25232   \dim_zero:N \l__image_llx_dim
25233   \dim_zero:N \l__image_lly_dim
25234   \dim_if_exist:cTF { c__image_ #1 \l__driver_image_attr_tl _urx_dim }
25235   {
25236     \dim_set_eq:Nc \l__image_urx_dim
25237     { c__image_ #1 \l__driver_image_attr_tl _urx_dim }
25238     \dim_set_eq:Nc \l__image_ury_dim
25239     { c__image_ #1 \l__driver_image_attr_tl _ury_dim }
25240   }
25241   { \__driver_image_getbb_auxii:n {#1} }
25242 }
25243 % \begin{macrocode}
25244 % Measuring the image is done by boxing up: for PDF images we could
25245 % use \pdfbox{pdfimagebbbox:D|}, but if doesn't work for other types.
25246 % As the box always starts at $(0,0)$ there is no need to worry about
25247 % the lower-left position.
25248 % \begin{macrocode}
25249 \cs_new_protected:Npn \__driver_image_getbb_auxii:n #1
25250 {
25251   \tex_immediate:D \pdfbox{pdfimage:D
25252   \bool_lazy_or:nnT
25253   { \l__image_interpolate_bool }
25254   { ! \tl_if_empty_p:N \l__image_decode_tl }
25255   {
25256     attr ~
25257     {
25258       \tl_if_empty:NF \l__image_decode_tl
25259       { /Decode~[ \l__image_decode_tl ] }
25260       \bool_if:NT \l__image_interpolate_bool
25261       { /Interpolate~true }
25262     }
25263   }
25264   \int_compare:nNnT \l__image_page_int > 0
25265   { page ~ \int_use:N \l__image_page_int }
25266   \tl_if_empty:NF \l__image_pagebox_tl
25267   { \l__image_pagebox_tl }
25268   {#1}
25269   \hbox_set:Nn \l__image_tmp_box

```

```

25270     { \pdfrefximage:D \pdflastximage:D }
25271 \dim_set:Nn \l__image_urx_dim { \box_wd:N \l__image_tmp_box }
25272 \dim_set:Nn \l__image_ury_dim { \box_ht:N \l__image_tmp_box }
25273 \int_const:cn { c__image_ #1 \l__driver_image_attr_tl _int }
25274 { \tex_the:D \pdfrefximage:D }
25275 \dim_const:cn { c__image_ #1 \l__driver_image_attr_tl _urx_dim }
25276 { \l__image_urx_dim }
25277 \dim_const:cn { c__image_ #1 \l__driver_image_attr_tl _ury_dim }
25278 { \l__image_ury_dim }
25279 }

```

(End definition for `__driver_image_getbb_jpg:n` and others.)

`__driver_image_include_jpg:n` Images are already loaded for the measurement part of the code, so inclusion is straightforward, with only any attributes to worry about. The latter carry through from determination of the bounding box.

```

25280 \cs_new_protected:Npn \__driver_image_include_jpg:n #1
25281 {
25282     \pdfrefximage:D
25283     \int_use:c { c__image_ #1 \l__driver_image_attr_tl _int }
25284 }
25285 \cs_new_eq:NN \__driver_image_include_pdf:n \__driver_image_include_jpg:n
25286 \cs_new_eq:NN \__driver_image_include_png:n \__driver_image_include_jpg:n

```

(End definition for `__driver_image_include_jpg:n`, `__driver_image_include_pdf:n`, and `__driver_image_include_png:n`.)

```

25287 </pdfmode>

```

44.8 dvipdfmx driver

```

25288 <*dvipdfmx | xdvipdfmx>

```

The `dvipdfmx` shares code with the PDF mode one (using the common section to this file) but also with `xdvipdfmx`. The latter is close to identical to `dvipdfmx` and so all of the code here is extracted for both drivers, with some `clean up` for `xdvipdfmx` as required.

44.8.1 Basics

`__driver_literal:n` Equivalent to `pdf:content` but favored as the link to the pdfTeX primitive approach is clearer. Some higher-level operations use `\tex_special:D` directly: see the later comments on where this is useful.

```

25289 \cs_new_protected:Npn \__driver_literal:n #1
25290 { \tex_special:D { pdf:literal~ #1 } }

```

(End definition for `__driver_literal:n`.)

`__driver_scope_begin:` Scoping is done using the driver-specific specials.

```

\__driver_scope_end:
25291 \cs_new_protected:Npn \__driver_scope_begin:
25292 { \tex_special:D { x:gsave } }
25293 \cs_new_protected:Npn \__driver_scope_end:
25294 { \tex_special:D { x:grestore } }

```

(End definition for `__driver_scope_begin:` and `__driver_scope_end:.`)

44.8.2 Box operations

`_driver_box_use_clip:N` The code here is identical to that for `pdfmode`: unlike rotation and scaling, there is no higher-level support in the driver for clipping.

```

25295 \cs_new_protected:Npn \_driver_box_use_clip:N #1
25296 {
25297   \_driver_scope_begin:
25298   \_driver_literal:n
25299   {
25300     0~
25301     \dim_to_decimal_in_bp:n { -\box_dp:N #1 } ~
25302     \dim_to_decimal_in_bp:n { \box_wd:N #1 } ~
25303     \dim_to_decimal_in_bp:n { \box_ht:N #1 + \box_dp:N #1 } ~
25304     re~W~n
25305   }
25306   \hbox_overlap_right:n { \box_use:N #1 }
25307   \_driver_scope_end:
25308   \skip_horizontal:n { \box_wd:N #1 }
25309 }

```

(End definition for `_driver_box_use_clip:N`.)

`_driver_box_use_rotate:Nn` Rotating in (x)dvi_{pdf} can be implemented using either PDF or driver-specific code. The former approach however is not “aware” of the content of boxes: this means that any embedded links would not be adjusted by the rotation. As such, the driver-native approach is preferred: the code therefore is similar (though not identical) to the `dvips` version (notice the rotation angle here is positive). As for `dvips`, zero rotation is written as 0 not -0.

```

25310 \cs_new_protected:Npn \_driver_box_use_rotate:Nn #1#2
25311 {
25312   \_driver_scope_begin:
25313   \tex_special:D
25314   {
25315     x:rotate~
25316     \fp_compare:nNnTF {#2} = \c_zero_fp
25317     { 0 }
25318     { \fp_eval:n { round ( #2 , 5 ) } }
25319   }
25320   \box_use:N #1
25321   \_driver_scope_end:
25322 }

```

(End definition for `_driver_box_use_rotate:Nn`.)

`_driver_box_use_scale:Nnn` Much the same idea for scaling: use the higher-level driver operation to allow for box content.

```

25323 \cs_new_protected:Npn \_driver_box_use_scale:Nnn #1#2#3
25324 {
25325   \_driver_scope_begin:
25326   \tex_special:D
25327   {
25328     x:scale~
25329     \fp_eval:n { round ( #2 , 5 ) } ~
25330     \fp_eval:n { round ( #3 , 5 ) }

```

```

25331     }
25332     \hbox_overlap_right:n { \box_use:N #1 }
25333     \__driver_scope_end:
25334 }

```

(End definition for __driver_box_use_scale:Nnn.)

44.9 Images

```

\__driver_image_getbb_eps:n Simply use the generic functions: only for dvipdfmx in the extraction cases.
\__driver_image_getbb_jpg:n 25335 \cs_new_eq:NN \__driver_image_getbb_eps:n \__image_read_bb:n
\__driver_image_getbb_pdf:n 25336 (*dvipdfmx)
\__driver_image_getbb_png:n 25337 \cs_new_protected:Npn \__driver_image_getbb_jpg:n #1
25338 {
25339     \int_zero:N \l__image_page_int
25340     \tl_clear:N \l__image_pagebox_tl
25341     \__image_extract_bb:n {#1}
25342 }
25343 \cs_new_eq:NN \__driver_image_getbb_png:n \__driver_image_getbb_jpg:n
25344 \cs_new_protected:Npn \__driver_image_getbb_pdf:n #1
25345 {
25346     \tl_clear:N \l__image_decode_tl
25347     \bool_set_false:N \l__image_interpolate_bool
25348     \__image_extract_bb:n {#1}
25349 }
25350 </dvipdfmx>

```

(End definition for __driver_image_getbb_eps:n and others.)

\g__driver_image_int Used to track the object number associated with each image.

```

25351 \int_new:N \g__driver_image_int

```

(End definition for \g__driver_image_int.)

```

\__driver_image_include_eps:n The special syntax depends on the file type. There is a difference in how PDF images
\__driver_image_include_jpg:n are best handled between dvipdfmx and xdvipdfmx: for the latter it is better to use the
\__driver_image_include_pdf:n primitive route. The relevant code for that is included later in this file.
\__driver_image_include_png:n 25352 \cs_new_protected:Npn \__driver_image_include_eps:n #1
\__driver_image_include_auxi:nn 25353 {
\__driver_image_include_auxii:nnn 25354     \tex_special:D { PSfile = #1 }
\__driver_image_include_auxii:xnn 25355 }
\__driver_image_include_auxiii:nnn 25356 \cs_new_protected:Npn \__driver_image_include_jpg:n #1
25357 { \__driver_image_include_auxi:nn {#1} { image } }
25358 \cs_new_eq:NN \__driver_image_include_png:n \__driver_image_include_jpg:n
25359 (*dvipdfmx)
25360 \cs_new_protected:Npn \__driver_image_include_pdf:n #1
25361 { \__driver_image_include_auxi:nn {#1} { epdf } }
25362 </dvipdfmx>

```

Image inclusion is set up to use the fact that each image is stored in the PDF as an XObject. This means that we can include repeated images only once and refer to them. To allow that, track the nature of each image: much the same as for the direct PDF mode case.

```

25363 \cs_new_protected:Npn \__driver_image_include_auxi:nn #1#2

```



```

25364 {
25365   \_driver_image_include_auxii:xnn
25366   {
25367     \tl_if_empty:NF \l__image_pagebox_tl
25368     { : \l__image_pagebox_tl }
25369     \int_compare:nNnT \l__image_page_int > 1
25370     { :P \int_use:N \l__image_page_int }
25371     \tl_if_empty:NF \l__image_decode_tl
25372     { :D \l__image_decode_tl }
25373     \bool_if:NT \l__image_interpolate_bool
25374     { :I }
25375   }
25376   {#1} {#2}
25377 }
25378 \cs_new_protected:Npn \_driver_image_include_auxiii:nnn #1#2#3
25379 {
25380   \int_if_exist:cTF { c__image_ #2#1 _int }
25381   {
25382     \tex_special:D
25383     { pdf:usexobj~@image \int_use:c { c__image_ #2#1 _int } }
25384   }
25385   { \_driver_image_include_auxiii:nn {#2} {#1} {#3} }
25386 }
25387 \cs_generate_variant:Nn \_driver_image_include_auxii:nnn { x }

```

Inclusion using the specials is relatively straight-forward, but there is one wrinkle. To get the pagebox correct for PDF images in all cases, it is necessary to provide both that information and the bbox argument: odd things happen otherwise!

```

25388 \cs_new_protected:Npn \_driver_image_include_auxiii:nnn #1#2#3
25389 {
25390   \int_gincr:N \g__driver_image_int
25391   \int_const:cn { c__image_ #1#2 _int } { \g__driver_image_int }
25392   \tex_special:D
25393   {
25394     pdf:#3~
25395     @image \int_use:c { c__image_ #1#2 _int }
25396     \int_compare:nNnT \l__image_page_int > 1
25397     { page ~ \int_use:N \l__image_page_int \c_space_tl }
25398     \tl_if_empty:NF \l__image_pagebox_tl
25399     {
25400       pagebox ~ \l__image_pagebox_tl \c_space_tl
25401       bbox ~
25402         \dim_to_decimal_in_bp:n \l__image_llx_dim \c_space_tl
25403         \dim_to_decimal_in_bp:n \l__image_lly_dim \c_space_tl
25404         \dim_to_decimal_in_bp:n \l__image_urx_dim \c_space_tl
25405         \dim_to_decimal_in_bp:n \l__image_ury_dim \c_space_tl
25406     }
25407     (#1)
25408     \bool_lazy_or:nnT
25409     { \l__image_interpolate_bool }
25410     { ! \tl_if_empty_p:N \l__image_decode_tl }
25411     {
25412       <<
25413       \tl_if_empty:NF \l__image_decode_tl

```

```

25414         { /Decode~[ \l__image_decode_tl ] }
25415         \bool_if:NT \l__image_interpolate_bool
25416         { /Interpolate~true> }
25417     >>
25418 }
25419 }
25420 }

```

(End definition for _driver_image_include_eps:n and others.)

```

25421 </dvipdfmx | xdvipdfmx>

```

44.10 xdvipdfmx driver

```

25422 (*xdvipdfmx)

```

44.11 Images

For xdvipdfmx, there are two primitives that allow us to obtain the bounding box without needing `extractbb`. The only complexity is passing the various minor variations to a common core process. The \TeX primitive omits the text box from the page box specification, so there is also some “trimming” to do here.

```

\_driver_image_getbb_jpg:n
\_driver_image_getbb_pdf:n
\_driver_image_getbb_png:n
    \_driver_image_getbb_auxi:nN
    \_driver_image_getbb_auxii:nNn
    \_driver_image_getbb_auxii:VnN
    \_driver_image_getbb_auxiii:nNnn
    \_driver_image_getbb_auxiv:nNnn
    \_driver_image_getbb_auxiv:VnNnn
    \_driver_image_getbb_auxv:nNnn
    \_driver_image_getbb_auxv:nNnn
    \_driver_image_getbb_pagebox:w
25423 \cs_new_protected:Npn \_driver_image_getbb_jpg:n #1
25424 {
25425     \int_zero:N \l__image_page_int
25426     \tl_clear:N \l__image_pagebox_tl
25427     \_driver_image_getbb_auxi:nN {#1} \xetex_picfile:D
25428 }
25429 \cs_new_eq:NN \_driver_image_getbb_png:n \_driver_image_getbb_jpg:n
25430 \cs_new_protected:Npn \_driver_image_getbb_pdf:n #1
25431 {
25432     \tl_clear:N \l__image_decode_tl
25433     \bool_set_false:N \l__image_interpolate_bool
25434     \_driver_image_getbb_auxi:nN {#1} \xetex_pdffile:D
25435 }
25436 \cs_new_protected:Npn \_driver_image_getbb_auxi:nN #1#2
25437 {
25438     \int_compare:nNnTF \l__image_page_int > 1
25439     { \_driver_image_getbb_auxii:VnN \l__image_page_int {#1} #2 }
25440     { \_driver_image_getbb_auxiii:nNnn {#1} #2 }
25441 }
25442 \cs_new_protected:Npn \_driver_image_getbb_auxii:nNn #1#2#3
25443 { \_driver_image_getbb_aux:nNnn {#2} #3 { :P #1 } { page #1 } }
25444 \cs_generate_variant:Nn \_driver_image_getbb_auxii:nNn { V }
25445 \cs_new_protected:Npn \_driver_image_getbb_auxiii:nNnn #1#2#3#4
25446 {
25447     \tl_if_empty:NTF \l__image_pagebox_tl
25448     { \_driver_image_getbb_auxiv:VnNnn \l__image_pagebox_tl }
25449     { \_driver_image_getbb_auxv:nNnn }
25450     {#1} #2 {#3} {#4}
25451 }
25452 \cs_new_protected:Npn \_driver_image_getbb_auxiv:nNnn #1#2#3#4#5
25453 {
25454     \use:x
25455     {

```

```

25456 \_driver_image_getbb_auxv:nNnn {#2} #3 { : #1 #4 }
25457 { #5 ~ \_driver_image_getbb_pagebox:w #1 }
25458 }
25459 }
25460 \cs_generate_variant:Nn \_driver_image_getbb_auxiv:nnNnn { V }
25461 \cs_new_protected:Npn \_driver_image_getbb_auxv:nNnn #1#2#3#4
25462 {
25463 \dim_zero:N \l__image_llx_dim
25464 \dim_zero:N \l__image_lly_dim
25465 \dim_if_exist:cTF { c__image_ #1#3 _urx_dim }
25466 {
25467 \dim_set_eq:Nc \l__image_urx_dim { c__image_ #1#3 _urx_dim }
25468 \dim_set_eq:Nc \l__image_ury_dim { c__image_ #1#3 _ury_dim }
25469 }
25470 { \_driver_image_getbb_auxvi:nNnn {#1} #2 {#3} {#4} }
25471 }
25472 \cs_new_protected:Npn \_driver_image_getbb_auxvi:nNnn #1#2#3#4
25473 {
25474 \hbox_set:Nn \l__image_tmp_box { #2 #1 ~ #4 }
25475 \dim_set:Nn \l__image_utx_dim { \box_wd:N \l__image_tmp_box }
25476 \dim_set:Nn \l__image_ury_dim { \box_ht:N \l__image_tmp_box }
25477 \dim_const:cn { c__image_ #1#3 _urx_dim }
25478 { \l__image_urx_dim }
25479 \dim_const:cn { c__image_ #1#3 _ury_dim }
25480 { \l__image_ury_dim }
25481 }
25482 \cs_new:Npn \_driver_image_getbb_pagebox:w #1 box {#1}

```

(End definition for _driver_image_getbb_jpg:n and others.)

_driver_image_include_pdf:n For PDF images, properly supporting the `pagebox` concept in X_YTeX is best done using the `\xetex_pdffile:D` primitive. The syntax here is the same as for the image measurement part, although we know at this stage that there must be some valid setting for `\l__image_pagebox_tl`.

```

25483 \cs_new_protected:Npn \_driver_image_include_pdf:n #1
25484 {
25485 \xetex_pdffile:D "#1" ~
25486 \int_compare:nNnT \l__image_page_int > 0
25487 { page~ \int_use:N \l__image_page_int }
25488 \_driver_image_getbb_auxiv:VnNnn \l__image_pagebox_tl
25489 }

```

(End definition for _driver_image_include_pdf:n.)

```

25490 </xdvipdfmx>

```

44.12 Drawing commands: pdfmode and (x)dvipdfmx

Both `pdfmode` and `(x)dvipdfmx` directly produce PDF output and understand a shared set of specials for drawing commands.

```

25491 (*dvipdfmx | pdfmode | xdvipdfmx)

```

44.13 Drawing

`_driver_draw_literal:n` Pass data through using a dedicated interface.

`_driver_draw_literal:x` 25492 `\cs_new_eq:NN _driver_draw_literal:n _driver_literal:n`
25493 `\cs_generate_variant:Nn _driver_draw_literal:n { x }`
(End definition for _driver_draw_literal:n.)

`_driver_draw_begin:` No special requirements here, so simply set up a drawing scope.
`_driver_draw_end:` 25494 `\cs_new_protected:Npn _driver_draw_begin:`
25495 `{ _driver_draw_scope_begin: }`
25496 `\cs_new_protected:Npn _driver_draw_end:`
25497 `{ _driver_draw_scope_end: }`
(End definition for _driver_draw_begin: and _driver_draw_end:.)

`_driver_draw_scope_begin:` In contrast to a general scope, a drawing scope is always done using the PDF operators
`_driver_draw_scope_end:` so is the same for all relevant drivers.

25498 `\cs_new_protected:Npn _driver_draw_scope_begin:`
25499 `{ _driver_draw_literal:n { q } }`
25500 `\cs_new_protected:Npn _driver_draw_scope_end:`
25501 `{ _driver_draw_literal:n { Q } }`
(End definition for _driver_draw_scope_begin: and _driver_draw_scope_end:.)

`_driver_draw_moveto:nn` Path creation operations all resolve directly to PDF primitive steps, with only the need to
`_driver_draw_lineto:nn` convert to bp. Notice that x-type expansion is included here to ensure that any variable
`_driver_draw_curveto:nnnnnn` values are forced to literals before any possible caching.
`_driver_draw_rectangle:nnnn`

25502 `\cs_new_protected:Npn _driver_draw_moveto:nn #1#2`
25503 `{`
25504 `_driver_draw_literal:x`
25505 `{ \dim_to_decimal_in_bp:n {#1} ~ \dim_to_decimal_in_bp:n {#2} ~ m }`
25506 `}`
25507 `\cs_new_protected:Npn _driver_draw_lineto:nn #1#2`
25508 `{`
25509 `_driver_draw_literal:x`
25510 `{ \dim_to_decimal_in_bp:n {#1} ~ \dim_to_decimal_in_bp:n {#2} ~ l }`
25511 `}`
25512 `\cs_new_protected:Npn _driver_draw_curveto:nnnnnn #1#2#3#4#5#6`
25513 `{`
25514 `_driver_draw_literal:x`
25515 `{`
25516 `\dim_to_decimal_in_bp:n {#1} ~ \dim_to_decimal_in_bp:n {#2} ~`
25517 `\dim_to_decimal_in_bp:n {#3} ~ \dim_to_decimal_in_bp:n {#4} ~`
25518 `\dim_to_decimal_in_bp:n {#5} ~ \dim_to_decimal_in_bp:n {#6} ~`
25519 `c`
25520 `}`
25521 `}`
25522 `\cs_new_protected:Npn _driver_draw_rectangle:nnnn #1#2#3#4`
25523 `{`
25524 `_driver_draw_literal:x`
25525 `{`
25526 `\dim_to_decimal_in_bp:n {#1} ~ \dim_to_decimal_in_bp:n {#2} ~`
25527 `\dim_to_decimal_in_bp:n {#3} ~ \dim_to_decimal_in_bp:n {#4} ~`

```

25528         re
25529     }
25530 }

```

(End definition for `_driver_draw_moveto:nn` and others.)

The even-odd rule here can be implemented as a simply switch.

```

\__driver\_draw\_evenodd\_rule:
\__driver\_draw\_nonzero\_rule:
\g\_driver\_draw\_eor\_bool
25531 \cs\_new\_protected:Npn \__driver\_draw\_evenodd\_rule:
25532 { \bool\_gset\_true:N \g\_driver\_draw\_eor\_bool }
25533 \cs\_new\_protected:Npn \__driver\_draw\_nonzero\_rule:
25534 { \bool\_gset\_false:N \g\_driver\_draw\_eor\_bool }
25535 \bool\_new:N \g\_driver\_draw\_eor\_bool

```

(End definition for `_driver_draw_evenodd_rule:`, `_driver_draw_nonzero_rule:`, and `\g_driver_draw_eor_bool`.)

Converting paths to output is again a case of mapping directly to PDF operations.

```

\__driver\_draw\_closepath:
\__driver\_draw\_stroke:
\__driver\_draw\_closestroke:
\__driver\_draw\_fill:
\__driver\_draw\_fillstroke:
\__driver\_draw\_clip:
\__driver\_draw\_discardpath:
25536 \cs\_new\_protected:Npn \__driver\_draw\_closepath:
25537 { \__driver\_draw\_literal:n { h } }
25538 \cs\_new\_protected:Npn \__driver\_draw\_stroke:
25539 { \__driver\_draw\_literal:n { S } }
25540 \cs\_new\_protected:Npn \__driver\_draw\_closestroke:
25541 { \__driver\_draw\_literal:n { s } }
25542 \cs\_new\_protected:Npn \__driver\_draw\_fill:
25543 {
25544     \__driver\_draw\_literal:x
25545     { f \bool\_if:NT \g\_driver\_draw\_eor\_bool * }
25546 }
25547 \cs\_new\_protected:Npn \__driver\_draw\_fillstroke:
25548 {
25549     \__driver\_draw\_literal:x
25550     { B \bool\_if:NT \g\_driver\_draw\_eor\_bool * }
25551 }
25552 \cs\_new\_protected:Npn \__driver\_draw\_clip:
25553 {
25554     \__driver\_draw\_literal:x
25555     { W \bool\_if:NT \g\_driver\_draw\_eor\_bool * }
25556 }
25557 \cs\_new\_protected:Npn \__driver\_draw\_discardpath:
25558 { \__driver\_draw\_literal:n { n } }

```

(End definition for `_driver_draw_closepath:` and others.)

Converting paths to output is again a case of mapping directly to PDF operations.

```

\__driver\_draw\_dash:nn
\__driver\_draw\_dash:n
\__driver\_draw\_linewidth:n
\__driver\_draw\_miterlimit:n
\__driver\_draw\_cap\_butt:
\__driver\_draw\_cap\_round:
\__driver\_draw\_cap\_rectangle:
\__driver\_draw\_join\_miter:
\__driver\_draw\_join\_round:
\__driver\_draw\_join\_bevel:
25559 \cs\_new\_protected:Npn \__driver\_draw\_dash:nn #1#2
25560 {
25561     \__driver\_draw\_literal:x
25562     {
25563         [ ~
25564         \clist\_map\_function:nN {#1} \__driver\_draw\_dash:n
25565         ] ~
25566         \dim\_to\_decimal\_in\_bp:n {#2} ~ d
25567     }
25568 }
25569 \cs\_new:Npn \__driver\_draw\_dash:n #1

```

```

25570 { \dim_to_decimal_in_bp:n {#1} ~ }
25571 \cs_new_protected:Npn \__driver_draw_linewidth:n #1
25572 {
25573   \__driver_draw_literal:x
25574   { \dim_to_decimal_in_bp:n {#1} ~ w }
25575 }
25576 \cs_new_protected:Npn \__driver_draw_miterlimit:n #1
25577 { \__driver_draw_literal:x { \fp_eval:n {#1} ~ M } }
25578 \cs_new_protected:Npn \__driver_draw_cap_but:
25579 { \__driver_draw_literal:n { 0 ~ J } }
25580 \cs_new_protected:Npn \__driver_draw_cap_round:
25581 { \__driver_draw_literal:n { 1 ~ J } }
25582 \cs_new_protected:Npn \__driver_draw_cap_rectangle:
25583 { \__driver_draw_literal:n { 2 ~ J } }
25584 \cs_new_protected:Npn \__driver_draw_join_miter:
25585 { \__driver_draw_literal:n { 0 ~ j } }
25586 \cs_new_protected:Npn \__driver_draw_join_round:
25587 { \__driver_draw_literal:n { 1 ~ j } }
25588 \cs_new_protected:Npn \__driver_draw_join_bevel:
25589 { \__driver_draw_literal:n { 2 ~ j } }

```

(End definition for __driver_draw_dash:nn and others.)

Yet more fast conversion, all using the FPU to allow for expressions in numerical input.

```

\__driver_draw_color_cmyk:nnnn
\__driver_draw_color_cmyk_fill:nnnn
\__driver_draw_color_cmyk_stroke:nnnn
\__driver_draw_color_cmyk_aux:nnnn
\__driver_draw_color_gray:n
\__driver_draw_color_gray_fill:n
\__driver_draw_color_gray_stroke:n
\__driver_draw_color_gray_aux:n
\__driver_draw_color_rgb:nnn
\__driver_draw_color_rgb_fill:nnn
\__driver_draw_color_rgb_stroke:nnn
\__driver_draw_color_rgb_aux:nnn
25590 \cs_new_protected:Npn \__driver_draw_color_cmyk:nnnn #1#2#3#4
25591 {
25592   \use:x
25593   {
25594     \__driver_draw_color_cmyk_aux:nnnn
25595     { \fp_eval:n {#1} }
25596     { \fp_eval:n {#2} }
25597     { \fp_eval:n {#3} }
25598     { \fp_eval:n {#4} }
25599   }
25600 }
25601 \cs_new_protected:Npn \__driver_draw_color_cmyk_aux:nnnn #1#2#3#4
25602 {
25603   \__driver_draw_literal:n
25604   { #1 ~ #2 ~ #3 ~ #4 ~ k ~ #1 ~ #2 ~ #3 ~ #4 ~ K }
25605 }
25606 \cs_new_protected:Npn \__driver_draw_color_cmyk_fill:nnnn #1#2#3#4
25607 {
25608   \__driver_draw_literal:x
25609   {
25610     \fp_eval:n {#1} ~ \fp_eval:n {#2} ~
25611     \fp_eval:n {#3} ~ \fp_eval:n {#4} ~
25612     k
25613   }
25614 }
25615 \cs_new_protected:Npn \__driver_draw_color_cmyk_stroke:nnnn #1#2#3#4
25616 {
25617   \__driver_draw_literal:x
25618   {
25619     \fp_eval:n {#1} ~ \fp_eval:n {#2} ~

```

```

25620         \fp_eval:n {#3} ~ \fp_eval:n {#4} ~
25621         K
25622     }
25623 }
25624 \cs_new_protected:Npn \__driver_draw_color_gray:n #1
25625 {
25626     \use:x
25627     { \__driver_draw_color_gray_aux:n { \fp_eval:n {#1} } }
25628 }
25629 \cs_new_protected:Npn \__driver_draw_color_gray_aux:n #1
25630 {
25631     \__driver_draw_literal:n { #1 ~ g ~ #1 ~ G }
25632 }
25633 \cs_new_protected:Npn \__driver_draw_color_gray_fill:n #1
25634 { \__driver_draw_literal:x { \fp_eval:n {#1} ~ g } }
25635 \cs_new_protected:Npn \__driver_draw_color_gray_stroke:n #1
25636 { \__driver_draw_literal:x { \fp_eval:n {#1} ~ G } }
25637 \cs_new_protected:Npn \__driver_draw_color_rgb:nnn #1#2#3
25638 {
25639     \use:x
25640     {
25641         \__driver_draw_color_rgb_aux:nnn
25642         { \fp_eval:n {#1} }
25643         { \fp_eval:n {#2} }
25644         { \fp_eval:n {#3} }
25645     }
25646 }
25647 \cs_new_protected:Npn \__driver_draw_color_rgb_aux:nnn #1#2#3
25648 {
25649     \__driver_draw_literal:n
25650     { #1 ~ #2 ~ #3 ~ rg ~ #1 ~ #2 ~ #3 ~ RG }
25651 }
25652 \cs_new_protected:Npn \__driver_draw_color_rgb_fill:nnn #1#2#3
25653 {
25654     \__driver_draw_literal:x
25655     { \fp_eval:n {#1} ~ \fp_eval:n {#2} ~ \fp_eval:n {#3} ~ rg }
25656 }
25657 \cs_new_protected:Npn \__driver_draw_color_rgb_stroke:nnn #1#2#3
25658 {
25659     \__driver_draw_literal:x
25660     { \fp_eval:n {#1} ~ \fp_eval:n {#2} ~ \fp_eval:n {#3} ~ RG }
25661 }

```

(End definition for __driver_draw_color_cmyk:nnnn and others.)

__driver_draw_transformcm:nnnnnn

The first four arguments here are floats (the affine matrix), the last two are a displacement vector. Once again, force evaluation to allow for caching.

```

25662 \cs_new_protected:Npn \__driver_draw_transformcm:nnnnnn #1#2#3#4#5#6
25663 {
25664     \__driver_draw_literal:x
25665     {
25666         \fp_eval:n {#1} ~ \fp_eval:n {#2} ~
25667         \fp_eval:n {#3} ~ \fp_eval:n {#4} ~
25668         \dim_to_decimal_in_bp:n {#5} ~ \dim_to_decimal_in_bp:n {#6} ~

```

```

25669         cm
25670     }
25671 }

```

(End definition for `_driver_draw_transformcm:nnnnnn`.)

```

\_driver\_draw\_hbox:Nnnnnnn
  \l\_driver\_tmp\_box

```

Inserting a T_EX box transformed to the requested position and using the current matrix is done using a mixture of T_EX and low-level manipulation. The offset can be handled by T_EX, so only any rotation/skew/scaling component needs to be done using the matrix operation. As this operation can never be cached, the scope is set directly not using the `draw` version.

```

25672 \cs_new_protected:Npn \_driver\_draw\_hbox:Nnnnnnn #1#2#3#4#5#6#7
25673 {
25674     \hbox_set:Nn \l\_driver\_tmp\_box
25675     {
25676         \tex_kern:D \_dim_eval:n {#6}
25677         \_driver\_scope_begin:
25678         \_driver\_draw\_transformcm:nnnnnn {#2} {#3} {#4} {#5}
25679         { Opt } { Opt }
25680         \box_move_up:nn {#7} { \box_use:N #1 }
25681         \_driver\_scope_end:
25682     }
25683     \box_set_wd:Nn \l\_driver\_tmp\_box { Opt }
25684     \box_set_ht:Nn \l\_driver\_tmp\_box { Opt }
25685     \box_set_dp:Nn \l\_driver\_tmp\_box { Opt }
25686     \box_use:N \l\_driver\_tmp\_box
25687 }
25688 \box_new:N \l\_driver\_tmp\_box

```

(End definition for `_driver_draw_hbox:Nnnnnnn` and `\l_driver_tmp_box`.)

```

25689 </dviptfm | pdfmode | xdvipdfmx>

```

44.14 dvisvgm driver

```

25690 (*dvisvgm)

```

44.14.1 Basics

```

\_driver\_literal:n

```

Unlike the other drivers, the requirements for making SVG files mean that we can't conveniently transform all operations to the current point. That makes life a bit more tricky later as that needs to be accounted for. A new line is added after each call to help to keep the output readable for debugging.

```

25691 \cs_new_protected:Npn \_driver\_literal:n #1
25692 { \tex_special:D { dvisvgm:raw~ #1 { ?nl } } }

```

(End definition for `_driver_literal:n`.)

```

\_driver\_scope_begin:
  \_driver\_scope_end:

```

A scope in SVG terms is slightly different to the other drivers as operations have to be “tied” to these not simply inside them.

```

25693 \cs_new_protected:Npn \_driver\_scope_begin:
25694 { \_driver\_literal:n { <g> } }
25695 \cs_new_protected:Npn \_driver\_scope_end:
25696 { \_driver\_literal:n { </g> } }

```

(End definition for `_driver_scope_begin:` and `_driver_scope_end:.`)

44.15 Driver-specific auxiliaries

`_driver_scope_begin:n` In SVG transformations, clips and so on are attached directly to scopes so we need a way or allowing for that. This is rather more useful than `_driver_scope_begin:` as a result. No assumptions are made about the nature of the scoped operation(s).

```
25697 \cs_new_protected:Npn \_driver_scope_begin:n #1
25698 { \_driver_literal:n { <g~ #1 > } }
```

(End definition for `_driver_scope_begin:n`.)

44.15.1 Box operations

`_driver_box_use_clip:N` Clipping in SVG is more involved than with other drivers. The first issue is that the clipping path must be defined separately from where it is used, so we need to track how many paths have applied. The naming here uses `l3cp` as the namespace with a number following. Rather than use a rectangular operation, we define the path manually as this allows it to have a depth: easier than the alternative approach of shifting content up and down using scopes to allow for the depth of the $\text{T}_{\text{E}}\text{X}$ box and keep the reference point the same!

```
25699 \cs_new_protected:Npn \_driver_box_use_clip:N #1
25700 {
25701   \int_gincr:N \g__driver_clip_path_int
25702   \_driver_literal:n
25703     { < clipPath-id = " l3cp \int_use:N \g__driver_clip_path_int " > }
25704   \_driver_literal:n
25705     {
25706       <
25707         path ~ d =
25708           "
25709             M ~ 0 ~
25710               \dim_to_decimal:n { -\box_dp:N #1 } ~
25711               L ~ \dim_to_decimal:n { \box_wd:N #1 } ~
25712               \dim_to_decimal:n { -\box_dp:N #1 } ~
25713               L ~ \dim_to_decimal:n { \box_wd:N #1 } ~
25714               \dim_to_decimal:n { \box_ht:N #1 + \box_dp:N #1 } ~
25715               L ~ 0 ~
25716               \dim_to_decimal:n { \box_ht:N #1 + \box_dp:N #1 } ~
25717               Z
25718           "
25719         />
25720       }
25721   \_driver_literal:n
25722     { < /clipPath > }
```

In general the SVG set up does not try to transform coordinates to the current point. For clipping we need to do that, so have a transformation here to get us to the right place, and a matching one just before the $\text{T}_{\text{E}}\text{X}$ box is inserted to get things back on track. The clip path needs to come between those two such that it lines up with the current point, as does the $\text{T}_{\text{E}}\text{X}$ box.

```
25723 \_driver_scope_begin:n
25724 {
25725   transform =
25726   "
```

```

25727         translate ( { ?x } , { ?y } ) ~
25728         scale ( 1 , -1 )
25729     "
25730 }
25731 \__driver_scope_begin:n
25732 {
25733     clip-path = "url ( \c_hash_str l3cp \int_use:N \g__driver_clip_path_int ) "
25734 }
25735 \__driver_scope_begin:n
25736 {
25737     transform =
25738     "
25739         scale ( -1 , 1 ) ~
25740         translate ( { ?x } , { ?y } ) ~
25741         scale ( -1 , -1 )
25742     "
25743 }
25744 \box_use:N #1
25745 \__driver_scope_end:
25746 \__driver_scope_end:
25747 \__driver_scope_end:
25748 % \skip_horizontal:n { \box_wd:N #1 }
25749 }
25750 \int_new:N \g__driver_clip_path_int

```

(End definition for __driver_box_use_clip:N and \g__driver_clip_path_int.)

__driver_box_use_rotate:Nn Rotation has a dedicated operation which includes a centre-of-rotation optional pair. That can be picked up from the driver syntax, so there is no need to worry about the transformation matrix.

```

25751 \cs_new_protected:Npn \__driver_box_use_rotate:Nn #1#2
25752 {
25753     \__driver_scope_begin:n
25754     {
25755         transform =
25756         "
25757             rotate
25758             ( \fp_eval:n { round ( -#2 , 5 ) } , ~ { ?x } , ~ { ?y } )
25759         "
25760     }
25761     \box_use:N #1
25762     \__driver_scope_end:
25763 }

```

(End definition for __driver_box_use_rotate:Nn.)

__driver_box_use_scale:Nnn In contrast to rotation, we have to account for the current position in this case. That is done using a couple of translations in addition to the scaling (which is therefore done backward with a flip).

```

25764 \cs_new_protected:Npn \__driver_box_use_scale:Nnn #1#2#3
25765 {
25766     \__driver_scope_begin:n
25767     {
25768         transform =

```

```

25769         "
25770         translate ( { ?x } , { ?y } ) ~
25771         scale
25772         (
25773             \fp_eval:n { round ( -#2 , 5 ) } ,
25774             \fp_eval:n { round ( -#3 , 5 ) }
25775         ) ~
25776         translate ( { ?x } , { ?y } ) ~
25777         scale ( -1 )
25778         "
25779     }
25780     \hbox_overlap_right:n { \box_use:N #1 }
25781     \__driver_scope_end:
25782 }

```

(End definition for __driver_box_use_scale:Nnn.)

44.16 Images

__driver_image_getbb_png:n
__driver_image_getbb_jpg:n

These can be included by extracting the bounding box data.

```

25783 \cs_new_eq:NN \__driver_image_getbb_png:n \__image_extract_bb:n
25784 \cs_new_eq:NN \__driver_image_getbb_jpg:n \__image_extract_bb:n

```

(End definition for __driver_image_getbb_png:n and __driver_image_getbb_jpg:n.)

_driver_image_include_png:n
_driver_image_include_jpg:n
_driver_image_include_bitmap_quote:w

The driver here has built-in support for basic image inclusion (see `dvisvgm.def` for a more complex approach, needed if clipping, *etc.*, is covered at the image driver level). The only issue is that `#1` must be quote-corrected. The `dvisvgm:img` operation quotes the file name, but if it is already quoted (contains spaces) then we have an issue: we simply strip off any quotes as a result.

```

25785 \cs_new_protected:Npn \__driver_image_include_png:n #1
25786 {
25787     \tex_special:D
25788     {
25789         dvisvgm:img~
25790         \dim_to_decimal:n { \l__image_ury_dim } ~
25791         \dim_to_decimal:n { \l__image_ury_dim } ~
25792         \__driver_image_include_bitmap_quote:w #1 " " \q_stop
25793     }
25794 }
25795 \cs_new_eq:NN \__driver_image_include_jpg:n \__driver_image_include_png:n
25796 \cs_new:Npn \__driver_image_include_bitmap_quote:w #1 " #2 " #3 \q_stop { #1#2 }

```

(End definition for __driver_image_include_png:n, __driver_image_include_jpg:n, and __driver_image_include_bitmap_quote:w.)

44.17 Drawing

__driver_draw_literal:n
__driver_draw_literal:x

The same as the more general literal call.

```

25797 \cs_new_eq:NN \__driver_draw_literal:n \__driver_literal:n
25798 \cs_generate_variant:Nn \__driver_draw_literal:n { x }

```

(End definition for __driver_draw_literal:n.)

`__driver_draw_begin:` A drawing needs to be set up such that the co-ordinate system is translated. That is
`__driver_draw_end:` done inside a scope, which as described below

```

25799 \cs_new_protected:Npn \__driver_draw_begin:
25800 {
25801   \__driver_draw_scope_begin:
25802   \__driver_draw_scope:n { transform="translate({?x},{?y})~scale(1,-1)" }
25803 }
25804 \cs_new_protected:Npn \__driver_draw_end:
25805 { \__driver_draw_scope_end: }

```

(End definition for `__driver_draw_begin:` and `__driver_draw_end:.`)

`__driver_draw_scope_begin:` Several settings that with other drivers are “stand alone” have to be given as part of
`__driver_draw_scope_end:` a scope in SVG. As a result, there is a need to provide a mechanism to automatically
`__driver_draw_scope:n` close these extra scopes. That is done using a dedicated function and a pair of tracking
`__driver_draw_scope:x` variables. Within each graphics scope we use a global variable to do the work, with a
`\g__driver_draw_scope_int` group used to save the value between scopes. The result is that no direct action is needed
`\l__driver_draw_scope_int` when creating a scope.

```

25806 \cs_new_protected:Npn \__driver_draw_scope_begin:
25807 {
25808   \int_set_eq:NN
25809   \l__driver_draw_scope_int
25810   \g__driver_draw_scope_int
25811   \group_begin:
25812   \int_gzero:N \g__driver_draw_scope_int
25813 }
25814 \cs_new_protected:Npn \__driver_draw_scope_end:
25815 {
25816   \prg_replicate:nn
25817   { \g__driver_draw_scope_int }
25818   { \__driver_draw_literal:n { </g> } }
25819   \group_end:
25820   \int_gset_eq:NN
25821   \g__driver_draw_scope_int
25822   \l__driver_draw_scope_int
25823 }
25824 \cs_new_protected:Npn \__driver_draw_scope:n #1
25825 {
25826   \__driver_draw_literal:n { <g~ #1 > }
25827   \int_gincr:N \g__driver_draw_scope_int
25828 }
25829 \cs_generate_variant:Nn \__driver_draw_scope:n { x }
25830 \int_new:N \g__driver_draw_scope_int
25831 \int_new:N \l__driver_draw_scope_int

```

(End definition for `__driver_draw_scope_begin:` and others.)

`__driver_draw_moveto:nn` Once again, some work is needed to get path constructs correct. Rather than write the
`__driver_draw_lineto:nn` values as they are given, the entire path needs to be collected up before being output
`__driver_draw_rectangle:nnnn` in one go. For that we use a dedicated storage routine, which adds spaces as required.
`__driver_draw_curveto:nnnnnn` Since paths should be fully expanded there is no need to worry about the internal x-type
`__driver_draw_add_to_path:n` expansion.

```

\g__driver_draw_path_tl
25832 \cs_new_protected:Npn \__driver_draw_moveto:nn #1#2

```

```

25833 {
25834   \__driver_draw_add_to_path:n
25835   { M ~ \dim_to_decimal:n {#1} ~ \dim_to_decimal:n {#2} }
25836 }
25837 \cs_new_protected:Npn \__driver_draw_lineto:nn #1#2
25838 {
25839   \__driver_draw_add_to_path:n
25840   { L ~ \dim_to_decimal:n {#1} ~ \dim_to_decimal:n {#2} }
25841 }
25842 \cs_new_protected:Npn \__driver_draw_rectangle:nnnn #1#2#3#4
25843 {
25844   \__driver_draw_add_to_path:n
25845   {
25846     M ~ \dim_to_decimal:n {#1} ~ \dim_to_decimal:n {#2}
25847     h ~ \dim_to_decimal:n {#3} ~
25848     v ~ \dim_to_decimal:n {#4} ~
25849     h ~ \dim_to_decimal:n { -#3 } ~
25850     Z
25851   }
25852 }
25853 \cs_new_protected:Npn \__driver_draw_curveto:nnnnnn #1#2#3#4#5#6
25854 {
25855   \__driver_draw_add_to_path:n
25856   {
25857     C ~
25858     \dim_to_decimal:n {#1} ~ \dim_to_decimal:n {#2} ~
25859     \dim_to_decimal:n {#3} ~ \dim_to_decimal:n {#4} ~
25860     \dim_to_decimal:n {#5} ~ \dim_to_decimal:n {#6}
25861   }
25862 }
25863 \cs_new_protected:Npn \__driver_draw_add_to_path:n #1
25864 {
25865   \tl_gset:Nx \g__driver_draw_path_tl
25866   {
25867     \g__driver_draw_path_tl
25868     \tl_if_empty:NF \g__driver_draw_path_tl { \c_space_tl }
25869     #1
25870   }
25871 }
25872 \tl_new:N \g__driver_draw_path_tl

```

(End definition for __driver_draw_moveto:nn and others.)

__driver_draw_evenodd_rule: The fill rules here have to be handled as scopes.

```

\__driver_draw_nonzero_rule:
25873 \cs_new_protected:Npn \__driver_draw_evenodd_rule:
25874 { \__driver_draw_scope:n { fill-rule="evenodd" } }
25875 \cs_new_protected:Npn \__driver_draw_nonzero_rule:
25876 { \__driver_draw_scope:n { fill-rule="nonzero" } }

```

(End definition for __driver_draw_evenodd_rule: and __driver_draw_nonzero_rule:.)

```

\__driver_draw_path:n
\__driver_draw_closepath:
\__driver_draw_stroke:
\__driver_draw_closestroke:
\__driver_draw_fill:
\__driver_draw_fillstroke:
\__driver_draw_clip:
\__driver_draw_discardpath:
\g__driver_draw_clip_bool
\g__driver_draw_path_int

```

Setting fill and stroke effects and doing clipping all has to be done using scopes. This means setting up the various requirements in a shared auxiliary which deals with the bits and pieces. Clipping paths are reused for path drawing: not essential but avoids

constructing them twice. Discarding a path needs a separate function as it's not quite the same.

```

25877 \cs_new_protected:Npn \__driver_draw_closepath:
25878 { \__driver_draw_add_to_path:n { Z } }
25879 \cs_new_protected:Npn \__driver_draw_path:n #1
25880 {
25881   \bool_if:NTF \g__driver_draw_clip_bool
25882   {
25883     \int_gincr:N \g__driver_clip_path_int
25884     \__driver_draw_literal:x
25885     {
25886       < clipPath-id = " l3cp \int_use:N \g__driver_clip_path_int " >
25887       { ?nl }
25888       <path-d=" \g__driver_draw_path_tl "/> { ?nl }
25889       < /clipPath > { ? nl }
25890       <
25891         use-xlink:href =
25892         "\c_hash_str l3path \int_use:N \g__driver_path_int " ~
25893         #1
25894       />
25895     }
25896     \__driver_draw_scope:x
25897     {
25898       clip-path =
25899       "url( \c_hash_str l3cp \int_use:N \g__driver_clip_path_int)"
25900     }
25901   }
25902   {
25903     \__driver_draw_literal:x
25904     { <path ~ d=" \g__driver_draw_path_tl " ~ #1 /> }
25905   }
25906   \tl_gclear:N \g__driver_draw_path_tl
25907   \bool_gset_false:N \g__driver_draw_clip_bool
25908 }
25909 \int_new:N \g__driver_path_int
25910 \cs_new_protected:Npn \__driver_draw_stroke:
25911 { \__driver_draw_path:n { style="fill:none" } }
25912 \cs_new_protected:Npn \__driver_draw_closestroke:
25913 {
25914   \__driver_draw_closepath:
25915   \__driver_draw_stroke:
25916 }
25917 \cs_new_protected:Npn \__driver_draw_fill:
25918 { \__driver_draw_path:n { style="stroke:none" } }
25919 \cs_new_protected:Npn \__driver_draw_fillstroke:
25920 { \__driver_draw_path:n { } }
25921 \cs_new_protected:Npn \__driver_draw_clip:
25922 { \bool_gset_true:N \g__driver_draw_clip_bool }
25923 \bool_new:N \g__driver_draw_clip_bool
25924 \cs_new_protected:Npn \__driver_draw_discardpath:
25925 {
25926   \bool_if:NT \g__driver_draw_clip_bool
25927   {
25928     \int_gincr:N \g__driver_clip_path_int

```

```

25929     \_driver_draw_literal:x
25930     {
25931         < clipPath-id = " l3cp \int_use:N \g__driver_clip_path_int " >
25932             { ?nl }
25933             <path-d=" \g__driver_draw_path_tl "/> { ?nl }
25934             < /clipPath >
25935         }
25936     \_driver_draw_scope:x
25937     {
25938         clip-path =
25939             "url( \c_hash_str l3cp \int_use:N \g__driver_clip_path_int)"
25940     }
25941 }
25942 \tl_gclear:N \g__driver_draw_path_tl
25943 \bool_gset_false:N \g__driver_draw_clip_bool
25944 }

```

(End definition for _driver_draw_path:n and others.)

All of these ideas are properties of scopes in SVG. The only slight complexity is converting the dash array properly (doing any required maths).

```

\__driver_draw_dash:nn
\__driver_draw_dash:n
\__driver_draw_dash_aux:nn
\__driver_draw_linewidth:n
\__driver_draw_miterlimit:n
\__driver_draw_cap_butt:
\__driver_draw_cap_round:
\__driver_draw_cap_rectangle:
\__driver_draw_join_miter:
\__driver_draw_join_round:
\__driver_draw_join_bevel:
25945 \cs_new_protected:Npn \_driver_draw_dash:nn #1#2
25946 {
25947     \use:x
25948     {
25949         \__driver_draw_dash_aux:nn
25950         { \clist_map_function:nn {#1} \__driver_draw_dash:n }
25951         { \dim_to_decimal:n {#2} }
25952     }
25953 }
25954 \cs_new:Npn \_driver_draw_dash:n #1
25955 { , \dim_to_decimal_in_bp:n {#1} }
25956 \cs_new_protected:Npn \_driver_draw_dash_aux:nn #1#2
25957 {
25958     \__driver_draw_scope:x
25959     {
25960         stroke-dasharray =
25961         "
25962             \tl_if_empty:oTF { \use_none:n #1 }
25963             { none }
25964             { \use_none:n #1 }
25965         " ~
25966         stroke-offset=" #2 "
25967     }
25968 }
25969 \cs_new_protected:Npn \_driver_draw_linewidth:n #1
25970 { \__driver_draw_scope:x { stroke-width=" \dim_to_decimal:n {#1} " } }
25971 \cs_new_protected:Npn \_driver_draw_miterlimit:n #1
25972 { \__driver_draw_scope:x { stroke-miterlimit=" \fp_eval:n {#1} " } }
25973 \cs_new_protected:Npn \_driver_draw_cap_butt:
25974 { \__driver_draw_scope:n { stroke-linecap="butt" } }
25975 \cs_new_protected:Npn \_driver_draw_cap_round:
25976 { \__driver_draw_scope:n { stroke-linecap="round" } }
25977 \cs_new_protected:Npn \_driver_draw_cap_rectangle:

```

```

25978 { \_driver\_draw\_scope:n { stroke-linecap="square" } }
25979 \cs\_new\_protected:Npn \_driver\_draw\_join\_miter:
25980 { \_driver\_draw\_scope:n { stroke-linejoin="miter" } }
25981 \cs\_new\_protected:Npn \_driver\_draw\_join\_round:
25982 { \_driver\_draw\_scope:n { stroke-linejoin="round" } }
25983 \cs\_new\_protected:Npn \_driver\_draw\_join\_bevel:
25984 { \_driver\_draw\_scope:n { stroke-linejoin="bevel" } }

```

(End definition for _driver_draw_dash:nn and others.)

SVG only works with RGB colors, so there is some conversion to do. The values also need to be given as percentages, which means a little more maths.

```

\_driver\_draw\_color\_cmyk:nnnn
\_driver\_draw\_color\_cmyk\_fill:nnnn
\_driver\_draw\_color\_cmyk\_stroke:nnnn
\_driver\_draw\_color\_gray:n
  \_driver\_draw\_color\_gray\_fill:n
  \_driver\_draw\_color\_gray\_stroke:n
\_driver\_draw\_color\_rgb:nnnn
  \_driver\_draw\_color\_rgb\_fill:nnnn
  \_driver\_draw\_color\_rgb\_stroke:nnnn
25985 \cs\_new\_protected:Npn \_driver\_draw\_color\_cmyk\_aux:NNnnnnn #1#2#3#4#5#6
25986 {
25987   \use:x
25988   {
25989     \_driver\_draw\_color\_rgb\_auxii:nnn
25990     { \fp\_eval:n { -100 * ( (#3) * ( 1 - (#6) ) - 1 ) } }
25991     { \fp\_eval:n { -100 * ( (#4) * ( 1 - (#6) ) + #6 - 1 ) } }
25992     { \fp\_eval:n { -100 * ( (#5) * ( 1 - (#6) ) + #6 - 1 ) } }
25993   }
25994   #1 #2
25995 }
25996 \cs\_new\_protected:Npn \_driver\_draw\_color\_cmyk:nnnn
25997 { \_driver\_draw\_color\_cmyk\_aux:NNnnnnn \c\_true\_bool \c\_true\_bool }
25998 \cs\_new\_protected:Npn \_driver\_draw\_color\_cmyk\_fill:nnnn
25999 { \_driver\_draw\_color\_cmyk\_aux:NNnnnnn \c\_false\_bool \c\_true\_bool }
26000 \cs\_new\_protected:Npn \_driver\_draw\_color\_cmyk\_stroke:nnnn
26001 { \_driver\_draw\_color\_cmyk\_aux:NNnnnnn \c\_true\_bool \c\_false\_bool }
26002 \cs\_new\_protected:Npn \_driver\_draw\_color\_gray\_aux:NNn #1#2#3
26003 {
26004   \use:x
26005   {
26006     \_driver\_draw\_color\_gray\_aux:nnN
26007     { \fp\_eval:n { 100 * (#3) } }
26008   }
26009   #1 #2
26010 }
26011 \cs\_new\_protected:Npn \_driver\_draw\_color\_gray\_aux:nnN #1
26012 { \_driver\_draw\_color\_rgb\_auxii:nnnNN {#1} {#1} {#1} }
26013 \cs\_generate\_variant:Nn \_driver\_draw\_color\_gray\_aux:nnN { x }
26014 \cs\_new\_protected:Npn \_driver\_draw\_color\_gray:n
26015 { \_driver\_draw\_color\_gray\_aux:NNn \c\_true\_bool \c\_true\_bool }
26016 \cs\_new\_protected:Npn \_driver\_draw\_color\_gray\_fill:n
26017 { \_driver\_draw\_color\_gray\_aux:NNn \c\_false\_bool \c\_true\_bool }
26018 \cs\_new\_protected:Npn \_driver\_draw\_color\_gray\_stroke:n
26019 { \_driver\_draw\_color\_gray\_aux:NNn \c\_true\_bool \c\_false\_bool }
26020 \cs\_new\_protected:Npn \_driver\_draw\_color\_rgb\_auxi:NNnnn #1#2#3#4#5
26021 {
26022   \use:x
26023   {
26024     \_driver\_draw\_color\_rgb\_auxii:nnnNN
26025     { \fp\_eval:n { 100 * (#3) } }
26026     { \fp\_eval:n { 100 * (#4) } }

```



```

26027         { \fp_eval:n { 100 * (#5) } }
26028     }
26029     #1 #2
26030 }
26031 \cs_new_protected:Npn \__driver_draw_color_rgb_auxii:nnnNN #1#2#3#4#5
26032 {
26033     \__driver_draw_scope:x
26034     {
26035         \bool_if:NT #4
26036         {
26037             fill =
26038             "
26039             rgb
26040             (
26041                 #1 \c_percent_str ,
26042                 #2 \c_percent_str ,
26043                 #3 \c_percent_str
26044             )
26045             "
26046             \bool_if:NT #5 { ~ }
26047         }
26048         \bool_if:NT #5
26049         {
26050             stroke =
26051             "
26052             rgb
26053             (
26054                 #1 \c_percent_str ,
26055                 #2 \c_percent_str ,
26056                 #3 \c_percent_str
26057             )
26058             "
26059         }
26060     }
26061 }
26062 \cs_new_protected:Npn \__driver_draw_color_rgb:nnn
26063 { \__driver_draw_color_rgb_auxi:NNnnn \c_true_bool \c_true_bool }
26064 \cs_new_protected:Npn \__driver_draw_color_rgb_fill:nnn
26065 { \__driver_draw_color_rgb_auxi:NNnnn \c_false_bool \c_true_bool }
26066 \cs_new_protected:Npn \__driver_draw_color_rgb_stroke:nnn
26067 { \__driver_draw_color_rgb_auxi:NNnnn \c_true_bool \c_false_bool }

```

(End definition for __driver_draw_color_cmyk:nnnn and others.)

__driver_draw_transformcm:nnnnnn The first four arguments here are floats (the affine matrix), the last two are a displacement vector. Once again, force evaluation to allow for caching.

```

26068 \cs_new_protected:Npn \__driver_draw_transformcm:nnnnnn #1#2#3#4#5#6
26069 {
26070     \__driver_draw_scope:x
26071     {
26072         transform =
26073         "
26074         matrix
26075         (

```

```

26076         \fp_eval:n {#1} , \fp_eval:n {#2} ,
26077         \fp_eval:n {#3} , \fp_eval:n {#4} ,
26078         \dim_to_decimal:n {#5} , \dim_to_decimal:n {#6}
26079     )
26080     "
26081 }
26082 }

```

(End definition for _driver_draw_transformcm:nnnnnn.)

_driver_draw_hbox:Nnnnnnn No special savings can be made here: simply displace the box inside a scope. As there is nothing to re-box, just make the box passed of zero size.

```

26083 \cs_new_protected:Npn \_driver_draw_hbox:Nnnnnnn #1#2#3#4#5#6#7
26084 {
26085     \_driver_scope_begin:
26086     \_driver_draw_transformcm:nnnnnn {#2} {#3} {#4} {#5} {#6} {#7}
26087     \_driver_literal:n
26088     {
26089         < g~
26090         stroke="none"~
26091         transform="scale(-1,1)~translate({?x},{?y})~scale(-1,-1)"
26092         >
26093     }
26094     \box_set_wd:Nn #1 { Opt }
26095     \box_set_ht:Nn #1 { Opt }
26096     \box_set_dp:Nn #1 { Opt }
26097     \box_use:N #1
26098     \_driver_literal:n { </g> }
26099     \_driver_scope_end:
26100 }

```

(End definition for _driver_draw_hbox:Nnnnnnn.)

26101 </dvisvgm>

26102 </initex | package>

Index

The italic numbers denote the pages where the corresponding entry is described, numbers underlined point to the definition, all others indicate the places where it is used.

Symbols	
!	194
\!	8211
\"	7147, 7150, 24233
\#	6, 4428, 4460, 7147, 9517
\\$	4427, 7147, 7150, 18631
\%	4429, 7147, 9519
\&	4420, 7147, 7150, 8211, 8212
&&	194
\'	24233
\(24276
\)	24276
*	194
*	4092, 4115, 7320, 7322, 7326, 7334
**	194
+	194, 194
\,	10401
-	194, 194
\-	205, 286
\.	24233
/	194
\/	285
\:	4426
\::	36, 321, 337, 2344, 2345, 2346, 2347, 2348, 2349, 2350, 2352, 2354, 2361, 2366, 2372, 2503, 2504, 2505, 2506, 2507, 2508, 2509, 2510, 2511, 2512, 2513, 2514, 2515, 2516, 2517, 2518, 2519, 2520, 2521, 2522, 2523, 2524, 2525, 2526, 2527, 2528, 2529, 2530, 2531, 2532, 2533, 2534, 2535, 2536, 2537, 2538, 2539, 2540, 2541, 2542, 2543, 2544, 2546, 2548, 2553, 2558, 2563, 2600, 2601, 2602, 2603, 2606
\::N	36, 2348, 2515, 2521, 2522, 2523, 2524, 2525, 2537, 2538, 2539, 2603
\::V	36, 2366, 2506, 2512, 2523, 2525, 2527, 2529
\::V_unbraced	2545
\::c	36, 2350, 2504, 2509, 2516, 2521, 2526, 2527, 2528, 2529, 2530, 2542, 2543
\::error	243, 23010
\::f	36, 2354, 2508, 2511, 2513, 2514, 2521, 2532, 2533, 2535, 2536, 2602
\::f_unbraced	2545
\::n	36, 2347, 2504, 2505, 2506, 2507, 2508, 2517, 2522, 2523, 2526, 2527, 2530, 2531, 2532, 2533, 2535, 2536, 2538, 2540, 2541, 2543, 2600, 2603
\::o	36, 2352, 2505, 2509, 2510, 2511, 2512, 2513, 2518, 2519, 2522, 2524, 2526, 2528, 2531, 2534, 2535, 2536, 2539, 2541, 2544, 2601
\::o_unbraced	2545, 2600, 2601, 2602, 2603
\::p	36, 321, 2349
\::v	36, 2366, 2507
\::v_unbraced	2545
\::x	36, 2361, 2503, 2515, 2516, 2517, 2518, 2519, 2520, 2537, 2538, 2539, 2540, 2541, 2542, 2543, 2544
\::x_unbraced	2545, 2606
<	194
=	194
>	194
?	194
?:	193
\\	1594, 2322, 4422, 7147, 8146, 8164, 8166, 8171, 8172, 8186, 8187, 8190, 8191, 8288, 8378, 8386, 8622, 8630, 8637, 8649, 8650, 8675, 8676, 8683, 8709, 8711, 8712, 8785, 8786, 8802, 8803, 8804, 8805, 8806, 8853, 8860, 8867, 9522, 9757, 9763, 9770, 11280, 11281, 11287, 11306, 11319, 11325, 11777, 11780, 11781, 11782, 11789, 11792, 11793, 17196, 17199, 17224, 17225, 17232, 17233, 17732, 19135, 19242, 19243, 19244, 19265, 20529, 20532, 20535, 20538, 20542, 20545, 20580, 20589, 20593, 20598, 20618, 20620, 20621, 20622, 20625, 20627, 20632, 20635, 20639, 20641, 20645, 20647, 20653, 20655, 20659, 20661, 20665, 20670, 20671, 20713, 20715, 20720, 20722, 20728, 20733, 20734, 20738, 20742, 20752, 20755, 20759, 20760, 20764, 20772, 20835, 22304
\{	4, 4423, 7147, 8209, 8803, 9516, 17973, 20538, 20545, 20593, 20635, 20671, 20760, 20764, 24288
\}	5, 4424, 7147, 8210, 8803, 9518, 20545, 20636, 20671, 20760, 20764, 24288
\^	7, 10, 103, 194, 195, 196, 197, 2014, 2626, 3072, 4425, 7147, 7150, 7152, 7158, 7220, 8225, 9447, 9482,

- 15320, 17352, 17423, 17426, 17919,
17924, 17925, 17926, 17927, 17930,
17941, 17978, 18039, 18041, 18043,
18045, 18047, 18049, 18630, 20143,
20146, 20157, 20160, 20169, 20172,
20175, 20178, 20192, 20195, 24233
~ 194
_ 4431, 7147, 7150
\^ 24233
|| 193
\~ 3093, 4430, 7147,
7150, 9520, 17963, 17967, 17973, 24233
- _ 284, 1914, 4092,
4115, 4461, 7147, 7313, 8209, 8210,
8677, 8701, 8794, 8796, 8803, 8805,
8896, 9523, 17467, 17918, 17923,
17967, 17977, 18165, 20189, 24425
- ### A
- \A 4093, 4116
\AA 24215
\aa 24215
\above 287
\abovedisplayshortskip 288
\abovedisplayskip 289
\abovewithdelims 290
abs 194
\accent 291
acos 196
acosd 196
acot 197
acotd 197
acsc 196
acscd 196
\adjdemerits 292
\adjustspacing 954
\advance 168, 184, 293
\AE 24216
\ae 24216
\afterassignment 294
\aftergroup 295
\alignmark 863
\alignstab 864
asec 196
asecd 196
asin 196
asind 196
assert commands:
 \assert_int:n 19431, 20348
atan 197
atand 197
\AtBeginDocument 518, 9170, 24657, 24702
- \atop 296
\atopwithdelims 297
\attribute 865
\attributedef 866
\automatichyphenpenalty 867
\autospacing 1127
\autoxspacing 1128
- ### B
- \badness 298
\baselineskip 299
\batchmode 300
\begin 205, 209, 13492, 25243, 25248
begin internal commands:
 __regex_begin 20272
\begincsname 868
\begingroup 13,
20, 38, 42, 48, 73, 142, 162, 274, 301
\beginL 609
\beginR 610
\belowdisplayshortskip 302
\belowdisplayskip 303
\binoppenalty 304
\bodydir 941
bool commands:
 \bool_const:Nn 243, 23035
 \bool_do_until:Nn 102, 6406
 \bool_do_until:nn 102, 6412
 \bool_do_while:Nn 102, 6406
 \bool_do_while:nn 102, 6412
 .bool_gset:N 172, 10839
 \bool_gset:Nn 99, 6265
 \bool_gset_eq:NN 99, 6261, 17910, 19724
 \bool_gset_false:N 98,
6245, 19690, 24896, 24914, 24939,
24962, 24978, 25534, 25907, 25943
 .bool_gset_inverse:N 172, 10847
 \bool_gset_true:N 98, 6245,
19731, 24894, 24965, 25532, 25922
 \bool_if:NTF 99,
238, 2191, 6273, 6282, 6283, 6401,
6403, 6407, 6409, 8264, 8269, 8274,
8279, 8284, 8780, 9718, 9725, 10616,
10811, 10820, 10986, 11011, 11025,
11042, 11076, 11104, 11123, 11125,
11130, 11137, 11161, 11207, 18756,
18765, 19137, 19210, 19215, 19231,
19258, 19378, 19604, 19612, 20801,
20806, 21782, 22184, 24905, 24909,
24926, 24930, 24934, 24946, 24953,
24957, 24969, 24973, 25211, 25260,
25373, 25415, 25545, 25550, 25555,
25881, 25926, 26035, 26046, 26048

- \bool_if:nTF 99, 101,
102, 102, 102, 103, 960, 977, 6290,
6308, 6368, 6374, 6375, 6383, 6389,
6391, 6414, 6423, 6427, 6436, 23117
- \bool_if_exist:nTF
..... 99, 6304, 10637, 10653
- \bool_if_exist_p:N 99, 6304
- \bool_if_p:N 99, 6273
- \bool_if_p:n 101, 440, 6267,
6270, 6308, 6316, 6393, 6396, 23039
- \bool_lazy_all:nTF
..... 100, 101, 101, 6363, 19011
- \bool_lazy_all_p:n 101, 6363
- \bool_lazy_and:nnTF ... 100, 101,
101, 6372, 22369, 23878, 23928, 24258
- \bool_lazy_and_p:nn .. 101, 101, 6372
- \bool_lazy_any:nTF
..... 100, 101, 101, 6378, 23680
- \bool_lazy_any_p:n
..... 101, 101, 6378, 23881
- \bool_lazy_or:nnTF
..... 100, 101, 101, 6387,
23786, 24036, 24236, 25252, 25408
- \bool_lazy_or_p:nn .. 101, 6387, 24261
- \bool_log:N 99, 6291
- \bool_log:n 99, 6285
- \bool_new:N 98,
6243, 6300, 6301, 6302, 6303, 8100,
9477, 10531, 10532, 10535, 10536,
10540, 10637, 10653, 17773, 18200,
19660, 19661, 19663, 19664, 19665,
21499, 24897, 24966, 25535, 25923
- \bool_not_p:n 101, 6393
- .bool_set:N 172, 10839
- \bool_set:Nn 99, 943, 6265
- \bool_set_eq:NN 99, 6261, 17905, 19877
- \bool_set_false:N 98,
253, 6245, 9562, 9702, 9710, 9720,
9727, 10557, 10996, 11021, 11033,
11053, 11062, 11111, 18731, 18917,
19639, 19700, 19711, 19754, 19818,
21778, 22182, 25221, 25347, 25433
- .bool_set_inverse:N 172, 10847
- \bool_set_true:N 98, 267, 6245, 9689,
10552, 10994, 11019, 11035, 11051,
11057, 11118, 18736, 18921, 19636,
19816, 19876, 21796, 21811, 21842
- \bool_show:N 99, 6291
- \bool_show:n 99, 6285
- \bool_until_do:Nn 102, 6400
- \bool_until_do:nn 102, 6412
- \bool_while_do:Nn 102, 6400
- \bool_while_do:nn 103, 6412
- \bool_xor_p:nn 102, 6394
- \c_false_bool 20, 98, 308,
331, 435, 437, 438, 438, 439, 1780,
1820, 1863, 1868, 1908, 1925, 2134,
2141, 2668, 6243, 6250, 6256, 6354,
6397, 18419, 18432, 18647, 18682,
18956, 19091, 19107, 19154, 19297,
20452, 22349, 22401, 22416, 25999,
26001, 26017, 26019, 26065, 26067
- \g_tmpa_bool 100, 6300
- \l_tmpa_bool 99, 6300
- \g_tmpb_bool 100, 6300
- \l_tmpb_bool 99, 6300
- \c_true_bool 20, 98,
308, 350, 435, 437, 438, 438, 439,
1820, 1908, 1924, 2153, 6247, 6253,
6355, 6356, 6398, 17779, 17907,
18332, 18386, 18430, 18613, 18638,
18681, 18688, 19089, 19099, 19152,
19364, 19542, 19553, 19568, 19704,
19730, 20282, 20358, 20416, 22356,
22364, 22376, 22383, 22392, 22405,
22412, 25997, 25999, 26001, 26015,
26017, 26019, 26063, 26065, 26067
- bool internal commands:
 - __bool_!:Nw 6334
 - __bool_&_0: 6346
 - __bool_&_1: 6346
 - __bool_&_2: 6346
 - __bool_(:Nw 6339
 - __bool_)_0: 6346
 - __bool_)_1: 6346
 - __bool_)_2: 6346
 - __bool_choose:NNN .. 6341, 6345, 6346
 - __bool_get_next:NN
. 437, 438, 6322, 6324, 6336, 6342,
6357, 6358, 6359, 6360, 6361, 6362
 - __bool_lazy_all:n 6363
 - __bool_lazy_any:n 6378
 - __bool_p:Nw 6344
 - __bool_show:NN 6291
 - __bool_to_str:n 6285, 6298
 - __bool_|_0: 6346
 - __bool_|_1: 6346
 - __bool_|_2: 6346
- \botmark 305
- \botmarks 611
- \box 306
- box commands:
 - \box_autosize_to_wd_and_ht:Nnn ..
..... 225, 21403
 - \box_autosize_to_wd_and_ht_plus_-
dp:Nnn 225, 21403
 - \box_clear:N 218,
218, 20851, 20858, 21535, 21595, 21642

- \box_clear_new:N [218](#), [20857](#)
- \box_clip:N [240](#), [240](#), [240](#), [22495](#)
- \box_dp:N [220](#),
[12242](#), [20883](#), [20890](#), [21184](#), [21302](#),
[21392](#), [21407](#), [21665](#), [21666](#), [21736](#),
[21738](#), [21755](#), [21769](#), [21923](#), [21941](#),
[22254](#), [22506](#), [22513](#), [22518](#), [22654](#),
[24804](#), [24806](#), [25155](#), [25157](#), [25301](#),
[25303](#), [25710](#), [25712](#), [25714](#), [25716](#)
- \box_gclear:N [218](#), [20851](#), [20860](#)
- \box_gclear_new:N [218](#), [20857](#)
- \box_gset_eq:NN ... [218](#), [20854](#), [20863](#)
- \box_gset_eq_clear:NN ... [218](#), [20871](#)
- \box_gset_to_last:N [221](#), [20931](#)
- \box_ht:N [220](#), [12241](#),
[20883](#), [20892](#), [21183](#), [21301](#), [21391](#),
[21404](#), [21407](#), [21590](#), [21637](#), [21667](#),
[21668](#), [21732](#), [21734](#), [21755](#), [21762](#),
[21922](#), [21940](#), [22252](#), [22523](#), [22531](#),
[22536](#), [22651](#), [22653](#), [24806](#), [25157](#),
[25272](#), [25303](#), [25476](#), [25714](#), [25716](#)
- \box_if_empty:NTF
..... [220](#), [20925](#), [20928](#), [20929](#)
- \box_if_empty_p:N [220](#), [20925](#)
- \box_if_exist:NTF
..... [218](#), [20858](#), [20860](#), [20879](#), [20964](#)
- \box_if_exist_p:N [218](#), [20879](#)
- \box_if_horizontal:NTF
..... [220](#), [20913](#), [20918](#), [20919](#)
- \box_if_horizontal_p:N ... [220](#), [20913](#)
- \box_if_vertical:NTF
..... [221](#), [20913](#), [20922](#), [20923](#)
- \box_if_vertical_p:N [221](#), [20913](#)
- \box_log:N [222](#), [20950](#)
- \box_log:Nnn [222](#), [20950](#)
- \box_move_down:nn [219](#), [929](#), [20902](#),
[22510](#), [22518](#), [22556](#), [22563](#), [22633](#)
- \box_move_left:nn [219](#), [20902](#)
- \box_move_right:nn [219](#), [20902](#)
- \box_move_up:nn
..... [219](#), [20902](#), [21961](#), [22249](#),
[22527](#), [22536](#), [22570](#), [22583](#), [25680](#)
- \box_new:N [218](#), [218](#),
[20843](#), [20939](#), [20940](#), [20941](#), [20942](#),
[20943](#), [21170](#), [21475](#), [21542](#), [25688](#)
- \box_resize:Nnn [21458](#)
- \box_resize_to_ht:Nn [226](#), [21321](#)
- \box_resize_to_ht_plus_dp:Nn ...
..... [226](#), [21321](#)
- \box_resize_to_wd:Nn [226](#), [21321](#)
- \box_resize_to_wd_and_ht:Nnn ...
..... [226](#), [21321](#)
- \box_resize_to_wd_and_ht_plus_dp:Nnn
dp:Nnn [227](#), [21283](#),
[21459](#), [21461](#), [21463](#), [21465](#), [22764](#)
- \box_rotate:Nn [227](#), [21171](#), [22627](#)
- \box_scale:Nnn [227](#), [21379](#), [22786](#)
- \box_set_dp:Nn [220](#), [929](#),
[20889](#), [21210](#), [21433](#), [21436](#), [21923](#),
[21941](#), [22253](#), [22513](#), [22521](#), [22559](#),
[22564](#), [22638](#), [25116](#), [25685](#), [26096](#)
- \box_set_eq:NN . [218](#), [20852](#), [20863](#),
[21652](#), [21943](#), [22257](#), [22541](#), [22588](#)
- \box_set_eq_clear:NN [218](#), [20871](#)
- \box_set_ht:Nn [220](#),
[20889](#), [21209](#), [21432](#), [21437](#), [21922](#),
[21940](#), [22251](#), [22530](#), [22539](#), [22573](#),
[22586](#), [22636](#), [25115](#), [25684](#), [26095](#)
- \box_set_to_last:N [221](#), [20931](#)
- \box_set_wd:Nn [220](#), [20889](#),
[21211](#), [21449](#), [21924](#), [21942](#), [22255](#),
[22639](#), [25114](#), [25167](#), [25683](#), [26094](#)
- \box_show:N [221](#), [20944](#)
- \box_show:Nnn [221](#), [20944](#)
- \box_trim:Nnnnn [240](#), [22498](#)
- \box_use:N [219](#),
[219](#), [20898](#), [21198](#), [21958](#), [21961](#),
[22246](#), [22249](#), [22503](#), [22511](#), [22519](#),
[22528](#), [22537](#), [22549](#), [22557](#), [22563](#),
[22571](#), [22584](#), [22634](#), [22641](#), [24810](#),
[24824](#), [24836](#), [25117](#), [25160](#), [25185](#),
[25199](#), [25306](#), [25320](#), [25332](#), [25680](#),
[25686](#), [25744](#), [25761](#), [25780](#), [26097](#)
- \box_use_clear:N [21458](#)
- \box_use_drop:N
..... [219](#), [20898](#), [21213](#), [21444](#),
[21453](#), [21468](#), [21471](#), [22039](#), [22176](#)
- \box_viewport:Nnnnn [240](#), [22544](#)
- \box_wd:N [220](#),
[12240](#), [20883](#), [20894](#), [21185](#), [21303](#),
[21393](#), [21413](#), [21669](#), [21670](#), [21734](#),
[21738](#), [21744](#), [21749](#), [21891](#), [21924](#),
[21942](#), [21959](#), [22247](#), [22256](#), [22550](#),
[22653](#), [22658](#), [22823](#), [22830](#), [24805](#),
[24812](#), [25156](#), [25162](#), [25271](#), [25302](#),
[25308](#), [25475](#), [25711](#), [25713](#), [25748](#)
- \c_empty_box
.. [218](#), [220](#), [221](#), [20852](#), [20854](#), [20939](#)
- \g_tmpa_box [221](#), [20940](#)
- \l_tmpa_box [221](#), [20940](#)
- \g_tmpb_box [221](#), [20940](#)
- \l_tmpb_box [221](#), [20940](#)
- box internal commands:
\l_box_angle_fp
.. [21159](#), [21175](#), [21176](#), [21177](#), [21206](#)
__box_autosize:Nnnn [21403](#)

- \l__box_bottom_dim [21162](#),
[21184](#), [21241](#), [21245](#), [21250](#), [21256](#),
[21261](#), [21265](#), [21274](#), [21276](#), [21293](#),
[21302](#), [21311](#), [21344](#), [21392](#), [21398](#)
 - \l__box_bottom_new_dim
[21166](#), [21210](#), [21242](#), [21253](#), [21264](#),
[21275](#), [21310](#), [21397](#), [21433](#), [21437](#)
 - \l__box_cos_fp [21160](#),
[21177](#), [21189](#), [21194](#), [21221](#), [21233](#)
 - \l__box_internal_box [21170](#), [21198](#),
[21199](#), [21205](#), [21209](#), [21210](#), [21211](#),
[21213](#), [21423](#), [21432](#), [21433](#), [21436](#),
[21437](#), [21444](#), [21449](#), [21453](#), [22500](#),
[22508](#), [22511](#), [22513](#), [22516](#), [22519](#),
[22521](#), [22523](#), [22525](#), [22528](#), [22530](#),
[22531](#), [22534](#), [22536](#), [22537](#), [22539](#),
[22541](#), [22546](#), [22554](#), [22557](#), [22559](#),
[22562](#), [22563](#), [22564](#), [22568](#), [22571](#),
[22573](#), [22581](#), [22584](#), [22586](#), [22588](#)
 - \l__box_left_dim . . . [21162](#), [21186](#),
[21241](#), [21243](#), [21252](#), [21256](#), [21261](#),
[21267](#), [21272](#), [21276](#), [21304](#), [21394](#)
 - \l__box_left_new_dim [21166](#), [21201](#),
[21212](#), [21244](#), [21255](#), [21266](#), [21277](#)
 - __box_log:nNnn [20950](#)
 - __box_resize:N
. . . [21283](#), [21332](#), [21347](#), [21359](#), [21375](#)
 - __box_resize:NNN [21283](#)
 - __box_resize_common:N
. [21314](#), [21401](#), [21421](#)
 - __box_resize_set_corners:N
. . . [21283](#), [21325](#), [21340](#), [21355](#), [21367](#)
 - \l__box_right_dim . . [21162](#), [21185](#),
[21239](#), [21245](#), [21250](#), [21254](#), [21263](#),
[21265](#), [21274](#), [21278](#), [21289](#), [21303](#),
[21309](#), [21357](#), [21369](#), [21393](#), [21400](#)
 - \l__box_right_new_dim . . . [21166](#),
[21212](#), [21246](#), [21257](#), [21268](#), [21279](#),
[21308](#), [21399](#), [21441](#), [21443](#), [21449](#)
 - __box_rotate:N [21171](#)
 - __box_rotate_quadrant_four:
. [21171](#), [21270](#)
 - __box_rotate_quadrant_one:
. [21171](#), [21237](#)
 - __box_rotate_quadrant_three:
. [21171](#), [21259](#)
 - __box_rotate_quadrant_two:
. [21171](#), [21248](#)
 - __box_rotate_x:nnN
[21171](#), [21215](#), [21243](#), [21245](#), [21254](#),
[21256](#), [21265](#), [21267](#), [21276](#), [21278](#)
 - __box_rotate_y:nnN
[21171](#), [21226](#), [21239](#), [21241](#), [21250](#),
[21252](#), [21261](#), [21263](#), [21272](#), [21274](#)
 - __box_scale_aux:N [21379](#), [21418](#)
 - \l__box_scale_x_fp [21281](#),
[21288](#), [21309](#), [21331](#), [21346](#), [21356](#),
[21358](#), [21368](#), [21383](#), [21400](#), [21413](#),
[21415](#), [21416](#), [21417](#), [21427](#), [21439](#)
 - \l__box_scale_y_fp
. [21281](#), [21290](#), [21311](#), [21313](#),
[21326](#), [21331](#), [21341](#), [21346](#), [21358](#),
[21370](#), [21384](#), [21396](#), [21398](#), [21414](#),
[21415](#), [21416](#), [21417](#), [21428](#), [21430](#)
 - __box_show:NNnn [20948](#), [20958](#), [20962](#)
 - \l__box_sin_fp
. . . [21160](#), [21176](#), [21187](#), [21222](#), [21232](#)
 - \l__box_top_dim [21162](#), [21183](#), [21239](#),
[21243](#), [21252](#), [21254](#), [21263](#), [21267](#),
[21272](#), [21278](#), [21293](#), [21301](#), [21313](#),
[21329](#), [21344](#), [21373](#), [21391](#), [21396](#)
 - \l__box_top_new_dim
[21166](#), [21209](#), [21240](#), [21251](#), [21262](#),
[21273](#), [21312](#), [21395](#), [21432](#), [21436](#)
 - \boxdir 942
 - \boxmaxdepth 307
 - bp 199
 - \brokenpenalty 308
- C**
- \c 24233
 - \catcode 4, 5, 6, 7, 10, 212, 213, 214, 215,
216, 217, 218, 219, 220, 225, 226,
227, 228, 229, 230, 231, 232, 233, 309
 - catcode commands:
 - \c_catcode_active_space_tl [252](#), [24423](#)
 - \c_catcode_active_tl
. [119](#), [469](#), [7333](#), [7393](#)
 - \c_catcode_letter_token
. [119](#), [469](#), [7315](#), [7383](#), [17545](#)
 - \c_catcode_other_space_tl . . [115](#),
[531](#), [7313](#), [9491](#), [9523](#), [9594](#), [9682](#), [9747](#)
 - \c_catcode_other_token
. [119](#), [469](#), [7315](#), [7388](#), [17543](#)
 - \catcodetable 869
 - cc 199
 - ceil 195
 - \char 310, 7498
 - char commands:
 - \l_char_active_seq
. [118](#), [145](#), [153](#), [7145](#), [8988](#)
 - \char_generate:nn
. [115](#), [128](#), [866](#), [7171](#), [7313](#),
[8896](#), [18067](#), [19021](#), [23570](#), [24056](#),
[24057](#), [24069](#), [24070](#), [24190](#), [24191](#)
 - \char_gset_active_eq:NN . . . [114](#), [7151](#)
 - \char_gset_active_eq:nN . . . [114](#), [7151](#)
 - \char_set_active_eq:NN [114](#), [7151](#), [8991](#)

- \char_set_active_eq:nN 114, 7151
- \char_set_catcode:nn
 - 117, 242, 243, 244, 245, 246, 247,
 - 248, 249, 250, 7051, 7058, 7060,
 - 7062, 7064, 7066, 7068, 7070, 7072,
 - 7074, 7076, 7078, 7080, 7082, 7084,
 - 7086, 7088, 7090, 7092, 7094, 7096,
 - 7098, 7100, 7102, 7104, 7106, 7108,
 - 7110, 7112, 7114, 7116, 7118, 7120
- \char_set_catcode_active:N
 - 116, 7057, 7152,
 - 7220, 7334, 8212, 17352, 20143, 24424
- \char_set_catcode_active:n
 - 116, 7089, 7276, 10400, 10401
- \char_set_catcode_alignment:N
 - 116, 7057, 7322, 20192
- \char_set_catcode_alignment:n
 - 116, 260, 7089, 7255
- \char_set_catcode_comment:N 116, 7057
- \char_set_catcode_comment:n 116, 7089
- \char_set_catcode_end_line:N
 - 116, 7057
- \char_set_catcode_end_line:n
 - 116, 7089
- \char_set_catcode_escape:N 116, 7057
- \char_set_catcode_escape:n 116, 7089
- \char_set_catcode_group_begin:N
 - 116, 7057, 17423, 20146
- \char_set_catcode_group_begin:n
 - 116, 7089, 7248
- \char_set_catcode_group_end:N
 - 116, 7057, 17426, 20160
- \char_set_catcode_group_end:n
 - 116, 7089, 7250
- \char_set_catcode_ignore:N 116, 7057
- \char_set_catcode_ignore:n
 - 116, 257, 258, 7089
- \char_set_catcode_invalid:N 116, 7057
- \char_set_catcode_invalid:n 116, 7089
- \char_set_catcode_letter:N
 - 116, 7057, 13608, 13609, 20169
- \char_set_catcode_letter:n
 - 116, 261, 263, 7089, 7272
- \char_set_catcode_math_subscript:N
 - 116, 7057, 7326, 20157
- \char_set_catcode_math_subscript:n
 - 116, 7089, 7267
- \char_set_catcode_math_superscript:N
 - 116, 7057, 20195
- \char_set_catcode_math_superscript:n
 - 116, 262, 7089, 7265
- \char_set_catcode_math_toggle:N
 - 116, 7057, 7320, 20172
- \char_set_catcode_math_toggle:n
 - 116, 7089, 7253
- \char_set_catcode_other:N
 - 116, 7057, 17578, 20175
- \char_set_catcode_other:n
 - 116, 259, 264, 7089, 7223, 7274
- \char_set_catcode_parameter:N
 - 116, 7057, 20178
- \char_set_catcode_parameter:n
 - 116, 7089, 7263
- \char_set_catcode_space:N . 116, 7057
- \char_set_catcode_space:n
 - 116, 265, 7089, 7270
- \char_set_lccode:nn
 - 117, 3078, 3095, 7121, 7158,
 - 7280, 7281, 8209, 8210, 8211, 24425
- \char_set_mathcode:nn 118, 7121
- \char_set_sfcode:nn 118, 7121
- \char_set_uccode:nn 117, 7121
- \char_show_value_catcode:n 117, 7051
- \char_show_value_lccode:n . 117, 7121
- \char_show_value_mathcode:n 118, 7121
- \char_show_value_sfcode:n . 118, 7121
- \char_show_value_uccode:n . 118, 7121
- \l_char_special_seq 118, 7145
- \char_value_catcode:n
 - 117, 242, 243, 244, 245, 246, 247,
 - 248, 249, 250, 3090, 3120, 7051, 23572
- \char_value_lccode:n 117, 7121
- \char_value_mathcode:n 118, 7121
- \char_value_sfcode:n 118, 7121
- \char_value_uccode:n 118, 7121
- char internal commands:
 - _char_generate:nn
 - 128, 976, 7171, 24019,
 - 24021, 24062, 24064, 24075, 24077
 - _char_generate_aux:nn 7171
 - _char_generate_aux:nnw 7171
 - _char_generate_aux:w . . . 7174, 7184
 - _char_generate_invalid_catcode: 7171
 - \c_char_max_int 7171
 - _char_tmp:n
 - 7278, 7290, 7293, 7295, 7298
 - _char_tmp:nN 7153, 7164, 7165
 - \l_char_tmp_tl 7171
- \chardef 222, 235, 311
- chk internal commands:
 - _chk_if_free_cs:N
 - 22, 467, 492, 2035, 2052,
 - 2100, 2858, 2865, 2871, 4586, 5212,
 - 5235, 5996, 6129, 7316, 7318, 7328,
 - 7780, 9842, 10148, 10278, 20846, 23038
 - _chk_if_free_msg:nn . . . 8108, 8120

- choice commands:
 - .choice: [172](#), [10855](#)
- choices commands:
 - .choices:nn [172](#), [10857](#)
- \cite [24281](#)
- \cleaders [312](#)
- \clearmarks [870](#)
- clist commands:
 - \clist_clear:N [105](#),
[105](#), [6511](#), [6528](#), [6724](#), [10978](#), [11003](#)
 - \clist_clear_new:N [105](#), [6515](#)
 - \clist_concat:NNN [106](#), [6555](#), [6608](#), [6621](#)
 - \clist_const:Nn [105](#), [6508](#)
 - \clist_count:N
... [110](#), [112](#), [6904](#), [6933](#), [6965](#), [22602](#)
 - \clist_count:n [110](#), [6904](#), [6996](#), [22593](#)
 - \clist_gclear:N [105](#), [6511](#), [6530](#)
 - \clist_gclear_new:N [105](#), [6515](#)
 - \clist_gconcat:NNN
... [106](#), [6555](#), [6610](#), [6623](#)
 - \clist_get:NN [111](#), [6633](#)
 - \clist_get:NNTF [111](#), [6670](#), [6679](#), [6680](#)
 - \clist_gpop:NN [111](#), [6644](#)
 - \clist_gpop:NNTF [112](#), [6670](#), [6698](#), [6699](#)
 - \clist_gpush:Nn [112](#), [6701](#)
 - \clist_gput_left:Nn
... [106](#), [6607](#), [6709](#), [6710](#),
[6711](#), [6712](#), [6713](#), [6714](#), [6715](#), [6716](#)
 - \clist_gput_right:Nn [107](#), [6620](#)
 - \clist_gremove_all:Nn [107](#), [6734](#)
 - \clist_gremove_duplicates:N [107](#), [6718](#)
 - \clist_greverse:N [107](#), [6765](#)
 - .clist_gset:N [172](#), [10867](#)
 - \clist_gset:Nn [106](#), [445](#), [6601](#)
 - \clist_gset_eq:NN ... [106](#), [6519](#), [6721](#)
 - \clist_gset_from_seq:NN ... [106](#), [6527](#)
 - \clist_gsort:Nn [108](#), [6783](#), [16975](#)
 - \clist_if_empty:NNTF
... [108](#), [6564](#), [6751](#), [6783](#),
[6828](#), [6858](#), [6878](#), [10743](#), [16983](#), [22601](#)
 - \clist_if_empty:nTF [108](#), [6787](#)
 - \clist_if_empty_p:N [108](#), [6783](#)
 - \clist_if_empty_p:n [108](#), [6787](#)
 - \clist_if_exist:NNTF
... [106](#), [6570](#), [6931](#), [9079](#), [9157](#)
 - \clist_if_exist_p:N [106](#), [6570](#)
 - \clist_if_in:NnTF
[108](#), [6727](#), [6801](#), [6817](#), [6818](#), [6819](#), [6820](#)
 - \clist_if_in:nnTF
... [108](#), [6801](#), [6823](#), [6824](#), [11650](#)
 - \clist_item:Nn
... [112](#), [459](#), [931](#), [6962](#), [22602](#)
 - \clist_item:nn . [112](#), [931](#), [6993](#), [22597](#)
 - \clist_log:N [113](#), [7023](#)
 - \clist_log:n [113](#), [7037](#)
 - \clist_map_break: [109](#), [6832](#), [6837](#),
[6846](#), [6850](#), [6866](#), [6884](#), [6900](#), [11176](#)
 - \clist_map_break:n
... [110](#), [6900](#), [11119](#), [16986](#)
 - \clist_map_function:NN [91](#),
[105](#), [109](#), [4613](#), [4623](#), [6826](#), [6909](#), [7033](#)
 - \clist_map_function:Nn [455](#)
 - \clist_map_function:nN
... [109](#), [456](#), [4618](#), [4628](#),
[6842](#), [7042](#), [11217](#), [23140](#), [24985](#), [25564](#)
 - \clist_map_function:nn [25950](#)
 - \clist_map_inline:Nn [109](#), [109](#), [454](#),
[766](#), [6725](#), [6856](#), [11114](#), [11167](#), [16986](#)
 - \clist_map_inline:nn
... [109](#), [1463](#), [1471](#), [6856](#),
[10705](#), [10774](#), [22344](#), [24479](#), [24488](#)
 - \clist_map_variable:NNn ... [109](#), [6876](#)
 - \clist_map_variable:nNn ... [109](#), [6876](#)
 - \clist_new:N .. [105](#), [105](#), [445](#), [6506](#),
[6717](#), [7044](#), [7045](#), [7046](#), [7047](#), [10528](#)
 - \clist_pop:NN [111](#), [6644](#)
 - \clist_pop:NNTF [112](#), [6670](#), [6695](#), [6696](#)
 - \clist_push:Nn [112](#), [6701](#)
 - \clist_put_left:Nn
... [106](#), [6607](#), [6701](#), [6702](#),
[6703](#), [6704](#), [6705](#), [6706](#), [6707](#), [6708](#)
 - \clist_put_right:Nn
... [107](#), [6620](#), [6728](#), [11204](#)
 - \clist_rand_item:N [240](#), [22592](#)
 - \clist_rand_item:n .. [240](#), [246](#), [22592](#)
 - \clist_remove_all:Nn [107](#), [6734](#)
 - \clist_remove_duplicates:N [107](#), [6718](#)
 - \clist_reverse:N [107](#), [6765](#)
 - \clist_reverse:n
... [107](#), [452](#), [6766](#), [6768](#), [6771](#)
 - .clist_set:N [172](#), [10867](#)
 - \clist_set:Nn
... [106](#), [445](#), [6601](#), [6608](#), [6610](#),
[6621](#), [6623](#), [6807](#), [6872](#), [6889](#), [10742](#)
 - \clist_set_eq:NN [106](#), [6519](#), [6719](#), [11099](#)
 - \clist_set_from_seq:NN ... [106](#), [6527](#)
 - \clist_show:N [112](#), [113](#), [7023](#)
 - \clist_show:n [112](#), [113](#), [7037](#)
 - \clist_sort:Nn [108](#), [6783](#), [16975](#)
 - \clist_use:Nn [111](#), [6929](#)
 - \clist_use:Nnnn [110](#), [400](#), [6929](#)
 - \clist_wrap_item:n [766](#), [767](#)
 - \c_empty_clist
... [113](#), [6503](#), [6635](#), [6650](#), [6672](#), [6688](#)
 - \l_foo_clist [202](#)
 - \g_tmpa_clist [113](#), [7044](#)
 - \l_tmpa_clist [113](#), [7044](#)
 - \g_tmpb_clist [113](#), [7044](#)

- \l_tmpb_clist [113](#), [7044](#)
- clist internal commands:
 - __clist_concat:NNNN [6555](#)
 - __clist_count:n [6904](#)
 - __clist_count:w [6904](#)
 - __clist_get:wN [6633](#), [6675](#)
 - __clist_if_empty_n:w [6787](#)
 - __clist_if_empty_n:wNw [6787](#)
 - __clist_if_in_return:nn [6801](#)
 - \l_clist_internal_clist
 - ... [6504](#), [6613](#), [6614](#), [6626](#), [6627](#),
[6807](#), [6808](#), [6872](#), [6873](#), [6889](#), [6890](#)
 - \l__clist_internal_remove_clist .
 - [6717](#), [6724](#), [6727](#), [6728](#), [6730](#)
 - __clist_item:nnnN [6962](#), [6995](#)
 - __clist_item_n:nw [6993](#)
 - __clist_item_n_end:n [6993](#)
 - __clist_item_N_loop:nw [6962](#)
 - __clist_item_n_loop:nw [6993](#)
 - __clist_item_n_strip:w [6993](#)
 - __clist_map_function:Nw
 - [454](#), [6826](#), [6863](#)
 - __clist_map_function_n:Nn [455](#), [6842](#)
 - __clist_map_unbrace:Nw ... [455](#), [6842](#)
 - __clist_map_variable:Nnw [6876](#)
 - __clist_pop:NNN [6644](#)
 - __clist_pop:wN [6644](#)
 - __clist_pop:wwNNN .. [449](#), [6644](#), [6691](#)
 - __clist_pop_TF:NNN [6670](#)
 - __clist_put_left:NNNn [6607](#)
 - __clist_put_right:NNNn [6620](#)
 - __clist_rand_item:nn [22592](#)
 - __clist_remove_all: [6734](#)
 - __clist_remove_all:NNn [6734](#)
 - __clist_remove_all:w [451](#), [6734](#)
 - __clist_remove_duplicates:NN . [6718](#)
 - __clist_reverse:wwNww [452](#), [6771](#)
 - __clist_reverse_end:ww ... [452](#), [6771](#)
 - __clist_set_from_seq:NNNN ... [6527](#)
 - __clist_set_from_seq:w [6527](#)
 - __clist_show:NN [7023](#)
 - __clist_show:Nn [7037](#)
 - __clist_tmp:w
 - ... [451](#), [6505](#), [6740](#), [6761](#), [6812](#), [6814](#)
 - __clist_trim_spaces:n
 - [6509](#), [6580](#), [6602](#), [6604](#)
 - __clist_trim_spaces:nn ... [447](#), [6580](#)
 - __clist_trim_spaces_generic:nn .
 - [447](#), [6574](#)
 - __clist_trim_spaces_generic:nw .
 - [447](#),
[454](#), [6574](#), [6582](#), [6592](#), [6597](#), [6844](#), [6852](#)
 - __clist_use:nwn [6929](#)
 - __clist_use:nwwwnwn [457](#), [6929](#)
- __clist_use:wnn [6929](#)
- __clist_wrap_item:n ... [6527](#), [16989](#)
- \closein [313](#)
- \closeout [314](#)
- \clubpenalties [612](#)
- \clubpenalty [315](#)
- cm [199](#)
- code commands:
 - .code:n [172](#), [10865](#)
- coffin commands:
 - \coffin_attach:NnnNnnnn
 - [230](#), [922](#), [21918](#)
 - \coffin_attach_mark:NnnNnnnn ...
 - [21918](#), [22106](#), [22127](#), [22143](#)
 - \coffin_clear:N [229](#), [21531](#)
 - \coffin_display_handles:Nn [231](#), [22149](#)
 - \coffin_dp:N
 - [231](#), [21665](#), [22273](#), [22762](#), [22788](#)
 - \coffin_ht:N
 - [231](#), [21665](#), [22272](#), [22762](#), [22788](#)
 - \coffin_if_exist:NTF
 - [229](#), [21508](#), [21519](#), [21520](#), [21524](#)
 - \coffin_if_exist_p:N [229](#), [21508](#)
 - \coffin_join:NnnNnnnn ... [231](#), [21881](#)
 - \coffin_log_structure:N .. [232](#), [22259](#)
 - \coffin_mark_handle:Nnnn . [232](#), [22094](#)
 - \coffin_new:N [229](#),
[907](#), [21540](#), [21657](#), [21661](#), [21662](#),
[21663](#), [21664](#), [22042](#), [22043](#), [22044](#)
 - \coffin_resize:Nnn [241](#), [22755](#)
 - \coffin_rotate:Nn [241](#), [22614](#)
 - \coffin_scale:Nnn [241](#), [22782](#)
 - \coffin_set_eq:NN
 - [229](#), [21648](#), [21915](#), [21934](#), [21963](#), [22170](#)
 - \coffin_set_horizontal_pole:Nnn .
 - [230](#), [21702](#)
 - \coffin_set_vertical_pole:Nnn ...
 - [230](#), [21702](#)
 - \coffin_show_structure:N
 - [232](#), [232](#), [22259](#)
 - \coffin_typeset:Nnnnn ... [231](#), [22034](#)
 - \coffin_wd:N
 - [231](#), [21665](#), [22274](#), [22758](#), [22792](#)
 - \c_empty_coffin ... [232](#), [21657](#), [22037](#)
 - \l_tmpa_coffin [232](#), [21663](#)
 - \l_tmpb_coffin [232](#), [21663](#)
- coffin internal commands:
 - __coffin_align:NnnNnnnnN
 - .. [21883](#), [21920](#), [21938](#), [21946](#), [22037](#)
 - \l__coffin_aligned_coffin
 - [21657](#), [21884](#),
[21885](#), [21889](#), [21895](#), [21897](#), [21898](#),
[21914](#), [21915](#), [21921](#), [21922](#), [21923](#),
[21924](#), [21925](#), [21927](#), [21929](#), [21933](#),

- 21934, 21939, 21940, 21941, 21942,
- 21943, 21977, 21992, 22038, 22039,
- 22244, 22251, 22253, 22255, 22257
- \l__coffin_aligned_internal_-
- coffin 21657, 21956, 21963
- \l__coffin_bottom_corner_dim ...
- 22610, 22633, 22637,
- 22707, 22718, 22719, 22739, 22747
- \l__coffin_bounding_prop 22608, 22623, 22650,
- 22652, 22655, 22657, 22663, 22726
- \l__coffin_bounding_shift_dim ...
- .. 22609, 22632, 22725, 22731, 22732
- __coffin_calculate_intersection:Nnn
- 21774, 21948, 21951, 22237
- __coffin_calculate_intersection:nnnnnnnn
- 21774, 22183
- __coffin_calculate_intersection_-
- aux:nnnnN 21774
- \c__coffin_corners_prop 21478, 21547, 21684
- \l__coffin_cos_fp 932, 934, 22606, 22617, 22690, 22699
- __coffin_display_attach:Nnnnn 22149
- \l__coffin_display_coffin 22042, 22170, 22176, 22246,
- 22247, 22252, 22254, 22256, 22257
- \l__coffin_display_coord_coffin .
- 22042, 22108,
- 22128, 22144, 22191, 22211, 22230
- \l__coffin_display_font_tl 22087, 22116, 22199
- __coffin_display_handles_-
- aux:nnnn 22149
- __coffin_display_handles_-
- aux:nnnnnn 22149
- \l__coffin_display_handles_prop .
- .. 22045, 22119, 22123, 22202, 22206
- \l__coffin_display_offset_dim ...
- .. 22082, 22145, 22146, 22231, 22232
- \l__coffin_display_pole_coffin ..
- .. 22042, 22096, 22107, 22151, 22189
- \l__coffin_display_poles_prop ...
- 22086, 22161,
- 22166, 22169, 22171, 22173, 22180
- \l__coffin_display_x_dim 22084, 22186, 22241
- \l__coffin_display_y_dim 22084, 22187, 22243
- \l__coffin_error_bool 21499, 21778, 21782,
- 21796, 21811, 21842, 22182, 22184
- __coffin_find_bounding_shift: ..
- 22626, 22723
- __coffin_find_bounding_shift_-
- aux:nn 22723
- __coffin_find_corner_maxima:N ..
- 22625, 22703
- __coffin_find_corner_maxima_-
- aux:nn 22703
- __coffin_get_pole:NnN 21671, 21776, 21777, 22001, 22002,
- 22005, 22006, 22163, 22164, 22167
- __coffin_gset_eq_structure:NN 21688
- __coffin_if_exist:NTF 21522, 21533, 21555, 21570, 21601,
- 21617, 21650, 21704, 21715, 22267
- \l__coffin_internal_box 21475, 21584,
- 21590, 21595, 21631, 21637, 21642,
- 22628, 22636, 22638, 22639, 22641
- \l__coffin_internal_dim 21475, 21890, 21892, 21893,
- 22654, 22656, 22658, 22787, 22790
- \l__coffin_internal_tl ... 21475,
- 21975, 21976, 21978, 22120, 22121,
- 22124, 22125, 22133, 22138, 22203,
- 22204, 22207, 22208, 22217, 22222
- \l__coffin_left_corner_dim 22610, 22632, 22640,
- 22708, 22714, 22715, 22738, 22746
- __coffin_mark_handle_aux:nnnnNnn
- 22094
- __coffin_offset_corner:Nnnnn . 21984
- __coffin_offset_corners:Nnn ...
- .. 21903, 21904, 21910, 21911, 21984
- __coffin_offset_pole:Nnnnnnn . 21965
- __coffin_offset_poles:Nnn 21901, 21902,
- 21907, 21908, 21930, 21931, 21965
- \l__coffin_offset_x_dim 21500, 21887, 21888, 21891,
- 21899, 21901, 21903, 21909, 21912,
- 21932, 21952, 21960, 22240, 22248
- \l__coffin_offset_y_dim 21500, 21902, 21904, 21909, 21912,
- 21932, 21954, 21961, 22242, 22249
- \l__coffin_pole_a_tl 21502, 21776, 21781, 22001, 22004,
- 22005, 22008, 22163, 22165, 22168
- \l__coffin_pole_b_tl ... 21502,
- 21777, 21781, 22002, 22004, 22006,
- 22008, 22164, 22165, 22167, 22168
- \c__coffin_poles_prop 21485, 21549, 21686
- __coffin_reset_structure:N ...
- 21536, 21562, 21581,
- 21607, 21628, 21681, 21895, 21925

- _coffin_resize_common:Nnn 22765, 22768, 22793
- \l_coffin_right_corner_dim 22610, 22640, 22706, 22716, 22717
- _coffin_rotate_bounding:nnn 22624, 22660
- _coffin_rotate_corner:Nnnn 22619, 22660
- _coffin_rotate_pole:Nnnnnn 22621, 22672
- _coffin_rotate_vector:nnNN 22662, 22668, 22674, 22675, 22684
- _coffin_scale_corner:Nnnn 22771, 22804
- _coffin_scale_pole:Nnnnnn 22773, 22804
- _coffin_scale_vector:nnNN 22797, 22806, 22812
- \l_coffin_scale_x_fp 22751, 22757, 22774, 22784, 22786, 22792, 22800
- \l_coffin_scale_y_fp . . . 22751, 22759, 22785, 22786, 22790, 22802
- \l_coffin_scaled_total_height_dim 22753, 22789, 22794
- \l_coffin_scaled_width_dim 22753, 22791, 22794
- _coffin_set_bounding:N 22622, 22648
- _coffin_set_eq_structure:NN 21653, 21688
- _coffin_set_pole:Nnn 21585, 21632, 21702, 21977, 22014, 22018, 22026, 22030, 22677, 22813
- _coffin_shift_corner:Nnnn 22643, 22734
- _coffin_shift_pole:Nnnnnn 22645, 22734
- _coffin_show_structure:NN . . 22259
- \l_coffin_sin_fp 932, 934, 22606, 22616, 22691, 22698
- \l_coffin_slope_x_fp 21497, 21836, 21841, 21849, 21855
- \l_coffin_slope_y_fp 21497, 21838, 21841, 21850, 21855
- \l_coffin_top_corner_dim 22610, 22637, 22705, 22720, 22721
- _coffin_update_B:nnnnnnnnN . 21999
- _coffin_update_corners:N 21564, 21583, 21609, 21630, 21729
- _coffin_update_poles:N 21563, 21582, 21608, 21629, 21740, 21898, 21929
- _coffin_update_T:nnnnnnnnN . 21999
- _coffin_update_vertical_poles:NNN 21914, 21933, 21999
- \l_coffin_x_dim 21504, 21785, 21794, 21814, 21817, 21824, 21833, 21844, 21859, 21949, 21953, 21972, 21980, 22186, 22238, 22662, 22664, 22668, 22670, 22674, 22679, 22806, 22808, 22812, 22815
- \l_coffin_x_prime_dim 21504, 21949, 21953, 22238, 22241, 22676, 22680
- _coffin_x_shift_corner:Nnnn 22777, 22819
- _coffin_x_shift_pole:Nnnnnn 22779, 22819
- \l_coffin_y_dim 21504, 21786, 21799, 21802, 21809, 21826, 21831, 21860, 21950, 21955, 21973, 21980, 22187, 22239, 22662, 22664, 22668, 22670, 22674, 22679, 22806, 22808, 22812, 22815
- \l_coffin_y_prime_dim 21504, 21950, 21955, 22239, 22243, 22676, 22681
- \color 22102, 22114, 22157, 22197
- color commands:
 - \color_ensure_current: 233, 905, 21559, 21603, 22315
 - \color_group_begin: . . . 233, 233, 22309
 - \color_group_end: . . . 233, 233, 22309
- color internal commands:
 - \l_color_current_tl 234, 22318, 22320, 22323
- \columnwidth 21577, 21623
- \copy 316
- \copyfont 955
- cos 196
- cosd 196
- cot 196
- cotd 196
- \count 164, 166, 167, 168, 172, 173, 175, 176, 179, 181, 182, 183, 184, 188, 189, 191, 192, 317, 7506
- \countdef 318
- \cr 319
- \crampeddisplaystyle 871
- \crampedscriptscriptstyle 872
- \crampedscriptstyle 873
- \crampedtextstyle 874
- \crr 320
- \cs 13487
- cs commands:
 - \cs:w . . . 16, 17, 864, 865, 1345, 1366, 1368, 1417, 1960, 1988, 2181, 2241, 2351, 2390, 2399, 2401, 2405, 2406, 2407, 2447, 2453, 2459, 2465, 2485,

2487, 2492, 2499, 2500, 2584, 2588,
 2611, 2850, 5213, 5329, 6052, 6120,
 6447, 6449, 9843, 10099, 10149,
 10248, 10279, 11154, 11173, 11183,
 11197, 11454, 11500, 12199, 12315,
 12503, 12535, 12908, 12937, 14945,
 15212, 15745, 20082, 20084, 20847
 \cs_end: 16, 337, 1345, 1366,
 1368, 1372, 1417, 1954, 1960, 1982,
 1988, 2110, 2181, 2241, 2351, 2390,
 2399, 2401, 2405, 2406, 2407, 2447,
 2453, 2459, 2465, 2485, 2487, 2492,
 2499, 2500, 2584, 2588, 2611, 2850,
 5213, 5329, 6052, 6059, 6100, 6110,
 6120, 6444, 6450, 6452, 6454, 6456,
 6458, 6460, 6462, 6464, 6466, 6468,
 6470, 9843, 10099, 10149, 10248,
 10279, 10827, 11154, 11174, 11184,
 11197, 11454, 11508, 12199, 12318,
 12507, 12539, 12908, 12940, 14945,
 15212, 15904, 19967, 20097, 20847
 \cs_generate_from_arg_count:NNnn
 14, 2161, 2199
 \cs_generate_variant:Nn 10,
 25, 27, 28, 332, 2633, 2861, 2874,
 2875, 2880, 2881, 2886, 2887, 2905,
 2906, 2923, 2924, 2956, 2957, 2958,
 2959, 2960, 2961, 2986, 2987, 2988,
 2989, 2990, 2991, 2992, 2993, 3018,
 3019, 3020, 3021, 3022, 3023, 3024,
 3025, 3067, 3068, 3069, 3070, 3138,
 3139, 3140, 3141, 3203, 3204, 3209,
 3210, 3213, 3214, 3215, 3216, 3217,
 3218, 3219, 3220, 3229, 3230, 3231,
 3232, 3242, 3243, 3244, 3245, 3265,
 3266, 3267, 3268, 3287, 3288, 3289,
 3298, 3299, 3300, 3360, 3361, 3362,
 3363, 3380, 3393, 3409, 3414, 3416,
 3425, 3437, 3438, 3457, 3462, 3463,
 3561, 3572, 3573, 3595, 3605, 3622,
 3623, 3624, 3625, 3742, 3744, 3746,
 3786, 3801, 3802, 3805, 3806, 3814,
 3836, 3837, 3838, 3839, 3872, 3873,
 3878, 3879, 3921, 3922, 3923, 3924,
 3925, 3926, 3927, 3928, 3939, 3940,
 3941, 3942, 3949, 3950, 3951, 3980,
 3981, 3982, 3983, 4038, 4055, 4081,
 4132, 4191, 4270, 4289, 4327, 4342,
 4359, 4360, 4361, 4374, 4438, 4589,
 4592, 4595, 4598, 4601, 4630, 4631,
 4632, 4633, 4634, 4635, 4671, 4672,
 4677, 4678, 4700, 4701, 4702, 4703,
 4708, 4709, 4710, 4711, 4728, 4729,
 4754, 4755, 4772, 4773, 4782, 4783,
 4784, 4785, 4805, 4806, 4807, 4808,
 4809, 4810, 4839, 4852, 4853, 4868,
 4894, 4895, 4900, 4901, 4902, 4903,
 4904, 4905, 4914, 4915, 4916, 4917,
 4918, 4919, 4920, 4921, 4922, 4923,
 4924, 4925, 4949, 4969, 4998, 5009,
 5010, 5020, 5043, 5057, 5091, 5093,
 5216, 5241, 5259, 5260, 5265, 5266,
 5269, 5270, 5273, 5274, 5299, 5300,
 5301, 5302, 5315, 5316, 5317, 5318,
 5325, 5326, 5328, 5935, 5939, 6168,
 6169, 6199, 6200, 6201, 6202, 6215,
 6216, 6217, 6218, 6244, 6257, 6258,
 6259, 6260, 6263, 6264, 6271, 6272,
 6281, 6282, 6283, 6284, 6292, 6294,
 6404, 6405, 6410, 6411, 6510, 6551,
 6552, 6553, 6554, 6568, 6569, 6605,
 6606, 6616, 6617, 6618, 6619, 6629,
 6630, 6631, 6632, 6643, 6668, 6669,
 6679, 6680, 6681, 6695, 6696, 6697,
 6698, 6699, 6700, 6732, 6733, 6763,
 6764, 6769, 6770, 6817, 6818, 6819,
 6820, 6821, 6822, 6823, 6824, 6825,
 6841, 6875, 6899, 6912, 6952, 6961,
 6985, 6992, 7024, 7026, 7167, 7168,
 7169, 7170, 7783, 7786, 7789, 7792,
 7795, 7810, 7813, 7816, 7878, 7879,
 7880, 7881, 7888, 7889, 7908, 7909,
 7910, 7911, 7924, 7945, 7946, 7947,
 7948, 7949, 7950, 7964, 7966, 7968,
 7970, 7987, 7988, 7998, 7999, 8000,
 8001, 8024, 8025, 8026, 8027, 8028,
 8029, 8030, 8031, 8041, 8042, 8043,
 8044, 8045, 8046, 8061, 8062, 8077,
 8083, 8085, 8562, 9044, 9087, 9203,
 9206, 9217, 9218, 9219, 9240, 9258,
 9373, 9395, 9402, 9414, 9429, 9432,
 9450, 9846, 9853, 9859, 9860, 9865,
 9866, 9885, 9886, 9890, 9891, 9895,
 9896, 9903, 9904, 9911, 9912, 10098,
 10132, 10152, 10159, 10164, 10165,
 10170, 10171, 10190, 10191, 10193,
 10194, 10196, 10197, 10204, 10205,
 10212, 10213, 10247, 10259, 10260,
 10262, 10282, 10289, 10296, 10297,
 10302, 10303, 10328, 10329, 10332,
 10333, 10336, 10337, 10344, 10345,
 10352, 10353, 10364, 10366, 10549,
 10650, 10666, 10725, 10838, 10971,
 10972, 10975, 10983, 10991, 11000,
 11008, 11016, 11030, 11048, 11081,
 11220, 11767, 11770, 13279, 13483,
 13528, 16374, 16415, 16480, 16516,
 16520, 16568, 16770, 16777, 16778,

- 16779, 16782, 16783, 16786, 16787,
16792, 16793, 16800, 16801, 16802,
16803, 16805, 16807, 16953, 16960,
16967, 16974, 16979, 16980, 17718,
18408, 20850, 20855, 20856, 20861,
20862, 20869, 20870, 20877, 20878,
20886, 20887, 20888, 20895, 20896,
20897, 20900, 20901, 20917, 20918,
20919, 20920, 20921, 20922, 20923,
20924, 20927, 20928, 20929, 20930,
20937, 20938, 20946, 20949, 20952,
20961, 20979, 20988, 20989, 21002,
21003, 21018, 21019, 21040, 21041,
21055, 21056, 21083, 21084, 21097,
21098, 21111, 21112, 21127, 21128,
21150, 21151, 21154, 21155, 21298,
21335, 21350, 21362, 21378, 21388,
21405, 21408, 21518, 21519, 21520,
21521, 21539, 21552, 21567, 21598,
21614, 21647, 21656, 21726, 21727,
21728, 21917, 21945, 22041, 22148,
22234, 22261, 22264, 22497, 22543,
22590, 22604, 22647, 22767, 22796,
23002, 23003, 23004, 23005, 23041,
23052, 23067, 23086, 23109, 23110,
23136, 23142, 23229, 23248, 23304,
23305, 23331, 23332, 23348, 23383,
24298, 24300, 24303, 24306, 24403,
24690, 24751, 24846, 25387, 25444,
25460, 25493, 25798, 25829, 26013
\cs_gset:Nn 14, 2176, 2236
\cs_gset:Npn
. . . . 10, 12, 23, 1401, 2058, 2072,
2074, 4973, 8136, 8138, 8176, 12221
\cs_gset:Npx 12,
1401, 2059, 2072, 2075, 4978, 19975
\cs_gset:eq:NN 15,
2090, 2107, 2115, 2859, 2899, 2903,
4587, 4983, 4988, 5979, 6253, 6256,
7165, 7781, 8065, 8073, 9255, 9411,
22353, 22354, 22355, 22356, 22361,
22362, 22363, 22364, 22373, 22374,
22375, 22376, 22380, 22381, 22382,
22383, 22389, 22390, 22391, 22392
\cs_gset_nopar:Nn 14, 2176, 2236
\cs_gset_nopar:Npn
12, 1401, 1591, 2056, 2064, 2068, 6130
\cs_gset_nopar:Npx
. 12, 1401, 2057, 2064, 2069, 2866,
2872, 2949, 2952, 2955, 2976, 2979,
2982, 2985, 3008, 3011, 3014, 3017
\cs_gset_protected:Nn 14, 2176, 2236
\cs_gset_protected:Npn 12,
1401, 1685, 2062, 2084, 2086, 3384,
4042, 5557, 6861, 8068, 9315, 13533,
16882, 16890, 16903, 17360, 17621
\cs_gset_protected:Npx 12,
1401, 2063, 2084, 2087, 5564, 13540
\cs_gset_protected_nopar:Nn
. 14, 2176, 2236
\cs_gset_protected_nopar:Npn . . .
. 12, 1401, 2060, 2078, 2080
\cs_gset_protected_nopar:Npx . . .
. 12, 1401, 2061, 2078, 2081
\cs_if_eq:NNTF 20,
2268, 2275, 2276, 2279, 2280, 2283,
2284, 8369, 10794, 11994, 12004,
12030, 12032, 12034, 12226, 18997
\cs_if_eq_p:NN 20, 2268, 19013
\cs_if_exist 215
\cs_if_exist:N 20,
2925, 2926, 4679, 4681, 5275, 5277,
6304, 6306, 6570, 6572, 7989, 7991,
9867, 9869, 10172, 10174, 10304,
10306, 13341, 13342, 20879, 20881
\cs_if_exist:NNTF . 20, 24, 472, 500,
1520, 1529, 1940, 1997, 1999, 2001,
2003, 2005, 2007, 2009, 2011, 2288,
3885, 4393, 4401, 4447, 4450, 4463,
4555, 5243, 5244, 5246, 5247, 5968,
5969, 6094, 7225, 7226, 7228, 7473,
7490, 8105, 8941, 8963, 9021, 9191,
9195, 9274, 9335, 9361, 9365, 10563,
10673, 10719, 11097, 11139, 11151,
11164, 11170, 11181, 11195, 11233,
11241, 12219, 12366, 13328, 16608,
16619, 16880, 16898, 16901, 17358,
18752, 20072, 21510, 21512, 22351,
22359, 22367, 22387, 22483, 22850,
22875, 22923, 22979, 23158, 23168,
23515, 23556, 23563, 23589, 23609,
23616, 23759, 23981, 24005, 24741,
24766, 25125, 25132, 25138, 25144
\cs_if_exist_p:N 20, 22, 23, 1940, 22370
\cs_if_exist_use:N
. 16, 310, 1996, 11153, 19165
\cs_if_exist_use:NNTF 16,
1465, 1473, 1996, 1998, 2000, 2006,
2008, 10760, 11648, 12325, 12327,
18016, 18023, 18372, 18377, 18413,
18808, 18888, 20012, 22396, 23494,
23507, 23509, 23542, 23550, 24684
\cs_if_free:NNTF 20, 96,
500, 1968, 2039, 2800, 2814, 2846, 8434
\cs_if_free_p:N . . 20, 20, 22, 96, 1968
\cs_log:N 16, 319, 2313
\cs_meaning:N
. 15, 291, 1354, 1369, 1377, 2325

`\cs_new:Nn` 12, 97, [2176](#), [2236](#)
`\cs_new:Npn` 10, 11, 14, 23, 24, 96, 96,
300, [771](#), [2048](#), [2072](#), 2076, 2149,
2151, 2159, 2207, 2273, 2274, 2275,
2276, 2277, 2278, 2279, 2280, 2281,
2282, 2283, 2284, 2330, 2339, 2340,
2344, 2345, 2346, 2347, 2348, 2349,
2350, 2352, 2354, 2366, 2372, 2378,
2389, 2391, 2398, 2400, 2402, 2409,
2410, 2412, 2414, 2416, 2421, 2426,
2432, 2438, 2444, 2450, 2456, 2462,
2468, 2475, 2482, 2489, 2496, 2504,
2505, 2506, 2507, 2508, 2509, 2510,
2511, 2512, 2513, 2514, 2521, 2522,
2523, 2524, 2525, 2526, 2527, 2528,
2529, 2530, 2531, 2532, 2533, 2534,
2535, 2536, 2545, 2546, 2548, 2553,
2558, 2568, 2569, 2571, 2573, 2575,
2577, 2583, 2585, 2591, 2593, 2600,
2601, 2602, 2603, 2604, 2607, 2609,
2611, 2612, 2613, 2615, 2620, 2628,
2630, 2695, 2716, 2736, 2739, 2748,
2761, 2776, 2787, 2848, 3065, 3246,
3315, 3318, 3319, 3320, 3321, 3331,
3332, 3337, 3342, 3347, 3352, 3354,
3364, 3367, 3373, 3375, 3410, 3412,
3415, 3417, 3426, 3431, 3436, 3439,
3446, 3453, 3455, 3466, 3478, 3486,
3492, 3498, 3502, 3509, 3520, 3529,
3531, 3538, 3544, 3546, 3548, 3562,
3564, 3566, 3574, 3579, 3584, 3596,
3597, 3598, 3606, 3652, 3661, 3692,
3713, 3720, 3728, 3734, 3741, 3766,
3884, 3898, 3906, 3958, 3963, 3968,
3973, 3978, 3984, 3990, 3995, 4000,
4005, 4010, 4012, 4019, 4027, 4029,
4031, 4056, 4082, 4084, 4086, 4097,
4106, 4109, 4120, 4129, 4131, 4133,
4141, 4144, 4151, 4172, 4182, 4184,
4189, 4190, 4192, 4200, 4204, 4212,
4218, 4224, 4243, 4245, 4254, 4260,
4266, 4268, 4271, 4281, 4288, 4290,
4298, 4303, 4308, 4319, 4326, 4328,
4334, 4336, 4341, 4343, 4349, 4350,
4355, 4356, 4357, 4358, 4362, 4367,
4372, 4375, 4376, 4384, 4389, 4403,
4417, 4575, 4663, 4669, 4699, 4712,
4767, 4803, 4837, 4889, 4926, 4928,
4936, 4942, 4950, 4952, 4954, 4963,
5011, 5019, 5021, 5044, 5045, 5046,
5053, 5055, 5118, 5122, 5125, 5131,
5159, 5172, 5180, 5193, 5200, 5207,
5329, 5336, 5350, 5355, 5361, 5372,
5377, 5384, 5386, 5388, 5390, 5392,
5394, 5396, 5412, 5417, 5422, 5427,
5432, 5434, 5461, 5469, 5477, 5483,
5489, 5497, 5505, 5511, 5523, 5530,
5544, 5579, 5593, 5599, 5631, 5663,
5665, 5667, 5673, 5679, 5691, 5699,
5711, 5719, 5752, 5785, 5787, 5789,
5791, 5793, 5798, 5803, 5808, 5813,
5814, 5815, 5816, 5817, 5818, 5819,
5820, 5821, 5822, 5823, 5824, 5825,
5826, 5827, 5828, 5829, 5838, 5839,
5848, 5854, 5856, 5865, 5872, 5878,
5880, 5882, 5898, 5909, 5932, 6005,
6032, 6034, 6036, 6051, 6082, 6107,
6108, 6117, 6118, 6138, 6144, 6152,
6159, 6166, 6170, 6176, 6208, 6214,
6236, 6289, 6316, 6324, 6334, 6339,
6344, 6346, 6354, 6355, 6356, 6357,
6358, 6359, 6360, 6361, 6362, 6365,
6380, 6393, 6394, 6400, 6402, 6406,
6408, 6412, 6420, 6425, 6433, 6439,
6446, 6448, 6450, 6451, 6453, 6455,
6457, 6459, 6461, 6463, 6465, 6467,
6469, 6471, 6476, 6477, 6478, 6479,
6480, 6481, 6482, 6483, 6484, 6485,
6494, 6496, 6543, 6550, 6574, 6579,
6580, 6587, 6667, 6760, 6762, 6771,
6778, 6781, 6794, 6800, 6826, 6835,
6842, 6848, 6855, 6900, 6902, 6904,
6922, 6929, 6953, 6954, 6957, 6959,
6962, 6970, 6986, 6993, 7001, 7003,
7017, 7022, 7053, 7123, 7129, 7135,
7141, 7172, 7178, 7184, 7230, 7238,
7300, 7420, 7452, 7525, 7537, 7538,
7546, 7555, 7564, 7577, 7578, 7579,
7580, 7620, 7628, 7630, 7632, 7642,
7652, 7738, 7741, 7750, 7759, 7774,
7817, 7823, 7830, 7835, 7840, 7865,
7912, 7918, 8009, 8015, 8047, 8053,
8078, 8080, 8175, 8261, 8266, 8271,
8276, 8281, 8286, 8373, 8413, 8415,
8432, 8563, 8884, 8893, 8898, 8907,
8912, 8917, 8922, 9012, 9168, 9299,
9301, 9455, 9463, 9506, 9551, 9602,
9611, 9630, 9638, 9644, 9652, 9662,
9667, 9673, 9679, 9743, 9745, 9915,
9920, 9927, 9940, 9948, 9956, 9958,
9976, 9982, 9995, 9997, 9999, 10001,
10003, 10005, 10010, 10015, 10020,
10025, 10027, 10034, 10042, 10050,
10056, 10062, 10070, 10078, 10084,
10092, 10096, 10099, 10102, 10109,
10117, 10121, 10123, 10239, 10244,
10248, 10252, 10257, 10361, 10504,
10509, 10511, 10631, 11193, 11211,

11216, 11218, 11221, 11229, 11338,
11339, 11340, 11341, 11342, 11343,
11344, 11345, 11346, 11347, 11379,
11381, 11383, 11392, 11394, 11406,
11407, 11409, 11419, 11429, 11439,
11449, 11452, 11462, 11466, 11471,
11473, 11475, 11477, 11479, 11486,
11488, 11496, 11498, 11510, 11512,
11514, 11516, 11540, 11542, 11544,
11545, 11546, 11548, 11550, 11552,
11554, 11572, 11587, 11588, 11594,
11609, 11616, 11618, 11625, 11754,
11755, 11756, 11757, 11758, 11759,
11760, 11765, 11768, 11812, 11814,
11816, 11818, 11847, 11857, 11862,
11866, 11868, 11877, 11878, 11887,
11900, 11913, 11920, 11934, 11950,
11962, 11972, 11981, 11992, 12002,
12028, 12039, 12048, 12059, 12064,
12084, 12086, 12097, 12102, 12115,
12138, 12139, 12149, 12155, 12172,
12173, 12197, 12206, 12211, 12235,
12263, 12267, 12270, 12272, 12278,
12285, 12292, 12300, 12323, 12337,
12356, 12364, 12379, 12394, 12405,
12415, 12425, 12430, 12439, 12456,
12469, 12474, 12480, 12482, 12489,
12519, 12547, 12563, 12574, 12579,
12597, 12615, 12626, 12641, 12646,
12656, 12666, 12676, 12692, 12740,
12747, 12764, 12772, 12803, 12815,
12829, 12848, 12856, 12865, 12874,
12884, 12887, 12893, 12903, 12904,
12911, 12916, 12963, 12964, 12968,
12985, 13002, 13004, 13015, 13028,
13058, 13060, 13074, 13087, 13102,
13119, 13143, 13145, 13147, 13149,
13159, 13164, 13175, 13186, 13197,
13210, 13230, 13248, 13250, 13266,
13277, 13280, 13290, 13301, 13304,
13337, 13339, 13348, 13367, 13372,
13399, 13400, 13408, 13420, 13426,
13432, 13440, 13448, 13454, 13460,
13468, 13476, 13493, 13512, 13558,
13569, 13593, 13595, 13597, 13599,
13610, 13617, 13619, 13620, 13645,
13651, 13658, 13659, 13667, 13678,
13680, 13682, 13689, 13713, 13715,
13725, 13740, 13749, 13763, 13771,
13779, 13786, 13793, 13801, 13811,
13825, 13836, 13837, 13843, 13860,
13867, 13869, 13876, 13881, 13898,
13899, 13900, 13919, 13925, 13935,
13947, 13954, 13968, 13976, 14014,
14023, 14042, 14044, 14046, 14055,
14066, 14078, 14093, 14106, 14119,
14127, 14144, 14161, 14168, 14176,
14186, 14187, 14196, 14197, 14206,
14216, 14230, 14240, 14251, 14259,
14261, 14272, 14278, 14313, 14334,
14336, 14338, 14340, 14347, 14356,
14361, 14368, 14375, 14395, 14400,
14417, 14427, 14429, 14444, 14445,
14450, 14458, 14459, 14482, 14495,
14502, 14510, 14511, 14512, 14513,
14514, 14515, 14523, 14529, 14531,
14533, 14555, 14560, 14570, 14580,
14590, 14603, 14614, 14619, 14626,
14635, 14637, 14646, 14655, 14669,
14671, 14673, 14686, 14696, 14701,
14710, 14718, 14725, 14731, 14740,
14742, 14754, 14759, 14767, 14772,
14782, 14788, 14794, 14801, 14808,
14810, 14815, 14817, 14822, 14823,
14837, 14847, 14859, 14864, 14871,
14881, 14883, 14894, 14908, 14922,
14942, 14955, 14957, 14962, 14975,
14980, 14988, 14993, 15003, 15015,
15044, 15045, 15046, 15048, 15050,
15052, 15066, 15072, 15081, 15100,
15106, 15116, 15135, 15143, 15176,
15182, 15191, 15193, 15207, 15209,
15217, 15219, 15235, 15251, 15267,
15283, 15299, 15315, 15320, 15345,
15368, 15397, 15413, 15423, 15434,
15455, 15470, 15475, 15480, 15482,
15496, 15498, 15513, 15521, 15531,
15541, 15575, 15577, 15579, 15581,
15583, 15598, 15613, 15628, 15643,
15658, 15673, 15681, 15695, 15697,
15703, 15715, 15723, 15730, 15906,
15914, 15925, 15926, 15928, 15929,
15940, 15947, 15949, 15955, 15966,
15976, 15983, 15990, 16005, 16044,
16057, 16088, 16093, 16098, 16112,
16132, 16134, 16151, 16166, 16178,
16185, 16190, 16192, 16201, 16214,
16217, 16238, 16251, 16266, 16284,
16299, 16309, 16318, 16331, 16347,
16364, 16369, 16370, 16371, 16372,
16375, 16380, 16403, 16411, 16413,
16416, 16421, 16444, 16469, 16478,
16479, 16481, 16486, 16496, 16504,
16512, 16514, 16517, 16519, 16521,
16526, 16532, 16539, 16553, 16558,
16560, 16570, 16572, 16574, 16576,
16604, 16606, 16612, 16621, 16626,
16632, 16638, 16655, 16660, 16670,

- 16680, 16682, 16695, 16708, 16722,
 16731, 16736, 16745, 16747, 16754,
 16994, 16996, 17098, 17111, 17116,
 17122, 17123, 17129, 17135, 17141,
 17147, 17153, 17154, 17156, 17163,
 17169, 17255, 17320, 17325, 17326,
 17334, 17340, 17514, 17519, 17526,
 17559, 17564, 17579, 17602, 17607,
 17648, 17654, 17672, 17677, 17692,
 17694, 17696, 17703, 17733, 17762,
 17767, 18014, 18020, 18031, 18037,
 18050, 18055, 18070, 18082, 18092,
 18101, 18121, 18223, 18241, 18249,
 18261, 18273, 18741, 18995, 19009,
 19049, 19087, 19237, 19388, 19761,
 19889, 19891, 19897, 19898, 19905,
 19915, 20038, 20394, 20402, 20794,
 22592, 22594, 22599, 22930, 22936,
 22955, 22960, 22965, 22973, 22985,
 22994, 22996, 22998, 23000, 23006,
 23043, 23051, 23053, 23059, 23068,
 23069, 23070, 23079, 23088, 23090,
 23096, 23102, 23131, 23144, 23167,
 23260, 23273, 23279, 23284, 23296,
 23297, 23298, 23349, 23350, 23351,
 23352, 23353, 23354, 23355, 23363,
 23370, 23381, 23384, 23390, 23394,
 23408, 23420, 23425, 23433, 23447,
 23452, 23463, 23474, 23480, 23485,
 23492, 23504, 23517, 23521, 23536,
 23538, 23546, 23554, 23565, 23580,
 23581, 23583, 23585, 23587, 23598,
 23607, 23633, 23644, 23653, 23667,
 23673, 23676, 23691, 23697, 23699,
 23705, 23719, 23723, 23729, 23739,
 23745, 23761, 23771, 23778, 23798,
 23808, 23821, 23829, 23835, 23855,
 23864, 23870, 23892, 23905, 23914,
 23920, 23936, 23942, 23947, 23977,
 23979, 24234, 24244, 24250, 24292,
 24297, 24299, 24301, 24302, 24304,
 24305, 24307, 24308, 24316, 24328,
 24337, 24346, 24348, 24350, 24358,
 24366, 24371, 24377, 24400, 24401,
 24402, 24404, 24470, 24471, 24475,
 24476, 24691, 24692, 24694, 24752,
 24754, 24756, 24758, 24760, 24788,
 24990, 25482, 25569, 25796, 25954
 \cs_new:Npx 11, 32, 33, 330, 331, 2048, 2072,
 2077, 2654, 2830, 6913, 6923, 9500,
 12141, 12249, 12784, 12946, 13684,
 15562, 15568, 15742, 16588, 17539,
 18038, 18040, 18042, 18044, 18046,
 18048, 23017, 23019, 23021, 23028
 \cs_new_eq:NN . . . 15, 97, 311, 313,
 467, 1848, 2090, 2329, 2338, 2360,
 2902, 2903, 3197, 3198, 3366, 3785,
 3799, 3800, 3803, 3804, 3867, 4018,
 4414, 4436, 4437, 4582, 4602, 4603,
 4604, 4605, 4606, 4607, 4608, 4609,
 5058, 5059, 5060, 5061, 5062, 5063,
 5064, 5065, 5066, 5067, 5068, 5069,
 5070, 5071, 5072, 5073, 5074, 5075,
 5076, 5077, 5078, 5079, 5080, 5081,
 5082, 5083, 5111, 5112, 5113, 5114,
 5115, 5248, 5249, 5252, 5327, 5440,
 5578, 5934, 5938, 5981, 6232, 6240,
 6241, 6243, 6261, 6262, 6503, 6506,
 6507, 6511, 6512, 6513, 6514, 6515,
 6516, 6517, 6518, 6519, 6520, 6521,
 6522, 6523, 6524, 6525, 6526, 6701,
 6702, 6703, 6704, 6705, 6706, 6707,
 6708, 6709, 6710, 6711, 6712, 6713,
 6714, 6715, 6716, 7321, 7323, 7324,
 7325, 7327, 7330, 7331, 7573, 7574,
 7575, 7768, 7769, 7796, 7797, 7798,
 7799, 7800, 7801, 7802, 7803, 9202,
 9271, 9372, 9456, 9836, 9837, 9838,
 10033, 10097, 10131, 10135, 10136,
 10246, 10249, 10254, 10261, 10265,
 10266, 10363, 10365, 10369, 10370,
 11458, 11859, 11933, 11961, 11969,
 11970, 11971, 11979, 11980, 12739,
 12824, 12825, 12826, 16567, 16569,
 16617, 16769, 16780, 16781, 17287,
 17313, 17314, 17736, 17855, 17856,
 17953, 17961, 17982, 18027, 18028,
 18029, 18030, 18214, 19662, 20205,
 20883, 20884, 20885, 20898, 20899,
 20910, 20911, 20912, 21025, 21053,
 21054, 21135, 21152, 21153, 21665,
 21666, 21667, 21668, 21669, 21670,
 22309, 22346, 22347, 22348, 22349,
 22398, 22399, 22400, 22401, 22402,
 22403, 22404, 22405, 22409, 22410,
 22411, 22412, 22413, 22414, 22415,
 22416, 23406, 23502, 23577, 23758,
 23827, 23828, 24839, 25217, 25285,
 25286, 25335, 25343, 25358, 25429,
 25492, 25783, 25784, 25795, 25797
 \cs_new_nopar:Nn 13, 2176, 2236
 \cs_new_nopar:Npn
 . 11, 311, 312, 2048, 2064, 2070, 2327
 \cs_new_nopar:Npx 11, 2048, 2064, 2071
 \cs_new_protected:Nn . 13, 2176, 2236
 \cs_new_protected:Npn
 11, 299, 1661, 2048, 2084,

2088, 2090, 2091, 2092, 2093, 2094,
2095, 2096, 2097, 2098, 2103, 2104,
2105, 2106, 2108, 2161, 2171, 2173,
2184, 2189, 2286, 2295, 2297, 2299,
2301, 2303, 2311, 2313, 2314, 2316,
2317, 2319, 2361, 2503, 2515, 2516,
2517, 2518, 2519, 2520, 2537, 2538,
2539, 2540, 2541, 2542, 2543, 2544,
2563, 2606, 2627, 2634, 2659, 2663,
2666, 2675, 2785, 2810, 2840, 2856,
2863, 2869, 2876, 2878, 2882, 2884,
2889, 2895, 2913, 2921, 2939, 2942,
2945, 2948, 2951, 2954, 2963, 2966,
2969, 2972, 2975, 2978, 2981, 2984,
2995, 2998, 3001, 3004, 3007, 3010,
3013, 3016, 3027, 3029, 3031, 3033,
3055, 3073, 3085, 3087, 3101, 3130,
3132, 3134, 3136, 3142, 3164, 3170,
3199, 3201, 3205, 3207, 3284, 3285,
3286, 3381, 3391, 3394, 3400, 3402,
3458, 3460, 3568, 3570, 3743, 3745,
3747, 3752, 3754, 3767, 3774, 3776,
3828, 3830, 3832, 3834, 3840, 3855,
3868, 3870, 3874, 3876, 4039, 4053,
4062, 4072, 4074, 4412, 4413, 4584,
4590, 4593, 4596, 4599, 4610, 4615,
4620, 4625, 4636, 4638, 4640, 4673,
4675, 4683, 4691, 4704, 4706, 4714,
4716, 4718, 4730, 4732, 4734, 4756,
4758, 4760, 4811, 4819, 4829, 4840,
4842, 4844, 4846, 4854, 4863, 4869,
4871, 4873, 4970, 4975, 4980, 4986,
4992, 4999, 5090, 5092, 5094, 5210,
5221, 5256, 5258, 5261, 5263, 5268,
5272, 5288, 5291, 5294, 5297, 5304,
5307, 5310, 5313, 5320, 5323, 5330,
5553, 5560, 5572, 5936, 5940, 5994,
6006, 6008, 6013, 6049, 6056, 6057,
6068, 6070, 6071, 6072, 6127, 6223,
6243, 6246, 6249, 6252, 6255, 6266,
6269, 6285, 6287, 6291, 6293, 6295,
6505, 6508, 6527, 6529, 6531, 6555,
6557, 6559, 6601, 6603, 6607, 6609,
6611, 6620, 6622, 6624, 6633, 6641,
6644, 6646, 6648, 6656, 6686, 6718,
6720, 6722, 6734, 6736, 6738, 6765,
6767, 6810, 6856, 6870, 6876, 6887,
6892, 7023, 7025, 7027, 7037, 7038,
7039, 7051, 7055, 7057, 7059, 7061,
7063, 7065, 7067, 7069, 7071, 7073,
7075, 7077, 7079, 7081, 7083, 7085,
7087, 7089, 7091, 7093, 7095, 7097,
7099, 7101, 7103, 7105, 7107, 7109,
7111, 7113, 7115, 7117, 7119, 7121,
7125, 7127, 7131, 7133, 7137, 7139,
7143, 7155, 7581, 7583, 7585, 7590,
7608, 7610, 7612, 7614, 7616, 7618,
7661, 7769, 7778, 7784, 7787, 7790,
7793, 7808, 7811, 7814, 7855, 7857,
7866, 7872, 7882, 7890, 7899, 7951,
7952, 7953, 7972, 7974, 7976, 8063,
8082, 8084, 8086, 8110, 8118, 8123,
8125, 8132, 8134, 8141, 8182, 8194,
8199, 8216, 8246, 8252, 8296, 8298,
8367, 8403, 8417, 8442, 8462, 8463,
8476, 8481, 8507, 8516, 8518, 8520,
8537, 8564, 8566, 8568, 8570, 8577,
8985, 8999, 9014, 9045, 9060, 9066,
9073, 9088, 9102, 9107, 9113, 9118,
9130, 9151, 9152, 9153, 9202, 9204,
9221, 9224, 9241, 9247, 9259, 9260,
9261, 9288, 9290, 9303, 9305, 9307,
9313, 9320, 9372, 9375, 9378, 9396,
9403, 9415, 9416, 9417, 9427, 9430,
9433, 9439, 9445, 9452, 9454, 9464,
9494, 9512, 9537, 9560, 9572, 9591,
9595, 9683, 9699, 9707, 9716, 9723,
9729, 9801, 9809, 9815, 9822, 9824,
9826, 9828, 9830, 9832, 9840, 9848,
9855, 9857, 9861, 9863, 9880, 9883,
9888, 9893, 9898, 9901, 9906, 9909,
10133, 10137, 10146, 10154, 10161,
10163, 10166, 10168, 10185, 10188,
10192, 10195, 10199, 10202, 10207,
10210, 10263, 10267, 10276, 10284,
10291, 10294, 10298, 10300, 10323,
10326, 10331, 10335, 10339, 10342,
10347, 10350, 10367, 10371, 10385,
10402, 10408, 10413, 10426, 10432,
10437, 10451, 10454, 10464, 10474,
10496, 10505, 10507, 10541, 10543,
10550, 10555, 10560, 10573, 10578,
10602, 10614, 10635, 10651, 10667,
10669, 10671, 10687, 10697, 10699,
10701, 10723, 10726, 10740, 10753,
10758, 10762, 10770, 10772, 10782,
10809, 10818, 10827, 10828, 10839,
10841, 10843, 10845, 10847, 10849,
10851, 10853, 10855, 10857, 10859,
10861, 10863, 10865, 10867, 10869,
10871, 10873, 10875, 10877, 10879,
10881, 10883, 10885, 10887, 10889,
10891, 10893, 10895, 10897, 10899,
10901, 10903, 10905, 10907, 10909,
10911, 10913, 10915, 10917, 10919,
10921, 10923, 10925, 10927, 10929,
10931, 10933, 10935, 10937, 10939,
10941, 10943, 10945, 10947, 10949,

10951, 10953, 10955, 10957, 10959,
10961, 10963, 10965, 10973, 10976,
10984, 10992, 10998, 11001, 11009,
11017, 11023, 11031, 11037, 11039,
11049, 11055, 11060, 11065, 11082,
11095, 11109, 11135, 11149, 11159,
11202, 11246, 11248, 11250, 11349,
11646, 11663, 11665, 11667, 11669,
11697, 11699, 11701, 11703, 11723,
11725, 11727, 11729, 11731, 11733,
11735, 11737, 11739, 13257, 13264,
13529, 13536, 13548, 16144, 16768,
16771, 16773, 16775, 16784, 16785,
16788, 16790, 16794, 16795, 16796,
16797, 16798, 16804, 16806, 16808,
16813, 16815, 16839, 16858, 16866,
16878, 16915, 16922, 16947, 16954,
16961, 16968, 16975, 16977, 16981,
17004, 17013, 17033, 17043, 17053,
17055, 17057, 17058, 17065, 17068,
17078, 17088, 17179, 17186, 17188,
17203, 17237, 17239, 17246, 17264,
17266, 17268, 17270, 17272, 17281,
17288, 17297, 17306, 17342, 17353,
17369, 17379, 17381, 17405, 17412,
17424, 17427, 17430, 17440, 17448,
17455, 17464, 17478, 17495, 17506,
17612, 17619, 17632, 17642, 17731,
17734, 17737, 17739, 17748, 17754,
17760, 17790, 17792, 17793, 17798,
17804, 17812, 17824, 17840, 17857,
17867, 17875, 17877, 17885, 17896,
17914, 17916, 17921, 17929, 17931,
17938, 17943, 17945, 17947, 17954,
17962, 17964, 17966, 17968, 17975,
17980, 17983, 17997, 18217, 18281,
18294, 18304, 18314, 18341, 18370,
18375, 18380, 18400, 18409, 18418,
18420, 18427, 18436, 18438, 18440,
18442, 18448, 18470, 18484, 18511,
18516, 18550, 18585, 18606, 18608,
18618, 18627, 18632, 18641, 18650,
18665, 18678, 18684, 18695, 18708,
18714, 18727, 18747, 18777, 18786,
18799, 18804, 18822, 18830, 18835,
18837, 18839, 18854, 18870, 18872,
18894, 18906, 18926, 18947, 18954,
18961, 18973, 18979, 19033, 19068,
19077, 19093, 19111, 19117, 19168,
19178, 19180, 19182, 19189, 19248,
19261, 19277, 19288, 19307, 19322,
19329, 19336, 19338, 19352, 19359,
19373, 19389, 19398, 19412, 19427,
19445, 19454, 19456, 19468, 19480,
19492, 19505, 19512, 19532, 19563,
19597, 19615, 19621, 19630, 19672,
19688, 19702, 19721, 19726, 19737,
19767, 19782, 19794, 19802, 19814,
19821, 19823, 19825, 19845, 19850,
19857, 19862, 19867, 19872, 19921,
19945, 19984, 19994, 20010, 20022,
20032, 20065, 20079, 20088, 20094,
20103, 20138, 20144, 20147, 20155,
20158, 20161, 20170, 20173, 20176,
20179, 20184, 20193, 20196, 20199,
20204, 20206, 20211, 20216, 20221,
20229, 20249, 20251, 20255, 20256,
20280, 20288, 20297, 20309, 20318,
20326, 20365, 20414, 20441, 20443,
20445, 20474, 20502, 20812, 20814,
20816, 20827, 20844, 20851, 20853,
20857, 20859, 20864, 20867, 20872,
20875, 20889, 20891, 20893, 20902,
20904, 20906, 20908, 20932, 20935,
20944, 20947, 20950, 20953, 20955,
20962, 20980, 20983, 20986, 20991,
20997, 21005, 21012, 21020, 21027,
21034, 21042, 21047, 21049, 21051,
21057, 21059, 21061, 21066, 21072,
21078, 21086, 21092, 21100, 21106,
21114, 21121, 21129, 21137, 21144,
21157, 21171, 21181, 21215, 21226,
21237, 21248, 21259, 21270, 21283,
21299, 21306, 21316, 21321, 21336,
21351, 21363, 21379, 21389, 21403,
21406, 21409, 21421, 21460, 21464,
21468, 21471, 21522, 21531, 21540,
21553, 21568, 21599, 21613, 21615,
21646, 21648, 21671, 21681, 21688,
21695, 21702, 21713, 21724, 21729,
21740, 21774, 21789, 21867, 21881,
21918, 21936, 21946, 21965, 21970,
21984, 21989, 21999, 22010, 22022,
22034, 22094, 22141, 22149, 22178,
22227, 22235, 22259, 22262, 22265,
22310, 22315, 22422, 22495, 22498,
22544, 22614, 22648, 22660, 22666,
22672, 22684, 22703, 22712, 22723,
22729, 22734, 22742, 22755, 22768,
22782, 22797, 22804, 22810, 22819,
22826, 22835, 22837, 22839, 22841,
22892, 22898, 22907, 22915, 22921,
23012, 23014, 23016, 23036, 23111,
23113, 23115, 23121, 23123, 23125,
23137, 23170, 23213, 23224, 23232,
23243, 23300, 23302, 23306, 23324,
23327, 23329, 23333, 23575, 23576,
24432, 24449, 24454, 24461, 24463,

- 24465, 24472, 24473, 24656, 24673,
 24679, 24696, 24701, 24711, 24773,
 24784, 24786, 24796, 24814, 24827,
 24840, 24844, 24847, 24854, 24860,
 24862, 24864, 24869, 24874, 24883,
 24893, 24895, 24898, 24900, 24916,
 24921, 24941, 24964, 24967, 24980,
 24992, 24997, 24999, 25001, 25003,
 25005, 25007, 25009, 25011, 25016,
 25026, 25039, 25052, 25057, 25059,
 25061, 25070, 25082, 25094, 25106,
 25149, 25164, 25190, 25203, 25218,
 25230, 25249, 25280, 25289, 25291,
 25293, 25295, 25310, 25323, 25337,
 25344, 25352, 25356, 25360, 25363,
 25378, 25388, 25423, 25430, 25436,
 25442, 25445, 25452, 25461, 25472,
 25483, 25494, 25496, 25498, 25500,
 25502, 25507, 25512, 25522, 25531,
 25533, 25536, 25538, 25540, 25542,
 25547, 25552, 25557, 25559, 25571,
 25576, 25578, 25580, 25582, 25584,
 25586, 25588, 25590, 25601, 25606,
 25615, 25624, 25629, 25633, 25635,
 25637, 25647, 25652, 25657, 25662,
 25672, 25691, 25693, 25695, 25697,
 25699, 25751, 25764, 25785, 25799,
 25804, 25806, 25814, 25824, 25832,
 25837, 25842, 25853, 25863, 25873,
 25875, 25877, 25879, 25910, 25912,
 25917, 25919, 25921, 25924, 25945,
 25956, 25969, 25971, 25973, 25975,
 25977, 25979, 25981, 25983, 25985,
 25996, 25998, 26000, 26002, 26011,
 26014, 26016, 26018, 26020, 26031,
 26062, 26064, 26066, 26068, 26083
 \cs_new_protected:Npx
 11, 330, 331, 336, 1680,
 2048, 2084, 2089, 2178, 2238, 2643,
 2647, 2652, 2822, 2826, 2827, 3812,
 7161, 7680, 8307, 8309, 8311, 8313,
 8315, 8324, 8326, 8328, 8586, 8588,
 8590, 8592, 8594, 8603, 8605, 8607,
 18579, 18593, 18595, 22481, 24739,
 24764, 25123, 25130, 25136, 25142
 \cs_new_protected_nopar:Nn
 13, 2176, 2236
 \cs_new_protected_nopar:Npn
 11, 2048, 2065, 2078, 2082
 \cs_new_protected_nopar:Npx
 11, 2048, 2078, 2083
 \cs_set:Nn 13, 316, 2176, 2236
 \cs_set:Npn
 10, 11, 23, 96, 96, 312, 316,
 484, 1387, 1417, 1423, 1424, 1425,
 1426, 1427, 1428, 1429, 1430, 1431,
 1432, 1433, 1434, 1435, 1436, 1437,
 1438, 1439, 1440, 1441, 1442, 1443,
 1444, 1445, 1446, 1447, 1448, 1449,
 1450, 1451, 1507, 1604, 1613, 1615,
 1718, 1724, 1736, 1738, 1894, 1898,
 1902, 1906, 1911, 1917, 1918, 1930,
 1934, 1936, 1938, 1996, 1998, 2000,
 2002, 2004, 2006, 2008, 2010, 2029,
 2048, 2064, 2072, 2072, 2176, 2236,
 3108, 3173, 3293, 3464, 3857, 3887,
 5138, 5151, 6740, 6812, 7221, 7672,
 7678, 7859, 8127, 8129, 8951, 9470,
 10490, 11672, 11680, 11689, 11706,
 11714, 11742, 16938, 17275, 18000,
 18001, 18002, 18310, 18311, 18843,
 18844, 18859, 18860, 19138, 19162,
 19198, 19705, 19986, 23169, 24482
 \cs_set:Npx 11, 321, 565, 1387,
 1920, 2072, 2073, 3175, 7595, 7601,
 9516, 9517, 9518, 9519, 9520, 10477,
 10483, 10735, 17750, 17756, 19375
 \cs_set_eq:NN 15, 97, 299,
 313, 435, 1496, 1504, 1846, 2090,
 2647, 2665, 2826, 2893, 2902, 4762,
 4763, 4765, 4875, 4876, 4887, 6060,
 6247, 6250, 7164, 7358, 7588, 7593,
 7600, 7683, 9522, 9523, 9524, 9526,
 9528, 10730, 10745, 10749, 10777,
 10788, 10798, 11839, 11844, 17181,
 17182, 17187, 17408, 17451, 17475,
 19133, 19139, 19159, 19708, 20367
 \cs_set_nopar:Nn 13, 2176, 2236
 \cs_set_nopar:Npn 10,
 11, 119, 297, 312, 1387, 1416, 1492,
 1653, 1654, 2064, 2066, 10689, 10756
 \cs_set_nopar:Npx
 11, 1387, 1420, 2064, 2067, 2363,
 2565, 2940, 2943, 2946, 2964, 2967,
 2970, 2973, 2996, 2999, 3002, 3005
 \cs_set_protected:Nn 13, 2176, 2236
 \cs_set_protected:Npn 10, 11, 254,
 313, 1387, 1403, 1405, 1407, 1409,
 1411, 1413, 1418, 1453, 1456, 1461,
 1469, 1479, 1484, 1493, 1498, 1510,
 1511, 1515, 1517, 1526, 1535, 1540,
 1546, 1553, 1555, 1556, 1557, 1558,
 1559, 1561, 1572, 1574, 1586, 1602,
 1612, 1633, 1635, 1638, 1639, 1649,
 1651, 1659, 1668, 1678, 1690, 1693,
 1695, 1697, 1699, 1703, 1704, 1706,
 1708, 1712, 1714, 1716, 1722, 1728,
 1732, 1733, 1740, 1742, 1744, 1746,

- 1748, 1753, 1755, 1757, 1759, 1761,
1766, 1778, 1793, 1810, 1827, 1833,
1839, 1845, 1847, 1849, 1861, 1875,
2012, 2025, 2027, 2031, 2033, 2037,
2045, 2050, 2084, 2084, 2118, 2139,
3781, 3808, 4457, 4468, 4484, 4491,
4495, 4505, 4508, 4522, 4537, 4540,
4549, 4557, 4791, 5279, 7153, 7278,
7448, 7466, 8230, 8293, 8573, 8575,
8882, 8947, 9132, 9451, 9453, 9570,
9650, 9741, 9871, 10176, 10224,
10308, 10724, 12153, 12217, 12745,
12813, 12827, 12966, 12983, 13013,
13026, 13085, 13100, 13117, 17183,
18591, 18616, 18625, 19120, 19127,
19129, 19131, 19134, 19136, 19140,
19142, 19144, 19146, 19151, 19153,
19155, 19157, 19160, 19864, 19865,
20253, 21604, 21625, 22469, 22474,
22852, 22866, 22877, 24007, 24011,
24014, 24040, 24051, 24182, 24185,
24207, 24430, 24491, 24661, 24706
- \cs_set_protected:Npx
..... 11, 240, 1387, 2084, 2085, 8449
- \cs_set_protected_nopar:Nn
..... 14, 2176, 2236
- \cs_set_protected_nopar:Npn
..... 12, 313, 1387, 2078, 2078
- \cs_set_protected_nopar:Npx
..... 12, 1387, 2078, 2079
- \cs_show:N 16, 16, 20, 319, 2313
- \cs_to_str:N 4, 17, 44,
51, 307, 308, 308, 382, 1573, 1911,
1924, 4420, 4421, 4422, 4423, 4424,
4425, 4426, 4427, 4428, 4429, 4430,
4431, 9456, 13260, 17764, 19102, 24288
- \cs_undefine:N
..... 15, 428, 566, 2106, 8611, 8612, 8613
- cs internal commands:
- __cs_count_signature:N 22, 2149
- __cs_count_signature:nnN 2149
- __cs_generate_from_signature:n .
..... 2194, 2207
- __cs_generate_from_signature:NNn
..... 2180, 2184
- __cs_generate_from_signature:nnNNNn
..... 2186, 2189
- __cs_generate_internal_variant:n
..... 2817, 2822
- __cs_generate_internal_variant:wnNwnn
..... 2824, 2840
- __cs_generate_internal_variant:wnnw
..... 2822
- __cs_generate_internal_variant_-
loop:n 2822
- __cs_generate_variant:N . 2636, 2643
- __cs_generate_variant:nnNN
..... 2639, 2666
- __cs_generate_variant:Nnnw
..... 2673, 2675
- __cs_generate_variant:ww 2643
- __cs_generate_variant:wwNN
..... 332, 333, 2682, 2798
- __cs_generate_variant:wwNw .. 2643
- __cs_generate_variant_loop:nNwN
..... 332, 333, 2683, 2695
- __cs_generate_variant_loop_-
base:N 2695
- __cs_generate_variant_loop_-
end:nwwwNNnn . 332, 333, 2685, 2695
- __cs_generate_variant_loop_-
invalid:NNwNNnn 333, 2695
- __cs_generate_variant_loop_-
long:wNNnn 333, 2688, 2695
- __cs_generate_variant_loop_-
same:w 333, 2695
- __cs_generate_variant_loop_-
special:NNwNNnn 2695, 2793
- __cs_generate_variant_loop_-
warning:nnnnnn . 2695, 22469, 22474
- __cs_generate_variant_same:N ...
..... 333, 2738, 2787
- __cs_get_function_name:N .. 22, 1936
- __cs_get_function_signature:N ..
..... 22, 1936
- __cs_parm_from_arg_count:nnTF ..
..... 1768, 2118, 2163
- __cs_parm_from_arg_count_-
test:nnTF 2118
- __cs_split_function:NN
..... 22, 308, 1750, 1763, 1854, 1855,
1920, 1937, 1939, 2150, 2186, 2637
- __cs_split_function_auxi:w .. 1920
- __cs_split_function_auxii:w . 1920
- __cs_tmp:w 22, 330, 336, 2048, 2064,
2066, 2067, 2068, 2069, 2070, 2071,
2072, 2073, 2074, 2075, 2076, 2077,
2078, 2079, 2080, 2081, 2082, 2083,
2084, 2085, 2086, 2087, 2088, 2089,
2176, 2212, 2213, 2214, 2215, 2216,
2217, 2218, 2219, 2220, 2221, 2222,
2223, 2224, 2225, 2226, 2227, 2228,
2229, 2230, 2231, 2232, 2233, 2234,
2235, 2236, 2244, 2245, 2246, 2247,
2248, 2249, 2250, 2251, 2252, 2253,
2254, 2255, 2256, 2257, 2258, 2259,

- 2260, 2261, 2262, 2263, 2264, 2265,
- 2266, 2267, 2647, 2665, 2818, 2826
- _cs_to_str:N 307, 1911
- _cs_to_str:w 307, 1911
- csc 196
- cscd 196
- \csname 14, 21, 39, 43, 49,
- 68, 90, 92, 98, 123, 146, 150, 222, 321
- \currentgrouplevel 613
- \currentgrouptype 614
- \currentifbranch 615
- \currentiflevel 616
- \currentiftype 617
- D**
- \day 322
- dd 199
- \deadcycles 323
- debug commands:
- \debug_deprecation_off: 425
- \debug_deprecation_on: 425, 537
- \debug_off:n 239, 1459
- \debug_on:n 239, 1459
- \debug_resume: 239, 295, 905, 1490, 21550, 21660
- \debug_suspend: 239, 295, 905, 1490, 21543, 21658
- debug internal commands:
- _debug:TF 22, 1453, 1459, 1490, 1513, 1570,
- 1600, 1631, 1647, 1657, 1691, 1710,
- 5982, 9788, 11835, 20810, 20825, 22465
- _debug_check-declarations_off: 1513
- _debug_check-declarations_on: 1513
- _debug_check-expressions_off: 1600
- _debug_check-expressions_on: 1600
- _debug_chk_cs_exist:N 22,
- 296, 1513, 1893, 1897, 1901, 1905, 2633
- _debug_chk_expr:nNnN 23, 298, 1600, 5117, 5121,
- 5124, 5135, 5136, 5148, 5149, 5169,
- 5170, 5197, 5198, 5220, 5284, 5400,
- 5402, 5442, 5452, 5519, 5520, 5521,
- 9876, 9914, 9924, 9925, 9937, 9938,
- 9962, 9964, 10091, 10095, 10101,
- 10120, 10181, 10229, 10243, 10251,
- 10256, 10316, 10357, 22927, 22928
- _debug_chk_expr_aux:nNnN ... 1600
- _debug_chk_var_exist:N 23, 23, 296, 429, 1513, 2892,
- 2898, 2909, 2910, 2917, 2918, 6055
- _debug_chk_var_global:N ... 23,
- 296, 1513, 2897, 2947, 2950, 2953,
- 2974, 2977, 2980, 2983, 3006, 3009,
- 3012, 3015, 5257, 5271, 5293, 5296,
- 5309, 5312, 5322, 6251, 6254, 6268,
- 9856, 9882, 9892, 9900, 9908, 10162,
- 10187, 10201, 10209, 10293, 10325,
- 10334, 10341, 10349, 20866, 20874,
- 20934, 20985, 20996, 21011, 21033,
- 21077, 21091, 21105, 21120, 21143
- _debug_chk_var_local:N 23, 296, 1513,
- 2891, 2938, 2941, 2944, 2962, 2965,
- 2968, 2971, 2994, 2997, 3000, 3003,
- 5255, 5267, 5287, 5290, 5303, 5306,
- 5319, 6245, 6248, 6265, 9854, 9879,
- 9887, 9897, 9905, 10160, 10184,
- 10198, 10206, 10290, 10322, 10330,
- 10338, 10346, 20863, 20871, 20931,
- 20982, 20990, 21004, 21026, 21071,
- 21085, 21099, 21113, 21136, 21156
- _debug_chk_var_scope:NN 23, 23, 296, 1513, 2862, 2868,
- 5218, 6126, 9847, 10153, 10283, 23035
- _debug_chk_var_scope_aux:NN ... 1538, 1544, 1550, 1570
- _debug_chk_var_scope_aux:Nn . 1570
- _debug_chk_var_scope_aux:NNn ... 297, 1570
- _debug_deprecation:nnNnpn 299,
- 299, 1657, 3773, 3775, 7768, 9799,
- 9807, 9814, 9821, 9823, 9825, 9827,
- 9829, 9831, 17236, 17238, 21458,
- 21462, 21466, 21469, 22905, 22913
- _debug_deprecation_aux:nnNnn 1657
- _debug_deprecation_off: 1647
- \g_debug_deprecation_off_tl 299,
- 1647, 1675, 5986, 9795, 11842, 22472
- _debug_deprecation_on: 1647
- \g_debug_deprecation_on_tl 299,
- 1647, 1670, 5984, 9790, 11837, 22467
- _debug_log-functions_off: .. 1631
- _debug_log-functions_on: ... 1631
- _debug_log:n 23, 299, 1631, 2036, 2802, 8109, 10720
- _debug_patch:nnNnpn 23, 23, 24,
- 24, 300, 301, 340, 1691, 1892, 1896,
- 1900, 1904, 2035, 2633, 2798, 2862,
- 2868, 2907, 2915, 2938, 2941, 2944,
- 2947, 2950, 2953, 2962, 2965, 2968,
- 2971, 2974, 2977, 2980, 2983, 2994,
- 2997, 3000, 3003, 3006, 3009, 3012,
- 3015, 5255, 5257, 5267, 5271, 5303,
- 5306, 5309, 5312, 6054, 6106, 6126,
- 6245, 6248, 6251, 6254, 6265, 6268,
- 8108, 9847, 9854, 9856, 9887, 9892,

- 10153, 10160, 10162, 10283, 10290,
10293, 10330, 10334, 10717, 17989,
19282, 19301, 19340, 19424, 19477,
19666, 19685, 19791, 19942, 20863,
20866, 20871, 20874, 20931, 20934,
20982, 20985, 20990, 20996, 21004,
21011, 21026, 21033, 21071, 21077,
21085, 21091, 21099, 21105, 21113,
21120, 21136, 21143, 21156, 23035
- __debug_patch_args:nnnNNpn . 24,
1706, 5217, 5281, 9873, 10178, 10310
- __debug_patch_args:nNnpn
..... 24, 24, 1706, 4143, 4202,
5116, 5120, 5123, 5133, 5146, 5167,
5195, 5517, 7171, 9913, 9922, 9935,
10090, 10094, 10100, 10119, 10242,
10250, 10255, 10354, 16531, 22925
- __debug_patch_args_aux:nnnn . 1706
- __debug_patch_args_aux:nnnNNnn 1706
- __debug_patch_args_aux:nnnNNnnn
..... 1706
- __debug_patch_aux:nnnn 1691
- __debug_patch_auxii:nnnn 1691
- __debug_patch_conditional:nNnpnn
..... 23, 300, 1691, 6097
- __debug_patch_conditional_
args:nnnNNpnn 24, 1706
- __debug_patch_conditional_
args:nNnpnn 24,
1706, 5398, 5441, 5451, 9960, 10226
- __debug_suspended:TF
..... 295, 1490, 1519,
1528, 1537, 1542, 1548, 1606, 1636
- \l__debug_suspended_tl 1490
- __debug_tmp:w 1706
- __debug_trace:nnn 19342,
19669, 19686, 19792, 20810, 20834
- __debug_trace_pop:nnN
..... 17993, 19286, 19305,
19426, 19479, 19671, 19944, 20810
- __debug_trace_push:nnN
..... 17991, 19283, 19302,
19425, 19478, 19668, 19943, 20810
- \g__debug_trace_regex_int 20824
- \def 74,
75, 76, 105, 122, 124, 125, 143, 144,
147, 163, 178, 207, 211, 236, 275, 324
- default commands:
 .default:n 173, 10875
- \defaultthyphenchar 325
- \defaultskewchar 326
- deg 198
- \delcode 327
- \delimiter 328
- \delimiterfactor 329
- \delimitershortfall 330
- deprecation internal commands:
 __deprecation_error:Nnn
 1673, 5985, 9792, 22422
- \c__deprecation_minus_one
 5979, 5980, 5981, 5987
- \detokenize 68, 222, 618
- \DH 24217
- \dh 24217
- dim commands:
 \dim_abs:n 156, 9913
- \dim_add:Nn 156, 9897
- \dim_case:nn 159, 10005
- \dim_case:nnn 22435
- \dim_case:nnTF
 159, 10005, 10010, 10015, 22435
- \dim_compare:nNnTF
 157, 159, 159, 159,
 160, 9960, 10029, 10064, 10072,
 10081, 10087, 21792, 21795, 21798,
 21807, 21810, 21813, 21822, 21829,
 21887, 21892, 21899, 22012, 22024,
 22506, 22523, 22552, 22566, 22576
- \dim_compare:nTF
 87, 158, 160, 160, 160,
 160, 9971, 10036, 10044, 10053, 10059
- \dim_compare_p:n 158, 9971
- \dim_compare_p:nNn 157, 9960
- \dim_const:Nn
 155, 539, 548, 9847, 10139,
 10140, 25275, 25277, 25477, 25479
- \dim_do_until:nn 160, 10034
- \dim_do_until:nNnn 159, 10062
- \dim_do_while:nn 160, 10034
- \dim_do_while:nNnn 159, 10062
- \dim_eval:n
 157, 158, 160, 160, 169, 539, 545,
 9851, 10008, 10013, 10018, 10023,
 10090, 10134, 10138, 21589, 21636,
 21708, 21719, 21732, 21734, 21736,
 21738, 21744, 21749, 21755, 21762,
 21769, 21995, 21996, 22272, 22273,
 22274, 22651, 22653, 22658, 22738,
 22739, 22746, 22747, 22823, 22830
- \dim_gadd:Nn 156, 9897
- .dim_gset:N 173, 10883
- \dim_gset:Nn 156, 539, 9879
- \dim_gset_eq:NN 156, 9887
- \dim_gsub:Nn 156, 9897
- \dim_gzero:N 155, 9854, 9864
- \dim_gzero_new:N 155, 9861
- \dim_if_exist:NnTF
 . 155, 9862, 9864, 9867, 25234, 25465

- \dim_if_exist_p:N [155](#), [9867](#)
- \dim_log:N [162](#), [10135](#)
- \dim_log:n [162](#), [10135](#)
- \dim_max:nn .. [156](#), [9913](#), [22717](#), [22721](#)
- \dim_min:nn
 - [156](#), [9913](#), [22715](#), [22719](#), [22732](#)
- \dim_new:N [155](#), [155](#), [9839](#), [9850](#), [9862](#),
 - [9864](#), [10141](#), [10142](#), [10143](#), [10144](#),
 - [21162](#), [21163](#), [21164](#), [21165](#), [21166](#),
 - [21167](#), [21168](#), [21169](#), [21476](#), [21500](#),
 - [21501](#), [21504](#), [21505](#), [21506](#), [21507](#),
 - [22082](#), [22084](#), [22085](#), [22609](#), [22610](#),
 - [22611](#), [22612](#), [22613](#), [22753](#), [22754](#)
- \dim_ratio:nn .. [157](#), [546](#), [9956](#), [10128](#)
- .dim_set:N [173](#), [10883](#)
- \dim_set:Nn [156](#), [9879](#), [21183](#),
 - [21184](#), [21185](#), [21217](#), [21228](#), [21301](#),
 - [21302](#), [21303](#), [21318](#), [21391](#), [21392](#),
 - [21393](#), [21395](#), [21397](#), [21399](#), [21574](#),
 - [21620](#), [21794](#), [21799](#), [21809](#), [21814](#),
 - [21824](#), [21831](#), [21844](#), [21870](#), [21890](#),
 - [21949](#), [21950](#), [21952](#), [21954](#), [21972](#),
 - [21973](#), [22083](#), [22186](#), [22187](#), [22238](#),
 - [22239](#), [22240](#), [22242](#), [22654](#), [22686](#),
 - [22694](#), [22705](#), [22706](#), [22707](#), [22708](#),
 - [22714](#), [22716](#), [22718](#), [22720](#), [22725](#),
 - [22731](#), [22787](#), [22789](#), [22791](#), [22799](#),
 - [22801](#), [25271](#), [25272](#), [25475](#), [25476](#)
- \dim_set_eq:NN
 - .. [156](#), [9887](#), [21576](#), [21577](#), [21622](#),
 - [21623](#), [25236](#), [25238](#), [25467](#), [25468](#)
- \dim_show:N [162](#), [10131](#)
- \dim_show:n [162](#), [547](#), [10133](#)
- \dim_sub:Nn [156](#), [9897](#)
- \dim_to_decimal:n
 - [161](#), [10100](#), [10118](#), [10125](#),
 - [25710](#), [25711](#), [25712](#), [25713](#), [25714](#),
 - [25716](#), [25790](#), [25791](#), [25835](#), [25840](#),
 - [25846](#), [25847](#), [25848](#), [25849](#), [25858](#),
 - [25859](#), [25860](#), [25951](#), [25970](#), [26078](#)
- \dim_to_decimal_in_bp:n
 - [161](#), [161](#), [10117](#), [24804](#),
 - [24805](#), [24806](#), [24867](#), [24872](#), [24878](#),
 - [24879](#), [24887](#), [24888](#), [24889](#), [24987](#),
 - [24991](#), [24995](#), [25101](#), [25155](#), [25156](#),
 - [25157](#), [25301](#), [25302](#), [25303](#), [25402](#),
 - [25403](#), [25404](#), [25405](#), [25505](#), [25510](#),
 - [25516](#), [25517](#), [25518](#), [25526](#), [25527](#),
 - [25566](#), [25570](#), [25574](#), [25668](#), [25955](#)
- \dim_to_decimal_in_sp:n
 - [161](#), [161](#), [10119](#)
- \dim_to_decimal_in_unit:nn [161](#), [10123](#)
- \dim_to_fp:n
 - [162](#), [620](#), [637](#), [10131](#), [16531](#),
 - [21221](#), [21222](#), [21232](#), [21233](#), [21289](#),
 - [21292](#), [21293](#), [21319](#), [21328](#), [21329](#),
 - [21343](#), [21344](#), [21357](#), [21369](#), [21372](#),
 - [21373](#), [21837](#), [21839](#), [21849](#), [21850](#),
 - [21851](#), [21852](#), [21874](#), [21875](#), [21876](#),
 - [21877](#), [22690](#), [22691](#), [22698](#), [22699](#),
 - [22758](#), [22761](#), [22762](#), [22800](#), [22802](#)
- \dim_until_do:nn [160](#), [10034](#)
- \dim_until_do:nNnn [159](#), [10062](#)
- \dim_use:N [160](#), [160](#), [545](#), [9918](#),
 - [9929](#), [9930](#), [9931](#), [9942](#), [9943](#), [9944](#),
 - [9974](#), [9993](#), [10093](#), [10097](#), [10105](#),
 - [21980](#), [22656](#), [22658](#), [22664](#), [22670](#),
 - [22679](#), [22680](#), [22681](#), [22808](#), [22815](#)
- \dim_while_do:nn [160](#), [10034](#)
- \dim_while_do:nNnn [160](#), [10062](#)
- \dim_zero:N [155](#), [155](#), [9854](#),
 - [9862](#), [21186](#), [21304](#), [21394](#), [21785](#),
 - [21786](#), [25232](#), [25233](#), [25463](#), [25464](#)
- \dim_zero_new:N [155](#), [9861](#)
- \c_max_dim [162](#), [165](#),
 - [6017](#), [6022](#), [6024](#), [10139](#), [10270](#),
 - [22705](#), [22706](#), [22707](#), [22708](#), [22725](#)
- \g_tmpa_dim [162](#), [10141](#)
- \l_tmpa_dim [162](#), [10141](#)
- \g_tmpb_dim [162](#), [10141](#)
- \l_tmpb_dim [162](#), [10141](#)
- \c_zero_dim [162](#), [10139](#), [10269](#),
 - [21048](#), [21068](#), [21452](#), [21792](#), [21795](#),
 - [21798](#), [21807](#), [21810](#), [21813](#), [21822](#),
 - [21829](#), [21887](#), [21892](#), [21899](#), [22510](#),
 - [22521](#), [22527](#), [22539](#), [22552](#), [22556](#),
 - [22564](#), [22566](#), [22570](#), [22576](#), [22586](#)
- dim internal commands:
 - __dim_abs:N [9913](#)
 - __dim_case:nnTF [10005](#)
 - __dim_case:nw [10005](#)
 - __dim_case_end:nw [10005](#)
 - __dim_compare:w [9971](#)
 - __dim_compare:wNN [542](#), [9971](#)
 - __dim_compare_!:w [9971](#)
 - __dim_compare_<:w [9971](#)
 - __dim_compare_=:w [9971](#)
 - __dim_compare_>:w [9971](#)
 - __dim_compare_end:w ... [9979](#), [10003](#)
 - __dim_eval:n .. [169](#), [10094](#), [20890](#),
 - [20892](#), [20894](#), [20903](#), [20905](#), [20907](#),
 - [20909](#), [20993](#), [20999](#), [21029](#), [21036](#),
 - [21044](#), [21063](#), [21102](#), [21108](#), [21139](#),
 - [21146](#), [21158](#), [22502](#), [22504](#), [22548](#),
 - [22550](#), [22559](#), [22583](#), [22631](#), [25676](#)
 - __dim_eval:w [169](#), [169](#),
 - [546](#), [620](#), [9836](#), [9876](#), [9881](#), [9884](#),
 - [9899](#), [9902](#), [9907](#), [9910](#), [9914](#), [9918](#),

- 9924, 9925, 9929, 9930, 9931, 9937,
 9938, 9942, 9943, 9944, 9959, 9962,
 9964, 9968, 9974, 9993, 9998, 10091,
 10093, 10095, 10096, 10101, 10105,
 10120, 10122, 12276, 12289, 12852
 _dim_eval_end: 169,
 169, 9836, 9881, 9884, 9899, 9902,
 9907, 9910, 9918, 9933, 9946, 9959,
 9963, 9968, 10093, 10096, 10105, 10122
 _dim_maxmin:wwN 9913
 _dim_ratio:n 9956
 _dim_tmp:w
 540, 540, 548, 9871, 9879,
 9882, 9897, 9900, 9905, 9908, 10176,
 10184, 10187, 10198, 10201, 10206,
 10209, 10224, 10241, 10308, 10322,
 10325, 10338, 10341, 10346, 10349
 _dim_to_decimal:w 10100
 \dimen 331, 7505
 \dimendef 332
 \dimexpr 619
 \directlua 16, 23, 53, 59, 61, 875
 \disablejktoken 1162
 \discretionary 333
 \displayindent 334
 \displaylimits 335
 \displaystyle 336
 \displaywidowpenalties 620
 \displaywidowpenalty 337
 \displaywidth 338
 \divide 339
 \DJ 24218
 \dj 24218
 \do 1200
 \doublehyphenemerits 340
 \dp 341
 \draftmode 956
 driver internal commands:
 _driver_absolute_lengths:n
 24788, 24801
 _driver_box_use_clip:N
 255, 22496, 24796, 25149, 25295, 25699
 _driver_box_use_rotate:Nn
 255, 21204, 24814, 25164, 25310, 25751
 _driver_box_use_scale:Nnn
 256, 21425, 24827, 25190, 25323, 25764
 \g_driver_clip_path_int
 25699, 25883,
 25886, 25899, 25928, 25931, 25939
 _driver_color_convert:w 24739
 _driver_color_convert_cmyk:w 24739
 _driver_color_convert_gray:w 24739
 _driver_color_convert_rgb:w . 24739
 _driver_color_convert_spot: . 24679
 _driver_color_convert_spot:n 24692
 _driver_color_convert_spot:w ..
 24679, 24739
 _driver_color_pickup:N
 256, 22318, 24655, 24700
 _driver_color_pickup_aux:w ...
 984, 24671, 24673, 24700
 _driver_color_reset:
 22321, 24679, 24739
 _driver_color_select:n
 256, 22320, 24679, 24739
 \l_driver_color_stack_int
 24738, 24744, 24769
 _driver_convert_model:w 24679
 \l_driver_cos_fp 25164
 _driver_draw_add_to_path:n ...
 25832, 25878
 _driver_draw_begin:
 256, 24847, 25494, 25799
 _driver_draw_cap_but:
 259, 259, 24980, 25559, 25945
 _driver_draw_cap_rectangle: ...
 259, 24980, 25559, 25945
 _driver_draw_cap_round:
 259, 24980, 25559, 25945
 _driver_draw_clip:
 258, 24898, 25536, 25877
 \g_driver_draw_clip_bool
 24898, 25877
 _driver_draw_closepath:
 257, 24898, 25536, 25877
 _driver_draw_closestroke: ...
 257, 24898, 25536, 25877
 _driver_draw_color_cmyk:nnnn ..
 259, 25011, 25590, 25985
 _driver_draw_color_cmyk_-
 aux:nnnn 25590
 _driver_draw_color_cmyk_-
 aux:NNnnnn
 25985, 25997, 25999, 26001
 _driver_draw_color_cmyk_-
 fill:nnnn 259, 25011, 25590, 25985
 _driver_draw_color_cmyk_-
 stroke:nnnn 259, 25011, 25590, 25985
 _driver_draw_color_gray:n
 259, 25011, 25590, 25985
 _driver_draw_color_gray_aux:n .
 25590
 _driver_draw_color_gray_-
 aux:NNn . 26002, 26015, 26017, 26019
 _driver_draw_color_gray_-
 aux:nNN 26006, 26011, 26013
 _driver_draw_color_gray_fill:n
 259, 25011, 25590, 25985

_driver_draw_color_gray_-
 stroke:n . [259](#), [25011](#), [25590](#), [25985](#)
 _driver_draw_color_reset: . . [25011](#)
 _driver_draw_color_rgb:nnn . . .
 [259](#), [25011](#), [25590](#), [25985](#)
 _driver_draw_color_rgb_aux:nnn
 [25590](#)
 _driver_draw_color_rgb_-
 auxi:NNnnn
 [26020](#), [26063](#), [26065](#), [26067](#)
 _driver_draw_color_rgb_-
 auxii:nnn [25989](#)
 _driver_draw_color_rgb_-
 auxii:nnnNN . . . [26012](#), [26024](#), [26031](#)
 _driver_draw_color_rgb_-
 fill:nnn . [259](#), [25011](#), [25590](#), [25985](#)
 _driver_draw_color_rgb_-
 stroke:nnn [259](#), [25011](#), [25590](#), [25985](#)
 _driver_draw_curveto:nnnnnn . . .
 [257](#), [24864](#), [25502](#), [25832](#)
 _driver_draw_dash:n
 [24980](#), [25559](#), [25945](#)
 _driver_draw_dash:nn
 [258](#), [24980](#), [25559](#), [25945](#)
 _driver_draw_dash_aux:nn . . . [25945](#)
 _driver_draw_discardpath:
 [258](#), [24898](#), [25536](#), [25877](#)
 _driver_draw_end:
 [256](#), [24847](#), [25494](#), [25799](#)
 \g_driver_draw_eor_bool . [24893](#),
 [24909](#), [24926](#), [24934](#), [24946](#), [24957](#),
 [24973](#), [25531](#), [25545](#), [25550](#), [25555](#)
 _driver_draw_evenodd_rule: . . .
 [258](#), [24893](#), [25531](#), [25873](#)
 _driver_draw_fill:
 [258](#), [24898](#), [25536](#), [25877](#)
 _driver_draw_fillstroke:
 [258](#), [24898](#), [25536](#), [25877](#)
 _driver_draw_hbox:Nnnnnnn
 [260](#), [25106](#), [25672](#), [26083](#)
 _driver_draw_join_bevel:
 [259](#), [24980](#), [25559](#), [25945](#)
 _driver_draw_join_miter:
 [259](#), [24980](#), [25559](#), [25945](#)
 _driver_draw_join_round:
 [259](#), [24980](#), [25559](#), [25945](#)
 _driver_draw_lineto:nn
 [257](#), [24864](#), [25502](#), [25832](#)
 _driver_draw_linewidth:n
 [258](#), [24980](#), [25559](#), [25945](#)
 _driver_draw_literal:n
 [24844](#), [24861](#), [24863](#),
 [24866](#), [24871](#), [24876](#), [24885](#), [24899](#),
 [24902](#), [24903](#), [24904](#), [24907](#), [24913](#),
 [24923](#), [24924](#), [24929](#), [24932](#), [24938](#),
 [24943](#), [24944](#), [24949](#), [24950](#), [24951](#),
 [24952](#), [24955](#), [24961](#), [24971](#), [24977](#),
 [24982](#), [24994](#), [24998](#), [25000](#), [25002](#),
 [25004](#), [25006](#), [25008](#), [25010](#), [25013](#),
 [25014](#), [25018](#), [25028](#), [25041](#), [25054](#),
 [25058](#), [25060](#), [25063](#), [25072](#), [25084](#),
 [25096](#), [25492](#), [25499](#), [25501](#), [25504](#),
 [25509](#), [25514](#), [25524](#), [25537](#), [25539](#),
 [25541](#), [25544](#), [25549](#), [25554](#), [25558](#),
 [25561](#), [25573](#), [25577](#), [25579](#), [25581](#),
 [25583](#), [25585](#), [25587](#), [25589](#), [25603](#),
 [25608](#), [25617](#), [25631](#), [25634](#), [25636](#),
 [25649](#), [25654](#), [25659](#), [25664](#), [25797](#),
 [25818](#), [25826](#), [25884](#), [25903](#), [25929](#)
 _driver_draw_miterlimit:n
 [259](#), [24980](#), [25559](#), [25945](#)
 _driver_draw_move:nn [257](#)
 _driver_draw_moveto:nn
 [257](#), [24864](#), [25502](#), [25832](#)
 _driver_draw_nonzero_rule:
 [258](#), [24893](#), [25531](#), [25873](#)
 _driver_draw_path:n [25877](#)
 \g_driver_draw_path_int [25877](#)
 \g_driver_draw_path_tl . . . [25832](#),
 [25888](#), [25904](#), [25906](#), [25933](#), [25942](#)
 _driver_draw_rectangle:nnnn . . .
 [257](#), [24864](#), [25502](#), [25832](#)
 _driver_draw_scope:n
 [25802](#), [25806](#),
 [25874](#), [25876](#), [25896](#), [25936](#), [25958](#),
 [25970](#), [25972](#), [25974](#), [25976](#), [25978](#),
 [25980](#), [25982](#), [25984](#), [26033](#), [26070](#)
 _driver_draw_scope_begin:
 [256](#), [24860](#), [25495](#), [25498](#), [25801](#), [25806](#)
 _driver_draw_scope_end:
 [256](#), [24860](#), [25497](#), [25498](#), [25805](#), [25806](#)
 \g_driver_draw_scope_int [25806](#)
 \l_driver_draw_scope_int [25806](#)
 _driver_draw_stroke:
 [257](#), [258](#), [24898](#), [25536](#), [25877](#)
 _driver_draw_transformcm:nnnnnn
 [260](#), [25094](#),
 [25110](#), [25662](#), [25678](#), [26068](#), [26086](#)
 \l_driver_image_attr_tl . [25202](#),
 [25207](#), [25214](#), [25222](#), [25234](#), [25237](#),
 [25239](#), [25273](#), [25275](#), [25277](#), [25283](#)
 _driver_image_getbb_aux:nNnn [25443](#)
 _driver_image_getbb_auxi:n . [25203](#)
 _driver_image_getbb_auxii:nN . [25423](#)
 _driver_image_getbb_auxii:n . [25203](#)
 _driver_image_getbb_auxii:nnN .
 [25423](#)

_driver_image_getbb_auxiii:nNnn	25321, 25333, 25681, 25693, 25745,
.....	25746, 25747, 25762, 25781, 26099
_driver_image_getbb_auxiv:nnNnn	\l_driver_sin_fp 25164
.....	\l_driver_tmp_box 25672
_driver_image_getbb_auxv:nNnn	\dtou 1129
.....	\dump 342
_driver_image_getbb_auxvi:nNnn	\dviextension 876
.....	\dvifedback 877
_driver_image_getbb_eps:n	\dvivariable 878
.....	
_driver_image_getbb_jpg:n	
.....	
_driver_image_getbb_pagebox:w	
.....	
_driver_image_getbb_pdf:n	
.....	
_driver_image_getbb_png:n	
.....	
_driver_image_include_auxi:nn	
.....	
_driver_image_include_auxii:nnn	
.....	
_driver_image_include_auxiii:nn	
.....	
_driver_image_include_auxiii:nnn	
.....	
_driver_image_include_bitmap_	
quote:w	
_driver_image_include_eps:n	
.....	
_driver_image_include_jpg:n	
.....	
_driver_image_include_pdf:n	
.....	
_driver_image_include_png:n	
.....	
\g_driver_image_int	
.....	
_driver_literal:n	
.....	
_driver_matrix:n	
\g_driver_path_int	
_driver_scope_begin:	
_driver_scope_begin:n	
_driver_scope_end:	

- 12451, 12464, 12499, 12509, 12528,
 12541, 12554, 12558, 12569, 12592,
 12609, 12621, 12635, 12651, 12659,
 12661, 12671, 12682, 12698, 12714,
 12720, 12725, 12732, 12756, 12779,
 12806, 12924, 12928, 12935, 12955,
 12975, 12991, 13037, 13068, 13077,
 13092, 13108, 13128, 13169, 13183,
 13216, 13218, 13224, 13239, 13352,
 13363, 13384, 13387, 13390, 13393,
 13404, 13413, 13416, 13562, 13575,
 13578, 13585, 13603, 13617, 13634,
 13695, 13698, 13707, 13719, 13730,
 13744, 13757, 13797, 13831, 13851,
 13888, 13906, 13909, 13915, 13929,
 13964, 13982, 13985, 13988, 13991,
 14050, 14123, 14191, 14192, 14201,
 14236, 14319, 14323, 14327, 14389,
 14423, 14650, 14679, 14683, 14842,
 14851, 14903, 14914, 14930, 14938,
 14997, 15076, 15087, 15092, 15126,
 15139, 15151, 15157, 15330, 15337,
 15359, 15387, 15402, 15406, 15428,
 15459, 15462, 15487, 15490, 15527,
 15535, 15546, 15549, 15594, 15609,
 15624, 15639, 15654, 15669, 15690,
 15735, 15961, 15999, 16000, 16009,
 16053, 16105, 16119, 16120, 16121,
 16224, 16246, 16261, 16279, 16327,
 16343, 16493, 16543, 16548, 16645,
 16666, 16688, 16871, 16872, 17386,
 17389, 17392, 17402, 17417, 17444,
 17459, 17485, 17501, 17534, 17542,
 17544, 17546, 17547, 17548, 17549,
 17550, 17552, 17570, 17591, 17595,
 17660, 17664, 17844, 17845, 17849,
 17850, 17864, 17871, 18076, 18086,
 18133, 18142, 18154, 18155, 18157,
 18159, 18162, 18163, 18166, 18167,
 18176, 18178, 18180, 18183, 18184,
 18186, 18234, 18237, 18245, 18253,
 18256, 18265, 18268, 18277, 18285,
 18288, 18298, 18393, 18494, 18538,
 18542, 18545, 18556, 18561, 18659,
 18794, 18882, 18911, 18950, 18968,
 19073, 19103, 19367, 19385, 19404,
 19442, 19498, 19545, 19549, 19556,
 19577, 19588, 19707, 19822, 19908,
 19954, 20016, 20046, 20058, 20083,
 20099, 20284, 20432, 20454, 20505,
 20914, 20916, 20926, 23189, 23197,
 23205, 23954, 23961, 23973, 24330,
 24342, 24411, 24414, 24417, 24445
- em 199
- \emergencystretch 345
 \enablecjktoken 1163
 \end 118, 289, 346, 13484
 end internal commands:
 __regex_end 20272
 \endcsname 14, 21, 39, 43, 49,
 68, 90, 92, 98, 123, 146, 150, 222, 347
 \endgroup 13, 36,
 38, 42, 48, 74, 117, 135, 154, 203, 348
 \endinput 136, 349
 \endL 621
 \endlinechar 221, 234, 350
 \endR 622
 \enquote 13485
 \ensuremath 24281
 \eqno 351
 \errhelp 108, 127, 352
 \errmessage 116, 128, 353
 \ERROR 7292
 \errorcontextlines 354
 \errorstopmode 355
 \escapechar 356
 escapehex 24531
 \ETC 17720
 etex commands:
 \etex_beginL:D 609
 \etex_beginR:D 610
 \etex_botmarks:D 611
 \etex_clubpenalties:D 612
 \etex_currentgrouplevel:D 613
 \etex_currentgrouptype:D 614
 \etex_currentifbranch:D 615
 \etex_currentiflevel:D 616
 \etex_currentifttype:D 617
 \etex_detokenize:D
 349, 618, 1356, 3249, 3415,
 3902, 4023, 10480, 10498, 23218, 23237
 \etex_dimexpr:D 619, 9837
 \etex_displaywidowpenalties:D .. 620
 \etex_endL:D 621
 \etex_endR:D 622
 \etex_eTeXrevision:D 623
 \etex_eTeXversion:D 624
 \etex_everyeof:D
 625, 3044, 23313, 23340
 \etex_firstmarks:D 626
 \etex_fontchardp:D 627
 \etex_fontcharht:D 628
 \etex_fontcharic:D 629
 \etex_fontcharwd:D 630
 \etex_glueexpr:D 631, 10181,
 10186, 10189, 10200, 10203, 10208,
 10211, 10230, 10236, 10243, 10245,
 10251, 10253, 10256, 10258, 16537

- `\etex_glueshrink:D` 632, 23149
- `\etex_glueshrinkorder:D` 633
- `\etex_gluestretch:D`
 - 634, 17587, 17593, 23148
- `\etex_gluestretchorder:D` 635
- `\etex_gluetomu:D` 636
- `\etex_ifcsname:D` 637, 1346
- `\etex_ifdefined:D`
 - 638, 798, 1173, 1181,
 - 1212, 1215, 1221, 1275, 1276, 1283,
 - 1295, 1302, 1315, 1323, 1345, 1382
- `\etex_iffontchar:D` 639
- `\etex_interactionmode:D`
 - 640, 20954, 20957, 20959
- `\etex_interlinepenalties:D` 641
- `\etex_lastlinefit:D` 642
- `\etex_lastnodetype:D` 643
- `\etex_marks:D` 644
- `\etex_middle:D` 645
- `\etex_muexpr:D`
 - . 646, 10317, 10324, 10327, 10340,
 - 10343, 10348, 10351, 10357, 10362
- `\etex_mutogluue:D`
 - 23, 298, 647, 10317, 10358
- `\etex_numexpr:D` 648, 4446, 5112
- `\etex_pagediscards:D` 649
- `\etex_parshapedimen:D` 650
- `\etex_parshapeindent:D` 651
- `\etex_parshapelength:D` 652
- `\etex_predisplaydirection:D` ... 653
- `\etex_protected:D`
 - 654, 1389, 1391, 1393,
 - 1394, 1395, 1396, 1397, 1398, 1399,
 - 1400, 1408, 1410, 1412, 1414, 22424
- `\etex_readline:D` 655, 9295
- `\etex_savinghyphcodes:D` 656
- `\etex_savingvdiscards:D` 657
- `\etex_scantokens:D`
 - 658, 3061, 3111, 3126
- `\etex_showgroups:D` 659
- `\etex_showifs:D` 660
- `\etex_showtokens:D`
 - 365, 661, 1319, 3761, 8426
- `\etex_splitbotmarks:D` 662
- `\etex_splitdiscards:D` 663
- `\etex_splitfirstmarks:D` 664
- `\etex_TeXxTstate:D` 665
- `\etex_topmarks:D` 666
- `\etex_tracingassigns:D` 667
- `\etex_tracinggroups:D` 668
- `\etex_tracingifs:D` 669
- `\etex_tracingnesting:D` 670
- `\etex_tracingscantokens:D` 671
- `\etex_unexpanded:D` 329, 672, 1312,
 - 1351, 2612, 2614, 2617, 2622, 3550,
 - 3576, 3600, 5363, 7259, 23262, 23357
- `\etex_unless:D` 673, 1336
- `\etex_widowpenalties:D` 674
- `\eTeXrevision` 623
- `\eTeXversion` 624
- `\etoksapp` 879
- `\etokspre` 880
- `\euc` 1130
- `\everycr` 357
- `\everydisplay` 358
- `\everyeof` 625
- `\everyhbox` 359
- `\everyjob` 66, 67, 360
- `\everymath` 361
- `\everypar` 362
- `\everyvbox` 363
- `ex` 199
- `\exhyphenpenalty` 364
- `exp` 195
- exp commands:
 - `\exp:w` 34,
 - 35, 35, 302, 307, 322, 322, 323, 330,
 - 357, 357, 363, 376, 442, 511, 610,
 - 612, 613, 616, 616, 634, 638, 639,
 - 953, 1352, 1737, 1739, 2357, 2369,
 - 2375, 2415, 2419, 2424, 2430, 2436,
 - 2442, 2454, 2460, 2466, 2471, 2473,
 - 2480, 2551, 2556, 2561, 2570, 2572,
 - 2574, 2581, 2589, 2598, 2614, 2618,
 - 2623, 2625, 3334, 3339, 3344, 3349,
 - 3552, 3710, 3960, 3965, 3970, 3975,
 - 3992, 3997, 4002, 4007, 4159, 4168,
 - 4222, 5414, 5419, 5424, 5429, 6321,
 - 6441, 7174, 7180, 7666, 8886, 9616,
 - 9978, 10007, 10012, 10017, 10022,
 - 11426, 11627, 11867, 11985, 11986,
 - 11987, 11988, 12099, 12117, 12158,
 - 12202, 12209, 12214, 12223, 12239,
 - 12247, 12296, 12309, 12310, 12319,
 - 12331, 12349, 12350, 12370, 12383,
 - 12387, 12409, 12437, 12450, 12463,
 - 12487, 12498, 12508, 12527, 12540,
 - 12553, 12556, 12568, 12591, 12620,
 - 12634, 12650, 12670, 12681, 12687,
 - 12697, 12743, 12753, 12768, 12776,
 - 12793, 12809, 12816, 12853, 12862,
 - 12871, 12876, 12878, 12898, 12901,
 - 12908, 12909, 12958, 12974, 12996,
 - 13004, 13011, 13034, 13065, 13107,
 - 13125, 13195, 13207, 13236, 13238,
 - 13242, 13244, 13254, 13274, 13346,
 - 13360, 13370, 13479, 13480, 13481,

- 13628, 13631, 13639, 13663, 13671,
 14623, 15150, 15172, 15332, 15505,
 15711, 16103, 16104, 16108, 16378,
 16382, 16419, 16423, 16465, 16484,
 16488, 16524, 16528, 16595, 16691,
 16719, 16726, 16746, 16762, 23257,
 23264, 23359, 23400, 23414, 24335
 \exp_after:wN 32, 34, 35, 302,
 321, 323, 362, 365, 418, 490, 499,
 585, 587, 609, 610, 612, 613, 670,
 670, 728, 780, 802, 867, 1349, 1366,
 1368, 1373, 1375, 1577, 1607, 1608,
 1620, 1719, 1725, 1737, 1739, 1783,
 1796, 1814, 1816, 1866, 1871, 1878,
 1915, 1919, 1922, 1923, 1955, 1957,
 1960, 1983, 1985, 1988, 2111, 2113,
 2122, 2142, 2144, 2181, 2241, 2334,
 2344, 2351, 2353, 2356, 2357, 2364,
 2368, 2369, 2374, 2375, 2380, 2385,
 2387, 2390, 2399, 2401, 2404, 2405,
 2406, 2409, 2411, 2413, 2415, 2418,
 2423, 2428, 2429, 2430, 2434, 2435,
 2436, 2440, 2441, 2442, 2446, 2447,
 2448, 2452, 2453, 2454, 2458, 2459,
 2460, 2464, 2465, 2466, 2470, 2471,
 2472, 2473, 2477, 2478, 2479, 2480,
 2484, 2485, 2486, 2491, 2492, 2493,
 2494, 2498, 2499, 2500, 2501, 2547,
 2550, 2551, 2555, 2556, 2560, 2561,
 2568, 2570, 2572, 2574, 2576, 2579,
 2580, 2584, 2587, 2588, 2592, 2595,
 2596, 2597, 2605, 2608, 2610, 2611,
 2612, 2614, 2617, 2622, 2637, 2638,
 2639, 2640, 2645, 2649, 2671, 2678,
 2698, 2850, 3059, 3060, 3109, 3110,
 3124, 3125, 3184, 3185, 3186, 3191,
 3235, 3248, 3249, 3324, 3325, 3415,
 3523, 3550, 3581, 3586, 3587, 3588,
 3590, 3603, 3613, 3632, 3654, 3664,
 3667, 3684, 3685, 3695, 3700, 3701,
 3716, 3717, 3718, 3761, 3762, 3902,
 4021, 4022, 4034, 4088, 4111, 4146,
 4147, 4158, 4159, 4167, 4175, 4177,
 4183, 4186, 4206, 4207, 4208, 4220,
 4221, 4248, 4250, 4256, 4262, 4275,
 4295, 4306, 4322, 4330, 4338, 4345,
 4352, 4364, 4471, 4473, 4479, 4560,
 4674, 4676, 4688, 4696, 4795, 4833,
 4845, 4856, 4857, 4858, 4879, 4880,
 4927, 4956, 4957, 4958, 5028, 5029,
 5032, 5127, 5132, 5140, 5141, 5153,
 5154, 5175, 5176, 5202, 5203, 5347,
 5352, 5357, 5380, 5382, 5525, 5526,
 5527, 5721, 5749, 5754, 5782, 5795,
 5805, 5832, 5834, 5835, 5843, 5860,
 5904, 6052, 6061, 6111, 6113, 6120,
 6141, 6147, 6149, 6173, 6319, 6336,
 6341, 6345, 6442, 6638, 6653, 6675,
 6691, 6748, 6756, 6761, 6936, 6937,
 6940, 6941, 7174, 7175, 7180, 7181,
 7233, 7241, 7259, 7260, 7303, 7304,
 7305, 7416, 7437, 7484, 7520, 7549,
 7550, 7552, 7558, 7561, 7623, 7625,
 7635, 7636, 7637, 7639, 7645, 7646,
 7648, 7655, 7656, 7658, 7664, 7665,
 7668, 7745, 7754, 7763, 7862, 8056,
 8239, 8426, 8427, 8887, 8888, 8889,
 8890, 8902, 8934, 8954, 8964, 8969,
 9105, 9115, 9222, 9376, 9546, 9549,
 9599, 9608, 9611, 9614, 9615, 9617,
 9656, 9713, 9744, 9917, 9921, 9929,
 9930, 9942, 9943, 9973, 9978, 9989,
 9992, 10104, 10235, 10394, 10395,
 10404, 10406, 10423, 10428, 10430,
 10447, 10456, 10460, 10461, 10468,
 10470, 10471, 10480, 10498, 10501,
 10510, 10576, 10618, 10766, 10767,
 11074, 11154, 11155, 11174, 11184,
 11197, 11198, 11386, 11388, 11389,
 11400, 11401, 11402, 11412, 11414,
 11422, 11424, 11431, 11432, 11433,
 11434, 11435, 11436, 11441, 11442,
 11443, 11444, 11445, 11446, 11447,
 11518, 11520, 11547, 11551, 11576,
 11580, 11597, 11604, 11606, 11627,
 11686, 11694, 11711, 11720, 11766,
 11867, 11936, 11937, 11938, 11990,
 12000, 12019, 12025, 12051, 12052,
 12055, 12066, 12070, 12077, 12078,
 12089, 12090, 12099, 12106, 12108,
 12109, 12117, 12143, 12158, 12176,
 12177, 12180, 12181, 12183, 12184,
 12188, 12189, 12191, 12192, 12201,
 12202, 12209, 12214, 12223, 12237,
 12238, 12243, 12244, 12246, 12253,
 12254, 12256, 12274, 12275, 12279,
 12282, 12287, 12288, 12290, 12294,
 12295, 12297, 12306, 12307, 12308,
 12309, 12312, 12313, 12314, 12317,
 12331, 12348, 12349, 12359, 12360,
 12370, 12382, 12386, 12399, 12401,
 12409, 12419, 12421, 12427, 12432,
 12434, 12436, 12442, 12443, 12447,
 12449, 12461, 12462, 12484, 12486,
 12492, 12495, 12497, 12501, 12506,
 12511, 12512, 12522, 12523, 12525,
 12526, 12529, 12533, 12538, 12552,
 12555, 12567, 12576, 12583, 12584,

12585, 12586, 12588, 12590, 12601,
12602, 12603, 12604, 12606, 12608,
12610, 12611, 12612, 12618, 12619,
12629, 12633, 12634, 12636, 12637,
12638, 12643, 12649, 12660, 12662,
12669, 12670, 12672, 12673, 12680,
12686, 12696, 12749, 12750, 12751,
12752, 12766, 12767, 12769, 12774,
12775, 12790, 12792, 12809, 12816,
12850, 12851, 12852, 12858, 12859,
12860, 12861, 12867, 12868, 12869,
12870, 12877, 12889, 12890, 12896,
12897, 12899, 12900, 12906, 12907,
12922, 12923, 12925, 12926, 12933,
12934, 12936, 12939, 12951, 12953,
12954, 12956, 12957, 12959, 12972,
12973, 12974, 12976, 12977, 12978,
12988, 12989, 12990, 12995, 12997,
13008, 13009, 13010, 13018, 13019,
13021, 13031, 13032, 13033, 13036,
13038, 13039, 13040, 13063, 13064,
13067, 13069, 13070, 13071, 13090,
13091, 13093, 13094, 13095, 13105,
13106, 13107, 13109, 13110, 13111,
13123, 13124, 13127, 13129, 13130,
13131, 13151, 13152, 13153, 13154,
13155, 13156, 13157, 13167, 13168,
13170, 13171, 13172, 13178, 13188,
13189, 13190, 13191, 13192, 13193,
13194, 13195, 13200, 13201, 13202,
13203, 13204, 13205, 13206, 13222,
13223, 13225, 13226, 13233, 13234,
13235, 13240, 13241, 13243, 13252,
13253, 13268, 13270, 13271, 13272,
13345, 13359, 13369, 13377, 13378,
13478, 13561, 13563, 13602, 13604,
13626, 13627, 13630, 13637, 13638,
13641, 13642, 13649, 13654, 13661,
13662, 13669, 13670, 13703, 13704,
13705, 13707, 13718, 13743, 13745,
13751, 13752, 13756, 13759, 13781,
13783, 13796, 13798, 13804, 13806,
13809, 13815, 13817, 13819, 13820,
13821, 13823, 13828, 13830, 13832,
13836, 13839, 13845, 13846, 13850,
13852, 13853, 13854, 13862, 13864,
13865, 13872, 13878, 13885, 13886,
13891, 13892, 13893, 13894, 13913,
13914, 13915, 13921, 13922, 13923,
13928, 13930, 13938, 13940, 13942,
13943, 13945, 13956, 13958, 13960,
13961, 13966, 14017, 14018, 14025,
14026, 14028, 14030, 14032, 14034,
14036, 14038, 14040, 14049, 14051,
14057, 14059, 14061, 14062, 14063,
14069, 14071, 14073, 14074, 14075,
14096, 14097, 14100, 14108, 14110,
14114, 14115, 14116, 14117, 14122,
14124, 14130, 14133, 14136, 14139,
14147, 14150, 14153, 14156, 14163,
14165, 14171, 14179, 14181, 14183,
14200, 14202, 14209, 14211, 14214,
14220, 14222, 14224, 14225, 14226,
14228, 14242, 14243, 14246, 14264,
14266, 14268, 14280, 14283, 14286,
14289, 14292, 14295, 14298, 14301,
14305, 14317, 14321, 14325, 14328,
14343, 14349, 14351, 14353, 14363,
14387, 14390, 14402, 14404, 14408,
14409, 14410, 14412, 14413, 14415,
14421, 14422, 14428, 14431, 14432,
14433, 14434, 14447, 14452, 14454,
14461, 14464, 14467, 14470, 14473,
14476, 14484, 14485, 14497, 14505,
14507, 14517, 14519, 14526, 14535,
14537, 14540, 14543, 14546, 14549,
14562, 14564, 14572, 14574, 14582,
14584, 14593, 14596, 14599, 14606,
14621, 14622, 14639, 14641, 14642,
14699, 14712, 14714, 14720, 14733,
14735, 14737, 14761, 14775, 14777,
14784, 14786, 14826, 14827, 14828,
14830, 14831, 14832, 14834, 14835,
14841, 14843, 14844, 14850, 14852,
14853, 14854, 14855, 14867, 14873,
14875, 14910, 14917, 14924, 14944,
14945, 14947, 14949, 14951, 14964,
14969, 14970, 14971, 14972, 14973,
14977, 14982, 14984, 14990, 14996,
14998, 14999, 15005, 15006, 15007,
15008, 15009, 15010, 15011, 15012,
15017, 15019, 15021, 15023, 15025,
15029, 15031, 15033, 15035, 15037,
15039, 15057, 15061, 15069, 15070,
15075, 15077, 15086, 15089, 15090,
15091, 15093, 15094, 15095, 15103,
15109, 15121, 15124, 15125, 15127,
15128, 15152, 15153, 15156, 15158,
15174, 15178, 15179, 15180, 15196,
15202, 15211, 15212, 15213, 15221,
15237, 15253, 15269, 15285, 15301,
15327, 15331, 15332, 15336, 15338,
15374, 15380, 15381, 15383, 15385,
15386, 15388, 15389, 15399, 15400,
15403, 15404, 15405, 15407, 15408,
15409, 15426, 15427, 15429, 15430,
15436, 15438, 15441, 15444, 15447,
15450, 15458, 15461, 15463, 15466,

15473, 15477, 15485, 15486, 15489,
 15491, 15493, 15497, 15501, 15506,
 15507, 15515, 15516, 15517, 15518,
 15683, 15684, 15685, 15687, 15705,
 15706, 15707, 15708, 15709, 15710,
 15717, 15726, 15733, 15734, 15744,
 15908, 15909, 15910, 15931, 15932,
 15942, 15951, 15959, 15960, 15962,
 15963, 15968, 15969, 15978, 15985,
 15994, 15995, 16008, 16010, 16038,
 16039, 16048, 16051, 16076, 16082,
 16083, 16102, 16108, 16110, 16136,
 16137, 16139, 16153, 16154, 16162,
 16172, 16206, 16209, 16219, 16220,
 16223, 16225, 16231, 16245, 16247,
 16288, 16291, 16311, 16373, 16377,
 16382, 16385, 16406, 16407, 16414,
 16418, 16423, 16426, 16455, 16456,
 16462, 16463, 16464, 16471, 16479,
 16483, 16488, 16491, 16507, 16508,
 16519, 16523, 16528, 16534, 16535,
 16536, 16542, 16544, 16547, 16549,
 16591, 16593, 16594, 16615, 16635,
 16641, 16644, 16647, 16650, 16657,
 16663, 16667, 16677, 16686, 16691,
 16693, 16714, 16724, 16725, 16733,
 16740, 16749, 16750, 16758, 16862,
 17000, 17001, 17010, 17029, 17030,
 17045, 17046, 17047, 17250, 17258,
 17261, 17299, 17322, 17328, 17330,
 17341, 17399, 17400, 17401, 17402,
 17408, 17409, 17425, 17443, 17445,
 17451, 17452, 17482, 17484, 17486,
 17516, 17531, 17533, 17535, 17556,
 17566, 17574, 17584, 17594, 17596,
 17598, 17627, 17650, 17659, 17662,
 17663, 17665, 17666, 17674, 17675,
 17689, 17738, 17751, 17752, 17757,
 17758, 17761, 17764, 17801, 17808,
 17815, 17821, 17828, 17836, 17870,
 17872, 17881, 18007, 18035, 18052,
 18075, 18077, 18078, 18085, 18088,
 18089, 18113, 18135, 18144, 18244,
 18246, 18252, 18255, 18257, 18264,
 18267, 18269, 18276, 18278, 18284,
 18287, 18290, 18588, 18660, 18672,
 18793, 18796, 18977, 18985, 19056,
 19102, 19318, 19618, 19733, 19757,
 19810, 19836, 19900, 19901, 19909,
 19912, 20044, 20045, 20048, 20049,
 20057, 20059, 20060, 20069, 20082,
 20084, 20153, 20398, 20431, 20433,
 22328, 22489, 22846, 22871, 22932,
 22933, 23008, 23009, 23062, 23074,
 23083, 23089, 23092, 23262, 23282,
 23316, 23317, 23357, 23398, 23412,
 23429, 23430, 23627, 23628, 23649,
 23650, 23698, 23701, 23702, 23749,
 23782, 23874, 23924, 24018, 24020,
 24026, 24048, 24061, 24063, 24074,
 24076, 24198, 24254, 24331, 24333,
 24334, 24335, 24340, 24341, 24343,
 24353, 24354, 24361, 24362, 24439,
 24444, 24446, 24452, 24668, 24671
 \exp_args:cc
 29, 1365, 1819, 1830, 1836, 1842, 2398
 \exp_args:Nc
 . . . 27, 29, 317, 1365, 1369, 1377,
 1515, 1553, 1562, 1581, 1602, 1612,
 1633, 1638, 2046, 2065, 2091, 2096,
 2103, 2160, 2172, 2240, 2273, 2274,
 2275, 2276, 2298, 2302, 2398, 3153,
 3386, 3786, 3814, 6055, 6074, 9310,
 11259, 12008, 12233, 12982, 13001,
 13025, 13044, 13046, 13048, 13050,
 13052, 13054, 13056, 13099, 13115,
 13116, 13135, 13137, 17616, 18932
 \exp_args:Ncc 30, 2093, 2097,
 2105, 2281, 2282, 2283, 2284, 2398
 \exp_args:Nccc 30, 2398
 \exp_args:Ncco 30, 2475
 \exp_args:Nccx 31, 2521
 \exp_args:Ncf 30, 2426
 \exp_args:NcNc 30, 2475
 \exp_args:NcNo 30, 2475
 \exp_args:Ncno 31, 2521
 \exp_args:NcnV 31, 2521
 \exp_args:Ncnx 31, 2521
 \exp_args:Nco 30, 325, 2426
 \exp_args:Ncoo 31, 2521
 \exp_args:NcV 30, 2426
 \exp_args:Ncv 30, 2426
 \exp_args:NcVV 31, 2521
 \exp_args:Ncx 30, 2504, 8895
 \exp_args:Nf 29,
2414, 3722, 3723, 3739, 4135, 4137,
 4194, 4196, 4214, 4930, 4931, 4947,
 5415, 5420, 5425, 5430, 5595, 5664,
 5666, 5684, 5693, 5704, 5713, 5851,
 5868, 6035, 6925, 6976, 6990, 7011,
 7056, 7126, 7132, 7138, 7144, 8900,
 9648, 10008, 10013, 10018, 10023,
 13522, 19473, 22593, 22949, 22962,
 22987, 22989, 23013, 23015, 23281,
 23831, 23839, 23894, 23944, 24312,
 24320, 24324, 24368, 24374, 24384
 \exp_args:Nff . . 30, 2504, 6010, 24318
 \exp_args:Nffo 31, 2521

- \exp_args:Nfo 30, [2504](#)
- \exp_args:NNc 30, [291](#),
2092, 2095, 2104, 2174, 2277, 2278,
2279, 2280, 2315, 2318, [2398](#), 5556,
5563, 8902, 9222, 9376, 13532, 13539
- \exp_args:Nnc 30, [2504](#)
- \exp_args:NNcf 31, [2521](#)
- \exp_args:NNf 30, [1573](#), [2426](#),
5549, 9221, 9375, 9534, 15677, 15678
- \exp_args:Nnf 30, [2504](#), 11257
- \exp_args:Nnff 31, [2521](#)
- \exp_args:Nnnc 31, [2521](#)
- \exp_args:Nnnf 31, [2521](#)
- \exp_args:NNNo
. 30, [2409](#), 3050, 20305, 23319, 23344
- \exp_args:NNno 31, [2521](#)
- \exp_args:NNno 31, [2521](#), 7850
- \exp_args:NNNV 30, [2475](#), 8996
- \exp_args:NNnV 31, [2521](#)
- \exp_args:NNNx 31, [2521](#)
- \exp_args:NNnx 31, [2521](#)
- \exp_args:NNnx 31, [2521](#)
- \exp_args:NNNo 25, 30, [2409](#), 5583, 7856
- \exp_args:Nno
..... 30, [2504](#), 3064, 6880, 7737,
9981, 11671, 11679, 11688, 11705,
11713, 11741, 12262, 12266, 23323
- \exp_args:NNoo 31, [2521](#)
- \exp_args:NNox 31, [2521](#)
- \exp_args:NNox 31, [2521](#)
- \exp_args:NNV 30, [2426](#)
- \exp_args:NNv 30, [2426](#)
- \exp_args:NnV 30, [2504](#)
- \exp_args:Nnv 30, [2504](#)
- \exp_args:NNVV 31, [2521](#)
- \exp_args:NNx 30, 2323, [2504](#), 9159, 9172
- \exp_args:Nnx 30, [2504](#)
- \exp_args:No ... 27, 29, 767, 1463,
1471, 2307, 2312, [2409](#), 3044, 3049,
3284, 3285, 3286, 3318, 3319, 3320,
3321, 3374, 3392, 3401, 3459, 3461,
3569, 3571, 3597, 3606, 3741, 4028,
4054, 4059, 4073, 4131, 4142, 4190,
4201, 4269, 4288, 4326, 4341, 4666,
5583, 5670, 5676, 6577, 6755, 6766,
6768, 6803, 6808, 7005, 7009, 8420,
9123, 9325, 9437, 9467, 9541, 10241,
10862, 10880, 10908, 10930, 16989,
17284, 17636, 17693, 17695, 18404,
18454, 18475, 19080, 19095, 19447,
19847, 19982, 20017, 20055, 20451,
20480, 20954, 22957, 23313, 24297,
24299, 24302, 24305, 24382, 24391
- \exp_args:Noc 30, [2504](#)
- \exp_args:Nof 30, [2504](#)
- \exp_args:Noo . 30, [2504](#), 18497, 19460
- \exp_args:Noof 31, [2521](#)
- \exp_args:Nooo 31, [2521](#)
- \exp_args:Noox 31, [2521](#)
- \exp_args:Nox 30, [2504](#)
- \exp_args:NV
29, 2414, 9031, 9682, 9747, 10860,
10878, 10906, 10928, 17906, 24663
- \exp_args:Nv 29, [2414](#)
- \exp_args:NVo 30, [2504](#)
- \exp_args:NVV 30, [2426](#), 9594
- \exp_args:Nx 30,
2120, [2503](#), 3750, 6076, 6298, 7282,
8201, 9472, 10864, 10882, 10910,
10932, 16811, 18630, 18631, 18988
- \exp_args:Nxo 30, [2504](#)
- \exp_args:Nxx 30, [2504](#)
- \exp_end: 34, 35, 302,
304, 307, 322, 323, 330, 357, 357,
363, 376, 443, 510, 610, 638, 951,
1353, 1820, 1831, 1837, 1843, 2387,
2396, [2625](#), 3365, 3530, 3716, 3717,
4189, 6473, 6476, 6477, 6478, 6479,
6480, 6481, 6482, 6483, 6484, 6485,
7182, 7215, 7230, 7233, 7238, 7241,
7300, 7304, 8890, 11990, 12886,
15174, 16110, 16693, 23387, 24343
- \exp_end_continue_f:nw 35, [2625](#)
- \exp_end_continue_f:w 35, 35, 322,
612, 613, 2357, 2415, 2442, 2466,
2561, 2574, 2614, [2625](#), 6321, 7666,
8834, 9616, 9978, 11426, 11627,
12099, 12117, 12138, 12209, 12214,
12223, 12239, 12296, 12331, 12339,
12370, 12743, 12768, 12809, 12816,
12853, 12895, 12898, 12908, 12909,
13236, 13238, 13242, 13244, 13346,
13360, 13370, 13479, 13480, 13481,
13628, 13639, 13663, 13671, 14623,
15332, 15505, 15711, 16378, 16382,
16419, 16423, 16465, 16484, 16488,
16524, 16528, 16596, 16726, 23257
- \exp_last_two_unbraced:Nnn
..... 32, [2607](#), 21779, 22003, 22007
- \exp_last_unbraced:Nn 31, 32, [2568](#),
3121, 5682, 5702, 6538, 7020, 7307,
7833, 13733, 16988, 18066, 19204,
22132, 22137, 22215, 22221, 24708
- \exp_last_unbraced:NNn
..... 31, [2568](#), 3537, 6830,
6863, 8049, 9469, 21977, 23420, 23479
- \exp_last_unbraced:NNn
..... 31, [2568](#), 7914, 8004, 23055

- `\exp_last_unbraced:NNNn` [31](#), [2568](#)
`\exp_last_unbraced:NnNn` [31](#), [2568](#)
`\exp_last_unbraced:NNNNn`
. [31](#), [2568](#), [2658](#), [2662](#)
`\exp_not:N` [32](#), [32](#), [152](#), [199](#), [323](#),
[329](#), [342](#), [344](#), [360](#), [361](#), [471](#), [477](#),
[618](#), [767](#), [780](#), [789](#), [860](#), [863](#), [951](#),
[1349](#), [1682](#), [1686](#), [1787](#), [1853](#), [1856](#),
[1922](#), [1923](#), [1924](#), [1925](#), [1926](#), [1930](#),
[1931](#), [2180](#), [2181](#), [2240](#), [2241](#), [2344](#),
[2380](#), [2611](#), [2611](#), [2645](#), [2646](#), [2647](#),
[2648](#), [2649](#), [2650](#), [2651](#), [2652](#), [2654](#),
[2655](#), [2656](#), [2682](#), [2691](#), [2743](#), [2744](#),
[2745](#), [2746](#), [2818](#), [2824](#), [2825](#), [2826](#),
[2828](#), [2831](#), [2834](#), [2835](#), [2840](#), [2841](#),
[2842](#), [2850](#), [3044](#), [3106](#), [3177](#), [3303](#),
[3306](#), [3308](#), [3312](#), [3313](#), [3315](#), [3610](#),
[3613](#), [3629](#), [3632](#), [3663](#), [3670](#), [3813](#),
[4046](#), [4047](#), [4384](#), [4665](#), [4667](#), [5003](#),
[5568](#), [5831](#), [6915](#), [6918](#), [6926](#), [6927](#),
[7162](#), [7247](#), [7251](#), [7285](#), [7335](#), [7339](#),
[7344](#), [7349](#), [7354](#), [7361](#), [7368](#), [7373](#),
[7378](#), [7383](#), [7388](#), [7393](#), [7403](#), [7408](#),
[7413](#), [7416](#), [7417](#), [7418](#), [7420](#), [7421](#),
[7432](#), [7437](#), [7452](#), [7453](#), [7470](#), [7475](#),
[7476](#), [7477](#), [7478](#), [7479](#), [7480](#), [7482](#),
[7484](#), [7485](#), [7486](#), [7487](#), [7492](#), [7493](#),
[7514](#), [7517](#), [7518](#), [7520](#), [7521](#), [7522](#),
[7525](#), [7526](#), [7528](#), [7529](#), [7531](#), [7532](#),
[7534](#), [7597](#), [7603](#), [7634](#), [7637](#), [7644](#),
[7645](#), [7654](#), [7655](#), [7684](#), [7846](#), [7957](#),
[7980](#), [8308](#), [8310](#), [8312](#), [8314](#), [8319](#),
[8320](#), [8325](#), [8327](#), [8329](#), [8587](#), [8589](#),
[8591](#), [8593](#), [8598](#), [8599](#), [8604](#), [8606](#),
[8608](#), [10109](#), [10478](#), [10485](#), [10631](#),
[10632](#), [10640](#), [10642](#), [10656](#), [10658](#),
[10710](#), [10711](#), [10833](#), [10834](#), [12143](#),
[12144](#), [12145](#), [12149](#), [12150](#), [12175](#),
[12176](#), [12256](#), [12257](#), [12258](#), [12259](#),
[12260](#), [12341](#), [12381](#), [12385](#), [12407](#),
[12500](#), [12532](#), [12617](#), [12631](#), [12648](#),
[12658](#), [12668](#), [12705](#), [12708](#), [12786](#),
[12787](#), [12789](#), [12790](#), [12791](#), [12792](#),
[12793](#), [12794](#), [12797](#), [12800](#), [12918](#),
[12920](#), [12948](#), [12949](#), [12951](#), [12952](#),
[12953](#), [12954](#), [12955](#), [12956](#), [12957](#),
[12958](#), [12959](#), [12960](#), [12961](#), [13089](#),
[13104](#), [13544](#), [13686](#), [15564](#), [15565](#),
[15566](#), [15570](#), [15571](#), [15572](#), [16590](#),
[16591](#), [16593](#), [16594](#), [16595](#), [16596](#),
[16597](#), [16599](#), [16944](#), [16951](#), [16958](#),
[17387](#), [17390](#), [17541](#), [17542](#), [17543](#),
[17544](#), [17545](#), [17546](#), [17547](#), [17548](#),
[17549](#), [17550](#), [17551](#), [17552](#), [17555](#),
[17556](#), [17557](#), [18039](#), [18041](#), [18043](#),
[18045](#), [18047](#), [18049](#), [18392](#), [18394](#),
[18581](#), [18583](#), [18594](#), [18598](#), [18757](#),
[19173](#), [19841](#), [20145](#), [20156](#), [20391](#),
[20514](#), [22426](#), [22429](#), [22882](#), [23018](#),
[23020](#), [23024](#), [23026](#), [23031](#), [23033](#),
[23127](#), [23314](#), [23340](#), [24019](#), [24021](#),
[24062](#), [24064](#), [24075](#), [24077](#), [24435](#),
[24436](#), [24744](#), [24746](#), [24748](#), [24769](#)
`\exp_not:n` [32](#),
[33](#), [33](#), [33](#), [33](#), [33](#), [46](#), [47](#), [47](#), [49](#),
[50](#), [66](#), [70](#), [71](#), [110](#), [111](#), [112](#), [131](#),
[152](#), [240](#), [244](#), [245](#), [247](#), [249](#), [251](#),
[251](#), [252](#), [299](#), [329](#), [340](#), [342](#), [347](#),
[356](#), [392](#), [446](#), [449](#), [452](#), [486](#), [773](#),
[780](#), [785](#), [789](#), [797](#), [802](#), [860](#), [864](#),
[865](#), [868](#), [974](#), [1349](#), [1685](#), [1788](#),
[1790](#), [1858](#), [2122](#), [2344](#), [2565](#), [2611](#),
[2750](#), [2765](#), [2779](#), [2866](#), [2914](#), [2922](#),
[2940](#), [2943](#), [2949](#), [2952](#), [2964](#), [2967](#),
[2970](#), [2973](#), [2976](#), [2979](#), [2982](#), [2985](#),
[2996](#), [2999](#), [3002](#), [3005](#), [3008](#), [3011](#),
[3014](#), [3017](#), [3066](#), [3108](#), [3115](#), [3174](#),
[3178](#), [3179](#), [3180](#), [3454](#), [3456](#), [3738](#),
[3750](#), [3849](#), [3917](#), [4066](#), [4490](#), [4687](#),
[4688](#), [4695](#), [4696](#), [4712](#), [4744](#), [4764](#),
[4767](#), [4770](#), [4838](#), [4891](#), [4946](#), [5004](#),
[5044](#), [5054](#), [5569](#), [6547](#), [6548](#), [6563](#),
[6565](#), [6596](#), [6662](#), [6755](#), [6762](#), [6782](#),
[6919](#), [6925](#), [6953](#), [6958](#), [6989](#), [7022](#),
[7286](#), [7489](#), [7598](#), [7604](#), [7683](#), [7685](#),
[7847](#), [7921](#), [7958](#), [7961](#), [7962](#), [7981](#),
[7985](#), [8302](#), [8319](#), [8451](#), [8581](#), [8598](#),
[9010](#), [9295](#), [9347](#), [9431](#), [9448](#), [10419](#),
[10421](#), [10443](#), [10445](#), [10478](#), [10486](#),
[10487](#), [10511](#), [10677](#), [10713](#), [10737](#),
[10835](#), [10980](#), [11005](#), [11206](#), [11208](#),
[12251](#), [13545](#), [13687](#), [15744](#), [16772](#),
[16774](#), [16776](#), [17100](#), [17415](#), [17528](#),
[17554](#), [18392](#), [18394](#), [18991](#), [19377](#),
[19602](#), [19830](#), [19842](#), [19897](#), [20082](#),
[20084](#), [20091](#), [20145](#), [20153](#), [20167](#),
[20182](#), [20219](#), [20406](#), [20411](#), [22486](#),
[23069](#), [23082](#), [24471](#), [24474](#), [24476](#)
`\exp_stop_f:`
. [33](#), [35](#), [322](#), [359](#), [392](#), [582](#), [651](#),
[773](#), [780](#), [2354](#), [3908](#), [3918](#), [3931](#),
[3937](#), [4174](#), [4187](#), [4228](#), [4229](#), [4235](#),
[4247](#), [4263](#), [4490](#), [4513](#), [4524](#), [4532](#),
[4544](#), [4699](#), [5129](#), [5144](#), [5157](#), [5374](#),
[5379](#), [7186](#), [7189](#), [7190](#), [7197](#), [7198](#),
[7199](#), [7200](#), [7205](#), [7206](#), [7226](#), [7307](#),
[7424](#), [8902](#), [9222](#), [9376](#), [9604](#), [9618](#),
[9987](#), [10218](#), [11338](#), [11559](#), [11574](#),

- 11599, 11867, 11871, 11875, 11877,
 11881, 11885, 11893, 11898, 11911,
 11918, 11931, 11942, 11943, 11954,
 11955, 11964, 11967, 11977, 12012,
 12068, 12073, 12157, 12187, 12305,
 12347, 12398, 12418, 12445, 12459,
 12494, 12521, 12530, 12549, 12565,
 12581, 12599, 12659, 12678, 12694,
 12709, 12723, 12921, 12932, 13217,
 13221, 13391, 13397, 13399, 13402,
 13410, 13411, 13583, 13648, 13653,
 13696, 13702, 13717, 13754, 13827,
 13849, 13903, 13904, 13912, 14245,
 14263, 14316, 14320, 14324, 14342,
 14377, 14378, 14379, 14380, 14381,
 14407, 14419, 14436, 14676, 14677,
 14774, 14866, 14899, 14912, 14917,
 14926, 14928, 15054, 15083, 15088,
 15118, 15155, 15195, 15214, 15326,
 15372, 15373, 15378, 15384, 15402,
 15425, 15457, 15460, 15503, 15523,
 15529, 15544, 15585, 15600, 15615,
 15630, 15645, 15660, 15688, 15732,
 15958, 16121, 16123, 16160, 16171,
 16203, 16244, 16253, 16268, 16287,
 16320, 16333, 16383, 16424, 16472,
 16475, 16489, 16702, 16706, 16713,
 16861, 17119, 17260, 17355, 17362,
 17363, 17397, 17467, 17474, 17497,
 17500, 17504, 17521, 17568, 17587,
 17593, 17658, 17661, 17843, 17844,
 17845, 17850, 18131, 18151, 18152,
 18156, 18160, 18161, 18164, 18165,
 18173, 18174, 18177, 18181, 18182,
 18185, 18232, 18323, 18554, 18559,
 18587, 18657, 18658, 18697, 18788,
 19101, 19382, 19400, 19429, 19439,
 19494, 19507, 19518, 19534, 19585,
 19777, 19907, 19911, 19963, 20014,
 20026, 20042, 20047, 20053, 20096,
 20149, 20163, 20186, 20404, 20409,
 20430, 20504, 20516, 20521, 23568,
 23580, 23832, 23847, 23902, 24330,
 24339, 24352, 24360, 24408, 24409,
 24415, 24435, 24436, 24437, 24438
- exp internal commands:
- __exp_arg_last_unbraced:nn .. 2545
 - __exp_arg_next:Nnn 2344, 2351
 - __exp_arg_next:nnn
 .. 2344, 2353, 2356, 2364, 2368, 2374
 - __exp_eval_error_msg:w 2378
 - __exp_eval_register:N
 2369, 2375, 2378,
 2419, 2424, 2430, 2436, 2454, 2460,
 2472, 2473, 2480, 2551, 2556, 2570,
 2572, 2581, 2589, 2598, 2618, 2623
 - \l__exp_internal_tl
 35, 293, 1416, 1420,
 1421, 2344, 2363, 2364, 2565, 2566
 - __exp_last_two_unbraced:nnN . 2607
 - \expandafter 13,
 14, 21, 38, 39, 42, 43, 48, 49, 66, 67,
 90, 92, 98, 123, 146, 154, 169, 185, 365
 - \expanded 882
 - \expandglyphsinfont 957
 - \ExplFileDate 6
 - \ExplFileDescription 6
 - \ExplFileName 6
 - \ExplFileVersion 6
 - \explicitthyphenpenalty 881
 - \ExplSyntaxOff
 ... 3, 6, 6, 7, 207, 240, 254, 266, 267
 - \ExplSyntaxOn
 ... 3, 6, 6, 7, 236, 266, 267, 343, 462
- F**
- false 199
- \fam 366
- \fi 17, 35, 41,
 51, 70, 71, 72, 95, 96, 97, 100, 101,
 130, 139, 152, 153, 170, 186, 204, 367
- fi commands:
- \fi: 21, 86, 86, 86, 97, 103, 103, 153,
 168, 227, 227, 228, 302, 307, 309,
 347, 349, 376, 377, 380, 409, 418,
 444, 591, 600, 616, 631, 656, 716,
 780, 1331, 1376, 1457, 1567, 1584,
 1595, 1596, 1644, 1665, 1784, 1797,
 1817, 1867, 1872, 1879, 1914, 1919,
 1949, 1950, 1958, 1964, 1977, 1978,
 1986, 1992, 2114, 2135, 2145, 2157,
 2210, 2271, 2335, 2383, 2386, 2393,
 2394, 2656, 2672, 2679, 2688, 2702,
 2703, 2708, 2709, 2710, 2727, 2728,
 2729, 2730, 2731, 2732, 2733, 2734,
 2742, 2762, 2764, 2794, 2795, 2796,
 2904, 3190, 3191, 3227, 3240, 3253,
 3263, 3280, 3292, 3296, 3329, 3524,
 3577, 3582, 3591, 3593, 3620, 3643,
 3659, 3668, 3677, 3683, 3690, 3695,
 3706, 3710, 3718, 3912, 3919, 3932,
 3937, 4035, 4102, 4106, 4107, 4125,
 4179, 4189, 4233, 4239, 4240, 4251,
 4263, 4264, 4285, 4323, 4349, 4474,
 4480, 4492, 4493, 4518, 4530, 4534,
 4535, 4547, 4561, 4740, 4743, 4780,
 4796, 4817, 4827, 4878, 4883, 5132,
 5165, 5187, 5188, 5190, 5245, 5254,

5332, 5340, 5367, 5375, 5381, 5410,
5449, 5459, 5750, 5783, 5831, 5836,
5973, 6065, 6090, 6104, 6114, 6142,
6150, 6174, 6189, 6197, 6279, 6314,
6329, 6351, 6487, 6489, 6491, 6493,
6495, 6497, 6639, 6654, 6677, 6693,
7194, 7197, 7198, 7199, 7200, 7205,
7206, 7211, 7212, 7213, 7214, 7251,
7309, 7311, 7340, 7345, 7350, 7355,
7362, 7369, 7374, 7379, 7384, 7389,
7394, 7399, 7404, 7409, 7428, 7433,
7444, 7445, 7492, 7493, 7544, 7553,
7562, 7570, 7626, 7640, 7649, 7659,
7669, 8021, 8057, 8794, 8796, 9282,
9556, 9597, 9606, 9627, 9636, 9640,
9647, 9655, 9921, 9954, 9969, 9986,
9990, 10004, 10222, 10424, 10448,
10462, 10472, 10492, 10493, 10502,
11390, 11399, 11403, 11415, 11425,
11483, 11486, 11487, 11492, 11506,
11544, 11545, 11546, 11547, 11548,
11549, 11550, 11551, 11552, 11553,
11554, 11555, 11568, 11570, 11581,
11584, 11598, 11603, 11607, 11746,
11828, 11829, 11830, 11873, 11874,
11883, 11884, 11895, 11896, 11897,
11908, 11909, 11910, 11917, 11928,
11929, 11930, 11940, 11941, 11945,
11946, 11954, 11957, 11958, 11966,
11976, 11989, 12012, 12056, 12075,
12076, 12085, 12091, 12111, 12112,
12140, 12161, 12178, 12185, 12193,
12194, 12240, 12241, 12242, 12304,
12320, 12345, 12346, 12353, 12361,
12390, 12391, 12394, 12396, 12397,
12402, 12412, 12415, 12417, 12422,
12453, 12466, 12471, 12477, 12480,
12481, 12515, 12516, 12543, 12544,
12557, 12560, 12571, 12594, 12613,
12623, 12639, 12653, 12659, 12663,
12668, 12674, 12689, 12700, 12719,
12729, 12731, 12737, 12758, 12781,
12810, 12927, 12931, 12941, 12942,
12961, 12979, 12994, 12998, 13006,
13020, 13041, 13072, 13082, 13096,
13112, 13132, 13173, 13184, 13197,
13199, 13219, 13220, 13227, 13245,
13354, 13365, 13377, 13378, 13379,
13386, 13388, 13389, 13395, 13396,
13399, 13405, 13406, 13414, 13415,
13417, 13418, 13564, 13577, 13587,
13588, 13593, 13594, 13595, 13596,
13597, 13598, 13605, 13614, 13619,
13643, 13646, 13648, 13655, 13700,
13701, 13708, 13721, 13736, 13746,
13760, 13790, 13799, 13833, 13855,
13873, 13890, 13907, 13908, 13910,
13911, 13916, 13931, 13964, 13993,
13994, 13995, 13996, 13997, 14010,
14052, 14125, 14190, 14192, 14193,
14203, 14232, 14235, 14236, 14247,
14267, 14330, 14331, 14332, 14344,
14383, 14384, 14385, 14386, 14392,
14395, 14397, 14407, 14424, 14436,
14652, 14656, 14658, 14662, 14669,
14670, 14680, 14681, 14684, 14776,
14845, 14856, 14868, 14898, 14905,
14916, 14932, 14939, 15000, 15056,
15066, 15068, 15078, 15096, 15097,
15129, 15132, 15141, 15143, 15145,
15159, 15173, 15197, 15217, 15218,
15231, 15247, 15263, 15279, 15295,
15311, 15325, 15333, 15339, 15350,
15353, 15356, 15365, 15375, 15377,
15383, 15390, 15393, 15402, 15410,
15431, 15464, 15465, 15492, 15494,
15508, 15509, 15528, 15539, 15548,
15551, 15595, 15610, 15625, 15640,
15655, 15670, 15673, 15675, 15692,
15737, 15964, 16000, 16001, 16011,
16052, 16053, 16077, 16109, 16115,
16116, 16119, 16121, 16122, 16127,
16139, 16158, 16163, 16170, 16173,
16205, 16215, 16216, 16226, 16248,
16263, 16281, 16289, 16292, 16320,
16328, 16344, 16382, 16400, 16423,
16441, 16474, 16488, 16494, 16550,
16551, 16651, 16652, 16668, 16692,
16703, 16704, 16720, 16863, 16875,
16876, 16932, 17002, 17011, 17022,
17031, 17040, 17075, 17085, 17095,
17203, 17205, 17259, 17295, 17304,
17332, 17336, 17340, 17365, 17376,
17394, 17395, 17396, 17403, 17419,
17425, 17428, 17436, 17446, 17461,
17469, 17476, 17487, 17503, 17523,
17536, 17554, 17572, 17580, 17582,
17585, 17592, 17597, 17667, 17668,
17802, 17809, 17810, 17816, 17819,
17822, 17829, 17830, 17833, 17837,
17838, 17847, 17848, 17852, 17853,
17865, 17873, 17882, 17883, 17909,
18033, 18035, 18059, 18063, 18079,
18090, 18123, 18127, 18145, 18147,
18154, 18157, 18158, 18162, 18166,
18167, 18168, 18169, 18178, 18179,
18183, 18186, 18187, 18188, 18236,
18239, 18247, 18258, 18259, 18270,

- 18271, 18279, 18291, 18292, 18301,
18302, 18312, 18331, 18332, 18337,
18338, 18386, 18395, 18419, 18430,
18432, 18496, 18544, 18547, 18548,
18563, 18566, 18589, 18655, 18656,
18661, 18688, 18689, 18700, 18704,
18732, 18737, 18745, 18779, 18784,
18789, 18797, 18827, 18884, 18913,
18952, 18959, 18970, 19040, 19057,
19061, 19075, 19105, 19319, 19370,
19386, 19410, 19434, 19443, 19503,
19510, 19530, 19548, 19559, 19561,
19591, 19594, 19619, 19709, 19734,
19758, 19759, 19780, 19811, 19837,
19910, 19956, 19968, 20019, 20029,
20030, 20050, 20061, 20085, 20101,
20151, 20153, 20165, 20167, 20188,
20286, 20344, 20361, 20362, 20406,
20407, 20411, 20412, 20434, 20439,
20472, 20510, 20518, 20519, 20523,
20524, 20914, 20916, 20926, 22490,
23063, 23191, 23199, 23207, 23971,
23972, 23975, 24332, 24344, 24355,
24363, 24413, 24419, 24420, 24435,
24436, 24437, 24447, 24454, 24456
- file commands:
- \file_add_path:nN [9814](#)
 - \g_file_curr_dir_str
..... [145](#), [8930](#), [9092](#), [9098](#), [9109](#)
 - \g_file_curr_ext_str
..... [145](#), [8930](#), [9094](#), [9100](#), [9111](#)
 - \g_file_curr_name_str
..... [145](#), [8151](#), [8930](#), [8972](#),
[9093](#), [9099](#), [9110](#), [9787](#), [9793](#), [9796](#)
 - \g_file_current_name_tl ... [537](#), [9786](#)
 - \file_get_full_name:nN . [146](#), [154](#),
[938](#), [9014](#), [9055](#), [9068](#), [9209](#), [9814](#),
[9817](#), [22843](#), [22854](#), [22868](#), [22894](#),
[22900](#), [22909](#), [22917](#), [23308](#), [23335](#)
 - \file_get_md5five_hash:nN . [241](#), [22835](#)
 - \file_get_size:nN [241](#), [22835](#)
 - \file_get_timestamp:nN ... [241](#), [22835](#)
 - \file_if_exist:nTF
... [145](#), [146](#), [146](#), [9053](#), [22906](#), [22914](#)
 - \file_if_exist_input:n ... [242](#), [22892](#)
 - \file_if_exist_input:nTF
..... [242](#), [22892](#), [22905](#)
 - \file_input:n
[146](#), [146](#), [242](#), [242](#), [9066](#), [22906](#), [22914](#)
 - \file_input_stop: [242](#), [22921](#)
 - \file_list: [9823](#)
 - \file_log_list:
..... [146](#), [538](#), [9151](#), [9823](#), [9824](#)
 - \file_parse_full_name:nNN
..... [146](#), [9031](#), [9096](#), [9113](#)
 - \file_path_include:n
..... [241](#), [241](#), [241](#), [242](#), [9799](#)
 - \file_path_remove:n [9799](#)
 - \l_file_search_path_seq
..... [145](#), [145](#), [8981](#),
[9018](#), [9800](#), [9804](#), [9805](#), [9808](#), [9812](#)
 - \file_show_list: [146](#), [9151](#)
- file internal commands:
- \l__file_base_name_str
..... [153](#), [8976](#), [9016](#),
[9048](#), [9062](#), [9064](#), [9380](#), [9383](#), [9391](#)
 - \l__file_dir_str [8978](#), [9032](#), [9097](#), [9098](#)
 - \l__file_ext_str
..... [8978](#), [9032](#), [9033](#), [9097](#), [9100](#)
 - \l__file_full_name_str
..... [153](#), [8976](#), [9027](#), [9029](#),
[9031](#), [9036](#), [9038](#), [9041](#), [9049](#), [9050](#),
[9055](#), [9056](#), [9068](#), [9069](#), [9071](#), [9209](#),
[9210](#), [9213](#), [9803](#), [9804](#), [9805](#), [9811](#),
[9812](#), [22843](#), [22847](#), [22854](#), [22860](#),
[22868](#), [22872](#), [22894](#), [22895](#), [22896](#),
[22900](#), [22901](#), [22903](#), [22909](#), [22910](#),
[22911](#), [22917](#), [22918](#), [22919](#), [23308](#),
[23309](#), [23318](#), [23335](#), [23336](#), [23343](#)
 - __file_get_details:nN [22835](#)
 - __file_get_full_name_search:nN [9014](#)
 - __file_input:n
... [9066](#), [22896](#), [22903](#), [22911](#), [22919](#)
 - __file_input_pop: [9066](#)
 - __file_input_pop:nnn [9066](#)
 - __file_input_push:n [9066](#)
 - \g_file_internal_ior
[153](#), [9035](#), [9037](#), [9042](#), [9050](#), [9051](#), [9330](#)
 - __file_list:N [9151](#)
 - __file_list_aux:n [9151](#)
 - __file_missing:n
... [153](#), [9060](#), [9070](#), [9205](#), [23310](#), [23337](#)
 - __file_name_quote:nN [153](#), [8985](#), [9047](#)
 - __file_name_quote_aux:n . [9003](#), [9012](#)
 - __file_name_sanitize:nN ... [153](#),
[153](#), [8985](#), [9016](#), [9062](#), [9380](#), [9803](#), [9811](#)
 - __file_name_sanitize_aux:n .. [8985](#)
 - \l__file_name_str
..... [8978](#), [9032](#), [9097](#), [9099](#)
 - __file_parse_full_name_auxi:w [9113](#)
 - __file_parse_full_name_split:nNNNTF
..... [9113](#)
 - \g_file_record_seq [516](#),
[518](#), [518](#), [8967](#), [9076](#), [9081](#), [9163](#), [9174](#)
 - \g_file_stack_seq
..... [516](#), [8944](#), [9090](#), [9104](#)

- _file_tmp:w 8947, 8951, 8954, 8960, 8964, 9132, 9147, 9149
- \l_file_tmp_seq 8982, 9155, 9159, 9163, 9164, 9166, 9172, 9174
- \l_file_tmp_tl . 8975, 8990, 8991, 8993, 8994, 8995, 8997, 9104, 9105
- \finalhyphendemerits 368
- \firstmark 369
- \firstmarks 626
- \firstvalidlanguage 883
- flag commands:
 - \flag_clear:n 89, 89, 6054, 6069, 18982, 20368, 20369
 - \flag_clear_new:n 89, 6068
 - \flag_height:n 90, 6077, 6106, 6121, 20380, 20385, 20386
 - \flag_if_exist:n 90
 - \flag_if_exist:nTF 90, 6069, 6084, 6092
 - \flag_if_exist_p:n 90, 6092
 - \flag_if_raised:n 90
 - \flag_if_raised:nTF . 90, 6097, 18990
 - \flag_if_raised_p:n 90, 6097
 - \flag_log:n 89, 6070
 - \flag_new:n 89, 89, 428, 6049, 6069, 11642, 11643, 11644, 11645, 18972, 20272, 20273
 - \flag_raise:n 90, 6118, 11676, 11685, 11693, 11710, 11719, 11750, 19005, 19027, 20405, 20410
 - \flag_show:n 89, 6070
- flag fp commands:
 - flag_fp_division_by_zero . 191, 11642
 - flag_fp_invalid_operation 191, 11642
 - flag_fp_overflow 191, 11642
 - flag_fp_underflow 191, 11642
- flag internal commands:
 - _flag_chk_exist:n . 6080, 6097, 6106
 - _flag_clear:wn 6054
 - _flag_height_end:wn 6106
 - _flag_height_loop:wn 6106
 - _flag_show:Nn 6070
- \floatingpenalty 370
- floor 195
- \fmtname 145
- \font 371
- \fontchar dp 627
- \fontcharht 628
- \fontcharic 629
- \fontcharwd 630
- \fontdimen 372
- \fontid 884
- \fontname 373
- \forcecjktoken 1164
- \formatname 885
- fp commands:
 - \c_e_fp 190, 192, 16817
 - \fp_abs:n 194, 199, 754, 16570, 21319, 21396, 21398, 21400, 22790, 22792
 - \fp_add:Nn 185, 754, 16794
 - \fp_compare:nNnTF 187, 188, 188, 188, 13356, 13451, 13457, 13462, 13470, 13514, 13520, 16713, 16727, 16756, 21187, 21189, 21194, 21415, 21430, 21439, 21840, 22774, 24819, 25169, 25175, 25316
 - \fp_compare:nTF 187, 188, 188, 188, 189, 194, 13343, 13423, 13429, 13434, 13442
 - \fp_compare_p:n 187, 13343
 - \fp_compare_p:nNn 187, 13356
 - \fp_const:Nn 184, 16771, 16817, 16818, 16819, 16820
 - \fp_do_until:nn 188, 13420
 - \fp_do_until:nNnn 188, 13448
 - \fp_do_while:nn 188, 13420
 - \fp_do_while:nNnn 188, 13448
 - \fp_eval:n 185, 187, 193, 193, 194, 194, 194, 194, 194, 194, 195, 195, 195, 195, 195, 196, 196, 196, 196, 197, 197, 197, 198, 198, 199, 199, 761, 16567, 24821, 24832, 24833, 24998, 25020, 25021, 25032, 25033, 25045, 25046, 25058, 25060, 25065, 25076, 25088, 25099, 25100, 25180, 25195, 25197, 25318, 25329, 25330, 25577, 25595, 25596, 25597, 25598, 25610, 25611, 25619, 25620, 25627, 25634, 25636, 25642, 25643, 25644, 25655, 25660, 25666, 25667, 25758, 25773, 25774, 25972, 25990, 25991, 25992, 26007, 26025, 26026, 26027, 26076, 26077
 - \fp_format:nn 200
 - \fp_function:Nw 13250
 - \fp_gadd:Nn 185, 16794
 - .fp_gset:N 173, 10891
 - \fp_gset:Nn . 184, 16771, 16795, 16797
 - \fp_gset_eq:NN 185, 16780, 16785
 - \fp_gsub:Nn 185, 16794
 - \fp_gzero:N 184, 16784, 16791
 - \fp_gzero_new:N 184, 16788
 - \fp_if_exist:NnTF 186, 13341, 16789, 16791
 - \fp_if_exist_p:N 186, 13341
 - \fp_if_nan:nTF 200
 - \fp_log:N 191, 16804
 - \fp_log:n 191, 16813
 - \fp_max:nn 199, 16572

- \fp_min:nn [199](#), [16572](#)
- \fp_new:N [184](#), [184](#),
[16768](#), [16789](#), [16791](#), [16821](#), [16822](#),
[16823](#), [16824](#), [21159](#), [21160](#), [21161](#),
[21281](#), [21282](#), [21497](#), [21498](#), [22606](#),
[22607](#), [22751](#), [22752](#), [25188](#), [25189](#)
- \fp_new_function:Npn [13257](#)
- .fp_set:N [173](#), [10891](#)
- \fp_set:Nn [184](#), [16771](#), [16794](#),
[16796](#), [21175](#), [21176](#), [21177](#), [21288](#),
[21290](#), [21326](#), [21341](#), [21356](#), [21368](#),
[21370](#), [21383](#), [21384](#), [21413](#), [21414](#),
[21836](#), [21838](#), [22616](#), [22617](#), [22757](#),
[22759](#), [22784](#), [22785](#), [25168](#), [25171](#)
- \fp_set_eq:NN .. [185](#), [16780](#), [16784](#),
[21331](#), [21346](#), [21358](#), [21416](#), [21417](#)
- \fp_show:N [191](#), [16804](#)
- \fp_show:n [191](#), [16813](#)
- \fp_step_function:nnnN
..... [189](#), [13476](#), [13551](#)
- \fp_step_inline:nnnn [189](#), [13529](#)
- \fp_step_variable:nnnNn .. [189](#), [13529](#)
- \fp_sub:Nn [185](#), [16794](#)
- \fp_to_decimal:N [185](#),
[186](#), [11635](#), [16413](#), [16431](#), [16515](#), [16567](#)
- \fp_to_decimal:n
.. [185](#), [185](#), [185](#), [186](#), [752](#), [16413](#),
[16518](#), [16569](#), [16571](#), [16573](#), [16575](#)
- \fp_to_dim:N [185](#), [16514](#)
- \fp_to_dim:n [185](#), [190](#),
[16514](#), [21219](#), [21230](#), [21319](#), [21846](#),
[21872](#), [22688](#), [22696](#), [22800](#), [22802](#)
- \fp_to_int:N [186](#), [16519](#)
- \fp_to_int:n
[186](#), [758](#), [16519](#), [16728](#), [16729](#), [22952](#)
- \fp_to_int_dispatch:w [753](#)
- \fp_to_scientific:N
.... [186](#), [11636](#), [16372](#), [16390](#), [16397](#)
- \fp_to_scientific:n . [186](#), [186](#), [16372](#)
- \fp_to_tl:N [186](#), [16479](#), [16811](#)
- \fp_to_tl:n [186](#), [11352](#),
[11675](#), [11684](#), [11709](#), [11718](#), [11747](#),
[13506](#), [13517](#), [16479](#), [16814](#), [16816](#)
- \fp_trap:nn [191](#), [191](#),
[595](#), [11646](#), [11761](#), [11762](#), [11763](#), [11764](#)
- \fp_until_do:nn [188](#), [13420](#)
- \fp_until_do:nNnn [188](#), [13448](#)
- \fp_use:N
.... [186](#), [16567](#), [25174](#), [25178](#), [25183](#)
- \fp_while_do:nn [189](#), [13420](#)
- \fp_while_do:nNnn [188](#), [13448](#)
- \fp_zero:N [184](#), [184](#), [16784](#), [16789](#), [25170](#)
- \fp_zero_new:N [184](#), [16788](#)
- \c_inf_fp [190](#), [198](#), [11361](#),
[12818](#), [14007](#), [14087](#), [15125](#), [15148](#),
[15355](#), [15358](#), [15362](#), [15386](#), [15677](#)
- \c_nan_fp [198](#), [598](#), [622](#), [11361](#), [11686](#),
[11694](#), [11766](#), [12000](#), [12019](#), [12025](#),
[12209](#), [12214](#), [12223](#), [12331](#), [12370](#),
[12809](#), [12819](#), [13021](#), [13287](#), [13510](#),
[15329](#), [16108](#), [16615](#), [16677](#), [16691](#)
- \c_one_fp [190](#), [12822](#), [13202](#), [13223](#),
[13602](#), [14428](#), [15119](#), [15324](#), [15376](#),
[15601](#), [15631](#), [16102](#), [16686](#), [16817](#)
- \c_pi_fp .. [190](#), [198](#), [631](#), [12820](#), [16819](#)
- \g_tmpa_fp [190](#), [16821](#)
- \l_tmpa_fp [190](#), [16821](#)
- \g_tmpb_fp [190](#), [16821](#)
- \l_tmpb_fp [190](#), [16821](#)
- \c_zero_fp
[189](#), [660](#), [760](#), [11361](#), [11408](#), [12823](#),
[13214](#), [13226](#), [13604](#), [13836](#), [14003](#),
[15128](#), [15149](#), [15352](#), [15389](#), [16325](#),
[16397](#), [16542](#), [16769](#), [16784](#), [16785](#),
[21187](#), [21189](#), [21194](#), [21430](#), [21439](#),
[22774](#), [24819](#), [25169](#), [25175](#), [25316](#)
- fp internal commands:
- __fp_&o:ww [649](#), [657](#), [13607](#)
- __fp_*o:ww [13968](#)
- __fp_+o:ww [659](#), [659](#), [687](#), [13689](#)
- __fp_,o:ww [641](#), [12983](#)
- __fp_-o:ww [659](#), [659](#), [13684](#)
- __fp_/o:ww [668](#), [708](#), [14078](#)
- __fp^o:ww [15320](#)
- __fp_acos_o:w [745](#), [747](#), [16266](#)
- __fp_acot_o:Nw . [15576](#), [15578](#), [16088](#)
- __fp_acotii_o:Nww [16091](#), [16096](#), [16112](#)
- __fp_acotii_o:ww [741](#)
- __fp_acsc_normal_o:NwNnw
..... [747](#), [16324](#), [16339](#), [16347](#)
- __fp_acsc_o:w [16318](#)
- __fp_add:NNNn [16794](#)
- __fp_add_big_i:wNww [661](#)
- __fp_add_big_i_o:wNww
..... [659](#), [662](#), [13756](#), [13763](#)
- __fp_add_big_ii:wNww [661](#)
- __fp_add_big_ii_o:wNww [13759](#), [13763](#)
- __fp_add_inf_o:Nww ... [13705](#), [13725](#)
- __fp_add_normal_o:Nww
..... [661](#), [13704](#), [13740](#)
- __fp_add_npos_o:NwNnw
..... [661](#), [13743](#), [13749](#)
- __fp_add_return_ii_o:Nww
..... [13707](#), [13713](#), [13718](#)
- __fp_add_significand_carry_-
o:wwwNN [663](#), [13796](#), [13811](#)

__fp_add_significand_no_carry_-
 o:wwwNN [663](#), [13798](#), [13801](#)
 __fp_add_significand_o:NnnwnnnnN
 [662](#), [662](#), [13766](#), [13774](#), [13779](#)
 __fp_add_significand_pack:NNNNNN
 [13779](#)
 __fp_add_significand_test_o:N [13779](#)
 __fp_add_zeros_o:Nww . [13703](#), [13715](#)
 __fp_and_return:wNw [13607](#)
 __fp_array_count:n
 [11609](#), [11984](#), [16101](#), [16685](#)
 __fp_array_count_loop:Nw [11609](#)
 __fp_array_to_clist:n
 .. [12045](#), [13079](#), [13080](#), [16576](#), [16718](#)
 __fp_array_to_clist_loop:Nw . [16576](#)
 __fp_asec_o:w [16331](#)
 __fp_asin_auxi_o:NnNww
 [746](#), [748](#), [16296](#), [16299](#), [16358](#)
 __fp_asin_isqrt:wn [16299](#)
 __fp_asin_normal_o:NnwNnnnw ...
 [16257](#), [16273](#), [16284](#)
 __fp_asin_o:w [16251](#)
 __fp_atan_auxi:ww . [743](#), [16176](#), [16190](#)
 __fp_atan_auxii:w [16190](#)
 __fp_atan_combine_aux:ww [16217](#)
 __fp_atan_combine_o:NwwwwN ...
 [741](#), [742](#), [16136](#), [16153](#), [16217](#)
 __fp_atan_dispatch_o:NNnNw . [16088](#)
 __fp_atan_div:wNwnw
 [742](#), [16164](#), [16166](#)
 __fp_atan_inf_o:NNNw [741](#), [16124](#),
 [16125](#), [16126](#), [16134](#), [16269](#), [16342](#)
 __fp_atan_near:wwn [16166](#)
 __fp_atan_near_aux:wwn [16166](#)
 __fp_atan_normal_o:NNnwNnw
 [741](#), [16128](#), [16144](#)
 __fp_atan_o:Nw . [15580](#), [15582](#), [16088](#)
 __fp_atan_Taylor_break:w [16201](#)
 __fp_atan_Taylor_loop:www
 [743](#), [16196](#), [16201](#)
 __fp_atan_test_o:NwwNwn
 [746](#), [16147](#), [16151](#), [16306](#)
 __fp_atanii_o:Nww [16091](#), [16096](#), [16112](#)
 __fp_basics_pack_high:NNNNw ...
 .. [663](#), [679](#), [11477](#), [13804](#), [13956](#),
 [14057](#), [14069](#), [14209](#), [14402](#), [14873](#)
 __fp_basics_pack_high_carry:w ..
 [588](#), [11477](#)
 __fp_basics_pack_low:NNNNw ...
 [670](#), [679](#),
 [11477](#), [13806](#), [13958](#), [14059](#), [14071](#),
 [14211](#), [14351](#), [14353](#), [14404](#), [14875](#)
 __fp_basics_pack_weird_high:NNNNNNnw
 [201](#), [11488](#), [13815](#), [14220](#)
 __fp_basics_pack_weird_low:NNNNw
 [201](#), [11488](#), [13817](#), [14222](#)
 \c__fp_big_leading_shift_int ...
 .. [11463](#), [14281](#), [14563](#), [14573](#), [14583](#)
 \c__fp_big_middle_shift_int
 [11463](#), [14284](#), [14287](#), [14290](#),
 [14293](#), [14296](#), [14299](#), [14303](#), [14565](#),
 [14575](#), [14585](#), [14594](#), [14597](#), [14600](#)
 \c__fp_big_trailing_shift_int ...
 [11463](#), [14307](#), [14607](#)
 \c__fp_Bigg_leading_shift_int ...
 [11468](#), [14131](#), [14148](#)
 \c__fp_Bigg_middle_shift_int ...
 .. [11468](#), [14134](#), [14137](#), [14151](#), [14154](#)
 \c__fp_Bigg_trailing_shift_int ..
 [11468](#), [14140](#), [14157](#)
 \c__fp_block_int [11366](#), [14825](#)
 __fp_case_return:nw
 [11545](#), [11575](#), [11578](#), [11583](#), [12105](#),
 [15084](#), [16124](#), [16125](#), [16126](#), [16384](#),
 [16425](#), [16490](#), [16492](#), [16493](#), [16542](#)
 __fp_case_return_i_o:ww . [11552](#),
 [13706](#), [13720](#), [13729](#), [14001](#), [16115](#)
 __fp_case_return_ii_o:ww
 .. [11552](#), [14002](#), [15374](#), [15392](#), [16116](#)
 __fp_case_return_o:Nw
 [592](#), [11546](#), [15119](#), [15124](#),
 [15127](#), [15324](#), [15329](#), [15352](#), [15355](#),
 [15358](#), [15601](#), [15631](#), [16325](#), [16327](#)
 __fp_case_return_o:Nww
 [11550](#), [14003](#), [14004](#),
 [14007](#), [14008](#), [15376](#), [15385](#), [15388](#)
 __fp_case_return_same_o:w
 [592](#), [11548](#),
 [14232](#), [14236](#), [14420](#), [14423](#), [14904](#),
 [15131](#), [15349](#), [15586](#), [15594](#), [15609](#),
 [15624](#), [15639](#), [15646](#), [15654](#), [15669](#),
 [16254](#), [16262](#), [16280](#), [16326](#), [16343](#)
 __fp_case_use:nw
 [11544](#), [13731](#), [13999](#),
 [14000](#), [14005](#), [14006](#), [14086](#), [14089](#),
 [14234](#), [14897](#), [14900](#), [15360](#), [15587](#),
 [15592](#), [15602](#), [15607](#), [15617](#), [15622](#),
 [15632](#), [15637](#), [15647](#), [15652](#), [15662](#),
 [15667](#), [16256](#), [16259](#), [16269](#), [16271](#),
 [16277](#), [16321](#), [16323](#), [16334](#), [16337](#),
 [16342](#), [16387](#), [16394](#), [16428](#), [16435](#)
 __fp_chk:w [580](#), [581](#), [582](#),
 [631](#), [659](#), [661](#), [661](#), [663](#), [669](#), [672](#),
 [11348](#), [11361](#), [11362](#), [11363](#), [11364](#),
 [11365](#), [11375](#), [11380](#), [11382](#), [11383](#),
 [11404](#), [11407](#), [11409](#), [11419](#), [11432](#),
 [11451](#), [11556](#), [11572](#), [11742](#), [11747](#),
 [12002](#), [12048](#), [12057](#), [12059](#), [12832](#),

- 13348, 13373, 13374, 13493, 13506,
 13510, 13566, 13567, 13570, 13581,
 13582, 13590, 13591, 13599, 13610,
 13613, 13625, 13651, 13690, 13710,
 13711, 13713, 13714, 13715, 13723,
 13726, 13737, 13738, 13740, 13749,
 13825, 13977, 14011, 14012, 14015,
 14094, 14230, 14238, 14240, 14417,
 14425, 14427, 14429, 14433, 14894,
 14906, 14908, 15116, 15133, 15135,
 15321, 15340, 15342, 15343, 15346,
 15363, 15366, 15369, 15394, 15395,
 15397, 15413, 15498, 15511, 15513,
 15517, 15521, 15583, 15596, 15598,
 15611, 15613, 15626, 15628, 15641,
 15643, 15656, 15658, 15671, 15681,
 16113, 16129, 16130, 16134, 16145,
 16251, 16264, 16266, 16282, 16285,
 16295, 16318, 16329, 16331, 16345,
 16347, 16352, 16380, 16401, 16404,
 16421, 16442, 16445, 16486, 16502,
 16505, 16563, 16564, 16695, 16697
 __fp_compare:wNNNNw [13143](#)
 __fp_compare_aux:wn [13356](#)
 __fp_compare_back:ww
 [650](#), [651](#), [13217](#), [13369](#), [13372](#), [13580](#)
 __fp_compare_nan:w [651](#), [13372](#)
 __fp_compare_npos:nwnw [649](#),
 [651](#), [651](#), [13383](#), [13400](#), [13827](#), [14676](#)
 __fp_compare_return:w [13343](#)
 __fp_compare_significand:nnnnnnnn
 [13400](#)
 __fp_cos_o:w [15598](#)
 __fp_cot_o:w [727](#), [15658](#)
 __fp_cot_zero_o:Nnw
 [726](#), [728](#), [15616](#), [15658](#)
 __fp_csc_o:w [15613](#)
 __fp_decimate:nNnnnn
 [589](#), [592](#), [723](#), [11498](#),
 [11563](#), [11590](#), [12061](#), [13765](#), [13773](#),
 [13852](#), [15162](#), [15166](#), [15536](#), [16451](#)
 __fp_decimate:Nnnnn [11510](#)
 __fp_decimate_auxi:Nnnnn [590](#), [11514](#)
 __fp_decimate_auxii:Nnnnn ... [11514](#)
 __fp_decimate_auxiii:Nnnnn .. [11514](#)
 __fp_decimate_auxiv:Nnnnn ... [11514](#)
 __fp_decimate_auxix:Nnnnn ... [11514](#)
 __fp_decimate_auxv:Nnnnn [11514](#)
 __fp_decimate_auxvi:Nnnnn ... [11514](#)
 __fp_decimate_auxvii:Nnnnn .. [11514](#)
 __fp_decimate_auxviii:Nnnnn . [11514](#)
 __fp_decimate_auxx:Nnnnn [11514](#)
 __fp_decimate_auxxi:Nnnnn ... [11514](#)
 __fp_decimate_auxxii:Nnnnn .. [11514](#)
 __fp_decimate_auxxiii:Nnnnn . [11514](#)
 __fp_decimate_auxxiv:Nnnnn .. [11514](#)
 __fp_decimate_auxxv:Nnnnn ... [11514](#)
 __fp_decimate_auxxvi:Nnnnn .. [11514](#)
 __fp_decimate_pack:nnnnnnnnnw .
 [590](#), [11521](#), [11540](#)
 __fp_decimate_pack:nnnnnnnw
 [11541](#), [11542](#)
 __fp_decimate_tiny:Nnnnn [11510](#)
 __fp_div_npos_o:Nww
 [671](#), [672](#), [14083](#), [14093](#)
 __fp_div_significand_calc:wwnnnnnn
 [675](#),
 [675](#), [14110](#), [14119](#), [14165](#), [14977](#), [14984](#)
 __fp_div_significand_calc_-
 i:wwnnnnnn [14119](#)
 __fp_div_significand_calc_-
 ii:wwnnnnnn [14119](#)
 __fp_div_significand_i_o:wnnw ..
 [672](#), [675](#), [14100](#), [14106](#)
 __fp_div_significand_ii:wnw ...
 [677](#), [14114](#), [14115](#), [14116](#), [14161](#)
 __fp_div_significand_iii:wwnnnn
 [677](#), [14117](#), [14168](#)
 __fp_div_significand_iv:wwnnnnnn
 [678](#), [14171](#), [14176](#)
 __fp_div_significand_large_-
 o:wwNNNNwN [680](#), [14202](#), [14216](#)
 __fp_div_significand_pack:NNN ..
 [679](#),
 [710](#), [14163](#), [14196](#), [14964](#), [14982](#), [14990](#)
 __fp_div_significand_small_-
 o:wwNNNNwN [679](#), [14200](#), [14206](#)
 __fp_div_significand_test_o:w ..
 [679](#), [679](#), [14108](#), [14197](#)
 __fp_div_significand_v:NN
 [14181](#), [14183](#), [14186](#)
 __fp_div_significand_v:NNw .. [14176](#)
 __fp_div_significand_vi:Nw
 [678](#), [14176](#)
 __fp_division_by_zero_o:Nnw ...
 [595](#), [11706](#), [11754](#), [14901](#), [15677](#), [15678](#)
 __fp_division_by_zero_o:NNww ...
 [595](#), [11714](#), [11754](#), [14087](#), [14090](#), [15362](#)
 __fp_ep_compare:www . [14671](#), [16160](#)
 __fp_ep_compare_aux:www [14671](#)
 __fp_ep_div:wwwwn
 [738](#), [14701](#), [14812](#),
 [16078](#), [16175](#), [16179](#), [16188](#), [16355](#)
 __fp_ep_div_eps_pack:NNNNnw . [14731](#)
 __fp_ep_div_epsilon:wnNNNNn [700](#)
 __fp_ep_div_epsilon:wnNNNNnn
 [14728](#), [14731](#)
 __fp_ep_div_epsilonii:wnNNNNnn . [14731](#)

__fp_ep_div_esti:wwwn
 [699](#), [14707](#), [14710](#)
 __fp_ep_div_estii:wwnnwn ... [14710](#)
 __fp_ep_div_estiii:NNNNNwwwn . [14710](#)
 __fp_ep_inv_to_float_o:wN [728](#)
 __fp_ep_inv_to_float_o:wwN
 [736](#), [14808](#), [14816](#), [15620](#), [15635](#)
 __fp_ep_isqrt:wn [14754](#), [16316](#)
 __fp_ep_isqrt_aux:wn [14754](#)
 __fp_ep_isqrt_auxi:wn [14757](#), [14759](#)
 __fp_ep_isqrt_auxii:wwnnwn . [14754](#)
 __fp_ep_isqrt_epsilon:wn
 [702](#), [14791](#), [14794](#)
 __fp_ep_isqrt_epsilonii:wwN [14794](#)
 __fp_ep_isqrt_esti:wwnnwn
 [14769](#), [14772](#)
 __fp_ep_isqrt_estii:wwnnwn . [14772](#)
 __fp_ep_isqrt_estiii:NNNNNwwwn .
 [14772](#)
 __fp_ep_mul:wwwn
 .. [14686](#), [16035](#), [16065](#), [16303](#), [16314](#)
 __fp_ep_mul_raw:wwwn
 [14686](#), [15699](#), [15985](#)
 __fp_ep_to_ep:wwN . [14637](#), [14688](#),
 [14691](#), [14703](#), [14706](#), [14756](#), [16304](#)
 __fp_ep_to_ep_end:www [14637](#)
 __fp_ep_to_ep_loop:N
 [735](#), [14637](#), [15986](#)
 __fp_ep_to_ep_zero:ww [14637](#)
 __fp_ep_to_fixed:wn
 .. [14619](#), [15696](#), [16182](#), [16191](#), [16301](#)
 __fp_ep_to_fixed_auxi:www ... [14619](#)
 __fp_ep_to_fixed_auxii:nnnnnnwn
 [14619](#)
 __fp_ep_to_float_o:wN [728](#)
 __fp_ep_to_float_o:wwN [725](#),
 [736](#), [14808](#), [14820](#), [15590](#), [15605](#), [16084](#)
 __fp_error:nnnn
 [11675](#), [11683](#), [11692](#), [11709](#), [11717](#),
 [11745](#), [11768](#), [11850](#), [11995](#), [11997](#),
 [12018](#), [12023](#), [13078](#), [13505](#), [13516](#)
 __fp_exp_after_?_f:nw ... [618](#), [12197](#)
 __fp_exp_after_array_f:w
 [586](#), [11452](#),
 [12789](#), [13629](#), [13640](#), [13664](#), [13672](#)
 __fp_exp_after_f:nw
 [585](#), [618](#), [11409](#), [12831](#), [12913](#)
 __fp_exp_after_mark_f:nw [618](#), [12197](#)
 __fp_exp_after_normal:nnNw
 [11412](#), [11422](#), [11439](#)
 __fp_exp_after_normal:Nwwww ...
 [11441](#), [11449](#)
 __fp_exp_after_o:w .. [585](#), [11409](#),
 [11549](#), [11553](#), [11555](#), [12055](#), [12099](#),
 [12117](#), [12890](#), [13237](#), [13598](#), [13615](#),
 [13714](#), [14431](#), [15510](#), [15515](#), [16762](#)
 __fp_exp_after_special:nnNw ...
 [585](#), [11414](#), [11424](#), [11429](#)
 __fp_exp_after_stop_f:nw [11452](#)
 __fp_exp_large:w [15209](#)
 __fp_exp_large:wN [15209](#)
 __fp_exp_large_after:wn [15209](#)
 __fp_exp_large_i:wN [15209](#)
 __fp_exp_large_ii:wN [15209](#)
 __fp_exp_large_iii:wN [15209](#)
 __fp_exp_large_iv:wN [15209](#)
 __fp_exp_large_v:wN .. [15209](#), [15497](#)
 __fp_exp_normal_o:w .. [15121](#), [15135](#)
 __fp_exp_o:w [14882](#), [15116](#)
 __fp_exp_overflow:NN [15135](#)
 __fp_exp_pos_large:NnnNwn
 [15167](#), [15209](#)
 __fp_exp_pos_o:NNwnw
 [15138](#), [15140](#), [15143](#)
 __fp_exp_pos_o:Nnnw [15135](#)
 __fp_exp_Taylor:Nnnwn
 [15163](#), [15182](#), [15317](#)
 __fp_exp_Taylor_break:Nww ... [15182](#)
 __fp_exp_Taylor_ii:ww . [15188](#), [15191](#)
 __fp_exp_Taylor_loop:www [15182](#)
 __fp_expand:n [755](#), [11618](#), [16580](#)
 __fp_expand_loop:wnN [11618](#)
 __fp_exponent:w [11383](#)
 \c__fp_five_int [11865](#),
 [11889](#), [11902](#), [11915](#), [11922](#), [11974](#)
 __fp_fixed(calculation):wn .. [688](#)
 __fp_fixed_add:nnNnnwn [14513](#)
 __fp_fixed_add:Nnnnnwn [14513](#)
 __fp_fixed_add:wn
 .. [688](#), [691](#), [14513](#), [14752](#), [15058](#),
 [15066](#), [15077](#), [15095](#), [16187](#), [16247](#)
 __fp_fixed_add_after:NNNNNwn . [14513](#)
 __fp_fixed_add_one:wN
 [689](#), [14445](#), [14745](#), [15199](#), [15208](#), [16313](#)
 __fp_fixed_add_pack:NNNNNwn . [14513](#)
 __fp_fixed_continue:wn
 [14444](#), [14689](#), [14694](#), [14704](#), [15221](#),
 [15237](#), [15253](#), [15269](#), [15285](#), [15301](#),
 [15473](#), [15734](#), [16023](#), [16305](#), [16314](#)
 __fp_fixed_div_int:wnN [14482](#)
 __fp_fixed_div_int:wwN
 [690](#), [14482](#), [15057](#), [15198](#), [16206](#)
 __fp_fixed_div_int_after:Nw ...
 [690](#), [14482](#)
 __fp_fixed_div_int_auxi:wnn . [14482](#)
 __fp_fixed_div_int_auxii:wnn ...
 [690](#), [14482](#)

__fp_fixed_div_int_pack:Nw
 [690](#), [14482](#)
 __fp_fixed_div_myriad:wn
 [14450](#), [14749](#)
 __fp_fixed_inv_to_float_o:wN ...
 [14815](#), [15140](#), [15409](#)
 __fp_fixed_mul:nnnnnnnw [14533](#)
 __fp_fixed_mul:wnw
 .. [688](#), [689](#), [692](#), [735](#), [737](#), [14533](#),
 [14698](#), [14729](#), [14744](#), [14746](#), [14750](#),
 [14803](#), [14806](#), [14819](#), [15059](#), [15069](#),
 [15109](#), [15200](#), [15218](#), [15318](#), [15419](#),
 [15992](#), [16046](#), [16194](#), [16227](#), [16229](#)
 __fp_fixed_mul_add:nnnnwnnnn ...
 [695](#), [14601](#), [14603](#)
 __fp_fixed_mul_add:nnnnwnnwN ...
 [695](#), [14608](#), [14614](#)
 __fp_fixed_mul_add:Nwnnnwnnn ...
 [694](#), [14566](#), [14576](#), [14586](#), [14590](#)
 __fp_fixed_mul_add:wnwn . [693](#), [14560](#)
 __fp_fixed_mul_after:wnw
 [692](#), [14452](#), [14458](#), [14461](#),
 [14535](#), [14562](#), [14572](#), [14582](#), [15436](#)
 __fp_fixed_mul_one_minus_-
 mul:wnw [14560](#)
 __fp_fixed_mul_short:wnw
 [689](#), [14459](#),
 [14727](#), [14748](#), [14790](#), [14792](#), [16240](#)
 __fp_fixed_mul_sub_back:wnwn ...
 [693](#), [14560](#),
 [14804](#), [16013](#), [16015](#), [16016](#), [16017](#),
 [16018](#), [16019](#), [16020](#), [16021](#), [16022](#),
 [16026](#), [16028](#), [16029](#), [16030](#), [16031](#),
 [16032](#), [16033](#), [16034](#), [16059](#), [16061](#),
 [16062](#), [16063](#), [16064](#), [16067](#), [16069](#),
 [16070](#), [16071](#), [16072](#), [16207](#), [16215](#)
 __fp_fixed_one_minus_mul:wnw ...
 [693](#), [694](#), [14580](#)
 __fp_fixed_sub:wnw
 [14513](#), [14796](#), [15075](#), [15091](#),
 [15103](#), [15738](#), [16188](#), [16245](#), [16311](#)
 __fp_fixed_to_float_o:Nw
 [14822](#), [15084](#)
 __fp_fixed_to_float_o:wN
 [688](#), [704](#), [744](#), [14809](#), [14822](#),
 [15104](#), [15114](#), [15138](#), [15405](#), [16235](#)
 __fp_fixed_to_float_pack:ww ...
 [14854](#), [14864](#)
 __fp_fixed_to_float_rad_o:wN ...
 [14817](#), [16235](#)
 __fp_fixed_to_float_round_-
 up:wnnnnw [14867](#), [14871](#)
 __fp_fixed_to_float_zero:w
 [14850](#), [14859](#)
 __fp_fixed_to_loop:N
 [14827](#), [14837](#), [14841](#)
 __fp_fixed_to_loop_end:w
 [14843](#), [14847](#)
 __fp_from_dim:wNNnnnnnn [16531](#)
 __fp_from_dim:wnnnnwNn [16559](#), [16560](#)
 __fp_from_dim:wnnnnwNw [16531](#)
 __fp_from_dim:wNw [16531](#)
 __fp_from_dim_test:ww
 [753](#), [12274](#), [12287](#), [12850](#), [16531](#)
 __fp_function_apply:nw
 .. [647](#), [647](#), [648](#), [13252](#), [13268](#), [13290](#)
 __fp_function_args:Nwn .. [647](#), [13257](#)
 __fp_function_store:wwNwnn
 [648](#), [13290](#)
 __fp_function_store_end:wnnn ...
 [648](#), [13290](#)
 \c__fp_half_prec_int
 [11366](#), [12491](#), [12523](#)
 __fp_inf_fp:N [11379](#), [11730](#)
 __fp_int:wTF [11556](#), [16697](#)
 __fp_int_p:w [11556](#)
 __fp_invalid_operation:nnw
 [595](#), [11672](#), [11754](#),
 [11766](#), [16389](#), [16396](#), [16430](#), [16437](#)
 __fp_invalid_operation_o:nw [595](#),
 [11765](#), [14234](#), [14897](#), [15593](#), [15608](#),
 [15623](#), [15638](#), [15653](#), [15668](#), [16260](#),
 [16278](#), [16294](#), [16322](#), [16335](#), [16351](#)
 __fp_invalid_operation_o:Nww ...
 [595](#), [11680](#),
 [11754](#), [13733](#), [14005](#), [14006](#), [15504](#)
 __fp_invalid_operation_tl_o:nn .
 [595](#), [11689](#), [11754](#), [12043](#), [16717](#)
 \c__fp_leading_shift_int
 [11459](#), [14453](#),
 [14462](#), [14536](#), [15437](#), [15933](#), [15970](#)
 __fp_ln_c:NwNw [711](#), [712](#), [15041](#), [15072](#)
 __fp_ln_div_after:Nw
 [710](#), [14944](#), [14993](#)
 __fp_ln_div_i:w [14966](#), [14975](#)
 __fp_ln_div_ii:wnw
 .. [14969](#), [14970](#), [14971](#), [14972](#), [14980](#)
 __fp_ln_div_vi:wnw ... [14973](#), [14988](#)
 __fp_ln_exponent:wn [712](#), [14920](#), [15081](#)
 __fp_ln_exponent_one:ww [15086](#), [15100](#)
 __fp_ln_exponent_small:NNww ...
 [15089](#), [15093](#), [15106](#)
 \c__fp_ln_i_fixed_tl [14885](#)
 \c__fp_ln_ii_fixed_tl [14885](#)
 \c__fp_ln_iii_fixed_tl [14885](#)
 \c__fp_ln_iv_fixed_tl [14885](#)
 \c__fp_ln_ix_fixed_tl [14885](#)

- __fp_ln_npos_o:w [705](#), [706](#), [14906](#), [14908](#)
- __fp_ln_o:w .. [705](#), [721](#), [14884](#), [14894](#)
- __fp_ln_significand:NNNNnnnN ...
..... [707](#), [14919](#), [14922](#), [15417](#)
- __fp_ln_square_t_after:w
..... [15017](#), [15048](#)
- __fp_ln_square_t_pack:NNNNnw ...
.. [15019](#), [15021](#), [15023](#), [15025](#), [15046](#)
- __fp_ln_t_large:NNw
..... [710](#), [14998](#), [15005](#), [15015](#)
- __fp_ln_t_small:Nw ... [14996](#), [15003](#)
- __fp_ln_t_small:w [710](#)
- __fp_ln_Taylor:wwNw [711](#), [15049](#), [15050](#)
- __fp_ln_Taylor_break:w [15055](#), [15066](#)
- __fp_ln_Taylor_loop:www
..... [15051](#), [15052](#), [15061](#)
- __fp_ln_twice_t_after:w [15029](#), [15045](#)
- __fp_ln_twice_t_pack:Nw . [15031](#),
[15033](#), [15035](#), [15037](#), [15039](#), [15044](#)
- \c__fp_ln_vi_fixed_t1 [14885](#)
- \c__fp_ln_vii_fixed_t1 [14885](#)
- \c__fp_ln_viii_fixed_t1 [14885](#)
- \c__fp_ln_x_fixed_t1
..... [14885](#), [15103](#), [15110](#)
- __fp_ln_x_ii:wnnnn [14924](#), [14942](#)
- __fp_ln_x_iii:NNNNNNw . [14951](#), [14955](#)
- __fp_ln_x_iii_var:NNNNnw
..... [14949](#), [14957](#)
- __fp_ln_x_iv:wnnnnnnnn
..... [709](#), [14947](#), [14962](#)
- \c__fp_max_exp_exponent_int
..... [11372](#), [15146](#)
- \c__fp_max_exponent_int .. [11370](#),
[11376](#), [11397](#), [14660](#), [14861](#), [15472](#)
- \c__fp_middle_shift_int
..... [11459](#), [14465](#),
[14468](#), [14471](#), [14474](#), [14538](#), [14541](#),
[14544](#), [14547](#), [15439](#), [15442](#), [15445](#),
[15448](#), [15936](#), [15943](#), [15973](#), [15979](#)
- __fp_minmax_auxi:ww
..... [13574](#), [13586](#), [13593](#)
- __fp_minmax_auxii:ww
..... [13576](#), [13584](#), [13593](#)
- __fp_minmax_break_o:w . [13567](#), [13597](#)
- __fp_minmax_loop:Nww
..... [655](#), [13561](#), [13563](#), [13569](#)
- __fp_minmax_o:Nw
..... [649](#), [13338](#), [13340](#), [13558](#)
- \c__fp_minus_min_exponent_int ...
..... [11370](#), [11398](#)
- __fp_mul_cases_o:NnNnw
..... [671](#), [13970](#), [13976](#), [14080](#)
- __fp_mul_cases_o:nNnnw [13976](#)
- __fp_mul_npos_o:Nww
..... [668](#), [669](#), [671](#), [753](#), [13973](#), [14014](#), [16562](#)
- __fp_mul_significand_drop:NNNNnw
..... [670](#), [14023](#)
- __fp_mul_significand_keep:NNNNnw
..... [14023](#)
- __fp_mul_significand_large_-
f:NwwNNNN [14051](#), [14055](#)
- __fp_mul_significand_o:nnnnNnnn
..... [669](#), [669](#), [14021](#), [14023](#)
- __fp_mul_significand_small_-
f:NNwwwN [14049](#), [14066](#)
- __fp_mul_significand_test_f:NNN
..... [670](#), [14025](#), [14046](#)
- \c__fp_myriad_int [11369](#),
[14448](#), [14479](#), [14480](#), [14557](#), [14617](#)
- __fp_neg_sign:N
..... [659](#), [11392](#), [13687](#), [13840](#)
- __fp_new_function:NNnnn [13257](#)
- __fp_not_o:w [649](#), [12763](#), [13599](#)
- \c__fp_one_fixed_t1
..... [14442](#), [15057](#), [15213](#),
[15473](#), [15497](#), [16140](#), [16206](#), [16311](#)
- __fp_overflow:w
.. [584](#), [595](#), [597](#), [11400](#), [11754](#), [15148](#)
- \c__fp_overflowing_fp
..... [11373](#), [16390](#), [16431](#)
- __fp_pack:NNNNnw .. [11459](#), [14454](#),
[14464](#), [14467](#), [14470](#), [14473](#), [14476](#),
[14537](#), [14540](#), [14543](#), [14546](#), [14549](#),
[15438](#), [15441](#), [15444](#), [15447](#), [15450](#)
- __fp_pack_big:NNNNNNw ... [11463](#),
[14283](#), [14286](#), [14289](#), [14292](#), [14295](#),
[14298](#), [14301](#), [14305](#), [14564](#), [14574](#),
[14584](#), [14593](#), [14596](#), [14599](#), [14606](#)
- __fp_pack_Bigg:NNNNNNw
..... [11468](#), [14133](#),
[14136](#), [14139](#), [14150](#), [14153](#), [14156](#)
- __fp_pack_eight:wNNNNNNNN
..... [588](#), [666](#), [11475](#),
[13949](#), [14254](#), [14628](#), [15705](#), [15706](#)
- __fp_pack_twice_four:wNNNNNNNN .
..... [588](#),
[11473](#), [12092](#), [12093](#), [13891](#), [13892](#),
[14629](#), [14630](#), [14631](#), [14663](#), [14664](#),
[14665](#), [14852](#), [14853](#), [15185](#), [15186](#),
[15187](#), [15707](#), [15708](#), [15921](#), [16555](#)
- __fp_parse:n
.... [608](#), [619](#), [631](#), [638](#), [648](#), [653](#),
[754](#), [760](#), [761](#), [12123](#), [12271](#), [12874](#),
[12891](#), [13292](#), [13346](#), [13360](#), [13370](#),
[13481](#), [13524](#), [16378](#), [16419](#), [16484](#),
[16524](#), [16571](#), [16573](#), [16575](#), [16715](#),
[16751](#), [16772](#), [16774](#), [16776](#), [16799](#)

- __fp_parse_after:ww [12874](#)
- __fp_parse_apply_binary:NwNwN ..
..... [612](#), [613](#), [616](#),
[616](#), [643](#), [12904](#), [13009](#), [13032](#), [13083](#)
- __fp_parse_apply_compare:NwNNNNwN
..... [13201](#), [13210](#)
- __fp_parse_apply_compare_-
aux:NNwN [13222](#), [13225](#), [13230](#)
- __fp_parse_apply_juxtapose:NwwN
..... [643](#), [13060](#)
- __fp_parse_apply_unary:NNNwN ...
..... [12740](#), [12749](#), [12858](#), [12867](#)
- __fp_parse_caseless_inf:N ... [12824](#)
- __fp_parse_caseless_infinity:N .
..... [12824](#)
- __fp_parse_caseless_nan:N ... [12824](#)
- __fp_parse_compare:NNNNNNN . . [13143](#)
- __fp_parse_compare_auxi:NNNNNNN
..... [13143](#)
- __fp_parse_compare_auxii:NNNNN .
..... [13143](#)
- __fp_parse_compare_end:NNNNw . [13143](#)
- __fp_parse_continue:NwN
..... [612](#), [613](#), [639](#), [12893](#),
[12906](#), [13240](#), [13637](#), [13661](#), [13669](#)
- __fp_parse_continue_compare:NNwNN
..... [13233](#), [13248](#)
- __fp_parse_digits_:N [12153](#)
- __fp_parse_digits_i:N [12153](#)
- __fp_parse_digits_ii:N [12153](#)
- __fp_parse_digits_iii:N [12153](#)
- __fp_parse_digits_iv:N [12153](#)
- __fp_parse_digits_v:N [12153](#)
- __fp_parse_digits_vi:N
..... [12153](#), [12449](#), [12497](#)
- __fp_parse_digits_vii:N
..... [625](#), [12153](#), [12436](#), [12486](#)
- __fp_parse_excl_error: [13143](#)
- __fp_parse_expand:w
..... [615](#), [616](#), [616](#), [616](#), [12138](#), [12140](#),
[12162](#), [12202](#), [12247](#), [12279](#), [12283](#),
[12321](#), [12354](#), [12392](#), [12394](#), [12413](#),
[12415](#), [12437](#), [12454](#), [12467](#), [12487](#),
[12517](#), [12545](#), [12561](#), [12572](#), [12595](#),
[12624](#), [12634](#), [12641](#), [12654](#), [12670](#),
[12690](#), [12701](#), [12759](#), [12782](#), [12794](#),
[12863](#), [12872](#), [12880](#), [12960](#), [12974](#),
[12997](#), [13036](#), [13067](#), [13107](#), [13127](#),
[13195](#), [13208](#), [13255](#), [13275](#), [13633](#)
- __fp_parse_exponent:N
..... [629](#), [12246](#), [12428](#), [12577](#), [12644](#), [12646](#)
- __fp_parse_exponent:Nw
..... [12452](#), [12465](#),
[12514](#), [12542](#), [12593](#), [12622](#), [12641](#)
- __fp_parse_exponent_aux:N ... [12646](#)
- __fp_parse_exponent_body:N
..... [12672](#), [12676](#)
- __fp_parse_exponent_digits:N ...
..... [12680](#), [12692](#)
- __fp_parse_exponent_keep:N .. [12703](#)
- __fp_parse_exponent_keep:NTF ...
..... [12683](#), [12703](#)
- __fp_parse_exponent_sign:N
..... [12662](#), [12666](#)
- __fp_parse_function:NNN
..... [11813](#), [11815](#), [11817](#),
[11831](#), [12856](#), [13338](#), [13340](#), [15576](#),
[15578](#), [15580](#), [15582](#), [16605](#), [16607](#)
- __fp_parse_infix:NN
.. [618](#), [621](#), [636](#), [640](#), [648](#), [12201](#),
[12332](#), [12371](#), [12791](#), [12811](#), [12816](#),
[12831](#), [12853](#), [12913](#), [12916](#), [12972](#)
- __fp_parse_infix_!:N [13143](#)
- __fp_parse_infix_&:Nw [13100](#)
- __fp_parse_infix(:N [13058](#)
- __fp_parse_infix):N [12966](#)
- __fp_parse_infix*:N [13085](#)
- __fp_parse_infix+:N
..... [616](#), [648](#), [12138](#), [13026](#)
- __fp_parse_infix_,:N [12983](#)
- __fp_parse_infix_-:N [13026](#)
- __fp_parse_infix_/:N [13026](#)
- __fp_parse_infix::N . [13117](#), [13622](#)
- __fp_parse_infix<:N [13143](#)
- __fp_parse_infix=:N [13143](#)
- __fp_parse_infix>:N [13143](#)
- __fp_parse_infix?:N [13117](#)
- __fp_parse_infix_⟨operation⟩:N [616](#)
- __fp_parse_infix_~:N [13026](#)
- __fp_parse_infix_after_operand:NwN
..... [621](#), [12237](#), [12294](#), [12766](#), [12911](#)
- __fp_parse_infix_and:N [13026](#), [13116](#)
- __fp_parse_infix_check:NNN
..... [12936](#), [12946](#)
- __fp_parse_infix_comma:w [12983](#)
- __fp_parse_infix_comma_error:w .
..... [12983](#)
- __fp_parse_infix_end:N
..... [638](#), [641](#), [12881](#), [12885](#), [12964](#)
- __fp_parse_infix_juxtapose:N ...
..... [643](#), [12926](#), [12934](#), [13059](#), [13060](#)
- __fp_parse_infix_mark:NNN
..... [12923](#), [12963](#)
- __fp_parse_infix_mul:N [13026](#), [13093](#)
- __fp_parse_infix_or:N . [13026](#), [13115](#)
- __fp_parse_infix_|:Nw [13100](#)
- __fp_parse_large:N [623](#), [12399](#), [12482](#)

- __fp_parse_large_leading:wwNN [627](#), [12484](#), [12489](#)
- __fp_parse_large_round:NN [628](#), [12525](#), [12597](#)
- __fp_parse_large_round_aux:wwNN [12597](#)
- __fp_parse_large_round_test:NN [12597](#)
- __fp_parse_large_trailing:wwNN [628](#), [12495](#), [12519](#)
- __fp_parse_letters:N [621](#), [622](#), [12309](#), [12323](#)
- __fp_parse_lparen_after:NwN . [12772](#)
- __fp_parse_o:n [608](#), [12887](#), [13479](#), [13480](#), [16681](#), [16746](#)
- __fp_parse_one:Nw [611–614](#), [616](#), [623](#), [636](#), [639](#), [12138](#), [12173](#), [12376](#), [12739](#), [12899](#)
- __fp_parse_one_digit:NN [635](#), [12189](#), [12292](#)
- __fp_parse_one_fp:NN [618](#), [12181](#), [12197](#)
- __fp_parse_one_other:NN [12192](#), [12300](#)
- __fp_parse_one_register:NN [12184](#), [12235](#)
- __fp_parse_one_register_aux:Nw [12235](#)
- __fp_parse_one_register_-auxii:wwwNw [12235](#)
- __fp_parse_one_register_dim:ww [12235](#)
- __fp_parse_one_register_int:www [12235](#)
- __fp_parse_one_register_mu:www [12235](#)
- __fp_parse_one_register_wd:Nw [12235](#)
- __fp_parse_one_register_wd:w . [12235](#)
- __fp_parse_operand:Nw . . [611–614](#), [616](#), [638](#), [647](#), [647](#), [12138](#), [12755](#), [12757](#), [12778](#), [12780](#), [12863](#), [12872](#), [12879](#), [12893](#), [12996](#), [13035](#), [13066](#), [13126](#), [13208](#), [13255](#), [13275](#), [13632](#)
- __fp_parse_pack_carry:w . [626](#), [12469](#)
- __fp_parse_pack_leading:NNNNNww [12432](#), [12469](#), [12492](#)
- __fp_parse_pack_trailing:NNNNNww [12442](#), [12469](#), [12511](#), [12522](#), [12529](#)
- __fp_parse_prefix:NNN . [12312](#), [12356](#)
- __fp_parse_prefix_!:Nw [12745](#)
- __fp_parse_prefix_(:Nw [12772](#)
- __fp_parse_prefix_):Nw [12803](#)
- __fp_parse_prefix_+:Nw [12739](#)
- __fp_parse_prefix_-:Nw [12745](#)
- __fp_parse_prefix_.:Nw [12764](#)
- __fp_parse_prefix_unknown:NNN [12356](#)
- __fp_parse_return_semicolon:w [12139](#), [12160](#), [12352](#), [12559](#), [12570](#), [12652](#), [12684](#), [12699](#)
- __fp_parse_round:Nw [600](#), [11818](#)
- __fp_parse_round_after:wN [629](#), [12574](#), [12579](#), [12629](#)
- __fp_parse_round_deprecation_error:Nw [11818](#)
- __fp_parse_round_loop:N . . . [629](#), [629](#), [630](#), [12547](#), [12590](#), [12608](#), [12633](#)
- __fp_parse_round_no_error:Nw . [11818](#)
- __fp_parse_round_up:N [12547](#)
- __fp_parse_small:N [624](#), [12419](#), [12430](#)
- __fp_parse_small_leading:wwNN [625](#), [12434](#), [12439](#), [12501](#)
- __fp_parse_small_round:NN [12461](#), [12579](#), [12618](#)
- __fp_parse_small_trailing:wwNN [626](#), [12447](#), [12456](#), [12533](#)
- __fp_parse_strim_end:w [12405](#)
- __fp_parse_strim_zeros:N [623](#), [635](#), [12386](#), [12405](#), [12770](#)
- __fp_parse_trim_end:w [12379](#)
- __fp_parse_trim_zeros:N [12298](#), [12379](#)
- __fp_parse_unary_function:NNN [12856](#), [13679](#), [13681](#), [13683](#), [14882](#), [14884](#), [15564](#), [15570](#)
- __fp_parse_word:Nw [621](#), [12306](#), [12323](#)
- __fp_parse_word_abs:N [13678](#)
- __fp_parse_word_acos:N [15556](#)
- __fp_parse_word_acosd:N [15556](#)
- __fp_parse_word_acot:N [15575](#)
- __fp_parse_word_acotd:N [15575](#)
- __fp_parse_word_acsc:N [15556](#)
- __fp_parse_word_acscd:N [15556](#)
- __fp_parse_word_asec:N [15556](#)
- __fp_parse_word_asecd:N [15556](#)
- __fp_parse_word_asin:N [15556](#)
- __fp_parse_word_asind:N [15556](#)
- __fp_parse_word_atan:N [15575](#)
- __fp_parse_word_atand:N [15575](#)
- __fp_parse_word_bp:N [12827](#)
- __fp_parse_word_cc:N [12827](#)
- __fp_parse_word_ceil:N [11812](#)
- __fp_parse_word_cm:N [12827](#)
- __fp_parse_word_cos:N [15556](#)
- __fp_parse_word_cosd:N [15556](#)
- __fp_parse_word_cot:N [15556](#)
- __fp_parse_word_cotd:N [15556](#)
- __fp_parse_word_csc:N [15556](#)
- __fp_parse_word_cscd:N [15556](#)
- __fp_parse_word_dd:N [12827](#)
- __fp_parse_word_deg:N [12813](#)

- __fp_parse_word_em:N [12846](#)
- __fp_parse_word_ex:N [12846](#)
- __fp_parse_word_exp:N [14881](#)
- __fp_parse_word_false:N [12813](#)
- __fp_parse_word_floor:N [11812](#)
- __fp_parse_word_in:N [12827](#)
- __fp_parse_word_inf:N
..... [12813](#), [12824](#), [12825](#)
- __fp_parse_word_ln:N [14881](#)
- __fp_parse_word_max:N [13337](#)
- __fp_parse_word_min:N [13337](#)
- __fp_parse_word_mm:N [12827](#)
- __fp_parse_word_nan:N . [12813](#), [12826](#)
- __fp_parse_word_nc:N [12827](#)
- __fp_parse_word_nd:N [12827](#)
- __fp_parse_word_pc:N [12827](#)
- __fp_parse_word_pi:N [12813](#)
- __fp_parse_word_pt:N [12827](#)
- __fp_parse_word_rand:N [16604](#)
- __fp_parse_word_randint:N ... [16604](#)
- __fp_parse_word_round:N . [600](#), [11818](#)
- __fp_parse_word_sec:N [15556](#)
- __fp_parse_word_secd:N [15556](#)
- __fp_parse_word_sign:N [13678](#)
- __fp_parse_word_sin:N [15556](#)
- __fp_parse_word_sind:N [15556](#)
- __fp_parse_word_sp:N [12827](#)
- __fp_parse_word_sqrt:N [13678](#)
- __fp_parse_word_tan:N [15556](#)
- __fp_parse_word_tand:N [15556](#)
- __fp_parse_word_true:N [12813](#)
- __fp_parse_word_trunc:N [11812](#)
- __fp_parse_zero:
..... [623](#), [12401](#), [12421](#), [12425](#)
- __fp_pow_B:wwN [15420](#), [15455](#)
- __fp_pow_C_neg:w [15458](#), [15475](#)
- __fp_pow_C_overflow:w
..... [15463](#), [15470](#), [15491](#)
- __fp_pow_C_pack:w [15477](#), [15485](#), [15496](#)
- __fp_pow_C_pos:w [15461](#), [15480](#)
- __fp_pow_C_pos_loop:wN
..... [15481](#), [15482](#), [15489](#)
- __fp_pow_exponent:Nwnnnnnw
..... [15426](#), [15429](#), [15434](#)
- __fp_pow_exponent:wnN . [15418](#), [15423](#)
- __fp_pow_neg:www .. [723](#), [15331](#), [15498](#)
- __fp_pow_neg_aux:wNN ... [723](#), [15498](#)
- __fp_pow_neg_case:w .. [15500](#), [15521](#)
- __fp_pow_neg_case_aux:nnnnn . [15521](#)
- __fp_pow_neg_case_aux:Nnnw
..... [723](#), [15521](#)
- __fp_pow_normal_o:ww
..... [718](#), [719](#), [15336](#), [15368](#)
- __fp_pow_npos_aux:NNnnw
..... [15403](#), [15407](#), [15413](#)
- __fp_pow_npos_o:Nww [720](#), [15380](#), [15397](#)
- __fp_pow_zero_or_inf:ww
..... [718](#), [15338](#), [15345](#)
- \c__fp_prec_and_int ... [12123](#), [13055](#)
- \c__fp_prec_colon_int
..... [12123](#), [13138](#), [13632](#)
- \c__fp_prec_comma_int ... [12123](#),
[12778](#), [12805](#), [12987](#), [12992](#), [12996](#)
- \c__fp_prec_comp_int
..... [12123](#), [13166](#), [13208](#)
- \c__fp_prec_end_int [638](#), [12123](#), [12879](#)
- \c__fp_prec_func_int .. [12123](#), [12863](#)
- \c__fp_prec_funcii_int
.. [12123](#), [12777](#), [12872](#), [13255](#), [13275](#)
- \c__fp_prec_hat_int ... [12123](#), [13045](#)
- \c__fp_prec_hatii_int . [12123](#), [13045](#)
- \c__fp_prec_int [11366](#), [11502](#), [11563](#),
[11590](#), [12061](#), [15166](#), [15533](#), [15536](#),
[16449](#), [16451](#), [16457](#), [16499](#), [16701](#)
- \c__fp_prec_not_int
..... [634](#), [12123](#), [12762](#), [12763](#)
- \c__fp_prec_or_int [12123](#), [13057](#)
- \c__fp_prec_paren_int
..... [12123](#), [12780](#), [12970](#)
- \c__fp_prec_plus_int
..... [610](#), [12123](#), [13051](#), [13053](#)
- \c__fp_prec_quest_int
..... [12123](#), [13121](#), [13136](#)
- \c__fp_prec_times_int
.. [12123](#), [13047](#), [13049](#), [13062](#), [13066](#)
- \c__fp_rand_eight_int
..... [16621](#), [16640](#), [16643](#)
- \c__fp_rand_four_int
.. [16621](#), [16646](#), [16649](#), [16662](#), [16665](#)
- __fp_rand_myriads:n
..... [756](#), [758](#), [16626](#), [16681](#), [16751](#)
- __fp_rand_myriads_get:w [16626](#)
- __fp_rand_myriads_last: [16626](#)
- __fp_rand_myriads_last:w [16626](#)
- __fp_rand_myriads_loop:nn ... [16626](#)
- __fp_rand_o: [16670](#)
- __fp_rand_o:Nw
..... [16605](#), [16612](#), [16617](#), [16670](#)
- __fp_rand_o:w [16670](#)
- \c__fp_rand_size_int
..... [941](#), [16621](#), [16727](#),
[16738](#), [22946](#), [22947](#), [22958](#), [22967](#)
- __fp_rand_uniform: [16621](#),
[16636](#), [16658](#), [16725](#), [16741](#), [16759](#)
- __fp_randint_badarg:w [16682](#)
- __fp_randint_e:w [16682](#)
- __fp_randint_e:wnn [16682](#)

__fp_randint_e:wwNnn [16682](#)
 __fp_randint_e:wwwNnn ... [758](#), [16682](#)
 __fp_randint_narrow_e:nnnn .. [16682](#)
 __fp_randint_o:Nw [16607](#), [16617](#), [16682](#)
 __fp_randint_wide_e:nnnn [16682](#)
 __fp_randint_wide_e:wnnn [16682](#)
 __fp_reverse_args:Nww [746](#),
 [747](#), [11344](#), [16076](#), [16162](#), [16274](#), [16340](#)
 __fp_round:NNN [601](#), [602](#), [603](#), [671](#),
 [686](#), [11866](#), [11936](#), [13808](#), [13819](#),
 [14061](#), [14073](#), [14213](#), [14224](#), [14408](#)
 __fp_round:Nwn . [11986](#), [12039](#), [16529](#)
 __fp_round:Nww . [11987](#), [12008](#), [12039](#)
 __fp_round:Nwww [11988](#), [12002](#)
 __fp_round_digit:Nw .. [590](#), [604](#),
 [670](#), [671](#), [686](#), [11520](#), [11950](#), [13822](#),
 [13965](#), [14064](#), [14076](#), [14227](#), [14413](#)
 __fp_round_name_from_cs:N
 [11998](#), [12024](#), [12028](#), [12044](#)
 __fp_round_neg:NNN [602](#),
 [604](#), [667](#), [11961](#), [13927](#), [13942](#), [13960](#)
 __fp_round_no_arg_o:Nw [11985](#), [11992](#)
 __fp_round_normal:NnnwNnnn .. [12039](#)
 __fp_round_normal:NwNnn [12039](#)
 __fp_round_normal:NwNnnw [12039](#)
 __fp_round_normal_end:wwNnn . [12039](#)
 __fp_round_o:Nw
 .. [11813](#), [11815](#), [11817](#), [11832](#), [11981](#)
 __fp_round_pack:Nw [12039](#)
 __fp_round_return_one:
 [602](#), [11866](#), [11872](#),
 [11882](#), [11890](#), [11894](#), [11903](#), [11907](#),
 [11916](#), [11923](#), [11927](#), [11965](#), [11975](#)
 __fp_round_s:NNNw
 .. [601](#), [603](#), [629](#), [11934](#), [12583](#), [12601](#)
 __fp_round_special:NwNnn ... [12039](#)
 __fp_round_special_aux:Nw ... [12039](#)
 __fp_round_to_nearest:NNN . [605](#),
 [605](#), [11832](#), [11848](#), [11858](#), [11863](#),
 [11866](#), [11970](#), [11994](#), [12004](#), [16529](#)
 __fp_round_to_nearest_neg:NNN [11961](#)
 __fp_round_to_nearest_ninf:NNN .
 [605](#), [11866](#), [11979](#)
 __fp_round_to_nearest_ninf_-
 neg:NNN [11961](#)
 __fp_round_to_nearest_pinf:NNN .
 [605](#), [11866](#), [11971](#)
 __fp_round_to_nearest_pinf_-
 neg:NNN [11961](#)
 __fp_round_to_nearest_zero:NNN .
 [605](#), [11866](#)
 __fp_round_to_nearest_zero_-
 neg:NNN [11961](#)

__fp_round_to_ninf:NNN
 .. [11815](#), [11827](#), [11866](#), [11969](#), [12032](#)
 __fp_round_to_ninf_neg:NNN .. [11961](#)
 __fp_round_to_pinf:NNN
 .. [11817](#), [11821](#), [11866](#), [11961](#), [12034](#)
 __fp_round_to_pinf_neg:NNN .. [11961](#)
 __fp_round_to_zero:NNN
 [11813](#), [11824](#), [11866](#), [12030](#)
 __fp_round_to_zero_neg:NNN .. [11961](#)
 __fp_rrot:www [11345](#), [16207](#)
 __fp_sanitize:Nw
 [661](#), [664](#), [669](#), [672](#), [680](#), [737](#),
 [744](#), [11394](#), [12100](#), [12118](#), [13751](#),
 [13845](#), [14017](#), [14096](#), [14242](#), [14910](#),
 [15152](#), [15399](#), [16038](#), [16082](#), [16219](#)
 __fp_sanitize:wN
 [621](#), [624](#), [11394](#), [12297](#), [12769](#)
 __fp_sanitize_zero:w [11394](#)
 __fp_sec_o:w [15628](#)
 __fp_set_sign_o:w
 [12762](#), [13679](#), [14428](#), [14429](#)
 __fp_show:NN [16804](#)
 __fp_sign_aux_o:w [14417](#)
 __fp_sign_o:w [13681](#), [14417](#)
 __fp_sin_o:w [634](#), [745](#), [15583](#)
 __fp_sin_series_aux_o:NNwww . [15990](#)
 __fp_sin_series_o:NNwww . [725](#),
 [738](#), [15589](#), [15604](#), [15619](#), [15634](#), [15990](#)
 __fp_small_int:wTF ... [11572](#), [12041](#)
 __fp_small_int_normal:NwTF . [11572](#)
 __fp_small_int_test:NnnwNTF . [11572](#)
 __fp_small_int_test:NnnwNw
 [11591](#), [11594](#)
 __fp_small_int_true:wTF [11572](#)
 __fp_sqrt_auxi_o:NNNNwnnN
 [14264](#), [14272](#)
 __fp_sqrt_auxii_o:NnnnnnnnN ...
 [682](#), [684](#), [14274](#), [14278](#), [14358](#), [14370](#)
 __fp_sqrt_auxiii_o:wnnnnnnnnn ...
 [14275](#), [14313](#), [14359](#)
 __fp_sqrt_auxiv_o:NNNNw [14313](#)
 __fp_sqrt_auxix_o:wwnw [14347](#)
 __fp_sqrt_auxv_o:NNNNw [14313](#)
 __fp_sqrt_auxvi_o:NNNNw [14313](#)
 __fp_sqrt_auxvii_o:NNNNw ... [14313](#)
 __fp_sqrt_auxviii_o:nnnnnnn ...
 .. [14335](#), [14337](#), [14339](#), [14345](#), [14347](#)
 __fp_sqrt_auxx_o:Nnnnnnnn
 [14343](#), [14361](#)
 __fp_sqrt_auxxi_o:wnnN [14361](#)
 __fp_sqrt_auxxii_o:nnnnnnnw ...
 [14371](#), [14375](#)
 __fp_sqrt_auxxiii_o:w [14375](#)

- __fp_sqrt_auxxiv_o:wnnnnnnN ...
..... [14387](#), [14390](#), [14398](#), [14400](#)
- __fp_sqrt_Newton_o:wwn
..... [682](#), [14249](#), [14260](#), [14261](#)
- __fp_sqrt_npos_auxi_o:wwnnN . [14240](#)
- __fp_sqrt_npos_auxii_o:wNNNNNNN
..... [14240](#)
- __fp_sqrt_npos_o:w ... [14237](#), [14240](#)
- __fp_sqrt_o:w [13683](#), [14230](#)
- __fp_step:Nnnnnn [13529](#)
- __fp_step:NnnnnN [13476](#)
- __fp_step:wwwN [13476](#)
- __fp_sub_back_far_o:NnnwnnnN ..
..... [666](#), [13854](#), [13900](#)
- __fp_sub_back_near_after:wNNNNw
..... [13860](#), [13938](#)
- __fp_sub_back_near_o:nnnnnnnnN .
..... [664](#), [13850](#), [13860](#)
- __fp_sub_back_near_pack:NNNNNNw
..... [13860](#), [13940](#)
- __fp_sub_back_not_far_o:wwwNN .
..... [13915](#), [13935](#)
- __fp_sub_back_quite_far_ii:NN [13919](#)
- __fp_sub_back_quite_far_o:wwNN .
..... [13913](#), [13919](#)
- __fp_sub_back_shift:wnnnn
..... [665](#), [13872](#), [13876](#)
- __fp_sub_back_shift_ii:ww ... [13876](#)
- __fp_sub_back_shift_iii:NNNNNNNw
..... [13876](#)
- __fp_sub_back_shift_iv:nnnnw . [13876](#)
- __fp_sub_back_very_far_ii-
o:nnNwwNN [13947](#)
- __fp_sub_back_very_far_o:wwwNN
..... [13914](#), [13947](#)
- __fp_sub_eq_o:Nnnnw [13825](#)
- __fp_sub_npos_i_o:Nnnnw
..... [664](#), [13830](#), [13839](#), [13843](#)
- __fp_sub_npos_ii_o:Nnnnw [13825](#)
- __fp_sub_npos_o:NnwNnw
..... [663](#), [13745](#), [13825](#)
- __fp_tan_o:w [15643](#)
- __fp_tan_series_aux_o:Nnwww . [16044](#)
- __fp_tan_series_o:NNwww
..... [727](#), [728](#), [15650](#), [15665](#), [16044](#)
- __fp_ternary:NwwN . [649](#), [13136](#), [13620](#)
- __fp_ternary_auxi:NwwN .. [649](#), [13620](#)
- __fp_ternary_auxii:NwwN
..... [649](#), [13138](#), [13620](#)
- __fp_ternary_break_point:n .. [13620](#)
- __fp_ternary_loop:Nw [13620](#)
- __fp_ternary_loop_break:w ... [13620](#)
- __fp_ternary_map_break: [13620](#)
- __fp_tmp:w [590](#), [642](#), [11514](#),
[11524](#), [11525](#), [11526](#), [11527](#), [11528](#),
[11529](#), [11530](#), [11531](#), [11532](#), [11533](#),
[11534](#), [11535](#), [11536](#), [11537](#), [11538](#),
[11539](#), [12153](#), [12165](#), [12166](#), [12167](#),
[12168](#), [12169](#), [12170](#), [12171](#), [12217](#),
[12233](#), [12745](#), [12762](#), [12763](#), [12813](#),
[12818](#), [12819](#), [12820](#), [12821](#), [12822](#),
[12823](#), [12827](#), [12835](#), [12836](#), [12837](#),
[12838](#), [12839](#), [12840](#), [12841](#), [12842](#),
[12843](#), [12844](#), [12845](#), [12966](#), [12982](#),
[12983](#), [13001](#), [13013](#), [13025](#), [13026](#),
[13044](#), [13046](#), [13048](#), [13050](#), [13052](#),
[13054](#), [13056](#), [13085](#), [13099](#), [13100](#),
[13115](#), [13116](#), [13117](#), [13135](#), [13137](#)
- __fp_to_decimal_dispatch:w
..... [750](#), [752](#),
[753](#), [13522](#), [16414](#), [16418](#), [16421](#), [16528](#)
- __fp_to_decimal_huge:wnnnn .. [16421](#)
- __fp_to_decimal_large:Nnnw .. [16421](#)
- __fp_to_decimal_normal:wnnnn ..
..... [16421](#), [16500](#)
- __fp_to_int_dispatch:w
..... [16519](#), [16523](#), [16526](#)
- __fp_to_scientific_dispatch:w ..
.. [749](#), [750](#), [752](#), [16373](#), [16377](#), [16380](#)
- __fp_to_scientific_normal:wnnnn
..... [16380](#)
- __fp_to_scientific_normal:wNw [16380](#)
- __fp_to_tl_dispatch:w
.... [751](#), [16479](#), [16483](#), [16486](#), [16597](#)
- __fp_to_tl_normal:nnnn [16486](#)
- __fp_to_tl_scientific:wnnnn . [16486](#)
- __fp_to_tl_scientific:wNw ... [16486](#)
- \c_fp_trailing_shift_int
..... [11459](#), [14455](#),
[14477](#), [14550](#), [15451](#), [15936](#), [15973](#)
- __fp_trap_division_by_zero_-
set:N [11697](#)
- __fp_trap_division_by_zero_set_-
error: [11697](#)
- __fp_trap_division_by_zero_set_-
flag: [11697](#)
- __fp_trap_division_by_zero_set_-
none: [11697](#)
- __fp_trap_invalid_operation_-
set:N [11663](#)
- __fp_trap_invalid_operation_-
set_error: [11663](#)
- __fp_trap_invalid_operation_-
set_flag: [11663](#)
- __fp_trap_invalid_operation_-
set_none: [11663](#)
- __fp_trap_overflow_set:N [11723](#)

- __fp_trap_overflow_set:NnNn . [11723](#)
 - __fp_trap_overflow_set_error: [11723](#)
 - __fp_trap_overflow_set_flag: . [11723](#)
 - __fp_trap_overflow_set_none: . [11723](#)
 - __fp_trap_underflow_set:N . . . [11723](#)
 - __fp_trap_underflow_set_error: [11723](#)
 - __fp_trap_underflow_set_flag: [11723](#)
 - __fp_trap_underflow_set_none: [11723](#)
 - __fp_trig:NNNNwn . [15589](#), [15604](#), [15619](#), [15634](#), [15649](#), [15664](#), [15681](#)
 - __fp_trig_inverse_two_pi: [734](#), [15742](#), [15911](#)
 - __fp_trig_large:ww . . . [15689](#), [15906](#)
 - __fp_trig_large_auxi:wwwww . [15906](#)
 - __fp_trig_large_auxii:ww . . . [15906](#)
 - __fp_trig_large_auxiii:wNNNNNNNN [15906](#)
 - __fp_trig_large_auxiv:wN . . . [15906](#)
 - __fp_trig_large_auxix:Nw . . . [15949](#)
 - __fp_trig_large_auxv:www [15922](#), [15929](#)
 - __fp_trig_large_auxvi:wnnnnnnnn [15929](#)
 - __fp_trig_large_auxvii:w [15932](#), [15949](#)
 - __fp_trig_large_auxviii:w . . [15949](#)
 - __fp_trig_large_auxviii:ww [15951](#), [15955](#)
 - __fp_trig_large_auxx:wNNNNN . [15949](#)
 - __fp_trig_large_auxxi:w [15949](#)
 - __fp_trig_large_pack:NNNNw [15929](#), [15978](#)
 - __fp_trig_small:ww [729](#), [735](#), [15691](#), [15695](#), [15701](#), [15988](#)
 - __fp_trigd_large:ww . . [15689](#), [15703](#)
 - __fp_trigd_large_auxi:nnnnwNNNN [15703](#)
 - __fp_trigd_large_auxii:wNw . . [15703](#)
 - __fp_trigd_large_auxiii:www . [15703](#)
 - __fp_trigd_small:ww [730](#), [15691](#), [15697](#), [15740](#)
 - __fp_trim_zeros:w [16364](#), [16462](#), [16471](#), [16513](#)
 - __fp_trim_zeros_dot:w [16364](#)
 - __fp_trim_zeros_end:w [16364](#)
 - __fp_trim_zeros_loop:w [16364](#)
 - __fp_type_from_scan:N [617](#), [618](#), [11454](#), [12141](#), [12199](#)
 - __fp_type_from_scan:w [12141](#)
 - __fp_underflow:w [584](#), [595](#), [597](#), [11401](#), [11754](#), [15149](#)
 - __fp_use_i:ww [696](#), [746](#), [11346](#), [14666](#), [16293](#)
 - __fp_use_i:www [11346](#)
 - __fp_use_i_until_s:nw [735](#), [11341](#), [11388](#), [11564](#), [11623](#), [13018](#), [15733](#), [15931](#), [15937](#), [15968](#)
 - __fp_use_ii_until_s:nnw [11341](#), [11386](#)
 - __fp_use_none_stop_f:n [11338](#), [14830](#), [14831](#), [14832](#)
 - __fp_use_none_until_s:w [11341](#), [14266](#), [15507](#), [16288](#), [16291](#)
 - __fp_use_s:n [11339](#)
 - __fp_use_s:nn [11339](#)
 - __fp_zero_fp:N . [11379](#), [11738](#), [12106](#)
 - __fp_l_o:ww [649](#), [13607](#)
 - _fp_ [13610](#), [13617](#)
 - \futurelet [374](#)
- G**
- \gdef [375](#)
 - \GetIdInfo [6](#)
 - \gleaders [891](#)
 - \global [166](#), [167](#), [181](#), [182](#), [183](#), [194](#), [195](#), [196](#), [197](#), [198](#), [199](#), [200](#), [201](#), [202](#), [205](#), [272](#), [376](#)
 - \globaldefs [377](#)
 - \glueexpr [631](#)
 - \glueshrink [632](#)
 - \glueshrinkorder [633](#)
 - \gluestretch [634](#)
 - \gluestretchorder [635](#)
 - \gluetomu [636](#)
 - group commands:
 - \group_align_safe_begin/end: [444](#), [783](#)
 - \group_align_safe_begin: [104](#), [347](#), [351](#), [437](#), [3172](#), [3504](#), [6318](#), [6494](#), [7592](#), [17345](#), [23365](#)
 - \group_align_safe_end: [104](#), [347](#), [351](#), [3195](#), [3530](#), [6320](#), [6494](#), [7597](#), [7603](#), [17348](#), [23386](#)
 - \group_begin: [9](#), [924](#), [1358](#), [2315](#), [2318](#), [2321](#), [2625](#), [2816](#), [2928](#), [3037](#), [3043](#), [3071](#), [3271](#), [3780](#), [3807](#), [4091](#), [4114](#), [4440](#), [4459](#), [4789](#), [7151](#), [7157](#), [7218](#), [7291](#), [7315](#), [7333](#), [7357](#), [7447](#), [7465](#), [7671](#), [8208](#), [8229](#), [8292](#), [8572](#), [8881](#), [8946](#), [8987](#), [9479](#), [9514](#), [10399](#), [13607](#), [16924](#), [17274](#), [17344](#), [17351](#), [17422](#), [17577](#), [17900](#), [19623](#), [20137](#), [20290](#), [20299](#), [20311](#), [20320](#), [20328](#), [20447](#), [20476](#), [20966](#), [20981](#), [20984](#), [20987](#), [20994](#), [21000](#), [21009](#), [21016](#), [21031](#), [21038](#), [21045](#), [21048](#), [21058](#), [21060](#), [21064](#), [21069](#), [21075](#), [21081](#), [21089](#), [21095](#), [21103](#), [21109](#), [21118](#), [21125](#), [21141](#), [21148](#), [22309](#)

- 23312, 23339, 24004, 24013, 24035,
24184, 24206, 24423, 24429, 25811
- \c_group_begin_token 48,
119, 361, 468, 3637, 3672, 7315,
7339, 17387, 21008, 21015, 21030,
21037, 21117, 21124, 21140, 21147
- \group_end:
..... 9, 9, 393, 924, 1358, 2315,
2318, 2324, 2631, 2819, 2934, 3039,
3051, 3129, 3275, 3278, 3798, 3827,
4096, 4119, 4466, 4571, 4799, 4804,
7159, 7166, 7294, 7312, 7332, 7336,
7364, 7464, 7510, 7736, 8215, 8240,
8431, 8617, 8897, 8965, 8996, 9483,
9534, 10450, 13618, 16943, 17183,
17276, 17349, 17368, 17429, 17601,
17911, 19627, 19628, 20198, 20295,
20306, 20390, 20453, 20513, 20972,
20981, 20984, 20987, 20994, 21000,
21022, 21045, 21048, 21058, 21060,
21064, 21069, 21075, 21081, 21089,
21095, 21103, 21109, 21132, 22313,
23319, 23344, 24027, 24034, 24199,
24205, 24230, 24427, 24453, 25819
- \c_group_end_token 119,
468, 7315, 7344, 17390, 21023, 21133
- \group_insert_after:N
..... 9, 1364, 17908, 22321
- groups commands:
 .groups:n 173, 10899
- ## H
- \H 24233
- \halign 378
- \hangafter 379
- \hangindent 380
- \hbadness 381
- \hbox 382
- hbox commands:
 \hbox:n
 222, 20980, 21202, 21450, 22099, 22154
- \hbox_gset:Nn 222, 20982
- \hbox_gset:Nw 223, 21004
- \hbox_gset_end: 223, 21004
- \hbox_gset_to_wd:Nnn 222, 20990
- \hbox_gset_to_wd:Nnw 223, 21026
- \hbox_overlap_left:n 223, 21049
- \hbox_overlap_right:n
 222, 21049, 24810, 24836,
 25160, 25199, 25306, 25332, 25780
- \hbox_set:Nn
 .. 222, 223, 20982, 21173, 21198,
 21199, 21285, 21323, 21338, 21353,
 21365, 21381, 21411, 21423, 21557,
 21659, 21885, 21956, 22244, 22496,
 22500, 22508, 22516, 22525, 22534,
 22546, 22554, 22562, 22568, 22581,
 22628, 22641, 25269, 25474, 25674
- \hbox_set:Nw 223, 21004, 21603
- \hbox_set_end: 223, 223, 21004, 21606
- \hbox_set_to_wd:Nnn . 222, 223, 20990
- \hbox_set_to_wd:Nnw 223, 21026
- \hbox_to_wd:nn 222, 21042, 21441
- \hbox_to_zero:n
 222, 21042, 21050, 21052
- \hbox_unpack:N 223, 21053, 21889
- \hbox_unpack_clear:N 223, 21053
- hcoffin commands:
 \hcoffin_set:Nn
 229, 21553, 22096, 22108, 22151, 22191
- \hcoffin_set:Nw 229, 21599
- \hcoffin_set_end: 229, 21599
- \hfil 383
- \hfill 384
- \hfilneg 385
- \hfuzz 386
- \hjcode 886
- \hoffset 387
- \holdinginserts 388
- \hpack 887
- \hrule 389
- \hsize 390
- \hskip 391
- \hss 392
- \ht 393
- hundred commands:
 \c_one_hundred 85, 5961
- \hyphenation 394
- \hyphenationbounds 888
- \hyphenationmin 889
- \hyphenchar 395
- \hyphenpenalty 396
- \hyphenpenaltymode 890
- ## I
- \I 195
- \i 198, 24228
- \if 397
- if commands:
 \if:w 21, 114, 306, 307,
 333, 1331, 1576, 1588, 1590, 1914,
 2209, 2210, 2697, 2700, 2701, 2702,
 2703, 2718, 2719, 2720, 2721, 2722,
 2723, 2724, 2725, 2789, 2790, 2792,
 4486, 5831, 7557, 8794, 8796, 10476,
 10480, 10498, 12381, 12385, 12407,
 12500, 12532, 12551, 12617, 12631,
 12648, 12668, 13089, 13104, 15402

`\if_bool:N` 103, 103, 6240, 6275
`\if_box_empty:N` ... 228, 20910, 20926
`\if_case:w` 86,
376, 377, 418, 591, 671, 716, 723,
2123, 4187, 4263, 5111, 5722, 5755,
7306, 9618, 11396, 11559, 11574,
11983, 12012, 13177, 13217, 13692,
13827, 13902, 13927, 13979, 14419,
14436, 14675, 14899, 14926, 15083,
15118, 15221, 15237, 15253, 15269,
15285, 15301, 15326, 15378, 15500,
15523, 15585, 15600, 15615, 15630,
15645, 15660, 16100, 16117, 16170,
16253, 16268, 16320, 16333, 16383,
16424, 16489, 16684, 16710, 17398,
17587, 17860, 18134, 18880, 18909,
18966, 19382, 19439, 19777, 20081
`\if_catcode:w` 21, 352, 361, 362, 477,
1331, 3324, 3628, 3670, 3682, 3699,
7339, 7344, 7349, 7354, 7361, 7368,
7373, 7378, 7383, 7388, 7393, 7403,
7432, 7629, 7634, 12175, 12341,
12658, 12705, 12918, 13076, 17387,
17390, 17543, 17545, 17547, 17548,
17549, 17550, 17551, 24435, 24436
`\if_charcode:w`
..... 21, 114, 360, 361, 380,
477, 788, 1331, 3609, 3663, 4346,
7408, 7631, 11562, 17457, 17480,
17529, 18074, 18084, 18540, 19952
`\if_cs_exist:N`
.... 21, 1345, 1945, 1973, 7440, 7566
`\if_cs_exist:w` ... 21, 1345, 1372,
1954, 1982, 2110, 6059, 6100, 6110
`\if_dim:w` .. 168, 9836, 9950, 9968, 9991
`\if_eof:w` 153, 9271, 9278
`\if_false:` 21, 98,
347, 351, 359, 395, 409, 444, 780,
867, 1331, 3190, 3191, 3292, 3296,
3577, 3582, 3593, 3683, 3695, 3710,
3718, 4740, 4743, 4878, 4883, 5352,
6495, 7249, 9597, 9636, 9640, 9647,
9655, 9978, 17336, 17376, 17425,
17428, 18033, 18035, 18059, 18063,
18123, 18127, 18312, 18331, 18332,
18338, 18386, 18419, 18430, 18432,
18655, 18688, 18700, 18704, 18732,
18737, 18745, 18779, 18784, 18789,
18827, 19040, 19057, 19061, 20153,
20167, 20406, 20411, 20518, 20523
`\if_hbox:N` 227, 20910, 20914
`\if_int_compare:w`
..... 21, 86, 409, 410, 1362,
3908, 3916, 3931, 3936, 4174, 4228,
4229, 4235, 4247, 4263, 4489, 4513,
4524, 4525, 4532, 4544, 5111, 5161,
5245, 5332, 5385, 5387, 5389, 5391,
5393, 5395, 5397, 5406, 6495, 6497,
7186, 7189, 7190, 7197, 7198, 7199,
7200, 7205, 7206, 7424, 7548, 9604,
10216, 11397, 11398, 11502, 11599,
11871, 11881, 11889, 11902, 11915,
11922, 11943, 11955, 11964, 11974,
12068, 12073, 12157, 12187, 12302,
12304, 12340, 12345, 12398, 12418,
12445, 12459, 12494, 12521, 12549,
12565, 12581, 12599, 12658, 12678,
12694, 12707, 12721, 12754, 12777,
12805, 12919, 12929, 12931, 12970,
12987, 12992, 13030, 13062, 13121,
13166, 13358, 13388, 13391, 13402,
13405, 13410, 13411, 13414, 13417,
13579, 13653, 13696, 13717, 13754,
13849, 13903, 13904, 13907, 13910,
13980, 13989, 14190, 14263, 14316,
14320, 14324, 14342, 14377, 14378,
14379, 14380, 14381, 14407, 14677,
14680, 14774, 14866, 14912, 14928,
15054, 15088, 15146, 15155, 15195,
15371, 15373, 15384, 15402, 15425,
15457, 15460, 15503, 15533, 15688,
15732, 16121, 16159, 16168, 16203,
16287, 16290, 16472, 16640, 16646,
16662, 16700, 16860, 16930, 16998,
17006, 17017, 17020, 17038, 17073,
17083, 17093, 17257, 17292, 17301,
17362, 17434, 17467, 17474, 17497,
17521, 17568, 17583, 17658, 17661,
17800, 17806, 17807, 17814, 17817,
17820, 17826, 17827, 17831, 17834,
17835, 17843, 17844, 17845, 17850,
17879, 17880, 18131, 18151, 18152,
18153, 18156, 18160, 18161, 18164,
18165, 18173, 18174, 18177, 18181,
18182, 18185, 18232, 18254, 18266,
18275, 18283, 18286, 18296, 18299,
18323, 18390, 18489, 18554, 18559,
18587, 18654, 18686, 18788, 19071,
19101, 19317, 19400, 19429, 19494,
19507, 19518, 19534, 19585, 19617,
19755, 19756, 19805, 19832, 19907,
19963, 20014, 20024, 20026, 20042,
20096, 20149, 20163, 20186, 20331,
20359, 20404, 20409, 20430, 20504,
20516, 20521, 23187, 23195, 23203,
23949, 23950, 23955, 24330, 24339,
24352, 24360, 24408, 24409, 24415
`\if_int_odd:w`

- [86](#), [738](#), [5111](#), [5242](#), [5445](#),
[5455](#), [5967](#), [7196](#), [7204](#), [7224](#), [11893](#),
[11940](#), [11952](#), [13213](#), [13963](#), [14245](#),
[15544](#), [15958](#), [15997](#), [16007](#), [16050](#),
[16074](#), [16244](#), [17593](#), [17869](#), [18243](#),
[18251](#), [18263](#), [18659](#), [18949](#), [24434](#)
- `\if_meaning:w` [21](#), [348](#), [349](#), [361](#), [490](#),
[656](#), [1331](#), [1661](#), [1780](#), [1795](#), [1813](#),
[1863](#), [1868](#), [1877](#), [1942](#), [1960](#), [1970](#),
[1988](#), [2141](#), [2153](#), [2270](#), [2333](#), [2380](#),
[2381](#), [2645](#), [2668](#), [2677](#), [3223](#), [3235](#),
[3248](#), [3259](#), [3274](#), [3522](#), [3586](#), [3654](#),
[4033](#), [4100](#), [4123](#), [4283](#), [4321](#), [4477](#),
[4559](#), [4776](#), [4794](#), [4813](#), [4821](#), [5132](#),
[5182](#), [5187](#), [5188](#), [5367](#), [6140](#), [6146](#),
[6172](#), [6185](#), [6193](#), [6329](#), [6351](#), [6635](#),
[6650](#), [6672](#), [6688](#), [7398](#), [7437](#), [7475](#),
[7478](#), [7540](#), [7622](#), [7663](#), [8017](#), [8055](#),
[9554](#), [9921](#), [9984](#), [10415](#), [10439](#),
[10456](#), [10467](#), [11385](#), [11399](#), [11411](#),
[11421](#), [11481](#), [11490](#), [11581](#), [11596](#),
[11598](#), [11746](#), [11820](#), [11823](#), [11826](#),
[11870](#), [11880](#), [11892](#), [11905](#), [11906](#),
[11925](#), [11926](#), [11940](#), [11941](#), [11952](#),
[11953](#), [12011](#), [12050](#), [12085](#), [12088](#),
[12104](#), [12111](#), [12176](#), [12179](#), [12240](#),
[12241](#), [12242](#), [12358](#), [12471](#), [12477](#),
[12706](#), [12948](#), [13017](#), [13214](#), [13232](#),
[13350](#), [13377](#), [13378](#), [13379](#), [13380](#),
[13381](#), [13382](#), [13560](#), [13572](#), [13573](#),
[13601](#), [13612](#), [13622](#), [13693](#), [13728](#),
[13742](#), [13788](#), [13795](#), [13871](#), [13883](#),
[13983](#), [13986](#), [13997](#), [14048](#), [14121](#),
[14189](#), [14192](#), [14199](#), [14232](#), [14233](#),
[14236](#), [14648](#), [14659](#), [14839](#), [14849](#),
[14896](#), [14995](#), [15074](#), [15123](#), [15137](#),
[15323](#), [15335](#), [15348](#), [15351](#), [15354](#),
[15357](#), [15383](#), [15484](#), [15488](#), [15543](#),
[16000](#), [16053](#), [16115](#), [16116](#), [16118](#),
[16119](#), [16139](#), [16156](#), [16222](#), [16320](#),
[16382](#), [16423](#), [16488](#), [16541](#), [16546](#),
[16699](#), [16871](#), [16872](#), [17384](#), [17414](#),
[17442](#), [17541](#), [17907](#), [18231](#), [18536](#),
[18539](#), [18956](#), [19364](#), [19542](#), [19553](#),
[19568](#), [19704](#), [19730](#), [20054](#), [20282](#),
[20358](#), [20416](#), [20452](#), [23061](#), [24437](#)
- `\if_mode_horizontal:` [21](#), [1341](#), [6489](#)
- `\if_mode_inner:` [21](#), [1341](#), [6491](#)
- `\if_mode_math:` [21](#), [1341](#), [6493](#)
- `\if_mode_vertical:` [21](#), [1341](#), [6487](#), [22488](#)
- `\if_predicate:w` [96](#), [98](#), [103](#), [6240](#), [6310](#)
- `\if_true:` [21](#), [98](#), [349](#), [1331](#)
- `\if_vbox:N` [227](#), [20910](#), [20916](#)
- `\ifabsdim` [958](#)
- `\ifabsnum` [959](#)
- `\ifcase` [398](#)
- `\ifcat` [399](#)
- `\ifcsname` [637](#)
- `\ifdbbox` [1131](#)
- `\ifddir` [1132](#)
- `\ifdefined` [158](#), [638](#)
- `\ifdim` [400](#)
- `\ifeof` [401](#)
- `\iffalse` [402](#)
- `\iffontchar` [639](#)
- `\ifhbox` [403](#)
- `\ifhmode` [404](#)
- `\ifincsname` [783](#)
- `\ifinner` [405](#)
- `\ifmdir` [1133](#)
- `\ifmmode` [406](#)
- `\ifnum` [45](#), [60](#), [89](#), [95](#), [100](#), [164](#), [179](#), [407](#)
- `\ifodd` [408](#)
- `\ifpdfabsdim` [742](#)
- `\ifpdfabsnum` [743](#)
- `\ifpdfprimitive` [744](#)
- `\ifprimitive` [860](#)
- `\iftbox` [1134](#)
- `\iftdir` [1135](#)
- `\iftrue` [409](#)
- `\ifvbox` [410](#)
- `\ifvmode` [411](#)
- `\ifvoid` [412](#)
- `\ifx` [14](#), [21](#),
[39](#), [43](#), [49](#), [90](#), [92](#), [98](#), [123](#), [145](#), [146](#), [413](#)
- `\ifybox` [1136](#)
- `\ifydir` [1137](#)
- `\ignoreligaturesinfont` [960](#)
- `\ignorespaces` [414](#)
- `\IJ` [24219](#)
- `\ij` [24219](#)
- image internal commands:
 - `\l__image_decode_tl` [25209](#), [25210](#), [25220](#),
[25254](#), [25258](#), [25259](#), [25346](#), [25371](#),
[25372](#), [25410](#), [25413](#), [25414](#), [25432](#)
 - `__image_extract_bb:n` [25341](#), [25348](#), [25783](#), [25784](#)
 - `\l__image_interpolate_bool` [25211](#), [25221](#), [25253](#), [25260](#),
[25347](#), [25373](#), [25409](#), [25415](#), [25433](#)
 - `\l__image_llx_dim` [25232](#), [25402](#), [25463](#)
 - `\l__image_lly_dim` [25233](#), [25403](#), [25464](#)
 - `\l__image_page_int` [25205](#), [25225](#), [25226](#), [25264](#), [25265](#),
[25339](#), [25369](#), [25370](#), [25396](#), [25397](#),
[25425](#), [25438](#), [25439](#), [25486](#), [25487](#)

- \l__image_pagebox_tl 1004, 25206, 25224, 25266, 25267, 25340, 25367, 25368, 25398, 25400, 25426, 25447, 25448, 25488
- _image_read_bb:n 24839, 25335
- \l__image_tmp_box 25269, 25271, 25272, 25474, 25475, 25476
- \l__image_urx_dim 25236, 25271, 25276, 25404, 25467, 25478
- \l__image_ury_dim 25238, 25272, 25278, 25405, 25468, 25476, 25480, 25790, 25791
- \l__image_utx_dim 25475
- \immediate 415
- in 199
- \indent 416
- inf 198
- inherit commands:
 - .inherit:n 173, 10901
- \inhibitglue 1138
- \inhibitxspcode 1139
- \initcatcodetable 892
- initial commands:
 - .initial:n 174, 10903
- \input 50, 159, 160, 417
- \inputlineno 418
- \insert 419
- \insertht 961
- \insertpenalties 420
- int commands:
 - \c_eight 85, 5942
 - \c_eleven 85, 5942
 - \c_fifteen 85, 5942
 - \c_five 85, 5942
 - \l_foo_int 213
 - \c_four 85, 5942
 - \c_fourteen 85, 5942
 - \int_abs:n 75, 5123, 6017
 - \int_add:Nn . 77, 5287, 9703, 17851, 18951, 19524, 19525, 19739, 19829
 - \int_case:nn 79, 418, 5412, 5585, 5591
 - \int_case:nnn 22436
 - \int_case:nnTF 24, 79, 5025, 5412, 5417, 5422, 6933, 19205, 20799, 22436, 23841, 23896
 - \int_compare:nNnTF 77, 78, 79, 79, 80, 80, 3045, 3075, 3089, 3093, 3118, 3730, 3737, 4153, 4155, 4164, 4405, 4938, 4945, 5223, 5229, 5398, 5436, 5491, 5499, 5508, 5514, 5532, 5535, 5546, 5581, 5669, 5675, 5681, 5701, 5855, 5874, 5876, 5918, 6000, 6022, 6024, 6396, 6972, 6974, 6979, 6988, 7008, 9337, 9435, 10113, 13282, 16349, 16447, 16449, 16738, 16847, 17705, 17887, 17898, 18057, 18359, 18361, 19113, 19706, 19925, 19933, 20108, 20379, 20818, 22395, 22596, 22938, 22945, 22946, 22947, 22967, 23081, 23523, 23525, 23528, 23567, 23709, 23731, 23763, 23766, 23800, 23803, 23810, 23823, 23938, 24379, 25225, 25264, 25369, 25396, 25438, 25486
 - \int_compare:nTF 78, 80, 80, 80, 80, 87, 187, 542, 5345, 5463, 5471, 5480, 5486, 6015, 6017, 6038, 9249, 9276, 9405, 16498, 20565, 20779, 20780, 20785, 20786
 - \int_compare_p:n 78, 5345
 - \int_compare_p:nNn 21, 78, 5398, 19016, 19017, 22371, 23788, 23883, 23884, 23885, 23930, 24237, 24238, 24262, 24263
 - \int_const:Nn 76, 5217, 5884, 5885, 5886, 5887, 5888, 5889, 5890, 5891, 5892, 5893, 5894, 5895, 5896, 5897, 5942, 5943, 5944, 5945, 5946, 5947, 5948, 5949, 5950, 5951, 5952, 5953, 5954, 5955, 5956, 5957, 5958, 5959, 5960, 5961, 5962, 5963, 5964, 5965, 5980, 7227, 7246, 9178, 9332, 9333, 11366, 11367, 11368, 11369, 11370, 11371, 11372, 11459, 11460, 11461, 11463, 11464, 11465, 11468, 11469, 11470, 11865, 12123, 12124, 12125, 12126, 12127, 12128, 12129, 12130, 12131, 12132, 12133, 12134, 12135, 12136, 12137, 16623, 16624, 16625, 16913, 17786, 17787, 17788, 17789, 18192, 18193, 18194, 18195, 18196, 18197, 18201, 18202, 18203, 18204, 18205, 18206, 18207, 18208, 18209, 18210, 18211, 18212, 18213, 22337, 22339, 22341, 22342, 22343, 23172, 23210, 25273, 25391
 - \int_decr:N 77, 5303, 17026, 17027, 17028, 17071, 17072, 17081, 17082, 17091, 17092, 17377, 19779, 20098, 20164, 20360
 - \int_div_round:nn 75, 5167
 - \int_div_truncate:nn 76, 76, 5167, 5596, 5694, 5714, 22340, 23960, 23966, 23968, 23978
 - \int_do_until:nn 80, 5461
 - \int_do_until:nNnn 79, 5489
 - \int_do_while:nn 80, 5461
 - \int_do_while:nNnn 79, 5489

- \int_eval:n 14, 23, 24, 28, 75,
75, 76, 77, 78, 78, 79, 86, 87, 243,
314, 403, 422, 609, 651, 673, 675,
863, 943, 951, 2150, 2166, 3428,
3433, 3723, 3731, 3739, 4226, 4273,
4310, 4931, 4939, 4947, 5013, 5116,
5415, 5420, 5425, 5430, 5550, 5578,
5664, 5666, 5796, 5806, 5841, 5852,
5858, 5869, 5900, 5937, 5941, 5999,
6007, 6011, 6033, 6035, 6906, 6915,
6966, 6976, 6990, 6997, 7012, 9235,
9390, 9648, 10122, 11376, 13261,
17208, 17209, 19141, 19143, 19145,
19149, 19337, 19339, 19348, 19365,
19366, 19368, 19369, 19608, 19638,
20569, 20614, 20615, 20805, 20948,
20958, 22278, 22950, 22969, 22976,
23045, 23084, 23286, 23945, 23978,
23980, 24321, 24325, 24396, 24406
- \int_from_alph:n 83, 5839
- \int_from_base:nn
. 84, 5856, 5879, 5881, 5883
- \int_from_bin:n 83, 5878, 22437
- \int_from_binary:n 22437
- \int_from_hex:n 84, 5878, 22438
- \int_from_hexadecimal:n 22438
- \int_from_oct:n 84, 5878, 22439
- \int_from_octal:n 22439
- \int_from_roman:n 84, 5898
- \int_gadd:Nn 77, 5287
- \int_gdecr:N
. 77, 3389, 4051, 4990, 5303,
5576, 6867, 8072, 9318, 13552, 17630
- \int_gincr:N 77, 3383, 4041,
4982, 5303, 5555, 5562, 5997, 6860,
8067, 9309, 13531, 13538, 17615,
25390, 25701, 25827, 25883, 25928
- .int_gset:N 174, 10911
- \int_gset:Nn 77, 405, 5319, 8259
- \int_gset_eq:NN 76, 5267, 25820
- \int_gsub:Nn 77, 5287
- \int_gzero:N . . . 76, 5255, 5264, 25812
- \int_gzero_new:N 76, 5261
- \int_if_even:nTF 79, 5441, 9002
- \int_if_even_p:n 79, 5441
- \int_if_exist:NTF . 77, 5262, 5264,
5275, 5912, 5916, 18876, 18930, 25380
- \int_if_exist_p:N 77, 5275
- \int_if_odd:nTF 79, 5441, 14763
- \int_if_odd_p:n 79, 5441, 19252
- \int_incr:N 77, 5303,
10707, 16934, 17036, 17037, 17291,
17300, 17418, 17460, 17472, 17490,
17744, 17745, 18783, 19170, 19357,
19450, 19740, 19776, 19778, 19855,
20086, 20150, 20302, 20357, 20426
- \int_log:N 84, 5938
- \int_log:n 84, 5940
- \int_max:nn 76, 754, 5123,
14624, 15712, 19474, 20508, 20509
- \int_min:nn 76, 5123
- \int_mod:nn 76, 5167, 5586,
5685, 5705, 16734, 22338, 22963, 23980
- \int_new:N 76, 76,
5209, 5225, 5231, 5262, 5264, 5975,
5976, 5977, 5978, 5993, 6499, 9457,
9460, 9462, 9474, 10526, 16828,
16829, 16830, 16831, 16832, 16833,
16834, 16835, 16836, 16837, 16838,
17243, 17244, 17315, 17316, 17317,
17318, 17770, 17771, 17772, 17784,
18190, 18191, 18198, 18199, 18216,
19269, 19271, 19272, 19273, 19276,
19642, 19643, 19644, 19645, 19646,
19647, 19648, 19649, 19650, 19651,
19654, 19655, 19656, 19885, 20271,
20274, 20275, 20276, 20824, 24738,
25351, 25750, 25830, 25831, 25909
- \int_rand:nn
. 242, 246, 756, 944, 22597, 22602,
22923, 22982, 23075, 23134, 24295
- .int_set:N 174, 10911
- \int_set:Nn . . . 23, 77, 2322, 3046,
3103, 5319, 9294, 9296, 9441, 9443,
9458, 9468, 9480, 9515, 9521, 9531,
10711, 16841, 16843, 16845, 16868,
16869, 16884, 16892, 16893, 16905,
16906, 16917, 16918, 16919, 16936,
16939, 17372, 17435, 17732, 18957,
19270, 19332, 19334, 19415, 19470,
19471, 19484, 19495, 19519, 19537,
19586, 19675, 19697, 19715, 19804,
19839, 20307, 20456, 20481, 20957,
20959, 20967, 20968, 20969, 20970
- \int_set_eq:NN 76, 5267,
16885, 16927, 17842, 18297, 18300,
18308, 18309, 18345, 18397, 18690,
18782, 18791, 18878, 19292, 19309,
19355, 19356, 19406, 19516, 19517,
19569, 19624, 19677, 19680, 19694,
19696, 19699, 19710, 19713, 19741,
19742, 19746, 19879, 20417, 25808
- \int_show:N 84, 5934
- \int_show:n 84, 424, 943, 5936
- \int_step_... 215
- \int_step_function:nnnN 81,
414, 653, 5517, 5575, 7290, 7295,
7298, 9349, 19747, 20373, 20484, 20492

- \int_step_inline:nnnn . . . [81](#), [654](#),
[5553](#), [6002](#), [9187](#), [9357](#), [19691](#), [20829](#)
- \int_step_variable:nnnNn . . . [81](#), [5553](#)
- \int_sub:Nn [77](#), [5287](#), [9711](#),
[17846](#), [18495](#), [19572](#), [19580](#), [19589](#)
- \int_to_Alph:n [82](#), [83](#), [5599](#)
- \int_to_alph:n [82](#), [82](#), [83](#), [5599](#)
- \int_to_arabic:n [81](#), [5578](#)
- \int_to_Base:n [83](#)
- \int_to_base:n [83](#)
- \int_to_Base:nn . . . [83](#), [84](#), [5663](#), [5790](#)
- \int_to_base:nn
. [83](#), [84](#), [5663](#), [5786](#), [5788](#), [5792](#)
- \int_to_bin:n . . . [82](#), [83](#), [83](#), [5785](#), [22440](#)
- \int_to_binary:n [22440](#)
- \int_to_Hex:n [83](#), [84](#), [5785](#), [20545](#)
- \int_to_hex:n [83](#), [84](#), [5785](#), [22441](#)
- \int_to_hexadecimal:n [22441](#)
- \int_to_oct:n [83](#), [84](#), [5785](#), [22442](#)
- \int_to_octal:n [22442](#)
- \int_to_Roman:n [83](#), [84](#), [5793](#)
- \int_to_roman:n [83](#), [84](#), [5793](#)
- \int_to_symbols:nnn
. [82](#), [82](#), [5579](#), [5601](#), [5633](#)
- \int_until_do:nn [80](#), [5461](#)
- \int_until_do:nNnn [80](#), [5489](#)
- \int_use:N
[75](#), [77](#), [603](#), [608](#), [3385](#), [3387](#), [4043](#),
[4047](#), [4983](#), [4989](#), [5327](#), [5558](#), [5565](#),
[6862](#), [6864](#), [8066](#), [8074](#), [8175](#), [8701](#),
[9296](#), [9311](#), [9437](#), [10712](#), [13534](#),
[13541](#), [17251](#), [17262](#), [17617](#), [18325](#),
[18391](#), [18455](#), [18466](#), [18476](#), [18480](#),
[18491](#), [18492](#), [18498](#), [18499](#), [18505](#),
[18506](#), [18673](#), [19252](#), [19325](#), [19327](#),
[19345](#), [19346](#), [19347](#), [19448](#), [19461](#),
[19462](#), [19792](#), [19840](#), [19870](#), [19965](#),
[19977](#), [20056](#), [20307](#), [20547](#), [20819](#),
[25226](#), [25265](#), [25283](#), [25370](#), [25383](#),
[25395](#), [25397](#), [25487](#), [25703](#), [25733](#),
[25886](#), [25892](#), [25899](#), [25931](#), [25939](#)
- \int_while_do:nn [80](#), [5461](#)
- \int_while_do:nNnn [80](#), [5489](#)
- \int_zero:N [76](#), [76](#), [5255](#), [5262](#),
[9566](#), [10704](#), [17277](#), [17278](#), [17373](#),
[17374](#), [17375](#), [17473](#), [18307](#), [18493](#),
[18914](#), [19201](#), [19291](#), [19674](#), [19695](#),
[19948](#), [20301](#), [25205](#), [25339](#), [25425](#)
- \int_zero_new:N [76](#), [5261](#)
- \c_max_int [85](#), [800](#), [851](#), [5964](#),
[17817](#), [17831](#), [19742](#), [20945](#), [20951](#)
- \c_nine [85](#), [5942](#)
- \c_one
[85](#), [425](#), [5305](#), [5308](#), [5311](#), [5314](#), [5942](#)
- \c_seven [85](#), [5942](#)
- \c_six [85](#), [5942](#)
- \c_sixteen [85](#), [5942](#)
- \c_ten [85](#), [5942](#)
- \c_thirteen [85](#), [5942](#)
- \c_three [85](#), [5942](#)
- \g_tmpa_int [85](#), [5975](#)
- \l_tmpa_int [2](#), [85](#), [208](#), [5975](#)
- \g_tmpb_int [85](#), [5975](#)
- \l_tmpb_int [2](#), [85](#), [5975](#)
- \c_twelve [85](#), [5942](#)
- \c_two [85](#), [5942](#)
- \c_zero [85](#), [291](#), [307](#), [307](#), [951](#), [1381](#),
[1917](#), [1919](#), [5223](#), [5256](#), [5258](#), [5332](#),
[5340](#), [5532](#), [5535](#), [5942](#), [6495](#), [6497](#)
- int internal commands:
 - __int_abs:N [5123](#)
 - __int_case:nnTF [5412](#)
 - __int_case:nw [5412](#)
 - __int_case_end:nw [5412](#)
 - __int_compare:nnN [410](#), [5345](#)
 - __int_compare:NNw [410](#), [410](#), [5345](#)
 - __int_compare:Nw [409](#), [410](#), [5345](#)
 - __int_compare:w [409](#), [5345](#)
 - __int_compare_!=:NNw [5345](#)
 - __int_compare_<:NNw [5345](#)
 - __int_compare_<=:NNw [5345](#)
 - __int_compare_=:NNw [5345](#)
 - __int_compare_==:NNw [5345](#)
 - __int_compare_>:NNw [5345](#)
 - __int_compare_>=:NNw [5345](#)
 - __int_compare_end=:NNw [410](#), [5345](#)
 - __int_constdef:Nw [5217](#)
 - __int_div_truncate:NwNw [5167](#)
 - __int_eval:n [87](#), [2123](#), [4143](#),
[4203](#), [5120](#), [6443](#), [7052](#), [7054](#), [7122](#),
[7124](#), [7128](#), [7130](#), [7134](#), [7136](#), [7140](#),
[7142](#), [7171](#), [17869](#), [18135](#), [18949](#),
[19518](#), [19848](#), [19923](#), [20028](#), [23171](#)
 - __int_eval:w [23](#), [87](#), [87](#), [87](#), [403](#),
[404](#), [409](#), [602](#), [603](#), [604](#), [617](#), [631](#),
[661](#), [669](#), [670](#), [673](#), [677](#), [704](#), [716](#),
[4147](#), [4160](#), [4178](#), [4183](#), [4208](#), [4209](#),
[4221](#), [4257](#), [5111](#), [5117](#), [5119](#), [5121](#),
[5122](#), [5124](#), [5128](#), [5135](#), [5136](#), [5141](#),
[5142](#), [5148](#), [5149](#), [5154](#), [5155](#), [5169](#),
[5170](#), [5174](#), [5176](#), [5177](#), [5194](#), [5197](#),
[5198](#), [5202](#), [5203](#), [5204](#), [5220](#), [5239](#),
[5284](#), [5289](#), [5292](#), [5295](#), [5298](#), [5321](#),
[5324](#), [5348](#), [5382](#), [5400](#), [5402](#), [5406](#),
[5442](#), [5445](#), [5452](#), [5455](#), [5519](#), [5520](#),
[5521](#), [5526](#), [5527](#), [5528](#), [5722](#), [5749](#),
[5755](#), [5782](#), [6062](#), [6111](#), [7175](#), [7176](#),
[7182](#), [9600](#), [9609](#), [9633](#), [9645](#), [11393](#),

11502, 11505, 11611, 11939, 11943,
 11955, 11956, 11984, 12067, 12071,
 12110, 12298, 12303, 12344, 12433,
 12444, 12493, 12524, 12530, 12531,
 12577, 12587, 12589, 12605, 12607,
 12630, 12632, 12770, 12930, 13178,
 13361, 13753, 13761, 13782, 13784,
 13805, 13807, 13816, 13818, 13847,
 13853, 13863, 13865, 13939, 13941,
 13957, 13959, 13963, 13979, 14019,
 14027, 14029, 14031, 14033, 14035,
 14037, 14039, 14058, 14060, 14070,
 14072, 14098, 14101, 14109, 14111,
 14131, 14134, 14137, 14140, 14148,
 14151, 14154, 14157, 14164, 14166,
 14172, 14180, 14182, 14184, 14190,
 14210, 14212, 14221, 14223, 14244,
 14265, 14269, 14281, 14284, 14287,
 14290, 14293, 14296, 14299, 14302,
 14306, 14318, 14322, 14326, 14329,
 14350, 14352, 14354, 14364, 14403,
 14405, 14414, 14448, 14453, 14455,
 14462, 14465, 14468, 14471, 14474,
 14477, 14486, 14498, 14506, 14508,
 14518, 14520, 14527, 14536, 14538,
 14541, 14544, 14547, 14550, 14563,
 14565, 14573, 14575, 14583, 14585,
 14594, 14597, 14600, 14607, 14622,
 14640, 14643, 14699, 14713, 14715,
 14721, 14734, 14736, 14738, 14762,
 14778, 14785, 14786, 14809, 14825,
 14829, 14874, 14876, 14918, 14929,
 14948, 14950, 14952, 14965, 14978,
 14983, 14985, 14991, 15008, 15009,
 15010, 15011, 15012, 15013, 15018,
 15020, 15022, 15024, 15026, 15030,
 15032, 15034, 15036, 15038, 15040,
 15062, 15070, 15154, 15203, 15416,
 15437, 15439, 15442, 15445, 15448,
 15451, 15467, 15493, 15503, 15519,
 15686, 15718, 15727, 15909, 15910,
 15933, 15943, 15952, 15970, 15979,
 15986, 15997, 16007, 16040, 16050,
 16075, 16084, 16101, 16138, 16155,
 16157, 16169, 16170, 16210, 16221,
 16232, 16290, 16408, 16509, 16545,
 16642, 16648, 16664, 16685, 17001,
 17262, 17329, 17499, 17557, 17567,
 17571, 17575, 17598, 19901, 19902,
 19913, 20435, 22927, 22928, 22933,
 22934, 24334, 24341, 24354, 24362
 __int_eval_end:
 87, 87, 87, 5111, 5119,
 5122, 5128, 5178, 5194, 5205, 5239,
 5289, 5292, 5295, 5298, 5321, 5324,
 5401, 5406, 5445, 5455, 5722, 5749,
 5755, 5782, 11393, 11493, 11614,
 11984, 12081, 12085, 13178, 13361,
 13963, 13998, 14186, 14508, 14643,
 15467, 15519, 15719, 15728, 15997,
 16007, 16050, 16075, 16101, 16170,
 16643, 16649, 16665, 16685, 17571
 __int_from_alph:N 421, 5839
 __int_from_alph:nN 421, 5839
 __int_from_base:N 422, 5856
 __int_from_base:nnN 422, 5856
 __int_from_roman:NN 5898
 \c__int_from_roman_C_int 5884
 \c__int_from_roman_c_int 5884
 \c__int_from_roman_D_int 5884
 \c__int_from_roman_d_int 5884
 __int_from_roman_error:w 5898
 \c__int_from_roman_I_int 5884
 \c__int_from_roman_i_int 5884
 \c__int_from_roman_L_int 5884
 \c__int_from_roman_l_int 5884
 \c__int_from_roman_M_int 5884
 \c__int_from_roman_m_int 5884
 \c__int_from_roman_V_int 5884
 \c__int_from_roman_v_int 5884
 \c__int_from_roman_X_int 5884
 \c__int_from_roman_x_int 5884
 __int_maxmin:wwN 5123
 __int_mod:ww 5167
 __int_pass_signs:wn
 421, 5829, 5843, 5860
 __int_pass_signs_end:wn 5829
 __int_rand:ww 22923
 __int_rand_narrow:n 22923
 __int_rand_narrow:nn
 941, 22949, 22955, 22968
 __int_rand_narrow:nnn 22923
 __int_rand_narrow:nnnn .. 941, 22923
 __int_show:nN 5934
 __int_step:NnnnN 5517
 __int_step:NNnnnn 5553
 __int_step:wwwN 5517
 __int_tmp:w 407, 407, 5279,
 5287, 5290, 5293, 5296, 5319, 5322
 __int_to_Base:nn 5663
 __int_to_base:nn 5663
 __int_to_Base:nnN 5663
 __int_to_base:nnN 5663
 __int_to_Base:nnnnN 5663
 __int_to_base:nnnnN 5663
 __int_to_Letter:n 5663
 __int_to_letter:n 5663
 __int_to_roman:N 5793

__int_to_roman:w	14131, 14134, 14137, 14140, 14148,
..... 87, 410, 420, 1362,	14151, 14154, 14157, 14164, 14166,
5111, 5358, 5796, 5806, 7285, 7308,	14172, 14180, 14182, 14184, 14210,
11505, 12505, 12537, 14945, 15212	14212, 14221, 14223, 14227, 14244,
__int_to_Roman_aux:N 5805, 5808, 5811	14265, 14269, 14281, 14284, 14287,
__int_to_Roman_c:w 5793	14290, 14293, 14296, 14299, 14302,
__int_to_roman_c:w 5793	14306, 14318, 14322, 14326, 14329,
__int_to_Roman_d:w 5793	14350, 14352, 14354, 14364, 14388,
__int_to_roman_d:w 5793	14391, 14403, 14405, 14411, 14414,
__int_to_Roman_i:w 5793	14435, 14448, 14453, 14455, 14462,
__int_to_roman_i:w 5793	14465, 14468, 14471, 14474, 14477,
__int_to_Roman_l:w 5793	14486, 14498, 14506, 14508, 14518,
__int_to_roman_l:w 5793	14520, 14527, 14536, 14538, 14541,
__int_to_Roman_m:w 5793	14544, 14547, 14550, 14563, 14565,
__int_to_roman_m:w 5793	14573, 14575, 14583, 14585, 14594,
__int_to_Roman_Q:w 5793	14597, 14600, 14607, 14622, 14640,
__int_to_roman_Q:w 5793	14643, 14699, 14713, 14715, 14721,
__int_to_Roman_v:w 5793	14734, 14736, 14738, 14762, 14778,
__int_to_roman_v:w 5793	14785, 14786, 14829, 14831, 14832,
__int_to_Roman_x:w 5793	14833, 14874, 14876, 14911, 14918,
__int_to_roman_x:w 5793	14925, 14946, 14948, 14950, 14952,
__int_to_symbols:nnnn 5579	14965, 14969, 14970, 14971, 14972,
__int_value:w 87,	14973, 14978, 14983, 14985, 14991,
87, 403, 409, 439, 542, 584, 591,	15008, 15009, 15010, 15011, 15012,
604, 610, 617, 620, 625, 632, 651,	15013, 15018, 15020, 15022, 15024,
659, 667, 675, 738, 750, 780, 1621,	15026, 15030, 15032, 15034, 15036,
1919, 4147, 4148, 4160, 4178, 4183,	15038, 15040, 15062, 15070, 15086,
4207, 4208, 4209, 4221, 4257, 5111,	15091, 15095, 15154, 15203, 15214,
5119, 5127, 5128, 5140, 5141, 5142,	15401, 15437, 15439, 15442, 15445,
5153, 5154, 5155, 5174, 5176, 5177,	15448, 15451, 15458, 15461, 15463,
5194, 5202, 5203, 5204, 5348, 5352,	15467, 15489, 15491, 15519, 15686,
5382, 5526, 5527, 5528, 5749, 5782,	15718, 15727, 15909, 15910, 15911,
6022, 6033, 6062, 6111, 6121, 6342,	15933, 15943, 15952, 15970, 15979,
6345, 6443, 7175, 7176, 7182, 9600,	15986, 15996, 16040, 16049, 16084,
9609, 9959, 11443, 11444, 11445,	16138, 16155, 16210, 16221, 16232,
11446, 11447, 11519, 11580, 11598,	16408, 16471, 16509, 16537, 16545,
11611, 11939, 12053, 12067, 12069,	16547, 16549, 16636, 16642, 16648,
12071, 12074, 12110, 12245, 12275,	16658, 16664, 16725, 16734, 16741,
12276, 12289, 12298, 12428, 12433,	16759, 17001, 17329, 17341, 17517,
12435, 12444, 12448, 12485, 12493,	17555, 17557, 17567, 17575, 17594,
12496, 12502, 12513, 12524, 12530,	17596, 17604, 18053, 18524, 18530,
12531, 12534, 12577, 12587, 12589,	18562, 18564, 18573, 18574, 18697,
12605, 12607, 12630, 12644, 12722,	19090, 19104, 19848, 19901, 19902,
12724, 12770, 12852, 13272, 13376,	19913, 20399, 20431, 20433, 21512,
13703, 13704, 13705, 13707, 13753,	21544, 21545, 21546, 21548, 21674,
13756, 13759, 13782, 13784, 13805,	21683, 21685, 21690, 21691, 21692,
13807, 13816, 13818, 13822, 13840,	21693, 21697, 21698, 21699, 21700,
13847, 13853, 13863, 13865, 13879,	21725, 21731, 21733, 21735, 21737,
13887, 13895, 13939, 13941, 13957,	21742, 21747, 21752, 21759, 21766,
13959, 13962, 13965, 14019, 14027,	21897, 21927, 21928, 21967, 21986,
14029, 14031, 14033, 14035, 14037,	21992, 22162, 22618, 22620, 22642,
14039, 14058, 14060, 14064, 14070,	22644, 22669, 22709, 22736, 22744,
14072, 14076, 14098, 14101, 14109,	22770, 22772, 22776, 22778, 22807,
14111, 14114, 14115, 14116, 14117,	22821, 22828, 22933, 22934, 23075,

- 23084, 24334, 24341, 24354, 24362
- intarray internal commands:
- __intarray_count:N 88,
 - 88, 88, 6005, 6015, 6029, 6038, 6042
 - \g__intarray_font_int 5993, 5997, 5998
 - __intarray_gset:Nnn 88, 6006
 - __intarray_gset_aux:Nnn 6006
 - __intarray_gset_fast:Nnn ... 88,
 - 6006, 19693, 19769, 19771, 19773,
 - 19796, 19799, 19853, 20333, 20335,
 - 20341, 20349, 20351, 20354, 20420,
 - 20422, 20424, 20437, 20442, 20444
 - __intarray_item:Nn 88, 6032
 - __intarray_item_aux:Nn 6032
 - __intarray_item_fast:Nn 88,
 - 6032, 19764, 19785, 19788, 19806,
 - 19833, 19894, 19895, 19918, 19919,
 - 19926, 19929, 19930, 19934, 19937,
 - 19938, 19989, 19990, 20338, 20466
 - __intarray_new:Nn
... 88, 5994, 17781, 17782, 17783,
 - 19657, 19658, 20277, 20278, 20279
 - \interactionmode 640
 - \interlinepenalties 641
 - \interlinepenalty 421
- ior commands:
- \ior_close:N
..... 147, 147, 147, 9042, 9226, 9247
 - \ior_get:NN
..... 148, 148, 149, 153, 9288, 9304
 - \ior_get_str:NN 9821
 - \ior_if_eof:N 523
 - \ior_if_eof:Ntf
... 150, 9037, 9051, 9272, 9316, 9323
 - \ior_if_eof_p:N 150, 9272
 - \ior_list_streams: 9825
 - \ior_log_list: . 147, 9259, 9827, 9828
 - \ior_log_streams: 9825
 - \ior_map_break: 149, 9299, 9317
 - \ior_map_break:n 150, 9299
 - \ior_map_inline:Nn 149, 9303
 - \ior_new:N 147, 9202, 9330
 - \ior_open:Nn 147, 515, 9204
 - \ior_open:NnTF
..... 147, 9205, 9207, 9217, 9218
 - \ior_show_list: 147, 9259, 9825, 9826
 - \ior_str_get:NN
..... 148, 9290, 9306, 9821, 9822
 - \ior_str_map_inline:Nn 149, 9303
 - \c_term_ior
... 153, 9178, 9202, 9249, 9255, 9276
- ior internal commands:
- \l_ior_internal_tl 9303
 - __ior_list:N 9259
 - __ior_map_inline:Nn 9303
 - __ior_map_inline:Nnn 9303
 - __ior_map_inline_loop:NNN ... 9303
 - __ior_new:N 520, 9220, 9234
 - __ior_open:Nn
..... 154, 9035, 9050, 9213, 9224
 - __ior_open_stream:Nn 9224
 - \l_ior_stream_tl
..... 9184, 9227, 9235, 9243
 - \g__ior_streams_prop
..... 9185, 9244, 9252, 9266
 - \g__ior_streams_seq
..... 9179, 9227, 9253, 9254
- iow commands:
- \iow_char:N 151, 1594, 8709,
 - 8711, 8712, 8785, 8786, 8990, 9456,
 - 15320, 17196, 17199, 17224, 17225,
 - 17232, 17233, 18039, 18041, 18043,
 - 18045, 18047, 18049, 18630, 18631,
 - 19135, 19242, 19243, 19244, 19265,
 - 20529, 20532, 20535, 20538, 20542,
 - 20545, 20580, 20589, 20593, 20598,
 - 20618, 20620, 20621, 20622, 20625,
 - 20627, 20632, 20635, 20636, 20639,
 - 20641, 20645, 20647, 20653, 20655,
 - 20659, 20661, 20665, 20670, 20671,
 - 20713, 20715, 20720, 20722, 20728,
 - 20733, 20738, 20742, 20752, 20755,
 - 20759, 20760, 20764, 20772, 20835
 - \iow_close:N 147, 147, 9381, 9403
 - \iow_indent:n
..... 152, 152, 529, 530, 8650,
 - 9494, 9524, 9528, 11281, 11778, 11790
 - \l_iow_line_count_int
..... 152, 152, 530,
 - 794, 9457, 9532, 9568, 17707, 17711
 - \iow_list_streams: 9825
 - \iow_log:n 23, 150, 299, 1636, 2031,
 - 3768, 8248, 8249, 8250, 8394, 9451
 - \iow_log_list: . 147, 9415, 9831, 9832
 - \iow_log_streams: 9825
 - \iow_new:N 147, 9372
 - \iow_newline: 151,
 - 151, 151, 152, 154, 365, 494, 527,
 - 8204, 8220, 8222, 9168, 9455, 9522,
 - 9529, 17657, 19173, 22272, 22273,
 - 22274, 23018, 23020, 23023, 23030
 - \iow_now:Nn 150, 150, 150, 151, 151,
 - 9445, 9451, 9452, 9453, 9454, 23226
 - \iow_open:Nn 147, 9378
 - \iow_shipout:Nn
..... 151, 151, 151, 527, 9430, 23245
 - \iow_shipout_x:Nn
..... 151, 151, 151, 527, 9427

- \iow_show_list: 147, 9415, 9829, 9830
 - \iow_term:n 150, 2031, 8218,
8254, 8255, 8256, 8420, 9451, 20820
 - \iow_wrap:nnnN . 63, 141, 142, 142,
151, 151, 152, 152, 152, 365, 530,
943, 3753, 3768, 8196, 8197, 8249,
8255, 8392, 8399, 9497, 9509, 9512
 - \c_log_iow
.... 153, 523, 9332, 9405, 9451, 9452
 - \c_term_iow 153, 523, 9332,
9349, 9372, 9405, 9411, 9453, 9454
 - iow internal commands:
 - __iow_indent:n 529, 9494, 9524
 - __iow_indent_error:n 529, 9494, 9528
 - \l__iow_indent_int
.. 9473, 9566, 9584, 9695, 9703, 9711
 - \l__iow_indent_tl 9473,
9567, 9583, 9694, 9704, 9712, 9713
 - \l__iow_line_break_bool
..... 9477, 9562, 9689,
9702, 9710, 9718, 9720, 9725, 9727
 - \l__iow_line_part_tl
. 532, 533, 9475, 9564, 9576, 9597,
9654, 9657, 9688, 9701, 9709, 9732
 - \l__iow_line_target_int
... 535, 9460, 9531, 9690, 9695, 9721
 - \l__iow_line_tl
... 9475, 9563, 9580, 9669, 9685,
9701, 9709, 9731, 9732, 9737, 9739
 - __iow_list:N 9415
 - __iow_new:N 9374, 9389
 - \l__iow_newline_tl
..... 9459, 9529, 9530, 9532, 9736
 - \l__iow_one_indent_int
..... 9461, 9703, 9711
 - \l__iow_one_indent_tl 528, 9461, 9704
 - __iow_open_stream:Nn 9378
 - __iow_set_indent:n 528, 9461
 - \l__iow_stream_tl
..... 9354, 9382, 9390, 9398
 - \g__iow_streams_prop
..... 9355, 9399, 9408, 9422
 - \g__iow_streams_seq
..... 9343, 9382, 9409, 9410
 - __iow_tmp:w
533, 9570, 9594, 9650, 9682, 9741, 9747
 - __iow_unindent:w ... 528, 9461, 9713
 - __iow_with:Nnn
.. 154, 365, 494, 527, 3757, 3759,
8225, 8227, 8422, 8424, 9433, 9447
 - __iow_with_aux:nNnn 9433
 - __iow_wrap_break:w 9636, 9650
 - __iow_wrap_break_end:w ... 533, 9650
 - __iow_wrap_break_first:w 9650
 - __iow_wrap_break_loop:w 9650
 - __iow_wrap_break_none:w 9650
 - __iow_wrap_chunk:nw
..... 9568, 9570, 9705, 9714, 9721
 - __iow_wrap_do: 9533, 9537
 - __iow_wrap_end: 9716
 - __iow_wrap_end:n 9723
 - __iow_wrap_end_chunk:w
..... 531, 9588, 9595, 9686
 - \c__iow_wrap_end_marker_tl 9479, 9542
 - __iow_wrap_fix_newline:w 9537
 - __iow_wrap_indent: 9699
 - __iow_wrap_indent:n 9699
 - \c__iow_wrap_indent_marker_tl ...
..... 9479, 9502
 - __iow_wrap_line:nw
.... 531, 534, 9582, 9586, 9595, 9693
 - __iow_wrap_line_aux:Nw 9595
 - __iow_wrap_line_end:NnnnnnnN 9595
 - __iow_wrap_line_end:nw
..... 533, 9595, 9670, 9671, 9680
 - __iow_wrap_line_loop:w 9595
 - \c__iow_wrap_marker_tl
..... 529, 531, 9479, 9594
 - __iow_wrap_newline: 9716
 - __iow_wrap_newline:n 9716
 - \c__iow_wrap_newline_marker_tl ...
..... 531, 9479, 9557
 - __iow_wrap_next:nw . 9570, 9648, 9690
 - __iow_wrap_next_line:w .. 9642, 9683
 - __iow_wrap_start:w 9537
 - __iow_wrap_store_do:n
..... 9641, 9719, 9726, 9729
 - \l__iow_wrap_tl ... 530, 531, 535,
535, 9478, 9527, 9535, 9539, 9541,
9544, 9546, 9549, 9565, 9733, 9735
 - __iow_wrap_trim:N
..... 535, 9671, 9719, 9726, 9741
 - __iow_wrap_trim:w 9741
 - __iow_wrap_unindent: 9699
 - __iow_wrap_unindent:n 9707
 - \c__iow_wrap_unindent_marker_tl ...
..... 9479, 9504
- J**
- \J 197
 - \j 24229
 - \jcharwidowpenalty 1140
 - \jfam 1141
 - \jfont 1142
 - \jis 1143
 - job commands:
 - \c_job_name_tl 22434
 - \jobname 422

K		
\k	24233	545, 546, 547, 548, 549, 550, 551,
\kanjiskip	1144	552, 553, 554, 555, 556, 557, 558,
\kansuji	1145	559, 560, 561, 562, 563, 564, 565,
\kansujichar	1146	566, 567, 568, 569, 570, 571, 572,
\kcatcode	1147	573, 574, 575, 576, 577, 578, 579,
\kchar	1165	580, 581, 582, 583, 584, 585, 586,
\kchardef	1166	587, 588, 589, 590, 591, 592, 593,
\kern	423	594, 595, 596, 597, 598, 599, 600,
kernel internal commands:		601, 602, 603, 604, 605, 606, 607,
_kernel_check_defined:NTF	24,	608, 609, 610, 611, 612, 613, 614,
459, 491, 2286, 2305, 3749, 5096,		615, 616, 617, 618, 619, 620, 621,
6074, 6297, 7029, 8088, 16810, 20231		622, 623, 624, 625, 626, 627, 628,
_l_kernel_expl_bool		629, 630, 631, 632, 633, 634, 635,
7, 235, 238, 253, 267		636, 637, 638, 639, 640, 641, 642,
_kernel_primitive:NN		643, 644, 645, 646, 647, 648, 649,
268, 275, 284, 285,		650, 651, 652, 653, 654, 655, 656,
286, 287, 288, 289, 290, 291, 292,		657, 658, 659, 660, 661, 662, 663,
293, 294, 295, 296, 297, 298, 299,		664, 665, 666, 667, 668, 669, 670,
300, 301, 302, 303, 304, 305, 306,		671, 672, 673, 674, 675, 676, 677,
307, 308, 309, 310, 311, 312, 313,		678, 679, 680, 681, 682, 683, 684,
314, 315, 316, 317, 318, 319, 320,		685, 686, 687, 688, 689, 690, 691,
321, 322, 323, 324, 325, 326, 327,		692, 693, 694, 695, 696, 697, 698,
328, 329, 330, 331, 332, 333, 334,		699, 700, 701, 702, 703, 704, 705,
335, 336, 337, 338, 339, 340, 341,		706, 707, 708, 709, 710, 711, 712,
342, 343, 344, 345, 346, 347, 348,		713, 714, 715, 716, 717, 718, 719,
349, 350, 351, 352, 353, 354, 355,		720, 721, 722, 723, 724, 725, 726,
356, 357, 358, 359, 360, 361, 362,		727, 728, 729, 730, 731, 732, 733,
363, 364, 365, 366, 367, 368, 369,		734, 735, 736, 737, 738, 739, 740,
370, 371, 372, 373, 374, 375, 376,		741, 742, 743, 744, 745, 746, 747,
377, 378, 379, 380, 381, 382, 383,		748, 749, 750, 751, 752, 753, 754,
384, 385, 386, 387, 388, 389, 390,		755, 756, 757, 758, 759, 760, 761,
391, 392, 393, 394, 395, 396, 397,		762, 763, 764, 765, 766, 767, 768,
398, 399, 400, 401, 402, 403, 404,		769, 770, 771, 772, 773, 774, 775,
405, 406, 407, 408, 409, 410, 411,		776, 777, 778, 779, 780, 781, 782,
412, 413, 414, 415, 416, 417, 418,		783, 784, 785, 786, 787, 788, 789,
419, 420, 421, 422, 423, 424, 425,		790, 791, 796, 808, 809, 810, 811,
426, 427, 428, 429, 430, 431, 432,		812, 813, 814, 815, 816, 817, 818,
433, 434, 435, 436, 437, 438, 439,		819, 820, 821, 822, 823, 824, 825,
440, 441, 442, 443, 444, 445, 446,		826, 827, 828, 829, 830, 831, 832,
447, 448, 449, 450, 451, 452, 453,		833, 834, 835, 836, 837, 838, 839,
454, 455, 456, 457, 458, 459, 460,		840, 841, 842, 843, 844, 845, 846,
461, 462, 463, 464, 465, 466, 467,		847, 848, 849, 850, 851, 852, 853,
468, 469, 470, 471, 472, 473, 474,		854, 855, 856, 857, 858, 859, 860,
475, 476, 477, 478, 479, 480, 481,		861, 862, 863, 864, 865, 866, 867,
482, 483, 484, 485, 486, 487, 488,		868, 869, 870, 871, 872, 873, 874,
489, 490, 491, 492, 493, 494, 495,		875, 876, 877, 878, 879, 880, 881,
496, 497, 498, 499, 500, 501, 502,		882, 883, 884, 885, 886, 887, 888,
503, 504, 505, 506, 507, 508, 509,		889, 890, 891, 892, 893, 894, 895,
510, 511, 512, 513, 514, 515, 516,		896, 897, 898, 899, 900, 901, 902,
517, 518, 519, 520, 521, 522, 523,		903, 904, 905, 906, 907, 908, 909,
524, 525, 526, 527, 528, 529, 530,		910, 911, 912, 913, 914, 915, 916,
531, 532, 533, 534, 535, 536, 537,		917, 918, 919, 920, 921, 922, 923,
538, 539, 540, 541, 542, 543, 544,		924, 925, 926, 927, 928, 929, 930,
		931, 932, 933, 934, 935, 936, 937,

- 938, 939, 940, 941, 942, 943, 944,
 945, 946, 947, 948, 949, 950, 951,
 952, 953, 954, 955, 956, 957, 958,
 959, 960, 961, 962, 963, 964, 965,
 966, 967, 968, 969, 970, 971, 972,
 973, 974, 975, 976, 977, 978, 979,
 980, 981, 982, 983, 984, 985, 986,
 987, 988, 989, 990, 991, 992, 993,
 994, 995, 996, 997, 998, 999, 1000,
 1001, 1002, 1003, 1004, 1005, 1006,
 1007, 1008, 1009, 1010, 1011, 1012,
 1013, 1014, 1015, 1016, 1017, 1018,
 1019, 1020, 1021, 1022, 1023, 1024,
 1025, 1026, 1027, 1028, 1029, 1030,
 1031, 1032, 1033, 1034, 1035, 1036,
 1037, 1038, 1039, 1040, 1041, 1042,
 1043, 1044, 1045, 1046, 1047, 1048,
 1049, 1050, 1051, 1052, 1053, 1054,
 1055, 1056, 1057, 1058, 1059, 1060,
 1061, 1062, 1063, 1064, 1065, 1066,
 1067, 1068, 1069, 1070, 1071, 1072,
 1073, 1074, 1075, 1076, 1077, 1078,
 1079, 1080, 1081, 1082, 1083, 1084,
 1085, 1086, 1087, 1088, 1089, 1090,
 1091, 1092, 1093, 1094, 1095, 1096,
 1097, 1098, 1099, 1100, 1101, 1102,
 1103, 1104, 1105, 1106, 1107, 1108,
 1109, 1110, 1111, 1112, 1113, 1114,
 1115, 1116, 1117, 1118, 1119, 1120,
 1121, 1122, 1123, 1124, 1125, 1126,
 1127, 1128, 1129, 1130, 1131, 1132,
 1133, 1134, 1135, 1136, 1137, 1138,
 1139, 1140, 1141, 1142, 1143, 1144,
 1145, 1146, 1147, 1148, 1149, 1150,
 1151, 1152, 1153, 1154, 1155, 1156,
 1157, 1158, 1159, 1160, 1161, 1162,
 1163, 1164, 1165, 1166, 1167, 1168
 __kernel_register_log:N
 24, 2295, 5938, 10135,
 10136, 10265, 10266, 10369, 10370
 __kernel_register_show:N 24, 24,
 364, 2295, 5934, 10131, 10261, 10365
 __kernel_register_show_aux:NN 2295
 __kernel_register_show_aux:nNN 2295
 __kernel_show:NN 2313
 keys commands:
 \l_keys_choice_int
 172, 174, 176, 176,
 177, 10526, 10704, 10707, 10711, 10712
 \l_keys_choice_tl
 172, 174, 176, 177, 10526, 10710
 \keys_define:nn ... 171, 10541, 11279
 \keys_if_choice_exist:nnnTF
 180, 11238
 \keys_if_choice_exist_p:nnn
 180, 11238
 \keys_if_exist:nnTF
 180, 578, 11231, 11255
 \keys_if_exist_p:nn 180, 11231
 \l_keys_key_tl . 178, 10529, 10646,
 10662, 11085, 11171, 11173, 11206
 \keys_log:nn 180, 11246
 \l_keys_path_tl 178, 10533,
 10569, 10588, 10597, 10606, 10610,
 10624, 10639, 10641, 10643, 10655,
 10657, 10659, 10674, 10677, 10681,
 10689, 10690, 10691, 10694, 10708,
 10731, 10736, 10745, 10749, 10756,
 10760, 10764, 10771, 10778, 10789,
 10795, 10799, 10814, 10823, 10831,
 10866, 11067, 11074, 11097, 11100,
 11139, 11143, 11151, 11153, 11154,
 11165, 11168, 11188, 11213, 11214
 \keys_set:nn 170,
 174, 178, 178, 179, 10766, 10771,
 10963, 10987, 10995, 11043, 11052
 \keys_set_filter:nnn 180, 10998
 \keys_set_filter:nnnN ... 180, 10998
 \keys_set_groups:nnn 180, 10998
 \keys_set_known:nn 179, 10973
 \keys_set_known:nnN . 179, 573, 10973
 \keys_show:nn 180, 180, 11246
 \l_keys_value_tl 178,
 10539, 10814, 11142, 11145, 11147,
 11155, 11175, 11184, 11198, 11208
 keys internal commands:
 __keys_bool_set:Nn
 .. 10635, 10840, 10842, 10844, 10846
 __keys_bool_set_inverse:Nn
 .. 10651, 10848, 10850, 10852, 10854
 __keys_check_groups: . 11101, 11109
 __keys_choice_find:n . 10668, 11211
 __keys_choice_make:
 .. 10638, 10654, 10667, 10698, 10856
 __keys_choice_make:N 10667
 __keys_choice_make_aux:N 10667
 __keys_choices_make:nn
 .. 10697, 10858, 10860, 10862, 10864
 __keys_choices_make:Nnn 10697
 __keys_cmd_set:nn
 10639, 10641, 10643, 10655,
 10657, 10659, 10690, 10691, 10708,
 10717, 10764, 10771, 10831, 10866
 \c_keys_code_root_tl
 10519, 10719, 10724, 10760, 11151,
 11154, 11171, 11173, 11181, 11183,
 11195, 11197, 11234, 11242, 11260

```

\c__keys_default_root_tl .....
.. 10519, 10731, 10736, 11139, 11143
\__keys_default_set:n 10648, 10664,
10726, 10876, 10878, 10880, 10882
\__keys_define:n ..... 10546, 10550
\__keys_define:nn ..... 10546, 10550
\__keys_define:nnn ..... 10541
\__keys_define_aux:nn ..... 10550
\__keys_define_code:n . 10564, 10614
\__keys_define_code:w ..... 10614
\__keys_execute: .....
.. 11078, 11105, 11127, 11131, 11149
\__keys_execute:nn 11149, 11213, 11214
\__keys_execute_unknown: ..... 11149
\l__keys_filtered_bool .....
10535, 11011, 11019, 11021, 11025,
11033, 11035, 11104, 11125, 11130
\__keys_find_key_module:w .... 11055
\l__keys_groups_clist ... 10528,
10742, 10743, 10750, 11099, 11114
\c__keys_groups_root_tl .....
.. 10519, 10745, 10749, 11097, 11100
\__keys_groups_set:n .. 10740, 10900
\__keys_inherit:n ..... 10753, 10902
\c__keys_inherit_root_tl .....
..... 10519, 10756, 11165, 11168
\__keys_initialise:n .....
.. 10758, 10904, 10906, 10908, 10910
\__keys_keys_set_known:nn .... 10973
\__keys_meta_make:n ... 10762, 10920
\__keys_meta_make:nn .. 10762, 10922
\l__keys_module_tl .....
10530, 10542, 10545, 10547, 10590,
10591, 10597, 10767, 10964, 10967,
10969, 11058, 11063, 11073, 11079,
11087, 11089, 11181, 11183, 11188
\__keys_multichoice_find:n .....
..... 10670, 11211
\__keys_multichoice_make: .....
..... 10667, 10700, 10924
\__keys_multichoices_make:nn ...
.. 10697, 10926, 10928, 10930, 10932
\l__keys_no_value_bool .....
10531, 10552, 10557, 10616, 10811,
10820, 11057, 11062, 11137, 11207
\l__keys_only_known_bool .....
.. 10532, 10986, 10994, 10996, 11161
\__keys_parent:n ..... 10674,
10677, 10681, 11165, 11168, 11218
\__keys_parent:w ..... 11218
\__keys_property_find:n 10562, 10573
\__keys_property_find:w ..... 10573
\__keys_property_search:w .....
..... 10598, 10602, 10611

\l__keys_property_tl .....
..... 10534, 10563, 10566,
10569, 10575, 10576, 10582, 10594,
10607, 10619, 10620, 10623, 10627
\c__keys_props_root_tl ... 10525,
10563, 10620, 10627, 10839, 10841,
10843, 10845, 10847, 10849, 10851,
10853, 10855, 10857, 10859, 10861,
10863, 10865, 10867, 10869, 10871,
10873, 10875, 10877, 10879, 10881,
10883, 10885, 10887, 10889, 10891,
10893, 10895, 10897, 10899, 10901,
10903, 10905, 10907, 10909, 10911,
10913, 10915, 10917, 10919, 10921,
10923, 10925, 10927, 10929, 10931,
10933, 10935, 10937, 10939, 10941,
10943, 10945, 10947, 10949, 10951,
10953, 10955, 10957, 10959, 10961
\__keys_remove_spaces:n .. 10545,
10575, 10708, 10967, 11071, 11213,
11229, 11234, 11242, 11253, 11260
\l__keys_selective_bool .....
.. 10535, 11042, 11051, 11053, 11076
\l__keys_selective_seq .....
.. 10537, 11038, 11041, 11046, 11112
\__keys_set:n ..... 10968, 11055
\__keys_set:nn ..... 10968, 11055
\__keys_set:nnn ..... 10963
\__keys_set_aux: ..... 11055
\__keys_set_aux:nnn ..... 11055
\__keys_set_filter:nnn ..... 10998
\__keys_set_filter:nnnnN ..... 10998
\__keys_set_groups:nnn ..... 10998
\__keys_set_known:nn .. 10988, 10992
\__keys_set_known:nnnN ..... 10973
\__keys_set_selective: ..... 11055
\__keys_set_selective:nn ..... 10998
\__keys_set_selective:nnn .... 10998
\__keys_set_selective:nnnn ... 10998
\__keys_show:Nnn ..... 11246
\__keys_store_unused: .....
..... 11106, 11126, 11132, 11149
\l__keys_tmp_bool .....
..... 10540, 11111, 11118, 11123
\c__keys_type_root_tl .....
..... 10519, 10674, 10677, 10689
\__keys_undefine: 10755, 10772, 10958
\l__keys_unused_clist ..... 572,
10538, 10974, 10978, 10980, 10981,
10999, 11003, 11005, 11006, 11204
\__keys_validate_cleanup:w ... 10782
\__keys_validate_forbidden: .. 10782
\__keys_validate_required: ... 10782

```


<code>\c__keys_validate_root_tl</code>	13kernel.filemdfivesum	254, 24541
.. 10519 , 10789 , 10795 , 10799 , 11153	13kernel.filemoddate	254, 24553
<code>__keys_value_or_default:n</code>	13kernel.filesize	254, 24598
..... 11075 , 11135	13kernel.strcmp	254, 24608
<code>__keys_value_requirement:nn</code>	<code>\label</code>	24281
..... 10782 , 10960 , 10962	<code>\language</code>	424
<code>__keys_variable_set:NnnN</code>	<code>\lastallocatedread</code>	4447, 4448
.... 10828 , 10868 , 10870 , 10872 ,	<code>\lastallocatedtoks</code>	16899
10874 , 10884 , 10886 , 10888 , 10890 ,	<code>\lastbox</code>	425
10892 , 10894 , 10896 , 10898 , 10912 ,	<code>\lastkern</code>	426
10914 , 10916 , 10918 , 10934 , 10936 ,	<code>\lastlinefit</code>	642
10938 , 10940 , 10942 , 10944 , 10946 ,	<code>\lastnamedcs</code>	893
10948 , 10950 , 10952 , 10954 , 10956	<code>\lastnodetype</code>	643
keyval commands:	<code>\lastpenalty</code>	427
<code>\keyval_parse:NNn</code>	<code>\lastsavedboxresourceindex</code>	962
..... 182 , 10385 , 10546 , 10968	<code>\lastsavedimageresourceindex</code>	963
keyval internal commands:	<code>\lastsavedimageresourcepages</code>	964
<code>__keyval_action:</code>	<code>\lastskip</code>	428
<code>__keyval_def:Nn</code> . 10466 , 10482 , 10507	<code>\lastxpos</code>	965
<code>__keyval_def_aux:n</code>	<code>\lastypos</code>	966
<code>__keyval_def_aux:w</code>	<code>\latelua</code>	894
<code>__keyval_empty_key:</code> .. 10501 , 10505	LaTeX3 error commands:	
<code>\l__keyval_key_tl</code>	<code>\LaTeX3_error:</code>	510
.. 10382 , 10466 , 10467 , 10478 , 10486	<code>\lccode</code>	166,
<code>__keyval_loop:NNw</code> 10388 , 10394 , 10454	181 , 194 , 196 , 198 , 200 , 202 , 205 , 429	
<code>__keyval_sanitise_aux:w</code>	<code>\leaders</code>	430
<code>__keyval_sanitise_comma:</code>	<code>\left</code>	431
..... 10393 , 10398	left commands:	
<code>__keyval_sanitise_comma_auxi:w</code> .	<code>\c_left_brace_str</code> 62 , 4420 , 18084 ,	
..... 10398	18442 , 18446 , 18466 , 18480 , 18504 ,	
<code>__keyval_sanitise_comma_auxii:w</code>	18961 , 19038 , 20034 , 20069 , 20090	
..... 10398	<code>\leftghost</code>	943
<code>__keyval_sanitise_equals:</code>	<code>\lefthyphenmin</code>	432
..... 10392 , 10398	<code>\leftmarginkern</code>	784
<code>__keyval_sanitise_equals_auxi:w</code>	<code>\leftskip</code>	433
..... 10398	<code>\legno</code>	434
<code>__keyval_sanitise_equals_-</code>	<code>\let</code>	1, 40, 272, 273, 435
<code>auxii:w</code>	<code>\lsetcharcode</code>	895
10398	<code>\letterspacefont</code>	785
<code>\l__keyval_sanitise_tl</code>	<code>\limits</code>	436
.... 10384 , 10391 , 10395 , 10404 ,	<code>\LineBreak</code>	80, 81, 82, 83, 84,
10406 , 10410 , 10417 , 10419 , 10428 ,	85 , 86 , 87 , 105 , 112 , 113 , 114 , 122 , 124	
10430 , 10434 , 10441 , 10443 , 10452	<code>\linedir</code>	944
<code>__keyval_split:NNw</code> .. 10459 , 10464	<code>\linepenalty</code>	437
<code>__keyval_split_tidy:w</code>	<code>\lineskip</code>	438
10464	<code>\lineskiplimit</code>	439
<code>__keyval_split_value:NNw</code>	<code>\linewidth</code>	21576, 21622
10464	<code>\ln</code>	15426, 15429
<code>\l__keyval_value_tl</code>	<code>ln</code>	195
..... 10382 , 10482 , 10487	<code>\localbrokenpenalty</code>	945
<code>\kuten</code>	<code>\localinterlinepenalty</code>	946
1148 , 1167	<code>\lcalleftbox</code>	947
	<code>\lcalrightbox</code>	948
	<code>\loccount</code>	9195, 9365
L		
<code>\L</code>		24220
<code>\l</code>		24220
13kernel		24506
13kernel.charcat		254, 24535

- \loctoks 16871, 16872, 16898
- \long 275, 440, 7500, 7504
- \LongText 76, 110, 134
- \looseness 441
- \lower 442
- \lowercase 443
- \lpcode 786
- lua commands:
 - \lua_escape:n 254, 24470
 - \lua_escape_x:n ... 254, 22860, 24470
 - \lua_now:n 253, 24470
 - \lua_now_x:n 253, 22857, 24470
 - \lua_shipout:n 253, 24470
 - \lua_shipout_x:n 253, 24470
- \luaescapestring 896
- \luafunction 897
- luatex commands:
 - \luatex_alignmark:D 863, 1222
 - \luatex_aligntab:D 864, 1223
 - \luatex_attribute:D 865, 1224
 - \luatex_attributedef:D ... 866, 1225
 - \luatex_automaticallyhyphenpenalty:D 867
 - \luatex_begincsname:D 868
 - \luatex_bodydir:D 941, 1257, 1320
 - \luatex_boxdir:D 942, 1258
 - \luatex_catcodetable:D 869, 1226
 - \luatex_clearmarks:D 870, 1227
 - \luatex_crampeddisplaystyle:D ...
 - 871, 1228
 - \luatex_crampedscriptscriptstyle:D
 - 872, 1229
 - \luatex_crampedscriptstyle:D ...
 - 873, 1230
 - \luatex_crampedtextstyle:D 874, 1231
 - \luatex_directlua:D
 - 875, 1215, 1216, 3889, 7225, 7228,
 - 7234, 9335, 22850, 23176, 23215, 24470
 - \luatex_dviextension:D 876
 - \luatex_dvifeedback:D 877
 - \luatex_dvivariable:D 878
 - \luatex_etoksapp:D 879
 - \luatex_etokspre:D 880
 - \luatex_expanded:D ... 882, 1313, 3902
 - \luatex_explicithyphenpenalty:D 881
 - \luatex_firstvalidlanguage:D .. 883
 - \luatex_fontid:D 884, 1232
 - \luatex_formatname:D 885, 1233
 - \luatex_gleaders:D 891, 1234
 - \luatex_hjcode:D 886
 - \luatex_hpack:D 887
 - \luatex_hyphenationbounds:D ... 888
 - \luatex_hyphenationmin:D 889
 - \luatex_hyphenpenaltymode:D ... 890
 - \luatex_if_engine:TF
 - 22444, 22445, 22446
 - \luatex_if_engine_p: 22443
 - \luatex_initcatcodetable:D 892, 1235
 - \luatex_lastnamedcs:D 893
 - \luatex_latelua:D
 - 894, 1236, 23234, 24472
 - \luatex_leftghost:D 943, 1259
 - \luatex_letcharcode:D 895
 - \luatex_linedir:D 944
 - \luatex_localbrokenpenalty:D ...
 - 945, 1260
 - \luatex_localinterlinepenalty:D .
 - 946, 1261
 - \luatex_localleftbox:D 947, 1262
 - \luatex_localrightbox:D ... 948, 1263
 - \luatex_luaescapestring:D .. 369,
 - 896, 1237, 3900, 23218, 23237, 24475
 - \luatex_luafunction:D 897, 1238
 - \luatex luatexbanner:D 898
 - \luatex luatexdatestamp:D 899
 - \luatex luatexrevision:D 900
 - \luatex luatexversion:D
 - 901, 1276, 1295,
 - 1382, 3885, 5243, 5968, 9337, 22351
 - \luatex_mathdir:D 949, 1264
 - \luatex_mathdisplayskipmode:D .. 902
 - \luatex_matheqnogapstep:D 903
 - \luatex_mathnolimitsmode:D 904
 - \luatex_mathoption:D 905
 - \luatex_mathrulesfam:D 906
 - \luatex_mathscriptsmode:D 907
 - \luatex_mathstyle:D 908, 1239
 - \luatex_mathsurroundmode:D 909
 - \luatex_mathsurroundskip:D 910
 - \luatex_nohrule:D 911
 - \luatex_nokerns:D 912, 1240
 - \luatex_noligs:D 913, 1241
 - \luatex_nospaces:D 914
 - \luatex_novrule:D 915
 - \luatex_outputbox:D 916, 1242
 - \luatex_pagebottomoffset:D 917, 1265
 - \luatex_pagedir:D 950, 1266, 1321
 - \luatex_pageleftoffset:D .. 918, 1243
 - \luatex_pagerightoffset:D . 919, 1268
 - \luatex_pagetopoffset:D ... 920, 1244
 - \luatex_pardir:D 951, 1270
 - \luatex_pdfextension:D
 - 921, 24741, 24742,
 - 24766, 24767, 25125, 25126, 25132,
 - 25133, 25138, 25139, 25144, 25145
 - \luatex_pdffeedback:D 922
 - \luatex_pdfvariable:D 923
 - \luatex_postexhyphenchar:D 924, 1245

<code>\luatex_posthyphenchar:D</code> ..	925, 1246	<code>\luatexpageheight</code>	1267
<code>\luatex_predisplaygapfactor:D</code> ..	926	<code>\luatexpageleftoffset</code>	1243
<code>\luatex_preexhyphenchar:D</code> ..	927, 1247	<code>\luatexpagerightoffset</code>	1268
<code>\luatex_prehyphenchar:D</code> ...	928, 1248	<code>\luatexpagetopoffset</code>	1244
<code>\luatex_rightghost:D</code>	952, 1271	<code>\luatexpagewidth</code>	1269
<code>\luatex_savecatcodetable:D</code> ..	929, 1249	<code>\luatexpardir</code>	1270
<code>\luatex_scantextokens:D</code> ...	930, 1250	<code>\luatexpostexhyphenchar</code>	1245
<code>\luatex_setfontid:D</code>	931	<code>\luatexposthyphenchar</code>	1246
<code>\luatex_shapemode:D</code>	932	<code>\luatexpreeexhyphenchar</code>	1247
<code>\luatex_suppressifcsnameerror:D</code> ..	933, 1251	<code>\luatexprehyphenchar</code>	1248
<code>\luatex_suppresslongerror:D</code> ..	934, 1252	<code>\luatexrevision</code>	900
<code>\luatex_suppressmathparerror:D</code> ..	935, 1253	<code>\luatexrightghost</code>	1271
<code>\luatex_suppressoutererror:D</code> ..	936, 1254	<code>\luatexsavecatcodetable</code>	1249
<code>\luatex_textdir:D</code>	953, 1272	<code>\luatexscantextokens</code>	1250
<code>\luatex_toksapp:D</code>	937	<code>\luatexsuppressfontnotfounderror</code> ..	1221, 1256
<code>\luatex_tokspre:D</code>	938	<code>\luatexsuppressifcsnameerror</code>	1251
<code>\luatex_tpack:D</code>	939	<code>\luatexsuppresslongerror</code>	1252
<code>\luatex_vpack:D</code>	940	<code>\luatexsuppressmathparerror</code>	1253
<code>\luatexalignmark</code>	1222	<code>\luatexsuppressoutererror</code>	1254
<code>\luatexaligntab</code>	1223	<code>\luatextextdir</code>	1272
<code>\luatexattribute</code>	1224	<code>\luatextracingfonts</code>	1217
<code>\luatexattributedef</code>	1225	<code>\luatexUchar</code>	1255
<code>\luatexbanner</code>	898	<code>\luatexversion</code>	45, 100, 901
<code>\luatexbodydir</code>	1257		
<code>\luatexboxdir</code>	1258		
<code>\luatexcatcodetable</code>	1226		
<code>\luatexclearmarks</code>	1227		
<code>\luatexcrampeddisplaystyle</code>	1228		
<code>\luatexcrampedscriptscriptstyle</code> ..	1229		
<code>\luatexcrampedscriptstyle</code>	1230		
<code>\luatexcrampedtextstyle</code>	1231		
<code>\luatexdatestamp</code>	899		
<code>\luatexfontid</code>	1232		
<code>\luatexformatname</code>	1233		
<code>\luatexglleaders</code>	1234		
<code>\luatexinitcatcodetable</code>	1235		
<code>\luatexlatalua</code>	1236		
<code>\luatexleftghost</code>	1259		
<code>\luatexlocalbrokenpenalty</code>	1260		
<code>\luatexlocalinterlinepenalty</code>	1261		
<code>\luatexlocalleftbox</code>	1262		
<code>\luatexlocalrightbox</code>	1263		
<code>\luatexluaescapestring</code>	1237		
<code>\luatexluafunction</code>	1238		
<code>\luatexmathdir</code>	1264		
<code>\luatexmathstyle</code>	1239		
<code>\luatexnokerns</code>	1240		
<code>\luatexnoligs</code>	1241		
<code>\luatexoutputbox</code>	1242		
<code>\luatexpagebottomoffset</code>	1265		
<code>\luatexpagedir</code>	1266		

<code>\mathrulesfam</code>	906	<code>\msg_critical:nnnnnn</code>	138, 8342
<code>\mathscrtsmode</code>	907	<code>\msg_critical_text:n</code>	137, 8261 , 8345
<code>\mathstyle</code>	908	<code>\msg_error:nn</code>	139, 8353
<code>\mathsurround</code>	459	<code>\msg_error:nnn</code>	139, 8353
<code>\mathsurroundmode</code>	909	<code>\msg_error:nnnn</code>	139, 8353
<code>\mathsurroundskip</code>	910	<code>\msg_error:nnnnn</code>	139, 8353
<code>max</code>	195	<code>\msg_error:nnnnnn</code>	139, 242 , 8353
max commands:		<code>\msg_error_text:n</code> ...	137, 8261 , 8360
<code>\c_max_char_int</code>	85, 5965 , 18057 , 20547	<code>\msg_expandable_error:nn</code> .	243, 22985
<code>\c_max_register_int</code>	85, 215 , 763 , 764 ,	<code>\msg_expandable_error:nnn</code>	243, 22985
1382 , 5111 , 8701 , 16843 , 16869 ,		<code>\msg_expandable_error:nnnn</code>	243, 22985
16906 , 16914 , 16918 , 17292 , 17301		<code>\msg_expandable_error:nnnnn</code>	243, 22985
max internal commands:		<code>\msg_expandable_error:nnnnnn</code> ...	243, 22985
<code>\c_max_constdef_int</code>	5217	<code>\msg_fatal:nn</code>	138, 8331
<code>\maxdeadcycles</code>	460	<code>\msg_fatal:nnn</code>	138, 8331
<code>\maxdepth</code>	461	<code>\msg_fatal:nnnn</code>	138, 8331
<code>\mdfivesum</code>	859	<code>\msg_fatal:nnnnn</code>	138, 8331
<code>\meaning</code>	462	<code>\msg_fatal:nnnnnn</code>	138, 8331
<code>\medmuskip</code>	463	<code>\msg_fatal_text:n</code> ...	137, 8261 , 8334
<code>\message</code>	464	<code>\msg_gset:nnn</code>	136, 8118
<code>\MessageBreak</code>	122	<code>\msg_gset:nnnn</code>	136, 8118
meta commands:		<code>\msg_if_exist:nnTF</code>	137, 8103 , 8112 , 8444
<code>.meta:n</code>	174, 10919	<code>\msg_if_exist_p:nn</code>	137, 8103
<code>.meta:nn</code>	174, 10921	<code>\msg_info:nn</code>	139, 8382
<code>\middle</code>	645	<code>\msg_info:nnn</code>	139, 8382
<code>min</code>	195	<code>\msg_info:nnnn</code>	139, 8382
minus commands:		<code>\msg_info:nnnnn</code>	139, 8382
<code>\c_minus_inf_fp</code>	190,	<code>\msg_info:nnnnnn</code> .	139, 139 , 8382 , 8616
198 , 11361 , 14008 , 14090 , 14901 , 15678		<code>\msg_info_text:n</code> ...	138, 8261 , 8386
<code>\c_minus_zero_fp</code>	189, 11361 , 14004 , 16327	<code>\msg_interrupt:nnn</code>	141, 8182 , 8333 , 8344 , 8359
<code>\mkern</code>	465	<code>\msg_line_context:</code>	137, 493 , 2029 , 2036, 2805 , 8109 , 8175 , 8264 , 8269 , 8274, 8279 , 8284 , 8783 , 8800 , 10720
<code>mm</code>	199	<code>\msg_line_number:</code> ...	137, 8175 , 10513
mode commands:		<code>\msg_log:n</code>	142, 8246 , 8384
<code>\mode_if_horizontal:TF</code>	103, 6488	<code>\msg_log:nn</code>	139, 8390
<code>\mode_if_horizontal_p:</code>	103, 6488	<code>\msg_log:nnn</code>	139, 8390
<code>\mode_if_inner:TF</code>	103, 6490	<code>\msg_log:nnnn</code>	139, 8390
<code>\mode_if_inner_p:</code>	103, 6490	<code>\msg_log:nnnnn</code>	139, 8390
<code>\mode_if_math:TF</code>	103, 6492	<code>\msg_log:nnnnnn</code>	139, 8390
<code>\mode_if_math_p:</code>	103, 6492	<code>\msg_log:nnnnnnn</code>	139, 5092 , 7025 , 7038 , 8084 , 8390 , 9152 , 9260 , 9416 , 11249 , 22263
<code>\mode_if_vertical:TF</code>	103, 6486	<code>\msg_log_eval:Nn</code> .	243, 5941 , 6288 , 10138 , 10268 , 10372 , 16816 , 23012
<code>\mode_if_vertical_p:</code>	103, 6486	<code>\msg_new:nnn</code>	136, 8118 , 8567
<code>\mode_leave_vertical:</code>	239, 22036 , 22481	<code>\msg_new:nnnn</code> ...	136, 492 , 8118 , 8565
<code>\month</code>	466	<code>\msg_none:nn</code>	140, 8396
<code>\moveleft</code>	467	<code>\msg_none:nnn</code>	140, 8396
<code>\moveright</code>	468	<code>\msg_none:nnnn</code>	140, 8396
msg commands:		<code>\msg_none:nnnnn</code>	140, 8396
<code>\msg_critical:nn</code>	138, 8342		
<code>\msg_critical:nn(nn)</code>	242		
<code>\msg_critical:nnnn</code>	138, 8342		
<code>\msg_critical:nnnnn</code>	138, 8342		
<code>\msg_critical:nnnnnn</code>	138, 8342		

- \msg_none:nnnnnn [140](#), [8396](#)
- \msg_redirect_class:nn [140](#), [8516](#)
- \msg_redirect_module:nnn .. [141](#), [8516](#)
- \msg_redirect_name:nnn [141](#), [8507](#)
- \msg_see_documentation_text:n ...
..... [138](#), [8286](#), [8337](#), [8348](#), [8363](#)
- \msg_set:nnn [136](#), [8118](#), [8571](#)
- \msg_set:nnnn [136](#), [8118](#), [8569](#)
- \msg_show:nn [243](#), [8397](#)
- \msg_show:nnn [243](#), [8397](#)
- \msg_show:nnnn [243](#), [8397](#)
- \msg_show:nnnnnn [243](#), [8397](#)
- \msg_show:nnnnnn [243](#), [243](#),
[401](#), [459](#), [491](#), [5090](#), [7023](#), [7037](#),
[8082](#), [8397](#), [9151](#), [9259](#), [9415](#), [11247](#),
[17637](#), [17645](#), [20225](#), [20234](#), [22260](#)
- \msg_show_eval:Nn [243](#), [5937](#), [6286](#),
[10134](#), [10264](#), [10368](#), [16814](#), [23012](#)
- \msg_show_item:n
... [243](#), [243](#), [5100](#), [7033](#), [7042](#), [23017](#)
- \msg_show_item:nn [243](#), [491](#), [8092](#), [23017](#)
- \msg_show_item_unbraced:n [243](#), [23017](#)
- \msg_show_item_unbraced:nn . [243](#),
[521](#), [9267](#), [9423](#), [11257](#), [22279](#), [23017](#)
- \msg_term:n [142](#), [8246](#), [8376](#)
- \msg_warning:nn [139](#), [8374](#)
- \msg_warning:nnn [139](#), [8374](#)
- \msg_warning:nnnn [139](#), [8374](#)
- \msg_warning:nnnnnn [139](#), [8374](#), [8615](#)
- \msg_warning_text:n . [137](#), [8261](#), [8378](#)
- msg internal commands:
- __msg_class_chk_exist:nTF
..... [8432](#), [8446](#), [8512](#), [8522](#), [8527](#)
- \l__msg_class_loop_seq . [503](#), [8441](#),
[8531](#), [8539](#), [8549](#), [8550](#), [8553](#), [8555](#)
- __msg_class_new:nn
..... [500](#), [504](#), [8292](#), [8331](#), [8342](#),
[8353](#), [8374](#), [8382](#), [8390](#), [8396](#), [8397](#)
- \l__msg_class_tl [501](#),
[503](#), [8437](#), [8453](#), [8465](#), [8486](#), [8490](#),
[8493](#), [8501](#), [8540](#), [8542](#), [8544](#), [8558](#)
- \c__msg_coding_error_text_tl ...
[144](#), [8143](#), [8621](#), [8629](#), [8655](#), [8673](#),
[8682](#), [8694](#), [8708](#), [8717](#), [8738](#), [8745](#),
[8752](#), [8759](#), [8766](#), [8774](#), [8793](#), [11278](#),
[11299](#), [11305](#), [11312](#), [22287](#), [22298](#)
- \c__msg_continue_text_tl . [8143](#), [8187](#)
- \c__msg_critical_text_tl . [8143](#), [8350](#)
- \l__msg_current_class_tl
..... [502](#), [8437](#), [8448](#),
[8485](#), [8490](#), [8493](#), [8501](#), [8530](#), [8544](#)
- __msg_error:Nnnnnn [8353](#)
- __msg_error_code:nnnnnn [8614](#)
- __msg_expandable_error:n
..... [144](#), [511](#), [8881](#), [8900](#)
- __msg_expandable_error:w . [510](#), [8881](#)
- __msg_expandable_error_module:nn
..... [22985](#)
- __msg_fatal_code:nnnnnn [8610](#)
- \c__msg_fatal_text_tl ... [8143](#), [8339](#)
- \c__msg_help_text_tl [8143](#), [8191](#)
- \l__msg_hierarchy_seq
.... [501](#), [501](#), [8440](#), [8468](#), [8478](#), [8483](#)
- \l__msg_internal_tl . [8099](#), [8421](#), [8427](#)
- __msg_interrupt_more_text:n ...
..... [494](#), [8194](#)
- __msg_interrupt_text:n .. [8197](#), [8208](#)
- __msg_interrupt_wrap:nn
..... [8186](#), [8190](#), [8194](#)
- __msg_kernel_class_new:nN
... [505](#), [8572](#), [8610](#), [8614](#), [8615](#), [8616](#)
- __msg_kernel_class_new_aux:nN [8572](#)
- __msg_kernel_error:nn
... [143](#), [2012](#), [8610](#), [10491](#), [10506](#),
[17067](#), [18034](#), [18289](#), [18318](#), [18360](#),
[18363](#), [19044](#), [20106](#), [20187](#), [21784](#)
- __msg_kernel_error:nnn
..... [143](#), [1466](#), [1474](#), [1481](#),
[1486](#), [1522](#), [1531](#), [1663](#), [1781](#), [1823](#),
[1864](#), [1869](#), [2012](#), [2196](#), [2203](#), [2291](#),
[2669](#), [3146](#), [3844](#), [6227](#), [8435](#), [8610](#),
[9005](#), [9063](#), [10583](#), [10645](#), [10661](#),
[10805](#), [10822](#), [11351](#), [11658](#), [17190](#),
[18061](#), [18125](#), [18324](#), [18513](#), [18890](#),
[18903](#), [18942](#), [19062](#), [19964](#), [19971](#),
[20201](#), [20975](#), [21527](#), [22880](#), [24493](#)
- __msg_kernel_error:nnnn
..... [143](#), [1772](#), [1801](#), [1883](#),
[2012](#), [2041](#), [2165](#), [2753](#), [8114](#), [8460](#),
[8610](#), [10568](#), [10622](#), [10680](#), [10693](#),
[10813](#), [11187](#), [11654](#), [17060](#), [18490](#),
[18555](#), [18771](#), [20110](#), [20126](#), [21676](#)
- __msg_kernel_error:nnnnn
..... [143](#), [1593](#), [6028](#),
[8610](#), [9496](#), [17206](#), [20383](#), [20506](#), [22429](#)
- __msg_kernel_error:nnnnnn
..... [143](#), [2768](#), [6020](#), [8610](#), [22470](#)
- __msg_kernel_expandable_
error:nn [144](#), [2629](#), [4577](#),
[6474](#), [7187](#), [7191](#), [7193](#), [7201](#), [7207](#),
[7775](#), [8898](#), [12208](#), [13007](#), [16614](#), [22975](#)
- __msg_kernel_expandable_
error:nnn [144](#),
[2395](#), [3421](#), [5039](#), [5341](#), [5537](#),
[6086](#), [6948](#), [7850](#), [8898](#), [12213](#),
[12227](#), [12229](#), [12329](#), [12368](#), [12374](#),

- 12711, 12716, 12727, 12734, 12797,
12807, 12949, 12971, 13503, 24484
- _msg_kernel_expandable_-
 error:nnnn 144,
 1624, 8898, 13140, 13161, 13635, 22940
- _msg_kernel_expandable_-
 error:nnnnnn
 ... 144, 6041, 8898, 9508, 11769,
 13285, 16106, 16675, 16689, 22426
- _msg_kernel_expandable_-
 error:nnnnnn 144, 8898
- _msg_kernel_fatal:nn
 143, 8610, 9230, 9385
- _msg_kernel_fatal:nnn ... 143, 8610
- _msg_kernel_fatal:nnnn ... 143, 8610
- _msg_kernel_fatal:nnnnn ... 143, 8610
- _msg_kernel_fatal:nnnnnn 143, 8610
- _msg_kernel_info:nn 143, 8615
- _msg_kernel_info:nnn 143, 8615
- _msg_kernel_info:nnnn ... 143, 8615
- _msg_kernel_info:nnnnn .. 143, 8615
- _msg_kernel_info:nnnnnn . 143, 8615
- _msg_kernel_new:nnn
 142, 8564, 8660, 8662,
 8664, 8666, 8668, 8686, 8789, 8833,
 8835, 8837, 8839, 8841, 8843, 8845,
 8847, 8849, 8856, 8863, 8870, 9754,
 11328, 11797, 11799, 11801, 11803,
 11805, 11807, 13307, 13309, 13311,
 13313, 13315, 13317, 13319, 13321,
 13323, 13325, 13330, 13554, 13556,
 16610, 17721, 20788, 22302, 22981
- _msg_kernel_new:nnnn . 142, 8564,
 8618, 8626, 8634, 8641, 8652, 8670,
 8679, 8691, 8698, 8705, 8714, 8723,
 8729, 8735, 8742, 8749, 8756, 8763,
 8771, 8782, 8790, 8799, 8811, 8823,
 9748, 9760, 9767, 9774, 9779, 10512,
 11266, 11269, 11275, 11284, 11290,
 11296, 11302, 11309, 11316, 11322,
 11631, 11771, 11786, 17195, 17212,
 17219, 17228, 20528, 20534, 20541,
 20549, 20556, 20562, 20572, 20578,
 20602, 20609, 20617, 20624, 20631,
 20638, 20644, 20652, 20658, 20664,
 20673, 20680, 20689, 20692, 20700,
 20706, 20712, 20719, 20726, 20736,
 20747, 20757, 20767, 20776, 20782,
 22284, 22292, 22295, 22886, 24498
- _msg_kernel_set:nnn 142, 8564
- _msg_kernel_set:nnnn 142, 8564
- _msg_kernel_warning:nn
 143, 8615, 18721,
 18722, 18761, 18811, 18847, 18863
- _msg_kernel_warning:nnnn
 143, 8615, 18423, 18569
- _msg_kernel_warning:nnnnn
 143, 1682, 8615
- _msg_kernel_warning:nnnnnn ...
 143, 2786, 8547, 8615, 22475
- \l_msg_line_context_bool
 .. 8100, 8264, 8269, 8274, 8279, 8284
- \c_msg_more_text_prefix_tl
 8101, 8129, 8138, 8356
- \c_msg_no_info_text_tl .. 8143, 8186
- _msg_no_more_text:nnnn 8353
- \c_msg_on_line_text_tl .. 8143, 8178
- _msg_redirect:nnn 8516
- _msg_redirect_loop_chk:nnn ...
 8516, 8558
- _msg_redirect_loop_list:n .. 8516
- \l_msg_redirect_prop
 8439, 8465, 8510, 8513
- \c_msg_return_text_tl
 8143, 8624, 8632, 8639
- _msg_show:n 499, 8397
- _msg_show:nn 8397
- _msg_show:w 8397
- _msg_show_dot:w 8397
- _msg_show_eval:nnN 23012
- \c_msg_text_prefix_tl 8101,
 8105, 8127, 8136, 8336, 8347, 8362,
 8379, 8387, 8393, 8400, 8903, 22990
- _msg_tmp:w 8882, 8895
- \c_msg_trouble_text_tl 8143
- _msg_use:nnnnnnnn 8302, 8442
- _msg_use_code: 501, 8442
- _msg_use_hierarchy:nwN 8442
- _msg_use_redirect_module:n ...
 501, 8442
- _msg_use_redirect_name:n ... 8442
- \mskip 469
- \muexpr 646
- multichoice commands:
 .multichoice: 174, 10923
- multichoices commands:
 .multichoices:nn 174, 10923
- \multiply 470
- \mskip 471, 7507
- muskip commands:
 \c_max_muskip 168, 10373
- \muskip_add:Nn 166, 10338
- \muskip_const:Nn
 166, 10283, 10373, 10374

\muskip_eval:n	478
167, 167, 10287, 10354, 10368, 10372	
\muskip_gadd:Nn	479
166, 10338	
\muskip_gset:Nn	480
167, 10322	
\muskip_gset_eq:NN	967
167, 10330	
\muskip_gsub:Nn	1304
167, 10338	
\muskip_gzero:N	1313
166, 10290, 10301	
\muskip_gzero_new:N	1316
166, 10298	
\muskip_if_exist:NTF	1305
166, 10299, 10301, 10304	
\muskip_if_exist_p:N	1315, 1317
166, 10304	
\muskip_log:N	1306
168, 10369	
\muskip_log:n	1323, 1324
168, 10369	
\muskip_new:N	1307
166, 166, 10275, 10286, 10299,	
10301, 10375, 10376, 10377, 10378	
\muskip_set:Nn	1325
167, 10322	
\muskip_set_eq:NN	1325
167, 10330	
\muskip_show:N	1308
167, 10365	
\muskip_show:n	1309
167, 555, 10367	
\muskip_sub:Nn	1310
167, 10338	
\muskip_use:N	1326
167, 167, 10362, 10363	
\muskip_zero:N	1319
166, 166, 10290, 10299	
\muskip_zero_new:N	1312
166, 10298	
\g_tmpa_muskip	1311
168, 10375	
\l_tmpa_muskip	1318
168, 10375	
\g_tmpb_muskip	914
168, 10375	
\l_tmpb_muskip	
168, 10375	
\c_zero_muskip	notexpanded commands:
168, 10292, 10295, 10373	\notexpanded: <token> 127
\muskipdef	915
472	
\mutoglu	481
647	

N

nan	198
nc	199
nd	199
\newbox	405
\newcatcodetable	52
\newcount	405
\newdimen	405
\newlinechar	103, 473
\next	74, 106,
125, 126, 126, 131, 140, 144, 147, 155	
\NG	24221
\ng	24221
\noalign	474
\noautospace	1149
\noautoxspace	1150
\noboundary	475
\noexpand	118, 122, 133, 136, 476
\nohrule	911
\noindent	477
\nokerns	912
\noligs	913

O

\O	24222
\o	24222
\OE	24223
\oe	24223
\omit	484
one commands:	
\c_minus_one	425, 5979
\c_one_degree_fp	190, 198, 12821, 16819
\openin	485
\openout	486
\or	487
or commands:	
\or:	86, 376,
377, 716, 1331, 2125, 2126, 2127,	
2128, 2129, 2130, 2131, 2132, 2133,	
4187, 4264, 5111, 5724, 5725, 5726,	
5727, 5728, 5729, 5730, 5731, 5732,	
5733, 5734, 5735, 5736, 5737, 5738,	
5739, 5740, 5741, 5742, 5743, 5744,	
5745, 5746, 5747, 5748, 5757, 5758,	
5759, 5760, 5761, 5762, 5763, 5764,	
5765, 5766, 5767, 5768, 5769, 5770,	

5771, 5772, 5773, 5774, 5775, 5776, 5777, 5778, 5779, 5780, 5781, 7247, 7251, 7254, 7258, 7262, 7264, 7266, 7268, 7269, 7271, 7273, 7275, 7277, 9620, 9621, 9622, 9623, 9624, 9625, 9626, 11400, 11401, 11402, 11561, 11576, 11577, 11986, 11987, 12012, 13180, 13181, 13182, 13218, 13704, 13705, 13706, 13829, 13914, 14000, 14001, 14002, 14003, 14004, 14005, 14006, 14007, 14008, 14085, 14088, 14421, 14422, 14436, 14682, 14902, 14927, 14933, 14934, 14935, 14936, 14937, 15085, 15120, 15122, 15130, 15217, 15221, 15222, 15223, 15224, 15225, 15226, 15227, 15228, 15229, 15230, 15237, 15238, 15239, 15240, 15241, 15242, 15243, 15244, 15245, 15246, 15253, 15254, 15255, 15256, 15257, 15258, 15259, 15260, 15261, 15262, 15269, 15270, 15271, 15272, 15273, 15274, 15275, 15276, 15277, 15278, 15285, 15286, 15287, 15288, 15289, 15290, 15291, 15292, 15293, 15294, 15301, 15302, 15303, 15304, 15305, 15306, 15307, 15308, 15309, 15310, 15328, 15379, 15382, 15391, 15502, 15525, 15526, 15587, 15592, 15602, 15607, 15617, 15622, 15632, 15637, 15647, 15652, 15662, 15667, 16104, 16125, 16126, 16170, 16255, 16258, 16270, 16276, 16323, 16325, 16326, 16336, 16342, 16385, 16386, 16393, 16426, 16427, 16434, 16491, 16492, 16687, 16716, 17400, 17401, 17589, 17590, 17861, 17862, 17863, 17864, 18137, 18138, 18139, 18140, 18141, 19384, 19441, 19778, 19779	\pagefilllstretch 496 \pagefillstretch 497 \pagefilstretch 498 \pagegoal 499 \pageheight 969 \pageleftoffset 918 \pagerightoffset 919 \pageshrink 500 \pagestretch 501 \pagetopoffset 920 \pagetotal 502 \pagewidth 970 \par 10, 11, 11, 11, 12, 12, 12, 13, 13, 13, 14, 14, 14, 148, 313, 503, 891, 21058, 21060, 21064, 21069, 21075, 21081, 21089, 21095, 21103, 21109, 21131, 22312 \pardir 951 \parfillskip 504 \parindent 505 \parshape 506 \parshapedimen 650 \parshapeindent 651 \parshapelength 652 \parskip 507 \patterns 508 \pausing 509 pc 199 \pdfadjustspacing 745 \pdfannot 675 \pdfcatalog 676 \pdfcolorstack 678 \pdfcolorstackinit 679 \pdfcompresslevel 677 \pdfcopyfont 746 \pdfcreationdate 680 \pdfdecimaldigits 681 \pdfdest 682 \pdfdestmargin 683 \pdfdraftmode 747 \pdfeachlinedepth 748 \pdfeachlineheight 749 \pdfendlink 684 \pdfendthread 685 \pdfextension 921 \pdffeedback 922 \pdffilemoddate 750 \pdffilesize 751 \pdffirstlineheight 752 \pdffontattr 686 \pdffontexpand 753 \pdffontname 687 \pdffontobjnum 688 \pdffontsize 754
P	
\PackageError 125, 133 \pagebottomoffset 917 \pagedepth 495 \pagedir 950 \pagediscards 649	

<code>\pdfgamma</code>	689	<code>\pdfretval</code>	725
<code>\pdfgentounicode</code>	692	<code>\pdfsave</code>	726
<code>\pdfglyphtounicode</code>	693	<code>\pdfsavepos</code>	773
<code>\pdfhorigin</code>	694	<code>\pdfsetmatrix</code>	727
<code>\pdfignoreddimen</code>	755	<code>\pdfsetrandomseed</code>	775
<code>\pdfimageapplygamma</code>	690	<code>\pdfshellescape</code>	776
<code>\pdfimagegamma</code>	691	<code>\pdfstartlink</code>	728
<code>\pdfimagehicolor</code>	695	<code>\pdfstartthread</code>	729
<code>\pdfimageresolution</code>	696	<code>\pdfstrcmp</code>	40, 369, 774
<code>\pdfincludechars</code>	697	<code>\pdfsuppressptexinfo</code>	730
<code>\pdfinclusioncopyfonts</code>	698	pdftex commands:	
<code>\pdfinclusionerrorlevel</code>	699	<code>\pdftex_adjustspacing:D</code>	745, 954
<code>\pdfinfo</code>	700	<code>\pdftex_copyfont:D</code>	746, 955
<code>\pdfinsertht</code>	756	<code>\pdftex_draftmode:D</code>	747, 956
<code>\pdflastannot</code>	701	<code>\pdftex_eachlinedepth:D</code>	748
<code>\pdflastlinedepth</code>	757	<code>\pdftex_eachlineheight:D</code>	749
<code>\pdflastlink</code>	702	<code>\pdftex_efcode:D</code>	782
<code>\pdflastobj</code>	703	<code>\pdftex_filemoddate:D</code>	750
<code>\pdflastxform</code>	704	<code>\pdftex_filesize:D</code>	751
<code>\pdflastximage</code>	705	<code>\pdftex_firstlineheight:D</code>	752
<code>\pdflastximagecolordepth</code>	706	<code>\pdftex_fontexpand:D</code>	753, 957
<code>\pdflastximagepages</code>	707	<code>\pdftex_fontsize:D</code>	754
<code>\pdflastxpos</code>	758	<code>\pdftex_if_engine:TF</code>	
<code>\pdflastypos</code>	759	22448, 22449, 22450
<code>\pdflinkmargin</code>	708	<code>\pdftex_if_engine_p:</code>	22447
<code>\pdfliteral</code>	709	<code>\pdftex_ifabsdim:D</code>	742, 958
<code>\pdfmapfile</code>	760	<code>\pdftex_ifabsnum:D</code>	743, 959
<code>\pdfmapline</code>	761	<code>\pdftex_ifincsname:D</code>	783
<code>\pdfmdfivesum</code>	762	<code>\pdftex_ifprimitive:D</code>	744, 860
<code>\pdfminorversion</code>	710	<code>\pdftex_ignoreddimen:D</code>	755
<code>\pdfnames</code>	711	<code>\pdftex_ignoreligaturesinfont:D</code>	960
<code>\pdfnoligatures</code>	763	<code>\pdftex_insertht:D</code>	756, 961
<code>\pdfnormaldeviate</code>	764	<code>\pdftex_lastlinedepth:D</code>	757
<code>\pdfobj</code>	712	<code>\pdftex_lastxpos:D</code>	758, 965
<code>\pdfobjcompresslevel</code>	713	<code>\pdftex_lastypos:D</code>	759, 966
<code>\pdfoutline</code>	714	<code>\pdftex_leftmarginkern:D</code>	784
<code>\pdfoutput</code>	715	<code>\pdftex_letterspacefont:D</code>	785
<code>\pdfpageattr</code>	716	<code>\pdftex_lpcode:D</code>	786
<code>\pdfpagebox</code>	717	<code>\pdftex_mapfile:D</code>	760, 1278
<code>\pdfpageheight</code>	765	<code>\pdftex_mapline:D</code>	761, 1279
<code>\pdfpageref</code>	718	<code>\pdftex_mdffivesum:D</code> ..	762, 859, 22871
<code>\pdfpageresources</code>	719	<code>\pdftex_noligatures:D</code>	763
<code>\pdfpagesattr</code>	720	<code>\pdftex_normaldeviate:D</code>	764, 967
<code>\pdfpagewidth</code>	766	<code>\pdftex_pageheight:D</code> ..	765, 969, 1267
<code>\pdfpkmode</code>	767	<code>\pdftex_pagewidth:D</code>	766, 1269
<code>\pdfpkresolution</code>	768	<code>\pdftex_pagewith:D</code>	970
<code>\pdfprimitive</code>	769	<code>\pdftex_pdfannot:D</code>	675
<code>\pdfprotrudechars</code>	770	<code>\pdftex_pdfcatalog:D</code>	676
<code>\pdfpxdimen</code>	771	<code>\pdftex_pdfcolorstack:D</code>	
<code>\pdfrandomseed</code>	772	678, 24743, 24768
<code>\pdfrefobj</code>	721	<code>\pdftex_pdfcolorstackinit:D</code> ...	679
<code>\pdfrefxform</code>	722	<code>\pdftex_pdfcompresslevel:D</code>	677
<code>\pdfrefximage</code>	723	<code>\pdftex_pdfcreationdate:D</code>	680
<code>\pdfrestore</code>	724	<code>\pdftex_pdfdecimaldigits:D</code>	681

\pdfTeX_pdfdest:D	682	\pdfTeX_pdftexversion:D	288, 781, 1275, 1298, 22359
\pdfTeX_pdfdestmargin:D	683	\pdfTeX_pdfthread:D	731
\pdfTeX_pdfendlink:D	684	\pdfTeX_pdfthreadmargin:D	732
\pdfTeX_pdfendthread:D	685	\pdfTeX_pdftrailer:D	733
\pdfTeX_pdffontattr:D	686	\pdfTeX_pdfuniquestring:D	734
\pdfTeX_pdffontname:D	687	\pdfTeX_pdfvorigin:D	735
\pdfTeX_pdffontobjnum:D	688	\pdfTeX_pdfxform:D	736, 977
\pdfTeX_pdffgamma:D	689	\pdfTeX_pdfxformattr:D	737
\pdfTeX_pdffgentounicode:D	692	\pdfTeX_pdfxformname:D	738
\pdfTeX_pdffglyptounicode:D	693	\pdfTeX_pdfxformresources:D	739
\pdfTeX_pdfhorigin:D	694	\pdfTeX_pdfximage:D	740, 978, 25251
\pdfTeX_pdfimageapplygamma:D	690	\pdfTeX_pdfximagebbox:D	741, 25245
\pdfTeX_pdfimagegamma:D	691	\pdfTeX_pkmode:D	767
\pdfTeX_pdfimagehicolor:D	695	\pdfTeX_pkreolution:D	768
\pdfTeX_pdfimageresolution:D	696	\pdfTeX_primitive:D	769, 861
\pdfTeX_pdfincludechars:D	697	\pdfTeX_protrudechars:D	770, 971
\pdfTeX_pdfinclusioncopyfonts:D	698	\pdfTeX_pxdimen:D	771, 972
\pdfTeX_pdfinclusionerrorlevel:D	699	\pdfTeX_quitvmode:D	787, 22483, 22484
\pdfTeX_pdfinfo:D	700	\pdfTeX_randomseed:D	772, 973, 23167, 23168
\pdfTeX_pdflastannot:D	701	\pdfTeX_rightmargin:D	788
\pdfTeX_pdflastlink:D	702	\pdfTeX_rpcode:D	789
\pdfTeX_pdflastobj:D	703	\pdfTeX_savepos:D	773, 976
\pdfTeX_pdflastxform:D	704, 962	\pdfTeX_setrandomseed:D	775, 979, 23171
\pdfTeX_pdflastximage:D	705, 963, 25270, 25274	\pdfTeX_shellescape:D	776, 862, 23182
\pdfTeX_pdflastximagecolordepth:D	706	\pdfTeX_strcmp:D	774, 3884
\pdfTeX_pdflastximagepages:D	707, 964	\pdfTeX_synctex:D	790
\pdfTeX_pdflinkmargin:D	708	\pdfTeX_tagcode:D	791
\pdfTeX_pdfliteral:D	709, 25127	\pdfTeX_tracingfonts:D	777, 980, 1211, 1213, 1217
\pdfTeX_pdfminorversion:D	710	\pdfTeX_uniformdeviate:D	755, 756, 778, 981, 16608, 16619, 16622, 22923, 22958, 22979, 23158
\pdfTeX_pdfnames:D	711	\pdfTeX_banner	779
\pdfTeX_pdfobj:D	712	\pdfTeX_revision	780
\pdfTeX_pdfobjcompresslevel:D	713	\pdfTeX_version	95, 781
\pdfTeX_pdfoutline:D	714	\pdfThread	731
\pdfTeX_pdfoutput:D	715, 968, 22396	\pdfThreadmargin	732
\pdfTeX_pdfpageattr:D	716	\pdfTracingfonts	777, 1212, 1213
\pdfTeX_pdfpagebox:D	717	\pdfTrailer	733
\pdfTeX_pdfpageref:D	718	\pdfUniformdeviate	778
\pdfTeX_pdfpageresources:D	719	\pdfUniquestring	734
\pdfTeX_pdfpagesattr:D	720	\pdfVariable	923
\pdfTeX_pdfrefobj:D	721	\pdfvorigin	735
\pdfTeX_pdfrefxform:D	722, 974	\pdfxform	736
\pdfTeX_pdfrefximage:D	723, 975, 25270, 25282	\pdfxformattr	737
\pdfTeX_pdfrestore:D	724, 25140	\pdfxformname	738
\pdfTeX_pdfretval:D	725	\pdfxformresources	739
\pdfTeX_pdfsave:D	726, 25134	\pdfximage	740
\pdfTeX_pdfsetmatrix:D	727, 25146	\pdfximagebbox	741
\pdfTeX_pdfstartlink:D	728		
\pdfTeX_pdfstartthread:D	729		
\pdfTeX_pdfsuppressptexinfo:D	730		
\pdfTeX_pdftexbanner:D	779, 1296		
\pdfTeX_pdftexrevision:D	780, 1297		

peek commands:

`\peek_after:Nw` [104](#), [123](#), [123](#), [123](#), [7581](#), [7606](#), [7664](#)
`\peek_catcode:NTF` [123](#), [7688](#)
`\peek_catcode_ignore_spaces:NTF` .
 [123](#), [7688](#)
`\peek_catcode_remove:NTF` .. [123](#), [7688](#)
`\peek_catcode_remove_ignore_spaces:NTF` [124](#), [7688](#)
`\peek_charcode:NTF` [124](#), [7704](#)
`\peek_charcode_ignore_spaces:NTF`
 [124](#), [7704](#)
`\peek_charcode_remove:NTF` . [124](#), [7704](#)
`\peek_charcode_remove_ignore_spaces:NTF` [124](#), [7704](#)
`\peek_gafter:Nw` [123](#), [123](#), [7581](#)
`\peek_meaning:NTF` [124](#), [7720](#)
`\peek_meaning_ignore_spaces:NTF` .
 [125](#), [7720](#)
`\peek_meaning_remove:NTF` .. [125](#), [7720](#)
`\peek_meaning_remove_ignore_spaces:NTF` [125](#), [7720](#)
`\peek_N_type:TF`
 [252](#), [24429](#), [24463](#), [24465](#)

peek internal commands:

`__peek_def:nmmn` [7671](#),
[7688](#), [7692](#), [7696](#), [7700](#), [7704](#), [7708](#),
[7712](#), [7716](#), [7720](#), [7724](#), [7728](#), [7732](#)
`__peek_def:nmmnn` [7671](#)
`__peek_execute_branches:`
 [478](#), [7668](#), [7683](#)
`__peek_execute_branches_catcode:` [7628](#), [7691](#), [7693](#), [7699](#), [7701](#)
`__peek_execute_branches_catcode_aux:` [7628](#)
`__peek_execute_branches_catcode_auxii:N` [7628](#)
`__peek_execute_branches_catcode_auxiii:` [7628](#)
`__peek_execute_branches_charcode:`
 [7628](#), [7707](#), [7709](#), [7715](#), [7717](#)
`__peek_execute_branches_meaning:` [7620](#), [7723](#), [7725](#), [7731](#), [7733](#)
`__peek_execute_branches_N_type:`
 [24429](#)
`__peek_false:w` [977](#), [7577](#),
[7601](#), [7625](#), [7648](#), [7658](#), [24446](#), [24459](#)
`__peek_get_prefix_arg_replacement:wN`
 [7737](#)
`__peek_ignore_spaces_execute_branches:` [7661](#),
[7695](#), [7703](#), [7711](#), [7719](#), [7727](#), [7735](#)
`__peek_N_type:w` [24429](#)

`__peek_N_type_aux:nw` [24429](#)
`\l__peek_search_tl`
 [475](#), [477](#), [7576](#), [7594](#), [7645](#), [7655](#)
`\l__peek_search_token`
 [475](#), [7575](#), [7593](#), [7622](#)
`__peek_tmp:w` [7577](#), [7588](#), [24430](#), [24452](#)
`__peek_token_generic:NNTF` . [977](#),
[7608](#), [7610](#), [7612](#), [24462](#), [24464](#), [24466](#)
`__peek_token_generic_aux:NNNTF` .
 [7590](#), [7609](#), [7615](#)
`__peek_token_remove_generic:NNTF`
 [7608](#), [7616](#), [7618](#)
`__peek_true:w` .. [977](#), [7577](#), [7600](#),
[7623](#), [7646](#), [7656](#), [24444](#), [24458](#), [24459](#)
`__peek_true_aux:w`
 [476](#), [7577](#), [7587](#), [7595](#), [7609](#)
`__peek_true_remove:w` [476](#), [7585](#), [7615](#)
`\penalty` [510](#)
`\pi` [198](#)
`\pm` [13485](#), [13486](#)
`\postbreakpenalty` [1151](#)
`\postdisplaypenalty` [511](#)
`\postexhyphenchar` [924](#)
`\posthyphenchar` [925](#)
`\prebreakpenalty` [1152](#)
`\predisplaydirection` [653](#)
`\predisplaygapfactor` [926](#)
`\predisplaypenalty` [512](#)
`\predisplaysize` [513](#)
`\preexhyphenchar` [927](#)
`\prehyphenchar` [928](#)
`\pretolerance` [514](#)
`\prevdepth` [515](#)
`\prevgraf` [516](#)
prg commands:
`\prg_break_point:Nn` [94](#)
`\prg_do_nothing:`
 [9](#), [104](#), [342](#), [388](#), [459](#), [597](#),
[753](#), [815](#), [861](#), [1854](#), [1855](#), [2327](#),
[2338](#), [2712](#), [2737](#), [3032](#), [3060](#), [3110](#),
[3125](#), [3829](#), [3831](#), [4650](#), [4657](#), [4897](#),
[4899](#), [6661](#), [7002](#), [7006](#), [7013](#), [9350](#),
[9619](#), [10457](#), [11621](#), [11664](#), [11698](#),
[11724](#), [11732](#), [13189](#), [16565](#), [16965](#),
[16972](#), [17048](#), [17181](#), [17182](#), [17482](#),
[17531](#), [18320](#), [18357](#), [18358](#), [18365](#),
[18366](#), [19962](#), [20105](#), [23317](#), [23605](#)
`\prg_new_conditional:Nnn`
 . [96](#), [1753](#), [6242](#), [23185](#), [23193](#), [23201](#)
`\prg_new_conditional:Npnn`
 [23](#), [24](#), [96](#), [96](#), [300](#), [468](#),
[478](#), [1740](#), [2268](#), [3211](#), [3221](#), [3233](#),
[3255](#), [3257](#), [3303](#), [3322](#), [3607](#), [3626](#),
[3645](#), [3680](#), [3697](#), [3708](#), [3914](#), [3929](#),

3934, 4774, 5345, 5404, 5443, 5453,
 6092, 6098, 6183, 6191, 6203, 6209,
6242, 6273, 6308, 6363, 6372, 6378,
 6387, 6486, 6488, 6490, 6492, 6787,
 7337, 7342, 7347, 7352, 7359, 7365,
 7371, 7376, 7381, 7386, 7391, 7396,
 7401, 7406, 7413, 7430, 7435, 7470,
 7514, 7993, 8002, 8103, 9272, 9966,
 9971, 10214, 10233, 11231, 11238,
 11556, 12703, 13343, 13356, 18129,
 18149, 18171, 18229, 20913, 20915,
 20925, 21508, 23160, 23164, 23250
 \prg_new_eq_conditional:NNn
 97, 1845, 2925,
 2926, 3880, 3881, 3882, 3883, 4679,
 4681, 5084, 5085, 5086, 5087, 5088,
 5089, 5275, 5277, 6242, 6304, 6306,
 6570, 6572, 6783, 6785, 7989, 7991,
 9867, 9869, 10172, 10174, 10304,
 10306, 13341, 13342, 20879, 20881
 \prg_new_protected_conditional:Nnn
 96, 1753, 6242
 \prg_new_protected_conditional:Npnn
 . 96, 1740, 3269, 3290, 3943, 3952,
 4786, 4896, 4898, 4906, 4908, 4910,
 4912, 6242, 6670, 6682, 6684, 6801,
 6805, 7925, 7935, 8032, 9053, 9207,
 18534, 20239, 20244, 20257, 20259
 \prg_replicate:nn
 103, 442, 6439, 8842, 9472,
 14624, 15478, 15712, 15916, 15917,
 15919, 15921, 15934, 15971, 16457,
 16465, 17741, 18326, 19020, 19391,
 19417, 19570, 19578, 19967, 20406,
 20411, 20418, 20517, 20522, 25816
 \prg_return_false: 62, 97,
 98, 361, 393, 409, 453, 872, 1736,
 1943, 1948, 1961, 1966, 1974, 1991,
 2271, 3226, 3239, 3252, 3262, 3279,
 3295, 3313, 3328, 3619, 3642, 3658,
 3666, 3676, 3689, 3703, 3717, 3911,
 3919, 3932, 3937, 3947, 3956, 4779,
 4800, 4823, 5343, 5375, 5380, 5409,
 5448, 5456, 6095, 6103, 6188, 6196,
6242, 6278, 6313, 6369, 6375, 6376,
 6382, 6391, 6487, 6489, 6491, 6493,
 6673, 6689, 6790, 6815, 7340, 7345,
 7350, 7355, 7362, 7369, 7374, 7379,
 7384, 7389, 7394, 7399, 7404, 7409,
 7427, 7433, 7438, 7443, 7476, 7479,
 7518, 7543, 7560, 7569, 7933, 7943,
 7996, 8018, 8039, 8106, 9057, 9211,
 9281, 9969, 9988, 10003, 10004,
 10221, 10236, 11236, 11244, 11567,
 11569, 12718, 12730, 13351, 13364,
 18143, 18154, 18157, 18162, 18166,
 18167, 18175, 18178, 18183, 18186,
 18235, 18238, 18541, 18546, 20285,
 20914, 20916, 20926, 21514, 21516,
 23165, 23188, 23198, 23206, 23256
 \prg_return_true/false: 369
 \prg_return_true: 62,
 97, 98, 361, 361, 393, 486, 870, 872,
1736, 1946, 1963, 1971, 1976, 1989,
 1994, 2271, 3224, 3237, 3250, 3260,
 3276, 3295, 3312, 3326, 3617, 3640,
 3656, 3674, 3687, 3705, 3716, 3909,
 3919, 3932, 3937, 3947, 3956, 4777,
 4804, 4826, 5375, 5407, 5446, 5458,
 6095, 6101, 6186, 6194, 6242, 6276,
 6311, 6367, 6375, 6384, 6390, 6391,
 6487, 6489, 6491, 6493, 6676, 6692,
 6791, 6815, 7340, 7345, 7350, 7355,
 7362, 7369, 7374, 7379, 7384, 7389,
 7394, 7399, 7404, 7409, 7425, 7433,
 7441, 7541, 7567, 7931, 7941, 7996,
 8020, 8037, 8106, 9058, 9214, 9279,
 9284, 9286, 9969, 10004, 10219,
 10237, 11235, 11243, 11560, 11565,
 12713, 12736, 13353, 13362, 18132,
 18146, 18154, 18157, 18162, 18166,
 18178, 18183, 18186, 18233, 18537,
 18543, 20283, 20914, 20916, 20926,
 21513, 23161, 23190, 23196, 23204
 \prg_set_conditional:Nnn
 96, 1753, 6242
 \prg_set_conditional:Npnn 96, 97,
 98, 1740, 1940, 1952, 1968, 1980, 6242
 \prg_set_eq_conditional:NNn
 97, 1845, 6242
 \prg_set_protected_conditional:Nnn
 96, 1753, 6242
 \prg_set_protected_conditional:Npnn
 96, 1740, 6242
 prg internal commands:
 __prg_break:
 104, 858, 2338, 3736, 4933,
6500, 8022, 9051, 11612, 16583,
 17113, 17258, 17584, 17651, 17681,
 17682, 17683, 17684, 17685, 17686,
 18030, 19882, 19909, 23093, 23099
 __prg_break:n . . . 104, 104, 2338,
 3738, 4804, 4946, 6500, 7921, 19464
 __prg_break_point:
 104, 104, 514, 773, 946,
 2338, 3726, 4801, 4934, 6500, 7916,
 8007, 9028, 11613, 16584, 17106,
 17113, 17252, 17511, 17652, 17688,

- 18008, 19465, 19753, 19903, 23094
- _prg_break_point:Nn
 104, 104, 320, 320,
 397, 414, 2329, 3371, 3389, 3398,
 4025, 4051, 4070, 4961, 4996, 5007,
 5576, 6500, 6832, 6846, 6866, 6884,
 8051, 8070, 9317, 13552, 17630, 23057
- _prg_case_end:nw
 24, 3332, 4018, 5440, 10033
- _prg_compare_error:.. 87, 408,
 409, 542, 5330, 5348, 5350, 9974, 9976
- _prg_compare_error:Nw
 87, 409, 410, 410, 5330, 5370
- _prg_generate_conditional:nnNnnnnn
 1750, 1769, 1778
- _prg_generate_conditional:nnnnnnnw
 1778
- _prg_generate_conditional_-
 count:nnNnn 1753
- _prg_generate_conditional_-
 count:nnNnnnn 1753
- _prg_generate_conditional_-
 parm:nnNpnn 1740
- _prg_generate_F_form:wnnnnnnn 1810
- _prg_generate_p_form:wnnnnnnn 1810
- _prg_generate_T_form:wnnnnnnn 1810
- _prg_generate_TF_form:wnnnnnnn 1810
- _prg_map_1:w 104
- _prg_map_2:w 104
- _prg_map_break:Nn
 104, 320, 354, 456, 490, 2329, 3411,
 3413, 4083, 4085, 4951, 4953, 6500,
 6901, 6903, 8079, 8081, 9300, 9302
- _g_prg_map_int 104,
 353, 414, 791, 3383, 3385, 3387,
 3389, 4041, 4043, 4047, 4051, 4982,
 4983, 4989, 4990, 5555, 5558, 5562,
 5565, 5576, 6499, 6860, 6862, 6864,
 6867, 8066, 8067, 8072, 8074, 9309,
 9311, 9318, 13531, 13534, 13538,
 13541, 13552, 17615, 17617, 17630
- _prg_replicate:N 6439
- _prg_replicate_ 6439
- _prg_replicate_0:n 6439
- _prg_replicate_1:n 6439
- _prg_replicate_2:n 6439
- _prg_replicate_3:n 6439
- _prg_replicate_4:n 6439
- _prg_replicate_5:n 6439
- _prg_replicate_6:n 6439
- _prg_replicate_7:n 6439
- _prg_replicate_8:n 6439
- _prg_replicate_9:n 6439
- _prg_replicate_first:N 6439
- _prg_replicate_first_:n ... 6439
- _prg_replicate_first_0:n ... 6439
- _prg_replicate_first_1:n ... 6439
- _prg_replicate_first_2:n ... 6439
- _prg_replicate_first_3:n ... 6439
- _prg_replicate_first_4:n ... 6439
- _prg_replicate_first_5:n ... 6439
- _prg_replicate_first_6:n ... 6439
- _prg_replicate_first_7:n ... 6439
- _prg_replicate_first_8:n ... 6439
- _prg_replicate_first_9:n ... 6439
- _prg_set_eq_conditional:NNNn 1845
- _prg_set_eq_conditional:nnNnnNNw
 1853, 1861
- _prg_set_eq_conditional_F_-
 form:nnn 1861
- _prg_set_eq_conditional_F_-
 form:wNnnnn 1906
- _prg_set_eq_conditional_-
 loop:nnnnNw 1861
- _prg_set_eq_conditional_p_-
 form:nnn 1861
- _prg_set_eq_conditional_p_-
 form:wNnnnn 1894
- _prg_set_eq_conditional_T_-
 form:nnn 1861
- _prg_set_eq_conditional_T_-
 form:wNnnnn 1902
- _prg_set_eq_conditional_TF_-
 form:nnn 1861
- _prg_set_eq_conditional_TF_-
 form:wNnnnn 1898
- \primitive 861
- prop commands:
- \c_empty_prop
 134, 482, 7777, 7781, 7785, 7788, 7995
- \prop_clear:N
 129, 129, 7784, 7791, 19712, 21896
- \prop_clear_new:N
 129, 905, 7790, 21544, 21545
- \prop_const_from_keyval:Nn
 244, 7808, 21478, 21485
- \prop_count:N 244, 23043, 23075
- \prop_gclear:N 129, 7784, 7794
- \prop_gclear_new:N 129, 7790
- \prop_get:Nn 104, 22451, 22452
- \prop_get:NnN 91, 92, 130,
 131, 7882, 22119, 22123, 22202, 22206
- \prop_get:NnNTF
 130, 131, 132, 8032, 8041, 8042,
 8044, 8045, 8465, 8485, 8540, 21673
- \prop_gpop:NnN 130, 7890
- \prop_gpop:NnNTF
 130, 132, 7925, 7948, 7949

- \prop_gput:Nnn 130, [7951](#), 9199, 9244, 9369, 9399
- \prop_gput_if_new:Nnn 130, [7972](#)
- \prop_gremove:Nn 131, [7866](#), 9252, 9408
- \prop_gset_eq:NN 129, [7788](#), [7796](#), 21546, 21548, 21697, 21699
- \prop_gset_from_keyval:Nn . 244, [7808](#)
- \prop_if_empty:Ntf 131, [7993](#), 7999, 8000, 23072
- \prop_if_empty_p:N 131, [7993](#)
- \prop_if_exist:Ntf 131, [7791](#), [7794](#), [7989](#)
- \prop_if_exist_p:N 131, [7989](#)
- \prop_if_in:NnTF 131, [8002](#), 8026, 8027, 8028, 8029
- \prop_if_in_p:Nn 131, [8002](#)
- \prop_item:Nn 131, 244, [7912](#), 22451, 22452
- \prop_log:N 134, [8082](#)
- \prop_map_break: 133, 944, 8051, 8056, 8070, [8078](#), 23057, 23062
- \prop_map_break:n 133, [8078](#)
- \prop_map_function:NN 132, 243, 244, 488, 944, [8047](#), 8092, 9266, 9422, 22277, 23048
- \prop_map_inline:Nn 132, [8063](#), 20428, 21967, 21986, 22171, 22180, 22618, 22620, 22623, 22642, 22644, 22709, 22726, 22770, 22772, 22776, 22778
- \prop_map_tokens:Nn 244, [23053](#)
- \prop_new:N 129, [7778](#), 7791, 7794, 7804, 7805, 7806, 7807, 8295, 8439, 9185, 9355, 19652, 19653, 22045, 22086, 22608
- \prop_pop:NnN 130, [7890](#)
- \prop_pop:NnNtf 130, 132, [7925](#), 7945, 7946
- \prop_put:Nnn 130, 134, 332, 481, [7951](#), 8513, 8529, 8546, 19869, 21725, 21731, 21733, 21735, 21737, 21742, 21747, 21752, 21759, 21766, 21991, 22046, 22048, 22050, 22052, 22054, 22056, 22058, 22060, 22062, 22064, 22066, 22068, 22070, 22072, 22074, 22076, 22078, 22080, 22650, 22652, 22655, 22657, 22663, 22669, 22736, 22744, 22807, 22821, 22828
- \prop_put_if_new:Nnn 130, [7972](#)
- \prop_rand_key_value:N . . . 244, [23068](#)
- \prop_remove:Nn 131, [7866](#), 8510, 8525, 22166, 22169, 22173
- \prop_set_eq:NN 129, [7785](#), [7796](#), 19880, 21683, 21685, 21690, 21692, 21926, 22161
- \prop_set_from_keyval:Nn . . 244, [7808](#)
- \prop_show:N 133, [8082](#)
- \g_tmpa_prop 134, [7804](#)
- \l_tmpa_prop 134, [7804](#)
- \g_tmpb_prop 134, [7804](#)
- \l_tmpb_prop 134, [7804](#)
- prop internal commands:
 - __prop_count:nn [23043](#)
 - __prop_from_keyval:n [7808](#)
 - __prop_from_keyval_key:w . 483, [7808](#)
 - __prop_from_keyval_loop:w . . . [7808](#)
 - __prop_from_keyval_split:Nw . [7808](#)
 - __prop_from_keyval_value:w 483, [7808](#)
 - __prop_if_in:N 488, [8002](#)
 - __prop_if_in:nwn 488, [8002](#)
 - \l__prop_internal_tl 134, 487, [7776](#), 7955, 7961, 7962, 7978, 7985
 - __prop_item:Nn:nwn 486
 - __prop_item:Nn:nwn [7912](#)
 - __prop_map_function:Nwn . . . [8047](#)
 - __prop_map_tokens:nwn . . 944, [23053](#)
 - __prop_pair:wn 134, 134, 481, 484, 488, 490, [7774](#), 7846, 7860, 7863, 7915, 7918, 7957, 7980, 8005, 8009, 8050, 8053, 8066, 8068, 8073, 23056, 23059, 23079
 - __prop_put:Nnn [7951](#)
 - __prop_put_if_new:Nnn [7972](#)
 - __prop_rand:NN [23068](#)
 - __prop_rand:nNn 23068, [23069](#)
 - __prop_rand_item:Nw [23068](#)
 - __prop_show:NN . . . 8082, 8084, 8086
 - __prop_split:NnTF . 135, 487, 487, 488, [7855](#), 7868, 7874, 7884, 7892, 7901, 7927, 7937, 7960, 7983, 8034
 - __prop_split_aux:NnTF [7855](#)
 - __prop_split_aux:w 484, [7855](#)
- \protect 9526, 12224, 23647, 23674
- \protected 207, 209, 211, 236, 654, 7502, 7504
- \protrudechars 971
- \ProvidesExplClass 6
- \ProvidesExplFile 6, 24632
- \ProvidesExplPackage 6
- pt 199
- ptex commands:
 - \ptex_autospacing:D 1127
 - \ptex_autoxspacing:D 1128
 - \ptex_dtou:D 1129
 - \ptex_euc:D 1130
 - \ptex_ifdbbox:D 1131
 - \ptex_ifddir:D 1132

<code>\ptex_ifmdir:D</code>	1133	12144, 12145, 12150, 17119, 17154,
<code>\ptex_ifftbox:D</code>	1134	17156, 17159, 17163, 17166, 17169,
<code>\ptex_iftdir:D</code>	1135	17171, 17174, 24441, 24442, 24449
<code>\ptex_ifybox:D</code>	1136	<code>\q_nil</code> 19, 19, 92, 92, 92, 293,
<code>\ptex_ifydir:D</code>	1137	346, 348, 349, 356, 430, 433, 483,
<code>\ptex_inhibitglue:D</code>	1138	1437, 1440, 3157, 3235, 3236, 3248,
<code>\ptex_inhibitxspcode:D</code>	1139	3249, 3470, 3474, 3492, 3495, 3498,
<code>\ptex_jcharwidowpenalty:D</code>	1140	3586, 3587, 6132, 6185, 6206, 6208,
<code>\ptex_jfam:D</code>	1141	7833, 7835, 7840, 9547, 9554, 10405,
<code>\ptex_jfont:D</code>	1142	10415, 10429, 10439, 18986, 19001
<code>\ptex_jis:D</code>	1143, 5245, 22371	<code>\q_no_value</code>
<code>\ptex_kanjiskip:D</code> .	1144, 17358, 22367	65,
<code>\ptex_kansuji:D</code>	1145	66, 66, 66, 66, 66, 71, 71, 71, 91, 92,
<code>\ptex_kansujichar:D</code>	1146	92, 92, 111, 130, 130, 130, 394, 395,
<code>\ptex_kcatcode:D</code>	1147	430, 432, 449, 485, 485, 4814, 4822,
<code>\ptex_kuten:D</code>	1148	4834, 4858, 6132, 6193, 6212, 6214,
<code>\ptex_noautospaceing:D</code>	1149	6636, 6651, 7886, 7897, 7906, 9819
<code>\ptex_postbreakpenalty:D</code>	1151	<code>\quark_if_nil:n</code>
<code>\ptex_prebreakpenalty:D</code>	1152	<code>\quark_if_nil:NTF</code>
<code>\ptex_showmode:D</code>	1153 92, 6183, 19005, 19025
<code>\ptex_sjis:D</code>	1154	<code>\quark_if_nil:nTF</code>
<code>\ptex_tate:D</code>	1155 92, 431, 3155, 6203, 6217, 6218
<code>\ptex_tbaselineshift:D</code>	1156	<code>\quark_if_nil_p:N</code>
<code>\ptex_tfont:D</code>	1157	<code>\quark_if_nil_p:n</code>
<code>\ptex_xkanjiskip:D</code>	1158	<code>\quark_if_no_value:NTF</code> ..
<code>\ptex_xspcode:D</code>	1159	6200, 6201, 22121, 22125, 22204, 22208
<code>\ptex_ybaselineshift:D</code>	1160	<code>\quark_if_no_value:nTF</code>
<code>\ptex_yoko:D</code>	1161	<code>\quark_if_no_value_p:N</code>
<code>\pxdimen</code>	972	<code>\quark_if_no_value_p:n</code>
		<code>\quark_if_recursion_tail_break:N</code>
	 22453
		<code>\quark_if_recursion_tail_break:n</code>
	 22454
		<code>\quark_if_recursion_tail_stop:N</code> .
	 93, 5911, 6138, 6895, 24209
		<code>\quark_if_recursion_tail_stop:n</code> .
	 93,
		364, 432, 6152, 6589, 6925, 7825, 24042
		<code>\quark_if_recursion_tail_stop_-</code>
		do:Nn 93, 4391, 5850, 5867,
		5914, 6138, 23427, 23435, 23635, 23655
		<code>\quark_if_recursion_tail_stop_-</code>
		do:nn .. 93, 6152, 6367, 6382, 23707
		<code>\quark_new:N</code> . 91, 6126, 6132, 6133,
		6134, 6135, 6136, 6137, 6219, 6220
		<code>\q_recursion_stop</code>
	 19, 19, 93, 93, 93, 93, 93,
		94, 293, 305, 431, 1439, 1442, 1790,
		1858, 2641, 4369, 4376, 4381, 4569,
		5845, 5862, 5905, 5932, 6136, 6364,
		6379, 6585, 6883, 6919, 7821, 18986,
		19001, 23367, 23370, 23379, 23390,
		23404, 23418, 23425, 23431, 23450,
		23452, 23461, 23463, 23470, 23471,
		23474, 23477, 23490, 23629, 23651,

Q

quark commands:

<code>\q_mark</code>	24, 50, 92, 308, 331,
	332, 346, 353, 356, 356, 367, 373,
	380, 447, 449, 451, 452, 457, 483,
	484, 556, 772, 773, 774, 780, 1924,
	1925, 1931, 1933, 1934, 2651, 2652,
	2654, 2660, 2664, 2686, 2695, 2714,
	2740, 2743, 2752, 2767, 2811, 2825,
	2828, 2841, 3131, 3133, 3135, 3137,
	3353, 3364, 3442, 3443, 3446, 3449,
	3450, 3456, 3471, 3472, 3478, 3482,
	3484, 3487, 3979, 4011, 4089, 4106,
	4353, 4355, 5033, 5034, 5048, 5051,
	5358, 5361, 5433, 6132, 6584, 6593,
	6598, 6653, 6663, 6667, 6691, 6743,
	6749, 6762, 6774, 6775, 6776, 6779,
	6780, 6781, 6790, 6791, 6800, 6845,
	6853, 6942, 6943, 6955, 6956, 7019,
	7820, 7828, 7838, 7860, 7862, 7863,
	8407, 8470, 8471, 8476, 8479, 9660,
	9667, 9679, 10026, 10388, 10395,
	10405, 10429, 10451, 10461, 10471,

- 23673, 23703, 23719, 23721, 23724,
 23727, 23729, 23734, 23737, 23739,
 23742, 23745, 23750, 23771, 23774,
 23776, 23778, 23783, 23864, 23868,
 23870, 23875, 23889, 23914, 23918,
 23920, 23925, 23933, 24181, 24227,
 24244, 24248, 24250, 24255, 24270
 \q_recursion_tail 93,
 93, 93, 93, 93, 94, 94, 305, 372, 431,
 431, 454, 488, 490, 944, 1790, 1795,
 1858, 1877, 3370, 3388, 3397, 3725,
 4024, 4033, 4050, 4069, 4369, 4559,
 4569, 5845, 5862, 5905, 6136, 6140,
 6146, 6155, 6162, 6167, 6172, 6179,
 6364, 6379, 6585, 6831, 6845, 6865,
 6883, 6919, 7821, 8006, 8017, 8050,
 8055, 10388, 10395, 10456, 23056,
 23061, 23367, 23431, 23465, 23629,
 23651, 23682, 23703, 24180, 24226
 \q_stop 19, 19, 24, 31, 47,
 91, 92, 92, 92, 293, 308, 332, 346,
 355, 373, 377, 409, 421, 430, 452,
 457, 471, 473, 483, 484, 510, 773,
 773, 774, 1438, 1441, 1576, 1578,
 1806, 1811, 1828, 1834, 1840, 1888,
 1894, 1898, 1902, 1906, 1926, 1931,
 1933, 1934, 2655, 2664, 2690, 2740,
 2744, 2748, 2756, 2762, 2771, 2776,
 2778, 2811, 2831, 2842, 3156, 3325,
 3331, 3353, 3364, 3444, 3446, 3451,
 3453, 3476, 3498, 3577, 3579, 3596,
 3614, 3633, 3655, 3756, 3766, 3864,
 3979, 4011, 4089, 4098, 4104, 4106,
 4112, 4129, 4149, 4210, 4266, 4278,
 4316, 4332, 4339, 4347, 4349, 4353,
 4355, 4479, 4484, 4487, 4491, 4509,
 4522, 4533, 4537, 4540, 4542, 4543,
 4546, 4549, 4834, 4837, 4845, 4847,
 4927, 4928, 5035, 5048, 5051, 5053,
 5337, 5353, 5355, 5359, 5372, 5433,
 5838, 5844, 5861, 6132, 6638, 6641,
 6653, 6656, 6664, 6667, 6675, 6691,
 6749, 6776, 6779, 6780, 6792, 6800,
 6944, 6955, 6956, 6957, 6983, 7017,
 7418, 7421, 7453, 7487, 7522, 7526,
 7532, 7555, 7739, 7746, 7755, 7764,
 7827, 7835, 7838, 7840, 7860, 7863,
 8409, 8413, 8415, 8472, 8951, 8955,
 9116, 9118, 9132, 9147, 9149, 9547,
 9588, 9645, 9683, 9696, 9744, 9745,
 9979, 10003, 10026, 10237, 10239,
 10459, 10474, 10496, 10510, 10511,
 10576, 10578, 10598, 10602, 10611,
 10619, 10632, 11074, 11082, 11092,
 11219, 11221, 11226, 12145, 12150,
 12260, 12264, 16630, 16701, 17107,
 17116, 17120, 17122, 17154, 17155,
 17156, 17161, 17163, 17167, 17169,
 17177, 23010, 23076, 23089, 23090,
 23092, 23096, 23100, 23102, 23107,
 24430, 24443, 24452, 24671, 24673,
 24685, 24691, 24693, 24694, 24709,
 24712, 24748, 24752, 24753, 24754,
 24756, 24758, 24760, 25792, 25796
 quark internal commands:
 \s__fp 580, 581, 582, 614, 615,
 618, 631, 633, 657, 659, 661, 661,
 663, 669, 672, 753, 11348, 11361,
 11362, 11363, 11364, 11365, 11375,
 11380, 11382, 11383, 11404, 11407,
 11409, 11419, 11431, 11451, 11544,
 11546, 11548, 11549, 11550, 11552,
 11553, 11554, 11556, 11572, 11742,
 11747, 12002, 12048, 12057, 12059,
 12708, 12832, 13017, 13348, 13373,
 13374, 13493, 13506, 13510, 13566,
 13567, 13570, 13581, 13582, 13590,
 13591, 13593, 13594, 13595, 13597,
 13598, 13599, 13610, 13613, 13625,
 13651, 13684, 13687, 13690, 13710,
 13711, 13713, 13714, 13715, 13723,
 13726, 13737, 13738, 13740, 13749,
 13825, 13977, 14011, 14012, 14015,
 14094, 14230, 14238, 14240, 14417,
 14425, 14427, 14429, 14432, 14894,
 14906, 14908, 15116, 15133, 15135,
 15321, 15340, 15342, 15343, 15346,
 15363, 15366, 15369, 15394, 15395,
 15397, 15413, 15498, 15511, 15513,
 15516, 15521, 15583, 15596, 15598,
 15611, 15613, 15626, 15628, 15641,
 15643, 15656, 15658, 15671, 15681,
 16113, 16129, 16130, 16134, 16145,
 16251, 16264, 16266, 16282, 16285,
 16295, 16318, 16329, 16331, 16345,
 16347, 16352, 16380, 16401, 16404,
 16421, 16442, 16445, 16486, 16502,
 16505, 16563, 16564, 16695, 16697
 \s__fp_division 11356
 \s__fp_exact 11356, 11361,
 11362, 11363, 11364, 11365, 13566
 \s__fp_invalid 11356
 \s__fp_mark 594, 614, 615,
 618, 638, 640, 648, 11354, 11622,
 11623, 11625, 11629, 12881, 12920,
 13295, 13296, 13299, 13302, 13303
 \s__fp_overflow 11356, 11382
 \s__fp_stop 586, 11354, 12789,

- 12882, 12885, 13297, 13302, 13303,
13305, 13629, 13640, 13664, 13672
\s__fp_underflow [11356](#), [11380](#)
\s__prop [134](#), [134](#),
[481](#), [484](#), [490](#), [490](#), [944](#), [7773](#), [7774](#),
[7777](#), [7819](#), [7847](#), [7860](#), [7863](#), [7915](#),
[7918](#), [7958](#), [7981](#), [8005](#), [8009](#), [8050](#),
[8053](#), [8068](#), [23056](#), [23059](#), [23079](#), [23084](#)
__quark_if_nil:w [433](#), [6203](#)
__quark_if_no_value:w [6203](#)
__quark_if_recursion_tail:w ...
..... [431](#), [6152](#), [6179](#)
__quark_if_recursion_tail_-
break:NN [94](#), [3405](#), [4058](#), [4076](#), [6170](#)
__quark_if_recursion_tail_-
break:nN
.... [94](#), [3377](#), [3736](#), [6170](#), [6837](#), [6850](#)
\s__seq [74](#), [386](#), [389](#), [390](#), [395](#),
[400](#), [766](#), [945](#), [4575](#), [4583](#), [4613](#),
[4618](#), [4623](#), [4628](#), [4661](#), [4687](#), [4695](#),
[4699](#), [4878](#), [4928](#), [5045](#), [6237](#), [16951](#),
[16958](#), [20372](#), [23090](#), [23096](#), [23140](#)
\s__stop
.. [95](#), [95](#), [773](#), [6235](#), [6236](#), [15192](#),
[15207](#), [16367](#), [16371](#), [17120](#), [17122](#)
\s__tl [779](#), [780](#), [780](#), [781](#),
[782](#), [789](#), [790](#), [790](#), [17309](#), [17311](#),
[17528](#), [17555](#), [17561](#), [17586](#), [17604](#),
[17609](#), [17621](#), [17629](#), [17651](#), [17654](#)
\q__tl_act_mark
[357](#), [357](#), [357](#), [3502](#), [3505](#), [3522](#), [6219](#)
\q__tl_act_stop
[357](#), [3502](#), [3505](#), [3509](#), [3518](#), [3520](#),
[3526](#), [3531](#), [3534](#), [3538](#), [3541](#), [6219](#)
\quitvmode [787](#)
- ## R
- \r [24233](#)
\radical [517](#)
\raise [518](#)
rand [198](#)
randint [198](#)
\randomseed [973](#)
\read [519](#)
\readline [655](#)
\ref [24281](#)
regex commands:
 \c_foo_regex [205](#)
 \regex_(g)set:Nn [212](#)
 \regex_const:Nn [205](#), [212](#), [20206](#)
 \regex_count:NnN [213](#), [20249](#)
 \regex_count:nnN [213](#), [871](#), [20249](#)
 \regex_extract_all:NnN [20253](#)
 \regex_extract_all:nnN
 [206](#), [213](#), [796](#), [20253](#)
 \regex_extract_all:NnNTF . [213](#), [20253](#)
 \regex_extract_all:nnNTF . [213](#), [20253](#)
 \regex_extract_once:NnN [20253](#)
 \regex_extract_once:nnN
 [213](#), [213](#), [20253](#)
 \regex_extract_once:NnNTF [213](#), [20253](#)
 \regex_extract_once:nnNTF
 [210](#), [213](#), [20253](#)
 \regex_gset:Nn [212](#), [20206](#)
 \regex_match:NnTF [212](#), [20239](#)
 \regex_match:nnTF [212](#), [20239](#)
 \regex_new:N [212](#), [798](#), [20204](#)
 \regex_replace_all:NnN [20253](#)
 \regex_replace_all:nnN [206](#), [214](#), [20253](#)
 \regex_replace_all:NnNTF . [214](#), [20253](#)
 \regex_replace_all:nnNTF . [214](#), [20253](#)
 \regex_replace_once:NnN [20253](#)
 \regex_replace_once:nnN
 [213](#), [214](#), [20253](#)
 \regex_replace_once:NnNTF [214](#), [20253](#)
 \regex_replace_once:nnNTF [214](#), [20253](#)
 \regex_set:Nn [212](#), [20206](#)
 \regex_show:N [212](#), [20221](#)
 \regex_show:n [205](#), [212](#), [20221](#)
 \regex_split:NnN [20253](#)
 \regex_split:nnN [214](#), [20253](#)
 \regex_split:NnNTF [214](#), [20253](#)
 \regex_split:nnNTF [214](#), [20253](#)
regex internal commands:
 __regex_action_cost:n . [839](#), [842](#),
 [851](#), [19379](#), [19380](#), [19388](#), [19819](#), [19845](#)
 __regex_action_free:n
 [215](#), [839](#), [850](#), [19402](#), [19408](#),
 [19409](#), [19420](#), [19485](#), [19489](#), [19514](#),
 [19539](#), [19543](#), [19546](#), [19574](#), [19582](#),
 [19592](#), [19606](#), [19637](#), [19817](#), [19821](#)
 __regex_action_free_aux:nn .. [19821](#)
 __regex_action_free_group:n [215](#),
 [839](#), [850](#), [19432](#), [19554](#), [19557](#), [19821](#)
 __regex_action_start_wildcard: .
 [839](#), [19296](#), [19814](#)
 __regex_action_submatch:n
 [839](#), [19508](#), [19509](#), [19635](#), [19865](#), [19867](#)
 __regex_action_success:
 [215](#), [839](#), [19299](#), [19318](#), [19872](#)
 __regex_action_wildcard: [854](#)
 \c_regex_all_catcodes_int
 [18201](#), [18308](#), [18390](#), [18958](#)
 __regex_anchor:N
 [810](#), [849](#), [18613](#), [19139](#), [19597](#)
 \c_regex_ascii_lower_int
 [17789](#), [17846](#), [17851](#)

- \c_regex_ascii_max_control_int [17786](#), [17958](#)
- \c_regex_ascii_max_int [17786](#), [17951](#), [17959](#), [18153](#)
- \c_regex_ascii_min_int [17786](#), [17950](#), [17957](#)
- __regex_assertion:Nn [810](#), [848](#), [18613](#), [18638](#), [18647](#), [19136](#), [19597](#)
- __regex_b_test: [810](#), [848](#), [18638](#), [18647](#), [19138](#), [19597](#)
- \l_regex_balance_int [798](#), [861](#), [17784](#), [19674](#), [19774](#), [19778](#), [19779](#), [19948](#), [19977](#), [20150](#), [20164](#), [20456](#), [20481](#), [20504](#), [20508](#), [20509](#), [20516](#), [20517](#), [20521](#), [20522](#)
- \g_regex_balance_intarray [796](#), [798](#), [17781](#), [19773](#), [19929](#), [19937](#)
- \l_regex_balance_tl [215](#), [861](#), [19888](#), [19949](#), [19978](#), [20027](#)
- __regex_branch:n [810](#), [826](#), [845](#), [17778](#), [18312](#), [18784](#), [18827](#), [18997](#), [19120](#), [19477](#)
- __regex_break_point:TF [799](#), [822](#), [842](#), [17790](#), [17796](#), [19379](#), [19380](#), [19603](#), [19626](#)
- __regex_break_true:w [799](#), [799](#), [17790](#), [17796](#), [17801](#), [17808](#), [17815](#), [17821](#), [17828](#), [17836](#), [17881](#), [17892](#), [17908](#), [18588](#), [19618](#)
- __regex_build:N [870](#), [19277](#), [20246](#), [20252](#), [20256](#), [20260](#)
- __regex_build:n [870](#), [19277](#), [20241](#), [20250](#), [20255](#), [20258](#)
- __regex_build_for_cs:n [17904](#), [19301](#)
- __regex_build_new_state: [19293](#), [19294](#), [19310](#), [19311](#), [19340](#), [19361](#), [19393](#), [19430](#), [19435](#), [19482](#), [19497](#), [19502](#), [19541](#), [19560](#), [19595](#), [19599](#), [19632](#)
- __regex_build_transition_-left:NNN [19336](#), [19543](#), [19557](#), [19574](#)
- __regex_build_transition_-right:nNn [19336](#), [19394](#), [19432](#), [19485](#), [19489](#), [19514](#), [19539](#), [19546](#), [19554](#), [19582](#), [19592](#)
- __regex_build_transitions_-lazyness:NNNN [19359](#), [19401](#), [19407](#), [19419](#)
- \l_regex_capturing_group_int [796](#), [839](#), [877](#), [19276](#), [19291](#), [19448](#), [19450](#), [19461](#), [19462](#), [19470](#), [19471](#), [19474](#), [20024](#), [20418](#), [20486](#), [20494](#)
- \l_regex_case_changed_char_int [800](#), [17817](#), [17820](#), [17831](#), [17834](#), [17835](#), [17842](#), [17846](#), [17851](#), [19647](#), [19742](#)
- \c_regex_catcode_A_int [18201](#)
- \c_regex_catcode_B_int [18201](#)
- \c_regex_catcode_C_int [18201](#)
- \c_regex_catcode_D_int [18201](#)
- \c_regex_catcode_E_int [18201](#)
- \c_regex_catcode_in_class_mode_-int [18191](#), [18299](#), [18654](#), [18883](#), [18912](#)
- \g_regex_catcode_intarray [796](#), [798](#), [17781](#), [19771](#), [19788](#)
- \c_regex_catcode_L_int [18201](#)
- \c_regex_catcode_M_int [18201](#)
- \c_regex_catcode_mode_int [18191](#), [18296](#), [18359](#), [18686](#), [18881](#), [18910](#)
- \c_regex_catcode_O_int [18201](#)
- \c_regex_catcode_P_int [18201](#)
- \c_regex_catcode_S_int [18201](#)
- \c_regex_catcode_T_int [18201](#)
- \c_regex_catcode_U_int [18201](#)
- \l_regex_catcodes_bool [18198](#), [18917](#), [18921](#), [18956](#)
- \l_regex_catcodes_int [810](#), [18198](#), [18309](#), [18390](#), [18391](#), [18397](#), [18673](#), [18690](#), [18782](#), [18791](#), [18878](#), [18914](#), [18949](#), [18951](#), [18957](#), [18958](#)
- __regex_char_if_alphanumeric:N [18171](#)
- __regex_char_if_alphanumeric:NTF [18149](#), [18352](#), [20124](#)
- __regex_char_if_special:N [18149](#)
- __regex_char_if_special:NTF [18149](#), [18348](#)
- \g_regex_charcode_intarray [796](#), [798](#), [17781](#), [19769](#), [19785](#)
- __regex_chk_c_allowed:TF [18281](#), [18871](#)
- __regex_class:NnnN [809](#), [816](#), [818](#), [824](#), [17779](#), [18386](#), [18681](#), [18682](#), [18688](#), [19013](#), [19089](#), [19099](#), [19133](#), [19373](#)
- \c_regex_class_mode_int [18191](#), [18286](#), [18300](#)
- __regex_class_repeat:n [843](#), [19383](#), [19389](#), [19405](#), [19414](#)
- __regex_class_repeat:nN [19384](#), [19398](#)
- __regex_class_repeat:nnN [19385](#), [19412](#)
- __regex_command_K: [810](#), [19114](#), [19134](#), [19630](#)
- __regex_compile:n [18341](#), [19279](#), [20208](#), [20213](#), [20218](#), [20223](#)
- __regex_compile:w [815](#), [18304](#), [18343](#), [18963](#)

- `__regex_compile_$$` [18608](#)
- `__regex_compile_(:` [18799](#)
- `__regex_compile_):` [18830](#)
- `__regex_compile_.` [18579](#)
- `__regex_compile_/A:` [18608](#)
- `__regex_compile_/B:` [18632](#)
- `__regex_compile_/b:` [18632](#)
- `__regex_compile_/c:` [18870](#)
- `__regex_compile_/D:` [18591](#)
- `__regex_compile_/d:` [18591](#)
- `__regex_compile_/G:` [18608](#)
- `__regex_compile_/H:` [18591](#)
- `__regex_compile_/h:` [18591](#)
- `__regex_compile_/K:` [19111](#)
- `__regex_compile_/N:` [18591](#)
- `__regex_compile_/S:` [18591](#)
- `__regex_compile_/s:` [18591](#)
- `__regex_compile_/u:` [19033](#)
- `__regex_compile_/V:` [18591](#)
- `__regex_compile_/v:` [18591](#)
- `__regex_compile_/W:` [18591](#)
- `__regex_compile_/w:` [18591](#)
- `__regex_compile_/Z:` [18608](#)
- `__regex_compile_/z:` [18608](#)
- `__regex_compile_[:` [18665](#)
- `__regex_compile_]:` [18650](#)
- `__regex_compile_^:` [18608](#)
- `__regex_compile_abort_tokens:n` .
..... [18400](#), [18424](#), [18763](#), [18773](#)
- `__regex_compile_anchor:NTF` .. [18608](#)
- `__regex_compile_c[:w` [18906](#)
- `__regex_compile_cC:NN` [18885](#), [18894](#)
- `__regex_compile_c_lbrack_add:N` .
..... [18906](#)
- `__regex_compile_c_lbrack_end:` [18906](#)
- `__regex_compile_c_lbrack_-`
 `loop:NN` [18906](#)
- `__regex_compile_c_test:NN` ... [18870](#)
- `__regex_compile_class:NN` [18695](#)
- `__regex_compile_class:TFNN`
..... [824](#), [18680](#), [18691](#), [18695](#)
- `__regex_compile_class_catcode:w`
..... [18672](#), [18684](#)
- `__regex_compile_class_normal:w` .
..... [18675](#), [18678](#)
- `__regex_compile_class_posix:NNNNw`
..... [18714](#)
- `__regex_compile_class_posix_-`
 `end:w` [18714](#)
- `__regex_compile_class_posix_-`
 `loop:w` [18714](#)
- `__regex_compile_class_posix_-`
 `test:w` [18668](#), [18714](#)
- `__regex_compile_cs_aux:Nn` ... [18972](#)
- `__regex_compile_cs_aux:NNnnnN` [18972](#)
- `__regex_compile_end:`
..... [815](#), [18304](#), [18368](#), [18981](#)
- `__regex_compile_end_cs:` [18364](#), [18972](#)
- `__regex_compile_escaped:N`
..... [18353](#), [18370](#)
- `__regex_compile_group_begin:N` ..
.. [18777](#), [18813](#), [18818](#), [18836](#), [18838](#)
- `__regex_compile_group_end:`
..... [18777](#), [18833](#)
- `__regex_compile_lparen:w`
..... [18802](#), [18804](#)
- `__regex_compile_one:n`
.... [18380](#), [18523](#), [18529](#), [18583](#),
 [18594](#), [18597](#), [18607](#), [18754](#), [18988](#)
- `__regex_compile_quantifier:w` ...
..... [18398](#), [18409](#), [18660](#), [18793](#)
- `__regex_compile_quantifier_*`:w .
..... [18436](#)
- `__regex_compile_quantifier_+:`w .
..... [18436](#)
- `__regex_compile_quantifier_?:w` .
..... [18436](#)
- `__regex_compile_quantifier_-`
 `abort:nNN`
.. [18418](#), [18446](#), [18465](#), [18479](#), [18502](#)
- `__regex_compile_quantifier_-`
 `braced_auxi:w` [18442](#)
- `__regex_compile_quantifier_-`
 `braced_auxii:w` [18442](#)
- `__regex_compile_quantifier_-`
 `braced_auxiii:w` [18442](#)
- `__regex_compile_quantifier_-`
 `lazyness:nnNN` [818](#), [18427](#), [18437](#),
 [18439](#), [18441](#), [18454](#), [18475](#), [18497](#)
- `__regex_compile_quantifier_-`
 `none:` [18414](#), [18416](#), [18418](#)
- `__regex_compile_range:Nw`
..... [18521](#), [18534](#)
- `__regex_compile_raw:N`
..... [18231](#), [18349](#), [18353](#),
 [18355](#), [18373](#), [18378](#), [18405](#), [18514](#),
 [18516](#), [18536](#), [18582](#), [18628](#), [18663](#),
 [18711](#), [18725](#), [18743](#), [18796](#), [18801](#),
 [18814](#), [18824](#), [18832](#), [18848](#), [18849](#),
 [18850](#), [18857](#), [18864](#), [18865](#), [18866](#),
 [18874](#), [18928](#), [18977](#), [19045](#), [19051](#)
- `__regex_compile_raw_error:N` ...
..... [18511](#),
 [18619](#), [18635](#), [18644](#), [19036](#), [19115](#)
- `__regex_compile_special:N` [18349](#),
 [18370](#), [18411](#), [18429](#), [18452](#), [18457](#),
 [18473](#), [18487](#), [18520](#), [18539](#), [18698](#),

- 18716, 18729, 18750, 18806, 18841,
18857, 18896, 18915, 19038, 19054
- _regex_compile_special_group_
-:w [18839](#)
- _regex_compile_special_group_
::w [18835](#)
- _regex_compile_special_group_
i:w [18839](#)
- _regex_compile_special_group_
l:w [18835](#)
- _regex_compile_u_end:
..... [19057](#), [19063](#), [19068](#)
- _regex_compile_u_in_cs:
..... [19074](#), [19077](#)
- _regex_compile_u_in_cs_aux:n ..
..... [19084](#), [19087](#)
- _regex_compile_u_loop:NN ... [19033](#)
- _regex_compile_u_not_cs:
..... [19072](#), [19093](#)
- _regex_compile_l: [18822](#)
- _regex_compute_case_changed_
char: [17818](#), [17832](#), [17840](#)
- _regex_count:nnN [20250](#), [20252](#), [20297](#)
- \c_regex_cs_in_class_mode_int ..
..... [18191](#), [18969](#)
- \c_regex_cs_mode_int . [18191](#), [18967](#)
- \l_regex_cs_name_tl
..... [17785](#), [17901](#), [17906](#)
- \l_regex_curr_catcode_int [17860](#),
[17879](#), [17887](#), [17898](#), [19647](#), [19787](#)
- \l_regex_curr_char_int
..... [17800](#), [17806](#),
[17807](#), [17814](#), [17826](#), [17827](#), [17842](#),
[17843](#), [17844](#), [17845](#), [17850](#), [17880](#),
[18587](#), [19624](#), [19647](#), [19741](#), [19784](#)
- _regex_curr_cs_to_str:
..... [17762](#), [17890](#), [17901](#)
- \l_regex_curr_pos_int [797](#), [17765](#),
[19317](#), [19617](#), [19642](#), [19675](#), [19677](#),
[19680](#), [19706](#), [19715](#), [19740](#), [19756](#),
[19770](#), [19772](#), [19774](#), [19775](#), [19776](#),
[19786](#), [19789](#), [19870](#), [19879](#), [20348](#)
- \l_regex_curr_state_int
..... [851](#), [857](#), [19651](#), [19792](#),
[19797](#), [19798](#), [19800](#), [19804](#), [19807](#),
[19829](#), [19834](#), [19839](#), [19840](#), [19848](#)
- \l_regex_curr_submatches_prop ..
..... [19652](#), [19712](#), [19809](#),
[19841](#), [19842](#), [19860](#), [19869](#), [19881](#)
- \l_regex_default_catcodes_int ..
..... [810](#), [18198](#), [18308](#),
[18309](#), [18397](#), [18690](#), [18782](#), [18791](#)
- _regex_disable_submatches: ...
.. [17903](#), [18964](#), [19862](#), [20291](#), [20300](#)
- \l_regex_empty_success_bool ...
.. [19660](#), [19700](#), [19704](#), [19877](#), [20358](#)
- _regex_escape_\\:w [18030](#)
- _regex_escape_/a:w [18030](#)
- _regex_escape_/break:w [18030](#)
- _regex_escape_/e:w [18030](#)
- _regex_escape_/f:w [18030](#)
- _regex_escape_/n:w [18030](#)
- _regex_escape_/r:w [18030](#)
- _regex_escape_/t:w [18030](#)
- _regex_escape_/x:w [18050](#)
- _regex_escape_\\:w [18014](#)
- _regex_escape_break:w [18030](#)
- _regex_escape_escaped:N
..... [18001](#), [18024](#), [18027](#)
- _regex_escape_loop:N
..... [805](#), [18007](#), [18014](#), [18050](#),
[18089](#), [18097](#), [18098](#), [18115](#), [18127](#)
- _regex_escape_raw:N
.. [806](#), [18002](#), [18027](#), [18039](#), [18041](#),
[18043](#), [18045](#), [18047](#), [18049](#), [18066](#)
- _regex_escape_unescaped:N
..... [18000](#), [18017](#), [18027](#)
- _regex_escape_use:nnnn
..... [804](#), [815](#), [17989](#), [18346](#), [19950](#)
- _regex_escape_x:N [806](#), [18088](#), [18092](#)
- _regex_escape_x_end:w .. [806](#), [18050](#)
- _regex_escape_x_large:n [18050](#)
- _regex_escape_x_loop:N
..... [806](#), [18085](#), [18101](#)
- _regex_escape_x_loop_error: . [18101](#)
- _regex_escape_x_loop_error:n ..
..... [18104](#), [18116](#), [18121](#)
- _regex_escape_x_test:N
..... [806](#), [18053](#), [18070](#)
- _regex_escape_x_testii:N ... [18070](#)
- \l_regex_every_match_tl
..... [19659](#), [19719](#), [19723](#), [19728](#)
- _regex_extract: [872](#), [20315](#),
[20321](#), [20332](#), [20414](#), [20455](#), [20477](#)
- _regex_extract_all:nnN [20264](#), [20309](#)
- _regex_extract_b:wn [20414](#)
- _regex_extract_e:wn [20414](#)
- _regex_extract_once:nnN
..... [20262](#), [20309](#)
- _regex_extract_seq_aux:n
..... [20377](#), [20394](#)
- _regex_extract_seq_aux:ww .. [20394](#)
- \l_regex_fresh_thread_bool
..... [852](#), [856](#), [19636](#), [19639](#),
[19660](#), [19754](#), [19816](#), [19818](#), [19878](#)
- _regex_get_digits:NfW
..... [18217](#), [18444](#), [18459](#)

__regex_get_digits_loop:nw 18220, 18223, 18226
 __regex_get_digits_loop:w . . . 18217
 __regex_group:nnnN 809,
 826, 18813, 18818, 19127, 19297, 19445
 __regex_group_aux:nnnnN
 845, 19424, 19447, 19455, 19458
 __regex_group_aux:nnnnnN 844
 __regex_group_end_extract_seq:N
 20316, 20324, 20363, 20365
 __regex_group_end_replace:N
 20471, 20500, 20502
 \l__regex_group_level_int
 18190, 18307,
 18323, 18325, 18327, 18783, 18788
 __regex_group_no_capture:nnnN
 809, 18836, 19129, 19445
 __regex_group_repeat:nn 19440, 19492
 __regex_group_repeat:nnN
 19441, 19532
 __regex_group_repeat:nnnN
 19442, 19563
 __regex_group_repeat_aux:n
 846, 847, 19499, 19512, 19550, 19567
 __regex_group_resetting:nnnN
 809, 18838, 19131, 19456
 __regex_group_resetting_-
 loop:nnNn 19456
 __regex_group_submatches:nNN
 19500, 19505, 19535, 19551, 19565
 __regex_hexadecimal_use:N . . . 18129
 __regex_hexadecimal_use:NNTF
 18087, 18096, 18106, 18129
 __regex_if_end_range:NN 18534
 __regex_if_end_range:NNTF . . . 18534
 __regex_if_in_class:TF
 18241, 18316, 18383,
 18398, 18518, 18581, 18652, 18667,
 18801, 18824, 18832, 20583, 20596
 __regex_if_in_class_or_catcode:TF
 18261, 18610, 18634, 18643, 19035
 __regex_if_in_cs:TF
 18249, 18975, 20581, 20590
 __regex_if_match:nn
 20241, 20246, 20288
 __regex_if_raw_digit:NN 18229
 __regex_if_raw_digit:NNTF
 18219, 18225, 18229
 __regex_if_two_empty_matches:TF
 852, 19660, 19705, 19708, 19874
 __regex_if_within_catcode:TF
 18273, 18670
 \l__regex_internal_a_int
 818, 863, 17768,
 18444, 18455, 18466, 18476, 18480,
 18489, 18491, 18495, 18498, 18505,
 19406, 19409, 19415, 19420, 19501,
 19516, 19522, 19528, 19537, 19540,
 19544, 19547, 19552, 19555, 19558,
 19573, 19581, 19590, 20035, 20056
 \l__regex_internal_a_tl
 804, 833, 834, 835, 874,
 877, 17768, 17889, 17891, 17992,
 17999, 18012, 18732, 18737, 18752,
 18757, 18762, 18766, 18772, 18773,
 18983, 18992, 19040, 19070, 19080,
 19095, 19119, 19122, 19124, 19181,
 19200, 19223, 19234, 19331, 19332,
 19333, 19334, 19483, 19484, 19488,
 19490, 19947, 19982, 20227, 20236,
 20370, 20391, 20461, 20490, 20520
 \l__regex_internal_b_int
 17768, 18459, 18489, 18492,
 18493, 18495, 18499, 18506, 19517,
 19522, 19527, 19573, 19581, 19590
 \l__regex_internal_b_tl
 17768, 18005,
 18010, 18060, 18062, 18124, 18126
 \l__regex_internal_bool
 17768, 18731, 18736, 18756, 18765
 \l__regex_internal_c_int
 17768, 19519, 19524, 19525, 19529
 \l__regex_internal_regex
 815, 826, 18214, 18306,
 18335, 18781, 18792, 18985, 18991,
 19280, 20209, 20214, 20219, 20224
 \l__regex_internal_seq
 17768, 19250, 19251,
 19256, 19263, 19264, 19265, 19267
 \g__regex_internal_tl
 17768, 18004, 18007, 19079, 19083
 __regex_item_caseful_equal:n
 810, 17798, 17918,
 17919, 17923, 17924, 17925, 17926,
 17927, 17936, 17941, 17959, 17977,
 18310, 18859, 19015, 19090, 19140
 __regex_item_caseful_range:nn
 810, 17798, 17915,
 17930, 17933, 17934, 17935, 17949,
 17956, 17963, 17965, 17967, 17970,
 17971, 17972, 17973, 17978, 17981,
 17986, 17987, 18311, 18860, 19142
 __regex_item_caseless_equal:n
 810, 17812, 18843, 19144
 __regex_item_caseless_range:nn
 810, 17812, 18844, 19146
 __regex_item_catcode: 17857

```

\\__regex_item_catcode:nTF .....
    810, 824, 17857, 18391, 18692, 19151
\\__regex_item_catcode_reverse:nTF
    ..... 810, 17857, 18693, 19153
\\__regex_item_cs:n .....
    ..... 798, 810, 17896, 18991, 19160
\\__regex_item_equal:n .....
    .... 17855, 18310, 18524, 18530,
    18560, 18573, 18574, 18843, 18859
\\__regex_item_exact:nn .....
    ..... 810, 834, 17877, 19104, 19157
\\__regex_item_exact_cs:n .....
    810, 831, 17877, 18992, 19102, 19159
\\__regex_item_range:nn .....
    .. 17855, 18311, 18562, 18844, 18860
\\__regex_item_reverse:n .....
    .... 215, 810, 825, 17793, 17876,
    17940, 18598, 18756, 19155, 19627
\\l__regex_last_char_int .....
    ..... 19624, 19647, 19741
\\l__regex_left_state_int .....
    19272, 19295, 19325, 19332, 19345,
    19355, 19362, 19365, 19366, 19368,
    19369, 19395, 19403, 19406, 19433,
    19484, 19486, 19496, 19516, 19536,
    19538, 19566, 19569, 19572, 19575,
    19587, 19600, 19609, 19633, 19638
\\l__regex_left_state_seq .....
    ..... 19272, 19324, 19331, 19483
\\__regex_match:n .....
    .... 17906, 19666, 20294, 20304,
    20314, 20323, 20347, 20451, 20480
\\l__regex_match_count_int .....
    871, 872, 20271, 20301, 20302, 20307
\\__regex_match_init: ..... 19666
\\__regex_match_loop: .....
    ..... 853, 856, 19718, 19737
\\__regex_match_once: .....
    ..... 853, 854, 19683, 19702, 19733
\\__regex_match_one_active:n .. 19737
\\l__regex_match_success_bool ...
    852, 19663, 19711, 19724, 19730, 19876
\\l__regex_max_active_int .....
    ..... 19655, 19713, 19746,
    19750, 19755, 19854, 19855, 19859
\\l__regex_max_pos_int .....
    ..... 860, 18623, 18624, 18631,
    19244, 19317, 19642, 19680, 19756,
    20348, 20353, 20359, 20469, 20498
\\l__regex_max_state_int .....
    .. 838, 884, 19269, 19292, 19309,
    19347, 19348, 19354, 19356, 19357,
    19416, 19431, 19495, 19515, 19517,
    19525, 19569, 19575, 19583, 19593,
    19675, 19692, 19694, 19698, 20832
\\l__regex_min_active_int . 19655,
    19694, 19713, 19746, 19748, 19755
\\l__regex_min_pos_int 860, 18621,
    18630, 19242, 19642, 19677, 19696
\\l__regex_min_state_int .. 19269,
    19292, 19309, 19692, 19714, 20830
\\l__regex_min_submatch_int .....
    ..... 871, 874, 876, 19697,
    19699, 20274, 20374, 20485, 20493
\\l__regex_mode_int .....
    18191, 18243, 18251, 18254, 18263,
    18266, 18275, 18283, 18286, 18296,
    18297, 18299, 18300, 18345, 18359,
    18361, 18654, 18657, 18658, 18659,
    18686, 18697, 18879, 18880, 18908,
    18909, 18965, 18966, 19071, 19113
\\__regex_mode_quit_c: .....
    ..... 18294, 18382, 18780
\\__regex_msg_repeated:nnN .....
    .. 19196, 19218, 19222, 19232, 20794
\\__regex_multi_match:n .....
    852, 19721, 20302, 20321, 20329, 20477
\\c__regex_no_match_regex .....
    ..... 17776, 18214, 20205
\\c__regex_outer_mode_int .....
    18191, 18254, 18266, 18275, 18283,
    18297, 18345, 18361, 19071, 19113
\\__regex_pop_lr_states: .....
    ..... 19314, 19322, 19438
\\__regex_posix_alnum: ..... 17943
\\__regex_posix_alpha: ..... 17943
\\__regex_posix_ascii: ..... 17943
\\__regex_posix_blank: ..... 17943
\\__regex_posix_cntrl: ..... 17943
\\__regex_posix_digit: ..... 17943
\\__regex_posix_graph: ..... 17943
\\__regex_posix_lower: ..... 17943
\\__regex_posix_print: ..... 17943
\\__regex_posix_punct: ..... 17943
\\__regex_posix_space: ..... 17943
\\__regex_posix_upper: ..... 17943
\\__regex_posix_word: ..... 17943
\\__regex_posix_xdigit: ..... 17943
\\__regex_prop.: ..... 821, 18579
\\__regex_prop_d: ... 822, 17914, 17961
\\__regex_prop_h: ..... 17914, 17953
\\__regex_prop_N: ..... 17914, 18607
\\__regex_prop_s: ..... 17914
\\__regex_prop_v: ..... 17914
\\__regex_prop_w: .....
    .. 17914, 17982, 19625, 19627, 19628

```

```

__regex_push_lr_states: .....
    ..... 19312, 19322, 19436
__regex_query_get: .....
    ..... 19717, 19743, 19782
__regex_query_range:nn 860, 19893,
    19898, 19917, 19988, 20464, 20497
__regex_query_range_loop:ww . 19898
__regex_query_set:nnn .....
    .... 852, 19676, 19679, 19681, 19767
__regex_query_submatch:n .....
    ..... 19915, 20025, 20408
__regex_replace_all:nnN 20268, 20474
__regex_replace_once:nnN .....
    ..... 20266, 20445
__regex_replacement:n .....
    ..... 19942, 20450, 20479
__regex_replacement_aux:n ... 19942
__regex_replacement_balance-
    one_match:n ..... 215,
    859, 859, 19889, 19975, 20458, 20488
__regex_replacement_c:w ..... 20065
__regex_replacement_c_A:w 862, 20143
__regex_replacement_c_B:w ... 20146
__regex_replacement_c_C:w ... 20155
__regex_replacement_c_D:w ... 20157
__regex_replacement_c_E:w ... 20160
__regex_replacement_c_L:w ... 20169
__regex_replacement_c_M:w ... 20172
__regex_replacement_c_O:w ... 20175
__regex_replacement_c_P:w ... 20178
__regex_replacement_c_S:w ... 20184
__regex_replacement_c_T:w ... 20192
__regex_replacement_c_U:w ... 20195
__regex_replacement_cat:NNN ...
    ..... 20073, 20103
\l__regex_replacement_category-
    seq ..... 19886,
    19969, 19972, 19973, 20001, 20117
\l__regex_replacement_category-
    t1 ..... 862, 19886,
    19996, 20002, 20005, 20118, 20119
__regex_replacement_char:nnN ...
    ..... 868, 20138,
    20145, 20152, 20159, 20166, 20171,
    20174, 20177, 20181, 20194, 20197
\l__regex_replacement_csnames-
    int ..... 859, 19885, 19963,
    19965, 19967, 20026, 20081, 20086,
    20096, 20098, 20108, 20149, 20163
__regex_replacement_cu_aux:Nw ...
    ..... 20070, 20079, 20091
__regex_replacement_do_one-
    match:n . 19891, 19986, 20463, 20496
__regex_replacement_error:NNN ..
    ..... 20036, 20048,
    20059, 20074, 20077, 20092, 20199
__regex_replacement_escaped:N ..
    ..... 19959, 20010, 20122
__regex_replacement_exp_not:N ..
    ..... 864, 19897, 20070
__regex_replacement_g:w ..... 20032
__regex_replacement_g_digits:NN
    ..... 20032
__regex_replacement_normal:n ...
    19955, 19960, 19994, 20017, 20034,
    20040, 20067, 20090, 20100, 20115
__regex_replacement_put-
    submatch:n ... 20015, 20022, 20055
__regex_replacement_rbrace:N ...
    ..... 19953, 20054, 20094
__regex_replacement_u:w ..... 20088
__regex_return: .....
    870, 20242, 20247, 20258, 20260, 20280
\l__regex_right_state_int .....
    .... 19272, 19298, 19315, 19327,
    19334, 19346, 19355, 19356, 19395,
    19402, 19408, 19421, 19431, 19433,
    19486, 19490, 19501, 19515, 19524,
    19536, 19540, 19544, 19547, 19552,
    19555, 19558, 19566, 19580, 19583,
    19586, 19589, 19593, 19609, 19638
\l__regex_right_state_seq .....
    ..... 19272, 19326, 19333, 19488
\l__regex_saved_success_bool ...
    ..... 852, 17905, 17910, 19663
__regex_show:N . 19117, 20224, 20233
__regex_show_anchor_to_str:N ...
    ..... 19139, 19237
__regex_show_class:NnnnN .....
    ..... 19133, 19198
__regex_show_group_aux:nnnnN ...
    ..... 19128, 19130, 19132, 19189
__regex_show_item_catcode:NnTF .
    ..... 19152, 19154, 19248
__regex_show_item_exact_cs:n ...
    ..... 19159, 19261
\l__regex_show_lines_int .....
    ..... 18216, 19170, 19201, 19205
__regex_show_one:n 19123, 19135,
    19137, 19141, 19143, 19145, 19148,
    19158, 19162, 19168, 19184, 19191,
    19195, 19210, 19221, 19229, 19266
__regex_show_pop: .... 19178, 19194
\l__regex_show_prefix_seq .....
    ..... 18215, 19122,
    19124, 19163, 19174, 19179, 19181

```

- __regex_show_push:n 19164, [19178](#), 19192, 19202
- __regex_show_scope:nn 19156, 19161, [19178](#), 19253
- __regex_single_match: [852](#), 17902, [19721](#), 20292, 20312, 20448
- __regex_split:nnN 20270, [20326](#)
- __regex_standard_escapechar: ... 17731, 18003, 18344, 19290
- \l_regex_start_pos_int 18622, 19243, [19642](#), 19706, 19710, 19716, 20331, 20343, 20356, 20359, 20438, 20498
- \g__regex_state_active_intarray . 795, [851](#), [851](#), [852](#), [19657](#), 19693, 19796, 19799, 19806, 19833
- \l_regex_step_int 795, [19654](#), 19695, 19739, 19797, 19800, 19808, 19822, 19824
- __regex_store_state:n 19714, 19847, [19850](#)
- __regex_store_submatches: [19850](#), 19864
- __regex_submatch_balance:n 19890, [19921](#), 19979, 20028, 20399
- \g__regex_submatch_begin_intarray 796, [859](#), 19895, 19918, 19934, 19938, 19990, [20277](#), 20338, 20341, 20354, 20420, 20442
- \g__regex_submatch_end_intarray . 796, 19919, 19926, 19930, [20277](#), 20335, 20351, 20422, 20444, 20466
- \l_regex_submatch_int 796, [871](#), [873](#), [874](#), [876](#), 19699, [20274](#), 20350, 20352, 20355, 20357, 20360, 20376, 20417, 20421, 20423, 20425, 20426, 20487, 20495
- \g__regex_submatch_prev_intarray 796, [871](#), [875](#), 19894, 19989, [20277](#), 20333, 20349, 20424, 20437
- \g__regex_success_bool 852, 17905, 17907, 17910, [19663](#), 19690, 19724, 19731, 20282, 20416, 20452
- \l_regex_success_pos_int 19642, 19696, 19710, 19879, 20331
- \l_regex_success_submatches_prop .. [851](#), [875](#), [19652](#), 19880, 20428
- __regex_tests_action_cost:n ... 19373, 19394, 19403, 19421
- \g__regex_thread_state_intarray . 796, [850](#), [851](#), [851](#), [857](#), [19657](#), 19764, 19853
- __regex_tmp:w 17750, 17752, 17756, 17758, [17767](#), 18591, 18601, 18602, 18603, 18604, 18605, 18616, 18621, 18622, 18623, 18624, 18625, 18630, 18631, 20253, 20262, 20264, 20266, 20268, 20270
- __regex_toks_clear:N . [17734](#), 19354
- __regex_toks_memcpy:NNn [17739](#), 19526
- __regex_toks_put_left:Nn 17748, 19337, 19508, 19509
- __regex_toks_put_right:Nn 797, [17748](#), 19295, 19298, 19315, 19339, 19362, 19600, 19633
- __regex_toks_set:Nn 17734, 19775, 19859
- __regex_toks_use:w 17733, 19765, 19798, 19911, 20835
- __regex_trace_states:n 19285, 19304, [20825](#)
- __regex_use_state: 19791, 19810, 19836
- __regex_use_state_and_submatches:nn 854, 19763, [19802](#)
- \l_regex_zeroth_submatch_int ... 871, [875](#), [20274](#), 20334, 20336, 20339, 20342, 20417, 20435, 20438, 20459, 20463, 20467
- \regular_expression 214
- \relax 14, 21, 39, 43, 49, 90, 92, 98, 123, 146, 167, 181, 212, 213, 214, 215, 216, 217, 218, 219, 220, 221, 222, 225, 226, 227, 228, 229, 230, 231, 232, 233, 234, 235, 520
- \relpenalty 521
- \RequirePackage 149
- reverse commands:
 - \reverse_if:N 21, [380](#), [409](#), [410](#), [618](#), [1331](#), 4346, 4486, 5385, 5387, 5389, 5391, 9991, 9996, 10000, 10002, 12177, 15383, 16051, 16074, 17806, 17807, 17826, 17827, 17834, 17835
- right commands:
 - \c_right_brace_str 62, [4420](#), 18114, 18452, 18473, 18487, 18973, 18977, 19056, 19952
 - \rightghost 952
 - \righthyphenmin 523
 - \rightmargin kern 788
 - \rightskip 524
 - \romannumeral 525
 - round 195
 - round+ [11818](#)
 - round- [11818](#)
 - round0 [11818](#)
 - \rPCODE 789

- \rule 22103, 22158
- S**
- \saveboxresource 977
- \savecatcodetable 929
- \saveimageresource 978
- \savepos 976
- \savingshyphcodes 656
- \savingsvdiscards 657
- scan commands:
- \scan_align_safe_stop: 22455
- \scan_stop: 9,
 74, 94, 95, 125, 125, 126, 126, 252,
 266, 297, 309, 309, 311, 323, 323,
 339, 342, 355, 380, 410, 414, 433,
 471, 471, 477, 480, 481, 490, 511,
 540, 540, 540, 614, 618, 618, 619,
 619, 622, 810, 831, 977, 1358, 1590,
 1672, 1677, 1813, 1942, 1960, 1970,
 1988, 2381, 2641, 2677, 2703, 2726,
 2742, 3048, 3072, 4347, 4442, 4455,
 4460, 4461, 4462, 4525, 4876, 5576,
 5998, 5999, 6001, 6003, 6007, 6232,
 7358, 7432, 7634, 7748, 7757, 7766,
 9243, 9245, 9398, 9400, 9851, 9881,
 9884, 9889, 9894, 9899, 9902, 9907,
 9910, 10157, 10186, 10189, 10200,
 10203, 10208, 10211, 10245, 10253,
 10258, 10287, 10324, 10327, 10340,
 10343, 10348, 10351, 10362, 10415,
 10439, 10476, 10480, 10481, 10498,
 10499, 12175, 12179, 12341, 12358,
 12658, 12705, 12706, 12918, 12948,
 13552, 16872, 17432, 17471, 17475,
 17481, 17483, 17499, 17530, 17532,
 17890, 17891, 18227, 18999, 19263,
 19786, 19789, 19812, 20140, 20189,
 20367, 20981, 22099, 22154, 23148,
 23149, 23315, 23318, 23341, 24462,
 24464, 24466, 24769, 25133, 25139
- scan internal commands:
- \g__scan_marks_tl ... 6222, 6225, 6231
- __scan_new:N 95, 6223, 6235, 6237,
 7773, 11348, 11354, 11355, 11356,
 11357, 11358, 11359, 11360, 17311
- \scantextokens 930
- \scantokens 658
- \scriptfont 526
- \scriptscriptfont 527
- \scriptscriptstyle 528
- \scriptspace 529
- \scriptstyle 530
- \scrollmode 531
- sec 196
- secd 196
- seq commands:
- \c_empty_seq 73, 387, 4583,
 4587, 4591, 4594, 4776, 4813, 4821
- \l_foo_seq 210
- \seq_clear:N 64, 64, 73, 4590, 4597,
 4720, 8468, 8531, 9155, 19163, 19973
- \seq_clear_new:N 64, 4596
- \seq_concat:NNN ... 65, 73, 4673, 9163
- \seq_const_from_clist:Nn . 245, 23137
- \seq_count:N 66, 70,
 72, 88, 4939, 5011, 5025, 19972, 23134
- \seq_elt:w 386
- \seq_elt_end: 386
- \seq_gclear:N 64, 4590, 4600
- \seq_gclear_new:N 64, 4596
- \seq_gconcat:NNN 65, 4673, 9174
- \seq_get:NN ... 71, 5078, 19483, 19488
- \seq_get:NNTF 71, 5084
- \seq_get_left:NN
 ... 65, 4829, 5078, 5079, 5084, 5085
- \seq_get_left:NNTF 67, 4896, 4900, 4901
- \seq_get_right:NN 66, 4854
- \seq_get_right:NNTF
 ... 67, 4896, 4903, 4904
- \seq_gpop:NN 71, 5078, 9104
- \seq_gpop:NNTF .. 72, 5084, 9227, 9382
- \seq_gpop_left:NN
 ... 66, 4840, 5082, 5083, 5088, 5089
- \seq_gpop_left:NNTF
 ... 67, 4906, 4917, 4918
- \seq_gpop_right:NN 66, 4869
- \seq_gpop_right:NNTF
 ... 67, 4906, 4923, 4924
- \seq_gpush:Nn
 ... 25, 72, 5058, 9090, 9254, 9410
- \seq_gput_left:Nn
 . 65, 4683, 5068, 5069, 5070, 5071,
 5072, 5073, 5074, 5075, 5076, 5077
- \seq_gput_right:Nn
 65, 4704, 8952, 8959, 8972, 9076, 9081
- \seq_gremove_all:Nn 68, 4730
- \seq_gremove_duplicates:N .. 68, 4714
- \seq_greverse:N 68, 4756
- \seq_gset_eq:NN . 64, 4594, 4602, 4717
- \seq_gset_filter:NNn 245, 23111
- \seq_gset_from_clist:NN 64, 4610
- \seq_gset_from_clist:Nn 64, 4610
- \seq_gset_map:NNn 245, 23121
- \seq_gset_split:Nnn
 ... 65, 4636, 9181, 9347
- \seq_gsort:Nn 68, 4774, 16947
- \seq_if_empty:NTF 68,
 4774, 4783, 4784, 6533, 19969, 23133

- \seq_if_empty_p:N [68](#), [4774](#)
- \seq_if_exist:NTF
 - [65](#), [4597](#), [4600](#), [4679](#), [5023](#)
- \seq_if_exist_p:N [65](#), [4679](#)
- \seq_if_in:NnTF
 - [68](#), [72](#), [73](#), [4723](#), [4786](#), [4805](#), [4806](#), [4807](#), [4808](#), [9253](#), [9409](#), [9804](#)
- \seq_item:Nn [66](#), [213](#), [946](#), [4926](#), [8549](#), [8550](#), [8555](#), [23134](#)
- \seq_log:N [74](#), [5090](#)
- \seq_map_break: [69](#), [245](#), [245](#), [4950](#), [4960](#), [4961](#), [4996](#), [5007](#), [11119](#)
- \seq_map_break:n [70](#), [397](#), [4950](#), [8488](#), [8502](#), [9019](#), [16950](#), [16957](#)
- \seq_map_function:NN
 - [4](#), [69](#), [243](#), [4954](#), [5016](#), [5100](#), [6539](#), [8553](#), [9166](#), [19174](#), [19256](#)
- \seq_map_inline:Nn
 - [69](#), [69](#), [73](#), [946](#), [4721](#), [4992](#), [8483](#), [8988](#), [9018](#), [11112](#), [16950](#), [16957](#)
- \seq_map_variable:NNn [69](#), [4999](#)
- \seq_mapthread_function:NNN
 - [245](#), [23088](#)
- \seq_new:N [4](#), [64](#), [64](#), [4584](#), [4597](#), [4600](#), [4713](#), [5104](#), [5105](#), [5106](#), [5107](#), [7145](#), [7148](#), [8440](#), [8441](#), [8944](#), [8967](#), [8981](#), [8983](#), [9179](#), [9343](#), [10537](#), [17774](#), [18215](#), [19274](#), [19275](#), [19887](#)
- \seq_pop:N
 - [71](#), [5078](#), [19331](#), [19333](#), [20001](#)
- \seq_pop:NNTF [72](#), [5084](#)
- \seq_pop_left:NN
 - [66](#), [4840](#), [5080](#), [5081](#), [5086](#), [5087](#)
- \seq_pop_left:NNTF [67](#), [4906](#), [4914](#), [4915](#)
- \seq_pop_right:NN
 - [66](#), [4869](#), [19122](#), [19181](#)
- \seq_pop_right:NNTF
 - [67](#), [4906](#), [4920](#), [4921](#)
- \seq_push:Nn
 - [72](#), [5058](#), [5065](#), [19324](#), [19326](#), [20117](#)
- \seq_put_left:Nn [65](#), [4683](#), [5058](#), [5059](#), [5060](#), [5061](#), [5062](#), [5063](#), [5064](#), [5065](#), [5066](#), [5067](#), [8478](#)
- \seq_put_right:Nn [65](#), [72](#), [73](#), [4704](#), [4724](#), [8539](#), [9800](#), [9805](#), [19124](#), [19179](#)
- \seq_rand_item:N [245](#), [23131](#)
- \seq_remove_all:Nn
 - [65](#), [68](#), [72](#), [73](#), [4730](#), [9808](#), [9812](#)
- \seq_remove_duplicates:N
 - [68](#), [72](#), [73](#), [4714](#), [9164](#)
- \seq_reverse:N [68](#), [392](#), [4756](#)
- \seq_set_eq:NN [64](#), [73](#), [4591](#), [4602](#), [4715](#)
- \seq_set_filter:NNn
 - [245](#), [946](#), [19251](#), [23111](#)
- \seq_set_from_clist:NN [64](#), [4610](#)
- \seq_set_from_clist:Nn
 - [64](#), [946](#), [4610](#), [9159](#), [9172](#), [11041](#)
- \seq_set_map:NNn ... [245](#), [19264](#), [23121](#)
- \seq_set_split:Nnn
 - .. [65](#), [4636](#), [7146](#), [7149](#), [19250](#), [19263](#)
- \seq_show:N [74](#), [499](#), [5090](#)
- \seq_sort:Nn [68](#), [4774](#), [16947](#)
- \seq_use:Nn [71](#), [5021](#), [19267](#)
- \seq_use:Nnnn [70](#), [5021](#)
- \g_tmpa_seq [74](#), [5104](#)
- \l_tmpa_seq [74](#), [5104](#)
- \g_tmpb_seq [74](#), [5104](#)
- \l_tmpb_seq [74](#), [5104](#)
- seq internal commands:
 - __seq_count:n [5011](#)
 - __seq_get_left:wnw [4829](#)
 - __seq_get_right_loop:nn .. [395](#), [4854](#)
 - __seq_if_in: [4786](#)
 - \l__seq_internal_a_tl
 - [388](#), [4580](#), [4644](#), [4648](#), [4654](#), [4659](#), [4661](#), [4745](#), [4750](#), [4790](#), [4794](#)
 - \l__seq_internal_b_tl
 - [4580](#), [4741](#), [4745](#), [4793](#), [4794](#)
 - __seq_item:n [74](#), [74](#), [74](#), [386](#), [390](#), [393](#), [394](#), [395](#), [395](#), [398](#), [398](#), [399](#), [400](#), [766](#), [767](#), [874](#), [945](#), [946](#), [4575](#), [4687](#), [4695](#), [4705](#), [4707](#), [4712](#), [4762](#), [4763](#), [4765](#), [4770](#), [4791](#), [4834](#), [4837](#), [4847](#), [4875](#), [4876](#), [4887](#), [4973](#), [4978](#), [4984](#), [4988](#), [5032](#), [5047](#), [5050](#), [5053](#), [16951](#), [16958](#), [20367](#), [20396](#), [23127](#)
 - __seq_item:nN [4926](#)
 - __seq_item:nnn [4926](#)
 - __seq_item:wNn [4926](#)
 - __seq_map_function:NNn [4954](#)
 - __seq_mapthread_function:Nnnwnn
 - [23088](#)
 - __seq_mapthread_function:wNN . [23088](#)
 - __seq_mapthread_function:wNw . [23088](#)
 - __seq_pop:NNNN
 - [4811](#), [4841](#), [4843](#), [4870](#), [4872](#)
 - __seq_pop_item_def: [74](#), [74](#), [4752](#), [4970](#), [4996](#), [5007](#), [23119](#), [23129](#)
 - __seq_pop_left:NNN . [4840](#), [4907](#), [4909](#)
 - __seq_pop_left:wnwNNN [4840](#)
 - __seq_pop_right:NNN
 - [391](#), [4869](#), [4911](#), [4913](#)
 - __seq_pop_right_loop:nn [4869](#)
 - __seq_pop_TF:NNNN [396](#), [4811](#), [4897](#), [4899](#), [4907](#), [4909](#), [4911](#), [4913](#)
 - __seq_push_item_def: [4970](#)
 - __seq_push_item_def:n ... [74](#), [74](#), [4736](#), [4970](#), [4994](#), [5001](#), [23117](#), [23127](#)

- __seq_put_left_aux:w [390](#), [4683](#)
- __seq_remove_all_aux:NNn [4730](#)
- __seq_remove_duplicates:NN .. [4714](#)
- \l_seq_remove_seq
..... [4713](#), [4720](#), [4723](#), [4724](#), [4726](#)
- __seq_reverse:NN [4756](#)
- __seq_reverse_item:nw [392](#)
- __seq_reverse_item:nwn [4756](#)
- __seq_set_filter:NNNn [23111](#)
- __seq_set_map:NNNn [23121](#)
- __seq_set_split:NNnn [4636](#)
- __seq_set_split_auxi:w ... [388](#), [4636](#)
- __seq_set_split_auxii:w .. [388](#), [4636](#)
- __seq_set_split_end: [388](#), [4636](#)
- __seq_show:NN [5090](#)
- __seq_tmp:w
..... [4582](#), [4762](#), [4765](#), [4875](#), [4887](#)
- __seq_use:NNnNnn [5021](#)
- __seq_use:nwnn [5021](#)
- __seq_use:nwwwnwn [5021](#)
- __seq_use_setup:w [5021](#)
- __seq_wrap_item:n
.. [388](#), [946](#), [4613](#), [4618](#), [4623](#), [4628](#),
[4645](#), [4670](#), [4712](#), [4748](#), [23117](#), [23140](#)
- \setbox [532](#)
- \setfontid [931](#)
- \setlanguage [533](#)
- \setrandomseed [979](#)
- \sfcode [183](#), [534](#)
- \sffamily [22092](#)
- \shapemode [932](#)
- \shellescape [862](#)
- \Shipout [1198](#)
- \shipout [535](#), [1185](#), [1186](#)
- \ShortText [75](#), [116](#), [133](#)
- \show [536](#)
- \showbox [537](#)
- \showboxbreadth [538](#)
- \showboxdepth [539](#)
- \showgroups [659](#)
- \showifs [660](#)
- \showlists [540](#)
- \showmode [1153](#)
- \showthe [541](#)
- \ShowTokens [204](#)
- \showtokens [661](#)
- sign [195](#)
- sin [196](#)
- sind [196](#)
- \sjis [1154](#)
- \skewchar [542](#)
- \skip [543](#), [7508](#)
- skip commands:
 \c_max_skip [165](#), [10269](#)
- \skip_add:Nn [163](#), [10198](#)
- \skip_const:Nn
..... [163](#), [552](#), [10153](#), [10269](#), [10270](#)
- \skip_eval:n [164](#), [164](#), [164](#),
[164](#), [10157](#), [10217](#), [10242](#), [10264](#), [10268](#)
- \skip_gadd:Nn [163](#), [10198](#)
- .skip_gset:N [174](#), [10933](#)
- \skip_gset:Nn [163](#), [548](#), [10184](#)
- \skip_gset_eq:NN [163](#), [10192](#)
- \skip_gsub:Nn [164](#), [10198](#)
- \skip_gzero:N [163](#), [10160](#), [10169](#)
- \skip_gzero_new:N [163](#), [10166](#)
- \skip_horizontal:N [165](#), [10249](#)
- \skip_horizontal:n
[165](#), [10249](#), [24812](#), [25162](#), [25308](#), [25748](#)
- \skip_if_eq:nnTF [164](#), [10214](#)
- \skip_if_eq_p:nn [164](#), [10214](#)
- \skip_if_exist:NTF
..... [163](#), [10167](#), [10169](#), [10172](#)
- \skip_if_exist_p:N [163](#), [10172](#)
- \skip_if_finite:nTF [164](#), [10224](#), [23146](#)
- \skip_if_finite_p:n [164](#), [10224](#)
- \skip_log:N [165](#), [10265](#)
- \skip_log:n [165](#), [10265](#)
- \skip_new:N
.. [163](#), [163](#), [10145](#), [10156](#), [10167](#),
[10169](#), [10271](#), [10272](#), [10273](#), [10274](#)
- .skip_set:N [174](#), [10933](#)
- \skip_set:Nn [163](#), [10184](#)
- \skip_set_eq:NN [163](#), [10192](#)
- \skip_show:N [164](#), [10261](#)
- \skip_show:n [165](#), [551](#), [10263](#)
- \skip_split_finite_else_action:nnNN
..... [246](#), [23144](#)
- \skip_sub:Nn [164](#), [10198](#)
- \skip_use:N
..... [164](#), [164](#), [10236](#), [10245](#), [10246](#)
- \skip_vertical:N [166](#), [10249](#)
- \skip_vertical:n [166](#), [10249](#)
- \skip_zero:N [163](#), [163](#), [166](#), [10160](#), [10167](#)
- \skip_zero_new:N [163](#), [10166](#)
- \g_tmpa_skip [165](#), [10271](#)
- \l_tmpa_skip [165](#), [10271](#)
- \g_tmpb_skip [165](#), [10271](#)
- \l_tmpb_skip [165](#), [10271](#)
- \c_zero_skip . [165](#), [539](#), [9855](#), [9858](#),
[10161](#), [10163](#), [10269](#), [23152](#), [23153](#)
- skip internal commands:
 __skip_if_finite:wwNw [10224](#)
- \skipdef [544](#)
- sort commands:
 \sort_ordered: [17236](#)
- \sort_return_same:
..... [202](#), [769](#), [17053](#), [17236](#), [17237](#)

```

\sort_return_swapped: .....
..... 202, 769, 17053, 17238, 17239
\sort_reversed: ..... 17236
sort internal commands:
\__sort:nnNnn ..... 771, 772
\l__sort_A_int .....
..... 769, 16836, 16841, 16848,
16851, 16860, 17018, 17023, 17026,
17046, 17061, 17080, 17082, 17083
\l__sort_B_int .....
.. 768, 769, 16836, 17023, 17027,
17035, 17037, 17038, 17070, 17071,
17080, 17081, 17090, 17091, 17093
\l__sort_begin_int .....
762, 769, 16834, 17015, 17083, 17093
\l__sort_block_int .....
.... 762, 763, 767, 16833, 16843,
16848, 16852, 16855, 16860, 16861,
16939, 17006, 17009, 17016, 17019
\l__sort_C_int .....
..... 768, 769, 16836, 17024,
17028, 17035, 17036, 17047, 17062,
17070, 17072, 17073, 17090, 17092
\__sort_clist:NNn ..... 16975
\__sort_compare:nn . 769, 16938, 17045
\__sort_compute_range: .....
..... 762, 763, 764, 16865, 16926
\__sort_copy_block: 768, 17025, 17033
\__sort_disable_toksdef: 16925, 17185
\__sort_disabled_toksdef:n ... 17185
\l__sort_end_int 762, 768, 768, 769,
16834, 17007, 17015, 17016, 17017,
17018, 17019, 17020, 17021, 17038
\__sort_error: .. 17179, 17192, 17210
\__sort_i:nnnnNn ..... 772
\l__sort_length_int .....
..... 762, 763, 16828, 16936, 17006
\__sort_level: 775, 16940, 17004, 17183
\__sort_loop:wNn ..... 771, 772
\__sort_main:NNnNn .. 766, 16922,
16949, 16956, 16963, 16970, 16985
\l__sort_max_int .....
762, 763, 16828, 16845, 16919, 16930
\c__sort_max_length_int ..... 16865
\__sort_merge_blocks: .....
..... 17008, 17013, 17182
\__sort_merge_blocks_aux: .....
768, 17029, 17043, 17076, 17086, 17181
\__sort_merge_blocks_end: .....
..... 770, 17084, 17088
\l__sort_min_int ... 762, 763, 765,
767, 16828, 16842, 16850, 16868,
16884, 16892, 16905, 16917, 16927,
16937, 16995, 17007, 17208, 17209
\__sort_quick_cleanup:w ..... 17098
\__sort_quick_end:nnTFNn .....
..... 773, 774, 17118, 17153
\__sort_quick_only_i:NnnnnNn . 17123
\__sort_quick_only_i_end:nnwnw .
..... 17132, 17153
\__sort_quick_only_ii:NnnnnNn . 17123
\__sort_quick_only_ii_end:nnwnw
..... 17138, 17153
\__sort_quick_prepare:Nnnn ... 17098
\__sort_quick_prepare_end:NNNnw .
..... 17098
\__sort_quick_single_end:nnwnw .
..... 17126, 17153
\__sort_quick_split:NnNn .....
..... 772, 773, 17118,
17123, 17158, 17165, 17171, 17173
\__sort_quick_split_end:nnwnw ..
..... 17144, 17150, 17153
\__sort_quick_split_i:NnnnnNn ...
..... 771, 17123
\__sort_quick_split_ii:NnnnnNn 17123
\__sort_redefine_compute_range: .
..... 16865
\__sort_return_mark:N .....
..... 17049, 17050, 17053
\__sort_return_none_error: .....
..... 769, 17051, 17053
\__sort_return_same: .....
..... 17054, 17063, 17068
\__sort_return_swapped: 17056, 17078
\__sort_return_two_error:w ... 17053
\__sort_shrink_range: ..... 763,
764, 16839, 16870, 16886, 16894, 16907
\__sort_shrink_range_loop: ... 16839
\__sort_toks:NN ..... 766, 16951,
16958, 16965, 16972, 16989, 16994
\__sort_toks:NNw ..... 16994
\__sort_too_long_error:NNw .....
..... 16931, 17203
\l__sort_top_int ..... 762, 765,
767, 768, 769, 16828, 16927, 16930,
16933, 16934, 16937, 16998, 17017,
17020, 17021, 17024, 17073, 17209
\l__sort_true_max_int ..... 762,
763, 16828, 16842, 16855, 16869,
16885, 16893, 16906, 16918, 17208
sp ..... 199
spac commands:
\spac_directions_normal_body_dir
..... 1320
\spac_directions_normal_page_dir
..... 1321
\space ..... 55

```

- \spacefactor 545
- \spaceskip 546
- \span 547
- \special 548
- \splitbotmark 549
- \splitbotmarks 662
- \splitdiscards 663
- \splitfirstmark 550
- \splitfirstmarks 664
- \splitmaxdepth 551
- \splittopskip 552
- sqrt 197
- \SS 24224
- \ss 24224
- str commands:
 - \c_ampersand_str 62, 4420
 - \c_atsign_str 62, 4420
 - \c_backslash_str 62, 4420, 18020, 18570
 - \c_circumflex_str 62, 4420
 - \c_colon_str
 - ... 62, 4420, 7421, 7526, 7532, 10632
 - \c_dollar_str 62, 4420
 - \c_hash_str 62,
 - 4420, 4486, 25733, 25892, 25899, 25939
 - \c_percent_str .. 62, 4420, 26041,
 - 26042, 26043, 26054, 26055, 26056
 - \str_case:nn
 - ... 55, 3958, 8873, 11852, 18718
 - \str_case:nn(TF) 411
 - \str_case:nnn 22456, 22457
 - \str_case:nnTF 55,
 - 543, 3958, 3963, 3968, 3981, 3982,
 - 10784, 19240, 22456, 22457, 23832
 - \str_case_x:nn 55, 3958
 - \str_case_x:nnn 22458
 - \str_case_x:nnTF
 - .. 55, 3958, 3995, 4000, 18450, 22458
 - \str_clear:N
 - ... 52, 52, 3780, 9027, 9127, 9139
 - \str_clear_new:N 52, 3780
 - \str_concat:NNN 52, 3780
 - \str_const:Nn 51,
 - 3807, 4420, 4421, 4422, 4423, 4424,
 - 4425, 4426, 4427, 4428, 4429, 4430,
 - 4431, 22331, 22335, 22357, 22365,
 - 22377, 22384, 22393, 22406, 22417
 - \str_count:N 57, 4288, 9468, 9532, 17712
 - \str_count:n 57, 63, 4288, 17706
 - \str_count_ignore_spaces:n
 - ... 57, 379, 4288, 17341
 - \str_count_spaces:N 57, 4268
 - \str_count_spaces:n 57, 379, 4268, 4294
 - \str_fold_case:n
 - ... 60, 61, 248, 4356, 12327
 - \str_gclear:N 52, 3780
 - \str_gclear_new:N 3780
 - \str_gconcat:NNN 52, 3780
 - \str_gput_left:Nn 52, 3807
 - \str_gput_right:Nn 52, 3807
 - \str_gremove_all:Nn 53, 3874
 - \str_gremove_once:Nn 53, 3868
 - \str_greplace_all:Nnn 53, 3828, 3877
 - \str_greplace_once:Nnn 53, 3828, 3871
 - \str_gset:Nn
 - ... 52, 3807, 8937, 9109, 9110, 9111
 - \str_gset_eq:NN
 - ... 52, 3780, 8942, 9098, 9099, 9100
 - \str_head:N 58, 380, 4326
 - \str_head:n 58,
 - 344, 360, 380, 3121, 3616, 3663, 4326
 - \str_head_ignore_spaces:n .. 58, 4326
 - \str_if_empty:NTF
 - ... 53, 3880, 9029, 9033,
 - 9056, 9069, 9121, 9210, 9818, 22895,
 - 22901, 22910, 22918, 23309, 23336
 - \str_if_empty_p:N 53, 3880
 - \str_if_eq:NN 370
 - \str_if_eq:nn 129, 135
 - \str_if_eq:NNTF .. 54, 3934, 3939, 3940
 - \str_if_eq:nnTF .. 54, 55, 55, 131,
 - 244, 369, 391, 3306, 3914, 3923,
 - 3924, 3925, 3926, 3986, 4738, 7844,
 - 8289, 8499, 10586, 10604, 11116,
 - 12224, 18429, 18520, 18698, 18729,
 - 18749, 18806, 18841, 18856, 18915,
 - 20115, 23600, 23619, 23637, 23647,
 - 23660, 24714, 24717, 24720, 24723
 - \str_if_eq_p:NN 54, 3934
 - \str_if_eq_p:nn 54, 3914
 - \str_if_eq_x:nn 488
 - \str_if_eq_x:nnTF ... 54, 62, 2193,
 - 3914, 4014, 7920, 8011, 8542, 10676,
 - 18072, 18094, 18103, 18472, 18486,
 - 19038, 20034, 20090, 20668, 20796
 - \str_if_eq_x_p:nn 54, 3914
 - \str_if_exist:NTF 53, 3880
 - \str_if_exist_p:N 53, 3880
 - \str_if_in:Nn\str_if_in:nnTF .. 3943
 - \str_if_in:NnTF .. 54, 3943, 3949, 3950
 - \str_if_in:nnTF 54
 - \str_item:Nn 58, 4131
 - \str_item:nn 58, 375, 379, 4131
 - \str_item_ignore_spaces:nn
 - ... 58, 375, 4131
 - \str_lower_case:n 60, 248, 4356
 - \str_map_break: 56, 4019
 - \str_map_break:n 56, 57, 4019

- \str_map_function:NN [55](#), [55](#), [56](#), [56](#), [4019](#)
- \str_map_function:nN [55](#), [55](#), [372](#), [4019](#), [4028](#)
- \str_map_inline:Nn .. [56](#), [56](#), [56](#), [4019](#)
- \str_map_inline:nn ... [56](#), [4039](#), [4054](#)
- \str_map_variable:NNn [56](#), [4019](#)
- \str_map_variable:nNn [56](#), [4062](#), [4073](#)
- \str_new:N [51](#), [52](#), [3780](#),
[4432](#), [4433](#), [4434](#), [4435](#), [8930](#), [8931](#),
[8932](#), [8976](#), [8977](#), [8978](#), [8979](#), [8980](#)
- \str_put_left:Nn [52](#), [3807](#), [9124](#)
- \str_put_right:Nn [52](#), [3807](#), [9038](#)
- \str_range:Nnn [59](#), [4190](#)
- \str_range:nnn [59](#), [63](#), [379](#), [4190](#), [17709](#)
- \str_range_ignore_spaces:nnn [59](#), [4190](#)
- \str_remove_all:Nn [53](#), [53](#), [3874](#)
- \str_remove_once:Nn [53](#), [3868](#)
- \str_replace_all:Nnn . [53](#), [3828](#), [3875](#)
- \str_replace_once:Nnn [53](#), [3828](#), [3869](#)
- \str_set:Nn
.. [52](#), [53](#), [3807](#), [4077](#), [8997](#), [9001](#),
[9010](#), [9121](#), [9136](#), [9143](#), [22844](#), [22855](#)
- \str_set_eq:NN .. [52](#), [3780](#), [9041](#), [9126](#)
- \str_show:N [61](#), [4436](#)
- \str_show:n [61](#), [4436](#)
- \str_tail:N [58](#), [4341](#)
- \str_tail:n [58](#), [784](#), [4341](#), [9143](#)
- \str_tail_ignore_spaces:n .. [58](#), [4341](#)
- \str_upper_case:n [60](#), [248](#), [4356](#)
- \str_use:N [57](#), [3780](#)
- \c_tilde_str [62](#), [4420](#)
- \g_tmpa_str [62](#), [4432](#)
- \l_tmpa_str [53](#), [62](#), [4432](#)
- \g_tmpb_str [62](#), [4432](#)
- \l_tmpb_str [62](#), [4432](#)
- \c_underscore_str [62](#), [4420](#)
- str internal commands:
- __str_analysis_map_inline:nn .. [779](#)
- __str_case:nnTF [3958](#)
- __str_case:nw [3958](#)
- __str_case_end:nw [3958](#)
- __str_case_x:nnTF [3958](#)
- __str_case_x:nw [3958](#)
- __str_change_case:nn [4356](#)
- __str_change_case_aux:nn [4356](#)
- __str_change_case_char:nN ... [4356](#)
- __str_change_case_char_aux:nN ..
..... [4398](#), [4403](#), [4417](#)
- __str_change_case_end:nw [4356](#)
- __str_change_case_end:wn [4375](#), [4392](#)
- __str_change_case_loop:nw ... [4356](#)
- __str_change_case_output:nw . [4356](#)
- __str_change_case_result:n .. [4356](#)
- __str_change_case_space:n ... [4356](#)
- __str_collect_delimit_by_q-
 stop:w [4220](#), [4243](#)
- __str_collect_end:nnnnnnnnnw ...
..... [377](#), [4243](#)
- __str_collect_end:wn [4243](#)
- __str_collect_loop:wn [4243](#)
- __str_collect_loop:wnNNNNNNN . [4243](#)
- __str_count:n [63](#), [379](#), [4148](#), [4207](#), [4288](#)
- __str_count_aux:n [4288](#)
- __str_count_loop:NNNNNNNNN .. [4288](#)
- __str_count_spaces_loop:w ... [4268](#)
- __str_escape_x:n [3884](#)
- __str_head:w [380](#), [4326](#)
- __str_if_eq_x:nn
 . [62](#), [3884](#), [3908](#), [3917](#), [3931](#), [3936](#),
[4489](#), [4513](#), [4524](#), [4532](#), [4544](#), [7424](#),
[10217](#), [12708](#), [12722](#), [12920](#), [15371](#)
- __str_if_eq_x_return:nn
..... [62](#), [472](#), [3906](#), [7482](#)
- __str_item:nn [375](#), [4131](#)
- __str_item:w [375](#), [4131](#)
- __str_lookup_fold:N [4356](#)
- __str_lookup_lower:N [4356](#)
- __str_lookup_upper:N [4356](#)
- __str_map_function:Nn [372](#), [4019](#)
- __str_map_function:w [372](#), [4019](#)
- __str_map_inline:NN [4019](#)
- __str_map_variable:NnN [4019](#)
- __str_range:nnn [63](#), [4190](#)
- __str_range:nnw [4190](#)
- __str_range:w [4190](#)
- __str_range_normalize:nn
..... [4215](#), [4216](#), [4224](#)
- __str_replace:NNNnn [3828](#)
- __str_replace_aux:NNNnnn [3828](#)
- __str_replace_next:w [3828](#)
- __str_skip_end:NNNNNNNN .. [376](#), [4172](#)
- __str_skip_end:w [4172](#)
- __str_skip_exp_end:w
.... [376](#), [377](#), [4159](#), [4168](#), [4172](#), [4222](#)
- __str_skip_loop:wNNNNNNNNN ... [4172](#)
- __str_tail_auxi:w [4341](#)
- __str_tail_auxii:w [380](#), [4341](#)
- __str_tmp:n
.. [3781](#), [3787](#), [3790](#), [3808](#), [3815](#), [3818](#)
- __str_to_other:n [62](#), [63](#),
[63](#), [63](#), [372](#), [374](#), [379](#), [4086](#), [4138](#), [4197](#)
- __str_to_other_end:w [373](#), [4086](#)
- __str_to_other_fast:n .. [63](#), [4048](#),
[4067](#), [4109](#), [9467](#), [9541](#), [18004](#), [19080](#)
- __str_to_other_fast_end:w ... [4109](#)
- __str_to_other_fast_loop:w .. [4109](#)
- __str_to_other_loop:w [373](#), [4086](#)

- \strcmp 40
- \string 553
- \suppressfontnotfounderror 808
- \suppressifcsnameerror 933
- \suppresslongerror 934
- \suppressmathparerror 935
- \suppressoutererror 936
- \synctex 790
- sys commands:
 - \c_sys_day_int 235, 22337
 - \c_sys_engine_str 235, 22344
 - \sys_gset_rand_seed:n ... 246, 23170
 - \c_sys_hour_int 235, 22337
 - \sys_if_engine_luatex:TF
 - 235, 253, 22344,
 - 22353, 22354, 22444, 22445, 22446,
 - 23174, 23209, 23211, 23230, 24477
 - \sys_if_engine_luatex_p:
 - 235, 22344, 22443
 - \sys_if_engine_pdftex:TF
 - 235, 22344,
 - 22361, 22362, 22448, 22449, 22450
 - \sys_if_engine_pdftex_p:
 - 235, 22344, 22447, 24037
 - \sys_if_engine_ptex:TF
 - 235, 22344, 22380, 22381
 - \sys_if_engine_ptex_p: ... 235, 22344
 - \sys_if_engine_uptex:TF
 - 235, 22344, 22373, 22374
 - \sys_if_engine_uptex_p:
 - 235, 22344, 24038
 - \sys_if_engine_xetex:TF
 - 4, 235, 22344,
 - 22389, 22390, 22462, 22463, 22464
 - \sys_if_engine_xetex_p:
 - 235, 22344, 22461
 - \sys_if_output_dvi:TF
 - 236, 22395, 22398, 22399, 22409, 22410
 - \sys_if_output_dvi_p: ... 236, 22395
 - \sys_if_output_pdf:TF
 - 236, 22395, 22402, 22403, 22413, 22414
 - \sys_if_output_pdf_p: ... 236, 22395
 - \sys_if_rand_exist:TF ... 246, 23158
 - \sys_if_rand_exist_p: ... 246, 23158
 - \sys_if_shell: 247, 948
 - \sys_if_shell:TF 246, 23185
 - \sys_if_shell_p: 246, 23185
 - \sys_if_shell_restricted: ... 23201
 - \sys_if_shell_restricted:TF ... 247
 - \sys_if_shell_restricted_p: ... 247
 - \sys_if_shell_unrestricted:TF ...
 - 246, 23193, 23201
 - \sys_if_shell_unrestricted_p: ...
 - 246, 23193, 23201
- \c_sys_jobname_str
 - 145, 235, 22327, 22434
- \c_sys_minute_int 235, 22337
- \c_sys_month_int 235, 22337
- \c_sys_output_str 236, 22395
- \sys_rand_seed: 246, 23167
- \c_sys_shell_escape_int
 - 246, 23172, 23187, 23195, 23203
- \sys_shell_now:n 247, 23211
- \sys_shell_shipout:n ... 247, 23230
- \c_sys_year_int 235, 22337
- sys internal commands:
 - \c__sys_shell_stream_int
 - 23209, 23226, 23245
- syst commands:
 - \c_syst_last_allocated_read
 - 4450, 4451
 - \c_syst_last_allocated_toks .. 16899
- T
 - \t 24233
 - \tabskip 554
 - \tagcode 791
 - \tan 196
 - \tand 196
 - \tate 1155
 - \tbaselineshift 1156
 - \temp . 163, 169, 174, 177, 178, 185, 190, 193
- TeX and L^AT_EX 2_ε commands:
 - \@ 4421
 - \@@@tracingfonts 287
 - \@@end 286, 1173, 1174
 - \@@hyph 1177
 - \@@input 1178
 - \@@italiccorr 1179
 - \@@shipout 1181, 1182
 - \@@underline 1180
 - \@addtofilelist 9080
 - \@currname 512, 8941, 8942
 - \@currnamestack 8963, 8964
 - \@filelist 146, 513,
 - 516, 518, 518, 9079, 9157, 9160, 9173
 - \@firstoftwo 293
 - \@ifpackageloaded 24659, 24704
 - \@secondoftwo 293
 - \@tempa 143, 145, 1189, 1203, 1206
 - \@tfor 286, 1189
 - \@unexpandable@protect 619
 - \afterassignment 778
 - \AtBeginDocument 286
 - \botmark 473
 - \box 219, 796
 - \char 127
 - \chardef 122, 122, 405

- \copy 219
- \count 127, 763, 764, 796
- \cr 444
- \CROP@shipout 1190
- \csname 16
- \csstring 308
- \current@color
256, 984, 24663, 24668, 24671, 24709
- \currentgrouplevel 319, 943
- \currentgrouptype 319, 943
- \def 127
- \detokenize 352
- \dimen 472
- \dimendef 472
- \dimexpr 169
- \directlua 253
- \dp 220, 619, 620
- \dup@shipout 1191
- \e@alloc@top 764, 16885
- \edef 1, 337
- \endcsname 16
- \endinput 138
- \endlinechar 40, 40, 148, 343, 473
- \endtemplate 104, 444
- \errhelp 494, 494
- \errmessage 494, 494, 495
- \errorcontextlines 154, 365, 494, 888
- \escapechar 44, 307, 319, 529, 796
- \everyeof 342, 344
- \everypar 239, 928
- \expandafter 32, 33
- \expanded 279
- \fi 127
- \firstmark 331, 473
- \font 126
- \fontdimen 88, 216, 426, 427, 427
- \frozen@everydisplay 1175
- \frozen@everymath 1176
- \futurelet
... 444, 476, 477, 781, 783, 784, 784
- \global 268
- \GPTorg@shipout 1192
- \halign 104, 444, 465, 928
- \hskip 165
- \ht 220, 619, 620
- \hyphen 473
- \hyphenchar 426
- \ifcase 86
- \ifdim 168
- \ifeof 153
- \iffalse 98
- \ifhbox 227
- \ifnum 86
- \ifodd 86, 977
- \iftrue 98
- \ifvbox 227
- \ifvoid 228
- \ifx 21, 264
- \indent 928
- \input@path 145, 9021, 9023
- \italiccorr 473
- \jobname 235
- \l@expl@check@declarations@bool 1563
- \l@expl@enable@debug@bool
1455, 2888, 6081, 8780
- \l@expl@log@functions@bool ... 1640
- \lastnamedcs 310
- \lccode 264, 383, 425, 783, 787
- \leavevmode 239
- \let 268
- \latcharcode 463
- \LL@shipout 1193
- \loctoks 763, 764
- \long 128
- \lower 929
- \lowercase 866, 867, 867
- \luaescapestring 254
- \m@ne 425, 5979
- \makeatletter 6
- \mathchar 127
- \mathchardef 122, 405
- \meaning 15,
119, 127, 128, 471, 472, 477, 782, 977
- \mem@oldshipout 1194
- \newif 98
- \newlinechar
40, 40, 154, 311, 343, 365, 494, 527
- \newread 520
- \newtoks 202, 775, 795
- \newwrite 525
- \noexpand 32, 127
- \nullfont 473, 474
- \number 87, 665
- \numexpr 87
- \opem@shipout 1195
- \or 86
- \outer ... 128, 264, 520, 525, 927, 977
- \par 924
- \parindent 239
- \pdfmapfile 288
- \pdfmapline 288
- \pdfrandomseed 198
- \pdfsetrandomseed 198
- \pdfstrcmp . xiii, 261, 262, 264, 278, 981
- \pdftex_mdffivesum:D 938
- \pdfuniformdeviate 198, 755
- \pgfpages@originalshipout 1196
- \pgfsys@... 256

- `\pr@shipout` 1197
- `\primitive` 286
- `\protect` 530, 618, 618, 619, 959
- `\protected` 128
- `\ProvidesClass` 6
- `\ProvidesFile` 6
- `\ProvidesPackage` 6
- `\quitvmode` 928
- `\randomseed` 198
- `\read` 148
- `\readline` 148
- `\relax` 127, 264, 304,
309, 319, 428, 428, 581, 582, 604, 633
- `\RequirePackage` 6, 264, 512
- `\reserveinserts` 264
- `\robustify` 248
- `\romannumeral` 87
- `\scantokens` 342, 343, 344
- `\setrandomseed` 198
- `\sfcode` 265
- `\shipout` 286
- `\show` 16, 49, 319
- `\showbox` 888
- `\showthe` 319, 424, 547, 551, 554
- `\showtokens` 49, 365, 499
- `\skip` 788, 789
- `\space` 473
- `\splitbotmark` 473
- `\splitfirstmark` 473
- `\strcmp` 261, 278
- `\string` 119, 783, 784, 785
- `\synctex` 278
- `\tenrm` 126
- `\tex_lowercase:D` 466
- `\the` 77, 126, 160, 164, 167, 323
- `\toks` xx,
87, 202, 203, 762, 763, 763, 763,
764, 765, 766, 767, 768, 768, 769,
770, 770, 775, 777, 777, 777, 778,
778, 782, 784, 785, 787, 789, 791,
795, 796, 796, 796, 797, 797, 798,
802, 839, 846, 846, 850, 851, 851,
851, 852, 855, 857, 860, 861, 866, 884
- `\toksdef` 775
- `\topmark` 127, 473
- `\tracingfonts` 286
- `\tracingonline` 888
- `\typeout` 530
- `\uccode` 383
- `\Ucharcat` 464, 465, 466
- `\Ucharcat@table` 52, 55
- `\unexpanded` 33,
45, 45, 46, 49, 66, 70, 71, 107, 110,
111, 112, 131, 240, 244, 245, 247,
251, 251, 252, 337, 359, 360, 410, 465
- `\unhbox` 223
- `\unhcopy` 223
- `\uniformdeviate` 198, 755
- `\unless` 21
- `\unvbox` 225
- `\unvcopy` 225
- `\uppercase` 866
- `\usepackage` 512
- `\valign` 444
- `\verso@orig@shipout` 1199
- `\vskip` 166
- `\vsplit` 224
- `\vtop` 905
- `\wd` 220, 619, 620
- `\write` 151, 527
- tex commands:
 - `\tex_above:D` 287
 - `\tex_abovedisplayshortskip:D` .. 288
 - `\tex_abovedisplayskip:D` 289
 - `\tex_abovewithdelims:D` 290
 - `\tex_accent:D` 291
 - `\tex_adjdemerits:D` 292
 - `\tex_advance:D` 293, 5289,
5292, 5295, 5298, 5305, 5308, 5311,
5314, 9899, 9902, 9907, 9910, 10200,
10203, 10208, 10211, 10340, 10343,
10348, 10351, 17009, 17016, 17019,
17466, 17468, 17500, 17502, 18657
 - `\tex_afterassignment:D`
..... 294, 7587, 17407, 17450
 - `\tex_aftergroup:D` 295, 1364
 - `\tex_atop:D` 296
 - `\tex_atopwithdelims:D` 297
 - `\tex_badness:D` 298
 - `\tex_baselineskip:D` 299
 - `\tex_batchmode:D` 300
 - `\tex_begingroup:D` 301, 1184, 1359
 - `\tex_belowdisplayshortskip:D` .. 302
 - `\tex_belowdisplayskip:D` 303
 - `\tex_binoppenalty:D` 304
 - `\tex_botmark:D` 305
 - `\tex_box:D` ... 306, 20873, 20876, 20898
 - `\tex_boxmaxdepth:D` 307
 - `\tex_brokenpenalty:D` 308
 - `\tex_catcode:D`
309, 2626, 3072, 4460, 4461, 7052, 7054
 - `\tex_char:D` 310
 - `\tex_chardef:D` 291, 311, 1353, 1381,
1383, 1908, 1909, 4442, 4445, 5249,
6267, 6270, 7511, 9243, 9398, 23039
 - `\tex_cleaders:D` 312
 - `\tex_closein:D` 313, 4465, 9251

- `\tex_closeout:D` 314, 9407
- `\tex_clubpenalty:D` 315
- `\tex_copy:D` .. 316, 20865, 20868, 20899
- `\tex_count:D` 317, 4452, 9192, 9194,
9362, 9364, 16868, 16884, 16892, 16893
- `\tex_countdef:D` 318
- `\tex_cr:D` 319
- `\tex_crcr:D` 320
- `\tex_csname:D` 321, 1347
- `\tex_day:D` 322, 22341
- `\tex_deadcycles:D` 323
- `\tex_def:D` 324, 537,
794, 795, 796, 1365, 1367, 1369,
1370, 1387, 1389, 1390, 1391, 1393,
1394, 1395, 1397, 1398, 1399, 9796
- `\tex_defaultthyphenchar:D` 325
- `\tex_defaultskewchar:D` 326
- `\tex_delcode:D` 327
- `\tex_delimiter:D` 328
- `\tex_delimiterfactor:D` 329
- `\tex_delimitershortfall:D` 330
- `\tex_dimen:D` 331
- `\tex_dimendef:D` 332
- `\tex_discretionary:D` 333
- `\tex_displayindent:D` 334
- `\tex_displaylimits:D` 335
- `\tex_displaystyle:D` 336
- `\tex_displaywidowpenalty:D` 337
- `\tex_displaywidth:D` 338
- `\tex_divide:D` 339, 16861, 18658
- `\tex_doublehyphendemerits:D` ... 340
- `\tex_dp:D` 341, 20884
- `\tex_dump:D` 342
- `\tex_edef:D`
.... 343, 1185, 1186, 1202, 1388,
1392, 1396, 1400, 9597, 9654, 22424
- `\tex_else:D` 344, 1188, 1214, 1334, 1384
- `\tex_emergencystretch:D` 345
- `\tex_end:D` . 346, 1174, 1303, 2023, 8340
- `\tex_endcsname:D` 347, 1348
- `\tex_endgroup:D` 348, 1171, 1210, 1360
- `\tex_endinput:D` 349, 8351, 22921
- `\tex_endlinechar:D` . 251, 252, 266,
350, 3045, 3046, 3047, 3103, 9294, 9296
- `\tex_eqno:D` 351
- `\tex_errhelp:D` 352, 8201
- `\tex_errmessage:D` 353, 2015, 8232
- `\tex_errorcontextlines:D`
.. 354, 3759, 8227, 8259, 8424, 20970
- `\tex_errorstopmode:D` 355
- `\tex_escapechar:D` 356, 2322, 9480,
9515, 9521, 17372, 17434, 17435, 17732
- `\tex_everycr:D` 357
- `\tex_everydisplay:D` 358, 1175
- `\tex_everyhbox:D` 359
- `\tex_everyjob:D` 360, 1304,
8934, 8936, 8969, 8971, 22328, 22330
- `\tex_everymath:D` 361, 1176
- `\tex_everypar:D` 362
- `\tex_everyvbox:D` 363
- `\tex_exhyphenpenalty:D` 364
- `\tex_expandafter:D`
365, 799, 1189, 1203, 1205, 1206, 1349
- `\tex_fam:D` 366
- `\tex_fi:D` 367,
800, 1183, 1207, 1209, 1218, 1219,
1220, 1273, 1275, 1276, 1280, 1294,
1299, 1314, 1322, 1327, 1335, 1386
- `\tex_finalhyphendemerits:D` 368
- `\tex_firstmark:D` 369
- `\tex_floatingpenalty:D` 370
- `\tex_font:D` 371, 5998
- `\tex_fontdimen:D`
..... 372, 6001, 6003, 6007, 6033
- `\tex_fontname:D` 373
- `\tex_futurelet:D`
..... 374, 7582, 7584, 17380, 17438
- `\tex_gdef:D` 375, 1401, 1404, 1408, 1412
- `\tex_global:D` .. 272, 277, 279, 376,
540, 801, 803, 1205, 2094, 2101,
5226, 5232, 5236, 5258, 5272, 5295,
5298, 5311, 5314, 5324, 5998, 6270,
7317, 7319, 7329, 7584, 9243, 9398,
9851, 9858, 9884, 9894, 9902, 9910,
10157, 10163, 10189, 10195, 10203,
10211, 10287, 10295, 10327, 10335,
10343, 10351, 20868, 20876, 20936,
20987, 20999, 21014, 21036, 21080,
21094, 21108, 21123, 21146, 23039
- `\tex_globaldefs:D` 377
- `\tex_halign:D` 378
- `\tex_hangafter:D` 379
- `\tex_hangindent:D` 380
- `\tex_hbadness:D` 381
- `\tex_hbox:D` 382, 20981,
20984, 20987, 20993, 20999, 21007,
21014, 21029, 21036, 21044, 21048
- `\tex_hfil:D` 383
- `\tex_hfill:D` 384
- `\tex_hfilneg:D` 385
- `\tex_hfuzz:D` 386
- `\tex_hoffset:D` 387, 1316
- `\tex_holdinginserts:D` 388
- `\tex_hrule:D` 389
- `\tex_hsize:D` 390, 21574,
21576, 21577, 21620, 21622, 21623
- `\tex_hskip:D` 391, 10249

- `\tex_hss:D`
..... 392, 21050, 21052, 21445, 21454
- `\tex_ht:D` 393, 20883
- `\tex_hyphen:D` 286, 1177
- `\tex_hyphenation:D` 394
- `\tex_hyphenchar:D`
..... 395, 5999, 6000, 6001, 6005
- `\tex_hyphenpenalty:D` 396
- `\tex_if:D` 114, 397, 1337, 1338
- `\tex_ifcase:D` 398, 5115
- `\tex_ifcat:D` 399, 1339
- `\tex_ifdim:D` 400, 9836
- `\tex_ifeof:D` 401, 4470, 9271
- `\tex_iffalse:D` 402, 1332
- `\tex_ifhbox:D` 403, 20910
- `\tex_ifhmode:D` 404, 1342
- `\tex_ifinner:D` 405, 1344
- `\tex_ifmmode:D` 406, 1341
- `\tex_ifnum:D` 407, 1274, 1362
- `\tex_ifodd:D` 408, 1455, 1563,
1640, 2888, 5114, 6081, 6240, 6241
- `\tex_iftrue:D` 409, 1331
- `\tex_ifvbox:D` 410, 20911
- `\tex_ifvmode:D` 411, 1343
- `\tex_ifvoid:D` 412, 20912
- `\tex_ifx:D` 413, 1187, 1204, 1340
- `\tex_ignorespaces:D` 414
- `\tex_immediate:D` 415,
2032, 2034, 9400, 9407, 9448, 25251
- `\tex_indent:D` 416, 22489
- `\tex_input:D`
..... 417, 1178, 1305, 9084, 23318, 23343
- `\tex_inputlineno:D` ... 418, 2030, 8175
- `\tex_insert:D` 419
- `\tex_insertpenalties:D` 420
- `\tex_interlinepenalty:D` 421
- `\tex_italiccorrection:D`
..... 285, 1179, 1317
- `\tex_jobname:D`
..... 422, 8937, 8954, 8955, 22331, 22335
- `\tex_kern:D` 423,
21201, 21443, 21452, 21888, 21893,
21959, 21960, 22247, 22248, 22502,
22504, 22548, 22550, 22630, 25676
- `\tex_language:D` 424, 1306
- `\tex_lastbox:D` 425, 20933, 20936
- `\tex_lastkern:D` 426
- `\tex_lastpenalty:D` 427
- `\tex_lastskip:D` 428
- `\tex_lccode:D`
..... 429, 2929, 2930, 2931, 4092,
4093, 4115, 4116, 4412, 4525, 7128,
7130, 17355, 17363, 17432, 17434,
17437, 17467, 20140, 20189, 23575
- `\tex_leaders:D` 430
- `\tex_left:D` 431, 1324
- `\tex_lefthyphenmin:D` 432
- `\tex_leftskip:D` 433
- `\tex_leqno:D` 434
- `\tex_let:D` 273,
277, 279, 299, 425, 435, 801, 803,
1174, 1175, 1176, 1177, 1178, 1179,
1180, 1182, 1205, 1211, 1213, 1217,
1222, 1223, 1224, 1225, 1226, 1227,
1228, 1229, 1230, 1231, 1232, 1233,
1234, 1235, 1236, 1237, 1238, 1239,
1240, 1241, 1242, 1243, 1244, 1245,
1246, 1247, 1248, 1249, 1250, 1251,
1252, 1253, 1254, 1255, 1256, 1257,
1258, 1259, 1260, 1261, 1262, 1263,
1264, 1265, 1266, 1267, 1268, 1269,
1270, 1271, 1272, 1278, 1279, 1284,
1285, 1286, 1287, 1288, 1289, 1290,
1291, 1292, 1293, 1296, 1297, 1298,
1303, 1304, 1305, 1306, 1307, 1308,
1309, 1310, 1311, 1312, 1313, 1316,
1317, 1318, 1319, 1320, 1321, 1324,
1325, 1326, 1331, 1332, 1333, 1334,
1335, 1336, 1337, 1338, 1339, 1340,
1341, 1342, 1343, 1344, 1345, 1346,
1347, 1348, 1349, 1350, 1351, 1352,
1354, 1355, 1356, 1357, 1358, 1359,
1360, 1362, 1363, 1364, 1380, 1387,
1388, 1401, 1402, 1672, 1677, 2090,
5987, 7317, 7319, 7329, 17356, 17364
- `\tex_limits:D` 436
- `\tex_linepenalty:D` 437
- `\tex_lineskip:D` 438
- `\tex_lineskiplimit:D` 439
- `\tex_long:D` 440, 794, 795,
796, 1365, 1367, 1370, 1389, 1390,
1391, 1392, 1393, 1395, 1397, 1398,
1399, 1400, 1404, 1406, 1412, 1414
- `\tex_looseness:D` 441
- `\tex_lower:D` 442, 20909
- `\tex_lowercase:D` 443,
977, 2932, 3079, 3096, 3773, 3774,
4094, 4117, 7159, 7282, 8213, 17356,
17364, 17433, 20141, 20190, 24426
- `\tex_mag:D` 444
- `\tex_mark:D` 445
- `\tex_mathaccent:D` 446
- `\tex_mathbin:D` 447
- `\tex_mathchar:D` 448
- `\tex_mathchardef:D`
..... 291, 449, 1385, 5252, 5253
- `\tex_mathchoice:D` 450
- `\tex_mathclose:D` 451

<code>\tex_mathcode:D</code>	452, 7122, 7124	<code>\tex_par:D</code>	503
<code>\tex_mathinner:D</code>	453	<code>\tex_parfillskip:D</code>	504
<code>\tex_mathop:D</code>	454, 1307	<code>\tex_parindent:D</code>	505
<code>\tex_mathopen:D</code>	455	<code>\tex_parshape:D</code>	506
<code>\tex_mathord:D</code>	456	<code>\tex_parskip:D</code>	507
<code>\tex_mathpunct:D</code>	457	<code>\tex_patterns:D</code>	508
<code>\tex_mathrel:D</code>	458	<code>\tex_pausing:D</code>	509
<code>\tex_mathsurround:D</code>	459	<code>\tex_penalty:D</code>	510
<code>\tex_maxdeadcycles:D</code>	460	<code>\tex_postdisplaypenalty:D</code>	511
<code>\tex_maxdepth:D</code>	461	<code>\tex_predisplaypenalty:D</code>	512
<code>\tex_meaning:D</code>		<code>\tex_predisplaysize:D</code>	513
.	462, 1186, 1203, 1354, 1355	<code>\tex_pretolerance:D</code>	514
<code>\tex_medmuskip:D</code>	463	<code>\tex_prevdepth:D</code>	515
<code>\tex_message:D</code>	464	<code>\tex_prevgraf:D</code>	516
<code>\tex_middle:D</code>	1325	<code>\tex_radical:D</code>	517
<code>\tex_mkern:D</code>	465	<code>\tex_raise:D</code>	518, 20907
<code>\tex_month:D</code>	466, 1308, 22342	<code>\tex_read:D</code>	519, 4476, 9289
<code>\tex_moveleft:D</code>	467, 20903	<code>\tex_relax:D</code>	23, 298, 520,
<code>\tex_moveright:D</code>	468, 20905	583, 1358, 1608, 1621, 2014, 5113, 9838	
<code>\tex_mskip:D</code>	469	<code>\tex_relpemalty:D</code>	521
<code>\tex_multiply:D</code>	470	<code>\tex_right:D</code>	522, 1326
<code>\tex_muskip:D</code>	471	<code>\tex_righthyphenmin:D</code>	523
<code>\tex_muskipdef:D</code>	472	<code>\tex_rightskip:D</code>	524
<code>\tex_newlinechar:D</code> 473, 2014, 3047,		<code>\tex_romannumeral:D</code> 298, 307, 307,	
3075, 3078, 3757, 8225, 8422, 9447		329, 330, 525, 1352, 1363, 1619, 1913	
<code>\tex_noalign:D</code>	474	<code>\tex_scriptfont:D</code>	526
<code>\tex_noboundary:D</code>	475	<code>\tex_scriptscriptfont:D</code>	527
<code>\tex_noexpand:D</code>	476, 1350	<code>\tex_scriptscriptstyle:D</code>	528
<code>\tex_noindent:D</code>	477	<code>\tex_scriptspace:D</code>	529
<code>\tex_nolimits:D</code>	478	<code>\tex_scriptstyle:D</code>	530
<code>\tex_nonscript:D</code>	479	<code>\tex_scrollmode:D</code>	531
<code>\tex_nonstopmode:D</code>	480	<code>\tex_setbox:D</code>	532,
<code>\tex_nulldelimiterspace:D</code>	481	20865, 20868, 20873, 20876, 20933,	
<code>\tex_nullfont:D</code>	482, 7540	20936, 20984, 20987, 20993, 20999,	
<code>\tex_number:D</code>	483, 5111	21007, 21014, 21029, 21036, 21074,	
<code>\tex_omit:D</code>	484	21080, 21088, 21094, 21102, 21108,	
<code>\tex_openin:D</code>	485, 4462, 9245	21116, 21123, 21139, 21146, 21158	
<code>\tex_openout:D</code>	486, 9400	<code>\tex_setlanguage:D</code>	533
<code>\tex_or:D</code>	487, 1333	<code>\tex_sfcode:D</code>	534, 7140, 7142
<code>\tex_outer:D</code>	488, 1309, 22424	<code>\tex_shipout:D</code>	535, 1182, 1206
<code>\tex_output:D</code>	489	<code>\tex_show:D</code>	536
<code>\tex_outputpenalty:D</code>	490	<code>\tex_showbox:D</code>	537, 20971
<code>\tex_over:D</code>	491, 1310	<code>\tex_showboxbreadth:D</code>	538, 20967
<code>\tex_overfullrule:D</code>	492	<code>\tex_showboxdepth:D</code>	539, 20968
<code>\tex_oline:D</code>	493	<code>\tex_showlists:D</code>	540
<code>\tex_overwithdelims:D</code>	494	<code>\tex_showthe:D</code>	541
<code>\tex_pagedepth:D</code>	495	<code>\tex_skewchar:D</code>	542
<code>\tex_pagefilllstretch:D</code>	496	<code>\tex_skip:D</code>	543, 17470,
<code>\tex_pagefillstretch:D</code>	497	17498, 17517, 17571, 17587, 17593	
<code>\tex_pagefilstretch:D</code>	498	<code>\tex_skipdef:D</code>	544
<code>\tex_pagegoal:D</code>	499	<code>\tex_space:D</code>	284
<code>\tex_pageshrink:D</code>	500	<code>\tex_spacefactor:D</code>	545
<code>\tex_pagestretch:D</code>	501	<code>\tex_spaceskip:D</code>	546
<code>\tex_pagetotal:D</code>	502	<code>\tex_span:D</code>	547

- \tex_special:D 548, 24681, 24697, 24775, 24785,
24787, 24842, 24845, 24849, 24850,
24851, 24852, 24856, 24857, 24858,
25109, 25111, 25112, 25113, 25118,
25290, 25292, 25294, 25313, 25326,
25354, 25382, 25392, 25692, 25787
- \tex_splitbotmark:D 549
- \tex_splitfirstmark:D 550
- \tex_splitmaxdepth:D 551
- \tex_splittopskip:D 552
- \tex_string:D .. 553, 1185, 1189, 1357
- \tex_tabskip:D 554
- \tex_textfont:D 555
- \tex_textstyle:D 556
- \tex_the:D .. 23, 252, 323, 557, 614,
619, 620, 766, 1608, 2030, 2308,
2387, 2391, 5327, 5329, 6005, 7054,
7124, 7130, 7136, 7142, 8936, 8971,
10097, 10099, 10246, 10248, 10363,
12256, 12290, 12722, 16999, 17046,
17047, 17061, 17062, 17260, 17586,
17689, 17733, 17752, 17758, 17761,
17765, 20954, 22330, 23167, 25274
- \tex_thickmuskip:D 558
- \tex_thinmuskip:D 559
- \tex_time:D 560, 22338, 22340
- \tex_toks:D 561, 766, 16933,
16999, 17035, 17046, 17047, 17061,
17062, 17070, 17080, 17090, 17260,
17290, 17299, 17415, 17433, 17586,
17733, 17735, 17736, 17743, 17751,
17752, 17757, 17758, 17761, 17765
- \tex_toksdef:D 562, 17193
- \tex_tolerance:D 563
- \tex_topmark:D 564
- \tex_topskip:D 565
- \tex_tracingcommands:D 566
- \tex_tracinglostchars:D 567
- \tex_tracingmacros:D 568
- \tex_tracingonline:D 569, 20969
- \tex_tracingoutput:D 570
- \tex_tracingpages:D 571
- \tex_tracingparagraphs:D 572
- \tex_tracingrestores:D 573
- \tex_tracingstats:D 574
- \tex_uccode:D
..... 575, 4413, 7134, 7136, 23576
- \tex_uchyph:D 576
- \tex_undefined:D
272, 279, 473, 474, 803, 1211, 1278,
1279, 1296, 1297, 1298, 2107, 2115,
6060, 10732, 10746, 10779, 10800,
16871, 17356, 17364, 17442, 17541
- \tex_underline:D 577, 1180
- \tex_unhbox:D 578, 21054
- \tex_unhcopy:D 579, 21053
- \tex_unkern:D 580
- \tex_unpenalty:D 581
- \tex_unskip:D 582
- \tex_unvbox:D 583, 21153
- \tex_unvcopy:D 584, 21152
- \tex_uppercase:D 585, 3775, 3776
- \tex_vadjust:D 586
- \tex_valign:D 587
- \tex_vbadness:D 588
- \tex_vbox:D 589, 21058,
21063, 21068, 21074, 21080, 21102,
21108, 21116, 21123, 21139, 21146
- \tex_vcenter:D 590, 1311
- \tex_vfil:D 591
- \tex_vfill:D 592
- \tex_vfilneg:D 593
- \tex_vfuzz:D 594
- \tex_voffset:D 595, 1318
- \tex_vrule:D 596, 22099, 22154
- \tex_vsize:D 597
- \tex_vskip:D 598, 10254
- \tex_vsplit:D 599, 21158
- \tex_vss:D 600
- \tex_vtop:D .. 601, 21060, 21088, 21094
- \tex_wd:D 602, 20885
- \tex_widowpenalty:D 603
- \tex_write:D
... 604, 2032, 2034, 9428, 9431, 9448
- \tex_xdef:D 605, 1402, 1406, 1410, 1414
- \tex_xleaders:D 606
- \tex_xspaceskip:D 607
- \tex_year:D 608, 22343
- \texdir 953
- \textfont 555
- \textstyle 556
- \texttt 13486
- \TeXeTstate 665
- \tfont 1157
- \TH 24225
- \th 24225
- \the 67, 212, 213, 214,
215, 216, 217, 218, 219, 220, 221, 557
- \thickmuskip 558
- \thinmuskip 559
- thousand commands:
 \c_one_thousand 85, 5961
 \c_ten_thousand 85, 5961
- \time 560
- \tiny 22092

tl commands:

- \c_empty_tl [49](#), [417](#), [2859](#), [2877](#), [2879](#), [2927](#), [3223](#), [4477](#), [5671](#), [5677](#), [6503](#), [10467](#)
- \l_my_tl [205](#), [211](#)
- \c_novalue_tl [41](#), [50](#), [2928](#), [3309](#), [3311](#), [3315](#)
- \c_space_tl [50](#), [2937](#), [3538](#), [4384](#), [6918](#), [6927](#), [8179](#), [9084](#), [16594](#), [23018](#), [23020](#), [23420](#), [23480](#), [24668](#), [24695](#), [25174](#), [25179](#), [25182](#), [25397](#), [25400](#), [25402](#), [25403](#), [25404](#), [25405](#), [25868](#)
- \tl_act [357](#)
- \tl_case:Nn [42](#), [3332](#)
- \tl_case:nn [371](#)
- \tl_case:Nnn [22459](#), [22460](#)
- \tl_case:NnTF [42](#), [3332](#), [3337](#), [3342](#), [3361](#), [3362](#), [22459](#), [22460](#)
- \l_tl_case_change_accents_tl ... [249](#), [23628](#), [24231](#)
- \l_tl_case_change_exclude_tl ... [249](#), [249](#), [23650](#), [24278](#)
- \l_tl_case_change_math_tl [248](#), [23430](#), [24273](#)
- \tl_clear:N [37](#), [38](#), [2876](#), [2883](#), [6511](#), [6512](#), [9563](#), [9564](#), [9567](#), [9576](#), [9685](#), [9688](#), [9739](#), [10582](#), [11073](#), [11145](#), [17279](#), [19949](#), [22879](#), [25206](#), [25214](#), [25220](#), [25340](#), [25346](#), [25426](#), [25432](#)
- \tl_clear_new:N . [38](#), [2882](#), [6515](#), [6516](#)
- \tl_concat:NNN [38](#), [2907](#), [3803](#)
- \tl_const:Nn [37](#), [943](#), [2862](#), [2927](#), [2935](#), [2937](#), [3026](#), [4497](#), [4515](#), [4527](#), [4562](#), [4563](#), [4564](#), [4583](#), [6509](#), [7284](#), [7313](#), [7335](#), [7777](#), [7815](#), [8101](#), [8102](#), [8143](#), [8148](#), [8150](#), [8152](#), [8154](#), [8156](#), [8161](#), [8162](#), [8169](#), [9481](#), [9487](#), [10519](#), [10520](#), [10521](#), [10522](#), [10523](#), [10524](#), [10525](#), [11361](#), [11362](#), [11363](#), [11364](#), [11365](#), [11373](#), [14442](#), [14885](#), [14886](#), [14887](#), [14888](#), [14889](#), [14890](#), [14891](#), [14892](#), [14893](#), [16776](#), [17719](#), [17776](#), [20219](#), [23139](#), [23983](#), [23984](#), [23985](#), [23994](#), [23995](#), [23998](#), [23999](#), [24000](#), [24001](#), [24002](#), [24008](#), [24016](#), [24053](#), [24066](#), [24187](#), [24210](#), [24211](#), [24228](#), [24229](#), [24426](#)
- \tl_count:N [27](#), [42](#), [45](#), [45](#), [3426](#)
- \tl_count:n [27](#), [42](#), [45](#), [45](#), [315](#), [379](#), [404](#), [593](#), [1770](#), [1774](#), [2154](#), [2200](#), [3426](#), [3731](#), [13261](#), [13282](#), [19016](#), [24295](#), [24313](#)
- \tl_count_tokens:n [247](#), [23284](#)
- \tl_gclear:N [37](#), [2876](#), [2885](#), [6513](#), [6514](#), [25906](#), [25942](#)
- \tl_gclear_new:N . [38](#), [2882](#), [6517](#), [6518](#)
- \tl_gconcat:NNN [38](#), [2907](#), [3804](#)
- \tl_gput_left:Nn [38](#), [2962](#)
- \tl_gput_right:Nn [38](#), [1670](#), [1675](#), [2994](#), [4707](#), [5984](#), [5986](#), [6231](#), [9790](#), [9795](#), [11837](#), [11842](#), [22467](#), [22472](#)
- \tl_gremove_all:Nn [39](#), [3205](#)
- \tl_gremove_once:Nn [39](#), [3199](#)
- \tl_greplace_all:Nnn . [39](#), [3130](#), [3208](#)
- \tl_greplace_once:Nnn [39](#), [3130](#), [3202](#)
- \tl_greverse:N [45](#), [3568](#)
- .tl_gset:N [174](#), [10941](#)
- \tl_gset:Nn [38](#), [65](#), [203](#), [345](#), [766](#), [766](#), [2922](#), [2938](#), [3030](#), [3133](#), [3137](#), [3461](#), [3571](#), [3831](#), [3835](#), [4622](#), [4627](#), [4639](#), [4676](#), [4693](#), [4733](#), [4759](#), [4843](#), [4872](#), [4909](#), [4913](#), [6530](#), [6558](#), [6604](#), [6647](#), [6685](#), [6737](#), [6768](#), [7812](#), [7875](#), [7904](#), [7940](#), [7952](#), [7975](#), [9787](#), [16774](#), [16956](#), [16970](#), [16978](#), [17269](#), [17271](#), [17508](#), [18004](#), [19079](#), [23114](#), [23124](#), [23303](#), [23330](#), [25865](#)
- \tl_gset_eq:NN [38](#), [2879](#), [2888](#), [3800](#), [4606](#), [4607](#), [4608](#), [4609](#), [6262](#), [6523](#), [6524](#), [6525](#), [6526](#), [7800](#), [7801](#), [7802](#), [7803](#), [16781](#), [20214](#)
- \tl_gset_from_file:Nnn ... [250](#), [23300](#)
- \tl_gset_from_file_x:Nnn . [251](#), [23327](#)
- \tl_gset_rescan:Nnn [40](#), [3027](#)
- .tl_gset_x:N [174](#), [10941](#)
- \tl_gsort:Nn [46](#), [3502](#), [16961](#)
- \tl_gtrim_spaces:N [46](#), [3455](#)
- \tl_head:N [47](#), [3574](#)
- \tl_head:n [47](#), [47](#), [359](#), [360](#), [974](#), [3574](#), [24310](#)
- \tl_head:w [47](#), [360](#), [361](#), [3574](#), [3614](#), [3633](#), [3655](#)
- \tl_if_blank:nTF ... [40](#), [47](#), [47](#), [47](#), [3211](#), [3214](#), [3215](#), [3218](#), [3219](#), [3601](#), [3783](#), [3810](#), [4501](#), [4511](#), [6926](#), [7005](#), [8949](#), [10580](#), [11069](#), [11084](#), [11223](#), [17102](#), [23837](#), [23857](#), [23907](#), [24294](#)
- \tl_if_blank_p:n [40](#), [3211](#)
- \tl_if_empty:N [3882](#), [3883](#), [6783](#), [6785](#)
- \tl_if_empty:Ntf [41](#), [1502](#), [3221](#), [3230](#), [3231](#), [9580](#), [9669](#), [9744](#), [10566](#), [10590](#), [11089](#), [19996](#), [25209](#), [25258](#), [25266](#), [25367](#), [25371](#), [25398](#), [25413](#), [25447](#), [25868](#)
- \tl_if_empty:nTF [41](#), [349](#), [351](#), [352](#), [453](#), [1617](#), [1799](#), [1881](#), [3035](#), [3144](#), [3233](#), [3244](#), [3245](#), [3246](#)

- 3294, 3694, 3715, 3842, 4551, 4642,
 6154, 6161, 6178, 6546, 6590, 6796,
 6813, 6851, 7528, 7682, 7842, 8184,
 8419, 8509, 8524, 8644, 8648, 8689,
 8851, 8852, 8859, 8866, 8872, 8879,
 9134, 9137, 9574, 10634, 10728,
 11331, 12006, 16578, 16672, 17723,
 17724, 20791, 23255, 24459, 25962
 \tl_if_empty_p:N [41](#), [3221](#), 25254, 25410
 \tl_if_empty_p:n [41](#), [3233](#), [3246](#)
 \tl_if_eq:NN [370](#)
 \tl_if_eq:nn(TF) [107](#), [107](#)
 \tl_if_eq:NNTF [41](#),
 [42](#), [91](#), [391](#), [3257](#), [3267](#), [3268](#), [3356](#),
 [4745](#), [7995](#), [8490](#), [8544](#), [22165](#), [22168](#)
 \tl_if_eq:nnTF .. [41](#), [68](#), [68](#), [391](#), [3269](#)
 \tl_if_eq_p:NN [41](#), [3257](#)
 \tl_if_exist:N [3880](#), [3881](#)
 \tl_if_exist:NTF
 ... [38](#), [2883](#), [2885](#), [2925](#), [3419](#), [17634](#)
 \tl_if_exist_p:N [38](#), [2925](#)
 \tl_if_head_eq_catcode:nN [361](#)
 \tl_if_head_eq_catcode:nNTF
 ... [48](#), [3607](#), [23348](#), [23348](#)
 \tl_if_head_eq_catcode_p:nN [48](#), [3607](#)
 \tl_if_head_eq_charcode:nN [360](#)
 \tl_if_head_eq_charcode:nNTF
 ... [48](#), [3607](#), [3624](#), [3625](#)
 \tl_if_head_eq_charcode_p:nN [48](#), [3607](#)
 \tl_if_head_eq_meaning:nN [361](#)
 \tl_if_head_eq_meaning:nNTF [48](#), [3607](#)
 \tl_if_head_eq_meaning_p:nN
 ... [48](#), [3607](#), [19015](#)
 \tl_if_head_is_group:nTF [48](#),
 [3514](#), [3636](#), [3671](#), [3697](#), [23375](#), [23457](#)
 \tl_if_head_is_group_p:n ... [48](#), [3697](#)
 \tl_if_head_is_N_type:n [361](#)
 \tl_if_head_is_N_type:nTF
 ... [48](#), [3511](#), [3611](#), [3630](#), [3647](#),
 [3680](#), [23252](#), [23372](#), [23454](#), [23741](#),
 [23773](#), [23866](#), [23916](#), [24246](#), [24391](#)
 \tl_if_head_is_N_type_p:n .. [48](#), [3680](#)
 \tl_if_head_is_space:nTF
 . [48](#), [3708](#), [4378](#), [24373](#), [24382](#), [24663](#)
 \tl_if_head_is_space_p:n ... [48](#), [3708](#)
 \tl_if_in:Nn [453](#)
 \tl_if_in:nn [351](#)
 \tl_if_in:NnTF ... [41](#), [3166](#), [3284](#),
 [3284](#), [3285](#), [3287](#), [3288](#), [6225](#), [9009](#)
 \tl_if_in:nnTF [41](#),
 [350](#), [370](#), [3086](#), [3150](#), [3152](#), [3284](#),
 [3285](#), [3286](#), [3290](#), [3298](#), [3299](#), [3946](#),
 [3955](#), [8405](#), [8407](#), [17891](#), [21974](#), [24457](#)
 \tl_if_novalue:nTF [41](#), [3301](#)
 \tl_if_novalue_p:n [41](#)
 \tl_if_single:n [351](#)
 \tl_if_single:NTF [42](#), [3318](#), [3319](#), [3320](#)
 \tl_if_single:nTF
 ... [42](#), [3319](#), [3320](#), [3321](#), [3322](#)
 \tl_if_single_p:N [42](#), [3318](#)
 \tl_if_single_p:n [42](#), [3318](#), [3322](#)
 \tl_if_single_token:nTF .. [247](#), [23250](#)
 \tl_if_single_token_p:n .. [247](#), [23250](#)
 \tl_item:Nn [49](#), [3720](#)
 \tl_item:nn [49](#), [973](#), [3720](#), [24295](#)
 \tl_log:N [49](#), [3743](#)
 \tl_log:n
 ... [49](#), [319](#), [319](#), [761](#), [2300](#), [2316](#),
 [3745](#), [3767](#), [6071](#), [6293](#), [16806](#), [23015](#)
 \tl_lower_case:n .. [60](#), [117](#), [248](#), [23349](#)
 \tl_lower_case:nn [248](#), [23349](#)
 \tl_map_break:
 ... [43](#), [216](#), [792](#), [3371](#), [3377](#),
 [3389](#), [3398](#), [3405](#), [3410](#), [17629](#), [17630](#)
 \tl_map_break:n
 ... [43](#), [44](#), [3410](#), [9024](#), [16964](#), [16971](#)
 \tl_map_function:NN
 .. [42](#), [42](#), [42](#), [3367](#), [3434](#), [9003](#), [19083](#)
 \tl_map_function:nN [42](#),
 [42](#), [43](#), [2194](#), [3367](#), [3429](#), [4645](#), [18404](#)
 \tl_map_inline:Nn
 [42](#), [43](#), [766](#), [3381](#), [9023](#), [16964](#), [16971](#)
 \tl_map_inline:nn [43](#),
 [43](#), [93](#), [3381](#), [9484](#), [12846](#), [15556](#), [16899](#)
 \tl_map_variable:NNn [43](#), [3394](#)
 \tl_map_variable:nNn .. [43](#), [354](#), [3394](#)
 \tl_mixed_case:n .. [60](#), [248](#), [249](#), [23349](#)
 \tl_mixed_case:nn [248](#), [23349](#)
 \l_tl_mixed_case_ignore_tl
 ... [250](#), [23702](#), [24283](#)
 \l_tl_mixed_change_ignore_tl .. [250](#)
 \tl_new:N [37](#), [38](#),
 [119](#), [339](#), [2856](#), [2883](#), [2885](#), [3282](#),
 [3283](#), [3769](#), [3770](#), [3771](#), [3772](#), [4580](#),
 [4581](#), [6222](#), [6504](#), [6506](#), [6507](#), [7217](#),
 [7576](#), [7776](#), [8099](#), [8437](#), [8438](#), [8805](#),
 [8975](#), [9184](#), [9329](#), [9354](#), [9459](#), [9461](#),
 [9473](#), [9475](#), [9476](#), [9478](#), [9786](#), [10382](#),
 [10383](#), [10384](#), [10527](#), [10529](#), [10530](#),
 [10533](#), [10534](#), [10538](#), [10539](#), [17245](#),
 [17312](#), [17319](#), [17768](#), [17769](#), [17775](#),
 [17785](#), [19659](#), [19886](#), [19888](#), [21477](#),
 [21502](#), [21503](#), [22087](#), [22323](#), [24231](#),
 [24273](#), [24278](#), [24283](#), [25202](#), [25872](#)
 \tl_put_left:Nn [38](#), [2962](#)
 \tl_put_right:Nn [38](#),
 [203](#), [203](#), [1495](#), [2994](#), [4705](#), [7249](#),
 [7251](#), [7254](#), [7256](#), [7262](#), [7264](#), [7266](#),

- 7268, 7269, 7271, 7273, 7275, 7277,
 9701, 9704, 9709, 11087, 17248, 20027
 \tl_rand_item:N 251, 24292
 \tl_rand_item:n 251, 24292
 \tl_range:Nnn 251, 24299
 \tl_range:nnn ... 251, 252, 974, 24299
 \tl_range_braced:Nnn ... 252, 24299
 \tl_range_braced:nnn 251, 252, 24299
 \tl_range_unbraced:Nnn ... 252, 24299
 \tl_range_unbraced:nnn 251, 252, 24299
 \tl_remove_all:Nn .. 39, 39, 3205, 9008
 \tl_remove_once:Nn 39, 3199
 \tl_replace_all:Nnn
 39, 388, 451, 3130, 3206, 4654
 \tl_replace_once:Nnn
 39, 3130, 3200, 7292
 \tl_rescan:nn 40, 40, 3027
 \tl_reverse:N 45, 45, 3568
 \tl_reverse:n
 45, 45, 45, 950, 3548, 3569, 3571
 \tl_reverse_items:n . 45, 45, 45, 3439
 \tl_reverse_tokens:n 247, 23260
 .tl_set:N 174, 10941
 \tl_set:Nn 38, 39,
 40, 65, 174, 203, 330, 340, 345, 501,
 766, 766, 804, 1500, 2914, 2938,
 3028, 3057, 3116, 3131, 3135, 3272,
 3273, 3404, 3459, 3569, 3756, 3829,
 3833, 4612, 4617, 4637, 4644, 4648,
 4659, 4674, 4685, 4731, 4741, 4750,
 4757, 4790, 4793, 4814, 4822, 4831,
 4841, 4850, 4860, 4870, 4884, 4907,
 4911, 5003, 5568, 6528, 6556, 6602,
 6636, 6642, 6645, 6651, 6658, 6683,
 6735, 6766, 6894, 7247, 7252, 7594,
 7809, 7869, 7885, 7886, 7894, 7895,
 7897, 7903, 7906, 7929, 7930, 7939,
 7951, 7955, 7973, 7978, 8036, 8421,
 8448, 8530, 8803, 8990, 8993, 8994,
 9235, 9390, 9466, 9527, 9529, 9530,
 9539, 9544, 9565, 9712, 9731, 9733,
 9819, 10391, 10410, 10417, 10434,
 10441, 10452, 10508, 10545, 10547,
 10575, 10588, 10594, 10597, 10606,
 10607, 10610, 10710, 10967, 10969,
 10980, 10981, 11005, 11006, 11046,
 11067, 11079, 11085, 11147, 13544,
 16772, 16949, 16963, 16976, 17265,
 17267, 17889, 17901, 18005, 18062,
 18126, 18732, 18737, 18983, 19040,
 19070, 19723, 19728, 19809, 19841,
 20119, 20370, 20391, 20461, 20490,
 20514, 21678, 21975, 21976, 22089,
 22092, 22324, 22869, 23112, 23122,
 23301, 23326, 23328, 23342, 24024,
 24043, 24196, 24232, 24275, 24280,
 24284, 24665, 24674, 24715, 24718,
 24721, 24725, 24728, 25207, 25222
 \tl_set_eq:NN
 38, 435, 2877, 2888, 3799,
 4602, 4603, 4604, 4605, 6261, 6519,
 6520, 6521, 6522, 7796, 7797, 7798,
 7799, 8493, 8501, 11141, 16780, 20209
 \tl_set_from_file:Nnn ... 250, 23300
 \tl_set_from_file_x:Nnn .. 251, 23327
 \tl_set_rescan:Nnn 40, 40, 3027
 .tl_set_x:N 174, 10941
 \tl_show:N 49, 49, 792, 3743, 4437, 17640
 \tl_show:n 49, 49, 243, 319,
 319, 365, 365, 761, 943, 2296, 2313,
 3743, 3752, 4436, 6070, 6291, 7056,
 7126, 7132, 7138, 7144, 16804, 23013
 \tl_show_analysis:N . 204, 780, 17632
 \tl_show_analysis:n . 204, 780, 17632
 \tl_sort:Nn 46, 3502, 16961
 \tl_sort:nN . 46, 771, 772, 3502, 17098
 \tl_tail:N 47, 1501, 3574, 18992
 \tl_tail:n 47, 3574
 \tl_to_lowercase:n 3773
 \tl_to_str:N 44, 51, 152, 367,
 530, 864, 3415, 3850, 3936, 3946,
 4396, 8995, 9160, 9173, 9530, 9535
 \tl_to_str:n
 ... 40, 40, 44, 44, 51, 60, 61, 130,
 130, 152, 171, 178, 210, 211, 303,
 352, 367, 373, 380, 472, 487, 488,
 864, 865, 1356, 1378, 1463, 1471,
 1482, 1487, 1684, 1789, 1857, 2641,
 2650, 2653, 2660, 2664, 3049, 3147,
 3236, 3325, 3414, 3587, 3753, 3768,
 3813, 3851, 3946, 3955, 4089, 4111,
 4135, 4142, 4194, 4201, 4276, 4295,
 4306, 4331, 4339, 4347, 4353, 4365,
 5843, 5860, 5904, 6077, 7417, 7421,
 7453, 7454, 7487, 7500, 7502, 7504,
 7522, 7739, 7846, 7856, 7914, 7915,
 7957, 7980, 8004, 8005, 8303, 8304,
 8582, 8583, 9048, 9116, 9467, 9482,
 9982, 10110, 10241, 10476, 11230,
 12145, 12150, 12258, 12259, 12264,
 12268, 13076, 18404, 20084, 20226,
 22117, 22200, 22428, 22431, 22989,
 23018, 23020, 23024, 23026, 23031,
 23033, 23589, 23592, 24452, 24457
 \tl_to_uppercase:n 3773
 \tl_trim_spaces:N 46, 3455
 \tl_trim_spaces:n
 46, 50, 3455, 4666, 11230

- \tl_trim_spaces:n [356](#)
- \tl_upper_case:n .. [60](#), [117](#), [248](#), [23349](#)
- \tl_upper_case:nn [248](#), [23349](#)
- \tl_use:N [45](#),
[75](#), [160](#), [164](#), [167](#), [3417](#), [10778](#), [23559](#)
- \g_tmpa_tl [50](#), [3769](#)
- \l_tmpa_tl
..... [4](#), [39](#), [50](#), [1185](#), [1187](#), [1204](#), [3771](#)
- \g_tmpb_tl [50](#), [3769](#)
- \l_tmpb_tl
..... [50](#), [1186](#), [1187](#), [1202](#), [1204](#), [3771](#)
- tl internal commands:
- \c__tl_accents_lt_tl [964](#)
- __tl_act:NNNnn [357](#),
[357](#), [358](#), [950](#), [3502](#), [3553](#), [23265](#), [23288](#)
- __tl_act_count_group:nn [23284](#)
- __tl_act_count_normal:nN [23284](#)
- __tl_act_count_space:n [23284](#)
- __tl_act_end:w [3502](#)
- __tl_act_end:wn [951](#), [3523](#), [3529](#)
- __tl_act_group:nwnNNN [3502](#)
- __tl_act_group_recurse:Nnn
..... [23275](#), [23279](#)
- __tl_act_loop:w [3502](#)
- __tl_act_normal:NwnNNN [3502](#)
- __tl_act_output:n [358](#), [3502](#)
- __tl_act_result:n
[357](#), [3507](#), [3529](#), [3544](#), [3545](#), [3546](#), [3547](#)
- __tl_act_reverse [358](#)
- __tl_act_reverse_output:n
..... [3502](#), [3563](#), [3565](#), [3567](#), [23276](#)
- __tl_act_space:wnnNNN [357](#), [3502](#)
- __tl_analysis:n
[783](#), [792](#), [17342](#), [17614](#), [17636](#), [17644](#)
- __tl_analysis_a:n [17346](#), [17369](#)
- __tl_analysis_a_bgroup:w
..... [17400](#), [17422](#)
- __tl_analysis_a_cs:ww [17478](#)
- __tl_analysis_a_egroup:w
..... [17402](#), [17422](#)
- __tl_analysis_a_group:nw [17422](#)
- __tl_analysis_a_group_aux:w . [17422](#)
- __tl_analysis_a_group_auxii:w [17422](#)
- __tl_analysis_a_group_test:w . [17422](#)
- __tl_analysis_a_loop:w .. [17376](#),
[17379](#), [17420](#), [17462](#), [17475](#), [17493](#)
- __tl_analysis_a_safe:N
..... [17401](#), [17443](#), [17478](#)
- __tl_analysis_a_space:w [17399](#), [17405](#)
- __tl_analysis_a_space_test:w ...
..... [785](#), [17405](#)
- __tl_analysis_a_store:
..... [785](#), [17416](#), [17458](#), [17464](#)
- __tl_analysis_a_type:w [17380](#), [17381](#)
- __tl_analysis_b:n [17347](#), [17506](#)
- __tl_analysis_b_char:Nww
..... [17533](#), [17539](#)
- __tl_analysis_b_cs:Nww [17535](#), [17559](#)
- __tl_analysis_b_cs_test:ww .. [17559](#)
- __tl_analysis_b_loop:w
..... [791](#), [17506](#), [17605](#), [17610](#)
- __tl_analysis_b_normal:wwN
..... [17519](#), [17580](#)
- __tl_analysis_b_normals:ww
[790](#), [790](#), [17516](#), [17519](#), [17556](#), [17566](#)
- __tl_analysis_b_special:w
..... [17522](#), [17577](#)
- __tl_analysis_b_special_char:wN
..... [17577](#)
- __tl_analysis_b_special_space:w
..... [17577](#)
- \l__tl_analysis_char_token
..... [781](#), [785](#),
[786](#), [17313](#), [17409](#), [17414](#), [17452](#), [17457](#)
- __tl_analysis_cs_space_count:NN
..... [17326](#), [17492](#), [17562](#)
- __tl_analysis_cs_space_count:w .
..... [17326](#)
- __tl_analysis_cs_space_count_-
end:w [17326](#)
- __tl_analysis_disable:n
..... [17351](#), [17371](#), [17437](#), [17489](#)
- __tl_analysis_extract_charcode:
..... [17320](#), [17432](#)
- __tl_analysis_extract_charcode_-
aux:w [17320](#)
- __tl_analysis_from_str_map_-
inline:nn [779](#)
- \l__tl_analysis_index_int
..... [787](#), [788](#),
[17316](#), [17374](#), [17377](#), [17415](#), [17433](#),
[17470](#), [17472](#), [17498](#), [17500](#), [17583](#)
- \l__tl_analysis_internal_tl .. [17312](#)
- __tl_analysis_map_inline:nn ...
..... [779](#), [17612](#), [19095](#), [19678](#)
- __tl_analysis_map_inline_aux:Nn
..... [17612](#)
- \l__tl_analysis_nesting_int
..... [784](#), [17317](#), [17375](#), [17466](#), [17474](#)
- \l__tl_analysis_normal_int
..... [17315](#), [17373](#), [17418](#), [17460](#),
[17471](#), [17473](#), [17490](#), [17499](#), [17504](#)
- \g__tl_analysis_result_tl
..... [791](#), [17319](#), [17508](#), [17628](#), [17650](#)
- __tl_analysis_show:
..... [17638](#), [17646](#), [17648](#)
- __tl_analysis_show_active:n ...
..... [17663](#), [17692](#)

_tl_analysis_show_cs:n [17659](#), [17692](#)
 \c_tl_analysis_show_etc_str ...
 [794](#), [17712](#), [17714](#), [17719](#)
 _tl_analysis_show_long:nn .. [17692](#)
 _tl_analysis_show_long_
 aux:nnnn [17692](#), [17698](#)
 _tl_analysis_show_loop:wNw . [17648](#)
 _tl_analysis_show_normal:n ...
 [17666](#), [17672](#)
 _tl_analysis_show_value:N
 [17677](#), [17701](#)
 \l_tl_analysis_token
 [781](#), [781](#), [785](#),
 [786](#), [17313](#), [17323](#), [17380](#), [17384](#),
 [17387](#), [17390](#), [17438](#), [17442](#), [17457](#)
 \l_tl_analysis_type_int
 [785](#), [787](#), [17318](#),
 [17383](#), [17398](#), [17466](#), [17468](#), [17471](#)
 _tl_build:Nw [203](#),
 [203](#), [203](#), [804](#), [835](#), [17264](#), [17992](#),
 [17999](#), [18781](#), [19119](#), [19200](#), [19947](#)
 _tl_build_aux:NNw [778](#), [17264](#)
 _tl_build_end: [203](#), [203](#), [778](#), [835](#),
 [17281](#), [18011](#), [18334](#), [18339](#), [18790](#),
 [19166](#), [19209](#), [19214](#), [19228](#), [19981](#)
 _tl_build_end_assignment:n ...
 [778](#), [17275](#), [17281](#)
 _tl_build_end_aux:n [778](#)
 \l_tl_build_index_int ... [17243](#),
 [17257](#), [17278](#), [17290](#), [17291](#), [17292](#),
 [17294](#), [17299](#), [17300](#), [17301](#), [17303](#)
 _tl_build_one:n
 [203](#), [203](#), [777](#), [804](#),
 [862](#), [17288](#), [17993](#), [18010](#), [18060](#),
 [18124](#), [18312](#), [18329](#), [18335](#), [18338](#),
 [18385](#), [18388](#), [18419](#), [18430](#), [18432](#),
 [18557](#), [18571](#), [18612](#), [18637](#), [18646](#),
 [18655](#), [18687](#), [18700](#), [18704](#), [18779](#),
 [18784](#), [18789](#), [18792](#), [18826](#), [19081](#),
 [19097](#), [19114](#), [19171](#), [19218](#), [19223](#),
 [19234](#), [19966](#), [19997](#), [20025](#), [20082](#),
 [20084](#), [20097](#), [20141](#), [20156](#), [20190](#)
 \l_tl_build_result_tl
 [777](#), [778](#), [17245](#), [17248](#), [17279](#), [17285](#)
 \l_tl_build_start_index_int ...
 .. [17243](#), [17251](#), [17277](#), [17294](#), [17303](#)
 _tl_build_unpack:
 [17246](#), [17283](#), [17293](#), [17302](#)
 _tl_build_unpack_loop:w [17246](#)
 _tl_build_x:Nw ... [203](#), [17264](#), [18306](#)
 _tl_case:NnTF
 [3335](#), [3340](#), [3345](#), [3350](#), [3352](#)
 _tl_case:nnTF [3332](#)
 _tl_case:Nw [3332](#)
 _tl_case_end:nw [3332](#)
 _tl_change_case:nnn [23349](#), [23350](#),
 [23351](#), [23352](#), [23353](#), [23354](#), [23355](#)
 _tl_change_case_aux:nnn [23355](#)
 _tl_change_case_char:nN [23355](#)
 _tl_change_case_char_auxi:nN [23355](#)
 _tl_change_case_char_auxii:nN .
 [23355](#)
 _tl_change_case_char_lower:N [23355](#)
 _tl_change_case_char_lower:Nnn
 [23355](#)
 _tl_change_case_char_mixed:N [23355](#)
 _tl_change_case_char_mixed:Nnn
 [23355](#)
 _tl_change_case_char_upper:N [23355](#)
 _tl_change_case_char_upper:Nnn
 [23355](#)
 _tl_change_case_char_UTFviii:nn
 [23355](#)
 _tl_change_case_char_UTFviii:nnN
 [23355](#)
 _tl_change_case_char_UTFviii:nnN
 [23582](#), [23584](#), [23586](#), [23587](#)
 _tl_change_case_char_UTFviii:nnNN
 [23355](#)
 _tl_change_case_char_UTFviii:nnNNN
 [23355](#)
 _tl_change_case_char_UTFviii:nnNNNN
 [23355](#)
 _tl_change_case_char_UTFviii:nnNNNNN
 [23530](#), [23585](#)
 _tl_change_case_cs:N [23355](#)
 _tl_change_case_cs:NN [23355](#)
 _tl_change_case_cs:NNn [23355](#)
 _tl_change_case_cs_accents:NN .
 [23355](#)
 _tl_change_case_cs_expand:NN [23355](#)
 _tl_change_case_cs_expand:Nnw .
 [23355](#)
 _tl_change_case_cs_letterlike:Nn
 [23355](#)
 _tl_change_case_cs_letterlike:NnN
 [23355](#)
 _tl_change_case_end:wn [23355](#)
 _tl_change_case_group:nwnn . [23355](#)
 _tl_change_case_group_lower:nnnn
 [23355](#)
 _tl_change_case_group_mixed:nnnn
 [23355](#)
 _tl_change_case_group_upper:nnnn
 [23355](#)
 _tl_change_case_if_expandable:NTF
 [23355](#),
 [23747](#), [23780](#), [23872](#), [23922](#), [24252](#)
 _tl_change_case_loop:wn [962](#)

- _tl_change_case_loop:wnn [954, 956, 23355](#)
- _tl_change_case_lower_az:Nnw [23759](#)
- _tl_change_case_lower_lt:nNnw [23829](#)
- _tl_change_case_lower_lt:NNw [23829](#)
- _tl_change_case_lower_lt:Nnw [23829](#)
- _tl_change_case_lower_lt:nnw [23829](#)
- _tl_change_case_lower_lt:Nw . [23829](#)
- _tl_change_case_lower_sigma:Nnw [23729](#)
- _tl_change_case_lower_sigma:Nw [23729](#)
- _tl_change_case_lower_sigma:w [23729](#)
- _tl_change_case_lower_tr:Nnw [23759](#)
- _tl_change_case_lower_tr-
 auxi:Nw [23759](#)
- _tl_change_case_lower_tr-
 auxii:Nw [23759](#)
- _tl_change_case_math:NNNnnn [955, 23355](#)
- _tl_change_case_math:NwNNnn . [23355](#)
- _tl_change_case_math_group:nwNNnn [23355](#)
- _tl_change_case_math_loop:wNNnn [23355](#)
- _tl_change_case_math_space:wNNnn [23355](#)
- _tl_change_case_mixed_nl:NNw [24234](#)
- _tl_change_case_mixed_nl:Nnw [24234](#)
- _tl_change_case_mixed_nl:Nw . [24234](#)
- _tl_change_case_mixed_skip:N [23355](#)
- _tl_change_case_mixed_skip:NN [23355](#)
- _tl_change_case_mixed_skip-
 tidy:Nwn [23355](#)
- _tl_change_case_mixed_switch:w [23355](#)
- _tl_change_case_N_type:Nnnn . [23355](#)
- _tl_change_case_N_type:NNNnnn [23355](#)
- _tl_change_case_N_type:Nwnn . [23355](#)
- _tl_change_case_output:nwn [23355,](#)
 [23733, 23767, 23775, 23789, 23791,](#)
 [23801, 23812, 23824, 23851, 23860,](#)
 [23888, 23910, 23939, 24240, 24266](#)
- _tl_change_case_protect:wNN . [23355](#)
- _tl_change_case_result:n [23368, 23381, 23382, 23384](#)
- _tl_change_case_setup:NN [24207, 24212, 24214](#)
- _tl_change_case_space:wnn . . [23355](#)
- _tl_change_case_upper_az:Nnw [23759](#)
- _tl_change_case_upper_de-alt:Nnw [23936](#)
- _tl_change_case_upper_lt:NNw [23829](#)
- _tl_change_case_upper_lt:Nnw [23829](#)
- _tl_change_case_upper_lt:nnw [23829](#)
- _tl_change_case_upper_lt:Nw . [23829](#)
- _tl_change_case_upper_sigma:Nnw [23729](#)
- _tl_change_case_upper_tr:Nnw [23759](#)
- _tl_count:n [355, 3426](#)
- _tl_from_file_do:w [23300](#)
- _tl_gbuild:Nw [203, 17264](#)
- _tl_gbuild_x:Nw [203, 17264](#)
- _tl_head_auxi:nw [3574](#)
- _tl_head_auxii:n [3574](#)
- _tl_if_blank_p:NNw [3211](#)
- _tl_if_empty_return:n [348, 349,](#)
 [3212, 3246, 6205, 6211, 23253, 23257](#)
- _tl_if_head_eq_meaning_
 normal:nN [3648, 3652](#)
- _tl_if_head_eq_meaning_
 special:nN [3649, 3661](#)
- _tl_if_head_is_N_type:w . [362, 3680](#)
- _tl_if_head_is_space:w [3708](#)
- _tl_if_noalue:w [3301](#)
- _tl_if_single:nnw . [352, 3324, 3331](#)
- _tl_if_single:nTF [3322](#)
- _tl_if_single_p:n [3322](#)
- _tl_internal_a_tl . . [342, 365,](#)
 [3052, 3057, 3116, 3269, 3756, 3762,](#)
 [23320, 23326, 23342, 23345, 24024,](#)
 [24026, 24043, 24048, 24196, 24198](#)
- _tl_internal_b_tl [3269](#)
- _tl_item:nn [3720](#)
- _tl_item_aux:nn [3720](#)
- _tl_lookup_lower:N [23355](#)
- _tl_lookup_mixed:N [23355](#)
- _tl_lookup_upper:N [23355](#)
- _tl_loop:nn . . . [24040, 24049, 24080](#)
- _tl_map_function:Nn [353, 3367, 3386](#)
- _tl_map_variable:Nnn [3394](#)
- _tl_range:Nnnn [24299](#)
- _tl_range:nnNn [24299](#)
- _tl_range:nnnNn [24299](#)
- _tl_range:w [974, 24299](#)
- _tl_range_braced:w . . . [974, 24299](#)
- _tl_range_collect:nn . . [974, 24299](#)
- _tl_range_collect_braced:w [974, 24299](#)
- _tl_range_collect_group:nN . [24299](#)
- _tl_range_collect_group:nn [24393, 24402](#)
- _tl_range_collect_N:nN [24299](#)

- __tl_range_collect_space:nw . [24299](#)
- __tl_range_collect_unbraced:w [24299](#)
- __tl_range_items:nnNn [974](#)
- __tl_range_normalize:nn
 [24320](#), [24324](#), [24404](#)
- __tl_range_skip:w [974](#), [24299](#)
- __tl_range_skip_spaces:n [24299](#)
- __tl_range_unbraced:w . . . [974](#), [24299](#)
- __tl_replace:NnNNNnn
 [345](#), [346](#), [3131](#), [3133](#), [3135](#), [3137](#), [3142](#)
- __tl_replace_auxi:NnnNNNnn [346](#), [3142](#)
- __tl_replace_auxii:nNNNnn
 [345](#), [346](#), [347](#), [3142](#)
- __tl_replace_next:w
 [345](#), [347](#), [3135](#), [3137](#), [3142](#)
- __tl_replace_wrap:w
 [345](#), [347](#), [3131](#), [3133](#), [3142](#)
- __tl_rescan:w
 [343](#), [344](#), [3027](#), [3108](#), [3109](#), [3124](#)
- \c_tl_rescan_marker_tl [344](#),
 [3026](#), [3044](#), [3065](#), [3113](#), [23314](#), [23325](#)
- __tl_reverse_group:nn [23260](#)
- __tl_reverse_group_preserve:nn [3548](#)
- __tl_reverse_items:nwNwn [3439](#)
- __tl_reverse_items:wn [3439](#)
- __tl_reverse_normal:nN . . [3548](#), [23266](#)
- __tl_reverse_space:n . . [3548](#), [23268](#)
- __tl_set_from_file:NNnn [23300](#)
- __tl_set_from_file_x:NNnn . . [23327](#)
- __tl_set_rescan:n . . [342](#), [3049](#), [3071](#)
- __tl_set_rescan:NNnn [3027](#)
- __tl_set_rescan:NnTF [3071](#)
- __tl_set_rescan_multi:n
 [342](#), [343](#), [3027](#), [3081](#)
- __tl_set_rescan_multiple:n . . [343](#)
- __tl_set_rescan_single:nn [343](#), [3071](#)
- __tl_set_rescan_single_aux:nn [3071](#)
- __tl_show:n [3752](#)
- __tl_show:NN [3743](#)
- __tl_show:w [3752](#)
- __tl_tmp:w [351](#),
 [356](#), [3293](#), [3294](#), [3464](#), [3501](#), [24007](#),
 [24011](#), [24014](#), [24026](#), [24030](#), [24031](#),
 [24032](#), [24033](#), [24048](#), [24051](#), [24182](#),
 [24185](#), [24198](#), [24201](#), [24202](#), [24203](#)
- __tl_trim_spaces:nn [50](#), [483](#), [556](#),
 [3456](#), [3464](#), [6576](#), [7019](#), [7832](#), [10508](#)
- __tl_trim_spaces_auxi:w . . [356](#), [3464](#)
- __tl_trim_spaces_auxii:w . [356](#), [3464](#)
- __tl_trim_spaces_auxiii:w [356](#), [3464](#)
- __tl_trim_spaces_auxiv:w . [356](#), [3464](#)
- token commands:
- \c_alignment_token
 [119](#), [468](#), [7315](#), [7354](#), [17548](#)
- \c_parameter_token
 [119](#), [468](#), [860](#), [7315](#), [7358](#), [7361](#)
- \g_peek_token [123](#), [123](#), [7573](#), [7584](#)
- \l_peek_token [123](#), [123](#), [477](#),
 [478](#), [977](#), [7573](#), [7582](#), [7622](#), [7634](#),
 [7654](#), [7663](#), [24435](#), [24436](#), [24437](#), [24440](#)
- \c_space_token [48](#), [50](#), [119](#),
 [252](#), [361](#), [469](#), [3638](#), [3673](#), [7315](#),
 [7378](#), [7663](#), [9634](#), [17384](#), [17414](#),
 [17551](#), [18074](#), [18109](#), [23343](#), [24437](#)
- \token_get_arg_spec:N [125](#), [7737](#)
- \token_get_prefix_spec:N . . [126](#), [7737](#)
- \token_get_replacement_spec:N . . .
 [126](#), [7737](#), [11259](#)
- \token_if_active:NTF [121](#), [7391](#)
- \token_if_active_p:N [121](#), [7391](#)
- \token_if_alignment:NTF [120](#), [120](#), [7352](#)
- \token_if_alignment_p:N . . . [120](#), [7352](#)
- \token_if_chardef:NTF [122](#), [7465](#), [17681](#)
- \token_if_chardef_p:N [122](#), [7465](#)
- \token_if_cs:NTF [121](#), [7430](#), [23487](#)
- \token_if_cs_p:N
 [121](#), [7430](#), [23787](#), [23879](#), [23929](#), [24259](#)
- \token_if_dim_register:NTF
 [122](#), [7465](#), [17683](#)
- \token_if_dim_register_p:N [122](#), [7465](#)
- \token_if_eq_catcode:NNTF
 [121](#), [123](#), [123](#), [123](#), [124](#), [7401](#)
- \token_if_eq_catcode_p:NN . . [121](#), [7401](#)
- \token_if_eq_catcode:NNTF
 [121](#), [124](#), [124](#),
 [124](#), [124](#), [7406](#), [9013](#), [9634](#), [15147](#),
 [18109](#), [18114](#), [18710](#), [18885](#), [18898](#),
 [18900](#), [18938](#), [19056](#), [19999](#), [20069](#)
- \token_if_eq_charcode_p:NN [121](#), [7406](#)
- \token_if_eq_meaning:NNTF
 [121](#), [124](#), [125](#), [125](#),
 [125](#), [478](#), [7396](#), [9686](#), [11748](#), [12786](#),
 [13495](#), [13497](#), [13502](#), [13734](#), [15676](#),
 [18411](#), [18716](#), [18743](#), [18874](#), [18896](#),
 [18928](#), [19051](#), [19054](#), [20040](#), [20067](#),
 [20105](#), [20122](#), [23437](#), [23465](#), [23469](#)
- \token_if_eq_meaning_p:NN
 [121](#), [7396](#), [23682](#)
- \token_if_expandable:NTF
 [121](#), [7435](#), [17679](#), [23678](#)
- \token_if_expandable_p:N . . [121](#), [7435](#)
- \token_if_group_begin:NTF . [119](#), [7337](#)
- \token_if_group_begin_p:N . [119](#), [7337](#)
- \token_if_group_end:NTF . . . [120](#), [7342](#)
- \token_if_group_end_p:N . . . [120](#), [7342](#)
- \token_if_int_register:NTF
 [122](#), [7465](#), [17684](#)
- \token_if_int_register_p:N [122](#), [7465](#)

- \token_if_letter:N 471
- \token_if_letter:NTF 120, 7381, 23753
- \token_if_letter_p:N 120, 7381
- \token_if_long_macro:NTF .. 121, 7465
- \token_if_long_macro_p:N .. 121, 7465
- \token_if_macro:NTF
 - ... 121, 7411, 7517, 7743, 7752, 7761
- \token_if_macro_p:N 121, 7411
- \token_if_math_subscript:NTF ...
 - 120, 7371
- \token_if_math_subscript_p:N ...
 - 120, 7371
- \token_if_math_superscript:NTF ..
 - 120, 7365
- \token_if_math_superscript_p:N ..
 - 120, 7365
- \token_if_math_toggle:NTF . 120, 7347
- \token_if_math_toggle_p:N . 120, 7347
- \token_if_mathchardef:NTF
 - 122, 7465, 17682
- \token_if_mathchardef_p:N . 122, 7465
- \token_if_muskip_register:NTF ...
 - 122, 7465
- \token_if_muskip_register_p:N ...
 - 122, 7465
- \token_if_other:NTF 120, 7386
- \token_if_other_p:N 120, 7386
- \token_if_parameter:NTF ... 120, 7357
- \token_if_parameter_p:N ... 120, 7357
- \token_if_primitive:NTF ... 122, 7511
- \token_if_primitive_p:N ... 122, 7511
- \token_if_protected_long_macro:NTF 121, 7465
- \token_if_protected_long_macro_p:N
 - 121, 7465, 23684
- \token_if_protected_macro:NTF ...
 - 121, 7465
- \token_if_protected_macro_p:N ...
 - 121, 7465, 23683
- \token_if_skip_register:NTF
 - 122, 7465, 17685
- \token_if_skip_register_p:N 122, 7465
- \token_if_space:NTF 120, 7376
- \token_if_space_p:N 120, 7376
- \token_if_toks_register:NTF
 - 122, 7465, 17686
- \token_if_toks_register_p:N 122, 7465
- \token_new:Nn 7768
- \token_to_meaning:N
 - . 119, 470, 473, 1354, 1369, 2042,
 - 2650, 7315, 7417, 7486, 7521, 7746,
 - 7755, 7764, 17323, 17675, 17700, 24440
- \token_to_str:N 4, 17, 51,
 - 119, 152, 307, 363, 410, 472, 615,
 - 617, 863, 1356, 1369, 1369, 1523,
 - 1532, 1664, 1684, 1773, 1782, 1803,
 - 1824, 1865, 1870, 1885, 1914, 1915,
 - 1925, 1931, 2036, 2042, 2166, 2197,
 - 2204, 2292, 2312, 2325, 2670, 2754,
 - 2769, 2782, 2804, 2828, 2841, 3026,
 - 3685, 3701, 3750, 4059, 5099, 5366,
 - 6021, 6029, 6042, 6228, 6298, 6350,
 - 7032, 7315, 7498, 7499, 7504, 7505,
 - 7506, 7507, 7508, 7509, 8091, 9516,
 - 9517, 9518, 9519, 9520, 9526, 10420,
 - 10444, 11635, 11636, 12144, 12157,
 - 12158, 12187, 12316, 12366, 12398,
 - 12418, 12433, 12445, 12446, 12459,
 - 12460, 12485, 12494, 12496, 12521,
 - 12524, 12549, 12551, 12565, 12581,
 - 12599, 12668, 12678, 12679, 12694,
 - 12695, 12938, 13178, 15744, 16811,
 - 17191, 17207, 17331, 17410, 17453,
 - 17482, 17531, 17542, 17544, 17546,
 - 17552, 17588, 17599, 17638, 17674,
 - 17699, 17720, 18016, 18023, 18131,
 - 18135, 18809, 20018, 20235, 20813,
 - 20815, 20976, 21528, 21677, 22270,
 - 22428, 22431, 22887, 22890, 23542,
 - 23550, 23556, 23559, 23609, 23612,
 - 23620, 24210, 24211, 24228, 24229
- token internal commands:
 - \c_token_A_int 7511, 7548
 - __token_delimit_by_char:w .. 7447
 - __token_delimit_by_count:w .. 7447
 - __token_delimit_by_dimen:w .. 7447
 - __token_delimit_by_macro:w .. 7447
 - __token_delimit_by_muskip:w . 7447
 - __token_delimit_by_skip:w ... 7447
 - __token_delimit_by_toks:w ... 7447
 - __token_if_macro_p:w 7411
 - __token_if_primitive:NNw 7511
 - __token_if_primitive:Nw 7511
 - __token_if_primitive_loop:N . 7511
 - __token_if_primitive_nullfont:N
 - 7511
 - __token_if_primitive_space:w . 7511
 - __token_if_primitive_undefined:N
 - 7511
 - __token_tmp:w 472, 7448,
 - 7457, 7458, 7459, 7460, 7461, 7462,
 - 7463, 7466, 7498, 7499, 7500, 7501,
 - 7503, 7505, 7506, 7507, 7508, 7509
- \toks 561, 7509
- \toksapp 937
- \toksdef 562, 17187
- \tokspre 938
- \tolerance 563

<code>\topmark</code>	564	<code>\Umathcharnumdef</code>	1005
<code>\topmarks</code>	666	<code>\Umathcharslot</code>	1006
<code>\topskip</code>	565	<code>\Umathclosebinspacing</code>	1007
<code>\tpack</code>	939	<code>\Umathcloseclosespacing</code>	1008
<code>\tracingassigns</code>	667	<code>\Umathcloseinnerspacing</code>	1009
<code>\tracingcommands</code>	566	<code>\Umathcloseopenspacing</code>	1010
<code>\tracingfonts</code>	980	<code>\Umathcloseopspacing</code>	1011
<code>\tracinggroups</code>	668	<code>\Umathcloseordspacing</code>	1012
<code>\tracingifs</code>	669	<code>\Umathclosepunctspacing</code>	1013
<code>\tracinglostchars</code>	567	<code>\Umathcloserelspacing</code>	1014
<code>\tracingmacros</code>	568	<code>\Umathcode</code>	158, 1015
<code>\tracingnesting</code>	670	<code>\Umathcodenum</code>	1016
<code>\tracingonline</code>	569	<code>\Umathconnectoroverlapmin</code>	1017
<code>\tracingoutput</code>	570	<code>\Umathfractiondelsize</code>	1018
<code>\tracingpages</code>	571	<code>\Umathfractiondenomdown</code>	1019
<code>\tracingparagraphs</code>	572	<code>\Umathfractiondenomvgap</code>	1020
<code>\tracingrestores</code>	573	<code>\Umathfractionnumup</code>	1021
<code>\tracingscantokens</code>	671	<code>\Umathfractionnumvgap</code>	1022
<code>\tracingstats</code>	574	<code>\Umathfractionrule</code>	1023
<code>true</code>	199	<code>\Umathinnerbinspacing</code>	1024
<code>trunc</code>	195	<code>\Umathinnerclosespacing</code>	1025
two commands:		<code>\Umathinnerinnerspacing</code>	1026
<code>\c_thirty_two</code>	85, 5958	<code>\Umathinneropenspacing</code>	1027
<code>\c_two_hundred_fifty_five</code> ..	85, 5959	<code>\Umathinneropspacing</code>	1028
<code>\c_two_hundred_fifty_six</code> ...	85, 5959	<code>\Umathinnerordspacing</code>	1029
		<code>\Umathinnerpunctspacing</code>	1030
		<code>\Umathinnerrelspacing</code>	1031
		<code>\Umathlimitabovebgap</code>	1032
		<code>\Umathlimitabovekern</code>	1033
		<code>\Umathlimitabovevgap</code>	1034
		<code>\Umathlimitbelowbgap</code>	1035
		<code>\Umathlimitbelowkern</code>	1036
		<code>\Umathlimitbelowvgap</code>	1037
		<code>\Umathnolimitsubfactor</code>	1038
		<code>\Umathnolimitsupfactor</code>	1039
		<code>\Umathopbinspacing</code>	1040
		<code>\Umathopclosespacing</code>	1041
		<code>\Umathopenbinspacing</code>	1042
		<code>\Umathopenclosespacing</code>	1043
		<code>\Umathopeninnerspacing</code>	1044
		<code>\Umathopenopenspacing</code>	1045
		<code>\Umathopenopspacing</code>	1046
		<code>\Umathopenordspacing</code>	1047
		<code>\Umathopenpunctspacing</code>	1048
		<code>\Umathopenrelspacing</code>	1049
		<code>\Umathoperatorsize</code>	1050
		<code>\Umathoppinnerspacing</code>	1051
		<code>\Umathopopenspacing</code>	1052
		<code>\Umathopopspacing</code>	1053
		<code>\Umathopordspacing</code>	1054
		<code>\Umathoppunctspacing</code>	1055
		<code>\Umathoprelspacing</code>	1056
		<code>\Umathordbinspacing</code>	1057
		<code>\Umathordclosespacing</code>	1058
U			
<code>\u</code>	<i>xxi</i> , 832, 24233		
<code>\uccode</code> ..	167, 182, 195, 197, 199, 201, 575		
<code>\Uchar</code>	982		
<code>\Ucharcat</code>	983		
<code>\uchyph</code>	576		
<code>\ucs</code>	1168		
<code>\Udelcode</code>	984		
<code>\Udelcodenum</code>	985		
<code>\Udelimiter</code>	986		
<code>\Udelimiterover</code>	987		
<code>\Udelimiterunder</code>	988		
<code>\Uhexensible</code>	989		
<code>\Umathaccent</code>	990		
<code>\Umathaxis</code>	991		
<code>\Umathbinbinspacing</code>	992		
<code>\Umathbinclosespacing</code>	993		
<code>\Umathbininnerspacing</code>	994		
<code>\Umathbinopenspacing</code>	995		
<code>\Umathbinopspacing</code>	996		
<code>\Umathbinordspacing</code>	997		
<code>\Umathbinpunctspacing</code>	998		
<code>\Umathbinrelspacing</code>	999		
<code>\Umathchar</code>	1000		
<code>\Umathcharclass</code>	1001		
<code>\Umathchardef</code>	1002		
<code>\Umathcharfam</code>	1003		
<code>\Umathcharnum</code>	1004		

\backslash Umathordinnerspacing	1059	undefine commands:
\backslash Umathordopenspacing	1060	\backslash undefine: 175, 10957
\backslash Umathordopspacing	1061	\backslash underline 577
\backslash Umathordordspacing	1062	\backslash unexpanded 672
\backslash Umathordpunctspacing	1063	\backslash unhbox 578
\backslash Umathordreldspacing	1064	\backslash unhcopy 579
\backslash Umathoverbarkern	1065	unicode internal commands:
\backslash Umathoverbarrule	1066	\backslash c__unicode_accents_lt_tl 23832, 23981
\backslash Umathoverbarvgap	1067	\backslash __unicode_codepoint_to_UTFviii:n
\backslash Umathoverdelimiterbgap	1068	.. 23942, 24025, 24045, 24046, 24197
\backslash Umathoverdelimitervgap	1069	\backslash __unicode_codepoint_to_UTFviii_-
\backslash Umathpunctbinspacing	1070	auxi:n 23942
\backslash Umathpunctclosespacing	1071	\backslash __unicode_codepoint_to_UTFviii_-
\backslash Umathpunctinnerspacing	1072	auxii:Nnn 23942
\backslash Umathpunctopenspacing	1073	\backslash __unicode_codepoint_to_UTFviii_-
\backslash Umathpunctopspacing	1074	auxiii:n 23942
\backslash Umathpunctordspacing	1075	\backslash g__unicode_data_ior
\backslash Umathpunctpunctspacing	1076	.. 4442, 4445, 4462, 4465, 4470, 4476
\backslash Umathpunctrelspacing	1077	\backslash c__unicode_dot_above_tl 23888, 23981
\backslash Umathquad	1078	\backslash c__unicode_dotless_i_tl
\backslash Umathradicaldegreeafter	1079	.. 23775, 23789, 23801, 24004
\backslash Umathradicaldegreebefore	1080	\backslash c__unicode_dotted_I_tl 23824, 24004
\backslash Umathradicaldegreeraise	1081	\backslash c__unicode_final_sigma_tl
\backslash Umathradicalkern	1082	.. 23743, 23755, 23981
\backslash Umathradicalrule	1083	\backslash c__unicode_I_ogonek_tl 23900, 24004
\backslash Umathradicalvgap	1084	\backslash c__unicode_i_ogonek_tl 23845, 24004
\backslash Umathrelbinspacing	1085	\backslash __unicode_map_inline:n
\backslash Umathrelclosespacing	1086	.. 4457, 4521, 4539, 4554
\backslash Umathrelinnerspacing	1087	\backslash __unicode_map_loop: 4464, 4468, 4481
\backslash Umathrelopenspacing	1088	\backslash __unicode_parse:w .. 4479, 4484, 4491
\backslash Umathrelopspacing	1089	\backslash __unicode_parse_auxi:w
\backslash Umathrelordspacing	1090	.. 4487, 4505, 4522, 4540
\backslash Umathrelpunctspacing	1091	\backslash __unicode_parse_auxii:w
\backslash Umathrelrelspacing	1092	.. 4507, 4508,
\backslash Umathskewedfractionhgap	1093	4533, 4537, 4542, 4543, 4546, 4549
\backslash Umathskewedfractionvgap	1094	\backslash c__unicode_std_sigma_tl 23754, 23981
\backslash Umathspaceafterscript	1095	\backslash __unicode_store:nnnnn
\backslash Umathstackdenomdown	1096	.. 4495, 4538, 4552
\backslash Umathstacknumup	1097	\backslash __unicode_tmp:NN .. 4557, 4565, 4567
\backslash Umathstackvgap	1098	\backslash l__unicode_tmp_tl .. 4476, 4477, 4479
\backslash Umathsubshiftdown	1099	\backslash c__unicode_upper_Eszett_tl
\backslash Umathsubshiftdrop	1100	.. 23939, 23981
\backslash Umathsubsupshiftdown	1101	\backslash uniformdeviate 981
\backslash Umathsubsupvgap	1102	\backslash unkern 580
\backslash Umathsubtopmax	1103	\backslash unless 673
\backslash Umathsupbottommin	1104	\backslash unpenalty 581
\backslash Umathsupshiftdrop	1105	\backslash unskip 582
\backslash Umathsupshiftdrop	1105	\backslash unvbox 583
\backslash Umathsupshiftup	1106	\backslash unvcopy 584
\backslash Umathsupsubbottommax	1107	\backslash Uoverdelimiter 1113
\backslash Umathunderbarkern	1108	\backslash uppercase 585
\backslash Umathunderbarrule	1109	
\backslash Umathunderbarvgap	1110	
\backslash Umathunderdelimiterbgap	1111	
\backslash Umathunderdelimitervgap	1112	

uptex commands:

`\uptex_disablecjktoken:D`
 1162, 5244, 5247, 22370
`\uptex_enablecjktoken:D` 1163
`\uptex_forcecjktoken:D` 1164
`\uptex_kchar:D` 1165
`\uptex_kchardef:D` 1166, 5248
`\uptex_kuten:D` 1167
`\uptex_ucs:D` 1168
`\Uradical` 1114
`\Uroot` 1115

use commands:

`\use:N` 16, 89, 304, 1417,
 1564, 1566, 1614, 1641, 1643, 1798,
 1880, 2005, 2007, 2009, 2011, 4405,
 4409, 5364, 5800, 5810, 5915, 5919,
 5921, 5923, 5924, 5928, 6326, 6348,
 8336, 8347, 8362, 8371, 8379, 8387,
 8393, 8400, 8453, 9592, 9985, 10620,
 10627, 10830, 18319, 20005, 20132,
 22846, 22990, 23392, 23489, 23498,
 23537, 23567, 23571, 23572, 24753
`\use:n` 17, 19, 37, 126,
 249, 293, 344, 510, 594, 615, 773,
 852, 888, 1418, 1423, 1496, 1785,
 1831, 1851, 1928, 2111, 2680, 2838,
 3032, 3104, 3106, 3301, 3406, 3664,
 3847, 3945, 3954, 4044, 4064, 4078,
 4383, 4473, 4542, 4543, 4546, 6896,
 7271, 7329, 7411, 7450, 7468, 7512,
 8300, 8317, 8579, 8596, 8891, 9017,
 9292, 9345, 9436, 10107, 10629,
 11671, 11679, 11688, 11705, 11713,
 11741, 12147, 12226, 12290, 16941,
 17183, 17307, 17689, 17870, 18284,
 18287, 18402, 18902, 19125, 19174,
 19256, 19662, 19708, 19744, 19827,
 20388, 20511, 20971, 22347, 22353,
 22361, 22373, 22380, 22389, 22399,
 22402, 22409, 22414, 23010, 23064,
 24668, 24686, 25454, 25592, 25626,
 25639, 25947, 25987, 26004, 26022
`\use:nn` 17,
 1423, 2360, 3064, 6880, 7737, 9981,
 12253, 12262, 12266, 15332, 17657,
 23023, 23025, 23030, 23032, 23323
`\use:nnn` 17, 1423, 2163
`\use:nnnn` 17, 1423
`\use_i:nn` 18,
 291, 302, 484, 725, 728, 740, 744,
 745, 756, 962, 1373, 1427, 1576,
 1737, 1814, 1955, 1983, 2144, 2835,
 3588, 4674, 4676, 7862, 9144, 12226,
 13928, 14412, 14641, 15156, 15327,

 15566, 15576, 15580, 16008, 16223,
 16650, 17039, 17074, 17084, 17094,
 17484, 18244, 18255, 18264, 18267,
 18276, 22355, 22363, 22375, 22382,
 22391, 22404, 22411, 23687, 23792
`\use_i:nnn` 18, 756, 1429, 1937,
 4879, 6064, 7746, 13885, 16644, 20044
`\use_i:nnnn`
 18, 23, 438, 439, 1429, 6322, 6337,
 6342, 6358, 6360, 13903, 13910, 14101
`\use_i_delimit_by_q_nil:nw` . 19, 1440
`\use_i_delimit_by_q_recursion_-`
 `stop:nw` 19,
 1440, 6147, 6163, 6369, 6384,
 19028, 23439, 23639, 23662, 23711
`\use_i_delimit_by_q_stop:nw`
 19, 380, 1440,
 1576, 1578, 4158, 4167, 4284, 4335,
 4338, 6989, 9555, 16629, 16701, 23082
`\use_i_ii:nnn` 18, 1429, 2385, 4856, 4956
`\use_ii:nn` 18,
 104, 291, 302, 484, 725, 728, 740,
 744, 745, 755, 794, 799, 836, 1375,
 1427, 1739, 1816, 1957, 1985, 2142,
 2329, 3076, 3590, 7863, 9140, 11583,
 11606, 13930, 15158, 15572, 15578,
 15582, 16010, 16225, 16582, 17486,
 18246, 18252, 18257, 18269, 18278,
 19021, 19193, 22348, 22400, 22415,
 23495, 23510, 23686, 23689, 23758
`\use_ii:nnn` 18, 1429, 1939, 7755
`\use_ii:nnnn` . 18, 438, 439, 1429, 6337
`\use_iii:nnn` 18, 1429, 2334, 7764
`\use_iii:nnnn` 18,
 438, 439, 1429, 6337, 6359, 6361, 6362
`\use_iv:nnnn`
 18, 438, 439, 1429, 6337, 6357
`\use_none:n` 18, 23, 50, 348,
 356, 356, 398, 449, 452, 494, 531,
 612, 613, 616, 616, 792, 795, 801,
 1443, 1504, 1620, 1639, 1831, 2113,
 2167, 3191, 3212, 3499, 3587, 3603,
 3667, 3684, 3694, 3695, 3700, 3715,
 3718, 4471, 4578, 4944, 4965, 5670,
 5676, 6052, 6149, 6164, 6538, 6663,
 6756, 6782, 7561, 7825, 7827, 8235,
 8420, 8644, 8648, 9565, 9620, 9675,
 10457, 10480, 10498, 11224, 11526,
 11530, 11534, 11538, 11617, 12800,
 12965, 12977, 12989, 13003, 13039,
 13070, 13130, 13171, 13904, 13907,
 14828, 15744, 16590, 16634, 16641,
 16988, 17287, 17482, 17531, 17623,
 17656, 17872, 18035, 18144, 18290,

- 18899, 22346, 22354, 22362, 22374,
22381, 22390, 22398, 22403, 22410,
22413, 23104, 23105, 23253, 23852,
24382, 24391, 24725, 25962, 25964
`\use_none:nn` 18, 298,
347, 352, 361, 361, 395, 396, 1443,
1636, 1775, 1783, 3174, 3325, 3454,
3614, 3633, 4746, 4865, 4886, 6796,
9621, 9664, 11458, 11525, 11529,
11533, 11537, 17994, 19470, 20057
`\use_none:nnn` . 18, 361, 1443, 1519,
1528, 1537, 2755, 2770, 3655, 9622,
11524, 11528, 11532, 11536, 17687
`\use_none:nnnn` . . 18, 1443, 5538, 9623
`\use_none:nnnnn` 18, 294, 532, 597, 1443, 1542,
1548, 9624, 9633, 11666, 11700,
11726, 11734, 13508, 16647, 16663
`\use_none:nnnnnn` . 18, 1443, 1887, 9625
`\use_none:nnnnnnn` 18, 304,
597, 1443, 1606, 1805, 9626, 11668,
11702, 11728, 11736, 12079, 13944
`\use_none:nnnnnnnn` 18, 1443
`\use_none:nnnnnnnnn` 18, 1443
`\use_none_delimit_by_q_nil:w` 19, 1437
`\use_none_delimit_by_q_recursion-
stop:w` 19, 93, 93, 93, 93,
1437, 1796, 1866, 1871, 1878, 2671,
2678, 4560, 6141, 6156, 19006, 19030
`\use_none_delimit_by_q_stop:w` . . .
. . . 19, 434, 451, 977, 1437, 3862,
4156, 4165, 4322, 5380, 6743, 6975,
6980, 8471, 9989, 16630, 23009, 24442
use internal commands:
`_use_none_delimit_by_s_stop:w`
. 95, 95, 6236
`\useboxresource` 974
`\useimageresource` 975
`\Uskewed` 1116
`\Uskewedwithdelims` 1117
`\Ustack` 1118
`\Ustartdisplaymath` 1119
`\Ustartmath` 1120
`\Ustopdisplaymath` 1121
`\Ustopmath` 1122
`\Usubscript` 1123
`\Usuperscript` 1124
utex commands:
`\utex_binbinspacing:D` 992
`\utex_binclosespacing:D` 993
`\utex_bininnerspacing:D` 994
`\utex_binopenspacing:D` 995
`\utex_binopspacing:D` 996
`\utex_binordspacing:D` 997
`\utex_binpunctspacing:D` 998
`\utex_binrelspacing:D` 999
`\utex_char:D` . 382, 982, 1255, 4401,
4409, 4463, 4497, 4499, 4500, 4502,
4516, 4517, 4528, 4529, 4555, 23515,
23563, 23759, 23981, 23983, 23984,
23987, 23988, 23989, 23990, 23991,
23992, 23994, 23995, 24005, 24008
`\utex_charcat:D` 983, 7226, 7242
`\utex_closebinspacing:D` 1007
`\utex_closeclosespacing:D` 1008
`\utex_closeinnerspacing:D` 1009
`\utex_closeopenspacing:D` 1010
`\utex_closeopspacing:D` 1011
`\utex_closeordspacing:D` 1012
`\utex_closepunctspacing:D` 1013
`\utex_closerelspacing:D` 1014
`\utex_connectoroverlapmin:D` . . . 1017
`\utex_delcode:D` 984, 1284
`\utex_delcodenum:D` 985, 1285
`\utex_delimiter:D` 986, 1286
`\utex_delimiterover:D` 987
`\utex_delimiterunder:D` 988
`\utex_fractiondelsize:D` 1018
`\utex_fractiondenomdown:D` 1019
`\utex_fractiondenomvgap:D` 1020
`\utex_fractionnumup:D` 1021
`\utex_fractionnumvgap:D` 1022
`\utex_fractionrule:D` 1023
`\utex_hextensible:D` 989
`\utex_innerbinspacing:D` 1024
`\utex_innerclosespacing:D` 1025
`\utex_innerinnerspacing:D` 1026
`\utex_inneropenspacing:D` 1027
`\utex_inneropspacing:D` 1028
`\utex_innerordspacing:D` 1029
`\utex_innerpunctspacing:D` 1030
`\utex_innerrelspacing:D` 1031
`\utex_limitabovebgap:D` 1032
`\utex_limitabovekern:D` 1033
`\utex_limitabovevgap:D` 1034
`\utex_limitbelowbgap:D` 1035
`\utex_limitbelowkern:D` 1036
`\utex_limitbelowvgap:D` 1037
`\utex_mathaccent:D` 990, 1287
`\utex_mathaxis:D` 991
`\utex_mathchar:D` 1000, 1288
`\utex_mathcharclass:D` 1001
`\utex_mathchardef:D` 1002, 1289
`\utex_mathcharfam:D` 1003
`\utex_mathcharnum:D` 1004, 1290
`\utex_mathcharnumdef:D` . . . 1005, 1291
`\utex_mathcharslot:D` 1006
`\utex_mathcode:D` 1015, 1292

\utext_mathcodenum:D	1016,	1293	\utex_relopspacing:D	1089
\utex_nolimitsubfactor:D	1038		\utex_relordspacing:D	1090
\utex_nolimitsupfactor:D	1039		\utex_relpunctspacing:D	1091
\utex_opbinspacing:D	1040		\utex_relrelspacing:D	1092
\utex_opclosespacing:D	1041		\utex_root:D	1115
\utex_openbinspacing:D	1042		\utex_skewed:D	1116
\utex_openclosespacing:D	1043		\utex_skewedgefractionhgap:D	...	1093
\utex_openinnerspacing:D	1044		\utex_skewedgefractionvgap:D	...	1094
\utex_openopenspacing:D	1045		\utex_skewedwithdelims:D	1117
\utex_openopspacing:D	1046		\utex_spaceafterscript:D	1095
\utex_openordspacing:D	1047		\utex_stack:D	1118
\utex_openpunctspacing:D	1048		\utex_stackdenomdown:D	1096
\utex_openrelspacing:D	1049		\utex_stacknumup:D	1097
\utex_operatorsize:D	1050		\utex_stackvgap:D	1098
\utex_opinnerspacing:D	1051		\utex_startdisplaymath:D	1119
\utex_opopenspacing:D	1052		\utex_startmath:D	1120
\utex_opopspacing:D	1053		\utex_stopdisplaymath:D	1121
\utex_opordspacing:D	1054		\utex_stopmath:D	1122
\utex_oppunctspacing:D	1055		\utex_subscript:D	1123
\utex_oprelspacing:D	1056		\utex_subshiftedown:D	1099
\utex_ordbinspacing:D	1057		\utex_subshiftdown:D	1100
\utex_ordclosespacing:D	1058		\utex_subsupshiftdown:D	1101
\utex_ordinnerspacing:D	1059		\utex_subsupvgap:D	1102
\utex_ordopenspacing:D	1060		\utex_subtopmax:D	1103
\utex_ordopspacing:D	1061		\utex_supbottommin:D	1104
\utex_ordordspacing:D	1062		\utex_superscript:D	1124
\utex_ordpunctspacing:D	1063		\utex_supshiftdown:D	1105
\utex_ordrelspacing:D	1064		\utex_supshiftup:D	1106
\utex_overbarkern:D	1065		\utex_supsbottommax:D	1107
\utex_overbarrule:D	1066		\utex_underbarkern:D	1108
\utex_overbarvgap:D	1067		\utex_underbarrule:D	1109
\utex_overdelimiter:D	1113		\utex_underbarvgap:D	1110
\utex_overdelimiterbgap:D	1068		\utex_underdelimiter:D	1125
\utex_overdelimitervgap:D	1069		\utex_underdelimiterbgap:D	...	1111
\utex_punctbinspacing:D	1070		\utex_underdelimitervgap:D	...	1112
\utex_punctclosespacing:D	1071		\utex_vextensible:D	1126
\utex_punctinnerspacing:D	1072		\Underdelimiter	1125
\utex_punctopenspacing:D	1073		\Uvextensible	1126
\utex_punctopspacing:D	1074				
\utex_punctordspacing:D	1075		V		
\utex_punctpunctspacing:D	1076		\v	24233
\utex_punctrelspacing:D	1077		\adjust	586
\utex_quad:D	1078		\align	587
\utex_radical:D	1114		value commands:		
\utex_radicaldegreeafter:D	...	1079		.value_forbidden:n	175, 10959
\utex_radicaldegreebefore:D	..	1080		.value_required:n	175, 10959
\utex_radicaldegreeraise:D	...	1081		\vbaddness	588
\utex_radicalkern:D	1082		\ vbox	589
\utex_radicalrule:D	1083		vbox commands:		
\utex_radicalvgap:D	1084		\ vbox:n	223, 21057
\utex_relbinspacing:D	1085		\ vbox_gset:Nn	224, 21071
\utex_relclosespacing:D	1086		\ vbox_gset:Nw	224, 21113
\utex_relinnerspacing:D	1087		\ vbox_gset_end:	224, 21113
\utex_reloppenspacing:D	1088		\ vbox_gset_to_ht:Nnn	224, 21099

- \vbox_gset_to_ht:Nnw 224, 21136
- \vbox_gset_top:Nn 224, 21085
- \vbox_set:Nn 224, 224, 21071, 21572
- \vbox_set:Nw 224, 21113, 21619
- \vbox_set_end: 224, 224, 21113, 21627
- \vbox_set_split_to_ht:NNn 224, 21156
- \vbox_set_to_ht:Nnn 224, 224, 21099
- \vbox_set_to_ht:Nnw 224, 21136
- \vbox_set_to_wd:Nnw 224
- \vbox_set_top:Nn
- 224, 21085, 21584, 21631
- \vbox_to_ht:nn 224, 21061
- \vbox_to_zero:n 224, 21061
- \vbox_top:n 223, 21057
- \vbox_unpack:N
- 225, 225, 21152, 21584, 21631
- \vbox_unpack_clear:N 225, 21152
- \vcenter 590
- vcoffin commands:
- \vcoffin_set:Nnn 230, 21568
- \vcoffin_set:Nnw 230, 21615
- \vcoffin_set_end: 230, 21615
- \vfil 591
- \vfill 592
- \vfiling 593
- \vfuzz 594
- \voffset 595
- \vpack 940
- \vrule 596
- \vsize 597
- \vskip 598
- \vsplit 599
- \vss 600
- \vtop 601
- W
- \wd 602
- \widowpenalties 674
- \widowpenalty 603
- \write 604
- X
- \xdef 605
- xetex commands:
- \xetex_charclass:D 809
- \xetex_charglyph:D 810
- \xetex_countfeatures:D 811
- \xetex_countglyphs:D 812
- \xetex_countselectors:D 813
- \xetex_countvariations:D 814
- \xetex_dashbreakstate:D 816
- \xetex_defaultencoding:D 815
- \xetex_featurecode:D 817
- \xetex_featurename:D 818
- \xetex_findfeaturebyname:D 819
- \xetex_findselectorbyname:D 820
- \xetex_findvariationbyname:D 821
- \xetex_firstfontchar:D 822
- \xetex_fonttype:D 823
- \xetex_generateactualtext:D 824
- \xetex_glyph:D 825
- \xetex_glyphbounds:D 826
- \xetex_glyphindex:D 827
- \xetex_glyphname:D 828
- \xetex_if_engine:TF
- 22462, 22463, 22464
- \xetex_if_engine_p: 22461
- \xetex_inputencoding:D 829
- \xetex_inputnormalization:D 830
- \xetex_interchartokenstate:D 831
- \xetex_interchartoks:D 832
- \xetex_isdefaultselector:D 833
- \xetex_isexclusivefeature:D 834
- \xetex_lastfontchar:D 835
- \xetex_linebreaklocale:D 837
- \xetex_linebreakpenalty:D 838
- \xetex_linebreakskip:D 836
- \xetex_OTcountfeatures:D 839
- \xetex_OTcountlanguages:D 840
- \xetex_OTcountscripts:D 841
- \xetex_OTfeaturetag:D 842
- \xetex_OTlanguagetag:D 843
- \xetex_OTscripttag:D 844
- \xetex_pdffile:D 845, 25434, 25485
- \xetex_pdfpagecount:D 846
- \xetex_picfile:D 847, 25427
- \xetex_selectorname:D 848
- \xetex_suppressfontnotfounderror:D
- 808, 1256
- \xetex_tracingfonts:D 849
- \xetex_upwardsmode:D 850
- \xetex_useglypmetrics:D 851
- \xetex_variation:D 852
- \xetex_variationdefault:D 853
- \xetex_variationmax:D 854
- \xetex_variationmin:D 855
- \xetex_variationname:D 856
- \xetex_XeTeXrevision:D 857
- \xetex_XeTeXversion:D
- 858, 5246, 5969, 22387, 22875
- \XeTeXcharclass 809
- \XeTeXcharglyph 810
- \XeTeXcountfeatures 811
- \XeTeXcountglyphs 812
- \XeTeXcountselectors 813
- \XeTeXcountvariations 814
- \XeTeXdashbreakstate 816
- \XeTeXdefaultencoding 815

<code>\XeTeXdelcode</code>	1283, 1284	<code>\XeTeXmathcode</code>	1292
<code>\XeTeXdelcodenum</code>	1285	<code>\XeTeXmathcodenum</code>	1293
<code>\XeTeXdelimiter</code>	1286	<code>\XeTeXOTcountfeatures</code>	839
<code>\XeTeXfeaturecode</code>	817	<code>\XeTeXOTcountlanguages</code>	840
<code>\XeTeXfeaturename</code>	818	<code>\XeTeXOTcountscripts</code>	841
<code>\XeTeXfindfeaturebyname</code>	819	<code>\XeTeXOTfeaturetag</code>	842
<code>\XeTeXfindselectorbyname</code>	820	<code>\XeTeXOTlanguagetag</code>	843
<code>\XeTeXfindvariationbyname</code>	821	<code>\XeTeXOTscripttag</code>	844
<code>\XeTeXfirstfontchar</code>	822	<code>\XeTeXpdffile</code>	845
<code>\XeTeXfonttype</code>	823	<code>\XeTeXpdfpagecount</code>	846
<code>\XeTeXgenerateactualtext</code>	824	<code>\XeTeXpicfile</code>	847
<code>\XeTeXglyph</code>	825	<code>\XeTeXrevision</code>	857
<code>\XeTeXglyphbounds</code>	826	<code>\XeTeXselectorname</code>	848
<code>\XeTeXglyphindex</code>	827	<code>\XeTeXtracingfonts</code>	849
<code>\XeTeXglyphname</code>	828	<code>\XeTeXupwardsmode</code>	850
<code>\XeTeXinputencoding</code>	829	<code>\XeTeXuseglyphmetrics</code>	851
<code>\XeTeXinputnormalization</code>	830	<code>\XeTeXvariation</code>	852
<code>\XeTeXinterchartokenstate</code>	831	<code>\XeTeXvariationdefault</code>	853
<code>\XeTeXinterchartoks</code>	832	<code>\XeTeXvariationmax</code>	854
<code>\XeTeXisdefaultselector</code>	833	<code>\XeTeXvariationmin</code>	855
<code>\XeTeXisexclusivefeature</code>	834	<code>\XeTeXvariationname</code>	856
<code>\XeTeXlastfontchar</code>	835	<code>\XeTeXversion</code>	858
<code>\XeTeXlinebreaklocale</code>	837	<code>\xkanjiskip</code>	1158
<code>\XeTeXlinebreakpenalty</code>	838	<code>\xleaders</code>	606
<code>\XeTeXlinebreakskip</code>	836	<code>\xspaceskip</code>	607
<code>\XeTeXmathaccent</code>	1287	<code>\xspcode</code>	1159
<code>\XeTeXmathchar</code>	1288		
<code>\XeTeXmathchardef</code>	1289		
<code>\XeTeXmathcharnum</code>	1290		
<code>\XeTeXmathcharnumdef</code>	1291		