

The L^AT_EX3 Sources

The L^AT_EX3 Project*

March 7, 2017

Abstract

This is the reference documentation for the `expl3` programming environment. The `expl3` modules set up an experimental naming scheme for L^AT_EX commands, which allow the L^AT_EX programmer to systematically name functions and variables, and specify the argument types of functions.

The T_EX and ϵ -T_EX primitives are all given a new name according to these conventions. However, in the main direct use of the primitives is not required or encouraged: the `expl3` modules define an independent low-level L^AT_EX3 programming language.

At present, the `expl3` modules are designed to be loaded on top of L^AT_EX 2 ϵ . In time, a L^AT_EX3 format will be produced based on this code. This allows the code to be used in L^AT_EX 2 ϵ packages *now* while a stand-alone L^AT_EX3 is developed.

While `expl3` is still experimental, the bundle is now regarded as broadly stable. The syntax conventions and functions provided are now ready for wider use. There may still be changes to some functions, but these will be minor when compared to the scope of `expl3`.

New modules will be added to the distributed version of `expl3` as they reach maturity.

*E-mail: latex-team@latex-project.org

Contents

| | | |
|------------|---|-----------|
| I | Introduction to <code>expl3</code> and this document | 1 |
| 1 | Naming functions and variables | 1 |
| 1.1 | Terminological inexactitude | 3 |
| 2 | Documentation conventions | 3 |
| 3 | Formal language conventions which apply generally | 5 |
| 4 | <code>TeX</code> concepts not supported by <code>LaTeX3</code> | 5 |
| II | The <code>l3bootstrap</code> package: Bootstrap code | 6 |
| 1 | Using the <code>LaTeX3</code> modules | 6 |
| 1.1 | Internal functions and variables | 7 |
| III | The <code>l3names</code> package: Namespace for primitives | 8 |
| 1 | Setting up the <code>LaTeX3</code> programming language | 8 |
| IV | The <code>l3basics</code> package: Basic definitions | 9 |
| 1 | No operation functions | 9 |
| 2 | Grouping material | 9 |
| 3 | Control sequences and functions | 10 |
| 3.1 | Defining functions | 10 |
| 3.2 | Defining new functions using parameter text | 11 |
| 3.3 | Defining new functions using the signature | 12 |
| 3.4 | Copying control sequences | 15 |
| 3.5 | Deleting control sequences | 15 |
| 3.6 | Showing control sequences | 15 |
| 3.7 | Converting to and from control sequences | 16 |
| 4 | Using or removing tokens and arguments | 17 |
| 4.1 | Selecting tokens from delimited arguments | 19 |
| 5 | Predicates and conditionals | 19 |
| 5.1 | Tests on control sequences | 20 |
| 5.2 | Primitive conditionals | 21 |
| 6 | Internal kernel functions | 22 |
| V | The <code>l3expan</code> package: Argument expansion | 24 |

| | | |
|------------|---|-----------|
| 1 | Defining new variants | 24 |
| 2 | Methods for defining variants | 25 |
| 3 | Introducing the variants | 25 |
| 4 | Manipulating the first argument | 26 |
| 5 | Manipulating two arguments | 28 |
| 6 | Manipulating three arguments | 28 |
| 7 | Unbraced expansion | 29 |
| 8 | Preventing expansion | 30 |
| 9 | Controlled expansion | 31 |
| 10 | Internal functions and variables | 32 |
| VI | The <code>l3tl</code> package: Token lists | 34 |
| 1 | Creating and initialising token list variables | 34 |
| 2 | Adding data to token list variables | 35 |
| 3 | Modifying token list variables | 36 |
| 4 | Reassigning token list category codes | 36 |
| 5 | Token list conditionals | 37 |
| 6 | Mapping to token lists | 39 |
| 7 | Using token lists | 41 |
| 8 | Working with the content of token lists | 41 |
| 9 | The first token from a token list | 43 |
| 10 | Using a single item | 45 |
| 11 | Viewing token lists | 45 |
| 12 | Constant token lists | 46 |
| 13 | Scratch token lists | 46 |
| 14 | Internal functions | 46 |
| VII | The <code>l3str</code> package: Strings | 47 |

| | | |
|-------------|---|-----------|
| 1 | Building strings | 47 |
| 2 | Adding data to string variables | 48 |
| 2.1 | String conditionals | 48 |
| 3 | Working with the content of strings | 50 |
| 4 | String manipulation | 53 |
| 5 | Viewing strings | 54 |
| 6 | Constant token lists | 55 |
| 7 | Scratch strings | 55 |
| 7.1 | Internal string functions | 55 |
| VIII | The l3seq package: Sequences and stacks | 57 |
| 1 | Creating and initialising sequences | 57 |
| 2 | Appending data to sequences | 58 |
| 3 | Recovering items from sequences | 58 |
| 4 | Recovering values from sequences with branching | 59 |
| 5 | Modifying sequences | 60 |
| 6 | Sequence conditionals | 61 |
| 7 | Mapping to sequences | 61 |
| 8 | Using the content of sequences directly | 63 |
| 9 | Sequences as stacks | 64 |
| 10 | Sequences as sets | 65 |
| 11 | Constant and scratch sequences | 66 |
| 12 | Viewing sequences | 67 |
| 13 | Internal sequence functions | 67 |
| IX | The l3int package: Integers | 68 |
| 1 | Integer expressions | 68 |
| 2 | Creating and initialising integers | 69 |
| 3 | Setting and incrementing integers | 70 |

| | | |
|------------|---|-----------|
| 4 | Using integers | 70 |
| 5 | Integer expression conditionals | 71 |
| 6 | Integer expression loops | 72 |
| 7 | Integer step functions | 74 |
| 8 | Formatting integers | 74 |
| 9 | Converting from other formats to integers | 76 |
| 10 | Viewing integers | 77 |
| 11 | Constant integers | 78 |
| 12 | Scratch integers | 78 |
| 13 | Primitive conditionals | 79 |
| 14 | Internal functions | 79 |
| X | The <code>l3flag</code> package: expandable flags | 81 |
| 1 | Setting up flags | 81 |
| 2 | Expandable flag commands | 82 |
| XI | The <code>l3quark</code> package: Quarks | 83 |
| 1 | Introduction to quarks and scan marks | 83 |
| 1.1 | Quarks | 83 |
| 2 | Defining quarks | 83 |
| 3 | Quark tests | 84 |
| 4 | Recursion | 84 |
| 5 | An example of recursion with quarks | 85 |
| 6 | Internal quark functions | 86 |
| 7 | Scan marks | 86 |
| XII | The <code>l3prg</code> package: Control structures | 88 |
| 1 | Defining a set of conditional functions | 88 |
| 2 | The boolean data type | 90 |

| | | |
|--|---|---------|
| 3 | Boolean expressions | 92 |
| 4 | Logical loops | 92 |
| 5 | Producing multiple copies | 93 |
| 6 | Detecting \TeX 's mode | 94 |
| 7 | Primitive conditionals | 94 |
| 8 | Internal programming functions | 94 |
| XIII The l3clist package: Comma separated lists | | 96 |
| 1 | Creating and initialising comma lists | 96 |
| 2 | Adding data to comma lists | 97 |
| 3 | Modifying comma lists | 98 |
| 4 | Comma list conditionals | 99 |
| 5 | Mapping to comma lists | 99 |
| 6 | Using the content of comma lists directly | 101 |
| 7 | Comma lists as stacks | 102 |
| 8 | Using a single item | 103 |
| 9 | Viewing comma lists | 103 |
| 10 | Constant and scratch comma lists | 104 |
| XIV The l3token package: Token manipulation | | 105 |
| 1 | Creating character tokens | 105 |
| 2 | Manipulating and interrogating character tokens | 106 |
| 3 | Generic tokens | 109 |
| 4 | Converting tokens | 110 |
| 5 | Token conditionals | 110 |
| 6 | Peeking ahead at the next token | 113 |
| 7 | Decomposing a macro definition | 116 |
| 8 | Description of all possible tokens | 117 |

| | | |
|-------------|---|------------|
| 9 | Internal functions | 119 |
| XV | The l3prop package: Property lists | 120 |
| 1 | Creating and initialising property lists | 120 |
| 2 | Adding entries to property lists | 121 |
| 3 | Recovering values from property lists | 121 |
| 4 | Modifying property lists | 122 |
| 5 | Property list conditionals | 122 |
| 6 | Recovering values from property lists with branching | 123 |
| 7 | Mapping to property lists | 123 |
| 8 | Viewing property lists | 124 |
| 9 | Scratch property lists | 125 |
| 10 | Constants | 125 |
| 11 | Internal property list functions | 125 |
| XVI | The l3msg package: Messages | 126 |
| 1 | Creating new messages | 126 |
| 2 | Contextual information for messages | 127 |
| 3 | Issuing messages | 128 |
| 4 | Redirecting messages | 130 |
| 5 | Low-level message functions | 131 |
| 6 | Kernel-specific functions | 132 |
| 7 | Expandable errors | 134 |
| 8 | Internal l3msg functions | 134 |
| XVII | The l3file package: File and I/O operations | 136 |
| 1 | File operation functions | 136 |
| 1.1 | Input–output stream management | 137 |
| 1.2 | Reading from files | 138 |

| | | |
|--------------|---|------------|
| 2 | Writing to files | 139 |
| 2.1 | Wrapping lines in output | 141 |
| 2.2 | Constant input-output streams | 142 |
| 2.3 | Primitive conditionals | 142 |
| 2.4 | Internal file functions and variables | 142 |
| 2.5 | Internal input-output functions | 142 |
| | | |
| XVIII | The l3skip package: Dimensions and skips | 144 |
| 1 | Creating and initialising dim variables | 144 |
| 2 | Setting dim variables | 145 |
| 3 | Utilities for dimension calculations | 145 |
| 4 | Dimension expression conditionals | 146 |
| 5 | Dimension expression loops | 148 |
| 6 | Using dim expressions and variables | 149 |
| 7 | Viewing dim variables | 151 |
| 8 | Constant dimensions | 151 |
| 9 | Scratch dimensions | 151 |
| 10 | Creating and initialising skip variables | 152 |
| 11 | Setting skip variables | 152 |
| 12 | Skip expression conditionals | 153 |
| 13 | Using skip expressions and variables | 153 |
| 14 | Viewing skip variables | 153 |
| 15 | Constant skips | 154 |
| 16 | Scratch skips | 154 |
| 17 | Inserting skips into the output | 154 |
| 18 | Creating and initialising muskip variables | 155 |
| 19 | Setting muskip variables | 155 |
| 20 | Using muskip expressions and variables | 156 |
| 21 | Viewing muskip variables | 156 |
| 22 | Constant muskips | 157 |

| | | |
|---|--|------------|
| 23 | Scratch muskips | 157 |
| 24 | Primitive conditional | 157 |
| 25 | Internal functions | 158 |
| XIX The l3keys package: Key–value interfaces | | 159 |
| 1 | Creating keys | 160 |
| 2 | Sub-dividing keys | 164 |
| 3 | Choice and multiple choice keys | 164 |
| 4 | Setting keys | 167 |
| 5 | Handling of unknown keys | 167 |
| 6 | Selective key setting | 168 |
| 7 | Utility functions for keys | 169 |
| 8 | Low-level interface for parsing key–val lists | 170 |
| XX The l3fp package: floating points | | 172 |
| 1 | Creating and initialising floating point variables | 173 |
| 2 | Setting floating point variables | 173 |
| 3 | Using floating point numbers | 174 |
| 4 | Floating point conditionals | 175 |
| 5 | Floating point expression loops | 177 |
| 6 | Some useful constants, and scratch variables | 178 |
| 7 | Floating point exceptions | 179 |
| 8 | Viewing floating points | 180 |
| 9 | Floating point expressions | 180 |
| 9.1 | Input of floating point numbers | 180 |
| 9.2 | Precedence of operators | 181 |
| 9.3 | Operations | 182 |
| 10 | Disclaimer and roadmap | 188 |
| XXI The l3sort package: Sorting functions | | 191 |

| | | |
|--------------|--|------------|
| 1 | Controlling sorting | 191 |
| XXII | The l3box package: Boxes | 192 |
| 1 | Creating and initialising boxes | 192 |
| 2 | Using boxes | 193 |
| 3 | Measuring and setting box dimensions | 193 |
| 4 | Box conditionals | 194 |
| 5 | The last box inserted | 194 |
| 6 | Constant boxes | 195 |
| 7 | Scratch boxes | 195 |
| 8 | Viewing box contents | 195 |
| 9 | Horizontal mode boxes | 195 |
| 10 | Vertical mode boxes | 197 |
| 11 | Primitive box conditionals | 198 |
| XXIII | The l3coffins package: Coffin code layer | 200 |
| 1 | Creating and initialising coffins | 200 |
| 2 | Setting coffin content and poles | 200 |
| 3 | Joining and using coffins | 201 |
| 4 | Measuring coffins | 202 |
| 5 | Coffin diagnostics | 202 |
| 5.1 | Constants and variables | 203 |
| XXIV | The l3color package: Color support | 204 |
| 1 | Color in boxes | 204 |
| XXV | The l3sys package: System/runtime functions | 205 |
| 1 | The name of the job | 205 |
| 2 | Date and time | 205 |

| | | |
|---------------|---|------------|
| 3 | Engine | 205 |
| 4 | Output format | 206 |
| XXVI | The <code>l3deprecation</code> package: Deprecation errors | 207 |
| 1 | <code>l3deprecation</code> documentation | 207 |
| XXVII | The <code>l3candidates</code> package: Experimental additions to <code>l3kernel</code> | 208 |
| 1 | Important notice | 208 |
| 2 | Additions to <code>l3box</code> | 208 |
| 2.1 | Affine transformations | 208 |
| 2.2 | Viewing part of a box | 210 |
| 3 | Additions to <code>l3clist</code> | 211 |
| 4 | Additions to <code>l3coffins</code> | 211 |
| 5 | Additions to <code>l3file</code> | 211 |
| 6 | Additions to <code>l3int</code> | 213 |
| 7 | Additions to <code>l3msg</code> | 213 |
| 8 | Additions to <code>l3prg</code> | 213 |
| 9 | Additions to <code>l3prop</code> | 215 |
| 10 | Additions to <code>l3seq</code> | 215 |
| 11 | Additions to <code>l3skip</code> | 216 |
| 12 | Additions to <code>l3tl</code> | 216 |
| 13 | Additions to <code>l3tokens</code> | 221 |
| XXVIII | The <code>l3luatex</code> package: LuaTeX-specific functions | 222 |
| 1 | Breaking out to Lua | 222 |
| 1.1 | TeX code interfaces | 222 |
| 1.2 | Lua interfaces | 223 |
| XXIX | The <code>l3drivers</code> package: Drivers | 224 |
| 1 | Box clipping | 224 |

| | | |
|------------|--|------------|
| 2 | Box rotation and scaling | 224 |
| 3 | Color support | 225 |
| 4 | Drawing | 225 |
| 4.1 | Path construction | 226 |
| 4.2 | Stroking and filling | 226 |
| 4.3 | Stroke options | 227 |
| 4.4 | Color | 228 |
| 4.5 | Inserting \TeX material | 229 |
| 4.6 | Coordinate system transformations | 229 |
| XXX | Implementation | 229 |
| 1 | \l3bootstrap implementation | 229 |
| 1.1 | Format-specific code | 229 |
| 1.2 | The \pdfstrcmp primitive in \XeTeX | 230 |
| 1.3 | Loading support Lua code | 230 |
| 1.4 | Engine requirements | 231 |
| 1.5 | Extending allocators | 233 |
| 1.6 | Character data | 233 |
| 1.7 | The \LaTeX3 code environment | 235 |
| 2 | \l3names implementation | 236 |
| 3 | \l3basics implementation | 257 |
| 3.1 | Renaming some \TeX primitives (again) | 257 |
| 3.2 | Defining some constants | 260 |
| 3.3 | Defining functions | 260 |
| 3.4 | Selecting tokens | 261 |
| 3.5 | Gobbling tokens from input | 262 |
| 3.6 | Conditional processing and definitions | 262 |
| 3.7 | Dissecting a control sequence | 268 |
| 3.8 | Exist or free | 270 |
| 3.9 | Defining and checking (new) functions | 271 |
| 3.10 | More new definitions | 274 |
| 3.11 | Copying definitions | 276 |
| 3.12 | Undefining functions | 276 |
| 3.13 | Generating parameter text from argument count | 276 |
| 3.14 | Defining functions from a given number of arguments | 277 |
| 3.15 | Using the signature to define functions | 278 |
| 3.16 | Checking control sequence equality | 280 |
| 3.17 | Diagnostic functions | 281 |
| 3.18 | Doing nothing functions | 282 |
| 3.19 | Breaking out of mapping functions | 282 |

| | | |
|----------|---|------------|
| 4 | l3expan implementation | 283 |
| 4.1 | General expansion | 283 |
| 4.2 | Hand-tuned definitions | 286 |
| 4.3 | Definitions with the automated technique | 288 |
| 4.4 | Last-unbraced versions | 289 |
| 4.5 | Preventing expansion | 291 |
| 4.6 | Controlled expansion | 291 |
| 4.7 | Defining function variants | 292 |
| 5 | l3tl implementation | 298 |
| 5.1 | Functions | 298 |
| 5.2 | Constant token lists | 300 |
| 5.3 | Adding to token list variables | 300 |
| 5.4 | Reassigning token list category codes | 303 |
| 5.5 | Modifying token list variables | 306 |
| 5.6 | Token list conditionals | 310 |
| 5.7 | Mapping to token lists | 314 |
| 5.8 | Using token lists | 315 |
| 5.9 | Working with the contents of token lists | 316 |
| 5.10 | Token by token changes | 318 |
| 5.11 | The first token from a token list | 320 |
| 5.12 | Using a single item | 325 |
| 5.13 | Viewing token lists | 325 |
| 5.14 | Scratch token lists | 326 |
| 5.15 | Deprecated functions | 326 |
| 6 | l3str implementation | 327 |
| 6.1 | Creating and setting string variables | 327 |
| 6.2 | String comparisons | 328 |
| 6.3 | Accessing specific characters in a string | 331 |
| 6.4 | Counting characters | 335 |
| 6.5 | The first character in a string | 337 |
| 6.6 | String manipulation | 338 |
| 6.7 | Viewing strings | 340 |
| 6.8 | Unicode data for case changing | 340 |
| 7 | l3seq implementation | 343 |
| 7.1 | Allocation and initialisation | 344 |
| 7.2 | Appending data to either end | 347 |
| 7.3 | Modifying sequences | 348 |
| 7.4 | Sequence conditionals | 350 |
| 7.5 | Recovering data from sequences | 351 |
| 7.6 | Mapping to sequences | 355 |
| 7.7 | Using sequences | 357 |
| 7.8 | Sequence stacks | 357 |
| 7.9 | Viewing sequences | 358 |
| 7.10 | Scratch sequences | 359 |

| | | |
|-----------|---|------------|
| 8 | l3int implementation | 359 |
| 8.1 | Integer expressions | 360 |
| 8.2 | Creating and initialising integers | 361 |
| 8.3 | Setting and incrementing integers | 363 |
| 8.4 | Using integers | 364 |
| 8.5 | Integer expression conditionals | 364 |
| 8.6 | Integer expression loops | 368 |
| 8.7 | Integer step functions | 369 |
| 8.8 | Formatting integers | 370 |
| 8.9 | Converting from other formats to integers | 376 |
| 8.10 | Viewing integer | 379 |
| 8.11 | Constant integers | 379 |
| 8.12 | Scratch integers | 381 |
| 8.13 | Deprecated | 381 |
| 9 | l3flag implementation | 381 |
| 9.1 | Non-expandable flag commands | 381 |
| 9.2 | Expandable flag commands | 382 |
| 9.3 | Option check-declarations | 383 |
| 10 | l3quark implementation | 384 |
| 10.1 | Quarks | 384 |
| 10.2 | Scan marks | 387 |
| 11 | l3prg implementation | 388 |
| 11.1 | Primitive conditionals | 388 |
| 11.2 | Defining a set of conditional functions | 388 |
| 11.3 | The boolean data type | 388 |
| 11.4 | Boolean expressions | 391 |
| 11.5 | Logical loops | 396 |
| 11.6 | Producing multiple copies | 397 |
| 11.7 | Detecting T _E X's mode | 398 |
| 11.8 | Internal programming functions | 399 |
| 12 | l3clist implementation | 400 |
| 12.1 | Allocation and initialisation | 400 |
| 12.2 | Removing spaces around items | 402 |
| 12.3 | Adding data to comma lists | 403 |
| 12.4 | Comma lists as stacks | 404 |
| 12.5 | Modifying comma lists | 406 |
| 12.6 | Comma list conditionals | 408 |
| 12.7 | Mapping to comma lists | 409 |
| 12.8 | Using comma lists | 412 |
| 12.9 | Using a single item | 413 |
| 12.10 | Viewing comma lists | 414 |
| 12.11 | Scratch comma lists | 415 |

| | | |
|-----------|--|------------|
| 13 | l3token implementation | 415 |
| 13.1 | Manipulating and interrogating character tokens | 415 |
| 13.2 | Creating character tokens | 418 |
| 13.3 | Generic tokens | 422 |
| 13.4 | Token conditionals | 423 |
| 13.5 | Peeking ahead at the next token | 430 |
| 13.6 | Decomposing a macro definition | 435 |
| 14 | l3prop implementation | 436 |
| 14.1 | Allocation and initialisation | 437 |
| 14.2 | Accessing data in property lists | 438 |
| 14.3 | Property list conditionals | 442 |
| 14.4 | Recovering values from property lists with branching | 443 |
| 14.5 | Mapping to property lists | 444 |
| 14.6 | Viewing property lists | 445 |
| 15 | l3msg implementation | 445 |
| 15.1 | Creating messages | 446 |
| 15.2 | Messages: support functions and text | 447 |
| 15.3 | Showing messages: low level mechanism | 448 |
| 15.4 | Displaying messages | 450 |
| 15.5 | Kernel-specific functions | 457 |
| 15.6 | Expandable errors | 463 |
| 15.7 | Showing variables | 464 |
| 16 | l3file implementation | 467 |
| 16.1 | File operations | 467 |
| 16.2 | Input operations | 473 |
| 16.2.1 | Variables and constants | 473 |
| 16.2.2 | Stream management | 474 |
| 16.2.3 | Reading input | 476 |
| 16.3 | Output operations | 477 |
| 16.3.1 | Variables and constants | 477 |
| 16.4 | Stream management | 478 |
| 16.4.1 | Deferred writing | 480 |
| 16.4.2 | Immediate writing | 480 |
| 16.4.3 | Special characters for writing | 481 |
| 16.4.4 | Hard-wrapping lines to a character count | 481 |
| 16.5 | Messages | 490 |
| 16.6 | Deprecated functions | 490 |

| | | |
|-----------|---|------------|
| 17 | l3skip implementation | 490 |
| 17.1 | Length primitives renamed | 491 |
| 17.2 | Creating and initialising <code>dim</code> variables | 491 |
| 17.3 | Setting <code>dim</code> variables | 492 |
| 17.4 | Utilities for dimension calculations | 492 |
| 17.5 | Dimension expression conditionals | 493 |
| 17.6 | Dimension expression loops | 495 |
| 17.7 | Using <code>dim</code> expressions and variables | 496 |
| 17.8 | Viewing <code>dim</code> variables | 498 |
| 17.9 | Constant dimensions | 498 |
| 17.10 | Scratch dimensions | 498 |
| 17.11 | Creating and initialising <code>skip</code> variables | 498 |
| 17.12 | Setting <code>skip</code> variables | 499 |
| 17.13 | <code>Skip</code> expression conditionals | 500 |
| 17.14 | Using <code>skip</code> expressions and variables | 501 |
| 17.15 | Inserting skips into the output | 501 |
| 17.16 | Viewing <code>skip</code> variables | 501 |
| 17.17 | Constant skips | 502 |
| 17.18 | Scratch skips | 502 |
| 17.19 | Creating and initialising <code>muskip</code> variables | 502 |
| 17.20 | Setting <code>muskip</code> variables | 503 |
| 17.21 | Using <code>muskip</code> expressions and variables | 504 |
| 17.22 | Viewing <code>muskip</code> variables | 504 |
| 17.23 | Constant muskips | 504 |
| 17.24 | Scratch muskips | 504 |
| 18 | l3keys Implementation | 505 |
| 18.1 | Low-level interface | 505 |
| 18.2 | Constants and variables | 508 |
| 18.3 | The key defining mechanism | 510 |
| 18.4 | Turning properties into actions | 512 |
| 18.5 | Creating key properties | 517 |
| 18.6 | Setting keys | 521 |
| 18.7 | Utilities | 526 |
| 18.8 | Messages | 528 |
| 19 | l3fp implementation | 529 |
| 20 | l3fp-aux implementation | 530 |
| 20.1 | Internal representation | 530 |
| 20.2 | Internal storage of floating points numbers | 531 |
| 20.3 | Using arguments and semicolons | 531 |
| 20.4 | Constants, and structure of floating points | 532 |
| 20.5 | Overflow, underflow, and exact zero | 534 |
| 20.6 | Expanding after a floating point number | 535 |
| 20.7 | Packing digits | 536 |
| 20.8 | Decimate (dividing by a power of 10) | 538 |
| 20.9 | Functions for use within primitive conditional branches | 540 |
| 20.10 | Integer floating points | 541 |
| 20.11 | Small integer floating points | 542 |

| | | |
|-----------|--|------------|
| 20.12 | Length of a floating point array | 543 |
| 20.13 | x-like expansion expandably | 543 |
| 20.14 | Messages | 543 |
| 21 | l3fp-traps Implementation | 544 |
| 21.1 | Flags | 544 |
| 21.2 | Traps | 544 |
| 21.3 | Errors | 548 |
| 21.4 | Messages | 548 |
| 22 | l3fp-round implementation | 549 |
| 22.1 | Rounding tools | 549 |
| 22.2 | The round function | 553 |
| 23 | l3fp-parse implementation | 556 |
| 23.1 | Work plan | 556 |
| 23.1.1 | Storing results | 557 |
| 23.1.2 | Precedence and infix operators | 558 |
| 23.1.3 | Prefix operators, parentheses, and functions | 561 |
| 23.1.4 | Numbers and reading tokens one by one | 562 |
| 23.2 | Main auxiliary functions | 564 |
| 23.3 | Helpers | 564 |
| 23.4 | Parsing one number | 565 |
| 23.4.1 | Numbers: trimming leading zeros | 571 |
| 23.4.2 | Number: small significand | 572 |
| 23.4.3 | Number: large significand | 574 |
| 23.4.4 | Number: beyond 16 digits, rounding | 576 |
| 23.4.5 | Number: finding the exponent | 578 |
| 23.5 | Constants, functions and prefix operators | 581 |
| 23.5.1 | Prefix operators | 581 |
| 23.5.2 | Constants | 584 |
| 23.5.3 | Functions | 585 |
| 23.6 | Main functions | 587 |
| 23.7 | Infix operators | 588 |
| 23.7.1 | Closing parentheses and commas | 589 |
| 23.7.2 | Usual infix operators | 590 |
| 23.7.3 | Juxtaposition | 591 |
| 23.7.4 | Multi-character cases | 592 |
| 23.7.5 | Ternary operator | 593 |
| 23.7.6 | Comparisons | 594 |
| 23.8 | Candidate: defining new l3fp functions | 596 |
| 23.9 | Messages | 597 |

| | | |
|-----------|---|------------|
| 24 | I3fp-logic Implementation | 598 |
| 24.1 | Syntax of internal functions | 598 |
| 24.2 | Existence test | 598 |
| 24.3 | Comparison | 599 |
| 24.4 | Floating point expression loops | 601 |
| 24.5 | Extrema | 603 |
| 24.6 | Boolean operations | 605 |
| 24.7 | Ternary operator | 605 |
| 25 | I3fp-basics Implementation | 607 |
| 25.1 | Common to several operations | 607 |
| 25.2 | Addition and subtraction | 608 |
| 25.2.1 | Sign, exponent, and special numbers | 608 |
| 25.2.2 | Absolute addition | 610 |
| 25.2.3 | Absolute subtraction | 613 |
| 25.3 | Multiplication | 617 |
| 25.3.1 | Signs, and special numbers | 617 |
| 25.3.2 | Absolute multiplication | 618 |
| 25.4 | Division | 620 |
| 25.4.1 | Signs, and special numbers | 620 |
| 25.4.2 | Work plan | 621 |
| 25.4.3 | Implementing the significand division | 624 |
| 25.5 | Square root | 629 |
| 25.6 | Setting the sign | 636 |
| 26 | I3fp-extended implementation | 636 |
| 26.1 | Description of fixed point numbers | 636 |
| 26.2 | Helpers for numbers with extended precision | 637 |
| 26.3 | Multiplying a fixed point number by a short one | 638 |
| 26.4 | Dividing a fixed point number by a small integer | 639 |
| 26.5 | Adding and subtracting fixed points | 640 |
| 26.6 | Multiplying fixed points | 640 |
| 26.7 | Combining product and sum of fixed points | 642 |
| 26.8 | Extended-precision floating point numbers | 644 |
| 26.9 | Dividing extended-precision numbers | 646 |
| 26.10 | Inverse square root of extended precision numbers | 649 |
| 26.11 | Converting from fixed point to floating point | 651 |
| 27 | I3fp-expo implementation | 653 |
| 27.1 | Logarithm | 653 |
| 27.1.1 | Work plan | 653 |
| 27.1.2 | Some constants | 654 |
| 27.1.3 | Sign, exponent, and special numbers | 654 |
| 27.1.4 | Absolute ln | 654 |
| 27.2 | Exponential | 662 |
| 27.2.1 | Sign, exponent, and special numbers | 662 |
| 27.3 | Power | 666 |

| | | |
|-----------|---|------------|
| 28 | l3fp-trig Implementation | 672 |
| 28.1 | Direct trigonometric functions | 672 |
| 28.1.1 | Filtering special cases | 673 |
| 28.1.2 | Distinguishing small and large arguments | 676 |
| 28.1.3 | Small arguments | 676 |
| 28.1.4 | Argument reduction in degrees | 677 |
| 28.1.5 | Argument reduction in radians | 678 |
| 28.1.6 | Computing the power series | 684 |
| 28.2 | Inverse trigonometric functions | 687 |
| 28.2.1 | Arctangent and arccotangent | 688 |
| 28.2.2 | Arcsine and arccosine | 692 |
| 28.2.3 | Arccosecant and arcsecant | 694 |
| 29 | l3fp-convert implementation | 696 |
| 29.1 | Trimming trailing zeros | 696 |
| 29.2 | Scientific notation | 696 |
| 29.3 | Decimal representation | 697 |
| 29.4 | Token list representation | 699 |
| 29.5 | Formatting | 700 |
| 29.6 | Convert to dimension or integer | 700 |
| 29.7 | Convert from a dimension | 701 |
| 29.8 | Use and eval | 701 |
| 29.9 | Convert an array of floating points to a comma list | 702 |
| 30 | l3fp-random Implementation | 703 |
| 30.1 | Engine support | 703 |
| 30.2 | Random floating point | 705 |
| 30.3 | Random integer | 705 |
| 31 | l3fp-assign implementation | 707 |
| 31.1 | Assigning values | 707 |
| 31.2 | Updating values | 708 |
| 31.3 | Showing values | 708 |
| 31.4 | Some useful constants and scratch variables | 709 |
| 32 | l3sort implementation | 709 |
| 32.1 | Variables | 709 |
| 32.2 | Finding available \toks registers | 710 |
| 32.3 | Protected user commands | 712 |
| 32.4 | Merge sort | 715 |
| 32.5 | Expandable sorting | 718 |
| 32.6 | Messages | 722 |
| 32.7 | Deprecated functions | 724 |

| | | |
|-----------|--|------------|
| 33 | l3box implementation | 724 |
| 33.1 | Creating and initialising boxes | 724 |
| 33.2 | Measuring and setting box dimensions | 725 |
| 33.3 | Using boxes | 726 |
| 33.4 | Box conditionals | 726 |
| 33.5 | The last box inserted | 727 |
| 33.6 | Constant boxes | 727 |
| 33.7 | Scratch boxes | 727 |
| 33.8 | Viewing box contents | 727 |
| 33.9 | Horizontal mode boxes | 728 |
| 33.10 | Vertical mode boxes | 730 |
| 34 | l3coffins Implementation | 731 |
| 34.1 | Coffins: data structures and general variables | 731 |
| 34.2 | Basic coffin functions | 733 |
| 34.3 | Measuring coffins | 737 |
| 34.4 | Coffins: handle and pole management | 737 |
| 34.5 | Coffins: calculation of pole intersections | 740 |
| 34.6 | Aligning and typesetting of coffins | 743 |
| 34.7 | Coffin diagnostics | 747 |
| 34.8 | Messages | 752 |
| 35 | l3color Implementation | 753 |
| 36 | l3sys implementation | 754 |
| 36.1 | The name of the job | 754 |
| 36.2 | Time and date | 754 |
| 36.3 | Detecting the engine | 755 |
| 36.4 | Detecting the output | 756 |
| 37 | l3deprecation implementation | 756 |
| 38 | l3candidates Implementation | 758 |
| 38.1 | Additions to l3box | 758 |
| 38.2 | Affine transformations | 758 |
| 38.3 | Viewing part of a box | 766 |
| 38.4 | Additions to l3clist | 768 |
| 38.5 | Additions to l3coffins | 768 |
| 38.6 | Rotating coffins | 768 |
| 38.7 | Resizing coffins | 773 |
| 38.8 | Additions to l3file | 775 |
| 38.9 | Additions to l3int | 777 |
| 38.10 | Additions to l3msg | 778 |
| 38.11 | Additions to l3prg | 779 |
| 38.12 | Additions to l3prop | 780 |
| 38.13 | Additions to l3seq | 781 |
| 38.14 | Additions to l3skip | 783 |
| 38.15 | Additions to l3tl | 783 |
| 38.15.1 | Unicode case changing | 786 |
| 38.15.2 | Other additions to l3tl | 808 |

| | | |
|-----------|--|------------|
| 38.16 | Additions to l3tokens | 810 |
| 39 | l3luatex implementation | 811 |
| 39.1 | Breaking out to Lua | 811 |
| 39.2 | Messages | 812 |
| 39.3 | Lua functions for internal use | 812 |
| 39.4 | Generic Lua and font support | 813 |
| 40 | l3drivers Implementation | 813 |
| 40.1 | pdfmode driver | 814 |
| 40.1.1 | Basics | 814 |
| 40.1.2 | Color | 815 |
| 40.2 | dvipdfmx driver | 815 |
| 40.2.1 | Basics | 816 |
| 40.2.2 | Color | 816 |
| 40.3 | xdvipdfmx driver | 817 |
| 40.3.1 | Color | 817 |
| 40.4 | Common code for PDF production | 817 |
| 40.4.1 | Box operations | 817 |
| 40.5 | Drawing | 819 |
| 40.6 | dvips driver | 823 |
| 40.6.1 | Basics | 823 |
| 40.7 | Driver-specific auxiliaries | 824 |
| 40.7.1 | Box operations | 824 |
| 40.7.2 | Color | 825 |
| 40.8 | Drawing | 826 |
| 40.9 | dvisvgm driver | 832 |
| 40.9.1 | Basics | 832 |
| 40.10 | Driver-specific auxiliaries | 833 |
| 40.10.1 | Box operations | 833 |
| 40.10.2 | Color | 835 |
| 40.11 | Drawing | 835 |
| | Index | 843 |

Part I

Introduction to expl3 and this document

This document is intended to act as a comprehensive reference manual for the expl3 language. A general guide to the L^AT_EX3 programming language is found in [expl3.pdf](#).

1 Naming functions and variables

L^AT_EX3 does not use `@` as a “letter” for defining internal macros. Instead, the symbols `_` and `:` are used in internal macro names to provide structure. The name of each *function* is divided into logical units using `_`, while `:` separates the *name* of the function from the *argument specifier* (“arg-spec”). This describes the arguments expected by the function. In most cases, each argument is represented by a single letter. The complete list of arg-spec letters for a function is referred to as the *signature* of the function.

Each function name starts with the *module* to which it belongs. Thus apart from a small number of very basic functions, all expl3 function names contain at least one underscore to divide the module name from the descriptive name of the function. For example, all functions concerned with comma lists are in module `clist` and begin `\clist_`.

Every function must include an argument specifier. For functions which take no arguments, this will be blank and the function name will end `:`. Most functions take one or more arguments, and use the following argument specifiers:

- D** The **D** specifier means *do not use*. All of the T_EX primitives are initially `\let` to a **D** name, and some are then given a second name. Only the kernel team should use anything with a **D** specifier!
- N and n** These mean *no manipulation*, of a single token for **N** and of a set of tokens given in braces for **n**. Both pass the argument through exactly as given. Usually, if you use a single token for an **n** argument, all will be well.
- c** This means *cname*, and indicates that the argument will be turned into a *cname* before being used. So `\foo:c {ArgumentOne}` will act in the same way as `\foo:N \ArgumentOne`.
- V and v** These mean *value of variable*. The **V** and **v** specifiers are used to get the content of a variable without needing to worry about the underlying T_EX structure containing the data. A **V** argument will be a single token (similar to **N**), for example `\foo:V \MyVariable`; on the other hand, using **v** a *cname* is constructed first, and then the value is recovered, for example `\foo:v {MyVariable}`.
- o** This means *expansion once*. In general, the **V** and **v** specifiers are favoured over **o** for recovering stored information. However, **o** is useful for correctly processing information with delimited arguments.
- x** The **x** specifier stands for *exhaustive expansion*: every token in the argument is fully expanded until only unexpandable ones remain. The T_EX `\edef` primitive carries out this type of expansion. Functions which feature an **x**-type argument are in general *not* expandable, unless specifically noted.

- f** The **f** specifier stands for *full expansion*, and in contrast to **x** stops at the first non-expandable item (reading the argument from left to right) without trying to expand it. For example, when setting a token list variable (a macro used for storage), the sequence

```
\tl_set:Nn \l_my_a_tl { A }
\tl_set:Nn \l_my_b_tl { B }
\tl_set:Nf \l_my_a_tl { \l_my_a_tl \l_my_b_tl }
```

will leave `\l_my_a_tl` with the content `A\l_my_b_tl`, as `A` cannot be expanded and so terminates expansion before `\l_my_b_tl` is considered.

- T and F** For logic tests, there are the branch specifiers **T** (*true*) and **F** (*false*). Both specifiers treat the input in the same way as **n** (no change), but make the logic much easier to see.
- p** The letter **p** indicates `TeX parameters`. Normally this will be used for delimited functions as `expl3` provides better methods for creating simple sequential arguments.
- w** Finally, there is the **w** specifier for *weird* arguments. This covers everything else, but mainly applies to delimited values (where the argument must be terminated by some arbitrary string).

Notice that the argument specifier describes how the argument is processed prior to being passed to the underlying function. For example, `\foo:c` will take its argument, convert it to a control sequence and pass it to `\foo:N`.

Variables are named in a similar manner to functions, but begin with a single letter to define the type of variable:

- c** Constant: global parameters whose value should not be changed.
- g** Parameters whose value should only be set globally.
- l** Parameters whose value should only be set locally.

Each variable name is then build up in a similar way to that of a function, typically starting with the module¹ name and then a descriptive part. Variables end with a short identifier to show the variable type:

bool Either true or false.

box Box register.

clist Comma separated list.

coffin a “box with handles” — a higher-level data type for carrying out **box** alignment operations.

dim “Rigid” lengths.

fp floating-point values;

¹The module names are not used in case of generic scratch registers defined in the data type modules, e.g., the `int` module contains some scratch variables called `\l_tmpa_int`, `\l_tmpb_int`, and so on. In such a case adding the module name up front to denote the module and in the back to indicate the type, as in `\l_int_tmpa_int` would be very unreadable.

int Integer-valued count register.

prop Property list.

seq “Sequence”: a data-type used to implement lists (with access at both ends) and stacks.

skip “Rubber” lengths.

stream An input or output stream (for reading from or writing to, respectively).

tl Token list variables: placeholder for a token list.

1.1 Terminological inexactitude

A word of warning. In this document, and others referring to the `expl3` programming modules, we often refer to “variables” and “functions” as if they were actual constructs from a real programming language. In truth, `TeX` is a macro processor, and functions are simply macros that may or may not take arguments and expand to their replacement text. Many of the common variables are *also* macros, and if placed into the input stream will simply expand to their definition as well — a “function” with no arguments and a “token list variable” are in truth one and the same. On the other hand, some “variables” are actually registers that must be initialised and their values set and retrieved with specific functions.

The conventions of the `expl3` code are designed to clearly separate the ideas of “macros that contain data” and “macros that contain code”, and a consistent wrapper is applied to all forms of “data” whether they be macros or actually registers. This means that sometimes we will use phrases like “the function returns a value”, when actually we just mean “the macro expands to something”. Similarly, the term “execute” might be used in place of “expand” or it might refer to the more specific case of “processing in `TeX`’s stomach” (if you are familiar with the `TeXbook` parlance).

If in doubt, please ask; chances are we’ve been hasty in writing certain definitions and need to be told to tighten up our terminology.

2 Documentation conventions

This document is typeset with the experimental `l3doc` class; several conventions are used to help describe the features of the code. A number of conventions are used here to make the documentation clearer.

Each group of related functions is given in a box. For a function with a “user” name, this might read:

```
\ExplSyntaxOn
\ExplSyntaxOff
```

```
\ExplSyntaxOn ... \ExplSyntaxOff
```

The textual description of how the function works would appear here. The syntax of the function is shown in mono-spaced text to the right of the box. In this example, the function takes no arguments and so the name of the function is simply reprinted.

For programming functions, which use `_` and `:` in their name there are a few additional conventions: If two related functions are given with identical names but different argument specifiers, these are termed *variants* of each other, and the latter functions are printed in grey to show this more clearly. They will carry out the same function but will take different types of argument:

| | |
|-------------------------|--|
| <code>\seq_new:N</code> | <code>\seq_new:N</code> $\langle sequence \rangle$ |
| <code>\seq_new:c</code> | |

When a number of variants are described, the arguments are usually illustrated only for the base function. Here, $\langle sequence \rangle$ indicates that `\seq_new:N` expects the name of a sequence. From the argument specifier, `\seq_new:c` also expects a sequence name, but as a name rather than as a control sequence. Each argument given in the illustration should be described in the following text.

Fully expandable functions Some functions are fully expandable, which allows them to be used within an **x**-type argument (in plain \TeX terms, inside an `\edef`), as well as within an **f**-type argument. These fully expandable functions are indicated in the documentation by a star:

| | |
|-----------------------------|--|
| <code>\cs_to_str:N</code> ☆ | <code>\cs_to_str:N</code> $\langle cs \rangle$ |
|-----------------------------|--|

As with other functions, some text should follow which explains how the function works. Usually, only the star will indicate that the function is expandable. In this case, the function expects a $\langle cs \rangle$, shorthand for a $\langle control\ sequence \rangle$.

Restricted expandable functions A few functions are fully expandable but cannot be fully expanded within an **f**-type argument. In this case a hollow star is used to indicate this:

| | |
|-------------------------------------|--|
| <code>\seq_map_function:NN</code> ☆ | <code>\seq_map_function:NN</code> $\langle seq \rangle$ $\langle function \rangle$ |
|-------------------------------------|--|

Conditional functions Conditional (**if**) functions are normally defined in three variants, with **T**, **F** and **TF** argument specifiers. This allows them to be used for different “true”/“false” branches, depending on which outcome the conditional is being used to test. To indicate this without repetition, this information is given in a shortened form:

| | |
|--|---|
| <code>\sys_if_engine_xetex:TF</code> ☆ | <code>\sys_if_engine_xetex:TF</code> $\{\langle true\ code \rangle\}$ $\{\langle false\ code \rangle\}$ |
|--|---|

The underlining and italic of **TF** indicates that `\xetex_if_engine:T`, `\xetex_if_engine:F` and `\xetex_if_engine:TF` are all available. Usually, the illustration will use the **TF** variant, and so both $\langle true\ code \rangle$ and $\langle false\ code \rangle$ will be shown. The two variant forms **T** and **F** take only $\langle true\ code \rangle$ and $\langle false\ code \rangle$, respectively. Here, the star also shows that this function is expandable. With some minor exceptions, *all* conditional functions in the `expl3` modules should be defined in this way.

Variables, constants and so on are described in a similar manner:

| | |
|-------------------------|--|
| <code>\l_tmpa_tl</code> | |
|-------------------------|--|

A short piece of text will describe the variable: there is no syntax illustration in this case.

In some cases, the function is similar to one in $\text{\LaTeX 2}_{\epsilon}$ or plain \TeX . In these cases, the text will include an extra “ **\TeX hackers note**” section:

| | |
|--------------------------------|--|
| <code>\token_to_str:N</code> ☆ | <code>\token_to_str:N</code> $\langle token \rangle$ |
|--------------------------------|--|

The normal description text.

\TeX hackers note: Detail for the experienced \TeX or $\text{\LaTeX 2}_{\epsilon}$ programmer. In this case, it would point out that this function is the \TeX primitive `\string`.

Changes to behaviour When new functions are added to `expl3`, the date of first inclusion is given in the documentation. Where the documented behaviour of a function changes after it is first introduced, the date of the update will also be given. This means that the programmer can be sure that any release of `expl3` after the date given will contain the function of interest with expected behaviour as described. Note that changes to code internals, including bug fixes, are not recorded in this way *unless* they impact on the expected behaviour.

3 Formal language conventions which apply generally

As this is a formal reference guide for $\text{\LaTeX}3$ programming, the descriptions of functions are intended to be reasonably “complete”. However, there is also a need to avoid repetition. Formal ideas which apply to general classes of function are therefore summarised here.

For tests which have a `TF` argument specification, the test is evaluated to give a logically `TRUE` or `FALSE` result. Depending on this result, either the $\langle true\ code \rangle$ or the $\langle false\ code \rangle$ will be left in the input stream. In the case where the test is expandable, and a predicate (`_p`) variant is available, the logical value determined by the test is left in the input stream: this will typically be part of a larger logical construct.

4 \TeX concepts not supported by $\text{\LaTeX}3$

The \TeX concept of an “`\outer`” macro is *not supported* at all by $\text{\LaTeX}3$. As such, the functions provided here may break when used on top of $\text{\LaTeX}2_\epsilon$ if `\outer` tokens are used in the arguments.

Part II

The l3bootstrap package

Bootstrap code

1 Using the L^AT_EX3 modules

The modules documented in `source3` are designed to be used on top of L^AT_EX 2_ε and are loaded all as one with the usual `\usepackage{expl3}` or `\RequirePackage{expl3}` instructions. These modules will also form the basis of the L^AT_EX3 format, but work in this area is incomplete and not included in this documentation at present.

As the modules use a coding syntax different from standard L^AT_EX 2_ε it provides a few functions for setting it up.

`\ExplSyntaxOn`
`\ExplSyntaxOff`
 Updated: 2011-08-13

`\ExplSyntaxOn` *<code>* `\ExplSyntaxOff`

The `\ExplSyntaxOn` function switches to a category code régime in which spaces are ignored and in which the colon (:) and underscore (_) are treated as “letters”, thus allowing access to the names of code functions and variables. Within this environment, ~ is used to input a space. The `\ExplSyntaxOff` reverts to the document category code régime.

`\ProvidesExplPackage`
`\ProvidesExplClass`
`\ProvidesExplFile`

`\RequirePackage{expl3}`
`\ProvidesExplPackage` *<package>* *<date>* *<version>* *<description>*

These functions act broadly in the same way as the corresponding L^AT_EX 2_ε kernel functions `\ProvidesPackage`, `\ProvidesClass` and `\ProvidesFile`. However, they also implicitly switch `\ExplSyntaxOn` for the remainder of the code with the file. At the end of the file, `\ExplSyntaxOff` will be called to reverse this. (This is the same concept as L^AT_EX 2_ε provides in turning on `\makeatletter` within package and class code.) The *<date>* should be given in the format *<year>/<month>/<day>*.

`\GetIdInfo`
 Updated: 2012-06-04

`\RequirePackage{l3bootstrap}`
`\GetIdInfo $Id:` *<SVN info field>* `$` *<description>*

Extracts all information from a SVN field. Spaces are not ignored in these fields. The information pieces are stored in separate control sequences with `\ExplFileName` for the part of the file name leading up to the period, `\ExplFileDate` for date, `\ExplFileVersion` for version and `\ExplFileDescription` for the description.

To summarize: Every single package using this syntax should identify itself using one of the above methods. Special care is taken so that every package or class file loaded with `\RequirePackage` or alike are loaded with usual L^AT_EX 2_ε category codes and the L^AT_EX3 category code scheme is reloaded when needed afterwards. See implementation for details. If you use the `\GetIdInfo` command you can use the information when loading a package with

```
\ProvidesExplPackage{\ExplFileName}
  {\ExplFileDate}{\ExplFileVersion}{\ExplFileDescription}
```

1.1 Internal functions and variables

\l_kernel_expl_bool

A boolean which records the current code syntax status: **true** if currently inside a code environment. This variable should only be set by `\ExplSyntaxOn/\ExplSyntaxOff`.

Part III

The `l3names` package

Namespace for primitives

1 Setting up the \LaTeX 3 programming language

This module is at the core of the \LaTeX 3 programming language. It performs the following tasks:

- defines new names for all \TeX primitives;
- switches to the category code régime for programming;
- provides support settings for building the code as a \TeX format.

This module is entirely dedicated to primitives, which should not be used directly within \LaTeX 3 code (outside of “kernel-level” code). As such, the primitives are not documented here: *The \TeX book*, *\TeX by Topic* and the manuals for \pdfTeX , \XeTeX and \LuaTeX should be consulted for details of the primitives. These are named based on the engine which first introduced them:

`\tex_...` Introduced by \TeX itself;
`\etex_...` Introduced by the $\varepsilon\text{\TeX}$ extensions;
`\pdftex_...` Introduced by \pdfTeX ;
`\xetex_...` Introduced by \XeTeX ;
`\luatex_...` Introduced by \LuaTeX ;
`\utex_...` Introduced by \XeTeX and \LuaTeX ;
`\ptex_...` Introduced by \pTeX ;
`\uptex_...` Introduced by \upTeX .

Part IV

The l3basics package

Basic definitions

As the name suggest this package holds some basic definitions which are needed by most or all other packages in this set.

Here we describe those functions that are used all over the place. With that we mean functions dealing with the construction and testing of control sequences. Furthermore the basic parts of conditional processing are covered; conditional processing dealing with specific data types is described in the modules specific for the respective data types.

1 No operation functions

`\prg_do_nothing:` ★**`\prg_do_nothing:`**

An expandable function which does nothing at all: leaves nothing in the input stream after a single expansion.

`\scan_stop:`**`\scan_stop:`**

A non-expandable function which does nothing. Does not vanish on expansion but produces no typeset output.

2 Grouping material

`\group_begin:`
`\group_end:`**`\group_begin:`**
`\group_end:`

These functions begin and end a group for definition purposes. Assignments are local to groups unless carried out in a global manner. (A small number of exceptions to this rule will be noted as necessary elsewhere in this document.) Each **`\group_begin:`** must be matched by a **`\group_end:`**, although this does not have to occur within the same function. Indeed, it is often necessary to start a group within one function and finish it within another, for example when seeking to use non-standard category codes.

`\group_insert_after:N`**`\group_insert_after:N`** *<token>*

Adds *<token>* to the list of *<tokens>* to be inserted when the current group level ends. The list of *<tokens>* to be inserted will be empty at the beginning of a group: multiple applications of **`\group_insert_after:N`** may be used to build the inserted list one *<token>* at a time. The current group level may be closed by a **`\group_end:`** function or by a token with category code 2 (close-group). The later will be a **`}`** if standard category codes apply.

3 Control sequences and functions

As \TeX is a macro language, creating new functions means creating macros. At point of use, a function is replaced by the replacement text (“code”) in which each parameter in the code (**#1**, **#2**, *etc.*) is replaced the appropriate arguments absorbed by the function. In the following, *code* is therefore used as a shorthand for “replacement text”.

Functions which are not “protected” will be fully expanded inside an **x** expansion. In contrast, “protected” functions are not expanded within **x** expansions.

3.1 Defining functions

Functions can be created with no requirement that they are declared first (in contrast to variables, which must always be declared). Declaring a function before setting up the code means that the name chosen will be checked and an error raised if it is already in use. The name of a function can be checked at the point of definition using the `\cs_new...` functions: this is recommended for all functions which are defined for the first time.

There are three ways to define new functions. All classes define a function to expand to the substitution text. Within the substitution text the actual parameters are substituted for the formal parameters (**#1**, **#2**, ...).

new Create a new function with the **new** scope, such as `\cs_new:Npn`. The definition is global and will result in an error if it is already defined.

set Create a new function with the **set** scope, such as `\cs_set:Npn`. The definition is restricted to the current \TeX group and will not result in an error if the function is already defined.

gset Create a new function with the **gset** scope, such as `\cs_gset:Npn`. The definition is global and will not result in an error if the function is already defined.

Within each set of scope there are different ways to define a function. The differences depend on restrictions on the actual parameters and the expandability of the resulting function.

nopar Create a new function with the **nopar** restriction, such as `\cs_set_nopar:Npn`. The parameter may not contain `\par` tokens.

protected Create a new function with the **protected** restriction, such as `\cs_set_protected:Npn`. The parameter may contain `\par` tokens but the function will not expand within an **x**-type expansion.

Finally, the functions in Subsections 3.2 and 3.3 are primarily meant to define *base functions* only. Base functions can only have the following argument specifiers:

N and **n** No manipulation.

T and **F** Functionally equivalent to **n** (you are actually encouraged to use the family of `\prg_new_conditional`: functions described in Section 1).

p and **w** These are special cases.

The `\cs_new:` functions below (and friends) do not stop you from using other argument specifiers in your function names, but they do not handle expansion for you. You should define the base function and then use `\cs_generate_variant:Nn` to generate custom variants as described in Section 2.

3.2 Defining new functions using parameter text

| | |
|--------------------------|--|
| <code>\cs_new:Npn</code> | <code>\cs_new:Npn <function> <parameters> {<code>}</code> |
| <code>\cs_new:cpn</code> | Creates <i><function></i> to expand to <i><code></i> as replacement text. Within the <i><code></i> , the |
| <code>\cs_new:Npx</code> | <i><parameters></i> (#1, #2, etc.) will be replaced by those absorbed by the function. The |
| <code>\cs_new:cpx</code> | definition is global and an error will result if the <i><function></i> is already defined. |

| | |
|--------------------------------|--|
| <code>\cs_new_nopar:Npn</code> | <code>\cs_new_nopar:Npn <function> <parameters> {<code>}</code> |
| <code>\cs_new_nopar:cpn</code> | Creates <i><function></i> to expand to <i><code></i> as replacement text. Within the <i><code></i> , the |
| <code>\cs_new_nopar:Npx</code> | <i><parameters></i> (#1, #2, etc.) will be replaced by those absorbed by the function. When the |
| <code>\cs_new_nopar:cpx</code> | <i><function></i> is used the <i><parameters></i> absorbed cannot contain <code>\par</code> tokens. The definition |
| | is global and an error will result if the <i><function></i> is already defined. |

| | |
|------------------------------------|--|
| <code>\cs_new_protected:Npn</code> | <code>\cs_new_protected:Npn <function> <parameters> {<code>}</code> |
| <code>\cs_new_protected:cpn</code> | Creates <i><function></i> to expand to <i><code></i> as replacement text. Within the <i><code></i> , the |
| <code>\cs_new_protected:Npx</code> | <i><parameters></i> (#1, #2, etc.) will be replaced by those absorbed by the function. The |
| <code>\cs_new_protected:cpx</code> | <i><function></i> will not expand within an x-type argument. The definition is global and an |
| | error will result if the <i><function></i> is already defined. |

| | |
|--|---|
| <code>\cs_new_protected_nopar:Npn</code> | <code>\cs_new_protected_nopar:Npn <function> <parameters> {<code>}</code> |
| <code>\cs_new_protected_nopar:cpn</code> | |
| <code>\cs_new_protected_nopar:Npx</code> | |
| <code>\cs_new_protected_nopar:cpx</code> | |

Creates *<function>* to expand to *<code>* as replacement text. Within the *<code>*, the *<parameters>* (#1, #2, etc.) will be replaced by those absorbed by the function. When the *<function>* is used the *<parameters>* absorbed cannot contain `\par` tokens. The *<function>* will not expand within an x-type argument. The definition is global and an error will result if the *<function>* is already defined.

| | |
|--------------------------|---|
| <code>\cs_set:Npn</code> | <code>\cs_set:Npn <function> <parameters> {<code>}</code> |
| <code>\cs_set:cpn</code> | Sets <i><function></i> to expand to <i><code></i> as replacement text. Within the <i><code></i> , the |
| <code>\cs_set:Npx</code> | <i><parameters></i> (#1, #2, etc.) will be replaced by those absorbed by the function. The |
| <code>\cs_set:cpx</code> | assignment of a meaning to the <i><function></i> is restricted to the current \TeX group level. |

| | |
|--------------------------------|--|
| <code>\cs_set_nopar:Npn</code> | <code>\cs_set_nopar:Npn <function> <parameters> {<code>}</code> |
| <code>\cs_set_nopar:cpn</code> | Sets <i><function></i> to expand to <i><code></i> as replacement text. Within the <i><code></i> , the |
| <code>\cs_set_nopar:Npx</code> | <i><parameters></i> (#1, #2, etc.) will be replaced by those absorbed by the function. When the |
| <code>\cs_set_nopar:cpx</code> | <i><function></i> is used the <i><parameters></i> absorbed cannot contain <code>\par</code> tokens. The assignment |
| | of a meaning to the <i><function></i> is restricted to the current \TeX group level. |

| | |
|------------------------------------|---|
| <code>\cs_set_protected:Npn</code> | <code>\cs_set_protected:Npn <function> <parameters> {<code>}</code> |
| <code>\cs_set_protected:cpn</code> | Sets <i><function></i> to expand to <i><code></i> as replacement text. Within the <i><code></i> , the |
| <code>\cs_set_protected:Npx</code> | <i><parameters></i> (#1, #2, etc.) will be replaced by those absorbed by the function. The |
| <code>\cs_set_protected:cpx</code> | assignment of a meaning to the <i><function></i> is restricted to the current \TeX group level. |
| | The <i><function></i> will not expand within an x-type argument. |

| | |
|--|---|
| <code>\cs_set_protected_nopar:Npn</code> | <code>\cs_set_protected_nopar:Npn <function> <parameters> {<code>}</code> |
| <code>\cs_set_protected_nopar:cpn</code> | |
| <code>\cs_set_protected_nopar:Npx</code> | |
| <code>\cs_set_protected_nopar:cpx</code> | |

Sets $\langle function \rangle$ to expand to $\langle code \rangle$ as replacement text. Within the $\langle code \rangle$, the $\langle parameters \rangle$ ($\#1$, $\#2$, etc.) will be replaced by those absorbed by the function. When the $\langle function \rangle$ is used the $\langle parameters \rangle$ absorbed cannot contain `\par` tokens. The assignment of a meaning to the $\langle function \rangle$ is restricted to the current \TeX group level. The $\langle function \rangle$ will not expand within an x -type argument.

| | |
|---------------------------|--|
| <code>\cs_gset:Npn</code> | <code>\cs_gset:Npn <function> <parameters> {<code>}</code> |
| <code>\cs_gset:cpn</code> | |
| <code>\cs_gset:Npx</code> | |
| <code>\cs_gset:cpx</code> | |

Globally sets $\langle function \rangle$ to expand to $\langle code \rangle$ as replacement text. Within the $\langle code \rangle$, the $\langle parameters \rangle$ ($\#1$, $\#2$, etc.) will be replaced by those absorbed by the function. The assignment of a meaning to the $\langle function \rangle$ is *not* restricted to the current \TeX group level: the assignment is global.

| | |
|---------------------------------|--|
| <code>\cs_gset_nopar:Npn</code> | <code>\cs_gset_nopar:Npn <function> <parameters> {<code>}</code> |
| <code>\cs_gset_nopar:cpn</code> | |
| <code>\cs_gset_nopar:Npx</code> | |
| <code>\cs_gset_nopar:cpx</code> | |

Globally sets $\langle function \rangle$ to expand to $\langle code \rangle$ as replacement text. Within the $\langle code \rangle$, the $\langle parameters \rangle$ ($\#1$, $\#2$, etc.) will be replaced by those absorbed by the function. When the $\langle function \rangle$ is used the $\langle parameters \rangle$ absorbed cannot contain `\par` tokens. The assignment of a meaning to the $\langle function \rangle$ is *not* restricted to the current \TeX group level: the assignment is global.

| | |
|-------------------------------------|--|
| <code>\cs_gset_protected:Npn</code> | <code>\cs_gset_protected:Npn <function> <parameters> {<code>}</code> |
| <code>\cs_gset_protected:cpn</code> | |
| <code>\cs_gset_protected:Npx</code> | |
| <code>\cs_gset_protected:cpx</code> | |

Globally sets $\langle function \rangle$ to expand to $\langle code \rangle$ as replacement text. Within the $\langle code \rangle$, the $\langle parameters \rangle$ ($\#1$, $\#2$, etc.) will be replaced by those absorbed by the function. The assignment of a meaning to the $\langle function \rangle$ is *not* restricted to the current \TeX group level: the assignment is global. The $\langle function \rangle$ will not expand within an x -type argument.

| | |
|---|--|
| <code>\cs_gset_protected_nopar:Npn</code> | <code>\cs_gset_protected_nopar:Npn <function> <parameters> {<code>}</code> |
| <code>\cs_gset_protected_nopar:cpn</code> | |
| <code>\cs_gset_protected_nopar:Npx</code> | |
| <code>\cs_gset_protected_nopar:cpx</code> | |

Globally sets $\langle function \rangle$ to expand to $\langle code \rangle$ as replacement text. Within the $\langle code \rangle$, the $\langle parameters \rangle$ ($\#1$, $\#2$, etc.) will be replaced by those absorbed by the function. When the $\langle function \rangle$ is used the $\langle parameters \rangle$ absorbed cannot contain `\par` tokens. The assignment of a meaning to the $\langle function \rangle$ is *not* restricted to the current \TeX group level: the assignment is global. The $\langle function \rangle$ will not expand within an x -type argument.

3.3 Defining new functions using the signature

| | |
|---------------------------------|---|
| <code>\cs_new:Nn</code> | <code>\cs_new:Nn <function> {<code>}</code> |
| <code>\cs_new:(cn Nx cx)</code> | |

Creates $\langle function \rangle$ to expand to $\langle code \rangle$ as replacement text. Within the $\langle code \rangle$, the number of $\langle parameters \rangle$ is detected automatically from the function signature. These $\langle parameters \rangle$ ($\#1$, $\#2$, etc.) will be replaced by those absorbed by the function. The definition is global and an error will result if the $\langle function \rangle$ is already defined.

`\cs_new_nopar:Nn`
`\cs_new_nopar:(cn|Nx|cx)`

`\cs_new_nopar:Nn <function> {<code>}`

Creates $\langle function \rangle$ to expand to $\langle code \rangle$ as replacement text. Within the $\langle code \rangle$, the number of $\langle parameters \rangle$ is detected automatically from the function signature. These $\langle parameters \rangle$ ($\#1$, $\#2$, *etc.*) will be replaced by those absorbed by the function. When the $\langle function \rangle$ is used the $\langle parameters \rangle$ absorbed cannot contain `\par` tokens. The definition is global and an error will result if the $\langle function \rangle$ is already defined.

`\cs_new_protected:Nn`
`\cs_new_protected:(cn|Nx|cx)`

`\cs_new_protected:Nn <function> {<code>}`

Creates $\langle function \rangle$ to expand to $\langle code \rangle$ as replacement text. Within the $\langle code \rangle$, the number of $\langle parameters \rangle$ is detected automatically from the function signature. These $\langle parameters \rangle$ ($\#1$, $\#2$, *etc.*) will be replaced by those absorbed by the function. The $\langle function \rangle$ will not expand within an x-type argument. The definition is global and an error will result if the $\langle function \rangle$ is already defined.

`\cs_new_protected_nopar:Nn`
`\cs_new_protected_nopar:(cn|Nx|cx)`

`\cs_new_protected_nopar:Nn <function> {<code>}`

Creates $\langle function \rangle$ to expand to $\langle code \rangle$ as replacement text. Within the $\langle code \rangle$, the number of $\langle parameters \rangle$ is detected automatically from the function signature. These $\langle parameters \rangle$ ($\#1$, $\#2$, *etc.*) will be replaced by those absorbed by the function. When the $\langle function \rangle$ is used the $\langle parameters \rangle$ absorbed cannot contain `\par` tokens. The $\langle function \rangle$ will not expand within an x-type argument. The definition is global and an error will result if the $\langle function \rangle$ is already defined.

`\cs_set:Nn`
`\cs_set:(cn|Nx|cx)`

`\cs_set:Nn <function> {<code>}`

Sets $\langle function \rangle$ to expand to $\langle code \rangle$ as replacement text. Within the $\langle code \rangle$, the number of $\langle parameters \rangle$ is detected automatically from the function signature. These $\langle parameters \rangle$ ($\#1$, $\#2$, *etc.*) will be replaced by those absorbed by the function. The assignment of a meaning to the $\langle function \rangle$ is restricted to the current \TeX group level.

`\cs_set_nopar:Nn`
`\cs_set_nopar:(cn|Nx|cx)`

`\cs_set_nopar:Nn <function> {<code>}`

Sets $\langle function \rangle$ to expand to $\langle code \rangle$ as replacement text. Within the $\langle code \rangle$, the number of $\langle parameters \rangle$ is detected automatically from the function signature. These $\langle parameters \rangle$ ($\#1$, $\#2$, *etc.*) will be replaced by those absorbed by the function. When the $\langle function \rangle$ is used the $\langle parameters \rangle$ absorbed cannot contain `\par` tokens. The assignment of a meaning to the $\langle function \rangle$ is restricted to the current \TeX group level.

`\cs_set_protected:Nn`
`\cs_set_protected:(cn|Nx|cx)`

`\cs_set_protected:Nn <function> {<code>}`

Sets $\langle function \rangle$ to expand to $\langle code \rangle$ as replacement text. Within the $\langle code \rangle$, the number of $\langle parameters \rangle$ is detected automatically from the function signature. These $\langle parameters \rangle$ ($\#1$, $\#2$, *etc.*) will be replaced by those absorbed by the function. The $\langle function \rangle$ will not expand within an x-type argument. The assignment of a meaning to the $\langle function \rangle$ is restricted to the current \TeX group level.

| | |
|---|---|
| <code>\cs_set_protected_nopar:Nn</code> | <code>\cs_set_protected_nopar:Nn <function> {<code>}</code> |
| <code>\cs_set_protected_nopar:(cn Nx cx)</code> | |

Sets $\langle function \rangle$ to expand to $\langle code \rangle$ as replacement text. Within the $\langle code \rangle$, the number of $\langle parameters \rangle$ is detected automatically from the function signature. These $\langle parameters \rangle$ ($\#1$, $\#2$, *etc.*) will be replaced by those absorbed by the function. When the $\langle function \rangle$ is used the $\langle parameters \rangle$ absorbed cannot contain `\par` tokens. The $\langle function \rangle$ will not expand within an x-type argument. The assignment of a meaning to the $\langle function \rangle$ is restricted to the current TeX group level.

| | |
|----------------------------------|--|
| <code>\cs_gset:Nn</code> | <code>\cs_gset:Nn <function> {<code>}</code> |
| <code>\cs_gset:(cn Nx cx)</code> | |

Sets $\langle function \rangle$ to expand to $\langle code \rangle$ as replacement text. Within the $\langle code \rangle$, the number of $\langle parameters \rangle$ is detected automatically from the function signature. These $\langle parameters \rangle$ ($\#1$, $\#2$, *etc.*) will be replaced by those absorbed by the function. The assignment of a meaning to the $\langle function \rangle$ is global.

| | |
|--|--|
| <code>\cs_gset_nopar:Nn</code> | <code>\cs_gset_nopar:Nn <function> {<code>}</code> |
| <code>\cs_gset_nopar:(cn Nx cx)</code> | |

Sets $\langle function \rangle$ to expand to $\langle code \rangle$ as replacement text. Within the $\langle code \rangle$, the number of $\langle parameters \rangle$ is detected automatically from the function signature. These $\langle parameters \rangle$ ($\#1$, $\#2$, *etc.*) will be replaced by those absorbed by the function. When the $\langle function \rangle$ is used the $\langle parameters \rangle$ absorbed cannot contain `\par` tokens. The assignment of a meaning to the $\langle function \rangle$ is global.

| | |
|--|--|
| <code>\cs_gset_protected:Nn</code> | <code>\cs_gset_protected:Nn <function> {<code>}</code> |
| <code>\cs_gset_protected:(cn Nx cx)</code> | |

Sets $\langle function \rangle$ to expand to $\langle code \rangle$ as replacement text. Within the $\langle code \rangle$, the number of $\langle parameters \rangle$ is detected automatically from the function signature. These $\langle parameters \rangle$ ($\#1$, $\#2$, *etc.*) will be replaced by those absorbed by the function. The $\langle function \rangle$ will not expand within an x-type argument. The assignment of a meaning to the $\langle function \rangle$ is global.

| | |
|--|--|
| <code>\cs_gset_protected_nopar:Nn</code> | <code>\cs_gset_protected_nopar:Nn <function> {<code>}</code> |
| <code>\cs_gset_protected_nopar:(cn Nx cx)</code> | |

Sets $\langle function \rangle$ to expand to $\langle code \rangle$ as replacement text. Within the $\langle code \rangle$, the number of $\langle parameters \rangle$ is detected automatically from the function signature. These $\langle parameters \rangle$ ($\#1$, $\#2$, *etc.*) will be replaced by those absorbed by the function. When the $\langle function \rangle$ is used the $\langle parameters \rangle$ absorbed cannot contain `\par` tokens. The $\langle function \rangle$ will not expand within an x-type argument. The assignment of a meaning to the $\langle function \rangle$ is global.

| | |
|--|---|
| <code>\cs_generate_from_arg_count:NNnn</code> | <code>\cs_generate_from_arg_count:NNnn <function> <creator> <number></code> |
| <code>\cs_generate_from_arg_count:(cNnn Ncnn)</code> | <code><code></code> |

Updated: 2012-01-14

Uses the $\langle creator \rangle$ function (which should have signature Npn , for example `\cs_new:Npn`) to define a $\langle function \rangle$ which takes $\langle number \rangle$ arguments and has $\langle code \rangle$ as replacement text. The $\langle number \rangle$ of arguments is an integer expression, evaluated as detailed for `\int_eval:n`.

3.4 Copying control sequences

Control sequences (not just functions as defined above) can be set to have the same meaning using the functions described here. Making two control sequences equivalent means that the second control sequence is a *copy* of the first (rather than a pointer to it). Thus the old and new control sequence are not tied together: changes to one are not reflected in the other.

In the following text “cs” is used as an abbreviation for “control sequence”.

```
\cs_new_eq:NN
\cs_new_eq:(Nc|cN|cc)
```

```
\cs_new_eq:NN <cs1> <cs2>
\cs_new_eq:NN <cs1> <token>
```

Globally creates $\langle control\ sequence_1 \rangle$ and sets it to have the same meaning as $\langle control\ sequence_2 \rangle$ or $\langle token \rangle$. The second control sequence may subsequently be altered without affecting the copy.

```
\cs_set_eq:NN
\cs_set_eq:(Nc|cN|cc)
```

```
\cs_set_eq:NN <cs1> <cs2>
\cs_set_eq:NN <cs1> <token>
```

Sets $\langle control\ sequence_1 \rangle$ to have the same meaning as $\langle control\ sequence_2 \rangle$ (or $\langle token \rangle$). The second control sequence may subsequently be altered without affecting the copy. The assignment of a meaning to the $\langle control\ sequence_1 \rangle$ is restricted to the current \TeX group level.

```
\cs_gset_eq:NN
\cs_gset_eq:(Nc|cN|cc)
```

```
\cs_gset_eq:NN <cs1> <cs2>
\cs_gset_eq:NN <cs1> <token>
```

Globally sets $\langle control\ sequence_1 \rangle$ to have the same meaning as $\langle control\ sequence_2 \rangle$ (or $\langle token \rangle$). The second control sequence may subsequently be altered without affecting the copy. The assignment of a meaning to the $\langle control\ sequence_1 \rangle$ is *not* restricted to the current \TeX group level: the assignment is global.

3.5 Deleting control sequences

There are occasions where control sequences need to be deleted. This is handled in a very simple manner.

```
\cs_undefine:N
\cs_undefine:c
```

```
\cs_undefine:N <control\ sequence>
```

Sets $\langle control\ sequence \rangle$ to be globally undefined.

Updated: 2011-09-15

3.6 Showing control sequences

```
\cs_meaning:N ★
\cs_meaning:c ★
```

```
\cs_meaning:N <control\ sequence>
```

This function expands to the *meaning* of the $\langle control\ sequence \rangle$ control sequence. This will show the $\langle replacement\ text \rangle$ for a macro.

Updated: 2011-12-22

\TeX hackers note: This is \TeX ’s `\meaning` primitive. The `c` variant correctly reports undefined arguments.

`\cs_show:N`
`\cs_show:c`

Updated: 2017-02-14

`\cs_show:N` $\langle control\ sequence \rangle$
Displays the definition of the $\langle control\ sequence \rangle$ on the terminal.

T_EXhackers note: This is similar to the T_EX primitive `\show`, wrapped to a fixed number of characters per line.

`\cs_log:N`
`\cs_log:c`

New: 2014-08-22
Updated: 2017-02-14

`\cs_log:N` $\langle control\ sequence \rangle$
Writes the definition of the $\langle control\ sequence \rangle$ in the log file. See also `\cs_show:N` which displays the result in the terminal.

3.7 Converting to and from control sequences

`\use:c` ★

`\use:c` $\{\langle control\ sequence\ name \rangle\}$

Converts the given $\langle control\ sequence\ name \rangle$ into a single control sequence token. This process requires two expansions. The content for $\langle control\ sequence\ name \rangle$ may be literal material or from other expandable functions. The $\langle control\ sequence\ name \rangle$ must, when fully expanded, consist of character tokens which are not active: typically, they will be of category code 10 (space), 11 (letter) or 12 (other), or a mixture of these.

As an example of the `\use:c` function, both

`\use:c { a b c }`

and

`\tl_new:N \l_my_tl`
`\tl_set:Nn \l_my_tl { a b c }`
`\use:c { \tl_use:N \l_my_tl }`

would be equivalent to

`\abc`

after two expansions of `\use:c`.

`\cs_if_exist_use:N` ★
`\cs_if_exist_use:c` ★
`\cs_if_exist_use:NTF` ★
`\cs_if_exist_use:cTF` ★

New: 2012-11-10

`\cs_if_exist_use:N` $\langle control\ sequence \rangle$
`\cs_if_exist_use:NNTF` $\langle control\ sequence \rangle$ $\{\langle true\ code \rangle\}$ $\{\langle false\ code \rangle\}$

Tests whether the $\langle control\ sequence \rangle$ is currently defined (whether as a function or another control sequence type), and if it is inserts the $\langle control\ sequence \rangle$ into the input stream followed by the $\langle true\ code \rangle$. Otherwise the $\langle false\ code \rangle$ is used.

`\cs:w` ★
`\cs_end:` ★

`\cs:w` $\langle control\ sequence\ name \rangle$ `\cs_end:`

Converts the given $\langle control\ sequence\ name \rangle$ into a single control sequence token. This process requires one expansion. The content for $\langle control\ sequence\ name \rangle$ may be literal material or from other expandable functions. The $\langle control\ sequence\ name \rangle$ must, when fully expanded, consist of character tokens which are not active: typically, they will be of category code 10 (space), 11 (letter) or 12 (other), or a mixture of these.

T_EXhackers note: These are the T_EX primitives `\csname` and `\endcsname`.

As an example of the `\cs:w` and `\cs_end:` functions, both

```
\cs:w a b c \cs_end:
```

and

```
\tl_new:N \l_my_tl
\tl_set:Nn \l_my_tl { a b c }
\cs:w \tl_use:N \l_my_tl \cs_end:
```

would be equivalent to

```
\abc
```

after one expansion of `\cs:w`.

```
\cs_to_str:N ★ \cs_to_str:N <control sequence>
```

Converts the given *<control sequence>* into a series of characters with category code 12 (other), except spaces, of category code 10. The sequence will *not* include the current escape token, cf. `\token_to_str:N`. Full expansion of this function requires exactly 2 expansion steps, and so an x-type expansion, or two o-type expansions will be required to convert the *<control sequence>* to a sequence of characters in the input stream. In most cases, an f-expansion will be correct as well, but this loses a space at the start of the result.

4 Using or removing tokens and arguments

Tokens in the input can be read and used or read and discarded. If one or more tokens are wrapped in braces then in absorbing them the outer set will be removed. At the same time, the category code of each token is set when the token is read by a function (if it is read more than once, the category code is determined by the situation in force when first function absorbs the token).

```
\use:n ★ \use:n {<group1>}
\use:nn ★ \use:nn {<group1>} {<group2>}
\use:nnn ★ \use:nnn {<group1>} {<group2>} {<group3>}
\use:nnnn ★ \use:nnnn {<group1>} {<group2>} {<group3>} {<group4>}
```

As illustrated, these functions will absorb between one and four arguments, as indicated by the argument specifier. The braces surrounding each argument will be removed leaving the remaining tokens in the input stream. The category code of these tokens will also be fixed by this process (if it has not already been by some other absorption). All of these functions require only a single expansion to operate, so that one expansion of

```
\use:nn { abc } { { def } }
```

will result in the input stream containing

```
abc { def }
```

i.e. only the outer braces will be removed.

| | | |
|------------------------|---|--|
| <code>\use_i:nn</code> | ★ | <code>\use_i:nn {\langle arg_1 \rangle} {\langle arg_2 \rangle}</code> |
|------------------------|---|--|

| | | |
|-------------------------|---|---|
| <code>\use_ii:nn</code> | ★ | These functions absorb two arguments from the input stream. The function <code>\use_i:nn</code> discards the second argument, and leaves the content of the first argument in the input stream. <code>\use_ii:nn</code> discards the first argument and leaves the content of the second argument in the input stream. The category code of these tokens will also be fixed (if it has not already been by some other absorption). A single expansion is needed for the functions to take effect. |
|-------------------------|---|---|

| | | |
|-------------------------|---|---|
| <code>\use_i:nnn</code> | ★ | <code>\use_i:nnn {\langle arg_1 \rangle} {\langle arg_2 \rangle} {\langle arg_3 \rangle}</code> |
|-------------------------|---|---|

| | | |
|---------------------------|---|---|
| <code>\use_ii:nnn</code> | ★ | These functions absorb three arguments from the input stream. The function <code>\use_i:nnn</code> discards the second and third arguments, and leaves the content of the first argument in the input stream. <code>\use_ii:nnn</code> and <code>\use_iii:nnn</code> work similarly, leaving the content of second or third arguments in the input stream, respectively. The category code of these tokens will also be fixed (if it has not already been by some other absorption). A single expansion is needed for the functions to take effect. |
| <code>\use_iii:nnn</code> | ★ | |

| | | |
|--------------------------|---|--|
| <code>\use_i:nnnn</code> | ★ | <code>\use_i:nnnn {\langle arg_1 \rangle} {\langle arg_2 \rangle} {\langle arg_3 \rangle} {\langle arg_4 \rangle}</code> |
|--------------------------|---|--|

| | | |
|----------------------------|---|---|
| <code>\use_ii:nnnn</code> | ★ | These functions absorb four arguments from the input stream. The function <code>\use_i:nnnn</code> discards the second, third and fourth arguments, and leaves the content of the first argument in the input stream. <code>\use_ii:nnnn</code> , <code>\use_iii:nnnn</code> and <code>\use_iv:nnnn</code> work similarly, leaving the content of second, third or fourth arguments in the input stream, respectively. The category code of these tokens will also be fixed (if it has not already been by some other absorption). A single expansion is needed for the functions to take effect. |
| <code>\use_iii:nnnn</code> | ★ | |
| <code>\use_iv:nnnn</code> | ★ | |

| | | |
|----------------------------|---|--|
| <code>\use_i_ii:nnn</code> | ★ | <code>\use_i_ii:nnn {\langle arg_1 \rangle} {\langle arg_2 \rangle} {\langle arg_3 \rangle}</code> |
|----------------------------|---|--|

This functions will absorb three arguments and leave the content of the first and second in the input stream. The category code of these tokens will also be fixed (if it has not already been by some other absorption). A single expansion is needed for the functions to take effect. An example:

`\use_i_ii:nnn { abc } { { def } } { ghi }`

will result in the input stream containing

`abc { def }`

i.e. the outer braces will be removed and the third group will be removed.

| | | |
|--------------------------|---|--|
| <code>\use_none:n</code> | ★ | <code>\use_none:n {\langle group_1 \rangle}</code> |
|--------------------------|---|--|

| | | |
|--------------------------------|---|--|
| <code>\use_none:nn</code> | ★ | These functions absorb between one and nine groups from the input stream, leaving nothing on the resulting input stream. These functions work after a single expansion. One or more of the <code>n</code> arguments may be an unbraced single token (<i>i.e.</i> an <code>N</code> argument). |
| <code>\use_none:nnn</code> | ★ | |
| <code>\use_none:nnnn</code> | ★ | |
| <code>\use_none:nnnnn</code> | ★ | |
| <code>\use_none:nnnnnn</code> | ★ | |
| <code>\use_none:nnnnnnn</code> | ★ | |

| | |
|--------------------------------|---|
| <code>\use_none:nnnnnnn</code> | ★ |
|--------------------------------|---|

| | |
|---------------------------------|---|
| <code>\use_none:nnnnnnnn</code> | ★ |
|---------------------------------|---|

| | |
|----------------------------------|---|
| <code>\use_none:nnnnnnnnn</code> | ★ |
|----------------------------------|---|

| | |
|-----------------------------------|---|
| <code>\use_none:nnnnnnnnnn</code> | ★ |
|-----------------------------------|---|

| | |
|---------------------|---|
| <code>\use:x</code> | <code>\use:x {⟨expandable tokens⟩}</code> |
|---------------------|---|

| | |
|---------------------|---|
| Updated: 2011-12-31 | Fully expands the <i>⟨expandable tokens⟩</i> and inserts the result into the input stream at the current location. Any hash characters (#) in the argument must be doubled. |
|---------------------|---|

4.1 Selecting tokens from delimited arguments

A different kind of function for selecting tokens from the token stream are those that use delimited arguments.

| | | |
|--|---|--|
| <code>\use_none_delimit_by_q_nil:w</code> | ★ | <code>\use_none_delimit_by_q_nil:w ⟨balanced text⟩ \q_nil</code> |
| <code>\use_none_delimit_by_q_stop:w</code> | ★ | <code>\use_none_delimit_by_q_stop:w ⟨balanced text⟩ \q_stop</code> |
| <code>\use_none_delimit_by_q_recursion_stop:w</code> | ★ | <code>\use_none_delimit_by_q_recursion_stop:w ⟨balanced text⟩</code> <code>\q_recursion_stop</code> |

Absorb the *⟨balanced text⟩* from the input stream delimited by the marker given in the function name, leaving nothing in the input stream.

| | | |
|--|---|--|
| <code>\use_i_delimit_by_q_nil:nw</code> | ★ | <code>\use_i_delimit_by_q_nil:nw {⟨inserted tokens⟩} ⟨balanced text⟩</code> |
| <code>\use_i_delimit_by_q_stop:nw</code> | ★ | <code>\q_nil</code> |
| <code>\use_i_delimit_by_q_recursion_stop:nw</code> | ★ | <code>\use_i_delimit_by_q_stop:nw {⟨inserted tokens⟩} ⟨balanced</code> <code>text⟩ \q_stop</code> <code>\use_i_delimit_by_q_recursion_stop:nw {⟨inserted tokens⟩}</code> <code>⟨balanced text⟩ \q_recursion_stop</code> |

Absorb the *⟨balanced text⟩* from the input stream delimited by the marker given in the function name, leaving *⟨inserted tokens⟩* in the input stream for further processing.

5 Predicates and conditionals

L^AT_EX3 has three concepts for conditional flow processing:

Branching conditionals Functions that carry out a test and then execute, depending on its result, either the code supplied as the *⟨true code⟩* or the *⟨false code⟩*. These arguments are denoted with T and F, respectively. An example would be

`\cs_if_free:cTF {abc} {⟨true code⟩} {⟨false code⟩}`

a function that will turn the first argument into a control sequence (since it's marked as c) then checks whether this control sequence is still free and then depending on the result carry out the code in the second argument (true case) or in the third argument (false case).

These type of functions are known as “conditionals”; whenever a TF function is defined it will usually be accompanied by T and F functions as well. These are provided for convenience when the branch only needs to go a single way. Package writers are free to choose which types to define but the kernel definitions will always provide all three versions.

Important to note is that these branching conditionals with *⟨true code⟩* and/or *⟨false code⟩* are always defined in a way that the code of the chosen alternative can operate on following tokens in the input stream.

These conditional functions may or may not be fully expandable, but if they are expandable they will be accompanied by a “predicate” for the same test as described below.

Predicates “Predicates” are functions that return a special type of boolean value which can be tested by the boolean expression parser. All functions of this type are expandable and have names that end with `_p` in the description part. For example,

`\cs_if_free_p:N`

would be a predicate function for the same type of test as the conditional described above. It would return “true” if its argument (a single token denoted by `N`) is still free for definition. It would be used in constructions like

```
\bool_if:nTF {
  \cs_if_free_p:N \l_tmpz_tl || \cs_if_free_p:N \g_tmpz_tl
} {\true code} {\false code}
```

For each predicate defined, a “branching conditional” will also exist that behaves like a conditional described above.

Primitive conditionals There is a third variety of conditional, which is the original concept used in plain \TeX and $\text{\LaTeX 2}_{\epsilon}$. Their use is discouraged in `expl3` (although still used in low-level definitions) because they are more fragile and in many cases require more expansion control (hence more code) than the two types of conditionals described above.

`\c_true_bool`
`\c_false_bool`

Constants that represent `true` and `false`, respectively. Used to implement predicates.

5.1 Tests on control sequences

| | |
|-------------------------------|--|
| <code>\cs_if_eq_p:NN</code> ★ | <code>\cs_if_eq_p:NN {<cs₁>} {<cs₂>}</code> |
| <code>\cs_if_eq:NNTF</code> ★ | <code>\cs_if_eq:NNTF {<cs₁>} {<cs₂>} {\true code} {\false code}</code> |

Compares the definition of two *<control sequences>* and is logically `true` if they are the same, *i.e.* if they have exactly the same definition when examined with `\cs_show:N`.

| | |
|----------------------------------|---|
| <code>\cs_if_exist_p:N</code> ★ | <code>\cs_if_exist_p:N <control sequence></code> |
| <code>\cs_if_exist_p:c</code> ★ | <code>\cs_if_exist:NNTF <control sequence> {\true code} {\false code}</code> |
| <code>\cs_if_exist:NNTF</code> ★ | Tests whether the <i><control sequence></i> is currently defined (whether as a function or another control sequence type). Any valid definition of <i><control sequence></i> will evaluate as <code>true</code> . |
| <code>\cs_if_exist:cTF</code> ★ | |

| | |
|---------------------------------|---|
| <code>\cs_if_free_p:N</code> ★ | <code>\cs_if_free_p:N <control sequence></code> |
| <code>\cs_if_free_p:c</code> ★ | <code>\cs_if_free:NNTF <control sequence> {\true code} {\false code}</code> |
| <code>\cs_if_free:NNTF</code> ★ | Tests whether the <i><control sequence></i> is currently free to be defined. This test will be <code>false</code> if the <i><control sequence></i> currently exists (as defined by <code>\cs_if_exist:N</code>). |
| <code>\cs_if_free:cTF</code> ★ | |

5.2 Primitive conditionals

The ε -TeX engine itself provides many different conditionals. Some expand whatever comes after them and others don't. Hence the names for these underlying functions will often contain a :w part but higher level functions are often available. See for instance `\int_compare_p:nNn` which is a wrapper for `\if_int_compare:w`.

Certain conditionals deal with specific data types like boxes and fonts and are described there. The ones described below are either the universal conditionals or deal with control sequences. We will prefix primitive conditionals with `\if_`.

| | | |
|----------------------------|---|--|
| <code>\if_true:</code> | ★ | <code>\if_true: <true code> \else: <false code> \fi:</code> |
| <code>\if_false:</code> | ★ | <code>\if_false: <true code> \else: <false code> \fi:</code> |
| <code>\else:</code> | ★ | <code>\reverse_if:N <primitive conditional></code> |
| <code>\fi:</code> | ★ | |
| <code>\reverse_if:N</code> | ★ | |

`\if_true:` always executes *<true code>*, while `\if_false:` always executes *<false code>*. `\reverse_if:N` reverses any two-way primitive conditional. `\else:` and `\fi:` delimit the branches of the conditional. The function `\or:` is documented in `l3int` and used in case switches.

TeXhackers note: These are equivalent to their corresponding TeX primitive conditionals; `\reverse_if:N` is ε -TeX's `\unless`.

| | | |
|----------------------------|---|---|
| <code>\if_meaning:w</code> | ★ | <code>\if_meaning:w <arg₁₂</code> |
|----------------------------|---|---|

`\if_meaning:w` executes *<true code>* when *<arg_{1 and *<arg_{2 are the same, otherwise it executes *<false code>*. *<arg_{1 and *<arg_{2 could be functions, variables, tokens; in all cases the *unexpanded* definitions are compared.}*}*}*}*

TeXhackers note: This is TeX's `\ifx`.

| | | |
|-----------------------------|---|---|
| <code>\if:w</code> | ★ | <code>\if:w <token₁₂</code> |
| <code>\if_charcode:w</code> | ★ | <code>\if_catcode:w <token₁₂</code> |
| <code>\if_catcode:w</code> | ★ | |

These conditionals will expand any following tokens until two unexpandable tokens are left. If you wish to prevent this expansion, prefix the token in question with `\exp_not:N`. `\if_catcode:w` tests if the category codes of the two tokens are the same whereas `\if:w` tests if the character codes are identical. `\if_charcode:w` is an alternative name for `\if:w`.

| | | |
|-----------------------------|---|--|
| <code>\if_cs_exist:N</code> | ★ | <code>\if_cs_exist:N <cs> <true code> \else: <false code> \fi:</code> |
| <code>\if_cs_exist:w</code> | ★ | <code>\if_cs_exist:w <tokens> \cs_end: <true code> \else: <false code> \fi:</code> |

Check if *<cs>* appears in the hash table or if the control sequence that can be formed from *<tokens>* appears in the hash table. The latter function does not turn the control sequence in question into `\scan_stop:!` This can be useful when dealing with control sequences which cannot be entered as a single token.

| | | |
|-----------------------------------|---|--|
| <code>\if_mode_horizontal:</code> | ★ | <code>\if_mode_horizontal: <true code> \else: <false code> \fi:</code> |
| <code>\if_mode_vertical:</code> | ★ | |
| <code>\if_mode_math:</code> | ★ | |
| <code>\if_mode_inner:</code> | ★ | |

Execute *<true code>* if currently in horizontal mode, otherwise execute *<false code>*. Similar for the other functions.

6 Internal kernel functions

| | |
|--|---|
| <hr/> <code>__chk_if_exist_cs:N</code> <hr/> <code>__chk_if_exist_cs:c</code> | <code>__chk_if_exist_cs:N <cs></code> This function checks that <i><cs></i> exists according to the criteria for <code>\cs_if_exist_p:N</code> , and if not raises a kernel-level error. |
| <hr/> <code>__chk_if_free_cs:N</code> <hr/> <code>__chk_if_free_cs:c</code> | <code>__chk_if_free_cs:N <cs></code> This function checks that <i><cs></i> is free according to the criteria for <code>\cs_if_free_p:N</code> , and if not raises a kernel-level error. |
| <hr/> <code>__chk_if_exist_var:N</code> <hr/> | <code>__chk_if_exist_var:N <var></code> This function checks that <i><var></i> is defined according to the criteria for <code>\cs_if_free_p:N</code> , and if not raises a kernel-level error. This function is only created if the package option <code>check-declarations</code> is active. |
| <hr/> <code>__chk_log:x</code> <hr/> | <code>__chk_log:x {<message text>}</code> If the <code>log-functions</code> option is active, this function writes the <i><message text></i> to the log file using <code>\iow_log:x</code> . Otherwise, the <i><message text></i> is ignored using <code>\use_none:n</code> . |
| <hr/> <code>__chk_suspend_log:</code> <hr/> <code>__chk_resume_log:</code> | <code>__chk_suspend_log: ... __chk_log:x ... __chk_resume_log:</code> Any <code>__chk_log:x</code> command between <code>__chk_suspend_log:</code> and <code>__chk_resume_log:</code> is suppressed. These commands can be nested. |
| <hr/> <code>__cs_count_signature:N</code> ★ <hr/> <code>__cs_count_signature:c</code> ★ | <code>__cs_count_signature:N <function></code> Splits the <i><function></i> into the <i><name></i> (<i>i.e.</i> the part before the colon) and the <i><signature></i> (<i>i.e.</i> after the colon). The <i><number></i> of tokens in the <i><signature></i> is then left in the input stream. If there was no <i><signature></i> then the result is the marker value <code>-1</code> . |
| <hr/> <code>__cs_split_function:NN</code> ★ <hr/> | <code>__cs_split_function:NN <function> <processor></code> Splits the <i><function></i> into the <i><name></i> (<i>i.e.</i> the part before the colon) and the <i><signature></i> (<i>i.e.</i> after the colon). This information is then placed in the input stream after the <i><processor></i> function in three parts: the <i><name></i> , the <i><signature></i> and a logic token indicating if a colon was found (to differentiate variables from function names). The <i><name></i> will not include the escape character, and both the <i><name></i> and <i><signature></i> are made up of tokens with category code 12 (other). The <i><processor></i> should be a function with argument specification <code>:nnN</code> (plus any trailing arguments needed). |
| <hr/> <code>__cs_get_function_name:N</code> ★ <hr/> | <code>__cs_get_function_name:N <function></code> Splits the <i><function></i> into the <i><name></i> (<i>i.e.</i> the part before the colon) and the <i><signature></i> (<i>i.e.</i> after the colon). The <i><name></i> is then left in the input stream without the escape character present made up of tokens with category code 12 (other). |
| <hr/> <code>__cs_get_function_signature:N</code> ★ <hr/> | <code>__cs_get_function_signature:N <function></code> Splits the <i><function></i> into the <i><name></i> (<i>i.e.</i> the part before the colon) and the <i><signature></i> (<i>i.e.</i> after the colon). The <i><signature></i> is then left in the input stream made up of tokens with category code 12 (other). |

| | |
|-------------------------|---|
| <code>_cs_tmp:w</code> | Function used for various short-term usages, for instance defining functions whose definition involves tokens which are hard to insert normally (spaces, characters with category other). |
|-------------------------|---|

| | |
|---------------------------------------|--|
| <code>_kernel_register_show:N</code> | <code>_kernel_register_show:N <register></code> |
| <code>_kernel_register_show:c</code> | Used to show the contents of a T _E X register at the terminal, formatted such that internal parts of the mechanism are not visible. |

| | |
|--------------------------------------|--|
| <code>_kernel_register_log:N</code> | <code>_kernel_register_log:N <register></code> |
| <code>_kernel_register_log:c</code> | Used to write the contents of a T _E X register to the log file in a form similar to <code>_kernel_register_show:N</code> . |

Updated: 2015-08-03

| | |
|----------------------------------|---|
| <code>_prg_case_end:nw</code> ★ | <code>_prg_case_end:nw {<code>} <tokens> \q_mark {<true code>} \q_mark {<false code>} \q_stop</code> |
|----------------------------------|---|

Used to terminate case statements (`\int_case:nnTF`, *etc.*) by removing trailing *<tokens>* and the end marker `\q_stop`, inserting the *<code>* for the successful case (if one is found) and either the `true code` or `false code` for the over all outcome, as appropriate.

Part V

The l3expan package

Argument expansion

This module provides generic methods for expanding T_EX arguments in a systematic manner. The functions in this module all have prefix `exp`.

Not all possible variations are implemented for every base function. Instead only those that are used within the L^AT_EX3 kernel or otherwise seem to be of general interest are implemented. Consult the module description to find out which functions are actually defined. The next section explains how to define missing variants.

1 Defining new variants

The definition of variant forms for base functions may be necessary when writing new functions or when applying a kernel function in a situation that we haven't thought of before.

Internally preprocessing of arguments is done with functions from the `\exp_` module. They all look alike, an example would be `\exp_args:NNo`. This function has three arguments, the first and the second are a single tokens, while the third argument should be given in braces. Applying `\exp_args:NNo` will expand the content of third argument once before any expansion of the first and second arguments. If `\seq_gpush:No` was not defined it could be coded in the following way:

```
\exp_args:NNo \seq_gpush:Nn
  \g_file_name_stack
  \l_tmpa_tl
```

In other words, the first argument to `\exp_args:NNo` is the base function and the other arguments are preprocessed and then passed to this base function. In the example the first argument to the base function should be a single token which is left unchanged while the second argument is expanded once. From this example we can also see how the variants are defined. They just expand into the appropriate `\exp_` function followed by the desired base function, *e.g.*

```
\cs_generate_variant:Nn \seq_gpush:Nn { No }
```

results in the definition of `\seq_gpush:No`

```
\cs_new:Npn \seq_gpush:No { \exp_args:NNo \seq_gpush:Nn }
```

Providing variants in this way in style files is uncritical as the `\cs_generate_variant:Nn` function will only create new definitions if there is not already one available. Therefore adding such definition to later releases of the kernel will not make such style files obsolete.

The steps above may be automated by using the function `\cs_generate_variant:Nn`, described next.

2 Methods for defining variants

`\cs_generate_variant:Nn`

Updated: 2015-08-06

`\cs_generate_variant:Nn` \langle parent control sequence \rangle $\{$ \langle variant argument specifiers \rangle $\}$

This function is used to define argument-specifier variants of the \langle parent control sequence \rangle for L^AT_EX3 code-level macros. The \langle parent control sequence \rangle is first separated into the \langle base name \rangle and \langle original argument specifier \rangle . The comma-separated list of \langle variant argument specifiers \rangle is then used to define variants of the \langle original argument specifier \rangle where these are not already defined. For each \langle variant \rangle given, a function is created which will expand its arguments as detailed and pass them to the \langle parent control sequence \rangle . So for example

```
\cs_set:Npn \foo:Nn #1#2 { code here }
\cs_generate_variant:Nn \foo:Nn { c }
```

will create a new function `\foo:cn` which will expand its first argument into a control sequence name and pass the result to `\foo:Nn`. Similarly

```
\cs_generate_variant:Nn \foo:Nn { NV ,cV }
```

would generate the functions `\foo:NV` and `\foo:cV` in the same way. The `\cs_generate_variant:Nn` function can only be applied if the \langle parent control sequence \rangle is already defined. Only `n` and `N` arguments can be changed to other types. If the \langle parent control sequence \rangle is protected or if the \langle variant \rangle involves `x` arguments, then the \langle variant control sequence \rangle will also be protected. The \langle variant \rangle is created globally, as is any `\exp_args:N \langle variant \rangle` function needed to carry out the expansion.

3 Introducing the variants

The available internal functions for argument expansion come in two flavours, some of them are faster than others. Therefore (when speed is important) it is usually best to follow the following guidelines when defining new functions that are supposed to come with variant forms:

- Arguments that might need expansion should come first in the list of arguments to make processing faster.
- Arguments that should consist of single tokens should come first.
- Arguments that need full expansion (*i.e.*, are denoted with `x`) should be avoided if possible as they can not be processed expandably, *i.e.*, functions of this type will not work correctly in arguments that are themselves subject to `x` expansion.
- In general, unless in the last position, multi-token arguments `n`, `f`, and `o` will need special processing when more than one argument is being expanded. This special processing is not fast. Therefore it is best to use the optimized functions, namely those that contain only `N`, `c`, `V`, and `v`, and, in the last position, `o`, `f`, with possible trailing `N` or `n`, which are not expanded.

The `V` type returns the value of a register, which can be one of `tl`, `int`, `skip`, `dim`, `toks`, or built-in T_EX registers. The `v` type is the same except it first creates a control sequence out of its argument before returning the value.

In general, the programmer should not need to be concerned with expansion control. When simply using the content of a variable, functions with a `V` specifier should be used. For those referred to by `(cs)name`, the `v` specifier is available for the same purpose. Only when specific expansion steps are needed, such as when using delimited arguments, should the lower-level functions with `o` specifiers be employed.

The `f` type is so special that it deserves an example. It is typically used in contexts where only expandable commands are allowed. Then `x`-expansion cannot be used, and `f`-expansion provides an alternative that expands as much as can be done in such contexts. For instance, say that we want to evaluate the integer expression `3+4` and pass the result `7` as an argument to an expandable function `\example:n`. For this, one should define a variant using `\cs_generate_variant:Nn \example:n { f }`, then do

```
\example:f { \int_eval:n { 3 + 4 } }
```

Note that `x`-expansion would also expand `\int_eval:n` fully to its result `7`, but the variant `\example:x` cannot be expandable. Note also that `o`-expansion would not expand `\int_eval:n` fully to its result since that function requires several expansions. Besides the fact that `x`-expansion is protected rather than expandable, another difference between `f`-expansion and `x`-expansion is that `f`-expansion expands tokens from the beginning and stops as soon as a non-expandable token is encountered, while `x`-expansion continues expanding further tokens. Thus, for instance

```
\example:f { \int_eval:n { 1 + 2 } , \int_eval:n { 3 + 4 } }
```

will result in the call `\example:n { 3 , \int_eval:n { 3 + 4 } }` while using `\example:x` instead results in `\example:n { 3 , 7 }` at the cost of being protected. If you use this type of expansion in conditional processing then you should stick to using `TF` type functions only as it does not try to finish any `\if... \fi:` itself!

It is important to note that both `f`- and `o`-type expansion are concerned with the expansion of tokens from left to right in their arguments. In particular, `o`-type expansion applies to the first *token* in the argument it receives: it is conceptually similar to

```
\exp_after:wN <base function> \exp_after:wN { <argument> }
```

At the same time, `f`-type expansion stops at the *emph*first non-expandable token. This means for example that both

```
\tl_set:N0 \l_tmpa_tl { { \g_tmpb_tl } }
```

and

```
\tl_set:Nf \l_tmpa_tl { { \g_tmpb_tl } }
```

leave `\g_tmpb_tl` unchanged: `{` is the first token in the argument and is non-expandable.

4 Manipulating the first argument

These functions are described in detail: expansion of multiple tokens follows the same rules but is described in a shorter fashion.

| | |
|--|--|
| <hr/> <code>\exp_args:No</code> ★ <hr/> | <code>\exp_args:No</code> $\langle function \rangle$ $\{\langle tokens \rangle\}$... |
| | This function absorbs two arguments (the $\langle function \rangle$ name and the $\langle tokens \rangle$). The $\langle tokens \rangle$ are expanded once, and the result is inserted in braces into the input stream <i>after</i> reinsertion of the $\langle function \rangle$. Thus the $\langle function \rangle$ may take more than one argument: all others will be left unchanged. |
| <hr/> <code>\exp_args:Nc</code> ★ <hr/> <code>\exp_args:cc</code> ★ <hr/> | <code>\exp_args:Nc</code> $\langle function \rangle$ $\{\langle tokens \rangle\}$ |
| | This function absorbs two arguments (the $\langle function \rangle$ name and the $\langle tokens \rangle$). The $\langle tokens \rangle$ are expanded until only characters remain, and are then turned into a control sequence. (An internal error will occur if such a conversion is not possible). The result is inserted into the input stream <i>after</i> reinsertion of the $\langle function \rangle$. Thus the $\langle function \rangle$ may take more than one argument: all others will be left unchanged. The <code>:cc</code> variant constructs the $\langle function \rangle$ name in the same manner as described for the $\langle tokens \rangle$. |
| <hr/> <code>\exp_args:Nv</code> ★ <hr/> | <code>\exp_args:Nv</code> $\langle function \rangle$ $\langle variable \rangle$ |
| | This function absorbs two arguments (the names of the $\langle function \rangle$ and the $\langle variable \rangle$). The content of the $\langle variable \rangle$ are recovered and placed inside braces into the input stream <i>after</i> reinsertion of the $\langle function \rangle$. Thus the $\langle function \rangle$ may take more than one argument: all others will be left unchanged. |
| <hr/> <code>\exp_args:Nv</code> ★ <hr/> | <code>\exp_args:Nv</code> $\langle function \rangle$ $\{\langle tokens \rangle\}$ |
| | This function absorbs two arguments (the $\langle function \rangle$ name and the $\langle tokens \rangle$). The $\langle tokens \rangle$ are expanded until only characters remain, and are then turned into a control sequence. (An internal error will occur if such a conversion is not possible). This control sequence should be the name of a $\langle variable \rangle$. The content of the $\langle variable \rangle$ are recovered and placed inside braces into the input stream <i>after</i> reinsertion of the $\langle function \rangle$. Thus the $\langle function \rangle$ may take more than one argument: all others will be left unchanged. |
| <hr/> <code>\exp_args:Nf</code> ★ <hr/> | <code>\exp_args:Nf</code> $\langle function \rangle$ $\{\langle tokens \rangle\}$ |
| | This function absorbs two arguments (the $\langle function \rangle$ name and the $\langle tokens \rangle$). The $\langle tokens \rangle$ are fully expanded until the first non-expandable token or space is found, and the result is inserted in braces into the input stream <i>after</i> reinsertion of the $\langle function \rangle$. Thus the $\langle function \rangle$ may take more than one argument: all others will be left unchanged. |
| <hr/> <code>\exp_args:Nx</code> <hr/> | <code>\exp_args:Nx</code> $\langle function \rangle$ $\{\langle tokens \rangle\}$ |
| | This function absorbs two arguments (the $\langle function \rangle$ name and the $\langle tokens \rangle$) and exhaustively expands the $\langle tokens \rangle$ second. The result is inserted in braces into the input stream <i>after</i> reinsertion of the $\langle function \rangle$. Thus the $\langle function \rangle$ may take more than one argument: all others will be left unchanged. |

5 Manipulating two arguments

| | |
|------------------------------|--|
| <hr/> | |
| <code>\exp_args:NNo</code> * | <code>\exp_args:NNo <token> {<tokens>}</code> |
| <code>\exp_args:Nnc</code> * | |
| <code>\exp_args:Nnv</code> * | These optimized functions absorb three arguments and expand the second and third as detailed by their argument specifier. The first argument of the function is then the next item on the input stream, followed by the expansion of the second and third arguments. |
| <code>\exp_args:NNf</code> * | |
| <code>\exp_args:Nco</code> * | |
| <code>\exp_args:Ncf</code> * | |
| <code>\exp_args:Ncc</code> * | |
| <code>\exp_args:NVV</code> * | |
| <hr/> | |
| <code>\exp_args:Nno</code> * | <code>\exp_args:Nno <token> {<tokens>} {<tokens>}</code> |
| <code>\exp_args:NnV</code> * | |
| <code>\exp_args:Nnf</code> * | These functions absorb three arguments and expand the second and third as detailed by their argument specifier. The first argument of the function is then the next item on the input stream, followed by the expansion of the second and third arguments. These functions need special (slower) processing. |
| <code>\exp_args:Noo</code> * | |
| <code>\exp_args:Nof</code> * | |
| <code>\exp_args:Noc</code> * | |
| <code>\exp_args:Nff</code> * | |
| <code>\exp_args:Nfo</code> * | |
| <code>\exp_args:Nnc</code> * | |
| <hr/> | |
| Updated: 2012-01-14 | |
| <hr/> | |
| <code>\exp_args:NNx</code> | <code>\exp_args:NNx <token> {<tokens>}</code> |
| <code>\exp_args:Nnx</code> | |
| <code>\exp_args:Ncx</code> | These functions absorb three arguments and expand the second and third as detailed by their argument specifier. The first argument of the function is then the next item on the input stream, followed by the expansion of the second and third arguments. These functions are not expandable. |
| <code>\exp_args:Nox</code> | |
| <code>\exp_args:Nxo</code> | |
| <code>\exp_args:Nxx</code> | |
| <hr/> | |

6 Manipulating three arguments

| | |
|-------------------------------|--|
| <hr/> | |
| <code>\exp_args:NNNo</code> * | <code>\exp_args:NNNo <token> {<tokens>}</code> |
| <code>\exp_args:NNNV</code> * | |
| <code>\exp_args:Nccc</code> * | These optimized functions absorb four arguments and expand the second, third and fourth as detailed by their argument specifier. The first argument of the function is then the next item on the input stream, followed by the expansion of the second argument, <i>etc.</i> |
| <code>\exp_args:NcNc</code> * | |
| <code>\exp_args:NcNo</code> * | |
| <code>\exp_args:Ncco</code> * | |
| <hr/> | |
| <code>\exp_args:NNoo</code> * | <code>\exp_args:NNoo <token> {<tokens>} {<tokens>}</code> |
| <code>\exp_args:NNno</code> * | |
| <code>\exp_args:Nnno</code> * | These functions absorb four arguments and expand the second, third and fourth as detailed by their argument specifier. The first argument of the function is then the next item on the input stream, followed by the expansion of the second argument, <i>etc.</i> These functions need special (slower) processing. |
| <code>\exp_args:Nnnc</code> * | |
| <code>\exp_args:Nooo</code> * | |
| <hr/> | |

| | | |
|-----------------------------|-----------------------------|--|
| <code>\exp_args:NNNx</code> | <code>\exp_args:NNnx</code> | <code>\langle token_1 \rangle \langle token_2 \rangle \{\langle tokens_1 \rangle\} \{\langle tokens_2 \rangle\}</code> |
| <code>\exp_args:NNnx</code> | | |
| <code>\exp_args:NNox</code> | | |
| <code>\exp_args:Nnnx</code> | | |
| <code>\exp_args:Nnox</code> | | |
| <code>\exp_args:Noox</code> | | |
| <code>\exp_args:Ncnx</code> | | |
| <code>\exp_args:Nccx</code> | | |

New: 2015-08-12

7 Unbraced expansion

| | | | |
|---|---|-------------------------------------|--|
| <code>\exp_last_unbraced:Nv</code> | ★ | <code>\exp_last_unbraced:Nno</code> | <code>\langle token \rangle \langle tokens_1 \rangle \langle tokens_2 \rangle</code> |
| <code>\exp_last_unbraced:(Nf No Nv)</code> | ★ | | |
| <code>\exp_last_unbraced:Nco</code> | ★ | | |
| <code>\exp_last_unbraced:(NcV NNV NNo)</code> | ★ | | |
| <code>\exp_last_unbraced:Nno</code> | ★ | | |
| <code>\exp_last_unbraced:(Noo Nfo)</code> | ★ | | |
| <code>\exp_last_unbraced:NNNV</code> | ★ | | |
| <code>\exp_last_unbraced:NNNo</code> | ★ | | |
| <code>\exp_last_unbraced:NnNo</code> | ★ | | |

Updated: 2012-02-12

These functions absorb the number of arguments given by their specification, carry out the expansion indicated and leave the results in the input stream, with the last argument not surrounded by the usual braces. Of these, the `:Nno`, `:Noo`, and `:Nfo` variants need special (slower) processing.

TeXhackers note: As an optimization, the last argument is unbraced by some of those functions before expansion. This can cause problems if the argument is empty: for instance, `\exp_last_unbraced:Nf \foo_bar:w { } \q_stop` leads to an infinite loop, as the quark is `f`-expanded.

| | | |
|------------------------------------|------------------------------------|--|
| <code>\exp_last_unbraced:Nx</code> | <code>\exp_last_unbraced:Nx</code> | <code>\langle function \rangle \{\langle tokens \rangle\}</code> |
|------------------------------------|------------------------------------|--|

This functions fully expands the `\langle tokens \rangle` and leaves the result in the input stream after reinsertion of `\langle function \rangle`. This function is not expandable.

| | | | |
|---|---|---|--|
| <code>\exp_last_two_unbraced:Noo</code> | ★ | <code>\exp_last_two_unbraced:Noo</code> | <code>\langle token \rangle \langle tokens_1 \rangle \{\langle tokens_2 \rangle\}</code> |
|---|---|---|--|

This function absorbs three arguments and expand the second and third once. The first argument of the function is then the next item on the input stream, followed by the expansion of the second and third arguments, which are not wrapped in braces. This function needs special (slower) processing.

`\exp_after:wN` ★**`\exp_after:wN`** $\langle token_1 \rangle$ $\langle token_2 \rangle$

Carries out a single expansion of $\langle token_2 \rangle$ (which may consume arguments) prior to the expansion of $\langle token_1 \rangle$. If $\langle token_2 \rangle$ is a \TeX primitive, it will be executed rather than expanded, while if $\langle token_2 \rangle$ has not expansion (for example, if it is a character) then it will be left unchanged. It is important to notice that $\langle token_1 \rangle$ may be *any* single token, including group-opening and -closing tokens ($\{$ or $\}$ assuming normal \TeX category codes). Unless specifically required, expansion should be carried out using an appropriate argument specifier variant or the appropriate `\exp_arg:N` function.

\TeX hackers note: This is the \TeX primitive `\expandafter` renamed.

8 Preventing expansion

Despite the fact that the following functions are all about preventing expansion, they're designed to be used in an expandable context and hence are all marked as being 'expandable' since they themselves will not appear after the expansion has completed.

`\exp_not:N` ★**`\exp_not:N`** $\langle token \rangle$

Prevents expansion of the $\langle token \rangle$ in a context where it would otherwise be expanded, for example an \mathbf{x} -type argument.

\TeX hackers note: This is the \TeX `\noexpand` primitive.

`\exp_not:c` ★**`\exp_not:c`** $\{\langle tokens \rangle\}$

Expands the $\langle tokens \rangle$ until only unexpandable content remains, and then converts this into a control sequence. Further expansion of this control sequence is then inhibited.

`\exp_not:n` ★**`\exp_not:n`** $\{\langle tokens \rangle\}$

Prevents expansion of the $\langle tokens \rangle$ in a context where they would otherwise be expanded, for example an \mathbf{x} -type argument.

\TeX hackers note: This is the ε - \TeX `\unexpanded` primitive. Hence its argument *must* be surrounded by braces.

`\exp_not:V` ★**`\exp_not:V`** $\langle variable \rangle$

Recovers the content of the $\langle variable \rangle$, then prevents expansion of this material in a context where it would otherwise be expanded, for example an \mathbf{x} -type argument.

`\exp_not:v` ★**`\exp_not:v`** $\{\langle tokens \rangle\}$

Expands the $\langle tokens \rangle$ until only unexpandable content remains, and then converts this into a control sequence (which should be a $\langle variable \rangle$ name). The content of the $\langle variable \rangle$ is recovered, and further expansion is prevented in a context where it would otherwise be expanded, for example an \mathbf{x} -type argument.

| | |
|-----------------------------------|--|
| <hr/> <code>\exp_not:o</code> ★ | <code>\exp_not:o {⟨tokens⟩}</code> |
| | Expands the <i>⟨tokens⟩</i> once, then prevents any further expansion in a context where they would otherwise be expanded, for example an <i>x</i> -type argument. |
| <hr/> <code>\exp_not:f</code> ★ | <code>\exp_not:f {⟨tokens⟩}</code> |
| | Expands <i>⟨tokens⟩</i> fully until the first unexpandable token is found. Expansion then stops, and the result of the expansion (including any tokens which were not expanded) is protected from further expansion. |
| <hr/> <code>\exp_stop_f:</code> ★ | <code>\foo_bar:f { ⟨tokens⟩ \exp_stop_f: ⟨more tokens⟩ }</code> |
| <hr/> Updated: 2011-06-03 <hr/> | This function terminates an <i>f</i> -type expansion. Thus if a function <code>\foo_bar:f</code> starts an <i>f</i> -type expansion and all of <i>⟨tokens⟩</i> are expandable <code>\exp_stop_f:</code> will terminate the expansion of tokens even if <i>⟨more tokens⟩</i> are also expandable. The function itself is an implicit space token. Inside an <i>x</i> -type expansion, it will retain its form, but when typeset it produces the underlying space (␣). |

9 Controlled expansion

The `expl3` language makes all efforts to hide the complexity of \TeX expansion from the programmer by providing concepts that evaluate/expand arguments of functions prior to calling the “base” functions. Thus, instead of using many `\expandafter` calls and other trickery it is usually a matter of choosing the right variant of a function to achieve a desired result.

Of course, deep down \TeX is using expansion as always and there are cases where a programmer needs to control that expansion directly; typical situations are basic data manipulation tools. This section documents the functions for that level. You will find these commands used throughout the kernel code, but we hope that outside the kernel there will be little need to resort to them. Instead the argument manipulation methods document above should usually be sufficient.

While `\exp_after:wN` expands one token (out of order) it is sometimes necessary to expand several tokens in one go. The next set of commands provide this functionality. Be aware that it is absolutely required that the programmer has full control over the tokens to be expanded, i.e., it is not possible to use these functions to expand unknown input as part of *⟨expandable-tokens⟩* as that will break badly if unexpandable tokens are encountered in that place!

| | |
|-----------------------------|---|
| <hr/> <code>\exp:w</code> ★ | <code>\exp:w ⟨expandable-tokens⟩ \exp_end:</code> |
| <code>\exp_end:</code> ★ | Expands <i>⟨expandable-tokens⟩</i> until reaching <code>\exp_end:</code> at which point expansion stops. |
| <hr/> New: 2015-08-23 <hr/> | The full expansion of <i>⟨expandable-tokens⟩</i> has to be empty. If any token in <i>⟨expandable-tokens⟩</i> or any token generated by expanding the tokens therein is not expandable the expansion will end prematurely and as a result <code>\exp_end:</code> will be misinterpreted later on. ² |
| | In typical use cases the <code>\exp_end:</code> will be hidden somewhere in the replacement text of <i>⟨expandable-tokens⟩</i> rather than being on the same expansion level than <code>\exp:w</code> , e.g., you may see code such as |

```
\exp:w \@@_case:NnTF #1 {#2} { } { }
```

where somewhere during the expansion of `\@@_case:NnTF` the `\exp_end:` gets generated.

| | |
|------------------------------------|---|
| <code>\exp:w</code> | ★ |
| <code>\exp_end_continue_f:w</code> | ★ |

New: 2015-08-23

`\exp:w` $\langle expandable-tokens \rangle$ `\exp_end_continue_f:w` $\langle further-tokens \rangle$

Expands $\langle expandable-tokens \rangle$ until reaching `\exp_end_continue_f:w` at which point expansion continues as an f-type expansion expanding $\langle further-tokens \rangle$ until an unexpandable token is encountered (or the f-type expansion is explicitly terminated by `\exp_stop_f:`). As with all f-type expansions a space ending the expansion will get removed.

The full expansion of $\langle expandable-tokens \rangle$ has to be empty. If any token in $\langle expandable-tokens \rangle$ or any token generated by expanding the tokens therein is not expandable the expansion will end prematurely and as a result `\exp_end_continue_f:w` will be misinterpreted later on.³

In typical use cases $\langle expandable-tokens \rangle$ contains no tokens at all, e.g., you will see code such as

`\exp_after:wN { \exp:w \exp_end_continue_f:w #2 }`

where the `\exp_after:wN` triggers an f-expansion of the tokens in #2. For technical reasons this has to happen using two tokens (if they would be hidden inside another command `\exp_after:wN` would only expand the command but not trigger any additional f-expansion).

You might wonder why there are two different approaches available, after all the effect of

`\exp:w` $\langle expandable-tokens \rangle$ `\exp_end:`

can be alternatively achieved through an f-type expansion by using `\exp_stop_f:`, i.e.

`\exp:w \exp_end_continue_f:w` $\langle expandable-tokens \rangle$ `\exp_stop_f:`

The reason is simply that the first approach is slightly faster (one less token to parse and less expansion internally) so in places where such performance really matters and where we want to explicitly stop the expansion at a defined point the first form is preferable.

| | |
|-------------------------------------|---|
| <code>\exp:w</code> | ★ |
| <code>\exp_end_continue_f:nw</code> | ★ |

New: 2015-08-23

`\exp:w` $\langle expandable-tokens \rangle$ `\exp_end_continue_f:nw` $\langle further-tokens \rangle$

The difference to `\exp_end_continue_f:w` is that we first we pick up an argument which is then returned to the input stream. If $\langle further-tokens \rangle$ starts with a brace group then the braces are removed. If on the other hand it starts with space tokens then these space tokens are removed while searching for the argument. Thus such space tokens will not terminate the f-type expansion.

10 Internal functions and variables

`\l__exp_internal_tl`

The `\exp_` module has its private variables to temporarily store results of the argument expansion. This is done to avoid interference with other functions using temporary variables.

²Due to the implementation you might get the character in position 0 in the current font (typically “‘”) in the output without any error message!

³In this particular case you may get a character into the output as well as an error message.

```

\::n \cs_set:Npn \exp_args:Ncof { \::c \::o \::f \::: }
\::N
\::p Internal forms for the base expansion types. These names do not conform to the general
\::c LATEX3 approach as this makes them more readily visible in the log and so forth.
\::o
\::f
\::x
\::v
\::V
\:::

```

Part VI

The l3tl package

Token lists

T_EX works with tokens, and L^AT_EX3 therefore provides a number of functions to deal with lists of tokens. Token lists may be present directly in the argument to a function:

```
\foo:n { a collection of \tokens }
```

or may be stored in a so-called “token list variable”, which have the suffix `tl`: a token list variable can also be used as the argument to a function, for example

```
\foo:N \l_some_tl
```

In both cases, functions are available to test and manipulate the lists of tokens, and these have the module prefix `tl`. In many cases, function which can be applied to token list variables are paired with similar functions for application to explicit lists of tokens: the two “views” of a token list are therefore collected together here.

A token list (explicit, or stored in a variable) can be seen either as a list of “items”, or a list of “tokens”. An item is whatever `\use:n` would grab as its argument: a single non-space token or a brace group, with optional leading explicit space characters (each item is thus itself a token list). A token is either a normal `N` argument, or `␣`, `{`, or `}` (assuming normal T_EX category codes). Thus for example

```
{ Hello } ~ world
```

contains six items (Hello, w, o, r, l and d), but thirteen tokens (`{`, H, e, l, l, o, `}`, `␣`, w, o, r, l and d). Functions which act on items are often faster than their analogue acting directly on tokens.

1 Creating and initialising token list variables

```
\tl_new:N \tl_new:c
```

Creates a new $\langle tl\ var \rangle$ or raises an error if the name is already taken. The declaration is global. The $\langle tl\ var \rangle$ will initially be empty.

```
\tl_const:Nn \tl_const:(Nx|cn|cx)
```

Creates a new constant $\langle tl\ var \rangle$ or raises an error if the name is already taken. The value of the $\langle tl\ var \rangle$ will be set globally to the $\langle token\ list \rangle$.

```
\tl_clear:N \tl_clear:c \tl_gclear:N \tl_gclear:c
```

Clears all entries from the $\langle tl\ var \rangle$.

| | |
|-------------------------------------|---|
| <hr/> | |
| <code>\tl_clear_new:N</code> | <code>\tl_clear_new:N <tl var></code> |
| <code>\tl_clear_new:c</code> | |
| <code>\tl_gclear_new:N</code> | Ensures that the $\langle tl\ var \rangle$ exists globally by applying <code>\tl_new:N</code> if necessary, then applies |
| <code>\tl_gclear_new:c</code> | <code>\tl_(g)clear:N</code> to leave the $\langle tl\ var \rangle$ empty. |
| <hr/> | |
| <code>\tl_set_eq:NN</code> | <code>\tl_set_eq:NN <tl var₁> <tl var₂></code> |
| <code>\tl_set_eq:(cN Nc cc)</code> | Sets the content of $\langle tl\ var_1 \rangle$ equal to that of $\langle tl\ var_2 \rangle$. |
| <code>\tl_gset_eq:NN</code> | |
| <code>\tl_gset_eq:(cN Nc cc)</code> | |
| <hr/> | |
| <code>\tl_concat:NNN</code> | <code>\tl_concat:NNN <tl var₁> <tl var₂> <tl var₃></code> |
| <code>\tl_concat:ccc</code> | |
| <code>\tl_gconcat:NNN</code> | Concatenates the content of $\langle tl\ var_2 \rangle$ and $\langle tl\ var_3 \rangle$ together and saves the result in |
| <code>\tl_gconcat:ccc</code> | $\langle tl\ var_1 \rangle$. The $\langle tl\ var_2 \rangle$ will be placed at the left side of the new token list. |
| <hr/> | |
| New: 2012-05-18 | |
| <hr/> | |
| <code>\tl_if_exist_p:N *</code> | <code>\tl_if_exist_p:N <tl var></code> |
| <code>\tl_if_exist_p:c *</code> | <code>\tl_if_exist:NTF <tl var> {\true code} {\false code}</code> |
| <code>\tl_if_exist:NTF *</code> | |
| <code>\tl_if_exist:cTF *</code> | Tests whether the $\langle tl\ var \rangle$ is currently defined. This does not check that the $\langle tl\ var \rangle$ really is a token list variable. |
| <hr/> | |
| New: 2012-03-03 | |

2 Adding data to token list variables

| | |
|---|--|
| <hr/> | |
| <code>\tl_set:Nn</code> | <code>\tl_set:Nn <tl var> {\tokens}</code> |
| <code>\tl_set:(NV Nv No Nf Nx cn cV cv co cf cx)</code> | |
| <code>\tl_gset:Nn</code> | |
| <code>\tl_gset:(NV Nv No Nf Nx cn cV cv co cf cx)</code> | |
| <hr/> | |
| Sets $\langle tl\ var \rangle$ to contain $\langle tokens \rangle$, removing any previous content from the variable. | |
| <hr/> | |
| <code>\tl_put_left:Nn</code> | <code>\tl_put_left:Nn <tl var> {\tokens}</code> |
| <code>\tl_put_left:(NV No Nx cn cV co cx)</code> | |
| <code>\tl_gput_left:Nn</code> | |
| <code>\tl_gput_left:(NV No Nx cn cV co cx)</code> | |
| <hr/> | |
| Appends $\langle tokens \rangle$ to the left side of the current content of $\langle tl\ var \rangle$. | |
| <hr/> | |
| <code>\tl_put_right:Nn</code> | <code>\tl_put_right:Nn <tl var> {\tokens}</code> |
| <code>\tl_put_right:(NV No Nx cn cV co cx)</code> | |
| <code>\tl_gput_right:Nn</code> | |
| <code>\tl_gput_right:(NV No Nx cn cV co cx)</code> | |
| <hr/> | |
| Appends $\langle tokens \rangle$ to the right side of the current content of $\langle tl\ var \rangle$. | |

3 Modifying token list variables

```
\tl_replace_once:Nnn
\tl_replace_once:cnn
\tl_greplace_once:Nnn
\tl_greplace_once:cnn
```

Updated: 2011-08-11

```
\tl_replace_once:Nnn <tl var> {{<old tokens>}} {{<new tokens>}}
```

Replaces the first (leftmost) occurrence of *<old tokens>* in the *<tl var>* with *<new tokens>*. *<Old tokens>* cannot contain `{`, `}` or `#` (more precisely, explicit character tokens with category code 1 (begin-group) or 2 (end-group), and tokens with category code 6).

```
\tl_replace_all:Nnn
\tl_replace_all:cnn
\tl_greplace_all:Nnn
\tl_greplace_all:cnn
```

Updated: 2011-08-11

```
\tl_replace_all:Nnn <tl var> {{<old tokens>}} {{<new tokens>}}
```

Replaces all occurrences of *<old tokens>* in the *<tl var>* with *<new tokens>*. *<Old tokens>* cannot contain `{`, `}` or `#` (more precisely, explicit character tokens with category code 1 (begin-group) or 2 (end-group), and tokens with category code 6). As this function operates from left to right, the pattern *<old tokens>* may remain after the replacement (see `\tl_remove_all:Nn` for an example).

```
\tl_remove_once:Nn
\tl_remove_once:cn
\tl_gremove_once:Nn
\tl_gremove_once:cn
```

Updated: 2011-08-11

```
\tl_remove_once:Nn <tl var> {{<tokens>}}
```

Removes the first (leftmost) occurrence of *<tokens>* from the *<tl var>*. *<Tokens>* cannot contain `{`, `}` or `#` (more precisely, explicit character tokens with category code 1 (begin-group) or 2 (end-group), and tokens with category code 6).

```
\tl_remove_all:Nn
\tl_remove_all:cn
\tl_gremove_all:Nn
\tl_gremove_all:cn
```

Updated: 2011-08-11

```
\tl_remove_all:Nn <tl var> {{<tokens>}}
```

Removes all occurrences of *<tokens>* from the *<tl var>*. *<Tokens>* cannot contain `{`, `}` or `#` (more precisely, explicit character tokens with category code 1 (begin-group) or 2 (end-group), and tokens with category code 6). As this function operates from left to right, the pattern *<tokens>* may remain after the removal, for instance,

```
\tl_set:Nn \l_tmpa_tl {abbccd} \tl_remove_all:Nn \l_tmpa_tl {bc}
```

will result in `\l_tmpa_tl` containing `abcd`.

4 Reassigning token list category codes

These functions allow the rescanning of tokens: re-apply T_EX's tokenization process to apply category codes different from those in force when the tokens were absorbed. Whilst this functionality is supported, it is often preferable to find alternative approaches to achieving outcomes rather than rescanning tokens (for example construction of token lists token-by-token with intervening category code changes).

| | |
|--|---|
| <code>\tl_set_rescan:Nnn</code> | <code>\tl_set_rescan:Nnn <tl var> {<setup>} {<tokens>}</code> |
| <code>\tl_set_rescan:(Nno Nnx cnn cno cnx)</code> | |
| <code>\tl_gset_rescan:Nnn</code> | |
| <code>\tl_gset_rescan:(Nno Nnx cnn cno cnx)</code> | |

Updated: 2015-08-11

Sets $\langle tl\ var\rangle$ to contain $\langle tokens\rangle$, applying the category code régime specified in the $\langle setup\rangle$ before carrying out the assignment. (Category codes applied to tokens not explicitly covered by the $\langle setup\rangle$ will be those in force at the point of use of `\tl_set_rescan:Nnn`.) This allows the $\langle tl\ var\rangle$ to contain material with category codes other than those that apply when $\langle tokens\rangle$ are absorbed. The $\langle setup\rangle$ is run within a group and may contain any valid input, although only changes in category codes are relevant. See also `\tl_rescan:nn`.

TeXhackers note: The $\langle tokens\rangle$ are first turned into a string (using `\tl_to_str:n`). If the string contains one or more characters with character code `\newlinechar` (set equal to `\endlinechar` unless that is equal to 32, before the user $\langle setup\rangle$), then it is split into lines at these characters, then read as if reading multiple lines from a file, ignoring spaces (catcode 10) at the beginning and spaces and tabs (character code 32 or 9) at the end of every line. Otherwise, spaces (and tabs) are retained at both ends of the single-line string, as if it appeared in the middle of a line read from a file. Only the case of a single line is supported in LuaTeX because of a bug in this engine.

| | |
|----------------------------|---|
| <code>\tl_rescan:nn</code> | <code>\tl_rescan:nn {<setup>} {<tokens>}</code> |
|----------------------------|---|

Updated: 2015-08-11

Rescans $\langle tokens\rangle$ applying the category code régime specified in the $\langle setup\rangle$, and leaves the resulting tokens in the input stream. (Category codes applied to tokens not explicitly covered by the $\langle setup\rangle$ will be those in force at the point of use of `\tl_rescan:nn`.) The $\langle setup\rangle$ is run within a group and may contain any valid input, although only changes in category codes are relevant. See also `\tl_set_rescan:Nnn`, which is more robust than using `\tl_set:Nn` in the $\langle tokens\rangle$ argument of `\tl_rescan:nn`.

TeXhackers note: The $\langle tokens\rangle$ are first turned into a string (using `\tl_to_str:n`). If the string contains one or more characters with character code `\newlinechar` (set equal to `\endlinechar` unless that is equal to 32, before the user $\langle setup\rangle$), then it is split into lines at these characters, then read as if reading multiple lines from a file, ignoring spaces (catcode 10) at the beginning and spaces and tabs (character code 32 or 9) at the end of every line. Otherwise, spaces (and tabs) are retained at both ends of the single-line string, as if it appeared in the middle of a line read from a file. Only the case of a single line is supported in LuaTeX because of a bug in this engine.

5 Token list conditionals

| | | |
|-----------------------------------|---|---|
| <code>\tl_if_blank_p:n</code> | ★ | <code>\tl_if_blank_p:n {<token list>}</code> |
| <code>\tl_if_blank_p:(V o)</code> | ★ | <code>\tl_if_blank:nTF {<token list>} {<true code>} {<false code>}</code> |
| <code>\tl_if_blank:nTF</code> | ★ | |
| <code>\tl_if_blank:(V o)TF</code> | ★ | |

Tests if the $\langle token\ list\rangle$ consists only of blank spaces (*i.e.* contains no item). The test is **true** if $\langle token\ list\rangle$ is zero or more explicit space characters (explicit tokens with character code 32 and category code 10), and is **false** otherwise.

| | | |
|-------------------------------|---|---|
| <code>\tl_if_empty_p:N</code> | ★ | <code>\tl_if_empty_p:N <tl var></code> |
| <code>\tl_if_empty_p:c</code> | ★ | <code>\tl_if_empty:NNTF <tl var> {<true code>} {<false code>}</code> |
| <code>\tl_if_empty:nTF</code> | ★ | Tests if the <i><token list variable></i> is entirely empty (<i>i.e.</i> contains no tokens at all). |
| <code>\tl_if_empty:cTF</code> | ★ | |

| | | |
|-----------------------------------|---|--|
| <code>\tl_if_empty_p:n</code> | ★ | <code>\tl_if_empty_p:n {<token list>}</code> |
| <code>\tl_if_empty_p:(V o)</code> | ★ | <code>\tl_if_empty:nNTF {<token list>} {<true code>} {<false code>}</code> |
| <code>\tl_if_empty:nTF</code> | ★ | Tests if the <i><token list></i> is entirely empty (<i>i.e.</i> contains no tokens at all). |
| <code>\tl_if_empty:(V o)TF</code> | ★ | |

New: 2012-05-24
Updated: 2012-06-05

| | | |
|-------------------------------------|---|---|
| <code>\tl_if_eq_p:NN</code> | ★ | <code>\tl_if_eq_p:NN <tl var₁> <tl var₂></code> |
| <code>\tl_if_eq_p:(Nc cN cc)</code> | ★ | <code>\tl_if_eq:NNTF <tl var₁> <tl var₂> {<true code>} {<false code>}</code> |
| <code>\tl_if_eq:NNTF</code> | ★ | Compares the content of two <i><token list variables></i> and is logically true if the two contain the same list of tokens (<i>i.e.</i> identical in both the list of characters they contain and the category codes of those characters). Thus for example |
| <code>\tl_if_eq:(Nc cN cc)TF</code> | ★ | |

```

\tl_set:Nn \l_tmpa_tl { abc }
\tl_set:Nx \l_tmpb_tl { \tl_to_str:n { abc } }
\tl_if_eq:NNTF \l_tmpa_tl \l_tmpb_tl { true } { false }

```

yields **false**.

| | | |
|-----------------------------|---|--|
| <code>\tl_if_eq:nnTF</code> | ★ | <code>\tl_if_eq:nnTF {<token list₁>} {<token list₂>} {<true code>} {<false code>}</code> |
|-----------------------------|---|--|

Tests if *<token list₁>* and *<token list₂>* contain the same list of tokens, both in respect of character codes and category codes.

| | | |
|-----------------------------|---|---|
| <code>\tl_if_in:NnTF</code> | ★ | <code>\tl_if_in:NnTF <tl var> {<token list>} {<true code>} {<false code>}</code> |
| <code>\tl_if_in:cnTF</code> | ★ | Tests if the <i><token list></i> is found in the content of the <i><tl var></i> . The <i><token list></i> cannot contain the tokens <code>{</code> , <code>}</code> or <code>#</code> (more precisely, explicit character tokens with category code 1 (begin-group) or 2 (end-group), and tokens with category code 6). |

| | | |
|-------------------------------------|---|--|
| <code>\tl_if_in:nnTF</code> | ★ | <code>\tl_if_in:nnTF {<token list₁>} {<token list₂>} {<true code>} {<false code>}</code> |
| <code>\tl_if_in:(Vn on no)TF</code> | ★ | Tests if <i><token list₂></i> is found inside <i><token list₁></i> . The <i><token list₂></i> cannot contain the tokens <code>{</code> , <code>}</code> or <code>#</code> (more precisely, explicit character tokens with category code 1 (begin-group) or 2 (end-group), and tokens with category code 6). |

| | | |
|---------------------------------|---|---|
| <code>\tl_if_single_p:N</code> | ★ | <code>\tl_if_single_p:N <tl var></code> |
| <code>\tl_if_single_p:c</code> | ★ | <code>\tl_if_single:NNTF <tl var> {<true code>} {<false code>}</code> |
| <code>\tl_if_single:NNTF</code> | ★ | Tests if the content of the <i><tl var></i> consists of a single item, <i>i.e.</i> is a single normal token (neither an explicit space character nor a begin-group character) or a single brace group, surrounded by optional spaces on both sides. In other words, such a token list has token count 1 according to <code>\tl_count:N</code> . |
| <code>\tl_if_single:cTF</code> | ★ | |

Updated: 2011-08-13

| | |
|----------------------------------|--|
| <code>\tl_if_single_p:n</code> ★ | <code>\tl_if_single_p:n {⟨token list⟩}</code> |
| <code>\tl_if_single:nTF</code> ★ | <code>\tl_if_single:nTF {⟨token list⟩} {⟨true code⟩} {⟨false code⟩}</code> |

Updated: 2011-08-13

Tests if the *⟨token list⟩* has exactly one item, *i.e.* is a single normal token (neither an explicit space character nor a begin-group character) or a single brace group, surrounded by optional spaces on both sides. In other words, such a token list has token count 1 according to `\tl_count:n`.

| | |
|------------------------------|---|
| <code>\tl_case:Nn</code> ★ | <code>\tl_case:NnTF ⟨test token list variable⟩</code> |
| <code>\tl_case:cn</code> ★ | <code>{</code> |
| <code>\tl_case:NnTF</code> ★ | <code> ⟨token list variable case₁⟩ {⟨code case₁⟩}</code> |
| <code>\tl_case:cnTF</code> ★ | <code> ⟨token list variable case₂⟩ {⟨code case₂⟩}</code> |
| | <code> ...</code> |
| | <code> ⟨token list variable case_n⟩ {⟨code case_n⟩}</code> |
| | <code>}</code> |
| | <code>{⟨true code⟩}</code> |
| | <code>{⟨false code⟩}</code> |

New: 2013-07-24

This function compares the *⟨test token list variable⟩* in turn with each of the *⟨token list variable cases⟩*. If the two are equal (as described for `\tl_if_eq:NNTF`) then the associated *⟨code⟩* is left in the input stream. If any of the cases are matched, the *⟨true code⟩* is also inserted into the input stream (after the code for the appropriate case), while if none match then the *⟨false code⟩* is inserted. The function `\tl_case:Nn`, which does nothing if there is no match, is also available.

6 Mapping to token lists

| | |
|------------------------------------|--|
| <code>\tl_map_function:NN</code> ☆ | <code>\tl_map_function:NN ⟨tl var⟩ ⟨function⟩</code> |
| <code>\tl_map_function:cN</code> ☆ | |

Updated: 2012-06-29

Applies *⟨function⟩* to every *⟨item⟩* in the *⟨tl var⟩*. The *⟨function⟩* will receive one argument for each iteration. This may be a number of tokens if the *⟨item⟩* was stored within braces. Hence the *⟨function⟩* should anticipate receiving *n*-type arguments. See also `\tl_map_function:nN`.

| | |
|------------------------------------|--|
| <code>\tl_map_function:nN</code> ☆ | <code>\tl_map_function:nN ⟨token list⟩ ⟨function⟩</code> |
|------------------------------------|--|

Updated: 2012-06-29

Applies *⟨function⟩* to every *⟨item⟩* in the *⟨token list⟩*, The *⟨function⟩* will receive one argument for each iteration. This may be a number of tokens if the *⟨item⟩* was stored within braces. Hence the *⟨function⟩* should anticipate receiving *n*-type arguments. See also `\tl_map_function:NN`.

| | |
|--------------------------------|---|
| <code>\tl_map_inline:Nn</code> | <code>\tl_map_inline:Nn ⟨tl var⟩ {⟨inline function⟩}</code> |
| <code>\tl_map_inline:cn</code> | |

Updated: 2012-06-29

Applies the *⟨inline function⟩* to every *⟨item⟩* stored within the *⟨tl var⟩*. The *⟨inline function⟩* should consist of code which will receive the *⟨item⟩* as #1. One in line mapping can be nested inside another. See also `\tl_map_function:NN`.

| | |
|--------------------------------|---|
| <code>\tl_map_inline:nn</code> | <code>\tl_map_inline:nn ⟨token list⟩ {⟨inline function⟩}</code> |
|--------------------------------|---|

Updated: 2012-06-29

Applies the *⟨inline function⟩* to every *⟨item⟩* stored within the *⟨token list⟩*. The *⟨inline function⟩* should consist of code which will receive the *⟨item⟩* as #1. One in line mapping can be nested inside another. See also `\tl_map_function:nN`.

| | |
|-----------------------------------|---|
| <code>\tl_map_variable:NNn</code> | <code>\tl_map_variable:NNn <tl var> <variable> {<function>}</code> |
| <code>\tl_map_variable:cNn</code> | Applies the <i><function></i> to every <i><item></i> stored within the <i><tl var></i> . The <i><function></i> should consist of code which will receive the <i><item></i> stored in the <i><variable></i> . One variable mapping can be nested inside another. See also <code>\tl_map_inline:Nn</code> . |
| Updated: 2012-06-29 | |

| | |
|-----------------------------------|---|
| <code>\tl_map_variable:nNn</code> | <code>\tl_map_variable:nNn <token list> <variable> {<function>}</code> |
| Updated: 2012-06-29 | Applies the <i><function></i> to every <i><item></i> stored within the <i><token list></i> . The <i><function></i> should consist of code which will receive the <i><item></i> stored in the <i><variable></i> . One variable mapping can be nested inside another. See also <code>\tl_map_inline:nn</code> . |

| | |
|-------------------------------|--|
| <code>\tl_map_break: ☆</code> | <code>\tl_map_break:</code> |
| Updated: 2012-06-29 | Used to terminate a <code>\tl_map...</code> function before all entries in the <i><token list variable></i> have been processed. This will normally take place within a conditional statement, for example |

```

\tl_map_inline:Nn \l_my_tl
{
  \str_if_eq:nnT { #1 } { bingo } { \tl_map_break: }
  % Do something useful
}

```

See also `\tl_map_break:n`. Use outside of a `\tl_map...` scenario will lead to low level \TeX errors.

\TeX hackers note: When the mapping is broken, additional tokens may be inserted by the internal macro `__prg_break_point:Nn` before the *<tokens>* are inserted into the input stream. This will depend on the design of the mapping function.

| | |
|--------------------------------|---|
| <code>\tl_map_break:n ☆</code> | <code>\tl_map_break:n {<tokens>}</code> |
| Updated: 2012-06-29 | Used to terminate a <code>\tl_map...</code> function before all entries in the <i><token list variable></i> have been processed, inserting the <i><tokens></i> after the mapping has ended. This will normally take place within a conditional statement, for example |

```

\tl_map_inline:Nn \l_my_tl
{
  \str_if_eq:nnT { #1 } { bingo }
  { \tl_map_break:n { <tokens> } }
  % Do something useful
}

```

Use outside of a `\tl_map...` scenario will lead to low level \TeX errors.

\TeX hackers note: When the mapping is broken, additional tokens may be inserted by the internal macro `__prg_break_point:Nn` before the *<tokens>* are inserted into the input stream. This will depend on the design of the mapping function.

7 Using token lists

`\tl_to_str:n` ★ `\tl_to_str:n {⟨token list⟩}`

Converts the $\langle token\ list \rangle$ to a $\langle string \rangle$, leaving the resulting character tokens in the input stream. A $\langle string \rangle$ is a series of tokens with category code 12 (other) with the exception of spaces, which retain category code 10 (space).

TeXhackers note: Converting a $\langle token\ list \rangle$ to a $\langle string \rangle$ yields a concatenation of the string representations of every token in the $\langle token\ list \rangle$. The string representation of a control sequence is

- an escape character, whose character code is given by the internal parameter `\escapechar`, absent if the `\escapechar` is negative or greater than the largest character code;
- the control sequence name, as defined by `\cs_to_str:N`;
- a space, unless the control sequence name is a single character whose category at the time of expansion of `\tl_to_str:n` is not “letter”.

The string representation of an explicit character token is that character, doubled in the case of (explicit) macro parameter characters (normally `#`). In particular, the string representation of a token list may depend on the category codes in effect when it is evaluated, and the value of the `\escapechar`: for instance `\tl_to_str:n {\a}` normally produces the three character “backslash”, “lower-case a”, “space”, but it may also produce a single “lower-case a” if the escape character is negative and `a` is currently not a letter.

`\tl_to_str:N` ★ `\tl_to_str:N ⟨tl var⟩`

`\tl_to_str:c` ★
Converts the content of the $\langle tl\ var \rangle$ into a series of characters with category code 12 (other) with the exception of spaces, which retain category code 10 (space). This $\langle string \rangle$ is then left in the input stream. For low-level details, see the notes given for `\tl_to_str:n`.

`\tl_use:N` ★ `\tl_use:N ⟨tl var⟩`

`\tl_use:c` ★
Recovers the content of a $\langle tl\ var \rangle$ and places it directly in the input stream. An error will be raised if the variable does not exist or if it is invalid. Note that it is possible to use a $\langle tl\ var \rangle$ directly without an accessor function.

8 Working with the content of token lists

`\tl_count:n` ★ `\tl_count:n {⟨tokens⟩}`

`\tl_count:(V|o)` ★
Counts the number of $\langle items \rangle$ in $\langle tokens \rangle$ and leaves this information in the input stream. Unbraced tokens count as one element as do each token group $\{ \dots \}$. This process will ignore any unprotected spaces within $\langle tokens \rangle$. See also `\tl_count:N`. This function requires three expansions, giving an $\langle integer\ denotation \rangle$.

New: 2012-05-13

`\tl_count:N` ★
`\tl_count:c` ★

New: 2012-05-13

`\tl_count:N <tl var>`
Counts the number of token groups in the `<tl var>` and leaves this information in the input stream. Unbraced tokens count as one element as do each token group `{...}`. This process will ignore any unprotected spaces within the `<tl var>`. See also `\tl_count:n`. This function requires three expansions, giving an *<integer denotation>*.

`\tl_reverse:n` ★
`\tl_reverse:(V|o)` ★

Updated: 2012-01-08

`\tl_reverse:n {<token list>}`
Reverses the order of the *<items>* in the *<token list>*, so that *<item₁><item₂><item₃>...<item_n>* becomes *<item_n>...<item₃><item₂><item₁>*. This process will preserve unprotected space within the *<token list>*. Tokens are not reversed within braced token groups, which keep their outer set of braces. In situations where performance is important, consider `\tl_reverse_items:n`. See also `\tl_reverse:N`.

TeXhackers note: The result is returned within `\unexpanded`, which means that the token list will not expand further when appearing in an *x*-type argument expansion.

`\tl_reverse:N`
`\tl_reverse:c`
`\tl_greverse:N`
`\tl_greverse:c`

Updated: 2012-01-08

`\tl_reverse:N <tl var>`
Reverses the order of the *<items>* stored in *<tl var>*, so that *<item₁><item₂><item₃>...<item_n>* becomes *<item_n>...<item₃><item₂><item₁>*. This process will preserve unprotected spaces within the *<token list variable>*. Braced token groups are copied without reversing the order of tokens, but keep the outer set of braces. See also `\tl_reverse:n`, and, for improved performance, `\tl_reverse_items:n`.

`\tl_reverse_items:n` ★

New: 2012-01-08

`\tl_reverse_items:n {<token list>}`
Reverses the order of the *<items>* stored in *<tl var>*, so that *{<item₁>}{<item₂>}{<item₃>}...{<item_n>}* becomes *{<item_n>} ... {<item₃>}{<item₂>}{<item₁>}*. This process will remove any unprotected space within the *<token list>*. Braced token groups are copied without reversing the order of tokens, and keep the outer set of braces. Items which are initially not braced are copied with braces in the result. In cases where preserving spaces is important, consider the slower function `\tl_reverse:n`.

TeXhackers note: The result is returned within `\unexpanded`, which means that the token list will not expand further when appearing in an *x*-type argument expansion.

`\tl_trim_spaces:n` ★

New: 2011-07-09
Updated: 2012-06-25

`\tl_trim_spaces:n {<token list>}`
Removes any leading and trailing explicit space characters (explicit tokens with character code 32 and category code 10) from the *<token list>* and leaves the result in the input stream.

TeXhackers note: The result is returned within `\unexpanded`, which means that the token list will not expand further when appearing in an *x*-type argument expansion.

`\tl_trim_spaces:N`
`\tl_trim_spaces:c`
`\tl_gtrim_spaces:N`
`\tl_gtrim_spaces:c`

New: 2011-07-09

`\tl_trim_spaces:N <tl var>`
Removes any leading and trailing explicit space characters (explicit tokens with character code 32 and category code 10) from the content of the *<tl var>*. Note that this therefore *resets* the content of the variable.

| | |
|---------------------------|--|
| <code>\tl_sort:Nn</code> | <code>\tl_sort:Nn <tl var> {<comparison code>}</code> |
| <code>\tl_sort:cn</code> | Sorts the items in the <i><tl var></i> according to the <i><comparison code></i> , and assigns the result to <i><tl var></i> . The details of sorting comparison are described in Section 1. |
| <code>\tl_gsort:Nn</code> | |
| <code>\tl_gsort:cn</code> | |
| New: 2017-02-06 | |

| | |
|----------------------------|--|
| <code>\tl_sort:nN</code> ★ | <code>\tl_sort:nN {<token list>} <conditional></code> |
| New: 2017-02-06 | Sorts the items in the <i><token list></i> , using the <i><conditional></i> to compare items, and leaves the result in the input stream. The <i><conditional></i> should have signature <code>:nnTF</code> , and return true if the two items being compared should be left in the same order, and false if the items should be swapped. The details of sorting comparison are described in Section 1. |

TeXhackers note: The result is returned within `\exp_not:n`, which means that the token list will not expand further when appearing in an **x**-type argument expansion.

9 The first token from a token list

Functions which deal with either only the very first item (balanced text or single normal token) in a token list, or the remaining tokens.

| | |
|---------------------------------|---|
| <code>\tl_head:N</code> ★ | <code>\tl_head:n {<token list>}</code> |
| <code>\tl_head:n</code> ★ | Leaves in the input stream the first <i><item></i> in the <i><token list></i> , discarding the rest of the <i><token list></i> . All leading explicit space characters (explicit tokens with character code 32 and category code 10) are discarded; for example |
| <code>\tl_head:(V v f)</code> ★ | |
| Updated: 2012-09-09 | |

`\tl_head:n { abc }`

and

`\tl_head:n { ~ abc }`

will both leave **a** in the input stream. If the “head” is a brace group, rather than a single token, the braces will be removed, and so

`\tl_head:n { ~ { ~ ab } c }`

yields `␣ab`. A blank *<token list>* (see `\tl_if_blank:nTF`) will result in `\tl_head:n` leaving nothing in the input stream.

TeXhackers note: The result is returned within `\exp_not:n`, which means that the token list will not expand further when appearing in an **x**-type argument expansion.

| | | |
|-------------------------|---|--|
| <code>\tl_head:w</code> | ★ | <code>\tl_head:w <token list> { } \q_stop</code> |
|-------------------------|---|--|

Leaves in the input stream the first *<item>* in the *<token list>*, discarding the rest of the *<token list>*. All leading explicit space characters (explicit tokens with character code 32 and category code 10) are discarded. A blank *<token list>* (which consists only of space characters) will result in a low-level T_EX error, which may be avoided by the inclusion of an empty group in the input (as shown), without the need for an explicit test. Alternatively, `\tl_if_blank:nF` may be used to avoid using the function with a “blank” argument. This function requires only a single expansion, and thus is suitable for use within an o-type expansion. In general, `\tl_head:n` should be preferred if the number of expansions is not critical.

| | | |
|-------------------------------|---|--|
| <code>\tl_tail:N</code> | ★ | <code>\tl_tail:n {<token list>}</code> |
| <code>\tl_tail:n</code> | ★ | |
| <code>\tl_tail:(V v f)</code> | ★ | |

Updated: 2012-09-01

Discards all leading explicit space characters (explicit tokens with character code 32 and category code 10) and the first *<item>* in the *<token list>*, and leaves the remaining tokens in the input stream. Thus for example

`\tl_tail:n { a ~ {bc} d }`

and

`\tl_tail:n { ~ a ~ {bc} d }`

will both leave `_{}{bc}d` in the input stream. A blank *<token list>* (see `\tl_if_blank:nTF`) will result in `\tl_tail:n` leaving nothing in the input stream.

T_EXhackers note: The result is returned within `\exp_not:n`, which means that the token list will not expand further when appearing in an x-type argument expansion.

| | | |
|--|---|--|
| <code>\tl_if_head_eq_catcode_p:nN</code> | ★ | <code>\tl_if_head_eq_catcode_p:nN {<token list>} <test token></code> |
| <code>\tl_if_head_eq_catcode:nNTF</code> | ★ | <code>\tl_if_head_eq_catcode:nNTF {<token list>} <test token></code> |
| | | <code>{<true code>} {<false code>}</code> |

Updated: 2012-07-09

Tests if the first *<token>* in the *<token list>* has the same category code as the *<test token>*. In the case where the *<token list>* is empty, the test will always be **false**.

| | | |
|---|---|---|
| <code>\tl_if_head_eq_charcode_p:nN</code> | ★ | <code>\tl_if_head_eq_charcode_p:nN {<token list>} <test token></code> |
| <code>\tl_if_head_eq_charcode_p:fN</code> | ★ | <code>\tl_if_head_eq_charcode:nNTF {<token list>} <test token></code> |
| <code>\tl_if_head_eq_charcode:nNTF</code> | ★ | <code>{<true code>} {<false code>}</code> |
| <code>\tl_if_head_eq_charcode:fNTF</code> | ★ | |

Updated: 2012-07-09

Tests if the first *<token>* in the *<token list>* has the same character code as the *<test token>*. In the case where the *<token list>* is empty, the test will always be **false**.

| | | |
|--|---|--|
| <code>\tl_if_head_eq_meaning_p:nN</code> | ★ | <code>\tl_if_head_eq_meaning_p:nN {<token list>} <test token></code> |
| <code>\tl_if_head_eq_meaning:nNTF</code> | ★ | <code>\tl_if_head_eq_meaning:nNTF {<token list>} <test token></code> |
| | | <code>{<true code>} {<false code>}</code> |

Updated: 2012-07-09

Tests if the first *<token>* in the *<token list>* has the same meaning as the *<test token>*. In the case where *<token list>* is empty, the test will always be **false**.

```
\tl_if_head_is_group_p:n ★ \tl_if_head_is_group_p:nTF ★
```

New: 2012-07-08

```
\tl_if_head_is_group_p:n {\token list}
\tl_if_head_is_group:nTF {\token list} {\true code} {\false code}
```

Tests if the first $\langle token \rangle$ in the $\langle token list \rangle$ is an explicit begin-group character (with category code 1 and any character code), in other words, if the $\langle token list \rangle$ starts with a brace group. In particular, the test is **false** if the $\langle token list \rangle$ starts with an implicit token such as `\c_group_begin_token`, or if it is empty. This function is useful to implement actions on token lists on a token by token basis.

```
\tl_if_head_is_N_type_p:n ★ \tl_if_head_is_N_type_p:n {\token list}
\tl_if_head_is_N_type:nTF ★ \tl_if_head_is_N_type:nTF {\token list} {\true code} {\false code}
```

New: 2012-07-08

Tests if the first $\langle token \rangle$ in the $\langle token list \rangle$ is a normal N-type argument. In other words, it is neither an explicit space character (explicit token with character code 32 and category code 10) nor an explicit begin-group character (with category code 1 and any character code). An empty argument yields **false**, as it does not have a “normal” first token. This function is useful to implement actions on token lists on a token by token basis.

```
\tl_if_head_is_space_p:n ★ \tl_if_head_is_space_p:n {\token list}
\tl_if_head_is_space:nTF ★ \tl_if_head_is_space:nTF {\token list} {\true code} {\false code}
```

Updated: 2012-07-08

Tests if the first $\langle token \rangle$ in the $\langle token list \rangle$ is an explicit space character (explicit token with character code 12 and category code 10). In particular, the test is **false** if the $\langle token list \rangle$ starts with an implicit token such as `\c_space_token`, or if it is empty. This function is useful to implement actions on token lists on a token by token basis.

10 Using a single item

```
\tl_item:nn ★ \tl_item:Nn ★ \tl_item:cn ★
```

New: 2014-07-17

```
\tl_item:nn {\token list} {\integer expression}
```

Indexing items in the $\langle token list \rangle$ from 1 on the left, this function will evaluate the $\langle integer expression \rangle$ and leave the appropriate item from the $\langle token list \rangle$ in the input stream. If the $\langle integer expression \rangle$ is negative, indexing occurs from the right of the token list, starting at -1 for the right-most item. If the index is out of bounds, then the function expands to nothing.

T_EXhackers note: The result is returned within the `\unexpanded` primitive (`\exp_not:n`), which means that the $\langle item \rangle$ will not expand further when appearing in an x-type argument expansion.

11 Viewing token lists

```
\tl_show:N \tl_show:c
```

Updated: 2015-08-01

```
\tl_show:N \tl var
```

Displays the content of the $\langle tl var \rangle$ on the terminal.

T_EXhackers note: This is similar to the T_EX primitive `\show`, wrapped to a fixed number of characters per line.

| | |
|-------------------------------------|---|
| <hr/> <code>\tl_show:n</code> <hr/> | <code>\tl_show:n <token list></code> |
| <code>Updated: 2015-08-07</code> | Displays the <i><token list></i> on the terminal. |

TeXhackers note: This is similar to the ϵ -TeX primitive `\showtokens`, wrapped to a fixed number of characters per line.

| | |
|--|--|
| <hr/> <code>\tl_log:N</code> <code>\tl_log:c</code> <hr/> | <code>\tl_log:N <tl var></code> |
| <code>New: 2014-08-22</code> <code>Updated: 2015-08-01</code> | Writes the content of the <i><tl var></i> in the log file. See also <code>\tl_show:N</code> which displays the result in the terminal. |

| | |
|--|---|
| <hr/> <code>\tl_log:n</code> <hr/> | <code>\tl_log:n {\<token list>}</code> |
| <code>New: 2014-08-22</code> <code>Updated: 2015-08-07</code> | Writes the <i><token list></i> in the log file. See also <code>\tl_show:n</code> which displays the result in the terminal. |

12 Constant token lists

| | |
|--------------------------------------|--------------------------------|
| <hr/> <code>\c_empty_tl</code> <hr/> | Constant that is always empty. |
|--------------------------------------|--------------------------------|

| | |
|--------------------------------------|--|
| <hr/> <code>\c_space_tl</code> <hr/> | An explicit space character contained in a token list (compare this with <code>\c_space_token</code>). For use where an explicit space is required. |
|--------------------------------------|--|

13 Scratch token lists

| | |
|--|---|
| <hr/> <code>\l_tmpa_tl</code> <code>\l_tmpb_tl</code> <hr/> | Scratch token lists for local assignment. These are never used by the kernel code, and so are safe for use with any L ^A T _E X3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage. |
|--|---|

| | |
|--|--|
| <hr/> <code>\g_tmpa_tl</code> <code>\g_tmpb_tl</code> <hr/> | Scratch token lists for global assignment. These are never used by the kernel code, and so are safe for use with any L ^A T _E X3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage. |
|--|--|

14 Internal functions

| | |
|---|--|
| <hr/> <code>__tl_trim_spaces:nn</code> <hr/> | <code>__tl_trim_spaces:nn { \q_mark <token list> } {\<continuation>}</code> |
| | This function removes all leading and trailing explicit space characters from the <i><token list></i> , and expands to the <i><continuation></i> , followed by a brace group containing <code>\use_none:n \q_mark <trimmed token list></code> . For instance, <code>\tl_trim_spaces:n</code> is implemented by taking the <i><continuation></i> to be <code>\exp_not:o</code> , and the o-type expansion removes the <code>\q_mark</code> . This function is also used in <code>l3clist</code> and <code>l3candidates</code> . |

Part VII

The l3str package

Strings

TeX associates each character with a category code: as such, there is no concept of a “string” as commonly understood in many other programming languages. However, there are places where we wish to manipulate token lists while in some sense “ignoring” category codes: this is done by treating token lists as strings in a TeX sense.

A TeX string (and thus an expl3 string) is a series of characters which have category code 12 (“other”) with the exception of space characters which have category code 10 (“space”). Thus at a technical level, a TeX string is a token list with the appropriate category codes. In this documentation, these will simply be referred to as strings.

String variables are simply specialised token lists, but by convention should be named with the suffix `...str`. Such variables should contain characters with category code 12 (other), except spaces, which have category code 10 (blank space). All the functions in this module which accept a token list argument first convert it to a string using `\tl_to_str:n` for internal processing, and will not treat a token list or the corresponding string representation differently.

Note that as string variables are a special case of token list variables the coverage of `\str_...:N` functions is somewhat smaller than `\tl_...:N`.

The functions `\cs_to_str:N`, `\tl_to_str:n`, `\tl_to_str:N` and `\token_to_str:N` (and variants) will generate strings from the appropriate input: these are documented in `l3basics`, `l3tl` and `l3token`, respectively.

Most expandable functions in this module come in three flavours:

- `\str_...:N`, which expect a token list or string variable as their argument;
- `\str_...:n`, taking any token list (or string) as an argument;
- `\str_..._ignore_spaces:n`, which ignores any space encountered during the operation: these functions are typically faster than those which take care of escaping spaces appropriately.

1 Building strings

`\str_new:N`
`\str_new:c`

New: 2015-09-18

`\str_new:N` $\langle str\ var \rangle$
Creates a new $\langle str\ var \rangle$ or raises an error if the name is already taken. The declaration is global. The $\langle str\ var \rangle$ will initially be empty.

`\str_const:Nn`
`\str_const:(Nx|cn|cx)`

New: 2015-09-18

`\str_const:Nn` $\langle str\ var \rangle$ $\{ \langle token\ list \rangle \}$
Creates a new constant $\langle str\ var \rangle$ or raises an error if the name is already taken. The value of the $\langle str\ var \rangle$ will be set globally to the $\langle token\ list \rangle$, converted to a string.

| | |
|----------------------------|--|
| <code>\str_clear:N</code> | <code>\str_clear:N <str var></code> |
| <code>\str_clear:c</code> | |
| <code>\str_gclear:N</code> | Clears the content of the <code><str var></code> . |
| <code>\str_gclear:c</code> | |
| <hr/> | |
| New: 2015-09-18 | |

| | |
|-------------------------------|--|
| <code>\str_clear_new:N</code> | <code>\str_clear_new:N <str var></code> |
| <code>\str_clear_new:c</code> | |
| | Ensures that the <code><str var></code> exists globally by applying <code>\str_new:N</code> if necessary, then applies <code>\str_(g)clear:N</code> to leave the <code><str var></code> empty. |
| <hr/> | |
| New: 2015-09-18 | |

| | |
|--------------------------------------|--|
| <code>\str_set_eq:NN</code> | <code>\str_set_eq:NN <str var₁> <str var₂></code> |
| <code>\str_set_eq:(cN Nc cc)</code> | |
| <code>\str_gset_eq:NN</code> | Sets the content of <code><str var₁></code> equal to that of <code><str var₂></code> . |
| <code>\str_gset_eq:(cN Nc cc)</code> | |
| <hr/> | |
| New: 2015-09-18 | |

2 Adding data to string variables

| | |
|-----------------------------------|---|
| <code>\str_set:Nn</code> | <code>\str_set:Nn <str var> {<token list>}</code> |
| <code>\str_set:(Nx cn cx)</code> | |
| <code>\str_gset:Nn</code> | Converts the <code><token list></code> to a <code><string></code> , and stores the result in <code><str var></code> . |
| <code>\str_gset:(Nx cn cx)</code> | |
| <hr/> | |
| New: 2015-09-18 | |

| | |
|--|---|
| <code>\str_put_left:Nn</code> | <code>\str_put_left:Nn <str var> {<token list>}</code> |
| <code>\str_put_left:(Nx cn cx)</code> | |
| <code>\str_gput_left:Nn</code> | Converts the <code><token list></code> to a <code><string></code> , and prepends the result to <code><str var></code> . The current contents of the <code><str var></code> are not automatically converted to a string. |
| <code>\str_gput_left:(Nx cn cx)</code> | |
| <hr/> | |
| New: 2015-09-18 | |

| | |
|---|--|
| <code>\str_put_right:Nn</code> | <code>\str_put_right:Nn <str var> {<token list>}</code> |
| <code>\str_put_right:(Nx cn cx)</code> | |
| <code>\str_gput_right:Nn</code> | Converts the <code><token list></code> to a <code><string></code> , and appends the result to <code><str var></code> . The current contents of the <code><str var></code> are not automatically converted to a string. |
| <code>\str_gput_right:(Nx cn cx)</code> | |
| <hr/> | |
| New: 2015-09-18 | |

2.1 String conditionals

| | |
|----------------------------------|--|
| <code>\str_if_exist_p:N</code> ★ | <code>\str_if_exist_p:N <str var></code> |
| <code>\str_if_exist_p:c</code> ★ | <code>\str_if_exist:NTF <str var> {<true code>} {<false code>}</code> |
| <code>\str_if_exist:NTF</code> ★ | |
| <code>\str_if_exist:cTF</code> ★ | Tests whether the <code><str var></code> is currently defined. This does not check that the <code><str var></code> really is a string. |
| <hr/> | |
| New: 2015-09-18 | |

| | | |
|---------------------------------|---|---|
| <code>\str_if_empty_p:N</code> | ★ | <code>\str_if_empty_p:N</code> $\langle \text{str var} \rangle$ |
| <code>\str_if_empty_p:c</code> | ★ | <code>\str_if_empty:N</code> TF $\langle \text{str var} \rangle$ $\{\langle \text{true code} \rangle\}$ $\{\langle \text{false code} \rangle\}$ |
| <code>\str_if_empty:N</code> TF | ★ | Tests if the $\langle \text{string variable} \rangle$ is entirely empty (<i>i.e.</i> contains no characters at all). |
| <code>\str_if_empty:c</code> TF | ★ | |

New: 2015-09-18

| | | |
|---------------------------------------|---|--|
| <code>\str_if_eq_p:NN</code> | ★ | <code>\str_if_eq_p:NN</code> $\langle \text{str var}_1 \rangle$ $\langle \text{str var}_2 \rangle$ |
| <code>\str_if_eq_p:(Nc cN cc)</code> | ★ | <code>\str_if_eq:NN</code> TF $\langle \text{str var}_1 \rangle$ $\langle \text{str var}_2 \rangle$ $\{\langle \text{true code} \rangle\}$ $\{\langle \text{false code} \rangle\}$ |
| <code>\str_if_eq:NN</code> TF | ★ | Compares the content of two $\langle \text{str variables} \rangle$ and is logically true if the two contain the same characters. |
| <code>\str_if_eq:(Nc cN cc)</code> TF | ★ | |

New: 2015-09-18

| | | |
|---|---|---|
| <code>\str_if_eq_p:nn</code> | ★ | <code>\str_if_eq_p:nn</code> $\{\langle \text{tl}_1 \rangle\}$ $\{\langle \text{tl}_2 \rangle\}$ |
| <code>\str_if_eq_p:(Vn on no nV VV)</code> | ★ | <code>\str_if_eq:nn</code> TF $\{\langle \text{tl}_1 \rangle\}$ $\{\langle \text{tl}_2 \rangle\}$ $\{\langle \text{true code} \rangle\}$ $\{\langle \text{false code} \rangle\}$ |
| <code>\str_if_eq:nn</code> TF | ★ | Compares the two $\langle \text{token lists} \rangle$ on a character by character basis, and is true if the two lists contain the same characters in the same order. Thus for example |
| <code>\str_if_eq:(Vn on no nV VV)</code> TF | ★ | |

`\str_if_eq_p:no { abc } { \tl_to_str:n { abc } }`

is logically true.

| | | |
|---------------------------------|---|--|
| <code>\str_if_eq_x_p:nn</code> | ★ | <code>\str_if_eq_x_p:nn</code> $\{\langle \text{tl}_1 \rangle\}$ $\{\langle \text{tl}_2 \rangle\}$ |
| <code>\str_if_eq_x:nn</code> TF | ★ | <code>\str_if_eq_x:nn</code> TF $\{\langle \text{tl}_1 \rangle\}$ $\{\langle \text{tl}_2 \rangle\}$ $\{\langle \text{true code} \rangle\}$ $\{\langle \text{false code} \rangle\}$ |

New: 2012-06-05

Compares the full expansion of two $\langle \text{token lists} \rangle$ on a character by character basis, and is true if the two lists contain the same characters in the same order. Thus for example

`\str_if_eq_x_p:nn { abc } { \tl_to_str:n { abc } }`

is logically true.

| | | |
|--------------------------------------|---|---|
| <code>\str_case:nn</code> | ★ | <code>\str_case:nn</code> TF $\{\langle \text{test string} \rangle\}$ |
| <code>\str_case:(on nV nv)</code> | ★ | { |
| <code>\str_case:nn</code> TF | ★ | $\{\langle \text{string case}_1 \rangle\}$ $\{\langle \text{code case}_1 \rangle\}$ |
| <code>\str_case:(on nV nv)</code> TF | ★ | $\{\langle \text{string case}_2 \rangle\}$ $\{\langle \text{code case}_2 \rangle\}$ |
| | | ... |
| | | $\{\langle \text{string case}_n \rangle\}$ $\{\langle \text{code case}_n \rangle\}$ |
| | | } |
| | | $\{\langle \text{true code} \rangle\}$ |
| | | $\{\langle \text{false code} \rangle\}$ |

New: 2013-07-24

Updated: 2015-02-28

This function compares the $\langle \text{test string} \rangle$ in turn with each of the $\langle \text{string cases} \rangle$. If the two are equal (as described for `\str_if_eq:nnTF` then the associated $\langle \text{code} \rangle$ is left in the input stream. If any of the cases are matched, the $\langle \text{true code} \rangle$ is also inserted into the input stream (after the code for the appropriate case), while if none match then the $\langle \text{false code} \rangle$ is inserted. The function `\str_case:nn`, which does nothing if there is no match, is also available.

| | |
|---|---|
| <hr/> <code>\str_case_x:nnTF</code> ★ <hr/> | <code>\str_case_x:nnTF</code> $\{ \langle test\ string \rangle \}$ |
| New: 2013-07-24 | $\{$ $\{ \langle string\ case_1 \rangle \} \{ \langle code\ case_1 \rangle \}$ $\{ \langle string\ case_2 \rangle \} \{ \langle code\ case_2 \rangle \}$ \dots $\{ \langle string\ case_n \rangle \} \{ \langle code\ case_n \rangle \}$ $\}$ $\{ \langle true\ code \rangle \}$ $\{ \langle false\ code \rangle \}$ |

This function compares the full expansion of the $\langle test\ string \rangle$ in turn with the full expansion of the $\langle string\ cases \rangle$. If the two full expansions are equal (as described for `\str_if_eq:nnTF`) then the associated $\langle code \rangle$ is left in the input stream. If any of the cases are matched, the $\langle true\ code \rangle$ is also inserted into the input stream (after the code for the appropriate case), while if none match then the $\langle false\ code \rangle$ is inserted. The function `\str_case_x:nn`, which does nothing if there is no match, is also available. The $\langle test\ string \rangle$ is expanded in each comparison, and must always yield the same result: for example, random numbers must not be used within this string.

3 Working with the content of strings

| | |
|---------------------------------------|--|
| <hr/> <code>\str_use:N</code> ★ <hr/> | <code>\str_use:N</code> $\langle str\ var \rangle$ |
| <code>\str_use:c</code> ★ | |
| New: 2015-09-18 | |

Recovers the content of a $\langle str\ var \rangle$ and places it directly in the input stream. An error will be raised if the variable does not exist or if it is invalid. Note that it is possible to use a $\langle str \rangle$ directly without an accessor function.

| | |
|---|---|
| <hr/> <code>\str_count:N</code> ★ <hr/> | <code>\str_count:n</code> $\{ \langle token\ list \rangle \}$ |
| <code>\str_count:c</code> ★ | |
| <code>\str_count:n</code> ★ | |
| <code>\str_count_ignore_spaces:n</code> ★ | |
| New: 2015-09-18 | |

Leaves in the input stream the number of characters in the string representation of $\langle token\ list \rangle$, as an integer denotation. The functions differ in their treatment of spaces. In the case of `\str_count:N` and `\str_count:n`, all characters including spaces are counted. The `\str_count_ignore_spaces:n` function leaves the number of non-space characters in the input stream.

| | |
|--|--|
| <hr/> <code>\str_count_spaces:N</code> ★ <hr/> | <code>\str_count_spaces:n</code> $\{ \langle token\ list \rangle \}$ |
| <code>\str_count_spaces:c</code> ★ | |
| <code>\str_count_spaces:n</code> ★ | |
| New: 2015-09-18 | |

Leaves in the input stream the number of space characters in the string representation of $\langle token\ list \rangle$, as an integer denotation. Of course, this function has no `_ignore_spaces` variant.

| | | |
|--|---|---|
| <code>\str_head:N</code> | ★ | <code>\str_head:n {⟨token list⟩}</code> |
| <code>\str_head:c</code> | ★ | |
| <code>\str_head:n</code> | ★ | |
| <code>\str_head_ignore_spaces:n</code> | ★ | |

New: 2015-09-18

Converts the $\langle token list \rangle$ into a $\langle string \rangle$. The first character in the $\langle string \rangle$ is then left in the input stream, with category code “other”. The functions differ if the first character is a space: `\str_head:N` and `\str_head:n` return a space token with category code 10 (blank space), while the `\str_head_ignore_spaces:n` function ignores this space character and leaves the first non-space character in the input stream. If the $\langle string \rangle$ is empty (or only contains spaces in the case of the `_ignore_spaces` function), then nothing is left on the input stream.

| | | |
|--|---|---|
| <code>\str_tail:N</code> | ★ | <code>\str_tail:n {⟨token list⟩}</code> |
| <code>\str_tail:c</code> | ★ | |
| <code>\str_tail:n</code> | ★ | |
| <code>\str_tail_ignore_spaces:n</code> | ★ | |

New: 2015-09-18

Converts the $\langle token list \rangle$ to a $\langle string \rangle$, removes the first character, and leaves the remaining characters (if any) in the input stream, with category codes 12 and 10 (for spaces). The functions differ in the case where the first character is a space: `\str_tail:N` and `\str_tail:n` will trim only that space, while `\str_tail_ignore_spaces:n` removes the first non-space character and any space before it. If the $\langle token list \rangle$ is empty (or blank in the case of the `_ignore_spaces` variant), then nothing is left on the input stream.

| | | |
|---|---|---|
| <code>\str_item:Nn</code> | ★ | <code>\str_item:nn {⟨token list⟩} {⟨integer expression⟩}</code> |
| <code>\str_item:nn</code> | ★ | |
| <code>\str_item_ignore_spaces:nn</code> | ★ | |

New: 2015-09-18

Converts the $\langle token list \rangle$ to a $\langle string \rangle$, and leaves in the input stream the character in position $\langle integer expression \rangle$ of the $\langle string \rangle$, starting at 1 for the first (left-most) character. In the case of `\str_item:Nn` and `\str_item:nn`, all characters including spaces are taken into account. The `\str_item_ignore_spaces:nn` function skips spaces when counting characters. If the $\langle integer expression \rangle$ is negative, characters are counted from the end of the $\langle string \rangle$. Hence, -1 is the right-most character, *etc.*

```

\str_range:Nnn      ★ \str_range:nnn {⟨token list⟩} {⟨start index⟩} {⟨end index⟩}
\str_range:cnn      ★
\str_range:nnn      ★
\str_range_ignore_spaces:nnn ★

```

New: 2015-09-18

Converts the $\langle token\ list \rangle$ to a $\langle string \rangle$, and leaves in the input stream the characters from the $\langle start\ index \rangle$ to the $\langle end\ index \rangle$ inclusive. Positive $\langle indices \rangle$ are counted from the start of the string, 1 being the first character, and negative $\langle indices \rangle$ are counted from the end of the string, -1 being the last character. If either of $\langle start\ index \rangle$ or $\langle end\ index \rangle$ is 0, the result is empty. For instance,

```

\iow_term:x { \str_range:nnn { abcdef } { 2 } { 5 } }
\iow_term:x { \str_range:nnn { abcdef } { -4 } { -1 } }
\iow_term:x { \str_range:nnn { abcdef } { -2 } { -1 } }
\iow_term:x { \str_range:nnn { abcdef } { 0 } { -1 } }

```

will print bcde, cdef, ef, and an empty line to the terminal. The $\langle start\ index \rangle$ must always be smaller than or equal to the $\langle end\ index \rangle$: if this is not the case then no output is generated. Thus

```

\iow_term:x { \str_range:nnn { abcdef } { 5 } { 2 } }
\iow_term:x { \str_range:nnn { abcdef } { -1 } { -4 } }

```

both yield empty strings.

4 String manipulation

`\str_lower_case:n` ☆
`\str_lower_case:f` ☆
`\str_upper_case:n` ☆
`\str_upper_case:f` ☆

New: 2015-03-01

`\str_lower_case:n` {*<tokens>*}
`\str_upper_case:n` {*<tokens>*}

Converts the input *<tokens>* to their string representation, as described for `\tl_to_str:n`, and then to the lower or upper case representation using a one-to-one mapping as described by the Unicode Consortium file `UnicodeData.txt`.

These functions are intended for case changing programmatic data in places where upper/lower case distinctions are meaningful. One example would be automatically generating a function name from user input where some case changing is needed. In this situation the input is programmatic, not textual, case does have meaning and a language-independent one-to-one mapping is appropriate. For example

```

\cs_new_protected:Npn \myfunc:nn #1#2
{
  \cs_set_protected:cpn
  {
    user
    \str_upper_case:f { \tl_head:n {#1} }
    \str_lower_case:f { \tl_tail:n {#1} }
  }
  { #2 }
}

```

would be used to generate a function with an auto-generated name consisting of the upper case equivalent of the supplied name followed by the lower case equivalent of the rest of the input.

These functions should *not* be used for

- Caseless comparisons: use `\str_fold_case:n` for this situation (case folding is distinct from lower casing).
- Case changing text for typesetting: see the `\tl_lower_case:n(n)`, `\tl_upper_case:n(n)` and `\tl_mixed_case:n(n)` functions which correctly deal with context-dependence and other factors appropriate to text case changing.

T_EXhackers note: As with all `expl3` functions, the input supported by `\str_fold_case:n` is *engine-native* characters which are or interoperate with UTF-8. As such, when used with pdfT_EX *only* the Latin alphabet characters A–Z will be case-folded (*i.e.* the ASCII range which coincides with UTF-8). Full UTF-8 support is available with both X_ƎT_EX and LuaT_EX, subject only to the fact that X_ƎT_EX in particular has issues with characters of code above hexadecimal 0xFFFF when interacting with `\tl_to_str:n`.

`\str_fold_case:n` ★ `\str_fold_case:n` $\{(tokens)\}$

`\str_fold_case:V` ★

New: 2014-06-19

Updated: 2016-03-07

Converts the input $\langle tokens \rangle$ to their string representation, as described for `\tl_to_str:n`, and then folds the case of the resulting $\langle string \rangle$ to remove case information. The result of this process is left in the input stream.

String folding is a process used for material such as identifiers rather than for “text”. The folding provided by `\str_fold_case:n` follows the mappings provided by the [Unicode Consortium](#), who [state](#):

Case folding is primarily used for caseless comparison of text, such as identifiers in a computer program, rather than actual text transformation. Case folding in Unicode is based on the lowercase mapping, but includes additional changes to the source text to help make it language-insensitive and consistent. As a result, case-folded text should be used solely for internal processing and generally should not be stored or displayed to the end user.

The folding approach implemented by `\str_fold_case:n` follows the “full” scheme defined by the Unicode Consortium (*e.g.* `SS` folds to `ss`). As case-folding is a language-insensitive process, there is no special treatment of Turkic input (*i.e.* `I` always folds to `i` and not to `ı`).

TeXhackers note: As with all `expl3` functions, the input supported by `\str_fold_case:n` is *engine-native* characters which are or interoperate with UTF-8. As such, when used with pdfTeX *only* the Latin alphabet characters A–Z will be case-folded (*i.e.* the ASCII range which coincides with UTF-8). Full UTF-8 support is available with both XeTeX and LuaTeX, subject only to the fact that XeTeX in particular has issues with characters of code above hexadecimal 0xFFFF when interacting with `\tl_to_str:n`.

5 Viewing strings

`\str_show:N` `\str_show:N` $\langle str\ var \rangle$

`\str_show:c`

`\str_show:n`

New: 2015-09-18

Displays the content of the $\langle str\ var \rangle$ on the terminal.

6 Constant token lists

```

\c_ampersand_str
\c_atsign_str
\c_backslash_str
\c_left_brace_str
\c_right_brace_str
\c_circumflex_str
\c_colon_str
\c_dollar_str
\c_hash_str
\c_percent_str
\c_tilde_str
\c_underscore_str

```

New: 2015-09-19

Constant strings, containing a single character token, with category code 12.

7 Scratch strings

```

\l_tmpa_str
\l_tmpb_str

```

Scratch strings for local assignment. These are never used by the kernel code, and so are safe for use with any L^AT_EX3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.

```

\g_tmpa_str
\g_tmpb_str

```

Scratch strings for global assignment. These are never used by the kernel code, and so are safe for use with any L^AT_EX3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.

7.1 Internal string functions

```

\__str_if_eq_x:nn ★ \__str_if_eq_x:nn {\t1} {\t2}

```

Compares the full expansion of two *<token lists>* on a character by character basis, and is `true` if the two lists contain the same characters in the same order. Leaves 0 in the input stream if the condition is true, and +1 or -1 otherwise.

```

\__str_if_eq_x_return:nn \__str_if_eq_x_return:nn {\t1} {\t2}

```

Compares the full expansion of two *<token lists>* on a character by character basis, and is `true` if the two lists contain the same characters in the same order. Either `\prg_return_true:` or `\prg_return_false:` is then left in the input stream. This is a version of `\str_if_eq_x:nnTF` coded for speed.

```

\__str_to_other:n ★ \__str_to_other:n {\token list}

```

Converts the *<token list>* to a *<other string>*, where spaces have category code “other”. This function can be f-expanded without fear of losing a leading space, since spaces do not have category code 10 in its result. It takes a time quadratic in the character count of the string.

| | | | |
|-------------|---------------------------------------|--|--|
| <hr/> <hr/> | <code>__str_to_other_fast:n</code> ☆ | <code>__str_to_other_fast:n {⟨token list⟩}</code> | Same behaviour <code>__str_to_other:n</code> but only restricted-expandable. It takes a time linear in the character count of the string. It is used for <code>\iow_wrap:nnnN</code> . |
| <hr/> <hr/> | <code>__str_count:n</code> ★ | <code>__str_count:n {⟨other string⟩}</code> | This function expects an argument that is entirely made of characters with category “other”, as produced by <code>__str_to_other:n</code> . It leaves in the input stream the number of character tokens in the <i>⟨other string⟩</i> , faster than the analogous <code>\str_count:n</code> function. |
| <hr/> <hr/> | <code>__str_range:nnn</code> ★ | <code>__str_range:nnn {⟨other string⟩} {⟨start index⟩} {⟨end index⟩}</code> | Identical to <code>\str_range:nnn</code> except that the first argument is expected to be entirely made of characters with category “other”, as produced by <code>__str_to_other:n</code> , and the result is also an <i>⟨other string⟩</i> . |

Part VIII

The l3seq package

Sequences and stacks

L^AT_EX3 implements a “sequence” data type, which contain an ordered list of entries which may contain any *balanced text*. It is possible to map functions to sequences such that the function is applied to every item in the sequence.

Sequences are also used to implement stack functions in L^AT_EX3. This is achieved using a number of dedicated stack functions.

1 Creating and initialising sequences

| | |
|-------------------------|-------------------------|
| <code>\seq_new:N</code> | <code>\seq_new:N</code> |
| <code>\seq_new:c</code> | <code>\seq_new:c</code> |

`\seq_new:N` *<sequence>*

Creates a new *<sequence>* or raises an error if the name is already taken. The declaration is global. The *<sequence>* will initially contain no items.

| | |
|----------------------------|----------------------------|
| <code>\seq_clear:N</code> | <code>\seq_clear:N</code> |
| <code>\seq_clear:c</code> | <code>\seq_clear:c</code> |
| <code>\seq_gclear:N</code> | <code>\seq_gclear:N</code> |
| <code>\seq_gclear:c</code> | <code>\seq_gclear:c</code> |

`\seq_clear:N` *<sequence>*

Clears all items from the *<sequence>*.

| | |
|--------------------------------|--------------------------------|
| <code>\seq_clear_new:N</code> | <code>\seq_clear_new:N</code> |
| <code>\seq_clear_new:c</code> | <code>\seq_clear_new:c</code> |
| <code>\seq_gclear_new:N</code> | <code>\seq_gclear_new:N</code> |
| <code>\seq_gclear_new:c</code> | <code>\seq_gclear_new:c</code> |

`\seq_clear_new:N` *<sequence>*

Ensures that the *<sequence>* exists globally by applying `\seq_new:N` if necessary, then applies `\seq_(g)clear:N` to leave the *<sequence>* empty.

| | |
|--------------------------------------|--------------------------------------|
| <code>\seq_set_eq:NN</code> | <code>\seq_set_eq:NN</code> |
| <code>\seq_set_eq:(cN Nc cc)</code> | <code>\seq_set_eq:(cN Nc cc)</code> |
| <code>\seq_gset_eq:NN</code> | <code>\seq_gset_eq:NN</code> |
| <code>\seq_gset_eq:(cN Nc cc)</code> | <code>\seq_gset_eq:(cN Nc cc)</code> |

`\seq_set_eq:NN` *<sequence₁>* *<sequence₂>*

Sets the content of *<sequence₁>* equal to that of *<sequence₂>*.

| | |
|--|--|
| <code>\seq_set_from_clist:NN</code> | <code>\seq_set_from_clist:NN</code> |
| <code>\seq_set_from_clist:(cN Nc cc)</code> | <code>\seq_set_from_clist:(cN Nc cc)</code> |
| <code>\seq_set_from_clist:Nn</code> | <code>\seq_set_from_clist:Nn</code> |
| <code>\seq_set_from_clist:cn</code> | <code>\seq_set_from_clist:cn</code> |
| <code>\seq_gset_from_clist:NN</code> | <code>\seq_gset_from_clist:NN</code> |
| <code>\seq_gset_from_clist:(cN Nc cc)</code> | <code>\seq_gset_from_clist:(cN Nc cc)</code> |
| <code>\seq_gset_from_clist:Nn</code> | <code>\seq_gset_from_clist:Nn</code> |
| <code>\seq_gset_from_clist:cn</code> | <code>\seq_gset_from_clist:cn</code> |

`\seq_set_from_clist:NN` *<sequence>* *<comma-list>*

New: 2014-07-17

Converts the data in the *<comma list>* into a *<sequence>*: the original *<comma list>* is unchanged.

```

\seq_set_split:Nnn
\seq_set_split:NnV
\seq_gset_split:Nnn
\seq_gset_split:NnV

```

New: 2011-08-15
Updated: 2012-07-02

```
\seq_set_split:Nnn <sequence> {<delimiter>} {<token list>}
```

Splits the $\langle token list \rangle$ into $\langle items \rangle$ separated by $\langle delimiter \rangle$, and assigns the result to the $\langle sequence \rangle$. Spaces on both sides of each $\langle item \rangle$ are ignored, then one set of outer braces is removed (if any); this space trimming behaviour is identical to that of `l3clist` functions. Empty $\langle items \rangle$ are preserved by `\seq_set_split:Nnn`, and can be removed afterwards using `\seq_remove_all:Nn <sequence> {<>}`. The $\langle delimiter \rangle$ may not contain `{`, `}` or `#` (assuming \TeX 's normal category code régime). If the $\langle delimiter \rangle$ is empty, the $\langle token list \rangle$ is split into $\langle items \rangle$ as a $\langle token list \rangle$.

```

\seq_concat:NNN
\seq_concat:ccc
\seq_gconcat:NNN
\seq_gconcat:ccc

```

```
\seq_concat:NNN <sequence1> <sequence2> <sequence3>
```

Concatenates the content of $\langle sequence_2 \rangle$ and $\langle sequence_3 \rangle$ together and saves the result in $\langle sequence_1 \rangle$. The items in $\langle sequence_2 \rangle$ will be placed at the left side of the new sequence.

```

\seq_if_exist_p:N *
\seq_if_exist_p:c *
\seq_if_exist:NTF *
\seq_if_exist:cTF *

```

New: 2012-03-03

```
\seq_if_exist_p:N <sequence>
```

```
\seq_if_exist:NTF <sequence> {<true code>} {<false code>}
```

Tests whether the $\langle sequence \rangle$ is currently defined. This does not check that the $\langle sequence \rangle$ really is a sequence variable.

2 Appending data to sequences

```

\seq_put_left:Nn
\seq_put_left:(NV|Nv|No|Nx|cn|cV|cv|co|cx)
\seq_gput_left:Nn
\seq_gput_left:(NV|Nv|No|Nx|cn|cV|cv|co|cx)

```

```
\seq_put_left:Nn <sequence> {<item>}
```

Appends the $\langle item \rangle$ to the left of the $\langle sequence \rangle$.

```

\seq_put_right:Nn
\seq_put_right:(NV|Nv|No|Nx|cn|cV|cv|co|cx)
\seq_gput_right:Nn
\seq_gput_right:(NV|Nv|No|Nx|cn|cV|cv|co|cx)

```

```
\seq_put_right:Nn <sequence> {<item>}
```

Appends the $\langle item \rangle$ to the right of the $\langle sequence \rangle$.

3 Recovering items from sequences

Items can be recovered from either the left or the right of sequences. For implementation reasons, the actions at the left of the sequence are faster than those acting on the right. These functions all assign the recovered material locally, *i.e.* setting the $\langle token list variable \rangle$ used with `\tl_set:Nn` and *never* `\tl_gset:Nn`.

```

\seq_get_left:NN
\seq_get_left:cN

```

Updated: 2012-05-14

```
\seq_get_left:NN <sequence> <token list variable>
```

Stores the left-most item from a $\langle sequence \rangle$ in the $\langle token list variable \rangle$ without removing it from the $\langle sequence \rangle$. The $\langle token list variable \rangle$ is assigned locally. If $\langle sequence \rangle$ is empty the $\langle token list variable \rangle$ will contain the special marker `\q_no_value`.

| | |
|---|---|
| <hr/> <code>\seq_get_right:NN</code> <code>\seq_get_right:cN</code> <hr/> Updated: 2012-05-19 | <code>\seq_get_right:NN</code> $\langle sequence \rangle$ $\langle token list variable \rangle$ Stores the right-most item from a $\langle sequence \rangle$ in the $\langle token list variable \rangle$ without removing it from the $\langle sequence \rangle$. The $\langle token list variable \rangle$ is assigned locally. If $\langle sequence \rangle$ is empty the $\langle token list variable \rangle$ will contain the special marker <code>\q_no_value</code> . |
| <hr/> <code>\seq_pop_left:NN</code> <code>\seq_pop_left:cN</code> <hr/> Updated: 2012-05-14 | <code>\seq_pop_left:NN</code> $\langle sequence \rangle$ $\langle token list variable \rangle$ Pops the left-most item from a $\langle sequence \rangle$ into the $\langle token list variable \rangle$, <i>i.e.</i> removes the item from the sequence and stores it in the $\langle token list variable \rangle$. Both of the variables are assigned locally. If $\langle sequence \rangle$ is empty the $\langle token list variable \rangle$ will contain the special marker <code>\q_no_value</code> . |
| <hr/> <code>\seq_gpop_left:NN</code> <code>\seq_gpop_left:cN</code> <hr/> Updated: 2012-05-14 | <code>\seq_gpop_left:NN</code> $\langle sequence \rangle$ $\langle token list variable \rangle$ Pops the left-most item from a $\langle sequence \rangle$ into the $\langle token list variable \rangle$, <i>i.e.</i> removes the item from the sequence and stores it in the $\langle token list variable \rangle$. The $\langle sequence \rangle$ is modified globally, while the assignment of the $\langle token list variable \rangle$ is local. If $\langle sequence \rangle$ is empty the $\langle token list variable \rangle$ will contain the special marker <code>\q_no_value</code> . |
| <hr/> <code>\seq_pop_right:NN</code> <code>\seq_pop_right:cN</code> <hr/> Updated: 2012-05-19 | <code>\seq_pop_right:NN</code> $\langle sequence \rangle$ $\langle token list variable \rangle$ Pops the right-most item from a $\langle sequence \rangle$ into the $\langle token list variable \rangle$, <i>i.e.</i> removes the item from the sequence and stores it in the $\langle token list variable \rangle$. Both of the variables are assigned locally. If $\langle sequence \rangle$ is empty the $\langle token list variable \rangle$ will contain the special marker <code>\q_no_value</code> . |
| <hr/> <code>\seq_gpop_right:NN</code> <code>\seq_gpop_right:cN</code> <hr/> Updated: 2012-05-19 | <code>\seq_gpop_right:NN</code> $\langle sequence \rangle$ $\langle token list variable \rangle$ Pops the right-most item from a $\langle sequence \rangle$ into the $\langle token list variable \rangle$, <i>i.e.</i> removes the item from the sequence and stores it in the $\langle token list variable \rangle$. The $\langle sequence \rangle$ is modified globally, while the assignment of the $\langle token list variable \rangle$ is local. If $\langle sequence \rangle$ is empty the $\langle token list variable \rangle$ will contain the special marker <code>\q_no_value</code> . |
| <hr/> <code>\seq_item:Nn</code> ★ <code>\seq_item:cn</code> ★ <hr/> New: 2014-07-17 | <code>\seq_item:Nn</code> $\langle sequence \rangle$ $\{ \langle integer expression \rangle \}$ Indexing items in the $\langle sequence \rangle$ from 1 at the top (left), this function will evaluate the $\langle integer expression \rangle$ and leave the appropriate item from the sequence in the input stream. If the $\langle integer expression \rangle$ is negative, indexing occurs from the bottom (right) of the sequence. When the $\langle integer expression \rangle$ is larger than the number of items in the $\langle sequence \rangle$ (as calculated by <code>\seq_count:N</code>) then the function will expand to nothing. |

T_EXhackers note: The result is returned within the `\unexpanded` primitive (`\exp_not:n`), which means that the $\langle item \rangle$ will not expand further when appearing in an x-type argument expansion.

4 Recovering values from sequences with branching

The functions in this section combine tests for non-empty sequences with recovery of an item from the sequence. They offer increased readability and performance over separate testing and recovery phases.

`\seq_get_left:NNTF`
`\seq_get_left:cNTF`

New: 2012-05-14
Updated: 2012-05-19

`\seq_get_left:NNTF` $\langle sequence \rangle$ $\langle token list variable \rangle$ $\{\langle true code \rangle\}$ $\{\langle false code \rangle\}$

If the $\langle sequence \rangle$ is empty, leaves the $\langle false code \rangle$ in the input stream. The value of the $\langle token list variable \rangle$ is not defined in this case and should not be relied upon. If the $\langle sequence \rangle$ is non-empty, stores the left-most item from a $\langle sequence \rangle$ in the $\langle token list variable \rangle$ without removing it from a $\langle sequence \rangle$. The $\langle token list variable \rangle$ is assigned locally.

`\seq_get_right:NNTF`
`\seq_get_right:cNTF`

New: 2012-05-19

`\seq_get_right:NNTF` $\langle sequence \rangle$ $\langle token list variable \rangle$ $\{\langle true code \rangle\}$ $\{\langle false code \rangle\}$

If the $\langle sequence \rangle$ is empty, leaves the $\langle false code \rangle$ in the input stream. The value of the $\langle token list variable \rangle$ is not defined in this case and should not be relied upon. If the $\langle sequence \rangle$ is non-empty, stores the right-most item from a $\langle sequence \rangle$ in the $\langle token list variable \rangle$ without removing it from a $\langle sequence \rangle$. The $\langle token list variable \rangle$ is assigned locally.

`\seq_pop_left:NNTF`
`\seq_pop_left:cNTF`

New: 2012-05-14
Updated: 2012-05-19

`\seq_pop_left:NNTF` $\langle sequence \rangle$ $\langle token list variable \rangle$ $\{\langle true code \rangle\}$ $\{\langle false code \rangle\}$

If the $\langle sequence \rangle$ is empty, leaves the $\langle false code \rangle$ in the input stream. The value of the $\langle token list variable \rangle$ is not defined in this case and should not be relied upon. If the $\langle sequence \rangle$ is non-empty, pops the left-most item from a $\langle sequence \rangle$ in the $\langle token list variable \rangle$, *i.e.* removes the item from a $\langle sequence \rangle$. Both the $\langle sequence \rangle$ and the $\langle token list variable \rangle$ are assigned locally.

`\seq_gpop_left:NNTF`
`\seq_gpop_left:cNTF`

New: 2012-05-14
Updated: 2012-05-19

`\seq_gpop_left:NNTF` $\langle sequence \rangle$ $\langle token list variable \rangle$ $\{\langle true code \rangle\}$ $\{\langle false code \rangle\}$

If the $\langle sequence \rangle$ is empty, leaves the $\langle false code \rangle$ in the input stream. The value of the $\langle token list variable \rangle$ is not defined in this case and should not be relied upon. If the $\langle sequence \rangle$ is non-empty, pops the left-most item from a $\langle sequence \rangle$ in the $\langle token list variable \rangle$, *i.e.* removes the item from a $\langle sequence \rangle$. The $\langle sequence \rangle$ is modified globally, while the $\langle token list variable \rangle$ is assigned locally.

`\seq_pop_right:NNTF`
`\seq_pop_right:cNTF`

New: 2012-05-19

`\seq_pop_right:NNTF` $\langle sequence \rangle$ $\langle token list variable \rangle$ $\{\langle true code \rangle\}$ $\{\langle false code \rangle\}$

If the $\langle sequence \rangle$ is empty, leaves the $\langle false code \rangle$ in the input stream. The value of the $\langle token list variable \rangle$ is not defined in this case and should not be relied upon. If the $\langle sequence \rangle$ is non-empty, pops the right-most item from a $\langle sequence \rangle$ in the $\langle token list variable \rangle$, *i.e.* removes the item from a $\langle sequence \rangle$. Both the $\langle sequence \rangle$ and the $\langle token list variable \rangle$ are assigned locally.

`\seq_gpop_right:NNTF`
`\seq_gpop_right:cNTF`

New: 2012-05-19

`\seq_gpop_right:NNTF` $\langle sequence \rangle$ $\langle token list variable \rangle$ $\{\langle true code \rangle\}$ $\{\langle false code \rangle\}$

If the $\langle sequence \rangle$ is empty, leaves the $\langle false code \rangle$ in the input stream. The value of the $\langle token list variable \rangle$ is not defined in this case and should not be relied upon. If the $\langle sequence \rangle$ is non-empty, pops the right-most item from a $\langle sequence \rangle$ in the $\langle token list variable \rangle$, *i.e.* removes the item from a $\langle sequence \rangle$. The $\langle sequence \rangle$ is modified globally, while the $\langle token list variable \rangle$ is assigned locally.

5 Modifying sequences

While sequences are normally used as ordered lists, it may be necessary to modify the content. The functions here may be used to update sequences, while retaining the order of the unaffected entries.

```
\seq_remove_duplicates:N
\seq_remove_duplicates:c
\seq_gremove_duplicates:N
\seq_gremove_duplicates:c
```

```
\seq_remove_duplicates:N <sequence>
```

Removes duplicate items from the $\langle sequence \rangle$, leaving the left most copy of each item in the $\langle sequence \rangle$. The $\langle item \rangle$ comparison takes place on a token basis, as for `\tl_if_eq:nnTF`.

TeXhackers note: This function iterates through every item in the $\langle sequence \rangle$ and does a comparison with the $\langle items \rangle$ already checked. It is therefore relatively slow with large sequences.

```
\seq_remove_all:Nn
\seq_remove_all:cn
\seq_gremove_all:Nn
\seq_gremove_all:cn
```

```
\seq_remove_all:Nn <sequence> {<item>}
```

Removes every occurrence of $\langle item \rangle$ from the $\langle sequence \rangle$. The $\langle item \rangle$ comparison takes place on a token basis, as for `\tl_if_eq:nnTF`.

```
\seq_reverse:N
\seq_reverse:c
\seq_greverse:N
\seq_greverse:c
```

```
\seq_reverse:N <sequence>
```

Reverses the order of the items stored in the $\langle sequence \rangle$.

New: 2014-07-18

```
\seq_sort:Nn
\seq_sort:cn
\seq_gsort:Nn
\seq_gsort:cn
```

```
\seq_sort:Nn <sequence> {<comparison code>}
```

Sorts the items in the $\langle sequence \rangle$ according to the $\langle comparison code \rangle$, and assigns the result to $\langle sequence \rangle$. The details of sorting comparison are described in Section 1.

New: 2017-02-06

6 Sequence conditionals

```
\seq_if_empty_p:N ★
\seq_if_empty_p:c ★
\seq_if_empty:NTF ★
\seq_if_empty:cTF ★
```

```
\seq_if_empty_p:N <sequence>
```

```
\seq_if_empty:NNTF <sequence> {<true code>} {<false code>}
```

Tests if the $\langle sequence \rangle$ is empty (containing no items).

```
\seq_if_in:NnTF
\seq_if_in:(Nv|Nv|No|Nx|cn|cV|cv|co|cx)TF
```

```
\seq_if_in:NnTF <sequence> {<item>} {<true code>} {<false code>}
```

Tests if the $\langle item \rangle$ is present in the $\langle sequence \rangle$.

7 Mapping to sequences

```
\seq_map_function:NN ★
\seq_map_function:cN ★
```

Updated: 2012-06-29

```
\seq_map_function:NN <sequence> <function>
```

Applies $\langle function \rangle$ to every $\langle item \rangle$ stored in the $\langle sequence \rangle$. The $\langle function \rangle$ will receive one argument for each iteration. The $\langle items \rangle$ are returned from left to right. The function `\seq_map_inline:Nn` is faster than `\seq_map_function:NN` for sequences with more than about 10 items. One mapping may be nested inside another.

| | |
|---|---|
| <hr/> <code>\seq_map_inline:Nn</code> <hr/> | <code>\seq_map_inline:Nn <sequence> {<inline function>}</code> |
| <code>\seq_map_inline:cn</code> <hr/> | Applies <i><inline function></i> to every <i><item></i> stored within the <i><sequence></i> . The <i><inline function></i> should consist of code which will receive the <i><item></i> as #1. One in line mapping can be nested inside another. The <i><items></i> are returned from left to right. |
| Updated: 2012-06-29 | |

| | |
|--|---|
| <hr/> <code>\seq_map_variable:NNn</code> <hr/> | <code>\seq_map_variable:NNn <sequence> <tl var.> {<function using tl var.>}</code> |
| <code>\seq_map_variable:(Ncn cNn ccn)</code> <hr/> | |
| Updated: 2012-06-29 | |
| | Stores each entry in the <i><sequence></i> in turn in the <i><tl var.></i> and applies the <i><function using tl var.></i> The <i><function></i> will usually consist of code making use of the <i><tl var.></i> , but this is not enforced. One variable mapping can be nested inside another. The <i><items></i> are returned from left to right. |

| | |
|--|--|
| <hr/> <code>\seq_map_break: ☆</code> <hr/> | <code>\seq_map_break:</code> |
| Updated: 2012-06-29 | Used to terminate a <code>\seq_map...</code> function before all entries in the <i><sequence></i> have been processed. This will normally take place within a conditional statement, for example |

```

\seq_map_inline:Nn \l_my_seq
{
  \str_if_eq:nnTF { #1 } { bingo }
  { \seq_map_break: }
  {
    % Do something useful
  }
}

```

Use outside of a `\seq_map...` scenario will lead to low level T_EX errors.

T_EXhackers note: When the mapping is broken, additional tokens may be inserted by the internal macro `__prg_break_point:Nn` before further items are taken from the input stream. This will depend on the design of the mapping function.

`\seq_map_break:n` ☆

Updated: 2012-06-29

`\seq_map_break:n` {*tokens*}

Used to terminate a `\seq_map...` function before all entries in the *sequence* have been processed, inserting the *tokens* after the mapping has ended. This will normally take place within a conditional statement, for example

```
\seq_map_inline:Nn \l_my_seq
{
  \str_if_eq:nnTF { #1 } { bingo }
  { \seq_map_break:n { <tokens> } }
  {
    % Do something useful
  }
}
```

Use outside of a `\seq_map...` scenario will lead to low level T_EX errors.

T_EXhackers note: When the mapping is broken, additional tokens may be inserted by the internal macro `__prg_break_point:Nn` before the *tokens* are inserted into the input stream. This will depend on the design of the mapping function.

`\seq_count:N` ☆

`\seq_count:c` ☆

New: 2012-07-13

`\seq_count:N` *sequence*

Leaves the number of items in the *sequence* in the input stream as an *integer denotation*. The total number of items in a *sequence* will include those which are empty and duplicates, *i.e.* every item in a *sequence* is unique.

8 Using the content of sequences directly

`\seq_use:Nnnn` ☆

`\seq_use:cnnn` ☆

New: 2013-05-26

`\seq_use:Nnnn` *seq var* {*separator between two*}

{*separator between more than two*} {*separator between final two*}

Places the contents of the *seq var* in the input stream, with the appropriate *separator* between the items. Namely, if the sequence has more than two items, the *separator between more than two* is placed between each pair of items except the last, for which the *separator between final two* is used. If the sequence has exactly two items, then they are placed in the input stream separated by the *separator between two*. If the sequence has a single item, it is placed in the input stream, and an empty sequence produces no output. An error will be raised if the variable does not exist or if it is invalid.

For example,

```
\seq_set_split:Nnn \l_tmpa_seq { | } { a | b | c | {de} | f }
\seq_use:Nnnn \l_tmpa_seq { ~and~ } { ,~ } { ,~and~ }
```

will insert “a, b, c, de, and f” in the input stream. The first separator argument is not used in this case because the sequence has more than 2 items.

T_EXhackers note: The result is returned within the `\unexpanded` primitive (`\exp_not:n`), which means that the *items* will not expand further when appearing in an x-type argument expansion.

`\seq_use:Nn` ★
`\seq_use:cn` ★

New: 2013-05-26

`\seq_use:Nn` $\langle seq\ var \rangle$ $\{\langle separator \rangle\}$

Places the contents of the $\langle seq\ var \rangle$ in the input stream, with the $\langle separator \rangle$ between the items. If the sequence has a single item, it is placed in the input stream with no $\langle separator \rangle$, and an empty sequence produces no output. An error will be raised if the variable does not exist or if it is invalid.

For example,

```
\seq_set_split:Nnn \l_tmpa_seq { | } { a | b | c | {de} | f }
\seq_use:Nn \l_tmpa_seq { ~and~ }
```

will insert “a and b and c and de and f” in the input stream.

TeXhackers note: The result is returned within the `\unexpanded` primitive (`\exp_not:n`), which means that the $\langle items \rangle$ will not expand further when appearing in an `x`-type argument expansion.

9 Sequences as stacks

Sequences can be used as stacks, where data is pushed to and popped from the top of the sequence. (The left of a sequence is the top, for performance reasons.) The stack functions for sequences are not intended to be mixed with the general ordered data functions detailed in the previous section: a sequence should either be used as an ordered data type or as a stack, but not in both ways.

`\seq_get:NN`
`\seq_get:cn`

Updated: 2012-05-14

`\seq_get:NN` $\langle sequence \rangle$ $\langle token\ list\ variable \rangle$

Reads the top item from a $\langle sequence \rangle$ into the $\langle token\ list\ variable \rangle$ without removing it from the $\langle sequence \rangle$. The $\langle token\ list\ variable \rangle$ is assigned locally. If $\langle sequence \rangle$ is empty the $\langle token\ list\ variable \rangle$ will contain the special marker `\q_no_value`.

`\seq_pop:NN`
`\seq_pop:cn`

Updated: 2012-05-14

`\seq_pop:NN` $\langle sequence \rangle$ $\langle token\ list\ variable \rangle$

Pops the top item from a $\langle sequence \rangle$ into the $\langle token\ list\ variable \rangle$. Both of the variables are assigned locally. If $\langle sequence \rangle$ is empty the $\langle token\ list\ variable \rangle$ will contain the special marker `\q_no_value`.

`\seq_gpop:NN`
`\seq_gpop:cn`

Updated: 2012-05-14

`\seq_gpop:NN` $\langle sequence \rangle$ $\langle token\ list\ variable \rangle$

Pops the top item from a $\langle sequence \rangle$ into the $\langle token\ list\ variable \rangle$. The $\langle sequence \rangle$ is modified globally, while the $\langle token\ list\ variable \rangle$ is assigned locally. If $\langle sequence \rangle$ is empty the $\langle token\ list\ variable \rangle$ will contain the special marker `\q_no_value`.

`\seq_get:NNTF`
`\seq_get:cNTF`

New: 2012-05-14
Updated: 2012-05-19

`\seq_get:NNTF` $\langle sequence \rangle$ $\langle token\ list\ variable \rangle$ $\{\langle true\ code \rangle\}$ $\{\langle false\ code \rangle\}$

If the $\langle sequence \rangle$ is empty, leaves the $\langle false\ code \rangle$ in the input stream. The value of the $\langle token\ list\ variable \rangle$ is not defined in this case and should not be relied upon. If the $\langle sequence \rangle$ is non-empty, stores the top item from a $\langle sequence \rangle$ in the $\langle token\ list\ variable \rangle$ without removing it from the $\langle sequence \rangle$. The $\langle token\ list\ variable \rangle$ is assigned locally.

`\seq_pop:NNTF`
`\seq_pop:cNTF`

New: 2012-05-14
Updated: 2012-05-19

`\seq_pop:NNTF <sequence> <token list variable> {\true code} {\false code}`

If the `<sequence>` is empty, leaves the `<false code>` in the input stream. The value of the `<token list variable>` is not defined in this case and should not be relied upon. If the `<sequence>` is non-empty, pops the top item from the `<sequence>` in the `<token list variable>`, *i.e.* removes the item from the `<sequence>`. Both the `<sequence>` and the `<token list variable>` are assigned locally.

`\seq_gpop:NNTF`
`\seq_gpop:cNTF`

New: 2012-05-14
Updated: 2012-05-19

`\seq_gpop:NNTF <sequence> <token list variable> {\true code} {\false code}`

If the `<sequence>` is empty, leaves the `<false code>` in the input stream. The value of the `<token list variable>` is not defined in this case and should not be relied upon. If the `<sequence>` is non-empty, pops the top item from the `<sequence>` in the `<token list variable>`, *i.e.* removes the item from the `<sequence>`. The `<sequence>` is modified globally, while the `<token list variable>` is assigned locally.

`\seq_push:Nn`
`\seq_push:(NV|Nv|No|Nx|cn|cV|cv|co|cx)`
`\seq_gpush:Nn`
`\seq_gpush:(NV|Nv|No|Nx|cn|cV|cv|co|cx)`

`\seq_push:Nn <sequence> {\item}`

Adds the `{\item}` to the top of the `<sequence>`.

10 Sequences as sets

Sequences can also be used as sets, such that all of their items are distinct. Usage of sequences as sets is not currently widespread, hence no specific set function is provided. Instead, it is explained here how common set operations can be performed by combining several functions described in earlier sections. When using sequences to implement sets, one should be careful not to rely on the order of items in the sequence representing the set.

Sets should not contain several occurrences of a given item. To make sure that a `<sequence variable>` only has distinct items, use `\seq_remove_duplicates:N <sequence variable>`. This function is relatively slow, and to avoid performance issues one should only use it when necessary.

Some operations on a set `<seq var>` are straightforward. For instance, `\seq_count:N <seq var>` expands to the number of items, while `\seq_if_in:NnTF <seq var> {\item}` tests if the `<item>` is in the set.

Adding an `<item>` to a set `<seq var>` can be done by appending it to the `<seq var>` if it is not already in the `<seq var>`:

```
\seq_if_in:NnF <seq var> {\item}
{ \seq_put_right:Nn <seq var> {\item} }
```

Removing an `<item>` from a set `<seq var>` can be done using `\seq_remove_all:Nn`,

```
\seq_remove_all:Nn <seq var> {\item}
```

The intersection of two sets `<seq var1>` and `<seq var2>` can be stored into `<seq var3>` by collecting items of `<seq var1>` which are in `<seq var2>`.

```

\seq_clear:N <seq var3>
\seq_map_inline:Nn <seq var1>
{
\seq_if_in:NnT <seq var2> {#1}
{ \seq_put_right:Nn <seq var3> {#1} }
}

```

The code as written here only works if $\langle seq\ var_3 \rangle$ is different from the other two sequence variables. To cover all cases, items should first be collected in a sequence $\backslash l_ \langle pkg \rangle_internal_seq$, then $\langle seq\ var_3 \rangle$ should be set equal to this internal sequence. The same remark applies to other set functions.

The union of two sets $\langle seq\ var_1 \rangle$ and $\langle seq\ var_2 \rangle$ can be stored into $\langle seq\ var_3 \rangle$ through

```

\seq_concat:NNN <seq var3> <seq var1> <seq var2>
\seq_remove_duplicates:N <seq var3>

```

or by adding items to (a copy of) $\langle seq\ var_1 \rangle$ one by one

```

\seq_set_eq:NN <seq var3> <seq var1>
\seq_map_inline:Nn <seq var2>
{
\seq_if_in:NnF <seq var3> {#1}
{ \seq_put_right:Nn <seq var3> {#1} }
}

```

The second approach is faster than the first when the $\langle seq\ var_2 \rangle$ is short compared to $\langle seq\ var_1 \rangle$.

The difference of two sets $\langle seq\ var_1 \rangle$ and $\langle seq\ var_2 \rangle$ can be stored into $\langle seq\ var_3 \rangle$ by removing items of the $\langle seq\ var_2 \rangle$ from (a copy of) the $\langle seq\ var_1 \rangle$ one by one.

```

\seq_set_eq:NN <seq var3> <seq var1>
\seq_map_inline:Nn <seq var2>
{ \seq_remove_all:Nn <seq var3> {#1} }

```

The symmetric difference of two sets $\langle seq\ var_1 \rangle$ and $\langle seq\ var_2 \rangle$ can be stored into $\langle seq\ var_3 \rangle$ by computing the difference between $\langle seq\ var_1 \rangle$ and $\langle seq\ var_2 \rangle$ and storing the result as $\backslash l_ \langle pkg \rangle_internal_seq$, then the difference between $\langle seq\ var_2 \rangle$ and $\langle seq\ var_1 \rangle$, and finally concatenating the two differences to get the symmetric differences.

```

\seq_set_eq:NN \l\_ \langle pkg \rangle\_internal\_seq <seq var1>
\seq_map_inline:Nn <seq var2>
{ \seq_remove_all:Nn \l\_ \langle pkg \rangle\_internal\_seq {#1} }
\seq_set_eq:NN <seq var3> <seq var2>
\seq_map_inline:Nn <seq var1>
{ \seq_remove_all:Nn <seq var3> {#1} }
\seq_concat:NNN <seq var3> <seq var3> \l\_ \langle pkg \rangle\_internal\_seq

```

11 Constant and scratch sequences

$\backslash c_empty_seq$ Constant that is always empty.

New: 2012-07-02

`\l_tmpa_seq`
`\l_tmpb_seq`

New: 2012-04-26

Scratch sequences for local assignment. These are never used by the kernel code, and so are safe for use with any L^AT_EX3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.

`\g_tmpa_seq`
`\g_tmpb_seq`

New: 2012-04-26

Scratch sequences for global assignment. These are never used by the kernel code, and so are safe for use with any L^AT_EX3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.

12 Viewing sequences

`\seq_show:N`
`\seq_show:c`

Updated: 2015-08-01

`\seq_show:N` $\langle sequence \rangle$
Displays the entries in the $\langle sequence \rangle$ in the terminal.

`\seq_log:N`
`\seq_log:c`

New: 2014-08-12
Updated: 2015-08-01

`\seq_log:N` $\langle sequence \rangle$
Writes the entries in the $\langle sequence \rangle$ in the log file.

13 Internal sequence functions

`\s__seq`

This scan mark (equal to `\scan_stop:`) marks the beginning of a sequence variable.

`__seq_item:n` ★

`__seq_item:n` $\{\langle item \rangle\}$

The internal token used to begin each sequence entry. If expanded outside of a mapping or manipulation function, an error will be raised. The definition should always be set globally.

`__seq_push_item_def:n`
`__seq_push_item_def:x`

`__seq_push_item_def:n` $\{\langle code \rangle\}$

Saves the definition of `__seq_item:n` and redefines it to accept one parameter and expand to $\langle code \rangle$. This function should always be balanced by use of `__seq_pop_item_def:.`

`__seq_pop_item_def:`

`__seq_pop_item_def:`

Restores the definition of `__seq_item:n` most recently saved by `__seq_push_item_def:n`. This function should always be used in a balanced pair with `__seq_push_item_def:.`

Part IX

The l3int package

Integers

Calculation and comparison of integer values can be carried out using literal numbers, `int` registers, constants and integers stored in token list variables. The standard operators `+`, `-`, `/` and `*` and parentheses can be used within such expressions to carry arithmetic operations. This module carries out these functions on *integer expressions* (“`intexpr`”).

1 Integer expressions

| | |
|----------------------------|---|
| <code>\int_eval:n</code> ★ | <code>\int_eval:n {⟨integer expression⟩}</code> |
|----------------------------|---|

Evaluates the *⟨integer expression⟩*, expanding any integer and token list variables within the *⟨expression⟩* to their content (without requiring `\int_use:N/\tl_use:N`) and applying the standard mathematical rules. For example both

```
\int_eval:n { 5 + 4 * 3 - ( 3 + 4 * 5 ) }
```

and

```
\tl_new:N \l_my_tl
\tl_set:Nn \l_my_tl { 5 }
\int_new:N \l_my_int
\int_set:Nn \l_my_int { 4 }
\int_eval:n { \l_my_tl + \l_my_int * 3 - ( 3 + 4 * 5 ) }
```

both evaluate to -6 . The *⟨integer expression⟩* may contain the operators `+`, `-`, `*` and `/`, along with parenthesis `(` and `)`. Any functions within the expressions should expand to an *⟨integer denotation⟩*: a sequence of a sign and digits matching the regex `\-?[0-9]+`. After expansion `\int_eval:n` yields an *⟨integer denotation⟩* which is left in the input stream.

T_EXhackers note: Exactly two expansions are needed to evaluate `\int_eval:n`. The result is *not* an *⟨internal integer⟩*, and therefore requires suitable termination if used in a T_EX-style integer assignment.

| | |
|---------------------------|--|
| <code>\int_abs:n</code> ★ | <code>\int_abs:n {⟨integer expression⟩}</code> |
|---------------------------|--|

Updated: 2012-09-26 Evaluates the *⟨integer expression⟩* as described for `\int_eval:n` and leaves the absolute value of the result in the input stream as an *⟨integer denotation⟩* after two expansions.

| | |
|----------------------------------|--|
| <code>\int_div_round:nn</code> ★ | <code>\int_div_round:nn {⟨intexpr₁⟩} {⟨intexpr₂⟩}</code> |
|----------------------------------|--|

Updated: 2012-09-26 Evaluates the two *⟨integer expressions⟩* as described earlier, then divides the first value by the second, and rounds the result to the closest integer. Ties are rounded away from zero. Note that this is identical to using `/` directly in an *⟨integer expression⟩*. The result is left in the input stream as an *⟨integer denotation⟩* after two expansions.

| | |
|---|--|
| <hr/> <code>\int_div_truncate:nn</code> ★ <hr/> | <code>\int_div_truncate:nn {\langle integer_1 \rangle} {\langle integer_2 \rangle}</code> |
| Updated: 2012-02-09 | Evaluates the two $\langle integer expressions \rangle$ as described earlier, then divides the first value by the second, and rounds the result towards zero. Note that division using <code>/</code> rounds to the closest integer instead. The result is left in the input stream as an $\langle integer denotation \rangle$ after two expansions. |

| | |
|----------------------------------|--|
| <hr/> <code>\int_max:nn</code> ★ | <code>\int_max:nn {\langle integer_1 \rangle} {\langle integer_2 \rangle}</code> |
| <hr/> <code>\int_min:nn</code> ★ | <code>\int_min:nn {\langle integer_1 \rangle} {\langle integer_2 \rangle}</code> |
| Updated: 2012-09-26 | Evaluates the $\langle integer expressions \rangle$ as described for <code>\int_eval:n</code> and leaves either the larger or smaller value in the input stream as an $\langle integer denotation \rangle$ after two expansions. |

| | |
|----------------------------------|---|
| <hr/> <code>\int_mod:nn</code> ★ | <code>\int_mod:nn {\langle integer_1 \rangle} {\langle integer_2 \rangle}</code> |
| Updated: 2012-09-26 | Evaluates the two $\langle integer expressions \rangle$ as described earlier, then calculates the integer remainder of dividing the first expression by the second. This is obtained by subtracting <code>\int_div_truncate:nn {\langle integer_1 \rangle} {\langle integer_2 \rangle}</code> times $\langle integer_2 \rangle$ from $\langle integer_1 \rangle$. Thus, the result has the same sign as $\langle integer_1 \rangle$ and its absolute value is strictly less than that of $\langle integer_2 \rangle$. The result is left in the input stream as an $\langle integer denotation \rangle$ after two expansions. |

2 Creating and initialising integers

| | |
|-------------------------------|---|
| <hr/> <code>\int_new:N</code> | <code>\int_new:N \langle integer \rangle</code> |
| <hr/> <code>\int_new:c</code> | Creates a new $\langle integer \rangle$ or raises an error if the name is already taken. The declaration is global. The $\langle integer \rangle$ will initially be equal to 0. |

| | |
|----------------------------------|---|
| <hr/> <code>\int_const:Nn</code> | <code>\int_const:Nn \langle integer \rangle {\langle integer expression \rangle}</code> |
| <hr/> <code>\int_const:cn</code> | Creates a new constant $\langle integer \rangle$ or raises an error if the name is already taken. The value of the $\langle integer \rangle$ will be set globally to the $\langle integer expression \rangle$. |
| Updated: 2011-10-22 | |

| | |
|---------------------------------|--|
| <hr/> <code>\int_zero:N</code> | <code>\int_zero:N \langle integer \rangle</code> |
| <hr/> <code>\int_zero:c</code> | Sets $\langle integer \rangle$ to 0. |
| <hr/> <code>\int_gzero:N</code> | |
| <hr/> <code>\int_gzero:c</code> | |

| | |
|-------------------------------------|---|
| <hr/> <code>\int_zero_new:N</code> | <code>\int_zero_new:N \langle integer \rangle</code> |
| <hr/> <code>\int_zero_new:c</code> | Ensures that the $\langle integer \rangle$ exists globally by applying <code>\int_new:N</code> if necessary, then applies <code>\int_(g)zero:N</code> to leave the $\langle integer \rangle$ set to zero. |
| <hr/> <code>\int_gzero_new:N</code> | |
| <hr/> <code>\int_gzero_new:c</code> | |
| New: 2011-12-13 | |

| | |
|--|--|
| <hr/> <code>\int_set_eq:NN</code> | <code>\int_set_eq:NN \langle integer_1 \rangle \langle integer_2 \rangle</code> |
| <hr/> <code>\int_set_eq:(cN Nc cc)</code> | Sets the content of $\langle integer_1 \rangle$ equal to that of $\langle integer_2 \rangle$. |
| <hr/> <code>\int_gset_eq:NN</code> | |
| <hr/> <code>\int_gset_eq:(cN Nc cc)</code> | |

| | | |
|---|---|---|
| <code>\int_if_exist_p:N</code> | ★ | <code>\int_if_exist_p:N <integer></code> |
| <code>\int_if_exist_p:c</code> | ★ | <code>\int_if_exist:NTF <integer> {\true code} {\false code}</code> |
| <code>\int_if_exist:N\underline{TF}</code> | ★ | Tests whether the $\langle integer \rangle$ is currently defined. This does not check that the $\langle integer \rangle$ really is an integer variable. |
| <code>\int_if_exist:c\underline{TF}</code> | ★ | |

New: 2012-03-03

3 Setting and incrementing integers

| | |
|---------------------------|---|
| <code>\int_add:Nn</code> | <code>\int_add:Nn <integer> {\integer expression}</code> |
| <code>\int_add:cn</code> | Adds the result of the $\langle integer expression \rangle$ to the current content of the $\langle integer \rangle$. |
| <code>\int_gadd:Nn</code> | |
| <code>\int_gadd:cn</code> | |

Updated: 2011-10-22

| | |
|---------------------------|---|
| <code>\int_decr:N</code> | <code>\int_decr:N <integer></code> |
| <code>\int_decr:c</code> | Decreases the value stored in $\langle integer \rangle$ by 1. |
| <code>\int_gdecr:N</code> | |
| <code>\int_gdecr:c</code> | |

| | |
|---------------------------|---|
| <code>\int_incr:N</code> | <code>\int_incr:N <integer></code> |
| <code>\int_incr:c</code> | Increases the value stored in $\langle integer \rangle$ by 1. |
| <code>\int_gincr:N</code> | |
| <code>\int_gincr:c</code> | |

| | |
|---------------------------|---|
| <code>\int_set:Nn</code> | <code>\int_set:Nn <integer> {\integer expression}</code> |
| <code>\int_set:cn</code> | Sets $\langle integer \rangle$ to the value of $\langle integer expression \rangle$, which must evaluate to an integer (as described for <code>\int_eval:n</code>). |
| <code>\int_gset:Nn</code> | |
| <code>\int_gset:cn</code> | |

Updated: 2011-10-22

| | |
|---------------------------|--|
| <code>\int_sub:Nn</code> | <code>\int_sub:Nn <integer> {\integer expression}</code> |
| <code>\int_sub:cn</code> | Subtracts the result of the $\langle integer expression \rangle$ from the current content of the $\langle integer \rangle$. |
| <code>\int_gsub:Nn</code> | |
| <code>\int_gsub:cn</code> | |

Updated: 2011-10-22

4 Using integers

| | | |
|-------------------------|---|--|
| <code>\int_use:N</code> | ★ | <code>\int_use:N <integer></code> |
| <code>\int_use:c</code> | ★ | Recovers the content of an <i><integer></i> and places it directly in the input stream. An error will be raised if the variable does not exist or if it is invalid. Can be omitted in places where an <i><integer></i> is required (such as in the first and third arguments of <code>\int_compare:nNnTF</code>). |
| | | |

Updated: 2011-10-22

Updated: 2011-10-22

TeXhackers note: `\int_use:N` is the TeX primitive `\the`: this is one of several L^AT_EX3 names for this primitive.

5 Integer expression conditionals

```

\int_compare_p:nNn ★ \int_compare_p:nNn {\langle intexpr_1 \rangle} \langle relation \rangle {\langle intexpr_2 \rangle}
\int_compare:nNnTF ★ \int_compare:nNnTF
                        {\langle intexpr_1 \rangle} \langle relation \rangle {\langle intexpr_2 \rangle}
                        {\langle true code \rangle} {\langle false code \rangle}

```

This function first evaluates each of the $\langle integer\ expressions \rangle$ as described for `\int_eval:n`. The two results are then compared using the $\langle relation \rangle$:

| | |
|--------------|---|
| Equal | = |
| Greater than | > |
| Less than | < |

```

\int_compare_p:n ★ \int_compare_p:n
\int_compare:nTF ★ {
                    \langle intexpr_1 \rangle \langle relation_1 \rangle
                    ...
                    \langle intexpr_N \rangle \langle relation_N \rangle
                    \langle intexpr_{N+1} \rangle
                }
\int_compare:nTF
{
    \langle intexpr_1 \rangle \langle relation_1 \rangle
    ...
    \langle intexpr_N \rangle \langle relation_N \rangle
    \langle intexpr_{N+1} \rangle
}
{\langle true code \rangle} {\langle false code \rangle}

```

Updated: 2013-01-13

This function evaluates the $\langle integer\ expressions \rangle$ as described for `\int_eval:n` and compares consecutive result using the corresponding $\langle relation \rangle$, namely it compares $\langle intexpr_1 \rangle$ and $\langle intexpr_2 \rangle$ using the $\langle relation_1 \rangle$, then $\langle intexpr_2 \rangle$ and $\langle intexpr_3 \rangle$ using the $\langle relation_2 \rangle$, until finally comparing $\langle intexpr_N \rangle$ and $\langle intexpr_{N+1} \rangle$ using the $\langle relation_N \rangle$. The test yields **true** if all comparisons are **true**. Each $\langle integer\ expression \rangle$ is evaluated only once, and the evaluation is lazy, in the sense that if one comparison is **false**, then no other $\langle integer\ expression \rangle$ is evaluated and no other comparison is performed. The $\langle relations \rangle$ can be any of the following:

| | |
|--------------------------|---------|
| Equal | = or == |
| Greater than or equal to | >= |
| Greater than | > |
| Less than or equal to | <= |
| Less than | < |
| Not equal | != |

| | | |
|-----------------------------|---|---|
| <code>\int_case:n</code> | ★ | <code>\int_case:nnTF {⟨test integer expression⟩}</code> |
| <code>\int_case:nnTF</code> | ★ | <code>{</code> |
| <hr/> New: 2013-07-24 <hr/> | | <code>{⟨intexpr case₁⟩} {⟨code case₁⟩}</code> |
| | | <code>{⟨intexpr case₂⟩} {⟨code case₂⟩}</code> |
| | | <code>...</code> |
| | | <code>{⟨intexpr case_n⟩} {⟨code case_n⟩}</code> |
| | | <code>}</code> |
| | | <code>{⟨true code⟩}</code> |
| | | <code>{⟨false code⟩}</code> |

This function evaluates the *⟨test integer expression⟩* and compares this in turn to each of the *⟨integer expression cases⟩*. If the two are equal then the associated *⟨code⟩* is left in the input stream. If any of the cases are matched, the *⟨true code⟩* is also inserted into the input stream (after the code for the appropriate case), while if none match then the *⟨false code⟩* is inserted. The function `\int_case:nn`, which does nothing if there is no match, is also available. For example

```
\int_case:nnF
{ 2 * 5 }
{
  { 5 }      { Small }
  { 4 + 6 }   { Medium }
  { -2 * 10 } { Negative }
}
{ No idea! }
```

will leave “Medium” in the input stream.

| | | |
|-------------------------------|---|---|
| <code>\int_if_even_p:n</code> | ★ | <code>\int_if_odd_p:n {⟨integer expression⟩}</code> |
| <code>\int_if_even:nTF</code> | ★ | <code>\int_if_odd:nTF {⟨integer expression⟩}</code> |
| <code>\int_if_odd_p:n</code> | ★ | <code>{⟨true code⟩} {⟨false code⟩}</code> |
| <code>\int_if_odd:nTF</code> | ★ | |

This function first evaluates the *⟨integer expression⟩* as described for `\int_eval:n`. It then evaluates if this is odd or even, as appropriate.

6 Integer expression loops

| | | |
|---------------------------------|---|---|
| <code>\int_do_until:nNnn</code> | ☆ | <code>\int_do_until:nNnn {⟨intexpr₁⟩} ⟨relation⟩ {⟨intexpr₂⟩} {⟨code⟩}</code> |
|---------------------------------|---|---|

Places the *⟨code⟩* in the input stream for T_EX to process, and then evaluates the relationship between the two *⟨integer expressions⟩* as described for `\int_compare:nNnTF`. If the test is **false** then the *⟨code⟩* will be inserted into the input stream again and a loop will occur until the *⟨relation⟩* is **true**.

| | | |
|---------------------------------|---|---|
| <code>\int_do_while:nNnn</code> | ☆ | <code>\int_do_while:nNnn {⟨intexpr₁⟩} ⟨relation⟩ {⟨intexpr₂⟩} {⟨code⟩}</code> |
|---------------------------------|---|---|

Places the *⟨code⟩* in the input stream for T_EX to process, and then evaluates the relationship between the two *⟨integer expressions⟩* as described for `\int_compare:nNnTF`. If the test is **true** then the *⟨code⟩* will be inserted into the input stream again and a loop will occur until the *⟨relation⟩* is **false**.

| | |
|---|---|
| <hr/> <code>\int_until_do:nNnn</code> ☆ <hr/> | <code>\int_until_do:nNnn {⟨intexpr₁⟩} ⟨relation⟩ {⟨intexpr₂⟩} {⟨code⟩}</code> |
| | Evaluates the relationship between the two <i>⟨integer expressions⟩</i> as described for <code>\int_compare:nNnTF</code> , and then places the <i>⟨code⟩</i> in the input stream if the <i>⟨relation⟩</i> is false . After the <i>⟨code⟩</i> has been processed by T _E X the test will be repeated, and a loop will occur until the test is true . |
| <hr/> <code>\int_while_do:nNnn</code> ☆ <hr/> | <code>\int_while_do:nNnn {⟨intexpr₁⟩} ⟨relation⟩ {⟨intexpr₂⟩} {⟨code⟩}</code> |
| | Evaluates the relationship between the two <i>⟨integer expressions⟩</i> as described for <code>\int_compare:nNnTF</code> , and then places the <i>⟨code⟩</i> in the input stream if the <i>⟨relation⟩</i> is true . After the <i>⟨code⟩</i> has been processed by T _E X the test will be repeated, and a loop will occur until the test is false . |
| <hr/> <code>\int_do_until:nn</code> ☆ <hr/> | <code>\int_do_until:nn {⟨integer relation⟩} {⟨code⟩}</code> |
| Updated: 2013-01-13 | Places the <i>⟨code⟩</i> in the input stream for T _E X to process, and then evaluates the <i>⟨integer relation⟩</i> as described for <code>\int_compare:nTF</code> . If the test is false then the <i>⟨code⟩</i> will be inserted into the input stream again and a loop will occur until the <i>⟨relation⟩</i> is true . |
| <hr/> <code>\int_do_while:nn</code> ☆ <hr/> | <code>\int_do_while:nn {⟨integer relation⟩} {⟨code⟩}</code> |
| Updated: 2013-01-13 | Places the <i>⟨code⟩</i> in the input stream for T _E X to process, and then evaluates the <i>⟨integer relation⟩</i> as described for <code>\int_compare:nTF</code> . If the test is true then the <i>⟨code⟩</i> will be inserted into the input stream again and a loop will occur until the <i>⟨relation⟩</i> is false . |
| <hr/> <code>\int_until_do:nn</code> ☆ <hr/> | <code>\int_until_do:nn {⟨integer relation⟩} {⟨code⟩}</code> |
| Updated: 2013-01-13 | Evaluates the <i>⟨integer relation⟩</i> as described for <code>\int_compare:nTF</code> , and then places the <i>⟨code⟩</i> in the input stream if the <i>⟨relation⟩</i> is false . After the <i>⟨code⟩</i> has been processed by T _E X the test will be repeated, and a loop will occur until the test is true . |
| <hr/> <code>\int_while_do:nn</code> ☆ <hr/> | <code>\int_while_do:nn {⟨integer relation⟩} {⟨code⟩}</code> |
| Updated: 2013-01-13 | Evaluates the <i>⟨integer relation⟩</i> as described for <code>\int_compare:nTF</code> , and then places the <i>⟨code⟩</i> in the input stream if the <i>⟨relation⟩</i> is true . After the <i>⟨code⟩</i> has been processed by T _E X the test will be repeated, and a loop will occur until the test is false . |

7 Integer step functions

`\int_step_function:nnnN` ★

New: 2012-06-04

Updated: 2014-05-30

`\int_step_function:nnnN` $\langle initial\ value \rangle$ $\langle step \rangle$ $\langle final\ value \rangle$ $\langle function \rangle$

This function first evaluates the $\langle initial\ value \rangle$, $\langle step \rangle$ and $\langle final\ value \rangle$, all of which should be integer expressions. The $\langle function \rangle$ is then placed in front of each $\langle value \rangle$ from the $\langle initial\ value \rangle$ to the $\langle final\ value \rangle$ in turn (using $\langle step \rangle$ between each $\langle value \rangle$). The $\langle step \rangle$ must be non-zero. If the $\langle step \rangle$ is positive, the loop stops when the $\langle value \rangle$ becomes larger than the $\langle final\ value \rangle$. If the $\langle step \rangle$ is negative, the loop stops when the $\langle value \rangle$ becomes smaller than the $\langle final\ value \rangle$. The $\langle function \rangle$ should absorb one numerical argument. For example

```
\cs_set:Npn \my_func:n #1 { [I~saw~#1] \quad }
\int_step_function:nnnN { 1 } { 1 } { 5 } \my_func:n
```

would print

```
[I saw 1] [I saw 2] [I saw 3] [I saw 4] [I saw 5]
```

`\int_step_inline:nnnn`

New: 2012-06-04

Updated: 2014-05-30

`\int_step_inline:nnnn` $\langle initial\ value \rangle$ $\langle step \rangle$ $\langle final\ value \rangle$ $\langle code \rangle$

This function first evaluates the $\langle initial\ value \rangle$, $\langle step \rangle$ and $\langle final\ value \rangle$, all of which should be integer expressions. Then for each $\langle value \rangle$ from the $\langle initial\ value \rangle$ to the $\langle final\ value \rangle$ in turn (using $\langle step \rangle$ between each $\langle value \rangle$), the $\langle code \rangle$ is inserted into the input stream with `#1` replaced by the current $\langle value \rangle$. Thus the $\langle code \rangle$ should define a function of one argument (`#1`).

`\int_step_variable:nnnNn`

New: 2012-06-04

Updated: 2014-05-30

`\int_step_variable:nnnNn`
 $\langle initial\ value \rangle$ $\langle step \rangle$ $\langle final\ value \rangle$ $\langle tl\ var \rangle$ $\langle code \rangle$

This function first evaluates the $\langle initial\ value \rangle$, $\langle step \rangle$ and $\langle final\ value \rangle$, all of which should be integer expressions. Then for each $\langle value \rangle$ from the $\langle initial\ value \rangle$ to the $\langle final\ value \rangle$ in turn (using $\langle step \rangle$ between each $\langle value \rangle$), the $\langle code \rangle$ is inserted into the input stream, with the $\langle tl\ var \rangle$ defined as the current $\langle value \rangle$. Thus the $\langle code \rangle$ should make use of the $\langle tl\ var \rangle$.

8 Formatting integers

Integers can be placed into the output stream with formatting. These conversions apply to any integer expressions.

`\int_to_arabic:n` ★

Updated: 2011-10-22

`\int_to_arabic:n` $\langle integer\ expression \rangle$

Places the value of the $\langle integer\ expression \rangle$ in the input stream as digits, with category code 12 (other).

`\int_to_alph:n` ★ `\int_to_alph:n {⟨integer expression⟩}`

`\int_to_Alph:n` ★

Updated: 2011-09-17

Evaluates the *⟨integer expression⟩* and converts the result into a series of letters, which are then left in the input stream. The conversion rule uses the 26 letters of the English alphabet, in order, adding letters when necessary to increase the total possible range of representable numbers. Thus

```
\int_to_alph:n { 1 }
```

places **a** in the input stream,

```
\int_to_alph:n { 26 }
```

is represented as **z** and

```
\int_to_alph:n { 27 }
```

is converted to **aa**. For conversions using other alphabets, use `\int_to_symbols:nnn` to define an alphabet-specific function. The basic `\int_to_alph:n` and `\int_to_Alph:n` functions should not be modified. The resulting tokens are digits with category code 12 (other) and letters with category code 11 (letter).

`\int_to_symbols:nnn` ★

Updated: 2011-09-17

```
\int_to_symbols:nnn
  {⟨integer expression⟩} {⟨total symbols⟩}
  ⟨value to symbol mapping⟩
```

This is the low-level function for conversion of an *⟨integer expression⟩* into a symbolic form (which will often be letters). The *⟨total symbols⟩* available should be given as an integer expression. Values are actually converted to symbols according to the *⟨value to symbol mapping⟩*. This should be given as *⟨total symbols⟩* pairs of entries, a number and the appropriate symbol. Thus the `\int_to_alph:n` function is defined as

```
\cs_new:Npn \int_to_alph:n #1
{
  \int_to_symbols:nnn {#1} { 26 }
  {
    { 1 } { a }
    { 2 } { b }
    ...
    { 26 } { z }
  }
}
```

`\int_to_bin:n` ★

New: 2014-02-11

```
\int_to_bin:n {⟨integer expression⟩}
```

Calculates the value of the *⟨integer expression⟩* and places the binary representation of the result in the input stream.

| | |
|------------------------------|---|
| <code>\int_to_hex:n</code> ★ | <code>\int_to_hex:n {⟨integer expression⟩}</code> |
| <code>\int_to_Hex:n</code> ★ | Calculates the value of the <i>⟨integer expression⟩</i> and places the hexadecimal (base 16) representation of the result in the input stream. Letters are used for digits beyond 9: lower case letters for <code>\int_to_hex:n</code> and upper case ones for <code>\int_to_Hex:n</code> . The resulting tokens are digits with category code 12 (other) and letters with category code 11 (letter). |
| New: 2014-02-11 | |

| | |
|------------------------------|---|
| <code>\int_to_oct:n</code> ★ | <code>\int_to_oct:n {⟨integer expression⟩}</code> |
| New: 2014-02-11 | |
| | Calculates the value of the <i>⟨integer expression⟩</i> and places the octal (base 8) representation of the result in the input stream. The resulting tokens are digits with category code 12 (other) and letters with category code 11 (letter). |

| | |
|--------------------------------|---|
| <code>\int_to_base:nn</code> ★ | <code>\int_to_base:nn {⟨integer expression⟩} {⟨base⟩}</code> |
| <code>\int_to_Base:nn</code> ★ | Calculates the value of the <i>⟨integer expression⟩</i> and converts it into the appropriate representation in the <i>⟨base⟩</i> ; the later may be given as an integer expression. For bases greater than 10 the higher “digits” are represented by letters from the English alphabet: lower case letters for <code>\int_to_base:n</code> and upper case ones for <code>\int_to_Base:n</code> . The maximum <i>⟨base⟩</i> value is 36. The resulting tokens are digits with category code 12 (other) and letters with category code 11 (letter). |
| Updated: 2014-02-11 | |

TeXhackers note: This is a generic version of `\int_to_bin:n`, etc.

| | |
|--------------------------------|--|
| <code>\int_to_roman:n</code> ☆ | <code>\int_to_roman:n {⟨integer expression⟩}</code> |
| <code>\int_to_Roman:n</code> ☆ | Places the value of the <i>⟨integer expression⟩</i> in the input stream as Roman numerals, either lower case (<code>\int_to_roman:n</code>) or upper case (<code>\int_to_Roman:n</code>). The Roman numerals are letters with category code 11 (letter). |
| Updated: 2011-10-22 | |

9 Converting from other formats to integers

| | |
|---------------------------------|--|
| <code>\int_from_alph:n</code> ★ | <code>\int_from_alph:n {⟨letters⟩}</code> |
| Updated: 2014-08-25 | |
| | Converts the <i>⟨letters⟩</i> into the integer (base 10) representation and leaves this in the input stream. The <i>⟨letters⟩</i> are first converted to a string, with no expansion. Lower and upper case letters from the English alphabet may be used, with “a” equal to 1 through to “z” equal to 26. The function also accepts a leading sign, made of + and -. This is the inverse function of <code>\int_to_alph:n</code> and <code>\int_to_Alph:n</code> . |

| | |
|--------------------------------|--|
| <code>\int_from_bin:n</code> ★ | <code>\int_from_bin:n {⟨binary number⟩}</code> |
| New: 2014-02-11 | |
| Updated: 2014-08-25 | |
| | Converts the <i>⟨binary number⟩</i> into the integer (base 10) representation and leaves this in the input stream. The <i>⟨binary number⟩</i> is first converted to a string, with no expansion. The function accepts a leading sign, made of + and -, followed by binary digits. This is the inverse function of <code>\int_to_bin:n</code> . |

| | |
|--|---|
| <hr/> <code>\int_from_hex:n</code> ★ <hr/> | <code>\int_from_hex:n {⟨hexadecimal number⟩}</code> |
| New: 2014-02-11 Updated: 2014-08-25 <hr/> | Converts the <i>⟨hexadecimal number⟩</i> into the integer (base 10) representation and leaves this in the input stream. Digits greater than 9 may be represented in the <i>⟨hexadecimal number⟩</i> by upper or lower case letters. The <i>⟨hexadecimal number⟩</i> is first converted to a string, with no expansion. The function also accepts a leading sign, made of + and -. This is the inverse function of <code>\int_to_hex:n</code> and <code>\int_to_Hex:n</code> . |
| <hr/> <code>\int_from_oct:n</code> ★ <hr/> | <code>\int_from_oct:n {⟨octal number⟩}</code> |
| New: 2014-02-11 Updated: 2014-08-25 <hr/> | Converts the <i>⟨octal number⟩</i> into the integer (base 10) representation and leaves this in the input stream. The <i>⟨octal number⟩</i> is first converted to a string, with no expansion. The function accepts a leading sign, made of + and -, followed by octal digits. This is the inverse function of <code>\int_to_oct:n</code> . |
| <hr/> <code>\int_from_roman:n</code> ★ <hr/> | <code>\int_from_roman:n {⟨roman numeral⟩}</code> |
| Updated: 2014-08-25 <hr/> | Converts the <i>⟨roman numeral⟩</i> into the integer (base 10) representation and leaves this in the input stream. The <i>⟨roman numeral⟩</i> is first converted to a string, with no expansion. The <i>⟨roman numeral⟩</i> may be in upper or lower case; if the numeral contains characters besides <code>mdclxvi</code> or <code>MDCLXVI</code> then the resulting value will be -1. This is the inverse function of <code>\int_to_roman:n</code> and <code>\int_to_Roman:n</code> . |
| <hr/> <code>\int_from_base:nn</code> ★ <hr/> | <code>\int_from_base:nn {⟨number⟩} {⟨base⟩}</code> |
| Updated: 2014-08-25 <hr/> | Converts the <i>⟨number⟩</i> expressed in <i>⟨base⟩</i> into the appropriate value in base 10. The <i>⟨number⟩</i> is first converted to a string, with no expansion. The <i>⟨number⟩</i> should consist of digits and letters (either lower or upper case), plus optionally a leading sign. The maximum <i>⟨base⟩</i> value is 36. This is the inverse function of <code>\int_to_base:nn</code> and <code>\int_to_Base:nn</code> . |

10 Viewing integers

| | |
|--|--|
| <hr/> <code>\int_show:N</code> <code>\int_show:c</code> <hr/> | <code>\int_show:N ⟨integer⟩</code> |
| | Displays the value of the <i>⟨integer⟩</i> on the terminal. |
| <hr/> <code>\int_show:n</code> <hr/> | <code>\int_show:n {⟨integer expression⟩}</code> |
| New: 2011-11-22 Updated: 2015-08-07 <hr/> | Displays the result of evaluating the <i>⟨integer expression⟩</i> on the terminal. |
| <hr/> <code>\int_log:N</code> <code>\int_log:c</code> <hr/> | <code>\int_log:N ⟨integer⟩</code> |
| New: 2014-08-22 Updated: 2015-08-03 <hr/> | Writes the value of the <i>⟨integer⟩</i> in the log file. |
| <hr/> <code>\int_log:n</code> <hr/> | <code>\int_log:n {⟨integer expression⟩}</code> |
| New: 2014-08-22 Updated: 2015-08-07 <hr/> | Writes the result of evaluating the <i>⟨integer expression⟩</i> in the log file. |

11 Constant integers

`\c_zero`
`\c_one`
`\c_two`
`\c_three`
`\c_four`
`\c_five`
`\c_six`
`\c_seven`
`\c_eight`
`\c_nine`
`\c_ten`
`\c_eleven`
`\c_twelve`
`\c_thirteen`
`\c_fourteen`
`\c_fifteen`
`\c_sixteen`
`\c_thirty_two`
`\c_one_hundred`
`\c_two_hundred_fifty_five`
`\c_two_hundred_fifty_six`
`\c_one_thousand`
`\c_ten_thousand`

Integer values used with primitive tests and assignments: self-terminating nature makes these more convenient and faster than literal numbers.

`\c_max_int`

The maximum value that can be stored as an integer.

`\c_max_register_int`

Maximum number of registers.

`\c_max_char_int`

Maximum character code completely supported by the engine.

12 Scratch integers

`\l_tmpa_int`
`\l_tmpb_int`

Scratch integer for local assignment. These are never used by the kernel code, and so are safe for use with any L^AT_EX3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.

`\g_tmpa_int`
`\g_tmpb_int`

Scratch integer for global assignment. These are never used by the kernel code, and so are safe for use with any L^AT_EX3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.

13 Primitive conditionals

| | |
|----------------------------------|--|
| <code>\if_int_compare:w</code> ★ | <code>\if_int_compare:w <integer> <relation> <integer></code> <code> <true code></code> <code>\else:</code> <code> <false code></code> <code>\fi:</code> |
|----------------------------------|--|

Compare two integers using `<relation>`, which must be one of =, < or > with category code 12. The `\else:` branch is optional.

T_EXhackers note: These are both names for the T_EX primitive `\ifnum`.

| | |
|---------------------------|--|
| <code>\if_case:w</code> ★ | <code>\if_case:w <integer> <case₀></code> <code>\or: ★</code> <code> <case₁></code> <code> ... </code> <code> <default></code> <code>\fi:</code> |
|---------------------------|--|

Selects a case to execute based on the value of the `<integer>`. The first case (`<case0>`) is executed if `<integer>` is 0, the second (`<case1>`) if the `<integer>` is 1, *etc.* The `<integer>` may be a literal, a constant or an integer expression (*e.g.* using `\int_eval:n`).

T_EXhackers note: These are the T_EX primitives `\ifcase` and `\or`.

| | |
|------------------------------|--|
| <code>\if_int_odd:w</code> ★ | <code>\if_int_odd:w <tokens> <optional space></code> <code> <true code></code> <code>\else:</code> <code> <true code></code> <code>\fi:</code> |
|------------------------------|--|

Expands `<tokens>` until a non-numeric token or a space is found, and tests whether the resulting `<integer>` is odd. If so, `<true code>` is executed. The `\else:` branch is optional.

T_EXhackers note: This is the T_EX primitive `\ifodd`.

14 Internal functions

| | |
|----------------------------------|--|
| <code>__int_to_roman:w</code> ★ | <code>__int_to_roman:w <integer> <space> or <non-expandable token></code> |
|----------------------------------|--|

Converts `<integer>` to its lower case Roman representation. Expansion ends when a space or non-expandable token is found. Note that this function produces a string of letters with category code 12 and that protected functions *are* expanded by this process. Negative `<integer>` values result in no output, although the function does not terminate expansion until a suitable endpoint is found in the same way as for positive numbers.

T_EXhackers note: This is the T_EX primitive `\romannumeral` renamed.

| | | |
|-----------------------------|---|--|
| <code>__int_value:w</code> | ★ | <code>__int_value:w</code> $\langle integer \rangle$ |
| | | <code>__int_value:w</code> $\langle tokens \rangle$ $\langle optional\ space \rangle$ |

Expands $\langle tokens \rangle$ until an $\langle integer \rangle$ is formed. One space may be gobbled in the process.

TeXhackers note: This is the TeX primitive `\number`.

| | | |
|-------------------------------|---|--|
| <code>__int_eval:w</code> | ★ | <code>__int_eval:w</code> $\langle intexpr \rangle$ <code>__int_eval_end:</code> |
| <code>__int_eval_end:</code> | ★ | |

Evaluates $\langle integer\ expression \rangle$ as described for `\int_eval:n`. The evaluation stops when an unexpandable token which is not a valid part of an integer is read or when `__int_eval_end:` is reached. The latter is gobbled by the scanner mechanism: `__int_eval_end:` itself is unexpandable but used correctly the entire construct is expandable.

TeXhackers note: This is the ε -TeX primitive `\numexpr`.

| | |
|--------------------------------------|--|
| <code>__prg_compare_error:</code> | <code>__prg_compare_error:</code> |
| <code>__prg_compare_error:Nw</code> | <code>__prg_compare_error:Nw</code> $\langle token \rangle$ |

These are used within `\int_compare:nTF`, `\dim_compare:nTF` and so on to recover correctly if the n-type argument does not contain a properly-formed relation.

Part X

The l3flag package: expandable flags

Flags are the only data-type that can be modified in expansion-only contexts. This module is meant mostly for kernel use: in almost all cases, booleans or integers should be preferred to flags because they are very significantly faster.

A flag can hold any non-negative value, which we call its $\langle height \rangle$. In expansion-only contexts, a flag can only be “raised”: this increases the $\langle height \rangle$ by 1. The $\langle height \rangle$ can also be queried expandably. However, decreasing it, or setting it to zero requires non-expandable assignments.

Flag variables are always local. They are referenced by a $\langle flag name \rangle$ such as `str_missing`. The $\langle flag name \rangle$ is used as part of `\use:c` constructions hence is expanded at point of use. It must expand to character tokens only, with no spaces.

A typical use case of flags would be to keep track of whether an exceptional condition has occurred during expandable processing, and produce a meaningful (non-expandable) message after the end of the expandable processing. This is exemplified by `l3str-convert`, which for performance reasons performs conversions of individual characters expandably and for readability reasons produces a single error message describing incorrect inputs that were encountered.

Flags should not be used without carefully considering the fact that raising a flag takes a time and memory proportional to its height. Flags should not be used unless unavoidable.

1 Setting up flags

| | |
|--------------------------|---|
| <code>\flag_new:n</code> | <code>\flag_new:n {$\langle flag name \rangle$}</code> |
|--------------------------|---|

Creates a new flag with a name given by $\langle flag name \rangle$, or raises an error if the name is already taken. The $\langle flag name \rangle$ may not contain spaces. The declaration is global, but flags are always local variables. The $\langle flag \rangle$ will initially have zero height.

| | |
|----------------------------|---|
| <code>\flag_clear:n</code> | <code>\flag_clear:n {$\langle flag name \rangle$}</code> |
|----------------------------|---|

The $\langle flag \rangle$ ’s height is set to zero. The assignment is local.

| | |
|--------------------------------|---|
| <code>\flag_clear_new:n</code> | <code>\flag_clear_new:n {$\langle flag name \rangle$}</code> |
|--------------------------------|---|

Ensures that the $\langle flag \rangle$ exists globally by applying `\flag_new:n` if necessary, then applies `\flag_clear:n`, setting the height to zero locally.

| | |
|---------------------------|--|
| <code>\flag_show:n</code> | <code>\flag_show:n {$\langle flag name \rangle$}</code> |
|---------------------------|--|

Displays the $\langle flag \rangle$ ’s height in the terminal.

| | |
|--------------------------|---|
| <code>\flag_log:n</code> | <code>\flag_log:n {$\langle flag name \rangle$}</code> |
|--------------------------|---|

Writes the $\langle flag \rangle$ ’s height to the log file.

2 Expandable flag commands

| | |
|---|---|
| <hr/> <code>\flag_if_exist:n</code> ★ | <code>\flag_if_exist:n {⟨flag name⟩}</code> |
| <hr/> <code>\flag_if_exist:n</code> <u><code>TF</code></u> ★ | This function returns <code>true</code> if the <code>⟨flag name⟩</code> references a flag that has been defined previously, and <code>false</code> otherwise. |
| <hr/> <code>\flag_if_raised_p:n</code> ★ | <code>\flag_if_raised:n {⟨flag name⟩}</code> |
| <hr/> <code>\flag_if_raised:n</code> <u><code>TF</code></u> ★ | This function returns <code>true</code> if the <code>⟨flag⟩</code> has non-zero height, and <code>false</code> if the <code>⟨flag⟩</code> has zero height. |
| <hr/> <code>\flag_height:n</code> ★ | <code>\flag_height:n {⟨flag name⟩}</code> |
| | Expands to the height of the <code>⟨flag⟩</code> as an integer denotation. |
| <hr/> <code>\flag_raise:n</code> ★ | <code>\flag_raise:n {⟨flag name⟩}</code> |
| | The <code>⟨flag⟩</code> 's height is increased by 1 locally. |

Part XI

The l3quark package

Quarks

1 Introduction to quarks and scan marks

Two special types of constants in L^AT_EX3 are “quarks” and “scan marks”. By convention all constants of type quark start out with `\q_`, and scan marks start with `\s_`. Scan marks are for internal use by the kernel: they are not intended for more general use.

1.1 Quarks

Quarks are control sequences that expand to themselves and should therefore *never* be executed directly in the code. This would result in an endless loop!

They are meant to be used as delimiter in weird functions, with the most command use case as the ‘stop token’ (*i.e.* `\q_stop`). For example, when writing a macro to parse a user-defined date

```
\date_parse:n {19/June/1981}
```

one might write a command such as

```
\cs_new:Npn \date_parse:n #1 { \date_parse_aux:w #1 \q_stop }
\cs_new:Npn \date_parse_aux:w #1 / #2 / #3 \q_stop
{ <do something with the date> }
```

Quarks are sometimes also used as error return values for functions that receive erroneous input. For example, in the function `\prop_get:NnN` to retrieve a value stored in some key of a property list, if the key does not exist then the return value is the quark `\q_no_value`. As mentioned above, such quarks are extremely fragile and it is imperative when using such functions that code is carefully written to check for pathological cases to avoid leakage of a quark into an uncontrolled environment.

Quarks also permit the following ingenious trick when parsing tokens: when you pick up a token in a temporary variable and you want to know whether you have picked up a particular quark, all you have to do is compare the temporary variable to the quark using `\tl_if_eq:NNTF`. A set of special quark testing functions is set up below. All the quark testing functions are expandable although the ones testing only single tokens are much faster. An example of the quark testing functions and their use in recursion can be seen in the implementation of `\clist_map_function:NN`.

2 Defining quarks

| | |
|---------------------------|---|
| <code>\quark_new:N</code> | <code>\quark_new:N <quark></code> |
|---------------------------|---|

Creates a new `<quark>` which expands only to `<quark>`. The `<quark>` will be defined globally, and an error message will be raised if the name was already taken.

| | |
|---------------------------------|--|
| <u><code>\q_stop</code></u> | Used as a marker for delimited arguments, such as <code>\cs_set:Npn \tmp:w #1#2 \q_stop {#1}</code> |
| <u><code>\q_mark</code></u> | Used as a marker for delimited arguments when <code>\q_stop</code> is already in use. |
| <u><code>\q_nil</code></u> | Quark to mark a null value in structured variables or functions. Used as an end delimiter when this may itself may need to be tested (in contrast to <code>\q_stop</code> , which is only ever used as a delimiter). |
| <u><code>\q_no_value</code></u> | A canonical value for a missing value, when one is requested from a data structure. This is therefore used as a “return” value by functions such as <code>\prop_get:NnN</code> if there is no data to return. |

3 Quark tests

The method used to define quarks means that the single token (N) tests are faster than the multi-token (n) tests. The later should therefore only be used when the argument can definitely take more than a single token.

| | |
|--|---|
| <u><code>\quark_if_nil_p:N</code> ★</u> | <code>\quark_if_nil_p:N <token></code> |
| <u><code>\quark_if_nil:NTF</code> ★</u> | <code>\quark_if_nil:NTF <token> {\true code} {\false code}</code> |
| | Tests if the <i><token></i> is equal to <code>\q_nil</code> . |
| <u><code>\quark_if_nil_p:n</code> ★</u> | <code>\quark_if_nil_p:n {\token list}</code> |
| <u><code>\quark_if_nil_p:(o V)</code> ★</u> | <code>\quark_if_nil:nTF {\token list} {\true code} {\false code}</code> |
| <u><code>\quark_if_nil:nTF</code> ★</u> | Tests if the <i><token list></i> contains only <code>\q_nil</code> (distinct from <i><token list></i> being empty or containing <code>\q_nil</code> plus one or more other tokens). |
| <u><code>\quark_if_nil:(o V)TF</code> ★</u> | |
| <u><code>\quark_if_no_value_p:N</code> ★</u> | <code>\quark_if_no_value_p:N <token></code> |
| <u><code>\quark_if_no_value_p:c</code> ★</u> | <code>\quark_if_no_value:NTF <token> {\true code} {\false code}</code> |
| <u><code>\quark_if_no_value:NTF</code> ★</u> | Tests if the <i><token></i> is equal to <code>\q_no_value</code> . |
| <u><code>\quark_if_no_value:cTF</code> ★</u> | |
| <u><code>\quark_if_no_value_p:n</code> ★</u> | <code>\quark_if_no_value_p:n {\token list}</code> |
| <u><code>\quark_if_no_value:nTF</code> ★</u> | <code>\quark_if_no_value:nTF {\token list} {\true code} {\false code}</code> |
| | Tests if the <i><token list></i> contains only <code>\q_no_value</code> (distinct from <i><token list></i> being empty or containing <code>\q_no_value</code> plus one or more other tokens). |

4 Recursion

This module provides a uniform interface to intercepting and terminating loops as when one is doing tail recursion. The building blocks follow below and an example is shown in Section 5.

| | |
|--|---|
| <hr/> <hr/> <code>\q_recursion_tail</code> | This quark is appended to the data structure in question and appears as a real element there. This means it gets any list separators around it. |
| <hr/> <hr/> <code>\q_recursion_stop</code> | This quark is added <i>after</i> the data structure. Its purpose is to make it possible to terminate the recursion at any point easily. |
| <hr/> <hr/> <code>\quark_if_recursion_tail_stop:N</code> <code>\quark_if_recursion_tail_stop:N <token></code> | Tests if <i><token></i> contains only the marker <code>\q_recursion_tail</code> , and if so uses <code>\use_none_delimit_by_q_recursion_stop:w</code> to terminate the recursion that this belongs to. The recursion input must include the marker tokens <code>\q_recursion_tail</code> and <code>\q_recursion_stop</code> as the last two items. |
| <hr/> <hr/> <code>\quark_if_recursion_tail_stop:n</code> <code>\quark_if_recursion_tail_stop:n {<token list>}</code> <code>\quark_if_recursion_tail_stop:o</code> | Tests if the <i><token list></i> contains only <code>\q_recursion_tail</code> , and if so uses <code>\use_none_delimit_by_q_recursion_stop:w</code> to terminate the recursion that this belongs to. The recursion input must include the marker tokens <code>\q_recursion_tail</code> and <code>\q_recursion_stop</code> as the last two items. |
| <hr/> Updated: 2011-09-06 <hr/> | |
| <hr/> <hr/> <code>\quark_if_recursion_tail_stop_do:Nn</code> <code>\quark_if_recursion_tail_stop_do:Nn <token> {<insertion>}</code> | Tests if <i><token></i> contains only the marker <code>\q_recursion_tail</code> , and if so uses <code>\use_none_delimit_by_q_recursion_stop:w</code> to terminate the recursion that this belongs to. The recursion input must include the marker tokens <code>\q_recursion_tail</code> and <code>\q_recursion_stop</code> as the last two items. The <i><insertion></i> code is then added to the input stream after the recursion has ended. |
| <hr/> <hr/> <code>\quark_if_recursion_tail_stop_do:nn</code> <code>\quark_if_recursion_tail_stop_do:nn {<token list>} {<insertion>}</code> <code>\quark_if_recursion_tail_stop_do:on</code> | Tests if the <i><token list></i> contains only <code>\q_recursion_tail</code> , and if so uses <code>\use_none_delimit_by_q_recursion_stop:w</code> to terminate the recursion that this belongs to. The recursion input must include the marker tokens <code>\q_recursion_tail</code> and <code>\q_recursion_stop</code> as the last two items. The <i><insertion></i> code is then added to the input stream after the recursion has ended. |
| <hr/> Updated: 2011-09-06 <hr/> | |

5 An example of recursion with quarks

Quarks are mainly used internally in the `expl3` code to define recursion functions such as `\tl_map_inline:nn` and so on. Here is a small example to demonstrate how to use quarks in this fashion. We shall define a command called `\my_map_dbl:nn` which takes a token list and applies an operation to every *pair* of tokens. For example, `\my_map_dbl:nn {abcd} {[--#1--#2--]~}` would produce “`[-a-b-] [-c-d-]` ”. Using quarks to define such functions simplifies their logic and ensures robustness in many cases.

Here's the definition of `\my_map_dbl:nn`. First of all, define the function that will do the processing based on the inline function argument `#2`. Then initiate the recursion using an internal function. The token list `#1` is terminated using `\q_recursion_tail`, with delimiters according to the type of recursion (here a pair of `\q_recursion_tail`), concluding with `\q_recursion_stop`. These quarks are used to mark the end of the token list being operated upon.

```
\cs_new:Npn \my_map_dbl:nn #1#2
{
  \cs_set:Npn \__my_map_dbl_fn:nn ##1 ##2 {#2}
  \__my_map_dbl:nn #1 \q_recursion_tail \q_recursion_tail
  \q_recursion_stop
}
```

The definition of the internal recursion function follows. First check if either of the input tokens are the termination quarks. Then, if not, apply the inline function to the two arguments.

```
\cs_new:Nn \__my_map_dbl:nn
{
  \quark_if_recursion_tail_stop:n {#1}
  \quark_if_recursion_tail_stop:n {#2}
  \__my_map_dbl_fn:nn {#1} {#2}
}
```

Finally, recurse:

```
\__my_map_dbl:nn
}
```

Note that contrarily to L^AT_EX3 built-in mapping functions, this mapping function cannot be nested, since the second map will overwrite the definition of `__my_map_dbl_fn:nn`.

6 Internal quark functions

```
\__quark_if_recursion_tail_break:NN \__quark_if_recursion_tail_break:nN {<token list>}
\__quark_if_recursion_tail_break:nN \<type>_map_break:
```

Tests if `<token list>` contains only `\q_recursion_tail`, and if so terminates the recursion using `\<type>_map_break:.` The recursion end should be marked by `\prg_break_point:Nn \<type>_map_break:.`

7 Scan marks

Scan marks are control sequences set equal to `\scan_stop:`, hence will never expand in an expansion context and will be (largely) invisible if they are encountered in a typesetting context.

Like quarks, they can be used as delimiters in weird functions and are often safer to use for this purpose. Since they are harmless when executed by T_EX in non-expandable contexts, they can be used to mark the end of a set of instructions. This allows to skip to that point if the end of the instructions should not be performed (see l3regex).

The scan marks system is only for internal use by the kernel team in a small number of very specific places. These functions should not be used more generally.

| | |
|----------------------------|---|
| <code>_scan_new:N</code> | <code>_scan_new:N</code> $\langle scan\ mark \rangle$ |
|----------------------------|---|

Creates a new $\langle scan\ mark \rangle$ which is set equal to `\scan_stop:`. The $\langle scan\ mark \rangle$ will be defined globally, and an error message will be raised if the name was already taken by another scan mark.

| | |
|-----------------------|--|
| <code>\s_stop</code> | Used at the end of a set of instructions, as a marker that can be jumped to using <code>_use_none_delimit_by_s_stop:w</code> . |
|-----------------------|--|

| | |
|--|---|
| <code>_use_none_delimit_by_s_stop:w</code> | <code>_use_none_delimit_by_s_stop:w</code> $\langle tokens \rangle$ <code>\s_stop</code> |
|--|---|

Removes the $\langle tokens \rangle$ and `\s_stop` from the input stream. This leads to a low-level TeX error if `\s_stop` is absent.

Part XII

The l3prg package

Control structures

Conditional processing in L^AT_EX3 is defined as something that performs a series of tests, possibly involving assignments and calling other functions that do not read further ahead in the input stream. After processing the input, a *state* is returned. The states returned are *⟨true⟩* and *⟨false⟩*.

L^AT_EX3 has two forms of conditional flow processing based on these states. The first form is predicate functions that turn the returned state into a boolean *⟨true⟩* or *⟨false⟩*. For example, the function `\cs_if_free_p:N` checks whether the control sequence given as its argument is free and then returns the boolean *⟨true⟩* or *⟨false⟩* values to be used in testing with `\if_predicate:w` or in functions to be described below. The second form is the kind of functions choosing a particular argument from the input stream based on the result of the testing as in `\cs_if_free:NTF` which also takes one argument (the *N*) and then executes either `true` or `false` depending on the result.

T_EXhackers note: The arguments are executed after exiting the underlying `\if... \fi` structure.

1 Defining a set of conditional functions

```
\prg_new_conditional:Npnn
\prg_set_conditional:Npnn
\prg_new_conditional:Nnn
\prg_set_conditional:Nnn
```

Updated: 2012-02-06

```
\prg_new_conditional:Npnn \<name>:<arg spec> <parameters> {\<conditions>} {\<code>}
\prg_new_conditional:Nnn \<name>:<arg spec> {\<conditions>} {\<code>}
```

These functions create a family of conditionals using the same *{⟨code⟩}* to perform the test created. Those conditionals are expandable if *⟨code⟩* is. The **new** versions will check for existing definitions and perform assignments globally (*cf.* `\cs_new:Npn`) whereas the **set** versions do no check and perform assignments locally (*cf.* `\cs_set:Npn`). The conditionals created are dependent on the comma-separated list of *⟨conditions⟩*, which should be one or more of *p*, *T*, *F* and *TF*.

```
\prg_new_protected_conditional:Npnn \prg_new_protected_conditional:Npnn \<name>:<arg spec> <parameters>
\prg_set_protected_conditional:Npnn {\<conditions>} {\<code>}
\prg_new_protected_conditional:Nnn \prg_new_protected_conditional:Nnn \<name>:<arg spec>
\prg_set_protected_conditional:Nnn {\<conditions>} {\<code>}
```

Updated: 2012-02-06

These functions create a family of protected conditionals using the same *{⟨code⟩}* to perform the test created. The *⟨code⟩* does not need to be expandable. The **new** version will check for existing definitions and perform assignments globally (*cf.* `\cs_new:Npn`) whereas the **set** version will not (*cf.* `\cs_set:Npn`). The conditionals created are depended on the comma-separated list of *⟨conditions⟩*, which should be one or more of *T*, *F* and *TF* (not *p*).

The conditionals are defined by `\prg_new_conditional:Npnn` and friends as:

- `\<name>_p:<arg spec>` — a predicate function which will supply either a logical `true` or logical `false`. This function is intended for use in cases where one or more logical tests are combined to lead to a final outcome. This function cannot be defined for `protected` conditionals.
- `\<name>:<arg spec>T` — a function with one more argument than the original `<arg spec>` demands. The `<true branch>` code in this additional argument will be left on the input stream only if the test is `true`.
- `\<name>:<arg spec>F` — a function with one more argument than the original `<arg spec>` demands. The `<false branch>` code in this additional argument will be left on the input stream only if the test is `false`.
- `\<name>:<arg spec>TF` — a function with two more argument than the original `<arg spec>` demands. The `<true branch>` code in the first additional argument will be left on the input stream if the test is `true`, while the `<false branch>` code in the second argument will be left on the input stream if the test is `false`.

The `<code>` of the test may use `<parameters>` as specified by the second argument to `\prg_set_conditional:Npnn`: this should match the `<argument specification>` but this is not enforced. The `Nnn` versions infer the number of arguments from the argument specification given (*cf.* `\cs_new:Nn`, *etc.*). Within the `<code>`, the functions `\prg_return_true:` and `\prg_return_false:` are used to indicate the logical outcomes of the test.

An example can easily clarify matters here:

```
\prg_set_conditional:Npnn \foo_if_bar:NN #1#2 { p , T , TF }
{
  \if_meaning:w \l_tmpa_tl #1
  \prg_return_true:
\else:
  \if_meaning:w \l_tmpa_tl #2
  \prg_return_true:
\else:
  \prg_return_false:
\fi:
\fi:
}
```

This defines the function `\foo_if_bar_p:NN`, `\foo_if_bar:NNTF` and `\foo_if_bar:NNT` but not `\foo_if_bar:NNF` (because `F` is missing from the `<conditions>` list). The return statements take care of resolving the remaining `\else:` and `\fi:` before returning the state. There must be a return statement for each branch; failing to do so will result in erroneous output if that branch is executed.

| | |
|--|--|
| <code>\prg_new_eq_conditional:Nnn</code> | <code>\prg_new_eq_conditional:Nnn \<name1>:<arg spec1> \<name2>:<arg spec2></code> |
| <code>\prg_set_eq_conditional:Nnn</code> | <code>{<conditions>}</code> |

These functions copy a family of conditionals. The `new` version will check for existing definitions (*cf.* `\cs_new:Npn`) whereas the `set` version will not (*cf.* `\cs_set:Npn`). The conditionals copied are depended on the comma-separated list of `<conditions>`, which should be one or more of `p`, `T`, `F` and `TF`.

| | | |
|---------------------------------|---|---------------------------------|
| <code>\prg_return_true:</code> | ★ | <code>\prg_return_true:</code> |
| <code>\prg_return_false:</code> | ★ | <code>\prg_return_false:</code> |

These ‘return’ functions define the logical state of a conditional statement. They appear within the code for a conditional function generated by `\prg_set_conditional:Npnn`, *etc.*, to indicate when a true or false branch should be taken. While they may appear multiple times each within the code of such conditionals, the execution of the conditional must result in the expansion of one of these two functions *exactly once*.

The return functions trigger what is internally an f-expansion process to complete the evaluation of the conditional. Therefore, after `\prg_return_true:` or `\prg_return_false:` there must be no non-expandable material in the input stream for the remainder of the expansion of the conditional code. This includes other instances of either of these functions.

2 The boolean data type

This section describes a boolean data type which is closely connected to conditional processing as sometimes you want to execute some code depending on the value of a switch (*e.g.*, draft/final) and other times you perhaps want to use it as a predicate function in an `\if_predicate:w` test. The problem of the primitive `\if_false:` and `\if_true:` tokens is that it is not always safe to pass them around as they may interfere with scanning for termination of primitive conditional processing. Therefore, we employ two canonical booleans: `\c_true_bool` or `\c_false_bool`. Besides preventing problems as described above, it also allows us to implement a simple boolean parser supporting the logical operations And, Or, Not, *etc.* which can then be used on both the boolean type and predicate functions.

All conditional `\bool_` functions except assignments are expandable and expect the input to also be fully expandable (which will generally mean being constructed from predicate functions, possibly nested).

T_EXhackers note: The `bool` data type is not implemented using the `\iffalse/\iftrue` primitives, in contrast to `\newif`, *etc.*, in plain T_EX, L^AT_EX 2_ε and so on. Programmers should not base use of `bool` switches on any particular expectation of the implementation.

| | |
|--------------------------|--|
| <code>\bool_new:N</code> | <code>\bool_new:N <boolean></code> |
| <code>\bool_new:c</code> | |

Creates a new `<boolean>` or raises an error if the name is already taken. The declaration is global. The `<boolean>` will initially be `false`.

| | |
|---------------------------------|--|
| <code>\bool_set_false:N</code> | <code>\bool_set_false:N <boolean></code> |
| <code>\bool_set_false:c</code> | |
| <code>\bool_gset_false:N</code> | Sets <code><boolean></code> logically <code>false</code> . |
| <code>\bool_gset_false:c</code> | |

| | |
|--------------------------------|---|
| <code>\bool_set_true:N</code> | <code>\bool_set_true:N <boolean></code> |
| <code>\bool_set_true:c</code> | |
| <code>\bool_gset_true:N</code> | Sets <code><boolean></code> logically <code>true</code> . |
| <code>\bool_gset_true:c</code> | |

| | |
|---------------------------------------|--|
| <hr/> | |
| <code>\bool_set_eq:NN</code> | <code>\bool_set_eq:NN <boolean₁> <boolean₂></code> |
| <code>\bool_set_eq:(cN Nc cc)</code> | Sets the content of $\langle boolean_1 \rangle$ equal to that of $\langle boolean_2 \rangle$. |
| <code>\bool_gset_eq:NN</code> | |
| <code>\bool_gset_eq:(cN Nc cc)</code> | |
| <hr/> | |
| <code>\bool_set:Nn</code> | <code>\bool_set:Nn <boolean> {\<boolexpr>}</code> |
| <code>\bool_set:cn</code> | Evaluates the $\langle boolean \text{ expression} \rangle$ as described for <code>\bool_if:nTF</code> , and sets the $\langle boolean \rangle$ |
| <code>\bool_gset:Nn</code> | variable to the logical truth of this evaluation. |
| <code>\bool_gset:cn</code> | |
| <hr/> | |
| Updated: 2012-07-08 | |
| <hr/> | |
| <code>\bool_if_p:N</code> ★ | <code>\bool_if_p:N <boolean></code> |
| <code>\bool_if_p:c</code> ★ | <code>\bool_if:NTF <boolean> {\<true code>} {\<false code>}</code> |
| <code>\bool_if:NTF</code> ★ | Tests the current truth of $\langle boolean \rangle$, and continues expansion based on this result. |
| <code>\bool_if:cTF</code> ★ | |
| <hr/> | |
| <code>\bool_show:N</code> | <code>\bool_show:N <boolean></code> |
| <code>\bool_show:c</code> | Displays the logical truth of the $\langle boolean \rangle$ on the terminal. |
| New: 2012-02-09 | |
| Updated: 2015-08-01 | |
| <hr/> | |
| <code>\bool_show:n</code> | <code>\bool_show:n {\<boolean expression>}</code> |
| New: 2012-02-09 | Displays the logical truth of the $\langle boolean \text{ expression} \rangle$ on the terminal. |
| Updated: 2015-08-07 | |
| <hr/> | |
| <code>\bool_log:N</code> | <code>\bool_log:N <boolean></code> |
| <code>\bool_log:c</code> | Writes the logical truth of the $\langle boolean \rangle$ in the log file. |
| New: 2014-08-22 | |
| Updated: 2015-08-03 | |
| <hr/> | |
| <code>\bool_log:n</code> | <code>\bool_log:n {\<boolean expression>}</code> |
| New: 2014-08-22 | Writes the logical truth of the $\langle boolean \text{ expression} \rangle$ in the log file. |
| Updated: 2015-08-07 | |
| <hr/> | |
| <code>\bool_if_exist_p:N</code> ★ | <code>\bool_if_exist_p:N <boolean></code> |
| <code>\bool_if_exist_p:c</code> ★ | <code>\bool_if_exist:NTF <boolean> {\<true code>} {\<false code>}</code> |
| <code>\bool_if_exist:NTF</code> ★ | Tests whether the $\langle boolean \rangle$ is currently defined. This does not check that the $\langle boolean \rangle$ |
| <code>\bool_if_exist:cTF</code> ★ | really is a boolean variable. |
| New: 2012-03-03 | |
| <hr/> | |
| <code>\l_tmpa_bool</code> | A scratch boolean for local assignment. It is never used by the kernel code, and so is |
| <code>\l_tmpb_bool</code> | safe for use with any L ^A T _E X3-defined function. However, it may be overwritten by other |
| | non-kernel code and so should only be used for short-term storage. |
| <hr/> | |
| <code>\g_tmpa_bool</code> | A scratch boolean for global assignment. It is never used by the kernel code, and so is |
| <code>\g_tmpb_bool</code> | safe for use with any L ^A T _E X3-defined function. However, it may be overwritten by other |
| | non-kernel code and so should only be used for short-term storage. |

3 Boolean expressions

As we have a boolean datatype and predicate functions returning boolean $\langle true \rangle$ or $\langle false \rangle$ values, it seems only fitting that we also provide a parser for $\langle boolean\ expressions \rangle$.

A boolean expression is an expression which given input in the form of predicate functions and boolean variables, return boolean $\langle true \rangle$ or $\langle false \rangle$. It supports the logical operations And, Or and Not as the well-known infix operators $\&\&$ and $||$ and prefix $!$ with their usual precedences (namely, $\&\&$ binds more tightly than $||$). In addition to this, parentheses can be used to isolate sub-expressions. For example,

```
\int_compare_p:n { 1 = 1 } &&
(
  \int_compare_p:n { 2 = 3 } ||
  \int_compare_p:n { 4 <= 4 } ||
  \str_if_eq_p:nn { abc } { def }
) &&
! \int_compare_p:n { 2 = 4 }
```

is a valid boolean expression.

At present, the infix operators $\&\&$ and $||$ perform lazy evaluation as well, but this will change in a future release.

| | |
|--|---|
| \backslash bool_if_p:n ☆ \backslash bool_if:nTF ☆ | \backslash bool_if_p:n { $\langle boolean\ expression \rangle$ } \backslash bool_if:nTF { $\langle boolean\ expression \rangle$ } { $\langle true\ code \rangle$ } { $\langle false\ code \rangle$ } |
|--|---|

Updated: 2012-07-08

Tests the current truth of $\langle boolean\ expression \rangle$, and continues expansion based on this result. The $\langle boolean\ expression \rangle$ should consist of a series of predicates or boolean variables with the logical relationship between these defined using $\&\&$ (“And”), $||$ (“Or”), $!$ (“Not”) and parentheses. The logical Not applies to the next predicate or group.

| | |
|-----------------------------|---|
| \backslash bool_not_p:n ☆ | \backslash bool_not_p:n { $\langle boolean\ expression \rangle$ } |
|-----------------------------|---|

Updated: 2012-07-08

Function version of $!(\langle boolean\ expression \rangle)$ within a boolean expression.

| | |
|------------------------------|--|
| \backslash bool_xor_p:nn ☆ | \backslash bool_xor_p:nn { $\langle boolexpri_1 \rangle$ } { $\langle boolexpri_2 \rangle$ } |
|------------------------------|--|

Updated: 2012-07-08

Implements an “exclusive or” operation between two boolean expressions. There is no infix operation for this logical operator.

4 Logical loops

Loops using either boolean expressions or stored boolean values.

| | |
|--|--|
| \backslash bool_do_until:Nn ☆ \backslash bool_do_until:cn ☆ | \backslash bool_do_until:Nn $\langle boolean \rangle$ { $\langle code \rangle$ } \backslash bool_do_until:cn { $\langle boolean \rangle$ } { $\langle code \rangle$ } |
|--|--|

Places the $\langle code \rangle$ in the input stream for \TeX to process, and then checks the logical value of the $\langle boolean \rangle$. If it is **false** then the $\langle code \rangle$ will be inserted into the input stream again and the process will loop until the $\langle boolean \rangle$ is **true**.

| | |
|--|--|
| \backslash bool_do_while:Nn ☆ \backslash bool_do_while:cn ☆ | \backslash bool_do_while:Nn $\langle boolean \rangle$ { $\langle code \rangle$ } \backslash bool_do_while:cn { $\langle boolean \rangle$ } { $\langle code \rangle$ } |
|--|--|

Places the $\langle code \rangle$ in the input stream for \TeX to process, and then checks the logical value of the $\langle boolean \rangle$. If it is **true** then the $\langle code \rangle$ will be inserted into the input stream again and the process will loop until the $\langle boolean \rangle$ is **false**.

| | |
|--|---|
| <hr/> <code>\bool_until_do:Nn</code> ☆ <code>\bool_until_do:cn</code> ☆ <hr/> | <code>\bool_until_do:Nn <boolean> {<code>}</code> This function firsts checks the logical value of the <i><boolean></i> . If it is false the <i><code></i> is placed in the input stream and expanded. After the completion of the <i><code></i> the truth of the <i><boolean></i> is re-evaluated. The process will then loop until the <i><boolean></i> is true . |
| <hr/> <code>\bool_while_do:Nn</code> ☆ <code>\bool_while_do:cn</code> ☆ <hr/> | <code>\bool_while_do:Nn <boolean> {<code>}</code> This function firsts checks the logical value of the <i><boolean></i> . If it is true the <i><code></i> is placed in the input stream and expanded. After the completion of the <i><code></i> the truth of the <i><boolean></i> is re-evaluated. The process will then loop until the <i><boolean></i> is false . |
| <hr/> <code>\bool_do_until:nn</code> ☆ <div>Updated: 2012-07-08</div> <hr/> | <code>\bool_do_until:nn {<boolean expression>} {<code>}</code> Places the <i><code></i> in the input stream for T _E X to process, and then checks the logical value of the <i><boolean expression></i> as described for <code>\bool_if:nTF</code> . If it is false then the <i><code></i> will be inserted into the input stream again and the process will loop until the <i><boolean expression></i> evaluates to true . |
| <hr/> <code>\bool_do_while:nn</code> ☆ <div>Updated: 2012-07-08</div> <hr/> | <code>\bool_do_while:nn {<boolean expression>} {<code>}</code> Places the <i><code></i> in the input stream for T _E X to process, and then checks the logical value of the <i><boolean expression></i> as described for <code>\bool_if:nTF</code> . If it is true then the <i><code></i> will be inserted into the input stream again and the process will loop until the <i><boolean expression></i> evaluates to false . |
| <hr/> <code>\bool_until_do:nn</code> ☆ <div>Updated: 2012-07-08</div> <hr/> | <code>\bool_until_do:nn {<boolean expression>} {<code>}</code> This function firsts checks the logical value of the <i><boolean expression></i> (as described for <code>\bool_if:nTF</code>). If it is false the <i><code></i> is placed in the input stream and expanded. After the completion of the <i><code></i> the truth of the <i><boolean expression></i> is re-evaluated. The process will then loop until the <i><boolean expression></i> is true . |
| <hr/> <code>\bool_while_do:nn</code> ☆ <div>Updated: 2012-07-08</div> <hr/> | <code>\bool_while_do:nn {<boolean expression>} {<code>}</code> This function firsts checks the logical value of the <i><boolean expression></i> (as described for <code>\bool_if:nTF</code>). If it is true the <i><code></i> is placed in the input stream and expanded. After the completion of the <i><code></i> the truth of the <i><boolean expression></i> is re-evaluated. The process will then loop until the <i><boolean expression></i> is false . |

5 Producing multiple copies

| | |
|--|--|
| <hr/> <code>\prg_replicate:nn</code> ★ <div>Updated: 2011-07-04</div> <hr/> | <code>\prg_replicate:nn {<integer expression>} {<tokens>}</code> Evaluates the <i><integer expression></i> (which should be zero or positive) and creates the resulting number of copies of the <i><tokens></i> . The function is both expandable and safe for nesting. It yields its result after two expansion steps. |
|--|--|

6 Detecting T_EX's mode

| | | |
|-------------------------------------|-------------|--|
| <code>\mode_if_horizontal_p:</code> | ★ | <code>\mode_if_horizontal_p:</code> |
| <code>\mode_if_horizontal:</code> | <u>TF</u> ★ | <code>\mode_if_horizontal:TF</code> <code>{\true code}</code> <code>{\false code}</code> |

Detects if T_EX is currently in horizontal mode.

| | | |
|--------------------------------|-------------|---|
| <code>\mode_if_inner_p:</code> | ★ | <code>\mode_if_inner_p:</code> |
| <code>\mode_if_inner:</code> | <u>TF</u> ★ | <code>\mode_if_inner:TF</code> <code>{\true code}</code> <code>{\false code}</code> |

Detects if T_EX is currently in inner mode.

| | | |
|-------------------------------|-------------|--|
| <code>\mode_if_math_p:</code> | ★ | <code>\mode_if_math:TF</code> <code>{\true code}</code> <code>{\false code}</code> |
| <code>\mode_if_math:</code> | <u>TF</u> ★ | |

Detects if T_EX is currently in maths mode.

Updated: 2011-09-05

| | | |
|-----------------------------------|-------------|--|
| <code>\mode_if_vertical_p:</code> | ★ | <code>\mode_if_vertical_p:</code> |
| <code>\mode_if_vertical:</code> | <u>TF</u> ★ | <code>\mode_if_vertical:TF</code> <code>{\true code}</code> <code>{\false code}</code> |

Detects if T_EX is currently in vertical mode.

7 Primitive conditionals

| | | |
|------------------------------|---|--|
| <code>\if_predicate:w</code> | ★ | <code>\if_predicate:w</code> <code><predicate></code> <code><true code></code> <code>\else:</code> <code><false code></code> <code>\fi:</code> |
|------------------------------|---|--|

This function takes a predicate function and branches according to the result. (In practice this function would also accept a single boolean variable in place of the `<predicate>` but to make the coding clearer this should be done through `\if_bool:N`.)

| | | |
|-------------------------|---|---|
| <code>\if_bool:N</code> | ★ | <code>\if_bool:N</code> <code><boolean></code> <code><true code></code> <code>\else:</code> <code><false code></code> <code>\fi:</code> |
|-------------------------|---|---|

This function takes a boolean variable and branches according to the result.

8 Internal programming functions

| | | |
|---------------------------------------|---|---------------------------------------|
| <code>\group_align_safe_begin:</code> | ★ | <code>\group_align_safe_begin:</code> |
| <code>\group_align_safe_end:</code> | ★ | <code>...</code> |

Updated: 2011-08-11

`\group_align_safe_end:`

These functions are used to enclose material in a T_EX alignment environment within a specially-constructed group. This group is designed in such a way that it does not add brace groups to the output but does act as a group for the `&` token inside `\halign`. This is necessary to allow grabbing of tokens for testing purposes, as T_EX uses group level to determine the effect of alignment tokens. Without the special grouping, the use of a function such as `\peek_after:Nw` will result in a forbidden comparison of the internal `\endtemplate` token, yielding a fatal error. Each `\group_align_safe_begin:` must be matched by a `\group_align_safe_end:`, although this does not have to occur within the same function.

| | |
|---|--|
| <u>_prg_break_point:Nn</u> ★ | <p>_prg_break_point:Nn \<type>_map_break: {tokens}</p> <p>Used to mark the end of a recursion or mapping: the functions \<type>_map_break: and \<type>_map_break:n use this to break out of the loop. After the loop ends, the <tokens> are inserted into the input stream. This occurs even if the break functions are <i>not</i> applied: _prg_break_point:Nn is functionally-equivalent in these cases to \use_ii:nn.</p> |
| <u>_prg_map_break:Nn</u> ★ | <p>_prg_map_break:Nn \<type>_map_break: {<user code>}</p> <p>...</p> <p>_prg_break_point:Nn \<type>_map_break: {<ending code>}</p> <p>Breaks a recursion in mapping contexts, inserting in the input stream the <user code> after the <ending code> for the loop. The function breaks loops, inserting their <ending code>, until reaching a loop with the same <type> as its first argument. This \<type>_map_break: argument is simply used as a recognizable marker for the <type>.</p> |
| <u>\g__prg_map_int</u> | <p>This integer is used by non-expandable mapping functions to track the level of nesting in force. The functions _prg_map_1:w, _prg_map_2:w, <i>etc.</i>, labelled by \g__prg_map_int hold functions to be mapped over various list datatypes in inline and variable mappings.</p> |
| <u>_prg_break_point:</u> ★ | <p>This copy of \prg_do_nothing: is used to mark the end of a fast short-term recursions: the function _prg_break:n uses this to break out of the loop.</p> |
| <u>_prg_break:</u> ★ <u>_prg_break:n</u> ★ | <p>_prg_break:n {<tokens>} ... _prg_break_point:</p> <p>Breaks a recursion which has no <ending code> and which is not a user-breakable mapping (see for instance \prop_get:Nn), and inserts <tokens> in the input stream.</p> |

Part XIII

The l3clist package

Comma separated lists

Comma lists contain ordered data where items can be added to the left or right end of the list. The resulting ordered list can then be mapped over using `\clist_map_function:NN`. Several items can be added at once, and spaces are removed from both sides of each item on input. Hence,

```
\clist_new:N \l_my_clist
\clist_put_left:Nn \l_my_clist { ~ a ~ , ~ {b} ~ }
\clist_put_right:Nn \l_my_clist { ~ { c ~ } , d }
```

results in `\l_my_clist` containing `a,{b},{c~},d`. Comma lists cannot contain empty items, thus

```
\clist_clear_new:N \l_my_clist
\clist_put_right:Nn \l_my_clist { , ~ , , }
\clist_if_empty:NTF \l_my_clist { true } { false }
```

will leave `true` in the input stream. To include an item which contains a comma, or starts or ends with a space, surround it with braces. The sequence data type should be preferred to comma lists if items are to contain `{`, `}`, or `#` (assuming the usual \TeX category codes apply).

1 Creating and initialising comma lists

```
\clist_new:N
\clist_new:c
```

```
\clist_new:N <comma list>
```

Creates a new *<comma list>* or raises an error if the name is already taken. The declaration is global. The *<comma list>* will initially contain no items.

```
\clist_const:Nn
\clist_const:(Nx|cn|cx)
```

```
\clist_const:Nn <clist var> {<comma list>}
```

Creates a new constant *<clist var>* or raises an error if the name is already taken. The value of the *<clist var>* will be set globally to the *<comma list>*.

New: 2014-07-05

```
\clist_clear:N
\clist_clear:c
\clist_gclear:N
\clist_gclear:c
```

```
\clist_clear:N <comma list>
```

Clears all items from the *<comma list>*.

```
\clist_clear_new:N
\clist_clear_new:c
\clist_gclear_new:N
\clist_gclear_new:c
```

```
\clist_clear_new:N <comma list>
```

Ensures that the *<comma list>* exists globally by applying `\clist_new:N` if necessary, then applies `\clist_(g)clear:N` to leave the list empty.

| | |
|--|--|
| <code>\clist_set_eq:NN</code> | <code>\clist_set_eq:NN <comma list₁> <comma list₂></code> |
| <code>\clist_set_eq:(cN Nc cc)</code> | Sets the content of <code><comma list₁></code> equal to that of <code><comma list₂></code> . |
| <code>\clist_gset_eq:NN</code> | |
| <code>\clist_gset_eq:(cN Nc cc)</code> | |

| | |
|--|---|
| <code>\clist_set_from_seq:NN</code> | <code>\clist_set_from_seq:NN <comma list> <sequence></code> |
| <code>\clist_set_from_seq:(cN Nc cc)</code> | |
| <code>\clist_gset_from_seq:NN</code> | |
| <code>\clist_gset_from_seq:(cN Nc cc)</code> | |

New: 2014-07-17

Converts the data in the `<sequence>` into a `<comma list>`: the original `<sequence>` is unchanged. Items which contain either spaces or commas are surrounded by braces.

| | |
|---------------------------------|--|
| <code>\clist_concat:NNN</code> | <code>\clist_concat:NNN <comma list₁> <comma list₂> <comma list₃></code> |
| <code>\clist_concat:ccc</code> | Concatenates the content of <code><comma list₂></code> and <code><comma list₃></code> together and saves the result in <code><comma list₁></code> . The items in <code><comma list₂></code> will be placed at the left side of the new comma list. |
| <code>\clist_gconcat:NNN</code> | |
| <code>\clist_gconcat:ccc</code> | |

| | |
|------------------------------------|--|
| <code>\clist_if_exist_p:N *</code> | <code>\clist_if_exist_p:N <comma list></code> |
| <code>\clist_if_exist_p:c *</code> | <code>\clist_if_exist:NTF <comma list> {\true code} {\false code}</code> |
| <code>\clist_if_exist:NTF *</code> | Tests whether the <code><comma list></code> is currently defined. This does not check that the <code><comma list></code> really is a comma list. |
| <code>\clist_if_exist:cTF *</code> | |

New: 2012-03-03

2 Adding data to comma lists

| | |
|---|--|
| <code>\clist_set:Nn</code> | <code>\clist_set:Nn <comma list> {\<item₁>, ..., <item_n>}</code> |
| <code>\clist_set:(NV No Nx cn cV co cx)</code> | |
| <code>\clist_gset:Nn</code> | |
| <code>\clist_gset:(NV No Nx cn cV co cx)</code> | |

New: 2011-09-06

Sets `<comma list>` to contain the `<items>`, removing any previous content from the variable. Spaces are removed from both sides of each item.

| | |
|--|---|
| <code>\clist_put_left:Nn</code> | <code>\clist_put_left:Nn <comma list> {\<item₁>, ..., <item_n>}</code> |
| <code>\clist_put_left:(NV No Nx cn cV co cx)</code> | |
| <code>\clist_gput_left:Nn</code> | |
| <code>\clist_gput_left:(NV No Nx cn cV co cx)</code> | |

Updated: 2011-09-05

Appends the `<items>` to the left of the `<comma list>`. Spaces are removed from both sides of each item.

| | |
|---|---|
| <code>\clist_put_right:Nn</code> | <code>\clist_put_right:Nn <comma list> {\<item_1>, ..., \<item_n>}</code> |
| <code>\clist_put_right:(NV No Nx cn cV co cx)</code> | |
| <code>\clist_gput_right:Nn</code> | |
| <code>\clist_gput_right:(NV No Nx cn cV co cx)</code> | |

Updated: 2011-09-05

Appends the $\langle items \rangle$ to the right of the $\langle comma list \rangle$. Spaces are removed from both sides of each item.

3 Modifying comma lists

While comma lists are normally used as ordered lists, it may be necessary to modify the content. The functions here may be used to update comma lists, while retaining the order of the unaffected entries.

| | |
|--|--|
| <code>\clist_remove_duplicates:N</code> | <code>\clist_remove_duplicates:N <comma list></code> |
| <code>\clist_remove_duplicates:c</code> | |
| <code>\clist_gremove_duplicates:N</code> | |
| <code>\clist_gremove_duplicates:c</code> | |

Removes duplicate items from the $\langle comma list \rangle$, leaving the left most copy of each item in the $\langle comma list \rangle$. The $\langle item \rangle$ comparison takes place on a token basis, as for `\tl_if_eq:nn(TF)`.

TeXhackers note: This function iterates through every item in the $\langle comma list \rangle$ and does a comparison with the $\langle items \rangle$ already checked. It is therefore relatively slow with large comma lists. Furthermore, it will not work if any of the items in the $\langle comma list \rangle$ contains `{`, `}`, or `#` (assuming the usual TeX category codes apply).

| | |
|------------------------------------|--|
| <code>\clist_remove_all:Nn</code> | <code>\clist_remove_all:Nn <comma list> {\<item>}</code> |
| <code>\clist_remove_all:cn</code> | |
| <code>\clist_gremove_all:Nn</code> | |
| <code>\clist_gremove_all:cn</code> | |

Updated: 2011-09-06

Removes every occurrence of $\langle item \rangle$ from the $\langle comma list \rangle$. The $\langle item \rangle$ comparison takes place on a token basis, as for `\tl_if_eq:nn(TF)`.

TeXhackers note: The $\langle item \rangle$ may not contain `{`, `}`, or `#` (assuming the usual TeX category codes apply).

| | |
|--------------------------------|--|
| <code>\clist_reverse:N</code> | <code>\clist_reverse:N <comma list></code> |
| <code>\clist_reverse:c</code> | |
| <code>\clist_greverse:N</code> | |
| <code>\clist_greverse:c</code> | |

New: 2014-07-18

Reverses the order of items stored in the $\langle comma list \rangle$.

| | |
|-------------------------------|---|
| <code>\clist_reverse:n</code> | <code>\clist_reverse:n {\<comma list>}</code> |
|-------------------------------|---|

New: 2014-07-18

Leaves the items in the $\langle comma list \rangle$ in the input stream in reverse order. Braces and spaces are preserved by this process.

TeXhackers note: The result is returned within `\unexpanded`, which means that the comma list will not expand further when appearing in an x-type argument expansion.

| | |
|------------------------------|--|
| <code>\clist_sort:Nn</code> | <code>\clist_sort:Nn <clist var> {<comparison code>}</code> |
| <code>\clist_sort:cn</code> | |
| <code>\clist_gsort:Nn</code> | Sorts the items in the <i><clist var></i> according to the <i><comparison code></i> , and assigns the result to <i><clist var></i> . The details of sorting comparison are described in Section 1. |
| <code>\clist_gsort:cn</code> | |
| New: 2017-02-06 | |

4 Comma list conditionals

| | |
|------------------------------------|--|
| <code>\clist_if_empty_p:N</code> * | <code>\clist_if_empty_p:N <comma list></code> |
| <code>\clist_if_empty_p:c</code> * | <code>\clist_if_empty:NtF <comma list> {<true code>} {<false code>}</code> |
| <code>\clist_if_empty:NtF</code> * | Tests if the <i><comma list></i> is empty (containing no items). |
| <code>\clist_if_empty:cTf</code> * | |

| | |
|------------------------------------|--|
| <code>\clist_if_empty_p:n</code> * | <code>\clist_if_empty_p:n {<comma list>}</code> |
| <code>\clist_if_empty:nTf</code> * | <code>\clist_if_empty:nTf {<comma list>} {<true code>} {<false code>}</code> |

New: 2014-07-05

Tests if the *<comma list>* is empty (containing no items). The rules for space trimming are as for other n-type comma-list functions, hence the comma list *{~,~,~,~}* (without outer braces) is empty, while *{~,{}},}* (without outer braces) contains one element, which happens to be empty: the comma-list is not empty.

| | |
|--|---|
| <code>\clist_if_in:NnTf</code> | <code>\clist_if_in:NnTf <comma list> {<item>} {<true code>} {<false code>}</code> |
| <code>\clist_if_in:(NV No cn cV co)Tf</code> | |
| <code>\clist_if_in:nnTf</code> | |
| <code>\clist_if_in:(nV no)Tf</code> | |

Updated: 2011-09-06

Tests if the *<item>* is present in the *<comma list>*. In the case of an n-type *<comma list>*, spaces are stripped from each item, but braces are not removed. Hence,

```
\clist_if_in:nnTf { a , {b}~ , {b} , c } { b } {true} {false}
```

yields false.

TeXhackers note: The *<item>* may not contain `{}`, `}`, or `#` (assuming the usual TeX category codes apply), and should not contain `,` nor start or end with a space.

5 Mapping to comma lists

The functions described in this section apply a specified function to each item of a comma list.

When the comma list is given explicitly, as an n-type argument, spaces are trimmed around each item. If the result of trimming spaces is empty, the item is ignored. Otherwise, if the item is surrounded by braces, one set is removed, and the result is passed to the mapped function. Thus, if your comma list that is being mapped is *{a_,_{b}_,_,{ },_{c},}* then the arguments passed to the mapped function are ‘a’, ‘{b}_’, an empty argument, and ‘c’.

When the comma list is given as an N-type argument, spaces have already been trimmed on input, and items are simply stripped of one set of braces if any. This case is more efficient than using n-type comma lists.

| | |
|---------------------------------------|--|
| <code>\clist_map_function:NN</code> ☆ | <code>\clist_map_function:NN</code> $\langle comma list \rangle$ $\langle function \rangle$ |
| <code>\clist_map_function:cN</code> ☆ | Applies $\langle function \rangle$ to every $\langle item \rangle$ stored in the $\langle comma list \rangle$. The $\langle function \rangle$ will receive one argument for each iteration. The $\langle items \rangle$ are returned from left to right. The function <code>\clist_map_inline:Nn</code> is in general more efficient than <code>\clist_map_function:NN</code> . One mapping may be nested inside another. |
| <code>\clist_map_function:nN</code> ☆ | |
| Updated: 2012-06-29 | |

| | |
|-----------------------------------|---|
| <code>\clist_map_inline:Nn</code> | <code>\clist_map_inline:Nn</code> $\langle comma list \rangle$ $\{ \langle inline function \rangle \}$ |
| <code>\clist_map_inline:cn</code> | Applies $\langle inline function \rangle$ to every $\langle item \rangle$ stored within the $\langle comma list \rangle$. The $\langle inline function \rangle$ should consist of code which will receive the $\langle item \rangle$ as #1. One in line mapping can be nested inside another. The $\langle items \rangle$ are returned from left to right. |
| <code>\clist_map_inline:nn</code> | |
| Updated: 2012-06-29 | |

| | |
|--------------------------------------|---|
| <code>\clist_map_variable:NNn</code> | <code>\clist_map_variable:NNn</code> $\langle comma list \rangle$ $\langle tl var. \rangle$ $\{ \langle function using tl var. \rangle \}$ |
| <code>\clist_map_variable:cNn</code> | Stores each entry in the $\langle comma list \rangle$ in turn in the $\langle tl var. \rangle$ and applies the $\langle function using tl var. \rangle$. The $\langle function \rangle$ will usually consist of code making use of the $\langle tl var. \rangle$, but this is not enforced. One variable mapping can be nested inside another. The $\langle items \rangle$ are returned from left to right. |
| <code>\clist_map_variable:nNn</code> | |
| <hr/> Updated: 2012-06-29 <hr/> | |

| | |
|---|--------------------------------|
| <code>\clist_map_break:</code> ☆ | <code>\clist_map_break:</code> |
| Updated: 2012-06-29 | |
| Used to terminate a <code>\clist_map...</code> function before all entries in the $\langle comma list \rangle$ have been processed. This will normally take place within a conditional statement, for example | |

```

\clist_map_inline:Nn \l_my_clist
{
  \str_if_eq:nnTF { #1 } { bingo }
  { \clist_map_break: }
  {
    % Do something useful
  }
}

```

Use outside of a `\clist_map...` scenario will lead to low level TeX errors.

TeXhackers note: When the mapping is broken, additional tokens may be inserted by the internal macro `__prg_break_point:Nn` before further items are taken from the input stream. This will depend on the design of the mapping function.

`\clist_map_break:n` ☆

Updated: 2012-06-29

`\clist_map_break:n` {*<tokens>*}

Used to terminate a `\clist_map...` function before all entries in the *<comma list>* have been processed, inserting the *<tokens>* after the mapping has ended. This will normally take place within a conditional statement, for example

```
\clist_map_inline:Nn \l_my_clist
{
  \str_if_eq:nnTF { #1 } { bingo }
  { \clist_map_break:n { <tokens> } }
  {
    % Do something useful
  }
}
```

Use outside of a `\clist_map...` scenario will lead to low level TeX errors.

TeXhackers note: When the mapping is broken, additional tokens may be inserted by the internal macro `__prg_break_point:Nn` before the *<tokens>* are inserted into the input stream. This will depend on the design of the mapping function.

`\clist_count:N` ☆

`\clist_count:c` ☆

`\clist_count:n` ☆

New: 2012-07-13

`\clist_count:N` *<comma list>*

Leaves the number of items in the *<comma list>* in the input stream as an *<integer denotation>*. The total number of items in a *<comma list>* will include those which are duplicates, *i.e.* every item in a *<comma list>* is unique.

6 Using the content of comma lists directly

`\clist_use:Nnnn` ☆

`\clist_use:cnnn` ☆

New: 2013-05-26

`\clist_use:Nnnn` *<clist var>* {*<separator between two>*}

{*<separator between more than two>*} {*<separator between final two>*}

Places the contents of the *<clist var>* in the input stream, with the appropriate *<separator>* between the items. Namely, if the comma list has more than two items, the *<separator between more than two>* is placed between each pair of items except the last, for which the *<separator between final two>* is used. If the comma list has exactly two items, then they are placed in the input stream separated by the *<separator between two>*. If the comma list has a single item, it is placed in the input stream, and a comma list with no items produces no output. An error will be raised if the variable does not exist or if it is invalid.

For example,

```
\clist_set:Nn \l_tmpa_clist { a , b , , c , {de} , f }
\clist_use:Nnnn \l_tmpa_clist { ~and~ } { ,~ } { ,~and~ }
```

will insert “a, b, c, de, and f” in the input stream. The first separator argument is not used in this case because the comma list has more than 2 items.

TeXhackers note: The result is returned within the `\unexpanded` primitive (`\exp_not:n`), which means that the *<items>* will not expand further when appearing in an x-type argument expansion.

`\clist_use:Nn` ★

`\clist_use:cn` ★

New: 2013-05-26

`\clist_use:Nn` $\langle\textit{clist var}\rangle$ $\{\langle\textit{separator}\rangle\}$

Places the contents of the $\langle\textit{clist var}\rangle$ in the input stream, with the $\langle\textit{separator}\rangle$ between the items. If the comma list has a single item, it is placed in the input stream, and a comma list with no items produces no output. An error will be raised if the variable does not exist or if it is invalid.

For example,

```
\clist_set:Nn \l_tmpa_clist { a , b , , c , {de} , f }
\clist_use:Nn \l_tmpa_clist { ~and~ }
```

will insert “a and b and c and de and f” in the input stream.

T_EXhackers note: The result is returned within the `\unexpanded` primitive (`\exp_not:n`), which means that the $\langle\textit{items}\rangle$ will not expand further when appearing in an `x`-type argument expansion.

7 Comma lists as stacks

Comma lists can be used as stacks, where data is pushed to and popped from the top of the comma list. (The left of a comma list is the top, for performance reasons.) The stack functions for comma lists are not intended to be mixed with the general ordered data functions detailed in the previous section: a comma list should either be used as an ordered data type or as a stack, but not in both ways.

`\clist_get:NN`

`\clist_get:cN`

Updated: 2012-05-14

`\clist_get:NN` $\langle\textit{comma list}\rangle$ $\langle\textit{token list variable}\rangle$

Stores the left-most item from a $\langle\textit{comma list}\rangle$ in the $\langle\textit{token list variable}\rangle$ without removing it from the $\langle\textit{comma list}\rangle$. The $\langle\textit{token list variable}\rangle$ is assigned locally. If the $\langle\textit{comma list}\rangle$ is empty the $\langle\textit{token list variable}\rangle$ will contain the marker value `\q_no_value`.

`\clist_get:NNTF`

`\clist_get:cNTF`

New: 2012-05-14

`\clist_get:NNTF` $\langle\textit{comma list}\rangle$ $\langle\textit{token list variable}\rangle$ $\{\langle\textit{true code}\rangle\}$ $\{\langle\textit{false code}\rangle\}$

If the $\langle\textit{comma list}\rangle$ is empty, leaves the $\langle\textit{false code}\rangle$ in the input stream. The value of the $\langle\textit{token list variable}\rangle$ is not defined in this case and should not be relied upon. If the $\langle\textit{comma list}\rangle$ is non-empty, stores the top item from the $\langle\textit{comma list}\rangle$ in the $\langle\textit{token list variable}\rangle$ without removing it from the $\langle\textit{comma list}\rangle$. The $\langle\textit{token list variable}\rangle$ is assigned locally.

`\clist_pop:NN`

`\clist_pop:cN`

Updated: 2011-09-06

`\clist_pop:NN` $\langle\textit{comma list}\rangle$ $\langle\textit{token list variable}\rangle$

Pops the left-most item from a $\langle\textit{comma list}\rangle$ into the $\langle\textit{token list variable}\rangle$, *i.e.* removes the item from the comma list and stores it in the $\langle\textit{token list variable}\rangle$. Both of the variables are assigned locally.

`\clist_gpop:NN`

`\clist_gpop:cN`

`\clist_gpop:NN` $\langle\textit{comma list}\rangle$ $\langle\textit{token list variable}\rangle$

Pops the left-most item from a $\langle\textit{comma list}\rangle$ into the $\langle\textit{token list variable}\rangle$, *i.e.* removes the item from the comma list and stores it in the $\langle\textit{token list variable}\rangle$. The $\langle\textit{comma list}\rangle$ is modified globally, while the assignment of the $\langle\textit{token list variable}\rangle$ is local.

| | |
|------------------------------|--|
| <code>\clist_pop:NNTF</code> | <code>\clist_pop:NNTF <comma list> <token list variable> {<true code>} {<false code>}</code> |
| <code>\clist_pop:cNTF</code> | If the <i><comma list></i> is empty, leaves the <i><false code></i> in the input stream. The value of the <i><token list variable></i> is not defined in this case and should not be relied upon. If the <i><comma list></i> is non-empty, pops the top item from the <i><comma list></i> in the <i><token list variable></i> , i.e. removes the item from the <i><comma list></i> . Both the <i><comma list></i> and the <i><token list variable></i> are assigned locally. |
| New: 2012-05-14 | |

| | |
|-------------------------------|--|
| <code>\clist_gpop:NNTF</code> | <code>\clist_gpop:NNTF <comma list> <token list variable> {<true code>} {<false code>}</code> |
| <code>\clist_gpop:cNTF</code> | If the <i><comma list></i> is empty, leaves the <i><false code></i> in the input stream. The value of the <i><token list variable></i> is not defined in this case and should not be relied upon. If the <i><comma list></i> is non-empty, pops the top item from the <i><comma list></i> in the <i><token list variable></i> , i.e. removes the item from the <i><comma list></i> . The <i><comma list></i> is modified globally, while the <i><token list variable></i> is assigned locally. |
| New: 2012-05-14 | |

| | |
|---|--|
| <code>\clist_push:Nn</code> | <code>\clist_push:Nn <comma list> {<items>}</code> |
| <code>\clist_push:(NV No Nx cn cV co cx)</code> | |
| <code>\clist_gpush:Nn</code> | |
| <code>\clist_gpush:(NV No Nx cn cV co cx)</code> | |
| Adds the {<items>} to the top of the <i><comma list></i> . Spaces are removed from both sides of each item. | |

8 Using a single item

| | |
|-------------------------------|---|
| <code>\clist_item:Nn</code> ★ | <code>\clist_item:Nn <comma list> {<integer expression>}</code> |
| <code>\clist_item:cn</code> ★ | |
| <code>\clist_item:nn</code> ★ | Indexing items in the <i><comma list></i> from 1 at the top (left), this function will evaluate the <i><integer expression></i> and leave the appropriate item from the comma list in the input stream. If the <i><integer expression></i> is negative, indexing occurs from the bottom (right) of the comma list. When the <i><integer expression></i> is larger than the number of items in the <i><comma list></i> (as calculated by <code>\clist_count:N</code>) then the function will expand to nothing. |
| New: 2014-07-17 | |

TeXhackers note: The result is returned within the `\unexpanded` primitive (`\exp_not:n`), which means that the *<item>* will not expand further when appearing in an x-type argument expansion.

9 Viewing comma lists

| | |
|----------------------------|--|
| <code>\clist_show:N</code> | <code>\clist_show:N <comma list></code> |
| <code>\clist_show:c</code> | Displays the entries in the <i><comma list></i> in the terminal. |
| Updated: 2015-08-03 | |
| <code>\clist_show:n</code> | <code>\clist_show:n {<tokens>}</code> |
| <code>\clist_show:n</code> | Displays the entries in the comma list in the terminal. |
| Updated: 2013-08-03 | |

| | |
|---------------------------------------|--|
| <hr/> <code>\clist_log:N</code> <hr/> | <code>\clist_log:N</code> $\langle comma list \rangle$ |
| <code>\clist_log:c</code> <hr/> | Writes the entries in the $\langle comma list \rangle$ in the log file. See also <code>\clist_show:N</code> which displays the result in the terminal. |
| <hr/> | |
| New: 2014-08-22 | |
| Updated: 2015-08-03 | |

| | |
|---------------------------------------|--|
| <hr/> <code>\clist_log:n</code> <hr/> | <code>\clist_log:n</code> $\{\langle tokens \rangle\}$ |
| <code>\clist_log:n</code> <hr/> | Writes the entries in the comma list in the log file. See also <code>\clist_show:n</code> which displays the result in the terminal. |

10 Constant and scratch comma lists

| | |
|---|--------------------------------|
| <hr/> <code>\c_empty_clist</code> <hr/> | Constant that is always empty. |
| <hr/> | |
| New: 2012-07-02 | |

| | | |
|--|---|--|
| <hr/> <code>\l_tmpa_clist</code> <hr/> | Scratch comma lists for local assignment. These are never used by the kernel code, and so are safe for use with any L ^A T _E X3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage. | |
| <code>\l_tmpb_clist</code> <hr/> | | |
| <hr/> | | |
| New: 2011-09-06 | | |

| | | |
|----------------------------|--|--|
| <code>\g_tmpa_clist</code> | Scratch comma lists for global assignment. These are never used by the kernel code, and so are safe for use with any L ^A T _E X3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage. | |
| <code>\g_tmpb_clist</code> | | |
| <hr/> | | |
| New: 2011-09-06 | | |

Part XIV

The l3token package

Token manipulation

This module deals with tokens. Now this is perhaps not the most precise description so let's try with a better description: When programming in T_EX, it is often desirable to know just what a certain token is: is it a control sequence or something else. Similarly one often needs to know if a control sequence is expandable or not, a macro or a primitive, how many arguments it takes etc. Another thing of great importance (especially when it comes to document commands) is looking ahead in the token stream to see if a certain character is present and maybe even remove it or disregard other tokens while scanning. This module provides functions for both and as such will have two primary function categories: `\token_` for anything that deals with tokens and `\peek_` for looking ahead in the token stream.

Most functions we will describe here can be used on control sequences, as those are tokens as well.

It is important to distinguish two aspects of a token: its “shape” (for lack of a better word), which affects the matching of delimited arguments and the comparison of token lists containing this token, and its “meaning”, which affects whether the token expands or what operation it performs. One can have tokens of different shapes with the same meaning, but not the converse.

For instance, `\if:w`, `\if_charcode:w`, and `\tex_if:D` are three names for the same internal operation of T_EX, namely the primitive testing the next two characters for equality of their character code. They have the same meaning hence behave identically in many situations. However, T_EX distinguishes them when searching for a delimited argument. Namely, the example function `\show_until_if:w` defined below will take everything until `\if:w` as an argument, despite the presence of other copies of `\if:w` under different names.

```
\cs_new:Npn \show_until_if:w #1 \if:w { \tl_show:n {#1} }
\show_until_if:w \tex_if:D \if_charcode:w \if:w
```

A list of all possible shapes and a list of all possible meanings are given in section 8.

1 Creating character tokens

```
\char_set_active_eq:NN
\char_set_active_eq:Nc
\char_gset_active_eq:NN
\char_gset_active_eq:Nc
```

Updated: 2015-11-12

```
\char_set_active_eq:NN <char> <function>
```

Sets the behaviour of the `<char>` in situations where it is active (category code 13) to be equivalent to that of the `<function>`. The category code of the `<char>` is *unchanged* by this process. The `<function>` may itself be an active character.

```
\char_set_active_eq:nN
\char_set_active_eq:nc
\char_gset_active_eq:nN
\char_gset_active_eq:nc
```

New: 2015-11-12

```
\char_set_active_eq:nN {<integer expression>} <function>
```

Sets the behaviour of the `<char>` which has character code as given by the `<integer expression>` in situations where it is active (category code 13) to be equivalent to that of the `<function>`. The category code of the `<char>` is *unchanged* by this process. The `<function>` may itself be an active character.

`\char_generate:nn` ★

New: 2015-09-09

`\char_generate:nn` { $\langle charcode \rangle$ } { $\langle catcode \rangle$ }

Generates a character token of the given $\langle charcode \rangle$ and $\langle catcode \rangle$ (both of which may be integer expressions). The $\langle catcode \rangle$ may be one of

- 1 (begin group)
- 2 (end group)
- 3 (math toggle)
- 4 (alignment)
- 6 (parameter)
- 7 (math superscript)
- 8 (math subscript)
- 11 (letter)
- 12 (other)

and other values will raise an error.

The $\langle charcode \rangle$ may be any one valid for the engine in use. Note however that for X_YTeX releases prior to 0.99992 only the 8-bit range (0 to 255) is accepted due to engine limitations.

2 Manipulating and interrogating character tokens

| | |
|---|---|
| <code>\char_set_catcode_escape:N</code> | <code>\char_set_catcode_letter:N</code> $\langle character \rangle$ |
| <code>\char_set_catcode_group_begin:N</code> | |
| <code>\char_set_catcode_group_end:N</code> | |
| <code>\char_set_catcode_math_toggle:N</code> | |
| <code>\char_set_catcode_alignment:N</code> | |
| <code>\char_set_catcode_end_line:N</code> | |
| <code>\char_set_catcode_parameter:N</code> | |
| <code>\char_set_catcode_math_superscript:N</code> | |
| <code>\char_set_catcode_math_subscript:N</code> | |
| <code>\char_set_catcode_ignore:N</code> | |
| <code>\char_set_catcode_space:N</code> | |
| <code>\char_set_catcode_letter:N</code> | |
| <code>\char_set_catcode_other:N</code> | |
| <code>\char_set_catcode_active:N</code> | |
| <code>\char_set_catcode_comment:N</code> | |
| <code>\char_set_catcode_invalid:N</code> | |

Updated: 2015-11-11

Sets the category code of the $\langle character \rangle$ to that indicated in the function name. Depending on the current category code of the $\langle token \rangle$ the escape token may also be needed:

`\char_set_catcode_other:N` %

The assignment is local.

| | |
|---|--|
| <code>\char_set_catcode_escape:n</code> | <code>\char_set_catcode_letter:n {⟨integer expression⟩}</code> |
| <code>\char_set_catcode_group_begin:n</code> | |
| <code>\char_set_catcode_group_end:n</code> | |
| <code>\char_set_catcode_math_toggle:n</code> | |
| <code>\char_set_catcode_alignment:n</code> | |
| <code>\char_set_catcode_end_line:n</code> | |
| <code>\char_set_catcode_parameter:n</code> | |
| <code>\char_set_catcode_math_superscript:n</code> | |
| <code>\char_set_catcode_math_subscript:n</code> | |
| <code>\char_set_catcode_ignore:n</code> | |
| <code>\char_set_catcode_space:n</code> | |
| <code>\char_set_catcode_letter:n</code> | |
| <code>\char_set_catcode_other:n</code> | |
| <code>\char_set_catcode_active:n</code> | |
| <code>\char_set_catcode_comment:n</code> | |
| <code>\char_set_catcode_invalid:n</code> | |

Updated: 2015-11-11

Sets the category code of the $\langle character \rangle$ which has character code as given by the $\langle integer expression \rangle$. This version can be used to set up characters which cannot otherwise be given (*cf.* the N-type variants). The assignment is local.

| | |
|-----------------------------------|---|
| <code>\char_set_catcode:nn</code> | <code>\char_set_catcode:nn {⟨intexpr₁⟩} {⟨intexpr₂⟩}</code> |
|-----------------------------------|---|

Updated: 2015-11-11

These functions set the category code of the $\langle character \rangle$ which has character code as given by the $\langle integer expression \rangle$. The first $\langle integer expression \rangle$ is the character code and the second is the category code to apply. The setting applies within the current \TeX group. In general, the symbolic functions `\char_set_catcode_⟨type⟩` should be preferred, but there are cases where these lower-level functions may be useful.

| | |
|--------------------------------------|---|
| <code>\char_value_catcode:n</code> ★ | <code>\char_value_catcode:n {⟨integer expression⟩}</code> |
|--------------------------------------|---|

Expands to the current category code of the $\langle character \rangle$ with character code given by the $\langle integer expression \rangle$.

| | |
|---|--|
| <code>\char_show_value_catcode:n</code> | <code>\char_show_value_catcode:n {⟨integer expression⟩}</code> |
|---|--|

Displays the current category code of the $\langle character \rangle$ with character code given by the $\langle integer expression \rangle$ on the terminal.

| | |
|----------------------------------|--|
| <code>\char_set_lccode:nn</code> | <code>\char_set_lccode:nn {⟨intexpr₁⟩} {⟨intexpr₂⟩}</code> |
|----------------------------------|--|

Updated: 2015-08-06

Sets up the behaviour of the $\langle character \rangle$ when found inside `\tl_to_lowercase:n`, such that $\langle character_1 \rangle$ will be converted into $\langle character_2 \rangle$. The two $\langle characters \rangle$ may be specified using an $\langle integer expression \rangle$ for the character code concerned. This may include the \TeX ‘ $\langle character \rangle$ ’ method for converting a single character into its character code:

```
\char_set_lccode:nn { ‘\A } { ‘\a } % Standard behaviour
\char_set_lccode:nn { ‘\A } { ‘\A + 32 }
\char_set_lccode:nn { 50 } { 60 }
```

The setting applies within the current \TeX group.

| | |
|--|--|
| <hr/> <hr/> | <hr/> |
| <code>\char_value_lccode:n</code> ★ | <code>\char_value_lccode:n {\langle integer expression \rangle}</code> |
| | Expands to the current lower case code of the $\langle character \rangle$ with character code given by the $\langle integer expression \rangle$. |
| <hr/> <hr/> | <hr/> |
| <code>\char_show_value_lccode:n</code> | <code>\char_show_value_lccode:n {\langle integer expression \rangle}</code> |
| | Displays the current lower case code of the $\langle character \rangle$ with character code given by the $\langle integer expression \rangle$ on the terminal. |
| <hr/> <hr/> | <hr/> |
| <code>\char_set_uccode:nn</code> | <code>\char_set_uccode:nn {\langle intexpr_1 \rangle} {\langle intexpr_2 \rangle}</code> |
| Updated: 2015-08-06 | Sets up the behaviour of the $\langle character \rangle$ when found inside <code>\tl_to_uppercase:n</code> , such that $\langle character_1 \rangle$ will be converted into $\langle character_2 \rangle$. The two $\langle characters \rangle$ may be specified using an $\langle integer expression \rangle$ for the character code concerned. This may include the TeX ‘ $\langle character \rangle$ ’ method for converting a single character into its character code: |
| | <pre> \char_set_uccode:nn { ‘\a } { ‘\A } % Standard behaviour \char_set_uccode:nn { ‘\A } { ‘\A - 32 } \char_set_uccode:nn { 60 } { 50 } </pre> |
| | The setting applies within the current TeX group. |
| <hr/> <hr/> | <hr/> |
| <code>\char_value_uccode:n</code> ★ | <code>\char_value_uccode:n {\langle integer expression \rangle}</code> |
| | Expands to the current upper case code of the $\langle character \rangle$ with character code given by the $\langle integer expression \rangle$. |
| <hr/> <hr/> | <hr/> |
| <code>\char_show_value_uccode:n</code> | <code>\char_show_value_uccode:n {\langle integer expression \rangle}</code> |
| | Displays the current upper case code of the $\langle character \rangle$ with character code given by the $\langle integer expression \rangle$ on the terminal. |
| <hr/> <hr/> | <hr/> |
| <code>\char_set_mathcode:nn</code> | <code>\char_set_mathcode:nn {\langle intexpr_1 \rangle} {\langle intexpr_2 \rangle}</code> |
| Updated: 2015-08-06 | This function sets up the math code of $\langle character \rangle$. The $\langle character \rangle$ is specified as an $\langle integer expression \rangle$ which will be used as the character code of the relevant character. The setting applies within the current TeX group. |
| <hr/> <hr/> | <hr/> |
| <code>\char_value_mathcode:n</code> ★ | <code>\char_value_mathcode:n {\langle integer expression \rangle}</code> |
| | Expands to the current math code of the $\langle character \rangle$ with character code given by the $\langle integer expression \rangle$. |
| <hr/> <hr/> | <hr/> |
| <code>\char_show_value_mathcode:n</code> | <code>\char_show_value_mathcode:n {\langle integer expression \rangle}</code> |
| | Displays the current math code of the $\langle character \rangle$ with character code given by the $\langle integer expression \rangle$ on the terminal. |
| <hr/> <hr/> | <hr/> |
| <code>\char_set_sfcode:nn</code> | <code>\char_set_sfcode:nn {\langle intexpr_1 \rangle} {\langle intexpr_2 \rangle}</code> |
| Updated: 2015-08-06 | This function sets up the space factor for the $\langle character \rangle$. The $\langle character \rangle$ is specified as an $\langle integer expression \rangle$ which will be used as the character code of the relevant character. The setting applies within the current TeX group. |

| | |
|--|--|
| <hr/> <code>\char_value_sfcode:n</code> ★ <hr/> | <code>\char_value_sfcode:n {⟨integer expression⟩}</code> Expands to the current space factor for the $\langle character \rangle$ with character code given by the $\langle integer expression \rangle$. |
| <hr/> <code>\char_show_value_sfcode:n</code> <hr/> | <code>\char_show_value_sfcode:n {⟨integer expression⟩}</code> Displays the current space factor for the $\langle character \rangle$ with character code given by the $\langle integer expression \rangle$ on the terminal. |
| <hr/> <code>\l_char_active_seq</code> New: 2012-01-23 Updated: 2015-11-11 <hr/> | Used to track which tokens may require special handling at the document level as they are (or have been at some point) of category $\langle active \rangle$ (catcode 13). Each entry in the sequence consists of a single escaped token, for example <code>\~</code> . Active tokens should be added to the sequence when they are defined for general document use. |
| <hr/> <code>\l_char_special_seq</code> New: 2012-01-23 Updated: 2015-11-11 <hr/> | Used to track which tokens will require special handling when working with verbatim-like material at the document level as they are not of categories $\langle letter \rangle$ (catcode 11) or $\langle other \rangle$ (catcode 12). Each entry in the sequence consists of a single escaped token, for example <code>\</code> for the backslash or <code>\{</code> for an opening brace. Escaped tokens should be added to the sequence when they are defined for general document use. |

3 Generic tokens

| | |
|--|---|
| <hr/> <code>\token_new:Nn</code> <hr/> | <code>\token_new:Nn ⟨token₁⟩ {⟨token₂⟩}</code> Defines $\langle token_1 \rangle$ to globally be a snapshot of $\langle token_2 \rangle$. This will be an implicit representation of $\langle token_2 \rangle$. |
| <hr/> <code>\c_group_begin_token</code> <code>\c_group_end_token</code> <code>\c_math_toggle_token</code> <code>\c_alignment_token</code> <code>\c_parameter_token</code> <code>\c_math_superscript_token</code> <code>\c_math_subscript_token</code> <code>\c_space_token</code> <hr/> | These are implicit tokens which have the category code described by their name. They are used internally for test purposes but are also available to the programmer for other uses. |
| <hr/> <code>\c_catcode_letter_token</code> <code>\c_catcode_other_token</code> <hr/> | These are implicit tokens which have the category code described by their name. They are used internally for test purposes and should not be used other than for category code tests. |
| <hr/> <code>\c_catcode_active_tl</code> <hr/> | A token list containing an active token. This is used internally for test purposes and should not be used other than in appropriately-constructed category code tests. |

4 Converting tokens

| | | | |
|----------------------------------|---|----------------------------------|-------------------------|
| <code>\token_to_meaning:N</code> | ★ | <code>\token_to_meaning:N</code> | $\langle token \rangle$ |
| <code>\token_to_meaning:c</code> | ★ | | |

Inserts the current meaning of the $\langle token \rangle$ into the input stream as a series of characters of category code 12 (other). This will be the primitive \TeX description of the $\langle token \rangle$, thus for example both functions defined by `\cs_set_nopar:Npn` and token list variables defined using `\tl_new:N` will be described as **macros**.

\TeX hackers note: This is the \TeX primitive `\meaning`.

| | | | |
|------------------------------|---|------------------------------|-------------------------|
| <code>\token_to_str:N</code> | ★ | <code>\token_to_str:N</code> | $\langle token \rangle$ |
| <code>\token_to_str:c</code> | ★ | | |

Converts the given $\langle token \rangle$ into a series of characters with category code 12 (other). The current escape character will be the first character in the sequence, although this will also have category code 12 (the escape character is part of the $\langle token \rangle$). This function requires only a single expansion.

\TeX hackers note: `\token_to_str:N` is the \TeX primitive `\string` renamed.

5 Token conditionals

| | | | |
|--|---|--|--|
| <code>\token_if_group_begin_p:N</code> | ★ | <code>\token_if_group_begin_p:N</code> | $\langle token \rangle$ |
| <code>\token_if_group_begin:NTF</code> | ★ | <code>\token_if_group_begin:NTF</code> | $\langle token \rangle$ $\{\langle true code \rangle\}$ $\{\langle false code \rangle\}$ |

Tests if $\langle token \rangle$ has the category code of a begin group token (`{` when normal \TeX category codes are in force). Note that an explicit begin group token cannot be tested in this way, as it is not a valid N-type argument.

| | | | |
|--------------------------------------|---|--------------------------------------|--|
| <code>\token_if_group_end_p:N</code> | ★ | <code>\token_if_group_end_p:N</code> | $\langle token \rangle$ |
| <code>\token_if_group_end:NTF</code> | ★ | <code>\token_if_group_end:NTF</code> | $\langle token \rangle$ $\{\langle true code \rangle\}$ $\{\langle false code \rangle\}$ |

Tests if $\langle token \rangle$ has the category code of an end group token (`}` when normal \TeX category codes are in force). Note that an explicit end group token cannot be tested in this way, as it is not a valid N-type argument.

| | | | |
|--|---|--|--|
| <code>\token_if_math_toggle_p:N</code> | ★ | <code>\token_if_math_toggle_p:N</code> | $\langle token \rangle$ |
| <code>\token_if_math_toggle:NTF</code> | ★ | <code>\token_if_math_toggle:NTF</code> | $\langle token \rangle$ $\{\langle true code \rangle\}$ $\{\langle false code \rangle\}$ |

Tests if $\langle token \rangle$ has the category code of a math shift token (`$` when normal \TeX category codes are in force).

| | | | |
|--------------------------------------|---|--------------------------------------|--|
| <code>\token_if_alignment_p:N</code> | ★ | <code>\token_if_alignment_p:N</code> | $\langle token \rangle$ |
| <code>\token_if_alignment:NTF</code> | ★ | <code>\token_if_alignment:NTF</code> | $\langle token \rangle$ $\{\langle true code \rangle\}$ $\{\langle false code \rangle\}$ |

Tests if $\langle token \rangle$ has the category code of an alignment token (`&` when normal \TeX category codes are in force).

| | | | |
|--------------------------------------|---|--------------------------------------|--|
| <code>\token_if_parameter_p:N</code> | ★ | <code>\token_if_parameter_p:N</code> | $\langle token \rangle$ |
| <code>\token_if_parameter:NTF</code> | ★ | <code>\token_if_alignment:NTF</code> | $\langle token \rangle$ $\{\langle true code \rangle\}$ $\{\langle false code \rangle\}$ |

Tests if $\langle token \rangle$ has the category code of a macro parameter token (# when normal T_EX category codes are in force).

| | | | |
|---|---|---|--|
| <code>\token_if_math_superscript_p:N</code> | ★ | <code>\token_if_math_superscript_p:N</code> | $\langle token \rangle$ |
| <code>\token_if_math_superscript:NTF</code> | ★ | <code>\token_if_math_superscript:NTF</code> | $\langle token \rangle$ $\{\langle true code \rangle\}$ $\{\langle false code \rangle\}$ |

Tests if $\langle token \rangle$ has the category code of a superscript token (^ when normal T_EX category codes are in force).

| | | | |
|---|---|---|--|
| <code>\token_if_math_subscript_p:N</code> | ★ | <code>\token_if_math_subscript_p:N</code> | $\langle token \rangle$ |
| <code>\token_if_math_subscript:NTF</code> | ★ | <code>\token_if_math_subscript:NTF</code> | $\langle token \rangle$ $\{\langle true code \rangle\}$ $\{\langle false code \rangle\}$ |

Tests if $\langle token \rangle$ has the category code of a subscript token (_ when normal T_EX category codes are in force).

| | | | |
|----------------------------------|---|----------------------------------|--|
| <code>\token_if_space_p:N</code> | ★ | <code>\token_if_space_p:N</code> | $\langle token \rangle$ |
| <code>\token_if_space:NTF</code> | ★ | <code>\token_if_space:NTF</code> | $\langle token \rangle$ $\{\langle true code \rangle\}$ $\{\langle false code \rangle\}$ |

Tests if $\langle token \rangle$ has the category code of a space token. Note that an explicit space token with character code 32 cannot be tested in this way, as it is not a valid N-type argument.

| | | | |
|-----------------------------------|---|-----------------------------------|--|
| <code>\token_if_letter_p:N</code> | ★ | <code>\token_if_letter_p:N</code> | $\langle token \rangle$ |
| <code>\token_if_letter:NTF</code> | ★ | <code>\token_if_letter:NTF</code> | $\langle token \rangle$ $\{\langle true code \rangle\}$ $\{\langle false code \rangle\}$ |

Tests if $\langle token \rangle$ has the category code of a letter token.

| | | | |
|----------------------------------|---|----------------------------------|--|
| <code>\token_if_other_p:N</code> | ★ | <code>\token_if_other_p:N</code> | $\langle token \rangle$ |
| <code>\token_if_other:NTF</code> | ★ | <code>\token_if_other:NTF</code> | $\langle token \rangle$ $\{\langle true code \rangle\}$ $\{\langle false code \rangle\}$ |

Tests if $\langle token \rangle$ has the category code of an “other” token.

| | | | |
|-----------------------------------|---|-----------------------------------|--|
| <code>\token_if_active_p:N</code> | ★ | <code>\token_if_active_p:N</code> | $\langle token \rangle$ |
| <code>\token_if_active:NTF</code> | ★ | <code>\token_if_active:NTF</code> | $\langle token \rangle$ $\{\langle true code \rangle\}$ $\{\langle false code \rangle\}$ |

Tests if $\langle token \rangle$ has the category code of an active character.

| | | | |
|--|---|--|--|
| <code>\token_if_eq_catcode_p:NN</code> | ★ | <code>\token_if_eq_catcode_p:NN</code> | $\langle token_1 \rangle$ $\langle token_2 \rangle$ |
| <code>\token_if_eq_catcode:NNTF</code> | ★ | <code>\token_if_eq_catcode:NNTF</code> | $\langle token_1 \rangle$ $\langle token_2 \rangle$ $\{\langle true code \rangle\}$ $\{\langle false code \rangle\}$ |

Tests if the two $\langle tokens \rangle$ have the same category code.

| | | | |
|---|---|---|--|
| <code>\token_if_eq_charcode_p:NN</code> | ★ | <code>\token_if_eq_charcode_p:NN</code> | $\langle token_1 \rangle$ $\langle token_2 \rangle$ |
| <code>\token_if_eq_charcode:NNTF</code> | ★ | <code>\token_if_eq_charcode:NNTF</code> | $\langle token_1 \rangle$ $\langle token_2 \rangle$ $\{\langle true code \rangle\}$ $\{\langle false code \rangle\}$ |

Tests if the two $\langle tokens \rangle$ have the same character code.

| | | | |
|--|---|--|--|
| <code>\token_if_eq_meaning_p:NN</code> | ★ | <code>\token_if_eq_meaning_p:NN</code> | $\langle token_1 \rangle$ $\langle token_2 \rangle$ |
| <code>\token_if_eq_meaning:NNTF</code> | ★ | <code>\token_if_eq_meaning:NNTF</code> | $\langle token_1 \rangle$ $\langle token_2 \rangle$ $\{\langle true code \rangle\}$ $\{\langle false code \rangle\}$ |

Tests if the two $\langle tokens \rangle$ have the same meaning when expanded.

| | | |
|----------------------------------|---|---|
| <code>\token_if_macro_p:N</code> | ★ | <code>\token_if_macro_p:N <token></code> |
| <code>\token_if_macro:NTF</code> | ★ | <code>\token_if_macro:NTF <token> {\true code} {\false code}</code> |

Updated: 2011-05-23 Tests if the $\langle token \rangle$ is a \TeX macro.

| | | |
|-------------------------------|---|--|
| <code>\token_if_cs_p:N</code> | ★ | <code>\token_if_cs_p:N <token></code> |
| <code>\token_if_cs:NTF</code> | ★ | <code>\token_if_cs:NTF <token> {\true code} {\false code}</code> |

Tests if the $\langle token \rangle$ is a control sequence.

| | | |
|---------------------------------------|---|--|
| <code>\token_if_expandable_p:N</code> | ★ | <code>\token_if_expandable_p:N <token></code> |
| <code>\token_if_expandable:NTF</code> | ★ | <code>\token_if_expandable:NTF <token> {\true code} {\false code}</code> |

Tests if the $\langle token \rangle$ is expandable. This test returns $\langle false \rangle$ for an undefined token.

| | | |
|---------------------------------------|---|--|
| <code>\token_if_long_macro_p:N</code> | ★ | <code>\token_if_long_macro_p:N <token></code> |
| <code>\token_if_long_macro:NTF</code> | ★ | <code>\token_if_long_macro:NTF <token> {\true code} {\false code}</code> |

Updated: 2012-01-20 Tests if the $\langle token \rangle$ is a long macro.

| | | |
|--|---|---|
| <code>\token_if_protected_macro_p:N</code> | ★ | <code>\token_if_protected_macro_p:N <token></code> |
| <code>\token_if_protected_macro:NTF</code> | ★ | <code>\token_if_protected_macro:NTF <token> {\true code} {\false code}</code> |

Updated: 2012-01-20

Tests if the $\langle token \rangle$ is a protected macro: a macro which is both protected and long will return logical false .

| | | |
|---|---|--|
| <code>\token_if_protected_long_macro_p:N</code> | ★ | <code>\token_if_protected_long_macro_p:N <token></code> |
| <code>\token_if_protected_long_macro:NTF</code> | ★ | <code>\token_if_protected_long_macro:NTF <token> {\true code} {\false code}</code> |

Updated: 2012-01-20

Tests if the $\langle token \rangle$ is a protected long macro.

| | | |
|------------------------------------|---|---|
| <code>\token_if_chardef_p:N</code> | ★ | <code>\token_if_chardef_p:N <token></code> |
| <code>\token_if_chardef:NTF</code> | ★ | <code>\token_if_chardef:NTF <token> {\true code} {\false code}</code> |

Updated: 2012-01-20 Tests if the $\langle token \rangle$ is defined to be a chardef.

\TeX hackers note: Booleans, boxes and small integer constants are implemented as chardefs.

| | | |
|--|---|---|
| <code>\token_if_mathchardef_p:N</code> | ★ | <code>\token_if_mathchardef_p:N <token></code> |
| <code>\token_if_mathchardef:NTF</code> | ★ | <code>\token_if_mathchardef:NTF <token> {\true code} {\false code}</code> |

Updated: 2012-01-20

Tests if the $\langle token \rangle$ is defined to be a mathchardef.

| | | |
|---|---|--|
| <code>\token_if_dim_register_p:N</code> | ★ | <code>\token_if_dim_register_p:N <token></code> |
| <code>\token_if_dim_register:NTF</code> | ★ | <code>\token_if_dim_register:NTF <token> {\true code} {\false code}</code> |

Updated: 2012-01-20

Tests if the $\langle token \rangle$ is defined to be a dimension register.

| | | | |
|---|---|---|--|
| <code>\token_if_int_register_p:N</code> | ★ | <code>\token_if_int_register_p:N</code> | $\langle token \rangle$ |
| <code>\token_if_int_register:NTF</code> | ★ | <code>\token_if_int_register:NTF</code> | $\langle token \rangle$ $\{\langle true\ code \rangle\}$ $\{\langle false\ code \rangle\}$ |

Updated: 2012-01-20

Tests if the $\langle token \rangle$ is defined to be a integer register.

T_EXhackers note: Constant integers may be implemented as integer registers, chardefs, or mathchardefs depending on their value.

| | | | |
|--|---|--|--|
| <code>\token_if_muskip_register_p:N</code> | ★ | <code>\token_if_muskip_register_p:N</code> | $\langle token \rangle$ |
| <code>\token_if_muskip_register:NTF</code> | ★ | <code>\token_if_muskip_register:NTF</code> | $\langle token \rangle$ $\{\langle true\ code \rangle\}$ $\{\langle false\ code \rangle\}$ |

New: 2012-02-15

Tests if the $\langle token \rangle$ is defined to be a muskip register.

| | | | |
|--|---|--|--|
| <code>\token_if_skip_register_p:N</code> | ★ | <code>\token_if_skip_register_p:N</code> | $\langle token \rangle$ |
| <code>\token_if_skip_register:NTF</code> | ★ | <code>\token_if_skip_register:NTF</code> | $\langle token \rangle$ $\{\langle true\ code \rangle\}$ $\{\langle false\ code \rangle\}$ |

Updated: 2012-01-20

Tests if the $\langle token \rangle$ is defined to be a skip register.

| | | | |
|--|---|--|--|
| <code>\token_if_toks_register_p:N</code> | ★ | <code>\token_if_toks_register_p:N</code> | $\langle token \rangle$ |
| <code>\token_if_toks_register:NTF</code> | ★ | <code>\token_if_toks_register:NTF</code> | $\langle token \rangle$ $\{\langle true\ code \rangle\}$ $\{\langle false\ code \rangle\}$ |

Updated: 2012-01-20

Tests if the $\langle token \rangle$ is defined to be a toks register (not used by L^AT_EX3).

| | | | |
|--------------------------------------|---|--------------------------------------|--|
| <code>\token_if_primitive_p:N</code> | ★ | <code>\token_if_primitive_p:N</code> | $\langle token \rangle$ |
| <code>\token_if_primitive:NTF</code> | ★ | <code>\token_if_primitive:NTF</code> | $\langle token \rangle$ $\{\langle true\ code \rangle\}$ $\{\langle false\ code \rangle\}$ |

Updated: 2011-05-23

Tests if the $\langle token \rangle$ is an engine primitive.

6 Peeking ahead at the next token

There is often a need to look ahead at the next token in the input stream while leaving it in place. This is handled using the “peek” functions. The generic `\peek_after:Nw` is provided along with a family of predefined tests for common cases. As peeking ahead does *not* skip spaces the predefined tests include both a space-respecting and space-skipping version.

| | | | |
|-----------------------------|-----------------------------|----------------------------|-------------------------|
| <code>\peek_after:Nw</code> | <code>\peek_after:Nw</code> | $\langle function \rangle$ | $\langle token \rangle$ |
|-----------------------------|-----------------------------|----------------------------|-------------------------|

Locally sets the test variable `\l_peek_token` equal to $\langle token \rangle$ (as an implicit token, *not* as a token list), and then expands the $\langle function \rangle$. The $\langle token \rangle$ will remain in the input stream as the next item after the $\langle function \rangle$. The $\langle token \rangle$ here may be \sqcup , $\{$ or $\}$ (assuming normal T_EX category codes), *i.e.* it is not necessarily the next argument which would be grabbed by a normal function.

\peek_gafter:Nw**\peek_gafter:Nw** $\langle function \rangle$ $\langle token \rangle$

Globally sets the test variable `\g_peek_token` equal to $\langle token \rangle$ (as an implicit token, *not* as a token list), and then expands the $\langle function \rangle$. The $\langle token \rangle$ will remain in the input stream as the next item after the $\langle function \rangle$. The $\langle token \rangle$ here may be \sqcup , $\{$ or $\}$ (assuming normal T_EX category codes), *i.e.* it is not necessarily the next argument which would be grabbed by a normal function.

\l_peek_tokenToken set by `\peek_after:Nw` and available for testing as described above.

\g_peek_tokenToken set by `\peek_gafter:Nw` and available for testing as described above.

\peek_catcode:NTF**\peek_catcode:NTF** $\langle test token \rangle$ $\{\langle true code \rangle\}$ $\{\langle false code \rangle\}$

Updated: 2012-12-20

Tests if the next $\langle token \rangle$ in the input stream has the same category code as the $\langle test token \rangle$ (as defined by the test `\token_if_eq_catcode:NNTF`). Spaces are respected by the test and the $\langle token \rangle$ will be left in the input stream after the $\langle true code \rangle$ or $\langle false code \rangle$ (as appropriate to the result of the test).

\peek_catcode_ignore_spaces:NTF**\peek_catcode_ignore_spaces:NTF** $\langle test token \rangle$ $\{\langle true code \rangle\}$ $\{\langle false code \rangle\}$

Updated: 2012-12-20

Tests if the next non-space $\langle token \rangle$ in the input stream has the same category code as the $\langle test token \rangle$ (as defined by the test `\token_if_eq_catcode:NNTF`). Explicit and implicit space tokens (with character code 32 and category code 10) are ignored and removed by the test and the $\langle token \rangle$ will be left in the input stream after the $\langle true code \rangle$ or $\langle false code \rangle$ (as appropriate to the result of the test).

\peek_catcode_remove:NTF**\peek_catcode_remove:NTF** $\langle test token \rangle$ $\{\langle true code \rangle\}$ $\{\langle false code \rangle\}$

Updated: 2012-12-20

Tests if the next $\langle token \rangle$ in the input stream has the same category code as the $\langle test token \rangle$ (as defined by the test `\token_if_eq_catcode:NNTF`). Spaces are respected by the test and the $\langle token \rangle$ will be removed from the input stream if the test is true. The function will then place either the $\langle true code \rangle$ or $\langle false code \rangle$ in the input stream (as appropriate to the result of the test).

\peek_catcode_remove_ignore_spaces:NTF**\peek_catcode_remove_ignore_spaces:NTF** $\langle test token \rangle$ $\{\langle true code \rangle\}$ $\{\langle false code \rangle\}$

Updated: 2012-12-20

Tests if the next non-space $\langle token \rangle$ in the input stream has the same category code as the $\langle test token \rangle$ (as defined by the test `\token_if_eq_catcode:NNTF`). Explicit and implicit space tokens (with character code 32 and category code 10) are ignored and removed by the test and the $\langle token \rangle$ will be removed from the input stream if the test is true. The function will then place either the $\langle true code \rangle$ or $\langle false code \rangle$ in the input stream (as appropriate to the result of the test).

\peek_charcode:NTF**\peek_charcode:NTF** $\langle test token \rangle$ $\{\langle true code \rangle\}$ $\{\langle false code \rangle\}$

Updated: 2012-12-20

Tests if the next $\langle token \rangle$ in the input stream has the same character code as the $\langle test token \rangle$ (as defined by the test `\token_if_eq_charcode:NNTF`). Spaces are respected by the test and the $\langle token \rangle$ will be left in the input stream after the $\langle true code \rangle$ or $\langle false code \rangle$ (as appropriate to the result of the test).

| | |
|---|---|
| <u>\peek_charcode_ignore_spaces:NTF</u> | \peek_charcode_ignore_spaces:NTF <i><test token></i> <i>{<true code>}</i> <i>{<false code>}</i> |
|---|---|

Updated: 2012-12-20

Tests if the next non-space *<token>* in the input stream has the same character code as the *<test token>* (as defined by the test `\token_if_eq_charcode:NNTF`). Explicit and implicit space tokens (with character code 32 and category code 10) are ignored and removed by the test and the *<token>* will be left in the input stream after the *<true code>* or *<false code>* (as appropriate to the result of the test).

| | |
|----------------------------------|--|
| <u>\peek_charcode_remove:NTF</u> | \peek_charcode_remove:NTF <i><test token></i> <i>{<true code>}</i> <i>{<false code>}</i> |
|----------------------------------|--|

Updated: 2012-12-20

Tests if the next *<token>* in the input stream has the same character code as the *<test token>* (as defined by the test `\token_if_eq_charcode:NNTF`). Spaces are respected by the test and the *<token>* will be removed from the input stream if the test is true. The function will then place either the *<true code>* or *<false code>* in the input stream (as appropriate to the result of the test).

| | |
|--|--|
| <u>\peek_charcode_remove_ignore_spaces:NTF</u> | \peek_charcode_remove_ignore_spaces:NTF <i><test token></i> <i>{<true code>}</i> <i>{<false code>}</i> |
|--|--|

Updated: 2012-12-20

Tests if the next non-space *<token>* in the input stream has the same character code as the *<test token>* (as defined by the test `\token_if_eq_charcode:NNTF`). Explicit and implicit space tokens (with character code 32 and category code 10) are ignored and removed by the test and the *<token>* will be removed from the input stream if the test is true. The function will then place either the *<true code>* or *<false code>* in the input stream (as appropriate to the result of the test).

| | |
|--------------------------|--|
| <u>\peek_meaning:NTF</u> | \peek_meaning:NTF <i><test token></i> <i>{<true code>}</i> <i>{<false code>}</i> |
|--------------------------|--|

Updated: 2011-07-02

Tests if the next *<token>* in the input stream has the same meaning as the *<test token>* (as defined by the test `\token_if_eq_meaning:NNTF`). Spaces are respected by the test and the *<token>* will be left in the input stream after the *<true code>* or *<false code>* (as appropriate to the result of the test).

| | |
|--|--|
| <u>\peek_meaning_ignore_spaces:NTF</u> | \peek_meaning_ignore_spaces:NTF <i><test token></i> <i>{<true code>}</i> <i>{<false code>}</i> |
|--|--|

Updated: 2012-12-05

Tests if the next non-space *<token>* in the input stream has the same meaning as the *<test token>* (as defined by the test `\token_if_eq_meaning:NNTF`). Explicit and implicit space tokens (with character code 32 and category code 10) are ignored and removed by the test and the *<token>* will be left in the input stream after the *<true code>* or *<false code>* (as appropriate to the result of the test).

| | |
|---------------------------------|---|
| <u>\peek_meaning_remove:NTF</u> | \peek_meaning_remove:NTF <i><test token></i> <i>{<true code>}</i> <i>{<false code>}</i> |
|---------------------------------|---|

Updated: 2011-07-02

Tests if the next *<token>* in the input stream has the same meaning as the *<test token>* (as defined by the test `\token_if_eq_meaning:NNTF`). Spaces are respected by the test and the *<token>* will be removed from the input stream if the test is true. The function will then place either the *<true code>* or *<false code>* in the input stream (as appropriate to the result of the test).

| | |
|---|--|
| <code>\peek_meaning_remove_ignore_spaces:NTF</code> | <code>\peek_meaning_remove_ignore_spaces:NTF <test token></code> |
| Updated: 2012-12-05 | <code>{<true code>} {<false code>}</code> |

Tests if the next non-space $\langle token \rangle$ in the input stream has the same meaning as the $\langle test token \rangle$ (as defined by the test `\token_if_eq_meaning:NNTF`). Explicit and implicit space tokens (with character code 32 and category code 10) are ignored and removed by the test and the $\langle token \rangle$ will be removed from the input stream if the test is true. The function will then place either the $\langle true code \rangle$ or $\langle false code \rangle$ in the input stream (as appropriate to the result of the test).

7 Decomposing a macro definition

These functions decompose \TeX macros into their constituent parts: if the $\langle token \rangle$ passed is not a macro then no decomposition can occur. In the later case, all three functions leave `\scan_stop:` in the input stream.

| | |
|--------------------------------------|--|
| <code>\token_get_arg_spec:N</code> ★ | <code>\token_get_arg_spec:N <token></code> |
|--------------------------------------|--|

If the $\langle token \rangle$ is a macro, this function will leave the primitive \TeX argument specification in input stream as a string of tokens of category code 12 (with spaces having category code 10). Thus for example for a token `\next` defined by

`\cs_set:Npn \next #1#2 { x #1 y #2 }`

will leave `#1#2` in the input stream. If the $\langle token \rangle$ is not a macro then `\scan_stop:` will be left in the input stream.

\TeX hackers note: If the arg spec. contains the string `->`, then the `spec` function will produce incorrect results.

| | |
|--|--|
| <code>\token_get_replacement_spec:N</code> ★ | <code>\token_get_replacement_spec:N <token></code> |
|--|--|

If the $\langle token \rangle$ is a macro, this function will leave the replacement text in input stream as a string of tokens of category code 12 (with spaces having category code 10). Thus for example for a token `\next` defined by

`\cs_set:Npn \next #1#2 { x #1~y #2 }`

will leave `x#1 y#2` in the input stream. If the $\langle token \rangle$ is not a macro then `\scan_stop:` will be left in the input stream.

\TeX hackers note: If the arg spec. contains the string `->`, then the `spec` function will produce incorrect results.

`\token_get_prefix_spec:N` ★

`\token_get_prefix_spec:N` $\langle token \rangle$

If the $\langle token \rangle$ is a macro, this function will leave the \TeX prefixes applicable in input stream as a string of tokens of category code 12 (with spaces having category code 10). Thus for example for a token `\next` defined by

```
\cs_set:Npn \next #1#2 { x #1~y #2 }
```

will leave `\long` in the input stream. If the $\langle token \rangle$ is not a macro then `\scan_stop:` will be left in the input stream

8 Description of all possible tokens

Let us end by reviewing every case that a given token can fall into. This section is quite technical and some details are only meant for completeness. We distinguish the meaning of the token, which controls the expansion of the token and its effect on \TeX 's state, and its shape, which is used when comparing token lists such as for delimited arguments. Two tokens of the same shape must have the same meaning, but the converse does not hold.

A token has one of the following shapes.

- A control sequence, characterized by the sequence of characters that constitute its name: for instance, `\use:n` is a five-letter control sequence.
- An active character token, characterized by its character code (between 0 and 1114111 for \LuaTeX and \XeTeX and less for other engines) and category code 13.
- A character token, characterized by its character code and category code (one of 1, 2, 3, 4, 6, 7, 8, 10, 11 or 12 whose meaning is described below).⁴

There are also a few internal tokens. The following list may be incomplete in some engines.

- Expanding `\the\font` results in a token that looks identical to the command that was used to select the current font (such as `\tenrm`) but it differs from it in shape.
- A “frozen” `\relax`, which differs from the primitive in shape (but has the same meaning), is inserted when the closing `\fi` of a conditional is encountered before the conditional is evaluated.
- Expanding `\noexpand` $\langle token \rangle$ (when the $\langle token \rangle$ is expandable) results in an internal token, displayed (temporarily) as `\notexpanded: $\langle token \rangle$` , whose shape coincides with the $\langle token \rangle$ and whose meaning differs from `\relax`.
- An `\outer endtemplate:` (expanding to another internal token, `end of alignment template`) can be encountered when peeking ahead at the next token.
- Tricky programming might access a frozen `\endwrite`.
- Some frozen tokens can only be accessed in interactive sessions: `\cr`, `\right`, `\endgroup`, `\fi`, `\inaccessible`.

⁴In \LuaTeX , there is also the case of “bytes”, which behave as character tokens of category code 12 (other) and character code between 1114112 and 1114366. They are used to output individual bytes to files, rather than UTF-8.

The meaning of a (non-active) character token is fixed by its category code (and character code) and cannot be changed. We will call these tokens *explicit* character tokens. Category codes that a character token can have are listed below by giving a sample output of the T_EX primitive `\meaning`, together with their L^AT_EX3 names and most common example:

- 1 begin-group character (`group_begin`, often `{`),
- 2 end-group character (`group_end`, often `}`),
- 3 math shift character (`math_toggle`, often `$`),
- 4 alignment tab character (`alignment`, often `&`),
- 6 macro parameter character (`parameter`, often `#`),
- 7 superscript character (`math_superscript`, often `^`),
- 8 subscript character (`math_subscript`, often `_`),
- 10 blank space (`space`, often character code 32),
- 11 the letter (`letter`, such as `A`),
- 12 the character (`other`, such as `0`).

Category code 13 (`active`) is discussed below. Input characters can also have several other category codes which do not lead to character tokens for later processing: 0 (`escape`), 5 (`end_line`), 9 (`ignore`), 14 (`comment`), and 15 (`invalid`).

The meaning of a control sequence or active character can be identical to that of any character token listed above (with any character code), and we will call such tokens *implicit* character tokens. The meaning is otherwise in the following list:

- a macro, used in L^AT_EX3 for most functions and some variables (`\tl`, `\fp`, `\seq`, ...),
- a primitive such as `\def` or `\topmark`, used in L^AT_EX3 for some functions,
- a register such as `\count123`, used in L^AT_EX3 for the implementation of some variables (`\int`, `\dim`, ...),
- a constant integer such as `\char"56` or `\mathchar"121`,
- a font selection command,
- undefined.

Macros be `\protected` or not, `\long` or not (the opposite of what L^AT_EX3 calls `\nopro`), and `\outer` or not (unused in L^AT_EX3). Their `\meaning` takes the form

`<properties> macro: <parameters>-><replacement>`

where `<properties>` is among `\protected\long\outer`, `<parameters>` describes parameters that the macro expects, such as `#1#2#3`, and `<replacement>` describes how the parameters are manipulated, such as `#2/#1/#3`.

Now is perhaps a good time to mention some subtleties relating to tokens with category code 10 (space). Any input character with this category code (normally, space and tab characters) becomes a normal space, with character code 32 and category code 10.

When a macro takes an undelimited argument, explicit space characters (with character code 32 and category code 10) are ignored. If the following token is an explicit character token with category code 1 (begin-group) and an arbitrary character code, then \TeX scans ahead to obtain an equal number of explicit character tokens with category code 1 (begin-group) and 2 (end-group), and the resulting list of tokens (with outer braces removed) becomes the argument. Otherwise, a single token is taken as the argument for the macro: we call such single tokens “N-type”, as they are suitable to be used as an argument for a function with the signature `:N`.

9 Internal functions

| | |
|-----------------------------------|--|
| <code>_char_generate:nn</code> ★ | <code>_char_generate:nn {\langle charcode \rangle} {\langle catcode \rangle}</code> |
|-----------------------------------|--|

New: 2016-03-25

This function is identical in operation to the public `\char_generate:nn` but omits various sanity tests. In particular, this means it is used in certain places where engine variations need to be accounted for by the kernel. The `\langle catcode \rangle` must give an explicit integer after a single expansion.

Part XV

The l3prop package

Property lists

L^AT_EX3 implements a “property list” data type, which contain an unordered list of entries each of which consists of a $\langle key \rangle$ and an associated $\langle value \rangle$. The $\langle key \rangle$ and $\langle value \rangle$ may both be any $\langle balanced\ text \rangle$. It is possible to map functions to property lists such that the function is applied to every key–value pair within the list.

Each entry in a property list must have a unique $\langle key \rangle$: if an entry is added to a property list which already contains the $\langle key \rangle$ then the new entry will overwrite the existing one. The $\langle keys \rangle$ are compared on a string basis, using the same method as `\str_if_eq:nn`.

Property lists are intended for storing key-based information for use within code. This is in contrast to key–value lists, which are a form of *input* parsed by the `keys` module.

1 Creating and initialising property lists

| |
|--------------------------|
| <code>\prop_new:N</code> |
| <code>\prop_new:c</code> |

`\prop_new:N` $\langle property\ list \rangle$

Creates a new $\langle property\ list \rangle$ or raises an error if the name is already taken. The declaration is global. The $\langle property\ list \rangle$ will initially contain no entries.

| |
|-----------------------------|
| <code>\prop_clear:N</code> |
| <code>\prop_clear:c</code> |
| <code>\prop_gclear:N</code> |
| <code>\prop_gclear:c</code> |

`\prop_clear:N` $\langle property\ list \rangle$

Clears all entries from the $\langle property\ list \rangle$.

| |
|---------------------------------|
| <code>\prop_clear_new:N</code> |
| <code>\prop_clear_new:c</code> |
| <code>\prop_gclear_new:N</code> |
| <code>\prop_gclear_new:c</code> |

`\prop_clear_new:N` $\langle property\ list \rangle$

Ensures that the $\langle property\ list \rangle$ exists globally by applying `\prop_new:N` if necessary, then applies `\prop_(g)clear:N` to leave the list empty.

| |
|---------------------------------------|
| <code>\prop_set_eq:NN</code> |
| <code>\prop_set_eq:(cN Nc cc)</code> |
| <code>\prop_gset_eq:NN</code> |
| <code>\prop_gset_eq:(cN Nc cc)</code> |

`\prop_set_eq:NN` $\langle property\ list_1 \rangle$ $\langle property\ list_2 \rangle$

Sets the content of $\langle property\ list_1 \rangle$ equal to that of $\langle property\ list_2 \rangle$.

2 Adding entries to property lists

| | |
|--|--|
| <code>\prop_put:Nnn</code> <code>\prop_put: (NnV Nno Nnx NVn NVV Non Noo cnn cnV cno cnx cVn cVV con coo)</code> <code>\prop_gput:Nnn</code> <code>\prop_gput: (NnV Nno Nnx NVn NVV Non Noo cnn cnV cno cnx cVn cVV con coo)</code> | <code>\prop_put:Nnn <property list></code> <code>{<key>} {<value>}</code> |
|--|--|

Updated: 2012-07-09

Adds an entry to the *<property list>* which may be accessed using the *<key>* and which has *<value>*. Both the *<key>* and *<value>* may contain any *<balanced text>*. The *<key>* is stored after processing with `\tl_to_str:n`, meaning that category codes are ignored. If the *<key>* is already present in the *<property list>*, the existing entry is overwritten by the new *<value>*.

| | |
|--|---|
| <code>\prop_put_if_new:Nnn</code> <code>\prop_put_if_new:cnn</code> <code>\prop_gput_if_new:Nnn</code> <code>\prop_gput_if_new:cnn</code> | <code>\prop_put_if_new:Nnn <property list> {<key>} {<value>}</code> |
|--|---|

If the *<key>* is present in the *<property list>* then no action is taken. If the *<key>* is not present in the *<property list>* then a new entry is added. Both the *<key>* and *<value>* may contain any *<balanced text>*. The *<key>* is stored after processing with `\tl_to_str:n`, meaning that category codes are ignored.

3 Recovering values from property lists

| | |
|---|---|
| <code>\prop_get:NnN</code> <code>\prop_get: (NVN NoN cnN cVN coN)</code> | <code>\prop_get:NnN <property list> {<key>} <tl var></code> |
|---|---|

Updated: 2011-08-28

Recovers the *<value>* stored with *<key>* from the *<property list>*, and places this in the *<token list variable>*. If the *<key>* is not found in the *<property list>* then the *<token list variable>* will contain the special marker `\q_no_value`. The *<token list variable>* is set within the current \TeX group. See also `\prop_get:NnNTF`.

| | |
|---|---|
| <code>\prop_pop:NnN</code> <code>\prop_pop: (NoN cnN coN)</code> | <code>\prop_pop:NnN <property list> {<key>} <tl var></code> |
|---|---|

Updated: 2011-08-18

Recovers the *<value>* stored with *<key>* from the *<property list>*, and places this in the *<token list variable>*. If the *<key>* is not found in the *<property list>* then the *<token list variable>* will contain the special marker `\q_no_value`. The *<key>* and *<value>* are then deleted from the property list. Both assignments are local. See also `\prop_pop:NnNTF`.

| | |
|---|--|
| <code>\prop_gpop:NnN</code> <code>\prop_gpop: (NoN cnN coN)</code> | <code>\prop_gpop:NnN <property list> {<key>} <tl var></code> |
|---|--|

Updated: 2011-08-18

Recovers the *<value>* stored with *<key>* from the *<property list>*, and places this in the *<token list variable>*. If the *<key>* is not found in the *<property list>* then the *<token list variable>* will contain the special marker `\q_no_value`. The *<key>* and *<value>* are then deleted from the property list. The *<property list>* is modified globally, while the assignment of the *<token list variable>* is local. See also `\prop_gpop:NnNTF`.

| | |
|------------------------------|--|
| <code>\prop_item:Nn</code> ★ | <code>\prop_item:Nn</code> $\langle property list \rangle$ $\{\langle key \rangle\}$ |
|------------------------------|--|

| |
|------------------------------|
| <code>\prop_item:cn</code> ★ |
|------------------------------|

New: 2014-07-17

Expands to the $\langle value \rangle$ corresponding to the $\langle key \rangle$ in the $\langle property list \rangle$. If the $\langle key \rangle$ is missing, this has an empty expansion.

TeXhackers note: This function is slower than the non-expandable analogue `\prop_get:NnN`. The result is returned within the `\unexpanded` primitive (`\exp_not:n`), which means that the $\langle value \rangle$ will not expand further when appearing in an x-type argument expansion.

4 Modifying property lists

| |
|------------------------------|
| <code>\prop_remove:Nn</code> |
|------------------------------|

| |
|--------------------------------------|
| <code>\prop_remove:(NV cn cV)</code> |
|--------------------------------------|

| |
|-------------------------------|
| <code>\prop_gremove:Nn</code> |
|-------------------------------|

| |
|---------------------------------------|
| <code>\prop_gremove:(NV cn cV)</code> |
|---------------------------------------|

New: 2012-05-12

| |
|--|
| <code>\prop_remove:Nn</code> $\langle property list \rangle$ $\{\langle key \rangle\}$ |
|--|

Removes the entry listed under $\langle key \rangle$ from the $\langle property list \rangle$. If the $\langle key \rangle$ is not found in the $\langle property list \rangle$ no change occurs, *i.e* there is no need to test for the existence of a key before deleting it.

5 Property list conditionals

| |
|-----------------------------------|
| <code>\prop_if_exist_p:N</code> ★ |
|-----------------------------------|

| |
|-----------------------------------|
| <code>\prop_if_exist_p:c</code> ★ |
|-----------------------------------|

| |
|-----------------------------------|
| <code>\prop_if_exist:NTF</code> ★ |
|-----------------------------------|

| |
|-----------------------------------|
| <code>\prop_if_exist:cTF</code> ★ |
|-----------------------------------|

New: 2012-03-03

| |
|---|
| <code>\prop_if_exist_p:N</code> $\langle property list \rangle$ |
|---|

| |
|--|
| <code>\prop_if_exist:NTF</code> $\langle property list \rangle$ $\{\langle true code \rangle\}$ $\{\langle false code \rangle\}$ |
|--|

Tests whether the $\langle property list \rangle$ is currently defined. This does not check that the $\langle property list \rangle$ really is a property list variable.

| |
|-----------------------------------|
| <code>\prop_if_empty_p:N</code> ★ |
|-----------------------------------|

| |
|-----------------------------------|
| <code>\prop_if_empty_p:c</code> ★ |
|-----------------------------------|

| |
|-----------------------------------|
| <code>\prop_if_empty:NTF</code> ★ |
|-----------------------------------|

| |
|-----------------------------------|
| <code>\prop_if_empty:cTF</code> ★ |
|-----------------------------------|

| |
|---|
| <code>\prop_if_empty_p:N</code> $\langle property list \rangle$ |
|---|

| |
|--|
| <code>\prop_if_empty:NTF</code> $\langle property list \rangle$ $\{\langle true code \rangle\}$ $\{\langle false code \rangle\}$ |
|--|

Tests if the $\langle property list \rangle$ is empty (containing no entries).

| | | |
|-------------------------------|---|--|
| <code>\prop_if_in_p:Nn</code> | ★ | <code>\prop_if_in:NnTF</code> $\langle property list \rangle$ $\{\langle key \rangle\}$ $\{\langle true code \rangle\}$ $\{\langle false code \rangle\}$ |
|-------------------------------|---|--|

| | |
|---|---|
| <code>\prop_if_in_p:(NV No cn cV co)</code> | ★ |
|---|---|

| | |
|-------------------------------|---|
| <code>\prop_if_in:NnTF</code> | ★ |
|-------------------------------|---|

| | |
|---|---|
| <code>\prop_if_in:(NV No cn cV co)TF</code> | ★ |
|---|---|

Updated: 2011-09-15

Tests if the $\langle key \rangle$ is present in the $\langle property list \rangle$, making the comparison using the method described by `\str_if_eq:nnTF`.

TeXhackers note: This function iterates through every key–value pair in the $\langle property list \rangle$ and is therefore slower than using the non-expandable `\prop_get:NnNTF`.

6 Recovering values from property lists with branching

The functions in this section combine tests for the presence of a key in a property list with recovery of the associated valued. This makes them useful for cases where different cases follow dependent on the presence or absence of a key in a property list. They offer increased readability and performance over separate testing and recovery phases.

| | |
|--|---|
| <u>\prop_get:NnNTF</u> | <u>\prop_get:NnNTF</u> $\langle\textit{property list}\rangle$ $\{\langle\textit{key}\rangle\}$ $\langle\textit{token list variable}\rangle$ |
| <u>\prop_get:(NVN NoN cnN cVN coN)TF</u> | <u>\prop_get:(NVN NoN cnN cVN coN)TF</u> $\{\langle\textit{true code}\rangle\}$ $\{\langle\textit{false code}\rangle\}$ |
| Updated: 2012-05-19 | |

If the $\langle\textit{key}\rangle$ is not present in the $\langle\textit{property list}\rangle$, leaves the $\langle\textit{false code}\rangle$ in the input stream. The value of the $\langle\textit{token list variable}\rangle$ is not defined in this case and should not be relied upon. If the $\langle\textit{key}\rangle$ is present in the $\langle\textit{property list}\rangle$, stores the corresponding $\langle\textit{value}\rangle$ in the $\langle\textit{token list variable}\rangle$ without removing it from the $\langle\textit{property list}\rangle$, then leaves the $\langle\textit{true code}\rangle$ in the input stream. The $\langle\textit{token list variable}\rangle$ is assigned locally.

| | |
|------------------------|--|
| <u>\prop_pop:NnNTF</u> | <u>\prop_pop:NnNTF</u> $\langle\textit{property list}\rangle$ $\{\langle\textit{key}\rangle\}$ $\langle\textit{token list variable}\rangle$ $\{\langle\textit{true code}\rangle\}$ |
| <u>\prop_pop:cnNTF</u> | <u>\prop_pop:cnNTF</u> $\{\langle\textit{false code}\rangle\}$ |
| New: 2011-08-18 | If the $\langle\textit{key}\rangle$ is not present in the $\langle\textit{property list}\rangle$, leaves the $\langle\textit{false code}\rangle$ in the input stream. The value of the $\langle\textit{token list variable}\rangle$ is not defined in this case and should not be relied upon. If the $\langle\textit{key}\rangle$ is present in the $\langle\textit{property list}\rangle$, pops the corresponding $\langle\textit{value}\rangle$ in the $\langle\textit{token list variable}\rangle$, <i>i.e.</i> removes the item from the $\langle\textit{property list}\rangle$. Both the $\langle\textit{property list}\rangle$ and the $\langle\textit{token list variable}\rangle$ are assigned locally. |
| Updated: 2012-05-19 | |

| | |
|-------------------------|--|
| <u>\prop_gpop:NnNTF</u> | <u>\prop_gpop:NnNTF</u> $\langle\textit{property list}\rangle$ $\{\langle\textit{key}\rangle\}$ $\langle\textit{token list variable}\rangle$ $\{\langle\textit{true code}\rangle\}$ |
| <u>\prop_gpop:cnNTF</u> | <u>\prop_gpop:cnNTF</u> $\{\langle\textit{false code}\rangle\}$ |
| New: 2011-08-18 | If the $\langle\textit{key}\rangle$ is not present in the $\langle\textit{property list}\rangle$, leaves the $\langle\textit{false code}\rangle$ in the input stream. The value of the $\langle\textit{token list variable}\rangle$ is not defined in this case and should not be relied upon. If the $\langle\textit{key}\rangle$ is present in the $\langle\textit{property list}\rangle$, pops the corresponding $\langle\textit{value}\rangle$ in the $\langle\textit{token list variable}\rangle$, <i>i.e.</i> removes the item from the $\langle\textit{property list}\rangle$. The $\langle\textit{property list}\rangle$ is modified globally, while the $\langle\textit{token list variable}\rangle$ is assigned locally. |
| Updated: 2012-05-19 | |

7 Mapping to property lists

| | |
|--------------------------------|--|
| <u>\prop_map_function:NN</u> ☆ | <u>\prop_map_function:NN</u> $\langle\textit{property list}\rangle$ $\langle\textit{function}\rangle$ |
| <u>\prop_map_function:cN</u> ☆ | Applies $\langle\textit{function}\rangle$ to every $\langle\textit{entry}\rangle$ stored in the $\langle\textit{property list}\rangle$. The $\langle\textit{function}\rangle$ will receive two argument for each iteration: the $\langle\textit{key}\rangle$ and associated $\langle\textit{value}\rangle$. The order in which $\langle\textit{entries}\rangle$ are returned is not defined and should not be relied upon. |
| Updated: 2013-01-28 | |

| | |
|----------------------------|--|
| <u>\prop_map_inline:Nn</u> | <u>\prop_map_inline:Nn</u> $\langle\textit{property list}\rangle$ $\{\langle\textit{inline function}\rangle\}$ |
| <u>\prop_map_inline:cn</u> | Applies $\langle\textit{inline function}\rangle$ to every $\langle\textit{entry}\rangle$ stored within the $\langle\textit{property list}\rangle$. The $\langle\textit{inline function}\rangle$ should consist of code which will receive the $\langle\textit{key}\rangle$ as #1 and the $\langle\textit{value}\rangle$ as #2. The order in which $\langle\textit{entries}\rangle$ are returned is not defined and should not be relied upon. |
| Updated: 2013-01-08 | |

\prop_map_break: ☆

Updated: 2012-06-29

\prop_map_break:

Used to terminate a `\prop_map...` function before all entries in the *⟨property list⟩* have been processed. This will normally take place within a conditional statement, for example

```
\prop_map_inline:Nn \l_my_prop
{
  \str_if_eq:nnTF { #1 } { bingo }
  { \prop_map_break: }
  {
    % Do something useful
  }
}
```

Use outside of a `\prop_map...` scenario will lead to low level T_EX errors.

\prop_map_break:n ☆

Updated: 2012-06-29

\prop_map_break:n {*⟨tokens⟩*}

Used to terminate a `\prop_map...` function before all entries in the *⟨property list⟩* have been processed, inserting the *⟨tokens⟩* after the mapping has ended. This will normally take place within a conditional statement, for example

```
\prop_map_inline:Nn \l_my_prop
{
  \str_if_eq:nnTF { #1 } { bingo }
  { \prop_map_break:n { <tokens> } }
  {
    % Do something useful
  }
}
```

Use outside of a `\prop_map...` scenario will lead to low level T_EX errors.

8 Viewing property lists

\prop_show:N**\prop_show:c**

Updated: 2015-08-01

\prop_show:N *⟨property list⟩*

Displays the entries in the *⟨property list⟩* in the terminal.

\prop_log:N**\prop_log:c**

New: 2014-08-12

Updated: 2015-08-01

\prop_log:N *⟨property list⟩*

Writes the entries in the *⟨property list⟩* in the log file.

9 Scratch property lists

| | |
|---------------------|--|
| <u>\l_tmpa_prop</u> | Scratch property lists for local assignment. These are never used by the kernel code, and so are safe for use with any L ^A T _E X3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage. |
| <u>\l_tmpb_prop</u> | |
| New: 2012-06-23 | |

| | |
|---------------------|---|
| <u>\g_tmpa_prop</u> | Scratch property lists for global assignment. These are never used by the kernel code, and so are safe for use with any L ^A T _E X3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage. |
| <u>\g_tmpb_prop</u> | |
| New: 2012-06-23 | |

10 Constants

| | |
|----------------------|--|
| <u>\c_empty_prop</u> | A permanently-empty property list used for internal comparisons. |
|----------------------|--|

11 Internal property list functions

| | |
|-----------------|---|
| <u>\s__prop</u> | The internal token used at the beginning of property lists. This is also used after each $\langle key \rangle$ (see __prop_pair:wn). |
|-----------------|---|

| | |
|------------------------|--|
| <u>__prop_pair:wn</u> | <u>__prop_pair:wn</u> $\langle key \rangle$ \s__prop { $\langle item \rangle$ } |
| | The internal token used to begin each key–value pair in the property list. If expanded outside of a mapping or manipulation function, an error will be raised. The definition should always be set globally. |

| | |
|----------------------------|---|
| <u>\l_prop_internal_tl</u> | Token list used to store new key–value pairs to be inserted by functions of the \prop_put:Nnn family. |
|----------------------------|---|

| | |
|---------------------------|--|
| <u>__prop_split:NnTF</u> | <u>__prop_split:NnTF</u> $\langle property\ list \rangle$ { $\langle key \rangle$ } { $\langle true\ code \rangle$ } { $\langle false\ code \rangle$ } |
| Updated: 2013-01-08 | Splits the $\langle property\ list \rangle$ at the $\langle key \rangle$, giving three token lists: the $\langle extract \rangle$ of $\langle property\ list \rangle$ before the $\langle key \rangle$, the $\langle value \rangle$ associated with the $\langle key \rangle$ and the $\langle extract \rangle$ of the $\langle property\ list \rangle$ after the $\langle value \rangle$. Both $\langle extracts \rangle$ retain the internal structure of a property list, and the concatenation of the two $\langle extracts \rangle$ is a property list. If the $\langle key \rangle$ is present in the $\langle property\ list \rangle$ then the $\langle true\ code \rangle$ is left in the input stream, with #1, #2, and #3 replaced by the first $\langle extract \rangle$, the $\langle value \rangle$, and the second $\langle extract \rangle$. If the $\langle key \rangle$ is not present in the $\langle property\ list \rangle$ then the $\langle false\ code \rangle$ is left in the input stream, with no trailing material. Both $\langle true\ code \rangle$ and $\langle false\ code \rangle$ are used in the replacement text of a macro defined internally, hence macro parameter characters should be doubled, except #1, #2, and #3 which stand in the $\langle true\ code \rangle$ for the three extracts from the property list. The $\langle key \rangle$ comparison takes place as described for \str_if_eq:nn. |

Part XVI

The l3msg package

Messages

Messages need to be passed to the user by modules, either when errors occur or to indicate how the code is proceeding. The `l3msg` module provides a consistent method for doing this (as opposed to writing directly to the terminal or log).

The system used by `l3msg` to create messages divides the process into two distinct parts. Named messages are created in the first part of the process; at this stage, no decision is made about the type of output that the message will produce. The second part of the process is actually producing a message. At this stage a choice of message *class* has to be made, for example `error`, `warning` or `info`.

By separating out the creation and use of messages, several benefits are available. First, the messages can be altered later without needing details of where they are used in the code. This makes it possible to alter the language used, the detail level and so on. Secondly, the output which results from a given message can be altered. This can be done on a message class, module or message name basis. In this way, message behaviour can be altered and messages can be entirely suppressed.

1 Creating new messages

All messages have to be created before they can be used. The text of messages will automatically be wrapped to the length available in the console. As a result, formatting is only needed where it will help to show meaning. In particular, `\` may be used to force a new line and `_` forces an explicit space. Additionally, `\{`, `\#`, `\}`, `\%` and `\~` can be used to produce the corresponding character.

Messages may be subdivided *by one level* using the `/` character. This is used within the message filtering system to allow for example the L^AT_EX kernel messages to belong to the module `LaTeX` while still being filterable at a more granular level. Thus for example

```
\msg_new:nnnn { mymodule } { submodule / message } ...
```

will allow only those messages from the `submodule` to be filtered out.

```
\msg_new:nnnn
\msg_new:nnn
```

Updated: 2011-08-16

```
\msg_new:nnnn {<module>} {<message>} {<text>} {<more text>}
```

Creates a `<message>` for a given `<module>`. The message will be defined to first give `<text>` and then `<more text>` if the user requests it. If no `<more text>` is available then a standard text is given instead. Within `<text>` and `<more text>` four parameters (`#1` to `#4`) can be used: these will be supplied at the time the message is used. An error will be raised if the `<message>` already exists.

```
\msg_set:nnnn
\msg_set:nnn
\msg_gset:nnnn
\msg_gset:nnn
```

```
\msg_set:nnnn {<module>} {<message>} {<text>} {<more text>}
```

Sets up the text for a `<message>` for a given `<module>`. The message will be defined to first give `<text>` and then `<more text>` if the user requests it. If no `<more text>` is available then a standard text is given instead. Within `<text>` and `<more text>` four parameters (`#1` to `#4`) can be used: these will be supplied at the time the message is used.

| | |
|-----------------------------------|---|
| <code>\msg_if_exist_p:nn</code> ★ | <code>\msg_if_exist_p:nn {<module>} {<message>}</code> |
| <code>\msg_if_exist:nnTF</code> ★ | <code>\msg_if_exist:nnTF {<module>} {<message>} {<true code>} {<false code>}</code> |
| New: 2012-03-03 | Tests whether the <i><message></i> for the <i><module></i> is currently defined. |

2 Contextual information for messages

| | |
|-----------------------------------|---|
| <code>\msg_line_context:</code> ☆ | <code>\msg_line_context:</code> |
| | Prints the current line number when a message is given, and thus suitable for giving context to messages. The number itself is proceeded by the text <code>on line</code> . |

| | |
|----------------------------------|---|
| <code>\msg_line_number:</code> ★ | <code>\msg_line_number:</code> |
| | Prints the current line number when a message is given. |

| | |
|----------------------------------|---|
| <code>\msg_fatal_text:n</code> ★ | <code>\msg_fatal_text:n {<module>}</code> |
| | Produces the standard text |
| | <code>Fatal <module> error</code> |
| | This function can be redefined to alter the language in which the message is given, using #1 as the name of the <i><module></i> to be included. |

| | |
|-------------------------------------|---|
| <code>\msg_critical_text:n</code> ★ | <code>\msg_critical_text:n {<module>}</code> |
| | Produces the standard text |
| | <code>Critical <module> error</code> |
| | This function can be redefined to alter the language in which the message is given, using #1 as the name of the <i><module></i> to be included. |

| | |
|----------------------------------|---|
| <code>\msg_error_text:n</code> ★ | <code>\msg_error_text:n {<module>}</code> |
| | Produces the standard text |
| | <code><module> error</code> |
| | This function can be redefined to alter the language in which the message is given, using #1 as the name of the <i><module></i> to be included. |

| | |
|------------------------------------|---|
| <code>\msg_warning_text:n</code> ★ | <code>\msg_warning_text:n {<module>}</code> |
| | Produces the standard text |
| | <code><module> warning</code> |
| | This function can be redefined to alter the language in which the message is given, using #1 as the name of the <i><module></i> to be included. |

`\msg_info_text:n` ★ `\msg_info_text:n {<module>}`

Produces the standard text:

`<module>` info

This function can be redefined to alter the language in which the message is given, using #1 as the name of the `<module>` to be included.

`\msg_see_documentation_text:n` ★ `\msg_see_documentation_text:n {<module>}`

Produces the standard text

See the `<module>` documentation for further information.

This function can be redefined to alter the language in which the message is given, using #1 as the name of the `<module>` to be included.

3 Issuing messages

Messages behave differently depending on the message class. In all cases, the message may be issued supplying 0 to 4 arguments. If the number of arguments supplied here does not match the number in the definition of the message, extra arguments will be ignored, or empty arguments added (of course the sense of the message may be impaired). The four arguments will be converted to strings before being added to the message text: the x-type variants should be used to expand material.

`\msg_fatal:nnnnnn` `\msg_fatal:nnnnnn {<module>} {<message>} {<arg one>} {<arg two>} {<arg three>} {<arg four>}`
`\msg_fatal:nnxxxx`
`\msg_fatal:nnnnnn` Issues `<module>` error `<message>`, passing `<arg one>` to `<arg four>` to the text-creating
`\msg_fatal:nnxxx` functions. After issuing a fatal error the T_EX run will halt.
`\msg_fatal:nnnn`
`\msg_fatal:nnxx`
`\msg_fatal:nnn`
`\msg_fatal:nnx`
`\msg_fatal:nn`

Updated: 2012-08-11

`\msg_critical:nnnnnn` `\msg_critical:nnnnnn {<module>} {<message>} {<arg one>} {<arg two>} {<arg three>} {<arg four>}`
`\msg_critical:nnxxxx`

`\msg_critical:nnnnnn` Issues `<module>` error `<message>`, passing `<arg one>` to `<arg four>` to the text-creating
`\msg_critical:nnxxx` functions. After issuing a critical error, T_EX will stop reading the current input file. This
`\msg_critical:nnnn` may halt the T_EX run (if the current file is the main file) or may abort reading a sub-file.
`\msg_critical:nnxx`

`\msg_critical:nnn`
`\msg_critical:nnx`
`\msg_critical:nn`

Updated: 2012-08-11

| | |
|--------------------------------|--|
| <code>\msg_error:nnnnnn</code> | <code>\msg_error:nnnnnn {<module>} {<message>} {<arg one>} {<arg two>} {<arg three>} {<arg four>}</code> |
| <code>\msg_error:nnxxxx</code> | |
| <code>\msg_error:nnnnn</code> | Issues <i><module></i> error <i><message></i> , passing <i><arg one></i> to <i><arg four></i> to the text-creating functions. The error will interrupt processing and issue the text at the terminal. After user input, the run will continue. |
| <code>\msg_error:nnxxx</code> | |
| <code>\msg_error:nnnn</code> | |
| <code>\msg_error:nnxx</code> | |
| <code>\msg_error:nnn</code> | |
| <code>\msg_error:nnx</code> | |
| <code>\msg_error:nn</code> | |

Updated: 2012-08-11

| | |
|----------------------------------|--|
| <code>\msg_warning:nnnnnn</code> | <code>\msg_warning:nnxxxx {<module>} {<message>} {<arg one>} {<arg two>} {<arg three>} {<arg four>}</code> |
| <code>\msg_warning:nnxxxx</code> | |
| <code>\msg_warning:nnnnn</code> | Issues <i><module></i> warning <i><message></i> , passing <i><arg one></i> to <i><arg four></i> to the text-creating functions. The warning text will be added to the log file and the terminal, but the T _E X run will not be interrupted. |
| <code>\msg_warning:nnxxx</code> | |
| <code>\msg_warning:nnnn</code> | |
| <code>\msg_warning:nnxx</code> | |
| <code>\msg_warning:nnn</code> | |
| <code>\msg_warning:nnx</code> | |
| <code>\msg_warning:nn</code> | |

Updated: 2012-08-11

| | |
|-------------------------------|---|
| <code>\msg_info:nnnnnn</code> | <code>\msg_info:nnnnnn {<module>} {<message>} {<arg one>} {<arg two>} {<arg three>} {<arg four>}</code> |
| <code>\msg_info:nnxxxx</code> | |
| <code>\msg_info:nnnnn</code> | Issues <i><module></i> information <i><message></i> , passing <i><arg one></i> to <i><arg four></i> to the text-creating functions. The information text will be added to the log file. |
| <code>\msg_info:nnxxx</code> | |
| <code>\msg_info:nnnn</code> | |
| <code>\msg_info:nnxx</code> | |
| <code>\msg_info:nnn</code> | |
| <code>\msg_info:nnx</code> | |
| <code>\msg_info:nn</code> | |

Updated: 2012-08-11

| | |
|------------------------------|--|
| <code>\msg_log:nnnnnn</code> | <code>\msg_log:nnnnnn {<module>} {<message>} {<arg one>} {<arg two>} {<arg three>} {<arg four>}</code> |
| <code>\msg_log:nnxxxx</code> | |
| <code>\msg_log:nnnnn</code> | Issues <i><module></i> information <i><message></i> , passing <i><arg one></i> to <i><arg four></i> to the text-creating functions. The information text will be added to the log file: the output is briefer than <code>\msg_info:nnnnnn</code> . |
| <code>\msg_log:nnxxx</code> | |
| <code>\msg_log:nnnn</code> | |
| <code>\msg_log:nnxx</code> | |
| <code>\msg_log:nnn</code> | |
| <code>\msg_log:nnx</code> | |
| <code>\msg_log:nn</code> | |

Updated: 2012-08-11

| | |
|-------------------------------|---|
| <code>\msg_none:nnnnnn</code> | <code>\msg_none:nnnnnn {<module>} {<message>} {<arg one>} {<arg two>} {<arg three>} {<arg four>}</code> |
| <code>\msg_none:nnxxxx</code> | |
| <code>\msg_none:nnnnn</code> | Does nothing: used as a message class to prevent any output at all (see the discussion of message redirection). |
| <code>\msg_none:nnxxx</code> | |
| <code>\msg_none:nnnn</code> | |
| <code>\msg_none:nnxx</code> | |
| <code>\msg_none:nnn</code> | |
| <code>\msg_none:nnx</code> | |
| <code>\msg_none:nn</code> | |

Updated: 2012-08-11

4 Redirecting messages

Each message has a “name”, which can be used to alter the behaviour of the message when it is given. Thus we might have

```
\msg_new:nnnn { module } { my-message } { Some-text } { Some-more-text }
```

to define a message, with

```
\msg_error:nn { module } { my-message }
```

when it is used. With no filtering, this will raise an error. However, we could alter the behaviour with

```
\msg_redirect_class:nn { error } { warning }
```

to turn all errors into warnings, or with

```
\msg_redirect_module:nnn { module } { error } { warning }
```

to alter only messages from that module, or even

```
\msg_redirect_name:nnn { module } { my-message } { warning }
```

to target just one message. Redirection applies first to individual messages, then to messages from one module and finally to messages of one class. Thus it is possible to select out an individual message for special treatment even if the entire class is already redirected.

Multiple redirections are possible. Redirections can be cancelled by providing an empty argument for the target class. Redirection to a missing class will raise errors immediately. Infinite loops are prevented by eliminating the redirection starting from the target of the redirection that caused the loop to appear. Namely, if redirections are requested as $A \rightarrow B$, $B \rightarrow C$ and $C \rightarrow A$ in this order, then the $A \rightarrow B$ redirection is cancelled.

| | |
|-------------------------------------|---|
| <code>\msg_redirect_class:nn</code> | <code>\msg_redirect_class:nn {<class one>} {<class two>}</code> |
|-------------------------------------|---|

Updated: 2012-04-27

Changes the behaviour of messages of *<class one>* so that they are processed using the code for those of *<class two>*.

| | |
|-------------------------|--|
| <code>\msg_log:n</code> | <code>\msg_log:n {<text>}</code> |
|-------------------------|--|

| | |
|-----------------|---|
| New: 2012-06-28 | Writes to the log file with the $\langle text \rangle$ laid out in the format |
|-----------------|---|

```
.....  
. <text>  
.....
```

where the $\langle text \rangle$ will be wrapped to fit within the current line length. Wrapping takes place using `\iow_wrap:nnnN`; the documentation for the latter should be consulted for full details.

| | |
|--------------------------|---|
| <code>\msg_term:n</code> | <code>\msg_term:n {<text>}</code> |
|--------------------------|---|

| | |
|-----------------|--|
| New: 2012-06-28 | Writes to the terminal and log file with the $\langle text \rangle$ laid out in the format |
|-----------------|--|

```
*****  
* <text>  
*****
```

where the $\langle text \rangle$ will be wrapped to fit within the current line length. Wrapping takes place using `\iow_wrap:nnnN`; the documentation for the latter should be consulted for full details.

6 Kernel-specific functions

Messages from L^AT_EX3 itself are handled by the general message system, but have their own functions. This allows some text to be pre-defined, and also ensures that serious errors can be handled properly.

| | |
|------------------------------------|--|
| <code>_msg_kernel_new:nnnn</code> | <code>_msg_kernel_new:nnnn {<module>} {<message>} {<text>} {<more text>}</code> |
|------------------------------------|--|

| |
|-----------------------------------|
| <code>_msg_kernel_new:nnn</code> |
|-----------------------------------|

| |
|---------------------|
| Updated: 2011-08-16 |
|---------------------|

Creates a kernel $\langle message \rangle$ for a given $\langle module \rangle$. The message will be defined to first give $\langle text \rangle$ and then $\langle more text \rangle$ if the user requests it. If no $\langle more text \rangle$ is available then a standard text is given instead. Within $\langle text \rangle$ and $\langle more text \rangle$ four parameters (**#1** to **#4**) can be used: these will be supplied and expanded at the time the message is used. An error will be raised if the $\langle message \rangle$ already exists.

| | |
|------------------------------------|--|
| <code>_msg_kernel_set:nnnn</code> | <code>_msg_kernel_set:nnnn {<module>} {<message>} {<text>} {<more text>}</code> |
|------------------------------------|--|

| |
|-----------------------------------|
| <code>_msg_kernel_set:nnn</code> |
|-----------------------------------|

Sets up the text for a kernel $\langle message \rangle$ for a given $\langle module \rangle$. The message will be defined to first give $\langle text \rangle$ and then $\langle more text \rangle$ if the user requests it. If no $\langle more text \rangle$ is available then a standard text is given instead. Within $\langle text \rangle$ and $\langle more text \rangle$ four parameters (**#1** to **#4**) can be used: these will be supplied and expanded at the time the message is used.

```

\_msg_kernel_fatal:nnnnnn
\_msg_kernel_fatal:nnxxxx
\_msg_kernel_fatal:nnnnn
\_msg_kernel_fatal:nnxxx
\_msg_kernel_fatal:nnnn
\_msg_kernel_fatal:nnxx
\_msg_kernel_fatal:nnn
\_msg_kernel_fatal:nnx
\_msg_kernel_fatal:nn

```

Updated: 2012-08-11

```

\_msg_kernel_fatal:nnnnnn {\module} {\message} {\arg one} {\arg two} {\arg
three}} {\arg four}}

```

Issues kernel *⟨module⟩* error *⟨message⟩*, passing *⟨arg one⟩* to *⟨arg four⟩* to the text-creating functions. After issuing a fatal error the T_EX run will halt. Cannot be redirected.

```

\_msg_kernel_error:nnnnnn
\_msg_kernel_error:nnxxxx
\_msg_kernel_error:nnnnn
\_msg_kernel_error:nnxxx
\_msg_kernel_error:nnnn
\_msg_kernel_error:nnxx
\_msg_kernel_error:nnn
\_msg_kernel_error:nnx
\_msg_kernel_error:nn

```

Updated: 2012-08-11

```

\_msg_kernel_error:nnnnnn {\module} {\message} {\arg one} {\arg two} {\arg
three}} {\arg four}}

```

Issues kernel *⟨module⟩* error *⟨message⟩*, passing *⟨arg one⟩* to *⟨arg four⟩* to the text-creating functions. The error will stop processing and issue the text at the terminal. After user input, the run will continue. Cannot be redirected.

```

\_msg_kernel_warning:nnnnnn
\_msg_kernel_warning:nnxxxx
\_msg_kernel_warning:nnnnn
\_msg_kernel_warning:nnxxx
\_msg_kernel_warning:nnnn
\_msg_kernel_warning:nnxx
\_msg_kernel_warning:nnn
\_msg_kernel_warning:nnx
\_msg_kernel_warning:nn

```

Updated: 2012-08-11

```

\_msg_kernel_warning:nnnnnn {\module} {\message} {\arg one} {\arg
two}} {\arg three}} {\arg four}}

```

Issues kernel *⟨module⟩* warning *⟨message⟩*, passing *⟨arg one⟩* to *⟨arg four⟩* to the text-creating functions. The warning text will be added to the log file, but the T_EX run will not be interrupted.

```

\_msg_kernel_info:nnnnnn
\_msg_kernel_info:nnxxxx
\_msg_kernel_info:nnnnn
\_msg_kernel_info:nnxxx
\_msg_kernel_info:nnnn
\_msg_kernel_info:nnxx
\_msg_kernel_info:nnn
\_msg_kernel_info:nnx
\_msg_kernel_info:nn

```

Updated: 2012-08-11

```

\_msg_kernel_info:nnnnnn {\module} {\message} {\arg one} {\arg two} {\arg
three}} {\arg four}}

```

Issues kernel *⟨module⟩* information *⟨message⟩*, passing *⟨arg one⟩* to *⟨arg four⟩* to the text-creating functions. The information text will be added to the log file.

7 Expandable errors

In a few places, the L^AT_EX3 kernel needs to produce errors in an expansion only context. This must be handled internally very differently from normal error messages, as none of the tools to print to the terminal or the log file are expandable. However, the interface is similar, with the important caveat that the message text and arguments are not expanded, and messages should be very short.

| | | |
|---|---|---|
| <code>_msg_kernel_expandable_error:nnnnnn</code> | ★ | <code>_msg_kernel_expandable_error:nnnnnn {<module>} {<message>}</code> |
| <code>_msg_kernel_expandable_error:nnnnn</code> | ★ | <code>{<arg one>} {<arg two>} {<arg three>} {<arg four>}</code> |
| <code>_msg_kernel_expandable_error:nnnn</code> | ★ | |
| <code>_msg_kernel_expandable_error:nnn</code> | ★ | |
| <code>_msg_kernel_expandable_error:nn</code> | ★ | |

New: 2011-11-23

Issues an error, passing *<arg one>* to *<arg four>* to the text-creating functions. The resulting string must be shorter than a line, otherwise it will be cropped.

| | | |
|---------------------------------------|---|---|
| <code>_msg_expandable_error:n</code> | ★ | <code>_msg_expandable_error:n {<error message>}</code> |
|---------------------------------------|---|---|

New: 2011-08-11
Updated: 2011-08-13

Issues an “Undefined error” message from T_EX itself, and prints the *<error message>*. The *<error message>* must be short: it is cropped at the end of one line.

T_EXhackers note: This function expands to an empty token list after two steps. Tokens inserted in response to T_EX’s prompt are read with the current category code setting, and inserted just after the place where the error message was issued.

8 Internal l3msg functions

The following functions are used in several kernel modules.

| | |
|------------------------------|---|
| <code>_msg_log_next:</code> | <code>_msg_log_next: <show-command></code> |
|------------------------------|---|

New: 2015-08-05

Causes the next *<show-command>* to send its output to the log file instead of the terminal. This allows for instance `\cs_log:N` to be defined as `_msg_log_next:\cs_show:N`. The effect of this command lasts until the next use of `_msg_show_wrap:Nn` or `_msg_show_wrap:n` or `_msg_show_variable:NNNnn`, in other words until the next time the ε -T_EX primitive `\showtokens` would have been used for showing to the terminal or until the next **variable-not-defined** error.

| | |
|---|---|
| <code>_msg_show_pre:nnnnnn</code> | <code>_msg_show_pre:nnnnnn {<module>} {<message>} {<arg one>} {<arg two>}</code> |
| <code>_msg_show_pre:(nnxxxx nnnnnV)</code> | <code>{<arg three>} {<arg four>}</code> |

New: 2015-08-05

Prints the *<message>* from *<module>* in the terminal (or log file if `_msg_log_next:` was issued) without formatting. Used in messages which print complex variable contents completely.

| |
|--|
| <code>_msg_show_variable:NNNnn</code> |
| New: 2015-08-04 |

`_msg_show_variable:NNNnn` $\langle variable \rangle$ $\langle if-exist \rangle$ $\langle if-empty \rangle$ $\{ \langle msg \rangle \}$ $\{ \langle formatted content \rangle \}$

If the $\langle variable \rangle$ does not exist according to $\langle if-exist \rangle$ (typically `\cs_if_exist:NTF`) then throw an error and do nothing more. Otherwise, if $\langle msg \rangle$ is not empty, display the message `LaTeX/kernel/show- $\langle msg \rangle$` with `\token_to_str:N` $\langle variable \rangle$ as a first argument, and a second argument that is ? or empty depending on the result of $\langle if-empty \rangle$ (typically `\tl_if_empty:NTF`) on the $\langle variable \rangle$. Then display the $\langle formatted content \rangle$ by giving it as an argument to `_msg_show_wrap:n`.

| |
|-----------------------------------|
| <code>_msg_show_wrap:Nn</code> |
| New: 2015-08-03 |
| Updated: 2015-08-07 |

`_msg_show_wrap:Nn` $\langle function \rangle$ $\{ \langle expression \rangle \}$

Shows or logs the $\langle expression \rangle$ (turned into a string), an equal sign, and the result of applying the $\langle function \rangle$ to the $\{ \langle expression \rangle \}$. For instance, if the $\langle function \rangle$ is `\int_eval:n` and the $\langle expression \rangle$ is `1+2` then this will log `> 1+2=3`. The case where the $\langle function \rangle$ is `\tl_to_str:n` is special: then the string representation of the $\langle expression \rangle$ is only logged once.

| |
|----------------------------------|
| <code>_msg_show_wrap:n</code> |
| New: 2015-08-03 |

`_msg_show_wrap:n` $\{ \langle formatted text \rangle \}$

Shows or logs the $\langle formatted text \rangle$. After expansion, unless it is empty, the $\langle formatted text \rangle$ must contain `>`, and the part of $\langle formatted text \rangle$ before the first `>` is removed. Failure to do so causes low-level \TeX errors.

| |
|---|
| <code>_msg_show_item:n</code> |
| <code>_msg_show_item:nn</code> |
| <code>_msg_show_item_unbraced:nn</code> |
| Updated: 2012-09-09 |

`_msg_show_item:n` $\langle item \rangle$
`_msg_show_item:nn` $\langle item-key \rangle$ $\langle item-value \rangle$

Auxiliary functions used within the last argument of `_msg_show_variable:NNNnn` or `_msg_show_wrap:n` to format variable items correctly for display. The `_msg_show_item:n` version is used for simple lists, the `_msg_show_item:nn` and `_msg_show_item_unbraced:nn` versions for key-value like data structures.

| |
|---|
| <code>\c_msg_coding_error_text_tl</code> |
|---|

The text

This is a coding error.

used by kernel functions when erroneous programming input is encountered.

Part XVII

The l3file package

File and I/O operations

This module provides functions for working with external files. Some of these functions apply to an entire file, and have prefix `\file_...`, while others are used to work with files on a line by line basis and have prefix `\ior_...` (reading) or `\iow_...` (writing).

It is important to remember that when reading external files \TeX will attempt to locate them both the operating system path and entries in the \TeX file database (most \TeX systems use such a database). Thus the “current path” for \TeX is somewhat broader than that for other programs.

For functions which expect a $\langle file\ name \rangle$ argument, this argument may contain both literal items and expandable content, which should on full expansion be the desired file name. Any active characters (as declared in `\l_char_active_seq`) will *not* be expanded, allowing the direct use of these in file names. File names will be quoted using `"` tokens if they contain spaces: as a result, `"` tokens are *not* permitted in file names.

1 File operation functions

`\g_file_current_name_tl`

Contains the name of the current \LaTeX file. This variable should not be modified: it is intended for information only. It will be equal to `\c_sys_jobname_str` at the start of a \LaTeX run and will be modified each time a file is read using `\file_input:n`.

`\file_if_exist:nTF`

Updated: 2012-02-10

`\file_if_exist:nTF` $\{\langle file\ name \rangle\}$ $\{\langle true\ code \rangle\}$ $\{\langle false\ code \rangle\}$

Searches for $\langle file\ name \rangle$ using the current \TeX search path and the additional paths controlled by `\file_path_include:n`.

`\file_add_path:nN`

Updated: 2012-02-10

`\file_add_path:nN` $\{\langle file\ name \rangle\}$ $\langle tl\ var \rangle$

Searches for $\langle file\ name \rangle$ in the path as detailed for `\file_if_exist:nTF`, and if found sets the $\langle tl\ var \rangle$ the fully-qualified name of the file, *i.e.* the path and file name. If the file is not found then the $\langle tl\ var \rangle$ will contain the marker `\q_no_value`.

`\file_input:n`

Updated: 2012-02-17

`\file_input:n` $\{\langle file\ name \rangle\}$

Searches for $\langle file\ name \rangle$ in the path as detailed for `\file_if_exist:nTF`, and if found reads in the file as additional \LaTeX source. All files read are recorded for information and the file name stack is updated by this function. An error will be raised if the file is not found.

`\file_path_include:n`

Updated: 2012-07-04

`\file_path_include:n` $\{\langle path \rangle\}$

Adds $\langle path \rangle$ to the list of those used to search when reading files. The assignment is local. The $\langle path \rangle$ is processed in the same way as a $\langle file\ name \rangle$, *i.e.*, with `x`-type expansion except active characters.

| | |
|--|---|
| <hr/> <code>\file_path_remove:n</code> <hr/> | <code>\file_path_remove:n {<path>}</code> |
| Updated: 2012-07-04 | Removes $\langle path \rangle$ from the list of those used to search when reading files. The assignment is local. The $\langle path \rangle$ is processed in the same way as a $\langle file\ name \rangle$, <i>i.e.</i> , with <code>x</code> -type expansion except active characters. |

| | |
|--------------------------------------|--|
| <hr/> <code>\file_list:</code> <hr/> | <code>\file_list:</code> |
| | This function will list all files loaded using <code>\file_input:n</code> in the log file. |

1.1 Input–output stream management

As T_EX is limited to 16 input streams and 16 output streams, direct use of the streams by the programmer is not supported in L^AT_EX3. Instead, an internal pool of streams is maintained, and these are allocated and deallocated as needed by other modules. As a result, the programmer should close streams when they are no longer needed, to release them for other processes.

Note that I/O operations are global: streams should all be declared with global names and treated accordingly.

| | |
|-------------------------------------|---|
| <hr/> <code>\ior_new:N</code> <hr/> | <code>\ior_new:N <stream></code> |
| <code>\ior_new:c</code> | <code>\iow_new:N <stream></code> |
| <code>\iow_new:N</code> | |
| <code>\iow_new:c</code> | |
| New: 2011-09-26 | Globally reserves the name of the $\langle stream \rangle$, either for reading or for writing as appropriate. The $\langle stream \rangle$ is not opened until the appropriate <code>\..._open:Nn</code> function is used. Attempting to use a $\langle stream \rangle$ which has not been opened is an error, and the $\langle stream \rangle$ will behave as the corresponding <code>\c_term_....</code> |
| Updated: 2011-12-27 | |

| | |
|---------------------------------------|---|
| <hr/> <code>\ior_open:Nn</code> <hr/> | <code>\ior_open:Nn <stream> {<file name>}</code> |
| <code>\ior_open:cn</code> | |
| Updated: 2012-02-10 | Opens $\langle file\ name \rangle$ for reading using $\langle stream \rangle$ as the control sequence for file access. If the $\langle stream \rangle$ was already open it is closed before the new operation begins. The $\langle stream \rangle$ is available for access immediately and will remain allocated to $\langle file\ name \rangle$ until a <code>\ior_close:N</code> instruction is given or the T _E X run ends. |

| | |
|---|--|
| <hr/> <code>\ior_open:NnTF</code> <hr/> | <code>\ior_open:NnTF <stream> {<file name>} {<true code>} {<false code>}</code> |
| <code>\ior_open:cnTF</code> | |
| New: 2013-01-12 | Opens $\langle file\ name \rangle$ for reading using $\langle stream \rangle$ as the control sequence for file access. If the $\langle stream \rangle$ was already open it is closed before the new operation begins. The $\langle stream \rangle$ is available for access immediately and will remain allocated to $\langle file\ name \rangle$ until a <code>\ior_close:N</code> instruction is given or the T _E X run ends. The $\langle true\ code \rangle$ is then inserted into the input stream. If the file is not found, no error is raised and the $\langle false\ code \rangle$ is inserted into the input stream. |

| | |
|---------------------------------------|---|
| <hr/> <code>\iow_open:Nn</code> <hr/> | <code>\iow_open:Nn <stream> {<file name>}</code> |
| <code>\iow_open:cn</code> | |
| Updated: 2012-02-09 | Opens $\langle file\ name \rangle$ for writing using $\langle stream \rangle$ as the control sequence for file access. If the $\langle stream \rangle$ was already open it is closed before the new operation begins. The $\langle stream \rangle$ is available for access immediately and will remain allocated to $\langle file\ name \rangle$ until a <code>\iow_close:N</code> instruction is given or the T _E X run ends. Opening a file for writing will clear any existing content in the file (<i>i.e.</i> writing is <i>not</i> additive). |

| | |
|---------------------------|--|
| <code>\ior_close:N</code> | <code>\ior_close:N <stream></code> |
| <code>\ior_close:c</code> | <code>\ior_close:N <stream></code> |
| <code>\iow_close:N</code> | |
| <code>\iow_close:c</code> | |

Updated: 2012-07-31

Closes the `<stream>`. Streams should always be closed when they are finished with as this ensures that they remain available to other programmers.

| | |
|---------------------------------|---------------------------------|
| <code>\ior_list_streams:</code> | <code>\ior_list_streams:</code> |
| <code>\iow_list_streams:</code> | <code>\iow_list_streams:</code> |

Updated: 2015-08-01

Displays a list of the file names associated with each open stream: intended for tracking down problems.

1.2 Reading from files

| | |
|--------------------------|---|
| <code>\ior_get:NN</code> | <code>\ior_get:NN <stream> <token list variable></code> |
|--------------------------|---|

New: 2012-06-24

Function that reads one or more lines (until an equal number of left and right braces are found) from the input `<stream>` and stores the result locally in the `<token list>` variable. If the `<stream>` is not open, input is requested from the terminal. The material read from the `<stream>` will be tokenized by `TEX` according to the category codes in force when the function is used. Note that any blank lines will be converted to the token `\par`. Therefore, if skipping blank lines is requires a test such as

```
\ior_get:NN \l_my_stream \l_tmpa_tl
\tl_set:Nn \l_tmpb_tl { \par }
\tl_if_eq:NMF \l_tmpa_tl \l_tmpb_tl
...
```

may be used. Also notice that if multiple lines are read to match braces then the resulting token list will contain `\par` tokens. As normal `TEX` tokenization is in force, any lines which do not end in a comment character (usually `%`) will have the line ending converted to a space, so for example input

```
a b c
```

will result in a token list `a b c .`

T_EXhackers note: This protected macro expands to the `TEX` primitive `\read` along with the `to` keyword.

\ior_str_get:Nn

New: 2016-12-04

\ior_str_get:Nn $\langle stream \rangle$ $\langle token\ list\ variable \rangle$

Function that reads one line from the input $\langle stream \rangle$ and stores the result locally in the $\langle token\ list \rangle$ variable. If the $\langle stream \rangle$ is not open, input is requested from the terminal. The material is read from the $\langle stream \rangle$ as a series of tokens with category code 12 (other), with the exception of space characters which are given category code 10 (space). Multiple whitespace characters are retained by this process. It will always only read one line and any blank lines in the input will result in the $\langle token\ list\ variable \rangle$ being empty. Unlike **\ior_get:Nn**, line ends do not receive any special treatment. Thus input

a b c

will result in a token list a b c with the letters a, b, and c having category code 12.

TeXhackers note: This protected macro is a wrapper around the ε -TeX primitive **\readline**. However, the end-line character normally added by this primitive is not included in the result of **\ior_str_get:Nn**.

\ior_if_eof_p:N ★**\ior_if_eof:Ntf** ★

Updated: 2012-02-10

\ior_if_eof_p:N $\langle stream \rangle$ **\ior_if_eof:Ntf** $\langle stream \rangle$ $\{\langle true\ code \rangle\}$ $\{\langle false\ code \rangle\}$

Tests if the end of a $\langle stream \rangle$ has been reached during a reading operation. The test will also return a **true** value if the $\langle stream \rangle$ is not open.

2 Writing to files

\iow_now:Nn**\iow_now:(Nx|cn|cx)**

Updated: 2012-06-05

\iow_now:Nn $\langle stream \rangle$ $\{\langle tokens \rangle\}$

This functions writes $\langle tokens \rangle$ to the specified $\langle stream \rangle$ immediately (*i.e.* the write operation is called on expansion of **\iow_now:Nn**).

\iow_log:n**\iow_log:x****\iow_log:n** $\{\langle tokens \rangle\}$

This function writes the given $\langle tokens \rangle$ to the log (transcript) file immediately: it is a dedicated version of **\iow_now:Nn**.

\iow_term:n**\iow_term:x****\iow_term:n** $\{\langle tokens \rangle\}$

This function writes the given $\langle tokens \rangle$ to the terminal file immediately: it is a dedicated version of **\iow_now:Nn**.

\iow_shipout:Nn**\iow_shipout:(Nx|cn|cx)****\iow_shipout:Nn** $\langle stream \rangle$ $\{\langle tokens \rangle\}$

This functions writes $\langle tokens \rangle$ to the specified $\langle stream \rangle$ when the current page is finalised (*i.e.* at shipout). The x-type variants expand the $\langle tokens \rangle$ at the point where the function is used but *not* when the resulting tokens are written to the $\langle stream \rangle$ (*cf.* **\iow_shipout_x:Nn**).

TeXhackers note: When using expl3 with a format other than L^AT_EX, new line characters inserted using **\iow_newline:** or using the line-wrapping code **\iow_wrap:nnnN** will not be recognized in the argument of **\iow_shipout:Nn**. This may lead to the insertion of additionnal unwanted line-breaks.

`\iow_shipout_x:Nn`
`\iow_shipout_x:(Nx|cn|cx)`

Updated: 2012-09-08

`\iow_shipout_x:Nn <stream> {<tokens>}`

This functions writes $\langle tokens \rangle$ to the specified $\langle stream \rangle$ when the current page is finalised (*i.e.* at shipout). The $\langle tokens \rangle$ are expanded at the time of writing in addition to any expansion when the function is used. This makes these functions suitable for including material finalised during the page building process (such as the page number integer).

T_EXhackers note: This is a wrapper around the T_EX primitive `\write`. When using `expl3` with a format other than L^AT_EX, new line characters inserted using `\iow_newline:` or using the line-wrapping code `\iow_wrap:nnnN` will not be recognized in the argument of `\iow_shipout:Nn`. This may lead to the insertion of additionnal unwanted line-breaks.

`\iow_char:N` ★

`\iow_char:N \<char>`

Inserts $\langle char \rangle$ into the output stream. Useful when trying to write difficult characters such as %, {, }, *etc.* in messages, for example:

`\iow_now:Nx \g_my_iow { \iow_char:N \{ text \iow_char:N \} }`

The function has no effect if writing is taking place without expansion (*e.g.* in the second argument of `\iow_now:Nn`).

`\iow_newline:` ★

`\iow_newline:`

Function to add a new line within the $\langle tokens \rangle$ written to a file. The function has no effect if writing is taking place without expansion (*e.g.* in the second argument of `\iow_now:Nn`).

T_EXhackers note: When using `expl3` with a format other than L^AT_EX, the character inserted by `\iow_newline:` will not be recognized by T_EX, which may lead to the insertion of additionnal unwanted line-breaks. This issue only affects `\iow_shipout:Nn`, `\iow_shipout_x:Nn` and direct uses of primitive operations.

2.1 Wrapping lines in output

`\iow_wrap:nnnN`

New: 2012-06-28
Updated: 2015-08-05

`\iow_wrap:nnnN` $\langle text \rangle$ $\langle run-on text \rangle$ $\langle set up \rangle$ $\langle function \rangle$

This function will wrap the $\langle text \rangle$ to a fixed number of characters per line. At the start of each line which is wrapped, the $\langle run-on text \rangle$ will be inserted. The line character count targeted will be the value of `\l_iow_line_count_int` minus the number of characters in the $\langle run-on text \rangle$ for all lines except the first, for which the target number of characters is simply `\l_iow_line_count_int` since there is no run-on text. The $\langle text \rangle$ and $\langle run-on text \rangle$ are exhaustively expanded by the function, with the following substitutions:

- `\` may be used to force a new line,
- `_` may be used to represent a forced space (for example after a control sequence),
- `\#`, `\%`, `\{`, `\}`, `\~` may be used to represent the corresponding character,
- `\iow_indent:n` may be used to indent a part of the $\langle text \rangle$ (not the $\langle run-on text \rangle$).

Additional functions may be added to the wrapping by using the $\langle set up \rangle$, which is executed before the wrapping takes place: this may include overriding the substitutions listed.

Any expandable material in the $\langle text \rangle$ which is not to be expanded on wrapping should be converted to a string using `\token_to_str:N`, `\tl_to_str:n`, `\tl_to_str:N`, *etc.*

The result of the wrapping operation is passed as a braced argument to the $\langle function \rangle$, which will typically be a wrapper around a write operation. The output of `\iow_wrap:nnnN` (*i.e.* the argument passed to the $\langle function \rangle$) will consist of characters of category “other” (category code 12), with the exception of spaces which will have category “space” (category code 10). This means that the output will *not* expand further when written to a file.

T_EXhackers note: Internally, `\iow_wrap:nnnN` carries out an `x`-type expansion on the $\langle text \rangle$ to expand it. This is done in such a way that `\exp_not:N` or `\exp_not:n` *could* be used to prevent expansion of material. However, this is less conceptually clear than conversion to a string, which is therefore the supported method for handling expandable material in the $\langle text \rangle$.

`\iow_indent:n`

New: 2011-09-21

`\iow_indent:n` $\langle text \rangle$

In the first argument of `\iow_wrap:nnnN` (for instance in messages), indents $\langle text \rangle$ by four spaces. This function will not cause a line break, and only affects lines which start within the scope of the $\langle text \rangle$. In case the indented $\langle text \rangle$ should appear on separate lines from the surrounding text, use `\` to force line breaks.

`\l_iow_line_count_int`

New: 2012-06-24

The maximum number of characters in a line to be written by the `\iow_wrap:nnnN` function. This value depends on the T_EX system in use: the standard value is 78, which is typically correct for unmodified T_EXlive and MiK_TE_X systems.

`\c_catcode_other_space_tl`

New: 2011-09-05

Token list containing one character with category code 12, (“other”), and character code 32 (space).

2.2 Constant input–output streams

| | |
|--------------------------|---|
| <code>\c_term_ior</code> | Constant input stream for reading from the terminal. Reading from this stream using <code>\ior_get:NN</code> or similar will result in a prompt from T _E X of the form |
|--------------------------|---|

`<tl>=`

| | |
|---|--|
| <code>\c_log_ior</code> <code>\c_term_ior</code> | Constant output streams for writing to the log and to the terminal (plus the log), respectively. |
|---|--|

2.3 Primitive conditionals

| | |
|--------------------------|---|
| <code>\if_eof:w</code> ★ | <pre> \if_eof:w <stream> <true code> \else: <false code> \fi: </pre> <p>Tests if the <code><stream></code> returns “end of file”, which is true for non-existent files. The <code>\else:</code> branch is optional.</p> |
|--------------------------|---|

T_EXhackers note: This is the T_EX primitive `\ifeof`.

2.4 Internal file functions and variables

| | |
|-----------------------------------|---|
| <code>\g_file_internal_ior</code> | Used to test for the existence of files when opening. |
|-----------------------------------|---|

| | |
|---------------------------------------|---|
| <code>\l_file_internal_name_tl</code> | Used to return the full name of a file for internal use. This is set by <code>\file_if_exist:nTF</code> and <code>__file_if_exist:nT</code> , and the value may then be used to load a file directly provided no further operations intervene. |
|---------------------------------------|---|

| | |
|---------------------------------------|---|
| <code>__file_name_sanitize:nn</code> | <code>__file_name_sanitize:nn {<name>} {<tokens>}</code> |
|---------------------------------------|---|

| | |
|--------------------------------|---|
| <small>New: 2012-02-09</small> | Exhaustively-expands the <code><name></code> with the exception of any category <code><active></code> (catcode 13) tokens, which are not expanded. The list of <code><active></code> tokens is taken from <code>\l_char_active_seq</code> . The <code><sanitized name></code> is then inserted (in braces) after the <code><tokens></code> , which should further process the file name. If any spaces are found in the name after expansion, an error is raised. |
|--------------------------------|---|

2.5 Internal input–output functions

| | |
|--|--|
| <code>__ior_open:Nn</code> <code>__ior_open:No</code> | <code>__ior_open:Nn <stream> {<file name>}</code> |
|--|--|

| | |
|--------------------------------|---|
| <small>New: 2012-01-23</small> | This function has identical syntax to the public version. However, it does not take precautions against active characters in the <code><file name></code> , and it does not attempt to add a <code><path></code> to the <code><file name></code> : it is therefore intended to be used by higher-level functions which have already fully expanded the <code><file name></code> and which need to perform multiple open or close operations. See for example the implementation of <code>\file_add_path:nN</code> , |
|--------------------------------|---|

_iow_with:Nnn

New: 2014-08-23

_iow_with:Nnn $\langle integer \rangle$ $\{\langle value \rangle\}$ $\{\langle code \rangle\}$

If the $\langle integer \rangle$ is equal to the $\langle value \rangle$ then this function simply runs the $\langle code \rangle$. Otherwise it saves the current value of the $\langle integer \rangle$, sets it to the $\langle value \rangle$, runs the $\langle code \rangle$, and restores the $\langle integer \rangle$ to its former value. This is used to ensure that the `\newlinechar` is 10 when writing to a stream, which lets `\iow_newline:` work, and that `\errorcontextlines` is -1 when displaying a message.

Part XVIII

The l3skip package

Dimensions and skips

L^AT_EX3 provides two general length variables: `dim` and `skip`. Lengths stored as `dim` variables have a fixed length, whereas `skip` lengths have a rubber (stretch/shrink) component. In addition, the `muskip` type is available for use in math mode: this is a special form of `skip` where the lengths involved are determined by the current math font (in μ). There are common features in the creation and setting of length variables, but for clarity the functions are grouped by variable type.

1 Creating and initialising `dim` variables

| | |
|-------------------------|-------------------------|
| <code>\dim_new:N</code> | <code>\dim_new:N</code> |
| <code>\dim_new:c</code> | <code>\dim_new:c</code> |

`\dim_new:N` $\langle dimension \rangle$

Creates a new $\langle dimension \rangle$ or raises an error if the name is already taken. The declaration is global. The $\langle dimension \rangle$ will initially be equal to 0 pt.

| | |
|----------------------------|----------------------------|
| <code>\dim_const:Nn</code> | <code>\dim_const:Nn</code> |
| <code>\dim_const:cn</code> | <code>\dim_const:cn</code> |

`\dim_const:Nn` $\langle dimension \rangle$ $\{ \langle dimension expression \rangle \}$

Creates a new constant $\langle dimension \rangle$ or raises an error if the name is already taken. The value of the $\langle dimension \rangle$ will be set globally to the $\langle dimension expression \rangle$.

New: 2012-03-05

| | |
|---------------------------|---------------------------|
| <code>\dim_zero:N</code> | <code>\dim_zero:N</code> |
| <code>\dim_zero:c</code> | <code>\dim_zero:c</code> |
| <code>\dim_gzero:N</code> | <code>\dim_gzero:N</code> |
| <code>\dim_gzero:c</code> | <code>\dim_gzero:c</code> |

`\dim_zero:N` $\langle dimension \rangle$

Sets $\langle dimension \rangle$ to 0 pt.

| | |
|-------------------------------|-------------------------------|
| <code>\dim_zero_new:N</code> | <code>\dim_zero_new:N</code> |
| <code>\dim_zero_new:c</code> | <code>\dim_zero_new:c</code> |
| <code>\dim_gzero_new:N</code> | <code>\dim_gzero_new:N</code> |
| <code>\dim_gzero_new:c</code> | <code>\dim_gzero_new:c</code> |

`\dim_zero_new:N` $\langle dimension \rangle$

Ensures that the $\langle dimension \rangle$ exists globally by applying `\dim_new:N` if necessary, then applies `\dim_(g)zero:N` to leave the $\langle dimension \rangle$ set to zero.

New: 2012-01-07

| | | |
|--------------------------------|--------------------------------|---|
| <code>\dim_if_exist_p:N</code> | <code>\dim_if_exist_p:N</code> | ★ |
| <code>\dim_if_exist_p:c</code> | <code>\dim_if_exist_p:c</code> | ★ |
| <code>\dim_if_exist:NTF</code> | <code>\dim_if_exist:NTF</code> | ★ |
| <code>\dim_if_exist:cTF</code> | <code>\dim_if_exist:cTF</code> | ★ |

`\dim_if_exist_p:N` $\langle dimension \rangle$

`\dim_if_exist_p:c` $\langle dimension \rangle$ $\{ \langle true code \rangle \} \{ \langle false code \rangle \}$

Tests whether the $\langle dimension \rangle$ is currently defined. This does not check that the $\langle dimension \rangle$ really is a dimension variable.

New: 2012-03-03

2 Setting dim variables

| | |
|---------------------------|--|
| <code>\dim_add:Nn</code> | <code>\dim_add:Nn <dimension> {<dimension expression>}</code> |
| <code>\dim_add:cn</code> | |
| <code>\dim_gadd:Nn</code> | Adds the result of the $\langle dimension\ expression \rangle$ to the current content of the $\langle dimension \rangle$. |
| <code>\dim_gadd:cn</code> | |

Updated: 2011-10-22

| | |
|---------------------------|--|
| <code>\dim_set:Nn</code> | <code>\dim_set:Nn <dimension> {<dimension expression>}</code> |
| <code>\dim_set:cn</code> | |
| <code>\dim_gset:Nn</code> | Sets $\langle dimension \rangle$ to the value of $\langle dimension\ expression \rangle$, which must evaluate to a length with units. |
| <code>\dim_gset:cn</code> | |

Updated: 2011-10-22

| | |
|--------------------------------------|--|
| <code>\dim_set_eq:NN</code> | <code>\dim_set_eq:NN <dimension₁> <dimension₂></code> |
| <code>\dim_set_eq:(cN Nc cc)</code> | |
| <code>\dim_gset_eq:NN</code> | Sets the content of $\langle dimension_1 \rangle$ equal to that of $\langle dimension_2 \rangle$. |
| <code>\dim_gset_eq:(cN Nc cc)</code> | |

| | |
|---------------------------|---|
| <code>\dim_sub:Nn</code> | <code>\dim_sub:Nn <dimension> {<dimension expression>}</code> |
| <code>\dim_sub:cn</code> | |
| <code>\dim_gsub:Nn</code> | Subtracts the result of the $\langle dimension\ expression \rangle$ from the current content of the $\langle dimension \rangle$. |
| <code>\dim_gsub:cn</code> | |

Updated: 2011-10-22

3 Utilities for dimension calculations

| | |
|-------------------------|---|
| <code>\dim_abs:n</code> | ★ <code>\dim_abs:n {<dimexpr>}</code> |
| Updated: 2012-09-26 | Converts the $\langle dimexpr \rangle$ to its absolute value, leaving the result in the input stream as a $\langle dimension\ denotation \rangle$. |

| | |
|--------------------------|--|
| <code>\dim_max:nn</code> | ★ <code>\dim_max:nn {<dimexpr₁>} {<dimexpr₂>}</code> |
| <code>\dim_min:nn</code> | ★ <code>\dim_min:nn {<dimexpr₁>} {<dimexpr₂>}</code> |
| New: 2012-09-09 | |
| Updated: 2012-09-26 | Evaluates the two $\langle dimension\ expressions \rangle$ and leaves either the maximum or minimum value in the input stream as appropriate, as a $\langle dimension\ denotation \rangle$. |

`\dim_ratio:nn` ☆

Updated: 2011-10-22

`\dim_ratio:nn {⟨dimexpr1⟩} {⟨dimexpr2⟩}`

Parses the two *⟨dimension expressions⟩* and converts the ratio of the two to a form suitable for use inside a *⟨dimension expression⟩*. This ratio is then left in the input stream, allowing syntax such as

```
\dim_set:Nn \l_my_dim
{ 10 pt * \dim_ratio:nn { 5 pt } { 10 pt } }
```

The output of `\dim_ratio:nn` on full expansion is a ration expression between two integers, with all distances converted to scaled points. Thus

```
\tl_set:Nx \l_my_tl { \dim_ratio:nn { 5 pt } { 10 pt } }
\tl_show:N \l_my_tl
```

will display 327680/655360 on the terminal.

4 Dimension expression conditionals

`\dim_compare_p:nNn` ☆

`\dim_compare:nNnTF` ☆

`\dim_compare_p:nNn {⟨dimexpr1⟩} ⟨relation⟩ {⟨dimexpr2⟩}`

`\dim_compare:nNnTF`
`{⟨dimexpr1⟩} ⟨relation⟩ {⟨dimexpr2⟩}`
`{⟨true code⟩} {⟨false code⟩}`

This function first evaluates each of the *⟨dimension expressions⟩* as described for `\dim_eval:n`. The two results are then compared using the *⟨relation⟩*:

| | |
|--------------|---|
| Equal | = |
| Greater than | > |
| Less than | < |

| | |
|--|---|
| <code>\dim_compare_p:n</code> ★ <code>\dim_compare:nTF</code> ★ | <code>\dim_compare_p:n</code> <code>{</code> <code> ⟨dimexpr₁⟩ ⟨relation₁⟩</code> <code> ...</code> <code> ⟨dimexpr_N⟩ ⟨relation_N⟩</code> <code> ⟨dimexpr_{N+1}⟩</code> <code>}</code> <code>\dim_compare:nTF</code> <code>{</code> <code> ⟨dimexpr₁⟩ ⟨relation₁⟩</code> <code> ...</code> <code> ⟨dimexpr_N⟩ ⟨relation_N⟩</code> <code> ⟨dimexpr_{N+1}⟩</code> <code>}</code> <code>{⟨true code⟩} {⟨false code⟩}</code> |
|--|---|

Updated: 2013-01-13

This function evaluates the *⟨dimension expressions⟩* as described for `\dim_eval:n` and compares consecutive result using the corresponding *⟨relation⟩*, namely it compares *⟨dimexpr₁⟩* and *⟨dimexpr₂⟩* using the *⟨relation₁⟩*, then *⟨dimexpr₂⟩* and *⟨dimexpr₃⟩* using the *⟨relation₂⟩*, until finally comparing *⟨dimexpr_N⟩* and *⟨dimexpr_{N+1}⟩* using the *⟨relation_N⟩*. The test yields **true** if all comparisons are **true**. Each *⟨dimension expression⟩* is evaluated only once, and the evaluation is lazy, in the sense that if one comparison is **false**, then no other *⟨dimension expression⟩* is evaluated and no other comparison is performed. The *⟨relations⟩* can be any of the following:

| | |
|--------------------------|---------|
| Equal | = or == |
| Greater than or equal to | >= |
| Greater than | > |
| Less than or equal to | <= |
| Less than | < |
| Not equal | != |

| | |
|-------------------------------|--|
| <code>\dim_case:nn</code> ☆ | <code>\dim_case:nnTF {⟨test dimension expression⟩}</code> |
| <code>\dim_case:nnTF</code> ☆ | <code>{</code> <code> {⟨dimexpr case₁⟩} {⟨code case₁⟩}</code> <code> {⟨dimexpr case₂⟩} {⟨code case₂⟩}</code> <code> ...</code> <code> {⟨dimexpr case_n⟩} {⟨code case_n⟩}</code> <code>}</code> <code>{⟨true code⟩}</code> <code>{⟨false code⟩}</code> |

New: 2013-07-24

This function evaluates the *⟨test dimension expression⟩* and compares this in turn to each of the *⟨dimension expression cases⟩*. If the two are equal then the associated *⟨code⟩* is left in the input stream. If any of the cases are matched, the *⟨true code⟩* is also inserted into the input stream (after the code for the appropriate case), while if none match then the *⟨false code⟩* is inserted. The function `\dim_case:nn`, which does nothing if there is no match, is also available. For example

```

\dim_set:Nn \l_tmpa_dim { 5 pt }
\dim_case:nnF
{ 2 \l_tmpa_dim }
{
  { 5 pt }      { Small }
  { 4 pt + 6 pt } { Medium }
  { - 10 pt }   { Negative }
}
{ No idea! }
```

will leave “Medium” in the input stream.

5 Dimension expression loops

| | |
|-----------------------------------|---|
| <code>\dim_do_until:nNnn</code> ☆ | <code>\dim_do_until:nNnn {⟨dimexpr₁⟩} ⟨relation⟩ {⟨dimexpr₂⟩} {⟨code⟩}</code> |
|-----------------------------------|---|

Places the *⟨code⟩* in the input stream for T_EX to process, and then evaluates the relationship between the two *⟨dimension expressions⟩* as described for `\dim_compare:nNnTF`. If the test is **false** then the *⟨code⟩* will be inserted into the input stream again and a loop will occur until the *⟨relation⟩* is **true**.

| | |
|-----------------------------------|---|
| <code>\dim_do_while:nNnn</code> ☆ | <code>\dim_do_while:nNnn {⟨dimexpr₁⟩} ⟨relation⟩ {⟨dimexpr₂⟩} {⟨code⟩}</code> |
|-----------------------------------|---|

Places the *⟨code⟩* in the input stream for T_EX to process, and then evaluates the relationship between the two *⟨dimension expressions⟩* as described for `\dim_compare:nNnTF`. If the test is **true** then the *⟨code⟩* will be inserted into the input stream again and a loop will occur until the *⟨relation⟩* is **false**.

| | |
|-----------------------------------|---|
| <code>\dim_until_do:nNnn</code> ☆ | <code>\dim_until_do:nNnn {⟨dimexpr₁⟩} ⟨relation⟩ {⟨dimexpr₂⟩} {⟨code⟩}</code> |
|-----------------------------------|---|

Evaluates the relationship between the two *⟨dimension expressions⟩* as described for `\dim_compare:nNnTF`, and then places the *⟨code⟩* in the input stream if the *⟨relation⟩* is **false**. After the *⟨code⟩* has been processed by T_EX the test will be repeated, and a loop will occur until the test is **true**.

| | |
|---|---|
| <hr/> <code>\dim_while_do:nNnn</code> ☆ | <code>\dim_while_do:nNnn {<dimexpr₁>} <relation> {<dimexpr₂>} {<code>}</code> |
| | Evaluates the relationship between the two <i><dimension expressions></i> as described for <code>\dim_compare:nNnTF</code> , and then places the <i><code></i> in the input stream if the <i><relation></i> is true . After the <i><code></i> has been processed by T _E X the test will be repeated, and a loop will occur until the test is false . |
| <hr/> <code>\dim_do_until:nn</code> ☆ | <code>\dim_do_until:nn {<dimension relation>} {<code>}</code> |
| Updated: 2013-01-13 | Places the <i><code></i> in the input stream for T _E X to process, and then evaluates the <i><dimension relation></i> as described for <code>\dim_compare:nTF</code> . If the test is false then the <i><code></i> will be inserted into the input stream again and a loop will occur until the <i><relation></i> is true . |
| <hr/> <code>\dim_do_while:nn</code> ☆ | <code>\dim_do_while:nn {<dimension relation>} {<code>}</code> |
| Updated: 2013-01-13 | Places the <i><code></i> in the input stream for T _E X to process, and then evaluates the <i><dimension relation></i> as described for <code>\dim_compare:nTF</code> . If the test is true then the <i><code></i> will be inserted into the input stream again and a loop will occur until the <i><relation></i> is false . |
| <hr/> <code>\dim_until_do:nn</code> ☆ | <code>\dim_until_do:nn {<dimension relation>} {<code>}</code> |
| Updated: 2013-01-13 | Evaluates the <i><dimension relation></i> as described for <code>\dim_compare:nTF</code> , and then places the <i><code></i> in the input stream if the <i><relation></i> is false . After the <i><code></i> has been processed by T _E X the test will be repeated, and a loop will occur until the test is true . |
| <hr/> <code>\dim_while_do:nn</code> ☆ | <code>\dim_while_do:nn {<dimension relation>} {<code>}</code> |
| Updated: 2013-01-13 | Evaluates the <i><dimension relation></i> as described for <code>\dim_compare:nTF</code> , and then places the <i><code></i> in the input stream if the <i><relation></i> is true . After the <i><code></i> has been processed by T _E X the test will be repeated, and a loop will occur until the test is false . |

6 Using dim expressions and variables

| | |
|----------------------------------|---|
| <hr/> <code>\dim_eval:n</code> ☆ | <code>\dim_eval:n {<dimension expression>}</code> |
| Updated: 2011-10-22 | Evaluates the <i><dimension expression></i> , expanding any dimensions and token list variables within the <i><expression></i> to their content (without requiring <code>\dim_use:N/\tl_use:N</code>) and applying the standard mathematical rules. The result of the calculation is left in the input stream as a <i><dimension denotation></i> after two expansions. This will be expressed in points (pt), and will require suitable termination if used in a T _E X-style assignment as it is <i>not</i> an <i><internal dimension></i> . |
| <hr/> <code>\dim_use:N</code> ☆ | <code>\dim_use:N <dimension></code> |
| <code>\dim_use:c</code> ☆ | Recovers the content of a <i><dimension></i> and places it directly in the input stream. An error will be raised if the variable does not exist or if it is invalid. Can be omitted in places where a <i><dimension></i> is required (such as in the argument of <code>\dim_eval:n</code>). |

T_EXhackers note: `\dim_use:N` is the T_EX primitive `\the`: this is one of several L^AT_EX3 names for this primitive.

| | |
|----------------------------------|--|
| <code>\dim_to_decimal:n</code> ★ | <code>\dim_to_decimal:n {⟨dimexpr⟩}</code> |
|----------------------------------|--|

New: 2014-07-15

Evaluates the $\langle dimension expression \rangle$, and leaves the result, expressed in points (`pt`) in the input stream, with *no units*. The result is rounded by \TeX to four or five decimal places. If the decimal part of the result is zero, it is omitted, together with the decimal marker.

For example

`\dim_to_decimal:n { 1bp }`

leaves 1.00374 in the input stream, *i.e.* the magnitude of one “big point” when converted to (\TeX) points.

| | |
|--|--|
| <code>\dim_to_decimal_in_bp:n</code> ★ | <code>\dim_to_decimal_in_bp:n {⟨dimexpr⟩}</code> |
|--|--|

New: 2014-07-15

Evaluates the $\langle dimension expression \rangle$, and leaves the result, expressed in big points (`bp`) in the input stream, with *no units*. The result is rounded by \TeX to four or five decimal places. If the decimal part of the result is zero, it is omitted, together with the decimal marker.

For example

`\dim_to_decimal_in_bp:n { 1pt }`

leaves 0.99628 in the input stream, *i.e.* the magnitude of one (\TeX) point when converted to big points.

| | |
|--|--|
| <code>\dim_to_decimal_in_sp:n</code> ★ | <code>\dim_to_decimal_in_sp:n {⟨dimexpr⟩}</code> |
|--|--|

New: 2015-05-18

Evaluates the $\langle dimension expression \rangle$, and leaves the result, expressed in scaled points (`sp`) in the input stream, with *no units*. The result will necessarily be an integer.

| | |
|---|---|
| <code>\dim_to_decimal_in_unit:nn</code> ★ | <code>\dim_to_decimal_in_unit:nn {⟨dimexpr₁⟩} {⟨dimexpr₂⟩}</code> |
|---|---|

New: 2014-07-15

Evaluates the $\langle dimension expressions \rangle$, and leaves the value of $\langle dimexpr_1 \rangle$, expressed in a unit given by $\langle dimexpr_2 \rangle$, in the input stream. The result is a decimal number, rounded by \TeX to four or five decimal places. If the decimal part of the result is zero, it is omitted, together with the decimal marker.

For example

`\dim_to_decimal_in_unit:nn { 1bp } { 1mm }`

leaves 0.35277 in the input stream, *i.e.* the magnitude of one big point when converted to millimetres.

Note that this function is not optimised for any particular output and as such may give different results to `\dim_to_decimal_in_bp:n` or `\dim_to_decimal_in_sp:n`. In particular, the latter is able to take a wider range of input values as it is not limited by the ability to calculate a ratio using ε - \TeX primitives, which is required internally by `\dim_to_decimal_in_unit:nn`.

| | |
|---|--|
| <hr/> <code>\dim_to_fp:n</code> ★ <hr/> | <code>\dim_to_fp:n {⟨<i>dimexpr</i>⟩}</code> |
| <hr/> New: 2012-05-08 <hr/> | Expands to an internal floating point number equal to the value of the $\langle \textit{dimexpr} \rangle$ in pt. Since dimension expressions are evaluated much faster than their floating point equivalent, <code>\dim_to_fp:n</code> can be used to speed up parts of a computation where a low precision is acceptable. |

7 Viewing dim variables

| | |
|--|--|
| <hr/> <code>\dim_show:N</code> <code>\dim_show:c</code> <hr/> | <code>\dim_show:N ⟨<i>dimension</i>⟩</code> Displays the value of the $\langle \textit{dimension} \rangle$ on the terminal. |
| <hr/> <code>\dim_show:n</code> <hr/> New: 2011-11-22 Updated: 2015-08-07 <hr/> | <code>\dim_show:n {⟨<i>dimension expression</i>⟩}</code> Displays the result of evaluating the $\langle \textit{dimension expression} \rangle$ on the terminal. |
| <hr/> <code>\dim_log:N</code> <code>\dim_log:c</code> <hr/> New: 2014-08-22 Updated: 2015-08-03 <hr/> | <code>\dim_log:N ⟨<i>dimension</i>⟩</code> Writes the value of the $\langle \textit{dimension} \rangle$ in the log file. |
| <hr/> <code>\dim_log:n</code> <hr/> New: 2014-08-22 Updated: 2015-08-07 <hr/> | <code>\dim_log:n {⟨<i>dimension expression</i>⟩}</code> Writes the result of evaluating the $\langle \textit{dimension expression} \rangle$ in the log file. |

8 Constant dimensions

| | |
|--------------------------------------|--|
| <hr/> <code>\c_max_dim</code> <hr/> | The maximum value that can be stored as a dimension. This can also be used as a component of a skip. |
| <hr/> <code>\c_zero_dim</code> <hr/> | A zero length as a dimension. This can also be used as a component of a skip. |

9 Scratch dimensions

| | |
|--|--|
| <hr/> <code>\l_tmpa_dim</code> <code>\l_tmpb_dim</code> <hr/> | Scratch dimension for local assignment. These are never used by the kernel code, and so are safe for use with any L ^A T _E X3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage. |
| <hr/> <code>\g_tmpa_dim</code> <code>\g_tmpb_dim</code> <hr/> | Scratch dimension for global assignment. These are never used by the kernel code, and so are safe for use with any L ^A T _E X3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage. |

10 Creating and initialising skip variables

`\skip_new:N`
`\skip_new:c`

`\skip_new:N` $\langle skip \rangle$

Creates a new $\langle skip \rangle$ or raises an error if the name is already taken. The declaration is global. The $\langle skip \rangle$ will initially be equal to 0pt.

`\skip_const:Nn`
`\skip_const:cn`

`\skip_const:Nn` $\langle skip \rangle$ $\{ \langle skip \text{ expression} \rangle \}$

Creates a new constant $\langle skip \rangle$ or raises an error if the name is already taken. The value of the $\langle skip \rangle$ will be set globally to the $\langle skip \text{ expression} \rangle$.

New: 2012-03-05

`\skip_zero:N`
`\skip_zero:c`
`\skip_gzero:N`
`\skip_gzero:c`

`\skip_zero:N` $\langle skip \rangle$

Sets $\langle skip \rangle$ to 0pt.

`\skip_zero_new:N`
`\skip_zero_new:c`
`\skip_gzero_new:N`
`\skip_gzero_new:c`

`\skip_zero_new:N` $\langle skip \rangle$

Ensures that the $\langle skip \rangle$ exists globally by applying `\skip_new:N` if necessary, then applies `\skip_(g)zero:N` to leave the $\langle skip \rangle$ set to zero.

New: 2012-01-07

`\skip_if_exist_p:N` ★
`\skip_if_exist_p:c` ★
`\skip_if_exist:NTF` ★
`\skip_if_exist:cTF` ★

`\skip_if_exist_p:N` $\langle skip \rangle$

`\skip_if_exist:NTF` $\langle skip \rangle$ $\{ \langle true \text{ code} \rangle \} \{ \langle false \text{ code} \rangle \}$

Tests whether the $\langle skip \rangle$ is currently defined. This does not check that the $\langle skip \rangle$ really is a skip variable.

New: 2012-03-03

11 Setting skip variables

`\skip_add:Nn`
`\skip_add:cn`
`\skip_gadd:Nn`
`\skip_gadd:cn`

`\skip_add:Nn` $\langle skip \rangle$ $\{ \langle skip \text{ expression} \rangle \}$

Adds the result of the $\langle skip \text{ expression} \rangle$ to the current content of the $\langle skip \rangle$.

Updated: 2011-10-22

`\skip_set:Nn`
`\skip_set:cn`
`\skip_gset:Nn`
`\skip_gset:cn`

`\skip_set:Nn` $\langle skip \rangle$ $\{ \langle skip \text{ expression} \rangle \}$

Sets $\langle skip \rangle$ to the value of $\langle skip \text{ expression} \rangle$, which must evaluate to a length with units and may include a rubber component (for example 1 cm plus 0.5 cm).

Updated: 2011-10-22

`\skip_set_eq:NN`
`\skip_set_eq:(cN|Nc|cc)`
`\skip_gset_eq:NN`
`\skip_gset_eq:(cN|Nc|cc)`

`\skip_set_eq:NN` $\langle skip_1 \rangle$ $\langle skip_2 \rangle$

Sets the content of $\langle skip_1 \rangle$ equal to that of $\langle skip_2 \rangle$.

| | |
|----------------------------|--|
| <code>\skip_sub:Nn</code> | <code>\skip_sub:Nn <skip> {<skip expression>}</code> |
| <code>\skip_sub:cn</code> | |
| <code>\skip_gsub:Nn</code> | Subtracts the result of the <i><skip expression></i> from the current content of the <i><skip></i> . |
| <code>\skip_gsub:cn</code> | |

Updated: 2011-10-22

12 Skip expression conditionals

| | |
|---------------------------------|--|
| <code>\skip_if_eq_p:nn</code> ★ | <code>\skip_if_eq_p:nn {<skipexpr1>} {<skipexpr2>}</code> |
| <code>\skip_if_eq:nnTF</code> ★ | <code>\dim_compare:nTF</code> <code>{<skipexpr1>} {<skipexpr2>}</code> <code>{<true code>} {<false code>}</code> |

This function first evaluates each of the *<skip expressions>* as described for `\skip_eval:n`. The two results are then compared for exact equality, *i.e.* both the fixed and rubber components must be the same for the test to be true.

| | |
|------------------------------------|--|
| <code>\skip_if_finite_p:n</code> ★ | <code>\skip_if_finite_p:n {<skipexpr>}</code> |
| <code>\skip_if_finite:nTF</code> ★ | <code>\skip_if_finite:nTF {<skipexpr>} {<true code>} {<false code>}</code> |

New: 2012-03-05

Evaluates the *<skip expression>* as described for `\skip_eval:n`, and then tests if all of its components are finite.

13 Using skip expressions and variables

| | |
|-----------------------------|---|
| <code>\skip_eval:n</code> ★ | <code>\skip_eval:n {<skip expression>}</code> |
|-----------------------------|---|

Updated: 2011-10-22

Evaluates the *<skip expression>*, expanding any skips and token list variables within the *<expression>* to their content (without requiring `\skip_use:N/\tl_use:N`) and applying the standard mathematical rules. The result of the calculation is left in the input stream as a *<glue denotation>* after two expansions. This will be expressed in points (`\pt`), and will require suitable termination if used in a T_EX-style assignment as it is *not* an *<internal glue>*.

| | |
|----------------------------|---------------------------------------|
| <code>\skip_use:N</code> ★ | <code>\skip_use:N <skip></code> |
| <code>\skip_use:c</code> ★ | |

Recovers the content of a *<skip>* and places it directly in the input stream. An error will be raised if the variable does not exist or if it is invalid. Can be omitted in places where a *<dimension>* is required (such as in the argument of `\skip_eval:n`).

T_EXhackers note: `\skip_use:N` is the T_EX primitive `\the`; this is one of several L^AT_EX3 names for this primitive.

14 Viewing skip variables

| | |
|---------------------------|--|
| <code>\skip_show:N</code> | <code>\skip_show:N <skip></code> |
|---------------------------|--|

`\skip_show:c`

Updated: 2015-08-03

Displays the value of the *<skip>* on the terminal.

| | |
|--|--|
| <hr/> <code>\skip_show:n</code> <hr/> | <code>\skip_show:n {\langle skip expression \rangle}</code> |
| New: 2011-11-22 Updated: 2015-08-07 | Displays the result of evaluating the $\langle skip expression \rangle$ on the terminal. |

| | |
|--|---|
| <hr/> <code>\skip_log:N</code> <code>\skip_log:c</code> <hr/> | <code>\skip_log:N \langle skip \rangle</code> |
| New: 2014-08-22 Updated: 2015-08-03 | Writes the value of the $\langle skip \rangle$ in the log file. |

| | |
|--|--|
| <hr/> <code>\skip_log:n</code> <hr/> | <code>\skip_log:n {\langle skip expression \rangle}</code> |
| New: 2014-08-22 Updated: 2015-08-07 | Writes the result of evaluating the $\langle skip expression \rangle$ in the log file. |

15 Constant skips

| | |
|--------------------------------------|--|
| <hr/> <code>\c_max_skip</code> <hr/> | The maximum value that can be stored as a skip (equal to <code>\c_max_dim</code> in length), with no stretch nor shrink component. |
| Updated: 2012-11-02 | |

| | |
|---------------------------------------|--|
| <hr/> <code>\c_zero_skip</code> <hr/> | A zero length as a skip, with no stretch nor shrink component. |
| Updated: 2012-11-01 | |

16 Scratch skips

| | |
|--|--|
| <hr/> <code>\l_tmpa_skip</code> <code>\l_tmpb_skip</code> <hr/> | Scratch skip for local assignment. These are never used by the kernel code, and so are safe for use with any L ^A T _E X3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage. |
|--|--|

| | |
|--|---|
| <hr/> <code>\g_tmpa_skip</code> <code>\g_tmpb_skip</code> <hr/> | Scratch skip for global assignment. These are never used by the kernel code, and so are safe for use with any L ^A T _E X3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage. |
|--|---|

17 Inserting skips into the output

| | |
|---|--|
| <hr/> <code>\skip_horizontal:N</code> <code>\skip_horizontal:c</code> <code>\skip_horizontal:n</code> <hr/> | <code>\skip_horizontal:N \langle skip \rangle</code> <code>\skip_horizontal:n {\langle skipexpr \rangle}</code> |
| Updated: 2011-10-22 | Inserts a horizontal $\langle skip \rangle$ into the current list. |
| T_EXhackers note: <code>\skip_horizontal:N</code> is the T _E X primitive <code>\hskip</code> renamed. | |

| | |
|-------------------------------|--|
| <code>\skip_vertical:N</code> | <code>\skip_vertical:N <skip></code> |
| <code>\skip_vertical:c</code> | <code>\skip_vertical:n {<skipexpr>}</code> |
| <code>\skip_vertical:n</code> | |

Inserts a vertical $\langle skip \rangle$ into the current list.

Updated: 2011-10-22

T_EXhackers note: `\skip_vertical:N` is the T_EX primitive `\vskip` renamed.

18 Creating and initialising muskip variables

| | |
|----------------------------|---|
| <code>\muskip_new:N</code> | <code>\muskip_new:N <muskip></code> |
| <code>\muskip_new:c</code> | |

Creates a new $\langle muskip \rangle$ or raises an error if the name is already taken. The declaration is global. The $\langle muskip \rangle$ will initially be equal to 0 mu.

| | |
|-------------------------------|--|
| <code>\muskip_const:Nn</code> | <code>\muskip_const:Nn <muskip> {<muskip expression>}</code> |
| <code>\muskip_const:cn</code> | |

Creates a new constant $\langle muskip \rangle$ or raises an error if the name is already taken. The value of the $\langle muskip \rangle$ will be set globally to the $\langle muskip expression \rangle$.

New: 2012-03-05

| | |
|------------------------------|--|
| <code>\muskip_zero:N</code> | <code>\skip_zero:N <muskip></code> |
| <code>\muskip_zero:c</code> | |
| <code>\muskip_gzero:N</code> | |
| <code>\muskip_gzero:c</code> | |

Sets $\langle muskip \rangle$ to 0 mu.

| | |
|----------------------------------|--|
| <code>\muskip_zero_new:N</code> | <code>\muskip_zero_new:N <muskip></code> |
| <code>\muskip_zero_new:c</code> | |
| <code>\muskip_gzero_new:N</code> | |
| <code>\muskip_gzero_new:c</code> | |

Ensures that the $\langle muskip \rangle$ exists globally by applying `\muskip_new:N` if necessary, then applies `\muskip_(g)zero:N` to leave the $\langle muskip \rangle$ set to zero.

New: 2012-01-07

| | |
|-------------------------------------|---|
| <code>\muskip_if_exist_p:N</code> ★ | <code>\muskip_if_exist_p:N <muskip></code> |
| <code>\muskip_if_exist_p:c</code> ★ | <code>\muskip_if_exist:NTF <muskip> {<true code>} {<false code>}</code> |
| <code>\muskip_if_exist:NTF</code> ★ | |
| <code>\muskip_if_exist:cTF</code> ★ | |

Tests whether the $\langle muskip \rangle$ is currently defined. This does not check that the $\langle muskip \rangle$ really is a muskip variable.

New: 2012-03-03

19 Setting muskip variables

| | |
|------------------------------|--|
| <code>\muskip_add:Nn</code> | <code>\muskip_add:Nn <muskip> {<muskip expression>}</code> |
| <code>\muskip_add:cn</code> | |
| <code>\muskip_gadd:Nn</code> | |
| <code>\muskip_gadd:cn</code> | |

Adds the result of the $\langle muskip expression \rangle$ to the current content of the $\langle muskip \rangle$.

Updated: 2011-10-22

| | |
|------------------------------|--|
| <code>\muskip_set:Nn</code> | <code>\muskip_set:Nn <muskip> {<muskip expression>}</code> |
| <code>\muskip_set:cn</code> | Sets <i><muskip></i> to the value of <i><muskip expression></i> , which must evaluate to a math length with units and may include a rubber component (for example 1 mu plus 0.5 mu). |
| <code>\muskip_gset:Nn</code> | |
| <code>\muskip_gset:cn</code> | |
| Updated: 2011-10-22 | |

| | |
|---|--|
| <code>\muskip_set_eq:NN</code> | <code>\muskip_set_eq:NN <muskip₁> <muskip₂></code> |
| <code>\muskip_set_eq:(cN Nc cc)</code> | Sets the content of <i><muskip₁></i> equal to that of <i><muskip₂></i> . |
| <code>\muskip_gset_eq:NN</code> | |
| <code>\muskip_gset_eq:(cN Nc cc)</code> | |

| | |
|------------------------------|--|
| <code>\muskip_sub:Nn</code> | <code>\muskip_sub:Nn <muskip> {<muskip expression>}</code> |
| <code>\muskip_sub:cn</code> | Subtracts the result of the <i><muskip expression></i> from the current content of the <i><skip></i> . |
| <code>\muskip_gsub:Nn</code> | |
| <code>\muskip_gsub:cn</code> | |
| Updated: 2011-10-22 | |

20 Using muskip expressions and variables

| | |
|-------------------------------|--|
| <code>\muskip_eval:n</code> ★ | <code>\muskip_eval:n {<muskip expression>}</code> |
| Updated: 2011-10-22 | Evaluates the <i><muskip expression></i> , expanding any skips and token list variables within the <i><expression></i> to their content (without requiring <code>\muskip_use:N/\tl_use:N</code>) and applying the standard mathematical rules. The result of the calculation is left in the input stream as a <i><mu glue denotation></i> after two expansions. This will be expressed in mu, and will require suitable termination if used in a T _E X-style assignment as it is <i>not</i> an <i><internal mu glue></i> . |

| | |
|------------------------------|--|
| <code>\muskip_use:N</code> ★ | <code>\muskip_use:N <muskip></code> |
| <code>\muskip_use:c</code> ★ | Recovers the content of a <i><skip></i> and places it directly in the input stream. An error will be raised if the variable does not exist or if it is invalid. Can be omitted in places where a <i><dimension></i> is required (such as in the argument of <code>\muskip_eval:n</code>). |

T_EXhackers note: `\muskip_use:N` is the T_EX primitive `\the`: this is one of several L^AT_EX3 names for this primitive.

21 Viewing muskip variables

| | |
|-----------------------------|--|
| <code>\muskip_show:N</code> | <code>\muskip_show:N <muskip></code> |
| <code>\muskip_show:c</code> | Displays the value of the <i><muskip></i> on the terminal. |
| Updated: 2015-08-03 | |

| | |
|-----------------------------|---|
| <code>\muskip_show:n</code> | <code>\muskip_show:n {<muskip expression>}</code> |
| New: 2011-11-22 | Displays the result of evaluating the <i><muskip expression></i> on the terminal. |
| Updated: 2015-08-07 | |

| | |
|----------------------------|--|
| <code>\muskip_log:N</code> | <code>\muskip_log:N <muskip></code> |
| <code>\muskip_log:c</code> | Writes the value of the <code><muskip></code> in the log file. |

New: 2014-08-22
Updated: 2015-08-03

| | |
|----------------------------|---|
| <code>\muskip_log:n</code> | <code>\muskip_log:n {<muskip expression>}</code> |
| | Writes the result of evaluating the <code><muskip expression></code> in the log file. |

New: 2014-08-22
Updated: 2015-08-07

22 Constant muskips

| | |
|----------------------------|---|
| <code>\c_max_muskip</code> | The maximum value that can be stored as a muskip, with no stretch nor shrink component. |
|----------------------------|---|

| | |
|-----------------------------|--|
| <code>\c_zero_muskip</code> | A zero length as a muskip, with no stretch nor shrink component. |
|-----------------------------|--|

23 Scratch muskips

| | |
|--|--|
| <code>\l_tmpa_muskip</code> <code>\l_tmpb_muskip</code> | Scratch muskip for local assignment. These are never used by the kernel code, and so are safe for use with any L ^A T _E X3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage. |
|--|--|

| | |
|--|---|
| <code>\g_tmpa_muskip</code> <code>\g_tmpb_muskip</code> | Scratch muskip for global assignment. These are never used by the kernel code, and so are safe for use with any L ^A T _E X3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage. |
|--|---|

24 Primitive conditional

| | |
|------------------------|---|
| <code>\if_dim:w</code> | <code>\if_dim:w <dimen_{12 <code> <true code></code> <code>\else:</code> <code> <false></code> <code>\fi:</code>}</code> |
|------------------------|---|

Compare two dimensions. The `<relation>` is one of `<`, `=` or `>` with category code 12.

T_EXhackers note: This is the T_EX primitive `\ifdim`.

25 Internal functions

| | |
|---|---|
| <hr/> | |
| <code>_dim_eval:w</code> | ★ |
| <code>_dim_eval_end:</code> | ★ |
| <hr/> | |
| Evaluates $\langle dimension\ expression \rangle$ as described for <code>\dim_eval:n</code> . The evaluation stops when an unexpandable token which is not a valid part of a dimension is read or when <code>_dim_eval_end:</code> is reached. The latter is gobbled by the scanner mechanism: <code>_dim_eval_end:</code> itself is unexpandable but used correctly the entire construct is expandable. | |

TeXhackers note: This is the ε -TeX primitive `\dimexpr`.

Part XIX

The l3keys package

Key–value interfaces

The key–value method is a popular system for creating large numbers of settings for controlling function or package behaviour. The system normally results in input of the form

```
\MyModuleSetup{
  key-one = value one,
  key-two = value two
}
```

or

```
\MyModuleMacro[
  key-one = value one,
  key-two = value two
]{argument}
```

for the user.

The high level functions here are intended as a method to create key–value controls. Keys are themselves created using a key–value interface, minimising the number of functions and arguments required. Each key is created by setting one or more *properties* of the key:

```
\keys_define:nn { mymodule }
{
  key-one .code:n    = code including parameter #1,
  key-two .tl_set:N = \l_mymodule_store_tl
}
```

These values can then be set as with other key–value approaches:

```
\keys_set:nn { mymodule }
{
  key-one = value one,
  key-two = value two
}
```

At a document level, `\keys_set:nn` will be used within a document function, for example

```
\DeclareDocumentCommand \MyModuleSetup { m }
{ \keys_set:nn { mymodule } { #1 } }
\DeclareDocumentCommand \MyModuleMacro { o m }
{
  \group_begin:
    \keys_set:nn { mymodule } { #1 }
    % Main code for \MyModuleMacro
  \group_end:
}
```

Key names may contain any tokens, as they are handled internally using `\tl_to_str:n`; spaces are *ignored* in key names. As will be discussed in section 2, it is suggested that the character `/` is reserved for sub-division of keys into logical groups. Functions and variables are *not* expanded when creating key names, and so

```
\tl_set:Nn \l_mymodule_tmp_tl { key }
\keys_define:nn { mymodule }
{
  \l_mymodule_tmp_tl .code:n = code
}
```

will create a key called `\l_mymodule_tmp_tl`, and not one called `key`.

1 Creating keys

`\keys_define:nn`

Updated: 2015-11-07

`\keys_define:nn {<module>} {<keyval list>}`

Parses the *<keyval list>* and defines the keys listed there for *<module>*. The *<module>* name should be a text value, but there are no restrictions on the nature of the text. In practice the *<module>* should be chosen to be unique to the module in question (unless deliberately adding keys to an existing module).

The *<keyval list>* should consist of one or more key names along with an associated key *property*. The properties of a key determine how it acts. The individual properties are described in the following text; a typical use of `\keys_define:nn` might read

```
\keys_define:nn { mymodule }
{
  keyname .code:n = Some-code~using~#1,
  keyname .value_required:n = true
}
```

where the properties of the key begin from the `.` after the key name.

The various properties available take either no arguments at all, or require one or more arguments. This is indicated in the name of the property using an argument specification. In the following discussion, each property is illustrated attached to an arbitrary *<key>*, which when used may be supplied with a *<value>*. All key *definitions* are local.

Key properties are applied in the reading order and so the ordering is significant. Key properties which define “actions”, such as `.code:n`, `.tl_set:N`, *etc.*, will override one another. Some other properties are mutually exclusive, notably `.value_required:n` and `.value_forbidden:n`, and so will replace one another. However, properties covering non-exclusive behaviours may be given in any order. Thus for example the following definitions are equivalent.

```
\keys_define:nn { mymodule }
{
  keyname .code:n          = Some-code~using~#1,
  keyname .value_required:n = true
}
\keys_define:nn { mymodule }
```

```

{
  keyname .value_required:n = true,
  keyname .code:n           = Some~code~using~#1
}

```

Note that with the exception of the special `.undefine:` property, all key properties will define the key within the current T_EX scope.

```

.bool_set:N
.bool_set:c
.bool_gset:N
.bool_gset:c

```

Updated: 2013-07-08

$\langle key \rangle$.bool_set:N = $\langle boolean \rangle$

Defines $\langle key \rangle$ to set $\langle boolean \rangle$ to $\langle value \rangle$ (which must be either `true` or `false`). If the variable does not exist, it will be created globally at the point that the key is set up.

```

.bool_set_inverse:N
.bool_set_inverse:c
.bool_gset_inverse:N
.bool_gset_inverse:c

```

New: 2011-08-28

Updated: 2013-07-08

$\langle key \rangle$.bool_set_inverse:N = $\langle boolean \rangle$

Defines $\langle key \rangle$ to set $\langle boolean \rangle$ to the logical inverse of $\langle value \rangle$ (which must be either `true` or `false`). If the $\langle boolean \rangle$ does not exist, it will be created globally at the point that the key is set up.

```

.choice:

```

$\langle key \rangle$.choice:

Sets $\langle key \rangle$ to act as a choice key. Each valid choice for $\langle key \rangle$ must then be created, as discussed in section 3.

```

.choices:nn
.choices:(Vn|on|xn)

```

New: 2011-08-21

Updated: 2013-07-10

$\langle key \rangle$.choices:nn = $\{\langle choices \rangle\}$ $\{\langle code \rangle\}$

Sets $\langle key \rangle$ to act as a choice key, and defines a series $\langle choices \rangle$ which are implemented using the $\langle code \rangle$. Inside $\langle code \rangle$, `\l_keys_choice_tl` will be the name of the choice made, and `\l_keys_choice_int` will be the position of the choice in the list of $\langle choices \rangle$ (indexed from 1). Choices are discussed in detail in section 3.

```

.clist_set:N
.clist_set:c
.clist_gset:N
.clist_gset:c

```

New: 2011-09-11

$\langle key \rangle$.clist_set:N = $\langle comma list variable \rangle$

Defines $\langle key \rangle$ to set $\langle comma list variable \rangle$ to $\langle value \rangle$. Spaces around commas and empty items will be stripped. If the variable does not exist, it will be created globally at the point that the key is set up.

```

.code:n

```

Updated: 2013-07-10

$\langle key \rangle$.code:n = $\{\langle code \rangle\}$

Stores the $\langle code \rangle$ for execution when $\langle key \rangle$ is used. The $\langle code \rangle$ can include one parameter (#1), which will be the $\langle value \rangle$ given for the $\langle key \rangle$. The x-type variant will expand $\langle code \rangle$ at the point where the $\langle key \rangle$ is created.

`.default:n`
`.default:(V|o|x)`
Updated: 2013-07-09

$\langle key \rangle$ `.default:n = { $\langle default \rangle$ }`

Creates a $\langle default \rangle$ value for $\langle key \rangle$, which is used if no value is given. This will be used if only the key name is given, but not if a blank $\langle value \rangle$ is given:

```
\keys_define:nn { mymodule }
{
  key .code:n      = Hello~#1,
  key .default:n = World
}
\keys_set:nn { mymodule }
{
  key = Fred, % Prints 'Hello Fred'
  key,      % Prints 'Hello World'
  key = ,    % Prints 'Hello '
}
```

The default does not affect keys where values are required or forbidden. Thus a required value cannot be supplied by a default value, and giving a default value for a key which cannot take a value will not trigger an error.

`.dim_set:N`
`.dim_set:c`
`.dim_gset:N`
`.dim_gset:c`

$\langle key \rangle$ `.dim_set:N = $\langle dimension \rangle$`

Defines $\langle key \rangle$ to set $\langle dimension \rangle$ to $\langle value \rangle$ (which must a dimension expression). If the variable does not exist, it will be created globally at the point that the key is set up.

`.fp_set:N`
`.fp_set:c`
`.fp_gset:N`
`.fp_gset:c`

$\langle key \rangle$ `.fp_set:N = $\langle floating point \rangle$`

Defines $\langle key \rangle$ to set $\langle floating point \rangle$ to $\langle value \rangle$ (which must a floating point expression). If the variable does not exist, it will be created globally at the point that the key is set up.

`.groups:n`
New: 2013-07-14

$\langle key \rangle$ `.groups:n = { $\langle groups \rangle$ }`

Defines $\langle key \rangle$ as belonging to the $\langle groups \rangle$ declared. Groups provide a “secondary axis” for selectively setting keys, and are described in Section 6.

`.inherit:n`
New: 2016-11-22

$\langle key \rangle$ `.inherit:n = { $\langle parents \rangle$ }`

Specifies that the $\langle key \rangle$ path should inherit the keys listed as $\langle parents \rangle$. For example, with setting

```
\keys_define:n { foo } { test .code:n = \tl_show:n {#1} }
\keys_define:n { } { bar .inherit:n = foo }
```

setting

```
\keys_set:n { bar } { test = a }
```

will be equivalent to

```
\keys_set:n { foo } { test = a }
```

| | |
|---|--|
| <hr/> <code>.initial:n</code> <hr/> | <code><key> .initial:n = {<value>}</code> |
| <code>.initial:(V o x)</code> | Initialises the <code><key></code> with the <code><value></code> , equivalent to |
| <hr/> Updated: 2013-07-09 <hr/> | <code>\keys_set:nn {<module>} { <key> = <value> }</code> |
| <hr/> <code>.int_set:N</code> <hr/> | <code><key> .int_set:N = <integer></code> |
| <code>.int_set:c</code> | Defines <code><key></code> to set <code><integer></code> to <code><value></code> (which must be an integer expression). If the |
| <code>.int_gset:N</code> | variable does not exist, it will be created globally at the point that the key is set up. |
| <hr/> <code>.int_gset:c</code> <hr/> | |
| <hr/> <code>.meta:n</code> <hr/> | <code><key> .meta:n = {<keyval list>}</code> |
| <hr/> Updated: 2013-07-10 <hr/> | Makes <code><key></code> a meta-key, which will set <code><keyval list></code> in one go. If <code><key></code> is given with a |
| | value at the time the key is used, then the value will be passed through to the subsidiary |
| | <code><keys></code> for processing (as #1). |
| <hr/> <code>.meta:nn</code> <hr/> | <code><key> .meta:nn = {<path>} {<keyval list>}</code> |
| <hr/> New: 2013-07-10 <hr/> | Makes <code><key></code> a meta-key, which will set <code><keyval list></code> in one go using the <code><path></code> in place of |
| | the current one. If <code><key></code> is given with a value at the time the key is used, then the value |
| | will be passed through to the subsidiary <code><keys></code> for processing (as #1). |
| <hr/> <code>.multichoice:</code> <hr/> | <code><key> .multichoice:</code> |
| <hr/> New: 2011-08-21 <hr/> | Sets <code><key></code> to act as a multiple choice key. Each valid choice for <code><key></code> must then be |
| | created, as discussed in section 3. |
| <hr/> <code>.multichoices:nn</code> <hr/> | <code><key> .multichoices:nn {<choices>} {<code>}</code> |
| <code>.multichoices:(Vn on xn)</code> | Sets <code><key></code> to act as a multiple choice key, and defines a series <code><choices></code> which are im- |
| <hr/> New: 2011-08-21 <hr/> | plemented using the <code><code></code> . Inside <code><code></code> , <code>\l_keys_choice_tl</code> will be the name of the |
| <hr/> Updated: 2013-07-10 <hr/> | choice made, and <code>\l_keys_choice_int</code> will be the position of the choice in the list of |
| | <code><choices></code> (indexed from 1). Choices are discussed in detail in section 3. |
| <hr/> <code>.skip_set:N</code> <hr/> | <code><key> .skip_set:N = <skip></code> |
| <code>.skip_set:c</code> | Defines <code><key></code> to set <code><skip></code> to <code><value></code> (which must be a skip expression). If the variable |
| <code>.skip_gset:N</code> | does not exist, it will be created globally at the point that the key is set up. |
| <hr/> <code>.skip_gset:c</code> <hr/> | |
| <hr/> <code>.tl_set:N</code> <hr/> | <code><key> .tl_set:N = <token list variable></code> |
| <code>.tl_set:c</code> | Defines <code><key></code> to set <code><token list variable></code> to <code><value></code> . If the variable does not exist, it will |
| <code>.tl_gset:N</code> | be created globally at the point that the key is set up. |
| <hr/> <code>.tl_gset:c</code> <hr/> | |
| <hr/> <code>.tl_set_x:N</code> <hr/> | <code><key> .tl_set_x:N = <token list variable></code> |
| <code>.tl_set_x:c</code> | Defines <code><key></code> to set <code><token list variable></code> to <code><value></code> , which will be subjected to an x- |
| <code>.tl_gset_x:N</code> | type expansion (<i>i.e.</i> using <code>\tl_set:Nx</code>). If the variable does not exist, it will be created |
| <hr/> <code>.tl_gset_x:c</code> <hr/> | globally at the point that the key is set up. |

| | |
|-------------------------|-------------------------------------|
| <code>.undefine:</code> | <code><key> .undefine:</code> |
|-------------------------|-------------------------------------|

| | |
|-----------------|--|
| New: 2015-07-14 | Removes the definition of the <code><key></code> within the current scope. |
|-----------------|--|

| | |
|---------------------------------|--|
| <code>.value_forbidden:n</code> | <code><key> .value_forbidden:n = true false</code> |
|---------------------------------|--|

| | |
|-----------------|--|
| New: 2015-07-14 | Specifies that <code><key></code> cannot receive a <code><value></code> when used. If a <code><value></code> is given then an error will be issued. Setting the property <code>false</code> will cancel the restriction. |
|-----------------|--|

| | |
|--------------------------------|---|
| <code>.value_required:n</code> | <code><key> .value_required:n = true false</code> |
|--------------------------------|---|

| | |
|-----------------|--|
| New: 2015-07-14 | Specifies that <code><key></code> must receive a <code><value></code> when used. If a <code><value></code> is not given then an error will be issued. Setting the property <code>false</code> will cancel the restriction. |
|-----------------|--|

2 Sub-dividing keys

When creating large numbers of keys, it may be desirable to divide them into several sub-groups for a given module. This can be achieved either by adding a sub-division to the module name:

```
\keys_define:nn { module / subgroup }
{ key .code:n = code }
```

or to the key name:

```
\keys_define:nn { mymodule }
{ subgroup / key .code:n = code }
```

As illustrated, the best choice of token for sub-dividing keys in this way is `/`. This is because of the method that is used to represent keys internally. Both of the above code fragments set the same key, which has full name `module/subgroup/key`.

As will be illustrated in the next section, this subdivision is particularly relevant to making multiple choices.

3 Choice and multiple choice keys

The `l3keys` system supports two types of choice key, in which a series of pre-defined input values are linked to varying implementations. Choice keys are usually created so that the various values are mutually-exclusive: only one can apply at any one time. “Multiple” choice keys are also supported: these allow a selection of values to be chosen at the same time.

Mutually-exclusive choices are created by setting the `.choice:` property:

```
\keys_define:nn { mymodule }
{ key .choice: }
```

For keys which are set up as choices, the valid choices are generated by creating sub-keys of the choice key. This can be carried out in two ways.

In many cases, choices execute similar code which is dependant only on the name of the choice or the position of the choice in the list of all possibilities. Here, the keys can share the same code, and can be rapidly created using the `.choices:nn` property.

```

\keys_define:nn { mymodule }
{
  key .choices:nn =
    { choice-a, choice-b, choice-c }
    {
      You~gave~choice~'\tl_use:N \l_keys_choice_tl',~
      which~is~in~position~\int_use:N \l_keys_choice_int \c_space_tl
      in~the~list.
    }
}

```

The index `\l_keys_choice_int` in the list of choices starts at 1.

`\l_keys_choice_int`
`\l_keys_choice_tl`

Inside the code block for a choice generated using `.choices:nn`, the variables `\l_keys_choice_tl` and `\l_keys_choice_int` are available to indicate the name of the current choice, and its position in the comma list. The position is indexed from 1. Note that, as with standard key code generated using `.code:n`, the value passed to the key (i.e. the choice name) is also available as `#1`.

On the other hand, it is sometimes useful to create choices which use entirely different code from one another. This can be achieved by setting the `.choice:` property of a key, then manually defining sub-keys.

```

\keys_define:nn { mymodule }
{
  key .choice:,
  key / choice-a .code:n = code-a,
  key / choice-b .code:n = code-b,
  key / choice-c .code:n = code-c,
}

```

It is possible to mix the two methods, but manually-created choices should *not* use `\l_keys_choice_tl` or `\l_keys_choice_int`. These variables do not have defined behaviour when used outside of code created using `.choices:nn` (i.e. anything might happen).

It is possible to allow choice keys to take values which have not previously been defined by adding code for the special `unknown` choice. The general behavior of the `unknown` key is described in Section 5. A typical example in the case of a choice would be to issue a custom error message:

```

\keys_define:nn { mymodule }
{
  key .choice:,
  key / choice-a .code:n = code-a,
  key / choice-b .code:n = code-b,
  key / choice-c .code:n = code-c,
  key / unknown .code:n =
    \msg_error:nnxxx { mymodule } { unknown-choice }
    { key } % Name of choice key
    { choice-a , choice-b , choice-c } % Valid choices
    { \exp_not:n {#1} } % Invalid choice given
}

```

```
%
%
}
```

Multiple choices are created in a very similar manner to mutually-exclusive choices, using the properties `.multichoice:` and `.multichoices:nn`. As with mutually exclusive choices, multiple choices are define as sub-keys. Thus both

```
\keys_define:nn { mymodule }
{
  key .multichoices:nn =
    { choice-a, choice-b, choice-c }
    {
      You~gave~choice~'\tl_use:N \l_keys_choice_tl',~
      which~is~in~position~
      \int_use:N \l_keys_choice_int \c_space_tl
      in~the~list.
    }
}
```

and

```
\keys_define:nn { mymodule }
{
  key .multichoice:,
  key / choice-a .code:n = code-a,
  key / choice-b .code:n = code-b,
  key / choice-c .code:n = code-c,
}
```

are valid.

When a multiple choice key is set

```
\keys_set:nn { mymodule }
{
  key = { a , b , c } % 'key' defined as a multiple choice
}
```

each choice is applied in turn, equivalent to a `clist` mapping or to applying each value individually:

```
\keys_set:nn { mymodule }
{
  key = a ,
  key = b ,
  key = c ,
}
```

Thus each separate choice will have passed to it the `\l_keys_choice_tl` and `\l_keys_choice_int` in exactly the same way as described for `.choices:nn`.

4 Setting keys

```
\keys_set:nn  
\keys_set:(nV|nv|no)
```

Updated: 2015-11-07

```
\keys_set:nn {<module>} {<keyval list>}
```

Parses the *<keyval list>*, and sets those keys which are defined for *<module>*. The behaviour on finding an unknown key can be set by defining a special **unknown** key: this will be illustrated later.

```
\l_keys_key_tl  
\l_keys_path_tl  
\l_keys_value_tl
```

Updated: 2015-07-14

For each key processed, information of the full *path* of the key, the *name* of the key and the *value* of the key is available within three token list variables. These may be used within the code of the key.

The *value* is everything after the =, which may be empty if no value was given. This is stored in `\l_keys_value_tl`, and is not processed in any way by `\keys_set:nn`.

The *path* of the key is a “full” description of the key, and is unique for each key. It consists of the module and full key name, thus for example

```
\keys_set:nn { mymodule } { key-a = some-value }
```

has path `mymodule/key-a` while

```
\keys_set:nn { mymodule } { subset / key-a = some-value }
```

has path `mymodule/subset/key-a`. This information is stored in `\l_keys_path_tl`, and will have been processed by `\tl_to_str:n`.

The *name* of the key is the part of the path after the last /, and thus is not unique. In the preceding examples, both keys have name `key-a` despite having different paths. This information is stored in `\l_keys_key_tl`, and will have been processed by `\tl_to_str:n`.

5 Handling of unknown keys

If a key has not previously been defined (is unknown), `\keys_set:nn` will look for a special **unknown** key for the same module, and if this is not defined raises an error indicating that the key name was unknown. This mechanism can be used for example to issue custom error texts.

```
\keys_define:nn { mymodule }  
{  
  unknown .code:n =  
    You~tried~to~set~key~'\l_keys_key_tl'~to~'#1'.  
}
```

```

\keys_set_known:nnN      \keys_set_known:nnN {<module>} {<keyval list>} {<tl>}
\keys_set_known:(nVN|nvN|noN)
\keys_set_known:nn
\keys_set_known:(nV|nv|no)

```

New: 2011-08-23
Updated: 2015-11-07

In some cases, the desired behavior is to simply ignore unknown keys, collecting up information on these for later processing. The `\keys_set_known:nnN` function parses the `<keyval list>`, and sets those keys which are defined for `<module>`. Any keys which are unknown are not processed further by the parser. The key-value pairs for each *unknown* key name will be stored in the `<tl>` in a comma-separated form (*i.e.* an edited version of the `<keyval list>`). The `\keys_set_known:nn` version skips this stage.

Use of `\keys_set_known:nnN` can be nested, with the correct residual `<keyval list>` returned at each stage.

6 Selective key setting

In some cases it may be useful to be able to select only some keys for setting, even though these keys have the same path. For example, with a set of keys defined using

```

\keys define:nn { mymodule }
{
  key-one   .code:n   = { \my_func:n {#1} } ,
  key-two   .tl_set:N = \l_my_a_tl          ,
  key-three .tl_set:N = \l_my_b_tl          ,
  key-four  .fp_set:N = \l_my_a_fp          ,
}

```

the use of `\keys_set:nn` will attempt to set all four keys. However, in some contexts it may only be sensible to set some keys, or to control the order of setting. To do this, keys may be assigned to *groups*: arbitrary sets which are independent of the key tree. Thus modifying the example to read

```

\keys define:nn { mymodule }
{
  key-one   .code:n   = { \my_func:n {#1} } ,
  key-one   .groups:n = { first }           ,
  key-two   .tl_set:N = \l_my_a_tl          ,
  key-two   .groups:n = { first }           ,
  key-three .tl_set:N = \l_my_b_tl          ,
  key-three .groups:n = { second }          ,
  key-four  .fp_set:N = \l_my_a_fp          ,
}

```

will assign `key-one` and `key-two` to group `first`, `key-three` to group `second`, while `key-four` is not assigned to a group.

Selective key setting may be achieved either by selecting one or more groups to be made “active”, or by marking one or more groups to be ignored in key setting.

| | |
|--|---|
| <code>\keys_set_filter:nnnN</code> | <code>\keys_set_filter:nnnN {<module>} {<groups>} {<keyval list>} {<tl>}</code> |
| <code>\keys_set_filter:(nnVN nnvN nnoN)</code> | |
| <code>\keys_set_filter:nnn</code> | |
| <code>\keys_set_filter:(nnV nnv nno)</code> | |

New: 2013-07-14

Updated: 2015-11-07

Activates key filtering in an “opt-out” sense: keys assigned to any of the $\langle groups \rangle$ specified will be ignored. The $\langle groups \rangle$ are given as a comma-separated list. Unknown keys are not assigned to any group and will thus always be set. The key–value pairs for each key which is filtered out will be stored in the $\langle tl \rangle$ in a comma-separated form (*i.e.* an edited version of the $\langle keyval list \rangle$). The `\keys_set_filter:nnn` version skips this stage.

Use of `\keys_set_filter:nnnN` can be nested, with the correct residual $\langle keyval list \rangle$ returned at each stage.

| | |
|---|---|
| <code>\keys_set_groups:nnn</code> | <code>\keys_set_groups:nnn {<module>} {<groups>} {<keyval list>}</code> |
| <code>\keys_set_groups:(nnV nnv nno)</code> | |

New: 2013-07-14

Updated: 2015-11-07

Activates key filtering in an “opt-in” sense: only keys assigned to one or more of the $\langle groups \rangle$ specified will be set. The $\langle groups \rangle$ are given as a comma-separated list. Unknown keys are not assigned to any group and will thus never be set.

7 Utility functions for keys

| | |
|------------------------------------|--|
| <code>\keys_if_exist_p:nn</code> ★ | <code>\keys_if_exist_p:nn {<module>} {<key>}</code> |
| <code>\keys_if_exist:nnTF</code> ★ | <code>\keys_if_exist:nnTF {<module>} {<key>} {<true code>} {<false code>}</code> |

Updated: 2015-11-07 Tests if the $\langle key \rangle$ exists for $\langle module \rangle$, *i.e.* if any code has been defined for $\langle key \rangle$.

| | |
|--|---|
| <code>\keys_if_choice_exist_p:nnn</code> ★ | <code>\keys_if_choice_exist_p:nnn {<module>} {<key>} {<choice>}</code> |
| <code>\keys_if_choice_exist:nnnTF</code> ★ | <code>\keys_if_choice_exist:nnnTF {<module>} {<key>} {<choice>} {<true code>} {<false code>}</code> |

New: 2011-08-21

Updated: 2015-11-07

Tests if the $\langle choice \rangle$ is defined for the $\langle key \rangle$ within the $\langle module \rangle$, *i.e.* if any code has been defined for $\langle key \rangle / \langle choice \rangle$. The test is **false** if the $\langle key \rangle$ itself is not defined.

| | |
|----------------------------|---|
| <code>\keys_show:nn</code> | <code>\keys_show:nn {<module>} {<key>}</code> |
|----------------------------|---|

Updated: 2015-08-09

Displays in the terminal the information associated to the $\langle key \rangle$ for a $\langle module \rangle$, including the function which is used to actually implement it.

| | |
|---------------------------|--|
| <code>\keys_log:nn</code> | <code>\keys_log:nn {<module>} {<key>}</code> |
|---------------------------|--|

New: 2014-08-22

Updated: 2015-08-09

Writes in the log file the information associated to the $\langle key \rangle$ for a $\langle module \rangle$. See also `\keys_show:nn` which displays the result in the terminal.

8 Low-level interface for parsing key–val lists

To re-cap from earlier, a key–value list is input of the form

```
KeyOne = ValueOne ,  
KeyTwo = ValueTwo ,  
KeyThree
```

where each key–value pair is separated by a comma from the rest of the list, and each key–value pair does not necessarily contain an equals sign or a value! Processing this type of input correctly requires a number of careful steps, to correctly account for braces, spaces and the category codes of separators.

While the functions described earlier are used as a high-level interface for processing such input, in special circumstances you may wish to use a lower-level approach. The low-level parsing system converts a *key–value list* into *keys* and associated *values*. After the parsing phase is completed, the resulting keys and values (or keys alone) are available for further processing. This processing is not carried out by the low-level parser itself, and so the parser requires the names of two functions along with the key–value list. One function is needed to process key–value pairs (it receives two arguments), and a second function is required for keys given without any value (it is called with a single argument).

The parser does not double # tokens or expand any input. Active tokens = and , appearing at the outer level of braces are converted to category “other” (12) so that the parser does not “miss” any due to category code changes. Spaces are removed from the ends of the keys and values. Keys and values which are given in braces will have exactly one set removed (after space trimming), thus

```
key = {value here},
```

and

```
key = value here,
```

are treated identically.

\keyval_parse:NNn

Updated: 2011-09-08

\keyval_parse:NNn $\langle function_1 \rangle$ $\langle function_2 \rangle$ { $\langle key-value list \rangle$ }

Parses the $\langle key-value list \rangle$ into a series of $\langle keys \rangle$ and associated $\langle values \rangle$, or keys alone (if no $\langle value \rangle$ was given). $\langle function_1 \rangle$ should take one argument, while $\langle function_2 \rangle$ should absorb two arguments. After **\keyval_parse:NNn** has parsed the $\langle key-value list \rangle$, $\langle function_1 \rangle$ will be used to process keys given with no value and $\langle function_2 \rangle$ will be used to process keys given with a value. The order of the $\langle keys \rangle$ in the $\langle key-value list \rangle$ will be preserved. Thus

```
\keyval_parse:NNn \function:n \function:nn
{ key1 = value1 , key2 = value2, key3 = , key4 }
```

will be converted into an input stream

```
\function:nn { key1 } { value1 }
\function:nn { key2 } { value2 }
\function:nn { key3 } { }
\function:n { key4 }
```

Note that there is a difference between an empty value (an equals sign followed by nothing) and a missing value (no equals sign at all). Spaces are trimmed from the ends of the $\langle key \rangle$ and $\langle value \rangle$, then one *outer* set of braces is removed from the $\langle key \rangle$ and $\langle value \rangle$ as part of the processing.

Part XX

The l3fp package: floating points

A decimal floating point number is one which is stored as a significand and a separate exponent. The module implements expandably a wide set of arithmetic, trigonometric, and other operations on decimal floating point numbers, to be used within floating point expressions. Floating point expressions support the following operations with their usual precedence.

- Basic arithmetic: addition $x + y$, subtraction $x - y$, multiplication $x * y$, division x / y , square root \sqrt{x} , and parentheses.
- Comparison operators: $x < y$, $x <= y$, $x >? y$, $x != y$ etc.
- Boolean logic: negation $!x$, conjunction $x \&\& y$, disjunction $x || y$, ternary operator $x ? y : z$.
- Exponentials: $\exp x$, $\ln x$, x^y .
- Trigonometry: $\sin x$, $\cos x$, $\tan x$, $\cot x$, $\sec x$, $\csc x$ expecting their arguments in radians, and $\sind x$, $\cosd x$, $\tand x$, $\cotd x$, $\secd x$, $\cscd x$ expecting their arguments in degrees.
- Inverse trigonometric functions: $\asin x$, $\acos x$, $\atan x$, $\acot x$, $\asec x$, $\acsc x$ giving a result in radians, and $\asind x$, $\acosd x$, $\atand x$, $\acotd x$, $\asecd x$, $\acscd x$ giving a result in degrees.

(*not yet*) Hyperbolic functions and their inverse functions: $\sinh x$, $\cosh x$, $\tanh x$, $\coth x$, $\operatorname{sech} x$, $\operatorname{csch} x$, and $\operatorname{asinh} x$, $\operatorname{acosh} x$, $\operatorname{atanh} x$, $\operatorname{acoth} x$, $\operatorname{asech} x$, $\operatorname{acsch} x$.

- Extrema: $\max(x, y, \dots)$, $\min(x, y, \dots)$, $\operatorname{abs}(x)$.
- Rounding functions ($n = 0$ by default, $t = \operatorname{NaN}$ by default): $\operatorname{trunc}(x, n)$ rounds towards zero, $\operatorname{floor}(x, n)$ rounds towards $-\infty$, $\operatorname{ceil}(x, n)$ rounds towards $+\infty$, $\operatorname{round}(x, n, t)$ rounds to the closest value, with ties rounded to an even value by default, towards zero if $t = 0$, towards $+\infty$ if $t > 0$ and towards $-\infty$ if $t < 0$. And (*not yet*) modulo, and “quantize”.
- Random numbers: $\operatorname{rand}()$, $\operatorname{randint}(m, n)$ in pdfTeX and LuaTeX engines.
- Constants: `pi`, `deg` (one degree in radians).
- Dimensions, automatically expressed in points, *e.g.*, `pc` is 12.
- Automatic conversion (no need for `\langle type \rangle_use:N`) of integer, dimension, and skip variables to floating points, expressing dimensions in points and ignoring the stretch and shrink components of skips.

Floating point numbers can be given either explicitly (in a form such as `1.234e-34`, or `-.0001`), or as a stored floating point variable, which is automatically replaced by its current value. See section 9.1 for a description of what a floating point is, section 9.2 for details about how an expression is parsed, and section 9.3 to know what the various operations do. Some operations may raise exceptions (error messages), described in section 7.

An example of use could be the following.

`\LaTeX{}` can now compute: $\frac{\sin(3.5)}{2} + 2 \cdot 10^{-3}$
`= \ExplSyntaxOn \fp_to_decimal:n {sin 3.5 /2 + 2e-3} $.`

But in all fairness, this module is mostly meant as an underlying tool for higher-level commands. For example, one could provide a function to typeset nicely the result of floating point computations.

```
\documentclass{article}
\usepackage{xparse, siunitx}
\ExplSyntaxOn
\NewDocumentCommand { \calcnun } { m }
{ \num { \fp_to_scientific:n {#1} } }
\ExplSyntaxOff
\begin{document}
\calcnun { 2 pi * sin ( 2.3 ^ 5 ) }
\end{document}
```

1 Creating and initialising floating point variables

| | |
|------------------------------|---|
| <code>\fp_new:N</code> | <code>\fp_new:N <fp var></code> |
| <code>\fp_new:c</code> | Creates a new <i><fp var></i> or raises an error if the name is already taken. The declaration is global. The <i><fp var></i> will initially be +0. |
| Updated: 2012-05-08 | |
| <code>\fp_const:Nn</code> | <code>\fp_const:Nn <fp var> {<floating point expression>}</code> |
| <code>\fp_const:cn</code> | Creates a new constant <i><fp var></i> or raises an error if the name is already taken. The <i><fp var></i> will be set globally equal to the result of evaluating the <i><floating point expression></i> . |
| Updated: 2012-05-08 | |
| <code>\fp_zero:N</code> | <code>\fp_zero:N <fp var></code> |
| <code>\fp_zero:c</code> | Sets the <i><fp var></i> to +0. |
| <code>\fp_gzero:N</code> | |
| <code>\fp_gzero:c</code> | |
| Updated: 2012-05-08 | |
| <code>\fp_zero_new:N</code> | <code>\fp_zero_new:N <fp var></code> |
| <code>\fp_zero_new:c</code> | Ensures that the <i><fp var></i> exists globally by applying <code>\fp_new:N</code> if necessary, then applies <code>\fp_(g)zero:N</code> to leave the <i><fp var></i> set to +0. |
| <code>\fp_gzero_new:N</code> | |
| <code>\fp_gzero_new:c</code> | |
| Updated: 2012-05-08 | |

2 Setting floating point variables

| | |
|--------------------------|--|
| <code>\fp_set:Nn</code> | <code>\fp_set:Nn <fp var> {<floating point expression>}</code> |
| <code>\fp_set:cn</code> | Sets <i><fp var></i> equal to the result of computing the <i><floating point expression></i> . |
| <code>\fp_gset:Nn</code> | |
| <code>\fp_gset:cn</code> | |
| Updated: 2012-05-08 | |

| | |
|-------------------------------------|--|
| <code>\fp_set_eq:NN</code> | <code>\fp_set_eq:NN <fp var₁> <fp var₂></code> |
| <code>\fp_set_eq:(cN Nc cc)</code> | |
| <code>\fp_gset_eq:NN</code> | Sets the floating point variable $\langle fp\ var_1 \rangle$ equal to the current value of $\langle fp\ var_2 \rangle$. |
| <code>\fp_gset_eq:(cN Nc cc)</code> | |
| Updated: 2012-05-08 | |

| | |
|--------------------------|---|
| <code>\fp_add:Nn</code> | <code>\fp_add:Nn <fp var> {<floating point expression>}</code> |
| <code>\fp_add:cn</code> | |
| <code>\fp_gadd:Nn</code> | Adds the result of computing the $\langle floating\ point\ expression \rangle$ to the $\langle fp\ var \rangle$. |
| <code>\fp_gadd:cn</code> | |
| Updated: 2012-05-08 | |

| | |
|--------------------------|--|
| <code>\fp_sub:Nn</code> | <code>\fp_sub:Nn <fp var> {<floating point expression>}</code> |
| <code>\fp_sub:cn</code> | |
| <code>\fp_gsub:Nn</code> | Subtracts the result of computing the $\langle floating\ point\ expression \rangle$ from the $\langle fp\ var \rangle$. |
| <code>\fp_gsub:cn</code> | |
| Updated: 2012-05-08 | |

3 Using floating point numbers

| | |
|---------------------------|---|
| <code>\fp_eval:n</code> ★ | <code>\fp_eval:n {<floating point expression>}</code> |
| New: 2012-05-08 | |
| Updated: 2012-07-08 | Evaluates the $\langle floating\ point\ expression \rangle$ and expresses the result as a decimal number with no exponent. Leading or trailing zeros may be inserted to compensate for the exponent. Non-significant trailing zeros are trimmed, and integers are expressed without a decimal separator. The values $\pm\infty$ and NaN trigger an “invalid operation” exception. This function is identical to <code>\fp_to_decimal:n</code> . |

| | |
|---------------------------------|---|
| <code>\fp_to_decimal:N</code> ★ | <code>\fp_to_decimal:N <fp var></code> |
| <code>\fp_to_decimal:c</code> ★ | <code>\fp_to_decimal:n {<floating point expression>}</code> |
| <code>\fp_to_decimal:n</code> ★ | Evaluates the $\langle floating\ point\ expression \rangle$ and expresses the result as a decimal number with no exponent. Leading or trailing zeros may be inserted to compensate for the exponent. Non-significant trailing zeros are trimmed, and integers are expressed without a decimal separator. The values $\pm\infty$ and NaN trigger an “invalid operation” exception. |
| New: 2012-05-08 | |
| Updated: 2012-07-08 | |

| | |
|-----------------------------|--|
| <code>\fp_to_dim:N</code> ★ | <code>\fp_to_dim:N <fp var></code> |
| <code>\fp_to_dim:c</code> ★ | <code>\fp_to_dim:n {<floating point expression>}</code> |
| <code>\fp_to_dim:n</code> ★ | Evaluates the $\langle floating\ point\ expression \rangle$ and expresses the result as a dimension (in pt) suitable for use in dimension expressions. The output is identical to <code>\fp_to_decimal:n</code> , with an additional trailing pt (both letter tokens). In particular, the result may be outside the range $[-2^{14} + 2^{-17}, 2^{14} - 2^{-17}]$ of valid T _E X dimensions, leading to overflow errors if used as a dimension. The values $\pm\infty$ and NaN trigger an “invalid operation” exception. |
| Updated: 2016-03-22 | |

| | | | |
|---------------------------|---|---------------------------|--|
| <code>\fp_to_int:N</code> | ★ | <code>\fp_to_int:N</code> | $\langle fp\ var \rangle$ |
| <code>\fp_to_int:c</code> | ★ | <code>\fp_to_int:n</code> | $\{ \langle floating\ point\ expression \rangle \}$ |
| <code>\fp_to_int:n</code> | ★ | | Evaluates the $\langle floating\ point\ expression \rangle$, and rounds the result to the closest integer, rounding exact ties to an even integer. The result may be outside the range $[-2^{31} + 1, 2^{31} - 1]$ of valid TeX integers, leading to overflow errors if used in an integer expression. The values $\pm\infty$ and NaN trigger an “invalid operation” exception. |

Updated: 2012-07-08

| | | | |
|----------------------------------|---|----------------------------------|--|
| <code>\fp_to_scientific:N</code> | ★ | <code>\fp_to_scientific:N</code> | $\langle fp\ var \rangle$ |
| <code>\fp_to_scientific:c</code> | ★ | <code>\fp_to_scientific:n</code> | $\{ \langle floating\ point\ expression \rangle \}$ |
| <code>\fp_to_scientific:n</code> | ★ | | Evaluates the $\langle floating\ point\ expression \rangle$ and expresses the result in scientific notation: |

New: 2012-05-08
Updated: 2016-03-22

$\langle optional\ - \rangle \langle digit \rangle . \langle 15\ digits \rangle e \langle optional\ sign \rangle \langle exponent \rangle$

The leading $\langle digit \rangle$ is non-zero except in the case of ± 0 . The values $\pm\infty$ and NaN trigger an “invalid operation” exception. Normal category codes apply: thus the `e` is category code 11 (a letter).

| | | | |
|--------------------------|---|--------------------------|--|
| <code>\fp_to_tl:N</code> | ★ | <code>\fp_to_tl:N</code> | $\langle fp\ var \rangle$ |
| <code>\fp_to_tl:c</code> | ★ | <code>\fp_to_tl:n</code> | $\{ \langle floating\ point\ expression \rangle \}$ |
| <code>\fp_to_tl:n</code> | ★ | | Evaluates the $\langle floating\ point\ expression \rangle$ and expresses the result in (almost) the shortest possible form. Numbers in the ranges $(0, 10^{-3})$ and $[10^{16}, \infty)$ are expressed in scientific notation with trailing zeros trimmed and no decimal separator when there is a single significant digit (this differs from <code>\fp_to_scientific:n</code>). Numbers in the range $[10^{-3}, 10^{16})$ are expressed in a decimal notation without exponent, with trailing zeros trimmed, and no decimal separator for integer values (see <code>\fp_to_decimal:n</code>). Negative numbers start with <code>-</code> . The special values ± 0 , $\pm\infty$ and NaN are rendered as <code>0</code> , <code>-0</code> , <code>inf</code> , <code>-inf</code> , and <code>nan</code> respectively. Normal category codes apply and thus <code>inf</code> or <code>nan</code> , if produced, will be made up of letters. |

Updated: 2016-03-22

| | | | |
|------------------------|---|------------------------|---|
| <code>\fp_use:N</code> | ★ | <code>\fp_use:N</code> | $\langle fp\ var \rangle$ |
| <code>\fp_use:c</code> | ★ | | Inserts the value of the $\langle fp\ var \rangle$ into the input stream as a decimal number with no exponent. Leading or trailing zeros may be inserted to compensate for the exponent. Non-significant trailing zeros are trimmed. Integers are expressed without a decimal separator. The values $\pm\infty$ and NaN trigger an “invalid operation” exception. This function is identical to <code>\fp_to_decimal:N</code> . |

Updated: 2012-07-08

4 Floating point conditionals

| | | | |
|-------------------------------|---|-------------------------------|---|
| <code>\fp_if_exist_p:N</code> | ★ | <code>\fp_if_exist_p:N</code> | $\langle fp\ var \rangle$ |
| <code>\fp_if_exist_p:c</code> | ★ | <code>\fp_if_exist:NTF</code> | $\langle fp\ var \rangle \{ \langle true\ code \rangle \} \{ \langle false\ code \rangle \}$ |
| <code>\fp_if_exist:NTF</code> | ★ | | Tests whether the $\langle fp\ var \rangle$ is currently defined. This does not check that the $\langle fp\ var \rangle$ really is a floating point variable. |
| <code>\fp_if_exist:cTF</code> | ★ | | |

Updated: 2012-05-08

| | |
|--|---|
| <code>\fp_compare_p:nNn</code> ★ <code>\fp_compare:nNnTF</code> ★ | <code>\fp_compare_p:nNn {<fpexpr₁>} <relation> {<fpexpr₂>}</code> <code>\fp_compare:nNnTF {<fpexpr₁>} <relation> {<fpexpr₂>} {<true code>} {<false code>}</code> |
|--|---|

Updated: 2012-05-08

Compares the $\langle fpexpr_1 \rangle$ and the $\langle fpexpr_2 \rangle$, and returns **true** if the $\langle relation \rangle$ is obeyed. Two floating point numbers x and y may obey four mutually exclusive relations: $x \langle y, x=y, x \rangle y$, or x and y are not ordered. The latter case occurs exactly when one or both operands is NaN, and this relation is denoted by the symbol ?. Note that a NaN is distinct from any value, even another NaN, hence $x = x$ is not true for a NaN. To test if a value is NaN, compare it to an arbitrary number with the “not ordered” relation.

```

\fp_compare:nNnTF { <value> } ? { 0 }
{ } % <value> is nan
{ } % <value> is not nan

```

| | |
|--|---|
| <code>\fp_compare_p:n</code> ★ <code>\fp_compare:nTF</code> ★ | <code>\fp_compare_p:n</code> <code>{</code> <code> <fpexpr₁> <relation₁></code> <code> ...</code> <code> <fpexpr_N> <relation_N></code> <code> <fpexpr_{N+1}></code> <code>}</code> <code>\fp_compare:nTF</code> <code>{</code> <code> <fpexpr₁> <relation₁></code> <code> ...</code> <code> <fpexpr_N> <relation_N></code> <code> <fpexpr_{N+1}></code> <code>}</code> <code>{<true code>} {<false code>}</code> |
|--|---|

Updated: 2012-12-14

Evaluates the $\langle floating point expressions \rangle$ as described for `\fp_eval:n` and compares consecutive result using the corresponding $\langle relation \rangle$, namely it compares $\langle intexpr_1 \rangle$ and $\langle intexpr_2 \rangle$ using the $\langle relation_1 \rangle$, then $\langle intexpr_2 \rangle$ and $\langle intexpr_3 \rangle$ using the $\langle relation_2 \rangle$, until finally comparing $\langle intexpr_N \rangle$ and $\langle intexpr_{N+1} \rangle$ using the $\langle relation_N \rangle$. The test yields **true** if all comparisons are **true**. Each $\langle floating point expression \rangle$ is evaluated only once. Contrarily to `\int_compare:nTF`, all $\langle floating point expressions \rangle$ are computed, even if one comparison is **false**. Two floating point numbers x and y may obey four mutually exclusive relations: $x \langle y, x=y, x \rangle y$, or x and y are not ordered. The latter case occurs exactly when one or both operands is NaN, and this relation is denoted by the symbol ?. Each $\langle relation \rangle$ can be any (non-empty) combination of $<$, $=$, $>$, and $?$, plus an optional leading ! (which negates the $\langle relation \rangle$), with the restriction that the $\langle relation \rangle$ may not start with $?$, as this symbol has a different meaning (in combination with $:$) within floatin point expressions. The comparison $x \langle relation \rangle y$ is then **true** if the $\langle relation \rangle$ does not start with ! and the actual relation ($<$, $=$, $>$, or $?$) between x and y appears within the $\langle relation \rangle$, or on the contrary if the $\langle relation \rangle$ starts with ! and the relation between x and y does not appear within the $\langle relation \rangle$. Common choices of $\langle relation \rangle$ include \geq (greater or equal), \neq (not equal), $!?$ or \leq (comparable).

5 Floating point expression loops

| | |
|----------------------------------|--|
| <code>\fp_do_until:nNnn</code> ☆ | <code>\fp_do_until:nNnn {<fpexpr₁>} <relation> {<fpexpr₂>} {<code>}</code> |
| New: 2012-08-16 | Places the <i><code></i> in the input stream for T _E X to process, and then evaluates the relationship between the two <i><floating point expressions></i> as described for <code>\fp_compare:nNnTF</code> . If the test is false then the <i><code></i> will be inserted into the input stream again and a loop will occur until the <i><relation></i> is true . |
| <code>\fp_do_while:nNnn</code> ☆ | <code>\fp_do_while:nNnn {<fpexpr₁>} <relation> {<fpexpr₂>} {<code>}</code> |
| New: 2012-08-16 | Places the <i><code></i> in the input stream for T _E X to process, and then evaluates the relationship between the two <i><floating point expressions></i> as described for <code>\fp_compare:nNnTF</code> . If the test is true then the <i><code></i> will be inserted into the input stream again and a loop will occur until the <i><relation></i> is false . |
| <code>\fp_until_do:nNnn</code> ☆ | <code>\fp_until_do:nNnn {<fpexpr₁>} <relation> {<fpexpr₂>} {<code>}</code> |
| New: 2012-08-16 | Evaluates the relationship between the two <i><floating point expressions></i> as described for <code>\fp_compare:nNnTF</code> , and then places the <i><code></i> in the input stream if the <i><relation></i> is false . After the <i><code></i> has been processed by T _E X the test will be repeated, and a loop will occur until the test is true . |
| <code>\fp_while_do:nNnn</code> ☆ | <code>\fp_while_do:nNnn {<fpexpr₁>} <relation> {<fpexpr₂>} {<code>}</code> |
| New: 2012-08-16 | Evaluates the relationship between the two <i><floating point expressions></i> as described for <code>\fp_compare:nNnTF</code> , and then places the <i><code></i> in the input stream if the <i><relation></i> is true . After the <i><code></i> has been processed by T _E X the test will be repeated, and a loop will occur until the test is false . |
| <code>\fp_do_until:nn</code> ☆ | <code>\fp_do_until:nn { <fpexpr₁> <relation> <fpexpr₂> } {<code>}</code> |
| New: 2012-08-16 | Places the <i><code></i> in the input stream for T _E X to process, and then evaluates the relationship between the two <i><floating point expressions></i> as described for <code>\fp_compare:nTF</code> . If the test is false then the <i><code></i> will be inserted into the input stream again and a loop will occur until the <i><relation></i> is true . |
| <code>\fp_do_while:nn</code> ☆ | <code>\fp_do_while:nn { <fpexpr₁> <relation> <fpexpr₂> } {<code>}</code> |
| New: 2012-08-16 | Places the <i><code></i> in the input stream for T _E X to process, and then evaluates the relationship between the two <i><floating point expressions></i> as described for <code>\fp_compare:nTF</code> . If the test is true then the <i><code></i> will be inserted into the input stream again and a loop will occur until the <i><relation></i> is false . |
| <code>\fp_until_do:nn</code> ☆ | <code>\fp_until_do:nn { <fpexpr₁> <relation> <fpexpr₂> } {<code>}</code> |
| New: 2012-08-16 | Evaluates the relationship between the two <i><floating point expressions></i> as described for <code>\fp_compare:nTF</code> , and then places the <i><code></i> in the input stream if the <i><relation></i> is false . After the <i><code></i> has been processed by T _E X the test will be repeated, and a loop will occur until the test is true . |

| | |
|--|---|
| <hr/> <code>\fp_while_do:nn</code> ☆ <hr/> | <code>\fp_while_do:nn { <fpexpr₁> <relation> <fpexpr₂> } {<code>}</code> |
| New: 2012-08-16 | Evaluates the relationship between the two <i><floating point expressions></i> as described for <code>\fp_compare:nTF</code> , and then places the <i><code></i> in the input stream if the <i><relation></i> is true. After the <i><code></i> has been processed by T _E X the test will be repeated, and a loop will occur until the test is false . |

| | |
|--|--|
| <hr/> <code>\fp_step_function:nnnN</code> ☆ <code>\fp_step_function:nnnc</code> ☆ <hr/> | <code>\fp_step_function:nnnN {<initial value>} {<step>} {<final value>} <function></code> |
| New: 2016-11-21 Updated: 2016-12-06 | This function first evaluates the <i><initial value></i> , <i><step></i> and <i><final value></i> , all of which should be floating point expressions. The <i><function></i> is then placed in front of each <i><value></i> from the <i><initial value></i> to the <i><final value></i> in turn (using <i><step></i> between each <i><value></i>). The <i><step></i> must be non-zero. If the <i><step></i> is positive, the loop stops when the <i><value></i> becomes larger than the <i><final value></i> . If the <i><step></i> is negative, the loop stops when the <i><value></i> becomes smaller than the <i><final value></i> . The <i><function></i> should absorb one numerical argument. For example |

```
\cs_set:Npn \my_func:n #1 { [I~saw~#1] \quad }
\fp_step_function:nnnN { 1.0 } { 0.1 } { 1.5 } \my_func:n
```

would print

```
[I saw 1.0]   [I saw 1.1]   [I saw 1.2]   [I saw 1.3]   [I saw 1.4]   [I saw 1.5]
```

T_EXhackers note: Due to rounding, it may happen that adding the *<step>* to the *<value>* does not change the *<value>*; such cases give an error, as they would otherwise lead to an infinite loop.

| | |
|---|--|
| <hr/> <code>\fp_step_inline:nnnn</code> <hr/> | <code>\fp_step_inline:nnnn {<initial value>} {<step>} {<final value>} {<code>}</code> |
| New: 2016-11-21 Updated: 2016-12-06 | This function first evaluates the <i><initial value></i> , <i><step></i> and <i><final value></i> , all of which should be floating point expressions. Then for each <i><value></i> from the <i><initial value></i> to the <i><final value></i> in turn (using <i><step></i> between each <i><value></i>), the <i><code></i> is inserted into the input stream with #1 replaced by the current <i><value></i> . Thus the <i><code></i> should define a function of one argument (#1). |

6 Some useful constants, and scratch variables

| | |
|--|--|
| <hr/> <code>\c_zero_fp</code> <code>\c_minus_zero_fp</code> <hr/> | Zero, with either sign. |
| New: 2012-05-08 | |
| <hr/> <code>\c_one_fp</code> <hr/> | One as an fp : useful for comparisons in some places. |
| New: 2012-05-08 | |
| <hr/> <code>\c_inf_fp</code> <code>\c_minus_inf_fp</code> <hr/> | Infinity, with either sign. These can be input directly in a floating point expression as inf and -inf . |
| New: 2012-05-08 | |

| | |
|--|---|
| <hr/> <code>\c_e_fp</code> <hr/> | The value of the base of the natural logarithm, $e = \exp(1)$. |
| <hr/> Updated: 2012-05-08 <hr/> | |
| <hr/> <code>\c_pi_fp</code> <hr/> | The value of π . This can be input directly in a floating point expression as <code>pi</code> . |
| <hr/> Updated: 2013-11-17 <hr/> | |
| <hr/> <code>\c_one_degree_fp</code> <hr/> | The value of 1° in radians. Multiply an angle given in degrees by this value to obtain a result in radians. Note that trigonometric functions expecting an argument in radians or in degrees are both available. Within floating point expressions, this can be accessed as <code>deg</code> . |
| <hr/> New: 2012-05-08 <hr/> | |
| <hr/> Updated: 2013-11-17 <hr/> | |
| <hr/> <code>\l_tmpa_fp</code> <code>\l_tmpb_fp</code> <hr/> | Scratch floating points for local assignment. These are never used by the kernel code, and so are safe for use with any L ^A T _E X3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage. |
| <hr/> <code>\g_tmpa_fp</code> <code>\g_tmpb_fp</code> <hr/> | Scratch floating points for global assignment. These are never used by the kernel code, and so are safe for use with any L ^A T _E X3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage. |

7 Floating point exceptions

The functions defined in this section are experimental, and their functionality may be altered or removed altogether.

“Exceptions” may occur when performing some floating point operations, such as $0 / 0$, or $10 ** 1e9999$. The relevant IEEE standard defines 5 types of exceptions, of which we implement 4.

- *Overflow* occurs whenever the result of an operation is too large to be represented as a normal floating point number. This results in $\pm\infty$.
- *Underflow* occurs whenever the result of an operation is too close to 0 to be represented as a normal floating point number. This results in ± 0 .
- *Invalid operation* occurs for operations with no defined outcome, for instance $0/0$ or $\sin(\infty)$, and results in a NaN. It also occurs for conversion functions whose target type does not have the appropriate infinite or NaN value (*e.g.*, `\fp_to_dim:n`).
- *Division by zero* occurs when dividing a non-zero number by 0, or when evaluating functions at poles, *e.g.*, $\ln(0)$ or $\cot(0)$. This results in $\pm\infty$.

(*not yet*) *Inexact* occurs whenever the result of a computation is not exact, in other words, almost always. At the moment, this exception is entirely ignored in L^AT_EX3.

To each exception we associate a “flag”: `fp_overflow`, `fp_underflow`, `fp_invalid_operation` and `fp_division_by_zero`. The state of these flags can be tested and modified with commands from `l3flag`

By default, the “invalid operation” exception triggers an (expandable) error, and raises the corresponding flag. Other exceptions raise the corresponding flag but do not

trigger an error. The behaviour when an exception occurs can be modified (using `\fp_trap:nn`) to either produce an error and raise the flag, or only raise the flag, or do nothing at all.

| | |
|--|--|
| <code>\fp_trap:nn</code> | <code>\fp_trap:nn {⟨exception⟩} {⟨trap type⟩}</code> |
| New: 2012-07-19 Updated: 2017-02-13 | All occurrences of the <code>⟨exception⟩</code> (<code>overflow</code> , <code>underflow</code> , <code>invalid_operation</code> or <code>division_by_zero</code>) within the current group are treated as <code>⟨trap type⟩</code> , which can be <ul style="list-style-type: none"> • none: the <code>⟨exception⟩</code> will be entirely ignored, and leave no trace; • flag: the <code>⟨exception⟩</code> will turn the corresponding flag on when it occurs; • error: additionally, the <code>⟨exception⟩</code> will halt the T_EX run and display some information about the current operation in the terminal. |

This function is experimental, and may be altered or removed.

```
flag_fp_overflow
flag_fp_underflow
flag_fp_invalid_operation
flag_fp_division_by_zero
```

Flags denoting the occurrence of various floating-point exceptions.

8 Viewing floating points

| | |
|-------------------------|---|
| <code>\fp_show:N</code> | <code>\fp_show:N ⟨fp var⟩</code> |
| <code>\fp_show:c</code> | <code>\fp_show:n {⟨floating point expression⟩}</code> |
| <code>\fp_show:n</code> | Evaluates the <code>⟨floating point expression⟩</code> and displays the result in the terminal. |

New: 2012-05-08
Updated: 2015-08-07

| | |
|------------------------|---|
| <code>\fp_log:N</code> | <code>\fp_log:N ⟨fp var⟩</code> |
| <code>\fp_log:c</code> | <code>\fp_log:n {⟨floating point expression⟩}</code> |
| <code>\fp_log:n</code> | Evaluates the <code>⟨floating point expression⟩</code> and writes the result in the log file. |

New: 2014-08-22
Updated: 2015-08-07

9 Floating point expressions

9.1 Input of floating point numbers

We support four types of floating point numbers:

- $\pm 0.d_1d_2 \dots d_{16} \cdot 10^n$, a normal floating point number, with $d_i \in [0, 9]$, $d_1 \neq 0$, and $|n| \leq 10000$;
- ± 0 , zero, with a given sign;
- $\pm \infty$, infinity, with a given sign;

- **NaN**, is “not a number”, and can be either quiet or signalling (*not yet*: this distinction is currently unsupported);

(*not yet*) subnormal numbers $\pm 0.d_1d_2 \dots d_{16} \cdot 10^{-10000}$ with $d_1 = 0$.

Normal floating point numbers are stored in base 10, with 16 significant figures.

On input, a normal floating point number consists of:

- $\langle sign \rangle$: a possibly empty string of + and - characters;
- $\langle significand \rangle$: a non-empty string of digits together with zero or one dot;
- $\langle exponent \rangle$ optionally: the character **e**, followed by a possibly empty string of + and - tokens, and a non-empty string of digits.

The sign of the resulting number is + if $\langle sign \rangle$ contains an even number of -, and - otherwise, hence, an empty $\langle sign \rangle$ denotes a non-negative input. The stored significand is obtained from $\langle significand \rangle$ by omitting the decimal separator and leading zeros, and rounding to 16 significant digits, filling with trailing zeros if necessary. In particular, the value stored is exact if the input $\langle significand \rangle$ has at most 16 digits. The stored $\langle exponent \rangle$ is obtained by combining the input $\langle exponent \rangle$ (0 if absent) with a shift depending on the position of the significand and the number of leading zeros.

A special case arises if the resulting $\langle exponent \rangle$ is either too large or too small for the floating point number to be represented. This results either in an overflow (the number is then replaced by $\pm\infty$), or an underflow (resulting in ± 0).

The result is thus ± 0 if and only if $\langle significand \rangle$ contains no non-zero digit (*i.e.*, consists only in characters 0, and an optional period), or if there is an underflow. Note that a single dot is currently a valid floating point number, equal to +0, but that is not guaranteed to remain true.

The $\langle significand \rangle$ must be non-empty, so **e1** and **e-1** are not valid floating point numbers. Note that the latter could be mistaken with the difference of “**e**” and 1. To avoid confusions, the base of natural logarithms cannot be input as **e** and should be input as **exp(1)** or **\c_e_fp**.

Special numbers are input as follows:

- **inf** represents $+\infty$, and can be preceded by any $\langle sign \rangle$, yielding $\pm\infty$ as appropriate.
- **nan** represents a (quiet) non-number. It can be preceded by any sign, but that will be ignored.
- Any unrecognizable string triggers an error, and produces a **NaN**.

9.2 Precedence of operators

We list here all the operations supported in floating point expressions, in order of decreasing precedence: operations listed earlier bind more tightly than operations listed below them.

- Function calls (**sin**, **ln**, *etc*).
- Binary ****** and **^** (right associative).
- Unary **+**, **-**, **!**.

- Binary `*`, `/`, and implicit multiplication by juxtaposition (`2pi`, `3(4+5)`, *etc.*).
- Binary `+` and `-`.
- Comparisons `>=`, `!=`, `<?`, *etc.*
- Logical `and`, denoted by `&&`.
- Logical `or`, denoted by `||`.
- Ternary operator `?:` (right associative).

The precedence of operations can be overridden using parentheses. In particular, those precedences imply that

$$\begin{aligned}\sin 2\pi &= \sin(2\pi) = 0, \\ 2^{2\max(3,4)} &= 2^{2\max(3,4)} = 256.\end{aligned}$$

Functions are called on the value of their argument, contrarily to \TeX macros.

9.3 Operations

We now present the various operations allowed in floating point expressions, from the lowest precedence to the highest. When used as a truth value, a floating point expression is `false` if it is ± 0 , and `true` otherwise, including when it is `NaN`.

```
?: \fp_eval:n { <operand_1> ? <operand_2> : <operand_3> }
```

The ternary operator `?:` results in `<operand_2>` if `<operand_1>` is true, and `<operand_3>` if it is false (equal to ± 0). All three `<operands>` are evaluated in all cases. The operator is right associative, hence

```
\fp_eval:n
{
  1 + 3 > 4 ? 1 :
  2 + 4 > 5 ? 2 :
  3 + 5 > 6 ? 3 : 4
}
```

first tests whether `1 + 3 > 4`; since this isn't true, the branch following `:` is taken, and `2 + 4 > 5` is compared; since this is true, the branch before `:` is taken, and everything else is (evaluated then) ignored. That allows testing for various cases in a concise manner, with the drawback that all computations are made in all cases.

```
|| \fp_eval:n { <operand_1> <operand_2> }
```

If `<operand_1>` is true (non-zero), use that value, otherwise the value of `<operand_2>`. Both `<operands>` are evaluated in all cases.

```
&& \fp_eval:n { <operand_1> && <operand_2> }
```

If `<operand_1>` is false (equal to ± 0), use that value, otherwise the value of `<operand_2>`. Both `<operands>` are evaluated in all cases.

```

<      \fp_eval:n
=      {
>      \langle operand_1 \rangle \langle relation_1 \rangle
?      ...
      \langle operand_N \rangle \langle relation_N \rangle
Updated: 2013-12-14 \langle operand_{N+1} \rangle
      }

```

Each $\langle relation \rangle$ consists of a non-empty string of $<$, $=$, $>$, and $?$, optionally preceded by $!$, and may not start with $?$. This evaluates to $+1$ if all comparisons $\langle operand_i \rangle \langle relation_j \rangle$ $\langle operand_{i+1} \rangle$ are true, and $+0$ otherwise. All $\langle operands \rangle$ are evaluated in all cases. See `\fp_compare:nTF` for details.

```

+      \fp_eval:n { \langle operand_1 \rangle + \langle operand_2 \rangle }
-      \fp_eval:n { \langle operand_1 \rangle - \langle operand_2 \rangle }

```

Computes the sum or the difference of its two $\langle operands \rangle$. The “invalid operation” exception occurs for $\infty - \infty$. “Underflow” and “overflow” occur when appropriate.

```

*      \fp_eval:n { \langle operand_1 \rangle * \langle operand_2 \rangle }
/      \fp_eval:n { \langle operand_1 \rangle / \langle operand_2 \rangle }

```

Computes the product or the ratio of its two $\langle operands \rangle$. The “invalid operation” exception occurs for ∞/∞ , $0/0$, or $0 * \infty$. “Division by zero” occurs when dividing a finite non-zero number by ± 0 . “Underflow” and “overflow” occur when appropriate.

```

+      \fp_eval:n { + \langle operand \rangle }
-      \fp_eval:n { - \langle operand \rangle }
!      \fp_eval:n { ! \langle operand \rangle }

```

The unary $+$ does nothing, the unary $-$ changes the sign of the $\langle operand \rangle$, and $! \langle operand \rangle$ evaluates to 1 if $\langle operand \rangle$ is false and 0 otherwise (this is the `not` boolean function). Those operations never raise exceptions.

```

**     \fp_eval:n { \langle operand_1 \rangle ** \langle operand_2 \rangle }
^      \fp_eval:n { \langle operand_1 \rangle ^ \langle operand_2 \rangle }

```

Raises $\langle operand_1 \rangle$ to the power $\langle operand_2 \rangle$. This operation is right associative, hence `2 ** 2 ** 3` equals $2^{2^3} = 256$. If $\langle operand_1 \rangle$ is negative or -0 then: the result’s sign is $+$ if the $\langle operand_2 \rangle$ is infinite and $(-1)^p$ if the $\langle operand_2 \rangle$ is p/q with p integer and q odd; the result is $+0$ if `abs(\langle operand_1 \rangle)^\langle operand_2 \rangle` evaluates to zero; in other cases the “invalid operation” exception occurs because the sign cannot be determined. “Division by zero” occurs when raising ± 0 to a finite strictly negative power. “Underflow” and “overflow” occur when appropriate.

```

abs    \fp_eval:n { abs( \langle fpexpr \rangle ) }

```

Computes the absolute value of the $\langle fpexpr \rangle$. This function does not raise any exception beyond those raised when computing its operand $\langle fpexpr \rangle$. See also `\fp_abs:n`.

```

exp    \fp_eval:n { exp( \langle fpexpr \rangle ) }

```

Computes the exponential of the $\langle fpexpr \rangle$. “Underflow” and “overflow” occur when appropriate.

| | | |
|--|--|---|
| <hr/> | <code>\fp_eval:n { ln(<fpexpr>) }</code> | |
| | | Computes the natural logarithm of the $\langle fpexpr \rangle$. Negative numbers have no (real) logarithm, hence the “invalid operation” is raised in that case, including for $\ln(-0)$. “Division by zero” occurs when evaluating $\ln(+0) = -\infty$. “Underflow” and “overflow” occur when appropriate. |
| <hr/> | <code>\fp_eval:n { max(<fpexpr₁> , <fpexpr₂> , ...) }</code> | |
| <code>min</code> | <code>\fp_eval:n { min(<fpexpr₁> , <fpexpr₂> , ...) }</code> | |
| <hr/> | | Evaluates each $\langle fpexpr \rangle$ and computes the largest (smallest) of those. If any of the $\langle fpexpr \rangle$ is a NaN, the result is NaN. Those operations do not raise exceptions. |
| <hr/> | <code>\fp_eval:n { round (<fpexpr>) }</code> | |
| <code>trunc</code> | <code>\fp_eval:n { round (<fpexpr₁> , <fpexpr₂>) }</code> | |
| <code>ceil</code> | <code>\fp_eval:n { round (<fpexpr₁> , <fpexpr₂> , <fpexpr₃>) }</code> | |
| <code>floor</code> | | Only <code>round</code> accepts a third argument. Evaluates $\langle fpexpr_1 \rangle = x$ and $\langle fpexpr_2 \rangle = n$ and $\langle fpexpr_3 \rangle = t$ then rounds x to n places. If n is an integer, this rounds x to a multiple of 10^{-n} ; if $n = +\infty$, this always yields x ; if $n = -\infty$, this yields one of ± 0 , $\pm\infty$, or NaN; if n is neither $\pm\infty$ nor an integer, then an “invalid operation” exception is raised. When $\langle fpexpr_2 \rangle$ is omitted, $n = 0$, <i>i.e.</i> , $\langle fpexpr_1 \rangle$ is rounded to an integer. The rounding direction depends on the function. |
| <hr/> | | |
| <div>New: 2013-12-14 Updated: 2015-08-08</div> | | |
| | | <ul style="list-style-type: none"> • <code>round</code> yields the multiple of 10^{-n} closest to x, with ties (x half-way between two such multiples) rounded as follows. If t is <code>nan</code> or not given the even multiple is chosen (“ties to even”), if $t = \pm 0$ the multiple closest to 0 is chosen (“ties to zero”), if t is positive/negative the multiple closest to $\infty/-\infty$ is chosen (“ties towards positive/negative infinity”). • <code>floor</code>, or the deprecated <code>round-</code>, yields the largest multiple of 10^{-n} smaller or equal to x (“round towards negative infinity”); • <code>ceil</code>, or the deprecated <code>round+</code>, yields the smallest multiple of 10^{-n} greater or equal to x (“round towards positive infinity”); • <code>trunc</code>, or the deprecated <code>round0</code>, yields a multiple of 10^{-n} with the same sign as x and with the largest absolute value less than that of x (“round towards zero”). <p>“Overflow” occurs if x is finite and the result is infinite (this can only happen if $\langle fpexpr_2 \rangle < -9984$).</p> |

| | |
|------------------|---|
| <code>sin</code> | <code>\fp_eval:n { sin(<fpexpr>) }</code> |
| <code>cos</code> | <code>\fp_eval:n { cos(<fpexpr>) }</code> |
| <code>tan</code> | <code>\fp_eval:n { tan(<fpexpr>) }</code> |
| <code>cot</code> | <code>\fp_eval:n { cot(<fpexpr>) }</code> |
| <code>csc</code> | <code>\fp_eval:n { csc(<fpexpr>) }</code> |
| <code>sec</code> | <code>\fp_eval:n { sec(<fpexpr>) }</code> |

Updated: 2013-11-17

Computes the sine, cosine, tangent, cotangent, cosecant, or secant of the $\langle fpexpr \rangle$ given in radians. For arguments given in degrees, see `sind`, `cosd`, *etc.* Note that since π is irrational, $\sin(8\pi)$ is not quite zero, while its analog $\text{sind}(8 \times 180)$ is exactly zero. The trigonometric functions are undefined for an argument of $\pm\infty$, leading to the “invalid operation” exception. Additionally, evaluating tangent, cotangent, cosecant, or secant at one of their poles leads to a “division by zero” exception. “Underflow” and “overflow” occur when appropriate.

| | |
|-------------------|--|
| <code>sind</code> | <code>\fp_eval:n { sind(<fpexpr>) }</code> |
| <code>cosd</code> | <code>\fp_eval:n { cosd(<fpexpr>) }</code> |
| <code>tand</code> | <code>\fp_eval:n { tand(<fpexpr>) }</code> |
| <code>cotd</code> | <code>\fp_eval:n { cotd(<fpexpr>) }</code> |
| <code>cscd</code> | <code>\fp_eval:n { cscd(<fpexpr>) }</code> |
| <code>secd</code> | <code>\fp_eval:n { secd(<fpexpr>) }</code> |

New: 2013-11-02

Computes the sine, cosine, tangent, cotangent, cosecant, or secant of the $\langle fpexpr \rangle$ given in degrees. For arguments given in radians, see `sin`, `cos`, *etc.* Note that since π is irrational, $\sin(8\pi)$ is not quite zero, while its analog $\text{sind}(8 \times 180)$ is exactly zero. The trigonometric functions are undefined for an argument of $\pm\infty$, leading to the “invalid operation” exception. Additionally, evaluating tangent, cotangent, cosecant, or secant at one of their poles leads to a “division by zero” exception. “Underflow” and “overflow” occur when appropriate.

| | |
|-------------------|--|
| <code>asin</code> | <code>\fp_eval:n { asin(<fpexpr>) }</code> |
| <code>acos</code> | <code>\fp_eval:n { acos(<fpexpr>) }</code> |
| <code>acsc</code> | <code>\fp_eval:n { acsc(<fpexpr>) }</code> |
| <code>asec</code> | <code>\fp_eval:n { asec(<fpexpr>) }</code> |

New: 2013-11-02

Computes the arcsine, arccosine, arccosecant, or arcsecant of the $\langle fpexpr \rangle$ and returns the result in radians, in the range $[-\pi/2, \pi/2]$ for `asin` and `acsc` and $[0, \pi]$ for `acos` and `asec`. For a result in degrees, use `asind`, *etc.* If the argument of `asin` or `acos` lies outside the range $[-1, 1]$, or the argument of `acsc` or `asec` inside the range $(-1, 1)$, an “invalid operation” exception is raised. “Underflow” and “overflow” occur when appropriate.

| | |
|--------------------|---|
| <code>asind</code> | <code>\fp_eval:n { asind(<fpexpr>) }</code> |
| <code>acosd</code> | <code>\fp_eval:n { acosd(<fpexpr>) }</code> |
| <code>acscd</code> | <code>\fp_eval:n { acscd(<fpexpr>) }</code> |
| <code>asecd</code> | <code>\fp_eval:n { asecd(<fpexpr>) }</code> |

New: 2013-11-02

Computes the arcsine, arccosine, arccosecant, or arcsecant of the $\langle fpexpr \rangle$ and returns the result in degrees, in the range $[-90, 90]$ for `asin` and `acsc` and $[0, 180]$ for `acos` and `asec`. For a result in radians, use `asin`, *etc.* If the argument of `asin` or `acos` lies outside the range $[-1, 1]$, or the argument of `acsc` or `asec` inside the range $(-1, 1)$, an “invalid operation” exception is raised. “Underflow” and “overflow” occur when appropriate.

| | |
|------------------------|---|
| atan | <code>\fp_eval:n { atan(<fpexpr>) }</code> |
| acot | <code>\fp_eval:n { atan(<fpexpr₁> , <fpexpr₂>) }</code> |
| <hr/> | |
| New: 2013-11-02 | <code>\fp_eval:n { acot(<fpexpr>) }</code> |
| | <code>\fp_eval:n { acot(<fpexpr₁> , <fpexpr₂>) }</code> |

Those functions yield an angle in radians: **atand** and **acotd** are their analogs in degrees. The one-argument versions compute the arctangent or arccotangent of the $\langle fpexpr \rangle$: arctangent takes values in the range $[-\pi/2, \pi/2]$, and arccotangent in the range $[0, \pi]$. The two-argument arctangent computes the angle in polar coordinates of the point with Cartesian coordinates $(\langle fpexpr_2 \rangle, \langle fpexpr_1 \rangle)$: this is the arctangent of $\langle fpexpr_1 \rangle / \langle fpexpr_2 \rangle$, possibly shifted by π depending on the signs of $\langle fpexpr_1 \rangle$ and $\langle fpexpr_2 \rangle$. The two-argument arccotangent computes the angle in polar coordinates of the point $(\langle fpexpr_1 \rangle, \langle fpexpr_2 \rangle)$, equal to the arccotangent of $\langle fpexpr_1 \rangle / \langle fpexpr_2 \rangle$, possibly shifted by π . Both two-argument functions take values in the wider range $[-\pi, \pi]$. The ratio $\langle fpexpr_1 \rangle / \langle fpexpr_2 \rangle$ need not be defined for the two-argument arctangent: when both expressions yield ± 0 , or when both yield $\pm \infty$, the resulting angle is one of $\{\pm\pi/4, \pm 3\pi/4\}$ depending on signs. Only the “underflow” exception can occur.

| | |
|------------------------|--|
| atand | <code>\fp_eval:n { atand(<fpexpr>) }</code> |
| acotd | <code>\fp_eval:n { atand(<fpexpr₁> , <fpexpr₂>) }</code> |
| <hr/> | |
| New: 2013-11-02 | <code>\fp_eval:n { acotd(<fpexpr>) }</code> |
| | <code>\fp_eval:n { acotd(<fpexpr₁> , <fpexpr₂>) }</code> |

Those functions yield an angle in degrees: **atand** and **acotd** are their analogs in radians. The one-argument versions compute the arctangent or arccotangent of the $\langle fpexpr \rangle$: arctangent takes values in the range $[-90, 90]$, and arccotangent in the range $[0, 180]$. The two-argument arctangent computes the angle in polar coordinates of the point with Cartesian coordinates $(\langle fpexpr_2 \rangle, \langle fpexpr_1 \rangle)$: this is the arctangent of $\langle fpexpr_1 \rangle / \langle fpexpr_2 \rangle$, possibly shifted by 180 depending on the signs of $\langle fpexpr_1 \rangle$ and $\langle fpexpr_2 \rangle$. The two-argument arccotangent computes the angle in polar coordinates of the point $(\langle fpexpr_1 \rangle, \langle fpexpr_2 \rangle)$, equal to the arccotangent of $\langle fpexpr_1 \rangle / \langle fpexpr_2 \rangle$, possibly shifted by 180. Both two-argument functions take values in the wider range $[-180, 180]$. The ratio $\langle fpexpr_1 \rangle / \langle fpexpr_2 \rangle$ need not be defined for the two-argument arctangent: when both expressions yield ± 0 , or when both yield $\pm \infty$, the resulting angle is one of $\{\pm 45, \pm 135\}$ depending on signs. Only the “underflow” exception can occur.

| | |
|-------------|--|
| sqrt | <code>\fp_eval:n { sqrt(<fpexpr>) }</code> |
|-------------|--|

New: 2013-12-14 Computes the square root of the $\langle fpexpr \rangle$. The “invalid operation” is raised when the $\langle fpexpr \rangle$ is negative; no other exception can occur. Special values yield $\sqrt{-0} = -0$, $\sqrt{+0} = +0$, $\sqrt{+\infty} = +\infty$ and $\sqrt{\text{NaN}} = \text{NaN}$.

| | |
|--|--|
| <hr/> rand <hr/> | <code>\fp_eval:n { rand() }</code> |
| <hr/> <small>New: 2016-12-05</small> <hr/> | Produces a pseudo-random floating-point number (multiple of 10^{-16}) between 0 included and 1 excluded. Available in pdfTeX and LuaTeX engines only. |
| <p>TeXhackers note: This is based on pseudo-random numbers provided by the engine's primitive <code>\pdfuniformdeviate</code> in pdfTeX and <code>\uniformdeviate</code> in LuaTeX. The underlying code in pdfTeX and LuaTeX is based on Metapost, which follows an additive scheme recommended in Section 3.6 of “The Art of Computer Programming, Volume 2”.</p> <p>While we are more careful than <code>\uniformdeviate</code> to preserve uniformity of the underlying stream of 28-bit pseudo-random integers, these pseudo-random numbers should of course not be relied upon for serious numerical computations nor cryptography.</p> <p>The random seed can be queried using <code>\pdfrandomseed</code> and set using <code>\pdfsetrandomseed</code> (in LuaTeX <code>\randomseed</code> and <code>\setrandomseed</code>). While a 32-bit (signed) integer can be given as a seed, only the absolute value is used and any number beyond 2^{28} is divided by an appropriate power of 2. We recommend using an integer in $[0, 2^{28} - 1]$.</p> | |
| <hr/> randint <hr/> | <code>\fp_eval:n { randint(<fpexpr>) }</code> |
| <hr/> <small>New: 2016-12-05</small> <hr/> | <code>\fp_eval:n { randint(<fpexpr₁> , <fpexpr₂>) }</code> |
| | Produces a pseudo-random integer between 1 and <code><fpexpr></code> or between <code><fpexpr₁></code> and <code><fpexpr₂></code> inclusive. The bounds must be integers in the range $(-10^{16}, 10^{16})$ and the first must be smaller or equal to the second. See rand for important comments on how these pseudo-random numbers are generated. |
| <hr/> inf <hr/> | The special values $+\infty$, $-\infty$, and NaN are represented as <code>inf</code> , <code>-inf</code> and <code>nan</code> (see <code>\c_inf_fp</code> , <code>\c_minus_inf_fp</code> and <code>\c_nan_fp</code>). |
| <hr/> nan <hr/> | |
| <hr/> pi <hr/> | The value of π (see <code>\c_pi_fp</code>). |
| <hr/> deg <hr/> | The value of 1° in radians (see <code>\c_one_degree_fp</code>). |

| | |
|-----------------|--|
| <hr/> | |
| <code>em</code> | Those units of measurement are equal to their values in <code>pt</code> , namely |
| <code>ex</code> | |
| <code>in</code> | $1\text{in} = 72.27\text{pt}$ |
| <code>pt</code> | $1\text{pt} = 1\text{pt}$ |
| <code>pc</code> | |
| <code>cm</code> | $1\text{pc} = 12\text{pt}$ |
| <code>mm</code> | |
| <code>dd</code> | $1\text{cm} = \frac{1}{2.54}\text{in} = 28.45275590551181\text{pt}$ |
| <code>cc</code> | |
| <code>nd</code> | $1\text{mm} = \frac{1}{25.4}\text{in} = 2.845275590551181\text{pt}$ |
| <code>nc</code> | |
| <code>bp</code> | $1\text{dd} = 0.376065\text{mm} = 1.07000856496063\text{pt}$ |
| <code>sp</code> | $1\text{cc} = 12\text{dd} = 12.84010277952756\text{pt}$ |
| <hr/> | |
| | $1\text{nd} = 0.375\text{mm} = 1.066978346456693\text{pt}$ |
| | $1\text{nc} = 12\text{nd} = 12.80374015748031\text{pt}$ |
| | $1\text{bp} = \frac{1}{72}\text{in} = 1.00375\text{pt}$ |
| | $1\text{sp} = 2^{-16}\text{pt} = 1.52587890625e - 5\text{pt}.$ |

The values of the (font-dependent) units `em` and `ex` are gathered from $\text{T}_{\text{E}}\text{X}$ when the surrounding floating point expression is evaluated.

| | |
|--------------------|---------------------------|
| <hr/> | |
| <code>true</code> | Other names for 1 and +0. |
| <code>false</code> | |
| <hr/> | |

| | |
|---------------------------|---|
| <hr/> | |
| <code>\fp_abs:n</code> ★ | <code>\fp_abs:n</code> { <i>floating point expression</i> } |
| New: 2012-05-14 | |
| Updated: 2012-07-08 | |
| <hr/> | |
| | Evaluates the <i>floating point expression</i> as described for <code>\fp_eval:n</code> and leaves the absolute value of the result in the input stream. This function does not raise any exception beyond those raised when evaluating its argument. Within floating point expressions, <code>abs()</code> can be used. |
| <hr/> | |
| <code>\fp_max:nn</code> ★ | <code>\fp_max:nn</code> { <i>fp expression 1</i> } { <i>fp expression 2</i> } |
| <code>\fp_min:nn</code> ★ | |
| New: 2012-09-26 | |
| <hr/> | |
| | Evaluates the <i>floating point expressions</i> as described for <code>\fp_eval:n</code> and leaves the resulting larger (<code>max</code>) or smaller (<code>min</code>) value in the input stream. This function does not raise any exception beyond those raised when evaluating its argument. Within floating point expressions, <code>max()</code> and <code>min()</code> can be used. |

10 Disclaimer and roadmap

The package may break down if the escape character is among `0123456789_+`, or if it receives a $\text{T}_{\text{E}}\text{X}$ primitive conditional affected by `\exp_not:N`.

The following need to be done. I'll try to time-order the items.

- Decide what exponent range to consider.
- Support signalling `nan`.

- Modulo and remainder, and rounding functions `quantize`, `quantize0`, `quantize+`, `quantize-`, `quantize=`, `round=`. Should the modulo also be provided as (catcode 12) `%`?
- `\fp_format:nn` $\{\langle fpepr \rangle\}$ $\{\langle format \rangle\}$, but what should $\langle format \rangle$ be? More general pretty printing?
- Add `and`, `or`, `xor`? Perhaps under the names `all`, `any`, and `xor`?
- Add `log(x,b)` for logarithm of x in base b .
- `hypot` (Euclidean length). Cartesian-to-polar transform.
- Hyperbolic functions `cosh`, `sinh`, `tanh`.
- Inverse hyperbolics.
- Base conversion, input such as `0xAB.CDEF`.
- Factorial (not with `!`), gamma function.
- Improve coefficients of the `sin` and `tan` series.
- Treat upper and lower case letters identically in identifiers, and ignore underscores.
- Add an `array(1,2,3)` and `i=complex(0,1)`.
- Provide an experimental `map` function? Perhaps easier to implement if it is a single character, `@sin(1,2)`?
- Provide `\fp_if_nan:nTF`, and an `isnan` function?
- Support keyword arguments?

`Pgfmth` also provides box-measurements (depth, height, width), but boxes are not possible expandably.

Bugs. (Exclamation points mark important bugs.)

- Check that functions are monotonic when they should.
- Add exceptions to `?:`, `!<=>?`, `&&`, `||`, and `!`.
- Logarithms of numbers very close to 1 are inaccurate.
- When rounding towards $-\infty$, `\dim_to_fp:n` $\{0pt\}$ should return -0 , not $+0$.
- The result of $(\pm 0) + (\pm 0)$, of $x + (-x)$, and of $(-x) + x$ should depend on the rounding mode.
- `0e9999999999` gives a \TeX “number too large” error.
- Subnormals are not implemented.
- The overflow trap receives the wrong argument in `l3fp-expo` (see `exp(1e5678)` in `m3fp-traps001`).

Possible optimizations/improvements.

- Document that `l3trial/l3fp-types` introduces tools for adding new types.

- In subsection 9.1, write a grammar.
- It would be nice if the `parse` auxiliaries for each operation were set up in the corresponding module, rather than centralizing in `l3fp-parse`.
- Some functions should get an `_o` ending to indicate that they expand after their result.
- More care should be given to distinguish expandable/restricted expandable (auxiliary and internal) functions.
- The code for the `ternary` set of functions is ugly.
- There are many `~` missing in the doc to avoid bad line-breaks.
- The algorithm for computing the logarithm of the significand could be made to use a 5 terms Taylor series instead of 10 terms by taking $c = 2000/(\lfloor 200x \rfloor + 1) \in [10, 95]$ instead of $c \in [1, 10]$. Also, it would then be possible to simplify the computation of t . However, we would then have to hard-code the logarithms of 44 small integers instead of 9.
- Improve notations in the explanations of the division algorithm (`l3fp-basics`).
- Understand and document `_fp_basics_pack_weird_low:NNNNw` and `_fp_basics_pack_weird_high:NNNNNNNNw` better. Move the other `basics_pack` auxiliaries to `l3fp-aux` under a better name.
- Find out if underflow can really occur for trigonometric functions, and redoc as appropriate.
- Add bibliography. Some of Kahan’s articles, some previous T_EX fp packages, the international standards,...
- Also take into account the “inexact” exception?
- Support multi-character prefix operators (*e.g.*, `@/` or whatever)? Perhaps for including comments inside the computation itself??

Part XXI

The l3sort package

Sorting functions

1 Controlling sorting

L^AT_EX3 comes with a facility to sort list variables (sequences, token lists, or comma-lists) according to some user-defined comparison. For instance,

```
\clist_set:Nn \l_foo_clist { 3 , 01 , -2 , 5 , +1 }
\clist_sort:Nn \l_foo_clist
{
  \int_compare:nNnTF { #1 } > { #2 }
  { \sort_return_swapped: }
  { \sort_return_same: }
}
```

will result in `\l_foo_clist` holding the values `{ -2 , 01 , +1 , 3 , 5 }` sorted in non-decreasing order.

The code defining the comparison should call `\sort_return_swapped:` if the two items given as `#1` and `#2` are not in the correct order, and otherwise it should call `\sort_return_same:` to indicate that the order of this pair of items should not be changed.

For instance, a *comparison code* consisting only of `\sort_return_same:` with no test will yield a trivial sort: the final order is identical to the original order. Conversely, using a *comparison code* consisting only of `\sort_return_swapped:` will reverse the list (in a fairly inefficient way).

T_EXhackers note: The current implementation is limited to sorting approximately 20000 items (40000 in LuaT_EX), depending on what other packages are loaded.

Internally, the code from `l3sort` stores items in `\toks` registers allocated locally. Thus, the *comparison code* should not call `\newtoks` or other commands that allocate new `\toks` registers. On the other hand, altering the value of a previously allocated `\toks` register is not a problem.

Part XXII

The l3box package

Boxes

There are three kinds of box operations: horizontal mode denoted with prefix `\hbox_`, vertical mode with prefix `\vbox_`, and the generic operations working in both modes with prefix `\box_`.

1 Creating and initialising boxes

| | |
|-------------------------|---|
| <code>\box_new:N</code> | <code>\box_new:N</code> $\langle box \rangle$ |
| <code>\box_new:c</code> | Creates a new $\langle box \rangle$ or raises an error if the name is already taken. The declaration is global. The $\langle box \rangle$ will initially be void. |

| | |
|----------------------------|--|
| <code>\box_clear:N</code> | <code>\box_clear:N</code> $\langle box \rangle$ |
| <code>\box_clear:c</code> | Clears the content of the $\langle box \rangle$ by setting the box equal to <code>\c_void_box</code> . |
| <code>\box_gclear:N</code> | |
| <code>\box_gclear:c</code> | |

| | |
|--------------------------------|--|
| <code>\box_clear_new:N</code> | <code>\box_clear_new:N</code> $\langle box \rangle$ |
| <code>\box_clear_new:c</code> | Ensures that the $\langle box \rangle$ exists globally by applying <code>\box_new:N</code> if necessary, then applies <code>\box_(g)clear:N</code> to leave the $\langle box \rangle$ empty. |
| <code>\box_gclear_new:N</code> | |
| <code>\box_gclear_new:c</code> | |

| | |
|--------------------------------------|--|
| <code>\box_set_eq:NN</code> | <code>\box_set_eq:NN</code> $\langle box_1 \rangle$ $\langle box_2 \rangle$ |
| <code>\box_set_eq:(cN Nc cc)</code> | Sets the content of $\langle box_1 \rangle$ equal to that of $\langle box_2 \rangle$. |
| <code>\box_gset_eq:NN</code> | |
| <code>\box_gset_eq:(cN Nc cc)</code> | |

| | |
|---|---|
| <code>\box_set_eq_clear:NN</code> | <code>\box_set_eq_clear:NN</code> $\langle box_1 \rangle$ $\langle box_2 \rangle$ |
| <code>\box_set_eq_clear:(cN Nc cc)</code> | Sets the content of $\langle box_1 \rangle$ within the current TeX group equal to that of $\langle box_2 \rangle$, then clears $\langle box_2 \rangle$ globally. |

| | |
|--|--|
| <code>\box_gset_eq_clear:NN</code> | <code>\box_gset_eq_clear:NN</code> $\langle box_1 \rangle$ $\langle box_2 \rangle$ |
| <code>\box_gset_eq_clear:(cN Nc cc)</code> | Sets the content of $\langle box_1 \rangle$ equal to that of $\langle box_2 \rangle$, then clears $\langle box_2 \rangle$. These assignments are global. |

| | |
|----------------------------------|---|
| <code>\box_if_exist_p:N</code> ★ | <code>\box_if_exist_p:N</code> $\langle box \rangle$ |
| <code>\box_if_exist_p:c</code> ★ | <code>\box_if_exist:NTF</code> $\langle box \rangle$ $\{ \langle true\ code \rangle \}$ $\{ \langle false\ code \rangle \}$ |
| <code>\box_if_exist:NTF</code> ★ | Tests whether the $\langle box \rangle$ is currently defined. This does not check that the $\langle box \rangle$ really is a box. |
| <code>\box_if_exist:cTF</code> ★ | |

New: 2012-03-03

2 Using boxes

`\box_use:N`
`\box_use:c`

`\box_use:N` $\langle box \rangle$

Inserts the current content of the $\langle box \rangle$ onto the current list for typesetting.

TeXhackers note: This is the TeX primitive `\copy`.

`\box_use_clear:N`
`\box_use_clear:c`

`\box_use_clear:N` $\langle box \rangle$

Inserts the current content of the $\langle box \rangle$ onto the current list for typesetting, then globally clears the content of the $\langle box \rangle$.

TeXhackers note: This is the TeX primitive `\box`.

`\box_move_right:nn`
`\box_move_left:nn`

`\box_move_right:nn` $\{\langle dimexpr \rangle\} \{\langle box function \rangle\}$

This function operates in vertical mode, and inserts the material specified by the $\langle box function \rangle$ such that its reference point is displaced horizontally by the given $\langle dimexpr \rangle$ from the reference point for typesetting, to the right or left as appropriate. The $\langle box function \rangle$ should be a box operation such as `\box_use:N \<box>` or a “raw” box specification such as `\vbox:n { xyz }`.

`\box_move_up:nn`
`\box_move_down:nn`

`\box_move_up:nn` $\{\langle dimexpr \rangle\} \{\langle box function \rangle\}$

This function operates in horizontal mode, and inserts the material specified by the $\langle box function \rangle$ such that its reference point is displaced vertical by the given $\langle dimexpr \rangle$ from the reference point for typesetting, up or down as appropriate. The $\langle box function \rangle$ should be a box operation such as `\box_use:N \<box>` or a “raw” box specification such as `\vbox:n { xyz }`.

3 Measuring and setting box dimensions

`\box_dp:N`
`\box_dp:c`

`\box_dp:N` $\langle box \rangle$

Calculates the depth (below the baseline) of the $\langle box \rangle$ in a form suitable for use in a $\langle dimension expression \rangle$.

TeXhackers note: This is the TeX primitive `\dp`.

`\box_ht:N`
`\box_ht:c`

`\box_ht:N` $\langle box \rangle$

Calculates the height (above the baseline) of the $\langle box \rangle$ in a form suitable for use in a $\langle dimension expression \rangle$.

TeXhackers note: This is the TeX primitive `\ht`.

| | |
|------------------------|--|
| <code>\box_wd:N</code> | <code>\box_wd:N <box></code> |
| <code>\box_wd:c</code> | Calculates the width of the $\langle box \rangle$ in a form suitable for use in a $\langle dimension expression \rangle$. |

T_EXhackers note: This is the T_EX primitive `\wd`.

| | |
|-----------------------------|---|
| <code>\box_set_dp:Nn</code> | <code>\box_set_dp:Nn <box> {<dimension expression>}</code> |
| <code>\box_set_dp:cn</code> | Set the depth (below the baseline) of the $\langle box \rangle$ to the value of the $\{<dimension expression>\}$. This is a global assignment. |

| | |
|-----------------------------|--|
| <code>\box_set_ht:Nn</code> | <code>\box_set_ht:Nn <box> {<dimension expression>}</code> |
| <code>\box_set_ht:cn</code> | Set the height (above the baseline) of the $\langle box \rangle$ to the value of the $\{<dimension expression>\}$. This is a global assignment. |

| | |
|-----------------------------|--|
| <code>\box_set_wd:Nn</code> | <code>\box_set_wd:Nn <box> {<dimension expression>}</code> |
| <code>\box_set_wd:cn</code> | Set the width of the $\langle box \rangle$ to the value of the $\{<dimension expression>\}$. This is a global assignment. |

4 Box conditionals

| | |
|----------------------------------|---|
| <code>\box_if_empty_p:N</code> ★ | <code>\box_if_empty_p:N <box></code> |
| <code>\box_if_empty_p:c</code> ★ | <code>\box_if_empty:NTF <box> {<true code>} {<false code>}</code> |
| <code>\box_if_empty:NTF</code> ★ | Tests if $\langle box \rangle$ is a empty (equal to <code>\c_empty_box</code>). |
| <code>\box_if_empty:cTF</code> ★ | |

| | |
|---------------------------------------|--|
| <code>\box_if_horizontal_p:N</code> ★ | <code>\box_if_horizontal_p:N <box></code> |
| <code>\box_if_horizontal_p:c</code> ★ | <code>\box_if_horizontal:NTF <box> {<true code>} {<false code>}</code> |
| <code>\box_if_horizontal:NTF</code> ★ | Tests if $\langle box \rangle$ is a horizontal box. |
| <code>\box_if_horizontal:cTF</code> ★ | |

| | |
|-------------------------------------|--|
| <code>\box_if_vertical_p:N</code> ★ | <code>\box_if_vertical_p:N <box></code> |
| <code>\box_if_vertical_p:c</code> ★ | <code>\box_if_vertical:NTF <box> {<true code>} {<false code>}</code> |
| <code>\box_if_vertical:NTF</code> ★ | Tests if $\langle box \rangle$ is a vertical box. |
| <code>\box_if_vertical:cTF</code> ★ | |

5 The last box inserted

| | |
|----------------------------------|--|
| <code>\box_set_to_last:N</code> | <code>\box_set_to_last:N <box></code> |
| <code>\box_set_to_last:c</code> | Sets the $\langle box \rangle$ equal to the last item (box) added to the current partial list, removing the item from the list at the same time. When applied to the main vertical list, the $\langle box \rangle$ will always be void as it is not possible to recover the last added item. |
| <code>\box_gset_to_last:N</code> | |
| <code>\box_gset_to_last:c</code> | |

6 Constant boxes

`\c_empty_box`

Updated: 2012-11-04

This is a permanently empty box, which is neither set as horizontal nor vertical.

7 Scratch boxes

`\l_tmpa_box`

`\l_tmpb_box`

Updated: 2012-11-04

Scratch boxes for local assignment. These are never used by the kernel code, and so are safe for use with any L^AT_EX3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.

`\g_tmpa_box`

`\g_tmpb_box`

Scratch boxes for global assignment. These are never used by the kernel code, and so are safe for use with any L^AT_EX3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.

8 Viewing box contents

`\box_show:N`

`\box_show:c`

Updated: 2012-05-11

`\box_show:N` $\langle box \rangle$

Shows full details of the content of the $\langle box \rangle$ in the terminal.

`\box_show:Nnn`

`\box_show:cnn`

New: 2012-05-11

`\box_show:Nnn` $\langle box \rangle$ $\langle intexpr_1 \rangle$ $\langle intexpr_2 \rangle$

Display the contents of $\langle box \rangle$ in the terminal, showing the first $\langle intexpr_1 \rangle$ items of the box, and descending into $\langle intexpr_2 \rangle$ group levels.

`\box_log:N`

`\box_log:c`

New: 2012-05-11

`\box_log:N` $\langle box \rangle$

Writes full details of the content of the $\langle box \rangle$ to the log.

`\box_log:Nnn`

`\box_log:cnn`

New: 2012-05-11

`\box_log:Nnn` $\langle box \rangle$ $\langle intexpr_1 \rangle$ $\langle intexpr_2 \rangle$

Writes the contents of $\langle box \rangle$ to the log, showing the first $\langle intexpr_1 \rangle$ items of the box, and descending into $\langle intexpr_2 \rangle$ group levels.

9 Horizontal mode boxes

`\hbox:n`

`\hbox:n` $\{ \langle contents \rangle \}$

Typesets the $\langle contents \rangle$ into a horizontal box of natural width and then includes this box in the current list for typesetting.

| | |
|---|--|
| <hr/> <code>\hbox_to_wd:nn</code> <hr/> | <code>\hbox_to_wd:nn {<dimexpr>} {<contents>}</code> Typesets the $\langle contents \rangle$ into a horizontal box of width $\langle dimexpr \rangle$ and then includes this box in the current list for typesetting. |
| <hr/> <code>\hbox_to_zero:n</code> <hr/> | <code>\hbox_to_zero:n {<contents>}</code> Typesets the $\langle contents \rangle$ into a horizontal box of zero width and then includes this box in the current list for typesetting. |
| <hr/> <code>\hbox_set:Nn</code> <code>\hbox_set:cn</code> <code>\hbox_gset:Nn</code> <code>\hbox_gset:cn</code> <hr/> | <code>\hbox_set:Nn <box> {<contents>}</code> Typesets the $\langle contents \rangle$ at natural width and then stores the result inside the $\langle box \rangle$. |
| <hr/> <code>\hbox_set_to_wd:Nnn</code> <code>\hbox_set_to_wd:cnn</code> <code>\hbox_gset_to_wd:Nnn</code> <code>\hbox_gset_to_wd:cnn</code> <hr/> | <code>\hbox_set_to_wd:Nnn <box> {<dimexpr>} {<contents>}</code> Typesets the $\langle contents \rangle$ to the width given by the $\langle dimexpr \rangle$ and then stores the result inside the $\langle box \rangle$. |
| <hr/> <code>\hbox_overlap_right:n</code> <hr/> | <code>\hbox_overlap_right:n {<contents>}</code> Typesets the $\langle contents \rangle$ into a horizontal box of zero width such that material will protrude to the right of the insertion point. |
| <hr/> <code>\hbox_overlap_left:n</code> <hr/> | <code>\hbox_overlap_left:n {<contents>}</code> Typesets the $\langle contents \rangle$ into a horizontal box of zero width such that material will protrude to the left of the insertion point. |
| <hr/> <code>\hbox_set:Nw</code> <code>\hbox_set:cw</code> <code>\hbox_set_end:</code> <code>\hbox_gset:Nw</code> <code>\hbox_gset:cw</code> <code>\hbox_gset_end:</code> <hr/> | <code>\hbox_set:Nw <box> <contents> \hbox_set_end:</code> Typesets the $\langle contents \rangle$ at natural width and then stores the result inside the $\langle box \rangle$. In contrast to <code>\hbox_set:Nn</code> this function does not absorb the argument when finding the $\langle content \rangle$, and so can be used in circumstances where the $\langle content \rangle$ may not be a simple argument. |
| <hr/> <code>\hbox_unpack:N</code> <code>\hbox_unpack:c</code> <hr/> | <code>\hbox_unpack:N <box></code> Unpacks the content of the horizontal $\langle box \rangle$, retaining any stretching or shrinking applied when the $\langle box \rangle$ was set. |
| <hr/> <code>\hbox_unpack_clear:N</code> <code>\hbox_unpack_clear:c</code> <hr/> | <code>\hbox_unpack_clear:N <box></code> Unpacks the content of the horizontal $\langle box \rangle$, retaining any stretching or shrinking applied when the $\langle box \rangle$ was set. The $\langle box \rangle$ is then cleared globally. |

TeXhackers note: This is the TeX primitive `\unhcopy`.

TeXhackers note: This is the TeX primitive `\unhbox`.

10 Vertical mode boxes

Vertical boxes inherit their baseline from their contents. The standard case is that the baseline of the box is at the same position as that of the last item added to the box. This means that the box will have no depth unless the last item added to it had depth. As a result most vertical boxes have a large height value and small or zero depth. The exception are `_top` boxes, where the reference point is that of the first item added. These tend to have a large depth and small height, although the latter will typically be non-zero.

`\vbox:n`

`\vbox:n {\langle contents \rangle}`

Updated: 2011-12-18

Typesets the $\langle contents \rangle$ into a vertical box of natural height and includes this box in the current list for typesetting.

T_EXhackers note: This is the T_EX primitive `\vbox`.

`\vbox_top:n`

`\vbox_top:n {\langle contents \rangle}`

Updated: 2011-12-18

Typesets the $\langle contents \rangle$ into a vertical box of natural height and includes this box in the current list for typesetting. The baseline of the box will be equal to that of the *first* item added to the box.

T_EXhackers note: This is the T_EX primitive `\vtop`.

`\vbox_to_ht:nn`

`\vbox_to_ht:nn {\langle dimexpr \rangle} {\langle contents \rangle}`

Updated: 2011-12-18

Typesets the $\langle contents \rangle$ into a vertical box of height $\langle dimexpr \rangle$ and then includes this box in the current list for typesetting.

`\vbox_to_zero:n`

`\vbox_to_zero:n {\langle contents \rangle}`

Updated: 2011-12-18

Typesets the $\langle contents \rangle$ into a vertical box of zero height and then includes this box in the current list for typesetting.

`\vbox_set:Nn`

`\vbox_set:Nn \langle box \rangle {\langle contents \rangle}`
`\vbox_set:cn`
`\vbox_gset:Nn`
`\vbox_gset:cn`

Updated: 2011-12-18

Typesets the $\langle contents \rangle$ at natural height and then stores the result inside the $\langle box \rangle$.

`\vbox_set_top:Nn`

`\vbox_set_top:Nn \langle box \rangle {\langle contents \rangle}`
`\vbox_set_top:cn`
`\vbox_gset_top:Nn`
`\vbox_gset_top:cn`

Updated: 2011-12-18

Typesets the $\langle contents \rangle$ at natural height and then stores the result inside the $\langle box \rangle$. The baseline of the box will be equal to that of the *first* item added to the box.

`\vbox_set_to_ht:Nnn`

`\vbox_set_to_ht:Nnn \langle box \rangle {\langle dimexpr \rangle} {\langle contents \rangle}`
`\vbox_set_to_ht:cnn`
`\vbox_gset_to_ht:Nnn`
`\vbox_gset_to_ht:cnn`

Updated: 2011-12-18

Typesets the $\langle contents \rangle$ to the height given by the $\langle dimexpr \rangle$ and then stores the result inside the $\langle box \rangle$.

```
\vbox_set:Nw
\vbox_set:cw
\vbox_set_end:
\vbox_gset:Nw
\vbox_gset:cw
\vbox_gset_end:
```

Updated: 2011-12-18

```
\vbox_set:Nw <box> <contents> \vbox_set_end:
```

Typesets the $\langle contents \rangle$ at natural height and then stores the result inside the $\langle box \rangle$. In contrast to $\backslash\text{vbox_set:Nn}$ this function does not absorb the argument when finding the $\langle content \rangle$, and so can be used in circumstances where the $\langle content \rangle$ may not be a simple argument.

```
\vbox_set_split_to_ht:NNn
```

Updated: 2011-10-22

```
\vbox_set_split_to_ht:NNn <box1> <box2> {<dimexpr>}
```

Sets $\langle box_1 \rangle$ to contain material to the height given by the $\langle dimexpr \rangle$ by removing content from the top of $\langle box_2 \rangle$ (which must be a vertical box).

T_EXhackers note: This is the T_EX primitive $\backslash\text{vsplit}$.

```
\vbox_unpack:N
\vbox_unpack:c
```

```
\vbox_unpack:N <box>
```

Unpacks the content of the vertical $\langle box \rangle$, retaining any stretching or shrinking applied when the $\langle box \rangle$ was set.

T_EXhackers note: This is the T_EX primitive $\backslash\text{unvcopy}$.

```
\vbox_unpack_clear:N
\vbox_unpack_clear:c
```

```
\vbox_unpack:N <box>
```

Unpacks the content of the vertical $\langle box \rangle$, retaining any stretching or shrinking applied when the $\langle box \rangle$ was set. The $\langle box \rangle$ is then cleared globally.

T_EXhackers note: This is the T_EX primitive $\backslash\text{unvbox}$.

11 Primitive box conditionals

```
\if_hbox:N ★
```

```
\if_hbox:N <box>
  <true code>
\else:
  <false code>
\fi:
```

Tests if $\langle box \rangle$ is a horizontal box.

T_EXhackers note: This is the T_EX primitive $\backslash\text{ifhbox}$.

```
\if_vbox:N ★
```

```
\if_vbox:N <box>
  <true code>
\else:
  <false code>
\fi:
```

Tests if $\langle box \rangle$ is a vertical box.

T_EXhackers note: This is the T_EX primitive $\backslash\text{ifvbox}$.

`\if_box_empty:N` ★

```
\if_box_empty:N <box>
  <true code>
\else:
  <false code>
\fi:
```

Tests if `<box>` is an empty (void) box.

TeXhackers note: This is the TeX primitive `\ifvoid`.

Part XXIII

The l3coffins package

Coffin code layer

The material in this module provides the low-level support system for coffins. For details about the design concept of a coffin, see the xcoffins module (in the l3experimental bundle).

1 Creating and initialising coffins

| |
|----------------------------|
| <code>\coffin_new:N</code> |
| <code>\coffin_new:c</code> |
| New: 2011-08-17 |

`\coffin_new:N` $\langle coffin \rangle$

Creates a new $\langle coffin \rangle$ or raises an error if the name is already taken. The declaration is global. The $\langle coffin \rangle$ will initially be empty.

| |
|------------------------------|
| <code>\coffin_clear:N</code> |
| <code>\coffin_clear:c</code> |
| New: 2011-08-17 |

`\coffin_clear:N` $\langle coffin \rangle$

Clears the content of the $\langle coffin \rangle$ within the current T_EX group level.

| |
|--|
| <code>\coffin_set_eq:NN</code> |
| <code>\coffin_set_eq:(Nc cN cc)</code> |
| New: 2011-08-17 |

`\coffin_set_eq:NN` $\langle coffin_1 \rangle$ $\langle coffin_2 \rangle$

Sets both the content and poles of $\langle coffin_1 \rangle$ equal to those of $\langle coffin_2 \rangle$ within the current T_EX group level.

| |
|-------------------------------------|
| <code>\coffin_if_exist_p:N</code> ★ |
| <code>\coffin_if_exist_p:c</code> ★ |
| <code>\coffin_if_exist:NTF</code> ★ |
| <code>\coffin_if_exist:cTF</code> ★ |
| New: 2012-06-20 |

`\coffin_if_exist_p:N` $\langle box \rangle$

`\coffin_if_exist:NTF` $\langle box \rangle$ $\{\langle true\ code \rangle\}$ $\{\langle false\ code \rangle\}$

Tests whether the $\langle coffin \rangle$ is currently defined.

2 Setting coffin content and poles

All coffin functions create and manipulate coffins locally within the current T_EX group level.

| |
|------------------------------|
| <code>\hcoffin_set:Nn</code> |
| <code>\hcoffin_set:cn</code> |
| New: 2011-08-17 |
| Updated: 2011-09-03 |

`\hcoffin_set:Nn` $\langle coffin \rangle$ $\{\langle material \rangle\}$

Typesets the $\langle material \rangle$ in horizontal mode, storing the result in the $\langle coffin \rangle$. The standard poles for the $\langle coffin \rangle$ are then set up based on the size of the typeset material.

| |
|--------------------------------|
| <code>\hcoffin_set:Nw</code> |
| <code>\hcoffin_set:cw</code> |
| <code>\hcoffin_set_end:</code> |
| New: 2011-09-10 |

`\hcoffin_set:Nw` $\langle coffin \rangle$ $\langle material \rangle$ `\hcoffin_set_end:`

Typesets the $\langle material \rangle$ in horizontal mode, storing the result in the $\langle coffin \rangle$. The standard poles for the $\langle coffin \rangle$ are then set up based on the size of the typeset material. These functions are useful for setting the entire contents of an environment in a coffin.

```
\vcoffin_set:Nnn
\vcoffin_set:cnn
```

New: 2011-08-17
Updated: 2012-05-22

```
\vcoffin_set:Nnn <coffin> {\<width>} {\<material>}
```

Typesets the $\langle material \rangle$ in vertical mode constrained to the given $\langle width \rangle$ and stores the result in the $\langle coffin \rangle$. The standard poles for the $\langle coffin \rangle$ are then set up based on the size of the typeset material.

```
\vcoffin_set:Nnw
\vcoffin_set:cnnw
\vcoffin_set_end:
```

New: 2011-09-10
Updated: 2012-05-22

```
\vcoffin_set:Nnw <coffin> {\<width>} <material> \vcoffin_set_end:
```

Typesets the $\langle material \rangle$ in vertical mode constrained to the given $\langle width \rangle$ and stores the result in the $\langle coffin \rangle$. The standard poles for the $\langle coffin \rangle$ are then set up based on the size of the typeset material. These functions are useful for setting the entire contents of an environment in a coffin.

```
\coffin_set_horizontal_pole:Nnn \coffin_set_horizontal_pole:Nnn <coffin>
\coffin_set_horizontal_pole:cnn {\<pole>} {\<offset>}
```

New: 2012-07-20

Sets the $\langle pole \rangle$ to run horizontally through the $\langle coffin \rangle$. The $\langle pole \rangle$ will be located at the $\langle offset \rangle$ from the bottom edge of the bounding box of the $\langle coffin \rangle$. The $\langle offset \rangle$ should be given as a dimension expression.

```
\coffin_set_vertical_pole:Nnn \coffin_set_vertical_pole:Nnn <coffin> {\<pole>} {\<offset>}
\coffin_set_vertical_pole:cnn
```

New: 2012-07-20

Sets the $\langle pole \rangle$ to run vertically through the $\langle coffin \rangle$. The $\langle pole \rangle$ will be located at the $\langle offset \rangle$ from the left-hand edge of the bounding box of the $\langle coffin \rangle$. The $\langle offset \rangle$ should be given as a dimension expression.

3 Joining and using coffins

```
\coffin_attach:NnnNnnnn
\coffin_attach:(cnnNnnnn|NnnNnnnn|cnnNnnnn)
```

```
\coffin_attach:NnnNnnnn
<coffin1> {\<coffin1-pole1>} {\<coffin1-pole2>}
<coffin2> {\<coffin2-pole1>} {\<coffin2-pole2>}
{\<x-offset>} {\<y-offset>}
```

This function attaches $\langle coffin_2 \rangle$ to $\langle coffin_1 \rangle$ such that the bounding box of $\langle coffin_1 \rangle$ is not altered, *i.e.* $\langle coffin_2 \rangle$ can protrude outside of the bounding box of the coffin. The alignment is carried out by first calculating $\langle handle_1 \rangle$, the point of intersection of $\langle coffin_1-pole_1 \rangle$ and $\langle coffin_1-pole_2 \rangle$, and $\langle handle_2 \rangle$, the point of intersection of $\langle coffin_2-pole_1 \rangle$ and $\langle coffin_2-pole_2 \rangle$. $\langle coffin_2 \rangle$ is then attached to $\langle coffin_1 \rangle$ such that the relationship between $\langle handle_1 \rangle$ and $\langle handle_2 \rangle$ is described by the $\langle x-offset \rangle$ and $\langle y-offset \rangle$. The two offsets should be given as dimension expressions.

```
\coffin_join:NnnNnnnn
\coffin_join:(cnnNnnnn|Nnnncnnnn|cnnncnnnn)
```

```
\coffin_join:NnnNnnnn
  <coffin_1> {<coffin_1-pole_1>} {<coffin_1-pole_2>}
  <coffin_2> {<coffin_2-pole_1>} {<coffin_2-pole_2>}
  {<x-offset>} {<y-offset>}
```

This function joins $\langle coffin_2 \rangle$ to $\langle coffin_1 \rangle$ such that the bounding box of $\langle coffin_1 \rangle$ may expand. The new bounding box will cover the area containing the bounding boxes of the two original coffins. The alignment is carried out by first calculating $\langle handle_1 \rangle$, the point of intersection of $\langle coffin_1-pole_1 \rangle$ and $\langle coffin_1-pole_2 \rangle$, and $\langle handle_2 \rangle$, the point of intersection of $\langle coffin_2-pole_1 \rangle$ and $\langle coffin_2-pole_2 \rangle$. $\langle coffin_2 \rangle$ is then attached to $\langle coffin_1 \rangle$ such that the relationship between $\langle handle_1 \rangle$ and $\langle handle_2 \rangle$ is described by the $\langle x-offset \rangle$ and $\langle y-offset \rangle$. The two offsets should be given as dimension expressions.

```
\coffin_typeset:Nnnnn
\coffin_typeset:cnnnn
```

Updated: 2012-07-20

```
\coffin_typeset:Nnnnn <coffin> {<pole_1>} {<pole_2>}
  {<x-offset>} {<y-offset>}
```

Typesetting is carried out by first calculating $\langle handle \rangle$, the point of intersection of $\langle pole_1 \rangle$ and $\langle pole_2 \rangle$. The coffin is then typeset in horizontal mode such that the relationship between the current reference point in the document and the $\langle handle \rangle$ is described by the $\langle x-offset \rangle$ and $\langle y-offset \rangle$. The two offsets should be given as dimension expressions. Typesetting a coffin is therefore analogous to carrying out an alignment where the “parent” coffin is the current insertion point.

4 Measuring coffins

```
\coffin_dp:N
\coffin_dp:c
```

```
\coffin_dp:N <coffin>
```

Calculates the depth (below the baseline) of the $\langle coffin \rangle$ in a form suitable for use in a $\langle dimension expression \rangle$.

```
\coffin_ht:N
\coffin_ht:c
```

```
\coffin_ht:N <coffin>
```

Calculates the height (above the baseline) of the $\langle coffin \rangle$ in a form suitable for use in a $\langle dimension expression \rangle$.

```
\coffin_wd:N
\coffin_wd:c
```

```
\coffin_wd:N <coffin>
```

Calculates the width of the $\langle coffin \rangle$ in a form suitable for use in a $\langle dimension expression \rangle$.

5 Coffin diagnostics

```
\coffin_display_handles:Nn
\coffin_display_handles:cn
```

Updated: 2011-09-02

```
\coffin_display_handles:Nn <coffin> {<color>}
```

This function first calculates the intersections between all of the $\langle poles \rangle$ of the $\langle coffin \rangle$ to give a set of $\langle handles \rangle$. It then prints the $\langle coffin \rangle$ at the current location in the source, with the position of the $\langle handles \rangle$ marked on the coffin. The $\langle handles \rangle$ will be labelled as part of this process: the locations of the $\langle handles \rangle$ and the labels are both printed in the $\langle color \rangle$ specified.

`\coffin_mark_handle:Nnnn`
`\coffin_mark_handle:cnnn`

Updated: 2011-09-02

`\coffin_mark_handle:Nnnn` $\langle coffin \rangle$ $\{\langle pole_1 \rangle\}$ $\{\langle pole_2 \rangle\}$ $\{\langle color \rangle\}$

This function first calculates the $\langle handle \rangle$ for the $\langle coffin \rangle$ as defined by the intersection of $\langle pole_1 \rangle$ and $\langle pole_2 \rangle$. It then marks the position of the $\langle handle \rangle$ on the $\langle coffin \rangle$. The $\langle handle \rangle$ will be labelled as part of this process: the location of the $\langle handle \rangle$ and the label are both printed in the $\langle color \rangle$ specified.

`\coffin_show_structure:N`
`\coffin_show_structure:c`

Updated: 2015-08-01

`\coffin_show_structure:N` $\langle coffin \rangle$

This function shows the structural information about the $\langle coffin \rangle$ in the terminal. The width, height and depth of the typeset material are given, along with the location of all of the poles of the coffin.

Notice that the poles of a coffin are defined by four values: the x and y co-ordinates of a point that the pole passes through and the x - and y -components of a vector denoting the direction of the pole. It is the ratio between the later, rather than the absolute values, which determines the direction of the pole.

`\coffin_log_structure:N`
`\coffin_log_structure:c`

New: 2014-08-22
Updated: 2015-08-01

`\coffin_log_structure:N` $\langle coffin \rangle$

This function writes the structural information about the $\langle coffin \rangle$ in the log file. See also `\coffin_show_structure:N` which displays the result in the terminal.

5.1 Constants and variables

`\c_empty_coffin`

A permanently empty coffin.

`\l_tmpa_coffin`
`\l_tmpb_coffin`

New: 2012-06-19

Scratch coffins for local assignment. These are never used by the kernel code, and so are safe for use with any L^AT_EX3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.

Part XXIV

The **l3color** package

Color support

This module provides support for color in L^AT_EX3. At present, the material here is mainly intended to support a small number of low-level requirements in other **l3kernel** modules.

1 Color in boxes

Controlling the color of text in boxes requires a small number of control functions, so that the boxed material uses the color at the point where it is set, rather than where it is used.

\color_group_begin:
\color_group_end:

New: 2011-09-03

\color_group_begin:
...
\color_group_end:

Creates a color group: one used to “trap” color settings.

\color_ensure_current:

New: 2011-09-03

\color_ensure_current:

Ensures that material inside a box will use the foreground color at the point where the box is set, rather than that in force when the box is used. This function should usually be used within a **\color_group_begin: ... \color_group_end:** group.

Part XXV

The l3sys package

System/runtime functions

1 The name of the job

`\c_sys_jobname_str`

New: 2015-09-19

Constant that gets the “job name” assigned when T_EX starts.

T_EXhackers note: This copies the contents of the primitive `\jobname`. It is a constant that is set by T_EX and should not be overwritten by the package.

2 Date and time

`\c_sys_minute_int`
`\c_sys_hour_int`
`\c_sys_day_int`
`\c_sys_month_int`
`\c_sys_year_int`

New: 2015-09-22

The date and time at which the current job was started: these are all reported as integers.

T_EXhackers note: Whilst the underlying primitives can be altered by the user, this interface to the time and date is intended to be the “real” values.

3 Engine

`\sys_if_engine luatex_p:` ★
`\sys_if_engine luatex:` *TF* ★
`\sys_if_engine pdftex_p:` ★
`\sys_if_engine pdftex:` *TF* ★
`\sys_if_engine ptex_p:` ★
`\sys_if_engine ptex:` *TF* ★
`\sys_if_engine uptex_p:` ★
`\sys_if_engine uptex:` *TF* ★
`\sys_if_engine xetex_p:` ★
`\sys_if_engine xetex:` *TF* ★

New: 2015-09-07

`\sys_if_engine pdftex:TF` *{(true code)}* *{(false code)}*

Conditionals which allow engine-specific code to be used. The names follow naturally from those of the engine binaries: note that the (u)pt_EX tests are for ε -pT_EX and ε -upT_EX as expl3 requires the ε -T_EX extensions. Each conditional is true for *exactly one* supported engine. In particular, `\sys_if_engine ptex_p:` is true for ε -pT_EX but false for ε -upT_EX.

`\c_sys_engine_str`

New: 2015-09-19

The current engine given as a lower case string: will be one of `luatex`, `pdftex`, `ptex`, `uptex` or `xetex`.

4 Output format

| | | | | |
|------------------------------------|-----------|------------------------------------|---------------------------|----------------------------|
| <code>\sys_if_output_dvi_p:</code> | ★ | <code>\sys_if_output_dvi:TF</code> | <code>{\true code}</code> | <code>{\false code}</code> |
| <code>\sys_if_output_dvi:</code> | <u>TF</u> | ★ | | |
| <code>\sys_if_output_pdf_p:</code> | ★ | | | |
| <code>\sys_if_output_pdf:</code> | <u>TF</u> | ★ | | |

New: 2015-09-19

Conditionals which give the current output mode the T_EX run is operating in. This will always be one of two outcomes, DVI mode or PDF mode. The two sets of conditionals are thus complementary and are both provided to allow the programmer to emphasise the most appropriate case.

| |
|--------------------------------|
| <code>\c_sys_output_str</code> |
|--------------------------------|

New: 2015-09-19

The current output mode given as a lower case string: will be one of `dvi` or `pdf`.

Part XXVI

The l3deprecation package

Deprecation errors

1 l3deprecation documentation

A few commands have had to be deprecated over the years. This module defines deprecated and deleted commands to produce an error.

`\deprecation_error:` Defines commands that will soon become deprecated to produce errors.

(End definition for `\deprecation_error`:. This function is documented on page ??.)

Part XXVII

The l3candidates package

Experimental additions to l3kernel

1 Important notice

This module provides a space in which functions can be added to l3kernel (expl3) while still being experimental.

As such, the functions here may not remain in their current form, or indeed at all, in l3kernel in the future.

In contrast to the material in l3experimental, the functions here are all *small* additions to the kernel. We encourage programmers to test them out and report back on the LaTeX-L mailing list.

Thus, if you intend to use any of these functions from the candidate module in a public package offered to others for productive use (e.g., being placed on CTAN) please consider the following points carefully:

- Be prepared that your public packages might require updating when such functions are being finalized.
- Consider informing us that you use a particular function in your public package, e.g., by discussing this on the LaTeX-L mailing list. This way it becomes easier to coordinate any updates necessary without issues for the users of your package.
- Discussing and understanding use cases for a particular addition or concept also helps to ensure that we provide the right interfaces in the final version so please give us feedback if you consider a certain candidate function useful (or not).

We only add functions in this space if we consider them being serious candidates for a final inclusion into the kernel. However, real use sometimes leads to better ideas, so functions from this module are **not necessarily stable** and we may have to adjust them!

2 Additions to l3box

2.1 Affine transformations

Affine transformations are changes which (informally) preserve straight lines. Simple translations are affine transformations, but are better handled in T_EX by doing the translation first, then inserting an unmodified box. On the other hand, rotation and resizing of boxed material can best be handled by modifying boxes. These transformations are described here.

| | |
|------------------------------|--|
| <code>\box_resize:Nnn</code> | <code>\box_resize:Nnn <box> {<x-size>} {<y-size>}</code> |
| <code>\box_resize:cnn</code> | |

Resize the $\langle box \rangle$ to $\langle x-size \rangle$ horizontally and $\langle y-size \rangle$ vertically (both of the sizes are dimension expressions). The $\langle y-size \rangle$ is the vertical size (height plus depth) of the box. The updated $\langle box \rangle$ will be an hbox, irrespective of the nature of the $\langle box \rangle$ before the resizing is applied. Negative sizes will cause the material in the $\langle box \rangle$ to be reversed in direction, but the reference point of the $\langle box \rangle$ will be unchanged. Thus negative y -sizes will result in a box a depth dependent on the height of the original box a height dependent on the depth. The resizing applies within the current \TeX group level.

| | |
|---|--|
| <code>\box_resize_to_ht_plus_dp:Nn</code> | <code>\box_resize_to_ht_plus_dp:Nn <box> {<y-size>}</code> |
| <code>\box_resize_to_ht_plus_dp:cn</code> | |

Resize the $\langle box \rangle$ to $\langle y-size \rangle$ vertically, scaling the horizontal size by the same amount ($\langle y-size \rangle$ is a dimension expression). The $\langle y-size \rangle$ is the vertical size (height plus depth) of the box. The updated $\langle box \rangle$ will be an hbox, irrespective of the nature of the $\langle box \rangle$ before the resizing is applied. A negative size will cause the material in the $\langle box \rangle$ to be reversed in direction, but the reference point of the $\langle box \rangle$ will be unchanged. Thus negative y -sizes will result in a box with depth dependent on the height of the original box and height dependent on the depth of the original. The resizing applies within the current \TeX group level.

| | |
|-----------------------------------|--|
| <code>\box_resize_to_ht:Nn</code> | <code>\box_resize_to_ht:Nn <box> {<y-size>}</code> |
| <code>\box_resize_to_ht:cn</code> | |

Resize the $\langle box \rangle$ to $\langle y-size \rangle$ vertically, scaling the horizontal size by the same amount ($\langle y-size \rangle$ is a dimension expression). The $\langle y-size \rangle$ is the height only, not including depth, of the box. The updated $\langle box \rangle$ will be an hbox, irrespective of the nature of the $\langle box \rangle$ before the resizing is applied. A negative size will cause the material in the $\langle box \rangle$ to be reversed in direction, but the reference point of the $\langle box \rangle$ will be unchanged. Thus negative y -sizes will result in a box with depth dependent on the height of the original box and height dependent on the depth of the original. The resizing applies within the current \TeX group level.

| | |
|-----------------------------------|--|
| <code>\box_resize_to_wd:Nn</code> | <code>\box_resize_to_wd:Nn <box> {<x-size>}</code> |
| <code>\box_resize_to_wd:cn</code> | |

Resize the $\langle box \rangle$ to $\langle x-size \rangle$ horizontally, scaling the vertical size by the same amount ($\langle x-size \rangle$ is a dimension expression). The updated $\langle box \rangle$ will be an hbox, irrespective of the nature of the $\langle box \rangle$ before the resizing is applied. A negative size will cause the material in the $\langle box \rangle$ to be reversed in direction, but the reference point of the $\langle box \rangle$ will be unchanged. Thus negative y -sizes will result in a box a depth dependent on the height of the original box a height dependent on the depth. The resizing applies within the current \TeX group level.

| | |
|---|---|
| <code>\box_resize_to_wd_and_ht:Nnn</code> | <code>\box_resize_to_wd_and_ht:Nnn <box> {<x-size>} {<y-size>}</code> |
| <code>\box_resize_to_wd_and_ht:cnn</code> | |

New: 2014-07-03

Resize the $\langle box \rangle$ to a *height* of $\langle x-size \rangle$ horizontally and $\langle y-size \rangle$ vertically (both of the sizes are dimension expressions). The $\langle y-size \rangle$ is the *height* of the box, ignoring any depth. The updated $\langle box \rangle$ will be an hbox, irrespective of the nature of the $\langle box \rangle$ before the resizing is applied. Negative sizes will cause the material in the $\langle box \rangle$ to be reversed in direction, but the reference point of the $\langle box \rangle$ will be unchanged.

| | |
|-----------------------------|---|
| <code>\box_rotate:Nn</code> | <code>\box_rotate:Nn <box> {<angle>}</code> |
| <code>\box_rotate:cn</code> | Rotates the $\langle box \rangle$ by $\langle angle \rangle$ (in degrees) anti-clockwise about its reference point. The reference point of the updated box will be moved horizontally such that it is at the left side of the smallest rectangle enclosing the rotated material. The updated $\langle box \rangle$ will be an hbox, irrespective of the nature of the $\langle box \rangle$ before the rotation is applied. The rotation applies within the current T _E X group level. |

| | |
|-----------------------------|--|
| <code>\box_scale:Nnn</code> | <code>\box_scale:Nnn <box> {<x-scale>} {<y-scale>}</code> |
| <code>\box_scale:cnn</code> | Scales the $\langle box \rangle$ by factors $\langle x-scale \rangle$ and $\langle y-scale \rangle$ in the horizontal and vertical directions, respectively (both scales are integer expressions). The updated $\langle box \rangle$ will be an hbox, irrespective of the nature of the $\langle box \rangle$ before the scaling is applied. Negative scalings will cause the material in the $\langle box \rangle$ to be reversed in direction, but the reference point of the $\langle box \rangle$ will be unchanged. Thus negative y -scales will result in a box a depth dependent on the height of the original box a height dependent on the depth. The resizing applies within the current T _E X group level. |

2.2 Viewing part of a box

| | |
|--------------------------|--|
| <code>\box_clip:N</code> | <code>\box_clip:N <box></code> |
| <code>\box_clip:c</code> | Clips the $\langle box \rangle$ in the output so that only material inside the bounding box is displayed in the output. The updated $\langle box \rangle$ will be an hbox, irrespective of the nature of the $\langle box \rangle$ before the clipping is applied. The clipping applies within the current T _E X group level. |

These functions require the L^AT_EX3 native drivers: they will not work with the L^AT_EX 2_ε graphics drivers!

T_EXhackers note: Clipping is implemented by the driver, and as such the full content of the box is placed in the output file. Thus clipping does not remove any information from the raw output, and hidden material can therefore be viewed by direct examination of the file.

| | |
|------------------------------|--|
| <code>\box_trim:Nnnnn</code> | <code>\box_trim:Nnnnn <box> {<left>} {<bottom>} {<right>} {<top>}</code> |
| <code>\box_trim:cnnnn</code> | Adjusts the bounding box of the $\langle box \rangle$ $\langle left \rangle$ is removed from the left-hand edge of the bounding box, $\langle right \rangle$ from the right-hand edge and so fourth. All adjustments are $\langle dimension expressions \rangle$. Material output of the bounding box will still be displayed in the output unless <code>\box_clip:N</code> is subsequently applied. The updated $\langle box \rangle$ will be an hbox, irrespective of the nature of the $\langle box \rangle$ before the trim operation is applied. The adjustment applies within the current T _E X group level. The behavior of the operation where the trims requested is greater than the size of the box is undefined. |

| | |
|----------------------------------|---|
| <code>\box_viewport:Nnnnn</code> | <code>\box_viewport:Nnnnn <box> {<llx>} {<lly>} {<urx>} {<ury>}</code> |
| <code>\box_viewport:cnnnn</code> | Adjusts the bounding box of the $\langle box \rangle$ such that it has lower-left co-ordinates ($\langle llx \rangle$, $\langle lly \rangle$) and upper-right co-ordinates ($\langle urx \rangle$, $\langle ury \rangle$). All four co-ordinate positions are $\langle dimension expressions \rangle$. Material output of the bounding box will still be displayed in the output unless <code>\box_clip:N</code> is subsequently applied. The updated $\langle box \rangle$ will be an hbox, irrespective of the nature of the $\langle box \rangle$ before the viewport operation is applied. The adjustment applies within the current T _E X group level. |

3 Additions to l3clist

| | |
|-----------------------------------|---|
| <code>\clist_rand_item:N</code> ★ | <code>\clist_rand_item:N</code> $\langle\textit{clist var}\rangle$ |
| <code>\clist_rand_item:c</code> ★ | <code>\clist_rand_item:n</code> $\{\langle\textit{comma list}\rangle\}$ |
| <code>\clist_rand_item:n</code> ★ | Selects a pseudo-random item of the $\langle\textit{comma list}\rangle$. If the $\langle\textit{comma list}\rangle$ has no item, the result is empty. This is only available in pdfTeX and LuaTeX. |

New: 2016-12-06

TeXhackers note: The result is returned within the `\unexpanded` primitive (`\exp_not:n`), which means that the $\langle\textit{item}\rangle$ will not expand further when appearing in an x-type argument expansion.

4 Additions to l3coffins

| | |
|---------------------------------|---|
| <code>\coffin_resize:Nnn</code> | <code>\coffin_resize:Nnn</code> $\langle\textit{coffin}\rangle$ $\{\langle\textit{width}\rangle\}$ $\{\langle\textit{total-height}\rangle\}$ |
| <code>\coffin_resize:cnn</code> | Resized the $\langle\textit{coffin}\rangle$ to $\langle\textit{width}\rangle$ and $\langle\textit{total-height}\rangle$, both of which should be given as dimension expressions. |

| | |
|--------------------------------|---|
| <code>\coffin_rotate:Nn</code> | <code>\coffin_rotate:Nn</code> $\langle\textit{coffin}\rangle$ $\{\langle\textit{angle}\rangle\}$ |
| <code>\coffin_rotate:cn</code> | Rotates the $\langle\textit{coffin}\rangle$ by the given $\langle\textit{angle}\rangle$ (given in degrees counter-clockwise). This process will rotate both the coffin content and poles. Multiple rotations will not result in the bounding box of the coffin growing unnecessarily. |

| | |
|--------------------------------|---|
| <code>\coffin_scale:Nnn</code> | <code>\coffin_scale:Nnn</code> $\langle\textit{coffin}\rangle$ $\{\langle\textit{x-scale}\rangle\}$ $\{\langle\textit{y-scale}\rangle\}$ |
| <code>\coffin_scale:cnn</code> | Scales the $\langle\textit{coffin}\rangle$ by a factors $\langle\textit{x-scale}\rangle$ and $\langle\textit{y-scale}\rangle$ in the horizontal and vertical directions, respectively. The two scale factors should be given as real numbers. |

5 Additions to l3file

| | |
|---------------------------------------|---|
| <code>\file_if_exist_input:nTF</code> | <code>\file_if_exist_input:n</code> $\{\langle\textit{file name}\rangle\}$ |
| | <code>\file_if_exist_input:nTF</code> $\{\langle\textit{file name}\rangle\}$ $\{\langle\textit{true code}\rangle\}$ $\{\langle\textit{false code}\rangle\}$ |
| New: 2014-07-02 | Searches for $\langle\textit{file name}\rangle$ using the current TeX search path and the additional paths controlled by <code>\file_path_include:n</code> . If found, inserts the $\langle\textit{true code}\rangle$ then reads in the file as additional L ^A T _E X source as described for <code>\file_input:n</code> . Note that <code>\file_if_exist_input:n</code> does not raise an error if the file is not found, in contrast to <code>\file_input:n</code> . |

| | |
|---------------------------------|---|
| <code>\ior_map_inline:Nn</code> | <code>\ior_map_inline:Nn</code> $\langle\textit{stream}\rangle$ $\{\langle\textit{inline function}\rangle\}$ |
| New: 2012-02-11 | Applies the $\langle\textit{inline function}\rangle$ to $\langle\textit{lines}\rangle$ obtained by reading one or more lines (until an equal number of left and right braces are found) from the $\langle\textit{stream}\rangle$. The $\langle\textit{inline function}\rangle$ should consist of code which will receive the $\langle\textit{line}\rangle$ as #1. Note that TeX removes trailing space and tab characters (character codes 32 and 9) from every line upon input. TeX also ignores any trailing new-line marker from the file it reads. |

| | |
|-------------------------------------|---|
| <code>\ior_str_map_inline:Nn</code> | <code>\ior_str_map_inline:Nn {<stream>} {<inline function>}</code> |
| New: 2012-02-11 | Applies the <i><inline function></i> to every <i><line></i> in the <i><stream></i> . The material is read from the <i><stream></i> as a series of tokens with category code 12 (other), with the exception of space characters which are given category code 10 (space). The <i><inline function></i> should consist of code which will receive the <i><line></i> as #1. Note that T _E X removes trailing space and tab characters (character codes 32 and 9) from every line upon input. T _E X also ignores any trailing new-line marker from the file it reads. |

| | |
|------------------------------|--|
| <code>\ior_map_break:</code> | <code>\ior_map_break:</code> |
| New: 2012-06-29 | Used to terminate a <code>\ior_map...</code> function before all lines from the <i><stream></i> have been processed. This will normally take place within a conditional statement, for example |

```

\ior_map_inline:Nn \l_my_ior
{
  \str_if_eq:nnTF { #1 } { bingo }
  { \ior_map_break: }
  {
    % Do something useful
  }
}

```

Use outside of a `\ior_map...` scenario will lead to low level T_EX errors.

T_EXhackers note: When the mapping is broken, additional tokens may be inserted by the internal macro `__prg_break_point:Nn` before further items are taken from the input stream. This will depend on the design of the mapping function.

| | |
|-------------------------------|---|
| <code>\ior_map_break:n</code> | <code>\ior_map_break:n {<tokens>}</code> |
| New: 2012-06-29 | Used to terminate a <code>\ior_map...</code> function before all lines in the <i><stream></i> have been processed, inserting the <i><tokens></i> after the mapping has ended. This will normally take place within a conditional statement, for example |

```

\ior_map_inline:Nn \l_my_ior
{
  \str_if_eq:nnTF { #1 } { bingo }
  { \ior_map_break:n { <tokens> } }
  {
    % Do something useful
  }
}

```

Use outside of a `\ior_map...` scenario will lead to low level T_EX errors.

T_EXhackers note: When the mapping is broken, additional tokens may be inserted by the internal macro `__prg_break_point:Nn` before the *<tokens>* are inserted into the input stream. This will depend on the design of the mapping function.

| | |
|--------------------------------|--|
| <code>\ior_log_streams:</code> | <code>\ior_log_streams:</code> |
| <code>\iow_log_streams:</code> | <code>\iow_log_streams:</code> |
| New: 2014-08-22 | Writes in the log file a list of the file names associated with each open stream: intended for tracking down problems. |

6 Additions to l3int

| | |
|-----------------------------|---|
| <code>\int_rand:nn</code> ★ | <code>\int_rand:nn {⟨integer expression⟩} {⟨integer expression⟩}</code> |
| New: 2016-12-06 | Evaluates the two <i>⟨integer expressions⟩</i> and produces a pseudo-random number between the two (with bounds included). This is only available in pdfTeX and LuaTeX. |

7 Additions to l3msg

In very rare cases it may be necessary to produce errors in an expansion-only context. The functions in this section should only be used if there is no alternative approach using `\msg_error:nnnnnn` or other non-expandable commands from the previous section. Despite having a similar interface as non-expandable messages, expandable errors must be handled internally very differently from normal error messages, as none of the tools to print to the terminal or the log file are expandable. As a result, the message text and arguments are not expanded, and messages must be very short (with default settings, they are truncated after approximately 50 characters). It is advisable to ensure that the message is understandable even when truncated. Another particularity of expandable messages is that they cannot be redirected or turned off by the user.

| | |
|---|---|
| <code>\msg_expandable_error:nnnnnn</code> ★ | <code>\msg_expandable_error:nnnnnn {⟨module⟩} {⟨message⟩} {⟨arg one⟩} {⟨arg two⟩} {⟨arg three⟩} {⟨arg four⟩}</code> |
| <code>\msg_expandable_error:nnffff</code> ★ | |
| <code>\msg_expandable_error:nnnnn</code> ★ | |
| <code>\msg_expandable_error:nnfff</code> ★ | |
| <code>\msg_expandable_error:nnnn</code> ★ | |
| <code>\msg_expandable_error:nnff</code> ★ | |
| <code>\msg_expandable_error:nnn</code> ★ | |
| <code>\msg_expandable_error:nnf</code> ★ | |
| <code>\msg_expandable_error:nn</code> ★ | |

New: 2015-08-06

Issues an “Undefined error” message from TeX itself using the undefined control sequence `\::error` then prints “! *⟨module⟩*: ”*⟨error message⟩*, which should be short. With default settings, anything beyond approximately 60 characters long (or bytes in some engines) is cropped. A leading space might be removed as well.

8 Additions to l3prg

Minimal (lazy) evaluation can be obtained using the conditionals `\bool_lazy_all:nTF`, `\bool_lazy_and:nTF`, `\bool_lazy_any:nTF`, or `\bool_lazy_or:nTF`, which only evaluate their boolean expression arguments when they are needed to determine the resulting truth value. For example, when evaluating the boolean expression

```

\bool_lazy_and_p:nn
{
  \bool_lazy_any_p:n
  {
    { \int_compare_p:n { 2 = 3 } }
    { \int_compare_p:n { 4 <= 4 } }
    { \int_compare_p:n { 1 = \error } } % is skipped
  }
}
{ ! \int_compare_p:n { 2 = 4 } }

```

the line marked with `is skipped` is not expanded because the result of `\bool_lazy_any_p:n` is known once the second boolean expression is found to be logically `true`. On the other hand, the last line is expanded because its logical value is needed to determine the result of `\bool_lazy_and_p:nn`.

| | |
|-----------------------------------|--|
| <code>\bool_lazy_all_p:n</code> ★ | <code>\bool_lazy_all_p:n { {<booleanexpr₁>} {<booleanexpr₂>} ... {<booleanexpr_N>} }</code> |
| <code>\bool_lazy_all:nTF</code> ★ | <code>\bool_lazy_all:nTF { {<booleanexpr₁>} {<booleanexpr₂>} ... {<booleanexpr_N>} } {<true code>} {<false code>}</code> |

New: 2015-11-15

Implements the “And” operation on the *<boolean expressions>*, hence is `true` if all of them are `true` and `false` if any of them is `false`. Contrarily to the infix operator `&&`, only the *<boolean expressions>* which are needed to determine the result of `\bool_lazy_all:nTF` will be evaluated. See also `\bool_lazy_and:nnTF` when there are only two *<boolean expressions>*.

| | |
|------------------------------------|---|
| <code>\bool_lazy_and_p:nn</code> ★ | <code>\bool_lazy_and_p:nn {<booleanexpr₁>} {<booleanexpr₂>}</code> |
| <code>\bool_lazy_and:nnTF</code> ★ | <code>\bool_lazy_and:nnTF {<booleanexpr₁>} {<booleanexpr₂>} {<true code>} {<false code>}</code> |

New: 2015-11-15

Implements the “And” operation between two boolean expressions, hence is `true` if both are `true`. Contrarily to the infix operator `&&`, the *<booleanexpr₂>* will only be evaluated if it is needed to determine the result of `\bool_lazy_and:nnTF`. See also `\bool_lazy_all:nTF` when there are more than two *<boolean expressions>*.

| | |
|-----------------------------------|--|
| <code>\bool_lazy_any_p:n</code> ★ | <code>\bool_lazy_any_p:n { {<booleanexpr₁>} {<booleanexpr₂>} ... {<booleanexpr_N>} }</code> |
| <code>\bool_lazy_any:nTF</code> ★ | <code>\bool_lazy_any:nTF { {<booleanexpr₁>} {<booleanexpr₂>} ... {<booleanexpr_N>} } {<true code>} {<false code>}</code> |

New: 2015-11-15

Implements the “Or” operation on the *<boolean expressions>*, hence is `true` if any of them is `true` and `false` if all of them are `false`. Contrarily to the infix operator `||`, only the *<boolean expressions>* which are needed to determine the result of `\bool_lazy_any:nTF` will be evaluated. See also `\bool_lazy_or:nnTF` when there are only two *<boolean expressions>*.

| | |
|-----------------------------------|--|
| <code>\bool_lazy_or_p:nn</code> ★ | <code>\bool_lazy_or_p:nn {<booleanexpr₁>} {<booleanexpr₂>}</code> |
| <code>\bool_lazy_or:nnTF</code> ★ | <code>\bool_lazy_or:nnTF {<booleanexpr₁>} {<booleanexpr₂>} {<true code>} {<false code>}</code> |

New: 2015-11-15

Implements the “Or” operation between two boolean expressions, hence is `true` if either one is `true`. Contrarily to the infix operator `||`, the *<booleanexpr₂>* will only be evaluated if it is needed to determine the result of `\bool_lazy_or:nnTF`. See also `\bool_lazy_any:nTF` when there are more than two *<boolean expressions>*.

9 Additions to l3prop

| | |
|------------------------------|---|
| <code>\prop_count:N</code> ☆ | <code>\prop_count:N</code> $\langle property\ list \rangle$ |
|------------------------------|---|

| | |
|------------------------------|--|
| <code>\prop_count:c</code> ☆ | Leaves the number of key–value pairs in the $\langle property\ list \rangle$ in the input stream as an $\langle integer\ denotation \rangle$. |
|------------------------------|--|

| | |
|------------------------------------|--|
| <code>\prop_map_tokens:Nn</code> ☆ | <code>\prop_map_tokens:Nn</code> $\langle property\ list \rangle$ $\{ \langle code \rangle \}$ |
|------------------------------------|--|

| | |
|------------------------------------|--|
| <code>\prop_map_tokens:cn</code> ☆ | Analogue of <code>\prop_map_function:NN</code> which maps several tokens instead of a single function. The $\langle code \rangle$ receives each key–value pair in the $\langle property\ list \rangle$ as two trailing brace groups. For instance, |
|------------------------------------|--|

`\prop_map_tokens:Nn \l_my_prop { \str_if_eq:nnT { mykey } }`

will expand to the value corresponding to `mykey`: for each pair in `\l_my_prop` the function `\str_if_eq:nnT` receives `mykey`, the $\langle key \rangle$ and the $\langle value \rangle$ as its three arguments. For that specific task, `\prop_item:Nn` is faster.

| | |
|---------------------------------------|---|
| <code>\prop_rand_key_value:N</code> ☆ | <code>\prop_rand_key_value:N</code> $\langle prop\ var \rangle$ |
|---------------------------------------|---|

| | |
|---------------------------------------|---|
| <code>\prop_rand_key_value:c</code> ☆ | Selects a pseudo-random key–value pair in the $\langle property\ list \rangle$ and returns $\{ \langle key \rangle \} \{ \langle value \rangle \}$. If the $\langle property\ list \rangle$ is empty the result is empty. This is only available in pdfTeX and LuaTeX. |
|---------------------------------------|---|

New: 2016-12-06

TeXhackers note: The result is returned within the `\unexpanded` primitive (`\exp_not:n`), which means that the $\langle value \rangle$ will not expand further when appearing in an x-type argument expansion.

10 Additions to l3seq

| | |
|--|---|
| <code>\seq_mapthread_function:NNN</code> ☆ | <code>\seq_mapthread_function:NNN</code> $\langle seq_1 \rangle$ $\langle seq_2 \rangle$ $\langle function \rangle$ |
|--|---|

| | |
|--|--|
| <code>\seq_mapthread_function:(NcN cNN ccN)</code> ☆ | |
|--|--|

Applies $\langle function \rangle$ to every pair of items $\langle seq_1\text{-}item \rangle$ – $\langle seq_2\text{-}item \rangle$ from the two sequences, returning items from both sequences from left to right. The $\langle function \rangle$ will receive two n-type arguments for each iteration. The mapping will terminate when the end of either sequence is reached (*i.e.* whichever sequence has fewer items determines how many iterations occur).

| | |
|----------------------------------|---|
| <code>\seq_set_filter:NNn</code> | <code>\seq_set_filter:NNn</code> $\langle sequence_1 \rangle$ $\langle sequence_2 \rangle$ $\{ \langle inline\ boolexpr \rangle \}$ |
|----------------------------------|---|

| | |
|-----------------------------------|--|
| <code>\seq_gset_filter:NNn</code> | Evaluates the $\langle inline\ boolexpr \rangle$ for every $\langle item \rangle$ stored within the $\langle sequence_2 \rangle$. The $\langle inline\ boolexpr \rangle$ will receive the $\langle item \rangle$ as #1. The sequence of all $\langle items \rangle$ for which the $\langle inline\ boolexpr \rangle$ evaluated to <code>true</code> is assigned to $\langle sequence_1 \rangle$. |
|-----------------------------------|--|

TeXhackers note: Contrarily to other mapping functions, `\seq_map_break` cannot be used in this function, and will lead to low-level TeX errors.

| |
|--------------------------------|
| <code>\seq_set_map:NNn</code> |
| <code>\seq_gset_map:NNn</code> |
| New: 2011-12-22 |

`\seq_set_map:NNn` $\langle sequence_1 \rangle$ $\langle sequence_2 \rangle$ $\{ \langle inline function \rangle \}$

Applies $\langle inline function \rangle$ to every $\langle item \rangle$ stored within the $\langle sequence_2 \rangle$. The $\langle inline function \rangle$ should consist of code which will receive the $\langle item \rangle$ as #1. The sequence resulting from x-expanding $\langle inline function \rangle$ applied to each $\langle item \rangle$ is assigned to $\langle sequence_1 \rangle$. As such, the code in $\langle inline function \rangle$ should be expandable.

TeXhackers note: Contrarily to other mapping functions, `\seq_map_break:` cannot be used in this function, and will lead to low-level TeX errors.

| |
|---------------------------------|
| <code>\seq_rand_item:N</code> ★ |
| <code>\seq_rand_item:c</code> ★ |
| New: 2016-12-06 |

`\seq_rand_item:N` $\langle seq var \rangle$

Selects a pseudo-random item of the $\langle sequence \rangle$. If the $\langle sequence \rangle$ is empty the result is empty. This is only available in pdfTeX and LuaTeX.

TeXhackers note: The result is returned within the `\unexpanded` primitive (`\exp_not:n`), which means that the $\langle item \rangle$ will not expand further when appearing in an x-type argument expansion.

11 Additions to l3skip

| | |
|--|---|
| <code>\skip_split_finite_else_action:nnNN</code> | <code>\skip_split_finite_else_action:nnNN</code> $\{ \langle skipexpr \rangle \}$ $\{ \langle action \rangle \}$ $\langle dimen_1 \rangle$ $\langle dimen_2 \rangle$ |
|--|---|

Checks if the $\langle skipexpr \rangle$ contains finite glue. If it does then it assigns $\langle dimen_1 \rangle$ the stretch component and $\langle dimen_2 \rangle$ the shrink component. If it contains infinite glue set $\langle dimen_1 \rangle$ and $\langle dimen_2 \rangle$ to 0pt and place #2 into the input stream: this is usually an error or warning message of some sort.

12 Additions to l3tl

| | |
|--|--|
| <code>\tl_if_single_token_p:n</code> ★ | <code>\tl_if_single_token_p:n</code> $\{ \langle token list \rangle \}$ |
| <code>\tl_if_single_token:nTF</code> ★ | <code>\tl_if_single_token:nTF</code> $\{ \langle token list \rangle \}$ $\{ \langle true code \rangle \}$ $\{ \langle false code \rangle \}$ |

Tests if the token list consists of exactly one token, *i.e.* is either a single space character or a single “normal” token. Token groups ($\{ \dots \}$) are not single tokens.

| | |
|-------------------------------------|--|
| <code>\tl_reverse_tokens:n</code> ★ | <code>\tl_reverse_tokens:n</code> $\{ \langle tokens \rangle \}$ |
|-------------------------------------|--|

This function, which works directly on TeX tokens, reverses the order of the $\langle tokens \rangle$: the first will be the last and the last will become first. Spaces are preserved. The reversal also operates within brace groups, but the braces themselves are not exchanged, as this would lead to an unbalanced token list. For instance, `\tl_reverse_tokens:n {a~{b()}}` leaves `{()b}~a` in the input stream. This function requires two steps of expansion.

TeXhackers note: The result is returned within the `\unexpanded` primitive (`\exp_not:n`), which means that the token list will not expand further when appearing in an x-type argument expansion.

| | | |
|---------------------------------|---|--|
| <code>\tl_count_tokens:n</code> | ★ | <code>\tl_count_tokens:n {<tokens>}</code> |
|---------------------------------|---|--|

Counts the number of \TeX tokens in the $\langle tokens \rangle$ and leaves this information in the input stream. Every token, including spaces and braces, contributes one to the total; thus for instance, the token count of `a~{bc}` is 6. This function requires three expansions, giving an $\langle integer denotation \rangle$.

| | | |
|--------------------------------|---|--|
| <code>\tl_lower_case:n</code> | ★ | <code>\tl_upper_case:n {<tokens>}</code> |
| <code>\tl_upper_case:n</code> | ★ | <code>\tl_upper_case:nn {<language>} {<tokens>}</code> |
| <code>\tl_mixed_case:n</code> | ★ | These functions are intended to be applied to input which may be regarded broadly as “text”. They traverse the $\langle tokens \rangle$ and change the case of characters as discussed below. The character code of the characters replaced may be arbitrary: the replacement characters will have standard document-level category codes (11 for letters, 12 for letter-like characters which can also be case-changed). Begin-group and end-group characters in the $\langle tokens \rangle$ are normalized and become <code>{</code> and <code>}</code> , respectively. |
| <code>\tl_lower_case:nn</code> | ★ | |
| <code>\tl_upper_case:nn</code> | ★ | |
| <code>\tl_mixed_case:nn</code> | ★ | |

New: 2014-06-30
Updated: 2016-01-12

Importantly, notice that these functions are intended for working with user text for typesetting. For case changing programmatic data see the `l3str` module and discussion there of `\str_lower_case:n`, `\str_upper_case:n` and `\str_fold_case:n`.

The functions perform expansion on the input in most cases. In particular, input in the form of token lists or expandable functions will be expanded *unless* it falls within one of the special handling classes described below. This expansion approach means that in general the result of case changing will match the “natural” outcome expected from a “functional” approach to case modification. For example

```
\tl_set:Nn \l_tmpa_tl { hello }
\tl_upper_case:n { \l_tmpa_tl \c_space_tl world }
```

will produce

HELLO WORLD

The expansion approach taken means that in package mode any $\LaTeX 2_{\epsilon}$ “robust” commands which may appear in the input should be converted to engine-protected versions using for example the `\robustify` command from the `etoolbox` package.

`\l_tl_case_change_math_tl`

Case changing will not take place within math mode material so for example

```
\tl_upper_case:n { Some~text~$y = mx + c$~with~{Braces} }
```

will become

```
SOME TEXT $y = mx + c$ WITH {BRACES}
```

Material inside math mode is left entirely unchanged: in particular, no expansion is undertaken.

Detection of math mode is controlled by the list of tokens in `\l_tl_case_change_math_tl`, which should be in open-close pairs. In package mode the standard settings is

```
$ $ \ ( \)
```

Note that while expansion occurs when searching the text it does not apply to math mode material (which should be unaffected by case changing). As such, whilst the opening token for math mode may be “hidden” inside a command/macro, the closing one cannot be as this is being searched for in math mode. Typically, in the types of “text” the case changing functions are intended to apply to this should not be an issue.

`\l_tl_case_change_exclude_tl`

Case changing can be prevented by using any command on the list `\l_tl_case_change_exclude_tl`. Each entry should be a function to be followed by one argument: the latter will be preserved as-is with no expansion. Thus for example following

```
\tl_put_right:Nn \l_tl_case_change_exclude_tl { \NoChangeCase }
```

the input

```
\tl_upper_case:n  
{ Some~text~$y = mx + c$~with~\NoChangeCase {Protection} }
```

will result in

```
SOME TEXT $y = mx + c$ WITH \NoChangeCase {Protection}
```

Notice that the case changing mapping preserves the inclusion of the escape functions: it is left to other code to provide suitable definitions (typically equivalent to `\use:n`). In particular, the result of case changing is returned protected by `\exp_not:n`.

When used with $\text{\LaTeX} 2_{\epsilon}$ the commands `\cite`, `\ensuremath`, `\label` and `\ref` are automatically included in the list for exclusion from case changing.

`\l_t1_case_change_accents_t1`

This list specifies accent commands which should be left unexpanded in the output. This allows for example

```
\tl_upper_case:n { \" { a } }
```

to yield

```
\" { A }
```

irrespective of the expandability of `\"`.

The standard contents of this variable is `\", \', \., \^, \', \~, \c, \H, \k, \r, \t, \u` and `\v`.

“Mixed” case conversion may be regarded informally as converting the first character of the *<tokens>* to upper case and the rest to lower case. However, the process is more complex than this as there are some situations where a single lower case character maps to a special form, for example *ij* in Dutch which becomes *IJ*. As such, `\tl_mixed_case:n(n)` implement a more sophisticated mapping which accounts for this and for modifying accents on the first letter. Spaces at the start of the *<tokens>* are ignored when finding the first “letter” for conversion.

```
\tl_mixed_case:n { hello~WORLD } % => "Hello world"
\tl_mixed_case:n { ~hello~WORLD } % => " Hello world"
\tl_mixed_case:n { {hello}~WORLD } % => "{Hello} world"
```

When finding the first “letter” for this process, any content in math mode or covered by `\l_t1_case_change_exclude_t1` is ignored.

(Note that the Unicode Consortium describe this as “title case”, but that in English title case applies on a word-by-word basis. The “mixed” case implemented here is a lower level concept needed for both “title” and “sentence” casing of text.)

`\l_t1_mixed_case_ignore_t1`

The list of characters to ignore when searching for the first “letter” in mixed-casing is determined by `\l_t1_mixed_change_ignore_t1`. This has the standard setting

```
( [ { ' -
```

where comparisons are made on a character basis.

As is generally true for `expl3`, these functions are designed to work with Unicode input only. As such, UTF-8 input is assumed for *all* engines. When used with `XƎTeX` or `LuaTeX` a full range of Unicode transformations are enabled. Specifically, the standard mappings here follow those defined by the [Unicode Consortium](#) in `UnicodeData.txt` and `SpecialCasing.txt`. In the case of 8-bit engines, mappings are provided for characters which can be represented in output typeset using the `T1` font encoding. Thus for example `Ãd` can be case-changed using `pdfTeX`. For `pTeX` only the ASCII range is covered as the engine treats input outside of this range as east Asian.

Context-sensitive mappings are enabled: language-dependent cases are discussed below. Context detection will expand input but treats any unexpandable control sequences as “failures” to match a context.

Language-sensitive conversions are enabled using the *<language>* argument, and follow Unicode Consortium guidelines. Currently, the languages recognised for special handling are as follows.

- Azeri and Turkish (**az** and **tr**). The case pairs I/i-dotless and I-dot/i are activated for these languages. The combining dot mark is removed when lower casing I-dot and introduced when upper casing i-dotless.
- German (**de-alt**). An alternative mapping for German in which the lower case *Eszett* maps to a *großes Eszett*.
- Lithuanian (**lt**). The lower case letters i and j should retain a dot above when the accents grave, acute or tilde are present. This is implemented for lower casing of the relevant upper case letters both when input as single Unicode codepoints and when using combining accents. The combining dot is removed when upper casing in these cases. Note that *only* the accents used in Lithuanian are covered: the behaviour of other accents are not modified.
- Dutch (**nl**). Capitalisation of ij at the beginning of mixed cased input produces IJ rather than Ij. The output retains two separate letters, thus this transformation *is* available using pdfTeX.

Creating additional context-sensitive mappings requires knowledge of the underlying mapping implementation used here. The team are happy to add these to the kernel where they are well-documented (*e.g.* in Unicode Consortium or relevant government publications).

```
\tl_set_from_file:Nnn
\tl_set_from_file:cnn
\tl_gset_from_file:Nnn
\tl_gset_from_file:cnn
```

New: 2014-06-25

```
\tl_set_from_file:Nnn <tl> {<setup>} {<filename>}
```

Defines $\langle tl \rangle$ to the contents of $\langle filename \rangle$. Category codes may need to be set appropriately via the $\langle setup \rangle$ argument.

```
\tl_set_from_file_x:Nnn
\tl_set_from_file_x:cnn
\tl_gset_from_file_x:Nnn
\tl_gset_from_file_x:cnn
```

New: 2014-06-25

```
\tl_set_from_file_x:Nnn <tl> {<setup>} {<filename>}
```

Defines $\langle tl \rangle$ to the contents of $\langle filename \rangle$, expanding the contents of the file as it is read. Category codes and other definitions may need to be set appropriately via the $\langle setup \rangle$ argument.

```
\tl_rand_item:N ★
\tl_rand_item:c ★
\tl_rand_item:n ★
```

New: 2016-12-06

```
\tl_rand_item:N <tl var>
```

```
\tl_rand_item:n {<token list>}
```

Selects a pseudo-random item of the $\langle token list \rangle$. If the $\langle token list \rangle$ is blank, the result is empty. This is only available in pdfTeX and LuaTeX.

TeXhackers note: The result is returned within the `\unexpanded` primitive (`\exp_not:n`), which means that the $\langle item \rangle$ will not expand further when appearing in an **x**-type argument expansion.

| | |
|------------------------------|--|
| <code>\tl_range:Nnn</code> ★ | <code>\tl_range:Nnn <tl var> {(start index)} {(end index)}</code> |
| <code>\tl_range:cnn</code> ★ | <code>\tl_range:nnn {(token list)} {(start index)} {(end index)}</code> |
| <code>\tl_range:nnn</code> ★ | Leaves in the input stream the items from the <i><start index></i> to the <i><end index></i> inclusive. Positive <i><indices></i> are counted from the start of the <i><token list></i> , 1 being the first item, and negative <i><indices></i> are counted from the end of the token list, -1 being the last item. If either of <i><start index></i> or <i><end index></i> is 0, the result is empty. For instance, |
| New: 2017-02-17 | |

```

\tl_range:nnn { abcdef } { 2 } { 5 } }
\tl_range:nnn { abcdef } { -4 } { -1 } }
\tl_range:nnn { abcdef } { -2 } { -1 } }
\tl_range:nnn { abcdef } { 0 } { -1 } }

```

will print `bcde`, `cdef`, `ef`, and an empty line to the terminal. The *<start index>* must always be smaller than or equal to the *<end index>*: if this is not the case then no output is generated. Thus

```

\tl_range:nnn { abcdef } { 5 } { 2 } }
\tl_range:nnn { abcdef } { -1 } { -4 } }

```

both yield empty token lists.

TeXhackers note: The result is returned within the `\unexpanded` primitive (`\exp_not:n`), which means that the *<item>* will not expand further when appearing in an `x`-type argument expansion.

13 Additions to l3tokens

| | |
|------------------------------|---|
| <code>\peek_N_type:TF</code> | <code>\peek_N_type:TF {(true code)} {(false code)}</code> |
| Updated: 2012-12-20 | Tests if the next <i><token></i> in the input stream can be safely grabbed as an N-type argument. The test will be <i><false></i> if the next <i><token></i> is either an explicit or implicit begin-group or end-group token (with any character code), or an explicit or implicit space character (with character code 32 and category code 10), or an outer token (never used in L ^A T _E X3) and <i><true></i> in all other cases. Note that a <i><true></i> result ensures that the next <i><token></i> is a valid N-type argument. However, if the next <i><token></i> is for instance <code>\c_space_token</code> , the test will take the <i><false></i> branch, even though the next <i><token></i> is in fact a valid N-type argument. The <i><token></i> will be left in the input stream after the <i><true code></i> or <i><false code></i> (as appropriate to the result of the test). |

Part XXVIII

The l3`luatex` package

LuaTeX-specific functions

1 Breaking out to Lua

The LuaTeX engine provides access to the Lua programming language, and with it access to the “internals” of TeX. In order to use this within the framework provided here, a family of functions is available. When used with pdfTeX or XeTeX these will raise an error: use `\sys_if_engine luatex:T` to avoid this. Details of coding the LuaTeX engine are detailed in the LuaTeX manual.

1.1 TeX code interfaces

| | | |
|---------------------------|---|--|
| <code>\lua_now_x:n</code> | ★ | <code>\lua_now:n {⟨token list⟩}</code> |
|---------------------------|---|--|

| | |
|-------------------------|---|
| <code>\lua_now:n</code> | ★ |
|-------------------------|---|

New: 2015-06-29

The *⟨token list⟩* is first tokenized by TeX, which will include converting line ends to spaces in the usual TeX manner and which respects currently-applicable TeX category codes. The resulting *⟨Lua input⟩* is passed to the Lua interpreter for processing. Each `\lua_now:n` block is treated by Lua as a separate chunk. The Lua interpreter will execute the *⟨Lua input⟩* immediately, and in an expandable manner.

In the case of the `\lua_now_x:n` version the input is fully expanded by TeX in an x-type manner *but* the function remains fully expandable.

TeXhackers note: `\lua_now_x:n` is a macro wrapper around `\directlua:` when LuaTeX is in use two expansions will be required to yield the result of the Lua code.

| | | |
|-------------------------------|--|--|
| <code>\lua_shipout_x:n</code> | | <code>\lua_shipout:n {⟨token list⟩}</code> |
|-------------------------------|--|--|

| | |
|-----------------------------|--|
| <code>\lua_shipout:n</code> | |
|-----------------------------|--|

New: 2015-06-30

The *⟨token list⟩* is first tokenized by TeX, which will include converting line ends to spaces in the usual TeX manner and which respects currently-applicable TeX category codes. The resulting *⟨Lua input⟩* is passed to the Lua interpreter when the current page is finalised (*i.e.* at shipout). Each `\lua_shipout:n` block is treated by Lua as a separate chunk. The Lua interpreter will execute the *⟨Lua input⟩* during the page-building routine: no TeX expansion of the *⟨Lua input⟩* will occur at this stage.

In the case of the `\lua_shipout_x:n` version the input is fully expanded by TeX in an x-type manner during the shipout operation.

TeXhackers note: At a TeX level, the *⟨Lua input⟩* is stored as a “whatsit”.

| | | |
|-------|--------------------------------|---|
| <hr/> | <code>\lua_escape_x:n</code> ★ | <code>\lua_escape:n {⟨token list⟩}</code> |
| | <code>\lua_escape:n</code> ★ | Converts the <i>⟨token list⟩</i> such that it can safely be passed to Lua: embedded backslashes, double and single quotes, and newlines and carriage returns are escaped. This is done by prepending an extra token consisting of a backslash with category code 12, and for the line endings, converting them to <code>\n</code> and <code>\r</code> , respectively. |
| <hr/> | New: 2015-06-29 | |
| | | In the case of the <code>\lua_escape_x:n</code> version the input is fully expanded by $\mathrm{T}_{\mathrm{E}}\mathrm{X}$ in an <i>x</i> -type manner <i>but</i> the function remains fully expandable. |
| | | $\mathrm{T}_{\mathrm{E}}\mathrm{X}$hackers note: <code>\lua_escape_x:n</code> is a macro wrapper around <code>\luaescapestring</code> : when $\mathrm{LuaT}_{\mathrm{E}}\mathrm{X}$ is in use two expansions will be required to yield the result of the Lua code. |

1.2 Lua interfaces

As well as interfaces for $\mathrm{T}_{\mathrm{E}}\mathrm{X}$, there are a small number of Lua functions provided here. Currently these are intended for internal use only.

| | | |
|-------|--------------------------------|--|
| <hr/> | <code>l3kernel.strptime</code> | <code>\l3kernel.strptime(⟨str one⟩, ⟨str two⟩)</code> |
| | | Compares the two strings and returns 0 to $\mathrm{T}_{\mathrm{E}}\mathrm{X}$ if the two are identical. |
| <hr/> | <code>l3kernel.charcat</code> | <code>\l3kernel.charcat(⟨charcode⟩, ⟨catcode⟩)</code> |
| | | Constructs a character of <i>⟨charcode⟩</i> and <i>⟨catcode⟩</i> and returns the result to $\mathrm{T}_{\mathrm{E}}\mathrm{X}$. |

Part XXIX

The l3drivers package

Drivers

T_EX relies on drivers in order to carry out a number of tasks, such as using color, including graphics and setting up hyper-links. The nature of the code required depends on the exact driver in use. Currently, L^AT_EX3 is aware of the following drivers:

- **pdfmode**: The “driver” for direct PDF output by *both* pdfT_EX and LuaT_EX (no separate driver is used in this case: the engine deals with PDF creation itself).
- **dvips**: The dvips program, which works in conjugation with pdfT_EX or LuaT_EX in DVI mode.
- **dvipdfmx**: The dvipdfmx program, which works in conjugation with pdfT_EX or LuaT_EX in DVI mode.
- **dvisvgm**: The dvisvgm program, which works in conjugation with pdfT_EX or LuaT_EX in DVI mode to create SVG output.
- **xdvipdfmx**: The driver used by X_YT_EX.

The code here is all very low-level, and should not in general be used outside of the kernel. It is also important to note that many of the functions here are closely tied to the immediate level “up”, and they must be used in the correct contexts.

1 Box clipping

_driver_box_use_clip:N

New: 2011-11-11

_driver_box_use_clip:N $\langle box \rangle$

Inserts the content of the $\langle box \rangle$ at the current insertion point such that any material outside of the bounding box will not be displayed by the driver. The material in the $\langle box \rangle$ is still placed in the output stream: the clipping takes place at a driver level.

This function should only be used within a surrounding horizontal box construct.

2 Box rotation and scaling

_driver_box_use_rotate:Nn

New: 2016-05-12

_driver_box_use_rotate:Nn $\langle box \rangle$ $\{ \langle angle \rangle \}$

Inserts the content of the $\langle box \rangle$ at the current insertion point rotated by the $\langle angle \rangle$ (expressed in degrees). The material is inserted with no apparent height or width, and is rotated such the the T_EX reference point of the box is the center of rotation and remains the reference point after rotation. It is the responsibly of the code using this function to adjust the apparent size of the box to be correct at the T_EX side.

This function should only be used within a surrounding horizontal box construct.

| | |
|--|--|
| <code>_driver_box_use_scale:Nnn</code> | <code>_driver_box_use_scale:Nnn <box> {<x-scale>} {<y-scale>}</code> |
|--|--|

New: 2016-05-12

Inserts the content of the $\langle box \rangle$ at the current insertion point scale by the $\langle x-scale \rangle$ and $\langle y-scale \rangle$. The material is inserted with no apparent height or width. It is the responsibly of the code using this function to adjust the apparent size of the box to be correct at the \TeX side.

This function should only be used within a surrounding horizontal box construct.

3 Color support

| | |
|--|--|
| <code>_driver_color_ensure_current:</code> | <code>_driver_color_ensure_current:</code> |
|--|--|

New: 2011-09-03

Updated: 2012-05-18

Ensures that the color used to typeset material is that which was set when the material was placed in a box. This function is therefore required inside any “color safe” box to ensure that the box may be inserted in a location where the foreground color has been altered, while preserving the color used in the box.

4 Drawing

The drawing functions provided here are *highly* experimental. They are inspired heavily by the system layer of `pgf` (most have the same interface as the same functions in the latter’s `\pgfsys@... namespace`). They are intended to form the basis for higher level drawing interfaces, which themselves are likely to be further abstracted for user access. Again, this model is heavily inspired by `pgf` and `Tikz`.

These low level drawing interfaces abstract from the driver raw requirements but still require an appreciation of the concepts of PostScript/PDF/SVG graphic creation.

| | |
|-------------------------------------|-------------------------------------|
| <code>_driver_draw_begin:</code> | <code>_driver_draw_begin:</code> |
| <code>_driver_draw_end:</code> | <code><content></code> |

`_driver_draw_end:`

Defines a drawing environment. This will be a scope for the purposes of the graphics state. Depending on the driver, other set up may or may not take place here. The natural size of the $\langle content \rangle$ should be zero from the \TeX perspective: allowance for the size of the content must be made at a higher level (or indeed this can be skipped if the content is to overlap other material).

| | |
|--|--|
| <code>_driver_draw_scope_begin:</code> | <code>_driver_draw_scope_begin:</code> |
| <code>_driver_draw_scope_end:</code> | <code><content></code> |

`_driver_draw_scope_end:`

Defines a scope for drawing settings and so on. Changes to the graphic state and concepts such as color or linewidth are localised to a scope. This function pair must never be used if an partial path is under construction: such paths must be entirely contained at one unbroken scope level. Note that scopes do not form \TeX groups and may not be aligned with them.

4.1 Path construction

| | | | |
|-------------|--|--|--|
| <hr/> <hr/> | <code>__driver_draw_moveto:nn</code> | <code>__driver_draw_move:nn {<x>} {<y>}</code> | Moves the current drawing reference point to $(\langle x \rangle, \langle y \rangle)$; any active transformation matrix will apply. |
| <hr/> <hr/> | <code>__driver_draw_lineto:nn</code> | <code>__driver_draw_lineto:nn {<x>} {<y>}</code> | Adds a path from the current drawing reference point to $(\langle x \rangle, \langle y \rangle)$; any active transformation matrix will apply. Note that nothing is drawn until a fill or stroke operation is applied, and that the path may be discarded or used as a clip without appearing itself. |
| <hr/> <hr/> | <code>__driver_draw_curveto:nnnnnn</code> | <code>__driver_draw_curveto:nnnnnn {<x₁>} {<y₁>} {<x₂>} {<y₂>} {<x₃>} {<y₃>}</code> | Adds a Bezier curve path from the current drawing reference point to $(\langle x_3 \rangle, \langle y_3 \rangle)$, using $(\langle x_1 \rangle, \langle y_1 \rangle)$ and $(\langle x_2 \rangle, \langle y_2 \rangle)$ as control points; any active transformation matrix will apply. Note that nothing is drawn until a fill or stroke operation is applied, and that the path may be discarded or used as a clip without appearing itself. |
| <hr/> <hr/> | <code>__driver_draw_rectangle:nnnn</code> | <code>__driver_draw_rectangle:nnnn {<x>} {<y>} {<width>} {<height>}</code> | Adds rectangular path from $(\langle x_1 \rangle, \langle y_1 \rangle)$ of $\langle height \rangle$ and $\langle width \rangle$; any active transformation matrix will apply. Note that nothing is drawn until a fill or stroke operation is applied, and that the path may be discarded or used as a clip without appearing itself. |
| <hr/> <hr/> | <code>__driver_draw_closepath:</code> | | Closes an existing path, adding a line from the current point to the start of path. Note that nothing is drawn until a fill or stroke operation is applied, and that the path may be discarded or used as a clip without appearing itself. |

4.2 Stroking and filling

| | | | |
|-------------|--|--|---|
| <hr/> <hr/> | <code>__driver_draw_stroke:</code> | <code><path construction></code> | |
| <hr/> <hr/> | <code>__driver_draw_closestroke:</code> | <code>__driver_draw_stroke:</code> | |
| | | | Draws a line along the current path, which will also be closed when <code>__driver_draw_closestroke:</code> is used. The nature of the line drawn is influenced by settings for |
| | | | <ul style="list-style-type: none"> • Line thickness • Stroke color (or the current color if no specific stroke color is set) • Line capping (how non-closed line ends should look) • Join style (how a bend in the path should be rendered) • Dash pattern |

The path may also be used for clipping.

| | |
|---|--|
| <code>__driver_draw_fill:</code> | <code><path construction></code> |
| <code>__driver_draw_fillstroke:</code> | <code>__driver_draw_fill:</code> |

Fills the area surrounded by the current path: this will be closed prior to filling if it is not already. The `fillstroke` version will also stroke the path as described for `__driver_draw_stroke:`. The fill is influenced by the setting for fill color (or the current color if no specific stroke color is set). The path may also be used for clipping. For paths which are self-intersecting or comprising multiple parts, the determination of which areas are inside the path is made using the non-zero winding number rule unless the even-odd rule is active.

| | |
|---|---|
| <code>__driver_draw_nonzero_rule:</code> | <code>__driver_draw_nonzero_rule:</code> |
| <code>__driver_draw_evenodd_rule:</code> | |

Active either the non-zero winding number or the even-odd rule, respectively, for determining what is inside a fill or clip area. For technical reasons, these command are not influenced by scoping and apply on an ongoing basis.

| | |
|-----------------------------------|--|
| <code>__driver_draw_clip:</code> | <code><path construction></code> |
| <code>__driver_draw_clip:</code> | <code>__driver_draw_clip:</code> |

Indicates that the current path should be used for clipping, such that any subsequent material outside of the path (but within the current scope) will not be shown. This command should be given once a path is complete but before it is stroked or filled (if appropriate). This command is *not* affected by scoping: it applies to exactly one path as shown.

| | |
|--|--|
| <code>__driver_draw_discardpath:</code> | <code><path construction></code> |
| <code>__driver_draw_discardpath:</code> | <code>__driver_draw_discardpath:</code> |

Discards the current path without stroking or filling. This is primarily useful for paths constructed purely for clipping, as this alone does not end the paths existence.

4.3 Stroke options

| | |
|---|---|
| <code>__driver_draw_linewidth:n</code> | <code>__driver_draw_linewidth:n <{dimexpr}></code> |
|---|---|

Sets the width to be used for stroking to `<dimexpr>`.

| | |
|-------------------------------------|--|
| <code>__driver_draw_dash:nn</code> | <code>__driver_draw_dash:nn <{dash pattern}> <{phase}></code> |
|-------------------------------------|--|

Sets the pattern of dashing to be used when stroking a line. The `<dash pattern>` should be a comma-separated list of dimension expressions. This is then interpreted as a series of pairs of line-on and line-off lengths. For example `3pt, 4pt` means that 3pt on, 4pt off, 3pt on, and so on. A more complex pattern will also repeat: `3pt, 4pt, 1pt, 2pt` results in 3pt on, 4pt off, 1pt on, 2pt off, 3pt on, and so on. An odd number of entries means that the last is repeated, for example `3pt` is equal to `3pt, 3pt`. An empty pattern yields a solid line.

The `<phase>` specifies an offset at the start of the cycle. For example, with a pattern `3pt` a phase of `1pt` will mean that the output is 2pt on, 3pt off, 3pt on, 3pt on, *etc.*

| | |
|--|--------------------------------------|
| <code>__driver_draw_cap_but:</code> | <code>__driver_draw_cap_but:</code> |
| <code>__driver_draw_cap_rectangle:</code> | |
| <code>__driver_draw_cap_round:</code> | |

Sets the style of terminal stroke position to one of butt, rectangle or round.

| | |
|---|---|
| <code>__driver_draw_join_bevel:</code> | <code>__driver_draw_cap_but:</code> |
| <code>__driver_draw_join_miter:</code> | Sets the style of stroke joins to one of bevel, miter or round. |
| <code>__driver_draw_join_round:</code> | |

| | |
|--|--|
| <code>__driver_draw_miterlimit:n</code> | <code>__driver_draw_miterlimit:n {<dimexpr>}</code> |
|--|--|

Sets the miter limit of lines joined as a miter, as described in the PDF and PostScript manuals.

4.4 Color

| | |
|--|---|
| <code>__driver_draw_color_cmyk:nnnn</code> | <code>__driver_draw_color_cmyk:nnnn {<cyan>} {<magenta>} {<yellow>}</code> |
| <code>__driver_draw_color_cmyk_fill:nnnn</code> | <code>{<black>}</code> |
| <code>__driver_draw_color_cmyk_stroke:nnnn</code> | |

Sets the color for drawing to the CMYK values specified, all of which are fp expressions which should evaluate to between 0 and 1. The **fill** and **stroke** versions set only the color for those operations. Note that the general setting is more efficient with some drivers so should in most cases be preferred.

| | |
|---|---|
| <code>__driver_draw_color_gray:n</code> | <code>__driver_draw_color_gray:n {<gray>}</code> |
| <code>__driver_draw_color_gray_fill:n</code> | |
| <code>__driver_draw_color_gray_stroke:n</code> | |

Sets the color for drawing to the grayscale value specified, which is fp expressions which should evaluate to between 0 and 1. The **fill** and **stroke** versions set only the color for those operations. Note that the general setting is more efficient with some drivers so should in most cases be preferred.

| | |
|--|---|
| <code>__driver_draw_color_rgb:nnn</code> | <code>__driver_draw_color_gray:n {<red>} {<green>} {<blue>}</code> |
| <code>__driver_draw_color_rgb_fill:nnn</code> | |
| <code>__driver_draw_color_rgb_stroke:nnn</code> | |

Sets the color for drawing to the RGB values specified, all of which are fp expressions which should evaluate to between 0 and 1. The **fill** and **stroke** versions set only the color for those operations. Note that the general setting is more efficient with some drivers so should in most cases be preferred.

4.5 Inserting T_EX material

```

\__driver_draw_hbox:Nnnnnnn \__driver_draw_hbox:Nnnnnnn <box>
                             {\a}\{b}\{c}\{d}\{x}\{y}

```

Inserts the $\langle box \rangle$ as an hbox with the box reference point placed at (x, y) . The transformation matrix $[abcd]$ will be applied to the box, allowing it to be in synchronisation with any scaling, rotation or skewing applying more generally. Note that T_EX material should not be inserted directly into a drawing as it will not be in the correct location. Also note that as for other drawing elements the box here will have no size from a T_EX perspective.

4.6 Coordinate system transformations

```

\__driver_draw_transformcm:nnnnnn \__driver_draw_transformcm:nnnnnn {\a}\{b}\{c}\{d}
                                   {\x}\{y}

```

Applies the transformation matrix $[abcd]$ and offset vector (x, y) to the current graphic state. This will affect any subsequent items in the same scope but not those already given.

Part XXX

Implementation

1 l3bootstrap implementation

```

1 \*initex | package>
2 \@@=expl>

```

1.1 Format-specific code

The very first thing to do is to bootstrap the iniT_EX system so that everything else will actually work. T_EX does not start with some pretty basic character codes set up.

```

3 \*initex>
4 \catcode '\{ = 1 %
5 \catcode '\} = 2 %
6 \catcode '\# = 6 %
7 \catcode '\^ = 7 %
8 \initex>

```

Tab characters should not show up in the code, but to be on the safe side.

```

9 \*initex>
10 \catcode '\^^I = 10 %
11 \initex>

```

For LuaT_EX, the extra primitives need to be enabled. This is not needed in package mode: common formats have the primitives enabled.

```

12 \*initex>
13 \begingroup\expandafter\expandafter\expandafter\endgroup
14 \expandafter\ifx\curname directlua\endcurname\relax
15 \else

```

```

16 \directlua{tex.enableprimitives("", tex.extraprimitives())}%
17 \fi
18 </initex>

```

Depending on the versions available, the L^AT_EX format may not have the raw `\Umath` primitive names available. We fix that globally: it should cause no issues. Older LuaT_EX versions do not have a pre-built table of the primitive names here so sort one out ourselves. These end up globally-defined but at that is true with a newer format anyway and as they all start `\U` this should be reasonably safe.

```

19 <*package>
20 \begingroup
21 \expandafter\ifx\csname directlua\endcsname\relax
22 \else
23 \directlua{%
24     local i
25     local t = { }
26     for _,i in pairs(tex.extraprimitives("luatex")) do
27         if string.match(i,"^U") then
28             if not string.match(i,"^Uchar$") then
29                 table.insert(t,i)
30             end
31         end
32     end
33     tex.enableprimitives("", t)
34 }%
35 \fi
36 \endgroup
37 </package>

```

1.2 The `\pdfstrcmp` primitive in X_YT_EX

Only pdfT_EX has a primitive called `\pdfstrcmp`. The X_YT_EX version is just `\strcmp`, so there is some shuffling to do. As this is still a real primitive, using the pdfT_EX name is “safe”.

```

38 \begingroup\expandafter\expandafter\expandafter\endgroup
39 \expandafter\ifx\csname pdfstrcmp\endcsname\relax
40 \let\pdfstrcmp\strcmp
41 \fi

```

1.3 Loading support Lua code

When LuaT_EX is used there are various pieces of Lua code which need to be loaded. The code itself is defined in `l3luatex` and is extracted into a separate file. Thus here the task is to load the Lua code both now and (if required) at the start of each job.

```

42 \begingroup\expandafter\expandafter\expandafter\endgroup
43 \expandafter\ifx\csname directlua\endcsname\relax
44 \else
45 \ifnum\luatexversion<70 %
46 \else

```

In package mode a category code table is needed: either use a pre-loaded allocator or provide one using the L^AT_EX 2_ε-based generic code. In format mode the table used here can be hard-coded into the Lua.

```

47 \*package\
48 \begingroup\expandafter\expandafter\expandafter\endgroup
49 \expandafter\ifx\csname newcatcodetable\endcsname\relax
50 \input{ltluatex}%
51 \fi
52 \newcatcodetable\ucharcat@table
53 \directlua{
54   l3kernel = l3kernel or { }
55   local charcat_table = \number\ucharcat@table\space
56   l3kernel.charcat_table = charcat_table
57 }%
58 \endpackage\
59 \directlua{require("expl3")}%

```

As the user might be making a custom format, no assumption is made about matching package mode with only loading the Lua code once. Instead, a query to Lua will reveal what mode is in operation.

```

60 \ifnum 0%
61 \directlua{
62   if status.ini_version then
63     tex.write("1")
64   end
65 }>0 %
66 \everyjob\expandafter{%
67   \the\expandafter\everyjob
68   \csname\detokenize{lua_now_x:n}\endcsname{require("expl3")}%
69 }%
70 \fi
71 \fi
72 \fi

```

1.4 Engine requirements

The code currently requires ϵ -TeX and functionality equivalent to `\pdfstrcmp`, and also driver and Unicode character support. This is available in a reasonably-wide range of engines.

```

73 \begingroup
74 \def\next{\endgroup}%
75 \def\ShortText{Required primitives not found}%
76 \def\LongText%
77 {%
78   LaTeX3 requires the e-TeX primitives and additional functionality as
79   described in the README file.
80   \LineBreak
81   These are available in the engines\LineBreak
82   - pdfTeX v1.40\LineBreak
83   - XeTeX v0.9994\LineBreak
84   - LuaTeX v0.70\LineBreak
85   - e-(u)pTeX mid-2012\LineBreak
86   or later.\LineBreak
87   \LineBreak
88 }%
89 \ifnum0%
90 \expandafter\ifx\csname pdfstrcmp\endcsname\relax

```

```

91 \else
92 \expandafter\ifx\csname pdftexversion\endcsname\relax
93 1%
94 \else
95 \ifnum\pdftexversion<140 \else 1\fi
96 \fi
97 \fi
98 \expandafter\ifx\csname directlua\endcsname\relax
99 \else
100 \ifnum\luatexversion<40 \else 1\fi
101 \fi
102 =0 %
103 \newlinechar'\^^J %
104 <*initex>
105 \def\LineBreak{^^J}%
106 \edef\next
107 {%
108 \errhelp
109 {%
110 \LongText
111 For pdfTeX and XeTeX the '-etex' command-line switch is also
112 needed.\LineBreak
113 \LineBreak
114 Format building will abort!\LineBreak
115 }%
116 \errmessage{\ShortText}%
117 \endgroup
118 \noexpand\end
119 }%
120 </initex>
121 <*package>
122 \def\LineBreak{\noexpand\MessageBreak}%
123 \expandafter\ifx\csname PackageError\endcsname\relax
124 \def\LineBreak{^^J}%
125 \def\PackageError#1#2#3%
126 {%
127 \errhelp{#3}%
128 \errmessage{#1 Error: #2}%
129 }%
130 \fi
131 \edef\next
132 {%
133 \noexpand\PackageError{expl3}{\ShortText}
134 {\LongText Loading of expl3 will abort!}%
135 \endgroup
136 \noexpand\endinput
137 }%
138 </package>
139 \fi
140 \next

```

1.5 Extending allocators

In format mode, allocating registers is handled by `l3alloc`. However, in package mode it's much safer to rely on more general code. For example, the ability to extend \TeX 's allocation routine to allow for $\varepsilon\text{-}\text{\TeX}$ has been around since 1997 in the `etex` package.

Loading this support is delayed until here as we are now sure that the $\varepsilon\text{-}\text{\TeX}$ extensions and `\pdfstrcmp` or equivalent are available. Thus there is no danger of an “uncontrolled” error if the engine requirements are not met.

For $\text{\LaTeX}2_{\varepsilon}$ we need to make sure that the extended pool is being used: `expl3` uses a lot of registers. For formats from 2015 onward there is nothing to do as this is automatic. For older formats, the `etex` package needs to be loaded to do the job. In that case, some inserts are reserved also as these have to be from the standard pool. Note that `\reserveinserts` is `\outer` and so is accessed here by `csname`. In earlier versions, loading `etex` was done directly and so `\reserveinserts` appeared in the code: this then required a `\relax` after `\RequirePackage` to prevent an error with “unsafe” definitions as seen for example with `capoptions`. The optional loading here is done using a group and `\ifx` test as we are not quite in the position to have a single name for `\pdfstrcmp` just yet.

```
141 <*package>
142 \begingroup
143   \def\@tempa{LaTeX2e}%
144   \def\next{}%
145   \ifx\fmtname\@tempa
146     \expandafter\ifx\csname extrafloats\endcsname\relax
147       \def\next
148         {%
149           \RequirePackage{etex}%
150           \csname reserveinserts\endcsname{32}%
151         }%
152     \fi
153   \fi
154 \expandafter\endgroup
155 \next
156 </package>
```

1.6 Character data

\TeX needs various pieces of data to be set about characters, in particular which ones to treat as letters and which `\lccode` values apply as these affect hyphenation. It makes most sense to set this and related information up in one place. Whilst for \LuaTeX hyphenation patterns can be read anywhere, other engines have to build them into the format and so we *must* do this set up before reading the patterns. For the Unicode engines, there are shared loaders available to obtain the relevant information directly from the Unicode Consortium data files. These need standard (Ini) \TeX category codes and primitive availability and must therefore be loaded *very* early. This has a knock-on effect on the 8-bit set up: it makes sense to do the definitions for those here as well so it is all in one place.

For \XeTeX and \LuaTeX , which are natively Unicode engines, simply load the Unicode data.

```
157 <*initex>
158 \ifdefined\Umathcode
```

```

159 \input load-unicode-data %
160 \input load-unicode-math-classes %
161 \else

```

For the 8-bit engines a font encoding scheme must be chosen. At present, this is the EC (T1) scheme, with the assumption that languages for which this is not appropriate will be used with one of the Unicode engines.

```

162 \begingroup

```

Lower case chars: map to themselves when lower casing and down by "20 when upper casing. (The characters a–z are set up correctly by IniTeX.)

```

163 \def\temp{%
164   \ifnum\count0>\count2 %
165   \else
166     \global\lccode\count0 = \count0 %
167     \global\uccode\count0 = \numexpr\count0 - "20\relax
168     \advance\count0 by 1 %
169     \expandafter\temp
170   \fi
171 }
172 \count0 = "A0 %
173 \count2 = "BC %
174 \temp
175 \count0 = "E0 %
176 \count2 = "FF %
177 \temp

```

Upper case chars: map up by "20 when lower casing, to themselves when upper casing and require an \sfcode of 999. (The characters A–Z are set up correctly by IniTeX.)

```

178 \def\temp{%
179   \ifnum\count0>\count2 %
180   \else
181     \global\lccode\count0 = \numexpr\count0 + "20\relax
182     \global\uccode\count0 = \count0 %
183     \global\sfcode\count0 = 999 %
184     \advance\count0 by 1 %
185     \expandafter\temp
186   \fi
187 }
188 \count0 = "80 %
189 \count2 = "9C %
190 \temp
191 \count0 = "C0 %
192 \count2 = "DF %
193 \temp

```

A few special cases where things are not as one might expect using the above pattern: dotless-I, dotless-J, dotted-I and d-bar.

```

194 \global\lccode'\^Y = '\^Y %
195 \global\uccode'\^Y = '\I %
196 \global\lccode'\^Z = '\^Z %
197 \global\uccode'\^Y = '\J %
198 \global\lccode"9D = '\i %
199 \global\uccode"9D = "9D %
200 \global\lccode"9E = "9E %
201 \global\uccode"9E = "D0 %

```

Allow hyphenation at a zero-width glyph (used to break up ligatures or to place accents between characters).

```
202 \global\lccode23 = 23 %
203 \endgroup
204 \fi
```

In all cases it makes sense to set up - to map to itself: this allows hyphenation of the rest of a word following it (suggested by Lars Helström).

```
205 \global\lccode'\- = '\- %
206 \</initex>
```

1.7 The L^AT_EX3 code environment

The code environment is now set up.

\ExplSyntaxOff Before changing any category codes, in package mode we need to save the situation before loading. Note the set up here means that once applied `\ExplSyntaxOff` will be a “do nothing” command until `\ExplSyntaxOn` is used. For format mode, there is no need to save category codes so that step is skipped.

```
207 \protected\def\ExplSyntaxOff{}%
208 \<{*package}
209 \protected\edef\ExplSyntaxOff
210 {%
211   \protected\def\ExplSyntaxOff{}%
212   \catcode 9 = \the\catcode 9\relax
213   \catcode 32 = \the\catcode 32\relax
214   \catcode 34 = \the\catcode 34\relax
215   \catcode 38 = \the\catcode 38\relax
216   \catcode 58 = \the\catcode 58\relax
217   \catcode 94 = \the\catcode 94\relax
218   \catcode 95 = \the\catcode 95\relax
219   \catcode 124 = \the\catcode 124\relax
220   \catcode 126 = \the\catcode 126\relax
221   \endlinechar = \the\endlinechar\relax
222   \chardef\csname\detokenize{l__kernel_expl_bool}\endcsname = 0\relax
223 }%
224 \</package>
```

(End definition for \ExplSyntaxOff. This function is documented on page 6.)

The code environment is now set up.

```
225 \catcode 9 = 9\relax
226 \catcode 32 = 9\relax
227 \catcode 34 = 12\relax
228 \catcode 38 = 4\relax
229 \catcode 58 = 11\relax
230 \catcode 94 = 7\relax
231 \catcode 95 = 11\relax
232 \catcode 124 = 12\relax
233 \catcode 126 = 10\relax
234 \endlinechar = 32\relax
```

\l__kernel_expl_bool The status for experimental code syntax: this is on at present.

```
235 \chardef\l__kernel_expl_bool = 1\relax
```


(End definition for `\l__kernel_expl_bool`.)

\ExplSyntaxOn The idea here is that multiple `\ExplSyntaxOn` calls are not going to mess up category codes, and that multiple calls to `\ExplSyntaxOff` are also not wasting time. Applying `\ExplSyntaxOn` will alter the definition of `\ExplSyntaxOff` and so in package mode this function should not be used until after the end of the loading process!

```

236 \protected \def \ExplSyntaxOn
237 {
238   \bool_if:NF \l__kernel_expl_bool
239   {
240     \cs_set_protected:Npx \ExplSyntaxOff
241     {
242       \char_set_catcode:nn { 9 } { \char_value_catcode:n { 9 } }
243       \char_set_catcode:nn { 32 } { \char_value_catcode:n { 32 } }
244       \char_set_catcode:nn { 34 } { \char_value_catcode:n { 34 } }
245       \char_set_catcode:nn { 38 } { \char_value_catcode:n { 38 } }
246       \char_set_catcode:nn { 58 } { \char_value_catcode:n { 58 } }
247       \char_set_catcode:nn { 94 } { \char_value_catcode:n { 94 } }
248       \char_set_catcode:nn { 95 } { \char_value_catcode:n { 95 } }
249       \char_set_catcode:nn { 124 } { \char_value_catcode:n { 124 } }
250       \char_set_catcode:nn { 126 } { \char_value_catcode:n { 126 } }
251       \tex_endlinechar:D =
252       \tex_the:D \tex_endlinechar:D \scan_stop:
253       \bool_set_false:N \l__kernel_expl_bool
254       \cs_set_protected:Npn \ExplSyntaxOff { }
255     }
256   }
257   \char_set_catcode_ignore:n { 9 } % tab
258   \char_set_catcode_ignore:n { 32 } % space
259   \char_set_catcode_other:n { 34 } % double quote
260   \char_set_catcode_alignment:n { 38 } % ampersand
261   \char_set_catcode_letter:n { 58 } % colon
262   \char_set_catcode_math_superscript:n { 94 } % circumflex
263   \char_set_catcode_letter:n { 95 } % underscore
264   \char_set_catcode_other:n { 124 } % pipe
265   \char_set_catcode_space:n { 126 } % tilde
266   \tex_endlinechar:D = 32 \scan_stop:
267   \bool_set_true:N \l__kernel_expl_bool
268 }

```

(End definition for `\ExplSyntaxOn`. This function is documented on page 6.)

269 `</initex | package>`

2 l3names implementation

270 `<*initex | package>`

No prefix substitution here.

271 `<@@=`

The code here simply renames all of the primitives to new, internal, names. In format mode, it also deletes all of the existing names (although some do come back later).

\tex_undefined:D This function does not exist at all, but is the name used by the plain T_EX format for an undefined function. So it should be marked here as “taken”.

(End definition for `\tex_undefined:D`.)

The `\let` primitive is renamed by hand first as it is essential for the entire process to follow. This also uses `\global`, as that way we avoid leaving an unneeded csname in the hash table.

```
272 \let \tex_global:D \global
273 \let \tex_let:D \let
```

Everything is inside a (rather long) group, which keeps `__kernel_primitive:NN` trapped.

```
274 \begingroup
```

`__kernel_primitive:NN` A temporary function to actually do the renaming. This also allows the original names to be removed in format mode.

```
275 \long \def \__kernel_primitive:NN #1#2
276 {
277   \tex_global:D \tex_let:D #2 #1
278   \*initex
279   \tex_global:D \tex_let:D #1 \tex_undefined:D
280   \*initex
281 }
```

(End definition for `__kernel_primitive:NN`.)

To allow extracting “just the names”, a bit of DocStrip fiddling.

```
282 \*initex | package)
283 \*initex | names | package)
```

In the current incarnation of this package, all T_EX primitives are given a new name of the form `\tex_oldname:D`. But first three special cases which have symbolic original names. These are given modified new names, so that they may be entered without catcode tricks.

```
284 \__kernel_primitive:NN \tex_space:D
285 \__kernel_primitive:NN \tex_italiccorrection:D
286 \__kernel_primitive:NN \tex_hyphen:D
```

Now all the other primitives.

```
287 \__kernel_primitive:NN \tex_above:D
288 \__kernel_primitive:NN \tex_abovedisplayshortskip:D
289 \__kernel_primitive:NN \tex_abovedisplayskip:D
290 \__kernel_primitive:NN \tex_abovewithdelims:D
291 \__kernel_primitive:NN \tex_accent:D
292 \__kernel_primitive:NN \tex_adjdemerits:D
293 \__kernel_primitive:NN \tex_advance:D
294 \__kernel_primitive:NN \tex_afterassignment:D
295 \__kernel_primitive:NN \tex_aftergroup:D
296 \__kernel_primitive:NN \tex_atop:D
297 \__kernel_primitive:NN \tex_atopwithdelims:D
298 \__kernel_primitive:NN \tex_badness:D
299 \__kernel_primitive:NN \tex_baselineskip:D
300 \__kernel_primitive:NN \tex_batchmode:D
301 \__kernel_primitive:NN \tex_begingroup:D
302 \__kernel_primitive:NN \tex_belowdisplayshortskip:D
303 \__kernel_primitive:NN \tex_belowdisplayskip:D
304 \__kernel_primitive:NN \tex_binoppenalty:D
305 \__kernel_primitive:NN \tex_botmark:D
```

| | | |
|-----|--|------------------------------|
| 306 | _kernel_primitive:NN \box | \tex_box:D |
| 307 | _kernel_primitive:NN \boxmaxdepth | \tex_boxmaxdepth:D |
| 308 | _kernel_primitive:NN \brokenpenalty | \tex_brokenpenalty:D |
| 309 | _kernel_primitive:NN \catcode | \tex_catcode:D |
| 310 | _kernel_primitive:NN \char | \tex_char:D |
| 311 | _kernel_primitive:NN \chardef | \tex_chardef:D |
| 312 | _kernel_primitive:NN \cleaders | \tex_cleaders:D |
| 313 | _kernel_primitive:NN \closein | \tex_closein:D |
| 314 | _kernel_primitive:NN \closeout | \tex_closeout:D |
| 315 | _kernel_primitive:NN \clubpenalty | \tex_clubpenalty:D |
| 316 | _kernel_primitive:NN \copy | \tex_copy:D |
| 317 | _kernel_primitive:NN \count | \tex_count:D |
| 318 | _kernel_primitive:NN \countdef | \tex_countdef:D |
| 319 | _kernel_primitive:NN \cr | \tex_cr:D |
| 320 | _kernel_primitive:NN \crrcr | \tex_crrcr:D |
| 321 | _kernel_primitive:NN \csname | \tex_csname:D |
| 322 | _kernel_primitive:NN \day | \tex_day:D |
| 323 | _kernel_primitive:NN \deadcycles | \tex_deadcycles:D |
| 324 | _kernel_primitive:NN \def | \tex_def:D |
| 325 | _kernel_primitive:NN \defaultthyphenchar | \tex_defaultthyphenchar:D |
| 326 | _kernel_primitive:NN \defaultskewchar | \tex_defaultskewchar:D |
| 327 | _kernel_primitive:NN \delcode | \tex_delcode:D |
| 328 | _kernel_primitive:NN \delimiter | \tex_delimiter:D |
| 329 | _kernel_primitive:NN \delimiterfactor | \tex_delimiterfactor:D |
| 330 | _kernel_primitive:NN \delimitershortfall | \tex_delimitershortfall:D |
| 331 | _kernel_primitive:NN \dimen | \tex_dimen:D |
| 332 | _kernel_primitive:NN \dimendef | \tex_dimendef:D |
| 333 | _kernel_primitive:NN \discretionary | \tex_discretionary:D |
| 334 | _kernel_primitive:NN \displayindent | \tex_displayindent:D |
| 335 | _kernel_primitive:NN \displaylimits | \tex_displaylimits:D |
| 336 | _kernel_primitive:NN \displaystyle | \tex_displaystyle:D |
| 337 | _kernel_primitive:NN \displaywidowpenalty | \tex_displaywidowpenalty:D |
| 338 | _kernel_primitive:NN \displaywidth | \tex_displaywidth:D |
| 339 | _kernel_primitive:NN \divide | \tex_divide:D |
| 340 | _kernel_primitive:NN \doublehyphendemerits | \tex_doublehyphendemerits:D |
| 341 | _kernel_primitive:NN \dp | \tex_dp:D |
| 342 | _kernel_primitive:NN \dump | \tex_dump:D |
| 343 | _kernel_primitive:NN \edef | \tex_edef:D |
| 344 | _kernel_primitive:NN \else | \tex_else:D |
| 345 | _kernel_primitive:NN \emergencystretch | \tex_emergencystretch:D |
| 346 | _kernel_primitive:NN \end | \tex_end:D |
| 347 | _kernel_primitive:NN \endcsname | \tex_endcsname:D |
| 348 | _kernel_primitive:NN \endgroup | \tex_endgroup:D |
| 349 | _kernel_primitive:NN \endinput | \tex_endinput:D |
| 350 | _kernel_primitive:NN \endlinechar | \tex_endlinechar:D |
| 351 | _kernel_primitive:NN \eqno | \tex_eqno:D |
| 352 | _kernel_primitive:NN \errhelp | \tex_errhelp:D |
| 353 | _kernel_primitive:NN \errmessage | \tex_errmessage:D |
| 354 | _kernel_primitive:NN \errorcontextlines | \tex_errorcontextlines:D |
| 355 | _kernel_primitive:NN \errorstopmode | \tex_errorstopmode:D |
| 356 | _kernel_primitive:NN \escapechar | \tex_escapechar:D |
| 357 | _kernel_primitive:NN \everycr | \tex_everycr:D |
| 358 | _kernel_primitive:NN \everydisplay | \tex_everydisplay:D |
| 359 | _kernel_primitive:NN \everyhbox | \tex_everyhbox:D |

| | | | |
|-----|------------------------|----------------------|-----------------------------|
| 360 | _kernel_primitive:NN | \everyjob | \tex_everyjob:D |
| 361 | _kernel_primitive:NN | \everymath | \tex_everymath:D |
| 362 | _kernel_primitive:NN | \everypar | \tex_everypar:D |
| 363 | _kernel_primitive:NN | \everyvbox | \tex_everyvbox:D |
| 364 | _kernel_primitive:NN | \exhyphenpenalty | \tex_exhyphenpenalty:D |
| 365 | _kernel_primitive:NN | \expandafter | \tex_expandafter:D |
| 366 | _kernel_primitive:NN | \fam | \tex_fam:D |
| 367 | _kernel_primitive:NN | \fi | \tex_fi:D |
| 368 | _kernel_primitive:NN | \finalhyphendemerits | \tex_finalhyphendemerits:D |
| 369 | _kernel_primitive:NN | \firstmark | \tex_firstmark:D |
| 370 | _kernel_primitive:NN | \floatingpenalty | \tex_floatingpenalty:D |
| 371 | _kernel_primitive:NN | \font | \tex_font:D |
| 372 | _kernel_primitive:NN | \fontdimen | \tex_fontdimen:D |
| 373 | _kernel_primitive:NN | \fontname | \tex_fontname:D |
| 374 | _kernel_primitive:NN | \futurelet | \tex_futurelet:D |
| 375 | _kernel_primitive:NN | \gdef | \tex_gdef:D |
| 376 | _kernel_primitive:NN | \global | \tex_global:D |
| 377 | _kernel_primitive:NN | \globaldefs | \tex_globaldefs:D |
| 378 | _kernel_primitive:NN | \halign | \tex_halign:D |
| 379 | _kernel_primitive:NN | \hangafter | \tex_hangafter:D |
| 380 | _kernel_primitive:NN | \hangindent | \tex_hangindent:D |
| 381 | _kernel_primitive:NN | \hbadness | \tex_hbadness:D |
| 382 | _kernel_primitive:NN | \hbox | \tex_hbox:D |
| 383 | _kernel_primitive:NN | \hfil | \tex_hfil:D |
| 384 | _kernel_primitive:NN | \hfill | \tex_hfill:D |
| 385 | _kernel_primitive:NN | \hfilneg | \tex_hfilneg:D |
| 386 | _kernel_primitive:NN | \hfuzz | \tex_hfuzz:D |
| 387 | _kernel_primitive:NN | \hoffset | \tex_hoffset:D |
| 388 | _kernel_primitive:NN | \holdinginserts | \tex_holdinginserts:D |
| 389 | _kernel_primitive:NN | \hrule | \tex_hrule:D |
| 390 | _kernel_primitive:NN | \hsize | \tex_hsize:D |
| 391 | _kernel_primitive:NN | \hskip | \tex_hskip:D |
| 392 | _kernel_primitive:NN | \hss | \tex_hss:D |
| 393 | _kernel_primitive:NN | \ht | \tex_ht:D |
| 394 | _kernel_primitive:NN | \hyphenation | \tex_hyphenation:D |
| 395 | _kernel_primitive:NN | \hyphenchar | \tex_hyphenchar:D |
| 396 | _kernel_primitive:NN | \hyphenpenalty | \tex_hyphenpenalty:D |
| 397 | _kernel_primitive:NN | \if | \tex_if:D |
| 398 | _kernel_primitive:NN | \ifcase | \tex_ifcase:D |
| 399 | _kernel_primitive:NN | \ifcat | \tex_ifcat:D |
| 400 | _kernel_primitive:NN | \ifdim | \tex_ifdim:D |
| 401 | _kernel_primitive:NN | \ifeof | \tex_ifeof:D |
| 402 | _kernel_primitive:NN | \iffalse | \tex_iffalse:D |
| 403 | _kernel_primitive:NN | \ifhbox | \tex_ifhbox:D |
| 404 | _kernel_primitive:NN | \ifhmode | \tex_ifhmode:D |
| 405 | _kernel_primitive:NN | \ifinner | \tex_ifinner:D |
| 406 | _kernel_primitive:NN | \ifmmode | \tex_ifmmode:D |
| 407 | _kernel_primitive:NN | \ifnum | \tex_ifnum:D |
| 408 | _kernel_primitive:NN | \ifodd | \tex_ifodd:D |
| 409 | _kernel_primitive:NN | \iftrue | \tex_iftrue:D |
| 410 | _kernel_primitive:NN | \ifvbox | \tex_ifvbox:D |
| 411 | _kernel_primitive:NN | \ifvmode | \tex_ifvmode:D |
| 412 | _kernel_primitive:NN | \ifvoid | \tex_ifvoid:D |
| 413 | _kernel_primitive:NN | \ifx | \tex_ifx:D |

| | | |
|-----|---|---------------------------------------|
| 414 | <code>_kernel_primitive:NN \ignorespaces</code> | <code>\tex_ignorespaces:D</code> |
| 415 | <code>_kernel_primitive:NN \immediate</code> | <code>\tex_immediate:D</code> |
| 416 | <code>_kernel_primitive:NN \indent</code> | <code>\tex_indent:D</code> |
| 417 | <code>_kernel_primitive:NN \input</code> | <code>\tex_input:D</code> |
| 418 | <code>_kernel_primitive:NN \inputlineno</code> | <code>\tex_inputlineno:D</code> |
| 419 | <code>_kernel_primitive:NN \insert</code> | <code>\tex_insert:D</code> |
| 420 | <code>_kernel_primitive:NN \insertpenalties</code> | <code>\tex_insertpenalties:D</code> |
| 421 | <code>_kernel_primitive:NN \interlinepenalty</code> | <code>\tex_interlinepenalty:D</code> |
| 422 | <code>_kernel_primitive:NN \jobname</code> | <code>\tex_jobname:D</code> |
| 423 | <code>_kernel_primitive:NN \kern</code> | <code>\tex_kern:D</code> |
| 424 | <code>_kernel_primitive:NN \language</code> | <code>\tex_language:D</code> |
| 425 | <code>_kernel_primitive:NN \lastbox</code> | <code>\tex_lastbox:D</code> |
| 426 | <code>_kernel_primitive:NN \lastkern</code> | <code>\tex_lastkern:D</code> |
| 427 | <code>_kernel_primitive:NN \lastpenalty</code> | <code>\tex_lastpenalty:D</code> |
| 428 | <code>_kernel_primitive:NN \lastskip</code> | <code>\tex_lastskip:D</code> |
| 429 | <code>_kernel_primitive:NN \lccode</code> | <code>\tex_lccode:D</code> |
| 430 | <code>_kernel_primitive:NN \leaders</code> | <code>\tex_leaders:D</code> |
| 431 | <code>_kernel_primitive:NN \left</code> | <code>\tex_left:D</code> |
| 432 | <code>_kernel_primitive:NN \lefthyphenmin</code> | <code>\tex_lefthyphenmin:D</code> |
| 433 | <code>_kernel_primitive:NN \leftskip</code> | <code>\tex_leftskip:D</code> |
| 434 | <code>_kernel_primitive:NN \leqno</code> | <code>\tex_leqno:D</code> |
| 435 | <code>_kernel_primitive:NN \let</code> | <code>\tex_let:D</code> |
| 436 | <code>_kernel_primitive:NN \limits</code> | <code>\tex_limits:D</code> |
| 437 | <code>_kernel_primitive:NN \linepenalty</code> | <code>\tex_linepenalty:D</code> |
| 438 | <code>_kernel_primitive:NN \lineskip</code> | <code>\tex_lineskip:D</code> |
| 439 | <code>_kernel_primitive:NN \lineskiplimit</code> | <code>\tex_lineskiplimit:D</code> |
| 440 | <code>_kernel_primitive:NN \long</code> | <code>\tex_long:D</code> |
| 441 | <code>_kernel_primitive:NN \looseness</code> | <code>\tex_looseness:D</code> |
| 442 | <code>_kernel_primitive:NN \lower</code> | <code>\tex_lower:D</code> |
| 443 | <code>_kernel_primitive:NN \lowercase</code> | <code>\tex_lowercase:D</code> |
| 444 | <code>_kernel_primitive:NN \mag</code> | <code>\tex_mag:D</code> |
| 445 | <code>_kernel_primitive:NN \mark</code> | <code>\tex_mark:D</code> |
| 446 | <code>_kernel_primitive:NN \mathaccent</code> | <code>\tex_mathaccent:D</code> |
| 447 | <code>_kernel_primitive:NN \mathbin</code> | <code>\tex_mathbin:D</code> |
| 448 | <code>_kernel_primitive:NN \mathchar</code> | <code>\tex_mathchar:D</code> |
| 449 | <code>_kernel_primitive:NN \mathchardef</code> | <code>\tex_mathchardef:D</code> |
| 450 | <code>_kernel_primitive:NN \mathchoice</code> | <code>\tex_mathchoice:D</code> |
| 451 | <code>_kernel_primitive:NN \mathclose</code> | <code>\tex_mathclose:D</code> |
| 452 | <code>_kernel_primitive:NN \mathcode</code> | <code>\tex_mathcode:D</code> |
| 453 | <code>_kernel_primitive:NN \mathinner</code> | <code>\tex_mathinner:D</code> |
| 454 | <code>_kernel_primitive:NN \mathop</code> | <code>\tex_mathop:D</code> |
| 455 | <code>_kernel_primitive:NN \mathopen</code> | <code>\tex_mathopen:D</code> |
| 456 | <code>_kernel_primitive:NN \mathord</code> | <code>\tex_mathord:D</code> |
| 457 | <code>_kernel_primitive:NN \mathpunct</code> | <code>\tex_mathpunct:D</code> |
| 458 | <code>_kernel_primitive:NN \mathrel</code> | <code>\tex_mathrel:D</code> |
| 459 | <code>_kernel_primitive:NN \mathsurround</code> | <code>\tex_mathsurround:D</code> |
| 460 | <code>_kernel_primitive:NN \maxdeadcycles</code> | <code>\tex_maxdeadcycles:D</code> |
| 461 | <code>_kernel_primitive:NN \maxdepth</code> | <code>\tex_maxdepth:D</code> |
| 462 | <code>_kernel_primitive:NN \meaning</code> | <code>\tex_meaning:D</code> |
| 463 | <code>_kernel_primitive:NN \medmuskip</code> | <code>\tex_medmuskip:D</code> |
| 464 | <code>_kernel_primitive:NN \message</code> | <code>\tex_message:D</code> |
| 465 | <code>_kernel_primitive:NN \mkern</code> | <code>\tex_mkern:D</code> |
| 466 | <code>_kernel_primitive:NN \month</code> | <code>\tex_month:D</code> |
| 467 | <code>_kernel_primitive:NN \moveleft</code> | <code>\tex_moveleft:D</code> |

| | | | |
|-----|------------------------|-----------------------|------------------------------|
| 468 | _kernel_primitive:NN | \moveright | \tex_moveright:D |
| 469 | _kernel_primitive:NN | \mskip | \tex_mskip:D |
| 470 | _kernel_primitive:NN | \multiply | \tex_multiply:D |
| 471 | _kernel_primitive:NN | \muskip | \tex_muskip:D |
| 472 | _kernel_primitive:NN | \muskipdef | \tex_muskipdef:D |
| 473 | _kernel_primitive:NN | \newlinechar | \tex_newlinechar:D |
| 474 | _kernel_primitive:NN | \noalign | \tex_noalign:D |
| 475 | _kernel_primitive:NN | \noboundary | \tex_noboundary:D |
| 476 | _kernel_primitive:NN | \noexpand | \tex_noexpand:D |
| 477 | _kernel_primitive:NN | \noindent | \tex_noindent:D |
| 478 | _kernel_primitive:NN | \nolimits | \tex_nolimits:D |
| 479 | _kernel_primitive:NN | \nonscript | \tex_nonscript:D |
| 480 | _kernel_primitive:NN | \nonstopmode | \tex_nonstopmode:D |
| 481 | _kernel_primitive:NN | \nulldelimiterspace | \tex_nulldelimiterspace:D |
| 482 | _kernel_primitive:NN | \nullfont | \tex_nullfont:D |
| 483 | _kernel_primitive:NN | \number | \tex_number:D |
| 484 | _kernel_primitive:NN | \omit | \tex_omit:D |
| 485 | _kernel_primitive:NN | \openin | \tex_openin:D |
| 486 | _kernel_primitive:NN | \openout | \tex_openout:D |
| 487 | _kernel_primitive:NN | \or | \tex_or:D |
| 488 | _kernel_primitive:NN | \outer | \tex_outer:D |
| 489 | _kernel_primitive:NN | \output | \tex_output:D |
| 490 | _kernel_primitive:NN | \outputpenalty | \tex_outputpenalty:D |
| 491 | _kernel_primitive:NN | \over | \tex_over:D |
| 492 | _kernel_primitive:NN | \overfullrule | \tex_overfullrule:D |
| 493 | _kernel_primitive:NN | \overline | \tex_overline:D |
| 494 | _kernel_primitive:NN | \overwithdelims | \tex_overwithdelims:D |
| 495 | _kernel_primitive:NN | \pagedepth | \tex_pagedepth:D |
| 496 | _kernel_primitive:NN | \pagefilllstretch | \tex_pagefilllstretch:D |
| 497 | _kernel_primitive:NN | \pagefillstretch | \tex_pagefillstretch:D |
| 498 | _kernel_primitive:NN | \pagefilstretch | \tex_pagefilstretch:D |
| 499 | _kernel_primitive:NN | \pagegoal | \tex_pagegoal:D |
| 500 | _kernel_primitive:NN | \pageshrink | \tex_pageshrink:D |
| 501 | _kernel_primitive:NN | \pagestretch | \tex_pagestretch:D |
| 502 | _kernel_primitive:NN | \pagetotal | \tex_pagetotal:D |
| 503 | _kernel_primitive:NN | \par | \tex_par:D |
| 504 | _kernel_primitive:NN | \parfillskip | \tex_parfillskip:D |
| 505 | _kernel_primitive:NN | \parindent | \tex_parindent:D |
| 506 | _kernel_primitive:NN | \parshape | \tex_parshape:D |
| 507 | _kernel_primitive:NN | \parskip | \tex_parskip:D |
| 508 | _kernel_primitive:NN | \patterns | \tex_patterns:D |
| 509 | _kernel_primitive:NN | \pausing | \tex_pausing:D |
| 510 | _kernel_primitive:NN | \penalty | \tex_penalty:D |
| 511 | _kernel_primitive:NN | \postdisplaypenalty | \tex_postdisplaypenalty:D |
| 512 | _kernel_primitive:NN | \predisdisplaypenalty | \tex_predisdisplaypenalty:D |
| 513 | _kernel_primitive:NN | \predisplaysize | \tex_predisplaysize:D |
| 514 | _kernel_primitive:NN | \pretolerance | \tex_pretolerance:D |
| 515 | _kernel_primitive:NN | \prevdepth | \tex_prevdepth:D |
| 516 | _kernel_primitive:NN | \prevgraf | \tex_prevgraf:D |
| 517 | _kernel_primitive:NN | \radical | \tex_radical:D |
| 518 | _kernel_primitive:NN | \raise | \tex_raise:D |
| 519 | _kernel_primitive:NN | \read | \tex_read:D |
| 520 | _kernel_primitive:NN | \relax | \tex_relax:D |
| 521 | _kernel_primitive:NN | \relpenalty | \tex_relpenalty:D |

| | | |
|-----|---|---------------------------|
| 522 | _kernel_primitive:NN \right | \tex_right:D |
| 523 | _kernel_primitive:NN \righthypenmin | \tex_righthypenmin:D |
| 524 | _kernel_primitive:NN \rightskip | \tex_rightskip:D |
| 525 | _kernel_primitive:NN \romannumeral | \tex_romannumeral:D |
| 526 | _kernel_primitive:NN \scriptfont | \tex_scriptfont:D |
| 527 | _kernel_primitive:NN \scriptscriptfont | \tex_scriptscriptfont:D |
| 528 | _kernel_primitive:NN \scriptscriptstyle | \tex_scriptscriptstyle:D |
| 529 | _kernel_primitive:NN \scriptspace | \tex_scriptspace:D |
| 530 | _kernel_primitive:NN \scriptstyle | \tex_scriptstyle:D |
| 531 | _kernel_primitive:NN \scrollmode | \tex_scrollmode:D |
| 532 | _kernel_primitive:NN \setbox | \tex_setbox:D |
| 533 | _kernel_primitive:NN \setlanguage | \tex_setlanguage:D |
| 534 | _kernel_primitive:NN \sfcode | \tex_sfcode:D |
| 535 | _kernel_primitive:NN \shipout | \tex_shipout:D |
| 536 | _kernel_primitive:NN \show | \tex_show:D |
| 537 | _kernel_primitive:NN \showbox | \tex_showbox:D |
| 538 | _kernel_primitive:NN \showboxbreadth | \tex_showboxbreadth:D |
| 539 | _kernel_primitive:NN \showboxdepth | \tex_showboxdepth:D |
| 540 | _kernel_primitive:NN \showlists | \tex_showlists:D |
| 541 | _kernel_primitive:NN \showthe | \tex_showthe:D |
| 542 | _kernel_primitive:NN \skewchar | \tex_skewchar:D |
| 543 | _kernel_primitive:NN \skip | \tex_skip:D |
| 544 | _kernel_primitive:NN \skipdef | \tex_skipdef:D |
| 545 | _kernel_primitive:NN \spacefactor | \tex_spacefactor:D |
| 546 | _kernel_primitive:NN \spaceskip | \tex_spaceskip:D |
| 547 | _kernel_primitive:NN \span | \tex_span:D |
| 548 | _kernel_primitive:NN \special | \tex_special:D |
| 549 | _kernel_primitive:NN \splitbotmark | \tex_splitbotmark:D |
| 550 | _kernel_primitive:NN \splitfirstmark | \tex_splitfirstmark:D |
| 551 | _kernel_primitive:NN \splitmaxdepth | \tex_splitmaxdepth:D |
| 552 | _kernel_primitive:NN \splittopskip | \tex_splittopskip:D |
| 553 | _kernel_primitive:NN \string | \tex_string:D |
| 554 | _kernel_primitive:NN \tabskip | \tex_tabskip:D |
| 555 | _kernel_primitive:NN \textfont | \tex_textfont:D |
| 556 | _kernel_primitive:NN \textstyle | \tex_textstyle:D |
| 557 | _kernel_primitive:NN \the | \tex_the:D |
| 558 | _kernel_primitive:NN \thickmuskip | \tex_thickmuskip:D |
| 559 | _kernel_primitive:NN \thinmuskip | \tex_thinmuskip:D |
| 560 | _kernel_primitive:NN \time | \tex_time:D |
| 561 | _kernel_primitive:NN \toks | \tex_toks:D |
| 562 | _kernel_primitive:NN \toksdef | \tex_toksdef:D |
| 563 | _kernel_primitive:NN \tolerance | \tex_tolerance:D |
| 564 | _kernel_primitive:NN \topmark | \tex_topmark:D |
| 565 | _kernel_primitive:NN \topskip | \tex_topskip:D |
| 566 | _kernel_primitive:NN \tracingcommands | \tex_tracingcommands:D |
| 567 | _kernel_primitive:NN \tracinglostchars | \tex_tracinglostchars:D |
| 568 | _kernel_primitive:NN \tracingmacros | \tex_tracingmacros:D |
| 569 | _kernel_primitive:NN \tracingonline | \tex_tracingonline:D |
| 570 | _kernel_primitive:NN \tracingoutput | \tex_tracingoutput:D |
| 571 | _kernel_primitive:NN \tracingpages | \tex_tracingpages:D |
| 572 | _kernel_primitive:NN \tracingparagraphs | \tex_tracingparagraphs:D |
| 573 | _kernel_primitive:NN \tracingrestores | \tex_tracingrestores:D |
| 574 | _kernel_primitive:NN \tracingstats | \tex_tracingstats:D |
| 575 | _kernel_primitive:NN \uccode | \tex_uccode:D |

| | | | |
|-----|------------------------|---------------|---------------------|
| 576 | __kernel_primitive:NN | \uchyph | \tex_uchyph:D |
| 577 | __kernel_primitive:NN | \underline | \tex_underline:D |
| 578 | __kernel_primitive:NN | \unhbox | \tex_unhbox:D |
| 579 | __kernel_primitive:NN | \unhcopy | \tex_unhcopy:D |
| 580 | __kernel_primitive:NN | \unkern | \tex_unkern:D |
| 581 | __kernel_primitive:NN | \unpenalty | \tex_unpenalty:D |
| 582 | __kernel_primitive:NN | \unskip | \tex_unskip:D |
| 583 | __kernel_primitive:NN | \unvbox | \tex_unvbox:D |
| 584 | __kernel_primitive:NN | \unvcopy | \tex_unvcopy:D |
| 585 | __kernel_primitive:NN | \uppercase | \tex_uppercase:D |
| 586 | __kernel_primitive:NN | \vadjust | \tex_vadjust:D |
| 587 | __kernel_primitive:NN | \valign | \tex_valign:D |
| 588 | __kernel_primitive:NN | \vbadness | \tex_vbadness:D |
| 589 | __kernel_primitive:NN | \vbox | \tex_vbox:D |
| 590 | __kernel_primitive:NN | \vcenter | \tex_vcenter:D |
| 591 | __kernel_primitive:NN | \vfil | \tex_vfil:D |
| 592 | __kernel_primitive:NN | \vfill | \tex_vfill:D |
| 593 | __kernel_primitive:NN | \vfilneg | \tex_vfilneg:D |
| 594 | __kernel_primitive:NN | \vfuzz | \tex_vfuzz:D |
| 595 | __kernel_primitive:NN | \voffset | \tex_voffset:D |
| 596 | __kernel_primitive:NN | \vrule | \tex_vrule:D |
| 597 | __kernel_primitive:NN | \vsize | \tex_vsize:D |
| 598 | __kernel_primitive:NN | \vskip | \tex_vskip:D |
| 599 | __kernel_primitive:NN | \vsplit | \tex_vsplit:D |
| 600 | __kernel_primitive:NN | \vss | \tex_vss:D |
| 601 | __kernel_primitive:NN | \vtop | \tex_vtop:D |
| 602 | __kernel_primitive:NN | \wd | \tex_wd:D |
| 603 | __kernel_primitive:NN | \widowpenalty | \tex_widowpenalty:D |
| 604 | __kernel_primitive:NN | \write | \tex_write:D |
| 605 | __kernel_primitive:NN | \xdef | \tex_xdef:D |
| 606 | __kernel_primitive:NN | \xleaders | \tex_xleaders:D |
| 607 | __kernel_primitive:NN | \xspaceskip | \tex_xspaceskip:D |
| 608 | __kernel_primitive:NN | \year | \tex_year:D |

Since L^AT_EX3 requires at least the ε -T_EX extensions, we also rename the additional primitives. These are all given the prefix `\etex_`.

| | | | |
|-----|------------------------|------------------------|-------------------------------|
| 609 | __kernel_primitive:NN | \beginL | \etex_beginL:D |
| 610 | __kernel_primitive:NN | \beginR | \etex_beginR:D |
| 611 | __kernel_primitive:NN | \botmarks | \etex_botmarks:D |
| 612 | __kernel_primitive:NN | \clubpenalties | \etex_clubpenalties:D |
| 613 | __kernel_primitive:NN | \currentgrouplevel | \etex_currentgrouplevel:D |
| 614 | __kernel_primitive:NN | \currentgrouptype | \etex_currentgrouptype:D |
| 615 | __kernel_primitive:NN | \currentifbranch | \etex_currentifbranch:D |
| 616 | __kernel_primitive:NN | \currentiflevel | \etex_currentiflevel:D |
| 617 | __kernel_primitive:NN | \currentifttype | \etex_currentifttype:D |
| 618 | __kernel_primitive:NN | \detokenize | \etex_detokenize:D |
| 619 | __kernel_primitive:NN | \dimexpr | \etex_dimexpr:D |
| 620 | __kernel_primitive:NN | \displaywidowpenalties | \etex_displaywidowpenalties:D |
| 621 | __kernel_primitive:NN | \endL | \etex_endL:D |
| 622 | __kernel_primitive:NN | \endR | \etex_endR:D |
| 623 | __kernel_primitive:NN | \eTeXrevision | \etex_eTeXrevision:D |
| 624 | __kernel_primitive:NN | \eTeXversion | \etex_eTeXversion:D |
| 625 | __kernel_primitive:NN | \everyeof | \etex_everyeof:D |
| 626 | __kernel_primitive:NN | \firstmarks | \etex_firstmarks:D |

| | | |
|-----|--|--|
| 627 | <code>__kernel_primitive:NN \fontchardp</code> | <code>\etex_fontchardp:D</code> |
| 628 | <code>__kernel_primitive:NN \fontcharht</code> | <code>\etex_fontcharht:D</code> |
| 629 | <code>__kernel_primitive:NN \fontcharic</code> | <code>\etex_fontcharic:D</code> |
| 630 | <code>__kernel_primitive:NN \fontcharwd</code> | <code>\etex_fontcharwd:D</code> |
| 631 | <code>__kernel_primitive:NN \glueexpr</code> | <code>\etex_glueexpr:D</code> |
| 632 | <code>__kernel_primitive:NN \glueshrink</code> | <code>\etex_glueshrink:D</code> |
| 633 | <code>__kernel_primitive:NN \glueshrinkorder</code> | <code>\etex_glueshrinkorder:D</code> |
| 634 | <code>__kernel_primitive:NN \gluestretch</code> | <code>\etex_gluestretch:D</code> |
| 635 | <code>__kernel_primitive:NN \gluestretchorder</code> | <code>\etex_gluestretchorder:D</code> |
| 636 | <code>__kernel_primitive:NN \gluetomu</code> | <code>\etex_gluetomu:D</code> |
| 637 | <code>__kernel_primitive:NN \ifcsname</code> | <code>\etex_ifcsname:D</code> |
| 638 | <code>__kernel_primitive:NN \ifdefined</code> | <code>\etex_ifdefined:D</code> |
| 639 | <code>__kernel_primitive:NN \iffontchar</code> | <code>\etex_iffontchar:D</code> |
| 640 | <code>__kernel_primitive:NN \interactionmode</code> | <code>\etex_interactionmode:D</code> |
| 641 | <code>__kernel_primitive:NN \interlinepenalties</code> | <code>\etex_interlinepenalties:D</code> |
| 642 | <code>__kernel_primitive:NN \lastlinefit</code> | <code>\etex_lastlinefit:D</code> |
| 643 | <code>__kernel_primitive:NN \lastnodetype</code> | <code>\etex_lastnodetype:D</code> |
| 644 | <code>__kernel_primitive:NN \marks</code> | <code>\etex_marks:D</code> |
| 645 | <code>__kernel_primitive:NN \middle</code> | <code>\etex_middle:D</code> |
| 646 | <code>__kernel_primitive:NN \muexpr</code> | <code>\etex_muexpr:D</code> |
| 647 | <code>__kernel_primitive:NN \mutoglua</code> | <code>\etex_mutoglua:D</code> |
| 648 | <code>__kernel_primitive:NN \numexpr</code> | <code>\etex_numexpr:D</code> |
| 649 | <code>__kernel_primitive:NN \pagediscards</code> | <code>\etex_pagediscards:D</code> |
| 650 | <code>__kernel_primitive:NN \parshapedimen</code> | <code>\etex_parshapedimen:D</code> |
| 651 | <code>__kernel_primitive:NN \parshapeindent</code> | <code>\etex_parshapeindent:D</code> |
| 652 | <code>__kernel_primitive:NN \parshapelength</code> | <code>\etex_parshapelength:D</code> |
| 653 | <code>__kernel_primitive:NN \predisplaydirection</code> | <code>\etex_predisplaydirection:D</code> |
| 654 | <code>__kernel_primitive:NN \protected</code> | <code>\etex_protected:D</code> |
| 655 | <code>__kernel_primitive:NN \readline</code> | <code>\etex_readline:D</code> |
| 656 | <code>__kernel_primitive:NN \savingshyphcodes</code> | <code>\etex_savingshyphcodes:D</code> |
| 657 | <code>__kernel_primitive:NN \savingsvdiscards</code> | <code>\etex_savingsvdiscards:D</code> |
| 658 | <code>__kernel_primitive:NN \scantokens</code> | <code>\etex_scantokens:D</code> |
| 659 | <code>__kernel_primitive:NN \showgroups</code> | <code>\etex_showgroups:D</code> |
| 660 | <code>__kernel_primitive:NN \showifs</code> | <code>\etex_showifs:D</code> |
| 661 | <code>__kernel_primitive:NN \showtokens</code> | <code>\etex_showtokens:D</code> |
| 662 | <code>__kernel_primitive:NN \splitbotmarks</code> | <code>\etex_splitbotmarks:D</code> |
| 663 | <code>__kernel_primitive:NN \splitdiscards</code> | <code>\etex_splitdiscards:D</code> |
| 664 | <code>__kernel_primitive:NN \splitfirstmarks</code> | <code>\etex_splitfirstmarks:D</code> |
| 665 | <code>__kernel_primitive:NN \TeXXeTstate</code> | <code>\etex_TeXeTstate:D</code> |
| 666 | <code>__kernel_primitive:NN \topmarks</code> | <code>\etex_topmarks:D</code> |
| 667 | <code>__kernel_primitive:NN \tracingassigns</code> | <code>\etex_tracingassigns:D</code> |
| 668 | <code>__kernel_primitive:NN \tracinggroups</code> | <code>\etex_tracinggroups:D</code> |
| 669 | <code>__kernel_primitive:NN \tracingifs</code> | <code>\etex_tracingifs:D</code> |
| 670 | <code>__kernel_primitive:NN \tracingnesting</code> | <code>\etex_tracingnesting:D</code> |
| 671 | <code>__kernel_primitive:NN \tracingscantokens</code> | <code>\etex_tracingscantokens:D</code> |
| 672 | <code>__kernel_primitive:NN \unexpanded</code> | <code>\etex_unexpanded:D</code> |
| 673 | <code>__kernel_primitive:NN \unless</code> | <code>\etex_unless:D</code> |
| 674 | <code>__kernel_primitive:NN \widowpenalties</code> | <code>\etex_widowpenalties:D</code> |

The newer primitives are more complex: there are an awful lot of them, and we don't use them all at the moment. So the following is selective, based on those also available in LuaTeX or used in expl3. In the case of the pdfTeX primitives, we retain `pdf` at the start of the names *only* for directly PDF-related primitives, as there are a lot of pdfTeX primitives that start `\pdf...` but are not related to PDF output. These ones related to

PDF output or only work in PDF mode.

| | | | |
|-----|------------------------|--------------------------|------------------------------------|
| 675 | _kernel_primitive:NN | \pdfannot | \pdfTEX_pdfannot:D |
| 676 | _kernel_primitive:NN | \pdfcatalog | \pdfTEX_pdfcatalog:D |
| 677 | _kernel_primitive:NN | \pdfcompresslevel | \pdfTEX_pdfcompresslevel:D |
| 678 | _kernel_primitive:NN | \pdfcolorstack | \pdfTEX_pdfcolorstack:D |
| 679 | _kernel_primitive:NN | \pdfcolorstackinit | \pdfTEX_pdfcolorstackinit:D |
| 680 | _kernel_primitive:NN | \pdfcreationdate | \pdfTEX_pdfcreationdate:D |
| 681 | _kernel_primitive:NN | \pdfdecimaldigits | \pdfTEX_pdfdecimaldigits:D |
| 682 | _kernel_primitive:NN | \pdfdest | \pdfTEX_pdfdest:D |
| 683 | _kernel_primitive:NN | \pdfdestmargin | \pdfTEX_pdfdestmargin:D |
| 684 | _kernel_primitive:NN | \pdfendlink | \pdfTEX_pdfendlink:D |
| 685 | _kernel_primitive:NN | \pdfendthread | \pdfTEX_pdfendthread:D |
| 686 | _kernel_primitive:NN | \pdffontattr | \pdfTEX_pdffontattr:D |
| 687 | _kernel_primitive:NN | \pdffontname | \pdfTEX_pdffontname:D |
| 688 | _kernel_primitive:NN | \pdffontobjnum | \pdfTEX_pdffontobjnum:D |
| 689 | _kernel_primitive:NN | \pdfgamma | \pdfTEX_pdfgamma:D |
| 690 | _kernel_primitive:NN | \pdfimageapplygamma | \pdfTEX_pdfimageapplygamma:D |
| 691 | _kernel_primitive:NN | \pdfimagegamma | \pdfTEX_pdfimagegamma:D |
| 692 | _kernel_primitive:NN | \pdfgentounicode | \pdfTEX_pdfgentounicode:D |
| 693 | _kernel_primitive:NN | \pdfglyptounicode | \pdfTEX_pdfglyptounicode:D |
| 694 | _kernel_primitive:NN | \pdfhorigin | \pdfTEX_pdfhorigin:D |
| 695 | _kernel_primitive:NN | \pdfimagehicolor | \pdfTEX_pdfimagehicolor:D |
| 696 | _kernel_primitive:NN | \pdfimageresolution | \pdfTEX_pdfimageresolution:D |
| 697 | _kernel_primitive:NN | \pdfincludechars | \pdfTEX_pdfincludechars:D |
| 698 | _kernel_primitive:NN | \pdfinclusioncopyfonts | \pdfTEX_pdfinclusioncopyfonts:D |
| 699 | _kernel_primitive:NN | \pdfinclusionerrorlevel | \pdfTEX_pdfinclusionerrorlevel:D |
| 700 | _kernel_primitive:NN | \pdfinfo | \pdfTEX_pdfinfo:D |
| 701 | _kernel_primitive:NN | \pdflastannot | \pdfTEX_pdflastannot:D |
| 702 | _kernel_primitive:NN | \pdflastlink | \pdfTEX_pdflastlink:D |
| 703 | _kernel_primitive:NN | \pdflastobj | \pdfTEX_pdflastobj:D |
| 704 | _kernel_primitive:NN | \pdflastxform | \pdfTEX_pdflastxform:D |
| 705 | _kernel_primitive:NN | \pdflastximage | \pdfTEX_pdflastximage:D |
| 706 | _kernel_primitive:NN | \pdflastximagecolordepth | \pdfTEX_pdflastximagecolordepth:D |
| 707 | _kernel_primitive:NN | \pdflastximagepages | \pdfTEX_pdflastximagepages:D |
| 708 | _kernel_primitive:NN | \pdflinkmargin | \pdfTEX_pdflinkmargin:D |
| 709 | _kernel_primitive:NN | \pdfliteral | \pdfTEX_pdfliteral:D |
| 710 | _kernel_primitive:NN | \pdfminorversion | \pdfTEX_pdfminorversion:D |
| 711 | _kernel_primitive:NN | \pdfnames | \pdfTEX_pdfnames:D |
| 712 | _kernel_primitive:NN | \pdfobj | \pdfTEX_pdfobj:D |
| 713 | _kernel_primitive:NN | \pdfobjcompresslevel | \pdfTEX_pdfobjcompresslevel:D |
| 714 | _kernel_primitive:NN | \pdfoutline | \pdfTEX_pdfoutline:D |
| 715 | _kernel_primitive:NN | \pdfoutput | \pdfTEX_pdfoutput:D |
| 716 | _kernel_primitive:NN | \pdfpageattr | \pdfTEX_pdfpageattr:D |
| 717 | _kernel_primitive:NN | \pdfpagebox | \pdfTEX_pdfpagebox:D |
| 718 | _kernel_primitive:NN | \pdfpageref | \pdfTEX_pdfpageref:D |
| 719 | _kernel_primitive:NN | \pdfpageresources | \pdfTEX_pdfpageresources:D |
| 720 | _kernel_primitive:NN | \pdfpagesattr | \pdfTEX_pdfpagesattr:D |
| 721 | _kernel_primitive:NN | \pdfrefobj | \pdfTEX_pdfrefobj:D |
| 722 | _kernel_primitive:NN | \pdfrefxform | \pdfTEX_pdfrefxform:D |
| 723 | _kernel_primitive:NN | \pdfrefximage | \pdfTEX_pdfrefximage:D |
| 724 | _kernel_primitive:NN | \pdfrestore | \pdfTEX_pdfrestore:D |
| 725 | _kernel_primitive:NN | \pdfretval | \pdfTEX_pdfretval:D |
| 726 | _kernel_primitive:NN | \pdfsave | \pdfTEX_pdfsave:D |
| 727 | _kernel_primitive:NN | \pdfsetmatrix | \pdfTEX_pdfsetmatrix:D |

| | | | |
|-----|-------------------------------------|-----------------------------------|--|
| 728 | <code>__kernel_primitive:NN</code> | <code>\pdfstartlink</code> | <code>\pdftex_pdfstartlink:D</code> |
| 729 | <code>__kernel_primitive:NN</code> | <code>\pdfstartthread</code> | <code>\pdftex_pdfstartthread:D</code> |
| 730 | <code>__kernel_primitive:NN</code> | <code>\pdfsuppressptexinfo</code> | <code>\pdftex_pdfsuppressptexinfo:D</code> |
| 731 | <code>__kernel_primitive:NN</code> | <code>\pdfthread</code> | <code>\pdftex_pdfthread:D</code> |
| 732 | <code>__kernel_primitive:NN</code> | <code>\pdfthreadmargin</code> | <code>\pdftex_pdfthreadmargin:D</code> |
| 733 | <code>__kernel_primitive:NN</code> | <code>\pdftrailer</code> | <code>\pdftex_pdftrailer:D</code> |
| 734 | <code>__kernel_primitive:NN</code> | <code>\pdfuniqueresname</code> | <code>\pdftex_pdfuniqueresname:D</code> |
| 735 | <code>__kernel_primitive:NN</code> | <code>\pdfvorigin</code> | <code>\pdftex_pdfvorigin:D</code> |
| 736 | <code>__kernel_primitive:NN</code> | <code>\pdfxform</code> | <code>\pdftex_pdfxform:D</code> |
| 737 | <code>__kernel_primitive:NN</code> | <code>\pdfxformattr</code> | <code>\pdftex_pdfxformattr:D</code> |
| 738 | <code>__kernel_primitive:NN</code> | <code>\pdfxformname</code> | <code>\pdftex_pdfxformname:D</code> |
| 739 | <code>__kernel_primitive:NN</code> | <code>\pdfxformresources</code> | <code>\pdftex_pdfxformresources:D</code> |
| 740 | <code>__kernel_primitive:NN</code> | <code>\pdfximage</code> | <code>\pdftex_pdfximage:D</code> |
| 741 | <code>__kernel_primitive:NN</code> | <code>\pdfximagebbox</code> | <code>\pdftex_pdfximagebbox:D</code> |

While these are not.

| | | | |
|-----|-------------------------------------|----------------------------------|--|
| 742 | <code>__kernel_primitive:NN</code> | <code>\ifpdfabsdim</code> | <code>\pdftex_ifabsdim:D</code> |
| 743 | <code>__kernel_primitive:NN</code> | <code>\ifpdfabsnum</code> | <code>\pdftex_ifabsnum:D</code> |
| 744 | <code>__kernel_primitive:NN</code> | <code>\ifpdfprimitive</code> | <code>\pdftex_ifprimitive:D</code> |
| 745 | <code>__kernel_primitive:NN</code> | <code>\pdfadjustspacing</code> | <code>\pdftex_adjustspacing:D</code> |
| 746 | <code>__kernel_primitive:NN</code> | <code>\pdfcopyfont</code> | <code>\pdftex_copyfont:D</code> |
| 747 | <code>__kernel_primitive:NN</code> | <code>\pdfdraftmode</code> | <code>\pdftex_draftmode:D</code> |
| 748 | <code>__kernel_primitive:NN</code> | <code>\pdfeachlinedepth</code> | <code>\pdftex_eachlinedepth:D</code> |
| 749 | <code>__kernel_primitive:NN</code> | <code>\pdfeachlineheight</code> | <code>\pdftex_eachlineheight:D</code> |
| 750 | <code>__kernel_primitive:NN</code> | <code>\pdffirstlineheight</code> | <code>\pdftex_firstlineheight:D</code> |
| 751 | <code>__kernel_primitive:NN</code> | <code>\pdffontexpand</code> | <code>\pdftex_fontexpand:D</code> |
| 752 | <code>__kernel_primitive:NN</code> | <code>\pdffontsize</code> | <code>\pdftex_fontsize:D</code> |
| 753 | <code>__kernel_primitive:NN</code> | <code>\pdfignoreddimen</code> | <code>\pdftex_ignoreddimen:D</code> |
| 754 | <code>__kernel_primitive:NN</code> | <code>\pdfinsertht</code> | <code>\pdftex_insertht:D</code> |
| 755 | <code>__kernel_primitive:NN</code> | <code>\pdflastlinedepth</code> | <code>\pdftex_lastlinedepth:D</code> |
| 756 | <code>__kernel_primitive:NN</code> | <code>\pdflastxpos</code> | <code>\pdftex_lastxpos:D</code> |
| 757 | <code>__kernel_primitive:NN</code> | <code>\pdflastypos</code> | <code>\pdftex_lastypos:D</code> |
| 758 | <code>__kernel_primitive:NN</code> | <code>\pdfmapfile</code> | <code>\pdftex_mapfile:D</code> |
| 759 | <code>__kernel_primitive:NN</code> | <code>\pdfmapline</code> | <code>\pdftex_mapline:D</code> |
| 760 | <code>__kernel_primitive:NN</code> | <code>\pdfnoligatures</code> | <code>\pdftex_noligatures:D</code> |
| 761 | <code>__kernel_primitive:NN</code> | <code>\pdfnormaldeviate</code> | <code>\pdftex_normaldeviate:D</code> |
| 762 | <code>__kernel_primitive:NN</code> | <code>\pdfpageheight</code> | <code>\pdftex_pageheight:D</code> |
| 763 | <code>__kernel_primitive:NN</code> | <code>\pdfpagewidth</code> | <code>\pdftex_pagewidth:D</code> |
| 764 | <code>__kernel_primitive:NN</code> | <code>\pdfpkmode</code> | <code>\pdftex_pkmode:D</code> |
| 765 | <code>__kernel_primitive:NN</code> | <code>\pdfpkresolution</code> | <code>\pdftex_pkresolution:D</code> |
| 766 | <code>__kernel_primitive:NN</code> | <code>\pdfprimitive</code> | <code>\pdftex_primitive:D</code> |
| 767 | <code>__kernel_primitive:NN</code> | <code>\pdfprotrudechars</code> | <code>\pdftex_protrudechars:D</code> |
| 768 | <code>__kernel_primitive:NN</code> | <code>\pdfpxdimen</code> | <code>\pdftex_pxdimen:D</code> |
| 769 | <code>__kernel_primitive:NN</code> | <code>\pdfrandomseed</code> | <code>\pdftex_randomseed:D</code> |
| 770 | <code>__kernel_primitive:NN</code> | <code>\pdfsavepos</code> | <code>\pdftex_savepos:D</code> |
| 771 | <code>__kernel_primitive:NN</code> | <code>\pdfstrcmp</code> | <code>\pdftex_strcmp:D</code> |
| 772 | <code>__kernel_primitive:NN</code> | <code>\pdfsetrandomseed</code> | <code>\pdftex_setrandomseed:D</code> |
| 773 | <code>__kernel_primitive:NN</code> | <code>\pdfshellescape</code> | <code>\pdftex_shellescape:D</code> |
| 774 | <code>__kernel_primitive:NN</code> | <code>\pdftracingfonts</code> | <code>\pdftex_tracingfonts:D</code> |
| 775 | <code>__kernel_primitive:NN</code> | <code>\pdfuniformdeviate</code> | <code>\pdftex_uniformdeviate:D</code> |

The version primitives are not related to PDF mode but are related to pdfTeX so retain the full prefix.

| | | | |
|-----|-------------------------------------|------------------------------|---------------------------------------|
| 776 | <code>__kernel_primitive:NN</code> | <code>\pdftexbanner</code> | <code>\pdftex_pdftexbanner:D</code> |
| 777 | <code>__kernel_primitive:NN</code> | <code>\pdftexrevision</code> | <code>\pdftex_pdftexrevision:D</code> |

```
778 \__kernel_primitive:NN \pdfTeXversion \pdfTeXpdfTeXversion:D
```

These ones appear in pdfTeX but don't have pdf in the name at all. (\syncTeX is odd as it's really not from pdfTeX but from SyncTeX!)

```
779 \__kernel_primitive:NN \efcode \pdfTeXefcode:D
780 \__kernel_primitive:NN \ifincsname \pdfTeXifincsname:D
781 \__kernel_primitive:NN \leftmarginkern \pdfTeXleftmarginkern:D
782 \__kernel_primitive:NN \letterspacefont \pdfTeXletterspacefont:D
783 \__kernel_primitive:NN \lpcode \pdfTeXlpcode:D
784 \__kernel_primitive:NN \quitvmode \pdfTeXquitvmode:D
785 \__kernel_primitive:NN \rightmarginkern \pdfTeXrightmarginkern:D
786 \__kernel_primitive:NN \rpcode \pdfTeXrpcode:D
787 \__kernel_primitive:NN \syncTeX \pdfTeXsyncTeX:D
788 \__kernel_primitive:NN \tagcode \pdfTeXtagcode:D
```

Post pdfTeX primitive availability gets more complex. Both XeTeX and LuaTeX have varying names for some primitives from pdfTeX. Particularly for LuaTeX tracking all of that would be hard. Instead, we now check that we only save primitives if they actually exist.

```
789 </initex | names | package>
790 {*initex | package>
791 \tex_long:D \tex_def:D \use_ii:nn #1#2 {#2}
792 \tex_long:D \tex_def:D \use_none:n #1 { }
793 \tex_long:D \tex_def:D \__kernel_primitive:NN #1#2
794 {
795 \etex_ifdefined:D #1
796 \tex_expandafter:D \use_ii:nn
797 \tex_fi:D
798 \use_none:n { \tex_global:D \tex_let:D #2 #1 }
799 {*initex>
800 \tex_global:D \tex_let:D #1 \tex_undefined:D
801 </initex>
802 }
803 </initex | package>
804 {*initex | names | package>
```

XeTeX-specific primitives. Note that XeTeX's \strcmp is handled earlier and is “rolled up” into \pdfstrcmp. With the exception of the version primitives these don't carry XeTeX through into the “base” name. A few cross-compatibility names which lack the pdf of the original are handled later.

```
805 \__kernel_primitive:NN \suppressfontnotfounderror \xetex_suppressfontnotfounderror:D
806 \__kernel_primitive:NN \XeTeXcharclass \xetex_charclass:D
807 \__kernel_primitive:NN \XeTeXcharglyph \xetex_charglyph:D
808 \__kernel_primitive:NN \XeTeXcountfeatures \xetex_countfeatures:D
809 \__kernel_primitive:NN \XeTeXcountglyphs \xetex_countglyphs:D
810 \__kernel_primitive:NN \XeTeXcountselectors \xetex_countselectors:D
811 \__kernel_primitive:NN \XeTeXcountvariations \xetex_countvariations:D
812 \__kernel_primitive:NN \XeTeXdefaultencoding \xetex_defaultencoding:D
813 \__kernel_primitive:NN \XeTeXdashbreakstate \xetex_dashbreakstate:D
814 \__kernel_primitive:NN \XeTeXfeaturecode \xetex_featurecode:D
815 \__kernel_primitive:NN \XeTeXfeaturename \xetex_featurename:D
816 \__kernel_primitive:NN \XeTeXfindfeaturebyname \xetex_findfeaturebyname:D
817 \__kernel_primitive:NN \XeTeXfindselectorbyname \xetex_findselectorbyname:D
818 \__kernel_primitive:NN \XeTeXfindvariationbyname \xetex_findvariationbyname:D
819 \__kernel_primitive:NN \XeTeXfirstfontchar \xetex_firstfontchar:D
```

| | | |
|-----|---|---|
| 820 | <code>__kernel_primitive:NN \XeTeXfonttype</code> | <code>\xetex_fonttype:D</code> |
| 821 | <code>__kernel_primitive:NN \XeTeXgenerateactualtext</code> | <code>\xetex_generateactualtext:D</code> |
| 822 | <code>__kernel_primitive:NN \XeTeXglyph</code> | <code>\xetex_glyph:D</code> |
| 823 | <code>__kernel_primitive:NN \XeTeXglyphbounds</code> | <code>\xetex_glyphbounds:D</code> |
| 824 | <code>__kernel_primitive:NN \XeTeXglyphindex</code> | <code>\xetex_glyphindex:D</code> |
| 825 | <code>__kernel_primitive:NN \XeTeXglyphname</code> | <code>\xetex_glyphname:D</code> |
| 826 | <code>__kernel_primitive:NN \XeTeXinputencoding</code> | <code>\xetex_inputencoding:D</code> |
| 827 | <code>__kernel_primitive:NN \XeTeXinputnormalization</code> | <code>\xetex_inputnormalization:D</code> |
| 828 | <code>__kernel_primitive:NN \XeTeXinterchartokenstate</code> | <code>\xetex_interchartokenstate:D</code> |
| 829 | <code>__kernel_primitive:NN \XeTeXinterchartoks</code> | <code>\xetex_interchartoks:D</code> |
| 830 | <code>__kernel_primitive:NN \XeTeXisdefaultselector</code> | <code>\xetex_isdefaultselector:D</code> |
| 831 | <code>__kernel_primitive:NN \XeTeXisexclusivefeature</code> | <code>\xetex_isexclusivefeature:D</code> |
| 832 | <code>__kernel_primitive:NN \XeTeXlastfontchar</code> | <code>\xetex_lastfontchar:D</code> |
| 833 | <code>__kernel_primitive:NN \XeTeXlinebreakskip</code> | <code>\xetex_linebreakskip:D</code> |
| 834 | <code>__kernel_primitive:NN \XeTeXlinebreaklocale</code> | <code>\xetex_linebreaklocale:D</code> |
| 835 | <code>__kernel_primitive:NN \XeTeXlinebreakpenalty</code> | <code>\xetex_linebreakpenalty:D</code> |
| 836 | <code>__kernel_primitive:NN \XeTeXOTcountfeatures</code> | <code>\xetex_OTcountfeatures:D</code> |
| 837 | <code>__kernel_primitive:NN \XeTeXOTcountlanguages</code> | <code>\xetex_OTcountlanguages:D</code> |
| 838 | <code>__kernel_primitive:NN \XeTeXOTcountscripts</code> | <code>\xetex_OTcountscripts:D</code> |
| 839 | <code>__kernel_primitive:NN \XeTeXOTfeaturetag</code> | <code>\xetex_OTfeaturetag:D</code> |
| 840 | <code>__kernel_primitive:NN \XeTeXOTlanguagetag</code> | <code>\xetex_OTlanguagetag:D</code> |
| 841 | <code>__kernel_primitive:NN \XeTeXOTscripttag</code> | <code>\xetex_OTscripttag:D</code> |
| 842 | <code>__kernel_primitive:NN \XeTeXpdffile</code> | <code>\xetex_pdffile:D</code> |
| 843 | <code>__kernel_primitive:NN \XeTeXpdfpagecount</code> | <code>\xetex_pdfpagecount:D</code> |
| 844 | <code>__kernel_primitive:NN \XeTeXpicfile</code> | <code>\xetex_picfile:D</code> |
| 845 | <code>__kernel_primitive:NN \XeTeXselectorname</code> | <code>\xetex_selectorname:D</code> |
| 846 | <code>__kernel_primitive:NN \XeTeXtracingfonts</code> | <code>\xetex_tracingfonts:D</code> |
| 847 | <code>__kernel_primitive:NN \XeTeXupwardsmode</code> | <code>\xetex_upwardsmode:D</code> |
| 848 | <code>__kernel_primitive:NN \XeTeXuseglyphmetrics</code> | <code>\xetex_useglyphmetrics:D</code> |
| 849 | <code>__kernel_primitive:NN \XeTeXvariation</code> | <code>\xetex_variation:D</code> |
| 850 | <code>__kernel_primitive:NN \XeTeXvariationdefault</code> | <code>\xetex_variationdefault:D</code> |
| 851 | <code>__kernel_primitive:NN \XeTeXvariationmax</code> | <code>\xetex_variationmax:D</code> |
| 852 | <code>__kernel_primitive:NN \XeTeXvariationmin</code> | <code>\xetex_variationmin:D</code> |
| 853 | <code>__kernel_primitive:NN \XeTeXvariationname</code> | <code>\xetex_variationname:D</code> |

The version primitives retain XeTeX.

| | | |
|-----|--|-------------------------------------|
| 854 | <code>__kernel_primitive:NN \XeTeXrevision</code> | <code>\xetex_XeTeXrevision:D</code> |
| 855 | <code>__kernel_primitive:NN \XeTeXversion</code> | <code>\xetex_XeTeXversion:D</code> |

Primitives from pdfTeX that XeTeX renames: also helps with LuaTeX.

| | | |
|-----|--|------------------------------------|
| 856 | <code>__kernel_primitive:NN \ifprimitive</code> | <code>\pdfTEX_ifprimitive:D</code> |
| 857 | <code>__kernel_primitive:NN \primitive</code> | <code>\pdfTEX_primitive:D</code> |
| 858 | <code>__kernel_primitive:NN \shellescape</code> | <code>\pdfTEX_shellescape:D</code> |

Primitives from LuaTeX, some of which have been ported back to XeTeX. Notice that `\expanded` was intended for pdfTeX 1.50 but as that was not released we call this a LuaTeX primitive.

| | | |
|-----|--|--|
| 859 | <code>__kernel_primitive:NN \alignmark</code> | <code>\luaTeX_alignmark:D</code> |
| 860 | <code>__kernel_primitive:NN \aligntab</code> | <code>\luaTeX_aligntab:D</code> |
| 861 | <code>__kernel_primitive:NN \attribute</code> | <code>\luaTeX_attribute:D</code> |
| 862 | <code>__kernel_primitive:NN \attributedef</code> | <code>\luaTeX_attributedef:D</code> |
| 863 | <code>__kernel_primitive:NN \begincsname</code> | <code>\luaTeX_begincsname:D</code> |
| 864 | <code>__kernel_primitive:NN \catcodetable</code> | <code>\luaTeX_catcodetable:D</code> |
| 865 | <code>__kernel_primitive:NN \clearmarks</code> | <code>\luaTeX_clearmarks:D</code> |
| 866 | <code>__kernel_primitive:NN \crampeddisplaystyle</code> | <code>\luaTeX_crampeddisplaystyle:D</code> |

| | | | |
|-----|------------------------|---------------------------|-------------------------------------|
| 867 | _kernel_primitive:NN | \crampedscriptscriptstyle | \luatex_crampedscriptscriptstyle:D |
| 868 | _kernel_primitive:NN | \crampedscriptstyle | \luatex_crampedscriptstyle:D |
| 869 | _kernel_primitive:NN | \crampedtextstyle | \luatex_crampedtextstyle:D |
| 870 | _kernel_primitive:NN | \directlua | \luatex_directlua:D |
| 871 | _kernel_primitive:NN | \dviextension | \luatex_dviextension:D |
| 872 | _kernel_primitive:NN | \dvifedback | \luatex_dvifedback:D |
| 873 | _kernel_primitive:NN | \dvivariable | \luatex_dvivariable:D |
| 874 | _kernel_primitive:NN | \etoksapp | \luatex_etoksapp:D |
| 875 | _kernel_primitive:NN | \etokspre | \luatex_etokspre:D |
| 876 | _kernel_primitive:NN | \expanded | \luatex_expanded:D |
| 877 | _kernel_primitive:NN | \firstvalidlanguage | \luatex_firstvalidlanguage:D |
| 878 | _kernel_primitive:NN | \fontid | \luatex_fontid:D |
| 879 | _kernel_primitive:NN | \formatname | \luatex_formatname:D |
| 880 | _kernel_primitive:NN | \hjcode | \luatex_hjcode:D |
| 881 | _kernel_primitive:NN | \hpack | \luatex_hpack:D |
| 882 | _kernel_primitive:NN | \hyphenationbounds | \luatex_hyphenationbounds:D |
| 883 | _kernel_primitive:NN | \hyphenationmin | \luatex_hyphenationmin:D |
| 884 | _kernel_primitive:NN | \gleaders | \luatex_gleaders:D |
| 885 | _kernel_primitive:NN | \initcatcodetable | \luatex_initcatcodetable:D |
| 886 | _kernel_primitive:NN | \lastnamedcs | \luatex_lastnamedcs:D |
| 887 | _kernel_primitive:NN | \latelua | \luatex_latelua:D |
| 888 | _kernel_primitive:NN | \letcharcode | \luatex_letcharcode:D |
| 889 | _kernel_primitive:NN | \luaescapestring | \luatex_luaescapestring:D |
| 890 | _kernel_primitive:NN | \luafunction | \luatex_luafunction:D |
| 891 | _kernel_primitive:NN | \luatexbanner | \luatex_luatexbanner:D |
| 892 | _kernel_primitive:NN | \luatexdatestamp | \luatex_luatexdatestamp:D |
| 893 | _kernel_primitive:NN | \luatexrevision | \luatex_luatexrevision:D |
| 894 | _kernel_primitive:NN | \luatexversion | \luatex_luatexversion:D |
| 895 | _kernel_primitive:NN | \mathdisplayskipmode | \luatex_mathdisplayskipmode:D |
| 896 | _kernel_primitive:NN | \matheqnogapstep | \luatex_matheqnogapstep:D |
| 897 | _kernel_primitive:NN | \mathnolimitsmode | \luatex_mathnolimitsmode:D |
| 898 | _kernel_primitive:NN | \mathoption | \luatex_mathoption:D |
| 899 | _kernel_primitive:NN | \mathrulesfam | \luatex_mathrulesfam:D |
| 900 | _kernel_primitive:NN | \mathscriptsmode | \luatex_mathscriptsmode:D |
| 901 | _kernel_primitive:NN | \mathstyle | \luatex_mathstyle:D |
| 902 | _kernel_primitive:NN | \mathsurroundmode | \luatex_mathsurroundmode:D |
| 903 | _kernel_primitive:NN | \mathsurroundskip | \luatex_mathsurroundskip:D |
| 904 | _kernel_primitive:NN | \nohrule | \luatex_nohrule:D |
| 905 | _kernel_primitive:NN | \nokerns | \luatex_nokerns:D |
| 906 | _kernel_primitive:NN | \noligs | \luatex_noligs:D |
| 907 | _kernel_primitive:NN | \nospaces | \luatex_nospaces:D |
| 908 | _kernel_primitive:NN | \novrule | \luatex_novrule:D |
| 909 | _kernel_primitive:NN | \outputbox | \luatex_outputbox:D |
| 910 | _kernel_primitive:NN | \pagebottomoffset | \luatex_pagebottomoffset:D |
| 911 | _kernel_primitive:NN | \pageleftoffset | \luatex_pageleftoffset:D |
| 912 | _kernel_primitive:NN | \pagerightoffset | \luatex_pagerightoffset:D |
| 913 | _kernel_primitive:NN | \pagetopoffset | \luatex_pagetopoffset:D |
| 914 | _kernel_primitive:NN | \pdfextension | \luatex_pdfextension:D |
| 915 | _kernel_primitive:NN | \pdffeedback | \luatex_pdffeedback:D |
| 916 | _kernel_primitive:NN | \pdfvariable | \luatex_pdfvariable:D |
| 917 | _kernel_primitive:NN | \postexhyphenchar | \luatex_postexhyphenchar:D |
| 918 | _kernel_primitive:NN | \posthyphenchar | \luatex_posthyphenchar:D |
| 919 | _kernel_primitive:NN | \predisplaygapfactor | \luatex_predisplaygapfactor:D |
| 920 | _kernel_primitive:NN | \preexhyphenchar | \luatex_preexhyphenchar:D |

| | | |
|-----|--|--|
| 921 | <code>__kernel_primitive:NN \prehyphenchar</code> | <code>\luatex_prehyphenchar:D</code> |
| 922 | <code>__kernel_primitive:NN \savecatcodetable</code> | <code>\luatex_savecatcodetable:D</code> |
| 923 | <code>__kernel_primitive:NN \scantextokens</code> | <code>\luatex_scantextokens:D</code> |
| 924 | <code>__kernel_primitive:NN \setfontid</code> | <code>\luatex_setfontid:D</code> |
| 925 | <code>__kernel_primitive:NN \shapemode</code> | <code>\luatex_shapemode:D</code> |
| 926 | <code>__kernel_primitive:NN \suppressifcsnameerror</code> | <code>\luatex_suppressifcsnameerror:D</code> |
| 927 | <code>__kernel_primitive:NN \suppresslongerror</code> | <code>\luatex_suppresslongerror:D</code> |
| 928 | <code>__kernel_primitive:NN \suppressmathparerror</code> | <code>\luatex_suppressmathparerror:D</code> |
| 929 | <code>__kernel_primitive:NN \suppressoutererror</code> | <code>\luatex_suppressoutererror:D</code> |
| 930 | <code>__kernel_primitive:NN \toksapp</code> | <code>\luatex_toksapp:D</code> |
| 931 | <code>__kernel_primitive:NN \tokspre</code> | <code>\luatex_tokspre:D</code> |
| 932 | <code>__kernel_primitive:NN \tpack</code> | <code>\luatex_tpack:D</code> |
| 933 | <code>__kernel_primitive:NN \vpack</code> | <code>\luatex_vpack:D</code> |

Slightly more awkward are the directional primitives in LuaTeX. These come from Omega/Aleph, but we do not support those engines and so it seems most sensible to treat them as LuaTeX primitives for prefix purposes. One here is “new” but fits into the general set.

| | | |
|-----|--|--|
| 934 | <code>__kernel_primitive:NN \bodydir</code> | <code>\luatex_bodydir:D</code> |
| 935 | <code>__kernel_primitive:NN \boxdir</code> | <code>\luatex_boxdir:D</code> |
| 936 | <code>__kernel_primitive:NN \leftghost</code> | <code>\luatex_leftghost:D</code> |
| 937 | <code>__kernel_primitive:NN \linedir</code> | <code>\luatex_linedir:D</code> |
| 938 | <code>__kernel_primitive:NN \localbrokenpenalty</code> | <code>\luatex_localbrokenpenalty:D</code> |
| 939 | <code>__kernel_primitive:NN \localinterlinepenalty</code> | <code>\luatex_localinterlinepenalty:D</code> |
| 940 | <code>__kernel_primitive:NN \localleftbox</code> | <code>\luatex_localleftbox:D</code> |
| 941 | <code>__kernel_primitive:NN \localrightbox</code> | <code>\luatex_localrightbox:D</code> |
| 942 | <code>__kernel_primitive:NN \mathdir</code> | <code>\luatex_mathdir:D</code> |
| 943 | <code>__kernel_primitive:NN \pagedir</code> | <code>\luatex_pagedir:D</code> |
| 944 | <code>__kernel_primitive:NN \pardir</code> | <code>\luatex_pardir:D</code> |
| 945 | <code>__kernel_primitive:NN \rightghost</code> | <code>\luatex_rightghost:D</code> |
| 946 | <code>__kernel_primitive:NN \textdir</code> | <code>\luatex_textdir:D</code> |

Primitives from pdfTeX that LuaTeX renames.

| | | |
|-----|--|--|
| 947 | <code>__kernel_primitive:NN \adjustspacing</code> | <code>\pdfTeX_adjustspacing:D</code> |
| 948 | <code>__kernel_primitive:NN \copyfont</code> | <code>\pdfTeX_copyfont:D</code> |
| 949 | <code>__kernel_primitive:NN \draftmode</code> | <code>\pdfTeX_draftmode:D</code> |
| 950 | <code>__kernel_primitive:NN \expandglyphsinfont</code> | <code>\pdfTeX_fontexpand:D</code> |
| 951 | <code>__kernel_primitive:NN \ifabsdim</code> | <code>\pdfTeX_ifabsdim:D</code> |
| 952 | <code>__kernel_primitive:NN \ifabsnum</code> | <code>\pdfTeX_ifabsnum:D</code> |
| 953 | <code>__kernel_primitive:NN \ignoreligaturesinfont</code> | <code>\pdfTeX_ignoreligaturesinfont:D</code> |
| 954 | <code>__kernel_primitive:NN \insertht</code> | <code>\pdfTeX_insertht:D</code> |
| 955 | <code>__kernel_primitive:NN \lastsavedboxresourceindex</code> | <code>\pdfTeX_pdflastxform:D</code> |
| 956 | <code>__kernel_primitive:NN \lastsavedimageresourceindex</code> | <code>\pdfTeX_pdflastximage:D</code> |
| 957 | <code>__kernel_primitive:NN \lastsavedimageresourcepages</code> | <code>\pdfTeX_pdflastximagepages:D</code> |
| 958 | <code>__kernel_primitive:NN \lastxpos</code> | <code>\pdfTeX_lastxpos:D</code> |
| 959 | <code>__kernel_primitive:NN \lastypos</code> | <code>\pdfTeX_lastypos:D</code> |
| 960 | <code>__kernel_primitive:NN \normaldeviate</code> | <code>\pdfTeX_normaldeviate:D</code> |
| 961 | <code>__kernel_primitive:NN \outputmode</code> | <code>\pdfTeX_pdfoutput:D</code> |
| 962 | <code>__kernel_primitive:NN \pageheight</code> | <code>\pdfTeX_pageheight:D</code> |
| 963 | <code>__kernel_primitive:NN \pagewidth</code> | <code>\pdfTeX_pagewidth:D</code> |
| 964 | <code>__kernel_primitive:NN \protrudechars</code> | <code>\pdfTeX_protrudechars:D</code> |
| 965 | <code>__kernel_primitive:NN \pxdimen</code> | <code>\pdfTeX_pxdimen:D</code> |
| 966 | <code>__kernel_primitive:NN \randomseed</code> | <code>\pdfTeX_randomseed:D</code> |
| 967 | <code>__kernel_primitive:NN \useboxresource</code> | <code>\pdfTeX_pdfrefxform:D</code> |
| 968 | <code>__kernel_primitive:NN \useimageresource</code> | <code>\pdfTeX_pdfrefximage:D</code> |

| | | |
|-----|--|--|
| 969 | <code>__kernel_primitive:NN \savepos</code> | <code>\pdfutex_savepos:D</code> |
| 970 | <code>__kernel_primitive:NN \saveboxresource</code> | <code>\pdfutex_pdfxform:D</code> |
| 971 | <code>__kernel_primitive:NN \saveimageresource</code> | <code>\pdfutex_pdfximage:D</code> |
| 972 | <code>__kernel_primitive:NN \setrandomseed</code> | <code>\pdfutex_setrandomseed:D</code> |
| 973 | <code>__kernel_primitive:NN \tracingfonts</code> | <code>\pdfutex_tracingfonts:D</code> |
| 974 | <code>__kernel_primitive:NN \uniformdeviate</code> | <code>\pdfutex_uniformdeviate:D</code> |

The set of Unicode math primitives were introduced by \XeTeX and \LuaTeX in a somewhat complex fashion: a few first as $\text{\XeTeX}...$ which were then renamed with \LuaTeX having a lot more. These names now all start $\text{\U}...$ and mainly $\text{\Umath}...$. To keep things somewhat clear we therefore prefix all of these as $\text{\utex}...$ (introduced by a Unicode \TeX engine) and drop $\text{\U}(\text{math})$ from the names. Where there is a related \TeX90 primitive or where it really seems required we keep the math part of the name.

| | | |
|------|---|--|
| 975 | <code>__kernel_primitive:NN \Uchar</code> | <code>\utex_char:D</code> |
| 976 | <code>__kernel_primitive:NN \Ucharcat</code> | <code>\utex_charcat:D</code> |
| 977 | <code>__kernel_primitive:NN \Udelcode</code> | <code>\utex_delcode:D</code> |
| 978 | <code>__kernel_primitive:NN \Udelcodenum</code> | <code>\utex_delcodenum:D</code> |
| 979 | <code>__kernel_primitive:NN \Udelimiter</code> | <code>\utex_delimiter:D</code> |
| 980 | <code>__kernel_primitive:NN \Udelimiterover</code> | <code>\utex_delimiterover:D</code> |
| 981 | <code>__kernel_primitive:NN \Udelimiterunder</code> | <code>\utex_delimiterunder:D</code> |
| 982 | <code>__kernel_primitive:NN \Uhexensible</code> | <code>\utex_hextensible:D</code> |
| 983 | <code>__kernel_primitive:NN \Umathaccent</code> | <code>\utex_mathaccent:D</code> |
| 984 | <code>__kernel_primitive:NN \Umathaxis</code> | <code>\utex_mathaxis:D</code> |
| 985 | <code>__kernel_primitive:NN \Umathbinbinspacing</code> | <code>\utex_binbinspacing:D</code> |
| 986 | <code>__kernel_primitive:NN \Umathbinclosespacing</code> | <code>\utex_binclosespacing:D</code> |
| 987 | <code>__kernel_primitive:NN \Umathbininnerspacing</code> | <code>\utex_bininnerspacing:D</code> |
| 988 | <code>__kernel_primitive:NN \Umathbinopenspacing</code> | <code>\utex_binopenspacing:D</code> |
| 989 | <code>__kernel_primitive:NN \Umathbinopspacing</code> | <code>\utex_binopspacing:D</code> |
| 990 | <code>__kernel_primitive:NN \Umathbinordspacing</code> | <code>\utex_binordspacing:D</code> |
| 991 | <code>__kernel_primitive:NN \Umathbinpunctspacing</code> | <code>\utex_binpunctspacing:D</code> |
| 992 | <code>__kernel_primitive:NN \Umathbinrelspacing</code> | <code>\utex_binrelspacing:D</code> |
| 993 | <code>__kernel_primitive:NN \Umathchar</code> | <code>\utex_mathchar:D</code> |
| 994 | <code>__kernel_primitive:NN \Umathcharclass</code> | <code>\utex_mathcharclass:D</code> |
| 995 | <code>__kernel_primitive:NN \Umathchardef</code> | <code>\utex_mathchardef:D</code> |
| 996 | <code>__kernel_primitive:NN \Umathcharfam</code> | <code>\utex_mathcharfam:D</code> |
| 997 | <code>__kernel_primitive:NN \Umathcharnum</code> | <code>\utex_mathcharnum:D</code> |
| 998 | <code>__kernel_primitive:NN \Umathcharnumdef</code> | <code>\utex_mathcharnumdef:D</code> |
| 999 | <code>__kernel_primitive:NN \Umathcharslot</code> | <code>\utex_mathcharslot:D</code> |
| 1000 | <code>__kernel_primitive:NN \Umathclosebinspacing</code> | <code>\utex_closebinspacing:D</code> |
| 1001 | <code>__kernel_primitive:NN \Umathcloseclosespacing</code> | <code>\utex_closeclosespacing:D</code> |
| 1002 | <code>__kernel_primitive:NN \Umathcloseinnerspacing</code> | <code>\utex_closeinnerspacing:D</code> |
| 1003 | <code>__kernel_primitive:NN \Umathcloseopenspacing</code> | <code>\utex_closeopenspacing:D</code> |
| 1004 | <code>__kernel_primitive:NN \Umathcloseopspacing</code> | <code>\utex_closeopspacing:D</code> |
| 1005 | <code>__kernel_primitive:NN \Umathcloseordspacing</code> | <code>\utex_closeordspacing:D</code> |
| 1006 | <code>__kernel_primitive:NN \Umathclosepunctspacing</code> | <code>\utex_closepunctspacing:D</code> |
| 1007 | <code>__kernel_primitive:NN \Umathcloserelspacing</code> | <code>\utex_closerelspacing:D</code> |
| 1008 | <code>__kernel_primitive:NN \Umathcode</code> | <code>\utex_mathcode:D</code> |
| 1009 | <code>__kernel_primitive:NN \Umathcodenum</code> | <code>\utex_mathcodenum:D</code> |
| 1010 | <code>__kernel_primitive:NN \Umathconnectoroverlapmin</code> | <code>\utex_connectoroverlapmin:D</code> |
| 1011 | <code>__kernel_primitive:NN \Umathfractiondelsize</code> | <code>\utex_fractiondelsize:D</code> |
| 1012 | <code>__kernel_primitive:NN \Umathfractiondenomdown</code> | <code>\utex_fractiondenomdown:D</code> |
| 1013 | <code>__kernel_primitive:NN \Umathfractiondenomvgap</code> | <code>\utex_fractiondenomvgap:D</code> |
| 1014 | <code>__kernel_primitive:NN \Umathfractionnumup</code> | <code>\utex_fractionnumup:D</code> |
| 1015 | <code>__kernel_primitive:NN \Umathfractionnumvgap</code> | <code>\utex_fractionnumvgap:D</code> |

| | | | |
|------|------------------------|-------------------------|----------------------------|
| 1016 | _kernel_primitive:NN | \Umathfractionrule | \utex_fractionrule:D |
| 1017 | _kernel_primitive:NN | \Umathinnerbinspacing | \utex_innerbinspacing:D |
| 1018 | _kernel_primitive:NN | \Umathinnerclosespacing | \utex_innerclosespacing:D |
| 1019 | _kernel_primitive:NN | \Umathinnerinnerspacing | \utex_innerinnerspacing:D |
| 1020 | _kernel_primitive:NN | \Umathinneropenspacing | \utex_inneropenspacing:D |
| 1021 | _kernel_primitive:NN | \Umathinneropspacing | \utex_inneropspacing:D |
| 1022 | _kernel_primitive:NN | \Umathinnerordspacing | \utex_innerordspacing:D |
| 1023 | _kernel_primitive:NN | \Umathinnerpunctspacing | \utex_innerpunctspacing:D |
| 1024 | _kernel_primitive:NN | \Umathinnerrelspacing | \utex_innerrelspacing:D |
| 1025 | _kernel_primitive:NN | \Umathlimitabovebgap | \utex_limitabovebgap:D |
| 1026 | _kernel_primitive:NN | \Umathlimitabovekern | \utex_limitabovekern:D |
| 1027 | _kernel_primitive:NN | \Umathlimitabovevgap | \utex_limitabovevgap:D |
| 1028 | _kernel_primitive:NN | \Umathlimitbelowbgap | \utex_limitbelowbgap:D |
| 1029 | _kernel_primitive:NN | \Umathlimitbelowkern | \utex_limitbelowkern:D |
| 1030 | _kernel_primitive:NN | \Umathlimitbelowvgap | \utex_limitbelowvgap:D |
| 1031 | _kernel_primitive:NN | \Umathnolimitsubfactor | \utex_nolimitsubfactor:D |
| 1032 | _kernel_primitive:NN | \Umathnolimitsupfactor | \utex_nolimitsupfactor:D |
| 1033 | _kernel_primitive:NN | \Umathopbinspacing | \utex_opbinspacing:D |
| 1034 | _kernel_primitive:NN | \Umathopclosespacing | \utex_opclosespacing:D |
| 1035 | _kernel_primitive:NN | \Umathopenbinspacing | \utex_openbinspacing:D |
| 1036 | _kernel_primitive:NN | \Umathopenclosespacing | \utex_openclosespacing:D |
| 1037 | _kernel_primitive:NN | \Umathopeninnerspacing | \utex_openinnerspacing:D |
| 1038 | _kernel_primitive:NN | \Umathopenopenspacing | \utex_openopenspacing:D |
| 1039 | _kernel_primitive:NN | \Umathopenopspacing | \utex_openopspacing:D |
| 1040 | _kernel_primitive:NN | \Umathopenordspacing | \utex_openordspacing:D |
| 1041 | _kernel_primitive:NN | \Umathopenpunctspacing | \utex_openpunctspacing:D |
| 1042 | _kernel_primitive:NN | \Umathopenrelspacing | \utex_openrelspacing:D |
| 1043 | _kernel_primitive:NN | \Umathoperatorsize | \utex_operatorsize:D |
| 1044 | _kernel_primitive:NN | \Umathopinnerspacing | \utex_opinnerspacing:D |
| 1045 | _kernel_primitive:NN | \Umathopopenspacing | \utex_opopenspacing:D |
| 1046 | _kernel_primitive:NN | \Umathopopspacing | \utex_opopspacing:D |
| 1047 | _kernel_primitive:NN | \Umathopordspacing | \utex_opordspacing:D |
| 1048 | _kernel_primitive:NN | \Umathoppunctspacing | \utex_oppunctspacing:D |
| 1049 | _kernel_primitive:NN | \Umathoprelspacing | \utex_oprelspacing:D |
| 1050 | _kernel_primitive:NN | \Umathordbinspacing | \utex_ordbinspacing:D |
| 1051 | _kernel_primitive:NN | \Umathordclosespacing | \utex_ordclosespacing:D |
| 1052 | _kernel_primitive:NN | \Umathordinnerspacing | \utex_ordinnerspacing:D |
| 1053 | _kernel_primitive:NN | \Umathordopenspacing | \utex_ordopenspacing:D |
| 1054 | _kernel_primitive:NN | \Umathordopspacing | \utex_ordopspacing:D |
| 1055 | _kernel_primitive:NN | \Umathordordspacing | \utex_ordordspacing:D |
| 1056 | _kernel_primitive:NN | \Umathordpunctspacing | \utex_ordpunctspacing:D |
| 1057 | _kernel_primitive:NN | \Umathordrelspacing | \utex_ordrelspacing:D |
| 1058 | _kernel_primitive:NN | \Umathoverbarkern | \utex_overbarkern:D |
| 1059 | _kernel_primitive:NN | \Umathoverbarrule | \utex_overbarrule:D |
| 1060 | _kernel_primitive:NN | \Umathoverbarvgap | \utex_overbarvgap:D |
| 1061 | _kernel_primitive:NN | \Umathoverdelimiterbgap | \utex_overdelimiterbgap:D |
| 1062 | _kernel_primitive:NN | \Umathoverdelimitervgap | \utex_overdelimitervgap:D |
| 1063 | _kernel_primitive:NN | \Umathpunctbinspacing | \utex_punctbinspacing:D |
| 1064 | _kernel_primitive:NN | \Umathpunctclosespacing | \utex_punctclosespacing:D |
| 1065 | _kernel_primitive:NN | \Umathpunctinnerspacing | \utex_punctinnerspacing:D |
| 1066 | _kernel_primitive:NN | \Umathpunctopenspacing | \utex_punctopenspacing:D |
| 1067 | _kernel_primitive:NN | \Umathpunctopspacing | \utex_punctopspacing:D |
| 1068 | _kernel_primitive:NN | \Umathpunctordspacing | \utex_punctordspacing:D |
| 1069 | _kernel_primitive:NN | \Umathpunctpunctspacing | \utex_punctpunctspacing:D |

| | | | |
|-----------------------|------------------------|---------------------------|------------------------------|
| 1070 | _kernel_primitive:NN | \Umathpunctrelspacing | \utex_punctrelspacing:D |
| 1071 | _kernel_primitive:NN | \Umathquad | \utex_quad:D |
| 1072 | _kernel_primitive:NN | \Umathradicaldegreeafter | \utex_radicaldegreeafter:D |
| 1073 | _kernel_primitive:NN | \Umathradicaldegreebefore | \utex_radicaldegreebefore:D |
| 1074 | _kernel_primitive:NN | \Umathradicaldegreeraise | \utex_radicaldegreeraise:D |
| 1075 | _kernel_primitive:NN | \Umathradicalkern | \utex_radicalkern:D |
| 1076 | _kernel_primitive:NN | \Umathradicalrule | \utex_radicalrule:D |
| 1077 | _kernel_primitive:NN | \Umathradicalvgap | \utex_radicalvgap:D |
| 1078 | _kernel_primitive:NN | \Umathrelbinspacing | \utex_relbinspacing:D |
| 1079 | _kernel_primitive:NN | \Umathrelclosespacing | \utex_relclosespacing:D |
| 1080 | _kernel_primitive:NN | \Umathrelinnerspacing | \utex_relinnerspacing:D |
| 1081 | _kernel_primitive:NN | \Umathrelopenspacing | \utex_relopenspacing:D |
| 1082 | _kernel_primitive:NN | \Umathreltopspacing | \utex_reltopspacing:D |
| 1083 | _kernel_primitive:NN | \Umathrelordspacing | \utex_relordspacing:D |
| 1084 | _kernel_primitive:NN | \Umathrelpunctspacing | \utex_relpunctspacing:D |
| 1085 | _kernel_primitive:NN | \Umathrelrelspacing | \utex_relrelspacing:D |
| 1086 | _kernel_primitive:NN | \Umathskewedfractionhgap | \utex_skewedfractionhgap:D |
| 1087 | _kernel_primitive:NN | \Umathskewedfractionvgap | \utex_skewedfractionvgap:D |
| 1088 | _kernel_primitive:NN | \Umathspaceafterscript | \utex_spaceafterscript:D |
| 1089 | _kernel_primitive:NN | \Umathstackdenomdown | \utex_stackdenomdown:D |
| 1090 | _kernel_primitive:NN | \Umathstacknumup | \utex_stacknumup:D |
| 1091 | _kernel_primitive:NN | \Umathstackvgap | \utex_stackvgap:D |
| 1092 | _kernel_primitive:NN | \Umathsubshiftdown | \utex_subshiftdown:D |
| 1093 | _kernel_primitive:NN | \Umathsubshiftdrop | \utex_subshiftdrop:D |
| 1094 | _kernel_primitive:NN | \Umathsubsupshiftdown | \utex_subsupshiftdown:D |
| 1095 | _kernel_primitive:NN | \Umathsubsupvgap | \utex_subsupvgap:D |
| 1096 | _kernel_primitive:NN | \Umathsubtopmax | \utex_subtopmax:D |
| 1097 | _kernel_primitive:NN | \Umathsupbottommin | \utex_supbottommin:D |
| 1098 | _kernel_primitive:NN | \Umathsupshiftdrop | \utex_supshiftdrop:D |
| 1099 | _kernel_primitive:NN | \Umathsupshiftup | \utex_supshiftup:D |
| 1100 | _kernel_primitive:NN | \Umathsupsubbottommax | \utex_supsubbottommax:D |
| 1101 | _kernel_primitive:NN | \Umathunderbarkern | \utex_underbarkern:D |
| 1102 | _kernel_primitive:NN | \Umathunderbarrule | \utex_underbarrule:D |
| 1103 | _kernel_primitive:NN | \Umathunderbarvgap | \utex_underbarvgap:D |
| 1104 | _kernel_primitive:NN | \Umathunderdelimiterbgap | \utex_underdelimiterbgap:D |
| 1105 | _kernel_primitive:NN | \Umathunderdelimitervgap | \utex_underdelimitervgap:D |
| 1106 | _kernel_primitive:NN | \Uoverdelimiter | \utex_overdelimiter:D |
| 1107 | _kernel_primitive:NN | \Uradical | \utex_radical:D |
| 1108 | _kernel_primitive:NN | \Uroot | \utex_root:D |
| 1109 | _kernel_primitive:NN | \Uskewed | \utex_skewed:D |
| 1110 | _kernel_primitive:NN | \Uskewedwithdelims | \utex_skewedwithdelims:D |
| 1111 | _kernel_primitive:NN | \Ustack | \utex_stack:D |
| 1112 | _kernel_primitive:NN | \Ustartdisplaymath | \utex_startdisplaymath:D |
| 1113 | _kernel_primitive:NN | \Ustartmath | \utex_startmath:D |
| 1114 | _kernel_primitive:NN | \Ustopdisplaymath | \utex_stopdisplaymath:D |
| 1115 | _kernel_primitive:NN | \Ustopmath | \utex_stopmath:D |
| 1116 | _kernel_primitive:NN | \Usubscript | \utex_subscript:D |
| 1117 | _kernel_primitive:NN | \Usuperscript | \utex_superscript:D |
| 1118 | _kernel_primitive:NN | \Uunderdelimiter | \utex_underdelimiter:D |
| 1119 | _kernel_primitive:NN | \Uvextensible | \utex_vextensible:D |
| Primitives from pTeX. | | | |
| 1120 | _kernel_primitive:NN | \autospaceing | \ptex_autospaceing:D |
| 1121 | _kernel_primitive:NN | \autoxspaceing | \ptex_autoxspaceing:D |
| 1122 | _kernel_primitive:NN | \dtou | \ptex_dtou:D |

| | | |
|------|--|--|
| 1123 | <code>__kernel_primitive:NN \euc</code> | <code>\ptex_euc:D</code> |
| 1124 | <code>__kernel_primitive:NN \ifdbbox</code> | <code>\ptex_ifdbbox:D</code> |
| 1125 | <code>__kernel_primitive:NN \ifddir</code> | <code>\ptex_ifddir:D</code> |
| 1126 | <code>__kernel_primitive:NN \ifmdir</code> | <code>\ptex_ifmdir:D</code> |
| 1127 | <code>__kernel_primitive:NN \iftbox</code> | <code>\ptex_iftbox:D</code> |
| 1128 | <code>__kernel_primitive:NN \iftdir</code> | <code>\ptex_iftdir:D</code> |
| 1129 | <code>__kernel_primitive:NN \ifybox</code> | <code>\ptex_ifybox:D</code> |
| 1130 | <code>__kernel_primitive:NN \ifydir</code> | <code>\ptex_ifydir:D</code> |
| 1131 | <code>__kernel_primitive:NN \inhibitglue</code> | <code>\ptex_inhibitglue:D</code> |
| 1132 | <code>__kernel_primitive:NN \inhibitxspcode</code> | <code>\ptex_inhibitxspcode:D</code> |
| 1133 | <code>__kernel_primitive:NN \jcharwidowpenalty</code> | <code>\ptex_jcharwidowpenalty:D</code> |
| 1134 | <code>__kernel_primitive:NN \jfam</code> | <code>\ptex_jfam:D</code> |
| 1135 | <code>__kernel_primitive:NN \jfont</code> | <code>\ptex_jfont:D</code> |
| 1136 | <code>__kernel_primitive:NN \jis</code> | <code>\ptex_jis:D</code> |
| 1137 | <code>__kernel_primitive:NN \kanjiskip</code> | <code>\ptex_kanjiskip:D</code> |
| 1138 | <code>__kernel_primitive:NN \kansuji</code> | <code>\ptex_kansuji:D</code> |
| 1139 | <code>__kernel_primitive:NN \kansujichar</code> | <code>\ptex_kansujichar:D</code> |
| 1140 | <code>__kernel_primitive:NN \kcatcode</code> | <code>\ptex_kcatcode:D</code> |
| 1141 | <code>__kernel_primitive:NN \kuten</code> | <code>\ptex_kuten:D</code> |
| 1142 | <code>__kernel_primitive:NN \noautospace</code> | <code>\ptex_noautospace:D</code> |
| 1143 | <code>__kernel_primitive:NN \noautoxspace</code> | <code>\ptex_noautoxspace:D</code> |
| 1144 | <code>__kernel_primitive:NN \postbreakpenalty</code> | <code>\ptex_postbreakpenalty:D</code> |
| 1145 | <code>__kernel_primitive:NN \prebreakpenalty</code> | <code>\ptex_prebreakpenalty:D</code> |
| 1146 | <code>__kernel_primitive:NN \showmode</code> | <code>\ptex_showmode:D</code> |
| 1147 | <code>__kernel_primitive:NN \sjis</code> | <code>\ptex_sjis:D</code> |
| 1148 | <code>__kernel_primitive:NN \tate</code> | <code>\ptex_tate:D</code> |
| 1149 | <code>__kernel_primitive:NN \tbaselineshift</code> | <code>\ptex_tbaselineshift:D</code> |
| 1150 | <code>__kernel_primitive:NN \tfont</code> | <code>\ptex_tfont:D</code> |
| 1151 | <code>__kernel_primitive:NN \xkanjiskip</code> | <code>\ptex_xkanjiskip:D</code> |
| 1152 | <code>__kernel_primitive:NN \xspcode</code> | <code>\ptex_xspcode:D</code> |
| 1153 | <code>__kernel_primitive:NN \ybaselineshift</code> | <code>\ptex_ybaselineshift:D</code> |
| 1154 | <code>__kernel_primitive:NN \yoko</code> | <code>\ptex_yoko:D</code> |

Primitives from upTeX.

| | | |
|------|--|---------------------------------------|
| 1155 | <code>__kernel_primitive:NN \disablecjktoken</code> | <code>\uptex_disablecjktoken:D</code> |
| 1156 | <code>__kernel_primitive:NN \enablecjktoken</code> | <code>\uptex_enablecjktoken:D</code> |
| 1157 | <code>__kernel_primitive:NN \forcecjktoken</code> | <code>\uptex_forcecjktoken:D</code> |
| 1158 | <code>__kernel_primitive:NN \kchar</code> | <code>\uptex_kchar:D</code> |
| 1159 | <code>__kernel_primitive:NN \kchardef</code> | <code>\uptex_kchardef:D</code> |
| 1160 | <code>__kernel_primitive:NN \kuten</code> | <code>\uptex_kuten:D</code> |
| 1161 | <code>__kernel_primitive:NN \ucs</code> | <code>\uptex_ucs:D</code> |

End of the “just the names” part of the source.

```
1162 </initex | names | package>
1163 <*:initex | package>
```

The job is done: close the group (using the primitive renamed!).

```
1164 \tex_endgroup:D
```

L^AT_EX 2_ε will have moved a few primitives, so these are sorted out. A convenient test for L^AT_EX 2_ε is the \@@end saved primitive.

| | | |
|------|---|-----------------------------------|
| 1165 | <code><*package></code> | |
| 1166 | <code>\etex_ifdefined:D \@@end</code> | |
| 1167 | <code>\tex_let:D \tex_end:D</code> | <code>\@@end</code> |
| 1168 | <code>\tex_let:D \tex_everydisplay:D</code> | <code>\frozen@everydisplay</code> |
| 1169 | <code>\tex_let:D \tex_everymath:D</code> | <code>\frozen@everymath</code> |

```

1170 \tex_let:D \tex_hyphen:D \@@hyph
1171 \tex_let:D \tex_input:D \@@input
1172 \tex_let:D \tex_italiccorrection:D \@@italiccorr
1173 \tex_let:D \tex_underline:D \@@underline

```

Some tidying up is needed for `\(pdf)tracingfonts`. Newer LuaTeX has this simply as `\tracingfonts`, but that will have been overwritten by the L^AT_EX 2_ε kernel. So any spurious definition has to be removed, then the real version saved either from the pdfTeX name or from LuaTeX. In the latter case, we leave `\@@tracingfonts` available: this might be useful and almost all L^AT_EX 2_ε users will have expl3 loaded by fontspec. (We follow the usual kernel convention that @@ is used for saved primitives.)

```

1174 \tex_let:D \pdfTeX_tracingfonts:D \tex_undefined:D
1175 \etex_ifdefined:D \pdftracingfonts
1176 \tex_let:D \pdfTeX_tracingfonts:D \pdftracingfonts
1177 \tex_else:D
1178 \etex_ifdefined:D \luatex_directlua:D
1179 \luatex_directlua:D { tex.enableprimitives("@@", {"tracingfonts"}) }
1180 \tex_let:D \pdfTeX_tracingfonts:D \luatextracingfonts
1181 \tex_fi:D
1182 \tex_fi:D
1183 \tex_fi:D

```

That is also true for the LuaTeX primitives under L^AT_EX 2_ε (depending on the format-building date). There are a few primitives that get the right names anyway so are missing here!

```

1184 \etex_ifdefined:D \luatexsuppressfontnotfounderror
1185 \tex_let:D \luatex_alignmark:D \luatexalignmark
1186 \tex_let:D \luatex_aligntab:D \luatexaligntab
1187 \tex_let:D \luatex_attribute:D \luatexattribute
1188 \tex_let:D \luatex_attributedef:D \luatexattributedef
1189 \tex_let:D \luatex_catcodetable:D \luatexcatcodetable
1190 \tex_let:D \luatex_clearmarks:D \luatexclearmarks
1191 \tex_let:D \luatex_crampeddisplaystyle:D \luatexcrampeddisplaystyle
1192 \tex_let:D \luatex_crampedscriptscriptstyle:D \luatexcrampedscriptscriptstyle
1193 \tex_let:D \luatex_crampedscriptstyle:D \luatexcrampedscriptstyle
1194 \tex_let:D \luatex_crampedtextstyle:D \luatexcrampedtextstyle
1195 \tex_let:D \luatex_fontid:D \luatexfontid
1196 \tex_let:D \luatex_formatname:D \luatexformatname
1197 \tex_let:D \luatex_gleaders:D \luatexgleaders
1198 \tex_let:D \luatex_initcatcodetable:D \luatexinitcatcodetable
1199 \tex_let:D \luatex_latelua:D \luatexlatelua
1200 \tex_let:D \luatex_luaescapestring:D \luatexluaescapestring
1201 \tex_let:D \luatex_luafunction:D \luatexluafunction
1202 \tex_let:D \luatex_mathstyle:D \luatexmathstyle
1203 \tex_let:D \luatex_nokerns:D \luatexnokerns
1204 \tex_let:D \luatex_noligs:D \luatexnoligs
1205 \tex_let:D \luatex_outputbox:D \luatexoutputbox
1206 \tex_let:D \luatex_pageleftoffset:D \luatexpageleftoffset
1207 \tex_let:D \luatex_pagetopoffset:D \luatexpagetopoffset
1208 \tex_let:D \luatex_postexhyphenchar:D \luatexpostexhyphenchar
1209 \tex_let:D \luatex_posthyphenchar:D \luatexposthyphenchar
1210 \tex_let:D \luatex_preexhyphenchar:D \luatexpreexhyphenchar
1211 \tex_let:D \luatex_prehyphenchar:D \luatexprehyphenchar
1212 \tex_let:D \luatex_savecatcodetable:D \luatexsavecatcodetable

```

```

1213 \tex_let:D \luatex_scantextokens:D \luatexscantextokens
1214 \tex_let:D \luatex_suppressifcsnameerror:D \luatexsuppressifcsnameerror
1215 \tex_let:D \luatex_suppresslongerror:D \luatexsuppresslongerror
1216 \tex_let:D \luatex_suppressmathparerror:D \luatexsuppressmathparerror
1217 \tex_let:D \luatex_suppressoutererror:D \luatexsuppressoutererror
1218 \tex_let:D \utex_char:D \luatexUchar
1219 \tex_let:D \xetex_suppressfontnotfounderror:D \luatexsuppressfontnotfounderror

```

Which also covers those slightly odd ones.

```

1220 \tex_let:D \luatex_bodydir:D \luatexbodydir
1221 \tex_let:D \luatex_boxdir:D \luatexboxdir
1222 \tex_let:D \luatex_leftghost:D \luatexleftghost
1223 \tex_let:D \luatex_localbrokenpenalty:D \luatexlocalbrokenpenalty
1224 \tex_let:D \luatex_localinterlinepenalty:D \luatexlocalinterlinepenalty
1225 \tex_let:D \luatex_localleftbox:D \luatexlocalleftbox
1226 \tex_let:D \luatex_localrightbox:D \luatexlocalrightbox
1227 \tex_let:D \luatex_mathdir:D \luatexmathdir
1228 \tex_let:D \luatex_pagebottomoffset:D \luatexpagebottomoffset
1229 \tex_let:D \luatex_pagedir:D \luatexpagedir
1230 \tex_let:D \pdfTeX_pageheight:D \luatexpageheight
1231 \tex_let:D \luatex_pagerightoffset:D \luatexpagerightoffset
1232 \tex_let:D \pdfTeX_pagewidth:D \luatexpagewidth
1233 \tex_let:D \luatex_pardir:D \luatexpardir
1234 \tex_let:D \luatex_rightghost:D \luatexrightghost
1235 \tex_let:D \luatex_textdir:D \luatextextdir
1236 \tex_fi:D

```

Only pdfTeX and LuaTeX define \pdfmapfile and \pdfmapline: Tidy up the fact that some format-building processes leave a couple of questionable decisions about that!

```

1237 \tex_ifnum:D 0
1238 \etex_ifdefined:D \pdfTeX_pdfTeXversion:D 1 \tex_fi:D
1239 \etex_ifdefined:D \luatex luatexversion:D 1 \tex_fi:D
1240 = 0 %
1241 \tex_let:D \pdfTeX_mapfile:D \tex_undefined:D
1242 \tex_let:D \pdfTeX_mapline:D \tex_undefined:D
1243 \tex_fi:D
1244 </package>

```

Older XeTeX versions use \XeTeX as the prefix for the Unicode math primitives it knows. That is tidied up here (we support XeTeX versions from 0.9994 but this change was in 0.9999).

```

1245 (*initex | package)
1246 \etex_ifdefined:D \XeTeXdelcode
1247 \tex_let:D \utex_delcode:D \XeTeXdelcode
1248 \tex_let:D \utex_delcodenum:D \XeTeXdelcodenum
1249 \tex_let:D \utex_delimiter:D \XeTeXdelimiter
1250 \tex_let:D \utex_mathaccent:D \XeTeXmathaccent
1251 \tex_let:D \utex_mathchar:D \XeTeXmathchar
1252 \tex_let:D \utex_mathchardef:D \XeTeXmathchardef
1253 \tex_let:D \utex_mathcharnum:D \XeTeXmathcharnum
1254 \tex_let:D \utex_mathcharnumdef:D \XeTeXmathcharnumdef
1255 \tex_let:D \utex_mathcode:D \XeTeXmathcode
1256 \tex_let:D \utex_mathcodenum:D \XeTeXmathcodenum
1257 \tex_fi:D

```

Up to v0.80, LuaT_EX defines the pdfT_EX version data: rather confusing. Removing them means that `\pdfTEXversion:D` is a marker for pdfT_EX alone: useful in engine-dependent code later.

```

1258 \etex_ifdefined:D \luatex luatexversion:D
1259 \tex_let:D \pdfTEXbanner:D \tex_undefined:D
1260 \tex_let:D \pdfTEXrevision:D \tex_undefined:D
1261 \tex_let:D \pdfTEXversion:D \tex_undefined:D
1262 \tex_fi:D
1263 </initex | package>

```

For ConT_EXt, two tests are needed. Both Mark II and Mark IV move several primitives: these are all covered by the first test, again using `\end` as a marker. For Mark IV, a few more primitives are moved: they are implemented using some Lua code in the current ConT_EXt.

```

1264 <*package>
1265 \etex_ifdefined:D \normalend
1266 \tex_let:D \tex_end:D \normalend
1267 \tex_let:D \tex_everyjob:D \normaleveryjob
1268 \tex_let:D \tex_input:D \normalinput
1269 \tex_let:D \tex_language:D \normallanguage
1270 \tex_let:D \tex_mathop:D \normalmathop
1271 \tex_let:D \tex_month:D \normalmonth
1272 \tex_let:D \tex_outer:D \normalouter
1273 \tex_let:D \tex_over:D \normalover
1274 \tex_let:D \tex_vcenter:D \normalvcenter
1275 \tex_let:D \etex_unexpanded:D \normalunexpanded
1276 \tex_let:D \luatex_expanded:D \normalexpanded
1277 \tex_fi:D
1278 \etex_ifdefined:D \normalitaliccorrection
1279 \tex_let:D \tex_hoffset:D \normalhoffset
1280 \tex_let:D \tex_italiccorrection:D \normalitaliccorrection
1281 \tex_let:D \tex_voffset:D \normalvoffset
1282 \tex_let:D \etex_showtokens:D \normalshowtokens
1283 \tex_let:D \luatex_bodydir:D \spac_directions_normal_body_dir
1284 \tex_let:D \luatex_pagedir:D \spac_directions_normal_page_dir
1285 \tex_fi:D
1286 \etex_ifdefined:D \normalleft
1287 \tex_let:D \tex_left:D \normalleft
1288 \tex_let:D \tex_middle:D \normalmiddle
1289 \tex_let:D \tex_right:D \normalright
1290 \tex_fi:D
1291 </package>
1292 </initex | package>

```

3 l3basics implementation

```

1293 <*initex | package>

```

3.1 Renaming some T_EX primitives (again)

Having given all the T_EX primitives a consistent name, we need to give sensible names to the ones we actually want to use. These will be defined as needed in the appropriate

modules, but do a few now, just to get started.⁵

```

\if_true: Then some conditionals.
\if_false: 1294 \tex_let:D \if_true: \tex_iftrue:D
\or: 1295 \tex_let:D \if_false: \tex_iffalse:D
\else: 1296 \tex_let:D \or: \tex_or:D
\fi: 1297 \tex_let:D \else: \tex_else:D
\reverse_if:N 1298 \tex_let:D \fi: \tex_fi:D
\if:w 1299 \tex_let:D \reverse_if:N \etex_unless:D
\if_charcode:w 1300 \tex_let:D \if:w \tex_if:D
\if_catcode:w 1301 \tex_let:D \if_charcode:w \tex_if:D
\if_meaning:w 1302 \tex_let:D \if_catcode:w \tex_ifcat:D
1303 \tex_let:D \if_meaning:w \tex_ifx:D

```

(End definition for \if_true: and others. These functions are documented on page 21.)

```

\if_mode_math: TEX lets us detect some if its modes.
\if_mode_horizontal: 1304 \tex_let:D \if_mode_math: \tex_ifmmode:D
\if_mode_vertical: 1305 \tex_let:D \if_mode_horizontal: \tex_ifhmode:D
\if_mode_inner: 1306 \tex_let:D \if_mode_vertical: \tex_ifvmode:D
1307 \tex_let:D \if_mode_inner: \tex_ifinner:D

```

(End definition for \if_mode_math: and others. These functions are documented on page 21.)

```

\if_cs_exist:N Building csnames and testing if control sequences exist.
\if_cs_exist:w 1308 \tex_let:D \if_cs_exist:N \etex_ifdefined:D
\cs:w 1309 \tex_let:D \if_cs_exist:w \etex_ifcsname:D
\cs_end: 1310 \tex_let:D \cs:w \tex_csname:D
1311 \tex_let:D \cs_end: \tex_endcsname:D

```

(End definition for \if_cs_exist:N and others. These functions are documented on page 21.)

```

\exp_after:wN The five \exp_ functions are used in the l3expan module where they are described.
\exp_not:N 1312 \tex_let:D \exp_after:wN \tex_expandafter:D
\exp_not:n 1313 \tex_let:D \exp_not:N \tex_noexpand:D
1314 \tex_let:D \exp_not:n \etex_unexpanded:D
1315 \tex_let:D \exp:w \tex_romannumeral:D
1316 \tex_chardef:D \exp_end: = 0 ~

```

(End definition for \exp_after:wN, \exp_not:N, and \exp_not:n. These functions are documented on page 30.)

```

\token_to_meaning:N Examining a control sequence or token.
\cs_meaning:N 1317 \tex_let:D \token_to_meaning:N \tex_meaning:D
1318 \tex_let:D \cs_meaning:N \tex_meaning:D

```

(End definition for \token_to_meaning:N and \cs_meaning:N. These functions are documented on page 110.)

```

\tl_to_str:n Making strings.
\token_to_str:N 1319 \tex_let:D \tl_to_str:n \etex_detokenize:D
1320 \tex_let:D \token_to_str:N \tex_string:D

```

⁵This renaming gets expensive in terms of csname usage, an alternative scheme would be to just use the `\tex_...:D` name in the cases where no good alternative exists.

(End definition for `\tl_to_str:n` and `\token_to_str:N`. These functions are documented on page 41.)

`\scan_stop:` The next three are basic functions for which there also exist versions that are safe inside alignments. These safe versions are defined in the `l3prg` module.

```
\group_begin: 1321 \tex_let:D \scan_stop:      \tex_relax:D
\group_end:    1322 \tex_let:D \group_begin:    \tex_begingroup:D
               1323 \tex_let:D \group_end:      \tex_endgroup:D
```

(End definition for `\scan_stop:`, `\group_begin:`, and `\group_end:`. These functions are documented on page 9.)

`\if_int_compare:w` For integers.

```
\__int_to_roman:w 1324 \tex_let:D \if_int_compare:w  \tex_ifnum:D
                  1325 \tex_let:D \__int_to_roman:w  \tex_romannumeral:D
```

(End definition for `\if_int_compare:w` and `__int_to_roman:w`. These functions are documented on page 79.)

`\group_insert_after:N` Adding material after the end of a group.

```
1326 \tex_let:D \group_insert_after:N \tex_aftergroup:D
```

(End definition for `\group_insert_after:N`. This function is documented on page 9.)

`\exp_args:Nc` Discussed in `l3expan`, but needed much earlier.

```
\exp_args:cc 1327 \tex_long:D \tex_def:D \exp_args:Nc #1#2
              1328 { \exp_after:wN #1 \cs:w #2 \cs_end: }
              1329 \tex_long:D \tex_def:D \exp_args:cc #1#2
              1330 { \cs:w #1 \exp_after:wN \cs_end: \cs:w #2 \cs_end: }
```

(End definition for `\exp_args:Nc` and `\exp_args:cc`. These functions are documented on page 27.)

`\token_to_meaning:c` A small number of variants defined by hand. Some of the necessary functions (`\use_i:nn`, `\use_ii:nn`, and `\exp_args:NNc`) are not defined at that point yet, but will be defined before those variants are used. The `\cs_meaning:c` command must check for an undefined control sequence to avoid defining it mistakenly.

```
\token_to_str:c 1331 \tex_def:D \token_to_str:c { \exp_args:Nc \token_to_str:N }
\cs_meaning:c   1332 \tex_long:D \tex_def:D \cs_meaning:c #1
                1333 {
                1334   \if_cs_exist:w #1 \cs_end:
                1335   \exp_after:wN \use_i:nn
                1336   \else:
                1337   \exp_after:wN \use_ii:nn
                1338   \fi:
                1339   { \exp_args:Nc \cs_meaning:N {#1} }
                1340   { \tl_to_str:n {undefined} }
                1341   }
                1342 \tex_let:D \token_to_meaning:c = \cs_meaning:c
```

(End definition for `\token_to_meaning:c`, `\token_to_str:c`, and `\cs_meaning:c`. These functions are documented on page 110.)

3.2 Defining some constants

`\c_zero` We need the constant `\c_zero` which is used by some functions in the `l3alloc` module. The rest are defined in the `l3int` module – at least for the ones that can be defined with `\tex_chardef:D` or `\tex_mathchardef:D`. For other constants the `l3int` module is required but it can't be used until the allocation has been set up properly!

```
1343 \tex_chardef:D \c_zero      = 0 ~
```

(End definition for `\c_zero`. This variable is documented on page 78.)

`\c_max_register_int` This is here as this particular integer is needed both in package mode and to bootstrap `l3alloc`, and is documented in `l3int`.

```
1344 \etex_ifdefined:D \luatex luatexversion:D
1345   \tex_chardef:D \c_max_register_int = 65 535 ~
1346 \tex_else:D
1347   \tex_mathchardef:D \c_max_register_int = 32 767 ~
1348 \tex_fi:D
```

(End definition for `\c_max_register_int`. This variable is documented on page 78.)

3.3 Defining functions

We start by providing functions for the typical definition functions. First the local ones.

`\cs_set_nopar:Npn` `\cs_set_nopar:Npx` All assignment functions in L^AT_EX3 should be naturally protected; after all, the T_EX primitives for assignments are and it can be a cause of problems if others aren't.

```

\cs_set:Npn      1349 \tex_let:D \cs_set_nopar:Npn      \tex_def:D
\cs_set:Npx      1350 \tex_let:D \cs_set_nopar:Npx      \tex_edef:D
\cs_set:Npn      1351 \etex_protected:D \tex_long:D \tex_def:D \cs_set:Npn
\cs_set_protected_nopar:Npn 1352   { \tex_long:D \tex_def:D }
\cs_set_protected_nopar:Npx 1353 \etex_protected:D \tex_long:D \tex_def:D \cs_set:Npx
\cs_set_protected:Npn 1354   { \tex_long:D \tex_edef:D }
\cs_set_protected:Npx 1355 \etex_protected:D \tex_long:D \tex_def:D \cs_set_protected_nopar:Npn
\cs_set_protected:Npn 1356   { \etex_protected:D \tex_def:D }
\cs_set_protected:Npx 1357 \etex_protected:D \tex_long:D \tex_def:D \cs_set_protected_nopar:Npx
\cs_set_protected:Npn 1358   { \etex_protected:D \tex_edef:D }
\cs_set_protected:Npx 1359 \etex_protected:D \tex_long:D \tex_def:D \cs_set_protected:Npn
\cs_set_protected:Npn 1360   { \etex_protected:D \tex_long:D \tex_def:D }
\cs_set_protected:Npx 1361 \etex_protected:D \tex_long:D \tex_def:D \cs_set_protected:Npx
\cs_set_protected:Npn 1362   { \etex_protected:D \tex_long:D \tex_edef:D }
```

(End definition for `\cs_set_nopar:Npn` and others. These functions are documented on page 11.)

`\cs_gset_nopar:Npn` `\cs_gset_nopar:Npx` Global versions of the above functions.
`\cs_gset:Npn` `\cs_gset:Npx`
`\cs_gset:Npn` `\cs_gset:Npx`
`\cs_gset_protected_nopar:Npn` `\cs_gset_protected_nopar:Npx`
`\cs_gset_protected_nopar:Npn` `\cs_gset_protected_nopar:Npx`
`\cs_gset_protected:Npn` `\cs_gset_protected:Npn`
`\cs_gset_protected:Npx` `\cs_gset_protected:Npx`

```

1363 \tex_let:D \cs_gset_nopar:Npn      \tex_gdef:D
1364 \tex_let:D \cs_gset_nopar:Npx      \tex_xdef:D
1365 \cs_set_protected:Npn \cs_gset:Npn
1366   { \tex_long:D \tex_gdef:D }
1367 \cs_set_protected:Npn \cs_gset:Npx
1368   { \tex_long:D \tex_xdef:D }
1369 \cs_set_protected:Npn \cs_gset_protected_nopar:Npn
1370   { \etex_protected:D \tex_gdef:D }
1371 \cs_set_protected:Npn \cs_gset_protected_nopar:Npx
1372   { \etex_protected:D \tex_xdef:D }
```

```

1373 \cs_set_protected:Npn \cs_gset_protected:Npn
1374   { \etex_protected:D \tex_long:D \tex_gdef:D }
1375 \cs_set_protected:Npn \cs_gset_protected:Npx
1376   { \etex_protected:D \tex_long:D \tex_xdef:D }

```

(End definition for `\cs_gset_nopar:Npn` and others. These functions are documented on page 12.)

3.4 Selecting tokens

`\l__exp_internal_tl` Scratch token list variable for `l3expan`, used by `\use:x`, used in defining conditionals. We don't use `tl` methods because `l3basics` is loaded earlier.

```

1377 \cs_set_nopar:Npn \l__exp_internal_tl { }

```

(End definition for `\l__exp_internal_tl`.)

`\use:c` This macro grabs its argument and returns a csname from it.

```

1378 \cs_set:Npn \use:c #1 { \cs:w #1 \cs_end: }

```

(End definition for `\use:c`. This function is documented on page 16.)

`\use:x` Fully expands its argument and passes it to the input stream. Uses the reserved `\l__exp_internal_tl` which will be set up in `l3expan`.

```

1379 \cs_set_protected:Npn \use:x #1
1380   {
1381     \cs_set_nopar:Npx \l__exp_internal_tl {#1}
1382     \l__exp_internal_tl
1383   }

```

(End definition for `\use:x`. This function is documented on page 19.)

`\use:n` These macros grab their arguments and returns them back to the input (with outer braces removed).

```

\use:nnn 1384 \cs_set:Npn \use:n #1 {#1}
\use:nnnn 1385 \cs_set:Npn \use:nn #1#2 {#1#2}
1386 \cs_set:Npn \use:nnn #1#2#3 {#1#2#3}
1387 \cs_set:Npn \use:nnnn #1#2#3#4 {#1#2#3#4}

```

(End definition for `\use:n` and others. These functions are documented on page 17.)

`\use_i:nn` The equivalent to L^AT_EX 2_ε's `\@firstoftwo` and `\@secondoftwo`.

```

\use_ii:nn 1388 \cs_set:Npn \use_i:nn #1#2 {#1}
1389 \cs_set:Npn \use_ii:nn #1#2 {#2}

```

(End definition for `\use_i:nn` and `\use_ii:nn`. These functions are documented on page 18.)

`\use_i:nnn` We also need something for picking up arguments from a longer list.

```

\use_ii:nnn 1390 \cs_set:Npn \use_i:nnn #1#2#3 {#1}
\use_iii:nnn 1391 \cs_set:Npn \use_ii:nnn #1#2#3 {#2}
\use_i_ii:nnn 1392 \cs_set:Npn \use_iii:nnn #1#2#3 {#3}
\use_i:nnnn 1393 \cs_set:Npn \use_i_ii:nnn #1#2#3 {#1#2}
\use_ii:nnnn 1394 \cs_set:Npn \use_i:nnnn #1#2#3#4 {#1}
\use_iii:nnnn 1395 \cs_set:Npn \use_ii:nnnn #1#2#3#4 {#2}
\use_iv:nnnn 1396 \cs_set:Npn \use_iii:nnnn #1#2#3#4 {#3}
1397 \cs_set:Npn \use_iv:nnnn #1#2#3#4 {#4}

```

(End definition for `\use_i:nnn` and others. These functions are documented on page 18.)

`\use_none_delimit_by_q_nil:w` Functions that gobble everything until they see either `\q_nil`, `\q_stop`, or `\q_recursion_stop`, respectively.
`\use_none_delimit_by_q_stop:w`
`\use_none_delimit_by_q_recursion_stop:w`

```

1398 \cs_set:Npn \use_none_delimit_by_q_nil:w #1 \q_nil { }
1399 \cs_set:Npn \use_none_delimit_by_q_stop:w #1 \q_stop { }
1400 \cs_set:Npn \use_none_delimit_by_q_recursion_stop:w #1 \q_recursion_stop { }

```

(End definition for `\use_none_delimit_by_q_nil:w`, `\use_none_delimit_by_q_stop:w`, and `\use_none_delimit_by_q_recursion_stop:w`. These functions are documented on page 19.)

`\use_i_delimit_by_q_nil:nw` Same as above but execute first argument after gobbling. Very useful when you need to skip the rest of a mapping sequence but want an easy way to control what should be expanded next.
`\use_i_delimit_by_q_stop:nw`
`\use_i_delimit_by_q_recursion_stop:nw`

```

1401 \cs_set:Npn \use_i_delimit_by_q_nil:nw #1#2 \q_nil {#1}
1402 \cs_set:Npn \use_i_delimit_by_q_stop:nw #1#2 \q_stop {#1}
1403 \cs_set:Npn \use_i_delimit_by_q_recursion_stop:nw #1#2 \q_recursion_stop {#1}

```

(End definition for `\use_i_delimit_by_q_nil:nw`, `\use_i_delimit_by_q_stop:nw`, and `\use_i_delimit_by_q_recursion_stop:nw`. These functions are documented on page 19.)

3.5 Gobbling tokens from input

`\use_none:n` To gobble tokens from the input we use a standard naming convention: the number of tokens gobbled is given by the number of `n`'s following the `:` in the name. Although we could define functions to remove ten arguments or more using separate calls of `\use_none:nnnnn`, this is very non-intuitive to the programmer who will assume that expanding such a function once will take care of gobbling all the tokens in one go.

`\use_none:nn`
`\use_none:nnn`
`\use_none:nnnn`
`\use_none:nnnnn`
`\use_none:nnnnnn`
`\use_none:nnnnnnn`
`\use_none:nnnnnnnn`

```

1404 \cs_set:Npn \use_none:n #1 { }
1405 \cs_set:Npn \use_none:nn #1#2 { }
1406 \cs_set:Npn \use_none:nnn #1#2#3 { }
1407 \cs_set:Npn \use_none:nnnn #1#2#3#4 { }
1408 \cs_set:Npn \use_none:nnnnn #1#2#3#4#5 { }
1409 \cs_set:Npn \use_none:nnnnnn #1#2#3#4#5#6 { }
1410 \cs_set:Npn \use_none:nnnnnnn #1#2#3#4#5#6#7 { }
1411 \cs_set:Npn \use_none:nnnnnnnn #1#2#3#4#5#6#7#8 { }
1412 \cs_set:Npn \use_none:nnnnnnnnn #1#2#3#4#5#6#7#8#9 { }

```

(End definition for `\use_none:n` and others. These functions are documented on page 18.)

3.6 Conditional processing and definitions

Underneath any predicate function (`_p`) or other conditional forms (TF, etc.) is a built-in logic saying that it after all of the testing and processing must return the *state* this leaves T_EX in. Therefore, a simple user interface could be something like

```

\if_meaning:w #1#2
  \prg_return_true:
\else:
  \if_meaning:w #1#3
    \prg_return_true:
  \else:
    \prg_return_false:

```

```

\fi:
\fi:

```

Usually, a T_EX programmer would have to insert a number of `\exp_after:wN`s to ensure the state value is returned at exactly the point where the last conditional is finished. However, that obscures the code and forces the T_EX programmer to prove that he/she knows the $2^n - 1$ table. We therefore provide the simpler interface.

`\prg_return_true:` The idea here is that `\exp:w` will expand fully any `\else:` and the `\fi:` that are waiting to be discarded, before reaching the `\exp_end:` which will leave the expansion null. The code can then leave either the first or second argument in the input stream. This means that all of the branching code has to contain at least two tokens: see how the logical tests are actually implemented to see this.

```

1413 \cs_set:Npn \prg_return_true:
1414   { \exp_after:wN \use_i:nn \exp:w }
1415 \cs_set:Npn \prg_return_false:
1416   { \exp_after:wN \use_ii:nn \exp:w }

```

An extended state space could be implemented by including a more elaborate function in place of `\use_i:nn/\use_ii:nn`. Provided two arguments are absorbed then the code will work.

(End definition for \prg_return_true: and \prg_return_false:. These functions are documented on page 90.)

`\prg_set_conditional:Npnn` The user functions for the types using parameter text from the programmer. The various functions only differ by which function is used for the assignment. For those `Npnn` type functions, we must grab the parameter text, reading everything up to a left brace before continuing. Then split the base function into name and signature, and feed `{\langle name \rangle}` `{\langle signature \rangle}` `\langle boolean \rangle` `{\langle set or new \rangle}` `{\langle maybe protected \rangle}` `{\langle parameters \rangle}` `{TF, ...}` `{\langle code \rangle}` to the auxiliary function responsible for defining all conditionals.

```

1417 \cs_set_protected:Npn \prg_set_conditional:Npnn
1418   { \prg_generate_conditional_parm:nnNpnn { set } { } }
1419 \cs_set_protected:Npn \prg_new_conditional:Npnn
1420   { \prg_generate_conditional_parm:nnNpnn { new } { } }
1421 \cs_set_protected:Npn \prg_set_protected_conditional:Npnn
1422   { \prg_generate_conditional_parm:nnNpnn { set } { _protected } }
1423 \cs_set_protected:Npn \prg_new_protected_conditional:Npnn
1424   { \prg_generate_conditional_parm:nnNpnn { new } { _protected } }
1425 \cs_set_protected:Npn \prg_generate_conditional_parm:nnNpnn #1#2#3#4#
1426   {
1427     \cs_split_function:NN #3 \prg_generate_conditional:nnNnnnnn
1428     {#1} {#2} {#4}
1429   }

```

(End definition for \prg_set_conditional:Npnn and others. These functions are documented on page 88.)

`\prg_set_conditional:Nnn` The user functions for the types automatically inserting the correct parameter text based on the signature. The various functions only differ by which function is used for the assignment. Split the base function into name and signature. The second auxiliary generates the parameter text from the number of letters in the signature. Then feed `{\langle name \rangle}` `{\langle signature \rangle}` `\langle boolean \rangle` `{\langle set or new \rangle}` `{\langle maybe protected \rangle}` `{\langle parameters \rangle}` `{TF, ...}` `{\langle code \rangle}` to the auxiliary function responsible for defining all conditionals. If

the *signature* has more than 9 letters, the definition is aborted since T_EX macros have at most 9 arguments. The erroneous case where the function name contains no colon is captured later.

```

1430 \cs_set_protected:Npn \prg_set_conditional:Nnn
1431   { \prg_generate_conditional_count:nnNnn { set } { } }
1432 \cs_set_protected:Npn \prg_new_conditional:Nnn
1433   { \prg_generate_conditional_count:nnNnn { new } { } }
1434 \cs_set_protected:Npn \prg_set_protected_conditional:Nnn
1435   { \prg_generate_conditional_count:nnNnn { set } { _protected } }
1436 \cs_set_protected:Npn \prg_new_protected_conditional:Nnn
1437   { \prg_generate_conditional_count:nnNnn { new } { _protected } }
1438 \cs_set_protected:Npn \prg_generate_conditional_count:nnNnn #1#2#3
1439   {
1440     \cs_split_function:NN #3 \prg_generate_conditional_count:nnNnnnn
1441     {#1} {#2}
1442   }
1443 \cs_set_protected:Npn \prg_generate_conditional_count:nnNnnnn #1#2#3#4#5
1444   {
1445     \cs_parm_from_arg_count:nnF
1446     { \prg_generate_conditional:nnNnnnn {#1} {#2} #3 {#4} {#5} }
1447     { \tl_count:n {#2} }
1448     {
1449       \msg_kernel_error:nxx { kernel } { bad-number-of-arguments }
1450       { \token_to_str:c { #1 : #2 } }
1451       { \tl_count:n {#2} }
1452       \use_none:nn
1453     }
1454   }

```

(End definition for `\prg_set_conditional:Nnn` and others. These functions are documented on page 88.)

`\prg_generate_conditional:nnNnnnn`
`\prg_generate_conditional:nnnnnnw`

The workhorse here is going through a list of desired forms, *i.e.*, p, TF, T and F. The first three arguments come from splitting up the base form of the conditional, which gives the name, signature and a boolean to signal whether or not there was a colon in the name. In the absence of a colon, we throw an error and don't define any conditional. The fourth and fifth arguments build up the defining function. The sixth is the parameters to use (possibly empty), the seventh is the list of forms to define, the eighth is the replacement text which we will augment when defining the forms. The use of `\tl_to_str:n` makes the later loop more robust.

```

1455 \cs_set_protected:Npn \prg_generate_conditional:nnNnnnn #1#2#3#4#5#6#7#8
1456   {
1457     \if_meaning:w \c_false_bool #3
1458     \msg_kernel_error:nxx { kernel } { missing-colon }
1459     { \token_to_str:c {#1} }
1460     \exp_after:wN \use_none:nn
1461     \fi:
1462     \use:x
1463     {
1464       \exp_not:N \prg_generate_conditional:nnnnnnw
1465       \exp_not:n { {#4} {#5} {#1} {#2} {#6} {#8} }
1466       \tl_to_str:n {#7}
1467       \exp_not:n { , \q_recursion_tail , \q_recursion_stop }

```

```

1468     }
1469 }

```

Looping through the list of desired forms. First are six arguments and seventh is the form. Use the form to call the correct type. If the form does not exist, the `\use:c` construction results in `\relax`, and the error message is displayed (unless the form is empty, to allow for {T, , F}), then `\use_none:nnnnnnn` cleans up. Otherwise, the error message is removed by the variant form.

```

1470 \cs_set_protected:Npn \__prg_generate_conditional:nnnnnnw #1#2#3#4#5#6#7 ,
1471 {
1472     \if_meaning:w \q_recursion_tail #7
1473     \exp_after:wN \use_none_delimit_by_q_recursion_stop:w
1474     \fi:
1475     \use:c { __prg_generate_ #7 _form:wnnnnnn }
1476     \tl_if_empty:nF {#7}
1477     {
1478         \__msg_kernel_error:nnxx
1479         { kernel } { conditional-form-unknown }
1480         {#7} { \token_to_str:c { #3 : #4 } }
1481     }
1482     \use_none:nnnnnnn
1483     \q_stop
1484     {#1} {#2} {#3} {#4} {#5} {#6}
1485     \__prg_generate_conditional:nnnnnnw {#1} {#2} {#3} {#4} {#5} {#6}
1486 }

```

(End definition for `__prg_generate_conditional:nnNnnnnn` and `__prg_generate_conditional:nnnnnnw`.)

```

\__prg_generate_p_form:wnnnnnn
\__prg_generate_TF_form:wnnnnnn
\__prg_generate_T_form:wnnnnnn
\__prg_generate_F_form:wnnnnnn

```

How to generate the various forms. Those functions take the following arguments: 1: **set** or **new**, 2: empty or `_protected`, 3: function name 4: signature, 5: parameter text (or empty), 6: replacement. Remember that the logic-returning functions expect two arguments to be present after `\exp_end::` notice the construction of the different variants relies on this, and that the TF variant will be slightly faster than the T version. The **p** form is only valid for expandable tests, we check for that by making sure that the second argument is empty.

```

1487 \cs_set_protected:Npn \__prg_generate_p_form:wnnnnnn
1488     #1 \q_stop #2#3#4#5#6#7
1489 {
1490     \if_meaning:w \scan_stop: #3 \scan_stop:
1491     \exp_after:wN \use_i:nn
1492     \else:
1493     \exp_after:wN \use_ii:nn
1494     \fi:
1495     {
1496         \exp_args:cc { cs_ #2 #3 :Npn } { #4 _p: #5 } #6
1497         { #7 \exp_end: \c_true_bool \c_false_bool }
1498     }
1499     {
1500         \__msg_kernel_error:nnx { kernel } { protected-predicate }
1501         { \token_to_str:c { #4 _p: #5 } }
1502     }
1503 }
1504 \cs_set_protected:Npn \__prg_generate_T_form:wnnnnnn
1505     #1 \q_stop #2#3#4#5#6#7

```

```

1506 {
1507   \exp_args:cc { cs_ #2 #3 :Npn } { #4 : #5 T } #6
1508   { #7 \exp_end: \use:n \use_none:n }
1509 }
1510 \cs_set_protected:Npn \__prg_generate_F_form:wnnnnnn
1511   #1 \q_stop #2#3#4#5#6#7
1512 {
1513   \exp_args:cc { cs_ #2 #3 :Npn } { #4 : #5 F } #6
1514   { #7 \exp_end: { } }
1515 }
1516 \cs_set_protected:Npn \__prg_generate_TF_form:wnnnnnn
1517   #1 \q_stop #2#3#4#5#6#7
1518 {
1519   \exp_args:cc { cs_ #2 #3 :Npn } { #4 : #5 TF } #6
1520   { #7 \exp_end: { } }
1521 }

```

(End definition for __prg_generate_p_form:wnnnnnn and others.)

\prg_set_eq_conditional:NNn The setting-equal functions. Split both functions and feed $\{\langle name_1 \rangle\}$ $\{\langle signature_1 \rangle\}$ $\langle boolean_1 \rangle$ $\{\langle name_2 \rangle\}$ $\{\langle signature_2 \rangle\}$ $\langle boolean_2 \rangle$ $\langle copying\ function \rangle$ $\langle conditions \rangle$, $\backslash q_recursion_tail$, $\backslash q_recursion_stop$ to a first auxiliary.

\prg_new_eq_conditional:NNn

$\backslash_prg_set_eq_conditional:NNn$

```

1522 \cs_set_protected:Npn \prg_set_eq_conditional:NNn
1523 { \__prg_set_eq_conditional:NNNn \cs_set_eq:cc }
1524 \cs_set_protected:Npn \prg_new_eq_conditional:NNn
1525 { \__prg_set_eq_conditional:NNNn \cs_new_eq:cc }
1526 \cs_set_protected:Npn \__prg_set_eq_conditional:NNNn #1#2#3#4
1527 {
1528   \use:x
1529   {
1530     \exp_not:N \__prg_set_eq_conditional:nnNnnNNw
1531     \__cs_split_function:NN #2 \prg_do_nothing:
1532     \__cs_split_function:NN #3 \prg_do_nothing:
1533     \exp_not:N #1
1534     \tl_to_str:n {#4}
1535     \exp_not:n { , \q_recursion_tail , \q_recursion_stop }
1536   }
1537 }

```

(End definition for $\backslash prg_set_eq_conditional:NNn$, $\backslash prg_new_eq_conditional:NNn$, and $\backslash_prg_set_eq_conditional:NNNn$. These functions are documented on page 89.)

$\backslash_prg_set_eq_conditional:nnNnnNNw$
 $\backslash_prg_set_eq_conditional_loop:nnnnNw$
 $\backslash_prg_set_eq_conditional_p_form:nnn$
 $\backslash_prg_set_eq_conditional_TF_form:nnn$
 $\backslash_prg_set_eq_conditional_T_form:nnn$
 $\backslash_prg_set_eq_conditional_F_form:nnn$

Split the function to be defined, and setup a manual clist loop over argument #6 of the first auxiliary. The second auxiliary receives twice three arguments coming from splitting the function to be defined and the function to copy. Make sure that both functions contained a colon, otherwise we don't know how to build conditionals, hence abort. Call the looping macro, with arguments $\{\langle name_1 \rangle\}$ $\{\langle signature_1 \rangle\}$ $\{\langle name_2 \rangle\}$ $\{\langle signature_2 \rangle\}$ $\langle copying\ function \rangle$ and followed by the comma list. At each step in the loop, make sure that the conditional form we copy is defined, and copy it, otherwise abort.

```

1538 \cs_set_protected:Npn \__prg_set_eq_conditional:nnNnnNNw #1#2#3#4#5#6
1539 {
1540   \if_meaning:w \c_false_bool #3
1541   \__msg_kernel_error:nnx { kernel } { missing-colon }
1542   { \token_to_str:c {#1} }

```

```

1543     \exp_after:wN \use_none_delimit_by_q_recursion_stop:w
1544 \fi:
1545 \if_meaning:w \c_false_bool #6
1546   \_msg_kernel_error:nxx { kernel } { missing-colon }
1547   { \token_to_str:c {#4} }
1548   \exp_after:wN \use_none_delimit_by_q_recursion_stop:w
1549 \fi:
1550 \__prg_set_eq_conditional_loop:nnnnNw {#1} {#2} {#4} {#5}
1551 }
1552 \cs_set_protected:Npn \__prg_set_eq_conditional_loop:nnnnNw #1#2#3#4#5#6 ,
1553 {
1554   \if_meaning:w \q_recursion_tail #6
1555   \exp_after:wN \use_none_delimit_by_q_recursion_stop:w
1556 \fi:
1557 \use:c { __prg_set_eq_conditional_ #6 _form:wNnnnn }
1558   \tl_if_empty:nF {#6}
1559   {
1560     \_msg_kernel_error:nxxx
1561     { kernel } { conditional-form-unknown }
1562     {#6} { \token_to_str:c { #1 : #2 } }
1563   }
1564   \use_none:nnnnnn
1565   \q_stop
1566   #5 {#1} {#2} {#3} {#4}
1567   \__prg_set_eq_conditional_loop:nnnnNw {#1} {#2} {#3} {#4} #5
1568 }
1569 \cs_set:Npn \__prg_set_eq_conditional_p_form:wNnnnn #1 \q_stop #2#3#4#5#6
1570 {
1571   \__chk_if_exist_cs:c { #5 _p : #6 }
1572   #2 { #3 _p : #4 } { #5 _p : #6 }
1573 }
1574 \cs_set:Npn \__prg_set_eq_conditional_TF_form:wNnnnn #1 \q_stop #2#3#4#5#6
1575 {
1576   \__chk_if_exist_cs:c { #5 : #6 TF }
1577   #2 { #3 : #4 TF } { #5 : #6 TF }
1578 }
1579 \cs_set:Npn \__prg_set_eq_conditional_T_form:wNnnnn #1 \q_stop #2#3#4#5#6
1580 {
1581   \__chk_if_exist_cs:c { #5 : #6 T }
1582   #2 { #3 : #4 T } { #5 : #6 T }
1583 }
1584 \cs_set:Npn \__prg_set_eq_conditional_F_form:wNnnnn #1 \q_stop #2#3#4#5#6
1585 {
1586   \__chk_if_exist_cs:c { #5 : #6 F }
1587   #2 { #3 : #4 F } { #5 : #6 F }
1588 }

```

(End definition for __prg_set_eq_conditional:nnnnNw and others.)

All that is left is to define the canonical boolean true and false. I think Michael originated the idea of expandable boolean tests. At first these were supposed to expand into either TT or TF to be tested using \if:w but this was later changed to 00 and 01, so they could be used in logical operations. Later again they were changed to being numerical constants with values of 1 for true and 0 for false. We need this from the get-go.


```

\c_true_bool Here are the canonical boolean values.
\c_false_bool
1589 \tex_chardef:D \c_true_bool = 1 ~
1590 \tex_chardef:D \c_false_bool = 0 ~

```

(End definition for `\c_true_bool` and `\c_false_bool`. These variables are documented on page 20.)

3.7 Dissecting a control sequence

```

\cs_to_str:N This converts a control sequence into the character string of its name, removing the
__cs_to_str:N leading escape character. This turns out to be a non-trivial matter as there are different
__cs_to_str:w cases:

```

- The usual case of a printable escape character;
- the case of a non-printable escape characters, e.g., when the value of the `\escapechar` is negative;
- when the escape character is a space.

One approach to solve this is to test how many tokens result from `\token_to_str:N \a`. If there are two tokens, then the escape character is printable, while if it is non-printable then only one is present.

However, there is an additional complication: the control sequence itself may start with a space. Clearly that should *not* be lost in the process of converting to a string. So the approach adopted is a little more intricate still. When the escape character is printable, `\token_to_str:N _ _` yields the escape character itself and a space. The character codes are different, thus the `\if:w` test is false, and TeX reads `__cs_to_str:N` after turning the following control sequence into a string; this auxiliary removes the escape character, and stops the expansion of the initial `\tex_romannumeral:D`. The second case is that the escape character is not printable. Then the `\if:w` test is unfinished after reading a the space from `\token_to_str:N _ _`, and the auxiliary `__cs_to_str:w` is expanded, feeding – as a second character for the test; the test is false, and TeX skips to `\fi:`, then performs `\token_to_str:N`, and stops the `\tex_romannumeral:D` with `\c_zero`. The last case is that the escape character is itself a space. In this case, the `\if:w` test is true, and the auxiliary `__cs_to_str:w` comes into play, inserting `-__int_value:w`, which expands `\c_zero` to the character 0. The initial `\tex_romannumeral:D` then sees 0, which is not a terminated number, followed by the escape character, a space, which is removed, terminating the expansion of `\tex_romannumeral:D`. In all three cases, `\cs_to_str:N` takes two expansion steps to be fully expanded.

```

1591 \cs_set:Npn \cs_to_str:N
1592 {

```

We implement the expansion scheme using `\tex_romannumeral:D` terminating it with `\c_zero` rather than using `\exp:w` and `\exp_end:` as we normally do. The reason is that the code heavily depends on terminating the expansion with `\c_zero` so we make this dependency explicit.

```

1593 \tex_romannumeral:D
1594 \if:w \token_to_str:N \__cs_to_str:w \fi:
1595 \exp_after:wN \__cs_to_str:N \token_to_str:N
1596 }
1597 \cs_set:Npn \__cs_to_str:N #1 { \c_zero }
1598 \cs_set:Npn \__cs_to_str:w #1 \__cs_to_str:N
1599 { - \__int_value:w \fi: \exp_after:wN \c_zero }

```

If speed is a concern we could use `\csstring` in LuaTeX. For the empty csname that primitive gives an empty result while the current `\cs_to_str:N` gives incorrect results in all engines (this is impossible to fix without huge performance hit).

(End definition for `\cs_to_str:N`, `_cs_to_str:N`, and `_cs_to_str:w`. These functions are documented on page 17.)

`_cs_split_function:NN` This function takes a function name and splits it into name with the escape char removed and argument specification. In addition to this, a third argument, a boolean $\langle true \rangle$ or $\langle false \rangle$ is returned with $\langle true \rangle$ for when there is a colon in the function and $\langle false \rangle$ if there is not. Lastly, the second argument of `_cs_split_function:NN` is supposed to be a function taking three variables, one for name, one for signature, and one for the boolean. For example, `_cs_split_function:NN \foo_bar:cnx \use_i:nnn` as input becomes `\use_i:nnn {foo_bar} {cnx} \c_true_bool`.

We cannot use `:` directly as it has the wrong category code so an x-type expansion is used to force the conversion.

First ensure that we actually get a properly evaluated string by expanding `\cs_to_str:N` twice. If the function contained a colon, the auxiliary takes as #1 the function name, delimited by the first colon, then the signature #2, delimited by `\q_mark`, then `\c_true_bool` as #3, and #4 cleans up until `\q_stop`. Otherwise, the #1 contains the function name and `\q_mark \c_true_bool`, #2 is empty, #3 is `\c_false_bool`, and #4 cleans up. In both cases, #5 is the $\langle processor \rangle$. The second auxiliary trims the trailing `\q_mark` from the function name if present (that is, if the original function had no colon).

```

1600 \cs_set:Npx \_cs_split_function:NN #1
1601 {
1602   \exp_not:N \exp_after:wN \exp_not:N \exp_after:wN
1603   \exp_not:N \exp_after:wN \exp_not:N \_cs_split_function_auxi:w
1604   \exp_not:N \cs_to_str:N #1 \exp_not:N \q_mark \c_true_bool
1605   \token_to_str:N : \exp_not:N \q_mark \c_false_bool
1606   \exp_not:N \q_stop
1607 }
1608 \use:x
1609 {
1610   \cs_set:Npn \exp_not:N \_cs_split_function_auxi:w
1611     ##1 \token_to_str:N : ##2 \exp_not:N \q_mark ##3##4 \exp_not:N \q_stop ##5
1612 }
1613 { \_cs_split_function_auxii:w #5 #1 \q_mark \q_stop {#2} #3 }
1614 \cs_set:Npn \_cs_split_function_auxii:w #1#2 \q_mark #3 \q_stop
1615 { #1 {#2} }

```

(End definition for `_cs_split_function:NN`, `_cs_split_function_auxi:w`, and `_cs_split_function_auxii:w`.)

`_cs_get_function_name:N` Simple wrappers.

```

\cs_get_function_signature:N
1616 \cs_set:Npn \_cs_get_function_name:N #1
1617 { \_cs_split_function:NN #1 \use_i:nnn }
1618 \cs_set:Npn \_cs_get_function_signature:N #1
1619 { \_cs_split_function:NN #1 \use_ii:nnn }

```

(End definition for `_cs_get_function_name:N` and `_cs_get_function_signature:N`.)

3.8 Exist or free

A control sequence is said to *exist* (to be used) if has an entry in the hash table and its meaning is different from the primitive `\relax` token. A control sequence is said to be *free* (to be defined) if it does not already exist.

`\cs_if_exist_p:N` Two versions for checking existence. For the `N` form we firstly check for `\scan_stop:` and
`\cs_if_exist_p:c` then if it is in the hash table. There is no problem when inputting something like `\else:`
`\cs_if_exist:NTF` or `\fi:` as `TEX` will only ever skip input in case the token tested against is `\scan_stop:`.
`\cs_if_exist:cTF`

```

1620 \prg_set_conditional:Npnn \cs_if_exist:N #1 { p , T , F , TF }
1621 {
1622   \if_meaning:w #1 \scan_stop:
1623   \prg_return_false:
1624   \else:
1625     \if_cs_exist:N #1
1626     \prg_return_true:
1627     \else:
1628       \prg_return_false:
1629     \fi:
1630   \fi:
1631 }

```

For the `c` form we firstly check if it is in the hash table and then for `\scan_stop:` so that we do not add it to the hash table unless it was already there. Here we have to be careful as the text to be skipped if the first test is false may contain tokens that disturb the scanner. Therefore, we ensure that the second test is performed after the first one has concluded completely.

```

1632 \prg_set_conditional:Npnn \cs_if_exist:c #1 { p , T , F , TF }
1633 {
1634   \if_cs_exist:w #1 \cs_end:
1635   \exp_after:wN \use_i:nn
1636   \else:
1637     \exp_after:wN \use_ii:nn
1638   \fi:
1639   {
1640     \exp_after:wN \if_meaning:w \cs:w #1 \cs_end: \scan_stop:
1641     \prg_return_false:
1642     \else:
1643       \prg_return_true:
1644     \fi:
1645   }
1646   \prg_return_false:
1647 }

```

(End definition for `\cs_if_exist:NTF`. This function is documented on page 20.)

`\cs_if_free_p:N` The logical reversal of the above.

```

1648 \prg_set_conditional:Npnn \cs_if_free:N #1 { p , T , F , TF }
1649 {
1650   \if_meaning:w #1 \scan_stop:
1651   \prg_return_true:
1652   \else:
1653     \if_cs_exist:N #1
1654     \prg_return_false:

```

```

1655     \else:
1656       \prg_return_true:
1657     \fi:
1658   \fi:
1659 }
1660 \prg_set_conditional:Npnn \cs_if_free:c #1 { p , T , F , TF }
1661 {
1662   \if_cs_exist:w #1 \cs_end:
1663     \exp_after:wN \use_i:nn
1664   \else:
1665     \exp_after:wN \use_ii:nn
1666   \fi:
1667   {
1668     \exp_after:wN \if_meaning:w \cs:w #1 \cs_end: \scan_stop:
1669     \prg_return_true:
1670   \else:
1671     \prg_return_false:
1672   \fi:
1673 }
1674 { \prg_return_true: }
1675 }

```

(End definition for `\cs_if_free:NTF`. This function is documented on page 20.)

`\cs_if_exist_use:N` The `\cs_if_exist_use:...` functions cannot be implemented as conditionals because the true branch must leave both the control sequence itself and the true code in the input stream. For the `c` variants, we are careful not to put the control sequence in the hash table if it does not exist. In LuaTeX we could use the `\lastnamedcs` primitive.

```

1676 \cs_set:Npn \cs_if_exist_use:NTF #1#2
1677   { \cs_if_exist:NTF #1 { #1 #2 } }
1678 \cs_set:Npn \cs_if_exist_use:NF #1
1679   { \cs_if_exist:NTF #1 { #1 } }
1680 \cs_set:Npn \cs_if_exist_use:NT #1 #2
1681   { \cs_if_exist:NTF #1 { #1 #2 } { } }
1682 \cs_set:Npn \cs_if_exist_use:N #1
1683   { \cs_if_exist:NTF #1 { #1 } { } }
1684 \cs_set:Npn \cs_if_exist_use:cTF #1#2
1685   { \cs_if_exist:cTF {#1} { \use:c {#1} #2 } }
1686 \cs_set:Npn \cs_if_exist_use:cF #1
1687   { \cs_if_exist:cTF {#1} { \use:c {#1} } }
1688 \cs_set:Npn \cs_if_exist_use:cT #1#2
1689   { \cs_if_exist:cTF {#1} { \use:c {#1} #2 } { } }
1690 \cs_set:Npn \cs_if_exist_use:c #1
1691   { \cs_if_exist:cTF {#1} { \use:c {#1} } { } }

```

(End definition for `\cs_if_exist_use:NTF`. This function is documented on page 16.)

3.9 Defining and checking (new) functions

We provide two kinds of functions that can be used to define control sequences. On the one hand we have functions that check if their argument doesn't already exist, they are called `\..._new`. The second type of defining functions doesn't check if the argument is already defined.

Before we can define them, we need some auxiliary macros that allow us to generate error messages. The definitions here are only temporary, they will be redefined later on.

`\iow_log:x` We define a routine to write only to the log file. And a similar one for writing to both
`\iow_term:x` the log file and the terminal. These will be redefined later by `l3io`.

```
1692 \cs_set_protected:Npn \iow_log:x
1693   { \tex_immediate:D \tex_write:D -1 }
1694 \cs_set_protected:Npn \iow_term:x
1695   { \tex_immediate:D \tex_write:D 16 }
```

(End definition for `\iow_log:x` and `\iow_term:x`. These functions are documented on page 139.)

`__chk_log:x` This function is used to write some information to the log file in case the `log-function`
`__chk_suspend_log:` option is set. Otherwise its argument is ignored. Using this function rather than di-
`__chk_resume_log:` rectly using `\iow_log:x` allows for `__chk_suspend_log:` which disables such messages
until the matching `__chk_resume_log:`. These two commands are used to improve the
logging for complicated datatypes. They should come in pairs, which can be nested.
The function `\exp_not:o` is defined in `l3expan` later on but `__chk_suspend_log:` and
`__chk_resume_log:` are not used before that point.

```
1696 <*initex>
1697 \cs_set_protected:Npn \__chk_log:x { \use_none:n }
1698 \cs_set_protected:Npn \__chk_suspend_log: { }
1699 \cs_set_protected:Npn \__chk_resume_log: { }
1700 </initex>
1701 <*package>
1702 \tex_ifodd:D \l@expl@log@functions@bool
1703   \cs_set_protected:Npn \__chk_log:x { \iow_log:x }
1704   \cs_set_protected:Npn \__chk_suspend_log:
1705     {
1706       \cs_set_protected:Npx \__chk_resume_log:
1707       {
1708         \cs_set_protected:Npn \__chk_resume_log:
1709           { \exp_not:o { \__chk_resume_log: } }
1710         \cs_set_protected:Npn \__chk_log:x
1711           { \exp_not:o { \__chk_log:x } }
1712       }
1713       \cs_set_protected:Npn \__chk_log:x { \use_none:n }
1714     }
1715   \cs_set_protected:Npn \__chk_resume_log: { }
1716 \else:
1717   \cs_set_protected:Npn \__chk_log:x { \use_none:n }
1718   \cs_set_protected:Npn \__chk_suspend_log: { }
1719   \cs_set_protected:Npn \__chk_resume_log: { }
1720 \fi:
1721 </package>
```

(End definition for `__chk_log:x`, `__chk_suspend_log:`, and `__chk_resume_log:`.)

`__msg_kernel_error:nxxx` If an internal error occurs before L^AT_EX3 has loaded `l3msg` then the code should issue a
`__msg_kernel_error:nxx` usable if terse error message and halt. This can only happen if a coding error is made by
`__msg_kernel_error:nn` the team, so this is a reasonable response. Setting the `\newlinechar` is needed, to turn
`^^J` into a proper line break in plain T_EX.

```
1722 \cs_set_protected:Npn \__msg_kernel_error:nxxx #1#2#3#4
```

```

1723 {
1724   \tex_newlinechar:D = '\^^J \tex_relax:D
1725   \tex_errmessage:D
1726   {
1727     !!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!~! ^^J
1728     Argh,~internal~LaTeX3~error! ^^J ^^J
1729     Module ~ #1 , ~ message~name~"#2": ^^J
1730     Arguments~'#3'~and~'#4' ^^J ^^J
1731     This~is~one~for~The~LaTeX3~Project:~bailing~out
1732   }
1733   \tex_end:D
1734 }
1735 \cs_set_protected:Npn \_msg_kernel_error:nxx #1#2#3
1736 { \_msg_kernel_error:nxxx {#1} {#2} {#3} { } }
1737 \cs_set_protected:Npn \_msg_kernel_error:nn #1#2
1738 { \_msg_kernel_error:nxxx {#1} {#2} { } { } }

(End definition for \_msg_kernel_error:nxxx, \_msg_kernel_error:nxx, and \_msg_kernel_error:nn.)

```

\msg_line_context: Another one from l3msg which will be altered later.

```

1739 \cs_set:Npn \msg_line_context:
1740 { on~line~ \tex_the:D \tex_inputlineno:D }

(End definition for \msg_line_context:. This function is documented on page 127.)

```

__chk_if_free_cs:N This command is called by \cs_new_nopar:Npn and \cs_new_eq:NN *etc.* to make sure that the argument sequence is not already in use. If it is, an error is signalled. It checks if $\langle csname \rangle$ is undefined or \scan_stop:. Otherwise an error message is issued. We have to make sure we don't put the argument into the conditional processing since it may be an \if... type function!

__chk_if_free_cs:c

```

1741 \cs_set_protected:Npn \__chk_if_free_cs:N #1
1742 {
1743   \cs_if_free:NF #1
1744   {
1745     \_msg_kernel_error:nxxx { kernel } { command-already-defined }
1746     { \token_to_str:N #1 } { \token_to_meaning:N #1 }
1747   }
1748 }
1749 \*package
1750 \tex_ifodd:D \l@expl@log@functions@bool
1751 \cs_set_protected:Npn \__chk_if_free_cs:N #1
1752 {
1753   \cs_if_free:NF #1
1754   {
1755     \_msg_kernel_error:nxxx { kernel } { command-already-defined }
1756     { \token_to_str:N #1 } { \token_to_meaning:N #1 }
1757   }
1758   \__chk_log:x { Defining~\token_to_str:N #1~ \msg_line_context: }
1759 }
1760 \fi:
1761 \*package
1762 \cs_set_protected:Npn \__chk_if_free_cs:c
1763 { \exp_args:Nc \__chk_if_free_cs:N }

```

(End definition for __chk_if_free_cs:N.)

`__chk_if_exist_var:N` Create the checking function for variable definitions when the option is set.

```

1764 \*package>
1765 \tex_ifodd:D \l@expl@check@declarations@bool
1766 \cs_set_protected:Npn \__chk_if_exist_var:N #1
1767 {
1768   \cs_if_exist:NF #1
1769   {
1770     \__msg_kernel_error:nxx { check } { non-declared-variable }
1771     { \token_to_str:N #1 }
1772   }
1773 }
1774 \fi:
1775 \</package>

```

(End definition for `__chk_if_exist_var:N`.)

`__chk_if_exist_cs:N` This function issues an error message when the control sequence in its argument does
`__chk_if_exist_cs:c` not exist.

```

1776 \cs_set_protected:Npn \__chk_if_exist_cs:N #1
1777 {
1778   \cs_if_exist:NF #1
1779   {
1780     \__msg_kernel_error:nxx { kernel } { command-not-defined }
1781     { \token_to_str:N #1 }
1782   }
1783 }
1784 \cs_set_protected:Npn \__chk_if_exist_cs:c
1785 { \exp_args:Nc \__chk_if_exist_cs:N }

```

(End definition for `__chk_if_exist_cs:N`.)

3.10 More new definitions

`\cs_new_nopar:Npn` Function which check that the control sequence is free before defining it.

```

\cs_new_nopar:Npx 1786 \cs_set:Npn \__cs_tmp:w #1#2
\cs_new:Npn        1787 {
\cs_new:Npx        1788   \cs_set_protected:Npn #1 ##1
\cs_new_protected_nopar:Npn 1789   {
\cs_new_protected_nopar:Npx 1790     \__chk_if_free_cs:N ##1
\cs_new_protected:Npn      1791     #2 ##1
\cs_new_protected:Npx      1792   }
\__cs_tmp:w          1793 }
\__cs_tmp:w \cs_new_nopar:Npn      1794   \cs_gset_nopar:Npn
\__cs_tmp:w \cs_new_nopar:Npx      1795   \cs_gset_nopar:Npx
\__cs_tmp:w \cs_new:Npn            1796   \cs_gset:Npn
\__cs_tmp:w \cs_new:Npx            1797   \cs_gset:Npx
\__cs_tmp:w \cs_new_protected_nopar:Npn 1798   \cs_gset_protected_nopar:Npn
\__cs_tmp:w \cs_new_protected_nopar:Npx 1799   \cs_gset_protected_nopar:Npx
\__cs_tmp:w \cs_new_protected:Npn    1800   \cs_gset_protected:Npn
\__cs_tmp:w \cs_new_protected:Npx    1801   \cs_gset_protected:Npx

```

(End definition for `\cs_new_nopar:Npn` and others. These functions are documented on page 11.)

`\cs_set_nopar:cpn` Like `\cs_set_nopar:Npn` and `\cs_new_nopar:Npn`, except that the first argument consists of the sequence of characters that should be used to form the name of the desired control sequence (the `c` stands for `csname` argument, see the expansion module). Global versions are also provided.

`\cs_set_nopar:cpn` $\langle string \rangle \langle rep-text \rangle$ will turn $\langle string \rangle$ into a `csname` and then assign $\langle rep-text \rangle$ to it by using `\cs_set_nopar:Npn`. This means that there might be a parameter string between the two arguments.

```

1802 \cs_set:Npn \__cs_tmp:w #1#2
1803   { \cs_new_protected_nopar:Npn #1 { \exp_args:Nc #2 } }
1804 \__cs_tmp:w \cs_set_nopar:cpn \cs_set_nopar:Npn
1805 \__cs_tmp:w \cs_set_nopar:cpx \cs_set_nopar:Npx
1806 \__cs_tmp:w \cs_gset_nopar:cpn \cs_gset_nopar:Npn
1807 \__cs_tmp:w \cs_gset_nopar:cpx \cs_gset_nopar:Npx
1808 \__cs_tmp:w \cs_new_nopar:cpn \cs_new_nopar:Npn
1809 \__cs_tmp:w \cs_new_nopar:cpx \cs_new_nopar:Npx

```

(End definition for `\cs_set_nopar:cpn` and others. These functions are documented on page 11.)

`\cs_set:cpn` Variants of the `\cs_set:Npn` versions which make a `csname` out of the first arguments.
`\cs_set:cpx` We may also do this globally.

```

1810 \__cs_tmp:w \cs_set:cpn \cs_set:Npn
1811 \__cs_tmp:w \cs_set:cpx \cs_set:Npx
1812 \__cs_tmp:w \cs_gset:cpn \cs_gset:Npn
1813 \__cs_tmp:w \cs_gset:cpx \cs_gset:Npx
1814 \__cs_tmp:w \cs_new:cpn \cs_new:Npn
1815 \__cs_tmp:w \cs_new:cpx \cs_new:Npx

```

(End definition for `\cs_set:cpn` and others. These functions are documented on page 11.)

`\cs_set_protected_nopar:cpn` Variants of the `\cs_set_protected_nopar:Npn` versions which make a `csname` out of the first arguments. We may also do this globally.

```

1816 \__cs_tmp:w \cs_set_protected_nopar:cpn \cs_set_protected_nopar:Npn
1817 \__cs_tmp:w \cs_set_protected_nopar:cpx \cs_set_protected_nopar:Npx
1818 \__cs_tmp:w \cs_gset_protected_nopar:cpn \cs_gset_protected_nopar:Npn
1819 \__cs_tmp:w \cs_gset_protected_nopar:cpx \cs_gset_protected_nopar:Npx
1820 \__cs_tmp:w \cs_new_protected_nopar:cpn \cs_new_protected_nopar:Npn
1821 \__cs_tmp:w \cs_new_protected_nopar:cpx \cs_new_protected_nopar:Npx

```

(End definition for `\cs_set_protected_nopar:cpn` and others. These functions are documented on page 12.)

`\cs_set_protected:cpn` Variants of the `\cs_set_protected:Npn` versions which make a `csname` out of the first arguments. We may also do this globally.

```

1822 \__cs_tmp:w \cs_set_protected:cpn \cs_set_protected:Npn
1823 \__cs_tmp:w \cs_set_protected:cpx \cs_set_protected:Npx
1824 \__cs_tmp:w \cs_gset_protected:cpn \cs_gset_protected:Npn
1825 \__cs_tmp:w \cs_gset_protected:cpx \cs_gset_protected:Npx
1826 \__cs_tmp:w \cs_new_protected:cpn \cs_new_protected:Npn
1827 \__cs_tmp:w \cs_new_protected:cpx \cs_new_protected:Npx

```

(End definition for `\cs_set_protected:cpn` and others. These functions are documented on page 11.)

3.11 Copying definitions

`\cs_set_eq:NN` These macros allow us to copy the definition of a control sequence to another control sequence.

`\cs_set_eq:cN` The = sign allows us to define funny char tokens like = itself or `_` with this function.

`\cs_set_eq:Nc` For the definition of `\c_space_char{~}` to work we need the ~ after the =.

`\cs_set_eq:cc` `\cs_set_eq:NN` is long to avoid problems with a literal argument of `\par`. While

`\cs_gset_eq:NN` `\cs_new_eq:NN` will probably never be correct with a first argument of `\par`, define it

`\cs_gset_eq:cN` long in order to throw an “already defined” error rather than “runaway argument”.

`\cs_gset_eq:Nc`

`\cs_gset_eq:cc`

```

1828 \cs_new_protected:Npn \cs_set_eq:NN #1 { \tex_let:D #1 =~ }
1829 \cs_new_protected:Npn \cs_set_eq:cN { \exp_args:Nc \cs_set_eq:NN }
1830 \cs_new_protected:Npn \cs_set_eq:Nc { \exp_args:NNc \cs_set_eq:NN }
1831 \cs_new_protected:Npn \cs_set_eq:cc { \exp_args:Ncc \cs_set_eq:NN }
1832 \cs_new_protected:Npn \cs_gset_eq:NN { \tex_global:D \cs_set_eq:NN }
1833 \cs_new_protected:Npn \cs_gset_eq:Nc { \exp_args:NNc \cs_gset_eq:NN }
1834 \cs_new_protected:Npn \cs_gset_eq:cN { \exp_args:Nc \cs_gset_eq:NN }
1835 \cs_new_protected:Npn \cs_gset_eq:cc { \exp_args:Ncc \cs_gset_eq:NN }
1836 \cs_new_protected:Npn \cs_new_eq:NN #1
1837 {
1838   \__chk_if_free_cs:N #1
1839   \tex_global:D \cs_set_eq:NN #1
1840 }
1841 \cs_new_protected:Npn \cs_new_eq:cN { \exp_args:Nc \cs_new_eq:NN }
1842 \cs_new_protected:Npn \cs_new_eq:Nc { \exp_args:NNc \cs_new_eq:NN }
1843 \cs_new_protected:Npn \cs_new_eq:cc { \exp_args:Ncc \cs_new_eq:NN }

```

(End definition for `\cs_set_eq:NN`, `\cs_gset_eq:NN`, and `\cs_new_eq:NN`. These functions are documented on page 15.)

3.12 Undefined functions

`\cs_undefine:N` The following function is used to free the main memory from the definition of some

`\cs_undefine:c` function that isn’t in use any longer. The c variant is careful not to add the control sequence to the hash table if it isn’t there yet, and it also avoids nesting \TeX conditionals in case #1 is unbalanced in this matter.

```

1844 \cs_new_protected:Npn \cs_undefine:N #1
1845 { \cs_gset_eq:NN #1 \tex_undefined:D }
1846 \cs_new_protected:Npn \cs_undefine:c #1
1847 {
1848   \if_cs_exist:w #1 \cs_end:
1849     \exp_after:wN \use:n
1850   \else:
1851     \exp_after:wN \use_none:n
1852   \fi:
1853   { \cs_gset_eq:cN {#1} \tex_undefined:D }
1854 }

```

(End definition for `\cs_undefine:N`. This function is documented on page 15.)

3.13 Generating parameter text from argument count

`_cs_parm_from_arg_count:nnF` \LaTeX 3 provides shorthands to define control sequences and conditionals with a simple

`_cs_parm_from_arg_count_test:nnF` parameter text, derived directly from the signature, or more generally from knowing the

number of arguments, between 0 and 9. This function expands to its first argument, untouched, followed by a brace group containing the parameter text `{#1...#n}`, where n is the result of evaluating the second argument (as described in `\int_eval:n`). If the second argument gives a result outside the range $[0, 9]$, the third argument is returned instead, normally an error message. Some of the functions use here are not defined yet, but will be defined before this function is called.

```

1855 \cs_set_protected:Npn \__cs_parm_from_arg_count:nnF #1#2
1856 {
1857   \exp_args:Nx \__cs_parm_from_arg_count_test:nnF
1858   {
1859     \exp_after:wN \exp_not:n
1860     \if_case:w \__int_eval:w #2 \__int_eval_end:
1861       { }
1862       \or: { ##1 }
1863       \or: { ##1##2 }
1864       \or: { ##1##2##3 }
1865       \or: { ##1##2##3##4 }
1866       \or: { ##1##2##3##4##5 }
1867       \or: { ##1##2##3##4##5##6 }
1868       \or: { ##1##2##3##4##5##6##7 }
1869       \or: { ##1##2##3##4##5##6##7##8 }
1870       \or: { ##1##2##3##4##5##6##7##8##9 }
1871       \else: { \c_false_bool }
1872     \fi:
1873   }
1874   {#1}
1875 }
1876 \cs_set_protected:Npn \__cs_parm_from_arg_count_test:nnF #1#2
1877 {
1878   \if_meaning:w \c_false_bool #1
1879   \exp_after:wN \use_ii:nn
1880   \else:
1881     \exp_after:wN \use_i:nn
1882   \fi:
1883   { #2 {#1} }
1884 }

```

(End definition for `__cs_parm_from_arg_count:nnF` and `__cs_parm_from_arg_count_test:nnF`.)

3.14 Defining functions from a given number of arguments

`__cs_count_signature:N` Counting the number of tokens in the signature, *i.e.*, the number of arguments the function should take. Since this is not used in any time-critical function, we simply use `\tl_count:n` if there is a signature, otherwise `-1` arguments to signal an error. We need a variant form right away.

```

1885 \cs_new:Npn \__cs_count_signature:N #1
1886 { \int_eval:n { \__cs_split_function:NN #1 \__cs_count_signature:nnN } }
1887 \cs_new:Npn \__cs_count_signature:nnN #1#2#3
1888 {
1889   \if_meaning:w \c_true_bool #3
1890     \tl_count:n {#2}
1891   \else:
1892     -1

```

```

1893     \fi:
1894   }
1895   \cs_new:Npn \__cs_count_signature:c
1896     { \exp_args:Nc \__cs_count_signature:N }

```

(End definition for `__cs_count_signature:N` and `__cs_count_signature:nnN`.)

```

\cs_generate_from_arg_count:NNnn
\cs_generate_from_arg_count:cNnn
\cs_generate_from_arg_count:Ncnn

```

We provide a constructor function for defining functions with a given number of arguments. For this we need to choose the correct parameter text and then use that when defining. Since TeX supports from zero to nine arguments, we use a simple switch to choose the correct parameter text, ensuring the result is returned after finishing the conditional. If it is not between zero and nine, we throw an error.

1: function to define, 2: with what to define it, 3: the number of args it requires and 4: the replacement text

```

1897 \cs_new_protected:Npn \cs_generate_from_arg_count:NNnn #1#2#3#4
1898 {
1899   \__cs_parm_from_arg_count:nnF { \use:nnn #2 #1 } {#3}
1900   {
1901     \_msg_kernel_error:nnxx { kernel } { bad-number-of-arguments }
1902     { \token_to_str:N #1 } { \int_eval:n {#3} }
1903     \use_none:n
1904   }
1905   {#4}
1906 }

```

A variant form we need right away, plus one which is used elsewhere but which is most logically created here.

```

1907 \cs_new_protected:Npn \cs_generate_from_arg_count:cNnn
1908   { \exp_args:Nc \cs_generate_from_arg_count:NNnn }
1909 \cs_new_protected:Npn \cs_generate_from_arg_count:Ncnn
1910   { \exp_args:NNc \cs_generate_from_arg_count:NNnn }

```

(End definition for `\cs_generate_from_arg_count:NNnn`. This function is documented on page 14.)

3.15 Using the signature to define functions

We can now combine some of the tools we have to provide a simple interface for defining functions, where the number of arguments is read from the signature. For instance, `\cs_set:Nn \foo_bar:nn {#1,#2}`.

```

\cs_set:Nn
\cs_set:Nx

```

```

\cs_set_nopar:Nn
\cs_set_nopar:Nx

```

```

\cs_set_protected:Nn
\cs_set_protected:Nx

```

```

\cs_set_protected_nopar:Nn
\cs_set_protected_nopar:Nx

```

```

\cs_gset:Nn
\cs_gset:Nx

```

```

\cs_gset_nopar:Nn
\cs_gset_nopar:Nx

```

```

\cs_gset_protected:Nn
\cs_gset_protected:Nx

```

```

\cs_gset_protected_nopar:Nn
\cs_gset_protected_nopar:Nx

```

```

\cs_new:Nn
\cs_new:Nx

```

```

\cs_new_nopar:Nn
\cs_new_nopar:Nx

```

```

\cs_new_protected:Nn
\cs_new_protected:Nx

```

```

\cs_new_protected_nopar:Nn

```

We want to define `\cs_set:Nn` as

```

\cs_set_protected:Npn \cs_set:Nn #1#2
{
  \cs_generate_from_arg_count:NNnn #1 \cs_set:Npn
  { \__cs_count_signature:N #1 } {#2}
}

```

In short, to define `\cs_set:Nn` we need just use `\cs_set:Npn`, everything else is the same for each variant. Therefore, we can make it simpler by temporarily defining a function to do this for us.

```

1911 \cs_set:Npn \__cs_tmp:w #1#2#3
1912 {
1913   \cs_new_protected:cpx { cs_ #1 : #2 }

```

```

1914     {
1915         \exp_not:N \__cs_generate_from_signature:NNn
1916         \exp_after:wN \exp_not:N \cs:w cs_ #1 : #3 \cs_end:
1917     }
1918 }
1919 \cs_new_protected:Npn \__cs_generate_from_signature:NNn #1#2
1920 {
1921     \__cs_split_function:NN #2 \__cs_generate_from_signature:nnNNNn
1922     #1 #2
1923 }
1924 \cs_new_protected:Npn \__cs_generate_from_signature:nnNNNn #1#2#3#4#5#6
1925 {
1926     \bool_if:NTF #3
1927     {
1928         \str_if_eq_x:nnF { }
1929         { \tl_map_function:nN {#2} \__cs_generate_from_signature:n }
1930         {
1931             \__msg_kernel_error:nnx { kernel } { non-base-function }
1932             { \token_to_str:N #5 }
1933         }
1934         \cs_generate_from_arg_count:NNnn
1935         #5 #4 { \tl_count:n {#2} } {#6}
1936     }
1937     {
1938         \__msg_kernel_error:nnx { kernel } { missing-colon }
1939         { \token_to_str:N #5 }
1940     }
1941 }
1942 \cs_new:Npn \__cs_generate_from_signature:n #1
1943 {
1944     \if:w n #1 \else: \if:w N #1 \else:
1945     \if:w T #1 \else: \if:w F #1 \else: #1 \fi: \fi: \fi: \fi:
1946 }

```

Then we define the 24 variants beginning with N.

```

1947 \__cs_tmp:w { set } { Nn } { Npn }
1948 \__cs_tmp:w { set } { Nx } { Npx }
1949 \__cs_tmp:w { set_nopar } { Nn } { Npn }
1950 \__cs_tmp:w { set_nopar } { Nx } { Npx }
1951 \__cs_tmp:w { set_protected } { Nn } { Npn }
1952 \__cs_tmp:w { set_protected } { Nx } { Npx }
1953 \__cs_tmp:w { set_protected_nopar } { Nn } { Npn }
1954 \__cs_tmp:w { set_protected_nopar } { Nx } { Npx }
1955 \__cs_tmp:w { gset } { Nn } { Npn }
1956 \__cs_tmp:w { gset } { Nx } { Npx }
1957 \__cs_tmp:w { gset_nopar } { Nn } { Npn }
1958 \__cs_tmp:w { gset_nopar } { Nx } { Npx }
1959 \__cs_tmp:w { gset_protected } { Nn } { Npn }
1960 \__cs_tmp:w { gset_protected } { Nx } { Npx }
1961 \__cs_tmp:w { gset_protected_nopar } { Nn } { Npn }
1962 \__cs_tmp:w { gset_protected_nopar } { Nx } { Npx }
1963 \__cs_tmp:w { new } { Nn } { Npn }
1964 \__cs_tmp:w { new } { Nx } { Npx }
1965 \__cs_tmp:w { new_nopar } { Nn } { Npn }
1966 \__cs_tmp:w { new_nopar } { Nx } { Npx }

```

```

1967 \__cs_tmp:w { new_protected } { Nn } { Npn }
1968 \__cs_tmp:w { new_protected } { Nx } { Npx }
1969 \__cs_tmp:w { new_protected_nopar } { Nn } { Npn }
1970 \__cs_tmp:w { new_protected_nopar } { Nx } { Npx }

```

(End definition for \cs_set:Nn and others. These functions are documented on page 13.)

```

\cs_set:cn The 24 c variants simply use \exp_args:Nc.
\cs_set:cx
\cs_set_nopar:cn
\cs_set_nopar:cx
\cs_set_protected:cn
\cs_set_protected:cx
\cs_set_protected_nopar:cn
\cs_set_protected_nopar:cx
\cs_gset:cn
\cs_gset:cx
\cs_gset_nopar:cn
\cs_gset_nopar:cx
\cs_gset_protected:cn
\cs_gset_protected:cx
\cs_gset_protected_nopar:cn
\cs_gset_protected_nopar:cx
\cs_new:cn
\cs_new:cx
\cs_new_nopar:cn
\cs_new_nopar:cx
\cs_new_protected:cn
\cs_new_protected:cx
\cs_new_protected_nopar:cn
\cs_new_protected_nopar:cx
1971 \cs_set:Npn \__cs_tmp:w #1#2
1972 {
1973   \cs_new_protected:cpx { cs_ #1 : c #2 }
1974   {
1975     \exp_not:N \exp_args:Nc
1976     \exp_after:wN \exp_not:N \cs:w cs_ #1 : N #2 \cs_end:
1977   }
1978 }
1979 \__cs_tmp:w { set } { n }
1980 \__cs_tmp:w { set } { x }
1981 \__cs_tmp:w { set_nopar } { n }
1982 \__cs_tmp:w { set_nopar } { x }
1983 \__cs_tmp:w { set_protected } { n }
1984 \__cs_tmp:w { set_protected } { x }
1985 \__cs_tmp:w { set_protected_nopar } { n }
1986 \__cs_tmp:w { set_protected_nopar } { x }
1987 \__cs_tmp:w { gset } { n }
1988 \__cs_tmp:w { gset } { x }
1989 \__cs_tmp:w { gset_nopar } { n }
1990 \__cs_tmp:w { gset_nopar } { x }
1991 \__cs_tmp:w { gset_protected } { n }
1992 \__cs_tmp:w { gset_protected } { x }
1993 \__cs_tmp:w { gset_protected_nopar } { n }
1994 \__cs_tmp:w { gset_protected_nopar } { x }
1995 \__cs_tmp:w { new } { n }
1996 \__cs_tmp:w { new } { x }
1997 \__cs_tmp:w { new_nopar } { n }
1998 \__cs_tmp:w { new_nopar } { x }
1999 \__cs_tmp:w { new_protected } { n }
2000 \__cs_tmp:w { new_protected } { x }
2001 \__cs_tmp:w { new_protected_nopar } { n }
2002 \__cs_tmp:w { new_protected_nopar } { x }

```

(End definition for \cs_set:cn and others. These functions are documented on page 13.)

3.16 Checking control sequence equality

```

\cs_if_eq_p:NN Check if two control sequences are identical.
\cs_if_eq_p:cN
\cs_if_eq_p:Nc
\cs_if_eq_p:cc
\cs_if_eq:NNTF
\cs_if_eq:cNTF
\cs_if_eq:NcTF
\cs_if_eq:ccTF
2003 \prg_new_conditional:Npnn \cs_if_eq:NN #1#2 { p , T , F , TF }
2004 {
2005   \if_meaning:w #1#2
2006   \prg_return_true: \else: \prg_return_false: \fi:
2007 }
2008 \cs_new:Npn \cs_if_eq_p:cN { \exp_args:Nc \cs_if_eq_p:NN }
2009 \cs_new:Npn \cs_if_eq:cNTF { \exp_args:Nc \cs_if_eq:NNTF }
2010 \cs_new:Npn \cs_if_eq:cNT { \exp_args:Nc \cs_if_eq:NNT }

```

```

2011 \cs_new:Npn \cs_if_eq:cNF { \exp_args:Nc \cs_if_eq:NNF }
2012 \cs_new:Npn \cs_if_eq_p:Nc { \exp_args:NNc \cs_if_eq_p:NN }
2013 \cs_new:Npn \cs_if_eq:NcTF { \exp_args:NNc \cs_if_eq:NNTF }
2014 \cs_new:Npn \cs_if_eq:NcT { \exp_args:NNc \cs_if_eq:NNT }
2015 \cs_new:Npn \cs_if_eq:NcF { \exp_args:NNc \cs_if_eq:NNF }
2016 \cs_new:Npn \cs_if_eq_p:cc { \exp_args:Ncc \cs_if_eq_p:NN }
2017 \cs_new:Npn \cs_if_eq:ccTF { \exp_args:Ncc \cs_if_eq:NNTF }
2018 \cs_new:Npn \cs_if_eq:ccT { \exp_args:Ncc \cs_if_eq:NNT }
2019 \cs_new:Npn \cs_if_eq:ccF { \exp_args:Ncc \cs_if_eq:NNF }

```

(End definition for `\cs_if_eq:NNTF`. This function is documented on page 20.)

3.17 Diagnostic functions

`__kernel_register_show:N` Simply using the `\show` primitive does not allow for line-wrapping, so instead use `__-msg_show_variable:NNNnn` (defined in `l3msg`). This checks that the variable exists (using `\cs_if_exist:NTF`), then displays the third argument, namely `>~⟨variable⟩=⟨value⟩`. We expand the value before-hand as otherwise some integers (such as `\currentgrouplevel` or `\currentgrouptype`) altered by the line-wrapping code would show wrong values.

```

2020 \cs_new_protected:Npn \__kernel_register_show:N #1
2021 { \exp_args:No \__kernel_register_show_aux:nN { \tex_the:D #1 } #1 }
2022 \cs_new_protected:Npn \__kernel_register_show_aux:nN #1#2
2023 {
2024   \__msg_show_variable:NNNnn #2 \cs_if_exist:NTF ? { }
2025   { > ~ \token_to_str:N #2 = #1 }
2026 }
2027 \cs_new_protected:Npn \__kernel_register_show:c
2028 { \exp_args:Nc \__kernel_register_show:N }

```

(End definition for `__kernel_register_show:N` and `__kernel_register_show_aux:n`.)

`__kernel_register_log:N` Redirect the output of `__kernel_register_show:N` to the log.

```

\__kernel_register_log:c
2029 \cs_new_protected:Npn \__kernel_register_log:N
2030 { \__msg_log_next: \__kernel_register_show:N }
2031 \cs_new_protected:Npn \__kernel_register_log:c
2032 { \exp_args:Nc \__kernel_register_log:N }

```

(End definition for `__kernel_register_log:N`.)

`\cs_show:N` Some control sequences have a very long name or meaning. Thus, simply using TeX's primitive `\show` could lead to overlong lines. The output of this primitive is mimicked to some extent, then the re-built string is given to `\iow_wrap:nnnN` for line-wrapping. We must expand the meaning before passing it to the wrapping code as otherwise we would wrongly see the definitions that are in place there. To get correct escape characters, set the `\escapechar` in a group; this also localizes the assignment performed by `x`-expansion. The `\cs_show:c` command also converts its argument to a control sequence within a group to avoid showing `\relax` for undefined control sequences.

```

2033 \cs_new_protected:Npn \cs_show:N #1
2034 {
2035   \group_begin:
2036   \int_set:Nn \tex_escapechar:D { '\ }
2037   \exp_args:NNx
2038   \group_end:

```

```

2039     \__msg_show_wrap:n { > ~ \token_to_str:N #1 = \cs_meaning:N #1 }
2040   }
2041   \cs_new_protected:Npn \cs_show:c
2042     { \group_begin: \exp_args:NNc \group_end: \cs_show:N }

```

(End definition for `\cs_show:N`. This function is documented on page 16.)

`\cs_log:N` Use `\cs_show:N` or `\cs_show:c` after calling `__msg_log_next:` to redirect their output to the log file only. Note that `\cs_log:c` is not just a variant of `\cs_log:N` as the csname should be turned to a control sequence within a group (see `\cs_show:c`).

```

2043 \cs_new_protected:Npn \cs_log:N { \__msg_log_next: \cs_show:N }
2044 \cs_new_protected:Npn \cs_log:c { \__msg_log_next: \cs_show:c }

```

(End definition for `\cs_log:N`. This function is documented on page 16.)

3.18 Doing nothing functions

`\prg_do_nothing:` This does not fit anywhere else!

```

2045 \cs_new_nopar:Npn \prg_do_nothing: { }

```

(End definition for `\prg_do_nothing:.` This function is documented on page 9.)

3.19 Breaking out of mapping functions

`__prg_break_point:Nn` In inline mappings, the nesting level must be reset at the end of the mapping, even when the user decides to break out. This is done by putting the code that must be performed as an argument of `__prg_break_point:Nn`. The breaking functions are then defined to jump to that point and perform the argument of `__prg_break_point:Nn`, before the user's code (if any). There is a check that we close the correct loop, otherwise we continue breaking.

```

2046 \cs_new_eq:NN \__prg_break_point:Nn \use_ii:nn
2047 \cs_new:Npn \__prg_map_break:Nn #1#2#3 \__prg_break_point:Nn #4#5
2048   {
2049     #5
2050     \if_meaning:w #1 #4
2051       \exp_after:wN \use_iii:nnn
2052     \fi:
2053     \__prg_map_break:Nn #1 {#2}
2054   }

```

(End definition for `__prg_break_point:Nn` and `__prg_map_break:Nn`.)

`__prg_break_point:` Very simple analogues of `__prg_break_point:Nn` and `__prg_map_break:Nn`, for use in fast short-term recursions which are not mappings, do not need to support nesting, and in which nothing has to be done at the end of the loop.

```

2055 \cs_new_eq:NN \__prg_break_point: \prg_do_nothing:
2056 \cs_new:Npn \__prg_break: #1 \__prg_break_point: { }
2057 \cs_new:Npn \__prg_break:n #1#2 \__prg_break_point: {#1}

```

(End definition for `__prg_break_point:`, `__prg_break:`, and `__prg_break:n`.)

```

2058 </initex | package>

```

4 l3expan implementation

2059 $\langle *initex | package \rangle$

2060 $\langle @@=exp \rangle$

$\backslash exp_after:wN$ These are defined in l3basics.

$\backslash exp_not:N$

$\backslash exp_not:n$

(End definition for $\backslash exp_after:wN$, $\backslash exp_not:N$, and $\backslash exp_not:n$. These functions are documented on page 30.)

4.1 General expansion

In this section a general mechanism for defining functions to handle argument handling is defined. These general expansion functions are expandable unless x is used. (Any version of x is going to have to use one of the L^AT_EX3 names for $\backslash cs_set:Npx$ at some point, and so is never going to be expandable.)

The definition of expansion functions with this technique happens in section 4.3. In section 4.2 some common cases are coded by a more direct method for efficiency, typically using calls to $\backslash exp_after:wN$.

$\backslash l_exp_internal_tl$ This scratch token list variable is defined in l3basics, as it is needed “early”. This is just a reminder that is the case!

(End definition for $\backslash l_exp_internal_tl$.)

This code uses internal functions with names that start with $\backslash ::$ to perform the expansions. All macros are long as this turned out to be desirable since the tokens undergoing expansion may be arbitrary user input.

An argument manipulator $\backslash :: \langle Z \rangle$ always has signature $\#1 \backslash :: \#2 \#3$ where $\#1$ holds the remaining argument manipulations to be performed, $\backslash ::$ serves as an end marker for the list of manipulations, $\#2$ is the carried over result of the previous expansion steps and $\#3$ is the argument about to be processed. One exception to this rule is $\backslash :: p$, which has to grab an argument delimited by a left brace.

$\backslash _exp_arg_next:nnn$

$\backslash _exp_arg_next:Nnn$

$\#1$ is the result of an expansion step, $\#2$ is the remaining argument manipulations and $\#3$ is the current result of the expansion chain. This auxiliary function moves $\#1$ back after $\#3$ in the input stream and checks if any expansion is left to be done by calling $\#2$. In by far the most cases we will require to add a set of braces to the result of an argument manipulation so it is more effective to do it directly here. Actually, so far only the c of the final argument manipulation variants does not require a set of braces.

2061 $\backslash cs_new:Npn \backslash _exp_arg_next:nnn \#1 \#2 \#3 \{ \#2 \backslash :: \{ \#3 \{ \#1 \} \} \}$

2062 $\backslash cs_new:Npn \backslash _exp_arg_next:Nnn \#1 \#2 \#3 \{ \#2 \backslash :: \{ \#3 \#1 \} \}$

(End definition for $\backslash _exp_arg_next:nnn$ and $\backslash _exp_arg_next:Nnn$.)

$\backslash ::$ The end marker is just another name for the identity function.

2063 $\backslash cs_new:Npn \backslash :: \#1 \{ \#1 \}$

(End definition for $\backslash ::$.)

$\backslash :: n$ This function is used to skip an argument that doesn’t need to be expanded.

2064 $\backslash cs_new:Npn \backslash :: n \#1 \backslash :: \#2 \#3 \{ \#1 \backslash :: \{ \#2 \{ \#3 \} \} \}$

(End definition for $\backslash :: n$.)

\::N This function is used to skip an argument that consists of a single token and doesn't need to be expanded.

```
2065 \cs_new:Npn \::N #1 \::: #2#3 { #1 \::: {#2#3} }
```

(End definition for \::N.)

\::p This function is used to skip an argument that is delimited by a left brace and doesn't need to be expanded. It should not be wrapped in braces in the result.

```
2066 \cs_new:Npn \::p #1 \::: #2#3# { #1 \::: {#2#3} }
```

(End definition for \::p.)

\::c This function is used to skip an argument that is turned into a control sequence without expansion.

```
2067 \cs_new:Npn \::c #1 \::: #2#3
2068 { \exp_after:wN \__exp_arg_next:Nnn \cs:w #3 \cs_end: {#1} {#2} }
```

(End definition for \::c.)

\::o This function is used to expand an argument once.

```
2069 \cs_new:Npn \::o #1 \::: #2#3
2070 { \exp_after:wN \__exp_arg_next:nnn \exp_after:wN {#3} {#1} {#2} }
```

(End definition for \::o.)

\::f This function is used to expand a token list until the first unexpandable token is found. This is achieved through `\exp:w \exp_end_continue_f:w` that expands everything in its way following it. This scanning procedure is terminated once the expansion hits something non-expandable or a space. We introduce `\exp_stop_f:` to mark such an end of expansion marker. In the example shown earlier the scanning was stopped once \TeX had fully expanded `\cs_set_eq:Nc \aaa { b \l_tmpa_tl b }` into `\cs_set_eq:NN \aaa = \blurb` which then turned out to contain the non-expandable token `\cs_set_eq:NN`. Since the expansion of `\exp:w \exp_end_continue_f:w` is $\langle null \rangle$, we wind up with a fully expanded list, only \TeX has not tried to execute any of the non-expandable tokens. This is what differentiates this function from the `x` argument type.

```
2071 \cs_new:Npn \::f #1 \::: #2#3
2072 {
2073   \exp_after:wN \__exp_arg_next:nnn
2074   \exp_after:wN { \exp:w \exp_end_continue_f:w #3 }
2075   {#1} {#2}
2076 }
2077 \use:nn { \cs_new_eq:NN \exp_stop_f: } { ~ }
```

(End definition for \::f and \exp_stop_f:.)

\::x This function is used to expand an argument fully.

```
2078 \cs_new_protected:Npn \::x #1 \::: #2#3
2079 {
2080   \cs_set_nopar:Npx \l__exp_internal_tl { {#3} }
2081   \exp_after:wN \__exp_arg_next:nnn \l__exp_internal_tl {#1} {#2}
2082 }
```

(End definition for \::x.)

\::v These functions return the value of a register, i.e., one of `tl`, `clist`, `int`, `skip`, `dim` and `muskip`. The **V** version expects a single token whereas **v** like `c` creates a `cname` from its argument given in braces and then evaluates it as if it was a **V**. The `\exp:w` sets off an expansion similar to an `f` type expansion, which we will terminate using `\exp_end:`. The argument is returned in braces.

```

2083 \cs_new:Npn \::V #1 \::: #2#3
2084 {
2085     \exp_after:wN \__exp_arg_next:nnn
2086     \exp_after:wN { \exp:w \__exp_eval_register:N #3 }
2087     {#1} {#2}
2088 }
2089 \cs_new:Npn \::v # 1\::: #2#3
2090 {
2091     \exp_after:wN \__exp_arg_next:nnn
2092     \exp_after:wN { \exp:w \__exp_eval_register:c {#3} }
2093     {#1} {#2}
2094 }
```

(End definition for `\::v` and `\::V`.)

`__exp_eval_register:N`
`__exp_eval_register:c`
`__exp_eval_error_msg:w`

This function evaluates a register. Now a register might exist as one of two things: A parameter-less macro or a built-in `TeX` register such as `\count`. For the `TeX` registers we have to utilize a `\the` whereas for the macros we merely have to expand them once. The trick is to find out when to use `\the` and when not to. What we do here is try to find out whether the token will expand to something else when hit with `\exp_after:wN`. The technique is to compare the meaning of the register in question when it has been prefixed with `\exp_not:N` and the register itself. If it is a macro, the prefixed `\exp_not:N` will temporarily turn it into the primitive `\scan_stop:`.

```

2095 \cs_new:Npn \__exp_eval_register:N #1
2096 {
2097     \exp_after:wN \if_meaning:w \exp_not:N #1 #1
```

If the token was not a macro it may be a malformed variable from a `c` expansion in which case it is equal to the primitive `\scan_stop:`. In that case we throw an error. We could let `TeX` do it for us but that would result in the rather obscure

! You can't use '`\relax`' after `\the`.

which while quite true doesn't give many hints as to what actually went wrong. We provide something more sensible.

```

2098     \if_meaning:w \scan_stop: #1
2099     \__exp_eval_error_msg:w
2100     \fi:
```

The next bit requires some explanation. The function must be initiated by `\exp:w` and we want to terminate this expansion chain by inserting the `\exp_end:` token. However, we have to expand the register `#1` before we do that. If it is a `TeX` register, we need to execute the sequence `\exp_after:wN \exp_end: \tex_the:D #1` and if it is a macro we need to execute `\exp_after:wN \exp_end: #1`. We therefore issue the longer of the two sequences and if the register is a macro, we remove the `\tex_the:D`.

```

2101     \else:
2102     \exp_after:wN \use_i_ii:nnn
2103     \fi:
```

```

2104 \exp_after:wN \exp_end: \tex_the:D #1
2105 }
2106 \cs_new:Npn \__exp_eval_register:c #1
2107 { \exp_after:wN \__exp_eval_register:N \cs:w #1 \cs_end: }

```

Clean up nicely, then call the undefined control sequence. The result is an error message looking like this:

```

! Undefined control sequence.
<argument> \LaTeX3 error:
                               Erroneous variable used!
1.55 \tl_set:Nv \l_tmpa_tl {undefined_tl}

2108 \cs_new:Npn \__exp_eval_error_msg:w #1 \tex_the:D #2
2109 {
2110   \fi:
2111   \fi:
2112   \__msg_kernel_expandable_error:nnn { kernel } { bad-variable } {#2}
2113   \exp_end:
2114 }

```

(End definition for `__exp_eval_register:N` and `__exp_eval_error_msg:w`.)

4.2 Hand-tuned definitions

One of the most important features of these functions is that they are fully expandable and therefore allow to prefix them with `\tex_global:D` for example.

`\exp_args:No` Those lovely runs of expansion!

```

2115 \cs_new:Npn \exp_args:No #1#2 { \exp_after:wN #1 \exp_after:wN {#2} }
2116 \cs_new:Npn \exp_args:NNo #1#2#3
2117 { \exp_after:wN #1 \exp_after:wN #2 \exp_after:wN {#3} }
2118 \cs_new:Npn \exp_args:NNNo #1#2#3#4
2119 { \exp_after:wN #1 \exp_after:wN#2 \exp_after:wN #3 \exp_after:wN {#4} }

```

(End definition for `\exp_args:No`, `\exp_args:NNo`, and `\exp_args:NNNo`. These functions are documented on page 27.)

`\exp_args:Nc` In l3basics.

`\exp_args:cc` (End definition for `\exp_args:Nc` and `\exp_args:cc`. These functions are documented on page 27.)

`\exp_args:NNc` Here are the functions that turn their argument into csnames but are expandable.

```

2120 \cs_new:Npn \exp_args:NNc #1#2#3
2121 { \exp_after:wN #1 \exp_after:wN #2 \cs:w # 3 \cs_end: }
2122 \cs_new:Npn \exp_args:Ncc #1#2#3
2123 { \exp_after:wN #1 \cs:w #2 \exp_after:wN \cs_end: \cs:w #3 \cs_end: }
2124 \cs_new:Npn \exp_args:Nccc #1#2#3#4
2125 {
2126   \exp_after:wN #1
2127   \cs:w #2 \exp_after:wN \cs_end:
2128   \cs:w #3 \exp_after:wN \cs_end:
2129   \cs:w #4 \cs_end:
2130 }

```

(End definition for `\exp_args:NNc`, `\exp_args:Ncc`, and `\exp_args:Nccc`. These functions are documented on page 28.)

```

\exp_args:Nf
\exp_args:NV
\exp_args:Nv
2131 \cs_new:Npn \exp_args:Nf #1#2
2132 { \exp_after:wN #1 \exp_after:wN { \exp:w \exp_end_continue_f:w #2 } }
2133 \cs_new:Npn \exp_args:Nv #1#2
2134 {
2135   \exp_after:wN #1 \exp_after:wN
2136   { \exp:w \__exp_eval_register:c {#2} }
2137 }
2138 \cs_new:Npn \exp_args:NV #1#2
2139 {
2140   \exp_after:wN #1 \exp_after:wN
2141   { \exp:w \__exp_eval_register:N #2 }
2142 }

```

(End definition for `\exp_args:Nf`, `\exp_args:Nv`, and `\exp_args:Nv`. These functions are documented on page 27.)

`\exp_args:NNV` Some more hand-tuned function with three arguments. If we forced that an `o` argument always has braces, we could implement `\exp_args:Nco` with less tokens and only two arguments.

```

\exp_args:NNV
\exp_args:NNv
\exp_args:NNf
\exp_args:NVV
\exp_args:Ncf
\exp_args:Nco
2143 \cs_new:Npn \exp_args:NNf #1#2#3
2144 {
2145   \exp_after:wN #1
2146   \exp_after:wN #2
2147   \exp_after:wN { \exp:w \exp_end_continue_f:w #3 }
2148 }
2149 \cs_new:Npn \exp_args:NNv #1#2#3
2150 {
2151   \exp_after:wN #1
2152   \exp_after:wN #2
2153   \exp_after:wN { \exp:w \__exp_eval_register:c {#3} }
2154 }
2155 \cs_new:Npn \exp_args:NNV #1#2#3
2156 {
2157   \exp_after:wN #1
2158   \exp_after:wN #2
2159   \exp_after:wN { \exp:w \__exp_eval_register:N #3 }
2160 }
2161 \cs_new:Npn \exp_args:Nco #1#2#3
2162 {
2163   \exp_after:wN #1
2164   \cs:w #2 \exp_after:wN \cs_end:
2165   \exp_after:wN {#3}
2166 }
2167 \cs_new:Npn \exp_args:Ncf #1#2#3
2168 {
2169   \exp_after:wN #1
2170   \cs:w #2 \exp_after:wN \cs_end:
2171   \exp_after:wN { \exp:w \exp_end_continue_f:w #3 }
2172 }
2173 \cs_new:Npn \exp_args:NVV #1#2#3

```

```

2174 {
2175     \exp_after:wN #1
2176     \exp_after:wN { \exp:w \exp_after:wN
2177         \__exp_eval_register:N \exp_after:wN #2 \exp_after:wN }
2178     \exp_after:wN { \exp:w \__exp_eval_register:N #3 }
2179 }

```

(End definition for `\exp_args:NNV` and others. These functions are documented on page 28.)

`\exp_args:Ncco` A few more that we can hand-tune.

```

\exp_args:NcNc 2180 \cs_new:Npn \exp_args:NNNV #1#2#3#4
\exp_args:NcNo 2181 {
\exp_args:NNNV 2182     \exp_after:wN #1
2183     \exp_after:wN #2
2184     \exp_after:wN #3
2185     \exp_after:wN { \exp:w \__exp_eval_register:N #4 }
2186 }
2187 \cs_new:Npn \exp_args:NcNc #1#2#3#4
2188 {
2189     \exp_after:wN #1
2190     \cs:w #2 \exp_after:wN \cs_end:
2191     \exp_after:wN #3
2192     \cs:w #4 \cs_end:
2193 }
2194 \cs_new:Npn \exp_args:NcNo #1#2#3#4
2195 {
2196     \exp_after:wN #1
2197     \cs:w #2 \exp_after:wN \cs_end:
2198     \exp_after:wN #3
2199     \exp_after:wN {#4}
2200 }
2201 \cs_new:Npn \exp_args:Ncco #1#2#3#4
2202 {
2203     \exp_after:wN #1
2204     \cs:w #2 \exp_after:wN \cs_end:
2205     \cs:w #3 \exp_after:wN \cs_end:
2206     \exp_after:wN {#4}
2207 }

```

(End definition for `\exp_args:Ncco` and others. These functions are documented on page 28.)

4.3 Definitions with the automated technique

Some of these could be done more efficiently, but the complexity of coding then becomes an issue. Notice that the auto-generated functions are all not long: they don't actually take any arguments themselves.

```

\exp_args:Nx
2208 \cs_new_protected:Npn \exp_args:Nx { \::x \::: }

```

(End definition for `\exp_args:Nx`. This function is documented on page 27.)

`\exp_args:Nnc` Here are the actual function definitions, using the helper functions above.

```

\exp_args:Nfo 2209 \cs_new:Npn \exp_args:Nnc { \::n \::c \:: }
\exp_args:Nff 2210 \cs_new:Npn \exp_args:Nfo { \::f \::o \:: }
\exp_args:Nnf 2211 \cs_new:Npn \exp_args:Nff { \::f \::f \:: }
\exp_args:Nno 2212 \cs_new:Npn \exp_args:Nnf { \::n \::f \:: }
\exp_args:NnV 2213 \cs_new:Npn \exp_args:Nno { \::n \::o \:: }
\exp_args:Noo 2214 \cs_new:Npn \exp_args:NnV { \::n \::V \:: }
\exp_args:Nof 2215 \cs_new:Npn \exp_args:Noo { \::o \::o \:: }
\exp_args:Noc 2216 \cs_new:Npn \exp_args:Nof { \::o \::f \:: }
\exp_args:NNx 2217 \cs_new:Npn \exp_args:Noc { \::o \::c \:: }
\exp_args:Ncx 2218 \cs_new_protected:Npn \exp_args:NNx { \::N \::x \:: }
\exp_args:Nnx 2219 \cs_new_protected:Npn \exp_args:Ncx { \::c \::x \:: }
\exp_args:Nox 2220 \cs_new_protected:Npn \exp_args:Nnx { \::n \::x \:: }
\exp_args:Nxo 2221 \cs_new_protected:Npn \exp_args:Nox { \::o \::x \:: }
\exp_args:Nxx 2222 \cs_new_protected:Npn \exp_args:Nxo { \::x \::o \:: }
2223 \cs_new_protected:Npn \exp_args:Nxx { \::x \::x \:: }

```

(End definition for `\exp_args:Nnc` and others. These functions are documented on page 28.)

```

\exp_args:NNno 2224 \cs_new:Npn \exp_args:NNno { \::N \::n \::o \:: }
\exp_args:NNoo 2225 \cs_new:Npn \exp_args:NNoo { \::N \::o \::o \:: }
\exp_args:NNnc 2226 \cs_new:Npn \exp_args:NNnc { \::n \::n \::c \:: }
\exp_args:Nooo 2227 \cs_new:Npn \exp_args:NNno { \::n \::n \::o \:: }
\exp_args:NNNx 2228 \cs_new:Npn \exp_args:Nooo { \::o \::o \::o \:: }
\exp_args:NNnx 2229 \cs_new_protected:Npn \exp_args:NNNx { \::N \::N \::x \:: }
\exp_args:NNox 2230 \cs_new_protected:Npn \exp_args:NNnx { \::N \::n \::x \:: }
\exp_args:Nnnx 2231 \cs_new_protected:Npn \exp_args:NNox { \::N \::o \::x \:: }
\exp_args:Nnox 2232 \cs_new_protected:Npn \exp_args:Nnnx { \::n \::n \::x \:: }
\exp_args:Nccx 2233 \cs_new_protected:Npn \exp_args:Nnox { \::n \::o \::x \:: }
\exp_args:Ncnx 2234 \cs_new_protected:Npn \exp_args:Nccx { \::c \::c \::x \:: }
\exp_args:Noox 2235 \cs_new_protected:Npn \exp_args:Ncnx { \::c \::n \::x \:: }
2236 \cs_new_protected:Npn \exp_args:Noox { \::o \::o \::x \:: }

```

(End definition for `\exp_args:NNno` and others. These functions are documented on page 28.)

4.4 Last-unbraced versions

`__exp_arg_last_unbraced:nn` There are a few places where the last argument needs to be available unbraced. First some helper macros.

```

\::f_unbraced 2237 \cs_new:Npn \__exp_arg_last_unbraced:nn #1#2 { #2#1 }
\::o_unbraced 2238 \cs_new:Npn \::f_unbraced \:: #1#2
\::V_unbraced 2239 {
\::v_unbraced 2240 \exp_after:wN \__exp_arg_last_unbraced:nn
\::x_unbraced 2241 \exp_after:wN { \exp:w \exp_end_continue_f:w #2 } {#1}
2242 }
2243 \cs_new:Npn \::o_unbraced \:: #1#2
2244 { \exp_after:wN \__exp_arg_last_unbraced:nn \exp_after:wN {#2} {#1} }
2245 \cs_new:Npn \::V_unbraced \:: #1#2
2246 {
2247 \exp_after:wN \__exp_arg_last_unbraced:nn
2248 \exp_after:wN { \exp:w \__exp_eval_register:N #2 } {#1}
2249 }
2250 \cs_new:Npn \::v_unbraced \:: #1#2

```

```

2251 {
2252     \exp_after:wN \__exp_arg_last_unbraced:nn
2253     \exp_after:wN { \exp:w \__exp_eval_register:c {#2} } {#1}
2254 }
2255 \cs_new_protected:Npn \:::x_unbraced \::: #1#2
2256 {
2257     \cs_set_nopar:Npx \l__exp_internal_tl { \exp_not:n {#1} #2 }
2258     \l__exp_internal_tl
2259 }

```

(End definition for __exp_arg_last_unbraced:nn and others.)

`\exp_last_unbraced:NV`
`\exp_last_unbraced:Nv`
`\exp_last_unbraced:Nf`
`\exp_last_unbraced:No`
`\exp_last_unbraced:Nco`
`\exp_last_unbraced:NcV`
`\exp_last_unbraced:NNV`
`\exp_last_unbraced:NNo`
`\exp_last_unbraced:NNNV`
`\exp_last_unbraced:NNNo`
`\exp_last_unbraced:Nno`
`\exp_last_unbraced:Noo`
`\exp_last_unbraced:Nfo`
`\exp_last_unbraced:NnNo`
`\exp_last_unbraced:Nx`

Now the business end: most of these are hand-tuned for speed, but the general system is in place.

```

2260 \cs_new:Npn \exp_last_unbraced:NV #1#2
2261 { \exp_after:wN #1 \exp:w \__exp_eval_register:N #2 }
2262 \cs_new:Npn \exp_last_unbraced:Nv #1#2
2263 { \exp_after:wN #1 \exp:w \__exp_eval_register:c {#2} }
2264 \cs_new:Npn \exp_last_unbraced:No #1#2 { \exp_after:wN #1 #2 }
2265 \cs_new:Npn \exp_last_unbraced:Nf #1#2
2266 { \exp_after:wN #1 \exp:w \exp_end_continue_f:w #2 }
2267 \cs_new:Npn \exp_last_unbraced:Nco #1#2#3
2268 { \exp_after:wN #1 \cs:w #2 \exp_after:wN \cs_end: #3 }
2269 \cs_new:Npn \exp_last_unbraced:NcV #1#2#3
2270 {
2271     \exp_after:wN #1
2272     \cs:w #2 \exp_after:wN \cs_end:
2273     \exp:w \__exp_eval_register:N #3
2274 }
2275 \cs_new:Npn \exp_last_unbraced:NNV #1#2#3
2276 {
2277     \exp_after:wN #1
2278     \exp_after:wN #2
2279     \exp:w \__exp_eval_register:N #3
2280 }
2281 \cs_new:Npn \exp_last_unbraced:NNo #1#2#3
2282 { \exp_after:wN #1 \exp_after:wN #2 #3 }
2283 \cs_new:Npn \exp_last_unbraced:NNNV #1#2#3#4
2284 {
2285     \exp_after:wN #1
2286     \exp_after:wN #2
2287     \exp_after:wN #3
2288     \exp:w \__exp_eval_register:N #4
2289 }
2290 \cs_new:Npn \exp_last_unbraced:NNNo #1#2#3#4
2291 { \exp_after:wN #1 \exp_after:wN #2 \exp_after:wN #3 #4 }
2292 \cs_new:Npn \exp_last_unbraced:Nno { \:::n \:::o_unbraced \::: }
2293 \cs_new:Npn \exp_last_unbraced:Noo { \:::o \:::o_unbraced \::: }
2294 \cs_new:Npn \exp_last_unbraced:Nfo { \:::f \:::o_unbraced \::: }
2295 \cs_new:Npn \exp_last_unbraced:NnNo { \:::n \:::N \:::o_unbraced \::: }
2296 \cs_new_protected:Npn \exp_last_unbraced:Nx { \:::x_unbraced \::: }

```

(End definition for \exp_last_unbraced:NV and others. These functions are documented on page 29.)

`\exp_last_two_unbraced:Noo`
`__exp_last_two_unbraced:noN`

If #2 is a single token then this can be implemented as

```

\cs_new:Npn \exp_last_two_unbraced:Noo #1 #2 #3
{ \exp_after:wN \exp_after:wN \exp_after:wN #1 \exp_after:wN #2 #3 }

```

However, for robustness this is not suitable. Instead, a bit of a shuffle is used to ensure that #2 can be multiple tokens.

```

2297 \cs_new:Npn \exp_last_two_unbraced:Noo #1#2#3
2298 { \exp_after:wN \__exp_last_two_unbraced:noN \exp_after:wN {#3} {#2} #1 }
2299 \cs_new:Npn \__exp_last_two_unbraced:noN #1#2#3
2300 { \exp_after:wN #3 #2 #1 }

```

(End definition for `\exp_last_two_unbraced:Noo` and `__exp_last_two_unbraced:noN`. These functions are documented on page 29.)

4.5 Preventing expansion

```

\exp_not:o
\exp_not:c 2301 \cs_new:Npn \exp_not:o #1 { \etex_unexpanded:D \exp_after:wN {#1} }
\exp_not:f 2302 \cs_new:Npn \exp_not:c #1 { \exp_after:wN \exp_not:N \cs:w #1 \cs_end: }
\exp_not:V 2303 \cs_new:Npn \exp_not:f #1
\exp_not:v 2304 { \etex_unexpanded:D \exp_after:wN { \exp:w \exp_end_continue_f:w #1 } }
2305 \cs_new:Npn \exp_not:V #1
2306 {
2307   \etex_unexpanded:D \exp_after:wN
2308   { \exp:w \__exp_eval_register:N #1 }
2309 }
2310 \cs_new:Npn \exp_not:v #1
2311 {
2312   \etex_unexpanded:D \exp_after:wN
2313   { \exp:w \__exp_eval_register:c {#1} }
2314 }

```

(End definition for `\exp_not:o` and others. These functions are documented on page 31.)

4.6 Controlled expansion

```

\exp:w To trigger a sequence of “arbitrary” many expansions we need a method to invoke TEX’s
\exp_end: expansion mechanism in such a way that a) we are able to stop it in a controlled manner
\exp_end_continue_f:w and b) that the result of what triggered the expansion in the first place is null, i.e., that
\exp_end_continue_f:nw we do not get any unwanted side effects. There aren’t that many possibilities in TEX;
in fact the one explained below might well be the only one (as normally the result of
expansion is not null).
```

The trick here is to make use of the fact that `\tex_romannumeral:D` expands the tokens following it when looking for a number and that its expansion is null if that number turns out to be zero or negative. So we use that to start the expansion sequence.

```

2315 %\cs_new_eq:NN \exp:w \tex_romannumeral:D

```

So to stop the expansion sequence in a controlled way all we need to provide is a constant integer zero as part of expanded tokens. As this is an integer constant it will immediately stop `\tex_romannumeral:D`’s search for a number.

```

2316 %\int_const:Nn \exp_end: { 0 }

```


(Note that according to our specification all tokens we expand initiated by `\exp:w` are supposed to be expandable (as well as their replacement text in the expansion) so we will not encounter a “number” that actually result in a roman numeral being generated. Or if we do then the programmer made a mistake.)

If on the other hand we want to stop the initial expansion sequence but continue with an f-type expansion we provide the alphabetic constant `‘^^@` that also represents 0 but this time TeX’s syntax for a *<number>* will continue searching for an optional space (and it will continue expansion doing that) — see TeXbook page 269 for details.

```
2317 \tex_catcode:D ‘^^@=13
2318 \cs_new_protected:Npn \exp_end_continue_f:w {‘^^@}
```

If the above definition ever appears outside its proper context the active character `^^@` will be executed so we turn this into an error.⁶

```
2319 \cs_new:Npn ^^@{\expansionERROR}
2320 \cs_new:Npn \exp_end_continue_f:nw #1 { ‘^^@ #1 }
2321 \tex_catcode:D ‘^^@=15
```

(End definition for `\exp:w` and others. These functions are documented on page 31.)

4.7 Defining function variants

```
2322 <@@=cs>
```

```
\cs_generate_variant:Nn #1 : Base form of a function; e.g., \tl_set:Nn
#2 : One or more variant argument specifiers; e.g., {Nx,c,cx}
```

After making sure that the base form exists, test whether it is protected or not and define `__cs_tmp:w` as either `\cs_new:Npx` or `\cs_new_protected:Npx`, which is then used to define all the variants (except those involving x-expansion, always protected). Split up the original base function only once, to grab its name and signature. Then we wish to iterate through the comma list of variant argument specifiers, which we first convert to a string: the reason is explained later.

```
2323 \cs_new_protected:Npn \cs_generate_variant:Nn #1#2
2324 {
2325   \__chk_if_exist_cs:N #1
2326   \__cs_generate_variant:N #1
2327   \exp_after:wN \__cs_split_function:NN
2328   \exp_after:wN #1
2329   \exp_after:wN \__cs_generate_variant:nnNN
2330   \exp_after:wN #1
2331   \tl_to_str:n {#2} , \scan_stop: , \q_recursion_stop
2332 }
```

(End definition for `\cs_generate_variant:Nn`. This function is documented on page 25.)

```
\__cs_generate_variant:N
\__cs_generate_variant:ww
\__cs_generate_variant:wwNw
```

The goal here is to pick up protected parent functions. There are four cases: the parent function can be a primitive or a macro, and can be expandable or not. For non-expandable primitives, all variants should be protected; skipping the `\else:` branch is safe because all primitive TeX conditionals are expandable.

The other case where variants should be protected is when the parent function is a protected macro: then `protected` appears in the meaning before the first occurrence of `macro`. The `ww` auxiliary removes everything in the meaning string after the first `ma`. We

⁶Need to get a real error message.

use `ma` rather than the full `macro` because the meaning of the `\firstmark` primitive (and four others) can contain an arbitrary string after a leading `firstmark:`. Then, look for `pr` in the part we extracted: no need to look for anything longer: the only strings we can have are an empty string, `\long`, `\protected`, `\protected\long`, `\first`, `\top`, `\bot`, `\splittop`, or `\splitbot`, with `\` replaced by the appropriate escape character. If `pr` appears in the part before `ma`, the first `\q_mark` is taken as an argument of the `wwNw` auxiliary, and `#3` is `\cs_new_protected:Npx`, otherwise it is `\cs_new:Npx`.

```

2333 \cs_new_protected:Npx \__cs_generate_variant:N #1
2334 {
2335   \exp_not:N \exp_after:wN \exp_not:N \if_meaning:w
2336   \exp_not:N \exp_not:N #1 #1
2337   \cs_set_eq:NN \exp_not:N \__cs_tmp:w \cs_new_protected:Npx
2338   \exp_not:N \else:
2339   \exp_not:N \exp_after:wN \exp_not:N \__cs_generate_variant:ww
2340   \exp_not:N \token_to_meaning:N #1 \tl_to_str:n { ma }
2341   \exp_not:N \q_mark
2342   \exp_not:N \q_mark \cs_new_protected:Npx
2343   \tl_to_str:n { pr }
2344   \exp_not:N \q_mark \cs_new:Npx
2345   \exp_not:N \q_stop
2346   \exp_not:N \fi:
2347 }
2348 \use:x
2349 {
2350   \cs_new_protected:Npn \exp_not:N \__cs_generate_variant:ww
2351   ##1 \tl_to_str:n { ma } ##2 \exp_not:N \q_mark
2352 }
2353 { \__cs_generate_variant:wwNw #1 }
2354 \use:x
2355 {
2356   \cs_new_protected:Npn \exp_not:N \__cs_generate_variant:wwNw
2357   ##1 \tl_to_str:n { pr } ##2 \exp_not:N \q_mark
2358   ##3 ##4 \exp_not:N \q_stop
2359 }
2360 { \cs_set_eq:NN \__cs_tmp:w #3 }

```

(End definition for `__cs_generate_variant:N`, `__cs_generate_variant:ww`, and `__cs_generate_variant:wwNw`.)

`__cs_generate_variant:nnNN`

- `#1` : Base name.
- `#2` : Base signature.
- `#3` : Boolean.
- `#4` : Base function.

If the boolean is `\c_false_bool`, the base function has no colon and we abort with an error; otherwise, set off a loop through the desired variant forms. The original function is retained as `#4` for efficiency.

```

2361 \cs_new_protected:Npn \__cs_generate_variant:nnNN #1#2#3#4
2362 {
2363   \if_meaning:w \c_false_bool #3
2364   \__msg_kernel_error:nnx { kernel } { missing-colon }
2365   { \token_to_str:c {#1} }
2366   \exp_after:wN \use_none_delimit_by_q_recursion_stop:w
2367   \fi:

```

```

2368   \_cs_generate_variant:Nnnw #4 {#1}{#2}
2369 }

```

(End definition for `_cs_generate_variant:nnNN`.)

```

\_cs_generate_variant:Nnnw #1 : Base function.
#2 : Base name.
#3 : Base signature.
#4 : Beginning of variant signature.

```

First check whether to terminate the loop over variant forms. Then, for each variant form, construct a new function name using the original base name, the variant signature consisting of l letters and the last $k - l$ letters of the base signature (of length k). For example, for a base function `\prop_put:Nnn` which needs a `cV` variant form, we want the new signature to be `cVn`.

There are further subtleties:

- In `\cs_generate_variant:Nn \foo:nnTF {xxTF}`, it would be better to define `\foo:xxTF` using `\exp_args:Nxx`, rather than a hypothetical `\exp_args:NxxTF`. Thus, we wish to trim a common trailing part from the base signature and the variant signature.
- In `\cs_generate_variant:Nn \foo:on {ox}`, the function `\foo:ox` should be defined using `\exp_args:Nnx`, not `\exp_args:Nox`, to avoid double `o` expansion.
- Lastly, `\cs_generate_variant:Nn \foo:on {xn}` should trigger an error, because we do not have a means to replace `o`-expansion by `x`-expansion.

All this boils down to a few rules. Only `n` and `N`-type arguments can be replaced by `\cs_generate_variant:Nn`. Other argument types are allowed to be passed unchanged from the base form to the variant: in the process they are changed to `n` (except for two cases: `N` and `p`-type arguments). A common trailing part is ignored.

We compare the base and variant signatures one character at a time within `x`-expansion. The result is given to `_cs_generate_variant:wwNN` in the form `<processed variant signature> \q_mark <errors> \q_stop <base function> <new function>`. If all went well, `<errors>` is empty; otherwise, it is a kernel error message, followed by some clean-up code (`\use_none:nnnn`).

Note the space after `#3` and after the following brace group. Those are ignored by \TeX when fetching the last argument for `_cs_generate_variant_loop:nNwN`, but can be used as a delimiter for `_cs_generate_variant_loop_end:nwwwNNnn`.

```

2370 \cs_new_protected:Npn \_cs_generate_variant:Nnnw #1#2#3#4 ,
2371 {
2372   \if_meaning:w \scan_stop: #4
2373   \exp_after:wN \use_none_delimit_by_q_recursion_stop:w
2374   \fi:
2375   \use:x
2376   {
2377     \exp_not:N \_cs_generate_variant:wwNN
2378     \_cs_generate_variant_loop:nNwN { }
2379     #4
2380     \_cs_generate_variant_loop_end:nwwwNNnn
2381     \q_mark
2382     #3 ~
2383     { ~ { } \fi: \_cs_generate_variant_loop_long:wNNnn } ~

```

```

2384         { }
2385         \q_stop
2386         \exp_not:N #1 {#2} {#4}
2387     }
2388     \__cs_generate_variant:Nnnw #1 {#2} {#3}
2389 }

```

(End definition for `__cs_generate_variant:Nnnw`.)

```

\__cs_generate_variant_loop:nNwN #1 : Last few (consecutive) letters common between the base and variant (in fact, \__-
\__cs_generate_variant_loop_same:w   cs_generate_variant_same:N <letter> for each letter).
\__cs_generate_variant_loop_end:nwwwNNnn #2 : Next variant letter.
\__cs_generate_variant_loop_long:wNNnn #3 : Remainder of variant form.
\__cs_generate_variant_loop_invalid:NNwNNnn #4 : Next base letter.

```

The first argument is populated by `__cs_generate_variant_loop_same:w` when a variant letter and a base letter match. It is flushed into the input stream whenever the two letters are different: if the loop ends before, the argument is dropped, which means that trailing common letters are ignored.

The case where the two letters are different is only allowed with a base letter of `N` or `n`. Otherwise, call `__cs_generate_variant_loop_invalid:NNwNNnn` to remove the end of the loop, get arguments at the end of the loop, and place an appropriate error message as a second argument of `__cs_generate_variant:wwNN`. If the letters are distinct and the base letter is indeed `n` or `N`, leave in the input stream whatever argument was collected, and the next variant letter `#2`, then loop by calling `__cs_generate_variant_loop:nNwN`.

The loop can stop in three ways.

- If the end of the variant form is encountered first, `#2` is `__cs_generate_variant_loop_end:nwwwNNnn` (expanded by the conditional `\if:w`), which inserts some tokens to end the conditional; grabs the *<base name>* as `#7`, the *<variant signature>* `#8`, the *<next base letter>* `#1` and the part `#3` of the base signature that wasn't read yet; and combines those into the *<new function>* to be defined.
- If the end of the base form is encountered first, `#4` is `~{}\fi`: which ends the conditional (with an empty expansion), followed by `__cs_generate_variant_loop_long:wNNnn`, which places an error as the second argument of `__cs_generate_variant:wwNN`.
- The loop can be interrupted early if the requested expansion is unavailable, namely when the variant and base letters differ and the base is neither `n` nor `N`. Again, an error is placed as the second argument of `__cs_generate_variant:wwNN`.

Note that if the variant form has the same length as the base form, `#2` is as described in the first point, and `#4` as described in the second point above. The `__cs_generate_variant_loop_end:nwwwNNnn` breaking function takes the empty brace group in `#4` as its first argument: this empty brace group produces the correct signature for the full variant.

```

2390 \cs_new:Npn \__cs_generate_variant_loop:nNwN #1#2#3 \q_mark #4
2391 {
2392     \if:w #2 #4
2393         \exp_after:wN \__cs_generate_variant_loop_same:w
2394     \else:

```

```

2395     \if:w N #4 \else:
2396     \if:w n #4 \else:
2397         \__cs_generate_variant_loop_invalid:NNwNNnn #4#2
2398     \fi:
2399     \fi:
2400 \fi:
2401 #1
2402 \prg_do_nothing:
2403 #2
2404 \__cs_generate_variant_loop:nNwN { } #3 \q_mark
2405 }
2406 \cs_new:Npn \__cs_generate_variant_loop_same:w
2407     #1 \prg_do_nothing: #2#3#4
2408 {
2409     #3 { #1 \__cs_generate_variant_same:N #2 }
2410 }
2411 \cs_new:Npn \__cs_generate_variant_loop_end:nwwwNNnn
2412     #1#2 \q_mark #3 ~ #4 \q_stop #5#6#7#8
2413 {
2414     \scan_stop: \scan_stop: \fi:
2415     \exp_not:N \q_mark
2416     \exp_not:N \q_stop
2417     \exp_not:N #6
2418     \exp_not:c { #7 : #8 #1 #3 }
2419 }
2420 \cs_new:Npn \__cs_generate_variant_loop_long:wNNnn #1 \q_stop #2#3#4#5
2421 {
2422     \exp_not:n
2423     {
2424         \q_mark
2425         \__msg_kernel_error:nxxx { kernel } { variant-too-long }
2426         {#5} { \token_to_str:N #3 }
2427         \use_none:nnnn
2428         \q_stop
2429         #3
2430         #3
2431     }
2432 }
2433 \cs_new:Npn \__cs_generate_variant_loop_invalid:NNwNNnn
2434     #1#2 \fi: \fi: \fi: #3 \q_stop #4#5#6#7
2435 {
2436     \fi: \fi: \fi:
2437     \exp_not:n
2438     {
2439         \q_mark
2440         \__msg_kernel_error:nxxxx { kernel } { invalid-variant }
2441         {#7} { \token_to_str:N #5 } {#1} {#2}
2442         \use_none:nnnn
2443         \q_stop
2444         #5
2445         #5
2446     }
2447 }

```

(End definition for __cs_generate_variant_loop:nNwN and others.)

`__cs_generate_variant_same:N` When the base and variant letters are identical, don't do any expansion. For most argument types, we can use the `n`-type no-expansion, but the `N` and `p` types require a slightly different behaviour with respect to braces.

```

2448 \cs_new:Npn \__cs_generate_variant_same:N #1
2449 {
2450   \if:w N #1
2451     N
2452   \else:
2453     \if:w p #1
2454       p
2455     \else:
2456       n
2457     \fi:
2458   \fi:
2459 }

```

(End definition for `__cs_generate_variant_same:N`.)

`__cs_generate_variant:wwNN` If the variant form has already been defined, log its existence. Otherwise, make sure that the `\exp_args:N #3` form is defined, and if it contains `x`, change `__cs_tmp:w` locally to `\cs_new_protected:Npx`. Then define the variant by combining the `\exp_args:N #3` variant and the base function.

```

2460 \cs_new_protected:Npn \__cs_generate_variant:wwNN
2461   #1 \q_mark #2 \q_stop #3#4
2462 {
2463   #2
2464   \cs_if_free:NTF #4
2465   {
2466     \group_begin:
2467       \__cs_generate_internal_variant:n {#1}
2468       \__cs_tmp:w #4 { \exp_not:c { \exp_args:N #1 } \exp_not:N #3 }
2469     \group_end:
2470   }
2471   {
2472     \__chk_log:x
2473     {
2474       Variant~\token_to_str:N #4~%
2475       already~defined;~ not~ changing~ it~ \msg_line_context:
2476     }
2477   }
2478 }

```

(End definition for `__cs_generate_variant:wwNN`.)

`__cs_generate_internal_variant:n` Test if `\exp_args:N #1` is already defined and if not define it via the `\::` commands using the chars in `#1`. If `#1` contains an `x` (this is the place where having converted the original comma-list argument to a string is very important), the result should be protected, and the next variant to be defined using that internal variant should be protected.

```

2479 \cs_new_protected:Npx \__cs_generate_internal_variant:n #1
2480 {
2481   \exp_not:N \__cs_generate_internal_variant:wwNwnn
2482   #1 \exp_not:N \q_mark
2483   { \cs_set_eq:NN \exp_not:N \__cs_tmp:w \cs_new_protected:Npx }
2484   \cs_new_protected:cpx

```

```

2485     \token_to_str:N x \exp_not:N \q_mark
2486     { }
2487     \cs_new:cpx
2488     \exp_not:N \q_stop
2489     { \exp_args:N #1 }
2490     {
2491       \exp_not:N \__cs_generate_internal_variant_loop:n #1
2492       { : \exp_not:N \use_i:nn }
2493     }
2494   }
2495   \use:x
2496   {
2497     \cs_new_protected:Npn \exp_not:N \__cs_generate_internal_variant:wwnNwnn
2498     ##1 \token_to_str:N x ##2 \exp_not:N \q_mark
2499     ##3 ##4 ##5 \exp_not:N \q_stop ##6 ##7
2500   }
2501   {
2502     #3
2503     \cs_if_free:cT {#6} { #4 {#6} {#7} }
2504   }

```

This command grabs char by char outputting `\::#1` (not expanded further). We avoid tests by putting a trailing `: \use_i:nn`, which leaves `\cs_end:` and removes the looping macro. The colon is in fact also turned into `\:::` so that the required structure for `\exp_args:N...` commands is correctly terminated.

```

2505   \cs_new:Npn \__cs_generate_internal_variant_loop:n #1
2506   {
2507     \exp_after:wN \exp_not:N \cs:w :: #1 \cs_end:
2508     \__cs_generate_internal_variant_loop:n
2509   }

```

(End definition for `__cs_generate_internal_variant:n`, `__cs_generate_internal_variant:wwnw`, and `__cs_generate_internal_variant_loop:n`.)

```

2510 </initex | package>

```

5 l3tl implementation

```

2511 <*initex | package>
2512 <@@=tl>

```

A token list variable is a $\text{T}_{\text{E}}\text{X}$ macro that holds tokens. By using the $\varepsilon\text{-T}_{\text{E}}\text{X}$ primitive `\unexpanded` inside a $\text{T}_{\text{E}}\text{X}$ `\edef` it is possible to store any tokens, including `#`, in this way.

5.1 Functions

`\tl_new:N` Creating new token list variables is a case of checking for an existing definition and doing the definition.

```

\tl_new:c
2513   \cs_new_protected:Npn \tl_new:N #1
2514   {
2515     \__chk_if_free_cs:N #1
2516     \cs_gset_eq:NN #1 \c_empty_tl
2517   }
2518   \cs_generate_variant:Nn \tl_new:N { c }

```

(End definition for `\tl_new:N`. This function is documented on page 34.)

`\tl_const:Nn` Constants are also easy to generate.

```

\tl_const:Nx 2519 \cs_new_protected:Npn \tl_const:Nn #1#2
\tl_const:cn 2520 {
\tl_const:cx 2521   \__chk_if_free_cs:N #1
2522   \cs_gset_nopar:Npx #1 { \exp_not:n {#2} }
2523 }
2524 \cs_new_protected:Npn \tl_const:Nx #1#2
2525 {
2526   \__chk_if_free_cs:N #1
2527   \cs_gset_nopar:Npx #1 {#2}
2528 }
2529 \cs_generate_variant:Nn \tl_const:Nn { c }
2530 \cs_generate_variant:Nn \tl_const:Nx { c }
```

(End definition for `\tl_const:Nn`. This function is documented on page 34.)

`\tl_clear:N` Clearing a token list variable means setting it to an empty value. Error checking will be sorted out by the parent function.

`\tl_gclear:N`

```

\tl_gclear:c 2531 \cs_new_protected:Npn \tl_clear:N #1
2532 { \tl_set_eq:NN #1 \c_empty_tl }
\tl_gclear:c 2533 \cs_new_protected:Npn \tl_gclear:N #1
2534 { \tl_gset_eq:NN #1 \c_empty_tl }
2535 \cs_generate_variant:Nn \tl_clear:N { c }
2536 \cs_generate_variant:Nn \tl_gclear:N { c }
```

(End definition for `\tl_clear:N` and `\tl_gclear:N`. These functions are documented on page 34.)

`\tl_clear_new:N` Clearing a token list variable means setting it to an empty value. Error checking will be sorted out by the parent function.

`\tl_gclear_new:N`

```

\tl_clear_new:c 2537 \cs_new_protected:Npn \tl_clear_new:N #1
\tl_gclear_new:c 2538 { \tl_if_exist:NTF #1 { \tl_clear:N #1 } { \tl_new:N #1 } }
2539 \cs_new_protected:Npn \tl_gclear_new:N #1
2540 { \tl_if_exist:NTF #1 { \tl_gclear:N #1 } { \tl_new:N #1 } }
2541 \cs_generate_variant:Nn \tl_clear_new:N { c }
2542 \cs_generate_variant:Nn \tl_gclear_new:N { c }
```

(End definition for `\tl_clear_new:N` and `\tl_gclear_new:N`. These functions are documented on page 35.)

`\tl_set_eq:NN` For setting token list variables equal to each other.

```

\tl_set_eq:Nc 2543 \cs_new_eq:NN \tl_set_eq:NN \cs_set_eq:NN
\tl_set_eq:cN 2544 \cs_new_eq:NN \tl_set_eq:cN \cs_set_eq:cN
\tl_set_eq:cc 2545 \cs_new_eq:NN \tl_set_eq:Nc \cs_set_eq:Nc
\tl_gset_eq:NN 2546 \cs_new_eq:NN \tl_set_eq:cc \cs_set_eq:cc
\tl_gset_eq:Nc 2547 \cs_new_eq:NN \tl_gset_eq:NN \cs_gset_eq:NN
\tl_gset_eq:cN 2548 \cs_new_eq:NN \tl_gset_eq:cN \cs_gset_eq:cN
\tl_gset_eq:Nc 2549 \cs_new_eq:NN \tl_gset_eq:Nc \cs_gset_eq:Nc
\tl_gset_eq:cc 2550 \cs_new_eq:NN \tl_gset_eq:cc \cs_gset_eq:cc
```

(End definition for `\tl_set_eq:NN` and `\tl_gset_eq:NN`. These functions are documented on page 35.)

`\tl_concat:NNN` Concatenating token lists is easy.

```

\tl_concat:ccc 2551 \cs_new_protected:Npn \tl_concat:NNN #1#2#3
\tl_gconcat:NNN 2552 { \tl_set:Nx #1 { \exp_not:o {#2} \exp_not:o {#3} } }
\tl_gconcat:ccc 2553 \cs_new_protected:Npn \tl_gconcat:NNN #1#2#3
2554 { \tl_gset:Nx #1 { \exp_not:o {#2} \exp_not:o {#3} } }
2555 \cs_generate_variant:Nn \tl_concat:NNN { ccc }
2556 \cs_generate_variant:Nn \tl_gconcat:NNN { ccc }

(End definition for \tl_concat:NNN and \tl_gconcat:NNN. These functions are documented on page 35.)

```

`\tl_if_exist_p:N` Copies of the cs functions defined in l3basics.

```

\tl_if_exist_p:c 2557 \prg_new_eq_conditional:NNn \tl_if_exist:N \cs_if_exist:N { TF , T , F , p }
\tl_if_exist:NTF 2558 \prg_new_eq_conditional:NNn \tl_if_exist:c \cs_if_exist:c { TF , T , F , p }
\tl_if_exist:cTF

(End definition for \tl_if_exist:NTF. This function is documented on page 35.)

```

5.2 Constant token lists

`\c_empty_tl` Never full. We need to define that constant before using `\tl_new:N`.

```

2559 \tl_const:Nn \c_empty_tl { }

(End definition for \c_empty_tl. This variable is documented on page 46.)

\c_space_tl A space as a token list (as opposed to as a character).

2560 \tl_const:Nn \c_space_tl { ~ }

(End definition for \c_space_tl. This variable is documented on page 46.)

```

5.3 Adding to token list variables

`\tl_set:Nn` By using `\exp_not:n` token list variables can contain # tokens, which makes the token list registers provided by T_EX more or less redundant. The `\tl_set:No` version is done “by hand” as it is used quite a lot.

```

\tl_set:Nv 2561 \cs_new_protected:Npn \tl_set:Nn #1#2
\tl_set:Nf 2562 { \cs_set_nopar:Npx #1 { \exp_not:n {#2} } }
\tl_set:Nx 2563 \cs_new_protected:Npn \tl_set:No #1#2
\tl_set:cn 2564 { \cs_set_nopar:Npx #1 { \exp_not:o {#2} } }
\tl_set:cV 2565 \cs_new_protected:Npn \tl_set:Nx #1#2
\tl_set:cv 2566 { \cs_set_nopar:Npx #1 {#2} }
\tl_set:co 2567 \cs_new_protected:Npn \tl_gset:Nn #1#2
\tl_set:cf 2568 { \cs_gset_nopar:Npx #1 { \exp_not:n {#2} } }
\tl_set:cx 2569 \cs_new_protected:Npn \tl_gset:No #1#2
2570 { \cs_gset_nopar:Npx #1 { \exp_not:o {#2} } }
\tl_gset:Nn 2571 \cs_new_protected:Npn \tl_gset:Nx #1#2
\tl_gset:Nv 2572 { \cs_gset_nopar:Npx #1 {#2} }
\tl_gset:Nv 2573 \cs_generate_variant:Nn \tl_set:Nn { NV , Nv , Nf }
\tl_gset:No 2574 \cs_generate_variant:Nn \tl_set:Nx { c }
\tl_gset:Nf 2575 \cs_generate_variant:Nn \tl_set:Nn { c , co , cV , cv , cf }
\tl_gset:Nx 2576 \cs_generate_variant:Nn \tl_gset:Nn { NV , Nv , Nf }
\tl_gset:cn 2577 \cs_generate_variant:Nn \tl_gset:Nx { c }
\tl_gset:cV 2578 \cs_generate_variant:Nn \tl_gset:Nn { c , co , cV , cv , cf }
\tl_gset:cv
\tl_gset:co
\tl_gset:cf
\tl_gset:cx

(End definition for \tl_set:Nn and \tl_gset:Nn. These functions are documented on page 35.)

```

\tl_put_left:Nn Adding to the left is done directly to gain a little performance.

```

\tl_put_left:NV 2579 \cs_new_protected:Npn \tl_put_left:Nn #1#2
\tl_put_left:No 2580 { \cs_set_nopar:Npx #1 { \exp_not:n {#2} \exp_not:o #1 } }
\tl_put_left:Nx 2581 \cs_new_protected:Npn \tl_put_left:NV #1#2
\tl_put_left:cn 2582 { \cs_set_nopar:Npx #1 { \exp_not:V #2 \exp_not:o #1 } }
\tl_put_left:cV 2583 \cs_new_protected:Npn \tl_put_left:No #1#2
\tl_put_left:co 2584 { \cs_set_nopar:Npx #1 { \exp_not:o {#2} \exp_not:o #1 } }
\tl_put_left:cx 2585 \cs_new_protected:Npn \tl_put_left:Nx #1#2
\tl_gput_left:Nn 2586 { \cs_set_nopar:Npx #1 { #2 \exp_not:o #1 } }
\tl_gput_left:NV 2587 \cs_new_protected:Npn \tl_gput_left:Nn #1#2
\tl_gput_left:No 2588 { \cs_gset_nopar:Npx #1 { \exp_not:n {#2} \exp_not:o #1 } }
\tl_gput_left:Nx 2589 \cs_new_protected:Npn \tl_gput_left:NV #1#2
\tl_gput_left:cn 2590 { \cs_gset_nopar:Npx #1 { \exp_not:V #2 \exp_not:o #1 } }
\tl_gput_left:cV 2591 \cs_new_protected:Npn \tl_gput_left:No #1#2
\tl_gput_left:co 2592 { \cs_gset_nopar:Npx #1 { \exp_not:o {#2} \exp_not:o #1 } }
\tl_gput_left:cx 2593 \cs_new_protected:Npn \tl_gput_left:Nx #1#2
2594 { \cs_gset_nopar:Npx #1 { #2 \exp_not:o {#1} } }
2595 \cs_generate_variant:Nn \tl_put_left:Nn { c }
2596 \cs_generate_variant:Nn \tl_put_left:NV { c }
2597 \cs_generate_variant:Nn \tl_put_left:No { c }
2598 \cs_generate_variant:Nn \tl_put_left:Nx { c }
2599 \cs_generate_variant:Nn \tl_gput_left:Nn { c }
2600 \cs_generate_variant:Nn \tl_gput_left:NV { c }
2601 \cs_generate_variant:Nn \tl_gput_left:No { c }
2602 \cs_generate_variant:Nn \tl_gput_left:Nx { c }

```

(End definition for \tl_put_left:Nn and \tl_gput_left:Nn. These functions are documented on page 35.)

\tl_put_right:Nn The same on the right.

```

\tl_put_right:NV 2603 \cs_new_protected:Npn \tl_put_right:Nn #1#2
\tl_put_right:No 2604 { \cs_set_nopar:Npx #1 { \exp_not:o #1 \exp_not:n {#2} } }
\tl_put_right:Nx 2605 \cs_new_protected:Npn \tl_put_right:NV #1#2
\tl_put_right:cn 2606 { \cs_set_nopar:Npx #1 { \exp_not:o #1 \exp_not:V #2 } }
\tl_put_right:cV 2607 \cs_new_protected:Npn \tl_put_right:No #1#2
\tl_put_right:co 2608 { \cs_set_nopar:Npx #1 { \exp_not:o #1 \exp_not:o {#2} } }
\tl_put_right:cx 2609 \cs_new_protected:Npn \tl_put_right:Nx #1#2
\tl_gput_right:Nn 2610 { \cs_set_nopar:Npx #1 { \exp_not:o #1 #2 } }
\tl_gput_right:NV 2611 \cs_new_protected:Npn \tl_gput_right:Nn #1#2
\tl_gput_right:No 2612 { \cs_gset_nopar:Npx #1 { \exp_not:o #1 \exp_not:n {#2} } }
\tl_gput_right:Nx 2613 \cs_new_protected:Npn \tl_gput_right:NV #1#2
\tl_gput_right:cn 2614 { \cs_gset_nopar:Npx #1 { \exp_not:o #1 \exp_not:V #2 } }
\tl_gput_right:cV 2615 \cs_new_protected:Npn \tl_gput_right:No #1#2
\tl_gput_right:co 2616 { \cs_gset_nopar:Npx #1 { \exp_not:o #1 \exp_not:o {#2} } }
\tl_gput_right:cx 2617 \cs_new_protected:Npn \tl_gput_right:Nx #1#2
2618 { \cs_gset_nopar:Npx #1 { \exp_not:o {#1} #2 } }
2619 \cs_generate_variant:Nn \tl_put_right:Nn { c }
2620 \cs_generate_variant:Nn \tl_put_right:NV { c }
2621 \cs_generate_variant:Nn \tl_put_right:No { c }
2622 \cs_generate_variant:Nn \tl_put_right:Nx { c }
2623 \cs_generate_variant:Nn \tl_gput_right:Nn { c }
2624 \cs_generate_variant:Nn \tl_gput_right:NV { c }
2625 \cs_generate_variant:Nn \tl_gput_right:No { c }
2626 \cs_generate_variant:Nn \tl_gput_right:Nx { c }

```

(End definition for `\tl_put_right:Nn` and `\tl_gput_right:Nn`. These functions are documented on page 35.)

When used as a package, there is an option to be picky and to check definitions exist. This part of the process is done now, so that variable types based on `tl` (for example `clist`, `seq` and `prop`) will inherit the appropriate definitions. No `\tl_map_...` yet as the mechanisms are not fully in place. Thus instead do a more low level set up for a mapping, as in `l3basics`.

```

2627 \*package>
2628 \tex_ifodd:D \l@expl@check@declarations@bool
2629 \cs_set_protected:Npn \__cs_tmp:w #1
2630 {
2631   \if_meaning:w \q_recursion_tail #1
2632   \exp_after:wN \use_none_delimit_by_q_recursion_stop:w
2633   \fi:
2634   \use:x
2635   {
2636     \cs_set_protected:Npn #1 \exp_not:n { ##1 ##2 }
2637     {
2638       \__chk_if_exist_var:N \exp_not:n {##1}
2639       \exp_not:o { #1 {##1} {##2} }
2640     }
2641   }
2642   \__cs_tmp:w
2643 }
2644 \__cs_tmp:w
2645 \tl_set:Nn \tl_set:No \tl_set:Nx
2646 \tl_gset:Nn \tl_gset:No \tl_gset:Nx
2647 \tl_put_left:Nn \tl_put_left:Nv
2648 \tl_put_left:No \tl_put_left:Nx
2649 \tl_gput_left:Nn \tl_gput_left:Nv
2650 \tl_gput_left:No \tl_gput_left:Nx
2651 \tl_put_right:Nn \tl_put_right:Nv
2652 \tl_put_right:No \tl_put_right:Nx
2653 \tl_gput_right:Nn \tl_gput_right:Nv
2654 \tl_gput_right:No \tl_gput_right:Nx
2655 \q_recursion_tail \q_recursion_stop
2656 \*package>

```

The two `set_eq` functions are done by hand as the internals there are a bit different.

```

2657 \*package>
2658 \cs_set_protected:Npn \tl_set_eq:NN #1#2
2659 {
2660   \__chk_if_exist_var:N #1
2661   \__chk_if_exist_var:N #2
2662   \cs_set_eq:NN #1 #2
2663 }
2664 \cs_set_protected:Npn \tl_gset_eq:NN #1#2
2665 {
2666   \__chk_if_exist_var:N #1
2667   \__chk_if_exist_var:N #2
2668   \cs_gset_eq:NN #1 #2
2669 }
2670 \*package>

```

There is also a need to check all three arguments of the `concat` functions: a token list #2 or #3 equal to `\scan_stop:` would lead to problems later on.

```

2671 (*package)
2672 \cs_set_protected:Npn \tl_concat:NNN #1#2#3
2673 {
2674   \__chk_if_exist_var:N #1
2675   \__chk_if_exist_var:N #2
2676   \__chk_if_exist_var:N #3
2677   \tl_set:Nx #1 { \exp_not:o {#2} \exp_not:o {#3} }
2678 }
2679 \cs_set_protected:Npn \tl_gconcat:NNN #1#2#3
2680 {
2681   \__chk_if_exist_var:N #1
2682   \__chk_if_exist_var:N #2
2683   \__chk_if_exist_var:N #3
2684   \tl_gset:Nx #1 { \exp_not:o {#2} \exp_not:o {#3} }
2685 }
2686 \tex_fi:D
2687 </package>

```

5.4 Reassigning token list category codes

`\c__tl_rescan_marker_tl` The rescanning code needs a special token list containing the same character (chosen here to be a colon) with two different category codes: it cannot appear in the tokens being rescanned since all colons have the same category code.

```

2688 \tl_const:Nx \c__tl_rescan_marker_tl { : \token_to_str:N : }

```

(End definition for `\c__tl_rescan_marker_tl`.)

```

\tl_set_rescan:Nnn
\tl_set_rescan:Nno
\tl_set_rescan:Nnx
\tl_set_rescan:cnn
\tl_set_rescan:cno
\tl_set_rescan:cnx
\tl_gset_rescan:Nnn
\tl_gset_rescan:Nno
\tl_gset_rescan:Nnx
\tl_gset_rescan:cnn
\tl_gset_rescan:cno
\tl_gset_rescan:cnx
\tl_rescan:nn
  \__tl_set_rescan:NNnn
  \__tl_set_rescan_multi:n
    \__tl_rescan:w

```

These functions use a common auxiliary. After some initial setup explained below, and the user setup #3 (followed by `\scan_stop:` to be safe), the tokens are rescanned by `_tl_set_rescan:n` and stored into `\l__tl_internal_a_tl`, then passed to #1#2 outside the group after expansion. The auxiliary `__tl_set_rescan:n` is defined later: in the simplest case, this auxiliary calls `__tl_set_rescan_multi:n`, whose code is included here to help understand the approach.

One difficulty when rescanning is that `\scantokens` treats the argument as a file, and without the correct settings a T_EX error occurs:

```

! File ended while scanning definition of ...

```

The standard solution is to use an x-expanding assignment and set `\everyeof` to `\exp_not:N` to suppress the error at the end of the file. Since the rescanned tokens should not be expanded, they will be taken as a delimited argument of an auxiliary which wraps them in `\exp_not:n` (in fact `\exp_not:o`, as there is a `\prg_do_nothing:` to avoid losing braces). The delimiter cannot appear within the rescanned token list because it contains twice the same character, with different catcodes.

The difference between single-line and multiple-line files complicates the story, as explained below.

```

2689 \cs_new_protected:Npn \tl_set_rescan:Nnn
2690 { \__tl_set_rescan:NNnn \tl_set:Nn }
2691 \cs_new_protected:Npn \tl_gset_rescan:Nnn
2692 { \__tl_set_rescan:NNnn \tl_gset:Nn }

```

```

2693 \cs_new_protected:Npn \tl_rescan:nn
2694 { \__tl_set_rescan:NNnn \prg_do_nothing: \use:n }
2695 \cs_new_protected:Npn \__tl_set_rescan:NNnn #1#2#3#4
2696 {
2697   \tl_if_empty:nTF {#4}
2698   {
2699     \group_begin:
2700     #3
2701     \group_end:
2702     #1 #2 { }
2703   }
2704   {
2705     \group_begin:
2706     \exp_args:No \etex_everyeof:D { \c__tl_rescan_marker_tl \exp_not:N }
2707     \int_compare:nNtT \tex_endlinechar:D = { 32 }
2708     { \int_set:Nn \tex_endlinechar:D { -1 } }
2709     \tex_newlinechar:D \tex_endlinechar:D
2710     #3 \scan_stop:
2711     \exp_args:No \__tl_set_rescan:n { \tl_to_str:n {#4} }
2712     \exp_args:NNNo
2713     \group_end:
2714     #1 #2 \l__tl_internal_a_tl
2715   }
2716 }
2717 \cs_new_protected:Npn \__tl_set_rescan_multi:n #1
2718 {
2719   \tl_set:Nx \l__tl_internal_a_tl
2720   {
2721     \exp_after:wN \__tl_rescan:w
2722     \exp_after:wN \prg_do_nothing:
2723     \etex_scantokens:D {#1}
2724   }
2725 }
2726 \exp_args:Nno \use:nn
2727 { \cs_new:Npn \__tl_rescan:w #1 } \c__tl_rescan_marker_tl
2728 { \exp_not:o {#1} }
2729 \cs_generate_variant:Nn \tl_set_rescan:Nnn { Nno , Nnx }
2730 \cs_generate_variant:Nn \tl_set_rescan:Nnn { c , cno , cnx }
2731 \cs_generate_variant:Nn \tl_gset_rescan:Nnn { Nno , Nnx }
2732 \cs_generate_variant:Nn \tl_gset_rescan:Nnn { c , cno }

```

(End definition for `\tl_set_rescan:Nnn` and others. These functions are documented on page 37.)

| | |
|---|---|
| <pre> __tl_set_rescan:n __tl_set_rescan:NnTF __tl_set_rescan_single:nn __tl_set_rescan_single_aux:nn </pre> | <p>This function calls <code>__tl_set_rescan_multiple:n</code> or <code>__tl_set_rescan_single:nn</code> { ' } depending on whether its argument is a single-line fragment of code/data or is made of multiple lines by testing for the presence of a <code>\newlinechar</code> character. If <code>\newlinechar</code> is out of range, the argument is assumed to be a single line.</p> |
|---|---|

The case of multiple lines is a straightforward application of `\scantokens` as described above. The only subtlety is that `\newlinechar` should be equal to `\endlinechar` because `\newlinechar` characters become new lines and then become `\endlinechar` characters when writing to an abstract file and reading back. This equality is ensured by setting `\newlinechar` equal to `\endlinechar`. Prior to this, `\endlinechar` is set to -1 if it was 32 (in particular true after `\ExplSyntaxOn`) to avoid unreasonable line-breaks at every space for instance in error messages triggered by the user setup. Another side effect

of reading back from the file is that spaces (catcode 10) are ignored at the beginning of lines, and spaces and tabs (character code 32 and 9) are ignored at the end of lines.

For a single line, no `\endlinechar` should be added, so it will be set to `-1`, and spaces should not be removed.

Trailing spaces and tabs are a difficult matter, as \TeX removes these at a very low level. The only way to preserve them is to rescan not the argument but the argument followed by a character with a reasonable category code. Here, 11 (letter), 12 (other) and 13 (active) are accepted, as these are suitable for delimiting an argument, and it is very unlikely that none of the ASCII characters are in one of these categories. To avoid selecting one particular character to put at the end, whose category code may have been modified, there is a loop through characters from `'` (ASCII 39) to `~` (ASCII 127). The choice of starting point was made because this is the start of a very long range of characters whose standard category is letter or other, thus minimizing the number of steps needed by the loop (most often just a single one). Once a valid character is found, run some code very similar to `__tl_set_rescan_multi:n`, except that `__tl_rescan:w` must be redefined to also remove the additional character (with the appropriate catcode). Getting the delimiter with the right catcode requires using `\scantokens` inside an `x`-expansion, hence using the previous definition of `__tl_rescan:w` as well. The odd `\exp_not:N\use:n` ensures that the trailing `\exp_not:N` in `\everyeof` does not prevent the expansion of `\c__tl_rescan_marker_tl`, but rather of a closing brace (this does nothing). If no valid character is found, similar code is ran, and the only difference is that trailing spaces are not preserved (bear in mind that this only happens if no character between 39 and 127 has catcode letter, other or active).

There is also some work to preserve leading spaces: test whether the first character (given by `\str_head:n`, with an extra space to circumvent a limitation of `f`-expansion) has catcode 10 and add what \TeX would add in the middle of a line for any sequence of such characters: a single space with catcode 10 and character code 32.

```

2733 \group_begin:
2734   \tex_catcode:D '\^~@ = 12 \scan_stop:
2735   \cs_new_protected:Npn \__tl_set_rescan:n #1
2736     {
2737       \int_compare:nNnTF \tex_newlinechar:D < 0
2738         { \use_ii:n }
2739         {
2740           \char_set_lccode:nn { 0 } { \tex_newlinechar:D }
2741           \tex_lowercase:D { \__tl_set_rescan:NnTF ^~@ } {#1}
2742         }
2743         { \__tl_set_rescan_multi:n }
2744         { \__tl_set_rescan_single:nn { ' } } }
2745     {#1}
2746   }
2747   \cs_new_protected:Npn \__tl_set_rescan:NnTF #1#2
2748     { \tl_if_in:nnTF {#2} {#1} }
2749   \cs_new_protected:Npn \__tl_set_rescan_single:nn #1
2750     {
2751       \int_compare:nNnTF
2752         { \char_value_catcode:n { '#1 } / 3 } = 4
2753         { \__tl_set_rescan_single_aux:nn {#1} }
2754         {
2755           \int_compare:nNnTF { '#1 } < { '\~ }
2756             {

```

```

2757         \char_set_lccode:nn { 0 } { '#1 + 1 }
2758         \tex_lowercase:D { \_tl_set_rescan_single:nn { ^~@ } }
2759     }
2760     { \_tl_set_rescan_single_aux:nn { } }
2761 }
2762 }
2763 \cs_new_protected:Npn \_tl_set_rescan_single_aux:nn #1#2
2764 {
2765     \int_set:Nn \tex_endlinechar:D { -1 }
2766     \use:x
2767     {
2768         \exp_not:N \use:n
2769         {
2770             \exp_not:n { \cs_set:Npn \_tl_rescan:w ##1 }
2771             \exp_after:wN \_tl_rescan:w
2772             \exp_after:wN \prg_do_nothing:
2773             \etex_scantokens:D {#1}
2774         }
2775         \c__tl_rescan_marker_tl
2776     }
2777     { \exp_not:o {##1} }
2778     \tl_set:Nx \l__tl_internal_a_tl
2779     {
2780         \int_compare:nNnT
2781         {
2782             \char_value_catcode:n
2783             { \exp_last_unbraced:Nf ' \str_head:n {#2} ~ }
2784         }
2785         = { 10 } { ~ }
2786         \exp_after:wN \_tl_rescan:w
2787         \exp_after:wN \prg_do_nothing:
2788         \etex_scantokens:D { #2 #1 }
2789     }
2790 }
2791 \group_end:

```

(End definition for `_tl_set_rescan:n` and others.)

5.5 Modifying token list variables

`\tl_replace_all:Nnn` All of the `replace` functions call `_tl_replace:NnnNnn` with appropriate arguments. `\tl_replace_all:cnn` The first two arguments are explained later. The next controls whether the replacement function calls itself (`_tl_replace_next:w`) or stops (`_tl_replace_wrap:w`) after the first replacement. Next comes an x-type assignment function `\tl_set:Nx` or `\tl_gset:Nx` for local or global replacements. Finally, the three arguments $\langle tl\ var \rangle$ $\{ \langle pattern \rangle \}$ $\{ \langle replacement \rangle \}$ provided by the user. When describing the auxiliary functions below, we denote the contents of the $\langle tl\ var \rangle$ by $\langle token\ list \rangle$.

```

2792 \cs_new_protected:Npn \tl_replace_once:Nnn
2793 { \_tl_replace:NnnNnn \q_mark ? \_tl_replace_wrap:w \tl_set:Nx }
2794 \cs_new_protected:Npn \tl_greplace_once:Nnn
2795 { \_tl_replace:NnnNnn \q_mark ? \_tl_replace_wrap:w \tl_gset:Nx }
2796 \cs_new_protected:Npn \tl_replace_all:Nnn
2797 { \_tl_replace:NnnNnn \q_mark ? \_tl_replace_next:w \tl_set:Nx }

```

```

2798 \cs_new_protected:Npn \tl_greplace_all:Nnn
2799   { \__tl_replace:NnnNNNnn \q_mark ? \__tl_replace_next:w \tl_gset:Nx }
2800 \cs_generate_variant:Nn \tl_replace_once:Nnn { c }
2801 \cs_generate_variant:Nn \tl_greplace_once:Nnn { c }
2802 \cs_generate_variant:Nn \tl_replace_all:Nnn { c }
2803 \cs_generate_variant:Nn \tl_greplace_all:Nnn { c }

```

(End definition for `\tl_replace_all:Nnn` and others. These functions are documented on page 36.)

```

\__tl_replace:NnnNNNnn
\__tl_replace_auxi:NnnNNNnn
\__tl_replace_auxii:NnnNNnn
\__tl_replace_next:w
\__tl_replace_wrap:w

```

To implement the actual replacement auxiliary `__tl_replace_auxii:nNNNnn` we will need a $\langle \textit{delimiter} \rangle$ with the following properties:

- all occurrences of the $\langle \textit{pattern} \rangle$ #6 in “ $\langle \textit{token list} \rangle \langle \textit{delimiter} \rangle$ ” belong to the $\langle \textit{token list} \rangle$ and have no overlap with the $\langle \textit{delimiter} \rangle$,
- the first occurrence of the $\langle \textit{delimiter} \rangle$ in “ $\langle \textit{token list} \rangle \langle \textit{delimiter} \rangle$ ” is the trailing $\langle \textit{delimiter} \rangle$.

We first find the building blocks for the $\langle \textit{delimiter} \rangle$, namely two tokens $\langle A \rangle$ and $\langle B \rangle$ such that $\langle A \rangle$ does not appear in #6 and #6 is not $\langle B \rangle$ (this condition is trivial if #6 has more than one token). Then we consider the delimiters “ $\langle A \rangle$ ” and “ $\langle A \rangle \langle A \rangle^n \langle B \rangle \langle A \rangle^n \langle B \rangle$ ”, for $n \geq 1$, where $\langle A \rangle^n$ denotes n copies of $\langle A \rangle$, and we choose as our $\langle \textit{delimiter} \rangle$ the first one which is not in the $\langle \textit{token list} \rangle$.

Every delimiter in the set obeys the first condition: #6 does not contain $\langle A \rangle$ hence cannot be overlapping with the $\langle \textit{token list} \rangle$ and the $\langle \textit{delimiter} \rangle$, and it cannot be within the $\langle \textit{delimiter} \rangle$ since it would have to be in one of the two $\langle B \rangle$ hence be equal to this single token (or empty, but this is an error case filtered separately). Given the particular form of these delimiters, for which no prefix is also a suffix, the second condition is actually a consequence of the weaker condition that the $\langle \textit{delimiter} \rangle$ we choose does not appear in the $\langle \textit{token list} \rangle$. Additionally, the set of delimiters is such that a $\langle \textit{token list} \rangle$ of n tokens can contain at most $O(n^{1/2})$ of them, hence we find a $\langle \textit{delimiter} \rangle$ with at most $O(n^{1/2})$ tokens in a time at most $O(n^{3/2})$. Bear in mind that these upper bounds are reached only in very contrived scenarios: we include the case “ $\langle A \rangle$ ” in the list of delimiters to try, so that the $\langle \textit{delimiter} \rangle$ will simply be `\q_mark` in the most common situation where neither the $\langle \textit{token list} \rangle$ nor the $\langle \textit{pattern} \rangle$ contains `\q_mark`.

Let us now ahead, optimizing for this most common case. First, two special cases: an empty $\langle \textit{pattern} \rangle$ #6 is an error, and if #1 is absent from both the $\langle \textit{token list} \rangle$ #5 and the $\langle \textit{pattern} \rangle$ #6 then we can use it as the $\langle \textit{delimiter} \rangle$ through `__tl_replace_auxii:nNNNnn {#1}`. Otherwise, we end up calling `__tl_replace:NnnNNNnn` repeatedly with the first two arguments `\q_mark {?}`, `\? {??}`, `\?? {???`, and so on, until #6 does not contain the control sequence #1, which we take as our $\langle A \rangle$. The argument #2 only serves to collect ? characters for #1. Note that the order of the tests means that the first two are done every time, which is wasteful (for instance, we repeatedly test for the emptiness of #6). However, this is rare enough not to matter. Finally, choose $\langle B \rangle$ to be `\q_nil` or `\q_stop` such that it is not equal to #6.

The `__tl_replace_auxi:NnnNNNnn` auxiliary receives $\{\langle A \rangle\}$ and $\{\langle A \rangle^n \langle B \rangle\}$ as its arguments, initially with $n = 1$. If “ $\langle A \rangle \langle A \rangle^n \langle B \rangle \langle A \rangle^n \langle B \rangle$ ” is in the $\langle \textit{token list} \rangle$ then increase n and try again. Once it is not anymore in the $\langle \textit{token list} \rangle$ we take it as our $\langle \textit{delimiter} \rangle$ and pass this to the `auxii` auxiliary.

```

2804 \cs_new_protected:Npn \__tl_replace:NnnNNNnn #1#2#3#4#5#6#7
2805   {
2806     \tl_if_empty:nTF {#6}

```



```

2807 {
2808   \_msg_kernel_error:nnx { kernel } { empty-search-pattern }
2809   { \tl_to_str:n {#7} }
2810 }
2811 {
2812   \tl_if_in:onTF { #5 #6 } {#1}
2813   {
2814     \tl_if_in:nnTF {#6} {#1}
2815     { \exp_args:Nc \_tl_replace:NnnNNnn {#2} {#2?} }
2816     {
2817       \quark_if_nil:nTF {#6}
2818       { \_tl_replace_auxi:NnnNNnn #5 {#1} { #1 \q_stop } }
2819       { \_tl_replace_auxi:NnnNNnn #5 {#1} { #1 \q_nil } }
2820     }
2821   }
2822   { \_tl_replace_auxii:nNNNnn {#1} }
2823   #3#4#5 {#6} {#7}
2824 }
2825 }
2826 \cs_new_protected:Npn \_tl_replace_auxi:NnnNNnn #1#2#3
2827 {
2828   \tl_if_in:NnTF #1 { #2 #3 #3 }
2829   { \_tl_replace_auxi:NnnNNnn #1 { #2 #3 } {#2} }
2830   { \_tl_replace_auxii:nNNNnn { #2 #3 #3 } }
2831 }

```

The auxiliary `_tl_replace_auxii:nNNNnn` receives the following arguments: $\langle\langle\textit{delimiter}\rangle\rangle$ $\langle\textit{function}\rangle$ $\langle\textit{assignment}\rangle$ $\langle\textit{tl var}\rangle$ $\langle\textit{pattern}\rangle$ $\langle\textit{replacement}\rangle$. All of its work is done between `\group_align_safe_begin:` and `\group_align_safe_end:` to avoid issues in alignments. It does the actual replacement within `#3 #4 {...}`, an x-expanding $\langle\textit{assignment}\rangle$ `#3` to the $\langle\textit{tl var}\rangle$ `#4`. The auxiliary `_tl_replace_next:w` is called, followed by the $\langle\textit{token list}\rangle$, some tokens including the $\langle\textit{delimiter}\rangle$ `#1`, followed by the $\langle\textit{pattern}\rangle$ `#5`. This auxiliary finds an argument delimited by `#5` (the presence of a trailing `#5` avoids runaway arguments) and calls `_tl_replace_wrap:w` to test whether this `#5` is found within the $\langle\textit{token list}\rangle$ or is the trailing one.

If on the one hand it is found within the $\langle\textit{token list}\rangle$, then `##1` cannot contain the $\langle\textit{delimiter}\rangle$ `#1` that we worked so hard to obtain, thus `_tl_replace_wrap:w` gets `##1` as its own argument `##1`, and protects it against the x-expanding assignment. It also finds `\exp_not:n` as `##2` and does nothing to it, thus letting through `\exp_not:n` $\langle\textit{replacement}\rangle$ into the assignment. Note that `_tl_replace_next:w` and `_tl_replace_wrap:w` are always called followed by two empty brace groups. These are safe because no delimiter can match them. They prevent losing braces when grabbing delimited arguments, but require the use of `\exp_not:o` and `\use_none:nn`, rather than simply `\exp_not:n`. Afterwards, `_tl_replace_next:w` is called to repeat the replacement, or `_tl_replace_wrap:w` if we only want a single replacement. In this second case, `##1` is the $\langle\textit{remaining tokens}\rangle$ in the $\langle\textit{token list}\rangle$ and `##2` is some $\langle\textit{ending code}\rangle$ which ends the assignment and removes the trailing tokens `#5` using some `\if_false: { \fi: }` trickery because `#5` may contain any delimiter.

If on the other hand the argument `##1` of `_tl_replace_next:w` is delimited by the trailing $\langle\textit{pattern}\rangle$ `#5`, then `##1` is “ $\{ \} \{ \} \langle\textit{token list}\rangle \langle\textit{delimiter}\rangle \langle\textit{ending code}\rangle$ ”, hence `_tl_replace_wrap:w` finds “ $\{ \} \{ \} \langle\textit{token list}\rangle$ ” as `##1` and the $\langle\textit{ending code}\rangle$ as `##2`. It leaves the $\langle\textit{token list}\rangle$ into the assignment and unbraces the $\langle\textit{ending code}\rangle$

which removes what remains (essentially the $\langle\textit{delimiter}\rangle$ and $\langle\textit{replacement}\rangle$).

```

2832 \cs_new_protected:Npn \__tl_replace_auxii:nNNNnn #1#2#3#4#5#6
2833 {
2834   \group_align_safe_begin:
2835   \cs_set:Npn \__tl_replace_wrap:w ##1 #1 ##2
2836     { \exp_not:o { \use_none:nn ##1 } ##2 }
2837   \cs_set:Npx \__tl_replace_next:w ##1 #5
2838   {
2839     \exp_not:N \__tl_replace_wrap:w ##1
2840     \exp_not:n { #1 }
2841     \exp_not:n { \exp_not:n {#6} }
2842     \exp_not:n { #2 { } { } }
2843   }
2844   #3 #4
2845   {
2846     \exp_after:wN \__tl_replace_next:w
2847     \exp_after:wN { \exp_after:wN }
2848     \exp_after:wN { \exp_after:wN }
2849     #4
2850     #1
2851     {
2852       \if_false: { \fi: }
2853       \exp_after:wN \use_none:n \exp_after:wN { \if_false: } \fi:
2854     }
2855     #5
2856   }
2857   \group_align_safe_end:
2858 }
2859 \cs_new_eq:NN \__tl_replace_wrap:w ?
2860 \cs_new_eq:NN \__tl_replace_next:w ?

```

(End definition for $__tl_replace:NnNNNnn$ and others.)

```

\tl_remove_once:Nn Removal is just a special case of replacement.
\tl_remove_once:cn
\tl_gremove_once:Nn
\tl_gremove_once:cn
2861 \cs_new_protected:Npn \tl_remove_once:Nn #1#2
2862   { \tl_replace_once:Nnn #1 {#2} { } }
2863 \cs_new_protected:Npn \tl_gremove_once:Nn #1#2
2864   { \tl_greplace_once:Nnn #1 {#2} { } }
2865 \cs_generate_variant:Nn \tl_remove_once:Nn { c }
2866 \cs_generate_variant:Nn \tl_gremove_once:Nn { c }

```

(End definition for $\tl_remove_once:Nn$ and $\tl_gremove_once:Nn$. These functions are documented on page 36.)

```

\tl_remove_all:Nn Removal is just a special case of replacement.
\tl_remove_all:cn
\tl_gremove_all:Nn
\tl_gremove_all:cn
2867 \cs_new_protected:Npn \tl_remove_all:Nn #1#2
2868   { \tl_replace_all:Nnn #1 {#2} { } }
2869 \cs_new_protected:Npn \tl_gremove_all:Nn #1#2
2870   { \tl_greplace_all:Nnn #1 {#2} { } }
2871 \cs_generate_variant:Nn \tl_remove_all:Nn { c }
2872 \cs_generate_variant:Nn \tl_gremove_all:Nn { c }

```

(End definition for $\tl_remove_all:Nn$ and $\tl_gremove_all:Nn$. These functions are documented on page 36.)

5.6 Token list conditionals

`\tl_if_blank_p:n` TeX skips spaces when reading a non-delimited arguments. Thus, a *token list* is blank if and only if `\use_none:n <token list> ?` is empty after one expansion. The auxiliary `__tl_if_empty_return:o` is a fast emptiness test, converting its argument to a string (after one expansion) and using the test `\if_meaning:w \q_nil ... \q_nil`.

```

\tl_if_blank_p:n 2873 \prg_new_conditional:Npnn \tl_if_blank:n #1 { p , T , F , TF }
\tl_if_blank_p:V 2874 { \__tl_if_empty_return:o { \use_none:n #1 ? } }
\tl_if_blank_p:o 2875 \cs_generate_variant:Nn \tl_if_blank_p:n { V }
\tl_if_blank:nTF 2876 \cs_generate_variant:Nn \tl_if_blank:nT { V }
\tl_if_blank:VTF 2877 \cs_generate_variant:Nn \tl_if_blank:nF { V }
\tl_if_blank:oTF 2878 \cs_generate_variant:Nn \tl_if_blank:nTF { V }
\__tl_if_blank_p:NNw 2879 \cs_generate_variant:Nn \tl_if_blank_p:n { o }
2880 \cs_generate_variant:Nn \tl_if_blank:nT { o }
2881 \cs_generate_variant:Nn \tl_if_blank:nF { o }
2882 \cs_generate_variant:Nn \tl_if_blank:nTF { o }

```

(End definition for `\tl_if_blank:nTF` and `__tl_if_blank_p:NNw`. These functions are documented on page 37.)

`\tl_if_empty_p:N` These functions check whether the token list in the argument is empty and execute the proper code from their argument(s).

```

\tl_if_empty_p:c 2883 \prg_new_conditional:Npnn \tl_if_empty:N #1 { p , T , F , TF }
\tl_if_empty:nTF 2884 {
2885   \if_meaning:w #1 \c_empty_tl
2886   \prg_return_true:
2887   \else:
2888   \prg_return_false:
2889   \fi:
2890 }
\tl_if_empty:NTF 2891 \cs_generate_variant:Nn \tl_if_empty_p:N { c }
\tl_if_empty:NNTF 2892 \cs_generate_variant:Nn \tl_if_empty:NT { c }
\tl_if_empty:NNTF 2893 \cs_generate_variant:Nn \tl_if_empty:NF { c }
\tl_if_empty:NNTF 2894 \cs_generate_variant:Nn \tl_if_empty:NNTF { c }

```

(End definition for `\tl_if_empty:NNTF`. This function is documented on page 38.)

`\tl_if_empty_p:n` Convert the argument to a string: this will be empty if and only if the argument is. Then `\if_meaning:w \q_nil ... \q_nil` is true if and only if the string ... is empty. It could be tempting to use `\if_meaning:w \q_nil #1 \q_nil` directly. This fails on a token list starting with `\q_nil` of course but more troubling is the case where argument is a complete conditional such as `\if_true: a \else: b \fi:` because then `\if_true:` is used by `\if_meaning:w`, the test turns out false, the `\else:` executes the false branch, the `\fi:` ends it and the `\q_nil` at the end starts executing...

```

2895 \prg_new_conditional:Npnn \tl_if_empty:n #1 { p , TF , T , F }
2896 {
2897   \exp_after:wN \if_meaning:w \exp_after:wN \q_nil
2898   \tl_to_str:n {#1} \q_nil
2899   \prg_return_true:
2900   \else:
2901   \prg_return_false:
2902   \fi:
2903 }
2904 \cs_generate_variant:Nn \tl_if_empty_p:n { V }

```

```

2905 \cs_generate_variant:Nn \tl_if_empty:nTF { V }
2906 \cs_generate_variant:Nn \tl_if_empty:nT { V }
2907 \cs_generate_variant:Nn \tl_if_empty:nF { V }

```

(End definition for `\tl_if_empty:nTF`. This function is documented on page 38.)

`\tl_if_empty_p:o` The auxiliary function `__tl_if_empty_return:o` is for use in various token list conditionals which reduce to testing if a given token list is empty after applying a simple function to it. The test for emptiness is based on `\tl_if_empty:nTF`, but the expansion is hard-coded for efficiency, as this auxiliary function is used in many places. Note that this works because `\etex_detokenize:D` expands tokens that follow until reading a catcode 1 (begin-group) token.

```

2908 \cs_new:Npn \__tl_if_empty_return:o #1
2909 {
2910   \exp_after:wN \if_meaning:w \exp_after:wN \q_nil
2911   \etex_detokenize:D \exp_after:wN {#1} \q_nil
2912   \prg_return_true:
2913   \else:
2914     \prg_return_false:
2915   \fi:
2916 }
2917 \prg_new_conditional:Npnn \tl_if_empty:o #1 { p , TF , T , F }
2918 { \__tl_if_empty_return:o {#1} }

```

(End definition for `\tl_if_empty:oTF` and `__tl_if_empty_return:o`. These functions are documented on page 38.)

`\tl_if_eq_p:NN` Returns `\c_true_bool` if and only if the two token list variables are equal.

```

\tl_if_eq_p:Nc      2919 \prg_new_conditional:Npnn \tl_if_eq:NN #1#2 { p , T , F , TF }
\tl_if_eq_p:cN      2920 {
\tl_if_eq_p:cc      2921   \if_meaning:w #1 #2
\tl_if_eq:NNTF      2922   \prg_return_true:
\tl_if_eq:NcTF      2923   \else:
\tl_if_eq:cNTF      2924   \prg_return_false:
\tl_if_eq:ccTF      2925   \fi:
2926 }
2927 \cs_generate_variant:Nn \tl_if_eq_p:NN { Nc , c , cc }
2928 \cs_generate_variant:Nn \tl_if_eq:NNTF { Nc , c , cc }
2929 \cs_generate_variant:Nn \tl_if_eq:NNT { Nc , c , cc }
2930 \cs_generate_variant:Nn \tl_if_eq:NNF { Nc , c , cc }

```

(End definition for `\tl_if_eq:NNTF`. This function is documented on page 38.)

`\tl_if_eq:nnTF` A simple store and compare routine.

```

\l__tl_internal_a_tl 2931 \prg_new_protected_conditional:Npnn \tl_if_eq:nn #1#2 { T , F , TF }
\l__tl_internal_b_tl 2932 {
2933   \group_begin:
2934     \tl_set:Nn \l__tl_internal_a_tl {#1}
2935     \tl_set:Nn \l__tl_internal_b_tl {#2}
2936     \if_meaning:w \l__tl_internal_a_tl \l__tl_internal_b_tl
2937     \group_end:
2938     \prg_return_true:
2939   \else:
2940     \group_end:

```

```

2941     \prg_return_false:
2942     \fi:
2943   }
2944   \tl_new:N \l__tl_internal_a_tl
2945   \tl_new:N \l__tl_internal_b_tl

```

(End definition for `\tl_if_eq:nnTF`, `\l__tl_internal_a_tl`, and `\l__tl_internal_b_tl`. These functions are documented on page 38.)

`\tl_if_in:NnTF` See `\tl_if_in:nnTF` for further comments. Here we simply expand the token list variable `\tl_if_in:cnTF` and pass it to `\tl_if_in:nnTF`.

```

2946   \cs_new_protected:Npn \tl_if_in:NnT { \exp_args:No \tl_if_in:nnT }
2947   \cs_new_protected:Npn \tl_if_in:NnF { \exp_args:No \tl_if_in:nnF }
2948   \cs_new_protected:Npn \tl_if_in:NnTF { \exp_args:No \tl_if_in:nnTF }
2949   \cs_generate_variant:Nn \tl_if_in:NnT { c }
2950   \cs_generate_variant:Nn \tl_if_in:NnF { c }
2951   \cs_generate_variant:Nn \tl_if_in:NnTF { c }

```

(End definition for `\tl_if_in:NnTF`. This function is documented on page 38.)

`\tl_if_in:nnTF` Once more, the test relies on the emptiness test for robustness. The function `__tl_tmp:w` removes tokens until the first occurrence of `#2`. If this does not appear in `#1`, then the final `#2` is removed, leaving an empty token list. Otherwise some tokens remain, and the test is false. See `\tl_if_empty:nTF` for details on the emptiness test.

Treating correctly cases like `\tl_if_in:nnTF {a state}{states}`, where `#1#2` contains `#2` before the end, requires special care. To cater for this case, we insert `{ }{ }` between the two token lists. This marker may not appear in `#2` because of \TeX limitations on what can delimit a parameter, hence we are safe. Using two brace groups makes the test work also for empty arguments. The `\if_false:` constructions are a faster way to do `\group_align_safe_begin:` and `\group_align_safe_end:`.

```

2952   \prg_new_protected_conditional:Npnn \tl_if_in:nn #1#2 { T , F , TF }
2953   {
2954     \if_false: { \fi:
2955       \cs_set:Npn \__tl_tmp:w ##1 #2 { }
2956       \tl_if_empty:oTF { \__tl_tmp:w #1 {} {} #2 }
2957       { \prg_return_false: } { \prg_return_true: }
2958     \if_false: } \fi:
2959   }
2960   \cs_generate_variant:Nn \tl_if_in:nnT { V , o , no }
2961   \cs_generate_variant:Nn \tl_if_in:nnF { V , o , no }
2962   \cs_generate_variant:Nn \tl_if_in:nnTF { V , o , no }

```

(End definition for `\tl_if_in:nnTF`. This function is documented on page 38.)

`\tl_if_single_p:N` Expand the token list and feed it to `\tl_if_single:n`.

```

\tl_if_single:NnTF
2963   \cs_new:Npn \tl_if_single_p:N { \exp_args:No \tl_if_single_p:n }
2964   \cs_new:Npn \tl_if_single:NnT { \exp_args:No \tl_if_single:nT }
2965   \cs_new:Npn \tl_if_single:NnF { \exp_args:No \tl_if_single:nF }
2966   \cs_new:Npn \tl_if_single:NnTF { \exp_args:No \tl_if_single:nTF }

```

(End definition for `\tl_if_single:NnTF`. This function is documented on page 38.)

`\tl_if_single_p:n` This test is similar to `\tl_if_empty:nTF`. Expanding `\use_none:nn #1 ??` once yields an empty result if #1 is blank, a single ? if #1 has a single item, and otherwise yields some tokens ending with ??. Then, `\tl_to_str:n` makes sure there are no odd category codes. An earlier version would compare the result to a single ? using string comparison, but the Lua call is slow in LuaTeX. Instead, `__tl_if_single:nw` picks the second token in front of it. If #1 is empty, this token will be the trailing ? and the catcode test yields **false**. If #1 has a single item, the token will be ^ and the catcode test yields **true**. Otherwise, it will be one of the characters resulting from `\tl_to_str:n`, and the catcode test yields **false**. Note that `\if_catcode:w` takes care of the expansions, and that `\tl_to_str:n` (the `\detokenize` primitive) actually expands tokens until finding a begin-group token.

```

2967 \prg_new_conditional:Npnn \tl_if_single:n #1 { p , T , F , TF }
2968 {
2969   \if_catcode:w ^ \exp_after:wN \__tl_if_single:nw
2970     \tl_to_str:n \exp_after:wN { \use_none:nn #1 ?? } ^ ? \q_stop
2971   \prg_return_true:
2972   \else:
2973     \prg_return_false:
2974   \fi:
2975 }
2976 \cs_new:Npn \__tl_if_single:nw #1#2#3 \q_stop {#2}

```

(End definition for `\tl_if_single:nTF` and `__tl_if_single:nTF`. These functions are documented on page 39.)

`\tl_case:Nn` The aim here is to allow the case statement to be evaluated using a known number of expansion steps (two), and without needing to use an explicit “end of recursion” marker. That is achieved by using the test input as the final case, as this will always be true. The trick is then to tidy up the output such that the appropriate case code plus either the **true** or **false** branch code is inserted.

```

\__tl_case:nnTF
\__tl_case:Nw
\__prg_case_end:nw
2977 \cs_new:Npn \tl_case:Nn #1#2
2978 {
2979   \exp:w
2980   \__tl_case:NnTF #1 {#2} { } { }
2981 }
2982 \cs_new:Npn \tl_case:NnT #1#2#3
2983 {
2984   \exp:w
2985   \__tl_case:NnTF #1 {#2} {#3} { }
2986 }
2987 \cs_new:Npn \tl_case:NnF #1#2#3
2988 {
2989   \exp:w
2990   \__tl_case:NnTF #1 {#2} { } {#3}
2991 }
2992 \cs_new:Npn \tl_case:NnTF #1#2
2993 {
2994   \exp:w
2995   \__tl_case:NnTF #1 {#2}
2996 }
2997 \cs_new:Npn \__tl_case:NnTF #1#2#3#4
2998 { \__tl_case:Nw #1 #2 #1 { } \q_mark {#3} \q_mark {#4} \q_stop }
2999 \cs_new:Npn \__tl_case:Nw #1#2#3

```

```

3000 {
3001   \tl_if_eq:NNTF #1 #2
3002     { \__tl_case_end:nw {#3} }
3003     { \__tl_case:Nw #1 }
3004 }
3005 \cs_generate_variant:Nn \tl_case:Nn { c }
3006 \cs_generate_variant:Nn \tl_case:NnT { c }
3007 \cs_generate_variant:Nn \tl_case:NnF { c }
3008 \cs_generate_variant:Nn \tl_case:NnTF { c }

```

To tidy up the recursion, there are two outcomes. If there was a hit to one of the cases searched for, then #1 will be the code to insert, #2 will be the *next* case to check on and #3 will be all of the rest of the cases code. That means that #4 will be the **true** branch code, and #5 will be tidy up the spare `\q_mark` and the **false** branch. On the other hand, if none of the cases matched then we arrive here using the “termination” case of comparing the search with itself. That means that #1 will be empty, #2 will be the first `\q_mark` and so #4 will be the **false** code (the **true** code is mopped up by #3).

```

3009 \cs_new:Npn \__prg_case_end:nw #1#2#3 \q_mark #4#5 \q_stop
3010   { \exp_end: #1 #4 }
3011 \cs_new_eq:NN \__tl_case_end:nw \__prg_case_end:nw

```

(End definition for `\tl_case:NnTF` and others. These functions are documented on page 39.)

5.7 Mapping to token lists

`\tl_map_function:nN` Expandable loop macro for token lists. These have the advantage of not needing to test if the argument is empty, because if it is, the stop marker will be read immediately and the loop terminated.

```

\__tl_map_function:Nn
3012 \cs_new:Npn \tl_map_function:nN #1#2
3013 {
3014   \__tl_map_function:Nn #2 #1
3015   \q_recursion_tail
3016   \__prg_break_point:Nn \tl_map_break: { }
3017 }
3018 \cs_new:Npn \tl_map_function:NN
3019   { \exp_args:No \tl_map_function:nN }
3020 \cs_new:Npn \__tl_map_function:Nn #1#2
3021 {
3022   \__quark_if_recursion_tail_break:nN {#2} \tl_map_break:
3023   #1 {#2} \__tl_map_function:Nn #1
3024 }
3025 \cs_generate_variant:Nn \tl_map_function:NN { c }

```

(End definition for `\tl_map_function:nN`, `\tl_map_function:NN`, and `__tl_map_function:Nn`. These functions are documented on page 39.)

`\tl_map_inline:nn` The inline functions are straight forward by now. We use a little trick with the counter `\g__prg_map_int` to make them nestable. We can also make use of `__tl_map_function:Nn` from before.

```

3026 \cs_new_protected:Npn \tl_map_inline:nn #1#2
3027 {
3028   \int_gincr:N \g__prg_map_int
3029   \cs_gset:cpn { __prg_map_ \int_use:N \g__prg_map_int :w } ##1 {#2}
3030   \exp_args:Nc \__tl_map_function:Nn

```

```

3031     { __prg_map_ \int_use:N \g__prg_map_int :w }
3032     #1 \q_recursion_tail
3033     \__prg_break_point:Nn \tl_map_break: { \int_gdecr:N \g__prg_map_int }
3034 }
3035 \cs_new_protected:Npn \tl_map_inline:Nn
3036 { \exp_args:No \tl_map_inline:nn }
3037 \cs_generate_variant:Nn \tl_map_inline:Nn { c }

```

`\tl_map_variable:nNn` `\tl_map_variable:nNn` $\langle token\ list \rangle$ $\langle temp \rangle$ $\langle action \rangle$ assigns $\langle temp \rangle$ to each element and executes $\langle action \rangle$.

(End definition for `\tl_map_variable:nNn`, `\tl_map_variable:NNn`, and `__tl_map_variable:Nnn`. These functions are documented on page 40.)

[illegible]

5.8 Using token lists

(End definition for `tl_to_str:n`. This function is documented on page 41.)

```
\tl_to_str:c      3058 \cs_new:Npn \tl_to_str:N #1 { \etex_detokenize:D \exp_after:wN {#1} }
                   3059 \cs_generate_variant:Nn \tl_to_str:N { c }
```


\tl_use:N Token lists which are simply not defined will give a clear T_EX error here. No such luck for ones equal to `\scan_stop`: so instead a test is made and if there is an issue an error is forced.

```

3060 \cs_new:Npn \tl_use:N #1
3061 {
3062   \tl_if_exist:NTF #1 {#1}
3063   {
3064     \_msg_kernel_expandable_error:nnn
3065     { kernel } { bad-variable } {#1}
3066   }
3067 }
3068 \cs_generate_variant:Nn \tl_use:N { c }

```

(End definition for `\tl_use:N`. This function is documented on page 41.)

5.9 Working with the contents of token lists

\tl_count:n Count number of elements within a token list or token list variable. Brace groups within the list are read as a single element. Spaces are ignored. `__tl_count:n` grabs the element and replaces it by +1. The 0 ensures that it works on an empty list.

```

3069 \cs_new:Npn \tl_count:n #1
3070 {
3071   \int_eval:n
3072   { 0 \tl_map_function:nN {#1} \__tl_count:n }
3073 }
3074 \cs_new:Npn \tl_count:N #1
3075 {
3076   \int_eval:n
3077   { 0 \tl_map_function:NN #1 \__tl_count:n }
3078 }
3079 \cs_new:Npn \__tl_count:n #1 { + 1 }
3080 \cs_generate_variant:Nn \tl_count:n { V , o }
3081 \cs_generate_variant:Nn \tl_count:N { c }

```

(End definition for `\tl_count:n`, `\tl_count:N`, and `__tl_count:n`. These functions are documented on page 41.)

\tl_reverse_items:n Reversal of a token list is done by taking one item at a time and putting it after `\q_stop`.

```

3082 \cs_new:Npn \tl_reverse_items:n #1
3083 {
3084   \__tl_reverse_items:nwNwn #1 ?
3085   \q_mark \__tl_reverse_items:nwNwn
3086   \q_mark \__tl_reverse_items:wn
3087   \q_stop { }
3088 }
3089 \cs_new:Npn \__tl_reverse_items:nwNwn #1 #2 \q_mark #3 #4 \q_stop #5
3090 {
3091   #3 #2
3092   \q_mark \__tl_reverse_items:nwNwn
3093   \q_mark \__tl_reverse_items:wn
3094   \q_stop { {#1} #5 }
3095 }
3096 \cs_new:Npn \__tl_reverse_items:wn #1 \q_stop #2
3097 { \exp_not:o { \use_none:nn #2 } }

```

(End definition for `\tl_reverse_items:n`, `__tl_reverse_items:nwNwn`, and `__tl_reverse_items:wn`. These functions are documented on page 42.)

`\tl_trim_spaces:n` Trimming spaces from around the input is deferred to an internal function whose first argument is the token list to trim, augmented by an initial `\q_mark`, and whose second argument is a *<continuation>*, which will receive as a braced argument `\use_none:n \q_mark` *<trimmed token list>*. In the case at hand, we take `\exp_not:o` as our continuation, so that space trimming will behave correctly within an x-type expansion.

```

3098 \cs_new:Npn \tl_trim_spaces:n #1
3099   { \__tl_trim_spaces:nn { \q_mark #1 } \exp_not:o }
3100 \cs_new_protected:Npn \tl_trim_spaces:N #1
3101   { \tl_set:Nx #1 { \exp_args:No \tl_trim_spaces:n {#1} } }
3102 \cs_new_protected:Npn \tl_gtrim_spaces:N #1
3103   { \tl_gset:Nx #1 { \exp_args:No \tl_trim_spaces:n {#1} } }
3104 \cs_generate_variant:Nn \tl_trim_spaces:N { c }
3105 \cs_generate_variant:Nn \tl_gtrim_spaces:N { c }

```

(End definition for `\tl_trim_spaces:n`, `\tl_trim_spaces:N`, and `\tl_gtrim_spaces:N`. These functions are documented on page 42.)

`__tl_trim_spaces:nn` Trimming spaces from around the input is done using delimited arguments and quarks, and to get spaces at odd places in the definitions, we nest those in `__tl_tmp:w`, which then receives a single space as its argument: `#1` is `␣`. Removing leading spaces is done with `__tl_trim_spaces_auxi:w`, which loops until `\q_mark␣` matches the end of the token list: then `##1` is the token list and `##3` is `__tl_trim_spaces_auxii:w`. This hands the relevant tokens to the loop `__tl_trim_spaces_auxiii:w`, responsible for trimming trailing spaces. The end is reached when `␣ \q_nil` matches the one present in the definition of `\tl_trim_spaces:n`. Then `__tl_trim_spaces_auxiv:w` puts the token list into a group, with `\use_none:n` placed there to gobble a lingering `\q_mark`, and feeds this to the *<continuation>*.

```

3106 \cs_set:Npn \__tl_tmp:w #1
3107   {
3108     \cs_new:Npn \__tl_trim_spaces:nn ##1
3109       {
3110         \__tl_trim_spaces_auxi:w
3111         ##1
3112         \q_nil
3113         \q_mark #1 { }
3114         \q_mark \__tl_trim_spaces_auxii:w
3115         \__tl_trim_spaces_auxiii:w
3116         #1 \q_nil
3117         \__tl_trim_spaces_auxiv:w
3118         \q_stop
3119       }
3120     \cs_new:Npn \__tl_trim_spaces_auxi:w ##1 \q_mark #1 ##2 \q_mark ##3
3121       {
3122         ##3
3123         \__tl_trim_spaces_auxi:w
3124         \q_mark
3125         ##2
3126         \q_mark #1 {##1}
3127       }
3128     \cs_new:Npn \__tl_trim_spaces_auxii:w

```

```

3129     \_tl_trim_spaces_auxi:w \q_mark \q_mark ##1
3130     {
3131     \_tl_trim_spaces_auxiii:w
3132     ##1
3133     }
3134     \cs_new:Npn \_tl_trim_spaces_auxiii:w ##1 #1 \q_nil ##2
3135     {
3136     ##2
3137     ##1 \q_nil
3138     \_tl_trim_spaces_auxiii:w
3139     }
3140     \cs_new:Npn \_tl_trim_spaces_auxiv:w ##1 \q_nil ##2 \q_stop ##3
3141     { ##3 { \use_none:n ##1 } }
3142   }
3143   \_tl_tmp:w { ~ }

```

(End definition for `_tl_trim_spaces:nn` and others.)

`\tl_sort:Nn` Implemented in `l3sort`.

`\tl_sort:cn`

`\tl_gsort:Nn` (End definition for `\tl_sort:Nn`, `\tl_gsort:Nn`, and `\tl_sort:nN`. These functions are documented on page 43.)

`\tl_gsort:cn`

`\tl_sort:nN`

5.10 Token by token changes

`\q__tl_act_mark` The `\tl_act` functions may be applied to any token list. Hence, we use two private quarks, to allow any token, even quarks, in the token list. Only `\q__tl_act_mark` and `\q__tl_act_stop` may not appear in the token lists manipulated by `_tl_act:NNNnn` functions. The quarks are effectively defined in `l3quark`.

`\q__tl_act_stop`

(End definition for `\q__tl_act_mark` and `\q__tl_act_stop`.)

`_tl_act:NNNnn`

`_tl_act_output:n`

`_tl_act_reverse_output:n`

`_tl_act_loop:w`

`_tl_act_normal:NwnNNN`

`_tl_act_group:nwnNNN`

`_tl_act_space:wwnNNN`

`_tl_act_end:w`

To help control the expansion, `_tl_act:NNNnn` should always be preceded by `\exp:w` and ends by producing `\exp_end:` once the result has been obtained. Then loop over tokens, groups, and spaces in #5. The marker `\q__tl_act_mark` is used both to avoid losing outer braces and to detect the end of the token list more easily. The result is stored as an argument for the dummy function `_tl_act_result:n`.

```

3144 \cs_new:Npn \_tl_act:NNNnn #1#2#3#4#5
3145 {
3146   \group_align_safe_begin:
3147   \_tl_act_loop:w #5 \q__tl_act_mark \q__tl_act_stop
3148   {#4} #1 #2 #3
3149   \_tl_act_result:n { }
3150 }

```

In the loop, we check how the token list begins and act accordingly. In the “normal” case, we may have reached `\q__tl_act_mark`, the end of the list. Then leave `\exp_end:` and the result in the input stream, to terminate the expansion of `\exp:w`. Otherwise, apply the relevant function to the “arguments”, #3 and to the head of the token list. Then repeat the loop. The scheme is the same if the token list starts with a group or with a space. Some extra work is needed to make `_tl_act_space:wwnNNN` gobble the space.

```

3151 \cs_new:Npn \_tl_act_loop:w #1 \q__tl_act_stop
3152 {
3153   \tl_if_head_is_N_type:nTF {#1}

```

```

3154     { \_tl_act_normal:NwnNNN }
3155     {
3156       \tl_if_head_is_group:nTF {#1}
3157       { \_tl_act_group:nwnNNN }
3158       { \_tl_act_space:wnnNNN }
3159     }
3160     #1 \q__tl_act_stop
3161   }
3162 \cs_new:Npn \_tl_act_normal:NwnNNN #1 #2 \q__tl_act_stop #3#4
3163 {
3164   \if_meaning:w \q__tl_act_mark #1
3165   \exp_after:wN \_tl_act_end:wn
3166   \fi:
3167   #4 {#3} #1
3168   \_tl_act_loop:w #2 \q__tl_act_stop
3169   {#3} #4
3170 }
3171 \cs_new:Npn \_tl_act_end:wn #1 \_tl_act_result:n #2
3172 { \group_align_safe_end: \exp_end: #2 }
3173 \cs_new:Npn \_tl_act_group:nwnNNN #1 #2 \q__tl_act_stop #3#4#5
3174 {
3175   #5 {#3} {#1}
3176   \_tl_act_loop:w #2 \q__tl_act_stop
3177   {#3} #4 #5
3178 }
3179 \exp_last_unbraced:NNo
3180 \cs_new:Npn \_tl_act_space:wnnNNN \c_space_tl #1 \q__tl_act_stop #2#3#4#5
3181 {
3182   #5 {#2}
3183   \_tl_act_loop:w #1 \q__tl_act_stop
3184   {#2} #3 #4 #5
3185 }

```

Typically, the output is done to the right of what was already output, using `_tl_act_output:n`, but for the `_tl_act_reverse` functions, it should be done to the left.

```

3186 \cs_new:Npn \_tl_act_output:n #1 #2 \_tl_act_result:n #3
3187 { #2 \_tl_act_result:n { #3 #1 } }
3188 \cs_new:Npn \_tl_act_reverse_output:n #1 #2 \_tl_act_result:n #3
3189 { #2 \_tl_act_result:n { #1 #3 } }

```

(End definition for `_tl_act:NNNnn` and others.)

| | |
|---|--|
| <code>\tl_reverse:n</code> <code>\tl_reverse:o</code> <code>\tl_reverse:V</code> <code>_tl_reverse_normal:nN</code> <code>_tl_reverse_group_preserve:nn</code> <code>_tl_reverse_space:n</code> | <p>The goal here is to reverse without losing spaces nor braces. This is done using the general internal function <code>_tl_act:NNNnn</code>. Spaces and “normal” tokens are output on the left of the current output. Grouped tokens are output to the left but without any reversal within the group. All of the internal functions here drop one argument: this is needed by <code>_tl_act:NNNnn</code> when changing case (to record which direction the change is in), but not when reversing the tokens.</p> |
|---|--|

```

3190 \cs_new:Npn \tl_reverse:n #1
3191 {
3192   \etex_unexpanded:D \exp_after:wN
3193   {
3194     \exp:w
3195     \_tl_act:NNNnn

```

```

3196         \tl_reverse_normal:nN
3197         \tl_reverse_group_preserve:nn
3198         \tl_reverse_space:n
3199         { }
3200         {#1}
3201     }
3202 }
3203 \cs_generate_variant:Nn \tl_reverse:n { o , V }
3204 \cs_new:Npn \tl_reverse_normal:nN #1#2
3205 { \tl_act_reverse_output:n {#2} }
3206 \cs_new:Npn \tl_reverse_group_preserve:nn #1#2
3207 { \tl_act_reverse_output:n { {#2} } }
3208 \cs_new:Npn \tl_reverse_space:n #1
3209 { \tl_act_reverse_output:n { ~ } }

```

(End definition for `\tl_reverse:n` and others. These functions are documented on page 42.)

```

\relax \tl_reverse:N This reverses the list, leaving \exp_stop_f: in front, which stops the f-expansion.
\relax \tl_reverse:c 3210 \cs_new_protected:Npn \tl_reverse:N #1
\relax \tl_greverse:N 3211 { \tl_set:Nx #1 { \exp_args:No \tl_reverse:n { #1 } } }
\relax \tl_greverse:c 3212 \cs_new_protected:Npn \tl_greverse:N #1
3213 { \tl_gset:Nx #1 { \exp_args:No \tl_reverse:n { #1 } } }
3214 \cs_generate_variant:Nn \tl_reverse:N { c }
3215 \cs_generate_variant:Nn \tl_greverse:N { c }

```

(End definition for `\tl_reverse:N` and `\tl_greverse:N`. These functions are documented on page 42.)

5.11 The first token from a token list

```

\relax \tl_head:N Finding the head of a token list expandably will always strip braces, which is fine as
\relax \tl_head:n this is consistent with for example mapping to a list. The empty brace groups in \tl_
\relax \tl_head:V head:n ensure that a blank argument gives an empty result. The result is returned
\relax \tl_head:v within the \unexpanded primitive. The approach here is to use \if_false: to allow
\relax \tl_head:f us to use } as the closing delimiter: this is the only safe choice, as any other token
\__tl_head_auxi:nw would not be able to parse it's own code. Using a marker, we can see if what we are
\__tl_head_auxii:n grabbing is exactly the marker, or there is anything else to deal with. Is there is, there
\relax \tl_head:w is a loop. If not, tidy up and leave the item in the output stream. More detail in
\relax \tl_tail:N http://tex.stackexchange.com/a/70168.
\relax \tl_tail:n 3216 \cs_new:Npn \tl_head:n #1
\relax \tl_tail:V 3217 {
\relax \tl_tail:v 3218 \etex_unexpanded:D
\relax \tl_tail:f 3219 \if_false: { \fi: \__tl_head_auxi:nw #1 { } \q_stop }
3220 }
3221 \cs_new:Npn \__tl_head_auxi:nw #1#2 \q_stop
3222 {
3223 \exp_after:wN \__tl_head_auxii:n \exp_after:wN {
3224 \if_false: } \fi: {#1}
3225 }
3226 \cs_new:Npn \__tl_head_auxii:n #1
3227 {
3228 \exp_after:wN \if_meaning:w \exp_after:wN \q_nil
3229 \tl_to_str:n \exp_after:wN { \use_none:n #1 } \q_nil
3230 \exp_after:wN \use_i:nn

```

```

3231 \else:
3232 \exp_after:wN \use_ii:nn
3233 \fi:
3234 {#1}
3235 { \if_false: { \fi: \tl_head_auxi:nw #1 } }
3236 }
3237 \cs_generate_variant:Nn \tl_head:n { V , v , f }
3238 \cs_new:Npn \tl_head:w #1#2 \q_stop {#1}
3239 \cs_new:Npn \tl_head:N { \exp_args:No \tl_head:n }

```

To corrected leave the tail of a token list, it's important *not* to absorb any of the tail part as an argument. For example, the simple definition

```

\cs_new:Npn \tl_tail:n #1 { \tl_tail:w #1 \q_stop }
\cs_new:Npn \tl_tail:w #1#2 \q_stop

```

will give the wrong result for `\tl_tail:n { a { bc } }` (the braces will be stripped). Thus the only safe way to proceed is to first check that there is an item to grab (*i.e.* that the argument is not blank) and assuming there is to dispose of the first item. As with `\tl_head:n`, the result is protected from further expansion by `\unexpanded`. While we could optimise the test here, this would leave some tokens “banned” in the input, which we do not have with this definition.

```

3240 \cs_new:Npn \tl_tail:n #1
3241 {
3242 \etex_unexpanded:D
3243 \tl_if_blank:nTF {#1}
3244 { { } }
3245 { \exp_after:wN { \use_none:n #1 } }
3246 }
3247 \cs_generate_variant:Nn \tl_tail:n { V , v , f }
3248 \cs_new:Npn \tl_tail:N { \exp_args:No \tl_tail:n }

```

(End definition for `\tl_head:N` and others. These functions are documented on page 43.)

Accessing the first token of a token list is tricky in three cases: when it has category code 1 (begin-group token), when it is an explicit space, with category code 10 and character code 32, or when the token list is empty (obviously).

Forgetting temporarily about this issue we would use the following test in `\tl_if_head_eq_charcode:nN`. Here, `\tl_head:w` yields the first token of the token list, then passed to `\exp_not:N`.

```

\if_charcode:w
\exp_after:wN \exp_not:N \tl_head:w #1 \q_nil \q_stop
\exp_not:N #2

```

The two first special cases are detected by testing if the token list starts with an N-type token (the extra ? sends empty token lists to the `true` branch of this test). In those cases, the first token is a character, and since we only care about its character code, we can use `\str_head:n` to access it (this works even if it is a space character). An empty argument will result in `\tl_head:w` leaving two tokens: ? which is taken in the `\if_charcode:w` test, and `\use_none:nn`, which ensures that `\prg_return_false:` is returned regardless of whether the charcode test was `true` or `false`.

```

3249 \prg_new_conditional:Npnn \tl_if_head_eq_charcode:nN #1#2 { p , T , F , TF }
3250 {

```

```

3251 \if_charcode:w
3252 \exp_not:N #2
3253 \tl_if_head_is_N_type:nTF { #1 ? }
3254 {
3255     \exp_after:wN \exp_not:N
3256     \tl_head:w #1 { ? \use_none:nn } \q_stop
3257 }
3258 { \str_head:n {#1} }
3259 \prg_return_true:
3260 \else:
3261 \prg_return_false:
3262 \fi:
3263 }
3264 \cs_generate_variant:Nn \tl_if_head_eq_charcode_p:nN { f }
3265 \cs_generate_variant:Nn \tl_if_head_eq_charcode:nNTF { f }
3266 \cs_generate_variant:Nn \tl_if_head_eq_charcode:nNT { f }
3267 \cs_generate_variant:Nn \tl_if_head_eq_charcode:nNF { f }

```

For `\tl_if_head_eq_catcode:nN`, again we detect special cases with a `\tl_if_head_is_N_type:n`. Then we need to test if the first token is a begin-group token or an explicit space token, and produce the relevant token, either `\c_group_begin_token` or `\c_space_token`. Again, for an empty argument, a hack is used, removing `\prg_return_true:` and `\else:` with `\use_none:nn` in case the catcode test with the (arbitrarily chosen) `?` is true.

```

3268 \prg_new_conditional:Npnn \tl_if_head_eq_catcode:nN #1 #2 { p , T , F , TF }
3269 {
3270     \if_catcode:w
3271     \exp_not:N #2
3272     \tl_if_head_is_N_type:nTF { #1 ? }
3273     {
3274         \exp_after:wN \exp_not:N
3275         \tl_head:w #1 { ? \use_none:nn } \q_stop
3276     }
3277     {
3278         \tl_if_head_is_group:nTF {#1}
3279         { \c_group_begin_token }
3280         { \c_space_token }
3281     }
3282     \prg_return_true:
3283 \else:
3284     \prg_return_false:
3285 \fi:
3286 }

```

For `\tl_if_head_eq_meaning:nN`, again, detect special cases. In the normal case, use `\tl_head:w`, with no `\exp_not:N` this time, since `\if_meaning:w` causes no expansion. With an empty argument, the test is true, and `\use_none:nnn` removes `#2` and the usual `\prg_return_true:` and `\else:`. In the special cases, we know that the first token is a character, hence `\if_charcode:w` and `\if_catcode:w` together are enough. We combine them in some order, hopefully faster than the reverse. Tests are not nested because the arguments may contain unmatched primitive conditionals.

```

3287 \prg_new_conditional:Npnn \tl_if_head_eq_meaning:nN #1#2 { p , T , F , TF }
3288 {
3289     \tl_if_head_is_N_type:nTF { #1 ? }

```

```

3290     { \_tl\_if\_head\_eq\_meaning\_normal:nN }
3291     { \_tl\_if\_head\_eq\_meaning\_special:nN }
3292     {#1} #2
3293   }
3294 \cs_new:Npn \_tl\_if\_head\_eq\_meaning\_normal:nN #1 #2
3295 {
3296   \exp\_after:wN \if\_meaning:w
3297   \tl\_head:w #1 { ?? \use\_none:nnn } \q\_stop #2
3298   \prg\_return\_true:
3299 \else:
3300   \prg\_return\_false:
3301 \fi:
3302 }
3303 \cs_new:Npn \_tl\_if\_head\_eq\_meaning\_special:nN #1 #2
3304 {
3305   \if\_charcode:w \str\_head:n {#1} \exp\_not:N #2
3306   \exp\_after:wN \use:n
3307 \else:
3308   \prg\_return\_false:
3309   \exp\_after:wN \use\_none:n
3310 \fi:
3311 {
3312   \if\_catcode:w \exp\_not:N #2
3313       \tl\_if\_head\_is\_group:nTF {#1}
3314       { \c\_group\_begin\_token }
3315       { \c\_space\_token }
3316   \prg\_return\_true:
3317 \else:
3318   \prg\_return\_false:
3319 \fi:
3320 }
3321 }

```

(End definition for `\tl_if_head_eq_meaning:nNTF` and others. These functions are documented on page 44.)

`\tl_if_head_is_N_type_p:n` A token list can be empty, can start with an explicit space character (catcode 10 and charcode 32), can start with a begin-group token (catcode 1), or start with an N-type argument. In the first two cases, the line involving `_tl_if_head_is_N_type:w` produces `~` (and otherwise nothing). In the third case (begin-group token), the lines involving `\exp_after:wN` produce a single closing brace. The category code test is thus true exactly in the fourth case, which is what we want. One cannot optimize by moving one of the `*` to the beginning: if `#1` contains primitive conditionals, all of its occurrences must be dealt with before the `\if_catcode:w` tries to skip the `true` branch of the conditional.

```

3322 \prg\_new\_conditional:Npnn \tl\_if\_head\_is\_N\_type:n #1 { p , T , F , TF }
3323 {
3324   \if\_catcode:w
3325       \if\_false: { \fi: \_tl\_if\_head\_is\_N\_type:w ? #1 ~ }
3326       \exp\_after:wN \use\_none:n
3327       \exp\_after:wN { \exp\_after:wN { \token\_to\_str:N #1 ? } }
3328       * *
3329   \prg\_return\_true:
3330 \else:
3331   \prg\_return\_false:

```



```

3332     \fi:
3333   }
3334   \cs_new:Npn \__tl_if_head_is_N_type:w #1 ~
3335   {
3336     \tl_if_empty:oTF { \use_none:n #1 } { ^ } { }
3337     \exp_after:wN \use_none:n \exp_after:wN { \if_false: } \fi:
3338   }

```

(End definition for `\tl_if_head_is_N_type:nTF` and `__tl_if_head_is_N_type:w`. These functions are documented on page 45.)

`\tl_if_head_is_group:p:n` Pass the first token of #1 through `\token_to_str:N`, then check for the brace balance.
`\tl_if_head_is_group:nTF` The extra ? caters for an empty argument.⁷

```

3339   \prg_new_conditional:Npnn \tl_if_head_is_group:n #1 { p , T , F , TF }
3340   {
3341     \if_catcode:w
3342       \exp_after:wN \use_none:n
3343       \exp_after:wN { \exp_after:wN { \token_to_str:N #1 ? } }
3344       * *
3345     \prg_return_false:
3346   \else:
3347     \prg_return_true:
3348   \fi:
3349   }

```

(End definition for `\tl_if_head_is_group:nTF`. This function is documented on page 45.)

`\tl_if_head_is_space:p:n` The auxiliary’s argument is all that is before the first explicit space in `?#1?~`. If that
`\tl_if_head_is_space:nTF` is a single ? the test yields true. Otherwise, that is more than one token, and the
`__tl_if_head_is_space:w` test yields false. The work is done within braces (with an `\if_false: { \fi: ... }` construction) both to hide potential alignment tab characters from T_EX in a table, and to allow for removing what remains of the token list after its first space. The `\exp:w` and `\exp_end:` ensure that the result of a single step of expansion directly yields a balanced token list (no trailing closing brace).

```

3350   \prg_new_conditional:Npnn \tl_if_head_is_space:n #1 { p , T , F , TF }
3351   {
3352     \exp:w \if_false: { \fi:
3353       \__tl_if_head_is_space:w ? #1 ? ~ }
3354   }
3355   \cs_new:Npn \__tl_if_head_is_space:w #1 ~
3356   {
3357     \tl_if_empty:oTF { \use_none:n #1 }
3358     { \exp_after:wN \exp_end: \exp_after:wN \prg_return_true: }
3359     { \exp_after:wN \exp_end: \exp_after:wN \prg_return_false: }
3360     \exp_after:wN \use_none:n \exp_after:wN { \if_false: } \fi:
3361   }

```

(End definition for `\tl_if_head_is_space:nTF` and `__tl_if_head_is_space:w`. These functions are documented on page 45.)

⁷Bruno: this could be made faster, but we don’t: if we hope to ever have an e-type argument, we need all brace “tricks” to happen in one step of expansion, keeping the token list brace balanced at all times.

5.12 Using a single item

\tl_item:nn The idea here is to find the offset of the item from the left, then use a loop to grab the correct item. If the resulting offset is too large, then `\quark_if_recursion_tail_stop:n` terminates the loop, and returns nothing at all.

\tl_item:Nn

\tl_item:cn

__tl_item_aux:nn

__tl_item:nn

```

3362 \cs_new:Npn \tl_item:nn #1#2
3363 {
3364   \exp_args:Nf \__tl_item:nn
3365     { \exp_args:Nf \__tl_item_aux:nn { \int_eval:n {#2} } {#1} }
3366   #1
3367   \q_recursion_tail
3368   \__prg_break_point:
3369 }
3370 \cs_new:Npn \__tl_item_aux:nn #1#2
3371 {
3372   \int_compare:nNnTF {#1} < 0
3373     { \int_eval:n { \tl_count:n {#2} + 1 + #1 } }
3374     {#1}
3375 }
3376 \cs_new:Npn \__tl_item:nn #1#2
3377 {
3378   \__quark_if_recursion_tail_break:nN {#2} \__prg_break:
3379   \int_compare:nNnTF {#1} = 1
3380     { \__prg_break:n { \exp_not:n {#2} } }
3381     { \exp_args:Nf \__tl_item:nn { \int_eval:n { #1 - 1 } } }
3382 }
3383 \cs_new:Npn \tl_item:Nn { \exp_args:No \tl_item:nn }
3384 \cs_generate_variant:Nn \tl_item:Nn { c }

```

(End definition for `\tl_item:nn` and others. These functions are documented on page 45.)

5.13 Viewing token lists

\tl_show:N Showing token list variables is done after checking that the variable is defined (see `__kernel_register_show:N`).

\tl_show:c

```

3385 \cs_new_protected:Npn \tl_show:N #1
3386 {
3387   \__msg_show_variable:NNNnn #1 \tl_if_exist:NTF ? { }
3388   { > ~ \token_to_str:N #1 = \tl_to_str:N #1 }
3389 }
3390 \cs_generate_variant:Nn \tl_show:N { c }

```

(End definition for `\tl_show:N`. This function is documented on page 45.)

\tl_show:n The `__msg_show_wrap:n` internal function performs line-wrapping and shows the result using the `\etex_showtokens:D` primitive. Since `\tl_to_str:n` is expanded within the line-wrapping code, the escape character is always a backslash.

```

3391 \cs_new_protected:Npn \tl_show:n #1
3392 { \__msg_show_wrap:n { > ~ \tl_to_str:n {#1} } }

```

(End definition for `\tl_show:n`. This function is documented on page 46.)

\tl_log:N Redirect output of \tl_show:N and \tl_show:n to the log.

```

\tl_log:c      3393 \cs_new_protected:Npn \tl_log:N
\tl_log:n      3394 { \__msg_log_next: \tl_show:N }
                3395 \cs_generate_variant:Nn \tl_log:N { c }
                3396 \cs_new_protected:Npn \tl_log:n
                3397 { \__msg_log_next: \tl_show:n }
```

(End definition for \tl_log:N and \tl_log:n. These functions are documented on page 46.)

5.14 Scratch token lists

\g_tmpa_tl Global temporary token list variables. They are supposed to be set and used immediately, with no delay between the definition and the use because you can't count on other macros not to redefine them from under you.

\g_tmpb_tl

```

\tl_new:N \g_tmpa_tl
\tl_new:N \g_tmpb_tl
```

(End definition for \g_tmpa_tl and \g_tmpb_tl. These variables are documented on page 46.)

\l_tmpa_tl These are local temporary token list variables. Be sure not to assume that the value you put into them will survive for long—see discussion above.

\l_tmpb_tl

```

\tl_new:N \l_tmpa_tl
\tl_new:N \l_tmpb_tl
```

(End definition for \l_tmpa_tl and \l_tmpb_tl. These variables are documented on page 46.)

5.15 Deprecated functions

\tl_to_lowercase:n For removal after 2017-12-31.

\tl_to_uppercase:n

```

\tl_to_lowercase:n 3402 \cs_new_protected:Npn \tl_to_lowercase:n #1
\tl_to_uppercase:n 3403 {
                    3404   \__msg_kernel_warning:nnxxx { kernel } { deprecated-command }
                    3405   { 2017-12-31 }
                    3406   { \token_to_str:N \tl_to_lowercase:n }
                    3407   { }
                    3408   \cs_gset_eq:NN \tl_to_lowercase:n \tex_lowercase:D
                    3409   \tex_lowercase:D {#1}
                    3410 }
                    3411 \cs_new_protected:Npn \tl_to_uppercase:n #1
                    3412 {
                    3413   \__msg_kernel_warning:nnxxx { kernel } { deprecated-command }
                    3414   { 2017-12-31 }
                    3415   { \token_to_str:N \tl_to_uppercase:n }
                    3416   { }
                    3417   \cs_gset_eq:NN \tl_to_uppercase:n \tex_uppercase:D
                    3418   \tex_uppercase:D {#1}
                    3419 }
```

(End definition for \tl_to_lowercase:n and \tl_to_uppercase:n.)

```

3420 </initex | package>
```

6 l3str implementation

3421 $\langle *initex | package \rangle$

3422 $\langle @@=str \rangle$

6.1 Creating and setting string variables

$\backslash str_new:N$ A string is simply a token list. The full mapping system isn't set up yet so do things by hand.

$\backslash str_new:c$

$\backslash str_use:N$ 3423 $\backslash group_begin:$

$\backslash str_use:c$ 3424 $\backslash cs_set_protected:Npn \backslash _str_tmp:n \#1$

$\backslash str_clear:N$ 3425 $\{$

$\backslash str_clear:c$ 3426 $\backslash tl_if_blank:nF \{ \#1 \}$

$\backslash str_gclear:N$ 3427 $\{$

$\backslash str_gclear:c$ 3428 $\backslash cs_new_eq:cc \{ str_ \#1 :N \} \{ tl_ \#1 :N \}$

$\backslash str_clear_new:N$ 3429 $\backslash exp_args:Nc \backslash cs_generate_variant:Nn \{ str_ \#1 :N \} \{ c \}$

$\backslash str_clear_new:c$ 3430 $\backslash _str_tmp:n$

$\backslash str_gclear_new:N$ 3431 $\}$

$\backslash str_gclear_new:c$ 3432 $\}$

$\backslash str_set_eq:NN$ 3433 $\backslash _str_tmp:n$

$\backslash str_set_eq:cN$ 3434 $\{ new \}$

$\backslash str_set_eq:Nc$ 3435 $\{ use \}$

$\backslash str_set_eq:cc$ 3436 $\{ clear \}$

$\backslash str_gset_eq:NN$ 3437 $\{ gclear \}$

$\backslash str_gset_eq:cN$ 3438 $\{ clear_new \}$

$\backslash str_gset_eq:Nc$ 3439 $\{ gclear_new \}$

$\backslash str_gset_eq:cc$ 3440 $\{ \}$

3441 $\backslash group_end:$

3442 $\backslash cs_new_eq:NN \backslash str_set_eq:NN \backslash tl_set_eq:NN$

3443 $\backslash cs_new_eq:NN \backslash str_gset_eq:NN \backslash tl_gset_eq:NN$

3444 $\backslash cs_generate_variant:Nn \backslash str_set_eq:NN \{ c , Nc , cc \}$

3445 $\backslash cs_generate_variant:Nn \backslash str_gset_eq:NN \{ c , Nc , cc \}$

(End definition for $\backslash str_new:N$ and others. These functions are documented on page 47.)

$\backslash str_set:Nn$ Simply convert the token list inputs to $\langle strings \rangle$.

$\backslash str_set:Nx$ 3446 $\backslash group_begin:$

$\backslash str_set:cn$ 3447 $\backslash cs_set_protected:Npn \backslash _str_tmp:n \#1$

$\backslash str_set:cx$ 3448 $\{$

$\backslash str_gset:Nn$ 3449 $\backslash tl_if_blank:nF \{ \#1 \}$

$\backslash str_gset:Nx$ 3450 $\{$

$\backslash str_gset:cn$ 3451 $\backslash cs_new_protected:cpx \{ str_ \#1 :Nn \} \#1\#2$

$\backslash str_gset:cx$ 3452 $\{ \backslash exp_not:c \{ tl_ \#1 :Nx \} \#1 \{ \backslash exp_not:N \backslash tl_to_str:n \{ \#2 \} \} \}$

$\backslash str_const:Nn$ 3453 $\backslash exp_args:Nc \backslash cs_generate_variant:Nn \{ str_ \#1 :Nn \} \{ Nx , cn , cx \}$

$\backslash str_const:Nx$ 3454 $\backslash _str_tmp:n$

$\backslash str_const:cn$ 3455 $\}$

$\backslash str_const:cx$ 3456 $\}$

$\backslash str_put_left:Nn$ 3457 $\backslash _str_tmp:n$

$\backslash str_put_left:Nx$ 3458 $\{ set \}$

$\backslash str_put_left:cn$ 3459 $\{ gset \}$

$\backslash str_put_left:cx$ 3460 $\{ const \}$

$\backslash str_gput_left:Nn$ 3461 $\{ put_left \}$

$\backslash str_gput_left:Nx$ 3462 $\{ gput_left \}$

$\backslash str_gput_left:cn$ 3463 $\{ put_right \}$

$\backslash str_gput_left:cx$

$\backslash str_put_right:Nn$

$\backslash str_put_right:Nx$

$\backslash str_put_right:cn$

$\backslash str_put_right:cx$

$\backslash str_gput_right:Nn$

$\backslash str_gput_right:Nx$

$\backslash str_gput_right:cn$

$\backslash str_gput_right:cx$

```

3464     { gput_right }
3465     { }
3466 \group_end:

```

(End definition for `\str_set:Nn` and others. These functions are documented on page 48.)

6.2 String comparisons

```

\str_if_empty_p:N More copy-paste!
\str_if_empty_p:c 3467 \prg_new_eq_conditional:NNn \str_if_exist:N \tl_if_exist:N { p , T , F , TF }
\str_if_empty:NTF 3468 \prg_new_eq_conditional:NNn \str_if_exist:c \tl_if_exist:c { p , T , F , TF }
\str_if_empty:cTF 3469 \prg_new_eq_conditional:NNn \str_if_empty:N \tl_if_empty:N { p , T , F , TF }
\str_if_exist_p:N 3470 \prg_new_eq_conditional:NNn \str_if_empty:c \tl_if_empty:c { p , T , F , TF }
\str_if_exist_p:c
\str_if_exist:NTF (End definition for \str_if_empty:NTF and \str_if_exist:NTF. These functions are documented on
\str_if_exist:cTF page 49.)
\_str_if_eq_x:nn
\_str_escape_x:n

```

String comparisons rely on the primitive `\(pdf)strcmp` if available: LuaTeX does not have it, so emulation is required. As the net result is that we do not *always* use the primitive, the correct approach is to wrap up in a function with defined behaviour. That's done by providing a wrapper and then redefining in the LuaTeX case. Note that the necessary Lua code is covered in `l3bootstrap`: long-term this may need to go into a separate Lua file, but at present it's somewhere that spaces are not skipped for ease-of-input. The need to detokenize and force expansion of input arises from the case where a `#` token is used in the input, *e.g.* `_str_if_eq_x:nn {#} { \tl_to_str:n {#} }`, which otherwise will fail as `\luatex_luaescapestring:D` does not double such tokens.

```

3471 \cs_new:Npn \_str_if_eq_x:nn #1#2 { \pdfstrcmp:D {#1} {#2} }
3472 \cs_if_exist:NT \luatex_luaescapestring:D
3473 {
3474   \cs_set:Npn \_str_if_eq_x:nn #1#2
3475   {
3476     \luatex_directlua:D
3477     {
3478       l3kernel_strcmp
3479       (
3480         " \_str_escape_x:n {#1} " ,
3481         " \_str_escape_x:n {#2} "
3482       )
3483     }
3484   }
3485   \cs_new:Npn \_str_escape_x:n #1
3486   {
3487     \luatex_luaescapestring:D
3488     {
3489       \etex_detokenize:D \exp_after:wN { \luatex_expanded:D {#1} }
3490     }
3491   }
3492 }

```

(End definition for `_str_if_eq_x:nn` and `_str_escape_x:n`.)

`_str_if_eq_x_return:nn` It turns out that we often need to compare a token list with the result of applying some function to it, and return with `\prg_return_true/false:`. This test is similar to `\str_if_eq:nnTF` (see `l3str`), but is hard-coded for speed.

```

3493 \cs_new:Npn \__str_if_eq_x_return:nn #1 #2
3494 {
3495     \if_int_compare:w \__str_if_eq_x:nn {#1} {#2} = 0 \exp_stop_f:
3496     \prg_return_true:
3497     \else:
3498     \prg_return_false:
3499     \fi:
3500 }

```

(End definition for __str_if_eq_x_return:nn.)

\str_if_eq_p:nn Modern engines provide a direct way of comparing two token lists, but returning a number. This set of conditionals therefore make life a bit clearer. The nn and xx versions are created directly as this is most efficient.

```

\str_if_eq_p:Vn
\str_if_eq_p:on
\str_if_eq_p:nV
\str_if_eq_p:no
\str_if_eq_p:VV
\str_if_eq:nnTF
\str_if_eq:VnTF
\str_if_eq:onTF
\str_if_eq:nVTF
\str_if_eq:noTF
\str_if_eq:VVTF
\str_if_eq_x:nn
\str_if_eq_x:nnTF
3501 \prg_new_conditional:Npnn \str_if_eq:nn #1#2 { p , T , F , TF }
3502 {
3503     \if_int_compare:w
3504     \__str_if_eq_x:nn { \exp_not:n {#1} } { \exp_not:n {#2} }
3505     = 0 \exp_stop_f:
3506     \prg_return_true: \else: \prg_return_false: \fi:
3507 }
3508 \cs_generate_variant:Nn \str_if_eq_p:nn { V , o }
3509 \cs_generate_variant:Nn \str_if_eq_p:nn { nV , no , VV }
3510 \cs_generate_variant:Nn \str_if_eq:nnT { V , o }
3511 \cs_generate_variant:Nn \str_if_eq:nnT { nV , no , VV }
3512 \cs_generate_variant:Nn \str_if_eq:nnF { V , o }
3513 \cs_generate_variant:Nn \str_if_eq:nnF { nV , no , VV }
3514 \cs_generate_variant:Nn \str_if_eq:nnTF { V , o }
3515 \cs_generate_variant:Nn \str_if_eq:nnTF { nV , no , VV }
3516 \prg_new_conditional:Npnn \str_if_eq_x:nn #1#2 { p , T , F , TF }
3517 {
3518     \if_int_compare:w \__str_if_eq_x:nn {#1} {#2} = 0 \exp_stop_f:
3519     \prg_return_true: \else: \prg_return_false: \fi:
3520 }

```

(End definition for \str_if_eq:nnTF and \str_if_eq_x:nnTF. These functions are documented on page 49.)

\str_if_eq_p:NN Note that \str_if_eq:NN is different from \tl_if_eq:NN because it needs to ignore category codes.

```

\str_if_eq_p:Nc
\str_if_eq_p:cN
\str_if_eq_p:cc
\str_if_eq:NNTF
\str_if_eq:NcTF
\str_if_eq:cNTF
\str_if_eq:ccTF
3521 \prg_new_conditional:Npnn \str_if_eq:NN #1#2 { p , TF , T , F }
3522 {
3523     \if_int_compare:w \__str_if_eq_x:nn { \tl_to_str:N #1 } { \tl_to_str:N #2 }
3524     = 0 \exp_stop_f: \prg_return_true: \else: \prg_return_false: \fi:
3525 }
3526 \cs_generate_variant:Nn \str_if_eq:NNT { c , Nc , cc }
3527 \cs_generate_variant:Nn \str_if_eq:NNTF { c , Nc , cc }
3528 \cs_generate_variant:Nn \str_if_eq:NNTF { c , Nc , cc }
3529 \cs_generate_variant:Nn \str_if_eq_p:NN { c , Nc , cc }

```

(End definition for \str_if_eq:NNTF. This function is documented on page 49.)

\str_case:nn Much the same as \tl_case:nn(TF) here: just a change in the internal comparison.

```

\str_case:on
\str_case:nV
\str_case:nv
3530 \cs_new:Npn \str_case:nn #1#2
3531 {

```

```

\str_case:nnTF
\str_case:onTF
\str_case:nVTF
\str_case:nvTF
\str_case_x:nn
\str_case_x:nnTF
\__str_case:nnTF
\__str_case_x:nnTF
\__str_case:nw

```

```

3532     \exp:w
3533     \__str_case:nnTF {#1} {#2} { } { }
3534 }
3535 \cs_new:Npn \str_case:nnT #1#2#3
3536 {
3537     \exp:w
3538     \__str_case:nnTF {#1} {#2} {#3} { }
3539 }
3540 \cs_new:Npn \str_case:nnF #1#2
3541 {
3542     \exp:w
3543     \__str_case:nnTF {#1} {#2} { }
3544 }
3545 \cs_new:Npn \str_case:nnTF #1#2
3546 {
3547     \exp:w
3548     \__str_case:nnTF {#1} {#2}
3549 }
3550 \cs_new:Npn \__str_case:nnTF #1#2#3#4
3551 { \__str_case:nw {#1} #2 {#1} { } \q_mark {#3} \q_mark {#4} \q_stop }
3552 \cs_generate_variant:Nn \str_case:nn { o , nV , nv }
3553 \cs_generate_variant:Nn \str_case:nnT { o , nV , nv }
3554 \cs_generate_variant:Nn \str_case:nnF { o , nV , nv }
3555 \cs_generate_variant:Nn \str_case:nnTF { o , nV , nv }
3556 \cs_new:Npn \__str_case:nw #1#2#3
3557 {
3558     \str_if_eq:nnTF {#1} {#2}
3559     { \__str_case_end:nw {#3} }
3560     { \__str_case:nw {#1} }
3561 }
3562 \cs_new:Npn \str_case_x:nn #1#2
3563 {
3564     \exp:w
3565     \__str_case_x:nnTF {#1} {#2} { } { }
3566 }
3567 \cs_new:Npn \str_case_x:nnT #1#2#3
3568 {
3569     \exp:w
3570     \__str_case_x:nnTF {#1} {#2} {#3} { }
3571 }
3572 \cs_new:Npn \str_case_x:nnF #1#2
3573 {
3574     \exp:w
3575     \__str_case_x:nnTF {#1} {#2} { }
3576 }
3577 \cs_new:Npn \str_case_x:nnTF #1#2
3578 {
3579     \exp:w
3580     \__str_case_x:nnTF {#1} {#2}
3581 }
3582 \cs_new:Npn \__str_case_x:nnTF #1#2#3#4
3583 { \__str_case_x:nw {#1} #2 {#1} { } \q_mark {#3} \q_mark {#4} \q_stop }
3584 \cs_new:Npn \__str_case_x:nw #1#2#3
3585 {

```

```

3586 \str_if_eq_x:nnTF {#1} {#2}
3587 { \__str_case_end:nw {#3} }
3588 { \__str_case_x:nw {#1} }
3589 }
3590 \cs_new_eq:NN \__str_case_end:nw \__prg_case_end:nw

```

(End definition for `\str_case:nnTF` and others. These functions are documented on page 49.)

6.3 Accessing specific characters in a string

```

\__str_to_other:n
\__str_to_other_loop:w
\__str_to_other_end:w

```

First apply `\tl_to_str:n`, then replace all spaces by “other” spaces, 8 at a time, storing the converted part of the string between the `\q_mark` and `\q_stop` markers. The end is detected when `__str_to_other_loop:w` finds one of the trailing A, distinguished from any contents of the initial token list by their category. Then `__str_to_other_end:w` is called, and finds the result between `\q_mark` and the first A (well, there is also the need to remove a space).

```

3591 \cs_new:Npn \__str_to_other:n #1
3592 {
3593   \exp_after:wN \__str_to_other_loop:w
3594   \tl_to_str:n {#1} ~ A ~ A ~ A ~ A ~ A ~ A ~ A ~ \q_mark \q_stop
3595 }
3596 \group_begin:
3597 \tex_lccode:D '\* = '\ %
3598 \tex_lccode:D '\A = '\A
3599 \tex_lowercase:D
3600 {
3601   \group_end:
3602   \cs_new:Npn \__str_to_other_loop:w
3603     #1 ~ #2 ~ #3 ~ #4 ~ #5 ~ #6 ~ #7 ~ #8 ~ #9 \q_stop
3604   {
3605     \if_meaning:w A #8
3606     \__str_to_other_end:w
3607     \fi:
3608     \__str_to_other_loop:w
3609     #9 #1 * #2 * #3 * #4 * #5 * #6 * #7 * #8 * \q_stop
3610   }
3611   \cs_new:Npn \__str_to_other_end:w \fi: #1 \q_mark #2 * A #3 \q_stop
3612   { \fi: #2 }
3613 }

```

(End definition for `__str_to_other:n`, `__str_to_other_loop:w`, and `__str_to_other_end:w`.)

```

\__str_to_other_fast:n
\__str_to_other_fast_loop:w
\__str_to_other_fast_end:w

```

The difference with `__str_to_other:n` is that the converted part is left in the input stream, making these commands only restricted-expandable.

```

3614 \cs_new:Npn \__str_to_other_fast:n #1
3615 {
3616   \exp_after:wN \__str_to_other_fast_loop:w \tl_to_str:n {#1} ~
3617   A ~ A ~ A ~ A ~ A ~ A ~ A ~ A ~ A ~ A ~ \q_stop
3618 }
3619 \group_begin:
3620 \tex_lccode:D '\* = '\ %
3621 \tex_lccode:D '\A = '\A
3622 \tex_lowercase:D
3623 {

```



```

3624 \group_end:
3625 \cs_new:Npn \__str_to_other_fast_loop:w
3626   #1 ~ #2 ~ #3 ~ #4 ~ #5 ~ #6 ~ #7 ~ #8 ~ #9 ~
3627   {
3628     \if_meaning:w A #9
3629     \__str_to_other_fast_end:w
3630     \fi:
3631     #1 * #2 * #3 * #4 * #5 * #6 * #7 * #8 * #9
3632     \__str_to_other_fast_loop:w *
3633   }
3634 \cs_new:Npn \__str_to_other_fast_end:w #1 * A #2 \q_stop {#1}
3635 }

```

(End definition for `__str_to_other_fast:n`, `__str_to_other_fast_loop:w`, and `__str_to_other_fast_end:w`.)

`\str_item:Nn` The `\str_item:nn` hands its argument with spaces escaped to `__str_item:nn`, and `\str_item:cn` makes sure to turn the result back into a proper string (with category code 10 spaces) eventually. The `\str_item_ignore_spaces:nn` function does not escape spaces, which are thus ignored by `__str_item:nn` since everything else is done with unlimited arguments. Evaluate the $\langle index \rangle$ argument #2 and count characters in the string, passing those two numbers to `__str_item:w` for further analysis. If the $\langle index \rangle$ is negative, shift it by the $\langle count \rangle$ to know the how many character to discard, and if that is still negative give an empty result. If the $\langle index \rangle$ is larger than the $\langle count \rangle$, give an empty result, and otherwise discard $\langle index \rangle - 1$ characters before returning the following one. The shift by -1 is obtained by inserting an empty brace group before the string in that case: that brace group also covers the case where the $\langle index \rangle$ is zero.

```

3636 \cs_new:Npn \str_item:Nn { \exp_args:No \str_item:nn }
3637 \cs_generate_variant:Nn \str_item:Nn { c }
3638 \cs_new:Npn \str_item:nn #1#2
3639   {
3640     \exp_args:Nf \tl_to_str:n
3641     {
3642       \exp_args:Nf \__str_item:nn
3643       { \__str_to_other:n {#1} } {#2}
3644     }
3645   }
3646 \cs_new:Npn \str_item_ignore_spaces:nn #1
3647   { \exp_args:No \__str_item:nn { \tl_to_str:n {#1} } }
3648 \cs_new:Npn \__str_item:nn #1#2
3649   {
3650     \exp_after:wN \__str_item:w
3651     \__int_value:w \__int_eval:w #2 \exp_after:wN ;
3652     \__int_value:w \__str_count:n {#1} ;
3653     #1 \q_stop
3654   }
3655 \cs_new:Npn \__str_item:w #1; #2;
3656   {
3657     \int_compare:nNnTF {#1} < 0
3658     {
3659       \int_compare:nNnTF {#1} < {-#2}
3660       { \use_none_delimit_by_q_stop:w }
3661       {
3662         \exp_after:wN \use_i_delimit_by_q_stop:nw

```

```

3663         \exp:w \exp_after:wN \__str_skip_exp_end:w
3664         \__int_value:w \__int_eval:w #1 + #2 ;
3665     }
3666 }
3667 {
3668     \int_compare:nNnTF {#1} > {#2}
3669     { \use_none_delimit_by_q_stop:w }
3670     {
3671         \exp_after:wN \use_i_delimit_by_q_stop:nw
3672         \exp:w \__str_skip_exp_end:w #1 ; { }
3673     }
3674 }
3675 }

```

(End definition for `\str_item:Nn` and others. These functions are documented on page 51.)

```

\__str_skip_exp_end:w
\__str_skip_loop:wNNNNNNNN
\__str_skip_end:w
\__str_skip_end:NNNNNNNN

```

Removes $\max(\#1, 0)$ characters from the input stream, and then leaves `\exp_end:.` This should be expanded using `\exp:w`. We remove characters 8 at a time until there are at most 8 to remove. Then we do a dirty trick: the `\if_case:w` construction leaves between 0 and 8 times the `\or:` control sequence, and those `\or:` become arguments of `__str_skip_end:NNNNNNNN`. If the number of characters to remove is 6, say, then there are two `\or:` left, and the 8 arguments of `__str_skip_end:NNNNNNNN` are the two `\or:`, and 6 characters from the input stream, exactly what we wanted to remove. Then close the `\if_case:w` conditional with `\fi:`, and stop the initial expansion with `\exp_end:` (see places where `__str_skip_exp_end:w` is called).

```

3676 \cs_new:Npn \__str_skip_exp_end:w #1;
3677 {
3678     \if_int_compare:w #1 > 8 \exp_stop_f:
3679     \exp_after:wN \__str_skip_loop:wNNNNNNNN
3680     \else:
3681         \exp_after:wN \__str_skip_end:w
3682         \__int_value:w \__int_eval:w
3683     \fi:
3684     #1 ;
3685 }
3686 \cs_new:Npn \__str_skip_loop:wNNNNNNNN #1; #2#3#4#5#6#7#8#9
3687 { \exp_after:wN \__str_skip_exp_end:w \__int_value:w \__int_eval:w #1 - 8 ; }
3688 \cs_new:Npn \__str_skip_end:w #1 ;
3689 {
3690     \exp_after:wN \__str_skip_end:NNNNNNNN
3691     \if_case:w #1 \exp_stop_f: \or: \or: \or: \or: \or: \or: \or: \or:
3692 }
3693 \cs_new:Npn \__str_skip_end:NNNNNNNN #1#2#3#4#5#6#7#8 { \fi: \exp_end: }

```

(End definition for `__str_skip_exp_end:w` and others.)

```

\str_range:Nnn
\str_range:nnn
\str_range_ignore_spaces:nnn
\__str_range:nnn
\__str_range:w
\__str_range:nnw

```

Sanitize the string. Then evaluate the arguments. At this stage we also decrement the $\langle \textit{start index} \rangle$, since our goal is to know how many characters should be removed. Then limit the range to be non-negative and at most the length of the string (this avoids needing to check for the end of the string when grabbing characters), shifting negative numbers by the appropriate amount. Afterwards, skip characters, then keep some more, and finally drop the end of the string.

```

3694 \cs_new:Npn \str_range:Nnn { \exp_args:No \str_range:nnn }

```

```

3695 \cs_generate_variant:Nn \str_range:Nnn { c }
3696 \cs_new:Npn \str_range:nnn #1#2#3
3697 {
3698   \exp_args:Nf \tl_to_str:n
3699   {
3700     \exp_args:Nf \__str_range:nnn
3701     { \__str_to_other:n {#1} } {#2} {#3}
3702   }
3703 }
3704 \cs_new:Npn \str_range_ignore_spaces:nnn #1
3705 { \exp_args:No \__str_range:nnn { \tl_to_str:n {#1} } }
3706 \cs_new:Npn \__str_range:nnn #1#2#3
3707 {
3708   \exp_after:wN \__str_range:w
3709   \__int_value:w \__str_count:n {#1} \exp_after:wN ;
3710   \__int_value:w \__int_eval:w #2 - 1 \exp_after:wN ;
3711   \__int_value:w \__int_eval:w #3 ;
3712   #1 \q_stop
3713 }
3714 \cs_new:Npn \__str_range:w #1; #2; #3;
3715 {
3716   \exp_args:Nf \__str_range:nnw
3717   { \__str_range_normalize:nn {#2} {#1} }
3718   { \__str_range_normalize:nn {#3} {#1} }
3719 }
3720 \cs_new:Npn \__str_range:nnw #1#2
3721 {
3722   \exp_after:wN \__str_collect_delimit_by_q_stop:w
3723   \__int_value:w \__int_eval:w #2 - #1 \exp_after:wN ;
3724   \exp:w \__str_skip_exp_end:w #1 ;
3725 }

```

(End definition for `\str_range:Nnn` and others. These functions are documented on page 52.)

`__str_range_normalize:nn` This function converts an $\langle index \rangle$ argument into an explicit position in the string (a result of 0 denoting “out of bounds”). Expects two explicit integer arguments: the $\langle index \rangle$ #1 and the string count #2. If #1 is negative, replace it by #1 + #2 + 1, then limit to the range [0, #2].

```

3726 \cs_new:Npn \__str_range_normalize:nn #1#2
3727 {
3728   \int_eval:n
3729   {
3730     \if_int_compare:w #1 < 0 \exp_stop_f:
3731     \if_int_compare:w #1 < -#2 \exp_stop_f:
3732     0
3733     \else:
3734       #1 + #2 + 1
3735     \fi:
3736   \else:
3737     \if_int_compare:w #1 < #2 \exp_stop_f:
3738     #1
3739     \else:
3740     #2
3741     \fi:

```

```

3742     \fi:
3743   }
3744 }

```

(End definition for `_str_range_normalize:nn`.)

```

\_str_collect_delimit_by_q_stop:w Collects max(#1,0) characters, and removes everything else until \q_stop. This is some-
\_str_collect_loop:wn what similar to \_str_skip_exp_end:w, but accepts integer expression arguments. This
  \_str_collect_loop:wnNNNNNNN time we can only grab 7 characters at a time. At the end, we use an \if_case:w trick
  \_str_collect_end:wn again, so that the 8 first arguments of \_str_collect_end:nnnnnnnnnw are some \or:,
\_str_collect_end:nnnnnnnnnw followed by an \fi:, followed by #1 characters from the input stream. Simply leaving
this in the input stream will close the conditional properly and the \or: disappear.

3745 \cs_new:Npn \_str_collect_delimit_by_q_stop:w #1;
3746 { \_str_collect_loop:wn #1 ; { } }
3747 \cs_new:Npn \_str_collect_loop:wn #1 ;
3748 {
3749   \if_int_compare:w #1 > 7 \exp_stop_f:
3750     \exp_after:wN \_str_collect_loop:wnNNNNNNN
3751   \else:
3752     \exp_after:wN \_str_collect_end:wn
3753   \fi:
3754   #1 ;
3755 }
3756 \cs_new:Npn \_str_collect_loop:wnNNNNNNN #1; #2 #3#4#5#6#7#8#9
3757 {
3758   \exp_after:wN \_str_collect_loop:wn
3759   \_int_value:w \_int_eval:w #1 - 7 ;
3760   { #2 #3#4#5#6#7#8#9 }
3761 }
3762 \cs_new:Npn \_str_collect_end:wn #1 ;
3763 {
3764   \exp_after:wN \_str_collect_end:nnnnnnnnnw
3765   \if_case:w \if_int_compare:w #1 > 0 \exp_stop_f: #1 \else: 0 \fi: \exp_stop_f:
3766   \or: \or: \or: \or: \or: \or: \or: \fi:
3767 }
3768 \cs_new:Npn \_str_collect_end:nnnnnnnnnw #1#2#3#4#5#6#7#8 #9 \q_stop
3769 { #1#2#3#4#5#6#7#8 }

```

(End definition for `_str_collect_delimit_by_q_stop:w` and others.)

6.4 Counting characters

```

\str_count_spaces:N To speed up this function, we grab and discard 9 space-delimited arguments in each
\str_count_spaces:c iteration of the loop. The loop stops when the last argument is one of the trailing
\str_count_spaces:n X⟨number⟩, and that ⟨number⟩ is added to the sum of 9 that precedes, to adjust the
\_str_count_spaces_loop:w result.

```

```

3770 \cs_new:Npn \str_count_spaces:N
3771 { \exp_args:No \str_count_spaces:n }
3772 \cs_generate_variant:Nn \str_count_spaces:N { c }
3773 \cs_new:Npn \str_count_spaces:n #1
3774 {
3775   \int_eval:n
3776   {

```

```

3777     \exp_after:wN \_str_count_spaces_loop:w
3778     \tl_to_str:n {#1} ~
3779     X 7 ~ X 6 ~ X 5 ~ X 4 ~ X 3 ~ X 2 ~ X 1 ~ X 0 ~ X -1 ~
3780     \q_stop
3781   }
3782 }
3783 \cs_new:Npn \_str_count_spaces_loop:w #1~#2~#3~#4~#5~#6~#7~#8~#9~
3784 {
3785   \if_meaning:w X #9
3786     \use_i_delimit_by_q_stop:nw
3787   \fi:
3788   9 + \_str_count_spaces_loop:w
3789 }

```

(End definition for `\str_count_spaces:N`, `\str_count_spaces:n`, and `_str_count_spaces_loop:w`. These functions are documented on page 50.)

`\str_count:N` To count characters in a string we could first escape all spaces using `_str_to_other:n`, then pass the result to `\tl_count:n`. However, the escaping step would be quadratic in the number of characters in the string, and we can do better. Namely, sum the number of spaces (`\str_count_spaces:n`) and the result of `\tl_count:n`, which ignores spaces. `\str_count_ignore_spaces:n` Since strings tend to be longer than token lists, we use specialized functions to count characters ignoring spaces. Namely, `loop`, grabbing 9 non-space characters at each step, and end as soon as we reach one of the 9 trailing items. The internal function `_str_count:n`, used in `\str_item:nn` and `\str_range:nnn`, is similar to `\str_count_ignore_spaces:n` but expects its argument to already be a string or a string with spaces escaped.

```

3790 \cs_new:Npn \str_count:N { \exp_args:No \str_count:n }
3791 \cs_generate_variant:Nn \str_count:N { c }
3792 \cs_new:Npn \str_count:n #1
3793 {
3794   \_str_count_aux:n
3795   {
3796     \str_count_spaces:n {#1}
3797     + \exp_after:wN \_str_count_loop:NNNNNNNNN \tl_to_str:n {#1}
3798   }
3799 }
3800 \cs_new:Npn \_str_count:n #1
3801 {
3802   \_str_count_aux:n
3803   { \_str_count_loop:NNNNNNNNN #1 }
3804 }
3805 \cs_new:Npn \str_count_ignore_spaces:n #1
3806 {
3807   \_str_count_aux:n
3808   { \exp_after:wN \_str_count_loop:NNNNNNNNN \tl_to_str:n {#1} }
3809 }
3810 \cs_new:Npn \_str_count_aux:n #1
3811 {
3812   \int_eval:n
3813   {
3814     #1
3815     { X 8 } { X 7 } { X 6 }
3816     { X 5 } { X 4 } { X 3 }

```

```

3817         { X 2 } { X 1 } { X 0 }
3818         \q_stop
3819     }
3820 }
3821 \cs_new:Npn \__str_count_loop:NNNNNNNNN #1#2#3#4#5#6#7#8#9
3822 {
3823     \if_meaning:w X #9
3824     \exp_after:wN \use_none_delimit_by_q_stop:w
3825     \fi:
3826     9 + \__str_count_loop:NNNNNNNNN
3827 }

```

(End definition for `\str_count:N` and others. These functions are documented on page 50.)

6.5 The first character in a string

`\str_head:N` The `_ignore_spaces` variant applies `\tl_to_str:n` then grabs the first item, thus skipping spaces. As usual, `\str_head:N` expands its argument and hands it to `\str_head:n`.
`\str_head:c` To circumvent the fact that \TeX skips spaces when grabbing undelimited macro parameters, `__str_head:w` takes an argument delimited by a space. If `#1` starts with a non-space character, `\use_i_delimit_by_q_stop:nw` leaves that in the input stream. On the other hand, if `#1` starts with a space, the `__str_head:w` takes an empty argument, and the single (initially braced) space in the definition of `__str_head:w` makes its way to the output. Finally, for an empty argument, the (braced) empty brace group in the definition of `\str_head:n` gives an empty result after passing through `\use_i_delimit_by_q_stop:nw`.

```

3828 \cs_new:Npn \str_head:N { \exp_args:No \str_head:n }
3829 \cs_generate_variant:Nn \str_head:N { c }
3830 \cs_new:Npn \str_head:n #1
3831 {
3832     \exp_after:wN \__str_head:w
3833     \tl_to_str:n {#1}
3834     { { } } ~ \q_stop
3835 }
3836 \cs_new:Npn \__str_head:w #1 ~ %
3837 { \use_i_delimit_by_q_stop:nw #1 { ~ } }
3838 \cs_new:Npn \str_head_ignore_spaces:n #1
3839 {
3840     \exp_after:wN \use_i_delimit_by_q_stop:nw
3841     \tl_to_str:n {#1} { } \q_stop
3842 }

```

(End definition for `\str_head:N` and others. These functions are documented on page 51.)

`\str_tail:N` Getting the tail is a little bit more convoluted than the head of a string. We hit the front of the string with `\reverse_if:N \if_charcode:w \scan_stop:.` This removes the first character, and necessarily makes the test true, since the character cannot match `\scan_stop:.` The auxiliary function then inserts the required `\fi:` to close the conditional, and leaves the tail of the string in the input stream. The details are such that an empty string has an empty tail (this requires in particular that the end-marker `X` be unexpandable and not a control sequence). The `_ignore_spaces` is rather simpler: after converting the input to a string, `__str_tail_auxii:w` removes one undelimited argument and leaves

everything else until an end-marker `\q_mark`. One can check that an empty (or blank) string yields an empty tail.

```

3843 \cs_new:Npn \str_tail:N { \exp_args:No \str_tail:n }
3844 \cs_generate_variant:Nn \str_tail:N { c }
3845 \cs_new:Npn \str_tail:n #1
3846 {
3847   \exp_after:wN \__str_tail_auxi:w
3848   \reverse_if:N \if_charcode:w
3849     \scan_stop: \tl_to_str:n {#1} X X \q_stop
3850 }
3851 \cs_new:Npn \__str_tail_auxi:w #1 X #2 \q_stop { \fi: #1 }
3852 \cs_new:Npn \str_tail_ignore_spaces:n #1
3853 {
3854   \exp_after:wN \__str_tail_auxii:w
3855   \tl_to_str:n {#1} \q_mark \q_mark \q_stop
3856 }
3857 \cs_new:Npn \__str_tail_auxii:w #1 #2 \q_mark #3 \q_stop { #2 }

```

(End definition for `\str_tail:N` and others. These functions are documented on page 51.)

6.6 String manipulation

| | |
|--|--|
| <pre> \str_fold_case:n \str_fold_case:V \str_lower_case:n \str_lower_case:f \str_upper_case:n \str_upper_case:f __str_change_case:nn __str_change_case_aux:nn __str_change_case_result:n __str_change_case_output:nw __str_change_case_output:fw __str_change_case_end:nw __str_change_case_loop:nw __str_change_case_space:n __str_change_case_char:nN __str_lookup_lower:N __str_lookup_upper:N __str_lookup_fold:N </pre> | <p>Case changing for programmatic reasons is done by first detokenizing input then doing a simple loop that only has to worry about spaces and everything else. The output is detokenized to allow data sharing with text-based case changing.</p> <pre> 3858 \cs_new:Npn \str_fold_case:n #1 { __str_change_case:nn {#1} { fold } } 3859 \cs_new:Npn \str_lower_case:n #1 { __str_change_case:nn {#1} { lower } } 3860 \cs_new:Npn \str_upper_case:n #1 { __str_change_case:nn {#1} { upper } } 3861 \cs_generate_variant:Nn \str_fold_case:n { V } 3862 \cs_generate_variant:Nn \str_lower_case:n { f } 3863 \cs_generate_variant:Nn \str_upper_case:n { f } 3864 \cs_new:Npn __str_change_case:nn #1 3865 { 3866 \exp_after:wN __str_change_case_aux:nn \exp_after:wN 3867 { \tl_to_str:n {#1} } 3868 } 3869 \cs_new:Npn __str_change_case_aux:nn #1#2 3870 { 3871 __str_change_case_loop:nw {#2} #1 \q_recursion_tail \q_recursion_stop 3872 __str_change_case_result:n { } 3873 } 3874 \cs_new:Npn __str_change_case_output:nw #1#2 __str_change_case_result:n #3 3875 { #2 __str_change_case_result:n { #3 #1 } } 3876 \cs_generate_variant:Nn __str_change_case_output:nw { f } 3877 \cs_new:Npn __str_change_case_end:wn #1 __str_change_case_result:n #2 { #2 } 3878 \cs_new:Npn __str_change_case_loop:nw #1#2 \q_recursion_stop 3879 { 3880 \tl_if_head_is_space:nTF {#2} 3881 { __str_change_case_space:n } 3882 { __str_change_case_char:nN } 3883 {#1} #2 \q_recursion_stop 3884 } 3885 \use:x </pre> |
|--|--|

```

3886 { \cs_new:Npn \exp_not:N \__str_change_case_space:n ##1 \c_space_tl }
3887 {
3888   \__str_change_case_output:nw { ~ }
3889   \__str_change_case_loop:nw {#1}
3890 }
3891 \cs_new:Npn \__str_change_case_char:nN #1#2
3892 {
3893   \quark_if_recursion_tail_stop_do:Nn #2
3894   { \__str_change_case_end:wn }
3895   \cs_if_exist:cTF { c__unicode_ #1 _ #2 _tl }
3896   {
3897     \__str_change_case_output:fw
3898     { \tl_to_str:c { c__unicode_ #1 _ #2 _tl } }
3899   }
3900   { \__str_change_case_char_aux:nN {#1} #2 }
3901   \__str_change_case_loop:nw {#1}
3902 }

```

For Unicode engines there's a look up to see if the current character has a valid one-to-one case change mapping. That's not needed for 8-bit engines: as they don't have `\utex_char:D` all of the changes they can make are hard-coded and so already picked up above.

```

3903 \cs_if_exist:NTF \utex_char:D
3904 {
3905   \cs_new:Npn \__str_change_case_char_aux:nN #1#2
3906   {
3907     \int_compare:nNnTF { \use:c { __str_lookup_ #1 :N } #2 } = { 0 }
3908     { \__str_change_case_output:nw {#2} }
3909     {
3910       \__str_change_case_output:fw
3911       { \utex_char:D \use:c { __str_lookup_ #1 :N } #2 ~ }
3912     }
3913   }
3914   \cs_new_protected:Npn \__str_lookup_lower:N #1 { \tex_lccode:D '#1 }
3915   \cs_new_protected:Npn \__str_lookup_upper:N #1 { \tex_uccode:D '#1 }
3916   \cs_new_eq:NN \__str_lookup_fold:N \__str_lookup_lower:N
3917 }
3918 {
3919   \cs_new:Npn \__str_change_case_char_aux:nN #1#2
3920   { \__str_change_case_output:nw {#2} }
3921 }

```

(End definition for `\str_fold_case:n` and others. These functions are documented on page 54.)

| | |
|--|---|
| <code>\c_ampersand_str</code> <code>\c_atsign_str</code> <code>\c_backslash_str</code> <code>\c_left_brace_str</code> <code>\c_right_brace_str</code> <code>\c_circumflex_str</code> <code>\c_colon_str</code> <code>\c_dollar_str</code> <code>\c_hash_str</code> <code>\c_percent_str</code> <code>\c_tilde_str</code> <code>\c_underscore_str</code> | <p>For all of those strings, use <code>\cs_to_str:N</code> to get characters with the correct category code without worries</p> <pre> 3922 \str_const:Nx \c_ampersand_str { \cs_to_str:N & } 3923 \str_const:Nx \c_atsign_str { \cs_to_str:N @ } 3924 \str_const:Nx \c_backslash_str { \cs_to_str:N \ } 3925 \str_const:Nx \c_left_brace_str { \cs_to_str:N { } 3926 \str_const:Nx \c_right_brace_str { \cs_to_str:N } } 3927 \str_const:Nx \c_circumflex_str { \cs_to_str:N ^ } 3928 \str_const:Nx \c_colon_str { \cs_to_str:N : } 3929 \str_const:Nx \c_dollar_str { \cs_to_str:N \$ } </pre> |
|--|---|


```

3930 \str_const:Nx \c_hash_str      { \cs_to_str:N \# }
3931 \str_const:Nx \c_percent_str   { \cs_to_str:N \% }
3932 \str_const:Nx \c_tilde_str     { \cs_to_str:N \~ }
3933 \str_const:Nx \c_underscore_str { \cs_to_str:N \_ }

```

(End definition for `\c_ampersand_str` and others. These variables are documented on page 55.)

`\l_tmpa_str` Scratch strings.

```

\l_tmpb_str 3934 \str_new:N \l_tmpa_str
\g_tmpa_str 3935 \str_new:N \l_tmpb_str
\g_tmpb_str 3936 \str_new:N \g_tmpa_str
3937 \str_new:N \g_tmpb_str

```

(End definition for `\l_tmpa_str` and others. These variables are documented on page 55.)

6.7 Viewing strings

`\str_show:n` Displays a string on the terminal.

```

\str_show:n 3938 \cs_new_eq:NN \str_show:n \tl_show:n
\str_show:N 3939 \cs_new_eq:NN \str_show:N \tl_show:N
3940 \cs_generate_variant:Nn \str_show:N { c }

```

(End definition for `\str_show:n` and `\str_show:N`. These functions are documented on page 54.)

6.8 Unicode data for case changing

```

3941 <@@=unicode>

```

Case changing both for strings and “text” requires data from the Unicode Consortium. Some of this is build in to the format (as `\lccode` and `\uccode` values) but this covers only the simple one-to-one situations and does not fully handle for example case folding.

The data required for cross-module manipulations is loaded here: currently this means for `str` and `tl` functions. As such, the prefix used is not `str` but rather `unicode`. For performance (as the entire data set must be read during each run) and as this code comes somewhat early in the load process, there is quite a bit of low-level code here.

As only the data needs to remain at the end of this process, everything is set up inside a group.

```

3942 \group_begin:

```

A read stream is needed. The I/O module is not yet in place *and* we do not want to use up a stream. We therefore use a known free one in format mode or look for the next free one in package mode (covers plain, L^AT_EX 2_ε and ConT_EXt MkII and MkIV).

```

3943 <*:initex>
3944 \tex_chardef:D \g__unicode_data_ior = 0 \scan_stop:
3945 </initex>
3946 <*package>
3947 \tex_chardef:D \g__unicode_data_ior
3948 \etex_numexpr:D
3949 \cs_if_exist:NTF \lastallocatedread
3950 { \lastallocatedread }
3951 {
3952 \cs_if_exist:NTF \c_syst_last_allocated_read
3953 { \c_syst_last_allocated_read }

```

```

3954         { \tex_count:D 16 ~ }
3955     }
3956     + 1
3957     \scan_stop:
3958 \endpackage

```

Set up to read each file. As they use C-style comments, there is a need to deal with #. At the same time, spaces are important so they need to be picked up as they are important. Beyond that, the current category code scheme works fine. With no I/O loop available, hard-code one that will work quickly.

```

3959 \cs_set_protected:Npn \__unicode_map_inline:n #1
3960 {
3961     \group_begin:
3962     \tex_catcode:D '# = 12 \scan_stop:
3963     \tex_catcode:D '\ = 10 \scan_stop:
3964     \tex_openin:D \g__unicode_data_ior = #1 \scan_stop:
3965     \cs_if_exist:NT \utex_char:D
3966     { \__unicode_map_loop: }
3967     \tex_closein:D \g__unicode_data_ior
3968     \group_end:
3969 }
3970 \cs_set_protected:Npn \__unicode_map_loop:
3971 {
3972     \tex_if_eof:D \g__unicode_data_ior
3973     \exp_after:wN \use_none:n
3974     \else:
3975     \exp_after:wN \use:n
3976     \fi:
3977     {
3978         \tex_read:D \g__unicode_data_ior to \l__unicode_tmp_tl
3979         \if_meaning:w \c_empty_tl \l__unicode_tmp_tl
3980         \else:
3981         \exp_after:wN \__unicode_parse:w \l__unicode_tmp_tl \q_stop
3982         \fi:
3983         \__unicode_map_loop:
3984     }
3985 }

```

The lead-off parser for each line is common for all of the files. If the line starts with a # it's a comment. There's one special comment line to look out for in `SpecialCasing.txt` as we want to ignore everything after it. As this line does not appear in any other sources and the test is quite quick (there are relatively few comment lines), it can be present in all of the passes.

```

3986 \cs_set_protected:Npn \__unicode_parse:w #1#2 \q_stop
3987 {
3988     \reverse_if:N \if:w \c_hash_str #1
3989     \__unicode_parse_auxi:w #1#2 \q_stop
3990     \else:
3991     \if_int_compare:w \__str_if_eq_x:nn
3992     { \exp_not:n {#2} } { ~Conditional~Mappings~ } = 0 \exp_stop_f:
3993     \cs_set_protected:Npn \__unicode_parse:w ##1 \q_stop { }
3994     \fi:
3995     \fi:
3996 }

```

Storing each exception is always done in the same way: create a constant token list which expands to exactly the mapping. These will have the category codes “now” (so should be letters) but will be detokenized for string use.

```

3997 \cs_set_protected:Npn \__unicode_store:nnnnn #1#2#3#4#5
3998 {
3999   \tl_const:cx { c__unicode_ #2 _ \utex_char:D "#1 _tl }
4000   {
4001     \utex_char:D "#3 ~
4002     \utex_char:D "#4 ~
4003     \tl_if_blank:nF {#5}
4004     { \utex_char:D "#5 }
4005   }
4006 }

```

Parse the main Unicode data file for title case exceptions (the one-to-one lower and upper case mappings it contains will all be covered by the \TeX data).

```

4007 \cs_set_protected:Npn \__unicode_parse_auxi:w
4008   #1 ; #2 ; #3 ; #4 ; #5 ; #6 ; #7 ; #8 ; #9 ;
4009   { \__unicode_parse_auxii:w #1 ; }
4010 \cs_set_protected:Npn \__unicode_parse_auxii:w
4011   #1 ; #2 ; #3 ; #4 ; #5 ; #6 ; #7 \q_stop
4012   {
4013     \tl_if_blank:nF {#7}
4014     {
4015       \if_int_compare:w \__str_if_eq_x:nn { #5 ~ } {#7} = 0 \exp_stop_f:
4016       \else:
4017         \tl_const:cx
4018         { c__unicode_title_ \utex_char:D "#1 _tl }
4019         { \utex_char:D "#7 }
4020       \fi:
4021     }
4022   }
4023 \__unicode_map_inline:n { UnicodeData.txt }

```

The set up for case folding is in two parts. For the basic (core) mappings, folding is the same as lower casing in most positions so only store the differences. For the more complex foldings, always store the result, splitting up the two or three code points in the input as required.

```

4024 \cs_set_protected:Npn \__unicode_parse_auxi:w #1 ;~ #2 ;~ #3 ; #4 \q_stop
4025 {
4026   \if_int_compare:w \__str_if_eq_x:nn {#2} { C } = 0 \exp_stop_f:
4027   \if_int_compare:w \tex_lccode:D "#1 = "#3 \scan_stop:
4028   \else:
4029     \tl_const:cx
4030     { c__unicode_fold_ \utex_char:D "#1 _tl }
4031     { \utex_char:D "#3 ~ }
4032   \fi:
4033   \else:
4034     \if_int_compare:w \__str_if_eq_x:nn {#2} { F } = 0 \exp_stop_f:
4035     \__unicode_parse_auxii:w #1 ~ #3 ~ \q_stop
4036   \fi:
4037   \fi:
4038 }
4039 \cs_set_protected:Npn \__unicode_parse_auxii:w #1 ~ #2 ~ #3 ~ #4 \q_stop
4040 { \__unicode_store:nnnnn {#1} { fold } {#2} {#3} {#4} }

```

```
4041 \__unicode_map_inline:n { CaseFolding.txt }
```

For upper and lower casing special situations, there is a bit more to do as we also have title casing to consider.

```
4042 \cs_set_protected:Npn \__unicode_parse_auxii:w #1 ;~ #2 ;~ #3 ;~ #4 ; #5 \q_stop
4043 {
4044   \use:n { \__unicode_parse_auxii:w #1 ~ lower ~ #2 ~ } ~ \q_stop
4045   \use:n { \__unicode_parse_auxii:w #1 ~ upper ~ #4 ~ } ~ \q_stop
4046   \if_int_compare:w \__str_if_eq_x:nn {#3} {#4} = 0 \exp_stop_f:
4047   \else:
4048     \use:n { \__unicode_parse_auxii:w #1 ~ title ~ #3 ~ } ~ \q_stop
4049   \fi:
4050 }
4051 \cs_set_protected:Npn \__unicode_parse_auxii:w #1 ~ #2 ~ #3 ~ #4 ~ #5 \q_stop
4052 {
4053   \tl_if_empty:nF {#4}
4054   { \__unicode_store:nnnnn {#1} {#2} {#3} {#4} {#5} }
4055 }
4056 \__unicode_map_inline:n { SpecialCasing.txt }
```

For the 8-bit engines, the above does nothing but there is some set up needed. There is no expandable character generator primitive so some alternative is needed. As we’ve not used up hash space for the above, we can go for the fast approach here of one name per letter. Keeping folding and lower casing separate makes the use later a bit easier.

```
4057 \cs_if_exist:NF \utex_char:D
4058 {
4059   \cs_set_protected:Npn \__unicode_tmp:NN #1#2
4060   {
4061     \if_meaning:w \q_recursion_tail #2
4062     \exp_after:wN \use_none_delimit_by_q_recursion_stop:w
4063     \fi:
4064     \tl_const:cn { c__unicode_fold_ #1 _tl } {#2}
4065     \tl_const:cn { c__unicode_lower_ #1 _tl } {#2}
4066     \tl_const:cn { c__unicode_upper_ #2 _tl } {#1}
4067     \__unicode_tmp:NN
4068   }
4069   \__unicode_tmp:NN
4070   AaBbCcDdEeFfGgHhIiJjKkLlMmNnOoPpQqRrSsTtUuVvWwXxYyZz
4071   ? \q_recursion_tail \q_recursion_stop
4072 }
```

All done: tidy up.

```
4073 \group_end:
4074 </initex | package>
```

7 l3seq implementation

The following test files are used for this code: *m3seq002*, *m3seq003*.

```
4075 <*initex | package>
4076 <@@=seq>
```

A sequence is a control sequence whose top-level expansion is of the form “\s__seq __seq_item:n {<item₁>} ... __seq_item:n {<item_n>}”, with a leading scan mark followed by *n* items of the same form. An earlier implementation used the structure

“`\seq_elt:w <item1> \seq_elt_end: ... \seq_elt:w <itemn> \seq_elt_end:`”. This allowed rapid searching using a delimited function, but was not suitable for items containing `{`, `}` and `#` tokens, and also lead to the loss of surrounding braces around items.

`\s__seq` The variable is defined in the `l3quark` module, loaded later.

(End definition for `\s__seq`.)

`__seq_item:n` The delimiter is always defined, but when used incorrectly simply removes its argument and hits an undefined control sequence to raise an error.

```
4077 \cs_new:Npn \__seq_item:n
4078 {
4079     \__msg_kernel_expandable_error:nn { kernel } { misused-sequence }
4080     \use_none:n
4081 }
```

(End definition for `__seq_item:n`.)

`\l__seq_internal_a_tl` Scratch space for various internal uses.

```
4082 \tl_new:N \l__seq_internal_a_tl
4083 \tl_new:N \l__seq_internal_b_tl
```

(End definition for `\l__seq_internal_a_tl` and `\l__seq_internal_b_tl`.)

`__seq_tmp:w` Scratch function for internal use.

```
4084 \cs_new_eq:NN \__seq_tmp:w ?
```

(End definition for `__seq_tmp:w`.)

`\c_empty_seq` A sequence with no item, following the structure mentioned above.

```
4085 \tl_const:Nn \c_empty_seq { \s__seq }
```

(End definition for `\c_empty_seq`. This variable is documented on page 66.)

7.1 Allocation and initialisation

`\seq_new:N` Sequences are initialized to `\c_empty_seq`.

```
\seq_new:c 4086 \cs_new_protected:Npn \seq_new:N #1
4087 {
4088     \__chk_if_free_cs:N #1
4089     \cs_gset_eq:NN #1 \c_empty_seq
4090 }
4091 \cs_generate_variant:Nn \seq_new:N { c }
```

(End definition for `\seq_new:N`. This function is documented on page 57.)

`\seq_clear:N` Clearing a sequence is similar to setting it equal to the empty one.

```
\seq_clear:c 4092 \cs_new_protected:Npn \seq_clear:N #1
\seq_gclear:N 4093 { \seq_set_eq:NN #1 \c_empty_seq }
\seq_gclear:c 4094 \cs_generate_variant:Nn \seq_clear:N { c }
4095 \cs_new_protected:Npn \seq_gclear:N #1
4096 { \seq_gset_eq:NN #1 \c_empty_seq }
4097 \cs_generate_variant:Nn \seq_gclear:N { c }
```

(End definition for `\seq_clear:N` and `\seq_gclear:N`. These functions are documented on page 57.)

```

\seq_clear_new:N Once again we copy code from the token list functions.
\seq_clear_new:c 4098 \cs_new_protected:Npn \seq_clear_new:N #1
\seq_gclear_new:N 4099 { \seq_if_exist:NTF #1 { \seq_clear:N #1 } { \seq_new:N #1 } }
\seq_gclear_new:c 4100 \cs_generate_variant:Nn \seq_clear_new:N { c }
4101 \cs_new_protected:Npn \seq_gclear_new:N #1
4102 { \seq_if_exist:NTF #1 { \seq_gclear:N #1 } { \seq_new:N #1 } }
4103 \cs_generate_variant:Nn \seq_gclear_new:N { c }

```

(End definition for `\seq_clear_new:N` and `\seq_gclear_new:N`. These functions are documented on page 57.)

```

\seq_set_eq:NN Copying a sequence is the same as copying the underlying token list.
\seq_set_eq:cN 4104 \cs_new_eq:NN \seq_set_eq:NN \tl_set_eq:NN
\seq_set_eq:Nc 4105 \cs_new_eq:NN \seq_set_eq:Nc \tl_set_eq:Nc
\seq_set_eq:cc 4106 \cs_new_eq:NN \seq_set_eq:cN \tl_set_eq:cN
\seq_gset_eq:NN 4107 \cs_new_eq:NN \seq_set_eq:cc \tl_set_eq:cc
\seq_gset_eq:cN 4108 \cs_new_eq:NN \seq_gset_eq:NN \tl_gset_eq:NN
\seq_gset_eq:Nc 4109 \cs_new_eq:NN \seq_gset_eq:Nc \tl_gset_eq:Nc
\seq_gset_eq:cN 4110 \cs_new_eq:NN \seq_gset_eq:cN \tl_gset_eq:cN
\seq_gset_eq:cc 4111 \cs_new_eq:NN \seq_gset_eq:cc \tl_gset_eq:cc

```

(End definition for `\seq_set_eq:NN` and `\seq_gset_eq:NN`. These functions are documented on page 57.)

```

\seq_set_from_clist:NN Setting a sequence from a comma-separated list is done using a simple mapping.
\seq_set_from_clist:cN 4112 \cs_new_protected:Npn \seq_set_from_clist:NN #1#2
\seq_set_from_clist:Nc 4113 {
\seq_set_from_clist:cc 4114   \tl_set:Nx #1
\seq_set_from_clist:Nn 4115   { \s__seq \clist_map_function:NN #2 \__seq_wrap_item:n }
\seq_set_from_clist:cn 4116 }
\seq_gset_from_clist:NN 4117 \cs_new_protected:Npn \seq_set_from_clist:Nn #1#2
\seq_gset_from_clist:cN 4118 {
\seq_gset_from_clist:Nc 4119   \tl_set:Nx #1
\seq_gset_from_clist:Nn 4120   { \s__seq \clist_map_function:nN {#2} \__seq_wrap_item:n }
\seq_gset_from_clist:cc 4121 }
\seq_gset_from_clist:Nn 4122 \cs_new_protected:Npn \seq_gset_from_clist:NN #1#2
\seq_gset_from_clist:cn 4123 {
4124   \tl_gset:Nx #1
4125   { \s__seq \clist_map_function:NN #2 \__seq_wrap_item:n }
4126 }
4127 \cs_new_protected:Npn \seq_gset_from_clist:Nn #1#2
4128 {
4129   \tl_gset:Nx #1
4130   { \s__seq \clist_map_function:nN {#2} \__seq_wrap_item:n }
4131 }
4132 \cs_generate_variant:Nn \seq_set_from_clist:NN { Nc }
4133 \cs_generate_variant:Nn \seq_set_from_clist:NN { c , cc }
4134 \cs_generate_variant:Nn \seq_set_from_clist:Nn { c }
4135 \cs_generate_variant:Nn \seq_gset_from_clist:NN { Nc }
4136 \cs_generate_variant:Nn \seq_gset_from_clist:NN { c , cc }
4137 \cs_generate_variant:Nn \seq_gset_from_clist:Nn { c }

```

(End definition for `\seq_set_from_clist:NN` and others. These functions are documented on page 57.)

`\seq_set_split:Nnn` When the separator is empty, everything is very simple, just map `__seq_wrap_item:n`
`\seq_set_split:NnV` through the items of the last argument. For non-trivial separators, the goal is to split
`\seq_gset_split:Nnn` a given token list at the marker, strip spaces from each item, and remove one set of
`\seq_gset_split:NnV` outer braces if after removing leading and trailing spaces the item is enclosed within
`__seq_set_split:Nnn` braces. After `\tl_replace_all:Nnn`, the token list `\l__seq_internal_a_tl` is a repe-
`__seq_set_split_auxi:w` tition of the pattern `__seq_set_split_auxi:w \prg_do_nothing: <item with spaces>`
`__seq_set_split_auxii:w` `__seq_set_split_end:.` Then, x-expansion causes `__seq_set_split_auxi:w` to trim
`__seq_set_split_end:` spaces, and leaves its result as `__seq_set_split_auxii:w <trimmed item> __seq-`
`__seq_set_split_end:` `set_split_end:.` This is then converted to the l3seq internal structure by another x-
expansion. In the first step, we insert `\prg_do_nothing:` to avoid losing braces too early:
that would cause space trimming to act within those lost braces. The second step is solely
there to strip braces which are outermost after space trimming.

```

4138 \cs_new_protected:Npn \seq_set_split:Nnn
4139 { \__seq_set_split:Nnn \tl_set:Nx }
4140 \cs_new_protected:Npn \seq_gset_split:Nnn
4141 { \__seq_set_split:Nnn \tl_gset:Nx }
4142 \cs_new_protected:Npn \__seq_set_split:Nnn #1#2#3#4
4143 {
4144   \tl_if_empty:nTF {#3}
4145   {
4146     \tl_set:Nn \l__seq_internal_a_tl
4147     { \tl_map_function:nN {#4} \__seq_wrap_item:n }
4148   }
4149   {
4150     \tl_set:Nn \l__seq_internal_a_tl
4151     {
4152       \__seq_set_split_auxi:w \prg_do_nothing:
4153       #4
4154       \__seq_set_split_end:
4155     }
4156     \tl_replace_all:Nnn \l__seq_internal_a_tl { #3 }
4157     {
4158       \__seq_set_split_end:
4159       \__seq_set_split_auxi:w \prg_do_nothing:
4160     }
4161     \tl_set:Nx \l__seq_internal_a_tl { \l__seq_internal_a_tl }
4162   }
4163   #1 #2 { \s__seq \l__seq_internal_a_tl }
4164 }
4165 \cs_new:Npn \__seq_set_split_auxi:w #1 \__seq_set_split_end:
4166 {
4167   \exp_not:N \__seq_set_split_auxii:w
4168   \exp_args:No \tl_trim_spaces:n {#1}
4169   \exp_not:N \__seq_set_split_end:
4170 }
4171 \cs_new:Npn \__seq_set_split_auxii:w #1 \__seq_set_split_end:
4172 { \__seq_wrap_item:n {#1} }
4173 \cs_generate_variant:Nn \seq_set_split:Nnn { NnV }
4174 \cs_generate_variant:Nn \seq_gset_split:Nnn { NnV }

```

(End definition for `\seq_set_split:Nnn` and others. These functions are documented on page 58.)

`\seq_concat:NNN` When concatenating sequences, one must remove the leading `\s__seq` of the second
`\seq_concat:ccc`
`\seq_gconcat:NNN`
`\seq_gconcat:ccc`

sequence. The result starts with `\s__seq` (of the first sequence), which stops `f`-expansion.

```

4175 \cs_new_protected:Npn \seq_concat:NNN #1#2#3
4176 { \tl_set:Nf #1 { \exp_after:wN \use_i:nn \exp_after:wN #2 #3 } }
4177 \cs_new_protected:Npn \seq_gconcat:NNN #1#2#3
4178 { \tl_gset:Nf #1 { \exp_after:wN \use_i:nn \exp_after:wN #2 #3 } }
4179 \cs_generate_variant:Nn \seq_concat:NNN { ccc }
4180 \cs_generate_variant:Nn \seq_gconcat:NNN { ccc }

```

(End definition for `\seq_concat:NNN` and `\seq_gconcat:NNN`. These functions are documented on page 58.)

```

\seq_if_exist_p:N Copies of the cs functions defined in l3basics.
\seq_if_exist_p:c
\seq_if_exist:NTF
\seq_if_exist:cTF
4181 \prg_new_eq_conditional:NNn \seq_if_exist:N \cs_if_exist:N
4182 { TF , T , F , p }
4183 \prg_new_eq_conditional:NNn \seq_if_exist:c \cs_if_exist:c
4184 { TF , T , F , p }

```

(End definition for `\seq_if_exist:N`. This function is documented on page 58.)

7.2 Appending data to either end

```

\seq_put_left:Nn When adding to the left of a sequence, remove \s__seq. This is done by \__seq_put_
\seq_put_left:NV left_aux:w, which also stops f-expansion.
\seq_put_left:Nv
\seq_put_left:No
\seq_put_left:Nx
\seq_put_left:cn
\seq_put_left:cV
\seq_put_left:cv
\seq_put_left:co
\seq_put_left:cx
4185 \cs_new_protected:Npn \seq_put_left:Nn #1#2
4186 {
4187   \tl_set:Nx #1
4188   {
4189     \exp_not:n { \s__seq \__seq_item:n {#2} }
4190     \exp_not:f { \exp_after:wN \__seq_put_left_aux:w #1 }
4191   }
4192 }
4193 \cs_new_protected:Npn \seq_gput_left:Nn #1#2
4194 {
4195   \tl_gset:Nx #1
4196   {
4197     \exp_not:n { \s__seq \__seq_item:n {#2} }
4198     \exp_not:f { \exp_after:wN \__seq_put_left_aux:w #1 }
4199   }
4200 }
4201 \cs_new:Npn \__seq_put_left_aux:w \s__seq { \exp_stop_f: }
4202 \cs_generate_variant:Nn \seq_put_left:Nn { NV , Nv , No , Nx }
4203 \cs_generate_variant:Nn \seq_put_left:Nn { c , cV , cv , co , cx }
4204 \cs_generate_variant:Nn \seq_gput_left:Nn { NV , Nv , No , Nx }
4205 \cs_generate_variant:Nn \seq_gput_left:Nn { c , cV , cv , co , cx }
\__seq_put_left_aux:w

```

(End definition for `\seq_put_left:Nn`, `\seq_gput_left:Nn`, and `__seq_put_left_aux:w`. These functions are documented on page 58.)

```

\seq_put_right:Nn Since there is no trailing marker, adding an item to the right of a sequence simply means
\seq_put_right:NV wrapping it in \__seq_item:n.
\seq_put_right:Nv
\seq_put_right:No
\seq_put_right:Nx
\seq_put_right:cn
\seq_put_right:cV
\seq_put_right:cv
\seq_put_right:co
\seq_put_right:cx
4206 \cs_new_protected:Npn \seq_put_right:Nn #1#2
4207 { \tl_put_right:Nn #1 { \__seq_item:n {#2} } }
4208 \cs_new_protected:Npn \seq_gput_right:Nn #1#2
4209 { \tl_gput_right:Nn #1 { \__seq_item:n {#2} } }
\seq_gput_right:Nn
\seq_gput_right:NV
\seq_gput_right:Nv
\seq_gput_right:No
\seq_gput_right:Nx
\seq_gput_right:cn

```



```

4210 \cs_generate_variant:Nn \seq_gput_right:Nn { NV , Nv , No , Nx }
4211 \cs_generate_variant:Nn \seq_gput_right:Nn { c , cV , cv , co , cx }
4212 \cs_generate_variant:Nn \seq_put_right:Nn { NV , Nv , No , Nx }
4213 \cs_generate_variant:Nn \seq_put_right:Nn { c , cV , cv , co , cx }

```

(End definition for `\seq_put_right:Nn` and `\seq_gput_right:Nn`. These functions are documented on page 58.)

7.3 Modifying sequences

`__seq_wrap_item:n` This function converts its argument to a proper sequence item in an x-expansion context.

```

4214 \cs_new:Npn \__seq_wrap_item:n #1 { \exp_not:n { \__seq_item:n {#1} } }

```

(End definition for `__seq_wrap_item:n`.)

`\l__seq_remove_seq` An internal sequence for the removal routines.

```

4215 \seq_new:N \l__seq_remove_seq

```

(End definition for `\l__seq_remove_seq`.)

`\seq_remove_duplicates:N` Removing duplicates means making a new list then copying it.

`\seq_remove_duplicates:c`

`\seq_gremove_duplicates:N`

`\seq_gremove_duplicates:c`

`__seq_remove_duplicates:NN`

```

4216 \cs_new_protected:Npn \seq_remove_duplicates:N
4217 { \__seq_remove_duplicates:NN \seq_set_eq:NN }
4218 \cs_new_protected:Npn \seq_gremove_duplicates:N
4219 { \__seq_remove_duplicates:NN \seq_gset_eq:NN }
4220 \cs_new_protected:Npn \__seq_remove_duplicates:NN #1#2
4221 {
4222   \seq_clear:N \l__seq_remove_seq
4223   \seq_map_inline:Nn #2
4224   {
4225     \seq_if_in:NnF \l__seq_remove_seq {##1}
4226     { \seq_put_right:Nn \l__seq_remove_seq {##1} }
4227   }
4228   #1 #2 \l__seq_remove_seq
4229 }
4230 \cs_generate_variant:Nn \seq_remove_duplicates:N { c }
4231 \cs_generate_variant:Nn \seq_gremove_duplicates:N { c }

```

(End definition for `\seq_remove_duplicates:N`, `\seq_gremove_duplicates:N`, and `__seq_remove_duplicates:NN`. These functions are documented on page 61.)

`\seq_remove_all:Nn` The idea of the code here is to avoid a relatively expensive addition of items one at

`\seq_remove_all:cn` a time to an intermediate sequence. The approach taken is therefore similar to that

`\seq_gremove_all:Nn` in `__seq_pop_right:NNN`, using a “flexible” x-type expansion to do most of the work.

`\seq_gremove_all:cn` As `\tl_if_eq:nnT` is not expandable, a two-part strategy is needed. First, the x-type

`__seq_remove_all_aux:NNn` expansion uses `\str_if_eq:nnT` to find potential matches. If one is found, the expansion is halted and the necessary set up takes place to use the `\tl_if_eq:NNT` test. The x-type is started again, including all of the items copied already. This will happen repeatedly until the entire sequence has been scanned. The code is set up to avoid needing and intermediate scratch list: the lead-off x-type expansion (`#1 #2 {#2}`) will ensure that nothing is lost.

```

4232 \cs_new_protected:Npn \seq_remove_all:Nn
4233 { \__seq_remove_all_aux:NNn \tl_set:Nx }
4234 \cs_new_protected:Npn \seq_gremove_all:Nn

```

```

4235 { \_seq_remove_all_aux:NNn \tl_gset:Nx }
4236 \cs_new_protected:Npn \_seq_remove_all_aux:NNn #1#2#3
4237 {
4238   \_seq_push_item_def:n
4239   {
4240     \str_if_eq:nnT {##1} {#3}
4241     {
4242       \if_false: { \fi: }
4243       \tl_set:Nn \l__seq_internal_b_tl {##1}
4244       #1 #2
4245       { \if_false: } \fi:
4246       \exp_not:o {#2}
4247       \tl_if_eq:NNT \l__seq_internal_a_tl \l__seq_internal_b_tl
4248       { \use_none:n }
4249     }
4250     \_seq_wrap_item:n {##1}
4251   }
4252   \tl_set:Nn \l__seq_internal_a_tl {#3}
4253   #1 #2 {#2}
4254   \_seq_pop_item_def:
4255 }
4256 \cs_generate_variant:Nn \seq_remove_all:Nn { c }
4257 \cs_generate_variant:Nn \seq_gremove_all:Nn { c }

```

(End definition for `\seq_remove_all:Nn`, `\seq_gremove_all:Nn`, and `_seq_remove_all_aux:NNn`. These functions are documented on page 61.)

```

\seq_reverse:N Previously, \seq_reverse:N was coded by collecting the items in reverse order after an
\seq_reverse:c \exp_stop_f: marker.
\seq_greverse:N
\seq_greverse:c \cs_new_protected:Npn \seq_reverse:N #1
\__seq_reverse:NN {
\_seq_reverse_item:nwn \cs_set_eq:NN \@_item:n \@_reverse_item:nw
\__seq_reverse_item:nwn \tl_set:Nf #2 { #2 \exp_stop_f: }
}
\cs_new:Npn \@_reverse_item:nw #1 #2 \exp_stop_f:
{
#2 \exp_stop_f:
\@_item:n {#1}
}

```

At first, this seems optimal, since we can forget about each item as soon as it is placed after `\exp_stop_f:`. Unfortunately, TeX's usual tail recursion does not take place in this case: since the following `_seq_reverse_item:nw` only reads tokens until `\exp_stop_f:`, and never reads the `\@_item:n {#1}` left by the previous call, TeX cannot remove that previous call from the stack, and in particular must retain the various macro parameters in memory, until the end of the replacement text is reached. The stack is thus only flushed after all the `_seq_reverse_item:nw` are expanded. Keeping track of the arguments of all those calls uses up a memory quadratic in the length of the sequence. TeX can then not cope with more than a few thousand items.

Instead, we collect the items in the argument of `\exp_not:n`. The previous calls are cleanly removed from the stack, and the memory consumption becomes linear.

```

4258 \cs_new_protected:Npn \seq_reverse:N

```

```

4259 { \__seq_reverse:NN \tl_set:Nx }
4260 \cs_new_protected:Npn \seq_greverse:N
4261 { \__seq_reverse:NN \tl_gset:Nx }
4262 \cs_new_protected:Npn \__seq_reverse:NN #1 #2
4263 {
4264   \cs_set_eq:NN \__seq_tmp:w \__seq_item:n
4265   \cs_set_eq:NN \__seq_item:n \__seq_reverse_item:nwn
4266   #1 #2 { #2 \exp_not:n { } }
4267   \cs_set_eq:NN \__seq_item:n \__seq_tmp:w
4268 }
4269 \cs_new:Npn \__seq_reverse_item:nwn #1 #2 \exp_not:n #3
4270 {
4271   #2
4272   \exp_not:n { \__seq_item:n {#1} #3 }
4273 }
4274 \cs_generate_variant:Nn \seq_reverse:N { c }
4275 \cs_generate_variant:Nn \seq_greverse:N { c }

```

(End definition for `\seq_reverse:N` and others. These functions are documented on page 61.)

`\seq_sort:Nn` Implemented in `l3sort`.

`\seq_sort:cn`

(End definition for `\seq_sort:Nn` and `\seq_gsort:Nn`. These functions are documented on page 61.)

`\seq_gsort:Nn`

`\seq_gsort:cn`

7.4 Sequence conditionals

`\seq_if_empty_p:N` Similar to token lists, we compare with the empty sequence.

`\seq_if_empty_p:c`

`\seq_if_empty:NTF`

`\seq_if_empty:cTF`

```

4276 \prg_new_conditional:Npnn \seq_if_empty:N #1 { p , T , F , TF }
4277 {
4278   \if_meaning:w #1 \c_empty_seq
4279   \prg_return_true:
4280   \else:
4281     \prg_return_false:
4282   \fi:
4283 }
4284 \cs_generate_variant:Nn \seq_if_empty_p:N { c }
4285 \cs_generate_variant:Nn \seq_if_empty:NT { c }
4286 \cs_generate_variant:Nn \seq_if_empty:NF { c }
4287 \cs_generate_variant:Nn \seq_if_empty:NTF { c }

```

(End definition for `\seq_if_empty:NTF`. This function is documented on page 61.)

`\seq_if_in:NnTF` The approach here is to define `__seq_item:n` to compare its argument with the test sequence. If the two items are equal, the mapping is terminated and `\group_end: \prg_return_true:` is inserted after skipping over the rest of the recursion. On the other hand, if there is no match then the loop will break returning `\prg_return_false:`. Everything is inside a group so that `__seq_item:n` is preserved in nested situations.

`\seq_if_in:cnTF`

`\seq_if_in:cVTF`

`\seq_if_in:cvTF`

`\seq_if_in:coTF`

`\seq_if_in:cxTF`

`__seq_if_in:`

```

4288 \prg_new_protected_conditional:Npnn \seq_if_in:Nn #1#2
4289 { T , F , TF }
4290 {
4291   \group_begin:
4292     \tl_set:Nn \l__seq_internal_a_tl {#2}
4293     \cs_set_protected:Npn \__seq_item:n ##1
4294     {

```

```

4295         \tl_set:Nn \l__seq_internal_b_tl {##1}
4296         \if_meaning:w \l__seq_internal_a_tl \l__seq_internal_b_tl
4297             \exp_after:wN \__seq_if_in:
4298         \fi:
4299     }
4300     #1
4301     \group_end:
4302     \prg_return_false:
4303     \__prg_break_point:
4304 }
4305 \cs_new:Npn \__seq_if_in:
4306 { \__prg_break:n { \group_end: \prg_return_true: } }
4307 \cs_generate_variant:Nn \seq_if_in:NnT { NV , Nv , No , Nx }
4308 \cs_generate_variant:Nn \seq_if_in:NnT { c , cV , cv , co , cx }
4309 \cs_generate_variant:Nn \seq_if_in:NnF { NV , Nv , No , Nx }
4310 \cs_generate_variant:Nn \seq_if_in:NnF { c , cV , cv , co , cx }
4311 \cs_generate_variant:Nn \seq_if_in:NnTF { NV , Nv , No , Nx }
4312 \cs_generate_variant:Nn \seq_if_in:NnTF { c , cV , cv , co , cx }

```

(End definition for `\seq_if_in:NnTF` and `__seq_if_in:`. These functions are documented on page 61.)

7.5 Recovering data from sequences

`__seq_pop:NNNN` The two `pop` functions share their emptiness tests. We also use a common emptiness test
`__seq_pop_TF:NNNN` for all branching `get` and `pop` functions.

```

4313 \cs_new_protected:Npn \__seq_pop:NNNN #1#2#3#4
4314 {
4315     \if_meaning:w #3 \c_empty_seq
4316         \tl_set:Nn #4 { \q_no_value }
4317     \else:
4318         #1#2#3#4
4319     \fi:
4320 }
4321 \cs_new_protected:Npn \__seq_pop_TF:NNNN #1#2#3#4
4322 {
4323     \if_meaning:w #3 \c_empty_seq
4324         % \tl_set:Nn #4 { \q_no_value }
4325         \prg_return_false:
4326     \else:
4327         #1#2#3#4
4328         \prg_return_true:
4329     \fi:
4330 }

```

(End definition for `__seq_pop:NNNN` and `__seq_pop_TF:NNNN`.)

`\seq_get_left:NN` Getting an item from the left of a sequence is pretty easy: just trim off the first item
`\seq_get_left:cN` after `__seq_item:n` at the start. We append a `\q_no_value` item to cover the case of
`__seq_get_left:wnw` an empty sequence

```

4331 \cs_new_protected:Npn \seq_get_left:NN #1#2
4332 {
4333     \tl_set:Nx #2
4334     {
4335         \exp_after:wN \__seq_get_left:wnw

```

```

4336         #1 \__seq_item:n { \q_no_value } \q_stop
4337     }
4338 }
4339 \cs_new:Npn \__seq_get_left:wnw #1 \__seq_item:n #2#3 \q_stop
4340 { \exp_not:n {#2} }
4341 \cs_generate_variant:Nn \seq_get_left:NN { c }

```

(End definition for `\seq_get_left:NN` and `__seq_get_left:wnw`. These functions are documented on page 58.)

```

\seq_pop_left:NN The approach to popping an item is pretty similar to that to get an item, with the only
\seq_pop_left:cN difference being that the sequence itself has to be redefined. This makes it more sensible
\seq_gpop_left:NN to use an auxiliary function for the local and global cases.
\seq_gpop_left:cN
\__seq_pop_left:NNN
\__seq_pop_left:wnwNNN
4342 \cs_new_protected:Npn \seq_pop_left:NN
4343 { \__seq_pop:NNNN \__seq_pop_left:NNN \tl_set:Nn }
4344 \cs_new_protected:Npn \seq_gpop_left:NN
4345 { \__seq_pop:NNNN \__seq_pop_left:NNN \tl_gset:Nn }
4346 \cs_new_protected:Npn \__seq_pop_left:NNN #1#2#3
4347 { \exp_after:wN \__seq_pop_left:wnwNNN #2 \q_stop #1#2#3 }
4348 \cs_new_protected:Npn \__seq_pop_left:wnwNNN
4349 #1 \__seq_item:n #2#3 \q_stop #4#5#6
4350 {
4351     #4 #5 { #1 #3 }
4352     \tl_set:Nn #6 {#2}
4353 }
4354 \cs_generate_variant:Nn \seq_pop_left:NN { c }
4355 \cs_generate_variant:Nn \seq_gpop_left:NN { c }

```

(End definition for `\seq_pop_left:NN` and others. These functions are documented on page 59.)

```

\seq_get_right:NN First remove \s__seq and prepend \q_no_value, then take two arguments at a time.
\seq_get_right:cN Before the right-hand end of the sequence, this is a brace group followed by \__seq_
\__seq_get_right_loop:nn item:n, both removed by \use_none:nn. At the end of the sequence, the two question
marks are taken by \use_none:nn, and the assignment is placed before the right-most
item. In the next iteration, \__seq_get_right_loop:nn receives two empty arguments,
and \use_none:nn stops the loop.

```

```

4356 \cs_new_protected:Npn \seq_get_right:NN #1#2
4357 {
4358     \exp_after:wN \use_i_ii:nnn
4359     \exp_after:wN \__seq_get_right_loop:nn
4360     \exp_after:wN \q_no_value
4361     #1
4362     { ?? \tl_set:Nn #2 }
4363     { } { }
4364 }
4365 \cs_new_protected:Npn \__seq_get_right_loop:nn #1#2
4366 {
4367     \use_none:nn #2 {#1}
4368     \__seq_get_right_loop:nn
4369 }
4370 \cs_generate_variant:Nn \seq_get_right:NN { c }

```

(End definition for `\seq_get_right:NN` and `__seq_get_right_loop:nn`. These functions are documented on page 59.)

`\seq_pop_right:NN` The approach to popping from the right is a bit more involved, but does use some
`\seq_pop_right:cN` of the same ideas as getting from the right. What is needed is a “flexible length”
`\seq_gpop_right:NN` way to set a token list variable. This is supplied by the `{ \if_false: } \fi:`
`\seq_gpop_right:cN` `... \if_false: { \fi: }` construct. Using an x-type expansion and a “non-expanding”
`__seq_pop_right:NNN` definition for `__seq_item:n`, the left-most $n - 1$ entries in a sequence of n items will
`__seq_pop_right_loop:nn` be stored back in the sequence. That needs a loop of unknown length, hence using the
strange `\if_false:` way of including braces. When the last item of the sequence is
reached, the closing brace for the assignment is inserted, and `\tl_set:Nn #3` is inserted
in front of the final entry. This therefore does the pop assignment. One more iteration
is performed, with an empty argument and `\use_none:nn`, which finally stops the loop.

```

4371 \cs_new_protected:Npn \seq_pop_right:NN
4372 { \__seq_pop:NNNN \__seq_pop_right:NNN \tl_set:Nx }
4373 \cs_new_protected:Npn \seq_gpop_right:NN
4374 { \__seq_pop:NNNN \__seq_pop_right:NNN \tl_gset:Nx }
4375 \cs_new_protected:Npn \__seq_pop_right:NNN #1#2#3
4376 {
4377   \cs_set_eq:NN \__seq_tmp:w \__seq_item:n
4378   \cs_set_eq:NN \__seq_item:n \scan_stop:
4379   #1 #2
4380   { \if_false: } \fi: \s__seq
4381     \exp_after:wN \use_i:nnn
4382     \exp_after:wN \__seq_pop_right_loop:nn
4383     #2
4384     {
4385       \if_false: { \fi: }
4386       \tl_set:Nx #3
4387     }
4388     { } \use_none:nn
4389     \cs_set_eq:NN \__seq_item:n \__seq_tmp:w
4390   }
4391   \cs_new:Npn \__seq_pop_right_loop:nn #1#2
4392   {
4393     #2 { \exp_not:n {#1} }
4394     \__seq_pop_right_loop:nn
4395   }
4396   \cs_generate_variant:Nn \seq_pop_right:NN { c }
4397   \cs_generate_variant:Nn \seq_gpop_right:NN { c }

```

(End definition for `\seq_pop_right:NN` and others. These functions are documented on page 59.)

`\seq_get_left:NNTF` Getting from the left or right with a check on the results. The first argument to `__-`
`\seq_get_left:cNTF` `seq_pop_TF:NNNN` is left unused.

```

4398 \prg_new_protected_conditional:Npnn \seq_get_left:NN #1#2 { T , F , TF }
4399 { \__seq_pop_TF:NNNN \prg_do_nothing: \seq_get_left:NN #1#2 }
4400 \prg_new_protected_conditional:Npnn \seq_get_right:NN #1#2 { T , F , TF }
4401 { \__seq_pop_TF:NNNN \prg_do_nothing: \seq_get_right:NN #1#2 }
4402 \cs_generate_variant:Nn \seq_get_left:NNT { c }
4403 \cs_generate_variant:Nn \seq_get_left:NNF { c }
4404 \cs_generate_variant:Nn \seq_get_left:NNTF { c }
4405 \cs_generate_variant:Nn \seq_get_right:NNT { c }
4406 \cs_generate_variant:Nn \seq_get_right:NNF { c }
4407 \cs_generate_variant:Nn \seq_get_right:NNTF { c }

```

(End definition for \seq_get_left:NNTF and \seq_get_right:NNTF. These functions are documented on page 60.)

\seq_pop_left:NNTF More or less the same for popping.
\seq_pop_left:cNTF
\seq_gpop_left:NNTF
\seq_gpop_left:cNTF
\seq_pop_right:NNTF
\seq_pop_right:cNTF
\seq_gpop_right:NNTF
\seq_gpop_right:cNTF

```

4408 \prg_new_protected_conditional:Npnn \seq_pop_left:NN #1#2 { T , F , TF }
4409 { \__seq_pop_TF:NNTN \__seq_pop_left:NN \tl_set:Nn #1 #2 }
4410 \prg_new_protected_conditional:Npnn \seq_gpop_left:NN #1#2 { T , F , TF }
4411 { \__seq_pop_TF:NNTN \__seq_pop_left:NN \tl_gset:Nn #1 #2 }
4412 \prg_new_protected_conditional:Npnn \seq_pop_right:NN #1#2 { T , F , TF }
4413 { \__seq_pop_TF:NNTN \__seq_pop_right:NN \tl_set:Nx #1 #2 }
4414 \prg_new_protected_conditional:Npnn \seq_gpop_right:NN #1#2 { T , F , TF }
4415 { \__seq_pop_TF:NNTN \__seq_pop_right:NN \tl_gset:Nx #1 #2 }
4416 \cs_generate_variant:Nn \seq_pop_left:NNT { c }
4417 \cs_generate_variant:Nn \seq_pop_left:NNTF { c }
4418 \cs_generate_variant:Nn \seq_gpop_left:NNT { c }
4419 \cs_generate_variant:Nn \seq_gpop_left:NNTF { c }
4420 \cs_generate_variant:Nn \seq_gpop_left:NNTF { c }
4421 \cs_generate_variant:Nn \seq_gpop_left:NNTF { c }
4422 \cs_generate_variant:Nn \seq_pop_right:NNT { c }
4423 \cs_generate_variant:Nn \seq_pop_right:NNTF { c }
4424 \cs_generate_variant:Nn \seq_gpop_right:NNT { c }
4425 \cs_generate_variant:Nn \seq_gpop_right:NNTF { c }
4426 \cs_generate_variant:Nn \seq_gpop_right:NNTF { c }
4427 \cs_generate_variant:Nn \seq_gpop_right:NNTF { c }

```

(End definition for \seq_pop_left:NNTF and others. These functions are documented on page 60.)

\seq_item:Nn The idea here is to find the offset of the item from the left, then use a loop
\seq_item:cn to grab the correct item. If the resulting offset is too large, then the stop code
__seq_item:wNn { ? __prg_break: } { } will be used by the auxiliary, terminating the loop and re-
__seq_item:nN turning nothing at all.
__seq_item:nnn

```

4428 \cs_new:Npn \seq_item:Nn #1
4429 { \exp_after:wN \__seq_item:wNn #1 \q_stop #1 }
4430 \cs_new:Npn \__seq_item:wNn \s__seq #1 \q_stop #2#3
4431 {
4432   \exp_args:Nf \__seq_item:nnn
4433   { \exp_args:Nf \__seq_item:nN { \int_eval:n {#3} } #2 }
4434   #1
4435   { ? \__prg_break: } { }
4436   \__prg_break_point:
4437 }
4438 \cs_new:Npn \__seq_item:nN #1#2
4439 {
4440   \int_compare:nNnTF {#1} < 0
4441   { \int_eval:n { \seq_count:N #2 + 1 + #1 } }
4442   {#1}
4443 }
4444 \cs_new:Npn \__seq_item:nnn #1#2#3
4445 {
4446   \use_none:n #2
4447   \int_compare:nNnTF {#1} = 1
4448   { \__prg_break:n { \exp_not:n {#3} } }
4449   { \exp_args:Nf \__seq_item:nnn { \int_eval:n { #1 - 1 } } }
4450 }
4451 \cs_generate_variant:Nn \seq_item:Nn { c }

```

(End definition for `\seq_item:Nn` and others. These functions are documented on page 59.)

7.6 Mapping to sequences

`\seq_map_break:` To break a function, the special token `__prg_break_point:Nn` is used to find the end of the code. Any ending code is then inserted before the return value of `\seq_map_break:n` is inserted.

```

4452 \cs_new:Npn \seq_map_break:
4453   { \__prg_map_break:Nn \seq_map_break: { } }
4454 \cs_new:Npn \seq_map_break:n
4455   { \__prg_map_break:Nn \seq_map_break: }
```

(End definition for `\seq_map_break:` and `\seq_map_break:n`. These functions are documented on page 62.)

`\seq_map_function:NN` The idea here is to apply the code of #2 to each item in the sequence without altering the definition of `__seq_item:n`. This is done as by noting that every odd token in the sequence must be `__seq_item:n`, which can be gobbled by `\use_none:n`. At the end of the loop, #2 is instead `? \seq_map_break:`, which therefore breaks the loop without needing to do a (relatively-expensive) quark test.

```

4456 \cs_new:Npn \seq_map_function:NN #1#2
4457   {
4458     \exp_after:wN \use_i_ii:nnn
4459     \exp_after:wN \__seq_map_function:NNn
4460     \exp_after:wN #2
4461     #1
4462     { ? \seq_map_break: } { }
4463     \__prg_break_point:Nn \seq_map_break: { }
4464   }
4465 \cs_new:Npn \__seq_map_function:NNn #1#2#3
4466   {
4467     \use_none:n #2
4468     #1 {#3}
4469     \__seq_map_function:NNn #1
4470   }
4471 \cs_generate_variant:Nn \seq_map_function:NN { c }
```

(End definition for `\seq_map_function:NN` and `__seq_map_function:NNn`. These functions are documented on page 61.)

`__seq_push_item_def:n` The definition of `__seq_item:n` needs to be saved and restored at various points within the mapping and manipulation code. That is handled here: as always, this approach uses global assignments.

```

\__seq_push_item_def:x
\__seq_push_item_def:
\__seq_pop_item_def:
4472 \cs_new_protected:Npn \__seq_push_item_def:n
4473   {
4474     \__seq_push_item_def:
4475     \cs_gset:Npn \__seq_item:n ##1
4476   }
4477 \cs_new_protected:Npn \__seq_push_item_def:x
4478   {
4479     \__seq_push_item_def:
4480     \cs_gset:Npx \__seq_item:n ##1
4481   }
4482 \cs_new_protected:Npn \__seq_push_item_def:
```



```

4483 {
4484     \int_gincr:N \g__prg_map_int
4485     \cs_gset_eq:cN { __prg_map_ \int_use:N \g__prg_map_int :w }
4486     \__seq_item:n
4487 }
4488 \cs_new_protected:Npn \__seq_pop_item_def:
4489 {
4490     \cs_gset_eq:Nc \__seq_item:n
4491     { __prg_map_ \int_use:N \g__prg_map_int :w }
4492     \int_gdecr:N \g__prg_map_int
4493 }

```

(End definition for `__seq_push_item_def:n`, `__seq_push_item_def:`, and `__seq_pop_item_def:`.)

`\seq_map_inline:Nn` The idea here is that `__seq_item:n` is already “applied” to each item in a sequence, and so an in-line mapping is just a case of redefining `__seq_item:n`.

`\seq_map_inline:cn`

```

4494 \cs_new_protected:Npn \seq_map_inline:Nn #1#2
4495 {
4496     \__seq_push_item_def:n {#2}
4497     #1
4498     \__prg_break_point:Nn \seq_map_break: { \__seq_pop_item_def: }
4499 }
4500 \cs_generate_variant:Nn \seq_map_inline:Nn { c }

```

(End definition for `\seq_map_inline:Nn`. This function is documented on page 62.)

`\seq_map_variable:NNn` This is just a specialised version of the in-line mapping function, using an `x`-type expansion for the code set up so that the number of `#` tokens required is as expected.

`\seq_map_variable:Ncn`

`\seq_map_variable:cNn`

`\seq_map_variable:ccn`

```

4501 \cs_new_protected:Npn \seq_map_variable:NNn #1#2#3
4502 {
4503     \__seq_push_item_def:x
4504     {
4505         \tl_set:Nn \exp_not:N #2 {##1}
4506         \exp_not:n {#3}
4507     }
4508     #1
4509     \__prg_break_point:Nn \seq_map_break: { \__seq_pop_item_def: }
4510 }
4511 \cs_generate_variant:Nn \seq_map_variable:NNn { Nc }
4512 \cs_generate_variant:Nn \seq_map_variable:NNn { c , cc }

```

(End definition for `\seq_map_variable:NNn`. This function is documented on page 62.)

`\seq_count:N` Counting the items in a sequence is done using the same approach as for other count functions: turn each entry into a `+1` then use integer evaluation to actually do the mathematics.

`\seq_count:c`

`__seq_count:n`

```

4513 \cs_new:Npn \seq_count:N #1
4514 {
4515     \int_eval:n
4516     {
4517         0
4518         \seq_map_function:NN #1 \__seq_count:n
4519     }
4520 }
4521 \cs_new:Npn \__seq_count:n #1 { + 1 }
4522 \cs_generate_variant:Nn \seq_count:N { c }

```

(End definition for `\seq_count:N` and `_seq_count:n`. These functions are documented on page 63.)

7.7 Using sequences

`\seq_use:Nnnn` See `\clist_use:Nnnn` for a general explanation. The main difference is that we use `_seq_item:n` as a delimiter rather than commas. We also need to add `_seq_item:n` at various places, and `\s__seq`.

```

\seq_use:cnnn
\_seq_use:NNnNnn
\_seq_use_setup:w
\_seq_use:nwwwnwn
\_seq_use:nwnn
\seq_use:Nn
\seq_use:cn
4523 \cs_new:Npn \seq_use:Nnnn #1#2#3#4
4524 {
4525   \seq_if_exist:NTF #1
4526   {
4527     \int_case:nnF { \seq_count:N #1 }
4528     {
4529       { 0 } { }
4530       { 1 } { \exp_after:wN \_seq_use:NNnNnn #1 ? { } { } }
4531       { 2 } { \exp_after:wN \_seq_use:NNnNnn #1 {#2} }
4532     }
4533     {
4534       \exp_after:wN \_seq_use_setup:w #1 \_seq_item:n
4535       \q_mark { \_seq_use:nwwwnwn {#3} }
4536       \q_mark { \_seq_use:nwnn {#4} }
4537       \q_stop { }
4538     }
4539   }
4540   {
4541     \_msg_kernel_expandable_error:nnn
4542     { kernel } { bad-variable } {#1}
4543   }
4544 }
4545 \cs_generate_variant:Nn \seq_use:Nnnn { c }
4546 \cs_new:Npn \_seq_use:NNnNnn #1#2#3#4#5#6 { \exp_not:n { #3 #6 #5 } }
4547 \cs_new:Npn \_seq_use_setup:w \s__seq { \_seq_use:nwwwnwn { } }
4548 \cs_new:Npn \_seq_use:nwwwnwn
4549   #1 \_seq_item:n #2 \_seq_item:n #3 \_seq_item:n #4#5
4550   \q_mark #6#7 \q_stop #8
4551   {
4552     #6 \_seq_item:n {#3} \_seq_item:n {#4} #5
4553     \q_mark {#6} #7 \q_stop { #8 #1 #2 }
4554   }
4555 \cs_new:Npn \_seq_use:nwnn #1 \_seq_item:n #2 #3 \q_stop #4
4556   { \exp_not:n { #4 #1 #2 } }
4557 \cs_new:Npn \seq_use:Nn #1#2
4558   { \seq_use:Nnnn #1 {#2} {#2} {#2} }
4559 \cs_generate_variant:Nn \seq_use:Nn { c }

```

(End definition for `\seq_use:Nnnn` and others. These functions are documented on page 63.)

7.8 Sequence stacks

The same functions as for sequences, but with the correct naming.

`\seq_push:Nn` Pushing to a sequence is the same as adding on the left.

```

\seq_push:NV
\seq_push:Nv
\seq_push:No
\seq_push:Nx
\seq_push:cn
\seq_push:cV
\seq_push:cV
\seq_push:co
\seq_push:cx
\seq_gpush:Nn
\seq_gpush:NV
\seq_gpush:Nv

```

```

4561 \cs_new_eq:NN \seq_push:NV \seq_put_left:NV
4562 \cs_new_eq:NN \seq_push:Nv \seq_put_left:Nv
4563 \cs_new_eq:NN \seq_push:No \seq_put_left:No
4564 \cs_new_eq:NN \seq_push:Nx \seq_put_left:Nx
4565 \cs_new_eq:NN \seq_push:cn \seq_put_left:cn
4566 \cs_new_eq:NN \seq_push:cV \seq_put_left:cV
4567 \cs_new_eq:NN \seq_push:cv \seq_put_left:cv
4568 \cs_new_eq:NN \seq_push:co \seq_put_left:co
4569 \cs_new_eq:NN \seq_push:cx \seq_put_left:cx
4570 \cs_new_eq:NN \seq_gpush:Nn \seq_gput_left:Nn
4571 \cs_new_eq:NN \seq_gpush:NV \seq_gput_left:NV
4572 \cs_new_eq:NN \seq_gpush:Nv \seq_gput_left:Nv
4573 \cs_new_eq:NN \seq_gpush:No \seq_gput_left:No
4574 \cs_new_eq:NN \seq_gpush:Nx \seq_gput_left:Nx
4575 \cs_new_eq:NN \seq_gpush:cn \seq_gput_left:cn
4576 \cs_new_eq:NN \seq_gpush:cV \seq_gput_left:cV
4577 \cs_new_eq:NN \seq_gpush:cv \seq_gput_left:cv
4578 \cs_new_eq:NN \seq_gpush:co \seq_gput_left:co
4579 \cs_new_eq:NN \seq_gpush:cx \seq_gput_left:cx

```

(End definition for `\seq_push:Nn` and `\seq_gpush:Nn`. These functions are documented on page 65.)

`\seq_get:NN` In most cases, getting items from the stack does not need to specify that this is from the left. So alias are provided.

```

\seq_get:cN
\seq_pop:NN
\seq_gpop:NN
\seq_gpop:cN
4580 \cs_new_eq:NN \seq_get:NN \seq_get_left:NN
4581 \cs_new_eq:NN \seq_get:cN \seq_get_left:cN
4582 \cs_new_eq:NN \seq_pop:NN \seq_pop_left:NN
4583 \cs_new_eq:NN \seq_pop:cN \seq_pop_left:cN
4584 \cs_new_eq:NN \seq_gpop:NN \seq_gpop_left:NN
4585 \cs_new_eq:NN \seq_gpop:cN \seq_gpop_left:cN

```

(End definition for `\seq_get:NN`, `\seq_pop:NN`, and `\seq_gpop:NN`. These functions are documented on page 64.)

`\seq_get:NNTF` More copies.

```

\seq_get:cNTF
\seq_pop:NNTF
\seq_pop:cNTF
\seq_gpop:NNTF
\seq_gpop:cNTF
4586 \prg_new_eq_conditional:NNn \seq_get:NN \seq_get_left:NN { T , F , TF }
4587 \prg_new_eq_conditional:NNn \seq_get:cN \seq_get_left:cN { T , F , TF }
4588 \prg_new_eq_conditional:NNn \seq_pop:NN \seq_pop_left:NN { T , F , TF }
4589 \prg_new_eq_conditional:NNn \seq_pop:cN \seq_pop_left:cN { T , F , TF }
4590 \prg_new_eq_conditional:NNn \seq_gpop:NN \seq_gpop_left:NN { T , F , TF }
4591 \prg_new_eq_conditional:NNn \seq_gpop:cN \seq_gpop_left:cN { T , F , TF }

```

(End definition for `\seq_get:NNTF`, `\seq_pop:NNTF`, and `\seq_gpop:NNTF`. These functions are documented on page 64.)

7.9 Viewing sequences

`\seq_show:N` Apply the general `_msg_show_variable:NNNnn`.

```

\seq_show:c
4592 \cs_new_protected:Npn \seq_show:N #1
4593 {
4594   \_msg_show_variable:NNNnn #1
4595   \seq_if_exist:NTF \seq_if_empty:NTF { seq }
4596   { \seq_map_function:NN #1 \_msg_show_item:n }
4597 }
4598 \cs_generate_variant:Nn \seq_show:N { c }

```

(End definition for `\seq_show:N`. This function is documented on page 67.)

`\seq_log:N` Redirect output of `\seq_show:N` to the log.
`\seq_log:c` 4599 `\cs_new_protected:Npn \seq_log:N`
 4600 `{ __msg_log_next: \seq_show:N }`
 4601 `\cs_generate_variant:Nn \seq_log:N { c }`

(End definition for `\seq_log:N`. This function is documented on page 67.)

7.10 Scratch sequences

`\l_tmpa_seq` Temporary comma list variables.
`\l_tmpb_seq` 4602 `\seq_new:N \l_tmpa_seq`
`\g_tmpa_seq` 4603 `\seq_new:N \l_tmpb_seq`
`\g_tmpb_seq` 4604 `\seq_new:N \g_tmpa_seq`
 4605 `\seq_new:N \g_tmpb_seq`

(End definition for `\l_tmpa_seq` and others. These variables are documented on page 67.)

4606 `</initex | package>`

8 l3int implementation

4607 `<*initex | package>`

4608 `<@@=int>`

The following test files are used for this code: `m3int001,m3int002,m3int03`.

`\c_max_register_int` Done in l3basics.

(End definition for `\c_max_register_int`. This variable is documented on page 78.)

`__int_to_roman:w` Done in l3basics.

`\if_int_compare:w` (End definition for `__int_to_roman:w` and `\if_int_compare:w`.)

`\or:` Done in l3basics.

(End definition for `\or:`. This function is documented on page 79.)

`__int_value:w` Here are the remaining primitives for number comparisons and expressions.

`__int_eval:w` 4609 `\cs_new_eq:NN __int_value:w` `\tex_number:D`
`__int_eval_end:` 4610 `\cs_new_eq:NN __int_eval:w` `\etex_numexpr:D`
`\if_int_odd:w` 4611 `\cs_new_eq:NN __int_eval_end:` `\tex_relax:D`
`\if_case:w` 4612 `\cs_new_eq:NN \if_int_odd:w` `\tex_ifodd:D`
 4613 `\cs_new_eq:NN \if_case:w` `\tex_ifcase:D`

(End definition for `__int_value:w` and others.)

8.1 Integer expressions

\int_eval:n Wrapper for `__int_eval:w`: can be used in an integer expression or directly in the input stream.

```
4614 \cs_new:Npn \int_eval:n #1
4615 { \__int_value:w \__int_eval:w #1 \__int_eval_end: }
```

(End definition for `\int_eval:n`. This function is documented on page 68.)

\int_abs:n Functions for min, max, and absolute value with only one evaluation. The absolute value is obtained by removing a leading sign if any. All three functions expand in two steps.

```
\__int_abs:N
\int_max:nn
\int_min:nn
\__int_maxmin:wwN
4616 \cs_new:Npn \int_abs:n #1
4617 {
4618   \__int_value:w \exp_after:wN \__int_abs:N
4619   \__int_value:w \__int_eval:w #1 \__int_eval_end:
4620   \exp_stop_f:
4621 }
4622 \cs_new:Npn \__int_abs:N #1
4623 { \if_meaning:w - #1 \else: \exp_after:wN #1 \fi: }
4624 \cs_set:Npn \int_max:nn #1#2
4625 {
4626   \__int_value:w \exp_after:wN \__int_maxmin:wwN
4627   \__int_value:w \__int_eval:w #1 \exp_after:wN ;
4628   \__int_value:w \__int_eval:w #2 ;
4629   >
4630   \exp_stop_f:
4631 }
4632 \cs_set:Npn \int_min:nn #1#2
4633 {
4634   \__int_value:w \exp_after:wN \__int_maxmin:wwN
4635   \__int_value:w \__int_eval:w #1 \exp_after:wN ;
4636   \__int_value:w \__int_eval:w #2 ;
4637   <
4638   \exp_stop_f:
4639 }
4640 \cs_new:Npn \__int_maxmin:wwN #1 ; #2 ; #3
4641 {
4642   \if_int_compare:w #1 #3 #2 ~
4643   #1
4644   \else:
4645   #2
4646   \fi:
4647 }
```

(End definition for `\int_abs:n` and others. These functions are documented on page 68.)

\int_div_truncate:nn As `__int_eval:w` rounds the result of a division we also provide a version that truncates the result. We use an auxiliary to make sure numerator and denominator are only evaluated once: this comes in handy when those are more expressions are expensive to evaluate (e.g., `\tl_count:n`). If the numerator `#1#2` is 0, then we divide 0 by the denominator (this ensures that 0/0 is correctly reported as an error). Otherwise, shift the numerator `#1#2` towards 0 by $(| \#3\#4 | - 1)/2$, which we round away from zero. It turns out that this quantity exactly compensates the difference between ε -TeX's rounding and

the truncating behaviour that we want. The details are thanks to Heiko Oberdiek: getting things right in all cases is not so easy.

```

4648 \cs_new:Npn \int_div_truncate:nn #1#2
4649 {
4650   \__int_value:w \__int_eval:w
4651   \exp_after:wN \__int_div_truncate:NwNw
4652   \__int_value:w \__int_eval:w #1 \exp_after:wN ;
4653   \__int_value:w \__int_eval:w #2 ;
4654   \__int_eval_end:
4655 }
4656 \cs_new:Npn \__int_div_truncate:NwNw #1#2; #3#4;
4657 {
4658   \if_meaning:w 0 #1
4659   0
4660   \else:
4661   (
4662     #1#2
4663     \if_meaning:w - #1 + \else: - \fi:
4664     ( \if_meaning:w - #3 - \fi: #3#4 - 1 ) / 2
4665   )
4666   \fi:
4667   / #3#4
4668 }

```

For the sake of completeness:

```

4669 \cs_new:Npn \int_div_round:nn #1#2
4670 { \__int_value:w \__int_eval:w ( #1 ) / ( #2 ) \__int_eval_end: }

```

Finally there's the modulus operation.

```

4671 \cs_new:Npn \int_mod:nn #1#2
4672 {
4673   \__int_value:w \__int_eval:w \exp_after:wN \__int_mod:ww
4674   \__int_value:w \__int_eval:w #1 \exp_after:wN ;
4675   \__int_value:w \__int_eval:w #2 ;
4676   \__int_eval_end:
4677 }
4678 \cs_new:Npn \__int_mod:ww #1; #2;
4679 { #1 - ( \__int_div_truncate:NwNw #1 ; #2 ; ) * #2 }

```

(End definition for `\int_div_truncate:nn` and others. These functions are documented on page 69.)

8.2 Creating and initialising integers

`\int_new:N` Two ways to do this: one for the format and one for the L^AT_EX 2_ε package. In plain T_EX, `\int_new:c` `\newcount` (and other allocators) are `\outer:` to allow the code here to work in “generic” mode this is therefore accessed by name. (The same applies to `\newbox`, `\newdimen` and so on.)

```

4680 \*package>
4681 \cs_new_protected:Npn \int_new:N #1
4682 {
4683   \__chk_if_free_cs:N #1
4684   \cs:w newcount \cs_end: #1
4685 }
4686 \*package>
4687 \cs_generate_variant:Nn \int_new:N { c }

```

(End definition for `\int_new:N`. This function is documented on page 69.)

```

\int_const:Nn As stated, most constants can be defined as \chardef or \mathchardef but that's engine
\int_const:cn dependent. As a result, there is some set up code to determine what can be done. No
\__int_constdef:Nw full engine testing just yet so everything is a little awkward.
\c__max_constdef_int
4688 \cs_new_protected:Npn \int_const:Nn #1#2
4689 {
4690   \int_compare:nNnTF {#2} < \c_zero
4691   {
4692     \int_new:N #1
4693     \int_gset:Nn #1 {#2}
4694   }
4695   {
4696     \int_compare:nNnTF {#2} > \c__max_constdef_int
4697     {
4698       \int_new:N #1
4699       \int_gset:Nn #1 {#2}
4700     }
4701     {
4702       \__chk_if_free_cs:N #1
4703       \tex_global:D \__int_constdef:Nw #1 =
4704         \__int_eval:w #2 \__int_eval_end:
4705     }
4706   }
4707 }
4708 \cs_generate_variant:Nn \int_const:Nn { c }
4709 \if_int_odd:w 0
4710   \cs_if_exist:NT \luatex luatexversion:D { 1 }
4711   \cs_if_exist:NT \uptex_disablecjktoken:D
4712     { \if_int_compare:w \ptex_jis:D "2121 = "3000 ~ 1 \fi: }
4713   \cs_if_exist:NT \xetex_XeTeXversion:D { 1 } ~
4714   \cs_if_exist:NTF \uptex_disablecjktoken:D
4715     { \cs_new_eq:NN \__int_constdef:Nw \uptex_kchardef:D }
4716     { \cs_new_eq:NN \__int_constdef:Nw \tex_chardef:D }
4717   \__int_constdef:Nw \c__max_constdef_int 1114111 ~
4718 \else:
4719   \cs_new_eq:NN \__int_constdef:Nw \tex_mathchardef:D
4720   \tex_mathchardef:D \c__max_constdef_int 32767 ~
4721 \fi:

```

(End definition for `\int_const:Nn`, `__int_constdef:Nw`, and `\c__max_constdef_int`. These functions are documented on page 69.)

```

\int_zero:N Functions that reset an <integer> register to zero.
\int_zero:c 4722 \cs_new_protected:Npn \int_zero:N #1 { #1 = \c_zero }
\int_gzero:N 4723 \cs_new_protected:Npn \int_gzero:N #1 { \tex_global:D #1 = \c_zero }
\int_gzero:c 4724 \cs_generate_variant:Nn \int_zero:N { c }
4725 \cs_generate_variant:Nn \int_gzero:N { c }

```

(End definition for `\int_zero:N` and `\int_gzero:N`. These functions are documented on page 69.)

```

\int_zero_new:N Create a register if needed, otherwise clear it.
\int_zero_new:c 4726 \cs_new_protected:Npn \int_zero_new:N #1
\int_gzero_new:N 4727 { \int_if_exist:NTF #1 { \int_zero:N #1 } { \int_new:N #1 } }
\int_gzero_new:c

```

```

4728 \cs_new_protected:Npn \int_gzero_new:N #1
4729 { \int_if_exist:NTF #1 { \int_gzero:N #1 } { \int_new:N #1 } }
4730 \cs_generate_variant:Nn \int_zero_new:N { c }
4731 \cs_generate_variant:Nn \int_gzero_new:N { c }

```

(End definition for `\int_zero_new:N` and `\int_gzero_new:N`. These functions are documented on page 69.)

```

\int_set_eq:NN Setting equal means using one integer inside the set function of another.
\int_set_eq:cn 4732 \cs_new_protected:Npn \int_set_eq:NN #1#2 { #1 = #2 }
\int_set_eq:Nc 4733 \cs_generate_variant:Nn \int_set_eq:NN { c }
\int_set_eq:cc 4734 \cs_generate_variant:Nn \int_set_eq:NN { Nc , cc }
\int_gset_eq:NN 4735 \cs_new_protected:Npn \int_gset_eq:NN #1#2 { \tex_global:D #1 = #2 }
\int_gset_eq:cn 4736 \cs_generate_variant:Nn \int_gset_eq:NN { c }
\int_gset_eq:Nc 4737 \cs_generate_variant:Nn \int_gset_eq:NN { Nc , cc }
\int_gset_eq:cc

```

(End definition for `\int_set_eq:NN` and `\int_gset_eq:NN`. These functions are documented on page 69.)

```

\int_if_exist_p:N Copies of the cs functions defined in l3basics.
\int_if_exist_p:c 4738 \prg_new_eq_conditional:NNn \int_if_exist:N \cs_if_exist:N
\int_if_exist:NTF 4739 { TF , T , F , p }
\int_if_exist:cTF 4740 \prg_new_eq_conditional:NNn \int_if_exist:c \cs_if_exist:c
4741 { TF , T , F , p }

```

(End definition for `\int_if_exist:NTF`. This function is documented on page 70.)

8.3 Setting and incrementing integers

```

\int_add:Nn Adding and subtracting to and from a counter ...
\int_add:cn 4742 \cs_new_protected:Npn \int_add:Nn #1#2
\int_gadd:Nn 4743 { \tex_advance:D #1 by \__int_eval:w #2 \__int_eval_end: }
\int_gadd:cn 4744 \cs_new_protected:Npn \int_sub:Nn #1#2
\int_sub:Nn 4745 { \tex_advance:D #1 by - \__int_eval:w #2 \__int_eval_end: }
\int_sub:cn 4746 \cs_new_protected:Npn \int_gadd:Nn
\int_gsub:Nn 4747 { \tex_global:D \int_add:Nn }
\int_gsub:cn 4748 \cs_new_protected:Npn \int_gsub:Nn
4749 { \tex_global:D \int_sub:Nn }
4750 \cs_generate_variant:Nn \int_add:Nn { c }
4751 \cs_generate_variant:Nn \int_gadd:Nn { c }
4752 \cs_generate_variant:Nn \int_sub:Nn { c }
4753 \cs_generate_variant:Nn \int_gsub:Nn { c }

```

(End definition for `\int_add:Nn` and others. These functions are documented on page 70.)

```

\int_incr:N Incrementing and decrementing of integer registers is done with the following functions.
\int_incr:c 4754 \cs_new_protected:Npn \int_incr:N #1
\int_gincr:N 4755 { \tex_advance:D #1 \c_one }
\int_gincr:c 4756 \cs_new_protected:Npn \int_decr:N #1
\int_decr:N 4757 { \tex_advance:D #1 - \c_one }
\int_decr:c 4758 \cs_new_protected:Npn \int_gincr:N
\int_gdecr:N 4759 { \tex_global:D \int_incr:N }
\int_gdecr:c 4760 \cs_new_protected:Npn \int_gdecr:N
4761 { \tex_global:D \int_decr:N }
4762 \cs_generate_variant:Nn \int_incr:N { c }

```



```

4763 \cs_generate_variant:Nn \int_decr:N { c }
4764 \cs_generate_variant:Nn \int_gincr:N { c }
4765 \cs_generate_variant:Nn \int_gdecr:N { c }

```

(End definition for `\int_incr:N` and others. These functions are documented on page 70.)

```

\int_set:Nn As integers are register-based TeX will issue an error if they are not defined. Thus there
\int_set:cn is no need for the checking code seen with token list variables.
\int_gset:Nn
\int_gset:cn
4766 \cs_new_protected:Npn \int_set:Nn #1#2
4767 { #1 ~ \__int_eval:w #2\__int_eval_end: }
4768 \cs_new_protected:Npn \int_gset:Nn { \tex_global:D \int_set:Nn }
4769 \cs_generate_variant:Nn \int_set:Nn { c }
4770 \cs_generate_variant:Nn \int_gset:Nn { c }

```

(End definition for `\int_set:Nn` and `\int_gset:Nn`. These functions are documented on page 70.)

8.4 Using integers

```

\int_use:N Here is how counters are accessed:
\int_use:c
4771 \cs_new_eq:NN \int_use:N \tex_the:D

```

We hand-code this for some speed gain:

```

4772 %\cs_generate_variant:Nn \int_use:N { c }
4773 \cs_new:Npn \int_use:c #1 { \tex_the:D \cs:w #1 \cs_end: }

```

(End definition for `\int_use:N`. This function is documented on page 70.)

8.5 Integer expression conditionals

```

\__prg_compare_error: Those functions are used for comparison tests which use a simple syntax where only
\__prg_compare_error:Nw one set of braces is required and additional operators such as != and >= are supported.
The tests first evaluate their left-hand side, with a trailing \__prg_compare_error:.
This marker is normally not expanded, but if the relation symbol is missing from the
test's argument, then the marker inserts = (and itself) after triggering the relevant TeX
error. If the first token which appears after evaluating and removing the left-hand side is
not a known relation symbol, then a judiciously placed \__prg_compare_error:Nw gets
expanded, cleaning up the end of the test and telling the user what the problem was.

```

```

4774 \cs_new_protected:Npn \__prg_compare_error:
4775 {
4776   \if_int_compare:w \c_zero \c_zero \fi:
4777   =
4778   \__prg_compare_error:
4779 }
4780 \cs_new:Npn \__prg_compare_error:Nw
4781 #1#2 \q_stop
4782 {
4783   { }
4784   \c_zero \fi:
4785   \__msg_kernel_expandable_error:nnn
4786   { kernel } { unknown-comparison } {#1}
4787   \prg_return_false:
4788 }

```

(End definition for `__prg_compare_error:` and `__prg_compare_error:Nw`.)

```

\int_compare_p:n Comparison tests using a simple syntax where only one set of braces is required, additional
\int_compare:nTF operators such as != and >= are supported, and multiple comparisons can be performed
  \__int_compare:w at once, for instance 0 < 5 <= 1. The idea is to loop through the argument, finding one
  \__int_compare:Nw operand at a time, and comparing it to the previous one. The looping auxiliary \__-
  \__int_compare:NNw int_compare:Nw reads one <operand> and one <comparison> symbol, and leaves roughly
  \__int_compare:nnN
  \__int_compare_end=:NNw
  \__int_compare=:NNw
  \__int_compare_<:NNw
  \__int_compare_>:NNw
  \__int_compare_=:NNw
  \__int_compare_!=:NNw
  \__int_compare_<=:NNw
  \__int_compare_>=:NNw

```

```

  <operand> \prg_return_false: \fi:
  \reverse_if:N \if_int_compare:w <operand> <comparison>
  \__int_compare:Nw

```

in the input stream. Each call to this auxiliary provides the second operand of the last call's `\if_int_compare:w`. If one of the *<comparisons>* is `false`, the `true` branch of the TeX conditional is taken (because of `\reverse_if:N`), immediately returning `false` as the result of the test. There is no TeX conditional waiting the first operand, so we add an `\if_false:` and expand by hand with `__int_value:w`, thus skipping `\prg_return_false:` on the first iteration.

Before starting the loop, the first step is to make sure that there is at least one relation symbol. We first let TeX evaluate this left hand side of the (in)equality using `__int_eval:w`. Since the relation symbols `<`, `>`, `=` and `!` are not allowed in integer expressions, they will terminate it. If the argument contains no relation symbol, `__prg_compare_error:` is expanded, inserting `=` and itself after an error. In all cases, `__int_compare:w` receives as its argument an integer, a relation symbol, and some more tokens. We then setup the loop, which will be ended by the two odd-looking items `e` and `{=nd_}`, with a trailing `\q_stop` used to grab the entire argument when necessary.

```

4789 \prg_new_conditional:Npnn \int_compare:n #1 { p , T , F , TF }
4790 {
4791   \exp_after:wN \__int_compare:w
4792   \__int_value:w \__int_eval:w #1 \__prg_compare_error:
4793 }
4794 \cs_new:Npn \__int_compare:w #1 \__prg_compare_error:
4795 {
4796   \exp_after:wN \if_false: \__int_value:w
4797   \__int_compare:Nw #1 e { = nd_ } \q_stop
4798 }

```

The goal here is to find an *<operand>* and a *<comparison>*. The *<operand>* is already evaluated, but we cannot yet grab it as an argument. To access the following relation symbol, we remove the number by applying `__int_to_roman:w`, after making sure that the argument becomes non-positive: its roman numeral representation is then empty. Then probe the first two tokens with `__int_compare:NNw` to determine the relation symbol, building a control sequence from it (`\token_to_str:N` gives better errors if #1 is not a character). All the extended forms have an extra `=` hence the test for that as a second token. If the relation symbol is unknown, then the control sequence is turned by TeX into `\scan_stop:`, ignored thanks to `\unexpanded`, and `__prg_compare_error:Nw` raises an error.

```

4799 \cs_new:Npn \__int_compare:Nw #1#2 \q_stop
4800 {
4801   \exp_after:wN \__int_compare:NNw
4802   \__int_to_roman:w - 0 #2 \q_mark
4803   #1#2 \q_stop
4804 }
4805 \cs_new:Npn \__int_compare:NNw #1#2#3 \q_mark

```

```

4806 {
4807   \etex_unexpanded:D
4808   \use:c
4809   {
4810     __int_compare_ \token_to_str:N #1
4811     \if_meaning:w = #2 = \fi:
4812     :NNw
4813   }
4814   \__prg_compare_error:Nw #1
4815 }

```

When the last *operand* is seen, `__int_compare:NNw` receives `e` and `=nd_` as arguments, hence calling `__int_compare_end=:NNw` to end the loop: return the result of the last comparison (involving the operand that we just found). When a normal relation is found, the appropriate auxiliary calls `__int_compare:nnN` where `#1` is `\if_int_compare:w` or `\reverse_if:N \if_int_compare:w`, `#2` is the *operand*, and `#3` is one of `<`, `=`, or `>`. As announced earlier, we leave the *operand* for the previous conditional. If this conditional is true the result of the test is known, so we remove all tokens and return `false`. Otherwise, we apply the conditional `#1` to the *operand* `#2` and the comparison `#3`, and call `__int_compare:Nw` to look for additional operands, after evaluating the following expression.

```

4816 \cs_new:cpn { __int_compare_end=:NNw } #1#2#3 e #4 \q_stop
4817 {
4818   {#3} \exp_stop_f:
4819   \prg_return_false: \else: \prg_return_true: \fi:
4820 }
4821 \cs_new:Npn \__int_compare:nnN #1#2#3
4822 {
4823   {#2} \exp_stop_f:
4824   \prg_return_false: \exp_after:wN \use_none_delimit_by_q_stop:w
4825   \fi:
4826   #1 #2 #3 \exp_after:wN \__int_compare:Nw \__int_value:w \__int_eval:w
4827 }

```

The actual comparisons are then simple function calls, using the relation as delimiter for a delimited argument and discarding `__prg_compare_error:Nw` *token* responsible for error detection.

```

4828 \cs_new:cpn { __int_compare=:NNw } #1#2#3 =
4829 { \__int_compare:nnN { \reverse_if:N \if_int_compare:w } {#3} = }
4830 \cs_new:cpn { __int_compare:<:NNw } #1#2#3 <
4831 { \__int_compare:nnN { \reverse_if:N \if_int_compare:w } {#3} < }
4832 \cs_new:cpn { __int_compare:>:NNw } #1#2#3 >
4833 { \__int_compare:nnN { \reverse_if:N \if_int_compare:w } {#3} > }
4834 \cs_new:cpn { __int_compare=:NNw } #1#2#3 ==
4835 { \__int_compare:nnN { \reverse_if:N \if_int_compare:w } {#3} = }
4836 \cs_new:cpn { __int_compare!=:NNw } #1#2#3 !=
4837 { \__int_compare:nnN { \if_int_compare:w } {#3} = }
4838 \cs_new:cpn { __int_compare<=:NNw } #1#2#3 <=
4839 { \__int_compare:nnN { \if_int_compare:w } {#3} > }
4840 \cs_new:cpn { __int_compare>=:NNw } #1#2#3 >=
4841 { \__int_compare:nnN { \if_int_compare:w } {#3} < }

```

(End definition for `\int_compare:nTF` and others. These functions are documented on page 71.)

`\int_compare_p:nNn` More efficient but less natural in typing.

```

\int_compare:nNnTF
4842 \prg_new_conditional:Npnn \int_compare:nNn #1#2#3 { p , T , F , TF }
4843 {
4844     \if_int_compare:w \__int_eval:w #1 #2 \__int_eval:w #3 \__int_eval_end:
4845     \prg_return_true:
4846     \else:
4847     \prg_return_false:
4848     \fi:
4849 }

```

(End definition for `\int_compare:nNnTF`. This function is documented on page 71.)

`\int_case:nn` For integer cases, the first task to fully expand the check condition. The over all idea is then much the same as for `\str_case:nn(TF)` as described in l3basics.

```

\int_case:nnTF
\__int_case:nnTF
\__int_case:nw
\__int_case_end:nw
4850 \cs_new:Npn \int_case:nnTF #1
4851 {
4852     \exp:w
4853     \exp_args:Nf \__int_case:nnTF { \int_eval:n {#1} }
4854 }
4855 \cs_new:Npn \int_case:nnT #1#2#3
4856 {
4857     \exp:w
4858     \exp_args:Nf \__int_case:nnTF { \int_eval:n {#1} } {#2} {#3} { }
4859 }
4860 \cs_new:Npn \int_case:nnF #1#2
4861 {
4862     \exp:w
4863     \exp_args:Nf \__int_case:nnTF { \int_eval:n {#1} } {#2} { }
4864 }
4865 \cs_new:Npn \int_case:nn #1#2
4866 {
4867     \exp:w
4868     \exp_args:Nf \__int_case:nnTF { \int_eval:n {#1} } {#2} { } { }
4869 }
4870 \cs_new:Npn \__int_case:nnTF #1#2#3#4
4871 { \__int_case:nw {#1} #2 {#1} { } \q_mark {#3} \q_mark {#4} \q_stop }
4872 \cs_new:Npn \__int_case:nw #1#2#3
4873 {
4874     \int_compare:nNnTF {#1} = {#2}
4875     { \__int_case_end:nw {#3} }
4876     { \__int_case:nw {#1} }
4877 }
4878 \cs_new_eq:NN \__int_case_end:nw \__prg_case_end:nw

```

(End definition for `\int_case:nnTF` and others. These functions are documented on page 72.)

`\int_if_odd_p:n` A predicate function.

```

\int_if_odd:nTF
\int_if_even_p:n
\int_if_even:nTF
4879 \prg_new_conditional:Npnn \int_if_odd:n #1 { p , T , F , TF}
4880 {
4881     \if_int_odd:w \__int_eval:w #1 \__int_eval_end:
4882     \prg_return_true:
4883     \else:
4884     \prg_return_false:
4885     \fi:

```

```

4886 }
4887 \prg_new_conditional:Npnn \int_if_even:n #1 { p , T , F , TF}
4888 {
4889   \if_int_odd:w \__int_eval:w #1 \__int_eval_end:
4890   \prg_return_false:
4891   \else:
4892   \prg_return_true:
4893   \fi:
4894 }

```

(End definition for `\int_if_odd:nTF` and `\int_if_even:nTF`. These functions are documented on page 72.)

8.6 Integer expression loops

`\int_while_do:nn` These are quite easy given the above functions. The `while` versions test first and then execute the body. The `do_while` does it the other way round.

```

\int_until_do:nn
\int_do_while:nn
\int_do_until:nn
4895 \cs_new:Npn \int_while_do:nn #1#2
4896 {
4897   \int_compare:nT {#1}
4898   {
4899     #2
4900     \int_while_do:nn {#1} {#2}
4901   }
4902 }
4903 \cs_new:Npn \int_until_do:nn #1#2
4904 {
4905   \int_compare:nF {#1}
4906   {
4907     #2
4908     \int_until_do:nn {#1} {#2}
4909   }
4910 }
4911 \cs_new:Npn \int_do_while:nn #1#2
4912 {
4913   #2
4914   \int_compare:nT {#1}
4915   { \int_do_while:nn {#1} {#2} }
4916 }
4917 \cs_new:Npn \int_do_until:nn #1#2
4918 {
4919   #2
4920   \int_compare:nF {#1}
4921   { \int_do_until:nn {#1} {#2} }
4922 }

```

(End definition for `\int_while_do:nn` and others. These functions are documented on page 73.)

`\int_while_do:nNnn` As above but not using the more natural syntax.

```

\int_until_do:nNnn
\int_do_while:nNnn
\int_do_until:nNnn
4923 \cs_new:Npn \int_while_do:nNnn #1#2#3#4
4924 {
4925   \int_compare:nNnT {#1} #2 {#3}
4926   {
4927     #4

```

```

4928     \int_while_do:nNnn {#1} #2 {#3} {#4}
4929   }
4930 }
4931 \cs_new:Npn \int_until_do:nNnn #1#2#3#4
4932 {
4933   \int_compare:nNnF {#1} #2 {#3}
4934   {
4935     #4
4936     \int_until_do:nNnn {#1} #2 {#3} {#4}
4937   }
4938 }
4939 \cs_new:Npn \int_do_while:nNnn #1#2#3#4
4940 {
4941   #4
4942   \int_compare:nNnT {#1} #2 {#3}
4943   { \int_do_while:nNnn {#1} #2 {#3} {#4} }
4944 }
4945 \cs_new:Npn \int_do_until:nNnn #1#2#3#4
4946 {
4947   #4
4948   \int_compare:nNnF {#1} #2 {#3}
4949   { \int_do_until:nNnn {#1} #2 {#3} {#4} }
4950 }

```

(End definition for `\int_while_do:nNnn` and others. These functions are documented on page 73.)

8.7 Integer step functions

`\int_step_function:nnnN`
 `__int_step:wwwN`
 `__int_step:NnnnN`

Before all else, evaluate the initial value, step, and final value. Repeating a function by steps first needs a check on the direction of the steps. After that, do the function for the start value then step and loop around. It would be more symmetrical to test for a step size of zero before checking the sign, but we optimize for the most frequent case (positive step).

```

4951 \cs_new:Npn \int_step_function:nnnN #1#2#3
4952 {
4953   \exp_after:wN \__int_step:wwwN
4954   \__int_value:w \__int_eval:w #1 \exp_after:wN ;
4955   \__int_value:w \__int_eval:w #2 \exp_after:wN ;
4956   \__int_value:w \__int_eval:w #3 ;
4957 }
4958 \cs_new:Npn \__int_step:wwwN #1; #2; #3; #4
4959 {
4960   \int_compare:nNnTF {#2} > \c_zero
4961   { \__int_step:NnnnN > }
4962   {
4963     \int_compare:nNnTF {#2} = \c_zero
4964     {
4965       \__msg_kernel_expandable_error:nnn { kernel } { zero-step } {#4}
4966       \use_none:nnnn
4967     }
4968     { \__int_step:NnnnN < }
4969   }
4970   {#1} {#2} {#3} #4
4971 }

```

```

4972 \cs_new:Npn \__int_step:NnnnN #1#2#3#4#5
4973 {
4974   \int_compare:nNf {#2} #1 {#4}
4975   {
4976     #5 {#2}
4977     \exp_args:NNf \__int_step:NnnnN
4978     #1 { \int_eval:n { #2 + #3 } } {#3} {#4} #5
4979   }
4980 }

```

(End definition for `\int_step_function:nnnN`, `__int_step:wwwN`, and `__int_step:NnnnN`. These functions are documented on page 74.)

`\int_step_inline:nnnn`
`\int_step_variable:nnnNn`
`__int_step:NNnnnn`

The approach here is to build a function, with a global integer required to make the nesting safe (as seen in other in line functions), and map that function using `\int_step_function:nnnN`. We put a `__prg_break_point:Nn` so that `map_break` functions from other modules correctly decrement `\g__prg_map_int` before looking for their own break point. The first argument is `\scan_stop:`, so no breaking function will recognize this break point as its own.

```

4981 \cs_new_protected:Npn \int_step_inline:nnnn
4982 {
4983   \int_gincr:N \g__prg_map_int
4984   \exp_args:NNc \__int_step:NNnnnn
4985   \cs_gset:Npn
4986   { __prg_map_ \int_use:N \g__prg_map_int :w }
4987 }
4988 \cs_new_protected:Npn \int_step_variable:nnnNn #1#2#3#4#5
4989 {
4990   \int_gincr:N \g__prg_map_int
4991   \exp_args:NNc \__int_step:NNnnnn
4992   \cs_gset:Npx
4993   { __prg_map_ \int_use:N \g__prg_map_int :w }
4994   {#1}{#2}{#3}
4995   {
4996     \tl_set:Nn \exp_not:N #4 {##1}
4997     \exp_not:n {#5}
4998   }
4999 }
5000 \cs_new_protected:Npn \__int_step:NNnnnn #1#2#3#4#5#6
5001 {
5002   #1 #2 ##1 {#6}
5003   \int_step_function:nnnN {#3} {#4} {#5} #2
5004   \__prg_break_point:Nn \scan_stop: { \int_gdecr:N \g__prg_map_int }
5005 }

```

(End definition for `\int_step_inline:nnnn`, `\int_step_variable:nnnNn`, and `__int_step:NNnnnn`. These functions are documented on page 74.)

8.8 Formatting integers

`\int_to_arabic:n` Nothing exciting here.

```

5006 \cs_new_eq:NN \int_to_arabic:n \int_eval:n

```

(End definition for `\int_to_arabic:n`. This function is documented on page 74.)

`\int_to_symbols:nnn` For conversion of integers to arbitrary symbols the method is in general as follows. The input number (#1) is compared to the total number of symbols available at each place (#2). If the input is larger than the total number of symbols available then the modulus is needed, with one added so that the positions don't have to number from zero. Using an `f`-type expansion, this is done so that the system is recursive. The actual conversion function therefore gets a 'nice' number at each stage. Of course, if the initial input was small enough then there is no problem and everything is easy.

```

5007 \cs_new:Npn \int_to_symbols:nnn #1#2#3
5008 {
5009   \int_compare:nNnTF {#1} > {#2}
5010   {
5011     \exp_args:NNo \exp_args:No \__int_to_symbols:nnnn
5012     {
5013       \int_case:nn
5014       { 1 + \int_mod:nn { #1 - 1 } {#2} }
5015       {#3}
5016     }
5017     {#1} {#2} {#3}
5018   }
5019   { \int_case:nn {#1} {#3} }
5020 }
5021 \cs_new:Npn \__int_to_symbols:nnnn #1#2#3#4
5022 {
5023   \exp_args:Nf \int_to_symbols:nnn
5024   { \int_div_truncate:nn { #2 - 1 } {#3} } {#3} {#4}
5025   #1
5026 }

```

(End definition for `\int_to_symbols:nnn` and `__int_to_symbols:nnnn`. These functions are documented on page 75.)

`\int_to_alph:n` These both use the above function with input functions that make sense for the alphabet in English.

`\int_to_Alph:n`

```

5027 \cs_new:Npn \int_to_alph:n #1
5028 {
5029   \int_to_symbols:nnn {#1} { 26 }
5030   {
5031     { 1 } { a }
5032     { 2 } { b }
5033     { 3 } { c }
5034     { 4 } { d }
5035     { 5 } { e }
5036     { 6 } { f }
5037     { 7 } { g }
5038     { 8 } { h }
5039     { 9 } { i }
5040     { 10 } { j }
5041     { 11 } { k }
5042     { 12 } { l }
5043     { 13 } { m }
5044     { 14 } { n }
5045     { 15 } { o }
5046     { 16 } { p }
5047     { 17 } { q }

```



```

5048      { 18 } { r }
5049      { 19 } { s }
5050      { 20 } { t }
5051      { 21 } { u }
5052      { 22 } { v }
5053      { 23 } { w }
5054      { 24 } { x }
5055      { 25 } { y }
5056      { 26 } { z }
5057    }
5058  }
5059  \cs_new:Npn \int_to_Alph:n #1
5060  {
5061    \int_to_symbols:nnn {#1} { 26 }
5062    {
5063      { 1 } { A }
5064      { 2 } { B }
5065      { 3 } { C }
5066      { 4 } { D }
5067      { 5 } { E }
5068      { 6 } { F }
5069      { 7 } { G }
5070      { 8 } { H }
5071      { 9 } { I }
5072      { 10 } { J }
5073      { 11 } { K }
5074      { 12 } { L }
5075      { 13 } { M }
5076      { 14 } { N }
5077      { 15 } { O }
5078      { 16 } { P }
5079      { 17 } { Q }
5080      { 18 } { R }
5081      { 19 } { S }
5082      { 20 } { T }
5083      { 21 } { U }
5084      { 22 } { V }
5085      { 23 } { W }
5086      { 24 } { X }
5087      { 25 } { Y }
5088      { 26 } { Z }
5089    }
5090  }

```

(End definition for `\int_to_alph:n` and `\int_to_Alph:n`. These functions are documented on page 75.)

| | | |
|--|---|--|
| <pre> \int_to_base:nn \int_to_Base:nn __int_to_base:nn __int_to_Base:nn __int_to_base:nnN __int_to_Base:nnN __int_to_base:nnnN __int_to_Base:nnnN __int_to_letter:n __int_to_Letter:n </pre> | <pre> 5091 \cs_new:Npn \int_to_base:nn #1 5092 { \exp_args:Nf __int_to_base:nn { \int_eval:n {#1} } } 5093 \cs_new:Npn \int_to_Base:nn #1 5094 { \exp_args:Nf __int_to_Base:nn { \int_eval:n {#1} } } 5095 \cs_new:Npn __int_to_base:nn #1#2 </pre> | <p>Converting from base ten (#1) to a second base (#2) starts with computing #1: if it is a complicated calculation, we shouldn't perform it twice. Then check the sign, store it, either - or <code>\c_empty_tl</code>, and feed the absolute value to the next auxiliary function.</p> |
|--|---|--|

```

5096 {
5097   \int_compare:nNnTF {#1} < 0
5098     { \exp_args:No \__int_to_base:nnN { \use_none:n #1 } {#2} - }
5099     { \__int_to_base:nnN {#1} {#2} \c_empty_tl }
5100 }
5101 \cs_new:Npn \__int_to_Base:nn #1#2
5102 {
5103   \int_compare:nNnTF {#1} < 0
5104     { \exp_args:No \__int_to_Base:nnN { \use_none:n #1 } {#2} - }
5105     { \__int_to_Base:nnN {#1} {#2} \c_empty_tl }
5106 }

```

Here, the idea is to provide a recursive system to deal with the input. The output is built up after the end of the function. At each pass, the value in #1 is checked to see if it is less than the new base (#2). If it is, then it is converted directly, putting the sign back in front. On the other hand, if the value to convert is greater than or equal to the new base then the modulus and remainder values are found. The modulus is converted to a symbol and put on the right, and the remainder is carried forward to the next round.

```

5107 \cs_new:Npn \__int_to_base:nnN #1#2#3
5108 {
5109   \int_compare:nNnTF {#1} < {#2}
5110     { \exp_last_unbraced:Nf #3 { \__int_to_letter:n {#1} } }
5111     {
5112       \exp_args:Nf \__int_to_base:nnnN
5113         { \__int_to_letter:n { \int_mod:nn {#1} {#2} } }
5114         {#1}
5115         {#2}
5116         #3
5117     }
5118 }
5119 \cs_new:Npn \__int_to_base:nnnN #1#2#3#4
5120 {
5121   \exp_args:Nf \__int_to_base:nnN
5122     { \int_div_truncate:nn {#2} {#3} }
5123     {#3}
5124     #4
5125     #1
5126 }
5127 \cs_new:Npn \__int_to_Base:nnN #1#2#3
5128 {
5129   \int_compare:nNnTF {#1} < {#2}
5130     { \exp_last_unbraced:Nf #3 { \__int_to_Letter:n {#1} } }
5131     {
5132       \exp_args:Nf \__int_to_Base:nnnN
5133         { \__int_to_Letter:n { \int_mod:nn {#1} {#2} } }
5134         {#1}
5135         {#2}
5136         #3
5137     }
5138 }
5139 \cs_new:Npn \__int_to_Base:nnnN #1#2#3#4
5140 {
5141   \exp_args:Nf \__int_to_Base:nnN
5142     { \int_div_truncate:nn {#2} {#3} }

```

```

5143     {#3}
5144     #4
5145     #1
5146 }

```

Convert to a letter only if necessary, otherwise simply return the value unchanged. It would be cleaner to use `\int_case:nn`, but in our case, the cases are contiguous, so it is forty times faster to use the `\if_case:w` primitive. The first `\exp_after:wN` expands the conditional, jumping to the correct case, the second one expands after the resulting character to close the conditional. Since `#1` might be an expression, and not directly a single digit, we need to evaluate it properly, and expand the trailing `\fi:`.

```

5147 \cs_new:Npn \__int_to_letter:n #1
5148 {
5149     \exp_after:wN \exp_after:wN
5150     \if_case:w \__int_eval:w #1 - 10 \__int_eval_end:
5151     a
5152     \or: b
5153     \or: c
5154     \or: d
5155     \or: e
5156     \or: f
5157     \or: g
5158     \or: h
5159     \or: i
5160     \or: j
5161     \or: k
5162     \or: l
5163     \or: m
5164     \or: n
5165     \or: o
5166     \or: p
5167     \or: q
5168     \or: r
5169     \or: s
5170     \or: t
5171     \or: u
5172     \or: v
5173     \or: w
5174     \or: x
5175     \or: y
5176     \or: z
5177     \else: \__int_value:w \__int_eval:w #1 \exp_after:wN \__int_eval_end:
5178     \fi:
5179 }
5180 \cs_new:Npn \__int_to_Letter:n #1
5181 {
5182     \exp_after:wN \exp_after:wN
5183     \if_case:w \__int_eval:w #1 - 10 \__int_eval_end:
5184     A
5185     \or: B
5186     \or: C
5187     \or: D
5188     \or: E
5189     \or: F

```

```

5190     \or: G
5191     \or: H
5192     \or: I
5193     \or: J
5194     \or: K
5195     \or: L
5196     \or: M
5197     \or: N
5198     \or: O
5199     \or: P
5200     \or: Q
5201     \or: R
5202     \or: S
5203     \or: T
5204     \or: U
5205     \or: V
5206     \or: W
5207     \or: X
5208     \or: Y
5209     \or: Z
5210     \else: \__int_value:w \__int_eval:w #1 \exp_after:wN \__int_eval_end:
5211     \fi:
5212 }

```

(End definition for `\int_to_base:nn` and others. These functions are documented on page 76.)

`\int_to_bin:n` Wrappers around the generic function.

```

\int_to_hex:n 5213 \cs_new:Npn \int_to_bin:n #1
\int_to_Hex:n 5214 { \int_to_base:nn {#1} { 2 } }
\int_to_oct:n 5215 \cs_new:Npn \int_to_hex:n #1
5216 { \int_to_base:nn {#1} { 16 } }
5217 \cs_new:Npn \int_to_Hex:n #1
5218 { \int_to_Base:nn {#1} { 16 } }
5219 \cs_new:Npn \int_to_oct:n #1
5220 { \int_to_base:nn {#1} { 8 } }

```

(End definition for `\int_to_bin:n` and others. These functions are documented on page 75.)

`\int_to_roman:n` The `__int_to_roman:w` primitive creates tokens of category code 12 (other). Usually, what is actually wanted is letters. The approach here is to convert the output of the primitive into letters using appropriate control sequence names. That keeps everything expandable. The loop will be terminated by the conversion of the Q.

```

\__int_to_roman:N 5221 \cs_new:Npn \int_to_roman:n #1
\__int_to_roman:N 5222 {
\__int_to_roman_i:w 5223   \exp_after:wN \__int_to_roman:N
\__int_to_roman_v:w 5224   \__int_to_roman:w \int_eval:n {#1} Q
\__int_to_roman_x:w 5225   }
\__int_to_roman_l:w 5226 \cs_new:Npn \__int_to_roman:N #1
\__int_to_roman_c:w 5227 {
\__int_to_roman_d:w 5228   \use:c { __int_to_roman_ #1 :w }
\__int_to_roman_m:w 5229   \__int_to_roman:N
\__int_to_roman_Q:w 5230   }
\__int_to_Roman_i:w 5231 \cs_new:Npn \int_to_Roman:n #1
\__int_to_Roman_v:w 5232 {
\__int_to_Roman_x:w
\__int_to_Roman_l:w
\__int_to_Roman_c:w
\__int_to_Roman_d:w
\__int_to_Roman_m:w
\__int_to_Roman_Q:w

```

```

5233 \exp_after:wN \__int_to_Roman_aux:N
5234 \__int_to_roman:w \int_eval:n {#1} Q
5235 }
5236 \cs_new:Npn \__int_to_Roman_aux:N #1
5237 {
5238 \use:c { \__int_to_Roman_ #1 :w }
5239 \__int_to_Roman_aux:N
5240 }
5241 \cs_new:Npn \__int_to_roman_i:w { i }
5242 \cs_new:Npn \__int_to_roman_v:w { v }
5243 \cs_new:Npn \__int_to_roman_x:w { x }
5244 \cs_new:Npn \__int_to_roman_l:w { l }
5245 \cs_new:Npn \__int_to_roman_c:w { c }
5246 \cs_new:Npn \__int_to_roman_d:w { d }
5247 \cs_new:Npn \__int_to_roman_m:w { m }
5248 \cs_new:Npn \__int_to_roman_Q:w #1 { }
5249 \cs_new:Npn \__int_to_Roman_i:w { I }
5250 \cs_new:Npn \__int_to_Roman_v:w { V }
5251 \cs_new:Npn \__int_to_Roman_x:w { X }
5252 \cs_new:Npn \__int_to_Roman_l:w { L }
5253 \cs_new:Npn \__int_to_Roman_c:w { C }
5254 \cs_new:Npn \__int_to_Roman_d:w { D }
5255 \cs_new:Npn \__int_to_Roman_m:w { M }
5256 \cs_new:Npn \__int_to_Roman_Q:w #1 { }

```

(End definition for `\int_to_roman:n` and others. These functions are documented on page 76.)

8.9 Converting from other formats to integers

```

\__int_pass_signs:wn
\__int_pass_signs_end:wn

```

Called as `__int_pass_signs:wn <signs and digits> \q_stop {<code>}`, this function leaves in the input stream any sign it finds, then inserts the `<code>` before the first non-sign token (and removes `\q_stop`). More precisely, it deletes any `+` and passes any `-` to the input stream, hence should be called in an integer expression.

```

5257 \cs_new:Npn \__int_pass_signs:wn #1
5258 {
5259 \if:w + \if:w - \exp_not:N #1 + \fi: \exp_not:N #1
5260 \exp_after:wN \__int_pass_signs:wn
5261 \else:
5262 \exp_after:wN \__int_pass_signs_end:wn
5263 \exp_after:wN #1
5264 \fi:
5265 }
5266 \cs_new:Npn \__int_pass_signs_end:wn #1 \q_stop #2 { #2 #1 }

```

(End definition for `__int_pass_signs:wn` and `__int_pass_signs_end:wn`.)

```

\int_from_alph:n
\__int_from_alph:nN
\__int_from_alph:N

```

First take care of signs then loop through the input using the `recursion` quarks. The `__int_from_alph:nN` auxiliary collects in its first argument the value obtained so far, and the auxiliary `__int_from_alph:N` converts one letter to an expression which evaluates to the correct number.

```

5267 \cs_new:Npn \int_from_alph:n #1
5268 {
5269 \int_eval:n
5270 {

```

```

5271         \exp_after:wN \_int_pass_signs:wn \tl_to_str:n {#1}
5272         \q_stop { \_int_from_alph:nN { 0 } }
5273         \q_recursion_tail \q_recursion_stop
5274     }
5275 }
5276 \cs_new:Npn \_int_from_alph:nN #1#2
5277 {
5278     \quark_if_recursion_tail_stop_do:Nn #2 {#1}
5279     \exp_args:Nf \_int_from_alph:nN
5280     { \int_eval:n { #1 * 26 + \_int_from_alph:N #2 } }
5281 }
5282 \cs_new:Npn \_int_from_alph:N #1
5283 { '#1 - \int_compare:nNnTF { '#1 } < { 91 } { 64 } { 96 } }

```

(End definition for `\int_from_alph:n`, `_int_from_alph:nN`, and `_int_from_alph:N`. These functions are documented on page 76.)

`\int_from_base:nn` Leave the signs into the integer expression, then loop through characters, collecting the value found so far in the first argument of `_int_from_base:nnN`. To convert a single character, `_int_from_base:N` checks first for digits, then distinguishes lower from upper case letters, turning them into the appropriate number. Note that this auxiliary does not use `\int_eval:n`, hence is not safe for general use.

```

5284 \cs_new:Npn \int_from_base:nn #1#2
5285 {
5286     \int_eval:n
5287     {
5288         \exp_after:wN \_int_pass_signs:wn \tl_to_str:n {#1}
5289         \q_stop { \_int_from_base:nnN { 0 } {#2} }
5290         \q_recursion_tail \q_recursion_stop
5291     }
5292 }
5293 \cs_new:Npn \_int_from_base:nnN #1#2#3
5294 {
5295     \quark_if_recursion_tail_stop_do:Nn #3 {#1}
5296     \exp_args:Nf \_int_from_base:nnN
5297     { \int_eval:n { #1 * #2 + \_int_from_base:N #3 } }
5298     {#2}
5299 }
5300 \cs_new:Npn \_int_from_base:N #1
5301 {
5302     \int_compare:nNnTF { '#1 } < { 58 }
5303     {#1}
5304     { '#1 - \int_compare:nNnTF { '#1 } < { 91 } { 55 } { 87 } }
5305 }

```

(End definition for `\int_from_base:nn`, `_int_from_base:nnN`, and `_int_from_base:N`. These functions are documented on page 77.)

`\int_from_bin:n` Wrappers around the generic function.

```

\int_from_hex:n
\int_from_oct:n
5306 \cs_new:Npn \int_from_bin:n #1
5307 { \int_from_base:nn {#1} { 2 } }
5308 \cs_new:Npn \int_from_hex:n #1
5309 { \int_from_base:nn {#1} { 16 } }
5310 \cs_new:Npn \int_from_oct:n #1
5311 { \int_from_base:nn {#1} { 8 } }

```

(End definition for `\int_from_bin:n`, `\int_from_hex:n`, and `\int_from_oct:n`. These functions are documented on page 76.)

| | |
|---------------------------------------|--|
| <code>\c__int_from_roman_i_int</code> | Constants used to convert from Roman numerals to integers. |
| <code>\c__int_from_roman_v_int</code> | 5312 <code>\int_const:cn { c__int_from_roman_i_int } { 1 }</code> |
| <code>\c__int_from_roman_x_int</code> | 5313 <code>\int_const:cn { c__int_from_roman_v_int } { 5 }</code> |
| <code>\c__int_from_roman_l_int</code> | 5314 <code>\int_const:cn { c__int_from_roman_x_int } { 10 }</code> |
| <code>\c__int_from_roman_c_int</code> | 5315 <code>\int_const:cn { c__int_from_roman_l_int } { 50 }</code> |
| <code>\c__int_from_roman_d_int</code> | 5316 <code>\int_const:cn { c__int_from_roman_c_int } { 100 }</code> |
| <code>\c__int_from_roman_m_int</code> | 5317 <code>\int_const:cn { c__int_from_roman_d_int } { 500 }</code> |
| <code>\c__int_from_roman_I_int</code> | 5318 <code>\int_const:cn { c__int_from_roman_m_int } { 1000 }</code> |
| <code>\c__int_from_roman_V_int</code> | 5319 <code>\int_const:cn { c__int_from_roman_I_int } { 1 }</code> |
| <code>\c__int_from_roman_X_int</code> | 5320 <code>\int_const:cn { c__int_from_roman_V_int } { 5 }</code> |
| <code>\c__int_from_roman_L_int</code> | 5321 <code>\int_const:cn { c__int_from_roman_X_int } { 10 }</code> |
| <code>\c__int_from_roman_C_int</code> | 5322 <code>\int_const:cn { c__int_from_roman_L_int } { 50 }</code> |
| <code>\c__int_from_roman_D_int</code> | 5323 <code>\int_const:cn { c__int_from_roman_C_int } { 100 }</code> |
| <code>\c__int_from_roman_M_int</code> | 5324 <code>\int_const:cn { c__int_from_roman_D_int } { 500 }</code> |
| | 5325 <code>\int_const:cn { c__int_from_roman_M_int } { 1000 }</code> |

(End definition for `\c__int_from_roman_i_int` and others.)

| | |
|--|---|
| <code>\int_from_roman:n</code> | The method here is to iterate through the input, finding the appropriate value for each |
| <code>__int_from_roman:NN</code> | letter and building up a sum. This is then evaluated by \TeX . If any unknown letter is |
| <code>__int_from_roman_error:w</code> | found, skip to the closing parenthesis and insert <code>*0-1</code> afterwards, to replace the value by |
| | <code>-1</code> . |

```

5326 \cs_new:Npn \int_from_roman:n #1
5327 {
5328   \int_eval:n
5329   {
5330     (
5331       0
5332       \exp_after:wN \__int_from_roman:NN \tl_to_str:n {#1}
5333       \q_recursion_tail \q_recursion_tail \q_recursion_stop
5334     )
5335   }
5336 }
5337 \cs_new:Npn \__int_from_roman:NN #1#2
5338 {
5339   \quark_if_recursion_tail_stop:N #1
5340   \int_if_exist:cF { c__int_from_roman_ #1 _int }
5341   { \__int_from_roman_error:w }
5342   \quark_if_recursion_tail_stop_do:Nn #2
5343   { + \use:c { c__int_from_roman_ #1 _int } }
5344   \int_if_exist:cF { c__int_from_roman_ #2 _int }
5345   { \__int_from_roman_error:w }
5346   \int_compare:nNnTF
5347   { \use:c { c__int_from_roman_ #1 _int } }
5348   <
5349   { \use:c { c__int_from_roman_ #2 _int } }
5350   {
5351     + \use:c { c__int_from_roman_ #2 _int }
5352     - \use:c { c__int_from_roman_ #1 _int }
5353     \__int_from_roman:NN
5354   }

```

```

5355     {
5356       + \use:c { c__int_from_roman_ #1 _int }
5357       \__int_from_roman:NN #2
5358     }
5359   }
5360 \cs_new:Npn \__int_from_roman_error:w #1 \q_recursion_stop #2
5361   { #2 * 0 - 1 }

```

(End definition for `\int_from_roman:n`, `__int_from_roman:NN`, and `__int_from_roman_error:w`. These functions are documented on page 77.)

8.10 Viewing integer

`\int_show:N` Diagnostics.
`\int_show:c` 5362 `\cs_new_eq:NN \int_show:N __kernel_register_show:N`
`__int_show:nN` 5363 `\cs_generate_variant:Nn \int_show:N { c }`

(End definition for `\int_show:N` and `__int_show:nN`. These functions are documented on page 77.)

`\int_show:n` We don't use the TeX primitive `\showthe` to show integer expressions: this gives a more unified output.

```

5364 \cs_new_protected:Npn \int_show:n
5365   { \__msg_show_wrap:Nn \int_eval:n }

```

(End definition for `\int_show:n`. This function is documented on page 77.)

`\int_log:N` Diagnostics.
`\int_log:c` 5366 `\cs_new_eq:NN \int_log:N __kernel_register_log:N`
5367 `\cs_generate_variant:Nn \int_log:N { c }`

(End definition for `\int_log:N`. This function is documented on page 77.)

`\int_log:n` Redirect output of `\int_show:n` to the log.

```

5368 \cs_new_protected:Npn \int_log:n
5369   { \__msg_log_next: \int_show:n }

```

(End definition for `\int_log:n`. This function is documented on page 77.)

8.11 Constant integers

`\c_zero` Again, in `l3basics`

(End definition for `\c_zero`. This variable is documented on page 78.)

`\c_one` Low-number values not previously defined.
`\c_two` 5370 `\int_const:Nn \c_one { 1 }`
`\c_three` 5371 `\int_const:Nn \c_two { 2 }`
`\c_four` 5372 `\int_const:Nn \c_three { 3 }`
`\c_five` 5373 `\int_const:Nn \c_four { 4 }`
`\c_six` 5374 `\int_const:Nn \c_five { 5 }`
`\c_seven` 5375 `\int_const:Nn \c_six { 6 }`
`\c_eight` 5376 `\int_const:Nn \c_seven { 7 }`
`\c_nine` 5377 `\int_const:Nn \c_eight { 8 }`
`\c_ten` 5378 `\int_const:Nn \c_nine { 9 }`
`\c_eleven` 5379 `\int_const:Nn \c_ten { 10 }`
`\c_twelve`
`\c_thirteen`
`\c_fourteen`
`\c_fifteen`
`\c_sixteen`


```

5380 \int_const:Nn \c_eleven { 11 }
5381 \int_const:Nn \c_twelve { 12 }
5382 \int_const:Nn \c_thirteen { 13 }
5383 \int_const:Nn \c_fourteen { 14 }
5384 \int_const:Nn \c_fifteen { 15 }
5385 \int_const:Nn \c_sixteen { 16 }

```

(End definition for `\c_one` and others. These variables are documented on page 78.)

`\c_thirty_two` One middling value.

```

5386 \int_const:Nn \c_thirty_two { 32 }

```

(End definition for `\c_thirty_two`. This variable is documented on page 78.)

`\c_two_hundred_fifty_five` Two classic mid-range integer constants.

```

\c_two_hundred_fifty_six 5387 \int_const:Nn \c_two_hundred_fifty_five { 255 }
5388 \int_const:Nn \c_two_hundred_fifty_six { 256 }

```

(End definition for `\c_two_hundred_fifty_five` and `\c_two_hundred_fifty_six`. These variables are documented on page 78.)

`\c_one_hundred` Simple runs of powers of ten.

```

\c_one_thousand 5389 \int_const:Nn \c_one_hundred { 100 }
\c_ten_thousand 5390 \int_const:Nn \c_one_thousand { 1000 }
5391 \int_const:Nn \c_ten_thousand { 10000 }

```

(End definition for `\c_one_hundred`, `\c_one_thousand`, and `\c_ten_thousand`. These variables are documented on page 78.)

`\c_max_int` The largest number allowed is $2^{31} - 1$

```

5392 \int_const:Nn \c_max_int { 2 147 483 647 }

```

(End definition for `\c_max_int`. This variable is documented on page 78.)

`\c_max_char_int` The largest character code is 1114111 (hexadecimal 10FFFF) in X_YTeX and LuaTeX and 255 in other engines. In many places pTeX and upTeX support larger character codes but for instance the values of `\lccode` are restricted to $[0, 255]$.

```

5393 \int_const:Nn \c_max_char_int
5394 {
5395   \if_int_odd:w 0
5396     \cs_if_exist:NT \luatex luatexversion:D { 1 }
5397     \cs_if_exist:NT \xetex XeTeXversion:D { 1 } ~
5398     "10FFFF
5399   \else:
5400     "FF
5401   \fi:
5402 }

```

(End definition for `\c_max_char_int`. This variable is documented on page 78.)

8.12 Scratch integers

`\l_tmpa_int` We provide two local and two global scratch counters, maybe we need more or less.

```
\l_tmpb_int 5403 \int_new:N \l_tmpa_int
\g_tmpa_int 5404 \int_new:N \l_tmpb_int
\g_tmpb_int 5405 \int_new:N \g_tmpa_int
           5406 \int_new:N \g_tmpb_int
```

(End definition for `\l_tmpa_int` and others. These variables are documented on page 78.)

8.13 Deprecated

`\c_minus_one` The actual allocation mechanism is in `l3alloc`; it requires `\c_one` to be defined. In package mode, reuse `\m@ne`.

```
5407 \<package>
5408 \cs_new_eq:NN \c_minus_one \m@ne
5409 \</package>
5410 \<initex>
5411 \int_const:Nn \c_minus_one { -1 }
5412 \</initex>
```

(End definition for `\c_minus_one`.)

```
5413 \</initex | package>
```

9 l3flag implementation

```
5414 \<initex | package>
```

```
5415 \<@@=flag>
```

The following test files are used for this code: `m3flag001`.

9.1 Non-expandable flag commands

The height h of a flag (initially zero) is stored by setting control sequences of the form `\flag <name> <integer>` to `\relax` for $0 \leq \langle integer \rangle < h$. When a flag is raised, a “trap” function `\flag <name>` is called. The existence of this function is also used to test for the existence of a flag.

`\flag_new:n` For each flag, we define a “trap” function, which by default simply increases the flag by 1 by letting the appropriate control sequence to `\relax`. This can be done expandably!

```
5416 \cs_new_protected:Npn \flag_new:n #1
5417 {
5418   \cs_new:cpn { flag~#1 } ##1 ;
5419   { \exp_after:wN \use_none:n \cs:w flag~#1~##1 \cs_end: }
5420 }
```

(End definition for `\flag_new:n`. This function is documented on page 81.)

`\flag_clear:n` Undefine control sequences, starting from the 0 flag, upwards, until reaching an undefined control sequence. We don’t use `\cs_undefine:c` because that would act globally.

```
\__flag_clear:wn 5421 \cs_new_protected:Npn \flag_clear:n { \__flag_clear:wn 0 ; }
5422 \cs_new_protected:Npn \__flag_clear:wn #1 ; #2
5423 {
5424   \if_cs_exist:w flag~#2~#1 \cs_end:
```

```

5425     \cs_set_eq:cN { flag~#2~#1 } \tex_undefined:D
5426     \exp_after:wN \__flag_clear:wn
5427     \__int_value:w \__int_eval:w 1 + #1
5428   \else:
5429     \use_i:nnn
5430   \fi:
5431   ; {#2}
5432 }

```

(End definition for `\flag_clear:n` and `__flag_clear:wn`. These functions are documented on page 81.)

`\flag_clear_new:n` As for other datatypes, clear the *flag* or create a new one, as appropriate.

```

5433 \cs_new_protected:Npn \flag_clear_new:n #1
5434 { \flag_if_exist:nTF {#1} { \flag_clear:n } { \flag_new:n } {#1} }

```

(End definition for `\flag_clear_new:n`. This function is documented on page 81.)

`\flag_show:n` Show the height (terminal or log file) using appropriate `l3msg` auxiliaries.

```

\flag_log:n
5435 \cs_new_protected:Npn \flag_show:n #1
5436 {
5437   \exp_args:Nc \__msg_show_variable:NNNnn { flag~#1 } \cs_if_exist:NTF ? { }
5438   { > ~ flag ~ #1 ~ height = \flag_height:n {#1} }
5439 }
5440 \cs_new_protected:Npn \flag_log:n
5441 { \__msg_log_next: \flag_show:n }

```

(End definition for `\flag_show:n` and `\flag_log:n`. These functions are documented on page 81.)

9.2 Expandable flag commands

`\flag_if_exist_p:n` A flag exist if the corresponding trap `\flag <flag name>:n` is defined.

`\flag_if_exist:nTF`

```

5442 \prg_new_conditional:Npnn \flag_if_exist:n #1 { p , T , F , TF }
5443 {
5444   \cs_if_exist:cTF { flag~#1 }
5445   { \prg_return_true: } { \prg_return_false: }
5446 }

```

(End definition for `\flag_if_exist:nTF`. This function is documented on page 82.)

`\flag_if_raised_p:n` Test if the flag has a non-zero height, by checking the 0 control sequence.

`\flag_if_raised:nTF`

```

5447 \prg_new_conditional:Npnn \flag_if_raised:n #1 { p , T , F , TF }
5448 {
5449   \if_cs_exist:w flag~#1~0 \cs_end:
5450   \prg_return_true:
5451   \else:
5452   \prg_return_false:
5453   \fi:
5454 }

```

(End definition for `\flag_if_raised:nTF`. This function is documented on page 82.)

\flag_height:n Extract the value of the flag by going through all of the control sequences starting from 0.

```

5455 \cs_new:Npn \flag_height:n { \__flag_height_loop:wn 0; }
5456 \cs_new:Npn \__flag_height_loop:wn #1 ; #2
5457 {
5458   \if_cs_exist:w flag~#2~#1 \cs_end:
5459   \exp_after:wN \__flag_height_loop:wn \__int_value:w \__int_eval:w 1 +
5460   \else:
5461   \exp_after:wN \__flag_height_end:wn
5462   \fi:
5463   #1 ; {#2}
5464 }
5465 \cs_new:Npn \__flag_height_end:wn #1 ; #2 {#1}

```

(End definition for \flag_height:n, __flag_height_loop:wn, and __flag_height_end:wn. These functions are documented on page 82.)

\flag_raise:n Simply apply the trap to the height, after expanding the latter.

```

5466 \cs_new:Npn \flag_raise:n #1
5467 {
5468   \cs:w flag~#1 \exp_after:wN \cs_end:
5469   \__int_value:w \flag_height:n {#1} ;
5470 }

```

(End definition for \flag_raise:n. This function is documented on page 82.)

9.3 Option check-declarations

__flag_chk_exist:n In package mode, there is an option to check all variables used are defined. Since flags are not implemented in terms of other variables, we need to add checks by hand. Not all functions need to be patched because some are defined in terms of others.

```

5471 (*package)
5472 \tex_ifodd:D \l@expl@check@declarations@bool
5473 \cs_set_protected:Npn \flag_clear:n #1
5474 {
5475   \exp_args:Nc \__chk_if_exist_var:N { flag~#1 }
5476   \__flag_clear:wn 0 ; {#1}
5477 }
5478 \cs_set:Npn \__flag_chk_exist:n #1
5479 {
5480   \flag_if_exist:nF {#1}
5481   {
5482     \_msg_kernel_expandable_error:nnn
5483     { kernel } { bad-variable } { flag~#1~ }
5484   }
5485 }
5486 \cs_set:Npn \flag_height:n #1
5487 {
5488   \__flag_chk_exist:n {#1}
5489   \__flag_height_loop:wn 0; {#1}
5490 }
5491 \prg_set_conditional:Npnn \flag_if_raised:n #1 { p , T , F , TF }
5492 {
5493   \__flag_chk_exist:n {#1}

```

```

5494     \if_cs_exist:w flag~#1~0 \cs_end:
5495     \prg_return_true:
5496   \else:
5497     \prg_return_false:
5498   \fi:
5499 }
5500 \fi:
5501 \end{package}

(End definition for \_flag_chk_exist:n.)

5502 \end{initex} \package

```

10 l3quark implementation

The following test files are used for this code: *m3quark001.lvt*.

```

5503 \begin{initex} \package

```

10.1 Quarks

```

5504 \@@=quark

```

\quark_new:N Allocate a new quark.

```

5505 \cs_new_protected:Npn \quark_new:N #1 { \tl_const:Nn #1 {#1} }

```

(End definition for \quark_new:N. This function is documented on page 83.)

\q_nil Some “public” quarks. \q_stop is an “end of argument” marker, \q_nil is a empty value
\q_mark and \q_no_value marks an empty argument.
\q_no_value
\q_stop

```

5506 \quark_new:N \q_nil
5507 \quark_new:N \q_mark
5508 \quark_new:N \q_no_value
5509 \quark_new:N \q_stop

```

(End definition for \q_nil and others. These variables are documented on page 84.)

\q_recursion_tail Quarks for ending recursions. Only ever used there! \q_recursion_tail is appended to
\q_recursion_stop whatever list structure we are doing recursion on, meaning it is added as a proper list
item with whatever list separator is in use. \q_recursion_stop is placed directly after
the list.

```

5510 \quark_new:N \q_recursion_tail
5511 \quark_new:N \q_recursion_stop

```

(End definition for \q_recursion_tail and \q_recursion_stop. These variables are documented on page 85.)

\quark_if_recursion_tail_stop:N When doing recursions, it is easy to spend a lot of time testing if the end marker has
\quark_if_recursion_tail_stop_do:Nn been found. To avoid this, a dedicated end marker is used each time a recursion is set up.
Thus if the marker is found everything can be wrapper up and finished off. The simple
case is when the test can guarantee that only a single token is being tested. In this case,
there is just a dedicated copy of the standard quark test. Both a gobbling version and
one inserting end code are provided.

```

5512 \cs_new:Npn \quark_if_recursion_tail_stop:N #1
5513 {

```

```

5514     \if_meaning:w \q_recursion_tail #1
5515     \exp_after:wN \use_none_delimit_by_q_recursion_stop:w
5516   \fi:
5517 }
5518 \cs_new:Npn \quark_if_recursion_tail_stop_do:Nn #1
5519 {
5520   \if_meaning:w \q_recursion_tail #1
5521   \exp_after:wN \use_i_delimit_by_q_recursion_stop:nw
5522   \else:
5523   \exp_after:wN \use_none:n
5524   \fi:
5525 }

```

(End definition for \quark_if_recursion_tail_stop:N and \quark_if_recursion_tail_stop_do:Nn. These functions are documented on page 85.)

\quark_if_recursion_tail_stop:n See \quark_if_nil:nTF for the details. Expanding __quark_if_recursion_tail:w once in front of the tokens chosen here gives an empty result if and only if #1 is exactly \q_recursion_tail.

```

\quark_if_recursion_tail_stop:o
\quark_if_recursion_tail_stop_do:nn
\quark_if_recursion_tail_stop_do:n
\__quark_if_recursion_tail:w
5526 \cs_new:Npn \quark_if_recursion_tail_stop:n #1
5527 {
5528   \tl_if_empty:oTF
5529   { \__quark_if_recursion_tail:w {} #1 {} ?! \q_recursion_tail ??? }
5530   { \use_none_delimit_by_q_recursion_stop:w }
5531   { }
5532 }
5533 \cs_new:Npn \quark_if_recursion_tail_stop_do:nn #1
5534 {
5535   \tl_if_empty:oTF
5536   { \__quark_if_recursion_tail:w {} #1 {} ?! \q_recursion_tail ??? }
5537   { \use_i_delimit_by_q_recursion_stop:nw }
5538   { \use_none:n }
5539 }
5540 \cs_new:Npn \__quark_if_recursion_tail:w
5541   #1 \q_recursion_tail #2 ? #3 ?! { #1 #2 }
5542 \cs_generate_variant:Nn \quark_if_recursion_tail_stop:n { o }
5543 \cs_generate_variant:Nn \quark_if_recursion_tail_stop_do:nn { o }

```

(End definition for \quark_if_recursion_tail_stop:n, \quark_if_recursion_tail_stop_do:nn, and __quark_if_recursion_tail:w. These functions are documented on page 85.)

__quark_if_recursion_tail_break:NN Analogs of the \quark_if_recursion_tail_stop... functions. Break the mapping using #2.

```

\__quark_if_recursion_tail_break:nN
5544 \cs_new:Npn \__quark_if_recursion_tail_break:NN #1#2
5545 {
5546   \if_meaning:w \q_recursion_tail #1
5547   \exp_after:wN #2
5548   \fi:
5549 }
5550 \cs_new:Npn \__quark_if_recursion_tail_break:nN #1#2
5551 {
5552   \tl_if_empty:oTF
5553   { \__quark_if_recursion_tail:w {} #1 {} ?! \q_recursion_tail ??? }
5554   { #2 }
5555   { }

```

```
5556 }
```

(End definition for `_quark_if_recursion_tail_break:NN` and `_quark_if_recursion_tail_break:nN`.)

`\quark_if_nil_p:N` Here we test if we found a special quark as the first argument. We better start with
`\quark_if_nil:N \underline{TF}` `\q_no_value` as the first argument since the whole thing may otherwise loop if #1 is
`\quark_if_no_value_p:N` wrongly given a string like aabc instead of a single token.⁸

```
\quark_if_no_value_p:c 5557 \prg_new_conditional:Npnn \quark_if_nil:N #1 { p, T , F , TF }
\quark_if_no_value:N $\underline{TF}$  5558 {
\quark_if_no_value:c $\underline{TF}$  5559   \if_meaning:w \q_nil #1
5560     \prg_return_true:
5561   \else:
5562     \prg_return_false:
5563   \fi:
5564 }
5565 \prg_new_conditional:Npnn \quark_if_no_value:N #1 { p, T , F , TF }
5566 {
5567   \if_meaning:w \q_no_value #1
5568     \prg_return_true:
5569   \else:
5570     \prg_return_false:
5571   \fi:
5572 }
5573 \cs_generate_variant:Nn \quark_if_no_value_p:N { c }
5574 \cs_generate_variant:Nn \quark_if_no_value:NT { c }
5575 \cs_generate_variant:Nn \quark_if_no_value:NF { c }
5576 \cs_generate_variant:Nn \quark_if_no_value:NTF { c }
```

(End definition for `\quark_if_nil:NTF` and `\quark_if_no_value:NTF`. These functions are documented on page 84.)

`\quark_if_nil_p:n` Let us explain `\quark_if_nil:n(TF)`. Expanding `_quark_if_nil:w` once is safe
`\quark_if_nil_p:V` thanks to the trailing `\q_nil ??!`. The result of expanding once is empty if and only
`\quark_if_nil_p:o` if both delimited arguments #1 and #2 are empty and #3 is delimited by the last to-
`\quark_if_nil:n \underline{TF}` kens ?!. Thanks to the leading {}, the argument #1 is empty if and only if the argument
`\quark_if_nil:VT \underline{F}` of `\quark_if_nil:n` starts with `\q_nil`. The argument #2 is empty if and only if this
`\quark_if_nil:o \underline{TF}` `\q_nil` is followed immediately by ? or by {}?, coming either from the trailing tokens in
`\quark_if_no_value_p:n` the definition of `\quark_if_nil:n`, or from its argument. In the first case, `_quark_-`
`\quark_if_no_value:N \underline{TF}` `if_nil:w` is followed by `{}\q_nil {}? !\q_nil ??!`, hence #3 is delimited by the final ?!,
`_quark_if_nil:w` and the test returns true as wanted. In the second case, the result is not empty since
`_quark_if_no_value:w` the first ?! in the definition of `\quark_if_nil:n` stop #3.

```
5577 \prg_new_conditional:Npnn \quark_if_nil:n #1 { p, T , F , TF }
5578 {
5579   \_tl_if_empty_return:o
5580   { \_quark_if_nil:w {} #1 {} ? ! \q_nil ? ? ! }
5581 }
5582 \cs_new:Npn \_quark_if_nil:w #1 \q_nil #2 ? #3 ? ! { #1 #2 }
5583 \prg_new_conditional:Npnn \quark_if_no_value:n #1 { p, T , F , TF }
5584 {
5585   \_tl_if_empty_return:o
5586   { \_quark_if_no_value:w {} #1 {} ? ! \q_no_value ? ? ! }
5587 }
```

⁸It may still loop in special circumstances however!

```

5588 \cs_new:Npn \__quark_if_no_value:w #1 \q_no_value #2 ? #3 ? ! { #1 #2 }
5589 \cs_generate_variant:Nn \quark_if_nil_p:n { V , o }
5590 \cs_generate_variant:Nn \quark_if_nil:nTF { V , o }
5591 \cs_generate_variant:Nn \quark_if_nil:nT { V , o }
5592 \cs_generate_variant:Nn \quark_if_nil:nF { V , o }

```

(End definition for \quark_if_nil:nTF and others. These functions are documented on page 84.)

\q_tl_act_mark These private quarks are needed by l3tl, but that is loaded before the quark module,
 \q_tl_act_stop hence their definition is deferred.

```

5593 \quark_new:N \q_tl_act_mark
5594 \quark_new:N \q_tl_act_stop

```

(End definition for \q_tl_act_mark and \q_tl_act_stop.)

10.2 Scan marks

```

5595 <@@=scan>

```

\g__scan_marks_tl The list of all scan marks currently declared.

```

5596 \tl_new:N \g__scan_marks_tl

```

(End definition for \g__scan_marks_tl.)

__scan_new:N Check whether the variable is already a scan mark, then declare it to be equal to \scan_stop: globally.

```

5597 \cs_new_protected:Npn \__scan_new:N #1
5598 {
5599   \tl_if_in:NnTF \g__scan_marks_tl { #1 }
5600   {
5601     \__msg_kernel_error:nnx { kernel } { scanmark-already-defined }
5602     { \token_to_str:N #1 }
5603   }
5604   {
5605     \tl_gput_right:Nn \g__scan_marks_tl {#1}
5606     \cs_new_eq:NN #1 \scan_stop:
5607   }
5608 }

```

(End definition for __scan_new:N.)

\s__stop We only declare one scan mark here, more can be defined by specific modules.

```

5609 \__scan_new:N \s__stop

```

(End definition for \s__stop.)

_use_none_delimit_by_s__stop:w Similar to \use_none_delimit_by_q_stop:w.

```

5610 \cs_new:Npn \_use_none_delimit_by_s__stop:w #1 \s__stop { }

```

(End definition for _use_none_delimit_by_s__stop:w.)

\s__seq This private scan mark is needed by l3seq, but that is loaded before the quark module, hence its definition is deferred.

```

5611 \__scan_new:N \s__seq

```

(End definition for \s__seq.)

```

5612 </initex | package>

```


11 l3prg implementation

The following test files are used for this code: *m3prg001.lvt,m3prg002.lvt,m3prg003.lvt*.

5613 \langle *initex | package \rangle

11.1 Primitive conditionals

\backslash if_bool:N Those two primitive TeX conditionals are synonyms.

\backslash if_predicate:w 5614 \backslash cs_new_eq:NN \backslash if_bool:N \backslash tex_ifodd:D

5615 \backslash cs_new_eq:NN \backslash if_predicate:w \backslash tex_ifodd:D

(End definition for \backslash if_bool:N and \backslash if_predicate:w. These functions are documented on page 94.)

11.2 Defining a set of conditional functions

These are all defined in l3basics, as they are needed “early”. This is just a reminder!

(End definition for \backslash prg_set_conditional:Npnn and others. These functions are documented on page 88.)

11.3 The boolean data type

5616 \langle @@=bool \rangle

Boolean variables have to be initiated when they are created. Other than that there is not much to say here.

5617 \backslash cs_new_protected:Npn \backslash bool_new:N #1 { \backslash cs_new_eq:NN #1 \backslash c_false_bool }

5618 \backslash cs_generate_variant:Nn \backslash bool_new:N { c }

(End definition for \backslash bool_new:N. This function is documented on page 90.)

\backslash bool_set_true:N Setting is already pretty easy.

\backslash bool_set_true:c 5619 \backslash cs_new_protected:Npn \backslash bool_set_true:N #1

\backslash bool_gset_true:N 5620 { \backslash cs_set_eq:NN #1 \backslash c_true_bool }

\backslash bool_gset_true:c 5621 \backslash cs_new_protected:Npn \backslash bool_set_false:N #1

\backslash bool_set_false:N 5622 { \backslash cs_set_eq:NN #1 \backslash c_false_bool }

\backslash bool_set_false:c 5623 \backslash cs_new_protected:Npn \backslash bool_gset_true:N #1

\backslash bool_gset_true:N 5624 { \backslash cs_gset_eq:NN #1 \backslash c_true_bool }

\backslash bool_gset_false:N 5625 \backslash cs_new_protected:Npn \backslash bool_gset_false:N #1

\backslash bool_gset_false:c 5626 { \backslash cs_gset_eq:NN #1 \backslash c_false_bool }

5627 \backslash cs_generate_variant:Nn \backslash bool_set_true:N { c }

5628 \backslash cs_generate_variant:Nn \backslash bool_set_false:N { c }

5629 \backslash cs_generate_variant:Nn \backslash bool_gset_true:N { c }

5630 \backslash cs_generate_variant:Nn \backslash bool_gset_false:N { c }

(End definition for \backslash bool_set_true:N and others. These functions are documented on page 90.)

\backslash bool_set_eq:NN The usual copy code.

\backslash bool_set_eq:cN 5631 \backslash cs_new_eq:NN \backslash bool_set_eq:NN \backslash cs_set_eq:NN

\backslash bool_set_eq:Nc 5632 \backslash cs_new_eq:NN \backslash bool_set_eq:Nc \backslash cs_set_eq:Nc

\backslash bool_set_eq:cc 5633 \backslash cs_new_eq:NN \backslash bool_set_eq:cN \backslash cs_set_eq:cN

\backslash bool_gset_eq:NN 5634 \backslash cs_new_eq:NN \backslash bool_set_eq:cc \backslash cs_set_eq:cc

\backslash bool_gset_eq:cN 5635 \backslash cs_new_eq:NN \backslash bool_gset_eq:NN \backslash cs_gset_eq:NN

\backslash bool_gset_eq:Nc 5636 \backslash cs_new_eq:NN \backslash bool_gset_eq:Nc \backslash cs_gset_eq:Nc

\backslash bool_gset_eq:cN 5637 \backslash cs_new_eq:NN \backslash bool_gset_eq:cN \backslash cs_gset_eq:cN

\backslash bool_gset_eq:cc 5638 \backslash cs_new_eq:NN \backslash bool_gset_eq:cc \backslash cs_gset_eq:cc

(End definition for `\bool_set_eq:NN` and `\bool_gset_eq:NN`. These functions are documented on page 91.)

`\bool_set:Nn` This function evaluates a boolean expression and assigns the first argument the meaning
`\bool_set:cn` `\c_true_bool` or `\c_false_bool`.
`\bool_gset:Nn`
`\bool_gset:cn`

```

5639 \cs_new_protected:Npn \bool_set:Nn #1#2
5640 { \tex_chardef:D #1 = \bool_if_p:n {#2} }
5641 \cs_new_protected:Npn \bool_gset:Nn #1#2
5642 { \tex_global:D \tex_chardef:D #1 = \bool_if_p:n {#2} }
5643 \cs_generate_variant:Nn \bool_set:Nn { c }
5644 \cs_generate_variant:Nn \bool_gset:Nn { c }

```

(End definition for `\bool_set:Nn` and `\bool_gset:Nn`. These functions are documented on page 91.)

Booleans are not based on token lists but do need checking: this code complements similar material in `l3tl`.

```

5645 (*package)
5646 \if_bool:N \l@expl@check@declarations@bool
5647 \cs_set_protected:Npn \bool_set_true:N #1
5648 {
5649   \__chk_if_exist_var:N #1
5650   \cs_set_eq:NN #1 \c_true_bool
5651 }
5652 \cs_set_protected:Npn \bool_set_false:N #1
5653 {
5654   \__chk_if_exist_var:N #1
5655   \cs_set_eq:NN #1 \c_false_bool
5656 }
5657 \cs_set_protected:Npn \bool_gset_true:N #1
5658 {
5659   \__chk_if_exist_var:N #1
5660   \cs_gset_eq:NN #1 \c_true_bool
5661 }
5662 \cs_set_protected:Npn \bool_gset_false:N #1
5663 {
5664   \__chk_if_exist_var:N #1
5665   \cs_gset_eq:NN #1 \c_false_bool
5666 }
5667 \cs_set_protected:Npn \bool_set_eq:NN #1
5668 {
5669   \__chk_if_exist_var:N #1
5670   \cs_set_eq:NN #1
5671 }
5672 \cs_set_protected:Npn \bool_gset_eq:NN #1
5673 {
5674   \__chk_if_exist_var:N #1
5675   \cs_gset_eq:NN #1
5676 }
5677 \cs_set_protected:Npn \bool_set:Nn #1#2
5678 {
5679   \__chk_if_exist_var:N #1
5680   \tex_chardef:D #1 = \bool_if_p:n {#2}
5681 }
5682 \cs_set_protected:Npn \bool_gset:Nn #1#2
5683 {

```

```

5684     \__chk_if_exist_var:N #1
5685     \tex_global:D \tex_chardef:D #1 = \bool_if_p:n {#2}
5686   }
5687   \fi:
5688 \endpackage

```

\bool_if_p:N Straight forward here. We could optimize here if we wanted to as the boolean can just be input directly.

```

\bool_if_p:c
\bool_if:NTF
\bool_if:cTF
5689 \prg_new_conditional:Npnn \bool_if:N #1 { p , T , F , TF }
5690 {
5691   \if_meaning:w \c_true_bool #1
5692   \prg_return_true:
5693   \else:
5694   \prg_return_false:
5695   \fi:
5696 }
5697 \cs_generate_variant:Nn \bool_if_p:N { c }
5698 \cs_generate_variant:Nn \bool_if:NT { c }
5699 \cs_generate_variant:Nn \bool_if:NF { c }
5700 \cs_generate_variant:Nn \bool_if:NTF { c }

```

(End definition for \bool_if:NTF. This function is documented on page 91.)

\bool_show:N Show the truth value of the boolean, as true or false.

```

\bool_show:c
\bool_show:n
\__bool_to_str:n
5701 \cs_new_protected:Npn \bool_show:N #1
5702 {
5703   \__msg_show_variable:NNNnn #1 \bool_if_exist:NTF ? { }
5704   { > ~ \token_to_str:N #1 = \__bool_to_str:n {#1} }
5705 }
5706 \cs_new_protected:Npn \bool_show:n
5707 { \__msg_show_wrap:Nn \__bool_to_str:n }
5708 \cs_new:Npn \__bool_to_str:n #1
5709 { \bool_if:nTF {#1} { true } { false } }
5710 \cs_generate_variant:Nn \bool_show:N { c }

```

(End definition for \bool_show:N, \bool_show:n, and __bool_to_str:n. These functions are documented on page 91.)

\bool_log:N Redirect output of \bool_show:N to the log.

```

\bool_log:c
\bool_log:n
5711 \cs_new_protected:Npn \bool_log:N
5712 { \__msg_log_next: \bool_show:N }
5713 \cs_new_protected:Npn \bool_log:n
5714 { \__msg_log_next: \bool_show:n }
5715 \cs_generate_variant:Nn \bool_log:N { c }

```

(End definition for \bool_log:N and \bool_log:n. These functions are documented on page 91.)

\l_tmpa_bool A few booleans just if you need them.

```

\l_tmpb_bool
\g_tmpa_bool
\g_tmpb_bool
5716 \bool_new:N \l_tmpa_bool
5717 \bool_new:N \l_tmpb_bool
5718 \bool_new:N \g_tmpa_bool
5719 \bool_new:N \g_tmpb_bool

```

(End definition for \l_tmpa_bool and others. These variables are documented on page 91.)

```

\bool_if_exist_p:N Copies of the cs functions defined in l3basics.
\bool_if_exist_p:c 5720 \prg_new_eq_conditional:NNn \bool_if_exist:N \cs_if_exist:N
\bool_if_exist:NTF 5721 { TF , T , F , p }
\bool_if_exist:cTF 5722 \prg_new_eq_conditional:NNn \bool_if_exist:c \cs_if_exist:c
                    5723 { TF , T , F , p }

```

(End definition for `\bool_if_exist:N`. This function is documented on page 91.)

11.4 Boolean expressions

`\bool_if_p:n` Evaluating the truth value of a list of predicates is done using an input syntax somewhat similar to the one found in other programming languages with (and) for grouping, ! for logical “Not”, && for logical “And” and || for logical “Or”. We shall use the terms Not, And, Or, Open and Close for these operations.

`\bool_if:nTF` Any expression is terminated by a Close operation. Evaluation happens from left to right in the following manner using a `GetNext` function:

- If an Open is seen, start evaluating a new expression using the `Eval` function and call `GetNext` again.
- If a Not is seen, remove the ! and call a `GetNotNext` function, which eventually reverses the logic compared to `GetNext`.
- If none of the above, reinsert the token found (this is supposed to be a predicate function) in front of an `Eval` function, which evaluates it to the boolean value $\langle true \rangle$ or $\langle false \rangle$.

The `Eval` function then contains a post-processing operation which grabs the instruction following the predicate. This is either And, Or or Close. In each case the truth value is used to determine where to go next. The following situations can arise:

$\langle true \rangle$ **And** Current truth value is true, logical And seen, continue with `GetNext` to examine truth value of next boolean (sub-)expression.

$\langle false \rangle$ **And** Current truth value is false, logical And seen, stop evaluating the predicates within this sub-expression and break to the nearest Close. Then return $\langle false \rangle$.

$\langle true \rangle$ **Or** Current truth value is true, logical Or seen, stop evaluating the predicates within this sub-expression and break to the nearest Close. Then return $\langle true \rangle$.

$\langle false \rangle$ **Or** Current truth value is false, logical Or seen, continue with `GetNext` to examine truth value of next boolean (sub-)expression.

$\langle true \rangle$ **Close** Current truth value is true, Close seen, return $\langle true \rangle$.

$\langle false \rangle$ **Close** Current truth value is false, Close seen, return $\langle false \rangle$.

We introduce an additional Stop operation with the same semantics as the Close operation.

$\langle true \rangle$ **Stop** Current truth value is true, return $\langle true \rangle$.

$\langle false \rangle$ **Stop** Current truth value is false, return $\langle false \rangle$.

The reasons for this follow below.

```

5724 \prg_new_conditional:Npnn \bool_if:n #1 { T , F , TF }
5725 {
5726   \if_predicate:w \bool_if_p:n {#1}
5727   \prg_return_true:
5728   \else:
5729     \prg_return_false:
5730   \fi:
5731 }

```

(End definition for `\bool_if:nTF`. This function is documented on page 92.)

`\bool_if_p:n` First issue a `\group_align_safe_begin:` as we are using `&&` as syntax shorthand for the And operation and we need to hide it for \TeX . This will be closed at the end of the expression parsing (see S below).

`_bool_if_left_parentheses:wwwn`
`_bool_if_right_parentheses:wwwn`
`_bool_if_or:wwwn`

Minimal (“short-circuit”) evaluation of boolean expressions requires skipping to the end of the current parenthesized group when `\langle true \rangle ||` is seen, but to the next `||` or closing parenthesis when `\langle false \rangle &&` is seen. To avoid having separate functions for the two cases, we transform the boolean expression by doubling each parenthesis and adding parenthesis around each `||`. This ensures that `&&` will bind tighter than `||`.

The replacement is done in three passes, for left and right parentheses and for `||`. At each pass, the part of the expression that has been transformed is stored before `\q_nil`, the rest lies until the first `\q_mark`, followed by an empty brace group. A trailing marker ensures that the auxiliaries’ delimited arguments will not run-away. As long as the delimiter matches inside the expression, material is moved before `\q_nil` and we continue. Afterwards, the trailing marker is taken as a delimiter, `#4` is the next auxiliary, immediately followed by a new `\q_nil` delimiter, which indicates that nothing has been treated at this pass. The last step calls `_bool_if_parse:NNNww` which cleans up and triggers the evaluation of the expression itself.

```

5732 \cs_new:Npn \bool_if_p:n #1
5733 {
5734   \group_align_safe_begin:
5735   \_bool_if_left_parentheses:wwwn \q_nil
5736   #1 \q_mark { }
5737   ( \q_mark { \_bool_if_right_parentheses:wwwn \q_nil }
5738   ) \q_mark { \_bool_if_or:wwwn \q_nil }
5739   || \q_mark \_bool_if_parse:NNNww
5740   \q_stop
5741 }
5742 \cs_new:Npn \_bool_if_left_parentheses:wwwn #1 \q_nil #2 ( #3 \q_mark #4
5743 { #4 \_bool_if_left_parentheses:wwwn #1 #2 (( \q_nil #3 \q_mark {#4} }
5744 \cs_new:Npn \_bool_if_right_parentheses:wwwn #1 \q_nil #2 ) #3 \q_mark #4
5745 { #4 \_bool_if_right_parentheses:wwwn #1 #2 )) \q_nil #3 \q_mark {#4} }
5746 \cs_new:Npn \_bool_if_or:wwwn #1 \q_nil #2 || #3 \q_mark #4
5747 { #4 \_bool_if_or:wwwn #1 #2 )|( \q_nil #3 \q_mark {#4} }

```

(End definition for `\bool_if_p:n` and others. These functions are documented on page 92.)

`_bool_if_parse:NNNww` After removing extra tokens from the transformation phase, start evaluating. At the end, we will need to finish the special `align_safe` group before finally returning a `\c_true_bool` or `\c_false_bool` as there might otherwise be something left in front in the input stream. For this we call the Stop operation, denoted simply by a S following the last Close operation.

```

5748 \cs_new:Npn \__bool_if_parse:NNNnw #1#2#3#4 \q_mark #5 \q_stop
5749 {
5750   \__bool_get_next:NN \use_i:nn (( #4 )) S
5751 }

```

(End definition for __bool_if_parse:NNNnw.)

`__bool_get_next:NN` The GetNext operation. This is a switch: if what follows is neither ! nor (, we assume it is a predicate. The first argument is `\use_ii:nn` if the logic must eventually be reversed (after a !), otherwise it is `\use_i:nn`. This function eventually expand to the truth value `\c_true_bool` or `\c_false_bool` of the expression which follows until the next unmatched closing parenthesis.

```

5752 \cs_new:Npn \__bool_get_next:NN #1#2
5753 {
5754   \use:c
5755   {
5756     __bool_
5757     \if_meaning:w !#2 ! \else: \if_meaning:w (#2 ( \else: p \fi: \fi:
5758     :Nw
5759   }
5760   #1 #2
5761 }

```

(End definition for __bool_get_next:NN.)

`__bool_!:Nw` The Not operation reverses the logic: discard the ! token and call the GetNext operation with its first argument reversed.

```

5762 \cs_new:cpn { __bool_!:Nw } #1#2
5763 { \exp_after:wN \__bool_get_next:NN #1 \use_ii:nn \use_i:nn }

```

(End definition for __bool_!:Nw.)

`__bool_(:Nw` The Open operation starts a sub-expression after discarding the token. This is done by calling GetNext, with a post-processing step which looks for And, Or or Close afterwards.

```

5764 \cs_new:cpn { __bool_(:Nw } #1#2
5765 {
5766   \exp_after:wN \__bool_choose:NNN \exp_after:wN #1
5767   \__int_value:w \__bool_get_next:NN \use_i:nn
5768 }

```

(End definition for __bool_(:Nw.)

`__bool_p:Nw` If what follows GetNext is neither ! nor (, evaluate the predicate using the primitive `__int_value:w`. The canonical true and false values have numerical values 1 and 0 respectively. Look for And, Or or Close afterwards.

```

5769 \cs_new:cpn { __bool_p:Nw } #1
5770 { \exp_after:wN \__bool_choose:NNN \exp_after:wN #1 \__int_value:w }

```

(End definition for __bool_p:Nw.)

`_bool_choose:NNN` Branching the eight-way switch. The arguments are 1: `\use_i:nn` or `\use_ii:nn`, 2: 0 or 1 encoding the current truth value, 3: the next operation, And, Or, Close or Stop. If #1 is `\use_ii:nn`, the logic of #2 must be reversed.

```

5771 \cs_new:Npn \_bool_choose:NNN #1#2#3
5772 {
5773   \use:c
5774   {
5775     __bool_ #3 _
5776     #1 #2 { \if_meaning:w 0 #2 1 \else: 0 \fi: }
5777     :w
5778   }
5779 }

```

(End definition for `_bool_choose:NNN`.)

`_bool_)_0:w` Closing a group is just about returning the result. The Stop operation is similar except
`_bool_)_1:w` it closes the special alignment group before returning the boolean.

```

5780 \cs_new:cpn { __bool_)_0:w } { \c_false_bool }
5781 \cs_new:cpn { __bool_)_1:w } { \c_true_bool }
5782 \cs_new:cpn { __bool_S_0:w } { \group_align_safe_end: \c_false_bool }
5783 \cs_new:cpn { __bool_S_1:w } { \group_align_safe_end: \c_true_bool }

```

(End definition for `_bool_)_0:w` and others.)

`_bool_&_1:w` Two cases where we simply continue scanning. We must remove the second `&` or `|`.
`_bool_|_0:w`

```

5784 \cs_new:cpn { __bool_&_1:w } & { \_bool_get_next:NN \use_i:nn }
5785 \cs_new:cpn { __bool_|_0:w } | { \_bool_get_next:NN \use_i:nn }

```

(End definition for `_bool_&_1:w` and `_bool_|_0:w`.)

`_bool_&_0:w` When the truth value has already been decided, we have to throw away the remainder
`_bool_|_1:w` of the current group as we are doing minimal evaluation. This is slightly tricky as there
`_bool_eval_skip_to_end_auxi:Nw` are no braces so we have to play match the `()` manually.
`_bool_eval_skip_to_end_auxii:Nw`
`_bool_eval_skip_to_end_auxiii:Nw`

```

5786 \cs_new:cpn { __bool_&_0:w } &
5787 { \_bool_eval_skip_to_end_auxi:Nw \c_false_bool }
5788 \cs_new:cpn { __bool_|_1:w } |
5789 { \_bool_eval_skip_to_end_auxi:Nw \c_true_bool }

```

There is always at least one `)` waiting, namely the outer one. However, we are facing the problem that there may be more than one that need to be finished off and we have to detect the correct number of them. Here is a complicated example showing how this is done. After evaluating the following, we realize we must skip everything after the first And. Note the extra Close at the end.

```
\c_false_bool && ((abc) && xyz) && ((xyz) && (def)))
```

First read up to the first Close. This gives us the list we first read up until the first right parenthesis so we are looking at the token list

```
((abc
```

This contains two Open markers so we must remove two groups. Since no evaluation of the contents is to be carried out, it doesn't matter how we remove the groups as long as we wind up with the correct result. We therefore first remove a `()` pair and what preceded the Open – but leave the contents as it may contain Open tokens itself – leaving

```
(abc && xyz) && ((xyz) && (def)))
```

Another round of this gives us

```
(abc && xyz
```

which still contains an Open so we remove another () pair, giving us

```
abc && xyz && ((xyz) && (def)))
```

Again we read up to a Close and again find Open tokens:

```
abc && xyz && ((xyz
```

Further reduction gives us

```
(xyz && (def)))
```

and then

```
(xyz && (def
```

with reduction to

```
xyz && (def))
```

and ultimately we arrive at no Open tokens being skipped and we can finally close the group nicely.

```
5790 %% (
5791 \cs_new:Npn \__bool_eval_skip_to_end_auxi:Nw #1#2 )
5792 {
5793   \__bool_eval_skip_to_end_auxii:Nw #1#2 ( % )
5794   \q_no_value \q_stop
5795   {#2}
5796 }
```

If no right parenthesis, then #3 is no_value and we are done, return the boolean #1. If there is, we need to grab a () pair and then recurse

```
5797 \cs_new:Npn \__bool_eval_skip_to_end_auxii:Nw #1#2 ( #3#4 \q_stop #5 % )
5798 {
5799   \quark_if_no_value:NTF #3
5800   {#1}
5801   { \__bool_eval_skip_to_end_auxiii:Nw #1 #5 }
5802 }
```

Keep the boolean, throw away anything up to the (as it is irrelevant, remove a () pair but remember to reinsert #3 as it may contain (tokens!

```
5803 \cs_new:Npn \__bool_eval_skip_to_end_auxiii:Nw #1#2 ( #3 )
5804 { % (
5805   \__bool_eval_skip_to_end_auxi:Nw #1#3 )
5806 }
```

(End definition for __bool_&_0:w and others.)

\bool_not_p:n The Not variant just reverses the outcome of \bool_if_p:n. Can be optimized but this is nice and simple and according to the implementation plan. Not even particularly useful to have it when the infix notation is easier to use.

```
5807 \cs_new:Npn \bool_not_p:n #1 { \bool_if_p:n { ! ( #1 ) } }
```


(End definition for `\bool_not_p:n`. This function is documented on page 92.)

`\bool_xor_p:nn` Exclusive or. If the boolean expressions have same truth value, return false, otherwise return true.

```
5808 \cs_new:Npn \bool_xor_p:nn #1#2
5809 {
5810   \int_compare:nNnTF { \bool_if_p:n {#1} } = { \bool_if_p:n {#2} }
5811     \c_false_bool
5812     \c_true_bool
5813 }
```

(End definition for `\bool_xor_p:nn`. This function is documented on page 92.)

11.5 Logical loops

`\bool_while_do:Nn` A while loop where the boolean is tested before executing the statement. The “while” version executes the code as long as the boolean is true; the “until” version executes the code as long as the boolean is false.

```
\bool_while_do:cn
\bool_until_do:cn
5814 \cs_new:Npn \bool_while_do:Nn #1#2
5815 { \bool_if:NT #1 { #2 \bool_while_do:Nn #1 {#2} } }
5816 \cs_new:Npn \bool_until_do:Nn #1#2
5817 { \bool_if:NF #1 { #2 \bool_until_do:Nn #1 {#2} } }
5818 \cs_generate_variant:Nn \bool_while_do:Nn { c }
5819 \cs_generate_variant:Nn \bool_until_do:Nn { c }
```

(End definition for `\bool_while_do:Nn` and `\bool_until_do:Nn`. These functions are documented on page 93.)

`\bool_do_while:Nn` A do-while loop where the body is performed at least once and the boolean is tested after executing the body. Otherwise identical to the above functions.

```
\bool_do_while:cn
\bool_do_until:cn
5820 \cs_new:Npn \bool_do_while:Nn #1#2
5821 { #2 \bool_if:NT #1 { \bool_do_while:Nn #1 {#2} } }
5822 \cs_new:Npn \bool_do_until:Nn #1#2
5823 { #2 \bool_if:NF #1 { \bool_do_until:Nn #1 {#2} } }
5824 \cs_generate_variant:Nn \bool_do_while:Nn { c }
5825 \cs_generate_variant:Nn \bool_do_until:Nn { c }
```

(End definition for `\bool_do_while:Nn` and `\bool_do_until:Nn`. These functions are documented on page 92.)

`\bool_while_do:nn` Loop functions with the test either before or after the first body expansion.

```
\bool_do_while:nn
\bool_until_do:nn
\bool_do_until:nn
5826 \cs_new:Npn \bool_while_do:nn #1#2
5827 {
5828   \bool_if:nT {#1}
5829   {
5830     #2
5831     \bool_while_do:nn {#1} {#2}
5832   }
5833 }
5834 \cs_new:Npn \bool_do_while:nn #1#2
5835 {
5836   #2
5837   \bool_if:nT {#1} { \bool_do_while:nn {#1} {#2} }
5838 }
```

```

5839 \cs_new:Npn \bool_until_do:nn #1#2
5840 {
5841   \bool_if:nF {#1}
5842   {
5843     #2
5844     \bool_until_do:nn {#1} {#2}
5845   }
5846 }
5847 \cs_new:Npn \bool_do_until:nn #1#2
5848 {
5849   #2
5850   \bool_if:nF {#1} { \bool_do_until:nn {#1} {#2} }
5851 }

```

(End definition for `\bool_while_do:nn` and others. These functions are documented on page 93.)

11.6 Producing multiple copies

```

5852 <@@=prg>

```

\prg_replicate:nn This function uses a cascading csname technique by David Kastrup (who else :-)

The idea is to make the input 25 result in first adding five, and then 20 copies of the code to be replicated. The technique uses cascading csnames which means that we start building several csnames so we end up with a list of functions to be called in reverse order. This is important here (and other places) because it means that we can for instance make the function that inserts five copies of something to also hand down ten to the next function in line. This is exactly what happens here: in the example with 25 then the next function is the one that inserts two copies but it sees the ten copies handed down by the previous function. In order to avoid the last function to insert say, 100 copies of the original argument just to gobble them again we define separate functions to be inserted first. These functions also close the expansion of `\exp:w`, which ensures that `\prg_replicate:nn` only requires two steps of expansion.

This function has one flaw though: Since it constantly passes down ten copies of its previous argument it will severely affect the main memory once you start demanding hundreds of thousands of copies. Now I don't think this is a real limitation for any ordinary use, and if necessary, it is possible to write `\prg_replicate:nn {1000} { \prg_replicate:nn {1000} {<code>} }`. An alternative approach is to create a string of m's with `\exp:w` which can be done with just four macros but that method has its own problems since it can exhaust the string pool. Also, it is considerably slower than what we use here so the few extra csnames are well spent I would say.

```

5853 \cs_new:Npn \prg_replicate:nn #1
5854 {
5855   \exp:w
5856   \exp_after:wN \__prg_replicate_first:N
5857   \__int_value:w \__int_eval:w #1 \__int_eval_end:
5858   \cs_end:
5859 }
5860 \cs_new:Npn \__prg_replicate:N #1
5861 { \cs:w \__prg_replicate_#1 :n \__prg_replicate:N }
5862 \cs_new:Npn \__prg_replicate_first:N #1
5863 { \cs:w \__prg_replicate_first_#1 :n \__prg_replicate:N }

```

Then comes all the functions that do the hard work of inserting all the copies. The first function takes `:n` as a parameter.

```

5864 \cs_new:Npn \__prg_replicate_ :n #1 { \cs_end: }
5865 \cs_new:cpn { __prg_replicate_0:n } #1
5866 { \cs_end: {#1#1#1#1#1#1#1#1#1#1} }
5867 \cs_new:cpn { __prg_replicate_1:n } #1
5868 { \cs_end: {#1#1#1#1#1#1#1#1#1#1} #1 }
5869 \cs_new:cpn { __prg_replicate_2:n } #1
5870 { \cs_end: {#1#1#1#1#1#1#1#1#1#1} #1#1 }
5871 \cs_new:cpn { __prg_replicate_3:n } #1
5872 { \cs_end: {#1#1#1#1#1#1#1#1#1#1} #1#1#1 }
5873 \cs_new:cpn { __prg_replicate_4:n } #1
5874 { \cs_end: {#1#1#1#1#1#1#1#1#1#1} #1#1#1#1 }
5875 \cs_new:cpn { __prg_replicate_5:n } #1
5876 { \cs_end: {#1#1#1#1#1#1#1#1#1#1} #1#1#1#1#1 }
5877 \cs_new:cpn { __prg_replicate_6:n } #1
5878 { \cs_end: {#1#1#1#1#1#1#1#1#1#1} #1#1#1#1#1#1 }
5879 \cs_new:cpn { __prg_replicate_7:n } #1
5880 { \cs_end: {#1#1#1#1#1#1#1#1#1#1} #1#1#1#1#1#1#1 }
5881 \cs_new:cpn { __prg_replicate_8:n } #1
5882 { \cs_end: {#1#1#1#1#1#1#1#1#1#1} #1#1#1#1#1#1#1#1 }
5883 \cs_new:cpn { __prg_replicate_9:n } #1
5884 { \cs_end: {#1#1#1#1#1#1#1#1#1#1} #1#1#1#1#1#1#1#1#1 }

```

Users shouldn't ask for something to be replicated once or even not at all but...

```

5885 \cs_new:cpn { __prg_replicate_first_-:n } #1
5886 {
5887   \exp_end:
5888   \__msg_kernel_expandable_error:nn { kernel } { negative-replication }
5889 }
5890 \cs_new:cpn { __prg_replicate_first_0:n } #1 { \exp_end: }
5891 \cs_new:cpn { __prg_replicate_first_1:n } #1 { \exp_end: #1 }
5892 \cs_new:cpn { __prg_replicate_first_2:n } #1 { \exp_end: #1#1 }
5893 \cs_new:cpn { __prg_replicate_first_3:n } #1 { \exp_end: #1#1#1 }
5894 \cs_new:cpn { __prg_replicate_first_4:n } #1 { \exp_end: #1#1#1#1 }
5895 \cs_new:cpn { __prg_replicate_first_5:n } #1 { \exp_end: #1#1#1#1#1 }
5896 \cs_new:cpn { __prg_replicate_first_6:n } #1 { \exp_end: #1#1#1#1#1#1 }
5897 \cs_new:cpn { __prg_replicate_first_7:n } #1 { \exp_end: #1#1#1#1#1#1#1 }
5898 \cs_new:cpn { __prg_replicate_first_8:n } #1 { \exp_end: #1#1#1#1#1#1#1#1 }
5899 \cs_new:cpn { __prg_replicate_first_9:n } #1 { \exp_end: #1#1#1#1#1#1#1#1#1 }

```

(End definition for `\prg_replicate:nn` and others. These functions are documented on page 93.)

11.7 Detecting T_FX's mode

`\mode_if_vertical_p:` For testing vertical mode. Strikes me here on the bus with David, that as long as we are just talking about returning true and false states, we can just use the primitive conditionals for this and gobbling the `\exp_end:` in the input stream. However this requires knowledge of the implementation so we keep things nice and clean and use the return statements.

```
5900 \prg_new_conditional:Npnn \mode_if_vertical: { p , T , F , TF }
5901 { \if mode vertical: \prg return true: \else: \prg return false: \fi: }
```

(End definition for `\mode if vertical:TF`. This function is documented on page 94.)

`\mode_if_horizontal_p:` For testing horizontal mode.

`\mode_if_horizontal:TF`

```

5902 \prg_new_conditional:Npnn \mode_if_horizontal: { p , T , F , TF }
5903   { \if_mode_horizontal: \prg_return_true: \else: \prg_return_false: \fi: }

```

(End definition for `\mode_if_horizontal:TF`. This function is documented on page 94.)

`\mode_if_inner_p:` For testing inner mode.

`\mode_if_inner:TF`

```

5904 \prg_new_conditional:Npnn \mode_if_inner: { p , T , F , TF }
5905   { \if_mode_inner: \prg_return_true: \else: \prg_return_false: \fi: }

```

(End definition for `\mode_if_inner:TF`. This function is documented on page 94.)

`\mode_if_math_p:` For testing math mode. At the beginning of an alignment cell, this should be used only inside a non-expandable function.

`\mode_if_math:TF`

```

5906 \prg_new_conditional:Npnn \mode_if_math: { p , T , F , TF }
5907   { \if_mode_math: \prg_return_true: \else: \prg_return_false: \fi: }

```

(End definition for `\mode_if_math:TF`. This function is documented on page 94.)

11.8 Internal programming functions

`\group_align_safe_begin:` \TeX 's alignment structures present many problems. As Knuth says himself in *TeX: The Program*: “It’s sort of a miracle whenever `\halign` or `\valign` work, [...]” One problem relates to commands that internally issues a `\cr` but also peek ahead for the next character for use in, say, an optional argument. If the next token happens to be a `&` with category code 4 we will get some sort of weird error message because the underlying `\futurelet` will store the token at the end of the alignment template. This could be a `&_4` giving a message like `! Misplaced \cr.` or even worse: it could be the `\endtemplate` token causing even more trouble! To solve this we have to open a special group so that \TeX still thinks it’s on safe ground but at the same time we don’t want to introduce any brace group that may find its way to the output. The following functions help with this by using code documented only in Appendix D of *The TeXbook*... We place the `\if_false: { \fi: }` part at that place so that the successive expansions of `\group_align_safe_begin/end:` are always brace balanced.

```

5908 \cs_new:Npn \group_align_safe_begin:
5909   { \if_int_compare:w \if_false: { \fi: ‘} = \c_zero \fi: }
5910 \cs_new:Npn \group_align_safe_end:
5911   { \if_int_compare:w ‘{ = \c_zero } \fi: }

```

(End definition for `\group_align_safe_begin:` and `\group_align_safe_end:.`)

```

5912 <@@=prg>

```

`\g__prg_map_int` A nesting counter for mapping.

```

5913 \int_new:N \g__prg_map_int

```

(End definition for `\g__prg_map_int.`)

`__prg_break_point:Nn` These are defined in `l3basics`, as they are needed “early”. This is just a reminder that is the case!

`__prg_map_break:Nn`

(End definition for `__prg_break_point:Nn` and `__prg_map_break:Nn.`)

`__prg_break_point:` Also done in `l3basics` as in format mode these are needed within `l3alloc`.

`__prg_break:`

`__prg_break:n`

(End definition for `__prg_break_point:`, `__prg_break:`, and `__prg_break:n.`)

```

5914 </initex | package>

```

12 l3clist implementation

The following test files are used for this code: *m3clist002*.

```
5915 (*initex | package)
```

```
5916 (@@=clist)
```

\c_empty_clist An empty comma list is simply an empty token list.

```
5917 \cs_new_eq:NN \c_empty_clist \c_empty_tl
```

(End definition for `\c_empty_clist`. This variable is documented on page 104.)

\l__clist_internal_clist Scratch space for various internal uses. This comma list variable cannot be declared as such because it comes before `\clist_new:N`

```
5918 \tl_new:N \l__clist_internal_clist
```

(End definition for `\l__clist_internal_clist`.)

__clist_tmp:w A temporary function for various purposes.

```
5919 \cs_new_protected:Npn \__clist_tmp:w { }
```

(End definition for `__clist_tmp:w`.)

12.1 Allocation and initialisation

\clist_new:N Internally, comma lists are just token lists.

```
\clist_new:c      5920 \cs_new_eq:NN \clist_new:N \tl_new:N
                  5921 \cs_new_eq:NN \clist_new:c \tl_new:c
```

(End definition for `\clist_new:N`. This function is documented on page 96.)

\clist_const:Nn Creating and initializing a constant comma list is done in a way similar to `\clist_set:Nn` and `\clist_gset:Nn`, being careful to strip spaces.

```
\clist_const:cn  5922 \cs_new_protected:Npn \clist_const:Nn #1#2
\clist_const:Nx  5923 { \tl_const:Nx #1 { \__clist_trim_spaces:n {#2} } }
\clist_const:cx  5924 \cs_generate_variant:Nn \clist_const:Nn { c , Nx , cx }
```

(End definition for `\clist_const:Nn`. This function is documented on page 96.)

\clist_clear:N Clearing comma lists is just the same as clearing token lists.

```
\clist_clear:c   5925 \cs_new_eq:NN \clist_clear:N \tl_clear:N
\clist_gclear:N  5926 \cs_new_eq:NN \clist_clear:c \tl_clear:c
\clist_gclear:c  5927 \cs_new_eq:NN \clist_gclear:N \tl_gclear:N
                  5928 \cs_new_eq:NN \clist_gclear:c \tl_gclear:c
```

(End definition for `\clist_clear:N` and `\clist_gclear:N`. These functions are documented on page 96.)

\clist_clear_new:N Once again a copy from the token list functions.

```
\clist_clear_new:c 5929 \cs_new_eq:NN \clist_clear_new:N \tl_clear_new:N
\clist_gclear_new:c 5930 \cs_new_eq:NN \clist_clear_new:c \tl_clear_new:c
\clist_gclear_new:N 5931 \cs_new_eq:NN \clist_gclear_new:N \tl_gclear_new:N
\clist_gclear_new:c 5932 \cs_new_eq:NN \clist_gclear_new:c \tl_gclear_new:c
```

(End definition for `\clist_clear_new:N` and `\clist_gclear_new:N`. These functions are documented on page 96.)

`\clist_set_eq:NN` Once again, these are simple copies from the token list functions.

```

\clist_set_eq:cN 5933 \cs_new_eq:NN \clist_set_eq:NN \tl_set_eq:NN
\clist_set_eq:Nc 5934 \cs_new_eq:NN \clist_set_eq:Nc \tl_set_eq:Nc
\clist_set_eq:cc 5935 \cs_new_eq:NN \clist_set_eq:cN \tl_set_eq:cN
\clist_gset_eq:NN 5936 \cs_new_eq:NN \clist_set_eq:cc \tl_set_eq:cc
\clist_gset_eq:cN 5937 \cs_new_eq:NN \clist_gset_eq:NN \tl_gset_eq:NN
\clist_gset_eq:Nc 5938 \cs_new_eq:NN \clist_gset_eq:Nc \tl_gset_eq:Nc
\clist_gset_eq:cN 5939 \cs_new_eq:NN \clist_gset_eq:cN \tl_gset_eq:cN
\clist_gset_eq:cc 5940 \cs_new_eq:NN \clist_gset_eq:cc \tl_gset_eq:cc

```

(End definition for `\clist_set_eq:NN` and `\clist_gset_eq:NN`. These functions are documented on page 97.)

`\clist_set_from_seq:NN` Setting a comma list from a comma-separated list is done using a simple mapping. We wrap most items with `\exp_not:n`, and a comma. Items which contain a comma or a space are surrounded by an extra set of braces. The first comma must be removed, except in the case of an empty comma-list.

```

\clist_set_from_seq:cN 5941 \cs_new_protected:Npn \clist_set_from_seq:NN
\clist_set_from_seq:Nc 5942 { \__clist_set_from_seq:NNNN \clist_clear:N \tl_set:Nx }
\clist_set_from_seq:cc 5943 \cs_new_protected:Npn \clist_gset_from_seq:NN
\clist_gset_from_seq:cN 5944 { \__clist_set_from_seq:NNNN \clist_gclear:N \tl_gset:Nx }
\clist_gset_from_seq:Nc 5945 \cs_new_protected:Npn \__clist_set_from_seq:NNNN #1#2#3#4
\clist_gset_from_seq:cc 5946 {
\__clist_set_from_seq:NNNN 5947 \seq_if_empty:NTF #4
\__clist_wrap_item:n 5948 { #1 #3 }
\__clist_set_from_seq:w 5949 {
5950 #2 #3
5951 {
5952 \exp_last_unbraced:Nf \use_none:n
5953 { \seq_map_function:NN #4 \__clist_wrap_item:n }
5954 }
5955 }
5956 }
5957 \cs_new:Npn \__clist_wrap_item:n #1
5958 {
5959 ,
5960 \tl_if_empty:oTF { \__clist_set_from_seq:w #1 ~ , #1 ~ }
5961 { \exp_not:n {#1} }
5962 { \exp_not:n { {#1} } }
5963 }
5964 \cs_new:Npn \__clist_set_from_seq:w #1 , #2 ~ { }
5965 \cs_generate_variant:Nn \clist_set_from_seq:NN { Nc }
5966 \cs_generate_variant:Nn \clist_set_from_seq:NN { c , cc }
5967 \cs_generate_variant:Nn \clist_gset_from_seq:NN { Nc }
5968 \cs_generate_variant:Nn \clist_gset_from_seq:NN { c , cc }

```

(End definition for `\clist_set_from_seq:NN` and others. These functions are documented on page 97.)

`\clist_concat:NNN` Concatenating comma lists is not quite as easy as it seems, as there needs to be the correct addition of a comma to the output. So a little work to do.

```

\clist_concat:ccc 5969 \cs_new_protected:Npn \clist_concat:NNN
\clist_gconcat:NNN 5970 { \__clist_concat:NNNN \tl_set:Nx }
\clist_gconcat:ccc 5971 \cs_new_protected:Npn \clist_gconcat:NNN
\__clist_concat:NNNN 5972 { \__clist_concat:NNNN \tl_gset:Nx }

```

```

5973 \cs_new_protected:Npn \__clist_concat:NNNN #1#2#3#4
5974 {
5975     #1 #2
5976     {
5977         \exp_not:o #3
5978         \clist_if_empty:NF #3 { \clist_if_empty:NF #4 { , } }
5979         \exp_not:o #4
5980     }
5981 }
5982 \cs_generate_variant:Nn \clist_concat:NNN { ccc }
5983 \cs_generate_variant:Nn \clist_gconcat:NNN { ccc }

```

(End definition for `\clist_concat:NNN`, `\clist_gconcat:NNN`, and `__clist_concat:NNNN`. These functions are documented on page 97.)

```

\clist_if_exist_p:N Copies of the cs functions defined in l3basics.
\clist_if_exist_p:c 5984 \prg_new_eq_conditional:NNn \clist_if_exist:N \cs_if_exist:N
\clist_if_exist:NTF 5985 { TF , T , F , p }
\clist_if_exist:cTF 5986 \prg_new_eq_conditional:NNn \clist_if_exist:c \cs_if_exist:c
                    5987 { TF , T , F , p }

```

(End definition for `\clist_if_exist:NTF`. This function is documented on page 97.)

12.2 Removing spaces around items

`__clist_trim_spaces_generic:nw` This expands to the `<code>`, followed by a brace group containing the `<item>`, with leading and trailing spaces removed. The calling function is responsible for inserting `\q_mark` in front of the `<item>`, as well as testing for the end of the list. We reuse a `l3tl` internal function, whose first argument must start with `\q_mark`. That trims the item #2, then feeds the result (after having to do an o-type expansion) to `__clist_trim_spaces_generic:nn` which places the `<code>` in front of the `<trimmed item>`.

```

5988 \cs_new:Npn \__clist_trim_spaces_generic:nw #1#2 ,
5989 {
5990     \__tl_trim_spaces:nn {#2}
5991     { \exp_args:No \__clist_trim_spaces_generic:nn } {#1}
5992 }
5993 \cs_new:Npn \__clist_trim_spaces_generic:nn #1#2 { #2 {#1} }

```

(End definition for `__clist_trim_spaces_generic:nw` and `__clist_trim_spaces_generic:nn`.)

`__clist_trim_spaces:n` The first argument of `__clist_trim_spaces:nn` is initially empty, and later a comma, namely, as soon as we have added an item to the resulting list. The auxiliary tests for the end of the list, and also prevents empty arguments from finding their way into the output.

```

5994 \cs_new:Npn \__clist_trim_spaces:n #1
5995 {
5996     \__clist_trim_spaces_generic:nw
5997     { \__clist_trim_spaces:nn { } }
5998     \q_mark #1 ,
5999     \q_recursion_tail, \q_recursion_stop
6000 }
6001 \cs_new:Npn \__clist_trim_spaces:nn #1 #2
6002 {
6003     \quark_if_recursion_tail_stop:n {#2}

```

```

6004     \tl_if_empty:nTF {#2}
6005     {
6006         \__clist_trim_spaces_generic:nw
6007         { \__clist_trim_spaces:nn {#1} } \q_mark
6008     }
6009     {
6010         #1 \exp_not:n {#2}
6011         \__clist_trim_spaces_generic:nw
6012         { \__clist_trim_spaces:nn { , } } \q_mark
6013     }
6014 }

```

(End definition for `__clist_trim_spaces:n` and `__clist_trim_spaces:nn`.)

12.3 Adding data to comma lists

```

\clist_set:Nn
\clist_set:NV 6015 \cs_new_protected:Npn \clist_set:Nn #1#2
\clist_set:No 6016 { \tl_set:Nx #1 { \__clist_trim_spaces:n {#2} } }
\clist_set:Nx 6017 \cs_new_protected:Npn \clist_gset:Nn #1#2
\clist_set:cn 6018 { \tl_gset:Nx #1 { \__clist_trim_spaces:n {#2} } }
\clist_set:cV 6019 \cs_generate_variant:Nn \clist_set:Nn { NV , No , Nx , c , cV , co , cx }
\clist_set:co 6020 \cs_generate_variant:Nn \clist_gset:Nn { NV , No , Nx , c , cV , co , cx }
\clist_set:cx
\clist_gset:Nn
\clist_gset:NV
\clist_gset:No
\clist_gset:Nx
\clist_gset:cn
\clist_gset:cV
\clist_gset:co
\clist_gset:cx
\clist_gput_left:Nn
\clist_gput_left:NV
\clist_gput_left:No
\clist_gput_left:Nx
\clist_gput_left:cn
\clist_gput_left:cV
\clist_gput_left:co
\clist_gput_left:cx
\__clist_put_left:NNNn
\clist_put_right:Nn
\clist_put_right:NV
\clist_put_right:No
\clist_put_right:Nx
\clist_put_right:cn
\clist_put_right:cV
\clist_put_right:co
\clist_put_right:cx
\clist_gput_right:Nn
\clist_gput_right:NV
\clist_gput_right:No
\clist_gput_right:Nx
\clist_gput_right:cn
\clist_gput_right:cV
\clist_gput_right:co
\clist_gput_right:cx
\__clist_put_right:NNNn

```

(End definition for `\clist_set:Nn` and `\clist_gset:Nn`. These functions are documented on page 97.)

Comma lists cannot hold empty values: there are therefore a couple of sanity checks to avoid accumulating commas.

```

6021 \cs_new_protected:Npn \clist_put_left:Nn
6022 { \__clist_put_left:NNNn \clist_concat:NNN \clist_set:Nn }
6023 \cs_new_protected:Npn \clist_gput_left:Nn
6024 { \__clist_put_left:NNNn \clist_gconcat:NNN \clist_set:Nn }
6025 \cs_new_protected:Npn \__clist_put_left:NNNn #1#2#3#4
6026 {
6027     #2 \l__clist_internal_clist {#4}
6028     #1 #3 \l__clist_internal_clist #3
6029 }
6030 \cs_generate_variant:Nn \clist_put_left:Nn { NV , No , Nx }
6031 \cs_generate_variant:Nn \clist_put_left:Nn { c , cV , co , cx }
6032 \cs_generate_variant:Nn \clist_gput_left:Nn { NV , No , Nx }
6033 \cs_generate_variant:Nn \clist_gput_left:Nn { c , cV , co , cx }

```

(End definition for `\clist_put_left:Nn`, `\clist_gput_left:Nn`, and `__clist_put_left:NNNn`. These functions are documented on page 97.)


```

6042 }
6043 \cs_generate_variant:Nn \clist_put_right:Nn { NV , No , Nx }
6044 \cs_generate_variant:Nn \clist_put_right:Nn { c , cV , co , cx }
6045 \cs_generate_variant:Nn \clist_gput_right:Nn { NV , No , Nx }
6046 \cs_generate_variant:Nn \clist_gput_right:Nn { c , cV , co , cx }

```

(End definition for `\clist_put_right:Nn`, `\clist_gput_right:Nn`, and `__clist_put_right:NNNn`. These functions are documented on page 98.)

12.4 Comma lists as stacks

`\clist_get:NN` Getting an item from the left of a comma list is pretty easy: just trim off the first item
`\clist_get:cN` using the comma.
`__clist_get:wN`

```

6047 \cs_new_protected:Npn \clist_get:NN #1#2
6048 {
6049   \if_meaning:w #1 \c_empty_clist
6050     \tl_set:Nn #2 { \q_no_value }
6051   \else:
6052     \exp_after:wN \__clist_get:wN #1 , \q_stop #2
6053   \fi:
6054 }
6055 \cs_new_protected:Npn \__clist_get:wN #1 , #2 \q_stop #3
6056 { \tl_set:Nn #3 {#1} }
6057 \cs_generate_variant:Nn \clist_get:NN { c }

```

(End definition for `\clist_get:NN` and `__clist_get:wN`. These functions are documented on page 102.)

`\clist_pop:NN` An empty clist leads to `\q_no_value`, otherwise grab until the first comma and assign
`\clist_pop:cN` to the variable. The second argument of `__clist_pop:wwNNN` is a comma list ending
`\clist_gpop:NN` in a comma and `\q_mark`, unless the original clist contained exactly one item: then the
`\clist_gpop:cN` argument is just `\q_mark`. The next auxiliary picks either `\exp_not:n` or `\use_none:n`
`__clist_pop:NNN` as #2, ensuring that the result can safely be an empty comma list.
`__clist_pop:wwNNN`
`__clist_pop:wN`

```

6058 \cs_new_protected:Npn \clist_pop:NN
6059 { \__clist_pop:NNN \tl_set:Nx }
6060 \cs_new_protected:Npn \clist_gpop:NN
6061 { \__clist_pop:NNN \tl_gset:Nx }
6062 \cs_new_protected:Npn \__clist_pop:NNN #1#2#3
6063 {
6064   \if_meaning:w #2 \c_empty_clist
6065     \tl_set:Nn #3 { \q_no_value }
6066   \else:
6067     \exp_after:wN \__clist_pop:wwNNN #2 , \q_mark \q_stop #1#2#3
6068   \fi:
6069 }
6070 \cs_new_protected:Npn \__clist_pop:wwNNN #1 , #2 \q_stop #3#4#5
6071 {
6072   \tl_set:Nn #5 {#1}
6073   #3 #4
6074   {
6075     \__clist_pop:wN \prg_do_nothing:
6076     #2 \exp_not:o
6077     , \q_mark \use_none:n
6078     \q_stop
6079   }

```

```

6080 }
6081 \cs_new:Npn \__clist_pop:wN #1 , \q_mark #2 #3 \q_stop { #2 {#1} }
6082 \cs_generate_variant:Nn \clist_pop:NN { c }
6083 \cs_generate_variant:Nn \clist_gpop:NN { c }

```

(End definition for \clist_pop:NN and others. These functions are documented on page 102.)

```

\clist_get:NNTF The same, as branching code: very similar to the above.
\clist_get:cNTF 6084 \prg_new_protected_conditional:Npnn \clist_get:NN #1#2 { T , F , TF }
\clist_pop:NNTF 6085 {
\clist_pop:cNTF 6086   \if_meaning:w #1 \c_empty_clist
\clist_gpop:NNTF 6087   \prg_return_false:
\clist_gpop:cNTF 6088   \else:
\__clist_pop_TF:NNN 6089   \exp_after:wN \__clist_get:wN #1 , \q_stop #2
6090   \prg_return_true:
6091   \fi:
6092 }
6093 \cs_generate_variant:Nn \clist_get:NNT { c }
6094 \cs_generate_variant:Nn \clist_get:NNF { c }
6095 \cs_generate_variant:Nn \clist_get:NNTF { c }
6096 \prg_new_protected_conditional:Npnn \clist_pop:NN #1#2 { T , F , TF }
6097 { \__clist_pop_TF:NNN \tl_set:Nx #1 #2 }
6098 \prg_new_protected_conditional:Npnn \clist_gpop:NN #1#2 { T , F , TF }
6099 { \__clist_pop_TF:NNN \tl_gset:Nx #1 #2 }
6100 \cs_new_protected:Npn \__clist_pop_TF:NNN #1#2#3
6101 {
6102   \if_meaning:w #2 \c_empty_clist
6103   \prg_return_false:
6104   \else:
6105     \exp_after:wN \__clist_pop:wwNNN #2 , \q_mark \q_stop #1#2#3
6106     \prg_return_true:
6107   \fi:
6108 }
6109 \cs_generate_variant:Nn \clist_pop:NNT { c }
6110 \cs_generate_variant:Nn \clist_pop:NNF { c }
6111 \cs_generate_variant:Nn \clist_pop:NNTF { c }
6112 \cs_generate_variant:Nn \clist_gpop:NNT { c }
6113 \cs_generate_variant:Nn \clist_gpop:NNF { c }
6114 \cs_generate_variant:Nn \clist_gpop:NNTF { c }

```

(End definition for \clist_get:NNTF and others. These functions are documented on page 102.)

```

\clist_push:Nn Pushing to a comma list is the same as adding on the left.
\clist_push:NV 6115 \cs_new_eq:NN \clist_push:Nn \clist_put_left:Nn
\clist_push:No 6116 \cs_new_eq:NN \clist_push:NV \clist_put_left:NV
\clist_push:Nx 6117 \cs_new_eq:NN \clist_push:No \clist_put_left:No
\clist_push:cn 6118 \cs_new_eq:NN \clist_push:Nx \clist_put_left:Nx
\clist_push:cV 6119 \cs_new_eq:NN \clist_push:cn \clist_put_left:cn
\clist_push:co 6120 \cs_new_eq:NN \clist_push:cV \clist_put_left:cV
\clist_push:cx 6121 \cs_new_eq:NN \clist_push:co \clist_put_left:co
\clist_gpush:Nn 6122 \cs_new_eq:NN \clist_push:cx \clist_put_left:cx
\clist_gpush:NV 6123 \cs_new_eq:NN \clist_gpush:Nn \clist_gput_left:Nn
\clist_gpush:No 6124 \cs_new_eq:NN \clist_gpush:NV \clist_gput_left:NV
\clist_gpush:Nx 6125 \cs_new_eq:NN \clist_gpush:No \clist_gput_left:No
\clist_gpush:cn 6126 \cs_new_eq:NN \clist_gpush:Nx \clist_gput_left:Nx
\clist_gpush:cV
\clist_gpush:co
\clist_gpush:cx

```

```

6127 \cs_new_eq:NN \clist_gpush:cn \clist_gput_left:cn
6128 \cs_new_eq:NN \clist_gpush:cV \clist_gput_left:cV
6129 \cs_new_eq:NN \clist_gpush:co \clist_gput_left:co
6130 \cs_new_eq:NN \clist_gpush:cx \clist_gput_left:cx

```

(End definition for `\clist_push:Nn` and `\clist_gpush:Nn`. These functions are documented on page 103.)

12.5 Modifying comma lists

`\l__clist_internal_remove_clist` An internal comma list for the removal routines.

```

6131 \clist_new:N \l__clist_internal_remove_clist

```

(End definition for `\l__clist_internal_remove_clist`.)

`\clist_remove_duplicates:N` Removing duplicates means making a new list then copying it.

```

\clist_remove_duplicates:c
\clist_gremove_duplicates:N
\clist_gremove_duplicates:c
  \__clist_remove_duplicates:NN
6132 \cs_new_protected:Npn \clist_remove_duplicates:N
6133 { \__clist_remove_duplicates:NN \clist_set_eq:NN }
6134 \cs_new_protected:Npn \clist_gremove_duplicates:N
6135 { \__clist_remove_duplicates:NN \clist_gset_eq:NN }
6136 \cs_new_protected:Npn \__clist_remove_duplicates:NN #1#2
6137 {
6138   \clist_clear:N \l__clist_internal_remove_clist
6139   \clist_map_inline:Nn #2
6140   {
6141     \clist_if_in:NnF \l__clist_internal_remove_clist {##1}
6142     { \clist_put_right:Nn \l__clist_internal_remove_clist {##1} }
6143   }
6144   #1 #2 \l__clist_internal_remove_clist
6145 }
6146 \cs_generate_variant:Nn \clist_remove_duplicates:N { c }
6147 \cs_generate_variant:Nn \clist_gremove_duplicates:N { c }

```

(End definition for `\clist_remove_duplicates:N`, `\clist_gremove_duplicates:N`, and `__clist_remove_duplicates:NN`. These functions are documented on page 98.)

`\clist_remove_all:Nn` The method used here is very similar to `\tl_replace_all:Nnn`. Build a function delimited by the `<item>` that should be removed, surrounded with commas, and call that function followed by the expanded comma list, and another copy of the `<item>`. The loop is controlled by the argument grabbed by `__clist_remove_all:w`: when the item was found, the `\q_mark` delimiter used is the one inserted by `__clist_tmp:w`, and `\use_none_delimit_by_q_stop:w` is deleted. At the end, the final `<item>` is grabbed, and the argument of `__clist_tmp:w` contains `\q_mark`: in that case, `__clist_remove_all:w` removes the second `\q_mark` (inserted by `__clist_tmp:w`), and lets `\use_none_delimit_by_q_stop:w` act.

No brace is lost because items are always grabbed with a leading comma. The result of the first assignment has an extra leading comma, which we remove in a second assignment. Two exceptions: if the clist lost all of its elements, the result is empty, and we shouldn't remove anything; if the clist started up empty, the first step happens to turn it into a single comma, and the second step removes it.

```

6148 \cs_new_protected:Npn \clist_remove_all:Nn
6149 { \__clist_remove_all:NNn \tl_set:Nx }
6150 \cs_new_protected:Npn \clist_gremove_all:Nn

```

```

6151 { \_clist_remove_all:Nn \tl_gset:Nx }
6152 \cs_new_protected:Npn \_clist_remove_all:Nn #1#2#3
6153 {
6154   \cs_set:Npn \_clist_tmp:w ##1 , #3 ,
6155   {
6156     ##1
6157     , \q_mark , \use_none_delimit_by_q_stop:w ,
6158     \_clist_remove_all:
6159   }
6160   #1 #2
6161   {
6162     \exp_after:wN \_clist_remove_all:
6163     #2 , \q_mark , #3 , \q_stop
6164   }
6165   \clist_if_empty:NF #2
6166   {
6167     #1 #2
6168     {
6169       \exp_args:No \exp_not:o
6170       { \exp_after:wN \use_none:n #2 }
6171     }
6172   }
6173 }
6174 \cs_new:Npn \_clist_remove_all:
6175 { \exp_after:wN \_clist_remove_all:w \_clist_tmp:w , }
6176 \cs_new:Npn \_clist_remove_all:w #1 , \q_mark , #2 , { \exp_not:n {#1} }
6177 \cs_generate_variant:Nn \clist_remove_all:Nn { c }
6178 \cs_generate_variant:Nn \clist_gremove_all:Nn { c }

```

(End definition for `\clist_remove_all:Nn` and others. These functions are documented on page 98.)

`\clist_reverse:N` Use `\clist_reverse:n` in an x-expanding assignment. The extra work that `\clist_reverse:n` does to preserve braces and spaces would not be needed for the well-controlled case of N-type comma lists, but the slow-down is not too bad.

`\clist_reverse:c`

`\clist_greverse:N`

`\clist_greverse:c`

```

6179 \cs_new_protected:Npn \clist_reverse:N #1
6180 { \tl_set:Nx #1 { \exp_args:No \clist_reverse:n {#1} } }
6181 \cs_new_protected:Npn \clist_greverse:N #1
6182 { \tl_gset:Nx #1 { \exp_args:No \clist_reverse:n {#1} } }
6183 \cs_generate_variant:Nn \clist_reverse:N { c }
6184 \cs_generate_variant:Nn \clist_greverse:N { c }

```

(End definition for `\clist_reverse:N` and `\clist_greverse:N`. These functions are documented on page 98.)

`\clist_reverse:n` The reversed token list is built one item at a time, and stored between `\q_stop` and `\q_mark`, in the form of ? followed by zero or more instances of “`<item>`,”. We start from a comma list “`<item1>, ..., <itemn>`”. During the loop, the auxiliary `_clist_reverse:wwNww` receives “`?<itemi>`” as #1, “`<itemi+1>, ..., <itemn>`” as #2, `_clist_reverse:wwNww` as #3, what remains until `\q_stop` as #4, and “`<itemi-1>, ..., <item1>`,” as #5. The auxiliary moves #1 just before #5, with a comma, and calls itself (#3). After the last item is moved, `_clist_reverse:wwNww` receives “`\q_mark _clist_reverse:wwNww !`” as its argument #1, thus `_clist_reverse_end:ww` as its argument #3. This second auxiliary cleans up until the marker !, removes the trailing comma (introduced when the first item was moved after `\q_stop`), and leaves its argument #1

within `\exp_not:n`. There is also a need to remove a leading comma, hence `\exp_not:o` and `\use_none:n`.

```

6185 \cs_new:Npn \clist_reverse:n #1
6186 {
6187   \__clist_reverse:wwNww ? #1 ,
6188   \q_mark \__clist_reverse:wwNww ! ,
6189   \q_mark \__clist_reverse_end:ww
6190   \q_stop ? \q_mark
6191 }
6192 \cs_new:Npn \__clist_reverse:wwNww
6193   #1 , #2 \q_mark #3 #4 \q_stop ? #5 \q_mark
6194   { #3 ? #2 \q_mark #3 #4 \q_stop #1 , #5 \q_mark }
6195 \cs_new:Npn \__clist_reverse_end:ww #1 ! #2 , \q_mark
6196   { \exp_not:o { \use_none:n #2 } }

```

(End definition for `\clist_reverse:n`, `__clist_reverse:wwNww`, and `__clist_reverse_end:ww`. These functions are documented on page 98.)

`\clist_sort:Nn` Implemented in `l3sort`.

`\clist_sort:cn`

`\clist_gsort:Nn` (End definition for `\clist_sort:Nn` and `\clist_gsort:Nn`. These functions are documented on page 99.)

`\clist_gsort:cn`

12.6 Comma list conditionals

`\clist_if_empty_p:N` Simple copies from the token list variable material.

`\clist_if_empty_p:c`

`\clist_if_empty:NTF`

`\clist_if_empty:cTF`

```

6197 \prg_new_eq_conditional:Nnn \clist_if_empty:N \tl_if_empty:N
6198   { p , T , F , TF }
6199 \prg_new_eq_conditional:Nnn \clist_if_empty:c \tl_if_empty:c
6200   { p , T , F , TF }

```

(End definition for `\clist_if_empty:NTF`. This function is documented on page 99.)

`\clist_if_empty_p:n`

`\clist_if_empty:nTF`

`__clist_if_empty_n:w`

`__clist_if_empty_n:wNw`

As usual, we insert a token (here ?) before grabbing any argument: this avoids losing braces. The argument of `\tl_if_empty:oTF` is empty if #1 is ? followed by blank spaces (besides, this particular variant of the emptiness test is optimized). If the item of the comma list is blank, grab the next one. As soon as one item is non-blank, exit: the second auxiliary will grab `\prg_return_false:` as #2, unless every item in the comma list was blank and the loop actually got broken by the trailing `\q_mark \prg_return_false:` item.

```

6201 \prg_new_conditional:Npnn \clist_if_empty:n #1 { p , T , F , TF }
6202 {
6203   \__clist_if_empty_n:w ? #1
6204   , \q_mark \prg_return_false:
6205   , \q_mark \prg_return_true:
6206   \q_stop
6207 }
6208 \cs_new:Npn \__clist_if_empty_n:w #1 ,
6209 {
6210   \tl_if_empty:oTF { \use_none:nn #1 ? }
6211   { \__clist_if_empty_n:w ? }
6212   { \__clist_if_empty_n:wNw }
6213 }
6214 \cs_new:Npn \__clist_if_empty_n:wNw #1 \q_mark #2#3 \q_stop {#2}

```

(End definition for `\clist_if_empty:nTF`, `_clist_if_empty_n:w`, and `_clist_if_empty_n:wNw`. These functions are documented on page 99.)

```

\clist_if_in:NnTF See description of the \tl_if_in:Nn function for details. We simply surround the comma
\clist_if_in:NVTF list, and the item, with commas.
\clist_if_in:NoTF
\clist_if_in:cnTF 6215 \prg_new_protected_conditional:Npnn \clist_if_in:Nn #1#2 { T , F , TF }
\clist_if_in:cVTF 6216 {
\clist_if_in:coTF 6217 \exp_args:No \_clist_if_in_return:nn #1 {#2}
\clist_if_in:nnTF 6218 }
\clist_if_in:nVTF 6219 \prg_new_protected_conditional:Npnn \clist_if_in:nn #1#2 { T , F , TF }
\clist_if_in:noTF 6220 {
6221 \clist_set:Nn \l__clist_internal_clist {#1}
6222 \exp_args:No \_clist_if_in_return:nn \l__clist_internal_clist {#2}
6223 }
6224 \cs_new_protected:Npn \_clist_if_in_return:nn #1#2
6225 {
6226 \cs_set:Npn \_clist_tmp:w ##1 ,#2, { }
6227 \tl_if_empty:oTF
6228 { \_clist_tmp:w ,#1, {} {} ,#2, }
6229 { \prg_return_false: } { \prg_return_true: }
6230 }
6231 \cs_generate_variant:Nn \clist_if_in:NnT { NV , No }
6232 \cs_generate_variant:Nn \clist_if_in:NnT { c , cV , co }
6233 \cs_generate_variant:Nn \clist_if_in:NnF { NV , No }
6234 \cs_generate_variant:Nn \clist_if_in:NnF { c , cV , co }
6235 \cs_generate_variant:Nn \clist_if_in:NnTF { NV , No }
6236 \cs_generate_variant:Nn \clist_if_in:NnTF { c , cV , co }
6237 \cs_generate_variant:Nn \clist_if_in:nnT { nV , no }
6238 \cs_generate_variant:Nn \clist_if_in:nnF { nV , no }
6239 \cs_generate_variant:Nn \clist_if_in:nnTF { nV , no }

```

(End definition for `\clist_if_in:NnTF`, `\clist_if_in:nnTF`, and `_clist_if_in_return:nn`. These functions are documented on page 99.)

12.7 Mapping to comma lists

```

\clist_map_function:NN If the variable is empty, the mapping is skipped (otherwise, that comma-list would be
\clist_map_function:cN seen as consisting of one empty item). Then loop over the comma-list, grabbing one
\_clist_map_function:Nw comma-delimited item at a time. The end is marked by \q_recursion_tail. The aux-
iliary function \_clist_map_function:Nw is used directly in \clist_map_inline:Nn.
Change with care.

```

```

6240 \cs_new:Npn \clist_map_function:NN #1#2
6241 {
6242 \clist_if_empty:NF #1
6243 {
6244 \exp_last_unbraced:NNo \_clist_map_function:Nw #2 #1
6245 , \q_recursion_tail ,
6246 \_prg_break_point:Nn \clist_map_break: { }
6247 }
6248 }
6249 \cs_new:Npn \_clist_map_function:Nw #1#2 ,
6250 {
6251 \_quark_if_recursion_tail_break:nN {#2} \clist_map_break:
6252 #1 {#2}

```

```

6253     \__clist_map_function:Nw #1
6254   }
6255   \cs_generate_variant:Nn \clist_map_function:NN { c }

```

(End definition for `\clist_map_function:NN` and `__clist_map_function:Nw`. These functions are documented on page 100.)

`\clist_map_function:nN` The `n`-type mapping function is a bit more awkward, since spaces must be trimmed from each item. Space trimming is again based on `__clist_trim_spaces_generic:nw`. The auxiliary `__clist_map_function_n:Nn` receives as arguments the function, and the result of removing leading and trailing spaces from the item which lies until the next comma. Empty items are ignored, then one level of braces is removed by `__clist_map_unbrace:Nw`.

```

6256 \cs_new:Npn \clist_map_function:nN #1#2
6257 {
6258   \__clist_trim_spaces_generic:nw { \__clist_map_function_n:Nn #2 }
6259   \q_mark #1, \q_recursion_tail,
6260   \__prg_break_point:Nn \clist_map_break: { }
6261 }
6262 \cs_new:Npn \__clist_map_function_n:Nn #1 #2
6263 {
6264   \__quark_if_recursion_tail_break:nN {#2} \clist_map_break:
6265   \tl_if_empty:nF {#2} { \__clist_map_unbrace:Nw #1 #2, }
6266   \__clist_trim_spaces_generic:nw { \__clist_map_function_n:Nn #1 }
6267   \q_mark
6268 }
6269 \cs_new:Npn \__clist_map_unbrace:Nw #1 #2, { #1 {#2} }

```

(End definition for `\clist_map_function:nN`, `__clist_map_function_n:Nn`, and `__clist_map_unbrace:Nw`. These functions are documented on page 100.)

`\clist_map_inline:Nn` `\clist_map_inline:cn` `\clist_map_inline:nn` Inline mapping is done by creating a suitable function “on the fly”: this is done globally to avoid any issues with TeX’s groups. We use a different function for each level of nesting.

Since the mapping is non-expandable, we can perform the space-trimming needed by the `n` version simply by storing the comma-list in a variable. We don’t need a different comma-list for each nesting level: the comma-list is expanded before the mapping starts.

```

6270 \cs_new_protected:Npn \clist_map_inline:Nn #1#2
6271 {
6272   \clist_if_empty:NF #1
6273   {
6274     \int_gincr:N \g__prg_map_int
6275     \cs_gset:cpn { __prg_map_ \int_use:N \g__prg_map_int :w } ##1 {#2}
6276     \exp_last_unbraced:Nco \__clist_map_function:Nw
6277     { __prg_map_ \int_use:N \g__prg_map_int :w }
6278     #1 , \q_recursion_tail ,
6279     \__prg_break_point:Nn \clist_map_break:
6280     { \int_gdecr:N \g__prg_map_int }
6281   }
6282 }
6283 \cs_new_protected:Npn \clist_map_inline:nn #1
6284 {
6285   \clist_set:Nn \l__clist_internal_clist {#1}
6286   \clist_map_inline:Nn \l__clist_internal_clist

```

```

6287 }
6288 \cs_generate_variant:Nn \clist_map_inline:Nn { c }

```

(End definition for `\clist_map_inline:Nn` and `\clist_map_inline:nn`. These functions are documented on page 100.)

`\clist_map_variable:NNn` As for other comma-list mappings, filter out the case of an empty list. Same approach
`\clist_map_variable:cNn` as `\clist_map_function:Nn`, additionally we store each item in the given variable. As
`\clist_map_variable:nNn` for inline mappings, space trimming for the `n` variant is done by storing the comma list
`__clist_map_variable:Nnw` in a variable.

```

6289 \cs_new_protected:Npn \clist_map_variable:NNn #1#2#3
6290 {
6291   \clist_if_empty:NF #1
6292   {
6293     \exp_args:Nno \use:nn
6294     { \__clist_map_variable:Nnw #2 {#3} }
6295     #1
6296     , \q_recursion_tail , \q_recursion_stop
6297     \__prg_break_point:Nn \clist_map_break: { }
6298   }
6299 }
6300 \cs_new_protected:Npn \clist_map_variable:nNn #1
6301 {
6302   \clist_set:Nn \l__clist_internal_clist {#1}
6303   \clist_map_variable:NNn \l__clist_internal_clist
6304 }
6305 \cs_new_protected:Npn \__clist_map_variable:Nnw #1#2#3,
6306 {
6307   \tl_set:Nn #1 {#3}
6308   \quark_if_recursion_tail_stop:N #1
6309   \use:n {#2}
6310   \__clist_map_variable:Nnw #1 {#2}
6311 }
6312 \cs_generate_variant:Nn \clist_map_variable:NNn { c }

```

(End definition for `\clist_map_variable:NNn`, `\clist_map_variable:nNn`, and `__clist_map_variable:Nnw`. These functions are documented on page 100.)

`\clist_map_break:` The break statements use the general `__prg_map_break:Nn` mechanism.
`\clist_map_break:n`

```

6313 \cs_new:Npn \clist_map_break:
6314 { \__prg_map_break:Nn \clist_map_break: { } }
6315 \cs_new:Npn \clist_map_break:n
6316 { \__prg_map_break:Nn \clist_map_break: }

```

(End definition for `\clist_map_break:` and `\clist_map_break:n`. These functions are documented on page 100.)

`\clist_count:N` Counting the items in a comma list is done using the same approach as for other token
`\clist_count:c` count functions: turn each entry into a +1 then use integer evaluation to actually do the
`\clist_count:n` mathematics. In the case of an `n`-type comma-list, we could of course use `\clist_map_-`
`__clist_count:n` `function:nNn`, but that is very slow, because it carefully removes spaces. Instead, we loop
`__clist_count:w` manually, and skip blank items (but not `{}`, hence the extra spaces).

```

6317 \cs_new:Npn \clist_count:N #1
6318 {

```



```

6319     \int_eval:n
6320     {
6321         0
6322         \clist_map_function:NN #1 \__clist_count:n
6323     }
6324 }
6325 \cs_generate_variant:Nn \clist_count:N { c }
6326 \cs_new:Npx \clist_count:n #1
6327 {
6328     \exp_not:N \int_eval:n
6329     {
6330         0
6331         \exp_not:N \__clist_count:w \c_space_tl
6332         #1 \exp_not:n { , \q_recursion_tail , \q_recursion_stop }
6333     }
6334 }
6335 \cs_new:Npn \__clist_count:n #1 { + 1 }
6336 \cs_new:Npx \__clist_count:w #1 ,
6337 {
6338     \exp_not:n { \exp_args:Nf \quark_if_recursion_tail_stop:n } {#1}
6339     \exp_not:N \tl_if_blank:nF {#1} { + 1 }
6340     \exp_not:N \__clist_count:w \c_space_tl
6341 }

```

(End definition for `\clist_count:N` and others. These functions are documented on page 101.)

12.8 Using comma lists

`\clist_use:Nnnn` First check that the variable exists. Then count the items in the comma list. If it has none, output nothing. If it has one item, output that item, brace stripped (note that space-trimming has already been done when the comma list was assigned). If it has two, place the *<separator between two>* in the middle.

Otherwise, `__clist_use:nwwwnwn` takes the following arguments; 1: a *<separator>*, 2, 3, 4: three items from the comma list (or quarks), 5: the rest of the comma list, 6: a *<continuation>* function (`use_ii` or `use_iii` with its *<separator>* argument), 7: junk, and 8: the temporary result, which is built in a brace group following `\q_stop`. The *<separator>* and the first of the three items are placed in the result, then we use the *<continuation>*, placing the remaining two items after it. When we begin this loop, the three items really belong to the comma list, the first `\q_mark` is taken as a delimiter to the `use_ii` function, and the continuation is `use_ii` itself. When we reach the last two items of the original token list, `\q_mark` is taken as a third item, and now the second `\q_mark` serves as a delimiter to `use_ii`, switching to the other *<continuation>*, `use_iii`, which uses the *<separator between final two>*.

```

6342 \cs_new:Npn \clist_use:Nnnn #1#2#3#4
6343 {
6344     \clist_if_exist:NTF #1
6345     {
6346         \int_case:nnF { \clist_count:N #1 }
6347         {
6348             { 0 } { }
6349             { 1 } { \exp_after:wN \__clist_use:wnn #1 , , { } }
6350             { 2 } { \exp_after:wN \__clist_use:wnn #1 , {#2} }
6351         }

```

```

6352         {
6353             \exp_after:wN \__clist_use:nwwwnwn
6354             \exp_after:wN { \exp_after:wN } #1 ,
6355             \q_mark , { \__clist_use:nwwwnwn {#3} }
6356             \q_mark , { \__clist_use:nwn {#4} }
6357             \q_stop { }
6358         }
6359     }
6360     {
6361         \_msg_kernel_expandable_error:nnn
6362         { kernel } { bad-variable } {#1}
6363     }
6364 }
6365 \cs_generate_variant:Nn \clist_use:Nnnn { c }
6366 \cs_new:Npn \__clist_use:wn #1 , #2 , #3 { \exp_not:n { #1 #3 #2 } }
6367 \cs_new:Npn \__clist_use:nwwwnwn
6368     #1#2 , #3 , #4 , #5 \q_mark , #6#7 \q_stop #8
6369     { #6 {#3} , {#4} , #5 \q_mark , {#6} #7 \q_stop { #8 #1 #2 } }
6370 \cs_new:Npn \__clist_use:nwn #1#2 , #3 \q_stop #4
6371     { \exp_not:n { #4 #1 #2 } }
6372 \cs_new:Npn \clist_use:Nn #1#2
6373     { \clist_use:Nnnn #1 {#2} {#2} {#2} }
6374 \cs_generate_variant:Nn \clist_use:Nn { c }

```

(End definition for `\clist_use:Nnnn` and others. These functions are documented on page [101](#).)

12.9 Using a single item

```

\clist_item:Nn
\clist_item:cn
\__clist_item:nnnN
\__clist_item:ffoN
\__clist_item:ffnN
\__clist_item_N_loop:nw

```

To avoid needing to test the end of the list at each step, we first compute the $\langle length \rangle$ of the list. If the item number is 0, less than $-\langle length \rangle$, or more than $\langle length \rangle$, the result is empty. If it is negative, but not less than $-\langle length \rangle$, add $\langle length \rangle + 1$ to the item number before performing the loop. The loop itself is very simple, return the item if the counter reached 1, otherwise, decrease the counter and repeat.

```

6375 \cs_new:Npn \clist_item:Nn #1#2
6376 {
6377     \__clist_item:ffoN
6378     { \clist_count:N #1 }
6379     { \int_eval:n {#2} }
6380     #1
6381     \__clist_item_N_loop:nw
6382 }
6383 \cs_new:Npn \__clist_item:nnnN #1#2#3#4
6384 {
6385     \int_compare:nNnTF {#2} < 0
6386     {
6387         \int_compare:nNnTF {#2} < { - #1 }
6388         { \use_none_delimit_by_q_stop:w }
6389         { \exp_args:Nf #4 { \int_eval:n { #2 + 1 + #1 } } }
6390     }
6391     {
6392         \int_compare:nNnTF {#2} > {#1}
6393         { \use_none_delimit_by_q_stop:w }
6394         { #4 {#2} }
6395     }

```

```

6396     { } , #3 , \q_stop
6397   }
6398   \cs_generate_variant:Nn \__clist_item:nnnN { ffo, ff }
6399   \cs_new:Npn \__clist_item_N_loop:nw #1 #2,
6400   {
6401     \int_compare:nNnTF {#1} = 0
6402     { \use_i_delimit_by_q_stop:nw { \exp_not:n {#2} } }
6403     { \exp_args:Nf \__clist_item_N_loop:nw { \int_eval:n { #1 - 1 } } }
6404   }
6405   \cs_generate_variant:Nn \clist_item:Nn { c }

```

(End definition for `\clist_item:Nn`, `__clist_item:nnnN`, and `__clist_item_N_loop:nw`. These functions are documented on page 103.)

`\clist_item:nn` This starts in the same way as `\clist_item:Nn` by counting the items of the comma list. `__clist_item_n:nw` The final item should be space-trimmed before being brace-stripped, hence we insert a couple of odd-looking `\prg_do_nothing:` to avoid losing braces. Blank items are ignored.

```

\__clist_item_n_loop:nw
\__clist_item_n_end:n
\__clist_item_n_strip:w
6406   \cs_new:Npn \clist_item:nn #1#2
6407   {
6408     \__clist_item:ffnN
6409     { \clist_count:n {#1} }
6410     { \int_eval:n {#2} }
6411     {#1}
6412     \__clist_item_n:nw
6413   }
6414   \cs_new:Npn \__clist_item_n:nw #1
6415   { \__clist_item_n_loop:nw {#1} \prg_do_nothing: }
6416   \cs_new:Npn \__clist_item_n_loop:nw #1 #2,
6417   {
6418     \exp_args:No \tl_if_blank:nTF {#2}
6419     { \__clist_item_n_loop:nw {#1} \prg_do_nothing: }
6420     {
6421       \int_compare:nNnTF {#1} = 0
6422       { \exp_args:No \__clist_item_n_end:n {#2} }
6423       {
6424         \exp_args:Nf \__clist_item_n_loop:nw
6425         { \int_eval:n { #1 - 1 } }
6426         \prg_do_nothing:
6427       }
6428     }
6429   }
6430   \cs_new:Npn \__clist_item_n_end:n #1 #2 \q_stop
6431   {
6432     \__tl_trim_spaces:nn { \q_mark #1 }
6433     { \exp_last_unbraced:No \__clist_item_n_strip:w } ,
6434   }
6435   \cs_new:Npn \__clist_item_n_strip:w #1 , { \exp_not:n {#1} }

```

(End definition for `\clist_item:nn` and others. These functions are documented on page 103.)

12.10 Viewing comma lists

`\clist_show:N` Apply the general `__msg_show_variable:NNNnn`. In the case of an `n`-type comma-list, `\clist_show:c` we must do things by hand, using the same message `show-clist` as for an `N`-type comma-list but with an empty name (first argument).

```

6436 \cs_new_protected:Npn \clist_show:N #1
6437 {
6438   \__msg_show_variable:NNNnn #1
6439   \clist_if_exist:NTF \clist_if_empty:NTF { \clist }
6440   { \clist_map_function:NN #1 \__msg_show_item:n }
6441 }
6442 \cs_new_protected:Npn \clist_show:n #1
6443 {
6444   \__msg_show_pre:nnxxxx { LaTeX / kernel } { show-clist }
6445   { } { \clist_if_empty:nF {#1} { ? } } { } { }
6446   \__msg_show_wrap:n
6447   { \clist_map_function:nN {#1} \__msg_show_item:n }
6448 }
6449 \cs_generate_variant:Nn \clist_show:N { c }

```

(End definition for `\clist_show:N` and `\clist_show:n`. These functions are documented on page 103.)

`\clist_log:N` Redirect output of `\clist_show:N` and `\clist_show:n` to the log.

```

\clist_log:c
\clist_log:n
6450 \cs_new_protected:Npn \clist_log:N
6451 { \__msg_log_next: \clist_show:N }
6452 \cs_new_protected:Npn \clist_log:n
6453 { \__msg_log_next: \clist_show:n }
6454 \cs_generate_variant:Nn \clist_log:N { c }

```

(End definition for `\clist_log:N` and `\clist_log:n`. These functions are documented on page 104.)

12.11 Scratch comma lists

`\l_tmpa_clist` Temporary comma list variables.

```

\l_tmpb_clist
\g_tmpa_clist
\g_tmpb_clist
6455 \clist_new:N \l_tmpa_clist
6456 \clist_new:N \l_tmpb_clist
6457 \clist_new:N \g_tmpa_clist
6458 \clist_new:N \g_tmpb_clist

```

(End definition for `\l_tmpa_clist` and others. These variables are documented on page 104.)

6459 `\<initex | package>`

13 l3token implementation

6460 `\<*initex | package>`

6461 `\<@@=char>`

13.1 Manipulating and interrogating character tokens

Simple wrappers around the primitives.

```

\char_set_catcode:nn
\char_value_catcode:n
\char_show_value_catcode:n
6462 \cs_new_protected:Npn \char_set_catcode:nn #1#2
6463 {
6464   \tex_catcode:D \__int_eval:w #1 \__int_eval_end:
6465   = \__int_eval:w #2 \__int_eval_end:
6466 }
6467 \cs_new:Npn \char_value_catcode:n #1
6468 { \tex_the:D \tex_catcode:D \__int_eval:w #1 \__int_eval_end: }
6469 \cs_new_protected:Npn \char_show_value_catcode:n #1
6470 { \__msg_show_wrap:n { > ~ \char_value_catcode:n {#1} } }

```

(End definition for `\char_set_catcode:nn`, `\char_value_catcode:n`, and `\char_show_value_catcode:n`.
These functions are documented on page 107.)

```

\char_set_catcode_escape:N
\char_set_catcode_group_begin:N
\char_set_catcode_group_end:N
\char_set_catcode_math_toggle:N
\char_set_catcode_alignment:N
\char_set_catcode_end_line:N
\char_set_catcode_parameter:N
\char_set_catcode_math_superscript:N
\char_set_catcode_math_subscript:N
\char_set_catcode_ignore:N
\char_set_catcode_space:N
\char_set_catcode_letter:N
\char_set_catcode_other:N
\char_set_catcode_active:N
\char_set_catcode_comment:N
\char_set_catcode_invalid:N

6471 \cs_new_protected:Npn \char_set_catcode_escape:N #1
6472   { \char_set_catcode:nn { '#1 } { 0 } }
6473 \cs_new_protected:Npn \char_set_catcode_group_begin:N #1
6474   { \char_set_catcode:nn { '#1 } { 1 } }
6475 \cs_new_protected:Npn \char_set_catcode_group_end:N #1
6476   { \char_set_catcode:nn { '#1 } { 2 } }
6477 \cs_new_protected:Npn \char_set_catcode_math_toggle:N #1
6478   { \char_set_catcode:nn { '#1 } { 3 } }
6479 \cs_new_protected:Npn \char_set_catcode_alignment:N #1
6480   { \char_set_catcode:nn { '#1 } { 4 } }
6481 \cs_new_protected:Npn \char_set_catcode_end_line:N #1
6482   { \char_set_catcode:nn { '#1 } { 5 } }
6483 \cs_new_protected:Npn \char_set_catcode_parameter:N #1
6484   { \char_set_catcode:nn { '#1 } { 6 } }
6485 \cs_new_protected:Npn \char_set_catcode_math_superscript:N #1
6486   { \char_set_catcode:nn { '#1 } { 7 } }
6487 \cs_new_protected:Npn \char_set_catcode_math_subscript:N #1
6488   { \char_set_catcode:nn { '#1 } { 8 } }
6489 \cs_new_protected:Npn \char_set_catcode_ignore:N #1
6490   { \char_set_catcode:nn { '#1 } { 9 } }
6491 \cs_new_protected:Npn \char_set_catcode_space:N #1
6492   { \char_set_catcode:nn { '#1 } { 10 } }
6493 \cs_new_protected:Npn \char_set_catcode_letter:N #1
6494   { \char_set_catcode:nn { '#1 } { 11 } }
6495 \cs_new_protected:Npn \char_set_catcode_other:N #1
6496   { \char_set_catcode:nn { '#1 } { 12 } }
6497 \cs_new_protected:Npn \char_set_catcode_active:N #1
6498   { \char_set_catcode:nn { '#1 } { 13 } }
6499 \cs_new_protected:Npn \char_set_catcode_comment:N #1
6500   { \char_set_catcode:nn { '#1 } { 14 } }
6501 \cs_new_protected:Npn \char_set_catcode_invalid:N #1
6502   { \char_set_catcode:nn { '#1 } { 15 } }

```

(End definition for `\char_set_catcode_escape:N` and others. These functions are documented on page 106.)

```

\char_set_catcode_escape:n
\char_set_catcode_group_begin:n
\char_set_catcode_group_end:n
\char_set_catcode_math_toggle:n
\char_set_catcode_alignment:n
\char_set_catcode_end_line:n
\char_set_catcode_parameter:n
\char_set_catcode_math_superscript:n
\char_set_catcode_math_subscript:n
\char_set_catcode_ignore:n
\char_set_catcode_space:n
\char_set_catcode_letter:n
\char_set_catcode_other:n
\char_set_catcode_active:n
\char_set_catcode_comment:n
\char_set_catcode_invalid:n

6503 \cs_new_protected:Npn \char_set_catcode_escape:n #1
6504   { \char_set_catcode:nn {#1} { 0 } }
6505 \cs_new_protected:Npn \char_set_catcode_group_begin:n #1
6506   { \char_set_catcode:nn {#1} { 1 } }
6507 \cs_new_protected:Npn \char_set_catcode_group_end:n #1
6508   { \char_set_catcode:nn {#1} { 2 } }
6509 \cs_new_protected:Npn \char_set_catcode_math_toggle:n #1
6510   { \char_set_catcode:nn {#1} { 3 } }
6511 \cs_new_protected:Npn \char_set_catcode_alignment:n #1
6512   { \char_set_catcode:nn {#1} { 4 } }
6513 \cs_new_protected:Npn \char_set_catcode_end_line:n #1
6514   { \char_set_catcode:nn {#1} { 5 } }
6515 \cs_new_protected:Npn \char_set_catcode_parameter:n #1

```

```

6516 { \char_set_catcode:nn {#1} { 6 } }
6517 \cs_new_protected:Npn \char_set_catcode_math_superscript:n #1
6518 { \char_set_catcode:nn {#1} { 7 } }
6519 \cs_new_protected:Npn \char_set_catcode_math_subscript:n #1
6520 { \char_set_catcode:nn {#1} { 8 } }
6521 \cs_new_protected:Npn \char_set_catcode_ignore:n #1
6522 { \char_set_catcode:nn {#1} { 9 } }
6523 \cs_new_protected:Npn \char_set_catcode_space:n #1
6524 { \char_set_catcode:nn {#1} { 10 } }
6525 \cs_new_protected:Npn \char_set_catcode_letter:n #1
6526 { \char_set_catcode:nn {#1} { 11 } }
6527 \cs_new_protected:Npn \char_set_catcode_other:n #1
6528 { \char_set_catcode:nn {#1} { 12 } }
6529 \cs_new_protected:Npn \char_set_catcode_active:n #1
6530 { \char_set_catcode:nn {#1} { 13 } }
6531 \cs_new_protected:Npn \char_set_catcode_comment:n #1
6532 { \char_set_catcode:nn {#1} { 14 } }
6533 \cs_new_protected:Npn \char_set_catcode_invalid:n #1
6534 { \char_set_catcode:nn {#1} { 15 } }

```

(End definition for `\char_set_catcode_escape:n` and others. These functions are documented on page 107.)

```

\char_set_mathcode:nn Pretty repetitive, but necessary!
\char_value_mathcode:n
\char_show_value_mathcode:n
\char_set_lccode:nn
\char_value_lccode:n
\char_show_value_lccode:n
\char_set_uccode:nn
\char_value_uccode:n
\char_show_value_uccode:n
\char_set_sfcode:nn
\char_value_sfcode:n
\char_show_value_sfcode:n
6535 \cs_new_protected:Npn \char_set_mathcode:nn #1#2
6536 {
6537   \tex_mathcode:D \__int_eval:w #1 \__int_eval_end:
6538   = \__int_eval:w #2 \__int_eval_end:
6539 }
6540 \cs_new:Npn \char_value_mathcode:n #1
6541 { \tex_the:D \tex_mathcode:D \__int_eval:w #1 \__int_eval_end: }
6542 \cs_new_protected:Npn \char_show_value_mathcode:n #1
6543 { \__msg_show_wrap:n { > ~ \char_value_mathcode:n {#1} } }
6544 \cs_new_protected:Npn \char_set_lccode:nn #1#2
6545 {
6546   \tex_lccode:D \__int_eval:w #1 \__int_eval_end:
6547   = \__int_eval:w #2 \__int_eval_end:
6548 }
6549 \cs_new:Npn \char_value_lccode:n #1
6550 { \tex_the:D \tex_lccode:D \__int_eval:w #1 \__int_eval_end: }
6551 \cs_new_protected:Npn \char_show_value_lccode:n #1
6552 { \__msg_show_wrap:n { > ~ \char_value_lccode:n {#1} } }
6553 \cs_new_protected:Npn \char_set_uccode:nn #1#2
6554 {
6555   \tex_uccode:D \__int_eval:w #1 \__int_eval_end:
6556   = \__int_eval:w #2 \__int_eval_end:
6557 }
6558 \cs_new:Npn \char_value_uccode:n #1
6559 { \tex_the:D \tex_uccode:D \__int_eval:w #1 \__int_eval_end: }
6560 \cs_new_protected:Npn \char_show_value_uccode:n #1
6561 { \__msg_show_wrap:n { > ~ \char_value_uccode:n {#1} } }
6562 \cs_new_protected:Npn \char_set_sfcode:nn #1#2
6563 {
6564   \tex_sfcode:D \__int_eval:w #1 \__int_eval_end:

```

```

6565     = \__int_eval:w #2 \__int_eval_end:
6566   }
6567 \cs_new:Npn \char_value_sfcode:n #1
6568 { \tex_the:D \tex_sfcode:D \__int_eval:w #1\__int_eval_end: }
6569 \cs_new_protected:Npn \char_show_value_sfcode:n #1
6570 { \__msg_show_wrap:n { > ~ \char_value_sfcode:n {#1} } }

```

(End definition for `\char_set_mathcode:nn` and others. These functions are documented on page 108.)

`\l_char_active_seq` Two sequences for dealing with special characters. The first is characters which may be active, the second longer list is for “special” characters more generally. Both lists are escaped so that for example bulk code assignments can be carried out. In both cases, the order is by ASCII character code (as is done in for example `\ExplSyntaxOn`).

`\l_char_special_seq`

```

6571 \seq_new:N \l_char_special_seq
6572 \seq_set_split:Nnn \l_char_special_seq { }
6573 { \ \ " \# \$ \% \& \ \ ^ \_ \{ \} \~ }
6574 \seq_new:N \l_char_active_seq
6575 \seq_set_split:Nnn \l_char_active_seq { }
6576 { \ " \$ \% \^ \_ \~ }

```

(End definition for `\l_char_active_seq` and `\l_char_special_seq`. These variables are documented on page 109.)

13.2 Creating character tokens

`\char_set_active_eq:NN` Four simple functions with very similar definitions, so set up using an auxiliary. These are similar to LuaTeX’s `\letcharcode` primitive.

`\char_set_active_eq:Nc`

`\char_gset_active_eq:NN`

`\char_gset_active_eq:Nc`

`\char_set_active_eq:nN`

`\char_set_active_eq:nc`

`\char_gset_active_eq:nN`

`\char_gset_active_eq:nc`

```

6577 \group_begin:
6578 \char_set_catcode_active:N \^^@
6579 \cs_set_protected:Npn \__char_tmp:nN #1#2
6580 {
6581   \cs_new_protected:cpn { #1 :nN } ##1
6582   {
6583     \group_begin:
6584     \char_set_lccode:nn { '\^^@ } { ##1 }
6585     \tex_lowercase:D { \group_end: #2 ^^@ }
6586   }
6587   \cs_new_protected:cpx { #1 :NN } ##1
6588   { \exp_not:c { #1 : nN } { '##1 } }
6589 }
6590 \__char_tmp:nN { char_set_active_eq } \cs_set_eq:NN
6591 \__char_tmp:nN { char_gset_active_eq } \cs_gset_eq:NN
6592 \group_end:
6593 \cs_generate_variant:Nn \char_set_active_eq:NN { Nc }
6594 \cs_generate_variant:Nn \char_gset_active_eq:NN { Nc }
6595 \cs_generate_variant:Nn \char_set_active_eq:nN { nc }
6596 \cs_generate_variant:Nn \char_gset_active_eq:nN { nc }

```

(End definition for `\char_set_active_eq:NN` and others. These functions are documented on page 105.)

`\char_generate:nn` The aim here is to generate characters of (broadly) arbitrary category code. Where possible, that is done using engine support (XeTeX, LuaTeX). There are though various issues which are covered below. At the interface layer, turn the two arguments into integers up-front so this is only done once.

`__char_generate:nn`

`__char_generate_aux:nnw`

`\l__char_tmp_tl`

`\c__char_max_int`

`__char_generate_invalid_catcode:`

```

6597 \cs_new:Npn \char_generate:nn #1#2
6598 {
6599   \exp:w \exp_after:wN \__char_generate_aux:w
6600   \__int_value:w \__int_eval:w #1 \exp_after:wN ;
6601   \__int_value:w \__int_eval:w #2 ;
6602 }
6603 \cs_new:Npn \__char_generate:nn #1#2
6604 {
6605   \exp:w \exp_after:wN
6606   \__char_generate_aux:nnw \exp_after:wN
6607   { \__int_value:w \__int_eval:w #1 \exp_after:wN }
6608   {#2} \exp_end:
6609 }

```

Before doing any actual conversion, first some special case filtering. The `\Ucharcat` primitive cannot make active chars, so that is turned off here: if the primitive gets altered then the code is already in place for 8-bit engines and will kick in for LuaTeX too. Spaces are also banned here as LuaTeX emulation only makes normal (charcode 32 spaces. However, `^^@` is filtered out separately as that can't be done with macro emulation either, so is flagged up separately. That done, hand off to the engine-dependent part.

```

6610 \cs_new:Npn \__char_generate_aux:w #1 ; #2 ;
6611 {
6612   \if_int_compare:w #2 = 13 \exp_stop_f:
6613   \__msg_kernel_expandable_error:nn { kernel } { char-active }
6614   \else:
6615     \if_int_compare:w #2 = 10 \exp_stop_f:
6616     \if_int_compare:w #1 = 0 \exp_stop_f:
6617     \__msg_kernel_expandable_error:nn { kernel } { char-null-space }
6618     \else:
6619     \__msg_kernel_expandable_error:nn { kernel } { char-space }
6620     \fi:
6621   \else:
6622     \if_int_odd:w 0
6623     \if_int_compare:w #2 < 1 \exp_stop_f: 1 \fi:
6624     \if_int_compare:w #2 = 5 \exp_stop_f: 1 \fi:
6625     \if_int_compare:w #2 = 9 \exp_stop_f: 1 \fi:
6626     \if_int_compare:w #2 > 13 \exp_stop_f: 1 \fi: \exp_stop_f:
6627     \__msg_kernel_expandable_error:nn { kernel }
6628     { char-invalid-catcode }
6629   \else:
6630     \if_int_odd:w 0
6631     \if_int_compare:w #1 < 0 \exp_stop_f: 1 \fi:
6632     \if_int_compare:w #1 > \c__char_max_int 1 \fi: \exp_stop_f:
6633     \__msg_kernel_expandable_error:nn { kernel }
6634     { char-out-of-range }
6635   \else:
6636     \__char_generate_aux:nnw {#1} {#2}
6637   \fi:
6638   \fi:
6639   \fi:
6640   \fi:
6641   \exp_end:
6642 }
6643 \tl_new:N \l__char_tmp_tl

```


Engine-dependent definitions are now needed for the implementation. For LuaTeX and recent XeTeX releases there is engine-level support. They can do cases that macro emulation can't. All of those are filtered out here using a primitive-based boolean expression for speed. The final level is the basic definition at the engine level: the arguments here are integers so there is no need to worry about them too much.

```

6644 \group_begin:
6645 \*package>
6646   \char_set_catcode_active:N \^^L
6647   \cs_set:Npn \^^L { }
6648 \*package>
6649 \char_set_catcode_other:n { 0 }
6650 \if_int_odd:w 0
6651   \cs_if_exist:NT \luatex_directlua:D { 1 }
6652   \cs_if_exist:NT \utex_charcat:D { 1 } \exp_stop_f:
6653   \int_const:Nn \c__char_max_int { 1114111 }
6654   \cs_if_exist:NTF \luatex_directlua:D
6655   {
6656     \cs_new:Npn \__char_generate_aux:nw #1#2#3 \exp_end:
6657     {
6658       #3
6659       \exp_after:wN \exp_end:
6660       \luatex_directlua:D { l3kernel.charcat(#1, #2) }
6661     }
6662   }
6663   {
6664     \cs_new:Npn \__char_generate_aux:nw #1#2#3 \exp_end:
6665     {
6666       #3
6667       \exp_after:wN \exp_end:
6668       \utex_charcat:D #1 ~ #2 ~
6669     }
6670   }
6671 \else:

```

For engines where `\Ucharcat` isn't available (or emulated) then we have to work in macros, and cover only the 8-bit range. The first stage is to build up a `tl` containing `^^@` with each category code that can be accessed in this way, with an error set up for the other cases. This is all done such that it can be quickly accessed using a `\if_case:w` low-level conditional. There are a few things to notice here. As `^^L` is `\outer` we need to locally set it to avoid a problem. To get open/close braces into the list, they are set up using `\if_false:` pairing and are then x-type expanded together into the desired form.

```

6672   \int_const:Nn \c__char_max_int { 255 }
6673   \tl_set:Nn \l__char_tmp_tl { \exp_not:N \or: }
6674   \char_set_catcode_group_begin:n { 0 } % {
6675   \tl_put_right:Nn \l__char_tmp_tl { ^^@ \if_false: } }
6676   \char_set_catcode_group_end:n { 0 }
6677   \tl_put_right:Nn \l__char_tmp_tl { { \fi: \exp_not:N \or: ^^@ } % }
6678   \tl_set:Nx \l__char_tmp_tl { \l__char_tmp_tl }
6679   \char_set_catcode_math_toggle:n { 0 }
6680   \tl_put_right:Nn \l__char_tmp_tl { \or: ^^@ }

```

As TeX will be very unhappy if it finds an alignment character inside a primitive `\halign` even when skipping false branches, some precautions are required. TeX will be happy if the token is hidden inside `\unexpanded` (which needs to be the primitive). The expansion

chain here is required so that the conditional gets cleaned up correctly (other code assumes there is exactly one token to skip during the clean-up).

```

6681 \char_set_catcode_alignment:n { 0 }
6682 \tl_put_right:Nn \l__char_tmp_tl
6683 {
6684   \or:
6685     \etex_unexpanded:D \exp_after:wN
6686     { \exp_after:wN ^^@ \exp_after:wN }
6687 }
6688 \tl_put_right:Nn \l__char_tmp_tl { \or: }
6689 \char_set_catcode_parameter:n { 0 }
6690 \tl_put_right:Nn \l__char_tmp_tl { \or: ^^@ }
6691 \char_set_catcode_math_superscript:n { 0 }
6692 \tl_put_right:Nn \l__char_tmp_tl { \or: ^^@ }
6693 \char_set_catcode_math_subscript:n { 0 }
6694 \tl_put_right:Nn \l__char_tmp_tl { \or: ^^@ }
6695 \tl_put_right:Nn \l__char_tmp_tl { \or: }

```

For making spaces, there needs to be an o-type expansion of a `\use:n` (or some other tokenization) to avoid dropping the space. We also set up active tokens although they are (currently) filtered out by the interface layer (`\Ucharcat` cannot make active tokens).

```

6696 \char_set_catcode_space:n { 0 }
6697 \tl_put_right:Nn \l__char_tmp_tl { \use:n { \or: } ^^@ }
6698 \char_set_catcode_letter:n { 0 }
6699 \tl_put_right:Nn \l__char_tmp_tl { \or: ^^@ }
6700 \char_set_catcode_other:n { 0 }
6701 \tl_put_right:Nn \l__char_tmp_tl { \or: ^^@ }
6702 \char_set_catcode_active:n { 0 }
6703 \tl_put_right:Nn \l__char_tmp_tl { \or: ^^@ }

```

Convert the above temporary list into a series of constant token lists, one for each character code, using `\tex_lowercase:D` to convert `^^@` in each case. The x-type expansion ensures that `\tex_lowercase:D` receives the contents of the token list. In package mode, `^^L` is awkward hence this is done in three parts. Notice that at this stage `^^@` is active.

```

6704 \cs_set_protected:Npn \__char_tmp:n #1
6705 {
6706   \char_set_lccode:nn { 0 } {#1}
6707   \char_set_lccode:nn { 32 } {#1}
6708   \exp_args:Nx \tex_lowercase:D
6709   {
6710     \tl_const:Nn
6711       \exp_not:c { c__char_ \__int_to_roman:w #1 _tl }
6712       { \exp_not:o \l__char_tmp_tl }
6713   }
6714 }
6715 <package>
6716 \int_step_function:nnnN { 0 } { 1 } { 11 } \__char_tmp:n
6717 \group_begin:
6718   \tl_replace_once:Nnn \l__char_tmp_tl { ^^@ } { \ERROR }
6719   \__char_tmp:n { 12 }
6720 \group_end:
6721 \int_step_function:nnnN { 13 } { 1 } { 255 } \__char_tmp:n
6722 </package>
6723 <*initex>

```

```

6724 \int_step_function:nnnN { 0 } { 1 } { 255 } \__char_tmp:n
6725 </initex>
6726 \cs_new:Npn \__char_generate_aux:nnw #1#2#3 \exp_end:
6727 {
6728   #3
6729   \exp_after:wN \exp_after:wN
6730   \exp_after:wN \exp_end:
6731   \exp_after:wN \exp_after:wN
6732   \if_case:w #2
6733   \exp_last_unbraced:Nv \exp_stop_f:
6734   { c__char_ \__int_to_roman:w #1 _tl }
6735   \fi:
6736 }
6737 \fi:
6738 \group_end:

```

(End definition for `\char_generate:nn` and others. These functions are documented on page 106.)

13.3 Generic tokens

```

6739 <@@=token>

```

`\token_to_meaning:N` These are all defined in `l3basics`, as they are needed “early”. This is just a reminder!

`\token_to_meaning:c`

(End definition for `\token_to_meaning:N` and `\token_to_str:N`. These functions are documented on page 110.)

`\token_to_str:N`

`\token_to_str:c`

`\token_new:Nn`

Creates a new token.

```

6740 \cs_new_protected:Npn \token_new:Nn #1#2 { \cs_new_eq:NN #1 #2 }

```

(End definition for `\token_new:Nn`. This function is documented on page 109.)

`\c_group_begin_token`

`\c_group_end_token`

`\c_math_toggle_token`

`\c_alignment_token`

`\c_parameter_token`

We define these useful tokens. For the brace and space tokens things have to be done by hand: the formal argument spec. for `\cs_new_eq:NN` does not cover them so we do things by hand. (As currently coded it would *work* with `\cs_new_eq:NN` but that’s not really a great idea to show off: we want people to stick to the defined interfaces and that includes us.) So that these few odd names go into the log when appropriate there is a need to hand-apply the `__chk_if_free_cs:N` check.

`\c_math_superscript_token`

`\c_math_subscript_token`

`\c_space_token`

`\c_catcode_letter_token`

`\c_catcode_other_token`

```

6741 \group_begin:
6742 \__chk_if_free_cs:N \c_group_begin_token
6743 \tex_global:D \tex_let:D \c_group_begin_token {
6744 \__chk_if_free_cs:N \c_group_end_token
6745 \tex_global:D \tex_let:D \c_group_end_token }
6746 \char_set_catcode_math_toggle:N \*
6747 \cs_new_eq:NN \c_math_toggle_token *
6748 \char_set_catcode_alignment:N \*
6749 \cs_new_eq:NN \c_alignment_token *
6750 \cs_new_eq:NN \c_parameter_token #
6751 \cs_new_eq:NN \c_math_superscript_token ^
6752 \char_set_catcode_math_subscript:N \*
6753 \cs_new_eq:NN \c_math_subscript_token *
6754 \__chk_if_free_cs:N \c_space_token
6755 \use:n { \tex_global:D \tex_let:D \c_space_token = ~ } ~
6756 \cs_new_eq:NN \c_catcode_letter_token a
6757 \cs_new_eq:NN \c_catcode_other_token 1
6758 \group_end:

```

(End definition for `\c_group_begin_token` and others. These functions are documented on page 109.)

`\c_catcode_active_tl` Not an implicit token!

```
6759 \group_begin:
6760   \char_set_catcode_active:N \*
6761   \tl_const:Nn \c_catcode_active_tl { \exp_not:N * }
6762 \group_end:
```

(End definition for `\c_catcode_active_tl`. This variable is documented on page 109.)

13.4 Token conditionals

`\token_if_group_begin_p:N` Check if token is a begin group token. We use the constant `\c_group_begin_token` for this.
`\token_if_group_begin:NTF`

```
6763 \prg_new_conditional:Npnn \token_if_group_begin:N #1 { p , T , F , TF }
6764 {
6765   \if_catcode:w \exp_not:N #1 \c_group_begin_token
6766   \prg_return_true: \else: \prg_return_false: \fi:
6767 }
```

(End definition for `\token_if_group_begin:NTF`. This function is documented on page 110.)

`\token_if_group_end_p:N` Check if token is a end group token. We use the constant `\c_group_end_token` for this.
`\token_if_group_end:NTF`

```
6768 \prg_new_conditional:Npnn \token_if_group_end:N #1 { p , T , F , TF }
6769 {
6770   \if_catcode:w \exp_not:N #1 \c_group_end_token
6771   \prg_return_true: \else: \prg_return_false: \fi:
6772 }
```

(End definition for `\token_if_group_end:NTF`. This function is documented on page 110.)

`\token_if_math_toggle_p:N` Check if token is a math shift token. We use the constant `\c_math_toggle_token` for this.
`\token_if_math_toggle:NTF`

```
6773 \prg_new_conditional:Npnn \token_if_math_toggle:N #1 { p , T , F , TF }
6774 {
6775   \if_catcode:w \exp_not:N #1 \c_math_toggle_token
6776   \prg_return_true: \else: \prg_return_false: \fi:
6777 }
```

(End definition for `\token_if_math_toggle:NTF`. This function is documented on page 110.)

`\token_if_alignment_p:N` Check if token is an alignment tab token. We use the constant `\c_alignment_token` for this.
`\token_if_alignment:NTF`

```
6778 \prg_new_conditional:Npnn \token_if_alignment:N #1 { p , T , F , TF }
6779 {
6780   \if_catcode:w \exp_not:N #1 \c_alignment_token
6781   \prg_return_true: \else: \prg_return_false: \fi:
6782 }
```

(End definition for `\token_if_alignment:NTF`. This function is documented on page 110.)

`\token_if_parameter_p:N` Check if token is a parameter token. We use the constant `\c_parameter_token` for this.
`\token_if_parameter:N \underline{TF}` We have to trick T_EX a bit to avoid an error message: within a group we prevent `\c_parameter_token` from behaving like a macro parameter character. The definitions of `\prg_new_conditional:Npnn` are global, so they will remain after the group.

```

6783 \group_begin:
6784 \cs_set_eq:NN \c_parameter_token \scan_stop:
6785 \prg_new_conditional:Npnn \token_if_parameter:N #1 { p , T , F , TF }
6786 {
6787     \if_catcode:w \exp_not:N #1 \c_parameter_token
6788     \prg_return_true: \else: \prg_return_false: \fi:
6789 }
6790 \group_end:

```

(End definition for `\token_if_parameter:N \underline{TF}` . This function is documented on page 111.)

`\token_if_math_superscript_p:N` Check if token is a math superscript token. We use the constant `\c_math_superscript_token` for this.
`\token_if_math_superscript:N \underline{TF}`

```

6791 \prg_new_conditional:Npnn \token_if_math_superscript:N #1
6792 { p , T , F , TF }
6793 {
6794     \if_catcode:w \exp_not:N #1 \c_math_superscript_token
6795     \prg_return_true: \else: \prg_return_false: \fi:
6796 }

```

(End definition for `\token_if_math_superscript:N \underline{TF}` . This function is documented on page 111.)

`\token_if_math_subscript_p:N` Check if token is a math subscript token. We use the constant `\c_math_subscript_token` for this.
`\token_if_math_subscript:N \underline{TF}`

```

6797 \prg_new_conditional:Npnn \token_if_math_subscript:N #1 { p , T , F , TF }
6798 {
6799     \if_catcode:w \exp_not:N #1 \c_math_subscript_token
6800     \prg_return_true: \else: \prg_return_false: \fi:
6801 }

```

(End definition for `\token_if_math_subscript:N \underline{TF}` . This function is documented on page 111.)

`\token_if_space_p:N` Check if token is a space token. We use the constant `\c_space_token` for this.
`\token_if_space:N \underline{TF}`

```

6802 \prg_new_conditional:Npnn \token_if_space:N #1 { p , T , F , TF }
6803 {
6804     \if_catcode:w \exp_not:N #1 \c_space_token
6805     \prg_return_true: \else: \prg_return_false: \fi:
6806 }

```

(End definition for `\token_if_space:N \underline{TF}` . This function is documented on page 111.)

`\token_if_letter_p:N` Check if token is a letter token. We use the constant `\c_catcode_letter_token` for this.
`\token_if_letter:N \underline{TF}`

```

6807 \prg_new_conditional:Npnn \token_if_letter:N #1 { p , T , F , TF }
6808 {
6809     \if_catcode:w \exp_not:N #1 \c_catcode_letter_token
6810     \prg_return_true: \else: \prg_return_false: \fi:
6811 }

```

(End definition for `\token_if_letter:N \underline{TF}` . This function is documented on page 111.)

`\token_if_other_p:N` Check if token is an other char token. We use the constant `\c_catcode_other_token`
`\token_if_other:N \underline{TF}` for this.

```
6812 \prg_new_conditional:Npnn \token_if_other:N #1 { p , T , F , TF }
6813 {
6814     \if_catcode:w \exp_not:N #1 \c_catcode_other_token
6815     \prg_return_true: \else: \prg_return_false: \fi:
6816 }
```

(End definition for `\token_if_other:N \underline{TF}` . This function is documented on page 111.)

`\token_if_active_p:N` Check if token is an active char token. We use the constant `\c_catcode_active_tl` for
`\token_if_active:N \underline{TF}` this. A technical point is that `\c_catcode_active_tl` is in fact a macro expanding to
`\exp_not:N *`, where `*` is active.

```
6817 \prg_new_conditional:Npnn \token_if_active:N #1 { p , T , F , TF }
6818 {
6819     \if_catcode:w \exp_not:N #1 \c_catcode_active_tl
6820     \prg_return_true: \else: \prg_return_false: \fi:
6821 }
```

(End definition for `\token_if_active:N \underline{TF}` . This function is documented on page 111.)

`\token_if_eq_meaning_p:NN` Check if the tokens #1 and #2 have same meaning.

`\token_if_eq_meaning:NN \underline{TF}`

```
6822 \prg_new_conditional:Npnn \token_if_eq_meaning:NN #1#2 { p , T , F , TF }
6823 {
6824     \if_meaning:w #1 #2
6825     \prg_return_true: \else: \prg_return_false: \fi:
6826 }
```

(End definition for `\token_if_eq_meaning:NN \underline{TF}` . This function is documented on page 111.)

`\token_if_eq_catcode_p:NN` Check if the tokens #1 and #2 have same category code.

`\token_if_eq_catcode:NN \underline{TF}`

```
6827 \prg_new_conditional:Npnn \token_if_eq_catcode:NN #1#2 { p , T , F , TF }
6828 {
6829     \if_catcode:w \exp_not:N #1 \exp_not:N #2
6830     \prg_return_true: \else: \prg_return_false: \fi:
6831 }
```

(End definition for `\token_if_eq_catcode:NN \underline{TF}` . This function is documented on page 111.)

`\token_if_eq_charcode_p:NN` Check if the tokens #1 and #2 have same character code.

`\token_if_eq_charcode:NN \underline{TF}`

```
6832 \prg_new_conditional:Npnn \token_if_eq_charcode:NN #1#2 { p , T , F , TF }
6833 {
6834     \if_charcode:w \exp_not:N #1 \exp_not:N #2
6835     \prg_return_true: \else: \prg_return_false: \fi:
6836 }
```

(End definition for `\token_if_eq_charcode:NN \underline{TF}` . This function is documented on page 111.)

`\token_if_macro_p:N` When a token is a macro, `\token_to_meaning:N` will always output something like
`\token_if_macro:N \underline{TF}` `\long macro:#1->#1` so we could naively check to see if the meaning contains `->`.
`__token_if_macro_p:w` However, this can fail the five `\...mark` primitives, whose meaning has the form
`\...mark:<user material>`. The problem is that the `<user material>` can contain `->`.

However, only characters, macros, and marks can contain the colon character. The idea is thus to grab until the first `:`, and analyse what is left. However, macros can have

any combination of `\long`, `\protected` or `\outer` (not used in L^AT_EX3) before the string `macro:.` We thus only select the part of the meaning between the first `ma` and the first following `:`. If this string is `cro`, then we have a macro. If the string is `rk`, then we have a mark. The string can also be `cro parameter character` for a colon with a weird category code (namely the usual category code of `#`). Otherwise, it is empty.

This relies on the fact that `\long`, `\protected`, `\outer` cannot contain `ma`, regardless of the escape character, even if the escape character is `m...`

Both `ma` and `:` must be of category code 12 (other), so are detokenized.

```

6837 \use:x
6838 {
6839   \prg_new_conditional:Npnn \exp_not:N \token_if_macro:N ##1
6840   { p , T , F , TF }
6841   {
6842     \exp_not:N \exp_after:wN \exp_not:N \__token_if_macro_p:w
6843     \exp_not:N \token_to_meaning:N ##1 \tl_to_str:n { ma : }
6844     \exp_not:N \q_stop
6845   }
6846   \cs_new:Npn \exp_not:N \__token_if_macro_p:w
6847   ##1 \tl_to_str:n { ma } ##2 \c_colon_str ##3 \exp_not:N \q_stop
6848 }
6849 {
6850   \if_int_compare:w \__str_if_eq_x:nn { #2 } { cro } = 0 \exp_stop_f:
6851   \prg_return_true:
6852   \else:
6853   \prg_return_false:
6854   \fi:
6855 }

```

(End definition for `\token_if_macro:N`TF and `__token_if_macro_p:w`. These functions are documented on page 112.)

`\token_if_cs_p:N` Check if token has same catcode as a control sequence. This follows the same pattern as `\token_if_letter:N` etc. We use `\scan_stop:` for this.

`\token_if_cs:N`TF

```

6856 \prg_new_conditional:Npnn \token_if_cs:N #1 { p , T , F , TF }
6857 {
6858   \if_catcode:w \exp_not:N #1 \scan_stop:
6859   \prg_return_true: \else: \prg_return_false: \fi:
6860 }

```

(End definition for `\token_if_cs:N`TF. This function is documented on page 112.)

`\token_if_expandable_p:N` Check if token is expandable. We use the fact that T_EX will temporarily convert `\exp_not:N` $\langle token \rangle$ into `\scan_stop:` if $\langle token \rangle$ is expandable. An undefined token is not considered as expandable. No problem nesting the conditionals, since the third `#1` is only skipped if it is non-expandable (hence not part of T_EX's conditional apparatus).

`\token_if_expandable:N`TF

```

6861 \prg_new_conditional:Npnn \token_if_expandable:N #1 { p , T , F , TF }
6862 {
6863   \exp_after:wN \if_meaning:w \exp_not:N #1 #1
6864   \prg_return_false:
6865   \else:
6866   \if_cs_exist:N #1
6867   \prg_return_true:
6868   \else:

```

```

6869         \prg_return_false:
6870         \fi:
6871     \fi:
6872 }

```

(End definition for `\token_if_expandable:NTF`. This function is documented on page 112.)

```

\__token_delimit_by_char:w
\__token_delimit_by_count:w
\__token_delimit_by_dimen:w
\__token_delimit_by_macro:w
\__token_delimit_by_muskip:w
\__token_delimit_by_skip:w
\__token_delimit_by_toks:w

```

These auxiliary functions are used below to define some conditionals which detect whether the `\meaning` of their argument begins with a particular string. Each auxiliary takes an argument delimited by a string, a second one delimited by `\q_stop`, and returns the first one and its delimiter. This result will eventually be compared to another string.

```

6873 \group_begin:
6874 \cs_set_protected:Npn \__token_tmp:w #1
6875 {
6876     \use:x
6877     {
6878         \cs_new:Npn \exp_not:c { __token_delimit_by_ #1 :w }
6879         #####1 \tl_to_str:n {#1} #####2 \exp_not:N \q_stop
6880         { #####1 \tl_to_str:n {#1} }
6881     }
6882 }
6883 \__token_tmp:w { char" }
6884 \__token_tmp:w { count }
6885 \__token_tmp:w { dimen }
6886 \__token_tmp:w { macro }
6887 \__token_tmp:w { muskip }
6888 \__token_tmp:w { skip }
6889 \__token_tmp:w { toks }
6890 \group_end:

```

(End definition for `__token_delimit_by_char:w` and others.)

```

\token_if_chardef_p:N
\token_if_chardef:NTF
\token_if_mathchardef_p:N
\token_if_mathchardef:NTF
\token_if_long_macro_p:N
\token_if_long_macro:NTF
\token_if_protected_macro_p:N
\token_if_protected_macro:NTF
\token_if_protected_long_macro_p:N
\token_if_protected_long_macro:NTF
\token_if_dim_register_p:N
\token_if_dim_register:NTF
\token_if_int_register_p:N
\token_if_int_register:NTF
\token_if_muskip_register_p:N
\token_if_muskip_register:NTF
\token_if_skip_register_p:N
\token_if_skip_register:NTF
\token_if_toks_register_p:N
\token_if_toks_register:NTF

```

Each of these conditionals tests whether its argument's `\meaning` starts with a given string. This is essentially done by having an auxiliary grab an argument delimited by the string and testing whether the argument was empty. Of course, a copy of this string must first be added to the end of the `\meaning` to avoid a runaway argument in case it does not contain the string. Two complications arise. First, the escape character is not fixed, and cannot be included in the delimiter of the auxiliary function (this function cannot be defined on the fly because tests must remain expandable): instead the first argument of the auxiliary (plus the delimiter to avoid complications with trailing spaces) is compared using `__str_if_eq_x_return:nn` to the result of applying `\token_to_str:N` to a control sequence. Second, the `\meaning` of primitives such as `\dimen` or `\dimendef` starts in the same way as registers such as `\dimen123`, so they must be tested for.

Characters used as delimiters must have catcode 12 and are obtained through `\tl_to_str:n`. This requires doing all definitions within x-expansion. The temporary function `__token_tmp:w` used to define each conditional receives three arguments: the name of the conditional, the auxiliary's delimiter (also used to name the auxiliary), and the string to which one compares the auxiliary's result. Note that the `\meaning` of a protected long macro starts with `\protected\long macro`, with no space after `\protected` but a space after `\long`, hence the mixture of `\token_to_str:N` and `\tl_to_str:n`.

For the first five conditionals, `\cs_if_exist:cT` turns out to be `false`, and the code boils down to a string comparison between the result of the auxiliary on the `\meaning`

of the conditional's argument #####1, and #3. Both are evaluated at run-time, as this is important to get the correct escape character.

The other five conditionals have additional code that compares the argument #####1 to two T_EX primitives which would wrongly be recognized as registers otherwise. Despite using T_EX's primitive conditional construction, this does not break when #####1 is itself a conditional, because branches of the conditionals are only skipped if #####1 is one of the two primitives that are tested for (which are not T_EX conditionals).

```

6891 \group_begin:
6892 \cs_set_protected:Npn \__token_tmp:w #1#2#3
6893 {
6894   \use:x
6895   {
6896     \prg_new_conditional:Npnn \exp_not:c { token_if_ #1 :N } #####1
6897     { p , T , F , TF }
6898     {
6899       \cs_if_exist:cT { tex_ #2 :D }
6900       {
6901         \exp_not:N \if_meaning:w #####1 \exp_not:c { tex_ #2 :D }
6902         \exp_not:N \prg_return_false:
6903         \exp_not:N \else:
6904         \exp_not:N \if_meaning:w #####1 \exp_not:c { tex_ #2 def:D }
6905         \exp_not:N \prg_return_false:
6906         \exp_not:N \else:
6907       }
6908       \exp_not:N \__str_if_eq_x_return:nn
6909       {
6910         \exp_not:N \exp_after:wN
6911         \exp_not:c { __token_delimit_by_ #2 :w }
6912         \exp_not:N \token_to_meaning:N #####1
6913         ? \tl_to_str:n {#2} \exp_not:N \q_stop
6914       }
6915       { \exp_not:n {#3} }
6916       \cs_if_exist:cT { tex_ #2 :D }
6917       {
6918         \exp_not:N \fi:
6919         \exp_not:N \fi:
6920       }
6921     }
6922   }
6923 }
6924 \__token_tmp:w { chardef } { char" } { \token_to_str:N \char" }
6925 \__token_tmp:w { mathchardef } { char" } { \token_to_str:N \mathchar" }
6926 \__token_tmp:w { long_macro } { macro } { \tl_to_str:n { \long } macro }
6927 \__token_tmp:w { protected_macro } { macro }
6928   { \tl_to_str:n { \protected } macro }
6929 \__token_tmp:w { protected_long_macro } { macro }
6930   { \token_to_str:N \protected \tl_to_str:n { \long } macro }
6931 \__token_tmp:w { dim_register } { dimen } { \token_to_str:N \dimen }
6932 \__token_tmp:w { int_register } { count } { \token_to_str:N \count }
6933 \__token_tmp:w { muskip_register } { muskip } { \token_to_str:N \muskip }
6934 \__token_tmp:w { skip_register } { skip } { \token_to_str:N \skip }
6935 \__token_tmp:w { toks_register } { toks } { \token_to_str:N \toks }
6936 \group_end:

```

(End definition for `\token_if_chardef:NTF` and others. These functions are documented on page 112.)

`\token_if_primitive_p:N` We filter out macros first, because they cause endless trouble later otherwise.

`\token_if_primitive:NTF` Primitives are almost distinguished by the fact that the result of `\token_to_meaning:N` is formed from letters only. Every other token has either a space (e.g., the letter A), a digit (e.g., `\count123`) or a double quote (e.g., `\char"A`).

Ten exceptions: on the one hand, `\tex_undefined:D` is not a primitive, but its meaning is undefined, only letters; on the other hand, `\space`, `\italiccorr`, `\hyphen`, `\firstmark`, `\topmark`, `\botmark`, `\splitfirstmark`, `\splitbotmark`, and `\nullfont` are primitives, but have non-letters in their meaning.

We start by removing the two first (non-space) characters from the meaning. This removes the escape character (which may be inexistent depending on `\endlinechar`), and takes care of three of the exceptions: `\space`, `\italiccorr` and `\hyphen`, whose meaning is at most two characters. This leaves a string terminated by some `:`, and `\q_stop`.

The meaning of each one of the five `\...mark` primitives has the form $\langle letters \rangle : \langle user material \rangle$. In other words, the first non-letter is a colon. We remove everything after the first colon.

We are now left with a string, which we must analyze. For primitives, it contains only letters. For non-primitives, it contains either `"`, or a space, or a digit. Two exceptions remain: `\tex_undefined:D`, which is not a primitive, and `\nullfont`, which is a primitive.

Spaces cannot be grabbed in an undelimited way, so we check them separately. If there is a space, we test for `\nullfont`. Otherwise, we go through characters one by one, and stop at the first character less than ‘A’ (this is not quite a test for “only letters”, but is close enough to work in this context). If this first character is `:` then we have a primitive, or `\tex_undefined:D`, and if it is `"` or a digit, then the token is not a primitive.

```

6937 \tex_chardef:D \c__token_A_int = 'A ~ %
6938 \use:x
6939 {
6940   \prg_new_conditional:Npnn \exp_not:N \token_if_primitive:N ##1
6941   { p , T , F , TF }
6942   {
6943     \exp_not:N \token_if_macro:NTF ##1
6944     \exp_not:N \prg_return_false:
6945     {
6946       \exp_not:N \exp_after:wN \exp_not:N \__token_if_primitive:NNw
6947       \exp_not:N \token_to_meaning:N ##1
6948       \tl_to_str:n { : : : } \exp_not:N \q_stop ##1
6949     }
6950   }
6951   \cs_new:Npn \exp_not:N \__token_if_primitive:NNw
6952   ##1##2 ##3 \c_colon_str ##4 \exp_not:N \q_stop
6953   {
6954     \exp_not:N \tl_if_empty:oTF
6955     { \exp_not:N \__token_if_primitive_space:w ##3 ~ }
6956     {
6957       \exp_not:N \__token_if_primitive_loop:N ##3
6958       \c_colon_str \exp_not:N \q_stop
6959     }
6960     { \exp_not:N \__token_if_primitive_nullfont:N }
6961   }
6962 }
```

```

6963 \cs_new:Npn \__token_if_primitive_space:w #1 ~ { }
6964 \cs_new:Npn \__token_if_primitive_nullfont:N #1
6965 {
6966   \if_meaning:w \tex_nullfont:D #1
6967   \prg_return_true:
6968   \else:
6969   \prg_return_false:
6970   \fi:
6971 }
6972 \cs_new:Npn \__token_if_primitive_loop:N #1
6973 {
6974   \if_int_compare:w '#1 < \c__token_A_int %
6975   \exp_after:wN \__token_if_primitive:Nw
6976   \exp_after:wN #1
6977   \else:
6978   \exp_after:wN \__token_if_primitive_loop:N
6979   \fi:
6980 }
6981 \cs_new:Npn \__token_if_primitive:Nw #1 #2 \q_stop
6982 {
6983   \if:w : #1
6984   \exp_after:wN \__token_if_primitive_undefined:N
6985   \else:
6986   \prg_return_false:
6987   \exp_after:wN \use_none:n
6988   \fi:
6989 }
6990 \cs_new:Npn \__token_if_primitive_undefined:N #1
6991 {
6992   \if_cs_exist:N #1
6993   \prg_return_true:
6994   \else:
6995   \prg_return_false:
6996   \fi:
6997 }

```

(End definition for `\token_if_primitive:NTF` and others. These functions are documented on page [113](#).)

13.5 Peeking ahead at the next token

```

6998 <@@=peek>

```

Peeking ahead is implemented using a two part mechanism. The outer level provides a defined interface to the lower level material. This allows a large amount of code to be shared. There are four cases:

1. peek at the next token;
2. peek at the next non-space token;
3. peek at the next token and remove it;
4. peek at the next non-space token and remove it.

`\l_peek_token` Storage tokens which are publicly documented: the token peeked.
`\g_peek_token`

```
6999 \cs_new_eq:NN \l_peek_token ?
7000 \cs_new_eq:NN \g_peek_token ?
```

(End definition for `\l_peek_token` and `\g_peek_token`. These variables are documented on page 114.)

`\l__peek_search_token` The token to search for as an implicit token: cf. `\l__peek_search_tl`.

```
7001 \cs_new_eq:NN \l__peek_search_token ?
```

(End definition for `\l__peek_search_token`.)

`\l__peek_search_tl` The token to search for as an explicit token: cf. `\l__peek_search_token`.

```
7002 \tl_new:N \l__peek_search_tl
```

(End definition for `\l__peek_search_tl`.)

`__peek_true:w` Functions used by the branching and space-stripping code.

```
\__peek_true_aux:w 7003 \cs_new:Npn \__peek_true:w { }
\__peek_false:w     7004 \cs_new:Npn \__peek_true_aux:w { }
\__peek_tmp:w       7005 \cs_new:Npn \__peek_false:w { }
                    7006 \cs_new:Npn \__peek_tmp:w { }
```

(End definition for `__peek_true:w` and others.)

`\peek_after:Nw` Simple wrappers for `\futurelet`: no arguments absorbed here.

```
\peek_gafter:Nw 7007 \cs_new_protected:Npn \peek_after:Nw
                 7008 { \tex_futurelet:D \l_peek_token }
                 7009 \cs_new_protected:Npn \peek_gafter:Nw
                 7010 { \tex_global:D \tex_futurelet:D \g_peek_token }
```

(End definition for `\peek_after:Nw` and `\peek_gafter:Nw`. These functions are documented on page 113.)

`__peek_true_remove:w` A function to remove the next token and then regain control.

```
7011 \cs_new_protected:Npn \__peek_true_remove:w
7012 {
7013   \group_align_safe_end:
7014   \tex_afterassignment:D \__peek_true_aux:w
7015   \cs_set_eq:NN \__peek_tmp:w
7016 }
```

(End definition for `__peek_true_remove:w`.)

`__peek_token_generic:NNTF` The generic function stores the test token in both implicit and explicit modes, and the `true` and `false` code as token lists, more or less. The two branches have to be absorbed here as the input stream needs to be cleared for the peek function itself.

```
7017 \cs_new_protected:Npn \__peek_token_generic:NNTF #1#2#3#4
7018 {
7019   \cs_set_eq:NN \l__peek_search_token #2
7020   \tl_set:Nn \l__peek_search_tl {#2}
7021   \cs_set:Npx \__peek_true:w
7022   {
7023     \exp_not:N \group_align_safe_end:
7024     \exp_not:n {#3}
7025   }
7026   \cs_set:Npx \__peek_false:w
```

```

7027     {
7028         \exp_not:N \group_align_safe_end:
7029         \exp_not:n {#4}
7030     }
7031     \group_align_safe_begin:
7032     \peek_after:Nw #1
7033 }
7034 \cs_new_protected:Npn \__peek_token_generic:NNT #1#2#3
7035 { \__peek_token_generic:NNTF #1 #2 {#3} { } }
7036 \cs_new_protected:Npn \__peek_token_generic:NNF #1#2#3
7037 { \__peek_token_generic:NNTF #1 #2 { } {#3} }

```

(End definition for __peek_token_generic:NNTF.)

__peek_token_remove_generic:NNTF For token removal there needs to be a call to the auxiliary function which does the work.

```

7038 \cs_new_protected:Npn \__peek_token_remove_generic:NNTF #1#2#3#4
7039 {
7040     \cs_set_eq:NN \l__peek_search_token #2
7041     \tl_set:Nn \l__peek_search_tl {#2}
7042     \cs_set_eq:NN \__peek_true:w \__peek_true_remove:w
7043     \cs_set:Npx \__peek_true_aux:w { \exp_not:n {#3} }
7044     \cs_set:Npx \__peek_false:w
7045     {
7046         \exp_not:N \group_align_safe_end:
7047         \exp_not:n {#4}
7048     }
7049     \group_align_safe_begin:
7050     \peek_after:Nw #1
7051 }
7052 \cs_new_protected:Npn \__peek_token_remove_generic:NNT #1#2#3
7053 { \__peek_token_remove_generic:NNTF #1 #2 {#3} { } }
7054 \cs_new_protected:Npn \__peek_token_remove_generic:NNF #1#2#3
7055 { \__peek_token_remove_generic:NNTF #1 #2 { } {#3} }

```

(End definition for __peek_token_remove_generic:NNTF.)

__peek_execute_branches_meaning: The meaning test is straight forward.

```

7056 \cs_new:Npn \__peek_execute_branches_meaning:
7057 {
7058     \if_meaning:w \l__peek_token \l__peek_search_token
7059     \exp_after:wN \__peek_true:w
7060     \else:
7061     \exp_after:wN \__peek_false:w
7062     \fi:
7063 }

```

(End definition for __peek_execute_branches_meaning:.)

__peek_execute_branches_catcode: The catcode and charcode tests are very similar, and in order to use the same auxiliaries we do something a little bit odd, firing \if_catcode:w and \if_charcode:w before finding the operands for those tests, which will only be given in the auxii:N and auxiii:N auxiliaries. For our purposes, three kinds of tokens may follow the peeking function:

- control sequences which are not equal to a non-active character token (*e.g.*, macro, primitive);

- active characters which are not equal to a non-active character token (*e.g.*, macro, primitive);
- explicit non-active character tokens, or control sequences or active characters set equal to a non-active character token.

The first two cases are not distinguishable simply using \TeX 's `\futurelet`, because we can only access the `\meaning` of tokens in that way. In those cases, detected thanks to a comparison with `\scan_stop:`, we grab the following token, and compare it explicitly with the explicit search token stored in `\l_peek_search_tl`. The `\exp_not:N` prevents outer macros (coming from non- \LaTeX 3 code) from blowing up. In the third case, `\l_peek_token` is good enough for the test, and we compare it again with the explicit search token. Just like the peek token, the search token may be of any of the three types above, hence the need to use the explicit token that was given to the peek function.

```

7064 \cs_new:Npn \__peek_execute_branches_catcode:
7065 { \if_catcode:w \__peek_execute_branches_catcode_aux: }
7066 \cs_new:Npn \__peek_execute_branches_charcode:
7067 { \if_charcode:w \__peek_execute_branches_catcode_aux: }
7068 \cs_new:Npn \__peek_execute_branches_catcode_aux:
7069 {
7070     \if_catcode:w \exp_not:N \l_peek_token \scan_stop:
7071         \exp_after:wN \exp_after:wN
7072         \exp_after:wN \__peek_execute_branches_catcode_auxii:N
7073         \exp_after:wN \exp_not:N
7074     \else:
7075         \exp_after:wN \__peek_execute_branches_catcode_auxiii:
7076     \fi:
7077 }
7078 \cs_new:Npn \__peek_execute_branches_catcode_auxii:N #1
7079 {
7080     \exp_not:N #1
7081     \exp_after:wN \exp_not:N \l_peek_search_tl
7082     \exp_after:wN \__peek_true:w
7083 \else:
7084     \exp_after:wN \__peek_false:w
7085 \fi:
7086 #1
7087 }
7088 \cs_new:Npn \__peek_execute_branches_catcode_auxiii:
7089 {
7090     \exp_not:N \l_peek_token
7091     \exp_after:wN \exp_not:N \l_peek_search_tl
7092     \exp_after:wN \__peek_true:w
7093 \else:
7094     \exp_after:wN \__peek_false:w
7095 \fi:
7096 }
```

(End definition for `__peek_execute_branches_catcode:` and others.)

`__peek_ignore_spaces_execute_branches:` This function removes one space token at a time, and calls `__peek_execute_branches:` when encountering the first non-space token. We directly use the primitive meaning test rather than `\token_if_eq_meaning:NNTF` because `\l_peek_token` may be an outer

macro (coming from non-L^AT_EX3 packages). Spaces are removed using a side-effect of f-expansion: `\exp:w \exp_end_continue_f:w` removes one space.

```

7097 \cs_new_protected:Npn \__peek_ignore_spaces_execute_branches:
7098 {
7099   \if_meaning:w \l_peek_token \c_space_token
7100   \exp_after:wN \peek_after:Nw
7101   \exp_after:wN \__peek_ignore_spaces_execute_branches:
7102   \exp:w \exp_end_continue_f:w
7103   \else:
7104   \exp_after:wN \__peek_execute_branches:
7105   \fi:
7106 }

```

(End definition for `__peek_ignore_spaces_execute_branches:.`)

`__peek_def:nnnn` The public functions themselves cannot be defined using `\prg_new_conditional:Npnn` and so a couple of auxiliary functions are used. As a result, everything is done inside a group. As a result things are a bit complicated.

```

7107 \group_begin:
7108   \cs_set:Npn \__peek_def:nnnn #1#2#3#4
7109   {
7110     \__peek_def:nnnnn {#1} {#2} {#3} {#4} { TF }
7111     \__peek_def:nnnnn {#1} {#2} {#3} {#4} { T }
7112     \__peek_def:nnnnn {#1} {#2} {#3} {#4} { F }
7113   }
7114   \cs_set:Npn \__peek_def:nnnnn #1#2#3#4#5
7115   {
7116     \cs_new_protected:cpx { #1 #5 }
7117     {
7118       \tl_if_empty:nF {#2}
7119       { \exp_not:n { \cs_set_eq:NN \__peek_execute_branches: #2 } }
7120       \exp_not:c { #3 #5 }
7121       \exp_not:n {#4}
7122     }
7123   }

```

(End definition for `__peek_def:nnnn` and `__peek_def:nnnnn`.)

`\peek_catcode:NTF` With everything in place the definitions can take place. First for category codes.
`\peek_catcode_ignore_spaces:NTF`
`\peek_catcode_remove:NTF`
`\peek_catcode_remove_ignore_spaces:NTF`

```

7124 \__peek_def:nnnn { peek_catcode:N }
7125 { }
7126 { __peek_token_generic:NN }
7127 { \__peek_execute_branches_catcode: }
7128 \__peek_def:nnnn { peek_catcode_ignore_spaces:N }
7129 { \__peek_execute_branches_catcode: }
7130 { __peek_token_generic:NN }
7131 { \__peek_ignore_spaces_execute_branches: }
7132 \__peek_def:nnnn { peek_catcode_remove:N }
7133 { }
7134 { __peek_token_remove_generic:NN }
7135 { \__peek_execute_branches_catcode: }
7136 \__peek_def:nnnn { peek_catcode_remove_ignore_spaces:N }
7137 { \__peek_execute_branches_catcode: }
7138 { __peek_token_remove_generic:NN }
7139 { \__peek_ignore_spaces_execute_branches: }

```

(End definition for `\peek_catcode:NTF` and others. These functions are documented on page 114.)

`\peek_charcode:NTF` Then for character codes.

```

7140 \__peek_def:nnnn { peek_charcode:N }
7141 { }
7142 { __peek_token_generic:NN }
7143 { \__peek_execute_branches_charcode: }
7144 \__peek_def:nnnn { peek_charcode_ignore_spaces:N }
7145 { \__peek_execute_branches_charcode: }
7146 { __peek_token_generic:NN }
7147 { \__peek_ignore_spaces_execute_branches: }
7148 \__peek_def:nnnn { peek_charcode_remove:N }
7149 { }
7150 { __peek_token_remove_generic:NN }
7151 { \__peek_execute_branches_charcode: }
7152 \__peek_def:nnnn { peek_charcode_remove_ignore_spaces:N }
7153 { \__peek_execute_branches_charcode: }
7154 { __peek_token_remove_generic:NN }
7155 { \__peek_ignore_spaces_execute_branches: }

```

(End definition for `\peek_charcode:NTF` and others. These functions are documented on page 114.)

`\peek_meaning:NTF` Finally for meaning, with the group closed to remove the temporary definition functions.

```

7156 \__peek_def:nnnn { peek_meaning:N }
7157 { }
7158 { __peek_token_generic:NN }
7159 { \__peek_execute_branches_meaning: }
7160 \__peek_def:nnnn { peek_meaning_ignore_spaces:N }
7161 { \__peek_execute_branches_meaning: }
7162 { __peek_token_generic:NN }
7163 { \__peek_ignore_spaces_execute_branches: }
7164 \__peek_def:nnnn { peek_meaning_remove:N }
7165 { }
7166 { __peek_token_remove_generic:NN }
7167 { \__peek_execute_branches_meaning: }
7168 \__peek_def:nnnn { peek_meaning_remove_ignore_spaces:N }
7169 { \__peek_execute_branches_meaning: }
7170 { __peek_token_remove_generic:NN }
7171 { \__peek_ignore_spaces_execute_branches: }
7172 \group_end:

```

(End definition for `\peek_meaning:NTF` and others. These functions are documented on page 115.)

13.6 Decomposing a macro definition

`\token_get_prefix_spec:N` We sometimes want to test if a control sequence can be expanded to reveal a hidden value.
`\token_get_arg_spec:N` However, we cannot just expand the macro blindly as it may have arguments and none
`\token_get_replacement_spec:N` might be present. Therefore we define these functions to pick either the prefix(es), the
`__peek_get_prefix_arg_replacement:wN` argument specification, or the replacement text from a macro. All of this information is
returned as characters with catcode 12. If the token in question isn't a macro, the token
`\scan_stop:` is returned instead.

```

7173 \exp_args:Nno \use:nn
7174 { \cs_new:Npn \__peek_get_prefix_arg_replacement:wN #1 }
7175 { \tl_to_str:n { macro : } #2 -> #3 \q_stop #4 }

```



```

7176 { #4 {#1} {#2} {#3} }
7177 \cs_new:Npn \token_get_prefix_spec:N #1
7178 {
7179   \token_if_macro:NTF #1
7180   {
7181     \exp_after:wN \__peek_get_prefix_arg_replacement:wN
7182     \token_to_meaning:N #1 \q_stop \use_i:nnn
7183   }
7184   { \scan_stop: }
7185 }
7186 \cs_new:Npn \token_get_arg_spec:N #1
7187 {
7188   \token_if_macro:NTF #1
7189   {
7190     \exp_after:wN \__peek_get_prefix_arg_replacement:wN
7191     \token_to_meaning:N #1 \q_stop \use_ii:nnn
7192   }
7193   { \scan_stop: }
7194 }
7195 \cs_new:Npn \token_get_replacement_spec:N #1
7196 {
7197   \token_if_macro:NTF #1
7198   {
7199     \exp_after:wN \__peek_get_prefix_arg_replacement:wN
7200     \token_to_meaning:N #1 \q_stop \use_iii:nnn
7201   }
7202   { \scan_stop: }
7203 }

```

(End definition for `\token_get_prefix_spec:N` and others. These functions are documented on page 117.)

```

7204 </initex | package>

```

14 l3prop implementation

The following test files are used for this code: `m3prop001`, `m3prop002`, `m3prop003`, `m3prop004`, `m3show001`.

```

7205 <*initex | package>
7206 <@@=prop>

```

A property list is a macro whose top-level expansion is of the form

```

\__prop \__prop_pair:wn <key1> \s__prop {<value1>}
...
\__prop_pair:wn <keyn> \s__prop {<valuen>}

```

where `\s__prop` is a scan mark (equal to `\scan_stop:`), and `__prop_pair:wn` can be used to map through the property list.

\s__prop A private scan mark is used as a marker after each key, and at the very beginning of the property list.

```

7207 \__scan_new:N \s__prop

```

(End definition for `\s__prop`.)

`__prop_pair:wn` The delimiter is always defined, but when misused simply triggers an error and removes its argument.

```
7208 \cs_new:Npn \__prop_pair:wn #1 \s__prop #2
7209 { \__msg_kernel_expandable_error:nn { kernel } { misused-prop } }
```

(End definition for `__prop_pair:wn`.)

`\l__prop_internal_tl` Token list used to store the new key-value pair inserted by `\prop_put:Nnn` and friends.

```
7210 \tl_new:N \l__prop_internal_tl
```

(End definition for `\l__prop_internal_tl`.)

`\c_empty_prop` An empty prop.

```
7211 \tl_const:Nn \c_empty_prop { \s__prop }
```

(End definition for `\c_empty_prop`. This variable is documented on page 125.)

14.1 Allocation and initialisation

`\prop_new:N` Property lists are initialized with the value `\c_empty_prop`.

```
\prop_new:c
7212 \cs_new_protected:Npn \prop_new:N #1
7213 {
7214   \__chk_if_free_cs:N #1
7215   \cs_gset_eq:NN #1 \c_empty_prop
7216 }
7217 \cs_generate_variant:Nn \prop_new:N { c }
```

(End definition for `\prop_new:N`. This function is documented on page 120.)

`\prop_clear:N` The same idea for clearing.

```
\prop_clear:c
\prop_gclear:N
\prop_gclear:c
7218 \cs_new_protected:Npn \prop_clear:N #1
7219 { \prop_set_eq:NN #1 \c_empty_prop }
7220 \cs_generate_variant:Nn \prop_clear:N { c }
7221 \cs_new_protected:Npn \prop_gclear:N #1
7222 { \prop_gset_eq:NN #1 \c_empty_prop }
7223 \cs_generate_variant:Nn \prop_gclear:N { c }
```

(End definition for `\prop_clear:N` and `\prop_gclear:N`. These functions are documented on page 120.)

`\prop_clear_new:N` Once again a simple variation of the token list functions.

```
\prop_clear_new:c
\prop_gclear_new:N
\prop_gclear_new:c
7224 \cs_new_protected:Npn \prop_clear_new:N #1
7225 { \prop_if_exist:NTF #1 { \prop_clear:N #1 } { \prop_new:N #1 } }
7226 \cs_generate_variant:Nn \prop_clear_new:N { c }
7227 \cs_new_protected:Npn \prop_gclear_new:N #1
7228 { \prop_if_exist:NTF #1 { \prop_gclear:N #1 } { \prop_new:N #1 } }
7229 \cs_generate_variant:Nn \prop_gclear_new:N { c }
```

(End definition for `\prop_clear_new:N` and `\prop_gclear_new:N`. These functions are documented on page 120.)

```

\prop_set_eq:NN These are simply copies from the token list functions.
\prop_set_eq:cN 7230 \cs_new_eq:NN \prop_set_eq:NN \tl_set_eq:NN
\prop_set_eq:Nc 7231 \cs_new_eq:NN \prop_set_eq:Nc \tl_set_eq:Nc
\prop_set_eq:cc 7232 \cs_new_eq:NN \prop_set_eq:cN \tl_set_eq:cN
\prop_gset_eq:NN 7233 \cs_new_eq:NN \prop_set_eq:cc \tl_set_eq:cc
\prop_gset_eq:cN 7234 \cs_new_eq:NN \prop_gset_eq:NN \tl_gset_eq:NN
\prop_gset_eq:Nc 7235 \cs_new_eq:NN \prop_gset_eq:Nc \tl_gset_eq:Nc
\prop_gset_eq:cN 7236 \cs_new_eq:NN \prop_gset_eq:cN \tl_gset_eq:cN
\prop_gset_eq:cc 7237 \cs_new_eq:NN \prop_gset_eq:cc \tl_gset_eq:cc

```

(End definition for `\prop_set_eq:NN` and `\prop_gset_eq:NN`. These functions are documented on page 120.)

```

\l_tmpa_prop We can now initialize the scratch variables.
\l_tmpb_prop
\g_tmpa_prop 7238 \prop_new:N \l_tmpa_prop
\g_tmpb_prop 7239 \prop_new:N \l_tmpb_prop
\g_tmpa_prop 7240 \prop_new:N \g_tmpa_prop
\g_tmpb_prop 7241 \prop_new:N \g_tmpb_prop

```

(End definition for `\l_tmpa_prop` and others. These variables are documented on page 125.)

14.2 Accessing data in property lists

`__prop_split:NnTF` This function is used by most of the module, and hence must be fast. It receives a *property list*, a *key*, a *true code* and a *false code*. The aim is to split the *property list* at the given *key* into the *extract₁* before the key–value pair, the *value* associated with the *key* and the *extract₂* after the key–value pair. This is done using a delimited function, whose definition is as follows, where the *key* is turned into a string.

```

\cs_set:Npn \__prop_split_aux:w #1
\__prop_pair:wn <key> \s__prop #2
#3 \q_mark #4 #5 \q_stop
{ #4 {<true code>} {<false code>} }

```

If the *key* is present in the property list, `__prop_split_aux:w`'s #1 is the part before the *key*, #2 is the *value*, #3 is the part after the *key*, #4 is `\use_i:nn`, and #5 is additional tokens that we do not care about. The *true code* is left in the input stream, and can use the parameters #1, #2, #3 for the three parts of the property list as desired. Namely, the original property list is in this case #1 `__prop_pair:wn <key> \s__prop {#2} #3`.

If the *key* is not there, then the *function* is `\use_ii:nn`, which keeps the *false code*.

```

7242 \cs_new_protected:Npn \__prop_split:NnTF #1#2
7243 { \exp_args:NNo \__prop_split_aux:NnTF #1 { \tl_to_str:n {#2} } }
7244 \cs_new_protected:Npn \__prop_split_aux:NnTF #1#2#3#4
7245 {
7246   \cs_set:Npn \__prop_split_aux:w ##1
7247     \__prop_pair:wn #2 \s__prop ##2 ##3 \q_mark ##4 ##5 \q_stop
7248     { ##4 {#3} {#4} }
7249   \exp_after:wN \__prop_split_aux:w #1 \q_mark \use_i:nn
7250   \__prop_pair:wn #2 \s__prop { } \q_mark \use_ii:nn \q_stop
7251 }
7252 \cs_new:Npn \__prop_split_aux:w { }

```

(End definition for `_prop_split:NnTF`, `_prop_split_aux:NnTF`, and `_prop_split_aux:w`.)

`\prop_remove:Nn` Deleting from a property starts by splitting the list. If the key is present in the property list, the returned value is ignored. If the key is missing, nothing happens.

`\prop_remove:NV`

`\prop_remove:cn` 7253 `\cs_new_protected:Npn \prop_remove:Nn #1#2`

`\prop_remove:cV` 7254 `{`

`\prop_gremove:Nn` 7255 `_prop_split:NnTF #1 {#2}`

`\prop_gremove:NV` 7256 `{ \tl_set:Nn #1 { ##1 ##3 } }`

`\prop_gremove:cn` 7257 `{ }`

`\prop_gremove:cV` 7258 `}`

7259 `\cs_new_protected:Npn \prop_gremove:Nn #1#2`

7260 `{`

7261 `_prop_split:NnTF #1 {#2}`

7262 `{ \tl_gset:Nn #1 { ##1 ##3 } }`

7263 `{ }`

7264 `}`

7265 `\cs_generate_variant:Nn \prop_remove:Nn { NV }`

7266 `\cs_generate_variant:Nn \prop_remove:Nn { c , cV }`

7267 `\cs_generate_variant:Nn \prop_gremove:Nn { NV }`

7268 `\cs_generate_variant:Nn \prop_gremove:Nn { c , cV }`

(End definition for `\prop_remove:Nn` and `\prop_gremove:Nn`. These functions are documented on page 122.)

`\prop_get:NnN` Getting an item from a list is very easy: after splitting, if the key is in the property list, just set the token list variable to the return value, otherwise to `\q_no_value`.

`\prop_get:NVN`

`\prop_get:NoN` 7269 `\cs_new_protected:Npn \prop_get:NnN #1#2#3`

`\prop_get:cnN` 7270 `{`

`\prop_get:cVN` 7271 `_prop_split:NnTF #1 {#2}`

`\prop_get:coN` 7272 `{ \tl_set:Nn #3 {##2} }`

7273 `{ \tl_set:Nn #3 { \q_no_value } }`

7274 `}`

7275 `\cs_generate_variant:Nn \prop_get:NnN { NV , No }`

7276 `\cs_generate_variant:Nn \prop_get:NnN { c , cV , co }`

(End definition for `\prop_get:NnN`. This function is documented on page 121.)

`\prop_pop:NnN` Popping a value also starts by doing the split. If the key is present, save the value in the token list and update the property list as when deleting. If the key is missing, save `\q_no_value` in the token list.

`\prop_pop:NoN`

`\prop_pop:cnN`

`\prop_pop:coN` 7277 `\cs_new_protected:Npn \prop_pop:NnN #1#2#3`

`\prop_gpop:NnN` 7278 `{`

`\prop_gpop:NoN` 7279 `_prop_split:NnTF #1 {#2}`

`\prop_gpop:cnN` 7280 `{`

`\prop_gpop:coN` 7281 `\tl_set:Nn #3 {##2}`

7282 `\tl_set:Nn #1 { ##1 ##3 }`

7283 `}`

7284 `{ \tl_set:Nn #3 { \q_no_value } }`

7285 `}`

7286 `\cs_new_protected:Npn \prop_gpop:NnN #1#2#3`

7287 `{`

7288 `_prop_split:NnTF #1 {#2}`

7289 `{`

7290 `\tl_set:Nn #3 {##2}`

```

7291         \tl_gset:Nn #1 { ##1 ##3 }
7292     }
7293     { \tl_set:Nn #3 { \q_no_value } }
7294 }
7295 \cs_generate_variant:Nn \prop_pop:NnN { No }
7296 \cs_generate_variant:Nn \prop_pop:NnN { c , co }
7297 \cs_generate_variant:Nn \prop_gpop:NnN { No }
7298 \cs_generate_variant:Nn \prop_gpop:NnN { c , co }

```

(End definition for `\prop_pop:NnN` and `\prop_gpop:NnN`. These functions are documented on page 121.)

`\prop_item:Nn` Getting the value corresponding to a key in a property list in an expandable fashion is similar to mapping some tokens. Go through the property list one $\langle key \rangle$ – $\langle value \rangle$ pair at a time: the arguments of `__prop_item_Nn:nwn` are the $\langle key \rangle$ we are looking for, a $\langle key \rangle$ of the property list, and its associated value. The $\langle keys \rangle$ are compared (as strings). If they match, the $\langle value \rangle$ is returned, within `\exp_not:n`. The loop terminates even if the $\langle key \rangle$ is missing, and yields an empty value, because we have appended the appropriate $\langle key \rangle$ – $\langle empty\ value \rangle$ pair to the property list.

```

7299 \cs_new:Npn \prop_item:Nn #1#2
7300 {
7301     \exp_last_unbraced:Noo \__prop_item_Nn:nwn { \tl_to_str:n {#2} } #1
7302     \__prop_pair:wn \tl_to_str:n {#2} \s__prop { }
7303     \__prg_break_point:
7304 }
7305 \cs_new:Npn \__prop_item_Nn:nwn #1#2 \__prop_pair:wn #3 \s__prop #4
7306 {
7307     \str_if_eq_x:nnTF {#1} {#3}
7308     { \__prg_break:n { \exp_not:n {#4} } }
7309     { \__prop_item_Nn:nwn {#1} }
7310 }
7311 \cs_generate_variant:Nn \prop_item:Nn { c }

```

(End definition for `\prop_item:Nn` and `__prop_item_Nn:nwn`. These functions are documented on page 122.)

`\prop_pop:NnNTF` Popping an item from a property list, keeping track of whether the key was present or not, is implemented as a conditional. If the key was missing, neither the property list, nor the token list are altered. Otherwise, `\prg_return_true:` is used after the assignments.

```

\prop_gpop:NnNTF
7312 \prg_new_protected_conditional:Npnn \prop_pop:NnN #1#2#3 { T , F , TF }
7313 {
7314     \__prop_split:NnTF #1 {#2}
7315     {
7316         \tl_set:Nn #3 {##2}
7317         \tl_set:Nn #1 { ##1 ##3 }
7318         \prg_return_true:
7319     }
7320     { \prg_return_false: }
7321 }
7322 \prg_new_protected_conditional:Npnn \prop_gpop:NnN #1#2#3 { T , F , TF }
7323 {
7324     \__prop_split:NnTF #1 {#2}
7325     {
7326         \tl_set:Nn #3 {##2}
7327         \tl_gset:Nn #1 { ##1 ##3 }

```

```

7328     \prg_return_true:
7329     }
7330     { \prg_return_false: }
7331 }
7332 \cs_generate_variant:Nn \prop_pop:NnNT { c }
7333 \cs_generate_variant:Nn \prop_pop:NnNF { c }
7334 \cs_generate_variant:Nn \prop_pop:NnNTF { c }
7335 \cs_generate_variant:Nn \prop_gpop:NnNT { c }
7336 \cs_generate_variant:Nn \prop_gpop:NnNF { c }
7337 \cs_generate_variant:Nn \prop_gpop:NnNTF { c }

```

(End definition for `\prop_pop:NnNTF` and `\prop_gpop:NnNTF`. These functions are documented on page 123.)

\prop_put:Nnn Since the branches of `__prop_split:NnTF` are used as the replacement text of an internal macro, and since the *<key>* and new *<value>* may contain arbitrary tokens, it is not safe to include them in the argument of `__prop_split:NnTF`. We thus start by storing in `\l__prop_internal_tl` tokens which (after x-expansion) encode the key–value pair. This variable can safely be used in `__prop_split:NnTF`. If the *<key>* was absent, append the new key–value to the list. Otherwise concatenate the extracts **##1** and **##3** with the new key–value pair `\l__prop_internal_tl`. The updated entry is placed at the same spot as the original *<key>* in the property list, preserving the order of entries.

```

7338 \cs_new_protected:Npn \prop_put:Nnn { \__prop_put:NNnn \tl_set:Nx }
7339 \cs_new_protected:Npn \prop_gput:Nnn { \__prop_put:NNnn \tl_gset:Nx }
7340 \cs_new_protected:Npn \__prop_put:NNnn #1#2#3#4
7341 {
7342     \tl_set:Nn \l__prop_internal_tl
7343     {
7344         \exp_not:N \__prop_pair:wn \tl_to_str:n {#3}
7345         \s__prop { \exp_not:n {#4} }
7346     }
7347     \__prop_split:NnTF #2 {#3}
7348     { #1 #2 { \exp_not:n {##1} \l__prop_internal_tl \exp_not:n {##3} } }
7349     { #1 #2 { \exp_not:o {#2} \l__prop_internal_tl } }
7350 }
7351 \cs_generate_variant:Nn \prop_put:Nnn
7352 { NnV , Nno , Nnx , NV , NVV , No , Noo }
7353 \cs_generate_variant:Nn \prop_put:Nnn
7354 { c , cnV , cno , cnx , cV , cVV , co , coo }
7355 \cs_generate_variant:Nn \prop_gput:Nnn
7356 { NnV , Nno , Nnx , NV , NVV , No , Noo }
7357 \cs_generate_variant:Nn \prop_gput:Nnn
7358 { c , cnV , cno , cnx , cV , cVV , co , coo }

```

(End definition for `\prop_put:Nnn`, `\prop_gput:Nnn`, and `__prop_put:NNnn`. These functions are documented on page 121.)

\prop_put_if_new:Nnn Adding conditionally also splits. If the key is already present, the three brace groups given by `__prop_split:NnTF` are removed. If the key is new, then the value is added, being careful to convert the key to a string using `\tl_to_str:n`.

```

7359 \cs_new_protected:Npn \prop_put_if_new:Nnn
7360 { \__prop_put_if_new:NNnn \tl_set:Nx }
7361 \cs_new_protected:Npn \prop_gput_if_new:Nnn
7362 { \__prop_put_if_new:NNnn \tl_gset:Nx }

```

```

7363 \cs_new_protected:Npn \__prop_put_if_new:NNnn #1#2#3#4
7364 {
7365   \tl_set:Nn \l__prop_internal_tl
7366   {
7367     \exp_not:N \__prop_pair:wn \tl_to_str:n {#3}
7368     \s__prop \exp_not:n { {#4} }
7369   }
7370   \__prop_split:NnTF #2 {#3}
7371   { }
7372   { #1 #2 { \exp_not:o {#2} \l__prop_internal_tl } }
7373 }
7374 \cs_generate_variant:Nn \prop_put_if_new:Nnn { c }
7375 \cs_generate_variant:Nn \prop_gput_if_new:Nnn { c }

```

(End definition for `\prop_put_if_new:Nnn`, `\prop_gput_if_new:Nnn`, and `__prop_put_if_new:NNnn`. These functions are documented on page 121.)

14.3 Property list conditionals

`\prop_if_exist_p:N` Copies of the `cs` functions defined in `l3basics`.
`\prop_if_exist_p:c` 7376 \prg_new_eq_conditional:NNn \prop_if_exist:N \cs_if_exist:N
`\prop_if_exist:NTF` 7377 { TF , T , F , p }
`\prop_if_exist:cTF` 7378 \prg_new_eq_conditional:NNn \prop_if_exist:c \cs_if_exist:c
7379 { TF , T , F , p }

(End definition for `\prop_if_exist:NTF`. This function is documented on page 122.)

`\prop_if_empty_p:N` Same test as for token lists.
`\prop_if_empty_p:c` 7380 \prg_new_conditional:Npnn \prop_if_empty:N #1 { p , T , F , TF }
`\prop_if_empty:NTF` 7381 {
`\prop_if_empty:cTF` 7382 \tl_if_eq:NNTF #1 \c_empty_prop
7383 \prg_return_true: \prg_return_false:
7384 }
7385 \cs_generate_variant:Nn \prop_if_empty_p:N { c }
7386 \cs_generate_variant:Nn \prop_if_empty:N { NT }
7387 \cs_generate_variant:Nn \prop_if_empty:N { NF }
7388 \cs_generate_variant:Nn \prop_if_empty:N { NTF }

(End definition for `\prop_if_empty:NTF`. This function is documented on page 122.)

`\prop_if_in_p:Nn` Testing expandably if a key is in a property list requires to go through the key–value
`\prop_if_in_p:Nv` pairs one by one. This is rather slow, and a faster test would be
`\prop_if_in_p:No` \prg_new_protected_conditional:Npnn \prop_if_in:Nn #1 #2
`\prop_if_in_p:cn` {
`\prop_if_in_p:cV` \@@_split:NnTF #1 {#2}
`\prop_if_in_p:co` { \prg_return_true: }
`\prop_if_in:NnTF` { \prg_return_false: }
`\prop_if_in:NvTF` }
`\prop_if_in:NoTF` }
`\prop_if_in:cnTF` but `__prop_split:NnTF` is non-expandable.
`\prop_if_in:cVTF` Instead, the key is compared to each key in turn using `\str_if_eq_x:nn`, which is
`\prop_if_in:coTF` expandable. To terminate the mapping, we append to the property list the key that is
`__prop_if_in:nwnn` searched for. This second `\tl_to_str:n` is not expanded at the start, but only when in-
`__prop_if_in:N` cluded in the `\str_if_eq_x:nn`. It cannot make the breaking mechanism choke, because

the arbitrary token list material is enclosed in braces. The second argument of `__prop_if_in:nwn` is most often empty. When the *key* is found in the list, `__prop_if_in:N` receives `__prop_pair:wn`, and if it is found as the extra item, the function receives `\q_recursion_tail`, easily recognizable.

Here, `\prop_map_function:NN` is not sufficient for the mapping, since it can only map a single token, and cannot carry the key that is searched for.

```

7389 \prg_new_conditional:Npnn \prop_if_in:Nn #1#2 { p , T , F , TF }
7390 {
7391   \exp_last_unbraced:Noo \__prop_if_in:nwn { \tl_to_str:n {#2} } #1
7392   \__prop_pair:wn \tl_to_str:n {#2} \s__prop { }
7393   \q_recursion_tail
7394   \__prg_break_point:
7395 }
7396 \cs_new:Npn \__prop_if_in:nwn #1#2 \__prop_pair:wn #3 \s__prop #4
7397 {
7398   \str_if_eq_x:nnTF {#1} {#3}
7399   { \__prop_if_in:N }
7400   { \__prop_if_in:nwn {#1} }
7401 }
7402 \cs_new:Npn \__prop_if_in:N #1
7403 {
7404   \if_meaning:w \q_recursion_tail #1
7405   \prg_return_false:
7406   \else:
7407     \prg_return_true:
7408   \fi:
7409   \__prg_break:
7410 }
7411 \cs_generate_variant:Nn \prop_if_in_p:Nn { NV , No }
7412 \cs_generate_variant:Nn \prop_if_in_p:Nn { c , cV , co }
7413 \cs_generate_variant:Nn \prop_if_in:NnT { NV , No }
7414 \cs_generate_variant:Nn \prop_if_in:NnT { c , cV , co }
7415 \cs_generate_variant:Nn \prop_if_in:NnF { NV , No }
7416 \cs_generate_variant:Nn \prop_if_in:NnF { c , cV , co }
7417 \cs_generate_variant:Nn \prop_if_in:NnTF { NV , No }
7418 \cs_generate_variant:Nn \prop_if_in:NnTF { c , cV , co }

```

(End definition for `\prop_if_in:NnTF`, `__prop_if_in:nwn`, and `__prop_if_in:N`. These functions are documented on page 122.)

14.4 Recovering values from property lists with branching

`\prop_get:NnTF` Getting the value corresponding to a key, keeping track of whether the key was present or not, is implemented as a conditional (with side effects). If the key was absent, the token list is not altered.

```

7419 \prg_new_protected_conditional:Npnn \prop_get:NnN #1#2#3 { T , F , TF }
7420 {
7421   \__prop_split:NnTF #1 {#2}
7422   {
7423     \tl_set:Nn #3 {##2}
7424     \prg_return_true:
7425   }
7426   { \prg_return_false: }

```



```

7427 }
7428 \cs_generate_variant:Nn \prop_get:NnNT { NV , No }
7429 \cs_generate_variant:Nn \prop_get:NnNF { NV , No }
7430 \cs_generate_variant:Nn \prop_get:NnNTF { NV , No }
7431 \cs_generate_variant:Nn \prop_get:NnNT { c , cV , co }
7432 \cs_generate_variant:Nn \prop_get:NnNF { c , cV , co }
7433 \cs_generate_variant:Nn \prop_get:NnNTF { c , cV , co }

```

(End definition for `\prop_get:NnNTF`. This function is documented on page 123.)

14.5 Mapping to property lists

`\prop_map_function:NN` The fastest way to do a recursion here is to use an `\if_meaning:w` test: the keys are strings, and thus cannot match the marker `\q_recursion_tail`. A special case to note is when the key #3 is empty: then `\q_recursion_tail` is compared to `\exp_after:wN`, also different. Note that #2 is empty, except at the first iteration, where it is `\s__prop`.

```

\prop_map_function:Nc
\prop_map_function:cN
\prop_map_function:cc
__prop_map_function:Nwwn
7434 \cs_new:Npn \prop_map_function:NN #1#2
7435 {
7436   \exp_last_unbraced:NNo __prop_map_function:Nwwn #2 #1
7437   __prop_pair:wn \q_recursion_tail \s__prop { }
7438   __prg_break_point:Nn \prop_map_break: { }
7439 }
7440 \cs_new:Npn __prop_map_function:Nwwn #1#2 __prop_pair:wn #3 \s__prop #4
7441 {
7442   \if_meaning:w \q_recursion_tail #3
7443   \exp_after:wN \prop_map_break:
7444   \fi:
7445   #1 {#3} {#4}
7446   __prop_map_function:Nwwn #1
7447 }
7448 \cs_generate_variant:Nn \prop_map_function:NN { Nc }
7449 \cs_generate_variant:Nn \prop_map_function:NN { c , cc }

```

(End definition for `\prop_map_function:NN` and `__prop_map_function:Nwwn`. These functions are documented on page 123.)

`\prop_map_inline:Nn` Mapping in line requires a nesting level counter. Store the current definition of `__prop_pair:wn`, and define it anew. At the end of the loop, revert to the earlier definition. Note that besides pairs of the form `__prop_pair:wn <key> \s__prop {<value>}`, there are a leading and a trailing tokens, but both are equal to `\scan_stop:`, hence have no effect in such inline mapping.

```

7450 \cs_new_protected:Npn \prop_map_inline:Nn #1#2
7451 {
7452   \cs_gset_eq:cN
7453   { __prg_map_ \int_use:N \g__prg_map_int :wn } __prop_pair:wn
7454   \int_gincr:N \g__prg_map_int
7455   \cs_gset:Npn __prop_pair:wn ##1 \s__prop ##2 {#2}
7456   #1
7457   __prg_break_point:Nn \prop_map_break:
7458   {
7459     \int_gdecr:N \g__prg_map_int
7460     \cs_gset_eq:Nc __prop_pair:wn
7461     { __prg_map_ \int_use:N \g__prg_map_int :wn }
7462   }

```

```

7463 }
7464 \cs_generate_variant:Nn \prop_map_inline:Nn { c }

```

(End definition for `\prop_map_inline:Nn`. This function is documented on page 123.)

`\prop_map_break:` The break statements are based on the general `__prg_map_break:Nn`.

```

\prop_map_break:n
7465 \cs_new:Npn \prop_map_break:
7466 { \__prg_map_break:Nn \prop_map_break: { } }
7467 \cs_new:Npn \prop_map_break:n
7468 { \__prg_map_break:Nn \prop_map_break: }

```

(End definition for `\prop_map_break:` and `\prop_map_break:n`. These functions are documented on page 124.)

14.6 Viewing property lists

`\prop_show:N` Apply the general `__msg_show_variable:NNNnn`. Contrarily to sequences and comma lists, we use `__msg_show_item:nn` to format both the key and the value for each pair.

```

\prop_show:c
7469 \cs_new_protected:Npn \prop_show:N #1
7470 {
7471   \__msg_show_variable:NNNnn #1
7472   \prop_if_exist:NTF \prop_if_empty:NTF { prop }
7473   { \prop_map_function:NN #1 \__msg_show_item:nn }
7474 }
7475 \cs_generate_variant:Nn \prop_show:N { c }

```

(End definition for `\prop_show:N`. This function is documented on page 124.)

`\prop_log:N` Redirect output of `\prop_show:N` to the log.

```

\prop_log:c
7476 \cs_new_protected:Npn \prop_log:N
7477 { \__msg_log_next: \prop_show:N }
7478 \cs_generate_variant:Nn \prop_log:N { c }

```

(End definition for `\prop_log:N`. This function is documented on page 124.)

```

7479 </initex | package>

```

15 l3msg implementation

```

7480 <*initex | package>

```

```

7481 <@@=msg>

```

`\l_msg_internal_tl` A general scratch for the module.

```

7482 \tl_new:N \l_msg_internal_tl

```

(End definition for `\l_msg_internal_tl`.)

`\l_msg_line_context_bool` Controls whether the line context is shown as part of the decoration of all (non-expandable) messages.

```

7483 \bool_new:N \l_msg_line_context_bool

```

(End definition for `\l_msg_line_context_bool`.)

15.1 Creating messages

Messages are created and used separately, so there two parts to the code here. First, a mechanism for creating message text. This is pretty simple, as there is not actually a lot to do.

```
\c__msg_text_prefix_tl Locations for the text of messages.
\c__msg_more_text_prefix_tl
7484 \tl_const:Nn \c__msg_text_prefix_tl { msg-text~>~ }
7485 \tl_const:Nn \c__msg_more_text_prefix_tl { msg-extra-text~>~ }

(End definition for \c__msg_text_prefix_tl and \c__msg_more_text_prefix_tl.)
```

```
\msg_if_exist_p:nn Test whether the control sequence containing the message text exists or not.
\msg_if_exist:nnTF
7486 \prg_new_conditional:Npnn \msg_if_exist:nn #1#2 { p , T , F , TF }
7487 {
7488   \cs_if_exist:cTF { \c__msg_text_prefix_tl #1 / #2 }
7489   { \prg_return_true: } { \prg_return_false: }
7490 }
```

(End definition for \msg_if_exist:nnTF. This function is documented on page 127.)

```
\__chk_if_free_msg:nn This auxiliary is similar to \__chk_if_free_cs:N, and is used when defining messages
with \msg_new:nnnn. It could be inlined in \msg_new:nnnn, but the experimental l3trace
module needs to disable this check when reloading a package with the extra tracing
information.
```

```
7491 \cs_new_protected:Npn \__chk_if_free_msg:nn #1#2
7492 {
7493   \msg_if_exist:nnT {#1} {#2}
7494   {
7495     \__msg_kernel_error:nxxx { kernel } { message-already-defined }
7496     {#1} {#2}
7497   }
7498 }
7499 <*package>
7500 \if_bool:N \l@expl@log@functions@bool
7501   \cs_gset_protected:Npn \__chk_if_free_msg:nn #1#2
7502   {
7503     \msg_if_exist:nnT {#1} {#2}
7504     {
7505       \__msg_kernel_error:nxxx { kernel } { message-already-defined }
7506       {#1} {#2}
7507     }
7508     \__chk_log:x { Defining~message~ #1 / #2 ~\msg_line_context: }
7509   }
7510 \fi:
7511 </package>
```

(End definition for __chk_if_free_msg:nn.)

```
\msg_new:nnnn Setting a message simply means saving the appropriate text into two functions. A sanity
\msg_new:nnn check first.
\msg_gset:nnnn
\msg_gset:nnn
\msg_set:nnnn
\msg_set:nnn
7512 \cs_new_protected:Npn \msg_new:nnnn #1#2
7513 {
7514   \__chk_if_free_msg:nn {#1} {#2}
```

```

7515 \msg_gset:nnnn {#1} {#2}
7516 }
7517 \cs_new_protected:Npn \msg_new:nnn #1#2#3
7518 { \msg_new:nnnn {#1} {#2} {#3} { } }
7519 \cs_new_protected:Npn \msg_set:nnnn #1#2#3#4
7520 {
7521   \cs_set:cpn { \c__msg_text_prefix_tl #1 / #2 }
7522     ##1##2##3##4 {#3}
7523   \cs_set:cpn { \c__msg_more_text_prefix_tl #1 / #2 }
7524     ##1##2##3##4 {#4}
7525 }
7526 \cs_new_protected:Npn \msg_set:nnn #1#2#3
7527 { \msg_set:nnnn {#1} {#2} {#3} { } }
7528 \cs_new_protected:Npn \msg_gset:nnnn #1#2#3#4
7529 {
7530   \cs_gset:cpn { \c__msg_text_prefix_tl #1 / #2 }
7531     ##1##2##3##4 {#3}
7532   \cs_gset:cpn { \c__msg_more_text_prefix_tl #1 / #2 }
7533     ##1##2##3##4 {#4}
7534 }
7535 \cs_new_protected:Npn \msg_gset:nnn #1#2#3
7536 { \msg_gset:nnnn {#1} {#2} {#3} { } }

```

(End definition for `\msg_new:nnnn` and others. These functions are documented on page 126.)

15.2 Messages: support functions and text

`\c__msg_coding_error_text_tl` Simple pieces of text for messages.

```

\c__msg_continue_text_tl 7537 \tl_const:Nn \c__msg_coding_error_text_tl
\c__msg_critical_text_tl 7538 {
\c__msg_fatal_text_tl    7539   This-is-a-coding-error.
\c__msg_help_text_tl     7540   \ \ \
\c__msg_no_info_text_tl  7541 }
\c__msg_on_line_text_tl  7542 \tl_const:Nn \c__msg_continue_text_tl
\c__msg_return_text_tl   7543 { Type~<return>~to~continue }
\c__msg_trouble_text_tl  7544 \tl_const:Nn \c__msg_critical_text_tl
                          7545 { Reading~the~current~file~'\g_file_current_name_tl'~will~stop. }
                          7546 \tl_const:Nn \c__msg_fatal_text_tl
                          7547 { This-is-a-fatal-error:~LaTeX-will~abort. }
\c__msg_help_text_tl     7548 \tl_const:Nn \c__msg_help_text_tl
                          7549 { For~immediate~help~type~H~<return> }
\c__msg_no_info_text_tl  7550 \tl_const:Nn \c__msg_no_info_text_tl
                          7551 {
                          7552   LaTeX~does~not~know~anything~more~about~this~error,~sorry.
                          7553   \c__msg_return_text_tl
                          7554 }
                          7555 \tl_const:Nn \c__msg_on_line_text_tl { on-line }
                          7556 \tl_const:Nn \c__msg_return_text_tl
                          7557 {
                          7558   \ \ \
                          7559   Try~typing~<return>~to~proceed.
                          7560   \ \
                          7561   If~that~doesn't~work,~type~X~<return>~to~quit.
                          7562 }

```

```

7563 \tl_const:Nn \c__msg_trouble_text_tl
7564 {
7565   \\\ \\\
7566   More~errors~will~almost~certainly~follow: \\\
7567   the~LaTeX~run~should~be~aborted.
7568 }

```

(End definition for `\c__msg_coding_error_text_tl` and others.)

`\msg_line_number:` For writing the line number nicely. `\msg_line_context:` was set up earlier, so this is not new.

```

7569 \cs_new:Npn \msg_line_number: { \int_use:N \tex_inputlineno:D }
7570 \cs_gset:Npn \msg_line_context:
7571 {
7572   \c__msg_on_line_text_tl
7573   \c_space_tl
7574   \msg_line_number:
7575 }

```

(End definition for `\msg_line_number:` and `\msg_line_context:`. These functions are documented on page 127.)

15.3 Showing messages: low level mechanism

`\msg_interrupt:nnn` The low-level interruption macro is rather opaque, unfortunately. Depending on the availability of more information there is a choice of how to set up the further help. We feed the extra help text and the message itself to a wrapping auxiliary, in this order because we must first setup TeX's `\errhelp` register before issuing an `\errmessage`.

```

7576 \cs_new_protected:Npn \msg_interrupt:nnn #1#2#3
7577 {
7578   \tl_if_empty:nTF {#3}
7579   {
7580     \__msg_interrupt_wrap:nn { \\\ \c__msg_no_info_text_tl }
7581     {#1 \\\ \\\ #2 \\\ \\\ \c__msg_continue_text_tl }
7582   }
7583   {
7584     \__msg_interrupt_wrap:nn { \\\ #3 }
7585     {#1 \\\ \\\ #2 \\\ \\\ \c__msg_help_text_tl }
7586   }
7587 }

```

(End definition for `\msg_interrupt:nnn`. This function is documented on page 131.)

`__msg_interrupt_wrap:nn`
`__msg_interrupt_more_text:n`

First setup TeX's `\errhelp` register with the extra help #1, then build a nice-looking error message with #2. Everything is done using x-type expansion as the new line markers are different for the two type of text and need to be correctly set up. The auxiliary `__msg_interrupt_more_text:n` receives its argument as a line-wrapped string, which is thus unaffected by expansion.

```

7588 \cs_new_protected:Npn \__msg_interrupt_wrap:nn #1#2
7589 {
7590   \iow_wrap:nnnN {#1} { | ~ } { } \__msg_interrupt_more_text:n
7591   \iow_wrap:nnnN {#2} { ! ~ } { } \__msg_interrupt_text:n
7592 }
7593 \cs_new_protected:Npn \__msg_interrupt_more_text:n #1

```

```

7594 {
7595   \exp_args:Nx \tex_errhelp:D
7596   {
7597     |,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,
7598     #1 \iow_newline:
7599     |.....
7600   }
7601 }

```

(End definition for `_msg_interrupt_wrap:nn` and `_msg_interrupt_more_text:n`.)

`_msg_interrupt_text:n` The business end of the process starts by producing some visual separation of the message from the main part of the log. The error message needs to be printed with everything made “invisible”: T_EX’s own information involves the macro in which `\errmessage` is called, and the end of the argument of the `\errmessage`, including the closing brace. We use an active `!` to call the `\errmessage` primitive, and end its argument with `\use_none:n {<dots>}` which fills the output with dots. Two trailing closing braces are turned into spaces to hide them as well. The group in which we alter the definition of the active `!` is closed before producing the message: this ensures that tokens inserted by typing `I` in the command-line will be inserted after the message is entirely cleaned up.

The `_iow_with:Nnn` auxiliary, defined in `l3file`, expects an *<integer variable>*, an integer *<value>*, and some *<code>*. It runs the *<code>* after ensuring that the *<integer variable>* takes the given *<value>*, then restores the former value of the *<integer variable>* if needed. We use it to ensure that the `\newlinechar` is 10, as needed for `\iow_newline:` to work, and that `\errorcontextlines` is `-1`, to avoid showing irrelevant context. Note that restoring the former value of these integers requires inserting tokens after the `\errmessage`, which go in the way of tokens which could be inserted by the user. This is unavoidable.

```

7602 \group_begin:
7603   \char_set_lccode:nn {'\} {'\ }
7604   \char_set_lccode:nn {'\} {'\ }
7605   \char_set_lccode:nn {'\& {'\!}
7606   \char_set_catcode_active:N \&
7607   \tex_lowercase:D
7608   {
7609     \group_end:
7610     \cs_new_protected:Npn \_msg_interrupt_text:n #1
7611     {
7612       \iow_term:x
7613       {
7614         \iow_newline:
7615         !!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!
7616         \iow_newline:
7617         !
7618       }
7619       \_iow_with:Nnn \tex_newlinechar:D { '\^J }
7620       {
7621         \_iow_with:Nnn \tex_errorcontextlines:D { -1 }
7622         {
7623           \group_begin:
7624           \cs_set_protected:Npn &
7625           {
7626             \tex_errmessage:D

```

```

7627         {
7628             #1
7629             \use_none:n
7630             { ..... }
7631         }
7632     }
7633     \exp_after:wN
7634     \group_end:
7635     &
7636 }
7637 }
7638 }
7639 }

```

(End definition for `_msg_interrupt_text:n`.)

`\msg_log:n` Printing to the log or terminal without a stop is rather easier. A bit of simple visual
`\msg_term:n` work sets things off nicely.

```

7640 \cs_new_protected:Npn \msg_log:n #1
7641 {
7642     \iow_log:n { ..... }
7643     \iow_wrap:nnnN { . ~ #1 } { . ~ } { } \iow_log:n
7644     \iow_log:n { ..... }
7645 }
7646 \cs_new_protected:Npn \msg_term:n #1
7647 {
7648     \iow_term:n { ***** }
7649     \iow_wrap:nnnN { * ~ #1 } { * ~ } { } \iow_term:n
7650     \iow_term:n { ***** }
7651 }

```

(End definition for `\msg_log:n` and `\msg_term:n`. These functions are documented on page [132](#).)

15.4 Displaying messages

L^AT_EX is handling error messages and so the T_EX ones are disabled. This is already done by the L^AT_EX 2_ε kernel, so to avoid messing up any deliberate change by a user this is only set in format mode.

```

7652 <*initex>
7653 \int_gset:Nn \tex_errorcontextlines:D { -1 }
7654 </initex>

```

`\msg_fatal_text:n` A function for issuing messages: both the text and order could in principle vary.

```

\msg_critical_text:n
\msg_error_text:n
\msg_warning_text:n
\msg_info_text:n
7655 \cs_new:Npn \msg_fatal_text:n #1
7656 {
7657     Fatal~#1~error
7658     \bool_if:NT \l__msg_line_context_bool { ~ \msg_line_context: }
7659 }
7660 \cs_new:Npn \msg_critical_text:n #1
7661 {
7662     Critical~#1~error
7663     \bool_if:NT \l__msg_line_context_bool { ~ \msg_line_context: }
7664 }
7665 \cs_new:Npn \msg_error_text:n #1

```

```

7666 {
7667   #1~error
7668   \bool_if:NT \l__msg_line_context_bool { ~ \msg_line_context: }
7669 }
7670 \cs_new:Npn \msg_warning_text:n #1
7671 {
7672   #1~warning
7673   \bool_if:NT \l__msg_line_context_bool { ~ \msg_line_context: }
7674 }
7675 \cs_new:Npn \msg_info_text:n #1
7676 {
7677   #1~info
7678   \bool_if:NT \l__msg_line_context_bool { ~ \msg_line_context: }
7679 }

```

(End definition for `\msg_fatal_text:n` and others. These functions are documented on page 127.)

`\msg_see_documentation_text:n` Contextual footer information. The \LaTeX module only comprises \LaTeX 3 code, so we refer to the \LaTeX 3 documentation rather than simply “ \LaTeX ”.

```

7680 \cs_new:Npn \msg_see_documentation_text:n #1
7681 {
7682   \\\ See~the~
7683   \str_if_eq:nnTF {#1} { LaTeX } { LaTeX3 } {#1} ~
7684   documentation~for~further~information.
7685 }

```

(End definition for `\msg_see_documentation_text:n`. This function is documented on page 128.)

`__msg_class_new:nn`

```

7686 \group_begin:
7687 \cs_set_protected:Npn \__msg_class_new:nn #1#2
7688 {
7689   \prop_new:c { l__msg_redirect_ #1 _prop }
7690   \cs_new_protected:cpn { __msg_ #1 _code:nnnnnn }
7691     ##1##2##3##4##5##6 {#2}
7692   \cs_new_protected:cpn { msg_ #1 :nnnnnn } ##1##2##3##4##5##6
7693   {
7694     \use:x
7695     {
7696       \exp_not:n { \__msg_use:nnnnnnn {#1} {##1} {##2} }
7697       { \tl_to_str:n {##3} } { \tl_to_str:n {##4} }
7698       { \tl_to_str:n {##5} } { \tl_to_str:n {##6} }
7699     }
7700   }
7701   \cs_new_protected:cpx { msg_ #1 :nnnnn } ##1##2##3##4##5
7702     { \exp_not:c { msg_ #1 :nnnnnn } {##1} {##2} {##3} {##4} {##5} { } }
7703   \cs_new_protected:cpx { msg_ #1 :nnnn } ##1##2##3##4
7704     { \exp_not:c { msg_ #1 :nnnnnn } {##1} {##2} {##3} {##4} { } { } }
7705   \cs_new_protected:cpx { msg_ #1 :nnn } ##1##2##3
7706     { \exp_not:c { msg_ #1 :nnnnnn } {##1} {##2} {##3} { } { } { } }
7707   \cs_new_protected:cpx { msg_ #1 :nn } ##1##2
7708     { \exp_not:c { msg_ #1 :nnnnnn } {##1} {##2} { } { } { } { } }
7709   \cs_new_protected:cpx { msg_ #1 :nnxxxx } ##1##2##3##4##5##6
7710   {

```



```

7711         \use:x
7712         {
7713             \exp_not:N \exp_not:n
7714             { \exp_not:c { msg_ #1 :nnnnnn } {##1} {##2} }
7715             {##3} {##4} {##5} {##6}
7716         }
7717     }
7718     \cs_new_protected:cpx { msg_ #1 :nnxxx } ##1##2##3##4##5
7719     { \exp_not:c { msg_ #1 :nnxxx } {##1} {##2} {##3} {##4} {##5} { } }
7720     \cs_new_protected:cpx { msg_ #1 :nnxx } ##1##2##3##4
7721     { \exp_not:c { msg_ #1 :nnxxx } {##1} {##2} {##3} {##4} { } { } }
7722     \cs_new_protected:cpx { msg_ #1 :nnx } ##1##2##3
7723     { \exp_not:c { msg_ #1 :nnxxx } {##1} {##2} {##3} { } { } { } }
7724 }

```

(End definition for `_msg_class_new:nn`.)

`\msg_fatal:nnnnnn` For fatal errors, after the error message T_EX bails out.

```

\msg_fatal:nnxxxx 7725 \_msg_class_new:nn { fatal }
\msg_fatal:nnnnn 7726 {
\msg_fatal:nnxxx 7727     \msg_interrupt:nnn
\msg_fatal:nnnn 7728     { \msg_fatal_text:n {#1} : ~ "#2" }
\msg_fatal:nnxx 7729     {
\msg_fatal:nnn 7730         \use:c { \c__msg_text_prefix_tl #1 / #2 } {#3} {#4} {#5} {#6}
\msg_fatal:nnx 7731         \msg_see_documentation_text:n {#1}
\msg_fatal:nn 7732     }
7733     { \c__msg_fatal_text_tl }
7734     \tex_end:D
7735 }

```

(End definition for `\msg_fatal:nnnnnn` and others. These functions are documented on page 128.)

`\msg_critical:nnnnnn` Not quite so bad: just end the current file.

```

\msg_critical:nnxxxx 7736 \_msg_class_new:nn { critical }
\msg_critical:nnnnn 7737 {
\msg_critical:nnxxx 7738     \msg_interrupt:nnn
\msg_critical:nnnn 7739     { \msg_critical_text:n {#1} : ~ "#2" }
\msg_critical:nnxx 7740     {
\msg_critical:nnn 7741         \use:c { \c__msg_text_prefix_tl #1 / #2 } {#3} {#4} {#5} {#6}
\msg_critical:nnx 7742         \msg_see_documentation_text:n {#1}
\msg_critical:nn 7743     }
7744     { \c__msg_critical_text_tl }
7745     \tex_endinput:D
7746 }

```

(End definition for `\msg_critical:nnnnnn` and others. These functions are documented on page 128.)

`\msg_error:nnnnnn` For an error, the interrupt routine is called. We check if there is a “more text” by comparing that control sequence with a permanently empty text.

```

\msg_error:nnxxxx 7747 \_msg_class_new:nn { error }
\msg_error:nnxxx 7748 {
\msg_error:nnnn 7749     \_msg_error:cnnnnn
\msg_error:nnxx 7750     { \c__msg_more_text_prefix_tl #1 / #2 }
\msg_error:nnn 7751     {#3} {#4} {#5} {#6}
\msg_error:nnx 7752     {
\msg_error:nn

```

```

\__msg_error:cnnnnn
\__msg_no_more_text:nnnn

```

```

7753         \msg_interrupt:nnn
7754         { \msg_error_text:n {#1} : ~ "#2" }
7755         {
7756             \use:c { \c__msg_text_prefix_tl #1 / #2 } {#3} {#4} {#5} {#6}
7757             \msg_see_documentation_text:n {#1}
7758         }
7759     }
7760 }
7761 \cs_new_protected:Npn \__msg_error:cnnnnn #1#2#3#4#5#6
7762 {
7763     \cs_if_eq:cNTF {#1} \__msg_no_more_text:nnnn
7764     { #6 { } }
7765     { #6 { \use:c {#1} {#2} {#3} {#4} {#5} } }
7766 }
7767 \cs_new:Npn \__msg_no_more_text:nnnn #1#2#3#4 { }

```

(End definition for `\msg_error:nnnnnn` and others. These functions are documented on page 129.)

`\msg_warning:nnnnnn` Warnings are printed to the terminal.

```

\msg_warning:nnxxxx 7768 \__msg_class_new:nn { warning }
\msg_warning:nnnnn 7769 {
\msg_warning:nnxxx 7770     \msg_term:n
\msg_warning:nnnn 7771     {
\msg_warning:nnxx 7772         \msg_warning_text:n {#1} : ~ "#2" \\ \\
\msg_warning:nnn 7773         \use:c { \c__msg_text_prefix_tl #1 / #2 } {#3} {#4} {#5} {#6}
\msg_warning:nnx 7774     }
\msg_warning:nn 7775 }

```

(End definition for `\msg_warning:nnnnnn` and others. These functions are documented on page 129.)

`\msg_info:nnnnnn` Information only goes into the log.

```

\msg_info:nnxxxx 7776 \__msg_class_new:nn { info }
\msg_info:nnnnn 7777 {
\msg_info:nnxxx 7778     \msg_log:n
\msg_info:nnnn 7779     {
\msg_info:nnxx 7780         \msg_info_text:n {#1} : ~ "#2" \\ \\
\msg_info:nnn 7781         \use:c { \c__msg_text_prefix_tl #1 / #2 } {#3} {#4} {#5} {#6}
\msg_info:nnx 7782     }
\msg_info:nn 7783 }

```

(End definition for `\msg_info:nnnnnn` and others. These functions are documented on page 129.)

`\msg_log:nnnnnn` "Log" data is very similar to information, but with no extras added.

```

\msg_log:nnxxxx 7784 \__msg_class_new:nn { log }
\msg_log:nnnnn 7785 {
\msg_log:nnxxx 7786     \iow_wrap:nnnN
\msg_log:nnnn 7787     { \use:c { \c__msg_text_prefix_tl #1 / #2 } {#3} {#4} {#5} {#6} }
\msg_log:nnxx 7788     { } { } \iow_log:n
\msg_log:nnn 7789 }
\msg_log:nnx
\msg_log:nn

```

(End definition for `\msg_log:nnnnnn` and others. These functions are documented on page 129.)

`\msg_none:nnnnnn` The `none` message type is needed so that input can be gobbled.

```

\msg_none:nnxxxx 7790 \__msg_class_new:nn { none } { }
\msg_none:nnnnn
\msg_none:nnxxx
\msg_none:nnnn
\msg_none:nnxx
\msg_none:nnn
\msg_none:nnx
\msg_none:nn

```

(End definition for \msg_none:nnnnnn and others. These functions are documented on page 130.)

End the group to eliminate _msg_class_new:nn.

7791 \group_end:

_msg_class_chk_exist:nT Checking that a message class exists. We build this from \cs_if_free:cTF rather than \cs_if_exist:cTF because that avoids reading the second argument earlier than necessary.

```
7792 \cs_new:Npn \_msg_class_chk_exist:nT #1
7793 {
7794   \cs_if_free:cTF { \_msg_ #1 _code:nnnnnn }
7795   { \_msg_kernel_error:nx { kernel } { message-class-unknown } {#1} }
7796 }
```

(End definition for _msg_class_chk_exist:nT.)

\l__msg_class_tl Support variables needed for the redirection system.

```
\l__msg_current_class_tl
7797 \tl_new:N \l__msg_class_tl
7798 \tl_new:N \l__msg_current_class_tl
```

(End definition for \l__msg_class_tl and \l__msg_current_class_tl.)

\l__msg_redirect_prop For redirection of individually-named messages

```
7799 \prop_new:N \l__msg_redirect_prop
```

(End definition for \l__msg_redirect_prop.)

\l__msg_hierarchy_seq During redirection, split the message name into a sequence with items {/module/submodule}, {/module}, and {}.

```
7800 \seq_new:N \l__msg_hierarchy_seq
```

(End definition for \l__msg_hierarchy_seq.)

\l__msg_class_loop_seq Classes encountered when following redirections to check for loops.

```
7801 \seq_new:N \l__msg_class_loop_seq
```

(End definition for \l__msg_class_loop_seq.)

_msg_use:nnnnnn

Actually using a message is a multi-step process. First, some safety checks on the message and class requested. The code and arguments are then stored to avoid passing them around. The assignment to _msg_use_code: is similar to \tl_set:Nn. The message is eventually produced with whatever \l__msg_class_tl is when _msg_use_code: is called.

```
7802 \cs_new_protected:Npn \_msg_use:nnnnnn #1#2#3#4#5#6#7
7803 {
7804   \msg_if_exist:nnTF {#2} {#3}
7805   {
7806     \_msg_class_chk_exist:nT {#1}
7807     {
7808       \tl_set:Nn \l__msg_current_class_tl {#1}
7809       \cs_set_protected:Npx \_msg_use_code:
7810       {
7811         \exp_not:n
7812         {
7813           \use:c { \_msg_ \l__msg_class_tl _code:nnnnnn }

```

```

7814         {#2} {#3} {#4} {#5} {#6} {#7}
7815     }
7816 }
7817     \__msg_use_redirect_name:n { #2 / #3 }
7818 }
7819 }
7820 { \__msg_kernel_error:nxx { kernel } { message-unknown } {#2} {#3} }
7821 }
7822 \cs_new_protected:Npn \__msg_use_code: { }

```

The first check is for a individual message redirection. If this applies then no further redirection is attempted. Otherwise, split the message name into `module/submodule/message` (with an arbitrary number of slashes), and store `{/module/submodule}`, `{/module}` and `{}` into `\l__msg_hierarchy_seq`. We will then map through this sequence, applying the most specific redirection.

```

7823 \cs_new_protected:Npn \__msg_use_redirect_name:n #1
7824 {
7825     \prop_get:NnNTF \l__msg_redirect_prop { / #1 } \l__msg_class_tl
7826     { \__msg_use_code: }
7827     {
7828         \seq_clear:N \l__msg_hierarchy_seq
7829         \__msg_use_hierarchy:nwN { }
7830         #1 \q_mark \__msg_use_hierarchy:nwN
7831         / \q_mark \use_none_delimit_by_q_stop:w
7832         \q_stop
7833         \__msg_use_redirect_module:n { }
7834     }
7835 }
7836 \cs_new_protected:Npn \__msg_use_hierarchy:nwN #1#2 / #3 \q_mark #4
7837 {
7838     \seq_put_left:Nn \l__msg_hierarchy_seq {#1}
7839     #4 { #1 / #2 } #3 \q_mark #4
7840 }

```

At this point, the items of `\l__msg_hierarchy_seq` are the various levels at which we should look for a redirection. Redirections which are less specific than the argument of `__msg_use_redirect_module:n` are not attempted. This argument is empty for a class redirection, `/module` for a module redirection, *etc.* Loop through the sequence to find the most specific redirection, with module `##1`. The loop is interrupted after testing for a redirection for `##1` equal to the argument `#1` (least specific redirection allowed). When a redirection is found, break the mapping, then if the redirection targets the same class, output the code with that class, and otherwise set the target as the new current class, and search for further redirections. Those redirections should be at least as specific as `##1`.

```

7841 \cs_new_protected:Npn \__msg_use_redirect_module:n #1
7842 {
7843     \seq_map_inline:Nn \l__msg_hierarchy_seq
7844     {
7845         \prop_get:cnNTF { \l__msg_redirect_ \l__msg_current_class_tl _prop }
7846         {##1} \l__msg_class_tl
7847         {
7848             \seq_map_break:n
7849             {
7850                 \tl_if_eq:NNTF \l__msg_current_class_tl \l__msg_class_tl

```

```

7851         { \__msg_use_code: }
7852         {
7853             \tl_set_eq:NN \l__msg_current_class_tl \l__msg_class_tl
7854             \__msg_use_redirect_module:n {##1}
7855         }
7856     }
7857 }
7858 {
7859     \str_if_eq:nnT {##1} {#1}
7860     {
7861         \tl_set_eq:NN \l__msg_class_tl \l__msg_current_class_tl
7862         \seq_map_break:n { \__msg_use_code: }
7863     }
7864 }
7865 }
7866 }

```

(End definition for __msg_use:nnnnnnn and others.)

\msg_redirect_name:nnn Named message will always use the given class even if that class is redirected further. An empty target class cancels any existing redirection for that message.

```

7867 \cs_new_protected:Npn \msg_redirect_name:nnn #1#2#3
7868 {
7869     \tl_if_empty:nTF {#3}
7870     { \prop_remove:Nn \l__msg_redirect_prop { / #1 / #2 } }
7871     {
7872         \__msg_class_chk_exist:nT {#3}
7873         { \prop_put:Nnn \l__msg_redirect_prop { / #1 / #2 } {#3} }
7874     }
7875 }

```

(End definition for \msg_redirect_name:nnn. This function is documented on page 131.)

\msg_redirect_class:nn If the target class is empty, eliminate the corresponding redirection. Otherwise, add the redirection. We must then check for a loop: as an initialization, we start by storing the initial class in \l__msg_current_class_tl.

\msg_redirect_module:nnn
__msg_redirect:nnn
__msg_redirect_loop_chk:nnn
__msg_redirect_loop_list:n

```

7876 \cs_new_protected:Npn \msg_redirect_class:nn
7877 { \__msg_redirect:nnn { } }
7878 \cs_new_protected:Npn \msg_redirect_module:nnn #1
7879 { \__msg_redirect:nnn { / #1 } }
7880 \cs_new_protected:Npn \__msg_redirect:nnn #1#2#3
7881 {
7882     \__msg_class_chk_exist:nT {#2}
7883     {
7884         \tl_if_empty:nTF {#3}
7885         { \prop_remove:cn { l__msg_redirect_ #2 _prop } {#1} }
7886         {
7887             \__msg_class_chk_exist:nT {#3}
7888             {
7889                 \prop_put:cn { l__msg_redirect_ #2 _prop } {#1} {#3}
7890                 \tl_set:Nn \l__msg_current_class_tl {#2}
7891                 \seq_clear:N \l__msg_class_loop_seq
7892                 \__msg_redirect_loop_chk:nnn {#2} {#3} {#1}
7893             }

```

```

7894     }
7895   }
7896 }

```

Since multiple redirections can only happen with increasing specificity, a loop requires that all steps are of the same specificity. The new redirection can thus only create a loop with other redirections for the exact same module, #1, and not submodules. After some initialization above, follow redirections with `\l__msg_class_tl`, and keep track in `\l__msg_class_loop_seq` of the various classes encountered. A redirection from a class to itself, or the absence of redirection both mean that there is no loop. A redirection to the initial class marks a loop. To break it, we must decide which redirection to cancel. The user most likely wants the newly added redirection to hold with no further redirection. We thus remove the redirection starting from #2, target of the new redirection. Note that no message is emitted by any of the underlying functions: otherwise we may get an infinite loop because of a message from the message system itself.

```

7897 \cs_new_protected:Npn \__msg_redirect_loop_chk:nnn #1#2#3
7898 {
7899   \seq_put_right:Nn \l__msg_class_loop_seq {#1}
7900   \prop_get:cnNT { l__msg_redirect_ #1 _prop } {#3} \l__msg_class_tl
7901   {
7902     \str_if_eq:x:nnF { \l__msg_class_tl } {#1}
7903     {
7904       \tl_if_eq:NNTF \l__msg_class_tl \l__msg_current_class_tl
7905       {
7906         \prop_put:cnn { l__msg_redirect_ #2 _prop } {#3} {#2}
7907         \__msg_kernel_warning:nxxxxx
7908         { kernel } { message-redirect-loop }
7909         { \seq_item:Nn \l__msg_class_loop_seq { 1 } }
7910         { \seq_item:Nn \l__msg_class_loop_seq { 2 } }
7911         {#3}
7912         {
7913           \seq_map_function:NN \l__msg_class_loop_seq
7914             \__msg_redirect_loop_list:n
7915             { \seq_item:Nn \l__msg_class_loop_seq { 1 } }
7916         }
7917       }
7918       { \__msg_redirect_loop_chk:onn \l__msg_class_tl {#2} {#3} }
7919     }
7920   }
7921 }
7922 \cs_generate_variant:Nn \__msg_redirect_loop_chk:nnn { o }
7923 \cs_new:Npn \__msg_redirect_loop_list:n #1 { {#1} ~ => ~ }

```

(End definition for `\msg_redirect_class:nn` and others. These functions are documented on page 130.)

15.5 Kernel-specific functions

`__msg_kernel_new:nnnn` The kernel needs some messages of its own. These are created using pre-built functions.
`__msg_kernel_new:nnn` Two functions are provided: one more general and one which only has the short text
`__msg_kernel_set:nnnn` part.
`__msg_kernel_set:nnn`

```

7924 \cs_new_protected:Npn \__msg_kernel_new:nnnn #1#2
7925 { \msg_new:nnnn { LaTeX } { #1 / #2 } }
7926 \cs_new_protected:Npn \__msg_kernel_new:nnn #1#2

```

```

7927 { \msg_new:nnn { LaTeX } { #1 / #2 } }
7928 \cs_new_protected:Npn \__msg_kernel_set:nnnn #1#2
7929 { \msg_set:nnnn { LaTeX } { #1 / #2 } }
7930 \cs_new_protected:Npn \__msg_kernel_set:nnn #1#2
7931 { \msg_set:nnn { LaTeX } { #1 / #2 } }

```

(End definition for __msg_kernel_new:nnnn and others.)

```

\__msg_kernel_class_new:nN
\__msg_kernel_class_new_aux:nN

```

All the functions for kernel messages come in variants ranging from 0 to 4 arguments. Those with less than 4 arguments are defined in terms of the 4-argument variant, in a way very similar to __msg_class_new:nn. This auxiliary is destroyed at the end of the group.

```

7932 \group_begin:
7933 \cs_set_protected:Npn \__msg_kernel_class_new:nN #1
7934 { \__msg_kernel_class_new_aux:nN { kernel_ #1 } }
7935 \cs_set_protected:Npn \__msg_kernel_class_new_aux:nN #1#2
7936 {
7937   \cs_new_protected:cpn { __msg_ #1 :nnnnnn } ##1##2##3##4##5##6
7938   {
7939     \use:x
7940     {
7941       \exp_not:n { #2 { LaTeX } { ##1 / ##2 } }
7942       { \tl_to_str:n {##3} } { \tl_to_str:n {##4} }
7943       { \tl_to_str:n {##5} } { \tl_to_str:n {##6} }
7944     }
7945   }
7946   \cs_new_protected:cpx { __msg_ #1 :nnnnn } ##1##2##3##4##5
7947   { \exp_not:c { __msg_ #1 :nnnnnn } {##1} {##2} {##3} {##4} {##5} { } }
7948   \cs_new_protected:cpx { __msg_ #1 :nnnn } ##1##2##3##4
7949   { \exp_not:c { __msg_ #1 :nnnnnn } {##1} {##2} {##3} {##4} { } { } }
7950   \cs_new_protected:cpx { __msg_ #1 :nnn } ##1##2##3
7951   { \exp_not:c { __msg_ #1 :nnnnnn } {##1} {##2} {##3} { } { } { } }
7952   \cs_new_protected:cpx { __msg_ #1 :nn } ##1##2
7953   { \exp_not:c { __msg_ #1 :nnnnnn } {##1} {##2} { } { } { } { } }
7954   \cs_new_protected:cpx { __msg_ #1 :nnxxx } ##1##2##3##4##5##6
7955   {
7956     \use:x
7957     {
7958       \exp_not:N \exp_not:n
7959       { \exp_not:c { __msg_ #1 :nnnnnn } {##1} {##2} }
7960       {##3} {##4} {##5} {##6}
7961     }
7962   }
7963   \cs_new_protected:cpx { __msg_ #1 :nnxxx } ##1##2##3##4##5
7964   { \exp_not:c { __msg_ #1 :nnxxx } {##1} {##2} {##3} {##4} {##5} { } }
7965   \cs_new_protected:cpx { __msg_ #1 :nnxx } ##1##2##3##4
7966   { \exp_not:c { __msg_ #1 :nnxxx } {##1} {##2} {##3} {##4} { } { } }
7967   \cs_new_protected:cpx { __msg_ #1 :nnx } ##1##2##3
7968   { \exp_not:c { __msg_ #1 :nnxxx } {##1} {##2} {##3} { } { } { } }
7969 }

```

(End definition for __msg_kernel_class_new:nN and __msg_kernel_class_new_aux:nN.)

```

\__msg_kernel_fatal:nnnnnn
\__msg_kernel_fatal:nnxxxx
\__msg_kernel_fatal:nnnnn
\__msg_kernel_fatal:nnxxx
\__msg_kernel_fatal:nnnn
\__msg_kernel_fatal:nnxx
\__msg_kernel_fatal:nnn
\__msg_kernel_fatal:nnx
\__msg_kernel_fatal:nn
\__msg_kernel_fatal:nnnnnn
\__msg_kernel_warning:nnnnnn
\__msg_kernel_error:nnxxxx
\__msg_kernel_error:nnnnn
\__msg_kernel_warning:nnxxx
\__msg_kernel_error:nnxxx
\__msg_kernel_warning:nnxxx
\__msg_kernel_error:nnxxx
\__msg_kernel_warning:nnxx
\__msg_kernel_error:nnxx
\__msg_kernel_warning:nnx
\__msg_kernel_error:nnx
\__msg_kernel_warning:nn
\__msg_kernel_error:nn
\__msg_kernel_info:nnnnnn
\__msg_kernel_info:nnxxxx
\__msg_kernel_info:nnnnn
\__msg_kernel_info:nnxxx
\__msg_kernel_info:nnnn
\__msg_kernel_info:nnxx
\__msg_kernel_info:nnn
\__msg_kernel_info:nnx
\__msg_kernel_info:nn

```

Neither fatal kernel errors nor kernel errors can be redirected. We directly use the code for (non-kernel) fatal errors and errors, adding the “`LATEX`” module name. Three functions are already defined by `l3basics`; we need to undefine them to avoid errors.

```

7970 \__msg_kernel_class_new:nN { fatal } \__msg_fatal_code:nnnnnn
7971 \cs_undefine:N \__msg_kernel_error:nnxx
7972 \cs_undefine:N \__msg_kernel_error:nnx
7973 \cs_undefine:N \__msg_kernel_error:nn
7974 \__msg_kernel_class_new:nN { error } \__msg_error_code:nnnnnn

```

(End definition for `__msg_kernel_fatal:nnnnnn` and others.)

Kernel messages which can be redirected simply use the machinery for normal messages, with the module name “`LATEX`”.

```

7975 \__msg_kernel_class_new:nN { warning } \msg_warning:nnxxxxx
7976 \__msg_kernel_class_new:nN { info } \msg_info:nnxxxxx

```

(End definition for `__msg_kernel_warning:nnnnnn` and others.)

End the group to eliminate `__msg_kernel_class_new:nN`.

```

7977 \group_end:

```

Error messages needed to actually implement the message system itself.

```

7978 \__msg_kernel_new:nnnn { kernel } { message-already-defined }
7979 { Message~'#2'~for~module~'#1'~already-defined. }
7980 {
7981   \c__msg_coding_error_text_tl
7982   LaTeX~was~asked~to~define~a~new~message~called~'#2'\
7983   by~the~module~'#1':~this~message~already~exists.
7984   \c__msg_return_text_tl
7985 }
7986 \__msg_kernel_new:nnnn { kernel } { message-unknown }
7987 { Unknown~message~'#2'~for~module~'#1'. }
7988 {
7989   \c__msg_coding_error_text_tl
7990   LaTeX~was~asked~to~display~a~message~called~'#2'\
7991   by~the~module~'#1':~this~message~does~not~exist.
7992   \c__msg_return_text_tl
7993 }
7994 \__msg_kernel_new:nnnn { kernel } { message-class-unknown }
7995 { Unknown~message~class~'#1'. }
7996 {
7997   LaTeX~has~been~asked~to~redirect~messages~to~a~class~'#1':\
7998   this~was~never~defined.
7999   \c__msg_return_text_tl
8000 }
8001 \__msg_kernel_new:nnnn { kernel } { message-redirect-loop }
8002 {
8003   Message~redirection~loop~caused~by~ {#1} ~>~ {#2}
8004   \tl_if_empty:nF {#3} { ~for~module~' \use_none:n #3 ' } .
8005 }
8006 {
8007   Adding~the~message~redirection~ {#1} ~>~ {#2}
8008   \tl_if_empty:nF {#3} { ~for~the~module~' \use_none:n #3 ' } ~
8009   created~an~infinite~loop\\\
8010   \iow_indent:n { #4 \\\ }
8011 }

```


Messages for earlier kernel modules.

```

8012 \_msg_kernel_new:nnnn { kernel } { bad-number-of-arguments }
8013 { Function~'#1'~cannot~be~defined~with~#2~arguments. }
8014 {
8015   \c__msg_coding_error_text_tl
8016   LaTeX~has~been~asked~to~define~a~function~'#1'~with~
8017   #2~arguments.~
8018   TeX~allows~between~0~and~9~arguments~for~a~single~function.
8019 }
8020 \_msg_kernel_new:nnn { kernel } { char-active }
8021 { Cannot~generate~active~chars. }
8022 \_msg_kernel_new:nnn { kernel } { char-invalid-catcode }
8023 { Invalid~catcode~for~char~generation. }
8024 \_msg_kernel_new:nnn { kernel } { char-null-space }
8025 { Cannot~generate~null~char~as~a~space. }
8026 \_msg_kernel_new:nnn { kernel } { char-out-of-range }
8027 { Charcode~requested~out~of~engine~range. }
8028 \_msg_kernel_new:nnn { kernel } { char-space }
8029 { Cannot~generate~space~chars. }
8030 \_msg_kernel_new:nnnn { kernel } { command-already-defined }
8031 { Control~sequence~#1~already~defined. }
8032 {
8033   \c__msg_coding_error_text_tl
8034   LaTeX~has~been~asked~to~create~a~new~control~sequence~'#1'~
8035   but~this~name~has~already~been~used~elsewhere. \\ \\
8036   The~current~meaning~is:\\
8037   \\ #2
8038 }
8039 \_msg_kernel_new:nnnn { kernel } { command-not-defined }
8040 { Control~sequence~#1~undefined. }
8041 {
8042   \c__msg_coding_error_text_tl
8043   LaTeX~has~been~asked~to~use~a~control~sequence~'#1':\\
8044   this~has~not~been~defined~yet.
8045 }
8046 \_msg_kernel_new:nnn { kernel } { deprecated-command }
8047 {
8048   The~deprecated~command~'#2'~has~been~or~will~be~removed~on~#1.
8049   \tl_if_empty:nF {#3} { ~Use~instead~'#3'. }
8050 }
8051 \_msg_kernel_new:nnnn { kernel } { empty-search-pattern }
8052 { Empty~search~pattern. }
8053 {
8054   \c__msg_coding_error_text_tl
8055   LaTeX~has~been~asked~to~replace~an~empty~pattern~by~'#1':~that~
8056   would~lead~to~an~infinite~loop!
8057 }
8058 \_msg_kernel_new:nnnn { kernel } { out-of-registers }
8059 { No~room~for~a~new~#1. }
8060 {
8061   TeX~only~supports~\int_use:N \c_max_register_int \ %
8062   of~each~type.~All~the~#1~registers~have~been~used.~
8063   This~run~will~be~aborted~now.
8064 }

```

```

8065 \_msg_kernel_new:nnnn { kernel } { non-base-function }
8066 { Function~'#1'~is-not-a-base-function }
8067 {
8068   \c_msg_coding_error_text_tl
8069   Functions~defined~through~\iow_char:N\cs_new:Nn~must~have~
8070   a~signature~consisting~of~only~normal~arguments~'N'~and~'n'.~
8071   To~define~variants~use~\iow_char:N\cs_generate_variant:Nn~
8072   and~to~define~other~functions~use~\iow_char:N\cs_new:Npn.
8073 }
8074 \_msg_kernel_new:nnnn { kernel } { missing-colon }
8075 { Function~'#1'~contains-no~':'. }
8076 {
8077   \c_msg_coding_error_text_tl
8078   Code~level~functions~must~contain~':'~to~separate~the~
8079   argument~specification~from~the~function~name.~This~is~
8080   needed~when~defining~conditionals~or~variants,~or~when~building~a~
8081   parameter~text~from~the~number~of~arguments~of~the~function.
8082 }
8083 \_msg_kernel_new:nnnn { kernel } { protected-predicate }
8084 { Predicate~'#1'~must~be~expandable. }
8085 {
8086   \c_msg_coding_error_text_tl
8087   LaTeX~has~been~asked~to~define~'#1'~as~a~protected~predicate.~
8088   Only~expandable~tests~can~have~a~predicate~version.
8089 }
8090 \_msg_kernel_new:nnnn { kernel } { conditional-form-unknown }
8091 { Conditional~form~'#1'~for~function~'#2'~unknown. }
8092 {
8093   \c_msg_coding_error_text_tl
8094   LaTeX~has~been~asked~to~define~the~conditional~form~'#1'~of~
8095   the~function~'#2',~but~only~'TF',~'T',~'F',~and~'p'~forms~exist.
8096 }
8097 (*package)
8098 \bool_if:NT \l@expl@check@declarations@bool
8099 {
8100   \_msg_kernel_new:nnnn { check } { non-declared-variable }
8101   { The~variable~'#1'~has~not~been~declared~\msg_line_context:. }
8102   {
8103     Checking~is~active,~and~you~have~tried~do~so~something~like: \\
8104     \ \ \tl_set:Nn ~ #1 ~ \{ ~ ... ~ \} \\
8105     without~first~having: \\
8106     \ \ \tl_new:N ~ #1 \\
8107     \\
8108     LaTeX~will~create~the~variable~and~continue.
8109   }
8110 }
8111 (/package)
8112 \_msg_kernel_new:nnnn { kernel } { scanmark-already-defined }
8113 { Scan~mark~'#1'~already~defined. }
8114 {
8115   \c_msg_coding_error_text_tl
8116   LaTeX~has~been~asked~to~create~a~new~scan~mark~'#1'~
8117   but~this~name~has~already~been~used~for~a~scan~mark.
8118 }

```

```

8119 \__msg_kernel_new:nnnn { kernel } { variable-not-defined }
8120 { Variable~#1~undefined. }
8121 {
8122   \c__msg_coding_error_text_tl
8123   LaTeX~has~been~asked~to~show~a~variable~#1,~but~this~has~not~
8124   been~defined~yet.
8125 }
8126 \__msg_kernel_new:nnnn { kernel } { variant-too-long }
8127 { Variant~form~'~#1'~longer~than~base~signature~of~'~#2'. }
8128 {
8129   \c__msg_coding_error_text_tl
8130   LaTeX~has~been~asked~to~create~a~variant~of~the~function~'~#2'~
8131   with~a~signature~starting~with~'~#1',~but~that~is~longer~than~
8132   the~signature~(part~after~the~colon)~of~'~#2'.
8133 }
8134 \__msg_kernel_new:nnnn { kernel } { invalid-variant }
8135 { Variant~form~'~#1'~invalid~for~base~form~'~#2'. }
8136 {
8137   \c__msg_coding_error_text_tl
8138   LaTeX~has~been~asked~to~create~a~variant~of~the~function~'~#2'~
8139   with~a~signature~starting~with~'~#1',~but~cannot~change~an~argument~
8140   from~type~'~#3'~to~type~'~#4'.
8141 }

```

Some errors only appear in expandable settings, hence don't need a “more-text” argument.

```

8142 \__msg_kernel_new:nnn { kernel } { bad-variable }
8143 { Erroneous~variable~#1~used! }
8144 \__msg_kernel_new:nnn { kernel } { misused-sequence }
8145 { A~sequence~was~misused. }
8146 \__msg_kernel_new:nnn { kernel } { misused-prop }
8147 { A~property~list~was~misused. }
8148 \__msg_kernel_new:nnn { kernel } { negative-replication }
8149 { Negative~argument~for~\prg_replicate:nn. }
8150 \__msg_kernel_new:nnn { kernel } { unknown-comparison }
8151 { Relation~'~#1'~unknown:~use~=,~<,~>,~==,~!=,~<=,~>=. }
8152 \__msg_kernel_new:nnn { kernel } { zero-step }
8153 { Zero~step~size~for~step~function~#1. }

```

Messages used by the “show” functions.

```

8154 \__msg_kernel_new:nnn { kernel } { show-clist }
8155 {
8156   The~comma~list~ \tl_if_empty:nF {#1} { #1 ~ }
8157   \tl_if_empty:nTF {#2}
8158   { is~empty }
8159   { contains~the~items~(without~outer~braces): }
8160 }
8161 \__msg_kernel_new:nnn { kernel } { show-prop }
8162 {
8163   The~property~list~#1~
8164   \tl_if_empty:nTF {#2}
8165   { is~empty }
8166   { contains~the~pairs~(without~outer~braces): }
8167 }
8168 \__msg_kernel_new:nnn { kernel } { show-seq }

```

```

8169 {
8170   The~sequence~#1~
8171   \tl_if_empty:nTF {#2}
8172     { is~empty }
8173     { contains~the~items~(without~outer~braces): }
8174 }
8175 \__msg_kernel_new:nnn { kernel } { show-streams }
8176 {
8177   \tl_if_empty:nTF {#2} { No~ } { The~following~ }
8178   \str_case:nn {#1}
8179     {
8180       { ior } { input ~ }
8181       { iow } { output ~ }
8182     }
8183   streams~are~
8184   \tl_if_empty:nTF {#2} { open } { in~use: }
8185 }

```

15.6 Expandable errors

`__msg_expandable_error:n` In expansion only context, we cannot use the normal means of reporting errors. Instead, we feed \TeX an undefined control sequence, `\LaTeX3 error:.` It is thus interrupted, and shows the context, which thanks to the odd-looking `\use:n` is

```

<argument> \LaTeX3 error:
                The error message.

```

In other words, \TeX is processing the argument of `\use:n`, which is `\LaTeX3 error: <error message>`. Then `__msg_expandable_error:w` cleans up. In fact, there is an extra subtlety: if the user inserts tokens for error recovery, they should be kept. Thus we also use an odd space character (with category code 7) and keep tokens until that space character, dropping everything else until `\q_stop`. The `\exp_end:` prevents losing braces around the user-inserted text if any, and stops the expansion of `\exp:w`. The group is used to prevent `\LaTeX3~error:` from being globally equal to `\scan_stop:.`

```

8186 \group_begin:
8187 \cs_set_protected:Npn \__msg_tmp:w #1#2
8188 {
8189   \cs_new:Npn \__msg_expandable_error:n ##1
8190     {
8191       \exp:w
8192       \exp_after:wN \exp_after:wN
8193       \exp_after:wN \__msg_expandable_error:w
8194       \exp_after:wN \exp_after:wN
8195       \exp_after:wN \exp_end:
8196       \use:n { #1 #2 ##1 } #2
8197     }
8198   \cs_new:Npn \__msg_expandable_error:w ##1 #2 ##2 #2 {##1}
8199 }
8200 \exp_args:Ncx \__msg_tmp:w { LaTeX3~error: }
8201 { \char_generate:nn { ‘\ } { 7 } }
8202 \group_end:

```

(End definition for `__msg_expandable_error:n` and `__msg_expandable_error:w`.)

`_msg_kernel_expandable_error:nnnnnn`
`_msg_kernel_expandable_error:nnnnnn`
`_msg_kernel_expandable_error:nnnn`
`_msg_kernel_expandable_error:nnn`
`_msg_kernel_expandable_error:nn`

The command built from the csname `\c_@@_text_prefix_tl LaTeX / #1 / #2` takes four arguments and builds the error text, which is fed to `_msg_expandable_error:n`.

```

8203 \cs_new:Npn \_msg_kernel_expandable_error:nnnnnn #1#2#3#4#5#6
8204 {
8205   \exp_args:Nf \_msg_expandable_error:n
8206   {
8207     \exp_args:NNc \exp_after:wN \exp_stop_f:
8208     { \c__msg_text_prefix_tl LaTeX / #1 / #2 }
8209     {#3} {#4} {#5} {#6}
8210   }
8211 }
8212 \cs_new:Npn \_msg_kernel_expandable_error:nnnnn #1#2#3#4#5
8213 {
8214   \_msg_kernel_expandable_error:nnnnnn
8215   {#1} {#2} {#3} {#4} {#5} { }
8216 }
8217 \cs_new:Npn \_msg_kernel_expandable_error:nnnn #1#2#3#4
8218 {
8219   \_msg_kernel_expandable_error:nnnnnn
8220   {#1} {#2} {#3} {#4} { } { }
8221 }
8222 \cs_new:Npn \_msg_kernel_expandable_error:nnn #1#2#3
8223 {
8224   \_msg_kernel_expandable_error:nnnnnn
8225   {#1} {#2} {#3} { } { } { }
8226 }
8227 \cs_new:Npn \_msg_kernel_expandable_error:nn #1#2
8228 {
8229   \_msg_kernel_expandable_error:nnnnnn
8230   {#1} {#2} { } { } { } { }
8231 }

```

(End definition for `_msg_kernel_expandable_error:nnnnnn` and others.)

15.7 Showing variables

Functions defined in this section are used for diagnostic functions in `l3clist`, `l3file`, `l3prop`, `l3seq`, `xtemplate`

`\g__msg_log_next_bool`
`_msg_log_next:`

```

8232 \bool_new:N \g__msg_log_next_bool
8233 \cs_new_protected:Npn \_msg_log_next:
8234 { \bool_gset_true:N \g__msg_log_next_bool }

```

(End definition for `\g__msg_log_next_bool` and `_msg_log_next:`)

`_msg_show_pre:nnnnnn`
`_msg_show_pre:nnxxxx`
`_msg_show_pre:nnnnnV`
`_msg_show_pre_aux:n`

Print the text of a message to the terminal or log file without formatting: short cuts around `\iow_wrap:nnnN`. The choice of terminal or log file is done by `_msg_show_pre_aux:n`.

```

8235 \cs_new_protected:Npn \_msg_show_pre:nnnnnn #1#2#3#4#5#6
8236 {
8237   \exp_args:Nx \iow_wrap:nnnN
8238   {
8239     \exp_not:c { \c__msg_text_prefix_tl #1 / #2 }

```

```

8240         { \tl_to_str:n {#3} }
8241         { \tl_to_str:n {#4} }
8242         { \tl_to_str:n {#5} }
8243         { \tl_to_str:n {#6} }
8244     }
8245     { } { } \__msg_show_pre_aux:n
8246 }
8247 \cs_new_protected:Npn \__msg_show_pre:nnxxxx #1#2#3#4#5#6
8248 {
8249     \use:x
8250     { \exp_not:n { \__msg_show_pre:nnnnnn {#1} {#2} } {#3} {#4} {#5} {#6} }
8251 }
8252 \cs_generate_variant:Nn \__msg_show_pre:nnnnnn { nnnnnV }
8253 \cs_new_protected:Npn \__msg_show_pre_aux:n
8254 { \bool_if:NTF \g__msg_log_next_bool { \iow_log:n } { \iow_term:n } }

```

(End definition for __msg_show_pre:nnnnnn and __msg_show_pre_aux:n.)

__msg_show_variable:NNNnn The arguments of __msg_show_variable:NNNnn are

- The *⟨variable⟩* to be shown as #1.
- An *⟨if-exist⟩* conditional #2 with NTF signature.
- An *⟨if-empty⟩* conditional #3 or other function with NTF signature (sometimes \use_ii:nnn).
- The *⟨message⟩* #4 to use.
- A construction #5 which produces the formatted string eventually passed to the \showtokens primitive. Typically this is a mapping of the form \seq_map_function:NN *⟨variable⟩* __msg_show_item:n.

If *⟨if-exist⟩* *⟨variable⟩* is false, throw an error and remember to reset \g__msg_log_next_bool, which is otherwise reset by __msg_show_wrap:n. If *⟨message⟩* is not empty, output the message LaTeX/kernel/show-*⟨message⟩* with as its arguments the *⟨variable⟩*, and either an empty second argument or ? depending on the result of *⟨if-empty⟩* *⟨variable⟩*. Afterwards, show the contents of #5 using __msg_show_wrap:n or __msg_log_wrap:n.

```

8255 \cs_new_protected:Npn \__msg_show_variable:NNNnn #1#2#3#4#5
8256 {
8257     #2 #1
8258     {
8259         \tl_if_empty:nF {#4}
8260         {
8261             \__msg_show_pre:nnxxxx { LaTeX / kernel } { show- #4 }
8262             { \token_to_str:N #1 } { #3 #1 { } { ? } } { } { }
8263         }
8264         \__msg_show_wrap:n {#5}
8265     }
8266     {
8267         \__msg_kernel_error:nnx { kernel } { variable-not-defined }
8268         { \token_to_str:N #1 }
8269         \bool_gset_false:N \g__msg_log_next_bool
8270     }
8271 }

```

(End definition for `_msg_show_variable:Nnnn`.)

`_msg_show_wrap:Nn` A short-hand used for `\int_show:n` and many other functions that passes to `_msg_show_wrap:n` the result of applying #1 (a function such as `\int_eval:n`) to the expression #2. The leading `>~` is needed by `_msg_show_wrap:n`. The use of x-expansion ensures that #1 is expanded in the scope in which the show command is called, rather than in the group created by `\iow_wrap:nnnN`. This is only important for expressions involving the `\currentgrouplevel` or `\currentgrouptype`. On the other hand we want the expression to be converted to a string with the usual escape character, hence within the wrapping code.

```

8272 \cs_new_protected:Npn \_msg\_show\_wrap:Nn #1#2
8273 {
8274   \exp_args:Nx \_msg\_show\_wrap:n
8275   {
8276     > ~ \exp_not:n { \tl_to_str:n {#2} } =
8277     \exp_not:N \tl_to_str:n { #1 {#2} }
8278   }
8279 }
```

(End definition for `_msg_show_wrap:Nn`.)

`_msg_show_wrap:n` The argument of `_msg_show_wrap:n` is line-wrapped using `\iow_wrap:nnnN`. Everything before the first `>` in the wrapped text is removed, as well as an optional space following it (because of f-expansion). In order for line-wrapping to give the correct result, the first `>` must in fact appear at the beginning of a line and be followed by a space (or a line-break), so in practice, the argument of `_msg_show_wrap:n` begins with `>~` or `\>~`.

The line-wrapped text is then either sent to the log file through `\iow_log:x`, or shown in the terminal using the ε -TeX primitive `\showtokens` after removing a leading `>~` and trailing dot since those are added automatically by `\showtokens`. The trailing dot was included in the first place because its presence can affect line-wrapping. Note that the space after `>` is removed through f-expansion rather than by using an argument delimited by `>~` because the space may have been replaced by a line-break when line-wrapping.

A special case is that if the line-wrapped text is a single dot (in other words if the argument of `_msg_show_wrap:n` x-expands to nothing) then no `>~` should be removed. This makes it unnecessary to check explicitly for emptiness when using for instance `\seq_map_function:NN` $\langle seq\ var \rangle$ `_msg_show_item:n` as the argument of `_msg_show_wrap:n`.

Finally, the token list `\l_msg_internal_tl` containing the result of all these manipulations is displayed to the terminal using `\etex_showtokens:D` and odd `\exp_after:wN` which expand the closing brace to improve the output slightly. The calls to `_iow_with:Nnn` ensure that the `\newlinechar` is set to 10 so that the `\iow_newline:` inserted by the line-wrapping code are correctly recognized by TeX, and that `\errorcontextlines` is `-1` to avoid printing irrelevant context.

Note also that `\g_msg_log_next_bool` is only reset if that is necessary. This allows the user of an interactive prompt to insert tokens as a response to ε -TeX's `\showtokens`.

```

8280 \cs_new_protected:Npn \_msg\_show\_wrap:n #1
8281 { \iow\_wrap:nnnN { #1 . } { } { } \_msg\_show\_wrap\_aux:n }
8282 \cs_new_protected:Npn \_msg\_show\_wrap\_aux:n #1
8283 {
8284   \tl\_if\_single:nTF {#1}
```

```

8285     { \tl_clear:N \l__msg_internal_tl }
8286     { \tl_set:Nf \l__msg_internal_tl { \__msg_show_wrap_aux:w #1 \q_stop } }
8287 \bool_if:NTF \g__msg_log_next_bool
8288 {
8289     \iow_log:x { > ~ \l__msg_internal_tl . }
8290     \bool_gset_false:N \g__msg_log_next_bool
8291 }
8292 {
8293     \__iow_with:Nnn \tex_newlinechar:D { 10 }
8294     {
8295         \__iow_with:Nnn \tex_errorcontextlines:D { -1 }
8296         {
8297             \etex_showtokens:D \exp_after:wN \exp_after:wN \exp_after:wN
8298             { \exp_after:wN \l__msg_internal_tl }
8299         }
8300     }
8301 }
8302 }
8303 \cs_new:Npn \__msg_show_wrap_aux:w #1 > #2 . \q_stop {#2}

```

(End definition for `__msg_show_wrap:n`, `__msg_show_wrap_aux:n`, and `__msg_show_wrap_aux:w`.)

Each item in the variable is formatted using one of the following functions.

```

8304 \cs_new:Npn \__msg_show_item:n #1
8305 {
8306     \> \ \ \{ \tl_to_str:n {#1} \}
8307 }
8308 \cs_new:Npn \__msg_show_item:nn #1#2
8309 {
8310     \> \ \ \{ \tl_to_str:n {#1} \}
8311     \ \ => \ \ \{ \tl_to_str:n {#2} \}
8312 }
8313 \cs_new:Npn \__msg_show_item_unbraced:nn #1#2
8314 {
8315     \> \ \ \tl_to_str:n {#1}
8316     \ \ => \ \ \tl_to_str:n {#2}
8317 }

```

(End definition for `__msg_show_item:n`, `__msg_show_item:nn`, and `__msg_show_item_unbraced:nn`.)

```

8318 </initex | package>

```

16 l3file implementation

The following test files are used for this code: `m3file001`.

```

8319 <*initex | package>
8320 <@@=file>

```

16.1 File operations

`\g_file_current_name_tl` The name of the current file should be available at all times. For the format the file name needs to be picked up at the start of the file. In L^AT_EX 2_ε package mode the current file name is collected from `\@currname`.


```

8321 \tl_new:N \g_file_current_name_tl
8322 <*\initex>
8323 \tex_everyjob:D \exp_after:wN
8324 {
8325   \tex_the:D \tex_everyjob:D
8326   \tl_gset:Nx \g_file_current_name_tl { \tex_jobname:D }
8327 }
8328 </initex>
8329 <*\package>
8330 \cs_if_exist:NT \@currname
8331 { \tl_gset_eq:NN \g_file_current_name_tl \@currname }
8332 </package>

```

(End definition for `\g_file_current_name_tl`. This variable is documented on page 136.)

`\g__file_stack_seq` The input list of files is stored as a sequence stack.

```

8333 \seq_new:N \g__file_stack_seq

```

(End definition for `\g__file_stack_seq`.)

`\g__file_record_seq` The total list of files used is recorded separately from the current file stack, as nothing is ever popped from this list. The current file name should be included in the file list! In format mode, this is done at the very start of the \TeX run. In package mode we will eventually copy the contents of `\@filelist`.

```

8334 \seq_new:N \g__file_record_seq
8335 <*\initex>
8336 \tex_everyjob:D \exp_after:wN
8337 {
8338   \tex_the:D \tex_everyjob:D
8339   \seq_gput_right:NV \g__file_record_seq \g_file_current_name_tl
8340 }
8341 </initex>

```

(End definition for `\g__file_record_seq`.)

`\l__file_internal_tl` Used as a short-term scratch variable. It may be possible to reuse `\l__file_internal_name_tl` there.

```

8342 \tl_new:N \l__file_internal_tl

```

(End definition for `\l__file_internal_tl`.)

`\l__file_internal_name_tl` Used to return the fully-qualified name of a file.

```

8343 \tl_new:N \l__file_internal_name_tl

```

(End definition for `\l__file_internal_name_tl`.)

`\l__file_search_path_seq` The current search path.

```

8344 \seq_new:N \l__file_search_path_seq

```

(End definition for `\l__file_search_path_seq`.)

`\l__file_saved_search_path_seq` The current search path has to be saved for package use.

```

8345 <*\package>
8346 \seq_new:N \l__file_saved_search_path_seq
8347 </package>

```

(End definition for \l__file_saved_search_path_seq.)

\l__file_internal_seq Scratch space for comma list conversion in package mode.

```

8348 \begin{package}
8349 \seq_new:N \l__file_internal_seq
8350 \end{package}

```

(End definition for \l__file_internal_seq.)

__file_name_sanitize:nn For converting a token list to a string where active characters are treated as strings from the start. The logic to the quoting normalisation is the same as used by lualatexquotejobname: check for balanced ", and assuming they balance strip all of them out before quoting the entire name if it contains spaces.

```

8351 \cs_new_protected:Npn \__file_name_sanitize:nn #1#2
8352 {
8353   \group_begin:
8354   \seq_map_inline:Nn \l_char_active_seq
8355   {
8356     \tl_set:Nx \l__file_internal_tl { \iow_char:N ##1 }
8357     \char_set_active_eq:NN ##1 \l__file_internal_tl
8358   }
8359   \tl_set:Nx \l__file_internal_name_tl {#1}
8360   \tl_set:Nx \l__file_internal_name_tl
8361   { \tl_to_str:N \l__file_internal_name_tl }
8362   \int_compare:nNnTF
8363   {
8364     \int_mod:nn
8365     {
8366       0 \tl_map_function:NN \l__file_internal_name_tl
8367       \__file_name_sanitize_aux:n
8368     }
8369     { 2 }
8370   }
8371   = 0
8372   {
8373     \tl_remove_all:Nn \l__file_internal_name_tl { " }
8374     \tl_if_in:NnT \l__file_internal_name_tl { ~ }
8375     {
8376       \tl_set:Nx \l__file_internal_name_tl
8377       { " \exp_not:V \l__file_internal_name_tl " }
8378     }
8379   }
8380   {
8381     \__msg_kernel_error:nnx
8382     { kernel } { unbalanced-quote-in-filename }
8383     { \l__file_internal_name_tl }
8384   }
8385   \use:x
8386   {
8387     \group_end:
8388     \exp_not:n {#2} { \l__file_internal_name_tl }
8389   }
8390 }
8391 \cs_new:Npn \__file_name_sanitize_aux:n #1

```

```
8392 { \token_if_eq_charcode:NNT #1 " { + 1 } }
```

(End definition for `_file_name_sanitize:n` and `_file_name_sanitize_aux:n`.)

`\file_add_path:nN` The way to test if a file exists is to try to open it: if it does not exist then TeX will report end-of-file. For files which are in the current directory, this is straight-forward.
`_file_add_path:nN` For other locations, a search has to be made looking at each potential path in turn. The
`_file_add_path_search:nN` first location is of course treated as the correct one. If nothing is found, #2 is returned empty.

```
8393 \cs_new_protected:Npn \file_add_path:nN #1
8394 { \_file_name_sanitize:nN {#1} { \_file_add_path:nN } }
8395 \cs_new_protected:Npn \_file_add_path:nN #1#2
8396 {
8397   \_ior_open:Nn \g__file_internal_ior {#1}
8398   \ior_if_eof:NTF \g__file_internal_ior
8399   { \_file_add_path_search:nN {#1} #2 }
8400   { \tl_set:Nn #2 {#1} }
8401   \ior_close:N \g__file_internal_ior
8402 }
8403 \cs_new_protected:Npn \_file_add_path_search:nN #1#2
8404 {
8405   \tl_set:Nn #2 { \q_no_value }
8406   (*package)
8407   \cs_if_exist:NT \input@path
8408   {
8409     \seq_set_eq:NN \l__file_saved_search_path_seq
8410     \l__file_search_path_seq
8411     \seq_set_split:NnV \l__file_internal_seq { , } \input@path
8412     \seq_concat:NNN \l__file_search_path_seq
8413     \l__file_search_path_seq \l__file_internal_seq
8414   }
8415   </package>
8416   \seq_map_inline:Nn \l__file_search_path_seq
8417   {
8418     \_ior_open:Nn \g__file_internal_ior { ##1 #1 }
8419     \ior_if_eof:NF \g__file_internal_ior
8420     {
8421       \tl_set:Nx #2 { ##1 #1 }
8422       \seq_map_break:
8423     }
8424   }
8425   (*package)
8426   \cs_if_exist:NT \input@path
8427   {
8428     \seq_set_eq:NN \l__file_search_path_seq
8429     \l__file_saved_search_path_seq
8430   }
8431   </package>
8432 }
```

(End definition for `\file_add_path:nN`, `_file_add_path:nN`, and `_file_add_path_search:nN`. These functions are documented on page 136.)

`\file_if_exist:nTF` The test for the existence of a file is a wrapper around the function to add a path to a file. If the file was found, the path will contain something, whereas if the file was not located then the return value will be `\q_no_value`.

```

8433 \prg_new_protected_conditional:Npnn \file_if_exist:n #1 { T , F , TF }
8434 {
8435   \file_add_path:nN {#1} \l__file_internal_name_tl
8436   \quark_if_no_value:NTF \l__file_internal_name_tl
8437   { \prg_return_false: }
8438   { \prg_return_true: }
8439 }

```

(End definition for `\file_if_exist:nTF`. This function is documented on page 136.)

`\file_input:n` Loading a file is done in a safe way, checking first that the file exists and loading only if it does. Push the file name on the `\g__file_stack_seq`, and add it to the file list, either `\g__file_record_seq`, or `\@filelist` in package mode.

```

\__file_if_exist:nT
\__file_input:n
\__file_input:V
\__file_input_aux:n
\__file_input_aux:o
8440 \cs_new_protected:Npn \file_input:n #1
8441 {
8442   \__file_if_exist:nT {#1}
8443   { \__file_input:V \l__file_internal_name_tl }
8444 }

```

This code is spun out as a separate function to encapsulate the error message into a easy-to-reuse form.

```

8445 \cs_new_protected:Npn \__file_if_exist:nT #1#2
8446 {
8447   \file_if_exist:nTF {#1}
8448   {#2}
8449   {
8450     \__file_name_sanitize:nn {#1}
8451     { \_msg_kernel_error:nnx { kernel } { file-not-found } }
8452   }
8453 }
8454 \cs_new_protected:Npn \__file_input:n #1
8455 {
8456   \tl_if_in:nnTF {#1} { . }
8457   { \__file_input_aux:n {#1} }
8458   { \__file_input_aux:o { \tl_to_str:n { #1 . tex } } }
8459 }
8460 \cs_generate_variant:Nn \__file_input:n { V }
8461 \cs_new_protected:Npn \__file_input_aux:n #1
8462 {
8463   \*initex
8464   \seq_gput_right:Nn \g__file_record_seq {#1}
8465   \</initex
8466   \*package
8467   \clist_if_exist:NTF \@filelist
8468   { \@addtofilelist {#1} }
8469   { \seq_gput_right:Nn \g__file_record_seq {#1} }
8470   \</package
8471   \seq_gpush:No \g__file_stack_seq \g_file_current_name_tl
8472   \tl_gset:Nn \g_file_current_name_tl {#1}
8473   \tex_input:D #1 \c_space_tl
8474   \seq_gpop:NN \g__file_stack_seq \l__file_internal_tl

```

```

8475 \tl_gset_eq:NN \g_file_current_name_tl \l__file_internal_tl
8476 }
8477 \cs_generate_variant:Nn \__file_input_aux:n { o }

```

(End definition for `\file_input:n` and others. These functions are documented on page 136.)

```

\file_path_include:n Wrapper functions to manage the search path.
\file_path_remove:n
\__file_path_include:n
8478 \cs_new_protected:Npn \file_path_include:n #1
8479 { \__file_name_sanitiz:nn {#1} { \__file_path_include:n } }
8480 \cs_new_protected:Npn \__file_path_include:n #1
8481 {
8482   \seq_if_in:NnF \l__file_search_path_seq {#1}
8483   { \seq_put_right:Nn \l__file_search_path_seq {#1} }
8484 }
8485 \cs_new_protected:Npn \file_path_remove:n #1
8486 {
8487   \__file_name_sanitiz:nn {#1}
8488   { \seq_remove_all:Nn \l__file_search_path_seq }
8489 }

```

(End definition for `\file_path_include:n`, `\file_path_remove:n`, and `__file_path_include:n`. These functions are documented on page 136.)

\file_list: A function to list all files used to the log, without duplicates. In package mode, if `\@filelist` is still defined, we need to take this list of file names into account (we capture it `\AtBeginDocument` into `\g__file_record_seq`), turning each file name into a string.

```

8490 \cs_new_protected:Npn \file_list:
8491 {
8492   \seq_set_eq:NN \l__file_internal_seq \g__file_record_seq
8493   (*package)
8494   \clist_if_exist:NT \@filelist
8495   {
8496     \clist_map_inline:Nn \@filelist
8497     {
8498       \seq_put_right:No \l__file_internal_seq
8499       { \tl_to_str:n {##1} }
8500     }
8501   }
8502   (/package)
8503   \seq_remove_duplicates:N \l__file_internal_seq
8504   \iow_log:n { *~File~List~* }
8505   \seq_map_inline:Nn \l__file_internal_seq { \iow_log:n {##1} }
8506   \iow_log:n { ***** }
8507 }

```

(End definition for `\file_list:`. This function is documented on page 137.)

When used as a package, there is a need to hold onto the standard file list as well as the new one here. File names recorded in `\@filelist` must be turned to strings before being added to `\g__file_record_seq`.

```

8508 (*package)
8509 \AtBeginDocument
8510 {
8511   \clist_map_inline:Nn \@filelist

```

```

8512     { \seq_gput_right:No \g__file_record_seq { \tl_to_str:n {#1} } }
8513   }
8514 \endpackage

```

16.2 Input operations

```
8515 \@@=ior
```

16.2.1 Variables and constants

\c_term_ior Reading from the terminal (with a prompt) is done using a positive but non-existent stream number. Unlike writing, there is no concept of reading from the log.

```
8516 \int_const:Nn \c_term_ior { 16 }
```

(End definition for \c_term_ior. This variable is documented on page 142.)

\g__ior_streams_seq A list of the currently-available input streams to be used as a stack. In format mode, all streams (from 0 to 15) are available, while the package requests streams to L^AT_EX 2_ε as they are needed (initially none are needed), so the starting point varies!

```

8517 \seq_new:N \g__ior_streams_seq
8518 \*initex
8519 \seq_gset_split:Nnn \g__ior_streams_seq { , }
8520 { 0 , 1 , 2 , 3 , 4 , 5 , 6 , 7 , 8 , 9 , 10 , 11 , 12 , 13 , 14 , 15 }
8521 \*initex

```

(End definition for \g__ior_streams_seq.)

\l__ior_stream_tl Used to recover the raw stream number from the stack.

```
8522 \tl_new:N \l__ior_stream_tl
```

(End definition for \l__ior_stream_tl.)

\g__ior_streams_prop The name of the file attached to each stream is tracked in a property list. To get the correct number of reserved streams in package mode the underlying mechanism needs to be queried. For L^AT_EX 2_ε and plain T_EX this data is stored in \count16: with the etex package loaded we need to subtract 1 as the register holds the number of the next stream to use. In ConT_EXt, we need to look at \count38 but there is no subtraction: like the original plain T_EX/L^AT_EX 2_ε mechanism it holds the value of the *last* stream allocated.

```

8523 \prop_new:N \g__ior_streams_prop
8524 \*package
8525 \int_step_inline:nnnn
8526 { 0 }
8527 { 1 }
8528 {
8529   \cs_if_exist:NTF \normalend
8530   { \tex_count:D 38 \scan_stop: }
8531   {
8532     \tex_count:D 16 \scan_stop:
8533     \cs_if_exist:NT \loccount { - 1 }
8534   }
8535 }
8536 {
8537   \prop_gput:Nnn \g__ior_streams_prop {#1} { Reserved-by~format }
8538 }
8539 \endpackage

```

(End definition for \g__ior_streams_prop.)

16.2.2 Stream management

\ior_new:N Reserving a new stream is done by defining the name as equal to using the terminal.

```
\ior_new:c      8540 \cs_new_protected:Npn \ior_new:N #1 { \cs_new_eq:NN #1 \c_term_ior }
                8541 \cs_generate_variant:Nn \ior_new:N { c }
```

(End definition for \ior_new:N. This function is documented on page 137.)

\ior_open:Nn Opening an input stream requires a bit of pre-processing. The file name is sanitized to deal with active characters, before an auxiliary adds a path and checks that the file really exists. If those two tests pass, then pass the information on to the lower-level function which deals with streams.

\ior_open:cn
__ior_open_aux:Nn

```
8542 \cs_new_protected:Npn \ior_open:Nn #1#2
8543 { \__file_name_sanitiz:nn {#2} { \__ior_open_aux:Nn #1 } }
8544 \cs_generate_variant:Nn \ior_open:Nn { c }
8545 \cs_new_protected:Npn \__ior_open_aux:Nn #1#2
8546 {
8547   \file_add_path:nN {#2} \l__file_internal_name_tl
8548   \quark_if_no_value:NTF \l__file_internal_name_tl
8549   { \__msg_kernel_error:nxx { kernel } { file-not-found } {#2} }
8550   { \__ior_open:No #1 \l__file_internal_name_tl }
8551 }
```

(End definition for \ior_open:Nn and __ior_open_aux:Nn. These functions are documented on page 137.)

\ior_open:NnTF Much the same idea for opening a read with a conditional, except the auxiliary function does not issue an error if the file is not found.

\ior_open:cnTF
__ior_open_aux:NnTF

```
8552 \prg_new_protected_conditional:Npnn \ior_open:Nn #1#2 { T , F , TF }
8553 { \__file_name_sanitiz:nn {#2} { \__ior_open_aux:NnTF #1 } }
8554 \cs_generate_variant:Nn \ior_open:NnT { c }
8555 \cs_generate_variant:Nn \ior_open:NnF { c }
8556 \cs_generate_variant:Nn \ior_open:NnTF { c }
8557 \cs_new_protected:Npn \__ior_open_aux:NnTF #1#2
8558 {
8559   \file_add_path:nN {#2} \l__file_internal_name_tl
8560   \quark_if_no_value:NTF \l__file_internal_name_tl
8561   { \prg_return_false: }
8562   {
8563     \__ior_open:No #1 \l__file_internal_name_tl
8564     \prg_return_true:
8565   }
8566 }
```

(End definition for \ior_open:NnTF and __ior_open_aux:NnTF. These functions are documented on page 137.)

__ior_new:N In package mode, streams are reserved using \newread before they can be managed by \ior. To prevent \ior from being affected by redefinitions of \newread (such as done by the third-party package morewrites), this macro is saved here under a private name. The complicated code ensures that __ior_new:N is not \outer despite plain TeX's \newread being \outer.

```
8567 \*package)
8568 \exp_args:NNf \cs_new_protected:Npn \__ior_new:N
8569 { \exp_args:Nnc \exp_after:wN \exp_stop_f: { newread } }
8570 \*package)
```

(End definition for `_ior_new:N`.)

`_ior_open:Nn` The stream allocation itself uses the fact that there is a list of all of those available, so
`_ior_open:No` allocation is simply a question of using the number at the top of the list. In package
`_ior_open_stream:Nn` mode, life gets more complex as it's important to keep things in sync. That is done using
a two-part approach: any streams that have already been taken up by `ior` but are now
free are tracked, so we first try those. If that fails, ask plain `TeX` or `LATeX 2ε` for a new
stream and use that number (after a bit of conversion).

```

8571 \cs_new_protected:Npn \_ior_open:Nn #1#2
8572 {
8573   \ior_close:N #1
8574   \seq_gpop:NNTF \g__ior_streams_seq \l__ior_stream_tl
8575   { \_ior_open_stream:Nn #1 {#2} }
8576   \*initex
8577   { \_msg_kernel_fatal:nn { kernel } { input-streams-exhausted } }
8578   \*initex
8579   \*package
8580   {
8581     \_ior_new:N #1
8582     \tl_set:Nx \l__ior_stream_tl { \int_eval:n {#1} }
8583     \_ior_open_stream:Nn #1 {#2}
8584   }
8585   \*package
8586 }
8587 \cs_generate_variant:Nn \_ior_open:Nn { No }
8588 \cs_new_protected:Npn \_ior_open_stream:Nn #1#2
8589 {
8590   \tex_global:D \tex_chardef:D #1 = \l__ior_stream_tl \scan_stop:
8591   \prop_gput:NVn \g__ior_streams_prop #1 {#2}
8592   \tex_openin:D #1 #2 \scan_stop:
8593 }

```

(End definition for `_ior_open:Nn` and `_ior_open_stream:Nn`.)

`\ior_close:N` Closing a stream means getting rid of it at the `TeX` level and removing from the various
`\ior_close:c` data structures. Unless the name passed is an invalid stream number (outside the range
`[0, 15]`), it can be closed. On the other hand, it only gets added to the stack if it was not
already there, to avoid duplicates building up.

```

8594 \cs_new_protected:Npn \ior_close:N #1
8595 {
8596   \int_compare:nT { -1 < #1 < \c_term_ior }
8597   {
8598     \tex_closein:D #1
8599     \prop_gremove:NV \g__ior_streams_prop #1
8600     \seq_if_in:NVF \g__ior_streams_seq #1
8601     { \seq_gpush:NV \g__ior_streams_seq #1 }
8602     \cs_gset_eq:NN #1 \c_term_ior
8603   }
8604 }
8605 \cs_generate_variant:Nn \ior_close:N { c }

```

(End definition for `\ior_close:N`. This function is documented on page 138.)

\ior_list_streams: Show the property lists, but with some “pretty printing”. See the `l3msg` module. The first argument of the message is `ior` (as opposed to `iow`) and the second is empty if no read stream is open and non-empty (in fact a question mark) otherwise. The code of the message `show-streams` takes care of translating `ior/iow` to English. The list of streams is formatted using `__msg_show_item_unbraced:nn`.

```

8606 \cs_new_protected:Npn \ior_list_streams:
8607 { \__ior_list_streams:Nn \g__ior_streams_prop { ior } }
8608 \cs_new_protected:Npn \__ior_list_streams:Nn #1#2
8609 {
8610   \__msg_show_pre:nnxxxx { LaTeX / kernel } { show-streams }
8611   {#2} { \prop_if_empty:NF #1 { ? } } { } { }
8612   \__msg_show_wrap:n
8613   { \prop_map_function:NN #1 \__msg_show_item_unbraced:nn }
8614 }

```

(End definition for `\ior_list_streams:` and `__ior_list_streams:Nn`. These functions are documented on page 138.)

16.2.3 Reading input

\if_eof:w The primitive conditional

```

8615 \cs_new_eq:NN \if_eof:w \tex_ifeof:D

```

(End definition for `\if_eof:w`.)

\ior_if_eof_p:N To test if some particular input stream is exhausted the following conditional is provided.
\ior_if_eof:NTF The primitive test can only deal with numbers in the range $[0, 15]$ so we catch outliers (they are exhausted).

```

8616 \prg_new_conditional:Npnn \ior_if_eof:N #1 { p , T , F , TF }
8617 {
8618   \cs_if_exist:NTF #1
8619   {
8620     \int_compare:nTF { -1 < #1 < \c_term_ior }
8621     {
8622       \if_eof:w #1
8623       \prg_return_true:
8624       \else:
8625       \prg_return_false:
8626       \fi:
8627     }
8628     { \prg_return_true: }
8629   }
8630   { \prg_return_true: }
8631 }

```

(End definition for `\ior_if_eof:NTF`. This function is documented on page 139.)

\ior_get:NN And here we read from files.

```

8632 \cs_new_protected:Npn \ior_get:NN #1#2
8633 { \tex_read:D #1 to #2 }

```

(End definition for `\ior_get:NN`. This function is documented on page 138.)

`\ior_str_get:NN` Reading as strings is a more complicated wrapper, as we wish to remove the endline character.

```

8634 \cs_new_protected:Npn \ior_str_get:NN #1#2
8635 {
8636   \use:x
8637   {
8638     \int_set:Nn \tex_endlinechar:D { -1 }
8639     \exp_not:n { \etex_readline:D #1 to #2 }
8640     \int_set:Nn \tex_endlinechar:D { \int_use:N \tex_endlinechar:D }
8641   }
8642 }
```

(End definition for `\ior_str_get:NN`. This function is documented on page 139.)

`\g__file_internal_ior` Needed by the higher-level code, but cannot be created until here.

```

8643 \ior_new:N \g__file_internal_ior
```

(End definition for `\g__file_internal_ior`.)

16.3 Output operations

```

8644 <@@=iow>
```

There is a lot of similarity here to the input operations, at least for many of the basics. Thus quite a bit is copied from the earlier material with minor alterations.

16.3.1 Variables and constants

`\c_log_iow` Here we allocate two output streams for writing to the transcript file only (`\c_log_iow`)
`\c_term_iow` and to both the terminal and transcript file (`\c_term_iow`). Recent LuaTeX provide 128 write streams; we also use `\c_term_iow` as the first non-allowed write stream so its value depends on the engine.

```

8645 \int_const:Nn \c_log_iow { -1 }
8646 \int_const:Nn \c_term_iow
8647 {
8648   \cs_if_exist:NTF \luatex_directlua:D
8649   {
8650     \int_compare:nNnTF \luatex luatexversion:D > { 80 }
8651     { 128 }
8652     { 16 }
8653   }
8654   { 16 }
8655 }
```

(End definition for `\c_log_iow` and `\c_term_iow`. These variables are documented on page 142.)

`\g_iow_streams_seq` A list of the currently-available output streams to be used as a stack.

```

8656 \seq_new:N \g_iow_streams_seq
8657 <*initex>
8658 \use:x
8659 {
8660   \exp_not:n { \seq_gset_split:Nnn \g_iow_streams_seq { } }
8661   {
8662     \int_step_function:nnnN { 0 } { 1 } { \c_term_iow }
8663     \prg_do_nothing:
```

```

8664     }
8665   }
8666 </initex>

(End definition for \g__iow_streams_seq.)

```

\l__iow_stream_tl Used to recover the raw stream number from the stack.

```

8667 \tl_new:N \l__iow_stream_tl

(End definition for \l__iow_stream_tl.)

```

\g__iow_streams_prop As for reads with the appropriate adjustment of the register numbers to check on.

```

8668 \prop_new:N \g__iow_streams_prop
8669 <*package>
8670 \int_step_inline:nnnn
8671   { 0 }
8672   { 1 }
8673   {
8674     \cs_if_exist:NTF \normalend
8675     { \tex_count:D 39 \scan_stop: }
8676     {
8677       \tex_count:D 17 \scan_stop:
8678       \cs_if_exist:NT \loccount { - 1 }
8679     }
8680   }
8681   {
8682     \prop_gput:Nnn \g__iow_streams_prop {#1} { Reserved-by~format }
8683   }
8684 </package>

(End definition for \g__iow_streams_prop.)

```

16.4 Stream management

\iow_new:N Reserving a new stream is done by defining the name as equal to writing to the terminal:
\iow_new:c odd but at least consistent.

```

8685 \cs_new_protected:Npn \iow_new:N #1 { \cs_new_eq:NN #1 \c_term_iow }
8686 \cs_generate_variant:Nn \iow_new:N { c }

(End definition for \iow_new:N. This function is documented on page 137.)

```

__iow_new:N As for read streams, copy \newwrite in package mode, making sure that it is not \outer.

```

8687 <*package>
8688 \exp_args:NNf \cs_new_protected:Npn \__iow_new:N
8689   { \exp_args:NNc \exp_after:wN \exp_stop_f: { newwrite } }
8690 </package>

(End definition for \__iow_new:N.)

```

\iow_open:Nn The same idea as for reading, but without the path and without the need to allow for a conditional version.

```

\iow_open:cn
\__iow_open:Nn
\__iow_open_stream:Nn
8691 \cs_new_protected:Npn \iow_open:Nn #1#2
8692   { \__file_name_sanitise:nn {#2} { \__iow_open:Nn #1 } }
8693 \cs_generate_variant:Nn \iow_open:Nn { c }
8694 \cs_new_protected:Npn \__iow_open:Nn #1#2

```

```

8695 {
8696   \iow_close:N #1
8697   \seq_gpop:NNTF \g__iow_streams_seq \l__iow_stream_tl
8698   { \__iow_open_stream:Nn #1 {#2} }
8699   \*initex
8700   { \__msg_kernel_fatal:nn { kernel } { output-streams-exhausted } }
8701   \*package
8702   {
8703     \__iow_new:N #1
8704     \tl_set:Nx \l__iow_stream_tl { \int_eval:n {#1} }
8705     \__iow_open_stream:Nn #1 {#2}
8706   }
8707 \*package
8708 }
8709 \cs_generate_variant:Nn \__iow_open:Nn { No }
8710 \cs_new_protected:Npn \__iow_open_stream:Nn #1#2
8711 {
8712   \tex_global:D \tex_chardef:D #1 = \l__iow_stream_tl \scan_stop:
8713   \prop_gput:Nvn \g__iow_streams_prop #1 {#2}
8714   \tex_immediate:D \tex_openout:D #1 #2 \scan_stop:
8715 }
8716 }

```

(End definition for `\iow_open:Nn`, `__iow_open:Nn`, and `__iow_open_stream:Nn`. These functions are documented on page 137.)

`\iow_close:N` Closing a stream is not quite the reverse of opening one. First, the close operation is easier than the open one, and second as the stream is actually a number we can use it directly to show that the slot has been freed up.

`\iow_close:c`

```

8717 \cs_new_protected:Npn \iow_close:N #1
8718 {
8719   \int_compare:nT { - \c_log_iow < #1 < \c_term_iow }
8720   {
8721     \tex_immediate:D \tex_closeout:D #1
8722     \prop_gremove:Nv \g__iow_streams_prop #1
8723     \seq_if_in:NvF \g__iow_streams_seq #1
8724     { \seq_gpush:Nv \g__iow_streams_seq #1 }
8725     \cs_gset_eq:NN #1 \c_term_iow
8726   }
8727 }
8728 \cs_generate_variant:Nn \iow_close:N { c }

```

(End definition for `\iow_close:N`. This function is documented on page 138.)

`\iow_list_streams:` Done as for input, but with a copy of the auxiliary so the name is correct.

`__iow_list_streams:Nn`

```

8729 \cs_new_protected:Npn \iow_list_streams:
8730 { \__iow_list_streams:Nn \g__iow_streams_prop { iow } }
8731 \cs_new_eq:NN \__iow_list_streams:Nn \__ior_list_streams:Nn

```

(End definition for `\iow_list_streams:` and `__iow_list_streams:Nn`. These functions are documented on page 138.)

16.4.1 Deferred writing

`\iow_shipout_x:Nn` First the easy part, this is the primitive, which expects its argument to be braced.

```

\iow_shipout_x:Nx 8732 \cs_new_protected:Npn \iow_shipout_x:Nn #1#2
\iow_shipout_x:cn 8733 { \tex_write:D #1 {#2} }
\iow_shipout_x:cx 8734 \cs_generate_variant:Nn \iow_shipout_x:Nn { c, Nx, cx }
```

(End definition for `\iow_shipout_x:Nn`. This function is documented on page 140.)

`\iow_shipout:Nn` With ε -TeX available deferred writing without expansion is easy.

```

\iow_shipout:Nx 8735 \cs_new_protected:Npn \iow_shipout:Nn #1#2
\iow_shipout:cn 8736 { \tex_write:D #1 { \exp_not:n {#2} } }
\iow_shipout:cx 8737 \cs_generate_variant:Nn \iow_shipout:Nn { c, Nx, cx }
```

(End definition for `\iow_shipout:Nn`. This function is documented on page 139.)

16.4.2 Immediate writing

`__iow_with:Nnn` If the integer #1 is equal to #2, just leave #3 in the input stream. Otherwise, pass the old value to an auxiliary, which sets the integer to the new value, runs the code, and restores the integer.

```

8738 \cs_new_protected:Npn \__iow_with:Nnn #1#2
8739 {
8740   \int_compare:nNnTF {#1} = {#2}
8741   { \use:n }
8742   { \exp_args:No \__iow_with_aux:nNnn { \int_use:N #1 } #1 {#2} }
8743 }
8744 \cs_new_protected:Npn \__iow_with_aux:nNnn #1#2#3#4
8745 {
8746   \int_set:Nn #2 {#3}
8747   #4
8748   \int_set:Nn #2 {#1}
8749 }
```

(End definition for `__iow_with:Nnn` and `__iow_with_aux:nNnn`.)

`\iow_now:Nn` This routine writes the second argument onto the output stream without expansion. If this stream isn't open, the output goes to the terminal instead. If the first argument is no output stream at all, we get an internal error. We don't use the expansion done by `\write` to get the Nx variant, because it differs in subtle ways from x-expansion, namely, macro parameter characters would not need to be doubled. We set the `\newlinechar` to 10 using `__iow_with:Nnn` to support formats such as plain TeX: otherwise, `\iow_newline:` would not work. We do not do this for `\iow_shipout:Nn` or `\iow_shipout_x:Nn`, as TeX looks at the value of the `\newlinechar` at shipout time in those cases.

```

8750 \cs_new_protected:Npn \iow_now:Nn #1#2
8751 {
8752   \__iow_with:Nnn \tex_newlinechar:D { '\^^J }
8753   { \tex_immediate:D \tex_write:D #1 { \exp_not:n {#2} } }
8754 }
8755 \cs_generate_variant:Nn \iow_now:Nn { c, Nx, cx }
```

(End definition for `\iow_now:Nn`. This function is documented on page 139.)

`\iow_log:n` Writing to the log and the terminal directly are relatively easy.

`\iow_log:x` 8756 `\cs_set_protected:Npn \iow_log:x { \iow_now:Nx \c_log_iow }`

`\iow_term:n` 8757 `\cs_new_protected:Npn \iow_log:n { \iow_now:Nn \c_log_iow }`

`\iow_term:x` 8758 `\cs_set_protected:Npn \iow_term:x { \iow_now:Nx \c_term_iow }`

 8759 `\cs_new_protected:Npn \iow_term:n { \iow_now:Nn \c_term_iow }`

(End definition for `\iow_log:n` and `\iow_term:n`. These functions are documented on page 139.)

16.4.3 Special characters for writing

`\iow_newline:` Global variable holding the character that forces a new line when something is written to an output stream.

8760 `\cs_new:Npn \iow_newline: { ^^J }`

(End definition for `\iow_newline:`. This function is documented on page 140.)

`\iow_char:N` Function to write any escaped char to an output stream.

8761 `\cs_new_eq:NN \iow_char:N \cs_to_str:N`

(End definition for `\iow_char:N`. This function is documented on page 140.)

16.4.4 Hard-wrapping lines to a character count

The code here implements a generic hard-wrapping function. This is used by the messaging system, but is designed such that it is available for other uses.

`\c_catcode_other_space_tl` Create a space with category code 12: an “other” space.

8762 `\tl_const:Nx \c_catcode_other_space_tl { \char_generate:nn { \ } { 12 } }`

(End definition for `\c_catcode_other_space_tl`. This function is documented on page 141.)

`\l_iow_line_count_int` This is the “raw” number of characters in a line which can be written to the terminal. The standard value is the line length typically used by T_EXLive and MikT_EX.

8763 `\int_new:N \l_iow_line_count_int`

8764 `\int_set:Nn \l_iow_line_count_int { 78 }`

(End definition for `\l_iow_line_count_int`. This variable is documented on page 141.)

`\l__iow_newline_tl` The token list inserted to produce a new line, with the *⟨run-on text⟩*.

8765 `\tl_new:N \l__iow_newline_tl`

(End definition for `\l__iow_newline_tl`.)

`\l__iow_line_target_int` This stores the target line count: the full number of characters in a line, minus any part for a leader at the start of each line.

8766 `\int_new:N \l__iow_line_target_int`

(End definition for `\l__iow_line_target_int`.)

`__iow_set_indent:n` The `one_indent` variables hold one indentation marker and its length. The `__iow_unindent:w` auxiliary removes one indentation. The function `__iow_set_indent:n` (that could possibly be public) sets the indentation in a consistent way. We set it to four spaces by default.

```

8767 \tl_new:N \l__iow_one_indent_tl
8768 \int_new:N \l__iow_one_indent_int
8769 \cs_new:Npn \__iow_unindent:w { }
8770 \cs_new_protected:Npn \__iow_set_indent:n #1
8771 {
8772   \tl_set:Nx \l__iow_one_indent_tl
8773     { \exp_args:No \__str_to_other_fast:n { \tl_to_str:n {#1} } }
8774   \int_set:Nn \l__iow_one_indent_int { \str_count:N \l__iow_one_indent_tl }
8775   \exp_last_unbraced:NNo
8776     \cs_set:Npn \__iow_unindent:w \l__iow_one_indent_tl { }
8777 }
8778 \exp_args:Nx \__iow_set_indent:n { \prg_replicate:nn { 4 } { ~ } }

```

(End definition for `__iow_set_indent:n` and others.)

`\l__iow_indent_tl` The current indentation (some copies of `\l__iow_one_indent_tl`) and its number of
`\l__iow_indent_int` characters.

```

8779 \tl_new:N \l__iow_indent_tl
8780 \int_new:N \l__iow_indent_int

```

(End definition for `\l__iow_indent_tl` and `\l__iow_indent_int`.)

`\l__iow_line_tl` These hold the current line of text and a partial line to be added to it, respectively.
`\l__iow_line_part_tl`

```

8781 \tl_new:N \l__iow_line_tl
8782 \tl_new:N \l__iow_line_part_tl

```

(End definition for `\l__iow_line_tl` and `\l__iow_line_part_tl`.)

`\l__iow_line_break_bool` Indicates whether the line was broken precisely at a chunk boundary.

```

8783 \bool_new:N \l__iow_line_break_bool

```

(End definition for `\l__iow_line_break_bool`.)

`\l__iow_wrap_tl` Used for the expansion step before detokenizing, and for the output from wrapping text: fully expanded and with lines which are not overly long.

```

8784 \tl_new:N \l__iow_wrap_tl

```

(End definition for `\l__iow_wrap_tl`.)

`\c__iow_wrap_marker_tl` Every special action of the wrapping code is starts with the same recognizable string,
`\c__iow_wrap_end_marker_tl` `\c__iow_wrap_marker_tl`. Upon seeing that “word”, the wrapping code reads one space-
`\c__iow_wrap_newline_marker_tl` delimited argument to know what operation to perform. The setting of `\escapechar` here
`\c__iow_wrap_indent_marker_tl` is not very important, but makes `\c__iow_wrap_marker_tl` look marginally nicer.

```

8785 \group_begin:
8786   \int_set:Nn \tex_escapechar:D { -1 }
8787   \tl_const:Nx \c__iow_wrap_marker_tl
8788     { \tl_to_str:n { \^^I \^^O \^^W \^^_ \^^W \^^R \^^A \^^P } }
8789 \group_end:
8790 \tl_map_inline:nn
8791   { { end } { newline } { indent } { unindent } }

```

```

8792 {
8793   \tl_const:cx { c__iow_wrap_ #1 _marker_tl }
8794   {
8795     \c__iow_wrap_marker_tl
8796     #1
8797     \c_catcode_other_space_tl
8798   }
8799 }

```

(End definition for `\c__iow_wrap_marker_tl` and others.)

`\iow_indent:n` We set `\iow_indent:n` to produce an error when outside messages. Within wrapped message, it is set to `__iow_indent:n` when valid and otherwise to `__iow_indent_error:n`.
`__iow_indent:n` The first places the instruction for increasing the indentation before its argument, and
`__iow_indent_error:n` the instruction for unindenting afterwards. The second produces an error expandably. Note that there will be no forced line-break, so the indentation only changes when the next line is started.

```

8800 \cs_new_protected:Npn \iow_indent:n #1
8801 {
8802   \__msg_kernel_error:nnnnn { kernel } { iow-indent }
8803   { \iow_wrap:nnnN } { \iow_indent:n } { #1 }
8804   #1
8805 }
8806 \cs_new:Npx \__iow_indent:n #1
8807 {
8808   \c__iow_wrap_indent_marker_tl
8809   #1
8810   \c__iow_wrap_unindent_marker_tl
8811 }
8812 \cs_new:Npn \__iow_indent_error:n #1
8813 {
8814   \__msg_kernel_expandable_error:nnnnn { kernel } { iow-indent }
8815   { \iow_wrap:nnnN } { \iow_indent:n } { #1 }
8816   #1
8817 }

```

(End definition for `\iow_indent:n`, `__iow_indent:n`, and `__iow_indent_error:n`. These functions are documented on page 141.)

`\iow_wrap:nnnN` The main wrapping function works as follows. First give `\`, `_` and other formatting
`__iow_wrap_set:Nx` commands the correct definition for messages and perform the given setup #3. The definition of `_` uses an “other” space rather than a normal space, because the latter might be absorbed by `TeX` to end a number or other f-type expansions.

```

8818 \cs_new_protected:Npn \iow_wrap:nnnN #1#2#3#4
8819 {
8820   \group_begin:
8821   \int_set:Nn \tex_escapechar:D { -1 }
8822   \cs_set:Npx \{ { \token_to_str:N \{ }
8823   \cs_set:Npx \# { \token_to_str:N \# }
8824   \cs_set:Npx \} { \token_to_str:N \} }
8825   \cs_set:Npx \% { \token_to_str:N \% }
8826   \cs_set:Npx \~ { \token_to_str:N \~ }
8827   \int_set:Nn \tex_escapechar:D { 92 }
8828   \cs_set_eq:NN \ \ \c__iow_wrap_newline_marker_tl

```



```

8829 \cs_set_eq:NN \ \c_catcode_other_space_tl
8830 \cs_set_eq:NN \iow_indent:n \__iow_indent:n
8831 #3

```

Then fully-expand the input: in package mode, the expansion uses L^AT_EX 2_ε’s `\protected` mechanism. As soon as the expansion is done, reset `\iow_indent:n` to its error definition: it only works in the first argument of `\iow_wrap:nnnN`.

```

8832 <*initex>
8833 \tl_set:Nx \l__iow_wrap_tl {#1}
8834 </initex>
8835 <*package>
8836 \__iow_wrap_set:Nx \l__iow_wrap_tl {#1}
8837 </package>
8838 \cs_set_eq:NN \iow_indent:n \__iow_indent_error:n

```

Afterwards, set the newline marker (two assignments to fully expand, then convert to a string) and initialize the target count for lines (the first line has target count `\l_iow_line_count_int` instead).

```

8839 \tl_set:Nx \l__iow_newline_tl { \iow_newline: #2 }
8840 \tl_set:Nx \l__iow_newline_tl { \tl_to_str:N \l__iow_newline_tl }
8841 \int_set:Nn \l__iow_line_target_int
8842 { \l_iow_line_count_int - \str_count:N \l__iow_newline_tl + 1 }

```

There is then a loop over the input, which will store the wrapped result in `\l__iow_wrap_tl`. After the loop, the resulting text is passed on to the function which has been given as a post-processor. The `\tl_to_str:N` step converts the “other” spaces back to normal spaces. The `f`-expansion removes a leading space from `\l__iow_wrap_tl`.

```

8843 \__iow_wrap_do:
8844 \exp_args:Nnf \group_end:
8845 #4 { \tl_to_str:N \l__iow_wrap_tl }
8846 }

```

As using the generic loader will mean that `\protected@edef` is not available, it’s not placed directly in the wrap function but is set up as an auxiliary. In the generic loader this can then be redefined.

```

8847 <*package>
8848 \cs_new_eq:NN \__iow_wrap_set:Nx \protected@edef
8849 </package>

```

(End definition for `\iow_wrap:nnnN` and `__iow_wrap_set:Nx`. These functions are documented on page 141.)

```

\__iow_wrap_do:
\__iow_wrap_start:w

```

Escape spaces. Set up a few variables, in particular the initial value of `\l__iow_wrap_tl`: the space will stop the `f`-expansion of the main wrapping function and `\use_none:n` will remove a newline marker inserted by later code. The main loop consists of repeatedly calling the `chunk` auxiliary to wrap chunks delimited by (newline or indentation) markers.

```

8850 \cs_new_protected:Npn \__iow_wrap_do:
8851 {
8852 \tl_set:Nx \l__iow_wrap_tl
8853 {
8854 \exp_args:No \__str_to_other_fast:n \l__iow_wrap_tl
8855 \c__iow_wrap_end_marker_tl
8856 }
8857 \exp_after:wN \__iow_wrap_start:w \l__iow_wrap_tl
8858 }

```

```

8859 \cs_new_protected:Npn \__iow_wrap_start:w
8860 {
8861   \bool_set_false:N \l__iow_line_break_bool
8862   \tl_clear:N \l__iow_line_tl
8863   \tl_clear:N \l__iow_line_part_tl
8864   \tl_set:Nn \l__iow_wrap_tl { ~ \use_none:n }
8865   \int_zero:N \l__iow_indent_int
8866   \tl_clear:N \l__iow_indent_tl
8867   \__iow_wrap_chunk:nw { \l__iow_line_count_int }
8868 }

```

(End definition for __iow_wrap_do: and __iow_wrap_start:w.)

__iow_wrap_chunk:nw The chunk and next auxiliaries are defined indirectly to obtain the expansions of \c_catcode_other_space_tl and \c__iow_wrap_marker_tl in their definition. The next auxiliary calls a function corresponding to the type of marker (its ##2), which can be newline or indent or unindent or end. The first argument of the chunk auxiliary is a target number of characters and the second is some string to wrap. If the chunk is empty simply call next. Otherwise, set up a call to __iow_wrap_line:nw, including the indentation if the current line is empty, and including a trailing space (#1) before the __iow_wrap_end_chunk:w auxiliary.

```

8869 \cs_set_protected:Npn \__iow_tmp:w #1#2
8870 {
8871   \cs_new_protected:Npn \__iow_wrap_chunk:nw ##1##2 #2
8872   {
8873     \tl_if_empty:NTF {##2}
8874     {
8875       \tl_clear:N \l__iow_line_part_tl
8876       \__iow_wrap_next:nw {##1}
8877     }
8878     {
8879       \tl_if_empty:NTF \l__iow_line_tl
8880       {
8881         \__iow_wrap_line:nw
8882         { \l__iow_indent_tl }
8883         ##1 - \l__iow_indent_int ;
8884       }
8885       { \__iow_wrap_line:nw { } ##1 ; }
8886       ##2 #1
8887       \__iow_wrap_end_chunk:w 7 6 5 4 3 2 1 0 \q_stop
8888     }
8889   }
8890   \cs_new_protected:Npn \__iow_wrap_next:nw ##1##2 #1
8891   { \use:c { __iow_wrap_##2:n } {##1} }
8892 }
8893 \exp_args:NVV \__iow_tmp:w \c_catcode_other_space_tl \c__iow_wrap_marker_tl

```

(End definition for __iow_wrap_chunk:nw and __iow_wrap_next:nw.)

__iow_wrap_line:nw This is followed by {<string>}<intexpr>;. It stores the <string> and up to <intexpr> characters from the current chunk into \l__iow_line_part_tl. Characters are grabbed 8 at a time and left in \l__iow_line_part_tl by the line_loop auxiliary. When $k < 8$ remain to be found, the line_aux auxiliary calls the line_end auxiliary followed by (the single digit) k , then $7 - k$ empty brace groups, then the chunk's remaining characters.

__iow_wrap_line_loop:w

__iow_wrap_line_aux:Nw

__iow_wrap_line_end:NnnnnnnN

__iow_wrap_line_end:nw

__iow_wrap_end_chunk:w

The `line_end` auxiliary leaves k characters from the chunk in the line part, then ends the assignment. Ignore the `\use_none:nnnnn` line for now. If the next character is a space the line can be broken there: store what we found into the result and get the next line. Otherwise some work is needed to find a break-point. So far we have ignored what happens if the chunk is shorter than the requested number of characters: this is dealt with by the `end_chunk` auxiliary, which gets treated like a character by the rest of the code. It ends up being called either as one of the arguments #2-#9 of the `line_loop` auxiliary or as one of the arguments #2-#8 of the `line_end` auxiliary. In both cases stop the assignment and work out how many characters are still needed. The weird `\use_none:nnnnn` ensures that the required data is in the right place.

```

8894 \cs_new_protected:Npn \__iow_wrap_line:nw #1
8895 {
8896   \tex_edef:D \l__iow_line_part_tl { \if_false: } \fi:
8897   #1
8898   \exp_after:wN \__iow_wrap_line_loop:w
8899   \__int_value:w \__int_eval:w
8900 }
8901 \cs_new:Npn \__iow_wrap_line_loop:w #1 ; #2#3#4#5#6#7#8#9
8902 {
8903   \if_int_compare:w #1 < 8 \exp_stop_f:
8904     \__iow_wrap_line_aux:Nw #1
8905   \fi:
8906   #2 #3 #4 #5 #6 #7 #8 #9
8907   \exp_after:wN \__iow_wrap_line_loop:w
8908   \__int_value:w \__int_eval:w #1 - 8 ;
8909 }
8910 \cs_new:Npn \__iow_wrap_line_aux:Nw #1#2#3 \exp_after:wN #4 ;
8911 {
8912   #2
8913   \exp_after:wN \__iow_wrap_line_end:NnnnnnnnN
8914   \exp_after:wN #1
8915   \exp:w \exp_end_continue_f:w
8916   \exp_after:wN \exp_after:wN
8917   \if_case:w #1 \exp_stop_f:
8918     \prg_do_nothing:
8919   \or: \use_none:n
8920   \or: \use_none:nn
8921   \or: \use_none:nnn
8922   \or: \use_none:nnnn
8923   \or: \use_none:nnnnn
8924   \or: \use_none:nnnnnn
8925   \or: \use_none:nnnnnnn
8926   \fi:
8927   { } { } { } { } { } { } { } { } { } #3
8928 }
8929 \cs_new:Npn \__iow_wrap_line_end:NnnnnnnnN #1#2#3#4#5#6#7#8#9
8930 {
8931   #2 #3 #4 #5 #6 #7 #8
8932   \use_none:nnnnn \__int_eval:w 8 - ; #9
8933   \token_if_eq_charcode:NNTF \c_space_token #9
8934     { \__iow_wrap_line_end:nw { } }
8935     { \if_false: { \fi: } \__iow_wrap_break:w #9 }
8936 }

```

```

8937 \cs_new:Npn \__iow_wrap_line_end:nw #1
8938 {
8939   \if_false: { \fi: }
8940   \__iow_wrap_store_do:n {#1}
8941   \__iow_wrap_next_line:w
8942 }
8943 \cs_new:Npn \__iow_wrap_end_chunk:w
8944 #1 \__int_eval:w #2 - #3 ; #4#5 \q_stop
8945 {
8946   \if_false: { \fi: }
8947   \exp_args:Nf \__iow_wrap_next:nw { \int_eval:n { #2 - #4 } }
8948 }

```

(End definition for __iow_wrap_line:nw and others.)

__iow_wrap_break:w Functions here are defined indirectly: __iow_tmp:w is eventually called with an “other”
 __iow_wrap_break_first:w space as its argument. The goal is to remove from \l__iow_line_part_tl the part
 __iow_wrap_break_none:w after the last space. In most cases this is done by repeatedly calling the **break_loop**
 __iow_wrap_break_loop:w auxiliary, which leaves “words” (delimited by spaces) until it hits the trailing space: then
 __iow_wrap_break_end:w its argument **##3** is ? __iow_wrap_break_end:w instead of a single token, and that
break_end auxiliary leaves in the assignment the line until the last space, then calls
 __iow_wrap_line_end:nw to finish up the line and move on to the next. If there is
 no space in \l__iow_line_part_tl then the **break_first** auxiliary calls the **break_**
none auxiliary. In that case, if the current line is empty, the complete word (including
##4, characters beyond what we had grabbed) is added to the line, making it over-long.
 Otherwise, the word will be used for the following line (and the last space of the line so
 far is removed because it was inserted due to the presence of a marker).

```

8949 \cs_set_protected:Npn \__iow_tmp:w #1
8950 {
8951   \cs_new:Npn \__iow_wrap_break:w
8952   {
8953     \tex_edef:D \l__iow_line_part_tl
8954     { \if_false: } \fi:
8955     \exp_after:wN \__iow_wrap_break_first:w
8956     \l__iow_line_part_tl
8957     #1
8958     { ? \__iow_wrap_break_end:w }
8959     \q_mark
8960   }
8961   \cs_new:Npn \__iow_wrap_break_first:w ##1 #1 ##2
8962   {
8963     \use_none:nn ##2 \__iow_wrap_break_none:w
8964     \__iow_wrap_break_loop:w ##1 #1 ##2
8965   }
8966   \cs_new:Npn \__iow_wrap_break_none:w ##1##2 #1 ##3 \q_mark ##4 #1
8967   {
8968     \tl_if_empty:NTF \l__iow_line_tl
8969     { ##2 ##4 \__iow_wrap_line_end:nw { } }
8970     { \__iow_wrap_line_end:nw { \__iow_wrap_trim:N } ##2 ##4 #1 }
8971   }
8972   \cs_new:Npn \__iow_wrap_break_loop:w ##1 #1 ##2 #1 ##3
8973   {
8974     \use_none:n ##3

```

```

8975     ##1 #1
8976     \__iow_wrap_break_loop:w ##2 #1 ##3
8977 }
8978 \cs_new:Npn \__iow_wrap_break_end:w ##1 #1 ##2 ##3 #1 ##4 \q_mark
8979 { ##1 \__iow_wrap_line_end:nw { } ##3 }
8980 }
8981 \exp_args:NV \__iow_tmp:w \c_catcode_other_space_tl

```

(End definition for __iow_wrap_break:w and others.)

__iow_wrap_next_line:w The special case where the end of a line coincides with the end of a chunk is detected here, to avoid a spurious empty line. Otherwise, call __iow_wrap_line:nw to find characters for the next line (remembering to account for the indentation).

```

8982 \cs_new_protected:Npn \__iow_wrap_next_line:w #1#2 \q_stop
8983 {
8984   \tl_clear:N \l__iow_line_tl
8985   \token_if_eq_meaning:NNTF #1 \__iow_wrap_end_chunk:w
8986   {
8987     \tl_clear:N \l__iow_line_part_tl
8988     \bool_set_true:N \l__iow_line_break_bool
8989     \__iow_wrap_next:nw { \l__iow_line_target_int }
8990   }
8991   {
8992     \__iow_wrap_line:nw
8993     { \l__iow_indent_tl }
8994     \l__iow_line_target_int - \l__iow_indent_int ;
8995     #1 #2 \q_stop
8996   }
8997 }

```

(End definition for __iow_wrap_next_line:w.)

__iow_wrap_indent: These functions are called after a chunk has been wrapped, when encountering **indent/unindent** markers. Add the line part (last line part of the previous chunk) to the line so far and reset a boolean denoting the presence of a line-break. Most importantly, add or remove one indent from the current indent (both the integer and the token list). Finally, continue wrapping.

```

8998 \cs_new_protected:Npn \__iow_wrap_indent:n #1
8999 {
9000   \tl_put_right:Nx \l__iow_line_tl { \l__iow_line_part_tl }
9001   \bool_set_false:N \l__iow_line_break_bool
9002   \int_add:Nn \l__iow_indent_int { \l__iow_one_indent_int }
9003   \tl_put_right:No \l__iow_indent_tl { \l__iow_one_indent_tl }
9004   \__iow_wrap_chunk:nw {#1}
9005 }
9006 \cs_new_protected:Npn \__iow_wrap_unindent:n #1
9007 {
9008   \tl_put_right:Nx \l__iow_line_tl { \l__iow_line_part_tl }
9009   \bool_set_false:N \l__iow_line_break_bool
9010   \int_sub:Nn \l__iow_indent_int { \l__iow_one_indent_int }
9011   \tl_set:Nx \l__iow_indent_tl
9012   { \exp_after:wN \__iow_unindent:w \l__iow_indent_tl }
9013   \__iow_wrap_chunk:nw {#1}
9014 }

```

(End definition for _iow_wrap_indent: and _iow_wrap_unindent:.)

_iow_wrap_newline: These functions are called after a chunk has been line-wrapped, when encountering a
 _iow_wrap_end: newline/end marker. Unless we just took a line-break, store the line part and the line
 so far into the whole \l_iow_wrap_tl, trimming a trailing space. In the newline case
 look for a new line (of length \l_iow_line_target_int) in a new chunk.

```

9015 \cs_new_protected:Npn \_iow_wrap_newline:n #1
9016 {
9017   \bool_if:NF \l\_iow_line_break_bool
9018     { \_iow_wrap_store_do:n { \_iow_wrap_trim:N } }
9019   \bool_set_false:N \l\_iow_line_break_bool
9020   \_iow_wrap_chunk:nw { \l\_iow_line_target_int }
9021 }
9022 \cs_new_protected:Npn \_iow_wrap_end:n #1
9023 {
9024   \bool_if:NF \l\_iow_line_break_bool
9025     { \_iow_wrap_store_do:n { \_iow_wrap_trim:N } }
9026   \bool_set_false:N \l\_iow_line_break_bool
9027 }

```

(End definition for _iow_wrap_newline: and _iow_wrap_end:.)

_iow_wrap_store_do:n First add the last line part to the line, then append it to \l_iow_wrap_tl with the
 appropriate new line (with “run-on” text), possibly with its last space removed (#1 is
 empty or _iow_wrap_trim:N).

```

9028 \cs_new_protected:Npn \_iow_wrap_store_do:n #1
9029 {
9030   \tl_set:Nx \l\_iow_line_tl
9031     { \l\_iow_line_tl \l\_iow_line_part_tl }
9032   \tl_set:Nx \l\_iow_wrap_tl
9033     {
9034       \l\_iow_wrap_tl
9035       \l\_iow_newline_tl
9036       #1 \l\_iow_line_tl
9037     }
9038   \tl_clear:N \l\_iow_line_tl
9039 }

```

(End definition for _iow_wrap_store_do:n.)

_iow_wrap_trim:N Remove one trailing “other” space from the argument.

```

\_iow_wrap_trim:w
9040 \cs_set_protected:Npn \_iow_tmp:w #1
9041 {
9042   \cs_new:Npn \_iow_wrap_trim:N ##1
9043     { \tl_if_empty:NF ##1 { \exp_after:wN \_iow_wrap_trim:w ##1 \q_stop } }
9044   \cs_new:Npn \_iow_wrap_trim:w ##1 #1 \q_stop {##1}
9045 }
9046 \exp_args:NV \_iow_tmp:w \c_catcode_other_space_tl

```

(End definition for _iow_wrap_trim:N and _iow_wrap_trim:w.)

16.5 Messages

```

9047 \__msg_kernel_new:nnnn { kernel } { file-not-found }
9048 { File~'#1'~not-found. }
9049 {
9050   The-requested-file-could-not-be-found-in-the-current-directory,~
9051   in-the-Tex-search-path-or-in-the-LaTeX-search-path.
9052 }
9053 \__msg_kernel_new:nnnn { kernel } { input-streams-exhausted }
9054 { Input-streams-exhausted }
9055 {
9056   Tex-can-only-open-up-to-16-input-streams-at-one-time.\\
9057   All-16-are-currently-in-use,~and-something-wanted-to-open-
9058   another-one.
9059 }
9060 \__msg_kernel_new:nnnn { kernel } { output-streams-exhausted }
9061 { Output-streams-exhausted }
9062 {
9063   Tex-can-only-open-up-to-16-output-streams-at-one-time.\\
9064   All-16-are-currently-in-use,~and-something-wanted-to-open-
9065   another-one.
9066 }
9067 \__msg_kernel_new:nnnn { kernel } { unbalanced-quote-in-filename }
9068 { Unbalanced-quotes-in-file-name~'#1'. }
9069 {
9070   File-names-must-contain-balanced-numbers-of-quotes~(").
9071 }
9072 \__msg_kernel_new:nnnn { kernel } { iow-indent }
9073 { Only~#1 (arg-1)~allows~#2 }
9074 {
9075   The-command~#2 can-only-be-used-in-messages~
9076   which-will-be-wrapped-using~#1.~
9077   It-was-called-with-argument~'#3'.
9078 }

```

16.6 Deprecated functions

\ior_get_str:NN For removal after 2017-12-31.

```

9079 \cs_new_protected:Npn \ior_get_str:NN
9080 {
9081   \__msg_kernel_warning:nxxxx { kernel } { deprecated-command }
9082   { 2017-12-31 }
9083   { \token_to_str:N \ior_get_str:NN }
9084   { \token_to_str:N \ior_str_get:NN }
9085   \cs_gset_eq:NN \ior_get_str:NN \ior_str_get:NN
9086   \ior_str_get:NN
9087 }

```

(End definition for \ior_get_str:NN.)

```

9088 </initex | package>

```

17 l3skip implementation

```

9089 (*initex | package>

```

9090 <@@=dim>

17.1 Length primitives renamed

\if_dim:w Primitives renamed.
__dim_eval:w 9091 \cs_new_eq:NN \if_dim:w \tex_ifdim:D
__dim_eval_end: 9092 \cs_new_eq:NN __dim_eval:w \etex_dimexpr:D
9093 \cs_new_eq:NN __dim_eval_end: \tex_relax:D

(End definition for \if_dim:w, __dim_eval:w, and __dim_eval_end:. These functions are documented on page 157.)

17.2 Creating and initialising dim variables

\dim_new:N Allocating <dim> registers ...
\dim_new:c 9094 <*package>
9095 \cs_new_protected:Npn \dim_new:N #1
9096 {
9097 __chk_if_free_cs:N #1
9098 \cs:w newdimen \cs_end: #1
9099 }
9100 </package>
9101 \cs_generate_variant:Nn \dim_new:N { c }

(End definition for \dim_new:N. This function is documented on page 144.)

\dim_const:Nn Contrarily to integer constants, we cannot avoid using a register, even for constants.
\dim_const:cn 9102 \cs_new_protected:Npn \dim_const:Nn #1
9103 {
9104 \dim_new:N #1
9105 \dim_gset:Nn #1
9106 }
9107 \cs_generate_variant:Nn \dim_const:Nn { c }

(End definition for \dim_const:Nn. This function is documented on page 144.)

\dim_zero:N Reset the register to zero.
\dim_zero:c 9108 \cs_new_protected:Npn \dim_zero:N #1 { #1 \c_zero_dim }
\dim_gzero:N 9109 \cs_new_protected:Npn \dim_gzero:N { \tex_global:D \dim_zero:N }
\dim_gzero:c 9110 \cs_generate_variant:Nn \dim_zero:N { c }
9111 \cs_generate_variant:Nn \dim_gzero:N { c }

(End definition for \dim_zero:N and \dim_gzero:N. These functions are documented on page 144.)

\dim_zero_new:N Create a register if needed, otherwise clear it.
\dim_zero_new:c 9112 \cs_new_protected:Npn \dim_zero_new:N #1
\dim_gzero_new:N 9113 { \dim_if_exist:NTF #1 { \dim_zero:N #1 } { \dim_new:N #1 } }
\dim_gzero_new:c 9114 \cs_new_protected:Npn \dim_gzero_new:N #1
9115 { \dim_if_exist:NTF #1 { \dim_gzero:N #1 } { \dim_new:N #1 } }
9116 \cs_generate_variant:Nn \dim_zero_new:N { c }
9117 \cs_generate_variant:Nn \dim_gzero_new:N { c }

(End definition for \dim_zero_new:N and \dim_gzero_new:N. These functions are documented on page 144.)

\dim_if_exist_p:N Copies of the cs functions defined in l3basics.

```

\dim_if_exist_p:c 9118 \prg_new_eq_conditional:Nn \dim_if_exist:N \cs_if_exist:N
\dim_if_exist:NTF 9119 { TF , T , F , p }
\dim_if_exist:cTF 9120 \prg_new_eq_conditional:Nn \dim_if_exist:c \cs_if_exist:c
9121 { TF , T , F , p }

```

(End definition for \dim_if_exist:N~~TF~~. This function is documented on page 144.)

17.3 Setting dim variables

\dim_set:Nn Setting dimensions is easy enough.

```

\dim_set:cn 9122 \cs_new_protected:Npn \dim_set:Nn #1#2
\dim_gset:Nn 9123 { #1 ~ \__dim_eval:w #2 \__dim_eval_end: }
\dim_gset:cn 9124 \cs_new_protected:Npn \dim_gset:Nn { \tex_global:D \dim_set:Nn }
9125 \cs_generate_variant:Nn \dim_set:Nn { c }
9126 \cs_generate_variant:Nn \dim_gset:Nn { c }

```

(End definition for \dim_set:Nn and \dim_gset:Nn. These functions are documented on page 145.)

\dim_set_eq:NN All straightforward.

```

\dim_set_eq:cn 9127 \cs_new_protected:Npn \dim_set_eq:NN #1#2 { #1 = #2 }
\dim_set_eq:Nc 9128 \cs_generate_variant:Nn \dim_set_eq:NN { c }
\dim_set_eq:cc 9129 \cs_generate_variant:Nn \dim_set_eq:NN { Nc , cc }
\dim_gset_eq:Nn 9130 \cs_new_protected:Npn \dim_gset_eq:NN #1#2 { \tex_global:D #1 = #2 }
\dim_gset_eq:cn 9131 \cs_generate_variant:Nn \dim_gset_eq:NN { c }
\dim_gset_eq:Nc 9132 \cs_generate_variant:Nn \dim_gset_eq:NN { Nc , cc }
\dim_gset_eq:cc

```

(End definition for \dim_set_eq:NN and \dim_gset_eq:NN. These functions are documented on page 145.)

\dim_add:Nn Using by here deals with the (incorrect) case \dimen123.

```

\dim_add:cn 9133 \cs_new_protected:Npn \dim_add:Nn #1#2
\dim_gadd:Nn 9134 { \tex_advance:D #1 by \__dim_eval:w #2 \__dim_eval_end: }
\dim_gadd:cn 9135 \cs_new_protected:Npn \dim_gadd:Nn { \tex_global:D \dim_add:Nn }
\dim_sub:Nn 9136 \cs_generate_variant:Nn \dim_add:Nn { c }
\dim_sub:cn 9137 \cs_generate_variant:Nn \dim_gadd:Nn { c }
\dim_gsub:Nn 9138 \cs_new_protected:Npn \dim_sub:Nn #1#2
\dim_gsub:cn 9139 { \tex_advance:D #1 by - \__dim_eval:w #2 \__dim_eval_end: }
9140 \cs_new_protected:Npn \dim_gsub:Nn { \tex_global:D \dim_sub:Nn }
9141 \cs_generate_variant:Nn \dim_sub:Nn { c }
9142 \cs_generate_variant:Nn \dim_gsub:Nn { c }

```

(End definition for \dim_add:Nn and others. These functions are documented on page 145.)

17.4 Utilities for dimension calculations

\dim_abs:n Functions for min, max, and absolute value with only one evaluation. The absolute value is evaluated by removing a leading - if present.

```

\__dim_abs:N 9143 \cs_new:Npn \dim_abs:n #1
\dim_max:nn 9144 {
\dim_min:nn 9145 { \exp_after:wN \__dim_abs:N
\__dim_maxmin:wwN 9146 \dim_use:N \__dim_eval:w #1 \__dim_eval_end:
9147 }
9148 \cs_new:Npn \__dim_abs:N #1

```

```

9149 { \if_meaning:w - #1 \else: \exp_after:wN #1 \fi: }
9150 \cs_new:Npn \dim_max:nn #1#2
9151 {
9152   \dim_use:N \__dim_eval:w \exp_after:wN \__dim_maxmin:wwN
9153   \dim_use:N \__dim_eval:w #1 \exp_after:wN ;
9154   \dim_use:N \__dim_eval:w #2 ;
9155   >
9156   \__dim_eval_end:
9157 }
9158 \cs_new:Npn \dim_min:nn #1#2
9159 {
9160   \dim_use:N \__dim_eval:w \exp_after:wN \__dim_maxmin:wwN
9161   \dim_use:N \__dim_eval:w #1 \exp_after:wN ;
9162   \dim_use:N \__dim_eval:w #2 ;
9163   <
9164   \__dim_eval_end:
9165 }
9166 \cs_new:Npn \__dim_maxmin:wwN #1 ; #2 ; #3
9167 {
9168   \if_dim:w #1 #3 #2 ~
9169   #1
9170   \else:
9171   #2
9172   \fi:
9173 }

```

(End definition for `\dim_abs:n` and others. These functions are documented on page 145.)

`\dim_ratio:nn` With dimension expressions, something like `10 pt * (5 pt / 10 pt)` will not work. `__dim_ratio:n` Instead, the ratio part needs to be converted to an integer expression. Using `__int_value:w` forces everything into `sp`, avoiding any decimal parts.

```

9174 \cs_new:Npn \dim_ratio:nn #1#2
9175 { \__dim_ratio:n {#1} / \__dim_ratio:n {#2} }
9176 \cs_new:Npn \__dim_ratio:n #1
9177 { \__int_value:w \__dim_eval:w #1 \__dim_eval_end: }

```

(End definition for `\dim_ratio:nn` and `__dim_ratio:n`. These functions are documented on page 146.)

17.5 Dimension expression conditionals

`\dim_compare_p:nNn` Simple comparison.

```

\dim_compare:nNnTF
9178 \prg_new_conditional:Npnn \dim_compare:nNn #1#2#3 { p , T , F , TF }
9179 {
9180   \if_dim:w \__dim_eval:w #1 #2 \__dim_eval:w #3 \__dim_eval_end:
9181   \prg_return_true: \else: \prg_return_false: \fi:
9182 }

```

(End definition for `\dim_compare:nNnTF`. This function is documented on page 146.)

`\dim_compare_p:n` This code is adapted from the `\int_compare:nTF` function. First make sure that there is
`\dim_compare:nTF` at least one relation operator, by evaluating a dimension expression with a trailing `__-`
`__dim_compare:w` `prg_compare_error:.` Just like for integers, the looping auxiliary `__dim_compare:wNN`
`__dim_compare:wNN` closes a primitive conditional and opens a new one. It is actually easier to grab a di-
`__dim_compare:=:w` mension operand than an integer one, because once evaluated, dimensions all end with
`__dim_compare!:w`
`__dim_compare<:w`
`__dim_compare>:w`

pt (with category other). Thus we do not need specific auxiliaries for the three “simple” relations <, =, and >.

```

9183 \prg_new_conditional:Npnn \dim_compare:n #1 { p , T , F , TF }
9184 {
9185     \exp_after:wN \__dim_compare:w
9186     \dim_use:N \__dim_eval:w #1 \__prg_compare_error:
9187 }
9188 \cs_new:Npn \__dim_compare:w #1 \__prg_compare_error:
9189 {
9190     \exp_after:wN \if_false: \exp:w \exp_end_continue_f:w
9191     \__dim_compare:wNN #1 ? { = \__dim_compare_end:w \else: } \q_stop
9192 }
9193 \exp_args:Nno \use:nn
9194 { \cs_new:Npn \__dim_compare:wNN #1 }
9195 { \tl_to_str:n {pt} }
9196 #2#3
9197 {
9198     \if_meaning:w = #3
9199     \use:c { __dim_compare_#2:w }
9200     \fi:
9201     #1 pt \exp_stop_f:
9202     \prg_return_false:
9203     \exp_after:wN \use_none_delimit_by_q_stop:w
9204     \fi:
9205     \reverse_if:N \if_dim:w #1 pt #2
9206     \exp_after:wN \__dim_compare:wNN
9207     \dim_use:N \__dim_eval:w #3
9208 }
9209 \cs_new:cpn { __dim_compare_! :w }
9210 #1 \reverse_if:N #2 ! #3 = { #1 #2 = #3 }
9211 \cs_new:cpn { __dim_compare_ = :w }
9212 #1 \__dim_eval:w = { #1 \__dim_eval:w }
9213 \cs_new:cpn { __dim_compare_ < :w }
9214 #1 \reverse_if:N #2 < #3 = { #1 #2 > #3 }
9215 \cs_new:cpn { __dim_compare_ > :w }
9216 #1 \reverse_if:N #2 > #3 = { #1 #2 < #3 }
9217 \cs_new:Npn \__dim_compare_end:w #1 \prg_return_false: #2 \q_stop
9218 { #1 \prg_return_false: \else: \prg_return_true: \fi: }

```

(End definition for \dim_compare:nTF and others. These functions are documented on page 147.)

| | |
|---|---|
| <pre> \dim_case:nn \dim_case:nnTF __dim_case:nnTF __dim_case:nw __dim_case_end:nw </pre> | <p>For dimension cases, the first task to fully expand the check condition. The over all idea is then much the same as for \str_case:nn(TF) as described in l3basics.</p> <pre> 9219 \cs_new:Npn \dim_case:nnTF #1 9220 { 9221 \exp:w 9222 \exp_args:Nf __dim_case:nnTF { \dim_eval:n {#1} } 9223 } 9224 \cs_new:Npn \dim_case:nnT #1#2#3 9225 { 9226 \exp:w 9227 \exp_args:Nf __dim_case:nnTF { \dim_eval:n {#1} } {#2} {#3} { } 9228 } 9229 \cs_new:Npn \dim_case:nnF #1#2 </pre> |
|---|---|

```

9230 {
9231   \exp:w
9232   \exp_args:Nf \__dim_case:nnTF { \dim_eval:n {#1} } {#2} { }
9233 }
9234 \cs_new:Npn \dim_case:nn #1#2
9235 {
9236   \exp:w
9237   \exp_args:Nf \__dim_case:nnTF { \dim_eval:n {#1} } {#2} { } { }
9238 }
9239 \cs_new:Npn \__dim_case:nnTF #1#2#3#4
9240 { \__dim_case:nw {#1} #2 {#1} { } \q_mark {#3} \q_mark {#4} \q_stop }
9241 \cs_new:Npn \__dim_case:nw #1#2#3
9242 {
9243   \dim_compare:nNnTF {#1} = {#2}
9244   { \__dim_case_end:nw {#3} }
9245   { \__dim_case:nw {#1} }
9246 }
9247 \cs_new_eq:NN \__dim_case_end:nw \__prg_case_end:nw

```

(End definition for `\dim_case:nnTF` and others. These functions are documented on page 148.)

17.6 Dimension expression loops

`\dim_while_do:nn` `while_do` and `do_while` functions for dimensions. Same as for the `int` type only the names have changed.

```

\dim_while_do:nn
\dim_until_do:nn
\dim_do_while:nn
\dim_do_until:nn
9248 \cs_new:Npn \dim_while_do:nn #1#2
9249 {
9250   \dim_compare:nT {#1}
9251   {
9252     #2
9253     \dim_while_do:nn {#1} {#2}
9254   }
9255 }
9256 \cs_new:Npn \dim_until_do:nn #1#2
9257 {
9258   \dim_compare:nF {#1}
9259   {
9260     #2
9261     \dim_until_do:nn {#1} {#2}
9262   }
9263 }
9264 \cs_new:Npn \dim_do_while:nn #1#2
9265 {
9266   #2
9267   \dim_compare:nT {#1}
9268   { \dim_do_while:nn {#1} {#2} }
9269 }
9270 \cs_new:Npn \dim_do_until:nn #1#2
9271 {
9272   #2
9273   \dim_compare:nF {#1}
9274   { \dim_do_until:nn {#1} {#2} }
9275 }

```

(End definition for `\dim_while_do:n` and others. These functions are documented on page 149.)

`\dim_while_do:nNnn` `while_do` and `do_while` functions for dimensions. Same as for the `int` type only the names have changed.

```

\dim_until_do:nNnn
\dim_do_while:nNnn
\dim_do_until:nNnn
9276 \cs_new:Npn \dim_while_do:nNnn #1#2#3#4
9277 {
9278   \dim_compare:nNnT {#1} #2 {#3}
9279   {
9280     #4
9281     \dim_while_do:nNnn {#1} #2 {#3} {#4}
9282   }
9283 }
9284 \cs_new:Npn \dim_until_do:nNnn #1#2#3#4
9285 {
9286   \dim_compare:nNnF {#1} #2 {#3}
9287   {
9288     #4
9289     \dim_until_do:nNnn {#1} #2 {#3} {#4}
9290   }
9291 }
9292 \cs_new:Npn \dim_do_while:nNnn #1#2#3#4
9293 {
9294   #4
9295   \dim_compare:nNnT {#1} #2 {#3}
9296   { \dim_do_while:nNnn {#1} #2 {#3} {#4} }
9297 }
9298 \cs_new:Npn \dim_do_until:nNnn #1#2#3#4
9299 {
9300   #4
9301   \dim_compare:nNnF {#1} #2 {#3}
9302   { \dim_do_until:nNnn {#1} #2 {#3} {#4} }
9303 }
```

(End definition for `\dim_while_do:nNnn` and others. These functions are documented on page 149.)

17.7 Using dim expressions and variables

`\dim_eval:n` Evaluating a dimension expression expandably.

```

9304 \cs_new:Npn \dim_eval:n #1
9305 { \dim_use:N \__dim_eval:w #1 \__dim_eval_end: }
```

(End definition for `\dim_eval:n`. This function is documented on page 149.)

`\dim_use:N` Accessing a $\langle dim \rangle$.

`\dim_use:c` `\cs_new_eq:NN \dim_use:N \tex_the:D`

We hand-code this for some speed gain:

```

9307 %\cs_generate_variant:Nn \dim_use:N { c }
9308 \cs_new:Npn \dim_use:c #1 { \tex_the:D \cs:w #1 \cs_end: }
```

(End definition for `\dim_use:N`. This function is documented on page 149.)

`\dim_to_decimal:n` A function which comes up often enough to deserve a place in the kernel. Evaluate the dimension expression `#1` then remove the trailing `pt`. The argument is put in parentheses as this prevents the dimension expression from terminating early and leaving extra tokens lying around. This is used a lot by low-level manipulations.

```

9309 \cs_new:Npn \dim_to_decimal:n #1
9310 {
9311   \exp_after:wN
9312   \__dim_to_decimal:w \dim_use:N \__dim_eval:w (#1) \__dim_eval_end:
9313 }
9314 \use:x
9315 {
9316   \cs_new:Npn \exp_not:N \__dim_to_decimal:w
9317     ##1 . ##2 \tl_to_str:n { pt }
9318 }
9319 {
9320   \int_compare:nNnTF {#2} > { 0 }
9321     { #1 . #2 }
9322     { #1 }
9323 }
```

(End definition for `\dim_to_decimal:n` and `__dim_to_decimal:w`. These functions are documented on page 150.)

`\dim_to_decimal_in_bp:n` Conversion to big points is done using a scaling inside `__dim_eval:w` as ε -TeX does that using 64-bit precision. Here, 800/803 is the integer fraction for 72/72.27. This is a common case so is hand-coded for accuracy (and speed).

```

9324 \cs_new:Npn \dim_to_decimal_in_bp:n #1
9325 { \dim_to_decimal:n { ( #1 ) * 800 / 803 } }
```

(End definition for `\dim_to_decimal_in_bp:n`. This function is documented on page 150.)

`\dim_to_decimal_in_sp:n` Another hard-coded conversion: this one is necessary to avoid things going off-scale.

```

9326 \cs_new:Npn \dim_to_decimal_in_sp:n #1
9327 { \int_eval:n { \__dim_eval:w #1 \__dim_eval_end: } }
```

(End definition for `\dim_to_decimal_in_sp:n`. This function is documented on page 150.)

`\dim_to_decimal_in_unit:nn` An analogue of `\dim_ratio:nn` that produces a decimal number as its result, rather than a rational fraction for use within dimension expressions.

```

9328 \cs_new:Npn \dim_to_decimal_in_unit:nn #1#2
9329 {
9330   \dim_to_decimal:n
9331   {
9332     1pt *
9333     \dim_ratio:nn {#1} {#2}
9334   }
9335 }
```

(End definition for `\dim_to_decimal_in_unit:nn`. This function is documented on page 150.)

`\dim_to_fp:n` Defined in `l3fp-convert`, documented here.

(End definition for `\dim_to_fp:n`. This function is documented on page 151.)

17.8 Viewing dim variables

\dim_show:N Diagnostics.

\dim_show:c 9336 \cs_new_eq:NN \dim_show:N __kernel_register_show:N
9337 \cs_generate_variant:Nn \dim_show:N { c }

(End definition for \dim_show:N. This function is documented on page 151.)

\dim_show:n Diagnostics. We don't use the TeX primitive `\showthe` to show dimension expressions: this gives a more unified output.

9338 \cs_new_protected:Npn \dim_show:n
9339 { __msg_show_wrap:Nn \dim_eval:n }

(End definition for \dim_show:n. This function is documented on page 151.)

\dim_log:N Diagnostics. Redirect output of `\dim_show:n` to the log.

\dim_log:c 9340 \cs_new_eq:NN \dim_log:N __kernel_register_log:N
\dim_log:n 9341 \cs_new_eq:NN \dim_log:c __kernel_register_log:c
9342 \cs_new_protected:Npn \dim_log:n
9343 { __msg_log_next: \dim_show:n }

(End definition for \dim_log:N and \dim_log:n. These functions are documented on page 151.)

17.9 Constant dimensions

\c_zero_dim Constant dimensions.

\c_max_dim 9344 \dim_const:Nn \c_zero_dim { 0 pt }
9345 \dim_const:Nn \c_max_dim { 16383.99999 pt }

(End definition for \c_zero_dim and \c_max_dim. These variables are documented on page 151.)

17.10 Scratch dimensions

\l_tmpa_dim We provide two local and two global scratch registers, maybe we need more or less.

\l_tmpp_dim 9346 \dim_new:N \l_tmpa_dim
\g_tmpa_dim 9347 \dim_new:N \l_tmpp_dim
\g_tmpp_dim 9348 \dim_new:N \g_tmpa_dim
9349 \dim_new:N \g_tmpp_dim

(End definition for \l_tmpa_dim and others. These variables are documented on page 151.)

17.11 Creating and initialising skip variables

\skip_new:N Allocation of a new internal registers.

\skip_new:c 9350 *package
9351 \cs_new_protected:Npn \skip_new:N #1
9352 {
9353 __chk_if_free_cs:N #1
9354 \cs:w newskip \cs_end: #1
9355 }
9356 *package
9357 \cs_generate_variant:Nn \skip_new:N { c }

(End definition for \skip_new:N. This function is documented on page 152.)

\skip_const:Nn Contrarily to integer constants, we cannot avoid using a register, even for constants.

```
\skip_const:cn
9358 \cs_new_protected:Npn \skip_const:Nn #1
9359 {
9360     \skip_new:N #1
9361     \skip_gset:Nn #1
9362 }
9363 \cs_generate_variant:Nn \skip_const:Nn { c }
```

(End definition for \skip_const:Nn. This function is documented on page 152.)

\skip_zero:N Reset the register to zero.

```
\skip_zero:c
9364 \cs_new_protected:Npn \skip_zero:N #1 { #1 \c_zero_skip }
\skip_gzero:N
9365 \cs_new_protected:Npn \skip_gzero:N { \tex_global:D \skip_zero:N }
\skip_gzero:c
9366 \cs_generate_variant:Nn \skip_zero:N { c }
9367 \cs_generate_variant:Nn \skip_gzero:N { c }
```

(End definition for \skip_zero:N and \skip_gzero:N. These functions are documented on page 152.)

\skip_zero_new:N Create a register if needed, otherwise clear it.

```
\skip_zero_new:c
9368 \cs_new_protected:Npn \skip_zero_new:N #1
\skip_gzero_new:N
9369 { \skip_if_exist:NTF #1 { \skip_zero:N #1 } { \skip_new:N #1 } }
\skip_gzero_new:c
9370 \cs_new_protected:Npn \skip_gzero_new:N #1
9371 { \skip_if_exist:NTF #1 { \skip_gzero:N #1 } { \skip_new:N #1 } }
9372 \cs_generate_variant:Nn \skip_zero_new:N { c }
9373 \cs_generate_variant:Nn \skip_gzero_new:N { c }
```

(End definition for \skip_zero_new:N and \skip_gzero_new:N. These functions are documented on page 152.)

\skip_if_exist_p:N Copies of the cs functions defined in l3basics.

```
\skip_if_exist_p:c
9374 \prg_new_eq_conditional:NNn \skip_if_exist:N \cs_if_exist:N
\skip_if_exist:N $\overline{TF}$ 
9375 { TF , T , F , p }
\skip_if_exist:c $\overline{TF}$ 
9376 \prg_new_eq_conditional:NNn \skip_if_exist:c \cs_if_exist:c
9377 { TF , T , F , p }
```

(End definition for \skip_if_exist:N \overline{TF} . This function is documented on page 152.)

17.12 Setting skip variables

\skip_set:Nn Much the same as for dimensions.

```
\skip_set:cn
9378 \cs_new_protected:Npn \skip_set:Nn #1#2
\skip_gset:Nn
9379 { #1 ~ \etex_glueexpr:D #2 \scan_stop: }
\skip_gset:cn
9380 \cs_new_protected:Npn \skip_gset:Nn { \tex_global:D \skip_set:Nn }
9381 \cs_generate_variant:Nn \skip_set:Nn { c }
9382 \cs_generate_variant:Nn \skip_gset:Nn { c }
```

(End definition for \skip_set:Nn and \skip_gset:Nn. These functions are documented on page 152.)

\skip_set_eq:NN All straightforward.

```
\skip_set_eq:cN
9383 \cs_new_protected:Npn \skip_set_eq:NN #1#2 { #1 = #2 }
\skip_set_eq:Nc
9384 \cs_generate_variant:Nn \skip_set_eq:NN { c }
\skip_set_eq:cc
9385 \cs_generate_variant:Nn \skip_set_eq:NN { Nc , cc }
\skip_gset_eq:NN
9386 \cs_new_protected:Npn \skip_gset_eq:NN #1#2 { \tex_global:D #1 = #2 }
\skip_gset_eq:cN
9387 \cs_generate_variant:Nn \skip_gset_eq:NN { c }
\skip_gset_eq:Nc
9388 \cs_generate_variant:Nn \skip_gset_eq:NN { Nc , cc }
\skip_gset_eq:cc
```


(End definition for `\skip_set_eq:Nn` and `\skip_gset_eq:Nn`. These functions are documented on page 152.)

```

\skip_add:Nn Using by here deals with the (incorrect) case \skip123.
\skip_add:cn
\skip_gadd:Nn 9389 \cs_new_protected:Npn \skip_add:Nn #1#2
\skip_gadd:cn 9390 { \tex_advance:D #1 by \etex_glueexpr:D #2 \scan_stop: }
\skip_sub:Nn 9391 \cs_new_protected:Npn \skip_gadd:Nn { \tex_global:D \skip_add:Nn }
\skip_sub:cn 9392 \cs_generate_variant:Nn \skip_add:Nn { c }
\skip_gsub:Nn 9393 \cs_generate_variant:Nn \skip_gadd:Nn { c }
\skip_gsub:cn 9394 \cs_new_protected:Npn \skip_sub:Nn #1#2
9395 { \tex_advance:D #1 by - \etex_glueexpr:D #2 \scan_stop: }
9396 \cs_new_protected:Npn \skip_gsub:Nn { \tex_global:D \skip_sub:Nn }
9397 \cs_generate_variant:Nn \skip_sub:Nn { c }
9398 \cs_generate_variant:Nn \skip_gsub:Nn { c }

```

(End definition for `\skip_add:Nn` and others. These functions are documented on page 152.)

17.13 Skip expression conditionals

`\skip_if_eq_p:nn` Comparing skips means doing two expansions to make strings, and then testing them.
`\skip_if_eq:nnTF` As a result, only equality is tested.

```

9399 \prg_new_conditional:Npnn \skip_if_eq:nn #1#2 { p , T , F , TF }
9400 {
9401   \if_int_compare:w
9402     \__str_if_eq_x:nn { \skip_eval:n { #1 } } { \skip_eval:n { #2 } }
9403     = 0 \exp_stop_f:
9404     \prg_return_true:
9405   \else:
9406     \prg_return_false:
9407   \fi:
9408 }

```

(End definition for `\skip_if_eq:nnTF`. This function is documented on page 153.)

`\skip_if_finite_p:n` With ε -TeX, we have an easy access to the order of infinities of the stretch and shrink
`\skip_if_finite:nTF` components of a skip. However, to access both, we either need to evaluate the expression
`__skip_if_finite:wwNw` twice, or evaluate it, then call an auxiliary to extract both pieces of information from the
result. Since we are going to need an auxiliary anyways, it is quicker to make it search
for the string `fil` which characterizes infinite glue.

```

9409 \cs_set_protected:Npn \__cs_tmp:w #1
9410 {
9411   \prg_new_conditional:Npnn \skip_if_finite:n ##1 { p , T , F , TF }
9412   {
9413     \exp_after:wN \__skip_if_finite:wwNw
9414     \skip_use:N \etex_glueexpr:D ##1 ; \prg_return_false:
9415     #1 ; \prg_return_true: \q_stop
9416   }
9417   \cs_new:Npn \__skip_if_finite:wwNw ##1 #1 ##2 ; ##3 ##4 \q_stop {##3}
9418 }
9419 \exp_args:No \__cs_tmp:w { \tl_to_str:n { fil } }

```

(End definition for `\skip_if_finite:nTF` and `__skip_if_finite:wwNw`. These functions are documented on page 153.)

17.14 Using skip expressions and variables

`\skip_eval:n` Evaluating a skip expression expandably.

```
9420 \cs_new:Npn \skip_eval:n #1
9421 { \skip_use:N \etex_glueexpr:D #1 \scan_stop: }
```

(End definition for `\skip_eval:n`. This function is documented on page 153.)

`\skip_use:N` Accessing a `\skip`.

```
\skip_use:c
9422 \cs_new_eq:NN \skip_use:N \tex_the:D
9423 %\cs_generate_variant:Nn \skip_use:N { c }
9424 \cs_new:Npn \skip_use:c #1 { \tex_the:D \cs:w #1 \cs_end: }
```

(End definition for `\skip_use:N`. This function is documented on page 153.)

17.15 Inserting skips into the output

`\skip_horizontal:N` Inserting skips.

```
\skip_horizontal:c
\skip_horizontal:n
\skip_vertical:N
\skip_vertical:c
\skip_vertical:n
9425 \cs_new_eq:NN \skip_horizontal:N \tex_hskip:D
9426 \cs_new:Npn \skip_horizontal:n #1
9427 { \skip_horizontal:N \etex_glueexpr:D #1 \scan_stop: }
9428 \cs_new_eq:NN \skip_vertical:N \tex_vskip:D
9429 \cs_new:Npn \skip_vertical:n #1
9430 { \skip_vertical:N \etex_glueexpr:D #1 \scan_stop: }
9431 \cs_generate_variant:Nn \skip_horizontal:N { c }
9432 \cs_generate_variant:Nn \skip_vertical:N { c }
```

(End definition for `\skip_horizontal:N` and others. These functions are documented on page 154.)

17.16 Viewing skip variables

`\skip_show:N` Diagnostics.

```
\skip_show:c
9433 \cs_new_eq:NN \skip_show:N \__kernel_register_show:N
9434 \cs_generate_variant:Nn \skip_show:N { c }
```

(End definition for `\skip_show:N`. This function is documented on page 153.)

`\skip_show:n` Diagnostics. We don't use the TeX primitive `\showthe` to show skip expressions: this gives a more unified output.

```
9435 \cs_new_protected:Npn \skip_show:n
9436 { \__msg_show_wrap:Nn \skip_eval:n }
```

(End definition for `\skip_show:n`. This function is documented on page 154.)

`\skip_log:N` Diagnostics. Redirect output of `\skip_show:n` to the log.

```
\skip_log:c
\skip_log:n
9437 \cs_new_eq:NN \skip_log:N \__kernel_register_log:N
9438 \cs_new_eq:NN \skip_log:c \__kernel_register_log:c
9439 \cs_new_protected:Npn \skip_log:n
9440 { \__msg_log_next: \skip_show:n }
```

(End definition for `\skip_log:N` and `\skip_log:n`. These functions are documented on page 154.)

17.17 Constant skips

`\c_zero_skip` Skips with no rubber component are just dimensions but need to terminate correctly.

`\c_max_skip` 9441 \skip_const:Nn \c_zero_skip { \c_zero_dim }
9442 \skip_const:Nn \c_max_skip { \c_max_dim }

(End definition for \c_zero_skip and \c_max_skip. These functions are documented on page 154.)

17.18 Scratch skips

`\l_tmpa_skip` We provide two local and two global scratch registers, maybe we need more or less.

`\l_tmpb_skip` 9443 \skip_new:N \l_tmpa_skip
9444 \skip_new:N \l_tmpb_skip
9445 \skip_new:N \g_tmpa_skip
9446 \skip_new:N \g_tmpb_skip

(End definition for \l_tmpa_skip and others. These variables are documented on page 154.)

17.19 Creating and initialising muskip variables

`\muskip_new:N` And then we add muskips.

`\muskip_new:c` 9447 *package
9448 \cs_new_protected:Npn \muskip_new:N #1
9449 {
9450 __chk_if_free_cs:N #1
9451 \cs:w newmuskip \cs_end: #1
9452 }
9453 *package
9454 \cs_generate_variant:Nn \muskip_new:N { c }

(End definition for \muskip_new:N. This function is documented on page 155.)

`\muskip_const:Nn` Contrarily to integer constants, we cannot avoid using a register, even for constants.

`\muskip_const:cn` 9455 \cs_new_protected:Npn \muskip_const:Nn #1
9456 {
9457 \muskip_new:N #1
9458 \muskip_gset:Nn #1
9459 }
9460 \cs_generate_variant:Nn \muskip_const:Nn { c }

(End definition for \muskip_const:Nn. This function is documented on page 155.)

`\muskip_zero:N` Reset the register to zero.

`\muskip_zero:c` 9461 \cs_new_protected:Npn \muskip_zero:N #1
9462 { #1 \c_zero_muskip }
`\muskip_gzero:N` 9463 \cs_new_protected:Npn \muskip_gzero:N { \tex_global:D \muskip_zero:N }
`\muskip_gzero:c` 9464 \cs_generate_variant:Nn \muskip_zero:N { c }
9465 \cs_generate_variant:Nn \muskip_gzero:N { c }

(End definition for \muskip_zero:N and \muskip_gzero:N. These functions are documented on page 155.)

\muskip_zero_new:N Create a register if needed, otherwise clear it.

```

\muskip_zero_new:c 9466 \cs_new_protected:Npn \muskip_zero_new:N #1
\muskip_gzero_new:N 9467 { \muskip_if_exist:NTF #1 { \muskip_zero:N #1 } { \muskip_new:N #1 } }
\muskip_gzero_new:c 9468 \cs_new_protected:Npn \muskip_gzero_new:N #1
9469 { \muskip_if_exist:NTF #1 { \muskip_gzero:N #1 } { \muskip_new:N #1 } }
9470 \cs_generate_variant:Nn \muskip_zero_new:N { c }
9471 \cs_generate_variant:Nn \muskip_gzero_new:N { c }

(End definition for \muskip_zero_new:N and \muskip_gzero_new:N. These functions are documented on
page 155.)

```

\muskip_if_exist_p:N Copies of the cs functions defined in l3basics.

```

\muskip_if_exist_p:c 9472 \prg_new_eq_conditional:NNn \muskip_if_exist:N \cs_if_exist:N
\muskip_if_exist:N $\underline{TF}$  9473 { TF , T , F , p }
\muskip_if_exist:c $\underline{TF}$  9474 \prg_new_eq_conditional:NNn \muskip_if_exist:c \cs_if_exist:c
9475 { TF , T , F , p }

(End definition for \muskip_if_exist:NTF. This function is documented on page 155.)

```

17.20 Setting muskip variables

\muskip_set:Nn This should be pretty familiar.

```

\muskip_set:cn 9476 \cs_new_protected:Npn \muskip_set:Nn #1#2
\muskip_gset:Nn 9477 { #1 ~ \etex_muexpr:D #2 \scan_stop: }
\muskip_gset:cn 9478 \cs_new_protected:Npn \muskip_gset:Nn { \tex_global:D \muskip_set:Nn }
9479 \cs_generate_variant:Nn \muskip_set:Nn { c }
9480 \cs_generate_variant:Nn \muskip_gset:Nn { c }

(End definition for \muskip_set:Nn and \muskip_gset:Nn. These functions are documented on page
156.)

```

\muskip_set_eq:NN All straightforward.

```

\muskip_set_eq:cN 9481 \cs_new_protected:Npn \muskip_set_eq:NN #1#2 { #1 = #2 }
\muskip_set_eq:Nc 9482 \cs_generate_variant:Nn \muskip_set_eq:NN { c }
\muskip_set_eq:cc 9483 \cs_generate_variant:Nn \muskip_set_eq:NN { Nc , cc }
\muskip_gset_eq:NN 9484 \cs_new_protected:Npn \muskip_gset_eq:NN #1#2 { \tex_global:D #1 = #2 }
\muskip_gset_eq:cN 9485 \cs_generate_variant:Nn \muskip_gset_eq:NN { c }
\muskip_gset_eq:Nc 9486 \cs_generate_variant:Nn \muskip_gset_eq:NN { Nc , cc }
\muskip_gset_eq:cc

(End definition for \muskip_set_eq:NN and \muskip_gset_eq:NN. These functions are documented on
page 156.)

```

\muskip_add:Nn Using by here deals with the (incorrect) case \muskip123.

```

\muskip_add:cn 9487 \cs_new_protected:Npn \muskip_add:Nn #1#2
\muskip_gadd:Nn 9488 { \tex_advance:D #1 by \etex_muexpr:D #2 \scan_stop: }
\muskip_gadd:cn 9489 \cs_new_protected:Npn \muskip_gadd:Nn { \tex_global:D \muskip_add:Nn }
\muskip_sub:Nn 9490 \cs_generate_variant:Nn \muskip_add:Nn { c }
\muskip_sub:cn 9491 \cs_generate_variant:Nn \muskip_gadd:Nn { c }
\muskip_gsub:Nn 9492 \cs_new_protected:Npn \muskip_sub:Nn #1#2
\muskip_gsub:cn 9493 { \tex_advance:D #1 by - \etex_muexpr:D #2 \scan_stop: }
9494 \cs_new_protected:Npn \muskip_gsub:Nn { \tex_global:D \muskip_sub:Nn }
9495 \cs_generate_variant:Nn \muskip_sub:Nn { c }
9496 \cs_generate_variant:Nn \muskip_gsub:Nn { c }

(End definition for \muskip_add:Nn and others. These functions are documented on page 155.)

```

17.21 Using muskip expressions and variables

\muskip_eval:n Evaluating a muskip expression expandably.

```
9497 \cs_new:Npn \muskip_eval:n #1
9498 { \muskip_use:N \etex_muexpr:D #1 \scan_stop: }
```

(End definition for \muskip_eval:n. This function is documented on page 156.)

\muskip_use:N Accessing a $\langle muskip \rangle$.

\muskip_use:c

```
9499 \cs_new_eq:NN \muskip_use:N \tex_the:D
9500 \cs_generate_variant:Nn \muskip_use:N { c }
```

(End definition for \muskip_use:N. This function is documented on page 156.)

17.22 Viewing muskip variables

\muskip_show:N Diagnostics.

\muskip_show:c

```
9501 \cs_new_eq:NN \muskip_show:N \__kernel_register_show:N
9502 \cs_generate_variant:Nn \muskip_show:N { c }
```

(End definition for \muskip_show:N. This function is documented on page 156.)

\muskip_show:n Diagnostics. We don't use the TeX primitive \showthe to show muskip expressions: this gives a more unified output.

```
9503 \cs_new_protected:Npn \muskip_show:n
9504 { \__msg_show_wrap:Nn \muskip_eval:n }
```

(End definition for \muskip_show:n. This function is documented on page 156.)

\muskip_log:N Diagnostics. Redirect output of \muskip_show:n to the log.

\muskip_log:c

\muskip_log:n

```
9505 \cs_new_eq:NN \muskip_log:N \__kernel_register_log:N
9506 \cs_new_eq:NN \muskip_log:c \__kernel_register_log:c
9507 \cs_new_protected:Npn \muskip_log:n
9508 { \__msg_log_next: \muskip_show:n }
```

(End definition for \muskip_log:N and \muskip_log:n. These functions are documented on page 157.)

17.23 Constant muskips

\c_zero_muskip Constant muskips given by their value.

\c_max_muskip

```
9509 \muskip_const:Nn \c_zero_muskip { 0 mu }
9510 \muskip_const:Nn \c_max_muskip { 16383.99999 mu }
```

(End definition for \c_zero_muskip and \c_max_muskip. These functions are documented on page 157.)

17.24 Scratch muskips

\l_tmpa_muskip We provide two local and two global scratch registers, maybe we need more or less.

\l_tmpb_muskip

\g_tmpa_muskip

\g_tmpb_muskip

```
9511 \muskip_new:N \l_tmpa_muskip
9512 \muskip_new:N \l_tmpb_muskip
9513 \muskip_new:N \g_tmpa_muskip
9514 \muskip_new:N \g_tmpb_muskip
```

(End definition for \l_tmpa_muskip and others. These variables are documented on page 157.)

```
9515 </initex | package>
```

18 l3keys Implementation

9516 $\langle *initex | package \rangle$

18.1 Low-level interface

The low-level key parser is based heavily on `keyval`, but with a number of additional “safety” requirements and with the idea that the parsed list of key–value pairs can be processed in a variety of ways. The net result is that this code needs around twice the amount of time as `keyval` to parse the same list of keys. To optimise speed as far as reasonably practical, a number of lower-level approaches are taken rather than using the higher-level `expl3` interfaces.

9517 $\langle @@=keyval \rangle$

`\l__keyval_key_tl` The current key name and value.

`\l__keyval_value_tl` 9518 `\tl_new:N \l__keyval_key_tl`

9519 `\tl_new:N \l__keyval_value_tl`

(End definition for `\l__keyval_key_tl` and `\l__keyval_value_tl`.)

`\l__keyval_sanitise_tl` A token list variable for dealing with awkward category codes in the input.

9520 `\tl_new:N \l__keyval_sanitise_tl`

(End definition for `\l__keyval_sanitise_tl`.)

`\keyval_parse:NNn` The main function starts off by normalising category codes in package mode. That’s relatively “expensive” so is skipped (hopefully) in format mode. We then hand off to the parser. The use of `\q_mark` here prevents loss of braces from the key argument. This particular quark is chosen as it fits in with `__tl_trim_spaces:nn` and allows a performance enhancement as the token can be carried through. Notice that by passing the two processor commands along the input stack we avoid the need to track these at all.

9521 `\cs_new_protected:Npn \keyval_parse:NNn #1#2#3`
 9522 `{`
 9523 `*initex`
 9524 `__keyval_loop:NNw #1#2 \q_mark #3 , \q_recursion_tail ,`
 9525 `*initex`
 9526 `*package`
 9527 `\tl_set:Nn \l__keyval_sanitise_tl {#3}`
 9528 `__keyval_sanitise_equals:`
 9529 `__keyval_sanitise_comma:`
 9530 `\exp_after:wN __keyval_loop:NNw \exp_after:wN #1 \exp_after:wN #2`
 9531 `\exp_after:wN \q_mark \l__keyval_sanitise_tl , \q_recursion_tail ,`
 9532 `*package`
 9533 `}`

(End definition for `\keyval_parse:NNn`. This function is documented on page 171.)

`__keyval_sanitise_equals:` A reasonably fast search and replace set up specifically for the active tokens. The nature of the input is known so everything is hard-coded. With only two tokens to cover, the speed gain from using dedicated functions is worth it.

`__keyval_sanitise_comma:`
`__keyval_sanitise_equals_auxi:w`
`__keyval_sanitise_equals_auxii:w`
`__keyval_sanitise_comma_auxi:w`
`__keyval_sanitise_comma_auxii:w`
`__keyval_sanitise_aux:w`

9534 `*package`
 9535 `\group_begin:`
 9536 `\char_set_catcode_active:n { ‘\= }`

```

9537 \char_set_catcode_active:n { '\, }
9538 \cs_new_protected:Npn \__keyval_sanitise_equals:
9539 {
9540   \exp_after:wN \__keyval_sanitise_equals_auxi:w \l__keyval_sanitise_tl
9541   \q_mark = \q_nil =
9542   \exp_after:wN \__keyval_sanitise_aux:w \l__keyval_sanitise_tl
9543 }
9544 \cs_new_protected:Npn \__keyval_sanitise_equals_auxi:w #1 =
9545 {
9546   \tl_set:Nn \l__keyval_sanitise_tl {#1}
9547   \__keyval_sanitise_equals_auxii:w
9548 }
9549 \cs_new_protected:Npn \__keyval_sanitise_equals_auxii:w #1 =
9550 {
9551   \if_meaning:w \q_nil #1 \scan_stop:
9552   \else:
9553     \tl_set:Nx \l__keyval_sanitise_tl
9554     {
9555       \exp_not:o \l__keyval_sanitise_tl
9556       \token_to_str:N =
9557       \exp_not:n {#1}
9558     }
9559     \exp_after:wN \__keyval_sanitise_equals_auxii:w
9560   \fi:
9561 }
9562 \cs_new_protected:Npn \__keyval_sanitise_comma:
9563 {
9564   \exp_after:wN \__keyval_sanitise_comma_auxi:w \l__keyval_sanitise_tl
9565   \q_mark , \q_nil ,
9566   \exp_after:wN \__keyval_sanitise_aux:w \l__keyval_sanitise_tl
9567 }
9568 \cs_new_protected:Npn \__keyval_sanitise_comma_auxi:w #1 ,
9569 {
9570   \tl_set:Nn \l__keyval_sanitise_tl {#1}
9571   \__keyval_sanitise_comma_auxii:w
9572 }
9573 \cs_new_protected:Npn \__keyval_sanitise_comma_auxii:w #1 ,
9574 {
9575   \if_meaning:w \q_nil #1 \scan_stop:
9576   \else:
9577     \tl_set:Nx \l__keyval_sanitise_tl
9578     {
9579       \exp_not:o \l__keyval_sanitise_tl
9580       \token_to_str:N ,
9581       \exp_not:n {#1}
9582     }
9583     \exp_after:wN \__keyval_sanitise_comma_auxii:w
9584   \fi:
9585 }
9586 \group_end:
9587 \cs_new_protected:Npn \__keyval_sanitise_aux:w #1 \q_mark
9588 { \tl_set:Nn \l__keyval_sanitise_tl {#1} }
9589 </package>

```

(End definition for __keyval_sanitise_equals: and others.)

`__keyval_loop:NNw` A fast test for the end of the loop, remembering to remove the leading quark first. Assuming that is not the case, look for a key and value then loop around, re-inserting a leading quark in front of the next position.

```

9590 \cs_new_protected:Npn \__keyval_loop:NNw #1#2#3 ,
9591 {
9592   \exp_after:wN \if_meaning:w \exp_after:wN \q_recursion_tail
9593   \use_none:n #3 \prg_do_nothing:
9594   \else:
9595     \__keyval_split:NNw #1#2#3 == \q_stop
9596     \exp_after:wN \__keyval_loop:NNw \exp_after:wN #1 \exp_after:wN #2
9597     \exp_after:wN \q_mark
9598   \fi:
9599 }

```

(End definition for `__keyval_loop:NNw`.)

`__keyval_split:NNw` The value is picked up separately from the key so there can be another quark inserted at the front, keeping braces and allowing both parts to share the same code paths. The
`__keyval_split_value:NNw` key is found first then there's a check that there is something there: this is biased to the
`__keyval_split_tidy:w` common case of there actually being a key. For the value, we first need to see if there is
`__keyval_action:` anything to do: if there is, extract it. The appropriate action is then inserted in front of the key and value. Doing this using an assignment is marginally faster than an expansion chain.

```

9600 \cs_new_protected:Npn \__keyval_split:NNw #1#2#3 =
9601 {
9602   \__keyval_def:Nn \l__keyval_key_tl {#3}
9603   \if_meaning:w \l__keyval_key_tl \c_empty_tl
9604     \exp_after:wN \__keyval_split_tidy:w
9605   \else:
9606     \exp_after:wN \__keyval_split_value:NNw \exp_after:wN #1 \exp_after:wN #2
9607     \exp_after:wN \q_mark
9608   \fi:
9609 }
9610 \cs_new_protected:Npn \__keyval_split_value:NNw #1#2#3 = #4 \q_stop
9611 {
9612   \if:w \scan_stop: \tl_to_str:n {#4} \scan_stop:
9613     \cs_set:Npx \__keyval_action:
9614     { \exp_not:N #1 { \exp_not:o \l__keyval_key_tl } }
9615   \else:
9616     \if:w \scan_stop: \etex_detokenize:D \exp_after:wN { \use_none:n #4 }
9617     \scan_stop:
9618     \__keyval_def:Nn \l__keyval_value_tl {#3}
9619     \cs_set:Npx \__keyval_action:
9620     {
9621       \exp_not:N #2
9622       { \exp_not:o \l__keyval_key_tl }
9623       { \exp_not:o \l__keyval_value_tl }
9624     }
9625   \else:
9626     \cs_set:Npn \__keyval_action:
9627     { \__msg_kernel_error:nn { kernel } { misplaced-equals-sign } }
9628   \fi:
9629 \fi:

```



```

9630   \__keyval_action:
9631   }
9632 \cs_new_protected:Npn \__keyval_split_tidy:w #1 \q_stop
9633   {
9634     \if:w \scan_stop: \etex_detokenize:D \exp_after:wN { \use_none:n #1 }
9635     \scan_stop:
9636     \else:
9637       \exp_after:wN \__keyval_empty_key:
9638     \fi:
9639   }
9640 \cs_new:Npn \__keyval_action: { }
9641 \cs_new_protected:Npn \__keyval_empty_key:
9642   { \__msg_kernel_error:nn { kernel } { misplaced-equals-sign } }

```

(End definition for __keyval_split:NNw and others.)

__keyval_def:Nn First trim spaces off, then potentially remove a set of braces. By using the internal interface __tl_trim_spaces:nn we can take advantage of the fact it needs a leading \q_mark in this process. The \exp_after:wN removes the quark, the delimited argument deals with any braces.

```

9643 \cs_new_protected:Npn \__keyval_def:Nn #1#2
9644   { \tl_set:Nx #1 { \__tl_trim_spaces:nn {#2} \__keyval_def_aux:n } }
9645 \cs_new:Npn \__keyval_def_aux:n #1
9646   { \exp_after:wN \__keyval_def_aux:w #1 \q_stop }
9647 \cs_new:Npn \__keyval_def_aux:w #1 \q_stop { \exp_not:n {#1} }

```

(End definition for __keyval_def:Nn, __keyval_def_aux:n, and __keyval_def_aux:w.)

One message for the low level parsing system.

```

9648 \__msg_kernel_new:nnnn { kernel } { misplaced-equals-sign }
9649   { Misplaced-equals-sign-in~key-value-input~\msg_line_number: }
9650   {
9651     LaTeX-is-attempting-to-parse-some-key-value-input-but-found-
9652     two-equals-signs-not-separated-by-a-comma.
9653   }

```

18.2 Constants and variables

9654 <@@=keys>

Various storage areas for the different data which make up keys.

```

\c__keys_code_root_tl
\c__keys_default_root_tl
\c__keys_groups_root_tl
\c__keys_inherit_root_tl
\c__keys_type_root_tl
\c__keys_validate_root_tl
9655 \tl_const:Nn \c__keys_code_root_tl { key~code~>~ }
9656 \tl_const:Nn \c__keys_default_root_tl { key~default~>~ }
9657 \tl_const:Nn \c__keys_groups_root_tl { key~groups~>~ }
9658 \tl_const:Nn \c__keys_inherit_root_tl { key~inherit~>~ }
9659 \tl_const:Nn \c__keys_type_root_tl { key~type~>~ }
9660 \tl_const:Nn \c__keys_validate_root_tl { key~validate~>~ }

```

(End definition for \c__keys_code_root_tl and others.)

\c__keys_props_root_tl The prefix for storing properties.

```

9661 \tl_const:Nn \c__keys_props_root_tl { key~prop~>~ }

```

(End definition for \c__keys_props_root_tl.)

`\l_keys_choice_int` Publicly accessible data on which choice is being used when several are generated as a set.

`\l_keys_choice_tl`

```

9662 \int_new:N \l_keys_choice_int
9663 \tl_new:N \l_keys_choice_tl

```

(End definition for \l_keys_choice_int and \l_keys_choice_tl. These variables are documented on page 165.)

`\l__keys_groups_clist` Used for storing and recovering the list of groups which apply to a key: set as a comma list but at one point we have to use this for a token list recovery.

```

9664 \clist_new:N \l__keys_groups_clist

```

(End definition for \l__keys_groups_clist.)

`\l_keys_key_tl` The name of a key itself: needed when setting keys.

```

9665 \tl_new:N \l_keys_key_tl

```

(End definition for \l_keys_key_tl. This variable is documented on page 167.)

`\l__keys_module_tl` The module for an entire set of keys.

```

9666 \tl_new:N \l__keys_module_tl

```

(End definition for \l__keys_module_tl.)

`\l__keys_no_value_bool` A marker is needed internally to show if only a key or a key plus a value was seen: this is recorded here.

```

9667 \bool_new:N \l__keys_no_value_bool

```

(End definition for \l__keys_no_value_bool.)

`\l__keys_only_known_bool` Used to track if only “known” keys are being set.

```

9668 \bool_new:N \l__keys_only_known_bool

```

(End definition for \l__keys_only_known_bool.)

`\l_keys_path_tl` The “path” of the current key is stored here: this is available to the programmer and so is public.

```

9669 \tl_new:N \l_keys_path_tl

```

(End definition for \l_keys_path_tl. This variable is documented on page 167.)

`\l__keys_property_tl` The “property” begin set for a key at definition time is stored here.

```

9670 \tl_new:N \l__keys_property_tl

```

(End definition for \l__keys_property_tl.)

`\l__keys_selective_bool` Two flags for using key groups: one to indicate that “selective” setting is active, a second to specify which type (“opt-in” or “opt-out”).

`\l__keys_filtered_bool`

```

9671 \bool_new:N \l__keys_selective_bool
9672 \bool_new:N \l__keys_filtered_bool

```

(End definition for \l__keys_selective_bool and \l__keys_filtered_bool.)

`\l__keys_selective_seq` The list of key groups being filtered in or out during selective setting.

```

9673 \seq_new:N \l__keys_selective_seq

```

(End definition for `\l__keys_selective_seq`.)

`\l__keys_unused_clist` Used when setting only some keys to store those left over.

```
9674 \tl_new:N \l__keys_unused_clist
```

(End definition for `\l__keys_unused_clist`.)

`\l_keys_value_tl` The value given for a key: may be empty if no value was given.

```
9675 \tl_new:N \l_keys_value_tl
```

(End definition for `\l_keys_value_tl`. This variable is documented on page 167.)

`\l__keys_tmp_bool` Scratch space.

```
9676 \bool_new:N \l__keys_tmp_bool
```

(End definition for `\l__keys_tmp_bool`.)

18.3 The key defining mechanism

`\keys_define:nn` The public function for definitions is just a wrapper for the lower level mechanism, more or less. The outer function is designed to keep a track of the current module, to allow safe nesting. The module is set removing any leading / (which is not needed here).

`__keys_define:nnn`
`__keys_define:onn`

```
9677 \cs_new_protected:Npn \keys_define:nn
9678 { \__keys_define:onn \l__keys_module_tl }
9679 \cs_new_protected:Npn \__keys_define:nnn #1#2#3
9680 {
9681   \tl_set:Nx \l__keys_module_tl { \__keys_remove_spaces:n {#2} }
9682   \keyval_parse:NNn \__keys_define:n \__keys_define:nn {#3}
9683   \tl_set:Nn \l__keys_module_tl {#1}
9684 }
9685 \cs_generate_variant:Nn \__keys_define:nnn { o }
```

(End definition for `\keys_define:nn` and `__keys_define:nnn`. These functions are documented on page 160.)

`__keys_define:n` The outer functions here record whether a value was given and then converge on a common internal mechanism. There is first a search for a property in the current key name, then a check to make sure it is known before the code hands off to the next step.

`__keys_define:nn`
`__keys_define_aux:nn`

```
9686 \cs_new_protected:Npn \__keys_define:n #1
9687 {
9688   \bool_set_true:N \l__keys_no_value_bool
9689   \__keys_define_aux:nn {#1} { }
9690 }
9691 \cs_new_protected:Npn \__keys_define:nn #1#2
9692 {
9693   \bool_set_false:N \l__keys_no_value_bool
9694   \__keys_define_aux:nn {#1} {#2}
9695 }
9696 \cs_new_protected:Npn \__keys_define_aux:nn #1#2
9697 {
9698   \__keys_property_find:n {#1}
9699   \cs_if_exist:cTF { \c__keys_props_root_tl \l__keys_property_tl }
9700   { \__keys_define_code:n {#2} }
9701   { }
```

```

9702         \tl_if_empty:NF \l__keys_property_tl
9703         {
9704             \__msg_kernel_error:nxxx { kernel } { property-unknown }
9705             { \l__keys_property_tl } { \l_keys_path_tl }
9706         }
9707     }
9708 }

```

(End definition for __keys_define:n, __keys_define:nn, and __keys_define_aux:nn.)

__keys_property_find:n Searching for a property means finding the last . in the input, and storing the text before and after it. Everything is turned into strings, so there is no problem using an x-type expansion.

```

9709 \cs_new_protected:Npn \__keys_property_find:n #1
9710 {
9711     \tl_set:Nx \l__keys_property_tl { \__keys_remove_spaces:n {#1} }
9712     \exp_after:wN \__keys_property_find:w \l__keys_property_tl . . \q_stop {#1}
9713 }
9714 \cs_new_protected:Npn \__keys_property_find:w #1 . #2 . #3 \q_stop #4
9715 {
9716     \tl_if_blank:nTF {#3}
9717     {
9718         \tl_clear:N \l__keys_property_tl
9719         \__msg_kernel_error:nnn { kernel } { key-no-property } {#4}
9720     }
9721     {
9722         \str_if_eq:nnTF {#3} { . }
9723         {
9724             \tl_set:Nx \l_keys_path_tl
9725             {
9726                 \tl_if_empty:NF \l__keys_module_tl
9727                 { \l__keys_module_tl / }
9728                 #1
9729             }
9730             \tl_set:Nn \l__keys_property_tl { . #2 }
9731         }
9732         {
9733             \tl_set:Nx \l_keys_path_tl { \l__keys_module_tl / #1 . #2 }
9734             \__keys_property_search:w #3 \q_stop
9735         }
9736     }
9737 }
9738 \cs_new_protected:Npn \__keys_property_search:w #1 . #2 \q_stop
9739 {
9740     \str_if_eq:nnTF {#2} { . }
9741     {
9742         \tl_set:Nx \l_keys_path_tl { \l_keys_path_tl }
9743         \tl_set:Nn \l__keys_property_tl { . #1 }
9744     }
9745     {
9746         \tl_set:Nx \l_keys_path_tl { \l_keys_path_tl . #1 }
9747         \__keys_property_search:w #2 \q_stop
9748     }
9749 }

```

(End definition for `__keys_property_find:n` and `__keys_property_find:w`.)

`__keys_define_code:n` Two possible cases. If there is a value for the key, then just use the function. If not, then a check to make sure there is no need for a value with the property. If there should be one then complain, otherwise execute it. There is no need to check for a `:` as if it is missing the earlier tests will have failed.

```

9750 \cs_new_protected:Npn \__keys_define_code:n #1
9751 {
9752   \bool_if:NTF \l__keys_no_value_bool
9753   {
9754     \exp_after:wN \__keys_define_code:w
9755     \l__keys_property_tl \q_stop
9756     { \use:c { \c__keys_props_root_tl \l__keys_property_tl } }
9757     {
9758       \__msg_kernel_error:nxxx { kernel }
9759       { property-requires-value } { \l__keys_property_tl }
9760       { \l_keys_path_tl }
9761     }
9762   }
9763   { \use:c { \c__keys_props_root_tl \l__keys_property_tl } {#1} }
9764 }
9765 \use:x
9766 {
9767   \cs_new:Npn \exp_not:N \__keys_define_code:w
9768   ##1 \c_colon_str ##2 \exp_not:N \q_stop
9769 }
9770 { \tl_if_empty:nTF {#2} }
```

(End definition for `__keys_define_code:n` and `__keys_define_code:w`.)

18.4 Turning properties into actions

`__keys_bool_set:Nn` Boolean keys are really just choices, but all done by hand. The second argument here is the scope: either empty or `g` for global.

```

9771 \cs_new_protected:Npn \__keys_bool_set:Nn #1#2
9772 {
9773   \bool_if_exist:NF #1 { \bool_new:N #1 }
9774   \__keys_choice_make:
9775   \__keys_cmd_set:nx { \l_keys_path_tl / true }
9776   { \exp_not:c { bool_ #2 set_true:N } \exp_not:N #1 }
9777   \__keys_cmd_set:nx { \l_keys_path_tl / false }
9778   { \exp_not:c { bool_ #2 set_false:N } \exp_not:N #1 }
9779   \__keys_cmd_set:nn { \l_keys_path_tl / unknown }
9780   {
9781     \__msg_kernel_error:nxx { kernel } { boolean-values-only }
9782     { \l_keys_key_tl }
9783   }
9784   \__keys_default_set:n { true }
9785 }
9786 \cs_generate_variant:Nn \__keys_bool_set:Nn { c }
```

(End definition for `__keys_bool_set:Nn`.)

`__keys_bool_set_inverse:Nn` Inverse boolean setting is much the same.

```
\__keys_bool_set_inverse:cn
9787 \cs_new_protected:Npn \__keys_bool_set_inverse:Nn #1#2
9788 {
9789   \bool_if_exist:NF #1 { \bool_new:N #1 }
9790   \__keys_choice_make:
9791   \__keys_cmd_set:nx { \l_keys_path_tl / true }
9792     { \exp_not:c { bool_ #2 set_false:N } \exp_not:N #1 }
9793   \__keys_cmd_set:nx { \l_keys_path_tl / false }
9794     { \exp_not:c { bool_ #2 set_true:N } \exp_not:N #1 }
9795   \__keys_cmd_set:nn { \l_keys_path_tl / unknown }
9796     {
9797       \_msg_kernel_error:nxx { kernel } { boolean-values-only }
9798       { \l_keys_key_tl }
9799     }
9800   \__keys_default_set:n { true }
9801 }
9802 \cs_generate_variant:Nn \__keys_bool_set_inverse:Nn { c }
```

(End definition for `__keys_bool_set_inverse:Nn`.)

`__keys_choice_make:` To make a choice from a key, two steps: set the code, and set the unknown key. As
`__keys_multichoice_make:` multichoice and choices are essentially the same bar one function, the code is given
`__keys_choice_make:N` together.
`__keys_choice_make_aux:N`

```
9803 \cs_new_protected:Npn \__keys_choice_make:
9804 { \__keys_choice_make:N \__keys_choice_find:n }
9805 \cs_new_protected:Npn \__keys_multichoice_make:
9806 { \__keys_choice_make:N \__keys_multichoice_find:n }
9807 \cs_new_protected:Npn \__keys_choice_make:N #1
9808 {
9809   \cs_if_exist:cTF
9810   { \c__keys_type_root_tl \__keys_parent:o \l_keys_path_tl }
9811   {
9812     \str_if_eq_x:nnTF
9813     { \exp_not:v { \c__keys_type_root_tl \__keys_parent:o \l_keys_path_tl } }
9814     { choice }
9815     {
9816       \_msg_kernel_error:nxxx { kernel } { nested-choice-key }
9817       { \l_keys_path_tl } { \__keys_parent:o \l_keys_path_tl }
9818     }
9819     { \__keys_choice_make_aux:N #1 }
9820   }
9821   { \__keys_choice_make_aux:N #1 }
9822 }
9823 \cs_new_protected:Npn \__keys_choice_make_aux:N #1
9824 {
9825   \cs_set_nopar:cpn { \c__keys_type_root_tl \l_keys_path_tl } { choice }
9826   \__keys_cmd_set:nn { \l_keys_path_tl } { #1 {##1} }
9827   \__keys_cmd_set:nn { \l_keys_path_tl / unknown }
9828   {
9829     \_msg_kernel_error:nxxx { kernel } { key-choice-unknown }
9830     { \l_keys_path_tl } {##1}
9831   }
9832 }
```

(End definition for `_keys_choice_make:` and others.)

| | | |
|---|---|---|
| <code>_keys_choices_make:nn</code> <code>_keys_multichoices_make:nn</code> <code>_keys_choices_make:Nnn</code> | Auto-generating choices means setting up the root key as a choice, then defining each choice in turn. | <pre> 9833 \cs_new_protected:Npn _keys_choices_make:nn 9834 { _keys_choices_make:Nnn _keys_choice_make: } 9835 \cs_new_protected:Npn _keys_multichoices_make:nn 9836 { _keys_choices_make:Nnn _keys_multichoice_make: } 9837 \cs_new_protected:Npn _keys_choices_make:Nnn #1#2#3 9838 { 9839 #1 9840 \int_zero:N \l_keys_choice_int 9841 \clist_map_inline:nn {#2} 9842 { 9843 \int_incr:N \l_keys_choice_int 9844 _keys_cmd_set:nx { \l_keys_path_tl / _keys_remove_spaces:n {##1} } 9845 { 9846 \tl_set:Nn \exp_not:N \l_keys_choice_tl {##1} 9847 \int_set:Nn \exp_not:N \l_keys_choice_int 9848 { \int_use:N \l_keys_choice_int } 9849 \exp_not:n {#3} 9850 } 9851 } 9852 } </pre> |
|---|---|---|

(End definition for `_keys_choices_make:nn`, `_keys_multichoices_make:nn`, and `_keys_choices_make:Nnn`.)

| | | |
|--|--|---|
| <code>_keys_cmd_set:nn</code> <code>_keys_cmd_set:nx</code> <code>_keys_cmd_set:Vn</code> <code>_keys_cmd_set:Vo</code> | Setting the code for a key first checks that the basic data structures exist, then saves the code. | <pre> 9853 \cs_new_protected:Npn _keys_cmd_set:nn #1#2 9854 { 9855 \cs_if_exist:cF { \c__keys_code_root_tl #1 } 9856 { _chk_log:x { Defining-key-#1~\msg_line_context: } } 9857 \cs_set_protected:cpn { \c__keys_code_root_tl #1 } ##1 {#2} 9858 } 9859 \cs_generate_variant:Nn _keys_cmd_set:nn { nx , Vn , Vo } </pre> |
|--|--|---|

(End definition for `_keys_cmd_set:nn`.)

| | | |
|-----------------------------------|--|---|
| <code>_keys_default_set:n</code> | Setting a default value is easy. These are stored using <code>\cs_set:cpx</code> as this avoids any worries about whether a token list exists. | <pre> 9860 \cs_new_protected:Npn _keys_default_set:n #1 9861 { 9862 \tl_if_empty:nTF {#1} 9863 { 9864 \cs_set_eq:cN 9865 { \c__keys_default_root_tl \l_keys_path_tl } 9866 \tex_undefined:D 9867 } 9868 { 9869 \cs_set:cpx 9870 { \c__keys_default_root_tl \l_keys_path_tl } 9871 { \exp_not:n {#1} } </pre> |
|-----------------------------------|--|---|

```

9872     }
9873 }

```

(End definition for _keys_default_set:n.)

_keys_groups_set:n Assigning a key to one or more groups uses comma lists. As the list of groups only exists if there is anything to do, the setting is done using a scratch list. For the usual grouping reasons we use the low-level approach to undefining a list.

```

9874 \cs_new_protected:Npn \_keys_groups_set:n #1
9875 {
9876   \clist_set:Nn \l__keys_groups_clist {#1}
9877   \clist_if_empty:NTF \l__keys_groups_clist
9878   {
9879     \cs_set_eq:cN { \c__keys_groups_root_tl \l_keys_path_tl }
9880     \tex_undefined:D
9881   }
9882   {
9883     \clist_set_eq:cN { \c__keys_groups_root_tl \l_keys_path_tl }
9884     \l__keys_groups_clist
9885   }
9886 }

```

(End definition for _keys_groups_set:n.)

_keys_inherit:n Inheritance means ignoring anything already said about the key: zap the lot and set up.

```

9887 \cs_new_protected:Npn \_keys_inherit:n #1
9888 {
9889   \__keys_undefine:
9890   \cs_set_nopar:cpn { \c__keys_inherit_root_tl \l_keys_path_tl } {#1}
9891 }

```

(End definition for _keys_inherit:n.)

_keys_initialise:n A set up for initialisation: just run the code if it exists.

```

9892 \cs_new_protected:Npn \_keys_initialise:n #1
9893 {
9894   \cs_if_exist_use:cT { \c__keys_code_root_tl \l_keys_path_tl } { {#1} }
9895 }

```

(End definition for _keys_initialise:n.)

_keys_meta_make:n To create a meta-key, simply set up to pass data through.

```

9896 \cs_new_protected:Npn \_keys_meta_make:n #1
9897 {
9898   \__keys_cmd_set:Vo \l_keys_path_tl
9899   {
9900     \exp_after:wN \keys_set:nn
9901     \exp_after:wN { \l__keys_module_tl } {#1}
9902   }
9903 }
9904 \cs_new_protected:Npn \_keys_meta_make:nn #1#2
9905 { \__keys_cmd_set:Vn \l_keys_path_tl { \keys_set:nn {#1} {#2} } }

```

(End definition for _keys_meta_make:n and _keys_meta_make:nn.)

`__keys_undefine:` Undefined a key has to be done without `\cs_undefine:c` as that function acts globally.

```

9906 \cs_new_protected:Npn \__keys_undefine:
9907 {
9908   \clist_map_inline:nn
9909     { code , default , groups , inherit , type , validate }
9910     {
9911       \cs_set_eq:cN
9912       { \tl_use:c { c__keys_ ##1 _root_tl } \l_keys_path_tl }
9913       \tex_undefined:D
9914     }
9915 }

```

(End definition for __keys_undefine:.)

`__keys_value_requirement:nn` Validating key input is done using a second function which runs before the main key code. Setting that up means setting it equal to a generic stub which does the check. This approach makes the lookup very fast at the cost of one additional csname per key that needs it. The cleanup here has to know the structure of the following code.

```

9916 \cs_new_protected:Npn \__keys_value_requirement:nn #1#2
9917 {
9918   \str_case:nnF {#2}
9919   {
9920     { true }
9921     {
9922       \cs_set_eq:cc
9923       { \c__keys_validate_root_tl \l_keys_path_tl }
9924       { __keys_validate_ #1 : }
9925     }
9926     { false }
9927     {
9928       \cs_if_eq:ccT
9929       { \c__keys_validate_root_tl \l_keys_path_tl }
9930       { __keys_validate_ #1 : }
9931       {
9932         \cs_set_eq:cN
9933         { \c__keys_validate_root_tl \l_keys_path_tl }
9934         \tex_undefined:D
9935       }
9936     }
9937   }
9938   {
9939     \__msg_kernel_error:nxx { kernel } { property-boolean-values-only }
9940     { .value_ #1 :n }
9941   }
9942 }
9943 \cs_new_protected:Npn \__keys_validate_forbidden:
9944 {
9945   \bool_if:NF \l__keys_no_value_bool
9946   {
9947     \__msg_kernel_error:nxxx { kernel } { value-forbidden }
9948     { \l_keys_path_tl } { \l_keys_value_tl }
9949     \__keys_validate_cleanup:w
9950   }
9951 }

```

```

9952 \cs_new_protected:Npn \__keys_validate_required:
9953 {
9954   \bool_if:NT \l__keys_no_value_bool
9955   {
9956     \__msg_kernel_error:nnx { kernel } { value-required }
9957     { \l_keys_path_tl }
9958     \__keys_validate_cleanup:w
9959   }
9960 }
9961 \cs_new_protected:Npn \__keys_validate_cleanup:w #1 \cs_end: #2#3 { }

```

(End definition for `__keys_value_requirement:nn` and others.)

`__keys_variable_set:NnnN` Setting a variable takes the type and scope separately so that it is easy to make a new
`__keys_variable_set:cnnN` variable if needed.

```

9962 \cs_new_protected:Npn \__keys_variable_set:NnnN #1#2#3#4
9963 {
9964   \use:c { #2_if_exist:Nf } #1 { \use:c { #2_new:N } #1 }
9965   \__keys_cmd_set:nx { \l_keys_path_tl }
9966   {
9967     \exp_not:c { #2 _ #3 set:N #4 }
9968     \exp_not:N #1
9969     \exp_not:n { {##1} }
9970   }
9971 }
9972 \cs_generate_variant:Nn \__keys_variable_set:NnnN { c }

```

(End definition for `__keys_variable_set:NnnN`.)

18.5 Creating key properties

The key property functions are all wrappers for internal functions, meaning that things stay readable and can also be altered later on.

Importantly, while key properties have “normal” argument specs, the underlying code always supplies one braced argument to these. As such, argument expansion is handled by hand rather than using the standard tools. This shows up particularly for the two-argument properties, where things would otherwise go badly wrong.

```

. bool_set:N One function for this.
. bool_set:c 9973 \cs_new_protected:cpn { \c__keys_props_root_tl .bool_set:N } #1
. bool_gset:N 9974 { \__keys_bool_set:Nn #1 { } }
. bool_gset:c 9975 \cs_new_protected:cpn { \c__keys_props_root_tl .bool_set:c } #1
9976 { \__keys_bool_set:cn {#1} { } }
9977 \cs_new_protected:cpn { \c__keys_props_root_tl .bool_gset:N } #1
9978 { \__keys_bool_set:Nn #1 { g } }
9979 \cs_new_protected:cpn { \c__keys_props_root_tl .bool_gset:c } #1
9980 { \__keys_bool_set:cn {#1} { g } }

```

(End definition for `.bool_set:N` and `.bool_gset:N`. These functions are documented on page 161.)

```

. bool_set_inverse:N One function for this.
. bool_set_inverse:c 9981 \cs_new_protected:cpn { \c__keys_props_root_tl .bool_set_inverse:N } #1
. bool_gset_inverse:N 9982 { \__keys_bool_set_inverse:Nn #1 { } }
. bool_gset_inverse:c 9983 \cs_new_protected:cpn { \c__keys_props_root_tl .bool_set_inverse:c } #1

```

```

9984 { \__keys_bool_set_inverse:cn {#1} { } }
9985 \cs_new_protected:cpn { \c__keys_props_root_tl .bool_gset_inverse:N } #1
9986 { \__keys_bool_set_inverse:Nn #1 { g } }
9987 \cs_new_protected:cpn { \c__keys_props_root_tl .bool_gset_inverse:c } #1
9988 { \__keys_bool_set_inverse:cn {#1} { g } }

```

(End definition for `.bool_set_inverse:N` and `.bool_gset_inverse:N`. These functions are documented on page 161.)

.choice: Making a choice is handled internally, as it is also needed by `.generate_choices:n`.

```

9989 \cs_new_protected:cpn { \c__keys_props_root_tl .choice: }
9990 { \__keys_choice_make: }

```

(End definition for `.choice:.` This function is documented on page 161.)

.choices:nn For auto-generation of a series of mutually-exclusive choices. Here, #1 will consist of two separate arguments, hence the slightly odd-looking implementation.

```

.choices:Vn
.choices:on
.choices:xn
9991 \cs_new_protected:cpn { \c__keys_props_root_tl .choices:nn } #1
9992 { \__keys_choices_make:nn #1 }
9993 \cs_new_protected:cpn { \c__keys_props_root_tl .choices:Vn } #1
9994 { \exp_args:NV \__keys_choices_make:nn #1 }
9995 \cs_new_protected:cpn { \c__keys_props_root_tl .choices:on } #1
9996 { \exp_args:No \__keys_choices_make:nn #1 }
9997 \cs_new_protected:cpn { \c__keys_props_root_tl .choices:xn } #1
9998 { \exp_args:Nx \__keys_choices_make:nn #1 }

```

(End definition for `.choices:nn`. This function is documented on page 161.)

.code:n Creating code is simply a case of passing through to the underlying `set` function.

```

9999 \cs_new_protected:cpn { \c__keys_props_root_tl .code:n } #1
10000 { \__keys_cmd_set:nn { \l_keys_path_tl } {#1} }

```

(End definition for `.code:n`. This function is documented on page 161.)

.clist_set:N

```

.clist_set:c
.clist_gset:N
.clist_gset:c
10001 \cs_new_protected:cpn { \c__keys_props_root_tl .clist_set:N } #1
10002 { \__keys_variable_set:NnnN #1 { clist } { } n }
10003 \cs_new_protected:cpn { \c__keys_props_root_tl .clist_set:c } #1
10004 { \__keys_variable_set:cnN {#1} { clist } { } n }
10005 \cs_new_protected:cpn { \c__keys_props_root_tl .clist_gset:N } #1
10006 { \__keys_variable_set:NnnN #1 { clist } { g } n }
10007 \cs_new_protected:cpn { \c__keys_props_root_tl .clist_gset:c } #1
10008 { \__keys_variable_set:cnN {#1} { clist } { g } n }

```

(End definition for `.clist_set:N` and `.clist_gset:N`. These functions are documented on page 161.)

.default:n Expansion is left to the internal functions.

```

.default:V
.default:o
.default:x
10009 \cs_new_protected:cpn { \c__keys_props_root_tl .default:n } #1
10010 { \__keys_default_set:n {#1} }
10011 \cs_new_protected:cpn { \c__keys_props_root_tl .default:V } #1
10012 { \exp_args:NV \__keys_default_set:n #1 }
10013 \cs_new_protected:cpn { \c__keys_props_root_tl .default:o } #1
10014 { \exp_args:No \__keys_default_set:n {#1} }
10015 \cs_new_protected:cpn { \c__keys_props_root_tl .default:x } #1
10016 { \exp_args:Nx \__keys_default_set:n {#1} }

```

(End definition for `.default:n`. This function is documented on page 162.)

```
.dim_set:N Setting a variable is very easy: just pass the data along.
.dim_set:c 10017 \cs_new_protected:cpn { \c__keys_props_root_tl .dim_set:N } #1
           { \__keys_variable_set:NnnN #1 { dim } { } n }
.dim_gset:N 10018
.dim_gset:c 10019 \cs_new_protected:cpn { \c__keys_props_root_tl .dim_set:c } #1
           { \__keys_variable_set:cnnN {#1} { dim } { } n }
           10020
           10021 \cs_new_protected:cpn { \c__keys_props_root_tl .dim_gset:N } #1
           10022 { \__keys_variable_set:NnnN #1 { dim } { g } n }
           10023 \cs_new_protected:cpn { \c__keys_props_root_tl .dim_gset:c } #1
           10024 { \__keys_variable_set:cnnN {#1} { dim } { g } n }
```

(End definition for `.dim_set:N` and `.dim_gset:N`. These functions are documented on page 162.)

```
.fp_set:N Setting a variable is very easy: just pass the data along.
.fp_set:c 10025 \cs_new_protected:cpn { \c__keys_props_root_tl .fp_set:N } #1
           { \__keys_variable_set:NnnN #1 { fp } { } n }
.fp_gset:N 10026
.fp_gset:c 10027 \cs_new_protected:cpn { \c__keys_props_root_tl .fp_set:c } #1
           10028 { \__keys_variable_set:cnnN {#1} { fp } { } n }
           10029 \cs_new_protected:cpn { \c__keys_props_root_tl .fp_gset:N } #1
           10030 { \__keys_variable_set:NnnN #1 { fp } { g } n }
           10031 \cs_new_protected:cpn { \c__keys_props_root_tl .fp_gset:c } #1
           10032 { \__keys_variable_set:cnnN {#1} { fp } { g } n }
```

(End definition for `.fp_set:N` and `.fp_gset:N`. These functions are documented on page 162.)

```
.groups:n A single property to create groups of keys.
           10033 \cs_new_protected:cpn { \c__keys_props_root_tl .groups:n } #1
           10034 { \__keys_groups_set:n {#1} }
```

(End definition for `.groups:n`. This function is documented on page 162.)

```
.inherit:n Nothing complex: only one variant at the moment!
           10035 \cs_new_protected:cpn { \c__keys_props_root_tl .inherit:n } #1
           10036 { \__keys_inherit:n {#1} }
```

(End definition for `.inherit:n`. This function is documented on page 162.)

```
.initial:n The standard hand-off approach.
.initial:V 10037 \cs_new_protected:cpn { \c__keys_props_root_tl .initial:n } #1
.initial:o 10038 { \__keys_initialise:n {#1} }
.initial:x 10039 \cs_new_protected:cpn { \c__keys_props_root_tl .initial:V } #1
           10040 { \exp_args:NV \__keys_initialise:n #1 }
           10041 \cs_new_protected:cpn { \c__keys_props_root_tl .initial:o } #1
           10042 { \exp_args:No \__keys_initialise:n {#1} }
           10043 \cs_new_protected:cpn { \c__keys_props_root_tl .initial:x } #1
           10044 { \exp_args:Nx \__keys_initialise:n {#1} }
```

(End definition for `.initial:n`. This function is documented on page 163.)

.int_set:N Setting a variable is very easy: just pass the data along.

```

.int_set:c 10045 \cs_new_protected:cpn { \c__keys_props_root_tl .int_set:N } #1
.int_gset:N 10046 { \__keys_variable_set:NnnN #1 { int } { } n }
.int_gset:c 10047 \cs_new_protected:cpn { \c__keys_props_root_tl .int_set:c } #1
10048 { \__keys_variable_set:cnnN {#1} { int } { } n }
10049 \cs_new_protected:cpn { \c__keys_props_root_tl .int_gset:N } #1
10050 { \__keys_variable_set:NnnN #1 { int } { g } n }
10051 \cs_new_protected:cpn { \c__keys_props_root_tl .int_gset:c } #1
10052 { \__keys_variable_set:cnnN {#1} { int } { g } n }

```

(End definition for .int_set:N and .int_gset:N. These functions are documented on page 163.)

.meta:n Making a meta is handled internally.

```

10053 \cs_new_protected:cpn { \c__keys_props_root_tl .meta:n } #1
10054 { \__keys_meta_make:n {#1} }

```

(End definition for .meta:n. This function is documented on page 163.)

.meta:nn Meta with path: potentially lots of variants, but for the moment no so many defined.

```

10055 \cs_new_protected:cpn { \c__keys_props_root_tl .meta:nn } #1
10056 { \__keys_meta_make:nn #1 }

```

(End definition for .meta:nn. This function is documented on page 163.)

.multichoice: The same idea as .choice: and .choices:nn, but where more than one choice is allowed.

.multichoices:nn

```

10057 \cs_new_protected:cpn { \c__keys_props_root_tl .multichoice: }
10058 { \__keys_multichoice_make: }
.multichoices:Vn 10059 \cs_new_protected:cpn { \c__keys_props_root_tl .multichoices:nn } #1
10060 { \__keys_multichoices_make:nn #1 }
.multichoices:on 10061 \cs_new_protected:cpn { \c__keys_props_root_tl .multichoices:Vn } #1
10062 { \exp_args:NV \__keys_multichoices_make:nn #1 }
10063 \cs_new_protected:cpn { \c__keys_props_root_tl .multichoices:on } #1
10064 { \exp_args:No \__keys_multichoices_make:nn #1 }
10065 \cs_new_protected:cpn { \c__keys_props_root_tl .multichoices:xn } #1
10066 { \exp_args:Nx \__keys_multichoices_make:nn #1 }

```

(End definition for .multichoice: and .multichoices:nn. These functions are documented on page 163.)

.skip_set:N Setting a variable is very easy: just pass the data along.

```

.skip_set:c 10067 \cs_new_protected:cpn { \c__keys_props_root_tl .skip_set:N } #1
.skip_gset:N 10068 { \__keys_variable_set:NnnN #1 { skip } { } n }
.skip_gset:c 10069 \cs_new_protected:cpn { \c__keys_props_root_tl .skip_set:c } #1
10070 { \__keys_variable_set:cnnN {#1} { skip } { } n }
10071 \cs_new_protected:cpn { \c__keys_props_root_tl .skip_gset:N } #1
10072 { \__keys_variable_set:NnnN #1 { skip } { g } n }
10073 \cs_new_protected:cpn { \c__keys_props_root_tl .skip_gset:c } #1
10074 { \__keys_variable_set:cnnN {#1} { skip } { g } n }

```

(End definition for .skip_set:N and .skip_gset:N. These functions are documented on page 163.)

```

.tl_set:N Setting a variable is very easy: just pass the data along.
.tl_set:c 10075 \cs_new_protected:cpn { \c__keys_props_root_tl .tl_set:N } #1
.tl_gset:N 10076 { \__keys_variable_set:NnnN #1 { tl } { } n }
.tl_gset:c 10077 \cs_new_protected:cpn { \c__keys_props_root_tl .tl_set:c } #1
.tl_set_x:N 10078 { \__keys_variable_set:cnnN {#1} { tl } { } n }
.tl_set_x:c 10079 \cs_new_protected:cpn { \c__keys_props_root_tl .tl_set_x:N } #1
.tl_gset_x:N 10080 { \__keys_variable_set:NnnN #1 { tl } { } x }
.tl_gset_x:c 10081 \cs_new_protected:cpn { \c__keys_props_root_tl .tl_set_x:c } #1
10082 { \__keys_variable_set:cnnN {#1} { tl } { } x }
10083 \cs_new_protected:cpn { \c__keys_props_root_tl .tl_gset:N } #1
10084 { \__keys_variable_set:NnnN #1 { tl } { g } n }
10085 \cs_new_protected:cpn { \c__keys_props_root_tl .tl_gset:c } #1
10086 { \__keys_variable_set:cnnN {#1} { tl } { g } n }
10087 \cs_new_protected:cpn { \c__keys_props_root_tl .tl_gset_x:N } #1
10088 { \__keys_variable_set:NnnN #1 { tl } { g } x }
10089 \cs_new_protected:cpn { \c__keys_props_root_tl .tl_gset_x:c } #1
10090 { \__keys_variable_set:cnnN {#1} { tl } { g } x }

```

(End definition for .tl_set:N and others. These functions are documented on page 163.)

.undefine: Another simple wrapper.

```

10091 \cs_new_protected:cpn { \c__keys_props_root_tl .undefine: }
10092 { \__keys_undefine: }

```

(End definition for .undefine:. This function is documented on page 164.)

.value_forbidden:n These are very similar, so both call the same function.

```

.value_required:n 10093 \cs_new_protected:cpn { \c__keys_props_root_tl .value_forbidden:n } #1
10094 { \__keys_value_requirement:nn { forbidden } {#1} }
10095 \cs_new_protected:cpn { \c__keys_props_root_tl .value_required:n } #1
10096 { \__keys_value_requirement:nn { required } {#1} }

```

(End definition for .value_forbidden:n and .value_required:n. These functions are documented on page 164.)

18.6 Setting keys

\keys_set:nn A simple wrapper again.

```

\keys_set:nV 10097 \cs_new_protected:Npn \keys_set:nn
\keys_set:nv 10098 { \__keys_set:onnn { \l__keys_module_tl } }
\keys_set:no 10099 \cs_new_protected:Npn \__keys_set:nnn #1#2#3
\__keys_set:nnn 10100 {
\__keys_set:onnn 10101 \tl_set:Nx \l__keys_module_tl { \__keys_remove_spaces:n {#2} }
10102 \keyval_parse:NNn \__keys_set:n \__keys_set:nn {#3}
10103 \tl_set:Nn \l__keys_module_tl {#1}
10104 }
10105 \cs_generate_variant:Nn \keys_set:nn { nV , nv , no }
10106 \cs_generate_variant:Nn \__keys_set:nnn { o }

```

(End definition for \keys_set:nn and __keys_set:nnn. These functions are documented on page 167.)

\keys_set_known:nnN

\keys_set_known:nVN

\keys_set_known:nvN

\keys_set_known:noN

__keys_set_known:nnnN

__keys_set_known:onnN

\keys_set_known:nn

\keys_set_known:nV

\keys_set_known:nv

\keys_set_known:no

Setting known keys simply means setting the appropriate flag, then running the standard code. To allow for nested setting, any existing value of `\l__keys_unused_clist` is saved on the stack and reset afterwards. Note that for speed/simplicity reasons we use a `tl` operation to set the `clist` here!

```
10107 \cs_new_protected:Npn \keys_set_known:nnN
10108 { \__keys_set_known:onnN \l__keys_unused_clist }
10109 \cs_generate_variant:Nn \keys_set_known:nnN { nV , nv , no }
10110 \cs_new_protected:Npn \__keys_set_known:nnnN #1#2#3#4
10111 {
10112   \clist_clear:N \l__keys_unused_clist
10113   \keys_set_known:nn {#2} {#3}
10114   \tl_set:Nx #4 { \exp_not:o { \l__keys_unused_clist } }
10115   \tl_set:Nn \l__keys_unused_clist {#1}
10116 }
10117 \cs_generate_variant:Nn \__keys_set_known:nnnN { o }
10118 \cs_new_protected:Npn \keys_set_known:nn #1#2
10119 {
10120   \bool_set_true:N \l__keys_only_known_bool
10121   \keys_set:nn {#1} {#2}
10122   \bool_set_false:N \l__keys_only_known_bool
10123 }
10124 \cs_generate_variant:Nn \keys_set_known:nn { nV , nv , no }
```

(End definition for `\keys_set_known:nnN`, `__keys_set_known:nnnN`, and `\keys_set_known:nn`. These functions are documented on page 168.)

\keys_set_filter:nnnN

\keys_set_filter:nnVN

\keys_set_filter:nnvN

\keys_set_filter:nnoN

__keys_set_filter:nnnnN

__keys_set_filter:onnN

\keys_set_filter:nnn

\keys_set_filter:nnV

\keys_set_filter:nnv

\keys_set_filter:nno

\keys_set_groups:nnn

\keys_set_groups:nnV

\keys_set_groups:nnv

\keys_set_groups:nno

The idea of setting keys in a selective manner again uses flags wrapped around the basic code. The comments on `\keys_set_known:nnN` also apply here.

```
10125 \cs_new_protected:Npn \keys_set_filter:nnnN
10126 { \__keys_set_filter:onnN \l__keys_unused_clist }
10127 \cs_generate_variant:Nn \keys_set_filter:nnnN { nnV , nnv , nno }
10128 \cs_new_protected:Npn \__keys_set_filter:nnnnN #1#2#3#4#5
10129 {
10130   \clist_clear:N \l__keys_unused_clist
10131   \keys_set_filter:nnn {#2} {#3} {#4}
10132   \tl_set:Nx #5 { \exp_not:o { \l__keys_unused_clist } }
10133   \tl_set:Nn \l__keys_unused_clist {#1}
10134 }
10135 \cs_generate_variant:Nn \__keys_set_filter:nnnnN { o }
10136 \cs_new_protected:Npn \keys_set_filter:nnn #1#2#3
10137 {
10138   \bool_set_true:N \l__keys_selective_bool
10139   \bool_set_true:N \l__keys_filtered_bool
10140   \seq_set_from_clist:Nn \l__keys_selective_seq {#2}
10141   \keys_set:nn {#1} {#3}
10142   \bool_set_false:N \l__keys_selective_bool
10143 }
10144 \cs_generate_variant:Nn \keys_set_filter:nnn { nnV , nnv , nno }
10145 \cs_new_protected:Npn \keys_set_groups:nnn #1#2#3
10146 {
10147   \bool_set_true:N \l__keys_selective_bool
10148   \bool_set_false:N \l__keys_filtered_bool
10149   \seq_set_from_clist:Nn \l__keys_selective_seq {#2}
10150   \keys_set:nn {#1} {#3}
```

```

10151     \bool_set_false:N \l__keys_selective_bool
10152   }
10153   \cs_generate_variant:Nn \keys_set_groups:nnn { nnV , nnv , nno }

```

(End definition for \keys_set_filter:nnnN and others. These functions are documented on page 169.)

```

\__keys_set:n A shared system once again. First, set the current path and add a default if needed.
\__keys_set:nn There are then checks to see if the a value is required or forbidden. If everything passes,
\__keys_set_aux:nnn move on to execute the code.
\__keys_set_aux:onn
\__keys_find_key_module:w
\__keys_set_aux:
\__keys_set_selective:
10154 \cs_new_protected:Npn \__keys_set:n #1
10155 {
10156     \bool_set_true:N \l__keys_no_value_bool
10157     \__keys_set_aux:onn \l__keys_module_tl {#1} { }
10158 }
10159 \cs_new_protected:Npn \__keys_set:nn #1#2
10160 {
10161     \bool_set_false:N \l__keys_no_value_bool
10162     \__keys_set_aux:onn \l__keys_module_tl {#1} {#2}
10163 }

```

The key path here can be fully defined, after which there is a search for the key and module names: the user may have passed them with part of what is actually the module (for our purposes) in the key name. As that happens on a per-key basis, we use the stack approach to restore the module name without a group.

```

10164 \cs_new_protected:Npn \__keys_set_aux:nnn #1#2#3
10165 {
10166     \tl_set:Nx \l_keys_path_tl
10167     {
10168         \tl_if_blank:nF {#1}
10169         { #1 / }
10170         \__keys_remove_spaces:n {#2}
10171     }
10172     \tl_clear:N \l__keys_module_tl
10173     \exp_after:wN \__keys_find_key_module:w \l_keys_path_tl / \q_stop
10174     \__keys_value_or_default:n {#3}
10175     \bool_if:NTF \l__keys_selective_bool
10176     { \__keys_set_selective: }
10177     { \__keys_execute: }
10178     \tl_set:Nn \l__keys_module_tl {#1}
10179 }
10180 \cs_generate_variant:Nn \__keys_set_aux:nnn { o }
10181 \cs_new_protected:Npn \__keys_find_key_module:w #1 / #2 \q_stop
10182 {
10183     \tl_if_blank:nTF {#2}
10184     { \tl_set:Nn \l_keys_key_tl {#1} }
10185     {
10186         \tl_put_right:Nx \l__keys_module_tl
10187         {
10188             \tl_if_empty:NF \l__keys_module_tl { / }
10189             #1
10190         }
10191         \__keys_find_key_module:w #2 \q_stop
10192     }
10193 }

```


If selective setting is active, there are a number of possible sub-cases to consider. The key name may not be known at all or if it is, it may not have any groups assigned. There is then the question of whether the selection is opt-in or opt-out.

```

10194 \cs_new_protected:Npn \__keys_set_selective:
10195 {
10196   \cs_if_exist:cTF { \c__keys_groups_root_tl \l_keys_path_tl }
10197   {
10198     \clist_set_eq:Nc \l__keys_groups_clist
10199     { \c__keys_groups_root_tl \l_keys_path_tl }
10200     \__keys_check_groups:
10201   }
10202   {
10203     \bool_if:NTF \l__keys_filtered_bool
10204     { \__keys_execute: }
10205     { \__keys_store_unused: }
10206   }
10207 }

```

In the case where selective setting requires a comparison of the list of groups which apply to a key with the list of those which have been set active. That requires two mappings, and again a different outcome depending on whether opt-in or opt-out is set.

```

10208 \cs_new_protected:Npn \__keys_check_groups:
10209 {
10210   \bool_set_false:N \l__keys_tmp_bool
10211   \seq_map_inline:Nn \l__keys_selective_seq
10212   {
10213     \clist_map_inline:Nn \l__keys_groups_clist
10214     {
10215       \str_if_eq:nnT {##1} {####1}
10216       {
10217         \bool_set_true:N \l__keys_tmp_bool
10218         \clist_map_break:n { \seq_map_break: }
10219       }
10220     }
10221   }
10222   \bool_if:NTF \l__keys_tmp_bool
10223   {
10224     \bool_if:NTF \l__keys_filtered_bool
10225     { \__keys_store_unused: }
10226     { \__keys_execute: }
10227   }
10228   {
10229     \bool_if:NTF \l__keys_filtered_bool
10230     { \__keys_execute: }
10231     { \__keys_store_unused: }
10232   }
10233 }

```

(End definition for __keys_set:n and others.)

__keys_value_or_default:n If a value is given, return it as #1, otherwise send a default if available.

```

10234 \cs_new_protected:Npn \__keys_value_or_default:n #1
10235 {
10236   \bool_if:NTF \l__keys_no_value_bool

```

```

10237     {
10238         \cs_if_exist:cTF { \c__keys_default_root_tl \l_keys_path_tl }
10239         {
10240             \tl_set_eq:Nc
10241                 \l_keys_value_tl
10242                 { \c__keys_default_root_tl \l_keys_path_tl }
10243         }
10244         { \tl_clear:N \l_keys_value_tl }
10245     }
10246     { \tl_set:Nn \l_keys_value_tl {#1} }
10247 }

```

(End definition for __keys_value_or_default:n.)

__keys_execute: Actually executing a key is done in two parts. First, look for the key itself, then look for the **unknown** key with the same path. If both of these fail, complain. What exactly happens if a key is unknown depends on whether unknown keys are being skipped or if an error should be raised.

```

10248 \cs_new_protected:Npn \__keys_execute:
10249 {
10250     \cs_if_exist:cTF { \c__keys_code_root_tl \l_keys_path_tl }
10251     {
10252         \cs_if_exist_use:c { \c__keys_validate_root_tl \l_keys_path_tl }
10253         \cs:w \c__keys_code_root_tl \l_keys_path_tl \exp_after:wN \cs_end:
10254         \exp_after:wN { \l_keys_value_tl }
10255     }
10256     { \__keys_execute_unknown: }
10257 }
10258 \cs_new_protected:Npn \__keys_execute_unknown:
10259 {
10260     \bool_if:NTF \l__keys_only_known_bool
10261     { \__keys_store_unused: }
10262     {
10263         \cs_if_exist:cTF
10264         { \c__keys_inherit_root_tl \__keys_parent:o \l_keys_path_tl }
10265         {
10266             \clist_map_inline:cn
10267             { \c__keys_inherit_root_tl \__keys_parent:o \l_keys_path_tl }
10268             {
10269                 \cs_if_exist:cT
10270                 { \c__keys_code_root_tl ##1 / \l_keys_key_tl }
10271                 {
10272                     \cs:w \c__keys_code_root_tl ##1 / \l_keys_key_tl
10273                     \exp_after:wN \cs_end: \exp_after:wN
10274                     { \l_keys_value_tl }
10275                     \clist_map_break:
10276                 }
10277             }
10278         }
10279         {
10280             \cs_if_exist:cTF { \c__keys_code_root_tl \l__keys_module_tl / unknown }
10281             {
10282                 \cs:w \c__keys_code_root_tl \l__keys_module_tl / unknown
10283                 \exp_after:wN \cs_end: \exp_after:wN { \l_keys_value_tl }

```

```

10284         }
10285         {
10286             \_msg_kernel_error:nxx { kernel } { key-unknown }
10287             { \l_keys_path_tl } { \l__keys_module_tl }
10288         }
10289     }
10290 }
10291 }
10292 \cs_new:Npn \__keys_execute:nn #1#2
10293 {
10294     \cs_if_exist:cTF { \c__keys_code_root_tl #1 }
10295     {
10296         \cs:w \c__keys_code_root_tl #1 \exp_after:wN \cs_end:
10297         \exp_after:wN { \l_keys_value_tl }
10298     }
10299     {#2}
10300 }
10301 \cs_new_protected:Npn \__keys_store_unused:
10302 {
10303     \clist_put_right:Nx \l__keys_unused_clist
10304     {
10305         \exp_not:o \l_keys_key_tl
10306         \bool_if:NF \l__keys_no_value_bool
10307         { = { \exp_not:o \l_keys_value_tl } }
10308     }
10309 }

```

(End definition for __keys_execute: and others.)

__keys_choice_find:n Executing a choice has two parts. First, try the choice given, then if that fails call the
 __keys_multichoice_find:n unknown key. That will exist, as it is created when a choice is first made. So there is no
 need for any escape code. For multiple choices, the same code ends up used in a mapping.

```

10310 \cs_new:Npn \__keys_choice_find:n #1
10311 {
10312     \__keys_execute:nn { \l_keys_path_tl / \__keys_remove_spaces:n {#1} }
10313     { \__keys_execute:nn { \l_keys_path_tl / unknown } { } }
10314 }
10315 \cs_new:Npn \__keys_multichoice_find:n #1
10316 { \clist_map_function:nN {#1} \__keys_choice_find:n }

```

(End definition for __keys_choice_find:n and __keys_multichoice_find:n.)

18.7 Utilities

__keys_parent:n Used to strip off the ending part of the key path after the last /.

```

\__keys_parent:o
\__keys_parent:w
10317 \cs_new:Npn \__keys_parent:n #1
10318 { \__keys_parent:w #1 / / \q_stop { } }
10319 \cs_generate_variant:Nn \__keys_parent:n { o }
10320 \cs_new:Npn \__keys_parent:w #1 / #2 / #3 \q_stop #4
10321 {
10322     \tl_if_blank:nTF {#2}
10323     { \use_none:n #4 }
10324     {
10325         \__keys_parent:w #2 / #3 \q_stop { #4 / #1 }

```

```

10326     }
10327 }

```

(End definition for `_keys_parent:n` and `_keys_parent:w`.)

`_keys_remove_spaces:n` Removes all spaces from the input which is detokenized as a result. This function has the same effect as `\zap@space` in L^AT_EX 2_ε after applying `\tl_to_str:n`. It is set up to be fast as the use case here is tightly defined. The `?` is only there to allow for a space after `\use_none:nn` responsible for ending the loop.

`_keys_remove_spaces:w`

```

10328 \cs_new:Npn \_keys_remove_spaces:n #1
10329 {
10330   \exp_after:wN \_keys_remove_spaces:w \tl_to_str:n {#1}
10331   \use_none:nn ? ~
10332 }
10333 \cs_new:Npn \_keys_remove_spaces:w #1 ~
10334 { #1 \_keys_remove_spaces:w }

```

(End definition for `_keys_remove_spaces:n` and `_keys_remove_spaces:w`.)

`\keys_if_exist:p:nn` A utility for others to see if a key exists.

`\keys_if_exist:nnTF`

```

10335 \prg_new_conditional:Npnn \keys_if_exist:nn #1#2 { p , T , F , TF }
10336 {
10337   \cs_if_exist:cTF
10338   { \c__keys_code_root_tl \_keys_remove_spaces:n { #1 / #2 } }
10339   { \prg_return_true: }
10340   { \prg_return_false: }
10341 }

```

(End definition for `\keys_if_exist:nnTF`. This function is documented on page 169.)

`\keys_if_choice_exist:p:nnn` Just an alternative view on `\keys_if_exist:nnTF`.

`\keys_if_choice_exist:nnnTF`

```

10342 \prg_new_conditional:Npnn \keys_if_choice_exist:nnn #1#2#3
10343 { p , T , F , TF }
10344 {
10345   \cs_if_exist:cTF
10346   { \c__keys_code_root_tl \_keys_remove_spaces:n { #1 / #2 / #3 } }
10347   { \prg_return_true: }
10348   { \prg_return_false: }
10349 }

```

(End definition for `\keys_if_choice_exist:nnnTF`. This function is documented on page 169.)

`\keys_show:nn` To show a key, test for its existence to issue the correct message (same message, but with a `t` or `f` argument, then build the control sequences which contain the code and other information about the key, call an intermediate auxiliary which constructs the code that will be displayed to the terminal, and finally conclude with `_msg_show_wrap:n`.

`_keys_show:N`

```

10350 \cs_new_protected:Npn \keys_show:nn #1#2
10351 {
10352   \keys_if_exist:nnTF {#1} {#2}
10353   {
10354     \_msg_show_pre:nnxxx { LaTeX / kernel } { show-key }
10355     { \_keys_remove_spaces:n { #1 / #2 } } { t } { } { }
10356     \exp_args:Nc \_keys_show:N
10357     { \c__keys_code_root_tl \_keys_remove_spaces:n { #1 / #2 } }

```

```

10358     }
10359     {
10360         \_msg_show_pre:nnxxx { LaTeX / kernel } { show-key }
10361         { \_keys_remove_spaces:n { #1 / #2 } } { f } { } { }
10362         \_msg_show_wrap:n { }
10363     }
10364 }
10365 \cs_new_protected:Npn \_keys_show:N #1
10366 {
10367     \use:x
10368     {
10369         \_msg_show_wrap:n
10370         {
10371             \exp_not:N \_msg_show_item_unbraced:nn { code }
10372             { \token_get_replacement_spec:N #1 }
10373         }
10374     }
10375 }

```

(End definition for `\keys_show:nn` and `_keys_show:N`. These functions are documented on page 169.)

`\keys_log:nn` Redirect output of `\keys_show:nn` to the log.

```

10376 \cs_new_protected:Npn \keys_log:nn
10377 { \_msg_log_next: \keys_show:nn }

```

(End definition for `\keys_log:nn`. This function is documented on page 169.)

18.8 Messages

For when there is a need to complain.

```

10378 \_msg_kernel_new:nnnn { kernel } { boolean-values-only }
10379 { Key~'#1'~accepts~boolean~values~only. }
10380 { The~key~'#1'~only~accepts~the~values~'true'~and~'false'. }
10381 \_msg_kernel_new:nnnn { kernel } { key-choice-unknown }
10382 { Key~'#1'~accepts~only~a~fixed~set~of~choices. }
10383 {
10384     The~key~'#1'~only~accepts~predefined~values,~
10385     and~'#2'~is~not~one~of~these.
10386 }
10387 \_msg_kernel_new:nnnn { kernel } { key-no-property }
10388 { No~property~given~in~definition~of~key~'#1'. }
10389 {
10390     \c__msg_coding_error_text_tl
10391     Inside~\keys_define:nn each~key~name~
10392     needs~a~property: \ \ \
10393     \iow_indent:n { #1 .<property> } \ \ \
10394     LaTeX~did~not~find~a~'. ' ~to~indicate~the~start~of~a~property.
10395 }
10396 \_msg_kernel_new:nnnn { kernel } { key-unknown }
10397 { The~key~'#1'~is~unknown~and~is~being~ignored. }
10398 {
10399     The~module~'#2'~does~not~have~a~key~called~'#1'. \ \
10400     Check~that~you~have~spelled~the~key~name~correctly.
10401 }

```

```

10402 \_msg_kernel_new:nnnn { kernel } { nested-choice-key }
10403 { Attempt-to-define-~'~#1'~as-a-nested-choice-key. }
10404 {
10405   The-key~'~#1'~cannot-be-defined-as-a-choice-as-the-parent-key~'~#2'~is~
10406   itself-a-choice.
10407 }
10408 \_msg_kernel_new:nnnn { kernel } { property-boolean-values-only }
10409 { The-property~'~#1'~accepts-boolean-values-only. }
10410 {
10411   \c_msg_coding_error_text_tl
10412   The-property~'~#1'~only-accepts-the-values~'true'~and~'false'.
10413 }
10414 \_msg_kernel_new:nnnn { kernel } { property-requires-value }
10415 { The-property~'~#1'~requires-a-value. }
10416 {
10417   \c_msg_coding_error_text_tl
10418   LaTeX-was-asked-to-set-property~'~#1'~for-key~'~#2'~.\\
10419   No-value-was-given-for-the-property,~and-one-is-required.
10420 }
10421 \_msg_kernel_new:nnnn { kernel } { property-unknown }
10422 { The-key-property~'~#1'~is-unknown. }
10423 {
10424   \c_msg_coding_error_text_tl
10425   LaTeX-has-been-asked-to-set-the-property~'~#1'~for-key~'~#2':~
10426   this-property-is-not-defined.
10427 }
10428 \_msg_kernel_new:nnnn { kernel } { value-forbidden }
10429 { The-key~'~#1'~does-not-take-a-value. }
10430 {
10431   The-key~'~#1'~should-be-given-without-a-value.\\
10432   The-value~'~#2'~was-present:~the-key-will-be-ignored.
10433 }
10434 \_msg_kernel_new:nnnn { kernel } { value-required }
10435 { The-key~'~#1'~requires-a-value. }
10436 {
10437   The-key~'~#1'~must-have-a-value.\\
10438   No-value-was-present:~the-key-will-be-ignored.
10439 }
10440 \_msg_kernel_new:nnn { kernel } { show-key }
10441 {
10442   The-key~#1~
10443   \str_if_eq:nnTF {#2} { t }
10444   { has-the-properties: }
10445   { is-undefined. }
10446 }
10447 </initex | package>

```

19 l3fp implementation

Nothing to see here: everything is in the subfiles!

20 l3fp-aux implementation

10448 $\langle *initex \mid package \rangle$

10449 $\langle @@=fp \rangle$

20.1 Internal representation

Internally, a floating point number $\langle X \rangle$ is a token list containing

$\backslash s_fp \backslash_fp_chk:w \langle case \rangle \langle sign \rangle \langle body \rangle ;$

Let us explain each piece separately.

Internal floating point numbers will be used in expressions, and in this context will be subject to f-expansion. They must leave a recognizable mark after f-expansion, to prevent the floating point number from being re-parsed. Thus, $\backslash s_fp$ is simply another name for $\backslash relax$.

Since floating point numbers are always accessed by the various operations using f-expansion, we can safely let them be protected: x-expansion will then leave them untouched. However, when used directly without an accessor function, floating points should produce an error. $\backslash s_fp$ will do nothing, and $\backslash_fp_chk:w$ produces an error.

The (decimal part of the) IEEE-754-2008 standard requires the format to be able to represent special floating point numbers besides the usual positive and negative cases. The various possibilities will be distinguished by their $\langle case \rangle$, which is a single digit:⁹

- 0 zeros: +0 and -0,
- 1 “normal” numbers (positive and negative),
- 2 infinities: +inf and -inf,
- 3 quiet and signalling nan.

The $\langle sign \rangle$ is 0 (positive) or 2 (negative), except in the case of **nan**, which have $\langle sign \rangle = 1$. This ensures that changing the $\langle sign \rangle$ digit to $2 - \langle sign \rangle$ is exactly equivalent to changing the sign of the number.

Special floating point numbers have the form

$\backslash s_fp \backslash_fp_chk:w \langle case \rangle \langle sign \rangle \backslash s_fp_... ;$

where $\backslash s_fp_...$ is a scan mark carrying information about how the number was formed (useful for debugging).

Normal floating point numbers ($\langle case \rangle = 1$) have the form

$\backslash s_fp \backslash_fp_chk:w 1 \langle sign \rangle \{ \langle exponent \rangle \} \{ \langle X_1 \rangle \} \{ \langle X_2 \rangle \} \{ \langle X_3 \rangle \} \{ \langle X_4 \rangle \} ;$

Here, the $\langle exponent \rangle$ is an integer, at most $\backslash c_fp_max_exponent_int = 10000$ in absolute value. The body consists in four blocks of exactly 4 digits, $0000 \leq \langle X_i \rangle \leq 9999$, such that

$$\langle X \rangle = (-1)^{\langle sign \rangle} 10^{-\langle exponent \rangle} \sum_{i=1}^4 \langle X_i \rangle 10^{-4i}$$

and such that the $\langle exponent \rangle$ is minimal. This implies $1000 \leq \langle X_1 \rangle \leq 9999$.

⁹Bruno: I need to implement subnormal numbers. Also, quiet and signalling **nan** must be better distinguished.

Table 1: Internal representation of floating point numbers.

| Representation | Meaning |
|---|--------------------------|
| 0 0 \s_fp_... ; | Positive zero. |
| 0 2 \s_fp_... ; | Negative zero. |
| 1 0 {\exponent} {\langle X_1 \rangle} {\langle X_2 \rangle} {\langle X_3 \rangle} {\langle X_4 \rangle} ; | Positive floating point. |
| 1 2 {\exponent} {\langle X_1 \rangle} {\langle X_2 \rangle} {\langle X_3 \rangle} {\langle X_4 \rangle} ; | Negative floating point. |
| 2 0 \s_fp_... ; | Positive infinity. |
| 2 2 \s_fp_... ; | Negative infinity. |
| 3 1 \s_fp_... ; | Quiet nan. |
| 3 1 \s_fp_... ; | Signalling nan. |

20.2 Internal storage of floating points numbers

A floating point number $\langle X \rangle$ is stored as

`\s_fp _fp_chk:w \langle case \rangle \langle sign \rangle \langle body \rangle ;`

Here, $\langle case \rangle$ is 0 for ± 0 , 1 for normal numbers, 2 for $\pm\infty$, and 3 for nan, and $\langle sign \rangle$ is 0 for positive numbers, 1 for nans, and 2 for negative numbers. The $\langle body \rangle$ of normal numbers is $\{\langle exponent \rangle\} \{\langle X_1 \rangle\} \{\langle X_2 \rangle\} \{\langle X_3 \rangle\} \{\langle X_4 \rangle\}$, with

$$\langle X \rangle = (-1)^{\langle sign \rangle} 10^{-\langle exponent \rangle} \sum_i \langle X_i \rangle 10^{-4i}.$$

Calculations are done in base 10000, *i.e.* one myriad. The $\langle exponent \rangle$ lies between $\pm c_fp_max_exponent_int = \pm 10000$ inclusive.

Additionally, positive and negative floating point numbers may only be stored with $1000 \leq \langle X_1 \rangle < 10000$. This requirement is necessary in order to preserve accuracy and speed.

20.3 Using arguments and semicolons

`_fp_use_none_stop_f:n` This function removes an argument (typically a digit) and replaces it by `\exp_stop_f:`, a marker which stops f-type expansion.

10450 `\cs_new:Npn _fp_use_none_stop_f:n #1 { \exp_stop_f: }`

(End definition for `_fp_use_none_stop_f:n`.)

`_fp_use_s:n` Those functions place a semicolon after one or two arguments (typically digits).

`_fp_use_s:nn` 10451 `\cs_new:Npn _fp_use_s:n #1 { #1; }`
10452 `\cs_new:Npn _fp_use_s:nn #1#2 { #1#2; }`

(End definition for `_fp_use_s:n` and `_fp_use_s:nn`.)

`_fp_use_none_until_s:w` Those functions select specific arguments among a set of arguments delimited by a semicolon.
`_fp_use_i_until_s:nw`
`_fp_use_ii_until_s:nnw`

10453 `\cs_new:Npn _fp_use_none_until_s:w #1; { }`
10454 `\cs_new:Npn _fp_use_i_until_s:nw #1#2; { #1 }`
10455 `\cs_new:Npn _fp_use_ii_until_s:nnw #1#2#3; { #2 }`

(End definition for `_fp_use_none_until_s:w`, `_fp_use_i_until_s:nw`, and `_fp_use_ii_until_s:nnw`.)

`__fp_reverse_args:Nww` Many internal functions take arguments delimited by semicolons, and it is occasionally useful to swap two such arguments.

```
10456 \cs_new:Npn \__fp_reverse_args:Nww #1 #2; #3; { #1 #3; #2; }
```

(End definition for `__fp_reverse_args:Nww`.)

`__fp_rrot:www` Rotate three arguments delimited by semicolons. This is the inverse (or the square) of the Forth primitive ROT.

```
10457 \cs_new:Npn \__fp_rrot:www #1; #2; #3; { #2; #3; #1; }
```

(End definition for `__fp_rrot:www`.)

`__fp_use_i:ww` Many internal functions take arguments delimited by semicolons, and it is occasionally useful to remove one or two such arguments.

```
10458 \cs_new:Npn \__fp_use_i:ww #1; #2; { #1; }
```

```
10459 \cs_new:Npn \__fp_use_i:www #1; #2; #3; { #1; }
```

(End definition for `__fp_use_i:ww` and `__fp_use_i:www`.)

20.4 Constants, and structure of floating points

`\s__fp` Floating points numbers all start with `\s__fp __fp_chk:w`, where `\s__fp` is equal to the TeX primitive `\relax`, and `__fp_chk:w` is protected. The rest of the floating point number is made of characters (or `\relax`). This ensures that nothing expands under f-expansion, nor under x-expansion. However, when typeset, `\s__fp` does nothing, and `__fp_chk:w` is expanded. We define `__fp_chk:w` to produce an error.

```
10460 \__scan_new:N \s__fp
10461 \cs_new_protected:Npn \__fp_chk:w #1 ;
10462 {
10463   \__msg_kernel_error:nnx { kernel } { misused-fp }
10464   { \fp_to_tl:n { \s__fp \__fp_chk:w #1 ; } }
10465 }
```

(End definition for `\s__fp` and `__fp_chk:w`.)

`\s__fp_mark` Aliases of `\tex_relax:D`, used to terminate expressions.

```
\s__fp_stop 10466 \__scan_new:N \s__fp_mark
10467 \__scan_new:N \s__fp_stop
```

(End definition for `\s__fp_mark` and `\s__fp_stop`.)

`\s__fp_invalid` A couple of scan marks used to indicate where special floating point numbers come from.

```
\s__fp_underflow 10468 \__scan_new:N \s__fp_invalid
\s__fp_overflow 10469 \__scan_new:N \s__fp_underflow
\s__fp_division 10470 \__scan_new:N \s__fp_overflow
\s__fp_exact 10471 \__scan_new:N \s__fp_division
10472 \__scan_new:N \s__fp_exact
```

(End definition for `\s__fp_invalid` and others.)

`\c_zero_fp` The special floating points. All of them have the form
`\c_minus_zero_fp` `\s__fp __fp_chk:w <case> <sign> \s__fp...` ;
`\c_inf_fp`
`\c_minus_inf_fp`
`\c_nan_fp`

where the dots in `\s__fp...` are one of `invalid`, `underflow`, `overflow`, `division`, `exact`, describing how the floating point was created. We define the floating points here as “exact”.

```

10473 \tl_const:Nn \c_zero_fp      { \s__fp \__fp_chk:w 0 0 \s__fp_exact ; }
10474 \tl_const:Nn \c_minus_zero_fp { \s__fp \__fp_chk:w 0 2 \s__fp_exact ; }
10475 \tl_const:Nn \c_inf_fp       { \s__fp \__fp_chk:w 2 0 \s__fp_exact ; }
10476 \tl_const:Nn \c_minus_inf_fp { \s__fp \__fp_chk:w 2 2 \s__fp_exact ; }
10477 \tl_const:Nn \c_nan_fp       { \s__fp \__fp_chk:w 3 1 \s__fp_exact ; }

```

(End definition for `\c_zero_fp` and others. These variables are documented on page 178.)

```

\c__fp_prec_int  The number of digits of floating points.
\c__fp_half_prec_int 10478 \int_const:Nn \c__fp_prec_int { 16 }
\c__fp_block_int  10479 \int_const:Nn \c__fp_half_prec_int { 8 }
                  10480 \int_const:Nn \c__fp_block_int { 4 }

```

(End definition for `\c__fp_prec_int`, `\c__fp_half_prec_int`, and `\c__fp_block_int`.)

```

\c__fp_myriad_int Blocks have 4 digits so this integer is useful.
                  10481 \int_const:Nn \c__fp_myriad_int { 10000 }

```

(End definition for `\c__fp_myriad_int`.)

```

\c__fp_max_exponent_int Normal floating point numbers have an exponent at most max_exponent in absolute
                        value. Larger numbers are rounded to  $\pm\infty$ . Smaller numbers are subnormal (not im-
                        plemented yet), and digits beyond  $10^{-\text{max\_exponent}}$  are rounded away, hence the true min-
                        imum exponent is  $-\text{max\_exponent} - 16$ ; beyond this, numbers are rounded to zero.
                        Why this choice of limits? When computing  $(a \cdot 10^n)^{(b \cdot 10^p)}$ , we need to evaluate
                         $\log(a \cdot 10^n) = \log(a) + n \log(10)$  as a fixed point number, which we manipulate as blocks
                        of 4 digits. Multiplying such a fixed point number by  $n < 10000$  is much cheaper than
                        larger  $n$ , because we can multiply  $n$  with each block safely.

```

```

10482 \int_const:Nn \c__fp_max_exponent_int { 10000 }

```

(End definition for `\c__fp_max_exponent_int`.)

```

\c__fp_max_exp_exponent_int If a number's exponent is larger than that, its exponential overflows/underflows.

```

```

10483 \int_const:Nn \c__fp_max_exp_exponent_int { 5 }

```

(End definition for `\c__fp_max_exp_exponent_int`.)

```

\__fp_zero_fp:N In case of overflow or underflow, we have to output a zero or infinity with a given sign.
\__fp_inf_fp:N

```

```

10484 \cs_new:Npn \__fp_zero_fp:N #1
10485   { \s__fp \__fp_chk:w 0 #1 \s__fp_underflow ; }
10486 \cs_new:Npn \__fp_inf_fp:N #1
10487   { \s__fp \__fp_chk:w 2 #1 \s__fp_overflow ; }

```

(End definition for `__fp_zero_fp:N` and `__fp_inf_fp:N`.)

`__fp_max_fp:N` In some cases, we need to output the smallest or biggest positive or negative finite numbers.
`__fp_min_fp:N`

```

10488 \cs_new:Npn \__fp_min_fp:N #1
10489 {
10490   \s__fp \__fp_chk:w 1 #1
10491   { \int_eval:n { - \c__fp_max_exponent_int } }
10492   {1000} {0000} {0000} {0000} ;
10493 }
10494 \cs_new:Npn \__fp_max_fp:N #1
10495 {
10496   \s__fp \__fp_chk:w 1 #1
10497   { \int_use:N \c__fp_max_exponent_int }
10498   {9999} {9999} {9999} {9999} ;
10499 }
```

(End definition for `__fp_max_fp:N` and `__fp_min_fp:N`.)

`__fp_exponent:w` For normal numbers, the function expands to the exponent, otherwise to 0.

```

10500 \cs_new:Npn \__fp_exponent:w \s__fp \__fp_chk:w #1
10501 {
10502   \if_meaning:w 1 #1
10503     \exp_after:wN \__fp_use_ii_until_s:nnw
10504   \else:
10505     \exp_after:wN \__fp_use_i_until_s:nw
10506     \exp_after:wN 0
10507   \fi:
10508 }
```

(End definition for `__fp_exponent:w`.)

`__fp_neg_sign:N` When appearing in an integer expression or after `__int_value:w`, this expands to the sign opposite to #1, namely 0 (positive) is turned to 2 (negative), 1 (nan) to 1, and 2 to 0.

```

10509 \cs_new:Npn \__fp_neg_sign:N #1
10510 { \__int_eval:w 2 - #1 \__int_eval_end: }
```

(End definition for `__fp_neg_sign:N`.)

20.5 Overflow, underflow, and exact zero

`__fp_sanitize:Nw` Expects the sign and the exponent in some order, then the significand (which we don't touch). Outputs the corresponding floating point number, possibly underflowed to ± 0
`__fp_sanitize:wN` or overflowed to $\pm\infty$. The functions `__fp_underflow:w` and `__fp_overflow:w` are
`__fp_sanitize_zero:w` defined in `l3fp-traps`.

```

10511 \cs_new:Npn \__fp_sanitize:Nw #1 #2;
10512 {
10513   \if_case:w
10514     \if_int_compare:w #2 > \c__fp_max_exponent_int 1 ~ \else:
10515     \if_int_compare:w #2 < - \c__fp_max_exponent_int 2 ~ \else:
10516     \if_meaning:w 1 #1 3 ~ \else: 0 ~ \fi: \fi: \fi:
10517   \or: \exp_after:wN \__fp_overflow:w
10518   \or: \exp_after:wN \__fp_underflow:w
10519   \or: \exp_after:wN \__fp_sanitize_zero:w
10520   \fi:
```

```

10521 \s__fp \__fp_chk:w 1 #1 {#2}
10522 }
10523 \cs_new:Npn \__fp_sanitizewN #1; #2 { \__fp_sanitizewN #2 #1; }
10524 \cs_new:Npn \__fp_sanitizewZero:w \s__fp \__fp_chk:w #1 #2 #3;
10525 { \c_zero_fp }

(End definition for \__fp_sanitizewN, \__fp_sanitizewN, and \__fp_sanitizewZero:w.)

```

20.6 Expanding after a floating point number

`__fp_exp_after_o:w` Places *<tokens>* (empty in the case of `__fp_exp_after_o:w`) between the *<floating point>* and the *<more tokens>*, then hits those tokens with either o-expansion (one `\exp_after:wN`) or f-expansion, and leaves the floating point number unchanged.

We first distinguish normal floating points, which have a significand, from the much simpler special floating points.

```

10526 \cs_new:Npn \__fp_exp_after_o:w \s__fp \__fp_chk:w #1
10527 {
10528   \if_meaning:w 1 #1
10529     \exp_after:wN \__fp_exp_after_normal:nNNw
10530   \else:
10531     \exp_after:wN \__fp_exp_after_special:nNNw
10532   \fi:
10533   { }
10534   #1
10535 }
10536 \cs_new:Npn \__fp_exp_after_o:nw #1 \s__fp \__fp_chk:w #2
10537 {
10538   \if_meaning:w 1 #2
10539     \exp_after:wN \__fp_exp_after_normal:nNNw
10540   \else:
10541     \exp_after:wN \__fp_exp_after_special:nNNw
10542   \fi:
10543   { #1 }
10544   #2
10545 }
10546 \cs_new:Npn \__fp_exp_after_f:nw #1 \s__fp \__fp_chk:w #2
10547 {
10548   \if_meaning:w 1 #2
10549     \exp_after:wN \__fp_exp_after_normal:nNNw
10550   \else:
10551     \exp_after:wN \__fp_exp_after_special:nNNw
10552   \fi:
10553   { \exp:w \exp_end_continue_f:w #1 }
10554   #2
10555 }

```

(End definition for `__fp_exp_after_o:w`, `__fp_exp_after_o:nw`, and `__fp_exp_after_f:nw`.)

`__fp_exp_after_special:nNNw` Special floating point numbers are easy to jump over since they contain few tokens.

```

10556 \cs_new:Npn \__fp_exp_after_special:nNNw #1#2#3#4;
10557 {
10558   \exp_after:wN \s__fp
10559   \exp_after:wN \__fp_chk:w
10560   \exp_after:wN #2

```

```

10561 \exp_after:wN #3
10562 \exp_after:wN #4
10563 \exp_after:wN ;
10564 #1
10565 }

```

(End definition for `__fp_exp_after_special:nNNw`.)

`__fp_exp_after_normal:nNNw`

For normal floating point numbers, life is slightly harder, since we have many tokens to jump over. Here it would be slightly better if the digits were not braced but instead were delimited arguments (for instance delimited by `,`). That may be changed some day.

```

10566 \cs_new:Npn \__fp_exp_after_normal:nNNw #1 1 #2 #3 #4#5#6#7;
10567 {
10568   \exp_after:wN \__fp_exp_after_normal:Nwwwww
10569   \exp_after:wN #2
10570   \__int_value:w #3 \exp_after:wN ;
10571   \__int_value:w 1 #4 \exp_after:wN ;
10572   \__int_value:w 1 #5 \exp_after:wN ;
10573   \__int_value:w 1 #6 \exp_after:wN ;
10574   \__int_value:w 1 #7 \exp_after:wN ; #1
10575 }
10576 \cs_new:Npn \__fp_exp_after_normal:Nwwwww
10577   #1 #2; 1 #3 ; 1 #4 ; 1 #5 ; 1 #6 ;
10578   { \s__fp \__fp_chk:w 1 #1 {#2} {#3} {#4} {#5} {#6} ; }

```

(End definition for `__fp_exp_after_normal:nNNw`.)

`__fp_exp_after_array_f:w`

`__fp_exp_after_stop_f:nw`

```

10579 \cs_new:Npn \__fp_exp_after_array_f:w #1
10580 {
10581   \cs:w \__fp_exp_after \__fp_type_from_scan:N #1 _f:nw \cs_end:
10582   { \__fp_exp_after_array_f:w }
10583   #1
10584 }
10585 \cs_new_eq:NN \__fp_exp_after_stop_f:nw \use_none:nn

```

(End definition for `__fp_exp_after_array_f:w` and `__fp_exp_after_stop_f:nw`.)

20.7 Packing digits

When a positive integer `#1` is known to be less than 10^8 , the following trick will split it into two blocks of 4 digits, padding with zeros on the left.

```

\cs_new:Npn \pack:NNNNNw #1 #2#3#4#5 #6; { {#2#3#4#5} {#6} }
\exp_after:wN \pack:NNNNNw
\__int_value:w \__int_eval:w 1 0000 0000 + #1 ;

```

The idea is that adding 10^8 to the number ensures that it has exactly 9 digits, and can then easily find which digits correspond to what position in the number. Of course, this can be modified for any number of digits less or equal to 9 (we are limited by $\text{T}_{\text{E}}\text{X}$'s integers). This method is very heavily relied upon in `l3fp-basics`.

More specifically, the auxiliary inserts `+ #1#2#3#4#5 ; {#6}`, which allows us to compute several blocks of 4 digits in a nested manner, performing carries on the fly. Say we want to compute 12345×66778899 . With simplified names, we would do

```

\exp_after:wN \post_processing:w
\__int_value:w \__int_eval:w - 5 0000
\exp_after:wN \pack:NNNNNw
\__int_value:w \__int_eval:w 4 9995 0000
+ 12345 * 6677
\exp_after:wN \pack:NNNNNw
\__int_value:w \__int_eval:w 5 0000 0000
+ 12345 * 8899 ;

```

The `\exp_after:wN` triggers `__int_value:w __int_eval:w`, which starts a first computation, whose initial value is $-5\,0000$ (the “leading shift”). In that computation appears an `\exp_after:wN`, which triggers the nested computation `__int_value:w __int_eval:w` with starting value $4\,9995\,0000$ (the “middle shift”). That, in turn, expands `\exp_after:wN` which triggers the third computation. The third computation’s value is $5\,0000\,0000 + 12345 \times 8899$, which has 9 digits. Adding $5 \cdot 10^8$ to the product allowed us to know how many digits to expect as long as the numbers to multiply are not too big; it will also work to some extent with negative results. The `pack` function puts the last 4 of those 9 digits into a brace group, moves the semi-colon delimiter, and inserts a `+`, which combines the carry with the previous computation. The shifts nicely combine into $5\,0000\,0000/10^4 + 4\,9995\,0000 = 5\,0000\,0000$. As long as the operands are in some range, the result of this second computation will have 9 digits. The corresponding `pack` function, expanded after the result is computed, braces the last 4 digits, and leaves `+ <5 digits>` for the initial computation. The “leading shift” cancels the combination of the other shifts, and the `\post_processing:w` takes care of packing the last few digits.

Admittedly, this is quite intricate. It is probably the key in making `l3fp` as fast as other pure \TeX floating point units despite its increased precision. In fact, this is used so much that we provide different sets of packing functions and shifts, depending on ranges of input.

```

\__fp_pack:NNNNNw This set of shifts allows for computations involving results in the range  $[-4 \cdot 10^8, 5 \cdot 10^8 - 1]$ .
\c_fp_trailing_shift_int Shifted values all have exactly 9 digits.
\c_fp_middle_shift_int
\c_fp_leading_shift_int
10586 \int_const:Nn \c_fp_leading_shift_int { - 5 0000 }
10587 \int_const:Nn \c_fp_middle_shift_int { 5 0000 * 9999 }
10588 \int_const:Nn \c_fp_trailing_shift_int { 5 0000 * 10000 }
10589 \cs_new:Npn \__fp_pack:NNNNNw #1 #2#3#4#5 #6; { + #1#2#3#4#5 ; {#6} }

```

(End definition for `__fp_pack:NNNNNw` and others.)

```

\__fp_pack_big:NNNNNNw This set of shifts allows for computations involving results in the range  $[-5 \cdot 10^8, 6 \cdot 10^8 - 1]$ 
\c_fp_big_trailing_shift_int (actually a bit more). Shifted values all have exactly 10 digits. Note that the upper
\c_fp_big_middle_shift_int bound is due to  $\text{\TeX}$ ’s limit of  $2^{31} - 1$  on integers. The shifts are chosen to be roughly
\c_fp_big_leading_shift_int the mid-point of  $10^9$  and  $2^{31}$ , the two bounds on 10-digit integers in  $\text{\TeX}$ .
10590 \int_const:Nn \c_fp_big_leading_shift_int { - 15 2374 }
10591 \int_const:Nn \c_fp_big_middle_shift_int { 15 2374 * 9999 }
10592 \int_const:Nn \c_fp_big_trailing_shift_int { 15 2374 * 10000 }
10593 \cs_new:Npn \__fp_pack_big:NNNNNNw #1#2 #3#4#5#6 #7;
10594 { + #1#2#3#4#5#6 ; {#7} }

```

(End definition for `__fp_pack_big:NNNNNNw` and others.)

`__fp_pack_Bigg:NNNNNNw` This set of shifts allows for computations with results in the range $[-1 \cdot 10^9, 147483647]$; the end-point is $2^{31} - 1 - 2 \cdot 10^9 \simeq 1.47 \cdot 10^8$. Shifted values all have exactly 10 digits.

`\c__fp_Bigg_trailing_shift_int`

`\c__fp_Bigg_middle_shift_int`

`\c__fp_Bigg_leading_shift_int`

```

10595 \int_const:Nn \c__fp_Bigg_leading_shift_int { - 20 0000 }
10596 \int_const:Nn \c__fp_Bigg_middle_shift_int { 20 0000 * 9999 }
10597 \int_const:Nn \c__fp_Bigg_trailing_shift_int { 20 0000 * 10000 }
10598 \cs_new:Npn \__fp_pack_Bigg:NNNNNNw #1#2 #3#4#5#6 #7;
10599 { + #1#2#3#4#5#6 ; {#7} }

```

(End definition for `__fp_pack_Bigg:NNNNNNw` and others.)

`__fp_pack_twice_four:wNNNNNNNN` Grabs two sets of 4 digits and places them before the semi-colon delimiter. Putting several copies of this function before a semicolon will pack more digits since each will take the digits packed by the others in its first argument.

```

10600 \cs_new:Npn \__fp_pack_twice_four:wNNNNNNNN #1; #2#3#4#5 #6#7#8#9
10601 { #1 {#2#3#4#5} {#6#7#8#9} ; }

```

(End definition for `__fp_pack_twice_four:wNNNNNNNN`.)

`__fp_pack_eight:wNNNNNNNN` Grabs one set of 8 digits and places them before the semi-colon delimiter as a single group. Putting several copies of this function before a semicolon will pack more digits since each will take the digits packed by the others in its first argument.

```

10602 \cs_new:Npn \__fp_pack_eight:wNNNNNNNN #1; #2#3#4#5 #6#7#8#9
10603 { #1 {#2#3#4#5#6#7#8#9} ; }

```

(End definition for `__fp_pack_eight:wNNNNNNNN`.)

20.8 Decimate (dividing by a power of 10)

`__fp_decimate:nNnnnn` Each $\langle X_i \rangle$ consists in 4 digits exactly, and $1000 \leq \langle X_1 \rangle < 9999$. The first argument determines by how much we shift the digits. $\langle f_1 \rangle$ is called as follows: where $0 \leq \langle X'_i \rangle < 10^8 - 1$ are 8 digit numbers, forming the truncation of our number. In other words,

$$\left(\sum_{i=1}^4 \langle X_i \rangle \cdot 10^{-4i} \cdot 10^{-\langle shift \rangle} - \langle X'_1 \rangle \cdot 10^{-8} + \langle X'_2 \rangle \cdot 10^{-16} \right) \in [0, 10^{-16}).$$

To round properly later, we need to remember some information about the difference. The $\langle rounding \rangle$ digit is 0 if and only if the difference is exactly 0, and 5 if and only if the difference is exactly $0.5 \cdot 10^{-16}$. Otherwise, it is the (non-0, non-5) digit closest to 10^{17} times the difference. In particular, if the shift is 17 or more, all the digits are dropped, $\langle rounding \rangle$ is 1 (not 0), and $\langle X'_1 \rangle \langle X'_2 \rangle$ are both zero.

If the shift is 1, the $\langle rounding \rangle$ digit is simply the only digit that was pushed out of the brace groups (this is important for subtraction). It would be more natural for the $\langle rounding \rangle$ digit to be placed after the $\langle X_i \rangle$, but the choice we make involves less reshuffling.

Note that this function fails for negative $\langle shift \rangle$.

```

10604 \cs_new:Npn \__fp_decimate:nNnnnn #1
10605 {
10606   \cs:w
10607   __fp_decimate_
10608   \if_int_compare:w \__int_eval:w #1 > \c__fp_prec_int
10609     tiny
10610   \else:

```

```

10611         \__int_to_roman:w \__int_eval:w #1
10612         \fi:
10613         :Nnnnn
10614     \cs_end:
10615 }

```

Each of the auxiliaries see the function $\langle f_1 \rangle$, followed by 4 blocks of 4 digits.

(End definition for `__fp_decimate:nNnnnn`.)

```

\__fp_decimate_:Nnnnn
\__fp_decimate_tiny:Nnnnn
10616 \cs_new:Npn \__fp_decimate_:Nnnnn #1 #2#3#4#5
10617 { #1 0 {#2#3} {#4#5} ; }
10618 \cs_new:Npn \__fp_decimate_tiny:Nnnnn #1 #2#3#4#5
10619 { #1 1 { 0000 0000 } { 0000 0000 } 0 #2#3#4#5 ; }

```

(End definition for `__fp_decimate_:Nnnnn` and `__fp_decimate_tiny:Nnnnn`.)

```

\__fp_decimate_auxi:Nnnnn
\__fp_decimate_auxii:Nnnnn
\__fp_decimate_auxiii:Nnnnn
\__fp_decimate_auxiv:Nnnnn
\__fp_decimate_auxv:Nnnnn
\__fp_decimate_auxvi:Nnnnn
\__fp_decimate_auxvii:Nnnnn
\__fp_decimate_auxviii:Nnnnn
\__fp_decimate_auxix:Nnnnn
\__fp_decimate_auxx:Nnnnn
\__fp_decimate_auxxi:Nnnnn
\__fp_decimate_auxxii:Nnnnn
\__fp_decimate_auxxiii:Nnnnn
\__fp_decimate_auxxiv:Nnnnn
\__fp_decimate_auxxv:Nnnnn
\__fp_decimate_auxxvi:Nnnnn
10620 \cs_new:Npn \__fp_tmp:w #1 #2 #3
10621 {
10622     \cs_new:cpn { __fp_decimate_ #1 :Nnnnn } ##1 ##2##3##4##5
10623     {
10624         \exp_after:wN ##1
10625         \__int_value:w
10626         \exp_after:wN \__fp_round_digit:Nw #2 ;
10627         \__fp_decimate_pack:nnnnnnnnnw #3 ;
10628     }
10629 }
10630 \__fp_tmp:w {i} {\use_none:nnn #50}{ 0{#2}#3{#4}#5 }
10631 \__fp_tmp:w {ii} {\use_none:nn #5 }{ 00{#2}#3{#4}#5 }
10632 \__fp_tmp:w {iii} {\use_none:n #5 }{ 000{#2}#3{#4}#5 }
10633 \__fp_tmp:w {iv} { #5 }{ {0000}#2{#3}#4 #5 }
10634 \__fp_tmp:w {v} {\use_none:nnn #4#5 }{ 0{0000}#2{#3}#4 #5 }
10635 \__fp_tmp:w {vi} {\use_none:nn #4#5 }{ 00{0000}#2{#3}#4 #5 }
10636 \__fp_tmp:w {vii} {\use_none:n #4#5 }{ 000{0000}#2{#3}#4 #5 }
10637 \__fp_tmp:w {viii}{ #4#5 }{ {0000}0000{#2}#3 #4 #5 }
10638 \__fp_tmp:w {ix} {\use_none:nnn #3#4+#5}{ 0{0000}0000{#2}#3 #4 #5 }
10639 \__fp_tmp:w {x} {\use_none:nn #3#4+#5}{ 00{0000}0000{#2}#3 #4 #5 }
10640 \__fp_tmp:w {xi} {\use_none:n #3#4+#5}{ 000{0000}0000{#2}#3 #4 #5 }
10641 \__fp_tmp:w {xii} { #3#4+#5}{ {0000}0000{0000}#2 #3 #4 #5 }
10642 \__fp_tmp:w {xiii}{\use_none:nnn#2#3+#4#5}{ 0{0000}0000{0000}#2 #3 #4 #5 }
10643 \__fp_tmp:w {xiv} {\use_none:nn #2#3+#4#5}{ 00{0000}0000{0000}#2 #3 #4 #5 }
10644 \__fp_tmp:w {xv} {\use_none:n #2#3+#4#5}{ 000{0000}0000{0000}#2 #3 #4 #5 }
10645 \__fp_tmp:w {xvi} { #2#3+#4#5}{ {0000}0000{0000}0000 #2 #3 #4 #5 }

```

¹⁰No, the argument spec is not a mistake: the function calls an auxiliary to do half of the job.

(End definition for `_fp_decimate_auxi:Nnnnn` and others.)

`_fp_decimate_pack:nnnnnnnnnw`

The computation of the *rounding* digit leaves an unfinished `_int_value:w`, which expands the following functions. This allows us to repack nicely the digits we keep. Those digits come as an alternation of unbraced and braced blocks of 4 digits, such that the first 5 groups of token consist in 4 single digits, and one brace group (in some order), and the next 5 have the same structure. This is followed by some digits and a semicolon.

```
10646 \cs_new:Npn \_fp\_decimate\_pack:nnnnnnnnnw #1#2#3#4#5
10647 { \_fp\_decimate\_pack:nnnnnnnw { #1#2#3#4#5 } }
10648 \cs_new:Npn \_fp\_decimate\_pack:nnnnnnnw #1 #2#3#4#5#6
10649 { {#1} {#2#3#4#5#6} }
```

(End definition for `_fp_decimate_pack:nnnnnnnnnw`.)

20.9 Functions for use within primitive conditional branches

The functions described in this section are not pretty and can easily be misused. When correctly used, each of them removes one `\fi:` as part of its parameter text, and puts one back as part of its replacement text.

Many computation functions in `l3fp` must perform tests on the type of floating points that they receive. This is often done in an `\if_case:w` statement or another conditional statement, and only a few cases lead to actual computations: most of the special cases are treated using a few standard functions which we define now. A typical use context for those functions would be In this example, the case 0 will return the floating point *fp var*, expanding once after that floating point. Case 1 will do *some computation* using the *floating point* (presumably compute the operation requested by the user in that non-trivial case). Case 2 will return the *floating point* without modifying it, removing the *junk* and expanding once after. Case 3 will close the conditional, remove the *junk* and the *floating point*, and expand *something* next. In other cases, the “*junk*” is expanded, performing some other operation on the *floating point*. We provide similar functions with two trailing *floating points*.

`_fp_case_use:nw`

This function ends a `TeX` conditional, removes junk until the next floating point, and places its first argument before that floating point, to perform some operation on the floating point.

```
10650 \cs_new:Npn \_fp\_case\_use:nw #1#2 \fi: #3 \s\_fp { \fi: #1 \s\_fp }
```

(End definition for `_fp_case_use:nw`.)

`_fp_case_return:nw`

This function ends a `TeX` conditional, removes junk and a floating point, and places its first argument in the input stream. A quirk is that we don’t define this function requiring a floating point to follow, simply anything ending in a semicolon. This, in turn, means that the *junk* may not contain semicolons.

```
10651 \cs_new:Npn \_fp\_case\_return:nw #1#2 \fi: #3 ; { \fi: #1 }
```

(End definition for `_fp_case_return:nw`.)

`_fp_case_return_o:Nw`

This function ends a `TeX` conditional, removes junk and a floating point, and returns its first argument (an *fp var*) then expands once after it.

```
10652 \cs_new:Npn \_fp\_case\_return\_o:Nw #1#2 \fi: #3 \s\_fp #4 ;
10653 { \fi: \exp\_after:wN #1 }
```

(End definition for `_fp_case_return_o:Nw`.)

`__fp_case_return_same_o:w` This function ends a TeX conditional, removes junk, and returns the following floating point, expanding once after it.

```
10654 \cs_new:Npn \__fp_case_return_same_o:w #1 \fi: #2 \s__fp
10655 { \fi: \__fp_exp_after_o:w \s__fp }
```

(End definition for `__fp_case_return_same_o:w`.)

`__fp_case_return_o:Nww` Same as `__fp_case_return_o:Nw` but with two trailing floating points.

```
10656 \cs_new:Npn \__fp_case_return_o:Nww #1#2 \fi: #3 \s__fp #4 ; #5 ;
10657 { \fi: \exp_after:wN #1 }
```

(End definition for `__fp_case_return_o:Nww`.)

`__fp_case_return_i_o:ww` Similar to `__fp_case_return_same_o:w`, but this returns the first or second of two trailing floating point numbers, expanding once after the result.

```
10658 \cs_new:Npn \__fp_case_return_i_o:ww #1 \fi: #2 \s__fp #3 ; \s__fp #4 ;
10659 { \fi: \__fp_exp_after_o:w \s__fp #3 ; }
10660 \cs_new:Npn \__fp_case_return_ii_o:ww #1 \fi: #2 \s__fp #3 ;
10661 { \fi: \__fp_exp_after_o:w }
```

(End definition for `__fp_case_return_i_o:ww` and `__fp_case_return_ii_o:ww`.)

20.10 Integer floating points

`__fp_int_p:w` Tests if the floating point argument is an integer. This holds if the rounding digit resulting from `__fp_decimate:nNnnnn` is 0.

`__fp_int:wTF`

`__fp_int_normal:nnnnn`

`__fp_int_test:Nw`

```
10662 \prg_new_conditional:Npnn \__fp_int:w \s__fp \__fp_chk:w #1 #2 #3; { TF , T , F , p }
10663 {
10664   \if_case:w #1 \exp_stop_f:
10665     \prg_return_true:
10666   \or:   \__fp_int_normal:nnnnn #3
10667   \else: \prg_return_false:
10668   \fi:
10669 }
10670 \cs_new:Npn \__fp_int_normal:nnnnn #1 #2#3#4#5
10671 {
10672   \if_int_compare:w #1 > 0 \exp_stop_f:
10673     \__fp_decimate:nNnnnn { \c__fp_prec_int - #1 }
10674     \__fp_int_test:Nw
10675     {#2} {#3} {#4} {#5}
10676   \else:
10677     \prg_return_false:
10678   \fi:
10679 }
10680 \cs_new:Npn \__fp_int_test:Nw #1#2;
10681 {
10682   \if_meaning:w 0 #1
10683     \prg_return_true:
10684   \else:
10685     \prg_return_false:
10686   \fi:
10687 }
```

(End definition for `__fp_int:wTF`, `__fp_int_normal:nnnnn`, and `__fp_int_test:Nw`.)

20.11 Small integer floating points

`_fp_small_int:wTF` Tests if the floating point argument is an integer or $\pm\infty$. If so, it is converted to an integer in the range $[-10^8, 10^8]$ and fed as a braced argument to the *⟨true code⟩*. Otherwise, the *⟨false code⟩* is performed. First filter special cases: neither `nan` nor infinities are integers. `_fp_small_int_normal:NnwTF` Normal numbers with a non-positive exponent are never integers. When the exponent is greater than 8, the number is too large for the range. Otherwise, decimate, and test the digits after the decimal separator. The `\use_iii:nnn` remove a trailing `;` and the true branch, leaving only the false branch. The `_int_value:w` appearing in the case where the normal floating point is an integer takes care of expanding all the conditionals until the trailing `;`. That integer is fed to `_fp_small_int_true:wTF` which places it as a braced argument of the true branch. The `\use_i:nn` in `_fp_small_int_test:NnnwNTF` removes the top-level `\else:` coming from `_fp_small_int_normal:NnwTF`, hence will call the `\use_iii:nnn` which follows, taking the false branch.

```

10688 \cs_new:Npn \_fp_small_int:wTF \s_fp \_fp_chk:w #1#2
10689 {
10690   \if_case:w #1 \exp_stop_f:
10691     \_fp_case_return:nw { \_fp_small_int_true:wTF 0 ; }
10692   \or: \exp_after:wN \_fp_small_int_normal:NnwTF
10693   \or:
10694     \_fp_case_return:nw
10695     {
10696       \exp_after:wN \_fp_small_int_true:wTF \_int_value:w
10697       \if_meaning:w 2 #2 - \fi: 1 0000 0000 ;
10698     }
10699   \else: \_fp_case_return:nw \use_ii:nn
10700   \fi:
10701   #2
10702 }
10703 \cs_new:Npn \_fp_small_int_true:wTF #1; #2#3 { #2 {#1} }
10704 \cs_new:Npn \_fp_small_int_normal:NnwTF #1#2#3;
10705 {
10706   \if_int_compare:w #2 > 0 \exp_stop_f:
10707   \_fp_decimate:nNnnnn { \c_fp_prec_int - #2 }
10708   \_fp_small_int_test:NnnwNnw
10709   #3 #1 {#2}
10710   \else:
10711     \exp_after:wN \use_iii:nnn
10712   \fi:
10713   ;
10714 }
10715 \cs_new:Npn \_fp_small_int_test:NnnwNnw #1#2#3#4; #5#6
10716 {
10717   \if_meaning:w 0 #1
10718     \exp_after:wN \_fp_small_int_true:wTF
10719     \_int_value:w \if_meaning:w 2 #5 - \fi:
10720     \if_int_compare:w #6 > \c_fp_half_prec_int
10721     1 0000 0000
10722   \else:
10723     #3
10724   \fi:
10725   \else:
10726     \use_i:nn

```

```

10727     \fi:
10728 }

```

(End definition for `_fp_small_int:wTF` and others.)

20.12 Length of a floating point array

`_fp_array_count:n` Count the number of items in an array of floating points. The technique is very similar to `\tl_count:n`, but with the loop built-in. Checking for the end of the loop is done with the `\use_none:n #1` construction.

```

10729 \cs_new:Npn \_fp_array_count:n #1
10730 {
10731     \__int_value:w \__int_eval:w 0
10732     \_fp_array_count_loop:Nw #1 { ? \__prg_break: } ;
10733     \__prg_break_point:
10734     \__int_eval_end:
10735 }
10736 \cs_new:Npn \_fp_array_count_loop:Nw #1#2;
10737 { \use_none:n #1 + 1 \_fp_array_count_loop:Nw }

```

(End definition for `_fp_array_count:n` and `_fp_array_count_loop:Nw`.)

20.13 x-like expansion expandably

`_fp_expand:n` This expandable function behaves in a way somewhat similar to `\use:x`, but much less robust. The argument is f-expanded, then the leading item (often a single character token) is moved to a storage area after `\s__fp_mark`, and f-expansion is applied again, repeating until the argument is empty. The result built one piece at a time is then inserted in the input stream. Note that spaces are ignored by this procedure, unless surrounded with braces. Multiple tokens which do not need expansion can be inserted within braces.

```

10738 \cs_new:Npn \_fp_expand:n #1
10739 {
10740     \_fp_expand_loop:nwnN { }
10741     #1 \prg_do_nothing:
10742     \s__fp_mark { } \_fp_expand_loop:nwnN
10743     \s__fp_mark { } \_fp_use_i_until_s:nw ;
10744 }
10745 \cs_new:Npn \_fp_expand_loop:nwnN #1#2 \s__fp_mark #3 #4
10746 {
10747     \exp_after:wN #4 \exp:w \exp_end_continue_f:w
10748     #2
10749     \s__fp_mark { #3 #1 } #4
10750 }

```

(End definition for `_fp_expand:n` and `_fp_expand_loop:nwnN`.)

20.14 Messages

Using a floating point directly is an error.

```

10751 \_msg_kernel_new:nnnn { kernel } { misused-fp }
10752 { A~floating~point~with~value~'#1'~was~misused. }
10753 {

```

```

10754     To~obtain~the~value~of~a~floating~point~variable,~use~
10755     '\token_to_str:N \fp_to_decimal:N',~
10756     '\token_to_str:N \fp_to_scientific:N',~or~other~
10757     conversion~functions.
10758   }
10759 </initex | package>

```

21 l3fp-traps Implementation

```

10760 <*initex | package>
10761 <@@=fp>

```

Exceptions should be accessed by an `n`-type argument, among

- `invalid_operation`
- `division_by_zero`
- `overflow`
- `underflow`
- `inexact` (actually never used).

21.1 Flags

Flags to denote exceptions.

```

flag_fp_invalid_operation 10762 \flag_new:n { fp_invalid_operation }
flag_fp_division_by_zero 10763 \flag_new:n { fp_division_by_zero }
flag_fp_overflow          10764 \flag_new:n { fp_overflow }
flag_fp_underflow         10765 \flag_new:n { fp_underflow }

```

(End definition for flag `fp_invalid_operation` and others. These variables are documented on page 180.)

21.2 Traps

Exceptions can be trapped to obtain custom behaviour. When an invalid operation or a division by zero is trapped, the trap receives as arguments the result as an `N`-type floating point number, the function name (multiple letters for prefix operations, or a single symbol for infix operations), and the operand(s). When an overflow or underflow is trapped, the trap receives the resulting overly large or small floating point number if it is not too big, otherwise it receives $+\infty$. Currently, the `inexact` exception is entirely ignored.

The behaviour when an exception occurs is controlled by the definitions of the functions

- `__fp_invalid_operation:nnw,`
- `__fp_invalid_operation_o:Nww,`
- `__fp_invalid_operation_tl_o:ff,`
- `__fp_division_by_zero_o:Nnw,`
- `__fp_division_by_zero_o:NNww,`

- __fp_overflow:w,
- __fp_underflow:w.

Rather than changing them directly, we provide a user interface as \fp_trap:nn {\exception} {\way of trapping}, where the {\way of trapping} is one of error, flag, or none.

We also provide __fp_invalid_operation_o:nw, defined in terms of __fp_invalid_operation:nnw.

\fp_trap:nn

```

10766 \cs_new_protected:Npn \fp_trap:nn #1#2
10767 {
10768   \cs_if_exist_use:cF { __fp_trap_#1_set_#2: }
10769   {
10770     \clist_if_in:nnTF
10771     { invalid_operation , division_by_zero , overflow , underflow }
10772     {#1}
10773     {
10774       \__msg_kernel_error:nnxx { kernel }
10775       { unknown-fpu-trap-type } {#1} {#2}
10776     }
10777     {
10778       \__msg_kernel_error:nnx
10779       { kernel } { unknown-fpu-exception } {#1}
10780     }
10781   }
10782 }
```

(End definition for \fp_trap:nn. This function is documented on page 180.)

__fp_trap_invalid_operation_set_error:
 __fp_trap_invalid_operation_set_flag:
 __fp_trap_invalid_operation_set_none:
 __fp_trap_invalid_operation_set:N

We provide three types of trapping for invalid operations: either produce an error and raise the relevant flag; or only raise the flag; or don't even raise the flag. In most cases, the function produces as a result its first argument, possibly with post-expansion.

```

10783 \cs_new_protected:Npn \__fp_trap_invalid_operation_set_error:
10784 { \__fp_trap_invalid_operation_set:N \prg_do_nothing: }
10785 \cs_new_protected:Npn \__fp_trap_invalid_operation_set_flag:
10786 { \__fp_trap_invalid_operation_set:N \use_none:nnnnn }
10787 \cs_new_protected:Npn \__fp_trap_invalid_operation_set_none:
10788 { \__fp_trap_invalid_operation_set:N \use_none:nnnnnnnn }
10789 \cs_new_protected:Npn \__fp_trap_invalid_operation_set:N #1
10790 {
10791   \exp_args:Nno \use:n
10792   { \cs_set:Npn \__fp_invalid_operation:nnw ##1##2##3; }
10793   {
10794     #1
10795     \__fp_error:nnfn { invalid } {##2} { \fp_to_tl:n { ##3; } } { }
10796     \flag_raise:n { fp_invalid_operation }
10797     ##1
10798   }
10799   \exp_args:Nno \use:n
10800   { \cs_set:Npn \__fp_invalid_operation_o:Nww ##1##2; ##3; }
10801   {
10802     #1
```

```

10803         \_fp_error:nffn { invalid-ii }
10804         { \fp_to_tl:n { ##2; } } { \fp_to_tl:n { ##3; } } {##1}
10805         \flag_raise:n { fp_invalid_operation }
10806         \exp_after:wN \c_nan_fp
10807     }
10808     \exp_args:Nno \use:n
10809     { \cs_set:Npn \_fp_invalid_operation_tl_o:ff ##1##2 }
10810     {
10811         #1
10812         \_fp_error:nffn { invalid } {##1} {##2} { }
10813         \flag_raise:n { fp_invalid_operation }
10814         \exp_after:wN \c_nan_fp
10815     }
10816 }

```

(End definition for _fp_trap_invalid_operation_set_error: and others.)

_fp_trap_division_by_zero_set_error: We provide three types of trapping for invalid operations and division by zero: either
_fp_trap_division_by_zero_set_flag: produce an error and raise the relevant flag; or only raise the flag; or don't even raise the
_fp_trap_division_by_zero_set_none: flag. In all cases, the function must produce a result, namely its first argument, $\pm\infty$ or
_fp_trap_division_by_zero_set:N NaN.

```

10817 \cs_new_protected:Npn \_fp_trap_division_by_zero_set_error:
10818 { \_fp_trap_division_by_zero_set:N \prg_do_nothing: }
10819 \cs_new_protected:Npn \_fp_trap_division_by_zero_set_flag:
10820 { \_fp_trap_division_by_zero_set:N \use_none:nnnnn }
10821 \cs_new_protected:Npn \_fp_trap_division_by_zero_set_none:
10822 { \_fp_trap_division_by_zero_set:N \use_none:nnnnnnn }
10823 \cs_new_protected:Npn \_fp_trap_division_by_zero_set:N #1
10824 {
10825     \exp_args:Nno \use:n
10826     { \cs_set:Npn \_fp_division_by_zero_o:Nnw ##1##2##3; }
10827     {
10828         #1
10829         \_fp_error:nfn { zero-div } {##2} { \fp_to_tl:n { ##3; } } { }
10830         \flag_raise:n { fp_division_by_zero }
10831         \exp_after:wN ##1
10832     }
10833     \exp_args:Nno \use:n
10834     { \cs_set:Npn \_fp_division_by_zero_o:NNww ##1##2##3; ##4; }
10835     {
10836         #1
10837         \_fp_error:nffn { zero-div-ii }
10838         { \fp_to_tl:n { ##3; } } { \fp_to_tl:n { ##4; } } {##2}
10839         \flag_raise:n { fp_division_by_zero }
10840         \exp_after:wN ##1
10841     }
10842 }

```

(End definition for _fp_trap_division_by_zero_set_error: and others.)

_fp_trap_overflow_set_error: Just as for invalid operations and division by zero, the three different behaviours are
_fp_trap_overflow_set_flag: obtained by feeding \prg_do_nothing:, \use_none:nnnnn or \use_none:nnnnnnn to an
_fp_trap_overflow_set_none: auxiliary, with a further auxiliary common to overflow and underflow functions. In most
_fp_trap_overflow_set:N cases, the argument of the _fp_overflow:w and _fp_underflow:w functions will

```

\_fp_trap_underflow_set_error:
\_fp_trap_underflow_set_flag:
\_fp_trap_underflow_set_none:
\_fp_trap_underflow_set:N
\_fp_trap_overflow_set:NnNn

```

be an (almost) normal number (with an exponent outside the allowed range), and the error message thus displays that number together with the result to which it overflowed or underflowed. For extreme cases such as 10^{9999} , the exponent would be too large for T_EX, and `__fp_overflow:w` receives $\pm\infty$ (`__fp_underflow:w` would receive ± 0); then we cannot do better than simply say an overflow or underflow occurred.

```

10843 \cs_new_protected:Npn \__fp_trap_overflow_set_error:
10844 { \__fp_trap_overflow_set:N \prg_do_nothing: }
10845 \cs_new_protected:Npn \__fp_trap_overflow_set_flag:
10846 { \__fp_trap_overflow_set:N \use_none:n }
10847 \cs_new_protected:Npn \__fp_trap_overflow_set_none:
10848 { \__fp_trap_overflow_set:N \use_none:n }
10849 \cs_new_protected:Npn \__fp_trap_overflow_set:N #1
10850 { \__fp_trap_overflow_set:NnNn #1 { overflow } \__fp_inf_fp:N { inf } }
10851 \cs_new_protected:Npn \__fp_trap_underflow_set_error:
10852 { \__fp_trap_underflow_set:N \prg_do_nothing: }
10853 \cs_new_protected:Npn \__fp_trap_underflow_set_flag:
10854 { \__fp_trap_underflow_set:N \use_none:n }
10855 \cs_new_protected:Npn \__fp_trap_underflow_set_none:
10856 { \__fp_trap_underflow_set:N \use_none:n }
10857 \cs_new_protected:Npn \__fp_trap_underflow_set:N #1
10858 { \__fp_trap_overflow_set:NnNn #1 { underflow } \__fp_zero_fp:N { 0 } }
10859 \cs_new_protected:Npn \__fp_trap_overflow_set:NnNn #1#2#3#4
10860 {
10861   \exp_args:Nno \use:n
10862   { \cs_set:cpn { __fp_ #2 :w } \s__fp \__fp_chk:w ##1##2##3; }
10863   {
10864     #1
10865     \__fp_error:nffn
10866     { flow \if_meaning:w 1 ##1 -to \fi: }
10867     { \fp_to_tl:n { \s__fp \__fp_chk:w ##1##2##3; } }
10868     { \token_if_eq_meaning:NNF 0 ##2 { - } #4 }
10869     {#2}
10870     \flag_raise:n { fp_#2 }
10871     #3 ##2
10872   }
10873 }

```

(End definition for `__fp_trap_overflow_set_error:` and others.)

| | |
|--|---|
| <pre> __fp_invalid_operation:nnw __fp_invalid_operation_o:Nww __fp_invalid_operation_tl_o:ff __fp_division_by_zero_o:Nnw __fp_division_by_zero_o:NNww __fp_overflow:w __fp_underflow:w </pre> | <pre> 10874 \cs_new:Npn __fp_invalid_operation:nnw #1#2#3; { } 10875 \cs_new:Npn __fp_invalid_operation_o:Nww #1#2; #3; { } 10876 \cs_new:Npn __fp_invalid_operation_tl_o:ff #1 #2 { } 10877 \cs_new:Npn __fp_division_by_zero_o:Nnw #1#2#3; { } 10878 \cs_new:Npn __fp_division_by_zero_o:NNww #1#2#3; #4; { } 10879 \cs_new:Npn __fp_overflow:w { } 10880 \cs_new:Npn __fp_underflow:w { } 10881 \fp_trap:nn { invalid_operation } { error } 10882 \fp_trap:nn { division_by_zero } { flag } 10883 \fp_trap:nn { overflow } { flag } 10884 \fp_trap:nn { underflow } { flag } </pre> |
|--|---|

Initialize the control sequences (to log properly their existence). Then set invalid operations to trigger an error, and division by zero, overflow, and underflow to act silently on their flag.

(End definition for _fp_invalid_operation:nw and others.)

_fp_invalid_operation_o:nw Convenient short-hands for returning \c_nan_fp for a unary or binary operation, and
 _fp_invalid_operation_o:fw expanding after.

```
10885 \cs_new:Npn \_fp_invalid_operation_o:nw
10886   { \_fp_invalid_operation:nw { \exp_after:wN \c_nan_fp } }
10887 \cs_generate_variant:Nn \_fp_invalid_operation_o:nw { f }
```

(End definition for _fp_invalid_operation_o:nw.)

21.3 Errors

```
\_fp_error:nnnn
\_fp_error:nnfn 10888 \cs_new:Npn \_fp_error:nnnn #1
\_fp_error:nffn 10889   { \_msg_kernel_expandable_error:nnnn { kernel } { fp - #1 } }
10890 \cs_generate_variant:Nn \_fp_error:nnnn { nfn, nff }
```

(End definition for _fp_error:nnnn.)

21.4 Messages

Some messages.

```
10891 \_msg_kernel_new:nnnn { kernel } { unknown-fpu-exception }
10892   {
10893     The~FPU~exception~'#1'~is~not~known:~
10894     that~trap~will~never~be~triggered.
10895   }
10896   {
10897     The~only~exceptions~to~which~traps~can~be~attached~are \\
10898     \iow_indent:n
10899     {
10900       * ~ invalid_operation \\
10901       * ~ division_by_zero \\
10902       * ~ overflow \\
10903       * ~ underflow
10904     }
10905   }
10906 \_msg_kernel_new:nnnn { kernel } { unknown-fpu-trap-type }
10907   { The~FPU~trap~type~'#2'~is~not~known. }
10908   {
10909     The~trap~type~must~be~one~of \\
10910     \iow_indent:n
10911     {
10912       * ~ error \\
10913       * ~ flag \\
10914       * ~ none
10915     }
10916   }
10917 \_msg_kernel_new:nnn { kernel } { fp-flow }
10918   { An ~ #3 ~ occurred. }
10919 \_msg_kernel_new:nnn { kernel } { fp-flow-to }
10920   { #1 ~ #3 ed ~ to ~ #2 . }
10921 \_msg_kernel_new:nnn { kernel } { fp-zero-div }
10922   { Division~by~zero~in~ #1 (#2) }
```

```

10923 \__msg_kernel_new:nnn { kernel } { fp-zero-div-ii }
10924 { Division-by-zero-in~ (#1) #3 (#2) }
10925 \__msg_kernel_new:nnn { kernel } { fp-invalid }
10926 { Invalid-operation~ #1 (#2) }
10927 \__msg_kernel_new:nnn { kernel } { fp-invalid-ii }
10928 { Invalid-operation~ (#1) #3 (#2) }
10929 </initex | package>

```

22 l3fp-round implementation

```

10930 <*initex | package>
10931 <@@=fp>

```

22.1 Rounding tools

`\c__fp_five_int` This is used as the half-point for which numbers are rounded up/down.

```

10932 \int_const:Nn \c__fp_five_int { 5 }

```

(End definition for `\c__fp_five_int`.)

Floating point operations often yield a result that cannot be exactly represented in a significand with 16 digits. In that case, we need to round the exact result to a representable number. The IEEE standard defines four rounding modes:

- Round to nearest: round to the representable floating point number whose absolute difference with the exact result is the smallest. If the exact result lies exactly at the mid-point between two consecutive representable floating point numbers, round to the floating point number whose last digit is even.
- Round towards negative infinity: round to the greatest floating point number not larger than the exact result.
- Round towards zero: round to a floating point number with the same sign as the exact result, with the largest absolute value not larger than the absolute value of the exact result.
- Round towards positive infinity: round to the least floating point number not smaller than the exact result.

This is not fully implemented in l3fp yet, and transcendental functions fall back on the “round to nearest” mode. All rounding for basic algebra is done through the functions defined in this module, which can be redefined to change their rounding behaviour (but there is not interface for that yet).

The rounding tools available in this module are many variations on a base function `__fp_round:NNN`, which expands to `0\exp_stop_f:` or `1\exp_stop_f:` depending on whether the final result should be rounded up or down.

- `__fp_round:NNN <sign> <digit1> <digit2>` can expand to `0\exp_stop_f:` or `1\exp_stop_f:`.
- `__fp_round_s:NNNw <sign> <digit1> <digit2> <more digits>`; can expand to `0\exp_stop_f:;` or `1\exp_stop_f:;`.
- `__fp_round_neg:NNN <sign> <digit1> <digit2>` can expand to `0\exp_stop_f:` or `1\exp_stop_f:`.

See implementation comments for details on the syntax.

`__fp_round:NNN` If rounding the number $\langle final\ sign \rangle \langle digit_1 \rangle . \langle digit_2 \rangle$ to an integer rounds it towards zero (truncates it), this function expands to `0\exp_stop_f:`, and otherwise to `1\exp_stop_f:`.
`__fp_round_to_nearest:NNN` Typically used within the scope of an `__int_eval:w`, to add 1 if needed, and thereby round correctly. The result depends on the rounding mode.

`__fp_round_to_nearest_ninf:NNN` It is very important that $\langle final\ sign \rangle$ be the final sign of the result. Otherwise, the result will be incorrect in the case of rounding towards $-\infty$ or towards $+\infty$. Also recall that $\langle final\ sign \rangle$ is 0 for positive, and 2 for negative.
`__fp_round_to_nearest_zero:NNN`
`__fp_round_to_nearest_pinf:NNN`
`__fp_round_to_ninf:NNN`
`__fp_round_to_zero:NNN`
`__fp_round_to_pinf:NNN`

By default, the functions below return `0\exp_stop_f:`, but this is superseded by `__fp_round_return_one:`, which instead returns `1\exp_stop_f:`, expanding everything and removing `0\exp_stop_f:` in the process. In the case of rounding towards $\pm\infty$ or towards 0, this is not really useful, but it prepares us for the “round to nearest, ties to even” mode.

The “round to nearest” mode is the default. If the $\langle digit_2 \rangle$ is larger than 5, then round up. If it is less than 5, round down. If it is exactly 5, then round such that $\langle digit_1 \rangle$ plus the result is even. In other words, round up if $\langle digit_1 \rangle$ is odd.

The “round to nearest” mode has three variants, which differ in how ties are rounded: down towards $-\infty$, truncated towards 0, or up towards $+\infty$.

```

10933 \cs_new:Npn \__fp_round_return_one:
10934   { \exp_after:wN 1 \exp_after:wN \exp_stop_f: \exp:w }
10935 \cs_new:Npn \__fp_round_to_ninf:NNN #1 #2 #3
10936   {
10937     \if_meaning:w 2 #1
10938       \if_int_compare:w #3 > 0 \exp_stop_f:
10939         \__fp_round_return_one:
10940       \fi:
10941     \fi:
10942     0 \exp_stop_f:
10943   }
10944 \cs_new:Npn \__fp_round_to_zero:NNN #1 #2 #3 { 0 \exp_stop_f: }
10945 \cs_new:Npn \__fp_round_to_pinf:NNN #1 #2 #3
10946   {
10947     \if_meaning:w 0 #1
10948       \if_int_compare:w #3 > 0 \exp_stop_f:
10949         \__fp_round_return_one:
10950       \fi:
10951     \fi:
10952     0 \exp_stop_f:
10953   }
10954 \cs_new:Npn \__fp_round_to_nearest:NNN #1 #2 #3
10955   {
10956     \if_int_compare:w #3 > \c__fp_five_int
10957       \__fp_round_return_one:
10958     \else:
10959       \if_meaning:w 5 #3
10960         \if_int_odd:w #2 \exp_stop_f:
10961         \__fp_round_return_one:
10962       \fi:
10963     \fi:
10964     \fi:
10965     0 \exp_stop_f:

```

```

10966 }
10967 \cs_new:Npn \__fp_round_to_nearest_ninf:NNN #1 #2 #3
10968 {
10969   \if_int_compare:w #3 > \c__fp_five_int
10970     \__fp_round_return_one:
10971   \else:
10972     \if_meaning:w 5 #3
10973     \if_meaning:w 2 #1
10974     \__fp_round_return_one:
10975   \fi:
10976   \fi:
10977   \fi:
10978   0 \exp_stop_f:
10979 }
10980 \cs_new:Npn \__fp_round_to_nearest_zero:NNN #1 #2 #3
10981 {
10982   \if_int_compare:w #3 > \c__fp_five_int
10983     \__fp_round_return_one:
10984   \fi:
10985   0 \exp_stop_f:
10986 }
10987 \cs_new:Npn \__fp_round_to_nearest_pinf:NNN #1 #2 #3
10988 {
10989   \if_int_compare:w #3 > \c__fp_five_int
10990     \__fp_round_return_one:
10991   \else:
10992     \if_meaning:w 5 #3
10993     \if_meaning:w 0 #1
10994     \__fp_round_return_one:
10995   \fi:
10996   \fi:
10997   \fi:
10998   0 \exp_stop_f:
10999 }
11000 \cs_new_eq:NN \__fp_round:NNN \__fp_round_to_nearest:NNN

```

(End definition for __fp_round:NNN and others.)

__fp_round_s:NNNw Similar to __fp_round:NNN, but with an extra semicolon, this function expands to 0\exp_stop_f:; if rounding $\langle \text{final sign} \rangle \langle \text{digit} \rangle . \langle \text{more digits} \rangle$ to an integer truncates, and to 1\exp_stop_f:; otherwise. The $\langle \text{more digits} \rangle$ part must be a digit, followed by something that does not overflow a \int_use:N __int_eval:w construction. The only relevant information about this piece is whether it is zero or not.

```

11001 \cs_new:Npn \__fp_round_s:NNNw #1 #2 #3 #4;
11002 {
11003   \exp_after:wN \__fp_round:NNN
11004   \exp_after:wN #1
11005   \exp_after:wN #2
11006   \__int_value:w \__int_eval:w
11007   \if_int_odd:w 0 \if_meaning:w 0 #3 1 \fi:
11008   \if_meaning:w 5 #3 1 \fi:
11009   \exp_stop_f:
11010   \if_int_compare:w \__int_eval:w #4 > 0 \exp_stop_f:
11011   1 +

```

```

11012         \fi:
11013     \fi:
11014     #3
11015 ;
11016 }

```

(End definition for _fp_round_s:NNNw.)

_fp_round_digit:Nw This function should always be called within an _int_value:w or _int_eval:w expansion; it may add an extra _int_eval:w, which means that the integer or integer expression should not be ended with a synonym of \relax, but with a semi-colon for instance.

```

11017 \cs_new:Npn \_fp_round_digit:Nw #1 #2;
11018 {
11019     \if_int_odd:w \if_meaning:w 0 #1 1 \else:
11020         \if_meaning:w 5 #1 1 \else:
11021             0 \fi: \fi: \exp_stop_f:
11022     \if_int_compare:w \_int_eval:w #2 > 0 \exp_stop_f:
11023     \_int_eval:w 1 +
11024     \fi:
11025     \fi:
11026     #1
11027 }

```

(End definition for _fp_round_digit:Nw.)

_fp_round_neg:NNN This expands to 0\exp_stop_f: or 1\exp_stop_f: after doing the following test. Starting from a number of the form $\langle final\ sign \rangle 0.\langle 15\ digits \rangle \langle digit_1 \rangle$ with exactly 15 (non-all-zero) digits before $\langle digit_1 \rangle$, subtract from it $\langle final\ sign \rangle 0.0\dots 0 \langle digit_2 \rangle$, where there are 16 zeros. If in the current rounding mode the result should be rounded down, then this function returns 1\exp_stop_f:. Otherwise, *i.e.*, if the result is rounded back to the first operand, then this function returns 0\exp_stop_f:.

It turns out that this negative “round to nearest” is identical to the positive one. And this is the default mode.

```

11028 \cs_new_eq:NN \_fp_round_to_ninf_neg:NNN \_fp_round_to_pinf:NNN
11029 \cs_new:Npn \_fp_round_to_zero_neg:NNN #1 #2 #3
11030 {
11031     \if_int_compare:w #3 > 0 \exp_stop_f:
11032     \_fp_round_return_one:
11033     \fi:
11034     0 \exp_stop_f:
11035 }
11036 \cs_new_eq:NN \_fp_round_to_pinf_neg:NNN \_fp_round_to_ninf:NNN
11037 \cs_new_eq:NN \_fp_round_to_nearest_neg:NNN \_fp_round_to_nearest:NNN
11038 \cs_new_eq:NN \_fp_round_to_nearest_ninf_neg:NNN \_fp_round_to_nearest_pinf:NNN
11039 \cs_new:Npn \_fp_round_to_nearest_zero_neg:NNN #1 #2 #3
11040 {
11041     \if_int_compare:w #3 < \c__fp_five_int \else:
11042         \_fp_round_return_one:
11043         \fi:
11044     0 \exp_stop_f:
11045 }
11046 \cs_new_eq:NN \_fp_round_to_nearest_pinf_neg:NNN \_fp_round_to_nearest_ninf:NNN
11047 \cs_new_eq:NN \_fp_round_neg:NNN \_fp_round_to_nearest_neg:NNN

```

(End definition for `_fp_round_neg:NNN` and others.)

22.2 The round function

`_fp_round_o:Nw` The `trunc`, `ceil` and `floor` functions expect one or two arguments (the second is 0 by default), and the `round` function also accepts a third argument (`nan` by default), which will change #1 from `_fp_round_to_nearest:NNN` to one of its analogues.

```

11048 \cs_new:Npn \_fp_round_o:Nw #1#2 @
11049 {
11050   \if_case:w
11051     \_int_eval:w \_fp_array_count:n {#2} \_int_eval_end:
11052     \_fp_round_no_arg_o:Nw #1 \exp:w
11053   \or: \_fp_round:Nwn #1 #2 {0} \exp:w
11054   \or: \_fp_round:Nww #1 #2 \exp:w
11055   \else: \_fp_round:Nwww #1 #2 @ \exp:w
11056   \fi:
11057   \exp_end_continue_f:w
11058 }

```

(End definition for `_fp_round_o:Nw`.)

`_fp_round_no_arg_o:Nw`

```

11059 \cs_new:Npn \_fp_round_no_arg_o:Nw #1
11060 {
11061   \cs_if_eq:NNTF #1 \_fp_round_to_nearest:NNN
11062     { \_fp_error:nnnn { num-args } { round () } { 1 } { 3 } }
11063     {
11064       \_fp_error:nffn { num-args }
11065       { \_fp_round_name_from_cs:N #1 () } { 1 } { 2 }
11066     }
11067   \exp_after:wN \c_nan_fp
11068 }

```

(End definition for `_fp_round_no_arg_o:Nw`.)

`_fp_round:Nwww` Having three arguments is only allowed for `round`, not `trunc`, `ceil`, `floor`, so check for that case. If all is well, construct one of `_fp_round_to_nearest:NNN`, `_fp_round_to_nearest_zero:NNN`, `_fp_round_to_nearest_ninf:NNN`, `_fp_round_to_nearest_pinf:NNN` and act accordingly.

```

11069 \cs_new:Npn \_fp_round:Nwww #1#2 ; #3 ; \s_fp \_fp_chk:w #4#5#6 ; #7 @
11070 {
11071   \cs_if_eq:NNTF #1 \_fp_round_to_nearest:NNN
11072     {
11073       \tl_if_empty:nTF {#7}
11074       {
11075         \exp_args:Nc \_fp_round:Nww
11076         {
11077           \_fp_round_to_nearest
11078           \if_meaning:w 0 #4 _zero \else:
11079           \if_case:w #5 \exp_stop_f: _pinf \or: \else: _ninf \fi: \fi:
11080           :NNN
11081         }
11082         #2 ; #3 ;
11083       }

```

```

11084         {
11085             \__fp_error:nnnn { num-args } { round ( ) } { 1 } { 3 }
11086             \exp_after:wN \c_nan_fp
11087         }
11088     }
11089     {
11090         \__fp_error:nffn { num-args }
11091         { \__fp_round_name_from_cs:N #1 ( ) } { 1 } { 2 }
11092         \exp_after:wN \c_nan_fp
11093     }
11094 }

```

(End definition for __fp_round:Nwww.)

__fp_round_name_from_cs:N

```

11095 \cs_new:Npn \__fp_round_name_from_cs:N #1
11096 {
11097     \cs_if_eq:NNTF #1 \__fp_round_to_zero:NNN { trunc }
11098     {
11099         \cs_if_eq:NNTF #1 \__fp_round_to_ninf:NNN { floor }
11100         {
11101             \cs_if_eq:NNTF #1 \__fp_round_to_pinf:NNN { ceil }
11102             { round }
11103         }
11104     }
11105 }

```

(End definition for __fp_round_name_from_cs:N.)

__fp_round:Nww

__fp_round:Nwn

```

11106 \cs_new:Npn \__fp_round:Nww #1#2 ; #3 ;
11107 {
11108     \__fp_small_int:wTF #3; { \__fp_round:Nwn #1#2; }
11109     {
11110         \__fp_invalid_operation_tl_o:ff
11111         { \__fp_round_name_from_cs:N #1 }
11112         { \__fp_array_to_clist:n { #2; #3; } }
11113     }
11114 }
11115 \cs_new:Npn \__fp_round:Nwn #1 \s__fp \__fp_chk:w #2#3#4; #5
11116 {
11117     \if_meaning:w 1 #2
11118         \exp_after:wN \__fp_round_normal:NwNNnw
11119         \exp_after:wN #1
11120         \__int_value:w #5
11121     \else:
11122         \exp_after:wN \__fp_exp_after_o:w
11123     \fi:
11124     \s__fp \__fp_chk:w #2#3#4;
11125 }
11126 \cs_new:Npn \__fp_round_normal:NwNNnw #1#2 \s__fp \__fp_chk:w 1#3#4#5;
11127 {
11128     \__fp_decimate:nNnnnn { \c__fp_prec_int - #4 - #2 }
11129     \__fp_round_normal:NnnwNNnn #5 #1 #3 {#4} {#2}
11130 }

```

```

11131 \cs_new:Npn \__fp_round_normal:NnnwNnn #1#2#3#4; #5#6
11132 {
11133   \exp_after:wN \__fp_round_normal:NNwNnn
11134   \__int_value:w \__int_eval:w
11135   \if_int_compare:w #2 > 0 \exp_stop_f:
11136     1 \__int_value:w #2
11137     \exp_after:wN \__fp_round_pack:Nw
11138     \__int_value:w \__int_eval:w 1#3 +
11139   \else:
11140     \if_int_compare:w #3 > 0 \exp_stop_f:
11141       1 \__int_value:w #3 +
11142     \fi:
11143   \fi:
11144   \exp_after:wN #5
11145   \exp_after:wN #6
11146   \use_none:nnnnnn #3
11147   #1
11148   \__int_eval_end:
11149   0000 0000 0000 0000 ; #6
11150 }
11151 \cs_new:Npn \__fp_round_pack:Nw #1
11152 { \if_meaning:w 2 #1 + 1 \fi: \__int_eval_end: }
11153 \cs_new:Npn \__fp_round_normal:NNwNnn #1 #2
11154 {
11155   \if_meaning:w 0 #2
11156     \exp_after:wN \__fp_round_special:NwwNnn
11157     \exp_after:wN #1
11158   \fi:
11159   \__fp_pack_twice_four:wNNNNNNNN
11160   \__fp_pack_twice_four:wNNNNNNNN
11161   \__fp_round_normal_end:wwNnn
11162   ; #2
11163 }
11164 \cs_new:Npn \__fp_round_normal_end:wwNnn #1;#2;#3#4#5
11165 {
11166   \exp_after:wN \__fp_exp_after_o:w \exp:w \exp_end_continue_f:w
11167   \__fp_sanitise:Nw #3 #4 ; #1 ;
11168 }
11169 \cs_new:Npn \__fp_round_special:NwwNnn #1#2;#3;#4#5#6
11170 {
11171   \if_meaning:w 0 #1
11172     \__fp_case_return:nw
11173     { \exp_after:wN \__fp_zero_fp:N \exp_after:wN #4 }
11174   \else:
11175     \exp_after:wN \__fp_round_special_aux:Nw
11176     \exp_after:wN #4
11177     \__int_value:w \__int_eval:w 1
11178     \if_meaning:w 1 #1 -#6 \else: +#5 \fi:
11179   \fi:
11180   ;
11181 }
11182 \cs_new:Npn \__fp_round_special_aux:Nw #1#2;
11183 {
11184   \exp_after:wN \__fp_exp_after_o:w \exp:w \exp_end_continue_f:w

```



```

11185     \_fp_sanitize:Nw #1#2; {1000}{0000}{0000}{0000};
11186   }

```

(End definition for `_fp_round:Nww` and others.)

```

11187 \</initex | package>

```

23 l3fp-parse implementation

```

11188 \*initex | package>

```

```

11189 \@@=fp>

```

23.1 Work plan

The task at hand is non-trivial, and some previous failed attempts show that the code leads to unreadable logs, so we had better get it (almost) right the first time. Let us first describe our goal, then discuss the design precisely before writing any code.

`_fp_parse:n` Evaluates the *floating point expression* and leaves the result in the input stream as an internal floating point number. This function forms the basis of almost all public `l3fp` functions. During evaluation, each token is fully `f`-expanded.

`_fp_parse_o:n` does the same but expands once after its result.

T_EXhackers note: Registers (integers, toks, etc.) are automatically unpacked, without requiring a function such as `\int_use:N`. Invalid tokens remaining after `f`-expansion will lead to unrecoverable low-level T_EX errors.

(End definition for `_fp_parse:n`.)

Floating point expressions are composed of numbers, given in various forms, infix operators, such as `+`, `**`, or `,` (which joins two numbers into a list), and prefix operators, such as the unary `-`, functions, or opening parentheses. Here is a list of precedences which control the order of evaluation (some distinctions are irrelevant for the order of evaluation, but serve as signals), from the tightest binding to the loosest binding.

16 Function calls with multiple arguments.

15 Function calls expecting exactly one argument.

13/14 Binary `**` and `^` (right to left).

12 Unary `+`, `-`, `!` (right to left).

10 Binary `*`, `/`, and juxtaposition (implicit `*`).

9 Binary `+` and `-`.

7 Comparisons.

6 Logical **and**, denoted by `&&`.

5 Logical **or**, denoted by `||`.

4 Ternary operator `?:`, piece `?`.

3 Ternary operator `?:`, piece `:`.

2 Commas, and parentheses accepting commas.

1 Parentheses expecting exactly one argument.

0 Start and end of the expression.

```
\c__fp_prec_funcii_int
\c__fp_prec_func_int      11190 \int_const:Nn \c__fp_prec_funcii_int { 16 }
\c__fp_prec_hatii_int     11191 \int_const:Nn \c__fp_prec_func_int { 15 }
\c__fp_prec_hat_int       11192 \int_const:Nn \c__fp_prec_hatii_int { 14 }
\c__fp_prec_not_int       11193 \int_const:Nn \c__fp_prec_hat_int { 13 }
\c__fp_prec_times_int     11194 \int_const:Nn \c__fp_prec_not_int { 12 }
\c__fp_prec_plus_int      11195 \int_const:Nn \c__fp_prec_times_int { 10 }
\c__fp_prec_comp_int      11196 \int_const:Nn \c__fp_prec_plus_int { 9 }
\c__fp_prec_and_int       11197 \int_const:Nn \c__fp_prec_comp_int { 7 }
\c__fp_prec_or_int        11198 \int_const:Nn \c__fp_prec_and_int { 6 }
\c__fp_prec_quest_int     11199 \int_const:Nn \c__fp_prec_or_int { 5 }
\c__fp_prec_colon_int     11200 \int_const:Nn \c__fp_prec_quest_int { 4 }
\c__fp_prec_comma_int     11201 \int_const:Nn \c__fp_prec_colon_int { 3 }
\c__fp_prec_paren_int     11202 \int_const:Nn \c__fp_prec_comma_int { 2 }
\c__fp_prec_end_int       11203 \int_const:Nn \c__fp_prec_paren_int { 1 }
                          11204 \int_const:Nn \c__fp_prec_end_int { 0 }
```

(End definition for `\c__fp_prec_funcii_int` and others.)

23.1.1 Storing results

The main question in parsing expressions expandably is to decide where to put the intermediate results computed for various subexpressions.

One option is to store the values at the start of the expression, and carry them together as the first argument of each macro. However, we want to `f-expand` tokens one by one in the expression (as `\int_eval:n` does), and with this approach, expanding the next unread token forces us to jump with `\exp_after:wN` over every value computed earlier in the expression. With this approach, the run-time will grow at least quadratically in the length of the expression, if not as its cube (inserting the `\exp_after:wN` is tricky and slow).

A second option is to place those values at the end of the expression. Then expanding the next unread token is straightforward, but this still hits a performance issue: for long expressions we would be reaching all the way to the end of the expression at every step of the calculation. The run-time is again quadratic.

A variation of the above attempts to place the intermediate results which appear when computing a parenthesized expression near the closing parenthesis. This still lets us expand tokens as we go, and avoids performance problems as long as there are enough parentheses. However, it would be much better to avoid requiring the closing parenthesis to be present as soon as the corresponding opening parenthesis is read: the closing parenthesis may still be hidden in a macro yet to be expanded.

Hence, we need to go for some fine expansion control: the result is stored *before* the start!

Let us illustrate this idea in a simple model: adding positive integers which may be resulting from the expansion of macros, or may be values of registers. Assume that one number, say, 12345, has already been found, and that we want to parse the next number. The current status of the code may look as follows.

```

\exp_after:wN \add:ww \__int_value:w 12345 \exp_after:wN ;
\exp:w \operand:w <stuff>

```

One step of expansion expands `\exp_after:wN`, which triggers the primitive `__int_value:w`, which reads the five digits we have already found, 12345. This integer is unfinished, causing the second `\exp_after:wN` to expand, and to trigger the construction `\exp:w`, which expands `\operand:w`, defined to read what follows and make a number out of it, then leave `\exp_end:`, the number, and a semicolon in the input stream. Once `\operand:w` is done expanding, we obtain essentially

```

\exp_after:wN \add:ww \__int_value:w 12345 ;
\exp:w \exp_end: 333444 ;

```

where in fact `\exp_after:wN` has already been expanded, `__int_value:w` has already seen 12345, and `\exp:w` is still looking for a number. It finds `\exp_end:`, hence expands to nothing. Now, `__int_value:w` sees the `;`, which cannot be part of a number. The expansion stops, and we are left with

```

\add:ww 12345 ; 333444 ;

```

which can safely perform the addition by grabbing two arguments delimited by `;`.

If we were to continue parsing the expression, then the following number should also be cleaned up before the next use of a binary operation such as `\add:ww`. Just like `__int_value:w 12345 \exp_after:wN ;` expanded what follows once, we need `\add:ww` to do the calculation, and in the process to expand the following once. This is also true in our real application: all the functions of the form `__fp..._o:ww` expand what follows once. This comes at the cost of leaving tokens in the input stack, and we will need to be careful not to waste this memory. All of our discussion above is nice but simplistic, as operations should not simply be performed in the order they appear.

23.1.2 Precedence and infix operators

The various operators we will encounter have different precedences, which influence the order of calculations: $1 + 2 \times 3 = 1 + (2 \times 3)$ because \times has a higher precedence than $+$. The true analog of our macro `\operand:w` must thus take care of that. When looking for an operand, it needs to perform calculations until reaching an operator which has lower precedence than the one which called `\operand:w`. This means that `\operand:w` must know what the previous binary operator is, or rather, its precedence: we thus rename it `\operand:Nw`. Let us describe as an example how the calculation $41 - 2^3 * 4 + 5$ will be done. Here, we abuse notations: the first argument of `\operand:Nw` should be an integer constant (`\c__fp_prec_plus_int`, ...) equal to the precedence of the given operator, not directly the operator itself.

- Clean up 41 and find $-$. We call `\operand:Nw -` to find the second operand.
- Clean up 2 and find $^$.
- Compare the precedences of $-$ and $^$. Since the latter is higher, we need to compute the exponentiation. For this, find the second operand with a nested call to `\operand:Nw ^`.
- Clean up 3 and find $*$.

- Compare the precedences of \wedge and $*$. Since the former is higher, `\operand:Nw` \wedge has found the second operand of the exponentiation, which is computed: $2^3 = 8$.
- We now have $41+8*4+5$, and `\operand:Nw -` is still looking for a second operand for the subtraction. Is it 8?
- Compare the precedences of $-$ and $*$. Since the latter is higher, we are not done with 8. Call `\operand:Nw *` to find the second operand of the multiplication.
- Clean up 4, and find $-$.
- Compare the precedences of $*$ and $-$. Since the former is higher, `\operand:Nw *` has found the second operand of the multiplication, which is computed: $8*4 = 32$.
- We now have $41+32+5$, and `\operand:Nw -` is still looking for a second operand for the subtraction. Is it 32?
- Compare the precedences of $-$ and $+$. Since they are equal, `\operand:Nw -` has found the second operand for the subtraction, which is computed: $41 - 32 = 9$.
- We now have $9+5$.

The procedure above stops short of performing all computations, but adding a surrounding call to `\operand:Nw` with a very low precedence ensures that all computations will be performed before `\operand:Nw` is done. Adding a trailing marker with the same very low precedence prevents the surrounding `\operand:Nw` from going beyond the marker.

The pattern above to find an operand for a given operator, is to find one number and the next operator, then compare precedences to know if the next computation should be done. If it should, then perform it after finding its second operand, and look at the next operator, then compare precedences to know if the next computation should be done. This continues until we find that the next computation should not be done. Then, we stop.

We are now ready to get a bit more technical and describe which of the `l3fp-parse` functions correspond to each step above.

First, `__fp_parse_operand:Nw` is the `\operand:Nw` function above, with small modifications due to expansion issues discussed later. We denote by $\langle precedence \rangle$ the argument of `__fp_parse_operand:Nw`, that is, the precedence of the binary operator whose operand we are trying to find. The basic action is to read numbers from the input stream. This is done by `__fp_parse_one:Nw`. A first approximation of this function is that it reads one $\langle number \rangle$, performing no computation, and finds the following binary $\langle operator \rangle$. Then it expands to

$$\langle number \rangle \\ __\text{fp_parse_infix_}\langle operator \rangle:N \langle precedence \rangle$$

expanding the `infix` auxiliary before leaving the above in the input stream.

We now explain the `infix` auxiliaries. We need some flexibility in how we treat the case of equal precedences: most often, the first operation encountered should be performed, such as $1-2-3$ being computed as $(1-2)-3$, but 2^3^4 should be evaluated as $2^{(3^4)}$ instead. For this reason, and to support the equivalence between $**$ and \wedge more easily, each binary operator is converted to a control sequence `__fp_parse_infix_\langle operator \rangle:N` when it is encountered for the first time. Instead of passing both precedences to a test function to do the comparison steps above, we pass the

$\langle precedence \rangle$ (of the earlier operator) to the `infix` auxiliary for the following $\langle operator \rangle$, to know whether to perform the computation of the $\langle operator \rangle$. If it should not be performed, the `infix` auxiliary expands to

```
@ \use_none:n \__fp_parse_infix_<operator>:N
```

and otherwise it calls `__fp_parse_operand:Nw` with the precedence of the $\langle operator \rangle$ to find its second operand $\langle number_2 \rangle$ and the next $\langle operator_2 \rangle$, and expands to

```
@ \__fp_parse_apply_binary:NwNwN
<operator> <number_2>
@ \__fp_parse_infix_<operator_2>:N
```

The `infix` function is responsible for comparing precedences, but cannot directly call the computation functions, because the first operand $\langle number \rangle$ is before the `infix` function in the input stream. This is why we stop the expansion here and give control to another function to close the loop.

A definition of `__fp_parse_operand:Nw` $\langle precedence \rangle$ with some of the expansion control removed is

```
\exp_after:wN \__fp_parse_continue:NwN
\exp_after:wN <precedence>
\exp:w \exp_end_continue_f:w
\__fp_parse_one:Nw <precedence>
```

This expands `__fp_parse_one:Nw` $\langle precedence \rangle$ completely, which finds a number, wraps the next $\langle operator \rangle$ into an `infix` function, feeds this function the $\langle precedence \rangle$, and expands it, yielding either

```
\__fp_parse_continue:NwN <precedence>
<number> @
\use_none:n \__fp_parse_infix_<operator>:N
```

or

```
\__fp_parse_continue:NwN <precedence>
<number> @
\__fp_parse_apply_binary:NwNwN
<operator> <number_2>
@ \__fp_parse_infix_<operator_2>:N
```

The definition of `__fp_parse_continue:NwN` is then very simple:

```
\cs_new:Npn \__fp_parse_continue:NwN #1#2@#3 { #3 #1 #2 @ }
```

In the first case, `#3` is `\use_none:n`, yielding

```
\use_none:n <precedence> <number> @
\__fp_parse_infix_<operator>:N
```

then $\langle number \rangle$ `@ __fp_parse_infix_<operator>:N`. In the second case, `#3` is `__fp_parse_apply_binary:NwNwN`, whose role is to compute $\langle number \rangle$ $\langle operator \rangle$ $\langle number_2 \rangle$ and to prepare for the next comparison of precedences: first we get

```

    \__fp_parse_apply_binary:NwNwN
    <precedence> <number> @
    <operator> <number2>
    @ \__fp_parse_infix_<operator2>:N

```

then

```

    \exp_after:wN \__fp_parse_continue:NwN
    \exp_after:wN <precedence>
    \exp:w \exp_end_continue_f:w
    \__fp_<operator>_o:ww <number> <number2>
    \exp:w \exp_end_continue_f:w
    \__fp_parse_infix_<operator2>:N <precedence>

```

where `__fp_<operator>_o:ww` computes `<number> <operator> <number2>` and expands after the result, thus triggers the comparison of the precedence of the `<operator2>` and the `<precedence>`, continuing the loop.

We have introduced the most important functions here, and the next few paragraphs will describe various subtleties.

23.1.3 Prefix operators, parentheses, and functions

Prefix operators (unary `-`, `+`, `!`) and parentheses are taken care of by the same mechanism, and functions (`sin`, `exp`, etc.) as well. Finding the argument of the unary `-`, for instance, is very similar to grabbing the second operand of a binary infix operator, with a subtle precedence explained below. Once that operand is found, the operator can be applied to it (for the unary `-`, this simply flips the sign). A left parenthesis is just a prefix operator with a very low precedence equal to that of the closing parenthesis (which is treated as an infix operator, since it normally appears just after numbers), so that all computations are performed until the closing parenthesis. The prefix operator associated to the left parenthesis does not alter its argument, but it removes the closing parenthesis (with some checks).

Prefix operators are the reason why we only summarily described the function `__fp_parse_one:Nw` earlier. This function is responsible for reading in the input stream the first possible `<number>` and the next infix `<operator>`. If what follows `__fp_parse_one:Nw <precedence>` is a prefix operator, then we must find the operand of this prefix operator through a nested call to `__fp_parse_operand:Nw` with the appropriate precedence, then apply the operator to the operand found to yield the result of `__fp_parse_one:Nw`. So far, all is simple.

The unary operators `+`, `-`, `!` complicate things a little bit: `-3**2` should be $-(3^2) = -9$, and not $(-3)^2 = 9$. This would easily be done by giving `-` a lower precedence, equal to that of the infix `+` and `-`. Unfortunately, this fails in cases such as `3**-2*4`, yielding $3^{-2 \times 4}$ instead of the correct $3^{-2} \times 4$. A second attempt would be to call `__fp_parse_operand:Nw` with the `<precedence>` of the previous operator, but `0>-2+3` is then parsed as `0>-(2+3)`: the addition is performed because it binds more tightly than the comparison which precedes `-`. The correct approach is for a unary `-` to perform operations whose precedence is greater than both that of the previous operation, and that of the unary `-` itself. The unary `-` is given a precedence higher than multiplication and division. This does not lead to any surprising result, since $-(x/y) = (-x)/y$ and similarly for multiplication, and it reduces the number of nested calls to `__fp_parse_operand:Nw`.

Functions are implemented as prefix operators with very high precedence, so that their argument is the first number that can possibly be built.

Note that contrarily to the `infix` functions discussed earlier, the `prefix` functions do perform tests on the previous *precedence* to decide whether to find an argument or not, since we know that we need a number, and must never stop there.

23.1.4 Numbers and reading tokens one by one

So far, we have glossed over one important point: what is a “number”? A number is typically given in the form $\langle\textit{significand}\rangle\textit{e}\langle\textit{exponent}\rangle$, where the $\langle\textit{significand}\rangle$ is any non-empty string composed of decimal digits and at most one decimal separator (a period), the exponent “ $\textit{e}\langle\textit{exponent}\rangle$ ” is optional and is composed of an exponent mark `e` followed by a possibly empty string of signs `+` or `-` and a non-empty string of decimal digits. The $\langle\textit{significand}\rangle$ can also be an integer, dimension, skip, or muskip variable, in which case dimensions are converted from points (or mu units) to floating points, and the $\langle\textit{exponent}\rangle$ can also be an integer variable. Numbers can also be given as floating point variables, or as named constants such as `nan`, `inf` or `pi`. We may add more types in the future.

When `_fp_parse_one:Nw` is looking for a “number”, here is what happens.

- If the next token is a control sequence with the meaning of `\scan_stop:`, it can be: `\s__fp`, in which case our job is done, as what follows is an internal floating point number, or `\s__fp_mark`, in which case the expression has come to an early end, as we are still looking for a number here, or something else, in which case we consider the control sequence to be a bad variable resulting from `c`-expansion.
- If the next token is a control sequence with a different meaning, we assume that it is a register, unpack it with `\tex_the:D`, and use its value (in `pt` for dimensions and skips, `mu` for muskips) as the $\langle\textit{significand}\rangle$ of a number: we look for an exponent.
- If the next token is a digit, we remove any leading zeros, then read a significand larger than 1 if the next character is a digit, read a significand smaller than 1 if the next character is a period, or we have found a significand equal to 0 otherwise, and look for an exponent.
- If the next token is a letter, we collect more letters until the first non-letter: the resulting word may denote a function such as `asin`, a constant such as `pi` or be unknown. In the first case, we call `_fp_parse_operand:Nw` to find the argument of the function, then apply the function, before declaring that we are done. Otherwise, we are done, either with the value of the constant, or with the value `nan` for unknown words.
- If the next token is anything else, we check whether it is a known prefix operator, in which case `_fp_parse_operand:Nw` finds its operand. If it is not known, then either a number is missing (if the token is a known infix operator) or the token is simply invalid in floating point expressions.

Once a number is found, `_fp_parse_one:Nw` also finds an infix operator. This goes as follows.

- If the next token is a control sequence, it could be the special marker `\s__fp_mark`, and otherwise it is a case of juxtaposing numbers, such as `2\c_zero`, with an implied multiplication.

- If the next token is a letter, it is also a case of juxtaposition, as letters cannot be proper infix operators.
- Otherwise (including in the case of digits), if the token is a known infix operator, the appropriate `_fp_infix_⟨operator⟩:N` function is built, and if it does not exist, we complain. In particular, the juxtaposition `\c_zero 2` is disallowed.

In the above, we need to test whether a character token #1 is a digit:

```
\if_int_compare:w 9 < 1 \token_to_str:N #1 \exp_stop_f:
  is a digit
\else:
  not a digit
\fi:
```

To exclude 0, replace 9 by 10. The use of `\token_to_str:N` ensures that a digit with any catcode is detected. To test if a character token is a letter, we need to work with its character code, testing if ‘#1 lies in [65,90] (uppercase letters) or [97,112] (lowercase letters)

```
\if_int_compare:w \_int_eval:w
  ( ‘#1 \if_int_compare:w ‘#1 > ‘Z - 32 \fi: ) / 26 = 3 \exp_stop_f:
  is a letter
\else:
  not a letter
\fi:
```

At all steps, we try to accept all category codes: when #1 is kept to be used later, it is almost always converted to category code other through `\token_to_str:N`. More precisely, catcodes {3,6,7,8,11,12} should work without trouble, but {1,2,4,10,13} will not work, and of course {0,5,9} cannot become tokens.

Floating point expressions should behave as much as possible like ε -TeX-based integer expressions and dimension expressions. In particular, **f**-expansion should be performed as the expression is read, token by token, forcing the expansion of protected macros, and ignoring spaces. One advantage of expanding at every step is that restricted expandable functions can then be used in floating point expressions just as they can be in other kinds of expressions. Problematically, spaces stop **f**-expansion: for instance, the macro `\X` below will not be expanded if we simply perform **f**-expansion.

```
\DeclareDocumentCommand {\test} {m} { \fp_eval:n {#1} }
\ExplSyntaxOff
\test { 1 + \X }
```

Of course, spaces will not appear in a code setting, but may very easily come in document-level input, from which some expressions may come. To avoid this problem, at every step, we do essentially what `\use:f` would do: take an argument, put it back in the input stream, then **f**-expand it. This is not a complete solution, since a macro’s expansion could contain leading spaces which will stop the **f**-expansion before further macro calls are performed. However, in practice it should be enough: in particular, floating point numbers will correctly be expanded to the underlying `\s__fp ...` structure. The **f**-expansion is performed by `_fp_parse_expand:w`.

23.2 Main auxiliary functions

`_fp_parse_operand:Nw` Reads the "...", performing every computation with a precedence higher than $\langle precedence \rangle$, then expands to where the $\langle operation \rangle$ is the first operation with a lower precedence, possibly `end`, and the "..." start just after the $\langle operation \rangle$.

(End definition for `_fp_parse_operand:Nw`.)

`_fp_parse_infix_+:N` If `+` has a precedence higher than the $\langle precedence \rangle$, cleans up a second $\langle operand \rangle$ and finds the $\langle operation_2 \rangle$ which follows, and expands to Otherwise expands to A similar function exists for each infix operator.

(End definition for `_fp_parse_infix_+:N`.)

`_fp_parse_one:Nw` Cleans up one or two operands depending on how the precedence of the next operation compares to the $\langle precedence \rangle$. If the following $\langle operation \rangle$ has a precedence higher than $\langle precedence \rangle$, expands to and otherwise expands to

(End definition for `_fp_parse_one:Nw`.)

23.3 Helpers

`_fp_parse_expand:w` This function must always come within a `\exp:w` expansion. The $\langle tokens \rangle$ should be the part of the expression that we have not yet read. This requires in particular closing all conditionals properly before expanding.

```
11205 \cs_new:Npn \_fp_parse_expand:w #1 { \exp_end_continue_f:w #1 }
```

(End definition for `_fp_parse_expand:w`.)

`_fp_parse_return_semicolon:w` This very odd function swaps its position with the following `\fi:` and removes `_fp_parse_expand:w` normally responsible for expansion. That turns out to be useful.

```
11206 \cs_new:Npn \_fp_parse_return_semicolon:w
11207     #1 \fi: \_fp_parse_expand:w { \fi: ; #1 }
```

(End definition for `_fp_parse_return_semicolon:w`.)

`_fp_type_from_scan:N` Grabs the pieces of the stringified $\langle token \rangle$ which lies after the first `s_fp`. If the $\langle token \rangle$ does not contain that string, the result is `_?`.

`_fp_type_from_scan:w`

```
11208 \cs_new:Npx \_fp_type_from_scan:N #1
11209     {
11210         \exp_not:N \exp_after:wN \exp_not:N \_fp_type_from_scan:w
11211         \exp_not:N \token_to_str:N #1 \exp_not:N \q_mark
11212         \tl_to_str:n { s\_fp _? } \exp_not:N \q_mark \exp_not:N \q_stop
11213     }
11214 \use:x
11215     {
11216         \cs_new:Npn \exp_not:N \_fp_type_from_scan:w
11217             ##1 \tl_to_str:n { s\_fp } ##2 \exp_not:N \q_mark ##3 \exp_not:N \q_stop
11218             {##2}
11219     }
```

(End definition for `_fp_type_from_scan:N` and `_fp_type_from_scan:w`.)

`__fp_parse_digits_vii:N` These functions must be called within an `__int_value:w` or `__int_eval:w` construction. The first token which follows must be `f`-expanded prior to calling those functions.
`__fp_parse_digits_vi:N` The functions read tokens one by one, and output digits into the input stream, until
`__fp_parse_digits_v:N` meeting a non-digit, or up to a number of digits equal to their index. The full expansion
`__fp_parse_digits_iv:N` is
`__fp_parse_digits_iii:N`
`__fp_parse_digits_ii:N` $\langle \text{digits} \rangle ; \langle \text{filling } 0 \rangle ; \langle \text{length} \rangle$
`__fp_parse_digits_i:N`
`__fp_parse_digits_:N`

where $\langle \text{filling } 0 \rangle$ is a string of zeros such that $\langle \text{digits} \rangle \langle \text{filling } 0 \rangle$ has the length given by the index of the function, and $\langle \text{length} \rangle$ is the number of zeros in the $\langle \text{filling } 0 \rangle$ string. Each function puts a digit into the input stream and calls the next function, until we find a non-digit. We are careful to pass the tested tokens through `\token_to_str:N` to normalize their category code.

```

11220 \cs_set_protected:Npn \__fp_tmp:w #1 #2 #3
11221 {
11222   \cs_new:cpn { __fp_parse_digits_ #1 :N } ##1
11223   {
11224     \if_int_compare:w 9 < 1 \token_to_str:N ##1 \exp_stop_f:
11225     \token_to_str:N ##1 \exp_after:wN #2 \exp:w
11226     \else:
11227       \__fp_parse_return_semicolon:w #3 ##1
11228     \fi:
11229     \__fp_parse_expand:w
11230   }
11231 }
11232 \__fp_tmp:w {vii} \__fp_parse_digits_vi:N { 0000000 ; 7 }
11233 \__fp_tmp:w {vi} \__fp_parse_digits_v:N { 000000 ; 6 }
11234 \__fp_tmp:w {v} \__fp_parse_digits_iv:N { 00000 ; 5 }
11235 \__fp_tmp:w {iv} \__fp_parse_digits_iii:N { 0000 ; 4 }
11236 \__fp_tmp:w {iii} \__fp_parse_digits_ii:N { 000 ; 3 }
11237 \__fp_tmp:w {ii} \__fp_parse_digits_i:N { 00 ; 2 }
11238 \__fp_tmp:w {i} \__fp_parse_digits_:N { 0 ; 1 }
11239 \cs_new:Npn \__fp_parse_digits_:N { ; ; 0 }

```

(End definition for `__fp_parse_digits_vii:N` and others.)

23.4 Parsing one number

`__fp_parse_one:Nw` This function finds one number, and packs the symbol which follows in an `\..._infix...` csname. `#1` is the previous $\langle \text{precedence} \rangle$, and `#2` the first token of the operand. We distinguish four cases: `#2` is equal to `\scan_stop:` in meaning, `#2` is a different control sequence, `#2` is a digit, and `#2` is something else (this last case will be split further). Despite the earlier `f`-expansion, `#2` may still be expandable if it was protected by `\exp_not:N`, as may happen with the $\text{\LaTeX 2}_{\epsilon}$ command `\protect`. Using a well placed `\reverse_if:N`, this case is sent to `__fp_parse_one_fp:NN` which deals with it robustly.

```

11240 \cs_new:Npn \__fp_parse_one:Nw #1 #2
11241 {
11242   \if_catcode:w \scan_stop: \exp_not:N #2
11243   \exp_after:wN \if_meaning:w \exp_not:N #2 #2 \else:
11244   \exp_after:wN \reverse_if:N
11245   \fi:
11246   \if_meaning:w \scan_stop: #2
11247   \exp_after:wN \exp_after:wN

```

```

11248     \exp_after:wN \_fp_parse_one_fp:NN
11249   \else:
11250     \exp_after:wN \exp_after:wN
11251     \exp_after:wN \_fp_parse_one_register:NN
11252   \fi:
11253 \else:
11254   \if_int_compare:w 9 < 1 \token_to_str:N #2 \exp_stop_f:
11255     \exp_after:wN \exp_after:wN
11256     \exp_after:wN \_fp_parse_one_digit:NN
11257   \else:
11258     \exp_after:wN \exp_after:wN
11259     \exp_after:wN \_fp_parse_one_other:NN
11260   \fi:
11261 \fi:
11262 #1 #2
11263 }

```

(End definition for _fp_parse_one:Nw.)

```

\_fp_parse_one_fp:NN
\_fp_exp_after_mark_f:nw
\_fp_exp_after_?_f:nw

```

This function receives a $\langle precedence \rangle$ and a control sequence equal to `\scan_stop:` in meaning. There are three cases, dispatched using `_fp_type_from_scan:N`.

- `\s_fp` starts a floating point number, and we call `_fp_exp_after_f:nw`, which f-expands after the floating point.
- `\s_fp_mark` is a premature end, we call `_fp_exp_after_mark_f:nw`, which triggers an fp-early-end error.
- For a control sequence not containing `\s_fp`, we call `_fp_exp_after_?_f:nw`, causing a bad-variable error.

This scheme is extensible: additional types can be added by starting the variables with a scan mark of the form `\s_fp_⟨type⟩` and defining `_fp_exp_after_⟨type⟩_f:nw`. In all cases, we make sure that the second argument of `_fp_parse_infix:NN` is correctly expanded. A special case only enabled in L^AT_EX 2_ε is that if `\protect` is encountered then the error message mentions the control sequence which follows it rather than `\protect` itself. The test for L^AT_EX 2_ε uses `\@unexpandable@protect` rather than `\protect` because `\protect` is often `\scan_stop:` hence “does not exist”.

```

11264 \cs_new:Npn \_fp_parse_one_fp:NN #1#2
11265 {
11266   \cs:w \_fp_exp_after \_fp_type_from_scan:N #2 _f:nw \cs_end:
11267   {
11268     \exp_after:wN \_fp_parse_infix:NN
11269     \exp_after:wN #1 \exp:w \_fp_parse_expand:w
11270   }
11271   #2
11272 }
11273 \cs_new:Npn \_fp_exp_after_mark_f:nw #1
11274 {
11275   \_msg_kernel_expandable_error:nn { kernel } { fp-early-end }
11276   \exp_after:wN \c_nan_fp \exp:w \exp_end_continue_f:w #1
11277 }
11278 \cs_new:cpn { \_fp_exp_after_?_f:nw } #1#2
11279 {

```

```

11280 \_msg_kernel_expandable_error:nnn { kernel } { bad-variable } {#2}
11281 \exp_after:wN \c_nan_fp \exp:w \exp_end_continue_f:w #1
11282 }
11283 \*package)
11284 \group_begin:
11285 \char_set_catcode_letter:N \@
11286 \cs_if_exist:NT \@unexpandable@protect
11287 {
11288 \cs_gset:cpn { __fp_exp_after_?_f:nw } #1#2
11289 {
11290 \exp_after:wN \c_nan_fp \exp:w \exp_end_continue_f:w #1
11291 \str_if_eq:nnTF {#2} { \protect }
11292 {
11293 \cs_if_eq:nnTF #2 \@unexpandable@protect { \use_i:nn } { \use:n }
11294 { \_msg_kernel_expandable_error:nnn { kernel } { fp-robust-cmd } }
11295 }
11296 { \_msg_kernel_expandable_error:nnn { kernel } { bad-variable } {#2} }
11297 }
11298 }
11299 \group_end:
11300 \*package)

```

(End definition for `_fp_parse_one_fp:NN`, `_fp_exp_after_mark_f:nw`, and `_fp_exp_after_?_f:nw`.)

`_fp_parse_one_register:NN` This is called whenever #2 is a control sequence other than `\scan_stop:` in meaning. We
`_fp_parse_one_register_aux:Nw` special-case `\wd`, `\ht`, `\dp` (see later) and otherwise assume that it is a register, but care-
`_fp_parse_one_register_auxii:wwwNw` fully unpack it with `\tex_the:D` within braces. First, we find the exponent following #2.
`_fp_parse_one_register_int:www` Then we unpack #2 with `\tex_the:D`, and the `auxii` auxiliary distinguishes integer reg-
`_fp_parse_one_register_mu:www` isters from dimensions/skips from muskips, according to the presence of a period and/or
`_fp_parse_one_register_dim:ww` of pt. For integers, simply convert $\langle value \rangle e \langle exponent \rangle$ to a floating point number with
`_fp_parse_one_register_wd:w` `_fp_parse:n` (this is somewhat wasteful). For other registers, the decimal rounding
`_fp_parse_one_register_wd:Nw` provided by T_EX does not accurately represent the binary value that it manipulates, so
we extract this binary value as a number of scaled points with `_int_value:w _dim_eval:w` $\langle decimal value \rangle$ pt, and use an auxiliary of `\dim_to_fp:n`, which performs
the multiplication by 2^{-16} , correctly rounded.

```

11301 \cs_new:Npn \_fp_parse_one_register:NN #1#2
11302 {
11303 \exp_after:wN \_fp_parse_infix_after_operand:NwN
11304 \exp_after:wN #1
11305 \exp:w \exp_end_continue_f:w
11306 \if_meaning:w \box_wd:N #2 \_fp_parse_one_register_wd:w \fi:
11307 \if_meaning:w \box_ht:N #2 \_fp_parse_one_register_wd:w \fi:
11308 \if_meaning:w \box_dp:N #2 \_fp_parse_one_register_wd:w \fi:
11309 \exp_after:wN \_fp_parse_one_register_aux:Nw
11310 \exp_after:wN #2
11311 \_int_value:w
11312 \exp_after:wN \_fp_parse_exponent:N
11313 \exp:w \_fp_parse_expand:w
11314 }
11315 \cs_new:Npx \_fp_parse_one_register_aux:Nw #1
11316 {
11317 \exp_not:n
11318 {

```

```

11319         \exp_after:wN \use:nn
11320         \exp_after:wN \__fp_parse_one_register_auxii:wwwNw
11321     }
11322     \exp_not:N \exp_after:wN { \exp_not:N \tex_the:D #1 }
11323     ; \exp_not:N \__fp_parse_one_register_dim:ww
11324     \tl_to_str:n { pt } ; \exp_not:N \__fp_parse_one_register_mu:www
11325     . \tl_to_str:n { pt } ; \exp_not:N \__fp_parse_one_register_int:www
11326     \exp_not:N \q_stop
11327 }
11328 \use:x
11329 {
11330     \cs_new:Npn \exp_not:N \__fp_parse_one_register_auxii:wwwNw
11331         ##1 . ##2 \tl_to_str:n { pt } ##3 ; ##4##5 \exp_not:N \q_stop
11332         { ##4 ##1.##2; }
11333     \cs_new:Npn \exp_not:N \__fp_parse_one_register_mu:www
11334         ##1 \tl_to_str:n { mu } ; ##2 ;
11335         { \exp_not:N \__fp_parse_one_register_dim:ww ##1 ; }
11336 }
11337 \cs_new:Npn \__fp_parse_one_register_int:www #1; #2.; #3;
11338 { \__fp_parse:n { #1 e #3 } }
11339 \cs_new:Npn \__fp_parse_one_register_dim:ww #1; #2;
11340 {
11341     \exp_after:wN \__fp_from_dim_test:ww
11342     \__int_value:w #2 \exp_after:wN ,
11343     \__int_value:w \__dim_eval:w #1 pt ;
11344 }

```

The `\wd`, `\dp`, `\ht` primitives expect an integer argument. We abuse the exponent parser to find the integer argument: simply include the exponent marker `e`. Once that “exponent” is found, use `\tex_the:D` to find the box dimension and then copy what we did for dimensions.

```

11345 \cs_new:Npn \__fp_parse_one_register_wd:w
11346     #1#2 \exp_after:wN #3#4 \__fp_parse_expand:w
11347     {
11348         #1
11349         \exp_after:wN \__fp_parse_one_register_wd:Nw
11350         #4 \__fp_parse_expand:w e
11351     }
11352 \cs_new:Npn \__fp_parse_one_register_wd:Nw #1#2 ;
11353 {
11354     \exp_after:wN \__fp_from_dim_test:ww
11355     \exp_after:wN 0 \exp_after:wN ,
11356     \__int_value:w \__dim_eval:w
11357     \exp_after:wN \use:n \exp_after:wN { \tex_the:D #1 #2 } ;
11358 }

```

(End definition for `__fp_parse_one_register:NN` and others.)

`__fp_parse_one_digit:NN` A digit marks the beginning of an explicit floating point number. Once the number is found, we will catch the case of overflow and underflow with `__fp_sanitize:wN`, then `__fp_parse_infix_after_operand:NwN` expands `__fp_parse_infix:NN` after the number we find, to wrap the following infix operator as required. Finding the number itself begins by removing leading zeros: further steps are described later.

```

11359 \cs_new:Npn \__fp_parse_one_digit:NN #1

```

```

11360 {
11361     \exp_after:wN \__fp_parse_infix_after_operand:NwN
11362     \exp_after:wN #1
11363     \exp:w \exp_end_continue_f:w
11364     \exp_after:wN \__fp_sanitizewN
11365     \__int_value:w \__int_eval:w 0 \__fp_parse_trim_zeros:N
11366 }

```

(End definition for __fp_parse_one_digit:NN.)

__fp_parse_one_other:NN For this function, #2 is a character token which is not a digit. If it is a letter, __fp_parse_letters:N beyond this one and give the result to __fp_parse_word:Nw. Otherwise, the character is assumed to be a prefix operator, and we build __fp_parse_prefix_{operator}:Nw.

```

11367 \cs_new:Npn \__fp_parse_one_other:NN #1 #2
11368 {
11369     \if_int_compare:w
11370         \__int_eval:w
11371         ( '#2 \if_int_compare:w '#2 > 'Z - 32 \fi: ) / 26
11372         = 3 \exp_stop_f:
11373         \exp_after:wN \__fp_parse_word:Nw
11374         \exp_after:wN #1
11375         \exp_after:wN #2
11376         \exp:w \exp_after:wN \__fp_parse_letters:N
11377         \exp:w
11378     \else:
11379         \exp_after:wN \__fp_parse_prefix:NNN
11380         \exp_after:wN #1
11381         \exp_after:wN #2
11382         \cs:w
11383         __fp_parse_prefix_ \token_to_str:N #2 :Nw
11384         \exp_after:wN
11385         \cs_end:
11386         \exp:w
11387     \fi:
11388     \__fp_parse_expand:w
11389 }

```

(End definition for __fp_parse_one_other:NN.)

__fp_parse_word:Nw Finding letters is a simple recursion. Once __fp_parse_letters:N has done its job, __fp_parse_letters:N we try to build a control sequence from the word #2. If it is a known word, then the corresponding action is taken, and otherwise, we complain about an unknown word, yield \c_nan_fp, and look for the following infix operator. Note that the unknown word could be a mistyped function as well as a mistyped constant, so there is no way to tell whether to look for arguments; we do not.

```

11390 \cs_new:Npn \__fp_parse_word:Nw #1#2;
11391 {
11392     \cs_if_exist_use:cF { __fp_parse_word_#2:N }
11393     {
11394         \_msg_kernel_expandable_error:nnn
11395         { kernel } { unknown-fp-word } {#2}
11396         \exp_after:wN \c_nan_fp \exp:w \exp_end_continue_f:w
11397         \__fp_parse_infix:NN

```

```

11398     }
11399     #1
11400 }
11401 \cs_new:Npn \__fp_parse_letters:N #1
11402 {
11403     \exp_end_continue_f:w
11404     \if_int_compare:w
11405         \if_catcode:w \scan_stop: \exp_not:N #1
11406         0
11407     \else:
11408         \__int_eval:w
11409         ( '#1 \if_int_compare:w '#1 > 'Z - 32 \fi: ) / 26
11410     \fi:
11411     = 3 \exp_stop_f:
11412     \exp_after:wN #1
11413     \exp:w \exp_after:wN \__fp_parse_letters:N
11414     \exp:w
11415 \else:
11416     \__fp_parse_return_semicolon:w #1
11417 \fi:
11418 \__fp_parse_expand:w
11419 }

```

(End definition for __fp_parse_word:Nw and __fp_parse_letters:N.)

__fp_parse_prefix:NNN
 __fp_parse_prefix_unknown:NNN

For this function, #1 is the previous *<precedence>*, #2 is the operator just seen, and #3 is a control sequence which implements the operator if it is a known operator. If this control sequence is \scan_stop:, then the operator is in fact unknown. Either the expression is missing a number there (if the operator is valid as an infix operator), and we put `nan`, wrapping the infix operator in a csname as appropriate, or the character is simply invalid in floating point expressions, and we continue looking for a number, starting again from __fp_parse_one:Nw.

```

11420 \cs_new:Npn \__fp_parse_prefix:NNN #1#2#3
11421 {
11422     \if_meaning:w \scan_stop: #3
11423     \exp_after:wN \__fp_parse_prefix_unknown:NNN
11424     \exp_after:wN #2
11425     \fi:
11426     #3 #1
11427 }
11428 \cs_new:Npn \__fp_parse_prefix_unknown:NNN #1#2#3
11429 {
11430     \cs_if_exist:cTF { __fp_parse_infix_ \token_to_str:N #1 :N }
11431     {
11432         \_msg_kernel_expandable_error:nnn
11433         { kernel } { fp-missing-number } {#1}
11434         \exp_after:wN \c_nan_fp \exp:w \exp_end_continue_f:w
11435         \__fp_parse_infix:NN #3 #1
11436     }
11437     {
11438         \_msg_kernel_expandable_error:nnn
11439         { kernel } { fp-unknown-symbol } {#1}
11440         \__fp_parse_one:Nw #3
11441     }

```

```
11442 }
```

(End definition for `_fp_parse_prefix:NNN` and `_fp_parse_prefix_unknown:NNN`.)

23.4.1 Numbers: trimming leading zeros

Numbers will be parsed as follows: first we trim leading zeros, then if the next character is a digit, start reading a significand ≥ 1 with the set of functions `_fp_parse_large...`; if it is a period, the significand is < 1 ; and otherwise it is zero. In the second case, trim additional zeros after the period, counting them for an exponent shift $\langle exp_1 \rangle < 0$, then read the significand with the set of functions `_fp_parse_small...`. Once the significand is read, read the exponent if `e` is present.

```
\_fp_parse_trim_zeros:N
\_fp_parse_trim_end:w
```

This function expects an already expanded token. It removes any leading zero, then distinguishes three cases: if the first non-zero token is a digit, then call `_fp_parse_large:N` (the significand is ≥ 1); if it is `.`, then continue trimming zeros with `_fp_parse_strim_zeros:N`; otherwise, our number is exactly zero, and we call `_fp_parse_zero:` to take care of that case.

```
11443 \cs_new:Npn \_fp_parse_trim_zeros:N #1
11444 {
11445   \if:w 0 \exp_not:N #1
11446     \exp_after:wN \_fp_parse_trim_zeros:N
11447     \exp:w
11448   \else:
11449     \if:w . \exp_not:N #1
11450       \exp_after:wN \_fp_parse_strim_zeros:N
11451       \exp:w
11452     \else:
11453       \_fp_parse_trim_end:w #1
11454     \fi:
11455   \fi:
11456   \_fp_parse_expand:w
11457 }
11458 \cs_new:Npn \_fp_parse_trim_end:w #1 \fi: \fi: \_fp_parse_expand:w
11459 {
11460   \fi:
11461   \fi:
11462   \if_int_compare:w 9 < 1 \token_to_str:N #1 \exp_stop_f:
11463     \exp_after:wN \_fp_parse_large:N
11464   \else:
11465     \exp_after:wN \_fp_parse_zero:
11466   \fi:
11467   #1
11468 }
```

(End definition for `_fp_parse_trim_zeros:N` and `_fp_parse_trim_end:w`.)

```
\_fp_parse_strim_zeros:N
\_fp_parse_strim_end:w
```

If we have removed all digits until a period (or if the body started with a period), then enter the “`small_trim`” loop which outputs `-1` for each removed `0`. Those `-1` are added to an integer expression waiting for the exponent. If the first non-zero token is a digit, call `_fp_parse_small:N` (our significand is smaller than 1), and otherwise, the number is an exact zero. The name `strim` stands for “small trim”.

```
11469 \cs_new:Npn \_fp_parse_strim_zeros:N #1
```



```

11470 {
11471     \if:w 0 \exp_not:N #1
11472     - 1
11473     \exp_after:wN \__fp_parse_strim_zeros:N \exp:w
11474 \else:
11475     \__fp_parse_strim_end:w #1
11476 \fi:
11477 \__fp_parse_expand:w
11478 }
11479 \cs_new:Npn \__fp_parse_strim_end:w #1 \fi: \__fp_parse_expand:w
11480 {
11481     \fi:
11482     \if_int_compare:w 9 < 1 \token_to_str:N #1 \exp_stop_f:
11483     \exp_after:wN \__fp_parse_small:N
11484 \else:
11485     \exp_after:wN \__fp_parse_zero:
11486 \fi:
11487 #1
11488 }

```

(End definition for __fp_parse_strim_zeros:N and __fp_parse_strim_end:w.)

__fp_parse_zero: After reading a significand of 0, we need to remove any exponent, then put a sign of 1 for __fp_sanitize:wN, small hack to denote an exact zero (rather than an underflow).

```

11489 \cs_new:Npn \__fp_parse_zero:
11490 {
11491     \exp_after:wN ; \exp_after:wN 1
11492     \__int_value:w \__fp_parse_exponent:N
11493 }

```

(End definition for __fp_parse_zero:.)

23.4.2 Number: small significand

__fp_parse_small:N This function is called after we have passed the decimal separator and removed all leading zeros from the significand. It is followed by a non-zero digit (with any catcode). The goal is to read up to 16 digits. But we can't do that all at once, because __int_value:w (which allows us to collect digits and continue expanding) can only go up to 9 digits. Hence we grab digits in two steps of 8 digits. Since #1 is a digit, read seven more digits using __fp_parse_digits_vii:N. The `small_leading` auxiliary will leave those digits in the __int_value:w, and grab some more, or stop if there are no more digits. Then the `pack_leading` auxiliary puts the various parts in the appropriate order for the processing further up.

```

11494 \cs_new:Npn \__fp_parse_small:N #1
11495 {
11496     \exp_after:wN \__fp_parse_pack_leading:NNNNNww
11497     \__int_value:w \__int_eval:w 1 \token_to_str:N #1
11498     \exp_after:wN \__fp_parse_small_leading:wwNN
11499     \__int_value:w 1
11500     \exp_after:wN \__fp_parse_digits_vii:N
11501     \exp:w \__fp_parse_expand:w
11502 }

```

(End definition for __fp_parse_small:N.)

_fp_parse_small_leading:wwNN

We leave *<digits>* *<zeros>* in the input stream: the functions used to grab digits are such that this constitutes digits 1 through 8 of the significand. Then prepare to pack 8 more digits, with an exponent shift of zero (this shift is used in the case of a large significand). If #4 is a digit, leave it behind for the packing function, and read 6 more digits to reach a total of 15 digits: further digits are involved in the rounding. Otherwise put 8 zeros in to complete the significand, then look for an exponent.

```
11503 \cs_new:Npn \_fp_parse_small_leading:wwNN 1 #1 ; #2; #3 #4
11504 {
11505     #1 #2
11506     \exp_after:wN \_fp_parse_pack_trailing:NNNNNNww
11507     \exp_after:wN 0
11508     \_int_value:w \_int_eval:w 1
11509     \if_int_compare:w 9 < 1 \token_to_str:N #4 \exp_stop_f:
11510         \token_to_str:N #4
11511         \exp_after:wN \_fp_parse_small_trailing:wwNN
11512         \_int_value:w 1
11513         \exp_after:wN \_fp_parse_digits_vi:N
11514         \exp:w
11515     \else:
11516         0000 0000 \_fp_parse_exponent:Nw #4
11517     \fi:
11518     \_fp_parse_expand:w
11519 }
```

(End definition for _fp_parse_small_leading:wwNN.)

_fp_parse_small_trailing:wwNN

Leave digits 10 to 15 (arguments #1 and #2) in the input stream. If the *<next token>* is a digit, it is the 16th digit, we keep it, then the `small_round` auxiliary considers this digit and all further digits to perform the rounding: the function expands to nothing, to +0 or to +1. Otherwise, there is no 16-th digit, so we put a 0, and look for an exponent.

```
11520 \cs_new:Npn \_fp_parse_small_trailing:wwNN 1 #1 ; #2; #3 #4
11521 {
11522     #1 #2
11523     \if_int_compare:w 9 < 1 \token_to_str:N #4 \exp_stop_f:
11524         \token_to_str:N #4
11525         \exp_after:wN \_fp_parse_small_round:NN
11526         \exp_after:wN #4
11527         \exp:w
11528     \else:
11529         0 \_fp_parse_exponent:Nw #4
11530     \fi:
11531     \_fp_parse_expand:w
11532 }
```

(End definition for _fp_parse_small_trailing:wwNN.)

_fp_parse_pack_trailing:NNNNNNww

_fp_parse_pack_leading:NNNNNNww

_fp_parse_pack_carry:w

Those functions are expanded after all the digits are found, we took care of the rounding, as well as the exponent. The last argument is the exponent. The previous five arguments are 8 digits which we pack in groups of 4, and the argument before that is 1, except in the rare case where rounding lead to a carry, in which case the argument is 2. The `trailing` function has an exponent shift as its first argument, which we add to the exponent found in the `e...` syntax. If the trailing digits cause a carry, the integer expression for the leading digits is incremented (+1 in the code below). If the leading digits propagate this

carry all the way up, the function `__fp_parse_pack_carry:w` increments the exponent, and changes the significand from 0000... to 1000...: this is simple because such a carry can only occur to give rise to a power of 10.

```

11533 \cs_new:Npn \__fp_parse_pack_trailing:NNNNNww #1 #2 #3#4#5#6 #7; #8 ;
11534 {
11535     \if_meaning:w 2 #2 + 1 \fi:
11536     ; #8 + #1 ; {#3#4#5#6} {#7};
11537 }
11538 \cs_new:Npn \__fp_parse_pack_leading:NNNNNww #1 #2#3#4#5 #6; #7;
11539 {
11540     + #7
11541     \if_meaning:w 2 #1 \__fp_parse_pack_carry:w \fi:
11542     ; 0 {#2#3#4#5} {#6}
11543 }
11544 \cs_new:Npn \__fp_parse_pack_carry:w \fi: ; 0 #1
11545 { \fi: + 1 ; 0 {1000} }

```

(End definition for `__fp_parse_pack_trailing:NNNNNww`, `__fp_parse_pack_leading:NNNNNww`, and `__fp_parse_pack_carry:w`.)

23.4.3 Number: large significand

Parsing a significand larger than 1 is a little bit more difficult than parsing small significands. We need to count the number of digits before the decimal separator, and add that to the final exponent. We also need to test for the presence of a dot each time we run out of digits, and branch to the appropriate `parse_small` function in those cases.

`__fp_parse_large:N` This function is followed by the first non-zero digit of a “large” significand (≥ 1). It is called within an integer expression for the exponent. Grab up to 7 more digits, for a total of 8 digits.

```

11546 \cs_new:Npn \__fp_parse_large:N #1
11547 {
11548     \exp_after:wN \__fp_parse_large_leading:wwNN
11549     \__int_value:w 1 \token_to_str:N #1
11550     \exp_after:wN \__fp_parse_digits_vii:N
11551     \exp:w \__fp_parse_expand:w
11552 }

```

(End definition for `__fp_parse_large:N`.)

`__fp_parse_large_leading:wwNN` We shift the exponent by the number of digits in #1, namely the target number, 8, minus the *number of zeros* (number of digits missing). Then prepare to pack the 8 first digits. If the *next token* is a digit, read up to 6 more digits (digits 10 to 15). If it is a period, try to grab the end of our 8 first digits, branching to the `small` functions since the number of digit does not affect the exponent anymore. Finally, if this is the end of the significand, insert the *zeros* to complete the 8 first digits, insert 8 more, and look for an exponent.

```

11553 \cs_new:Npn \__fp_parse_large_leading:wwNN 1 #1 ; #2; #3 #4
11554 {
11555     + \c__fp_half_prec_int - #3
11556     \exp_after:wN \__fp_parse_pack_leading:NNNNNww
11557     \__int_value:w \__int_eval:w 1 #1
11558     \if_int_compare:w 9 < 1 \token_to_str:N #4 \exp_stop_f:
11559     \exp_after:wN \__fp_parse_large_trailing:wwNN

```

```

11560     \__int_value:w 1 \token_to_str:N #4
11561     \exp_after:wN \__fp_parse_digits_vi:N
11562     \exp:w
11563   \else:
11564     \if:w . \exp_not:N #4
11565       \exp_after:wN \__fp_parse_small_leading:wwNN
11566       \__int_value:w 1
11567       \cs:w
11568         __fp_parse_digits_
11569         \__int_to_roman:w #3
11570       :N \exp_after:wN
11571       \cs_end:
11572       \exp:w
11573     \else:
11574       #2
11575       \exp_after:wN \__fp_parse_pack_trailing:NNNNNNww
11576       \exp_after:wN 0
11577       \__int_value:w 1 0000 0000
11578       \__fp_parse_exponent:Nw #4
11579     \fi:
11580   \fi:
11581   \__fp_parse_expand:w
11582 }

```

(End definition for __fp_parse_large_leading:wwNN.)

__fp_parse_large_trailing:wwNN

We have just read 15 digits. If the *<next token>* is a digit, then the exponent shift caused by this block of 8 digits is 8, first argument to the `pack_trailing` function. We keep the *<digits>* and this 16-th digit, and find how this should be rounded using `__fp_parse_large_round:NN`. Otherwise, the exponent shift is the number of *<digits>*, 7 minus the *<number of zeros>*, and we test for a decimal point. This case happens in 123451234512345.67 with exactly 15 digits before the decimal separator. Then branch to the appropriate `small` auxiliary, grabbing a few more digits to complement the digits we already grabbed. Finally, if this is truly the end of the significand, look for an exponent after using the *<zeros>* and providing a 16-th digit of 0.

```

11583 \cs_new:Npn \__fp_parse_large_trailing:wwNN 1 #1 ; #2; #3 #4
11584 {
11585   \if_int_compare:w 9 < 1 \token_to_str:N #4 \exp_stop_f:
11586     \exp_after:wN \__fp_parse_pack_trailing:NNNNNNww
11587     \exp_after:wN \c__fp_half_prec_int
11588     \__int_value:w \__int_eval:w 1 #1 \token_to_str:N #4
11589     \exp_after:wN \__fp_parse_large_round:NN
11590     \exp_after:wN #4
11591     \exp:w
11592   \else:
11593     \exp_after:wN \__fp_parse_pack_trailing:NNNNNNww
11594     \__int_value:w \__int_eval:w 7 - #3 \exp_stop_f:
11595     \__int_value:w \__int_eval:w 1 #1
11596     \if:w . \exp_not:N #4
11597       \exp_after:wN \__fp_parse_small_trailing:wwNN
11598       \__int_value:w 1
11599       \cs:w
11600         __fp_parse_digits_
11601         \__int_to_roman:w #3

```

```

11602             :N \exp_after:wN
11603             \cs_end:
11604             \exp:w
11605         \else:
11606             #2 0 \__fp_parse_exponent:Nw #4
11607         \fi:
11608     \fi:
11609     \__fp_parse_expand:w
11610 }

```

(End definition for __fp_parse_large_trailing:wwNN.)

23.4.4 Number: beyond 16 digits, rounding

__fp_parse_round_loop:N This loop is called when rounding a number (whether the mantissa is small or large).
 __fp_parse_round_up:N It should appear in an integer expression. This function reads digits one by one, until reaching a non-digit, and adds 1 to the integer expression for each digit. If all digits found are 0, the function ends the expression by ;0, otherwise by ;1. This is done by switching the loop to round_up at the first non-zero digit, thus we avoid to test whether digits are 0 or not once we see a first non-zero digit.

```

11611 \cs_new:Npn \__fp_parse_round_loop:N #1
11612 {
11613     \if_int_compare:w 9 < 1 \token_to_str:N #1 \exp_stop_f:
11614     + 1
11615     \if:w 0 \token_to_str:N #1
11616         \exp_after:wN \__fp_parse_round_loop:N
11617         \exp:w
11618     \else:
11619         \exp_after:wN \__fp_parse_round_up:N
11620         \exp:w
11621     \fi:
11622 \else:
11623     \__fp_parse_return_semicolon:w 0 #1
11624 \fi:
11625 \__fp_parse_expand:w
11626 }
11627 \cs_new:Npn \__fp_parse_round_up:N #1
11628 {
11629     \if_int_compare:w 9 < 1 \token_to_str:N #1 \exp_stop_f:
11630     + 1
11631     \exp_after:wN \__fp_parse_round_up:N
11632     \exp:w
11633 \else:
11634     \__fp_parse_return_semicolon:w 1 #1
11635 \fi:
11636 \__fp_parse_expand:w
11637 }

```

(End definition for __fp_parse_round_loop:N and __fp_parse_round_up:N.)

__fp_parse_round_after:wN After the loop __fp_parse_round_loop:N, this function fetches an exponent with __fp_parse_exponent:N, and combines it with the number of digits counted by __fp_parse_round_loop:N. At the same time, the result 0 or 1 is added to the surrounding integer expression.

```

11638 \cs_new:Npn \__fp_parse_round_after:wN #1; #2
11639 {
11640     + #2 \exp_after:wN ;
11641     \__int_value:w \__int_eval:w #1 + \__fp_parse_exponent:N
11642 }

```

(End definition for __fp_parse_round_after:wN.)

__fp_parse_small_round:NN
__fp_parse_round_after:wN

Here, #1 is the digit that we are currently rounding (we only care whether it is even or odd). If #2 is not a digit, then fetch an exponent and expand to ;*<exponent>* only. Otherwise, we will expand to +0 or +1, then ;*<exponent>*. To decide which, call __fp_round_s:NNNw to know whether to round up, giving it as arguments a sign 0 (all explicit numbers are positive), the digit #1 to round, the first following digit #2, and either +0 or +1 depending on whether the following digits are all zero or not. This last argument is obtained by __fp_parse_round_loop:N, whose number of digits we discard by multiplying it by 0. The exponent which follows the number is also fetched by __fp_parse_round_after:wN.

```

11643 \cs_new:Npn \__fp_parse_small_round:NN #1#2
11644 {
11645     \if_int_compare:w 9 < 1 \token_to_str:N #2 \exp_stop_f:
11646     +
11647     \exp_after:wN \__fp_round_s:NNNw
11648     \exp_after:wN 0
11649     \exp_after:wN #1
11650     \exp_after:wN #2
11651     \__int_value:w \__int_eval:w
11652     \exp_after:wN \__fp_parse_round_after:wN
11653     \__int_value:w \__int_eval:w 0 * \__int_eval:w 0
11654     \exp_after:wN \__fp_parse_round_loop:N
11655     \exp:w
11656     \else:
11657         \__fp_parse_exponent:Nw #2
11658     \fi:
11659     \__fp_parse_expand:w
11660 }

```

(End definition for __fp_parse_small_round:NN and __fp_parse_round_after:wN.)

__fp_parse_large_round:NN
__fp_parse_large_round_test:NN
__fp_parse_large_round_aux:wNN

Large numbers are harder to round, as there may be a period in the way. Again, #1 is the digit that we are currently rounding (we only care whether it is even or odd). If there are no more digits (#2 is not a digit), then we must test for a period: if there is one, then switch to the rounding function for small significands, otherwise fetch an exponent. If there are more digits (#2 is a digit), then round, checking with __fp_parse_round_loop:N if all further digits vanish, or some are non-zero. This loop is not enough, as it is stopped by a period. After the loop, the aux function tests for a period: if it is present, then we must continue looking for digits, this time discarding the number of digits we find.

```

11661 \cs_new:Npn \__fp_parse_large_round:NN #1#2
11662 {
11663     \if_int_compare:w 9 < 1 \token_to_str:N #2 \exp_stop_f:
11664     +
11665     \exp_after:wN \__fp_round_s:NNNw
11666     \exp_after:wN 0

```

```

11667     \exp_after:wN #1
11668     \exp_after:wN #2
11669     \__int_value:w \__int_eval:w
11670     \exp_after:wN \__fp_parse_large_round_aux:wNN
11671     \__int_value:w \__int_eval:w 1
11672     \exp_after:wN \__fp_parse_round_loop:N
11673 \else: %^^A could be dot, or e, or other
11674     \exp_after:wN \__fp_parse_large_round_test:NN
11675     \exp_after:wN #1
11676     \exp_after:wN #2
11677 \fi:
11678 }
11679 \cs_new:Npn \__fp_parse_large_round_test:NN #1#2
11680 {
11681     \if:w . \exp_not:N #2
11682         \exp_after:wN \__fp_parse_small_round:NN
11683         \exp_after:wN #1
11684         \exp:w
11685     \else:
11686         \__fp_parse_exponent:Nw #2
11687     \fi:
11688     \__fp_parse_expand:w
11689 }
11690 \cs_new:Npn \__fp_parse_large_round_aux:wNN #1 ; #2 #3
11691 {
11692     + #2
11693     \exp_after:wN \__fp_parse_round_after:wN
11694     \__int_value:w \__int_eval:w #1
11695     \if:w . \exp_not:N #3
11696         + 0 * \__int_eval:w 0
11697         \exp_after:wN \__fp_parse_round_loop:N
11698         \exp:w \exp_after:wN \__fp_parse_expand:w
11699     \else:
11700         \exp_after:wN ;
11701         \exp_after:wN 0
11702         \exp_after:wN #3
11703     \fi:
11704 }

```

(End definition for __fp_parse_large_round:NN, __fp_parse_large_round_test:NN, and __fp_parse_large_round_aux:wNN.)

23.4.5 Number: finding the exponent

Expansion is a little bit tricky here, in part because we accept input where multiplication is implicit.

```

\@@_parse:n { 3.2 erf(0.1) }
\@@_parse:n { 3.2 e\l_my_int }
\@@_parse:n { 3.2 \c_pi_fp }

```

The first case indicates that just looking one character ahead for an “e” is not enough, since we would mistake the function `erf` for an exponent of “rf”. An alternative would be to look two tokens ahead and check if what follows is a sign or a digit, considering in that case that we must be finding an exponent. But taking care of the second case

requires that we unpack registers after `e`. However, blindly expanding the two tokens ahead completely would break the third example (unpacking is even worse). Indeed, in the course of reading 3.2, `\c_pi_fp` is expanded to `\s__fp __fp_chk:w 1 0 {-1} {3141} \dots`; and `\s__fp` stops the expansion. Expanding two tokens ahead would then force the expansion of `__fp_chk:w` (despite it being protected), and that function tries to produce an error.

What can we do? Really, the reason why this last case breaks is that just as `TeX` does, we should read ahead as little as possible. Here, the only case where there may be an exponent is if the first token ahead is `e`. Then we expand (and possibly unpack) the second token.

`__fp_parse_exponent:Nw` This auxiliary is convenient to smuggle some material through `\fi:` ending conditional processing. We place those `\fi:` (argument #2) at a very odd place because this allows us to insert `__int_eval:w \dots` there if needed.

```

11705 \cs_new:Npn \__fp_parse_exponent:Nw #1 #2 \__fp_parse_expand:w
11706 {
11707   \exp_after:wN ;
11708   \__int_value:w #2 \__fp_parse_exponent:N #1
11709 }

```

(End definition for `__fp_parse_exponent:Nw`.)

`__fp_parse_exponent:N`
`__fp_parse_exponent_aux:N` This function should be called within an `__int_value:w` expansion (or within an integer expression). It leaves digits of the exponent behind it in the input stream, and terminates the expansion with a semicolon. If there is no `e`, leave an exponent of 0. If there is an `e`, expand the next token to run some tests on it. The first rough test is that if the character code of #1 is greater than that of 9 (largest code valid for an exponent, less than any code valid for an identifier), there was in fact no exponent; otherwise, we search for the sign of the exponent.

```

11710 \cs_new:Npn \__fp_parse_exponent:N #1
11711 {
11712   \if:w e \exp_not:N #1
11713     \exp_after:wN \__fp_parse_exponent_aux:N
11714     \exp:w
11715   \else:
11716     0 \__fp_parse_return_semicolon:w #1
11717   \fi:
11718   \__fp_parse_expand:w
11719 }
11720 \cs_new:Npn \__fp_parse_exponent_aux:N #1
11721 {
11722   \if_int_compare:w \if_catcode:w \scan_stop: \exp_not:N #1
11723     0 \else: '#1 \fi: > '9 \exp_stop_f:
11724     0 \exp_after:wN ; \exp_after:wN e
11725   \else:
11726     \exp_after:wN \__fp_parse_exponent_sign:N
11727   \fi:
11728   #1
11729 }

```

(End definition for `__fp_parse_exponent:N` and `__fp_parse_exponent_aux:N`.)

`__fp_parse_exponent_sign:N` Read signs one by one (if there is any).

```

11730 \cs_new:Npn \__fp_parse_exponent_sign:N #1
11731 {
11732   \if:w + \if:w - \exp_not:N #1 + \fi: \token_to_str:N #1
11733   \exp_after:wN \__fp_parse_exponent_sign:N
11734   \exp:w \exp_after:wN \__fp_parse_expand:w
11735   \else:
11736     \exp_after:wN \__fp_parse_exponent_body:N
11737     \exp_after:wN #1
11738   \fi:
11739 }

```

(End definition for `__fp_parse_exponent_sign:N`.)

`__fp_parse_exponent_body:N` An exponent can be an explicit integer (most common case), or various other things (most of which are invalid).

```

11740 \cs_new:Npn \__fp_parse_exponent_body:N #1
11741 {
11742   \if_int_compare:w 9 < 1 \token_to_str:N #1 \exp_stop_f:
11743   \token_to_str:N #1
11744   \exp_after:wN \__fp_parse_exponent_digits:N
11745   \exp:w
11746   \else:
11747     \__fp_parse_exponent_keep:NTF #1
11748     { \__fp_parse_return_semicolon:w #1 }
11749     {
11750       \exp_after:wN ;
11751       \exp:w
11752     }
11753   \fi:
11754   \__fp_parse_expand:w
11755 }

```

(End definition for `__fp_parse_exponent_body:N`.)

`__fp_parse_exponent_digits:N` Read digits one by one, and leave them behind in the input stream. When finding a non-digit, stop, and insert a semicolon. Note that we do not check for overflow of the exponent, hence there can be a \TeX error. It is mostly harmless, except when parsing 0e9876543210, which should be a valid representation of 0, but is not.

```

11756 \cs_new:Npn \__fp_parse_exponent_digits:N #1
11757 {
11758   \if_int_compare:w 9 < 1 \token_to_str:N #1 \exp_stop_f:
11759   \token_to_str:N #1
11760   \exp_after:wN \__fp_parse_exponent_digits:N
11761   \exp:w
11762   \else:
11763     \__fp_parse_return_semicolon:w #1
11764   \fi:
11765   \__fp_parse_expand:w
11766 }

```

(End definition for `__fp_parse_exponent_digits:N`.)

`__fp_parse_exponent_keep:NTF` This is the last building block for parsing exponents. The argument #1 is already fully expanded, and neither + nor - nor a digit. It can be:

- `\s__fp`, marking the start of an internal floating point, invalid here;
- another control sequence equal to `\relax`, probably a bad variable;
- a register: in this case we make sure that it is an integer register, not a dimension;
- a character other than +, - or digits, again, an error.

```

11767 \prg_new_conditional:Npnn \__fp_parse_exponent_keep:N #1 { TF }
11768 {
11769   \if_catcode:w \scan_stop: \exp_not:N #1
11770   \if_meaning:w \scan_stop: #1
11771   \if_int_compare:w
11772     \__str_if_eq_x:nn { \s__fp } { \exp_not:N #1 }
11773     = 0 \exp_stop_f:
11774     0
11775     \__msg_kernel_expandable_error:nnn
11776     { kernel } { fp-after-e } { floating~point~ }
11777     \prg_return_true:
11778   \else:
11779     0
11780     \__msg_kernel_expandable_error:nnn
11781     { kernel } { bad-variable } { #1 }
11782     \prg_return_false:
11783   \fi:
11784   \else:
11785     \if_int_compare:w
11786       \__str_if_eq_x:nn { \__int_value:w #1 } { \tex_the:D #1 }
11787       = 0 \exp_stop_f:
11788       \__int_value:w #1
11789     \else:
11790       0
11791       \__msg_kernel_expandable_error:nnn
11792       { kernel } { fp-after-e } { dimension~#1 }
11793     \fi:
11794     \prg_return_false:
11795   \fi:
11796   \else:
11797     0
11798     \__msg_kernel_expandable_error:nnn
11799     { kernel } { fp-missing } { exponent }
11800     \prg_return_true:
11801   \fi:
11802 }

```

(End definition for `__fp_parse_exponent_keep:N`.)

23.5 Constants, functions and prefix operators

23.5.1 Prefix operators

`__fp_parse_prefix_+:Nw` A unary + does nothing: we should continue looking for a number.

```

11803 \cs_new_eq:cN { \__fp_parse_prefix_+:Nw } \__fp_parse_one:Nw

```

(End definition for `__fp_parse_prefix_+:Nw`.)

`__fp_parse_apply_unary:NNWwN` Here, #1 is a precedence, #2 is some extra data used by some functions, #3 is *e.g.*, `_fp_sin_o:w`, and expands once after the calculation, #4 is the operand, and #5 is a `__fp_parse_infix_...:N` function. We feed the data #2, and the argument #4, to the function #3, which expands `\exp:w` thus the infix function #5.

```

11804 \cs_new:Npn \__fp_parse_apply_unary:NNWwN #1#2#3#4#5
11805 {
11806     #3 #2 #4 @
11807     \exp:w \exp_end_continue_f:w #5 #1
11808 }

```

(End definition for `__fp_parse_apply_unary:NNWwN`.)

`__fp_parse_prefix_-:Nw` The unary `-` and boolean not are harder: we parse the operand using a precedence equal to the maximum of the previous precedence ##1 and the precedence `\c__fp_prec_not_int` of the unary operator, then call the appropriate `__fp_⟨operation⟩_o:w` function, where the *⟨operation⟩* is `set_sign` or `not`.

`__fp_parse_prefix!:Nw`

```

11809 \cs_set_protected:Npn \__fp_tmp:w #1#2#3#4
11810 {
11811     \cs_new:cpn { __fp_parse_prefix_ #1 :Nw } ##1
11812     {
11813         \exp_after:wN \__fp_parse_apply_unary:NNWwN
11814         \exp_after:wN ##1
11815         \exp_after:wN #4
11816         \exp_after:wN #3
11817         \exp:w
11818         \if_int_compare:w #2 < ##1
11819             \__fp_parse_operand:Nw ##1
11820         \else:
11821             \__fp_parse_operand:Nw #2
11822         \fi:
11823         \__fp_parse_expand:w
11824     }
11825 }
11826 \__fp_tmp:w - \c__fp_prec_not_int \__fp_set_sign_o:w 2
11827 \__fp_tmp:w ! \c__fp_prec_not_int \__fp_not_o:w ?

```

(End definition for `__fp_parse_prefix_-:Nw` and `__fp_parse_prefix!:Nw`.)

`__fp_parse_prefix.:Nw` Numbers which start with a decimal separator (a period) end up here. Of course, we do not look for an operand, but for the rest of the number. This function is very similar to `__fp_parse_one_digit:NN` but calls `__fp_parse_strim_zeros:N` to trim zeros after the decimal point, rather than the `trim_zeros` function for zeros before the decimal point.

```

11828 \cs_new:cpn { __fp_parse_prefix.:Nw } #1
11829 {
11830     \exp_after:wN \__fp_parse_infix_after_operand:NwN
11831     \exp_after:wN #1
11832     \exp:w \exp_end_continue_f:w
11833     \exp_after:wN \__fp_sanitize:wN
11834     \__int_value:w \__int_eval:w 0 \__fp_parse_strim_zeros:N
11835 }

```

(End definition for `__fp_parse_prefix.:Nw`.)

```

    \__fp_parse_prefix_(:Nw
    \__fp_parse_lparen_after:NwN

```

The left parenthesis is treated as a unary prefix operator because it appears in exactly the same settings. Commas will be allowed if the previous precedence is 16 (function with multiple arguments). In this case, find an operand using the precedence 1; otherwise the precedence 0. Once the operand is found, the `lparen_after` auxiliary makes sure that there was a closing parenthesis (otherwise it complains), and leaves in the input stream the array it found as an operand, fetching the following infix operator.

```

11836 \group_begin:
11837   \char_set_catcode_letter:N (
11838   \char_set_catcode_letter:N )
11839   \cs_new:Npn \__fp_parse_prefix_(:Nw #1
11840   {
11841     \exp_after:wN \__fp_parse_lparen_after:NwN
11842     \exp_after:wN #1
11843     \exp:w
11844     \if_int_compare:w #1 = \c__fp_prec_funcii_int
11845       \__fp_parse_operand:Nw \c__fp_prec_comma_int
11846     \else:
11847       \__fp_parse_operand:Nw \c__fp_prec_paren_int
11848     \fi:
11849     \__fp_parse_expand:w
11850   }
11851   \cs_new:Npn \__fp_parse_lparen_after:NwN #1#2 @ #3
11852   {
11853     \token_if_eq_meaning:NNTF #3 \__fp_parse_infix_):N
11854     {
11855       \__fp_exp_after_array_f:w #2 \s__fp_stop
11856       \exp_after:wN \__fp_parse_infix:NN
11857       \exp_after:wN #1
11858       \exp:w \__fp_parse_expand:w
11859     }
11860     {
11861       \__msg_kernel_expandable_error:nnn
11862       { kernel } { fp-missing } { } ) }
11863     #2 @ \use_none:n #3
11864   }
11865   }
11866 \group_end:

```

(End definition for `__fp_parse_prefix_(:Nw` and `__fp_parse_lparen_after:NwN`.)

```

    \__fp_parse_prefix_):Nw

```

The right parenthesis can appear as unary prefixes when arguments of a multi-argument function end with a comma, or when there is no argument, as in `max(1,2,)` or in `rand()`. In single-argument functions (precedence 0 rather than 1) forbid this.

```

11867 \cs_new:cpn { __fp_parse_prefix_):Nw } #1
11868 {
11869   \if_int_compare:w #1 = \c__fp_prec_comma_int
11870   \else:
11871     \__msg_kernel_expandable_error:nnn
11872     { kernel } { fp-missing-number } { } ) }
11873   \exp_after:wN \c_nan_fp \exp:w \exp_end_continue_f:w
11874   \fi:
11875   \__fp_parse_infix:NN #1 )
11876 }

```

(End definition for `__fp_parse_prefix_):Nw`.)

23.5.2 Constants

Some words correspond to constant floating points. The floating point constant is left as a result of `__fp_parse_one:Nw` after expanding `__fp_parse_infix:NN`.

```

\__fp_parse_word_inf:N
\__fp_parse_word_nan:N
\__fp_parse_word_pi:N
\__fp_parse_word_deg:N
\__fp_parse_word_true:N
\__fp_parse_word_false:N
11877 \cs_set_protected:Npn \__fp_tmp:w #1 #2
11878 {
11879   \cs_new:cpn { __fp_parse_word_#1:N }
11880   { \exp_after:wN #2 \exp:w \exp_end_continue_f:w \__fp_parse_infix:NN }
11881 }

```

```

11882 \__fp_tmp:w { inf } \c_inf_fp
11883 \__fp_tmp:w { nan } \c_nan_fp
11884 \__fp_tmp:w { pi } \c_pi_fp
11885 \__fp_tmp:w { deg } \c_one_degree_fp
11886 \__fp_tmp:w { true } \c_one_fp
11887 \__fp_tmp:w { false } \c_zero_fp

```

(End definition for `__fp_parse_word_inf:N` and others.)

Dimension units are also floating point constants but their value is not stored as a floating point constant. We give the values explicitly here.

```

\__fp_parse_word_pt:N
\__fp_parse_word_in:N
\__fp_parse_word_pc:N
\__fp_parse_word_cm:N
\__fp_parse_word_mm:N
\__fp_parse_word_dd:N
\__fp_parse_word_cc:N
\__fp_parse_word_nd:N
\__fp_parse_word_nc:N
\__fp_parse_word_bp:N
\__fp_parse_word_sp:N
11888 \cs_set_protected:Npn \__fp_tmp:w #1 #2
11889 {
11890   \cs_new:cpn { __fp_parse_word_#1:N }
11891   {
11892     \__fp_exp_after_f:nw { \__fp_parse_infix:NN }
11893     \s__fp \__fp_chk:w 10 #2 ;
11894   }
11895 }
11896 \__fp_tmp:w {pt} { {1} {1000} {0000} {0000} {0000} }
11897 \__fp_tmp:w {in} { {2} {7227} {0000} {0000} {0000} }
11898 \__fp_tmp:w {pc} { {2} {1200} {0000} {0000} {0000} }
11899 \__fp_tmp:w {cm} { {2} {2845} {2755} {9055} {1181} }
11900 \__fp_tmp:w {mm} { {1} {2845} {2755} {9055} {1181} }
11901 \__fp_tmp:w {dd} { {1} {1070} {0085} {6496} {0630} }
11902 \__fp_tmp:w {cc} { {2} {1284} {0102} {7795} {2756} }
11903 \__fp_tmp:w {nd} { {1} {1066} {9783} {4645} {6693} }
11904 \__fp_tmp:w {nc} { {2} {1280} {3740} {1574} {8031} }
11905 \__fp_tmp:w {bp} { {1} {1003} {7500} {0000} {0000} }
11906 \__fp_tmp:w {sp} { {-4} {1525} {8789} {0625} {0000} }

```

(End definition for `__fp_parse_word_pt:N` and others.)

The font-dependent units `em` and `ex` must be evaluated on the fly. We reuse an auxiliary of `\dim_to_fp:n`.

```

11907 \tl_map_inline:nn { {em} {ex} }
11908 {
11909   \cs_new:cpn { __fp_parse_word_#1:N }
11910   {
11911     \exp_after:wN \__fp_from_dim_test:ww
11912     \exp_after:wN 0 \exp_after:wN ,
11913     \__int_value:w \__dim_eval:w 1 #1 \exp_after:wN ;
11914     \exp:w \exp_end_continue_f:w \__fp_parse_infix:NN
11915   }
11916 }

```

(End definition for `__fp_parse_word_em:N` and `__fp_parse_word_ex:N`.)

23.5.3 Functions

```

\__fp_parse_unary_function:nNN
\__fp_parse_function:NNN
11917 \cs_new:Npn \__fp_parse_unary_function:nNN #1#2#3
11918 {
11919     \exp_after:wN \__fp_parse_apply_unary:NNNwN
11920     \exp_after:wN #3
11921     \exp_after:wN #2
11922     \cs:w __fp_#1_o:w \exp_after:wN \cs_end:
11923     \exp:w
11924     \__fp_parse_operand:Nw \c__fp_prec_func_int \__fp_parse_expand:w
11925 }
11926 \cs_new:Npn \__fp_parse_function:NNN #1#2#3
11927 {
11928     \exp_after:wN \__fp_parse_apply_unary:NNNwN
11929     \exp_after:wN #3
11930     \exp_after:wN #2
11931     \exp_after:wN #1
11932     \exp:w
11933     \__fp_parse_operand:Nw \c__fp_prec_funcii_int \__fp_parse_expand:w
11934 }

```

(End definition for `__fp_parse_unary_function:nNN` and `__fp_parse_function:NNN`.)

```

\__fp_parse_word_acot:N
\__fp_parse_word_acotd:N
\__fp_parse_word_atan:N
\__fp_parse_word_atand:N
\__fp_parse_word_max:N
\__fp_parse_word_min:N
\__fp_parse_word_rand:N
\__fp_parse_word_randint:N
21935 \cs_new:Npn \__fp_parse_word_acot:N
21936 { \__fp_parse_function:NNN \__fp_acot_o:Nw \use_i:nn }
21937 \cs_new:Npn \__fp_parse_word_acotd:N
21938 { \__fp_parse_function:NNN \__fp_acot_o:Nw \use_ii:nn }
21939 \cs_new:Npn \__fp_parse_word_atan:N
21940 { \__fp_parse_function:NNN \__fp_atan_o:Nw \use_i:nn }
21941 \cs_new:Npn \__fp_parse_word_atand:N
21942 { \__fp_parse_function:NNN \__fp_atan_o:Nw \use_ii:nn }
21943 \cs_new:Npn \__fp_parse_word_max:N
21944 { \__fp_parse_function:NNN \__fp_minmax_o:Nw 2 }
21945 \cs_new:Npn \__fp_parse_word_min:N
21946 { \__fp_parse_function:NNN \__fp_minmax_o:Nw 0 }
21947 \cs_new:Npn \__fp_parse_word_rand:N
21948 { \__fp_parse_function:NNN \__fp_rand_o:Nw ? }
21949 \cs_new:Npn \__fp_parse_word_randint:N
21950 { \__fp_parse_function:NNN \__fp_randint_o:Nw ? }

```

(End definition for `__fp_parse_word_acot:N` and others.)

```

\__fp_parse_word_abs:N
\__fp_parse_word_exp:N
\__fp_parse_word_ln:N
\__fp_parse_word_sqrt:N
21951 \cs_new:Npn \__fp_parse_word_abs:N
21952 { \__fp_parse_unary_function:nNN { set_sign } 0 }
21953 \cs_new:Npn \__fp_parse_word_exp:N
21954 { \__fp_parse_unary_function:nNN {exp} ? }
21955 \cs_new:Npn \__fp_parse_word_ln:N
21956 { \__fp_parse_unary_function:nNN {ln} ? }
21957 \cs_new:Npn \__fp_parse_word_sqrt:N
21958 { \__fp_parse_unary_function:nNN {sqrt} ? }

```

Unary functions.

(End definition for `_fp_parse_word_abs:N` and others.)

```

\_fp_parse_word_acos:N      Unary functions.
\_fp_parse_word_acosd:N    11959 \tl_map_inline:nn
\_fp_parse_word_acsc:N      {
\_fp_parse_word_acscd:N    11961   {acos} {acsc} {asec} {asin}
\_fp_parse_word_asec:N      11962   {cos} {cot} {csc} {sec} {sin} {tan}
\_fp_parse_word_asecd:N    11963 }
\_fp_parse_word_asin:N      11964 {
\_fp_parse_word_asind:N    11965   \cs_new:cpn { \_fp_parse_word_#1:N }
\_fp_parse_word_cos:N      11966   { \_fp_parse_unary_function:nnn {#1} \use_i:nn }
\_fp_parse_word_cosd:N    11967   \cs_new:cpn { \_fp_parse_word_#1d:N }
\_fp_parse_word_cot:N      11968   { \_fp_parse_unary_function:nnn {#1} \use_ii:nn }
\_fp_parse_word_cotd:N    11969 }
\_fp_parse_word_csc:N

```

(End definition for `_fp_parse_word_acos:N` and others.)

```

\_fp_parse_word_cscd:N
\_fp_parse_word_trunc:N    11970 \cs_new:Npn \_fp_parse_word_trunc:N
\_fp_parse_word_sec:N      { \_fp_parse_function:nnn \_fp_round_o:Nw \_fp_round_to_zero:nnn }
\_fp_parse_word_floord:N  11971 \cs_new:Npn \_fp_parse_word_floor:N
\_fp_parse_word_ceild:N    11972 { \_fp_parse_function:nnn \_fp_round_o:Nw \_fp_round_to_ninf:nnn }
\_fp_parse_word_sin:N      11973 \cs_new:Npn \_fp_parse_word_ceil:N
\_fp_parse_word_sind:N    11974 { \_fp_parse_function:nnn \_fp_round_o:Nw \_fp_round_to_pinf:nnn }
\_fp_parse_word_tan:N      11975
\_fp_parse_word_tand:N

```

(End definition for `_fp_parse_word_trunc:N`, `_fp_parse_word_floor:N`, and `_fp_parse_word_ceil:N`.)

```

\_fp_parse_word_round:N    This looks for +, -, 0 after round. That syntax is deprecated.
\_fp_parse_round:Nw      11976 \cs_new:Npn \_fp_parse_word_round:N #1#2
round+                   11977 {
round0                   11978   \if_meaning:w + #2
round-                   11979   \_fp_parse_round:Nw \_fp_round_to_pinf:nnn
                           11980   \else:
                           11981     \if_meaning:w 0 #2
                           11982     \_fp_parse_round:Nw \_fp_round_to_zero:nnn
                           11983     \else:
                           11984       \if_meaning:w - #2
                           11985       \_fp_parse_round:Nw \_fp_round_to_ninf:nnn
                           11986       \fi:
                           11987       \fi:
                           11988       \fi:
                           11989       \_fp_parse_function:nnn
                           11990       \_fp_round_o:Nw \_fp_round_to_nearest:nnn #1
                           11991       #2
                           11992     }
                           11993   \cs_new:Npn \_fp_parse_round:Nw
                           11994     #1 #2 \_fp_round_to_nearest:nnn #3#4 { #2 #1 #3 }

```

(End definition for `_fp_parse_word_round:N` and others.)

23.6 Main functions

`__fp_parse:n` Start an `\exp:w` expansion so that `__fp_parse:n` expands in two steps. The `__fp_parse_operand:Nw` function will perform computations until reaching an operation with precedence `\c__fp_prec_end_int` or less, namely, the end of the expression. The marker `\s__fp_mark` indicates that the next token is an already parsed version of an infix operator, and `__fp_parse_infix_end:N` has infinitely negative precedence. Finally, clean up a (well-defined) set of extra tokens and stop the initial expansion with `\exp_end:.`

```

11995 \cs_new:Npn \__fp_parse:n #1
11996 {
11997   \exp:w
11998   \exp_after:wN \__fp_parse_after:ww
11999   \exp:w
12000   \__fp_parse_operand:Nw \c__fp_prec_end_int
12001   \__fp_parse_expand:w #1
12002   \s__fp_mark \__fp_parse_infix_end:N
12003   \s__fp_stop
12004 }
12005 \cs_new:Npn \__fp_parse_after:ww
12006   #1@ \__fp_parse_infix_end:N \s__fp_stop
12007 { \exp_end: #1 }

```

(End definition for `__fp_parse:n` and `__fp_parse_after:ww`.)

`__fp_parse_o:n`

```

12008 \cs_new:Npn \__fp_parse_o:n #1
12009 {
12010   \exp_after:wN \exp_after:wN
12011   \exp_after:wN \__fp_exp_after_o:w
12012   \__fp_parse:n {#1}
12013 }

```

(End definition for `__fp_parse_o:n`.)

`__fp_parse_operand:Nw`
`__fp_parse_continue:NwN`

The `__fp_parse_operand` This is just a shorthand which sets up both `__fp_parse_continue` and `__fp_parse_one` with the same precedence. Note the trailing `\exp:w`. This function should be used with much care.

```

12014 \cs_new:Npn \__fp_parse_operand:Nw #1
12015 {
12016   \exp_end_continue_f:w
12017   \exp_after:wN \__fp_parse_continue:NwN
12018   \exp_after:wN #1
12019   \exp:w \exp_end_continue_f:w
12020   \exp_after:wN \__fp_parse_one:Nw
12021   \exp_after:wN #1
12022   \exp:w
12023 }
12024 \cs_new:Npn \__fp_parse_continue:NwN #1 #2 @ #3 { #3 #1 #2 @ }

```

(End definition for `__fp_parse_operand:Nw` and `__fp_parse_continue:NwN`.)

`_fp_parse_apply_binary:NwNwN` Receives $\langle precedence \rangle \langle operand_1 \rangle @ \langle operation \rangle \langle operand_2 \rangle @ \langle infix command \rangle$. Builds the appropriate call to the $\langle operation \rangle$ #3.

```

12025 \cs_new:Npn \_fp_parse_apply_binary:NwNwN #1 #2@ #3 #4@ #5
12026 {
12027   \exp_after:wN \_fp_parse_continue:NwN
12028   \exp_after:wN #1
12029   \exp:w \exp_end_continue_f:w \cs:w \_fp_#3_o:ww \cs_end: #2 #4
12030   \exp:w \exp_end_continue_f:w #5 #1
12031 }

```

(End definition for `_fp_parse_apply_binary:NwNwN`.)

23.7 Infix operators

`_fp_parse_infix_after_operand:NwN`

```

12032 \cs_new:Npn \_fp_parse_infix_after_operand:NwN #1 #2;
12033 {
12034   \_fp_exp_after_f:nw { \_fp_parse_infix:NN #1 }
12035   #2;
12036 }
12037 \group_begin:
12038   \char_set_catcode_letter:N \*
12039   \cs_new:Npn \_fp_parse_infix:NN #1 #2
12040   {
12041     \if_catcode:w \scan_stop: \exp_not:N #2
12042     \if_int_compare:w
12043       \_str_if_eq_x:nn { \s__fp_mark } { \exp_not:N #2 }
12044       = 0 \exp_stop_f:
12045       \exp_after:wN \exp_after:wN
12046       \exp_after:wN \_fp_parse_infix_mark:NNN
12047     \else:
12048       \exp_after:wN \exp_after:wN
12049       \exp_after:wN \_fp_parse_infix_juxtapose:N
12050     \fi:
12051   \else:
12052     \if_int_compare:w
12053       \_int_eval:w
12054       ( '#2 \if_int_compare:w '#2 > 'Z - 32 \fi: ) / 26
12055       = 3 \exp_stop_f:
12056       \exp_after:wN \exp_after:wN
12057       \exp_after:wN \_fp_parse_infix_juxtapose:N
12058     \else:
12059       \exp_after:wN \_fp_parse_infix_check:NNN
12060       \cs:w
12061         \_fp_parse_infix_ \token_to_str:N #2 :N
12062       \exp_after:wN \exp_after:wN \exp_after:wN
12063     \cs_end:
12064     \fi:
12065   \fi:
12066   #1
12067   #2
12068 }
12069 \cs_new:Npn \_fp_parse_infix_check:NNN #1#2#3
12070 {

```

```

12071 \if_meaning:w \scan_stop: #1
12072 \__msg_kernel_expandable_error:nnn
12073 { kernel } { fp-missing } { * }
12074 \exp_after:wN \__fp_parse_infix_*:N
12075 \exp_after:wN #2
12076 \exp_after:wN #3
12077 \else:
12078 \exp_after:wN #1
12079 \exp_after:wN #2
12080 \exp:w \exp_after:wN \__fp_parse_expand:w
12081 \fi:
12082 }
12083 \group_end:

```

(End definition for __fp_parse_infix_after_operand:NwN.)

23.7.1 Closing parentheses and commas

__fp_parse_infix_mark:NNN As an infix operator, \s__fp_mark means that the next token (#3) has already gone through __fp_parse_infix:NN and should be provided the precedence #1. The scan mark #2 is discarded.

```

12084 \cs_new:Npn \__fp_parse_infix_mark:NNN #1#2#3 { #3 #1 }

```

(End definition for __fp_parse_infix_mark:NNN.)

__fp_parse_infix_end:N This one is a little bit odd: force every previous operator to end, regardless of the precedence.

```

12085 \cs_new:Npn \__fp_parse_infix_end:N #1
12086 { @ \use_none:n \__fp_parse_infix_end:N }

```

(End definition for __fp_parse_infix_end:N.)

__fp_parse_infix_):N This is very similar to __fp_parse_infix_end:N, complaining about an extra closing parenthesis if the previous operator was the beginning of the expression.

```

12087 \group_begin:
12088 \char_set_catcode_letter:N \)
12089 \cs_new:Npn \__fp_parse_infix_):N #1
12090 {
12091 \if_int_compare:w #1 < \c__fp_prec_paren_int
12092 \__msg_kernel_expandable_error:nnn { kernel } { fp-extra } { ) }
12093 \exp_after:wN \__fp_parse_infix:NN
12094 \exp_after:wN #1
12095 \exp:w \exp_after:wN \__fp_parse_expand:w
12096 \else:
12097 \exp_after:wN @
12098 \exp_after:wN \use_none:n
12099 \exp_after:wN \__fp_parse_infix_):N
12100 \fi:
12101 }
12102 \group_end:

```

(End definition for __fp_parse_infix_):N.)

`__fp_parse_infix_`,:N `__fp_`,_o:ww is a complicated way of replacing any number of floating point arguments by nan.

```

\__fp_parse_infix_comma:w
\__fp_parse_infix_comma_error:w
\__fp_
```

```

12103 \group_begin:
12104   \char_set_catcode_letter:N \,
12105   \cs_new:Npn \__fp_parse_infix_,:N #1
12106   {
12107     \if_int_compare:w #1 > \c__fp_prec_comma_int
12108     \exp_after:wN @
12109     \exp_after:wN \use_none:n
12110     \exp_after:wN \__fp_parse_infix_,:N
12111   \else:
12112     \if_int_compare:w #1 < \c__fp_prec_comma_int
12113     \__fp_parse_infix_comma_error:w
12114   \fi:
12115     \exp_after:wN \__fp_parse_infix_comma:w
12116     \exp:w \__fp_parse_operand:Nw \c__fp_prec_comma_int
12117     \exp_after:wN \__fp_parse_expand:w
12118   \fi:
12119 }
12120 \cs_new:Npn \__fp_parse_infix_comma:w #1 @
12121 { #1 @ \use_none:n }
12122 \cs_new:Npn \__fp_parse_infix_comma_error:w #1 \exp:w
12123 {
12124   \fi:
12125   \_msg_kernel_expandable_error:nn { kernel } { fp-extra-comma }
12126   \exp_after:wN @
12127   \exp_after:wN \__fp_parse_apply_binary:NwNwN
12128   \exp_after:wN ,
12129   \exp:w
12130 }
12131 \cs_new:Npn \__fp_
```

(End definition for `__fp_parse_infix_`,:N and others.)

23.7.2 Usual infix operators

`__fp_parse_infix_+`:N As described in the “work plan”, each infix operator has an associated `\..._infix...` function, a computing function, and precedence, given as arguments to `__fp_tmp:w`.
`__fp_parse_infix_-`:N Using the general mechanism for arithmetic operations. The power operation must be associative in the opposite order from all others. For this, we use two distinct precedences.
`__fp_parse_infix_/`:N The odd requirement to set `\+` here is to cover the case where `expl3` is loaded by plain \TeX : `\+` is an `\outer` macro there, and so the following code would otherwise give an error in that case.
`__fp_parse_infix_mul`:N
`__fp_parse_infix_and`:N
`__fp_parse_infix_or`:N
`__fp_parse_infix^`:N

```

12141 \group_begin:
```

```

12142 \cs_set:Npn \+ { }
12143 \cs_set:Npn \+ { }
12144 \cs_set:Npn \+ { }
12145 \char_set_catcode_other:N \&
12146 \char_set_catcode_letter:N \^
12147 \char_set_catcode_letter:N \_
12148 \char_set_catcode_letter:N \-
12149 \char_set_catcode_letter:N \+
12150 \cs_set_protected:Npn \__fp_tmp:w #1#2#3#4
12151 {
12152   \cs_new:Npn #1 ##1
12153   {
12154     \if_int_compare:w ##1 < #3
12155       \exp_after:wN @
12156       \exp_after:wN \__fp_parse_apply_binary:NwNwN
12157       \exp_after:wN #2
12158       \exp:w
12159       \__fp_parse_operand:Nw #4
12160       \exp_after:wN \__fp_parse_expand:w
12161     \else:
12162       \exp_after:wN @
12163       \exp_after:wN \use_none:n
12164       \exp_after:wN #1
12165     \fi:
12166   }
12167 }
12168 \__fp_tmp:w \__fp_parse_infix_~:N ~ \c__fp_prec_hatii_int \c__fp_prec_hat_int
12169 \__fp_tmp:w \__fp_parse_infix_/:N / \c__fp_prec_times_int \c__fp_prec_times_int
12170 \__fp_tmp:w \__fp_parse_infix_mul:N * \c__fp_prec_times_int \c__fp_prec_times_int
12171 \__fp_tmp:w \__fp_parse_infix_-:N - \c__fp_prec_plus_int \c__fp_prec_plus_int
12172 \__fp_tmp:w \__fp_parse_infix_+:N + \c__fp_prec_plus_int \c__fp_prec_plus_int
12173 \__fp_tmp:w \__fp_parse_infix_and:N & \c__fp_prec_and_int \c__fp_prec_and_int
12174 \__fp_tmp:w \__fp_parse_infix_or:N | \c__fp_prec_or_int \c__fp_prec_or_int
12175 \group_end:

```

(End definition for __fp_parse_infix_+:N and others.)

23.7.3 Juxtaposition

__fp_parse_infix_(:N When an opening parenthesis appears where we expect an infix operator, we compute the product of the previous operand and the contents of the parentheses using __fp_parse_infix_juxtapose:N.

```

12176 \cs_new:cpn { __fp_parse_infix_(:N } #1
12177 { \__fp_parse_infix_juxtapose:N #1 ( }

```

(End definition for __fp_parse_infix_(:N.)

__fp_parse_infix_juxtapose:N Juxtaposition follows the same scheme as other binary operations, but calls __fp_parse_apply_juxtapose:NwNwN rather than directly calling __fp_parse_apply_binary:NwNwN. This lets us catch errors such as ... (1,2,3)pt where one operand of the juxtaposition is not a single number: both #3 and #5 of the apply auxiliary must be empty.

```

12178 \cs_new:Npn \__fp_parse_infix_juxtapose:N #1
12179 {

```

```

12180 \if_int_compare:w #1 < \c__fp_prec_times_int
12181 \exp_after:wN @
12182 \exp_after:wN \__fp_parse_apply_juxtapose:NwwN
12183 \exp:w
12184 \__fp_parse_operand:Nw \c__fp_prec_times_int
12185 \exp_after:wN \__fp_parse_expand:w
12186 \else:
12187 \exp_after:wN @
12188 \exp_after:wN \use_none:n
12189 \exp_after:wN \__fp_parse_infix_juxtapose:N
12190 \fi:
12191 }
12192 \cs_new:Npn \__fp_parse_apply_juxtapose:NwwN #1 #2;#3@ #4;#5@
12193 {
12194 \if_catcode:w ^ \tl_to_str:n { #3 #5 } ^
12195 \else:
12196 \__fp_error:nffn { invalid-ii }
12197 { \__fp_array_to_clist:n { #2; #3 } }
12198 { \__fp_array_to_clist:n { #4; #5 } }
12199 { }
12200 \fi:
12201 \__fp_parse_apply_binary:NwNwN #1 #2;@ * #4;@
12202 }

```

(End definition for __fp_parse_infix_juxtapose:N and __fp_parse_apply_juxtapose:NwwN.)

23.7.4 Multi-character cases

__fp_parse_infix_*:N

```

12203 \group_begin:
12204 \char_set_catcode_letter:N ^
12205 \cs_new:cpn { __fp_parse_infix_*:N } #1#2
12206 {
12207 \if:w * \exp_not:N #2
12208 \exp_after:wN \__fp_parse_infix_^:N
12209 \exp_after:wN #1
12210 \else:
12211 \exp_after:wN \__fp_parse_infix_mul:N
12212 \exp_after:wN #1
12213 \exp_after:wN #2
12214 \fi:
12215 }
12216 \group_end:

```

(End definition for __fp_parse_infix_*:N.)

__fp_parse_infix_|:Nw

__fp_parse_infix_&:Nw

```

12217 \group_begin:
12218 \char_set_catcode_letter:N \
12219 \char_set_catcode_letter:N &
12220 \cs_new:Npn \__fp_parse_infix_|:N #1#2
12221 {
12222 \if:w | \exp_not:N #2
12223 \exp_after:wN \__fp_parse_infix_|:N

```

```

12224         \exp_after:wN #1
12225         \exp:w \exp_after:wN \__fp_parse_expand:w
12226     \else:
12227         \exp_after:wN \__fp_parse_infix_or:N
12228         \exp_after:wN #1
12229         \exp_after:wN #2
12230     \fi:
12231 }
12232 \cs_new:Npn \__fp_parse_infix_&:N #1#2
12233 {
12234     \if:w & \exp_not:N #2
12235         \exp_after:wN \__fp_parse_infix_&:N
12236         \exp_after:wN #1
12237         \exp:w \exp_after:wN \__fp_parse_expand:w
12238     \else:
12239         \exp_after:wN \__fp_parse_infix_and:N
12240         \exp_after:wN #1
12241         \exp_after:wN #2
12242     \fi:
12243 }
12244 \group_end:

```

(End definition for __fp_parse_infix_|:Nw and __fp_parse_infix_&:Nw.)

23.7.5 Ternary operator

```

\__fp_parse_infix_?:N
\__fp_parse_infix_:N
12245 \group_begin:
12246     \char_set_catcode_letter:N \?
12247     \cs_new:Npn \__fp_parse_infix_?:N #1
12248     {
12249         \if_int_compare:w #1 < \c__fp_prec_quest_int
12250             \exp_after:wN @
12251             \exp_after:wN \__fp_ternary:NwwN
12252             \exp:w
12253             \__fp_parse_operand:Nw \c__fp_prec_quest_int
12254             \exp_after:wN \__fp_parse_expand:w
12255         \else:
12256             \exp_after:wN @
12257             \exp_after:wN \use_none:n
12258             \exp_after:wN \__fp_parse_infix_?:N
12259         \fi:
12260     }
12261     \cs_new:Npn \__fp_parse_infix_:N #1
12262     {
12263         \if_int_compare:w #1 < \c__fp_prec_quest_int
12264             \__msg_kernel_expandable_error:nnnn
12265             { kernel } { fp-missing } { ? } { ~for~?: }
12266             \exp_after:wN @
12267             \exp_after:wN \__fp_ternary_auxii:NwwN
12268             \exp:w
12269             \__fp_parse_operand:Nw \c__fp_prec_colon_int
12270             \exp_after:wN \__fp_parse_expand:w
12271         \else:

```

```

12272         \exp_after:wN @
12273         \exp_after:wN \use_none:n
12274         \exp_after:wN \__fp_parse_infix_::N
12275     \fi:
12276 }
12277 \group_end:

```

(End definition for __fp_parse_infix_?:N and __fp_parse_infix_::N.)

23.7.6 Comparisons

```

\__fp_parse_infix_<:N
\__fp_parse_infix_=:N
\__fp_parse_infix_>:N
\__fp_parse_infix_!:N
\__fp_parse_excl_error:
\__fp_parse_compare:NNNNNNN
\__fp_parse_compare_auxi:NNNNNNN
\__fp_parse_compare_auxii:NNNNN
\__fp_parse_compare_end:NNNNw
\__fp_compare:wNNNNw

12278 \cs_new:cpn { \__fp_parse_infix_<:N } #1
12279 { \__fp_parse_compare:NNNNNNN #1 1 0 0 0 0 < }
12280 \cs_new:cpn { \__fp_parse_infix_=:N } #1
12281 { \__fp_parse_compare:NNNNNNN #1 1 0 0 0 0 = }
12282 \cs_new:cpn { \__fp_parse_infix_>:N } #1
12283 { \__fp_parse_compare:NNNNNNN #1 1 0 0 0 0 > }
12284 \cs_new:cpn { \__fp_parse_infix_!:N } #1
12285 {
12286     \exp_after:wN \__fp_parse_compare:NNNNNNN
12287     \exp_after:wN #1
12288     \exp_after:wN 0
12289     \exp_after:wN 1
12290     \exp_after:wN 1
12291     \exp_after:wN 1
12292     \exp_after:wN 1
12293 }
12294 \cs_new:Npn \__fp_parse_excl_error:
12295 {
12296     \__msg_kernel_expandable_error:nnnn
12297     { kernel } { fp-missing } { = } { ~after~!. }
12298 }
12299 \cs_new:Npn \__fp_parse_compare:NNNNNNN #1
12300 {
12301     \if_int_compare:w #1 < \c__fp_prec_comp_int
12302         \exp_after:wN \__fp_parse_compare_auxi:NNNNNNN
12303         \exp_after:wN \__fp_parse_excl_error:
12304     \else:
12305         \exp_after:wN @
12306         \exp_after:wN \use_none:n
12307         \exp_after:wN \__fp_parse_compare:NNNNNNN
12308     \fi:
12309 }
12310 \cs_new:Npn \__fp_parse_compare_auxi:NNNNNNN #1#2#3#4#5#6#7
12311 {
12312     \if_case:w
12313         \if_catcode:w \scan_stop: \exp_not:N #7
12314         4 \exp_stop_f:
12315     \else:
12316         \__int_eval:w '#7 - '< \__int_eval_end:
12317     \fi:
12318     \__fp_parse_compare_auxii:NNNNN #2#2#4#5#6
12319 \or: \__fp_parse_compare_auxii:NNNNN #2#3#2#5#6

```

```

12320     \or: \_fp_parse_compare_auxii:NNNN #2#3#4#2#6
12321     \or: \_fp_parse_compare_auxii:NNNN #2#3#4#5#2
12322     \else: #1 \_fp_parse_compare_end:NNNw #3#4#5#6#7
12323     \fi:
12324 }
12325 \cs_new:Npn \_fp_parse_compare_auxii:NNNN #1#2#3#4#5
12326 {
12327     \exp_after:wN \_fp_parse_compare_auxi:NNNNNN
12328     \exp_after:wN \prg_do_nothing:
12329     \exp_after:wN #1
12330     \exp_after:wN #2
12331     \exp_after:wN #3
12332     \exp_after:wN #4
12333     \exp_after:wN #5
12334     \exp:w \exp_after:wN \_fp_parse_expand:w
12335 }
12336 \cs_new:Npn \_fp_parse_compare_end:NNNw #1#2#3#4#5 \fi:
12337 {
12338     \fi:
12339     \exp_after:wN @
12340     \exp_after:wN \_fp_parse_apply_compare:NwNNNNNwN
12341     \exp_after:wN \c_one_fp
12342     \exp_after:wN #1
12343     \exp_after:wN #2
12344     \exp_after:wN #3
12345     \exp_after:wN #4
12346     \exp:w
12347     \_fp_parse_operand:Nw \c__fp_prec_comp_int \_fp_parse_expand:w #5
12348 }
12349 \cs_new:Npn \_fp_parse_apply_compare:NwNNNNNwN
12350     #1 #2@ #3 #4#5#6#7 #8@ #9
12351 {
12352     \if_int_odd:w
12353         \if_meaning:w \c_zero_fp #3
12354         0
12355     \else:
12356         \if_case:w \_fp_compare_back:ww #8 #2 \exp_stop_f:
12357             #5 \or: #6 \or: #7 \else: #4
12358         \fi:
12359     \fi:
12360     \exp_stop_f:
12361     \exp_after:wN \_fp_parse_apply_compare_aux:NNwN
12362     \exp_after:wN \c_one_fp
12363 \else:
12364     \exp_after:wN \_fp_parse_apply_compare_aux:NNwN
12365     \exp_after:wN \c_zero_fp
12366 \fi:
12367 #1 #8 #9
12368 }
12369 \cs_new:Npn \_fp_parse_apply_compare_aux:NNwN #1 #2 #3; #4
12370 {
12371     \if_meaning:w \_fp_parse_compare:NNNNNN #4
12372     \exp_after:wN \_fp_parse_continue_compare:NNwNN
12373     \exp_after:wN #1

```



```

12374     \exp_after:wN #2
12375     \exp:w \exp_end_continue_f:w
12376     \_fp_exp_after_o:w #3;
12377     \exp:w \exp_end_continue_f:w
12378   \else:
12379     \exp_after:wN \_fp_parse_continue:NwN
12380     \exp_after:wN #2
12381     \exp:w \exp_end_continue_f:w
12382     \exp_after:wN #1
12383     \exp:w \exp_end_continue_f:w
12384   \fi:
12385   #4 #2
12386 }
12387 \cs_new:Npn \_fp_parse_compare:NNwNN #1#2 #3@ #4#5
12388 { #4 #2 #3@ #1 }

```

(End definition for `_fp_parse_infix_<:N` and others.)

23.8 Candidate: defining new `l3fp` functions

`\fp_function:Nw` Parse the argument of the function `#1` using `_fp_parse_operand:Nw` with a precedence of 16, and pass the function and argument to `_fp_function_apply:nw`.

```

12389 \cs_new:Npn \fp_function:Nw #1
12390 {
12391   \exp_after:wN \_fp_function_apply:nw
12392   \exp_after:wN #1
12393   \exp:w
12394     \_fp_parse_operand:Nw \c__fp_prec_funcii_int \_fp_parse_expand:w
12395 }

```

(End definition for `\fp_function:Nw`.)

`\fp_new_function:Npn` Save the code provided by the user in the control sequence `_fp_user_#1`. Define `_fp_new_function:NNnnn` `#1` to call `_fp_function_apply:nw` after parsing one operand using `_fp_parse_operand:Nw` with precedence 16. The auxiliary `_fp_function_args:Nwn` receives the user function and the number of arguments (half of the number of tokens in the parameter text `#2`), followed by the operand (as a token list of floating points). It checks the number of arguments, and applies the user function to the arguments (without the outer brace group).

```

12396 \cs_new_protected:Npn \fp_new_function:Npn #1#2#
12397 {
12398   \_fp_new_function:Ncfnn #1
12399   { \_fp_user_ \cs_to_str:N #1 }
12400   { \int_eval:n { \tl_count:n {#2} / 2 } }
12401   {#2}
12402 }
12403 \cs_new_protected:Npn \_fp_new_function:NNnnn #1#2#3#4#5
12404 {
12405   \cs_new:Npn #1
12406   {
12407     \exp_after:wN \_fp_function_apply:nw \exp_after:wN
12408     {
12409       \exp_after:wN \_fp_function_args:Nwn
12410       \exp_after:wN #2

```

```

12411         \__int_value:w #3 \exp_after:wN ; \exp_after:wN
12412     }
12413     \exp:w
12414     \__fp_parse_operand:Nw \c__fp_prec_funcii_int \__fp_parse_expand:w
12415 }
12416 \cs_new:Npn #2 #4 {#5}
12417 }
12418 \cs_generate_variant:Nn \__fp_new_function:NNnnn { Ncf }
12419 \cs_new:Npn \__fp_function_args:Nwn #1#2; #3
12420 {
12421     \int_compare:nNnTF { \tl_count:n {#3} } = {#2}
12422     { #1 #3 }
12423     {
12424         \_msg_kernel_expandable_error:nnnnn
12425         { kernel } { fp-num-args } { #1() } {#2} {#2}
12426         \c_nan_fp
12427     }
12428 }

```

(End definition for `\fp_new_function:Npn`, `__fp_new_function:NNnnn`, and `__fp_function_args:Nwn`.)

```

\__fp_function_apply:nw
\__fp_function_store:wwNwnn
\__fp_function_store_end:wnnn

```

The auxiliary `__fp_function_apply:nw` is called after parsing an operand, so it receives some code `#1`, then the operand ending with `@`, then a function such as `__fp_parse_infix_+:N` (but not always of this form, see comparisons for instance). Package the operand (an array) into a token list with floating point items: this is the role of `__fp_function_store:wwNwnn` and `__fp_function_store_end:wnnn`. Then apply `__fp_parse:n` to the code `#1` followed by a brace group with this token list. This results in a floating point result, which will correctly be parsed as the next operand of whatever was looking for one. The trailing `\s__fp_mark` is used as a special infix operator to indicate that the next token has already gone through `__fp_parse_infix:NN`.

```

12429 \cs_new:Npn \__fp_function_apply:nw #1#2 @
12430 {
12431     \__fp_parse:n
12432     {
12433         \__fp_function_store:wwNwnn #2
12434         \s__fp_mark \__fp_function_store:wwNwnn ;
12435         \s__fp_mark \__fp_function_store_end:wnnn
12436         \s__fp_stop { } { } {#1}
12437     }
12438     \s__fp_mark
12439 }
12440 \cs_new:Npn \__fp_function_store:wwNwnn
12441     #1; #2 \s__fp_mark #3#4 \s__fp_stop #5#6
12442     { #3 #2 \s__fp_mark #3#4 \s__fp_stop { #5 #6 } { { #1; } } }
12443 \cs_new:Npn \__fp_function_store_end:wnnn
12444     #1 \s__fp_stop #2#3#4
12445     { #4 {#2} }

```

(End definition for `__fp_function_apply:nw`, `__fp_function_store:wwNwnn`, and `__fp_function_store_end:wnnn`.)

23.9 Messages

```

12446 \_msg_kernel_new:nnn { kernel } { unknown-fp-word }

```

```

12447 { Unknown~fp~word~#1. }
12448 \__msg_kernel_new:nnn { kernel } { fp-missing }
12449 { Missing~#1~inserted #2. }
12450 \__msg_kernel_new:nnn { kernel } { fp-extra }
12451 { Extra~#1~ignored. }
12452 \__msg_kernel_new:nnn { kernel } { fp-early-end }
12453 { Premature~end~in~fp~expression. }
12454 \__msg_kernel_new:nnn { kernel } { fp-after-e }
12455 { Cannot~use~#1 after~'e'. }
12456 \__msg_kernel_new:nnn { kernel } { fp-missing-number }
12457 { Missing-number~before~'#1'. }
12458 \__msg_kernel_new:nnn { kernel } { fp-unknown-symbol }
12459 { Unknown~symbol~#1~ignored. }
12460 \__msg_kernel_new:nnn { kernel } { fp-extra-comma }
12461 { Unexpected~comma:~extra~arguments~ignored. }
12462 \__msg_kernel_new:nnn { kernel } { fp-num-args }
12463 { #1~expects~between~#2~and~#3~arguments. }
12464 <*package>
12465 \cs_if_exist:cT { @unexpandable@protect }
12466 {
12467   \__msg_kernel_new:nnn { kernel } { fp-robust-cmd }
12468   { Robust~command~#1 invalid~in~fp~expression! }
12469 }
12470 </package>
12471 </initex | package>

```

24 l3fp-logic Implementation

```

12472 <*initex | package>
12473 <@@=fp>

```

24.1 Syntax of internal functions

- __fp_compare_npos:nwnw {<exp_{o1}>} <body₁> ; {<exp_{o2}>} <body₂> ;
- __fp_minmax_o:Nw <sign> <floating point array>
- __fp_not_o:w ? <floating point array> (with one floating point number only)
- __fp_&_o:ww <floating point> <floating point>
- __fp_|_o:ww <floating point> <floating point>
- __fp_ternary:NwwN, __fp_ternary_auxi:NwwN, __fp_ternary_auxii:NwwN have to be understood.

24.2 Existence test

\fp_if_exist_p:N Copies of the cs functions defined in l3basics.

```

\fp_if_exist_p:c 12474 \prg_new_eq_conditional:NNn \fp_if_exist:N \cs_if_exist:N { TF , T , F , p }
\fp_if_exist:NTF 12475 \prg_new_eq_conditional:NNn \fp_if_exist:c \cs_if_exist:c { TF , T , F , p }
\fp_if_exist:cTF

```

(End definition for \fp_if_exist:N~~TF~~. This function is documented on page 175.)

24.3 Comparison

`\fp_compare_p:n` Within floating point expressions, comparison operators are treated as operations, so we evaluate #1, then compare with 0.

`\fp_compare:nTF`

```
\__fp_compare_return:w
12476 \prg_new_conditional:Npnn \fp_compare:n #1 { p , T , F , TF }
12477 {
12478   \exp_after:wN \__fp_compare_return:w
12479   \exp:w \exp_end_continue_f:w \__fp_parse:n {#1}
12480 }
12481 \cs_new:Npn \__fp_compare_return:w \s__fp \__fp_chk:w #1#2;
12482 {
12483   \if_meaning:w 0 #1
12484   \prg_return_false:
12485   \else:
12486   \prg_return_true:
12487   \fi:
12488 }
```

(End definition for `\fp_compare:nTF` and `__fp_compare_return:w`. These functions are documented on page 176.)

`\fp_compare_p:nNn`

`\fp_compare:nNnTF`

`__fp_compare_aux:wn`

Evaluate #1 and #3, using an auxiliary to expand both, and feed the two floating point numbers swapped to `__fp_compare_back:ww`, defined below. Compare the result with ‘#2-‘=, which is -1 for $<$, 0 for $=$, 1 for $>$ and 2 for $?$.

```
12489 \prg_new_conditional:Npnn \fp_compare:nNn #1#2#3 { p , T , F , TF }
12490 {
12491   \if_int_compare:w
12492     \exp_after:wN \__fp_compare_aux:wn
12493     \exp:w \exp_end_continue_f:w \__fp_parse:n {#1} {#3}
12494     = \__int_eval:w ‘#2 - ‘= \__int_eval_end:
12495     \prg_return_true:
12496   \else:
12497     \prg_return_false:
12498   \fi:
12499 }
12500 \cs_new:Npn \__fp_compare_aux:wn #1; #2
12501 {
12502   \exp_after:wN \__fp_compare_back:ww
12503   \exp:w \exp_end_continue_f:w \__fp_parse:n {#2} #1;
12504 }
```

(End definition for `\fp_compare:nNnTF` and `__fp_compare_aux:wn`. These functions are documented on page 176.)

`__fp_compare_back:ww`
`__fp_compare_nan:w`

`__fp_compare_back:ww` $\langle y \rangle$; $\langle x \rangle$;

Expands (in the same way as `\int_eval:n`) to -1 if $x < y$, 0 if $x = y$, 1 if $x > y$, and 2 otherwise (denoted as $x?y$). If either operand is `nan`, stop the comparison with `__fp_compare_nan:w` returning 2 . If x is negative, swap the outputs 1 and -1 (i.e., $>$ and $<$); we can henceforth assume that $x \geq 0$. If $y \geq 0$, and they have the same type, either they are normal and we compare them with `__fp_compare_npos:nwnw`, or they are equal. If $y \geq 0$, but of a different type, the highest type is a larger number. Finally, if $y \leq 0$, then $x > y$, unless both are zero.

```
12505 \cs_new:Npn \__fp_compare_back:ww
12506   \s__fp \__fp_chk:w #1 #2 #3;
```

```

12507 \s__fp \__fp_chk:w #4 #5 #6;
12508 {
12509 \__int_value:w
12510 \if_meaning:w 3 #1 \exp_after:wN \__fp_compare_nan:w \fi:
12511 \if_meaning:w 3 #4 \exp_after:wN \__fp_compare_nan:w \fi:
12512 \if_meaning:w 2 #5 - \fi:
12513 \if_meaning:w #2 #5
12514 \if_meaning:w #1 #4
12515 \if_meaning:w 1 #1
12516 \__fp_compare_npos:nwnw #6; #3;
12517 \else:
12518 0
12519 \fi:
12520 \else:
12521 \if_int_compare:w #4 < #1 - \fi: 1
12522 \fi:
12523 \else:
12524 \if_int_compare:w #1#4 = 0 \exp_stop_f:
12525 0
12526 \else:
12527 1
12528 \fi:
12529 \fi:
12530 \exp_stop_f:
12531 }
12532 \cs_new:Npn \__fp_compare_nan:w #1 \fi: \exp_stop_f: { 2 \exp_stop_f: }

```

(End definition for __fp_compare_back:ww and __fp_compare_nan:w.)

__fp_compare_npos:nwnw
__fp_compare_significand:nnnnnnnn

__fp_compare_npos:nwnw { $\langle expo_1 \rangle$ } $\langle body_1 \rangle$; { $\langle expo_2 \rangle$ } $\langle body_2 \rangle$;

Within an __int_value:w ... \exp_stop_f: construction, this expands to 0 if the two numbers are equal, -1 if the first is smaller, and 1 if the first is bigger. First compare the exponents: the larger one denotes the larger number. If they are equal, we must compare significands. If both the first 8 digits and the next 8 digits coincide, the numbers are equal. If only the first 8 digits coincide, the next 8 decide. Otherwise, the first 8 digits are compared.

```

12533 \cs_new:Npn \__fp_compare_npos:nwnw #1#2; #3#4;
12534 {
12535 \if_int_compare:w #1 = #3 \exp_stop_f:
12536 \__fp_compare_significand:nnnnnnnn #2 #4
12537 \else:
12538 \if_int_compare:w #1 < #3 - \fi: 1
12539 \fi:
12540 }
12541 \cs_new:Npn \__fp_compare_significand:nnnnnnnn #1#2#3#4#5#6#7#8
12542 {
12543 \if_int_compare:w #1#2 = #5#6 \exp_stop_f:
12544 \if_int_compare:w #3#4 = #7#8 \exp_stop_f:
12545 0
12546 \else:
12547 \if_int_compare:w #3#4 < #7#8 - \fi: 1
12548 \fi:
12549 \else:
12550 \if_int_compare:w #1#2 < #5#6 - \fi: 1

```

```

12551     \fi:
12552   }

```

(End definition for `_fp_compare_npos:nwnw` and `_fp_compare_significand:nnnnnnnn`.)

24.4 Floating point expression loops

`\fp_do_until:nn` These are quite easy given the above functions. The `do_until` and `do_while` versions execute the body, then test. The `until_do` and `while_do` do it the other way round.

```

\fp_do_while:nn
\fp_until_do:nn
\fp_while_do:nn
12553 \cs_new:Npn \fp_do_until:nn #1#2
12554 {
12555   #2
12556   \fp_compare:nF {#1}
12557   { \fp_do_until:nn {#1} {#2} }
12558 }
12559 \cs_new:Npn \fp_do_while:nn #1#2
12560 {
12561   #2
12562   \fp_compare:nT {#1}
12563   { \fp_do_while:nn {#1} {#2} }
12564 }
12565 \cs_new:Npn \fp_until_do:nn #1#2
12566 {
12567   \fp_compare:nF {#1}
12568   {
12569     #2
12570     \fp_until_do:nn {#1} {#2}
12571   }
12572 }
12573 \cs_new:Npn \fp_while_do:nn #1#2
12574 {
12575   \fp_compare:nT {#1}
12576   {
12577     #2
12578     \fp_while_do:nn {#1} {#2}
12579   }
12580 }

```

(End definition for `\fp_do_until:nn` and others. These functions are documented on page 177.)

`\fp_do_until:nNnn` As above but not using the `nNn` syntax.

```

\fp_do_while:nNnn
\fp_until_do:nNnn
\fp_while_do:nNnn
12581 \cs_new:Npn \fp_do_until:nNnn #1#2#3#4
12582 {
12583   #4
12584   \fp_compare:nNnF {#1} #2 {#3}
12585   { \fp_do_until:nNnn {#1} #2 {#3} {#4} }
12586 }
12587 \cs_new:Npn \fp_do_while:nNnn #1#2#3#4
12588 {
12589   #4
12590   \fp_compare:nNnT {#1} #2 {#3}
12591   { \fp_do_while:nNnn {#1} #2 {#3} {#4} }
12592 }
12593 \cs_new:Npn \fp_until_do:nNnn #1#2#3#4

```

```

12594 {
12595   \fp_compare:nNnF {#1} #2 {#3}
12596   {
12597     #4
12598     \fp_until_do:nNnn {#1} #2 {#3} {#4}
12599   }
12600 }
12601 \cs_new:Npn \fp_while_do:nNnn #1#2#3#4
12602 {
12603   \fp_compare:nNnT {#1} #2 {#3}
12604   {
12605     #4
12606     \fp_while_do:nNnn {#1} #2 {#3} {#4}
12607   }
12608 }

```

(End definition for `\fp_do_until:nNnn` and others. These functions are documented on page 177.)

```

\fp_step_function:nnnN
\fp_step_function:nnnc
  \__fp_step:wwwN
  \__fp_step:NnnnnN
  \__fp_step:NfnnnnN

```

The approach here is somewhat similar to `\int_step_function:nnnN`. There are two subtleties: we use the internal parser `__fp_parse:n` to avoid converting back and forth from the internal representation; and (due to rounding) even a non-zero step does not guarantee that the loop counter will increase.

```

12609 \cs_new:Npn \fp_step_function:nnnN #1#2#3
12610 {
12611   \exp_after:wN \__fp_step:wwwN
12612   \exp:w \exp_end_continue_f:w \__fp_parse_o:n {#1}
12613   \exp:w \exp_end_continue_f:w \__fp_parse_o:n {#2}
12614   \exp:w \exp_end_continue_f:w \__fp_parse:n {#3}
12615 }
12616 \cs_generate_variant:Nn \fp_step_function:nnnN { nnc }
12617 % \end{macrocode}
12618 % Only \enquote{normal} floating points (not $\pm 0$,
12619 % $\pm\texttt{\texttt{inf}}$, \texttt{nan}) can be used as step; if positive,
12620 % call \cs{__fp_step:NnnnnN} with argument |>| otherwise~|<|. This
12621 % function has one more argument than its integer counterpart, namely
12622 % the previous value, to catch the case where the loop has made no
12623 % progress. Conversion to decimal is done just before calling the
12624 % user's function.
12625 % \begin{macrocode}
12626 \cs_new:Npn \__fp_step:wwwN #1 ; \s__fp \__fp_chk:w #2#3#4 ; #5; #6
12627 {
12628   \token_if_eq_meaning:NNTF #2 1
12629   {
12630     \token_if_eq_meaning:NNTF #3 0
12631     { \__fp_step:NnnnnN > }
12632     { \__fp_step:NnnnnN < }
12633   }
12634   {
12635     \token_if_eq_meaning:NNTF #2 0
12636     { \__msg_kernel_expandable_error:nnn { kernel } { zero-step } {#6} }
12637     {
12638       \__fp_error:nnfn { bad-step } { }
12639       { \fp_to_tl:n { \s__fp \__fp_chk:w #2#3#4 ; } } {#6}
12640     }

```

```

12641         \use_none:nnnnn
12642     }
12643     { #1 ; } { \c_nan_fp } { \s__fp \__fp_chk:w #2#3#4 ; } { #5 ; } #6
12644 }
12645 \cs_new:Npn \__fp_step:NnnnnN #1#2#3#4#5#6
12646 {
12647     \fp_compare:nNnTF {#2} = {#3}
12648     {
12649         \__fp_error:nffn { tiny-step }
12650         { \fp_to_tl:n {#3} } { \fp_to_tl:n {#4} } {#6}
12651     }
12652     {
12653         \fp_compare:nNnF {#2} #1 {#5}
12654         {
12655             \exp_args:Nf #6 { \__fp_to_decimal_dispatch:w #2 }
12656             \__fp_step:NfnnnN
12657             #1 { \__fp_parse:n { #2 + #4 } } {#2} {#4} {#5} #6
12658         }
12659     }
12660 }
12661 \cs_generate_variant:Nn \__fp_step:NnnnnN { Nf }

```

(End definition for `\fp_step_function:nnnN`, `__fp_step:wwwN`, and `__fp_step:NnnnnN`. These functions are documented on page 178.)

\fp_step_inline:nnnn As for `\int_step_inline:nnnn`, create a global function and apply it, following up with a break point.

```

12662 \cs_new_protected:Npn \fp_step_inline:nnnn #1#2#3#4
12663 {
12664     \int_gincr:N \g__prg_map_int
12665     \cs_gset_protected:cpn { __prg_map_ \int_use:N \g__prg_map_int :w }
12666     ##1 {#4}
12667     \fp_step_function:nnnc {#1} {#2} {#3}
12668     { __prg_map_ \int_use:N \g__prg_map_int :w }
12669     \__prg_break_point:Nn \scan_stop: { \int_gdecr:N \g__prg_map_int }
12670 }

```

(End definition for `\fp_step_inline:nnnn`. This function is documented on page 178.)

```

12671 \__msg_kernel_new:nnn { kernel } { fp-bad-step }
12672 { Invalid-step-size-#2~in-step-function-#3. }
12673 \__msg_kernel_new:nnn { kernel } { fp-tiny-step }
12674 { Tiny-step-size-(#1+#2=#1)~in-step-function-#3. }

```

24.5 Extrema

__fp_minmax_o:Nw The argument `#1` is 2 to find the maximum of an array `#2` of floating point numbers, and 0 to find the minimum. We read numbers sequentially, keeping track of the largest (smallest) number found so far. If numbers are equal (for instance ± 0), the first is kept. We append $-\infty$ (∞), for the case of an empty array, currently impossible. Since no number is smaller (larger) than that, it will never alter the maximum (minimum). The weird fp-like trailing marker breaks the loop correctly: see the precise definition of `__fp_minmax_loop:Nww`.

```

12675 \cs_new:Npn \__fp_minmax_o:Nw #1#2 @

```



```

12676 {
12677   \if_meaning:w 0 #1
12678   \exp_after:wN \__fp_minmax_loop:Nww \exp_after:wN +
12679   \else:
12680   \exp_after:wN \__fp_minmax_loop:Nww \exp_after:wN -
12681   \fi:
12682   #2
12683   \s__fp \__fp_chk:w 2 #1 \s__fp_exact ;
12684   \s__fp \__fp_chk:w { 3 \__fp_minmax_break_o:w } ;
12685 }

```

(End definition for __fp_minmax_o:Nw.)

__fp_minmax_loop:Nww The first argument is $-$ or $+$ to denote the case where the currently largest (smallest) number found (first floating point argument) should be replaced by the new number (second floating point argument). If the new number is `nan`, keep that as the extremum, unless that extremum is already a `nan`. Otherwise, compare the two numbers. If the new number is larger (in the case of `max`) or smaller (in the case of `min`), the test yields `true`, and we keep the second number as a new maximum; otherwise we keep the first number. Then loop.

```

12686 \cs_new:Npn \__fp_minmax_loop:Nww
12687   #1 \s__fp \__fp_chk:w #2#3; \s__fp \__fp_chk:w #4#5;
12688 {
12689   \if_meaning:w 3 #4
12690   \if_meaning:w 3 #2
12691   \__fp_minmax_auxi:ww
12692   \else:
12693   \__fp_minmax_auxii:ww
12694   \fi:
12695   \else:
12696   \if_int_compare:w
12697     \__fp_compare_back:ww
12698     \s__fp \__fp_chk:w #4#5;
12699     \s__fp \__fp_chk:w #2#3;
12700     = #1 1 \exp_stop_f:
12701     \__fp_minmax_auxii:ww
12702   \else:
12703   \__fp_minmax_auxi:ww
12704   \fi:
12705   \fi:
12706   \__fp_minmax_loop:Nww #1
12707   \s__fp \__fp_chk:w #2#3;
12708   \s__fp \__fp_chk:w #4#5;
12709 }

```

(End definition for __fp_minmax_loop:Nww.)

__fp_minmax_auxi:ww Keep the first/second number, and remove the other.
 __fp_minmax_auxii:ww

```

12710 \cs_new:Npn \__fp_minmax_auxi:ww #1 \fi: \fi: #2 \s__fp #3 ; \s__fp #4;
12711 { \fi: \fi: #2 \s__fp #3 ; }
12712 \cs_new:Npn \__fp_minmax_auxii:ww #1 \fi: \fi: #2 \s__fp #3 ;
12713 { \fi: \fi: #2 }

```

(End definition for __fp_minmax_auxi:ww and __fp_minmax_auxii:ww.)

`__fp_minmax_break_o:w` This function is called from within an `\if_meaning:w` test. Skip to the end of the tests, close the current test with `\fi:`, clean up, and return the appropriate number with one post-expansion.

```
12714 \cs_new:Npn \__fp_minmax_break_o:w #1 \fi: \fi: #2 \s__fp #3; #4;
12715 { \fi: \__fp_exp_after_o:w \s__fp #3; }
```

(End definition for `__fp_minmax_break_o:w`.)

24.6 Boolean operations

`__fp_not_o:w` Return true or false, with two expansions, one to exit the conditional, and one to please `l3fp-parse`. The first argument is provided by `l3fp-parse` and is ignored.

```
12716 \cs_new:cpn { __fp_not_o:w } #1 \s__fp \__fp_chk:w #2#3; @
12717 {
12718   \if_meaning:w 0 #2
12719     \exp_after:wN \exp_after:wN \exp_after:wN \c_one_fp
12720   \else:
12721     \exp_after:wN \exp_after:wN \exp_after:wN \c_zero_fp
12722   \fi:
12723 }
```

(End definition for `__fp_not_o:w`.)

`__fp_&o:ww` For `and`, if the first number is zero, return it (with the same sign). Otherwise, return
`__fp_|o:ww` the second one. For `or`, the logic is reversed: if the first number is non-zero, return
`__fp_and_return:wNw` it, otherwise return the second number: we achieve that by hi-jacking `__fp_&o:ww`, inserting an extra argument, `\else:`, before `\s__fp`. In all cases, expand after the floating point number.

```
12724 \group_begin:
12725   \char_set_catcode_letter:N &
12726   \char_set_catcode_letter:N |
12727   \cs_new:Npn \__fp_&o:ww #1 \s__fp \__fp_chk:w #2#3;
12728   {
12729     \if_meaning:w 0 #2 #1
12730       \__fp_and_return:wNw \s__fp \__fp_chk:w #2#3;
12731     \fi:
12732     \__fp_exp_after_o:w
12733   }
12734   \cs_new:Npn \__fp_|o:ww { \__fp_&o:ww \else: }
12735 \group_end:
12736 \cs_new:Npn \__fp_and_return:wNw #1; \fi: #2#3; { \fi: #2 #1; }
```

(End definition for `__fp_&o:ww`, `__fp_|o:ww`, and `__fp_and_return:wNw`.)

24.7 Ternary operator

`__fp_ternary:NwN` The first function receives the test and the true branch of the `?:` ternary operator. It
`__fp_ternary_auxi:NwN` returns the true branch, unless the test branch is zero. In that case, the function returns
`__fp_ternary_auxii:NwN` a very specific nan. The second function receives the output of the first function, and the
`__fp_ternary_loop_break:w` false branch. It returns the previous input, unless that is the special nan, in which case
`__fp_ternary_loop:Nw` we return the false branch.

```
\__fp_ternary_map_break: 12737 \cs_new:Npn \__fp_ternary:NwN #1 #2@ #3@ #4
__fp_ternary_break_point:n 12738 {
```

```

12739 \if_meaning:w \__fp_parse_infix_:N #4
12740 \__fp_ternary_loop:Nw
12741 #2
12742 \s__fp \__fp_chk:w { \__fp_ternary_loop_break:w } ;
12743 \__fp_ternary_break_point:n { \exp_after:wN \__fp_ternary_auxi:NwwN }
12744 \exp_after:wN #1
12745 \exp:w \exp_end_continue_f:w
12746 \__fp_exp_after_array_f:w #3 \s__fp_stop
12747 \exp_after:wN @
12748 \exp:w
12749 \__fp_parse_operand:Nw \c__fp_prec_colon_int
12750 \__fp_parse_expand:w
12751 \else:
12752 \__msg_kernel_expandable_error:nnnn
12753 { kernel } { fp-missing } { : } { ~for~?: }
12754 \exp_after:wN \__fp_parse_continue:NwN
12755 \exp_after:wN #1
12756 \exp:w \exp_end_continue_f:w
12757 \__fp_exp_after_array_f:w #3 \s__fp_stop
12758 \exp_after:wN #4
12759 \exp_after:wN #1
12760 \fi:
12761 }
12762 \cs_new:Npn \__fp_ternary_loop_break:w
12763 #1 \fi: #2 \__fp_ternary_break_point:n #3
12764 {
12765 0 = 0 \exp_stop_f: \fi:
12766 \exp_after:wN \__fp_ternary_auxii:NwwN
12767 }
12768 \cs_new:Npn \__fp_ternary_loop:Nw \s__fp \__fp_chk:w #1#2;
12769 {
12770 \if_int_compare:w #1 > 0 \exp_stop_f:
12771 \exp_after:wN \__fp_ternary_map_break:
12772 \fi:
12773 \__fp_ternary_loop:Nw
12774 }
12775 \cs_new:Npn \__fp_ternary_map_break: #1 \__fp_ternary_break_point:n #2 {#2}
12776 \cs_new:Npn \__fp_ternary_auxi:NwwN #1#2@#3@#4
12777 {
12778 \exp_after:wN \__fp_parse_continue:NwN
12779 \exp_after:wN #1
12780 \exp:w \exp_end_continue_f:w
12781 \__fp_exp_after_array_f:w #2 \s__fp_stop
12782 #4 #1
12783 }
12784 \cs_new:Npn \__fp_ternary_auxii:NwwN #1#2@#3@#4
12785 {
12786 \exp_after:wN \__fp_parse_continue:NwN
12787 \exp_after:wN #1
12788 \exp:w \exp_end_continue_f:w
12789 \__fp_exp_after_array_f:w #3 \s__fp_stop
12790 #4 #1
12791 }

```

(End definition for `_fp_ternary:NwwN` and others.)

12792 \langle /initex | package \rangle

25 13fp-basics Implementation

12793 \langle *initex | package \rangle

12794 \langle @@=fp \rangle

The 13fp-basics module implements addition, subtraction, multiplication, and division of two floating points, and the absolute value and sign-changing operations on one floating point. All operations implemented in this module yield the outcome of rounding the infinitely precise result of the operation to the nearest floating point.

Some algorithms used below end up being quite similar to some described in “What Every Computer Scientist Should Know About Floating Point Arithmetic”, by David Goldberg, which can be found at <http://cr.yp.to/2005-590/goldberg.pdf>.

25.1 Common to several operations

`_fp_basics_pack_low:NNNNw` Addition and multiplication of significands are done in two steps: first compute a (more or less) exact result, then round and pack digits in the final (braced) form. These functions take care of the packing, with special attention given to the case where rounding has caused a carry. Since rounding can only shift the final digit by 1, a carry always produces an exact power of 10. Thus, `_fp_basics_pack_high_carry:w` is always followed by four times {0000}.

```
12795 \cs_new:Npn \_fp_basics_pack_low:NNNNw #1 #2#3#4#5 #6;
12796 { + #1 - 1 ; {#2#3#4#5} {#6} ; }
12797 \cs_new:Npn \_fp_basics_pack_high:NNNNw #1 #2#3#4#5 #6;
12798 {
12799   \if_meaning:w 2 #1
12800     \_fp_basics_pack_high_carry:w
12801   \fi:
12802   ; {#2#3#4#5} {#6}
12803 }
12804 \cs_new:Npn \_fp_basics_pack_high_carry:w \fi: ; #1
12805 { \fi: + 1 ; {1000} }
```

(End definition for `_fp_basics_pack_low:NNNNw`, `_fp_basics_pack_high:NNNNw`, and `_fp_basics_pack_high_carry:w`.)

`_fp_basics_pack_weird_low:NNNNw` I don’t fully understand those functions, used for additions and divisions. Hence the name.
`_fp_basics_pack_weird_high:NNNNNNNw`

```
12806 \cs_new:Npn \_fp_basics_pack_weird_low:NNNNw #1 #2#3#4 #5;
12807 {
12808   \if_meaning:w 2 #1
12809     + 1
12810   \fi:
12811   \_int_eval_end:
12812   #2#3#4; {#5} ;
12813 }
12814 \cs_new:Npn \_fp_basics_pack_weird_high:NNNNNNNw
12815 1 #1#2#3#4 #5#6#7#8 #9; { ; {#1#2#3#4} {#5#6#7#8} {#9} }
```

(End definition for `_fp_basics_pack_weird_low:NNNNw` and `_fp_basics_pack_weird_high:NNNNNNNw`.)

25.2 Addition and subtraction

We define here two functions, `__fp_-_o:ww` and `__fp+_o:ww`, which perform the subtraction and addition of their two floating point operands, and expand the tokens following the result once.

A more obscure function, `__fp_add_big_i_o:wNww`, is used in `l3fp-exo`.

The logic goes as follows:

- `__fp_-_o:ww` calls `__fp+_o:ww` to do the work, with the sign of the second operand flipped;
- `__fp+_o:ww` dispatches depending on the type of floating point, calling specialized auxiliaries;
- in all cases except summing two normal floating point numbers, we return one or the other operands depending on the signs, or detect an invalid operation in the case of $\infty - \infty$;
- for normal floating point numbers, compare the signs;
- to add two floating point numbers of the same sign or of opposite signs, shift the significand of the smaller one to match the bigger one, perform the addition or subtraction of significands, check for a carry, round, and pack using the `__fp_basics_pack_...` functions.

The trickiest part is to round correctly when adding or subtracting normal floating point numbers.

25.2.1 Sign, exponent, and special numbers

`__fp_-_o:ww` A previous version of this function grabbed its two operands, changed the sign of the second, and called `__fp+_o:ww`. However, for efficiency reasons, the operands were swapped in the process, which means that error messages ended up wrong. Now, the `__fp+_o:ww` auxiliary has a hook: it takes one argument between the first `\s__fp` and `__fp_chk:w`, which is applied to the sign of the second operand. Positioning the hook there means that `__fp+_o:ww` can still check that it was followed by `\s__fp` and not arbitrary junk.

```

12816 \cs_new:cpx { __fp_-_o:ww } \s__fp
12817 {
12818   \exp_not:c { __fp+_o:ww }
12819   \exp_not:n { \s__fp \__fp_neg_sign:N }
12820 }

```

(End definition for `__fp_-_o:ww`.)

`__fp+_o:ww` This function is either called directly with an empty `#1` to compute an addition, or it is called by `__fp_-_o:ww` with `__fp_neg_sign:N` as `#1` to compute a subtraction (equivalent to changing the $\langle sign_2 \rangle$ of the second operand). If the $\langle types \rangle$ `#2` and `#4` are the same, dispatch to case `#2` (0, 1, 2, or 3), where we call specialized functions: thanks to `__int_value:w`, those receive the tweaked $\langle sign_2 \rangle$ (expansion of `#1#5`) as an argument. If the $\langle types \rangle$ are distinct, the result is simply the floating point number with the highest $\langle type \rangle$. Since case 3 (used for two `nan`) also picks the first operand, we can also use it

when $\langle type_1 \rangle$ is greater than $\langle type_2 \rangle$. Also note that we don't need to worry about $\langle sign_2 \rangle$ in that case since the second operand is discarded.

```

12821 \cs_new:cpn { __fp+_o:ww }
12822   \s__fp #1 \__fp_chk:w #2 #3 ; \s__fp \__fp_chk:w #4 #5
12823   {
12824     \if_case:w
12825       \if_meaning:w #2 #4
12826       #2
12827     \else:
12828       \if_int_compare:w #2 > #4 \exp_stop_f:
12829       3
12830     \else:
12831       4
12832     \fi:
12833     \fi:
12834     \exp_stop_f:
12835       \exp_after:wN \__fp_add_zeros_o:Nww \__int_value:w
12836   \or:   \exp_after:wN \__fp_add_normal_o:Nww \__int_value:w
12837   \or:   \exp_after:wN \__fp_add_inf_o:Nww \__int_value:w
12838   \or:   \__fp_case_return_i_o:ww
12839   \else: \exp_after:wN \__fp_add_return_ii_o:Nww \__int_value:w
12840   \fi:
12841   #1 #5
12842   \s__fp \__fp_chk:w #2 #3 ;
12843   \s__fp \__fp_chk:w #4 #5
12844   }

```

(End definition for `__fp+_o:ww`.)

`__fp_add_return_ii_o:Nww` Ignore the first operand, and return the second, but using the sign #1 rather than #4. As usual, expand after the floating point.

```

12845 \cs_new:Npn \__fp_add_return_ii_o:Nww #1 #2 ; \s__fp \__fp_chk:w #3 #4
12846   { \__fp_exp_after_o:w \s__fp \__fp_chk:w #3 #1 }

```

(End definition for `__fp_add_return_ii_o:Nww`.)

`__fp_add_zeros_o:Nww` Adding two zeros yields `\c_zero_fp`, except if both zeros were -0 .

```

12847 \cs_new:Npn \__fp_add_zeros_o:Nww #1 \s__fp \__fp_chk:w 0 #2
12848   {
12849     \if_int_compare:w #2 #1 = 20 \exp_stop_f:
12850     \exp_after:wN \__fp_add_return_ii_o:Nww
12851   \else:
12852     \__fp_case_return_i_o:ww
12853   \fi:
12854   #1
12855   \s__fp \__fp_chk:w 0 #2
12856   }

```

(End definition for `__fp_add_zeros_o:Nww`.)

`__fp_add_inf_o:Nww` If both infinities have the same sign, just return that infinity, otherwise, it is an invalid operation. We find out if that invalid operation is an addition or a subtraction by testing whether the tweaked $\langle sign_2 \rangle$ (#1) and the $\langle sign_2 \rangle$ (#4) are identical.

```

12857 \cs_new:Npn \__fp_add_inf_o:Nww

```

```

12858     #1 \s__fp \__fp_chk:w 2 #2 #3; \s__fp \__fp_chk:w 2 #4
12859   {
12860     \if_meaning:w #1 #2
12861       \__fp_case_return_i_o:ww
12862     \else:
12863       \__fp_case_use:nw
12864       {
12865         \if_meaning:w #1 #4
12866         \exp_after:wN \__fp_invalid_operation_o:Nww
12867         \exp_after:wN +
12868       \else:
12869         \exp_after:wN \__fp_invalid_operation_o:Nww
12870         \exp_after:wN -
12871       \fi:
12872     }
12873   \fi:
12874   \s__fp \__fp_chk:w 2 #2 #3;
12875   \s__fp \__fp_chk:w 2 #4
12876 }

```

(End definition for __fp_add_inf_o:Nww.)

```

\__fp_add_normal_o:Nww \__fp_add_normal_o:Nww <sign2> \s__fp \__fp_chk:w 1 <sign1> <exp1>
<body1> ; \s__fp \__fp_chk:w 1 <initial sign2> <exp2> <body2> ;

```

We now have two normal numbers to add, and we have to check signs and exponents more carefully before performing the addition.

```

12877 \cs_new:Npn \__fp_add_normal_o:Nww #1 \s__fp \__fp_chk:w 1 #2
12878 {
12879   \if_meaning:w #1#2
12880     \exp_after:wN \__fp_add_npos_o:NnwNnw
12881   \else:
12882     \exp_after:wN \__fp_sub_npos_o:NnwNnw
12883   \fi:
12884   #2
12885 }

```

(End definition for __fp_add_normal_o:Nww.)

25.2.2 Absolute addition

In this subsection, we perform the addition of two positive normal numbers.

```

\__fp_add_npos_o:NnwNnw \__fp_add_npos_o:NnwNnw <sign1> <exp1> <body1> ; \s__fp \__fp_chk:w 1
<initial sign2> <exp2> <body2> ;

```

Since we are doing an addition, the final sign is $\langle sign_1 \rangle$. Start an `__int_eval:w`, responsible for computing the exponent: the result, and the $\langle final\ sign \rangle$ are then given to `__fp_sanitize:Nw` which checks for overflow. The exponent is computed as the largest exponent #2 or #5, incremented if there is a carry. To add the significands, we decimate the smaller number by the difference between the exponents. This is done by `__fp_add_big_i:wNnw` or `__fp_add_big_ii:wNnw`. We need to bring the final sign with us in the midst of the calculation to round properly at the end.

```

12886 \cs_new:Npn \__fp_add_npos_o:NnwNnw #1#2#3 ; \s__fp \__fp_chk:w 1 #4 #5
12887 {

```

```

12888 \exp_after:wN \_fp_sanitize:Nw
12889 \exp_after:wN #1
12890 \_int_value:w \_int_eval:w
12891 \if_int_compare:w #2 > #5 \exp_stop_f:
12892 #2
12893 \exp_after:wN \_fp_add_big_i_o:wNww \_int_value:w -
12894 \else:
12895 #5
12896 \exp_after:wN \_fp_add_big_ii_o:wNww \_int_value:w
12897 \fi:
12898 \_int_eval:w #5 - #2 ; #1 #3;
12899 }

```

(End definition for _fp_add_npos_o:NnwNnw.)

_fp_add_big_i_o:wNww _fp_add_big_i_o:wNww $\langle shift \rangle$; $\langle final\ sign \rangle$ $\langle body_1 \rangle$; $\langle body_2 \rangle$;
_fp_add_big_ii_o:wNww Shift the significand of the small number, then add with _fp_add_significand_o:NnnwnnnnN.

```

12900 \cs_new:Npn \_fp_add_big_i_o:wNww #1; #2 #3; #4;
12901 {
12902   \_fp_decimate:nNnnnn {#1}
12903   \_fp_add_significand_o:NnnwnnnnN
12904   #4
12905   #3
12906   #2
12907 }
12908 \cs_new:Npn \_fp_add_big_ii_o:wNww #1; #2 #3; #4;
12909 {
12910   \_fp_decimate:nNnnnn {#1}
12911   \_fp_add_significand_o:NnnwnnnnN
12912   #3
12913   #4
12914   #2
12915 }

```

(End definition for _fp_add_big_i_o:wNww and _fp_add_big_ii_o:wNww.)

_fp_add_significand_o:NnnwnnnnN _fp_add_significand_o:NnnwnnnnN $\langle rounding\ digit \rangle$ $\{ \langle Y'_1 \rangle \}$ $\{ \langle Y'_2 \rangle \}$
_fp_add_significand_pack:NNNNNNN $\langle extra-digits \rangle$; $\{ \langle X_1 \rangle \}$ $\{ \langle X_2 \rangle \}$ $\{ \langle X_3 \rangle \}$ $\{ \langle X_4 \rangle \}$ $\langle final\ sign \rangle$
_fp_add_significand_test_o:N To round properly, we must know at which digit the rounding should occur. This

requires to know whether the addition produces an overall carry or not. Thus, we do the computation now and check for a carry, then go back and do the rounding. The rounding may cause a carry in very rare cases such as $0.99\dots95 \rightarrow 1.00\dots0$, but this situation always give an exact power of 10, for which it is easy to correct the result at the end.

```

12916 \cs_new:Npn \_fp_add_significand_o:NnnwnnnnN #1 #2#3 #4; #5#6#7#8
12917 {
12918   \exp_after:wN \_fp_add_significand_test_o:N
12919   \_int_value:w \_int_eval:w 1#5#6 + #2
12920   \exp_after:wN \_fp_add_significand_pack:NNNNNNN
12921   \_int_value:w \_int_eval:w 1#7#8 + #3 ; #1
12922 }
12923 \cs_new:Npn \_fp_add_significand_pack:NNNNNNN #1 #2#3#4#5#6#7
12924 {
12925   \if_meaning:w 2 #1

```



```

12926         + 1
12927     \fi:
12928     ; #2 #3 #4 #5 #6 #7 ;
12929 }
12930 \cs_new:Npn \__fp_add_significand_test_o:N #1
12931 {
12932     \if_meaning:w 2 #1
12933     \exp_after:wN \__fp_add_significand_carry_o:wwwNN
12934     \else:
12935     \exp_after:wN \__fp_add_significand_no_carry_o:wwwNN
12936     \fi:
12937 }

```

(End definition for __fp_add_significand_o:NnnwnnnnN, __fp_add_significand_pack:NNNNNNN, and __fp_add_significand_test_o:N.)

__fp_add_significand_no_carry_o:wwwNN <8d> ; <6d> ; <2d> ; <rounding digit> <sign>

If there's no carry, grab all the digits again and round. The packing function __fp_basics_pack_high:NNNNNw takes care of the case where rounding brings a carry.

```

12938 \cs_new:Npn \__fp_add_significand_no_carry_o:wwwNN
12939 #1; #2; #3#4 ; #5#6
12940 {
12941     \exp_after:wN \__fp_basics_pack_high:NNNNNw
12942     \__int_value:w \__int_eval:w 1 #1
12943     \exp_after:wN \__fp_basics_pack_low:NNNNNw
12944     \__int_value:w \__int_eval:w 1 #2 #3#4
12945     + \__fp_round:NNN #6 #4 #5
12946     \exp_after:wN ;
12947 }

```

(End definition for __fp_add_significand_no_carry_o:wwwNN.)

__fp_add_significand_carry_o:wwwNN <8d> ; <6d> ; <2d> ; <rounding digit> <sign>

The case where there is a carry is very similar. Rounding can even raise the first digit from 1 to 2, but we don't care.

```

12948 \cs_new:Npn \__fp_add_significand_carry_o:wwwNN
12949 #1; #2; #3#4; #5#6
12950 {
12951     + 1
12952     \exp_after:wN \__fp_basics_pack_weird_high:NNNNNNNNw
12953     \__int_value:w \__int_eval:w 1 1 #1
12954     \exp_after:wN \__fp_basics_pack_weird_low:NNNNNw
12955     \__int_value:w \__int_eval:w 1 #2#3 +
12956     \exp_after:wN \__fp_round:NNN
12957     \exp_after:wN #6
12958     \exp_after:wN #3
12959     \__int_value:w \__fp_round_digit:Nw #4 #5 ;
12960     \exp_after:wN ;
12961 }

```

(End definition for __fp_add_significand_carry_o:wwwNN.)

25.2.3 Absolute subtraction

`_fp_sub_npos_o:NnwNnw`
`_fp_sub_eq_o:Nnwnw`
`_fp_sub_npos_ii_o:Nnwnw`

`_fp_sub_npos_o:NnwNnw` $\langle sign_1 \rangle$ $\langle exp_1 \rangle$ $\langle body_1 \rangle$; `\s_fp _fp_chk:w 1`
 $\langle initial\ sign_2 \rangle$ $\langle exp_2 \rangle$ $\langle body_2 \rangle$;

Rounding properly in some modes requires to know what the sign of the result will be. Thus, we start by comparing the exponents and significands. If the numbers coincide, return zero. If the second number is larger, swap the numbers and call `_fp_sub_npos_i_o:Nnwnw` with the opposite of $\langle sign_1 \rangle$.

```

12962 \cs_new:Npn \_fp_sub_npos_o:NnwNnw #1#2#3; \s\_fp \_fp_chk:w 1 #4#5#6;
12963 {
12964   \if_case:w \_fp_compare_npos:nwnw {#2} #3; {#5} #6; \exp_stop_f:
12965   \exp_after:wN \_fp_sub_eq_o:Nnwnw
12966   \or:
12967   \exp_after:wN \_fp_sub_npos_i_o:Nnwnw
12968   \else:
12969   \exp_after:wN \_fp_sub_npos_ii_o:Nnwnw
12970   \fi:
12971   #1 {#2} #3; {#5} #6;
12972 }
12973 \cs_new:Npn \_fp_sub_eq_o:Nnwnw #1#2; #3; { \exp_after:wN \c_zero_fp }
12974 \cs_new:Npn \_fp_sub_npos_ii_o:Nnwnw #1 #2; #3;
12975 {
12976   \exp_after:wN \_fp_sub_npos_i_o:Nnwnw
12977   \_int_value:w \_fp_neg_sign:N #1
12978   #3; #2;
12979 }

```

(End definition for `_fp_sub_npos_o:NnwNnw`, `_fp_sub_eq_o:Nnwnw`, and `_fp_sub_npos_ii_o:Nnwnw`.)

`_fp_sub_npos_i_o:Nnwnw`

After the computation is done, `_fp_sanitize:Nw` checks for overflow/underflow. It expects the $\langle final\ sign \rangle$ and the $\langle exponent \rangle$ (delimited by ;). Start an integer expression for the exponent, which starts with the exponent of the largest number, and may be decreased if the two numbers are very close. If the two numbers have the same exponent, call the **near** auxiliary. Otherwise, decimate y , then call the **far** auxiliary to evaluate the difference between the two significands. Note that we decimate by 1 less than one could expect.

```

12980 \cs_new:Npn \_fp_sub_npos_i_o:Nnwnw #1 #2#3; #4#5;
12981 {
12982   \exp_after:wN \_fp_sanitize:Nw
12983   \exp_after:wN #1
12984   \_int_value:w \_int_eval:w
12985   #2
12986   \if_int_compare:w #2 = #4 \exp_stop_f:
12987   \exp_after:wN \_fp_sub_back_near_o:nnnnnnnnN
12988   \else:
12989   \exp_after:wN \_fp_decimate:nNnnnn \exp_after:wN
12990   { \_int_value:w \_int_eval:w #2 - #4 - 1 \exp_after:wN }
12991   \exp_after:wN \_fp_sub_back_far_o:NnnwnnnnN
12992   \fi:
12993   #5
12994   #3
12995   #1
12996 }

```

(End definition for _fp_sub_npos_i_o:Nnwnw.)

_fp_sub_back_near_o:nnnnnnnnN _fp_sub_back_near_o:nnnnnnnnN {<Y₁>} {<Y₂>} {<Y₃>} {<Y₄>} {<X₁>}
 _fp_sub_back_near_pack:NNNNNNw {<X₂>} {<X₃>} {<X₄>} {<final sign>}
 _fp_sub_back_near_after:wNNNNw

In this case, the subtraction is exact, so we discard the *<final sign>* #9. The very large shifts of 10⁹ and 1.1·10⁹ are unnecessary here, but allow the auxiliaries to be reused later. Each integer expression produces a 10 digit result. If the resulting 16 digits start with a 0, then we need to shift the group, padding with trailing zeros.

```

12997 \cs_new:Npn \_fp_sub_back_near_o:nnnnnnnnN #1#2#3#4 #5#6#7#8 #9
12998 {
12999   \exp_after:wN \_fp_sub_back_near_after:wNNNNw
13000   \_int_value:w \_int_eval:w 10#5#6 - #1#2 - 11
13001   \exp_after:wN \_fp_sub_back_near_pack:NNNNNNw
13002   \_int_value:w \_int_eval:w 11#7#8 - #3#4 \exp_after:wN ;
13003 }
13004 \cs_new:Npn \_fp_sub_back_near_pack:NNNNNNw #1#2#3#4#5#6#7 ;
13005 { + #1#2 ; {#3#4#5#6} {#7} ; }
13006 \cs_new:Npn \_fp_sub_back_near_after:wNNNNw 10 #1#2#3#4 #5 ;
13007 {
13008   \if_meaning:w 0 #1
13009     \exp_after:wN \_fp_sub_back_shift:wnnnn
13010   \fi:
13011   ; {#1#2#3#4} {#5}
13012 }

```

(End definition for _fp_sub_back_near_o:nnnnnnnnN, _fp_sub_back_near_pack:NNNNNNw, and _fp_sub_back_near_after:wNNNNw.)

_fp_sub_back_shift:wnnnn _fp_sub_back_shift:wnnnn ; {<Z₁>} {<Z₂>} {<Z₃>} {<Z₄>} ;
 _fp_sub_back_shift_ii:ww This function is called with <Z₁> ≤ 999. Act with \number to trim leading zeros from
 _fp_sub_back_shift_iii:NNNNNNNNw <Z₁> <Z₂> (we don't do all four blocks at once, since non-zero blocks would then overflow
 _fp_sub_back_shift_iv:nnnnw T_EX's integers). If the first two blocks are zero, the auxiliary receives an empty #1 and

trims #2#30 from leading zeros, yielding a total shift between 7 and 16 to the exponent. Otherwise we get the shift from #1 alone, yielding a result between 1 and 6. Once the exponent is taken care of, trim leading zeros from #1#2#3 (when #1 is empty, the space before #2#3 is ignored), get four blocks of 4 digits and finally clean up. Trailing zeros are added so that digits can be grabbed safely.

```

13013 \cs_new:Npn \_fp_sub_back_shift:wnnnn ; #1#2
13014 {
13015   \exp_after:wN \_fp_sub_back_shift_ii:ww
13016   \_int_value:w #1 #2 0 ;
13017 }
13018 \cs_new:Npn \_fp_sub_back_shift_ii:ww #1 0 ; #2#3 ;
13019 {
13020   \if_meaning:w @ #1 @
13021     - 7
13022   - \exp_after:wN \use_i:nnn
13023   \exp_after:wN \_fp_sub_back_shift_iii:NNNNNNNNw
13024   \_int_value:w #2#3 0 ~ 123456789;
13025   \else:
13026     - \_fp_sub_back_shift_iii:NNNNNNNNw #1 123456789;
13027   \fi:
13028   \exp_after:wN \_fp_pack_twice_four:wNNNNNNNN

```

```

13029 \exp_after:wN \_fp_pack_twice_four:wNNNNNNNN
13030 \exp_after:wN \_fp_sub_back_shift_iv:nnnnw
13031 \exp_after:wN ;
13032 \_int_value:w
13033 #1 ~ #2#3 0 ~ 0000 0000 0000 000 ;
13034 }
13035 \cs_new:Npn \_fp_sub_back_shift_iii:NNNNNNNNw #1#2#3#4#5#6#7#8#9; {#8}
13036 \cs_new:Npn \_fp_sub_back_shift_iv:nnnnw #1 ; #2 ; { ; #1 ; }

```

(End definition for _fp_sub_back_shift:wnnnn and others.)

_fp_sub_back_far_o:NnnwnnnnN $\langle \text{rounding} \rangle \{ \langle Y'_1 \rangle \} \{ \langle Y'_2 \rangle \}$
 $\langle \text{extra-digits} \rangle ; \{ \langle X_1 \rangle \} \{ \langle X_2 \rangle \} \{ \langle X_3 \rangle \} \{ \langle X_4 \rangle \} \langle \text{final sign} \rangle$

If the difference is greater than $10^{\langle \text{expo}_x \rangle}$, call the `very_far` auxiliary. If the result is less than $10^{\langle \text{expo}_x \rangle}$, call the `not_far` auxiliary. If it is too close a call to know yet, namely if $1 \langle Y'_1 \rangle \langle Y'_2 \rangle = \langle X_1 \rangle \langle X_2 \rangle \langle X_3 \rangle \langle X_4 \rangle 0$, then call the `quite_far` auxiliary. We use the odd combination of space and semi-colon delimiters to allow the `not_far` auxiliary to grab each piece individually, the `very_far` auxiliary to use `_fp_pack_eight:wNNNNNNNN`, and the `quite_far` to ignore the significands easily (using the `; delimiter`).

```

13037 \cs_new:Npn \_fp_sub_back_far_o:NnnwnnnnN #1 #2#3 #4; #5#6#7#8
13038 {
13039   \if_case:w
13040     \if_int_compare:w 1 #2 = #5#6 \use_i:nnnn #7 \exp_stop_f:
13041     \if_int_compare:w #3 = \use_none:n #7#8 0 \exp_stop_f:
13042     0
13043   \else:
13044     \if_int_compare:w #3 > \use_none:n #7#8 0 - \fi: 1
13045     \fi:
13046   \else:
13047     \if_int_compare:w 1 #2 > #5#6 \use_i:nnnn #7 - \fi: 1
13048     \fi:
13049     \exp_stop_f:
13050     \exp_after:wN \_fp_sub_back_quite_far_o:wwNN
13051   \or: \exp_after:wN \_fp_sub_back_very_far_o:wwwNN
13052   \else: \exp_after:wN \_fp_sub_back_not_far_o:wwwNN
13053   \fi:
13054   #2 ~ #3 ; #5 #6 ~ #7 #8 ; #1
13055 }

```

(End definition for _fp_sub_back_far_o:NnnwnnnnN.)

_fp_sub_back_quite_far_o:wwNN
 _fp_sub_back_quite_far_ii:NN

The easiest case is when $x - y$ is extremely close to a power of 10, namely the first digit of x is 1, and all others vanish when subtracting y . Then the $\langle \text{rounding} \rangle$ #3 and the $\langle \text{final sign} \rangle$ #4 control whether we get 1 or 0.9999999999999999. In the usual round-to-nearest mode, we will get 1 whenever the $\langle \text{rounding} \rangle$ digit is less than or equal to 5 (remember that the $\langle \text{rounding} \rangle$ digit is only equal to 5 if there was no further non-zero digit).

```

13056 \cs_new:Npn \_fp_sub_back_quite_far_o:wwNN #1; #2; #3#4
13057 {
13058   \exp_after:wN \_fp_sub_back_quite_far_ii:NN
13059   \exp_after:wN #3
13060   \exp_after:wN #4
13061 }
13062 \cs_new:Npn \_fp_sub_back_quite_far_ii:NN #1#2
13063 {

```

```

13064 \if_case:w \__fp_round_neg:NNN #2 0 #1
13065 \exp_after:wN \use_i:nn
13066 \else:
13067 \exp_after:wN \use_ii:nn
13068 \fi:
13069 { ; {1000} {0000} {0000} {0000} ; }
13070 { - 1 ; {9999} {9999} {9999} {9999} ; }
13071 }

```

(End definition for __fp_sub_back_quite_far_o:wwwNN and __fp_sub_back_quite_far_ii:NN.)

__fp_sub_back_not_far_o:wwwNN

In the present case, x and y have different exponents, but y is large enough that $x - y$ has a smaller exponent than x . Decrement the exponent (with -1). Then proceed in a way similar to the `near` auxiliaries seen earlier, but multiplying x by 10 (#30 and #40 below), and with the added quirk that the *rounding* digit has to be taken into account. Namely, we may have to decrease the result by one unit if `__fp_round_neg:NNN` returns 1. This function expects the *final sign* #6, the last digit of `1100000000+#40-#2`, and the *rounding* digit. Instead of redoing the computation for the second argument, we note that `__fp_round_neg:NNN` only cares about its parity, which is identical to that of the last digit of #2.

```

13072 \cs_new:Npn \__fp_sub_back_not_far_o:wwwNN #1 ~ #2; #3 ~ #4; #5#6
13073 {
13074   - 1
13075   \exp_after:wN \__fp_sub_back_near_after:wNNNNw
13076   \__int_value:w \__int_eval:w 1#30 - #1 - 11
13077   \exp_after:wN \__fp_sub_back_near_pack:NNNNNNw
13078   \__int_value:w \__int_eval:w 11 0000 0000 + #40 - #2
13079   - \exp_after:wN \__fp_round_neg:NNN
13080   \exp_after:wN #6
13081   \use_none:nnnnnnn #2 #5
13082   \exp_after:wN ;
13083 }

```

(End definition for __fp_sub_back_not_far_o:wwwNN.)

__fp_sub_back_very_far_o:wwwNN
__fp_sub_back_very_far_ii_o:nnNwNN

The case where $x - y$ and x have the same exponent is a bit more tricky, mostly because it cannot reuse the same auxiliaries. Shift the y significand by adding a leading 0. Then the logic is similar to the `not_far` functions above. Rounding is a bit more complicated: we have two *rounding* digits #3 and #6 (from the decimation, and from the new shift) to take into account, and getting the parity of the main result requires a computation. The first `__int_value:w` triggers the second one because the number is unfinished; we can thus not use 0 in place of 2 there.

```

13084 \cs_new:Npn \__fp_sub_back_very_far_o:wwwNN #1#2#3#4#5#6#7
13085 {
13086   \__fp_pack_eight:wNNNNNNNN
13087   \__fp_sub_back_very_far_ii_o:nnNwNN
13088   { 0 #1#2#3 #4#5#6#7 }
13089   ;
13090 }
13091 \cs_new:Npn \__fp_sub_back_very_far_ii_o:nnNwNN #1#2 ; #3 ; #4 ~ #5; #6#7
13092 {
13093   \exp_after:wN \__fp_basics_pack_high:NNNNNw
13094   \__int_value:w \__int_eval:w 1#4 - #1 - 1

```

```

13095     \exp_after:wN \__fp_basics_pack_low:NNNNNw
13096     \__int_value:w \__int_eval:w 2#5 - #2
13097     - \exp_after:wN \__fp_round_neg:NNN
13098     \exp_after:wN #7
13099     \__int_value:w
13100     \if_int_odd:w \__int_eval:w #5 - #2 \__int_eval_end:
13101     1 \else: 2 \fi:
13102     \__int_value:w \__fp_round_digit:Nw #3 #6 ;
13103     \exp_after:wN ;
13104 }

```

(End definition for __fp_sub_back_very_far_o:wwwNN and __fp_sub_back_very_far_ii_o:nnNwwNN.)

25.3 Multiplication

25.3.1 Signs, and special numbers

__fp*_o:ww We go through an auxiliary, which is common with __fp/_o:ww. The first argument is the operation, used for the invalid operation exception. The second is inserted in a formula to dispatch cases slightly differently between multiplication and division. The third is the operation for normal floating points. The fourth is there for extra cases needed in __fp/_o:ww.

```

13105 \cs_new:cpn { __fp*_o:ww }
13106 {
13107     \__fp_mul_cases_o:NnNnw
13108     *
13109     { - 2 + }
13110     \__fp_mul_npos_o:Nww
13111     { }
13112 }

```

(End definition for __fp*_o:ww.)

__fp_mul_cases_o:nNnnnw Split into 10 cases (12 for division). If both numbers are normal, go to case 0 (same sign) or case 1 (opposite signs): in both cases, call __fp_mul_npos_o:Nww to do the work. If the first operand is `nan`, go to case 2, in which the second operand is discarded; if the second operand is `nan`, go to case 3, in which the first operand is discarded (note the weird interaction with the final test on signs). Then we separate the case where the first number is normal and the second is zero: this goes to cases 4 and 5 for multiplication, 10 and 11 for division. Otherwise, we do a computation which dispatches the products $0 \times 0 = 0 \times 1 = 1 \times 0 = 0$ to case 4 or 5 depending on the combined sign, the products $0 \times \infty$ and $\infty \times 0$ to case 6 or 7 (invalid operation), and the products $1 \times \infty = \infty \times 1 = \infty \times \infty = \infty$ to cases 8 and 9. Note that the code for these two cases (which return $\pm\infty$) is inserted as argument #4, because it differs in the case of divisions.

```

13113 \cs_new:Npn \__fp_mul_cases_o:NnNnw
13114 #1#2#3#4 \s__fp \__fp_chk:w #5#6#7; \s__fp \__fp_chk:w #8#9
13115 {
13116     \if_case:w \__int_eval:w
13117         \if_int_compare:w #5 #8 = 11 ~
13118         1
13119         \else:
13120         \if_meaning:w 3 #8
13121         3

```

```

13122         \else:
13123             \if_meaning:w 3 #5
13124             2
13125         \else:
13126             \if_int_compare:w #5 #8 = 10 ~
13127             9 #2 - 2
13128         \else:
13129             (#5 #2 #8) / 2 * 2 + 7
13130         \fi:
13131     \fi:
13132 \fi:
13133 \fi:
13134 \if_meaning:w #6 #9 - 1 \fi:
13135     \__int_eval_end:
13136     \__fp_case_use:nw { #3 0 }
13137 \or: \__fp_case_use:nw { #3 2 }
13138 \or: \__fp_case_return_i_o:ww
13139 \or: \__fp_case_return_ii_o:ww
13140 \or: \__fp_case_return_o:Nww \c_zero_fp
13141 \or: \__fp_case_return_o:Nww \c_minus_zero_fp
13142 \or: \__fp_case_use:nw { \__fp_invalid_operation_o:Nww #1 }
13143 \or: \__fp_case_use:nw { \__fp_invalid_operation_o:Nww #1 }
13144 \or: \__fp_case_return_o:Nww \c_inf_fp
13145 \or: \__fp_case_return_o:Nww \c_minus_inf_fp
13146 #4
13147 \fi:
13148 \s__fp \__fp_chk:w #5 #6 #7;
13149 \s__fp \__fp_chk:w #8 #9
13150 }

```

(End definition for __fp_mul_cases_o:nNnnnw.)

25.3.2 Absolute multiplication

In this subsection, we perform the multiplication of two positive normal numbers.

```

\__fp_mul_npos_o:Nww \__fp_mul_npos_o:Nww <final sign> \s__fp \__fp_chk:w 1 <sign1> {<exp1>}
<body1> ; \s__fp \__fp_chk:w 1 <sign2> {<exp2>} <body2> ;

```

After the computation, __fp_sanitize:Nw checks for overflow or underflow. As we did for addition, __int_eval:w computes the exponent, catching any shift coming from the computation in the significand. The <final sign> is needed to do the rounding properly in the significand computation. We setup the post-expansion here, triggered by __fp_mul_significand_o:nnnnNnnnn.

```

13151 \cs_new:Npn \__fp_mul_npos_o:Nww
13152 #1 \s__fp \__fp_chk:w #2 #3 #4 #5 ; \s__fp \__fp_chk:w #6 #7 #8 #9 ;
13153 {
13154     \exp_after:wN \__fp_sanitize:Nw
13155     \exp_after:wN #1
13156     \__int_value:w \__int_eval:w
13157     #4 + #8
13158     \__fp_mul_significand_o:nnnnNnnnn #5 #1 #9
13159 }

```

(End definition for __fp_mul_npos_o:Nww.)

```

\__fp_mul_significand_o:nnnnNnnnn \__fp_mul_significand_o:nnnnNnnnn {<X1>} {<X2>} {<X3>} {<X4>} <sign>
\__fp_mul_significand_drop:NNNNNw {<Y1>} {<Y2>} {<Y3>} {<Y4>}
\__fp_mul_significand_keep:NNNNNw

```

Note the three semicolons at the end of the definition. One is for the last `__fp_mul_significand_drop:NNNNNw`; one is for `__fp_round_digit:Nw` later on; and one, preceded by `\exp_after:wN`, which is correctly expanded (within an `__int_eval:w`), is used by `__fp_basics_pack_low:NNNNNw`.

The product of two 16 digit integers has 31 or 32 digits, but it is impossible to know which one before computing. The place where we round depends on that number of digits, and may depend on all digits until the last in some rare cases. The approach is thus to compute the 5 first blocks of 4 digits (the first one is between 100 and 9999 inclusive), and a compact version of the remaining 3 blocks. Afterwards, the number of digits is known, and we can do the rounding within yet another set of `__int_eval:w`.

```

13160 \cs_new:Npn \__fp_mul_significand_o:nnnnNnnnn #1#2#3#4 #5 #6#7#8#9
13161 {
13162   \exp_after:wN \__fp_mul_significand_test_f:NNN
13163   \exp_after:wN #5
13164   \__int_value:w \__int_eval:w 99990000 + #1*#6 +
13165   \exp_after:wN \__fp_mul_significand_keep:NNNNNw
13166   \__int_value:w \__int_eval:w 99990000 + #1*#7 + #2*#6 +
13167   \exp_after:wN \__fp_mul_significand_keep:NNNNNw
13168   \__int_value:w \__int_eval:w 99990000 + #1*#8 + #2*#7 + #3*#6 +
13169   \exp_after:wN \__fp_mul_significand_drop:NNNNNw
13170   \__int_value:w \__int_eval:w 99990000 + #1*#9 + #2*#8 + #3*#7 + #4*#6 +
13171   \exp_after:wN \__fp_mul_significand_drop:NNNNNw
13172   \__int_value:w \__int_eval:w 99990000 + #2*#9 + #3*#8 + #4*#7 +
13173   \exp_after:wN \__fp_mul_significand_drop:NNNNNw
13174   \__int_value:w \__int_eval:w 99990000 + #3*#9 + #4*#8 +
13175   \exp_after:wN \__fp_mul_significand_drop:NNNNNw
13176   \__int_value:w \__int_eval:w 100000000 + #4*#9 ;
13177   ; \exp_after:wN ;
13178 }
13179 \cs_new:Npn \__fp_mul_significand_drop:NNNNNw #1#2#3#4#5 #6;
13180 { #1#2#3#4#5 ; + #6 }
13181 \cs_new:Npn \__fp_mul_significand_keep:NNNNNw #1#2#3#4#5 #6;
13182 { #1#2#3#4#5 ; #6 ; }

```

(End definition for `__fp_mul_significand_o:nnnnNnnnn`, `__fp_mul_significand_drop:NNNNNw`, and `__fp_mul_significand_keep:NNNNNw`.)

```

\__fp_mul_significand_test_f:NNN \__fp_mul_significand_test_f:NNN <sign> 1 <digits 1-8> ; <digits 9-12> ;
<digits 13-16> ; + <digits 17-20> + <digits 21-24> + <digits 25-28> + <digits
29-32> ; \exp_after:wN ;

```

If the *<digit 1>* is non-zero, then for rounding we only care about the digits 16 and 17, and whether further digits are zero or not (check for exact ties). On the other hand, if *<digit 1>* is zero, we care about digits 17 and 18, and whether further digits are zero.

```

13183 \cs_new:Npn \__fp_mul_significand_test_f:NNN #1 #2 #3
13184 {
13185   \if_meaning:w 0 #3
13186   \exp_after:wN \__fp_mul_significand_small_f:NNwwwN
13187   \else:
13188   \exp_after:wN \__fp_mul_significand_large_f:NwwNNNNN
13189   \fi:
13190   #1 #3

```



```
13191 }
```

(End definition for `_fp_mul_significand_test_f:NNN`.)

`_fp_mul_significand_large_f:NwwNNNN`

In this branch, $\langle digit\ 1 \rangle$ is non-zero. The result is thus $\langle digits\ 1-16 \rangle$, plus some rounding which depends on the digits 16, 17, and whether all subsequent digits are zero or not. Here, `_fp_round_digit:Nw` takes digits 17 and further (as an integer expression), and replaces it by a $\langle rounding\ digit \rangle$, suitable for `_fp_round:NNN`.

```
13192 \cs_new:Npn \_fp_mul_significand_large_f:NwwNNNN #1 #2; #3; #4#5#6#7; +
13193 {
13194   \exp_after:wN \_fp_basics_pack_high:NNNNNw
13195   \__int_value:w \__int_eval:w 1#2
13196   \exp_after:wN \_fp_basics_pack_low:NNNNNw
13197   \__int_value:w \__int_eval:w 1#3#4#5#6#7
13198   + \exp_after:wN \_fp_round:NNN
13199   \exp_after:wN #1
13200   \exp_after:wN #7
13201   \__int_value:w \_fp_round_digit:Nw
13202 }
```

(End definition for `_fp_mul_significand_large_f:NwwNNNN`.)

`_fp_mul_significand_small_f:NNwwN`

In this branch, $\langle digit\ 1 \rangle$ is zero. Our result will thus be $\langle digits\ 2-17 \rangle$, plus some rounding which depends on the digits 17, 18, and whether all subsequent digits are zero or not. The 8 digits `1#3` are followed, after expansion of the `small_pack` auxiliary, by the next digit, to form a 9 digit number.

```
13203 \cs_new:Npn \_fp_mul_significand_small_f:NNwwN #1 #2#3; #4#5; #6; + #7
13204 {
13205   - 1
13206   \exp_after:wN \_fp_basics_pack_high:NNNNNw
13207   \__int_value:w \__int_eval:w 1#3#4
13208   \exp_after:wN \_fp_basics_pack_low:NNNNNw
13209   \__int_value:w \__int_eval:w 1#5#6#7
13210   + \exp_after:wN \_fp_round:NNN
13211   \exp_after:wN #1
13212   \exp_after:wN #7
13213   \__int_value:w \_fp_round_digit:Nw
13214 }
```

(End definition for `_fp_mul_significand_small_f:NNwwN`.)

25.4 Division

25.4.1 Signs, and special numbers

Time is now ripe to tackle the hardest of the four elementary operations: division.

`_fp/_:oww`

Filtering special floating point is very similar to what we did for multiplications, with a few variations. Invalid operation exceptions display `/` rather than `*`. In the formula for dispatch, we replace `- 2 +` by `-`. The case of normal numbers is treated using `_fp_div_npos_o:Nww` rather than `_fp_mul_npos_o:Nww`. There are two additional cases: if the first operand is normal and the second is a zero, then the division by zero exception is raised: cases 10 and 11 of the `\if_case:w` construction in `_fp_mul_cases_o:NnNww` are provided as the fourth argument here.

```

13215 \cs_new:cpn { __fp/_o:ww }
13216 {
13217     \__fp_mul_cases_o:NnNnw
13218     /
13219     { - }
13220     \__fp_div_npos_o:Nww
13221     {
13222         \or:
13223         \__fp_case_use:nw
13224         { \__fp_division_by_zero_o:NNnw \c_inf_fp / }
13225         \or:
13226         \__fp_case_use:nw
13227         { \__fp_division_by_zero_o:NNnw \c_minus_inf_fp / }
13228     }
13229 }

```

(End definition for __fp/_o:ww.)

```

\__fp_div_npos_o:Nww      \__fp_div_npos_o:Nww <final sign> \s__fp \__fp_chk:w 1 <sign_A> {<exp A>}
                           {<A_1>} {<A_2>} {<A_3>} {<A_4>} ; \s__fp \__fp_chk:w 1 <sign_Z> {<exp Z>}
                           {<Z_1>} {<Z_2>} {<Z_3>} {<Z_4>} ;

```

We want to compute A/Z . As for multiplication, `__fp_sanitize:Nw` checks for overflow or underflow; we provide it with the $\langle final\ sign \rangle$, and an integer expression in which we compute the exponent. We set up the arguments of `__fp_div_significand_i_o:wnnw`, namely an integer $\langle y \rangle$ obtained by adding 1 to the first 5 digits of Z (explanation given soon below), then the four $\{ \langle A_i \rangle \}$, then the four $\{ \langle Z_i \rangle \}$, a semi-colon, and the $\langle final\ sign \rangle$, used for rounding at the end.

```

13230 \cs_new:Npn \__fp_div_npos_o:Nww
13231     #1 \s__fp \__fp_chk:w 1 #2 #3 #4 ; \s__fp \__fp_chk:w 1 #5 #6 #7#8#9;
13232 {
13233     \exp_after:wN \__fp_sanitize:Nw
13234     \exp_after:wN #1
13235     \__int_value:w \__int_eval:w
13236     #3 - #6
13237     \exp_after:wN \__fp_div_significand_i_o:wnnw
13238     \__int_value:w \__int_eval:w #7 \use_i:nnnn #8 + 1 ;
13239     #4
13240     {#7}{#8}#9 ;
13241     #1
13242 }

```

(End definition for __fp_div_npos_o:Nww.)

25.4.2 Work plan

In this subsection, we explain how to avoid overflowing $\text{T}_{\text{E}}\text{X}$'s integers when performing the division of two positive normal numbers.

We are given two numbers, $A = 0.A_1A_2A_3A_4$ and $Z = 0.Z_1Z_2Z_3Z_4$, in blocks of 4 digits, and we know that the first digits of A_1 and of Z_1 are non-zero. To compute A/Z , we proceed as follows.

- Find an integer $Q_A \simeq 10^4 A/Z$.
- Replace A by $B = 10^4 A - Q_A Z$.

- Find an integer $Q_B \simeq 10^4 B/Z$.
- Replace B by $C = 10^4 B - Q_B Z$.
- Find an integer $Q_C \simeq 10^4 C/Z$.
- Replace C by $D = 10^4 C - Q_C Z$.
- Find an integer $Q_D \simeq 10^4 D/Z$.
- Consider $E = 10^4 D - Q_D Z$, and ensure correct rounding.

The result is then $Q = 10^{-4}Q_A + 10^{-8}Q_B + 10^{-12}Q_C + 10^{-16}Q_D + \text{rounding}$. Since the Q_i are integers, B , C , D , and E are all exact multiples of 10^{-16} , in other words, computing with 16 digits after the decimal separator yields exact results. The problem will be overflow: in general B , C , D , and E may be greater than 1.

Unfortunately, things are not as easy as they seem. In particular, we want all intermediate steps to be positive, since negative results would require extra calculations at the end. This requires that $Q_A \leq 10^4 A/Z$ etc. A reasonable attempt would be to define Q_A as

$$\backslash\text{int_eval:n} \left\{ \frac{A_1 A_2}{Z_1 + 1} - 1 \right\} \leq 10^4 \frac{A}{Z}$$

Subtracting 1 at the end takes care of the fact that $\varepsilon\text{-TeX}$'s $\backslash_ \text{int_eval:w}$ rounds divisions instead of truncating (really, $1/2$ would be sufficient, but we work with integers). We add 1 to Z_1 because $Z_1 \leq 10^4 Z < Z_1 + 1$ and we need Q_A to be an underestimate. However, we are now underestimating Q_A too much: it can be wrong by up to 100, for instance when $Z = 0.1$ and $A \simeq 1$. Then B could take values up to 10 (maybe more), and a few steps down the line, we would run into arithmetic overflow, since TeX can only handle integers less than roughly $2 \cdot 10^9$.

A better formula is to take

$$Q_A = \backslash\text{int_eval:n} \left\{ \frac{10 \cdot A_1 A_2}{\lfloor 10^{-3} \cdot Z_1 Z_2 \rfloor + 1} - 1 \right\}.$$

This is always less than $10^9 A/(10^5 Z)$, as we wanted. In words, we take the 5 first digits of Z into account, and the 8 first digits of A , using 0 as a 9-th digit rather than the true digit for efficiency reasons. We shall prove that using this formula to define all the Q_i avoids any overflow. For convenience, let us denote

$$y = \lfloor 10^{-3} \cdot Z_1 Z_2 \rfloor + 1,$$

so that, taking into account the fact that $\varepsilon\text{-TeX}$ rounds ties away from zero,

$$\begin{aligned} Q_A &= \left\lfloor \frac{A_1 A_2 0}{y} - \frac{1}{2} \right\rfloor \\ &> \frac{A_1 A_2 0}{y} - \frac{3}{2}. \end{aligned}$$

Note that $10^4 < y \leq 10^5$, and $999 \leq Q_A \leq 99989$. Also note that this formula does not cause an overflow as long as $A < (2^{31} - 1)/10^9 \simeq 2.147 \dots$, since the numerator involves an integer slightly smaller than $10^9 A$.

Let us bound B :

$$\begin{aligned}
10^5 B &= A_1 A_2 0 + 10 \cdot 0 \cdot A_3 A_4 - 10 \cdot Z_1 \cdot Z_2 Z_3 Z_4 \cdot Q_A \\
&< A_1 A_2 0 \cdot \left(1 - 10 \cdot \frac{Z_1 \cdot Z_2 Z_3 Z_4}{y}\right) + \frac{3}{2} \cdot 10 \cdot Z_1 \cdot Z_2 Z_3 Z_4 + 10 \\
&\leq \frac{A_1 A_2 0 \cdot (y - 10 \cdot Z_1 \cdot Z_2 Z_3 Z_4)}{y} + \frac{3}{2} y + 10 \\
&\leq \frac{A_1 A_2 0 \cdot 1}{y} + \frac{3}{2} y + 10 \leq \frac{10^9 A}{y} + 1.6 \cdot y.
\end{aligned}$$

At the last step, we hide 10 into the second term for later convenience. The same reasoning yields

$$\begin{aligned}
10^5 B &< 10^9 A/y + 1.6y, \\
10^5 C &< 10^9 B/y + 1.6y, \\
10^5 D &< 10^9 C/y + 1.6y, \\
10^5 E &< 10^9 D/y + 1.6y.
\end{aligned}$$

The goal is now to prove that none of B , C , D , and E can go beyond $(2^{31} - 1)/10^9 = 2.147 \dots$.

Combining the various inequalities together with $A < 1$, we get

$$\begin{aligned}
10^5 B &< 10^9/y + 1.6y, \\
10^5 C &< 10^{13}/y^2 + 1.6(y + 10^4), \\
10^5 D &< 10^{17}/y^3 + 1.6(y + 10^4 + 10^8/y), \\
10^5 E &< 10^{21}/y^4 + 1.6(y + 10^4 + 10^8/y + 10^{12}/y^2).
\end{aligned}$$

All of those bounds are convex functions of y (since every power of y involved is convex, and the coefficients are positive), and thus maximal at one of the end-points of the allowed range $10^4 < y \leq 10^5$. Thus,

$$\begin{aligned}
10^5 B &< \max(1.16 \cdot 10^5, 1.7 \cdot 10^5), \\
10^5 C &< \max(1.32 \cdot 10^5, 1.77 \cdot 10^5), \\
10^5 D &< \max(1.48 \cdot 10^5, 1.777 \cdot 10^5), \\
10^5 E &< \max(1.64 \cdot 10^5, 1.7777 \cdot 10^5).
\end{aligned}$$

All of those bounds are less than $2.147 \cdot 10^5$, and we are thus within T_{EX} 's bounds in all cases!

We will later need to have a bound on the Q_i . Their definitions imply that $Q_A < 10^9 A/y - 1/2 < 10^5 A$ and similarly for the other Q_i . Thus, all of them are less than 177770.

The last step is to ensure correct rounding. We have

$$A/Z = \sum_{i=1}^4 (10^{-4i} Q_i) + 10^{-16} E/Z$$

exactly. Furthermore, we know that the result will be in $[0.1, 10)$, hence will be rounded to a multiple of 10^{-16} or of 10^{-15} , so we only need to know the integer part of E/Z , and a “rounding” digit encoding the rest. Equivalently, we need to find the integer part of $2E/Z$, and determine whether it was an exact integer or not (this serves to detect ties). Since

$$\frac{2E}{Z} = 2 \frac{10^5 E}{10^5 Z} \leq 2 \frac{10^5 E}{10^4} < 36,$$

this integer part is between 0 and 35 inclusive. We let $\varepsilon\text{-TeX}$ round

$$P = \text{\texttt{\textbackslash int_eval:n}} \left\{ \frac{2 \cdot E_1 E_2}{Z_1 Z_2} \right\},$$

which differs from $2E/Z$ by at most

$$\frac{1}{2} + 2 \left| \frac{E}{Z} - \frac{E}{10^{-8} Z_1 Z_2} \right| + 2 \left| \frac{10^8 E - E_1 E_2}{Z_1 Z_2} \right| < 1,$$

($1/2$ comes from $\varepsilon\text{-TeX}$ ’s rounding) because each absolute value is less than 10^{-7} . Thus P is either the correct integer part, or is off by 1; furthermore, if $2E/Z$ is an integer, $P = 2E/Z$. We will check the sign of $2E - PZ$. If it is negative, then $E/Z \in ((P-1)/2, P/2)$. If it is zero, then $E/Z = P/2$. If it is positive, then $E/Z \in (P/2, (P+1)/2)$. In each case, we know how to round to an integer, depending on the parity of P , and the rounding mode.

25.4.3 Implementing the significand division

`_fp_div_significand_i_o:wnnw`

`_fp_div_significand_i_o:wnnw` $\langle y \rangle$; $\{\langle A_1 \rangle\} \{\langle A_2 \rangle\} \{\langle A_3 \rangle\} \{\langle A_4 \rangle\}$
 $\{\langle Z_1 \rangle\} \{\langle Z_2 \rangle\} \{\langle Z_3 \rangle\} \{\langle Z_4 \rangle\}$; $\langle sign \rangle$

Compute $10^6 + Q_A$ (a 7 digit number thanks to the shift), unbrace $\langle A_1 \rangle$ and $\langle A_2 \rangle$, and prepare the $\langle continuation \rangle$ arguments for 4 consecutive calls to `_fp_div_significand_calc:wnnnnnnnn`. Each of these calls will need $\langle y \rangle$ (#1), and it turns out that we need post-expansion there, hence the `_int_value:w`. Here, #4 is six brace groups, which give the six first n-type arguments of the `calc` function.

```

13243 \cs_new:Npn \_fp\_div\_significand\_i\_o:wnnw #1 ; #2#3 #4 ;
13244 {
13245   \exp_after:wN \_fp\_div\_significand\_test\_o:w
13246   \_int\_value:w \_int\_eval:w
13247   \exp_after:wN \_fp\_div\_significand\_calc:wnnnnnnnn
13248   \_int\_value:w \_int\_eval:w 999999 + #2 #3 0 / #1 ;
13249   #2 #3 ;
13250   #4
13251   { \exp_after:wN \_fp\_div\_significand\_ii:wN \_int\_value:w #1 }
13252   { \exp_after:wN \_fp\_div\_significand\_ii:wN \_int\_value:w #1 }
13253   { \exp_after:wN \_fp\_div\_significand\_ii:wN \_int\_value:w #1 }
13254   { \exp_after:wN \_fp\_div\_significand\_iii:wnnnnnnn \_int\_value:w #1 }
13255 }
```

(End definition for `_fp_div_significand_i_o:wnnw`.)

`_fp_div_significand_calc:wnnnnnnnn`
`_fp_div_significand_calc_i:wnnnnnnnn`
`_fp_div_significand_calc_ii:wnnnnnnnn`

`_fp_div_significand_calc:wnnnnnnnn` $\langle 10^6 + Q_A \rangle$; $\langle A_1 \rangle \langle A_2 \rangle$; $\{\langle A_3 \rangle\}$
 $\{\langle A_4 \rangle\} \{\langle Z_1 \rangle\} \{\langle Z_2 \rangle\} \{\langle Z_3 \rangle\} \{\langle Z_4 \rangle\} \{\langle continuation \rangle\}$

expands to

$$\langle 10^6 + Q_A \rangle \langle continuation \rangle ; \langle B_1 \rangle \langle B_2 \rangle ; \{\langle B_3 \rangle\} \{\langle B_4 \rangle\} \{\langle Z_1 \rangle\} \{\langle Z_2 \rangle\} \{\langle Z_3 \rangle\} \{\langle Z_4 \rangle\}$$

where $B = 10^4 A - Q_A \cdot Z$. This function is also used to compute C , D , E (with the input shifted accordingly), and is used in `l3fp-expo`.

We know that $0 < Q_A < 1.8 \cdot 10^5$, so the product of Q_A with each Z_i is within $\text{T}_{\text{E}}\text{X}$'s bounds. However, it is a little bit too large for our purposes: we would not be able to use the usual trick of adding a large power of 10 to ensure that the number of digits is fixed.

The bound on Q_A , implies that $10^6 + Q_A$ starts with the digit 1, followed by 0 or 1. We test, and call different auxiliaries for the two cases. An earlier implementation did the tests within the computation, but since we added a $\langle continuation \rangle$, this is not possible because the macro has 9 parameters.

The result we want is then (the overall power of 10 is arbitrary):

$$10^{-4}(\#2 - \#1 \cdot \#5 - 10 \cdot \langle i \rangle \cdot \#5\#6) + 10^{-8}(\#3 - \#1 \cdot \#6 - 10 \cdot \langle i \rangle \cdot \#7) \\ + 10^{-12}(\#4 - \#1 \cdot \#7 - 10 \cdot \langle i \rangle \cdot \#8) + 10^{-16}(-\#1 \cdot \#8),$$

where $\langle i \rangle$ stands for the 10^5 digit of Q_A , which is 0 or 1, and $\#1$, $\#2$, *etc.* are the parameters of either auxiliary. The factors of 10 come from the fact that $Q_A = 10 \cdot 10^4 \cdot \langle i \rangle + \#1$. As usual, to combine all the terms, we need to choose some shifts which must ensure that the number of digits of the second, third, and fourth terms are each fixed. Here, the positive contributions are at most 10^8 and the negative contributions can go up to 10^9 . Indeed, for the auxiliary with $\langle i \rangle = 1$, $\#1$ is at most 80000, leading to contributions of at worse $-8 \cdot 10^8 4$, while the other negative term is very small $< 10^6$ (except in the first expression, where we don't care about the number of digits); for the auxiliary with $\langle i \rangle = 0$, $\#1$ can go up to 99999, but there is no other negative term. Hence, a good choice is $2 \cdot 10^9$, which produces totals in the range $[10^9, 2.1 \cdot 10^9]$. We are flirting with $\text{T}_{\text{E}}\text{X}$'s limits once more.

```

13256 \cs_new:Npn \__fp_div_significand_calc:wwnnnnnnn #1#
13257 {
13258   \if_meaning:w 1 #1
13259     \exp_after:wN \__fp_div_significand_calc_i:wwnnnnnnn
13260   \else:
13261     \exp_after:wN \__fp_div_significand_calc_ii:wwnnnnnnn
13262   \fi:
13263 }
13264 \cs_new:Npn \__fp_div_significand_calc_i:wwnnnnnnn #1; #2;#3#4 #5#6#7#8 #9
13265 {
13266   1 1 #1
13267   #9 \exp_after:wN ;
13268   \__int_value:w \__int_eval:w \c__fp_Bigg_leading_shift_int
13269   + #2 - #1 * #5 - #5#60
13270   \exp_after:wN \__fp_pack_Bigg:NNNNNNw
13271   \__int_value:w \__int_eval:w \c__fp_Bigg_middle_shift_int
13272   + #3 - #1 * #6 - #70
13273   \exp_after:wN \__fp_pack_Bigg:NNNNNNw
13274   \__int_value:w \__int_eval:w \c__fp_Bigg_middle_shift_int
13275   + #4 - #1 * #7 - #80
13276   \exp_after:wN \__fp_pack_Bigg:NNNNNNw
13277   \__int_value:w \__int_eval:w \c__fp_Bigg_trailing_shift_int
13278   - #1 * #8 ;

```

```

13279     {#5}{#6}{#7}{#8}
13280   }
13281 \cs_new:Npn \__fp_div_significand_calc_ii:wwnnnnnnn #1; #2;#3#4 #5#6#7#8 #9
13282 {
13283   1 0 #1
13284   #9 \exp_after:wN ;
13285   \__int_value:w \__int_eval:w \c__fp_Bigg_leading_shift_int
13286   + #2 - #1 * #5
13287   \exp_after:wN \__fp_pack_Bigg:NNNNNNw
13288   \__int_value:w \__int_eval:w \c__fp_Bigg_middle_shift_int
13289   + #3 - #1 * #6
13290   \exp_after:wN \__fp_pack_Bigg:NNNNNNw
13291   \__int_value:w \__int_eval:w \c__fp_Bigg_middle_shift_int
13292   + #4 - #1 * #7
13293   \exp_after:wN \__fp_pack_Bigg:NNNNNNw
13294   \__int_value:w \__int_eval:w \c__fp_Bigg_trailing_shift_int
13295   - #1 * #8 ;
13296   {#5}{#6}{#7}{#8}
13297 }

```

(End definition for __fp_div_significand_calc:wwnnnnnnn, __fp_div_significand_calc_i:wwnnnnnnn, and __fp_div_significand_calc_ii:wwnnnnnnn.)

```

\__fp_div_significand_ii:wwn    \__fp_div_significand_ii:wwn ⟨y⟩ ; ⟨B1⟩ ; {⟨B2⟩} {⟨B3⟩} {⟨B4⟩} {⟨Z1⟩}
                                {⟨Z2⟩} {⟨Z3⟩} {⟨Z4⟩} ⟨continuations⟩ ⟨sign⟩

```

Compute Q_B by evaluating $\langle B_1 \rangle \langle B_2 \rangle 0 / y - 1$. The result will be output to the left, in an `__int_eval:w` which we start now. Once that is evaluated (and the other Q_i also, since later expansions are triggered by this one), a packing auxiliary takes care of placing the digits of Q_B in an appropriate way for the final addition to obtain Q . This auxiliary is also used to compute Q_C and Q_D with the inputs C and D instead of B .

```

13298 \cs_new:Npn \__fp_div_significand_ii:wwn #1; #2;#3
13299 {
13300   \exp_after:wN \__fp_div_significand_pack:NNN
13301   \__int_value:w \__int_eval:w
13302   \exp_after:wN \__fp_div_significand_calc:wwnnnnnnn
13303   \__int_value:w \__int_eval:w 999999 + #2 #3 0 / #1 ; #2 #3 ;
13304 }

```

(End definition for __fp_div_significand_ii:wwn.)

```

\__fp_div_significand_iii:wwnnnnn    \__fp_div_significand_iii:wwnnnnn ⟨y⟩ ; ⟨E1⟩ ; {⟨E2⟩} {⟨E3⟩} {⟨E4⟩}
                                       {⟨Z1⟩} {⟨Z2⟩} {⟨Z3⟩} {⟨Z4⟩} ⟨sign⟩

```

We compute $P \simeq 2E/Z$ by rounding $2E_1E_2/Z_1Z_2$. Note the first 0, which multiplies Q_D by 10: we will later add (roughly) $5 \cdot P$, which amounts to adding $P/2 \simeq E/Z$ to Q_D , the appropriate correction from a hypothetical Q_E .

```

13305 \cs_new:Npn \__fp_div_significand_iii:wwnnnnn #1; #2;#3#4#5 #6#7
13306 {
13307   0
13308   \exp_after:wN \__fp_div_significand_iv:wwnnnnnnn
13309   \__int_value:w \__int_eval:w ( 2 * #2 #3 ) / #6 #7 ; % <- P
13310   #2 ; {#3} {#4} {#5}
13311   {#6} {#7}
13312 }

```

(End definition for `_fp_div_significand_iii:wwnnnnn`.)

`_fp_div_significand_iv:wwnnnnnn`
`_fp_div_significand_v:NNw`
`_fp_div_significand_vi:Nw`

`_fp_div_significand_iv:wwnnnnnn` $\langle P \rangle$; $\langle E_1 \rangle$; $\{\langle E_2 \rangle\}$ $\{\langle E_3 \rangle\}$ $\{\langle E_4 \rangle\}$
 $\{\langle Z_1 \rangle\}$ $\{\langle Z_2 \rangle\}$ $\{\langle Z_3 \rangle\}$ $\{\langle Z_4 \rangle\}$ $\langle sign \rangle$

This adds to the current expression $(10^7 + 10 \cdot Q_D)$ a contribution of $5 \cdot P + \text{sign}(T)$ with $T = 2E - PZ$. This amounts to adding $P/2$ to Q_D , with an extra $\langle \text{rounding} \rangle$ digit. This $\langle \text{rounding} \rangle$ digit is 0 or 5 if T does not contribute, *i.e.*, if $0 = T = 2E - PZ$, in other words if $10^{16}A/Z$ is an integer or half-integer. Otherwise it is in the appropriate range, $[1, 4]$ or $[6, 9]$. This is precise enough for rounding purposes (in any mode).

It seems an overkill to compute T exactly as I do here, but I see no faster way right now.

Once more, we need to be careful and show that the calculation $\#1 \cdot \#6\#7$ below does not cause an overflow: naively, P can be up to 35, and $\#6\#7$ up to 10^8 , but both cannot happen simultaneously. To show that things are fine, we split in two (non-disjoint) cases.

- For $P < 10$, the product obeys $P \cdot \#6\#7 < 10^8 \cdot P < 10^9$.
- For large $P \geq 3$, the rounding error on P , which is at most 1, is less than a factor of 2, hence $P \leq 4E/Z$. Also, $\#6\#7 \leq 10^8 \cdot Z$, hence $P \cdot \#6\#7 \leq 4E \cdot 10^8 < 10^9$.

Both inequalities could be made tighter if needed.

Note however that $P \cdot \#8\#9$ may overflow, since the two factors are now independent, and the result may reach $3.5 \cdot 10^9$. Thus we compute the two lower levels separately. The rest is standard, except that we use $+$ as a separator (ending integer expressions explicitly). T is negative if the first character is $-$, it is positive if the first character is neither 0 nor $-$. It is also positive if the first character is 0 and second argument of `_fp_div_significand_vi:Nw`, a sum of several terms, is also zero. Otherwise, there was an exact agreement: $T = 0$.

```

13313 \cs_new:Npn \_fp_div_significand_iv:wwnnnnnn #1; #2; #3#4#5 #6#7#8#9
13314 {
13315   + 5 * #1
13316   \exp_after:wN \_fp_div_significand_vi:Nw
13317   \_int_value:w \_int_eval:w -20 + 2*#2#3 - #1*#6#7 +
13318   \exp_after:wN \_fp_div_significand_v:NN
13319   \_int_value:w \_int_eval:w 199980 + 2*#4 - #1*#8 +
13320   \exp_after:wN \_fp_div_significand_v:NN
13321   \_int_value:w \_int_eval:w 200000 + 2*#5 - #1*#9 ;
13322 }
13323 \cs_new:Npn \_fp_div_significand_v:NN #1#2 { #1#2 \_int_eval_end: + }
13324 \cs_new:Npn \_fp_div_significand_vi:Nw #1#2;
13325 {
13326   \if_meaning:w 0 #1
13327   \if_int_compare:w \_int_eval:w #2 > 0 + 1 \fi:
13328   \else:
13329   \if_meaning:w - #1 - \else: + \fi: 1
13330   \fi:
13331   ;
13332 }

```

(End definition for `_fp_div_significand_iv:wwnnnnnn`, `_fp_div_significand_v:NNw`, and `_fp_div_significand_vi:Nw`.)

`_fp_div_significand_pack:NNN` At this stage, we are in the following situation: \TeX is in the process of expanding several integer expressions, thus functions at the bottom expand before those above.

```
\_fp_div_significand_test_o:w 10^6 + Q_A \_fp_div_significand_-
pack:NNN 10^6 + Q_B \_fp_div_significand_pack:NNN 10^6 + Q_C \_fp_-
div_significand_pack:NNN 10^7 + 10 \cdot Q_D + 5 \cdot P + \varepsilon ; \langle sign \rangle
```

Here, $\varepsilon = \text{sign}(T)$ is 0 in case $2E = PZ$, 1 in case $2E > PZ$, which means that P was the correct value, but not with an exact quotient, and -1 if $2E < PZ$, *i.e.*, P was an overestimate. The packing function we define now does nothing special: it removes the 10^6 and carries two digits (for the 10^5 's and the 10^4 's).

```
13333 \cs_new:Npn \_fp_div_significand_pack:NNN 1 #1 #2 { + #1 #2 ; }
```

(End definition for `_fp_div_significand_pack:NNN`.)

```
\_fp_div_significand_test_o:w \_fp_div_significand_test_o:w 1 0 \langle 5d \rangle ; \langle 4d \rangle ; \langle 4d \rangle ; \langle 5d \rangle ; \langle sign \rangle
```

The reason we know that the first two digits are 1 and 0 is that the final result is known to be between 0.1 (inclusive) and 10, hence \widetilde{Q}_A (the tilde denoting the contribution from the other Q_i) is at most 99999, and $10^6 + \widetilde{Q}_A = 10 \dots$.

It is now time to round. This depends on how many digits the final result will have.

```
13334 \cs_new:Npn \_fp_div_significand_test_o:w 10 #1
13335 {
13336   \if_meaning:w 0 #1
13337     \exp_after:wN \_fp_div_significand_small_o:wwwNNNNwN
13338   \else:
13339     \exp_after:wN \_fp_div_significand_large_o:wwwNNNNwN
13340   \fi:
13341   #1
13342 }
```

(End definition for `_fp_div_significand_test_o:w`.)

```
\_fp_div_significand_small_o:wwwNNNNwN \_fp_div_significand_small_o:wwwNNNNwN 0 \langle 4d \rangle ; \langle 4d \rangle ; \langle 4d \rangle ; \langle 5d \rangle
; \langle final sign \rangle
```

Standard use of the functions `_fp_basics_pack_low:NNNNw` and `_fp_basics_pack_high:NNNNw`. We finally get to use the $\langle final\ sign \rangle$ which has been sitting there for a while.

```
13343 \cs_new:Npn \_fp_div_significand_small_o:wwwNNNNwN
13344   0 #1; #2; #3; #4#5#6#7#8; #9
13345 {
13346   \exp_after:wN \_fp_basics_pack_high:NNNNw
13347   \_int_value:w \_int_eval:w 1 #1#2
13348   \exp_after:wN \_fp_basics_pack_low:NNNNw
13349   \_int_value:w \_int_eval:w 1 #3#4#5#6#7
13350   + \_fp_round:NNN #9 #7 #8
13351   \exp_after:wN ;
13352 }
```

(End definition for `_fp_div_significand_small_o:wwwNNNNwN`.)

```

\__fp_div_significand_large_o:wwwNNNNwN \__fp_div_significand_large_o:wwwNNNNwN <5d> ; <4d> ; <4d> ; <5d> ;
<sign>

```

We know that the final result cannot reach 10, hence 1#1#2, together with contributions from the level below, cannot reach $2 \cdot 10^9$. For rounding, we build the *<rounding digit>* from the last two of our 18 digits.

```

13353 \cs_new:Npn \__fp_div_significand_large_o:wwwNNNNwN
13354 #1; #2; #3; #4#5#6#7#8; #9
13355 {
13356   + 1
13357   \exp_after:wN \__fp_basics_pack_weird_high:NNNNNNNNw
13358   \__int_value:w \__int_eval:w 1 #1 #2
13359   \exp_after:wN \__fp_basics_pack_weird_low:NNNNw
13360   \__int_value:w \__int_eval:w 1 #3 #4 #5 #6 +
13361   \exp_after:wN \__fp_round:NNN
13362   \exp_after:wN #9
13363   \exp_after:wN #6
13364   \__int_value:w \__fp_round_digit:Nw #7 #8 ;
13365   \exp_after:wN ;
13366 }

```

(End definition for __fp_div_significand_large_o:wwwNNNNwN.)

25.5 Square root

__fp_sqrt_o:w Zeros are unchanged: $\sqrt{-0} = -0$ and $\sqrt{+0} = +0$. Negative numbers (other than -0) have no real square root. Positive infinity, and `nan`, are unchanged. Finally, for normal positive numbers, there is some work to do.

```

13367 \cs_new:Npn \__fp_sqrt_o:w #1 \s__fp \__fp_chk:w #2#3#4; @
13368 {
13369   \if_meaning:w 0 #2 \__fp_case_return_same_o:w \fi:
13370   \if_meaning:w 2 #3
13371     \__fp_case_use:nw { \__fp_invalid_operation_o:nw { sqrt } }
13372   \fi:
13373   \if_meaning:w 1 #2 \else: \__fp_case_return_same_o:w \fi:
13374   \__fp_sqrt_npos_o:w
13375   \s__fp \__fp_chk:w #2 #3 #4;
13376 }

```

(End definition for __fp_sqrt_o:w.)

__fp_sqrt_npos_o:w Prepare __fp_sanitize:Nw to receive the final sign 0 (the result is always positive) and the exponent, equal to half of the exponent #1 of the argument. If the exponent #1 is even, find a first approximation of the square root of the significand $10^8 a_1 + a_2 = 10^8 \#2\#3 + \#4\#5$ through Newton's method, starting at $x = 57234133 \simeq 10^{7.75}$. Otherwise, first shift the significand of of the argument by one digit, getting $a'_1 \in [10^6, 10^7)$ instead of $[10^7, 10^8)$, then use Newton's method starting at $17782794 \simeq 10^{7.25}$.

```

13377 \cs_new:Npn \__fp_sqrt_npos_o:w \s__fp \__fp_chk:w 1 0 #1#2#3#4#5;
13378 {
13379   \exp_after:wN \__fp_sanitize:Nw
13380   \exp_after:wN 0
13381   \__int_value:w \__int_eval:w
13382   \if_int_odd:w #1 \exp_stop_f:
13383     \exp_after:wN \__fp_sqrt_npos_auxi_o:wwwNNN

```

```

13384      \fi:
13385      #1 / 2
13386      \__fp_sqrt_Newton_o:wnn 56234133; 0; {#2#3} {#4#5} 0
13387    }
13388    \cs_new:Npn \__fp_sqrt_npos_auxii_o:wnnnN #1 / 2 #2; 0; #3#4#5
13389    {
13390      ( #1 + 1 ) / 2
13391      \__fp_pack_eight:wNNNNNNNN
13392      \__fp_sqrt_npos_auxii_o:wnnnNNNNN
13393      ;
13394      0 #3 #4
13395    }
13396    \cs_new:Npn \__fp_sqrt_npos_auxii_o:wnnnNNNNN #1; #2#3#4#5#6#7#8#9
13397    { \__fp_sqrt_Newton_o:wnn 17782794; 0; {#1} {#2#3#4#5#6#7#8#9} }

```

(End definition for `__fp_sqrt_npos_o:w`, `__fp_sqrt_npos_auxii_o:wnnnN`, and `__fp_sqrt_npos_auxii_o:wnnnNNNNN`.)

`__fp_sqrt_Newton_o:wnn`

Newton's method maps $x \mapsto [(x + [10^8 a_1/x])/2]$ in each iteration, where $[b/c]$ denotes ε -TeX's division. This division rounds the real number b/c to the closest integer, rounding ties away from zero, hence when c is even, $b/c - 1/2 + 1/c \leq [b/c] \leq b/c + 1/2$ and when c is odd, $b/c - 1/2 + 1/(2c) \leq [b/c] \leq b/c + 1/2 - 1/(2c)$. For all c , $b/c - 1/2 + 1/(2c) \leq [b/c] \leq b/c + 1/2$.

Let us prove that the method converges when implemented with ε -TeX integer division, for any $10^6 \leq a_1 < 10^8$ and starting value $10^6 \leq x < 10^8$. Using the inequalities above and the arithmetic-geometric inequality $(x + t)/2 \geq \sqrt{xt}$ for $t = 10^8 a_1/x$, we find

$$x' = \left\lceil \frac{x + [10^8 a_1/x]}{2} \right\rceil \geq \frac{x + 10^8 a_1/x - 1/2 + 1/(2x)}{2} \geq \sqrt{10^8 a_1} - \frac{1}{4} + \frac{1}{4x}.$$

After any step of iteration, we thus have $\delta = x - \sqrt{10^8 a_1} \geq -0.25 + 0.25 \cdot 10^{-8}$. The new difference $\delta' = x' - \sqrt{10^8 a_1}$ after one step is bounded above as

$$x' - \sqrt{10^8 a_1} \leq \frac{x + 10^8 a_1/x + 1/2}{2} + \frac{1}{2} - \sqrt{10^8 a_1} \leq \frac{\delta}{2} \frac{\delta}{\sqrt{10^8 a_1} + \delta} + \frac{3}{4}.$$

For $\delta > 3/2$, this last expression is $\leq \delta/2 + 3/4 < \delta$, hence δ decreases at each step: since all x are integers, δ must reach a value $-1/4 < \delta \leq 3/2$. In this range of values, we get $\delta' \leq \frac{3}{4} \frac{3}{2\sqrt{10^8 a_1}} + \frac{3}{4} \leq 0.75 + 1.125 \cdot 10^{-7}$. We deduce that the difference $\delta = x - \sqrt{10^8 a_1}$ eventually reaches a value in the interval $[-0.25 + 0.25 \cdot 10^{-8}, 0.75 + 11.25 \cdot 10^{-8}]$, whose width is $1 + 11 \cdot 10^{-8}$. The corresponding interval for x may contain two integers, hence x might oscillate between those two values.

However, the fact that $x \mapsto x - 1$ and $x - 1 \mapsto x$ puts stronger constraints, which are not compatible: the first implies

$$x + [10^8 a_1/x] \leq 2x - 2$$

hence $10^8 a_1/x \leq x - 3/2$, while the second implies

$$x - 1 + [10^8 a_1/(x - 1)] \geq 2x - 1$$

hence $10^8 a_1/(x - 1) \geq x - 1/2$. Combining the two inequalities yields $x^2 - 3x/2 \geq 10^8 a_1 \geq x - 3x/2 + 1/2$, which cannot hold. Therefore, the iteration always converges to a single

integer x . To stop the iteration when two consecutive results are equal, the function `_fp_sqrt_Newton_o:wnn` receives the newly computed result as `#1`, the previous result as `#2`, and a_1 as `#3`. Note that ε -TeX combines the computation of a multiplication and a following division, thus avoiding overflow in `#3 * 100000000 / #1`. In any case, the result is within $[10^7, 10^8]$.

```

13398 \cs_new:Npn \_fp_sqrt_Newton_o:wnn #1; #2; #3
13399 {
13400   \if_int_compare:w #1 = #2 \exp_stop_f:
13401     \exp_after:wN \_fp_sqrt_auxi_o:NNNNwnnnN
13402     \_int_value:w \_int_eval:w 9999 9999 +
13403     \exp_after:wN \_fp_use_none_until_s:w
13404   \fi:
13405   \exp_after:wN \_fp_sqrt_Newton_o:wnn
13406   \_int_value:w \_int_eval:w (#1 + #3 * 1 0000 0000 / #1) / 2 ;
13407   #1; {#3}
13408 }

```

(End definition for `_fp_sqrt_Newton_o:wnn`.)

`_fp_sqrt_auxi_o:NNNNwnnnN`

This function is followed by $10^8 + x - 1$, which has 9 digits starting with 1, then ; $\{ \langle a_1 \rangle \} \{ \langle a_2 \rangle \} \langle a' \rangle$. Here, $x \simeq \sqrt{10^8 a_1}$ and we want to estimate the square root of $a = 10^{-8} a_1 + 10^{-16} a_2 + 10^{-17} a'$. We set up an initial underestimate

$$y = (x - 1)10^{-8} + 0.2499998875 \cdot 10^{-8} \lesssim \sqrt{a}.$$

From the inequalities shown earlier, we know that $y \leq \sqrt{10^{-8} a_1} \leq \sqrt{a}$ and that $\sqrt{10^{-8} a_1} \leq y + 10^{-8} + 11 \cdot 10^{-16}$ hence (using $0.1 \leq y \leq \sqrt{a} \leq 1$)

$$a - y^2 \leq 10^{-8} a_1 + 10^{-8} - y^2 \leq (y + 10^{-8} + 11 \cdot 10^{-16})^2 - y^2 + 10^{-8} < 3.2 \cdot 10^{-8},$$

and $\sqrt{a} - y = (a - y^2) / (\sqrt{a} + y) \leq 16 \cdot 10^{-8}$. Next, `_fp_sqrt_auxii_o:NnnnnnnnnN` will be called several times to get closer and closer underestimates of \sqrt{a} . By construction, the underestimates y are always increasing, $a - y^2 < 3.2 \cdot 10^{-8}$ for all. Also, $y < 1$.

```

13409 \cs_new:Npn \_fp_sqrt_auxi_o:NNNNwnnnN 1 #1#2#3#4#5;
13410 {
13411   \_fp_sqrt_auxii_o:NnnnnnnnnN
13412   \_fp_sqrt_auxiii_o:wnnnnnnnnn
13413   {#1#2#3#4} {#5} {2499} {9988} {7500}
13414 }

```

(End definition for `_fp_sqrt_auxi_o:NNNNwnnnN`.)

`_fp_sqrt_auxii_o:NnnnnnnnnN`

This receives a continuation function `#1`, then five blocks of 4 digits for y , then two 8-digit blocks and a single digit for a . A common estimate of $\sqrt{a} - y = (a - y^2) / (\sqrt{a} + y)$ is $(a - y^2) / (2y)$, which leads to alternating overestimates and underestimates. We tweak this, to only work with underestimates (no need then to worry about signs in the computation). Each step finds the largest integer $j \leq 6$ such that $10^{4j}(a - y^2) < 2 \cdot 10^8$, then computes the integer (with ε -TeX's rounding division)

$$10^{4j} z = \left[([10^{4j}(a - y^2)] - 257) \cdot (0.5 \cdot 10^8) / [10^8 y + 1] \right].$$

The choice of j ensures that $10^{4j} z < 2 \cdot 10^8 \cdot 0.5 \cdot 10^8 / 10^7 = 10^9$, thus $10^9 + 10^{4j} z$ has exactly 10 digits, does not overflow TeX's integer range, and starts with 1. Incidentally, since all $a - y^2 \leq 3.2 \cdot 10^{-8}$, we know that $j \geq 3$.

Let us show that z is an underestimate of $\sqrt{a}-y$. On the one hand, $\sqrt{a}-y \leq 16 \cdot 10^{-8}$ because this holds for the initial y and values of y can only increase. On the other hand, the choice of j implies that $\sqrt{a}-y \leq 5(\sqrt{a}+y)(\sqrt{a}-y) = 5(a-y^2) < 10^{9-4j}$. For $j = 3$, the first bound is better, while for larger j , the second bound is better. For all $j \in [3, 6]$, we find $\sqrt{a}-y < 16 \cdot 10^{-2j}$. From this, we deduce that

$$10^{4j}(\sqrt{a}-y) = \frac{10^{4j}(a-y^2-(\sqrt{a}-y)^2)}{2y} \geq \frac{\lfloor 10^{4j}(a-y^2) \rfloor - 257}{2 \cdot 10^{-8} \lfloor 10^8 y + 1 \rfloor} + \frac{1}{2}$$

where we have replaced the bound $10^{4j}(16 \cdot 10^{-2j}) = 256$ by 257 and extracted the corresponding term $1/(2 \cdot 10^{-8} \lfloor 10^8 y + 1 \rfloor) \geq 1/2$. Given that ε -TeX's integer division obeys $\lfloor b/c \rfloor \leq b/c + 1/2$, we deduce that $10^{4j}z \leq 10^{4j}(\sqrt{a}-y)$, hence $y+z \leq \sqrt{a}$ is an underestimate of \sqrt{a} , as claimed. One implementation detail: because the computation involves $-4*4 - 2*3*5 - 2*2*6$ which may be as low as $-5 \cdot 10^8$, we need to use the `pack_big` functions, and the big shifts.

```

13415 \cs_new:Npn \__fp_sqrt_auxii_o:NnnnnnnN #1 #2#3#4#5#6 #7#8#9
13416 {
13417   \exp_after:wN #1
13418   \__int_value:w \__int_eval:w \c__fp_big_leading_shift_int
13419   + #7 - #2 * #2
13420   \exp_after:wN \__fp_pack_big:NNNNNNw
13421   \__int_value:w \__int_eval:w \c__fp_big_middle_shift_int
13422   - 2 * #2 * #3
13423   \exp_after:wN \__fp_pack_big:NNNNNNw
13424   \__int_value:w \__int_eval:w \c__fp_big_middle_shift_int
13425   + #8 - #3 * #3 - 2 * #2 * #4
13426   \exp_after:wN \__fp_pack_big:NNNNNNw
13427   \__int_value:w \__int_eval:w \c__fp_big_middle_shift_int
13428   - 2 * #3 * #4 - 2 * #2 * #5
13429   \exp_after:wN \__fp_pack_big:NNNNNNw
13430   \__int_value:w \__int_eval:w \c__fp_big_middle_shift_int
13431   + #9 000 0000 - #4 * #4 - 2 * #3 * #5 - 2 * #2 * #6
13432   \exp_after:wN \__fp_pack_big:NNNNNNw
13433   \__int_value:w \__int_eval:w \c__fp_big_middle_shift_int
13434   - 2 * #4 * #5 - 2 * #3 * #6
13435   \exp_after:wN \__fp_pack_big:NNNNNNw
13436   \__int_value:w \__int_eval:w \c__fp_big_middle_shift_int
13437   - #5 * #5 - 2 * #4 * #6
13438   \exp_after:wN \__fp_pack_big:NNNNNNw
13439   \__int_value:w \__int_eval:w
13440   \c__fp_big_middle_shift_int
13441   - 2 * #5 * #6
13442   \exp_after:wN \__fp_pack_big:NNNNNNw
13443   \__int_value:w \__int_eval:w
13444   \c__fp_big_trailing_shift_int
13445   - #6 * #6 ;
13446   % (
13447   - 257 ) * 5000 0000 / (#2#3 + 1) + 10 0000 0000 ;
13448   {#2}{#3}{#4}{#5}{#6} {#7}{#8}{#9}
13449 }

```

(End definition for `__fp_sqrt_auxii_o:NnnnnnnN`.)

```

\__fp_sqrt_auxiii_o:wnnnnnnnn
\__fp_sqrt_auxiv_o:NNNNNw
\__fp_sqrt_auxv_o:NNNNNw
\__fp_sqrt_auxvi_o:NNNNNw
\__fp_sqrt_auxvii_o:NNNNNw

```

We receive here the difference $a - y^2 = d = \sum_i d_i \cdot 10^{-4i}$, as $\langle d_2 \rangle ; \{\langle d_3 \rangle\} \dots \{\langle d_{10} \rangle\}$, where each block has 4 digits, except $\langle d_2 \rangle$. This function finds the largest $j \leq 6$ such that $10^{4j}(a - y^2) < 2 \cdot 10^8$, then leaves an open parenthesis and the integer $\lfloor 10^{4j}(a - y^2) \rfloor$ in an integer expression. The closing parenthesis is provided by the caller `__fp_sqrt_auxii_o:NNnnnnnnN`, which completes the expression

$$10^{4j}z = \left[(\lfloor 10^{4j}(a - y^2) \rfloor - 257) \cdot (0.5 \cdot 10^8) / \lfloor 10^8 y + 1 \rfloor \right]$$

for an estimate of $10^{4j}(\sqrt{a} - y)$. If $d_2 \geq 2$, $j = 3$ and the `auxiv` auxiliary receives $10^{12}z$. If $d_2 \leq 1$ but $10^4 d_2 + d_3 \geq 2$, $j = 4$ and the `auxv` auxiliary is called, and receives $10^{16}z$, and so on. In all those cases, the `auxviii` auxiliary is set up to add z to y , then go back to the `auxii` step with continuation `auxiii` (the function we are currently describing). The maximum value of j is 6, regardless of whether $10^{12}d_2 + 10^8 d_3 + 10^4 d_4 + d_5 \geq 1$. In this last case, we detect when $10^{24}z < 10^7$, which essentially means $\sqrt{a} - y \lesssim 10^{-17}$: once this threshold is reached, there is enough information to find the correctly rounded \sqrt{a} with only one more call to `__fp_sqrt_auxii_o:NNnnnnnnN`. Note that the iteration cannot be stuck before reaching $j = 6$, because for $j < 6$, one has $2 \cdot 10^8 \leq 10^{4(j+1)}(a - y^2)$, hence

$$10^{4j}z \geq \frac{(20000 - 257)(0.5 \cdot 10^8)}{\lfloor 10^8 y + 1 \rfloor} \geq (20000 - 257) \cdot 0.5 > 0.$$

```

13450 \cs_new:Npn \__fp_sqrt_auxiii_o:wnnnnnnnn
13451   #1; #2#3#4#5#6#7#8#9
13452   {
13453     \if_int_compare:w #1 > 1 \exp_stop_f:
13454     \exp_after:wN \__fp_sqrt_auxiv_o:NNNNNw
13455     \__int_value:w \__int_eval:w (#1#2 %)
13456   \else:
13457     \if_int_compare:w #1#2 > 1 \exp_stop_f:
13458     \exp_after:wN \__fp_sqrt_auxv_o:NNNNNw
13459     \__int_value:w \__int_eval:w (#1#2#3 %)
13460   \else:
13461     \if_int_compare:w #1#2#3 > 1 \exp_stop_f:
13462     \exp_after:wN \__fp_sqrt_auxvi_o:NNNNNw
13463     \__int_value:w \__int_eval:w (#1#2#3#4 %)
13464   \else:
13465     \exp_after:wN \__fp_sqrt_auxvii_o:NNNNNw
13466     \__int_value:w \__int_eval:w (#1#2#3#4#5 %)
13467   \fi:
13468   \fi:
13469   \fi:
13470 }
13471 \cs_new:Npn \__fp_sqrt_auxiv_o:NNNNNw 1#1#2#3#4#5#6;
13472   { \__fp_sqrt_auxviii_o:nnnnnnn {#1#2#3#4#5#6} {00000000} }
13473 \cs_new:Npn \__fp_sqrt_auxv_o:NNNNNw 1#1#2#3#4#5#6;
13474   { \__fp_sqrt_auxviii_o:nnnnnnn {000#1#2#3#4#5} {#60000} }
13475 \cs_new:Npn \__fp_sqrt_auxvi_o:NNNNNw 1#1#2#3#4#5#6;
13476   { \__fp_sqrt_auxviii_o:nnnnnnn {0000000#1} {#2#3#4#5#6} }
13477 \cs_new:Npn \__fp_sqrt_auxvii_o:NNNNNw 1#1#2#3#4#5#6;
13478   {
13479     \if_int_compare:w #1#2 = 0 \exp_stop_f:
13480     \exp_after:wN \__fp_sqrt_auxx_o:NNnnnnnn
13481   \fi:

```

```

13482     \_fp_sqrt_auxviii_o:nnnnnnnn {00000000} {000#1#2#3#4#5}
13483   }

```

(End definition for _fp_sqrt_auxiii_o:wnnnnnnn and others.)

_fp_sqrt_auxviii_o:nnnnnnnn Simply add the two 8-digit blocks of z , aligned to the last four of the five 4-digit blocks of y , then call the auxii auxiliary to evaluate $y'^2 = (y + z)^2$.

```

13484 \cs_new:Npn \_fp_sqrt_auxviii_o:nnnnnnnn #1#2 #3#4#5#6#7
13485 {
13486   \exp_after:wN \_fp_sqrt_auxix_o:wnwnw
13487   \_int_value:w \_int_eval:w #3
13488   \exp_after:wN \_fp_basics_pack_low:NNNNw
13489   \_int_value:w \_int_eval:w #1 + 1#4#5
13490   \exp_after:wN \_fp_basics_pack_low:NNNNw
13491   \_int_value:w \_int_eval:w #2 + 1#6#7 ;
13492 }
13493 \cs_new:Npn \_fp_sqrt_auxix_o:wnwnw #1; #2#3; #4#5;
13494 {
13495   \_fp_sqrt_auxii_o:NnnnnnnnN
13496   \_fp_sqrt_auxiii_o:wnnnnnnnnn {#1}{#2}{#3}{#4}{#5}
13497 }

```

(End definition for _fp_sqrt_auxviii_o:nnnnnnnn and _fp_sqrt_auxix_o:wnwnw.)

_fp_sqrt_auxx_o:Nnnnnnnnn At this stage, $j = 6$ and $10^{24}z < 10^7$, hence
 _fp_sqrt_auxxi_o:wwnnN

$$10^7 + 1/2 > 10^{24}z + 1/2 \geq (10^{24}(a - y^2) - 258) \cdot (0.5 \cdot 10^8) / (10^8y + 1),$$

then $10^{24}(a - y^2) - 258 < 2(10^7 + 1/2)(y + 10^{-8})$, and

$$10^{24}(a - y^2) < (10^7 + 1290.5)(1 + 10^{-8}/y)(2y) < (10^7 + 1290.5)(1 + 10^{-7})(y + \sqrt{a}),$$

which finally implies $0 \leq \sqrt{a} - y < 0.2 \cdot 10^{-16}$. In particular, y is an underestimate of \sqrt{a} and $y + 0.5 \cdot 10^{-16}$ is a (strict) overestimate. There is at exactly one multiple m of $0.5 \cdot 10^{-16}$ in the interval $[y, y + 0.5 \cdot 10^{-16})$. If $m^2 > a$, then the square root is inexact and is obtained by rounding $m - \epsilon$ to a multiple of 10^{-16} (the precise shift $0 < \epsilon < 0.5 \cdot 10^{-16}$ is irrelevant for rounding). If $m^2 = a$ then the square root is exactly m , and there is no rounding. If $m^2 < a$ then we round $m + \epsilon$. For now, discard a few irrelevant arguments #1, #2, #3, and find the multiple of $0.5 \cdot 10^{-16}$ within $[y, y + 0.5 \cdot 10^{-16})$; rather, only the last 4 digits #8 of y are considered, and we do not perform any carry yet. The auxxi auxiliary sets up auxii with a continuation function auxxii instead of auxiii as before. To prevent auxii from giving a negative results $a - m^2$, we compute $a + 10^{-16} - m^2$ instead, always positive since $m < \sqrt{a} + 0.5 \cdot 10^{-16}$ and $a \leq 1 - 10^{-16}$.

```

13498 \cs_new:Npn \_fp_sqrt_auxx_o:Nnnnnnnnn #1#2#3 #4#5#6#7#8
13499 {
13500   \exp_after:wN \_fp_sqrt_auxxi_o:wwnnN
13501   \_int_value:w \_int_eval:w
13502     (#8 + 2499) / 5000 * 5000 ;
13503   {#4} {#5} {#6} {#7} ;
13504 }
13505 \cs_new:Npn \_fp_sqrt_auxxi_o:wwnnN #1; #2; #3#4#5
13506 {
13507   \_fp_sqrt_auxii_o:NnnnnnnnN

```

```

13508     \__fp_sqrt_auxxii_o:nnnnnnnnnw
13509     #2 {#1}
13510     {#3} { #4 + 1 } #5
13511 }

```

(End definition for __fp_sqrt_auxx_o:nnnnnnnn and __fp_sqrt_auxxi_o:wnnnN.)

__fp_sqrt_auxxii_o:nnnnnnnnnw
__fp_sqrt_auxxiii_o:w

The difference $0 \leq a + 10^{-16} - m^2 \leq 10^{-16} + (\sqrt{a} - m)(\sqrt{a} + m) \leq 2 \cdot 10^{-16}$ was just computed: its first 8 digits vanish, as do the next four, #1, and most of the following four, #2. The guess m is an overestimate if $a + 10^{-16} - m^2 < 10^{-16}$, that is, #1#2 vanishes. Otherwise it is an underestimate, unless $a + 10^{-16} - m^2 = 10^{-16}$ exactly. For an underestimate, call the auxxiv function with argument 9998. For an exact result call it with 9999, and for an overestimate call it with 10000.

```

13512 \cs_new:Npn \__fp_sqrt_auxxii_o:nnnnnnnnnw 0; #1#2#3#4#5#6#7#8 #9;
13513 {
13514   \if_int_compare:w #1#2 > 0 \exp_stop_f:
13515   \if_int_compare:w #1#2 = 1 \exp_stop_f:
13516   \if_int_compare:w #3#4 = 0 \exp_stop_f:
13517   \if_int_compare:w #5#6 = 0 \exp_stop_f:
13518   \if_int_compare:w #7#8 = 0 \exp_stop_f:
13519   \__fp_sqrt_auxxiii_o:w
13520   \fi:
13521   \fi:
13522   \fi:
13523   \fi:
13524   \exp_after:wN \__fp_sqrt_auxxiv_o:wnnnnnnnN
13525   \__int_value:w 9998
13526   \else:
13527   \exp_after:wN \__fp_sqrt_auxxiv_o:wnnnnnnnN
13528   \__int_value:w 10000
13529   \fi:
13530   ;
13531 }
13532 \cs_new:Npn \__fp_sqrt_auxxiii_o:w \fi: \fi: \fi: \fi: #1 \fi: ;
13533 {
13534   \fi: \fi: \fi: \fi: \fi:
13535   \__fp_sqrt_auxxiv_o:wnnnnnnnN 9999 ;
13536 }

```

(End definition for __fp_sqrt_auxxii_o:nnnnnnnnnw and __fp_sqrt_auxxiii_o:w.)

__fp_sqrt_auxxiv_o:wnnnnnnnN

This receives 9998, 9999 or 10000 as #1 when m is an underestimate, exact, or an overestimate, respectively. Then comes m as five blocks of 4 digits, but where the last block #6 may be 0, 5000, or 10000. In the latter case, we need to add a carry, unless m is an overestimate (#1 is then 10000). Then comes a as three arguments. Rounding is done by __fp_round:NNN, whose first argument is the final sign 0 (square roots are positive). We fake its second argument. It should be the last digit kept, but this is only used when ties are “rounded to even”, and only when the result is exactly half-way between two representable numbers rational square roots of numbers with 16 significant digits have: this situation never arises for the square root, as any exact square root of a 16 digit number has at most 8 significant digits. Finally, the last argument is the next digit, possibly shifted by 1 when there are further nonzero digits. This is achieved by __fp_round_digit:Nw, which receives (after removal of the 10000’s digit) one of 0000, 0001, 4999, 5000, 5001, or 9999, which it converts to 0, 1, 4, 5, 6, and 9, respectively.


```

13537 \cs_new:Npn \__fp_sqrt_auxxiv_o:wnnnnnnN #1; #2#3#4#5#6 #7#8#9
13538 {
13539   \exp_after:wN \__fp_basics_pack_high:NNNNw
13540   \__int_value:w \__int_eval:w 1 0000 0000 + #2#3
13541   \exp_after:wN \__fp_basics_pack_low:NNNNw
13542   \__int_value:w \__int_eval:w 1 0000 0000
13543   + #4#5
13544   \if_int_compare:w #6 > #1 \exp_stop_f: + 1 \fi:
13545   + \exp_after:wN \__fp_round:NNN
13546   \exp_after:wN 0
13547   \exp_after:wN 0
13548   \__int_value:w
13549   \exp_after:wN \use_i:nn
13550   \exp_after:wN \__fp_round_digit:Nw
13551   \__int_value:w \__int_eval:w #6 + 19999 - #1 ;
13552   \exp_after:wN ;
13553 }

```

(End definition for __fp_sqrt_auxxiv_o:wnnnnnnN.)

25.6 Setting the sign

`__fp_set_sign_o:w` This function is used for the unary minus and for `abs`. It leaves the sign of `nan` invariant, turns negative numbers (sign 2) to positive numbers (sign 0) and positive numbers (sign 0) to positive or negative numbers depending on `#1`. It also expands after itself in the input stream, just like `__fp_+_o:ww`.

```

13554 \cs_new:Npn \__fp_set_sign_o:w #1 \s__fp \__fp_chk:w #2#3#4; @
13555 {
13556   \exp_after:wN \__fp_exp_after_o:w
13557   \exp_after:wN \s__fp
13558   \exp_after:wN \__fp_chk:w
13559   \exp_after:wN #2
13560   \__int_value:w
13561   \if_case:w #3 \exp_stop_f: #1 \or: 1 \or: 0 \fi: \exp_stop_f:
13562   #4;
13563 }

```

(End definition for __fp_set_sign_o:w.)

13564 `</initex | package>`

26 l3fp-extended implementation

13565 `<*initex | package>`

13566 `<@@=fp>`

26.1 Description of fixed point numbers

This module provides a few functions to manipulate positive floating point numbers with extended precision (24 digits), but mostly provides functions for fixed-point numbers with this precision (24 digits). Those are used in the computation of Taylor series for the logarithm, exponential, and trigonometric functions. Since we eventually only care about the 16 first digits of the final result, some of the calculations are not performed

with the full 24-digit precision. In other words, the last two blocks of each fixed point number may be wrong as long as the error is small enough to be rounded away when converting back to a floating point number. The fixed point numbers are expressed as

$$\{\langle a_1 \rangle\} \{\langle a_2 \rangle\} \{\langle a_3 \rangle\} \{\langle a_4 \rangle\} \{\langle a_5 \rangle\} \{\langle a_6 \rangle\} ;$$

where each $\langle a_i \rangle$ is exactly 4 digits (ranging from 0000 to 9999), except $\langle a_1 \rangle$, which may be any “not-too-large” non-negative integer, with or without leading zeros. Here, “not-too-large” depends on the specific function (see the corresponding comments for details). Checking for overflow is the responsibility of the code calling those functions. The fixed point number a corresponding to the representation above is $a = \sum_{i=1}^6 \langle a_i \rangle \cdot 10^{-4i}$.

Most functions we define here have the form They perform the $\langle calculation \rangle$ on the two $\langle operands \rangle$, then feed the result (6 brace groups followed by a semicolon) to the $\langle continuation \rangle$, responsible for the next step of the calculation. Some functions only accept an N-type $\langle continuation \rangle$. This allows constructions such as

```
\__fp_fixed_add:wn \langle X_1 \rangle ; \langle X_2 \rangle ;
\__fp_fixed_mul:wn \langle X_3 \rangle ;
\__fp_fixed_add:wn \langle X_4 \rangle ;
```

to compute $(X_1 + X_2) \cdot X_3 + X_4$. This turns out to be very appropriate for computing continued fractions and Taylor series.

At the end of the calculation, the result is turned back to a floating point number using `__fp_fixed_to_float:wn`. This function has to change the exponent of the floating point number: it must be used after starting an integer expression for the overall exponent of the result.

26.2 Helpers for numbers with extended precision

`\c__fp_one_fixed_tl` The fixed-point number 1, used in `l3fp-expo`.

```
13567 \tl_const:Nn \c__fp_one_fixed_tl
13568 { {10000} {0000} {0000} {0000} {0000} {0000} }
```

(End definition for `\c__fp_one_fixed_tl`.)

`__fp_fixed_continue:wn` This function does nothing. Of course, there is no bound on a_1 (except T_EX’s own $2^{31} - 1$).

```
13569 \cs_new:Npn \__fp_fixed_continue:wn #1; #2 { #2 #1; }
```

(End definition for `__fp_fixed_continue:wn`.)

`__fp_fixed_add_one:wn` This function adds 1 to the fixed point $\langle a \rangle$, by changing a_1 to $10000 + a_1$, then calls the $\langle continuation \rangle$. This requires $a_1 \leq 2^{31} - 10001$.

```
13570 \cs_new:Npn \__fp_fixed_add_one:wn #1#2; #3
13571 {
13572   \exp_after:wn #3 \exp_after:wn
13573   { \__int_value:w \__int_eval:w \c__fp_myriad_int + #1 } #2 ;
13574 }
```

(End definition for `__fp_fixed_add_one:wn`.)

`__fp_fixed_div_myriad:wn` Divide a fixed point number by 10000. This is a little bit more subtle than just removing the last group and adding a leading group of zeros: the first group #1 may have any number of digits, and we must split #1 into the new first group and a second group of exactly 4 digits. The choice of shifts allows #1 to be in the range $[0, 5 \cdot 10^8 - 1]$.

```

13575 \cs_new:Npn \__fp_fixed_div_myriad:wn #1#2#3#4#5#6;
13576 {
13577   \exp_after:wN \__fp_fixed_mul_after:wnn
13578   \__int_value:w \__int_eval:w \c__fp_leading_shift_int
13579   \exp_after:wN \__fp_pack:NNNNNw
13580   \__int_value:w \__int_eval:w \c__fp_trailing_shift_int
13581   + #1 ; {#2}{#3}{#4}{#5};
13582 }

```

(End definition for `__fp_fixed_div_myriad:wn`.)

`__fp_fixed_mul_after:wnn` The fixed point operations which involve multiplication end by calling this auxiliary. It braces the last block of digits, and places the *continuation* #2 in front. The *continuation* was brought up through the expansions by the packing functions.

```

13583 \cs_new:Npn \__fp_fixed_mul_after:wnn #1; #2; #3 { #3 {#1} #2; }

```

(End definition for `__fp_fixed_mul_after:wnn`.)

26.3 Multiplying a fixed point number by a short one

`__fp_fixed_mul_short:wnn` Computes the product $c = ab$ of $a = \sum_i \langle a_i \rangle 10^{-4i}$ and $b = \sum_i \langle b_i \rangle 10^{-4i}$, rounds it to the closest multiple of 10^{-24} , and leaves *continuation* $\{\langle c_1 \rangle\} \dots \{\langle c_6 \rangle\}$; in the input stream, where each of the $\langle c_i \rangle$ are blocks of 4 digits, except $\langle c_1 \rangle$, which is any \TeX integer. Note that indices for $\langle b \rangle$ start at 0: a second operand of $\{0001\}\{0000\}\{0000\}$ will leave the first operand unchanged (rather than dividing it by 10^4 , as `__fp_fixed_mul:wnn` would).

```

13584 \cs_new:Npn \__fp_fixed_mul_short:wnn #1#2#3#4#5#6; #7#8#9;
13585 {
13586   \exp_after:wN \__fp_fixed_mul_after:wnn
13587   \__int_value:w \__int_eval:w \c__fp_leading_shift_int
13588   + #1*#7
13589   \exp_after:wN \__fp_pack:NNNNNw
13590   \__int_value:w \__int_eval:w \c__fp_middle_shift_int
13591   + #1*#8 + #2*#7
13592   \exp_after:wN \__fp_pack:NNNNNw
13593   \__int_value:w \__int_eval:w \c__fp_middle_shift_int
13594   + #1*#9 + #2*#8 + #3*#7
13595   \exp_after:wN \__fp_pack:NNNNNw
13596   \__int_value:w \__int_eval:w \c__fp_middle_shift_int
13597   + #2*#9 + #3*#8 + #4*#7
13598   \exp_after:wN \__fp_pack:NNNNNw
13599   \__int_value:w \__int_eval:w \c__fp_middle_shift_int
13600   + #3*#9 + #4*#8 + #5*#7
13601   \exp_after:wN \__fp_pack:NNNNNw
13602   \__int_value:w \__int_eval:w \c__fp_trailing_shift_int
13603   + #4*#9 + #5*#8 + #6*#7
13604   + ( #5*#9 + #6*#8 + #6*#9 / \c__fp_myriad_int )
13605   / \c__fp_myriad_int ; ;
13606 }

```

(End definition for `_fp_fixed_mul_short:wnn`.)

26.4 Dividing a fixed point number by a small integer

`_fp_fixed_div_int:wnN`
`_fp_fixed_div_int:wnN`
`_fp_fixed_div_int_auxi:wnn`
`_fp_fixed_div_int_auxii:wnn`
`_fp_fixed_div_int_pack:Nw`
`_fp_fixed_div_int_after:Nw`

Divides the fixed point number $\langle a \rangle$ by the (small) integer $0 < \langle n \rangle < 10^4$ and feeds the result to the $\langle continuation \rangle$. There is no bound on a_1 .

The arguments of the `i` auxiliary are 1: one of the a_i , 2: n , 3: the `ii` or the `iii` auxiliary. It computes a (somewhat tight) lower bound Q_i for the ratio a_i/n .

The `ii` auxiliary receives Q_i , n , and a_i as arguments. It adds Q_i to a surrounding integer expression, and starts a new one with the initial value 9999, which ensures that the result of this expression will have 5 digits. The auxiliary also computes $a_i - n \cdot Q_i$, placing the result in front of the 4 digits of a_{i+1} . The resulting $a'_{i+1} = 10^4(a_i - n \cdot Q_i) + a_{i+1}$ serves as the first argument for a new call to the `i` auxiliary.

When the `iii` auxiliary is called, the situation looks like this:

```
\_fp\_fixed\_div\_int\_after:Nw  $\langle continuation \rangle$ 
-1 +  $Q_1$ 
\_fp\_fixed\_div\_int\_pack:Nw 9999 +  $Q_2$ 
\_fp\_fixed\_div\_int\_pack:Nw 9999 +  $Q_3$ 
\_fp\_fixed\_div\_int\_pack:Nw 9999 +  $Q_4$ 
\_fp\_fixed\_div\_int\_pack:Nw 9999 +  $Q_5$ 
\_fp\_fixed\_div\_int\_pack:Nw 9999
\_fp\_fixed\_div\_int\_auxii:wnn  $Q_6$  ;  $\{\langle n \rangle\} \{\langle a_6 \rangle\}$ 
```

where expansion is happening from the last line up. The `iii` auxiliary adds $Q_6 + 2 \simeq a_6/n + 1$ to the last 9999, giving the integer closest to $10000 + a_6/n$.

Each `pack` auxiliary receives 5 digits followed by a semicolon. The first digit is added as a carry to the integer expression above, and the 4 other digits are braced. Each call to the `pack` auxiliary thus produces one brace group. The last brace group is produced by the `after` auxiliary, which places the $\langle continuation \rangle$ as appropriate.

```
13607 \cs_new:Npn \_fp\_fixed\_div\_int:wnN #1#2#3#4#5#6 ; #7 ; #8
13608 {
13609   \exp_after:wN \_fp\_fixed\_div\_int\_after:Nw
13610   \exp_after:wN #8
13611   \__int_value:w \__int_eval:w - 1
13612   \_fp\_fixed\_div\_int:wnN
13613   #1; {#7} \_fp\_fixed\_div\_int\_auxi:wnn
13614   #2; {#7} \_fp\_fixed\_div\_int\_auxi:wnn
13615   #3; {#7} \_fp\_fixed\_div\_int\_auxi:wnn
13616   #4; {#7} \_fp\_fixed\_div\_int\_auxi:wnn
13617   #5; {#7} \_fp\_fixed\_div\_int\_auxi:wnn
13618   #6; {#7} \_fp\_fixed\_div\_int\_auxii:wnn ;
13619 }
13620 \cs_new:Npn \_fp\_fixed\_div\_int:wnN #1; #2 #3
13621 {
13622   \exp_after:wN #3
13623   \__int_value:w \__int_eval:w #1 / #2 - 1 ;
13624   {#2}
13625   {#1}
13626 }
13627 \cs_new:Npn \_fp\_fixed\_div\_int\_auxi:wnn #1; #2 #3
13628 {
```

```

13629      + #1
13630      \exp_after:wN \__fp_fixed_div_int_pack:Nw
13631      \__int_value:w \__int_eval:w 9999
13632      \exp_after:wN \__fp_fixed_div_int:wnN
13633      \__int_value:w \__int_eval:w #3 - #1*#2 \__int_eval_end:
13634    }
13635    \cs_new:Npn \__fp_fixed_div_int_auxii:wnn #1; #2 #3 { + #1 + 2 ; }
13636    \cs_new:Npn \__fp_fixed_div_int_pack:Nw #1 #2; { + #1; {#2} }
13637    \cs_new:Npn \__fp_fixed_div_int_after:Nw #1 #2; { #1 {#2} }

```

(End definition for `__fp_fixed_div_int:wnN` and others.)

26.5 Adding and subtracting fixed points

`__fp_fixed_add:wnn` Computes $a + b$ (resp. $a - b$) and feeds the result to the $\langle continuation \rangle$. This function requires $0 \leq a_1, b_1 \leq 114748$, its result must be positive (this happens automatically for addition) and its first group must have at most 5 digits: $(a \pm b)_1 < 100000$. The two functions only differ by a sign, hence use a common auxiliary. It would be nice to grab the 12 brace groups in one go; only 9 parameters are allowed. Start by grabbing the sign, a_1, \dots, a_4 , the rest of a , and b_1 and b_2 . The second auxiliary receives the rest of a , the sign multiplying b , the rest of b , and the $\langle continuation \rangle$ as arguments. After going down through the various level, we go back up, packing digits and bringing the $\langle continuation \rangle$ (#8, then #7) from the end of the argument list to its start.

```

13638 \cs_new:Npn \__fp_fixed_add:wnn { \__fp_fixed_add:Nnnnnwnn + }
13639 \cs_new:Npn \__fp_fixed_sub:wnn { \__fp_fixed_add:Nnnnnwnn - }
13640 \cs_new:Npn \__fp_fixed_add:Nnnnnwnn #1 #2#3#4#5 #6; #7#8
13641 {
13642   \exp_after:wN \__fp_fixed_add_after:NNNNNwn
13643   \__int_value:w \__int_eval:w 9 9999 9998 + #2#3 #1 #7#8
13644   \exp_after:wN \__fp_fixed_add_pack:NNNNNwn
13645   \__int_value:w \__int_eval:w 1 9999 9998 + #4#5
13646   \__fp_fixed_add:nnNnnwn #6 #1
13647 }
13648 \cs_new:Npn \__fp_fixed_add:nnNnnwn #1#2 #3 #4#5 #6#7 ; #8
13649 {
13650   #3 #4#5
13651   \exp_after:wN \__fp_fixed_add_pack:NNNNNwn
13652   \__int_value:w \__int_eval:w 2 0000 0000 #3 #6#7 + #1#2 ; {#8} ;
13653 }
13654 \cs_new:Npn \__fp_fixed_add_pack:NNNNNwn #1 #2#3#4#5 #6; #7
13655 { + #1 ; {#7} {#2#3#4#5} {#6} }
13656 \cs_new:Npn \__fp_fixed_add_after:NNNNNwn 1 #1 #2#3#4#5 #6; #7
13657 { #7 {#1#2#3#4#5} {#6} }

```

(End definition for `__fp_fixed_add:wnn` and others.)

26.6 Multiplying fixed points

`__fp_fixed_mul:wnn` Computes $a \times b$ and feeds the result to $\langle continuation \rangle$. This function requires $0 \leq a_1, b_1 < 10000$. Once more, we need to play around the limit of 9 arguments for \TeX macros. Note that we don't need to obtain an exact rounding, contrarily to the `*` operator, so

things could be harder. We wish to perform carries in

$$\begin{aligned}
a \times b = & a_1 \cdot b_1 \cdot 10^{-8} \\
& + (a_1 \cdot b_2 + a_2 \cdot b_1) \cdot 10^{-12} \\
& + (a_1 \cdot b_3 + a_2 \cdot b_2 + a_3 \cdot b_1) \cdot 10^{-16} \\
& + (a_1 \cdot b_4 + a_2 \cdot b_3 + a_3 \cdot b_2 + a_4 \cdot b_1) \cdot 10^{-20} \\
& + \left(a_2 \cdot b_4 + a_3 \cdot b_3 + a_4 \cdot b_2 \right. \\
& \quad \left. + \frac{a_3 \cdot b_4 + a_4 \cdot b_3 + a_1 \cdot b_6 + a_2 \cdot b_5 + a_5 \cdot b_2 + a_6 \cdot b_1}{10^4} \right. \\
& \quad \left. + a_1 \cdot b_5 + a_5 \cdot b_1 \right) \cdot 10^{-24} + O(10^{-24}),
\end{aligned}$$

where the $O(10^{-24})$ stands for terms which are at most $5 \cdot 10^{-24}$; ignoring those leads to an error of at most 5 ulp. Note how the first 15 terms only depend on a_1, \dots, a_4 and b_1, \dots, b_4 , while the last 6 terms only depend on a_1, a_2, a_5, a_6 , and the corresponding parts of b . Hence, the first function grabs a_1, \dots, a_4 , the rest of a , and b_1, \dots, b_4 , and writes the 15 first terms of the expression, including a left parenthesis for the fraction. The `i` auxiliary receives $a_5, a_6, b_1, b_2, a_1, a_2, b_5, b_6$ and finally the $\langle continuation \rangle$ as arguments. It writes the end of the expression, including the right parenthesis and the denominator of the fraction. The $\langle continuation \rangle$ is finally placed in front of the 6 brace groups by `__fp_fixed_mul_after:wnn`.

```

13658 \cs_new:Npn \__fp_fixed_mul:wnn #1#2#3#4 #5; #6#7#8#9
13659 {
13660   \exp_after:wN \__fp_fixed_mul_after:wnn
13661   \__int_value:w \__int_eval:w \c__fp_leading_shift_int
13662   \exp_after:wN \__fp_pack:NNNNNw
13663   \__int_value:w \__int_eval:w \c__fp_middle_shift_int
13664   + #1*#6
13665   \exp_after:wN \__fp_pack:NNNNNw
13666   \__int_value:w \__int_eval:w \c__fp_middle_shift_int
13667   + #1*#7 + #2*#6
13668   \exp_after:wN \__fp_pack:NNNNNw
13669   \__int_value:w \__int_eval:w \c__fp_middle_shift_int
13670   + #1*#8 + #2*#7 + #3*#6
13671   \exp_after:wN \__fp_pack:NNNNNw
13672   \__int_value:w \__int_eval:w \c__fp_middle_shift_int
13673   + #1*#9 + #2*#8 + #3*#7 + #4*#6
13674   \exp_after:wN \__fp_pack:NNNNNw
13675   \__int_value:w \__int_eval:w \c__fp_trailing_shift_int
13676   + #2*#9 + #3*#8 + #4*#7
13677   + ( #3*#9 + #4*#8
13678     + \__fp_fixed_mul:nnnnnnnw #5 {#6}{#7} {#1}{#2}
13679   )
13680 \cs_new:Npn \__fp_fixed_mul:nnnnnnnw #1#2 #3#4 #5#6 #7#8 ;
13681 {
13682   #1*#4 + #2*#3 + #5*#8 + #6*#7 ) / \c__fp_myriad_int
13683   + #1*#3 + #5*#7 ; ;
13684 }
```

(End definition for `__fp_fixed_mul:wnn` and `__fp_fixed_mul:nnnnnnnw`.)

26.7 Combining product and sum of fixed points

`__fp_fixed_mul_add:wwn` Compute $a \times b + c$, $c - a \times b$, and $1 - a \times b$ and feed the result to the *(continuation)*.
`__fp_fixed_mul_sub_back:wwn` Those functions require $0 \leq a_1, b_1, c_1 \leq 10000$. Since those functions are at the heart of
`__fp_fixed_mul_one_minus_mul:wwn` the computation of Taylor expansions, we over-optimize them a bit, and in particular we do not factor out the common parts of the three functions.

For definiteness, consider the task of computing $a \times b + c$. We will perform carries in

$$\begin{aligned} a \times b + c = & (a_1 \cdot b_1 + c_1 c_2) \cdot 10^{-8} \\ & + (a_1 \cdot b_2 + a_2 \cdot b_1) \cdot 10^{-12} \\ & + (a_1 \cdot b_3 + a_2 \cdot b_2 + a_3 \cdot b_1 + c_3 c_4) \cdot 10^{-16} \\ & + (a_1 \cdot b_4 + a_2 \cdot b_3 + a_3 \cdot b_2 + a_4 \cdot b_1) \cdot 10^{-20} \\ & + \left(a_2 \cdot b_4 + a_3 \cdot b_3 + a_4 \cdot b_2 \right. \\ & \quad \left. + \frac{a_3 \cdot b_4 + a_4 \cdot b_3 + a_1 \cdot b_6 + a_2 \cdot b_5 + a_5 \cdot b_2 + a_6 \cdot b_1}{10^4} \right. \\ & \quad \left. + a_1 \cdot b_5 + a_5 \cdot b_1 + c_5 c_6 \right) \cdot 10^{-24} + O(10^{-24}), \end{aligned}$$

where $c_1 c_2$, $c_3 c_4$, $c_5 c_6$ denote the 8-digit number obtained by juxtaposing the two blocks of digits of c , and \cdot denotes multiplication. The task is obviously tough because we have 18 brace groups in front of us.

Each of the three function starts the first two levels (the first, corresponding to 10^{-4} , is empty), with $c_1 c_2$ in the first level, calls the `i` auxiliary with arguments described later, and adds a trailing $+ c_5 c_6$; *{(continuation)}*; . The $+ c_5 c_6$ piece, which is omitted for `__fp_fixed_one_minus_mul:wwn`, will be taken in the integer expression for the 10^{-24} level.

```

13685 \cs_new:Npn \__fp_fixed_mul_add:wwn #1; #2; #3#4#5#6#7#8;
13686 {
13687   \exp_after:wN \__fp_fixed_mul_after:wwn
13688   \__int_value:w \__int_eval:w \c__fp_big_leading_shift_int
13689   \exp_after:wN \__fp_pack_big:NNNNNNw
13690   \__int_value:w \__int_eval:w \c__fp_big_middle_shift_int + #3 #4
13691   \__fp_fixed_mul_add:Nwnnnwnnn +
13692   + #5 #6 ; #2 ; #1 ; #2 ; +
13693   + #7 #8 ; ;
13694 }
13695 \cs_new:Npn \__fp_fixed_mul_sub_back:wwn #1; #2; #3#4#5#6#7#8;
13696 {
13697   \exp_after:wN \__fp_fixed_mul_after:wwn
13698   \__int_value:w \__int_eval:w \c__fp_big_leading_shift_int
13699   \exp_after:wN \__fp_pack_big:NNNNNNw
13700   \__int_value:w \__int_eval:w \c__fp_big_middle_shift_int + #3 #4
13701   \__fp_fixed_mul_add:Nwnnnwnnn -
13702   + #5 #6 ; #2 ; #1 ; #2 ; -
13703   + #7 #8 ; ;
13704 }
13705 \cs_new:Npn \__fp_fixed_one_minus_mul:wwn #1; #2;
13706 {
13707   \exp_after:wN \__fp_fixed_mul_after:wwn
13708   \__int_value:w \__int_eval:w \c__fp_big_leading_shift_int
13709   \exp_after:wN \__fp_pack_big:NNNNNNw

```

```

13710     \__int_value:w \__int_eval:w \c__fp_big_middle_shift_int + 1 0000 0000
13711     \__fp_fixed_mul_add:Nwnnnwnnn -
13712         ; #2 ; #1 ; #2 ; -
13713         ; ;
13714 }

```

(End definition for __fp_fixed_mul_add:www, __fp_fixed_mul_sub_back:www, and __fp_fixed_mul_one_minus_mul:wnn.)

__fp_fixed_mul_add:Nwnnnwnnn Here, $\langle op \rangle$ is either + or -. Arguments #3, #4, #5 are $\langle b_1 \rangle$, $\langle b_2 \rangle$, $\langle b_3 \rangle$; arguments #7, #8, #9 are $\langle a_1 \rangle$, $\langle a_2 \rangle$, $\langle a_3 \rangle$. We can build three levels: $a_1 \cdot b_1$ for 10^{-8} , $(a_1 \cdot b_2 + a_2 \cdot b_1)$ for 10^{-12} , and $(a_1 \cdot b_3 + a_2 \cdot b_2 + a_3 \cdot b_1 + c_3 c_4)$ for 10^{-16} . The a - b products use the sign #1. Note that #2 is empty for __fp_fixed_one_minus_mul:wnn. We call the *ii* auxiliary for levels 10^{-20} and 10^{-24} , keeping the pieces of $\langle a \rangle$ we've read, but not $\langle b \rangle$, since there is another copy later in the input stream.

```

13715 \cs_new:Npn \__fp_fixed_mul_add:Nwnnnwnnn #1 #2; #3#4#5#6; #7#8#9
13716 {
13717     #1 #7*#3
13718     \exp_after:wN \__fp_pack_big:NNNNNNw
13719     \__int_value:w \__int_eval:w \c__fp_big_middle_shift_int
13720     #1 #7*#4 #1 #8*#3
13721     \exp_after:wN \__fp_pack_big:NNNNNNw
13722     \__int_value:w \__int_eval:w \c__fp_big_middle_shift_int
13723     #1 #7*#5 #1 #8*#4 #1 #9*#3 #2
13724     \exp_after:wN \__fp_pack_big:NNNNNNw
13725     \__int_value:w \__int_eval:w \c__fp_big_middle_shift_int
13726     #1 \__fp_fixed_mul_add:nnnnwnnnn {#7}{#8}{#9}
13727 }

```

(End definition for __fp_fixed_mul_add:Nwnnnwnnn.)

__fp_fixed_mul_add:nnnnwnnnn Level 10^{-20} is $(a_1 \cdot b_4 + a_2 \cdot b_3 + a_3 \cdot b_2 + a_4 \cdot b_1)$, multiplied by the sign, which was inserted by the *i* auxiliary. Then we prepare level 10^{-24} . We don't have access to all parts of $\langle a \rangle$ and $\langle b \rangle$ needed to make all products. Instead, we prepare the partial expressions

$$b_1 + a_4 \cdot b_2 + a_3 \cdot b_3 + a_2 \cdot b_4 + a_1$$

$$b_2 + a_4 \cdot b_3 + a_3 \cdot b_4 + a_2.$$

Obviously, those expressions make no mathematical sense: we will complete them with $a_5 \cdot$ and $\cdot b_5$, and with $a_6 \cdot b_1 + a_5 \cdot$ and $\cdot b_5 + a_1 \cdot b_6$, and of course with the trailing $+ c_5 c_6$. To do all this, we keep a_1 , a_5 , a_6 , and the corresponding pieces of $\langle b \rangle$.

```

13728 \cs_new:Npn \__fp_fixed_mul_add:nnnnwnnnn #1#2#3#4#5; #6#7#8#9
13729 {
13730     ( #1*#9 + #2*#8 + #3*#7 + #4*#6 )
13731     \exp_after:wN \__fp_pack_big:NNNNNNw
13732     \__int_value:w \__int_eval:w \c__fp_big_trailing_shift_int
13733     \__fp_fixed_mul_add:nnnnwnnnN
13734     { #6 + #4*#7 + #3*#8 + #2*#9 + #1 }
13735     { #7 + #4*#8 + #3*#9 + #2 }
13736     {#1} #5;
13737     {#6}
13738 }

```

(End definition for __fp_fixed_mul_add:nnnnwnnnn.)

`_fp_fixed_mul_add:nnnnwnnwn` Complete the $\langle partial_1 \rangle$ and $\langle partial_2 \rangle$ expressions as explained for the `ii` auxiliary. The second one is divided by 10000: this is the carry from level 10^{-28} . The trailing $+c_5c_6$ is taken into the expression for level 10^{-24} . Note that the total of level 10^{-24} is in the interval $[-5 \cdot 10^8, 6 \cdot 10^8]$ (give or take a couple of 10000), hence adding it to the shift gives a 10-digit number, as expected by the packing auxiliaries. See `l3fp-aux` for the definition of the shifts and packing auxiliaries.

```

13739 \cs_new:Npn \_fp_fixed_mul_add:nnnnwnnwn #1#2 #3#4#5; #6#7#8; #9
13740 {
13741     #9 (#4* #1 *#7)
13742     #9 (#5*#6+#4* #2 *#7+#3*#8) / \c_fp_myriad_int
13743 }

```

(End definition for `_fp_fixed_mul_add:nnnnwnnwn`.)

26.8 Extended-precision floating point numbers

In this section we manipulate floating point numbers with roughly 24 significant figures (“extended-precision” numbers, in short, “ep”), which take the form of an integer exponent, followed by a comma, then six groups of digits, ending with a semicolon. The first group of digit may be any non-negative integer, while other groups of digits have 4 digits. In other words, an extended-precision number is an exponent ending in a comma, then a fixed point number.

`_fp_ep_to_fixed:wwn` Converts an extended-precision number with an exponent at most 4 to a fixed point number whose first block will have 12 digits, most often starting with many zeros.

```

\_fp_ep_to_fixed_auxi:www
\_fp_ep_to_fixed_auxii:nnnnnnwnn
13744 \cs_new:Npn \_fp_ep_to_fixed:wwn #1,#2
13745 {
13746     \exp_after:wN \_fp_ep_to_fixed_auxi:www
13747     \_int_value:w \_int_eval:w 1 0000 0000 + #2 \exp_after:wN ;
13748     \exp:w \exp_end_continue_f:w
13749     \prg_replicate:nn { 4 - \int_max:nn {#1} { -32 } } { 0 } ;
13750 }
13751 \cs_new:Npn \_fp_ep_to_fixed_auxi:www #1#; #2; #3#4#5#6#7;
13752 {
13753     \_fp_pack_eight:wNNNNNNNN
13754     \_fp_pack_twice_four:wNNNNNNNN
13755     \_fp_pack_twice_four:wNNNNNNNN
13756     \_fp_pack_twice_four:wNNNNNNNN
13757     \_fp_ep_to_fixed_auxii:nnnnnnwnn ;
13758     #2 #1#3#4#5#6#7 0000 !
13759 }
13760 \cs_new:Npn \_fp_ep_to_fixed_auxii:nnnnnnwnn #1#2#3#4#5#6#7; #8! #9
13761 { #9 {#1#2}{#3}{#4}{#5}{#6}{#7}; }

```

(End definition for `_fp_ep_to_fixed:wwn`, `_fp_ep_to_fixed_auxi:www`, and `_fp_ep_to_fixed_auxii:nnnnnnwnn`.)

`_fp_ep_to_ep:wwN` Normalize an extended-precision number. More precisely, leading zeros are removed from the mantissa of the argument, decreasing its exponent as appropriate. Then the digits are packed into 6 groups of 4 (discarding any remaining digit, not rounding). Finally, the continuation `#8` is placed before the resulting exponent–mantissa pair. The input exponent may in fact be given as an integer expression. The `loop` auxiliary grabs a digit: if it is 0, decrement the exponent and continue looping, and otherwise call the `end`

auxiliary, which places all digits in the right order (the digit that was not 0, and any remaining digits), followed by some 0, then packs them up neatly in $3 \times 2 = 6$ blocks of four. At the end of the day, remove with `__fp_use_i:ww` any digit that did not make it in the final mantissa (typically only zeros, unless the original first block has more than 4 digits).

```

13762 \cs_new:Npn \__fp_ep_to_ep:wwN #1,#2#3#4#5#6#7; #8
13763 {
13764   \exp_after:wN #8
13765   \__int_value:w \__int_eval:w #1 + 4
13766   \exp_after:wN \use_i:nn
13767   \exp_after:wN \__fp_ep_to_ep_loop:N
13768   \__int_value:w \__int_eval:w 1 0000 0000 + #2 \__int_eval_end:
13769   #3#4#5#6#7 ; ; !
13770 }
13771 \cs_new:Npn \__fp_ep_to_ep_loop:N #1
13772 {
13773   \if_meaning:w 0 #1
13774   - 1
13775   \else:
13776     \__fp_ep_to_ep_end:www #1
13777   \fi:
13778   \__fp_ep_to_ep_loop:N
13779 }
13780 \cs_new:Npn \__fp_ep_to_ep_end:www
13781 #1 \fi: \__fp_ep_to_ep_loop:N #2; #3!
13782 {
13783   \fi:
13784   \if_meaning:w ; #1
13785   - 2 * \c_fp_max_exponent_int
13786   \__fp_ep_to_ep_zero:ww
13787   \fi:
13788   \__fp_pack_twice_four:wNNNNNNNN
13789   \__fp_pack_twice_four:wNNNNNNNN
13790   \__fp_pack_twice_four:wNNNNNNNN
13791   \__fp_use_i:ww , ;
13792   #1 #2 0000 0000 0000 0000 0000 0000 ;
13793 }
13794 \cs_new:Npn \__fp_ep_to_ep_zero:ww \fi: #1; #2; #3;
13795 { \fi: , {1000}{0000}{0000}{0000}{0000}{0000} ; }

```

(End definition for `__fp_ep_to_ep:wwN` and others.)

`__fp_ep_compare:www`
`__fp_ep_compare_aux:www`

In `l3fp-trig` we need to compare two extended-precision numbers. This is based on the same function for positive floating point numbers, with an extra test if comparing only 16 decimals is not enough to distinguish the numbers. Note that this function only works if the numbers are normalized so that their first block is in `[1000,9999]`.

```

13796 \cs_new:Npn \__fp_ep_compare:www #1,#2#3#4#5#6#7;
13797 { \__fp_ep_compare_aux:www {#1}{#2}{#3}{#4}{#5}; #6#7; }
13798 \cs_new:Npn \__fp_ep_compare_aux:www #1;#2;#3;#4#5#6#7#8#9;
13799 {
13800   \if_case:w
13801     \__fp_compare_npos:nwnw #1; {#3}{#4}{#5}{#6}{#7}; \exp_stop_f:
13802     \if_int_compare:w #2 = #8#9 \exp_stop_f:

```

```

13803         0
13804         \else:
13805             \if_int_compare:w #2 < #8#9 - \fi: 1
13806             \fi:
13807         \or: 1
13808         \else: -1
13809         \fi:
13810     }

```

(End definition for `__fp_ep_compare:www` and `__fp_ep_compare_aux:www`.)

`__fp_ep_mul:wwwN` Multiply two extended-precision numbers: first normalize them to avoid losing too much precision, then multiply the mantissas `#2` and `#4` as fixed point numbers, and sum the exponents `#1` and `#3`. The result's first block is in `[100,9999]`.

`__fp_ep_mul_raw:wwwN`

```

13811 \cs_new:Npn \__fp_ep_mul:wwwN #1,#2; #3,#4;
13812 {
13813     \__fp_ep_to_ep:wwN #3,#4;
13814     \__fp_fixed_continue:wn
13815     {
13816         \__fp_ep_to_ep:wwN #1,#2;
13817         \__fp_ep_mul_raw:wwwN
13818     }
13819     \__fp_fixed_continue:wn
13820 }
13821 \cs_new:Npn \__fp_ep_mul_raw:wwwN #1,#2; #3,#4; #5
13822 {
13823     \__fp_fixed_mul:wn #2; #4;
13824     { \exp_after:wN #5 \__int_value:w \__int_eval:w #1 + #3 , }
13825 }

```

(End definition for `__fp_ep_mul:wwwN` and `__fp_ep_mul_raw:wwwN`.)

26.9 Dividing extended-precision numbers

Divisions of extended-precision numbers are difficult to perform with exact rounding: the technique used in `l3fp-basics` for 16-digit floating point numbers does not generalize easily to 24-digit numbers. Thankfully, there is no need for exact rounding.

Let us call $\langle n \rangle$ the numerator and $\langle d \rangle$ the denominator. After a simple normalization step, we can assume that $\langle n \rangle \in [0.1, 1)$ and $\langle d \rangle \in [0.1, 1)$, and compute $\langle n \rangle / (10 \langle d \rangle) \in (0.01, 1)$. In terms of the 6 blocks of digits $\langle n_1 \rangle \cdots \langle n_6 \rangle$ and the 6 blocks $\langle d_1 \rangle \cdots \langle d_6 \rangle$, the condition translates to $\langle n_1 \rangle, \langle d_1 \rangle \in [1000, 9999]$.

We will first find an integer estimate $a \simeq 10^8 / \langle d \rangle$ by computing

$$\begin{aligned}
 \alpha &= \left\lceil \frac{10^9}{\langle d_1 \rangle + 1} \right\rceil \\
 \beta &= \left\lceil \frac{10^9}{\langle d_1 \rangle} \right\rceil \\
 a &= 10^3 \alpha + (\beta - \alpha) \cdot \left(10^3 - \left\lceil \frac{\langle d_2 \rangle}{10} \right\rceil \right) - 1250,
 \end{aligned}$$

where $\left\lceil \frac{\cdot}{\cdot} \right\rceil$ denotes ε -TEX's rounding division, which rounds ties away from zero. The idea is to interpolate between $10^3 \alpha$ and $10^3 \beta$ with a parameter $\langle d_2 \rangle / 10^4$, so that when

$\langle d_2 \rangle = 0$ one gets $a = 10^3\beta - 1250 \simeq 10^{12}/\langle d_1 \rangle \simeq 10^8/\langle d \rangle$, while when $\langle d_2 \rangle = 9999$ one gets $a = 10^3\alpha - 1250 \simeq 10^{12}/(\langle d_1 \rangle + 1) \simeq 10^8/\langle d \rangle$. The shift by 1250 helps to ensure that a is an underestimate of the correct value. We will prove that

$$1 - 1.755 \cdot 10^{-5} < \frac{\langle d \rangle a}{10^8} < 1.$$

We can then compute the inverse of $\langle d \rangle a / 10^8 = 1 - \epsilon$ using the relation $1/(1 - \epsilon) \simeq (1 + \epsilon)(1 + \epsilon^2) + \epsilon^4$, which is correct up to a relative error of $\epsilon^5 < 1.6 \cdot 10^{-24}$. This allows us to find the desired ratio as

$$\frac{\langle n \rangle}{\langle d \rangle} = \frac{\langle n \rangle a}{10^8} ((1 + \epsilon)(1 + \epsilon^2) + \epsilon^4).$$

Let us prove the upper bound first (multiplied by 10^{15}). Note that $10^7 \langle d \rangle < 10^3 \langle d_1 \rangle + 10^{-1}(\langle d_2 \rangle + 1)$, and that $\varepsilon\text{-TeX}$'s division $\left\lfloor \frac{\langle d_2 \rangle}{10} \right\rfloor$ will at most underestimate $10^{-1}(\langle d_2 \rangle + 1)$ by 0.5, as can be checked for each possible last digit of $\langle d_2 \rangle$. Then,

$$10^7 \langle d \rangle a < \left(10^3 \langle d_1 \rangle + \left\lfloor \frac{\langle d_2 \rangle}{10} \right\rfloor + \frac{1}{2} \right) \left(\left(10^3 - \left\lfloor \frac{\langle d_2 \rangle}{10} \right\rfloor \right) \beta + \left\lfloor \frac{\langle d_2 \rangle}{10} \right\rfloor \alpha - 1250 \right) \quad (1)$$

$$< \left(10^3 \langle d_1 \rangle + \left\lfloor \frac{\langle d_2 \rangle}{10} \right\rfloor + \frac{1}{2} \right) \quad (2)$$

$$\left(\left(10^3 - \left\lfloor \frac{\langle d_2 \rangle}{10} \right\rfloor \right) \left(\frac{10^9}{\langle d_1 \rangle} + \frac{1}{2} \right) + \left\lfloor \frac{\langle d_2 \rangle}{10} \right\rfloor \left(\frac{10^9}{\langle d_1 \rangle + 1} + \frac{1}{2} \right) - 1250 \right) \quad (3)$$

$$< \left(10^3 \langle d_1 \rangle + \left\lfloor \frac{\langle d_2 \rangle}{10} \right\rfloor + \frac{1}{2} \right) \left(\frac{10^{12}}{\langle d_1 \rangle} - \left\lfloor \frac{\langle d_2 \rangle}{10} \right\rfloor \frac{10^9}{\langle d_1 \rangle (\langle d_1 \rangle + 1)} - 750 \right) \quad (4)$$

We recognize a quadratic polynomial in $\left\lfloor \frac{\langle d_2 \rangle}{10} \right\rfloor$ with a negative leading coefficient: this polynomial is bounded above, according to $(\left\lfloor \frac{\langle d_2 \rangle}{10} \right\rfloor + a)(b - c\left\lfloor \frac{\langle d_2 \rangle}{10} \right\rfloor) \leq (b + ca)^2/(4c)$. Hence,

$$10^7 \langle d \rangle a < \frac{10^{15}}{\langle d_1 \rangle (\langle d_1 \rangle + 1)} \left(\langle d_1 \rangle + \frac{1}{2} + \frac{1}{4} 10^{-3} - \frac{3}{8} \cdot 10^{-9} \langle d_1 \rangle (\langle d_1 \rangle + 1) \right)^2$$

Since $\langle d_1 \rangle$ takes integer values within $[1000, 9999]$, it is a simple programming exercise to check that the squared expression is always less than $\langle d_1 \rangle (\langle d_1 \rangle + 1)$, hence $10^7 \langle d \rangle a < 10^{15}$. The upper bound is proven. We also find that $\frac{3}{8}$ can be replaced by slightly smaller numbers, but nothing less than $0.374563\dots$, and going back through the derivation of the upper bound, we find that 1250 is as small a shift as we can obtain without breaking the bound.

Now, the lower bound. The same computation as for the upper bound implies

$$10^7 \langle d \rangle a > \left(10^3 \langle d_1 \rangle + \left\lfloor \frac{\langle d_2 \rangle}{10} \right\rfloor - \frac{1}{2} \right) \left(\frac{10^{12}}{\langle d_1 \rangle} - \left\lfloor \frac{\langle d_2 \rangle}{10} \right\rfloor \frac{10^9}{\langle d_1 \rangle (\langle d_1 \rangle + 1)} - 1750 \right)$$

This time, we want to find the minimum of this quadratic polynomial. Since the leading coefficient is still negative, the minimum is reached for one of the extreme values $\left\lfloor \frac{y}{10} \right\rfloor = 0$ or $\left\lfloor \frac{y}{10} \right\rfloor = 100$, and we easily check the bound for those values.

We have proven that the algorithm will give us a precise enough answer. Incidentally, the upper bound that we derived tells us that $a < 10^8/\langle d \rangle \leq 10^9$, hence we can compute a safely as a TeX integer, and even add 10^9 to it to ease grabbing of all the digits. The lower bound implies $10^8 - 1755 < a$, which we do not care about.

`_fp_ep_div:wwwn` Compute the ratio of two extended-precision numbers. The result is an extended-precision number whose first block lies in the range $[100, 9999]$, and is placed after the $\langle continuation \rangle$ once we are done. First normalize the inputs so that both first block lie in $[1000, 9999]$, then call `_fp_ep_div_esti:wwwn` $\langle denominator \rangle$ $\langle numerator \rangle$, responsible for estimating the inverse of the denominator.

```

13826 \cs_new:Npn \_fp_ep_div:wwwn #1,#2; #3,#4;
13827 {
13828   \_fp_ep_to_ep:wwN #1,#2;
13829   \_fp_fixed_continue:wn
13830   {
13831     \_fp_ep_to_ep:wwN #3,#4;
13832     \_fp_ep_div_esti:wwwn
13833   }
13834 }

```

(End definition for `_fp_ep_div:wwwn`.)

`_fp_ep_div_esti:wwwn` The `esti` function evaluates $\alpha = 10^9 / (\langle d_1 \rangle + 1)$, which is used twice in the expression
`_fp_ep_div_estii:wwnnwwn` for a , and combines the exponents $\#1$ and $\#4$ (with a shift by 1 because we will compute
`_fp_ep_div_estiii:NNNNNwwwn` $\langle n \rangle / (10 \langle d \rangle)$). Then the `estii` function evaluates $10^9 + a$, and puts the exponent $\#2$
after the continuation $\#7$: from there on we can forget exponents and focus on the
mantissa. The `estiii` function multiplies the denominator $\#7$ by $10^{-8}a$ (obtained as a
split into the single digit $\#1$ and two blocks of 4 digits, $\#2\#3\#4\#5$ and $\#6$). The result
 $10^{-8}a \langle d \rangle = (1 - \epsilon)$, and a partially packed $10^{-9}a$ (as a block of four digits, and five
individual digits, not packed by lack of available macro parameters here) are passed to
`_fp_ep_div_epsilon:wnNNNNn`, which computes $10^{-9}a / (1 - \epsilon)$, that is, $1 / (10 \langle d \rangle)$ and we
finally multiply this by the numerator $\#8$.

```

13835 \cs_new:Npn \_fp_ep_div_esti:wwwn #1,#2#3; #4,
13836 {
13837   \exp_after:wN \_fp_ep_div_estii:wwnnwwn
13838   \_int_value:w \_int_eval:w 10 0000 0000 / ( #2 + 1 )
13839   \exp_after:wN ;
13840   \_int_value:w \_int_eval:w #4 - #1 + 1 ,
13841   {#2} #3;
13842 }
13843 \cs_new:Npn \_fp_ep_div_estii:wwnnwwn #1; #2,#3#4#5; #6; #7
13844 {
13845   \exp_after:wN \_fp_ep_div_estiii:NNNNNwwwn
13846   \_int_value:w \_int_eval:w 10 0000 0000 - 1750
13847   + #1 000 + (10 0000 0000 / #3 - #1) * (1000 - #4 / 10) ;
13848   {#3}{#4}#5; #6; { #7 #2, }
13849 }
13850 \cs_new:Npn \_fp_ep_div_estiii:NNNNNwwwn 1#1#2#3#4#5#6; #7;
13851 {
13852   \_fp_fixed_mul_short:wnn #7; {#1}{#2#3#4#5}{#6};
13853   \_fp_ep_div_epsilon:wnNNNNn {#1#2#3#4}#5#6
13854   \_fp_fixed_mul:wnn
13855 }

```

(End definition for `_fp_ep_div_esti:wwwn`, `_fp_ep_div_estii:wwnnwwn`, and `_fp_ep_div_estiii:NNNNNwwwn`.)

`_fp_ep_div_epsilon:wnNNNNn` The bounds shown above imply that the `epsi` function's first operand is $(1 - \epsilon)$ with
`_fp_ep_div_eps_pack:NNNNNw` $\epsilon \in [0, 1.755 \cdot 10^{-5}]$. The `epsi` function computes ϵ as $1 - (1 - \epsilon)$. Since $\epsilon < 10^{-4}$, its
`_fp_ep_div_epsii:wnNNNNn`

first block vanishes and there is no need to explicitly use `#1` (which is 9999). Then `epsi` evaluates $10^{-9}a/(1 - \epsilon)$ as $(1 + \epsilon^2)(1 + \epsilon)(10^{-9}a\epsilon) + 10^{-9}a$. Importantly, we compute $10^{-9}a\epsilon$ before multiplying it with the rest, rather than multiplying by ϵ and then $10^{-9}a$, as this second option loses more precision. Also, the combination of `short_mul` and `div_myriad` is both faster and more precise than a simple `mul`.

```

13856 \cs_new:Npn \__fp_ep_div_epsilon:wnNNNNNn #1#2#3#4#5#6;
13857 {
13858   \exp_after:wN \__fp_ep_div_epsilon:wnNNNNNn
13859   \__int_value:w \__int_eval:w 1 9998 - #2
13860   \exp_after:wN \__fp_ep_div_epsilon_pack:NNNNNw
13861   \__int_value:w \__int_eval:w 1 9999 9998 - #3#4
13862   \exp_after:wN \__fp_ep_div_epsilon_pack:NNNNNw
13863   \__int_value:w \__int_eval:w 2 0000 0000 - #5#6 ; ;
13864 }
13865 \cs_new:Npn \__fp_ep_div_epsilon_pack:NNNNNw #1#2#3#4#5#6;
13866 { + #1 ; {#2#3#4#5} {#6} }
13867 \cs_new:Npn \__fp_ep_div_epsilon:wnNNNNNn 1#1; #2; #3#4#5#6#7#8
13868 {
13869   \__fp_fixed_mul:wnn {0000}{#1}#2; {0000}{#1}#2;
13870   \__fp_fixed_add_one:wN
13871   \__fp_fixed_mul:wnn {10000} {#1} #2 ;
13872   {
13873     \__fp_fixed_mul_short:wnn {0000}{#1}#2; {#3}{#4#5#6#7}{#8000};
13874     \__fp_fixed_div_myriad:wn
13875     \__fp_fixed_mul:wnn
13876   }
13877   \__fp_fixed_add:wnn {#3}{#4#5#6#7}{#8000}{0000}{0000}{0000};
13878 }

```

(End definition for `__fp_ep_div_epsilon:wnNNNNNn`, `__fp_ep_div_epsilon_pack:NNNNNw`, and `__fp_ep_div_epsilon:wnNNNNNn`.)

26.10 Inverse square root of extended precision numbers

The idea here is similar to division. Normalize the input, multiplying by powers of 100 until we have $x \in [0.01, 1)$. Then find an integer approximation $r \in [101, 1003]$ of $10^2/\sqrt{x}$, as the fixed point of iterations of the Newton method: essentially $r \mapsto (r + 10^8/(x_1r))/2$, starting from a guess that optimizes the number of steps before convergence. In fact, just as there is a slight shift when computing divisions to ensure that some inequalities hold, we will replace 10^8 by a slightly larger number which will ensure that $r^2x \geq 10^4$. This also causes $r \in [101, 1003]$. Another correction to the above is that the input is actually normalized to $[0.1, 1)$, and we use either 10^8 or 10^9 in the Newton method, depending on the parity of the exponent. Skipping those technical hurdles, once we have the approximation r , we set $y = 10^{-4}r^2x$ (or rather, the correct power of 10 to get $y \simeq 1$) and compute $y^{-1/2}$ through another application of Newton's method. This time, the starting value is $z = 1$, each step maps $z \mapsto z(1.5 - 0.5yz^2)$, and we perform a fixed number of steps. Our final result combines r with $y^{-1/2}$ as $x^{-1/2} = 10^{-2}ry^{-1/2}$.

`__fp_ep_isqrt:wnn`

`__fp_ep_isqrt_aux:wnn`

`__fp_ep_isqrt_auxii:wnnnwnn`

First normalize the input, then check the parity of the exponent `#1`. If it is even, the result's exponent will be $-\#1/2$, otherwise it will be $(\#1 - 1)/2$ (except in the case where the input was an exact power of 100). The `auxii` function receives as `#1` the result's exponent just computed, as `#2` the starting value for the iteration giving r (the

values 168 and 535 lead to the least number of iterations before convergence, on average), as #3 and #4 one empty argument and one 0, depending on the parity of the original exponent, as #5 and #6 the normalized mantissa ($\#5 \in [1000, 9999]$), and as #7 the continuation. It sets up the iteration giving r : the `esti` function thus receives the initial two guesses #2 and 0, an approximation #5 of 10^4x (its first block of digits), and the empty/zero arguments #3 and #4, followed by the mantissa and an altered continuation where we have stored the result's exponent.

```

13879 \cs_new:Npn \__fp_ep_isqrt:wnn #1,#2;
13880 {
13881   \__fp_ep_to_ep:wwN #1,#2;
13882   \__fp_ep_isqrt_auxi:wnn
13883 }
13884 \cs_new:Npn \__fp_ep_isqrt_auxi:wnn #1,
13885 {
13886   \exp_after:wN \__fp_ep_isqrt_auxii:wwnnwn
13887   \__int_value:w \__int_eval:w
13888   \int_if_odd:nTF {#1}
13889     { (1 - #1) / 2 , 535 , { 0 } { } }
13890     { 1 - #1 / 2 , 168 , { } { 0 } }
13891 }
13892 \cs_new:Npn \__fp_ep_isqrt_auxii:wwnnwn #1, #2, #3#4 #5#6; #7
13893 {
13894   \__fp_ep_isqrt_esti:wwnnwn #2, 0, #5, {#3} {#4}
13895   {#5} #6 ; { #7 #1 , }
13896 }

```

(End definition for `__fp_ep_isqrt:wnn`, `__fp_ep_isqrt_aux:wnn`, and `__fp_ep_isqrt_auxii:wwnnwn`.)

```

\__fp_ep_isqrt_esti:wwnnwn
\__fp_ep_isqrt_estii:wwnnwn
\__fp_ep_isqrt_estiii:NNNNNwwnn

```

If the last two approximations gave the same result, we are done: call the `estii` function to clean up. Otherwise, evaluate $(\langle prev \rangle + 1.005 \cdot 10^8 \text{ or } 9 / (\langle prev \rangle \cdot x)) / 2$, as the next approximation: omitting the 1.005 factor, this would be Newton's method. We can check by brute force that if #4 is empty (the original exponent was even), the process computes an integer slightly larger than $100/\sqrt{x}$, while if #4 is 0 (the original exponent was odd), the result is an integer slightly larger than $100/\sqrt{x/10}$. Once we are done, we evaluate $100r^2/2$ or $10r^2/2$ (when the exponent is even or odd, respectively) and feed that to `estiii`. This third auxiliary finds $y_{\text{even}}/2 = 10^{-4}r^2x/2$ or $y_{\text{odd}}/2 = 10^{-5}r^2x/2$ (again, depending on earlier parity). A simple program shows that $y \in [1, 1.0201]$. The number $y/2$ is fed to `__fp_ep_isqrt_epsilon:wn`, which computes $1/\sqrt{y}$, and we finally multiply the result by r .

```

13897 \cs_new:Npn \__fp_ep_isqrt_esti:wwnnwn #1, #2, #3, #4
13898 {
13899   \if_int_compare:w #1 = #2 \exp_stop_f:
13900   \exp_after:wN \__fp_ep_isqrt_estii:wwnnwn
13901   \fi:
13902   \exp_after:wN \__fp_ep_isqrt_esti:wwnnwn
13903   \__int_value:w \__int_eval:w
13904   (#1 + 1 0050 0000 #4 / (#1 * #3)) / 2 ,
13905   #1, #3, {#4}
13906 }
13907 \cs_new:Npn \__fp_ep_isqrt_estii:wwnnwn #1, #2, #3, #4#5
13908 {
13909   \exp_after:wN \__fp_ep_isqrt_estiii:NNNNNwwnn
13910   \__int_value:w \__int_eval:w 1000 0000 + #2 * #2 #5 * 5

```

```

13911     \exp_after:wN , \_int_value:w \_int_eval:w 10000 + #2 ;
13912   }
13913 \cs_new:Npn \__fp_ep_isqrt_estiii:NNNNNwwwn 1#1#2#3#4#5#6, 1#7#8; #9;
13914   {
13915     \__fp_fixed_mul_short:wwn #9; {#1} {#2#3#4#5} {#600} ;
13916     \__fp_ep_isqrt_epsilon:wN
13917     \__fp_fixed_mul_short:wwn {#7} {#80} {0000} ;
13918   }

(End definition for \__fp_ep_isqrt_esti:wwnnwn, \__fp_ep_isqrt_estii:wwnnwn, and \__fp_ep_
isqrt_estiii:NNNNNwwwn.)

```

Here, we receive a fixed point number $y/2$ with $y \in [1, 1.0201]$. Starting from $z = 1$ we iterate $z \mapsto z(3/2 - z^2 y/2)$. In fact, we start from the first iteration $z = 3/2 - y/2$ to avoid useless multiplications. The `epsii` auxiliary receives z as `#1` and y as `#2`.

```

13919 \cs_new:Npn \__fp_ep_isqrt_epsilon:wN #1;
13920   {
13921     \__fp_fixed_sub:wwn {15000}{0000}{0000}{0000}{0000}{0000}; #1;
13922     \__fp_ep_isqrt_epsilon:wwN #1;
13923     \__fp_ep_isqrt_epsilon:wwN #1;
13924     \__fp_ep_isqrt_epsilon:wwN #1;
13925   }
13926 \cs_new:Npn \__fp_ep_isqrt_epsii:wwN #1; #2;
13927   {
13928     \__fp_fixed_mul:wwn #1; #1;
13929     \__fp_fixed_mul_sub_back:wwwn #2;
13930     {15000}{0000}{0000}{0000}{0000}{0000};
13931     \__fp_fixed_mul:wwn #1;
13932   }

```

(End definition for `__fp_ep_isqrt_epsilon:wN` and `__fp_ep_isqrt_epsii:wwN`.)

26.11 Converting from fixed point to floating point

After computing Taylor series, we wish to convert the result from extended precision (with or without an exponent) to the public floating point format. The functions here should be called within an integer expression for the overall exponent of the floating point.

An extended-precision number is simply a comma-delimited exponent followed by a fixed point number. Leave the exponent in the current integer expression then convert the fixed point number.

```

13933 \cs_new:Npn \__fp_ep_to_float:wwN #1,
13934   { + \_int_eval:w #1 \__fp_fixed_to_float:wN }
13935 \cs_new:Npn \__fp_ep_inv_to_float:wwN #1,#2;
13936   {
13937     \__fp_ep_div:wwwn 1,{1000}{0000}{0000}{0000}{0000}{0000}; #1,#2;
13938     \__fp_ep_to_float:wwN
13939   }

```

(End definition for `__fp_ep_to_float:wwN` and `__fp_ep_inv_to_float:wwN`.)

Another function which reduces to converting an extended precision number to a float.

```

13940 \cs_new:Npn \__fp_fixed_inv_to_float:wN
13941   { \__fp_ep_inv_to_float:wwN 0, }

```


(End definition for _fp_fixed_inv_to_float:wN.)

_fp_fixed_to_float_rad:wN Converts the fixed point number #1 from degrees to radians then to a floating point number. This could perhaps remain in l3fp-trig.

```

13942 \cs_new:Npn \_fp_fixed_to_float_rad:wN #1;
13943 {
13944   \_fp_fixed_mul:wwN #1; {5729}{5779}{5130}{8232}{0876}{7981};
13945   { \_fp_ep_to_float:wwN 2, }
13946 }

```

(End definition for _fp_fixed_to_float_rad:wN.)

_fp_fixed_to_float:wN yields

_fp_fixed_to_float:Nw $\langle exponent \rangle$; $\{\langle a'_1 \rangle\}$ $\{\langle a'_2 \rangle\}$ $\{\langle a'_3 \rangle\}$ $\{\langle a'_4 \rangle\}$;

And the to_fixed version gives six brace groups instead of 4, ensuring that $1000 \leq \langle a'_1 \rangle \leq 9999$. At this stage, we know that $\langle a_1 \rangle$ is positive (otherwise, it is sign of an error before), and we assume that it is less than 10^8 .¹¹

```

13947 \cs_new:Npn \_fp_fixed_to_float:Nw #1#2; { \_fp_fixed_to_float:wN #2; #1 }
13948 \cs_new:Npn \_fp_fixed_to_float:wN #1#2#3#4#5#6; #7
13949 {
13950   + \_int_eval:w \_fp_block_int % for the 8-digit-at-the-start thing.
13951   \exp_after:wN \exp_after:wN
13952   \exp_after:wN \_fp_fixed_to_loop:N
13953   \exp_after:wN \use_none:n
13954   \_int_value:w \_int_eval:w
13955   1 0000 0000 + #1 \exp_after:wN \_fp_use_none_stop_f:n
13956   \_int_value:w 1#2 \exp_after:wN \_fp_use_none_stop_f:n
13957   \_int_value:w 1#3#4 \exp_after:wN \_fp_use_none_stop_f:n
13958   \_int_value:w 1#5#6
13959   \exp_after:wN ;
13960   \exp_after:wN ;
13961 }
13962 \cs_new:Npn \_fp_fixed_to_loop:N #1
13963 {
13964   \if_meaning:w 0 #1
13965   - 1
13966   \exp_after:wN \_fp_fixed_to_loop:N
13967   \else:
13968   \exp_after:wN \_fp_fixed_to_loop_end:w
13969   \exp_after:wN #1
13970   \fi:
13971 }
13972 \cs_new:Npn \_fp_fixed_to_loop_end:w #1 #2 ;
13973 {
13974   \if_meaning:w ; #1
13975   \exp_after:wN \_fp_fixed_to_float_zero:w
13976   \else:
13977   \exp_after:wN \_fp_pack_twice_four:wNNNNNNNN
13978   \exp_after:wN \_fp_pack_twice_four:wNNNNNNNN
13979   \exp_after:wN \_fp_fixed_to_float_pack:ww

```

¹¹Bruno: I must double check this assumption.

```

13980     \exp_after:wN ;
13981     \fi:
13982     #1 #2 0000 0000 0000 0000 ;
13983   }
13984   \cs_new:Npn \__fp_fixed_to_float_zero:w ; 0000 0000 0000 0000 ;
13985   {
13986     - 2 * \c__fp_max_exponent_int ;
13987     {0000} {0000} {0000} {0000} ;
13988   }
13989   \cs_new:Npn \__fp_fixed_to_float_pack:ww #1 ; #2#3 ; ;
13990   {
13991     \if_int_compare:w #2 > 4 \exp_stop_f:
13992       \exp_after:wN \__fp_fixed_to_float_round_up:wnnnnw
13993       \fi:
13994       ; #1 ;
13995   }
13996   \cs_new:Npn \__fp_fixed_to_float_round_up:wnnnnw ; #1#2#3#4 ;
13997   {
13998     \exp_after:wN \__fp_basics_pack_high:NNNNNw
13999     \__int_value:w \__int_eval:w 1 #1#2
14000     \exp_after:wN \__fp_basics_pack_low:NNNNNw
14001     \__int_value:w \__int_eval:w 1 #3#4 + 1 ;
14002   }

(End definition for \__fp_fixed_to_float:wN and \__fp_fixed_to_float:Nw.)

14003 </initex | package>

```

27 13fp-expo implementation

```

14004 <*initex | package>
14005 <@@=fp>

```

27.1 Logarithm

27.1.1 Work plan

As for many other functions, we filter out special cases in `__fp_ln_o:w`. Then `__fp_ln_npos_o:w` receives a positive normal number, which we write in the form $a \cdot 10^b$ with $a \in [0.1, 1)$.

The rest of this section is actually not in sync with the code. Or is the code not in sync with the section? In the current code, $c \in [1, 10]$ will be such that $0.7 \leq ac < 1.4$.

We are given a positive normal number, of the form $a \cdot 10^b$ with $a \in [0.1, 1)$. To compute its logarithm, we find a small integer $5 \leq c < 50$ such that $0.91 \leq ac/5 < 1.1$, and use the relation

$$\ln(a \cdot 10^b) = b \cdot \ln(10) - \ln(c/5) + \ln(ac/5).$$

The logarithms $\ln(10)$ and $\ln(c/5)$ are looked up in a table. The last term is computed using the following Taylor series of \ln near 1:

$$\ln\left(\frac{ac}{5}\right) = \ln\left(\frac{1+t}{1-t}\right) = 2t \left(1 + t^2 \left(\frac{1}{3} + t^2 \left(\frac{1}{5} + t^2 \left(\frac{1}{7} + t^2 \left(\frac{1}{9} + \dots\right)\right)\right)\right)\right)$$

where $t = 1 - 10/(ac + 5)$. We can now see one reason for the choice of $ac \sim 5$: then $ac + 5 = 10(1 - \epsilon)$ with $-0.05 < \epsilon \leq 0.045$, hence

$$t = \frac{\epsilon}{1 - \epsilon} = \epsilon(1 + \epsilon)(1 + \epsilon^2)(1 + \epsilon^4) \dots,$$

is not too difficult to compute.

27.1.2 Some constants

A few values of the logarithm as extended fixed point numbers. Those are needed in the implementation. It turns out that we don't need the value of $\ln(5)$.

```
\c__fp_ln_i_fixed_t1
\c__fp_ln_ii_fixed_t1
\c__fp_ln_iii_fixed_t1
\c__fp_ln_iv_fixed_t1
\c__fp_ln_vi_fixed_t1
\c__fp_ln_vii_fixed_t1
\c__fp_ln_viii_fixed_t1
\c__fp_ln_ix_fixed_t1
\c__fp_ln_x_fixed_t1
14006 \tl_const:Nn \c__fp_ln_i_fixed_t1 { {0000}{0000}{0000}{0000}{0000} }
14007 \tl_const:Nn \c__fp_ln_ii_fixed_t1 { {6931}{4718}{0559}{9453}{0941}{7232} }
14008 \tl_const:Nn \c__fp_ln_iii_fixed_t1 { {10986}{1228}{8668}{1096}{9139}{5245} }
14009 \tl_const:Nn \c__fp_ln_iv_fixed_t1 { {13862}{9436}{1119}{8906}{1883}{4464} }
14010 \tl_const:Nn \c__fp_ln_vi_fixed_t1 { {17917}{5946}{9228}{0550}{0081}{2477} }
14011 \tl_const:Nn \c__fp_ln_vii_fixed_t1 { {19459}{1014}{9055}{3133}{0510}{5353} }
14012 \tl_const:Nn \c__fp_ln_viii_fixed_t1 { {20794}{4154}{1679}{8359}{2825}{1696} }
14013 \tl_const:Nn \c__fp_ln_ix_fixed_t1 { {21972}{2457}{7336}{2193}{8279}{0490} }
14014 \tl_const:Nn \c__fp_ln_x_fixed_t1 { {23025}{8509}{2994}{0456}{8401}{7991} }
```

(End definition for `\c__fp_ln_i_fixed_t1` and others.)

27.1.3 Sign, exponent, and special numbers

`__fp_ln_o:w` The logarithm of negative numbers (including $-\infty$ and -0) raises the “invalid” exception. The logarithm of $+0$ is $-\infty$, raising a division by zero exception. The logarithm of $+\infty$ or a `nan` is itself. Positive normal numbers call `__fp_ln_npos_o:w`.

```
14015 \cs_new:Npn \__fp_ln_o:w #1 \s__fp \__fp_chk:w #2#3#4; @
14016 {
14017   \if_meaning:w 2 #3
14018     \__fp_case_use:nw { \__fp_invalid_operation_o:nw { ln } }
14019   \fi:
14020   \if_case:w #2 \exp_stop_f:
14021     \__fp_case_use:nw
14022     { \__fp_division_by_zero_o:Nnw \c_minus_inf_fp { ln } }
14023   \or:
14024   \else:
14025     \__fp_case_return_same_o:w
14026   \fi:
14027   \__fp_ln_npos_o:w \s__fp \__fp_chk:w #2#3#4;
14028 }
```

(End definition for `__fp_ln_o:w`.)

27.1.4 Absolute ln

`__fp_ln_npos_o:w` We catch the case of a significand very close to 0.1 or to 1. In all other cases, the final result is at least 10^{-4} , and then an error of $0.5 \cdot 10^{-20}$ is acceptable.

```
14029 \cs_new:Npn \__fp_ln_npos_o:w \s__fp \__fp_chk:w 10#1#2#3;
14030 { %^^A todo: ln(1) should be "exact zero", not "underflow"
14031   \exp_after:wN \__fp_sanitize:Nw
14032   \__int_value:w % for the overall sign
```

```

14033     \if_int_compare:w #1 < 1 \exp_stop_f:
14034         2
14035     \else:
14036         0
14037     \fi:
14038     \exp_after:wN \exp_stop_f:
14039     \__int_value:w \__int_eval:w % for the exponent
14040     \__fp_ln_significand:NNNNnnnnN #2#3
14041     \__fp_ln_exponent:wn {#1}
14042 }

```

(End definition for __fp_ln_npos_o:w.)

__fp_ln_significand:NNNNnnnnN $\langle X_1 \rangle \{ \langle X_2 \rangle \} \{ \langle X_3 \rangle \} \{ \langle X_4 \rangle \} \langle continuation \rangle$
This function expands to

$\langle continuation \rangle \{ \langle Y_1 \rangle \} \{ \langle Y_2 \rangle \} \{ \langle Y_3 \rangle \} \{ \langle Y_4 \rangle \} \{ \langle Y_5 \rangle \} \{ \langle Y_6 \rangle \} ;$

where $Y = -\ln(X)$ as an extended fixed point.

```

14043 \cs_new:Npn \__fp_ln_significand:NNNNnnnnN #1#2#3#4
14044 {
14045     \exp_after:wN \__fp_ln_x_ii:wnnnnn
14046     \__int_value:w
14047     \if_case:w #1 \exp_stop_f:
14048     \or:
14049         \if_int_compare:w #2 < 4 \exp_stop_f:
14050         \__int_eval:w 10 - #2
14051     \else:
14052         6
14053     \fi:
14054     \or: 4
14055     \or: 3
14056     \or: 2
14057     \or: 2
14058     \or: 2
14059     \else: 1
14060     \fi:
14061     ; { #1 #2 #3 #4 }
14062 }

```

(End definition for __fp_ln_significand:NNNNnnnnN.)

__fp_ln_x_ii:wnnnnn We have thus found $c \in [1, 10]$ such that $0.7 \leq ac < 1.4$ in all cases. Compute $1 + x = 1 + ac \in [1.7, 2.4)$.

```

14063 \cs_new:Npn \__fp_ln_x_ii:wnnnnn #1; #2#3#4#5
14064 {
14065     \exp_after:wN \__fp_ln_div_after:Nw
14066     \cs:w c__fp_ln_ \__int_to_roman:w #1 _fixed_tl \exp_after:wN \cs_end:
14067     \__int_value:w
14068     \exp_after:wN \__fp_ln_x_iv:wnnnnnnnnn
14069     \__int_value:w \__int_eval:w
14070     \exp_after:wN \__fp_ln_x_iii_var:NNNNNw
14071     \__int_value:w \__int_eval:w 9999 9990 + #1*#2#3 +
14072     \exp_after:wN \__fp_ln_x_iii:NNNNNNw
14073     \__int_value:w \__int_eval:w 10 0000 0000 + #1*#4#5 ;

```

```

14074      {20000} {0000} {0000} {0000}
14075    } %^A todo: reoptimize (a generalization attempt failed).
14076 \cs_new:Npn \__fp_ln_x_iii:NNNNNNw #1#2 #3#4#5#6 #7;
14077   { #1#2; {#3#4#5#6} {#7} }
14078 \cs_new:Npn \__fp_ln_x_iii_var:NNNNNNw #1 #2#3#4#5 #6;
14079   {
14080     #1#2#3#4#5 + 1 ;
14081     {#1#2#3#4#5} {#6}
14082   }

```

The Taylor series will be expressed in terms of $t = (x-1)/(x+1) = 1-2/(x+1)$. We now compute the quotient with extended precision, reusing some code from `__fp/_o:ww`. Note that $1+x$ is known exactly.

To reuse notations from `l3fp-basics`, we want to compute A/Z with $A = 2$ and $Z = x + 1$. In `l3fp-basics`, we considered the case where both A and Z are arbitrary, in the range $[0.1, 1)$, and we had to monitor the growth of the sequence of remainders A , B , C , etc. to ensure that no overflow occurred during the computation of the next quotient. The main source of risk was our choice to define the quotient as roughly $10^9 \cdot A/10^5 \cdot Z$: then A was bound to be below $2.147 \cdots$, and this limit was never far.

In our case, we can simply work with $10^8 \cdot A$ and $10^4 \cdot Z$, because our reason to work with higher powers has gone: we needed the integer $y \simeq 10^5 \cdot Z$ to be at least 10^4 , and now, the definition $y \simeq 10^4 \cdot Z$ suffices.

Let us thus define $y = \lfloor 10^4 \cdot Z \rfloor + 1 \in (1.7 \cdot 10^4, 2.4 \cdot 10^4]$, and

$$Q_1 = \left\lfloor \frac{\lfloor 10^8 \cdot A \rfloor}{y} - \frac{1}{2} \right\rfloor.$$

(The $1/2$ comes from how `eTeX` rounds.) As for division, it is easy to see that $Q_1 \leq 10^4 A/Z$, *i.e.*, Q_1 is an underestimate.

Exactly as we did for division, we set $B = 10^4 A - Q_1 Z$. Then

$$\begin{aligned}
10^4 B &\leq A_1 A_2 \cdot A_3 A_4 - \left(\frac{A_1 A_2}{y} - \frac{3}{2} \right) 10^4 Z \\
&\leq A_1 A_2 \left(1 - \frac{10^4 Z}{y} \right) + 1 + \frac{3}{2} y \\
&\leq 10^8 \frac{A}{y} + 1 + \frac{3}{2} y
\end{aligned}$$

In the same way, and using $1.7 \cdot 10^4 \leq y \leq 2.4 \cdot 10^4$, and convexity, we get

$$\begin{aligned} 10^4 A &= 2 \cdot 10^4 \\ 10^4 B &\leq 10^8 \frac{A}{y} + 1.6y \leq 4.7 \cdot 10^4 \\ 10^4 C &\leq 10^8 \frac{B}{y} + 1.6y \leq 5.8 \cdot 10^4 \\ 10^4 D &\leq 10^8 \frac{C}{y} + 1.6y \leq 6.3 \cdot 10^4 \\ 10^4 E &\leq 10^8 \frac{D}{y} + 1.6y \leq 6.5 \cdot 10^4 \\ 10^4 F &\leq 10^8 \frac{E}{y} + 1.6y \leq 6.6 \cdot 10^4 \end{aligned}$$

Note that we compute more steps than for division: since t is not the end result, we need to know it with more accuracy (on the other hand, the ending is much simpler, as we don't need an exact rounding for transcendental functions, but just a faithful rounding).¹²

`__fp_ln_x_iv:wnnnnnnnn <1 or 2> <8d> ; {<4d>} {<4d>} <fixed-tl>`

The number is x . Compute y by adding 1 to the five first digits.

```

14083 \cs_new:Npn \__fp_ln_x_iv:wnnnnnnnn #1; #2#3#4#5 #6#7#8#9
14084 {
14085   \exp_after:wN \__fp_div_significand_pack:NNN
14086   \__int_value:w \__int_eval:w
14087   \__fp_ln_div_i:w #1 ;
14088   #6 #7 ; {#8} {#9}
14089   {#2} {#3} {#4} {#5}
14090   { \exp_after:wN \__fp_ln_div_ii:wnn \__int_value:w #1 }
14091   { \exp_after:wN \__fp_ln_div_ii:wnn \__int_value:w #1 }
14092   { \exp_after:wN \__fp_ln_div_ii:wnn \__int_value:w #1 }
14093   { \exp_after:wN \__fp_ln_div_ii:wnn \__int_value:w #1 }
14094   { \exp_after:wN \__fp_ln_div_vi:wnn \__int_value:w #1 }
14095 }
14096 \cs_new:Npn \__fp_ln_div_i:w #1;
14097 {
14098   \exp_after:wN \__fp_div_significand_calc:wnnnnnnnn
14099   \__int_value:w \__int_eval:w 999999 + 2 0000 0000 / #1 ; % Q1
14100 }
14101 \cs_new:Npn \__fp_ln_div_ii:wnn #1; #2;#3 % y; B1;B2 <- for k=1
14102 {
14103   \exp_after:wN \__fp_div_significand_pack:NNN
14104   \__int_value:w \__int_eval:w
14105   \exp_after:wN \__fp_div_significand_calc:wnnnnnnnn
14106   \__int_value:w \__int_eval:w 999999 + #2 #3 / #1 ; % Q2
14107   #2 #3 ;
14108 }
14109 \cs_new:Npn \__fp_ln_div_vi:wnn #1; #2;#3#4#5 #6#7#8#9 %y;F1;F2F3F4x1x2x3x4
14110 {

```

¹²Bruno: to be completed.

```

14111 \exp_after:wN \_fp_div_significand_pack:NNN
14112 \_int_value:w \_int_eval:w 1000000 + #2 #3 / #1 ; % Q6
14113 }

```

We now have essentially¹³

$$\begin{aligned} & _fp_ln_div_after:Nw \langle fixed\ tl \rangle _fp_div_significand_pack:NNN 10^6 + \\ & Q_1 _fp_div_significand_pack:NNN 10^6 + Q_2 _fp_div_significand_ \\ & pack:NNN 10^6 + Q_3 _fp_div_significand_pack:NNN 10^6 + Q_4 _fp_ \\ & div_significand_pack:NNN 10^6 + Q_5 _fp_div_significand_pack:NNN \\ & 10^6 + Q_6 ; \langle exponent \rangle ; \langle continuation \rangle \end{aligned}$$

where $\langle fixed\ tl \rangle$ holds the logarithm of a number in $[1, 10]$, and $\langle exponent \rangle$ is the exponent. Also, the expansion is done backwards. Then $_fp_div_significand_pack:NNN$ puts things in the correct order to add the Q_i together and put semicolons between each piece. Once those have been expanded, we get

$$\begin{aligned} & _fp_ln_div_after:Nw \langle fixed\ tl \rangle \langle 1d \rangle ; \langle 4d \rangle ; \langle 4d \rangle ; \langle 4d \rangle ; \langle 4d \rangle ; \langle 4d \rangle ; \\ & \langle 4d \rangle ; \langle exponent \rangle ; \end{aligned}$$

Just as with division, we know that the first two digits are 1 and 0 because of bounds on the final result of the division $2/(x+1)$, which is between roughly 0.8 and 1.2. We then compute $1 - 2/(x+1)$, after testing whether $2/(x+1)$ is greater than or smaller than 1.

```

14114 \cs_new:Npn \_fp_ln_div_after:Nw #1#2;
14115 {
14116   \if_meaning:w 0 #2
14117     \exp_after:wN \_fp_ln_t_small:Nw
14118   \else:
14119     \exp_after:wN \_fp_ln_t_large:NNw
14120     \exp_after:wN -
14121   \fi:
14122   #1
14123 }
14124 \cs_new:Npn \_fp_ln_t_small:Nw #1 #2; #3; #4; #5; #6; #7;
14125 {
14126   \exp_after:wN \_fp_ln_t_large:NNw
14127   \exp_after:wN + % <sign>
14128   \exp_after:wN #1
14129   \_int_value:w \_int_eval:w 9999 - #2 \exp_after:wN ;
14130   \_int_value:w \_int_eval:w 9999 - #3 \exp_after:wN ;
14131   \_int_value:w \_int_eval:w 9999 - #4 \exp_after:wN ;
14132   \_int_value:w \_int_eval:w 9999 - #5 \exp_after:wN ;
14133   \_int_value:w \_int_eval:w 9999 - #6 \exp_after:wN ;
14134   \_int_value:w \_int_eval:w 1 0000 - #7 ;
14135 }

```

$$\begin{aligned} & _fp_ln_t_large:NNw \langle sign \rangle \langle fixed\ tl \rangle \langle t_1 \rangle ; \langle t_2 \rangle ; \langle t_3 \rangle ; \langle t_4 \rangle ; \langle t_5 \rangle ; \langle t_6 \rangle ; \\ & \langle exponent \rangle ; \langle continuation \rangle \end{aligned}$$

Compute the square t^2 , and keep t at the end with its sign. We know that $t < 0.1765$, so every piece has at most 4 digits. However, since we were not careful in $_fp_ln_t_small:w$, they can have less than 4 digits.

¹³Bruno: add a mention that the error on Q_6 is bounded by 10 (probably 6.7), and thus corresponds to an error of 10^{-23} on the final result, small enough in all cases.

```

14136 \cs_new:Npn \__fp_ln_t_large:NNw #1 #2 #3; #4; #5; #6; #7; #8;
14137 {
14138   \exp_after:wN \__fp_ln_square_t_after:w
14139   \__int_value:w \__int_eval:w 9999 0000 + #3*#3
14140   \exp_after:wN \__fp_ln_square_t_pack:NNNNNw
14141   \__int_value:w \__int_eval:w 9999 0000 + 2*#3*#4
14142   \exp_after:wN \__fp_ln_square_t_pack:NNNNNw
14143   \__int_value:w \__int_eval:w 9999 0000 + 2*#3*#5 + #4*#4
14144   \exp_after:wN \__fp_ln_square_t_pack:NNNNNw
14145   \__int_value:w \__int_eval:w 9999 0000 + 2*#3*#6 + 2*#4*#5
14146   \exp_after:wN \__fp_ln_square_t_pack:NNNNNw
14147   \__int_value:w \__int_eval:w 1 0000 0000 + 2*#3*#7 + 2*#4*#6 + #5*#5
14148   + (2*#3*#8 + 2*#4*#7 + 2*#5*#6) / 1 0000
14149   % ; ; ;
14150   \exp_after:wN \__fp_ln_twice_t_after:w
14151   \__int_value:w \__int_eval:w -1 + 2*#3
14152   \exp_after:wN \__fp_ln_twice_t_pack:Nw
14153   \__int_value:w \__int_eval:w 9999 + 2*#4
14154   \exp_after:wN \__fp_ln_twice_t_pack:Nw
14155   \__int_value:w \__int_eval:w 9999 + 2*#5
14156   \exp_after:wN \__fp_ln_twice_t_pack:Nw
14157   \__int_value:w \__int_eval:w 9999 + 2*#6
14158   \exp_after:wN \__fp_ln_twice_t_pack:Nw
14159   \__int_value:w \__int_eval:w 9999 + 2*#7
14160   \exp_after:wN \__fp_ln_twice_t_pack:Nw
14161   \__int_value:w \__int_eval:w 10000 + 2*#8 ; ;
14162   { \__fp_ln_c:NwNw #1 }
14163   #2
14164   }
14165   \cs_new:Npn \__fp_ln_twice_t_pack:Nw #1 #2; { + #1 ; {#2} }
14166   \cs_new:Npn \__fp_ln_twice_t_after:w #1; { ; ; ; {#1} }
14167   \cs_new:Npn \__fp_ln_square_t_pack:NNNNNw #1 #2#3#4#5 #6;
14168   { + #1#2#3#4#5 ; {#6} }
14169   \cs_new:Npn \__fp_ln_square_t_after:w 1 0 #1#2#3 #4;
14170   { \__fp_ln_Taylor:wwNw {0#1#2#3} {#4} }

```

(End definition for __fp_ln_x_ii:wnnnn.)

__fp_ln_Taylor:wwNw Denoting $T = t^2$, we get

```

\__fp_ln_Taylor:wwNw {⟨T1⟩} {⟨T2⟩} {⟨T3⟩} {⟨T4⟩} {⟨T5⟩} {⟨T6⟩} ; ;
{⟨(2t)1⟩} {⟨(2t)2⟩} {⟨(2t)3⟩} {⟨(2t)4⟩} {⟨(2t)5⟩} {⟨(2t)6⟩} ; { \__fp_ln_
c:NwNn ⟨sign⟩ } ⟨fixed tl⟩ ⟨exponent⟩ ; ⟨continuation⟩

```

And we want to compute

$$\ln\left(\frac{1+t}{1-t}\right) = 2t \left(1 + T \left(\frac{1}{3} + T \left(\frac{1}{5} + T \left(\frac{1}{7} + T \left(\frac{1}{9} + \cdots\right)\right)\right)\right)\right)$$

The process looks as follows

```

\loop 5; A;
\div_int 5; 1.0; \add A; \mul T; {\loop \eval 5-2;}
\add 0.2; A; \mul T; {\loop \eval 5-2;}
\mul B; T; {\loop 3;}
\loop 3; C;

```


14

This uses the routine for dividing a number by a small integer ($< 10^4$).

```

14171 \cs_new:Npn \__fp_ln_Taylor:wwNw
14172 { \__fp_ln_Taylor_loop:www 21 ; {0000}{0000}{0000}{0000}{0000}{0000} ; }
14173 \cs_new:Npn \__fp_ln_Taylor_loop:www #1; #2; #3;
14174 {
14175   \if_int_compare:w #1 = 1 \exp_stop_f:
14176   \__fp_ln_Taylor_break:w
14177   \fi:
14178   \exp_after:wN \__fp_fixed_div_int:wwN \c__fp_one_fixed_tl ; #1;
14179   \__fp_fixed_add:wwN #2;
14180   \__fp_fixed_mul:wwN #3;
14181   {
14182     \exp_after:wN \__fp_ln_Taylor_loop:www
14183     \__int_value:w \__int_eval:w #1 - 2 ;
14184   }
14185   #3;
14186 }
14187 \cs_new:Npn \__fp_ln_Taylor_break:w \fi: #1 \__fp_fixed_add:wwN #2#3; #4 ;;
14188 {
14189   \fi:
14190   \exp_after:wN \__fp_fixed_mul:wwN
14191   \exp_after:wN { \__int_value:w \__int_eval:w 10000 + #2 } #3;
14192 }

```

(End definition for `__fp_ln_Taylor:wwNw`.)

`__fp_ln_c:NwNw` $\langle sign \rangle \{ \langle r_1 \rangle \} \{ \langle r_2 \rangle \} \{ \langle r_3 \rangle \} \{ \langle r_4 \rangle \} \{ \langle r_5 \rangle \} \{ \langle r_6 \rangle \} ; \langle fixed\ tl \rangle$
 $\langle exponent \rangle ; \langle continuation \rangle$

We are now reduced to finding $\ln(c)$ and $\langle exponent \rangle \ln(10)$ in a table, and adding it to the mixture. The first step is to get $\ln(c) - \ln(x) = -\ln(a)$, then we get $b \ln(10)$ and add or subtract.

For now, $\ln(x)$ is given as $\cdot 10^0$. Unless both the exponent is 1 and $c = 1$, we shift to working in units of $\cdot 10^4$, since the final result will be at least $\ln(10/7) \simeq 0.35$.¹⁵

```

14193 \cs_new:Npn \__fp_ln_c:NwNw #1 #2; #3
14194 {
14195   \if_meaning:w + #1
14196   \exp_after:wN \exp_after:wN \exp_after:wN \__fp_fixed_sub:wwN
14197   \else:
14198   \exp_after:wN \exp_after:wN \exp_after:wN \__fp_fixed_add:wwN
14199   \fi:
14200   #3 ; #2 ;
14201 }

```

16

(End definition for `__fp_ln_c:NwNw`.)

`__fp_ln_exponent:wn` $__fp_ln_exponent:wn \{ \langle s_1 \rangle \} \{ \langle s_2 \rangle \} \{ \langle s_3 \rangle \} \{ \langle s_4 \rangle \} \{ \langle s_5 \rangle \} \{ \langle s_6 \rangle \} ;$
 $\{ \langle exponent \rangle \}$

¹⁴Bruno: add explanations.

¹⁵Bruno: that was wrong at some point, I must check.

¹⁶Bruno: this *must* be updated with correct values!

Compute $\langle exponent \rangle$ times $\ln(10)$. Apart from the cases where $\langle exponent \rangle$ is 0 or 1, the result will necessarily be at least $\ln(10) \simeq 2.3$ in magnitude. We can thus drop the least significant 4 digits. In the case of a very large (positive or negative) exponent, we can (and we need to) drop 4 additional digits, since the result is of order 10^4 . Naively, one would think that in both cases we can drop 4 more digits than we do, but that would be slightly too tight for rounding to happen correctly. Besides, we already have addition and subtraction for 24 digits fixed point numbers.

```

14202 \cs_new:Npn \__fp_ln_exponent:wn #1; #2
14203 {
14204   \if_case:w #2 \exp_stop_f:
14205     0 \__fp_case_return:nw { \__fp_fixed_to_float:Nw 2 }
14206   \or:
14207     \exp_after:wN \__fp_ln_exponent_one:ww \__int_value:w
14208   \else:
14209     \if_int_compare:w #2 > 0 \exp_stop_f:
14210       \exp_after:wN \__fp_ln_exponent_small:NNww
14211       \exp_after:wN 0
14212       \exp_after:wN \__fp_fixed_sub:wwn \__int_value:w
14213     \else:
14214       \exp_after:wN \__fp_ln_exponent_small:NNww
14215       \exp_after:wN 2
14216       \exp_after:wN \__fp_fixed_add:wwn \__int_value:w -
14217     \fi:
14218   \fi:
14219   #2; #1;
14220 }

```

Now we painfully write all the cases.¹⁷ No overflow nor underflow can happen, except when computing $\ln(1)$.

```

14221 \cs_new:Npn \__fp_ln_exponent_one:ww 1; #1;
14222 {
14223   0
14224   \exp_after:wN \__fp_fixed_sub:wwn \c__fp_ln_x_fixed_t1 ; #1;
14225   \__fp_fixed_to_float:wN 0
14226 }

```

For small exponents, we just drop one block of digits, and set the exponent of the log to 4 (minus any shift coming from leading zeros in the conversion from fixed point to floating point). Note that here the exponent has been made positive.

```

14227 \cs_new:Npn \__fp_ln_exponent_small:NNww #1#2#3; #4#5#6#7#8#9;
14228 {
14229   4
14230   \exp_after:wN \__fp_fixed_mul:wwn
14231     \c__fp_ln_x_fixed_t1 ;
14232     {#3}{0000}{0000}{0000}{0000}{0000} ;
14233   #2
14234     {0000}{#4}{#5}{#6}{#7}{#8};
14235   \__fp_fixed_to_float:wN #1
14236 }

```

(End definition for $\backslash_fp_ln_exponent:wn$.)

¹⁷Bruno: do rounding.

27.2 Exponential

27.2.1 Sign, exponent, and special numbers

`__fp_exp_o:w`

```
14237 \cs_new:Npn \__fp_exp_o:w #1 \s__fp \__fp_chk:w #2#3#4; @
14238 {
14239   \if_case:w #2 \exp_stop_f:
14240     \__fp_case_return_o:Nw \c_one_fp
14241   \or:
14242     \exp_after:wN \__fp_exp_normal:w
14243   \or:
14244     \if_meaning:w 0 #3
14245       \exp_after:wN \__fp_case_return_o:Nw
14246       \exp_after:wN \c_inf_fp
14247     \else:
14248       \exp_after:wN \__fp_case_return_o:Nw
14249       \exp_after:wN \c_zero_fp
14250     \fi:
14251   \or:
14252     \__fp_case_return_same_o:w
14253   \fi:
14254   \s__fp \__fp_chk:w #2#3#4;
14255 }
```

(End definition for __fp_exp_o:w.)

`__fp_exp_normal:w`

`__fp_exp_pos:Nnwnw`

```
14256 \cs_new:Npn \__fp_exp_normal:w \s__fp \__fp_chk:w 1#1
14257 {
14258   \if_meaning:w 0 #1
14259     \__fp_exp_pos:Nnwnw + \__fp_fixed_to_float:wN
14260   \else:
14261     \__fp_exp_pos:Nnwnw - \__fp_fixed_inv_to_float:wN
14262   \fi:
14263 }
14264 \cs_new:Npn \__fp_exp_pos:Nnwnw #1#2#3 \fi: #4#5;
14265 {
14266   \fi:
14267   \exp_after:wN \__fp_sanitize:Nw
14268   \exp_after:wN 0
14269   \__int_value:w #1 \__int_eval:w
14270   \if_int_compare:w #4 < - \c__fp_half_prec_int
14271     1
14272     \exp_after:wN \__fp_add_big_i_o:wNww
14273     \__int_value:w \__int_eval:w 1 - #4 ;
14274     0 {1000}{0000}{0000}{0000} ; #5;
14275     \exp:w
14276   \else:
14277     \if_int_compare:w #4 > \c__fp_max_exp_exponent_int
14278       \exp_after:wN \__fp_exp_overflow:
14279       \exp:w
14280     \else:
14281       \if_int_compare:w #4 < 0 \exp_stop_f:
14282       \exp_after:wN \use_i:nn
```

```

14283         \else:
14284             \exp_after:wN \use_ii:nn
14285         \fi:
14286         {
14287             0
14288             \__fp_decimate:nNnnnn { - #4 }
14289             \__fp_exp_Taylor:Nnnwn
14290         }
14291         {
14292             \__fp_decimate:nNnnnn { \c__fp_prec_int - #4 }
14293             \__fp_exp_pos_large:NnnNwn
14294         }
14295         #5
14296         {#4}
14297         #1 #2 0
14298         \exp:w
14299         \fi:
14300     \fi:
14301     \exp_after:wN \exp_end:
14302 }
14303 \cs_new:Npn \__fp_exp_overflow:
14304 { + 2 * \c__fp_max_exponent_int ; {1000} {0000} {0000} {0000} ; }

```

(End definition for __fp_exp_normal:w and __fp_exp_pos:Nnnwn.)

__fp_exp_Taylor:Nnnwn
 __fp_exp_Taylor_loop:www
 __fp_exp_Taylor_break:Nww

This function is called for numbers in the range $[10^{-9}, 10^{-1})$. Our only task is to compute the Taylor series. The first argument is irrelevant (rounding digit used by some other functions). The next three arguments, at least 16 digits, delimited by a semicolon, form a fixed point number, so we pack it in blocks of 4 digits.

```

14305 \cs_new:Npn \__fp_exp_Taylor:Nnnwn #1#2#3 #4; #5 #6
14306 {
14307     #6
14308     \__fp_pack_twice_four:wNNNNNNNN
14309     \__fp_pack_twice_four:wNNNNNNNN
14310     \__fp_pack_twice_four:wNNNNNNNN
14311     \__fp_exp_Taylor_ii:ww
14312     ; #2#3#4 0000 0000 ;
14313 }
14314 \cs_new:Npn \__fp_exp_Taylor_ii:ww #1; #2;
14315 { \__fp_exp_Taylor_loop:www 10 ; #1 ; #1 ; \s_stop }
14316 \cs_new:Npn \__fp_exp_Taylor_loop:www #1; #2; #3;
14317 {
14318     \if_int_compare:w #1 = 1 \exp_stop_f:
14319     \exp_after:wN \__fp_exp_Taylor_break:Nww
14320     \fi:
14321     \__fp_fixed_div_int:wwN #3 ; #1 ;
14322     \__fp_fixed_add_one:wN
14323     \__fp_fixed_mul:wwN #2 ;
14324     {
14325         \exp_after:wN \__fp_exp_Taylor_loop:www
14326         \__int_value:w \__int_eval:w #1 - 1 ;
14327         #2 ;
14328     }
14329 }

```

```

14330 \cs_new:Npn \__fp_exp_Taylor_break:Nww #1 #2; #3 \s__stop
14331 { \__fp_fixed_add_one:wN #2 ; }

```

(End definition for __fp_exp_Taylor:Nnnwn, __fp_exp_Taylor_loop:www, and __fp_exp_Taylor-break:Nww.)

```

\__fp_exp_pos_large:NnnNwn
\__fp_exp_large_after:wwn
  \__fp_exp_large:w
    \__fp_exp_large_v:wN
    \__fp_exp_large_iv:wN
    \__fp_exp_large_iii:wN
    \__fp_exp_large_ii:wN
    \__fp_exp_large_i:wN
    \__fp_exp_large:wN

```

The first two arguments are irrelevant (a rounding digit, and a brace group with 8 zeros). The third argument is the integer part of our number, then we have the decimal part delimited by a semicolon, and finally the exponent, in the range $[0, 5]$. Remove leading zeros from the integer part: putting #4 in there too ensures that an integer part of 0 is also removed. Then read digits one by one, looking up $\exp(\langle digit \rangle \cdot 10^{\langle exponent \rangle})$ in a table, and multiplying that to the current total. The loop is done by having the auxiliary for one exponent call the auxiliary for the next exponent. The current total is expressed by leaving the exponent behind in the input stream (we are currently within an __int_eval:w), and keeping track of a fixed point number, #1 for the numbered auxiliaries. Our usage of \if_case:w is somewhat dirty for optimization: T_EX jumps to the appropriate case, but we then close the \if_case:w “by hand”, using \or: and \fi: as delimiters.

```

14332 \cs_new:Npn \__fp_exp_pos_large:NnnNwn #1#2#3 #4#5; #6
14333 {
14334   \exp_after:wN \exp_after:wN
14335   \cs:w \__fp_exp_large_ \__int_to_roman:w #6 :wN \exp_after:wN \cs_end:
14336   \exp_after:wN \c__fp_one_fixed_tl
14337   \exp_after:wN ;
14338   \__int_value:w #3 #4 \exp_stop_f:
14339   #5 00000 ;
14340 }
14341 \cs_new:Npn \__fp_exp_large:w #1 \or: #2 \fi:
14342 { \fi: \__fp_fixed_mul:wwn #1; }
14343 \cs_new:Npn \__fp_exp_large_v:wN #1; #2
14344 {
14345   \if_case:w #2 ~ \exp_after:wN \__fp_fixed_continue:wn \or:
14346   + 4343 \__fp_exp_large:w {8806}{8182}{2566}{2921}{5872}{6150} \or:
14347   + 8686 \__fp_exp_large:w {7756}{0047}{2598}{6861}{0458}{3204} \or:
14348   + 13029 \__fp_exp_large:w {6830}{5723}{7791}{4884}{1932}{7351} \or:
14349   + 17372 \__fp_exp_large:w {6015}{5609}{3095}{3052}{3494}{7574} \or:
14350   + 21715 \__fp_exp_large:w {5297}{7951}{6443}{0315}{3251}{3576} \or:
14351   + 26058 \__fp_exp_large:w {4665}{6719}{0099}{3379}{5527}{2929} \or:
14352   + 30401 \__fp_exp_large:w {4108}{9724}{3326}{3186}{5271}{5665} \or:
14353   + 34744 \__fp_exp_large:w {3618}{6973}{3140}{0875}{3856}{4102} \or:
14354   + 39087 \__fp_exp_large:w {3186}{9209}{6113}{3900}{6705}{9685} \or:
14355   \fi:
14356   #1;
14357   \__fp_exp_large_iv:wN
14358 }
14359 \cs_new:Npn \__fp_exp_large_iv:wN #1; #2
14360 {
14361   \if_case:w #2 ~ \exp_after:wN \__fp_fixed_continue:wn \or:
14362   + 435 \__fp_exp_large:w {1970}{0711}{1401}{7046}{9938}{8888} \or:
14363   + 869 \__fp_exp_large:w {3881}{1801}{9428}{4368}{5764}{8232} \or:
14364   + 1303 \__fp_exp_large:w {7646}{2009}{8905}{4704}{8893}{1073} \or:
14365   + 1738 \__fp_exp_large:w {1506}{3559}{7005}{0524}{9009}{7592} \or:
14366   + 2172 \__fp_exp_large:w {2967}{6283}{8402}{3667}{0689}{6630} \or:
14367   + 2606 \__fp_exp_large:w {5846}{4389}{5650}{2114}{7278}{5046} \or:
14368   + 3041 \__fp_exp_large:w {1151}{7900}{5080}{6878}{2914}{4154} \or:

```

```

14369         + 3475 \_fp_exp_large:w {2269}{1083}{0850}{6857}{8724}{4002} \or:
14370         + 3909 \_fp_exp_large:w {4470}{3047}{3316}{5442}{6408}{6591} \or:
14371     \fi:
14372     #1;
14373     \_fp_exp_large_iii:wN
14374 }
14375 \cs_new:Npn \_fp_exp_large_iii:wN #1; #2
14376 {
14377     \if_case:w #2 ~          \exp_after:wN \_fp_fixed_continue:wn \or:
14378     + 44 \_fp_exp_large:w {2688}{1171}{4181}{6135}{4484}{1263} \or:
14379     + 87 \_fp_exp_large:w {7225}{9737}{6812}{5749}{2581}{7748} \or:
14380     + 131 \_fp_exp_large:w {1942}{4263}{9524}{1255}{9365}{8421} \or:
14381     + 174 \_fp_exp_large:w {5221}{4696}{8976}{4143}{9505}{8876} \or:
14382     + 218 \_fp_exp_large:w {1403}{5922}{1785}{2837}{4107}{3977} \or:
14383     + 261 \_fp_exp_large:w {3773}{0203}{0092}{9939}{8234}{0143} \or:
14384     + 305 \_fp_exp_large:w {1014}{2320}{5473}{5004}{5094}{5533} \or:
14385     + 348 \_fp_exp_large:w {2726}{3745}{7211}{2566}{5673}{6478} \or:
14386     + 391 \_fp_exp_large:w {7328}{8142}{2230}{7421}{7051}{8866} \or:
14387     \fi:
14388     #1;
14389     \_fp_exp_large_ii:wN
14390 }
14391 \cs_new:Npn \_fp_exp_large_ii:wN #1; #2
14392 {
14393     \if_case:w #2 ~          \exp_after:wN \_fp_fixed_continue:wn \or:
14394     + 5 \_fp_exp_large:w {2202}{6465}{7948}{0671}{6516}{9579} \or:
14395     + 9 \_fp_exp_large:w {4851}{6519}{5409}{7902}{7796}{9107} \or:
14396     + 14 \_fp_exp_large:w {1068}{6474}{5815}{2446}{2146}{9905} \or:
14397     + 18 \_fp_exp_large:w {2353}{8526}{6837}{0199}{8540}{7900} \or:
14398     + 22 \_fp_exp_large:w {5184}{7055}{2858}{7072}{4640}{8745} \or:
14399     + 27 \_fp_exp_large:w {1142}{0073}{8981}{5684}{2836}{6296} \or:
14400     + 31 \_fp_exp_large:w {2515}{4386}{7091}{9167}{0062}{6578} \or:
14401     + 35 \_fp_exp_large:w {5540}{6223}{8439}{3510}{0525}{7117} \or:
14402     + 40 \_fp_exp_large:w {1220}{4032}{9431}{7840}{8020}{0271} \or:
14403     \fi:
14404     #1;
14405     \_fp_exp_large_i:wN
14406 }
14407 \cs_new:Npn \_fp_exp_large_i:wN #1; #2
14408 {
14409     \if_case:w #2 ~          \exp_after:wN \_fp_fixed_continue:wn \or:
14410     + 1 \_fp_exp_large:w {2718}{2818}{2845}{9045}{2353}{6029} \or:
14411     + 1 \_fp_exp_large:w {7389}{0560}{9893}{0650}{2272}{3043} \or:
14412     + 2 \_fp_exp_large:w {2008}{5536}{9231}{8766}{7740}{9285} \or:
14413     + 2 \_fp_exp_large:w {5459}{8150}{0331}{4423}{9078}{1103} \or:
14414     + 3 \_fp_exp_large:w {1484}{1315}{9102}{5766}{0342}{1116} \or:
14415     + 3 \_fp_exp_large:w {4034}{2879}{3492}{7351}{2260}{8387} \or:
14416     + 4 \_fp_exp_large:w {1096}{6331}{5842}{8458}{5992}{6372} \or:
14417     + 4 \_fp_exp_large:w {2980}{9579}{8704}{1728}{2747}{4359} \or:
14418     + 4 \_fp_exp_large:w {8103}{0839}{2757}{5384}{0077}{1000} \or:
14419     \fi:
14420     #1;
14421     \_fp_exp_large_:wN
14422 }

```

```

14423 \cs_new:Npn \__fp_exp_large:wN #1; #2
14424 {
14425   \if_case:w #2 ~      \exp_after:wN \__fp_fixed_continue:wn \or:
14426     + 1 \__fp_exp_large:w {1105}{1709}{1807}{5647}{6248}{1171} \or:
14427     + 1 \__fp_exp_large:w {1221}{4027}{5816}{0169}{8339}{2107} \or:
14428     + 1 \__fp_exp_large:w {1349}{8588}{0757}{6003}{1039}{8374} \or:
14429     + 1 \__fp_exp_large:w {1491}{8246}{9764}{1270}{3178}{2485} \or:
14430     + 1 \__fp_exp_large:w {1648}{7212}{7070}{0128}{1468}{4865} \or:
14431     + 1 \__fp_exp_large:w {1822}{1188}{0039}{0508}{9748}{7537} \or:
14432     + 1 \__fp_exp_large:w {2013}{7527}{0747}{0476}{5216}{2455} \or:
14433     + 1 \__fp_exp_large:w {2225}{5409}{2849}{2467}{6045}{7954} \or:
14434     + 1 \__fp_exp_large:w {2459}{6031}{1115}{6949}{6638}{0013} \or:
14435   \fi:
14436   #1;
14437   \__fp_exp_large_after:wnn
14438 }
14439 \cs_new:Npn \__fp_exp_large_after:wnn #1; #2; #3
14440 {
14441   \__fp_exp_Taylor:Nnnwn ? { } { } 0 #2; {} #3
14442   \__fp_fixed_mul:wnn #1;
14443 }

```

(End definition for `__fp_exp_pos_large:NnnNwn` and others.)

27.3 Power

Raising a number a to a power b leads to many distinct situations.

| a^b | $-\infty$ | $(-\infty, -0)$ | $-p/5^k$ | ± 0 | $+p/5^k$ | $(0, \infty)$ | $+\infty$ | NaN |
|-----------------|-----------|-----------------|-----------------|---------|-----------------|---------------|-----------|-----|
| $+\infty$ | +0 | | +0 | +1 | $+\infty$ | | $+\infty$ | NaN |
| $(1, \infty)$ | +0 | | $+ a ^b$ | +1 | $+ a ^b$ | | $+\infty$ | NaN |
| +1 | +1 | | +1 | +1 | +1 | | +1 | +1 |
| $(0, 1)$ | $+\infty$ | | $+ a ^b$ | +1 | $+ a ^b$ | | +0 | NaN |
| +0 | $+\infty$ | | $+\infty$ | +1 | +0 | | +0 | NaN |
| -0 | $+\infty$ | NaN | $(-1)^p \infty$ | +1 | $(-1)^p 0$ | +0 | +0 | NaN |
| $(-1, 0)$ | $+\infty$ | NaN | $(-1)^p a ^b$ | +1 | $(-1)^p a ^b$ | NaN | +0 | NaN |
| -1 | +1 | NaN | $(-1)^p$ | +1 | $(-1)^p$ | NaN | +1 | NaN |
| $(-\infty, -1)$ | +0 | NaN | $(-1)^p a ^b$ | +1 | $(-1)^p a ^b$ | NaN | $+\infty$ | NaN |
| $-\infty$ | +0 | +0 | $(-1)^p 0$ | +1 | $(-1)^p \infty$ | NaN | $+\infty$ | NaN |
| NaN | NaN | NaN | NaN | +1 | NaN | NaN | NaN | NaN |

We distinguished in this table the cases of finite (positive or negative) exponents of the form $b = p/q$ with q odd (hence necessarily a power of 5), as $(-1)^{p/q} = (-1)^p$ is defined in that case. One peculiarity of this operation is that $\text{NaN}^0 = 1^{\text{NaN}} = 1$, because this relation is obeyed for any number, even $\pm\infty$.

`__fp^_o:ww` We cram most of the tests into a single function to save csnames. First treat the case $b = 0$: $a^0 = 1$ for any a , even `nan`. Then test the sign of a .

- If it is positive, and a is a normal number, call `__fp_pow_normal:ww` followed by the two `fp` a and b . For $a = +0$ or $+\infty$, call `__fp_pow_zero_or_inf:ww` instead, to return either $+0$ or $+\infty$ as appropriate.

- If a is a `nan`, then skip to the next semicolon (which happens to be conveniently the end of b) and return `nan`.
- Finally, if a is negative, compute a^b (`__fp_pow_normal:ww` which ignores the sign of its first operand), and keep an extra copy of a and b (the second brace group, containing $\{ b a \}$, is inserted between a and b). Then do some tests to find the final sign of the result if it exists.

```

14444 \cs_new:cpn { __fp_ \iow_char:N \^_o:ww }
14445   \s__fp \__fp_chk:w #1#2#3; \s__fp \__fp_chk:w #4#5#6;
14446   {
14447     \if_meaning:w 0 #4
14448       \__fp_case_return_o:Nw \c_one_fp
14449     \fi:
14450     \if_case:w #2 \exp_stop_f:
14451       \exp_after:wN \use_i:nn
14452     \or:
14453       \__fp_case_return_o:Nw \c_nan_fp
14454     \else:
14455       \exp_after:wN \__fp_pow_neg:www
14456       \exp:w \exp_end_continue_f:w \exp_after:wN \use:nn
14457     \fi:
14458     {
14459       \if_meaning:w 1 #1
14460         \exp_after:wN \__fp_pow_normal:ww
14461       \else:
14462         \exp_after:wN \__fp_pow_zero_or_inf:ww
14463       \fi:
14464       \s__fp \__fp_chk:w #1#2#3;
14465     }
14466     { \s__fp \__fp_chk:w #4#5#6; \s__fp \__fp_chk:w #1#2#3; }
14467     \s__fp \__fp_chk:w #4#5#6;
14468   }

```

(End definition for `__fp_^o:ww`.)

`__fp_pow_zero_or_inf:ww`

Raising -0 or $-\infty$ to `nan` yields `nan`. For other powers, the result is $+0$ if 0 is raised to a positive power or ∞ to a negative power, and $+\infty$ otherwise. Thus, if the type of a and the sign of b coincide, the result is 0 , since those conveniently take the same possible values, 0 and 2 . Otherwise, either $a = \pm\infty$ and $b > 0$ and the result is $+\infty$, or $a = \pm 0$ with $b < 0$ and we have a division by zero unless $b = -\infty$.

```

14469 \cs_new:Npn \__fp_pow_zero_or_inf:ww
14470   \s__fp \__fp_chk:w #1#2; \s__fp \__fp_chk:w #3#4
14471   {
14472     \if_meaning:w 1 #4
14473       \__fp_case_return_same_o:w
14474     \fi:
14475     \if_meaning:w #1 #4
14476       \__fp_case_return_o:Nw \c_zero_fp
14477     \fi:
14478     \if_meaning:w 2 #1
14479       \__fp_case_return_o:Nw \c_inf_fp
14480     \fi:
14481     \if_meaning:w 2 #3

```



```

14482     \__fp_case_return_o:Nw \c_inf_fp
14483 \else:
14484     \__fp_case_use:nw
14485     {
14486         \__fp_division_by_zero_o:NNww \c_inf_fp ^
14487         \s__fp \__fp_chk:w #1 #2 ;
14488     }
14489 \fi:
14490 \s__fp \__fp_chk:w #3#4
14491 }

```

(End definition for __fp_pow_zero_or_inf:ww.)

__fp_pow_normal:ww

We have in front of us a , and $b \neq 0$, we know that a is a normal number, and we wish to compute $|a|^b$. If $|a| = 1$, we return 1, unless $a = -1$ and b is **nan**. Indeed, returning 1 at this point would wrongly raise “invalid” when the sign is considered. If $|a| \neq 1$, test the type of b :

- 0 Impossible, we already filtered $b = \pm 0$.
- 1 Call __fp_pow_npos:ww.
- 2 Return $+\infty$ or $+0$ depending on the sign of b and whether the exponent of a is positive or not.
- 3 Return b .

```

14492 \cs_new:Npn \__fp_pow_normal:ww
14493 \s__fp \__fp_chk:w 1 #1#2#3; \s__fp \__fp_chk:w #4#5
14494 {
14495     \if_int_compare:w \__str_if_eq_x:nn { #2 #3 }
14496         { 1 {1000} {0000} {0000} {0000} } = 0 \exp_stop_f:
14497         \if_int_compare:w #4 #1 = 32 \exp_stop_f:
14498         \exp_after:wN \__fp_case_return_ii_o:ww
14499         \fi:
14500         \__fp_case_return_o:Nww \c_one_fp
14501     \fi:
14502     \if_case:w #4 \exp_stop_f:
14503     \or:
14504         \exp_after:wN \__fp_pow_npos:Nww
14505         \exp_after:wN #5
14506     \or:
14507         \if_meaning:w 2 #5 \exp_after:wN \reverse_if:N \fi:
14508         \if_int_compare:w #2 > 0 \exp_stop_f:
14509         \exp_after:wN \__fp_case_return_o:Nww
14510         \exp_after:wN \c_inf_fp
14511     \else:
14512         \exp_after:wN \__fp_case_return_o:Nww
14513         \exp_after:wN \c_zero_fp
14514     \fi:
14515     \or:
14516         \__fp_case_return_ii_o:ww
14517     \fi:
14518     \s__fp \__fp_chk:w 1 #1 {#2} #3 ;
14519     \s__fp \__fp_chk:w #4 #5
14520 }

```

(End definition for _fp_pow_normal:ww.)

_fp_pow_npos:Nww We now know that $a \neq \pm 1$ is a normal number, and b is a normal number too. We want to compute $|a|^b = (|x| \cdot 10^n)^{y \cdot 10^p} = \exp((\ln|x| + n \ln(10)) \cdot y \cdot 10^p) = \exp(z)$. To compute the exponential accurately, we need to know the digits of z up to the 16-th position. Since the exponential of 10^5 is infinite, we only need at most 21 digits, hence the fixed point result of _fp_ln_o:w is precise enough for our needs. Start an integer expression for the decimal exponent of $e^{|z|}$. If z is negative, negate that decimal exponent, and prepare to take the inverse when converting from the fixed point to the floating point result.

```

14521 \cs_new:Npn \_fp_pow_npos:Nww #1 \s__fp \_fp_chk:w 1#2#3
14522 {
14523   \exp_after:wN \_fp_sanitize:Nw
14524   \exp_after:wN 0
14525   \__int_value:w
14526   \if:w #1 \if_int_compare:w #3 > 0 \exp_stop_f: 0 \else: 2 \fi:
14527   \exp_after:wN \_fp_pow_npos_aux:NNnw
14528   \exp_after:wN +
14529   \exp_after:wN \_fp_fixed_to_float:wN
14530   \else:
14531   \exp_after:wN \_fp_pow_npos_aux:NNnw
14532   \exp_after:wN -
14533   \exp_after:wN \_fp_fixed_inv_to_float:wN
14534   \fi:
14535   {#3}
14536 }

```

(End definition for _fp_pow_npos:Nww.)

_fp_pow_npos_aux:NNnw The first argument is the conversion function from fixed point to float. Then comes an exponent and the 4 brace groups of x , followed by b . Compute $-\ln(x)$.

```

14537 \cs_new:Npn \_fp_pow_npos_aux:NNnw #1#2#3#4#5; \s__fp \_fp_chk:w 1#6#7#8;
14538 {
14539   #1
14540   \__int_eval:w
14541   \_fp_ln_significand:NNNNnnN #4#5
14542   \_fp_pow_exponent:wnN {#3}
14543   \_fp_fixed_mul:wwN #8 {0000}{0000} ;
14544   \_fp_pow_B:wwN #7;
14545   #1 #2 0 % fixed_to_float:wN
14546 }
14547 \cs_new:Npn \_fp_pow_exponent:wnN #1; #2
14548 {
14549   \if_int_compare:w #2 > 0 \exp_stop_f:
14550   \exp_after:wN \_fp_pow_exponent:Nwnnnnw % n\ln(10) - (-\ln(x))
14551   \exp_after:wN +
14552   \else:
14553   \exp_after:wN \_fp_pow_exponent:Nwnnnnw % -(\ln|\ln(10) + (-\ln(x)))
14554   \exp_after:wN -
14555   \fi:
14556   #2; #1;
14557 }
14558 \cs_new:Npn \_fp_pow_exponent:Nwnnnnw #1#2; #3#4#5#6#7#8;
14559 { %^A todo: use that in ln.

```

```

14560 \exp_after:wN \__fp_fixed_mul_after:wwn
14561 \__int_value:w \__int_eval:w \c__fp_leading_shift_int
14562 \exp_after:wN \__fp_pack:NNNNNw
14563 \__int_value:w \__int_eval:w \c__fp_middle_shift_int
14564 #1#2*23025 - #1 #3
14565 \exp_after:wN \__fp_pack:NNNNNw
14566 \__int_value:w \__int_eval:w \c__fp_middle_shift_int
14567 #1 #2*8509 - #1 #4
14568 \exp_after:wN \__fp_pack:NNNNNw
14569 \__int_value:w \__int_eval:w \c__fp_middle_shift_int
14570 #1 #2*2994 - #1 #5
14571 \exp_after:wN \__fp_pack:NNNNNw
14572 \__int_value:w \__int_eval:w \c__fp_middle_shift_int
14573 #1 #2*0456 - #1 #6
14574 \exp_after:wN \__fp_pack:NNNNNw
14575 \__int_value:w \__int_eval:w \c__fp_trailing_shift_int
14576 #1 #2*8401 - #1 #7
14577 #1 ( #2*7991 - #8 ) / 1 0000 ; ;
14578 }
14579 \cs_new:Npn \__fp_pow_B:wwN #1#2#3#4#5#6; #7;
14580 {
14581 \if_int_compare:w #7 < 0 \exp_stop_f:
14582 \exp_after:wN \__fp_pow_C_neg:w \__int_value:w -
14583 \else:
14584 \if_int_compare:w #7 < 22 \exp_stop_f:
14585 \exp_after:wN \__fp_pow_C_pos:w \__int_value:w
14586 \else:
14587 \exp_after:wN \__fp_pow_C_overflow:w \__int_value:w
14588 \fi:
14589 \fi:
14590 #7 \exp_after:wN ;
14591 \__int_value:w \__int_eval:w 10 0000 + #1 \__int_eval_end:
14592 #2#3#4#5#6 0000 0000 0000 0000 0000 0000 ; %^A todo: how many 0?
14593 }
14594 \cs_new:Npn \__fp_pow_C_overflow:w #1; #2; #3
14595 {
14596 + 2 * \c__fp_max_exponent_int
14597 \exp_after:wN \__fp_fixed_continue:wn \c__fp_one_fixed_t1 ;
14598 }
14599 \cs_new:Npn \__fp_pow_C_neg:w #1 ; 1
14600 {
14601 \exp_after:wN \exp_after:wN \exp_after:wN \__fp_pow_C_pack:w
14602 \prg_replicate:nn {#1} {0}
14603 }
14604 \cs_new:Npn \__fp_pow_C_pos:w #1; 1
14605 { \__fp_pow_C_pos_loop:wN #1; }
14606 \cs_new:Npn \__fp_pow_C_pos_loop:wN #1; #2
14607 {
14608 \if_meaning:w 0 #1
14609 \exp_after:wN \__fp_pow_C_pack:w
14610 \exp_after:wN #2
14611 \else:
14612 \if_meaning:w 0 #2
14613 \exp_after:wN \__fp_pow_C_pos_loop:wN \__int_value:w

```

```

14614         \else:
14615             \exp_after:wN \__fp_pow_C_overflow:w \__int_value:w
14616         \fi:
14617         \__int_eval:w #1 - 1 \exp_after:wN ;
14618     \fi:
14619 }
14620 \cs_new:Npn \__fp_pow_C_pack:w
14621 { \exp_after:wN \__fp_exp_large_v:wN \c__fp_one_fixed_tl ; }

```

(End definition for __fp_pow_npos_aux:NNnw.)

__fp_pow_neg:www
__fp_pow_neg_aux:wNN

This function is followed by three floating point numbers: a^b , $a \in [-\infty, -0]$, and b . If b is an even integer (case -1), $a^b = a^b$. If b is an odd integer (case 0), $a^b = -a^b$, obtained by a call to __fp_pow_neg_aux:wNN. Otherwise, the sign is undefined. This is invalid, unless a^b turns out to be $+0$ or nan , in which case we return that as a^b . In particular, since the underflow detection occurs before __fp_pow_neg:www is called, $(-0.1)**(12345.67)$ will give $+0$ rather than complaining that the sign is not defined.

```

14622 \cs_new:Npn \__fp_pow_neg:www \s__fp \__fp_chk:w #1#2; #3; #4;
14623 {
14624     \if_case:w \__fp_pow_neg_case:w #4 ;
14625     \exp_after:wN \__fp_pow_neg_aux:wNN
14626 \or:
14627     \if_int_compare:w \__int_eval:w #1 / 2 = 1 \exp_stop_f:
14628     \__fp_invalid_operation_o:Nww ^ #3; #4;
14629     \exp:w \exp_end_continue_f:w
14630     \exp_after:wN \exp_after:wN
14631     \exp_after:wN \__fp_use_none_until_s:w
14632 \fi:
14633 \fi:
14634 \__fp_exp_after_o:w
14635 \s__fp \__fp_chk:w #1#2;
14636 }
14637 \cs_new:Npn \__fp_pow_neg_aux:wNN #1 \s__fp \__fp_chk:w #2#3
14638 {
14639     \exp_after:wN \__fp_exp_after_o:w
14640     \exp_after:wN \s__fp
14641     \exp_after:wN \__fp_chk:w
14642     \exp_after:wN #2
14643     \__int_value:w \__int_eval:w 2 - #3 \__int_eval_end:
14644 }

```

(End definition for __fp_pow_neg:www and __fp_pow_neg_aux:wNN.)

__fp_pow_neg_case:w
__fp_pow_neg_case_aux:nnnn
__fp_pow_neg_case_aux:w

This function expects a floating point number, and determines its “parity”. It should be used after \if_case:w or in an integer expression. It gives -1 if the number is an even integer divided by some power of 5, 0 if the number is an odd integer divided by some power of 5, and 1 otherwise. Zeros and $\pm\infty$ are even (because very large finite floating points are even), while nan is a non-integer. The sign of normal numbers is irrelevant to parity. The idea is to repeatedly multiply the number by 5 (by halving the mantissa and shifting the exponent) until the mantissa is odd (this can only happen at most 53 times since $2^{54} > 10^{16}$): if the resulting exponent is larger than 16 the parity is even, if it is exactly 16 the parity is odd, and otherwise we should return 1. Of course there is a shortcut: we stop as soon as the exponent exceeds 16.

```

14645 \cs_new:Npn \__fp_pow_neg_case:w \s__fp \__fp_chk:w #1#2#3;
14646 {
14647   \if_case:w #1 \exp_stop_f:
14648     -1
14649   \or: \__fp_pow_neg_case_aux:nnnnn #3
14650   \or: -1
14651   \else: 1
14652   \fi:
14653   \exp_stop_f:
14654 }
14655 \cs_new:Npn \__fp_pow_neg_case_aux:nnnnn #1#2#3#4#5
14656 { \__fp_pow_neg_case_aux:w #1 ; #2 #3 ; #4 #5 ; }
14657 \cs_new:Npn \__fp_pow_neg_case_aux:w #1 ; #2 ; #3 ;
14658 {
14659   \if_int_compare:w #1 > \c__fp_prec_int
14660     -1
14661   \else:
14662     \if_int_odd:w #3 \exp_stop_f:
14663     \if_int_compare:w #1 = \c__fp_prec_int
14664       0
14665     \else:
14666       1
14667     \fi:
14668   \else:
14669     \exp_after:wN \__fp_pow_neg_case_aux:w
14670     \__int_value:w \__int_eval:w #1 + 1 \exp_after:wN ;
14671     \__int_value:w \__int_eval:w (#2 + 1) / 2 - 1 \exp_after:wN ;
14672     \__int_value:w \__int_eval:w
14673     \if_int_odd:w #2 \exp_stop_f: 5000 0000 + \fi: #3 / 2 ;
14674   \fi:
14675   \fi:
14676 }

```

(End definition for `__fp_pow_neg_case:w`, `__fp_pow_neg_case_aux:nnnnn`, and `__fp_pow_neg_case_aux:w`.)

```

14677 </initex | package>

```

28 13fp-trig Implementation

```

14678 <*initex | package>

```

```

14679 <@@=fp>

```

28.1 Direct trigonometric functions

The approach for all trigonometric functions (sine, cosine, tangent, cotangent, cosecant, and secant), with arguments given in radians or in degrees, is the same.

- Filter out special cases (± 0 , $\pm \infty$ and NaN).
- Keep the sign for later, and work with the absolute value $|x|$ of the argument.
- Small numbers ($|x| < 1$ in radians, $|x| < 10$ in degrees) are converted to fixed point numbers (and to radians if $|x|$ is in degrees).

- For larger numbers, we need argument reduction. Subtract a multiple of $\pi/2$ (in degrees, 90) to bring the number to the range to $[0, \pi/2)$ (in degrees, $[0, 90)$).
- Reduce further to $[0, \pi/4]$ (in degrees, $[0, 45]$) using $\sin x = \cos(\pi/2 - x)$, and when working in degrees, convert to radians.
- Use the appropriate power series depending on the octant $\lfloor \frac{x}{\pi/4} \rfloor \bmod 8$ (in degrees, the same formula with $\pi/4 \rightarrow 45$), the sign, and the function to compute.

28.1.1 Filtering special cases

`__fp_sin_o:w` This function, and its analogs for `cos`, `csc`, `sec`, `tan`, and `cot` instead of `sin`, are followed either by `\use_i:nn` and a float in radians or by `\use_ii:nn` and a float in degrees. The sine of ± 0 or NaN is the same float. The sine of $\pm\infty$ raises an invalid operation exception with the appropriate function name. Otherwise, call the `trig` function to perform argument reduction and if necessary convert the reduced argument to radians. Then, `__fp_sin_series_o:NNwww` will be called to compute the Taylor series: this function receives a sign `#3`, an initial octant of 0, and the function `__fp_ep_to_float:wwN` which converts the result of the series to a floating point directly rather than taking its inverse, since $\sin(x) = \#3 \sin|x|$.

```

14680 \cs_new:Npn \__fp_sin_o:w #1 \s__fp \__fp_chk:w #2#3#4; @
14681 {
14682   \if_case:w #2 \exp_stop_f:
14683     \__fp_case_return_same_o:w
14684   \or: \__fp_case_use:nw
14685     {
14686       \__fp_trig:NNNNwn #1 \__fp_sin_series_o:NNwww
14687       \__fp_ep_to_float:wwN #3 0
14688     }
14689   \or: \__fp_case_use:nw
14690     { \__fp_invalid_operation_o:fw { #1 { sin } { sind } } }
14691   \else: \__fp_case_return_same_o:w
14692   \fi:
14693   \s__fp \__fp_chk:w #2 #3 #4;
14694 }

```

(End definition for `__fp_sin_o:w`.)

`__fp_cos_o:w` The cosine of ± 0 is 1. The cosine of $\pm\infty$ raises an invalid operation exception. The cosine of NaN is itself. Otherwise, the `trig` function reduces the argument to at most half a right-angle and converts if necessary to radians. We will then call the same series as for sine, but using a positive sign 0 regardless of the sign of x , and with an initial octant of 2, because $\cos(x) = +\sin(\pi/2 + |x|)$.

```

14695 \cs_new:Npn \__fp_cos_o:w #1 \s__fp \__fp_chk:w #2#3; @
14696 {
14697   \if_case:w #2 \exp_stop_f:
14698     \__fp_case_return_o:Nw \c_one_fp
14699   \or: \__fp_case_use:nw
14700     {
14701       \__fp_trig:NNNNwn #1 \__fp_sin_series_o:NNwww
14702       \__fp_ep_to_float:wwN 0 2
14703     }
14704   \or: \__fp_case_use:nw

```

```

14705         { \__fp_invalid_operation_o:fw { #1 { cos } { cosd } } }
14706     \else: \__fp_case_return_same_o:w
14707     \fi:
14708     \s__fp \__fp_chk:w #2 #3;
14709 }

```

(End definition for __fp_cos_o:w.)

__fp_csc_o:w The cosecant of ± 0 is $\pm\infty$ with the same sign, with a division by zero exception (see **__fp_cot_zero_o:Nfw** defined below), which requires the function name. The cosecant of $\pm\infty$ raises an invalid operation exception. The cosecant of NaN is itself. Otherwise, the **trig** function performs the argument reduction, and converts if necessary to radians before calling the same series as for sine, using the sign #3, a starting octant of 0, and inverting during the conversion from the fixed point sine to the floating point result, because $\csc(x) = \#3(\sin|x|)^{-1}$.

```

14710 \cs_new:Npn \__fp_csc_o:w #1 \s__fp \__fp_chk:w #2#3#4; @
14711 {
14712     \if_case:w #2 \exp_stop_f:
14713         \__fp_cot_zero_o:Nfw #3 { #1 { csc } { cscd } }
14714     \or: \__fp_case_use:nw
14715         {
14716             \__fp_trig:NNNNNwn #1 \__fp_sin_series_o:NNwww
14717             \__fp_ep_inv_to_float:wwN #3 0
14718         }
14719     \or: \__fp_case_use:nw
14720         { \__fp_invalid_operation_o:fw { #1 { csc } { cscd } } }
14721     \else: \__fp_case_return_same_o:w
14722     \fi:
14723     \s__fp \__fp_chk:w #2 #3 #4;
14724 }

```

(End definition for __fp_csc_o:w.)

__fp_sec_o:w The secant of ± 0 is 1. The secant of $\pm\infty$ raises an invalid operation exception. The secant of NaN is itself. Otherwise, the **trig** function reduces the argument and turns it to radians before calling the same series as for sine, using a positive sign 0, a starting octant of 2, and inverting upon conversion, because $\sec(x) = +1/\sin(\pi/2 + |x|)$.

```

14725 \cs_new:Npn \__fp_sec_o:w #1 \s__fp \__fp_chk:w #2#3; @
14726 {
14727     \if_case:w #2 \exp_stop_f:
14728         \__fp_case_return_o:Nw \c_one_fp
14729     \or: \__fp_case_use:nw
14730         {
14731             \__fp_trig:NNNNNwn #1 \__fp_sin_series_o:NNwww
14732             \__fp_ep_inv_to_float:wwN 0 2
14733         }
14734     \or: \__fp_case_use:nw
14735         { \__fp_invalid_operation_o:fw { #1 { sec } { secd } } }
14736     \else: \__fp_case_return_same_o:w
14737     \fi:
14738     \s__fp \__fp_chk:w #2 #3;
14739 }

```

(End definition for __fp_sec_o:w.)

`__fp_tan_o:w` The tangent of ± 0 or NaN is the same floating point number. The tangent of $\pm\infty$ raises an invalid operation exception. Once more, the `trig` function does the argument reduction step and conversion to radians before calling `__fp_tan_series_o:NNwww`, with a sign `#3` and an initial octant of 1 (this shift is somewhat arbitrary). See `__fp_cot_o:w` for an explanation of the 0 argument.

```

14740 \cs_new:Npn \__fp_tan_o:w #1 \s__fp \__fp_chk:w #2#3#4; @
14741 {
14742   \if_case:w #2 \exp_stop_f:
14743     \__fp_case_return_same_o:w
14744   \or: \__fp_case_use:nw
14745     {
14746       \__fp_trig:NNNNwn #1
14747       \__fp_tan_series_o:NNwww 0 #3 1
14748     }
14749   \or: \__fp_case_use:nw
14750     { \__fp_invalid_operation_o:fw { #1 { tan } { tand } } }
14751   \else: \__fp_case_return_same_o:w
14752   \fi:
14753   \s__fp \__fp_chk:w #2 #3 #4;
14754 }

```

(End definition for `__fp_tan_o:w`.)

`__fp_cot_o:w` The cotangent of ± 0 is $\pm\infty$ with the same sign, with a division by zero exception (see `__fp_cot_zero_o:Nfw`). The cotangent of $\pm\infty$ raises an invalid operation exception. The cotangent of NaN is itself. We use $\cot x = -\tan(\pi/2 + x)$, and the initial octant for the tangent was chosen to be 1, so the octant here starts at 3. The change in sign is obtained by feeding `__fp_tan_series_o:NNwww` two signs rather than just the sign of the argument: the first of those indicates whether we compute tangent or cotangent. Those signs are eventually combined.

```

14755 \cs_new:Npn \__fp_cot_o:w #1 \s__fp \__fp_chk:w #2#3#4; @
14756 {
14757   \if_case:w #2 \exp_stop_f:
14758     \__fp_cot_zero_o:Nfw #3 { #1 { cot } { cotd } }
14759   \or: \__fp_case_use:nw
14760     {
14761       \__fp_trig:NNNNwn #1
14762       \__fp_tan_series_o:NNwww 2 #3 3
14763     }
14764   \or: \__fp_case_use:nw
14765     { \__fp_invalid_operation_o:fw { #1 { cot } { cotd } } }
14766   \else: \__fp_case_return_same_o:w
14767   \fi:
14768   \s__fp \__fp_chk:w #2 #3 #4;
14769 }
14770 \cs_new:Npn \__fp_cot_zero_o:Nfw #1#2#3 \fi:
14771 {
14772   \fi:
14773   \token_if_eq_meaning:NNTF 0 #1
14774     { \exp_args:NNf \__fp_division_by_zero_o:Nnw \c_inf_fp }
14775     { \exp_args:NNf \__fp_division_by_zero_o:Nnw \c_minus_inf_fp }
14776   {#2}
14777 }

```


(End definition for `_fp_cot_o:w` and `_fp_cot_zero_o:Nfw`.)

28.1.2 Distinguishing small and large arguments

`_fp_trig:NNNNwn` The first argument is `\use_i:nn` if the operand is in radians and `\use_ii:nn` if it is in degrees. Arguments #2 to #5 control what trigonometric function we compute, and #6 to #8 are pieces of a normal floating point number. Call the `_series` function #2, with arguments #3, either a conversion function (`_fp_ep_to_float:wN` or `_fp_ep_inv_to_float:wN`) or a sign 0 or 2 when computing tangent or cotangent; #4, a sign 0 or 2; the octant, computed in an integer expression starting with #5 and stopped by a period; and a fixed point number obtained from the floating point number by argument reduction (if necessary) and conversion to radians (if necessary). Any argument reduction adjusts the octant accordingly by leaving a (positive) shift into its integer expression. Let us explain the integer comparison. Two of the four `\exp_after:wN` are expanded, the expansion hits the test, which is true if the float is at least 1 when working in radians, and at least 10 when working in degrees. Then one of the remaining `\exp_after:wN` hits #1, which picks the `trig` or `trigd` function in whichever branch of the conditional was taken. The final `\exp_after:wN` closes the conditional. At the end of the day, a number is `large` if it is ≥ 1 in radians or ≥ 10 in degrees, and `small` otherwise. All four `trig/trigd` auxiliaries receive the operand as an extended-precision number.

```

14778 \cs_new:Npn \_fp_trig:NNNNwn #1#2#3#4#5 \s_fp \_fp_chk:w 1#6#7#8;
14779 {
14780   \exp_after:wN #2
14781   \exp_after:wN #3
14782   \exp_after:wN #4
14783   \_int_value:w \_int_eval:w #5
14784   \exp_after:wN \exp_after:wN \exp_after:wN \exp_after:wN
14785   \if_int_compare:w #7 > #1 0 1 \exp_stop_f:
14786   #1 \_fp_trig_large:ww \_fp_trigd_large:ww
14787   \else:
14788   #1 \_fp_trig_small:ww \_fp_trigd_small:ww
14789   \fi:
14790   #7,#8{0000}{0000};
14791 }

```

(End definition for `_fp_trig:NNNNwn`.)

28.1.3 Small arguments

`_fp_trig_small:ww` This receives a small extended-precision number in radians and converts it to a fixed point number. Some trailing digits may be lost in the conversion, so we keep the original floating point number around: when computing sine or tangent (or their inverses), the last step will be to multiply by the floating point number (as an extended-precision number) rather than the fixed point number. The period serves to end the integer expression for the octant.

```

14792 \cs_new:Npn \_fp_trig_small:ww #1,#2;
14793 { \_fp_ep_to_fixed:wwn #1,#2; . #1,#2; }

```

(End definition for `_fp_trig_small:ww`.)

`_fp_trigd_small:ww` Convert the extended-precision number to radians, then call `_fp_trig_small:ww` to massage it in the form appropriate for the `_series` auxiliary.

```

14794 \cs_new:Npn \__fp_trigd_small:ww #1,#2;
14795 {
14796   \__fp_ep_mul_raw:wwwN
14797   -1,{1745}{3292}{5199}{4329}{5769}{2369}; #1,#2;
14798   \__fp_trig_small:ww
14799 }

```

(End definition for __fp_trigd_small:ww.)

28.1.4 Argument reduction in degrees

__fp_trigd_large:ww Note that $25 \times 360 = 9000$, so $10^{k+1} \equiv 10^k \pmod{360}$ for $k \geq 3$. When the exponent #1 is very large, we can thus safely replace it by 22 (or even 19). We turn the floating point number into a fixed point number with two blocks of 8 digits followed by five blocks of 4 digits. The original float is $100 \times \langle block_1 \rangle \cdots \langle block_3 \rangle . \langle block_4 \rangle \cdots \langle block_7 \rangle$, or is equal to it modulo 360 if the exponent #1 is very large. The first auxiliary finds $\langle block_1 \rangle + \langle block_2 \rangle \pmod{9}$, a single digit, and prepends it to the 4 digits of $\langle block_3 \rangle$. It also unpacks $\langle block_4 \rangle$ and grabs the 4 digits of $\langle block_7 \rangle$. The second auxiliary grabs the $\langle block_3 \rangle$ plus any contribution from the first two blocks as #1, the first digit of $\langle block_4 \rangle$ (just after the decimal point in hundreds of degrees) as #2, and the three other digits as #3. It finds the quotient and remainder of #1#2 modulo 9, adds twice the quotient to the integer expression for the octant, and places the remainder (between 0 and 8) before #3 to form a new $\langle block_4 \rangle$. The resulting fixed point number is $x \in [0, 0.9]$. If $x \geq 0.45$, we add 1 to the octant and feed $0.9 - x$ with an exponent of 2 (to compensate the fact that we are working in units of hundreds of degrees rather than degrees) to __fp_trigd_small:ww. Otherwise, we feed it x with an exponent of 2. The third auxiliary also discards digits which were not packed into the various $\langle blocks \rangle$. Since the original exponent #1 is at least 2, those are all 0 and no precision is lost (#6 and #7 are four 0 each).

```

14800 \cs_new:Npn \__fp_trigd_large:ww #1, #2#3#4#5#6#7;
14801 {
14802   \exp_after:wN \__fp_pack_eight:wNNNNNNNN
14803   \exp_after:wN \__fp_pack_eight:wNNNNNNNN
14804   \exp_after:wN \__fp_pack_twice_four:wNNNNNNNN
14805   \exp_after:wN \__fp_pack_twice_four:wNNNNNNNN
14806   \exp_after:wN \__fp_trigd_large_auxi:nnnnwNNNN
14807   \exp_after:wN ;
14808   \exp:w \exp_end_continue_f:w
14809   \prg_replicate:nn { \int_max:nn { 22 - #1 } { 0 } } { 0 }
14810   #2#3#4#5#6#7 0000 0000 0000 !
14811 }
14812 \cs_new:Npn \__fp_trigd_large_auxi:nnnnwNNNN #1#2#3#4#5; #6#7#8#9
14813 {
14814   \exp_after:wN \__fp_trigd_large_auxii:wNw
14815   \__int_value:w \__int_eval:w #1 + #2
14816   - (#1 + #2 - 4) / 9 * 9 \__int_eval_end:
14817   #3;
14818   #4; #5{#6#7#8#9};
14819 }
14820 \cs_new:Npn \__fp_trigd_large_auxii:wNw #1; #2#3;
14821 {
14822   + (#1#2 - 4) / 9 * 2
14823   \exp_after:wN \__fp_trigd_large_auxiii:www
14824   \__int_value:w \__int_eval:w #1#2

```

```

14825         - (#1#2 - 4) / 9 * 9 \_int_eval_end: #3 ;
14826     }
14827 \cs_new:Npn \_fp_trigd_large_auxiii:www #1; #2; #3!
14828 {
14829     \if_int_compare:w #1 < 4500 \exp_stop_f:
14830         \exp_after:wN \_fp_use_i_until_s:nw
14831         \exp_after:wN \_fp_fixed_continue:wn
14832     \else:
14833         + 1
14834     \fi:
14835     \_fp_fixed_sub:wnn {9000}{0000}{0000}{0000}{0000}{0000};
14836     {#1}#2{0000}{0000};
14837     { \_fp_trigd_small:ww 2, }
14838 }

```

(End definition for `_fp_trigd_large:ww` and others.)

28.1.5 Argument reduction in radians

Arguments greater or equal to 1 need to be reduced to a range where we only need a few terms of the Taylor series. We reduce to the range $[0, 2\pi]$ by subtracting multiples of 2π , then to the smaller range $[0, \pi/2]$ by subtracting multiples of $\pi/2$ (keeping track of how many times $\pi/2$ is subtracted), then to $[0, \pi/4]$ by mapping $x \rightarrow \pi/2 - x$ if appropriate. When the argument is very large, say, 10^{100} , an equally large multiple of 2π must be subtracted, hence we must work with a very good approximation of 2π in order to get a sensible remainder modulo 2π .

Specifically, we multiply the argument by an approximation of $1/(2\pi)$ with 10048 digits, then discard the integer part of the result, keeping 52 digits of the fractional part. From the fractional part of $x/(2\pi)$ we deduce the octant (quotient of the first three digits by 125). We then multiply by 8 or -8 (the latter when the octant is odd), ignore any integer part (related to the octant), and convert the fractional part to an extended precision number, before multiplying by $\pi/4$ to convert back to a value in radians in $[0, \pi/4]$.

It is possible to prove that given the precision of floating points and their range of exponents, the 52 digits may start at most with 24 zeros. The 5 last digits are affected by carries from computations which are not done, hence we are left with at least $52 - 24 - 5 = 23$ significant digits, enough to round correctly up to $0.6 \cdot \text{ulp}$ in all cases.

`_fp_trig_inverse_two_pi:` This macro expands to `,,!` or `,!` followed by 10112 decimals of $10^{-16}/(2\pi)$. The number of decimals we really need is the maximum exponent plus the number of digits we will need later, 52, plus 12 ($4 - 1$ groups of 4 digits). We store the decimals as a control sequence name, and convert it to a token list when required: strings take up less memory than their token list representation.

```

14839 \cs_new:Npx \_fp_trig_inverse_two_pi:
14840 {
14841     \exp_not:n { \exp_after:wN \use_none:n \token_to_str:N }
14842     \cs:w , , !
14843     0000000000000000159154943091895335768883763372514362034459645740 ~
14844     4564487476673440588967976342265350901138027662530859560728427267 ~
14845     5795803689291184611457865287796741073169983922923996693740907757 ~
14846     3077746396925307688717392896217397661693362390241723629011832380 ~
14847     1142226997557159404618900869026739561204894109369378440855287230 ~

```

14848 9994644340024867234773945961089832309678307490616698646280469944 ~
14849 8652187881574786566964241038995874139348609983868099199962442875 ~
14850 5851711788584311175187671605465475369880097394603647593337680593 ~
14851 0249449663530532715677550322032477781639716602294674811959816584 ~
14852 0606016803035998133911987498832786654435279755070016240677564388 ~
14853 8495713108801221993761476813777647378906330680464579784817613124 ~
14854 2731406996077502450029775985708905690279678513152521001631774602 ~
14855 0924811606240561456203146484089248459191435211575407556200871526 ~
14856 6068022171591407574745827225977462853998751553293908139817724093 ~
14857 5825479707332871904069997590765770784934703935898280871734256403 ~
14858 6689511662545705943327631268650026122717971153211259950438667945 ~
14859 0376255608363171169525975812822494162333431451061235368785631136 ~
14860 3669216714206974696012925057833605311960859450983955671870995474 ~
14861 6510431623815517580839442979970999505254387566129445883306846050 ~
14862 7852915151410404892988506388160776196993073410389995786918905980 ~
14863 9373777206187543222718930136625526123878038753888110681406765434 ~
14864 0828278526933426799556070790386060352738996245125995749276297023 ~
14865 5940955843011648296411855777124057544494570217897697924094903272 ~
14866 9477021664960356531815354400384068987471769158876319096650696440 ~
14867 4776970687683656778104779795450353395758301881838687937766124814 ~
14868 9530599655802190835987510351271290432315804987196868777594656634 ~
14869 6221034204440855497850379273869429353661937782928735937843470323 ~
14870 0237145837923557118636341929460183182291964165008783079331353497 ~
14871 7909974586492902674506098936890945883050337030538054731232158094 ~
14872 3197676032283131418980974982243833517435698984750103950068388003 ~
14873 9786723599608024002739010874954854787923568261139948903268997427 ~
14874 0834961149208289037767847430355045684560836714793084567233270354 ~
14875 8539255620208683932409956221175331839402097079357077496549880868 ~
14876 6066360968661967037474542102831219251846224834991161149566556037 ~
14877 9696761399312829960776082779901007830360023382729879085402387615 ~
14878 5744543092601191005433799838904654921248295160707285300522721023 ~
14879 6017523313173179759311050328155109373913639645305792607180083617 ~
14880 9548767246459804739772924481092009371257869183328958862839904358 ~
14881 6866663975673445140950363732719174311388066383072592302759734506 ~
14882 0548212778037065337783032170987734966568490800326988506741791464 ~
14883 6835082816168533143361607309951498531198197337584442098416559541 ~
14884 5225064339431286444038388356150879771645017064706751877456059160 ~
14885 8716857857939226234756331711132998655941596890719850688744230057 ~
14886 5191977056900382183925622033874235362568083541565172971088117217 ~
14887 9593683256488518749974870855311659830610139214454460161488452770 ~
14888 2511411070248521739745103866736403872860099674893173561812071174 ~
14889 0478899368886556923078485023057057144063638632023685201074100574 ~
14890 8592281115721968003978247595300166958522123034641877365043546764 ~
14891 6456565971901123084767099309708591283646669191776938791433315566 ~
14892 5066981321641521008957117286238426070678451760111345080069947684 ~
14893 2235698962488051577598095339708085475059753626564903439445420581 ~
14894 7886435683042000315095594743439252544850674914290864751442303321 ~
14895 3324569511634945677539394240360905438335528292434220349484366151 ~
14896 46632286024776666604953140657343575530140908279880914786669343492 ~
14897 2737602634997829957018161964321233140475762897484082891174097478 ~
14898 2637899181699939487497715198981872666294601830539583275209236350 ~
14899 6853889228468247259972528300766856937583659722919824429747406163 ~
14900 8183113958306744348516928597383237392662402434501997809940402189 ~
14901 6134834273613676449913827154166063424829363741850612261086132119 ~

14902 9863346284709941839942742955915628333990480382117501161211667205 ~
14903 1912579303552929241134403116134112495318385926958490443846807849 ~
14904 0973982808855297045153053991400988698840883654836652224668624087 ~
14905 2540140400911787421220452307533473972538149403884190586842311594 ~
14906 6322744339066125162393106283195323883392131534556381511752035108 ~
14907 7459558201123754359768155340187407394340363397803881721004531691 ~
14908 8295194879591767395417787924352761740724605939160273228287946819 ~
14909 3649128949714953432552723591659298072479985806126900733218844526 ~
14910 7943350455801952492566306204876616134365339920287545208555344144 ~
14911 0990512982727454659118132223284051166615650709837557433729548631 ~
14912 2041121716380915606161165732000083306114606181280326258695951602 ~
14913 4632166138576614804719932707771316441201594960110632830520759583 ~
14914 4850305079095584982982186740289838551383239570208076397550429225 ~
14915 9847647071016426974384504309165864528360324933604354657237557916 ~
14916 1366324120457809969715663402215880545794313282780055246132088901 ~
14917 8742121092448910410052154968097113720754005710963406643135745439 ~
14918 9159769435788920793425617783022237011486424925239248728713132021 ~
14919 7667360756645598272609574156602343787436291321097485897150713073 ~
14920 9104072643541417970572226547980381512759579124002534468048220261 ~
14921 7342299001020483062463033796474678190501811830375153802879523433 ~
14922 4195502135689770912905614317878792086205744999257897569018492103 ~
14923 2420647138519113881475640209760554895793785141404145305151583964 ~
14924 2823265406020603311891586570272086250269916393751527887360608114 ~
14925 5569484210322407772727421651364234366992716340309405307480652685 ~
14926 0930165892136921414312937134106157153714062039784761842650297807 ~
14927 8606266969960809184223476335047746719017450451446166382846208240 ~
14928 8673595102371302904443779408535034454426334130626307459513830310 ~
14929 2293146934466832851766328241515210179422644395718121717021756492 ~
14930 1964449396532222187658488244511909401340504432139858628621083179 ~
14931 3939608443898019147873897723310286310131486955212620518278063494 ~
14932 5711866277825659883100535155231665984394090221806314454521212978 ~
14933 9734471488741258268223860236027109981191520568823472398358013366 ~
14934 0683786328867928619732367253606685216856320119489780733958419190 ~
14935 6659583867852941241871821727987506103946064819585745620060892122 ~
14936 8416394373846549589932028481236433466119707324309545859073361878 ~
14937 6290631850165106267576851216357588696307451999220010776676830946 ~
14938 9814975622682434793671310841210219520899481912444048751171059184 ~
14939 4139907889455775184621619041530934543802808938628073237578615267 ~
14940 7971143323241969857805637630180884386640607175368321362629671224 ~
14941 2609428540110963218262765120117022552929289655594608204938409069 ~
14942 0760692003954646191640021567336017909631872891998634341086903200 ~
14943 5796637103128612356988817640364252540837098108148351903121318624 ~
14944 7228181050845123690190646632235938872454630737272808789830041018 ~
14945 9485913673742589418124056729191238003306344998219631580386381054 ~
14946 2457893450084553280313511884341007373060595654437362488771292628 ~
14947 9807423539074061786905784443105274262641767830058221486462289361 ~
14948 9296692992033046693328438158053564864073184440599549689353773183 ~
14949 6726613130108623588021288043289344562140479789454233736058506327 ~
14950 0439981932635916687341943656783901281912202816229500333012236091 ~
14951 8587559201959081224153679499095448881099758919890811581163538891 ~
14952 6339402923722049848375224236209100834097566791710084167957022331 ~
14953 7897107102928884897013099533995424415335060625843921452433864640 ~
14954 3432440657317477553405404481006177612569084746461432976543900008 ~
14955 3826521145210162366431119798731902751191441213616962045693602633 ~

```

14956 6102355962140467029012156796418735746835873172331004745963339773 ~
14957 2477044918885134415363760091537564267438450166221393719306748706 ~
14958 2881595464819775192207710236743289062690709117919412776212245117 ~
14959 2354677115640433357720616661564674474627305622913332030953340551 ~
14960 3841718194605321501426328000879551813296754972846701883657425342 ~
14961 5016994231069156343106626043412205213831587971115075454063290657 ~
14962 0248488648697402872037259869281149360627403842332874942332178578 ~
14963 7750735571857043787379693402336902911446961448649769719434527467 ~
14964 4429603089437192540526658890710662062575509930379976658367936112 ~
14965 8137451104971506153783743579555867972129358764463093757203221320 ~
14966 2460565661129971310275869112846043251843432691552928458573495971 ~
14967 5042565399302112184947232132380516549802909919676815118022483192 ~
14968 5127372199792134331067642187484426215985121676396779352982985195 ~
14969 8545392106957880586853123277545433229161989053189053725391582222 ~
14970 923259727813342781825606488233760719681014481453198336237910767 ~
14971 1255017528826351836492103572587410356573894694875444694018175923 ~
14972 0609370828146501857425324969212764624247832210765473750568198834 ~
14973 5641035458027261252285503154325039591848918982630498759115406321 ~
14974 0354263890012837426155187877318375862355175378506956599570028011 ~
14975 5841258870150030170259167463020842412449128392380525772514737141 ~
14976 2310230172563968305553583262840383638157686828464330456805994018 ~
14977 7001071952092970177990583216417579868116586547147748964716547948 ~
14978 8312140431836079844314055731179349677763739898930227765607058530 ~
14979 4083747752640947435070395214524701683884070908706147194437225650 ~
14980 2823145872995869738316897126851939042297110721350756978037262545 ~
14981 8141095038270388987364516284820180468288205829135339013835649144 ~
14982 3004015706509887926715417450706686888783438055583501196745862340 ~
14983 8059532724727843829259395771584036885940989939255241688378793572 ~
14984 7967951654076673927031256418760962190243046993485989199060012977 ~
14985 7469214532970421677817261517850653008552559997940209969455431545 ~
14986 2745856704403686680428648404512881182309793496962721836492935516 ~
14987 2029872469583299481932978335803459023227052612542114437084359584 ~
14988 9443383638388317751841160881711251279233374577219339820819005406 ~
14989 3292937775306906607415304997682647124407768817248673421685881509 ~
14990 9133422075930947173855159340808957124410634720893194912880783576 ~
14991 3115829400549708918023366596077070927599010527028150868897828549 ~
14992 4340372642729262103487013992868853550062061514343078665396085995 ~
14993 0058714939141652065302070085265624074703660736605333805263766757 ~
14994 2018839497277047222153633851135483463624619855425993871933367482 ~
14995 0422097449956672702505446423243957506869591330193746919142980999 ~
14996 3424230550172665212092414559625960554427590951996824313084279693 ~
14997 7113207021049823238195747175985519501864630940297594363194450091 ~
14998 9150616049228764323192129703446093584259267276386814363309856853 ~
14999 2786024332141052330760658841495858718197071242995959226781172796 ~
15000 4438853796763139274314227953114500064922126500133268623021550837
15001 \cs_end:
15002 }

```

(End definition for _fp_trig_inverse_two_pi:.)

```

\_fp_trig_large:ww The exponent #1 is between 1 and 10000. We discard the integer part of  $10^{\#1-16}/(2\pi)$ ,
\_fp_trig_large_auxi:wwwwww that is, the first #1 digits of  $10^{-16}/(2\pi)$ , because it yields an integer contribution to
\_fp_trig_large_auxii:ww  $x/(2\pi)$ . The auxii auxiliary discards 64 digits at a time thanks to spaces inserted in the
\_fp_trig_large_auxiii:wwNNNNNNNN result of \_fp_trig_inverse_two_pi:, while auxiii discards 8 digits at a time, and
\_fp_trig_large_auxiv:wN

```

`auxiv` discards digits one at a time. Then 64 digits are packed into groups of 4 and the `auxv` auxiliary is called.

```

15003 \cs_new:Npn \__fp_trig_large:ww #1, #2#3#4#5#6;
15004 {
15005     \exp_after:wN \__fp_trig_large_auxi:wwwww
15006     \__int_value:w \__int_eval:w (#1 - 32) / 64 \exp_after:wN ,
15007     \__int_value:w \__int_eval:w (#1 - 4) / 8 \exp_after:wN ,
15008     \__int_value:w #1 \__fp_trig_inverse_two_pi: ;
15009     {#2}{#3}{#4}{#5} ;
15010 }
15011 \cs_new:Npn \__fp_trig_large_auxi:wwwww #1, #2, #3, #4!
15012 {
15013     \prg_replicate:nn {#1} { \__fp_trig_large_auxii:ww }
15014     \prg_replicate:nn { #2 - #1 * 8 }
15015     { \__fp_trig_large_auxiii:wNNNNNNNN }
15016     \prg_replicate:nn { #3 - #2 * 8 }
15017     { \__fp_trig_large_auxiv:wN }
15018     \prg_replicate:nn { 8 } { \__fp_pack_twice_four:wNNNNNNNN }
15019     \__fp_trig_large_auxv:www
15020 ;
15021 }
15022 \cs_new:Npn \__fp_trig_large_auxii:ww #1; #2 ~ { #1; }
15023 \cs_new:Npn \__fp_trig_large_auxiii:wNNNNNNNN
15024     #1; #2#3#4#5#6#7#8#9 { #1; }
15025 \cs_new:Npn \__fp_trig_large_auxiv:wN #1; #2 { #1; }

```

(End definition for `__fp_trig_large:ww` and others.)

```

\__fp_trig_large_auxv:www
\__fp_trig_large_auxvi:wNNNNNNNN
\__fp_trig_large_pack:NNNNw

```

First come the first 64 digits of the fractional part of $10^{*1-16}/(2\pi)$, arranged in 16 blocks of 4, and ending with a semicolon. Then some more digits of the same fractional part, ending with a semicolon, then 4 blocks of 4 digits holding the significand of the original argument. Multiply the 16-digit significand with the 64-digit fractional part: the `auxvi` auxiliary receives the significand as `#2#3#4#5` and 16 digits of the fractional part as `#6#7#8#9`, and computes one step of the usual ladder of `pack` functions we use for multiplication (see *e.g.*, `__fp_fixed_mul:wwn`), then discards one block of the fractional part to set things up for the next step of the ladder. We perform 13 such steps, replacing the last `middle` shift by the appropriate `trailing` shift, then discard the significand and remaining 3 blocks from the fractional part, as there are not enough digits to compute any more step in the ladder. The last semicolon closes the ladder, and we return control to the `auxvii` auxiliary.

```

15026 \cs_new:Npn \__fp_trig_large_auxv:www #1; #2; #3;
15027 {
15028     \exp_after:wN \__fp_use_i_until_s:nw
15029     \exp_after:wN \__fp_trig_large_auxvii:w
15030     \__int_value:w \__int_eval:w \c__fp_leading_shift_int
15031     \prg_replicate:nn { 13 }
15032     { \__fp_trig_large_auxvi:wNNNNNNNN }
15033     + \c__fp_trailing_shift_int - \c__fp_middle_shift_int
15034     \__fp_use_i_until_s:nw
15035     ; #3 #1 ; ;
15036 }
15037 \cs_new:Npn \__fp_trig_large_auxvi:wNNNNNNNN #1; #2#3#4#5#6#7#8#9
15038 {

```

```

15039 \exp_after:wN \_fp_trig_large_pack:NNNNw
15040 \_int_value:w \_int_eval:w \c\_fp\_middle\_shift\_int
15041 + #2*#9 + #3*#8 + #4*#7 + #5*#6
15042 #1; {#2}{#3}{#4}{#5} {#7}{#8}{#9}
15043 }
15044 \cs_new:Npn \_fp_trig_large_pack:NNNNw #1#2#3#4#5#6;
15045 { + #1#2#3#4#5 ; #6 }

```

(End definition for _fp_trig_large_auxv:www, _fp_trig_large_auxvi:wnnnnnnnn, and _fp_trig_large_pack:NNNNw.)

The `auxvii` auxiliary is followed by 52 digits and a semicolon. We find the octant as the integer part of 8 times what follows, or equivalently as the integer part of $\#1\#2\#3/125$, and add it to the surrounding integer expression for the octant. We then compute 8 times the 52-digit number, with a minus sign if the octant is odd. Again, the last `middle` shift is converted to a `trailing` shift. Any integer part (including negative values which come up when the octant is odd) is discarded by `_fp_use_i_until_s:nw`. The resulting fractional part should then be converted to radians by multiplying by $2\pi/8$, but first, build an extended precision number by abusing `_fp_ep_to_ep_loop:N` with the appropriate trailing markers. Finally, `_fp_trig_small:ww` sets up the argument for the functions which compute the Taylor series.

```

15046 \cs_new:Npn \_fp_trig_large_auxvii:w #1#2#3
15047 {
15048   \exp_after:wN \_fp_trig_large_auxviii:ww
15049   \_int_value:w \_int_eval:w (#1#2#3 - 62) / 125 ;
15050   #1#2#3
15051 }
15052 \cs_new:Npn \_fp_trig_large_auxviii:ww #1;
15053 {
15054   + #1
15055   \if_int_odd:w #1 \exp_stop_f:
15056   \exp_after:wN \_fp_trig_large_auxix:Nw
15057   \exp_after:wN -
15058   \else:
15059   \exp_after:wN \_fp_trig_large_auxix:Nw
15060   \exp_after:wN +
15061   \fi:
15062 }
15063 \cs_new:Npn \_fp_trig_large_auxix:Nw
15064 {
15065   \exp_after:wN \_fp\_use\_i\_until\_s:nw
15066   \exp_after:wN \_fp_trig_large_auxxi:w
15067   \_int_value:w \_int_eval:w \c\_fp\_leading\_shift\_int
15068   \prg_replicate:nn { 13 }
15069   { \_fp_trig_large_auxx:wnnnnn }
15070   + \c\_fp\_trailing\_shift\_int - \c\_fp\_middle\_shift\_int
15071   ;
15072 }
15073 \cs_new:Npn \_fp_trig_large_auxx:wnnnnn #1; #2 #3#4#5#6
15074 {
15075   \exp_after:wN \_fp_trig_large_pack:NNNNw
15076   \_int_value:w \_int_eval:w \c\_fp\_middle\_shift\_int
15077   #2 8 * #3#4#5#6
15078   #1; #2

```



```

15079 }
15080 \cs_new:Npn \__fp_trig_large_auxxi:w #1;
15081 {
15082   \exp_after:wN \__fp_ep_mul_raw:wwwN
15083   \__int_value:w \__int_eval:w 0 \__fp_ep_to_ep_loop:N #1 ; ; !
15084   0,{7853}{9816}{3397}{4483}{0961}{5661};
15085   \__fp_trig_small:ww
15086 }

```

(End definition for `__fp_trig_large_auxvii:w` and others.)

28.1.6 Computing the power series

`__fp_sin_series_o:NNwww` Here we receive a conversion function `__fp_ep_to_float:wwN` or `__fp_ep_inv_to_float:wwN`, a *sign* (0 or 2), a (non-negative) *octant* delimited by a dot, a *fixed point* number delimited by a semicolon, and an extended-precision number. The auxiliary receives:

- the conversion function #1;
- the final sign, which depends on the octant #3 and the sign #2;
- the octant #3, which will control the series we use;
- the square #4 * #4 of the argument as a fixed point number, computed with `__fp_fixed_mul:wwn`;
- the number itself as an extended-precision number.

If the octant is in $\{1, 2, 5, 6, \dots\}$, we are near an extremum of the function and we use the series

$$\cos(x) = 1 - x^2 \left(\frac{1}{2!} - x^2 \left(\frac{1}{4!} - x^2 \left(\dots \right) \right) \right).$$

Otherwise, the series

$$\sin(x) = x \left(1 - x^2 \left(\frac{1}{3!} - x^2 \left(\frac{1}{5!} - x^2 \left(\dots \right) \right) \right) \right)$$

is used. Finally, the extended-precision number is converted to a floating point number with the given sign, and `__fp_sanitizew` checks for overflow and underflow.

```

15087 \cs_new:Npn \__fp_sin_series_o:NNwww #1#2#3. #4;
15088 {
15089   \__fp_fixed_mul:wwn #4; #4;
15090   {
15091     \exp_after:wN \__fp_sin_series_aux_o:NNwww
15092     \exp_after:wN #1
15093     \__int_value:w
15094     \if_int_odd:w \__int_eval:w (#3 + 2) / 4 \__int_eval_end:
15095       #2
15096     \else:
15097       \if_meaning:w #2 0 2 \else: 0 \fi:
15098       \fi:
15099     {#3}
15100   }
15101 }

```

```

15102 \cs_new:Npn \__fp_sin_series_aux_o:NNnwww #1#2#3 #4; #5,#6;
15103 {
15104   \if_int_odd:w \__int_eval:w #3 / 2 \__int_eval_end:
15105     \exp_after:wN \use_i:nn
15106   \else:
15107     \exp_after:wN \use_ii:nn
15108   \fi:
15109   { % 1/18!
15110     \__fp_fixed_mul_sub_back:wwwn {0000}{0000}{0000}{0001}{5619}{2070};
15111     #4;{0000}{0000}{0000}{0477}{9477}{3324};
15112     \__fp_fixed_mul_sub_back:wwwn #4;{0000}{0000}{0011}{4707}{4559}{7730};
15113     \__fp_fixed_mul_sub_back:wwwn #4;{0000}{0000}{2087}{6756}{9878}{6810};
15114     \__fp_fixed_mul_sub_back:wwwn #4;{0000}{0027}{5573}{1922}{3985}{8907};
15115     \__fp_fixed_mul_sub_back:wwwn #4;{0000}{2480}{1587}{3015}{8730}{1587};
15116     \__fp_fixed_mul_sub_back:wwwn #4;{0013}{8888}{8888}{8888}{8888}{8889};
15117     \__fp_fixed_mul_sub_back:wwwn #4;{0416}{6666}{6666}{6666}{6666}{6667};
15118     \__fp_fixed_mul_sub_back:wwwn #4;{5000}{0000}{0000}{0000}{0000}{0000};
15119     \__fp_fixed_mul_sub_back:wwwn#4;{10000}{0000}{0000}{0000}{0000}{0000};
15120     { \__fp_fixed_continue:wn 0, }
15121   }
15122   { % 1/17!
15123     \__fp_fixed_mul_sub_back:wwwn {0000}{0000}{0000}{0028}{1145}{7254};
15124     #4;{0000}{0000}{0000}{7647}{1637}{3182};
15125     \__fp_fixed_mul_sub_back:wwwn #4;{0000}{0000}{0160}{5904}{3836}{8216};
15126     \__fp_fixed_mul_sub_back:wwwn #4;{0000}{0002}{5052}{1083}{8544}{1719};
15127     \__fp_fixed_mul_sub_back:wwwn #4;{0000}{0275}{5731}{9223}{9858}{9065};
15128     \__fp_fixed_mul_sub_back:wwwn #4;{0001}{9841}{2698}{4126}{9841}{2698};
15129     \__fp_fixed_mul_sub_back:wwwn #4;{0083}{3333}{3333}{3333}{3333}{3333};
15130     \__fp_fixed_mul_sub_back:wwwn #4;{1666}{6666}{6666}{6666}{6666}{6667};
15131     \__fp_fixed_mul_sub_back:wwwn#4;{10000}{0000}{0000}{0000}{0000}{0000};
15132     { \__fp_ep_mul:wwwn 0, } #5,#6;
15133   }
15134   {
15135     \exp_after:wN \__fp_sanitize:Nw
15136     \exp_after:wN #2
15137     \__int_value:w \__int_eval:w #1
15138   }
15139   #2
15140 }

```

(End definition for __fp_sin_series_o:NNnwww and __fp_sin_series_aux_o:NNnwww.)

__fp_tan_series_o:NNnwww
 __fp_tan_series_aux_o:Nnwww

Contrarily to __fp_sin_series_o:NNnwww which received a conversion auxiliary as #1, here, #1 is 0 for tangent and 2 for cotangent. Consider first the case of the tangent. The octant #3 starts at 1, which means that it is 1 or 2 for $|x| \in [0, \pi/2]$, it is 3 or 4 for $|x| \in [\pi/2, \pi]$, and so on: the intervals on which $\tan|x| \geq 0$ coincide with those for which $\lfloor (\#3 + 1)/2 \rfloor$ is odd. We also have to take into account the original sign of x to get the sign of the final result; it is straightforward to check that the first __int_value:w expansion produces 0 for a positive final result, and 2 otherwise. A similar story holds for $\cot(x)$.

The auxiliary receives the sign, the octant, the square of the (reduced) input, and the (reduced) input (an extended-precision number) as arguments. It then computes the

numerator and denominator of

$$\tan(x) \simeq \frac{x(1 - x^2(a_1 - x^2(a_2 - x^2(a_3 - x^2(a_4 - x^2 a_5))))))}{1 - x^2(b_1 - x^2(b_2 - x^2(b_3 - x^2(b_4 - x^2 b_5)))}.$$

The ratio is computed by `__fp_ep_div:wwwn`, then converted to a floating point number. For octants #3 (really, quadrants) next to a pole of the functions, the fixed point numerator and denominator are exchanged before computing the ratio. Note that this `\if_int_odd:w` test relies on the fact that the octant is at least 1.

```

15141 \cs_new:Npn \__fp_tan_series_o:NNwww #1#2#3. #4;
15142 {
15143   \__fp_fixed_mul:wwn #4; #4;
15144   {
15145     \exp_after:wN \__fp_tan_series_aux_o:Nnwww
15146     \__int_value:w
15147     \if_int_odd:w \__int_eval:w #3 / 2 \__int_eval_end:
15148     \exp_after:wN \reverse_if:N
15149     \fi:
15150     \if_meaning:w #1#2 2 \else: 0 \fi:
15151     {#3}
15152   }
15153 }
15154 \cs_new:Npn \__fp_tan_series_aux_o:Nnwww #1 #2 #3; #4,#5;
15155 {
15156   \__fp_fixed_mul_sub_back:wwwn {0000}{0000}{1527}{3493}{0856}{7059};
15157   #3; {0000}{0159}{6080}{0274}{5257}{6472};
15158   \__fp_fixed_mul_sub_back:wwwn #3; {0002}{4571}{2320}{0157}{2558}{8481};
15159   \__fp_fixed_mul_sub_back:wwwn #3; {0115}{5830}{7533}{5397}{3168}{2147};
15160   \__fp_fixed_mul_sub_back:wwwn #3; {1929}{8245}{6140}{3508}{7719}{2982};
15161   \__fp_fixed_mul_sub_back:wwwn #3; {10000}{0000}{0000}{0000}{0000}{0000};
15162   { \__fp_ep_mul:wwwn 0, } #4,#5;
15163   {
15164     \__fp_fixed_mul_sub_back:wwwn {0000}{0007}{0258}{0681}{9408}{4706};
15165     #3; {0000}{2343}{7175}{1399}{6151}{7670};
15166     \__fp_fixed_mul_sub_back:wwwn #3; {0019}{2638}{4588}{9232}{8861}{3691};
15167     \__fp_fixed_mul_sub_back:wwwn #3; {0536}{6357}{0691}{4344}{6852}{4252};
15168     \__fp_fixed_mul_sub_back:wwwn #3; {5263}{1578}{9473}{6842}{1052}{6315};
15169     \__fp_fixed_mul_sub_back:wwwn #3; {10000}{0000}{0000}{0000}{0000}{0000};
15170     {
15171       \reverse_if:N \if_int_odd:w
15172       \__int_eval:w (#2 - 1) / 2 \__int_eval_end:
15173       \exp_after:wN \__fp_reverse_args:Nww
15174       \fi:
15175       \__fp_ep_div:wwwn 0,
15176     }
15177   }
15178   {
15179     \exp_after:wN \__fp_sanitizew
15180     \exp_after:wN #1
15181     \__int_value:w \__int_eval:w \__fp_ep_to_float:wwN
15182   }
15183   #1
15184 }

```

(End definition for `__fp_tan_series_o:NNwww` and `__fp_tan_series_aux_o:Nnwww`.)

28.2 Inverse trigonometric functions

All inverse trigonometric functions (arcsine, arccosine, arctangent, arccotangent, arcsecant, and arcsecant) are based on a function often denoted **atan2**. This function is accessed directly by feeding two arguments to arctangent, and is defined by $\text{atan}(y, x) = \text{atan}(y/x)$ for generic y and x . Its advantages over the conventional arctangent is that it takes values in $[-\pi, \pi]$ rather than $[-\pi/2, \pi/2]$, and that it is better behaved in boundary cases. Other inverse trigonometric functions are expressed in terms of **atan** as

$$\text{acos } x = \text{atan}(\sqrt{1-x^2}, x) \quad (5)$$

$$\text{asin } x = \text{atan}(x, \sqrt{1-x^2}) \quad (6)$$

$$\text{asec } x = \text{atan}(\sqrt{x^2-1}, 1) \quad (7)$$

$$\text{acsc } x = \text{atan}(1, \sqrt{x^2-1}) \quad (8)$$

$$\text{atan } x = \text{atan}(x, 1) \quad (9)$$

$$\text{acot } x = \text{atan}(1, x). \quad (10)$$

Rather than introducing a new function, **atan2**, the arctangent function **atan** is overloaded: it can take one or two arguments. In the comments below, following many texts, we call the first argument y and the second x , because $\text{atan}(y, x) = \text{atan}(y/x)$ is the angular coordinate of the point (x, y) .

As for direct trigonometric functions, the first step in computing $\text{atan}(y, x)$ is argument reduction. The sign of y will give that of the result. We distinguish eight regions where the point $(x, |y|)$ can lie, of angular size roughly $\pi/8$, characterized by their “octant”, between 0 and 7 included. In each region, we compute an arctangent as a Taylor series, then shift this arctangent by the appropriate multiple of $\pi/4$ and sign to get the result. Here is a list of octants, and how we compute the arctangent (we assume $y > 0$: otherwise replace y by $-y$ below):

0 $0 < |y| < 0.41421x$, then $\text{atan } \frac{|y|}{x}$ is given by a nicely convergent Taylor series;

1 $0 < 0.41421x < |y| < x$, then $\text{atan } \frac{|y|}{x} = \frac{\pi}{4} - \text{atan } \frac{x-|y|}{x+|y|}$;

2 $0 < 0.41421|y| < x < |y|$, then $\text{atan } \frac{|y|}{x} = \frac{\pi}{4} + \text{atan } \frac{-x+|y|}{x+|y|}$;

3 $0 < x < 0.41421|y|$, then $\text{atan } \frac{|y|}{x} = \frac{\pi}{2} - \text{atan } \frac{x}{|y|}$;

4 $0 < -x < 0.41421|y|$, then $\text{atan } \frac{|y|}{x} = \frac{\pi}{2} + \text{atan } \frac{-x}{|y|}$;

5 $0 < 0.41421|y| < -x < |y|$, then $\text{atan } \frac{|y|}{x} = \frac{3\pi}{4} - \text{atan } \frac{x+|y|}{-x+|y|}$;

6 $0 < -0.41421x < |y| < -x$, then $\text{atan } \frac{|y|}{x} = \frac{3\pi}{4} + \text{atan } \frac{-x-|y|}{-x+|y|}$;

7 $0 < |y| < -0.41421x$, then $\text{atan } \frac{|y|}{x} = \pi - \text{atan } \frac{|y|}{-x}$.

In the following, we will denote by z the ratio among $|\frac{y}{x}|$, $|\frac{x}{y}|$, $|\frac{x+y}{x-y}|$, $|\frac{x-y}{x+y}|$ which appears in the right-hand side above.

28.2.1 Arctangent and arccotangent

The parsing step manipulates `atan` and `acot` like `min` and `max`, reading in an array of operands, but also leaves `\use_i:nn` or `\use_ii:nn` depending on whether the result should be given in radians or in degrees. Here, we dispatch according to the number of arguments. The one-argument versions of arctangent and arccotangent are special cases of the two-argument ones: $\text{atan}(y) = \text{atan}(y, 1) = \text{acot}(1, y)$ and $\text{acot}(x) = \text{atan}(1, x) = \text{acot}(x, 1)$.

```

15185 \cs_new:Npn \__fp_atan_o:Nw
15186 {
15187   \__fp_atan_dispatch_o:NNnNw
15188   \__fp_acotii_o:Nww \__fp_atanii_o:Nww { atan }
15189 }
15190 \cs_new:Npn \__fp_acot_o:Nw
15191 {
15192   \__fp_atan_dispatch_o:NNnNw
15193   \__fp_atanii_o:Nww \__fp_acotii_o:Nww { acot }
15194 }
15195 \cs_new:Npn \__fp_atan_dispatch_o:NNnNw #1#2#3#4#5@
15196 {
15197   \if_case:w
15198     \__int_eval:w \__fp_array_count:n {#5} - 1 \__int_eval_end:
15199     \exp_after:wN #1 \exp_after:wN #4 \c_one_fp #5
15200     \exp:w
15201   \or: #2 #4 #5 \exp:w
15202   \else:
15203     \__msg_kernel_expandable_error:nnnnn
15204     { kernel } { fp-num-args } { #3() } { 1 } { 2 }
15205     \exp_after:wN \c_nan_fp \exp:w
15206   \fi:
15207   \exp_after:wN \exp_end:
15208 }

```

(End definition for `__fp_atan_o:Nw`, `__fp_acot_o:Nw`, and `__fp_atan_dispatch_o:NNnNw`.)

`__fp_atanii_o:Nww` If either operand is `nan`, we return it. If both are normal, we call `__fp_atan_normal_o:NNnwNnw`. If both are zero or both infinity, we call `__fp_atan_inf_o:NNNw` with argument 2, leading to a result among $\{\pm\pi/4, \pm3\pi/4\}$ (in degrees, $\{\pm45, \pm135\}$). Otherwise, one is much bigger than the other, and we call `__fp_atan_inf_o:NNNw` with either an argument of 4, leading to the values $\pm\pi/2$ (in degrees, ±90), or 0, leading to $\{\pm0, \pm\pi\}$ (in degrees, $\{\pm0, \pm180\}$). Since $\text{acot}(x, y) = \text{atan}(y, x)$, `__fp_acotii_o:ww` simply reverses its two arguments.

```

15209 \cs_new:Npn \__fp_atanii_o:Nww
15210   #1 \s__fp \__fp_chk:w #2#3#4; \s__fp \__fp_chk:w #5
15211 {
15212   \if_meaning:w 3 #2 \__fp_case_return_i_o:ww \fi:
15213   \if_meaning:w 3 #5 \__fp_case_return_ii_o:ww \fi:
15214   \if_case:w
15215     \if_meaning:w #2 #5
15216     \if_meaning:w 1 #2 10 \else: 0 \fi:
15217   \else:
15218     \if_int_compare:w #2 > #5 \exp_stop_f: 1 \else: 2 \fi:
15219   \fi:

```

```

15220     \exp_stop_f:
15221     \__fp_case_return:nw { \__fp_atan_inf_o:NNNw #1 #3 2 }
15222 \or: \__fp_case_return:nw { \__fp_atan_inf_o:NNNw #1 #3 4 }
15223 \or: \__fp_case_return:nw { \__fp_atan_inf_o:NNNw #1 #3 0 }
15224 \fi:
15225 \__fp_atan_normal_o:NNnwNnw #1
15226 \s__fp \__fp_chk:w #2#3#4;
15227 \s__fp \__fp_chk:w #5
15228 }
15229 \cs_new:Npn \__fp_acotii_o:Nww #1#2; #3;
15230 { \__fp_atanii_o:Nww #1#3; #2; }

```

(End definition for __fp_atanii_o:Nww and __fp_acotii_o:Nww.)

__fp_atan_inf_o:NNNw This auxiliary is called whenever one number is ± 0 or $\pm\infty$ (and neither is NaN). Then the result only depends on the signs, and its value is a multiple of $\pi/4$. We use the same auxiliary as for normal numbers, __fp_atan_combine_o:NwwwwwN, with arguments the final sign #2; the octant #3; $\text{atan } z/z = 1$ as a fixed point number; $z = 0$ as a fixed point number; and $z = 0$ as an extended-precision number. Given the values we provide, $\text{atan } z$ will be computed to be 0, and the result will be $[\#3/2] \cdot \pi/4$ if the sign #5 of x is positive, and $[(7 - \#3)/2] \cdot \pi/4$ for negative x , where the divisions are rounded up.

```

15231 \cs_new:Npn \__fp_atan_inf_o:NNNw #1#2#3 \s__fp \__fp_chk:w #4#5#6;
15232 {
15233     \exp_after:wN \__fp_atan_combine_o:NwwwwwN
15234     \exp_after:wN #2
15235     \__int_value:w \__int_eval:w
15236     \if_meaning:w 2 #5 7 - \fi: #3 \exp_after:wN ;
15237     \c__fp_one_fixed_tl ;
15238     {0000}{0000}{0000}{0000}{0000}{0000};
15239     0,{0000}{0000}{0000}{0000}{0000}{0000}; #1
15240 }

```

(End definition for __fp_atan_inf_o:NNNw.)

__fp_atan_normal_o:NNnwNnw Here we simply reorder the floating point data into a pair of signed extended-precision numbers, that is, a sign, an exponent ending with a comma, and a six-block mantissa ending with a semi-colon. This extended precision is required by other inverse trigonometric functions, to compute things like $\text{atan}(x, \sqrt{1 - x^2})$ without intermediate rounding errors.

```

15241 \cs_new_protected:Npn \__fp_atan_normal_o:NNnwNnw
15242     #1 \s__fp \__fp_chk:w 1#2#3#4; \s__fp \__fp_chk:w 1#5#6#7;
15243 {
15244     \__fp_atan_test_o:NwwNwwN
15245     #2 #3, #4{0000}{0000};
15246     #5 #6, #7{0000}{0000}; #1
15247 }

```

(End definition for __fp_atan_normal_o:NNnwNnw.)

__fp_atan_test_o:NwwNwwN This receives: the sign #1 of y , its exponent #2, its 24 digits #3 in groups of 4, and similarly for x . We prepare to call __fp_atan_combine_o:NwwwwwN which expects the sign #1, the octant, the ratio $(\text{atan } z)/z = 1 - \dots$, and the value of z , both as a fixed point number and as an extended-precision floating point number with a mantissa in $[0.01, 1)$. For now, we place #1 as a first argument, and start an integer expression for

the octant. The sign of x does not affect what z will be, so we simply leave a contribution to the octant: $\langle \text{octant} \rangle \rightarrow 7 - \langle \text{octant} \rangle$ for negative x . Then we order $|y|$ and $|x|$ in a non-decreasing order: if $|y| > |x|$, insert 3– in the expression for the octant, and swap the two numbers. The finer test with 0.41421 is done by `__fp_atan_div:wnwnnw` after the operands have been ordered.

```

15248 \cs_new:Npn \__fp_atan_test_o:NwwNwwN #1#2,#3; #4#5,#6;
15249 {
15250   \exp_after:wN \__fp_atan_combine_o:NwwwwwN
15251   \exp_after:wN #1
15252   \__int_value:w \__int_eval:w
15253   \if_meaning:w 2 #4
15254     7 - \__int_eval:w
15255   \fi:
15256   \if_int_compare:w
15257     \__fp_ep_compare:www #2,#3; #5,#6; > 0 \exp_stop_f:
15258     3 -
15259   \exp_after:wN \__fp_reverse_args:Nww
15260   \fi:
15261   \__fp_atan_div:wnwnnw #2,#3; #5,#6;
15262 }

```

(End definition for `__fp_atan_test_o:NwwNwwN`.)

```

\__fp_atan_div:wnwnnw
\__fp_atan_near:wwwn
\__fp_atan_near_aux:wwn

```

This receives two positive numbers a and b (equal to $|x|$ and $|y|$ in some order), each as an exponent and 6 blocks of 4 digits, such that $0 < a < b$. If $0.41421b < a$, the two numbers are “near”, hence the point (y, x) that we started with is closer to the diagonals $\{|y| = |x|\}$ than to the axes $\{xy = 0\}$. In that case, the octant is 1 (possibly combined with the 7– and 3– inserted earlier) and we wish to compute $\text{atan} \frac{b-a}{a+b}$. Otherwise, the octant is 0 (again, combined with earlier terms) and we wish to compute $\text{atan} \frac{a}{b}$. In any case, call `__fp_atan_auxi:ww` followed by z , as a comma-delimited exponent and a fixed point number.

```

15263 \cs_new:Npn \__fp_atan_div:wnwnnw #1,#2#3; #4,#5#6;
15264 {
15265   \if_int_compare:w
15266     \__int_eval:w 41421 * #5 < #2 000
15267     \if_case:w \__int_eval:w #4 - #1 \__int_eval_end: 00 \or: 0 \fi:
15268     \exp_stop_f:
15269     \exp_after:wN \__fp_atan_near:wwwn
15270   \fi:
15271   0
15272   \__fp_ep_div:wwwn #1,{#2}#3; #4,{#5}#6;
15273   \__fp_atan_auxi:ww
15274 }
15275 \cs_new:Npn \__fp_atan_near:wwwn
15276   0 \__fp_ep_div:wwwn #1,#2; #3,
15277   {
15278     1
15279     \__fp_ep_to_fixed:wwn #1 - #3, #2;
15280     \__fp_atan_near_aux:wwn
15281   }
15282 \cs_new:Npn \__fp_atan_near_aux:wwn #1; #2;
15283 {
15284   \__fp_fixed_add:wwn #1; #2;

```

```

15285     { \_fp_fixed_sub:wwn #2; #1; { \_fp_ep_div:wwwn 0, } 0, }
15286   }

```

(End definition for _fp_atan_div:wwwn, _fp_atan_near:wwn, and _fp_atan_near_aux:wwn.)

_fp_atan_auxi:ww Convert z from a representation as an exponent and a fixed point number in $[0.01, 1)$ to a fixed point number only, then set up the call to _fp_atan_Taylor_loop:www, followed by the fixed point representation of z and the old representation.

_fp_atan_auxii:w

```

15287 \cs_new:Npn \_fp_atan_auxi:ww #1,#2;
15288   { \_fp_ep_to_fixed:wwn #1,#2; \_fp_atan_auxii:w #1,#2; }
15289 \cs_new:Npn \_fp_atan_auxii:w #1;
15290   {
15291     \_fp_fixed_mul:wwn #1; #1;
15292     {
15293       \_fp_atan_Taylor_loop:www 39 ;
15294       {0000}{0000}{0000}{0000}{0000}{0000} ;
15295     }
15296     ! #1;
15297   }

```

(End definition for _fp_atan_auxi:ww and _fp_atan_auxii:w.)

_fp_atan_Taylor_loop:www
_fp_atan_Taylor_break:w

We compute the series of $(\operatorname{atan} z)/z$. A typical intermediate stage has $\#1 = 2k - 1$, $\#2 = \frac{1}{2k+1} - z^2(\frac{1}{2k+3} - z^2(\dots - z^2\frac{1}{39}))$, and $\#3 = z^2$. To go to the next step $k \rightarrow k - 1$, we compute $\frac{1}{2k-1}$, then subtract from it z^2 times $\#2$. The loop stops when $k = 0$: then $\#2$ is $(\operatorname{atan} z)/z$, and there is a need to clean up all the unnecessary data, end the integer expression computing the octant with a semicolon, and leave the result $\#2$ afterwards.

```

15298 \cs_new:Npn \_fp_atan_Taylor_loop:www #1; #2; #3;
15299   {
15300     \if_int_compare:w #1 = -1 \exp_stop_f:
15301     \_fp_atan_Taylor_break:w
15302     \fi:
15303     \exp_after:wN \_fp_fixed_div_int:wwN \c_fp_one_fixed_tl ; #1;
15304     \_fp_rrrot:www \_fp_fixed_mul_sub_back:wwwn #2; #3;
15305     {
15306       \exp_after:wN \_fp_atan_Taylor_loop:www
15307       \_int_value:w \_int_eval:w #1 - 2 ;
15308     }
15309     #3;
15310   }
15311 \cs_new:Npn \_fp_atan_Taylor_break:w
15312   \fi: #1 \_fp_fixed_mul_sub_back:wwwn #2; #3 !
15313   { \fi: ; #2 ; }

```

(End definition for _fp_atan_Taylor_loop:www and _fp_atan_Taylor_break:w.)

_fp_atan_combine_o:NwwwwN
_fp_atan_combine_aux:ww

This receives a $\langle sign \rangle$, an $\langle octant \rangle$, a fixed point value of $(\operatorname{atan} z)/z$, a fixed point number z , and another representation of z , as an $\langle exponent \rangle$ and the fixed point number $10^{-\langle exponent \rangle} z$, followed by either $\backslash\text{use_i:nn}$ (when working in radians) or $\backslash\text{use_ii:nn}$ (when working in degrees). The function computes the floating point result

$$\langle sign \rangle \left(\left\lceil \frac{\langle octant \rangle}{2} \right\rceil \frac{\pi}{4} + (-1)^{\langle octant \rangle} \frac{\operatorname{atan} z}{z} \cdot z \right), \quad (11)$$

multiplied by $180/\pi$ if working in degrees, and using in any case the most appropriate representation of z . The floating point result is passed to `__fp_sanitize:Nw`, which checks for overflow or underflow. If the octant is 0, leave the exponent #5 for `__fp_sanitize:Nw`, and multiply $\#3 = \frac{\operatorname{atan} z}{z}$ with #6, the adjusted z . Otherwise, multiply $\#3 = \frac{\operatorname{atan} z}{z}$ with $\#4 = z$, then compute the appropriate multiple of $\frac{\pi}{4}$ and add or subtract the product $\#3 \cdot \#4$. In both cases, convert to a floating point with `__fp_fixed_to_float:wN`.

```

15314 \cs_new:Npn \__fp_atan_combine_o:NwwwwN #1 #2; #3; #4; #5,#6; #7
15315 {
15316   \exp_after:wN \__fp_sanitize:Nw
15317   \exp_after:wN #1
15318   \__int_value:w \__int_eval:w
15319   \if_meaning:w 0 #2
15320     \exp_after:wN \use_i:nn
15321   \else:
15322     \exp_after:wN \use_ii:nn
15323   \fi:
15324   { #5 \__fp_fixed_mul:wwn #3; #6; }
15325   {
15326     \__fp_fixed_mul:wwn #3; #4;
15327     {
15328       \exp_after:wN \__fp_atan_combine_aux:ww
15329       \__int_value:w \__int_eval:w #2 / 2 ; #2;
15330     }
15331   }
15332   { #7 \__fp_fixed_to_float:wN \__fp_fixed_to_float_rad:wN }
15333   #1
15334 }
15335 \cs_new:Npn \__fp_atan_combine_aux:ww #1; #2;
15336 {
15337   \__fp_fixed_mul_short:wwn
15338   {7853}{9816}{3397}{4483}{0961}{5661};
15339   {#1}{0000}{0000};
15340   {
15341     \if_int_odd:w #2 \exp_stop_f:
15342     \exp_after:wN \__fp_fixed_sub:wwn
15343   \else:
15344     \exp_after:wN \__fp_fixed_add:wwn
15345   \fi:
15346 }
15347 }

```

(End definition for `__fp_atan_combine_o:NwwwwN` and `__fp_atan_combine_aux:ww`.)

28.2.2 Arcsine and arccosine

`__fp_asin_o:w` Again, the first argument provided by `l3fp-parse` is `\use_i:nn` if we are to work in radians and `\use_ii:nn` for degrees. Then comes a floating point number. The arcsine of ± 0 or NaN is the same floating point number. The arcsine of $\pm\infty$ raises an invalid operation exception. Otherwise, call an auxiliary common with `__fp_acos_o:w`, feeding it information about what function is being performed (for “invalid operation” exceptions).

```

15348 \cs_new:Npn \__fp_asin_o:w #1 \s__fp \__fp_chk:w #2#3; @
15349 {

```

```

15350 \if_case:w #2 \exp_stop_f:
15351 \__fp_case_return_same_o:w
15352 \or:
15353 \__fp_case_use:nw
15354 { \__fp_asin_normal_o:NfwNnnnnw #1 { #1 { asin } { asind } } }
15355 \or:
15356 \__fp_case_use:nw
15357 { \__fp_invalid_operation_o:fw { #1 { asin } { asind } } }
15358 \else:
15359 \__fp_case_return_same_o:w
15360 \fi:
15361 \s__fp \__fp_chk:w #2 #3;
15362 }

```

(End definition for __fp_asin_o:w.)

__fp_acos_o:w The arccosine of ± 0 is $\pi/2$ (in degrees, 90). The arccosine of $\pm\infty$ raises an invalid operation exception. The arccosine of NaN is itself. Otherwise, call an auxiliary common with __fp_sin_o:w, informing it that it was called by acos or acosd, and preparing to swap some arguments down the line.

```

15363 \cs_new:Npn \__fp_acos_o:w #1 \s__fp \__fp_chk:w #2#3; @
15364 {
15365 \if_case:w #2 \exp_stop_f:
15366 \__fp_case_use:nw { \__fp_atan_inf_o:NNNw #1 0 4 }
15367 \or:
15368 \__fp_case_use:nw
15369 {
15370 \__fp_asin_normal_o:NfwNnnnnw #1 { #1 { acos } { acosd } }
15371 \__fp_reverse_args:Nww
15372 }
15373 \or:
15374 \__fp_case_use:nw
15375 { \__fp_invalid_operation_o:fw { #1 { acos } { acosd } } }
15376 \else:
15377 \__fp_case_return_same_o:w
15378 \fi:
15379 \s__fp \__fp_chk:w #2 #3;
15380 }

```

(End definition for __fp_acos_o:w.)

__fp_asin_normal_o:NfwNnnnnw If the exponent #5 is strictly less than 1, the operand lies within $(-1, 1)$ and the operation is permitted: call __fp_asin_auxi_o:nNww with the appropriate arguments. If the number is exactly ± 1 (the test works because we know that $\#5 \geq 1$, $\#6\#7 \geq 10000000$, $\#8\#9 \geq 0$, with equality only for ± 1), we also call __fp_asin_auxi_o:nNww. Otherwise, __fp_use_i:ww gets rid of the asin auxiliary, and raises instead an invalid operation, because the operand is outside the domain of arcsine or arccosine.

```

15381 \cs_new:Npn \__fp_asin_normal_o:NfwNnnnnw
15382 #1#2#3 \s__fp \__fp_chk:w 1#4#5#6#7#8#9;
15383 {
15384 \if_int_compare:w #5 < 1 \exp_stop_f:
15385 \exp_after:wN \__fp_use_none_until_s:w
15386 \fi:
15387 \if_int_compare:w \__int_eval:w #5 + #6#7 + #8#9 = 1000 0001 ~

```

```

15388     \exp_after:wN \__fp_use_none_until_s:w
15389     \fi:
15390     \__fp_use_i:ww
15391     \__fp_invalid_operation_o:fw {#2}
15392     \s__fp \__fp_chk:w 1#4{#5}{#6}{#7}{#8}{#9};
15393     \__fp_asin_auxi_o:NnNww
15394     #1 {#3} #4 #5,{#6}{#7}{#8}{#9}{0000}{0000};
15395 }

```

(End definition for __fp_asin_normal_o:NfwNnnnnw.)

__fp_asin_auxi_o:NnNww
 __fp_asin_isqrt:wn

We compute $x/\sqrt{1-x^2}$. This function is used by `asin` and `acos`, but also by `acsc` and `asec` after inverting the operand, thus it must manipulate extended-precision numbers. First evaluate $1-x^2$ as $(1+x)(1-x)$: this behaves better near $x=1$. We do the addition/subtraction with fixed point numbers (they are not implemented for extended-precision floats), but go back to extended-precision floats to multiply and compute the inverse square root $1/\sqrt{1-x^2}$. Finally, multiply by the (positive) extended-precision float $|x|$, and feed the (signed) result, and the number $+1$, as arguments to the arctangent function. When computing the arccosine, the arguments $x/\sqrt{1-x^2}$ and $+1$ are swapped by #2 (__fp_reverse_args:Nww in that case) before __fp_atan_test_o:NwwNwwN is evaluated. Note that the arctangent function requires normalized arguments, hence the need for `ep_to_ep` and `continue` after `ep_mul`.

```

15396 \cs_new:Npn \__fp_asin_auxi_o:NnNww #1#2#3#4,#5;
15397 {
15398     \__fp_ep_to_fixed:wwn #4,#5;
15399     \__fp_asin_isqrt:wn
15400     \__fp_ep_mul:wwwwn #4,#5;
15401     \__fp_ep_to_ep:wwN
15402     \__fp_fixed_continue:wn
15403     { #2 \__fp_atan_test_o:NwwNwwN #3 }
15404     0 1,{1000}{0000}{0000}{0000}{0000}{0000}; #1
15405 }
15406 \cs_new:Npn \__fp_asin_isqrt:wn #1;
15407 {
15408     \exp_after:wN \__fp_fixed_sub:wwn \c__fp_one_fixed_tl ; #1;
15409     {
15410         \__fp_fixed_add_one:wn #1;
15411         \__fp_fixed_continue:wn { \__fp_ep_mul:wwwwn 0, } 0,
15412     }
15413     \__fp_ep_isqrt:wwn
15414 }

```

(End definition for __fp_asin_auxi_o:NnNww and __fp_asin_isqrt:wn.)

28.2.3 Arccosecant and arcsecant

__fp_acsc_o:w Cases are mostly labelled by #2, except when #2 is 2: then we use #3#2, which is 02 = 2 when the number is $+\infty$ and 22 when the number is $-\infty$. The arccosecant of ± 0 raises an invalid operation exception. The arccosecant of $\pm\infty$ is ± 0 with the same sign. The arcosecant of NaN is itself. Otherwise, __fp_acsc_normal_o:NfwNnw does some more tests, keeping the function name (`acsc` or `acscd`) as an argument for invalid operation exceptions.

```

15415 \cs_new:Npn \__fp_acsc_o:w #1 \s__fp \__fp_chk:w #2#3#4; @

```

```

15416 {
15417     \if_case:w \if_meaning:w 2 #2 #3 \fi: #2 \exp_stop_f:
15418         \__fp_case_use:nw
15419         { \__fp_invalid_operation_o:fw { #1 { acsc } { acscd } } }
15420     \or: \__fp_case_use:nw
15421         { \__fp_acsc_normal_o:NfwNnw #1 { #1 { acsc } { acscd } } }
15422     \or: \__fp_case_return_o:Nw \c_zero_fp
15423     \or: \__fp_case_return_same_o:w
15424     \else: \__fp_case_return_o:Nw \c_minus_zero_fp
15425     \fi:
15426     \s__fp \__fp_chk:w #2 #3 #4;
15427 }

```

(End definition for __fp_acsc_o:w.)

__fp_asec_o:w The arcsecant of ± 0 raises an invalid operation exception. The arcsecant of $\pm\infty$ is $\pi/2$ (in degrees, 90). The arcosecant of NaN is itself. Otherwise, do some more tests, keeping the function name asec (or asecd) as an argument for invalid operation exceptions, and a __fp_reverse_args:Nww following precisely that appearing in __fp_acos_o:w.

```

15428 \cs_new:Npn \__fp_asec_o:w #1 \s__fp \__fp_chk:w #2#3; @
15429 {
15430     \if_case:w #2 \exp_stop_f:
15431         \__fp_case_use:nw
15432         { \__fp_invalid_operation_o:fw { #1 { asec } { asecd } } }
15433     \or:
15434         \__fp_case_use:nw
15435         {
15436             \__fp_acsc_normal_o:NfwNnw #1 { #1 { asec } { asecd } }
15437             \__fp_reverse_args:Nww
15438         }
15439     \or: \__fp_case_use:nw { \__fp_atan_inf_o:NNNw #1 0 4 }
15440     \else: \__fp_case_return_same_o:w
15441     \fi:
15442     \s__fp \__fp_chk:w #2 #3;
15443 }

```

(End definition for __fp_asec_o:w.)

__fp_acsc_normal_o:NfwNnw If the exponent is non-positive, the operand is less than 1 in absolute value, which is always an invalid operation: complain. Otherwise, compute the inverse of the operand, and feed it to __fp_asin_auxi_o:nNww (with all the appropriate arguments). This computes what we want thanks to $\text{acsc}(x) = \text{asin}(1/x)$ and $\text{asec}(x) = \text{acos}(1/x)$.

```

15444 \cs_new:Npn \__fp_acsc_normal_o:NfwNnw #1#2#3 \s__fp \__fp_chk:w 1#4#5#6;
15445 {
15446     \int_compare:nNtTF {#5} < 1
15447     {
15448         \__fp_invalid_operation_o:fw {#2}
15449         \s__fp \__fp_chk:w 1#4{#5}#6;
15450     }
15451     {
15452         \__fp_ep_div:wwwwn
15453         1,{1000}{0000}{0000}{0000}{0000};
15454         #5,#6{0000}{0000};
15455         { \__fp_asin_auxi_o:nNww #1 {#3} #4 }

```

```

15456     }
15457 }

(End definition for \_fp_acsc_normal_o:NfwNnw.)

15458 </initex | package>

```

29 13fp-convert implementation

```

15459 (*initex | package)
15460 <@@=fp>

```

29.1 Trimming trailing zeros

`_fp_trim_zeros:w` If #1 ends with a 0, the loop auxiliary takes that zero as an end-delimiter for its first argument, and the second argument is the same loop auxiliary. Once the last trailing zero is reached, the second argument will be the dot auxiliary, which removes a trailing dot if any. We then clean-up with the `end` auxiliary, keeping only the number.

```

15461 \cs_new:Npn \_fp_trim_zeros:w #1 ;
15462 {
15463   \_fp_trim_zeros_loop:w #1
15464   ; \_fp_trim_zeros_loop:w 0; \_fp_trim_zeros_dot:w .; \s_stop
15465 }
15466 \cs_new:Npn \_fp_trim_zeros_loop:w #1 0; #2 { #2 #1 ; #2 }
15467 \cs_new:Npn \_fp_trim_zeros_dot:w #1 .; { \_fp_trim_zeros_end:w #1 ; }
15468 \cs_new:Npn \_fp_trim_zeros_end:w #1 ; #2 \s_stop { #1 }

```

(End definition for `_fp_trim_zeros:w` and others.)

29.2 Scientific notation

`\fp_to_scientific:N` The three public functions evaluate their argument, then pass it to `_fp_to_scientific_dispatch:w`.

```

\fp_to_scientific:c
\fp_to_scientific:n
15469 \cs_new:Npn \fp_to_scientific:N #1
15470 { \exp_after:wN \_fp_to_scientific_dispatch:w #1 }
15471 \cs_generate_variant:Nn \fp_to_scientific:N { c }
15472 \cs_new:Npn \fp_to_scientific:n
15473 {
15474   \exp_after:wN \_fp_to_scientific_dispatch:w
15475   \exp:w \exp_end_continue_f:w \_fp_parse:n
15476 }

```

(End definition for `\fp_to_scientific:N` and `\fp_to_scientific:n`. These functions are documented on page 175.)

`_fp_to_scientific_dispatch:w` Expressing an internal floating point number in scientific notation is quite easy: no rounding, and the format is very well defined. First cater for the sign: negative numbers (`#2 = 2`) start with `-`; we then only need to care about positive numbers and `nan`. Then filter the special cases: ± 0 are represented as 0; infinities are converted to a number slightly larger than the largest after an “invalid operation” exception; `nan` is represented as 0 after an “invalid operation” exception. In the normal case, decrement the exponent and unbrace the 4 brace groups, then in a second step grab the first digit (previously hidden in braces) to order the various parts correctly.

```

15477 \cs_new:Npn \__fp_to_scientific_dispatch:w \s__fp \__fp_chk:w #1#2
15478 {
15479   \if_meaning:w 2 #2 \exp_after:wN - \exp:w \exp_end_continue_f:w \fi:
15480   \if_case:w #1 \exp_stop_f:
15481     \__fp_case_return:nw { 0.000000000000000e0 }
15482   \or: \exp_after:wN \__fp_to_scientific_normal:wnnnnn
15483   \or:
15484     \__fp_case_use:nw
15485     {
15486       \exp_args:Nf \__fp_invalid_operation:nnw
15487       {
15488         \__fp_expand:n
15489         { { 1.000000000000000e } \int_use:N \c__fp_max_exponent_int }
15490       }
15491       { fp_to_scientific }
15492     }
15493   \or:
15494     \__fp_case_use:nw
15495     {
15496       \__fp_invalid_operation:nnw
15497       { 0.000000000000000e0 }
15498       { fp_to_scientific }
15499     }
15500   \fi:
15501   \s__fp \__fp_chk:w #1 #2
15502 }
15503 \cs_new:Npn \__fp_to_scientific_normal:wnnnnn
15504 \s__fp \__fp_chk:w 1 #1 #2 #3#4#5#6 ;
15505 {
15506   \exp_after:wN \__fp_to_scientific_normal:wNw
15507   \exp_after:wN e
15508   \__int_value:w \__int_eval:w #2 - 1
15509   ; #3 #4 #5 #6 ;
15510 }
15511 \cs_new:Npn \__fp_to_scientific_normal:wNw #1 ; #2#3;
15512 { #2.#3 #1 }

```

(End definition for `__fp_to_scientific_dispatch:w`, `__fp_to_scientific_normal:wnnnnn`, and `__fp_to_scientific_normal:wNw`.)

29.3 Decimal representation

`\fp_to_decimal:N` All three public variants are based on the same `__fp_to_decimal_dispatch:w` after evaluating their argument to an internal floating point.

```

\fp_to_decimal:c
\fp_to_decimal:n
15513 \cs_new:Npn \fp_to_decimal:N #1
15514 { \exp_after:wN \__fp_to_decimal_dispatch:w #1 }
15515 \cs_generate_variant:Nn \fp_to_decimal:N { c }
15516 \cs_new:Npn \fp_to_decimal:n
15517 {
15518   \exp_after:wN \__fp_to_decimal_dispatch:w
15519   \exp:w \exp_end_continue_f:w \__fp_parse:n
15520 }

```

(End definition for `\fp_to_decimal:N` and `\fp_to_decimal:n`. These functions are documented on page 174.)

```

\__fp_to_decimal_dispatch:w
    \__fp_to_decimal_normal:wnnnnn
\__fp_to_decimal_large:Nnnw
\__fp_to_decimal_huge:wnnnn

```

The structure is similar to `__fp_to_scientific_dispatch:w`. Insert `-` for negative numbers. Zero gives 0, $\pm\infty$ and NaN yield an “invalid operation” exception; note that $\pm\infty$ produces a very large output, which we don’t expand now since it most likely won’t be needed. Normal numbers with an exponent in the range [1,15] have that number of digits before the decimal separator: “decimate” them, and remove leading zeros with `__int_value:w`, then trim trailing zeros and dot. Normal numbers with an exponent 16 or larger have no decimal separator, we only need to add trailing zeros. When the exponent is non-positive, the result should be 0.<zeros><digits>, trimmed.

```

15521 \cs_new:Npn \__fp_to_decimal_dispatch:w \s__fp \__fp_chk:w #1#2
15522 {
15523     \if_meaning:w 2 #2 \exp_after:wN - \exp:w \exp_end_continue_f:w \fi:
15524     \if_case:w #1 \exp_stop_f:
15525         \__fp_case_return:nw { 0 }
15526     \or: \exp_after:wN \__fp_to_decimal_normal:wnnnnn
15527     \or:
15528         \__fp_case_use:nw
15529         {
15530             \__fp_invalid_operation:nnw
15531             {
15532                 \exp_after:wN \exp_after:wN \exp_after:wN 1
15533                 \prg_replicate:nn \c__fp_max_exponent_int 0
15534             }
15535             { fp_to_decimal }
15536         }
15537     \or:
15538         \__fp_case_use:nw
15539         {
15540             \__fp_invalid_operation:nnw
15541             { 0 }
15542             { fp_to_decimal }
15543         }
15544     \fi:
15545     \s__fp \__fp_chk:w #1 #2
15546 }
15547 \cs_new:Npn \__fp_to_decimal_normal:wnnnnn
15548 \s__fp \__fp_chk:w 1 #1 #2 #3#4#5#6 ;
15549 {
15550     \int_compare:nNnTF {#2} > 0
15551     {
15552         \int_compare:nNnTF {#2} < \c__fp_prec_int
15553         {
15554             \__fp_decimate:nNnnnn { \c__fp_prec_int - #2 }
15555             \__fp_to_decimal_large:Nnnw
15556         }
15557         {
15558             \exp_after:wN \exp_after:wN
15559             \exp_after:wN \__fp_to_decimal_huge:wnnnn
15560             \prg_replicate:nn { #2 - \c__fp_prec_int } { 0 } ;
15561         }
15562         {#3} {#4} {#5} {#6}
15563     }
15564     {
15565         \exp_after:wN \__fp_trim_zeros:w

```

```

15566         \exp_after:wN 0
15567         \exp_after:wN .
15568         \exp:w \exp_end_continue_f:w \prg_replicate:nn { - #2 } { 0 }
15569         #3#4#5#6 ;
15570     }
15571 }
15572 \cs_new:Npn \__fp_to_decimal_large:Nnnw #1#2#3#4;
15573 {
15574     \exp_after:wN \__fp_trim_zeros:w \__int_value:w
15575     \if_int_compare:w #2 > 0 \exp_stop_f:
15576     #2
15577     \fi:
15578     \exp_stop_f:
15579     #3.#4 ;
15580 }
15581 \cs_new:Npn \__fp_to_decimal_huge:wnnnn #1; #2#3#4#5 { #2#3#4#5 #1 }

```

(End definition for __fp_to_decimal_dispatch:w and others.)

29.4 Token list representation

\fp_to_tl:N These three public functions evaluate their argument, then pass it to __fp_to_tl_dispatch:w.

\fp_to_tl:c

\fp_to_tl:n

```

15582 \cs_new:Npn \fp_to_tl:N #1 { \exp_after:wN \__fp_to_tl_dispatch:w #1 }
15583 \cs_generate_variant:Nn \fp_to_tl:N { c }
15584 \cs_new:Npn \fp_to_tl:n
15585 {
15586     \exp_after:wN \__fp_to_tl_dispatch:w
15587     \exp:w \exp_end_continue_f:w \__fp_parse:n
15588 }

```

(End definition for \fp_to_tl:N and \fp_to_tl:n. These functions are documented on page 175.)

__fp_to_tl_dispatch:w
__fp_to_tl_normal:nnnnn
__fp_to_tl_scientific:wnnnnn
__fp_to_tl_scientific:wNw

A structure similar to __fp_to_scientific_dispatch:w and __fp_to_decimal_dispatch:w, but without the “invalid operation” exception. First filter special cases. We express normal numbers in decimal notation if the exponent is in the range $[-2, 16]$, and otherwise use scientific notation.

```

15589 \cs_new:Npn \__fp_to_tl_dispatch:w \s__fp \__fp_chk:w #1#2
15590 {
15591     \if_meaning:w 2 #2 \exp_after:wN - \exp:w \exp_end_continue_f:w \fi:
15592     \if_case:w #1 \exp_stop_f:
15593         \__fp_case_return:nw { 0 }
15594     \or: \exp_after:wN \__fp_to_tl_normal:nnnnn
15595     \or: \__fp_case_return:nw { inf }
15596     \else: \__fp_case_return:nw { nan }
15597     \fi:
15598 }
15599 \cs_new:Npn \__fp_to_tl_normal:nnnnn #1
15600 {
15601     \int_compare:nTF
15602     { -2 <= #1 <= \c__fp_prec_int }
15603     { \__fp_to_decimal_normal:wnnnnn }
15604     { \__fp_to_tl_scientific:wnnnnn }
15605     \s__fp \__fp_chk:w 1 0 {#1}

```



```

15606     }
15607 \cs_new:Npn \__fp_to_tl_scientific:wnnnnn
15608   \s__fp \__fp_chk:w 1 #1 #2 #3#4#5#6 ;
15609   {
15610     \exp_after:wN \__fp_to_tl_scientific:wNw
15611     \exp_after:wN e
15612     \__int_value:w \__int_eval:w #2 - 1
15613     ; #3 #4 #5 #6 ;
15614   }
15615 \cs_new:Npn \__fp_to_tl_scientific:wNw #1 ; #2#3;
15616   { \__fp_trim_zeros:w #2.#3 ; #1 }

```

(End definition for __fp_to_tl_dispatch:w and others.)

29.5 Formatting

This is not implemented yet, as it is not yet clear what a correct interface would be, for this kind of structured conversion from a floating point (or other types of variables) to a string. Ideas welcome.

29.6 Convert to dimension or integer

\fp_to_dim:N These three public functions rely on \fp_to_decimal:n internally. We make sure to produce pt with category other.

```

\fp_to_dim:c
\fp_to_dim:n
15617 \cs_new:Npn \fp_to_dim:N #1
15618   { \fp_to_decimal:N #1 pt }
15619 \cs_generate_variant:Nn \fp_to_dim:N { c }
15620 \cs_new:Npn \fp_to_dim:n #1
15621   { \fp_to_decimal:n {#1} pt }

```

(End definition for \fp_to_dim:N and \fp_to_dim:n. These functions are documented on page 174.)

\fp_to_int:N These three public functions evaluate their argument, then pass it to \fp_to_int_dispatch:w.

```

\fp_to_int:c
\fp_to_int:n
15622 \cs_new:Npn \fp_to_int:N #1 { \exp_after:wN \__fp_to_int_dispatch:w #1 }
15623 \cs_generate_variant:Nn \fp_to_int:N { c }
15624 \cs_new:Npn \fp_to_int:n
15625   {
15626     \exp_after:wN \__fp_to_int_dispatch:w
15627     \exp:w \exp_end_continue_f:w \__fp_parse:n
15628   }

```

(End definition for \fp_to_int:N and \fp_to_int:n. These functions are documented on page 175.)

__fp_to_int_dispatch:w To convert to an integer, first round to 0 places (to the nearest integer), then express the result as a decimal number: the definition of __fp_to_decimal_dispatch:w is such that there will be no trailing dot nor zero.

```

15629 \cs_new:Npn \__fp_to_int_dispatch:w #1;
15630   {
15631     \exp_after:wN \__fp_to_decimal_dispatch:w \exp:w \exp_end_continue_f:w
15632     \__fp_round:Nwn \__fp_round_to_nearest:NNN #1; { 0 }
15633   }

```

(End definition for __fp_to_int_dispatch:w.)

29.7 Convert from a dimension

\dim_to_fp:n The dimension expression (which can in fact be a glue expression) is evaluated, converted to a number (*i.e.*, expressed in scaled points), then multiplied by $2^{-16} = 0.0000152587890625$ to give a value expressed in points. The auxiliary **__fp_mul_npos_o:Nww** expects the desired *final sign* and two floating point operands (of the form **\s__fp ...** ;) as arguments. This set of functions is also used to convert dimension registers to floating points while parsing expressions: in this context there is an additional exponent, which is the first argument of **__fp_from_dim_test:ww**, and is combined with the exponent -4 of 2^{-16} . There is also a need to expand afterwards: this is performed by **__fp_mul_npos_o:Nww**, and cancelled by **\prg_do_nothing:** in **\dim_to_fp:n**.

```

15634 \cs_new:Npn \dim_to_fp:n #1
15635 {
15636   \exp_after:wN \__fp_from_dim_test:ww
15637   \exp_after:wN 0
15638   \exp_after:wN ,
15639   \__int_value:w \etex_glueexpr:D #1 ;
15640 }
15641 \cs_new:Npn \__fp_from_dim_test:ww #1, #2
15642 {
15643   \if_meaning:w 0 #2
15644     \__fp_case_return:nw { \exp_after:wN \c_zero_fp }
15645   \else:
15646     \exp_after:wN \__fp_from_dim:wNw
15647     \__int_value:w \__int_eval:w #1 - 4
15648     \if_meaning:w - #2
15649       \exp_after:wN , \exp_after:wN 2 \__int_value:w
15650     \else:
15651       \exp_after:wN , \exp_after:wN 0 \__int_value:w #2
15652     \fi:
15653   \fi:
15654 }
15655 \cs_new:Npn \__fp_from_dim:wNw #1,#2#3;
15656 {
15657   \__fp_pack_twice_four:wNNNNNNNN \__fp_from_dim:wNNnnnnnn ;
15658   #3 000 0000 00 {10}987654321; #2 {#1}
15659 }
15660 \cs_new:Npn \__fp_from_dim:wNNnnnnnn #1; #2#3#4#5#6#7#8#9
15661 { \__fp_from_dim:wnnnnwNn #1 {#2#300} {0000} ; }
15662 \cs_new:Npn \__fp_from_dim:wnnnnwNn #1; #2#3#4#5#6; #7#8
15663 {
15664   \__fp_mul_npos_o:Nww #7
15665   \s__fp \__fp_chk:w 1 #7 {#5} #1 ;
15666   \s__fp \__fp_chk:w 1 0 {#8} {1525} {8789} {0625} {0000} ;
15667   \prg_do_nothing:
15668 }
```

(End definition for **\dim_to_fp:n** and others. These functions are documented on page 151.)

29.8 Use and eval

\fp_use:N Those public functions are simple copies of the decimal conversions.
\fp_use:c 15669 \cs_new_eq:NN \fp_use:N \fp_to_decimal:N
\fp_eval:n

```

15670 \cs_generate_variant:Nn \fp_use:N { c }
15671 \cs_new_eq:NN \fp_eval:n \fp_to_decimal:n

```

(End definition for `\fp_use:N` and `\fp_eval:n`. These functions are documented on page 175.)

\fp_abs:n Trivial but useful. See the implementation of `\fp_add:Nn` for an explanation of why to use `__fp_parse:n`, namely, for better error reporting.

```

15672 \cs_new:Npn \fp_abs:n #1
15673 { \fp_to_decimal:n { abs \__fp_parse:n {#1} } }

```

(End definition for `\fp_abs:n`. This function is documented on page 188.)

\fp_max:nn Similar to `\fp_abs:n`, for consistency with `\int_max:nn`, etc.

```

\fp_min:nn 15674 \cs_new:Npn \fp_max:nn #1#2
15675 { \fp_to_decimal:n { max ( \__fp_parse:n {#1} , \__fp_parse:n {#2} ) } }
15676 \cs_new:Npn \fp_min:nn #1#2
15677 { \fp_to_decimal:n { min ( \__fp_parse:n {#1} , \__fp_parse:n {#2} ) } }

```

(End definition for `\fp_max:nn` and `\fp_min:nn`. These functions are documented on page 188.)

29.9 Convert an array of floating points to a comma list

`__fp_array_to_clist:n` Converts an array of floating point numbers to a comma-list. If speed here ends up irrelevant, we can simplify the code for the auxiliary to become

```

\cs_new:Npn \__fp_array_to_clist_loop:Nw #1#2;
{
  \use_none:n #1
  { , ~ } \fp_to_tl:n { #1 #2 ; }
  \__fp_array_to_clist_loop:Nw
}

```

The `\use_ii:nn` function is expanded after `__fp_expand:n` is done, and it removes ,~ from the start of the representation.

```

15678 \cs_new:Npn \__fp_array_to_clist:n #1
15679 {
15680   \tl_if_empty:nF {#1}
15681   {
15682     \__fp_expand:n
15683     {
15684       { \use_ii:nn }
15685       \__fp_array_to_clist_loop:Nw #1 { ? \__prg_break: } ;
15686       \__prg_break_point:
15687     }
15688   }
15689 }
15690 \cs_new:Npx \__fp_array_to_clist_loop:Nw #1#2;
15691 {
15692   \exp_not:N \use_none:n #1
15693   \exp_not:N \exp_after:wN
15694   {
15695     \exp_not:N \exp_after:wN ,
15696     \exp_not:N \exp_after:wN \c_space_tl
15697     \exp_not:N \exp:w

```

```

15698      \exp_not:N      \exp_end_continue_f:w
15699      \exp_not:N      \__fp_to_tl_dispatch:w #1 #2 ;
15700      }
15701      \exp_not:N \__fp_array_to_clist_loop:Nw
15702  }

(End definition for \__fp_array_to_clist:n and \__fp_array_to_clist_loop:Nw.)

15703 </initex | package>

```

30 l3fp-random Implementation

```

15704 <*initex | package>
15705 <@@=fp>

```

30.1 Engine support

At present, X_YTeX, pTeX and upTeX do not provide random numbers, while LuaTeX and pdfTeX provide the primitive `\pdfutex_uniformdeviate:D` (`\pdfuniformdeviate` in pdfTeX and `\uniformdeviate` in LuaTeX). We write the test twice simply in order to write the false branch first.

```

15706 \cs_if_exist:NF \pdfutex_uniformdeviate:D
15707 {
15708   \__msg_kernel_new:nnn { kernel } { fp-no-random }
15709   { Random~numbers~unavailable }
15710   \cs_new:Npn \__fp_rand_o:Nw ? #1 @
15711   {
15712     \__msg_kernel_expandable_error:nn { kernel } { fp-no-random }
15713     \exp_after:wN \c_nan_fp
15714   }
15715   \cs_new_eq:NN \__fp_randint_o:Nw \__fp_rand_o:Nw
15716 }
15717 \cs_if_exist:NT \pdfutex_uniformdeviate:D
15718 {

```

`__fp_rand_uniform:` The `\pdfutex_uniformdeviate:D` primitive gives a pseudo-random integer in a range $[0, n - 1]$ of the user's choice. This number is meant to be uniformly distributed, but is produced by rescaling a uniform pseudo-random integer in $[0, 2^{28} - 1]$. For instance, setting n to (any multiple of) 2^{29} gives only even values. Thus it is only safe to call `\pdfutex_uniformdeviate:D` with argument 2^{28} . This integer is also used in the implementation of `\int_rand:nn`. We will also use variants of this number rounded down to multiples of 10^4 and 10^8 .

```

15719 \cs_new:Npn \__fp_rand_uniform:
15720 { \pdfutex_uniformdeviate:D \c__fp_rand_size_int }
15721 \int_const:Nn \c__fp_rand_size_int { 268 435 456 }
15722 \int_const:Nn \c__fp_rand_four_int { 268 430 000 }
15723 \int_const:Nn \c__fp_rand_eight_int { 200 000 000 }

```

(End definition for `__fp_rand_uniform:` and others.)

`__fp_rand_myriads:n` Used as `__fp_rand_myriads:n {XXX}` with one input character per block of four digit we want. Given a pseudo-random integer from the primitive, we extract 2 blocks of digits if possible, namely if the integer is less than 2×10^8 . If that's not possible, we try to

```

\__fp_rand_myriads_loop:nn
\__fp_rand_myriads_get:w
\__fp_rand_myriads_last:
\__fp_rand_myriads_last:w

```

extract 1 block, which succeeds in the range $[2 \times 10^8, 26843 \times 10^4)$. For the 5456 remaining possible values we just throw away the random integer and get a new one. Depending on whether we got 2, 1, or 0 blocks, remove the same number of characters from the input stream with `\use_i:nnn`, `\use_i:nn` or nothing.

```

15724 \cs_new:Npn \__fp_rand_myriads:n #1
15725 {
15726   \__fp_rand_myriads_loop:nn #1
15727   { ? \use_i_delimit_by_q_stop:nw \__fp_rand_myriads_last: }
15728   { ? \use_none_delimit_by_q_stop:w } \q_stop
15729 }
15730 \cs_new:Npn \__fp_rand_myriads_loop:nn #1#2
15731 {
15732   \use_none:n #2
15733   \exp_after:wN \__fp_rand_myriads_get:w
15734   \__int_value:w \__fp_rand_uniform: ; {#1}{#2}
15735 }
15736 \cs_new:Npn \__fp_rand_myriads_get:w #1 ;
15737 {
15738   \if_int_compare:w #1 < \c__fp_rand_eight_int
15739   \exp_after:wN \use_none:n
15740   \__int_value:w \__int_eval:w
15741   \c__fp_rand_eight_int + #1 \__int_eval_end:
15742   \exp_after:wN \use_i:nnn
15743   \else:
15744   \if_int_compare:w #1 < \c__fp_rand_four_int
15745   \exp_after:wN \use_none:nnnnn
15746   \__int_value:w \__int_eval:w
15747   \c__fp_rand_four_int + #1 \__int_eval_end:
15748   \exp_after:wN \exp_after:wN \exp_after:wN \use_i:nn
15749   \fi:
15750   \fi:
15751   \__fp_rand_myriads_loop:nn
15752 }
15753 \cs_new:Npn \__fp_rand_myriads_last:
15754 {
15755   \exp_after:wN \__fp_rand_myriads_last:w
15756   \__int_value:w \__fp_rand_uniform: ;
15757 }
15758 \cs_new:Npn \__fp_rand_myriads_last:w #1 ;
15759 {
15760   \if_int_compare:w #1 < \c__fp_rand_four_int
15761   \exp_after:wN \use_none:nnnnn
15762   \__int_value:w \__int_eval:w
15763   \c__fp_rand_four_int + #1 \__int_eval_end:
15764   \else:
15765   \exp_after:wN \__fp_rand_myriads_last:
15766   \fi:
15767 }

```

(End definition for `__fp_rand_myriads:n` and others.)

30.2 Random floating point

`__fp_rand_o:Nw` First we check that `random` was called without argument. Then get four blocks of four digits.

```
__fp_rand_o:
__fp_rand_o:w
15768 \cs_new:Npn __fp_rand_o:Nw ? #1 @
15769 {
15770   \tl_if_empty:nTF {#1}
15771   { __fp_rand_o: }
15772   {
15773     \msg_kernel_expandable_error:nnnnn
15774     { kernel } { fp-num-args } { rand() } { 0 } { 0 }
15775     \exp_after:wN \c_nan_fp
15776   }
15777 }
15778 \cs_new:Npn __fp_rand_o:
15779 { __fp_parse_o:n { . __fp_rand_myriads:n { xxxx } } }
```

(End definition for `__fp_rand_o:Nw`, `__fp_rand_o:`, and `__fp_rand_o:w`.)

30.3 Random integer

`__fp_randint_o:Nw` Enforce that there is one argument (then add first argument 1) or two arguments. Enforce that they are integers in $(-10^{16}, 10^{16})$ and ordered. We distinguish narrow ranges (less than 2^{28}) from wider ones.

`__fp_randint_e:w` For narrow ranges, compute the number n of possible outputs as an integer using `fp_to_int:n`, and reduce a pseudo-random 28-bit integer r modulo n . On its own, this is not uniform when $[0, 2^{28} - 1]$ does not divide evenly into intervals of size n . The auxiliary `__fp_randint_e:wwwNnn` discards the pseudo-random integer if it lies in an incomplete interval, and repeats.

`__fp_randint_e:wnn` For wide ranges we use the same code except for the last eight digits which use `__fp_rand_myriads:n`. It is not safe to combine the first digits with the last eight as a single string of digits, as this may exceed 16 digits and be rounded. Instead, we first add the first few digits (times 10^8) to the lower bound. The result is compared to the upper bound and the process repeats if needed.

```
15780 \cs_new:Npn __fp_randint_o:Nw ? #1 @
15781 {
15782   \if_case:w
15783   \__int_eval:w __fp_array_count:n {#1} - 1 \__int_eval_end:
15784   \exp_after:wN __fp_randint_e:w \c_one_fp #1
15785   \or: __fp_randint_e:w #1
15786   \else:
15787     \msg_kernel_expandable_error:nnnnn
15788     { kernel } { fp-num-args } { randint() } { 1 } { 2 }
15789     \exp_after:wN \c_nan_fp \exp:w
15790   \fi:
15791   \exp_after:wN \exp_end:
15792 }
15793 \cs_new:Npn __fp_randint_badarg:w \s_fp __fp_chk:w #1#2#3;
15794 {
15795   \__fp_int:wTF \s_fp __fp_chk:w #1#2#3;
15796   {
15797     \if_meaning:w 1 #1
15798     \if_int_compare:w
```

```

15799         \use_i_delimit_by_q_stop:nw #3 \q_stop > \c__fp_prec_int
15800         1 \exp_stop_f:
15801         \fi:
15802     \fi:
15803 }
15804 { 1 \exp_stop_f: }
15805 }
15806 \cs_new:Npn \__fp_randint_e:w #1; #2;
15807 {
15808     \if_case:w
15809         \__fp_randint_badarg:w #1;
15810         \__fp_randint_badarg:w #2;
15811         \fp_compare:nNnTF { #1; } > { #2; } { 1 } { 0 } \exp_stop_f:
15812         \exp_after:wN \exp_after:wN \exp_after:wN \__fp_randint_e:wnn
15813         \__fp_parse:n { #2; - #1; } { #1; } { #2; }
15814     \or:
15815         \__fp_invalid_operation_tl_o:ff
15816         { randint } { \__fp_array_to_clist:n { #1; #2; } }
15817         \exp:w
15818     \fi:
15819 }
15820 \cs_new:Npn \__fp_randint_e:wnn #1;
15821 {
15822     \exp_after:wN \__fp_randint_e:wwNnn
15823     \__int_value:w \__fp_rand_uniform: \exp_after:wN ;
15824     \exp:w \exp_end_continue_f:w
15825     \fp_compare:nNnTF { #1 ; } < \c__fp_rand_size_int
15826     { \fp_to_int:n { #1 ; + 1 } ; \__fp_randint_narrow_e:nnnn }
15827     { \fp_to_int:n { floor(#1 ; * 1e-8 + 1) } ; \__fp_randint_wide_e:nnnn }
15828 }
15829 \cs_new:Npn \__fp_randint_e:wwNnn #1 ; #2 ;
15830 {
15831     \exp_after:wN \__fp_randint_e:wwwNnn
15832     \__int_value:w \int_mod:nn {#1} {#2} ; #1 ; #2 ;
15833 }
15834 \cs_new:Npn \__fp_randint_e:wwwNnn #1 ; #2 ; #3 ; #4
15835 {
15836     \int_compare:nNnTF { #2 - #1 + #3 } > \c__fp_rand_size_int
15837     {
15838         \exp_after:wN \__fp_randint_e:wwNnn
15839         \__int_value:w \__fp_rand_uniform: ; #3 ; #4
15840     }
15841     { #4 {#1} {#3} }
15842 }
15843 \cs_new:Npn \__fp_randint_narrow_e:nnnn #1#2#3#4
15844 { \__fp_parse_o:n { #3 + #1 } \exp:w }
15845 \cs_new:Npn \__fp_randint_wide_e:nnnn #1#2#3#4
15846 {
15847     \exp_after:wN \exp_after:wN
15848     \exp_after:wN \__fp_randint_wide_e:wnnn
15849     \__fp_parse:n { #3 + #1e8 + \__fp_rand_myriads:n { xx } }
15850     {#2} {#3} {#4}
15851 }
15852 \cs_new:Npn \__fp_randint_wide_e:wnnn #1 ; #2#3#4

```

```

15853 {
15854   \fp_compare:nNnTF { #1 ; } > {#4}
15855   {
15856     \exp_after:wN \__fp_randint_e:wwNnn
15857     \__int_value:w \__fp_rand_uniform: ; #2 ;
15858     \__fp_randint_wide_e:nnnn {#3} {#4}
15859   }
15860   { \__fp_exp_after_o:w #1 ; \exp:w }
15861 }

```

(End definition for `__fp_randint_o:Nw` and others.)

End the initial conditional that ensures these commands are only defined in pdfTeX and LuaTeX.

```

15862 }
15863 </initex | package>

```

31 l3fp-assign implementation

```

15864 <*initex | package>
15865 <@@=fp>

```

31.1 Assigning values

\fp_new:N Floating point variables are initialized to be +0.

```

15866 \cs_new_protected:Npn \fp_new:N #1
15867 { \cs_new_eq:NN #1 \c_zero_fp }
15868 \cs_generate_variant:Nn \fp_new:N {c}

```

(End definition for `\fp_new:N`. This function is documented on page 173.)

\fp_set:Nn Simply use `__fp_parse:n` within various f-expanding assignments.

```

\fp_set:cn 15869 \cs_new_protected:Npn \fp_set:Nn #1#2
\fp_gset:Nn 15870 { \tl_set:Nx #1 { \exp_not:f { \__fp_parse:n {#2} } } }
\fp_gset:cn 15871 \cs_new_protected:Npn \fp_gset:Nn #1#2
\fp_const:Nn 15872 { \tl_gset:Nx #1 { \exp_not:f { \__fp_parse:n {#2} } } }
\fp_const:cn 15873 \cs_new_protected:Npn \fp_const:Nn #1#2
15874 { \tl_const:Nx #1 { \exp_not:f { \__fp_parse:n {#2} } } }
15875 \cs_generate_variant:Nn \fp_set:Nn {c}
15876 \cs_generate_variant:Nn \fp_gset:Nn {c}
15877 \cs_generate_variant:Nn \fp_const:Nn {c}

```

(End definition for `\fp_set:Nn`, `\fp_gset:Nn`, and `\fp_const:Nn`. These functions are documented on page 173.)

\fp_set_eq:NN Copying a floating point is the same as copying the underlying token list.

```

\fp_set_eq:cN 15878 \cs_new_eq:NN \fp_set_eq:NN \tl_set_eq:NN
\fp_set_eq:Nc 15879 \cs_new_eq:NN \fp_gset_eq:NN \tl_gset_eq:NN
\fp_set_eq:cc 15880 \cs_generate_variant:Nn \fp_set_eq:NN { c , Nc , cc }
\fp_gset_eq:NN 15881 \cs_generate_variant:Nn \fp_gset_eq:NN { c , Nc , cc }
\fp_gset_eq:cN
\fp_gset_eq:Nc
\fp_gset_eq:cc

```

(End definition for `\fp_set_eq:NN` and `\fp_gset_eq:NN`. These functions are documented on page 174.)


```

\fp_zero:N Setting a floating point to zero: copy \c_zero_fp.
\fp_zero:c 15882 \cs_new_protected:Npn \fp_zero:N #1 { \fp_set_eq:NN #1 \c_zero_fp }
\fp_gzero:N 15883 \cs_new_protected:Npn \fp_gzero:N #1 { \fp_gset_eq:NN #1 \c_zero_fp }
\fp_gzero:c 15884 \cs_generate_variant:Nn \fp_zero:N { c }
15885 \cs_generate_variant:Nn \fp_gzero:N { c }

(End definition for \fp_zero:N and \fp_gzero:N. These functions are documented on page 173.)

```

```

\fp_zero_new:N Set the floating point to zero, or define it if needed.
\fp_zero_new:c 15886 \cs_new_protected:Npn \fp_zero_new:N #1
\fp_gzero_new:N 15887 { \fp_if_exist:NTF #1 { \fp_zero:N #1 } { \fp_new:N #1 } }
\fp_gzero_new:c 15888 \cs_new_protected:Npn \fp_gzero_new:N #1
15889 { \fp_if_exist:NTF #1 { \fp_gzero:N #1 } { \fp_new:N #1 } }
15890 \cs_generate_variant:Nn \fp_zero_new:N { c }
15891 \cs_generate_variant:Nn \fp_gzero_new:N { c }

(End definition for \fp_zero_new:N and \fp_gzero_new:N. These functions are documented on page 173.)

```

31.2 Updating values

These match the equivalent functions in l3int and l3skip.

```

\fp_add:Nn For the sake of error recovery we should not simply set #1 to #1 ± (#2): for instance, if #2
\fp_add:cn is 0)+2, the parsing error would be raised at the last closing parenthesis rather than at
\fp_gadd:Nn the closing parenthesis in the user argument. Thus we evaluate #2 instead of just putting
\fp_gadd:cn parentheses. As an optimization we use \__fp_parse:n rather than \fp_eval:n, which
\fp_sub:Nn would convert the result away from the internal representation and back.
\fp_sub:cn 15892 \cs_new_protected:Npn \fp_add:Nn { \__fp_add:NNNn \fp_set:Nn + }
\fp_gsub:Nn 15893 \cs_new_protected:Npn \fp_gadd:Nn { \__fp_add:NNNn \fp_gset:Nn + }
\fp_gsub:cn 15894 \cs_new_protected:Npn \fp_sub:Nn { \__fp_add:NNNn \fp_set:Nn - }
\__fp_add:NNNn 15895 \cs_new_protected:Npn \fp_gsub:Nn { \__fp_add:NNNn \fp_gset:Nn - }
15896 \cs_new_protected:Npn \__fp_add:NNNn #1#2#3#4
15897 { #1 #3 { #3 #2 \__fp_parse:n {#4} } }
15898 \cs_generate_variant:Nn \fp_add:Nn { c }
15899 \cs_generate_variant:Nn \fp_gadd:Nn { c }
15900 \cs_generate_variant:Nn \fp_sub:Nn { c }
15901 \cs_generate_variant:Nn \fp_gsub:Nn { c }

(End definition for \fp_add:Nn and others. These functions are documented on page 174.)

```

31.3 Showing values

```

\fp_show:N This shows the result of computing its argument. The input of \__msg_show_-
\fp_show:c variable:NNNnn must start with >~ (or be empty).
\fp_show:n 15902 \cs_new_protected:Npn \fp_show:N #1
15903 {
15904   \__msg_show_variable:NNNnn #1 \fp_if_exist:NTF ? { }
15905   { > ~ \token_to_str:N #1 = \fp_to_tl:N #1 }
15906 }
15907 \cs_new_protected:Npn \fp_show:n
15908 { \__msg_show_wrap:Nn \fp_to_tl:n }
15909 \cs_generate_variant:Nn \fp_show:N { c }

```

(End definition for `\fp_show:N` and `\fp_show:n`. These functions are documented on page 180.)

`\fp_log:N` Redirect output of `\fp_show:N` and `\fp_show:n` to the log.

```
\fp_log:c 15910 \cs_new_protected:Npn \fp_log:N
\fp_log:n 15911 { \__msg_log_next: \fp_show:N }
15912 \cs_new_protected:Npn \fp_log:n
15913 { \__msg_log_next: \fp_show:n }
15914 \cs_generate_variant:Nn \fp_log:N { c }
```

(End definition for `\fp_log:N` and `\fp_log:n`. These functions are documented on page 180.)

31.4 Some useful constants and scratch variables

`\c_one_fp` Some constants.

```
\c_e_fp 15915 \fp_const:Nn \c_e_fp { 2.718 2818 2845 9045 }
15916 \fp_const:Nn \c_one_fp { 1 }
```

(End definition for `\c_one_fp` and `\c_e_fp`. These variables are documented on page 178.)

`\c_pi_fp` We simply round π to the closest multiple of 10^{-15} .

```
\c_one_degree_fp 15917 \fp_const:Nn \c_pi_fp { 3.141 5926 5358 9793 }
15918 \fp_const:Nn \c_one_degree_fp { 0.0 1745 3292 5199 4330 }
```

(End definition for `\c_pi_fp` and `\c_one_degree_fp`. These variables are documented on page 179.)

`\l_tmpa_fp` Scratch variables are simply initialized there.

```
\l_tmpb_fp 15919 \fp_new:N \l_tmpa_fp
\g_tmpa_fp 15920 \fp_new:N \l_tmpb_fp
\g_tmpb_fp 15921 \fp_new:N \g_tmpa_fp
15922 \fp_new:N \g_tmpb_fp
```

(End definition for `\l_tmpa_fp` and others. These variables are documented on page 179.)

```
15923 </initex | package>
```

32 l3sort implementation

```
15924 <*initex | package>
```

```
15925 <@@=sort>
```

32.1 Variables

`\l__sort_length_int` The sequence has `\l__sort_length_int` items and is stored from `\l__sort_min_int` to `\l__sort_top_int - 1`. While reading the sequence in memory, we check that `\l__sort_top_int` remains at most `\l__sort_max_int`, precomputed by `__sort_compute_range:`. That bound is such that the merge sort will only use `\toks` registers less than `\l__sort_true_max_int`, namely those that have not been allocated for use in other code: the user's comparison code could alter these.

```
15926 \int_new:N \l__sort_length_int
15927 \int_new:N \l__sort_min_int
15928 \int_new:N \l__sort_top_int
15929 \int_new:N \l__sort_max_int
15930 \int_new:N \l__sort_true_max_int
```

(End definition for \l__sort_length_int and others.)

\l__sort_block_int Merge sort is done in several passes. In each pass, blocks of size \l__sort_block_int are merged in pairs. The block size starts at 1, and, for a length in the range $[2^k + 1, 2^{k+1}]$, reaches 2^k in the last pass.

```
15931 \int_new:N \l__sort_block_int
```

(End definition for \l__sort_block_int.)

\l__sort_begin_int \l__sort_end_int When merging two blocks, \l__sort_begin_int marks the lowest index in the two blocks, and \l__sort_end_int marks the highest index, plus 1.

```
15932 \int_new:N \l__sort_begin_int
```

```
15933 \int_new:N \l__sort_end_int
```

(End definition for \l__sort_begin_int and \l__sort_end_int.)

\l__sort_A_int \l__sort_B_int \l__sort_C_int When merging two blocks (whose end-points are beg and end), A starts from the high end of the low block, and decreases until reaching beg. The index B starts from the top of the range and marks the register in which a sorted item should be put. Finally, C points to the copy of the high block in the interval of registers starting at \l__sort_length_int, upwards. C starts from the upper limit of that range.

```
15934 \int_new:N \l__sort_A_int
```

```
15935 \int_new:N \l__sort_B_int
```

```
15936 \int_new:N \l__sort_C_int
```

(End definition for \l__sort_A_int, \l__sort_B_int, and \l__sort_C_int.)

32.2 Finding available \toks registers

__sort_shrink_range: __sort_shrink_range_loop: After __sort_compute_range: (defined below) determines that \toks registers between \l__sort_min_int (included) and \l__sort_true_max_int (excluded) have not yet been assigned, __sort_shrink_range: computes \l__sort_max_int to reflect the need for a buffer when merging blocks in the merge sort. Given $2^n \leq A \leq 2^n + 2^{n-1}$ registers we can sort $\lfloor A/2 \rfloor + 2^{n-2}$ items while if we have $2^n + 2^{n-1} \leq A \leq 2^{n+1}$ registers we can sort $A - 2^{n-1}$ items. We first find out a power 2^n such that $2^n \leq A \leq 2^{n+1}$ by repeatedly halving \l__sort_block_int, starting at 2^{15} or 2^{14} namely half the total number of registers, then we use the formulas and set \l__sort_max_int.

```
15937 \cs_new_protected:Npn \__sort_shrink_range:
15938 {
15939   \int_set:Nn \l__sort_A_int
15940     { \l__sort_true_max_int - \l__sort_min_int + 1 }
15941   \int_set:Nn \l__sort_block_int { \c_max_register_int / 2 }
15942   \__sort_shrink_range_loop:
15943   \int_set:Nn \l__sort_max_int
15944     {
15945     \int_compare:nNnTF
15946       { \l__sort_block_int * 3 / 2 } > \l__sort_A_int
15947       {
15948         \l__sort_min_int
15949         + ( \l__sort_A_int - 1 ) / 2
15950         + \l__sort_block_int / 4
15951         - 1
15952       }
15953     }
```

```

15953         { \l__sort_true_max_int - \l__sort_block_int / 2 }
15954     }
15955 }
15956 \cs_new_protected:Npn \__sort_shrink_range_loop:
15957 {
15958     \if_int_compare:w \l__sort_A_int < \l__sort_block_int
15959         \tex_divide:D \l__sort_block_int 2 \exp_stop_f:
15960         \exp_after:wN \__sort_shrink_range_loop:
15961     \fi:
15962 }

```

(End definition for __sort_shrink_range: and __sort_shrink_range_loop:.)

__sort_compute_range: First find out what \toks have not yet been assigned. There are many cases. In L^AT_EX 2_ε with no package, available \toks range from \count15 + 1 to \c_max_register_int included (this was not altered despite the 2015 changes). When \loctoks is defined, namely in plain (e)T_EX, or when the package etex is loaded in L^AT_EX 2_ε, redefine __sort_compute_range: to use the range \count265 to \count275 - 1. The elocalloc package also defines \loctoks but uses yet another number for the upper bound, namely \e@alloc@top (minus one). We must check for \loctoks every time a sorting function is called, as etex or elocalloc could be loaded.

In ConT_EXt MkIV the range is from \c_syst_last_allocated_toks + 1 to \c_max_register_int, and in MkII it is from \lastallocatedtoks + 1 to \c_max_register_int. In all these cases, call __sort_shrink_range:. The L^AT_EX 3 format mode is easiest: no \toks are ever allocated so available \toks range from 0 to \c_max_register_int and we precompute the result of __sort_shrink_range:.

```

15963 (*package)
15964 \cs_new_protected:Npn \__sort_compute_range:
15965 {
15966     \int_set:Nn \l__sort_min_int { \tex_count:D 15 + 1 }
15967     \int_set:Nn \l__sort_true_max_int { \c_max_register_int + 1 }
15968     \__sort_shrink_range:
15969     \if_meaning:w \loctoks \tex_undefined:D \else:
15970         \if_meaning:w \loctoks \scan_stop: \else:
15971             \__sort_redefine_compute_range:
15972             \__sort_compute_range:
15973         \fi:
15974     \fi:
15975 }
15976 \cs_new_protected:Npn \__sort_redefine_compute_range:
15977 {
15978     \cs_if_exist:cTF { ver@elocalloc.sty }
15979     {
15980         \cs_gset_protected:Npn \__sort_compute_range:
15981         {
15982             \int_set:Nn \l__sort_min_int { \tex_count:D 265 }
15983             \int_set_eq:NN \l__sort_true_max_int \e@alloc@top
15984             \__sort_shrink_range:
15985         }
15986     }
15987     {
15988         \cs_gset_protected:Npn \__sort_compute_range:
15989         {

```

```

15990         \int_set:Nn \l__sort_min_int { \tex_count:D 265 }
15991         \int_set:Nn \l__sort_true_max_int { \tex_count:D 275 }
15992         \__sort_shrink_range:
15993     }
15994 }
15995 }
15996 \cs_if_exist:NT \loctoks { \__sort_redefine_compute_range: }
15997 \tl_map_inline:nn { \lastallocatedtoks \c_syst_last_allocated_toks }
15998 {
15999     \cs_if_exist:NT #1
16000     {
16001         \cs_gset_protected:Npn \__sort_compute_range:
16002         {
16003             \int_set:Nn \l__sort_min_int { #1 + 1 }
16004             \int_set:Nn \l__sort_true_max_int { \c_max_register_int + 1 }
16005             \__sort_shrink_range:
16006         }
16007     }
16008 }
16009 </package>
16010 *initex>
16011 \int_const:Nn \c__sort_max_length_int
16012 { ( \c_max_register_int + 1 ) * 3 / 4 }
16013 \cs_new_protected:Npn \__sort_compute_range:
16014 {
16015     \int_set:Nn \l__sort_min_int { 0 }
16016     \int_set:Nn \l__sort_true_max_int { \c_max_register_int + 1 }
16017     \int_set:Nn \l__sort_max_int { \c__sort_max_length_int }
16018 }
16019 </initex>

```

(End definition for `__sort_compute_range:`, `__sort_redefine_compute_range:`, and `\c__sort_max_length_int`.)

32.3 Protected user commands

`__sort_main:NNNnNn` Sorting happens in three steps. First store items in `\toks` registers ranging from `\l__sort_min_int` to `\l__sort_top_int - 1`, while checking that the list is not too long. If we reach the maximum length, all further items are entirely ignored after raising an error. Secondly, sort the array of `\toks` registers, using the user-defined sorting function, #6. Finally, unpack the `\toks` registers (now sorted) into a variable of the right type, by x-expanding the code in #4, specific to each type of list.

```

16020 \cs_new_protected:Npn \__sort_main:NNNnNn #1#2#3#4#5#6
16021 {
16022     \group_begin:
16023     (package) \__sort_disable_toksdef:
16024     \__sort_compute_range:
16025     \int_set_eq:NN \l__sort_top_int \l__sort_min_int
16026     #2 #5
16027     {
16028         \if_int_compare:w \l__sort_top_int = \l__sort_max_int
16029         \__sort_too_long_error:NNw #3 #5
16030         \fi:
16031         \tex_toks:D \l__sort_top_int {##1}

```

```

16032         \int_incr:N \l__sort_top_int
16033     }
16034     \int_set:Nn \l__sort_length_int
16035       { \l__sort_top_int - \l__sort_min_int }
16036     \cs_set:Npn \__sort_compare:nn ##1 ##2 { #6 }
16037     \int_set:Nn \l__sort_block_int { 1 }
16038     \__sort_level:
16039     \use:x
16040     {
16041         \group_end:
16042         #1 \exp_not:N #5 {#4}
16043     }
16044 }

```

(End definition for `__sort_main:NNNnNn`.)

`\seq_sort:Nn` The first argument to `__sort_main:NNNnNn` is the final assignment function used, either `\tl_set:Nn` or `\tl_gset:Nn` to control local versus global results. The second argument is what mapping function is used when storing items to `\toks` registers, and the third breaks away from the loop. The fourth is used to build back the correct kind of list from the contents of the `\toks` registers, including the leading `\s__seq`. Fifth and sixth arguments are the variable to sort, and the sorting method as inline code.

```

16045 \cs_new_protected:Npn \seq_sort:Nn
16046 {
16047     \__sort_main:NNNnNn \tl_set:Nn
16048     \seq_map_inline:Nn \seq_map_break:n
16049     { \s__seq \__sort_toks:NN \exp_not:N \__seq_item:n }
16050 }
16051 \cs_generate_variant:Nn \seq_sort:Nn { c }
16052 \cs_new_protected:Npn \seq_gsort:Nn
16053 {
16054     \__sort_main:NNNnNn \tl_gset:Nn
16055     \seq_map_inline:Nn \seq_map_break:n
16056     { \s__seq \__sort_toks:NN \exp_not:N \__seq_item:n }
16057 }
16058 \cs_generate_variant:Nn \seq_gsort:Nn { c }

```

(End definition for `\seq_sort:Nn` and `\seq_gsort:Nn`. These functions are documented on page 61.)

`\tl_sort:Nn` Again, use `\tl_set:Nn` or `\tl_gset:Nn` to control the scope of the assignment. Mapping through the token list is done with `\tl_map_inline:Nn`, and producing the token list is very similar to sequences, removing `__seq_item:n`.

`\tl_gsort:Nn`
`\tl_gsort:cn`

```

16059 \cs_new_protected:Npn \tl_sort:Nn
16060 {
16061     \__sort_main:NNNnNn \tl_set:Nn
16062     \tl_map_inline:Nn \tl_map_break:n
16063     { \__sort_toks:NN \prg_do_nothing: \prg_do_nothing: }
16064 }
16065 \cs_generate_variant:Nn \tl_sort:Nn { c }
16066 \cs_new_protected:Npn \tl_gsort:Nn
16067 {
16068     \__sort_main:NNNnNn \tl_gset:Nn
16069     \tl_map_inline:Nn \tl_map_break:n
16070     { \__sort_toks:NN \prg_do_nothing: \prg_do_nothing: }

```

```

16071 }
16072 \cs_generate_variant:Nn \tl_gsort:Nn { c }

```

(End definition for `\tl_sort:Nn` and `\tl_gsort:Nn`. These functions are documented on page 43.)

`\clist_sort:Nn` The case of empty comma-lists is a little bit special as usual, and filtered out: there is nothing to sort in that case. Otherwise, the input is done with `\clist_map_inline:Nn`, and the output requires some more elaborate processing than for sequences and token lists. The first comma must be removed. An item must be wrapped in an extra set of braces if it contains either the space or the comma characters. This is taken care of by `\clist_wrap_item:n`, but `__sort_toks:NN` would simply feed `\tex_the:D \tex_toks:D <number>` as an argument to that function; hence we need to expand this argument once to unpack the register.

```

16073 \cs_new_protected:Npn \clist_sort:Nn
16074 { \__sort_clist:NNn \tl_set:Nn }
16075 \cs_new_protected:Npn \clist_gsort:Nn
16076 { \__sort_clist:NNn \tl_gset:Nn }
16077 \cs_generate_variant:Nn \clist_sort:Nn { c }
16078 \cs_generate_variant:Nn \clist_gsort:Nn { c }
16079 \cs_new_protected:Npn \__sort_clist:NNn #1#2#3
16080 {
16081   \clist_if_empty:NF #2
16082   {
16083     \__sort_main:NNNnNn #1
16084     \clist_map_inline:Nn \clist_map_break:n
16085     {
16086       \exp_last_unbraced:Nf \use_none:n
16087       { \__sort_toks:NN \exp_args:No \__clist_wrap_item:n }
16088     }
16089     #2 {#3}
16090   }
16091 }

```

(End definition for `\clist_sort:Nn`, `\clist_gsort:Nn`, and `__sort_clist:NNn`. These functions are documented on page 99.)

`__sort_toks:NN` Unpack the various `\toks` registers, from `\l__sort_min_int` to `\l__sort_top_int - 1`.
`__sort_toks:NNw` The functions #1 and #2 allow us to treat the three data structures in a unified way:

- for sequences, they are `\exp_not:N __seq_item:n`, expanding to the `__seq_item:n` separator, as expected;
- for token lists, they expand to nothing;
- for comma lists, they expand to `\exp_args:No \clist_wrap_item:n`, taking care of unpacking the register before letting the undocumented internal `clist` function `\clist_wrap_item:n` do the work of putting a comma and possibly braces.

```

16092 \cs_new:Npn \__sort_toks:NN #1#2
16093 { \__sort_toks:NNw #1 #2 \l__sort_min_int ; }
16094 \cs_new:Npn \__sort_toks:NNw #1#2#3 ;
16095 {
16096   \if_int_compare:w #3 < \l__sort_top_int
16097   #1 #2 { \tex_the:D \tex_toks:D #3 }
16098   \exp_after:wN \__sort_toks:NNw \exp_after:wN #1 \exp_after:wN #2

```

```

16099     \__int_value:w \__int_eval:w #3 + 1 \exp_after:wN ;
16100     \fi:
16101 }

```

(End definition for `__sort_toks:NN` and `__sort_toks:NNw`.)

32.4 Merge sort

`__sort_level:` This function is called once blocks of size `\l__sort_block_int` (initially 1) are each sorted. If the whole list fits in one block, then we are done (this also takes care of the case of an empty list or a list with one item). Otherwise, go through pairs of blocks starting from 0, then double the block size, and repeat.

```

16102 \cs_new_protected:Npn \__sort_level:
16103 {
16104     \if_int_compare:w \l__sort_block_int < \l__sort_length_int
16105         \l__sort_end_int \l__sort_min_int
16106         \__sort_merge_blocks:
16107         \tex_advance:D \l__sort_block_int \l__sort_block_int
16108         \exp_after:wN \__sort_level:
16109     \fi:
16110 }

```

(End definition for `__sort_level:`.)

`__sort_merge_blocks:` This function is called to merge a pair of blocks, starting at the last value of `\l__sort_end_int` (end-point of the previous pair of blocks). If shifting by one block to the right we reach the end of the list, then this pass has ended: the end of the list is sorted already. Otherwise, store the result of that shift in *A*, which will index the first block starting from the top end. Then locate the end-point (maximum) of the second block: shift *end* upwards by one more block, but keeping it $\leq \text{top}$. Copy this upper block of `\toks` registers in registers above *length*, indexed by *C*: this is covered by `__sort_copy_block:`. Once this is done we are ready to do the actual merger using `__sort_merge_blocks_aux:`, after shifting *A*, *B* and *C* so that they point to the largest index in their respective ranges rather than pointing just beyond those ranges. Of course, once that pair of blocks is merged, move on to the next pair.

```

16111 \cs_new_protected:Npn \__sort_merge_blocks:
16112 {
16113     \l__sort_begin_int \l__sort_end_int
16114     \tex_advance:D \l__sort_end_int \l__sort_block_int
16115     \if_int_compare:w \l__sort_end_int < \l__sort_top_int
16116         \l__sort_A_int \l__sort_end_int
16117         \tex_advance:D \l__sort_end_int \l__sort_block_int
16118         \if_int_compare:w \l__sort_end_int > \l__sort_top_int
16119             \l__sort_end_int \l__sort_top_int
16120         \fi:
16121         \l__sort_B_int \l__sort_A_int
16122         \l__sort_C_int \l__sort_top_int
16123         \__sort_copy_block:
16124         \int_decr:N \l__sort_A_int
16125         \int_decr:N \l__sort_B_int
16126         \int_decr:N \l__sort_C_int
16127         \exp_after:wN \__sort_merge_blocks_aux:
16128         \exp_after:wN \__sort_merge_blocks:

```



```

16129     \fi:
16130   }

```

(End definition for `_sort_merge_blocks:`.)

`_sort_copy_block:` We wish to store a copy of the “upper” block of `\toks` registers, ranging between the initial value of `\l_sort_B_int` (included) and `\l_sort_end_int` (excluded) into a new range starting at the initial value of `\l_sort_C_int`, namely `\l_sort_top_int`.

```

16131 \cs_new_protected:Npn \_sort_copy_block:
16132 {
16133   \tex_toks:D \l\_sort_C_int \tex_toks:D \l\_sort_B_int
16134   \int_incr:N \l\_sort_C_int
16135   \int_incr:N \l\_sort_B_int
16136   \if_int_compare:w \l\_sort_B_int = \l\_sort_end_int
16137     \use_i:nn
16138   \fi:
16139   \_sort_copy_block:
16140 }

```

(End definition for `_sort_copy_block:`.)

`_sort_merge_blocks_aux:` At this stage, the first block starts at `\l_sort_begin_int`, and ends at `\l_sort_A_int`, and the second block starts at `\l_sort_top_int` and ends at `\l_sort_C_int`. The result of the merger is stored at positions indexed by `\l_sort_B_int`, which starts at `\l_sort_end_int - 1` and decreases down to `\l_sort_begin_int`, covering the full range of the two blocks. In other words, we are building the merger starting with the largest values. The comparison function is defined to return either `swapped` or `same`. Of course, this means the arguments need to be given in the order they appear originally in the list.

```

16141 \cs_new_protected:Npn \_sort_merge_blocks_aux:
16142 {
16143   \exp_after:wN \_sort_compare:nn \exp_after:wN
16144     { \tex_the:D \tex_toks:D \exp_after:wN \l\_sort_A_int \exp_after:wN }
16145   \exp_after:wN { \tex_the:D \tex_toks:D \l\_sort_C_int }
16146   \prg_do_nothing:
16147   \_sort_return_mark:N
16148   \_sort_return_mark:N
16149   \_sort_return_none_error:
16150 }

```

(End definition for `_sort_merge_blocks_aux:`.)

`\sort_return_same:` The marker removes one token. Each comparison should call `\sort_return_same:` or `\sort_return_swapped:` exactly once. If neither is called, `_sort_return_none_error:` is called.

```

\sort_return_swapped:
\_sort_return_mark:N
\_sort_return_none_error:
\_sort_return_two_error:w
16151 \cs_new_protected:Npn \sort_return_same: #1 \_sort_return_mark:N
16152 { #1 \_sort_return_mark:N \_sort_return_two_error:w \_sort_return_same: }
16153 \cs_new_protected:Npn \sort_return_swapped: #1 \_sort_return_mark:N
16154 { #1 \_sort_return_mark:N \_sort_return_two_error:w \_sort_return_swapped: }
16155 \cs_new_protected:Npn \_sort_return_mark:N #1 { }
16156 \cs_new_protected:Npn \_sort_return_none_error:
16157 {
16158   \_msg_kernel_error:nxxx { sort } { return-none }
16159   { \tex_the:D \tex_toks:D \l\_sort_A_int }

```

```

16160      { \tex_the:D \tex_toks:D \l__sort_C_int }
16161      \__sort_return_same:
16162    }
16163    \cs_new_protected:Npn \__sort_return_two_error:w
16164      #1 \__sort_return_none_error:
16165      { \__msg_kernel_error:nn { sort } { return-two } }

```

(End definition for \sort_return_same: and others. These functions are documented on page ??.)

__sort_return_same: If the comparison function returns **same**, then the second argument fed to **__sort_compare:nn** should remain to the right of the other one. Since we build the merger starting from the right, we copy that **\toks** register into the allotted range, then shift the pointers *B* and *C*, and go on to do one more step in the merger, unless the second block has been exhausted: then the remainder of the first block is already in the correct registers and we are done with merging those two blocks.

```

16166    \cs_new_protected:Npn \__sort_return_same:
16167      {
16168        \tex_toks:D \l__sort_B_int \tex_toks:D \l__sort_C_int
16169        \int_decr:N \l__sort_B_int
16170        \int_decr:N \l__sort_C_int
16171        \if_int_compare:w \l__sort_C_int < \l__sort_top_int
16172          \use_i:nn
16173        \fi:
16174        \__sort_merge_blocks_aux:
16175      }

```

(End definition for __sort_return_same:.)

__sort_return_swapped: If the comparison function returns **swapped**, then the next item to add to the merger is the first argument, contents of the **\toks** register *A*. Then shift the pointers *A* and *B* to the left, and go for one more step for the merger, unless the left block was exhausted (*A* goes below the threshold). In that case, all remaining **\toks** registers in the second block, indexed by *C*, are copied to the merger by **__sort_merge_blocks_end:**.

```

16176    \cs_new_protected:Npn \__sort_return_swapped:
16177      {
16178        \tex_toks:D \l__sort_B_int \tex_toks:D \l__sort_A_int
16179        \int_decr:N \l__sort_B_int
16180        \int_decr:N \l__sort_A_int
16181        \if_int_compare:w \l__sort_A_int < \l__sort_begin_int
16182          \__sort_merge_blocks_end: \use_i:nn
16183        \fi:
16184        \__sort_merge_blocks_aux:
16185      }

```

(End definition for __sort_return_swapped:.)

__sort_merge_blocks_end: This function's task is to copy the **\toks** registers in the block indexed by *C* to the merger indexed by *B*. The end can equally be detected by checking when *B* reaches the threshold **begin**, or when *C* reaches **top**.

```

16186    \cs_new_protected:Npn \__sort_merge_blocks_end:
16187      {
16188        \tex_toks:D \l__sort_B_int \tex_toks:D \l__sort_C_int
16189        \int_decr:N \l__sort_B_int
16190        \int_decr:N \l__sort_C_int

```

```

16191     \if_int_compare:w \l__sort_B_int < \l__sort_begin_int
16192         \use_i:nn
16193     \fi:
16194     \__sort_merge_blocks_end:
16195 }

```

(End definition for __sort_merge_blocks_end:.)

32.5 Expandable sorting

Sorting expandably is very different from sorting and assigning to a variable. Since tokens cannot be stored, they must remain in the input stream, and be read through at every step. It is thus necessarily much slower (at best $O(n^2 \ln n)$) than non-expandable sorting functions ($O(n \ln n)$).

A prototypical version of expandable quicksort is as follows. If the argument has no item, return nothing, otherwise partition, using the first item as a pivot (argument #4 of __sort:nnNnn). The arguments of __sort:nnNnn are 1. items less than #4, 2. items greater or equal to #4, 3. comparison, 4. pivot, 5. next item to test. If #5 is the tail of the list, call \tl_sort:nN on #1 and on #2, placing #4 in between; \use:ff expands the parts to make \tl_sort:nN f-expandable. Otherwise, compare #4 and #5 using #3. If they are ordered, place #5 amongst the “greater” items, otherwise amongst the “lesser” items, and continue partitioning.

```

\cs_new:Npn \tl_sort:nN #1#2
{
  \tl_if_blank:nF {#1}
  {
    \__sort:nnNnn { } { } #2
    #1 \q_recursion_tail \q_recursion_stop
  }
}
\cs_new:Npn \__sort:nnNnn #1#2#3#4#5
{
  \quark_if_recursion_tail_stop_do:nn {#5}
  { \use:ff { \tl_sort:nN {#1} #3 {#4} } { \tl_sort:nN {#2} #3 } }
  #3 {#4} {#5}
  { \__sort:nnNnn {#1} { #2 {#5} } #3 {#4} }
  { \__sort:nnNnn { #1 {#5} } {#2} #3 {#4} }
}
\cs_generate_variant:Nn \use:nn { ff }

```

There are quite a few optimizations available here: the code below is less legible, but more than twice as fast.

In the simple version of the code, __sort:nnNnn is called $O(n \ln n)$ times on average (the number of comparisons required by the quicksort algorithm). Hence most of our focus will be on optimizing that function.

The first speed up is to avoid testing for the end of the list at every call to __sort:nnNnn. For this, the list is prepared by changing each $\langle item \rangle$ of the original token list into $\langle command \rangle \{ \langle item \rangle \}$, just like sequences are stored. We arrange things such that the $\langle command \rangle$ is the $\langle conditional \rangle$ provided by the user: the loop over the $\langle prepared tokens \rangle$ then looks like

```

\cs_new:Npn \__sort_loop:wNn ... #6#7
{
  #6 {<pivot>} {#7} <loop big> <loop small>
  <extra arguments>
}
\__sort_loop:wNn ... <prepared tokens>
<end-loop> {} \q_stop

```

In this example, which matches the structure of `__sort_quick_split_i:NnnnnNn` and a few other functions below, the `__sort_loop:wNn` auxiliary normally receives the user's `<conditional>` as `#6` and an `<item>` as `#7`. This is compared to the `<pivot>` (the argument `#5`, not shown here), and the `<conditional>` leaves the `<loop big>` or `<loop small>` auxiliary, which both have the same form as `__sort_loop:wNn`, receiving the next pair `<conditional> {<item>}` as `#6` and `#7`. At the end, `#6` is the `<end-loop>` function, which terminates the loop.

The second speed up is to minimize the duplicated tokens between the `true` and `false` branches of the conditional. For this, we introduce two versions of `__sort:nnNnn`, which receive the new item as `#1` and place it either into the list `#2` of items less than the pivot `#4` or into the list `#3` of items greater or equal to the pivot.

```

\cs_new:Npn \__sort_i:nnnnNn #1#2#3#4#5#6
{
  #5 {#4} {#6} \__sort_ii:nnnnNn \__sort_i:nnnnNn
  {#6} { #2 {#1} } {#3} {#4}
}
\cs_new:Npn \__sort_ii:nnnnNn #1#2#3#4#5#6
{
  #5 {#4} {#6} \__sort_ii:nnnnNn \__sort_i:nnnnNn
  {#6} {#2} { #3 {#1} } {#4}
}

```

Note that the two functions have the form of `__sort_loop:wNn` above, receiving as `#5` the conditional or a function to end the loop. In fact, the lists `#2` and `#3` must be made of pairs `<conditional> {<item>}`, so we have to replace `{#6}` above by `{ #5 {#6} }`, and `{#1}` by `#1`. The actual functions have one more argument, so all argument numbers are shifted compared to this code.

The third speed up is to avoid `\use:ff` using a continuation-passing style: `__sort_quick_split:NnNn` expects a list followed by `\q_mark {<code>}`, and expands to `<code> <sorted list>`. Sorting the two parts of the list around the pivot is done with

```

\__sort_quick_split:NnNn #2 ... \q_mark
{
  \__sort_quick_split:NnNn #1 ... \q_mark {<code>}
  {<pivot>}
}

```

Items which are larger than the `<pivot>` are sorted, then placed after code that sorts the smaller items, and after the (braced) `<pivot>`.

The fourth speed up is avoid the recursive call to `\tl_sort:nN` with an empty first argument. For this, we introduce functions similar to the `__sort_i:nnnnNn` of the last example, but aware of whether the list of `<conditional> {<item>}` read so far that are less than the pivot, and the list of those greater or equal, are empty or not: see

`__sort_quick_split:NnNn` and functions defined below. Knowing whether the lists are empty or not is useless if we do not use distinct ending codes as appropriate. The splitting auxiliaries communicate to the `<end-loop>` function (that is initially placed after the “prepared” list) by placing a specific ending function, ignored when looping, but useful at the end. In fact, the `<end-loop>` function does nothing but place the appropriate ending function in front of all its arguments. The ending functions take care of sorting non-empty sublists, placing the pivot in between, and the continuation before.

The final change in fact slows down the code a little, but is required to avoid memory issues: schematically, when `TEX` encounters

```
\use:n { \use:n { \use:n { ... } ... } ... }
```

the argument of the first `\use:n` is not completely read by the second `\use:n`, hence must remain in memory; then the argument of the second `\use:n` is not completely read when grabbing the argument of the third `\use:n`, hence must remain in memory, and so on. The memory consumption grows quadratically with the number of nested `\use:n`. In practice, this means that we must read everything until a trailing `\q_stop` once in a while, otherwise sorting lists of more than a few thousand items would exhaust a typical `TEX`’s memory.

`\tl_sort:nN`

```
\__sort_quick_prepare:Nnnn
  \__sort_quick_prepare_end:NNNnw
  \__sort_quick_cleanup:w
```

The code within the `\exp_not:f` sorts the list, leaving in most cases a leading `\exp_not:f`, which stops the expansion, letting the result be return within `\exp_not:n`. We filter out the case of a list with no item, which would otherwise cause problems. Then prepare the token list #1 by inserting the conditional #2 before each item. The prepare auxiliary receives the conditional as #1, the prepared token list so far as #2, the next prepared item as #3, and the item after that as #4. The loop ends when #4 contains `__prg_break_point:`, then the `prepare_end` auxiliary finds the prepared token list as #4. The scene is then set up for `__sort_quick_split:NnNn`, which will sort the prepared list and perform the post action placed after `\q_mark`, namely removing the trailing `\s_stop` and `\q_stop` and leaving `\exp_stop_f:` to stop f-expansion.

```
16196 \cs_new:Npn \tl_sort:nN #1#2
16197 {
16198   \exp_not:f
16199   {
16200     \tl_if_blank:nF {#1}
16201     {
16202       \__sort_quick_prepare:Nnnn #2 { } { }
16203       #1
16204       { \__prg_break_point: \__sort_quick_prepare_end:NNNnw }
16205       \q_stop
16206     }
16207   }
16208 }
16209 \cs_new:Npn \__sort_quick_prepare:Nnnn #1#2#3#4
16210 {
16211   \__prg_break: #4 \__prg_break_point:
16212   \__sort_quick_prepare:Nnnn #1 { #2 #3 } { #1 {#4} }
16213 }
16214 \cs_new:Npn \__sort_quick_prepare_end:NNNnw #1#2#3#4#5 \q_stop
16215 {
16216   \__sort_quick_split:NnNn #4 \__sort_quick_end:nnTFNn { }
16217   \q_mark { \__sort_quick_cleanup:w \exp_stop_f: }
```

```

16218     \s__stop \q_stop
16219   }
16220 \cs_new:Npn \__sort_quick_cleanup:w #1 \s__stop \q_stop {#1}

```

(End definition for `\tl_sort:nN` and others. These functions are documented on page 43.)

```

\__sort_quick_split:NnNn
\__sort_quick_only_i:NnnnnNn
  \__sort_quick_only_ii:NnnnnNn
  \__sort_quick_split_i:NnnnnNn
  \__sort_quick_split_ii:NnnnnNn

```

The `only_i`, `only_ii`, `split_i` and `split_ii` auxiliaries receive a useless first argument, the new item #2 (that they append to either one of the next two arguments), the list #3 of items less than the pivot, bigger items #4, the pivot #5, a *function* #6, and an item #7. The *function* is the user's *conditional* except at the end of the list where it is `__sort_quick_end:nnTFNn`. The comparison is applied to the *pivot* and the *item*, and calls the `only_i` or `split_i` auxiliaries if the *item* is smaller, and the `only_ii` or `split_ii` auxiliaries otherwise. In both cases, the next auxiliary goes to work right away, with no intermediate expansion that would slow down operations. Note that the argument #2 left for the next call has the form *conditional* {*item*}, so that the lists #3 and #4 keep the right form to be fed to the next sorting function. The `split` auxiliary differs from these in that it is missing three of the arguments, which would be empty, and its first argument is always the user's *conditional* rather than an ending function.

```

16221 \cs_new:Npn \__sort_quick_split:NnNn #1#2#3#4
16222 {
16223   #3 {#2} {#4} \__sort_quick_only_ii:NnnnnNn \__sort_quick_only_i:NnnnnNn
16224   \__sort_quick_single_end:nnnwnw
16225   { #3 {#4} } { } { } {#2}
16226 }
16227 \cs_new:Npn \__sort_quick_only_i:NnnnnNn #1#2#3#4#5#6#7
16228 {
16229   #6 {#5} {#7} \__sort_quick_split_ii:NnnnnNn \__sort_quick_only_i:NnnnnNn
16230   \__sort_quick_only_i_end:nnnwnw
16231   { #6 {#7} } { #3 #2 } { } {#5}
16232 }
16233 \cs_new:Npn \__sort_quick_only_ii:NnnnnNn #1#2#3#4#5#6#7
16234 {
16235   #6 {#5} {#7} \__sort_quick_only_ii:NnnnnNn \__sort_quick_split_i:NnnnnNn
16236   \__sort_quick_only_ii_end:nnnwnw
16237   { #6 {#7} } { } { #4 #2 } {#5}
16238 }
16239 \cs_new:Npn \__sort_quick_split_i:NnnnnNn #1#2#3#4#5#6#7
16240 {
16241   #6 {#5} {#7} \__sort_quick_split_ii:NnnnnNn \__sort_quick_split_i:NnnnnNn
16242   \__sort_quick_split_end:nnnwnw
16243   { #6 {#7} } { #3 #2 } {#4} {#5}
16244 }
16245 \cs_new:Npn \__sort_quick_split_ii:NnnnnNn #1#2#3#4#5#6#7
16246 {
16247   #6 {#5} {#7} \__sort_quick_split_ii:NnnnnNn \__sort_quick_split_i:NnnnnNn
16248   \__sort_quick_split_end:nnnwnw
16249   { #6 {#7} } {#3} { #4 #2 } {#5}
16250 }

```

(End definition for `__sort_quick_split:NnNn` and others.)

```

\__sort_quick_end:nnTFNn
  \__sort_quick_single_end:nnnwnw
  \__sort_quick_only_i_end:nnnwnw
  \__sort_quick_only_ii_end:nnnwnw
  \__sort_quick_split_end:nnnwnw

```

The `__sort_quick_end:nnTFNn` appears instead of the user's conditional, and receives as its arguments the pivot #1, a fake item #2, a `true` and a `false` branches #3 and #4, followed by an ending function #5 (one of the four auxiliaries here) and another copy #6

of the fake item. All those are discarded except the function #5. This function receives lists #1 and #2 of items less than or greater than the pivot #3, then a continuation code #5 just after \q_mark. To avoid a memory problem described earlier, all of the ending functions read #6 until \q_stop and place #6 back into the input stream. When the lists #1 and #2 are empty, the single auxiliary simply places the continuation #5 before the pivot {#3}. When #2 is empty, #1 is sorted and placed before the pivot {#3}, taking care to feed the continuation #5 as a continuation for the function sorting #1. When #1 is empty, #2 is sorted, and the continuation argument is used to place the continuation #5 and the pivot {#3} before the sorted result. Finally, when both lists are non-empty, items larger than the pivot are sorted, then items less than the pivot, and the continuations are done in such a way to place the pivot in between.

```

16251 \cs_new:Npn \__sort_quick_end:nnTFNn #1#2#3#4#5#6 {#5}
16252 \cs_new:Npn \__sort_quick_single_end:nnnwnw #1#2#3#4 \q_mark #5#6 \q_stop
16253 { #5 {#3} #6 \q_stop }
16254 \cs_new:Npn \__sort_quick_only_i_end:nnnwnw #1#2#3#4 \q_mark #5#6 \q_stop
16255 {
16256   \__sort_quick_split:NnNn #1
16257   \__sort_quick_end:nnTFNn { } \q_mark {#5}
16258   {#3}
16259   #6 \q_stop
16260 }
16261 \cs_new:Npn \__sort_quick_only_ii_end:nnnwnw #1#2#3#4 \q_mark #5#6 \q_stop
16262 {
16263   \__sort_quick_split:NnNn #2
16264   \__sort_quick_end:nnTFNn { } \q_mark { #5 {#3} }
16265   #6 \q_stop
16266 }
16267 \cs_new:Npn \__sort_quick_split_end:nnnwnw #1#2#3#4 \q_mark #5#6 \q_stop
16268 {
16269   \__sort_quick_split:NnNn #2 \__sort_quick_end:nnTFNn { } \q_mark
16270   {
16271     \__sort_quick_split:NnNn #1
16272     \__sort_quick_end:nnTFNn { } \q_mark {#5}
16273     {#3}
16274   }
16275   #6 \q_stop
16276 }

```

(End definition for __sort_quick_end:nnTFNn and others.)

32.6 Messages

__sort_error: Bailing out of the sorting code is a bit tricky. It may not be safe to use a delimited argument, so instead we redefine many l3sort commands to be trivial, with __sort_level: getting rid of the final assignment. This error recovery won't work in a group.

```

16277 \cs_new_protected:Npn \__sort_error:
16278 {
16279   \cs_set_eq:NN \__sort_merge_blocks_aux: \prg_do_nothing:
16280   \cs_set_eq:NN \__sort_merge_blocks: \prg_do_nothing:
16281   \cs_set_protected:Npn \__sort_level: \use:x ##1 { \group_end: }
16282 }

```

(End definition for __sort_error:.)

`__sort_disable_toksdef:` While sorting, `\toksdef` is locally disabled to prevent users from using `\newtoks` or similar commands in their comparison code: the `\toks` registers that would be assigned are in use by `\l3sort`. In format mode, none of this is needed since there is no `\toks` allocator.

```

16283 \begin{package}
16284 \cs_new_protected:Npn \__sort_disable_toksdef:
16285   { \cs_set_eq:NN \toksdef \__sort_disabled_toksdef:n }
16286 \cs_new_protected:Npn \__sort_disabled_toksdef:n #1
16287   {
16288     \__msg_kernel_error:nnx { sort } { toksdef }
16289     { \token_to_str:N #1 }
16290     \__sort_error:
16291     \tex_toksdef:D #1
16292   }
16293 \__msg_kernel_new:nnnn { sort } { toksdef }
16294 { Allocation~of~\iow_char:N\toks~registers~impossible~while~sorting. }
16295 {
16296   The~comparison~code~used~for~sorting~a~list~has~attempted~to~
16297   define~#1~as~a~new~\iow_char:N\toks~register~using~\iow_char:N\newtoks~
16298   or~a~similar~command.~The~list~will~not~be~sorted.
16299 }
16300 \end{package}

```

(End definition for `__sort_disable_toksdef:` and `__sort_disabled_toksdef:n`.)

`__sort_too_long_error:NNw` When there are too many items in a sequence, this is an error, and we clean up properly the mapping over items in the list: break using the type-specific breaking function `#1`.

```

16301 \cs_new_protected:Npn \__sort_too_long_error:NNw #1#2 \fi:
16302   {
16303     \fi:
16304     \__msg_kernel_error:nnxxx { sort } { too-large }
16305     { \token_to_str:N #2 }
16306     { \int_eval:n { \l__sort_true_max_int - \l__sort_min_int } }
16307     { \int_eval:n { \l__sort_top_int - \l__sort_min_int } }
16308     #1 \__sort_error:
16309   }
16310 \__msg_kernel_new:nnnn { sort } { too-large }
16311 { The~list~#1~is~too~long~to~be~sorted~by~TeX. }
16312 {
16313   TeX~has~#2~toks~registers~still~available:~
16314   this~only~allows~to~sort~with~up~to~#3~
16315   items.~All~extra~items~will~be~deleted.
16316 }

```

(End definition for `__sort_too_long_error:NNw`.)

```

16317 \__msg_kernel_new:nnnn { sort } { return-none }
16318 { The~comparison~code~did~not~return. }
16319 {
16320   When~sorting~a~list,~the~code~to~compare~items~#1~and~#2~
16321   did~not~call~
16322   \iow_char:N\sort_return_same: ~nor~
16323   \iow_char:N\sort_return_swapped: .~
16324   Exactly~one~of~these~should~be~called.
16325 }

```



```

16326 \__msg_kernel_new:nnnn { sort } { return-two }
16327 { The~comparison~code~returned~multiple~times. }
16328 {
16329   When~sorting~a~list,~the~code~to~compare~items~called~
16330   \iow_char:N\\sort_return_same: ~or~
16331   \iow_char:N\\sort_return_swapped: ~multiple~times.~
16332   Exactly~one~of~these~should~be~called.
16333 }

```

32.7 Deprecated functions

\sort_ordered: These functions were renamed for consistency.

```

\sort_reversed:
16334 \cs_new_protected:Npn \sort_ordered:
16335 {
16336   \__msg_kernel_warning:nnxxx { kernel } { deprecated-command }
16337   { 2018-12-31 }
16338   { \token_to_str:N \sort_ordered: }
16339   { \token_to_str:N \sort_return_same: }
16340   \cs_gset_eq:NN \sort_ordered: \sort_return_same:
16341   \sort_return_same:
16342 }
16343 \cs_new_protected:Npn \sort_reversed:
16344 {
16345   \__msg_kernel_warning:nnxxx { kernel } { deprecated-command }
16346   { 2018-12-31 }
16347   { \token_to_str:N \sort_reversed: }
16348   { \token_to_str:N \sort_return_swapped: }
16349   \cs_gset_eq:NN \sort_reversed: \sort_return_swapped:
16350   \sort_return_swapped:
16351 }

```

(End definition for \sort_ordered: and \sort_reversed:.)

```

16352 </initex | package>

```

33 l3box implementation

```

16353 <*initex | package>

```

```

16354 <@@=box>

```

The code in this module is very straight forward so I'm not going to comment it very extensively.

33.1 Creating and initialising boxes

The following test files are used for this code: m3box001.lvt.

\box_new:N Defining a new $\langle box \rangle$ register: remember that box 255 is not generally available.

```

\box_new:c
16355 <*package>
16356 \cs_new_protected:Npn \box_new:N #1
16357 {
16358   \__chk_if_free_cs:N #1
16359   \cs:w newbox \cs_end: #1
16360 }

```

```

16361 \end{package}
16362 \cs_generate_variant:Nn \box_new:N { c }

```

Clear a $\langle box \rangle$ register.

```

16363 \cs_new_protected:Npn \box_clear:N #1
\box_clear:N { \box_set_eq:NN #1 \c_empty_box }
16364 \cs_new_protected:Npn \box_gclear:N #1
\box_gclear:N { \box_gset_eq:NN #1 \c_empty_box }
16365 \cs_generate_variant:Nn \box_clear:N { c }
16366 \cs_generate_variant:Nn \box_gclear:N { c }

```

Clear or new.

```

16369 \cs_new_protected:Npn \box_clear_new:N #1
\box_clear_new:N { \box_if_exist:NTF #1 { \box_clear:N #1 } { \box_new:N #1 } }
16370 \cs_new_protected:Npn \box_gclear_new:N #1
\box_gclear_new:N { \box_if_exist:NTF #1 { \box_gclear:N #1 } { \box_new:N #1 } }
16371 \cs_generate_variant:Nn \box_clear_new:N { c }
16372 \cs_generate_variant:Nn \box_gclear_new:N { c }

```

Assigning the contents of a box to be another box.

```

16375 \cs_new_protected:Npn \box_set_eq:NN #1#2
\box_set_eq:cN { \tex_setbox:D #1 \tex_copy:D #2 }
16376 \cs_new_protected:Npn \box_gset_eq:NN
\box_gset_eq:Nc { \tex_global:D \box_set_eq:NN }
16377 \cs_generate_variant:Nn \box_set_eq:NN { c , Nc , cc }
16378 \cs_generate_variant:Nn \box_gset_eq:NN { c , Nc , cc }

```

Assigning the contents of a box to be another box. This clears the second box globally (that's how $\text{T}_{\text{E}}\text{X}$ does it).

```

16381 \cs_new_protected:Npn \box_set_eq_clear:NN #1#2
\box_set_eq_clear:cN { \tex_setbox:D #1 \tex_box:D #2 }
16382 \cs_new_protected:Npn \box_gset_eq_clear:NN
\box_gset_eq_clear:Nc { \tex_global:D \box_set_eq_clear:NN }
16383 \cs_generate_variant:Nn \box_set_eq_clear:NN { c , Nc , cc }
16384 \cs_generate_variant:Nn \box_gset_eq_clear:NN { c , Nc , cc }

```

Copies of the cs functions defined in l3basics .

```

16387 \prg_new_eq_conditional:NNn \box_if_exist:N \cs_if_exist:N
\box_if_exist_p:N { TF , T , F , p }
16388 \prg_new_eq_conditional:NNn \box_if_exist:c \cs_if_exist:c
\box_if_exist:N $\underline{TF}$  { TF , T , F , p }
16389 \box_if_exist:c $\underline{TF}$ 

```

33.2 Measuring and setting box dimensions

Accessing the height, depth, and width of a $\langle box \rangle$ register.

```

16391 \cs_new_eq:NN \box_ht:N \tex_ht:D
\box_ht:c { \cs_new_eq:NN \box_dp:N \tex_dp:D }
16392 \cs_new_eq:NN \box_wd:N \tex_wd:D
\box_dp:N { \cs_generate_variant:Nn \box_ht:N { c } }
16393 \cs_generate_variant:Nn \box_dp:N { c }
\box_wd:N { \cs_generate_variant:Nn \box_wd:N { c } }
16394 \box_wd:c

```

Measuring is easy: all primitive work. These primitives are not expandable, so the derived functions are not either.

```

\box_set_ht:Nn 16397 \cs_new_protected:Npn \box_set_dp:Nn #1#2
\box_set_ht:cn 16398 { \box_dp:N #1 \__dim_eval:w #2 \__dim_eval_end: }
\box_set_dp:Nn 16399 \cs_new_protected:Npn \box_set_ht:Nn #1#2
\box_set_dp:cn 16400 { \box_ht:N #1 \__dim_eval:w #2 \__dim_eval_end: }
\box_set_wd:Nn 16401 \cs_new_protected:Npn \box_set_wd:Nn #1#2
\box_set_wd:cn 16402 { \box_wd:N #1 \__dim_eval:w #2 \__dim_eval_end: }
16403 \cs_generate_variant:Nn \box_set_ht:Nn { c }
16404 \cs_generate_variant:Nn \box_set_dp:Nn { c }
16405 \cs_generate_variant:Nn \box_set_wd:Nn { c }

```

33.3 Using boxes

Using a $\langle box \rangle$. These are just \TeX primitives with meaningful names.

```

\box_use_clear:Nn 16406 \cs_new_eq:NN \box_use_clear:N \tex_box:D
\box_use_clear:c 16407 \cs_new_eq:NN \box_use:N \tex_copy:D
\box_use:N 16408 \cs_generate_variant:Nn \box_use_clear:N { c }
\box_use:c 16409 \cs_generate_variant:Nn \box_use:N { c }

```

Move box material in different directions.

```

\box_move_left:nn 16410 \cs_new_protected:Npn \box_move_left:nn #1#2
\box_move_right:nn 16411 { \tex_moveleft:D \__dim_eval:w #1 \__dim_eval_end: #2 }
\box_move_up:nn 16412 \cs_new_protected:Npn \box_move_right:nn #1#2
\box_move_down:nn 16413 { \tex_moveright:D \__dim_eval:w #1 \__dim_eval_end: #2 }
16414 \cs_new_protected:Npn \box_move_up:nn #1#2
16415 { \tex_raise:D \__dim_eval:w #1 \__dim_eval_end: #2 }
16416 \cs_new_protected:Npn \box_move_down:nn #1#2
16417 { \tex_lower:D \__dim_eval:w #1 \__dim_eval_end: #2 }

```

33.4 Box conditionals

The primitives for testing if a $\langle box \rangle$ is empty/void or which type of box it is.

```

\if_hbox:N 16418 \cs_new_eq:NN \if_hbox:N \tex_ifhbox:D
\if_vbox:N 16419 \cs_new_eq:NN \if_vbox:N \tex_ifvbox:D
\if_box_empty:N 16420 \cs_new_eq:NN \if_box_empty:N \tex_ifvoid:D

\box_if_horizontal_p:N 16421 \prg_new_conditional:Npnn \box_if_horizontal:N #1 { p , T , F , TF }
\box_if_horizontal_p:c 16422 { \if_hbox:N #1 \prg_return_true: \else: \prg_return_false: \fi: }
\box_if_horizontal:N $\underline{TF}$  16423 \prg_new_conditional:Npnn \box_if_vertical:N #1 { p , T , F , TF }
\box_if_horizontal:c $\underline{TF}$  16424 { \if_vbox:N #1 \prg_return_true: \else: \prg_return_false: \fi: }
\box_if_vertical_p:N 16425 \cs_generate_variant:Nn \box_if_horizontal_p:N { c }
\box_if_vertical_p:c 16426 \cs_generate_variant:Nn \box_if_horizontal:NT { c }
\box_if_vertical:N $\underline{TF}$  16427 \cs_generate_variant:Nn \box_if_horizontal:NF { c }
\box_if_vertical:c $\underline{TF}$  16428 \cs_generate_variant:Nn \box_if_horizontal:NTF { c }
16429 \cs_generate_variant:Nn \box_if_vertical_p:N { c }
16430 \cs_generate_variant:Nn \box_if_vertical:NT { c }
16431 \cs_generate_variant:Nn \box_if_vertical:NF { c }
16432 \cs_generate_variant:Nn \box_if_vertical:NTF { c }

```

Testing if a $\langle box \rangle$ is empty/void.

```

16433 \prg_new_conditional:Npnn \box_if_empty:N #1 { p , T , F , TF }
\box_if_empty_p:N      { \if_box_empty:N #1 \prg_return_true: \else: \prg_return_false: \fi: }
16434
\box_if_empty_p:c      16435 \cs_generate_variant:Nn \box_if_empty_p:N { c }
\box_if_empty:N $\underline{TF}$  16436 \cs_generate_variant:Nn \box_if_empty:NT { c }
\box_if_empty:c $\underline{TF}$  16437 \cs_generate_variant:Nn \box_if_empty:NF { c }
16438 \cs_generate_variant:Nn \box_if_empty:NTF { c }

```

(End definition for $\backslash\text{box_new:N}$ and others. These functions are documented on page 192.)

33.5 The last box inserted

```

\box_set_to_last:N Set a box to the previous box.
\box_set_to_last:c 16439 \cs_new_protected:Npn \box_set_to_last:N #1
\box_gset_to_last:N 16440 { \tex_setbox:D #1 \tex_lastbox:D }
\box_gset_to_last:c 16441 \cs_new_protected:Npn \box_gset_to_last:N
16442 { \tex_global:D \box_set_to_last:N }
16443 \cs_generate_variant:Nn \box_set_to_last:N { c }
16444 \cs_generate_variant:Nn \box_gset_to_last:N { c }

```

(End definition for $\backslash\text{box_set_to_last:N}$ and $\backslash\text{box_gset_to_last:N}$. These functions are documented on page 194.)

33.6 Constant boxes

```

\c_empty_box A box we never use.
16445 \box_new:N \c_empty_box

```

(End definition for $\backslash\text{c_empty_box}$. This variable is documented on page 195.)

33.7 Scratch boxes

```

\l_tmpa_box Scratch boxes.
\l_tmpb_box 16446 \box_new:N \l_tmpa_box
\g_tmpa_box 16447 \box_new:N \l_tmpb_box
\g_tmpb_box 16448 \box_new:N \g_tmpa_box
16449 \box_new:N \g_tmpb_box

```

(End definition for $\backslash\text{l_tmpa_box}$ and others. These variables are documented on page 195.)

33.8 Viewing box contents

TeX's $\backslash\text{showbox}$ is not really that helpful in many cases, and it is also inconsistent with other L^AT_EX3 show functions as it does not actually shows material in the terminal. So we provide a richer set of functionality.

```

\box_show:N Essentially a wrapper around the internal function, but evaluating the breadth and depth
\box_show:c arguments now outside the group.
\box_show:Nnn 16450 \cs_new_protected:Npn \box_show:N #1
\box_show:cnn 16451 { \box_show:Nnn #1 \c_max_int \c_max_int }
16452 \cs_generate_variant:Nn \box_show:N { c }
16453 \cs_new_protected:Npn \box_show:Nnn #1#2#3
16454 { \__box_show:NNff 1 #1 { \int_eval:n {#2} } { \int_eval:n {#3} } }
16455 \cs_generate_variant:Nn \box_show:Nnn { c }

```

(End definition for `\box_show:N` and `\box_show:Nnn`. These functions are documented on page 195.)

```

\box_log:N Getting TEX to write to the log without interruption the run is done by altering the
\box_log:c interaction mode. For that, the  $\varepsilon$ -TEX extensions are needed.
\box_log:Nnn
\box_log:cnn
\__box_log:nNnn
16456 \cs_new_protected:Npn \box_log:N #1
16457 { \box_log:Nnn #1 \c_max_int \c_max_int }
16458 \cs_generate_variant:Nn \box_log:N { c }
16459 \cs_new_protected:Npn \box_log:Nnn
16460 { \exp_args:No \__box_log:nNnn { \tex_the:D \etex_interactionmode:D } }
16461 \cs_new_protected:Npn \__box_log:nNnn #1#2#3#4
16462 {
16463   \int_set:Nn \etex_interactionmode:D { 0 }
16464   \__box_show:NNff 0 #2 { \int_eval:n {#3} } { \int_eval:n {#4} }
16465   \int_set:Nn \etex_interactionmode:D {#1}
16466 }
16467 \cs_generate_variant:Nn \box_log:Nnn { c }

```

(End definition for `\box_log:N`, `\box_log:Nnn`, and `__box_log:nNnn`. These functions are documented on page 195.)

`__box_show:NNnn` The internal auxiliary to actually do the output uses a group to deal with breadth and
`__box_show:NNff` depth values. The `\use:n` here gives better output appearance. Setting `\tracingonline` and `\errorcontextlines` is used to control what appears in the terminal.

```

16468 \cs_new_protected:Npn \__box_show:NNnn #1#2#3#4
16469 {
16470   \box_if_exist:NTF #2
16471   {
16472     \group_begin:
16473     \int_set:Nn \tex_showboxbreadth:D {#3}
16474     \int_set:Nn \tex_showboxdepth:D {#4}
16475     \int_set:Nn \tex_tracingonline:D {#1}
16476     \int_set:Nn \tex_errorcontextlines:D { -1 }
16477     \tex_showbox:D \use:n {#2}
16478   \group_end:
16479   }
16480   {
16481     \_msg_kernel_error:nxx { kernel } { variable-not-defined }
16482     { \token_to_str:N #2 }
16483   }
16484 }
16485 \cs_generate_variant:Nn \__box_show:NNnn { NNff }

```

(End definition for `__box_show:NNnn`.)

33.9 Horizontal mode boxes

\hbox:n (The test suite for this command, and others in this file, is `m3box002.lvt`.)
 Put a horizontal box directly into the input stream.

```

16486 \cs_new_protected:Npn \hbox:n #1 { \tex_hbox:D \scan_stop: {#1} }

```

(End definition for `\hbox:n`. This function is documented on page 195.)

\hbox_set:Nn

\hbox_set:cn

\hbox_gset:Nn

\hbox_gset:cn

```
16487 \cs_new_protected:Npn \hbox_set:Nn #1#2
16488 { \tex_setbox:D #1 \tex_hbox:D {#2} }
16489 \cs_new_protected:Npn \hbox_gset:Nn { \tex_global:D \hbox_set:Nn }
16490 \cs_generate_variant:Nn \hbox_set:Nn { c }
16491 \cs_generate_variant:Nn \hbox_gset:Nn { c }
```

(End definition for `\hbox_set:Nn` and `\hbox_gset:Nn`. These functions are documented on page 196.)

\hbox_set_to_wd:Nnn

Storing material in a horizontal box with a specified width.

\hbox_set_to_wd:cnn

\hbox_gset_to_wd:Nnn

\hbox_gset_to_wd:cnn

```
16492 \cs_new_protected:Npn \hbox_set_to_wd:Nnn #1#2#3
16493 { \tex_setbox:D #1 \tex_hbox:D to \__dim_eval:w #2 \__dim_eval_end: {#3} }
16494 \cs_new_protected:Npn \hbox_gset_to_wd:Nnn
16495 { \tex_global:D \hbox_set_to_wd:Nnn }
16496 \cs_generate_variant:Nn \hbox_set_to_wd:Nnn { c }
16497 \cs_generate_variant:Nn \hbox_gset_to_wd:Nnn { c }
```

(End definition for `\hbox_set_to_wd:Nnn` and `\hbox_gset_to_wd:Nnn`. These functions are documented on page 196.)

\hbox_set:Nw

Storing material in a horizontal box. This type is useful in environment definitions.

\hbox_set:cw

\hbox_gset:Nw

\hbox_gset:cw

\hbox_set_end:

\hbox_gset_end:

```
16498 \cs_new_protected:Npn \hbox_set:Nw #1
16499 { \tex_setbox:D #1 \tex_hbox:D \c_group_begin_token }
16500 \cs_new_protected:Npn \hbox_gset:Nw
16501 { \tex_global:D \hbox_set:Nw }
16502 \cs_generate_variant:Nn \hbox_set:Nw { c }
16503 \cs_generate_variant:Nn \hbox_gset:Nw { c }
16504 \cs_new_eq:NN \hbox_set_end: \c_group_end_token
16505 \cs_new_eq:NN \hbox_gset_end: \c_group_end_token
```

(End definition for `\hbox_set:Nw` and others. These functions are documented on page 196.)

\hbox_to_wd:nn

Put a horizontal box directly into the input stream.

\hbox_to_zero:n

```
16506 \cs_new_protected:Npn \hbox_to_wd:nn #1#2
16507 { \tex_hbox:D to \__dim_eval:w #1 \__dim_eval_end: {#2} }
16508 \cs_new_protected:Npn \hbox_to_zero:n #1 { \tex_hbox:D to \c_zero_dim {#1} }
```

(End definition for `\hbox_to_wd:nn` and `\hbox_to_zero:n`. These functions are documented on page 196.)

\hbox_overlap_left:n

\hbox_overlap_right:n

Put a zero-sized box with the contents pushed against one side (which makes it stick out on the other) directly into the input stream.

```
16509 \cs_new_protected:Npn \hbox_overlap_left:n #1
16510 { \hbox_to_zero:n { \tex_hss:D #1 } }
16511 \cs_new_protected:Npn \hbox_overlap_right:n #1
16512 { \hbox_to_zero:n { #1 \tex_hss:D } }
```

(End definition for `\hbox_overlap_left:n` and `\hbox_overlap_right:n`. These functions are documented on page 196.)

\hbox_unpack:N

Unpacking a box and if requested also clear it.

\hbox_unpack:c

\hbox_unpack_clear:N

\hbox_unpack_clear:c

```
16513 \cs_new_eq:NN \hbox_unpack:N \tex_unhcopy:D
16514 \cs_new_eq:NN \hbox_unpack_clear:N \tex_unhbox:D
16515 \cs_generate_variant:Nn \hbox_unpack:N { c }
16516 \cs_generate_variant:Nn \hbox_unpack_clear:N { c }
```

(End definition for `\hbox_unpack:N` and `\hbox_unpack_clear:N`. These functions are documented on page 196.)

33.10 Vertical mode boxes

TeX ends these boxes directly with the internal *end_graf* routine. This means that there is no `\par` at the end of vertical boxes unless we insert one.

`\vbox:n` *The following test files are used for this code: m3box003.lvt.*

The following test files are used for this code: m3box003.lvt.

`\vbox_top:n` Put a vertical box directly into the input stream.

```
16517 \cs_new_protected:Npn \vbox:n #1 { \tex_vbox:D { #1 \par } }
16518 \cs_new_protected:Npn \vbox_top:n #1 { \tex_vtop:D { #1 \par } }
```

(End definition for `\vbox:n` and `\vbox_top:n`. These functions are documented on page 197.)

`\vbox_to_ht:nn` Put a vertical box directly into the input stream.

```
\vbox_to_zero:n 16519 \cs_new_protected:Npn \vbox_to_ht:nn #1#2
\vbox_to_ht:nn 16520 { \tex_vbox:D to \__dim_eval:w #1 \__dim_eval_end: { #2 \par } }
\vbox_to_zero:n 16521 \cs_new_protected:Npn \vbox_to_zero:n #1
\vbox_to_zero:n 16522 { \tex_vbox:D to \c_zero_dim { #1 \par } }
```

(End definition for `\vbox_to_ht:nn` and others. These functions are documented on page 197.)

`\vbox_set:Nn` Storing material in a vertical box with a natural height.

```
\vbox_set:cn 16523 \cs_new_protected:Npn \vbox_set:Nn #1#2
\vbox_gset:Nn 16524 { \tex_setbox:D #1 \tex_vbox:D { #2 \par } }
\vbox_gset:cn 16525 \cs_new_protected:Npn \vbox_gset:Nn { \tex_global:D \vbox_set:Nn }
16526 \cs_generate_variant:Nn \vbox_set:Nn { c }
16527 \cs_generate_variant:Nn \vbox_gset:Nn { c }
```

(End definition for `\vbox_set:Nn` and `\vbox_gset:Nn`. These functions are documented on page 197.)

`\vbox_set_top:Nn` Storing material in a vertical box with a natural height and reference point at the baseline
`\vbox_set_top:cn` of the first object in the box.

```
\vbox_gset_top:Nn 16528 \cs_new_protected:Npn \vbox_set_top:Nn #1#2
\vbox_gset_top:cn 16529 { \tex_setbox:D #1 \tex_vtop:D { #2 \par } }
16530 \cs_new_protected:Npn \vbox_gset_top:Nn
16531 { \tex_global:D \vbox_set_top:Nn }
16532 \cs_generate_variant:Nn \vbox_set_top:Nn { c }
16533 \cs_generate_variant:Nn \vbox_gset_top:Nn { c }
```

(End definition for `\vbox_set_top:Nn` and `\vbox_gset_top:Nn`. These functions are documented on page 197.)

`\vbox_set_to_ht:Nnn` Storing material in a vertical box with a specified height.

```
\vbox_set_to_ht:cnn 16534 \cs_new_protected:Npn \vbox_set_to_ht:Nnn #1#2#3
\vbox_gset_to_ht:Nnn 16535 {
\vbox_gset_to_ht:cnn 16536 \tex_setbox:D #1 \tex_vbox:D to \__dim_eval:w #2 \__dim_eval_end:
16537 { #3 \par }
16538 }
16539 \cs_new_protected:Npn \vbox_gset_to_ht:Nnn
16540 { \tex_global:D \vbox_set_to_ht:Nnn }
16541 \cs_generate_variant:Nn \vbox_set_to_ht:Nnn { c }
16542 \cs_generate_variant:Nn \vbox_gset_to_ht:Nnn { c }
```

(End definition for `\vbox_set_to_ht:Nnn` and `\vbox_gset_to_ht:Nnn`. These functions are documented on page 197.)

\vbox_set:Nw Storing material in a vertical box. This type is useful in environment definitions.

```

\vbox_set:cw 16543 \cs_new_protected:Npn \vbox_set:Nw #1
\vbox_gset:Nw 16544 { \tex_setbox:D #1 \tex_vbox:D \c_group_begin_token }
\vbox_gset:cw 16545 \cs_new_protected:Npn \vbox_gset:Nw
\vbox_set_end: 16546 { \tex_global:D \vbox_set:Nw }
\vbox_gset_end: 16547 \cs_generate_variant:Nn \vbox_set:Nw { c }
16548 \cs_generate_variant:Nn \vbox_gset:Nw { c }
16549 \cs_new_protected:Npn \vbox_set_end:
16550 {
16551   \par
16552   \c_group_end_token
16553 }
16554 \cs_new_eq:NN \vbox_gset_end: \vbox_set_end:

```

(End definition for `\vbox_set:Nw` and others. These functions are documented on page 198.)

\vbox_unpack:N Unpacking a box and if requested also clear it.

```

\vbox_unpack:c 16555 \cs_new_eq:NN \vbox_unpack:N \tex_unvcopy:D
\vbox_unpack_clear:N 16556 \cs_new_eq:NN \vbox_unpack_clear:N \tex_unvbox:D
\vbox_unpack_clear:c 16557 \cs_generate_variant:Nn \vbox_unpack:N { c }
16558 \cs_generate_variant:Nn \vbox_unpack_clear:N { c }

```

(End definition for `\vbox_unpack:N` and `\vbox_unpack_clear:N`. These functions are documented on page 198.)

\vbox_set_split_to_ht:NNn Splitting a vertical box in two.

```

16559 \cs_new_protected:Npn \vbox_set_split_to_ht:NNn #1#2#3
16560 { \tex_setbox:D #1 \tex_vsplit:D #2 to \__dim_eval:w #3 \__dim_eval_end: }

```

(End definition for `\vbox_set_split_to_ht:NNn`. This function is documented on page 198.)

```

16561 \</initex | package>

```

34 l3coffins Implementation

```

16562 \<*initex | package>
16563 \<@@=coffin>

```

34.1 Coffins: data structures and general variables

\l__coffin_internal_box Scratch variables.

```

\vbox_unpack_clear:c 16564 \box_new:N \l__coffin_internal_box
\vbox_unpack_clear:c 16565 \dim_new:N \l__coffin_internal_dim
\vbox_unpack_clear:c 16566 \tl_new:N \l__coffin_internal_tl

```

(End definition for `\l__coffin_internal_box`, `\l__coffin_internal_dim`, and `\l__coffin_internal_tl`.)

\c__coffin_corners_prop The “corners”; of a coffin define the real content, as opposed to the \TeX bounding box. They all start off in the same place, of course.

```

16567 \prop_new:N \c__coffin_corners_prop
16568 \prop_put:Nnn \c__coffin_corners_prop { tl } { { 0 pt } { 0 pt } }
16569 \prop_put:Nnn \c__coffin_corners_prop { tr } { { 0 pt } { 0 pt } }
16570 \prop_put:Nnn \c__coffin_corners_prop { bl } { { 0 pt } { 0 pt } }
16571 \prop_put:Nnn \c__coffin_corners_prop { br } { { 0 pt } { 0 pt } }

```


(End definition for \c__coffin_corners_prop.)

\c__coffin_poles_prop Pole positions are given for horizontal, vertical and reference-point based values.

```

16572 \prop_new:N \c__coffin_poles_prop
16573 \tl_set:Nn \l__coffin_internal_tl { { 0 pt } { 0 pt } { 0 pt } { 1000 pt } }
16574 \prop_put:Nno \c__coffin_poles_prop { l } { \l__coffin_internal_tl }
16575 \prop_put:Nno \c__coffin_poles_prop { hc } { \l__coffin_internal_tl }
16576 \prop_put:Nno \c__coffin_poles_prop { r } { \l__coffin_internal_tl }
16577 \tl_set:Nn \l__coffin_internal_tl { { 0 pt } { 0 pt } { 1000 pt } { 0 pt } }
16578 \prop_put:Nno \c__coffin_poles_prop { b } { \l__coffin_internal_tl }
16579 \prop_put:Nno \c__coffin_poles_prop { vc } { \l__coffin_internal_tl }
16580 \prop_put:Nno \c__coffin_poles_prop { t } { \l__coffin_internal_tl }
16581 \prop_put:Nno \c__coffin_poles_prop { B } { \l__coffin_internal_tl }
16582 \prop_put:Nno \c__coffin_poles_prop { H } { \l__coffin_internal_tl }
16583 \prop_put:Nno \c__coffin_poles_prop { T } { \l__coffin_internal_tl }

```

(End definition for \c__coffin_poles_prop.)

\l__coffin_slope_x_fp Used for calculations of intersections.

```

\l__coffin_slope_y_fp
16584 \fp_new:N \l__coffin_slope_x_fp
16585 \fp_new:N \l__coffin_slope_y_fp

```

(End definition for \l__coffin_slope_x_fp and \l__coffin_slope_y_fp.)

\l__coffin_error_bool For propagating errors so that parts of the code can work around them.

```

16586 \bool_new:N \l__coffin_error_bool

```

(End definition for \l__coffin_error_bool.)

\l__coffin_offset_x_dim The offset between two sets of coffin handles when typesetting. These values are corrected from those requested in an alignment for the positions of the handles.

```

16587 \dim_new:N \l__coffin_offset_x_dim
16588 \dim_new:N \l__coffin_offset_y_dim

```

(End definition for \l__coffin_offset_x_dim and \l__coffin_offset_y_dim.)

\l__coffin_pole_a_tl Needed for finding the intersection of two poles.

```

\l__coffin_pole_b_tl
16589 \tl_new:N \l__coffin_pole_a_tl
16590 \tl_new:N \l__coffin_pole_b_tl

```

(End definition for \l__coffin_pole_a_tl and \l__coffin_pole_b_tl.)

\l__coffin_x_dim For calculating intersections and so forth.

```

\l__coffin_y_dim
16591 \dim_new:N \l__coffin_x_dim
16592 \dim_new:N \l__coffin_y_dim
\l__coffin_x_prime_dim
16593 \dim_new:N \l__coffin_x_prime_dim
\l__coffin_y_prime_dim
16594 \dim_new:N \l__coffin_y_prime_dim

```

(End definition for \l__coffin_x_dim and others.)

34.2 Basic coffin functions

There are a number of basic functions needed for creating coffins and placing material in them. This all relies on the following data structures.

\coffin_if_exist_p:N Several of the higher-level coffin functions will give multiple errors if the coffin does not exist. A cleaner way to handle this is provided here: both the box and the coffin structure

\coffin_if_exist_p:c are checked.

\coffin_if_exist:N \underline{TF}

\coffin_if_exist:c \underline{TF}

```
16595 \prg_new_conditional:Npnn \coffin_if_exist:N #1 { p , T , F , TF }
16596 {
16597   \cs_if_exist:NTF #1
16598   {
16599     \cs_if_exist:cTF { l__coffin_poles_ \__int_value:w #1 _prop }
16600     { \prg_return_true: }
16601     { \prg_return_false: }
16602   }
16603   { \prg_return_false: }
16604 }
16605 \cs_generate_variant:Nn \coffin_if_exist_p:N { c }
16606 \cs_generate_variant:Nn \coffin_if_exist:NT { c }
16607 \cs_generate_variant:Nn \coffin_if_exist:NF { c }
16608 \cs_generate_variant:Nn \coffin_if_exist:N $\underline{TF}$  { c }
```

(End definition for \coffin_if_exist:N \underline{TF} . This function is documented on page 200.)

__coffin_if_exist:NT Several of the higher-level coffin functions will give multiple errors if the coffin does not exist. So a wrapper is provided to deal with this correctly, issuing an error on erroneous use.

```
16609 \cs_new_protected:Npn \__coffin_if_exist:NT #1#2
16610 {
16611   \coffin_if_exist:N $\underline{TF}$  #1
16612   { #2 }
16613   {
16614     \__msg_kernel_error:nnx { kernel } { unknown-coffin }
16615     { \token_to_str:N #1 }
16616   }
16617 }
```

(End definition for __coffin_if_exist:NT.)

\coffin_clear:N Clearing coffins means emptying the box and resetting all of the structures.

\coffin_clear:c

```
16618 \cs_new_protected:Npn \coffin_clear:N #1
16619 {
16620   \__coffin_if_exist:NT #1
16621   {
16622     \box_clear:N #1
16623     \__coffin_reset_structure:N #1
16624   }
16625 }
16626 \cs_generate_variant:Nn \coffin_clear:N { c }
```

(End definition for \coffin_clear:N. This function is documented on page 200.)

\coffin_new:N Creating a new coffin means making the underlying box and adding the data structures.
\coffin_new:c These are created globally, as there is a need to avoid any strange effects if the coffin is created inside a group. This means that the usual rule about \l_... variables has to be broken.

```

16627 \cs_new_protected:Npn \coffin_new:N #1
16628 {
16629   \box_new:N #1
16630   \__chk_suspend_log:
16631   \prop_clear_new:c { l__coffin_corners_ \__int_value:w #1 _prop }
16632   \prop_clear_new:c { l__coffin_poles_ \__int_value:w #1 _prop }
16633   \prop_gset_eq:cN { l__coffin_corners_ \__int_value:w #1 _prop }
16634     \c__coffin_corners_prop
16635   \prop_gset_eq:cN { l__coffin_poles_ \__int_value:w #1 _prop }
16636     \c__coffin_poles_prop
16637   \__chk_resume_log:
16638 }
16639 \cs_generate_variant:Nn \coffin_new:N { c }

```

(End definition for \coffin_new:N. This function is documented on page 200.)

\hcoffin_set:Nn Horizontal coffins are relatively easy: set the appropriate box, reset the structures then
\hcoffin_set:cn update the handle positions.

```

16640 \cs_new_protected:Npn \hcoffin_set:Nn #1#2
16641 {
16642   \__coffin_if_exist:NT #1
16643   {
16644     \hbox_set:Nn #1
16645     {
16646       \color_group_begin:
16647       \color_ensure_current:
16648       #2
16649       \color_group_end:
16650     }
16651     \__coffin_reset_structure:N #1
16652     \__coffin_update_poles:N #1
16653     \__coffin_update_corners:N #1
16654   }
16655 }
16656 \cs_generate_variant:Nn \hcoffin_set:Nn { c }

```

(End definition for \hcoffin_set:Nn. This function is documented on page 200.)

\vcoffin_set:Nnn Setting vertical coffins is more complex. First, the material is typeset with a given width.
\vcoffin_set:cnn The default handles and poles are set as for a horizontal coffin, before finding the top baseline using a temporary box. No \color_ensure_current: here as that would add a whatsit to the start of the vertical box and mess up the location of the T pole (see *T_{EX} by Topic* for discussion of the \vtop primitive, used to do the measuring).

```

16657 \cs_new_protected:Npn \vcoffin_set:Nnn #1#2#3
16658 {
16659   \__coffin_if_exist:NT #1
16660   {
16661     \vbox_set:Nn #1
16662     {
16663       \dim_set:Nn \tex_hsize:D {#2}

```

```

16664 \*package>
16665         \dim_set_eq:NN \linewidth \tex_hsize:D
16666         \dim_set_eq:NN \columnwidth \tex_hsize:D
16667 </package>
16668         \color_group_begin:
16669             #3
16670         \color_group_end:
16671     }
16672     \__coffin_reset_structure:N #1
16673     \__coffin_update_poles:N #1
16674     \__coffin_update_corners:N #1
16675     \vbox_set_top:Nn \l__coffin_internal_box { \vbox_unpack:N #1 }
16676     \__coffin_set_pole:Nnx #1 { T }
16677     {
16678         { 0 pt }
16679         {
16680             \dim_eval:n
16681             { \box_ht:N #1 - \box_ht:N \l__coffin_internal_box }
16682         }
16683         { 1000 pt }
16684         { 0 pt }
16685     }
16686     \box_clear:N \l__coffin_internal_box
16687 }
16688 }
16689 \cs_generate_variant:Nn \vcoffin_set:Nnn { c }

```

(End definition for \vcoffin_set:Nnn. This function is documented on page 201.)

\hcoffin_set:Nw
\hcoffin_set:cw
\hcoffin_set_end:

These are the “begin”/“end” versions of the above: watch the grouping!

```

16690 \cs_new_protected:Npn \hcoffin_set:Nw #1
16691 {
16692     \__coffin_if_exist:NT #1
16693     {
16694         \hbox_set:Nw #1 \color_group_begin: \color_ensure_current:
16695         \cs_set_protected:Npn \hcoffin_set_end:
16696         {
16697             \color_group_end:
16698             \hbox_set_end:
16699             \__coffin_reset_structure:N #1
16700             \__coffin_update_poles:N #1
16701             \__coffin_update_corners:N #1
16702         }
16703     }
16704 }
16705 \cs_new_protected:Npn \hcoffin_set_end: { }
16706 \cs_generate_variant:Nn \hcoffin_set:Nw { c }

```

(End definition for \hcoffin_set:Nw and \hcoffin_set_end:. These functions are documented on page 200.)

\vcoffin_set:Nnw
\vcoffin_set:cnw
\vcoffin_set_end:

The same for vertical coffins.

```

16707 \cs_new_protected:Npn \vcoffin_set:Nnw #1#2
16708 {
16709     \__coffin_if_exist:NT #1

```

```

16710     {
16711         \vbox_set:Nw #1
16712         \dim_set:Nn \tex_hsize:D {#2}
16713     }*package>
16714         \dim_set_eq:NN \linewidth \tex_hsize:D
16715         \dim_set_eq:NN \columnwidth \tex_hsize:D
16716 </package>
16717     \color_group_begin:
16718     \cs_set_protected:Npn \vcoffin_set_end:
16719     {
16720         \color_group_end:
16721         \vbox_set_end:
16722         \__coffin_reset_structure:N #1
16723         \__coffin_update_poles:N #1
16724         \__coffin_update_corners:N #1
16725         \vbox_set_top:Nn \l__coffin_internal_box { \vbox_unpack:N #1 }
16726         \__coffin_set_pole:Nnx #1 { T }
16727         {
16728             { 0 pt }
16729             {
16730                 \dim_eval:n
16731                 { \box_ht:N #1 - \box_ht:N \l__coffin_internal_box }
16732             }
16733             { 1000 pt }
16734             { 0 pt }
16735         }
16736         \box_clear:N \l__coffin_internal_box
16737     }
16738 }
16739 }
16740 \cs_new_protected:Npn \vcoffin_set_end: { }
16741 \cs_generate_variant:Nn \vcoffin_set:Nnw { c }

```

(End definition for `\vcoffin_set:Nnw` and `\vcoffin_set_end:`. These functions are documented on page 201.)

`\coffin_set_eq:NN` Setting two coffins equal is just a wrapper around other functions.

```

\coffin_set_eq:Nc 16742 \cs_new_protected:Npn \coffin_set_eq:NN #1#2
\coffin_set_eq:cN 16743 {
\coffin_set_eq:cc 16744     \__coffin_if_exist:NT #1
16745     {
16746         \box_set_eq:NN #1 #2
16747         \__coffin_set_eq_structure:NN #1 #2
16748     }
16749 }
16750 \cs_generate_variant:Nn \coffin_set_eq:NN { c , Nc , cc }

```

(End definition for `\coffin_set_eq:NN`. This function is documented on page 200.)

`\c_empty_coffin` Special coffins: these cannot be set up earlier as they need `\coffin_new:N`. The empty coffin is set as a box as the full coffin-setting system needs some material which is not yet available.

```

\l__coffin_aligned_coffin
\l__coffin_aligned_internal_coffin
16751 \coffin_new:N \c_empty_coffin
16752 \hbox_set:Nn \c_empty_coffin { }

```

```

16753 \coffin_new:N \l__coffin_aligned_coffin
16754 \coffin_new:N \l__coffin_aligned_internal_coffin

```

(End definition for `\c_empty_coffin`, `\l__coffin_aligned_coffin`, and `\l__coffin_aligned_internal_coffin`. These variables are documented on page 203.)

`\l_tmpa_coffin` The usual scratch space.

```

\l_tmpb_coffin 16755 \coffin_new:N \l_tmpa_coffin
16756 \coffin_new:N \l_tmpb_coffin

```

(End definition for `\l_tmpa_coffin` and `\l_tmpb_coffin`. These variables are documented on page 203.)

34.3 Measuring coffins

`\coffin_dp:N` Coffins are just boxes when it comes to measurement. However, semantically a separate set of functions are required.

```

\coffin_dp:c 16757 \cs_new_eq:NN \coffin_dp:N \box_dp:N
\coffin_ht:N 16758 \cs_new_eq:NN \coffin_dp:c \box_dp:c
\coffin_ht:c 16759 \cs_new_eq:NN \coffin_ht:N \box_ht:N
\coffin_wd:N 16760 \cs_new_eq:NN \coffin_ht:c \box_ht:c
\coffin_wd:c 16761 \cs_new_eq:NN \coffin_wd:N \box_wd:N
16762 \cs_new_eq:NN \coffin_wd:c \box_wd:c

```

(End definition for `\coffin_dp:N`, `\coffin_ht:N`, and `\coffin_wd:N`. These functions are documented on page 202.)

34.4 Coffins: handle and pole management

`__coffin_get_pole:NnN` A simple wrapper around the recovery of a coffin pole, with some error checking and recovery built-in.

```

16763 \cs_new_protected:Npn \__coffin_get_pole:NnN #1#2#3
16764 {
16765   \prop_get:cnNF
16766     { l__coffin_poles_ \__int_value:w #1 _prop } {#2} #3
16767   {
16768     \_msg_kernel_error:nxx { kernel } { unknown-coffin-pole }
16769     {#2} { \token_to_str:N #1 }
16770     \tl_set:Nn #3 { { 0 pt } { 0 pt } { 0 pt } { 0 pt } }
16771   }
16772 }

```

(End definition for `__coffin_get_pole:NnN`.)

`__coffin_reset_structure:N` Resetting the structure is a simple copy job.

```

16773 \cs_new_protected:Npn \__coffin_reset_structure:N #1
16774 {
16775   \prop_set_eq:cN { l__coffin_corners_ \__int_value:w #1 _prop }
16776   \c__coffin_corners_prop
16777   \prop_set_eq:cN { l__coffin_poles_ \__int_value:w #1 _prop }
16778   \c__coffin_poles_prop
16779 }

```

(End definition for `__coffin_reset_structure:N`.)

`_coffin_set_eq_structure:NN` Setting coffin structures equal simply means copying the property list.

```

\coffin_gset_eq_structure:NN
16780 \cs_new_protected:Npn \_coffin_set_eq_structure:NN #1#2
16781 {
16782   \prop_set_eq:cc { l__coffin_corners_ \_int_value:w #1 _prop }
16783   { l__coffin_corners_ \_int_value:w #2 _prop }
16784   \prop_set_eq:cc { l__coffin_poles_ \_int_value:w #1 _prop }
16785   { l__coffin_poles_ \_int_value:w #2 _prop }
16786 }
16787 \cs_new_protected:Npn \_coffin_gset_eq_structure:NN #1#2
16788 {
16789   \prop_gset_eq:cc { l__coffin_corners_ \_int_value:w #1 _prop }
16790   { l__coffin_corners_ \_int_value:w #2 _prop }
16791   \prop_gset_eq:cc { l__coffin_poles_ \_int_value:w #1 _prop }
16792   { l__coffin_poles_ \_int_value:w #2 _prop }
16793 }

```

(End definition for `_coffin_set_eq_structure:NN` and `_coffin_gset_eq_structure:NN`.)

`\coffin_set_horizontal_pole:Nnn` Setting the pole of a coffin at the user/designer level requires a bit more care. The idea here is to provide a reasonable interface to the system, then to do the setting with full expansion. The three-argument version is used internally to do a direct setting.

`\coffin_set_vertical_pole:Nnn`

`\coffin_set_vertical_pole:cnn`

`_coffin_set_pole:Nnn`

`_coffin_set_pole:Nnx`

```

16794 \cs_new_protected:Npn \coffin_set_horizontal_pole:Nnn #1#2#3
16795 {
16796   \_coffin_if_exist:NT #1
16797   {
16798     \_coffin_set_pole:Nnx #1 {#2}
16799     {
16800       { 0 pt } { \dim_eval:n {#3} }
16801       { 1000 pt } { 0 pt }
16802     }
16803   }
16804 }
16805 \cs_new_protected:Npn \coffin_set_vertical_pole:Nnn #1#2#3
16806 {
16807   \_coffin_if_exist:NT #1
16808   {
16809     \_coffin_set_pole:Nnx #1 {#2}
16810     {
16811       { \dim_eval:n {#3} } { 0 pt }
16812       { 0 pt } { 1000 pt }
16813     }
16814   }
16815 }
16816 \cs_new_protected:Npn \_coffin_set_pole:Nnn #1#2#3
16817 { \prop_put:cnn { l__coffin_poles_ \_int_value:w #1 _prop } {#2} {#3} }
16818 \cs_generate_variant:Nn \coffin_set_horizontal_pole:Nnn { c }
16819 \cs_generate_variant:Nn \coffin_set_vertical_pole:Nnn { c }
16820 \cs_generate_variant:Nn \_coffin_set_pole:Nnn { Nnx }

```

(End definition for `\coffin_set_horizontal_pole:Nnn`, `\coffin_set_vertical_pole:Nnn`, and `_coffin_set_pole:Nnn`. These functions are documented on page 201.)

`_coffin_update_corners:N` Updating the corners of a coffin is straight-forward as at this stage there can be no rotation. So the corners of the content are just those of the underlying TeX box.

```

16821 \cs_new_protected:Npn \__coffin_update_corners:N #1
16822 {
16823   \prop_put:cnx { l__coffin_corners_ \__int_value:w #1 _prop } { tl }
16824   { { 0 pt } { \dim_eval:n { \box_ht:N #1 } } } }
16825   \prop_put:cnx { l__coffin_corners_ \__int_value:w #1 _prop } { tr }
16826   { { \dim_eval:n { \box_wd:N #1 } } { \dim_eval:n { \box_ht:N #1 } } } }
16827   \prop_put:cnx { l__coffin_corners_ \__int_value:w #1 _prop } { bl }
16828   { { 0 pt } { \dim_eval:n { - \box_dp:N #1 } } } }
16829   \prop_put:cnx { l__coffin_corners_ \__int_value:w #1 _prop } { br }
16830   { { \dim_eval:n { \box_wd:N #1 } } { \dim_eval:n { -\box_dp:N #1 } } } }
16831 }

```

(End definition for __coffin_update_corners:N.)

__coffin_update_poles:N This function is called when a coffin is set, and updates the poles to reflect the nature of size of the box. Thus this function only alters poles where the default position is dependent on the size of the box. It also does not set poles which are relevant only to vertical coffins.

```

16832 \cs_new_protected:Npn \__coffin_update_poles:N #1
16833 {
16834   \prop_put:cnx { l__coffin_poles_ \__int_value:w #1 _prop } { hc }
16835   {
16836     { \dim_eval:n { 0.5 \box_wd:N #1 } }
16837     { 0 pt } { 0 pt } { 1000 pt }
16838   }
16839   \prop_put:cnx { l__coffin_poles_ \__int_value:w #1 _prop } { r }
16840   {
16841     { \dim_eval:n { \box_wd:N #1 } }
16842     { 0 pt } { 0 pt } { 1000 pt }
16843   }
16844   \prop_put:cnx { l__coffin_poles_ \__int_value:w #1 _prop } { vc }
16845   {
16846     { 0 pt }
16847     { \dim_eval:n { ( \box_ht:N #1 - \box_dp:N #1 ) / 2 } }
16848     { 1000 pt }
16849     { 0 pt }
16850   }
16851   \prop_put:cnx { l__coffin_poles_ \__int_value:w #1 _prop } { t }
16852   {
16853     { 0 pt }
16854     { \dim_eval:n { \box_ht:N #1 } }
16855     { 1000 pt }
16856     { 0 pt }
16857   }
16858   \prop_put:cnx { l__coffin_poles_ \__int_value:w #1 _prop } { b }
16859   {
16860     { 0 pt }
16861     { \dim_eval:n { - \box_dp:N #1 } }
16862     { 1000 pt }
16863     { 0 pt }
16864   }
16865 }

```

(End definition for __coffin_update_poles:N.)

34.5 Coffins: calculation of pole intersections

```
\_coffin_calculate_intersection:Nmn
\_coffin_calculate_intersection:nnnnnnnn
\_coffin_calculate_intersection_aux:nnnnnN
```

The lead off in finding intersections is to recover the two poles and then hand off to the auxiliary for the actual calculation. There may of course not be an intersection, for which an error trap is needed.

```
16866 \cs_new_protected:Npn \_coffin_calculate_intersection:Nnn #1#2#3
16867 {
16868   \_coffin_get_pole:NnN #1 {#2} \l__coffin_pole_a_tl
16869   \_coffin_get_pole:NnN #1 {#3} \l__coffin_pole_b_tl
16870   \bool_set_false:N \l__coffin_error_bool
16871   \exp_last_two_unbraced:Noo
16872   \_coffin_calculate_intersection:nnnnnnnn
16873   \l__coffin_pole_a_tl \l__coffin_pole_b_tl
16874   \bool_if:NT \l__coffin_error_bool
16875   {
16876     \_msg_kernel_error:nn { kernel } { no-pole-intersection }
16877     \dim_zero:N \l__coffin_x_dim
16878     \dim_zero:N \l__coffin_y_dim
16879   }
16880 }
```

The two poles passed here each have four values (as dimensions), (a, b, c, d) and (a', b', c', d') . These are arguments 1–4 and 5–8, respectively. In both cases a and b are the co-ordinates of a point on the pole and c and d define the direction of the pole. Finding the intersection depends on the directions of the poles, which are given by d/c and d'/c' . However, if one of the poles is either horizontal or vertical then one or more of c, d, c' and d' will be zero and a special case is needed.

```
16881 \cs_new_protected:Npn \_coffin_calculate_intersection:nnnnnnnn
16882   #1#2#3#4#5#6#7#8
16883 {
16884   \dim_compare:nNnTF {#3} = { \c_zero_dim }
```

The case where the first pole is vertical. So the x -component of the interaction will be at a . There is then a test on the second pole: if it is also vertical then there is an error.

```
16885   {
16886     \dim_set:Nn \l__coffin_x_dim {#1}
16887     \dim_compare:nNnTF {#7} = { \c_zero_dim
16888       { \bool_set_true:N \l__coffin_error_bool }
```

The second pole may still be horizontal, in which case the y -component of the intersection will be b' . If not,

$$y = \frac{d'}{c'} (x - a') + b'$$

with the x -component already known to be #1. This calculation is done as a generalised auxiliary.

```
16889   {
16890     \dim_compare:nNnTF {#8} = { \c_zero_dim
16891       { \dim_set:Nn \l__coffin_y_dim {#6} }
16892     }
16893     \_coffin_calculate_intersection_aux:nnnnnN
16894     {#1} {#5} {#6} {#7} {#8} \l__coffin_y_dim
16895   }
16896 }
16897 }
```

If the first pole is not vertical then it may be horizontal. If so, then the procedure is essentially the same as that already done but with the x - and y -components interchanged.

```

16898     {
16899         \dim_compare:nNnTF {#4} = \c_zero_dim
16900     {
16901         \dim_set:Nn \l__coffin_y_dim {#2}
16902         \dim_compare:nNnTF {#8} = { \c_zero_dim }
16903         { \bool_set_true:N \l__coffin_error_bool }
16904     }
16905     \dim_compare:nNnTF {#7} = \c_zero_dim
16906     { \dim_set:Nn \l__coffin_x_dim {#5} }

```

The formula for the case where the second pole is neither horizontal nor vertical is

$$x = \frac{c'}{d'}(y - b') + a'$$

which is again handled by the same auxiliary.

```

16907     {
16908         \__coffin_calculate_intersection_aux:nnnnnN
16909         {#2} {#6} {#5} {#8} {#7} \l__coffin_x_dim
16910     }
16911 }
16912 }

```

The first pole is neither horizontal nor vertical. This still leaves the second pole, which may be a special case. For those possibilities, the calculations are the same as above with the first and second poles interchanged.

```

16913     {
16914         \dim_compare:nNnTF {#7} = \c_zero_dim
16915     {
16916         \dim_set:Nn \l__coffin_x_dim {#5}
16917         \__coffin_calculate_intersection_aux:nnnnnN
16918         {#5} {#1} {#2} {#3} {#4} \l__coffin_y_dim
16919     }
16920     {
16921         \dim_compare:nNnTF {#8} = \c_zero_dim
16922     {
16923         \dim_set:Nn \l__coffin_y_dim {#6}
16924         \__coffin_calculate_intersection_aux:nnnnnN
16925         {#6} {#2} {#1} {#4} {#3} \l__coffin_x_dim
16926     }

```

If none of the special cases apply then there is still a need to check that there is a unique intersection between the two pole. This is the case if they have different slopes.

```

16927     {
16928         \fp_set:Nn \l__coffin_slope_x_fp
16929         { \dim_to_fp:n {#4} / \dim_to_fp:n {#3} }
16930         \fp_set:Nn \l__coffin_slope_y_fp
16931         { \dim_to_fp:n {#8} / \dim_to_fp:n {#7} }
16932         \fp_compare:nNnTF
16933         \l__coffin_slope_x_fp = \l__coffin_slope_y_fp
16934         { \bool_set_true:N \l__coffin_error_bool }

```

All of the tests pass, so there is the full complexity of the calculation:

$$x = \frac{a(d/c) - a'(d'/c') - b + b'}{(d/c) - (d'/c')}$$

and noting that the two ratios are already worked out from the test just performed. There is quite a bit of shuffling from dimensions to floating points in order to do the work. The y -values is then worked out using the standard auxiliary starting from the x -position.

```

16935         {
16936             \dim_set:Nn \l__coffin_x_dim
16937             {
16938                 \fp_to_dim:n
16939                 {
16940                     (
16941                         \dim_to_fp:n {#1} * \l__coffin_slope_x_fp
16942                         - ( \dim_to_fp:n {#5} * \l__coffin_slope_y_fp )
16943                         - \dim_to_fp:n {#2}
16944                         + \dim_to_fp:n {#6}
16945                     )
16946                     /
16947                     ( \l__coffin_slope_x_fp - \l__coffin_slope_y_fp )
16948                 }
16949             }
16950             \__coffin_calculate_intersection_aux:nnnnnN
16951             { \l__coffin_x_dim }
16952             {#5} {#6} {#8} {#7} \l__coffin_y_dim
16953         }
16954     }
16955 }
16956 }
16957 }
16958 }
```

The formula for finding the intersection point is in most cases the same. The formula here is

$$\#6 = \#4 \cdot \left(\frac{\#1 - \#2}{\#5} \right) \#3$$

Thus #4 and #5 should be the directions of the pole while #2 and #3 are co-ordinates.

```

16959 \cs_new_protected:Npn \__coffin_calculate_intersection_aux:nnnnnN
16960     #1#2#3#4#5#6
16961     {
16962         \dim_set:Nn #6
16963         {
16964             \fp_to_dim:n
16965             {
16966                 \dim_to_fp:n {#4} *
16967                 ( \dim_to_fp:n {#1} - \dim_to_fp:n {#2} ) /
16968                 \dim_to_fp:n {#5}
16969                 + \dim_to_fp:n {#3}
16970             }
16971         }
16972     }
```

(End definition for `__coffin_calculate_intersection:Nnn`, `__coffin_calculate_intersection:nnnnnnnn`, and `__coffin_calculate_intersection_aux:nnnnnnN`.)

34.6 Aligning and typesetting of coffins

`\coffin_join:NnnNnnnn`
`\coffin_join:cnnNnnnn`
`\coffin_join:Nnncnnnn`
`\coffin_join:cnnccnnnn`

This command joins two coffins, using a horizontal and vertical pole from each coffin and making an offset between the two. The result is stored as the as a third coffin, which will have all of its handles reset to standard values. First, the more basic alignment function is used to get things started.

```
16973 \cs_new_protected:Npn \coffin_join:NnnNnnnn #1#2#3#4#5#6#7#8
16974 {
16975   \__coffin_align:NnnNnnnnN
16976   #1 {#2} {#3} #4 {#5} {#6} {#7} {#8} \l__coffin_aligned_coffin
```

Correct the placement of the reference point. If the x -offset is negative then the reference point of the second box is to the left of that of the first, which is corrected using a kern. On the right side the first box might stick out, which will show up if it is wider than the sum of the x -offset and the width of the second box. So a second kern may be needed.

```
16977   \hbox_set:Nn \l__coffin_aligned_coffin
16978   {
16979     \dim_compare:nNnT { \l__coffin_offset_x_dim } < \c_zero_dim
16980     { \tex_kern:D -\l__coffin_offset_x_dim }
16981     \hbox_unpack:N \l__coffin_aligned_coffin
16982     \dim_set:Nn \l__coffin_internal_dim
16983     { \l__coffin_offset_x_dim - \box_wd:N #1 + \box_wd:N #4 }
16984     \dim_compare:nNnT \l__coffin_internal_dim < \c_zero_dim
16985     { \tex_kern:D -\l__coffin_internal_dim }
16986   }
```

The coffin structure is reset, and the corners are cleared: only those from the two parent coffins are needed.

```
16987   \__coffin_reset_structure:N \l__coffin_aligned_coffin
16988   \prop_clear:c
16989   { \l__coffin_corners_ \__int_value:w \l__coffin_aligned_coffin _ prop }
16990   \__coffin_update_poles:N \l__coffin_aligned_coffin
```

The structures of the parent coffins are now transferred to the new coffin, which requires that the appropriate offsets are applied. That will then depend on whether any shift was needed.

```
16991   \dim_compare:nNnTF \l__coffin_offset_x_dim < \c_zero_dim
16992   {
16993     \__coffin_offset_poles:Nnn #1 { -\l__coffin_offset_x_dim } { 0 pt }
16994     \__coffin_offset_poles:Nnn #4 { 0 pt } { \l__coffin_offset_y_dim }
16995     \__coffin_offset_corners:Nnn #1 { -\l__coffin_offset_x_dim } { 0 pt }
16996     \__coffin_offset_corners:Nnn #4 { 0 pt } { \l__coffin_offset_y_dim }
16997   }
16998   {
16999     \__coffin_offset_poles:Nnn #1 { 0 pt } { 0 pt }
17000     \__coffin_offset_poles:Nnn #4
17001     { \l__coffin_offset_x_dim } { \l__coffin_offset_y_dim }
17002     \__coffin_offset_corners:Nnn #1 { 0 pt } { 0 pt }
17003     \__coffin_offset_corners:Nnn #4
17004     { \l__coffin_offset_x_dim } { \l__coffin_offset_y_dim }
17005   }
```

```

17006     \__coffin_update_vertical_poles:NNN #1 #4 \l__coffin_aligned_coffin
17007     \coffin_set_eq:NN #1 \l__coffin_aligned_coffin
17008 }
17009 \cs_generate_variant:Nn \coffin_join:NnnNnnnn { c , Nnnc , cncn }

```

(End definition for \coffin_join:NnnNnnnn. This function is documented on page 202.)

\coffin_attach:NnnNnnnn

\coffin_attach:cnnNnnnn

\coffin_attach:Nnncnnnn

\coffin_attach:cncncnnnn

\coffin_attach_mark:NnnNnnnn

A more simple version of the above, as it simply uses the size of the first coffin for the new one. This means that the work here is rather simplified compared to the above code. The function used when marking a position is hear also as it is similar but without the structure updates.

```

17010 \cs_new_protected:Npn \coffin_attach:NnnNnnnn #1#2#3#4#5#6#7#8
17011 {
17012     \__coffin_align:NnnNnnnnN
17013     #1 {#2} {#3} #4 {#5} {#6} {#7} {#8} \l__coffin_aligned_coffin
17014     \box_set_ht:Nn \l__coffin_aligned_coffin { \box_ht:N #1 }
17015     \box_set_dp:Nn \l__coffin_aligned_coffin { \box_dp:N #1 }
17016     \box_set_wd:Nn \l__coffin_aligned_coffin { \box_wd:N #1 }
17017     \__coffin_reset_structure:N \l__coffin_aligned_coffin
17018     \prop_set_eq:cc
17019     { \l__coffin_corners_ \__int_value:w \l__coffin_aligned_coffin _prop }
17020     { \l__coffin_corners_ \__int_value:w #1 _prop }
17021     \__coffin_update_poles:N \l__coffin_aligned_coffin
17022     \__coffin_offset_poles:Nnn #1 { 0 pt } { 0 pt }
17023     \__coffin_offset_poles:Nnn #4
17024     { \l__coffin_offset_x_dim } { \l__coffin_offset_y_dim }
17025     \__coffin_update_vertical_poles:NNN #1 #4 \l__coffin_aligned_coffin
17026     \coffin_set_eq:NN #1 \l__coffin_aligned_coffin
17027 }
17028 \cs_new_protected:Npn \coffin_attach_mark:NnnNnnnn #1#2#3#4#5#6#7#8
17029 {
17030     \__coffin_align:NnnNnnnnN
17031     #1 {#2} {#3} #4 {#5} {#6} {#7} {#8} \l__coffin_aligned_coffin
17032     \box_set_ht:Nn \l__coffin_aligned_coffin { \box_ht:N #1 }
17033     \box_set_dp:Nn \l__coffin_aligned_coffin { \box_dp:N #1 }
17034     \box_set_wd:Nn \l__coffin_aligned_coffin { \box_wd:N #1 }
17035     \box_set_eq:NN #1 \l__coffin_aligned_coffin
17036 }
17037 \cs_generate_variant:Nn \coffin_attach:NnnNnnnn { c , Nnnc , cncn }

```

(End definition for \coffin_attach:NnnNnnnn and \coffin_attach_mark:NnnNnnnn. These functions are documented on page 201.)

__coffin_align:NnnNnnnnN

The internal function aligns the two coffins into a third one, but performs no corrections on the resulting coffin poles. The process begins by finding the points of intersection for the poles for each of the input coffins. Those for the first coffin are worked out after those for the second coffin, as this allows the ‘primed’ storage area to be used for the second coffin. The ‘real’ box offsets are then calculated, before using these to re-box the input coffins. The default poles are then set up, but the final result will depend on how the bounding box is being handled.

```

17038 \cs_new_protected:Npn \__coffin_align:NnnNnnnnN #1#2#3#4#5#6#7#8#9
17039 {
17040     \__coffin_calculate_intersection:Nnn #4 {#5} {#6}
17041     \dim_set:Nn \l__coffin_x_prime_dim { \l__coffin_x_dim }

```

```

17042 \dim_set:Nn \l__coffin_y_prime_dim { \l__coffin_y_dim }
17043 \__coffin_calculate_intersection:Nnn #1 {#2} {#3}
17044 \dim_set:Nn \l__coffin_offset_x_dim
17045 { \l__coffin_x_dim - \l__coffin_x_prime_dim + #7 }
17046 \dim_set:Nn \l__coffin_offset_y_dim
17047 { \l__coffin_y_dim - \l__coffin_y_prime_dim + #8 }
17048 \hbox_set:Nn \l__coffin_aligned_internal_coffin
17049 {
17050   \box_use:N #1
17051   \tex_kern:D -\box_wd:N #1
17052   \tex_kern:D \l__coffin_offset_x_dim
17053   \box_move_up:nn { \l__coffin_offset_y_dim } { \box_use:N #4 }
17054 }
17055 \coffin_set_eq:NN #9 \l__coffin_aligned_internal_coffin
17056 }

```

(End definition for __coffin_align:NnnNnnnnN.)

__coffin_offset_poles:Nnn Transferring structures from one coffin to another requires that the positions are updated by the offset between the two coffins. This is done by mapping to the property list of the source coffins, moving as appropriate and saving to the new coffin data structures. The test for a - means that the structures from the parent coffins are uniquely labelled and do not depend on the order of alignment. The pay off for this is that - should not be used in coffin pole or handle names, and that multiple alignments do not result in a whole set of values.

```

17057 \cs_new_protected:Npn \__coffin_offset_poles:Nnn #1#2#3
17058 {
17059   \prop_map_inline:cn { l__coffin_poles_ \__int_value:w #1 _prop }
17060   { \__coffin_offset_pole:Nnnnnnn #1 {##1} ##2 {#2} {#3} }
17061 }
17062 \cs_new_protected:Npn \__coffin_offset_pole:Nnnnnnn #1#2#3#4#5#6#7#8
17063 {
17064   \dim_set:Nn \l__coffin_x_dim { #3 + #7 }
17065   \dim_set:Nn \l__coffin_y_dim { #4 + #8 }
17066   \tl_if_in:nnTF {#2} { - }
17067   { \tl_set:Nn \l__coffin_internal_tl { {#2} } }
17068   { \tl_set:Nn \l__coffin_internal_tl { { #1 - #2 } } }
17069   \exp_last_unbraced:NNo \__coffin_set_pole:Nnx \l__coffin_aligned_coffin
17070   { \l__coffin_internal_tl }
17071   {
17072     { \dim_use:N \l__coffin_x_dim } { \dim_use:N \l__coffin_y_dim }
17073     {#5} {#6}
17074   }
17075 }

```

(End definition for __coffin_offset_poles:Nnn and __coffin_offset_pole:Nnnnnnn.)

__coffin_offset_corners:Nnn Saving the offset corners of a coffin is very similar, except that there is no need to worry about naming: every corner can be saved here as order is unimportant.

```

17076 \cs_new_protected:Npn \__coffin_offset_corners:Nnn #1#2#3
17077 {
17078   \prop_map_inline:cn { l__coffin_corners_ \__int_value:w #1 _prop }
17079   { \__coffin_offset_corner:Nnnnn #1 {##1} ##2 {#2} {#3} }
17080 }

```

```

17081 \cs_new_protected:Npn \__coffin_offset_corner:Nnnnn #1#2#3#4#5#6
17082 {
17083   \prop_put:cnx
17084   { l__coffin_corners_ \__int_value:w \l__coffin_aligned_coffin _prop }
17085   { #1 - #2 }
17086   {
17087     { \dim_eval:n { #3 + #5 } }
17088     { \dim_eval:n { #4 + #6 } }
17089   }
17090 }

```

(End definition for __coffin_offset_corners:Nnn and __coffin_offset_corner:Nnnnn.)

__coffin_update_vertical_poles:NNN The T and B poles will need to be recalculated after alignment. These functions find the larger absolute value for the poles, but this is of course only logical when the poles are horizontal.

```

17091 \cs_new_protected:Npn \__coffin_update_vertical_poles:NNN #1#2#3
17092 {
17093   \__coffin_get_pole:NnN #3 { #1 -T } \l__coffin_pole_a_tl
17094   \__coffin_get_pole:NnN #3 { #2 -T } \l__coffin_pole_b_tl
17095   \exp_last_two_unbraced:Noo \__coffin_update_T:nnnnnnnnN
17096   \l__coffin_pole_a_tl \l__coffin_pole_b_tl #3
17097   \__coffin_get_pole:NnN #3 { #1 -B } \l__coffin_pole_a_tl
17098   \__coffin_get_pole:NnN #3 { #2 -B } \l__coffin_pole_b_tl
17099   \exp_last_two_unbraced:Noo \__coffin_update_B:nnnnnnnnN
17100   \l__coffin_pole_a_tl \l__coffin_pole_b_tl #3
17101 }
17102 \cs_new_protected:Npn \__coffin_update_T:nnnnnnnnN #1#2#3#4#5#6#7#8#9
17103 {
17104   \dim_compare:nNnTF {#2} < {#6}
17105   {
17106     \__coffin_set_pole:Nnx #9 { T }
17107     { { 0 pt } {#6} { 1000 pt } { 0 pt } }
17108   }
17109   {
17110     \__coffin_set_pole:Nnx #9 { T }
17111     { { 0 pt } {#2} { 1000 pt } { 0 pt } }
17112   }
17113 }
17114 \cs_new_protected:Npn \__coffin_update_B:nnnnnnnnN #1#2#3#4#5#6#7#8#9
17115 {
17116   \dim_compare:nNnTF {#2} < {#6}
17117   {
17118     \__coffin_set_pole:Nnx #9 { B }
17119     { { 0 pt } {#2} { 1000 pt } { 0 pt } }
17120   }
17121   {
17122     \__coffin_set_pole:Nnx #9 { B }
17123     { { 0 pt } {#6} { 1000 pt } { 0 pt } }
17124   }
17125 }

```

(End definition for __coffin_update_vertical_poles:NNN, __coffin_update_T:nnnnnnnnN, and __coffin_update_B:nnnnnnnnN.)

`\coffin_typeset:Nnnnn` Typesetting a coffin means aligning it with the current position, which is done using a coffin with no content at all. As well as aligning to the empty coffin, there is also a need to leave vertical mode, if necessary.

```

17126 \cs_new_protected:Npn \coffin_typeset:Nnnnn #1#2#3#4#5
17127 {
17128   \hbox_unpack:N \c_empty_box
17129   \__coffin_align:NnnNnnnnN \c_empty_coffin { H } { 1 }
17130   #1 {#2} {#3} {#4} {#5} \l__coffin_aligned_coffin
17131   \box_use:N \l__coffin_aligned_coffin
17132 }
17133 \cs_generate_variant:Nn \coffin_typeset:Nnnnn { c }

```

(End definition for `\coffin_typeset:Nnnnn`. This function is documented on page 202.)

34.7 Coffin diagnostics

`\l__coffin_display_coffin` Used for printing coffins with data structures attached.

```

\l__coffin_display_coord_coffin 17134 \coffin_new:N \l__coffin_display_coffin
\l__coffin_display_pole_coffin 17135 \coffin_new:N \l__coffin_display_coord_coffin
17136 \coffin_new:N \l__coffin_display_pole_coffin

```

(End definition for `\l__coffin_display_coffin`, `\l__coffin_display_coord_coffin`, and `\l__coffin_display_pole_coffin`.)

`\l__coffin_display_handles_prop` This property list is used to print coffin handles at suitable positions. The offsets are expressed as multiples of the basic offset value, which therefore acts as a scale-factor.

```

17137 \prop_new:N \l__coffin_display_handles_prop
17138 \prop_put:Nnn \l__coffin_display_handles_prop { tl }
17139 { { b } { r } { -1 } { 1 } }
17140 \prop_put:Nnn \l__coffin_display_handles_prop { thc }
17141 { { b } { hc } { 0 } { 1 } }
17142 \prop_put:Nnn \l__coffin_display_handles_prop { tr }
17143 { { b } { l } { 1 } { 1 } }
17144 \prop_put:Nnn \l__coffin_display_handles_prop { vcl }
17145 { { vc } { r } { -1 } { 0 } }
17146 \prop_put:Nnn \l__coffin_display_handles_prop { vhc }
17147 { { vc } { hc } { 0 } { 0 } }
17148 \prop_put:Nnn \l__coffin_display_handles_prop { vcr }
17149 { { vc } { l } { 1 } { 0 } }
17150 \prop_put:Nnn \l__coffin_display_handles_prop { bl }
17151 { { t } { r } { -1 } { -1 } }
17152 \prop_put:Nnn \l__coffin_display_handles_prop { bhc }
17153 { { t } { hc } { 0 } { -1 } }
17154 \prop_put:Nnn \l__coffin_display_handles_prop { br }
17155 { { t } { l } { 1 } { -1 } }
17156 \prop_put:Nnn \l__coffin_display_handles_prop { Tl }
17157 { { t } { r } { -1 } { -1 } }
17158 \prop_put:Nnn \l__coffin_display_handles_prop { Thc }
17159 { { t } { hc } { 0 } { -1 } }
17160 \prop_put:Nnn \l__coffin_display_handles_prop { Tr }
17161 { { t } { l } { 1 } { -1 } }
17162 \prop_put:Nnn \l__coffin_display_handles_prop { Hl }
17163 { { vc } { r } { -1 } { 1 } }
17164 \prop_put:Nnn \l__coffin_display_handles_prop { Hhc }

```



```

17165 { { vc } { hc } { 0 } { 1 } }
17166 \prop_put:Nnn \l__coffin_display_handles_prop { Hr }
17167 { { vc } { 1 } { 1 } { 1 } }
17168 \prop_put:Nnn \l__coffin_display_handles_prop { Bl }
17169 { { b } { r } { -1 } { -1 } }
17170 \prop_put:Nnn \l__coffin_display_handles_prop { Bhc }
17171 { { b } { hc } { 0 } { -1 } }
17172 \prop_put:Nnn \l__coffin_display_handles_prop { Br }
17173 { { b } { 1 } { 1 } { -1 } }

```

(End definition for `\l__coffin_display_handles_prop`.)

`\l__coffin_display_offset_dim` The standard offset for the label from the handle position when displaying handles.

```

17174 \dim_new:N \l__coffin_display_offset_dim
17175 \dim_set:Nn \l__coffin_display_offset_dim { 2 pt }

```

(End definition for `\l__coffin_display_offset_dim`.)

`\l__coffin_display_x_dim` As the intersections of poles have to be calculated to find which ones to print, there is
`\l__coffin_display_y_dim` a need to avoid repetition. This is done by saving the intersection into two dedicated values.

```

17176 \dim_new:N \l__coffin_display_x_dim
17177 \dim_new:N \l__coffin_display_y_dim

```

(End definition for `\l__coffin_display_x_dim` and `\l__coffin_display_y_dim`.)

`\l__coffin_display_poles_prop` A property list for printing poles: various things need to be deleted from this to get a “nice” output.

```

17178 \prop_new:N \l__coffin_display_poles_prop

```

(End definition for `\l__coffin_display_poles_prop`.)

`\l__coffin_display_font_tl` Stores the settings used to print coffin data: this keeps things flexible.

```

17179 \tl_new:N \l__coffin_display_font_tl
17180 {*\initex}
17181 \tl_set:Nn \l__coffin_display_font_tl { } % TODO
17182 </initex>
17183 {*\package}
17184 \tl_set:Nn \l__coffin_display_font_tl { \sfamily \tiny }
17185 </package>

```

(End definition for `\l__coffin_display_font_tl`.)

`\coffin_mark_handle:Nnnn` Marking a single handle is relatively easy. The standard attachment function is used,
`\coffin_mark_handle:cnnn` meaning that there are two calculations for the location. However, this is likely to be
`__coffin_mark_handle_aux:nnnnNnn` okay given the load expected. Contrast with the more optimised version for showing all handles which comes next.

```

17186 \cs_new_protected:Npn \coffin_mark_handle:Nnnn #1#2#3#4
17187 {
17188   \hcoffin_set:Nn \l__coffin_display_pole_coffin
17189   {
17190     {*\initex}
17191     \hbox:n { \tex_vrule:D width 1 pt height 1 pt \scan_stop: } % TODO
17192     </initex>
17193     {*\package}

```

```

17194         \color {#4}
17195         \rule { 1 pt } { 1 pt }
17196     \end{package}
17197 }
17198 \coffin_attach_mark:NnnNnnnn #1 {#2} {#3}
17199 \l__coffin_display_pole_coffin { hc } { vc } { 0 pt } { 0 pt }
17200 \hcoffin_set:Nn \l__coffin_display_coord_coffin
17201 {
17202 *initex
17203 % TODO
17204 \end{initex}
17205 *package
17206 \color {#4}
17207 \end{package}
17208 \l__coffin_display_font_tl
17209 ( \tl_to_str:n { #2 , #3 } )
17210 }
17211 \prop_get:NnN \l__coffin_display_handles_prop
17212 { #2 #3 } \l__coffin_internal_tl
17213 \quark_if_no_value:NTF \l__coffin_internal_tl
17214 {
17215     \prop_get:NnN \l__coffin_display_handles_prop
17216     { #3 #2 } \l__coffin_internal_tl
17217     \quark_if_no_value:NTF \l__coffin_internal_tl
17218     {
17219         \coffin_attach_mark:NnnNnnnn #1 {#2} {#3}
17220         \l__coffin_display_coord_coffin { l } { vc }
17221         { 1 pt } { 0 pt }
17222     }
17223     {
17224         \exp_last_unbraced:No \__coffin_mark_handle_aux:nnnnNnn
17225         \l__coffin_internal_tl #1 {#2} {#3}
17226     }
17227 }
17228 {
17229     \exp_last_unbraced:No \__coffin_mark_handle_aux:nnnnNnn
17230     \l__coffin_internal_tl #1 {#2} {#3}
17231 }
17232 }
17233 \cs_new_protected:Npn \__coffin_mark_handle_aux:nnnnNnn #1#2#3#4#5#6#7
17234 {
17235     \coffin_attach_mark:NnnNnnnn #5 {#6} {#7}
17236     \l__coffin_display_coord_coffin {#1} {#2}
17237     { #3 \l__coffin_display_offset_dim }
17238     { #4 \l__coffin_display_offset_dim }
17239 }
17240 \cs_generate_variant:Nn \coffin_mark_handle:Nnnn { c }

```

(End definition for `\coffin_mark_handle:Nnnn` and `__coffin_mark_handle_aux:nnnnNnn`. These functions are documented on page 203.)

`\coffin_display_handles:Nn`
`\coffin_display_handles:cn`
`__coffin_display_handles_aux:nnnnnn`
`__coffin_display_handles_aux:nnnn`
`__coffin_display_attach:Nnnnn`

Printing the poles starts by removing any duplicates, for which the H poles is used as the definitive version for the baseline and bottom. Two loops are then used to find the combinations of handles for all of these poles. This is done such that poles are removed

during the loops to avoid duplication.

```

17241 \cs_new_protected:Npn \coffin_display_handles:Nn #1#2
17242 {
17243   \hcoffin_set:Nn \l__coffin_display_pole_coffin
17244   {
17245     <*initex>
17246     \hbox:n { \tex_vrule:D width 1 pt height 1 pt \scan_stop: } % TODO
17247   </initex>
17248   <*package>
17249     \color {#2}
17250     \rule { 1 pt } { 1 pt }
17251   </package>
17252   }
17253   \prop_set_eq:Nc \l__coffin_display_poles_prop
17254   { \l__coffin_poles_ \__int_value:w #1 _prop }
17255   \__coffin_get_pole:NnN #1 { H } \l__coffin_pole_a_tl
17256   \__coffin_get_pole:NnN #1 { T } \l__coffin_pole_b_tl
17257   \tl_if_eq:NNT \l__coffin_pole_a_tl \l__coffin_pole_b_tl
17258   { \prop_remove:Nn \l__coffin_display_poles_prop { T } }
17259   \__coffin_get_pole:NnN #1 { B } \l__coffin_pole_b_tl
17260   \tl_if_eq:NNT \l__coffin_pole_a_tl \l__coffin_pole_b_tl
17261   { \prop_remove:Nn \l__coffin_display_poles_prop { B } }
17262   \coffin_set_eq:NN \l__coffin_display_coffin #1
17263   \prop_map_inline:Nn \l__coffin_display_poles_prop
17264   {
17265     \prop_remove:Nn \l__coffin_display_poles_prop {##1}
17266     \__coffin_display_handles_aux:nnnnnn {##1} ##2 {#2}
17267   }
17268   \box_use:N \l__coffin_display_coffin
17269 }

```

For each pole there is a check for an intersection, which here does not give an error if none is found. The successful values are stored and used to align the pole coffin with the main coffin for output. The positions are recovered from the preset list if available.

```

17270 \cs_new_protected:Npn \__coffin_display_handles_aux:nnnnnn #1#2#3#4#5#6
17271 {
17272   \prop_map_inline:Nn \l__coffin_display_poles_prop
17273   {
17274     \bool_set_false:N \l__coffin_error_bool
17275     \__coffin_calculate_intersection:nnnnnnnn {#2} {#3} {#4} {#5} ##2
17276     \bool_if:NF \l__coffin_error_bool
17277     {
17278       \dim_set:Nn \l__coffin_display_x_dim { \l__coffin_x_dim }
17279       \dim_set:Nn \l__coffin_display_y_dim { \l__coffin_y_dim }
17280       \__coffin_display_attach:Nnnnn
17281       \l__coffin_display_pole_coffin { hc } { vc }
17282       { 0 pt } { 0 pt }
17283       \hcoffin_set:Nn \l__coffin_display_coord_coffin
17284       {
17285         <*initex>
17286         % TODO
17287       </initex>
17288     <*package>
17289     \color {#6}

```

```

17290 \end{package}
17291 \l__coffin_display_font_tl
17292 ( \tl_to_str:n { #1 , ##1 } )
17293 }
17294 \prop_get:NnN \l__coffin_display_handles_prop
17295 { #1 ##1 } \l__coffin_internal_tl
17296 \quark_if_no_value:NTF \l__coffin_internal_tl
17297 {
17298   \prop_get:NnN \l__coffin_display_handles_prop
17299   { ##1 #1 } \l__coffin_internal_tl
17300   \quark_if_no_value:NTF \l__coffin_internal_tl
17301   {
17302     \__coffin_display_attach:Nnnnn
17303     \l__coffin_display_coord_coffin { 1 } { vc }
17304     { 1 pt } { 0 pt }
17305   }
17306   {
17307     \exp_last_unbraced:No
17308     \__coffin_display_handles_aux:nnnn
17309     \l__coffin_internal_tl
17310   }
17311 }
17312 {
17313   \exp_last_unbraced:No \__coffin_display_handles_aux:nnnn
17314   \l__coffin_internal_tl
17315 }
17316 }
17317 }
17318 }
17319 \cs_new_protected:Npn \__coffin_display_handles_aux:nnnn #1#2#3#4
17320 {
17321   \__coffin_display_attach:Nnnnn
17322   \l__coffin_display_coord_coffin {#1} {#2}
17323   { #3 \l__coffin_display_offset_dim }
17324   { #4 \l__coffin_display_offset_dim }
17325 }
17326 \cs_generate_variant:Nn \coffin_display_handles:Nn { c }

```

This is a dedicated version of `\coffin_attach:NnnNnnnn` with a hard-wired first coffin. As the intersection is already known and stored for the display coffin the code simply uses it directly, with no calculation.

```

17327 \cs_new_protected:Npn \__coffin_display_attach:Nnnnn #1#2#3#4#5
17328 {
17329   \__coffin_calculate_intersection:Nnn #1 {#2} {#3}
17330   \dim_set:Nn \l__coffin_x_prime_dim { \l__coffin_x_dim }
17331   \dim_set:Nn \l__coffin_y_prime_dim { \l__coffin_y_dim }
17332   \dim_set:Nn \l__coffin_offset_x_dim
17333   { \l__coffin_display_x_dim - \l__coffin_x_prime_dim + #4 }
17334   \dim_set:Nn \l__coffin_offset_y_dim
17335   { \l__coffin_display_y_dim - \l__coffin_y_prime_dim + #5 }
17336   \hbox_set:Nn \l__coffin_aligned_coffin
17337   {
17338     \box_use:N \l__coffin_display_coffin
17339     \tex_kern:D -\box_wd:N \l__coffin_display_coffin

```

```

17340     \tex_kern:D \l__coffin_offset_x_dim
17341     \box_move_up:nn { \l__coffin_offset_y_dim } { \box_use:N #1 }
17342   }
17343   \box_set_ht:Nn \l__coffin_aligned_coffin
17344     { \box_ht:N \l__coffin_display_coffin }
17345   \box_set_dp:Nn \l__coffin_aligned_coffin
17346     { \box_dp:N \l__coffin_display_coffin }
17347   \box_set_wd:Nn \l__coffin_aligned_coffin
17348     { \box_wd:N \l__coffin_display_coffin }
17349   \box_set_eq:NN \l__coffin_display_coffin \l__coffin_aligned_coffin
17350 }

```

(End definition for `\coffin_display_handles:Nn` and others. These functions are documented on page 202.)

`\coffin_show_structure:N` For showing the various internal structures attached to a coffin in a way that keeps things relatively readable. If there is no apparent structure then the code complains.

`\coffin_show_structure:c`

```

17351 \cs_new_protected:Npn \coffin_show_structure:N #1
17352 {
17353   \__coffin_if_exist:NT #1
17354   {
17355     \__msg_show_pre:nnxxxx { LaTeX / kernel } { show-coffin }
17356     { \token_to_str:N #1 }
17357     { \dim_eval:n { \coffin_ht:N #1 } }
17358     { \dim_eval:n { \coffin_dp:N #1 } }
17359     { \dim_eval:n { \coffin_wd:N #1 } }
17360     \__msg_show_wrap:n
17361     {
17362       \prop_map_function:cN
17363         { l__coffin_poles_ \__int_value:w #1 _prop }
17364         \__msg_show_item_unbraced:nn
17365     }
17366   }
17367 }
17368 \cs_generate_variant:Nn \coffin_show_structure:N { c }

```

(End definition for `\coffin_show_structure:N`. This function is documented on page 203.)

`\coffin_log_structure:N` Redirect output of `\coffin_show_structure:N` to the log.

`\coffin_log_structure:c`

```

17369 \cs_new_protected:Npn \coffin_log_structure:N
17370 { \__msg_log_next: \coffin_show_structure:N }
17371 \cs_generate_variant:Nn \coffin_log_structure:N { c }

```

(End definition for `\coffin_log_structure:N`. This function is documented on page 203.)

34.8 Messages

```

17372 \__msg_kernel_new:nnnn { kernel } { no-pole-intersection }
17373 { No~intersection~between~coffin~poles. }
17374 {
17375   \c__msg_coding_error_text_tl
17376   LaTeX~was~asked~to~find~the~intersection~between~two~poles,~
17377   but~they~do~not~have~a~unique~meeting~point:~
17378   the~value~(0~pt,~0~pt)~will~be~used.
17379 }

```

```

17380 \__msg_kernel_new:nnnn { kernel } { unknown-coffin }
17381 { Unknown-coffin~'#1'. }
17382 { The-coffin~'#1'~was~never~defined. }
17383 \__msg_kernel_new:nnnn { kernel } { unknown-coffin-pole }
17384 { Pole~'#1'~unknown-for-coffin~'#2'. }
17385 {
17386   \c__msg_coding_error_text_tl
17387   LaTeX~was~asked~to~find~a~typesetting~pole~for~a~coffin,~
17388   but~either~the~coffin~does~not~exist~or~the~pole~name~is~wrong.
17389 }
17390 \__msg_kernel_new:nnn { kernel } { show-coffin }
17391 {
17392   Size-of-coffin~#1 : \
17393   > ~ ht~==~#2 \
17394   > ~ dp~==~#3 \
17395   > ~ wd~==~#4 \
17396   Poles-of-coffin~#1 :
17397 }
17398 </initex | package>

```

35 l3color Implementation

```

17399 <*initex | package>

```

\color_group_begin: Grouping for color is almost the same as using the basic `\group_begin:` and `\group_end:` functions. However, in vertical mode the end-of-group needs a `\par`, which in horizontal mode does nothing.

```

17400 \cs_new_eq:NN \color_group_begin: \group_begin:
17401 \cs_new_protected:Npn \color_group_end:
17402 {
17403   \tex_par:D
17404   \group_end:
17405 }

```

(End definition for \color_group_begin: and \color_group_end:. These functions are documented on page 204.)

\color_ensure_current: A driver-independent wrapper for setting the foreground color to the current color “now”.

```

17406 <*initex>
17407 \cs_new_protected:Npn \color_ensure_current:
17408 { \__driver_color_ensure_current: }
17409 </initex>

```

In package mode, the driver code may not be loaded. To keep down dependencies, if there is no driver code available and no `\set@color` then color is not in use and this function can be a no-op.

```

17410 <*package>
17411 \cs_new_protected:Npn \color_ensure_current: { }
17412 \AtBeginDocument
17413 {
17414   \cs_if_exist:NTF \__driver_color_ensure_current:
17415   {
17416     \cs_set_protected:Npn \color_ensure_current:
17417     { \__driver_color_ensure_current: }

```

```

17418     }
17419     {
17420         \cs_if_exist:NT \set@color
17421         {
17422             \cs_set_protected:Npn \color_ensure_current:
17423             { \set@color }
17424         }
17425     }
17426 }
17427 \</package>

```

(End definition for `\color_ensure_current:`. This function is documented on page 204.)

```

17428 \</initex | package>

```

36 l3sys implementation

```

17429 \<*initex | package>

```

36.1 The name of the job

`\c_sys_jobname_str` Inherited from the L^AT_EX3 name for the primitive: this needs to actually contain the text of the job name rather than the name of the primitive, of course.

```

17430 \<*initex>
17431 \tex_everyjob:D \exp_after:wN
17432 {
17433     \tex_the:D \tex_everyjob:D
17434     \str_const:Nx \c_sys_jobname_str { \tex_jobname:D }
17435 }
17436 \</initex>
17437 \<*package>
17438 \str_const:Nx \c_sys_jobname_str { \tex_jobname:D }
17439 \</package>

```

(End definition for `\c_sys_jobname_str`. This variable is documented on page 205.)

36.2 Time and date

`\c_sys_minute_int` Copies of the information provided by T_EX

```

\c_sys_hour_int 17440 \int_const:Nn \c_sys_minute_int
\c_sys_day_int   17441 { \int_mod:nn { \tex_time:D } { 60 } }
\c_sys_month_int 17442 \int_const:Nn \c_sys_hour_int
\c_sys_year_int  17443 { \int_div_truncate:nn { \tex_time:D } { 60 } }
17444 \int_const:Nn \c_sys_day_int { \tex_day:D }
17445 \int_const:Nn \c_sys_month_int { \tex_month:D }
17446 \int_const:Nn \c_sys_year_int { \tex_year:D }

```

(End definition for `\c_sys_minute_int` and others. These variables are documented on page 205.)

36.3 Detecting the engine

`\sys_if_engine luatex_p:` Set up the engine tests on the basis exactly one test should be true. Mainly a case of looking for the appropriate marker primitive. For `upTeX`, there is a complexity in that setting `-kanji-internal=sjis` or `-kanji-internal=euc` effective makes it more like `pTeX`. In those cases we therefore report `pTeX` rather than `upTeX`.

```

\sys_if_engine luatex_p:
\sys_if_engine luatex:TF
\sys_if_engine pdftex_p:
\sys_if_engine pdftex:TF
  \sys_if_engine ptex_p:
  \sys_if_engine ptex:TF
\sys_if_engine uptex_p:
\sys_if_engine uptex:TF
\sys_if_engine xetex_p:
\sys_if_engine xetex:TF
  \c_sys_engine_str
17447 \clist_map_inline:nn { lua , pdf , p , up , xe }
17448 {
17449   \cs_new_eq:cN { sys_if_engine_ #1 tex:T } \use_none:n
17450   \cs_new_eq:cN { sys_if_engine_ #1 tex:F } \use_n:
17451   \cs_new_eq:cN { sys_if_engine_ #1 tex:TF } \use_ii:nn
17452   \cs_new_eq:cN { sys_if_engine_ #1 tex_p: } \c_false_bool
17453 }
17454 \cs_if_exist:NT \luatex luatexversion:D
17455 {
17456   \cs_gset_eq:NN \sys_if_engine luatex:T \use_n:
17457   \cs_gset_eq:NN \sys_if_engine luatex:F \use_none:n
17458   \cs_gset_eq:NN \sys_if_engine luatex:TF \use_i:nn
17459   \cs_gset_eq:NN \sys_if_engine luatex_p: \c_true_bool
17460   \str_const:Nn \c_sys_engine_str { luatex }
17461 }
17462 \cs_if_exist:NT \pdftex pdftexversion:D
17463 {
17464   \cs_gset_eq:NN \sys_if_engine pdftex:T \use_n:
17465   \cs_gset_eq:NN \sys_if_engine pdftex:F \use_none:n
17466   \cs_gset_eq:NN \sys_if_engine pdftex:TF \use_i:nn
17467   \cs_gset_eq:NN \sys_if_engine pdftex_p: \c_true_bool
17468   \str_const:Nn \c_sys_engine_str { pdftex }
17469 }
17470 \cs_if_exist:NT \ptex kanjiskip:D
17471 {
17472   \bool_if:nTF
17473   {
17474     \cs_if_exist_p:N \uptex_disablecjktoken:D &&
17475     \int_compare_p:nNn { \ptex_jis:D "2121 } = { "3000 }
17476   }
17477   {
17478     \cs_gset_eq:NN \sys_if_engine uptex:T \use_n:
17479     \cs_gset_eq:NN \sys_if_engine uptex:F \use_none:n
17480     \cs_gset_eq:NN \sys_if_engine uptex:TF \use_i:nn
17481     \cs_gset_eq:NN \sys_if_engine uptex_p: \c_true_bool
17482     \str_const:Nn \c_sys_engine_str { uptex }
17483   }
17484   {
17485     \cs_gset_eq:NN \sys_if_engine ptex:T \use_n:
17486     \cs_gset_eq:NN \sys_if_engine ptex:F \use_none:n
17487     \cs_gset_eq:NN \sys_if_engine ptex:TF \use_i:nn
17488     \cs_gset_eq:NN \sys_if_engine ptex_p: \c_true_bool
17489     \str_const:Nn \c_sys_engine_str { ptex }
17490   }
17491 }
17492 \cs_if_exist:NT \xetex XeTeXversion:D
17493 {
17494   \cs_gset_eq:NN \sys_if_engine xetex:T \use_n:

```



```

17495 \cs_gset_eq:NN \sys_if_engine_xetex:F \use_none:n
17496 \cs_gset_eq:NN \sys_if_engine_xetex:TF \use_i:nn
17497 \cs_gset_eq:NN \sys_if_engine_xetex_p: \c_true_bool
17498 \str_const:Nn \c_sys_engine_str { xetex }
17499 }

```

(End definition for `\sys_if_engine_luatex:TF` and others. These functions are documented on page 205.)

36.4 Detecting the output

`\sys_if_output_dvi_p:` This is a simple enough concept: the two views here are complementary.

```

\sys_if_output_dvi:TF 17500 \int_compare:nNnTF
\sys_if_output_pdf_p: 17501 { \cs_if_exist_use:NF \pdftex_pdfoutput:D { 0 } } > { 0 }
\sys_if_output_pdf:TF 17502 {
\c_sys_output_str      17503 \cs_new_eq:NN \sys_if_output_dvi:T \use_none:n
17504 \cs_new_eq:NN \sys_if_output_dvi:F \use:n
17505 \cs_new_eq:NN \sys_if_output_dvi:TF \use_ii:nn
17506 \cs_new_eq:NN \sys_if_output_dvi_p: \c_false_bool
17507 \cs_new_eq:NN \sys_if_output_pdf:T \use:n
17508 \cs_new_eq:NN \sys_if_output_pdf:F \use_none:n
17509 \cs_new_eq:NN \sys_if_output_pdf:TF \use_i:nn
17510 \cs_new_eq:NN \sys_if_output_pdf_p: \c_true_bool
17511 \str_const:Nn \c_sys_output_str { pdf }
17512 }
17513 {
17514 \cs_new_eq:NN \sys_if_output_dvi:T \use:n
17515 \cs_new_eq:NN \sys_if_output_dvi:F \use_none:n
17516 \cs_new_eq:NN \sys_if_output_dvi:TF \use_i:nn
17517 \cs_new_eq:NN \sys_if_output_dvi_p: \c_true_bool
17518 \cs_new_eq:NN \sys_if_output_pdf:T \use_none:n
17519 \cs_new_eq:NN \sys_if_output_pdf:F \use:n
17520 \cs_new_eq:NN \sys_if_output_pdf:TF \use_ii:nn
17521 \cs_new_eq:NN \sys_if_output_pdf_p: \c_false_bool
17522 \str_const:Nn \c_sys_output_str { dvi }
17523 }

```

(End definition for `\sys_if_output_dvi:TF`, `\sys_if_output_pdf:TF`, and `\c_sys_output_str`. These functions are documented on page 206.)

```

17524 </initex | package>

```

37 l3deprecation implementation

```

17525 <*initex | package>
17526 <@@=deprecation>

```

`__deprecation_error:Nnn` The `\outer` definition here ensures the command will not appear in an argument. Use this auxiliary on all commands that have been removed since 2015.

```

17527 \cs_new_protected:Npn \__deprecation_error:Nnn #1#2#3
17528 {
17529 \etex_protected:D \tex_outer:D \tex_edef:D #1
17530 {
17531 \exp_not:N \__msg_kernel_expandable_error:nnnnn

```

```

17532         { kernel } { deprecated-command }
17533         { \tl_to_str:n {#3} } { \token_to_str:N #1 } { \tl_to_str:n {#2} }
17534     \exp_not:N \__msg_kernel_error:nnxxx
17535     { kernel } { deprecated-command }
17536     { \tl_to_str:n {#3} } { \token_to_str:N #1 } { \tl_to_str:n {#2} }
17537 }
17538 }
17539 \__deprecation_error:Nnn \c_job_name_tl { \c_sys_jobname_str } { 2017-01-01 }
17540 \__deprecation_error:Nnn \dim_case:nnn { \dim_case:nnF } { 2015-07-14 }
17541 \__deprecation_error:Nnn \int_case:nnn { \int_case:nnF } { 2015-07-14 }
17542 \__deprecation_error:Nnn \int_from_binary:n { \int_from_bin:n } { 2016-01-05 }
17543 \__deprecation_error:Nnn \int_from_hexadecimal:n { \int_from_hex:n } { 2016-01-05 }
17544 \__deprecation_error:Nnn \int_from_octal:n { \int_from_oct:n } { 2016-01-05 }
17545 \__deprecation_error:Nnn \int_to_binary:n { \int_to_bin:n } { 2016-01-05 }
17546 \__deprecation_error:Nnn \int_to_hexadecimal:n { \int_to_hex:n } { 2016-01-05 }
17547 \__deprecation_error:Nnn \int_to_octal:n { \int_to_oct:n } { 2016-01-05 }
17548 \__deprecation_error:Nnn \luaTeX_if_engine_p: { \sys_if_engine_luaTeX_p: } { 2017-01-01 }
17549 \__deprecation_error:Nnn \luaTeX_if_engine:F { \sys_if_engine_luaTeX:F } { 2017-01-01 }
17550 \__deprecation_error:Nnn \luaTeX_if_engine:T { \sys_if_engine_luaTeX:T } { 2017-01-01 }
17551 \__deprecation_error:Nnn \luaTeX_if_engine:TF { \sys_if_engine_luaTeX:TF } { 2017-01-01 }
17552 \__deprecation_error:Nnn \pdfTeX_if_engine_p: { \sys_if_engine_pdfTeX_p: } { 2017-01-01 }
17553 \__deprecation_error:Nnn \pdfTeX_if_engine:F { \sys_if_engine_pdfTeX:F } { 2017-01-01 }
17554 \__deprecation_error:Nnn \pdfTeX_if_engine:T { \sys_if_engine_pdfTeX:T } { 2017-01-01 }
17555 \__deprecation_error:Nnn \pdfTeX_if_engine:TF { \sys_if_engine_pdfTeX:TF } { 2017-01-01 }
17556 \__deprecation_error:Nnn \prop_get:cn { \prop_item:cn } { 2016-01-05 }
17557 \__deprecation_error:Nnn \prop_get:Nn { \prop_item:Nn } { 2016-01-05 }
17558 \__deprecation_error:Nnn \quark_if_recursion_tail_break:N { } { 2015-07-14 }
17559 \__deprecation_error:Nnn \quark_if_recursion_tail_break:n { } { 2015-07-14 }
17560 \__deprecation_error:Nnn \scan_align_safe_stop: { protected-commands } { 2017-01-01 }
17561 \__deprecation_error:Nnn \str_case:nnn { \str_case:nnF } { 2015-07-14 }
17562 \__deprecation_error:Nnn \str_case:onn { \str_case:onF } { 2015-07-14 }
17563 \__deprecation_error:Nnn \str_case:x:nnn { \str_case:x:nnF } { 2015-07-14 }
17564 \__deprecation_error:Nnn \tl_case:cn { \tl_case:cnF } { 2015-07-14 }
17565 \__deprecation_error:Nnn \tl_case:Nnn { \tl_case:NnF } { 2015-07-14 }
17566 \__deprecation_error:Nnn \xetex_if_engine_p: { \sys_if_engine_xetex_p: } { 2017-01-01 }
17567 \__deprecation_error:Nnn \xetex_if_engine:F { \sys_if_engine_xetex:F } { 2017-01-01 }
17568 \__deprecation_error:Nnn \xetex_if_engine:T { \sys_if_engine_xetex:T } { 2017-01-01 }
17569 \__deprecation_error:Nnn \xetex_if_engine:TF { \sys_if_engine_xetex:TF } { 2017-01-01 }

```

(End definition for `__deprecation_error:Nnn`.)

`\deprecation_error:` Some commands were more recently deprecated and not yet removed; only make these into errors if the user requests it. This allows testing code even if it relies on other packages: load all other packages, call `\deprecation_error:`, and load the code that one is interested in testing.

```

17570 \cs_new_protected:Npn \deprecation_error:
17571 {
17572     \__deprecation_error:Nnn \tl_to_lowercase:n { } { 2017-12-31 }
17573     \__deprecation_error:Nnn \tl_to_uppercase:n { } { 2017-12-31 }
17574     \__deprecation_error:Nnn \ior_get_str:NN { \ior_str_get:NN } { 2017-12-31 }
17575     \__deprecation_error:Nnn \c_minus_one { - 1 } { 2018-12-31 }
17576     \__deprecation_error:Nnn \sort_ordered: { \sort_return_same: } { 2018-12-31 }
17577     \__deprecation_error:Nnn \sort_reversed: { \sort_return_swapped: } { 2018-12-31 }
17578     \cs_set_eq:NN \deprecation_error: \scan_stop:

```

17579 }

(End definition for \deprecation_error:. This function is documented on page ??.)

17580 </initex | package>

38 l3candidates Implementation

17581 <*initex | package>

38.1 Additions to l3box

17582 <@@=box>

38.2 Affine transformations

\l__box_angle_fp When rotating boxes, the angle itself may be needed by the engine-dependent code. This is done using the fp module so that the value is tidied up properly.

17583 \fp_new:N \l__box_angle_fp

(End definition for \l__box_angle_fp.)

\l__box_cos_fp These are used to hold the calculated sine and cosine values while carrying out a rotation.

\l__box_sin_fp 17584 \fp_new:N \l__box_cos_fp

17585 \fp_new:N \l__box_sin_fp

(End definition for \l__box_cos_fp and \l__box_sin_fp.)

\l__box_top_dim These are the positions of the four edges of a box before manipulation.

\l__box_bottom_dim 17586 \dim_new:N \l__box_top_dim

\l__box_left_dim 17587 \dim_new:N \l__box_bottom_dim

\l__box_right_dim 17588 \dim_new:N \l__box_left_dim

17589 \dim_new:N \l__box_right_dim

(End definition for \l__box_top_dim and others.)

\l__box_top_new_dim These are the positions of the four edges of a box after manipulation.

\l__box_bottom_new_dim 17590 \dim_new:N \l__box_top_new_dim

\l__box_left_new_dim 17591 \dim_new:N \l__box_bottom_new_dim

\l__box_right_new_dim 17592 \dim_new:N \l__box_left_new_dim

17593 \dim_new:N \l__box_right_new_dim

(End definition for \l__box_top_new_dim and others.)

\l__box_internal_box Scratch space, but also needed by some parts of the driver.

17594 \box_new:N \l__box_internal_box

(End definition for \l__box_internal_box.)




Figure 1: Co-ordinates of a box prior to rotation.

\box_rotate:Nn

Rotation of a box starts with working out the relevant sine and cosine. The actual rotation is in an auxiliary to keep the flow slightly clearer

__box_rotate:N

__box_rotate_x:nnN

__box_rotate_y:nnN

__box_rotate_quadrant_one:

__box_rotate_quadrant_two:

__box_rotate_quadrant_three:

__box_rotate_quadrant_four:

17595 \cs_new_protected:Npn \box_rotate:Nn #1#2

17596 {

17597 \hbox_set:Nn #1

17598 {

17599 \group_begin:

17600 \fp_set:Nn \l__box_angle_fp {#2}

17601 \fp_set:Nn \l__box_sin_fp {sind (\l__box_angle_fp)}

17602 \fp_set:Nn \l__box_cos_fp {cosd (\l__box_angle_fp)}

17603 __box_rotate:N #1

17604 \group_end:

17605 }

17606 }

The edges of the box are then recorded: the left edge will always be at zero. Rotation of the four edges then takes place: this is most efficiently done on a quadrant by quadrant basis.

17607 \cs_new_protected:Npn __box_rotate:N #1

17608 {

17609 \dim_set:Nn \l__box_top_dim { \box_ht:N #1 }

17610 \dim_set:Nn \l__box_bottom_dim { -\box_dp:N #1 }

17611 \dim_set:Nn \l__box_right_dim { \box_wd:N #1 }

17612 \dim_zero:N \l__box_left_dim

The next step is to work out the x and y coordinates of vertices of the rotated box in relation to its original coordinates. The box can be visualized with vertices B , C , D and E is illustrated (Figure 1). The vertex O is the reference point on the baseline, and in this implementation is also the centre of rotation. The formulae are, for a point P and angle α :

$$\begin{aligned} P'_x &= P_x - O_x \\ P'_y &= P_y - O_y \\ P''_x &= (P'_x \cos(\alpha)) - (P'_y \sin(\alpha)) \\ P''_y &= (P'_x \sin(\alpha)) + (P'_y \cos(\alpha)) \\ P'''_x &= P''_x + O_x + L_x \\ P'''_y &= P''_y + O_y \end{aligned}$$

The “extra” horizontal translation L_x at the end is calculated so that the leftmost point of the resulting box has x -coordinate 0. This is desirable as \TeX boxes must have the

reference point at the left edge of the box. (As O is always $(0,0)$, this part of the calculation is omitted here.)

```

17613 \fp_compare:nNnTF \l__box_sin_fp > \c_zero_fp
17614 {
17615     \fp_compare:nNnTF \l__box_cos_fp > \c_zero_fp
17616     { \__box_rotate_quadrant_one: }
17617     { \__box_rotate_quadrant_two: }
17618 }
17619 {
17620     \fp_compare:nNnTF \l__box_cos_fp < \c_zero_fp
17621     { \__box_rotate_quadrant_three: }
17622     { \__box_rotate_quadrant_four: }
17623 }

```

The position of the box edges are now known, but the box at this stage be misplaced relative to the current TeX reference point. So the content of the box is moved such that the reference point of the rotated box will be in the same place as the original.

```

17624 \hbox_set:Nn \l__box_internal_box { \box_use:N #1 }
17625 \hbox_set:Nn \l__box_internal_box
17626 {
17627     \tex_kern:D -\l__box_left_new_dim
17628     \hbox:n
17629     {
17630         \__driver_box_use_rotate:Nn
17631         \l__box_internal_box
17632         \l__box_angle_fp
17633     }
17634 }

```

Tidy up the size of the box so that the material is actually inside the bounding box. The result can then be used to reset the original box.

```

17635 \box_set_ht:Nn \l__box_internal_box { \l__box_top_new_dim }
17636 \box_set_dp:Nn \l__box_internal_box { -\l__box_bottom_new_dim }
17637 \box_set_wd:Nn \l__box_internal_box
17638 { \l__box_right_new_dim - \l__box_left_new_dim }
17639 \box_use:N \l__box_internal_box
17640 }

```

These functions take a general point $(\#1,\#2)$ and rotate its location about the origin, using the previously-set sine and cosine values. Each function gives only one component of the location of the updated point. This is because for rotation of a box each step needs only one value, and so performance is gained by avoiding working out both x' and y' at the same time. Contrast this with the equivalent function in the `l3coffins` module, where both parts are needed.

```

17641 \cs_new_protected:Npn \__box_rotate_x:nnN #1#2#3
17642 {
17643     \dim_set:Nn #3
17644     {
17645         \fp_to_dim:n
17646         {
17647             \l__box_cos_fp * \dim_to_fp:n {#1}
17648             - \l__box_sin_fp * \dim_to_fp:n {#2}
17649         }
17650     }

```

```

17651 }
17652 \cs_new_protected:Npn \__box_rotate_y:nnN #1#2#3
17653 {
17654   \dim_set:Nn #3
17655   {
17656     \fp_to_dim:n
17657     {
17658       \l__box_sin_fp * \dim_to_fp:n {#1}
17659       + \l__box_cos_fp * \dim_to_fp:n {#2}
17660     }
17661   }
17662 }

```

Rotation of the edges is done using a different formula for each quadrant. In every case, the top and bottom edges only need the resulting y -values, whereas the left and right edges need the x -values. Each case is a question of picking out which corner ends up at with the maximum top, bottom, left and right value. Doing this by hand means a lot less calculating and avoids lots of comparisons.

```

17663 \cs_new_protected:Npn \__box_rotate_quadrant_one:
17664 {
17665   \__box_rotate_y:nnN \l__box_right_dim \l__box_top_dim
17666   \l__box_top_new_dim
17667   \__box_rotate_y:nnN \l__box_left_dim \l__box_bottom_dim
17668   \l__box_bottom_new_dim
17669   \__box_rotate_x:nnN \l__box_left_dim \l__box_top_dim
17670   \l__box_left_new_dim
17671   \__box_rotate_x:nnN \l__box_right_dim \l__box_bottom_dim
17672   \l__box_right_new_dim
17673 }
17674 \cs_new_protected:Npn \__box_rotate_quadrant_two:
17675 {
17676   \__box_rotate_y:nnN \l__box_right_dim \l__box_bottom_dim
17677   \l__box_top_new_dim
17678   \__box_rotate_y:nnN \l__box_left_dim \l__box_top_dim
17679   \l__box_bottom_new_dim
17680   \__box_rotate_x:nnN \l__box_right_dim \l__box_top_dim
17681   \l__box_left_new_dim
17682   \__box_rotate_x:nnN \l__box_left_dim \l__box_bottom_dim
17683   \l__box_right_new_dim
17684 }
17685 \cs_new_protected:Npn \__box_rotate_quadrant_three:
17686 {
17687   \__box_rotate_y:nnN \l__box_left_dim \l__box_bottom_dim
17688   \l__box_top_new_dim
17689   \__box_rotate_y:nnN \l__box_right_dim \l__box_top_dim
17690   \l__box_bottom_new_dim
17691   \__box_rotate_x:nnN \l__box_right_dim \l__box_bottom_dim
17692   \l__box_left_new_dim
17693   \__box_rotate_x:nnN \l__box_left_dim \l__box_top_dim
17694   \l__box_right_new_dim
17695 }
17696 \cs_new_protected:Npn \__box_rotate_quadrant_four:
17697 {
17698   \__box_rotate_y:nnN \l__box_left_dim \l__box_top_dim

```

```

17699     \l__box_top_new_dim
17700     \__box_rotate_y:nnN \l__box_right_dim \l__box_bottom_dim
17701     \l__box_bottom_new_dim
17702     \__box_rotate_x:nnN \l__box_left_dim \l__box_bottom_dim
17703     \l__box_left_new_dim
17704     \__box_rotate_x:nnN \l__box_right_dim \l__box_top_dim
17705     \l__box_right_new_dim
17706 }

```

(End definition for `\box_rotate:Nn` and others. These functions are documented on page 210.)

```

\l__box_scale_x_fp Scaling is potentially-different in the two axes.
\l__box_scale_y_fp 17707 \fp_new:N \l__box_scale_x_fp
17708 \fp_new:N \l__box_scale_y_fp

```

(End definition for `\l__box_scale_x_fp` and `\l__box_scale_y_fp`.)

\box_resize:Nnn Resizing a box starts by working out the various dimensions of the existing box.

```

\box_resize:cnn 17709 \cs_new_protected:Npn \box_resize:Nnn #1#2#3
\__box_resize_set_corners:N 17710 {
\__box_resize:N 17711     \hbox_set:Nn #1
\__box_resize:NNN 17712     {
17713         \group_begin:
17714         \__box_resize_set_corners:N #1

```

The x -scaling and resulting box size is easy enough to work out: the dimension is that given as #2, and the scale is simply the new width divided by the old one.

```

17715         \fp_set:Nn \l__box_scale_x_fp
17716         { \dim_to_fp:n {#2} / \dim_to_fp:n { \l__box_right_dim } }

```

The y -scaling needs both the height and the depth of the current box.

```

17717         \fp_set:Nn \l__box_scale_y_fp
17718         {
17719             \dim_to_fp:n {#3}
17720             / \dim_to_fp:n { \l__box_top_dim - \l__box_bottom_dim }
17721         }

```

Hand off to the auxiliary which does the rest of the work.

```

17722         \__box_resize:N #1
17723         \group_end:
17724     }
17725 }
17726 \cs_generate_variant:Nn \box_resize:Nnn { c }
17727 \cs_new_protected:Npn \__box_resize_set_corners:N #1
17728 {
17729     \dim_set:Nn \l__box_top_dim { \box_ht:N #1 }
17730     \dim_set:Nn \l__box_bottom_dim { -\box_dp:N #1 }
17731     \dim_set:Nn \l__box_right_dim { \box_wd:N #1 }
17732     \dim_zero:N \l__box_left_dim
17733 }

```

With at least one real scaling to do, the next phase is to find the new edge co-ordinates. In the x direction this is relatively easy: just scale the right edge. In the y direction, both dimensions have to be scaled, and this again needs the absolute scale value. Once that is all done, the common resize/rescale code can be employed.

```

17734 \cs_new_protected:Npn \__box_resize:N #1

```

```

17735 {
17736   \__box_resize:NNN \l__box_right_new_dim
17737   \l__box_scale_x_fp \l__box_right_dim
17738   \__box_resize:NNN \l__box_bottom_new_dim
17739   \l__box_scale_y_fp \l__box_bottom_dim
17740   \__box_resize:NNN \l__box_top_new_dim
17741   \l__box_scale_y_fp \l__box_top_dim
17742   \__box_resize_common:N #1
17743 }
17744 \cs_new_protected:Npn \__box_resize:NNN #1#2#3
17745 {
17746   \dim_set:Nn #1
17747   { \fp_to_dim:n { \fp_abs:n { #2 } * \dim_to_fp:n { #3 } } }
17748 }

```

(End definition for `\box_resize:Nnn` and others. These functions are documented on page 209.)

| | |
|--|--|
| <code>\box_resize_to_ht:Nn</code> <code>\box_resize_to_ht:cn</code> <code>\box_resize_to_ht_plus_dp:Nn</code> <code>\box_resize_to_ht_plus_dp:cn</code> <code>\box_resize_to_wd:Nn</code> <code>\box_resize_to_wd:cn</code> <code>\box_resize_to_wd_and_ht:Nnn</code> <code>\box_resize_to_wd_and_ht:cnn</code> | <p>Scaling to a (total) height or to a width is a simplified version of the main resizing operation, with the scale simply copied between the two parts. The internal auxiliary is called using the scaling value twice, as the sign for both parts is needed (as this allows the same internal code to be used as for the general case).</p> <pre> 17749 \cs_new_protected:Npn \box_resize_to_ht:Nn #1#2 17750 { 17751 \hbox_set:Nn #1 17752 { 17753 \group_begin: 17754 __box_resize_set_corners:N #1 17755 \fp_set:Nn \l__box_scale_y_fp 17756 { 17757 \dim_to_fp:n {#2} 17758 / \dim_to_fp:n { \l__box_top_dim } 17759 } 17760 \fp_set_eq:NN \l__box_scale_x_fp \l__box_scale_y_fp 17761 __box_resize:N #1 17762 \group_end: 17763 } 17764 } 17765 \cs_generate_variant:Nn \box_resize_to_ht:Nn { c } 17766 \cs_new_protected:Npn \box_resize_to_ht_plus_dp:Nn #1#2 17767 { 17768 \hbox_set:Nn #1 17769 { 17770 \group_begin: 17771 __box_resize_set_corners:N #1 17772 \fp_set:Nn \l__box_scale_y_fp 17773 { 17774 \dim_to_fp:n {#2} 17775 / \dim_to_fp:n { \l__box_top_dim - \l__box_bottom_dim } 17776 } 17777 \fp_set_eq:NN \l__box_scale_x_fp \l__box_scale_y_fp 17778 __box_resize:N #1 17779 \group_end: 17780 } 17781 } </pre> |
|--|--|


```

17782 \cs_generate_variant:Nn \box_resize_to_ht_plus_dp:Nn { c }
17783 \cs_new_protected:Npn \box_resize_to_wd:Nn #1#2
17784 {
17785   \hbox_set:Nn #1
17786   {
17787     \group_begin:
17788       \__box_resize_set_corners:N #1
17789       \fp_set:Nn \l__box_scale_x_fp
17790         { \dim_to_fp:n {#2} / \dim_to_fp:n { \l__box_right_dim } }
17791       \fp_set_eq:NN \l__box_scale_y_fp \l__box_scale_x_fp
17792       \__box_resize:N #1
17793     \group_end:
17794   }
17795 }
17796 \cs_generate_variant:Nn \box_resize_to_wd:Nn { c }
17797 \cs_new_protected:Npn \box_resize_to_wd_and_ht:Nnn #1#2#3
17798 {
17799   \hbox_set:Nn #1
17800   {
17801     \group_begin:
17802       \__box_resize_set_corners:N #1
17803       \fp_set:Nn \l__box_scale_x_fp
17804         { \dim_to_fp:n {#2} / \dim_to_fp:n { \l__box_right_dim } }
17805       \fp_set:Nn \l__box_scale_y_fp
17806       {
17807         \dim_to_fp:n {#3}
17808         / \dim_to_fp:n { \l__box_top_dim }
17809       }
17810       \__box_resize:N #1
17811     \group_end:
17812   }
17813 }
17814 \cs_generate_variant:Nn \box_resize_to_wd_and_ht:Nnn { c }

```

(End definition for `\box_resize_to_ht:Nn` and others. These functions are documented on page 209.)

`\box_scale:Nnn` When scaling a box, setting the scaling itself is easy enough. The new dimensions are also relatively easy to find, allowing only for the need to keep them positive in all cases. Once that is done then after a check for the trivial scaling a hand-off can be made to the common code. The dimension scaling operations are carried out using the TeX mechanism as it avoids needing to use too many fp operations.

`\box_scale:cnn`

```

17815 \cs_new_protected:Npn \box_scale:Nnn #1#2#3
17816 {
17817   \hbox_set:Nn #1
17818   {
17819     \group_begin:
17820       \fp_set:Nn \l__box_scale_x_fp {#2}
17821       \fp_set:Nn \l__box_scale_y_fp {#3}
17822       \dim_set:Nn \l__box_top_dim { \box_ht:N #1 }
17823       \dim_set:Nn \l__box_bottom_dim { -\box_dp:N #1 }
17824       \dim_set:Nn \l__box_right_dim { \box_wd:N #1 }
17825       \dim_zero:N \l__box_left_dim
17826       \dim_set:Nn \l__box_top_new_dim
17827         { \fp_abs:n { \l__box_scale_y_fp } \l__box_top_dim }

```

```

17828         \dim_set:Nn \l__box_bottom_new_dim
17829         { \fp_abs:n { \l__box_scale_y_fp } \l__box_bottom_dim }
17830         \dim_set:Nn \l__box_right_new_dim
17831         { \fp_abs:n { \l__box_scale_x_fp } \l__box_right_dim }
17832         \__box_resize_common:N #1
17833     \group_end:
17834 }
17835 }
17836 \cs_generate_variant:Nn \box_scale:Nnn { c }

```

(End definition for `\box_scale:Nnn`. This function is documented on page 210.)

`__box_resize_common:N` The main resize function places in input into a box which will start of with zero width, and includes the handles for engine rescaling.

```

17837 \cs_new_protected:Npn \__box_resize_common:N #1
17838 {
17839     \hbox_set:Nn \l__box_internal_box
17840     {
17841         \__driver_box_use_scale:Nnn
17842         #1
17843         \l__box_scale_x_fp
17844         \l__box_scale_y_fp
17845     }

```

The new height and depth can be applied directly.

```

17846     \fp_compare:nNnTF \l__box_scale_y_fp > \c_zero_fp
17847     {
17848         \box_set_ht:Nn \l__box_internal_box { \l__box_top_new_dim }
17849         \box_set_dp:Nn \l__box_internal_box { -\l__box_bottom_new_dim }
17850     }
17851     {
17852         \box_set_dp:Nn \l__box_internal_box { \l__box_top_new_dim }
17853         \box_set_ht:Nn \l__box_internal_box { -\l__box_bottom_new_dim }
17854     }

```

Things are not quite as obvious for the width, as the reference point needs to remain unchanged. For positive scaling factors resizing the box is all that is needed. However, for case of a negative scaling the material must be shifted such that the reference point ends up in the right place.

```

17855     \fp_compare:nNnTF \l__box_scale_x_fp < \c_zero_fp
17856     {
17857         \hbox_to_wd:nn { \l__box_right_new_dim }
17858         {
17859             \tex_kern:D \l__box_right_new_dim
17860             \box_use:N \l__box_internal_box
17861             \tex_hss:D
17862         }
17863     }
17864     {
17865         \box_set_wd:Nn \l__box_internal_box { \l__box_right_new_dim }
17866         \hbox:n
17867         {
17868             \tex_kern:D \c_zero_dim
17869             \box_use:N \l__box_internal_box
17870             \tex_hss:D

```

```

17871     }
17872   }
17873 }

```

(End definition for `_box_resize_common:N`.)

38.3 Viewing part of a box

`\box_clip:N` A wrapper around the driver-dependent code.

```

\box_clip:c 17874 \cs_new_protected:Npn \box_clip:N #1
17875   { \hbox_set:Nn #1 { \_driver_box_use_clip:N #1 } }
17876 \cs_generate_variant:Nn \box_clip:N { c }

```

(End definition for `\box_clip:N`. This function is documented on page 210.)

`\box_trim:Nnnnn` Trimming from the left- and right-hand edges of the box is easy: kern the appropriate parts off each side.

`\box_trim:cnnnn`

```

17877 \cs_new_protected:Npn \box_trim:Nnnnn #1#2#3#4#5
17878   {
17879     \hbox_set:Nn \l__box_internal_box
17880     {
17881       \tex_kern:D -\_dim_eval:w #2 \_dim_eval_end:
17882       \box_use:N #1
17883       \tex_kern:D -\_dim_eval:w #4 \_dim_eval_end:
17884     }

```

For the height and depth, there is a need to watch the baseline is respected. Material always has to stay on the correct side, so trimming has to check that there is enough material to trim. First, the bottom edge. If there is enough depth, simply set the depth, or if not move down so the result is zero depth. `\box_move_down:nn` is used in both cases so the resulting box always contains a `\lower` primitive. The internal box is used here as it allows safe use of `\box_set_dp:Nn`.

```

17885   \dim_compare:nNnTF { \box_dp:N #1 } > {#3}
17886   {
17887     \hbox_set:Nn \l__box_internal_box
17888     {
17889       \box_move_down:nn \c_zero_dim
17890       { \box_use:N \l__box_internal_box }
17891     }
17892     \box_set_dp:Nn \l__box_internal_box { \box_dp:N #1 - (#3) }
17893   }
17894   {
17895     \hbox_set:Nn \l__box_internal_box
17896     {
17897       \box_move_down:nn { #3 - \box_dp:N #1 }
17898       { \box_use:N \l__box_internal_box }
17899     }
17900     \box_set_dp:Nn \l__box_internal_box \c_zero_dim
17901   }

```

Same thing, this time from the top of the box.

```

17902   \dim_compare:nNnTF { \box_ht:N \l__box_internal_box } > {#5}
17903   {
17904     \hbox_set:Nn \l__box_internal_box

```

```

17905         {
17906             \box_move_up:nn \c_zero_dim
17907             { \box_use:N \l__box_internal_box }
17908         }
17909         \box_set_ht:Nn \l__box_internal_box
17910         { \box_ht:N \l__box_internal_box - (#5) }
17911     }
17912     {
17913         \hbox_set:Nn \l__box_internal_box
17914         {
17915             \box_move_up:nn { #5 - \box_ht:N \l__box_internal_box }
17916             { \box_use:N \l__box_internal_box }
17917         }
17918         \box_set_ht:Nn \l__box_internal_box \c_zero_dim
17919     }
17920     \box_set_eq:NN #1 \l__box_internal_box
17921 }
17922 \cs_generate_variant:Nn \box_trim:Nnnnn { c }

```

(End definition for `\box_trim:Nnnnn`. This function is documented on page 210.)

`\box_viewport:Nnnnn` The same general logic as for the trim operation, but with absolute dimensions. As a result, there are some things to watch out for in the vertical direction.

`\box_viewport:cnnnn`

```

17923 \cs_new_protected:Npn \box_viewport:Nnnnn #1#2#3#4#5
17924 {
17925     \hbox_set:Nn \l__box_internal_box
17926     {
17927         \tex_kern:D -\__dim_eval:w #2 \__dim_eval_end:
17928         \box_use:N #1
17929         \tex_kern:D \__dim_eval:w #4 - \box_wd:N #1 \__dim_eval_end:
17930     }
17931     \dim_compare:nNnTF {#3} < \c_zero_dim
17932     {
17933         \hbox_set:Nn \l__box_internal_box
17934         {
17935             \box_move_down:nn \c_zero_dim
17936             { \box_use:N \l__box_internal_box }
17937         }
17938         \box_set_dp:Nn \l__box_internal_box { -\dim_eval:n {#3} }
17939     }
17940     {
17941         \hbox_set:Nn \l__box_internal_box
17942         { \box_move_down:nn {#3} { \box_use:N \l__box_internal_box } }
17943         \box_set_dp:Nn \l__box_internal_box \c_zero_dim
17944     }
17945     \dim_compare:nNnTF {#5} > \c_zero_dim
17946     {
17947         \hbox_set:Nn \l__box_internal_box
17948         {
17949             \box_move_up:nn \c_zero_dim
17950             { \box_use:N \l__box_internal_box }
17951         }
17952         \box_set_ht:Nn \l__box_internal_box
17953         {

```

```

17954         #5
17955         \dim_compare:nNnT {#3} > \c_zero_dim
17956         { - (#3) }
17957     }
17958 }
17959 {
17960     \hbox_set:Nn \l__box_internal_box
17961     {
17962         \box_move_up:nn { -\dim_eval:n {#5} }
17963         { \box_use:N \l__box_internal_box }
17964     }
17965     \box_set_ht:Nn \l__box_internal_box \c_zero_dim
17966 }
17967 \box_set_eq:NN #1 \l__box_internal_box
17968 }
17969 \cs_generate_variant:Nn \box_viewport:Nnnnn { c }

```

(End definition for `\box_viewport:Nnnnn`. This function is documented on page 210.)

38.4 Additions to `l3clist`

```

17970 <@@=clist>

```

`\clist_rand_item:n` The N-type function is not implemented through the `n`-type function for efficiency: for instance comma-list variables do not require space-trimming of their items. Even testing for emptiness of an `n`-type comma-list is slow, so we count items first and use that both for the emptiness test and the pseudo-random integer. Importantly, `\clist_item:Nn` and `\clist_item:nn` only evaluate their argument once.

```

17971 \cs_new:Npn \clist_rand_item:n #1
17972 { \exp_args:Nf \__clist_rand_item:nn { \clist_count:n {#1} } {#1} }
17973 \cs_new:Npn \__clist_rand_item:nn #1#2
17974 {
17975     \int_compare:nNnF {#1} = 0
17976     { \clist_item:nn {#2} { \int_rand:nn { 1 } {#1} } }
17977 }
17978 \cs_new:Npn \clist_rand_item:N #1
17979 {
17980     \clist_if_empty:NF #1
17981     { \clist_item:Nn #1 { \int_rand:nn { 1 } { \clist_count:N #1 } } }
17982 }
17983 \cs_generate_variant:Nn \clist_rand_item:N { c }

```

(End definition for `\clist_rand_item:n`, `\clist_rand_item:N`, and `__clist_rand_item:nn`. These functions are documented on page 211.)

38.5 Additions to `l3coffins`

```

17984 <@@=coffin>

```

38.6 Rotating coffins

`\l__coffin_sin_fp` Used for rotations to get the sine and cosine values.

```

\l__coffin_cos_fp
17985 \fp_new:N \l__coffin_sin_fp
17986 \fp_new:N \l__coffin_cos_fp

```

(End definition for \l__coffin_sin_fp and \l__coffin_cos_fp.)

\l__coffin_bounding_prop A property list for the bounding box of a coffin. This is only needed during the rotation, so there is just the one.

```
17987 \prop_new:N \l__coffin_bounding_prop
```

(End definition for \l__coffin_bounding_prop.)

\l__coffin_bounding_shift_dim The shift of the bounding box of a coffin from the real content.

```
17988 \dim_new:N \l__coffin_bounding_shift_dim
```

(End definition for \l__coffin_bounding_shift_dim.)

\l__coffin_left_corner_dim These are used to hold maxima for the various corner values: these thus define the minimum size of the bounding box after rotation.

\l__coffin_right_corner_dim

\l__coffin_bottom_corner_dim

```
17989 \dim_new:N \l__coffin_left_corner_dim
```

```
17990 \dim_new:N \l__coffin_right_corner_dim
```

```
17991 \dim_new:N \l__coffin_bottom_corner_dim
```

```
17992 \dim_new:N \l__coffin_top_corner_dim
```

(End definition for \l__coffin_left_corner_dim and others.)

\coffin_rotate:Nn Rotating a coffin requires several steps which can be conveniently run together. The sine and cosine of the angle in degrees are computed. This is then used to set \l__coffin_sin_fp and \l__coffin_cos_fp, which are carried through unchanged for the rest of the procedure.

\coffin_rotate:cn

```
17993 \cs_new_protected:Npn \coffin_rotate:Nn #1#2
```

```
17994 {
```

```
17995   \fp_set:Nn \l__coffin_sin_fp { sind ( #2 ) }
```

```
17996   \fp_set:Nn \l__coffin_cos_fp { cosd ( #2 ) }
```

The corners and poles of the coffin can now be rotated around the origin. This is best achieved using mapping functions.

```
17997   \prop_map_inline:cn { l__coffin_corners_ \__int_value:w #1 _prop }
```

```
17998   { \__coffin_rotate_corner:Nnnn #1 {##1} ##2 }
```

```
17999   \prop_map_inline:cn { l__coffin_poles_ \__int_value:w #1 _prop }
```

```
18000   { \__coffin_rotate_pole:Nnnnnn #1 {##1} ##2 }
```

The bounding box of the coffin needs to be rotated, and to do this the corners have to be found first. They are then rotated in the same way as the corners of the coffin material itself.

```
18001   \__coffin_set_bounding:N #1
```

```
18002   \prop_map_inline:Nn \l__coffin_bounding_prop
```

```
18003   { \__coffin_rotate_bounding:nnn {##1} ##2 }
```

At this stage, there needs to be a calculation to find where the corners of the content and the box itself will end up.

```
18004   \__coffin_find_corner_maxima:N #1
```

```
18005   \__coffin_find_bounding_shift:
```

```
18006   \box_rotate:Nn #1 {#2}
```

The correction of the box position itself takes place here. The idea is that the bounding box for a coffin is tight up to the content, and has the reference point at the bottom-left. The x -direction is handled by moving the content by the difference in the positions of the bounding box and the content left edge. The y -direction is dealt with by moving the box down by any depth it has acquired. The internal box is used here to allow for the next step.

```

18007 \hbox_set:Nn \l__coffin_internal_box
18008 {
18009   \tex_kern:D
18010   \__dim_eval:w
18011   \l__coffin_bounding_shift_dim - \l__coffin_left_corner_dim
18012   \__dim_eval_end:
18013   \box_move_down:nn { \l__coffin_bottom_corner_dim }
18014   { \box_use:N #1 }
18015 }

```

If there have been any previous rotations then the size of the bounding box will be bigger than the contents. This can be corrected easily by setting the size of the box to the height and width of the content. As this operation requires setting box dimensions and these transcend grouping, the safe way to do this is to use the internal box and to reset the result into the target box.

```

18016 \box_set_ht:Nn \l__coffin_internal_box
18017 { \l__coffin_top_corner_dim - \l__coffin_bottom_corner_dim }
18018 \box_set_dp:Nn \l__coffin_internal_box { 0 pt }
18019 \box_set_wd:Nn \l__coffin_internal_box
18020 { \l__coffin_right_corner_dim - \l__coffin_left_corner_dim }
18021 \hbox_set:Nn #1 { \box_use:N \l__coffin_internal_box }

```

The final task is to move the poles and corners such that they are back in alignment with the box reference point.

```

18022 \prop_map_inline:cn { l__coffin_corners_ \__int_value:w #1 _prop }
18023 { \__coffin_shift_corner:Nnnn #1 {##1} ##2 }
18024 \prop_map_inline:cn { l__coffin_poles_ \__int_value:w #1 _prop }
18025 { \__coffin_shift_pole:Nnnnnn #1 {##1} ##2 }
18026 }
18027 \cs_generate_variant:Nn \coffin_rotate:Nn { c }

```

(End definition for `\coffin_rotate:Nn`. This function is documented on page 211.)

`__coffin_set_bounding:N` The bounding box corners for a coffin are easy enough to find: this is the same code as for the corners of the material itself, but using a dedicated property list.

```

18028 \cs_new_protected:Npn \__coffin_set_bounding:N #1
18029 {
18030   \prop_put:Nnx \l__coffin_bounding_prop { tl }
18031   { { 0 pt } { \dim_eval:n { \box_ht:N #1 } } }
18032   \prop_put:Nnx \l__coffin_bounding_prop { tr }
18033   { { \dim_eval:n { \box_wd:N #1 } } { \dim_eval:n { \box_ht:N #1 } } }
18034   \dim_set:Nn \l__coffin_internal_dim { -\box_dp:N #1 }
18035   \prop_put:Nnx \l__coffin_bounding_prop { bl }
18036   { { 0 pt } { \dim_use:N \l__coffin_internal_dim } }
18037   \prop_put:Nnx \l__coffin_bounding_prop { br }
18038   { { \dim_eval:n { \box_wd:N #1 } } { \dim_use:N \l__coffin_internal_dim } }
18039 }

```

(End definition for _coffin_set_bounding:N.)

_coffin_rotate_bounding:nnn

Rotating the position of the corner of the coffin is just a case of treating this as a vector from the reference point. The same treatment is used for the corners of the material itself and the bounding box.

```

18040 \cs_new_protected:Npn \_coffin_rotate_bounding:nnn #1#2#3
18041 {
18042   \_coffin_rotate_vector:nnNN {#2} {#3} \l__coffin_x_dim \l__coffin_y_dim
18043   \prop_put:Nnx \l__coffin_bounding_prop {#1}
18044   { { \dim_use:N \l__coffin_x_dim } { \dim_use:N \l__coffin_y_dim } }
18045 }
18046 \cs_new_protected:Npn \_coffin_rotate_corner:Nnnn #1#2#3#4
18047 {
18048   \_coffin_rotate_vector:nnNN {#3} {#4} \l__coffin_x_dim \l__coffin_y_dim
18049   \prop_put:cnx { \l__coffin_corners_ \_int_value:w #1 _prop } {#2}
18050   { { \dim_use:N \l__coffin_x_dim } { \dim_use:N \l__coffin_y_dim } }
18051 }

```

(End definition for _coffin_rotate_bounding:nnn and _coffin_rotate_corner:Nnnn.)

_coffin_rotate_pole:Nnnnnn

Rotating a single pole simply means shifting the co-ordinate of the pole and its direction. The rotation here is about the bottom-left corner of the coffin.

```

18052 \cs_new_protected:Npn \_coffin_rotate_pole:Nnnnnn #1#2#3#4#5#6
18053 {
18054   \_coffin_rotate_vector:nnNN {#3} {#4} \l__coffin_x_dim \l__coffin_y_dim
18055   \_coffin_rotate_vector:nnNN {#5} {#6}
18056   \l__coffin_x_prime_dim \l__coffin_y_prime_dim
18057   \_coffin_set_pole:Nnx #1 {#2}
18058   {
18059     { \dim_use:N \l__coffin_x_dim } { \dim_use:N \l__coffin_y_dim }
18060     { \dim_use:N \l__coffin_x_prime_dim }
18061     { \dim_use:N \l__coffin_y_prime_dim }
18062   }
18063 }

```

(End definition for _coffin_rotate_pole:Nnnnnn.)

_coffin_rotate_vector:nnNN

A rotation function, which needs only an input vector (as dimensions) and an output space. The values \l__coffin_cos_fp and \l__coffin_sin_fp should previously have been set up correctly. Working this way means that the floating point work is kept to a minimum: for any given rotation the sin and cosine values do no change, after all.

```

18064 \cs_new_protected:Npn \_coffin_rotate_vector:nnNN #1#2#3#4
18065 {
18066   \dim_set:Nn #3
18067   {
18068     \fp_to_dim:n
18069     {
18070       \dim_to_fp:n {#1} * \l__coffin_cos_fp
18071       - \dim_to_fp:n {#2} * \l__coffin_sin_fp
18072     }
18073   }
18074   \dim_set:Nn #4
18075   {
18076     \fp_to_dim:n

```



```

18077         {
18078             \dim_to_fp:n {#1} * \l__coffin_sin_fp
18079             + \dim_to_fp:n {#2} * \l__coffin_cos_fp
18080         }
18081     }
18082 }

```

(End definition for __coffin_rotate_vector:nnNN.)

_coffin_find_corner_maxima:N
_coffin_find_corner_maxima_aux:nn

The idea here is to find the extremities of the content of the coffin. This is done by looking for the smallest values for the bottom and left corners, and the largest values for the top and right corners. The values start at the maximum dimensions so that the case where all are positive or all are negative works out correctly.

```

18083 \cs_new_protected:Npn \__coffin_find_corner_maxima:N #1
18084 {
18085     \dim_set:Nn \l__coffin_top_corner_dim { -\c_max_dim }
18086     \dim_set:Nn \l__coffin_right_corner_dim { -\c_max_dim }
18087     \dim_set:Nn \l__coffin_bottom_corner_dim { \c_max_dim }
18088     \dim_set:Nn \l__coffin_left_corner_dim { \c_max_dim }
18089     \prop_map_inline:cn { l__coffin_corners_ \__int_value:w #1 _prop }
18090     { \__coffin_find_corner_maxima_aux:nn ##2 }
18091 }
18092 \cs_new_protected:Npn \__coffin_find_corner_maxima_aux:nn #1#2
18093 {
18094     \dim_set:Nn \l__coffin_left_corner_dim
18095     { \dim_min:nn { \l__coffin_left_corner_dim } {#1} }
18096     \dim_set:Nn \l__coffin_right_corner_dim
18097     { \dim_max:nn { \l__coffin_right_corner_dim } {#1} }
18098     \dim_set:Nn \l__coffin_bottom_corner_dim
18099     { \dim_min:nn { \l__coffin_bottom_corner_dim } {#2} }
18100     \dim_set:Nn \l__coffin_top_corner_dim
18101     { \dim_max:nn { \l__coffin_top_corner_dim } {#2} }
18102 }

```

(End definition for __coffin_find_corner_maxima:N and __coffin_find_corner_maxima_aux:nn.)

_coffin_find_bounding_shift:
_coffin_find_bounding_shift_aux:nn

The approach to finding the shift for the bounding box is similar to that for the corners. However, there is only one value needed here and a fixed input property list, so things are a bit clearer.

```

18103 \cs_new_protected:Npn \__coffin_find_bounding_shift:
18104 {
18105     \dim_set:Nn \l__coffin_bounding_shift_dim { \c_max_dim }
18106     \prop_map_inline:Nn \l__coffin_bounding_prop
18107     { \__coffin_find_bounding_shift_aux:nn ##2 }
18108 }
18109 \cs_new_protected:Npn \__coffin_find_bounding_shift_aux:nn #1#2
18110 {
18111     \dim_set:Nn \l__coffin_bounding_shift_dim
18112     { \dim_min:nn { \l__coffin_bounding_shift_dim } {#1} }
18113 }

```

(End definition for __coffin_find_bounding_shift: and __coffin_find_bounding_shift_aux:nn.)

`__coffin_shift_corner:Nnnn` Shifting the corners and poles of a coffin means subtracting the appropriate values from the x - and y -components. For the poles, this means that the direction vector is unchanged.

```

18114 \cs_new_protected:Npn \__coffin_shift_corner:Nnnn #1#2#3#4
18115 {
18116   \prop_put:cnx { l__coffin_corners_ \__int_value:w #1 _ prop } {#2}
18117   {
18118     { \dim_eval:n { #3 - \l__coffin_left_corner_dim } }
18119     { \dim_eval:n { #4 - \l__coffin_bottom_corner_dim } }
18120   }
18121 }
18122 \cs_new_protected:Npn \__coffin_shift_pole:Nnnnnn #1#2#3#4#5#6
18123 {
18124   \prop_put:cnx { l__coffin_poles_ \__int_value:w #1 _ prop } {#2}
18125   {
18126     { \dim_eval:n { #3 - \l__coffin_left_corner_dim } }
18127     { \dim_eval:n { #4 - \l__coffin_bottom_corner_dim } }
18128     {#5} {#6}
18129   }
18130 }

```

(End definition for `__coffin_shift_corner:Nnnn` and `__coffin_shift_pole:Nnnnnn`.)

38.7 Resizing coffins

`\l__coffin_scale_x_fp` Storage for the scaling factors in x and y , respectively.
`\l__coffin_scale_y_fp`

```

18131 \fp_new:N \l__coffin_scale_x_fp
18132 \fp_new:N \l__coffin_scale_y_fp

```

(End definition for `\l__coffin_scale_x_fp` and `\l__coffin_scale_y_fp`.)

`\l__coffin_scaled_total_height_dim` When scaling, the values given have to be turned into absolute values.
`\l__coffin_scaled_width_dim`

```

18133 \dim_new:N \l__coffin_scaled_total_height_dim
18134 \dim_new:N \l__coffin_scaled_width_dim

```

(End definition for `\l__coffin_scaled_total_height_dim` and `\l__coffin_scaled_width_dim`.)

`\coffin_resize:Nnn` Resizing a coffin begins by setting up the user-friendly names for the dimensions of the coffin box. The new sizes are then turned into scale factor. This is the same operation as takes place for the underlying box, but that operation is grouped and so the same calculation is done here.
`\coffin_resize:cnn`

```

18135 \cs_new_protected:Npn \coffin_resize:Nnn #1#2#3
18136 {
18137   \fp_set:Nn \l__coffin_scale_x_fp
18138   { \dim_to_fp:n {#2} / \dim_to_fp:n { \coffin_wd:N #1 } }
18139   \fp_set:Nn \l__coffin_scale_y_fp
18140   {
18141     \dim_to_fp:n {#3}
18142     / \dim_to_fp:n { \coffin_ht:N #1 + \coffin_dp:N #1 }
18143   }
18144   \box_resize:Nnn #1 {#2} {#3}
18145   \__coffin_resize_common:Nnn #1 {#2} {#3}
18146 }
18147 \cs_generate_variant:Nn \coffin_resize:Nnn { c }

```

(End definition for `\coffin_resize:Nnn`. This function is documented on page 211.)

`__coffin_resize_common:Nnn` The poles and corners of the coffin are scaled to the appropriate places before actually resizing the underlying box.

```

18148 \cs_new_protected:Npn \__coffin_resize_common:Nnn #1#2#3
18149 {
18150   \prop_map_inline:cn { l__coffin_corners_ \__int_value:w #1 _prop }
18151   { \__coffin_scale_corner:Nnnn #1 {##1} ##2 }
18152   \prop_map_inline:cn { l__coffin_poles_ \__int_value:w #1 _prop }
18153   { \__coffin_scale_pole:Nnnnnn #1 {##1} ##2 }

```

Negative x -scaling values will place the poles in the wrong location: this is corrected here.

```

18154   \fp_compare:nNnT \l__coffin_scale_x_fp < \c_zero_fp
18155   {
18156     \prop_map_inline:cn { l__coffin_corners_ \__int_value:w #1 _prop }
18157     { \__coffin_x_shift_corner:Nnnn #1 {##1} ##2 }
18158     \prop_map_inline:cn { l__coffin_poles_ \__int_value:w #1 _prop }
18159     { \__coffin_x_shift_pole:Nnnnnn #1 {##1} ##2 }
18160   }
18161 }

```

(End definition for `__coffin_resize_common:Nnn`.)

`\coffin_scale:Nnn` For scaling, the opposite calculation is done to find the new dimensions for the coffin.
`\coffin_scale:cnn` Only the total height is needed, as this is the shift required for corners and poles. The scaling is done the T_EX way as this works properly with floating point values without needing to use the `fp` module.

```

18162 \cs_new_protected:Npn \coffin_scale:Nnn #1#2#3
18163 {
18164   \fp_set:Nn \l__coffin_scale_x_fp {#2}
18165   \fp_set:Nn \l__coffin_scale_y_fp {#3}
18166   \box_scale:Nnn #1 { \l__coffin_scale_x_fp } { \l__coffin_scale_y_fp }
18167   \dim_set:Nn \l__coffin_internal_dim
18168   { \coffin_ht:N #1 + \coffin_dp:N #1 }
18169   \dim_set:Nn \l__coffin_scaled_total_height_dim
18170   { \fp_abs:n { \l__coffin_scale_y_fp } \l__coffin_internal_dim }
18171   \dim_set:Nn \l__coffin_scaled_width_dim
18172   { -\fp_abs:n { \l__coffin_scale_x_fp } \coffin_wd:N #1 }
18173   \__coffin_resize_common:Nnn #1
18174   { \l__coffin_scaled_width_dim } { \l__coffin_scaled_total_height_dim }
18175 }
18176 \cs_generate_variant:Nn \coffin_scale:Nnn { c }

```

(End definition for `\coffin_scale:Nnn`. This function is documented on page 211.)

`__coffin_scale_vector:nnNN` This functions scales a vector from the origin using the pre-set scale factors in x and y . This is a much less complex operation than rotation, and as a result the code is a lot clearer.

```

18177 \cs_new_protected:Npn \__coffin_scale_vector:nnNN #1#2#3#4
18178 {
18179   \dim_set:Nn #3
18180   { \fp_to_dim:n { \dim_to_fp:n {#1} * \l__coffin_scale_x_fp } }
18181   \dim_set:Nn #4

```

```

18182     { \fp_to_dim:n { \dim_to_fp:n {#2} * \l__coffin_scale_y_fp } }
18183   }

```

(End definition for `__coffin_scale_vector:nnNN`.)

`__coffin_scale_corner:Nnnn` Scaling both corners and poles is a simple calculation using the preceding vector scaling.

```

\__coffin_scale_pole:Nnnnnn
18184 \cs_new_protected:Npn \__coffin_scale_corner:Nnnn #1#2#3#4
18185 {
18186   \__coffin_scale_vector:nnNN {#3} {#4} \l__coffin_x_dim \l__coffin_y_dim
18187   \prop_put:cnx { l__coffin_corners_ \__int_value:w #1 _prop } {#2}
18188   { { \dim_use:N \l__coffin_x_dim } { \dim_use:N \l__coffin_y_dim } }
18189 }
18190 \cs_new_protected:Npn \__coffin_scale_pole:Nnnnnn #1#2#3#4#5#6
18191 {
18192   \__coffin_scale_vector:nnNN {#3} {#4} \l__coffin_x_dim \l__coffin_y_dim
18193   \__coffin_set_pole:Nnx #1 {#2}
18194   {
18195     { \dim_use:N \l__coffin_x_dim } { \dim_use:N \l__coffin_y_dim }
18196     {#5} {#6}
18197   }
18198 }

```

(End definition for `__coffin_scale_corner:Nnnn` and `__coffin_scale_pole:Nnnnnn`.)

`__coffin_x_shift_corner:Nnnn` These functions correct for the x displacement that takes place with a negative horizontal
`__coffin_x_shift_pole:Nnnnnn` scaling.

```

18199 \cs_new_protected:Npn \__coffin_x_shift_corner:Nnnn #1#2#3#4
18200 {
18201   \prop_put:cnx { l__coffin_corners_ \__int_value:w #1 _prop } {#2}
18202   {
18203     { \dim_eval:n { #3 + \box_wd:N #1 } } {#4}
18204   }
18205 }
18206 \cs_new_protected:Npn \__coffin_x_shift_pole:Nnnnnn #1#2#3#4#5#6
18207 {
18208   \prop_put:cnx { l__coffin_poles_ \__int_value:w #1 _prop } {#2}
18209   {
18210     { \dim_eval:n { #3 + \box_wd:N #1 } } {#4}
18211     {#5} {#6}
18212   }
18213 }

```

(End definition for `__coffin_x_shift_corner:Nnnn` and `__coffin_x_shift_pole:Nnnnnn`.)

38.8 Additions to l3file

```

18214 <@@=file>

```

`\file_if_exist_input:nTF` Input of a file with a test for existence cannot be done the usual way as the tokens to insert are in an odd place.

```

18215 \cs_new_protected:Npn \file_if_exist_input:n #1
18216 {
18217   \file_if_exist:nT {#1}
18218   { \__file_input:V \l__file_internal_name_tl }
18219 }

```

```

18220 \cs_new_protected:Npn \file_if_exist_input:nT #1#2
18221 {
18222     \file_if_exist:nT {#1}
18223     {
18224         #2
18225         \__file_input:V \l__file_internal_name_tl
18226     }
18227 }
18228 \cs_new_protected:Npn \file_if_exist_input:nF #1
18229 {
18230     \file_if_exist:nTF {#1}
18231     { \__file_input:V \l__file_internal_name_tl }
18232 }
18233 \cs_new_protected:Npn \file_if_exist_input:nTF #1#2
18234 {
18235     \file_if_exist:nTF {#1}
18236     {
18237         #2
18238         \__file_input:V \l__file_internal_name_tl
18239     }
18240 }

```

(End definition for \file_if_exist_input:nTF. This function is documented on page 211.)

```

18241 <@@=ior>

```

\ior_map_break: Usual map breaking functions. Those are not yet in l3kernel proper since the mapping below is the first of its kind.

```

18242 \cs_new:Npn \ior_map_break:
18243 { \__prg_map_break:Nn \ior_map_break: { } }
18244 \cs_new:Npn \ior_map_break:n
18245 { \__prg_map_break:Nn \ior_map_break: }

```

(End definition for \ior_map_break: and \ior_map_break:n. These functions are documented on page 212.)

\ior_map_inline:Nn Mapping to an input stream can be done on either a token or a string basis, hence the set up. Within that, there is a check to avoid reading past the end of a file, hence the two applications of \ior_if_eof:N. This mapping cannot be nested as the stream has only one “current line”.

```

\ior_str_map_inline:Nn
\__ior_map_inline:NNn
\__ior_map_inline:NNNn
\__ior_map_inline_loop:NNN
\l__ior_internal_tl
18246 \cs_new_protected:Npn \ior_map_inline:Nn
18247 { \__ior_map_inline:NNn \ior_get:NN }
18248 \cs_new_protected:Npn \ior_str_map_inline:Nn
18249 { \__ior_map_inline:NNn \ior_str_get:NN }
18250 \cs_new_protected:Npn \__ior_map_inline:NNn
18251 {
18252     \int_gincr:N \g__prg_map_int
18253     \exp_args:Nc \__ior_map_inline:NNNn
18254     { __prg_map_ \int_use:N \g__prg_map_int :n }
18255 }
18256 \cs_new_protected:Npn \__ior_map_inline:NNNn #1#2#3#4
18257 {
18258     \cs_set:Npn #1 ##1 {#4}
18259     \ior_if_eof:NF #3 { \__ior_map_inline_loop:NNN #1#2#3 }
18260     \__prg_break_point:Nn \ior_map_break:

```

```

18261     { \int_gdecr:N \g__prg_map_int }
18262   }
18263 \cs_new_protected:Npn \__ior_map_inline_loop:NNN #1#2#3
18264 {
18265   #2 #3 \l__ior_internal_tl
18266   \ior_if_eof:NF #3
18267   {
18268     \exp_args:No #1 \l__ior_internal_tl
18269     \__ior_map_inline_loop:NNN #1#2#3
18270   }
18271 }
18272 \tl_new:N \l__ior_internal_tl

```

(End definition for `\ior_map_inline:Nn` and others. These functions are documented on page 211.)

\ior_log_streams: Redirect output of `\ior_list_streams:` to the log.

```

18273 \cs_new_protected:Npn \ior_log_streams:
18274 { \__msg_log_next: \ior_list_streams: }

```

(End definition for `\ior_log_streams:.` This function is documented on page 213.)

```

18275 <@@=iow>

```

\iow_log_streams: Redirect output of `\iow_list_streams:` to the log.

```

18276 \cs_new_protected:Npn \iow_log_streams:
18277 { \__msg_log_next: \iow_list_streams: }

```

(End definition for `\iow_log_streams:.` This function is documented on page 213.)

38.9 Additions to `l3int`

```

18278 <@@=int>

```

\int_rand:nn Evaluate the argument and filter out the case where the lower bound `#1` is more than the upper bound `#2`. Then determine whether the range is narrower than `\c__fp_rand_size_int`; `#2-#1` may overflow for very large positive `#2` and negative `#1`. If the range is wide, use slower code from `l3fp`. If the range is narrow, call `__int_rand_narrow:nn` `{<choices>}` `{#1}` where `<choices>` is the number of possible outcomes. Then `__int_rand_narrow:nnnn` receives a random number reduced modulo `<choices>`, the random number itself, `<choices>` and `#1`. To avoid bias, throw away the random number if it lies in the last, incomplete, interval of size `<choices>` in `[0, \c__fp_rand_size_int - 1]`, and try again.

```

18279 \cs_if_exist:NTF \pdfTeX_uniformdeviate:D
18280 {
18281   \cs_new:Npn \int_rand:nn #1#2
18282   {
18283     \exp_after:wN \__int_rand:ww
18284     \__int_value:w \__int_eval:w #1 \exp_after:wN ;
18285     \__int_value:w \__int_eval:w #2 ;
18286   }
18287   \cs_new:Npn \__int_rand:ww #1; #2;
18288   {
18289     \int_compare:nNnTF {#1} > {#2}
18290     {
18291       \__msg_kernel_expandable_error:nnnn

```

```

18292         { kernel } { backward-range } {#1} {#2}
18293         \__int_rand:ww #2; #1;
18294     }
18295     {
18296         \int_compare:nNnTF {#1} > 0
18297         { \int_compare:nNnTF { #2 - #1 } < \c__fp_rand_size_int }
18298         { \int_compare:nNnTF {#2} < { #1 + \c__fp_rand_size_int } }
18299         {
18300             \exp_args:Nf \__int_rand_narrow:nn
18301             { \int_eval:n { #2 - #1 + 1 } } {#1}
18302         }
18303         { \fp_to_int:n { randint(#1,#2) } }
18304     }
18305 }
18306 \cs_new:Npn \__int_rand_narrow:nn
18307 {
18308     \exp_args:No \__int_rand_narrow:nnn
18309     { \pdfTeX_uniformdeviate:D \c__fp_rand_size_int }
18310 }
18311 \cs_new:Npn \__int_rand_narrow:nnn #1#2
18312 {
18313     \exp_args:Nf \__int_rand_narrow:nnnn
18314     { \int_mod:nn {#1} {#2} } {#1} {#2}
18315 }
18316 \cs_new:Npn \__int_rand_narrow:nnnn #1#2#3#4
18317 {
18318     \int_compare:nNnTF { #2 - #1 + #3 } > \c__fp_rand_size_int
18319     { \__int_rand_narrow:nn {#3} {#4} }
18320     { \int_eval:n { #4 + #1 } }
18321 }
18322 }
18323 {
18324     \cs_new:Npn \int_rand:nn #1#2
18325     {
18326         \_msg_kernel_expandable_error:nn { kernel } { fp-no-random }
18327         \int_eval:n {#1}
18328     }
18329 }

```

(End definition for `\int_rand:nn` and others. These functions are documented on page 213.)

The following must be added to `l3msg`.

```

18330 \cs_if_exist:NT \pdfTeX_uniformdeviate:D
18331 {
18332     \_msg_kernel_new:nnn { kernel } { backward-range }
18333     { Bounds~ordered~backwards~in~\int_rand:nn {#1}~{#2}. }
18334 }

```

38.10 Additions to `l3msg`

```
18335 <@@=msg>
```

Pass to an auxiliary the message to display and the module name

```

18336 \cs_new:Npn \msg_expandable_error:nnnnnn #1#2#3#4#5#6
18337 {

```

```

\msg_expandable_error:nnnnnn
\msg_expandable_error:nnffff
\msg_expandable_error:nnnnn
\msg_expandable_error:nnfff
\msg_expandable_error:nnnn
\msg_expandable_error:nnff
\msg_expandable_error:nnn
\msg_expandable_error:nnf
\msg_expandable_error:nn
\msg_expandable_error:nn
\__msg_expandable_error_module:nn

```

```

18338 \exp_args:Nf \_msg_expandable_error_module:nn
18339 {
18340   \exp_args:Nf \tl_to_str:n
18341   { \use:c { \c__msg_text_prefix_tl #1 / #2 } {#3} {#4} {#5} {#6} }
18342 }
18343 {#1}
18344 }
18345 \cs_new:Npn \msg_expandable_error:nnnnn #1#2#3#4#5
18346 { \msg_expandable_error:nnnnnn {#1} {#2} {#3} {#4} {#5} { } }
18347 \cs_new:Npn \msg_expandable_error:nnnn #1#2#3#4
18348 { \msg_expandable_error:nnnnnn {#1} {#2} {#3} {#4} { } { } }
18349 \cs_new:Npn \msg_expandable_error:nnn #1#2#3
18350 { \msg_expandable_error:nnnnnn {#1} {#2} {#3} { } { } { } }
18351 \cs_new:Npn \msg_expandable_error:nn #1#2
18352 { \msg_expandable_error:nnnnnn {#1} {#2} { } { } { } { } }
18353 \cs_generate_variant:Nn \msg_expandable_error:nnnnnn { nnffff }
18354 \cs_generate_variant:Nn \msg_expandable_error:nnnnnn { nnfff }
18355 \cs_generate_variant:Nn \msg_expandable_error:nnnnnn { nnff }
18356 \cs_generate_variant:Nn \msg_expandable_error:nnnnnn { nnf }
18357 \cs_new:Npn \_msg_expandable_error_module:nn #1#2
18358 {
18359   \exp_after:wN \exp_after:wN
18360   \exp_after:wN \use_none_delimit_by_q_stop:w
18361   \use:n { \::error ! ~ #2 : ~ #1 } \q_stop
18362 }

```

(End definition for `\msg_expandable_error:nnnnnn` and others. These functions are documented on page 213.)

38.11 Additions to l3prg

```

18363 <@@=bool>

```

`\bool_lazy_all_p:n` Go through the list of expressions, stopping whenever an expression is `false`. If the end is reached without finding any `false` expression, then the result is `true`.
`\bool_lazy_all:nTF`
`_bool_lazy_all:n`

```

18364 \prg_new_conditional:Npnn \bool_lazy_all:n #1 { p , T , F , TF }
18365 { \_bool_lazy_all:n #1 \q_recursion_tail \q_recursion_stop }
18366 \cs_new:Npn \_bool_lazy_all:n #1
18367 {
18368   \quark_if_recursion_tail_stop_do:nn {#1} { \prg_return_true: }
18369   \bool_if:nF {#1}
18370   { \use_i_delimit_by_q_recursion_stop:nw { \prg_return_false: } }
18371   \_bool_lazy_all:n
18372 }

```

(End definition for `\bool_lazy_all:nTF` and `_bool_lazy_all:n`. These functions are documented on page 214.)

`\bool_lazy_and_p:nn` Only evaluate the second expression if the first is `true`.

`\bool_lazy_and:nnTF`

```

18373 \prg_new_conditional:Npnn \bool_lazy_and:nn #1#2 { p , T , F , TF }
18374 {
18375   \bool_if:nTF {#1}
18376   { \bool_if:nTF {#2} { \prg_return_true: } { \prg_return_false: } }
18377   { \prg_return_false: }
18378 }

```


(End definition for `\bool_lazy_and:nnTF`. This function is documented on page 214.)

`\bool_lazy_any_p:n` Go through the list of expressions, stopping whenever an expression is `true`. If the end is reached without finding any true expression, then the result is `false`.

`\bool_lazy_any:nTF`
`__bool_lazy_any:n`

```

18379 \prg_new_conditional:Npnn \bool_lazy_any:n #1 { p , T , F , TF }
18380 { \__bool_lazy_any:n #1 \q_recursion_tail \q_recursion_stop }
18381 \cs_new:Npn \__bool_lazy_any:n #1
18382 {
18383   \quark_if_recursion_tail_stop_do:nn {#1} { \prg_return_false: }
18384   \bool_if:nT {#1}
18385   { \use_i_delimit_by_q_recursion_stop:nw { \prg_return_true: } }
18386   \__bool_lazy_any:n
18387 }
```

(End definition for `\bool_lazy_any:nTF` and `__bool_lazy_any:n`. These functions are documented on page 214.)

`\bool_lazy_or_p:n` Only evaluate the second expression if the first is `false`.

`\bool_lazy_or:nnTF`

```

18388 \prg_new_conditional:Npnn \bool_lazy_or:nn #1#2 { p , T , F , TF }
18389 {
18390   \bool_if:nTF {#1}
18391   { \prg_return_true: }
18392   { \bool_if:nTF {#2} { \prg_return_true: } { \prg_return_false: } }
18393 }
```

(End definition for `\bool_lazy_or:nnTF`. This function is documented on page 214.)

38.12 Additions to `l3prop`

18394 `<@@=prop>`

`\prop_count:N` Counting the key–value pairs in a property list is done using the same approach as for other count functions: turn each entry into a `+1` then use integer evaluation to actually do the mathematics.

`\prop_count:c`
`__prop_count:nn`

```

18395 \cs_new:Npn \prop_count:N #1
18396 {
18397   \int_eval:n
18398   {
18399     0
18400     \prop_map_function:NN #1 \__prop_count:nn
18401   }
18402 }
18403 \cs_new:Npn \__prop_count:nn #1#2 { + 1 }
18404 \cs_generate_variant:Nn \prop_count:N { c }
```

(End definition for `\prop_count:N` and `__prop_count:nn`. These functions are documented on page 215.)

`\prop_map_tokens:Nn` The mapping is very similar to `\prop_map_function:NN`. It grabs one key–value pair at a time, and stops when reaching the marker key `\q_recursion_tail`, which cannot appear in normal keys since those are strings. The odd construction `\use:n {#1}` allows `#1` to contain any token without interfering with `\prop_map_break:.` Argument `#2` of `__prop_map_tokens:nwn` is `\s__prop` the first time, and is otherwise empty.

18405 `\cs_new:Npn \prop_map_tokens:Nn #1#2`

```

18406 {
18407   \exp_last_unbraced:Nno \__prop_map_tokens:nwnn {#2} #1
18408   \__prop_pair:wn \q_recursion_tail \s__prop { }
18409   \__prg_break_point:Nn \prop_map_break: { }
18410 }
18411 \cs_new:Npn \__prop_map_tokens:nwnn #1#2 \__prop_pair:wn #3 \s__prop #4
18412 {
18413   \if_meaning:w \q_recursion_tail #3
18414   \exp_after:wN \prop_map_break:
18415   \fi:
18416   \use:n {#1} {#3} {#4}
18417   \__prop_map_tokens:nwnn {#1}
18418 }
18419 \cs_generate_variant:Nn \prop_map_tokens:Nn { c }

```

(End definition for `\prop_map_tokens:Nn` and `__prop_map_tokens:nwnn`. These functions are documented on page 215.)

`\prop_rand_key_value:N`
`\prop_rand_key_value:c`
`__prop_rand:NN`
`__prop_rand_item:Nw`

Contrarily to `clist`, `seq` and `tl`, there is no function to get an item of a `prop` given an integer between 1 and the number of items, so we write the appropriate code. There is no bounds checking because `\int_rand:nn` is always within bounds. At the end, leave either the key #3 or the value #4 in the input stream.

```

18420 \cs_new:Npn \prop_rand_key_value:N { \__prop_rand:NN \__prop_rand:nNn }
18421 \cs_new:Npn \__prop_rand:nNn #1#2#3 { \exp_not:n { {#1} {#3} } }
18422 \cs_new:Npn \__prop_rand:NN #1#2
18423 {
18424   \prop_if_empty:NTF #2 { }
18425   {
18426     \exp_after:wN \__prop_rand_item:Nw \exp_after:wN #1
18427     \__int_value:w \int_rand:nn { 1 } { \prop_count:N #2 } #2
18428     \q_stop
18429   }
18430 }
18431 \cs_new:Npn \__prop_rand_item:Nw #1#2 \s__prop \__prop_pair:wn #3 \s__prop #4
18432 {
18433   \int_compare:nNnF {#2} > 1
18434   { \use_i_delimit_by_q_stop:nw { #1 {#3} \exp_not:n {#4} } }
18435   \exp_after:wN \__prop_rand_item:Nw \exp_after:wN #1
18436   \__int_value:w \int_eval:n { #2 - 1 } \s__prop
18437 }
18438 \cs_generate_variant:Nn \prop_rand_key_value:N { c }

```

(End definition for `\prop_rand_key_value:N`, `__prop_rand:NN`, and `__prop_rand_item:Nw`. These functions are documented on page 215.)

38.13 Additions to `l3seq`

18439 `<@@=seq>`

`\seq_mapthread_function:NNN`
`\seq_mapthread_function:NcN`
`\seq_mapthread_function:cNN`
`\seq_mapthread_function:ccN`
`__seq_mapthread_function:wNN`
`__seq_mapthread_function:wNw`
`__seq_mapthread_function:Nnnwnn`

The idea is to first expand both sequences, adding the usual `{ ? __prg_break: } { }` to the end of each one. This is most conveniently done in two steps using an auxiliary function. The mapping then throws away the first tokens of #2 and #5, which for items in the sequences will both be `\s__seq __seq_item:n`. The function to be mapped will then be applied to the two entries. When the code hits the end of one of the sequences,

the break material will stop the entire loop and tidy up. This avoids needing to find the count of the two sequences, or worrying about which is longer.

```

18440 \cs_new:Npn \seq_mapthread_function:NNN #1#2#3
18441 { \exp_after:wN \__seq_mapthread_function:wNN #2 \q_stop #1 #3 }
18442 \cs_new:Npn \__seq_mapthread_function:wNN \s__seq #1 \q_stop #2#3
18443 {
18444   \exp_after:wN \__seq_mapthread_function:wNw #2 \q_stop #3
18445   #1 { ? \__prg_break: } { }
18446   \__prg_break_point:
18447 }
18448 \cs_new:Npn \__seq_mapthread_function:wNw \s__seq #1 \q_stop #2
18449 {
18450   \__seq_mapthread_function:Nnnwnn #2
18451   #1 { ? \__prg_break: } { }
18452   \q_stop
18453 }
18454 \cs_new:Npn \__seq_mapthread_function:Nnnwnn #1#2#3#4 \q_stop #5#6
18455 {
18456   \use_none:n #2
18457   \use_none:n #5
18458   #1 {#3} {#6}
18459   \__seq_mapthread_function:Nnnwnn #1 #4 \q_stop
18460 }
18461 \cs_generate_variant:Nn \seq_mapthread_function:NNN { Nc }
18462 \cs_generate_variant:Nn \seq_mapthread_function:NNN { c , cc }

```

(End definition for `\seq_mapthread_function:NNN` and others. These functions are documented on page 215.)

`\seq_set_filter:NNn` Similar to `\seq_map_inline:Nn`, without a `__prg_break_point:` because the user's code is performed within the evaluation of a boolean expression, and skipping out of that would break horribly. The `__seq_wrap_item:n` function inserts the relevant `__seq_item:n` without expansion in the input stream, hence in the x-expanding assignment.

```

18463 \cs_new_protected:Npn \seq_set_filter:NNn
18464 { \__seq_set_filter:NNNn \tl_set:Nx }
18465 \cs_new_protected:Npn \seq_gset_filter:NNn
18466 { \__seq_set_filter:NNNn \tl_gset:Nx }
18467 \cs_new_protected:Npn \__seq_set_filter:NNNn #1#2#3#4
18468 {
18469   \__seq_push_item_def:n { \bool_if:nT {#4} { \__seq_wrap_item:n {##1} } }
18470   #1 #2 { #3 }
18471   \__seq_pop_item_def:
18472 }

```

(End definition for `\seq_set_filter:NNn`, `\seq_gset_filter:NNn`, and `__seq_set_filter:NNNn`. These functions are documented on page 215.)

`\seq_set_map:NNn` Very similar to `\seq_set_filter:NNn`. We could actually merge the two within a single function, but it would have weird semantics.

```

\seq_gset_map:NNn
\__seq_set_map:NNNn
18473 \cs_new_protected:Npn \seq_set_map:NNn
18474 { \__seq_set_map:NNNn \tl_set:Nx }
18475 \cs_new_protected:Npn \seq_gset_map:NNn
18476 { \__seq_set_map:NNNn \tl_gset:Nx }
18477 \cs_new_protected:Npn \__seq_set_map:NNNn #1#2#3#4

```

```

18478 {
18479   \__seq_push_item_def:n { \exp_not:N \__seq_item:n {#4} }
18480   #1 #2 { #3 }
18481   \__seq_pop_item_def:
18482 }

```

(End definition for `\seq_set_map:NNn`, `\seq_gset_map:NNn`, and `__seq_set_map:NNNn`. These functions are documented on page 216.)

`\seq_rand_item:N` Importantly, `\seq_item:Nn` only evaluates its argument once.

```

\seq_rand_item:c 18483 \cs_new:Npn \seq_rand_item:N #1
18484 {
18485   \seq_if_empty:NF #1
18486   { \seq_item:Nn #1 { \int_rand:nn { 1 } { \seq_count:N #1 } } }
18487 }
18488 \cs_generate_variant:Nn \seq_rand_item:N { c }

```

(End definition for `\seq_rand_item:N`. This function is documented on page 216.)

38.14 Additions to `l3skip`

```

18489 <@@=skip>

```

`\skip_split_finite_else_action:nnNN`

This macro is useful when performing error checking in certain circumstances. If the `<skip>` register holds finite glue it sets `#3` and `#4` to the stretch and shrink component, resp. If it holds infinite glue set `#3` and `#4` to zero and issue the special action `#2` which is probably an error message. Assignments are local.

```

18490 \cs_new:Npn \skip_split_finite_else_action:nnNN #1#2#3#4
18491 {
18492   \skip_if_finite:nTF {#1}
18493   {
18494     #3 = \etex_gluestretch:D #1 \scan_stop:
18495     #4 = \etex_glueshrink:D #1 \scan_stop:
18496   }
18497   {
18498     #3 = \c_zero_skip
18499     #4 = \c_zero_skip
18500     #2
18501   }
18502 }

```

(End definition for `\skip_split_finite_else_action:nnNN`. This function is documented on page 216.)

38.15 Additions to `l3tl`

```

18503 <@@=tl>

```

`\tl_if_single_token_p:n`

`\tl_if_single_token:nTF`

There are four cases: empty token list, token list starting with a normal token, with a brace group, or with a space token. If the token list starts with a normal token, remove it and check for emptiness. For the next case, an empty token list is not a single token. Finally, we have a non-empty token list starting with a space or a brace group. Applying `f`-expansion yields an empty result if and only if the token list is a single space.

```

18504 \prg_new_conditional:Npnn \tl_if_single_token:n #1 { p , T , F , TF }
18505 {
18506   \tl_if_head_is_N_type:nTF {#1}

```

```

18507     { \_tl\_if\_empty\_return:o { \use\_none:n #1 } }
18508     {
18509         \tl\_if\_empty:nTF {#1}
18510         { \prg\_return\_false: }
18511         { \_tl\_if\_empty\_return:o { \exp:w \exp\_end\_continue\_f:w #1 } }
18512     }
18513 }

```

(End definition for `\tl_if_single_token:nTF`. This function is documented on page 216.)

`\tl_reverse_tokens:n` The same as `\tl_reverse:n` but with recursion within brace groups.

```

\__tl\_reverse\_group:nn
18514 \cs\_new:Npn \tl\_reverse\_tokens:n #1
18515 {
18516     \etex\_unexpanded:D \exp\_after:wN
18517     {
18518         \exp:w
18519         \_tl\_act:NNNnn
18520         \_tl\_reverse\_normal:nN
18521         \_tl\_reverse\_group:nn
18522         \_tl\_reverse\_space:n
18523         { }
18524         {#1}
18525     }
18526 }
18527 \cs\_new:Npn \_tl\_reverse\_group:nn #1
18528 {
18529     \_tl\_act\_group\_recurse:Nnn
18530     \_tl\_act\_reverse\_output:n
18531     { \tl\_reverse\_tokens:n }
18532 }

```

In many applications of `_tl_act:NNNnn`, we need to recursively apply some transformation within brace groups, then output. In this code, `#1` is the output function, `#2` is the transformation, which should expand in two steps, and `#3` is the group.

```

18533 \cs\_new:Npn \_tl\_act\_group\_recurse:Nnn #1#2#3
18534 {
18535     \exp\_args:Nf #1
18536     { \exp\_after:wN \exp\_after:wN \exp\_after:wN { #2 {#3} } }
18537 }

```

(End definition for `\tl_reverse_tokens:n`, `_tl_reverse_group:nn`, and `_tl_act_group_recurse:Nnn`. These functions are documented on page 216.)

`\tl_count_tokens:n` The token count is computed through an `\int_eval:n` construction. Each `1+` is output to the *left*, into the integer expression, and the sum is ended by the `\exp_end:` inserted by `_tl_act_end:wN` (which is technically implemented as `\c_zero`). Somewhat a hack!

```

\__tl\_act\_count\_normal:nN
\__tl\_act\_count\_group:nn
\__tl\_act\_count\_space:n
18538 \cs\_new:Npn \tl\_count\_tokens:n #1
18539 {
18540     \int\_eval:n
18541     {
18542         \_tl\_act:NNNnn
18543         \_tl\_act\_count\_normal:nN
18544         \_tl\_act\_count\_group:nn
18545         \_tl\_act\_count\_space:n

```

```

18546         { }
18547         {#1}
18548     }
18549 }
18550 \cs_new:Npn \__tl_act_count_normal:nN #1 #2 { 1 + }
18551 \cs_new:Npn \__tl_act_count_space:n #1 { 1 + }
18552 \cs_new:Npn \__tl_act_count_group:nn #1 #2
18553 { 2 + \tl_count_tokens:n {#2} + }

```

(End definition for `\tl_count_tokens:n` and others. These functions are documented on page 217.)

`\tl_set_from_file:Nnn` The approach here is similar to that for doing a rescan, and so the same internals can be reused. Thus the plan is to insert a pair of tokens of the same charcode but different catcodes after the file has been read. This plus `\exp_not:N` allows the primitive to be used to carry out a set operation.

```

\__tl_set_from_file:NNnn
  \__tl_from_file_do:w
18554 \cs_new_protected:Npn \tl_set_from_file:Nnn
18555 { \__tl_set_from_file:NNnn \tl_set:Nn }
18556 \cs_new_protected:Npn \tl_gset_from_file:Nnn
18557 { \__tl_set_from_file:NNnn \tl_gset:Nn }
18558 \cs_generate_variant:Nn \tl_set_from_file:Nnn { c }
18559 \cs_generate_variant:Nn \tl_gset_from_file:Nnn { c }
18560 \cs_new_protected:Npn \__tl_set_from_file:NNnn #1#2#3#4
18561 {
18562   \__file_if_exist:nT {#4}
18563   {
18564     \group_begin:
18565       \exp_args:No \etex_everyeof:D
18566       { \c__tl_rescan_marker_tl \exp_not:N }
18567       #3 \scan_stop:
18568       \exp_after:wN \__tl_from_file_do:w
18569       \exp_after:wN \prg_do_nothing:
18570       \tex_input:D \l__file_internal_name_tl \scan_stop:
18571       \exp_args:NNNo \group_end:
18572       #1 #2 \l__tl_internal_a_tl
18573   }
18574 }
18575 \exp_args:Nno \use:nn
18576 { \cs_new_protected:Npn \__tl_from_file_do:w #1 }
18577 { \c__tl_rescan_marker_tl }
18578 { \tl_set:No \l__tl_internal_a_tl {#1} }

```

(End definition for `\tl_set_from_file:Nnn` and others. These functions are documented on page 220.)

`\tl_set_from_file_x:Nnn` When reading a file and allowing expansion of the content, the set up only needs to prevent TeX complaining about the end of the file. That is done simply, with a group then used to trap the definition needed. Once the business is done using some scratch space, the tokens can be transferred to the real target.

```

\__tl_set_from_file_x:NNnn
18579 \cs_new_protected:Npn \tl_set_from_file_x:Nnn
18580 { \__tl_set_from_file_x:NNnn \tl_set:Nn }
18581 \cs_new_protected:Npn \tl_gset_from_file_x:Nnn
18582 { \__tl_set_from_file_x:NNnn \tl_gset:Nn }
18583 \cs_generate_variant:Nn \tl_set_from_file_x:Nnn { c }
18584 \cs_generate_variant:Nn \tl_gset_from_file_x:Nnn { c }
18585 \cs_new_protected:Npn \__tl_set_from_file_x:NNnn #1#2#3#4

```

```

18586 {
18587   \__file_if_exist:nT {#4}
18588   {
18589     \group_begin:
18590     \etex_everyeof:D { \exp_not:N }
18591     #3 \scan_stop:
18592     \tl_set:Nx \l__tl_internal_a_tl
18593     { \tex_input:D \l__file_internal_name_tl \c_space_token }
18594     \exp_args:NNNo \group_end:
18595     #1 #2 \l__tl_internal_a_tl
18596   }
18597 }

```

(End definition for `\tl_set_from_file_x:Nnn`, `\tl_gset_from_file_x:Nnn`, and `__tl_set_from_file_x:NNnn`. These functions are documented on page 220.)

38.15.1 Unicode case changing

The mechanisms needed for case changing are somewhat involved, particularly to allow for all of the special cases. These functions also require the appropriate data extracted from the Unicode documentation (either manually or automatically).

`\tl_if_head_eq_catcode:oNTF` Extra variants.

```

18598 \cs_generate_variant:Nn \tl_if_head_eq_catcode:nNTF { o }

```

(End definition for `\tl_if_head_eq_catcode:oNTF`. This function is documented on page 44.)

`\tl_lower_case:n` The user level functions here are all wrappers around the internal functions for case changing. Note that `\tl_mixed_case:nn` could be done without an internal, but this way the logic is slightly clearer as everything essentially follows the same path.

```

\tl_upper_case:n
\tl_mixed_case:n
\tl_lower_case:nn
\tl_upper_case:nn
\tl_mixed_case:nn
18599 \cs_new:Npn \tl_lower_case:n { \__tl_change_case:nnn { lower } { } }
18600 \cs_new:Npn \tl_upper_case:n { \__tl_change_case:nnn { upper } { } }
18601 \cs_new:Npn \tl_mixed_case:n { \__tl_mixed_case:nn { } }
18602 \cs_new:Npn \tl_lower_case:nn { \__tl_change_case:nnn { lower } }
18603 \cs_new:Npn \tl_upper_case:nn { \__tl_change_case:nnn { upper } }
18604 \cs_new:Npn \tl_mixed_case:nn { \__tl_mixed_case:nn }

```

(End definition for `\tl_lower_case:n` and others. These functions are documented on page 217.)

`__tl_change_case:nnn` The mechanism for the core conversion of case is based on the idea that we can use a loop to grab the entire token list plus a quark: the latter is used as an end marker and to avoid any brace stripping. Depending on the nature of the first item in the grabbed argument, it can either processed as a single token, treated as a group or treated as a space. These different cases all work by re-reading #1 in the appropriate way, hence the repetition of #1 `\q_recursion_stop`.

```

18605 \cs_new:Npn \__tl_change_case:nnn #1#2#3
18606 {
18607   \etex_unexpanded:D \exp_after:wN
18608   {
18609     \exp:w
18610     \__tl_change_case_aux:nnn {#1} {#2} {#3}
18611   }
18612 }
18613 \cs_new:Npn \__tl_change_case_aux:nnn #1#2#3

```

```

\__tl_change_case:N_type:Nwnn
\__tl_change_case:N_type:NNNnnn
\__tl_change_case_math:Nwnn
\__tl_change_case_math:NwNNnn
\__tl_change_case_math_group:nwNNnn
\__tl_change_case_math_space:wNNnn
\__tl_change_case_N_type:Nnnn
\__tl_change_case_char:Nnn
\__tl_change_case_char:nN
\__tl_change_case_char_auxi:nN
\__tl_change_case_char_auxii:nN
\__tl_lookup_lower:N
\__tl_lookup_upper:N

```

```

18614 {
18615   \group_align_safe_begin:
18616   \__tl_change_case_loop:wnn
18617     #3 \q_recursion_tail \q_recursion_stop {#1} {#2}
18618   \__tl_change_case_result:n { }
18619 }
18620 \cs_new:Npn \__tl_change_case_loop:wnn #1 \q_recursion_stop
18621 {
18622   \tl_if_head_is_N_type:nTF {#1}
18623     { \__tl_change_case_N_type:Nwnn }
18624     {
18625       \tl_if_head_is_group:nTF {#1}
18626         { \__tl_change_case_group:nwnn }
18627         { \__tl_change_case_space:wnn }
18628     }
18629   #1 \q_recursion_stop
18630 }

```

Earlier versions of the code where only x-type expandable rather than f-type: this causes issues with nesting and so the slight performance hit is taken for a better outcome in usability terms. Setting up for f-type expandability has two requirements: a marker token after the main loop (see above) and a mechanism to “load” and finalise the result. That is handled in the code below, which includes the necessary material to end the `\exp:w` expansion.

```

18631 \cs_new:Npn \__tl_change_case_output:nwn #1#2 \__tl_change_case_result:n #3
18632 { #2 \__tl_change_case_result:n { #3 #1 } }
18633 \cs_generate_variant:Nn \__tl_change_case_output:nwn { V , o , v , f }
18634 \cs_new:Npn \__tl_change_case_end:wn #1 \__tl_change_case_result:n #2
18635 {
18636   \group_align_safe_end:
18637   \exp_end:
18638   #2
18639 }

```

Handling for the cases where the current argument is a brace group or a space is relatively easy. For the brace case, the routine works recursively, using the expandability of the mechanism to ensure that the result is finalised before storage. For the space case it is simply a question of removing the space in the input and storing it in the output. In both cases, and indeed for the N-type grabber, after removing the current item from the input `__tl_change_case_loop:wnn` is inserted in front of the remaining tokens.

```

18640 \cs_new:Npn \__tl_change_case_group:nwnn #1#2 \q_recursion_stop #3#4
18641 {
18642   \__tl_change_case_output:own
18643   {
18644     \exp_after:wN
18645     {
18646       \exp:w
18647       \__tl_change_case_aux:nnn {#3} {#4} {#1}
18648     }
18649   }
18650   \__tl_change_case_loop:wnn #2 \q_recursion_stop {#3} {#4}
18651 }
18652 \exp_last_unbraced:NNo \cs_new:Npn \__tl_change_case_space:wnn \c_space_tl
18653 {

```



```

18654     \_tl_change_case_output:nwn { ~ }
18655     \_tl_change_case_loop:wnn
18656   }

```

For N-type arguments there are several stages to the approach. First, a simply check for the end-of-input marker, which if found triggers the final clean up and output step. Assuming that is not the case, the first check is for math-mode escaping: this test can encompass control sequences or other N-type tokens so is handled up front.

```

18657 \cs_new:Npn \_tl_change_case_N_type:Nwnn #1#2 \q_recursion_stop
18658 {
18659   \quark_if_recursion_tail_stop_do:Nn #1
18660   { \_tl_change_case_end:wn }
18661   \exp_after:wN \_tl_change_case_N_type:NNNnnn
18662   \exp_after:wN #1 \l_tl_change_case_math_tl
18663   \q_recursion_tail ? \q_recursion_stop {#2}
18664 }

```

Looking for math mode escape first requires a loop over the possible token pairs to see if the current input (#1) matches an open-math case (#2). If it does then this test loop is ended and a new input-gathering one is begun. The latter simply transfers material from the input to the output without any expansion, testing each N-type token to see if it matches the close-math case required. If that is the situation then the “math loop” stops and resumes the main loop: as that might be either the standard case-changing one or the mixed-case alternative, it is not hard-coded into the math loop but is rather passed as argument #3 to _tl_change_case_math:NNNnnn. If no close-math token is found then the final clean-up will be forced (*i.e.* there is no assumption of “well-behaved” code in terms of math mode).

```

18665 \cs_new:Npn \_tl_change_case_N_type:NNNnnn #1#2#3
18666 {
18667   \quark_if_recursion_tail_stop_do:Nn #2
18668   { \_tl_change_case_N_type:Nnnn #1 }
18669   \token_if_eq_meaning:NNTF #1 #2
18670   {
18671     \use_i_delimit_by_q_recursion_stop:nw
18672     {
18673       \_tl_change_case_math:NNNnnn
18674       #1 #3 \_tl_change_case_loop:wnn
18675     }
18676   }
18677   { \_tl_change_case_N_type:NNNnnn #1 }
18678 }
18679 \cs_new:Npn \_tl_change_case_math:NNNnnn #1#2#3#4
18680 {
18681   \_tl_change_case_output:nwn {#1}
18682   \_tl_change_case_math_loop:wNNnn #4 \q_recursion_stop #2 #3
18683 }
18684 \cs_new:Npn \_tl_change_case_math_loop:wNNnn #1 \q_recursion_stop
18685 {
18686   \tl_if_head_is_N_type:nTF {#1}
18687   { \_tl_change_case_math:NwNNnn }
18688   {
18689     \tl_if_head_is_group:nTF {#1}
18690     { \_tl_change_case_math_group:nwNNnn }
18691     { \_tl_change_case_math_space:wNNnn }

```

```

18692     }
18693     #1 \q_recursion_stop
18694 }
18695 \cs_new:Npn \__tl_change_case_math:NwNnn #1#2 \q_recursion_stop #3#4
18696 {
18697     \token_if_eq_meaning:NNTF \q_recursion_tail #1
18698     { \__tl_change_case_end:wn }
18699     {
18700         \__tl_change_case_output:nwn {#1}
18701         \token_if_eq_meaning:NNTF #1 #3
18702         { #4 #2 \q_recursion_stop }
18703         { \__tl_change_case_math_loop:wNnn #2 \q_recursion_stop #3#4 }
18704     }
18705 }
18706 \cs_new:Npn \__tl_change_case_math_group:nwNnn #1#2 \q_recursion_stop
18707 {
18708     \__tl_change_case_output:nwn { {#1} }
18709     \__tl_change_case_math_loop:wNnn #2 \q_recursion_stop
18710 }
18711 \exp_last_unbraced:NNo
18712 \cs_new:Npn \__tl_change_case_math_space:wNnn \c_space_tl
18713 {
18714     \__tl_change_case_output:nwn { ~ }
18715     \__tl_change_case_math_loop:wNnn
18716 }

```

Once potential math-mode cases are filtered out the next stage is to test if the token grabbed is a control sequence: they cannot be used in the lookup table and also may require expansion. At this stage the loop code starting `__tl_change_case_loop:wnn` is inserted: all subsequent steps in the code which need a look-ahead are coded to rely on this and thus have w-type arguments if they may do a look-ahead.

```

18717 \cs_new:Npn \__tl_change_case_N_type:Nnn #1#2#3#4
18718 {
18719     \token_if_cs:NNTF #1
18720     { \__tl_change_case_cs_letterlike:Nnn #1 {#3} { } }
18721     { \__tl_change_case_char:Nnn #1 {#3} {#4} }
18722     \__tl_change_case_loop:wnn #2 \q_recursion_stop {#3} {#4}
18723 }

```

For character tokens there are some special cases to deal with then the majority of changes are covered by using the TeX data as a lookup along with expandable character generation. This avoids needing a very large number of macros or (as seen in earlier versions) a somewhat tricky split of the characters into various blocks. Notice that the special case code may do a look-ahead so requires a final w-type argument whereas the core lookup table does not and also guarantees an output so f-type expansion may be used to obtain the case-changed result.

```

18724 \cs_new:Npn \__tl_change_case_char:Nnn #1#2#3
18725 {
18726     \cs_if_exist_use:cF { \__tl_change_case_ #2 _ #3 :Nnw }
18727     { \use_ii:nn }
18728     #1
18729     {
18730         \use:c { \__tl_change_case_ #2 _ sigma:Nnw } #1
18731         { \__tl_change_case_char:nN {#2} #1 }

```

```

18732     }
18733 }

```

For Unicode engines we can handle all characters directly. However, for the 8-bit engines the aim is to deal with (a subset of) Unicode (UTF-8) input. They deal with that by making the upper half of the range active, so we look for that and if found work out how many UTF-8 octets there are to deal with. Those can then be grabbed to reconstruct the full Unicode character, which is then used in a lookup. (As will become obvious below, there is no intention here of covering all of Unicode.)

```

18734 \cs_if_exist:NTF \utex_char:D
18735 {
18736   \cs_new:Npn \__tl_change_case_char:nN #1#2
18737   { \__tl_change_case_char_auxi:nN {#1} #2 }
18738 }
18739 {
18740   \cs_new:Npn \__tl_change_case_char:nN #1#2
18741   {
18742     \int_compare:nNnTF { '#2 } > { "80 }
18743     {
18744       \int_compare:nNnTF { '#2 } < { "EO }
18745       { \__tl_change_case_char_UTFviii:nNNN {#1} #2 }
18746       {
18747         \int_compare:nNnTF { '#2 } < { "FO }
18748         { \__tl_change_case_char_UTFviii:nNNNN {#1} #2 }
18749         { \__tl_change_case_char_UTFviii:nNNNNN {#1} #2 }
18750       }
18751     }
18752     { \__tl_change_case_char_auxi:nN {#1} #2 }
18753   }
18754 }
18755 \cs_new:Npn \__tl_change_case_char_auxi:nN #1#2
18756 {
18757   \__tl_change_case_output:fwn
18758   {
18759     \cs_if_exist_use:cF { c__unicode_ #1 _ \token_to_str:N #2 _tl }
18760     { \__tl_change_case_char_auxii:nN {#1} #2 }
18761   }
18762 }
18763 \cs_if_exist:NTF \utex_char:D
18764 {
18765   \cs_new:Npn \__tl_change_case_char_auxii:nN #1#2
18766   {
18767     \int_compare:nNnTF { \use:c { __tl_lookup_ #1 :N } #2 } = { 0 }
18768     { \exp_stop_f: #2 }
18769     {
18770       \char_generate:nn
18771       { \use:c { __tl_lookup_ #1 :N } #2 }
18772       { \char_value_catcode:n { \use:c { __tl_lookup_ #1 :N } #2 } }
18773     }
18774   }
18775   \cs_new_protected:Npn \__tl_lookup_lower:N #1 { \tex_lccode:D '#1 }
18776   \cs_new_protected:Npn \__tl_lookup_upper:N #1 { \tex_uccode:D '#1 }
18777   \cs_new_eq:NN \__tl_lookup_title:N \__tl_lookup_upper:N
18778 }

```

```

18779 {
18780   \cs_new:Npn \__tl_change_case_char_auxii:nN #1#2 { \exp_stop_f: #2 }
18781   \cs_new:Npn \__tl_change_case_char_UTFviii:nNNN #1#2#3#4
18782     { \__tl_change_case_char_UTFviii:nnN {#1} {#2#4} #3 }
18783   \cs_new:Npn \__tl_change_case_char_UTFviii:nNNNN #1#2#3#4#5
18784     { \__tl_change_case_char_UTFviii:nnN {#1} {#2#4#5} #3 }
18785   \cs_new:Npn \__tl_change_case_char_UTFviii:nNNNNN #1#2#3#4#5#6
18786     { \__tl_change_case_char_UTFviii:nnN {#1} {#2#4#5#6} #3 }
18787   \cs_new:Npn \__tl_change_case_char_UTFviii:nnN #1#2#3
18788     {
18789       \cs_if_exist:cTF { c__unicode_ #1 _ \tl_to_str:n {#2} _tl }
18790       {
18791         \__tl_change_case_output:vwN
18792         { c__unicode_ #1 _ \tl_to_str:n {#2} _tl }
18793       }
18794       { \__tl_change_case_output:nwn {#2} }
18795     } #3
18796   }
18797 }

```

Before dealing with general control sequences there are the special ones to deal with. Letter-like control sequences are a simple look-up, while for accents the loop is much as done elsewhere. Notice that we have a no-op test to make sure there is no unexpected expansion of letter-like input. The third argument here is needed for mixed casing, where it if there is a hit there has to be a change-of-path.

```

18798 \cs_new:Npn \__tl_change_case_cs_letterlike:Nnn #1#2#3
18799 {
18800   \cs_if_exist:cTF { c__tl_change_case_ #2 _ \token_to_str:N #1 _tl }
18801   {
18802     \__tl_change_case_output:vwN
18803     { c__tl_change_case_ #2 _ \token_to_str:N #1 _tl }
18804   } #3
18805 }
18806 {
18807   \cs_if_exist:cTF
18808   {
18809     c__tl_change_case_
18810     \str_if_eq:nnTF {#2} { lower } { upper } { lower }
18811     _ \token_to_str:N #1 _tl
18812   }
18813   {
18814     \__tl_change_case_output:nwn {#1}
18815   } #3
18816 }
18817 {
18818   \exp_after:wN \__tl_change_case_cs_accents:NN
18819   \exp_after:wN #1 \l_tl_case_change_accents_tl
18820   \q_recursion_tail \q_recursion_stop
18821 }
18822 }
18823 }
18824 \cs_new:Npn \__tl_change_case_cs_accents:NN #1#2
18825 {
18826   \quark_if_recursion_tail_stop_do:Nn #2

```

```

18827 { \_tl_change_case_cs:N #1 }
18828 \str_if_eq:nnTF {#1} {#2}
18829 {
18830   \use_i_delimit_by_q_recursion_stop:nw
18831   { \_tl_change_case_output:nwn {#1} }
18832 }
18833 { \_tl_change_case_cs_accents:NN #1 }
18834 }

```

To deal with a control sequence there is first a need to test if it is on the list which indicate that case changing should be skipped. That's done using a loop as for the other special cases. If a hit is found then the argument is grabbed: that comes *after* the loop function which is therefore rearranged. In a L^AT_EX 2_ε context, `\protect` needs to be treated specially, to prevent expansion of the next token but output it without braces.

```

18835 \cs_new:Npn \_tl_change_case_cs:N #1
18836 {
18837   (*package)
18838   \str_if_eq:nnTF {#1} { \protect } { \_tl_change_case_protect:wNN }
18839   (/package)
18840   \exp_after:wN \_tl_change_case_cs:NN
18841   \exp_after:wN #1 \l_tl_case_change_exclude_tl
18842   \q_recursion_tail \q_recursion_stop
18843 }
18844 \cs_new:Npn \_tl_change_case_cs:NN #1#2
18845 {
18846   \quark_if_recursion_tail_stop_do:Nn #2
18847   {
18848     \_tl_change_case_cs_expand:Nnw #1
18849     { \_tl_change_case_output:nwn {#1} }
18850   }
18851   \str_if_eq:nnTF {#1} {#2}
18852   {
18853     \use_i_delimit_by_q_recursion_stop:nw
18854     { \_tl_change_case_cs:NNn #1 }
18855   }
18856   { \_tl_change_case_cs:NN #1 }
18857 }
18858 \cs_new:Npn \_tl_change_case_cs:NNn #1#2#3
18859 {
18860   \_tl_change_case_output:nwn { #1 {#3} }
18861   #2
18862 }
18863 (*package)
18864 \cs_new:Npn \_tl_change_case_protect:wNN #1 \q_recursion_stop #2 #3
18865 { \_tl_change_case_output:nwn { \protect #3 } #2 }
18866 (/package)

```

When a control sequence is not on the exclude list the other test if to see if it is expandable. Once again, if there is a hit then the loop function is grabbed as part of the clean-up and reinserted before the now expanded material. The test for expandability has to check for end-of-recursion as it is needed by the look-ahead code which might hit the end of the input. The test is done in two parts as `\bool_if:nTF` will choke if #1 is (!

```

18867 \cs_new:Npn \_tl_change_case_if_expandable:NTF #1
18868 {

```

```

18869 \token_if_expandable:NTF #1
18870 {
18871   \bool_lazy_any:nTF
18872   {
18873     { \token_if_eq_meaning_p:NN \q_recursion_tail #1 }
18874     { \token_if_protected_macro_p:N #1 }
18875     { \token_if_protected_long_macro_p:N #1 }
18876   }
18877   { \use_ii:nn }
18878   { \use_i:nn }
18879 }
18880 { \use_ii:nn }
18881 }
18882 \cs_new:Npn \__tl_change_case_cs_expand:Nnw #1#2
18883 {
18884   \__tl_change_case_if_expandable:NTF #1
18885   { \__tl_change_case_cs_expand:NN #1 }
18886   { #2 }
18887 }
18888 \cs_new:Npn \__tl_change_case_cs_expand:NN #1#2
18889 { \exp_after:wN #2 #1 }

```

(End definition for __tl_change_case:nnn and others.)

_tl_change_case_lower_sigma:Nnw If the current char is an upper case sigma, the a check is made on the next item in the input. If it is N-type and not a control sequence then there is a look-ahead phase.

```

\_tl_change_case_lower_sigma:w
\_tl_change_case_lower_sigma:Nw
\_tl_change_case_upper_sigma:Nnw
18890 \cs_new:Npn \__tl_change_case_lower_sigma:Nnw #1#2#3#4 \q_recursion_stop
18891 {
18892   \int_compare:nNnTF { '#1 } = { "03A3 }
18893   {
18894     \__tl_change_case_output:fwn
18895     { \__tl_change_case_lower_sigma:w #4 \q_recursion_stop }
18896   }
18897   {#2}
18898   #3 #4 \q_recursion_stop
18899 }
18900 \cs_new:Npn \__tl_change_case_lower_sigma:w #1 \q_recursion_stop
18901 {
18902   \tl_if_head_is_N_type:nTF {#1}
18903   { \__tl_change_case_lower_sigma:Nw #1 \q_recursion_stop }
18904   { \c__unicode_final_sigma_tl }
18905 }
18906 \cs_new:Npn \__tl_change_case_lower_sigma:Nw #1#2 \q_recursion_stop
18907 {
18908   \__tl_change_case_if_expandable:NTF #1
18909   {
18910     \exp_after:wN \__tl_change_case_lower_sigma:w #1
18911     #2 \q_recursion_stop
18912   }
18913   {
18914     \token_if_letter:NTF #1
18915     { \c__unicode_std_sigma_tl }
18916     { \c__unicode_final_sigma_tl }
18917   }
18918 }

```

Simply skip to the final step for upper casing.

```
18919 \cs_new_eq:NN \__tl_change_case_upper_sigma:Nnw \use_ii:nn
```

(End definition for __tl_change_case_lower_sigma:Nnw and others.)

```
\__tl_change_case_lower_tr:Nnw
\__tl_change_case_lower_tr_auxi:Nw
\__tl_change_case_lower_tr_auxii:Nw
\__tl_change_case_upper_tr:Nnw
\__tl_change_case_lower_az:Nnw
\__tl_change_case_upper_az:Nnw
```

The Turkic languages need special treatment for dotted-i and dotless-i. The lower casing rule can be expressed in terms of searching first for either a dotless-I or a dotted-I. In the latter case the mapping is easy, but in the former there is a second stage search.

```
18920 \cs_if_exist:NTF \utex_char:D
18921 {
18922   \cs_new:Npn \__tl_change_case_lower_tr:Nnw #1#2
18923   {
18924     \int_compare:nNnTF { '#1 } = { "0049 }
18925     { \__tl_change_case_lower_tr_auxi:Nw }
18926     {
18927       \int_compare:nNnTF { '#1 } = { "0130 }
18928       { \__tl_change_case_output:nwn { i } }
18929       { #2 }
18930     }
18931   }
```

After a dotless-I there may be a dot-above character. If there is then a dotted-i should be produced, otherwise output a dotless-i. When the combination is found both the dotless-I and the dot-above char have to be removed from the input, which is done by the \use_i:nn (it grabs __tl_change_case_loop:wn and the dot-above char and discards the latter).

```
18932   \cs_new:Npn \__tl_change_case_lower_tr_auxi:Nw #1#2 \q_recursion_stop
18933   {
18934     \tl_if_head_is_N_type:NTF { #2 }
18935     { \__tl_change_case_lower_tr_auxii:Nw #2 \q_recursion_stop }
18936     { \__tl_change_case_output:Vwn \c__unicode_dotless_i_tl }
18937     #1 #2 \q_recursion_stop
18938   }
18939   \cs_new:Npn \__tl_change_case_lower_tr_auxii:Nw #1#2 \q_recursion_stop
18940   {
18941     \__tl_change_case_if_expandable:NTF #1
18942     {
18943       \exp_after:wN \__tl_change_case_lower_tr_auxi:Nw #1
18944       #2 \q_recursion_stop
18945     }
18946     {
18947       \bool_lazy_or:nnTF
18948       { \token_if_cs_p:N #1 }
18949       { ! \int_compare_p:nNn { '#1 } = { "0307 } }
18950       { \__tl_change_case_output:Vwn \c__unicode_dotless_i_tl }
18951       {
18952         \__tl_change_case_output:nwn { i }
18953         \use_i:nn
18954       }
18955     }
18956   }
18957 }
```

For 8-bit engines, dot-above is not available so there is a simple test for an upper-case I. Then we can look for the UTF-8 representation of an upper case dotted-I without the combining char. If it's not there, preserve the UTF-8 sequence as-is.

```

18958 {
18959   \cs_new:Npn \__tl_change_case_lower_tr:Nnw #1#2
18960   {
18961     \int_compare:nNnTF { '#1 } = { "0049 }
18962     { \__tl_change_case_output:Vwn \c__unicode_dotless_i_tl }
18963     {
18964       \int_compare:nNnTF { '#1 } = { 196 }
18965       { \__tl_change_case_lower_tr_auxi:Nw #1 {#2} }
18966       {#2}
18967     }
18968   }
18969   \cs_new:Npn \__tl_change_case_lower_tr_auxi:Nw #1#2#3#4
18970   {
18971     \int_compare:nNnTF { '#4 } = { 176 }
18972     {
18973       \__tl_change_case_output:nwn { i }
18974       #3
18975     }
18976     {
18977       #2
18978       #3 #4
18979     }
18980   }
18981 }

```

Upper casing is easier: just one exception with no context.

```

18982 \cs_new:Npn \__tl_change_case_upper_tr:Nnw #1#2
18983 {
18984   \int_compare:nNnTF { '#1 } = { "0069 }
18985   { \__tl_change_case_output:Vwn \c__unicode_dotted_I_tl }
18986   {#2}
18987 }

```

Straight copies.

```

18988 \cs_new_eq:NN \__tl_change_case_lower_az:Nnw \__tl_change_case_lower_tr:Nnw
18989 \cs_new_eq:NN \__tl_change_case_upper_az:Nnw \__tl_change_case_upper_tr:Nnw

```

(End definition for __tl_change_case_lower_tr:Nnw and others.)

For Lithuanian, the issue to be dealt with is dots over lower case letters: these should be present if there is another accent. That means that there is some work to do when lower casing I and J. The first step is a simple match attempt: \c__tl_accents_lt_tl contains accented upper case letters which should gain a dot-above char in their lower case form. This is done using f-type expansion so only one pass is needed to find if it works or not. If there was no hit, the second stage is to check for I, J and I-ogonek, and if the current char is a match to look for a following accent.

```

\__tl_change_case_lower_lt:Nnw
\__tl_change_case_lower_lt:nNw
\__tl_change_case_lower_lt:nnw
\__tl_change_case_lower_lt:Nw
\__tl_change_case_lower_lt:NNw
\__tl_change_case_upper_lt:Nnw
\__tl_change_case_upper_lt:nnw
\__tl_change_case_upper_lt:Nw
\__tl_change_case_upper_lt:NNw
18990 \cs_new:Npn \__tl_change_case_lower_lt:Nnw #1
18991 {
18992   \exp_args:Nf \__tl_change_case_lower_lt:nNnw
18993   { \str_case:nVF #1 \c__unicode_accents_lt_tl \exp_stop_f: }
18994   #1

```



```

18995 }
18996 \cs_new:Npn \__tl_change_case_lower_lt:nNnw #1#2
18997 {
18998   \tl_if_blank:nTF {#1}
18999   {
19000     \exp_args:Nf \__tl_change_case_lower_lt:nnw
19001     {
19002       \int_case:nnF {'#2}
19003       {
19004         { "0049 } i
19005         { "004A } j
19006         { "012E } \c__unicode_i_ogonek_tl
19007       }
19008       \exp_stop_f:
19009     }
19010   }
19011   {
19012     \__tl_change_case_output:nnw {#1}
19013     \use_none:n
19014   }
19015 }
19016 \cs_new:Npn \__tl_change_case_lower_lt:nnw #1#2
19017 {
19018   \tl_if_blank:nTF {#1}
19019   {#2}
19020   {
19021     \__tl_change_case_output:nnw {#1}
19022     \__tl_change_case_lower_lt:Nw
19023   }
19024 }

```

Grab the next char and see if it is one of the accents used in Lithuanian: if it is, add the dot-above char into the output.

```

19025 \cs_new:Npn \__tl_change_case_lower_lt:Nw #1#2 \q_recursion_stop
19026 {
19027   \tl_if_head_is_N_type:nT {#2}
19028   { \__tl_change_case_lower_lt:NNw }
19029   #1 #2 \q_recursion_stop
19030 }
19031 \cs_new:Npn \__tl_change_case_lower_lt:NNw #1#2#3 \q_recursion_stop
19032 {
19033   \__tl_change_case_if_expandable:NTF #2
19034   {
19035     \exp_after:wN \__tl_change_case_lower_lt:Nw \exp_after:wN #1 #2
19036     #3 \q_recursion_stop
19037   }
19038   {
19039     \bool_lazy_and:nnT
19040     { ! \token_if_cs_p:N #2 }
19041     {
19042       \bool_lazy_any_p:n
19043       {
19044         { \int_compare_p:nNn { '#2 } = { "0300 } }
19045         { \int_compare_p:nNn { '#2 } = { "0301 } }

```

```

19046         { \int_compare_p:nNn { '#2 } = { "0303 } }
19047     }
19048 }
19049 { \__tl_change_case_output:Vwn \c__unicode_dot_above_tl }
19050 #1 #2#3 \q_recursion_stop
19051 }
19052 }

```

For upper casing, the test required is for a dot-above char after an I, J or I-ogonek. First a test for the appropriate letter, and if found a look-ahead and potentially one token dropped.

```

19053 \cs_new:Npn \__tl_change_case_upper_lt:Nnw #1
19054 {
19055     \exp_args:Nf \__tl_change_case_upper_lt:nnw
19056     {
19057         \int_case:nnF { '#1 }
19058         {
19059             { "0069 } I
19060             { "006A } J
19061             { "012F } \c__unicode_I_ogonek_tl
19062         }
19063         \exp_stop_f:
19064     }
19065 }
19066 \cs_new:Npn \__tl_change_case_upper_lt:nnw #1#2
19067 {
19068     \tl_if_blank:nTF {#1}
19069     {#2}
19070     {
19071         \__tl_change_case_output:wnw {#1}
19072         \__tl_change_case_upper_lt:Nw
19073     }
19074 }
19075 \cs_new:Npn \__tl_change_case_upper_lt:Nw #1#2 \q_recursion_stop
19076 {
19077     \tl_if_head_is_N_type:nT {#2}
19078     { \__tl_change_case_upper_lt:NNw }
19079     #1 #2 \q_recursion_stop
19080 }
19081 \cs_new:Npn \__tl_change_case_upper_lt:NNw #1#2#3 \q_recursion_stop
19082 {
19083     \__tl_change_case_if_expandable:NTF #2
19084     {
19085         \exp_after:wN \__tl_change_case_upper_lt:Nw \exp_after:wN #1 #2
19086         #3 \q_recursion_stop
19087     }
19088     {
19089         \bool_lazy_and:nnTF
19090         { ! \token_if_cs_p:N #2 }
19091         { \int_compare_p:nNn { '#2 } = { "0307 } }
19092         { #1 }
19093         { #1 #2 }
19094         #3 \q_recursion_stop
19095     }

```

```
19096 }
```

(End definition for `_tl_change_case_lower_lt:Nnw` and others.)

`_tl_change_case_upper_de-alt:Nnw` A simple alternative version for German.

```
19097 \cs_new:cpn { \_tl_change_case_upper_de-alt:Nnw } #1#2
19098 {
19099   \int_compare:nNnTF { '#1 } = { 223 }
19100   { \_tl_change_case_output:Vwn \c__unicode_upper_Eszett_tl }
19101   {#2}
19102 }
```

(End definition for `_tl_change_case_upper_de-alt:Nnw`.)

`_unicode_codepoint_to_UTFviii:n`
`_unicode_codepoint_to_UTFviii_auxi:n`
`_unicode_codepoint_to_UTFviii_auxii:Nnn`
`_unicode_codepoint_to_UTFviii_auxiii:n`

This code will convert a codepoint into the correct UTF-8 representation. As there are a variable number of octets, the result starts with the numeral 1–4 to indicate the nature of the returned value. Note that this code will cover the full range even though at this stage it is not required here. Also note that longer-term this is likely to need a public interface and/or moving to `l3str` (see experimental string conversions). In terms of the algorithm itself, see <https://en.wikipedia.org/wiki/UTF-8> for the octet pattern.

```
19103 \cs_new:Npn \_unicode_codepoint_to_UTFviii:n #1
19104 {
19105   \exp_args:Nf \_unicode_codepoint_to_UTFviii_auxi:n
19106   { \int_eval:n {#1} }
19107 }
19108 \cs_new:Npn \_unicode_codepoint_to_UTFviii_auxi:n #1
19109 {
19110   \if_int_compare:w #1 > "80 ~
19111   \if_int_compare:w #1 < "800 ~
19112     2
19113     \_unicode_codepoint_to_UTFviii_auxii:Nnn C {#1} { 64 }
19114     \_unicode_codepoint_to_UTFviii_auxiii:n {#1}
19115   \else:
19116     \if_int_compare:w #1 < "10000 ~
19117       3
19118       \_unicode_codepoint_to_UTFviii_auxii:Nnn E {#1} { 64 * 64 }
19119       \_unicode_codepoint_to_UTFviii_auxiii:n {#1}
19120       \_unicode_codepoint_to_UTFviii_auxiii:n
19121       { \int_div_truncate:nn {#1} { 64 } }
19122     \else:
19123       4
19124       \_unicode_codepoint_to_UTFviii_auxii:Nnn F
19125       {#1} { 64 * 64 * 64 }
19126       \_unicode_codepoint_to_UTFviii_auxiii:n
19127       { \int_div_truncate:nn {#1} { 64 * 64 } }
19128       \_unicode_codepoint_to_UTFviii_auxiii:n
19129       { \int_div_truncate:nn {#1} { 64 } }
19130       \_unicode_codepoint_to_UTFviii_auxiii:n {#1}
19131
19132     \fi:
19133   \fi:
19134   \else:
19135     1 {#1}
19136   \fi:
```

```

19137 }
19138 \cs_new:Npn \__unicode_codepoint_to_UTFviii_auxii:Nnn #1#2#3
19139 { { \int_eval:n { "#10 + \int_div_truncate:nn {#2} {#3} } } }
19140 \cs_new:Npn \__unicode_codepoint_to_UTFviii_auxiii:n #1
19141 { { \int_eval:n { \int_mod:nn {#1} { 64 } + 128 } } }

```

(End definition for __unicode_codepoint_to_UTFviii:n and others.)

\c__unicode_std_sigma_tl The above needs various special token lists containing pre-formed characters. This set are only available in Unicode engines, with no-op definitions for 8-bit use.

```

\c__unicode_final_sigma_tl
\c__unicode_accents_lt_tl
\c__unicode_dot_above_tl
\c__unicode_upper_Eszett_tl
19142 \cs_if_exist:NTF \utex_char:D
19143 {
19144   \tl_const:Nx \c__unicode_std_sigma_tl { \utex_char:D "03C3 ~ }
19145   \tl_const:Nx \c__unicode_final_sigma_tl { \utex_char:D "03C2 ~ }
19146   \tl_const:Nx \c__unicode_accents_lt_tl
19147   {
19148     \utex_char:D "00CC ~
19149     { \utex_char:D "0069 ~ \utex_char:D "0307 ~ \utex_char:D "0300 ~ }
19150     \utex_char:D "00CD ~
19151     { \utex_char:D "0069 ~ \utex_char:D "0307 ~ \utex_char:D "0301 ~ }
19152     \utex_char:D "0128 ~
19153     { \utex_char:D "0069 ~ \utex_char:D "0307 ~ \utex_char:D "0303 ~ }
19154   }
19155   \tl_const:Nx \c__unicode_dot_above_tl { \utex_char:D "0307 ~ }
19156   \tl_const:Nx \c__unicode_upper_Eszett_tl { \utex_char:D "1E9E ~ }
19157 }
19158 {
19159   \tl_const:Nn \c__unicode_std_sigma_tl { }
19160   \tl_const:Nn \c__unicode_final_sigma_tl { }
19161   \tl_const:Nn \c__unicode_accents_lt_tl { }
19162   \tl_const:Nn \c__unicode_dot_above_tl { }
19163   \tl_const:Nn \c__unicode_upper_Eszett_tl { }
19164 }

```

(End definition for \c__unicode_std_sigma_tl and others.)

\c__unicode_dotless_i_tl For cases where there is an 8-bit option in the T1 font set up, a variant is provided in both cases.

```

\c__unicode_dotted_I_tl
\c__unicode_i_ogonek_tl
\c__unicode_I_ogonek_tl
19165 \group_begin:
19166   \cs_if_exist:NTF \utex_char:D
19167   {
19168     \cs_set_protected:Npn \__tl_tmp:w #1#2
19169     { \tl_const:Nx #1 { \utex_char:D "#2 ~ } }
19170   }
19171   {
19172     \cs_set_protected:Npn \__tl_tmp:w #1#2
19173     {
19174       \group_begin:
19175       \cs_set_protected:Npn \__tl_tmp:w ##1##2##3
19176       {
19177         \tl_const:Nx #1
19178         {
19179           \exp_after:wN \exp_after:wN \exp_after:wN
19180           \exp_not:N \__char_generate:nn {##2} { 13 }

```

```

19181         \exp_after:wN \exp_after:wN \exp_after:wN
19182         \exp_not:N \__char_generate:nn {##3} { 13 }
19183     }
19184 }
19185 \tl_set:Nx \l__tl_internal_a_tl
19186 { \__unicode_codepoint_to_UTFviii:n {"#2} }
19187 \exp_after:wN \__tl_tmp:w \l__tl_internal_a_tl
19188 \group_end:
19189 }
19190 }
19191 \__tl_tmp:w \c__unicode_dotless_i_tl { 0131 }
19192 \__tl_tmp:w \c__unicode_dotted_I_tl { 0130 }
19193 \__tl_tmp:w \c__unicode_i_ogonek_tl { 012F }
19194 \__tl_tmp:w \c__unicode_I_ogonek_tl { 012E }
19195 \group_end:

```

(End definition for \c__unicode_dotless_i_tl and others.)

For 8-bit engines we now need to define the case-change data for the multi-octet mappings. These need a list of what code points are doable in T1 so the list is hard coded (there's no saving in loading the mappings dynamically). All of the straight-forward ones have two octets, so that is taken as read.

```

19196 \group_begin:
19197 \bool_if:nT
19198 {
19199     \sys_if_engine_pdftex_p: || \sys_if_engine_uptex_p:
19200 }
19201 {
19202     \cs_set_protected:Npn \__tl_loop:nn #1#2
19203     {
19204         \quark_if_recursion_tail_stop:n {#1}
19205         \tl_set:Nx \l__tl_internal_a_tl
19206         {
19207             \__unicode_codepoint_to_UTFviii:n {"#1}
19208             \__unicode_codepoint_to_UTFviii:n {"#2}
19209         }
19210         \exp_after:wN \__tl_tmp:w \l__tl_internal_a_tl
19211         \__tl_loop:nn
19212     }
19213     \cs_set_protected:Npn \__tl_tmp:w #1#2#3#4#5#6
19214     {
19215         \tl_const:cx
19216         {
19217             c__unicode_lower_
19218             \char_generate:nn {#2} { 12 }
19219             \char_generate:nn {#3} { 12 }
19220             _tl
19221         }
19222         {
19223             \exp_after:wN \exp_after:wN \exp_after:wN
19224             \exp_not:N \__char_generate:nn {#5} { 13 }
19225             \exp_after:wN \exp_after:wN \exp_after:wN
19226             \exp_not:N \__char_generate:nn {#6} { 13 }
19227         }
19228         \tl_const:cx

```

```

19229         {
19230             c__unicode_upper_
19231             \char_generate:nn {#5} { 12 }
19232             \char_generate:nn {#6} { 12 }
19233             _tl
19234         }
19235         {
19236             \exp_after:wN \exp_after:wN \exp_after:wN
19237             \exp_not:N \_char_generate:nn {#2} { 13 }
19238             \exp_after:wN \exp_after:wN \exp_after:wN
19239             \exp_not:N \_char_generate:nn {#3} { 13 }
19240         }
19241     }
19242     \_tl_loop:nn
19243     { 00C0 } { 00E0 }
19244     { 00C2 } { 00E2 }
19245     { 00C3 } { 00E3 }
19246     { 00C4 } { 00E4 }
19247     { 00C5 } { 00E5 }
19248     { 00C6 } { 00E6 }
19249     { 00C7 } { 00E7 }
19250     { 00C8 } { 00E8 }
19251     { 00C9 } { 00E9 }
19252     { 00CA } { 00EA }
19253     { 00CB } { 00EB }
19254     { 00CC } { 00EC }
19255     { 00CD } { 00ED }
19256     { 00CE } { 00EE }
19257     { 00CF } { 00EF }
19258     { 00D0 } { 00F0 }
19259     { 00D1 } { 00F1 }
19260     { 00D2 } { 00F2 }
19261     { 00D3 } { 00F3 }
19262     { 00D4 } { 00F4 }
19263     { 00D5 } { 00F5 }
19264     { 00D6 } { 00F6 }
19265     { 00D8 } { 00F8 }
19266     { 00D9 } { 00F9 }
19267     { 00DA } { 00FA }
19268     { 00DB } { 00FB }
19269     { 00DC } { 00FC }
19270     { 00DD } { 00FD }
19271     { 00DE } { 00FE }
19272     { 0100 } { 0101 }
19273     { 0102 } { 0103 }
19274     { 0104 } { 0105 }
19275     { 0106 } { 0107 }
19276     { 0108 } { 0109 }
19277     { 010A } { 010B }
19278     { 010C } { 010D }
19279     { 010E } { 010F }
19280     { 0110 } { 0111 }
19281     { 0112 } { 0113 }
19282     { 0114 } { 0115 }

```

| | | |
|-------|----------|----------|
| 19283 | { 0116 } | { 0117 } |
| 19284 | { 0118 } | { 0119 } |
| 19285 | { 011A } | { 011B } |
| 19286 | { 011C } | { 011D } |
| 19287 | { 011E } | { 011F } |
| 19288 | { 0120 } | { 0121 } |
| 19289 | { 0122 } | { 0123 } |
| 19290 | { 0124 } | { 0125 } |
| 19291 | { 0128 } | { 0129 } |
| 19292 | { 012A } | { 012B } |
| 19293 | { 012C } | { 012D } |
| 19294 | { 012E } | { 012F } |
| 19295 | { 0132 } | { 0133 } |
| 19296 | { 0134 } | { 0135 } |
| 19297 | { 0136 } | { 0137 } |
| 19298 | { 0139 } | { 013A } |
| 19299 | { 013B } | { 013C } |
| 19300 | { 013E } | { 013F } |
| 19301 | { 0141 } | { 0142 } |
| 19302 | { 0143 } | { 0144 } |
| 19303 | { 0145 } | { 0146 } |
| 19304 | { 0147 } | { 0148 } |
| 19305 | { 014A } | { 014B } |
| 19306 | { 014C } | { 014D } |
| 19307 | { 014E } | { 014F } |
| 19308 | { 0150 } | { 0151 } |
| 19309 | { 0152 } | { 0153 } |
| 19310 | { 0154 } | { 0155 } |
| 19311 | { 0156 } | { 0157 } |
| 19312 | { 0158 } | { 0159 } |
| 19313 | { 015A } | { 015B } |
| 19314 | { 015C } | { 015D } |
| 19315 | { 015E } | { 015F } |
| 19316 | { 0160 } | { 0161 } |
| 19317 | { 0162 } | { 0163 } |
| 19318 | { 0164 } | { 0165 } |
| 19319 | { 0168 } | { 0169 } |
| 19320 | { 016A } | { 016B } |
| 19321 | { 016C } | { 016D } |
| 19322 | { 016E } | { 016F } |
| 19323 | { 0170 } | { 0171 } |
| 19324 | { 0172 } | { 0173 } |
| 19325 | { 0174 } | { 0175 } |
| 19326 | { 0176 } | { 0177 } |
| 19327 | { 0178 } | { 00FF } |
| 19328 | { 0179 } | { 017A } |
| 19329 | { 017B } | { 017C } |
| 19330 | { 017D } | { 017E } |
| 19331 | { 01CD } | { 01CE } |
| 19332 | { 01CF } | { 01D0 } |
| 19333 | { 01D1 } | { 01D2 } |
| 19334 | { 01D3 } | { 01D4 } |
| 19335 | { 01E2 } | { 01E3 } |
| 19336 | { 01E6 } | { 01E7 } |

```

19337     { 01E8 } { 01E9 }
19338     { 01EA } { 01EB }
19339     { 01F4 } { 01F5 }
19340     { 0218 } { 0219 }
19341     { 021A } { 021B }
19342     \q_recursion_tail ?
19343     \q_recursion_stop
19344     \cs_set_protected:Npn \__tl_tmp:w #1#2#3
19345     {
19346         \group_begin:
19347         \cs_set_protected:Npn \__tl_tmp:w ##1##2##3
19348         {
19349             \tl_const:cx
19350             {
19351                 c__unicode_ #3 _
19352                 \char_generate:nn {##2} { 12 }
19353                 \char_generate:nn {##3} { 12 }
19354                 _tl
19355             }
19356             {#2}
19357         }
19358         \tl_set:Nx \l__tl_internal_a_tl
19359         { \__unicode_codepoint_to_UTFviii:n { "#1 } }
19360         \exp_after:wN \__tl_tmp:w \l__tl_internal_a_tl
19361         \group_end:
19362     }
19363     \__tl_tmp:w { 00DF } { SS } { upper }
19364     \__tl_tmp:w { 00DF } { Ss } { title }
19365     \__tl_tmp:w { 0131 } { I } { upper }
19366 }
19367 \group_end:

```

The (fixed) look-up mappings for letter-like control sequences.

```

19368 \group_begin:
19369     \cs_set_protected:Npn \__tl_change_case_setup:NN #1#2
19370     {
19371         \quark_if_recursion_tail_stop:N #1
19372         \tl_const:cn { c__tl_change_case_lower_ \token_to_str:N #1 _tl } { #2 }
19373         \tl_const:cn { c__tl_change_case_upper_ \token_to_str:N #2 _tl } { #1 }
19374         \__tl_change_case_setup:NN
19375     }
19376     \__tl_change_case_setup:NN
19377     \AA \aa
19378     \AE \ae
19379     \DH \dh
19380     \DJ \dj
19381     \IJ \ij
19382     \L \l
19383     \NG \ng
19384     \O \o
19385     \OE \oe
19386     \SS \ss
19387     \TH \th
19388     \q_recursion_tail ?
19389     \q_recursion_stop

```



```

19390 \tl_const:cn { c__tl_change_case_upper_ \token_to_str:N \i _tl } { I }
19391 \tl_const:cn { c__tl_change_case_upper_ \token_to_str:N \j _tl } { J }
19392 \group_end:

```

`\l_tl_case_change_accents_tl` A list of accents to leave alone.

```

19393 \tl_new:N \l_tl_case_change_accents_tl
19394 \tl_set:Nn \l_tl_case_change_accents_tl
19395 { \" \' \. \^ \' \~ \c \H \k \r \t \u \v }

```

(End definition for `\l_tl_case_change_accents_tl`. This variable is documented on page 219.)

`__tl_mixed_case:nn` Mixed (title) casing requires some custom handling of the case changing of the first letter in the input followed by a switch to the normal lower casing routine. That could be covered by passing a set of functions to generic routines, but at the cost of making the process rather opaque. Instead, the approach taken here is to use a dedicated set of functions which keep the different loop requirements clearly separate.

The main loop looks for the first “real” char in the input (skipping any pre-letter chars). Once one is found, it is case changed to upper case but first checking that there is not an entry in the exceptions list. Note that simply grabbing the first token in the input is no good here: it can’t handle pre-letter tokens or any special treatment of the first letter found (*e.g.* words starting with *i* in Turkish). Spaces at the start of the input are passed through without counting as being the “start” of the first word, while a brace group is assumed to be contain the first char with everything after the brace therefore lower cased.

```

\__tl_mixed_case_aux:nn
\__tl_mixed_case_loop:wn
\__tl_mixed_case_group:nwn
\__tl_mixed_case_space:wn
\__tl_mixed_case_N_type:Nwn
\__tl_mixed_case_N_type:NNNnn
\__tl_mixed_case_letterlike:Nw
\__tl_mixed_case_char:N
\__tl_mixed_case_skip:N
\__tl_mixed_case_skip:NN
\__tl_mixed_case_skip_tidy:Nwn
\__tl_mixed_case_char:nN
19396 \cs_new:Npn \__tl_mixed_case:nn #1#2
19397 {
19398   \etex_unexpanded:D \exp_after:wn
19399   {
19400     \exp:w
19401     \__tl_mixed_case_aux:nn {#1} {#2}
19402   }
19403 }
19404 \cs_new:Npn \__tl_mixed_case_aux:nn #1#2
19405 {
19406   \group_align_safe_begin:
19407   \__tl_mixed_case_loop:wn
19408   #2 \q_recursion_tail \q_recursion_stop {#1}
19409   \__tl_change_case_result:n { }
19410 }
19411 \cs_new:Npn \__tl_mixed_case_loop:wn #1 \q_recursion_stop
19412 {
19413   \tl_if_head_is_N_type:nTF {#1}
19414   { \__tl_mixed_case_N_type:Nwn }
19415   {
19416     \tl_if_head_is_group:nTF {#1}
19417     { \__tl_mixed_case_group:nwn }
19418     { \__tl_mixed_case_space:wn }
19419   }
19420   #1 \q_recursion_stop
19421 }
19422 \cs_new:Npn \__tl_mixed_case_group:nwn #1#2 \q_recursion_stop #3
19423 {
19424   \__tl_change_case_output:own

```

```

19425     {
19426         \exp_after:wN
19427         {
19428             \exp:w
19429             \__tl_mixed_case_aux:nn {#3} {#1}
19430         }
19431     }
19432     \__tl_change_case_loop:wnn #2 \q_recursion_stop { lower } {#3}
19433 }
19434 \exp_last_unbraced:NNo \cs_new:Npn \__tl_mixed_case_space:wn \c_space_tl
19435 {
19436     \__tl_change_case_output:nwn { ~ }
19437     \__tl_mixed_case_loop:wn
19438 }
19439 \cs_new:Npn \__tl_mixed_case_N_type:Nwn #1#2 \q_recursion_stop
19440 {
19441     \quark_if_recursion_tail_stop_do:Nn #1
19442     { \__tl_change_case_end:wn }
19443     \exp_after:wN \__tl_mixed_case_N_type:NNNnn
19444     \exp_after:wN #1 \l_tl_case_change_math_tl
19445     \q_recursion_tail ? \q_recursion_stop {#2}
19446 }
19447 \cs_new:Npn \__tl_mixed_case_N_type:NNNnn #1#2#3
19448 {
19449     \quark_if_recursion_tail_stop_do:Nn #2
19450     { \__tl_mixed_case_N_type:Nnn #1 }
19451     \token_if_eq_meaning:NNTF #1 #2
19452     {
19453         \use_i_delimit_by_q_recursion_stop:nw
19454         {
19455             \__tl_change_case_math:NNNnnn
19456             #1 #3 \__tl_mixed_case_loop:wn
19457         }
19458     }
19459     { \__tl_mixed_case_N_type:NNNnn #1 }
19460 }

```

The business end of the loop is here: there is first a need to deal with any control sequence cases before looking for characters to skip. If there is a hit for a letter-like control sequence, switch to lower casing.

```

19461 \cs_new:Npn \__tl_mixed_case_N_type:Nnn #1#2#3
19462 {
19463     \token_if_cs:NNTF #1
19464     {
19465         \__tl_change_case_cs_letterlike:Nnn #1 { upper }
19466         { \__tl_mixed_case_letterlike:Nw }
19467         \__tl_mixed_case_loop:wn #2 \q_recursion_stop {#3}
19468     }
19469     {
19470         \__tl_mixed_case_char:Nn #1 {#3}
19471         \__tl_change_case_loop:wnn #2 \q_recursion_stop { lower } {#3}
19472     }
19473 }
19474 \cs_new:Npn \__tl_mixed_case_letterlike:Nw #1#2 \q_recursion_stop

```

```
19475 { \_tl\_change\_case\_loop:wnn #2 \q\_recursion\_stop { lower } }
```

As detailed above, handling a mixed case char means first looking for exceptions then treating as an upper cased letter, but with a list of tokens to skip over too.

```
19476 \cs\_new:Npn \_tl\_mixed\_case\_char:Nn #1#2
19477 {
19478   \cs\_if\_exist\_use:cF { \_tl\_change\_case\_mixed\_ #2 :Nnw }
19479   {
19480     \cs\_if\_exist\_use:cF { \_tl\_change\_case\_upper\_ #2 :Nnw }
19481     { \use\_ii:nn }
19482   }
19483   #1
19484   { \_tl\_mixed\_case\_skip:N #1 }
19485 }
19486 \cs\_new:Npn \_tl\_mixed\_case\_skip:N #1
19487 {
19488   \exp\_after:wN \_tl\_mixed\_case\_skip:NN
19489   \exp\_after:wN #1 \l\_tl\_mixed\_case\_ignore\_tl
19490   \q\_recursion\_tail \q\_recursion\_stop
19491 }
19492 \cs\_new:Npn \_tl\_mixed\_case\_skip:NN #1#2
19493 {
19494   \quark\_if\_recursion\_tail\_stop\_do:nn {#2}
19495   { \_tl\_mixed\_case\_char:N #1 }
19496   \int\_compare:nNnT { '#1 } = { '#2 }
19497   {
19498     \use\_i\_delimit\_by\_q\_recursion\_stop:nw
19499     {
19500       \_tl\_change\_case\_output:nwn {#1}
19501       \_tl\_mixed\_case\_skip\_tidy:Nwn
19502     }
19503   }
19504   \_tl\_mixed\_case\_skip:NN #1
19505 }
19506 \cs\_new:Npn \_tl\_mixed\_case\_skip\_tidy:Nwn #1#2 \q\_recursion\_stop #3
19507 {
19508   \_tl\_mixed\_case\_loop:wn #2 \q\_recursion\_stop
19509 }
19510 \cs\_new:Npn \_tl\_mixed\_case\_char:N #1
19511 {
19512   \cs\_if\_exist:cTF { c\_unicode\_title\_ #1\_tl }
19513   {
19514     \_tl\_change\_case\_output:fwn
19515     { \tl\_use:c { c\_unicode\_title\_ #1\_tl } }
19516   }
19517   { \_tl\_change\_case\_char:nN { upper } #1 }
19518 }
```

(End definition for _tl_mixed_case:nn and others.)

_tl_change_case_mixed_nl:Nnw For Dutch, there is a single look-ahead test for ij when title casing. If the appropriate letters are found, produce IJ and gobble the j/J.

```
\_tl\_change\_case\_mixed\_nl:Nw
\_tl\_change\_case\_mixed\_nl:NNw
19519 \cs\_new:Npn \_tl\_change\_case\_mixed\_nl:Nnw #1
19520 {
19521   \bool\_lazy\_or:nnTF
```

```

19522     { \int_compare_p:nNn { '#1 } = { 'i } }
19523     { \int_compare_p:nNn { '#1 } = { 'I } }
19524     {
19525         \__tl_change_case_output:nwn { I }
19526         \__tl_change_case_mixed_n1:Nw
19527     }
19528 }
19529 \cs_new:Npn \__tl_change_case_mixed_n1:Nw #1#2 \q_recursion_stop
19530 {
19531     \tl_if_head_is_N_type:nT {#2}
19532     { \__tl_change_case_mixed_n1:NNw }
19533     #1 #2 \q_recursion_stop
19534 }
19535 \cs_new:Npn \__tl_change_case_mixed_n1:NNw #1#2#3 \q_recursion_stop
19536 {
19537     \__tl_change_case_if_expandable:NTF #2
19538     {
19539         \exp_after:wN \__tl_change_case_mixed_n1:Nw \exp_after:wN #1 #2
19540         #3 \q_recursion_stop
19541     }
19542     {
19543         \bool_lazy_and:nnTF
19544         { ! ( \token_if_cs_p:N #2 ) }
19545         {
19546             \bool_lazy_or_p:nn
19547             { \int_compare_p:nNn { '#2 } = { 'j } }
19548             { \int_compare_p:nNn { '#2 } = { 'J } }
19549         }
19550         {
19551             \__tl_change_case_output:nwn { J }
19552             #1
19553         }
19554         { #1 #2 }
19555         #3 \q_recursion_stop
19556     }
19557 }

```

(End definition for `__tl_change_case_mixed_n1:Nnw`, `__tl_change_case_mixed_n1:Nw`, and `__tl_change_case_mixed_n1:NNw`.)

`\l_tl_case_change_math_tl` The list of token pairs which are treated as math mode and so not case changed.

```

19558 \tl_new:N \l_tl_case_change_math_tl
19559 \*package
19560 \tl_set:Nn \l_tl_case_change_math_tl
19561 { $ $ \ ( \ ) }
19562 \*package

```

(End definition for `\l_tl_case_change_math_tl`. This variable is documented on page 218.)

`\l_tl_case_change_exclude_tl` The list of commands for which an argument is not case changed.

```

19563 \tl_new:N \l_tl_case_change_exclude_tl
19564 \*package
19565 \tl_set:Nn \l_tl_case_change_exclude_tl
19566 { \cite \ensuremath \label \ref }
19567 \*package

```

(End definition for `\l_tl_case_change_exclude_tl`. This variable is documented on page 218.)

`\l_tl_mixed_case_ignore_tl` Characters to skip over when finding the first letter in a word to be mixed cased.

```

19568 \tl_new:N \l_tl_mixed_case_ignore_tl
19569 \tl_set:Nx \l_tl_mixed_case_ignore_tl
19570 {
19571   ( % )
19572   [ % ]
19573   \cs_to_str:N \{ % \}
19574   '
19575   -
19576 }
```

(End definition for `\l_tl_mixed_case_ignore_tl`. This variable is documented on page 219.)

38.15.2 Other additions to `l3tl`

`\tl_rand_item:n` Importantly `\tl_item:nn` only evaluates its argument once.

```

\tl_rand_item:N 19577 \cs_new:Npn \tl_rand_item:n #1
\tl_rand_item:c 19578 {
19579   \tl_if_blank:nF {#1}
19580   { \tl_item:nn {#1} { \int_rand:nn { 1 } { \tl_count:n {#1} } } }
19581 }
19582 \cs_new:Npn \tl_rand_item:N { \exp_args:No \tl_rand_item:n }
19583 \cs_generate_variant:Nn \tl_rand_item:N { c }
```

(End definition for `\tl_rand_item:n` and `\tl_rand_item:N`. These functions are documented on page 220.)

`\tl_range:Nnn` To avoid checking for the end of the token list at every step, start by counting the number
`\tl_range:cnn` l of items and “normalizing” the bounds, namely clamping them to the interval $[0, l]$ and
`\tl_range:nnn` dealing with negative indices. More precisely, `__tl_range:nnw` receives the number of
`__tl_range:nnnw` items to skip at the beginning of the token list, and the index of the last item to keep.
`__tl_range:nnw` If nothing should be kept, leave `{}`: this stops the `f`-expansion of `\tl_head:f` and that
`__tl_range_normalize:nn` function produces an empty result. Otherwise, repeatedly call `__tl_range_skip:w`
`__tl_range_collect:w` to delete `#1` items from the input stream (the extra brace group avoids an off-by-one
`__tl_range_skip:w` mistake), then repeatedly call `__tl_range_collect:w` to store in its second argument
the items to be kept. Eventually, the result is a brace group followed by the rest of the
token list, and `\tl_head:f` cleans up and gives the result in `\exp_not:n`.

```

19584 \cs_new:Npn \tl_range:Nnn { \exp_args:No \tl_range:nnn }
19585 \cs_generate_variant:Nn \tl_range:Nnn { c }
19586 \cs_new:Npn \tl_range:nnn #1#2#3
19587 {
19588   \tl_head:f
19589   {
19590     \exp_args:Nf \__tl_range:nnnw { \tl_count:n {#1} } {#2} {#3}
19591     #1
19592   }
19593 }
19594 \cs_new:Npn \__tl_range:nnnw #1#2#3
19595 {
19596   \exp_args:Nff \__tl_range:nnw
19597   {
```

```

19598     \exp_args:Nf \__tl_range_normalize:nn
19599     { \int_eval:n { #2 - 1 } } {#1}
19600   }
19601   {
19602     \exp_args:Nf \__tl_range_normalize:nn
19603     { \int_eval:n {#3} } {#1}
19604   }
19605 }
19606 \cs_new:Npn \__tl_range:nnw #1#2
19607 {
19608   \if_int_compare:w #2 > #1 \exp_stop_f: \else:
19609     \exp_after:wN { \exp_after:wN }
19610   \fi:
19611   \exp_after:wN \__tl_range_collect:w
19612   \__int_value:w \__int_eval:w #2 - #1 \exp_after:wN ;
19613   \exp_after:wN { \exp_after:wN }
19614   \exp:w \__tl_range_skip:w #1 ; { }
19615 }
19616 \cs_new:Npn \__tl_range_skip:w #1 ; #2
19617 {
19618   \if_int_compare:w #1 > 0 \exp_stop_f:
19619     \exp_after:wN \__tl_range_skip:w
19620     \__int_value:w \__int_eval:w #1 - 1 \exp_after:wN ;
19621   \else:
19622     \exp_after:wN \exp_end:
19623   \fi:
19624 }
19625 \cs_new:Npn \__tl_range_collect:w #1 ; #2#3
19626 {
19627   \if_int_compare:w #1 > 1 \exp_stop_f:
19628     \exp_after:wN \__tl_range_collect:w
19629     \__int_value:w \__int_eval:w #1 - 1 \exp_after:wN ;
19630   \fi:
19631   { #2 {#3} }
19632 }

```

(End definition for `\tl_range:Nnn` and others. These functions are documented on page 221.)

`__tl_range_normalize:nn` This function converts an $\langle index \rangle$ argument into an explicit position in the token list (a result of 0 denoting “out of bounds”). Expects two explicit integer arguments: the $\langle index \rangle$ #1 and the string count #2. If #1 is negative, replace it by $\#1 + \#2 + 1$, then limit to the range $[0, \#2]$.

```

19633 \cs_new:Npn \__tl_range_normalize:nn #1#2
19634 {
19635   \int_eval:n
19636   {
19637     \if_int_compare:w #1 < 0 \exp_stop_f:
19638       \if_int_compare:w #1 < -#2 \exp_stop_f:
19639         0
19640       \else:
19641         #1 + #2 + 1
19642       \fi:
19643     \else:
19644       \if_int_compare:w #1 < #2 \exp_stop_f:

```

```

19645         #1
19646         \else:
19647         #2
19648         \fi:
19649     \fi:
19650 }
19651 }

```

(End definition for _tl_range_normalize:nn.)

38.16 Additions to l3tokens

19652 <@@=peek>

\peek_N_type:TF
 _peek_execute_branches_N_type:
 _peek_N_type:w
 _peek_N_type_aux:nnw

All tokens are N-type tokens, except in four cases: begin-group tokens, end-group tokens, space tokens with character code 32, and outer tokens. Since `\l_peek_token` might be outer, we cannot use the convenient `\bool_if:nTF` function, and must resort to the old trick of using `\ifodd` to expand a set of tests. The `false` branch of this test is taken if the token is one of the first three kinds of non-N-type tokens (explicit or implicit), thus we call `_peek_false:w`. In the `true` branch, we must detect outer tokens, without impacting performance too much for non-outer tokens. The first filter is to search for `outer` in the meaning of `\l_peek_token`. If that is absent, `\use_none_delimit_by_q_stop:w` cleans up, and we call `_peek_true:w`. Otherwise, the token can be a non-outer macro or a primitive mark whose parameter or replacement text contains `outer`, it can be the primitive `\outer`, or it can be an outer token. Macros and marks would have `ma` in the part before the first occurrence of `outer`; the meaning of `\outer` has nothing after `outer`, contrarily to outer macros; and that covers all cases, calling `_peek_true:w` or `_peek_false:w` as appropriate. Here, there is no *<search token>*, so we feed a dummy `\scan_stop:` to the `_peek_token_generic:NNTF` function.

```

19653 \group_begin:
19654   \cs_set_protected:Npn \_peek_tmp:w #1 \q_stop
19655   {
19656     \cs_new_protected:Npn \_peek_execute_branches_N_type:
19657     {
19658       \if_int_odd:w
19659         \if_catcode:w \exp_not:N \l_peek_token { 0 \exp_stop_f: \fi:
19660         \if_catcode:w \exp_not:N \l_peek_token } 0 \exp_stop_f: \fi:
19661         \if_meaning:w \l_peek_token \c_space_token 0 \exp_stop_f: \fi:
19662         1 \exp_stop_f:
19663         \exp_after:wN \_peek_N_type:w
19664         \token_to_meaning:N \l_peek_token
19665         \q_mark \_peek_N_type_aux:nnw
19666         #1 \q_mark \use_none_delimit_by_q_stop:w
19667         \q_stop
19668         \exp_after:wN \_peek_true:w
19669       \else:
19670         \exp_after:wN \_peek_false:w
19671       \fi:
19672     }
19673     \cs_new_protected:Npn \_peek_N_type:w ##1 #1 ##2 \q_mark ##3
19674     { ##3 {##1} {##2} }
19675   }
19676   \exp_after:wN \_peek_tmp:w \tl_to_str:n { outer } \q_stop

```

```

19677 \group_end:
19678 \cs_new_protected:Npn \__peek_N_type_aux:nnw #1 #2 #3 \fi:
19679 {
19680   \fi:
19681   \tl_if_in:noTF {#1} { \tl_to_str:n {ma} }
19682     { \__peek_true:w }
19683     { \tl_if_empty:nTF {#2} { \__peek_true:w } { \__peek_false:w } }
19684 }
19685 \cs_new_protected:Npn \peek_N_type:TF
19686 { \__peek_token_generic:NNTF \__peek_execute_branches_N_type: \scan_stop: }
19687 \cs_new_protected:Npn \peek_N_type:T
19688 { \__peek_token_generic:NNT \__peek_execute_branches_N_type: \scan_stop: }
19689 \cs_new_protected:Npn \peek_N_type:F
19690 { \__peek_token_generic:NNTF \__peek_execute_branches_N_type: \scan_stop: }

(End definition for \peek_N_type:TF and others. These functions are documented on page 221.)

19691 </initex | package>

```

39 l3luatex implementation

```

19692 <*initex | package>

```

39.1 Breaking out to Lua

```

19693 <*tex>

```

\lua_now_x:n Wrappers around the primitives. As with engines other than LuaTeX these have to be macros, we give them the same status in all cases. When LuaTeX is not in use, simply give an error message/

```

19694 \lua_now_x:n \lua_now:n #1 { \luatex_directlua:D {#1} }
19695 \lua_now:n \lua_now:n #1 { \lua_now_x:n { \exp_not:n {#1} } }
19696 \lua_shipout_x:n \lua_shipout_x:n #1 { \luatex_latelua:D {#1} }
19697 \lua_shipout:n \lua_shipout:n #1
19698 { \lua_shipout_x:n { \exp_not:n {#1} } }
19699 \lua_escape_x:n \lua_escape_x:n #1 { \luatex_luaescapestring:D {#1} }
19700 \lua_escape:n \lua_escape:n #1 { \lua_escape_x:n { \exp_not:n {#1} } }
19701 \sys_if_engine luatex:F
19702 {
19703   \clist_map_inline:nn
19704     { \lua_now_x:n , \lua_now:n , \lua_escape_x:n , \lua_escape:n }
19705     {
19706       \cs_set:Npn #1 ##1
19707       {
19708         \__msg_kernel_expandable_error:nnn
19709           { kernel } { luatex-required } { #1 }
19710       }
19711     }
19712   \clist_map_inline:nn
19713     { \lua_shipout_x :n , \lua_shipout:n }
19714     {
19715       \cs_set_protected:Npn #1 ##1
19716       {
19717         \__msg_kernel_error:nnn
19718           { kernel } { luatex-required } { #1 }

```



```

19719     }
19720   }
19721 }

```

(End definition for `\lua_now_x:n` and others. These functions are documented on page 222.)

39.2 Messages

```

19722 \_msg_kernel_new:nnnn { kernel } { luatex-required }
19723 { LuaTeX~engine~not~in~use!~Ignoring~#1. }
19724 {
19725   The~feature~you~are~using~is~only~available~
19726   with~the~LuaTeX~engine.~LaTeX3~ignored~'~#1'.
19727 }
19728 </tex>

```

39.3 Lua functions for internal use

```

19729 <*lua>

```

l3kernel Create a table for the kernel's own use.

```

19730 l3kernel = l3kernel or {}

```

(End definition for `l3kernel`.)

Various local copies of standard functions: naming convention is to retain the full text but replace all `.` by `_`.

```

19731 local tex_setcatcode = tex.setcatcode
19732 local tex_sprint = tex.sprint
19733 local tex_write = tex.write
19734 local unicode_utf8_char = unicode.utf8.char

```

l3kernel.strcmp String comparison which gives the same results as pdfTeX's `\pdfstrcmp`, although the ordering should likely not be relied upon!

```

19735 local function strcmp (A, B)
19736   if A == B then
19737     tex_write("0")
19738   elseif A < B then
19739     tex_write("-1")
19740   else
19741     tex_write("1")
19742   end
19743 end
19744 l3kernel.strcmp = strcmp

```

(End definition for `l3kernel.strcmp`.)

l3kernel.charcat Creating arbitrary chars needs a category code table. As set up here, one may have been assigned earlier (see `l3bootstrap`) or a hard-coded one is used. The latter is intended for format mode and should be adjusted to match an eventual allocator.

```

19745 local charcat_table = l3kernel.charcat_table or 1
19746 local function charcat (charcode, catcode)
19747   tex_setcatcode(charcat_table, charcode, catcode)
19748   tex_sprint(charcat_table, unicode_utf8_char(charcode))
19749 end
19750 l3kernel.charcat = charcat

```

(End definition for `l3kernel.charcat`.)

39.4 Generic Lua and font support

19751 \langle *initex \rangle

A small amount of generic code is used by almost all LuaTeX material so needs to be loaded by the format.

```
19752 attribute_count_name = "g__alloc_attribute_int"
19753 bytecode_count_name  = "g__alloc_bytecode_int"
19754 chunkname_count_name  = "g__alloc_chunkname_int"
19755 whatsit_count_name    = "g__alloc_whatsit_int"
19756 require("ltnluaTeX")
```

With the above available the font loader code used by plain TeX and L^ATeX 2_ε when used with LuaTeX can be loaded here. This is thus being treated more-or-less as part of the engine itself.

```
19757 require("luaotfload-main")
19758 local _void = luaotfload.main()
19759  $\langle$ /initex $\rangle$ 

19760  $\langle$ /lua $\rangle$ 
19761  $\langle$ /initex | package $\rangle$ 
```

40 l3drivers Implementation

19762 \langle *initex | package \rangle
 19763 \langle @@=driver \rangle

Whilst there is a reasonable amount of code overlap between drivers, it is much clearer to have the blocks more-or-less separated than run in together and DocStripped out in parts. As such, most of the following is set up on a per-driver basis, though there is some common code (again given in blocks not interspersed with other material).

All the file identifiers are up-front so that they come out in the right place in the files.

```
19764  $\langle$ *package $\rangle$ 
19765 \ProvidesExplFile
19766  $\langle$ *dvipdfmx $\rangle$ 
19767 {l3dvipdfmx.def}{\ExplFileDate}{\ExplFileVersion}
19768 {L3 Experimental driver: dvipdfmx}
19769  $\langle$ /dvipdfmx $\rangle$ 
19770  $\langle$ *dvips $\rangle$ 
19771 {l3dvips.def}{\ExplFileDate}{\ExplFileVersion}
19772 {L3 Experimental driver: dvips}
19773  $\langle$ /dvips $\rangle$ 
19774  $\langle$ *dvisvgm $\rangle$ 
19775 {l3dvisvgm.def}{\ExplFileDate}{\ExplFileVersion}
19776 {L3 Experimental driver: dvisvgm}
19777  $\langle$ /dvisvgm $\rangle$ 
19778  $\langle$ *pdfmode $\rangle$ 
19779 {l3pdfmode.def}{\ExplFileDate}{\ExplFileVersion}
19780 {L3 Experimental driver: PDF mode}
19781  $\langle$ /pdfmode $\rangle$ 
19782  $\langle$ *xdvipdfmx $\rangle$ 
19783 {l3xdvipdfmx.def}{\ExplFileDate}{\ExplFileVersion}
19784 {L3 Experimental driver: xdvipdfmx}
19785  $\langle$ /xdvipdfmx $\rangle$ 
```

```
19786 \end{package}
```

40.1 pdfmode driver

```
19787 \begin{pdfmode}
```

The direct PDF driver covers both pdfTeX and LuaTeX. The latter renames/restructures the driver primitives but this can be handled at one level of abstraction. As such, we avoid using two separate drivers for this material at the cost of some x-type definitions to get everything expanded up-front.

40.1.1 Basics

`_driver_literal:n` This is equivalent to `\special{pdf:}` but the engine can track it. Without the `direct` keyword everything is kept in sync: the transformation matrix is set to the current point automatically. Note that this is still inside the text (BT ...ET block).

```
19788 \cs_new_protected:Npx \_driver\_literal:n #1
19789 {
19790   \cs_if_exist:NTF \luatex_pdfextension:D
19791   { \luatex_pdfextension:D literal }
19792   { \pdfTEX_pdfliteral:D }
19793   {#1}
19794 }
```

(End definition for `_driver_literal:n`.)

`_driver_scope_begin:` Higher-level interfaces for saving and restoring the graphic state.

```
\_driver\_scope\_end:
19795 \cs_new_protected:Npx \_driver\_scope\_begin:
19796 {
19797   \cs_if_exist:NTF \luatex_pdfextension:D
19798   { \luatex_pdfextension:D save \scan_stop: }
19799   { \pdfTEX_pdfsave:D }
19800 }
19801 \cs_new_protected:Npx \_driver\_scope\_end:
19802 {
19803   \cs_if_exist:NTF \luatex_pdfextension:D
19804   { \luatex_pdfextension:D restore \scan_stop: }
19805   { \pdfTEX_pdfrestore:D }
19806 }
```

(End definition for `_driver_scope_begin:` and `_driver_scope_end:.`)

`_driver_matrix:n` Here the appropriate function is set up to insert an affine matrix into the PDF. With pdfTeX and LuaTeX in direct PDF output mode there is a primitive for this, which only needs the rotation/scaling/skew part.

```
19807 \cs_new_protected:Npx \_driver\_matrix:n #1
19808 {
19809   \cs_if_exist:NTF \luatex_pdfextension:D
19810   { \luatex_pdfextension:D setmatrix }
19811   { \pdfTEX_pdfsetmatrix:D }
19812   {#1}
19813 }
```

(End definition for `_driver_matrix:n`.)

40.1.2 Color

`\l__driver_current_color_tl` The current color in driver-dependent format: pick up the package-mode data if available.

```

19814 \tl_new:N \l__driver_current_color_tl
19815 \tl_set:Nn \l__driver_current_color_tl { 0~g~0~G }
19816 \*package
19817 \AtBeginDocument
19818 {
19819   \@ifpackageloaded { color }
19820   { \tl_set:Nn \l__driver_current_color_tl { \current@color } }
19821   { }
19822 }
19823 \*package

```

(End definition for `\l__driver_current_color_tl`.)

`\l__driver_color_stack_int` pdfTeX and LuaTeX have multiple stacks available, and to track which one is in use a variable is required.

```

19824 \int_new:N \l__driver_color_stack_int

```

(End definition for `\l__driver_color_stack_int`.)

`__driver_color_ensure_current:` There is a dedicated primitive/primitive interface for setting colors. As with scoping, this approach is not suitable for cached operations.

`__driver_color_reset:`

```

19825 \cs_new_protected:Npx \__driver_color_ensure_current:
19826 {
19827   \cs_if_exist:NTF \luatex_pdfextension:D
19828   { \luatex_pdfextension:D colorstack }
19829   { \pdfTEX_pdfcolorstack:D }
19830   \exp_not:N \l__driver_color_stack_int push
19831   { \exp_not:N \l__driver_current_color_tl }
19832   \group_insert_after:N \exp_not:N \__driver_color_reset:
19833 }
19834 \cs_new_protected:Npx \__driver_color_reset:
19835 {
19836   \cs_if_exist:NTF \luatex_pdfextension:D
19837   { \luatex_pdfextension:D colorstack }
19838   { \pdfTEX_pdfcolorstack:D }
19839   \exp_not:N \l__driver_color_stack_int pop \scan_stop:
19840 }

```

(End definition for `__driver_color_ensure_current:` and `__driver_color_reset:`.)

```

19841 \*pdfmode

```

40.2 dvipdfmx driver

```

19842 \*dvipdfmx |xdvipdfmx

```

The `dvipdfmx` shares code with the PDF mode one (using the common section to this file) but also with `xdvipdfmx`. The latter is close to identical to `dvipdfmx` and so

all of the code here is extracted for both drivers, with some `clean up` for `xdvipdfmx` as required.

40.2.1 Basics

`_driver_literal:n` Equivalent to `pdf:content` but favoured as the link to the pdfTeX primitive approach is clearer.

```
19843 \cs_new_protected:Npn \_driver_literal:n #1
19844 { \tex_special:D { pdf:literal~ #1 } }
```

(End definition for `_driver_literal:n`.)

`_driver_scope_begin:` Scoping is done using direct PDF operations here.

```
\_driver_scope_end:
19845 \cs_new_protected:Npn \_driver_scope_begin:
19846 { \_driver_literal:n { q } }
19847 \cs_new_protected:Npn \_driver_scope_end:
19848 { \_driver_literal:n { Q } }
```

(End definition for `_driver_scope_begin:` and `_driver_scope_end:.`)

`_driver_matrix:n` With (x)dvipdfmx the matrix has to include a translation part: that is always zero and so is built in here so that the same internal interface works for all PDF-related drivers.

```
19849 \cs_new_protected:Npn \_driver_matrix:n #1
19850 { \_driver_literal:n { #1 \c_space_tl 0~0~cm } }
```

(End definition for `_driver_matrix:n`.)

40.2.2 Color

`\l_driver_current_color_tl` The current color in driver-dependent format.

```
19851 \tl_new:N \l_driver_current_color_tl
19852 \tl_set:Nn \l_driver_current_color_tl { [ 0 ] }
19853 (*package)
19854 \AtBeginDocument
19855 {
19856   \@ifpackageloaded { color }
19857   { \tl_set:Nn \l_driver_current_color_tl { \current@color } }
19858   { }
19859 }
19860 </package>
```

(End definition for `\l_driver_current_color_tl`.)

`_driver_color_ensure_current:` Directly set the color using the specials with optimisation support.

```
\_driver_color_reset:
19861 \cs_new_protected:Npn \_driver_color_ensure_current:
19862 {
19863   \tex_special:D { pdf:bcolor~\l_driver_current_color_tl }
19864   \group_insert_after:N \_driver_color_reset:
19865 }
19866 \cs_new_protected:Npn \_driver_color_reset:
19867 { \tex_special:D { pdf:ecolor } }
```

(End definition for `_driver_color_ensure_current:` and `_driver_color_reset:.`)

```
19868 </dvipdfmx | xdvipdfmx>
```

40.3 xdvipdfmx driver

```
19869 <*xdvipdfmx>
```

40.3.1 Color

`_driver_color_ensure_current:` The L^AT_EX 2_ε driver uses dvips-like specials so there has to be a change of set up if color is loaded.

```
\_driver_color_reset:
19870 <*package>
19871 \AtBeginDocument
19872 {
19873   \@ifpackageloaded { color }
19874   {
19875     \cs_set_protected:Npn \_driver_color_ensure_current:
19876     {
19877       \tex_special:D { color~push~\_driver_current_color_tl }
19878       \group_insert_after:N \_driver_color_reset:
19879     }
19880     \cs_set_protected:Npn \_driver_color_reset:
19881     { \tex_special:D { color~pop } }
19882   }
19883   { }
19884 }
19885 </package>
```

(End definition for `_driver_color_ensure_current:` and `_driver_color_reset:`.)

```
19886 </xdvipdfmx>
```

40.4 Common code for PDF production

As all of the drivers which understand PDF-targeted specials act in much the same way there is a lot of shared code. Rather than try to DocStrip it interspersed with the above, we collect all of it here.

```
19887 <*dvipdfmx | pdfmode | xdvipdfmx>
```

40.4.1 Box operations

`_driver_box_use_clip:N` The general method is to save the current location, define a clipping path equivalent to the bounding box, then insert the content at the current position and in a zero width box. The “real” width is then made up using a horizontal skip before tidying up. There are other approaches that can be taken (for example using XForm objects), but the logic here shares as much code as possible and uses the same conversions (and so same rounding errors) in all cases.

```
19888 \cs_new_protected:Npn \_driver_box_use_clip:N #1
19889 {
19890   \_driver_scope_begin:
19891   \_driver_literal:n
19892   {
19893     0~
19894     \dim_to_decimal_in_bp:n { -\box_dp:N #1 } ~
19895     \dim_to_decimal_in_bp:n { \box_wd:N #1 } ~
19896     \dim_to_decimal_in_bp:n { \box_ht:N #1 + \box_dp:N #1 } ~
19897     re~W~n
```

```

19898     }
19899     \hbox_overlap_right:n { \box_use:N #1 }
19900     \__driver_scope_end:
19901     \skip_horizontal:n { \box_wd:N #1 }
19902 }

```

(End definition for __driver_box_use_clip:N.)

__driver_box_use_rotate:Nn

\l__driver_cos_fp
\l__driver_sin_fp

Rotations are set using an affine transformation matrix which therefore requires sine/cosine values not the angle itself. We store the rounded values to avoid rounding twice. There are also a couple of comparisons to ensure that -0 is not written to the output, as this avoids any issues with problematic display programs. Note that numbers are compared to 0 after rounding.

```

19903 \cs_new_protected:Npn \__driver_box_use_rotate:Nn #1#2
19904 {
19905     \__driver_scope_begin:
19906     \box_set_wd:Nn #1 \c_zero_dim
19907     \fp_set:Nn \l__driver_cos_fp { round ( cosd ( #2 ) , 5 ) }
19908     \fp_compare:nNnTF \l__driver_cos_fp = \c_zero_fp
19909         { \fp_zero:N \l__driver_cos_fp }
19910     \fp_set:Nn \l__driver_sin_fp { round ( sind ( #2 ) , 5 ) }
19911     \__driver_matrix:n
19912     {
19913         \fp_use:N \l__driver_cos_fp \c_space_tl
19914         \fp_compare:nNnTF \l__driver_sin_fp = \c_zero_fp
19915             { 0~0 }
19916         {
19917             \fp_use:N \l__driver_sin_fp
19918             \c_space_tl
19919             \fp_eval:n { -\l__driver_sin_fp }
19920         }
19921         \c_space_tl
19922         \fp_use:N \l__driver_cos_fp
19923     }
19924     \box_use:N #1
19925     \__driver_scope_end:
19926 }
19927 \fp_new:N \l__driver_cos_fp
19928 \fp_new:N \l__driver_sin_fp

```

(End definition for __driver_box_use_rotate:Nn, \l__driver_cos_fp, and \l__driver_sin_fp.)

__driver_box_use_scale:Nnn

The same idea as for rotation but without the complexity of signs and cosines.

```

19929 \cs_new_protected:Npn \__driver_box_use_scale:Nnn #1#2#3
19930 {
19931     \__driver_scope_begin:
19932     \__driver_matrix:n
19933     {
19934         \fp_eval:n { round ( #2 , 5 ) } ~
19935         0~0~
19936         \fp_eval:n { round ( #3 , 5 ) }
19937     }
19938     \hbox_overlap_right:n { \box_use:N #1 }
19939     \__driver_scope_end:
19940 }

```

(End definition for `_driver_box_use_scale:Nnn`.)

40.5 Drawing

`_driver_draw_literal:n` Pass data through using a dedicated interface.
`_driver_draw_literal:x`

```

19941 \cs_new_eq:NN \_driver_draw_literal:n \_driver_literal:n
19942 \cs_generate_variant:Nn \_driver_draw_literal:n { x }

```

(End definition for `_driver_draw_literal:n`.)

`_driver_draw_begin:` No special requirements here, so simply set up a drawing scope.
`_driver_draw_end:`

```

19943 \cs_new_protected:Npn \_driver_draw_begin:
19944 { \_driver_draw_scope_begin: }
19945 \cs_new_protected:Npn \_driver_draw_end:
19946 { \_driver_draw_scope_end: }

```

(End definition for `_driver_draw_begin:` and `_driver_draw_end:.`)

`_driver_draw_scope_begin:` In contrast to a general scope, a drawing scope is always done using the PDF operators
`_driver_draw_scope_end:` so is the same for all relevant drivers.

```

19947 \cs_new_protected:Npn \_driver_draw_scope_begin:
19948 { \_driver_draw_literal:n { q } }
19949 \cs_new_protected:Npn \_driver_draw_scope_end:
19950 { \_driver_draw_literal:n { Q } }

```

(End definition for `_driver_draw_scope_begin:` and `_driver_draw_scope_end:.`)

`_driver_draw_moveto:nn` Path creation operations all resolve directly to PDF primitive steps, with only the need to
`_driver_draw_lineto:nn` convert to bp. Notice that x-type expansion is included here to ensure that any variable
`_driver_draw_curveto:nnnnnn` values are forced to literals before any possible caching.
`_driver_draw_rectangle:nnnn`

```

19951 \cs_new_protected:Npn \_driver_draw_moveto:nn #1#2
19952 {
19953   \_driver_draw_literal:x
19954   { \dim_to_decimal_in_bp:n {#1} ~ \dim_to_decimal_in_bp:n {#2} ~ m }
19955 }
19956 \cs_new_protected:Npn \_driver_draw_lineto:nn #1#2
19957 {
19958   \_driver_draw_literal:x
19959   { \dim_to_decimal_in_bp:n {#1} ~ \dim_to_decimal_in_bp:n {#2} ~ l }
19960 }
19961 \cs_new_protected:Npn \_driver_draw_curveto:nnnnnn #1#2#3#4#5#6
19962 {
19963   \_driver_draw_literal:x
19964   {
19965     \dim_to_decimal_in_bp:n {#1} ~ \dim_to_decimal_in_bp:n {#2} ~
19966     \dim_to_decimal_in_bp:n {#3} ~ \dim_to_decimal_in_bp:n {#4} ~
19967     \dim_to_decimal_in_bp:n {#5} ~ \dim_to_decimal_in_bp:n {#6} ~
19968     c
19969   }
19970 }
19971 \cs_new_protected:Npn \_driver_draw_rectangle:nnnn #1#2#3#4
19972 {
19973   \_driver_draw_literal:x
19974   {

```



```

19975         \dim_to_decimal_in_bp:n {#1} ~ \dim_to_decimal_in_bp:n {#2} ~
19976         \dim_to_decimal_in_bp:n {#3} ~ \dim_to_decimal_in_bp:n {#4} ~
19977         re
19978     }
19979 }

```

(End definition for `__driver_draw_moveto:nn` and others.)

`__driver_draw_evenodd_rule:` The even-odd rule here can be implemented as a simply switch.

```

\__driver_draw_nonzero_rule:
    \g__driver_draw_eor_bool
19980 \cs_new_protected:Npn \__driver_draw_evenodd_rule:
19981     { \bool_gset_true:N \g__driver_draw_eor_bool }
19982 \cs_new_protected:Npn \__driver_draw_nonzero_rule:
19983     { \bool_gset_false:N \g__driver_draw_eor_bool }
19984 \bool_new:N \g__driver_draw_eor_bool

```

(End definition for `__driver_draw_evenodd_rule:`, `__driver_draw_nonzero_rule:`, and `\g__driver_draw_eor_bool`.)

`__driver_draw_closepath:` Converting paths to output is again a case of mapping directly to PDF operations.

```

    \__driver_draw_stroke:
\__driver_draw_closestroke:
    \__driver_draw_fill:
    \__driver_draw_fillstroke:
    \__driver_draw_clip:
\__driver_draw_discardpath:
19985 \cs_new_protected:Npn \__driver_draw_closepath:
19986     { \__driver_draw_literal:n { h } }
19987 \cs_new_protected:Npn \__driver_draw_stroke:
19988     { \__driver_draw_literal:n { S } }
19989 \cs_new_protected:Npn \__driver_draw_closestroke:
19990     { \__driver_draw_literal:n { s } }
19991 \cs_new_protected:Npn \__driver_draw_fill:
19992     {
19993         \__driver_draw_literal:x
19994         { f \bool_if:NT \g__driver_draw_eor_bool * }
19995     }
19996 \cs_new_protected:Npn \__driver_draw_fillstroke:
19997     {
19998         \__driver_draw_literal:x
19999         { B \bool_if:NT \g__driver_draw_eor_bool * }
20000     }
20001 \cs_new_protected:Npn \__driver_draw_clip:
20002     {
20003         \__driver_draw_literal:x
20004         { W \bool_if:NT \g__driver_draw_eor_bool * }
20005     }
20006 \cs_new_protected:Npn \__driver_draw_discardpath:
20007     { \__driver_draw_literal:n { n } }

```

(End definition for `__driver_draw_closepath:` and others.)

`__driver_draw_dash:nn` Converting paths to output is again a case of mapping directly to PDF operations.

```

    \__driver_draw_dash:n
\__driver_draw_linewidth:n
\__driver_draw_miterlimit:n
    \__driver_draw_cap_but:
    \__driver_draw_cap_round:
    \__driver_draw_cap_rectangle:
\__driver_draw_join_miter:
\__driver_draw_join_round:
\__driver_draw_join_bevel:
20008 \cs_new_protected:Npn \__driver_draw_dash:nn #1#2
20009     {
20010         \__driver_draw_literal:x
20011         {
20012             [ ~
20013             \clist_map_function:nn {#1} \__driver_draw_dash:n
20014             ] ~
20015             \dim_to_decimal_in_bp:n {#2} ~ d
20016         }

```

```

20017 }
20018 \cs_new:Npn \__driver_draw_dash:n #1
20019 { \dim_to_decimal_in_bp:n {#1} ~ }
20020 \cs_new_protected:Npn \__driver_draw_linewidth:n #1
20021 {
20022   \__driver_draw_literal:x
20023   { \dim_to_decimal_in_bp:n {#1} ~ w }
20024 }
20025 \cs_new_protected:Npn \__driver_draw_miterlimit:n #1
20026 { \__driver_draw_literal:x { \fp_eval:n {#1} ~ M } }
20027 \cs_new_protected:Npn \__driver_draw_cap_but:
20028 { \__driver_draw_literal:n { 0 ~ J } }
20029 \cs_new_protected:Npn \__driver_draw_cap_round:
20030 { \__driver_draw_literal:n { 1 ~ J } }
20031 \cs_new_protected:Npn \__driver_draw_cap_rectangle:
20032 { \__driver_draw_literal:n { 2 ~ J } }
20033 \cs_new_protected:Npn \__driver_draw_join_miter:
20034 { \__driver_draw_literal:n { 0 ~ j } }
20035 \cs_new_protected:Npn \__driver_draw_join_round:
20036 { \__driver_draw_literal:n { 1 ~ j } }
20037 \cs_new_protected:Npn \__driver_draw_join_bevel:
20038 { \__driver_draw_literal:n { 2 ~ j } }

```

(End definition for __driver_draw_dash:nn and others.)

Yet more fast conversion, all using the FPU to allow for expressions in numerical input.

```

\__driver_draw_color_cmyk:nnnn
\__driver_draw_color_cmyk_fill:nnnn
\__driver_draw_color_cmyk_stroke:nnnn
\__driver_draw_color_cmyk_aux:nnnn
\__driver_draw_color_gray:n
\__driver_draw_color_gray_fill:n
\__driver_draw_color_gray_stroke:n
\__driver_draw_color_gray_aux:n
\__driver_draw_color_rgb:nnn
\__driver_draw_color_rgb_fill:nnn
\__driver_draw_color_rgb_stroke:nnn
\__driver_draw_color_rgb_aux:nnn
20039 \cs_new_protected:Npn \__driver_draw_color_cmyk:nnnn #1#2#3#4
20040 {
20041   \use:x
20042   {
20043     \__driver_draw_color_cmyk_aux:nnnn
20044     { \fp_eval:n {#1} }
20045     { \fp_eval:n {#2} }
20046     { \fp_eval:n {#3} }
20047     { \fp_eval:n {#4} }
20048   }
20049 }
20050 \cs_new_protected:Npn \__driver_draw_color_cmyk_aux:nnnn #1#2#3#4
20051 {
20052   \__driver_draw_literal:n
20053   { #1 ~ #2 ~ #3 ~ #4 ~ k ~ #1 ~ #2 ~ #3 ~ #4 ~ K }
20054 }
20055 \cs_new_protected:Npn \__driver_draw_color_cmyk_fill:nnnn #1#2#3#4
20056 {
20057   \__driver_draw_literal:x
20058   {
20059     \fp_eval:n {#1} ~ \fp_eval:n {#2} ~
20060     \fp_eval:n {#3} ~ \fp_eval:n {#4} ~
20061     k
20062   }
20063 }
20064 \cs_new_protected:Npn \__driver_draw_color_cmyk_stroke:nnnn #1#2#3#4
20065 {
20066   \__driver_draw_literal:x

```

```

20067     {
20068         \fp_eval:n {#1} ~ \fp_eval:n {#2} ~
20069         \fp_eval:n {#3} ~ \fp_eval:n {#4} ~
20070         K
20071     }
20072 }
20073 \cs_new_protected:Npn \__driver_draw_color_gray:n #1
20074 {
20075     \use:x
20076     { \__driver_draw_color_gray_aux:n { \fp_eval:n {#1} } }
20077 }
20078 \cs_new_protected:Npn \__driver_draw_color_gray_aux:n #1
20079 {
20080     \__driver_draw_literal:n { #1 ~ g ~ #1 ~ G }
20081 }
20082 \cs_new_protected:Npn \__driver_draw_color_gray_fill:n #1
20083 { \__driver_draw_literal:x { \fp_eval:n {#1} ~ g } }
20084 \cs_new_protected:Npn \__driver_draw_color_gray_stroke:n #1
20085 { \__driver_draw_literal:x { \fp_eval:n {#1} ~ G } }
20086 \cs_new_protected:Npn \__driver_draw_color_rgb:nnn #1#2#3
20087 {
20088     \use:x
20089     {
20090         \__driver_draw_color_rgb_aux:nnn
20091         { \fp_eval:n {#1} }
20092         { \fp_eval:n {#2} }
20093         { \fp_eval:n {#3} }
20094     }
20095 }
20096 \cs_new_protected:Npn \__driver_draw_color_rgb_aux:nnn #1#2#3
20097 {
20098     \__driver_draw_literal:n
20099     { #1 ~ #2 ~ #3 ~ rg ~ #1 ~ #2 ~ #3 ~ RG }
20100 }
20101 \cs_new_protected:Npn \__driver_draw_color_rgb_fill:nnn #1#2#3
20102 {
20103     \__driver_draw_literal:x
20104     { \fp_eval:n {#1} ~ \fp_eval:n {#2} ~ \fp_eval:n {#3} ~ rg }
20105 }
20106 \cs_new_protected:Npn \__driver_draw_color_rgb_stroke:nnn #1#2#3
20107 {
20108     \__driver_draw_literal:x
20109     { \fp_eval:n {#1} ~ \fp_eval:n {#2} ~ \fp_eval:n {#3} ~ RG }
20110 }

```

(End definition for __driver_draw_color_cmyk:nnnn and others.)

__driver_draw_transformcm:nnnnnn The first four arguments here are floats (the affine matrix), the last two are a displacement vector. Once again, force evaluation to allow for caching.

```

20111 \cs_new_protected:Npn \__driver_draw_transformcm:nnnnnn #1#2#3#4#5#6
20112 {
20113     \__driver_draw_literal:x
20114     {
20115         \fp_eval:n {#1} ~ \fp_eval:n {#2} ~

```

```

20116         \fp_eval:n {#3} ~ \fp_eval:n {#4} ~
20117         \dim_to_decimal_in_bp:n {#5} ~ \dim_to_decimal_in_bp:n {#6} ~
20118         cm
20119     }
20120 }

```

(End definition for `_driver_draw_transformcm:nnnnnn`.)

```

\_driver_draw_hbox:Nnnnnnn
  \l_driver_tmp_box

```

Inserting a T_EX box transformed to the requested position and using the current matrix is done using a mixture of T_EX and low-level manipulation. The offset can be handled by T_EX, so only any rotation/skew/scaling component needs to be done using the matrix operation. As this operation can never be cached, the scope is set directly not using the `draw` version.

```

20121 \cs_new_protected:Npn \_driver_draw_hbox:Nnnnnnn #1#2#3#4#5#6#7
20122 {
20123     \hbox_set:Nn \l_driver_tmp_box
20124     {
20125         \tex_kern:D \_dim_eval:w #6 \_dim_eval_end:
20126         \_driver_scope_begin:
20127         \_driver_draw_transformcm:nnnnnn {#2} {#3} {#4} {#5}
20128         { Opt } { Opt }
20129         \box_move_up:nn {#7} { \box_use:N #1 }
20130         \_driver_scope_end:
20131     }
20132     \box_set_wd:Nn \l_driver_tmp_box { Opt }
20133     \box_set_ht:Nn \l_driver_tmp_box { Opt }
20134     \box_set_dp:Nn \l_driver_tmp_box { Opt }
20135     \box_use:N \l_driver_tmp_box
20136 }
20137 \box_new:N \l_driver_tmp_box

```

(End definition for `_driver_draw_hbox:Nnnnnnn` and `\l_driver_tmp_box`.)

```

20138 </dvipdfmx | pdfmode | xdvipdfmx>

```

40.6 dvips driver

```

20139 <dvips>

```

40.6.1 Basics

```

\_driver_literal:n

```

In the case of `dvips` there is no build-in saving of the current position, and so some additional PostScript is required to set up the transformation matrix and also to restore it afterwards. Notice the use of the stack to save the current position “up front” and to move back to it at the end of the process.

```

20140 \cs_new_protected:Npn \_driver_literal:n #1
20141 {
20142     \tex_special:D
20143     {
20144         ps:
20145         currentpoint~
20146         currentpoint~translate~
20147         #1 ~
20148         neg~exch~neg~exch~translate
20149     }
20150 }

```

(End definition for `_driver_literal:n`.)

`_driver_scope_begin:` Scope saving/restoring is done directly with no need to worry about the transformation matrix. General scoping is only for the graphics stack so the lower-cost `gsave/grstore` pair are used.

```
20151 \cs_new_protected:Npn \_driver_scope_begin:
20152   { \tex_special:D { ps:gsave } }
20153 \cs_new_protected:Npn \_driver_scope_end:
20154   { \tex_special:D { ps:grestore } }
```

(End definition for `_driver_scope_begin:` and `_driver_scope_end:.`)

40.7 Driver-specific auxiliaries

`_driver_absolute_lengths:n` The dvips driver scales all absolute dimensions based on the output resolution selected and any T_EX magnification. Thus for any operation involving absolute lengths there is a correction to make. This is based on `normalscale` from `special.pro` but using the stack rather than a definition to save the current matrix.

```
20155 \cs_new:Npn \_driver_absolute_lengths:n #1
20156   {
20157     matrix~currentmatrix~
20158     Resolution~72~div~VResolution~72~div~scale~
20159     DVImag~dup~scale~
20160     #1 ~
20161     setmatrix
20162   }
```

(End definition for `_driver_absolute_lengths:n`.)

40.7.1 Box operations

`_driver_box_use_clip:N` Much the same idea as for the PDF mode version but with a slightly different syntax for creating the clip path. To avoid any scaling issues we need the absolute length auxiliary here.

```
20163 \cs_new_protected:Npn \_driver_box_use_clip:N #1
20164   {
20165     \_driver_scope_begin:
20166     \_driver_literal:n
20167     {
20168       \_driver_absolute_lengths:n
20169       {
20170         0 ~
20171         \dim_to_decimal_in_bp:n { \box_dp:N #1 } ~
20172         \dim_to_decimal_in_bp:n { \box_wd:N #1 } ~
20173         \dim_to_decimal_in_bp:n { -\box_ht:N #1 - \box_dp:N #1 } ~
20174         rectclip
20175       }
20176     }
20177     \hbox_overlap_right:n { \box_use:N #1 }
20178     \_driver_scope_end:
20179     \skip_horizontal:n { \box_wd:N #1 }
20180   }
```

(End definition for `_driver_box_use_clip:N`.)

`__driver_box_use_rotate:Nn` Rotating using dvips does not require that the box dimensions are altered and has a very convenient built-in operation. Zero rotation must be written as 0 not -0 so there is a quick test.

```

20181 \cs_new_protected:Npn \__driver_box_use_rotate:Nn #1#2
20182 {
20183   \__driver_scope_begin:
20184   \__driver_literal:n
20185   {
20186     \fp_compare:nNnTF {#2} = \c_zero_fp
20187     { 0 }
20188     { \fp_eval:n { round ( -#2 , 5 ) } } ~
20189     rotate
20190   }
20191   \box_use:N #1
20192   \__driver_scope_end:
20193 }
20194 % \end{macro}
20195 %
20196 % \begin{macro}{\__driver_box_use_scale:Nnn}
20197 %   The \texttt{dvips} driver once again has a dedicated operation we can
20198 %   use here.
20199 %   \begin{macrocode}
20200 \cs_new_protected:Npn \__driver_box_use_scale:Nnn #1#2#3
20201 {
20202   \__driver_scope_begin:
20203   \__driver_literal:n
20204   {
20205     \fp_eval:n { round ( #2 , 5 ) } ~
20206     \fp_eval:n { round ( #3 , 5 ) } ~
20207     scale
20208   }
20209   \hbox_overlap_right:n { \box_use:N #1 }
20210   \__driver_scope_end:
20211 }

```

(End definition for `__driver_box_use_rotate:Nn`.)

40.7.2 Color

`\l__driver_current_color_tl` The current color in driver-dependent format.

```

20212 \tl_new:N \l__driver_current_color_tl
20213 \tl_set:Nn \l__driver_current_color_tl { gray-0 }
20214 (*package)
20215 \AtBeginDocument
20216 {
20217   \@ifpackageloaded { color }
20218   { \tl_set:Nn \l__driver_current_color_tl { \current@color } }
20219   { }
20220 }
20221 \</package>

```

(End definition for `\l__driver_current_color_tl`.)

`__driver_color_ensure_current:` Directly set the color using the specials: no optimisation here.
`__driver_color_reset:`

```

20222 \cs_new_protected:Npn \__driver_color_ensure_current:
20223 {
20224   \tex_special:D { color~push~\l__driver_current_color_tl }
20225   \group_insert_after:N \__driver_color_reset:
20226 }
20227 \cs_new_protected:Npn \__driver_color_reset:
20228 { \tex_special:D { color~pop } }

(End definition for \__driver_color_ensure_current: and \__driver_color_reset:.)

```

40.8 Drawing

`__driver_draw_literal:n` Literals with no positioning (using `ps:` each one is positioned but cut off from everything else, so no good for the stepwise approach needed here).

```

20229 \cs_new_protected:Npn \__driver_draw_literal:n #1
20230 { \tex_special:D { ps:: ~ #1 } }
20231 \cs_generate_variant:Nn \__driver_draw_literal:n { x }

(End definition for \__driver_draw_literal:n.)

```

`__driver_draw_begin:` The `ps::[begin]` special here deals with positioning but allows us to continue on to a matching `ps::[end]`: contrast with `ps:`, which positions but where we can't split material between separate calls. The `@beginspecial/@endspecial` pair are from `special.pro` and correct the scale and *y*-axis direction. The reference point at the start of the box is saved (as `l3x/l3y`) as it is needed when inserting various items.

```

20232 \cs_new_protected:Npn \__driver_draw_begin:
20233 {
20234   \tex_special:D { ps::[begin] }
20235   \tex_special:D { ps::~~save }
20236   \tex_special:D { ps::~~/l3x~currentpoint~/l3y~exch~def~def }
20237   \tex_special:D { ps::~~@beginspecial }
20238 }
20239 \cs_new_protected:Npn \__driver_draw_end:
20240 {
20241   \tex_special:D { ps::~~@endspecial }
20242   \tex_special:D { ps::~~restore }
20243   \tex_special:D { ps::[end] }
20244 }

(End definition for \__driver_draw_begin: and \__driver_draw_end:.)

```

`__driver_draw_scope_begin:` Scope here may need to contain saved definitions, so the entire memory rather than just the graphic state has to be sent to the stack.

```

20245 \cs_new_protected:Npn \__driver_draw_scope_begin:
20246 { \__driver_draw_literal:n { save } }
20247 \cs_new_protected:Npn \__driver_draw_scope_end:
20248 { \__driver_draw_literal:n { restore } }

(End definition for \__driver_draw_scope_begin: and \__driver_draw_scope_end:.)

```

`__driver_draw_moveto:nn` Path creation operations mainly resolve directly to PostScript primitive steps, with only the need to convert to `bp`. Notice that `x-type` expansion is included here to ensure that any variable values are forced to literals before any possible caching. There is no native

`__driver_draw_lineto:nn`

`__driver_draw_rectangle:nnnn`

`__driver_draw_curveto:nnnnnn`

rectangular path command (without also clipping, filling or stroking), so that task is done using a small amount of PostScript.

```

20249 \cs_new_protected:Npn \__driver_draw_moveto:nn #1#2
20250 {
20251   \__driver_draw_literal:x
20252   { \dim_to_decimal_in_bp:n {#1} ~ \dim_to_decimal_in_bp:n {#2} ~ moveto }
20253 }
20254 \cs_new_protected:Npn \__driver_draw_lineto:nn #1#2
20255 {
20256   \__driver_draw_literal:x
20257   { \dim_to_decimal_in_bp:n {#1} ~ \dim_to_decimal_in_bp:n {#2} ~ lineto }
20258 }
20259 \cs_new_protected:Npn \__driver_draw_rectangle:nnnn #1#2#3#4
20260 {
20261   \__driver_draw_literal:x
20262   {
20263     \dim_to_decimal_in_bp:n {#4} ~ \dim_to_decimal_in_bp:n {#3} ~
20264     \dim_to_decimal_in_bp:n {#1} ~ \dim_to_decimal_in_bp:n {#2} ~
20265     moveto~dup~0~rlineto~exch~0~exch~rlineto~neg~0~rlineto~closepath
20266   }
20267 }
20268 \cs_new_protected:Npn \__driver_draw_curveto:nnnnnn #1#2#3#4#5#6
20269 {
20270   \__driver_draw_literal:x
20271   {
20272     \dim_to_decimal_in_bp:n {#1} ~ \dim_to_decimal_in_bp:n {#2} ~
20273     \dim_to_decimal_in_bp:n {#3} ~ \dim_to_decimal_in_bp:n {#4} ~
20274     \dim_to_decimal_in_bp:n {#5} ~ \dim_to_decimal_in_bp:n {#6} ~
20275     curveto
20276   }
20277 }

```

(End definition for __driver_draw_moveto:nn and others.)

__driver_draw_evenodd_rule: The even-odd rule here can be implemented as a simply switch.

```

\__driver_draw_nonzero_rule:
  \g__driver_draw_eor_bool
20278 \cs_new_protected:Npn \__driver_draw_evenodd_rule:
20279 { \bool_gset_true:N \g__driver_draw_eor_bool }
20280 \cs_new_protected:Npn \__driver_draw_nonzero_rule:
20281 { \bool_gset_false:N \g__driver_draw_eor_bool }
20282 \bool_new:N \g__driver_draw_eor_bool

```

(End definition for __driver_draw_evenodd_rule:, __driver_draw_nonzero_rule:, and \g__driver_draw_eor_bool.)

__driver_draw_closepath: Unlike PDF, PostScript doesn't track separate colors for strokes and other elements. It is also desirable to have the `clip` keyword after a stroke or fill. To achieve those outcomes, there is some work to do. For color, if a stroke or fill color is defined it is used for the relevant operation, with a graphic scope inserted as required. That does mean that once such a color is set all further uses inside the same scope have to use scoping: see also **__driver_draw_fillstroke:** the color set up functions. For clipping, the required ordering is achieved using a T_EX switch. All of the operations end with a new path instruction as they do not terminate (again in contrast to PDF).

```

20283 \cs_new_protected:Npn \__driver_draw_closepath:
20284 { \__driver_draw_literal:n { closepath } }

```



```

20285 \cs_new_protected:Npn \__driver_draw_stroke:
20286 {
20287   \__driver_draw_literal:n { currentdict~/l3sc-known~{gsave~l3sc}~if }
20288   \__driver_draw_literal:n { stroke }
20289   \__driver_draw_literal:n { currentdict~/l3sc-known~{grestore}~if }
20290   \bool_if:NT \g__driver_draw_clip_bool
20291   {
20292     \__driver_draw_literal:x
20293     {
20294       \bool_if:NT \g__driver_draw_eor_bool { eo }
20295       clip
20296     }
20297   }
20298   \__driver_draw_literal:n { newpath }
20299   \bool_gset_false:N \g__driver_draw_clip_bool
20300 }
20301 \cs_new_protected:Npn \__driver_draw_closestroke:
20302 {
20303   \__driver_draw_closepath:
20304   \__driver_draw_stroke:
20305 }
20306 \cs_new_protected:Npn \__driver_draw_fill:
20307 {
20308   \__driver_draw_literal:n { currentdict~/l3fc-known~{gsave~l3fc}~if }
20309   \__driver_draw_literal:x
20310   {
20311     \bool_if:NT \g__driver_draw_eor_bool { eo }
20312     fill
20313   }
20314   \__driver_draw_literal:n { currentdict~/l3fc-known~{grestore}~if }
20315   \bool_if:NT \g__driver_draw_clip_bool
20316   {
20317     \__driver_draw_literal:x
20318     {
20319       \bool_if:NT \g__driver_draw_eor_bool { eo }
20320       clip
20321     }
20322   }
20323   \__driver_draw_literal:n { newpath }
20324   \bool_gset_false:N \g__driver_draw_clip_bool
20325 }
20326 \cs_new_protected:Npn \__driver_draw_fillstroke:
20327 {
20328   \__driver_draw_literal:n { currentdict~/l3fc-known~{gsave~l3fc}~if }
20329   \__driver_draw_literal:x
20330   {
20331     \bool_if:NT \g__driver_draw_eor_bool { eo }
20332     fill
20333   }
20334   \__driver_draw_literal:n { currentdict~/l3fc-known~{grestore}~if }
20335   \__driver_draw_literal:n { currentdict~/l3sc-known~{gsave~l3sc}~if }
20336   \__driver_draw_literal:n { stroke }
20337   \__driver_draw_literal:n { currentdict~/l3sc-known~{grestore}~if }
20338   \bool_if:NT \g__driver_draw_clip_bool

```

```

20339     {
20340         \_driver_draw_literal:x
20341         {
20342             \bool_if:NT \g__driver_draw_eor_bool { eo }
20343             clip
20344         }
20345     }
20346     \_driver_draw_literal:n { newpath }
20347     \bool_gset_false:N \g__driver_draw_clip_bool
20348 }
20349 \cs_new_protected:Npn \_driver_draw_clip:
20350 { \bool_gset_true:N \g__driver_draw_clip_bool }
20351 \bool_new:N \g__driver_draw_clip_bool
20352 \cs_new_protected:Npn \_driver_draw_discardpath:
20353 {
20354     \bool_if:NT \g__driver_draw_clip_bool
20355     {
20356         \_driver_draw_literal:x
20357         {
20358             \bool_if:NT \g__driver_draw_eor_bool { eo }
20359             clip
20360         }
20361     }
20362     \_driver_draw_literal:n { newpath }
20363     \bool_gset_false:N \g__driver_draw_clip_bool
20364 }

```

(End definition for _driver_draw_closepath: and others.)

Converting paths to output is again a case of mapping directly to PostScript operations.

```

\_driver_draw_dash:nn
\_driver_draw_dash:n
\_driver_draw_linewidth:n
\_driver_draw_miterlimit:n
\_driver_draw_cap_but:
\_driver_draw_cap_round:
\_driver_draw_cap_rectangle:
\_driver_draw_join_miter:
\_driver_draw_join_round:
\_driver_draw_join_bevel:
20365 \cs_new_protected:Npn \_driver_draw_dash:nn #1#2
20366 {
20367     \_driver_draw_literal:x
20368     {
20369         [ ~
20370         \clist_map_function:nN {#1} \_driver_draw_dash:n
20371         ] ~
20372         \dim_to_decimal_in_bp:n {#2} ~ setdash
20373     }
20374 }
20375 \cs_new:Npn \_driver_draw_dash:n #1
20376 { \dim_to_decimal_in_bp:n {#1} ~ }
20377 \cs_new_protected:Npn \_driver_draw_linewidth:n #1
20378 {
20379     \_driver_draw_literal:x
20380     { \dim_to_decimal_in_bp:n {#1} ~ setlinewidth }
20381 }
20382 \cs_new_protected:Npn \_driver_draw_miterlimit:n #1
20383 { \_driver_draw_literal:x { \fp_eval:n {#1} ~ setmiterlimit } }
20384 \cs_new_protected:Npn \_driver_draw_cap_but:
20385 { \_driver_draw_literal:n { 0 ~ setlinecap } }
20386 \cs_new_protected:Npn \_driver_draw_cap_round:
20387 { \_driver_draw_literal:n { 1 ~ setlinecap } }
20388 \cs_new_protected:Npn \_driver_draw_cap_rectangle:

```

```

20389 { \_driver\_draw\_literal:n { 2 ~ setlinecap } }
20390 \cs\_new\_protected:Npn \_driver\_draw\_join\_miter:
20391 { \_driver\_draw\_literal:n { 0 ~ setlinejoin } }
20392 \cs\_new\_protected:Npn \_driver\_draw\_join\_round:
20393 { \_driver\_draw\_literal:n { 1 ~ setlinejoin } }
20394 \cs\_new\_protected:Npn \_driver\_draw\_join\_bevel:
20395 { \_driver\_draw\_literal:n { 2 ~ setlinejoin } }

```

(End definition for _driver_draw_dash:nn and others.)

```

\_driver\_draw\_color\_reset: To allow color to be defined for strokes and fills separately and to respect scoping, the
    \_driver\_draw\_color\_cmyk:nnnn data needs to be stored at the PostScript level. We cannot undefine (local) fill/stroke
    \_driver\_draw\_color\_cmyk\_fill:nnnn colors once set up but we can set them blank to improve performance slightly.
    \_driver\_draw\_color\_cmyk\_stroke:nnnn
\_driver\_draw\_color\_gray:n
    \_driver\_draw\_color\_gray\_fill:n
    \_driver\_draw\_color\_gray\_stroke:n
\_driver\_draw\_color\_rgb:nnn
    \_driver\_draw\_color\_rgb\_fill:nnn
    \_driver\_draw\_color\_rgb\_stroke:nnn
20396 \cs\_new\_protected:Npn \_driver\_draw\_color\_reset:
20397 {
20398   \_driver\_draw\_literal:n { currentdic~/l3fc~known~{ /l3fc~ { } ~def }~if }
20399   \_driver\_draw\_literal:n { currentdic~/l3sc~known~{ /l3sc~ { } ~def }~if }
20400 }
20401 \cs\_new\_protected:Npn \_driver\_draw\_color\_cmyk:nnnn #1#2#3#4
20402 {
20403   \_driver\_draw\_literal:x
20404   {
20405     \fp\_eval:n {#1} ~ \fp\_eval:n {#2} ~
20406     \fp\_eval:n {#3} ~ \fp\_eval:n {#4} ~
20407     setcmykcolor ~
20408   }
20409   \_driver\_draw\_color\_reset:
20410 }
20411 \cs\_new\_protected:Npn \_driver\_draw\_color\_cmyk\_fill:nnnn #1#2#3#4
20412 {
20413   \_driver\_draw\_literal:x
20414   {
20415     /l3fc ~
20416     {
20417       \fp\_eval:n {#1} ~ \fp\_eval:n {#2} ~
20418       \fp\_eval:n {#3} ~ \fp\_eval:n {#4} ~
20419       setcmykcolor
20420     } ~
20421     def
20422   }
20423 }
20424 \cs\_new\_protected:Npn \_driver\_draw\_color\_cmyk\_stroke:nnnn #1#2#3#4
20425 {
20426   \_driver\_draw\_literal:x
20427   {
20428     /l3sc ~
20429     {
20430       \fp\_eval:n {#1} ~ \fp\_eval:n {#2} ~
20431       \fp\_eval:n {#3} ~ \fp\_eval:n {#4} ~
20432       setcmykcolor
20433     } ~
20434     def
20435   }
20436 }

```

```

20437 \cs_new_protected:Npn \__driver_draw_color_gray:n #1
20438 {
20439   \__driver_draw_literal:x { fp_eval:n {#1} ~ setgray }
20440   \__driver_draw_color_reset:
20441 }
20442 \cs_new_protected:Npn \__driver_draw_color_gray_fill:n #1
20443 { \__driver_draw_literal:x { /l3fc ~ { \fp_eval:n {#1} ~ setgray } ~ def } }
20444 \cs_new_protected:Npn \__driver_draw_color_gray_stroke:n #1
20445 { \__driver_draw_literal:x { /l3sc ~ { \fp_eval:n {#1} ~ setgray } ~ def } }
20446 \cs_new_protected:Npn \__driver_draw_color_rgb:nnn #1#2#3
20447 {
20448   \__driver_draw_literal:x
20449   {
20450     \fp_eval:n {#1} ~ \fp_eval:n {#2} ~ \fp_eval:n {#3} ~
20451     setrgbcolor
20452   }
20453   \__driver_draw_color_reset:
20454 }
20455 \cs_new_protected:Npn \__driver_draw_color_rgb_fill:nnn #1#2#3
20456 {
20457   \__driver_draw_literal:x
20458   {
20459     /l3fc ~
20460     {
20461       \fp_eval:n {#1} ~ \fp_eval:n {#2} ~ \fp_eval:n {#3} ~
20462       setrgbcolor
20463     } ~
20464     def
20465   }
20466 }
20467 \cs_new_protected:Npn \__driver_draw_color_rgb_stroke:nnn #1#2#3
20468 {
20469   \__driver_draw_literal:x
20470   {
20471     /l3sc ~
20472     {
20473       \fp_eval:n {#1} ~ \fp_eval:n {#2} ~ \fp_eval:n {#3} ~
20474       setrgbcolor
20475     } ~
20476     def
20477   }
20478 }

```

(End definition for __driver_draw_color_reset: and others.)

`__driver_draw_transformcm:nnnnnn`

The first four arguments here are floats (the affine matrix), the last two are a displacement vector. Once again, force evaluation to allow for caching.

```

20479 \cs_new_protected:Npn \__driver_draw_transformcm:nnnnnn #1#2#3#4#5#6
20480 {
20481   \__driver_draw_literal:x
20482   {
20483     [
20484       \fp_eval:n {#1} ~ \fp_eval:n {#2} ~
20485       \fp_eval:n {#3} ~ \fp_eval:n {#4} ~

```

```

20486         \dim_to_decimal_in_bp:n {#5} ~ \dim_to_decimal_in_bp:n {#6} ~
20487     ] ~
20488     concat
20489 }
20490 }

```

(End definition for `__driver_draw_transformcm:nnnnnn`.)

`__driver_draw_hbox:Nnnnnnn` Inside a picture `@beginspecial/@endspecial` are active, which is normally a good thing but means that the position and scaling will be off if the box is inserted directly. Instead, we need to reverse the effect of the (normally desirable) shift/scaling within the box. That requires knowing where the reference point for the drawing is: saved as `l3x/l3y` at the start of the picture. Transformation here is relative to the drawing origin so has to be done purely in driver code not using TeX offsets.

```

20491 \cs_new_protected:Npn \__driver_draw_hbox:Nnnnnnn #1#2#3#4#5#6#7
20492 {
20493     \__driver_scope_begin:
20494     \tex_special:D { ps::[end] }
20495     \__driver_draw_transformcm:nnnnnn {#2} {#3} {#4} {#5} {#6} {#7}
20496     \tex_special:D { ps::~72~Resolution~div~72~VResolution~div~neg~scale }
20497     \tex_special:D { ps::~magscale~{1~DVIImag~div~dup~scale}~if }
20498     \tex_special:D { ps::~l3x~neg~l3y~neg~translate }
20499     \group_begin:
20500         \box_set_wd:Nn #1 { Opt }
20501         \box_set_ht:Nn #1 { Opt }
20502         \box_set_dp:Nn #1 { Opt }
20503         \box_use:N #1
20504     \group_end:
20505     \tex_special:D { ps::[begin] }
20506     \__driver_scope_end:
20507 }

```

(End definition for `__driver_draw_hbox:Nnnnnnn`.)

```
20508 </dvips>
```

40.9 dvisvgm driver

```
20509 <*dvisvgm>
```

40.9.1 Basics

`__driver_literal:n` Unlike the other drivers, the requirements for making SVG files mean that we can't conveniently transform all operations to the current point. That makes life a bit more tricky later as that needs to be accounted for. A new line is added after each call to help to keep the output readable for debugging.

```

20510 \cs_new_protected:Npn \__driver_literal:n #1
20511 { \tex_special:D { dvisvgm:raw~ #1 { ?nl } } }

```

(End definition for `__driver_literal:n`.)

`__driver_scope_begin:` A scope in SVG terms is slightly different to the other drivers as operations have to be
`__driver_scope_end:` “tied” to these not simply inside them.

```

20512 \cs_new_protected:Npn \__driver_scope_begin:
20513 { \__driver_literal:n { <g> } }

```

```

20514 \cs_new_protected:Npn \__driver_scope_end:
20515 { \__driver_literal:n { </g> } }

```

(End definition for __driver_scope_begin: and __driver_scope_end:.)

40.10 Driver-specific auxiliaries

__driver_scope_begin:n In SVG transformations, clips and so on are attached directly to scopes so we need a way or allowing for that. This is rather more useful that **__driver_scope_begin:** as a result. No assumptions are made about the nature of the scoped operation(s).

```

20516 \cs_new_protected:Npn \__driver_scope_begin:n #1
20517 { \__driver_literal:n { <g~ #1 > } }

```

(End definition for __driver_scope_begin:n.)

40.10.1 Box operations

__driver_box_use_clip:N Clipping in SVG is more involved than with other drivers. The first issue is that the clipping path must be defined separately from where it is used, so we need to track how many paths have applied. The naming here uses **l3cp** as the namespace with a number following. Rather than use a rectangular operation, we define the path manually as this allows it to have a depth: easier than the alternative approach of shifting content up and down using scopes to allow for the depth of the **T_EX** box and keep the reference point the same!

\g__driver_clip_path_int

```

20518 \cs_new_protected:Npn \__driver_box_use_clip:N #1
20519 {
20520   \int_gincr:N \g__driver_clip_path_int
20521   \__driver_literal:n
20522     { < clipPath-id = " l3cp \int_use:N \g__driver_clip_path_int " > }
20523   \__driver_literal:n
20524     {
20525       <
20526         path ~ d =
20527         "
20528           M ~ 0 ~
20529             \dim_to_decimal:n { -\box_dp:N #1 } ~
20530             L ~ \dim_to_decimal:n { \box_wd:N #1 } ~
20531             \dim_to_decimal:n { -\box_dp:N #1 } ~
20532             L ~ \dim_to_decimal:n { \box_wd:N #1 } ~
20533             \dim_to_decimal:n { \box_ht:N #1 + \box_dp:N #1 } ~
20534             L ~ 0 ~
20535             \dim_to_decimal:n { \box_ht:N #1 + \box_dp:N #1 } ~
20536             Z
20537         "
20538       />
20539     }
20540   \__driver_literal:n
20541     { < /clipPath > }

```

In general the SVG set up does not try to transform coordinates to the current point. For clipping we need to do that, so have a transformation here to get us to the right place, and a matching one just before the **T_EX** box is inserted to get things back on track. The

clip path needs to come between those two such that it lines up with the current point, as does the \TeX box.

```

20542 \__driver_scope_begin:n
20543 {
20544     transform =
20545     "
20546         translate ( { ?x } , { ?y } ) ~
20547         scale ( 1 , -1 )
20548     "
20549 }
20550 \__driver_scope_begin:n
20551 {
20552     clip-path = "url ( \c_hash_str l3cp \int_use:N \g__driver_clip_path_int ) "
20553 }
20554 \__driver_scope_begin:n
20555 {
20556     transform =
20557     "
20558         scale ( -1 , 1 ) ~
20559         translate ( { ?x } , { ?y } ) ~
20560         scale ( -1 , -1 )
20561     "
20562 }
20563 \box_use:N #1
20564 \__driver_scope_end:
20565 \__driver_scope_end:
20566 \__driver_scope_end:
20567 % \skip_horizontal:n { \box_wd:N #1 }
20568 }
20569 \int_new:N \g__driver_clip_path_int

```

(End definition for $\backslash_driver_box_use_clip:N$ and $\backslash_driver_clip_path_int$.)

$\backslash_driver_box_use_rotate:Nn$ Rotation has a dedicated operation which includes a centre-of-rotation optional pair. That can be picked up from the driver syntax, so there is no need to worry about the transformation matrix.

```

20570 \cs_new_protected:Npn \__driver_box_use_rotate:Nn #1#2
20571 {
20572     \__driver_scope_begin:n
20573     {
20574         transform =
20575         "
20576             rotate
20577             ( \fp_eval:n { round ( -#2 , 5 ) } , ~ { ?x } , ~ { ?y } )
20578         "
20579     }
20580     \box_use:N #1
20581     \__driver_scope_end:
20582 }

```

(End definition for $\backslash_driver_box_use_rotate:Nn$.)

$\backslash_driver_box_use_scale:Nnn$ In contrast to rotation, we have to account for the current position in this case. That is done using a couple of translations in addition to the scaling (which is therefore done backward with a flip).

```

20583 \cs_new_protected:Npn \__driver_box_use_scale:Nnn #1#2#3
20584 {
20585   \__driver_scope_begin:n
20586   {
20587     transform =
20588     "
20589       translate ( { ?x } , { ?y } ) ~
20590       scale
20591       (
20592         \fp_eval:n { round ( -#2 , 5 ) } ,
20593         \fp_eval:n { round ( -#3 , 5 ) }
20594       ) ~
20595       translate ( { ?x } , { ?y } ) ~
20596       scale ( -1 )
20597     "
20598   }
20599   \hbox_overlap_right:n { \box_use:N #1 }
20600   \__driver_scope_end:
20601 }

```

(End definition for __driver_box_use_scale:Nnn.)

40.10.2 Color

\l__driver_current_color_tl The current color in driver-dependent format: the same as for dvips.

```

20602 \tl_new:N \l__driver_current_color_tl
20603 \tl_set:Nn \l__driver_current_color_tl { gray~0 }
20604 \*package
20605 \AtBeginDocument
20606 {
20607   \ifpackageloaded { color }
20608   { \tl_set:Nn \l__driver_current_color_tl { \current@color } }
20609   { }
20610 }
20611 \*package

```

(End definition for \l__driver_current_color_tl.)

__driver_color_ensure_current: Directly set the color: same as dvips.

```

\__driver_color_reset: 20612 \cs_new_protected:Npn \__driver_color_ensure_current:
20613 {
20614   \tex_special:D { color~push~\l__driver_current_color_tl }
20615   \group_insert_after:N \__driver_color_reset:
20616 }
20617 \cs_new_protected:Npn \__driver_color_reset:
20618 { \tex_special:D { color~pop } }

```

(End definition for __driver_color_ensure_current: and __driver_color_reset:.)

40.11 Drawing

__driver_draw_literal:n The same as the more general literal call.

```

\__driver_draw_literal:x 20619 \cs_new_eq:NN \__driver_draw_literal:n \__driver_literal:n
20620 \cs_generate_variant:Nn \__driver_draw_literal:n { x }

```


(End definition for `_driver_draw_literal:n`.)

`_driver_draw_begin:` A drawing needs to be set up such that the co-ordinate system is translated. That is
`_driver_draw_end:` done inside a scope, which as described below

```
20621 \cs_new_protected:Npn \_driver\_draw\_begin:
20622 {
20623   \_driver\_draw\_scope\_begin:
20624   \_driver\_draw\_scope:n { transform="translate({?x},{?y})~scale(1,-1)" }
20625 }
20626 \cs_new_protected:Npn \_driver\_draw\_end:
20627 { \_driver\_draw\_scope\_end: }
```

(End definition for `_driver_draw_begin:` and `_driver_draw_end:.`)

`_driver_draw_scope_begin:` Several settings that with other drivers are “stand alone” have to be given as part of
`_driver_draw_scope_end:` a scope in SVG. As a result, there is a need to provide a mechanism to automatically
`_driver_draw_scope:n` close these extra scopes. That is done using a dedicated function and a pair of tracking
`_driver_draw_scope:x` variables. Within each graphics scope we use a global variable to do the work, with a
`\g_driver_draw_scope_int` group used to save the value between scopes. The result is that no direct action is needed
`\l_driver_draw_scope_int` when creating a scope.

```
20628 \cs_new_protected:Npn \_driver\_draw\_scope\_begin:
20629 {
20630   \int_set_eq:NN
20631   \l\_driver\_draw\_scope\_int
20632   \g\_driver\_draw\_scope\_int
20633   \group\_begin:
20634   \int_gset:Nn \g\_driver\_draw\_scope\_int { 0 }
20635 }
20636 \cs_new_protected:Npn \_driver\_draw\_scope\_end:
20637 {
20638   \prg_replicate:nn
20639   { \g\_driver\_draw\_scope\_int }
20640   { \_driver\_draw\_literal:n { </g> } }
20641   \group\_end:
20642   \int_gset_eq:NN
20643   \g\_driver\_draw\_scope\_int
20644   \l\_driver\_draw\_scope\_int
20645 }
20646 \cs_new_protected:Npn \_driver\_draw\_scope:n #1
20647 {
20648   \_driver\_draw\_literal:n { <g~ #1 > }
20649   \int_gincr:N \g\_driver\_draw\_scope\_int
20650 }
20651 \cs_generate_variant:Nn \_driver\_draw\_scope:n { x }
20652 \int_new:N \g\_driver\_draw\_scope\_int
20653 \int_new:N \l\_driver\_draw\_scope\_int
```

(End definition for `_driver_draw_scope_begin:` and others.)

`_driver_draw_moveto:nn` Once again, some work is needed to get path constructs correct. Rather than write the
`_driver_draw_lineto:nn` values as they are given, the entire path needs to be collected up before being output in
`_driver_draw_rectangle:nnnn` one go. For that we use a dedicated storage routine, which will add spaces as required.
`_driver_draw_curveto:nnnnnn` Since paths should be fully expanded there is no need to worry about the internal x-type
`_driver_draw_add_to_path:n` expansion.
`\g_driver_draw_path_tl`

```

20654 \cs_new_protected:Npn \__driver_draw_moveto:nn #1#2
20655 {
20656   \__driver_draw_add_to_path:n
20657   { M ~ \dim_to_decimal:n {#1} ~ \dim_to_decimal:n {#2} }
20658 }
20659 \cs_new_protected:Npn \__driver_draw_lineto:nn #1#2
20660 {
20661   \__driver_draw_add_to_path:n
20662   { L ~ \dim_to_decimal:n {#1} ~ \dim_to_decimal:n {#2} }
20663 }
20664 \cs_new_protected:Npn \__driver_draw_rectangle:nnnn #1#2#3#4
20665 {
20666   \__driver_draw_add_to_path:n
20667   {
20668     M ~ \dim_to_decimal:n {#1} ~ \dim_to_decimal:n {#2}
20669     h ~ \dim_to_decimal:n {#3} ~
20670     v ~ \dim_to_decimal:n {#4} ~
20671     h ~ \dim_to_decimal:n { -#3 } ~
20672     Z
20673   }
20674 }
20675 \cs_new_protected:Npn \__driver_draw_curveto:nnnnnn #1#2#3#4#5#6
20676 {
20677   \__driver_draw_add_to_path:n
20678   {
20679     C ~
20680     \dim_to_decimal:n {#1} ~ \dim_to_decimal:n {#2} ~
20681     \dim_to_decimal:n {#3} ~ \dim_to_decimal:n {#4} ~
20682     \dim_to_decimal:n {#5} ~ \dim_to_decimal:n {#6}
20683   }
20684 }
20685 \cs_new_protected:Npn \__driver_draw_add_to_path:n #1
20686 {
20687   \tl_gset:Nx \g__driver_draw_path_tl
20688   {
20689     \g__driver_draw_path_tl
20690     \tl_if_empty:NF \g__driver_draw_path_tl { \c_space_tl }
20691     #1
20692   }
20693 }
20694 \tl_new:N \g__driver_draw_path_tl

```

(End definition for __driver_draw_moveto:nn and others.)

The fill rules here have to be handled as scopes.

```

20695 \cs_new_protected:Npn \__driver_draw_evenodd_rule:
20696 { \__driver_draw_scope:n { fill-rule="evenodd" } }
20697 \cs_new_protected:Npn \__driver_draw_nonzero_rule:
20698 { \__driver_draw_scope:n { fill-rule="nonzero" } }

```

(End definition for __driver_draw_evenodd_rule: and __driver_draw_nonzero_rule:.)

Setting fill and stroke effects and doing clipping all has to be done using scopes. This means setting up the various requirements in a shared auxiliary which deals with the bits and pieces. Clipping paths are reused for path drawing: not essential but avoids

```

\__driver_draw_path:n
\__driver_draw_closepath:
\__driver_draw_stroke:
\__driver_draw_closestroke:
\__driver_draw_fill:
\__driver_draw_fillstroke:
\__driver_draw_clip:
\__driver_draw_discardpath:
\g__driver_draw_clip_bool
\g__driver_draw_path_int

```

constructing them twice. Discarding a path needs a separate function as it's not quite the same.

```

20699 \cs_new_protected:Npn \__driver_draw_closepath:
20700 { \__driver_draw_add_to_path:n { Z } }
20701 \cs_new_protected:Npn \__driver_draw_path:n #1
20702 {
20703   \bool_if:NTF \g__driver_draw_clip_bool
20704   {
20705     \int_gincr:N \g__driver_clip_path_int
20706     \__driver_draw_literal:x
20707     {
20708       < clipPath-id = " l3cp \int_use:N \g__driver_clip_path_int " >
20709       { ?nl }
20710       <path-d=" \g__driver_draw_path_tl "/> { ?nl }
20711       < /clipPath > { ? nl }
20712       <
20713         use-xlink:href =
20714         "\c_hash_str l3path \int_use:N \g__driver_path_int " ~
20715         #1
20716       />
20717     }
20718     \__driver_draw_scope:x
20719     {
20720       clip-path =
20721       "url( \c_hash_str l3cp \int_use:N \g__driver_clip_path_int)"
20722     }
20723   }
20724   {
20725     \__driver_draw_literal:x
20726     { <path ~ d=" \g__driver_draw_path_tl " ~ #1 /> }
20727   }
20728   \tl_gclear:N \g__driver_draw_path_tl
20729   \bool_gset_false:N \g__driver_draw_clip_bool
20730 }
20731 \int_new:N \g__driver_path_int
20732 \cs_new_protected:Npn \__driver_draw_stroke:
20733 { \__driver_draw_path:n { style="fill:none" } }
20734 \cs_new_protected:Npn \__driver_draw_closestroke:
20735 {
20736   \__driver_draw_closepath:
20737   \__driver_draw_stroke:
20738 }
20739 \cs_new_protected:Npn \__driver_draw_fill:
20740 { \__driver_draw_path:n { style="stroke:none" } }
20741 \cs_new_protected:Npn \__driver_draw_fillstroke:
20742 { \__driver_draw_path:n { } }
20743 \cs_new_protected:Npn \__driver_draw_clip:
20744 { \bool_gset_true:N \g__driver_draw_clip_bool }
20745 \bool_new:N \g__driver_draw_clip_bool
20746 \cs_new_protected:Npn \__driver_draw_discardpath:
20747 {
20748   \bool_if:NT \g__driver_draw_clip_bool
20749   {
20750     \int_gincr:N \g__driver_clip_path_int

```

```

20751     \_driver_draw_literal:x
20752     {
20753         < clipPath-id = " l3cp \int_use:N \g__driver_clip_path_int " >
20754             { ?nl }
20755             <path-d=" \g__driver_draw_path_tl "/> { ?nl }
20756             < /clipPath >
20757         }
20758     \_driver_draw_scope:x
20759     {
20760         clip-path =
20761             "url( \c_hash_str l3cp \int_use:N \g__driver_clip_path_int)"
20762     }
20763 }
20764 \tl_gclear:N \g__driver_draw_path_tl
20765 \bool_gset_false:N \g__driver_draw_clip_bool
20766 }

```

(End definition for _driver_draw_path:n and others.)

All of these ideas are properties of scopes in SVG. The only slight complexity is converting the dash array properly (doing any required maths).

```

\__driver_draw_dash:nn
\__driver_draw_dash:n
\__driver_draw_dash_aux:nn
\__driver_draw_linewidth:n
\__driver_draw_miterlimit:n
\__driver_draw_cap_but:
\__driver_draw_cap_round:
\__driver_draw_cap_rectangle:
\__driver_draw_join_miter:
\__driver_draw_join_round:
\__driver_draw_join_bevel:
20767 \cs_new_protected:Npn \_driver_draw_dash:nn #1#2
20768 {
20769     \use:x
20770     {
20771         \_driver_draw_dash_aux:nn
20772         { \clist_map_function:nn {#1} \__driver_draw_dash:n }
20773         { \dim_to_decimal:n {#2} }
20774     }
20775 }
20776 \cs_new:Npn \_driver_draw_dash:n #1
20777 { , \dim_to_decimal_in_bp:n {#1} }
20778 \cs_new_protected:Npn \_driver_draw_dash_aux:nn #1#2
20779 {
20780     \_driver_draw_scope:x
20781     {
20782         stroke-dasharray =
20783         "
20784             \tl_if_empty:oTF { \use_none:n #1 }
20785             { none }
20786             { \use_none:n #1 }
20787         " ~
20788         stroke-offset=" #2 "
20789     }
20790 }
20791 \cs_new_protected:Npn \_driver_draw_linewidth:n #1
20792 { \_driver_draw_scope:x { stroke-width=" \dim_to_decimal:n {#1} " } }
20793 \cs_new_protected:Npn \_driver_draw_miterlimit:n #1
20794 { \_driver_draw_scope:x { stroke-miterlimit=" \fp_eval:n {#1} " } }
20795 \cs_new_protected:Npn \_driver_draw_cap_but:
20796 { \_driver_draw_scope:n { stroke-linecap="butt" } }
20797 \cs_new_protected:Npn \_driver_draw_cap_round:
20798 { \_driver_draw_scope:n { stroke-linecap="round" } }
20799 \cs_new_protected:Npn \_driver_draw_cap_rectangle:

```

```

20800 { \_driver\_draw\_scope:n { stroke-linecap="square" } }
20801 \cs\_new\_protected:Npn \_driver\_draw\_join\_miter:
20802 { \_driver\_draw\_scope:n { stroke-linejoin="miter" } }
20803 \cs\_new\_protected:Npn \_driver\_draw\_join\_round:
20804 { \_driver\_draw\_scope:n { stroke-linejoin="round" } }
20805 \cs\_new\_protected:Npn \_driver\_draw\_join\_bevel:
20806 { \_driver\_draw\_scope:n { stroke-linejoin="bevel" } }

```

(End definition for _driver_draw_dash:nn and others.)

SVG only works with RGB colors, so there is some conversion to do. The values also need to be given as percentages, which means a little more maths.

```

\_driver\_draw\_color\_cmyk:nnnn
\_driver\_draw\_color\_cmyk\_fill:nnnn
\_driver\_draw\_color\_cmyk\_stroke:nnnn
\_driver\_draw\_color\_gray:n
\_driver\_draw\_color\_gray\_fill:n
\_driver\_draw\_color\_gray\_stroke:n
\_driver\_draw\_color\_rgb:nnnn
\_driver\_draw\_color\_rgb\_fill:nnnn
\_driver\_draw\_color\_rgb\_stroke:nnnn

20807 \cs\_new\_protected:Npn \_driver\_draw\_color\_cmyk\_aux:NNnnnnn #1#2#3#4#5#6
20808 {
20809   \use:x
20810   {
20811     \_driver\_draw\_color\_rgb\_auxii:nnn
20812     { \fp\_eval:n { -100 * ( (#3) * ( 1 - (#6) ) - 1 ) } }
20813     { \fp\_eval:n { -100 * ( (#4) * ( 1 - (#6) ) + #6 - 1 ) } }
20814     { \fp\_eval:n { -100 * ( (#5) * ( 1 - (#6) ) + #6 - 1 ) } }
20815   }
20816   #1 #2
20817 }
20818 \cs\_new\_protected:Npn \_driver\_draw\_color\_cmyk:nnnn
20819 { \_driver\_draw\_color\_cmyk\_aux:NNnnnnn \c\_true\_bool \c\_true\_bool }
20820 \cs\_new\_protected:Npn \_driver\_draw\_color\_cmyk\_fill:nnnn
20821 { \_driver\_draw\_color\_cmyk\_aux:NNnnnnn \c\_false\_bool \c\_true\_bool }
20822 \cs\_new\_protected:Npn \_driver\_draw\_color\_cmyk\_stroke:nnnn
20823 { \_driver\_draw\_color\_cmyk\_aux:NNnnnnn \c\_true\_bool \c\_false\_bool }
20824 \cs\_new\_protected:Npn \_driver\_draw\_color\_gray\_aux:NNn #1#2#3
20825 {
20826   \use:x
20827   {
20828     \_driver\_draw\_color\_gray\_aux:nnn
20829     { \fp\_eval:n { 100 * (#3) } }
20830   }
20831   #1 #2
20832 }
20833 \cs\_new\_protected:Npn \_driver\_draw\_color\_gray\_aux:nnn #1
20834 { \_driver\_draw\_color\_rgb\_auxii:nnnnn {#1} {#1} {#1} }
20835 \cs\_generate\_variant:Nn \_driver\_draw\_color\_gray\_aux:nnn { x }
20836 \cs\_new\_protected:Npn \_driver\_draw\_color\_gray:n
20837 { \_driver\_draw\_color\_gray\_aux:NNn \c\_true\_bool \c\_true\_bool }
20838 \cs\_new\_protected:Npn \_driver\_draw\_color\_gray\_fill:n
20839 { \_driver\_draw\_color\_gray\_aux:NNn \c\_false\_bool \c\_true\_bool }
20840 \cs\_new\_protected:Npn \_driver\_draw\_color\_gray\_stroke:n
20841 { \_driver\_draw\_color\_gray\_aux:NNn \c\_true\_bool \c\_false\_bool }
20842 \cs\_new\_protected:Npn \_driver\_draw\_color\_rgb\_auxi:NNnnn #1#2#3#4#5
20843 {
20844   \use:x
20845   {
20846     \_driver\_draw\_color\_rgb\_auxii:nnnnn
20847     { \fp\_eval:n { 100 * (#3) } }
20848     { \fp\_eval:n { 100 * (#4) } }

```

```

20849         { \fp_eval:n { 100 * (#5) } }
20850     }
20851     #1 #2
20852 }
20853 \cs_new_protected:Npn \__driver_draw_color_rgb_auxii:nnnNN #1#2#3#4#5
20854 {
20855     \__driver_draw_scope:x
20856     {
20857         \bool_if:NT #4
20858         {
20859             fill =
20860             "
20861             rgb
20862             (
20863                 #1 \c_percent_str ,
20864                 #2 \c_percent_str ,
20865                 #3 \c_percent_str
20866             )
20867             "
20868             \bool_if:NT #5 { ~ }
20869         }
20870         \bool_if:NT #5
20871         {
20872             stroke =
20873             "
20874             rgb
20875             (
20876                 #1 \c_percent_str ,
20877                 #2 \c_percent_str ,
20878                 #3 \c_percent_str
20879             )
20880             "
20881         }
20882     }
20883 }
20884 \cs_new_protected:Npn \__driver_draw_color_rgb:nnn
20885 { \__driver_draw_color_rgb_auxi:NNnnn \c_true_bool \c_true_bool }
20886 \cs_new_protected:Npn \__driver_draw_color_rgb_fill:nnn
20887 { \__driver_draw_color_rgb_auxi:NNnnn \c_false_bool \c_true_bool }
20888 \cs_new_protected:Npn \__driver_draw_color_rgb_stroke:nnn
20889 { \__driver_draw_color_rgb_auxi:NNnnn \c_true_bool \c_false_bool }

```

(End definition for __driver_draw_color_cmyk:nnnn and others.)

__driver_draw_transformcm:nnnnnn The first four arguments here are floats (the affine matrix), the last two are a displacement vector. Once again, force evaluation to allow for caching.

```

20890 \cs_new_protected:Npn \__driver_draw_transformcm:nnnnnn #1#2#3#4#5#6
20891 {
20892     \__driver_draw_scope:x
20893     {
20894         transform =
20895         "
20896         matrix
20897         (

```

```

20898         \fp_eval:n {#1} , \fp_eval:n {#2} ,
20899         \fp_eval:n {#3} , \fp_eval:n {#4} ,
20900         \dim_to_decimal:n {#5} , \dim_to_decimal:n {#6}
20901     )
20902     "
20903 }
20904 }

```

(End definition for _driver_draw_transformcm:nnnnnn.)

_driver_draw_hbox:Nnnnnnn No special savings can be made here: simply displace the box inside a scope. As there is nothing to re-box, just make the box passed of zero size.

```

20905 \cs_new_protected:Npn \_driver_draw_hbox:Nnnnnnn #1#2#3#4#5#6#7
20906 {
20907     \_driver_scope_begin:
20908     \_driver_draw_transformcm:nnnnnn {#2} {#3} {#4} {#5} {#6} {#7}
20909     \_driver_literal:n
20910     {
20911         < g~
20912         stroke="none"~
20913         transform="scale(-1,1)~translate({?x},{?y})~scale(-1,-1)"
20914         >
20915     }
20916     \group_begin:
20917     \box_set_wd:Nn #1 { Opt }
20918     \box_set_ht:Nn #1 { Opt }
20919     \box_set_dp:Nn #1 { Opt }
20920     \box_use:N #1
20921     \group_end:
20922     \_driver_literal:n { </g> }
20923     \_driver_scope_end:
20924 }

```

(End definition for _driver_draw_hbox:Nnnnnnn.)

20925 </dvisvgm>

20926 </initex | package>

Index

The italic numbers denote the pages where the corresponding entry is described, numbers underlined point to the definition, all others indicate the places where it is used.

| Symbols | |
|--------------|--|
| ! | <i>183</i> |
| \! | <i>7605</i> |
| \" | <i>6573, 6576, 19395</i> |
| \# | <i>6, 3930, 3962, 6573, 8823</i> |
| \\$ | <i>3929, 6573, 6576</i> |
| \% | <i>3931, 6573, 8825</i> |
| \& | <i>3922, 6573, 6576, 7605, 7606, 12145, 12219</i> |
| && | <i>182</i> |
| \' | <i>19395</i> |
| \(| <i>19561</i> |
| \) | <i>12088, 19561</i> |
| * | <i>183</i> |
| * | <i>3597, 3620, 6746, 6748, 6752, 6760, 12038</i> |
| ** | <i>183</i> |
| + | <i>183, 183</i> |
| \+ | <i>590, 590, 12143, 12149</i> |
| \, | <i>9537, 12104</i> |
| - | <i>183, 183</i> |
| \- | <i>205, 286, 12148</i> |
| \. | <i>19395</i> |
| / | <i>183</i> |
| \/ | <i>285, 12147</i> |
| \: | <i>3928</i> |
| \:: | <i>33, 283, 298, 2061, 2062, 2063, 2064, 2065, 2066, 2067, 2069, 2071, 2078, 2083, 2089, 2208, 2209, 2210, 2211, 2212, 2213, 2214, 2215, 2216, 2217, 2218, 2219, 2220, 2221, 2222, 2223, 2224, 2225, 2226, 2227, 2228, 2229, 2230, 2231, 2232, 2233, 2234, 2235, 2236, 2238, 2243, 2245, 2250, 2255, 2292, 2293, 2294, 2295, 2296</i> |
| \:N | <i>33, 2065, 2218, 2224, 2225, 2229, 2230, 2231, 2295</i> |
| \:V | <i>33, 2083, 2214</i> |
| \:V_unbraced | <i>2237</i> |
| \:c | <i>33, 2067, 2209, 2217, 2219, 2226, 2234, 2235</i> |
| \:error | <i>213, 18361</i> |
| \:f | <i>33, 2071, 2210, 2211, 2212, 2216, 2294</i> |
| \:f_unbraced | <i>2237</i> |
| \:n | <i>33, 2064, 2209, 2212, 2213, 2214, 2220, 2224, 2226, 2227, 2230, 2232, 2233, 2235, 2292, 2295</i> |
| \:o | <i>33, 2069, 2210, 2213, 2215, 2216, 2217, 2221, 2222, 2224, 2225, 2227, 2228, 2231, 2233, 2236, 2293</i> |
| \:o_unbraced | <i>2237, 2292, 2293, 2294, 2295</i> |
| \:p | <i>33, 283, 2066</i> |
| \:v | <i>33, 2083</i> |
| \:v_unbraced | <i>2237</i> |
| \:x | <i>33, 2078, 2208, 2218, 2219, 2220, 2221, 2222, 2223, 2229, 2230, 2231, 2232, 2233, 2234, 2235, 2236</i> |
| \:x_unbraced | <i>2237, 2296</i> |
| < | <i>183</i> |
| = | <i>183</i> |
| > | <i>183</i> |
| ? | <i>183</i> |
| \? | <i>12246</i> |
| ?: | <i>182</i> |
| \\ | <i>2036, 3924, 6573, 7540, 7558, 7560, 7565, 7566, 7580, 7581, 7584, 7585, 7682, 7772, 7780, 7982, 7990, 7997, 8009, 8010, 8035, 8036, 8043, 8069, 8071, 8072, 8103, 8104, 8105, 8106, 8107, 8306, 8310, 8315, 8828, 9056, 9063, 10392, 10393, 10399, 10418, 10431, 10437, 10897, 10900, 10901, 10902, 10909, 10912, 10913, 16294, 16297, 16322, 16323, 16330, 16331, 17392, 17393, 17394, 17395</i> |
| \{ | <i>4, 3925, 6573, 7603, 8104, 8306, 8310, 8311, 8822, 19573</i> |
| \} | <i>5, 3926, 6573, 7604, 8104, 8306, 8310, 8311, 8824, 19573</i> |
| \^ | <i>7, 10, 103, 194, 195, 196, 197, 1724, 2317, 2321, 2734, 3927, 6573, 6576, 6578, 6584, 6646, 7619, 8752, 8788, 12146, 14444, 19395</i> |
| ^ | <i>183</i> |
| \ | <i>3933, 6573, 6576</i> |
| \' | <i>19395</i> |
| | <i>182</i> |
| \~ | <i>2755, 3932, 6573, 6576, 8826, 19395</i> |
| \sqcup | <i>284, 1594, 3597, 3620, 3963, 6573, 7603, 7604, 8037, 8061, 8104, 8106, 8201, 8306, 8310, 8311, 8315, 8316, 8762, 8829</i> |
| A | |
| \A | <i>3598, 3621</i> |
| \AA | <i>19377</i> |

- \aa 19377
 - \above 287
 - \abovedisplayshortskip 288
 - \abovedisplayskip 289
 - \abovewithdelims 290
 - abs 183
 - \accent 291
 - acos 185
 - acosh 185
 - acot 186
 - acoth 186
 - acsc 185
 - acsch 185
 - \adjdemerits 292
 - \adjustspacing 947
 - \advance 168, 184, 293
 - \AE 19378
 - \ae 19378
 - \afterassignment 294
 - \aftergroup 295
 - \alignmark 859
 - \alignat 860
 - asec 185
 - asech 185
 - asin 185
 - asinh 185
 - atan 186
 - atanh 186
 - \AtBeginDocument ... 472, 8509, 17412,
19817, 19854, 19871, 20215, 20605
 - \atop 296
 - \atopwithdelims 297
 - \attribute 861
 - \attributedef 862
 - \autoscaling 1120
 - \autoxspacing 1121
- B**
- \badness 298
 - \baselineskip 299
 - \batchmode 300
 - \begin 12625, 20196, 20199
 - \beginname 863
 - \begingroup 13,
20, 38, 42, 48, 73, 142, 162, 274, 301
 - \beginL 609
 - \beginR 610
 - \belowdisplayshortskip 302
 - \belowdisplayskip 303
 - \binoppenalty 304
 - \bodydir 934
 - bool commands:
 - \bool_do_until:Nn 92, 92, 5820
 - \bool_do_until:nn 93, 93, 5826
 - \bool_do_while:Nn 92, 92, 5820
 - \bool_do_while:nn 93, 93, 5826
 - .bool_gset:N 161, 9973
 - \bool_gset:Nn 91, 5639, 5682
 - \bool_gset_eq:NN 91, 5631, 5672
 - \bool_gset_false:N 90, 5619, 5662,
8269, 8290, 19983, 20281, 20299,
20324, 20347, 20363, 20729, 20765
 - .bool_gset_inverse:N 161, 9981
 - \bool_gset_true:N 90, 5619,
5657, 8234, 19981, 20279, 20350, 20744
 - \bool_if:NTF ... 91, 91, 238, 1926,
5689, 5698, 5699, 5815, 5817, 5821,
5823, 7658, 7663, 7668, 7673, 7678,
8098, 8254, 8287, 9017, 9024, 9752,
9945, 9954, 10175, 10203, 10222,
10224, 10229, 10236, 10260, 10306,
16874, 17276, 19994, 19999, 20004,
20290, 20294, 20311, 20315, 20319,
20331, 20338, 20342, 20354, 20358,
20703, 20748, 20857, 20868, 20870
 - \bool_if:nTF
... 91, 92, 92, 93, 93, 93, 93, 792,
810, 5709, 5724, 5828, 5837, 5841,
5850, 17472, 18369, 18375, 18376,
18384, 18390, 18392, 18469, 19197
 - \bool_if_exist:NTF
... 91, 91, 5703, 5720, 9773, 9789
 - \bool_if_exist_p:N 91, 91, 5720
 - \bool_if_p:N 91, 91, 5689
 - \bool_if_p:n 92, 92, 395, 5640, 5642,
5680, 5685, 5724, 5732, 5807, 5810
 - \bool_lazy_all:nTF
... 213, 214, 214, 214, 214, 18364
 - \bool_lazy_all_p:n .. 214, 214, 18364
 - \bool_lazy_and:nnTF 213, 214, 214,
214, 214, 18373, 19039, 19089, 19543
 - \bool_lazy_and_p:nn
... 214, 214, 214, 18373
 - \bool_lazy_any:nTF
... 213, 214, 214, 214, 214, 18379, 18871
 - \bool_lazy_any_p:n
... 214, 214, 214, 18379, 19042
 - \bool_lazy_or:nnTF 213,
214, 214, 214, 214, 18388, 18947, 19521
 - \bool_lazy_or_p:nn
... 214, 214, 18388, 19546
 - \bool_log:N 91, 91, 5711
 - \bool_log:n 91, 91, 5711
 - \bool_new:N 90, 90, 5617, 5716, 5717,
5718, 5719, 7483, 8232, 8783, 9667,
9668, 9671, 9672, 9676, 9773, 9789,
16586, 19984, 20282, 20351, 20745
 - \bool_not_p:n 92, 92, 5807

- `.bool_set:N` [161](#), [9973](#)
- `\bool_set:Nn` [91](#), [91](#), [5639](#), [5677](#)
- `\bool_set_eq:NN` ... [91](#), [91](#), [5631](#), [5667](#)
- `\bool_set_false:N` [90](#), [90](#), [253](#),
[5619](#), [5652](#), [8861](#), [9001](#), [9009](#), [9019](#),
[9026](#), [9693](#), [10122](#), [10142](#), [10148](#),
[10151](#), [10161](#), [10210](#), [16870](#), [17274](#)
- `.bool_set_inverse:N` [161](#), [9981](#)
- `\bool_set_true:N`
... [90](#), [90](#), [267](#), [5619](#), [5647](#), [8988](#),
[9688](#), [10120](#), [10138](#), [10139](#), [10147](#),
[10156](#), [10217](#), [16888](#), [16903](#), [16934](#)
- `\bool_show:N` .. [91](#), [91](#), [390](#), [5701](#), [5712](#)
- `\bool_show:n` [91](#), [91](#), [5701](#), [5714](#)
- `\bool_until_do:Nn` [93](#), [93](#), [5814](#)
- `\bool_until_do:nn` [93](#), [93](#), [5826](#)
- `\bool_while_do:Nn` [93](#), [93](#), [5814](#)
- `\bool_while_do:nn` [93](#), [93](#), [5826](#)
- `\bool_xor_p:nn` [92](#), [92](#), [5808](#)
- `\c_false_bool`
..... [20](#), [90](#), [269](#), [293](#), [389](#), [392](#),
[393](#), [1457](#), [1497](#), [1540](#), [1545](#), [1589](#),
[1605](#), [1871](#), [1878](#), [2363](#), [5617](#), [5622](#),
[5626](#), [5655](#), [5665](#), [5780](#), [5782](#), [5787](#),
[5811](#), [17452](#), [17506](#), [17521](#), [20821](#),
[20823](#), [20839](#), [20841](#), [20887](#), [20889](#)
- `\g_tmpa_bool` [91](#), [5716](#)
- `\l_tmpa_bool` [91](#), [5716](#)
- `\g_tmpb_bool` [91](#), [5716](#)
- `\l_tmpb_bool` [91](#), [5716](#)
- `\c_true_bool` [20](#), [90](#), [269](#),
[269](#), [311](#), [389](#), [392](#), [393](#), [1497](#), [1589](#),
[1604](#), [1889](#), [5620](#), [5624](#), [5650](#), [5660](#),
[5691](#), [5781](#), [5783](#), [5789](#), [5812](#), [17459](#),
[17467](#), [17481](#), [17488](#), [17497](#), [17510](#),
[17517](#), [20819](#), [20821](#), [20823](#), [20837](#),
[20839](#), [20841](#), [20885](#), [20887](#), [20889](#)
- bool internal commands:
 - `__bool_!:Nw` [5762](#)
 - `__bool_&_0:w` [5786](#)
 - `__bool_&_1:w` [5784](#)
 - `__bool_(:Nw` [5764](#)
 - `__bool_)_0:w` [5780](#)
 - `__bool_)_1:w` [5780](#)
 - `__bool_choose:NNN` .. [5766](#), [5770](#), [5771](#)
 - `__bool_eval_skip_to_end_auxi:Nw`
..... [5786](#)
 - `__bool_eval_skip_to_end_-
auxii:Nw` [5786](#)
 - `__bool_eval_skip_to_end_-
auxiii:Nw` [5786](#)
 - `__bool_get_next:NN`
.. [5750](#), [5752](#), [5763](#), [5767](#), [5784](#), [5785](#)
 - `__bool_if_left_parentheses:wwwn`
..... [5732](#)
 - `__bool_if_or:wwwn` [5732](#)
 - `__bool_if_parse:NNNww` [392](#), [5739](#), [5748](#)
 - `__bool_if_right_parentheses:wwwn`
..... [5732](#)
 - `__bool_lazy_all:n` [18364](#)
 - `__bool_lazy_any:n` [18379](#)
 - `__bool_p:Nw` [5769](#)
 - `__bool_S_0:w` [5780](#)
 - `__bool_S_1:w` [5780](#)
 - `__bool_to_str:n` [5701](#)
 - `__bool_|_0:w` [5784](#)
 - `__bool_|_1:w` [5786](#)
 - `\botmark` [305](#)
 - `\botmarks` [611](#)
 - `\box` [306](#)
 - box commands:
 - `\box_clear:N` [192](#),
[192](#), [16363](#), [16370](#), [16622](#), [16686](#), [16736](#)
 - `box_clear:N` [192](#)
 - `\box_clear_new:N` [192](#), [192](#), [16369](#)
 - `\box_clip:N` . [210](#), [210](#), [210](#), [210](#), [17874](#)
 - `\box_dp:N` .. [193](#), [193](#), [11308](#), [16391](#),
[16398](#), [16757](#), [16758](#), [16828](#), [16830](#),
[16847](#), [16861](#), [17015](#), [17033](#), [17346](#),
[17610](#), [17730](#), [17823](#), [17885](#), [17892](#),
[17897](#), [18034](#), [19894](#), [19896](#), [20171](#),
[20173](#), [20529](#), [20531](#), [20533](#), [20535](#)
 - `\box_gclear:N` [192](#), [16363](#), [16372](#)
 - `\box_gclear_new:N` [192](#), [16369](#)
 - `\box_gset_eq:NN` ... [192](#), [16366](#), [16375](#)
 - `\box_gset_eq_clear:NN` [192](#), [192](#), [16381](#)
 - `\box_gset_to_last:N` [194](#), [16439](#)
 - `\box_ht:N` [193](#), [193](#), [11307](#),
[16391](#), [16400](#), [16681](#), [16731](#), [16759](#),
[16760](#), [16824](#), [16826](#), [16847](#), [16854](#),
[17014](#), [17032](#), [17344](#), [17609](#), [17729](#),
[17822](#), [17902](#), [17910](#), [17915](#), [18031](#),
[18033](#), [19896](#), [20173](#), [20533](#), [20535](#)
 - `\box_if_empty:NTF`
..... [194](#), [194](#), [16433](#), [16436](#), [16437](#)
 - `\box_if_empty_p:N` ... [194](#), [194](#), [16433](#)
 - `\box_if_exist:NTF`
.. [192](#), [192](#), [16370](#), [16372](#), [16387](#), [16470](#)
 - `\box_if_exist_p:N` ... [192](#), [192](#), [16387](#)
 - `\box_if_horizontal:NTF`
..... [194](#), [194](#), [16421](#), [16426](#), [16427](#)
 - `\box_if_horizontal_p:N` [194](#), [194](#), [16421](#)
 - `\box_if_vertical:NTF`
..... [194](#), [194](#), [16421](#), [16430](#), [16431](#)
 - `\box_if_vertical_p:N` [194](#), [194](#), [16421](#)
 - `\box_log:N` [195](#), [195](#), [16456](#)
 - `\box_log:Nnn` [195](#), [195](#), [16456](#)

- \box_move_down:nn [193](#), [766](#), [16410](#),
[17889](#), [17897](#), [17935](#), [17942](#), [18013](#)
- \box_move_left:nn [193](#), [16410](#)
- \box_move_right:nn [193](#), [193](#), [16410](#)
- \box_move_up:nn [193](#), [193](#), [16410](#), [17053](#), [17341](#),
[17906](#), [17915](#), [17949](#), [17962](#), [20129](#)
- \box_new:N [192](#), [192](#), [192](#),
[16355](#), [16445](#), [16446](#), [16447](#), [16448](#),
[16449](#), [16564](#), [16629](#), [17594](#), [20137](#)
- \box_resize:Nnn [209](#), [209](#), [17709](#), [18144](#)
- \box_resize_to_ht:Nn [209](#), [209](#), [17749](#)
- \box_resize_to_ht_plus_dp:Nn [209](#), [209](#), [17749](#)
- \box_resize_to_wd:Nn [209](#), [209](#), [17749](#)
- \box_resize_to_wd_and_ht:Nnn [209](#), [209](#), [17749](#)
- \box_rotate:Nn [210](#), [210](#), [17595](#), [18006](#)
- \box_scale:Nnn [210](#), [210](#), [17815](#), [18166](#)
- \box_set_dp:Nn [194](#), [194](#), [766](#),
[16397](#), [17015](#), [17033](#), [17345](#), [17636](#),
[17849](#), [17852](#), [17892](#), [17900](#), [17938](#),
[17943](#), [18018](#), [20134](#), [20502](#), [20919](#)
- \box_set_eq:NN [192](#), [192](#), [16364](#), [16375](#),
[16746](#), [17035](#), [17349](#), [17920](#), [17967](#)
- \box_set_eq_clear:NN [192](#), [192](#), [16381](#)
- \box_set_ht:Nn [194](#), [194](#),
[16397](#), [17014](#), [17032](#), [17343](#), [17635](#),
[17848](#), [17853](#), [17909](#), [17918](#), [17952](#),
[17965](#), [18016](#), [20133](#), [20501](#), [20918](#)
- \box_set_to_last:N [194](#), [194](#), [16439](#)
- \box_set_wd:Nn [194](#), [194](#), [16397](#),
[17016](#), [17034](#), [17347](#), [17637](#), [17865](#),
[18019](#), [19906](#), [20132](#), [20500](#), [20917](#)
- \box_show:N [195](#), [195](#), [16450](#)
- \box_show:Nnn [195](#), [195](#), [16450](#)
- \box_trim:Nnnnn [210](#), [210](#), [17877](#)
- \box_use:N [193](#), [193](#), [16406](#),
[17050](#), [17053](#), [17131](#), [17268](#), [17338](#),
[17341](#), [17624](#), [17639](#), [17860](#), [17869](#),
[17882](#), [17890](#), [17898](#), [17907](#), [17916](#),
[17928](#), [17936](#), [17942](#), [17950](#), [17963](#),
[18014](#), [18021](#), [19899](#), [19924](#), [19938](#),
[20129](#), [20135](#), [20177](#), [20191](#), [20209](#),
[20503](#), [20563](#), [20580](#), [20599](#), [20920](#)
- \box_use_clear:N [193](#), [193](#), [16406](#)
- \box_viewport:Nnnnn [210](#), [210](#), [17923](#)
- \box_wd:N [194](#), [194](#),
[11306](#), [16391](#), [16402](#), [16761](#), [16762](#),
[16826](#), [16830](#), [16836](#), [16841](#), [16983](#),
[17016](#), [17034](#), [17051](#), [17339](#), [17348](#),
[17611](#), [17731](#), [17824](#), [17929](#), [18033](#),
[18038](#), [18203](#), [18210](#), [19895](#), [19901](#),
[20172](#), [20179](#), [20530](#), [20532](#), [20567](#)
- \c_empty_box [194](#), [195](#), [16364](#), [16366](#), [16445](#), [17128](#)
- \g_tmpa_box [195](#), [16446](#)
- \l_tmpa_box [195](#), [16446](#)
- \g_tmpb_box [195](#), [16446](#)
- \l_tmpb_box [195](#), [16446](#)
- \c_void_box [192](#)
- box internal commands:
 - \l__box_angle_fp [17583](#), [17600](#), [17601](#), [17602](#), [17632](#)
 - \l__box_bottom_dim [17586](#),
[17610](#), [17667](#), [17671](#), [17676](#), [17682](#),
[17687](#), [17691](#), [17700](#), [17702](#), [17720](#),
[17730](#), [17739](#), [17775](#), [17823](#), [17829](#)
 - \l__box_bottom_new_dim [17590](#), [17636](#), [17668](#), [17679](#), [17690](#),
[17701](#), [17738](#), [17828](#), [17849](#), [17853](#)
 - \l__box_cos_fp [17584](#),
[17602](#), [17615](#), [17620](#), [17647](#), [17659](#)
 - \l__box_internal_box [17594](#), [17624](#),
[17625](#), [17631](#), [17635](#), [17636](#), [17637](#),
[17639](#), [17839](#), [17848](#), [17849](#), [17852](#),
[17853](#), [17860](#), [17865](#), [17869](#), [17879](#),
[17887](#), [17890](#), [17892](#), [17895](#), [17898](#),
[17900](#), [17902](#), [17904](#), [17907](#), [17909](#),
[17910](#), [17913](#), [17915](#), [17916](#), [17918](#),
[17920](#), [17925](#), [17933](#), [17936](#), [17938](#),
[17941](#), [17942](#), [17943](#), [17947](#), [17950](#),
[17952](#), [17960](#), [17963](#), [17965](#), [17967](#)
 - \l__box_left_dim [17586](#), [17612](#),
[17667](#), [17669](#), [17678](#), [17682](#), [17687](#),
[17693](#), [17698](#), [17702](#), [17732](#), [17825](#)
 - \l__box_left_new_dim [17590](#), [17627](#),
[17638](#), [17670](#), [17681](#), [17692](#), [17703](#)
 - __box_log:nNnn [16456](#)
 - __box_resize:N [17709](#), [17761](#), [17778](#), [17792](#), [17810](#)
 - __box_resize:NNN [17709](#)
 - __box_resize_common:N [17742](#), [17832](#), [17837](#)
 - __box_resize_set_corners:N [17709](#), [17754](#), [17771](#), [17788](#), [17802](#)
 - \l__box_right_dim [17586](#), [17611](#),
[17665](#), [17671](#), [17676](#), [17680](#), [17689](#),
[17691](#), [17700](#), [17704](#), [17716](#), [17731](#),
[17737](#), [17790](#), [17804](#), [17824](#), [17831](#)
 - \l__box_right_new_dim [17590](#),
[17638](#), [17672](#), [17683](#), [17694](#), [17705](#),
[17736](#), [17830](#), [17857](#), [17859](#), [17865](#)
 - __box_rotate:N [17595](#)
 - __box_rotate_quadrant_four: [17595](#), [17696](#)

- _box_rotate_quadrant_one: [17595](#), [17663](#)
 - _box_rotate_quadrant_three: [17595](#), [17685](#)
 - _box_rotate_quadrant_two: [17595](#), [17674](#)
 - _box_rotate_x:nnN [17595](#), [17641](#), [17669](#), [17671](#), [17680](#), [17682](#), [17691](#), [17693](#), [17702](#), [17704](#)
 - _box_rotate_y:nnN [17595](#), [17652](#), [17665](#), [17667](#), [17676](#), [17678](#), [17687](#), [17689](#), [17698](#), [17700](#)
 - \l_box_scale_x_fp . [17707](#), [17715](#), [17737](#), [17760](#), [17777](#), [17789](#), [17791](#), [17803](#), [17820](#), [17831](#), [17843](#), [17855](#)
 - \l_box_scale_y_fp [17707](#), [17717](#), [17739](#), [17741](#), [17755](#), [17760](#), [17772](#), [17777](#), [17791](#), [17805](#), [17821](#), [17827](#), [17829](#), [17844](#), [17846](#)
 - _box_show:NNnn . [16454](#), [16464](#), [16468](#)
 - \l_box_sin_fp [17584](#), [17601](#), [17613](#), [17648](#), [17658](#)
 - \l_box_top_dim [17586](#), [17609](#), [17665](#), [17669](#), [17678](#), [17680](#), [17689](#), [17693](#), [17698](#), [17704](#), [17720](#), [17729](#), [17741](#), [17758](#), [17775](#), [17808](#), [17822](#), [17827](#)
 - \l_box_top_new_dim [17590](#), [17635](#), [17666](#), [17677](#), [17688](#), [17699](#), [17740](#), [17826](#), [17848](#), [17852](#)
 - \boxdir [935](#)
 - \boxmaxdepth [307](#)
 - bp [188](#)
 - \brokenpenalty [308](#)
- C**
- \c [19395](#)
 - \catcode [4](#), [5](#), [6](#), [7](#), [10](#), [212](#), [213](#), [214](#), [215](#), [216](#), [217](#), [218](#), [219](#), [220](#), [225](#), [226](#), [227](#), [228](#), [229](#), [230](#), [231](#), [232](#), [233](#), [309](#)
 - catcode commands:
 - \c_catcode_active_tl [109](#), [425](#), [425](#), [6759](#), [6819](#)
 - \c_catcode_letter_token [109](#), [424](#), [6741](#), [6809](#)
 - \c_catcode_other_space_tl . . [141](#), [485](#), [8762](#), [8797](#), [8829](#), [8893](#), [8981](#), [9046](#)
 - \c_catcode_other_token [109](#), [425](#), [6741](#), [6814](#)
 - \catcodetable [864](#)
 - cc [188](#)
 - ceil [184](#)
 - \char [310](#), [6924](#)
 - char commands:
 - \l_char_active_seq [109](#), [136](#), [142](#), [6571](#), [8354](#)
 - \char_generate:nn [106](#), [106](#), [119](#), [6597](#), [8201](#), [8762](#), [18770](#), [19218](#), [19219](#), [19231](#), [19232](#), [19352](#), [19353](#)
 - \char_gset_active_eq:NN . . . [105](#), [6577](#)
 - \char_gset_active_eq:nN . . . [105](#), [6577](#)
 - \char_set_active_eq:NN [105](#), [105](#), [6577](#), [8357](#)
 - \char_set_active_eq:nN [105](#), [105](#), [6577](#)
 - \char_set_catcode:nn [107](#), [107](#), [242](#), [243](#), [244](#), [245](#), [246](#), [247](#), [248](#), [249](#), [250](#), [6462](#), [6472](#), [6474](#), [6476](#), [6478](#), [6480](#), [6482](#), [6484](#), [6486](#), [6488](#), [6490](#), [6492](#), [6494](#), [6496](#), [6498](#), [6500](#), [6502](#), [6504](#), [6506](#), [6508](#), [6510](#), [6512](#), [6514](#), [6516](#), [6518](#), [6520](#), [6522](#), [6524](#), [6526](#), [6528](#), [6530](#), [6532](#), [6534](#)
 - \char_set_catcode_active:N [106](#), [6471](#), [6578](#), [6646](#), [6760](#), [7606](#)
 - \char_set_catcode_active:n [107](#), [6503](#), [6702](#), [9536](#), [9537](#)
 - \char_set_catcode_alignment:N [106](#), [6471](#), [6748](#)
 - \char_set_catcode_alignment:n [107](#), [260](#), [6503](#), [6681](#)
 - \char_set_catcode_comment:N [106](#), [6471](#)
 - \char_set_catcode_comment:n [107](#), [6503](#)
 - \char_set_catcode_end_line:N [106](#), [6471](#)
 - \char_set_catcode_end_line:n [107](#), [6503](#)
 - \char_set_catcode_escape:N [106](#), [6471](#)
 - \char_set_catcode_escape:n [107](#), [6503](#)
 - \char_set_catcode_group_begin:N [106](#), [6471](#)
 - \char_set_catcode_group_begin:n [107](#), [6503](#), [6674](#)
 - \char_set_catcode_group_end:N [106](#), [6471](#)
 - \char_set_catcode_group_end:n [107](#), [6503](#), [6676](#)
 - \char_set_catcode_ignore:N [106](#), [6471](#)
 - \char_set_catcode_ignore:n [107](#), [257](#), [258](#), [6503](#)
 - \char_set_catcode_invalid:N [106](#), [6471](#)
 - \char_set_catcode_invalid:n [107](#), [6503](#)
 - \char_set_catcode_letter:N [106](#), [106](#), [6471](#), [11285](#), [11837](#), [11838](#), [12038](#), [12088](#), [12104](#), [12146](#), [12147](#), [12148](#), [12149](#), [12204](#), [12218](#), [12219](#), [12246](#), [12725](#), [12726](#)

- `\char_set_catcode_letter:n` [107](#), [107](#), [261](#), [263](#), [6503](#), [6698](#)
- `\char_set_catcode_math_subscript:N` [106](#), [6471](#), [6752](#)
- `\char_set_catcode_math_subscript:n` [107](#), [6503](#), [6693](#)
- `\char_set_catcode_math_superscript:N` [106](#), [6471](#)
- `\char_set_catcode_math_superscript:n` [107](#), [262](#), [6503](#), [6691](#)
- `\char_set_catcode_math_toggle:N` [106](#), [6471](#), [6746](#)
- `\char_set_catcode_math_toggle:n` [107](#), [6503](#), [6679](#)
- `\char_set_catcode_other:N` [106](#), [6471](#), [12145](#)
- `\char_set_catcode_other:n` [107](#), [259](#), [264](#), [6503](#), [6649](#), [6700](#)
- `\char_set_catcode_parameter:N` ... [106](#), [6471](#)
- `\char_set_catcode_parameter:n` ... [107](#), [6503](#), [6689](#)
- `\char_set_catcode_space:N` . [106](#), [6471](#)
- `\char_set_catcode_space:n` [107](#), [265](#), [6503](#), [6696](#)
- `\char_set_lccode:nn` [107](#), [107](#), [2740](#), [2757](#), [6535](#), [6584](#), [6706](#), [6707](#), [7603](#), [7604](#), [7605](#)
- `\char_set_mathcode:nn` [108](#), [108](#), [6535](#)
- `\char_set_sfcode:nn` .. [108](#), [108](#), [6535](#)
- `\char_set_uccode:nn` .. [108](#), [108](#), [6535](#)
- `\char_show_value_catcode:n` [107](#), [107](#), [6462](#)
- `\char_show_value_lccode:n` [108](#), [108](#), [6535](#)
- `\char_show_value_mathcode:n` [108](#), [108](#), [6535](#)
- `\char_show_value_sfcode:n` [109](#), [109](#), [6535](#)
- `\char_show_value_uccode:n` [108](#), [108](#), [6535](#)
- `\l_char_special_seq` [109](#), [6571](#)
- `\char_value_catcode:n` [107](#), [107](#), [242](#), [243](#), [244](#), [245](#), [246](#), [247](#), [248](#), [249](#), [250](#), [2752](#), [2782](#), [6462](#), [18772](#)
- `\char_value_lccode:n` . [108](#), [108](#), [6535](#)
- `\char_value_mathcode:n` [108](#), [108](#), [6535](#)
- `\char_value_sfcode:n` . [109](#), [109](#), [6535](#)
- `\char_value_uccode:n` . [108](#), [108](#), [6535](#)
- char internal commands:
 - `__char_generate:nn` [119](#), [119](#), [6597](#), [19180](#), [19182](#), [19224](#), [19226](#), [19237](#), [19239](#)
 - `__char_generate_aux:nn` [6597](#)
 - `__char_generate_aux:nnw` [6597](#)
 - `__char_generate_aux:w` ... [6599](#), [6610](#)
 - `__char_generate_invalid_catcode:` [6597](#)
 - `\c_char_max_int` [6597](#)
 - `__char_tmp:n` [6704](#), [6716](#), [6719](#), [6721](#), [6724](#)
 - `__char_tmp:nN` [6579](#), [6590](#), [6591](#)
 - `\l_char_tmp_tl` [6597](#)
- `\chardef` [222](#), [235](#), [311](#)
- chk internal commands:
 - `__chk_if_exist_cs:N` [22](#), [22](#), [1571](#), [1576](#), [1581](#), [1586](#), [1776](#), [2325](#)
 - `__chk_if_exist_var:N` [22](#), [22](#), [1764](#), [2638](#), [2660](#), [2661](#), [2666](#), [2667](#), [2674](#), [2675](#), [2676](#), [2681](#), [2682](#), [2683](#), [5475](#), [5649](#), [5654](#), [5659](#), [5664](#), [5669](#), [5674](#), [5679](#), [5684](#)
 - `__chk_if_free_cs:N` .. [22](#), [22](#), [422](#), [446](#), [1741](#), [1790](#), [1838](#), [2515](#), [2521](#), [2526](#), [4088](#), [4683](#), [4702](#), [6742](#), [6744](#), [6754](#), [7214](#), [9097](#), [9353](#), [9450](#), [16358](#)
 - `__chk_if_free_msg:nn` ... [7491](#), [7514](#)
 - `__chk_log:n` [22](#), [22](#), [22](#), [1696](#), [1758](#), [2472](#), [7508](#), [9856](#)
 - `__chk_resume_log:` [22](#), [22](#), [22](#), [272](#), [272](#), [1696](#), [16637](#)
 - `__chk_suspend_log:` [22](#), [22](#), [22](#), [272](#), [272](#), [1696](#), [16630](#)
- choice commands:
 - `.choice:` [161](#), [9989](#)
- choices commands:
 - `.choices:nn` [161](#), [9991](#)
- `\cite` [19566](#)
- `\cleaders` [312](#)
- `\clearmarks` [865](#)
- clist commands:
 - `\clist_clear:N` [96](#), [96](#), [5925](#), [5942](#), [6138](#), [10112](#), [10130](#)
 - `clist_clear:N` [96](#)
 - `\clist_clear_new:N` [96](#), [96](#), [5929](#)
 - `\clist_concat:NNN` [97](#), [97](#), [5969](#), [6022](#), [6035](#)
 - `\clist_const:Nn` [96](#), [96](#), [5922](#)
 - `\clist_count:N` [101](#), [101](#), [103](#), [6317](#), [6346](#), [6378](#), [17981](#)
 - `\clist_count:n` [101](#), [6317](#), [6409](#), [17972](#)
 - `\clist_gclear:N` [96](#), [5925](#), [5944](#)
 - `\clist_gclear_new:N` [96](#), [5929](#)
 - `\clist_gconcat:NNN` [97](#), [5969](#), [6024](#), [6037](#)
 - `\clist_get:NN` [102](#), [102](#), [6047](#)
 - `\clist_get:NNTF` [102](#), [102](#), [6084](#), [6093](#), [6094](#)
 - `\clist_gpop:NN` [102](#), [102](#), [6058](#)

- \clist_gpop:NNTF [103](#), [103](#), [6084](#), [6112](#), [6113](#)
- \clist_gpush:Nn [103](#), [6115](#)
- \clist_gput_left:Nn [97](#), [6021](#), [6123](#), [6124](#), [6125](#), [6126](#), [6127](#), [6128](#), [6129](#), [6130](#)
- \clist_gput_right:Nn [98](#), [6034](#)
- \clist_gremove_all:Nn [98](#), [6148](#)
- \clist_gremove_duplicates:N [98](#), [6132](#)
- \clist_greverse:N [98](#), [6179](#)
- .clist_gset:N [161](#), [10001](#)
- \clist_gset:Nn [97](#), [400](#), [6015](#)
- \clist_gset_eq:NN [97](#), [5933](#), [6135](#)
- \clist_gset_from_seq:NN [97](#), [5941](#)
- \clist_gsort:Nn [99](#), [6197](#), [16073](#)
- \clist_if_empty:NNTF [99](#), [99](#), [5978](#), [6165](#), [6197](#), [6242](#), [6272](#), [6291](#), [6439](#), [9877](#), [16081](#), [17980](#)
- \clist_if_empty:nTF [99](#), [99](#), [6201](#), [6445](#)
- \clist_if_empty_p:N [99](#), [99](#), [6197](#)
- \clist_if_empty_p:n [99](#), [99](#), [6201](#)
- \clist_if_exist:NNTF [97](#), [97](#), [5984](#), [6344](#), [6439](#), [8467](#), [8494](#)
- \clist_if_exist_p:N [97](#), [97](#), [5984](#)
- \clist_if_in:NnTF [99](#), [99](#), [6141](#), [6215](#), [6231](#), [6232](#), [6233](#), [6234](#)
- \clist_if_in:nnTF [99](#), [6215](#), [6237](#), [6238](#), [10770](#)
- \clist_item:Nn [103](#), [103](#), [414](#), [768](#), [6375](#), [17981](#)
- \clist_item:nn [103](#), [768](#), [6406](#), [17976](#)
- \clist_log:N [104](#), [104](#), [6450](#)
- \clist_log:n [104](#), [104](#), [6450](#)
- \clist_map_break: [100](#), [100](#), [6246](#), [6251](#), [6260](#), [6264](#), [6279](#), [6297](#), [6313](#), [10275](#)
- \clist_map_break:n [101](#), [101](#), [6313](#), [10218](#), [16084](#)
- \clist_map_function:NN [83](#), [96](#), [100](#), [100](#), [100](#), [4115](#), [4125](#), [6240](#), [6322](#), [6440](#)
- \clist_map_function:Nn [411](#)
- \clist_map_function:nN [100](#), [411](#), [4120](#), [4130](#), [6256](#), [6447](#), [10316](#), [20013](#), [20370](#)
- \clist_map_function:nn [20772](#)
- \clist_map_inline:Nn [100](#), [100](#), [100](#), [409](#), [714](#), [6139](#), [6270](#), [8496](#), [8511](#), [10213](#), [10266](#), [16084](#)
- \clist_map_inline:nn [100](#), [6270](#), [9841](#), [9908](#), [17447](#), [19703](#), [19712](#)
- \clist_map_variable:NNn [100](#), [100](#), [6289](#)
- \clist_map_variable:nNn [100](#), [6289](#)
- \clist_new:N [96](#), [96](#), [96](#), [400](#), [5920](#), [6131](#), [6455](#), [6456](#), [6457](#), [6458](#), [9664](#)
- \clist_pop:NN [102](#), [102](#), [6058](#)
- \clist_pop:NNTF [103](#), [103](#), [6084](#), [6109](#), [6110](#)
- \clist_push:Nn [103](#), [103](#), [6115](#)
- \clist_put_left:Nn [97](#), [97](#), [6021](#), [6115](#), [6116](#), [6117](#), [6118](#), [6119](#), [6120](#), [6121](#), [6122](#)
- \clist_put_right:Nn [98](#), [98](#), [6034](#), [6142](#), [10303](#)
- \clist_rand_item:N [211](#), [211](#), [17971](#)
- \clist_rand_item:n [211](#), [211](#), [17971](#)
- \clist_remove_all:Nn [98](#), [98](#), [6148](#)
- \clist_remove_duplicates:N [98](#), [98](#), [6132](#)
- \clist_reverse:N [98](#), [98](#), [6179](#)
- \clist_reverse:n [98](#), [98](#), [407](#), [407](#), [6180](#), [6182](#), [6185](#)
- .clist_set:N [161](#), [10001](#)
- \clist_set:Nn [97](#), [97](#), [400](#), [6015](#), [6022](#), [6024](#), [6035](#), [6037](#), [6221](#), [6285](#), [6302](#), [9876](#)
- \clist_set_eq:NN [97](#), [97](#), [5933](#), [6133](#), [9883](#), [10198](#)
- \clist_set_from_seq:NN [97](#), [97](#), [5941](#)
- \clist_show:N [103](#), [103](#), [104](#), [415](#), [6436](#), [6451](#)
- \clist_show:n [103](#), [103](#), [104](#), [415](#), [6436](#), [6453](#)
- \clist_sort:Nn [99](#), [99](#), [6197](#), [16073](#)
- \clist_use:Nn [102](#), [102](#), [6342](#)
- \clist_use:Nnnn [101](#), [101](#), [357](#), [6342](#)
- \clist_wrap_item:n [714](#), [714](#), [714](#)
- \c_empty_clist [104](#), [5917](#), [6049](#), [6064](#), [6086](#), [6102](#)
- \l_foo_clist [191](#)
- \g_tmpa_clist [104](#), [6455](#)
- \l_tmpa_clist [104](#), [6455](#)
- \g_tmpb_clist [104](#), [6455](#)
- \l_tmpb_clist [104](#), [6455](#)
- clist internal commands:
 - __clist_concat:NNNN [5969](#)
 - __clist_count:n [6317](#)
 - __clist_count:w [6317](#)
 - __clist_get:wN [6047](#), [6089](#)
 - __clist_if_empty_n:w [6201](#)
 - __clist_if_empty_n:wNw [6201](#)
 - __clist_if_in_return:nn [6215](#)
 - \l__clist_internal_clist [5918](#), [6027](#), [6028](#), [6040](#), [6041](#), [6221](#), [6222](#), [6285](#), [6286](#), [6302](#), [6303](#)
 - \l__clist_internal_remove_clist [6131](#), [6138](#), [6141](#), [6142](#), [6144](#)
 - __clist_item:nnnN [6375](#), [6408](#)
 - __clist_item_n:nw [6406](#)

- __clist_item_n_end:n [6406](#)
- __clist_item_N_loop:nw [6375](#)
- __clist_item_n_loop:nw [6406](#)
- __clist_item_n_strip:w [6406](#)
- __clist_map_function:Nw
..... [409](#), [6240](#), [6276](#)
- __clist_map_function_n:Nn [410](#), [6256](#)
- __clist_map_unbrace:Nw ... [410](#), [6256](#)
- __clist_map_variable:Nnw [6289](#)
- __clist_pop:NNN [6058](#)
- __clist_pop:wN [6058](#)
- __clist_pop:wwNNN ... [404](#), [6058](#), [6105](#)
- __clist_pop_TF:NNN [6084](#)
- __clist_put_left:NNNn [6021](#)
- __clist_put_right:NNNn [6034](#)
- __clist_rand_item:nn [17971](#)
- __clist_remove_all: [6148](#)
- __clist_remove_all:NNn [6148](#)
- __clist_remove_all:w [406](#), [406](#), [6148](#)
- __clist_remove_duplicates:NN . [6132](#)
- __clist_reverse:wwNww
..... [407](#), [407](#), [407](#), [407](#), [6185](#)
- __clist_reverse_end:ww ... [407](#), [6185](#)
- __clist_set_from_seq:NNNN ... [5941](#)
- __clist_set_from_seq:w [5941](#)
- __clist_tmp:w [406](#),
[406](#), [406](#), [5919](#), [6154](#), [6175](#), [6226](#), [6228](#)
- __clist_trim_spaces:n
..... [5923](#), [5994](#), [6016](#), [6018](#)
- __clist_trim_spaces:nn ... [402](#), [5994](#)
- __clist_trim_spaces_generic:nn .
..... [402](#), [5988](#)
- __clist_trim_spaces_generic:nw .
[410](#), [5988](#), [5996](#), [6006](#), [6011](#), [6258](#), [6266](#)
- __clist_use:nwn [6342](#)
- __clist_use:nwwwnwn [412](#), [6342](#)
- __clist_use:wn [6342](#)
- __clist_wrap_item:n ... [5941](#), [16087](#)
- \closein [313](#)
- \closeout [314](#)
- \clubpenalties [612](#)
- \clubpenalty [315](#)
- cm [188](#)
- code commands:
 .code:n [161](#), [9999](#)
- coffin commands:
 \coffin_attach:NnnNnnnn
 [201](#), [201](#), [751](#), [17010](#)
- \coffin_attach_mark:NnnNnnnn ...
 [17010](#), [17198](#), [17219](#), [17235](#)
- \coffin_clear:N [200](#), [200](#), [16618](#)
- \coffin_display_handles:Nn
 [202](#), [202](#), [17241](#)
- \coffin_dp:N
 . [202](#), [202](#), [16757](#), [17358](#), [18142](#), [18168](#)
- \coffin_ht:N
 . [202](#), [202](#), [16757](#), [17357](#), [18142](#), [18168](#)
- \coffin_if_exist:NTF
 . [200](#), [200](#), [16595](#), [16606](#), [16607](#), [16611](#)
- \coffin_if_exist_p:N [200](#), [200](#), [16595](#)
- \coffin_join:NnnNnnnn [202](#), [202](#), [16973](#)
- \coffin_log_structure:N
 [203](#), [203](#), [17369](#)
- \coffin_mark_handle:Nnnn
 [203](#), [203](#), [17186](#)
- \coffin_new:N [200](#), [200](#),
[736](#), [16627](#), [16751](#), [16753](#), [16754](#),
[16755](#), [16756](#), [17134](#), [17135](#), [17136](#)
- \coffin_resize:Nnn .. [211](#), [211](#), [18135](#)
- \coffin_rotate:Nn ... [211](#), [211](#), [17993](#)
- \coffin_scale:Nnn ... [211](#), [211](#), [18162](#)
- \coffin_set_eq:NN [200](#),
[200](#), [16742](#), [17007](#), [17026](#), [17055](#), [17262](#)
- \coffin_set_horizontal_pole:Nnn .
 [201](#), [201](#), [16794](#)
- \coffin_set_vertical_pole:Nnn ...
 [201](#), [201](#), [16794](#)
- \coffin_show_structure:N
 [203](#), [203](#), [203](#), [752](#), [17351](#), [17370](#)
- \coffin_typeset:Nnnnn [202](#), [202](#), [17126](#)
- \coffin_wd:N
 . [202](#), [202](#), [16757](#), [17359](#), [18138](#), [18172](#)
- \c_empty_coffin ... [203](#), [16751](#), [17129](#)
- \l_tmpa_coffin [203](#), [16755](#)
- \l_tmpb_coffin [203](#), [16755](#)
- coffin internal commands:
 __coffin_align:NnnNnnnnN
 .. [16975](#), [17012](#), [17030](#), [17038](#), [17129](#)
- \l__coffin_aligned_coffin
 [16751](#), [16976](#),
[16977](#), [16981](#), [16987](#), [16989](#), [16990](#),
[17006](#), [17007](#), [17013](#), [17014](#), [17015](#),
[17016](#), [17017](#), [17019](#), [17021](#), [17025](#),
[17026](#), [17031](#), [17032](#), [17033](#), [17034](#),
[17035](#), [17069](#), [17084](#), [17130](#), [17131](#),
[17336](#), [17343](#), [17345](#), [17347](#), [17349](#)
- \l__coffin_aligned_internal_-
 coffin [16751](#), [17048](#), [17055](#)
- \l__coffin_bottom_corner_dim ...
 [17989](#), [18013](#), [18017](#),
[18087](#), [18098](#), [18099](#), [18119](#), [18127](#)
- \l__coffin_bounding_prop
 [17987](#), [18002](#), [18030](#),
[18032](#), [18035](#), [18037](#), [18043](#), [18106](#)
- \l__coffin_bounding_shift_dim ...
 .. [17988](#), [18011](#), [18105](#), [18111](#), [18112](#)

__coffin_calculate_intersection:Nnn
 [16866](#), [17040](#), [17043](#), [17329](#)
 __coffin_calculate_intersection:nnnnnnnn
 [16866](#), [17275](#)
 __coffin_calculate_intersection_
 aux:nnnnN [16866](#)
 \c__coffin_corners_prop
 [16567](#), [16634](#), [16776](#)
 \l__coffin_cos_fp
 . [769](#), [771](#), [17985](#), [17996](#), [18070](#), [18079](#)
 __coffin_display_attach:Nnnnn [17241](#)
 \l__coffin_display_coffin
 [17134](#), [17262](#), [17268](#), [17338](#),
 [17339](#), [17344](#), [17346](#), [17348](#), [17349](#)
 \l__coffin_display_coord_coffin .
 [17134](#), [17200](#),
 [17220](#), [17236](#), [17283](#), [17303](#), [17322](#)
 \l__coffin_display_font_tl
 [17179](#), [17208](#), [17291](#)
 __coffin_display_handles_
 aux:nnnn [17241](#)
 __coffin_display_handles_
 aux:nnnnnn [17241](#)
 \l__coffin_display_handles_prop .
 .. [17137](#), [17211](#), [17215](#), [17294](#), [17298](#)
 \l__coffin_display_offset_dim ...
 .. [17174](#), [17237](#), [17238](#), [17323](#), [17324](#)
 \l__coffin_display_pole_coffin ..
 .. [17134](#), [17188](#), [17199](#), [17243](#), [17281](#)
 \l__coffin_display_poles_prop ...
 [17178](#), [17253](#),
 [17258](#), [17261](#), [17263](#), [17265](#), [17272](#)
 \l__coffin_display_x_dim
 [17176](#), [17278](#), [17333](#)
 \l__coffin_display_y_dim
 [17176](#), [17279](#), [17335](#)
 \l__coffin_error_bool
 [16586](#), [16870](#), [16874](#),
 [16888](#), [16903](#), [16934](#), [17274](#), [17276](#)
 __coffin_find_bounding_shift: ..
 [18005](#), [18103](#)
 __coffin_find_bounding_shift_
 aux:nn [18103](#)
 __coffin_find_corner_maxima:N ..
 [18004](#), [18083](#)
 __coffin_find_corner_maxima_
 aux:nn [18083](#)
 __coffin_get_pole:NnN
 [16763](#), [16868](#), [16869](#), [17093](#), [17094](#),
 [17097](#), [17098](#), [17255](#), [17256](#), [17259](#)
 __coffin_gset_eq_structure:NN [16780](#)
 __coffin_if_exist:NTF
 [16609](#), [16620](#), [16642](#), [16659](#), [16692](#),
 [16709](#), [16744](#), [16796](#), [16807](#), [17353](#)
 \l__coffin_internal_box
 [16564](#), [16675](#),
 [16681](#), [16686](#), [16725](#), [16731](#), [16736](#),
 [18007](#), [18016](#), [18018](#), [18019](#), [18021](#)
 \l__coffin_internal_dim
 [16564](#), [16982](#), [16984](#), [16985](#),
 [18034](#), [18036](#), [18038](#), [18167](#), [18170](#)
 \l__coffin_internal_tl
 [16564](#), [16573](#),
 [16574](#), [16575](#), [16576](#), [16577](#), [16578](#),
 [16579](#), [16580](#), [16581](#), [16582](#), [16583](#),
 [17067](#), [17068](#), [17070](#), [17212](#), [17213](#),
 [17216](#), [17217](#), [17225](#), [17230](#), [17295](#),
 [17296](#), [17299](#), [17300](#), [17309](#), [17314](#)
 \l__coffin_left_corner_dim
 [17989](#), [18011](#), [18020](#),
 [18088](#), [18094](#), [18095](#), [18118](#), [18126](#)
 __coffin_mark_handle_aux:nnnnNnn
 [17186](#)
 __coffin_offset_corner:Nnnnn . [17076](#)
 __coffin_offset_corners:Nnn ...
 .. [16995](#), [16996](#), [17002](#), [17003](#), [17076](#)
 __coffin_offset_pole:Nnnnnnn . [17057](#)
 __coffin_offset_poles:Nnn
 [16993](#), [16994](#),
 [16999](#), [17000](#), [17022](#), [17023](#), [17057](#)
 \l__coffin_offset_x_dim
 [16587](#), [16979](#), [16980](#), [16983](#),
 [16991](#), [16993](#), [16995](#), [17001](#), [17004](#),
 [17024](#), [17044](#), [17052](#), [17332](#), [17340](#)
 \l__coffin_offset_y_dim
 [16587](#), [16994](#), [16996](#), [17001](#), [17004](#),
 [17024](#), [17046](#), [17053](#), [17334](#), [17341](#)
 \l__coffin_pole_a_tl
 [16589](#), [16868](#), [16873](#), [17093](#), [17096](#),
 [17097](#), [17100](#), [17255](#), [17257](#), [17260](#)
 \l__coffin_pole_b_tl [16589](#),
 [16869](#), [16873](#), [17094](#), [17096](#), [17098](#),
 [17100](#), [17256](#), [17257](#), [17259](#), [17260](#)
 \c__coffin_poles_prop
 [16572](#), [16636](#), [16778](#)
 __coffin_reset_structure:N
 [16623](#), [16651](#), [16672](#),
 [16699](#), [16722](#), [16773](#), [16987](#), [17017](#)
 __coffin_resize_common:Nnn
 [18145](#), [18148](#), [18173](#)
 \l__coffin_right_corner_dim
 .. [17989](#), [18020](#), [18086](#), [18096](#), [18097](#)
 __coffin_rotate_bounding:nnn ...
 [18003](#), [18040](#)
 __coffin_rotate_corner:Nnnn ...
 [17998](#), [18040](#)
 __coffin_rotate_pole:Nnnnnn ...
 [18000](#), [18052](#)

- _coffin_rotate_vector:nnNN ...
... [18042](#), [18048](#), [18054](#), [18055](#), [18064](#)
- _coffin_scale_corner:Nnnn
..... [18151](#), [18184](#)
- _coffin_scale_pole:Nnnnnn
..... [18153](#), [18184](#)
- _coffin_scale_vector:nnNN
..... [18177](#), [18186](#), [18192](#)
- \l_coffin_scale_x_fp [18131](#), [18137](#),
[18154](#), [18164](#), [18166](#), [18172](#), [18180](#)
- \l_coffin_scale_y_fp ... [18131](#),
[18139](#), [18165](#), [18166](#), [18170](#), [18182](#)
- \l_coffin_scaled_total_height_-
dim [18133](#), [18169](#), [18174](#)
- \l_coffin_scaled_width_dim
..... [18133](#), [18171](#), [18174](#)
- _coffin_set_bounding:N [18001](#), [18028](#)
- _coffin_set_eq_structure:NN ...
..... [16747](#), [16780](#)
- _coffin_set_pole:Nnn
[16676](#), [16726](#), [16794](#), [17069](#), [17106](#),
[17110](#), [17118](#), [17122](#), [18057](#), [18193](#)
- _coffin_shift_corner:Nnnn
..... [18023](#), [18114](#)
- _coffin_shift_pole:Nnnnnn
..... [18025](#), [18114](#)
- \l_coffin_sin_fp
... [769](#), [771](#), [17985](#), [17995](#), [18071](#), [18078](#)
- \l_coffin_slope_x_fp
... [16584](#), [16928](#), [16933](#), [16941](#), [16947](#)
- \l_coffin_slope_y_fp
... [16584](#), [16930](#), [16933](#), [16942](#), [16947](#)
- \l_coffin_top_corner_dim
... [17989](#), [18017](#), [18085](#), [18100](#), [18101](#)
- _coffin_update_B:nnnnnnnnN . [17091](#)
- _coffin_update_corners:N
... [16653](#), [16674](#), [16701](#), [16724](#), [16821](#)
- _coffin_update_poles:N
..... [16652](#), [16673](#),
[16700](#), [16723](#), [16832](#), [16990](#), [17021](#)
- _coffin_update_T:nnnnnnnnN . [17091](#)
- _coffin_update_vertical_-
poles:NNN [17006](#), [17025](#), [17091](#)
- \l_coffin_x_dim
[16591](#), [16877](#), [16886](#), [16906](#), [16909](#),
[16916](#), [16925](#), [16936](#), [16951](#), [17041](#),
[17045](#), [17064](#), [17072](#), [17278](#), [17330](#),
[18042](#), [18044](#), [18048](#), [18050](#), [18054](#),
[18059](#), [18186](#), [18188](#), [18192](#), [18195](#)
- \l_coffin_x_prime_dim
..... [16591](#), [17041](#),
[17045](#), [17330](#), [17333](#), [18056](#), [18060](#)
- _coffin_x_shift_corner:Nnnn ...
..... [18157](#), [18199](#)
- _coffin_x_shift_pole:Nnnnnn ...
..... [18159](#), [18199](#)
- \l_coffin_y_dim
..... [16591](#), [16878](#), [16891](#), [16894](#),
[16901](#), [16918](#), [16923](#), [16952](#), [17042](#),
[17047](#), [17065](#), [17072](#), [17279](#), [17331](#),
[18042](#), [18044](#), [18048](#), [18050](#), [18054](#),
[18059](#), [18186](#), [18188](#), [18192](#), [18195](#)
- \l_coffin_y_prime_dim
..... [16591](#), [17042](#),
[17047](#), [17331](#), [17335](#), [18056](#), [18061](#)
- \color [17194](#), [17206](#), [17249](#), [17289](#)
- color commands:
 \color_ensure_current:
 ... [204](#), [204](#), [734](#), [16647](#), [16694](#), [17406](#)
 \color_group_begin: ... [204](#), [204](#),
 [204](#), [16646](#), [16668](#), [16694](#), [16717](#), [17400](#)
 \color_group_end: [204](#), [204](#),
 [204](#), [16649](#), [16670](#), [16697](#), [16720](#), [17400](#)
- \columnwidth [16666](#), [16715](#)
- \copy [316](#)
- \copyfont [948](#)
- cos [185](#)
- cosd [185](#)
- cot [185](#)
- cotd [185](#)
- \count [164](#), [166](#), [167](#), [168](#),
 [172](#), [173](#), [175](#), [176](#), [179](#), [181](#), [182](#),
 [183](#), [184](#), [188](#), [189](#), [191](#), [192](#), [317](#), [6932](#)
- \countdef [318](#)
- \cr [319](#)
- \crampeddisplaystyle [866](#)
- \crampedscriptscriptstyle [867](#)
- \crampedscriptstyle [868](#)
- \crampedtextstyle [869](#)
- \crrc [320](#)
- \cs [12620](#)
- cs commands:
 \cs:w [16](#),
 [16](#), [16](#), [17](#), [1308](#), [1328](#), [1330](#), [1378](#),
 [1640](#), [1668](#), [1916](#), [1976](#), [2068](#), [2107](#),
 [2121](#), [2123](#), [2127](#), [2128](#), [2129](#), [2164](#),
 [2170](#), [2190](#), [2192](#), [2197](#), [2204](#), [2205](#),
 [2268](#), [2272](#), [2302](#), [2507](#), [4684](#), [4773](#),
 [5419](#), [5468](#), [5861](#), [5863](#), [9098](#), [9308](#),
 [9354](#), [9424](#), [9451](#), [10253](#), [10272](#),
 [10282](#), [10296](#), [10581](#), [10606](#), [11266](#),
 [11382](#), [11567](#), [11599](#), [11922](#), [12029](#),
 [12060](#), [14066](#), [14335](#), [14842](#), [16359](#)
 \cs_end: [16](#), [16](#), [16](#),
 [298](#), [1308](#), [1328](#), [1330](#), [1334](#), [1378](#),
 [1634](#), [1640](#), [1662](#), [1668](#), [1848](#), [1916](#),
 [1976](#), [2068](#), [2107](#), [2121](#), [2123](#), [2127](#),
 [2128](#), [2129](#), [2164](#), [2170](#), [2190](#), [2192](#),

2197, 2204, 2205, 2268, 2272, 2302,
 2507, 4684, 4773, 5419, 5424, 5449,
 5458, 5468, 5494, 5858, 5864, 5866,
 5868, 5870, 5872, 5874, 5876, 5878,
 5880, 5882, 5884, 9098, 9308, 9354,
 9424, 9451, 9961, 10253, 10273,
 10283, 10296, 10581, 10614, 11266,
 11385, 11571, 11603, 11922, 12029,
 12063, 14066, 14335, 15001, 16359
 \cs_generate_from_arg_count:NNnn
 14, 14, 1897, 1934
 \cs_generate_variant:Nn 10,
 24, 24, 25, 25, 25, 26, 294, 294, 294,
 294, 2323, 2518, 2529, 2530, 2535,
 2536, 2541, 2542, 2555, 2556, 2573,
 2574, 2575, 2576, 2577, 2578, 2595,
 2596, 2597, 2598, 2599, 2600, 2601,
 2602, 2619, 2620, 2621, 2622, 2623,
 2624, 2625, 2626, 2729, 2730, 2731,
 2732, 2800, 2801, 2802, 2803, 2865,
 2866, 2871, 2872, 2875, 2876, 2877,
 2878, 2879, 2880, 2881, 2882, 2891,
 2892, 2893, 2894, 2904, 2905, 2906,
 2907, 2927, 2928, 2929, 2930, 2949,
 2950, 2951, 2960, 2961, 2962, 3005,
 3006, 3007, 3008, 3025, 3037, 3053,
 3059, 3068, 3080, 3081, 3104, 3105,
 3203, 3214, 3215, 3237, 3247, 3264,
 3265, 3266, 3267, 3384, 3390, 3395,
 3429, 3444, 3445, 3453, 3508, 3509,
 3510, 3511, 3512, 3513, 3514, 3515,
 3526, 3527, 3528, 3529, 3552, 3553,
 3554, 3555, 3637, 3695, 3772, 3791,
 3829, 3844, 3861, 3862, 3863, 3876,
 3940, 4091, 4094, 4097, 4100, 4103,
 4132, 4133, 4134, 4135, 4136, 4137,
 4173, 4174, 4179, 4180, 4202, 4203,
 4204, 4205, 4210, 4211, 4212, 4213,
 4230, 4231, 4256, 4257, 4274, 4275,
 4284, 4285, 4286, 4287, 4307, 4308,
 4309, 4310, 4311, 4312, 4341, 4354,
 4355, 4370, 4396, 4397, 4402, 4403,
 4404, 4405, 4406, 4407, 4416, 4417,
 4418, 4419, 4420, 4421, 4422, 4423,
 4424, 4425, 4426, 4427, 4451, 4471,
 4500, 4511, 4512, 4522, 4545, 4559,
 4598, 4601, 4687, 4708, 4724, 4725,
 4730, 4731, 4733, 4734, 4736, 4737,
 4750, 4751, 4752, 4753, 4762, 4763,
 4764, 4765, 4769, 4770, 4772, 5363,
 5367, 5542, 5543, 5573, 5574, 5575,
 5576, 5589, 5590, 5591, 5592, 5618,
 5627, 5628, 5629, 5630, 5643, 5644,
 5697, 5698, 5699, 5700, 5710, 5715,
 5818, 5819, 5824, 5825, 5924, 5965,
 5966, 5967, 5968, 5982, 5983, 6019,
 6020, 6030, 6031, 6032, 6033, 6043,
 6044, 6045, 6046, 6057, 6082, 6083,
 6093, 6094, 6095, 6109, 6110, 6111,
 6112, 6113, 6114, 6146, 6147, 6177,
 6178, 6183, 6184, 6231, 6232, 6233,
 6234, 6235, 6236, 6237, 6238, 6239,
 6255, 6288, 6312, 6325, 6365, 6374,
 6398, 6405, 6449, 6454, 6593, 6594,
 6595, 6596, 7217, 7220, 7223, 7226,
 7229, 7265, 7266, 7267, 7268, 7275,
 7276, 7295, 7296, 7297, 7298, 7311,
 7332, 7333, 7334, 7335, 7336, 7337,
 7351, 7353, 7355, 7357, 7374, 7375,
 7385, 7386, 7387, 7388, 7411, 7412,
 7413, 7414, 7415, 7416, 7417, 7418,
 7428, 7429, 7430, 7431, 7432, 7433,
 7448, 7449, 7464, 7475, 7478, 7922,
 8252, 8460, 8477, 8541, 8544, 8554,
 8555, 8556, 8587, 8605, 8686, 8693,
 8710, 8728, 8734, 8737, 8755, 9101,
 9107, 9110, 9111, 9116, 9117, 9125,
 9126, 9128, 9129, 9131, 9132, 9136,
 9137, 9141, 9142, 9307, 9337, 9357,
 9363, 9366, 9367, 9372, 9373, 9381,
 9382, 9384, 9385, 9387, 9388, 9392,
 9393, 9397, 9398, 9423, 9431, 9432,
 9434, 9454, 9460, 9464, 9465, 9470,
 9471, 9479, 9480, 9482, 9483, 9485,
 9486, 9490, 9491, 9495, 9496, 9500,
 9502, 9685, 9786, 9802, 9859, 9972,
 10105, 10106, 10109, 10117, 10124,
 10127, 10135, 10144, 10153, 10180,
 10319, 10887, 10890, 12418, 12616,
 12661, 15471, 15515, 15583, 15619,
 15623, 15670, 15868, 15875, 15876,
 15877, 15880, 15881, 15884, 15885,
 15890, 15891, 15898, 15899, 15900,
 15901, 15909, 15914, 16051, 16058,
 16065, 16072, 16077, 16078, 16362,
 16367, 16368, 16373, 16374, 16379,
 16380, 16385, 16386, 16394, 16395,
 16396, 16403, 16404, 16405, 16408,
 16409, 16425, 16426, 16427, 16428,
 16429, 16430, 16431, 16432, 16435,
 16436, 16437, 16438, 16443, 16444,
 16452, 16455, 16458, 16467, 16485,
 16490, 16491, 16496, 16497, 16502,
 16503, 16515, 16516, 16526, 16527,
 16532, 16533, 16541, 16542, 16547,
 16548, 16557, 16558, 16605, 16606,
 16607, 16608, 16626, 16639, 16656,
 16689, 16706, 16741, 16750, 16818,

- 16819, 16820, 17009, 17037, 17133,
17240, 17326, 17368, 17371, 17726,
17765, 17782, 17796, 17814, 17836,
17876, 17922, 17969, 17983, 18027,
18147, 18176, 18353, 18354, 18355,
18356, 18404, 18419, 18438, 18461,
18462, 18488, 18558, 18559, 18583,
18584, 18598, 18633, 19583, 19585,
19942, 20231, 20620, 20651, 20835
\cs_gset:Nn 14, 14, 1911, 1971
\cs_gset:Npn 10, 12, 12, 1363,
1796, 1810, 1812, 3029, 4475, 4985,
6275, 7455, 7530, 7532, 7570, 11288
\cs_gset:Npx
12, 1363, 1797, 1810, 1813, 4480, 4992
\cs_gset_eq:NN
. 15, 15, 15, 1828, 1845, 1853,
2516, 2547, 2548, 2549, 2550, 2668,
3408, 3417, 4089, 4485, 4490, 5624,
5626, 5635, 5636, 5637, 5638, 5660,
5665, 5675, 6591, 7215, 7452, 7460,
8602, 8725, 9085, 16340, 16349,
17456, 17457, 17458, 17459, 17464,
17465, 17466, 17467, 17478, 17479,
17480, 17481, 17485, 17486, 17487,
17488, 17494, 17495, 17496, 17497
\cs_gset_nopar:Nn . . . 14, 14, 1911, 1971
\cs_gset_nopar:Npn
. 12, 12, 1363, 1794, 1802, 1806
\cs_gset_nopar:Npx
. 12, 1363, 1795, 1802, 1807, 2522,
2527, 2568, 2570, 2572, 2588, 2590,
2592, 2594, 2612, 2614, 2616, 2618
\cs_gset_protected:Nn
. 14, 14, 1911, 1971
\cs_gset_protected:Npn
. 12, 12, 1363, 1800, 1822,
1824, 7501, 12665, 15980, 15988, 16001
\cs_gset_protected:Npx
. 12, 1363, 1801, 1822, 1825
\cs_gset_protected_nopar:Nn
. 14, 14, 1911, 1971
\cs_gset_protected_nopar:Npn
. 12, 12, 1363, 1798, 1816, 1818
\cs_gset_protected_nopar:Npx
. 12, 1363, 1799, 1816, 1819
\cs_if_eq:NNTF
. 20, 20, 2003, 2010, 2011, 2014,
2015, 2018, 2019, 7763, 9928, 11061,
11071, 11097, 11099, 11101, 11293
\cs_if_eq_p:NN 20, 20, 2003
\cs_if_exist:N
. 20, 2557, 2558, 4181, 4183,
4738, 4740, 5720, 5722, 5984, 5986,
7376, 7378, 9118, 9120, 9374, 9376,
9472, 9474, 12474, 12475, 16387, 16389
\cs_if_exist:NTF
. 20, 20, 135, 281, 427, 454,
1620, 1677, 1679, 1681, 1683, 1685,
1687, 1689, 1691, 1768, 1778, 2024,
3472, 3895, 3903, 3949, 3952, 3965,
4057, 4710, 4711, 4713, 4714, 5396,
5397, 5437, 5444, 6651, 6652, 6654,
6899, 6916, 7488, 8330, 8407, 8426,
8529, 8533, 8618, 8648, 8674, 8678,
9699, 9809, 9855, 10196, 10238,
10250, 10263, 10269, 10280, 10294,
10337, 10345, 11286, 11430, 12465,
15706, 15717, 15978, 15996, 15999,
16597, 16599, 17414, 17420, 17454,
17462, 17470, 17492, 18279, 18330,
18734, 18763, 18789, 18800, 18807,
18920, 19142, 19166, 19512, 19790,
19797, 19803, 19809, 19827, 19836
\cs_if_exist_p:N . . . 20, 20, 22, 1620, 17474
\cs_if_exist_use:N . . . 16, 16, 1676, 10252
cs_if_exist_use:N 271
\cs_if_exist_use:NTF
. 16, 16, 1676, 1678, 1680,
1686, 1688, 9894, 10768, 11392,
17501, 18726, 18759, 19478, 19480
\cs_if_free:NTF 20, 20, 88,
454, 1648, 1743, 1753, 2464, 2503, 7794
\cs_if_free_p:N
. 20, 20, 20, 22, 22, 88, 1648
\cs_log:N 16, 16, 134, 282, 282, 2043
\cs_meaning:N
. 15, 15, 259, 1317, 1331, 1339, 2039
\cs_new:Nn 12, 12, 89, 1911, 1971
\cs_new:Npn 10, 11, 11, 14,
88, 88, 89, 719, 1786, 1810, 1814,
1885, 1887, 1895, 1942, 2008, 2009,
2010, 2011, 2012, 2013, 2014, 2015,
2016, 2017, 2018, 2019, 2047, 2056,
2057, 2061, 2062, 2063, 2064, 2065,
2066, 2067, 2069, 2071, 2083, 2089,
2095, 2106, 2108, 2115, 2116, 2118,
2120, 2122, 2124, 2131, 2133, 2138,
2143, 2149, 2155, 2161, 2167, 2173,
2180, 2187, 2194, 2201, 2209, 2210,
2211, 2212, 2213, 2214, 2215, 2216,
2217, 2224, 2225, 2226, 2227, 2228,
2237, 2238, 2243, 2245, 2250, 2260,
2262, 2264, 2265, 2267, 2269, 2275,
2281, 2283, 2290, 2292, 2293, 2294,
2295, 2297, 2299, 2301, 2302, 2303,
2305, 2310, 2319, 2320, 2390, 2406,
2411, 2420, 2433, 2448, 2505, 2727,

2908, 2963, 2964, 2965, 2966, 2976,
2977, 2982, 2987, 2992, 2997, 2999,
3009, 3012, 3018, 3020, 3054, 3056,
3058, 3060, 3069, 3074, 3079, 3082,
3089, 3096, 3098, 3108, 3120, 3128,
3134, 3140, 3144, 3151, 3162, 3171,
3173, 3180, 3186, 3188, 3190, 3204,
3206, 3208, 3216, 3221, 3226, 3238,
3239, 3240, 3248, 3294, 3303, 3334,
3355, 3362, 3370, 3376, 3383, 3471,
3485, 3493, 3530, 3535, 3540, 3545,
3550, 3556, 3562, 3567, 3572, 3577,
3582, 3584, 3591, 3602, 3611, 3614,
3625, 3634, 3636, 3638, 3646, 3648,
3655, 3676, 3686, 3688, 3693, 3694,
3696, 3704, 3706, 3714, 3720, 3726,
3745, 3747, 3756, 3762, 3768, 3770,
3773, 3783, 3790, 3792, 3800, 3805,
3810, 3821, 3828, 3830, 3836, 3838,
3843, 3845, 3851, 3852, 3857, 3858,
3859, 3860, 3864, 3869, 3874, 3877,
3878, 3886, 3891, 3905, 3919, 4077,
4165, 4171, 4201, 4214, 4269, 4305,
4339, 4391, 4428, 4430, 4438, 4444,
4452, 4454, 4456, 4465, 4513, 4521,
4523, 4546, 4547, 4548, 4555, 4557,
4614, 4616, 4622, 4640, 4648, 4656,
4669, 4671, 4678, 4773, 4780, 4794,
4799, 4805, 4816, 4821, 4828, 4830,
4832, 4834, 4836, 4838, 4840, 4850,
4855, 4860, 4865, 4870, 4872, 4895,
4903, 4911, 4917, 4923, 4931, 4939,
4945, 4951, 4958, 4972, 5007, 5021,
5027, 5059, 5091, 5093, 5095, 5101,
5107, 5119, 5127, 5139, 5147, 5180,
5213, 5215, 5217, 5219, 5221, 5226,
5231, 5236, 5241, 5242, 5243, 5244,
5245, 5246, 5247, 5248, 5249, 5250,
5251, 5252, 5253, 5254, 5255, 5256,
5257, 5266, 5267, 5276, 5282, 5284,
5293, 5300, 5306, 5308, 5310, 5326,
5337, 5360, 5418, 5455, 5456, 5465,
5466, 5512, 5518, 5526, 5533, 5540,
5544, 5550, 5582, 5588, 5610, 5708,
5732, 5742, 5744, 5746, 5748, 5752,
5762, 5764, 5769, 5771, 5780, 5781,
5782, 5783, 5784, 5785, 5786, 5788,
5791, 5797, 5803, 5807, 5808, 5814,
5816, 5820, 5822, 5826, 5834, 5839,
5847, 5853, 5860, 5862, 5864, 5865,
5867, 5869, 5871, 5873, 5875, 5877,
5879, 5881, 5883, 5885, 5890, 5891,
5892, 5893, 5894, 5895, 5896, 5897,
5898, 5899, 5908, 5910, 5957, 5964,
5988, 5993, 5994, 6001, 6081, 6174,
6176, 6185, 6192, 6195, 6208, 6214,
6240, 6249, 6256, 6262, 6269, 6313,
6315, 6317, 6335, 6342, 6366, 6367,
6370, 6372, 6375, 6383, 6399, 6406,
6414, 6416, 6430, 6435, 6467, 6540,
6549, 6558, 6567, 6597, 6603, 6610,
6656, 6664, 6726, 6846, 6878, 6951,
6963, 6964, 6972, 6981, 6990, 7003,
7004, 7005, 7006, 7056, 7064, 7066,
7068, 7078, 7088, 7174, 7177, 7186,
7195, 7208, 7252, 7299, 7305, 7396,
7402, 7434, 7440, 7465, 7467, 7569,
7655, 7660, 7665, 7670, 7675, 7680,
7767, 7792, 7923, 8189, 8198, 8203,
8212, 8217, 8222, 8227, 8303, 8304,
8308, 8313, 8391, 8760, 8769, 8812,
8901, 8910, 8929, 8937, 8943, 8951,
8961, 8966, 8972, 8978, 9042, 9044,
9143, 9148, 9150, 9158, 9166, 9174,
9176, 9188, 9194, 9209, 9211, 9213,
9215, 9217, 9219, 9224, 9229, 9234,
9239, 9241, 9248, 9256, 9264, 9270,
9276, 9284, 9292, 9298, 9304, 9308,
9309, 9316, 9324, 9326, 9328, 9417,
9420, 9424, 9426, 9429, 9497, 9640,
9645, 9647, 9767, 10292, 10310,
10315, 10317, 10320, 10328, 10333,
10450, 10451, 10452, 10453, 10454,
10455, 10456, 10457, 10458, 10459,
10484, 10486, 10488, 10494, 10500,
10509, 10511, 10523, 10524, 10526,
10536, 10546, 10556, 10566, 10576,
10579, 10589, 10593, 10598, 10600,
10602, 10604, 10616, 10618, 10620,
10622, 10646, 10648, 10650, 10651,
10652, 10654, 10656, 10658, 10660,
10670, 10680, 10688, 10703, 10704,
10715, 10729, 10736, 10738, 10745,
10874, 10875, 10876, 10877, 10878,
10879, 10880, 10885, 10888, 10933,
10935, 10944, 10945, 10954, 10967,
10980, 10987, 11001, 11017, 11029,
11039, 11048, 11059, 11069, 11095,
11106, 11115, 11126, 11131, 11151,
11153, 11164, 11169, 11182, 11205,
11206, 11216, 11222, 11239, 11240,
11264, 11273, 11278, 11301, 11330,
11333, 11337, 11339, 11345, 11352,
11359, 11367, 11390, 11401, 11420,
11428, 11443, 11458, 11469, 11479,
11489, 11494, 11503, 11520, 11533,
11538, 11544, 11546, 11553, 11583,
11611, 11627, 11638, 11643, 11661,

11679, 11690, 11705, 11710, 11720,
11730, 11740, 11756, 11804, 11811,
11828, 11839, 11851, 11867, 11879,
11890, 11909, 11917, 11926, 11935,
11937, 11939, 11941, 11943, 11945,
11947, 11949, 11951, 11953, 11955,
11957, 11965, 11967, 11970, 11972,
11974, 11976, 11993, 11995, 12005,
12008, 12014, 12024, 12025, 12032,
12039, 12069, 12084, 12085, 12089,
12105, 12120, 12122, 12131, 12152,
12176, 12178, 12192, 12205, 12220,
12232, 12247, 12261, 12278, 12280,
12282, 12284, 12294, 12299, 12310,
12325, 12336, 12349, 12369, 12387,
12389, 12405, 12416, 12419, 12429,
12440, 12443, 12481, 12500, 12505,
12532, 12533, 12541, 12553, 12559,
12565, 12573, 12581, 12587, 12593,
12601, 12609, 12626, 12645, 12675,
12686, 12710, 12712, 12714, 12716,
12727, 12734, 12736, 12737, 12762,
12768, 12775, 12776, 12784, 12795,
12797, 12804, 12806, 12814, 12821,
12845, 12847, 12857, 12877, 12886,
12900, 12908, 12916, 12923, 12930,
12938, 12948, 12962, 12973, 12974,
12980, 12997, 13004, 13006, 13013,
13018, 13035, 13036, 13037, 13056,
13062, 13072, 13084, 13091, 13105,
13113, 13151, 13160, 13179, 13181,
13183, 13192, 13203, 13215, 13230,
13243, 13256, 13264, 13281, 13298,
13305, 13313, 13323, 13324, 13333,
13334, 13343, 13353, 13367, 13377,
13388, 13396, 13398, 13409, 13415,
13450, 13471, 13473, 13475, 13477,
13484, 13493, 13498, 13505, 13512,
13532, 13537, 13554, 13569, 13570,
13575, 13583, 13584, 13607, 13620,
13627, 13635, 13636, 13637, 13638,
13639, 13640, 13648, 13654, 13656,
13658, 13680, 13685, 13695, 13705,
13715, 13728, 13739, 13744, 13751,
13760, 13762, 13771, 13780, 13794,
13796, 13798, 13811, 13821, 13826,
13835, 13843, 13850, 13856, 13865,
13867, 13879, 13884, 13892, 13897,
13907, 13913, 13919, 13926, 13933,
13935, 13940, 13942, 13947, 13948,
13962, 13972, 13984, 13989, 13996,
14015, 14029, 14043, 14063, 14076,
14078, 14083, 14096, 14101, 14109,
14114, 14124, 14136, 14165, 14166,
14167, 14169, 14171, 14173, 14187,
14193, 14202, 14221, 14227, 14237,
14256, 14264, 14303, 14305, 14314,
14316, 14330, 14332, 14341, 14343,
14359, 14375, 14391, 14407, 14423,
14439, 14444, 14469, 14492, 14521,
14537, 14547, 14558, 14579, 14594,
14599, 14604, 14606, 14620, 14622,
14637, 14645, 14655, 14657, 14680,
14695, 14710, 14725, 14740, 14755,
14770, 14778, 14792, 14794, 14800,
14812, 14820, 14827, 15003, 15011,
15022, 15023, 15025, 15026, 15037,
15044, 15046, 15052, 15063, 15073,
15080, 15087, 15102, 15141, 15154,
15185, 15190, 15195, 15209, 15229,
15231, 15248, 15263, 15275, 15282,
15287, 15289, 15298, 15311, 15314,
15335, 15348, 15363, 15381, 15396,
15406, 15415, 15428, 15444, 15461,
15466, 15467, 15468, 15469, 15472,
15477, 15503, 15511, 15513, 15516,
15521, 15547, 15572, 15581, 15582,
15584, 15589, 15599, 15607, 15615,
15617, 15620, 15622, 15624, 15629,
15634, 15641, 15655, 15660, 15662,
15672, 15674, 15676, 15678, 15710,
15719, 15724, 15730, 15736, 15753,
15758, 15768, 15778, 15780, 15793,
15806, 15820, 15829, 15834, 15843,
15845, 15852, 16092, 16094, 16196,
16209, 16214, 16220, 16221, 16227,
16233, 16239, 16245, 16251, 16252,
16254, 16261, 16267, 17971, 17973,
17978, 18242, 18244, 18281, 18287,
18306, 18311, 18316, 18324, 18336,
18345, 18347, 18349, 18351, 18357,
18366, 18381, 18395, 18403, 18405,
18411, 18420, 18421, 18422, 18431,
18440, 18442, 18448, 18454, 18483,
18490, 18514, 18527, 18533, 18538,
18550, 18551, 18552, 18599, 18600,
18601, 18602, 18603, 18604, 18605,
18613, 18620, 18631, 18634, 18640,
18652, 18657, 18665, 18679, 18684,
18695, 18706, 18712, 18717, 18724,
18736, 18740, 18755, 18765, 18780,
18781, 18783, 18785, 18787, 18798,
18824, 18835, 18844, 18858, 18864,
18867, 18882, 18888, 18890, 18900,
18906, 18922, 18932, 18939, 18959,
18969, 18982, 18990, 18996, 19016,
19025, 19031, 19053, 19066, 19075,
19081, 19097, 19103, 19108, 19138,

- 19140, 19396, 19404, 19411, 19422,
19434, 19439, 19447, 19461, 19474,
19476, 19486, 19492, 19506, 19510,
19519, 19529, 19535, 19577, 19582,
19584, 19586, 19594, 19606, 19616,
19625, 19633, 19694, 19695, 19699,
19700, 20018, 20155, 20375, 20776
\cs_new:Npx 11, 292, 293, 1786, 1810,
1815, 2344, 2487, 6326, 6336, 8806,
11208, 11315, 12816, 14839, 15690
\cs_new_eq:NN
. 15, 15, 15, 273, 276, 422,
422, 1525, 1828, 2046, 2055, 2077,
2315, 2543, 2544, 2545, 2546, 2547,
2548, 2549, 2550, 2859, 2860, 3011,
3428, 3442, 3443, 3590, 3916, 3938,
3939, 4084, 4104, 4105, 4106, 4107,
4108, 4109, 4110, 4111, 4560, 4561,
4562, 4563, 4564, 4565, 4566, 4567,
4568, 4569, 4570, 4571, 4572, 4573,
4574, 4575, 4576, 4577, 4578, 4579,
4580, 4581, 4582, 4583, 4584, 4585,
4609, 4610, 4611, 4612, 4613, 4715,
4716, 4719, 4771, 4878, 5006, 5362,
5366, 5408, 5606, 5614, 5615, 5617,
5631, 5632, 5633, 5634, 5635, 5636,
5637, 5638, 5917, 5920, 5921, 5925,
5926, 5927, 5928, 5929, 5930, 5931,
5932, 5933, 5934, 5935, 5936, 5937,
5938, 5939, 5940, 6115, 6116, 6117,
6118, 6119, 6120, 6121, 6122, 6123,
6124, 6125, 6126, 6127, 6128, 6129,
6130, 6740, 6747, 6749, 6750, 6751,
6753, 6756, 6757, 6999, 7000, 7001,
7230, 7231, 7232, 7233, 7234, 7235,
7236, 7237, 8540, 8615, 8685, 8731,
8761, 8848, 9091, 9092, 9093, 9247,
9306, 9336, 9340, 9341, 9422, 9425,
9428, 9433, 9437, 9438, 9499, 9501,
9505, 9506, 10585, 11000, 11028,
11036, 11037, 11038, 11046, 11047,
11803, 15669, 15671, 15715, 15867,
15878, 15879, 16391, 16392, 16393,
16406, 16407, 16418, 16419, 16420,
16504, 16505, 16513, 16514, 16554,
16555, 16556, 16757, 16758, 16759,
16760, 16761, 16762, 17400, 17449,
17450, 17451, 17452, 17503, 17504,
17505, 17506, 17507, 17508, 17509,
17510, 17514, 17515, 17516, 17517,
17518, 17519, 17520, 17521, 18777,
18919, 18988, 18989, 19941, 20619
\cs_new_nopar:Nn . . . 13, 13, 1911, 1971
\cs_new_nopar:Npn 11,
11, 273, 275, 1786, 1802, 1808, 2045
\cs_new_nopar:Npx 11, 1786, 1802, 1809
\cs_new_protected:Nn 13, 13, 1911, 1971
\cs_new_protected:Npn
. 11, 11, 1786, 1822, 1826,
1828, 1829, 1830, 1831, 1832, 1833,
1834, 1835, 1836, 1841, 1842, 1843,
1844, 1846, 1897, 1907, 1909, 1919,
1924, 2020, 2022, 2027, 2029, 2031,
2033, 2041, 2043, 2044, 2078, 2208,
2218, 2219, 2220, 2221, 2222, 2223,
2229, 2230, 2231, 2232, 2233, 2234,
2235, 2236, 2255, 2296, 2318, 2323,
2350, 2356, 2361, 2370, 2460, 2497,
2513, 2519, 2524, 2531, 2533, 2537,
2539, 2551, 2553, 2561, 2563, 2565,
2567, 2569, 2571, 2579, 2581, 2583,
2585, 2587, 2589, 2591, 2593, 2603,
2605, 2607, 2609, 2611, 2613, 2615,
2617, 2689, 2691, 2693, 2695, 2717,
2735, 2747, 2749, 2763, 2792, 2794,
2796, 2798, 2804, 2826, 2832, 2861,
2863, 2867, 2869, 2946, 2947, 2948,
3026, 3035, 3038, 3044, 3046, 3100,
3102, 3210, 3212, 3385, 3391, 3393,
3396, 3402, 3411, 3914, 3915, 4086,
4092, 4095, 4098, 4101, 4112, 4117,
4122, 4127, 4138, 4140, 4142, 4175,
4177, 4185, 4193, 4206, 4208, 4216,
4218, 4220, 4232, 4234, 4236, 4258,
4260, 4262, 4313, 4321, 4331, 4342,
4344, 4346, 4348, 4356, 4365, 4371,
4373, 4375, 4472, 4477, 4482, 4488,
4494, 4501, 4592, 4599, 4681, 4688,
4722, 4723, 4726, 4728, 4732, 4735,
4742, 4744, 4746, 4748, 4754, 4756,
4758, 4760, 4766, 4768, 4774, 4981,
4988, 5000, 5364, 5368, 5416, 5421,
5422, 5433, 5435, 5440, 5505, 5597,
5617, 5619, 5621, 5623, 5625, 5639,
5641, 5701, 5706, 5711, 5713, 5919,
5922, 5941, 5943, 5945, 5969, 5971,
5973, 6015, 6017, 6021, 6023, 6025,
6034, 6036, 6038, 6047, 6055, 6058,
6060, 6062, 6070, 6100, 6132, 6134,
6136, 6148, 6150, 6152, 6179, 6181,
6224, 6270, 6283, 6289, 6300, 6305,
6436, 6442, 6450, 6452, 6462, 6469,
6471, 6473, 6475, 6477, 6479, 6481,
6483, 6485, 6487, 6489, 6491, 6493,
6495, 6497, 6499, 6501, 6503, 6505,
6507, 6509, 6511, 6513, 6515, 6517,
6519, 6521, 6523, 6525, 6527, 6529,
6531, 6533, 6535, 6542, 6544, 6551,

6553, 6560, 6562, 6569, 6581, 6740,
7007, 7009, 7011, 7017, 7034, 7036,
7038, 7052, 7054, 7097, 7212, 7218,
7221, 7224, 7227, 7242, 7244, 7253,
7259, 7269, 7277, 7286, 7338, 7339,
7340, 7359, 7361, 7363, 7450, 7469,
7476, 7491, 7512, 7517, 7519, 7526,
7528, 7535, 7576, 7588, 7593, 7610,
7640, 7646, 7690, 7692, 7761, 7802,
7822, 7823, 7836, 7841, 7867, 7876,
7878, 7880, 7897, 7924, 7926, 7928,
7930, 7937, 8233, 8235, 8247, 8253,
8255, 8272, 8280, 8282, 8351, 8393,
8395, 8403, 8440, 8445, 8454, 8461,
8478, 8480, 8485, 8490, 8540, 8542,
8545, 8557, 8568, 8571, 8588, 8594,
8606, 8608, 8632, 8634, 8685, 8688,
8691, 8694, 8711, 8717, 8729, 8732,
8735, 8738, 8744, 8750, 8757, 8759,
8770, 8800, 8818, 8850, 8859, 8871,
8890, 8894, 8982, 8998, 9006, 9015,
9022, 9028, 9079, 9095, 9102, 9108,
9109, 9112, 9114, 9122, 9124, 9127,
9130, 9133, 9135, 9138, 9140, 9338,
9342, 9351, 9358, 9364, 9365, 9368,
9370, 9378, 9380, 9383, 9386, 9389,
9391, 9394, 9396, 9435, 9439, 9448,
9455, 9461, 9463, 9466, 9468, 9476,
9478, 9481, 9484, 9487, 9489, 9492,
9494, 9503, 9507, 9521, 9538, 9544,
9549, 9562, 9568, 9573, 9587, 9590,
9600, 9610, 9632, 9641, 9643, 9677,
9679, 9686, 9691, 9696, 9709, 9714,
9738, 9750, 9771, 9787, 9803, 9805,
9807, 9823, 9833, 9835, 9837, 9853,
9860, 9874, 9887, 9892, 9896, 9904,
9906, 9916, 9943, 9952, 9961, 9962,
9973, 9975, 9977, 9979, 9981, 9983,
9985, 9987, 9989, 9991, 9993, 9995,
9997, 9999, 10001, 10003, 10005,
10007, 10009, 10011, 10013, 10015,
10017, 10019, 10021, 10023, 10025,
10027, 10029, 10031, 10033, 10035,
10037, 10039, 10041, 10043, 10045,
10047, 10049, 10051, 10053, 10055,
10057, 10059, 10061, 10063, 10065,
10067, 10069, 10071, 10073, 10075,
10077, 10079, 10081, 10083, 10085,
10087, 10089, 10091, 10093, 10095,
10097, 10099, 10107, 10110, 10118,
10125, 10128, 10136, 10145, 10154,
10159, 10164, 10181, 10194, 10208,
10234, 10248, 10258, 10301, 10350,
10365, 10376, 10461, 10766, 10783,
10785, 10787, 10789, 10817, 10819,
10821, 10823, 10843, 10845, 10847,
10849, 10851, 10853, 10855, 10857,
10859, 12396, 12403, 12662, 15241,
15866, 15869, 15871, 15873, 15882,
15883, 15886, 15888, 15892, 15893,
15894, 15895, 15896, 15902, 15907,
15910, 15912, 15937, 15956, 15964,
15976, 16013, 16020, 16045, 16052,
16059, 16066, 16073, 16075, 16079,
16102, 16111, 16131, 16141, 16151,
16153, 16155, 16156, 16163, 16166,
16176, 16186, 16277, 16284, 16286,
16301, 16334, 16343, 16356, 16363,
16365, 16369, 16371, 16375, 16377,
16381, 16383, 16397, 16399, 16401,
16410, 16412, 16414, 16416, 16439,
16441, 16450, 16453, 16456, 16459,
16461, 16468, 16486, 16487, 16489,
16492, 16494, 16498, 16500, 16506,
16508, 16509, 16511, 16517, 16518,
16519, 16521, 16523, 16525, 16528,
16530, 16534, 16539, 16543, 16545,
16549, 16559, 16609, 16618, 16627,
16640, 16657, 16690, 16705, 16707,
16740, 16742, 16763, 16773, 16780,
16787, 16794, 16805, 16816, 16821,
16832, 16866, 16881, 16959, 16973,
17010, 17028, 17038, 17057, 17062,
17076, 17081, 17091, 17102, 17114,
17126, 17186, 17233, 17241, 17270,
17319, 17327, 17351, 17369, 17401,
17407, 17411, 17527, 17570, 17595,
17607, 17641, 17652, 17663, 17674,
17685, 17696, 17709, 17727, 17734,
17744, 17749, 17766, 17783, 17797,
17815, 17837, 17874, 17877, 17923,
17993, 18028, 18040, 18046, 18052,
18064, 18083, 18092, 18103, 18109,
18114, 18122, 18135, 18148, 18162,
18177, 18184, 18190, 18199, 18206,
18215, 18220, 18228, 18233, 18246,
18248, 18250, 18256, 18263, 18273,
18276, 18463, 18465, 18467, 18473,
18475, 18477, 18554, 18556, 18560,
18576, 18579, 18581, 18585, 18775,
18776, 19656, 19673, 19678, 19685,
19687, 19689, 19696, 19697, 19843,
19845, 19847, 19849, 19861, 19866,
19888, 19903, 19929, 19943, 19945,
19947, 19949, 19951, 19956, 19961,
19971, 19980, 19982, 19985, 19987,
19989, 19991, 19996, 20001, 20006,
20008, 20020, 20025, 20027, 20029,

- 20031, 20033, 20035, 20037, 20039,
20050, 20055, 20064, 20073, 20078,
20082, 20084, 20086, 20096, 20101,
20106, 20111, 20121, 20140, 20151,
20153, 20163, 20181, 20200, 20222,
20227, 20229, 20232, 20239, 20245,
20247, 20249, 20254, 20259, 20268,
20278, 20280, 20283, 20285, 20301,
20306, 20326, 20349, 20352, 20365,
20377, 20382, 20384, 20386, 20388,
20390, 20392, 20394, 20396, 20401,
20411, 20424, 20437, 20442, 20444,
20446, 20455, 20467, 20479, 20491,
20510, 20512, 20514, 20516, 20518,
20570, 20583, 20612, 20617, 20621,
20626, 20628, 20636, 20646, 20654,
20659, 20664, 20675, 20685, 20695,
20697, 20699, 20701, 20732, 20734,
20739, 20741, 20743, 20746, 20767,
20778, 20791, 20793, 20795, 20797,
20799, 20801, 20803, 20805, 20807,
20818, 20820, 20822, 20824, 20833,
20836, 20838, 20840, 20842, 20853,
20884, 20886, 20888, 20890, 20905
- \cs_new_protected:Npx
..... 11, 292, 293, 297, 1786,
1822, 1827, 1913, 1973, 2333, 2337,
2342, 2479, 2483, 2484, 3451, 6587,
7116, 7701, 7703, 7705, 7707, 7709,
7718, 7720, 7722, 7946, 7948, 7950,
7952, 7954, 7963, 7965, 7967, 19788,
19795, 19801, 19807, 19825, 19834
- \cs_new_protected_nopar:Nn
..... 13, 13, 1911, 1971
- \cs_new_protected_nopar:Npn
..... 11, 11, 1786, 1803, 1816, 1820
- \cs_new_protected_nopar:Npx
..... 11, 1786, 1816, 1821
- \cs_set:Nn . 13, 13, 278, 278, 1911, 1971
- \cs_set:Npn 10,
11, 11, 88, 88, 89, 275, 278, 438,
1349, 1378, 1384, 1385, 1386, 1387,
1388, 1389, 1390, 1391, 1392, 1393,
1394, 1395, 1396, 1397, 1398, 1399,
1400, 1401, 1402, 1403, 1404, 1405,
1406, 1407, 1408, 1409, 1410, 1411,
1412, 1413, 1415, 1569, 1574, 1579,
1584, 1591, 1597, 1598, 1610, 1614,
1616, 1618, 1676, 1678, 1680, 1682,
1684, 1686, 1688, 1690, 1739, 1786,
1802, 1810, 1810, 1911, 1971, 2770,
2835, 2955, 3106, 3474, 4624, 4632,
5478, 5486, 6154, 6226, 6647, 7108,
7114, 7246, 7521, 7523, 8776, 9626,
10792, 10800, 10809, 10826, 10834,
10862, 12143, 16036, 18258, 19706
- \cs_set:Npx 11, 283,
514, 1349, 1600, 1810, 1811, 2837,
7021, 7026, 7043, 7044, 8822, 8823,
8824, 8825, 8826, 9613, 9619, 9869
- \cs_set_eq:NN 15, 15, 15,
276, 284, 1523, 1828, 2337, 2360,
2483, 2543, 2544, 2545, 2546, 2662,
4264, 4265, 4267, 4377, 4378, 4389,
5425, 5620, 5622, 5631, 5632, 5633,
5634, 5650, 5655, 5670, 6590, 6784,
7015, 7019, 7040, 7042, 7119, 8828,
8829, 8830, 8838, 9864, 9879, 9911,
9922, 9932, 16279, 16280, 16285, 17578
- \cs_set_nopar:Nn ... 13, 13, 1911, 1971
- \cs_set_nopar:Npn
..... 10, 11, 11, 110, 275, 275,
275, 1349, 1377, 1802, 1804, 9825, 9890
- \cs_set_nopar:Npx
. 11, 1349, 1381, 1802, 1805, 2080,
2257, 2562, 2564, 2566, 2580, 2582,
2584, 2586, 2604, 2606, 2608, 2610
- \cs_set_protected:Nn 13, 13, 1911, 1971
- \cs_set_protected:Npn
..... 10, 11, 11, 254,
275, 1349, 1365, 1367, 1369, 1371,
1373, 1375, 1379, 1417, 1419, 1421,
1423, 1425, 1430, 1432, 1434, 1436,
1438, 1443, 1455, 1470, 1487, 1504,
1510, 1516, 1522, 1524, 1526, 1538,
1552, 1692, 1694, 1697, 1698, 1699,
1703, 1704, 1708, 1710, 1713, 1715,
1717, 1718, 1719, 1722, 1735, 1737,
1741, 1751, 1762, 1766, 1776, 1784,
1788, 1822, 1822, 1855, 1876, 2629,
2636, 2658, 2664, 2672, 2679, 3424,
3447, 3959, 3970, 3986, 3993, 3997,
4007, 4010, 4024, 4039, 4042, 4051,
4059, 4293, 5473, 5647, 5652, 5657,
5662, 5667, 5672, 5677, 5682, 6579,
6704, 6874, 6892, 7624, 7687, 7933,
7935, 8187, 8756, 8758, 8869, 8949,
9040, 9409, 9857, 11220, 11809,
11877, 11888, 12150, 16281, 16695,
16718, 17416, 17422, 19168, 19172,
19175, 19202, 19213, 19344, 19347,
19369, 19654, 19715, 19875, 19880
- \cs_set_protected:Npx
11, 240, 1349, 1706, 1822, 1823, 7809
- \cs_set_protected_nopar:Nn
..... 14, 14, 1911, 1971
- \cs_set_protected_nopar:Npn
..... 12, 12, 275, 1349, 1816, 1816

- \cs_set_protected_nopar:Npx 12, 1349, 1816, 1817
- \cs_show:N 16, 16, 16, 20, 134, 281, 282, 282, 282, 2033, 2043, 2044
- \cs_to_str:N 4, 17, 17, 41, 47, 268, 269, 269, 339, 1591, 1604, 3922, 3923, 3924, 3925, 3926, 3927, 3928, 3929, 3930, 3931, 3932, 3933, 8761, 12399, 19573
- \cs_undefine:N 15, 15, 381, 516, 1844, 7971, 7972, 7973
- cs internal commands:
 - __cs_count_signature:N . 22, 22, 1885
 - __cs_count_signature:nnN 1885
 - __cs_generate_from_signature:n 1929, 1942
 - __cs_generate_from_signature:NNn 1915, 1919
 - __cs_generate_from_signature:nnNNn 1921, 1924
 - __cs_generate_internal_variant:n 2467, 2479
 - __cs_generate_internal_variant:wnnNwnn 2481, 2497
 - __cs_generate_internal_variant:wnnw 2479
 - __cs_generate_internal_variant_loop:n 2479
 - __cs_generate_variant:N . 2326, 2333
 - __cs_generate_variant:nnNN 2329, 2361
 - __cs_generate_variant:Nnnw 2368, 2370
 - __cs_generate_variant:ww 2333
 - __cs_generate_variant:wwNN 294, 295, 295, 295, 2377, 2460
 - __cs_generate_variant:wwNw 2333
 - __cs_generate_variant_loop:nNwN 294, 295, 2378, 2390
 - __cs_generate_variant_loop_end:nwwwNNnn 294, 295, 295, 2380, 2390
 - __cs_generate_variant_loop_invalid:NNwNNnn 295, 2390
 - __cs_generate_variant_loop_long:wNNnn 295, 2383, 2390
 - __cs_generate_variant_loop_same:w 295, 2390
 - __cs_generate_variant_same:N 295, 2409, 2448
 - __cs_get_function_name:N 22, 22, 1616
 - __cs_get_function_signature:N 22, 22, 1616
 - __cs_parm_from_arg_count:nnTF 1445, 1855, 1899
 - __cs_parm_from_arg_count_test:nnTF 1855
 - __cs_split_function:NN 22, 22, 269, 1427, 1440, 1531, 1532, 1600, 1617, 1619, 1886, 1921, 2327
 - __cs_split_function_auxi:w . . 1600
 - __cs_split_function_auxii:w . 1600
 - __cs_tmp:w . . . 23, 292, 297, 1786, 1802, 1804, 1805, 1806, 1807, 1808, 1809, 1810, 1811, 1812, 1813, 1814, 1815, 1816, 1817, 1818, 1819, 1820, 1821, 1822, 1823, 1824, 1825, 1826, 1827, 1911, 1947, 1948, 1949, 1950, 1951, 1952, 1953, 1954, 1955, 1956, 1957, 1958, 1959, 1960, 1961, 1962, 1963, 1964, 1965, 1966, 1967, 1968, 1969, 1970, 1971, 1979, 1980, 1981, 1982, 1983, 1984, 1985, 1986, 1987, 1988, 1989, 1990, 1991, 1992, 1993, 1994, 1995, 1996, 1997, 1998, 1999, 2000, 2001, 2002, 2337, 2360, 2468, 2483, 2629, 2642, 2644, 9409, 9419
 - __cs_to_str:N 268, 1591
 - __cs_to_str:w 268, 268, 1591
 - csc 185
 - cscd 185
 - \csname 14, 21, 39, 43, 49, 68, 90, 92, 98, 123, 146, 150, 222, 321
 - \currentgrouplevel 613
 - \currentgrouptype 614
 - \currentifbranch 615
 - \currentiflevel 616
 - \currentifttype 617
- D**
- \day 322
- dd 188
- \deadcycles 323
- \def 74, 75, 76, 105, 122, 124, 125, 143, 144, 147, 163, 178, 207, 211, 236, 275, 324
- default commands:
 - .default:n 162, 10009
 - \defaultthyphenchar 325
 - \defaultskewchar 326
 - deg 187
 - \delcode 327
 - \delimiter 328
 - \delimiterfactor 329
 - \delimitershortfall 330
- deprecation commands:
 - \deprecation_error: . . . 1, 757, 17570

```

\__deprecation_error:Nnn .....
..... 17527, 17572,
17573, 17574, 17575, 17576, 17577
\detokenize ..... 68, 222, 618
\DH ..... 19379
\dh ..... 19379
dim commands:
\dim_abs:n ..... 145, 145, 9143
\dim_add:Nn ..... 145, 145, 9133
\dim_case:nn ..... 148, 148, 9219
\dim_case:nnn ..... 17540
\dim_case:nnTF .....
... 148, 148, 9219, 9224, 9229, 17540
\dim_compare:nNnTF .....
..... 146, 146, 148, 148,
148, 149, 9178, 9243, 9278, 9286,
9295, 9301, 16884, 16887, 16890,
16899, 16902, 16905, 16914, 16921,
16979, 16984, 16991, 17104, 17116,
17885, 17902, 17931, 17945, 17955
\dim_compare:nTF .....
..... 80, 147, 147, 149, 149, 149,
149, 153, 9183, 9250, 9258, 9267, 9273
\dim_compare_p:n ..... 147, 147, 9183
\dim_compare_p:nNn ... 146, 146, 9178
\dim_const:Nn 144, 144, 9102, 9344, 9345
\dim_do_until:nn ..... 149, 149, 9248
\dim_do_until:nNnn ... 148, 148, 9276
\dim_do_while:nn ..... 149, 149, 9248
\dim_do_while:nNnn ... 148, 148, 9276
\dim_eval:n 146, 147, 149, 149, 149,
158, 9222, 9227, 9232, 9237, 9304,
9339, 16680, 16730, 16800, 16811,
16824, 16826, 16828, 16830, 16836,
16841, 16847, 16854, 16861, 17087,
17088, 17357, 17358, 17359, 17938,
17962, 18031, 18033, 18038, 18118,
18119, 18126, 18127, 18203, 18210
\dim_gadd:Nn ..... 145, 9133
.dim_gset:N ..... 162, 10017
\dim_gset:Nn ..... 145, 9105, 9122
\dim_gset_eq:NN ..... 145, 9127
\dim_gsub:Nn ..... 145, 9133
\dim_gzero:N ..... 144, 9108, 9115
\dim_gzero_new:N ..... 144, 9112
\dim_if_exist:NTF .....
..... 144, 144, 9113, 9115, 9118
\dim_if_exist_p:N .... 144, 144, 9118
\dim_log:N ..... 151, 151, 9340
\dim_log:n ..... 151, 151, 9340
\dim_max:nn 145, 145, 9143, 18097, 18101
\dim_min:nn .....
..... 145, 145, 9143, 18095, 18099, 18112

```

```

\dim_new:N 144, 144, 144, 9094, 9104,
1113, 9115, 9346, 9347, 9348, 9349,
16565, 16587, 16588, 16591, 16592,
16593, 16594, 17174, 17176, 17177,
17586, 17587, 17588, 17589, 17590,
17591, 17592, 17593, 17988, 17989,
17990, 17991, 17992, 18133, 18134
\dim_ratio:nn .....
..... 146, 146, 146, 497, 9174, 9333
\dim_set:N ..... 162, 10017
\dim_set:Nn .....
... 145, 145, 9122, 16663, 16712,
16886, 16891, 16901, 16906, 16916,
16923, 16936, 16962, 16982, 17041,
17042, 17044, 17046, 17064, 17065,
17175, 17278, 17279, 17330, 17331,
17332, 17334, 17609, 17610, 17611,
17643, 17654, 17729, 17730, 17731,
17746, 17822, 17823, 17824, 17826,
17828, 17830, 18034, 18066, 18074,
18085, 18086, 18087, 18088, 18094,
18096, 18098, 18100, 18105, 18111,
18167, 18169, 18171, 18179, 18181
\dim_set_eq:NN ..... 145,
145, 9127, 16665, 16666, 16714, 16715
\dim_show:N ..... 151, 151, 9336
\dim_show:n . 151, 151, 498, 9338, 9343
\dim_sub:Nn ..... 145, 145, 9133
\dim_to_decimal:n . 150, 150, 9309,
9325, 9330, 20529, 20530, 20531,
20532, 20533, 20535, 20657, 20662,
20668, 20669, 20670, 20671, 20680,
20681, 20682, 20773, 20792, 20900
\dim_to_decimal_in_bp:n .....
..... 150, 150, 150,
9324, 19894, 19895, 19896, 19954,
19959, 19965, 19966, 19967, 19975,
19976, 20015, 20019, 20023, 20117,
20171, 20172, 20173, 20252, 20257,
20263, 20264, 20272, 20273, 20274,
20372, 20376, 20380, 20486, 20777
\dim_to_decimal_in_sp:n .....
..... 150, 150, 150, 9326
\dim_to_decimal_in_unit:nn .....
..... 150, 150, 150, 9328
\dim_to_fp:n ..... 151, 151,
151, 567, 584, 701, 9336, 15634,
16929, 16931, 16941, 16942, 16943,
16944, 16966, 16967, 16968, 16969,
17647, 17648, 17658, 17659, 17716,
17719, 17720, 17747, 17757, 17758,
17774, 17775, 17790, 17804, 17807,
17808, 18070, 18071, 18078, 18079,
18138, 18141, 18142, 18180, 18182

```

- \dim_until_do:nn [149](#), [149](#), [9248](#)
- \dim_until_do:nNnn . . . [148](#), [148](#), [9276](#)
- \dim_use:N [149](#), [149](#), [149](#), [149](#),
[9146](#), [9152](#), [9153](#), [9154](#), [9160](#), [9161](#),
[9162](#), [9186](#), [9207](#), [9305](#), [9306](#), [9312](#),
[17072](#), [18036](#), [18038](#), [18044](#), [18050](#),
[18059](#), [18060](#), [18061](#), [18188](#), [18195](#)
- \dim_while_do:nn [149](#), [149](#), [9248](#)
- \dim_while_do:nNnn . . . [149](#), [149](#), [9276](#)
- \dim_zero:N . . . [144](#), [144](#), [9108](#), [9113](#),
[16877](#), [16878](#), [17612](#), [17732](#), [17825](#)
- dim_zero:N [144](#)
- \dim_zero_new:N [144](#), [144](#), [9112](#)
- \c_max_dim . . . [151](#), [154](#), [9344](#), [9442](#),
[18085](#), [18086](#), [18087](#), [18088](#), [18105](#)
- \g_tmpa_dim [151](#), [9346](#)
- \l_tmpa_dim [151](#), [9346](#)
- \g_tmpb_dim [151](#), [9346](#)
- \l_tmpb_dim [151](#), [9346](#)
- \c_zero_dim
. . . [151](#), [9108](#), [9344](#), [9441](#), [16508](#),
[16522](#), [16884](#), [16887](#), [16890](#), [16899](#),
[16902](#), [16905](#), [16914](#), [16921](#), [16979](#),
[16984](#), [16991](#), [17868](#), [17889](#), [17900](#),
[17906](#), [17918](#), [17931](#), [17935](#), [17943](#),
[17945](#), [17949](#), [17955](#), [17965](#), [19906](#)
- dim internal commands:
- __dim_abs:N [9143](#)
- __dim_case:nnTF [9219](#)
- __dim_case:nw [9219](#)
- __dim_case_end:nw [9219](#)
- __dim_compare:w [9183](#)
- __dim_compare:wNN [493](#), [9183](#)
- __dim_compare_!:w [9183](#)
- __dim_compare_<:w [9183](#)
- __dim_compare_=:w [9183](#)
- __dim_compare_>:w [9183](#)
- __dim_compare_end:w [9191](#), [9217](#)
- __dim_eval:w
. . . [158](#), [158](#), [497](#), [567](#), [9091](#), [9123](#),
[9134](#), [9139](#), [9146](#), [9152](#), [9153](#), [9154](#),
[9160](#), [9161](#), [9162](#), [9177](#), [9180](#), [9186](#),
[9207](#), [9212](#), [9305](#), [9312](#), [9327](#), [11343](#),
[11356](#), [11913](#), [16398](#), [16400](#), [16402](#),
[16411](#), [16413](#), [16415](#), [16417](#), [16493](#),
[16507](#), [16520](#), [16536](#), [16560](#), [17881](#),
[17883](#), [17927](#), [17929](#), [18010](#), [20125](#)
- __dim_eval_end: [158](#), [158](#),
[158](#), [158](#), [9091](#), [9123](#), [9134](#), [9139](#),
[9146](#), [9156](#), [9164](#), [9177](#), [9180](#), [9305](#),
[9312](#), [9327](#), [16398](#), [16400](#), [16402](#),
[16411](#), [16413](#), [16415](#), [16417](#), [16493](#),
[16507](#), [16520](#), [16536](#), [16560](#), [17881](#),
[17883](#), [17927](#), [17929](#), [18012](#), [20125](#)
- __dim_maxmin:wwN [9143](#)
- __dim_ratio:n [9174](#)
- __dim_to_decimal:w [9309](#)
- \dimen [331](#), [6931](#)
- \dimendef [332](#)
- \dimexpr [619](#)
- \directlua [16](#), [23](#), [53](#), [59](#), [61](#), [870](#)
- \disablecjktoken [1155](#)
- \discretionary [333](#)
- \displayindent [334](#)
- \displaylimits [335](#)
- \displaystyle [336](#)
- \displaywidowpenalties [620](#)
- \displaywidowpenalty [337](#)
- \displaywidth [338](#)
- \divide [339](#)
- \DJ [19380](#)
- \dj [19380](#)
- \doublehyphendemerits [340](#)
- \dp [341](#)
- \draftmode [949](#)
- driver internal commands:
- __driver_absolute_lengths:n . . .
. [20155](#), [20168](#)
- __driver_box_use_clip:N
. . . [224](#), [224](#), [17875](#), [19888](#), [20163](#), [20518](#)
- __driver_box_use_rotate:Nn
. . . [224](#), [224](#), [17630](#), [19903](#), [20181](#), [20570](#)
- __driver_box_use_scale:Nnn
. . . [225](#), [17841](#), [19929](#), [20196](#), [20200](#), [20583](#)
- \g__driver_clip_path_int
. [20518](#), [20705](#),
[20708](#), [20721](#), [20750](#), [20753](#), [20761](#)
- __driver_color_ensure_current: . .
. . . [225](#), [225](#), [17408](#), [17414](#), [17417](#),
[19825](#), [19861](#), [19870](#), [20222](#), [20612](#)
- __driver_color_reset:
. . . [19825](#), [19861](#), [19870](#), [20222](#), [20612](#)
- \l__driver_color_stack_int
. [19824](#), [19830](#), [19839](#)
- \l__driver_cos_fp [19903](#)
- \l__driver_current_color_tl
. [19814](#), [19831](#), [19851](#), [19863](#),
[19877](#), [20212](#), [20224](#), [20602](#), [20614](#)
- __driver_draw_add_to_path:n
. [20654](#), [20700](#)
- __driver_draw_begin:
. [225](#), [225](#), [19943](#), [20232](#), [20621](#)
- __driver_draw_cap_but:
. . . [228](#), [228](#), [228](#), [20008](#), [20365](#), [20767](#)
- __driver_draw_cap_rectangle:
. [228](#), [20008](#), [20365](#), [20767](#)
- __driver_draw_cap_round:
. [228](#), [20008](#), [20365](#), [20767](#)

_driver_draw_clip:
 227, 227, 19985, 20283, 20699
 \g_driver_draw_clip_bool
 20283, 20699
 _driver_draw_closepath:
 226, 226, 19985, 20283, 20699
 _driver_draw_closestroke:
 226, 226, 19985, 20283, 20699
 _driver_draw_color_cmyk:nnnn ..
 228, 228, 20039, 20396, 20807
 _driver_draw_color_cmyk_-
 aux:nnnn 20039
 _driver_draw_color_cmyk_-
 aux:NNnnnn
 20807, 20819, 20821, 20823
 _driver_draw_color_cmyk_-
 fill:nnnn 228, 20039, 20396, 20807
 _driver_draw_color_cmyk_-
 stroke:nnnn 228, 20039, 20396, 20807
 _driver_draw_color_gray:n
 .. 228, 228, 228, 20039, 20396, 20807
 _driver_draw_color_gray_aux:n .
 20039
 _driver_draw_color_gray_-
 aux:NNn . 20824, 20837, 20839, 20841
 _driver_draw_color_gray_-
 aux:nNN 20828, 20833, 20835
 _driver_draw_color_gray_fill:n
 228, 20039, 20396, 20807
 _driver_draw_color_gray_-
 stroke:n . 228, 20039, 20396, 20807
 _driver_draw_color_reset: .. 20396
 _driver_draw_color_rgb:nnn ...
 228, 20039, 20396, 20807
 _driver_draw_color_rgb_aux:nnn
 20039
 _driver_draw_color_rgb_-
 auxi:NNnnn
 20842, 20885, 20887, 20889
 _driver_draw_color_rgb_-
 auxii:nnn 20811
 _driver_draw_color_rgb_-
 auxii:nnnNN ... 20834, 20846, 20853
 _driver_draw_color_rgb_-
 fill:nnn . 228, 20039, 20396, 20807
 _driver_draw_color_rgb_-
 stroke:nnn 228, 20039, 20396, 20807
 _driver_draw_curveto:nnnnnn ...
 226, 226, 19951, 20249, 20654
 _driver_draw_dash:n
 20008, 20365, 20767
 _driver_draw_dash:nn
 227, 227, 20008, 20365, 20767
 _driver_draw_dash_aux:nn ... 20767
 _driver_draw_discardpath:
 227, 227, 19985, 20283, 20699
 _driver_draw_end:
 225, 225, 19943, 20232, 20621
 \g_driver_draw_eor_bool . 19980,
 19994, 19999, 20004, 20278, 20294,
 20311, 20319, 20331, 20342, 20358
 _driver_draw_evenodd_rule: ...
 227, 19980, 20278, 20695
 _driver_draw_fill:
 227, 227, 19985, 20283, 20699
 _driver_draw_fillstroke:
 227, 19985, 20283, 20699
 _driver_draw_hbox:Nnnnnnn
 229, 229, 20121, 20491, 20905
 _driver_draw_join_bevel:
 228, 20008, 20365, 20767
 _driver_draw_join_miter:
 228, 20008, 20365, 20767
 _driver_draw_join_round:
 228, 20008, 20365, 20767
 _driver_draw_lineto:nn
 226, 226, 19951, 20249, 20654
 _driver_draw_linewidth:n
 227, 227, 20008, 20365, 20767
 _driver_draw_literal:n
 19941, 19948, 19950,
 19953, 19958, 19963, 19973, 19986,
 19988, 19990, 19993, 19998, 20003,
 20007, 20010, 20022, 20026, 20028,
 20030, 20032, 20034, 20036, 20038,
 20052, 20057, 20066, 20080, 20083,
 20085, 20098, 20103, 20108, 20113,
 20229, 20246, 20248, 20251, 20256,
 20261, 20270, 20284, 20287, 20288,
 20289, 20292, 20298, 20308, 20309,
 20314, 20317, 20323, 20328, 20329,
 20334, 20335, 20336, 20337, 20340,
 20346, 20356, 20362, 20367, 20379,
 20383, 20385, 20387, 20389, 20391,
 20393, 20395, 20398, 20399, 20403,
 20413, 20426, 20439, 20443, 20445,
 20448, 20457, 20469, 20481, 20619,
 20640, 20648, 20706, 20725, 20751
 _driver_draw_miterlimit:n
 228, 228, 20008, 20365, 20767
 _driver_draw_move:nn 226
 _driver_draw_moveto:nn
 226, 19951, 20249, 20654
 _driver_draw_nonzero_rule: ...
 227, 227, 19980, 20278, 20695
 _driver_draw_path:n 20699
 \g_driver_draw_path_int 20699

- `\g_driver_draw_path_tl` . . . [20654](#),
[20710](#), [20726](#), [20728](#), [20755](#), [20764](#)
 - `__driver_draw_rectangle:nmm` . . .
. [226](#), [226](#), [19951](#), [20249](#), [20654](#)
 - `__driver_draw_scope:n`
. [20624](#), [20628](#),
[20696](#), [20698](#), [20718](#), [20758](#), [20780](#),
[20792](#), [20794](#), [20796](#), [20798](#), [20800](#),
[20802](#), [20804](#), [20806](#), [20855](#), [20892](#)
 - `__driver_draw_scope_begin:` [225](#),
[225](#), [19944](#), [19947](#), [20245](#), [20623](#), [20628](#)
 - `__driver_draw_scope_end:` . . [225](#),
[225](#), [19946](#), [19947](#), [20245](#), [20627](#), [20628](#)
 - `\g_driver_draw_scope_int` [20628](#)
 - `\l_driver_draw_scope_int` [20628](#)
 - `__driver_draw_stroke:`
. . . [226](#), [226](#), [227](#), [19985](#), [20283](#), [20699](#)
 - `__driver_draw_transformcm:nmmmm`
. [229](#), [229](#), [20111](#),
[20127](#), [20479](#), [20495](#), [20890](#), [20908](#)
 - `__driver_literal:n` [19788](#),
[19843](#), [19846](#), [19848](#), [19850](#), [19891](#),
[19941](#), [20140](#), [20166](#), [20184](#), [20203](#),
[20510](#), [20513](#), [20515](#), [20517](#), [20521](#),
[20523](#), [20540](#), [20619](#), [20909](#), [20922](#)
 - `__driver_matrix:n`
. [19807](#), [19849](#), [19911](#), [19932](#)
 - `\g_driver_path_int` . . . [20714](#), [20731](#)
 - `__driver_scope_begin:`
. [833](#), [19795](#), [19845](#), [19890](#),
[19905](#), [19931](#), [20126](#), [20151](#), [20165](#),
[20183](#), [20202](#), [20493](#), [20512](#), [20907](#)
 - `__driver_scope_begin:n` . . [20516](#),
[20542](#), [20550](#), [20554](#), [20572](#), [20585](#)
 - `__driver_scope_end:`
. [19795](#), [19845](#), [19900](#),
[19925](#), [19939](#), [20130](#), [20151](#), [20178](#),
[20192](#), [20210](#), [20506](#), [20512](#), [20564](#),
[20565](#), [20566](#), [20581](#), [20600](#), [20923](#)
 - `\l_driver_sin_fp` [19903](#)
 - `\l_driver_tmp_box` [20121](#)
 - `\dtou` [1122](#)
 - `\dump` [342](#)
 - `\dviextension` [871](#)
 - `\dvifedback` [872](#)
 - `\divvariable` [873](#)
- E**
- `\edef` [4](#), [106](#), [131](#), [209](#), [343](#)
 - `\efcode` [779](#)
 - `\else` [15](#), [22](#), [44](#), [46](#),
[91](#), [94](#), [95](#), [99](#), [100](#), [161](#), [165](#), [180](#), [344](#)
- else commands:
- `\else:` [21](#), [79](#), [79](#),
[79](#), [79](#), [79](#), [89](#), [94](#), [94](#), [142](#), [142](#), [157](#),
[198](#), [198](#), [199](#), [263](#), [270](#), [292](#), [310](#),
[310](#), [322](#), [322](#), [542](#), [605](#), [1294](#), [1336](#),
[1492](#), [1624](#), [1627](#), [1636](#), [1642](#), [1652](#),
[1655](#), [1664](#), [1670](#), [1716](#), [1850](#), [1871](#),
[1880](#), [1891](#), [1944](#), [1945](#), [2006](#), [2101](#),
[2338](#), [2394](#), [2395](#), [2396](#), [2452](#), [2455](#),
[2887](#), [2900](#), [2913](#), [2923](#), [2939](#), [2972](#),
[3231](#), [3260](#), [3283](#), [3299](#), [3307](#), [3317](#),
[3330](#), [3346](#), [3497](#), [3506](#), [3519](#), [3524](#),
[3680](#), [3733](#), [3736](#), [3739](#), [3751](#), [3765](#),
[3974](#), [3980](#), [3990](#), [4016](#), [4028](#), [4033](#),
[4047](#), [4280](#), [4317](#), [4326](#), [4623](#), [4644](#),
[4660](#), [4663](#), [4718](#), [4819](#), [4846](#), [4883](#),
[4891](#), [5177](#), [5210](#), [5261](#), [5399](#), [5428](#),
[5451](#), [5460](#), [5496](#), [5522](#), [5561](#), [5569](#),
[5693](#), [5728](#), [5757](#), [5776](#), [5901](#), [5903](#),
[5905](#), [5907](#), [6051](#), [6066](#), [6088](#), [6104](#),
[6614](#), [6618](#), [6621](#), [6629](#), [6635](#), [6671](#),
[6766](#), [6771](#), [6776](#), [6781](#), [6788](#), [6795](#),
[6800](#), [6805](#), [6810](#), [6815](#), [6820](#), [6825](#),
[6830](#), [6835](#), [6852](#), [6859](#), [6865](#), [6868](#),
[6903](#), [6906](#), [6968](#), [6977](#), [6985](#), [6994](#),
[7060](#), [7074](#), [7083](#), [7093](#), [7103](#), [7406](#),
[8624](#), [9149](#), [9170](#), [9181](#), [9191](#), [9218](#),
[9405](#), [9552](#), [9576](#), [9594](#), [9605](#), [9615](#),
[9625](#), [9636](#), [10504](#), [10514](#), [10515](#),
[10516](#), [10530](#), [10540](#), [10550](#), [10610](#),
[10667](#), [10676](#), [10684](#), [10699](#), [10710](#),
[10722](#), [10725](#), [10958](#), [10971](#), [10991](#),
[11019](#), [11020](#), [11041](#), [11055](#), [11078](#),
[11079](#), [11121](#), [11139](#), [11174](#), [11178](#),
[11226](#), [11243](#), [11249](#), [11253](#), [11257](#),
[11378](#), [11407](#), [11415](#), [11448](#), [11452](#),
[11464](#), [11474](#), [11484](#), [11515](#), [11528](#),
[11563](#), [11573](#), [11592](#), [11605](#), [11618](#),
[11622](#), [11633](#), [11656](#), [11673](#), [11685](#),
[11699](#), [11715](#), [11723](#), [11725](#), [11735](#),
[11746](#), [11762](#), [11778](#), [11784](#), [11789](#),
[11796](#), [11820](#), [11846](#), [11870](#), [11980](#),
[11983](#), [12047](#), [12051](#), [12058](#), [12077](#),
[12096](#), [12111](#), [12161](#), [12186](#), [12195](#),
[12210](#), [12226](#), [12238](#), [12255](#), [12271](#),
[12304](#), [12315](#), [12322](#), [12355](#), [12357](#),
[12363](#), [12378](#), [12485](#), [12496](#), [12517](#),
[12520](#), [12523](#), [12526](#), [12537](#), [12546](#),
[12549](#), [12679](#), [12692](#), [12695](#), [12702](#),
[12720](#), [12734](#), [12751](#), [12827](#), [12830](#),
[12839](#), [12851](#), [12862](#), [12868](#), [12881](#),
[12894](#), [12934](#), [12968](#), [12988](#), [13025](#),
[13043](#), [13046](#), [13052](#), [13066](#), [13101](#),
[13119](#), [13122](#), [13125](#), [13128](#), [13187](#),

- 13260, 13328, 13329, 13338, 13373,
 13456, 13460, 13464, 13526, 13775,
 13804, 13808, 13967, 13976, 14024,
 14035, 14051, 14059, 14118, 14197,
 14208, 14213, 14247, 14260, 14276,
 14280, 14283, 14454, 14461, 14483,
 14511, 14526, 14530, 14552, 14583,
 14586, 14611, 14614, 14651, 14661,
 14665, 14668, 14691, 14706, 14721,
 14736, 14751, 14766, 14787, 14832,
 15058, 15096, 15097, 15106, 15150,
 15202, 15216, 15217, 15218, 15321,
 15343, 15358, 15376, 15424, 15440,
 15596, 15645, 15650, 15743, 15764,
 15786, 15969, 15970, 16422, 16424,
 16434, 19115, 19122, 19134, 19608,
 19621, 19640, 19643, 19646, 19669
 em 188
 \emergencystretch 345
 \enablecjktoken 1156
 \end 118, 257, 346, 12617, 20194
 \endcsname 14, 21, 39, 43, 49,
 68, 90, 92, 98, 123, 146, 150, 222, 347
 \endgroup 13, 36,
 38, 42, 48, 74, 117, 135, 154, 203, 348
 \endinput 136, 349
 \endL 621
 \endlinechar 221, 234, 350
 \endR 622
 \enquote 12618
 \ensuremath 19566
 \eqno 351
 \errhelp 108, 127, 352
 \errmessage 116, 128, 353
 \ERROR 6718
 \errorcontextlines 354
 \errorstopmode 355
 \escapechar 356
 etex commands:
 \etex_beginL:D 609
 \etex_beginR:D 610
 \etex_botmarks:D 611
 \etex_clubpenalties:D 612
 \etex_currentgrouplevel:D 613
 \etex_currentgrouptype:D 614
 \etex_currentifbranch:D 615
 \etex_currentiflevel:D 616
 \etex_currentiftype:D 617
 \etex_detokenize:D 311,
 618, 1319, 2911, 3058, 3489, 9616, 9634
 \etex_dimexpr:D 619, 9092
 \etex_displaywidowpenalties:D .. 620
 \etex_endL:D 621
 \etex_endR:D 622
 \etex_eTeXrevision:D 623
 \etex_eTeXversion:D 624
 \etex_everyeof:D
 625, 2706, 18565, 18590
 \etex_firstmarks:D 626
 \etex_fontcharp:D 627
 \etex_fontcharht:D 628
 \etex_fontcharic:D 629
 \etex_fontcharwd:D 630
 \etex_glueexpr:D . 631, 9379, 9390,
 9395, 9414, 9421, 9427, 9430, 15639
 \etex_glueshrink:D 632, 18495
 \etex_glueshrinkorder:D 633
 \etex_gluestretch:D 634, 18494
 \etex_gluestretchorder:D 635
 \etex_gluetomu:D 636
 \etex_ifcsname:D 637, 1309
 \etex_ifdefined:D . 638, 795, 1166,
 1175, 1178, 1184, 1238, 1239, 1246,
 1258, 1265, 1278, 1286, 1308, 1344
 \etex_iffontchar:D 639
 \etex_interactionmode:D
 640, 16460, 16463, 16465
 \etex_interlinepenalties:D 641
 \etex_lastlinefit:D 642
 \etex_lastnodetype:D 643
 \etex_marks:D 644
 \etex_middle:D 645
 \etex_muexpr:D
 646, 9477, 9488, 9493, 9498
 \etex_mutoglu:D 647
 \etex_numexpr:D 648, 3948, 4610
 \etex_pagediscards:D 649
 \etex_parshapedimen:D 650
 \etex_parshapeindent:D 651
 \etex_parshapelength:D 652
 \etex_predisplaydirection:D ... 653
 \etex_protected:D
 654, 1351, 1353, 1355,
 1356, 1357, 1358, 1359, 1360, 1361,
 1362, 1370, 1372, 1374, 1376, 17529
 \etex_readline:D 655, 8639
 \etex_savinghyphcodes:D 656
 \etex_savingvdiscards:D 657
 \etex_scantokens:D
 658, 2723, 2773, 2788
 \etex_showgroups:D 659
 \etex_showifs:D 660
 \etex_showtokens:D
 325, 466, 661, 1282, 8297
 \etex_splitbotmarks:D 662
 \etex_splitdiscards:D 663
 \etex_splitfirstmarks:D 664
 \etex_TeXTeXstate:D 665

- `\etex_topmarks:D` 666
- `\etex_tracingassigns:D` 667
- `\etex_tracinggroups:D` 668
- `\etex_tracingifs:D` 669
- `\etex_tracingnesting:D` 670
- `\etex_tracingscantokens:D` 671
- `\etex_unexpanded:D` 672, 1275, 1314,
2301, 2304, 2307, 2312, 3192, 3218,
3242, 4807, 6685, 18516, 18607, 19398
- `\etex_unless:D` 673, 1299
- `\etex_widowpenalties:D` 674
- `\eTeXrevision` 623
- `\eTeXversion` 624
- `\etoksapp` 874
- `\etokspre` 875
- `\euc` 1123
- `\everycr` 357
- `\everydisplay` 358
- `\everyeof` 625
- `\everyhbox` 359
- `\everyjob` 66, 67, 360
- `\everymath` 361
- `\everypar` 362
- `\everyvbox` 363
- `ex` 188
- `\exhyphenpenalty` 364
- `exp` 183
- exp commands:
 - `\exp:w` 31, 31, 31, 32, 32, 32,
32, 32, 32, 263, 268, 284, 284, 285,
285, 292, 318, 318, 324, 333, 397,
397, 463, 558, 558, 558, 558, 560,
561, 561, 564, 582, 587, 587, 787,
1315, 1414, 1416, 2074, 2086, 2092,
2132, 2136, 2141, 2147, 2153, 2159,
2171, 2176, 2178, 2185, 2241, 2248,
2253, 2261, 2263, 2266, 2273, 2279,
2288, 2304, 2308, 2313, 2315, 2979,
2984, 2989, 2994, 3194, 3352, 3532,
3537, 3542, 3547, 3564, 3569, 3574,
3579, 3663, 3672, 3724, 4852, 4857,
4862, 4867, 5855, 6599, 6605, 7102,
8191, 8915, 9190, 9221, 9226, 9231,
9236, 10553, 10747, 10934, 11052,
11053, 11054, 11055, 11166, 11184,
11225, 11269, 11276, 11281, 11290,
11305, 11313, 11363, 11376, 11377,
11386, 11396, 11413, 11414, 11434,
11447, 11451, 11473, 11501, 11514,
11527, 11551, 11562, 11572, 11591,
11604, 11617, 11620, 11632, 11655,
11684, 11698, 11714, 11734, 11745,
11751, 11761, 11807, 11817, 11832,
11843, 11858, 11873, 11880, 11914,
11923, 11932, 11997, 11999, 12019,
12022, 12029, 12030, 12080, 12095,
12116, 12122, 12129, 12158, 12183,
12225, 12237, 12252, 12268, 12334,
12346, 12375, 12377, 12381, 12383,
12393, 12413, 12479, 12493, 12503,
12612, 12613, 12614, 12745, 12748,
12756, 12780, 12788, 13748, 14275,
14279, 14298, 14456, 14629, 14808,
15200, 15201, 15205, 15475, 15479,
15519, 15523, 15568, 15587, 15591,
15627, 15631, 15697, 15789, 15817,
15824, 15844, 15860, 18511, 18518,
18609, 18646, 19400, 19428, 19614
- `\exp_after:wN` 30, 30, 31, 32, 32, 263,
283, 285, 323, 374, 444, 466, 535,
537, 537, 537, 557, 557, 558, 558,
558, 558, 558, 558, 558, 560, 560,
561, 561, 619, 619, 676, 676, 676,
1312, 1328, 1330, 1335, 1337, 1414,
1416, 1460, 1473, 1491, 1493, 1543,
1548, 1555, 1595, 1599, 1602, 1603,
1635, 1637, 1640, 1663, 1665, 1668,
1849, 1851, 1859, 1879, 1881, 1916,
1976, 2051, 2061, 2068, 2070, 2073,
2074, 2081, 2085, 2086, 2091, 2092,
2097, 2102, 2104, 2107, 2115, 2117,
2119, 2121, 2123, 2126, 2127, 2128,
2132, 2135, 2140, 2145, 2146, 2147,
2151, 2152, 2153, 2157, 2158, 2159,
2163, 2164, 2165, 2169, 2170, 2171,
2175, 2176, 2177, 2178, 2182, 2183,
2184, 2185, 2189, 2190, 2191, 2196,
2197, 2198, 2199, 2203, 2204, 2205,
2206, 2240, 2241, 2244, 2247, 2248,
2252, 2253, 2261, 2263, 2264, 2266,
2268, 2271, 2272, 2277, 2278, 2282,
2285, 2286, 2287, 2291, 2298, 2300,
2301, 2302, 2304, 2307, 2312, 2327,
2328, 2329, 2330, 2335, 2339, 2366,
2373, 2393, 2507, 2632, 2721, 2722,
2771, 2772, 2786, 2787, 2846, 2847,
2848, 2853, 2897, 2910, 2911, 2969,
2970, 3058, 3165, 3192, 3223, 3228,
3229, 3230, 3232, 3245, 3255, 3274,
3296, 3306, 3309, 3326, 3327, 3337,
3342, 3343, 3358, 3359, 3360, 3489,
3593, 3616, 3650, 3651, 3662, 3663,
3671, 3679, 3681, 3687, 3690, 3708,
3709, 3710, 3722, 3723, 3750, 3752,
3758, 3764, 3777, 3797, 3808, 3824,
3832, 3840, 3847, 3854, 3866, 3973,
3975, 3981, 4062, 4176, 4178, 4190,
4198, 4297, 4335, 4347, 4358, 4359,

4360, 4381, 4382, 4429, 4458, 4459,
4460, 4530, 4531, 4534, 4618, 4623,
4626, 4627, 4634, 4635, 4651, 4652,
4673, 4674, 4791, 4796, 4801, 4824,
4826, 4953, 4954, 4955, 5149, 5177,
5182, 5210, 5223, 5233, 5260, 5262,
5263, 5271, 5288, 5332, 5419, 5426,
5459, 5461, 5468, 5515, 5521, 5523,
5547, 5763, 5766, 5770, 5856, 6052,
6067, 6089, 6105, 6162, 6170, 6175,
6349, 6350, 6353, 6354, 6599, 6600,
6605, 6606, 6607, 6659, 6667, 6685,
6686, 6729, 6730, 6731, 6842, 6863,
6910, 6946, 6975, 6976, 6978, 6984,
6987, 7059, 7061, 7071, 7072, 7073,
7075, 7081, 7082, 7084, 7091, 7092,
7094, 7100, 7101, 7104, 7181, 7190,
7199, 7249, 7443, 7633, 8192, 8193,
8194, 8195, 8207, 8297, 8298, 8323,
8336, 8569, 8689, 8857, 8898, 8907,
8910, 8913, 8914, 8916, 8955, 9012,
9043, 9145, 9149, 9152, 9153, 9160,
9161, 9185, 9190, 9203, 9206, 9311,
9413, 9530, 9531, 9540, 9542, 9559,
9564, 9566, 9583, 9592, 9596, 9597,
9604, 9606, 9607, 9616, 9634, 9637,
9646, 9712, 9754, 9900, 9901, 10173,
10253, 10254, 10273, 10283, 10296,
10297, 10330, 10503, 10505, 10506,
10517, 10518, 10519, 10529, 10531,
10539, 10541, 10549, 10551, 10558,
10559, 10560, 10561, 10562, 10563,
10568, 10569, 10570, 10571, 10572,
10573, 10574, 10624, 10626, 10653,
10657, 10692, 10696, 10711, 10718,
10747, 10806, 10814, 10831, 10840,
10886, 10934, 11003, 11004, 11005,
11067, 11086, 11092, 11118, 11119,
11122, 11133, 11137, 11144, 11145,
11156, 11157, 11166, 11173, 11175,
11176, 11184, 11210, 11225, 11243,
11244, 11247, 11248, 11250, 11251,
11255, 11256, 11258, 11259, 11268,
11269, 11276, 11281, 11290, 11303,
11304, 11309, 11310, 11312, 11319,
11320, 11322, 11341, 11342, 11346,
11349, 11354, 11355, 11357, 11361,
11362, 11364, 11373, 11374, 11375,
11376, 11379, 11380, 11381, 11384,
11396, 11412, 11413, 11423, 11424,
11434, 11446, 11450, 11463, 11465,
11473, 11483, 11485, 11491, 11496,
11498, 11500, 11506, 11507, 11511,
11513, 11525, 11526, 11548, 11550,
11556, 11559, 11561, 11565, 11570,
11575, 11576, 11586, 11587, 11589,
11590, 11593, 11597, 11602, 11616,
11619, 11631, 11640, 11647, 11648,
11649, 11650, 11652, 11654, 11665,
11666, 11667, 11668, 11670, 11672,
11674, 11675, 11676, 11682, 11683,
11693, 11697, 11698, 11700, 11701,
11702, 11707, 11713, 11724, 11726,
11733, 11734, 11736, 11737, 11744,
11750, 11760, 11813, 11814, 11815,
11816, 11830, 11831, 11833, 11841,
11842, 11856, 11857, 11873, 11880,
11911, 11912, 11913, 11919, 11920,
11921, 11922, 11928, 11929, 11930,
11931, 11998, 12010, 12011, 12017,
12018, 12020, 12021, 12027, 12028,
12045, 12046, 12048, 12049, 12056,
12057, 12059, 12062, 12074, 12075,
12076, 12078, 12079, 12080, 12093,
12094, 12095, 12097, 12098, 12099,
12108, 12109, 12110, 12115, 12117,
12126, 12127, 12128, 12134, 12135,
12137, 12155, 12156, 12157, 12160,
12162, 12163, 12164, 12181, 12182,
12185, 12187, 12188, 12189, 12208,
12209, 12211, 12212, 12213, 12223,
12224, 12225, 12227, 12228, 12229,
12235, 12236, 12237, 12239, 12240,
12241, 12250, 12251, 12254, 12256,
12257, 12258, 12266, 12267, 12270,
12272, 12273, 12274, 12286, 12287,
12288, 12289, 12290, 12291, 12292,
12302, 12303, 12305, 12306, 12307,
12327, 12328, 12329, 12330, 12331,
12332, 12333, 12334, 12339, 12340,
12341, 12342, 12343, 12344, 12345,
12361, 12362, 12364, 12365, 12372,
12373, 12374, 12379, 12380, 12382,
12391, 12392, 12407, 12409, 12410,
12411, 12478, 12492, 12502, 12510,
12511, 12611, 12678, 12680, 12719,
12721, 12743, 12744, 12747, 12754,
12755, 12758, 12759, 12766, 12771,
12778, 12779, 12786, 12787, 12835,
12836, 12837, 12839, 12850, 12866,
12867, 12869, 12870, 12880, 12882,
12888, 12889, 12893, 12896, 12918,
12920, 12933, 12935, 12941, 12943,
12946, 12952, 12954, 12956, 12957,
12958, 12960, 12965, 12967, 12969,
12973, 12976, 12982, 12983, 12987,
12989, 12990, 12991, 12999, 13001,
13002, 13009, 13015, 13022, 13023,

13028, 13029, 13030, 13031, 13050,
 13051, 13052, 13058, 13059, 13060,
 13065, 13067, 13075, 13077, 13079,
 13080, 13082, 13093, 13095, 13097,
 13098, 13103, 13154, 13155, 13162,
 13163, 13165, 13167, 13169, 13171,
 13173, 13175, 13177, 13186, 13188,
 13194, 13196, 13198, 13199, 13200,
 13206, 13208, 13210, 13211, 13212,
 13233, 13234, 13237, 13245, 13247,
 13251, 13252, 13253, 13254, 13259,
 13261, 13267, 13270, 13273, 13276,
 13284, 13287, 13290, 13293, 13300,
 13302, 13308, 13316, 13318, 13320,
 13337, 13339, 13346, 13348, 13351,
 13357, 13359, 13361, 13362, 13363,
 13365, 13379, 13380, 13383, 13401,
 13403, 13405, 13417, 13420, 13423,
 13426, 13429, 13432, 13435, 13438,
 13442, 13454, 13458, 13462, 13465,
 13480, 13486, 13488, 13490, 13500,
 13524, 13527, 13539, 13541, 13545,
 13546, 13547, 13549, 13550, 13552,
 13556, 13557, 13558, 13559, 13572,
 13577, 13579, 13586, 13589, 13592,
 13595, 13598, 13601, 13609, 13610,
 13622, 13630, 13632, 13642, 13644,
 13651, 13660, 13662, 13665, 13668,
 13671, 13674, 13687, 13689, 13697,
 13699, 13707, 13709, 13718, 13721,
 13724, 13731, 13746, 13747, 13764,
 13766, 13767, 13824, 13837, 13839,
 13845, 13858, 13860, 13862, 13886,
 13900, 13902, 13909, 13911, 13951,
 13952, 13953, 13955, 13956, 13957,
 13959, 13960, 13966, 13968, 13969,
 13975, 13977, 13978, 13979, 13980,
 13992, 13998, 14000, 14031, 14038,
 14045, 14065, 14066, 14068, 14070,
 14072, 14085, 14090, 14091, 14092,
 14093, 14094, 14098, 14103, 14105,
 14111, 14117, 14119, 14120, 14126,
 14127, 14128, 14129, 14130, 14131,
 14132, 14133, 14138, 14140, 14142,
 14144, 14146, 14150, 14152, 14154,
 14156, 14158, 14160, 14178, 14182,
 14190, 14191, 14196, 14198, 14207,
 14210, 14211, 14212, 14214, 14215,
 14216, 14224, 14230, 14242, 14245,
 14246, 14248, 14249, 14267, 14268,
 14272, 14278, 14282, 14284, 14301,
 14319, 14325, 14334, 14335, 14336,
 14337, 14345, 14361, 14377, 14393,
 14409, 14425, 14451, 14455, 14456,
 14460, 14462, 14498, 14504, 14505,
 14507, 14509, 14510, 14512, 14513,
 14523, 14524, 14527, 14528, 14529,
 14531, 14532, 14533, 14550, 14551,
 14553, 14554, 14560, 14562, 14565,
 14568, 14571, 14574, 14582, 14585,
 14587, 14590, 14597, 14601, 14609,
 14610, 14613, 14615, 14617, 14621,
 14625, 14630, 14631, 14639, 14640,
 14641, 14642, 14669, 14670, 14671,
 14780, 14781, 14782, 14784, 14802,
 14803, 14804, 14805, 14806, 14807,
 14814, 14823, 14830, 14831, 14841,
 15005, 15006, 15007, 15028, 15029,
 15039, 15048, 15056, 15057, 15059,
 15060, 15065, 15066, 15075, 15082,
 15091, 15092, 15105, 15107, 15135,
 15136, 15145, 15148, 15173, 15179,
 15180, 15199, 15205, 15207, 15233,
 15234, 15236, 15250, 15251, 15259,
 15269, 15303, 15306, 15316, 15317,
 15320, 15322, 15328, 15342, 15344,
 15385, 15388, 15408, 15470, 15474,
 15479, 15482, 15506, 15507, 15514,
 15518, 15523, 15526, 15532, 15558,
 15559, 15565, 15566, 15567, 15574,
 15582, 15586, 15591, 15594, 15610,
 15611, 15622, 15626, 15631, 15636,
 15637, 15638, 15644, 15646, 15649,
 15651, 15693, 15695, 15696, 15713,
 15733, 15739, 15742, 15745, 15748,
 15755, 15761, 15765, 15775, 15784,
 15789, 15791, 15812, 15822, 15823,
 15831, 15838, 15847, 15848, 15856,
 15960, 16098, 16099, 16108, 16127,
 16128, 16143, 16144, 16145, 17431,
 18283, 18284, 18359, 18360, 18414,
 18426, 18435, 18441, 18444, 18516,
 18536, 18568, 18569, 18607, 18644,
 18661, 18662, 18818, 18819, 18840,
 18841, 18889, 18910, 18943, 19035,
 19085, 19179, 19181, 19187, 19210,
 19223, 19225, 19236, 19238, 19360,
 19398, 19426, 19443, 19444, 19488,
 19489, 19539, 19609, 19611, 19612,
 19613, 19619, 19620, 19622, 19628,
 19629, 19663, 19668, 19670, 19676
 \exp_arg:N 30
 \exp_args:cc
 27, 1327, 1496, 1507, 1513, 1519, 2120
 \exp_args:Nc 27,
 27, 280, 1327, 1331, 1339, 1763,
 1785, 1803, 1829, 1834, 1841, 1896,
 1908, 1975, 2008, 2009, 2010, 2011,

- 2028, 2032, 2120, 2815, 3030, 3429,
3453, 5437, 5475, 10356, 11075, 18253
- \exp_args:Ncc 28, 1831, 1835,
1843, 2016, 2017, 2018, 2019, 2120
- \exp_args:Nccc 28, 2120
- \exp_args:Ncco 28, 2180
- \exp_args:Nccx 29, 2224
- \exp_args:Ncf 28, 2143
- \exp_args:NcNc 28, 2180
- \exp_args:NcNo 28, 2180
- \exp_args:Ncnx 29, 2224
- \exp_args:Nco 28, 287, 2143
- \exp_args:Ncx 28, 2209, 8200
- \exp_args:Nf 27,
27, 2131, 3364, 3365, 3381, 3640,
3642, 3698, 3700, 3716, 4432, 4433,
4449, 4853, 4858, 4863, 4868, 5023,
5092, 5094, 5112, 5121, 5132, 5141,
5279, 5296, 6338, 6389, 6403, 6424,
8205, 8947, 9222, 9227, 9232, 9237,
12655, 15486, 17972, 18300, 18313,
18338, 18340, 18535, 18992, 19000,
19055, 19105, 19590, 19598, 19602
- \exp_args:Nff 28, 2209, 19596
- \exp_args:Nfo 28, 2209
- \exp_args:NNc
. . . 28, 28, 259, 1830, 1833, 1842,
1910, 2012, 2013, 2014, 2015, 2042,
2120, 4984, 4991, 8207, 8569, 8689
- \exp_args:Nnc 28, 2209
- \exp_args:NNf 28, 2143,
4977, 8568, 8688, 8844, 14774, 14775
- \exp_args:Nnf 28, 2209
- \exp_args:Nnnc 28, 2224
- \exp_args:NNNo
. . . . 28, 28, 2115, 2712, 18571, 18594
- \exp_args:NNno 28, 2224
- \exp_args:NNno 28, 2224
- \exp_args:NNNV 28, 2180
- \exp_args:NNNx 29, 2224
- \exp_args:NNnx 29, 29, 2224
- \exp_args:NNnx 29, 2224
- \exp_args:NNNo
. . . . 24, 24, 24, 28, 2115, 5011, 7243
- \exp_args:Nno 28, 2209, 2726,
6293, 7173, 9193, 10791, 10799,
10808, 10825, 10833, 10861, 18575
- \exp_args:NNoo 28, 28, 2224
- \exp_args:NNox 29, 2224
- \exp_args:Nnox 29, 2224
- \exp_args:NNV 28, 2143
- \exp_args:NNv 28, 2143
- \exp_args:NnV 28, 2209
- \exp_args:NNx 28, 28, 2037, 2209
- \exp_args:Nnx 28, 2209
- \exp_args:No 27,
27, 714, 2021, 2115, 2706, 2711,
2946, 2947, 2948, 2963, 2964, 2965,
2966, 3019, 3036, 3045, 3101, 3103,
3211, 3213, 3239, 3248, 3383, 3636,
3647, 3694, 3705, 3771, 3790, 3828,
3843, 4168, 5011, 5098, 5104, 5991,
6169, 6180, 6182, 6217, 6222, 6418,
6422, 8742, 8773, 8854, 9419, 9996,
10014, 10042, 10064, 16087, 16460,
18268, 18308, 18565, 19582, 19584
- \exp_args:Noc 28, 2209
- \exp_args:Nof 28, 2209
- \exp_args:Noo 28, 28, 2209
- \exp_args:Nooo 28, 2224
- \exp_args:Noox 29, 2224
- \exp_args:Nox 28, 2209
- \exp_args:NV 27, 27, 2131,
8981, 9046, 9994, 10012, 10040, 10062
- \exp_args:Nv 27, 27, 2131
- \exp_args:NVV 28, 2143, 8893
- \exp_args:Nx 27,
27, 1857, 2208, 6708, 7595, 8237,
8274, 8778, 9998, 10016, 10044, 10066
- \exp_args:Nxo 28, 2209
- \exp_args:Nxx 28, 2209
- \exp_end:
. . . 31, 31, 31, 31, 31, 31, 32, 263,
265, 268, 285, 285, 318, 318, 324,
333, 333, 398, 463, 558, 558, 558,
587, 784, 1316, 1497, 1508, 1514,
1520, 2104, 2113, 2315, 3010, 3172,
3358, 3359, 3693, 5887, 5890, 5891,
5892, 5893, 5894, 5895, 5896, 5897,
5898, 5899, 6608, 6641, 6656, 6659,
6664, 6667, 6726, 6730, 8195, 12007,
14301, 15207, 15791, 18637, 19622
- \exp_end_continue_f:nw . . 32, 32, 2315
- \exp_end_continue_f:w
. . 32, 32, 32, 32, 32, 32, 284, 284,
560, 561, 561, 2074, 2132, 2147,
2171, 2241, 2266, 2304, 2315, 7102,
8915, 9190, 10553, 10747, 11057,
11166, 11184, 11205, 11276, 11281,
11290, 11305, 11363, 11396, 11403,
11434, 11807, 11832, 11873, 11880,
11914, 12016, 12019, 12029, 12030,
12375, 12377, 12381, 12383, 12479,
12493, 12503, 12612, 12613, 12614,
12745, 12756, 12780, 12788, 13748,
14456, 14629, 14808, 15475, 15479,
15519, 15523, 15568, 15587, 15591,
15627, 15631, 15698, 15824, 18511

- `\exp_last_two_unbraced:Nnn`
 - . . . 29, 29, 2297, 16871, 17095, 17099
- `\exp_last_unbraced:Nn`
 - 29, 29, 29, 29, 2260,
 - 2783, 5110, 5130, 5952, 6433, 6733,
 - 16086, 17224, 17229, 17307, 17313
- `\exp_last_unbraced:NNn`
 - 29, 2260, 3179, 6244, 6276,
 - 7436, 8775, 17069, 18652, 18711, 19434
- `\exp_last_unbraced:Nnn`
 - 29, 29, 2260, 7301, 7391, 18407
- `\exp_last_unbraced:NNNn` 29, 2260
- `\exp_last_unbraced:NnNn` 29, 2260
- `\exp_not:N` 30, 30,
 - 30, 30, 141, 188, 285, 285, 303, 305,
 - 305, 321, 322, 426, 433, 565, 714,
 - 785, 1312, 1464, 1530, 1533, 1602,
 - 1603, 1604, 1605, 1606, 1610, 1611,
 - 1915, 1916, 1975, 1976, 2061, 2097,
 - 2301, 2302, 2335, 2336, 2337, 2338,
 - 2339, 2340, 2341, 2342, 2344, 2345,
 - 2346, 2350, 2351, 2356, 2357, 2358,
 - 2377, 2386, 2415, 2416, 2417, 2418,
 - 2468, 2481, 2482, 2483, 2485, 2488,
 - 2491, 2492, 2497, 2498, 2499, 2507,
 - 2706, 2768, 2839, 3252, 3255, 3271,
 - 3274, 3305, 3312, 3452, 3886, 4167,
 - 4169, 4505, 4996, 5259, 6328, 6331,
 - 6339, 6340, 6588, 6673, 6677, 6711,
 - 6761, 6765, 6770, 6775, 6780, 6787,
 - 6794, 6799, 6804, 6809, 6814, 6819,
 - 6829, 6834, 6839, 6842, 6843, 6844,
 - 6846, 6847, 6858, 6863, 6878, 6879,
 - 6896, 6901, 6902, 6903, 6904, 6905,
 - 6906, 6908, 6910, 6911, 6912, 6913,
 - 6918, 6919, 6940, 6943, 6944, 6946,
 - 6947, 6948, 6951, 6952, 6954, 6955,
 - 6957, 6958, 6960, 7023, 7028, 7046,
 - 7070, 7073, 7080, 7081, 7090, 7091,
 - 7120, 7344, 7367, 7702, 7704, 7706,
 - 7708, 7713, 7714, 7719, 7721, 7723,
 - 7947, 7949, 7951, 7953, 7958, 7959,
 - 7964, 7966, 7968, 8239, 8277, 9316,
 - 9614, 9621, 9767, 9768, 9776, 9778,
 - 9792, 9794, 9846, 9847, 9967, 9968,
 - 10371, 11210, 11211, 11212, 11216,
 - 11217, 11242, 11243, 11322, 11323,
 - 11324, 11325, 11326, 11330, 11331,
 - 11333, 11335, 11405, 11445, 11449,
 - 11471, 11564, 11596, 11681, 11695,
 - 11712, 11722, 11732, 11769, 11772,
 - 12041, 12043, 12207, 12222, 12234,
 - 12313, 12818, 15692, 15693, 15695,
 - 15696, 15697, 15698, 15699, 15701,
 - 16042, 16049, 16056, 17531, 17534,
 - 18479, 18566, 18590, 19180, 19182,
 - 19224, 19226, 19237, 19239, 19659,
 - 19660, 19830, 19831, 19832, 19839
- `\exp_not:n`
 - 30, 30, 30, 30, 30, 30, 31, 31,
 - 31, 31, 43, 43, 44, 45, 46, 59, 63, 64,
 - 101, 102, 103, 122, 141, 211, 215,
 - 216, 216, 218, 220, 221, 272, 300,
 - 303, 303, 308, 308, 308, 308, 317,
 - 349, 401, 404, 408, 408, 440, 720,
 - 720, 720, 808, 1312, 1465, 1467,
 - 1535, 1709, 1711, 1859, 2061, 2257,
 - 2301, 2422, 2437, 2522, 2552, 2554,
 - 2562, 2564, 2568, 2570, 2580, 2582,
 - 2584, 2586, 2588, 2590, 2592, 2594,
 - 2604, 2606, 2608, 2610, 2612, 2614,
 - 2616, 2618, 2636, 2638, 2639, 2677,
 - 2684, 2728, 2770, 2777, 2836, 2840,
 - 2841, 2842, 3097, 3099, 3380, 3504,
 - 3992, 4189, 4190, 4197, 4198, 4214,
 - 4246, 4266, 4269, 4272, 4340, 4393,
 - 4448, 4506, 4546, 4556, 4997, 5961,
 - 5962, 5977, 5979, 6010, 6076, 6169,
 - 6176, 6196, 6332, 6338, 6366, 6371,
 - 6402, 6435, 6712, 6915, 7024, 7029,
 - 7043, 7047, 7119, 7121, 7308, 7345,
 - 7348, 7349, 7368, 7372, 7696, 7713,
 - 7811, 7941, 7958, 8250, 8276, 8377,
 - 8388, 8639, 8660, 8736, 8753, 9555,
 - 9557, 9579, 9581, 9614, 9622, 9623,
 - 9647, 9813, 9849, 9871, 9969, 10114,
 - 10132, 10305, 10307, 11317, 12819,
 - 14841, 15870, 15872, 15874, 16198,
 - 18421, 18434, 19695, 19698, 19700
- `\exp_stop_f:` 31, 31, 31,
 - 32, 32, 32, 284, 320, 349, 349, 349,
 - 531, 600, 720, 2071, 3495, 3505,
 - 3518, 3524, 3678, 3691, 3730, 3731,
 - 3737, 3749, 3765, 3992, 4015, 4026,
 - 4034, 4046, 4201, 4620, 4630, 4638,
 - 4818, 4823, 6612, 6615, 6616, 6623,
 - 6624, 6625, 6626, 6631, 6632, 6652,
 - 6733, 6850, 8207, 8569, 8689, 8903,
 - 8917, 9201, 9403, 10450, 10664,
 - 10672, 10690, 10706, 10934, 10938,
 - 10942, 10944, 10948, 10952, 10960,
 - 10965, 10978, 10985, 10998, 11009,
 - 11010, 11021, 11022, 11031, 11034,
 - 11044, 11079, 11135, 11140, 11224,
 - 11254, 11372, 11411, 11462, 11482,
 - 11509, 11523, 11558, 11585, 11594,
 - 11613, 11629, 11645, 11663, 11723,
 - 11742, 11758, 11773, 11787, 12044,

| | |
|---|---|
| 12055, 12314, 12356, 12360, 12524, 12530, 12532, 12535, 12543, 12544, 12700, 12765, 12770, 12828, 12834, 12849, 12891, 12964, 12986, 13040, 13041, 13049, 13382, 13400, 13453, 13457, 13461, 13479, 13514, 13515, 13516, 13517, 13518, 13544, 13561, 13801, 13802, 13899, 13991, 14020, 14033, 14038, 14047, 14049, 14175, 14204, 14209, 14239, 14281, 14318, 14338, 14450, 14496, 14497, 14502, 14508, 14526, 14549, 14581, 14584, 14627, 14647, 14653, 14662, 14673, 14682, 14697, 14712, 14727, 14742, 14757, 14785, 14829, 15055, 15218, 15220, 15257, 15268, 15300, 15341, 15350, 15365, 15384, 15417, 15430, 15480, 15524, 15575, 15578, 15592, 15800, 15804, 15811, 15959, 16217, 18768, 18780, 18993, 19008, 19063, 19608, 19618, 19627, 19637, 19638, 19644, 19659, 19660, 19661, 19662 | |
| exp internal commands: | |
| <code>__exp_arg_last_unbraced:nn</code> | 2237 |
| <code>__exp_arg_next:Nnn</code> | 2061 , 2068 |
| <code>__exp_arg_next:nnn</code> | |
| | 2061 , 2070 , 2073 , 2081 , 2085 , 2091 |
| <code>__exp_eval_error_msg:w</code> | 2095 |
| <code>__exp_eval_register:N</code> | 2086 , 2092 , 2095 , 2136 , 2141 , 2153 , 2159 , 2177 , 2178 , 2185 , 2248 , 2253 , 2261 , 2263 , 2273 , 2279 , 2288 , 2308 , 2313 |
| <code>\l__exp_internal_tl</code> | |
| | 32 , 261 , 1377 , 1381 , 1382 , 2061 , 2080 , 2081 , 2257 , 2258 |
| <code>__exp_last_two_unbraced:nnN</code> | 2297 |
| <code>\expandafter</code> | 13 , 14 , 21 , 38 , 39 , 42 , 43 , 48 , 49 , 66 , 67 , 90 , 92 , 98 , 123 , 146 , 154 , 169 , 185 , 365 |
| <code>\expanded</code> | 876 |
| <code>\expandglyphsinfont</code> | 950 |
| <code>\expansionERROR</code> | 2319 |
| <code>\ExplFileDate</code> | |
| | 6 , 19767 , 19771 , 19775 , 19779 , 19783 |
| <code>\ExplFileDescription</code> | 6 |
| <code>\ExplFileName</code> | 6 |
| <code>\ExplFileVersion</code> | |
| | 6 , 19767 , 19771 , 19775 , 19779 , 19783 |
| <code>\ExplSyntaxOff</code> | 3 , 6 , 6 , 6 , 6 , 7 , 207 , 235 , 236 , 236 , 240 , 254 |
| <code>\ExplSyntaxOn</code> | 3 , 6 , 6 , 6 , 6 , 7 , 235 , 236 , 236 , 236 , 304 , 418 |
| | F |
| <code>false</code> | 188 |
| <code>\fam</code> | 366 |
| <code>\fi</code> | 17 , 35 , 41 , 51 , 70 , 71 , 72 , 95 , 96 , 97 , 100 , 101 , 130 , 139 , 152 , 153 , 170 , 186 , 204 , 367 |
| fi commands: | |
| <code>\fi:</code> | 21 , 79 , 79 , 79 , 89 , 94 , 94 , 142 , 157 , 198 , 198 , 199 , 263 , 268 , 270 , 308 , 310 , 310 , 333 , 335 , 337 , 365 , 374 , 399 , 540 , 564 , 579 , 579 , 605 , 664 , 1294 , 1338 , 1461 , 1474 , 1494 , 1544 , 1549 , 1556 , 1594 , 1599 , 1629 , 1630 , 1638 , 1644 , 1657 , 1658 , 1666 , 1672 , 1720 , 1760 , 1774 , 1852 , 1872 , 1882 , 1893 , 1945 , 2006 , 2052 , 2100 , 2103 , 2110 , 2111 , 2346 , 2367 , 2374 , 2383 , 2398 , 2399 , 2400 , 2414 , 2434 , 2436 , 2457 , 2458 , 2633 , 2852 , 2853 , 2889 , 2902 , 2915 , 2925 , 2942 , 2954 , 2958 , 2974 , 3166 , 3219 , 3224 , 3233 , 3235 , 3262 , 3285 , 3301 , 3310 , 3319 , 3325 , 3332 , 3337 , 3348 , 3352 , 3360 , 3499 , 3506 , 3519 , 3524 , 3607 , 3611 , 3612 , 3630 , 3683 , 3693 , 3735 , 3741 , 3742 , 3753 , 3765 , 3766 , 3787 , 3825 , 3851 , 3976 , 3982 , 3994 , 3995 , 4020 , 4032 , 4036 , 4037 , 4049 , 4063 , 4242 , 4245 , 4282 , 4298 , 4319 , 4329 , 4380 , 4385 , 4623 , 4646 , 4663 , 4664 , 4666 , 4712 , 4721 , 4776 , 4784 , 4811 , 4819 , 4825 , 4848 , 4885 , 4893 , 5178 , 5211 , 5259 , 5264 , 5401 , 5430 , 5453 , 5462 , 5498 , 5500 , 5516 , 5524 , 5548 , 5563 , 5571 , 5687 , 5695 , 5730 , 5757 , 5776 , 5901 , 5903 , 5905 , 5907 , 5909 , 5911 , 6053 , 6068 , 6091 , 6107 , 6620 , 6623 , 6624 , 6625 , 6626 , 6631 , 6632 , 6637 , 6638 , 6639 , 6640 , 6677 , 6735 , 6737 , 6766 , 6771 , 6776 , 6781 , 6788 , 6795 , 6800 , 6805 , 6810 , 6815 , 6820 , 6825 , 6830 , 6835 , 6854 , 6859 , 6870 , 6871 , 6918 , 6919 , 6970 , 6979 , 6988 , 6996 , 7062 , 7076 , 7085 , 7095 , 7105 , 7408 , 7444 , 7510 , 8626 , 8896 , 8905 , 8926 , 8935 , 8939 , 8946 , 8954 , 9149 , 9172 , 9181 , 9200 , 9204 , 9218 , 9407 , 9560 , 9584 , 9598 , 9608 , 9628 , 9629 , 9638 , 10507 , 10516 , 10520 , 10532 , 10542 , 10552 , 10612 , 10650 , 10651 , 10652 , 10653 , 10654 , 10655 , 10656 , 10657 , 10658 , 10659 , 10660 , 10661 , 10668 , 10678 , 10686 , 10697 , 10700 , 10712 , 10719 , 10724 , 10727 , 10866 , |

10940, 10941, 10950, 10951, 10962,
 10963, 10964, 10975, 10976, 10977,
 10984, 10995, 10996, 10997, 11007,
 11008, 11012, 11013, 11021, 11024,
 11025, 11033, 11043, 11056, 11079,
 11123, 11142, 11143, 11152, 11158,
 11178, 11179, 11207, 11228, 11245,
 11252, 11260, 11261, 11306, 11307,
 11308, 11371, 11387, 11409, 11410,
 11417, 11425, 11454, 11455, 11458,
 11460, 11461, 11466, 11476, 11479,
 11481, 11486, 11517, 11530, 11535,
 11541, 11544, 11545, 11579, 11580,
 11607, 11608, 11621, 11624, 11635,
 11658, 11677, 11687, 11703, 11717,
 11723, 11727, 11732, 11738, 11753,
 11764, 11783, 11793, 11795, 11801,
 11822, 11848, 11874, 11986, 11987,
 11988, 12050, 12054, 12064, 12065,
 12081, 12100, 12114, 12118, 12124,
 12136, 12165, 12190, 12200, 12214,
 12230, 12242, 12259, 12275, 12308,
 12317, 12323, 12336, 12338, 12358,
 12359, 12366, 12384, 12487, 12498,
 12510, 12511, 12512, 12519, 12521,
 12522, 12528, 12529, 12532, 12538,
 12539, 12547, 12548, 12550, 12551,
 12681, 12694, 12704, 12705, 12710,
 12711, 12712, 12713, 12714, 12715,
 12722, 12731, 12736, 12760, 12763,
 12765, 12772, 12801, 12804, 12805,
 12810, 12832, 12833, 12840, 12853,
 12871, 12873, 12883, 12897, 12927,
 12936, 12970, 12992, 13010, 13027,
 13044, 13045, 13047, 13048, 13053,
 13068, 13101, 13130, 13131, 13132,
 13133, 13134, 13147, 13189, 13262,
 13327, 13329, 13330, 13340, 13369,
 13372, 13373, 13384, 13404, 13467,
 13468, 13469, 13481, 13520, 13521,
 13522, 13523, 13529, 13532, 13534,
 13544, 13561, 13777, 13781, 13783,
 13787, 13794, 13795, 13805, 13806,
 13809, 13901, 13970, 13981, 13993,
 14019, 14026, 14037, 14053, 14060,
 14121, 14177, 14187, 14189, 14199,
 14217, 14218, 14250, 14253, 14262,
 14264, 14266, 14285, 14299, 14300,
 14320, 14341, 14342, 14355, 14371,
 14387, 14403, 14419, 14435, 14449,
 14457, 14463, 14474, 14477, 14480,
 14489, 14499, 14501, 14507, 14514,
 14517, 14526, 14534, 14555, 14588,
 14589, 14616, 14618, 14632, 14633,
 14652, 14667, 14673, 14674, 14675,
 14692, 14707, 14722, 14737, 14752,
 14767, 14770, 14772, 14789, 14834,
 15061, 15097, 15098, 15108, 15149,
 15150, 15174, 15206, 15212, 15213,
 15216, 15218, 15219, 15224, 15236,
 15255, 15260, 15267, 15270, 15302,
 15312, 15313, 15323, 15345, 15360,
 15378, 15386, 15389, 15417, 15425,
 15441, 15479, 15500, 15523, 15544,
 15577, 15591, 15597, 15652, 15653,
 15749, 15750, 15766, 15790, 15801,
 15802, 15818, 15961, 15973, 15974,
 16030, 16100, 16109, 16120, 16129,
 16138, 16173, 16183, 16193, 16301,
 16303, 16422, 16424, 16434, 18415,
 19132, 19133, 19136, 19610, 19623,
 19630, 19642, 19648, 19649, 19659,
 19660, 19661, 19671, 19678, 19680

file commands:

```

\file_add_path:nN .....
    136, 136, 142, 8393, 8435, 8547, 8559
\g_file_current_name_tl .....
    136, 7545, 8321, 8339, 8471, 8472, 8475
\file_if_exist:nTF .....
    ..... 136, 136, 136, 136, 142,
    8433, 8447, 18217, 18222, 18230, 18235
\file_if_exist_input:n .... 211, 211
\file_if_exist_input:nTF .....
    ..... 211, 211, 18215, 18220, 18228
\file_input:n .....
    ... 136, 136, 136, 137, 211, 211, 8440
\file_list: ..... 137, 137, 8490
\file_path_include:n .....
    ..... 136, 136, 136, 211, 8478
\file_path_remove:n .. 137, 137, 8478
  
```

file internal commands:

```

\__file_add_path:nN ..... 8393
\__file_add_path_search:nN ... 8393
\__file_if_exist:nTF .....
    ..... 142, 8440, 18562, 18587
\__file_input:n .....
    ... 8440, 18218, 18225, 18231, 18238
\__file_input_aux:n ..... 8440
\g__file_internal_ior .....
    142, 8397, 8398, 8401, 8418, 8419, 8643
\l__file_internal_name_tl .....
    ..... 142, 468, 8343, 8359, 8360,
    8361, 8366, 8373, 8374, 8376, 8377,
    8383, 8388, 8435, 8436, 8443, 8547,
    8548, 8550, 8559, 8560, 8563, 18218,
    18225, 18231, 18238, 18570, 18593
\l__file_internal_seq .... 8348,
    8411, 8413, 8492, 8498, 8503, 8505
  
```

| | |
|--|--|
| _file_internal_tl | 629 |
| 8342, 8356, 8357, 8474, 8475 | |
| _file_name_sanitize:nn | 630 |
| 142, 142, 8351, 8394, | |
| 8450, 8479, 8487, 8543, 8553, 8692 | |
| _file_name_sanitize_aux:n .. | 878 |
| 8351 | |
| _file_path_include:n | 372 |
| 8478 | |
| _g_file_record_seq | 373 |
| 471, | |
| 472, 472, 8334, 8464, 8469, 8492, 8512 | |
| _l_file_saved_search_path_seq .. | 1157 |
| 8345, 8409, 8429 | |
| _l_file_search_path_seq | 879 |
| 8344, 8410, 8412, | |
| 8413, 8416, 8428, 8482, 8483, 8488 | |
| _g_file_stack_seq | |
| 471, 8333, 8471, 8474 | |
| \finalhyphendemerits | fp commands: |
| \firstmark | _c_e_fp |
| \firstmarks | 179, 181, 15915 |
| \firstvalidlanguage | _fp_abs:n |
| flag commands: | 183, 188, 188, 702, 15672, 17747, |
| _flag_clear:n | 17827, 17829, 17831, 18170, 18172 |
| 81, 81, 81, 5421, 5434, 5473 | _fp_add:Nn |
| _flag_clear_new:n | 174, 174, 702, 15892 |
| 81, 81, 5433 | _fp_compare:nNnTF |
| _flag_height:n | 176, 176, 177, 177, 177, 177, |
| 82, 82, 5438, 5455, 5469, 5486 | 12489, 12584, 12590, 12595, 12603, |
| _flag_if_exist:n | 12647, 12653, 15811, 15825, 15854, |
| 82 | 16932, 17613, 17615, 17620, 17846, |
| _flag_if_exist:nTF 82, 5434, 5442, 5480 | 17855, 18154, 19908, 19914, 20186 |
| _flag_if_exist_p:n | _fp_compare:nTF |
| 82, 5442 | 176, 176, 177, 177, 177, 178, |
| _flag_if_raised:n | 183, 12476, 12556, 12562, 12567, 12575 |
| 82, 5491 | _fp_compare_p:n |
| _flag_if_raised:nTF | 176, 176, 12476 |
| 82, 5447 | _fp_compare_p:nNn ... |
| _flag_if_raised_p:n | 176, 176, 12489 |
| 82, 5447 | _fp_const:Nn |
| _flag_log:n | 173, |
| 81, 81, 5435 | 173, 15869, 15915, 15916, 15917, 15918 |
| _flag_new:n | _fp_do_until:nn |
| 81, 81, 81, | 177, 177, 12553 |
| 5416, 5434, 10762, 10763, 10764, 10765 | _fp_do_until:nNnn ... |
| _flag_raise:n .. | 177, 177, 12581 |
| 82, 82, 5466, 10796, | _fp_do_while:nn |
| 10805, 10813, 10830, 10839, 10870 | 177, 177, 12553 |
| _flag_show:n | _fp_do_while:nNnn ... |
| 81, 81, 5435 | 177, 177, 12581 |
| flag fp commands: | _fp_eval:n |
| flag_fp_division_by_zero .. | 174, 174, 176, 182, 182, 182, 183, |
| 180, 10762 | 183, 183, 183, 183, 183, 183, 183, |
| flag_fp_invalid_operation .. | 183, 183, 183, 183, 184, 184, 184, |
| 180, 10762 | 184, 184, 184, 185, 185, 185, 185, |
| flag_fp_overflow | 185, 185, 185, 185, 185, 185, 185, |
| 180, 10762 | 185, 185, 185, 185, 185, 185, 185, |
| flag_fp_underflow | 185, 185, 186, 186, 186, 186, 186, |
| 180, 10762 | 186, 186, 186, 186, 187, 187, 187, |
| flag internal commands: | 188, 188, 708, 15669, 19919, 19934, |
| _flag_chk_exist:n | 19936, 20026, 20044, 20045, 20046, |
| 5471 | 20047, 20059, 20060, 20068, 20069, |
| _flag_clear:wn | 20076, 20083, 20085, 20091, 20092, |
| 5421, 5476 | 20093, 20104, 20109, 20115, 20116, |
| _flag_height_end:wn | 20188, 20205, 20206, 20383, 20405, |
| 5455 | 20406, 20417, 20418, 20430, 20431, |
| _flag_height_loop:wn ... | 20443, 20445, 20450, 20461, 20473, |
| 5455, 5489 | 20484, 20485, 20577, 20592, 20593, |
| \floatingpenalty | 20794, 20812, 20813, 20814, 20829, |
| 370 | 20847, 20848, 20849, 20898, 20899 |
| floor | _fp_format:nn |
| 184 | 189 |
| \fmtname | _fp_function:Nw |
| 145 | 174, 15892 |
| \font | _fp_gadd:Nn |
| 371 | 162, 10025 |
| \fontcharcp | _fp_gset:N |
| 627 | |
| \fontcharht | |
| 628 | |

- \fp_gset:Nn .. [173](#), [15869](#), [15893](#), [15895](#)
- \fp_gset_eq:NN [174](#), [15878](#), [15883](#)
- \fp_gsub:Nn [174](#), [15892](#)
- \fp_gzero:N [173](#), [15882](#), [15889](#)
- \fp_gzero_new:N [173](#), [15886](#)
- \fp_if_exist:NTF
 . [175](#), [175](#), [12474](#), [15887](#), [15889](#), [15904](#)
- \fp_if_exist_p:N [175](#), [175](#), [12474](#)
- \fp_if_nan:nTF [189](#)
- \fp_log:N [180](#), [180](#), [15910](#)
- \fp_log:n [180](#), [180](#), [15910](#)
- \fp_max:nn [188](#), [188](#), [15674](#)
- \fp_min:nn [188](#), [15674](#)
- \fp_new:N [173](#), [173](#), [173](#),
 [15866](#), [15887](#), [15889](#), [15919](#), [15920](#),
 [15921](#), [15922](#), [16584](#), [16585](#), [17583](#),
 [17584](#), [17585](#), [17707](#), [17708](#), [17985](#),
 [17986](#), [18131](#), [18132](#), [19927](#), [19928](#)
- \fp_new_function:Npn [12396](#)
- .fp_set:N [162](#), [10025](#)
- \fp_set:Nn [173](#), [173](#),
 [15869](#), [15892](#), [15894](#), [16928](#), [16930](#),
 [17600](#), [17601](#), [17602](#), [17715](#), [17717](#),
 [17755](#), [17772](#), [17789](#), [17803](#), [17805](#),
 [17820](#), [17821](#), [17995](#), [17996](#), [18137](#),
 [18139](#), [18164](#), [18165](#), [19907](#), [19910](#)
- \fp_set_eq:NN [174](#),
 [174](#), [15878](#), [15882](#), [17760](#), [17777](#), [17791](#)
- \fp_show:N . [180](#), [180](#), [709](#), [15902](#), [15911](#)
- \fp_show:n . [180](#), [180](#), [709](#), [15902](#), [15913](#)
- \fp_step_function:nnnN
 [178](#), [178](#), [12609](#), [12667](#)
- \fp_step_inline:nnnn [178](#), [178](#), [12662](#)
- \fp_sub:Nn [174](#), [174](#), [15892](#)
- \fp_to_decimal:N [174](#),
 [174](#), [175](#), [10755](#), [15513](#), [15618](#), [15669](#)
- \fp_to_decimal:n
 [174](#), [174](#), [174](#), [174](#), [175](#), [700](#), [15513](#),
 [15621](#), [15671](#), [15673](#), [15675](#), [15677](#)
- \fp_to_dim:N [174](#), [174](#), [15617](#)
- \fp_to_dim:n [174](#), [174](#), [179](#),
 [15617](#), [16938](#), [16964](#), [17645](#), [17656](#),
 [17747](#), [18068](#), [18076](#), [18180](#), [18182](#)
- \fp_to_int:N [175](#), [175](#), [15622](#)
- \fp_to_int:n [175](#),
 [175](#), [705](#), [15622](#), [15826](#), [15827](#), [18303](#)
- \fp_to_int_dispatch:w [700](#)
- \fp_to_scientific:N
 [175](#), [175](#), [10756](#), [15469](#)
- \fp_to_scientific:n
 [175](#), [175](#), [175](#), [15469](#)
- \fp_to_tl:N ... [175](#), [175](#), [15582](#), [15905](#)
- \fp_to_tl:n [175](#), [175](#),
 [10464](#), [10795](#), [10804](#), [10829](#), [10838](#),
 [10867](#), [12639](#), [12650](#), [15582](#), [15908](#)
- \fp_trap:nn [180](#), [180](#), [180](#),
 [545](#), [10766](#), [10881](#), [10882](#), [10883](#), [10884](#)
- \fp_until_do:nn [177](#), [177](#), [12553](#)
- \fp_until_do:nNnn ... [177](#), [177](#), [12581](#)
- \fp_use:N
 . [175](#), [175](#), [15669](#), [19913](#), [19917](#), [19922](#)
- \fp_while_do:nn [178](#), [178](#), [12553](#)
- \fp_while_do:nNnn ... [177](#), [177](#), [12581](#)
- \fp_zero:N [173](#), [173](#), [15882](#), [15887](#), [19909](#)
- fp_zero:N [173](#)
- \fp_zero_new:N [173](#), [173](#), [15886](#)
- \c_inf_fp [178](#), [187](#),
 [10473](#), [11882](#), [13144](#), [13224](#), [14246](#),
 [14479](#), [14482](#), [14486](#), [14510](#), [14774](#)
- \c_nan_fp [187](#), [548](#), [569](#), [10473](#), [10806](#),
 [10814](#), [10886](#), [11067](#), [11086](#), [11092](#),
 [11276](#), [11281](#), [11290](#), [11396](#), [11434](#),
 [11873](#), [11883](#), [12137](#), [12426](#), [12643](#),
 [14453](#), [15205](#), [15713](#), [15775](#), [15789](#)
- \c_one_fp [178](#), [11886](#), [12341](#),
 [12362](#), [12719](#), [14240](#), [14448](#), [14500](#),
 [14698](#), [14728](#), [15199](#), [15784](#), [15915](#)
- \c_pi_fp .. [179](#), [187](#), [579](#), [11884](#), [15917](#)
- \g_tmpa_fp [179](#), [15919](#)
- \l_tmpa_fp [179](#), [15919](#)
- \g_tmpb_fp [179](#), [15919](#)
- \l_tmpb_fp [179](#), [15919](#)
- \c_zero_fp [178](#), [609](#), [708](#),
 [10473](#), [10525](#), [11887](#), [12353](#), [12365](#),
 [12721](#), [12973](#), [13140](#), [14249](#), [14476](#),
 [14513](#), [15422](#), [15644](#), [15867](#), [15882](#),
 [15883](#), [17613](#), [17615](#), [17620](#), [17846](#),
 [17855](#), [18154](#), [19908](#), [19914](#), [20186](#)
- fp internal commands:
- __fp_&_o:ww [598](#), [605](#), [12724](#)
- __fp*_o:ww [13105](#)
- __fp+_o:ww [608](#),
 [608](#), [608](#), [608](#), [608](#), [636](#), [12821](#)
- __fp_,_o:ww [590](#), [12103](#)
- __fp_-_o:ww [608](#), [608](#), [608](#), [12816](#)
- __fp/_o:ww [617](#), [617](#), [656](#), [13215](#)
- __fp^_o:ww [14444](#)
- __fp_acos_o:w [692](#), [695](#), [15363](#)
- __fp_acot_o:Nw . [11936](#), [11938](#), [15185](#)
- __fp_acotii_o:Nww [15188](#), [15193](#), [15209](#)
- __fp_acotii_o:ww [688](#)
- __fp_acsc_normal_o:NnwNnw
 [694](#), [15421](#), [15436](#), [15444](#)
- __fp_acsc_o:w [15415](#)
- __fp_add:NNNn [15892](#)
- __fp_add_big_i:wNww [610](#)

- __fp_add_big_i_o:wNww 608, 611, 12893, 12900, 14272
- __fp_add_big_ii_o:wNww 610
- __fp_add_big_ii_o:wNww 12896, 12900
- __fp_add_inf_o:Nww ... 12837, 12857
- __fp_add_normal_o:Nww 610, 12836, 12877
- __fp_add_npos_o:NwnNw 610, 12880, 12886
- __fp_add_return_ii_o:Nww 12839, 12845, 12850
- __fp_add_significand_carry_o:wwwNN 612, 12933, 12948
- __fp_add_significand_no_carry_o:wwwNN 612, 12935, 12938
- __fp_add_significand_o:NnnwnnnN 611, 611, 12903, 12911, 12916
- __fp_add_significand_pack:NNNNNN 12916
- __fp_add_significand_test_o:N 12916
- __fp_add_zeros_o:Nww . 12835, 12847
- __fp_and_return:wNw 12724
- __fp_array_count:n 10729, 11051, 15198, 15783
- __fp_array_count_loop:Nw 10729
- __fp_array_to_clist:n 11112, 12197, 12198, 15678, 15816
- __fp_array_to_clist_loop:Nw . 15678
- __fp_asec_o:w 15428
- __fp_asin_auxi_o:NnNww 15393, 15396, 15455
- __fp_asin_auxi_o:nNww . 693, 693, 695
- __fp_asin_isqrt:wn 15396
- __fp_asin_normal_o:NwnNnnnw ... 15354, 15370, 15381
- __fp_asin_o:w 15348
- __fp_atan_auxi:ww . 690, 15273, 15287
- __fp_atan_auxii:w 15287
- __fp_atan_combine_aux:ww 15314
- __fp_atan_combine_o:NwwwwwN ... 689, 689, 15233, 15250, 15314
- __fp_atan_dispatch_o:NNnNw .. 15185
- __fp_atan_div:wNwnw 690, 15261, 15263
- __fp_atan_inf_o:NNNw 688, 688, 15221, 15222, 15223, 15231, 15366, 15439
- __fp_atan_near:wwn 15263
- __fp_atan_near_aux:wwn 15263
- __fp_atan_normal_o:NNwnNw 688, 15225, 15241
- __fp_atan_o:Nw . 11940, 11942, 15185
- __fp_atan_Taylor_break:w 15298
- __fp_atan_Taylor_loop:www 691, 15293, 15298
- __fp_atan_test_o:NwnNwn 694, 15244, 15248, 15403
- __fp_atanii_o:Nww 15188, 15193, 15209
- __fp_basics_pack_high:NNNNNw ... 612, 628, 12795, 12941, 13093, 13194, 13206, 13346, 13539, 13998
- __fp_basics_pack_high_carry:w .. 607, 12795
- __fp_basics_pack_low:NNNNNw ... 619, 628, 12795, 12943, 13095, 13196, 13208, 13348, 13488, 13490, 13541, 14000
- __fp_basics_pack_weird_high:NNNNNNNNw 190, 12806, 12952, 13357
- __fp_basics_pack_weird_low:NNNNw 190, 12806, 12954, 13359
- \c__fp_big_leading_shift_int ... 10590, 13418, 13688, 13698, 13708
- \c__fp_big_middle_shift_int 10590, 13421, 13424, 13427, 13430, 13433, 13436, 13440, 13690, 13700, 13710, 13719, 13722, 13725
- \c__fp_big_trailing_shift_int ... 10590, 13444, 13732
- \c__fp_Bigg_leading_shift_int ... 10595, 13268, 13285
- \c__fp_Bigg_middle_shift_int ... 10595, 13271, 13274, 13288, 13291
- \c__fp_Bigg_trailing_shift_int .. 10595, 13277, 13294
- \c__fp_block_int 10478, 13950
- __fp_case_return:nw 10651, 10691, 10694, 10699, 11172, 14205, 15221, 15222, 15223, 15481, 15525, 15593, 15595, 15596, 15644
- __fp_case_return_i_o:ww . 10658, 12838, 12852, 12861, 13138, 15212
- __fp_case_return_ii_o:ww 10658, 13139, 14498, 14516, 15213
- __fp_case_return_o:Nw 541, 10652, 14240, 14245, 14248, 14448, 14453, 14476, 14479, 14482, 14698, 14728, 15422, 15424
- __fp_case_return_o:Nww 10656, 13140, 13141, 13144, 13145, 14500, 14509, 14512
- __fp_case_return_same_o:w 541, 10654, 13369, 13373, 14025, 14252, 14473, 14683, 14691, 14706, 14721, 14736, 14743, 14751, 14766, 15351, 15359, 15377, 15423, 15440

- __fp_case_use:nw [10650](#), [12863](#), [13136](#),
[13137](#), [13142](#), [13143](#), [13223](#), [13226](#),
[13371](#), [14018](#), [14021](#), [14484](#), [14684](#),
[14689](#), [14699](#), [14704](#), [14714](#), [14719](#),
[14729](#), [14734](#), [14744](#), [14749](#), [14759](#),
[14764](#), [15353](#), [15356](#), [15366](#), [15368](#),
[15374](#), [15418](#), [15420](#), [15431](#), [15434](#),
[15439](#), [15484](#), [15494](#), [15528](#), [15538](#)
- __fp_chk:w
..... [530](#), [530](#), [530](#), [530](#), [531](#), [532](#),
[532](#), [532](#), [532](#), [532](#), [579](#), [579](#), [608](#),
[610](#), [610](#), [610](#), [613](#), [618](#), [618](#), [621](#),
[621](#), [10460](#), [10473](#), [10474](#), [10475](#),
[10476](#), [10477](#), [10485](#), [10487](#), [10490](#),
[10496](#), [10500](#), [10521](#), [10524](#), [10526](#),
[10536](#), [10546](#), [10559](#), [10578](#), [10662](#),
[10688](#), [10862](#), [10867](#), [11069](#), [11115](#),
[11124](#), [11126](#), [11893](#), [12481](#), [12506](#),
[12507](#), [12626](#), [12639](#), [12643](#), [12683](#),
[12684](#), [12687](#), [12698](#), [12699](#), [12707](#),
[12708](#), [12716](#), [12727](#), [12730](#), [12742](#),
[12768](#), [12822](#), [12842](#), [12843](#), [12845](#),
[12846](#), [12847](#), [12855](#), [12858](#), [12874](#),
[12875](#), [12877](#), [12886](#), [12962](#), [13114](#),
[13148](#), [13149](#), [13152](#), [13231](#), [13367](#),
[13375](#), [13377](#), [13554](#), [13558](#), [14015](#),
[14027](#), [14029](#), [14237](#), [14254](#), [14256](#),
[14445](#), [14464](#), [14466](#), [14467](#), [14470](#),
[14487](#), [14490](#), [14493](#), [14518](#), [14519](#),
[14521](#), [14537](#), [14622](#), [14635](#), [14637](#),
[14641](#), [14645](#), [14680](#), [14693](#), [14695](#),
[14708](#), [14710](#), [14723](#), [14725](#), [14738](#),
[14740](#), [14753](#), [14755](#), [14768](#), [14778](#),
[15210](#), [15226](#), [15227](#), [15231](#), [15242](#),
[15348](#), [15361](#), [15363](#), [15379](#), [15382](#),
[15392](#), [15415](#), [15426](#), [15428](#), [15442](#),
[15444](#), [15449](#), [15477](#), [15501](#), [15504](#),
[15521](#), [15545](#), [15548](#), [15589](#), [15605](#),
[15608](#), [15665](#), [15666](#), [15793](#), [15795](#)
- __fp_compare:wNNNNw [12278](#)
- __fp_compare_aux:wn [12489](#)
- __fp_compare_back:ww
..... [599](#), [599](#), [12356](#), [12502](#), [12505](#), [12697](#)
- __fp_compare_nan:w [599](#), [12505](#)
- __fp_compare_npos:nwnw [598](#),
..... [599](#), [600](#), [12516](#), [12533](#), [12964](#), [13801](#)
- __fp_compare_return:w [12476](#)
- __fp_compare_significand:nnnnnnnn [12533](#)
- __fp_cos_o:w [14695](#)
- __fp_cot_o:w [675](#), [14755](#)
- __fp_cot_zero_o:Nnw
..... [674](#), [675](#), [14713](#), [14755](#)
- __fp_csc_o:w [14710](#)
- __fp_decimate:nNnnnn [541](#),
..... [10604](#), [10673](#), [10707](#), [11128](#), [12902](#),
..... [12910](#), [12989](#), [14288](#), [14292](#), [15554](#)
- __fp_decimate:Nnnnn [10616](#)
- __fp_decimate_auxi:Nnnnn [10620](#)
- __fp_decimate_auxii:Nnnnn ... [10620](#)
- __fp_decimate_auxiii:Nnnnn .. [10620](#)
- __fp_decimate_auxiv:Nnnnn ... [10620](#)
- __fp_decimate_auxix:Nnnnn ... [10620](#)
- __fp_decimate_auxv:Nnnnn [10620](#)
- __fp_decimate_auxvi:Nnnnn ... [10620](#)
- __fp_decimate_auxvii:Nnnnn .. [10620](#)
- __fp_decimate_auxviii:Nnnnn . [10620](#)
- __fp_decimate_auxx:Nnnnn [10620](#)
- __fp_decimate_auxxi:Nnnnn ... [10620](#)
- __fp_decimate_auxxii:Nnnnn .. [10620](#)
- __fp_decimate_auxxiii:Nnnnn . [10620](#)
- __fp_decimate_auxxiv:Nnnnn .. [10620](#)
- __fp_decimate_auxxv:Nnnnn ... [10620](#)
- __fp_decimate_auxxvi:Nnnnn .. [10620](#)
- __fp_decimate_pack:nnnnnnnnnw .
..... [539](#), [10627](#), [10646](#)
- __fp_decimate_pack:nnnnnnnw
..... [10647](#), [10648](#)
- __fp_decimate_tiny:Nnnnn [10616](#)
- __fp_div_npos_o:Nww
..... [620](#), [621](#), [13220](#), [13230](#)
- __fp_div_significand_calc:wwnnnnnnnn [624](#),
..... [624](#), [13247](#), [13256](#), [13302](#), [14098](#), [14105](#)
- __fp_div_significand_calc_-
i:wwnnnnnnnn [13256](#)
- __fp_div_significand_calc_-
ii:wwnnnnnnnn [13256](#)
- __fp_div_significand_i_o:wnnw ..
..... [621](#), [624](#), [13237](#), [13243](#)
- __fp_div_significand_ii:wwn ...
..... [626](#), [13251](#), [13252](#), [13253](#), [13298](#)
- __fp_div_significand_iii:wwnnnnnn
..... [626](#), [13254](#), [13305](#)
- __fp_div_significand_iv:wwnnnnnnnn
..... [627](#), [13308](#), [13313](#)
- __fp_div_significand_large_-
o:wwnnnnnwN [629](#), [13339](#), [13353](#)
- __fp_div_significand_pack:NNN ..
..... [628](#), [628](#),
..... [628](#), [658](#), [658](#), [658](#), [658](#), [658](#), [658](#),
..... [658](#), [13300](#), [13333](#), [14085](#), [14103](#), [14111](#)
- __fp_div_significand_small_-
o:wwnnnnnwN [628](#), [13337](#), [13343](#)
- __fp_div_significand_test_o:w ..
..... [628](#), [628](#), [13245](#), [13334](#)

__fp_div_significand_v:NN
 13318, 13320, 13323
 __fp_div_significand_v:NNw .. 13313
 __fp_div_significand_vi:Nw
 627, 13313
 __fp_division_by_zero_o:Nnw ...
 544, 10826, 10874, 14022, 14774, 14775
 __fp_division_by_zero_o:NNww ...
 544, 10834, 10874, 13224, 13227, 14486
 __fp_ep_compare:www .. 13796, 15257
 __fp_ep_compare_aux:www 13796
 __fp_ep_div:wwwwn
 686, 13826, 13937,
 15175, 15272, 15276, 15285, 15452
 __fp_ep_div_eps_pack:NNNNw .. 13856
 __fp_ep_div_epsilon:wnNNNNn
 648
 __fp_ep_div_epsilon:wnNNNNn
 13853, 13856
 __fp_ep_div_epsilon:wnNNNNn .. 13856
 __fp_ep_div_esti:wwwwn
 648, 13832, 13835
 __fp_ep_div_estii:wnnnwn .. 13835
 __fp_ep_div_estiii:NNNNwwwn .. 13835
 __fp_ep_inv_to_float:wN 676
 __fp_ep_inv_to_float:wwN
 684, 13933, 13941, 14717, 14732
 __fp_ep_isqrt:wn .. 13879, 15413
 __fp_ep_isqrt_aux:wn 13879
 __fp_ep_isqrt_auxii:wn 13882, 13884
 __fp_ep_isqrt_auxiii:wnnnwn .. 13879
 __fp_ep_isqrt_epsilon:wN
 650, 13916, 13919
 __fp_ep_isqrt_epsilon:wwN 13919
 __fp_ep_isqrt_esti:wnnnwn
 13894, 13897
 __fp_ep_isqrt_estii:wnnnwn .. 13897
 __fp_ep_isqrt_estiii:NNNNwwwn ..
 13897
 __fp_ep_mul:wwwwn
 13811, 15132, 15162, 15400, 15411
 __fp_ep_mul_raw:wwwN
 13811, 14796, 15082
 __fp_ep_to_ep:wwN .. 13762, 13813,
 13816, 13828, 13831, 13881, 15401
 __fp_ep_to_ep_end:www 13762
 __fp_ep_to_ep_loop:N
 683, 13762, 15083
 __fp_ep_to_ep_zero:ww 13762
 __fp_ep_to_fixed:wn
 13744, 14793, 15279, 15288, 15398
 __fp_ep_to_fixed_auxi:www ... 13744
 __fp_ep_to_fixed_auxiii:nnnnnnwn
 13744
 __fp_ep_to_float:wN 676
 __fp_ep_to_float:wwN 673,
 684, 13933, 13945, 14687, 14702, 15181
 __fp_error:nnnn
 10795, 10803, 10812, 10829,
 10837, 10865, 10888, 11062, 11064,
 11085, 11090, 12196, 12638, 12649
 __fp_exp_after_f:nw ... 566, 11264
 __fp_exp_after_array_f:w 10579,
 11855, 12746, 12757, 12781, 12789
 __fp_exp_after_f:nw
 566, 10526, 11892, 12034
 __fp_exp_after_mark_f:nw 566, 11264
 __fp_exp_after_normal:nNNw
 10529, 10539, 10549, 10566
 __fp_exp_after_normal:Nnnwn
 10568, 10576
 __fp_exp_after_o:nw 10526
 __fp_exp_after_o:w .. 535, 10526,
 10655, 10659, 10661, 11122, 11166,
 11184, 12011, 12376, 12715, 12732,
 12846, 13556, 14634, 14639, 15860
 __fp_exp_after_special:nNNw ...
 10531, 10541, 10551, 10556
 __fp_exp_after_stop_f:nw 10579
 __fp_exp_large:w 14332
 __fp_exp_large:wN 14332
 __fp_exp_large_after:wn 14332
 __fp_exp_large_i:wN 14332
 __fp_exp_large_ii:wN 14332
 __fp_exp_large_iii:wN 14332
 __fp_exp_large_iv:wN 14332
 __fp_exp_large_v:wN .. 14332, 14621
 __fp_exp_normal:w 14242, 14256
 __fp_exp_o:w 14237
 __fp_exp_overflow: ... 14278, 14303
 __fp_exp_pos:NNwnw
 14259, 14261, 14264
 __fp_exp_pos:Nnnwn 14256
 __fp_exp_pos_large:Nnnwn
 14293, 14332
 __fp_exp_Taylor:Nnnwn
 14289, 14305, 14441
 __fp_exp_Taylor_break:Nnw ... 14305
 __fp_exp_Taylor_ii:ww .. 14311, 14314
 __fp_exp_Taylor_loop:www 14305
 __fp_expand:n 702, 10738, 15488, 15682
 __fp_expand_loop:nnwN 10738
 __fp_exponent:w 10500
 \c__fp_five_int 10932,
 10956, 10969, 10982, 10989, 11041
 __fp_fixed_add:nnNnnwn 13638
 __fp_fixed_add:Nnnnnwn 13638

- __fp_fixed_add:wnn
 ... [637](#), [637](#), [13638](#), [13877](#), [14179](#),
 [14187](#), [14198](#), [14216](#), [15284](#), [15344](#)
- __fp_fixed_add_after:NNNNNwn . [13638](#)
- __fp_fixed_add_one:wN
 .. [13570](#), [13870](#), [14322](#), [14331](#), [15410](#)
- __fp_fixed_add_pack:NNNNNwn . [13638](#)
- __fp_fixed_continue:wn
 [13569](#), [13814](#), [13819](#), [13829](#), [14345](#),
 [14361](#), [14377](#), [14393](#), [14409](#), [14425](#),
 [14597](#), [14831](#), [15120](#), [15402](#), [15411](#)
- __fp_fixed_div_int:wnN [13607](#)
- __fp_fixed_div_int:wwN
 [13607](#), [14178](#), [14321](#), [15303](#)
- __fp_fixed_div_int_after:Nw ...
 [639](#), [13607](#)
- __fp_fixed_div_int_auxi:wnn . [13607](#)
- __fp_fixed_div_int_auxii:wnn ...
 [639](#), [13607](#)
- __fp_fixed_div_int_pack:Nw
 [639](#), [639](#), [639](#), [639](#), [639](#), [13607](#)
- __fp_fixed_div_myriad:wn
 [13575](#), [13874](#)
- __fp_fixed_inv_to_float:wN
 [13940](#), [14261](#), [14533](#)
- __fp_fixed_mul:nnnnnnnw [13658](#)
- __fp_fixed_mul:wnn
 [637](#), [638](#), [682](#), [684](#), [13658](#),
 [13823](#), [13854](#), [13869](#), [13871](#), [13875](#),
 [13928](#), [13931](#), [13944](#), [14180](#), [14190](#),
 [14230](#), [14323](#), [14342](#), [14442](#), [14543](#),
 [15089](#), [15143](#), [15291](#), [15324](#), [15326](#)
- __fp_fixed_mul_add:nnnnwnnnn ...
 [13726](#), [13728](#)
- __fp_fixed_mul_add:nnnnwnnwN ...
 [13733](#), [13739](#)
- __fp_fixed_mul_add:Nwnnnwnnn ...
 [13691](#), [13701](#), [13711](#), [13715](#)
- __fp_fixed_mul_add:wwn [13685](#)
- __fp_fixed_mul_after:wnn
 [641](#), [13577](#), [13583](#), [13586](#),
 [13660](#), [13687](#), [13697](#), [13707](#), [14560](#)
- __fp_fixed_mul_one_minus_-
 mul:wnn [13685](#)
- __fp_fixed_mul_short:wnn [13584](#),
 [13852](#), [13873](#), [13915](#), [13917](#), [15337](#)
- __fp_fixed_mul_sub_back:wwn ...
 [13685](#),
 [13929](#), [15110](#), [15112](#), [15113](#), [15114](#),
 [15115](#), [15116](#), [15117](#), [15118](#), [15119](#),
 [15123](#), [15125](#), [15126](#), [15127](#), [15128](#),
 [15129](#), [15130](#), [15131](#), [15156](#), [15158](#),
 [15159](#), [15160](#), [15161](#), [15164](#), [15166](#),
 [15167](#), [15168](#), [15169](#), [15304](#), [15312](#)
- __fp_fixed_one_minus_mul:wnn ...
 [642](#), [643](#), [13705](#)
- __fp_fixed_sub:wnn
 [13638](#), [13921](#), [14196](#), [14212](#),
 [14224](#), [14835](#), [15285](#), [15342](#), [15408](#)
- __fp_fixed_to_float:Nw [13947](#), [14205](#)
- __fp_fixed_to_float:wN
 [637](#), [692](#), [13934](#), [13947](#),
 [14225](#), [14235](#), [14259](#), [14529](#), [15332](#)
- __fp_fixed_to_float_pack:ww ...
 [13979](#), [13989](#)
- __fp_fixed_to_float_rad:wN
 [13942](#), [15332](#)
- __fp_fixed_to_float_round_-
 up:wnnnnw [13992](#), [13996](#)
- __fp_fixed_to_float_zero:w
 [13975](#), [13984](#)
- __fp_fixed_to_loop:N
 [13952](#), [13962](#), [13966](#)
- __fp_fixed_to_loop_end:w
 [13968](#), [13972](#)
- __fp_from_dim:wNNnnnnnn [15634](#)
- __fp_from_dim:wnnnnwNn [15661](#), [15662](#)
- __fp_from_dim:wnnnnwNw [15634](#)
- __fp_from_dim:wNw [15634](#)
- __fp_from_dim_test:ww
 [701](#), [11341](#), [11354](#), [11911](#), [15634](#)
- __fp_function_apply:nw
 .. [596](#), [596](#), [597](#), [12391](#), [12407](#), [12429](#)
- __fp_function_args:Nwn .. [596](#), [12396](#)
- __fp_function_store:wwNwnn ...
 [597](#), [12429](#)
- __fp_function_store_end:wnnn ...
 [597](#), [12429](#)
- \c__fp_half_prec_int
 .. [10478](#), [10720](#), [11555](#), [11587](#), [14270](#)
- __fp_inf_fp:N [10484](#), [10850](#)
- __fp_int:wIF [10662](#), [15795](#)
- __fp_int_normal:nnnnn [10662](#)
- __fp_int_p:w [10662](#)
- __fp_int_test:Nw [10662](#)
- __fp_invalid_operation:nnw
 [544](#), [545](#), [10792](#), [10874](#),
 [10886](#), [15486](#), [15496](#), [15530](#), [15540](#)
- __fp_invalid_operation_o:nw [545](#),
 [10885](#), [13371](#), [14018](#), [14690](#), [14705](#),
 [14720](#), [14735](#), [14750](#), [14765](#), [15357](#),
 [15375](#), [15391](#), [15419](#), [15432](#), [15448](#)
- __fp_invalid_operation_o:Nww ...
 [544](#), [10800](#), [10874](#),
 [12866](#), [12869](#), [13142](#), [13143](#), [14628](#)
- __fp_invalid_operation_tl_o:nn .
 [544](#), [10809](#), [10874](#), [11110](#), [15815](#)

- \c__fp_leading_shift_int [10586](#), [13578](#),
[13587](#), [13661](#), [14561](#), [15030](#), [15067](#)
- __fp_ln_c:NwNn [659](#)
- __fp_ln_c:NwNw ... [660](#), [14162](#), [14193](#)
- __fp_ln_div_after:Nw
..... [658](#), [658](#), [14065](#), [14114](#)
- __fp_ln_div_i:w [14087](#), [14096](#)
- __fp_ln_div_ii:wn
.. [14090](#), [14091](#), [14092](#), [14093](#), [14101](#)
- __fp_ln_div_vi:wn [14094](#), [14109](#)
- __fp_ln_exponent:wn [660](#), [14041](#), [14202](#)
- __fp_ln_exponent_one:ww [14207](#), [14221](#)
- __fp_ln_exponent_small:NNww ...
..... [14210](#), [14214](#), [14227](#)
- \c__fp_ln_i_fixed_tl [14006](#)
- \c__fp_ln_ii_fixed_tl [14006](#)
- \c__fp_ln_iii_fixed_tl [14006](#)
- \c__fp_ln_iv_fixed_tl [14006](#)
- \c__fp_ln_ix_fixed_tl [14006](#)
- __fp_ln_npos_o:w
..... [653](#), [654](#), [14027](#), [14029](#)
- __fp_ln_o:w [653](#), [669](#), [14015](#)
- __fp_ln_significand:NNNNnnN ...
..... [655](#), [14040](#), [14043](#), [14541](#)
- __fp_ln_square_t_after:w
..... [14138](#), [14169](#)
- __fp_ln_square_t_pack:NNNNw ...
.. [14140](#), [14142](#), [14144](#), [14146](#), [14167](#)
- __fp_ln_t_large:NNw
..... [658](#), [14119](#), [14126](#), [14136](#)
- __fp_ln_t_small:Nw ... [14117](#), [14124](#)
- __fp_ln_t_small:w [658](#)
- __fp_ln_Taylor:wwNw [659](#), [14170](#), [14171](#)
- __fp_ln_Taylor_break:w [14176](#), [14187](#)
- __fp_ln_Taylor_loop:www
..... [14172](#), [14173](#), [14182](#)
- __fp_ln_twice_t_after:w [14150](#), [14166](#)
- __fp_ln_twice_t_pack:Nw . [14152](#),
[14154](#), [14156](#), [14158](#), [14160](#), [14165](#)
- \c__fp_ln_vi_fixed_tl [14006](#)
- \c__fp_ln_vii_fixed_tl [14006](#)
- \c__fp_ln_viii_fixed_tl [14006](#)
- \c__fp_ln_x_fixed_tl
..... [14006](#), [14224](#), [14231](#)
- __fp_ln_x_ii:wnnnn ... [14045](#), [14063](#)
- __fp_ln_x_iii:NNNNNw . [14072](#), [14076](#)
- __fp_ln_x_iii_var:NNNNw
..... [14070](#), [14078](#)
- __fp_ln_x_iv:wnnnnnnnn
..... [657](#), [14068](#), [14083](#)
- \c__fp_max_exp_exponent_int
..... [10483](#), [14277](#)
- \c__fp_max_exponent_int
..... [530](#), [531](#), [10482](#),
[10491](#), [10497](#), [10514](#), [10515](#), [13785](#),
[13986](#), [14304](#), [14596](#), [15489](#), [15533](#)
- __fp_max_fp:N [10488](#)
- \c__fp_middle_shift_int
..... [10586](#), [13590](#),
[13593](#), [13596](#), [13599](#), [13663](#), [13666](#),
[13669](#), [13672](#), [14563](#), [14566](#), [14569](#),
[14572](#), [15033](#), [15040](#), [15070](#), [15076](#)
- __fp_min_fp:N [10488](#)
- __fp_minmax_auxi:ww
..... [12691](#), [12703](#), [12710](#)
- __fp_minmax_auxii:ww
..... [12693](#), [12701](#), [12710](#)
- __fp_minmax_break_o:w . [12684](#), [12714](#)
- __fp_minmax_loop:Nw
..... [603](#), [12678](#), [12680](#), [12686](#)
- __fp_minmax_o:Nw
..... [598](#), [11944](#), [11946](#), [12675](#)
- __fp_mul_cases_o:NnNnw
..... [620](#), [13107](#), [13113](#), [13217](#)
- __fp_mul_cases_o:nNnw [13113](#)
- __fp_mul_npos_o:Nw [617](#),
[618](#), [620](#), [701](#), [701](#), [13110](#), [13151](#), [15664](#)
- __fp_mul_significand_drop:NNNNw
..... [619](#), [13160](#)
- __fp_mul_significand_keep:NNNNw
..... [13160](#)
- __fp_mul_significand_large_-
f:NwNNNN [13188](#), [13192](#)
- __fp_mul_significand_o:nnnnNnnn
..... [618](#), [619](#), [13158](#), [13160](#)
- __fp_mul_significand_small_-
f:NNwwN [13186](#), [13203](#)
- __fp_mul_significand_test_f:NNN
..... [619](#), [13162](#), [13183](#)
- \c__fp_myriad_int [10481](#),
[13573](#), [13604](#), [13605](#), [13682](#), [13742](#)
- __fp_neg_sign:N
..... [608](#), [10509](#), [12819](#), [12977](#)
- __fp_new_function:NNnnn [12396](#)
- __fp_not_o:w [598](#), [11827](#), [12716](#)
- \c__fp_one_fixed_tl
..... [13567](#), [14178](#), [14336](#),
[14597](#), [14621](#), [15237](#), [15303](#), [15408](#)
- __fp_overflow:w
.... [534](#), [545](#), [546](#), [547](#), [10517](#), [10874](#)
- __fp_pack:NNNNw .. [10586](#), [13579](#),
[13589](#), [13592](#), [13595](#), [13598](#), [13601](#),
[13662](#), [13665](#), [13668](#), [13671](#), [13674](#),
[14562](#), [14565](#), [14568](#), [14571](#), [14574](#)
- __fp_pack_big:NNNNNw ... [10590](#),
[13420](#), [13423](#), [13426](#), [13429](#), [13432](#),

- 13435, 13438, 13442, 13689, 13699,
- 13709, 13718, 13721, 13724, 13731
- __fp_pack_Bigg:NNNNNNw
 10595, 13270,
 13273, 13276, 13287, 13290, 13293
- __fp_pack_eight:wNNNNNNNN
 615, 10602,
 13086, 13391, 13753, 14802, 14803
- __fp_pack_twice_four:wNNNNNNNN .
 10600, 11159, 11160, 13028, 13029,
 13754, 13755, 13756, 13788, 13789,
 13790, 13977, 13978, 14308, 14309,
 14310, 14804, 14805, 15018, 15657
- __fp_parse:n .. 567, 587, 597, 602,
 702, 707, 708, 11190, 11338, 11995,
 12012, 12431, 12479, 12493, 12503,
 12614, 12657, 15475, 15519, 15587,
 15627, 15673, 15675, 15677, 15813,
 15849, 15870, 15872, 15874, 15897
- __fp_parse_after:ww 11995
- __fp_parse_apply_binary:NwNwN ..
 560, 560, 560,
 561, 591, 12025, 12127, 12156, 12201
- __fp_parse_apply_compare:NwNNNNwN
 12340, 12349
- __fp_parse_apply_compare_-
 aux:NNwN 12361, 12364, 12369
- __fp_parse_apply_juxtapose:NwwN
 591, 12178
- __fp_parse_apply_unary:NNwN ...
 11804, 11813, 11919, 11928
- __fp_parse_compare:NNNNNNNN .. 12278
- __fp_parse_compare_auxi:NNNNNNNN
 12278
- __fp_parse_compare_auxii:NNNNN .
 12278
- __fp_parse_compare_end:NNNNw . 12278
- __fp_parse_continue 587
- __fp_parse_continue:NwN
 .. 560, 560, 560, 560, 561, 12014,
 12027, 12379, 12754, 12778, 12786
- __fp_parse_continue_compare:NNwNN
 12372, 12387
- __fp_parse_digits:N 11220
- __fp_parse_digits_i:N 11220
- __fp_parse_digits_ii:N 11220
- __fp_parse_digits_iii:N 11220
- __fp_parse_digits_iv:N 11220
- __fp_parse_digits_v:N 11220
- __fp_parse_digits_vi:N
 11220, 11513, 11561
- __fp_parse_digits_vii:N
 572, 11220, 11500, 11550
- __fp_parse_excl_error: 12278
- __fp_parse_expand:w 563,
 564, 11205, 11207, 11229, 11269,
 11313, 11346, 11350, 11388, 11418,
 11456, 11458, 11477, 11479, 11501,
 11518, 11531, 11551, 11581, 11609,
 11625, 11636, 11659, 11688, 11698,
 11705, 11718, 11734, 11754, 11765,
 11823, 11849, 11858, 11924, 11933,
 12001, 12080, 12095, 12117, 12160,
 12185, 12225, 12237, 12254, 12270,
 12334, 12347, 12394, 12414, 12750
- __fp_parse_exponent:N
 576, 11312, 11492, 11641, 11708, 11710
- __fp_parse_exponent:Nw
 11516, 11529,
 11578, 11606, 11657, 11686, 11705
- __fp_parse_exponent_aux:N ... 11710
- __fp_parse_exponent_body:N
 11736, 11740
- __fp_parse_exponent_digits:N ...
 11744, 11756
- __fp_parse_exponent_keep:N .. 11767
- __fp_parse_exponent_keep:NTF ...
 11747, 11767
- __fp_parse_exponent_sign:N
 11726, 11730
- __fp_parse_function:NNN
 11917, 11936, 11938,
 11940, 11942, 11944, 11946, 11948,
 11950, 11971, 11973, 11975, 11989
- __fp_parse_infix:NN
 .. 566, 568, 584, 589, 597, 11268,
 11397, 11435, 11856, 11875, 11880,
 11892, 11914, 12034, 12039, 12093
- __fp_parse_infix_
 11853, 12074, 12089, 12099, 12168,
 12169, 12171, 12172, 12208, 12220,
 12223, 12232, 12235, 12247, 12258
- __fp_parse_infix_!:N 12278
- __fp_parse_infix_&:Nw 12217
- __fp_parse_infix(:N 12176
- __fp_parse_infix):N 12087
- __fp_parse_infix*:N 12203
- __fp_parse_infix+:N
 597, 11205, 12141
- __fp_parse_infix_,:N 12103
- __fp_parse_infix -:N 12141
- __fp_parse_infix/:N 12141
- __fp_parse_infix::N . 12245, 12739
- __fp_parse_infix<:N 12278
- __fp_parse_infix=:N 12278
- __fp_parse_infix>:N 12278
- __fp_parse_infix?:N 12245
- __fp_parse_infix^:N 12141

__fp_parse_infix_after_operand:NwN
 [568](#), [11303](#), [11361](#), [11830](#), [12032](#)
 __fp_parse_infix_and:N [12141](#), [12239](#)
 __fp_parse_infix_check:NNN
 [12059](#), [12069](#)
 __fp_parse_infix_comma:w [12103](#)
 __fp_parse_infix_comma_error:w .
 [12103](#)
 __fp_parse_infix_end:N
 [587](#), [589](#), [12002](#), [12006](#), [12085](#)
 __fp_parse_infix_juxtapose:N ...
 [591](#), [12049](#), [12057](#), [12177](#), [12178](#)
 __fp_parse_infix_mark:NNN
 [12046](#), [12084](#)
 __fp_parse_infix_mul:N [12141](#), [12211](#)
 __fp_parse_infix_or:N . [12141](#), [12227](#)
 __fp_parse_infix_|:Nw [12217](#)
 __fp_parse_large:N [571](#), [11463](#), [11546](#)
 __fp_parse_large_leading:wwNN ..
 [11548](#), [11553](#)
 __fp_parse_large_round:NN
 [575](#), [11589](#), [11661](#)
 __fp_parse_large_round_aux:wNN .
 [11661](#)
 __fp_parse_large_round_test:NN .
 [11661](#)
 __fp_parse_large_trailing:wwNN .
 [11559](#), [11583](#)
 __fp_parse_letters:N
 [569](#), [569](#), [11376](#), [11390](#)
 __fp_parse_lparen_after:NwN . [11836](#)
 __fp_parse_o:n
 [556](#), [12008](#), [12612](#), [12613](#), [15779](#), [15844](#)
 __fp_parse_one [587](#)
 __fp_parse_one:Nw [559](#), [560](#),
 [560](#), [561](#), [561](#), [561](#), [562](#), [562](#), [570](#),
 [584](#), [11205](#), [11240](#), [11440](#), [11803](#), [12020](#)
 __fp_parse_one_digit:NN
 [582](#), [11256](#), [11359](#)
 __fp_parse_one_fp:NN
 [565](#), [11248](#), [11264](#)
 __fp_parse_one_other:NN [11259](#), [11367](#)
 __fp_parse_one_register:NN
 [11251](#), [11301](#)
 __fp_parse_one_register_aux:Nw .
 [11301](#)
 __fp_parse_one_register_-
 auxii:wwNw [11301](#)
 __fp_parse_one_register_dim:ww .
 [11301](#)
 __fp_parse_one_register_int:www
 [11301](#)
 __fp_parse_one_register_mu:www .
 [11301](#)
 __fp_parse_one_register_wd:Nw [11301](#)
 __fp_parse_one_register_wd:w . [11301](#)
 __fp_parse_operand [587](#)
 __fp_parse_operand:Nw .. [559](#), [559](#),
 [560](#), [560](#), [561](#), [561](#), [561](#), [562](#), [562](#),
 [587](#), [596](#), [596](#), [11205](#), [11819](#), [11821](#),
 [11845](#), [11847](#), [11924](#), [11933](#), [12000](#),
 [12014](#), [12116](#), [12159](#), [12184](#), [12253](#),
 [12269](#), [12347](#), [12394](#), [12414](#), [12749](#)
 __fp_parse_pack_carry:w . [574](#), [11533](#)
 __fp_parse_pack_leading:NNNNw
 [11496](#), [11533](#), [11556](#)
 __fp_parse_pack_trailing:NNNNw
 .. [11506](#), [11533](#), [11575](#), [11586](#), [11593](#)
 __fp_parse_prefix:NNN . [11379](#), [11420](#)
 __fp_parse_prefix_ [11839](#)
 __fp_parse_prefix!:Nw [11809](#)
 __fp_parse_prefix(:Nw [11836](#)
 __fp_parse_prefix):Nw [11867](#)
 __fp_parse_prefix+:Nw [11803](#)
 __fp_parse_prefix-:Nw [11809](#)
 __fp_parse_prefix.:Nw [11828](#)
 __fp_parse_prefix_unknown:NNN [11420](#)
 __fp_parse_return_semicolon:w ..
 [11206](#), [11227](#), [11416](#),
 [11623](#), [11634](#), [11716](#), [11748](#), [11763](#)
 __fp_parse_round:Nw [11976](#)
 __fp_parse_round_after:wN
 [577](#), [11638](#), [11643](#), [11693](#)
 __fp_parse_round_loop:N [576](#), [576](#),
 [577](#), [577](#), [11611](#), [11654](#), [11672](#), [11697](#)
 __fp_parse_round_up:N [11611](#)
 __fp_parse_small:N [571](#), [11483](#), [11494](#)
 __fp_parse_small_leading:wwNN ..
 [11498](#), [11503](#), [11565](#)
 __fp_parse_small_round:NN
 [11525](#), [11643](#), [11682](#)
 __fp_parse_small_trailing:wwNN .
 [11511](#), [11520](#), [11597](#)
 __fp_parse_strim_end:w [11469](#)
 __fp_parse_strim_zeros:N
 [571](#), [582](#), [11450](#), [11469](#), [11834](#)
 __fp_parse_trim_end:w [11443](#)
 __fp_parse_trim_zeros:N [11365](#), [11443](#)
 __fp_parse_unary_function:nNN ..
 [11917](#), [11952](#),
 [11954](#), [11956](#), [11958](#), [11966](#), [11968](#)
 __fp_parse_word:Nw [569](#), [11373](#), [11390](#)
 __fp_parse_word_abs:N [11951](#)
 __fp_parse_word_acos:N [11959](#)
 __fp_parse_word_acosd:N [11959](#)
 __fp_parse_word_acot:N [11935](#)
 __fp_parse_word_acotd:N [11935](#)
 __fp_parse_word_acsc:N [11959](#)

- _fp_parse_word_acscd:N [11959](#)
- _fp_parse_word_asec:N [11959](#)
- _fp_parse_word_asecd:N [11959](#)
- _fp_parse_word_asin:N [11959](#)
- _fp_parse_word_asind:N [11959](#)
- _fp_parse_word_atan:N [11935](#)
- _fp_parse_word_atand:N [11935](#)
- _fp_parse_word_bp:N [11888](#)
- _fp_parse_word_cc:N [11888](#)
- _fp_parse_word_ceil:N [11970](#)
- _fp_parse_word_cm:N [11888](#)
- _fp_parse_word_cos:N [11959](#)
- _fp_parse_word_cosd:N [11959](#)
- _fp_parse_word_cot:N [11959](#)
- _fp_parse_word_cotd:N [11959](#)
- _fp_parse_word_csc:N [11959](#)
- _fp_parse_word_cscd:N [11959](#)
- _fp_parse_word_dd:N [11888](#)
- _fp_parse_word_deg:N [11877](#)
- _fp_parse_word_em:N [11907](#)
- _fp_parse_word_ex:N [11907](#)
- _fp_parse_word_exp:N [11951](#)
- _fp_parse_word_false:N [11877](#)
- _fp_parse_word_floor:N [11970](#)
- _fp_parse_word_in:N [11888](#)
- _fp_parse_word_inf:N [11877](#)
- _fp_parse_word_ln:N [11951](#)
- _fp_parse_word_max:N [11935](#)
- _fp_parse_word_min:N [11935](#)
- _fp_parse_word_mm:N [11888](#)
- _fp_parse_word_nan:N [11877](#)
- _fp_parse_word_nc:N [11888](#)
- _fp_parse_word_nd:N [11888](#)
- _fp_parse_word_pc:N [11888](#)
- _fp_parse_word_pi:N [11877](#)
- _fp_parse_word_pt:N [11888](#)
- _fp_parse_word_rand:N [11935](#)
- _fp_parse_word_randint:N ... [11935](#)
- _fp_parse_word_round:N [11976](#)
- _fp_parse_word_sec:N [11959](#)
- _fp_parse_word_secd:N [11959](#)
- _fp_parse_word_sin:N [11959](#)
- _fp_parse_word_sind:N [11959](#)
- _fp_parse_word_sp:N [11888](#)
- _fp_parse_word_sqrt:N [11951](#)
- _fp_parse_word_tan:N [11959](#)
- _fp_parse_word_tand:N [11959](#)
- _fp_parse_word_true:N [11877](#)
- _fp_parse_word_trunc:N [11970](#)
- _fp_parse_zero: [571](#), [11465](#), [11485](#), [11489](#)
- _fp_pow_B:wwN [14544](#), [14579](#)
- _fp_pow_C_neg:w [14582](#), [14599](#)
- _fp_pow_C_overflow:w [14587](#), [14594](#), [14615](#)
- _fp_pow_C_pack:w [14601](#), [14609](#), [14620](#)
- _fp_pow_C_pos:w [14585](#), [14604](#)
- _fp_pow_C_pos_loop:wN [14605](#), [14606](#), [14613](#)
- _fp_pow_exponent:Nwnnnnnw [14550](#), [14553](#), [14558](#)
- _fp_pow_exponent:wnN . [14542](#), [14547](#)
- _fp_pow_neg:www .. [671](#), [14455](#), [14622](#)
- _fp_pow_neg_aux:wNN ... [671](#), [14622](#)
- _fp_pow_neg_case:w .. [14624](#), [14645](#)
- _fp_pow_neg_case_aux:nnnnn . [14645](#)
- _fp_pow_neg_case_aux:w [14645](#)
- _fp_pow_normal:ww [666](#), [667](#), [14460](#), [14492](#)
- _fp_pow_npos:Nww [14504](#), [14521](#)
- _fp_pow_npos:ww [668](#)
- _fp_pow_npos_aux:NNnw [14527](#), [14531](#), [14537](#)
- _fp_pow_zero_or_inf:ww [666](#), [14462](#), [14469](#)
- \c_fp_prec_and_int ... [11190](#), [12173](#)
- \c_fp_prec_colon_int [11190](#), [12269](#), [12749](#)
- \c_fp_prec_comma_int ... [11190](#), [11845](#), [11869](#), [12107](#), [12112](#), [12116](#)
- \c_fp_prec_comp_int [11190](#), [12301](#), [12347](#)
- \c_fp_prec_end_int [587](#), [11190](#), [12000](#)
- \c_fp_prec_func_int .. [11190](#), [11924](#)
- \c_fp_prec_funcii_int [11190](#), [11844](#), [11933](#), [12394](#), [12414](#)
- \c_fp_prec_hat_int ... [11190](#), [12168](#)
- \c_fp_prec_hatii_int . [11190](#), [12168](#)
- \c_fp_prec_int [10478](#), [10608](#), [10673](#), [10707](#), [11128](#), [14292](#), [14659](#), [14663](#), [15552](#), [15554](#), [15560](#), [15602](#), [15799](#)
- \c_fp_prec_not_int [582](#), [11190](#), [11826](#), [11827](#)
- \c_fp_prec_or_int [11190](#), [12174](#)
- \c_fp_prec_paren_int [11190](#), [11847](#), [12091](#)
- \c_fp_prec_plus_int [558](#), [11190](#), [12171](#), [12172](#)
- \c_fp_prec_quest_int [11190](#), [12249](#), [12253](#), [12263](#)
- \c_fp_prec_times_int [11190](#), [12169](#), [12170](#), [12180](#), [12184](#)
- \c_fp_rand_eight_int [15719](#), [15738](#), [15741](#)
- \c_fp_rand_four_int [15719](#), [15744](#), [15747](#), [15760](#), [15763](#)

__fp_rand_myriads:n
 703, 705, [15724](#), [15779](#), [15849](#)
 __fp_rand_myriads_get:w [15724](#)
 __fp_rand_myriads_last: [15724](#)
 __fp_rand_myriads_last:w [15724](#)
 __fp_rand_myriads_loop:nn ... [15724](#)
 __fp_rand_o: [15768](#)
 __fp_rand_o:Nw
 11948, [15710](#), [15715](#), [15768](#)
 __fp_rand_o:w [15768](#)
 \c_fp_rand_size_int
 777, 777, [15719](#), [15825](#),
 15836, [18297](#), [18298](#), [18309](#), [18318](#)
 __fp_rand_uniform: [15719](#),
 15734, [15756](#), [15823](#), [15839](#), [15857](#)
 __fp_randint_badarg:w [15780](#)
 __fp_randint_e:w [15780](#)
 __fp_randint_e:wnn [15780](#)
 __fp_randint_e:wwNnn [15780](#)
 __fp_randint_e:wwwNnn ... 705, [15780](#)
 __fp_randint_narrow_e:nnnn .. [15780](#)
 __fp_randint_o:Nw [11950](#), [15715](#), [15780](#)
 __fp_randint_wide_e:nnnn [15780](#)
 __fp_randint_wide_e:wnnn [15780](#)
 __fp_reverse_args:Nww 694,
 695, [10456](#), [15173](#), [15259](#), [15371](#), [15437](#)
 __fp_round:NNN 549, 549, 551, 620,
 635, [10933](#), [11003](#), [12945](#), [12956](#),
 13198, [13210](#), [13350](#), [13361](#), [13545](#)
 __fp_round:Nwn . 11053, [11106](#), [15632](#)
 __fp_round:Nww . 11054, [11075](#), [11106](#)
 __fp_round:Nwww [11055](#), [11069](#)
 __fp_round_digit:Nw 539,
 619, 620, 635, [10626](#), [11017](#), [12959](#),
 13102, [13201](#), [13213](#), [13364](#), [13550](#)
 __fp_round_name_from_cs:N
 11065, [11091](#), [11095](#), [11111](#)
 __fp_round_neg:NNN 549,
 616, 616, [11028](#), [13064](#), [13079](#), [13097](#)
 __fp_round_no_arg_o:Nw 11052, [11059](#)
 __fp_round_normal:NnnwNnn .. [11106](#)
 __fp_round_normal:NNwNnn [11106](#)
 __fp_round_normal:NwNNnw [11106](#)
 __fp_round_normal_end:wwNnn . [11106](#)
 __fp_round_o:Nw
 11048, [11971](#), [11973](#), [11975](#), [11990](#)
 __fp_round_pack:Nw [11106](#)
 __fp_round_return_one:
 550, [10933](#), [10939](#),
 10949, [10957](#), [10961](#), [10970](#), [10974](#),
 10983, [10990](#), [10994](#), [11032](#), [11042](#)
 __fp_round_s:NNNw
 549, 577, [11001](#), [11647](#), [11665](#)
 __fp_round_special:NwwNnn ... [11106](#)
 __fp_round_special_aux:Nw ... [11106](#)
 __fp_round_to_nearest:NNN
 553, 553, [10933](#), [11037](#),
 11061, [11071](#), [11990](#), [11994](#), [15632](#)
 __fp_round_to_nearest_neg:NNN [11028](#)
 __fp_round_to_nearest_ninf:NNN .
 553, [10933](#), [11046](#)
 __fp_round_to_nearest_ninf_-
 neg:NNN [11028](#)
 __fp_round_to_nearest_pinf:NNN .
 553, [10933](#), [11038](#)
 __fp_round_to_nearest_pinf_-
 neg:NNN [11028](#)
 __fp_round_to_nearest_zero:NNN .
 553, [10933](#)
 __fp_round_to_nearest_zero_-
 neg:NNN [11028](#)
 __fp_round_to_ninf:NNN
 10933, [11036](#), [11099](#), [11973](#), [11985](#)
 __fp_round_to_ninf_neg:NNN .. [11028](#)
 __fp_round_to_pinf:NNN
 10933, [11028](#), [11101](#), [11975](#), [11979](#)
 __fp_round_to_pinf_neg:NNN .. [11028](#)
 __fp_round_to_zero:NNN
 10933, [11097](#), [11971](#), [11982](#)
 __fp_round_to_zero_neg:NNN .. [11028](#)
 __fp_rrrot:www [10457](#), [15304](#)
 __fp_sanitize:Nw
 610, 613, 618, 621, 629, 684, 692,
 692, [10511](#), [11167](#), [11185](#), [12888](#),
 12982, [13154](#), [13233](#), [13379](#), [14031](#),
 14267, [14523](#), [15135](#), [15179](#), [15316](#)
 __fp_sanitize:wN
 568, 572, [10511](#), [11364](#), [11833](#)
 __fp_sanitize_zero:w [10511](#)
 __fp_sec_o:w [14725](#)
 __fp_set_sign_o:w [11826](#), [13554](#)
 __fp_sin_o:w 582, 693, [14680](#)
 __fp_sin_series_aux_o:NNwww . [15087](#)
 __fp_sin_series_o:NNwww .. 673,
 685, [14686](#), [14701](#), [14716](#), [14731](#), [15087](#)
 __fp_small_int:wTF ... [10688](#), [11108](#)
 __fp_small_int_normal:NnwTF ...
 542, [10688](#)
 __fp_small_int_test:NnnwNnw ...
 10708, [10715](#)
 __fp_small_int_test:NnnwNTF ...
 542, [10688](#)
 __fp_small_int_true:wTF . 542, [10688](#)
 __fp_sqrt_auxi_o:NNNNwnn
 13401, [13409](#)
 __fp_sqrt_auxii_o:NnnnnnnnN 631,
 633, 633, [13411](#), [13415](#), [13495](#), [13507](#)

__fp_sqrt_auxiii_o:wnnnnnnnn ...
 13412, 13450, 13496
 __fp_sqrt_auxiv_o:NNNNNw 13450
 __fp_sqrt_auxix_o:wnwnw 13484
 __fp_sqrt_auxv_o:NNNNNw 13450
 __fp_sqrt_auxvi_o:NNNNNw 13450
 __fp_sqrt_auxvii_o:NNNNNw ... 13450
 __fp_sqrt_auxviii_o:nnnnnnnn ...
 13472, 13474, 13476, 13482, 13484
 __fp_sqrt_auxx_o:Nnnnnnnnn
 13480, 13498
 __fp_sqrt_auxxi_o:wwnnN 13498
 __fp_sqrt_auxxii_o:nnnnnnnnw ...
 13508, 13512
 __fp_sqrt_auxxiii_o:w 13512
 __fp_sqrt_auxxiv_o:wnnnnnnnN ...
 13524, 13527, 13535, 13537
 __fp_sqrt_Newton_o:wwn
 631, 13386, 13397, 13398
 __fp_sqrt_npos_auxi_o:wwnnN . 13377
 __fp_sqrt_npos_auxii_o:wNNNNNNN
 13377
 __fp_sqrt_npos_o:w ... 13374, 13377
 __fp_sqrt_o:w 13367
 __fp_step:NnnnnN 12609
 __fp_step:wwnN 12609
 __fp_sub_back_far_o:NnnwnnnnN ..
 615, 12991, 13037
 __fp_sub_back_near_after:wNNNNw
 12997, 13075
 __fp_sub_back_near_o:nnnnnnnnN .
 614, 12987, 12997
 __fp_sub_back_near_pack:NNNNNNw
 12997, 13077
 __fp_sub_back_not_far_o:wwwNNN .
 13052, 13072
 __fp_sub_back_quite_far_ii:NN 13056
 __fp_sub_back_quite_far_o:wwNN .
 13050, 13056
 __fp_sub_back_shift:wnnnn
 614, 13009, 13013
 __fp_sub_back_shift_ii:ww ... 13013
 __fp_sub_back_shift_iii:NNNNNNNNw
 13013
 __fp_sub_back_shift_iv:nnnnw . 13013
 __fp_sub_back_very_far_ii_-
 o:nnNwNN 13084
 __fp_sub_back_very_far_o:wwwNN
 13051, 13084
 __fp_sub_eq_o:Nnwnw 12962
 __fp_sub_npos_i_o:Nnwnw
 613, 12967, 12976, 12980
 __fp_sub_npos_ii_o:Nnwnw 12962
 __fp_sub_npos_o:Nnwnw
 613, 12882, 12962
 __fp_tan_o:w 14740
 __fp_tan_series_aux_o:Nnwww . 15141
 __fp_tan_series_o:NNwww
 675, 675, 14747, 14762, 15141
 __fp_ternary:NwN . 598, 12251, 12737
 __fp_ternary_auxi:NwN .. 598, 12737
 __fp_ternary_auxii:NwN
 598, 12267, 12737
 __fp_ternary_break_point:n .. 12737
 __fp_ternary_loop:Nw 12737
 __fp_ternary_loop_break:w ... 12737
 __fp_ternary_map_break: 12737
 __fp_tmp:w 539, 590,
 10620, 10630, 10631, 10632, 10633,
 10634, 10635, 10636, 10637, 10638,
 10639, 10640, 10641, 10642, 10643,
 10644, 10645, 11220, 11232, 11233,
 11234, 11235, 11236, 11237, 11238,
 11809, 11826, 11827, 11877, 11882,
 11883, 11884, 11885, 11886, 11887,
 11888, 11896, 11897, 11898, 11899,
 11900, 11901, 11902, 11903, 11904,
 11905, 11906, 12150, 12168, 12169,
 12170, 12171, 12172, 12173, 12174
 __fp_to_decimal_dispatch:w
 697, 699,
 700, 12655, 15514, 15518, 15521, 15631
 __fp_to_decimal_huge:wnnnn .. 15521
 __fp_to_decimal_large:Nnnw .. 15521
 __fp_to_decimal_normal:wnnnnn ..
 15521, 15603
 __fp_to_int_dispatch:w
 15622, 15626, 15629
 __fp_to_scientific_dispatch:w ..
 696, 698, 699, 15470, 15474, 15477
 __fp_to_scientific_normal:wnnnnn
 15477
 __fp_to_scientific_normal:wNw 15477
 __fp_to_tl_dispatch:w
 699, 15582, 15586, 15589, 15699
 __fp_to_tl_normal:nnnnn 15589
 __fp_to_tl_scientific:wnnnnn . 15589
 __fp_to_tl_scientific:wNw ... 15589
 \c__fp_trailing_shift_int
 10586, 13580,
 13602, 13675, 14575, 15033, 15070
 __fp_trap_division_by_zero_-
 set:N 10817
 __fp_trap_division_by_zero_set_-
 error: 10817
 __fp_trap_division_by_zero_set_-
 flag: 10817

| | | | |
|--|--|-------------------------------|--|
| _fp_trap_division_by_zero_set:-none: | 10817 | _fp_trim_zeros:w | 15461 , 15565 , 15574 , 15616 |
| _fp_trap_invalid_operation-set:N | 10783 | _fp_trim_zeros_dot:w | 15461 |
| _fp_trap_invalid_operation-set_error: | 10783 | _fp_trim_zeros_end:w | 15461 |
| _fp_trap_invalid_operation-set_flag: | 10783 | _fp_trim_zeros_loop:w | 15461 |
| _fp_trap_invalid_operation-set_none: | 10783 | _fp_type_from_scan:N | 566 , 10581 , 11208 , 11266 |
| _fp_trap_overflow_set:N | 10843 | _fp_type_from_scan:w | 11208 |
| _fp_trap_overflow_set:NnNn . | 10843 | _fp_underflow:w | 534 , 545 , 546 , 547 , 10518 , 10874 |
| _fp_trap_overflow_set_error: . | 10843 | _fp_use_i:ww | 645 , 693 , 10458 , 13791 , 15390 |
| _fp_trap_overflow_set_flag: . | 10843 | _fp_use_i:www | 10458 |
| _fp_trap_overflow_set_none: . | 10843 | _fp_use_i_until_s:nw | 683 , 10453 , 10505 , 10743 , 12134 , 14830 , 15028 , 15034 , 15065 |
| _fp_trap_underflow_set:N ... | 10843 | _fp_use_ii_until_s:nnw | 10453 , 10503 |
| _fp_trap_underflow_set_error: . | 10843 | _fp_use_none_stop_f:n | 10450 , 13955 , 13956 , 13957 |
| _fp_trap_underflow_set_flag: . | 10843 | _fp_use_none_until_s:w | 10453 , 13403 , 14631 , 15385 , 15388 |
| _fp_trap_underflow_set_none: . | 10843 | _fp_use_s:n | 10451 |
| _fp_trig:NNNNNwn . | 14686 , 14701 , 14716 , 14731 , 14746 , 14761 , 14778 | _fp_use_s:nn | 10451 |
| _fp_trig_inverse_two_pi: | 681 , 14839 , 15008 | _fp_zero_fp:N . | 10484 , 10858 , 11173 |
| _fp_trig_large:ww ... | 14786 , 15003 | _fp_l_o:ww | 598 , 12724 |
| _fp_trig_large_auxi:wwwww . | 15003 | _fp | 12727 , 12734 |
| _fp_trig_large_auxii:ww | 15003 | \futurelet | 374 |
| _fp_trig_large_auxiii:wNNNNNNNN | 15003 | | |
| _fp_trig_large_auxiv:wN | 15003 | | |
| _fp_trig_large_auxix:Nw | 15046 | | |
| _fp_trig_large_auxv:www | 15019 , 15026 | | |
| _fp_trig_large_auxvi:wnnnnnnnn | 15026 | | |
| _fp_trig_large_auxvii:w | 15029 , 15046 | | |
| _fp_trig_large_auxviii:w ... | 15046 | | |
| _fp_trig_large_auxviii:ww | 15048 , 15052 | | |
| _fp_trig_large_auxx:wNNNNN . | 15046 | | |
| _fp_trig_large_auxxi:w | 15046 | | |
| _fp_trig_large_pack:NNNNNw ... | 15026 , 15075 | | |
| _fp_trig_small:ww | 676 , 683 , 14788 , 14792 , 14798 , 15085 | | |
| _fp_trigd_large:ww .. | 14786 , 14800 | | |
| _fp_trigd_large_auxi:nnnnwNNNN | 14800 | | |
| _fp_trigd_large_auxii:wNw .. | 14800 | | |
| _fp_trigd_large_auxiii:www . | 14800 | | |
| _fp_trigd_small:ww | 677 , 14788 , 14794 , 14837 | | |

| G | |
|---------------------------------|---|
| \gdef | 375 |
| \GetIdInfo | 6 , 6 , 6 |
| \gleaders | 884 |
| \global | 166 , 167 , 181 , 182 , 183 , 194 , 195 , 196 , 197 , 198 , 199 , 200 , 201 , 202 , 205 , 272 , 376 |
| \globaldefs | 377 |
| \glueexpr | 631 |
| \glueshrink | 632 |
| \glueshrinkorder | 633 |
| \gluestretch | 634 |
| \gluestretchorder | 635 |
| \gluetomu | 636 |
| group commands: | |
| \group_align_safe_begin/end: .. | 399 |
| \group_align_safe_begin: | 94 , 94 , 94 , 308 , 312 , 392 , 2834 , 3146 , 5734 , 5908 , 7031 , 7049 , 18615 , 19406 |
| \group_align_safe_end: | 94 , 94 , 94 , 308 , 312 , 2857 , 3172 , 5782 , 5783 , 5908 , 7013 , 7023 , 7028 , 7046 , 18636 |
| \group_begin: | 9 , 9 , 9 , 753 , 1321 , 2035 , 2042 , 2466 , 2699 , 2705 , 2733 , 2933 , 3423 , 3446 , 3596 , 3619 , 3942 , 3961 , 4291 , 6577 , 6583 , |

- 6644, 6717, 6741, 6759, 6783, 6873,
6891, 7107, 7602, 7623, 7686, 7932,
8186, 8353, 8785, 8820, 9535, 11284,
11836, 12037, 12087, 12103, 12141,
12203, 12217, 12245, 12724, 16022,
16472, 17400, 17599, 17713, 17753,
17770, 17787, 17801, 17819, 18564,
18589, 19165, 19174, 19196, 19346,
19368, 19653, 20499, 20633, 20916
- `\c_group_begin_token`
..... 45, 109, 322, 423,
3279, 3314, 6741, 6765, 16499, 16544
- `\group_end:` 9,
9, 9, 9, 350, 753, 1321, 2038, 2042,
2469, 2701, 2713, 2791, 2937, 2940,
3441, 3466, 3601, 3624, 3968, 4073,
4301, 4306, 6585, 6592, 6720, 6738,
6758, 6762, 6790, 6890, 6936, 7172,
7609, 7634, 7791, 7977, 8202, 8387,
8789, 8844, 9586, 11299, 11866,
12083, 12102, 12140, 12175, 12216,
12244, 12277, 12735, 16041, 16281,
16478, 17404, 17604, 17723, 17762,
17779, 17793, 17811, 17833, 18571,
18594, 19188, 19195, 19361, 19367,
19392, 19677, 20504, 20641, 20921
- `\c_group_end_token` 109,
423, 6741, 6770, 16504, 16505, 16552
- `\group_insert_after:N` 9, 9, 9, 1326,
19832, 19864, 19878, 20225, 20615
- groups commands:
 `.groups:n` 162, 10033
- ## H
- `\H` 19395
- `\halign` 378
- `\hangafter` 379
- `\hangindent` 380
- `\hbadness` 381
- `\hbox` 382
- hbox commands:
 `\hbox:n` 195,
195, 16486, 17191, 17246, 17628, 17866
- `\hbox_gset:Nn` 196, 16487
- `\hbox_gset:Nw` 196, 16498
- `\hbox_gset_end:` 196, 16498
- `\hbox_gset_to_wd:Nnn` 196, 16492
- `\hbox_overlap_left:n` 196, 196, 16509
- `\hbox_overlap_right:n`
..... 196, 196, 16509,
19899, 19938, 20177, 20209, 20599
- `\hbox_set:Nn` 196, 196, 196,
16487, 16644, 16752, 16977, 17048,
17336, 17597, 17624, 17625, 17711,
17751, 17768, 17785, 17799, 17817,
17839, 17875, 17879, 17887, 17895,
17904, 17913, 17925, 17933, 17941,
17947, 17960, 18007, 18021, 20123
- `\hbox_set:Nw` .. 196, 196, 16498, 16694
- `\hbox_set_end:` 196, 196, 16498, 16698
- `\hbox_set_to_wd:Nnn` . 196, 196, 16492
- `\hbox_to_wd:nn` 196, 196, 16506, 17857
- `\hbox_to_zero:n`
..... 196, 196, 16506, 16510, 16512
- `\hbox_unpack:N`
..... 196, 196, 16513, 16981, 17128
- `\hbox_unpack_clear:N` 196, 196, 16513
- hcoffin commands:
 `\hcoffin_set:Nn` 200,
200, 16640, 17188, 17200, 17243, 17283
- `\hcoffin_set:Nw` 200, 200, 16690
- `\hcoffin_set_end:` ... 200, 200, 16690
- `\hfil` 383
- `\hfill` 384
- `\hfilneg` 385
- `\hfuzz` 386
- `\hjcode` 880
- `\hoffset` 387
- `\holdinginserts` 388
- `\hpack` 881
- `\hrule` 389
- `\hsize` 390
- `\hskip` 391
- `\hss` 392
- `\ht` 393
- hundred commands:
 `\c_one_hundred` 78, 5389
- `\hyphenation` 394
- `\hyphenationbounds` 882
- `\hyphenationmin` 883
- `\hyphenchar` 395
- `\hyphenpenalty` 396
- ## I
- `\I` 195
- `\i` 198, 19390
- `\if` 397
- if commands:
 `\if:w` 21, 105, 105, 105,
267, 268, 268, 268, 295, 1294, 1594,
1944, 1945, 2392, 2395, 2396, 2450,
2453, 3988, 5259, 6983, 9612, 9616,
9634, 11445, 11449, 11471, 11564,
11596, 11615, 11681, 11695, 11712,
11732, 12207, 12222, 12234, 14526
- `\if_bool:N` . 94, 94, 94, 5614, 5646, 7500
- `\if_box_empty:N` 199, 199, 16418, 16434

`\if_case:w` 79,
 79, 333, 333, 335, 374, 540, 620,
 664, 664, 671, 1860, 3691, 3765,
 4609, 5150, 5183, 6732, 8917, 10513,
 10664, 10690, 11050, 11079, 12312,
 12356, 12824, 12964, 13039, 13064,
 13116, 13561, 13800, 14020, 14047,
 14204, 14239, 14345, 14361, 14377,
 14393, 14409, 14425, 14450, 14502,
 14624, 14647, 14682, 14697, 14712,
 14727, 14742, 14757, 15197, 15214,
 15267, 15350, 15365, 15417, 15430,
 15480, 15524, 15592, 15782, 15808
`\if_catcode:w`
 21, 313, 322, 323, 432, 1294, 2969,
 3270, 3312, 3324, 3341, 6765, 6770,
 6775, 6780, 6787, 6794, 6799, 6804,
 6809, 6814, 6819, 6829, 6858, 7065,
 7070, 11242, 11405, 11722, 11769,
 12041, 12194, 12313, 19659, 19660
`\if_charcode:w` 21, 105, 321, 322, 337,
 432, 1294, 3251, 3305, 3848, 6834, 7067
`\if_cs_exist:N`
 21, 1308, 1625, 1653, 6866, 6992
`\if_cs_exist:w` 21, 1308, 1334, 1634,
 1662, 1848, 5424, 5449, 5458, 5494
`\if_dim:w`
 157, 157, 9091, 9168, 9180, 9205
`\if_eof:w` 142, 142, 8615, 8622
`\if_false:` 21, 90,
 308, 312, 320, 353, 365, 399, 1294,
 2852, 2853, 2954, 2958, 3219, 3224,
 3235, 3325, 3337, 3352, 3360, 4242,
 4245, 4380, 4385, 4796, 5909, 6675,
 8896, 8935, 8939, 8946, 8954, 9190
`\if_hbox:N` 198, 198, 16418, 16422
`\if_int_compare:w` 21, 79,
 79, 365, 365, 366, 366, 1324, 3495,
 3503, 3518, 3523, 3678, 3730, 3731,
 3737, 3749, 3765, 3991, 4015, 4026,
 4027, 4034, 4046, 4609, 4642, 4712,
 4776, 4829, 4831, 4833, 4835, 4837,
 4839, 4841, 4844, 5909, 5911, 6612,
 6615, 6616, 6623, 6624, 6625, 6626,
 6631, 6632, 6850, 6974, 8903, 9401,
 10514, 10515, 10608, 10672, 10706,
 10720, 10938, 10948, 10956, 10969,
 10982, 10989, 11010, 11022, 11031,
 11041, 11135, 11140, 11224, 11254,
 11369, 11371, 11404, 11409, 11462,
 11482, 11509, 11523, 11558, 11585,
 11613, 11629, 11645, 11663, 11722,
 11742, 11758, 11771, 11785, 11818,
 11844, 11869, 12042, 12052, 12054,
 12091, 12107, 12112, 12154, 12180,
 12249, 12263, 12301, 12491, 12521,
 12524, 12535, 12538, 12543, 12544,
 12547, 12550, 12696, 12770, 12828,
 12849, 12891, 12986, 13040, 13041,
 13044, 13047, 13117, 13126, 13327,
 13400, 13453, 13457, 13461, 13479,
 13514, 13515, 13516, 13517, 13518,
 13544, 13802, 13805, 13899, 13991,
 14033, 14049, 14175, 14209, 14270,
 14277, 14281, 14318, 14495, 14497,
 14508, 14526, 14549, 14581, 14584,
 14627, 14659, 14663, 14785, 14829,
 15218, 15256, 15265, 15300, 15384,
 15387, 15575, 15738, 15744, 15760,
 15798, 15958, 16028, 16096, 16104,
 16115, 16118, 16136, 16171, 16181,
 16191, 19110, 19111, 19116, 19608,
 19618, 19627, 19637, 19638, 19644
`\if_int_odd:w` 79, 79, 686, 4609, 4709,
 4881, 4889, 5395, 6622, 6630, 6650,
 10960, 11007, 11019, 12352, 13100,
 13382, 14662, 14673, 15055, 15094,
 15104, 15147, 15171, 15341, 19658
`\if_meaning:w` 21, 310, 310, 322, 444,
 605, 1294, 1457, 1472, 1490, 1540,
 1545, 1554, 1622, 1640, 1650, 1668,
 1878, 1889, 2005, 2050, 2097, 2098,
 2335, 2363, 2372, 2631, 2885, 2897,
 2910, 2921, 2936, 3164, 3228, 3296,
 3605, 3628, 3785, 3823, 3979, 4061,
 4278, 4296, 4315, 4323, 4623, 4658,
 4663, 4664, 4811, 5514, 5520, 5546,
 5559, 5567, 5691, 5757, 5776, 6049,
 6064, 6086, 6102, 6824, 6863, 6901,
 6904, 6966, 7058, 7099, 7404, 7442,
 9149, 9198, 9551, 9575, 9592, 9603,
 10502, 10516, 10528, 10538, 10548,
 10682, 10697, 10717, 10719, 10866,
 10937, 10947, 10959, 10972, 10973,
 10992, 10993, 11007, 11008, 11019,
 11020, 11078, 11117, 11152, 11155,
 11171, 11178, 11243, 11246, 11306,
 11307, 11308, 11422, 11535, 11541,
 11770, 11978, 11981, 11984, 12071,
 12133, 12353, 12371, 12483, 12510,
 12511, 12512, 12513, 12514, 12515,
 12677, 12689, 12690, 12718, 12729,
 12739, 12799, 12808, 12825, 12860,
 12865, 12879, 12925, 12932, 13008,
 13020, 13120, 13123, 13134, 13185,
 13258, 13326, 13329, 13336, 13369,
 13370, 13373, 13773, 13784, 13964,
 13974, 14017, 14116, 14195, 14244,

- 14258, 14447, 14459, 14472, 14475,
 14478, 14481, 14507, 14608, 14612,
 15097, 15150, 15212, 15213, 15215,
 15216, 15236, 15253, 15319, 15417,
 15479, 15523, 15591, 15643, 15648,
 15797, 15969, 15970, 18413, 19661
 \if_mode_horizontal: . 21, 1304, 5903
 \if_mode_inner: 21, 1304, 5905
 \if_mode_math: 21, 1304, 5907
 \if_mode_vertical: . . . 21, 1304, 5901
 \if_predicate:w
 88, 90, 94, 94, 5614, 5726
 \if_true: 21, 90, 310, 310, 1294
 \if_vbox:N 198, 198, 16418, 16424
 \ifabsdim 951
 \ifabsnum 952
 \ifcase 398
 \ifcat 399
 \ifcsname 637
 \ifdbbox 1124
 \ifddir 1125
 \ifdefined 158, 638
 \ifdim 400
 \ifeof 401
 \iffalse 402
 \iffontchar 639
 \ifhbox 403
 \ifhmode 404
 \ifincsname 780
 \ifinner 405
 \ifmdir 1126
 \ifmmode 406
 \ifnum . . . 45, 60, 89, 95, 100, 164, 179, 407
 \ifodd 408
 \ifpdfabsdim 742
 \ifpdfabsnum 743
 \ifpdfprimitive 744
 \ifprimitive 856
 \iftbox 1127
 \iftdir 1128
 \iftrue 409
 \ifvbox 410
 \ifvmode 411
 \ifvoid 412
 \ifx 14, 21,
 39, 43, 49, 90, 92, 98, 123, 145, 146, 413
 \ifybox 1129
 \ifydir 1130
 \ignoreligaturesinfont 953
 \ignorespaces 414
 \IJ 19381
 \ij 19381
 \immediate 415
 in 188
 \indent 416
 inf 187
 inherit commands:
 .inherit:n 162, 10035
 \inhibitglue 1131
 \inhibitxspcode 1132
 \initcatcodetable 885
 initial commands:
 .initial:n 163, 10037
 \input 50, 159, 160, 417
 \inputlineno 418
 \insert 419
 \insertht 954
 \insertpenalties 420
 int commands:
 \c_eight 78, 5370
 \c_eleven 78, 5370
 \c_fifteen 78, 5370
 \c_five 78, 5370
 \c_four 78, 5370
 \c_fourteen 78, 5370
 \int_abs:n 68, 68, 4616
 \int_add:Nn 70, 70, 4742, 9002
 \int_case:nn
 72, 72, 374, 4850, 5013, 5019
 \int_case:nnn 17541
 \int_case:nnTF 23, 72, 72, 4527, 4850,
 4855, 4860, 6346, 17541, 19002, 19057
 \int_compare:nNnTF . 70, 71, 71, 72,
 72, 73, 73, 2707, 2737, 2751, 2755,
 2780, 3372, 3379, 3657, 3659, 3668,
 3907, 4440, 4447, 4690, 4696, 4842,
 4874, 4925, 4933, 4942, 4948, 4960,
 4963, 4974, 5009, 5097, 5103, 5109,
 5129, 5283, 5302, 5304, 5346, 5810,
 6385, 6387, 6392, 6401, 6421, 8362,
 8650, 8740, 9320, 12421, 15446,
 15550, 15552, 15836, 15945, 17500,
 17975, 18289, 18296, 18297, 18298,
 18318, 18433, 18742, 18744, 18747,
 18767, 18892, 18924, 18927, 18961,
 18964, 18971, 18984, 19099, 19496
 \int_compare:nTF 71, 71, 73, 73, 73,
 73, 80, 176, 493, 4789, 4897, 4905,
 4914, 4920, 8596, 8620, 8719, 15601
 \int_compare_p:n 71, 71, 4789
 \int_compare_p:nNn 21, 71, 71, 4842,
 17475, 18949, 19044, 19045, 19046,
 19091, 19522, 19523, 19547, 19548
 \int_const:Nn
 . . . 69, 69, 2316, 4688, 5312, 5313,
 5314, 5315, 5316, 5317, 5318, 5319,
 5320, 5321, 5322, 5323, 5324, 5325,
 5370, 5371, 5372, 5373, 5374, 5375,

- 5376, 5377, 5378, 5379, 5380, 5381,
 5382, 5383, 5384, 5385, 5386, 5387,
 5388, 5389, 5390, 5391, 5392, 5393,
 5411, 6653, 6672, 8516, 8645, 8646,
 10478, 10479, 10480, 10481, 10482,
 10483, 10586, 10587, 10588, 10590,
 10591, 10592, 10595, 10596, 10597,
 10932, 11190, 11191, 11192, 11193,
 11194, 11195, 11196, 11197, 11198,
 11199, 11200, 11201, 11202, 11203,
 11204, 15721, 15722, 15723, 16011,
 17440, 17442, 17444, 17445, 17446
 \int_decr:N 70, 70,
 4754, 16124, 16125, 16126, 16169,
 16170, 16179, 16180, 16189, 16190
 \int_div_round:nn 68, 68, 4648
 \int_div_truncate:nn
 69, 69, 69, 4648, 5024, 5122, 5142,
 17443, 19121, 19127, 19129, 19139
 \int_do_until:nn 73, 73, 4895
 \int_do_until:nNnn 72, 72, 4923
 \int_do_while:nn 73, 73, 4895
 \int_do_while:nNnn 72, 72, 4923
 \int_eval:n 14, 26, 26, 68, 68, 68, 68,
 68, 69, 70, 71, 71, 72, 79, 80, 135,
 277, 377, 466, 557, 599, 622, 622,
 624, 784, 1886, 1902, 3071, 3076,
 3365, 3373, 3381, 3728, 3775, 3812,
 4433, 4441, 4449, 4515, 4614, 4853,
 4858, 4863, 4868, 4978, 5006, 5092,
 5094, 5224, 5234, 5269, 5280, 5286,
 5297, 5328, 5365, 6319, 6328, 6379,
 6389, 6403, 6410, 6425, 8582, 8705,
 8947, 9327, 10491, 12400, 16306,
 16307, 16454, 16464, 18301, 18320,
 18327, 18397, 18436, 18540, 19106,
 19139, 19141, 19599, 19603, 19635
 \int_from_alpha:n 76, 76, 5267
 \int_from_base:nn
 77, 77, 5284, 5307, 5309, 5311
 \int_from_bin:n .. 76, 76, 5306, 17542
 \int_from_binary:n 17542
 \int_from_hex:n .. 77, 77, 5306, 17543
 \int_from_hexadecimal:n 17543
 \int_from_oct:n .. 77, 77, 5306, 17544
 \int_from_octal:n 17544
 \int_from_roman:n 77, 77, 5326
 \int_gadd:Nn 70, 4742
 \int_gdecr:N 70, 3033, 4492,
 4754, 5004, 6280, 7459, 12669, 18261
 \int_gincr:N 70, 3028, 4484,
 4754, 4983, 4990, 6274, 7454, 12664,
 18252, 20520, 20649, 20705, 20750
 .int_gset:N 163, 10045
 \int_gset:Nn
 ... 70, 4693, 4699, 4766, 7653, 20634
 \int_gset_eq:NN 69, 4732, 20642
 \int_gsub:Nn 70, 4742
 \int_gzero:N 69, 4722, 4729
 \int_gzero_new:N 69, 4726
 \int_if_even:nTF 72, 4879
 \int_if_even_p:n 72, 4879
 \int_if_exist:N
 . 70, 70, 4727, 4729, 4738, 5340, 5344
 \int_if_exist_p:N 70, 70, 4738
 \int_if_odd:nTF .. 72, 72, 4879, 13888
 \int_if_odd_p:n 72, 72, 4879
 \int_incr:N 70,
 70, 4754, 9843, 16032, 16134, 16135
 \int_log:N 77, 77, 5366
 \int_log:n 77, 77, 5368
 \int_max:nn
 69, 69, 702, 4616, 13749, 14809
 \int_min:nn 69, 69, 4616
 \int_mod:nn 69, 69, 4648, 5014, 5113,
 5133, 8364, 15832, 17441, 18314, 19141
 \int_new:N
 69, 69, 69, 4680, 4692, 4698, 4727,
 4729, 5403, 5404, 5405, 5406, 5913,
 8763, 8766, 8768, 8780, 9662, 15926,
 15927, 15928, 15929, 15930, 15931,
 15932, 15933, 15934, 15935, 15936,
 19824, 20569, 20652, 20653, 20731
 \int_rand:nn
 . 213, 213, 703, 781, 17976, 17981,
 18279, 18333, 18427, 18486, 19580
 .int_set:N 163, 10045
 \int_set:Nn
 .. 70, 70, 2036, 2708, 2765, 4766,
 8638, 8640, 8746, 8748, 8764, 8774,
 8786, 8821, 8827, 8841, 9847, 15939,
 15941, 15943, 15966, 15967, 15982,
 15990, 15991, 16003, 16004, 16015,
 16016, 16017, 16034, 16037, 16463,
 16465, 16473, 16474, 16475, 16476
 \int_set_eq:NN
 ... 69, 69, 4732, 15983, 16025, 20630
 \int_show:N 77, 77, 5362
 \int_show:n 77, 77, 379, 466, 5364, 5369
 \int_step_function:nnnN
 74, 74, 370,
 602, 4951, 5003, 6716, 6721, 6724, 8662
 \int_step_inline:nnnn
 74, 74, 603, 4981, 8525, 8670
 \int_step_variable:nnnN 74, 74, 4981
 \int_sub:Nn 70, 70, 4742, 9010
 \int_to_Alpha:n 75, 75, 76, 5027
 \int_to_alpha:n 75, 75, 75, 75, 76, 5027

- \int_to_arabic:n [74](#), [74](#), [5006](#)
- \int_to_Base:n [76](#)
- \int_to_base:n [76](#)
- \int_to_Base:nn ... [76](#), [77](#), [5091](#), [5218](#)
- \int_to_base:nn
... [76](#), [76](#), [77](#), [5091](#), [5214](#), [5216](#), [5220](#)
- \int_to_bin:n [75](#), [75](#), [76](#), [76](#), [5213](#), [17545](#)
- \int_to_binary:n [17545](#)
- \int_to_Hex:n [76](#), [76](#), [77](#), [5213](#)
- \int_to_hex:n [76](#), [76](#), [76](#), [77](#), [5213](#), [17546](#)
- \int_to_hexadecimal:n [17546](#)
- \int_to_oct:n . [76](#), [76](#), [77](#), [5213](#), [17547](#)
- \int_to_octal:n [17547](#)
- \int_to_Roman:n [76](#), [76](#), [77](#), [5221](#)
- \int_to_roman:n .. [76](#), [76](#), [76](#), [77](#), [5221](#)
- \int_to_symbols:nnn
..... [75](#), [75](#), [75](#), [5007](#), [5029](#), [5061](#)
- \int_until_do:nn [73](#), [73](#), [4895](#)
- \int_until_do:nNnn [73](#), [73](#), [4923](#)
- \int_use:N
... [68](#), [70](#), [70](#), [70](#), [551](#), [556](#), [3029](#),
[3031](#), [4485](#), [4491](#), [4771](#), [4986](#), [4993](#),
[6275](#), [6277](#), [7453](#), [7461](#), [7569](#), [8061](#),
[8640](#), [8742](#), [9848](#), [10497](#), [12665](#),
[12668](#), [15489](#), [18254](#), [20522](#), [20552](#),
[20708](#), [20714](#), [20721](#), [20753](#), [20761](#)
- \int_while_do:nn [73](#), [73](#), [4895](#)
- \int_while_do:nNnn [73](#), [73](#), [4923](#)
- \int_zero:N
..... [69](#), [69](#), [4722](#), [4727](#), [8865](#), [9840](#)
- int_zero:N [69](#)
- \int_zero_new:N [69](#), [69](#), [4726](#)
- \c_max_int [78](#), [5392](#), [16451](#), [16457](#)
- \c_nine [78](#), [5370](#)
- \c_one [78](#), [381](#), [4755](#), [4757](#), [5370](#)
- \c_seven [78](#), [5370](#)
- \c_six [78](#), [5370](#)
- \c_sixteen [78](#), [5370](#)
- \c_ten [78](#), [5370](#)
- \c_thirteen [78](#), [5370](#)
- \c_three [78](#), [5370](#)
- \g_tmpa_int [78](#), [5403](#)
- \l_tmpa_int [2](#), [78](#), [5403](#)
- \g_tmpb_int [78](#), [5403](#)
- \l_tmpb_int [2](#), [78](#), [5403](#)
- \c_twelve [78](#), [5370](#)
- \c_two [78](#), [5370](#)
- \c_zero [78](#),
[260](#), [268](#), [268](#), [268](#), [268](#), [784](#), [1343](#),
[1597](#), [1599](#), [4690](#), [4722](#), [4723](#), [4776](#),
[4784](#), [4960](#), [4963](#), [5370](#), [5909](#), [5911](#)
- int internal commands:
 __int_abs:N [4616](#)
 __int_case:nnTF [4850](#)
- __int_case:nw [4850](#)
- __int_case_end:nw [4850](#)
- __int_compare:nnN [366](#), [4789](#)
- __int_compare:NNw ... [365](#), [366](#), [4789](#)
- __int_compare:Nw . [365](#), [365](#), [366](#), [4789](#)
- __int_compare:w [365](#), [4789](#)
- __int_compare_!=:NNw [4789](#)
- __int_compare_<:NNw [4789](#)
- __int_compare_<=:NNw [4789](#)
- __int_compare_=:NNw [4789](#)
- __int_compare_==:NNw [4789](#)
- __int_compare_>:NNw [4789](#)
- __int_compare_>=:NNw [4789](#)
- __int_compare_end=:NNw .. [366](#), [4789](#)
- __int_constdef:Nw [4688](#)
- __int_div_truncate:NwNw [4648](#)
- __int_eval:w [80](#), [80](#),
[360](#), [360](#), [365](#), [550](#), [551](#), [552](#), [552](#),
[565](#), [579](#), [610](#), [618](#), [619](#), [619](#), [622](#),
[626](#), [664](#), [1860](#), [3651](#), [3664](#), [3682](#),
[3687](#), [3710](#), [3711](#), [3723](#), [3759](#), [4609](#),
[4615](#), [4619](#), [4627](#), [4628](#), [4635](#), [4636](#),
[4650](#), [4652](#), [4653](#), [4670](#), [4673](#), [4674](#),
[4675](#), [4704](#), [4743](#), [4745](#), [4767](#), [4792](#),
[4826](#), [4844](#), [4881](#), [4889](#), [4954](#), [4955](#),
[4956](#), [5150](#), [5177](#), [5183](#), [5210](#), [5427](#),
[5459](#), [5857](#), [6464](#), [6465](#), [6468](#), [6537](#),
[6538](#), [6541](#), [6546](#), [6547](#), [6550](#), [6555](#),
[6556](#), [6559](#), [6564](#), [6565](#), [6568](#), [6600](#),
[6601](#), [6607](#), [8899](#), [8908](#), [8932](#), [8944](#),
[10510](#), [10608](#), [10611](#), [10731](#), [11006](#),
[11010](#), [11022](#), [11023](#), [11051](#), [11134](#),
[11138](#), [11177](#), [11365](#), [11370](#), [11408](#),
[11497](#), [11508](#), [11557](#), [11588](#), [11594](#),
[11595](#), [11641](#), [11651](#), [11653](#), [11669](#),
[11671](#), [11694](#), [11696](#), [11834](#), [12053](#),
[12316](#), [12494](#), [12890](#), [12898](#), [12919](#),
[12921](#), [12942](#), [12944](#), [12953](#), [12955](#),
[12984](#), [12990](#), [13000](#), [13002](#), [13076](#),
[13078](#), [13094](#), [13096](#), [13100](#), [13116](#),
[13156](#), [13164](#), [13166](#), [13168](#), [13170](#),
[13172](#), [13174](#), [13176](#), [13195](#), [13197](#),
[13207](#), [13209](#), [13235](#), [13238](#), [13246](#),
[13248](#), [13268](#), [13271](#), [13274](#), [13277](#),
[13285](#), [13288](#), [13291](#), [13294](#), [13301](#),
[13303](#), [13309](#), [13317](#), [13319](#), [13321](#),
[13327](#), [13347](#), [13349](#), [13358](#), [13360](#),
[13381](#), [13402](#), [13406](#), [13418](#), [13421](#),
[13424](#), [13427](#), [13430](#), [13433](#), [13436](#),
[13439](#), [13443](#), [13455](#), [13459](#), [13463](#),
[13466](#), [13487](#), [13489](#), [13491](#), [13501](#),
[13540](#), [13542](#), [13551](#), [13573](#), [13578](#),
[13580](#), [13587](#), [13590](#), [13593](#), [13596](#),
[13599](#), [13602](#), [13611](#), [13623](#), [13631](#),

| | |
|--|--|
| 13633, 13643, 13645, 13652, 13661, | |
| 13663, 13666, 13669, 13672, 13675, | |
| 13688, 13690, 13698, 13700, 13708, | |
| 13710, 13719, 13722, 13725, 13732, | |
| 13747, 13765, 13768, 13824, 13838, | |
| 13840, 13846, 13859, 13861, 13863, | |
| 13887, 13903, 13910, 13911, 13934, | |
| 13950, 13954, 13999, 14001, 14039, | |
| 14050, 14069, 14071, 14073, 14086, | |
| 14099, 14104, 14106, 14112, 14129, | |
| 14130, 14131, 14132, 14133, 14134, | |
| 14139, 14141, 14143, 14145, 14147, | |
| 14151, 14153, 14155, 14157, 14159, | |
| 14161, 14183, 14191, 14269, 14273, | |
| 14326, 14540, 14561, 14563, 14566, | |
| 14569, 14572, 14575, 14591, 14617, | |
| 14627, 14643, 14670, 14671, 14672, | |
| 14783, 14815, 14824, 15006, 15007, | |
| 15030, 15040, 15049, 15067, 15076, | |
| 15083, 15094, 15104, 15137, 15147, | |
| 15172, 15181, 15198, 15235, 15252, | |
| 15254, 15266, 15267, 15307, 15318, | |
| 15329, 15387, 15508, 15612, 15647, | |
| 15740, 15746, 15762, 15783, 16099, | |
| 18284, 18285, 19612, 19620, 19629 | |
| __int_eval_end: 80, 80, 80, 80, 1860, | |
| 4609, 4615, 4619, 4654, 4670, 4676, | |
| 4704, 4743, 4745, 4767, 4844, 4881, | |
| 4889, 5150, 5177, 5183, 5210, 5857, | |
| 6464, 6465, 6468, 6537, 6538, 6541, | |
| 6546, 6547, 6550, 6555, 6556, 6559, | |
| 6564, 6565, 6568, 10510, 10734, | |
| 11051, 11148, 11152, 12316, 12494, | |
| 12811, 13100, 13135, 13323, 13633, | |
| 13768, 14591, 14643, 14816, 14825, | |
| 15094, 15104, 15147, 15172, 15198, | |
| 15267, 15741, 15747, 15763, 15783 | |
| __int_from_alph:N 376, 5267 | |
| __int_from_alph:nN 376, 5267 | |
| __int_from_base:N 377, 5284 | |
| __int_from_base:nnN 377, 5284 | |
| __int_from_roman:NN 5326 | |
| \c__int_from_roman_C_int 5312 | |
| \c__int_from_roman_c_int 5312 | |
| \c__int_from_roman_D_int 5312 | |
| \c__int_from_roman_d_int 5312 | |
| __int_from_roman_error:w 5326 | |
| \c__int_from_roman_I_int 5312 | |
| \c__int_from_roman_i_int 5312 | |
| \c__int_from_roman_L_int 5312 | |
| \c__int_from_roman_l_int 5312 | |
| \c__int_from_roman_M_int 5312 | |
| \c__int_from_roman_m_int 5312 | |
| \c__int_from_roman_V_int 5312 | |
| \c__int_from_roman_v_int 5312 | |
| \c__int_from_roman_X_int 5312 | |
| \c__int_from_roman_x_int 5312 | |
| __int_maxmin:wwN 4616 | |
| __int_mod:ww 4648 | |
| __int_pass_signs:wn 376, 5257, 5271, 5288 | |
| __int_pass_signs_end:wn 5257 | |
| __int_rand:ww 18279 | |
| __int_rand_narrow:n 18279 | |
| __int_rand_narrow:nn 777, 18300, 18306, 18319 | |
| __int_rand_narrow:nnn 18279 | |
| __int_rand_narrow:nnnn .. 777, 18279 | |
| __int_show:nN 5362 | |
| __int_step:NnnnN 4951 | |
| __int_step:NNnnnn 4981 | |
| __int_step:wwwN 4951 | |
| __int_to_Base:nn 5091 | |
| __int_to_base:nn 5091 | |
| __int_to_Base:nnN 5091 | |
| __int_to_base:nnN 5091 | |
| __int_to_Base:nnnN 5091 | |
| __int_to_base:nnnN 5091 | |
| __int_to_Letter:n 5091 | |
| __int_to_letter:n 5091 | |
| __int_to_roman:N 5221 | |
| __int_to_roman:w 79, 79, 365, 375, 1324, | |
| 4609, 4802, 5224, 5234, 6711, 6734, | |
| 10611, 11569, 11601, 14066, 14335 | |
| __int_to_Roman_aux:N 5233, 5236, 5239 | |
| __int_to_Roman_c:w 5221 | |
| __int_to_roman_c:w 5221 | |
| __int_to_Roman_d:w 5221 | |
| __int_to_roman_d:w 5221 | |
| __int_to_Roman_i:w 5221 | |
| __int_to_roman_i:w 5221 | |
| __int_to_Roman_l:w 5221 | |
| __int_to_roman_l:w 5221 | |
| __int_to_Roman_m:w 5221 | |
| __int_to_roman_m:w 5221 | |
| __int_to_Roman_Q:w 5221 | |
| __int_to_roman_Q:w 5221 | |
| __int_to_Roman_v:w 5221 | |
| __int_to_roman_v:w 5221 | |
| __int_to_Roman_x:w 5221 | |
| __int_to_roman_x:w 5221 | |
| __int_to_symbols:nnnn 5007 | |
| __int_value:w 80, 80, 80, 365, 393, 493, | |
| 534, 540, 542, 552, 558, 558, 558, | |
| 558, 558, 558, 565, 567, 572, 572, | |
| 579, 600, 608, 616, 624, 685, 698, | |

- 1599, 3651, 3652, 3664, 3682, 3687,
 3709, 3710, 3711, 3723, 3759, 4609,
 4615, 4618, 4619, 4626, 4627, 4628,
 4634, 4635, 4636, 4650, 4652, 4653,
 4670, 4673, 4674, 4675, 4792, 4796,
 4826, 4954, 4955, 4956, 5177, 5210,
 5427, 5459, 5469, 5767, 5770, 5857,
 6600, 6601, 6607, 8899, 8908, 9177,
 10570, 10571, 10572, 10573, 10574,
 10625, 10696, 10719, 10731, 11006,
 11120, 11134, 11136, 11138, 11141,
 11177, 11311, 11342, 11343, 11356,
 11365, 11492, 11497, 11499, 11508,
 11512, 11549, 11557, 11560, 11566,
 11577, 11588, 11594, 11595, 11598,
 11641, 11651, 11653, 11669, 11671,
 11694, 11708, 11786, 11788, 11834,
 11913, 12411, 12509, 12835, 12836,
 12837, 12839, 12890, 12893, 12896,
 12919, 12921, 12942, 12944, 12953,
 12955, 12959, 12977, 12984, 12990,
 13000, 13002, 13016, 13024, 13032,
 13076, 13078, 13094, 13096, 13099,
 13102, 13156, 13164, 13166, 13168,
 13170, 13172, 13174, 13176, 13195,
 13197, 13201, 13207, 13209, 13213,
 13235, 13238, 13246, 13248, 13251,
 13252, 13253, 13254, 13268, 13271,
 13274, 13277, 13285, 13288, 13291,
 13294, 13301, 13303, 13309, 13317,
 13319, 13321, 13347, 13349, 13358,
 13360, 13364, 13381, 13402, 13406,
 13418, 13421, 13424, 13427, 13430,
 13433, 13436, 13439, 13443, 13455,
 13459, 13463, 13466, 13487, 13489,
 13491, 13501, 13525, 13528, 13540,
 13542, 13548, 13551, 13560, 13573,
 13578, 13580, 13587, 13590, 13593,
 13596, 13599, 13602, 13611, 13623,
 13631, 13633, 13643, 13645, 13652,
 13661, 13663, 13666, 13669, 13672,
 13675, 13688, 13690, 13698, 13700,
 13708, 13710, 13719, 13722, 13725,
 13732, 13747, 13765, 13768, 13824,
 13838, 13840, 13846, 13859, 13861,
 13863, 13887, 13903, 13910, 13911,
 13954, 13956, 13957, 13958, 13999,
 14001, 14032, 14039, 14046, 14067,
 14069, 14071, 14073, 14086, 14090,
 14091, 14092, 14093, 14094, 14099,
 14104, 14106, 14112, 14129, 14130,
 14131, 14132, 14133, 14134, 14139,
 14141, 14143, 14145, 14147, 14151,
 14153, 14155, 14157, 14159, 14161,
 14183, 14191, 14207, 14212, 14216,
 14269, 14273, 14326, 14338, 14525,
 14561, 14563, 14566, 14569, 14572,
 14575, 14582, 14585, 14587, 14591,
 14613, 14615, 14643, 14670, 14671,
 14672, 14783, 14815, 14824, 15006,
 15007, 15008, 15030, 15040, 15049,
 15067, 15076, 15083, 15093, 15137,
 15146, 15181, 15235, 15252, 15307,
 15318, 15329, 15508, 15574, 15612,
 15639, 15647, 15649, 15651, 15734,
 15740, 15746, 15756, 15762, 15823,
 15832, 15839, 15857, 16099, 16599,
 16631, 16632, 16633, 16635, 16766,
 16775, 16777, 16782, 16783, 16784,
 16785, 16789, 16790, 16791, 16792,
 16817, 16823, 16825, 16827, 16829,
 16834, 16839, 16844, 16851, 16858,
 16989, 17019, 17020, 17059, 17078,
 17084, 17254, 17363, 17997, 17999,
 18022, 18024, 18049, 18089, 18116,
 18124, 18150, 18152, 18156, 18158,
 18187, 18201, 18208, 18284, 18285,
 18427, 18436, 19612, 19620, 19629
- \interactionmode 640
 \interlinepenalties 641
 \interlinepenalty 421
- ior commands:
- \ior_close:N
 . 137, 137, 138, 138, 8401, 8573, 8594
- \ior_get:NN
 138, 138, 139, 142, 8632, 18247
- \ior_get_str:NN 9079, 17574
- \ior_if_eof:N 776
- \ior_if_eof:NnTF 139,
 139, 8398, 8419, 8616, 18259, 18266
- \ior_if_eof_p:N 139, 139, 8616
- \ior_list_streams:
 138, 138, 777, 8606, 18274
- \ior_log_streams: ... 213, 213, 18273
- \ior_map_break: 212, 212, 18242, 18260
- \ior_map_break:n 212, 212, 18242
- \ior_map_inline:Nn .. 211, 211, 18246
- \ior_new:N 137, 137, 8540, 8643
- \ior_open:Nn 137, 137, 8542
- \ior_open:NnTF
 137, 137, 8552, 8554, 8555
- \ior_str_get:NN ... 139, 139, 139,
 8634, 9084, 9085, 9086, 17574, 18249
- \ior_str_map_inline:Nn 212, 212, 18246
- \c_term_ior
 ... 142, 8516, 8540, 8596, 8602, 8620
- ior internal commands:
- \l_ior_internal_tl 18246

- __ior_list_streams:Nn ... [8606](#), [8731](#)
- __ior_map_inline:NNn ... [18246](#)
- __ior_map_inline:NNNn ... [18246](#)
- __ior_map_inline_loop:NNN ... [18246](#)
- __ior_new:N ... [474](#), [8567](#), [8581](#)
- __ior_open:Nn ... [142](#), [142](#), [8397](#), [8418](#), [8550](#), [8563](#), [8571](#)
- __ior_open_aux:Nn ... [8542](#)
- __ior_open_aux:NnTF ... [8552](#)
- __ior_open_stream:Nn ... [8571](#)
- \l_ior_stream_tl ... [8522](#), [8574](#), [8582](#), [8590](#)
- \g_ior_streams_prop ... [8523](#), [8591](#), [8599](#), [8607](#)
- \g_ior_streams_seq ... [8517](#), [8574](#), [8600](#), [8601](#)
- ior commands:
 - \ior_char:N .. [140](#), [140](#), [8069](#), [8071](#), [8072](#), [8356](#), [8761](#), [14444](#), [16294](#), [16297](#), [16322](#), [16323](#), [16330](#), [16331](#)
 - \ior_close:N [137](#), [138](#), [138](#), [8696](#), [8717](#)
 - \ior_indent:n ... [141](#), [141](#), [141](#), [483](#), [484](#), [8010](#), [8800](#), [8830](#), [8838](#), [10393](#), [10898](#), [10910](#)
 - \l_ior_line_count_int ... [141](#), [141](#), [141](#), [484](#), [8763](#), [8842](#), [8867](#)
 - \ior_list_streams: ... [138](#), [138](#), [777](#), [8729](#), [18277](#)
 - \ior_log:n .. [22](#), [139](#), [139](#), [272](#), [466](#), [1692](#), [1703](#), [7642](#), [7643](#), [7644](#), [7788](#), [8254](#), [8289](#), [8504](#), [8505](#), [8506](#), [8756](#)
 - \ior_log_streams: ... [213](#), [213](#), [18276](#)
 - \ior_new:N ... [137](#), [137](#), [8685](#)
 - \ior_newline: ... [139](#), [140](#), [140](#), [140](#), [140](#), [143](#), [449](#), [466](#), [480](#), [7598](#), [7614](#), [7616](#), [8760](#), [8839](#)
 - \ior_now:Nn [139](#), [139](#), [139](#), [139](#), [139](#), [140](#), [140](#), [8750](#), [8756](#), [8757](#), [8758](#), [8759](#)
 - \ior_open:Nn ... [137](#), [137](#), [8691](#)
 - \ior_shipout:Nn ... [139](#), [139](#), [139](#), [140](#), [140](#), [8735](#)
 - \ior_shipout_x:Nn ... [139](#), [140](#), [140](#), [140](#), [480](#), [8732](#)
 - \ior_term:n ... [139](#), [139](#), [1692](#), [7612](#), [7648](#), [7649](#), [7650](#), [8254](#), [8756](#)
 - \ior_wrap:nnnN ... [56](#), [131](#), [132](#), [132](#), [139](#), [140](#), [141](#), [141](#), [141](#), [141](#), [281](#), [464](#), [466](#), [466](#), [484](#), [7590](#), [7591](#), [7643](#), [7649](#), [7786](#), [8237](#), [8281](#), [8803](#), [8815](#), [8818](#)
 - \c_log_ior ... [142](#), [477](#), [8645](#), [8719](#), [8756](#), [8757](#)
 - \c_term_ior ... [142](#), [477](#), [477](#), [8645](#), [8662](#), [8685](#), [8719](#), [8725](#), [8758](#), [8759](#)
- ior internal commands:
 - __ior_indent:n ... [483](#), [8800](#), [8830](#)
 - __ior_indent_error:n [483](#), [8800](#), [8838](#)
 - \l_ior_indent_int ... [8779](#), [8865](#), [8883](#), [8994](#), [9002](#), [9010](#)
 - \l_ior_indent_tl ... [8779](#), [8866](#), [8882](#), [8993](#), [9003](#), [9011](#), [9012](#)
 - \l_ior_line_break_bool ... [8783](#), [8861](#), [8988](#), [9001](#), [9009](#), [9017](#), [9019](#), [9024](#), [9026](#)
 - \l_ior_line_part_tl ... [485](#), [485](#), [487](#), [487](#), [8781](#), [8863](#), [8875](#), [8896](#), [8953](#), [8956](#), [8987](#), [9000](#), [9008](#), [9031](#)
 - \l_ior_line_target_int ... [489](#), [8766](#), [8841](#), [8989](#), [8994](#), [9020](#)
 - \l_ior_line_tl ... [8781](#), [8862](#), [8879](#), [8968](#), [8984](#), [9000](#), [9008](#), [9030](#), [9031](#), [9036](#), [9038](#)
 - __ior_list_streams:Nn ... [8729](#)
 - __ior_new:N ... [8687](#), [8704](#)
 - \l_ior_newline_tl ... [8765](#), [8839](#), [8840](#), [8842](#), [9035](#)
 - \l_ior_one_indent_int ... [8767](#), [9002](#), [9010](#)
 - \l_ior_one_indent_tl [482](#), [8767](#), [9003](#)
 - __ior_open:Nn ... [8691](#)
 - __ior_open_stream:Nn ... [8691](#)
 - __ior_set_indent:n ... [482](#), [8767](#)
 - \l_ior_stream_tl ... [8667](#), [8697](#), [8705](#), [8713](#)
 - \g_ior_streams_prop ... [8668](#), [8714](#), [8722](#), [8730](#)
 - \g_ior_streams_seq ... [8656](#), [8697](#), [8723](#), [8724](#)
 - __ior_tmp:w ... [487](#), [8869](#), [8893](#), [8949](#), [8981](#), [9040](#), [9046](#)
 - __ior_unindent:w ... [482](#), [8767](#), [9012](#)
 - __ior_with:Nnn [143](#), [143](#), [449](#), [466](#), [480](#), [7619](#), [7621](#), [8293](#), [8295](#), [8738](#), [8752](#)
 - __ior_with_aux:nNnn ... [8738](#)
 - __ior_wrap_break:w ... [8935](#), [8949](#)
 - __ior_wrap_break_end:w ... [487](#), [8949](#)
 - __ior_wrap_break_first:w ... [8949](#)
 - __ior_wrap_break_loop:w ... [8949](#)
 - __ior_wrap_break_none:w ... [8949](#)
 - __ior_wrap_chunk:nw ... [8867](#), [8869](#), [9004](#), [9013](#), [9020](#)
 - __ior_wrap_do: ... [8843](#), [8850](#)
 - __ior_wrap_end: ... [9015](#)
 - __ior_wrap_end:n ... [9022](#)
 - __ior_wrap_end_chunk:w ... [485](#), [8887](#), [8894](#), [8985](#)
 - \c_ior_wrap_end_marker_tl [8785](#), [8855](#)
 - __ior_wrap_indent: ... [8998](#)

- __iow_wrap_indent:n 8998
 - \c__iow_wrap_indent_marker_tl ...
..... 8785, 8808
 - __iow_wrap_line:nw
..... 485, 488, 8881, 8885, 8894, 8992
 - __iow_wrap_line_aux:Nw 8894
 - __iow_wrap_line_end:NnnnnnnN 8894
 - __iow_wrap_line_end:nw
..... 487, 8894, 8969, 8970, 8979
 - __iow_wrap_line_loop:w 8894
 - \c__iow_wrap_marker_tl
..... 482, 482, 485, 8785, 8893
 - __iow_wrap_newline: 9015
 - __iow_wrap_newline:n 9015
 - \c__iow_wrap_newline_marker_tl ..
..... 8785, 8828
 - __iow_wrap_next:nw . 8869, 8947, 8989
 - __iow_wrap_next_line:w .. 8941, 8982
 - __iow_wrap_set:Nn 8818
 - __iow_wrap_start:w 8850
 - __iow_wrap_store_do:n
..... 8940, 9018, 9025, 9028
 - \l__iow_wrap_tl ... 484, 484, 484,
489, 489, 8784, 8833, 8836, 8845,
8852, 8854, 8857, 8864, 9032, 9034
 - __iow_wrap_trim:N
..... 489, 8970, 9018, 9025, 9040
 - __iow_wrap_trim:w 9040
 - __iow_wrap_unindent: 8998
 - __iow_wrap_unindent:n 9006
 - \c__iow_wrap_unindent_marker_tl .
..... 8785, 8810
- J**
- \J 197
 - \j 19391
 - \jcharwidowpenalty 1133
 - \jfam 1134
 - \jfont 1135
 - \jis 1136
 - job commands:
 - \c_job_name_tl 17539
 - \jobname 422
- K**
- \k 19395
 - \kanjiskip 1137
 - \kansuji 1138
 - \kansujichar 1139
 - \kcatcode 1140
 - \kchar 1158
 - \kchardef 1159
 - \kern 423
- kernel internal commands:
- \l__kernel_expl_bool
..... 7, 235, 238, 253, 267
 - __kernel_primitive:NN
..... 237, 275, 284,
285, 286, 287, 288, 289, 290, 291,
292, 293, 294, 295, 296, 297, 298,
299, 300, 301, 302, 303, 304, 305,
306, 307, 308, 309, 310, 311, 312,
313, 314, 315, 316, 317, 318, 319,
320, 321, 322, 323, 324, 325, 326,
327, 328, 329, 330, 331, 332, 333,
334, 335, 336, 337, 338, 339, 340,
341, 342, 343, 344, 345, 346, 347,
348, 349, 350, 351, 352, 353, 354,
355, 356, 357, 358, 359, 360, 361,
362, 363, 364, 365, 366, 367, 368,
369, 370, 371, 372, 373, 374, 375,
376, 377, 378, 379, 380, 381, 382,
383, 384, 385, 386, 387, 388, 389,
390, 391, 392, 393, 394, 395, 396,
397, 398, 399, 400, 401, 402, 403,
404, 405, 406, 407, 408, 409, 410,
411, 412, 413, 414, 415, 416, 417,
418, 419, 420, 421, 422, 423, 424,
425, 426, 427, 428, 429, 430, 431,
432, 433, 434, 435, 436, 437, 438,
439, 440, 441, 442, 443, 444, 445,
446, 447, 448, 449, 450, 451, 452,
453, 454, 455, 456, 457, 458, 459,
460, 461, 462, 463, 464, 465, 466,
467, 468, 469, 470, 471, 472, 473,
474, 475, 476, 477, 478, 479, 480,
481, 482, 483, 484, 485, 486, 487,
488, 489, 490, 491, 492, 493, 494,
495, 496, 497, 498, 499, 500, 501,
502, 503, 504, 505, 506, 507, 508,
509, 510, 511, 512, 513, 514, 515,
516, 517, 518, 519, 520, 521, 522,
523, 524, 525, 526, 527, 528, 529,
530, 531, 532, 533, 534, 535, 536,
537, 538, 539, 540, 541, 542, 543,
544, 545, 546, 547, 548, 549, 550,
551, 552, 553, 554, 555, 556, 557,
558, 559, 560, 561, 562, 563, 564,
565, 566, 567, 568, 569, 570, 571,
572, 573, 574, 575, 576, 577, 578,
579, 580, 581, 582, 583, 584, 585,
586, 587, 588, 589, 590, 591, 592,
593, 594, 595, 596, 597, 598, 599,
600, 601, 602, 603, 604, 605, 606,
607, 608, 609, 610, 611, 612, 613,
614, 615, 616, 617, 618, 619, 620,
621, 622, 623, 624, 625, 626, 627,

628, 629, 630, 631, 632, 633, 634,
 635, 636, 637, 638, 639, 640, 641,
 642, 643, 644, 645, 646, 647, 648,
 649, 650, 651, 652, 653, 654, 655,
 656, 657, 658, 659, 660, 661, 662,
 663, 664, 665, 666, 667, 668, 669,
 670, 671, 672, 673, 674, 675, 676,
 677, 678, 679, 680, 681, 682, 683,
 684, 685, 686, 687, 688, 689, 690,
 691, 692, 693, 694, 695, 696, 697,
 698, 699, 700, 701, 702, 703, 704,
 705, 706, 707, 708, 709, 710, 711,
 712, 713, 714, 715, 716, 717, 718,
 719, 720, 721, 722, 723, 724, 725,
 726, 727, 728, 729, 730, 731, 732,
 733, 734, 735, 736, 737, 738, 739,
 740, 741, 742, 743, 744, 745, 746,
 747, 748, 749, 750, 751, 752, 753,
 754, 755, 756, 757, 758, 759, 760,
 761, 762, 763, 764, 765, 766, 767,
 768, 769, 770, 771, 772, 773, 774,
 775, 776, 777, 778, 779, 780, 781,
 782, 783, 784, 785, 786, 787, 788,
 793, 805, 806, 807, 808, 809, 810,
 811, 812, 813, 814, 815, 816, 817,
 818, 819, 820, 821, 822, 823, 824,
 825, 826, 827, 828, 829, 830, 831,
 832, 833, 834, 835, 836, 837, 838,
 839, 840, 841, 842, 843, 844, 845,
 846, 847, 848, 849, 850, 851, 852,
 853, 854, 855, 856, 857, 858, 859,
 860, 861, 862, 863, 864, 865, 866,
 867, 868, 869, 870, 871, 872, 873,
 874, 875, 876, 877, 878, 879, 880,
 881, 882, 883, 884, 885, 886, 887,
 888, 889, 890, 891, 892, 893, 894,
 895, 896, 897, 898, 899, 900, 901,
 902, 903, 904, 905, 906, 907, 908,
 909, 910, 911, 912, 913, 914, 915,
 916, 917, 918, 919, 920, 921, 922,
 923, 924, 925, 926, 927, 928, 929,
 930, 931, 932, 933, 934, 935, 936,
 937, 938, 939, 940, 941, 942, 943,
 944, 945, 946, 947, 948, 949, 950,
 951, 952, 953, 954, 955, 956, 957,
 958, 959, 960, 961, 962, 963, 964,
 965, 966, 967, 968, 969, 970, 971,
 972, 973, 974, 975, 976, 977, 978,
 979, 980, 981, 982, 983, 984, 985,
 986, 987, 988, 989, 990, 991, 992,
 993, 994, 995, 996, 997, 998, 999,
 1000, 1001, 1002, 1003, 1004, 1005,
 1006, 1007, 1008, 1009, 1010, 1011,
 1012, 1013, 1014, 1015, 1016, 1017,
 1018, 1019, 1020, 1021, 1022, 1023,
 1024, 1025, 1026, 1027, 1028, 1029,
 1030, 1031, 1032, 1033, 1034, 1035,
 1036, 1037, 1038, 1039, 1040, 1041,
 1042, 1043, 1044, 1045, 1046, 1047,
 1048, 1049, 1050, 1051, 1052, 1053,
 1054, 1055, 1056, 1057, 1058, 1059,
 1060, 1061, 1062, 1063, 1064, 1065,
 1066, 1067, 1068, 1069, 1070, 1071,
 1072, 1073, 1074, 1075, 1076, 1077,
 1078, 1079, 1080, 1081, 1082, 1083,
 1084, 1085, 1086, 1087, 1088, 1089,
 1090, 1091, 1092, 1093, 1094, 1095,
 1096, 1097, 1098, 1099, 1100, 1101,
 1102, 1103, 1104, 1105, 1106, 1107,
 1108, 1109, 1110, 1111, 1112, 1113,
 1114, 1115, 1116, 1117, 1118, 1119,
 1120, 1121, 1122, 1123, 1124, 1125,
 1126, 1127, 1128, 1129, 1130, 1131,
 1132, 1133, 1134, 1135, 1136, 1137,
 1138, 1139, 1140, 1141, 1142, 1143,
 1144, 1145, 1146, 1147, 1148, 1149,
 1150, 1151, 1152, 1153, 1154, 1155,
 1156, 1157, 1158, 1159, 1160, 1161
 __kernel_register_log:N
 23, 23, 2029, 5366,
 9340, 9341, 9437, 9438, 9505, 9506
 __kernel_register_show:N
 23, 23, 23, 281,
 325, 2020, 2030, 5362, 9336, 9433, 9501
 __kernel_register_show_aux:n . 2020
 __kernel_register_show_aux:nN ..
 2021, 2022
 keys commands:
 \l_keys_choice_int
 161, 163, 165, 165, 165,
 165, 166, 9662, 9840, 9843, 9847, 9848
 \l_keys_choice_tl 161,
 163, 165, 165, 165, 166, 9662, 9846
 \keys_define:nn
 160, 160, 160, 9677, 10391
 \keys_if_choice_exist:nnnTF
 169, 169, 10342
 \keys_if_choice_exist_p:nnn
 169, 169, 10342
 \keys_if_exist:nnnTF
 169, 169, 527, 10335, 10352
 \keys_if_exist_p:nn . 169, 169, 10335
 \l_keys_key_tl ... 167, 167, 9665,
 9782, 9798, 10184, 10270, 10272, 10305
 \keys_log:nn 169, 169, 10376
 \l_keys_path_tl 167, 167,
 9669, 9705, 9724, 9733, 9742, 9746,
 9760, 9775, 9777, 9779, 9791, 9793,

- 9795, 9810, 9813, 9817, 9825, 9826,
- 9827, 9830, 9844, 9865, 9870, 9879,
- 9883, 9890, 9894, 9898, 9905, 9912,
- 9923, 9929, 9933, 9948, 9957, 9965,
- 10000, 10166, 10173, 10196, 10199,
- 10238, 10242, 10250, 10252, 10253,
- 10264, 10267, 10287, 10312, 10313
- \keys_set:nn
 159, 163, 167, 167, 167, 167, 168,
 9900, 9905, 10097, 10121, 10141, 10150
- \keys_set_filter:nnn 169, 169, 10125
- \keys_set_filter:nnnN
 169, 169, 169, 10125
- \keys_set_groups:nnn 169, 169, 10125
- \keys_set_known:nn .. 168, 168, 10107
- \keys_set_known:nnN
 168, 168, 168, 168, 522, 10107
- \keys_show:nn
 169, 169, 169, 528, 10350, 10377
- \l_keys_value_tl 167, 167,
 9675, 9948, 10241, 10244, 10246,
 10254, 10274, 10283, 10297, 10307
- keys internal commands:
- __keys_bool_set:Nn
 9771, 9974, 9976, 9978, 9980
- __keys_bool_set_inverse:Nn
 9787, 9982, 9984, 9986, 9988
- __keys_check_groups: . 10200, 10208
- __keys_choice_find:n .. 9804, 10310
- __keys_choice_make:
 9774, 9790, 9803, 9834, 9990
- __keys_choice_make:N 9803
- __keys_choice_make_aux:N 9803
- __keys_choices_make:nn
 9833, 9992, 9994, 9996, 9998
- __keys_choices_make:Nnn 9833
- __keys_cmd_set:nn ... 9775, 9777,
 9779, 9791, 9793, 9795, 9826, 9827,
 9844, 9853, 9898, 9905, 9965, 10000
- \c__keys_code_root_tl
 ... 9655, 9855, 9857, 9894, 10250,
 10253, 10270, 10272, 10280, 10282,
 10294, 10296, 10338, 10346, 10357
- \c__keys_default_root_tl
 9655, 9865, 9870, 10238, 10242
- __keys_default_set:n 9784,
 9800, 9860, 10010, 10012, 10014, 10016
- __keys_define:n 9682, 9686
- __keys_define:nn 9682, 9686
- __keys_define:nnn 9677
- __keys_define_aux:nn 9686
- __keys_define_code:n ... 9700, 9750
- __keys_define_code:w 9750
- __keys_execute:
 ... 10177, 10204, 10226, 10230, 10248
- __keys_execute:nn 10248, 10312, 10313
- __keys_execute_unknown: 10248
- \l_keys_filtered_bool 9671,
 10139, 10148, 10203, 10224, 10229
- __keys_find_key_module:w 10154
- \l_keys_groups_clist
 . 9664, 9876, 9877, 9884, 10198, 10213
- \c__keys_groups_root_tl
 9655, 9879, 9883, 10196, 10199
- __keys_groups_set:n ... 9874, 10034
- __keys_inherit:n 9887, 10036
- \c__keys_inherit_root_tl
 9655, 9890, 10264, 10267
- __keys_initialise:n
 ... 9892, 10038, 10040, 10042, 10044
- __keys_meta_make:n 9896, 10054
- __keys_meta_make:nn ... 9896, 10056
- \l_keys_module_tl
 ... 9666, 9678, 9681, 9683, 9726,
 9727, 9733, 9901, 10098, 10101,
 10103, 10157, 10162, 10172, 10178,
 10186, 10188, 10280, 10282, 10287
- __keys_multichoice_find:n
 9806, 10310
- __keys_multichoice_make:
 9803, 9836, 10058
- __keys_multichoices_make:nn ...
 ... 9833, 10060, 10062, 10064, 10066
- \l_keys_no_value_bool
 9667, 9688, 9693, 9752,
 9945, 9954, 10156, 10161, 10236, 10306
- \l_keys_only_known_bool
 9668, 10120, 10122, 10260
- __keys_parent:n
 9810, 9813, 9817, 10264, 10267, 10317
- __keys_parent:w 10317
- __keys_property_find:n .. 9698, 9709
- __keys_property_find:w 9709
- __keys_property_search:w
 9734, 9738, 9747
- \l_keys_property_tl 9670,
 9699, 9702, 9705, 9711, 9712, 9718,
 9730, 9743, 9755, 9756, 9759, 9763
- \c__keys_props_root_tl
 9661, 9699, 9756, 9763,
 9973, 9975, 9977, 9979, 9981, 9983,
 9985, 9987, 9989, 9991, 9993, 9995,
 9997, 9999, 10001, 10003, 10005,
 10007, 10009, 10011, 10013, 10015,
 10017, 10019, 10021, 10023, 10025,
 10027, 10029, 10031, 10033, 10035,
 10037, 10039, 10041, 10043, 10045,

- 10047, 10049, 10051, 10053, 10055,
 10057, 10059, 10061, 10063, 10065,
 10067, 10069, 10071, 10073, 10075,
 10077, 10079, 10081, 10083, 10085,
 10087, 10089, 10091, 10093, 10095
 _keys_remove_spaces:n 9681, 9711,
 9844, 10101, 10170, 10312, 10328,
 10338, 10346, 10355, 10357, 10361
 _keys_remove_spaces:w 10328
 \l_keys_selective_bool ... 9671,
 10138, 10142, 10147, 10151, 10175
 \l_keys_selective_seq
 9673, 10140, 10149, 10211
 _keys_set:n 10102, 10154
 _keys_set:nn 10102, 10154
 _keys_set:nnn 10097
 _keys_set_aux: 10154
 _keys_set_aux:nnn 10154
 _keys_set_filter:nnnnN 10125
 _keys_set_known:nnnN 10107
 _keys_set_selective: 10154
 _keys_show:N 10350
 _keys_store_unused:
 10205, 10225, 10231, 10248
 \l_keys_tmp_bool
 9676, 10210, 10217, 10222
 \c_keys_type_root_tl
 9655, 9810, 9813, 9825
 _keys_undefine: .. 9889, 9906, 10092
 \l_keys_unused_clist 522,
 9674, 10108, 10112, 10114, 10115,
 10126, 10130, 10132, 10133, 10303
 _keys_validate_cleanup:w ... 9916
 _keys_validate_forbidden: .. 9916
 _keys_validate_required: ... 9916
 \c_keys_validate_root_tl
 9655, 9923, 9929, 9933, 10252
 _keys_value_or_default:n
 10174, 10234
 _keys_value_requirement:nn ...
 9916, 10094, 10096
 _keys_variable_set:NnnN
 9962, 10002, 10004, 10006,
 10008, 10018, 10020, 10022, 10024,
 10026, 10028, 10030, 10032, 10046,
 10048, 10050, 10052, 10068, 10070,
 10072, 10074, 10076, 10078, 10080,
 10082, 10084, 10086, 10088, 10090
 keyval commands:
 \keyval_parse:NNn
 171, 171, 171, 9521, 9682, 10102
 keyval internal commands:
 _keyval_action: 9600
 _keyval_def:Nn 9602, 9618, 9643
 _keyval_def_aux:n 9643
 _keyval_def_aux:w 9643
 _keyval_empty_key: 9637, 9641
 \l_keyval_key_tl
 9518, 9602, 9603, 9614, 9622
 _keyval_loop:NNw .. 9524, 9530, 9590
 _keyval_sanitise_aux:w 9534
 _keyval_sanitise_comma: 9529, 9534
 _keyval_sanitise_comma_auxi:w 9534
 _keyval_sanitise_comma_auxii:w
 9534
 _keyval_sanitise_equals: 9528, 9534
 _keyval_sanitise_equals_auxi:w
 9534
 _keyval_sanitise_equals_-
 auxii:w 9534
 \l_keyval_sanitise_tl 9520, 9527,
 9531, 9540, 9542, 9546, 9553, 9555,
 9564, 9566, 9570, 9577, 9579, 9588
 _keyval_split:NNw 9595, 9600
 _keyval_split_tidy:w 9600
 _keyval_split_value:NNw 9600
 \l_keyval_value_tl . 9518, 9618, 9623
 \kuten 1141, 1160
- ## L
- \L 19382
 \l 19382
 l3kernel 19730
 \l3kernel.charcat 223
 l3kernel.charcat 223, 19745
 \l3kernel.strcmp 223
 l3kernel.strcmp 223, 19735
 \label 19566
 \language 424
 \lastallocatedread 3949, 3950
 \lastallocatedtoks 15997
 \lastbox 425
 \lastkern 426
 \lastlinefit 642
 \lastnamedcs 886
 \lastnodetype 643
 \lastpenalty 427
 \lastsavedboxresourceindex 955
 \lastsavedimageresourceindex 956
 \lastsavedimageresourcepages 957
 \lastskip 428
 \lastxpos 958
 \lastypos 959
 \latelua 887
 LaTeX3 error commands:
 \LaTeX3_error: 463, 463
 \lccode 166,
 181, 194, 196, 198, 200, 202, 205, 429

- `\leaders` 430
- `\left` 431
- left commands:
 - `\c_left_brace_str` 55, 3922
- `\leftghost` 936
- `\lefthyphenmin` 432
- `\leftmargin` 781
- `\leftskip` 433
- `\leqno` 434
- `\let` 1, 40, 272, 273, 435
- `\latcharcode` 888
- `\letterspacefont` 782
- `\limits` 436
- `\LineBreak` 80, 81, 82, 83, 84, 85, 86, 87, 105, 112, 113, 114, 122, 124
- `\linedir` 937
- `\linepenalty` 437
- `\lineskip` 438
- `\lineskiplimit` 439
- `\linewidth` 16665, 16714
- `\ln` 14550, 14553
- `ln` 184
- `\localbrokenpenalty` 938
- `\localinterlinepenalty` 939
- `\lcalleftbox` 940
- `\lcalrightbox` 941
- `\loccount` 8533, 8678
- `\loctoks` 15969, 15970, 15996
- `\long` 275, 440, 6926, 6930
- `\LongText` 76, 110, 134
- `\looseness` 441
- `\lower` 442
- `\lowercase` 443
- `\lpcode` 783
- lua commands:
 - `\lua_escape:n` 223, 223, 19694
 - `\lua_escape_x:n` 223, 223, 223, 19694
 - `\lua_now:n` 222, 222, 222, 19694
 - `\lua_now_x:n` 222, 222, 222, 19694
 - `\lua_shipout:n` 222, 222, 222, 19694
 - `\lua_shipout_x` 19713
 - `\lua_shipout_x:n` 222, 222, 19694
- `\luaescapestring` 889
- `\luafunction` 890
- luatex commands:
 - `\luatex_alignmark:D` 859, 1185
 - `\luatex_aligntab:D` 860, 1186
 - `\luatex_attribute:D` 861, 1187
 - `\luatex_attributedef:D` 862, 1188
 - `\luatex_begincsname:D` 863
 - `\luatex_bodydir:D` 934, 1220, 1283
 - `\luatex_boxdir:D` 935, 1221
 - `\luatex_catcodetable:D` 864, 1189
 - `\luatex_clearmarks:D` 865, 1190
 - `\luatex_crampeddisplaystyle:D` ... 866, 1191
 - `\luatex_crampedscriptstyle:D` ... 867, 1192
 - `\luatex_crampedscriptstyle:D` ... 868, 1193
 - `\luatex_crampedtextstyle:D` 869, 1194
 - `\luatex_directlua:D` 870, 1178, 1179, 3476, 6651, 6654, 6660, 8648, 19694
 - `\luatex_dviextension:D` 871
 - `\luatex_dvifedback:D` 872
 - `\luatex_dvivvariable:D` 873
 - `\luatex_etoksapp:D` 874
 - `\luatex_etokspre:D` 875
 - `\luatex_expanded:D` ... 876, 1276, 3489
 - `\luatex_firstvalidlanguage:D` .. 877
 - `\luatex_fontid:D` 878, 1195
 - `\luatex_formatname:D` 879, 1196
 - `\luatex_gleaders:D` 884, 1197
 - `\luatex_hjcode:D` 880
 - `\luatex_hpack:D` 881
 - `\luatex_hyphenationbounds:D` ... 882
 - `\luatex_hyphenationmin:D` 883
 - `\luatex_if_engine:TF` 17549, 17550, 17551
 - `\luatex_if_engine_p:` 17548
 - `\luatex_initcatcodetable:D` 885, 1198
 - `\luatex_lastnamedcs:D` 886
 - `\luatex_latelua:D` ... 887, 1199, 19696
 - `\luatex_leftghost:D` 936, 1222
 - `\luatex_latcharcode:D` 888
 - `\luatex_linedir:D` 937
 - `\luatex_localbrokenpenalty:D` ... 938, 1223
 - `\luatex_localinterlinepenalty:D` . 939, 1224
 - `\luatex_lcalleftbox:D` ... 940, 1225
 - `\luatex_lcalrightbox:D` ... 941, 1226
 - `\luatex_luaescapestring:D` 328, 889, 1200, 3487, 19699
 - `\luatex_luafunction:D` ... 890, 1201
 - `\luatex_luafunction:D` 891
 - `\luatex luatexdatestamp:D` 892
 - `\luatex luatexrevision:D` 893
 - `\luatex luatexversion:D` 894, 1239, 1258, 1344, 3472, 4710, 5396, 8650, 17454
 - `\luatex_mathdir:D` 942, 1227
 - `\luatex_mathdisplayskipmode:D` .. 895
 - `\luatex_matheqnogapstep:D` 896
 - `\luatex_mathnolimitsmode:D` 897
 - `\luatex_mathoption:D` 898
 - `\luatex_mathrulesfam:D` 899
 - `\luatex_mathscriptsmode:D` 900

| | | | |
|--------------------------------|------------------------------------|---------------------------------|----------------------|
| \latex_mathstyle:D | 901, 1202 | \latexcrampedscriptstyle | 1193 |
| \latex_mathsurroundmode:D | 902 | \latexcrampedtextstyle | 1194 |
| \latex_mathsurroundskip:D | 903 | \latexdatestamp | 892 |
| \latex_nohrule:D | 904 | \latexfontid | 1195 |
| \latex_nokerns:D | 905, 1203 | \latexformatname | 1196 |
| \latex_noligs:D | 906, 1204 | \latexglleaders | 1197 |
| \latex_nospaces:D | 907 | \latexinitcatcodetable | 1198 |
| \latex_novrule:D | 908 | \latexlualua | 1199 |
| \latex_outputbox:D | 909, 1205 | \latexleftghost | 1222 |
| \latex_pagebottomoffset:D | 910, 1228 | \latexlocalbrokenpenalty | 1223 |
| \latex_pagedir:D | 943, 1229, 1284 | \latexlocalinterlinepenalty | 1224 |
| \latex_pageleftoffset:D | 911, 1206 | \latexlocalleftbox | 1225 |
| \latex_pagerightoffset:D | 912, 1231 | \latexlocalrightbox | 1226 |
| \latex_pagetopoffset:D | 913, 1207 | \latexpluaescapestring | 1200 |
| \latex_pardir:D | 944, 1233 | \latexpluafunction | 1201 |
| \latex_pdfextension:D | | \latexmathdir | 1227 |
| | 914, 19790, 19791, | \latexmathstyle | 1202 |
| | 19797, 19798, 19803, 19804, 19809, | \latexnokerns | 1203 |
| | 19810, 19827, 19828, 19836, 19837 | \latexnoligs | 1204 |
| \latex_pdffeedback:D | 915 | \latexoutputbox | 1205 |
| \latex_pdfvariable:D | 916 | \latexpagebottomoffset | 1228 |
| \latex_postexhyphenchar:D | 917, 1208 | \latexpagedir | 1229 |
| \latex_postthyphenchar:D | 918, 1209 | \latexpageheight | 1230 |
| \latex_predisplaygapfactor:D | 919 | \latexpageleftoffset | 1206 |
| \latex_preexhyphenchar:D | 920, 1210 | \latexpagerightoffset | 1231 |
| \latex_prehyphenchar:D | 921, 1211 | \latexpagetopoffset | 1207 |
| \latex_rightghost:D | 945, 1234 | \latexpagewidth | 1232 |
| \latex_savecatcodetable:D | 922, 1212 | \latexpardir | 1233 |
| \latex_scantextokens:D | 923, 1213 | \latexpostexhyphenchar | 1208 |
| \latex_setfontid:D | 924 | \latexpostthyphenchar | 1209 |
| \latex_shapemode:D | 925 | \latexpreexhyphenchar | 1210 |
| \latex_suppressifcsnameerror:D | | \latexprehyphenchar | 1211 |
| | 926, 1214 | \latexrevision | 893 |
| \latex_suppresslongererror:D | 927, 1215 | \latexrightghost | 1234 |
| \latex_suppressmathparerror:D | | \latexsavecatcodetable | 1212 |
| | 928, 1216 | \latexscantextokens | 1213 |
| \latex_suppressoutererror:D | | \latexsuppressfontnotfounderror | |
| | 929, 1217 | | 1184, 1219 |
| \latex_textdir:D | 946, 1235 | \latexsuppressifcsnameerror | 1214 |
| \latex_toksapp:D | 930 | \latexsuppresslongererror | 1215 |
| \latex_tokspre:D | 931 | \latexsuppressmathparerror | 1216 |
| \latex_tpack:D | 932 | \latexsuppressoutererror | 1217 |
| \latex_vpack:D | 933 | \latextextdir | 1235 |
| \latexalignmark | 1185 | \latextracingfonts | 1180 |
| \latexaligntab | 1186 | \latexUchar | 1218 |
| \latexattribute | 1187 | \latexversion | 45, 100, 894 |
| \latexattributedef | 1188 | | |
| \latexbanner | 891 | M | |
| \latexbodydir | 1220 | \mag | 444 |
| \latexboxdir | 1221 | \mark | 445 |
| \latexcatcodetable | 1189 | \marks | 644 |
| \latexclearmarks | 1190 | math commands: | |
| \latexcrampeddisplaystyle | 1191 | \c_math_subscript_token | |
| \latexcrampedscriptscriptstyle | 1192 | | 109, 424, 6741, 6799 |

- `\c_math_superscript_token` 109, 424, 6741, 6794
- `\c_math_toggle_token` 109, 423, 6741, 6775
- `\mathaccent` 446
- `\mathbin` 447
- `\mathchar` 448, 6925
- `\mathchardef` 449
- `\mathchoice` 450
- `\mathclose` 451
- `\mathcode` 452
- `\mathdir` 942
- `\mathdisplayskipmode` 895
- `\matheqnogapstep` 896
- `\mathinner` 453
- `\mathnolimitsmode` 897
- `\mathop` 454
- `\mathopen` 455
- `\mathoption` 898
- `\mathord` 456
- `\mathpunct` 457
- `\mathrel` 458
- `\mathrulesfam` 899
- `\mathscriptsmode` 900
- `\mathstyle` 901
- `\mathsurround` 459
- `\mathsurroundmode` 902
- `\mathsurroundskip` 903
- `max` 184
- max commands:
 - `\c_max_char_int` 78, 5393
 - `\c_max_register_int` 78, 711, 711, 711, 1344, 4609, 8061, 15941, 15967, 16004, 16012, 16016
- max internal commands:
 - `\c_max_constdef_int` 4688
 - `\maxdeadcycles` 460
 - `\maxdepth` 461
 - `\meaning` 462
 - `\medmuskip` 463
 - `\message` 464
 - `\MessageBreak` 122
- meta commands:
 - `.meta:n` 163, 10053
 - `.meta:nn` 163, 10055
 - `\middle` 645
- `min` 184
- minus commands:
 - `\c_minus_inf_fp` 178, 187, 10473, 13145, 13227, 14022, 14775
 - `\c_minus_zero_fp` 178, 10473, 13141, 15424
- `\mkern` 465
- `mm` 188
- mode commands:
 - `\mode_if_horizontal:TF` .. 94, 94, 5902
 - `\mode_if_horizontal_p:` .. 94, 94, 5902
 - `\mode_if_inner:TF` 94, 94, 5904
 - `\mode_if_inner_p:` 94, 94, 5904
 - `\mode_if_math:TF` 94, 94, 5906
 - `\mode_if_math_p:` 94, 5906
 - `\mode_if_vertical:TF` ... 94, 94, 5900
 - `\mode_if_vertical_p:` ... 94, 94, 5900
- `\month` 466
- `\moveleft` 467
- `\moveright` 468
- msg commands:
 - `\msg_critical:nn` 128, 7736
 - `\msg_critical:nnn` 128, 7736
 - `\msg_critical:nnnn` 128, 7736
 - `\msg_critical:nnnnn` 128, 7736
 - `\msg_critical:nnnnnn` . 128, 128, 7736
 - `\msg_critical_text:n` 127, 127, 7655, 7739
 - `\msg_error:nn` 129, 7747
 - `\msg_error:nnn` 129, 7747
 - `\msg_error:nnnn` 129, 7747
 - `\msg_error:nnnnn` 129, 7747
 - `\msg_error:nnnnnn` . 129, 129, 213, 7747
 - `\msg_error_text:n` 127, 127, 7655, 7754
 - `\msg_expandable_error:nn` . 213, 18336
 - `\msg_expandable_error:nnn` 213, 18336
 - `\msg_expandable_error:nnnn` 213, 18336
 - `\msg_expandable_error:nnnnn` 213, 18336
 - `\msg_expandable_error:nnnnnn` ... 213, 213, 18336
 - `\msg_fatal:nn` 128, 7725
 - `\msg_fatal:nnn` 128, 7725
 - `\msg_fatal:nnnn` 128, 7725
 - `\msg_fatal:nnnnn` 128, 7725
 - `\msg_fatal:nnnnnn` 128, 128, 7725
 - `\msg_fatal_text:n` 127, 127, 7655, 7728
 - `\msg_gset:nnn` 126, 7512
 - `\msg_gset:nnnn` 126, 7512
 - `\msg_if_exist:nnTF` 127, 127, 7486, 7493, 7503, 7804
 - `\msg_if_exist_p:nn` ... 127, 127, 7486
 - `\msg_info:nn` 129, 7776
 - `\msg_info:nnn` 129, 7776
 - `\msg_info:nnnn` 129, 7776
 - `\msg_info:nnnnn` 129, 7776
 - `\msg_info:nnnnnn` 129, 129, 129, 7776, 7976
 - `\msg_info_text:n` . 128, 128, 7655, 7780
 - `\msg_interrupt:nnn` 131, 131, 7576, 7727, 7738, 7753

- \msg_line_context: . [127](#), [127](#), [448](#),
[1739](#), [1758](#), [2475](#), [7508](#), [7569](#), [7658](#),
[7663](#), [7668](#), [7673](#), [7678](#), [8101](#), [9856](#)
- \msg_line_number: [127](#), [127](#), [7569](#), [9649](#)
- \msg_log:n [132](#), [132](#), [7640](#), [7778](#)
- \msg_log:nn [129](#), [7784](#)
- \msg_log:nnn [129](#), [7784](#)
- \msg_log:nnnn [129](#), [7784](#)
- \msg_log:nnnnn [129](#), [7784](#)
- \msg_log:nnnnnn [129](#), [129](#), [7784](#)
- \msg_new:nnn [126](#), [7512](#), [7927](#)
- \msg_new:nnnn
. [126](#), [126](#), [446](#), [446](#), [7512](#), [7925](#)
- \msg_none:nn [130](#), [7790](#)
- \msg_none:nnn [130](#), [7790](#)
- \msg_none:nnnn [130](#), [7790](#)
- \msg_none:nnnnn [130](#), [7790](#)
- \msg_none:nnnnnn [130](#), [130](#), [7790](#)
- \msg_redirect_class:nn [130](#), [130](#), [7876](#)
- \msg_redirect_module:nnn
. [131](#), [131](#), [7876](#)
- \msg_redirect_name:nnn [131](#), [131](#), [7867](#)
- \msg_see_documentation_text:n . . .
. [128](#), [128](#), [7680](#), [7731](#), [7742](#), [7757](#)
- \msg_set:nnn [126](#), [7512](#), [7931](#)
- \msg_set:nnnn [126](#), [126](#), [7512](#), [7929](#)
- \msg_term:n [132](#), [132](#), [7640](#), [7770](#)
- \msg_warning:nn [129](#), [7768](#)
- \msg_warning:nnn [129](#), [7768](#)
- \msg_warning:nnnn [129](#), [7768](#)
- \msg_warning:nnnnn [129](#), [7768](#)
- \msg_warning:nnnnnn
. [129](#), [129](#), [7768](#), [7975](#)
- \msg_warning_text:n
. [127](#), [127](#), [7655](#), [7772](#)
- msg internal commands:
 - __msg_class_chk_exist:nTF
. [7792](#), [7806](#), [7872](#), [7882](#), [7887](#)
 - \l__msg_class_loop_seq . [457](#), [7801](#),
[7891](#), [7899](#), [7909](#), [7910](#), [7913](#), [7915](#)
 - __msg_class_new:nn
. [454](#), [458](#), [7686](#), [7725](#),
[7736](#), [7747](#), [7768](#), [7776](#), [7784](#), [7790](#)
 - \l__msg_class_tl [454](#),
[457](#), [7797](#), [7813](#), [7825](#), [7846](#), [7850](#),
[7853](#), [7861](#), [7900](#), [7902](#), [7904](#), [7918](#)
 - \c__msg_coding_error_text_tl . . .
. [135](#), [7537](#), [7981](#), [7989](#), [8015](#),
[8033](#), [8042](#), [8054](#), [8068](#), [8077](#), [8086](#),
[8093](#), [8115](#), [8122](#), [8129](#), [8137](#), [10390](#),
[10411](#), [10417](#), [10424](#), [17375](#), [17386](#)
 - \c__msg_continue_text_tl . [7537](#), [7581](#)
 - \c__msg_critical_text_tl . [7537](#), [7744](#)
 - \l__msg_current_class_tl
. [456](#), [7797](#), [7808](#),
[7845](#), [7850](#), [7853](#), [7861](#), [7890](#), [7904](#)
 - __msg_error:Nnnnnn [7747](#)
 - __msg_error_code:nnnnnn [7974](#)
 - __msg_expandable_error:n
. [134](#), [134](#), [464](#), [8186](#), [8205](#)
 - __msg_expandable_error:w . [463](#), [8186](#)
 - __msg_expandable_error_module:nn
. [18336](#)
 - __msg_fatal_code:nnnnnn [7970](#)
 - \c__msg_fatal_text_tl . . . [7537](#), [7733](#)
 - \c__msg_help_text_tl [7537](#), [7585](#)
 - \l__msg_hierarchy_seq
. [455](#), [455](#), [7800](#), [7828](#), [7838](#), [7843](#)
 - \l__msg_internal_tl
. [466](#), [7482](#), [8285](#), [8286](#), [8289](#), [8298](#)
 - __msg_interrupt_more_text:n . . .
. [448](#), [7588](#)
 - __msg_interrupt_text:n . . [7591](#), [7602](#)
 - __msg_interrupt_wrap:nn
. [7580](#), [7584](#), [7588](#)
 - __msg_kernel_class_new:nN
. [459](#), [7932](#), [7970](#), [7974](#), [7975](#), [7976](#)
 - __msg_kernel_class_new_aux:nN [7932](#)
 - __msg_kernel_error:nn [133](#),
[1722](#), [7970](#), [9627](#), [9642](#), [16165](#), [16876](#)
 - __msg_kernel_error:nnn [133](#),
[1458](#), [1500](#), [1541](#), [1546](#), [1722](#), [1770](#),
[1780](#), [1931](#), [1938](#), [2364](#), [2808](#), [5601](#),
[7795](#), [7970](#), [8267](#), [8381](#), [8451](#), [8549](#),
[9719](#), [9781](#), [9797](#), [9939](#), [9956](#), [10463](#),
[10778](#), [16288](#), [16481](#), [16614](#), [19717](#)
 - __msg_kernel_error:nnnn
. [133](#), [1449](#), [1478](#), [1560](#),
[1722](#), [1745](#), [1755](#), [1901](#), [2425](#), [7495](#),
[7505](#), [7820](#), [7970](#), [9704](#), [9758](#), [9816](#),
[9829](#), [9947](#), [10286](#), [10774](#), [16158](#), [16768](#)
 - __msg_kernel_error:nnnnn
. [133](#), [7970](#), [8802](#), [16304](#), [17534](#)
 - __msg_kernel_error:nnnnnn
. [133](#), [133](#), [2440](#), [7970](#)
 - __msg_kernel_expandable_
error:nn [134](#), [4079](#),
[5888](#), [6613](#), [6617](#), [6619](#), [6627](#), [6633](#),
[7209](#), [8203](#), [11275](#), [12125](#), [15712](#), [18326](#)
 - __msg_kernel_expandable_
error:nnn [134](#), [2112](#), [3064](#), [4541](#),
[4785](#), [4965](#), [5482](#), [6361](#), [8203](#), [11280](#),
[11294](#), [11296](#), [11394](#), [11432](#), [11438](#),
[11775](#), [11780](#), [11791](#), [11798](#), [11861](#),
[11871](#), [12072](#), [12092](#), [12636](#), [19708](#)
 - __msg_kernel_expandable_
error:nnnn [134](#),

- [8203](#), [12264](#), [12296](#), [12752](#), [18291](#)
- _msg_kernel_expandable_-
 - error:nnnnn [134](#), [8203](#), [8814](#), [10889](#), [12424](#), [15203](#), [15773](#), [15787](#), [17531](#)
- _msg_kernel_expandable_-
 - error:nnnnnn [134](#), [134](#), [8203](#)
- _msg_kernel_fatal:nn [133](#), [7970](#), [8577](#), [8700](#)
- _msg_kernel_fatal:nnn ... [133](#), [7970](#)
- _msg_kernel_fatal:nnnn ... [133](#), [7970](#)
- _msg_kernel_fatal:nnnnn . [133](#), [7970](#)
- _msg_kernel_fatal:nnnnnn [133](#), [133](#), [7970](#)
- _msg_kernel_info:nn [133](#), [7975](#)
- _msg_kernel_info:nnn [133](#), [7975](#)
- _msg_kernel_info:nnnn ... [133](#), [7975](#)
- _msg_kernel_info:nnnnn .. [133](#), [7975](#)
- _msg_kernel_info:nnnnnn [133](#), [133](#), [7975](#)
- _msg_kernel_new:nnn [132](#), [7924](#), [8020](#), [8022](#), [8024](#), [8026](#), [8028](#), [8046](#), [8142](#), [8144](#), [8146](#), [8148](#), [8150](#), [8152](#), [8154](#), [8161](#), [8168](#), [8175](#), [10440](#), [10917](#), [10919](#), [10921](#), [10923](#), [10925](#), [10927](#), [12446](#), [12448](#), [12450](#), [12452](#), [12454](#), [12456](#), [12458](#), [12460](#), [12462](#), [12467](#), [12671](#), [12673](#), [15708](#), [17390](#), [18332](#)
- _msg_kernel_new:nnnn [132](#), [132](#), [7924](#), [7978](#), [7986](#), [7994](#), [8001](#), [8012](#), [8030](#), [8039](#), [8051](#), [8058](#), [8065](#), [8074](#), [8083](#), [8090](#), [8100](#), [8112](#), [8119](#), [8126](#), [8134](#), [9047](#), [9053](#), [9060](#), [9067](#), [9072](#), [9648](#), [10378](#), [10381](#), [10387](#), [10396](#), [10402](#), [10408](#), [10414](#), [10421](#), [10428](#), [10434](#), [10751](#), [10891](#), [10906](#), [16293](#), [16310](#), [16317](#), [16326](#), [17372](#), [17380](#), [17383](#), [19722](#)
- _msg_kernel_set:nnn [132](#), [7924](#)
- _msg_kernel_set:nnnn [132](#), [132](#), [7924](#)
- _msg_kernel_warning:nn .. [133](#), [7975](#)
- _msg_kernel_warning:nnn . [133](#), [7975](#)
- _msg_kernel_warning:nnnn [133](#), [7975](#)
- _msg_kernel_warning:nnnnn [133](#), [3404](#), [3413](#), [7975](#), [9081](#), [16336](#), [16345](#)
- _msg_kernel_warning:nnnnnn ... [133](#), [133](#), [7907](#), [7975](#)
- \l_msg_line_context_bool [7483](#), [7658](#), [7663](#), [7668](#), [7673](#), [7678](#)
- _msg_log_next: [134](#), [134](#), [134](#), [134](#), [282](#), [2030](#), [2043](#), [2044](#), [3394](#), [3397](#), [4600](#), [5369](#), [5441](#), [5712](#), [5714](#), [6451](#), [6453](#), [7477](#), [8232](#), [9343](#), [9440](#), [9508](#), [10377](#), [15911](#), [15913](#), [17370](#), [18274](#), [18277](#)
- \g_msg_log_next_bool [465](#), [466](#), [8232](#), [8254](#), [8269](#), [8287](#), [8290](#)
- _msg_log_wrap:n [465](#)
- \c_msg_more_text_prefix_tl [7484](#), [7523](#), [7532](#), [7750](#)
- \c_msg_no_info_text_tl .. [7537](#), [7580](#)
- _msg_no_more_text:nnnn [7747](#)
- \c_msg_on_line_text_tl .. [7537](#), [7572](#)
- _msg_redirect:nnn [7876](#)
- _msg_redirect_loop_chk:nnn ... [7876](#), [7918](#)
- _msg_redirect_loop_list:n .. [7876](#)
- \l_msg_redirect_prop [7799](#), [7825](#), [7870](#), [7873](#)
- \c_msg_return_text_tl [7537](#), [7984](#), [7992](#), [7999](#)
- _msg_show_item:n [135](#), [135](#), [135](#), [465](#), [466](#), [4596](#), [6440](#), [6447](#), [8304](#)
- _msg_show_item:nn [135](#), [135](#), [135](#), [445](#), [7473](#), [8304](#)
- _msg_show_item_unbraced:nn ... [135](#), [135](#), [476](#), [8304](#), [8613](#), [10371](#), [17364](#)
- _msg_show_pre:nnnnnn [134](#), [134](#), [6444](#), [8235](#), [8261](#), [8610](#), [10354](#), [10360](#), [17355](#)
- _msg_show_pre_aux:n [464](#), [8235](#)
- _msg_show_variable:NNNnn [134](#), [135](#), [135](#), [135](#), [281](#), [358](#), [414](#), [445](#), [465](#), [708](#), [2024](#), [3387](#), [4594](#), [5437](#), [5703](#), [6438](#), [7471](#), [8255](#), [15904](#)
- _msg_show_wrap:n [134](#), [135](#), [135](#), [135](#), [135](#), [325](#), [465](#), [465](#), [466](#), [466](#), [466](#), [466](#), [466](#), [527](#), [2039](#), [3392](#), [6446](#), [6470](#), [6543](#), [6552](#), [6561](#), [6570](#), [8264](#), [8274](#), [8280](#), [8612](#), [10362](#), [10369](#), [17360](#)
- _msg_show_wrap:Nn [134](#), [135](#), [135](#), [5365](#), [5707](#), [8272](#), [9339](#), [9436](#), [9504](#), [15908](#)
- _msg_show_wrap_aux:n [8280](#)
- _msg_show_wrap_aux:w [8280](#)
- \c_msg_text_prefix_tl [7484](#), [7488](#), [7521](#), [7530](#), [7730](#), [7741](#), [7756](#), [7773](#), [7781](#), [7787](#), [8208](#), [8239](#), [18341](#)
- _msg_tmp:w [8187](#), [8200](#)
- \c_msg_trouble_text_tl [7537](#)
- _msg_use:nnnnnnn [7696](#), [7802](#)
- _msg_use_code: [454](#), [454](#), [7802](#)
- _msg_use_hierarchy:nwN [7802](#)
- _msg_use_redirect_module:n ... [455](#), [7802](#)
- _msg_use_redirect_name:n ... [7802](#)

| | | | |
|---|--|--|--|
| <code>\mskip</code> | 469 | <code>\newlinechar</code> | 103, 473 |
| <code>\muexpr</code> | 646 | <code>\next</code> | 74, 106, 116, 116, 117, 131, 140, 144, 147, 155 |
| multichoice commands: | | <code>\NG</code> | 19383 |
| <code>.multichoice:</code> | 163, 10057 | <code>\ng</code> | 19383 |
| multichoices commands: | | <code>\noalign</code> | 474 |
| <code>.multichoices:nn</code> | 163, 10057 | <code>\noautospacing</code> | 1142 |
| <code>\multiply</code> | 470 | <code>\noautoxspacing</code> | 1143 |
| <code>\muskip</code> | 471, 6933 | <code>\noboundary</code> | 475 |
| muskip commands: | | <code>\noexpand</code> | 118, 122, 133, 136, 476 |
| <code>\c_max_muskip</code> | 157, 9509 | <code>\nohrule</code> | 904 |
| <code>\muskip_add:Nn</code> | 155, 155, 9487 | <code>\noindent</code> | 477 |
| <code>\muskip_const:Nn</code> | 155, 155, 9455, 9509, 9510 | <code>\nokerns</code> | 905 |
| <code>\muskip_eval:n</code> | 156, 156, 156, 9497, 9504 | <code>\noligs</code> | 906 |
| <code>\muskip_gadd:Nn</code> | 155, 9487 | <code>\nolimits</code> | 478 |
| <code>\muskip_gset:Nn</code> | 156, 9458, 9476 | <code>\nonscript</code> | 479 |
| <code>\muskip_gset_eq:NN</code> | 156, 9481 | <code>\nonstopmode</code> | 480 |
| <code>\muskip_gsub:Nn</code> | 156, 9487 | <code>\normaldeviate</code> | 960 |
| <code>\muskip_gzero:N</code> | 155, 9461, 9469 | <code>\normalend</code> | 1265, 1266, 8529, 8674 |
| <code>\muskip_gzero_new:N</code> | 155, 9466 | <code>\normaleveryjob</code> | 1267 |
| <code>\muskip_if_exist:NTF</code> | 155, 155, 9467, 9469, 9472 | <code>\normalexpanded</code> | 1276 |
| <code>\muskip_if_exist_p:N</code> | 155, 155, 9472 | <code>\normalhoffset</code> | 1279 |
| <code>\muskip_log:N</code> | 157, 157, 9505 | <code>\normalinput</code> | 1268 |
| <code>\muskip_log:n</code> | 157, 157, 9505 | <code>\normalitaliccorrection</code> | 1278, 1280 |
| <code>\muskip_new:N</code> | 155, 155, 155, 9447, 9457, 9467, 9469, 9511, 9512, 9513, 9514 | <code>\normallanguage</code> | 1269 |
| <code>\muskip_set:Nn</code> | 156, 156, 9476 | <code>\normalleft</code> | 1286, 1287 |
| <code>\muskip_set_eq:NN</code> | 156, 156, 9481 | <code>\normalmathop</code> | 1270 |
| <code>\muskip_show:N</code> | 156, 156, 9501 | <code>\normalmiddle</code> | 1288 |
| <code>\muskip_show:n</code> | 156, 156, 504, 9503, 9508 | <code>\normalmonth</code> | 1271 |
| <code>\muskip_sub:Nn</code> | 156, 156, 9487 | <code>\normalouter</code> | 1272 |
| <code>\muskip_use:N</code> | 156, 156, 156, 156, 9498, 9499 | <code>\normalover</code> | 1273 |
| <code>\muskip_zero:N</code> | 155, 9461, 9467 | <code>\normalright</code> | 1289 |
| <code>muskip_zero:N</code> | 155 | <code>\normalshowtokens</code> | 1282 |
| <code>\muskip_zero_new:N</code> | 155, 155, 9466 | <code>\normalunexpanded</code> | 1275 |
| <code>\g_tmpa_muskip</code> | 157, 9511 | <code>\normalvcenter</code> | 1274 |
| <code>\l_tmpa_muskip</code> | 157, 9511 | <code>\normalvoffset</code> | 1281 |
| <code>\g_tmpb_muskip</code> | 157, 9511 | <code>\nospaces</code> | 907 |
| <code>\l_tmpb_muskip</code> | 157, 9511 | notexpanded commands: | |
| <code>\c_zero_muskip</code> | 157, 9462, 9509 | <code>\notexpanded: <token></code> | 117 |
| <code>\muskipdef</code> | 472 | <code>\novrule</code> | 908 |
| <code>\mutoglu</code> | 647 | <code>\nulldelimiterspace</code> | 481 |

N

| | |
|-------------------------------------|-----|
| <code>nan</code> | 187 |
| <code>nc</code> | 188 |
| <code>nd</code> | 188 |
| <code>\newbox</code> | 361 |
| <code>\newcatcodetable</code> | 52 |
| <code>\newcount</code> | 361 |
| <code>\newdimen</code> | 361 |

O

| | |
|-------------------------------------|------------------------|
| <code>\O</code> | 19384 |
| <code>\o</code> | 19384 |
| <code>\OE</code> | 19385 |
| <code>\oe</code> | 19385 |
| <code>\omit</code> | 484 |
| one commands: | |
| <code>\c_minus_one</code> | 5407, 17575 |
| <code>\c_one_degree_fp</code> | 179, 187, 11885, 15917 |

| | | | |
|---------------------------------------|---------------------|---------------------------------------|--|
| <code>\openin</code> | 485 | <code>\over</code> | 491 |
| <code>\openout</code> | 486 | <code>\overfullrule</code> | 492 |
| <code>\or</code> | 487 | <code>\overline</code> | 493 |
| or commands: | | <code>\overwithdelims</code> | 494 |
| <code>\or:</code> | 79, | | |
| 79, 79, 333, 333, 333, 333, 335, 335, | | | |
| 664, 1294, 1862, 1863, 1864, 1865, | | | |
| 1866, 1867, 1868, 1869, 1870, 3691, | | | |
| 3766, 4609, 5152, 5153, 5154, 5155, | | | |
| 5156, 5157, 5158, 5159, 5160, 5161, | | | |
| 5162, 5163, 5164, 5165, 5166, 5167, | | | |
| 5168, 5169, 5170, 5171, 5172, 5173, | | | |
| 5174, 5175, 5176, 5185, 5186, 5187, | | | |
| 5188, 5189, 5190, 5191, 5192, 5193, | | | |
| 5194, 5195, 5196, 5197, 5198, 5199, | | | |
| 5200, 5201, 5202, 5203, 5204, 5205, | | | |
| 5206, 5207, 5208, 5209, 6673, 6677, | | | |
| 6680, 6684, 6688, 6690, 6692, 6694, | | | |
| 6695, 6697, 6699, 6701, 6703, 8919, | | | |
| 8920, 8921, 8922, 8923, 8924, 8925, | | | |
| 10517, 10518, 10519, 10666, 10692, | | | |
| 10693, 11053, 11054, 11079, 12319, | | | |
| 12320, 12321, 12357, 12836, 12837, | | | |
| 12838, 12966, 13051, 13137, 13138, | | | |
| 13139, 13140, 13141, 13142, 13143, | | | |
| 13144, 13145, 13222, 13225, 13561, | | | |
| 13807, 14023, 14048, 14054, 14055, | | | |
| 14056, 14057, 14058, 14206, 14241, | | | |
| 14243, 14251, 14341, 14345, 14346, | | | |
| 14347, 14348, 14349, 14350, 14351, | | | |
| 14352, 14353, 14354, 14361, 14362, | | | |
| 14363, 14364, 14365, 14366, 14367, | | | |
| 14368, 14369, 14370, 14377, 14378, | | | |
| 14379, 14380, 14381, 14382, 14383, | | | |
| 14384, 14385, 14386, 14393, 14394, | | | |
| 14395, 14396, 14397, 14398, 14399, | | | |
| 14400, 14401, 14402, 14409, 14410, | | | |
| 14411, 14412, 14413, 14414, 14415, | | | |
| 14416, 14417, 14418, 14425, 14426, | | | |
| 14427, 14428, 14429, 14430, 14431, | | | |
| 14432, 14433, 14434, 14452, 14503, | | | |
| 14506, 14515, 14626, 14649, 14650, | | | |
| 14684, 14689, 14699, 14704, 14714, | | | |
| 14719, 14729, 14734, 14744, 14749, | | | |
| 14759, 14764, 15201, 15222, 15223, | | | |
| 15267, 15352, 15355, 15367, 15373, | | | |
| 15420, 15422, 15423, 15433, 15439, | | | |
| 15482, 15483, 15493, 15526, 15527, | | | |
| 15537, 15594, 15595, 15785, 15814 | | | |
| <code>\outer</code> | 5, 5, 361, 488, 590 | | |
| <code>\output</code> | 489 | | |
| <code>\outputbox</code> | 909 | | |
| <code>\outputmode</code> | 961 | | |
| <code>\outputpenalty</code> | 490 | | |
| | | P | |
| | | <code>\PackageError</code> | 125, 133 |
| | | <code>\pagebottomoffset</code> | 910 |
| | | <code>\pagedepth</code> | 495 |
| | | <code>\pagedir</code> | 943 |
| | | <code>\pagediscards</code> | 649 |
| | | <code>\pagefilllstretch</code> | 496 |
| | | <code>\pagefillstretch</code> | 497 |
| | | <code>\pagefilstretch</code> | 498 |
| | | <code>\pagegoal</code> | 499 |
| | | <code>\pageheight</code> | 962 |
| | | <code>\pageleftoffset</code> | 911 |
| | | <code>\pagerightoffset</code> | 912 |
| | | <code>\pageshrink</code> | 500 |
| | | <code>\pagestretch</code> | 501 |
| | | <code>\pagetopoffset</code> | 913 |
| | | <code>\pagetotal</code> | 502 |
| | | <code>\pagewidth</code> | 963 |
| | | <code>\par</code> | 10, 10, 11, 11, 11, 12, 12, 12, |
| | | | 13, 13, 13, 14, 14, 14, 138, 138, 276, |
| | | | 276, 503, 730, 16517, 16518, 16520, |
| | | | 16522, 16524, 16529, 16537, 16551 |
| | | <code>\pardir</code> | 944 |
| | | <code>\parfillskip</code> | 504 |
| | | <code>\parindent</code> | 505 |
| | | <code>\parshape</code> | 506 |
| | | <code>\parshapedimen</code> | 650 |
| | | <code>\parshapeindent</code> | 651 |
| | | <code>\parshapelength</code> | 652 |
| | | <code>\parskip</code> | 507 |
| | | <code>\patterns</code> | 508 |
| | | <code>\pausing</code> | 509 |
| | | <code>pc</code> | 188 |
| | | <code>\pdfadjustspacing</code> | 745 |
| | | <code>\pdfannot</code> | 675 |
| | | <code>\pdfcatalog</code> | 676 |
| | | <code>\pdfcolorstack</code> | 678 |
| | | <code>\pdfcolorstackinit</code> | 679 |
| | | <code>\pdfcompresslevel</code> | 677 |
| | | <code>\pdfcopyfont</code> | 746 |
| | | <code>\pdfcreationdate</code> | 680 |
| | | <code>\pdfdecimaldigits</code> | 681 |
| | | <code>\pdfdest</code> | 682 |
| | | <code>\pdfdestmargin</code> | 683 |
| | | <code>\pdfdraftmode</code> | 747 |
| | | <code>\pdfeachlinedepth</code> | 748 |
| | | <code>\pdfeachlineheight</code> | 749 |
| | | <code>\pdfendlink</code> | 684 |
| | | <code>\pdfendthread</code> | 685 |

| | | | |
|---|-----|--|---------------------|
| <code>\pdfextension</code> | 914 | <code>\pdfprotrudechars</code> | 767 |
| <code>\pdffeedback</code> | 915 | <code>\pdfpxdimen</code> | 768 |
| <code>\pdffirstlineheight</code> | 750 | <code>\pdfrandomseed</code> | 769 |
| <code>\pdffontattr</code> | 686 | <code>\pdfrefobj</code> | 721 |
| <code>\pdffontexpand</code> | 751 | <code>\pdfrefxform</code> | 722 |
| <code>\pdffontname</code> | 687 | <code>\pdfrefximage</code> | 723 |
| <code>\pdffontobjnum</code> | 688 | <code>\pdfrestore</code> | 724 |
| <code>\pdffontsize</code> | 752 | <code>\pdfretval</code> | 725 |
| <code>\pdfgamma</code> | 689 | <code>\pdfsave</code> | 726 |
| <code>\pdfgentounicode</code> | 692 | <code>\pdfsavepos</code> | 770 |
| <code>\pdfglyptounicode</code> | 693 | <code>\pdfsetmatrix</code> | 727 |
| <code>\pdfhorigin</code> | 694 | <code>\pdfsetrandomseed</code> | 772 |
| <code>\pdfignoreddimen</code> | 753 | <code>\pdfshellescape</code> | 773 |
| <code>\pdfimageapplygamma</code> | 690 | <code>\pdfstartlink</code> | 728 |
| <code>\pdfimagegamma</code> | 691 | <code>\pdfstartthread</code> | 729 |
| <code>\pdfimagehicolor</code> | 695 | <code>\pdfstrcmp</code> | 40, 771 |
| <code>\pdfimageresolution</code> | 696 | <code>pdfstrcmp</code> | 328 |
| <code>\pdfincludechars</code> | 697 | <code>\pdfsuppressptexinfo</code> | 730 |
| <code>\pdfinclusioncopyfonts</code> | 698 | <code>pdftex</code> commands: | |
| <code>\pdfinclusionerrorlevel</code> | 699 | <code>\pdftex_adjustspacing:D</code> | 745, 947 |
| <code>\pdfinfo</code> | 700 | <code>\pdftex_copyfont:D</code> | 746, 948 |
| <code>\pdfinsertht</code> | 754 | <code>\pdftex_draftmode:D</code> | 747, 949 |
| <code>\pdflastannot</code> | 701 | <code>\pdftex_eachlinedepth:D</code> | 748 |
| <code>\pdflastlinedepth</code> | 755 | <code>\pdftex_eachlineheight:D</code> | 749 |
| <code>\pdflastlink</code> | 702 | <code>\pdftex_efcode:D</code> | 779 |
| <code>\pdflastobj</code> | 703 | <code>\pdftex_firstlineheight:D</code> | 750 |
| <code>\pdflastxform</code> | 704 | <code>\pdftex_fontexpand:D</code> | 751, 950 |
| <code>\pdflastximage</code> | 705 | <code>\pdftex_fontsize:D</code> | 752 |
| <code>\pdflastximagecolordepth</code> | 706 | <code>\pdftex_if_engine:TF</code> | |
| <code>\pdflastximagepages</code> | 707 | | 17553, 17554, 17555 |
| <code>\pdflastxpos</code> | 756 | <code>\pdftex_if_engine_p:</code> | 17552 |
| <code>\pdflastypos</code> | 757 | <code>\pdftex_ifabsdim:D</code> | 742, 951 |
| <code>\pdflinkmargin</code> | 708 | <code>\pdftex_ifabsnum:D</code> | 743, 952 |
| <code>\pdfliteral</code> | 709 | <code>\pdftex_ifincsname:D</code> | 780 |
| <code>\pdfmapfile</code> | 758 | <code>\pdftex_ifprimitive:D</code> | 744, 856 |
| <code>\pdfmapline</code> | 759 | <code>\pdftex_ignoredimen:D</code> | 753 |
| <code>\pdfminorversion</code> | 710 | <code>\pdftex_ignoreligaturesinfont:D</code> | 953 |
| <code>\pdfnames</code> | 711 | <code>\pdftex_insertht:D</code> | 754, 954 |
| <code>\pdfnoligatures</code> | 760 | <code>\pdftex_lastlinedepth:D</code> | 755 |
| <code>\pdfnormaldeviate</code> | 761 | <code>\pdftex_lastxpos:D</code> | 756, 958 |
| <code>\pdfobj</code> | 712 | <code>\pdftex_lastypos:D</code> | 757, 959 |
| <code>\pdfobjcompresslevel</code> | 713 | <code>\pdftex_leftmarginkern:D</code> | 781 |
| <code>\pdfoutline</code> | 714 | <code>\pdftex_letterspacefont:D</code> | 782 |
| <code>\pdfoutput</code> | 715 | <code>\pdftex_lpcode:D</code> | 783 |
| <code>\pdfpageattr</code> | 716 | <code>\pdftex_mapfile:D</code> | 758, 1241 |
| <code>\pdfpagebox</code> | 717 | <code>\pdftex_mapline:D</code> | 759, 1242 |
| <code>\pdfpageheight</code> | 762 | <code>\pdftex_noligatures:D</code> | 760 |
| <code>\pdfpageref</code> | 718 | <code>\pdftex_normaldeviate:D</code> | 761, 960 |
| <code>\pdfpageresources</code> | 719 | <code>\pdftex_pageheight:D</code> . | 762, 962, 1230 |
| <code>\pdfpagesattr</code> | 720 | <code>\pdftex_pagewidth:D</code> | 763, 1232 |
| <code>\pdfpagewidth</code> | 763 | <code>\pdftex_pagewith:D</code> | 963 |
| <code>\pdfpkmode</code> | 764 | <code>\pdftex_pdfannot:D</code> | 675 |
| <code>\pdfpkresolution</code> | 765 | <code>\pdftex_pdfcatalog:D</code> | 676 |
| <code>\pdfprimitive</code> | 766 | | |

| | |
|-----------------------------------|---|
| \pdfTEX_pdfcolorstack:D | 678, 19829, 19838 |
| \pdfTEX_pdfcolorstackinit:D | 679 |
| \pdfTEX_pdfcompresslevel:D | 677 |
| \pdfTEX_pdfcreationdate:D | 680 |
| \pdfTEX_pdfdecimaldigits:D | 681 |
| \pdfTEX_pdfdest:D | 682 |
| \pdfTEX_pdfdestmargin:D | 683 |
| \pdfTEX_pdfendlink:D | 684 |
| \pdfTEX_pdfendthread:D | 685 |
| \pdfTEX_pdffontattr:D | 686 |
| \pdfTEX_pdffontname:D | 687 |
| \pdfTEX_pdffontobjnum:D | 688 |
| \pdfTEX_pdfgamma:D | 689 |
| \pdfTEX_pdfgentounicode:D | 692 |
| \pdfTEX_pdfglyphoutunicode:D | 693 |
| \pdfTEX_pdfhorigin:D | 694 |
| \pdfTEX_pdfimageapplygamma:D | 690 |
| \pdfTEX_pdfimagegamma:D | 691 |
| \pdfTEX_pdfimagehicolor:D | 695 |
| \pdfTEX_pdfimageresolution:D | 696 |
| \pdfTEX_pdfincludechars:D | 697 |
| \pdfTEX_pdfinclusioncopyfonts:D | 698 |
| \pdfTEX_pdfinclusionerrorlevel:D | 699 |
| \pdfTEX_pdfinfo:D | 700 |
| \pdfTEX_pdflastannot:D | 701 |
| \pdfTEX_pdflastlink:D | 702 |
| \pdfTEX_pdflastobj:D | 703 |
| \pdfTEX_pdflastxform:D | 704, 955 |
| \pdfTEX_pdflastximage:D | 705, 956 |
| \pdfTEX_pdflastximagecolordepth:D | 706 |
| \pdfTEX_pdflastximagepages:D | 707, 957 |
| \pdfTEX_pdflinkmargin:D | 708 |
| \pdfTEX_pdfliteral:D | 709, 19792 |
| \pdfTEX_pdfminorversion:D | 710 |
| \pdfTEX_pdfnames:D | 711 |
| \pdfTEX_pdfobj:D | 712 |
| \pdfTEX_pdfobjcompresslevel:D | 713 |
| \pdfTEX_pdfoutline:D | 714 |
| \pdfTEX_pdfoutput:D | 715, 961, 17501 |
| \pdfTEX_pdfpageattr:D | 716 |
| \pdfTEX_pdfpagebox:D | 717 |
| \pdfTEX_pdfpageref:D | 718 |
| \pdfTEX_pdfpageresources:D | 719 |
| \pdfTEX_pdfpagesattr:D | 720 |
| \pdfTEX_pdfrefobj:D | 721 |
| \pdfTEX_pdfrefxform:D | 722, 967 |
| \pdfTEX_pdfrefximage:D | 723, 968 |
| \pdfTEX_pdfrestore:D | 724, 19805 |
| \pdfTEX_pdfretval:D | 725 |
| \pdfTEX_pdfsave:D | 726, 19799 |
| \pdfTEX_pdfsetmatrix:D | 727, 19811 |
| \pdfTEX_pdfstartlink:D | 728 |
| \pdfTEX_pdfstartthread:D | 729 |
| \pdfTEX_pdfsuppressptexinfo:D | 730 |
| \pdfTEX_pdftexbanner:D | 776, 1259 |
| \pdfTEX_pdftexrevision:D | 777, 1260 |
| \pdfTEX_pdftexversion:D | 257, 778, 1238, 1261, 17462 |
| \pdfTEX_pdfthread:D | 731 |
| \pdfTEX_pdfthreadmargin:D | 732 |
| \pdfTEX_pdftrailer:D | 733 |
| \pdfTEX_pdfuniqueresname:D | 734 |
| \pdfTEX_pdfvorigin:D | 735 |
| \pdfTEX_pdfxform:D | 736, 970 |
| \pdfTEX_pdfxformattr:D | 737 |
| \pdfTEX_pdfxformname:D | 738 |
| \pdfTEX_pdfxformresources:D | 739 |
| \pdfTEX_pdfximage:D | 740, 971 |
| \pdfTEX_pdfximagebbox:D | 741 |
| \pdfTEX_pkmode:D | 764 |
| \pdfTEX_pkresolution:D | 765 |
| \pdfTEX_primitive:D | 766, 857 |
| \pdfTEX_protrudechars:D | 767, 964 |
| \pdfTEX_pxdimen:D | 768, 965 |
| \pdfTEX_quitvmode:D | 784 |
| \pdfTEX_randomseed:D | 769, 966 |
| \pdfTEX_rightmarginkern:D | 785 |
| \pdfTEX_rpcode:D | 786 |
| \pdfTEX_savepos:D | 770, 969 |
| \pdfTEX_setrandomseed:D | 772, 972 |
| \pdfTEX_shellescape:D | 773, 858 |
| \pdfTEX_strcmp:D | 771, 3471 |
| \pdfTEX_synctex:D | 787 |
| \pdfTEX_tagcode:D | 788 |
| \pdfTEX_tracingfonts:D | 774, 973, 1174, 1176, 1180 |
| \pdfTEX_uniformdeviate:D | 703, 703, 703, 775, 974, 15706, 15717, 15720, 18279, 18309, 18330 |
| \pdfTEXbanner | 776 |
| \pdfTEXrevision | 777 |
| \pdfTEXversion | 95, 778 |
| \pdfthread | 731 |
| \pdfthreadmargin | 732 |
| \pdftracingfonts | 774, 1175, 1176 |
| \pdftrailer | 733 |
| \pdfuniformdeviate | 775 |
| \pdfuniqueresname | 734 |
| \pdfvariable | 916 |
| \pdfvorigin | 735 |
| \pdfxform | 736 |
| \pdfxformattr | 737 |
| \pdfxformname | 738 |
| \pdfxformresources | 739 |
| \pdfximage | 740 |
| \pdfximagebbox | 741 |

peek commands:

`\peek_after:Nw` 94, 113,
 113, 113, 114, 7007, 7032, 7050, 7100
`\peek_catcode:Ntf` 114, 114, 7124
`\peek_catcode_ignore_spaces:Ntf` .
 114, 114, 7124
`\peek_catcode_remove:Ntf`
 114, 114, 7124
`\peek_catcode_remove_ignore_-
 spaces:Ntf` 114, 114, 7124
`\peek_charcode:Ntf` ... 114, 114, 7140
`\peek_charcode_ignore_spaces:Ntf`
 115, 115, 7140
`\peek_charcode_remove:Ntf`
 115, 115, 7140
`\peek_charcode_remove_ignore_-
 spaces:Ntf` 115, 115, 7140
`\peek_gafter:Nw` .. 114, 114, 114, 7007
`\peek_meaning:Ntf` 115, 115, 7156
`\peek_meaning_ignore_spaces:Ntf` .
 115, 115, 7156
`\peek_meaning_remove:Ntf`
 115, 115, 7156
`\peek_meaning_remove_ignore_-
 spaces:Ntf` 116, 116, 7156
`\peek_N_type:Tf`
 221, 221, 19653, 19687, 19689

peek internal commands:

`__peek_def:nnnn` 7107,
 7124, 7128, 7132, 7136, 7140, 7144,
 7148, 7152, 7156, 7160, 7164, 7168
`__peek_def:nnnnn` 7107
`__peek_execute_branches:`
 433, 7104, 7119
`__peek_execute_branches_-
 catcode:` 7064, 7127, 7129, 7135, 7137
`__peek_execute_branches_-
 catcode_aux:` 7064
`__peek_execute_branches_-
 catcode_auxii:N` 7064
`__peek_execute_branches_-
 catcode_auxiii:` 7064
`__peek_execute_branches_-
 charcode:`
 7064, 7143, 7145, 7151, 7153
`__peek_execute_branches_-
 meaning:` 7056, 7159, 7161, 7167, 7169
`__peek_execute_branches_N_type:`
 19653
`__peek_false:w` 810, 810, 7003, 7026,
 7044, 7061, 7084, 7094, 19670, 19683
`__peek_get_prefix_arg_replacement:wN`
 7173

`__peek_ignore_spaces_execute_-
 branches:` 7097,
 7131, 7139, 7147, 7155, 7163, 7171
`__peek_N_type:w` 19653
`__peek_N_type_aux:nnw` 19653
`\l__peek_search_tl`
 431, 433, 7002, 7020, 7041, 7081, 7091
`\l__peek_search_token`
 431, 7001, 7019, 7040, 7058
`__peek_tmp:w` 7003, 7015, 19654, 19676
`__peek_token_generic:NNTF` . 810,
 7017, 7034, 7036, 19686, 19688, 19690
`__peek_token_remove_generic:NNTF`
 7038, 7052, 7054
`__peek_true:w`
 810, 810, 7003, 7021, 7042,
 7059, 7082, 7092, 19668, 19682, 19683
`__peek_true_aux:w` .. 7003, 7014, 7043
`__peek_true_remove:w` ... 7011, 7042
`\penalty` 510
`\pi` 187
`\pm` 12618, 12619
`\postbreakpenalty` 1144
`\postdisplaypenalty` 511
`\postexhyphenchar` 917
`\posthyphenchar` 918
`\prebreakpenalty` 1145
`\predisplaydirection` 653
`\predisplaygapfactor` 919
`\predisplaypenalty` 512
`\predisplaysize` 513
`\preexhyphenchar` 920
`\prehyphenchar` 921
`\pretolerance` 514
`\prevdepth` 515
`\prevgraf` 516
prg commands:
`\prg_break_point:Nn` 86
`\prg_do_nothing:` 9, 9, 95,
 303, 346, 346, 414, 546, 701, 1531,
 1532, 2045, 2055, 2402, 2407, 2694,
 2722, 2772, 2787, 4152, 4159, 4399,
 4401, 6075, 6415, 6419, 6426, 8663,
 8918, 9593, 10741, 10784, 10818,
 10844, 10852, 12328, 15667, 16063,
 16070, 16146, 16279, 16280, 18569
`\prg_new_conditional:Nnn`
 88, 88, 1430, 5616
`\prg_new_conditional:Npnn` ... 88,
 88, 88, 424, 434, 1417, 2003, 2873,
 2883, 2895, 2917, 2919, 2967, 3249,
 3268, 3287, 3322, 3339, 3350, 3501,
 3516, 3521, 4276, 4789, 4842, 4879,
 4887, 5442, 5447, 5557, 5565, 5577,

- 5583, [5616](#), 5689, 5724, 5900, 5902,
5904, 5906, 6201, 6763, 6768, 6773,
6778, 6785, 6791, 6797, 6802, 6807,
6812, 6817, 6822, 6827, 6832, 6839,
6856, 6861, 6896, 6940, 7380, 7389,
7486, 8616, 9178, 9183, 9399, 9411,
10335, 10342, 10662, 11767, 12476,
12489, 16421, 16423, 16433, 16595,
18364, 18373, 18379, 18388, 18504
- `\prg_new_eq_conditional:Nnn`
. 89, 89,
[1522](#), 2557, 2558, 3467, 3468, 3469,
3470, 4181, 4183, 4586, 4587, 4588,
4589, 4590, 4591, 4738, 4740, [5616](#),
5720, 5722, 5984, 5986, 6197, 6199,
7376, 7378, 9118, 9120, 9374, 9376,
9472, 9474, 12474, 12475, 16387, 16389
- `\prg_new_protected_conditional:Nnn`
. 88, 88, [1430](#), [5616](#)
- `\prg_new_protected_conditional:Npnn`
. 88, 88, [1417](#), 2931, 2952,
4288, 4398, 4400, 4408, 4410, 4412,
4414, [5616](#), 6084, 6096, 6098, 6215,
6219, 7312, 7322, 7419, 8433, 8552
- `\prg_replicate:nn`
. 93, 93, 397, 397, 397, [5853](#),
8149, 8778, 13749, 14602, 14809,
15013, 15014, 15016, 15018, 15031,
15068, 15533, 15560, 15568, 20638
- `\prg_return_false:` . 55, 89, 90, 90,
90, 321, 350, 365, 365, 408, [1413](#),
1623, 1628, 1641, 1646, 1654, 1671,
2006, 2888, 2901, 2914, 2924, 2941,
2957, 2973, 3261, 3284, 3300, 3308,
3318, 3331, 3345, 3359, 3498, 3506,
3519, 3524, 4281, 4302, 4325, 4787,
4819, 4824, 4847, 4884, 4890, 5445,
5452, 5497, 5562, 5570, [5616](#), 5694,
5729, 5901, 5903, 5905, 5907, 6087,
6103, 6204, 6229, 6766, 6771, 6776,
6781, 6788, 6795, 6800, 6805, 6810,
6815, 6820, 6825, 6830, 6835, 6853,
6859, 6864, 6869, 6902, 6905, 6944,
6969, 6986, 6995, 7320, 7330, 7383,
7405, 7426, 7489, 8437, 8561, 8625,
9181, 9202, 9217, 9218, 9406, 9414,
10340, 10348, 10667, 10677, 10685,
11782, 11794, 12484, 12497, 16422,
16424, 16434, 16601, 16603, 18370,
18376, 18377, 18383, 18392, 18510
- `\prg_return_true/false:` 328
- `\prg_return_true:` . . 55, 89, 90, 90,
90, 322, 322, 350, 440, [1413](#), 1626,
1643, 1651, 1656, 1669, 1674, 2006,
2886, 2899, 2912, 2922, 2938, 2957,
2971, 3259, 3282, 3298, 3316, 3329,
3347, 3358, 3496, 3506, 3519, 3524,
4279, 4306, 4328, 4819, 4845, 4882,
4892, 5445, 5450, 5495, 5560, 5568,
[5616](#), 5692, 5727, 5901, 5903, 5905,
5907, 6090, 6106, 6205, 6229, 6766,
6771, 6776, 6781, 6788, 6795, 6800,
6805, 6810, 6815, 6820, 6825, 6830,
6835, 6851, 6859, 6867, 6967, 6993,
7318, 7328, 7383, 7407, 7424, 7489,
8438, 8564, 8623, 8628, 8630, 9181,
9218, 9404, 9415, 10339, 10347,
10665, 10683, 11777, 11800, 12486,
12495, 16422, 16424, 16434, 16600,
18368, 18376, 18385, 18391, 18392
- `\prg_set_conditional:Nnn`
. 88, [1430](#), [5616](#)
- `\prg_set_conditional:Npnn`
. 88, 89, 90, [1417](#),
1620, 1632, 1648, 1660, 5491, [5616](#)
- `\prg_set_eq_conditional:Nnn`
. 89, [1522](#), [5616](#)
- `\prg_set_protected_conditional:Nnn`
. 88, [1430](#), [5616](#)
- `\prg_set_protected_conditional:Npnn`
. 88, [1417](#), [5616](#)
- prg internal commands:
- `__prg_break:`
. 95, [2055](#), 3378, 4435, [5914](#), 7409,
10732, 15685, 16211, 18445, 18451
- `__prg_break:n` 95, 95,
95, [2055](#), 3380, 4306, 4448, [5914](#), 7308
- `__prg_break_point:`
. 95, 95, 720, 782, [2055](#),
3368, 4303, 4436, [5914](#), 7303, 7394,
10733, 15686, 16204, 16211, 18446
- `__prg_break_point:Nn` 40,
40, 62, 63, 95, 95, 95, 95, 100, 101,
212, 212, 282, 282, 282, 355, 370,
[2046](#), 3016, 3033, 3042, 4463, 4498,
4509, 5004, [5914](#), 6246, 6260, 6279,
6297, 7438, 7457, 12669, 18260, 18409
- `__prg_case_end:nw`
. 23, 23, [2977](#), 3590, 4878, 9247
- `__prg_compare_error:` 80, 80, 364,
365, 493, [4774](#), 4792, 4794, 9186, 9188
- `__prg_compare_error:Nw`
. 80, 80, 364, 365, 366, [4774](#), 4814
- `__prg_generate_conditional:nnNnnnnn`
. 1427, 1446, [1455](#)
- `__prg_generate_conditional:nnnnnnnw`
. [1455](#)

| | | | |
|--|---|---|---|
| __prg_generate_conditional_- count:nnNnn | 1430 | __prg_set_eq_conditional_- loop:nnnnNw | 1538 |
| __prg_generate_conditional_- count:nnNnnnn | 1430 | __prg_set_eq_conditional_p_- form:nnn | 1538 |
| __prg_generate_conditional_- parm:nnNpnn | 1417 | __prg_set_eq_conditional_p_- form:wNnnnn | 1569 |
| __prg_generate_F_form:wnnnnnn | 1487 | __prg_set_eq_conditional_T_- form:nnn | 1538 |
| __prg_generate_p_form:wnnnnnn | 1487 | __prg_set_eq_conditional_T_- form:wNnnnn | 1579 |
| __prg_generate_T_form:wnnnnnn | 1487 | __prg_set_eq_conditional_TF_- form:nnn | 1538 |
| __prg_generate_TF_form:wnnnnnn | 1487 | __prg_set_eq_conditional_TF_- form:wNnnnn | 1574 |
| __prg_map_1:w | 95 | \primitive | 857 |
| __prg_map_2:w | 95 | prop commands: | |
| __prg_map_break:Nn | 95, 95, 282, 315, 411, 445, 2046, 3055, 3057, 4453, 4455, 5914, 6314, 6316, 7466, 7468, 18243, 18245 | \c_empty_prop | 125, 437, 7211, 7215, 7219, 7222, 7382 |
| \g__prg_map_int | 95, 95, 314, 370, 3028, 3029, 3031, 3033, 4484, 4485, 4491, 4492, 4983, 4986, 4990, 4993, 5004, 5913, 6274, 6275, 6277, 6280, 7453, 7454, 7459, 7461, 12664, 12665, 12668, 12669, 18252, 18254, 18261 | \prop_clear:N | 120, 120, 7218, 7225, 16988 |
| __prg_replicate:N | 5853 | prop_clear:N | 120 |
| __prg_replicate_ | 5853 | \prop_clear_new:N | 120, 120, 7224, 16631, 16632 |
| __prg_replicate_0:n | 5853 | \prop_count:N | 215, 215, 18395, 18427 |
| __prg_replicate_1:n | 5853 | \prop_gclear:N | 120, 7218, 7228 |
| __prg_replicate_2:n | 5853 | \prop_gclear_new:N | 120, 7224 |
| __prg_replicate_3:n | 5853 | \prop_get:Nn | 95, 17556, 17557 |
| __prg_replicate_4:n | 5853 | \prop_get:NnN | 83, 84, 121, 121, 122, 7269, 17211, 17215, 17294, 17298 |
| __prg_replicate_5:n | 5853 | \prop_get:NnNTF | 121, 122, 123, 123, 7419, 7428, 7429, 7431, 7432, 7825, 7845, 7900, 16765 |
| __prg_replicate_6:n | 5853 | \prop_gpop:NnN | 121, 121, 7277 |
| __prg_replicate_7:n | 5853 | \prop_gpop:NnNTF | 121, 123, 123, 7312, 7335, 7336 |
| __prg_replicate_8:n | 5853 | \prop_gput:Nnn | 121, 7338, 8537, 8591, 8682, 8714 |
| __prg_replicate_9:n | 5853 | \prop_gput_if_new:Nnn | 121, 7359 |
| __prg_replicate_first:N | 5853 | \prop_gremove:Nn | 122, 7253, 8599, 8722 |
| __prg_replicate_first_:n | 5853 | \prop_gset_eq:NN | 120, 7222, 7230, 16633, 16635, 16789, 16791 |
| __prg_replicate_first_0:n | 5853 | \prop_if_empty:NTF | 122, 122, 7380, 7386, 7387, 7472, 8611, 18424 |
| __prg_replicate_first_1:n | 5853 | \prop_if_empty_p:N | 122, 122, 7380 |
| __prg_replicate_first_2:n | 5853 | \prop_if_exist:NTF | 122, 122, 7225, 7228, 7376, 7472 |
| __prg_replicate_first_3:n | 5853 | \prop_if_exist_p:N | 122, 122, 7376 |
| __prg_replicate_first_4:n | 5853 | \prop_if_in:NnTF | 122, 122, 7389, 7413, 7414, 7415, 7416 |
| __prg_replicate_first_5:n | 5853 | \prop_if_in_p:Nn | 122, 7389 |
| __prg_replicate_first_6:n | 5853 | \prop_item:Nn | 122, 122, 215, 7299, 17556, 17557 |
| __prg_replicate_first_7:n | 5853 | \prop_log:N | 124, 124, 7476 |
| __prg_replicate_first_8:n | 5853 | | |
| __prg_replicate_first_9:n | 5853 | | |
| __prg_set_eq_conditional:NNNn | 1522 | | |
| __prg_set_eq_conditional:nnNnnNnw | 1530, 1538 | | |
| __prg_set_eq_conditional_F_- form:nnn | 1538 | | |
| __prg_set_eq_conditional_F_- form:wNnnnn | 1584 | | |

- \prop_map_break: ... [124](#), [124](#), [780](#),
[7438](#), [7443](#), [7457](#), [7465](#), [18409](#), [18414](#)
- \prop_map_break:n ... [124](#), [124](#), [7465](#)
- \prop_map_function:NN
..... [123](#), [123](#), [215](#), [443](#),
[780](#), [7434](#), [7473](#), [8613](#), [17362](#), [18400](#)
- \prop_map_inline:Nn [123](#), [123](#), [7450](#),
[17059](#), [17078](#), [17263](#), [17272](#), [17997](#),
[17999](#), [18002](#), [18022](#), [18024](#), [18089](#),
[18106](#), [18150](#), [18152](#), [18156](#), [18158](#)
- \prop_map_tokens:Nn . [215](#), [215](#), [18405](#)
- \prop_new:N [120](#), [120](#),
[120](#), [7212](#), [7225](#), [7228](#), [7238](#), [7239](#),
[7240](#), [7241](#), [7689](#), [7799](#), [8523](#), [8668](#),
[16567](#), [16572](#), [17137](#), [17178](#), [17987](#)
- \prop_pop:NnN [121](#), [121](#), [7277](#)
- \prop_pop:NnNTF
..... [121](#), [123](#), [7312](#), [7332](#), [7333](#)
- \prop_put:Nnn
[121](#), [121](#), [125](#), [294](#), [437](#), [7338](#), [7873](#),
[7889](#), [7906](#), [16568](#), [16569](#), [16570](#),
[16571](#), [16574](#), [16575](#), [16576](#), [16578](#),
[16579](#), [16580](#), [16581](#), [16582](#), [16583](#),
[16817](#), [16823](#), [16825](#), [16827](#), [16829](#),
[16834](#), [16839](#), [16844](#), [16851](#), [16858](#),
[17083](#), [17138](#), [17140](#), [17142](#), [17144](#),
[17146](#), [17148](#), [17150](#), [17152](#), [17154](#),
[17156](#), [17158](#), [17160](#), [17162](#), [17164](#),
[17166](#), [17168](#), [17170](#), [17172](#), [18030](#),
[18032](#), [18035](#), [18037](#), [18043](#), [18049](#),
[18116](#), [18124](#), [18187](#), [18201](#), [18208](#)
- \prop_put_if_new:Nnn . [121](#), [121](#), [7359](#)
- \prop_rand_key_value:N [215](#), [215](#), [18420](#)
- \prop_remove:Nn [122](#), [122](#),
[7253](#), [7870](#), [7885](#), [17258](#), [17261](#), [17265](#)
- \prop_set_eq:NN
..... [120](#), [120](#), [7219](#), [7230](#), [16775](#),
[16777](#), [16782](#), [16784](#), [17018](#), [17253](#)
- \prop_show:N [124](#), [124](#), [445](#), [7469](#), [7477](#)
- \g_tmpa_prop [125](#), [7238](#)
- \l_tmpa_prop [125](#), [7238](#)
- \g_tmpb_prop [125](#), [7238](#)
- \l_tmpb_prop [125](#), [7238](#)
- prop internal commands:
 - __prop_count:nn [18395](#)
 - __prop_if_in:N [443](#), [7389](#)
 - __prop_if_in:nwwn [443](#), [7389](#)
 - \l__prop_internal_tl .. [125](#), [441](#),
[441](#), [7210](#), [7342](#), [7348](#), [7349](#), [7365](#), [7372](#)
 - __prop_item_Nn:nwn [440](#)
 - __prop_item_Nn:nwwn [7299](#)
 - __prop_map_function:Nwwn [7434](#)
 - __prop_map_tokens:nwwn .. [780](#), [18405](#)
- __prop_pair:wn ... [125](#), [125](#), [125](#),
[436](#), [436](#), [436](#), [438](#), [438](#), [443](#), [444](#),
[444](#), [7208](#), [7247](#), [7250](#), [7302](#), [7305](#),
[7344](#), [7367](#), [7392](#), [7396](#), [7437](#), [7440](#),
[7453](#), [7455](#), [7460](#), [18408](#), [18411](#), [18431](#)
- __prop_put:Nnn [7338](#)
- __prop_put_if_new:Nnn [7359](#)
- __prop_rand:NN [18420](#)
- __prop_rand:nNn [18420](#), [18421](#)
- __prop_rand_item:Nw [18420](#)
- __prop_split:NnTF
..... [125](#), [125](#), [441](#), [441](#), [441](#),
[442](#), [7242](#), [7255](#), [7261](#), [7271](#), [7279](#),
[7288](#), [7314](#), [7324](#), [7347](#), [7370](#), [7421](#)
- __prop_split_aux:NnTF [7242](#)
- __prop_split_aux:w .. [438](#), [438](#), [7242](#)
- \protect [11291](#), [18838](#), [18865](#)
- \protected [207](#),
[209](#), [211](#), [236](#), [484](#), [654](#), [6928](#), [6930](#)
- \protrudechars [964](#)
- \ProvidesExplClass [6](#)
- \ProvidesExplFile [6](#), [19765](#)
- \ProvidesExplPackage [6](#), [6](#)
- pt [188](#)
- ptex commands:
 - \ptex_autospacing:D [1120](#)
 - \ptex_autoxspacing:D [1121](#)
 - \ptex_dtou:D [1122](#)
 - \ptex_euc:D [1123](#)
 - \ptex_ifdbbox:D [1124](#)
 - \ptex_ifddir:D [1125](#)
 - \ptex_ifmdir:D [1126](#)
 - \ptex_iftbody:D [1127](#)
 - \ptex_iftdir:D [1128](#)
 - \ptex_ifybox:D [1129](#)
 - \ptex_ifydir:D [1130](#)
 - \ptex_inhibitglue:D [1131](#)
 - \ptex_inhibitxspcode:D [1132](#)
 - \ptex_jcharwidowpenalty:D [1133](#)
 - \ptex_jfam:D [1134](#)
 - \ptex_jfont:D [1135](#)
 - \ptex_jis:D [1136](#), [4712](#), [17475](#)
 - \ptex_kanjiskip:D [1137](#), [17470](#)
 - \ptex_kansuji:D [1138](#)
 - \ptex_kansujichar:D [1139](#)
 - \ptex_kcatcode:D [1140](#)
 - \ptex_kuten:D [1141](#)
 - \ptex_noautospacing:D [1142](#)
 - \ptex_noautoxspacing:D [1143](#)
 - \ptex_postbreakpenalty:D [1144](#)
 - \ptex_prebreakpenalty:D [1145](#)
 - \ptex_showmode:D [1146](#)
 - \ptex_sjis:D [1147](#)
 - \ptex_tate:D [1148](#)

`\ptex_tbaselineshift:D` 1149
`\ptex_tfont:D` 1150
`\ptex_xkanjiskip:D` 1151
`\ptex_xspcode:D` 1152
`\ptex_ybaselineshift:D` 1153
`\ptex_yoko:D` 1154
`\pxdimen` 965

Q

quark commands:

`\q_mark` 23, 23, 46, 46, 84, 269,
 269, 269, 293, 294, 307, 307, 314,
 314, 317, 317, 317, 317, 331, 331,
 338, 392, 402, 402, 404, 404, 406,
 406, 406, 407, 407, 412, 412, 412,
 438, 505, 719, 719, 719, 720, 722,
 1604, 1605, 1611, 1613, 1614, 2341,
 2342, 2344, 2351, 2357, 2381, 2390,
 2404, 2412, 2415, 2424, 2439, 2461,
 2482, 2485, 2498, 2793, 2795, 2797,
 2799, 2998, 3009, 3085, 3086, 3089,
 3092, 3093, 3099, 3113, 3114, 3120,
 3124, 3126, 3129, 3551, 3583, 3594,
 3611, 3855, 3857, 4535, 4536, 4550,
 4553, 4802, 4805, 4871, 5506, 5736,
 5737, 5738, 5739, 5742, 5743, 5744,
 5745, 5746, 5747, 5748, 5998, 6007,
 6012, 6067, 6077, 6081, 6105, 6157,
 6163, 6176, 6188, 6189, 6190, 6193,
 6194, 6195, 6204, 6205, 6214, 6259,
 6267, 6355, 6356, 6368, 6369, 6432,
 7247, 7249, 7250, 7830, 7831, 7836,
 7839, 8959, 8966, 8978, 9240, 9524,
 9531, 9541, 9565, 9587, 9597, 9607,
 11211, 11212, 11217, 16217, 16252,
 16254, 16257, 16261, 16264, 16267,
 16269, 16272, 19665, 19666, 19673
`\q_nil` .. 19, 19, 84, 84, 84, 84, 262,
 307, 310, 310, 310, 310, 317, 384,
 386, 386, 386, 392, 392, 392, 1398,
 1401, 2819, 2897, 2898, 2910, 2911,
 3112, 3116, 3134, 3137, 3140, 3228,
 3229, 5506, 5559, 5580, 5582, 5735,
 5737, 5738, 5742, 5743, 5744, 5745,
 5746, 5747, 9541, 9551, 9565, 9575
`\q_no_value`
 58, 59, 59, 59, 59, 59, 64, 64,
 64, 83, 84, 84, 84, 84, 102, 121, 121,
 121, 136, 351, 352, 384, 386, 404,
 439, 439, 471, 4316, 4324, 4336,
 4360, 5506, 5567, 5586, 5588, 5794,
 6050, 6065, 7273, 7284, 7293, 8405
`\quark_if_nil:n` 386, 386, 386
`\quark_if_nil:NTF` 84, 84, 5557

`\quark_if_nil:NTF`
 .. 84, 84, 385, 2817, 5577, 5591, 5592
`\quark_if_nil_p:N` 84, 84, 5557
`\quark_if_nil_p:n` 84, 84, 5577
`\quark_if_no_value:NTF` 84,
 84, 5557, 5574, 5575, 5799, 8436,
 8548, 8560, 17213, 17217, 17296, 17300
`\quark_if_no_value:NTF` .. 84, 84, 5577
`\quark_if_no_value_p:N` .. 84, 84, 5557
`\quark_if_no_value_p:n` .. 84, 84, 5577
`\quark_if_recursion_tail_break:N`
 17558
`\quark_if_recursion_tail_break:n`
 17559
`\quark_if_recursion_tail_stop:N` .
 85, 85, 5339, 5512, 6308, 19371
`\quark_if_recursion_tail_stop:n` .
 . 85, 85, 325, 5526, 6003, 6338, 19204
`quark_if_recursion_tail_stop:n` . 385
`\quark_if_recursion_tail_stop_-`
`do:Nn` 85, 85,
 3893, 5278, 5295, 5342, 5512, 18659,
 18667, 18826, 18846, 19441, 19449
`\quark_if_recursion_tail_stop_-`
`do:nn`
 ... 85, 85, 5526, 18368, 18383, 19494
`\quark_new:N` 83, 83, 5505, 5506, 5507,
 5508, 5509, 5510, 5511, 5593, 5594
`\q_recursion_stop` 19,
 19, 85, 85, 85, 85, 85, 86, 262, 266,
 384, 1400, 1403, 1467, 1535, 2331,
 2655, 3871, 3878, 3883, 4071, 5273,
 5290, 5333, 5360, 5510, 5999, 6296,
 6332, 18365, 18380, 18617, 18620,
 18629, 18640, 18650, 18657, 18663,
 18682, 18684, 18693, 18695, 18702,
 18703, 18706, 18709, 18722, 18820,
 18842, 18864, 18890, 18895, 18898,
 18900, 18903, 18906, 18911, 18932,
 18935, 18937, 18939, 18944, 19025,
 19029, 19031, 19036, 19050, 19075,
 19079, 19081, 19086, 19094, 19343,
 19389, 19408, 19411, 19420, 19422,
 19432, 19439, 19445, 19467, 19471,
 19474, 19475, 19490, 19506, 19508,
 19529, 19533, 19535, 19540, 19555
`\q_recursion_tail` 85, 85, 85, 85, 85,
 85, 85, 85, 85, 86, 86, 86, 266, 384,
 385, 409, 443, 444, 444, 780, 1467,
 1472, 1535, 1554, 2631, 2655, 3015,
 3032, 3041, 3367, 3871, 4061, 4071,
 5273, 5290, 5333, 5510, 5514, 5520,
 5529, 5536, 5541, 5546, 5553, 5999,
 6245, 6259, 6278, 6296, 6332, 7393,

- 7404, 7437, 7442, 9524, 9531, 9592,
18365, 18380, 18408, 18413, 18617,
18663, 18697, 18820, 18842, 18873,
19342, 19388, 19408, 19445, 19490
- `\q_stop` 19, 19,
23, 23, 29, 44, 83, 84, 84, 84, 262,
269, 294, 307, 316, 331, 335, 365,
376, 376, 384, 407, 407, 407, 412,
427, 429, 438, 463, 720, 720, 722,
1399, 1402, 1483, 1488, 1505, 1511,
1517, 1565, 1569, 1574, 1579, 1584,
1606, 1611, 1613, 1614, 2345, 2358,
2385, 2412, 2416, 2420, 2428, 2434,
2443, 2461, 2488, 2499, 2818, 2970,
2976, 2998, 3009, 3087, 3089, 3094,
3096, 3118, 3140, 3219, 3221, 3238,
3256, 3275, 3297, 3551, 3583, 3594,
3603, 3609, 3611, 3617, 3634, 3653,
3712, 3768, 3780, 3818, 3834, 3841,
3849, 3851, 3855, 3857, 3981, 3986,
3989, 3993, 4011, 4024, 4035, 4039,
4042, 4044, 4045, 4048, 4051, 4336,
4339, 4347, 4349, 4429, 4430, 4537,
4550, 4553, 4555, 4781, 4797, 4799,
4803, 4816, 4871, 5266, 5272, 5289,
5506, 5740, 5748, 5794, 5797, 6052,
6055, 6067, 6070, 6078, 6081, 6089,
6105, 6163, 6190, 6193, 6194, 6206,
6214, 6357, 6368, 6369, 6370, 6396,
6430, 6844, 6847, 6879, 6913, 6948,
6952, 6958, 6981, 7175, 7182, 7191,
7200, 7247, 7250, 7832, 8286, 8303,
8887, 8944, 8982, 8995, 9043, 9044,
9191, 9217, 9240, 9415, 9417, 9595,
9610, 9632, 9646, 9647, 9712, 9714,
9734, 9738, 9747, 9755, 9768, 10173,
10181, 10191, 10318, 10320, 10325,
11212, 11217, 11326, 11331, 15728,
15799, 16205, 16214, 16218, 16220,
16252, 16253, 16254, 16259, 16261,
16265, 16267, 16275, 18361, 18428,
18441, 18442, 18444, 18448, 18452,
18454, 18459, 19654, 19667, 19676
- quark internal commands:
- `\s__fp` 530,
530, 530, 530, 530, 531, 532, 532,
532, 532, 562, 563, 566, 579, 579,
581, 605, 608, 608, 610, 610, 610,
613, 618, 618, 621, 621, 701, 10460,
10473, 10474, 10475, 10476, 10477,
10485, 10487, 10490, 10496, 10500,
10521, 10524, 10526, 10536, 10546,
10558, 10578, 10650, 10652, 10654,
10655, 10656, 10658, 10659, 10660,
10662, 10688, 10862, 10867, 11069,
11115, 11124, 11126, 11772, 11893,
12133, 12481, 12506, 12507, 12626,
12639, 12643, 12683, 12684, 12687,
12698, 12699, 12707, 12708, 12710,
12711, 12712, 12714, 12715, 12716,
12727, 12730, 12742, 12768, 12816,
12819, 12822, 12842, 12843, 12845,
12846, 12847, 12855, 12858, 12874,
12875, 12877, 12886, 12962, 13114,
13148, 13149, 13152, 13231, 13367,
13375, 13377, 13554, 13557, 14015,
14027, 14029, 14237, 14254, 14256,
14445, 14464, 14466, 14467, 14470,
14487, 14490, 14493, 14518, 14519,
14521, 14537, 14622, 14635, 14637,
14640, 14645, 14680, 14693, 14695,
14708, 14710, 14723, 14725, 14738,
14740, 14753, 14755, 14768, 14778,
15210, 15226, 15227, 15231, 15242,
15348, 15361, 15363, 15379, 15382,
15392, 15415, 15426, 15428, 15442,
15444, 15449, 15477, 15501, 15504,
15521, 15545, 15548, 15589, 15605,
15608, 15665, 15666, 15793, 15795
- `\s__fp_division` 10468
- `\s__fp_exact` 10468, 10473,
10474, 10475, 10476, 10477, 12683
- `\s__fp_invalid` 10468
- `\s__fp_mark` 543, 562, 562,
566, 587, 589, 597, 10466, 10742,
10743, 10745, 10749, 12002, 12043,
12434, 12435, 12438, 12441, 12442
- `\s__fp_overflow` 10468, 10487
- `\s__fp_stop` 10466, 11855,
12003, 12006, 12436, 12441, 12442,
12444, 12746, 12757, 12781, 12789
- `\s__fp_underflow` 10468, 10485
- `\s__prop` 125, 125, 436, 436,
436, 436, 438, 438, 444, 444, 780,
7207, 7208, 7211, 7247, 7250, 7302,
7305, 7345, 7368, 7392, 7396, 7437,
7440, 7455, 18408, 18411, 18431, 18436
- `__quark_if_nil:w` 386, 386, 5577
- `__quark_if_no_value:w` 5577
- `__quark_if_recursion_tail:w` ...
..... 385, 5526, 5553
- `__quark_if_recursion_tail_-
break:NN` 86, 3049, 5544
- `__quark_if_recursion_tail_-
break:nN` 86,
86, 3022, 3378, 5544, 6251, 6264
- `\s__seq` 67, 343,
346, 347, 347, 352, 357, 713, 781,

- [4077](#), [4085](#), [4115](#), [4120](#), [4125](#), [4130](#),
[4163](#), [4189](#), [4197](#), [4201](#), [4380](#), [4430](#),
[4547](#), [5611](#), [16049](#), [16056](#), [18442](#), [18448](#)
\ s__stop [87](#),
[87](#), [87](#), [87](#), [720](#), [5609](#), [5610](#), [14315](#),
[14330](#), [15464](#), [15468](#), [16218](#), [16220](#)
\ q__tl_act_mark
[318](#), [318](#), [318](#), [3144](#), [3147](#), [3164](#), [5593](#)
\ q__tl_act_stop
[318](#), [3144](#), [3147](#), [3151](#), [3160](#), [3162](#),
[3168](#), [3173](#), [3176](#), [3180](#), [3183](#), [5593](#)
\ quitvmode [784](#)
- ### R
- \ r [19395](#)
\ radical [517](#)
\ raise [518](#)
rand [187](#)
randint [187](#)
\ randomseed [966](#)
\ read [519](#)
\ readline [655](#)
\ ref [19566](#)
\ relax [14](#), [21](#), [39](#), [43](#), [49](#),
[90](#), [92](#), [98](#), [123](#), [146](#), [167](#), [181](#), [212](#),
[213](#), [214](#), [215](#), [216](#), [217](#), [218](#), [219](#),
[220](#), [221](#), [222](#), [225](#), [226](#), [227](#), [228](#),
[229](#), [230](#), [231](#), [232](#), [233](#), [234](#), [235](#), [520](#)
\ relpenalty [521](#)
\ RequirePackage [149](#)
reverse commands:
\ reverse_if:N ... [21](#), [21](#), [337](#), [365](#),
[365](#), [366](#), [565](#), [1294](#), [3848](#), [3988](#),
[4829](#), [4831](#), [4833](#), [4835](#), [9205](#), [9210](#),
[9214](#), [9216](#), [11244](#), [14507](#), [15148](#), [15171](#)
\ right [522](#)
right commands:
\ c_right_brace_str [55](#), [3922](#)
\ rightghost [945](#)
\ righthyphenmin [523](#)
\ rightmarginkern [785](#)
\ rightskip [524](#)
\ romannumeral [525](#)
round [184](#)
round+ [11976](#)
round- [11976](#)
round0 [11976](#)
\ rpcode [786](#)
\ rule [17195](#), [17250](#)
- ### S
- \ saveboxresource [970](#)
\ savecatcodetable [922](#)
\ saveimageresource [971](#)
\ savepos [969](#)
\ savinghyphcodes [656](#)
\ savingvdiscards [657](#)
scan commands:
\ scan_align_safe_stop: [17560](#)
\ scan_stop: .. [9](#), [9](#), [67](#), [86](#), [87](#), [116](#),
[116](#), [116](#), [117](#), [252](#), [266](#), [270](#), [270](#),
[270](#), [273](#), [285](#), [285](#), [303](#), [303](#), [316](#),
[337](#), [337](#), [365](#), [370](#), [387](#), [426](#), [426](#),
[433](#), [435](#), [436](#), [444](#), [463](#), [562](#), [565](#),
[566](#), [566](#), [567](#), [570](#), [810](#), [1321](#), [1490](#),
[1622](#), [1640](#), [1650](#), [1668](#), [2098](#), [2331](#),
[2372](#), [2414](#), [2710](#), [2734](#), [3849](#), [3944](#),
[3957](#), [3962](#), [3963](#), [3964](#), [4027](#), [4378](#),
[5004](#), [5606](#), [6784](#), [6858](#), [7070](#), [7184](#),
[7193](#), [7202](#), [8530](#), [8532](#), [8590](#), [8592](#),
[8675](#), [8677](#), [8713](#), [8715](#), [9379](#), [9390](#),
[9395](#), [9421](#), [9427](#), [9430](#), [9477](#), [9488](#),
[9493](#), [9498](#), [9551](#), [9575](#), [9612](#), [9616](#),
[9617](#), [9634](#), [9635](#), [11242](#), [11246](#),
[11405](#), [11422](#), [11722](#), [11769](#), [11770](#),
[12041](#), [12071](#), [12313](#), [12669](#), [15970](#),
[16486](#), [17191](#), [17246](#), [17578](#), [18494](#),
[18495](#), [18567](#), [18570](#), [18591](#), [19686](#),
[19688](#), [19690](#), [19798](#), [19804](#), [19839](#)
scan internal commands:
\ g__scan_marks_tl ... [5596](#), [5599](#), [5605](#)
\ __scan_new:N . [87](#), [87](#), [5597](#), [5609](#),
[5611](#), [7207](#), [10460](#), [10466](#), [10467](#),
[10468](#), [10469](#), [10470](#), [10471](#), [10472](#)
\ scantexttokens [923](#)
\ scantokens [658](#)
\ scriptfont [526](#)
\ scriptscriptfont [527](#)
\ scriptscriptstyle [528](#)
\ scriptspace [529](#)
\ scriptstyle [530](#)
\ scrollmode [531](#)
sec [185](#)
secd [185](#)
seq commands:
\ c_empty_seq [66](#), [344](#), [4085](#),
[4089](#), [4093](#), [4096](#), [4278](#), [4315](#), [4323](#)
\ seq_clear:N [57](#),
[57](#), [66](#), [4092](#), [4099](#), [4222](#), [7828](#), [7891](#)
seq_clear:N [57](#)
\ seq_clear_new:N [57](#), [57](#), [4098](#)
\ seq_concat:NNN
..... [58](#), [58](#), [66](#), [66](#), [4175](#), [8412](#)
\ seq_count:N [59](#),
[63](#), [63](#), [65](#), [4441](#), [4513](#), [4527](#), [18486](#)
\ seq_elt:w [344](#), [344](#)
\ seq_elt_end: [344](#), [344](#)
\ seq_gclear:N [57](#), [4092](#), [4102](#)

- `\seq_gclear_new:N` [57](#), [4098](#)
- `\seq_gconcat:NNN` [58](#), [4175](#)
- `\seq_get:NN` [64](#), [64](#), [4580](#)
- `\seq_get:NNTF` [64](#), [64](#), [4586](#)
- `\seq_get_left:NN`
 . [58](#), [58](#), [4331](#), [4580](#), [4581](#), [4586](#), [4587](#)
- `\seq_get_left:NNTF`
 [60](#), [60](#), [4398](#), [4402](#), [4403](#)
- `\seq_get_right:NN` [59](#), [59](#), [4356](#)
- `\seq_get_right:NNTF`
 [60](#), [60](#), [4398](#), [4405](#), [4406](#)
- `\seq_gpop:NN` [64](#), [64](#), [4580](#), [8474](#)
- `\seq_gpop:NNTF` [65](#), [65](#), [4586](#), [8574](#), [8697](#)
- `\seq_gpop_left:NN`
 . [59](#), [59](#), [4342](#), [4584](#), [4585](#), [4590](#), [4591](#)
- `\seq_gpop_left:NNTF`
 [60](#), [60](#), [4408](#), [4419](#), [4420](#)
- `\seq_gpop_right:NN` [59](#), [59](#), [4371](#)
- `\seq_gpop_right:NNTF`
 [60](#), [60](#), [4408](#), [4425](#), [4426](#)
- `\seq_gpush:Nn`
 [24](#), [65](#), [4560](#), [8471](#), [8601](#), [8724](#)
- `\seq_gput_left:Nn`
 . [58](#), [4185](#), [4570](#), [4571](#), [4572](#), [4573](#),
 [4574](#), [4575](#), [4576](#), [4577](#), [4578](#), [4579](#)
- `\seq_gput_right:Nn`
 [58](#), [4206](#), [8339](#), [8464](#), [8469](#), [8512](#)
- `\seq_gremove_all:Nn` [61](#), [4232](#)
- `\seq_gremove_duplicates:N` .. [61](#), [4216](#)
- `\seq_greverse:N` [61](#), [4258](#)
- `\seq_gset_eq:NN` . [57](#), [4096](#), [4104](#), [4219](#)
- `\seq_gset_filter:NNn` [215](#), [18463](#)
- `\seq_gset_from_clist:NN` [57](#), [4112](#)
- `\seq_gset_from_clist:Nn` [57](#), [4112](#)
- `\seq_gset_map:NNn` [216](#), [18473](#)
- `\seq_gset_split:Nnn`
 [58](#), [4138](#), [8519](#), [8660](#)
- `\seq_gsort:Nn` [61](#), [4276](#), [16045](#)
- `\seq_if_empty:NNTF` [61](#),
 [61](#), [4276](#), [4285](#), [4286](#), [4595](#), [5947](#), [18485](#)
- `\seq_if_empty_p:N` [61](#), [61](#), [4276](#)
- `\seq_if_exist:NNTF`
 . [58](#), [58](#), [4099](#), [4102](#), [4181](#), [4525](#), [4595](#)
- `\seq_if_exist_p:N` [58](#), [58](#), [4181](#)
- `\seq_if_in:NnTF` [61](#),
 [61](#), [65](#), [65](#), [66](#), [66](#), [4225](#), [4288](#), [4307](#),
 [4308](#), [4309](#), [4310](#), [8482](#), [8600](#), [8723](#)
- `\seq_item:Nn` [59](#),
 [59](#), [783](#), [4428](#), [7909](#), [7910](#), [7915](#), [18486](#)
- `\seq_log:N` [67](#), [67](#), [4599](#)
- `\seq_map_break:`
 [62](#), [62](#), [215](#), [216](#), [4452](#),
 [4462](#), [4463](#), [4498](#), [4509](#), [8422](#), [10218](#)
- `\seq_map_break:n` [63](#),
 [63](#), [355](#), [4452](#), [7848](#), [7862](#), [16048](#), [16055](#)
- `\seq_map_function:NN` [4](#), [61](#), [61](#), [61](#),
 [465](#), [466](#), [4456](#), [4518](#), [4596](#), [5953](#), [7913](#)
- `\seq_map_inline:Nn` [61](#), [62](#), [62](#), [66](#), [66](#),
 [66](#), [66](#), [66](#), [782](#), [4223](#), [4494](#), [7843](#),
 [8354](#), [8416](#), [8505](#), [10211](#), [16048](#), [16055](#)
- `\seq_map_variable:NNn` .. [62](#), [62](#), [4501](#)
- `\seq_mapthread_function:NNN`
 [215](#), [215](#), [18440](#)
- `\seq_new:N` [4](#), [57](#), [57](#), [57](#), [4086](#), [4099](#),
 [4102](#), [4215](#), [4602](#), [4603](#), [4604](#), [4605](#),
 [6571](#), [6574](#), [7800](#), [7801](#), [8333](#), [8334](#),
 [8344](#), [8346](#), [8349](#), [8517](#), [8656](#), [9673](#)
- `\seq_pop:NN` [64](#), [64](#), [4580](#)
- `\seq_pop:NNTF` [65](#), [65](#), [4586](#)
- `\seq_pop_left:NN`
 . [59](#), [59](#), [4342](#), [4582](#), [4583](#), [4588](#), [4589](#)
- `\seq_pop_left:NNTF`
 [60](#), [60](#), [4408](#), [4416](#), [4417](#)
- `\seq_pop_right:NN` [59](#), [59](#), [4371](#)
- `\seq_pop_right:NNTF`
 [60](#), [60](#), [4408](#), [4422](#), [4423](#)
- `\seq_push:Nn` [65](#), [65](#), [4560](#), [4567](#)
- `\seq_put_left:Nn` [58](#), [58](#),
 [4185](#), [4560](#), [4561](#), [4562](#), [4563](#), [4564](#),
 [4565](#), [4566](#), [4567](#), [4568](#), [4569](#), [7838](#)
- `\seq_put_right:Nn` [58](#), [58](#),
 [65](#), [66](#), [66](#), [4206](#), [4226](#), [7899](#), [8483](#), [8498](#)
- `\seq_rand_item:N` [216](#), [216](#), [18483](#)
- `\seq_remove_all:Nn` [58](#),
 [61](#), [61](#), [65](#), [65](#), [66](#), [66](#), [4232](#), [8488](#)
- `\seq_remove_duplicates:N`
 [61](#), [61](#), [65](#), [66](#), [4216](#), [8503](#)
- `\seq_reverse:N` [61](#), [61](#), [349](#), [4258](#)
- `\seq_set_eq:NN` . [57](#), [57](#), [66](#), [66](#), [66](#),
 [66](#), [4093](#), [4104](#), [4217](#), [8409](#), [8428](#), [8492](#)
- `\seq_set_filter:NNn`
 [215](#), [215](#), [782](#), [18463](#)
- `\seq_set_from_clist:NN` .. [57](#), [57](#), [4112](#)
- `\seq_set_from_clist:Nn`
 [57](#), [4112](#), [10140](#), [10149](#)
- `\seq_set_map:NNn` [216](#), [216](#), [18473](#)
- `\seq_set_split:Nnn`
 ... [58](#), [58](#), [58](#), [4138](#), [6572](#), [6575](#), [8411](#)
- `\seq_show:N` ... [67](#), [67](#), [359](#), [4592](#), [4600](#)
- `\seq_sort:Nn` [61](#), [61](#), [4276](#), [16045](#)
- `\seq_use:Nn` [64](#), [64](#), [4523](#)
- `\seq_use:Nnnn` [63](#), [63](#), [4523](#)
- `\g_tmpa_seq` [67](#), [4602](#)
- `\l_tmpa_seq` [67](#), [4602](#)
- `\g_tmpb_seq` [67](#), [4602](#)
- `\l_tmpb_seq` [67](#), [4602](#)

seq internal commands:

__seq_count:n [4513](#)
 __seq_get_left:wnw [4331](#)
 __seq_get_right_loop:nn .. [352](#), [4356](#)
 __seq_if_in: [4288](#)
 \l__seq_internal_a_tl
 [346](#), [4082](#), [4146](#), [4150](#), [4156](#),
 [4161](#), [4163](#), [4247](#), [4252](#), [4292](#), [4296](#)
 \l__seq_internal_b_tl
 [4082](#), [4243](#), [4247](#), [4295](#), [4296](#)
 __seq_item:n
 67, 67, 67, 67, 343, 343, 347, 350,
 350, 351, 352, 353, 355, 355, 355,
 356, 356, 357, 357, 713, 714, 714,
 781, 782, [4077](#), 4189, 4197, 4207,
 4209, 4214, 4264, 4265, 4267, 4272,
 4293, 4336, 4339, 4349, 4377, 4378,
 4389, 4475, 4480, 4486, 4490, 4534,
 4549, 4552, 4555, 16049, 16056, 18479
 __seq_item:nN [4428](#)
 __seq_item:nnn [4428](#)
 __seq_item:wNn [4428](#)
 __seq_map_function:NNn [4456](#)
 __seq_mapthread_function:Nnnwnn
 [18440](#)
 __seq_mapthread_function:wNN . [18440](#)
 __seq_mapthread_function:wNw . [18440](#)
 __seq_pop:NNNN
 [4313](#), [4343](#), [4345](#), [4372](#), [4374](#)
 __seq_pop_item_def: . 67, 67, 67,
 [4254](#), [4472](#), [4498](#), [4509](#), 18471, 18481
 __seq_pop_left:NNN . [4342](#), 4409, 4411
 __seq_pop_left:wnwNNN [4342](#)
 __seq_pop_right:NNN
 [348](#), [4371](#), [4413](#), [4415](#)
 __seq_pop_right_loop:nn [4371](#)
 __seq_pop_TF:NNNN [353](#), [4313](#),
 [4399](#), [4401](#), [4409](#), [4411](#), [4413](#), [4415](#)
 __seq_push_item_def: [4472](#)
 __seq_push_item_def:n
 67, 67, 67, 67,
 [4238](#), [4472](#), [4496](#), [4503](#), 18469, 18479
 __seq_put_left_aux:w [347](#), [4185](#)
 __seq_remove_all_aux:NNn [4232](#)
 __seq_remove_duplicates:NN .. [4216](#)
 \l__seq_remove_seq
 [4215](#), [4222](#), [4225](#), [4226](#), [4228](#)
 __seq_reverse:NN [4258](#)
 __seq_reverse_item:nw [349](#), [349](#)
 __seq_reverse_item:nwn [4258](#)
 __seq_set_filter:NNNn [18463](#)
 __seq_set_map:NNNn [18473](#)
 __seq_set_split:NNnn [4138](#)
 __seq_set_split_auxi:w [346](#), [346](#), [4138](#)

__seq_set_split_auxii:w .. [346](#), [4138](#)
 __seq_set_split_end: [346](#), [346](#), [4138](#)
 __seq_tmp:w
 [4084](#), [4264](#), [4267](#), [4377](#), [4389](#)
 __seq_use:NNnNnn [4523](#)
 __seq_use:nwnn [4523](#)
 __seq_use:nwwwwnwn [4523](#)
 __seq_use_setup:w [4523](#)
 __seq_wrap_item:n
 [346](#), [782](#), [4115](#), [4120](#), [4125](#),
 [4130](#), [4147](#), [4172](#), [4214](#), [4250](#), 18469
 \setbox [532](#)
 \setfontid [924](#)
 \setlanguage [533](#)
 \setrandomseed [972](#)
 \sfcode [183](#), [534](#)
 \sffamily [17184](#)
 \shapemode [925](#)
 \shellescape [858](#)
 \shipout [535](#)
 \ShortText [75](#), [116](#), [133](#)
 \show [536](#)
 \showbox [537](#)
 \showboxbreadth [538](#)
 \showboxdepth [539](#)
 \showgroups [659](#)
 \showifs [660](#)
 \showlists [540](#)
 \showmode [1146](#)
 \showthe [541](#)
 \showtokens [661](#)
 sin [185](#)
 sind [185](#)
 \sjis [1147](#)
 \skewchar [542](#)
 \skip [543](#), [6934](#)
 skip commands:
 \c_max_skip [154](#), [9441](#)
 \skip_add:Nn [152](#), [152](#), [9389](#)
 \skip_const:Nn
 [152](#), [152](#), [9358](#), [9441](#), [9442](#)
 \skip_eval:n [153](#),
 [153](#), [153](#), [153](#), [9402](#), [9420](#), [9436](#)
 \skip_gadd:Nn [152](#), [9389](#)
 .skip_gset:N [163](#), [10067](#)
 \skip_gset:Nn [152](#), [9361](#), [9378](#)
 \skip_gset_eq:NN [152](#), [9383](#)
 \skip_gsub:Nn [153](#), [9389](#)
 \skip_gzero:N [152](#), [9364](#), [9371](#)
 \skip_gzero_new:N [152](#), [9368](#)
 \skip_horizontal:N [154](#), [154](#), [154](#), [9425](#)
 \skip_horizontal:n
 . [154](#), [154](#), [9425](#), 19901, 20179, 20567
 \skip_if_eq:nnTF [153](#), [9399](#)

- \skip_if_eq_p:nn [153](#), [153](#), [9399](#)
- \skip_if_exist:NTF
 [152](#), [152](#), [9369](#), [9371](#), [9374](#)
- \skip_if_exist_p:N ... [152](#), [152](#), [9374](#)
- \skip_if_finite:nTF
 [153](#), [153](#), [9409](#), [18492](#)
- \skip_if_finite_p:n .. [153](#), [153](#), [9409](#)
- \skip_log:N [154](#), [154](#), [9437](#)
- \skip_log:n [154](#), [154](#), [9437](#)
- \skip_new:N [152](#), [152](#), [152](#), [9350](#), [9360](#),
 [9369](#), [9371](#), [9443](#), [9444](#), [9445](#), [9446](#)
- .skip_set:N [163](#), [10067](#)
- \skip_set:Nn [152](#), [152](#), [9378](#)
- \skip_set_eq:NN [152](#), [152](#), [9383](#)
- \skip_show:N [153](#), [153](#), [9433](#)
- \skip_show:n [154](#), [154](#), [501](#), [9435](#), [9440](#)
- \skip_split_finite_else_action:nnNN
 [216](#), [216](#), [18490](#)
- \skip_sub:Nn [153](#), [153](#), [9389](#)
- \skip_use:N
 . [153](#), [153](#), [153](#), [153](#), [9414](#), [9421](#), [9422](#)
- \skip_vertical:N .. [155](#), [155](#), [155](#), [9425](#)
- \skip_vertical:n [155](#), [155](#), [9425](#)
- \skip_zero:N [152](#), [152](#), [155](#), [9364](#), [9369](#)
- skip_zero:N [152](#)
- \skip_zero_new:N [152](#), [152](#), [9368](#)
- \g_tmpa_skip [154](#), [9443](#)
- \l_tmpa_skip [154](#), [9443](#)
- \g_tmpb_skip [154](#), [9443](#)
- \l_tmpb_skip [154](#), [9443](#)
- \c_zero_skip
 [154](#), [9364](#), [9441](#), [18498](#), [18499](#)
- skip internal commands:
 _skip_if_finite:wwNw [9409](#)
- \skipdef [544](#)
- sort commands:
 \sort_ordered: [16334](#), [17576](#)
- \sort_return_same: [191](#), [191](#),
 [716](#), [16151](#), [16339](#), [16340](#), [16341](#), [17576](#)
- \sort_return_swapped: .. [191](#), [191](#),
 [716](#), [16151](#), [16348](#), [16349](#), [16350](#), [17577](#)
- \sort_reversed: [16334](#), [17577](#)
- sort internal commands:
 _sort:nnNnn . [718](#), [718](#), [718](#), [718](#), [719](#)
- \l__sort_A_int
 [716](#), [15934](#), [15939](#), [15946](#),
 [15949](#), [15958](#), [16116](#), [16121](#), [16124](#),
 [16144](#), [16159](#), [16178](#), [16180](#), [16181](#)
- \l__sort_B_int
 ... [716](#), [716](#), [15934](#), [16121](#), [16125](#),
 [16133](#), [16135](#), [16136](#), [16168](#), [16169](#),
 [16178](#), [16179](#), [16188](#), [16189](#), [16191](#)
- \l__sort_begin_int [710](#),
 [716](#), [716](#), [15932](#), [16113](#), [16181](#), [16191](#)
- \l__sort_block_int
 [710](#), [710](#), [715](#), [15931](#), [15941](#),
 [15946](#), [15950](#), [15953](#), [15958](#), [15959](#),
 [16037](#), [16104](#), [16107](#), [16114](#), [16117](#)
- \l__sort_C_int
 [716](#), [716](#), [15934](#), [16122](#),
 [16126](#), [16133](#), [16134](#), [16145](#), [16160](#),
 [16168](#), [16170](#), [16171](#), [16188](#), [16190](#)
- _sort_clist:NNn [16073](#)
- _sort_compare:nn . [717](#), [16036](#), [16143](#)
- _sort_compute_range:
 [709](#), [710](#), [711](#), [15963](#), [16024](#)
- _sort_copy_block: [715](#), [16123](#), [16131](#)
- _sort_disable_toksdef: [16023](#), [16283](#)
- _sort_disabled_toksdef:n ... [16283](#)
- \l__sort_end_int [710](#), [715](#), [716](#), [716](#),
 [15932](#), [16105](#), [16113](#), [16114](#), [16115](#),
 [16116](#), [16117](#), [16118](#), [16119](#), [16136](#)
- _sort_error: .. [16277](#), [16290](#), [16308](#)
- _sort_i:nnnnNn [719](#)
- \l__sort_length_int
 [709](#), [710](#), [15926](#), [16034](#), [16104](#)
- _sort_level: [722](#), [16038](#), [16102](#), [16281](#)
- _sort_loop:wNn [719](#), [719](#), [719](#), [719](#), [719](#)
- _sort_main:NNnnNn .. [713](#), [16020](#),
 [16047](#), [16054](#), [16061](#), [16068](#), [16083](#)
- \l__sort_max_int [709](#),
 [710](#), [710](#), [15926](#), [15943](#), [16017](#), [16028](#)
- \c__sort_max_length_int [15963](#)
- _sort_merge_blocks:
 [16106](#), [16111](#), [16280](#)
- _sort_merge_blocks_aux:
 [715](#), [16127](#), [16141](#), [16174](#), [16184](#), [16279](#)
- _sort_merge_blocks_end:
 [717](#), [16182](#), [16186](#)
- \l__sort_min_int ... [709](#), [710](#), [712](#),
 [714](#), [15926](#), [15940](#), [15948](#), [15966](#),
 [15982](#), [15990](#), [16003](#), [16015](#), [16025](#),
 [16035](#), [16093](#), [16105](#), [16306](#), [16307](#)
- _sort_quick_cleanup:w [16196](#)
- _sort_quick_end:nnTFNn
 [721](#), [721](#), [16216](#), [16251](#)
- _sort_quick_only_i:NnnnnNn . [16221](#)
- _sort_quick_only_i_end:nnnwnw .
 [16230](#), [16251](#)
- _sort_quick_only_ii:NnnnnNn . [16221](#)
- _sort_quick_only_ii_end:nnnwnw
 [16236](#), [16251](#)
- _sort_quick_prepare:Nnnn ... [16196](#)
- _sort_quick_prepare_end:NNNnw .
 [16196](#)
- _sort_quick_single_end:nnnwnw .
 [16224](#), [16251](#)

- __sort_quick_split:NnNn
 .. 719, 719, 719, 720, 720, 16216,
 16221, 16256, 16263, 16269, 16271
- __sort_quick_split_end:nnwnw ..
 16242, 16248, 16251
- __sort_quick_split_i:NnnnnNn ...
 719, 16221
- __sort_quick_split_ii:NnnnnNn 16221
- __sort_redefine_compute_range: .
 15963
- __sort_return_mark:N
 16147, 16148, 16151
- __sort_return_none_error:
 716, 16149, 16151
- __sort_return_same:
 16152, 16161, 16166
- __sort_return_swapped: 16154, 16176
- __sort_return_two_error:w ... 16151
- __sort_shrink_range: .. 710, 711,
 711, 15937, 15968, 15984, 15992, 16005
- __sort_shrink_range_loop: ... 15937
- __sort_toks:NN 714, 16049,
 16056, 16063, 16070, 16087, 16092
- __sort_toks:NNw 16092
- __sort_too_long_error:NNw
 16029, 16301
- \l__sort_top_int ... 709, 709, 712,
 714, 716, 716, 15926, 16025, 16028,
 16031, 16032, 16035, 16096, 16115,
 16118, 16119, 16122, 16171, 16307
- \l__sort_true_max_int 709,
 710, 15926, 15940, 15953, 15967,
 15983, 15991, 16004, 16016, 16306
- sp 188
- spac commands:
 - \spac_directions_normal_body_dir
 1283
 - \spac_directions_normal_page_dir
 1284
 - \space 55
 - \spacefactor 545
 - \spaceskip 546
 - \span 547
 - \special 548
 - \splitbotmark 549
 - \splitbotmarks 662
 - \splitdiscards 663
 - \splitfirstmark 550
 - \splitfirstmarks 664
 - \splitmaxdepth 551
 - \splittopskip 552
 - sqr 186
 - sr commands:
 - \sr_if_empty_p:N 49
- \SS 19386
- \ss 19386
- str commands:
 - \c_ampersand_str 55, 3922
 - \c_atsign_str 55, 3922
 - \c_backslash_str 55, 3922
 - \c_circumflex_str 55, 3922
 - \c_colon_str
 55, 3922, 6847, 6952, 6958, 9768
 - \c_dollar_str 55, 3922
 - \c_hash_str 55,
 3922, 3988, 20552, 20714, 20721, 20761
 - \c_percent_str .. 55, 3922, 20863,
 20864, 20865, 20876, 20877, 20878
 - \str_case:nn 49, 49, 3530, 8178
 - \str_case:nn(TF) 367
 - \str_case:nnn 17561, 17562
 - \str_case:nnTF
 49, 49, 3530, 3535, 3540,
 3553, 3554, 9918, 17561, 17562, 18993
 - str_case:nnTF 494
 - \str_case_x:nn 50, 3530
 - \str_case_x:nnn 17563
 - \str_case_x:nnTF
 50, 50, 3530, 3567, 3572, 17563
 - \str_clear:N 48, 48, 3423
 - str_clear:N 48
 - \str_clear_new:N 48, 48, 3423
 - \str_const:Nn 47, 47,
 3446, 3922, 3923, 3924, 3925, 3926,
 3927, 3928, 3929, 3930, 3931, 3932,
 3933, 17434, 17438, 17460, 17468,
 17482, 17489, 17498, 17511, 17522
 - \str_count:N . 50, 50, 3790, 8774, 8842
 - \str_count:n 50, 50, 50, 56, 3790
 - \str_count_ignore_spaces:n
 50, 50, 336, 3790
 - \str_count_spaces:N 50, 3770
 - \str_count_spaces:n
 50, 50, 336, 3770, 3796
 - \str_fold_case:n
 .. 53, 53, 54, 54, 54, 54, 54, 217, 3858
 - \str_gclear:N 48, 3423
 - \str_gclear_new:N 3423
 - \str_gput_left:Nn 48, 3446
 - \str_gput_right:Nn 48, 3446
 - \str_gset:Nn 48, 3446
 - \str_gset_eq:NN 48, 3423
 - \str_head:N 51, 51, 337, 3828
 - \str_head:n 51, 51, 51, 305,
 321, 337, 337, 2783, 3258, 3305, 3828
 - \str_head_ignore_spaces:n 51, 51, 3828
 - \str_if_empty:NTF 49, 49, 3467
 - \str_if_empty_p:N 49, 3467

- \str_if_eq:NN 329
- \str_if_eq:nn 120, 125
- \str_if_eq:NNTF [49](#), [49](#), [3521](#), [3526](#), [3527](#)
- \str_if_eq:nnTF [49](#), [49](#), [49](#),
[50](#), [122](#), [215](#), [328](#), [348](#), [3501](#), [3510](#),
[3511](#), [3512](#), [3513](#), [3558](#), [4240](#), [7683](#),
[7859](#), [9722](#), [9740](#), [10215](#), [10443](#),
[11291](#), [18810](#), [18828](#), [18838](#), [18851](#)
- \str_if_eq_p:NN [49](#), [49](#), [3521](#)
- \str_if_eq_p:nn [49](#), [49](#), [3501](#)
- \str_if_eq_x:nn [442](#), [442](#)
- \str_if_eq_x:nnTF [49](#), [49](#), [55](#), [1928](#),
[3501](#), [3586](#), [7307](#), [7398](#), [7902](#), [9812](#)
- \str_if_eq_x_p:nn [49](#), [49](#), [3501](#)
- \str_if_exist:NTF [48](#), [48](#), [3467](#)
- \str_if_exist_p:N [48](#), [48](#), [3467](#)
- \str_item:Nn [51](#), [51](#), [3636](#)
- \str_item:nn [51](#), [51](#), [51](#), [332](#), [336](#), [3636](#)
- \str_item_ignore_spaces:nn
..... [51](#), [51](#), [332](#), [3636](#)
- \str_lower_case:n .. [53](#), [53](#), [217](#), [3858](#)
- \str_new:N [47](#),
[47](#), [48](#), [3423](#), [3934](#), [3935](#), [3936](#), [3937](#)
- \str_put_left:Nn [48](#), [48](#), [3446](#)
- \str_put_right:Nn [48](#), [48](#), [3446](#)
- \str_range:Nnn [52](#), [3694](#)
- \str_range:nnn .. [52](#), [52](#), [56](#), [336](#), [3694](#)
- \str_range_ignore_spaces:nnn [52](#), [3694](#)
- \str_set:Nn [48](#), [48](#), [3446](#)
- \str_set_eq:NN [48](#), [48](#), [3423](#)
- \str_show:N [54](#), [54](#), [3938](#)
- \str_show:n [54](#), [3938](#)
- \str_tail:N [51](#), [51](#), [3843](#)
- \str_tail:n [51](#), [51](#), [51](#), [3843](#)
- \str_tail_ignore_spaces:n [51](#), [51](#), [3843](#)
- \str_upper_case:n .. [53](#), [53](#), [217](#), [3858](#)
- \str_use:N [50](#), [50](#), [3423](#)
- \c_tilde_str [55](#), [3922](#)
- \g_tmpa_str [55](#), [3934](#)
- \l_tmpa_str [55](#), [3934](#)
- \g_tmpb_str [55](#), [3934](#)
- \l_tmpb_str [55](#), [3934](#)
- \c_underscore_str [55](#), [3922](#)
- str internal commands:
- _str_case:nnTF [3530](#)
- _str_case:nw [3530](#)
- _str_case_end:nw [3530](#)
- _str_case_x:nnTF [3530](#)
- _str_case_x:nw [3530](#)
- _str_change_case:nn [3858](#)
- _str_change_case_aux:nn [3858](#)
- _str_change_case_char:nN ... [3858](#)
- _str_change_case_char_aux:nN ..
..... [3900](#), [3905](#), [3919](#)
- _str_change_case_end:nw [3858](#)
- _str_change_case_end:wn [3877](#), [3894](#)
- _str_change_case_loop:nw ... [3858](#)
- _str_change_case_output:nw . [3858](#)
- _str_change_case_result:n .. [3858](#)
- _str_change_case_space:n ... [3858](#)
- _str_collect_delimit_by_q-
 stop:w [3722](#), [3745](#)
- _str_collect_end:nnnnnnnw ...
..... [335](#), [3745](#)
- _str_collect_end:wn [3745](#)
- _str_collect_loop:wn [3745](#)
- _str_collect_loop:wnNNNNNNN . [3745](#)
- _str_count:n
..... [56](#), [56](#), [336](#), [3652](#), [3709](#), [3790](#)
- _str_count_aux:n [3790](#)
- _str_count_loop:NNNNNNNNN .. [3790](#)
- _str_count_spaces_loop:w ... [3770](#)
- _str_escape_x:n [3471](#)
- _str_head:w [337](#), [337](#), [337](#), [3828](#)
- _str_if_eq_x:nn
.. [55](#), [55](#), [3471](#), [3495](#), [3504](#), [3518](#),
[3523](#), [3991](#), [4015](#), [4026](#), [4034](#), [4046](#),
[6850](#), [9402](#), [11772](#), [11786](#), [12043](#), [14495](#)
- _str_if_eq_x_return:nn
..... [55](#), [55](#), [427](#), [3493](#), [6908](#)
- _str_item:nn [332](#), [332](#), [3636](#)
- _str_item:w [332](#), [3636](#)
- _str_lookup_fold:N [3858](#)
- _str_lookup_lower:N [3858](#)
- _str_lookup_upper:N [3858](#)
- _str_range:nnn [56](#), [56](#), [3694](#)
- _str_range:nnw [3694](#)
- _str_range:w [3694](#)
- _str_range_normalize:nn
..... [3717](#), [3718](#), [3726](#)
- _str_skip_end:NNNNNNNN
..... [333](#), [333](#), [3676](#)
- _str_skip_end:w [3676](#)
- _str_skip_exp_end:w
.... [333](#), [335](#), [3663](#), [3672](#), [3676](#), [3724](#)
- _str_skip_loop:wNNNNNNNNN ... [3676](#)
- _str_tail_auxi:w [3843](#)
- _str_tail_auxii:w [337](#), [3843](#)
- _str_tmp:n
.. [3424](#), [3430](#), [3433](#), [3447](#), [3454](#), [3457](#)
- _str_to_other:n [55](#), [55](#),
[56](#), [56](#), [56](#), [331](#), [336](#), [3591](#), [3643](#), [3701](#)
- _str_to_other_end:w [331](#), [3591](#)
- _str_to_other_fast:n
..... [56](#), [56](#), [3614](#), [8773](#), [8854](#)
- _str_to_other_fast_end:w ... [3614](#)
- _str_to_other_fast_loop:w .. [3614](#)
- _str_to_other_loop:w [331](#), [3591](#)

- \strcmp 40
 - \string 553
 - \suppressfontnotfounderror 805
 - \suppressifcsnameerror 926
 - \suppresslongerror 927
 - \suppressmathparerror 928
 - \suppressoutererror 929
 - \synctex 787
 - sys commands:
 - \c_sys_day_int 205, 17440
 - \c_sys_engine_str 205, 17447
 - \c_sys_hour_int 205, 17440
 - \sys_if_engine_luatex:TF
 - 205, 222, 17447, 17456,
 - 17457, 17549, 17550, 17551, 19701
 - \sys_if_engine luatex_p:
 - 205, 17447, 17548
 - \sys_if_engine_pdftex:TF
 - 205, 205, 17447,
 - 17464, 17465, 17553, 17554, 17555
 - \sys_if_engine_pdftex_p:
 - 205, 17447, 17552, 19199
 - \sys_if_engine_ptex:TF
 - 205, 17447, 17485, 17486
 - \sys_if_engine_ptex_p: ... 205, 17447
 - \sys_if_engine_uptex:TF
 - 205, 17447, 17478, 17479
 - \sys_if_engine_uptex_p:
 - 205, 17447, 19199
 - \sys_if_engine_xetex:TF
 - 4, 205, 17447,
 - 17494, 17495, 17567, 17568, 17569
 - \sys_if_engine_xetex_p:
 - 205, 17447, 17566
 - \sys_if_output_dvi:TF 206,
 - 206, 17500, 17503, 17504, 17514, 17515
 - \sys_if_output_dvi_p: ... 206, 17500
 - \sys_if_output_pdf:TF
 - 206, 17500, 17507, 17508, 17518, 17519
 - \sys_if_output_pdf_p: ... 206, 17500
 - \c_sys_jobname_str
 - 136, 205, 17430, 17539
 - \c_sys_minute_int 205, 17440
 - \c_sys_month_int 205, 17440
 - \c_sys_output_str 206, 17500
 - \c_sys_year_int 205, 17440
 - syst commands:
 - \c_syst_last_allocated_read
 - 3952, 3953
 - \c_syst_last_allocated_toks .. 15997
- T
- \t 19395
 - \tabskip 554
 - \tagcode 788
 - \tan 185
 - \tand 185
 - \tate 1148
 - \tbaselineshift 1149
 - \temp . 163, 169, 174, 177, 178, 185, 190, 193
 - T_EX and L^AT_EX 2_ε commands:
 - \@ 3923, 11285
 - \@@end 254, 1166, 1167
 - \@@hyph 1170
 - \@@input 1171
 - \@@italiccorr 1172
 - \@@tracingfonts 255
 - \@@underline 1173
 - \@addtofilelist 8468
 - \@currname 467, 8330, 8331
 - \@filelist 468,
 - 471, 472, 472, 8467, 8494, 8496, 8511
 - \@firstoftwo 261
 - \@ifpackageloaded
 - .. 19819, 19856, 19873, 20217, 20607
 - \@secondoftwo 261
 - \@tempa 143, 145
 - \@unexpandable@protect
 - 566, 11286, 11293
 - \botmark 429
 - \box 193
 - \char 118
 - \chardef 362
 - \copy 193
 - \count 118, 711, 711, 711
 - \cr 399
 - \csname 16
 - \csstring 269
 - \current@color
 - 19820, 19857, 20218, 20608
 - \currentgrouplevel 281, 466
 - \currentgrouptype 281, 466
 - \def 118
 - \detokenize 313
 - \dimen 427, 427
 - \dimendef 427
 - \dimexpr 158
 - \directlua 222
 - \dp 193, 567, 568
 - \e@alloc@top 711, 15983
 - \edef 1, 298
 - \endcsname 16
 - \endinput 128
 - \endlinechar
 - .. 37, 37, 304, 304, 304, 304, 305, 429
 - \endtemplate 94, 399
 - \errhelp 448, 448
 - \errmessage ... 448, 449, 449, 449, 449

- `\errorcontextlines` . 143, 449, 466, 728
- `\escapechar` . . 41, 41, 41, 268, 281, 482
- `\everyeof` 303, 305
- `\expandafter` 30, 31
- `\expanded` 248
- `\fi` 117
- `\firstmark` 293, 429
- `\frozen@everydisplay` 1168
- `\frozen@everymath` 1169
- `\futurelet` 399, 431, 433
- `\global` 237
- `\halign` 94, 399, 420
- `\hskip` 154
- `\ht` 193, 567, 568
- `\hyphen` 429, 429
- `\ifcase` 79
- `\ifdim` 157
- `\ifeof` 142
- `\iffalse` 90
- `\ifhbox` 198
- `\ifnum` 79
- `\ifodd` 79, 810
- `\iftrue` 90
- `\ifvbox` 198
- `\ifvoid` 199
- `\ifx` 21, 233
- `\input@path` 8407, 8411, 8426
- `\italiccorr` 429, 429
- `\jobname` 205
- `\l@expl@check@declarations@bool` 1765, 2628, 5472, 5646, 8098
- `\l@expl@log@functions@bool` 1702, 1750, 7500
- `\lastnamedcs` 271
- `\lccode` 233, 340, 380
- `\let` 237
- `\letcharcode` 418
- `\loctoks` 711, 711, 711
- `\long` 118, 118
- `\lower` 766
- `\luaescapestring` 223
- `\m@ne` 381, 5408
- `\makeatletter` 6
- `\mathchar` 118
- `\mathchardef` 362
- `\meaning` 15, 110, 118, 118, 427, 427, 427, 427, 427, 427, 433, 810
- `\newif` 90
- `\newlinechar` . 37, 37, 143, 272, 304, 304, 304, 304, 449, 466, 480, 480
- `\newread` 474, 474, 474
- `\newtoks` 191, 723
- `\newwrite` 478
- `\noexpand` 30, 117
- `\nullfont` 429, 429, 429
- `\number` 80, 614
- `\numexpr` 80
- `\or` 79
- `\outer` 118, 118, 233, 474, 474, 478, 756, 810, 810
- `\par` 753
- `\pdfmapfile` 256
- `\pdfmapline` 256
- `\pdfrandomseed` 187
- `\pdfsetrandomseed` 187
- `\pdfstrcmp` xii, 230, 230, 231, 233, 233, 247, 812
- `\pdfuniformdeviate` 187, 703
- `\pgfsys@...` 225
- `\protect` 565, 566, 566, 566, 566, 792
- `\protected` 118, 118
- `\protected@edef` 484, 8848
- `\ProvidesClass` 6
- `\ProvidesFile` 6
- `\ProvidesPackage` 6
- `\randomseed` 187
- `\read` 138
- `\readline` 139
- `\relax` 117, 233, 265, 270, 281, 381, 381, 530, 532, 532, 552, 581
- `\RequirePackage` 6, 233
- `\reserveinserts` 233, 233
- `\robustify` 217
- `\romannumeral` 79
- `\scantokens` 303, 304, 305
- `\set@color` 753, 17420, 17423
- `\setrandomseed` 187
- `\sfcode` 234
- `\show` 16, 45, 281
- `\showbox` 727
- `\showthe` 281, 379, 498, 501, 504
- `\showtokens` 46, 134, 465, 466, 466, 466
- `\space` 429, 429
- `\splitbotmark` 429
- `\splitfirstmark` 429
- `\strcmp` 230, 247
- `\string` 110
- `\synctex` 247
- `\tenrm` 117
- `\tex_lowercase:D` 421, 421
- `\the` 70, 117, 149, 153, 156, 285, 285
- `\toks` xix, 191, 191, 191, 709, 710, 710, 711, 711, 711, 711, 712, 712, 712, 713, 713, 714, 715, 716, 717, 717, 717, 723, 723
- `\toksdef` 723
- `\topmark` 118, 429
- `\tracingfonts` 255

- tracingfonts 255
- \tracingonline 728
- \uccode 340
- \Ucharcat 419, 420, 421
- \ucharcat@table 52, 55
- \unexpanded
 - . 30, 42, 42, 42, 45, 59, 63, 64, 98,
 - 101, 102, 103, 122, 211, 215, 216,
 - 216, 220, 221, 298, 320, 321, 365, 420
- \unhbox 196
- \unhcopy 196
- \uniformdeviate 187, 187, 703
- \unless 21
- \unvbox 198
- \unvcopy 198
- \valign 399
- \vbox 197
- \vskip 155
- \vsplit 198
- \vtop 197, 734
- \wd 194, 567, 568
- \write 140, 480
- \zap@space 527
- tex commands:
 - \tex_above:D 287
 - \tex_abovedisplayshortskip:D .. 288
 - \tex_abovedisplayskip:D 289
 - \tex_abovewithdelims:D 290
 - \tex_accent:D 291
 - \tex_adjdemerits:D 292
 - \tex_advance:D 293, 4743,
 - 4745, 4755, 4757, 9134, 9139, 9390,
 - 9395, 9488, 9493, 16107, 16114, 16117
 - \tex_afterassignment:D 294, 7014
 - \tex_aftergroup:D 295, 1326
 - \tex_atop:D 296
 - \tex_atopwithdelims:D 297
 - \tex_badness:D 298
 - \tex_baselineskip:D 299
 - \tex_batchmode:D 300
 - \tex_begingroup:D 301, 1322
 - \tex_belowdisplayshortskip:D .. 302
 - \tex_belowdisplayskip:D 303
 - \tex_binoppenalty:D 304
 - \tex_botmark:D 305
 - \tex_box:D 306, 16382, 16406
 - \tex_boxmaxdepth:D 307
 - \tex_brokenpenalty:D 308
 - \tex_catcode:D 309, 2317,
 - 2321, 2734, 3962, 3963, 6464, 6468
 - \tex_char:D 310
 - \tex_chardef:D
 - 260, 311, 1316, 1343, 1345,
 - 1589, 1590, 3944, 3947, 4716, 5640,
 - 5642, 5680, 5685, 6937, 8590, 8713
 - \tex_cleaders:D 312
 - \tex_closein:D 313, 3967, 8598
 - \tex_closeout:D 314, 8721
 - \tex_clubpenalty:D 315
 - \tex_copy:D 316, 16376, 16407
 - \tex_count:D 317, 3954, 8530, 8532,
 - 8675, 8677, 15966, 15982, 15990, 15991
 - \tex_countdef:D 318
 - \tex_cr:D 319
 - \tex_crcr:D 320
 - \tex_csname:D 321, 1310
 - \tex_day:D 322, 17444
 - \tex_deadcycles:D 323
 - \tex_def:D
 - .. 324, 791, 792, 793, 1327, 1329,
 - 1331, 1332, 1349, 1351, 1352, 1353,
 - 1355, 1356, 1357, 1359, 1360, 1361
 - \tex_defaultthyphenchar:D 325
 - \tex_defaultskewchar:D 326
 - \tex_delcode:D 327
 - \tex_delimiter:D 328
 - \tex_delimiterfactor:D 329
 - \tex_delimitershortfall:D 330
 - \tex_dimen:D 331
 - \tex_dimendef:D 332
 - \tex_discretionary:D 333
 - \tex_displayindent:D 334
 - \tex_displaylimits:D 335
 - \tex_displaystyle:D 336
 - \tex_displaywidowpenalty:D 337
 - \tex_displaywidth:D 338
 - \tex_divide:D 339, 15959
 - \tex_doublehyphenemerits:D ... 340
 - \tex_dp:D 341, 16392
 - \tex_dump:D 342
 - \tex_edef:D 343, 1350,
 - 1354, 1358, 1362, 8896, 8953, 17529
 - \tex_else:D 344, 1177, 1297, 1346
 - \tex_emergencystretch:D 345
 - \tex_end:D . 346, 1167, 1266, 1733, 7734
 - \tex_endcsname:D 347, 1311
 - \tex_endgroup:D 348, 1164, 1323
 - \tex_endinput:D 349, 7745
 - \tex_endlinechar:D . 251, 252, 266,
 - 350, 2707, 2708, 2709, 2765, 8638, 8640
 - \tex_eqno:D 351
 - \tex_errhelp:D 352, 7595
 - \tex_errmessage:D 353, 1725, 7626
 - \tex_errorcontextlines:D
 - 354, 7621, 7653, 8295, 16476
 - \tex_errorstopmode:D 355

- `\tex_escapechar:D` 356, 2036, 8786, 8821, 8827
- `\tex_everycr:D` 357
- `\tex_everydisplay:D` 358, 1168
- `\tex_everyhbox:D` 359
- `\tex_everyjob:D` 360, 1267, 8323, 8325, 8336, 8338, 17431, 17433
- `\tex_everymath:D` 361, 1169
- `\tex_everypar:D` 362
- `\tex_everyvbox:D` 363
- `\tex_exhyphenpenalty:D` 364
- `\tex_expandafter:D` ... 365, 796, 1312
- `\tex_fam:D` 366
- `\tex_fi:D` 367, 797, 1181, 1182, 1183, 1236, 1238, 1239, 1243, 1257, 1262, 1277, 1285, 1290, 1298, 1348, 2686
- `\tex_finalhyphendemerits:D` ... 368
- `\tex_firstmark:D` 369
- `\tex_floatingpenalty:D` 370
- `\tex_font:D` 371
- `\tex_fontdimen:D` 372
- `\tex_fontname:D` 373
- `\tex_futurelet:D` 374, 7008, 7010
- `\tex_gdef:D` 375, 1363, 1366, 1370, 1374
- `\tex_global:D` .. 272, 277, 279, 286, 376, 798, 800, 1832, 1839, 4703, 4723, 4735, 4747, 4749, 4759, 4761, 4768, 5642, 5685, 6743, 6745, 6755, 7010, 8590, 8713, 9109, 9124, 9130, 9135, 9140, 9365, 9380, 9386, 9391, 9396, 9463, 9478, 9484, 9489, 9494, 16378, 16384, 16442, 16489, 16495, 16501, 16525, 16531, 16540, 16546
- `\tex_globaldefs:D` 377
- `\tex_halign:D` 378
- `\tex_hangafter:D` 379
- `\tex_hangindent:D` 380
- `\tex_hbadness:D` 381
- `\tex_hbox:D` 382, 16486, 16488, 16493, 16499, 16507, 16508
- `\tex_hfil:D` 383
- `\tex_hfill:D` 384
- `\tex_hfilneg:D` 385
- `\tex_hfuzz:D` 386
- `\tex_hoffset:D` 387, 1279
- `\tex_holdinginserts:D` 388
- `\tex_hrule:D` 389
- `\tex_hsize:D` 390, 16663, 16665, 16666, 16712, 16714, 16715
- `\tex_hskip:D` 391, 9425
- `\tex_hss:D`
- 392, 16510, 16512, 17861, 17870
- `\tex_ht:D` 393, 16391
- `\tex_hyphen:D` 286, 1170
- `\tex_hyphenation:D` 394
- `\tex_hyphenchar:D` 395
- `\tex_hyphenpenalty:D` 396
- `\tex_if:D` 105, 397, 1300, 1301
- `\tex_ifcase:D` 398, 4613
- `\tex_ifcat:D` 399, 1302
- `\tex_ifdim:D` 400, 9091
- `\tex_ifeof:D` 401, 3972, 8615
- `\tex_iffalse:D` 402, 1295
- `\tex_ifhbox:D` 403, 16418
- `\tex_ifhmode:D` 404, 1305
- `\tex_ifinner:D` 405, 1307
- `\tex_ifmmode:D` 406, 1304
- `\tex_ifnum:D` 407, 1237, 1324
- `\tex_ifodd:D` 408, 1702, 1750, 1765, 2628, 4612, 5472, 5614, 5615
- `\tex_iftrue:D` 409, 1294
- `\tex_ifvbox:D` 410, 16419
- `\tex_ifvmode:D` 411, 1306
- `\tex_ifvoid:D` 412, 16420
- `\tex_ifx:D` 413, 1303
- `\tex_ignorespaces:D` 414
- `\tex_immediate:D`
- ... 415, 1693, 1695, 8715, 8721, 8753
- `\tex_indent:D` 416
- `\tex_input:D`
- . 417, 1171, 1268, 8473, 18570, 18593
- `\tex_inputlineno:D` ... 418, 1740, 7569
- `\tex_insert:D` 419
- `\tex_insertpenalties:D` 420
- `\tex_interlinepenalty:D` 421
- `\tex_italiccorrection:D`
- 285, 1172, 1280
- `\tex_jobname:D` 422, 8326, 17434, 17438
- `\tex_kern:D` 423, 16980, 16985, 17051, 17052, 17339, 17340, 17627, 17859, 17868, 17881, 17883, 17927, 17929, 18009, 20125
- `\tex_language:D` 424, 1269
- `\tex_lastbox:D` 425, 16440
- `\tex_lastkern:D` 426
- `\tex_lastpenalty:D` 427
- `\tex_lastskip:D` 428
- `\tex_lccode:D` 429, 3597, 3598, 3620, 3621, 3914, 4027, 6546, 6550, 18775
- `\tex_leaders:D` 430
- `\tex_left:D` 431, 1287
- `\tex_lefthyphenmin:D` 432
- `\tex_leftskip:D` 433
- `\tex_leqno:D` 434
- `\tex_let:D` . 273, 277, 279, 435, 798, 800, 1167, 1168, 1169, 1170, 1171, 1172, 1173, 1174, 1176, 1180, 1185, 1186, 1187, 1188, 1189, 1190, 1191,

| | |
|--|----------------------------|
| 1192, 1193, 1194, 1195, 1196, 1197, | |
| 1198, 1199, 1200, 1201, 1202, 1203, | |
| 1204, 1205, 1206, 1207, 1208, 1209, | |
| 1210, 1211, 1212, 1213, 1214, 1215, | |
| 1216, 1217, 1218, 1219, 1220, 1221, | |
| 1222, 1223, 1224, 1225, 1226, 1227, | |
| 1228, 1229, 1230, 1231, 1232, 1233, | |
| 1234, 1235, 1241, 1242, 1247, 1248, | |
| 1249, 1250, 1251, 1252, 1253, 1254, | |
| 1255, 1256, 1259, 1260, 1261, 1266, | |
| 1267, 1268, 1269, 1270, 1271, 1272, | |
| 1273, 1274, 1275, 1276, 1279, 1280, | |
| 1281, 1282, 1283, 1284, 1287, 1288, | |
| 1289, 1294, 1295, 1296, 1297, 1298, | |
| 1299, 1300, 1301, 1302, 1303, 1304, | |
| 1305, 1306, 1307, 1308, 1309, 1310, | |
| 1311, 1312, 1313, 1314, 1315, 1317, | |
| 1318, 1319, 1320, 1321, 1322, 1323, | |
| 1324, 1325, 1326, 1342, 1349, 1350, | |
| 1363, 1364, 1828, 6743, 6745, 6755 | |
| <code>\tex_limits:D</code> | 436 |
| <code>\tex_linepenalty:D</code> | 437 |
| <code>\tex_lineskip:D</code> | 438 |
| <code>\tex_lineskiplimit:D</code> | 439 |
| <code>\tex_long:D</code> | 440, 791, 792, |
| 793, 1327, 1329, 1332, 1351, 1352, | |
| 1353, 1354, 1355, 1357, 1359, 1360, | |
| 1361, 1362, 1366, 1368, 1374, 1376 | |
| <code>\tex_looseness:D</code> | 441 |
| <code>\tex_lower:D</code> | 442, 16417 |
| <code>\tex_lowercase:D</code> | |
| | 443, 2741, 2758, 3408, |
| 3409, 3599, 3622, 6585, 6708, 7607 | |
| <code>\tex_mag:D</code> | 444 |
| <code>\tex_mark:D</code> | 445 |
| <code>\tex_mathaccent:D</code> | 446 |
| <code>\tex_mathbin:D</code> | 447 |
| <code>\tex_mathchar:D</code> | 448 |
| <code>\tex_mathchardef:D</code> | |
| | 260, 449, 1347, 4719, 4720 |
| <code>\tex_mathchoice:D</code> | 450 |
| <code>\tex_mathclose:D</code> | 451 |
| <code>\tex_mathcode:D</code> | 452, 6537, 6541 |
| <code>\tex_mathinner:D</code> | 453 |
| <code>\tex_mathop:D</code> | 454, 1270 |
| <code>\tex_mathopen:D</code> | 455 |
| <code>\tex_mathord:D</code> | 456 |
| <code>\tex_mathpunct:D</code> | 457 |
| <code>\tex_mathrel:D</code> | 458 |
| <code>\tex_mathsurround:D</code> | 459 |
| <code>\tex_maxdeadcycles:D</code> | 460 |
| <code>\tex_maxdepth:D</code> | 461 |
| <code>\tex_meaning:D</code> | 462, 1317, 1318 |
| <code>\tex_medmuskip:D</code> | 463 |
| <code>\tex_message:D</code> | 464 |
| <code>\tex_middle:D</code> | 1288 |
| <code>\tex_mkern:D</code> | 465 |
| <code>\tex_month:D</code> | 466, 1271, 17445 |
| <code>\tex_moveleft:D</code> | 467, 16411 |
| <code>\tex_moveright:D</code> | 468, 16413 |
| <code>\tex_mskip:D</code> | 469 |
| <code>\tex_multiply:D</code> | 470 |
| <code>\tex_muskip:D</code> | 471 |
| <code>\tex_muskipdef:D</code> | 472 |
| <code>\tex_newlinechar:D</code> | 473, 1724, |
| 2709, 2737, 2740, 7619, 8293, 8752 | |
| <code>\tex_noalign:D</code> | 474 |
| <code>\tex_noboundary:D</code> | 475 |
| <code>\tex_noexpand:D</code> | 476, 1313 |
| <code>\tex_noindent:D</code> | 477 |
| <code>\tex_nolimits:D</code> | 478 |
| <code>\tex_nonscript:D</code> | 479 |
| <code>\tex_nonstopmode:D</code> | 480 |
| <code>\tex_nulldelimiterspace:D</code> | 481 |
| <code>\tex_nullfont:D</code> | 482, 6966 |
| <code>\tex_number:D</code> | 483, 4609 |
| <code>\tex_omit:D</code> | 484 |
| <code>\tex_openin:D</code> | 485, 3964, 8592 |
| <code>\tex_openout:D</code> | 486, 8715 |
| <code>\tex_or:D</code> | 487, 1296 |
| <code>\tex_outer:D</code> | 488, 1272, 17529 |
| <code>\tex_output:D</code> | 489 |
| <code>\tex_outputpenalty:D</code> | 490 |
| <code>\tex_over:D</code> | 491, 1273 |
| <code>\tex_overfullrule:D</code> | 492 |
| <code>\tex_overline:D</code> | 493 |
| <code>\tex_overwithdelims:D</code> | 494 |
| <code>\tex_pagedepth:D</code> | 495 |
| <code>\tex_pagefilllstretch:D</code> | 496 |
| <code>\tex_pagefillstretch:D</code> | 497 |
| <code>\tex_pagefilstretch:D</code> | 498 |
| <code>\tex_pagegoal:D</code> | 499 |
| <code>\tex_pageshrink:D</code> | 500 |
| <code>\tex_pagestretch:D</code> | 501 |
| <code>\tex_pagetotal:D</code> | 502 |
| <code>\tex_par:D</code> | 503, 17403 |
| <code>\tex_parfillskip:D</code> | 504 |
| <code>\tex_parindent:D</code> | 505 |
| <code>\tex_parshape:D</code> | 506 |
| <code>\tex_parskip:D</code> | 507 |
| <code>\tex_patterns:D</code> | 508 |
| <code>\tex_pausing:D</code> | 509 |
| <code>\tex_penalty:D</code> | 510 |
| <code>\tex_postdisplaypenalty:D</code> | 511 |
| <code>\tex_predisplaypenalty:D</code> | 512 |
| <code>\tex_predisplaysize:D</code> | 513 |
| <code>\tex_pretolerance:D</code> | 514 |
| <code>\tex_prevdepth:D</code> | 515 |

- `\tex_prevgraf:D` 516
- `\tex_radical:D` 517
- `\tex_raise:D` 518, 16415
- `\tex_read:D` 519, 3978, 8633
- `\tex_relax:D`
..... 520, 532, 1321, 1724, 4611, 9093
- `\tex_relpenalty:D` 521
- `\tex_right:D` 522, 1289
- `\tex_righthypenmin:D` 523
- `\tex_rightskip:D` 524
- `\tex_romannumeral:D`
..... 268, 268, 268, 268,
268, 291, 525, 1315, 1325, 1593, 2315
- `\tex_romannumeral1:D` 291
- `\tex_scriptfont:D` 526
- `\tex_scriptscriptfont:D` 527
- `\tex_scriptscriptstyle:D` 528
- `\tex_scriptspace:D` 529
- `\tex_scriptstyle:D` 530
- `\tex_scrollmode:D` 531
- `\tex_setbox:D` 532, 16376,
16382, 16440, 16488, 16493, 16499,
16524, 16529, 16536, 16544, 16560
- `\tex_setlanguage:D` 533
- `\tex_sfcode:D` 534, 6564, 6568
- `\tex_shipout:D` 535
- `\tex_show:D` 536
- `\tex_showbox:D` 537, 16477
- `\tex_showboxbreadth:D` ... 538, 16473
- `\tex_showboxdepth:D` 539, 16474
- `\tex_showlists:D` 540
- `\tex_showthe:D` 541
- `\tex_skewchar:D` 542
- `\tex_skip:D` 543
- `\tex_skipdef:D` 544
- `\tex_space:D` 284
- `\tex_spacefactor:D` 545
- `\tex_spaceskip:D` 546
- `\tex_span:D` 547
- `\tex_special:D` 548, 19844,
19863, 19867, 19877, 19881, 20142,
20152, 20154, 20224, 20228, 20230,
20234, 20235, 20236, 20237, 20241,
20242, 20243, 20494, 20496, 20497,
20498, 20505, 20511, 20614, 20618
- `\tex_splitbotmark:D` 549
- `\tex_splitfirstmark:D` 550
- `\tex_splitmaxdepth:D` 551
- `\tex_splittopskip:D` 552
- `\tex_string:D` 553, 1320
- `\tex_tabskip:D` 554
- `\tex_textfont:D` 555
- `\tex_textstyle:D` 556
- `\tex_the:D` 252,
285, 557, 562, 567, 567, 568, 714,
1740, 2021, 2104, 2108, 4771, 4773,
6468, 6541, 6550, 6559, 6568, 8325,
8338, 9306, 9308, 9422, 9424, 9499,
11322, 11357, 11786, 16097, 16144,
16145, 16159, 16160, 16460, 17433
- `\tex_thickmuskip:D` 558
- `\tex_thinmuskip:D` 559
- `\tex_time:D` 560, 17441, 17443
- `\tex_toks:D` 561, 714,
16031, 16097, 16133, 16144, 16145,
16159, 16160, 16168, 16178, 16188
- `\tex_toksdef:D` 562, 16291
- `\tex_tolerance:D` 563
- `\tex_topmark:D` 564
- `\tex_topskip:D` 565
- `\tex_tracingcommands:D` 566
- `\tex_tracinglostchars:D` 567
- `\tex_tracingmacros:D` 568
- `\tex_tracingonline:D` 569, 16475
- `\tex_tracingoutput:D` 570
- `\tex_tracingpages:D` 571
- `\tex_tracingparagraphs:D` 572
- `\tex_tracingrestores:D` 573
- `\tex_tracingstats:D` 574
- `\tex_uccode:D`
..... 575, 3915, 6555, 6559, 18776
- `\tex_uchyph:D` 576
- `\tex_undefined:D` 272,
279, 429, 429, 429, 800, 1174, 1241,
1242, 1259, 1260, 1261, 1845, 1853,
5425, 9866, 9880, 9913, 9934, 15969
- `\tex_underline:D` 577, 1173
- `\tex_unhbox:D` 578, 16514
- `\tex_unhcopy:D` 579, 16513
- `\tex_unkern:D` 580
- `\tex_unpenalty:D` 581
- `\tex_unskip:D` 582
- `\tex_unvbox:D` 583, 16556
- `\tex_unvcopy:D` 584, 16555
- `\tex_uppercase:D` 585, 3417, 3418
- `\tex_vadjust:D` 586
- `\tex_valign:D` 587
- `\tex_vbadness:D` 588
- `\tex_vbox:D` 589, 16517,
16520, 16522, 16524, 16536, 16544
- `\tex_vcenter:D` 590, 1274
- `\tex_vfil:D` 591
- `\tex_vfill:D` 592
- `\tex_vfilneg:D` 593
- `\tex_vfuzz:D` 594
- `\tex_voffset:D` 595, 1281
- `\tex_vrule:D` 596, 17191, 17246

- `\tex_vsize:D` 597
- `\tex_vskip:D` 598, 9428
- `\tex_vsplit:D` 599, 16560
- `\tex_vss:D` 600
- `\tex_vtop:D` 601, 16518, 16529
- `\tex_wd:D` 602, 16393
- `\tex_widowpenalty:D` 603
- `\tex_write:D`
 - ... 604, 1693, 1695, 8733, 8736, 8753
- `\tex_xdef:D` 605, 1364, 1368, 1372, 1376
- `\tex_xleaders:D` 606
- `\tex_xspaceskip:D` 607
- `\tex_year:D` 608, 17446
- `\textdir` 946
- `\textfont` 555
- `\textstyle` 556
- `\texttt` 12619, 20197
- `\TeXeTstate` 665
- `\tfont` 1150
- `\TH` 19387
- `\th` 19387
- `\the` 67, 212, 213, 214,
 - 215, 216, 217, 218, 219, 220, 221, 557
- `\thickmuskip` 558
- `\thinmuskip` 559
- thousand commands:
 - `\c_one_thousand` 78, 5389
 - `\c_ten_thousand` 78, 5389
- `\time` 560
- `\tiny` 17184
- tl commands:
 - `\c_empty_tl`
 - ... 46, 372, 2516, 2532, 2534, 2559,
 - 2885, 3979, 5099, 5105, 5917, 9603
 - `\c_space_tl` 46,
 - 2560, 3180, 3886, 6331, 6340, 7573,
 - 8473, 15696, 18652, 18712, 19434,
 - 19850, 19913, 19918, 19921, 20690
 - `\tl_act` 318
 - `\tl_case:Nn` 39, 39, 2977
 - `tl_case:nn` 329
 - `\tl_case:Nnn` 17564, 17565
 - `\tl_case:NnTF` 39, 39, 2977,
 - 2982, 2987, 3006, 3007, 17564, 17565
 - `\l_tl_case_change_accents_tl` ...
 - ... 219, 18819, 19393
 - `\l_tl_case_change_exclude_tl` ...
 - ... 218, 218, 219, 18841, 19563
 - `\l_tl_case_change_math_tl`
 - ... 218, 218, 18662, 19444, 19558
 - `\tl_clear:N` 34, 34, 2531, 2538, 5925,
 - 5926, 8285, 8862, 8863, 8866, 8875,
 - 8984, 8987, 9038, 9718, 10172, 10244
 - `tl_clear:N` 35
 - `\tl_clear_new:N` 35, 35, 2537, 5929, 5930
 - `\tl_concat:NNN` 35, 35, 2551, 2672
 - `\tl_const:Nn` 34, 34, 2519,
 - 2559, 2560, 2688, 3999, 4017, 4029,
 - 4064, 4065, 4066, 4085, 5505, 5923,
 - 6710, 6761, 7211, 7484, 7485, 7537,
 - 7542, 7544, 7546, 7548, 7550, 7555,
 - 7556, 7563, 8762, 8787, 8793, 9655,
 - 9656, 9657, 9658, 9659, 9660, 9661,
 - 10473, 10474, 10475, 10476, 10477,
 - 13567, 14006, 14007, 14008, 14009,
 - 14010, 14011, 14012, 14013, 14014,
 - 15874, 19144, 19145, 19146, 19155,
 - 19156, 19159, 19160, 19161, 19162,
 - 19163, 19169, 19177, 19215, 19228,
 - 19349, 19372, 19373, 19390, 19391
 - `\tl_count:N` 38, 41, 42, 42, 3069
 - `\tl_count:n`
 - ... 39, 41, 41, 42, 277, 336, 336,
 - 360, 543, 1447, 1451, 1890, 1935,
 - 3069, 3373, 12400, 12421, 19580, 19590
 - `\tl_count_tokens:n` .. 217, 217, 18538
 - `\tl_gclear:N` 34,
 - 2531, 2540, 5927, 5928, 20728, 20764
 - `\tl_gclear_new:N` . 35, 2537, 5931, 5932
 - `\tl_gconcat:NNN` 35, 2551, 2679
 - `\tl_gput_left:Nn` . 35, 2579, 2649, 2650
 - `\tl_gput_right:Nn`
 - ... 35, 2603, 2653, 2654, 4209, 5605
 - `\tl_gremove_all:Nn` 36, 2867
 - `\tl_gremove_once:Nn` 36, 2861
 - `\tl_greplace_all:Nnn` . 36, 2792, 2870
 - `\tl_greplace_once:Nnn` 36, 2792, 2864
 - `\tl_greverse:N` 42, 3210
 - `.tl_gset:N` 163, 10075
 - `\tl_gset:Nn` 35,
 - 58, 306, 713, 713, 2554, 2561, 2646,
 - 2684, 2692, 2795, 2799, 3103, 3213,
 - 4124, 4129, 4141, 4178, 4195, 4235,
 - 4261, 4345, 4374, 4411, 4415, 5944,
 - 5972, 6018, 6061, 6099, 6151, 6182,
 - 7262, 7291, 7327, 7339, 7362, 8326,
 - 8472, 15872, 16054, 16068, 16076,
 - 18466, 18476, 18557, 18582, 20687
 - `\tl_gset_eq:NN` 35, 2534,
 - 2543, 2664, 3443, 4108, 4109, 4110,
 - 4111, 5937, 5938, 5939, 5940, 7234,
 - 7235, 7236, 7237, 8331, 8475, 15879
 - `\tl_gset_from_file:Nnn` ... 220, 18554
 - `\tl_gset_from_file_x:Nnn` . 220, 18579
 - `\tl_gset_rescan:Nnn` 37, 2689
 - `.tl_gset_x:N` 163, 10075
 - `\tl_gsort:Nn` 43, 3144, 16059
 - `\tl_gtrim_spaces:N` 42, 3098

- \tl_head:N [43](#), [3216](#)
- \tl_head:n [43](#), [43](#),
[43](#), [44](#), [320](#), [321](#), [808](#), [808](#), [3216](#), [19588](#)
- \tl_head:w [44](#), [44](#),
[321](#), [321](#), [322](#), [3216](#), [3256](#), [3275](#), [3297](#)
- \tl_if_blank:nTF ... [37](#), [37](#), [43](#), [44](#),
[44](#), [2873](#), [2876](#), [2877](#), [2880](#), [2881](#),
[3243](#), [3426](#), [3449](#), [4003](#), [4013](#), [6339](#),
[6418](#), [9716](#), [10168](#), [10183](#), [10322](#),
[16200](#), [18998](#), [19018](#), [19068](#), [19579](#)
- \tl_if_blank_p:n [37](#), [37](#), [2873](#)
- \tl_if_empty:N [3469](#), [3470](#), [6197](#), [6199](#)
- \tl_if_empty:Ntf [38](#),
[38](#), [135](#), [2883](#), [2892](#), [2893](#), [8879](#),
[8968](#), [9043](#), [9702](#), [9726](#), [10188](#), [20690](#)
- \tl_if_empty:nTF . [38](#), [38](#), [311](#), [312](#),
[313](#), [408](#), [1476](#), [1558](#), [2697](#), [2806](#),
[2895](#), [2906](#), [2907](#), [2908](#), [2956](#), [3336](#),
[3357](#), [4053](#), [4144](#), [5528](#), [5535](#), [5552](#),
[5960](#), [6004](#), [6210](#), [6227](#), [6265](#), [6954](#),
[7118](#), [7578](#), [7869](#), [7884](#), [8004](#), [8008](#),
[8049](#), [8156](#), [8157](#), [8164](#), [8171](#), [8177](#),
[8184](#), [8259](#), [8873](#), [9770](#), [9862](#), [11073](#),
[15680](#), [15770](#), [18509](#), [19683](#), [20784](#)
- \tl_if_empty_p:N [38](#), [38](#), [2883](#)
- \tl_if_empty_p:n ... [38](#), [38](#), [2895](#), [2908](#)
- \tl_if_eq:NN [329](#)
- \tl_if_eq:nn(TF) [98](#), [98](#)
- \tl_if_eq:Ntf [38](#), [38](#),
[39](#), [83](#), [348](#), [2919](#), [2929](#), [2930](#), [3001](#),
[4247](#), [7382](#), [7850](#), [7904](#), [17257](#), [17260](#)
- \tl_if_eq:nnTF [38](#), [38](#), [61](#), [61](#), [348](#), [2931](#)
- \tl_if_eq_p:NN [38](#), [38](#), [2919](#)
- \tl_if_exist:N [3467](#), [3468](#)
- \tl_if_exist:Ntf
. [35](#), [35](#), [2538](#), [2540](#), [2557](#), [3062](#), [3387](#)
- \tl_if_exist_p:N [35](#), [35](#), [2557](#)
- \tl_if_head_eq_catcode:nN [322](#)
- \tl_if_head_eq_catcode:nTF
..... [44](#), [44](#), [3249](#), [18598](#), [18598](#)
- \tl_if_head_eq_catcode_p:nN
..... [44](#), [44](#), [3249](#)
- \tl_if_head_eq_charcode:nN [321](#)
- \tl_if_head_eq_charcode:nTF
..... [44](#), [44](#), [3249](#), [3266](#), [3267](#)
- \tl_if_head_eq_charcode_p:nN
..... [44](#), [44](#), [3249](#)
- \tl_if_head_eq_meaning:nN [322](#)
- \tl_if_head_eq_meaning:nTF
..... [44](#), [44](#), [3249](#)
- \tl_if_head_eq_meaning_p:nN
..... [44](#), [44](#), [3249](#)
- \tl_if_head_is_group:nTF
..... [45](#), [45](#), [3156](#),
[3278](#), [3313](#), [3339](#), [18625](#), [18689](#), [19416](#)
- \tl_if_head_is_group_p:n [45](#), [45](#), [3339](#)
- \tl_if_head_is_N_type:n [322](#)
- \tl_if_head_is_N_type:nTF
.. [45](#), [45](#), [3153](#), [3253](#), [3272](#), [3289](#),
[3322](#), [18506](#), [18622](#), [18686](#), [18902](#),
[18934](#), [19027](#), [19077](#), [19413](#), [19531](#)
- \tl_if_head_is_N_type_p:n [45](#), [45](#), [3322](#)
- \tl_if_head_is_space:nTF
..... [45](#), [45](#), [3350](#), [3880](#)
- \tl_if_head_is_space_p:n [45](#), [45](#), [3350](#)
- \tl_if_in:Nn [409](#)
- \tl_if_in:NnTF [38](#), [38](#), [2828](#), [2946](#),
[2946](#), [2947](#), [2949](#), [2950](#), [5599](#), [8374](#)
- \tl_if_in:nnTF .. [38](#), [38](#), [312](#), [312](#),
[2748](#), [2812](#), [2814](#), [2946](#), [2947](#), [2948](#),
[2952](#), [2960](#), [2961](#), [8456](#), [17066](#), [19681](#)
- \tl_if_single:n [312](#)
- \tl_if_single:Ntf
..... [38](#), [38](#), [2963](#), [2964](#), [2965](#)
- \tl_if_single:nTF
.. [39](#), [39](#), [2964](#), [2965](#), [2966](#), [2967](#), [8284](#)
- \tl_if_single_p:N [38](#), [38](#), [2963](#)
- \tl_if_single_p:n .. [39](#), [39](#), [2963](#), [2967](#)
- \tl_if_single_token:nTF
..... [216](#), [216](#), [18504](#)
- \tl_if_single_token_p:n
..... [216](#), [216](#), [18504](#)
- \tl_item:Nn [45](#), [3362](#)
- \tl_item:nn .. [45](#), [45](#), [808](#), [3362](#), [19580](#)
- \tl_log:N [46](#), [46](#), [3393](#)
- \tl_log:n [46](#), [46](#), [3393](#)
- \tl_lower_case:n [217](#), [18599](#)
- tl_lower_case:n [53](#)
- \tl_lower_case:nn [217](#), [18599](#)
- \tl_map_break: [40](#),
[40](#), [3016](#), [3022](#), [3033](#), [3042](#), [3049](#), [3054](#)
- \tl_map_break:n
..... [40](#), [40](#), [40](#), [3054](#), [16062](#), [16069](#)
- \tl_map_function:NN
..... [39](#), [39](#), [39](#), [39](#), [3012](#), [3077](#), [8366](#)
- \tl_map_function:nN
[39](#), [39](#), [39](#), [39](#), [1929](#), [3012](#), [3072](#), [4147](#)
- \tl_map_inline:Nn
.. [39](#), [39](#), [40](#), [713](#), [3026](#), [16062](#), [16069](#)
- \tl_map_inline:nn [39](#), [39](#),
[40](#), [85](#), [3026](#), [8790](#), [11907](#), [11959](#), [15997](#)
- \tl_map_variable:NNn ... [40](#), [40](#), [3038](#)
- \tl_map_variable:nNn [40](#), [40](#), [315](#), [3038](#)
- \tl_mixed_case:n [217](#), [18599](#)
- tl_mixed_case:n [53](#), [219](#)
- \tl_mixed_case:nn ... [217](#), [786](#), [18599](#)

- \l_tl_mixed_case_ignore_tl 219, 19489, 19568
- \l_tl_mixed_change_ignore_tl . . 219
- \tl_new:N 34, 34, 35, 110, 300, 2513, 2538, 2540, 2944, 2945, 3398, 3399, 3400, 3401, 4082, 4083, 5596, 5918, 5920, 5921, 6643, 7002, 7210, 7482, 7797, 7798, 8106, 8321, 8342, 8343, 8522, 8667, 8765, 8767, 8779, 8781, 8782, 8784, 9518, 9519, 9520, 9663, 9665, 9666, 9669, 9670, 9674, 9675, 16566, 16589, 16590, 17179, 18272, 19393, 19558, 19563, 19568, 19814, 19851, 20212, 20602, 20694
- \tl_put_left:Nn 35, 35, 2579, 2647, 2648
- \tl_put_right:Nn 35, 35, 2603, 2651, 2652, 4207, 6675, 6677, 6680, 6682, 6688, 6690, 6692, 6694, 6695, 6697, 6699, 6701, 6703, 9000, 9003, 9008, 10186
- \tl_rand_item:N 220, 220, 19577
- \tl_rand_item:n 220, 220, 19577
- \tl_range:Nnn 221, 221, 19584
- \tl_range:nnn 221, 221, 19584
- \tl_remove_all:Nn 36, 36, 36, 36, 2867, 8373
- \tl_remove_once:Nn 36, 36, 2861
- \tl_replace_all:Nnn 36, 36, 346, 406, 2792, 2868, 4156
- \tl_replace_once:Nnn 36, 36, 2792, 2862, 6718
- \tl_rescan:nn . 37, 37, 37, 37, 37, 2689
- \tl_reverse:N 42, 42, 42, 3210
- \tl_reverse:n 42, 42, 42, 42, 784, 3190, 3211, 3213
- \tl_reverse_items:n 42, 42, 42, 42, 3082
- \tl_reverse_tokens:n 216, 216, 216, 18514
- .tl_set:N 163, 10075
- \tl_set:Nn 35, 35, 36, 37, 58, 163, 292, 300, 306, 454, 713, 713, 2552, 2561, 2645, 2677, 2690, 2719, 2778, 2793, 2797, 2934, 2935, 3048, 3101, 3211, 4114, 4119, 4139, 4146, 4150, 4161, 4176, 4187, 4233, 4243, 4252, 4259, 4292, 4295, 4316, 4324, 4333, 4343, 4352, 4362, 4372, 4386, 4409, 4413, 4505, 4996, 5942, 5970, 6016, 6050, 6056, 6059, 6065, 6072, 6097, 6149, 6180, 6307, 6673, 6678, 7020, 7041, 7256, 7272, 7273, 7281, 7282, 7284, 7290, 7293, 7316, 7317, 7326, 7338, 7342, 7360, 7365, 7423, 7808, 7890, 8104, 8286, 8356, 8359, 8360, 8376, 8400, 8405, 8421, 8582, 8705, 8772, 8833, 8839, 8840, 8852, 8864, 9011, 9030, 9032, 9527, 9546, 9553, 9570, 9577, 9588, 9644, 9681, 9683, 9711, 9724, 9730, 9733, 9742, 9743, 9746, 9846, 10101, 10103, 10114, 10115, 10132, 10133, 10166, 10178, 10184, 10246, 15870, 16047, 16061, 16074, 16573, 16577, 16770, 17067, 17068, 17181, 17184, 18464, 18474, 18555, 18578, 18580, 18592, 19185, 19205, 19358, 19394, 19560, 19565, 19569, 19815, 19820, 19852, 19857, 20213, 20218, 20603, 20608
- \tl_set_eq:Nn . 35, 35, 2532, 2543, 2658, 3442, 4104, 4105, 4106, 4107, 5933, 5934, 5935, 5936, 7230, 7231, 7232, 7233, 7853, 7861, 10240, 15878
- \tl_set_from_file:Nnn 220, 220, 18554
- \tl_set_from_file_x:Nnn 220, 220, 18579
- \tl_set_rescan:Nnn 37, 37, 37, 37, 2689
- .tl_set_x:N 163, 10075
- \tl_show:N 45, 45, 46, 326, 3385, 3394, 3939
- \tl_show:n 46, 46, 46, 326, 3391, 3397, 3938
- \tl_sort:Nn 43, 43, 3144, 16059
- \tl_sort:nN 43, 43, 718, 718, 719, 3144, 16196
- \tl_tail:N 44, 3216
- \tl_tail:n 44, 44, 44, 3216
- \tl_to_lowercase:n . 107, 3402, 17572
- \tl_to_str:N 41, 41, 47, 141, 484, 3058, 3388, 3523, 3898, 8361, 8840, 8845
- \tl_to_str:n 37, 37, 41, 41, 41, 41, 47, 47, 53, 53, 54, 54, 121, 121, 135, 141, 160, 167, 167, 264, 313, 313, 313, 325, 331, 337, 427, 427, 441, 442, 527, 1319, 1340, 1466, 1534, 2331, 2340, 2343, 2351, 2357, 2711, 2809, 2898, 2970, 3058, 3229, 3392, 3452, 3594, 3616, 3640, 3647, 3698, 3705, 3778, 3797, 3808, 3833, 3841, 3849, 3855, 3867, 5271, 5288, 5332, 6843, 6847, 6879, 6880, 6913, 6926, 6928, 6930, 6948, 7175, 7243, 7301, 7302, 7344, 7367, 7391, 7392, 7697, 7698, 7942, 7943, 8240, 8241, 8242, 8243, 8276, 8277, 8306, 8310, 8311, 8315, 8316, 8458, 8499, 8512, 8773, 8788, 9195, 9317, 9419, 9612, 10330, 11212,

- 11217, 11324, 11325, 11331, 11334,
 12194, 17209, 17292, 17533, 17536,
 18340, 18789, 18792, 19676, 19681
 \tl_to_uppercase:n . . . 108, 3402, 17573
 \tl_trim_spaces:N 42, 42, 3098
 \tl_trim_spaces:n 42, 42, 46, 3098, 4168
 \tl_trim_spaces:n 317
 \tl_upper_case:n 217, 217, 18599
 \tl_upper_case:n 53
 \tl_upper_case:nn . . . 217, 217, 18599
 \tl_use:N 41,
 41, 68, 149, 153, 156, 3060, 9912, 19515
 \g_tmpa_tl 46, 3398
 \l_tmpa_tl 4, 36, 36, 36, 46, 3400
 \g_tmpb_tl 46, 3398
 \l_tmpb_tl 46, 3400
 tl internal commands:
 \c_tl_accents_lt_tl 795
 __tl_act:NNNnn 318, 318,
 319, 319, 784, 3144, 3195, 18519, 18542
 __tl_act_count_group:nn 18538
 __tl_act_count_normal:nN 18538
 __tl_act_count_space:n 18538
 __tl_act_end:w 3144
 __tl_act_end:wn 784, 3165, 3171
 __tl_act_group:nwnNNN 3144
 __tl_act_group_recurse:Nnn
 18529, 18533
 __tl_act_loop:w 3144
 __tl_act_normal:NwnNNN 3144
 __tl_act_output:n 319, 3144
 __tl_act_result:n
 318, 3149, 3171, 3186, 3187, 3188, 3189
 __tl_act_reverse 319
 __tl_act_reverse_output:n
 3144, 3205, 3207, 3209, 18530
 __tl_act_space:wnnNNN 318, 3144
 __tl_case:NnTF
 2980, 2985, 2990, 2995, 2997
 __tl_case:nnTF 2977
 __tl_case:Nw 2977
 __tl_case_end:nw 2977
 __tl_change_case:nnn
 18599, 18600, 18602, 18603, 18605
 __tl_change_case_aux:nnn 18605
 __tl_change_case_char:nN
 18605, 19517
 __tl_change_case_char:Nnn . . . 18605
 __tl_change_case_char_auxi:nN 18605
 __tl_change_case_char_auxii:nN .
 18605
 __tl_change_case_char_UTFviii:nn
 18605
 __tl_change_case_char_UTFviii:nN
 18605
 __tl_change_case_char_UTFviii:nnN
 18605
 __tl_change_case_char_UTFviii:nnNN
 18605
 __tl_change_case_char_UTFviii:nnNNN
 18749, 18785
 __tl_change_case_cs:N 18605
 __tl_change_case_cs:NN 18605
 __tl_change_case_cs:NNn 18605
 __tl_change_case_cs_accents:NN .
 18605
 __tl_change_case_cs_expand:NN 18605
 __tl_change_case_cs_expand:Nnw .
 18605
 __tl_change_case_cs_letterlike:Nnn
 18605, 19465
 __tl_change_case_end:wn 18605, 19442
 __tl_change_case_group:nwnn . 18605
 __tl_change_case_if_expandable:NTF
 18605,
 18908, 18941, 19033, 19083, 19537
 __tl_change_case_loop:wn 794
 __tl_change_case_loop:wnn
 787, 789, 18605, 19432, 19471, 19475
 __tl_change_case_lower_az:Nnw 18920
 __tl_change_case_lower_lt:nNnw .
 18990
 __tl_change_case_lower_lt:NNw 18990
 __tl_change_case_lower_lt:Nnw 18990
 __tl_change_case_lower_lt:nnw 18990
 __tl_change_case_lower_lt:Nw . 18990
 __tl_change_case_lower_sigma:Nnw
 18890
 __tl_change_case_lower_sigma:Nw
 18890
 __tl_change_case_lower_sigma:w .
 18890
 __tl_change_case_lower_tr:Nnw 18920
 __tl_change_case_lower_tr_-
 auxi:Nw 18920
 __tl_change_case_lower_tr_-
 auxii:Nw 18920
 __tl_change_case_math:NNNnnn . . .
 788, 18605, 19455
 __tl_change_case_math:NwNNnn . 18605
 __tl_change_case_math_group:nwNNnn
 18605
 __tl_change_case_math_loop:wNNnn
 18605

- _tl_change_case_math_space:wNNnn [18605](#)
- _tl_change_case_mixed_nl:NNw [19519](#)
- _tl_change_case_mixed_nl:Nnw [19519](#)
- _tl_change_case_mixed_nl:Nw . [19519](#)
- _tl_change_case_N_type:Nnnn . [18605](#)
- _tl_change_case_N_type:NNNnnn . [18605](#)
- _tl_change_case_N_type:Nwnn . [18605](#)
- _tl_change_case_output:nwn ... [18605](#), [18894](#), [18928](#), [18936](#), [18950](#), [18952](#), [18962](#), [18973](#), [18985](#), [19012](#), [19021](#), [19049](#), [19071](#), [19100](#), [19424](#), [19436](#), [19500](#), [19514](#), [19525](#), [19551](#)
- _tl_change_case_protect:wNN . [18605](#)
- _tl_change_case_result:n [18618](#), [18631](#), [18632](#), [18634](#), [19409](#)
- _tl_change_case_setup:NN [19369](#), [19374](#), [19376](#)
- _tl_change_case_space:wnn .. [18605](#)
- _tl_change_case_upper_az:Nnw [18920](#)
- _tl_change_case_upper_de-alt:Nnw [19097](#)
- _tl_change_case_upper_lt:NNw [18990](#)
- _tl_change_case_upper_lt:Nnw [18990](#)
- _tl_change_case_upper_lt:nnw [18990](#)
- _tl_change_case_upper_lt:Nw . [18990](#)
- _tl_change_case_upper_sigma:Nnw [18890](#)
- _tl_change_case_upper_tr:Nnw [18920](#)
- _tl_count:n [316](#), [3069](#)
- _tl_from_file_do:w [18554](#)
- _tl_head_auxi:nw [3216](#)
- _tl_head_auxii:n [3216](#)
- _tl_if_blank_p:NNw [2873](#)
- _tl_if_empty_return:n . [310](#), [311](#), [2874](#), [2908](#), [5579](#), [5585](#), [18507](#), [18511](#)
- _tl_if_head_eq_meaning_-normal:nN [3290](#), [3294](#)
- _tl_if_head_eq_meaning_-special:nN [3291](#), [3303](#)
- _tl_if_head_is_N_type:w . [323](#), [3322](#)
- _tl_if_head_is_space:w [3350](#)
- _tl_if_single:nnw .. [313](#), [2969](#), [2976](#)
- _tl_if_single:nTF [2967](#)
- _tl_if_single_p:n [2967](#)
- \l_tl_internal_a_tl [303](#), [2714](#), [2719](#), [2778](#), [2931](#), [18572](#), [18578](#), [18592](#), [18595](#), [19185](#), [19187](#), [19205](#), [19210](#), [19358](#), [19360](#)
- \l_tl_internal_b_tl [2931](#)
- _tl_item:nn [3362](#)
- _tl_item_aux:nn [3362](#)
- _tl_lookup_lower:N [18605](#)
- _tl_lookup_title:N [18605](#)
- _tl_lookup_upper:N [18605](#)
- _tl_loop:nn ... [19202](#), [19211](#), [19242](#)
- _tl_map_function:Nn [314](#), [3012](#), [3030](#)
- _tl_map_variable:Nnn [3038](#)
- _tl_mixed_case:nn [18601](#), [18604](#), [19396](#)
- _tl_mixed_case_aux:nn [19396](#)
- _tl_mixed_case_char:N [19396](#)
- _tl_mixed_case_char:Nn [19470](#), [19476](#)
- _tl_mixed_case_char:nN [19396](#)
- _tl_mixed_case_group:nwn ... [19396](#)
- _tl_mixed_case_letterlike:Nw [19396](#)
- _tl_mixed_case_loop:wn [19396](#)
- _tl_mixed_case_N_type:Nnn . [19396](#)
- _tl_mixed_case_N_type:NNNnn . [19396](#)
- _tl_mixed_case_N_type:Nwn . [19396](#)
- _tl_mixed_case_N_type:N [19396](#)
- _tl_mixed_case_skip:NN [19396](#)
- _tl_mixed_case_skip_tidy:Nwn [19396](#)
- _tl_mixed_case_space:wn [19396](#)
- _tl_range:nnnw [19584](#)
- _tl_range:nnw [808](#), [19584](#)
- _tl_range_collect:w ... [808](#), [19584](#)
- _tl_range_normalize:nn [19584](#), [19633](#)
- _tl_range_skip:w [808](#), [19584](#)
- _tl_replace:NnNNNnn [306](#), [307](#), [2793](#), [2795](#), [2797](#), [2799](#), [2804](#)
- _tl_replace_auxi:NnnNNNnn [307](#), [2804](#)
- _tl_replace_auxii:nNNNnn [307](#), [307](#), [308](#), [2804](#)
- _tl_replace_next:w [306](#), [308](#), [308](#), [308](#), [308](#), [2797](#), [2799](#), [2804](#)
- _tl_replace_wrap:w ... [306](#), [308](#), [308](#), [308](#), [308](#), [2793](#), [2795](#), [2804](#)
- _tl_rescan:w [305](#), [305](#), [2689](#), [2770](#), [2771](#), [2786](#)
- \c_tl_rescan_marker_tl [305](#), [2688](#), [2706](#), [2727](#), [2775](#), [18566](#), [18577](#)
- _tl_reverse_group:nn [18514](#)
- _tl_reverse_group_preserve:nn [3190](#)
- _tl_reverse_items:nwNwn [3082](#)
- _tl_reverse_items:wn [3082](#)
- _tl_reverse_normal:nN . [3190](#), [18520](#)
- _tl_reverse_space:n .. [3190](#), [18522](#)
- _tl_set_from_file:NNnn [18554](#)
- _tl_set_from_file_x:NNnn ... [18579](#)
- _tl_set_rescan:n [303](#), [303](#), [2711](#), [2733](#)
- _tl_set_rescan:NNnn [2689](#)
- _tl_set_rescan:NnTF [2733](#)
- _tl_set_rescan_multi:n [303](#), [305](#), [2689](#), [2743](#)
- _tl_set_rescan_multiple:n ... [304](#)
- _tl_set_rescan_single:nn [304](#), [2733](#)

- _tl_set_rescan_single_aux:nn [2733](#)
- _tl_tmp:w [312](#),
[317](#), [2955](#), [2956](#), [3106](#), [3143](#), [19168](#),
[19172](#), [19175](#), [19187](#), [19191](#), [19192](#),
[19193](#), [19194](#), [19210](#), [19213](#), [19344](#),
[19347](#), [19360](#), [19363](#), [19364](#), [19365](#)
- _tl_trim_spaces:nn [46](#),
[46](#), [505](#), [3099](#), [3106](#), [5990](#), [6432](#), [9644](#)
- _tl_trim_spaces_auxi:w .. [317](#), [3106](#)
- _tl_trim_spaces_auxii:w . [317](#), [3106](#)
- _tl_trim_spaces_auxiii:w [317](#), [3106](#)
- _tl_trim_spaces_auxiv:w . [317](#), [3106](#)
- token commands:
- \c_alignment_token [109](#), [423](#), [6741](#), [6780](#)
- \c_parameter_token
..... [109](#), [424](#), [6741](#), [6784](#), [6787](#)
- \g_peek_token ... [114](#), [114](#), [6999](#), [7010](#)
- \l_peek_token . [113](#), [114](#), [433](#), [433](#),
[810](#), [810](#), [6999](#), [7008](#), [7058](#), [7070](#),
[7090](#), [7099](#), [19659](#), [19660](#), [19661](#), [19664](#)
- \c_space_token [45](#),
[46](#), [109](#), [221](#), [322](#), [424](#), [3280](#), [3315](#),
[6741](#), [6804](#), [7099](#), [8933](#), [18593](#), [19661](#)
- \token_get_arg_spec:N [116](#), [116](#), [7173](#)
- \token_get_prefix_spec:N
..... [117](#), [117](#), [7173](#)
- \token_get_replacement_spec:N ...
..... [116](#), [116](#), [7173](#), [10372](#)
- \token_if_active:NTF . [111](#), [111](#), [6817](#)
- \token_if_active_p:N . [111](#), [111](#), [6817](#)
- \token_if_alignment:NTF
..... [110](#), [110](#), [111](#), [6778](#)
- \token_if_alignment_p:N [110](#), [110](#), [6778](#)
- \token_if_chardef:NTF [112](#), [112](#), [6891](#)
- \token_if_chardef_p:N [112](#), [112](#), [6891](#)
- \token_if_cs:NTF
..... [112](#), [112](#), [6856](#), [18719](#), [19463](#)
- \token_if_cs_p:N [112](#),
[112](#), [6856](#), [18948](#), [19040](#), [19090](#), [19544](#)
- \token_if_dim_register:NTF
..... [112](#), [112](#), [6891](#)
- \token_if_dim_register_p:N
..... [112](#), [112](#), [6891](#)
- \token_if_eq_catcode:NNTF
... [111](#), [111](#), [114](#), [114](#), [114](#), [114](#), [6827](#)
- \token_if_eq_catcode_p:NN
..... [111](#), [111](#), [6827](#)
- \token_if_eq_charcode:NNTF
..... [111](#), [111](#),
[114](#), [115](#), [115](#), [115](#), [6832](#), [8392](#), [8933](#)
- \token_if_eq_charcode_p:NN
..... [111](#), [111](#), [6832](#)
- \token_if_eq_meaning:NNTF
..... [111](#), [111](#),
[115](#), [115](#), [115](#), [116](#), [433](#), [6822](#), [8985](#),
[10868](#), [11853](#), [12628](#), [12630](#), [12635](#),
[14773](#), [18669](#), [18697](#), [18701](#), [19451](#)
- \token_if_eq_meaning_p:NN
..... [111](#), [111](#), [6822](#), [18873](#)
- \token_if_expandable:NTF
..... [112](#), [112](#), [6861](#), [18869](#)
- \token_if_expandable_p:N
..... [112](#), [112](#), [6861](#)
- \token_if_group_begin:NTF
..... [110](#), [110](#), [6763](#)
- \token_if_group_begin_p:N
..... [110](#), [110](#), [6763](#)
- \token_if_group_end:NTF [110](#), [110](#), [6768](#)
- \token_if_group_end_p:N [110](#), [110](#), [6768](#)
- \token_if_int_register:NTF
..... [113](#), [113](#), [6891](#)
- \token_if_int_register_p:N
..... [113](#), [113](#), [6891](#)
- \token_if_letter:N [426](#)
- \token_if_letter:NTF
..... [111](#), [111](#), [6807](#), [18914](#)
- \token_if_letter_p:N . [111](#), [111](#), [6807](#)
- \token_if_long_macro:NTF
..... [112](#), [112](#), [6891](#)
- \token_if_long_macro_p:N
..... [112](#), [112](#), [6891](#)
- \token_if_macro:NTF
..... [112](#), [112](#), [6837](#), [6943](#), [7179](#), [7188](#), [7197](#)
- \token_if_macro_p:N .. [112](#), [112](#), [6837](#)
- \token_if_math_subscript:NTF ...
..... [111](#), [111](#), [6797](#)
- \token_if_math_subscript_p:N ...
..... [111](#), [111](#), [6797](#)
- \token_if_math_superscript:NTF ..
..... [111](#), [111](#), [6791](#)
- \token_if_math_superscript_p:N ..
..... [111](#), [111](#), [6791](#)
- \token_if_math_toggle:NTF
..... [110](#), [110](#), [6773](#)
- \token_if_math_toggle_p:N
..... [110](#), [110](#), [6773](#)
- \token_if_mathchardef:NTF
..... [112](#), [112](#), [6891](#)
- \token_if_mathchardef_p:N
..... [112](#), [112](#), [6891](#)
- \token_if_muskip_register:NTF ...
..... [113](#), [113](#), [6891](#)
- \token_if_muskip_register_p:N ...
..... [113](#), [113](#), [6891](#)
- \token_if_other:NTF .. [111](#), [111](#), [6812](#)
- \token_if_other_p:N .. [111](#), [111](#), [6812](#)
- \token_if_parameter:NTF ... [111](#), [6783](#)
- \token_if_parameter_p:N [111](#), [111](#), [6783](#)

- \token_if_primitive:NTF [113](#), [113](#), [6937](#)
 - \token_if_primitive_p:N [113](#), [113](#), [6937](#)
 - \token_if_protected_long_
 - macro:NTF [112](#), [112](#), [6891](#)
 - \token_if_protected_long_macro_
 - p:N [112](#), [112](#), [6891](#), [18875](#)
 - \token_if_protected_macro:NTF ...
 - [112](#), [112](#), [6891](#)
 - \token_if_protected_macro_p:N ...
 - [112](#), [112](#), [6891](#), [18874](#)
 - \token_if_skip_register:NTF
 - [113](#), [113](#), [6891](#)
 - \token_if_skip_register_p:N
 - [113](#), [113](#), [6891](#)
 - \token_if_space:NTF .. [111](#), [111](#), [6802](#)
 - \token_if_space_p:N .. [111](#), [111](#), [6802](#)
 - \token_if_toks_register:NTF
 - [113](#), [113](#), [6891](#)
 - \token_if_toks_register_p:N
 - [113](#), [113](#), [6891](#)
 - \token_new:Nn [109](#), [109](#), [6740](#)
 - \token_to_meaning:N
 - [110](#), [110](#), [425](#), [429](#), [1317](#),
 - [1331](#), [1746](#), [1756](#), [2340](#), [6740](#), [6843](#),
 - [6912](#), [6947](#), [7182](#), [7191](#), [7200](#), [19664](#)
 - \token_to_str:N
 - [4](#), [17](#), [47](#), [110](#), [110](#), [110](#),
 - [135](#), [141](#), [268](#), [324](#), [365](#), [427](#), [427](#),
 - [563](#), [563](#), [565](#), [1319](#), [1331](#), [1331](#),
 - [1450](#), [1459](#), [1480](#), [1501](#), [1542](#), [1547](#),
 - [1562](#), [1594](#), [1595](#), [1605](#), [1611](#), [1746](#),
 - [1756](#), [1758](#), [1771](#), [1781](#), [1902](#), [1932](#),
 - [1939](#), [2025](#), [2039](#), [2365](#), [2426](#), [2441](#),
 - [2474](#), [2485](#), [2498](#), [2688](#), [3327](#), [3343](#),
 - [3388](#), [3406](#), [3415](#), [4810](#), [5602](#), [5704](#),
 - [6740](#), [6924](#), [6925](#), [6930](#), [6931](#), [6932](#),
 - [6933](#), [6934](#), [6935](#), [8262](#), [8268](#), [8822](#),
 - [8823](#), [8824](#), [8825](#), [8826](#), [9083](#), [9084](#),
 - [9556](#), [9580](#), [10755](#), [10756](#), [11211](#),
 - [11224](#), [11225](#), [11254](#), [11383](#), [11430](#),
 - [11462](#), [11482](#), [11497](#), [11509](#), [11510](#),
 - [11523](#), [11524](#), [11549](#), [11558](#), [11560](#),
 - [11585](#), [11588](#), [11613](#), [11615](#), [11629](#),
 - [11645](#), [11663](#), [11732](#), [11742](#), [11743](#),
 - [11758](#), [11759](#), [12061](#), [14841](#), [15905](#),
 - [16289](#), [16305](#), [16338](#), [16339](#), [16347](#),
 - [16348](#), [16482](#), [16615](#), [16769](#), [17356](#),
 - [17533](#), [17536](#), [18759](#), [18800](#), [18803](#),
 - [18811](#), [19372](#), [19373](#), [19390](#), [19391](#)
 - token internal commands:
 - \c__token_A_int [6937](#), [6974](#)
 - __token_delimit_by_char":w .. [6873](#)
 - __token_delimit_by_count:w .. [6873](#)
 - __token_delimit_by_dimen:w .. [6873](#)
 - __token_delimit_by_macro:w .. [6873](#)
 - __token_delimit_by_muskip:w .. [6873](#)
 - __token_delimit_by_skip:w ... [6873](#)
 - __token_delimit_by_toks:w ... [6873](#)
 - __token_if_macro_p:w [6837](#)
 - __token_if_primitive:NNw [6937](#)
 - __token_if_primitive:Nw [6937](#)
 - __token_if_primitive_loop:N . [6937](#)
 - __token_if_primitive_nullfont:N
 - [6937](#)
 - __token_if_primitive_space:w . [6937](#)
 - __token_if_primitive_undefined:N
 - [6937](#)
 - __token_tmp:w [427](#), [6874](#),
 - [6883](#), [6884](#), [6885](#), [6886](#), [6887](#), [6888](#),
 - [6889](#), [6892](#), [6924](#), [6925](#), [6926](#), [6927](#),
 - [6929](#), [6931](#), [6932](#), [6933](#), [6934](#), [6935](#)
 - \toks [561](#), [6935](#)
 - \toksapp [930](#)
 - \toksdef [562](#), [16285](#)
 - \tokspre [931](#)
 - \tolerance [563](#)
 - \topmark [564](#)
 - \topmarks [666](#)
 - \topskip [565](#)
 - \tpack [932](#)
 - \tracingassigns [667](#)
 - \tracingcommands [566](#)
 - \tracingfonts [973](#)
 - \tracinggroups [668](#)
 - \tracingifs [669](#)
 - \tracinglostchars [567](#)
 - \tracingmacros [568](#)
 - \tracingnesting [670](#)
 - \tracingonline [569](#)
 - \tracingoutput [570](#)
 - \tracingpages [571](#)
 - \tracingparagraphs [572](#)
 - \tracingrestores [573](#)
 - \tracingscantokens [671](#)
 - \tracingstats [574](#)
 - true [188](#)
 - trunc [184](#)
 - two commands:
 - \c_thirty_two [78](#), [5386](#)
 - \c_two_hundred_fifty_five .. [78](#), [5387](#)
 - \c_two_hundred_fifty_six ... [78](#), [5387](#)
- U**
- \u [19395](#)
 - \uccode .. [167](#), [182](#), [195](#), [197](#), [199](#), [201](#), [575](#)
 - \Uchar [975](#)
 - \Ucharcat [976](#)
 - \uchyph [576](#)

| | | | |
|--|-----------|--|------|
| <code>\ucs</code> | 1161 | <code>\Umathlimitbelowvgap</code> | 1030 |
| <code>\Udelcode</code> | 977 | <code>\Umathnolimitsubfactor</code> | 1031 |
| <code>\Udelcodenum</code> | 978 | <code>\Umathnolimitsupfactor</code> | 1032 |
| <code>\Udelimiter</code> | 979 | <code>\Umathopbinspacing</code> | 1033 |
| <code>\Udelimiterover</code> | 980 | <code>\Umathopclosespacing</code> | 1034 |
| <code>\Udelimiterunder</code> | 981 | <code>\Umathopenbinspacing</code> | 1035 |
| <code>\Uhexensible</code> | 982 | <code>\Umathopenclosespacing</code> | 1036 |
| <code>\Umathaccent</code> | 983 | <code>\Umathopeninnerspacing</code> | 1037 |
| <code>\Umathaxis</code> | 984 | <code>\Umathopenopenspacing</code> | 1038 |
| <code>\Umathbinbinspacing</code> | 985 | <code>\Umathopenopspacing</code> | 1039 |
| <code>\Umathbinclosespacing</code> | 986 | <code>\Umathopenordspacing</code> | 1040 |
| <code>\Umathbininnerspacing</code> | 987 | <code>\Umathopenpunctspacing</code> | 1041 |
| <code>\Umathbinopenspacing</code> | 988 | <code>\Umathopenrelspacing</code> | 1042 |
| <code>\Umathbinopspacing</code> | 989 | <code>\Umathoperatorsize</code> | 1043 |
| <code>\Umathbinordspacing</code> | 990 | <code>\Umathopinnerspacing</code> | 1044 |
| <code>\Umathbinpunctspacing</code> | 991 | <code>\Umathopopenspacing</code> | 1045 |
| <code>\Umathbinrelspacing</code> | 992 | <code>\Umathopopspacing</code> | 1046 |
| <code>\Umathchar</code> | 993 | <code>\Umathopordspacing</code> | 1047 |
| <code>\Umathcharclass</code> | 994 | <code>\Umathoppunctspacing</code> | 1048 |
| <code>\Umathchardef</code> | 995 | <code>\Umathoprelspacing</code> | 1049 |
| <code>\Umathcharfam</code> | 996 | <code>\Umathordbinspacing</code> | 1050 |
| <code>\Umathcharnum</code> | 997 | <code>\Umathordclosespacing</code> | 1051 |
| <code>\Umathcharnumdef</code> | 998 | <code>\Umathordinnerspacing</code> | 1052 |
| <code>\Umathcharslot</code> | 999 | <code>\Umathordopenspacing</code> | 1053 |
| <code>\Umathclosebinspacing</code> | 1000 | <code>\Umathordopspacing</code> | 1054 |
| <code>\Umathcloseclosespacing</code> | 1001 | <code>\Umathordordspacing</code> | 1055 |
| <code>\Umathcloseinnerspacing</code> | 1002 | <code>\Umathordpunctspacing</code> | 1056 |
| <code>\Umathcloseopenspacing</code> | 1003 | <code>\Umathordrelspacing</code> | 1057 |
| <code>\Umathcloseopspacing</code> | 1004 | <code>\Umathoverbarkern</code> | 1058 |
| <code>\Umathcloseordspacing</code> | 1005 | <code>\Umathoverbarrule</code> | 1059 |
| <code>\Umathclosepunctspacing</code> | 1006 | <code>\Umathoverbarvgap</code> | 1060 |
| <code>\Umathcloserelspacing</code> | 1007 | <code>\Umathoverdelimiterbgap</code> | 1061 |
| <code>\Umathcode</code> | 158, 1008 | <code>\Umathoverdelimitervgap</code> | 1062 |
| <code>\Umathcodenum</code> | 1009 | <code>\Umathpunctbinspacing</code> | 1063 |
| <code>\Umathconnectoroverlapmin</code> | 1010 | <code>\Umathpunctclosespacing</code> | 1064 |
| <code>\Umathfractiondelsize</code> | 1011 | <code>\Umathpunctinnerspacing</code> | 1065 |
| <code>\Umathfractiondenomdown</code> | 1012 | <code>\Umathpunctopenspacing</code> | 1066 |
| <code>\Umathfractiondenomvgap</code> | 1013 | <code>\Umathpunctopspacing</code> | 1067 |
| <code>\Umathfractionnumup</code> | 1014 | <code>\Umathpunctordspacing</code> | 1068 |
| <code>\Umathfractionnumvgap</code> | 1015 | <code>\Umathpunctpunctspacing</code> | 1069 |
| <code>\Umathfractionrule</code> | 1016 | <code>\Umathpunctrelspacing</code> | 1070 |
| <code>\Umathinnerbinspacing</code> | 1017 | <code>\Umathquad</code> | 1071 |
| <code>\Umathinnerclosespacing</code> | 1018 | <code>\Umathradicaldegreeafter</code> | 1072 |
| <code>\Umathinnerinnerspacing</code> | 1019 | <code>\Umathradicaldegreebefore</code> | 1073 |
| <code>\Umathinneropenspacing</code> | 1020 | <code>\Umathradicaldegreeraise</code> | 1074 |
| <code>\Umathinneropspacing</code> | 1021 | <code>\Umathradicalkern</code> | 1075 |
| <code>\Umathinnerordspacing</code> | 1022 | <code>\Umathradicalrule</code> | 1076 |
| <code>\Umathinnerpunctspacing</code> | 1023 | <code>\Umathradicalvgap</code> | 1077 |
| <code>\Umathinnerrelspacing</code> | 1024 | <code>\Umathrelbinspacing</code> | 1078 |
| <code>\Umathlimitabovebgap</code> | 1025 | <code>\Umathrelclosespacing</code> | 1079 |
| <code>\Umathlimitabovekern</code> | 1026 | <code>\Umathrelinnerspacing</code> | 1080 |
| <code>\Umathlimitabovevgap</code> | 1027 | <code>\Umathrelopenspacing</code> | 1081 |
| <code>\Umathlimitbelowbgap</code> | 1028 | <code>\Umathrelopspacing</code> | 1082 |
| <code>\Umathlimitbelowkern</code> | 1029 | <code>\Umathrelordspacing</code> | 1083 |

- \Umathrelpunctspacing 1084
- \Umathrelrelspacing 1085
- \Umathskewedfractionhgap 1086
- \Umathskewedfractionvgap 1087
- \Umathspaceafterscript 1088
- \Umathstackdenomdown 1089
- \Umathstacknumup 1090
- \Umathstackvgap 1091
- \Umathsubshiftdown 1092
- \Umathsubshiftdrop 1093
- \Umathsubsupshiftdown 1094
- \Umathsubsupvgap 1095
- \Umathsubtopmax 1096
- \Umathsupbottommin 1097
- \Umathsupshiftdrop 1098
- \Umathsupshiftdown 1099
- \Umathsupsubbottommax 1100
- \Umathunderbarkern 1101
- \Umathunderbarrule 1102
- \Umathunderbarvgap 1103
- \Umathunderdelimitervgap 1104
- \Umathunderdelimitervgap 1105
- undefine commands:
 - .undefine: 164, 10091
- \underline 577
- \unexpanded 672
- \unhbox 578
- \unhcopy 579
- unicode internal commands:
 - \c__unicode_accents_lt_tl 18993, 19142
 - __unicode_codepoint_to_UTFviii:n .. 19103, 19186, 19207, 19208, 19359
 - __unicode_codepoint_to_UTFviii-auxi:n 19103
 - __unicode_codepoint_to_UTFviii-auxii:Nnn 19103
 - __unicode_codepoint_to_UTFviii-auxiii:n 19103
 - \g__unicode_data_ior 3944, 3947, 3964, 3967, 3972, 3978
 - \c__unicode_dot_above_tl 19049, 19142
 - \c__unicode_dotless_i_tl 18936, 18950, 18962, 19165
 - \c__unicode_dotted_I_tl 18985, 19165
 - \c__unicode_final_sigma_tl 18904, 18916, 19142
 - \c__unicode_I_ogonek_tl 19061, 19165
 - \c__unicode_i_ogonek_tl 19006, 19165
 - __unicode_map_inline:n 3959, 4023, 4041, 4056
 - __unicode_map_loop: 3966, 3970, 3983
 - __unicode_parse:w .. 3981, 3986, 3993
 - __unicode_parse_auxi:w 3989, 4007, 4024, 4042
 - __unicode_parse_auxii:w 4009, 4010, 4035, 4039, 4044, 4045, 4048, 4051
 - \c__unicode_std_sigma_tl 18915, 19142
 - __unicode_store:nnnnn 3997, 4040, 4054
 - __unicode_tmp:NN ... 4059, 4067, 4069
 - \l__unicode_tmp_tl .. 3978, 3979, 3981
 - \c__unicode_upper_Eszett_tl 19100, 19142
 - \uniformdeviate 974
 - \unkern 580
 - \unless 673
 - \unpenalty 581
 - \unskip 582
 - \unvbox 583
 - \unvcopy 584
 - \Uoverdelimiter 1106
 - \uppercase 585
 - uptex commands:
 - \uptex_disablecjktoken:D 1155, 4711, 4714, 17474
 - \uptex_enablecjktoken:D 1156
 - \uptex_forcecjktoken:D 1157
 - \uptex_kchar:D 1158
 - \uptex_kchardef:D 1159, 4715
 - \uptex_kuten:D 1160
 - \uptex_ucs:D 1161
 - \Uradical 1107
 - \Uroot 1108
 - use commands:
 - \use:N 16, 16, 16, 81, 265, 1378, 1475, 1557, 1685, 1687, 1689, 1691, 3907, 3911, 4808, 5228, 5238, 5343, 5347, 5349, 5351, 5352, 5356, 5754, 5773, 7730, 7741, 7756, 7765, 7773, 7781, 7787, 7813, 8891, 9199, 9756, 9763, 9964, 18341, 18730, 18767, 18771, 18772
 - \use:n 17, 17, 19, 19, 34, 117, 218, 261, 305, 463, 463, 543, 563, 720, 720, 720, 720, 720, 728, 1379, 1384, 1462, 1508, 1528, 1608, 1849, 2348, 2354, 2375, 2495, 2634, 2694, 2766, 2768, 3050, 3306, 3885, 3975, 4044, 4045, 4048, 6309, 6697, 6755, 6837, 6876, 6894, 6938, 7694, 7711, 7939, 7956, 8196, 8249, 8385, 8636, 8658, 8741, 9314, 9765, 10367, 10791, 10799, 10808, 10825, 10833, 10861, 11214, 11293, 11328, 11357, 16039, 16281,

- 16477, 17450, 17456, 17464, 17478,
17485, 17494, 17504, 17507, 17514,
17519, 18361, 18416, 20041, 20075,
20088, 20769, 20809, 20826, 20844
\use:nn ... 17, 17, 1384, 2077, 2726,
6293, 7173, 9193, 11319, 14456, 18575
\use:nnn 17, 17, 1384, 1899
\use:nnnn 17, 17, 1384
\use_i:nn 18,
18, 18, 259, 263, 393, 394, 438, 542,
673, 676, 688, 691, 692, 704, 794,
1335, 1388, 1414, 1491, 1635, 1663,
1881, 2492, 3230, 4176, 4178, 5750,
5763, 5767, 5784, 5785, 7249, 10726,
11293, 11936, 11940, 11966, 13065,
13549, 13766, 14282, 14451, 15105,
15320, 15748, 16137, 16172, 16182,
16192, 17458, 17466, 17480, 17487,
17496, 17509, 17516, 18878, 18953
\use_i:nnn ... 18, 18, 18, 704, 1390,
1617, 4381, 5429, 7182, 13022, 15742
\use_i:nnnn
18, 18, 18, 1390, 13040, 13047, 13238
\use_i_delimit_by_q_nil:nw
..... 19, 19, 1401
\use_i_delimit_by_q_recursion_-
stop:nw 19,
19, 1401, 5521, 5537, 18370, 18385,
18671, 18830, 18853, 19453, 19498
\use_i_delimit_by_q_stop:nw
..... 19, 19,
337, 337, 1401, 3662, 3671, 3786,
3837, 3840, 6402, 15727, 15799, 18434
\use_i_ii:nnn
..... 18, 18, 1390, 2102, 4358, 4458
\use_ii:nn
... 18, 18, 95, 259, 263, 393, 394,
394, 438, 673, 676, 688, 691, 692,
702, 791, 796, 1337, 1388, 1416,
1493, 1637, 1665, 1879, 2046, 2738,
3232, 5763, 7250, 10699, 11938,
11942, 11968, 13067, 14284, 15107,
15322, 15684, 17451, 17505, 17520,
18727, 18877, 18880, 18919, 19481
\use_ii:nnn 18, 18, 465, 1390, 1619, 7191
\use_ii:nnnn 18, 18, 1390
\use_iii:nnn 18,
18, 542, 542, 1390, 2051, 7200, 10711
\use_iii:nnnn 18, 18, 1390
\use_iv:nnnn 18, 18, 1390
\use_none:n 18, 18, 22, 46,
310, 317, 317, 355, 404, 408, 449,
484, 560, 560, 560, 560, 792, 798,
1404, 1508, 1697, 1713, 1717, 1851,
1903, 2853, 2874, 3141, 3229, 3245,
3309, 3326, 3336, 3337, 3342, 3357,
3360, 3973, 4080, 4446, 4467, 5098,
5104, 5419, 5523, 5538, 5952, 6077,
6170, 6196, 6987, 7629, 8004, 8008,
8864, 8919, 8974, 9593, 9616, 9634,
10323, 10632, 10636, 10640, 10644,
10737, 11863, 12086, 12098, 12109,
12121, 12163, 12188, 12257, 12273,
12306, 13041, 13044, 13953, 14841,
15692, 15732, 15739, 16086, 17449,
17457, 17465, 17479, 17486, 17495,
17503, 17508, 17515, 17518, 18456,
18457, 18507, 19013, 20784, 20786
\use_none:nn
. 18, 308, 313, 321, 322, 352, 352,
352, 353, 527, 1404, 1452, 1460,
2836, 2970, 3097, 3256, 3275, 4248,
4367, 4388, 6210, 8920, 8963, 10331,
10585, 10631, 10635, 10639, 10643
\use_none:nnn 18, 322, 1404,
3297, 8921, 10630, 10634, 10638, 10642
\use_none:nnnn
18, 294, 1404, 2427, 2442, 4966, 8922
\use_none:nnnnn 18, 262, 486, 486,
546, 1404, 8923, 8932, 10786, 10820,
10846, 10854, 12641, 15745, 15761
\use_none:nnnnnn . 18, 1404, 1564, 8924
\use_none:nnnnnnn 18,
265, 546, 1404, 1482, 8925, 10788,
10822, 10848, 10856, 11146, 13081
\use_none:nnnnnnnn 18, 1404
\use_none:nnnnnnnn 18, 1404
\use_none_delimit_by_q_nil:w ...
..... 19, 19, 1398
\use_none_delimit_by_q_recursion_-
stop:w 19, 19, 85, 85, 85,
85, 1398, 1473, 1543, 1548, 1555,
2366, 2373, 2632, 4062, 5515, 5530
\use_none_delimit_by_q_stop:w ...
. 19, 19, 387, 406, 406, 810, 1398,
3660, 3669, 3824, 4824, 6157, 6388,
6393, 7831, 9203, 15728, 18360, 19666
use internal commands:
 __use_none_delimit_by_s__stop:w
 87, 87, 87, 5610
\useboxresource 967
\useimageresource 968
\Uskewed 1109
\Uskewedwithdelims 1110
\Ustack 1111
\Ustartdisplaymath 1112
\Ustartmath 1113
\Ustopdisplaymath 1114

| | | | |
|--|---|--|------------|
| <code>\Ustopmath</code> | 1115 | <code>\utex_mathaccent:D</code> | 983, 1250 |
| <code>\Usubscript</code> | 1116 | <code>\utex_mathaxis:D</code> | 984 |
| <code>\Usuperscript</code> | 1117 | <code>\utex_mathchar:D</code> | 993, 1251 |
| utex commands: | | <code>\utex_mathcharclass:D</code> | 994 |
| <code>\utex_binbinspacing:D</code> | 985 | <code>\utex_mathchardef:D</code> | 995, 1252 |
| <code>\utex_binclosespacing:D</code> | 986 | <code>\utex_mathcharfam:D</code> | 996 |
| <code>\utex_bininnerspacing:D</code> | 987 | <code>\utex_mathcharnum:D</code> | 997, 1253 |
| <code>\utex_binopenspacing:D</code> | 988 | <code>\utex_mathcharnumdef:D</code> | 998, 1254 |
| <code>\utex_binopspacing:D</code> | 989 | <code>\utex_mathcharslot:D</code> | 999 |
| <code>\utex_binordspacing:D</code> | 990 | <code>\utex_mathcode:D</code> | 1008, 1255 |
| <code>\utex_binpunctspacing:D</code> | 991 | <code>\utex_mathcodenum:D</code> | 1009, 1256 |
| <code>\utex_binrelspacing:D</code> | 992 | <code>\utex_nolimitsubfactor:D</code> | 1031 |
| <code>\utex_char:D</code> | 339, 975, 1218, 3903, 3911, 3965, 3999, 4001, 4002, 4004, 4018, 4019, 4030, 4031, 4057, 18734, 18763, 18920, 19142, 19144, 19145, 19148, 19149, 19150, 19151, 19152, 19153, 19155, 19156, 19166, 19169 | <code>\utex_nolimitsupfactor:D</code> | 1032 |
| <code>\utex_charcat:D</code> | 976, 6652, 6668 | <code>\utex_opbinspacing:D</code> | 1033 |
| <code>\utex_closebinspacing:D</code> | 1000 | <code>\utex_opclosespacing:D</code> | 1034 |
| <code>\utex_closeclosespacing:D</code> | 1001 | <code>\utex_openbinspacing:D</code> | 1035 |
| <code>\utex_closeinnerspacing:D</code> | 1002 | <code>\utex_openclosespacing:D</code> | 1036 |
| <code>\utex_closeopenspacing:D</code> | 1003 | <code>\utex_openinnerspacing:D</code> | 1037 |
| <code>\utex_closeopspacing:D</code> | 1004 | <code>\utex_openopenspacing:D</code> | 1038 |
| <code>\utex_closeordspacing:D</code> | 1005 | <code>\utex_openopspacing:D</code> | 1039 |
| <code>\utex_closepunctspacing:D</code> | 1006 | <code>\utex_openordspacing:D</code> | 1040 |
| <code>\utex_closerelspacing:D</code> | 1007 | <code>\utex_openpunctspacing:D</code> | 1041 |
| <code>\utex_connectoroverlapmin:D</code> | 1010 | <code>\utex_openrelspacing:D</code> | 1042 |
| <code>\utex_delcode:D</code> | 977, 1247 | <code>\utex_operatorsize:D</code> | 1043 |
| <code>\utex_delcodenum:D</code> | 978, 1248 | <code>\utex_opinnerspacing:D</code> | 1044 |
| <code>\utex_delimiter:D</code> | 979, 1249 | <code>\utex_opopenspacing:D</code> | 1045 |
| <code>\utex_delimiterover:D</code> | 980 | <code>\utex_opopspacing:D</code> | 1046 |
| <code>\utex_delimiterunder:D</code> | 981 | <code>\utex_opordspacing:D</code> | 1047 |
| <code>\utex_fractiondelsize:D</code> | 1011 | <code>\utex_oppunctspacing:D</code> | 1048 |
| <code>\utex_fractiondenomdown:D</code> | 1012 | <code>\utex_oprelspacing:D</code> | 1049 |
| <code>\utex_fractiondenomvgap:D</code> | 1013 | <code>\utex_ordbinspacing:D</code> | 1050 |
| <code>\utex_fractionnumup:D</code> | 1014 | <code>\utex_ordclosespacing:D</code> | 1051 |
| <code>\utex_fractionnumvgap:D</code> | 1015 | <code>\utex_ordinnerspacing:D</code> | 1052 |
| <code>\utex_fractionrule:D</code> | 1016 | <code>\utex_ordopenspacing:D</code> | 1053 |
| <code>\utex_hextensible:D</code> | 982 | <code>\utex_ordopspacing:D</code> | 1054 |
| <code>\utex_innerbinspacing:D</code> | 1017 | <code>\utex_ordordspacing:D</code> | 1055 |
| <code>\utex_innerclosespacing:D</code> | 1018 | <code>\utex_ordpunctspacing:D</code> | 1056 |
| <code>\utex_innerinnerspacing:D</code> | 1019 | <code>\utex_ordrelspacing:D</code> | 1057 |
| <code>\utex_inneropenspacing:D</code> | 1020 | <code>\utex_overbarkern:D</code> | 1058 |
| <code>\utex_inneropspacing:D</code> | 1021 | <code>\utex_overbarrule:D</code> | 1059 |
| <code>\utex_innerordspacing:D</code> | 1022 | <code>\utex_overbarvgap:D</code> | 1060 |
| <code>\utex_innerpunctspacing:D</code> | 1023 | <code>\utex_overdelimitervgap:D</code> | 1062 |
| <code>\utex_innerrelspacing:D</code> | 1024 | <code>\utex_overdelimitervgap:D</code> | 1061 |
| <code>\utex_limitabovebgap:D</code> | 1025 | <code>\utex_punctbinspacing:D</code> | 1063 |
| <code>\utex_limitabovekern:D</code> | 1026 | <code>\utex_punctclosespacing:D</code> | 1064 |
| <code>\utex_limitabovevgap:D</code> | 1027 | <code>\utex_punctinnerspacing:D</code> | 1065 |
| <code>\utex_limitbelowbgap:D</code> | 1028 | <code>\utex_punctopenspacing:D</code> | 1066 |
| <code>\utex_limitbelowkern:D</code> | 1029 | <code>\utex_punctopspacing:D</code> | 1067 |
| <code>\utex_limitbelowvgap:D</code> | 1030 | <code>\utex_punctordspacing:D</code> | 1068 |
| | | <code>\utex_punctpunctspacing:D</code> | 1069 |
| | | <code>\utex_punctrelspacing:D</code> | 1070 |
| | | <code>\utex_quad:D</code> | 1071 |
| | | <code>\utex_radical:D</code> | 1107 |

[illegible]

| | | | |
|------------------------------------|---------------------|---------------------------|------------------------|
| \xetex_charglyph:D | 807 | \xetex_XeTeXversion:D | 855, 4713, 5397, 17492 |
| \xetex_countfeatures:D | 808 | \XeTeXcharclass | 806 |
| \xetex_countglyphs:D | 809 | \XeTeXcharglyph | 807 |
| \xetex_countselectors:D | 810 | \XeTeXcountfeatures | 808 |
| \xetex_countvariations:D | 811 | \XeTeXcountglyphs | 809 |
| \xetex_dashbreakstate:D | 813 | \XeTeXcountselectors | 810 |
| \xetex_defaultencoding:D | 812 | \XeTeXcountvariations | 811 |
| \xetex_featurecode:D | 814 | \XeTeXdashbreakstate | 813 |
| \xetex_featurename:D | 815 | \XeTeXdefaultencoding | 812 |
| \xetex_findfeaturebyname:D | 816 | \XeTeXdelcode | 1246, 1247 |
| \xetex_findselectorbyname:D | 817 | \XeTeXdelcodenum | 1248 |
| \xetex_findvariationbyname:D | 818 | \XeTeXdelimiter | 1249 |
| \xetex_firstfontchar:D | 819 | \XeTeXfeaturecode | 814 |
| \xetex_fonttype:D | 820 | \XeTeXfeaturename | 815 |
| \xetex_generateactualtext:D | 821 | \XeTeXfindfeaturebyname | 816 |
| \xetex_glyph:D | 822 | \XeTeXfindselectorbyname | 817 |
| \xetex_glyphbounds:D | 823 | \XeTeXfindvariationbyname | 818 |
| \xetex_glyphindex:D | 824 | \XeTeXfirstfontchar | 819 |
| \xetex_glyphname:D | 825 | \XeTeXfonttype | 820 |
| \xetex_if_engine:TF | 17567, 17568, 17569 | \XeTeXgenerateactualtext | 821 |
| \xetex_if_engine_p: | 17566 | \XeTeXglyph | 822 |
| \xetex_inputencoding:D | 826 | \XeTeXglyphbounds | 823 |
| \xetex_inputnormalization:D | 827 | \XeTeXglyphindex | 824 |
| \xetex_interchartokenstate:D | 828 | \XeTeXglyphname | 825 |
| \xetex_interchartoks:D | 829 | \XeTeXinputencoding | 826 |
| \xetex_isdefaultselector:D | 830 | \XeTeXinputnormalization | 827 |
| \xetex_isexclusivefeature:D | 831 | \XeTeXinterchartokenstate | 828 |
| \xetex_lastfontchar:D | 832 | \XeTeXinterchartoks | 829 |
| \xetex_linebreaklocale:D | 834 | \XeTeXisdefaultselector | 830 |
| \xetex_linebreakpenalty:D | 835 | \XeTeXisexclusivefeature | 831 |
| \xetex_linebreakskip:D | 833 | \XeTeXlastfontchar | 832 |
| \xetex_OTcountfeatures:D | 836 | \XeTeXlinebreaklocale | 834 |
| \xetex_OTcountlanguages:D | 837 | \XeTeXlinebreakpenalty | 835 |
| \xetex_OTcountscripts:D | 838 | \XeTeXlinebreakskip | 833 |
| \xetex_OTfeaturetag:D | 839 | \XeTeXmathaccent | 1250 |
| \xetex_OTlanguagetag:D | 840 | \XeTeXmathchar | 1251 |
| \xetex_OTscripttag:D | 841 | \XeTeXmathchardef | 1252 |
| \xetex_pdffile:D | 842 | \XeTeXmathcharnum | 1253 |
| \xetex_pdfpagecount:D | 843 | \XeTeXmathcharnumdef | 1254 |
| \xetex_picfile:D | 844 | \XeTeXmathcode | 1255 |
| \xetex_selectorname:D | 845 | \XeTeXmathcodenum | 1256 |
| \xetex_suppressfontnotfounderror:D | 805, 1219 | \XeTeXOTcountfeatures | 836 |
| \xetex_tracingfonts:D | 846 | \XeTeXOTcountlanguages | 837 |
| \xetex_upwardsmode:D | 847 | \XeTeXOTcountscripts | 838 |
| \xetex_useglyphmetrics:D | 848 | \XeTeXOTfeaturetag | 839 |
| \xetex_variation:D | 849 | \XeTeXOTlanguagetag | 840 |
| \xetex_variationdefault:D | 850 | \XeTeXOTscripttag | 841 |
| \xetex_variationmax:D | 851 | \XeTeXpdffile | 842 |
| \xetex_variationmin:D | 852 | \XeTeXpdfpagecount | 843 |
| \xetex_variationname:D | 853 | \XeTeXpicfile | 844 |
| \xetex_XeTeXrevision:D | 854 | \XeTeXrevision | 854 |
| | | \XeTeXselectorname | 845 |
| | | \XeTeXtracingfonts | 846 |

| | | | |
|-------------------------------------|-----|------------------------------|------|
| <code>\XeTeXupwardsmode</code> | 847 | <code>\xkanjiskip</code> | 1151 |
| <code>\XeTeXuseglypmetrics</code> | 848 | <code>\xleaders</code> | 606 |
| <code>\XeTeXvariation</code> | 849 | <code>\xspaceskip</code> | 607 |
| <code>\XeTeXvariationdefault</code> | 850 | <code>\xspcode</code> | 1152 |
| <code>\XeTeXvariationmax</code> | 851 | | |
| <code>\XeTeXvariationmin</code> | 852 | Y | |
| <code>\XeTeXvariationname</code> | 853 | <code>\ybaselineshift</code> | 1153 |
| <code>\XeTeXversion</code> | 855 | <code>\year</code> | 608 |
| | | <code>\yoko</code> | 1154 |